

# Manual for pgf-PeriodicTable 1.0.0

Hugo Gomes  
hugo.parelho@gmail.com

10th October 2022

1																	18					
1	H																	He				
2	Li	Be															B	C	N	O	F	Ne
3	Na	Mg											Al	Si	P	S	Cl	Ar				
4	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr				
5	Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe				
6	Cs	Ba	lanthanoids		Hf	Ta	W	Re	Os	Ir	Pt	Au	Hg	Tl	Pb	Bi	Po	At	Rn			
7	Fr	Ra	actinoids		Rf	Db	Sg	Bh	Hs	Mt	Ds	Rg	Cn	Nh	Fl	Mc	Lv	Ts	Og			
6	La	Ce	Pr	Nd	Pm	Sm	Eu	Gd	Tb	Dy	Ho	Er	Tm	Yb	Lu							
7	Ac	Th	Pa	U	Np	Pu	Am	Cm	Bk	Cf	Es	Fm	Md	No	Lr							

`\pgfPT[show title=false,show legend=false]`

## Abstract

The purpose of this package is to provide the Periodic Table of Elements in a simple way. It relies on `pgf/TikZ` to offer a full or partial periodic table with a variety of options and displaying the desired data. The data available, from all the actual 118 elements, is: atomic number, element name, chemical symbol, relative atomic mass, standard relative atomic mass, radioactivity, atomic radius (empirical), covalent radius, ionic radius, first ionization energy, electronegativity (Pauling), electroaffinity, oxidation states, melting point (in Kelvin and Celsius degrees), boiling point (in Kelvin and Celsius degrees), electron distribution, electronic configuration (increasing  $n$  and increasing  $n + \ell$ ), density, specific heat capacity, thermal conductivity, lattice structure, lattice constants ( $a$ ,  $b$ ,  $c$  and  $c/a$  ratio), discovery year, discovery country and visible range spectral lines. It is possible to get the Periodic Table in six languages: English, French, German, Portuguese (from Portugal and from Brazil), Spanish and Italian.

# Contents

<b>Installation and usage</b>	<b>1</b>
<b>The data</b>	<b>2</b>
<b>The commands</b>	<b>3</b>
\pgfPT	3
\pgfPTstyle[options list]	4
\pgfPTresetstyle	5
\pgfPTbuildcell(nrows,ncolumns)[entries]	6
\pgfPTresetcell	6
\pgfPTbuildcellstyle{name}(nrows,ncolumns)[entries]	6
\pgfPTpreviewcell	6
\pgfPTpreviewcellstyle{name}	7
\pgfPTnewColorScheme{name}[color list]	7
\pgfPTnewZlist{name}	9
<b>Options for \pgfPT: creating a «Periodic Table»</b>	<b>10</b>
✧ Periodic Table options: keys, styles and <i>pseudo styles</i>	10
➤ General layout	10
↪ Z list	10
↪ cell width	11
↪ cell height	11
➤ cell size	11
↪ cell line width	12
↪ cell line color	12
↪ cell style	12
➤ cell	13
↪ font	13
↪ back color scheme	14
↪ back color	15
➤ csSolid	16
➤ csSoft	17
➤ csJmol	17
➤ csCPK	18
➤ csRasmol	18
➤ csRasmolNew	19
➤ csWikipedia	19
➤ csMNM	20
➤ csPS	20
➤ csRadio	21
➤ csBlocks	21
➤ background	22
↪ IUPAC	22
↪ show label LaAc	24
↪ label LaAc font	25
↪ capitalize element names	25
➤ Name	25
➤ name	25
↪ languages	26
↪ other languages font	27
↪ other languages color	27
➤ other lang	28
↪ show MNM line	28
↪ MNM line color	29

~>	MNM line width	29
➤	MNM	30
➤	Title and Legend	31
~>	show title	31
~>	title font	31
~>	title color	31
➤	title	32
~>	show legend	32
~>	legend acronyms	33
➤	legend box	33
~>	legend back color	34
~>	legend radio color	35
~>	legend CS color	36
~>	legend Z color	37
~>	show legend pins	37
➤	legend pins	38
~>	show extra legend	39
➤	extra legend	39
➤	legend	40
➤	Periods and Groups	41
~>	show period numbers	41
~>	show group numbers	42
~>	period label color	42
~>	group label color	43
~>	label font	43
➤	per	43
➤	gr	44
➤	per+gr	44
➤	Blocks and Families	44
~>	show blocks	44
~>	blocks font	46
~>	s block color	46
~>	s block font color	46
~>	s block line width	46
~>	p block color	46
~>	p block font color	46
~>	p block line width	47
~>	d block color	47
~>	d block font color	47
~>	d block line width	47
~>	f block color	47
~>	f block font color	47
~>	f block line width	47
➤	blocks font color	47
➤	blocks line width	47
➤	blocks	48
~>	show families	49
~>	families font	50
~>	r family color	51
~>	r family font color	51
~>	r family line width	51
~>	tm family color	51
~>	tm family font color	51
~>	tm family line width	51
~>	itm family color	51

~> itm family font color	51
~> itm family line width	51
➤ families font color	52
➤ families line width	52
➤ families	53
➤ Periodic variations	54
~> show periodic variations	54
~> varR color	55
~> varR font	56
~> varR font color	56
~> varEi color	56
~> varEi font	56
~> varEi font color	57
~> vareaff color	57
~> vareaff font	57
~> vareaff font color	57
➤ var font	57
➤ var color	57
➤ varR	58
➤ varEi	58
➤ vareaff	59
➤ Dark mode	60
➤ dark mode	60
➤ Exercise layout	61
~> only cells	61
~> only cells plus Z	61
~> only cells with periods and group numbers	62
~> only cells with periods and group numbers plus Z	63
~> Z exercise list	63
~> exercise list in capitals	64
~> exercise list color	64
~> exercise list font	64
➤ cells+Z	65
➤ cells+p+g	65
➤ cells+p+g+Z	66
➤ exnocaps	66
➤ exColor	66
➤ exFont	67
➤ ex	67
✘ Cell contents options: keys, styles and <i>pseudo styles</i>	67
➤ The atomic number	67
~> Z bgcolor	67
~> Z color	68
~> Z font	68
~> Z use box width	68
~> Z align	68
~> Z padding	69
➤ Z box	69
➤ Z	69
➤ The chemical symbol	70
~> CS solid	70
~> CS liquid	70
~> CS gas	71
~> CS synt	71
➤ CS all	71

~> CS font . . . . .	72
~> CS render mode . . . . .	72
~> CS outline color . . . . .	73
~> CS outline width . . . . .	73
➤ CS . . . . .	74
➤ The atomic weight . . . . .	74
~> Ar color . . . . .	74
~> Ar font . . . . .	74
~> Ar label . . . . .	75
~> Ar precision . . . . .	75
➤ Ar . . . . .	76
➤ The lattice structure . . . . .	77
~> ls . . . . .	77
~> ls color . . . . .	77
~> ls font . . . . .	78
~> ls align . . . . .	78
➤ The discovery year . . . . .	78
~> DiscY color . . . . .	78
~> DiscY font . . . . .	79
~> DiscY BC scale . . . . .	79
➤ <i>The electron distribution</i> . . . . .	79
~> eDist color . . . . .	80
~> eDist font . . . . .	80
~> eDist sep . . . . .	80
➤ <i>The other contents</i> . . . . .	81
~> <content name> color . . . . .	81
~> <content name> font . . . . .	82
➤ cell font . . . . .	82
➤ cell color . . . . .	82
~> E precision . . . . .	83
~> T precision . . . . .	84
~> d precision . . . . .	86
~> Cp precision . . . . .	88
~> kT precision . . . . .	89
~> ls precision . . . . .	91
<b>Designing cells with <code>\pgfPTbuildcell</code></b> . . . . .	<b>93</b>
✕ The cell contents . . . . .	94
✕ Built-in cell styles . . . . .	96
<b>Designing color schemes</b> . . . . .	<b>99</b>
✕ Designing a color scheme with <code>\pgfPTnewColorScheme</code> . . . . .	99
✕ Designing a color scheme with <code>pgfPTcolorSchemes.html</code> . . . . .	99
<b>A few more examples</b> . . . . .	<b>103</b>
<b>Index</b> . . . . .	<b>109</b>

## Installation and usage

`pgf-PeriodicTable` is placed under the terms of the L<sup>A</sup>T<sub>E</sub>X Project Public License, version 1.3 or later (<http://www.latex-project.org/lppl.txt>). `pgf-PeriodicTable` loads and only requires the `TikZ` package.

You need to put the package files (`pgf-PeriodicTable.sty` & *friends*) in a location where PDF<sup>L</sup>A<sub>T</sub>E<sub>X</sub> can find them. According to the TDS conventions this may be a subdirectory named `tex/latex/pgf-PeriodicTable/` or `tex/latex/misc/` in your (site specific) installation tree (insert your appropriate directory delimiter instead of `/`, if needed).

If you are using PDF<sup>L</sup>A<sub>T</sub>E<sub>X</sub>, you can just simply include the style file without any option via the `\usepackage` command, `\usepackage{pgf-PeriodicTable}`

It can also be loaded with *one option* to select the desired language:  
`\usepackage[language flag]{pgf-PeriodicTable}`

*The language flags available are:*

- ✓ **en** for English (default),
- ✓ **fr** for French,
- ✓ **de** for German,
- ✓ **pt** for Portuguese (Portugal),
- ✓ **br** for Portuguese (Brazil),
- ✓ **es** for Spanish and
- ✓ **it** for Italian.

## The data

The data available in [pgf-PeriodicTable](#) was mainly compiled with selected and filtered data from Wikipedia, taken from November 2021 to July 2022.

acronym	description	unit	remarks (compiled from @date)
Ar	Relative Atomic Mass		(Wikidata @09/jan/2022)
Arstar	Standard Relative Atomic Mass		STANDARD ATOMIC WEIGHTS 2021, Commission on Isotopic Abundances and Atomic Weights, © <b>CIAAW, 2007–2022</b> ( <a href="https://ciaaw.org/impressum.htm">https://ciaaw.org/impressum.htm</a> )
radio	Radioactivity		(gperiodic-3.0.3, Dec 26 2018)
R	Atomic Radius	pm	Calculated (Wikidata @04/jul/2022)
Rcov	Covalente Radius	pm	Single bond, Wikidata @04/jul/2022)
Rion	Ionic Radius	pm	(Wikidata @04/jul/2022)
Ei	First Ionization Energy	$\text{kJ} \cdot \text{mol}^{-1}$	(Wikidata @04/jul/2022)
eneg	Electronegativity (Pauling)		(Wikidata @04/jul/2022)
eaff	Electroaffinity	$\text{kJ} \cdot \text{mol}^{-1}$	(Wikidata @04/jul/2022)
O	Oxidation States		(Wikidata @09/jan/2022)
Tmelt	Melting Point	K	at standard pressure (Wikidata @21/dez/2021)
TmeltC	Melting Point	°C	at standard pressure (Wikidata @21/dez/2021)
Tboil	Boiling Point	K	at standard pressure (Wikidata @21/dez/2021)
TboilC	Boiling Point	°C	at standard pressure (Wikidata @21/dez/2021)
eDist	Electron Distribution		(Wikidata @01/nov/2021)
eConfign	Electronic Configuration (increasing n)		(Wikidata @01/nov/2021)
eConfign	Electronic Configuration (increasing $n + \ell$ )		(Wikidata @01/nov/2021)
d	Density	$\text{g} \cdot \text{dm}^{-3}$	physical state at 25°C, 1 atm (Wikidata @01/nov/2021)
Cp	Specific heat capacity	$\text{J} \cdot \text{mol}^{-1} \cdot \text{K}^{-1}$	at 25°C and 100 kPa (Wikidata @20/nov/2021)
kT	Thermal Conductivity	$\text{W} \cdot \text{m}^{-1} \cdot \text{K}^{-1}$	at 25°C (Wikidata @21/nov/2021)
Is	Lattice Structure		(Wikidata @20/dez/2021 and <a href="#">University of Bielefeld</a> )
Isa	Lattice constant: a	pm	(University of Bielefeld @21/dez/2021)
Isb	Lattice constant: b	pm	(University of Bielefeld @21/dez/2021)
Isb	Lattice constant: c	pm	(University of Bielefeld @21/dez/2021)
Isca	Lattice c/a ratio		Calculated from available data and rounded to two digits
DiscY	Discover Year		(Wikidata @22/dez/2021)
DiscC	Discover Country		(Wikidata @22/dez/2021)
spectra	Visible range spectral lines		Elements spectrum made with <code>\pgfspectra</code> . See the <a href="#">pgf-spectra</a> manual for more details

The utilization of the *acronyms* will be explained in [Designing cells with \pgfPTbuildcell](#).

## The commands

The commands to achieve the Periodic Table of Elements are:

- `\pgfPT` or `\pgfPT[options list]` – draws a full or partial graphical Periodic Table controlled by the optional keys.
- `\pgfPTstyle[options list]` – sets the global style for the Periodic Table.
- `\pgfPTresetstyle` – resets the style for the Periodic Table with the default values.
- `\pgfPTbuildcell(nrows,ncolumns)[entries]` – builds the contents of each cell in the Periodic Table.
- `\pgfPTresetcell` – resets the cell to its default layout.
- `\pgfPTbuildcellstyle{name}(nrows,ncolumns)[entries]` – builds the contents of each cell in the Periodic Table and stores it in a named style.
- `\pgfPTpreviewcell` or `\pgfPTpreviewcell[scale factor]` – preview the last unnamed built cell with an optional scale factor. If no cells have yet been built, the default cell is shown.
- `\pgfPTpreviewcellstyle{name}` or `\pgfPTpreviewcellstyle[scale factor]{name}` – preview the named builded cell with an optional scale factor.
- `\pgfPTnewcolorscheme[trailing color]{name}{color list}` – makes a color scheme to fill the cells along the Periodic Table.
- `\pgfPTnewZlist{name}` – create a user defined atomic numbers (Z) named list.

### ► Utilization of `\pgfPT`

Use this command to draw the Periodic Table of Elements in the language selected at package inclusion (`\usepackage[language flag]{pgf-PeriodicTable}`):

`\pgfPT`

Periodic Table of Elements

1																	18	
1	H																	He
	hydrogen																	helium
	1.008																	4.0026
2	3	4											13	14	15	16	17	18
	Lj	Be											B	C	N	O	F	Ne
	lithium	beryllium											boron	carbon	nitrogen	oxygen	fluorine	neon
	6.94	9.0122											10.81	12.011	14.007	15.999	18.998	20.18
3	11	12											13	14	15	16	17	18
	Na	Mg											Al	Si	P	S	Cl	Ar
	sodium	magnesium											aluminium	silicon	phosphorus	sulfur	chlorine	argon
	22.99	24.305											26.982	28.085	30.974	32.06	35.45	39.95
4	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr
	potassium	calcium	scandium	titanium	vanadium	chromium	manganese	iron	cobalt	nickel	copper	zinc	gallium	germanium	arsenic	selenium	bromine	krypton
	39.098	40.078	44.956	47.867	50.942	51.996	54.938	55.845	58.933	58.693	63.546	65.38	69.723	72.63	74.922	78.971	79.904	83.798
5	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54
	Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe
	rubidium	strontium	yttrium	zirconium	niobium	molybdenum	technetium	ruthenium	rhodium	palladium	silver	cadmium	indium	tin	antimony	tellurium	iodine	xenon
	85.468	87.62	88.906	91.224	92.906	95.95	98	101.07	102.91	106.42	107.87	112.41	114.82	118.71	127.6	126.9	126.9	131.29
6	55	56	57-71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86
	Cs	Ba	lanthanoids	Hf	Ta	W	Re	Os	Ir	Pt	Au	Hg	Tl	Pb	Bi	Po	At	Rn
	caesium	barium		hafnium	tantalum	tungsten	rhenium	osmium	iridium	platinum	gold	mercury	thallium	lead	bismuth	polonium	astatine	radon
	132.91	137.33		178.49	180.95	183.84	186.21	190.23	192.22	195.08	196.97	200.59	204.38	207.2	208.98	(209)	(210)	(222)
7	87	88	89-103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118
	Fr	Ra	actinoids	Rf	Db	Sg	Bh	Hs	Mt	Ds	Rg	Cn	Nh	Fl	Mc	Lv	Ts	Og
	francium	radium		rutherfordium	bohrium	seaborgium	bohrium	hassium	meitnerium	darmstadtium	roentgenium	copernicium	nihonium	flerovium	moscovium	livermorium	tennessine	oganeson
	[223]	[226]		[267]	[268]	[269]	[270]	[270]	[278]	[281]	[282]	[285]	[286]	[289]	[290]	[293]	[294]	[294]
6	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71			
	La	Ce	Pr	Nd	Pm	Sm	Eu	Gd	Tb	Dy	Ho	Er	Tm	Yb	Lu			
	lanthanum	cerium	praseodymium	neodymium	promethium	samarium	europium	gadolinium	terbium	dysprosium	holmium	erbium	thulium	ytterbium	lutetium			
	138.91	140.12	140.91	144.24	[145]	150.36	151.96	157.25	158.93	162.5	164.93	167.26	168.93	173.05	174.97			
7	89	90	91	92	93	94	95	96	97	98	99	100	101	102	103			
	Ac	Th	Pa	U	Np	Pu	Am	Cm	Bk	Cf	Es	Fm	Md	No	Lr			
	actinium	thorium	protactinium	uranium	neptunium	plutonium	americium	curium	berkelium	californium	einsteinium	fermium	mendelevium	nobelium	lawrencium			
	[227]	232.04	231.04	238.03	[237]	[244]	[243]	[247]	[247]	[251]	[252]	[257]	[258]	[259]	[260]			

This command can also be used with options – as described in section [Options for \pgfPT: creating a «Periodic Table»](#) – to modify, for instance, the font of the Periodic Table or the colors of the cells:

```
\pgfPT[font=pnc,back color scheme=MNM]
```

### Periodic Table of Elements

### ► Utilization of \pgfPTstyle[options list]

This command globally sets a style for the Periodic Table:

```
\pgfPTstyle[font=ptm,IUPAC=false,show title=false]
\pgfPT
```

It is possible to locally override the *global style* defined:

```
\pgfPT[show title]
```

Periodic Table of Elements

The periodic table displays elements from Hydrogen (H) to Oganesson (Og). A legend box indicates the states of matter for various elements: H (gas), He (gas), Li (solid), Be (solid), B (solid), C (solid), N (gas), O (gas), F (gas), Ne (gas). The legend also lists: Ra (solid), N (solid), Ar (solid), and Ar (solid).

► Utilization of `\pgfPTresetstyle`

This command resets the style used in the Periodic Table to default values:

```
\pgfPTresetstyle
```

```
\pgfPT
```

Periodic Table of Elements

The periodic table displays elements from Hydrogen (H) to Oganesson (Og). A legend box indicates the states of matter for various elements: H (gas), He (gas), Li (solid), Be (solid), B (solid), C (solid), N (gas), O (gas), F (gas), Ne (gas). The legend also lists: Ra (solid), N (solid), Ar (solid), and Ar (solid).

### ► Utilization of `\pgfPTbuildcell(nrows,ncolumns)[entries]`

With `\pgfPTbuildcell` it is possible to customize the *elementar* cell of the Periodic Table. Each cell is built on the given *number of rows* and *number of columns*. After that, each *entry* is constructed according to the structure `row;column;what` or `initial row-final row;initial column-final column;what`.

- ✓ The first *syntax* – `row;column;what` – puts «*what*» in the «*row*» row and in the «*column*» column with the height of one row and the width of one column:
  - for example, `1;1;Z` puts the atomic number *Z* in row **1** and column **1**, which actually corresponds to a box anchored to the top left corner of the cell and that goes below and to the right of that corner.
- ✓ The second *syntax* – `initial row-final row;initial column-final column;what` – puts «*what*» from «*initial row*» to «*final row*» with the height of `final row – initial row + 1` and from «*initial column*» to «*final column*» with the width of `final column – initial column + 1`. It is important to keep in mind that when using this syntax the *row* and *column* could have any value between **1** and **number of rows** and **number of columns**, respectively.
  - for example, `1;1-2.1;Z` puts the atomic number *Z* in row **1** with the height of one row and from column **1** to *column 2.1*, with the width of `2.1 × column`. Note that in this example the two *syntaxes* are mixed up.

The **default cell** of the Periodic Table is constructed with the command:

```
\pgfPTbuildcell(5,3)% 5 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-2.5;CS),(4;1-3;name),(5;1-3;Ar)]
```

### ► Utilization of `\pgfPTresetcell`

The `\pgfPTresetcell` resets the cell to its default layout.

### ► Utilization of `\pgfPTbuildcellstyle{name}(nrows,ncol...)[entr...]`

The `\pgfPTbuildcellstyle` command works like `\pgfPTbuildcell`, but stores the cell style under the *name* provided. It is only used when called via the *cell style* passed as an option to `\pgfPT`. Otherwise it remains unavailable, unlike the `\pgfPTbuildcell` command which immediately affects the cells of the Periodic Table.

### ► Utilization of `\pgfPTpreviewcell`

The main purpose of this command is to show the built cell for *debugging*. With `\pgfPTpreviewcell` you can preview the last unnamed built cell with an optional *scale factor*. If no cells have yet been built, the default cell is shown.

```
\pgfPTpreviewcell
```

#### Using the last cell built

The build command:

```
\pgfPTbuildcell(5,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;Ar)]
```

	1	2	3
1	Z		radio
2			
3		CS	
4			name
5			Ar

scale 1:1

```
\pgfPTbuildcell(8,3)% 8 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4-5;1-3;name),
(6;1-3;spectra),(7;1-3;DiscC),(8;1-3;DiscY)]
\pgfPTpreviewcell[1.8]
```

### Using the last cell built

The build command:

```
\pgfPTbuildcell(8,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4-5;1-3;name),(6;1-3;spectra),(7;1-3;DiscC),(8;1-3;DiscY)]
```

	1	2	3
1	Z		radio
2		CS	
3			
4	name		
5			
6	spectra		
7	DiscC		
8	DiscY		

scale 1.8:1

### ► Utilization of `\pgfPTpreviewcellstyle{name}`

This previews a *named* cell, again with the optional *scale factor*.

```
\pgfPTpreviewcellstyle{myname}
```

User style **myname** doesn't exist!

```
\pgfPTbuilcellstyle{myname}(5,3)% 5 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;Ar*)]
\pgfPTpreviewcellstyle[2]{myname}
```

User style **myname**

The build command:

```
\pgfPTbuildcell(5,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;Ar*)]
```

	1	2	3
1	Z		radio
2		CS	
3			
4	name		
5	Arstar		

scale 2:1


### ► Utilization of `\pgfPTnewColorScheme{name}[color list]`

Use this command to create a *color scheme* for cells in the Periodic Table. It has two mandatory arguments – *name* and *color list* – and an optional argument – *trailing color*.

The *name* is used to identify the *color scheme*. The *color list* is a comma-separated list of red, green and blue values written as *r/g/b*, defined in ascending order of *Z* and starting at *Z=1*. The optional argument *trailing color* is appended to the end of the list and is used for all cells starting from this point on. It also has the form *r/g/b* and its default value is 1/1/1 (white).


```
\pgfPTnewColorScheme{myname}{.5/.5/.5,1/0/0,0/1/0,0/0/1}
\pgfPT[back color scheme=myname]
```

Periodic Table of Elements



```
\pgfPTnewColorScheme[.25/.25/.25]{myname}{.5/.5/.5,1/0/0,0/1/0,0/0/1}
\pgfPTresetcell
\pgfPT[back color scheme=myname,name color=white, Ar color=white,legend back color=black!30]
```


Periodic Table of Elements



There are a few *color schemes* predefined:

- ✓ **default**, the default built-in color scheme, which is loaded if no value is passed to the **back color scheme** key.
- ✓ **Soft**, a soft color pattern for cells, differentiating metals, non metals, semimetals, lanthanides and actinides.
- ✓ **Jmol**, a color scheme based upon **Jmol: an open-source Java viewer for chemical structures in 3D**.
- ✓ **CPK**, a color scheme that is based upon the colors of the popular plastic spacefilling models which were developed by Corey, Pauling and later improved by Kultun.
- ✓ **Rasmol** and **RasmolNew**, two color schemes based upon the computer program **RasMol**.
- ✓ **Wikipedia**, a color scheme built on the Periodic Table of Elements available at **Wikipedia**.
- ✓ **MNM**, a color pattern which distinguishes between **Metals**, semimetals and **Non Metals**.
- ✓ **PS**, a color scheme depicting the **Physical State** at room temperature.
- ✓ **Radio**, a two color color scheme showing the radioactivity of the elements.
- ✓ **Blocks**, a four colored color scheme showing the *s*, *p*, *d* and *f* blocks of the Periodic Table.

Writing a color scheme can be painstaking work, so a *script* is provided for that:




[pgfPTcolorSchemes.html](http://pgfPTcolorSchemes.html)

### ► Utilization of `\pgfPTnewZlist{name}`

This command makes a user defined atomic numbers' list with the provided **name**. The list can be anything that the `\foreach` loop, defined in the `TikZ` package, can understand. For more information on how to use `\foreach` loop refer to the section *Repeating Things: The Foreach Statement* in the `pgfmanual`.

```
\pgfPTnewZlist{myZlist}{1,...,57,72,80,81,...,85}
\pgfPT[Z list=myZlist,IUPAC=false]
```



## Options for `\pgfPT`: creating a «Periodic Table»

For the commands `\pgfPT` and `\pgfPTstyle` there are a set of options available to draw the Periodic Table or any portion of the Periodic Table, as described below.

The list of options is a comma separated list of any of the following elements:

- ↪ a 'key' or a 'key=value' pair,
- a 'style' or a 'style=value' pair,
- a *pseudo style* with a proper syntax: 'style={key 1=value 1, key 2=value 2, ... , key n=value n}', where none of the 'keys' are mandatory.

The options *can be divided* in two subsets, one that affects the *appearance* of the *entire* Periodic Table, the other that concerns the *contents* of each cell of the Periodic Table.

### ✂ Periodic Table options: keys, styles and *pseudo styles*

The following options and styles are used to *control* the Periodic Table *as a whole* in various aspects, such as the **cell width** or **cell height**, which elements are displayed (**Z list**), whether the title or legend are shown – **show title** or **show legend** – among others.

#### ➡ General layout

##### Z list

default: *all*

Set's the list of the elements to display in the Periodic Table. It could be a **name** or a **comma separated** list of atomic numbers, which in turn supports *the dots notation* as explained in the section *Repeating Things: The Foreach Statement* in the `pgfmanual`.

```
\pgfPT[Z list={1,...,36}]
```

Periodic Table of Elements

1																	18					
1	H																	He				
	hydrogen																	helium				
	1.008																	4.0026				
2	Li	Be															B	C	N	O	F	Ne
	lithium	beryllium															boron	carbon	nitrogen	oxygen	fluorine	neon
	6.94	9.0122															10.81	12.011	14.007	15.999	18.998	20.18
3	Na	Mg												Al	Si	P	S	Cl	Ar			
	sodium	magnesium												aluminium	silicon	phosphorus	sulfur	chlorine	argon			
	22.99	24.305												26.982	28.085	30.974	32.06	35.45	39.95			
4	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr				
	potassium	calcium	scandium	titanium	vanadium	chromium	manganese	iron	cobalt	nickel	copper	zinc	gallium	germanium	arsenic	selenium	bromine	krypton				
	39.098	40.078	44.956	47.867	50.942	51.996	54.938	55.845	58.933	58.693	63.546	65.38	69.723	72.63	74.922	78.971	79.904	83.798				

The possible **name** is one of the following:

##### ✓ built-in:

- ▷ 'all' is equivalent to `Z list={1,...,118}`, *i.e.*, all known elements.
- ▷ 's', 'p', 'd' or 'f', for the elements in the corresponding blocks.
- ▷ 'sp', 'spd', for the elements resulting from merging the corresponding blocks.
- ▷ 'lanthanoids' or simply 'La', for lanthanoids †.
- ▷ 'actinoids' or 'Ac', for actinoids †.
- ▷ 'G1\*', 'G1', ..., 'G18', which are used, respectively, for the elements of *group 1 without hydrogen*, *group 1*, ..., *group 18*.
- ▷ 'P1', ..., 'P7', 'P6\*', 'P7\*', which are used, respectively, for the elements of the *1<sup>st</sup> period*, ..., *7<sup>th</sup> period*, *6<sup>th</sup> period and lanthanoids* †, *7<sup>th</sup> period and actinoids* †.

† Depending on the value of the *IUPAC key*, the Lanthanum or Actinium are or are not included.

✓ any **user defined** name via `\pgfPTnewZlist{name}{list}`

**cell width**

default: 34pt

Sets the width of each base cell of the Periodic Table.

```
\pgfPT[Z list={1,...,36},cell width=40pt]
```

Periodic Table of Elements

**cell height**

default: 38.25pt

Sets the height of each base cell of the Periodic Table.

```
\pgfPT[Z list={1,...,36},cell height=50pt]
```

Periodic Table of Elements

**cell size**

default: 38.25pt

Style to set both the width and the height of each base cell of the Periodic Table.

```
\pgfPT[Z list={1,...,36},cell size=40pt]
```

Periodic Table of Elements


**cell line width**

default: 0.4pt

Sets the width of the line surrounding the base cell of the Periodic Table.

```
\pgfPT[Z list={1,...,36},cell line width=2pt]
```

Periodic Table of Elements




**cell line color**

default: black

Sets the color of the line surrounding the base cell of the Periodic Table.

```
\pgfPT[Z list={1,...,36},cell line color=red]
```

Periodic Table of Elements




**cell style**

default: {}

Loads a named cell style, built via \pgfPTbuildcellstyle, to use as a layout for each cell of the Periodic Table.

```
\pgfPTbuilcellstyle{myname}(5,3)% 5 rows by 3 columns
[(1;1-2;Z),(1;3;ls),(2-3;1.5-2.5;CS),(4;1-3;name),(5;1-3;eConfignl)]
\pgfPT[Z list={1,...,36},cell style=myname]
```

Periodic Table of Elements




**cell** default:  $\{w=34pt,h=38.25pt,lw=.4pt,lc=black\}$

*Pseudo style* to set the cell **w**idth, the cell **h**eight, the cell **s**ize, the cell **l**ine **w**idth, the cell **l**ine **c**olor and/or the cell **s**tyle. None of the **keys** – **w**, **h**, **s**, **lw**, **lc** and **style** – are mandatory.

**USAGE:** `cell={w=<length>,h=<length>,s=<length>,lw=<length>,lc=<color>,style=<name>}`

`\pgfPT[Z list={1,...,36},cell={w=40pt,h=50pt,lw=.6pt,lc=blue}]`

Periodic Table of Elements




**font** default: *phv*

Sets the font family, via the proper  $\text{\LaTeX}$  font name, to use in the Periodic Table. The *default* font is *phv*, i.e., the Helvetica font. The value of the **font** key can be any  $\text{\LaTeX}$  font name known to the local  $\text{\LaTeX}$  installation.

See  $\text{\LaTeX}$  font names below for further details.


`\pgfPT[Z list={1,...,36},font=ptm]`

Periodic Table of Elements



`\pgfPT[Z list={1,...,36},font=RobotoSlab-TLF]`

Periodic Table of Elements



**L<sup>A</sup>T<sub>E</sub>X font names:**

✓ The L<sup>A</sup>T<sub>E</sub>X font names commonly available in L<sup>A</sup>T<sub>E</sub>X distributions are:

**- Serif fonts**

- ▷ cmr – Computer Modern Roman
- ▷ lmr – Latin Modern Roman
- ▷ pbk – Bookman
- ▷ bch – Charter
- ▷ pnc – New Century Schoolbook
- ▷ ppl – Palatino
- ▷ ptm – Times

**- Sans Serif fonts**

- ▷ cmss – Computer Modern Sans Serif
- ▷ lmss – Latin Modern Sans Serif
- ▷ pag – Avant Garde
- ▷ phv – Helvetica

✓ There are other fonts available to L<sup>A</sup>T<sub>E</sub>X that require installation of the corresponding packages:

- ▷ the **roboto** package provides the following fonts:
  - Roboto-TLF – Roboto tabular lining
  - Roboto-LF – Roboto proportional lining
  - Roboto-OsF – Roboto proportional oldstyle
  - Roboto-TosF – Roboto tabular oldstyle
  - RobotoSlab-TLF – RobotoSlab proportional lining
  - RobotoSlab-OsF – RobotoSlab proportional oldstyle
  - RobotoSlab-TOsF – RobotoSlab tabular oldstyle
  - RobotoMono-TLF – RobotoMono proportional lining
- ▷ the **frursive** package provides the *frc* – French Cursive font.
- ▷ the **miama** package provides the *fmr* – Miama Nueva font.
- ▷ ...

For more information about fonts visit the [TUG Font Catalogue](#)

**back color scheme**

default: *default*

Sets a **named** back color scheme for the Periodic Table.

```
\pgfPT[back color scheme=Soft]
```

Periodic Table of Elements

The possible name is one of the following:

✓ **built-in:**

- ▷ 'Soft', a soft color scheme that distinguishes metal, non metals, silicon and germanium, lanthanoids and actinoids.
- ▷ 'Jmol', is the color scheme used in the computer software [Jmol](#): an open-source Java viewer for chemical structures in 3D.
- ▷ 'CPK', is the color scheme of the popular color convention for distinguishing atoms of different chemical elements in molecular models. The scheme is named after the CPK molecular models designed by chemists Robert Corey and Linus Pauling, and improved by Walter Koltun.
- ▷ 'Rasmol', is the color scheme used in the computer software [RasMol](#), a program for molecular graphics visualization originally developed by Roger Sayle.
- ▷ 'RasmolNew', is a color scheme used in RasMol with revision of CPK colors made by C. Chigbo (RasMol 2.7.3).
- ▷ 'Wikipedia', is the color scheme based on the [Wikipedia Periodic Table of Elements](#).
- ▷ 'MNM', is designed to show **M**etals and **N**on **M**etals in two different colors, showing also the semi-metals in a third color.
- ▷ 'PS', is designed to show the **P**hysical **S**tate of the elements at normal temperature and pressure (NTP) in different colors.
- ▷ 'Radio', is designed to show the **R**adioactive elements in one color and the non radioactive elements in another color.
- ▷ 'Blocks', for showing the elements in each block of the Periodic Table with the same color.
- ▷ 'solid', to show the background of each cell of the Periodic Table with the same color specified by the key 'back color'.

✓ any **user defined** name via `\pgfPTnewColorScheme{name}[color list]`

**back color**

default: *white*

Sets the background of each cell of the Periodic Table. It only takes effect if the **back color scheme** key is set to **solid**

```
\pgfPT[Z list={1,...,36},back color=black!15]
```

Periodic Table of Elements

The image shows a standard periodic table where every cell has a light gray background. The elements are arranged in their usual order, with atomic numbers and names. A legend box is present, showing symbols for Ra, Cs, N, and Ar, with labels for Atomic Number, Radioactive, Chemical Symbol, Name, and Relative Atomic Mass. The legend also includes a color key for 'solid', 'liquid', 'gaseous', and 'synthetic'.

```
\pgfPT[Z list={1,...,36},back color scheme=solid,back color=black!15]
```

Periodic Table of Elements

The image shows a standard periodic table where every cell has a solid black background. The elements are arranged in their usual order, with atomic numbers and names. A legend box is present, showing symbols for Ra, Cs, N, and Ar, with labels for Atomic Number, Radioactive, Chemical Symbol, Name, and Relative Atomic Mass. The legend also includes a color key for 'solid', 'liquid', 'gaseous', and 'synthetic'.

It is possible to set the *back color scheme* key with the built-in names using the following styles:

**csSolid** default: *white*  
 A style equivalent to `back color scheme=solid,back color=#1`

```
\pgfPT[csSolid]
```

Periodic Table of Elements

The image shows a standard periodic table with a white background and black text. A legend box in the upper left corner defines the element states: solid (black), liquid (red), gaseous (blue), and synthetic (yellow). It also lists the symbols for Atomic Number (Z), Radioactive (Ra), Chemical Symbol (Cs), Name (N), and Relative Atomic Mass (Ar).

```
\pgfPT[csSolid=black!15]
```

Periodic Table of Elements

This image shows the same periodic table as above, but with a light gray background. The text remains black. The legend and element data are identical to the first table.

**csSoft**

*no value*

A style equivalent to `back color scheme=Soft`

\pgfPT[csSoft]

Periodic Table of Elements

**csJmol**

*no value*

A style equivalent to `back color scheme=Jmol`

\pgfPT[csJmol]


Periodic Table of Elements

**csCPK**

*no value*

A style equivalent to `back color scheme=CPK`

```
\pgfPT[csCPK]
```




**csRasmol**

*no value*

A style equivalent to `back color scheme=Rasmol`

```
\pgfPT[csRasmol]
```




**csRasmolNew**

*no value*

A style equivalent to `back color scheme=RasmolNew`

```
\pgfPT[csRasmolNew]
```

Periodic Table of Elements




**csWikipedia**

*no value*

A style equivalent to `back color scheme=Wikipedia`

```
\pgfPT[csWikipedia]
```

Periodic Table of Elements



**csMNM**

*no value*

A style equivalent to `back color scheme=MNM`

\pgfPT[csMNM]

Periodic Table of Elements

The periodic table displays elements from Hydrogen (1) to Oganesson (118) in the main body, and Lanthanum (57) to Lawrencium (103) in the f-block below. Each element cell contains its symbol, name, and atomic weight. The color coding is as follows: s-block (yellow), p-block (light blue), d-block (light green), and f-block (light purple). A legend box in the top left corner defines the color coding: solid (yellow), liquid (light blue), gaseous (light green), and synthetic (light purple).

**csPS**

*no value*

A style equivalent to `back color scheme=PS`

\pgfPT[csPS]

Periodic Table of Elements

The periodic table displays elements from Hydrogen (1) to Oganesson (118) in the main body, and Lanthanum (57) to Lawrencium (103) in the f-block below. Each element cell contains its symbol, name, and atomic weight. The color coding is as follows: s-block (yellow), p-block (light blue), d-block (light green), and f-block (light purple). A legend box in the top left corner defines the color coding: solid (yellow), liquid (light blue), gaseous (light green), and synthetic (light purple).

**csRadio**

*no value*

A style equivalent to `back color scheme=Radio`

```
\pgfPT[csRadio]
```

Periodic Table of Elements

**csBlocks**

*no value*

A style equivalent to `back color scheme=Blocks`

```
\pgfPT[csBlocks]
```


Periodic Table of Elements

**background**

default: {}


A style to set the background of the Periodic Table, built with any of the TikZ keys that can be applied to a path construction.

```
\pgfPT[background={draw=red,line width=2pt,fill=red!10}]
```



```
\usetikzlibrary{shadows}
```

```
\pgfPT[background={left color=red!10,right color=green!10,postaction={drop shadow={left color=red!10,right color=green!10}}}]
```



**IUPAC**

default: true

When set to true draws the periodic table with *lanthanum* and *actinium* appended to block f and the labels *lanthanoids* and *actinoids* are placed at group 3, substituting *lanthanum* and *actinium*. When **IUPAC** is set to false, *lanthanum* and *actinium* are shown in group 3 and the labels *lanthanoids* and *actinoids* are placed near the *f* block (if the key **show label LaAc** is set to true).

\pgfPT

Periodic Table of Elements

1																	18		
1	H																	He	
2	Li	Be											B	C	N	O	F	Ne	
3	Na	Mg											Al	Si	P	S	Cl	Ar	
4	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr	
5	Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe	
6	Cs	Ba	lanthanoids		Hf	Ta	W	Re	Os	Ir	Pt	Au	Hg	Tl	Pb	Bi	Po	At	Rn
7	Fr	Ra	actinoids		Rf	Db	Sg	Bh	Hs	Mt	Ds	Rg	Cn	Nh	Fl	Mc	Lv	Ts	Og
6	lanthanoids																		
7	actinoids																		

\pgfPT[IUPAC=false]

Periodic Table of Elements

1																	18	
1	H																	He
2	Li	Be											B	C	N	O	F	Ne
3	Na	Mg											Al	Si	P	S	Cl	Ar
4	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr
5	Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe
6	Cs	Ba	La	Hf	Ta	W	Re	Os	Ir	Pt	Au	Hg	Tl	Pb	Bi	Po	At	Rn
7	Fr	Ra	Ac	Rf	Db	Sg	Bh	Hs	Mt	Ds	Rg	Cn	Nh	Fl	Mc	Lv	Ts	Og
6	lanthanoids																	
7	actinoids																	

**show label LaAc**

default: {}

Determines when the labels 'lanthanoids' and 'actinoids' are shown (true) or not shown (false) near the f block. When the IUPAC key is set to true, the default behavior is to show the labels and when the IUPAC key is set to false, the default behavior is to hide the labels. This *default behavior can be overridden by this key* setting it to true, to show the labels, or to false to hide them, independently of the value of the IUPAC key.

```
\pgfPTnewZlist{myZlist}{55,...,118}
\pgfPTstyle[show title=false,show legend=false,show group numbers=false]
\pgfPT[Z list=myZlist]
```

A periodic table showing elements from atomic number 55 to 118. The lanthanoid and actinoid series are shown as separate rows below the main table. Labels 'lanthanoids' and 'actinoids' are placed to the left of their respective rows.

A periodic table showing elements from atomic number 57 to 110. The lanthanoid and actinoid series are shown as separate rows below the main table. Labels 'lanthanoids' and 'actinoids' are placed to the left of their respective rows.

```
\pgfPT[Z list=myZlist,show label LaAc=true]
```

A periodic table showing elements from atomic number 55 to 118. The lanthanoid and actinoid series are shown as separate rows below the main table. Labels 'lanthanoids' and 'actinoids' are placed to the left of their respective rows.

A periodic table showing elements from atomic number 57 to 110. The lanthanoid and actinoid series are shown as separate rows below the main table. Labels 'lanthanoids' and 'actinoids' are placed to the left of their respective rows.

```
\pgfPT[Z list=myZlist,IUPAC=false]
```

A periodic table showing elements from atomic number 55 to 118. The lanthanoid and actinoid series are shown as separate rows below the main table. Labels 'lanthanoids' and 'actinoids' are placed to the left of their respective rows.

A periodic table showing elements from atomic number 57 to 110. The lanthanoid and actinoid series are shown as separate rows below the main table. Labels 'lanthanoids' and 'actinoids' are placed to the left of their respective rows.

```
\pgfPT[Z list=myZlist,IUPAC=false,show label LaAc=false]
```

A periodic table showing elements from atomic number 55 to 118. The lanthanoid and actinoid series are shown as separate rows below the main table. Labels 'lanthanoids' and 'actinoids' are placed to the left of their respective rows.

A periodic table showing elements from atomic number 57 to 110. The lanthanoid and actinoid series are shown as separate rows below the main table. Labels 'lanthanoids' and 'actinoids' are placed to the left of their respective rows.

**label LaAc font**

default: `\footnotesize\itshape`

Sets the font for the labels 'lanthanoids' and 'actinoids'.

```
\pgfPT[label LaAc font=\bfseries,Z list=myZlist,IUPAC=false]
```

**\pgfPTresetstyle**

**capitalize element names**

default: `false`

If set to true the first letter of the name of the elements is a capital letter

```
\pgfPT[Z list={1,...,36},capitalize element names=true]
```

Periodic Table of Elements

**Name**

*no value*

A style equivalent to `capitalize element names=true`

```
\pgfPT[Z list={1,...,36},Name]
```

Periodic Table of Elements

**name**

*no value*

A style equivalent to `capitalize element names=false`

```
\pgfPT[Z list={1,...,36},name]
```

Periodic Table of Elements

languages

default: {}

Sets a language list to use in the Periodic Table. It is a comma separated list of language flags: 'pt', 'en', 'fr', 'de', 'it', 'es' or 'br'. This key overrides the default language, that is, the language loaded at package inclusion.

```
\pgfPT[Z list={1,...,36},languages=pt]
```

Tabela Periódica dos Elementos

```
\pgfPT[Z list={1,...,36},cell style=pgfPT2lang,languages={en,fr}]
```

Periodic Table of Elements  
Tableau Périodique des Éléments

```
\pgfPT[Z list={1,...,36},cell style=pgfPT3lang,languages={pt,fr,it}]
```


Tabela Periódica dos Elementos  
Tableau Périodique des Éléments  
Tavola Periodica degli Elementi

When using a set of languages, space to accommodate the names in each cell must be provided by building a suitable cell - typically one cell row per language. The cell styles used in the two examples above are built-in and serve this purpose.

✓ Built-in style **pgfPT2lang**

The build command:


```
\pgfPTbuildcell(6,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4-5;1-3;name),(6;1-3;Ar)]
```



✓ Built-in style **pgfPT3lang**

The build command:

```
\pgfPTbuildcell(7,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4-6;1-3;name),(7;1-3;Ar)]
```




Also, the space for the title should be taken into account – if using more than three languages, the legend must be *turned off*, otherwise the title overlaps the legend.

**other languages font**

default: `\tiny`

Sets the font used in *other languages*, i.e., the languages started at the second entry of the list provide to the `languages` key.

```
\pgfPT[Z list={1,...,36},cell style=pgfPT3lang,languages={en,es,br}, other languages font=\tiny\bfseries]
```



**other languages color**

default: `black!70`

Sets the color of the font used in *other languages*.

```
\pgfPT[Z list={1,...,36},cell style=pgfPT3lang,languages={en,pt,br}, other languages color=purple]
```

**Periodic Table of Elements**  
Tabela Periódica dos Elementos  
Tabela Periódica dos Elementos

**other lang**

default:  $\{f=\textit{tiny},c=\textit{black!70}\}$

*Pseudo style* to set the keys: other languages font and/or other languages color. None of the keys – f and c – are mandatory.

```
USAGE: other lang={f=<font commands>,c=<color>}
```

```
\pgfPT[Z list={1,...,36},cell style=pgfPT3lang,languages={en,fr,de}, other lang={f=\textit{tiny}itshape,c=blue}]
```

**Periodic Table of Elements**  
Tableau Périodique des Éléments  
Periodensystem der Elemente

**show MNM line**

default: *true*

If set to *true* a line separating metals from non metals is shown in the Periodic Table. The line starts at the upper left corner of the cell of boron (2<sup>nd</sup> period, group 13) and ends at the lower right corner of polonium (6<sup>th</sup> period, group 16). If set to *false* no line is drawn.

```
\pgfPT[Z list=spd]
```

**Periodic Table of Elements**

`\pgfPT[show MNM line=false]`

Periodic Table of Elements

**MNM line color**

Sets the color of the *MNM line*.

default: `red!80!black`

`\pgfPT[MNM line color=green]`

Periodic Table of Elements

**MNM line width**

Sets the width of the *MNM line*.

default: `.8pt`

`\pgfPT[MNM line width=1.5pt]`

Periodic Table of Elements

The image shows a standard periodic table of elements. A legend box in the upper left corner defines the following properties for an element: **Z**: Atomic Number, **Ra**: Radioactive, **CS**: Chemical Symbol, **N**: Name, **Ar**: Relative Atomic Mass. The legend also includes a color key: **solid** (black), **liquid** (red), **gas** (blue), and **synthetic** (yellow). The table includes elements from Hydrogen (1) to Oganesson (118), with the lanthanide and actinide series shown as separate rows below the main table.

**MNM**

default:  $\{c=red!80!black,w=.8pt\}$

*Pseudo style* to set the **MNM** line color and/or width. None of the keys – c and w – are mandatory. The key **show MNM** line is set to true.

**USAGE:**  $MNM=\{c=<color>,w=<length>\}$

$\backslash\text{pgfPT}[MNM=\{w=1.5pt,c=red\}]$


Periodic Table of Elements

This image shows the same periodic table of elements as above, but with a red border around the main table area. The legend box and the separate lanthanide/actinide rows remain the same. The red border highlights the main body of the periodic table.


► Title and Legend

**show title** default: *true*  
 When set to *true* the title is shown, otherwise the title (Periodic Table of elements) is not shown.

```
\pgfPT[Z list={1,...,54}]
```




```
\pgfPT[Z list={1,...,54},show title=false]
```



**title font** default:  $\backslash Large\bfseries$   
 Sets the font used in the title.

```
\pgfPT[Z list={1,...,54},title font=\Huge\itshape]
```

*Periodic Table of Elements*



**title color** default: *black*  
 Sets the title color.

```
\pgfPT[Z list={1,...,54},title color=green!50!black]
```

Periodic Table of Elements

**title** default:  $\{f=\backslash Large\bfseries,c=black\}$   
*Pseudo style* to set the keys: title **f**ont and/or title **c**olor. None of the keys – f and c – are mandatory. The key **show title** is set to **true**.

```
USAGE: title={f=<font commands>,c=<color>}
```

```
\pgfPT[Z list={1,...,54},title={f=\Huge,c=teal}]
```

Periodic Table of Elements

**show legend** default: **true**  
 When set to **true** the legend is shown, otherwise it is not shown.

```
\pgfPT[Z list={1,...,54}]
```

Periodic Table of Elements

```
\pgfPT[Z list={1,...,54},show legend=false]
```

Periodic Table of Elements

legend acronyms

default: true

When set to **true**, the legend consists of a cell using acronyms for its contents and the corresponding descriptions below that cell. When set to **false**, only the cell is displayed with the descriptions in place of the acronyms. In the latter case, the description font size is automatically adjusted to the available box, which can *spoil the appearance of the whole caption*, depending on the described content.

```
\pgfPT[Z list={1,...,54}]
```

Periodic Table of Elements

```
\pgfPT[Z list={1,...,54},legend acronyms=false]
```

Periodic Table of Elements


legend box

default: left color=black!20,right color=black!10,draw=black!30

Style to define the appearance of the box around the legend, legend pins and acronym descriptions, built with any of the TikZ keys that can be applied to a path construction. *It only works when the key legend acronyms is set to true.*


```
\pgfPT[Z list={1,...,36}]
```

Periodic Table of Elements




```
\pgfPT[Z list={1,...,36},legend box={draw=blue!20,fill=blue!10}]
```

Periodic Table of Elements




```
\pgfPT[Z list={1,...,36},legend box={draw=blue!20,fill=blue!10,legend acronyms=false}]
```

Periodic Table of Elements



```
\pgfPT[Z list={1,...,36},legend box={}]
```

Periodic Table of Elements



**legend back color**

Sets the legend background color.

default: *white*

```
\pgfPT[Z list={1,...,36}]
```

Periodic Table of Elements

```
\pgfPT[Z list={1,...,36},legend back color=blue!10]
```

Periodic Table of Elements

**legend radio color**

default: *black*

Sets the color of the radioactivity acronym and corresponding description.

```
\pgfPT[Z list={1,...,36}]
```

Periodic Table of Elements

```
\pgfPT[Z list={1,...,36},legend radio color=red]
```

Periodic Table of Elements

`\pgfPT[Z list={1,...,36},legend radio color=red,legend acronyms=false]`

Periodic Table of Elements

legend CS color

default: *black!50*

Sets the color of the Chemical Symbol acronym and corresponding description.

`\pgfPT[Z list={1,...,36}]`

Periodic Table of Elements

`\pgfPT[Z list={1,...,36},legend CS color=red]`

Periodic Table of Elements

`\pgfPT[Z list={1,...,36},legend CS color=red,legend acronyms=false]`

Periodic Table of Elements


**legend Z color**

default: {}

Sets the color of the atomic number description (only applies when the key **legend acronyms** is set to **true**.)


```
\pgfPT[Z list={1,...,36}]
```

Periodic Table of Elements




```
\pgfPT[Z list={1,...,36},legend Z color=red]
```

Periodic Table of Elements



```
\pgfPT[Z list={1,...,36},legend Z color=red,legend acronyms=false]
```

Periodic Table of Elements




**show legend pins**

default: true

When set to **true** the legend pins are shown, otherwise they are not shown.


```
\pgfPT[Z list={1,...,36}]
```

Periodic Table of Elements



```
\pgfPT[Z list={1,...,36},show legend pins=false]
```

Periodic Table of Elements




legend pins

default:  $\{line\ width=.05pt,rounded\ corners=2pt,right\ color=black!5, left\ color=white,draw=black!50\}$

Style to define the appearance of the legend pins, built with any of the TikZ keys that can be applied to a path construction.


```
\pgfPT[Z list={1,...,36}]
```

Periodic Table of Elements




```
\pgfPT[Z list={1,...,36},legend pins={draw=red,fill=red!10}]
```

Periodic Table of Elements



```
\pgfPT[Z list={1,...,36},legend pins={draw=red,fill=red!10},legend acronyms=false]
```

Periodic Table of Elements




**show extra legend**

default: *true*

When set to *true* the extra legend is shown, otherwise it is not shown.

```
\pgfPTbuilcellstyle{myname}(6,3)% 6 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5.25-6.75;1-3;DiscC)]
\pgfPT[Z list={1,...,54},cell style=myname]
```

Periodic Table of Elements



```
\pgfPT[Z list={1,...,54},cell style=myname,show extra legend=false]
```

Periodic Table of Elements




**extra legend**

default:  $\{draw=black!50,fill=black!10,line\ width=.05pt,rounded\ corners=2pt\}$

Style to define the appearance of the extra legend, built with any of the  $Ti\&Z$  keys that can be applied to a path construction.


```
\pgfPT[Z list={1,...,54},cell style=pgfPTdisc]
```

Periodic Table of Elements




```
\pgfPT[Z list={1,...,54},cell style=pgfPTdisc,extra legend={draw=red,fill=red!10}]
```

Periodic Table of Elements



```
\pgfPT[Z list={1,...,54},cell style=pgfPTdisc,legend acronyms=false,extra legend={draw=red,fill=red!10}]
```

Periodic Table of Elements



legend

default: {bc=white,pins=true,extra=true,acro=true}

Pseudo style to set the keys: legend **back** color, show legend **pins**, show **extra** legend, legend **acronyms**, legend **radio** color, legend **CS** color, legend **Z** color, legend **pins** (style), **extra** legend (style) and/or legend **box** (style). None of the keys – bc, pins, extra, acro, radio, CS, Z, pins style, extra style and box – are mandatory. The key **show legend** is set to true.

```
USAGE: legend={bc=<color>,pins=<true|false>,extra=<true|false>,acro=<true|false>,radio=<color>,CS=<color>,Z=<color>,pins style=<tikz path keys>,extra style=<tikz path keys>,box=<tikz path keys>}
```

```
\pgfPT[Z list={1,...,54},cell style=myname,legend={bc=black!10,extra=false}]
```

Periodic Table of Elements



`\pgfPT[Z list={1,...,54},cell style=myname,legend={acro=false,extra=false}]`

Periodic Table of Elements

► Periods and Groups

show period numbers

default: true

When set to true the period numbers are shown, otherwise they are not shown.

`\pgfPT[Z list={1,...,54}]`

Periodic Table of Elements

`\pgfPT[Z list={1,...,54},show period numbers=false]`

Periodic Table of Elements

**show group numbers**

default: *true*

When set to *true* the group numbers are shown, otherwise they are not shown.

```
\pgfPT[Z list={1,...,54}]
```

Periodic Table of Elements

The periodic table shows elements from Hydrogen (H) to Xenon (Xe). Group numbers 1 through 18 are printed above the columns. A legend box for Carbon (C) is shown, listing its properties: Atomic Number (6), Radioactive (No), Chemical Symbol (C), Name (Carbon), and Relative Atomic Mass (12.011).

```
\pgfPT[Z list={1,...,54},show group numbers=false]
```

Periodic Table of Elements

The periodic table is identical to the previous one, but the group numbers (1-18) are not displayed above the columns.

**period label color**

default: *red!50!black*

Sets the period label color.

```
\pgfPT[Z list={1,...,54},period label color=black]
```

Periodic Table of Elements

The periodic table shows elements from Hydrogen (H) to Xenon (Xe). The period numbers (1 through 5) are printed to the left of the rows in black. A legend box for Carbon (C) is shown, listing its properties: Atomic Number (6), Radioactive (No), Chemical Symbol (C), Name (Carbon), and Relative Atomic Mass (12.011).


**group label color**

default: *blue!50!black*

Sets the group label color.

```
\pgfPT[Z list={1,...,54},group label color=black]
```

Periodic Table of Elements




**label font**

default: *\small\bfseries*

Sets the label font.

```
\pgfPT[Z list={1,...,54},label font=\itshape]
```

Periodic Table of Elements



**per**


default: *{gr=true,c=red!50!black,f=\small\bfseries}*

*Pseudo style* to set the keys: show **g**roup numbers, period label color and/or label **f**ont. None of the keys – gr, c and f – are mandatory. The key **show period numbers** is set to true.

```
USAGE: per={gr=<true|false>,c=<color>,f=<font commands>}
```

```
\pgfPT[Z list={1,...,54},per={gr=false,c=green!50!black}]
```

Periodic Table of Elements



**gr** default: `{per=true,c=blue!50!black,f=\small\bfseries}`

*Pseudo style* to set the keys: show **period** numbers, group label **color** and/or label **font**. None of the keys – per, c and f – are mandatory. The key **show group numbers** is set to **true**.

**USAGE:** `gr={per=<true|false>,c=<color>,f=<font commands>}`

`\pgfPT[Z list={1,...,54},gr={per=false,c=green!50!black}]`

Periodic Table of Elements

**per+gr** default: `{pc=red!50!black,gc=blue!50!black,f=\small\bfseries}`

*Pseudo style:* use **c** to set both keys group label color and period label color with the same color; use **pc** to set period label color, **gc** to set group label color and/or **f** to set label font. None of the keys – c, pc, gc and f – are mandatory. The keys **show period numbers** and **show group numbers** are set to **true**.

**USAGE:** `per+gr={c=<color>,pc=<color>,gc=<color>,f=<font commands>}`

`\pgfPT[Z list={1,...,54},per+gr={c=green!50!black,f=\fontfamily{frc}\selectfont\normalsize\bfseries}]`

Periodic Table of Elements

► **Blocks and Families**

**show blocks**

default: *false*

When set to **true** the blocks **s**, **p**, **d** and **f** are drawn overlaying the Periodic Table and their labels are shown. *Note that blocks are only shown when the Z list contains, at least, all elements of blocks s, p and d.*

`\pgfPT[Z list={1,...,54},show blocks=true]`

Periodic Table of Elements

The periodic table shows elements grouped into colored blocks: s-block (yellow), p-block (green), d-block (orange), and f-block (purple). A legend box defines the color coding: s-block (yellow), p-block (green), d-block (orange), and f-block (purple). The legend also defines the color coding for element states: solid (black), liquid (blue), gaseous (red), and radioactive (grey).

`\pgfPT[show blocks]`


Periodic Table of Elements

The periodic table shows elements grouped into colored blocks: s-block (yellow), p-block (green), d-block (orange), and f-block (purple). A legend box defines the color coding: s-block (yellow), p-block (green), d-block (orange), and f-block (purple). The legend also defines the color coding for element states: solid (black), liquid (blue), gaseous (red), and radioactive (grey).

`\pgfPT[Z list=spd,show blocks,show title=false]`


The periodic table shows elements grouped into colored blocks: s-block (yellow), p-block (green), d-block (orange), and f-block (purple). A legend box defines the color coding: s-block (yellow), p-block (green), d-block (orange), and f-block (purple). The legend also defines the color coding for element states: solid (black), liquid (blue), gaseous (red), and radioactive (grey).

```
\pgfPT[Z list=spd,show blocks,show title=false,IUPAC=false]
```



**blocks font** default: `\small\bfseries`  
 Sets the font used in the block labels.

```
\pgfPT[Z list=spd,show blocks,show title=false,blocks font=\small\bfseries\fontfamily{ptm}\selectfont]
```



**s block color** default:  RGB: 255,231,132  
 Sets the block s color.

**s block font color** default: {}  
 Sets the s block label font color. If no color is provided, the s block color will be used as the font color.

**s block line width** default: 0.8pt  
 Sets the width of the line surrounding the s block.

**p block color** default:  RGB: 170,255,172  
 Sets the block p color.

**p block font color** default: {}  
 Sets the p block label font color. If no color is provided, the p block color will be used as the font color.

**p block line width** default: 0.8pt  
Sets the width of the line surrounding the p block.

**d block color** default:  RGB: 255,187,187  
Sets the block d color.

**d block font color** default: {}  
Sets the d block label font color. If no color is provided, the **d block color** will be used as the font color.

**d block line width** default: 0.8pt  
Sets the width of the line surrounding the d block.


**f block color** default:  RGB: 177,203,228  
Sets the block f color.

**f block font color** default: {}  
Sets the f block label font color. If no color is provided, the **f block color** will be used as the font color.

**f block line width** default: 0.8pt  
Sets the width of the line surrounding the f block.


**blocks font color** default: black  
Style to set a common color for the labels of s, p, d and f blocks. The key **show blocks** is set to true.

```
\pgfPT[blocks font color,show title=false]
```



**blocks line width** default: 0.8pt  
Style to set a common width of the lines surrounding the s, p, d and f blocks. The key **show blocks** is set to true.

\pgfPT[blocks line width=1.5pt]




**blocks** default: `{sc=locos,pc=locop,dc=locod,fc=locof,lw=.8pt,font=\small\bfseries}`  
*Pseudo style* to set the keys: block **s** color, block **p** color, block **d** color, block **f** color, the common line widths of the blocks, the **s** block line width, the **p** block line width, the **d** block line width, the **f** block line width, blocks font, **s** block font color, **p** block font color, **d** block font color and/or **f** block font color. None of the keys – `sc`, `pc`, `dc`, `fc`, `lw`, `slw`, `plw`, `dlw`, `flw`, `sfc`, `pcf`, `dfc` and `ffc` – are mandatory. The key `show blocks` is set to `true`.

**NOTE:**

The colors provided to the color keys of the blocks – `sc`, `pc`, `dc` and `fc` – could be any defined color via the command `\definecolor` or by *mixing* colors, using, for instance, the syntax `color1!value!color2` or `color1!value`, as explained in the `xcolor` package documentation.


**USAGE:** `blocks={sc=<color>,pc=<color>,dc=<color>,fc=<color>,lw=<lenght>,slw=<lenght>,plw=<lenght>,dlw=<lenght>,flw=<lenght>,f=<font commands>,sfc=<color>,pcf=<color>,dfc=<color>,ffc=<color>}`

\pgfPT[blocks={sc=red!70!white,pc=green!70!white,dc=yellow!70!white,lw=2pt}, show title=false,Z list=spd]



`\pgfPT[blocks={sc=red!70!white,pc=green!70!white,dc=yellow!70!white,dfc=yellow!70!black,lw=2pt}]`

Periodic Table of Elements




**show families**

default: *false*

When set to **true** the main families – representative elements, transition metals and internal transition metals – are drawn overlaying the Periodic Table and their labels are shown. *Note that families are only shown when the Z list contains, at least, all elements of blocks s, p and d.*


`\pgfPT[Z list={1,...,111},show families]`

Periodic Table of Elements




\pgfPT[show families]

Periodic Table of Elements



\pgfPT[show families,IUPAC=false]

Periodic Table of Elements




families font

Sets the font used in the family labels.

default: \small\bfseries

\pgfPT[show families,families font=\normalsize]



**r family color** default:  RGB: 170,255,172  
 Sets the representative elements *block* color.

**r family font color** default: {}  
 Sets the representative elements *block* label font color. If no color is provided, the **r family color** will be used as the font color.

**r family line width** default: 0.8pt  
 Sets the width of the line surrounding the representative elements *block*.

**tm family color** default:  RGB: 255,187,187  
 Sets the transition metals *block* color.

**tm family font color** default: {}  
 Sets the transition metals *block* label font color. If no color is provided, the **tm family color** will be used as the font color.

**tm family line width** default: 0.8pt  
 Sets the width of the line surrounding the transition metals *block*.


**itm family color** default:  RGB: 177,203,228  
 Sets the internal transition metals *block* color.

**itm family font color** default: {}  
 Sets the internal transition metals *block* label font color. If no color is provided, the **itm family color** will be used as the font color.

**itm family line width** default: 0.8pt  
 Sets the width of the line surrounding the internal transition metals *block*.


**families font color** default: *black*  
 Style to set a common color for the labels of representative elements, transition metals and internal transition metals *blocks*. The key `show blocks` is set to `true`.

```
\pgfPT[families font color=blue!50!black]
```



**families line width** default: *0.8pt*  
 Style to set a common width of the lines surrounding the representative elements, transition metals and internal transition metals *blocks*. The key `show families` is set to `true`.

```
\pgfPT[show families,families line width=1.5pt]
```



**families** default:  $\{rc=blcor,tc=blcot,ic=blocoi,lw=.8pt,f=\small\bfseries\}$


*Pseudo style* to set the keys: **r** family color, **tm** family color, **itm** family color, the common line widths of the families, the **r** family line width, the **tm** family line width, the **itm** family line width, the families font, **r** family font color, **tm** family font color and/or **itm** family font color. None of the keys – rc, tc, ic, lw, rlw, tlw, ilw, f, rfc, tfc and ifc – are mandatory. The key **show families** is set to true.

**NOTE:**


The colors provided to the color keys of the families could be any defined color via the command `\definecolor` or by *mixing* colors, using, for instance, the syntax `color1!value!color2`, as explained in the `xcolor` package documentation.

**USAGE:** families={rc=<color>,tc=<color>,ic=<color>,lw=<lenght>,rlw=<lenght>,tlw=<lenght>,ilw=<lenght>,f=<font commands>,rfc=<color>,tfc=<color>,ifc=<color>}


`\pgfPT[families={rc=red!70!white,ic=yellow!70!white,lw=2pt},show title=false]`



`\pgfPT[families={rc=blue,ic=yellow!70!white,rlw=2pt},show title=false]`



`\pgfPT[families={rc=blue,ic=yellow!70!white,rlw=2pt,ifc=yellow!70!black},show title=false]`



► Periodic variations

**show periodic variations**

default: *false*


When set to *true* the periodic variations – for atomic radius, ionization energy and/or electron affinity – are shown with two *arrows*. One horizontal arrow is placed at the top of the Periodic Table for the variation over the period and the other vertically to the left of the Periodic Table for the variation over the group.

**NOTE:**


The variations are only shown when the *base cell* of the Periodic Table contains the atomic radius, the ionization energy and/or the electron affinity. If none of them is present setting this key (*show periodic variations*) has no effect.

`\pgfPTstyle[Z list=spd,show title=false]`


`\pgfPT[show periodic variations]`



`\pgfPT[show periodic variations,cell style=pgfPTR]`



`\pgfPT[show periodic variations,cell style=pgfPTREi]`



**varR color**


default:  RGB: 128,191,191

Sets the color used in the filling of the arrows for the atomic radius variations.

**NOTE:**

The color provided to **varR color** could be any defined color via the command `\definecolor` or by *mixing* colors, using, for instance, the syntax `color1!value!color2`, as explained in the `xcolor` package documentation.

`\pgfPT[show periodic variations,cell style=pgfPTR,varR color=teal,R color=purple]`




**varR font**

default: `\footnotesize\bfseries`

Sets the font for the text displayed inside the arrow, describing the variation of the atomic radius.

```
\pgfPT[show periodic variations,cell style=pgfPTR,varR font=\small\itshape]
```



**varR font color**

default:  (value of varR color)!50!black

Sets the color of the text showing the atomic radius variations displayed inside the corresponding arrows.  
See the note in varR color.

**varEi color**

default:  RGB: 128,191,191

Sets the color used in the filling of the arrows for the ionization energy variations.  
See the note in varR color.

**varEi font**

default: `\footnotesize\bfseries`

Sets the font for the text displayed inside the arrow, describing the variation of the ionization energy.

**varEi font color** default:      (value of varEi color)!50!black  
 Sets the color of the text showing the ionization energy variations displayed inside the corresponding arrows.  
 See the note in varR color.


**vareaff color** default:      RGB: 128,191,191  
 Sets the color used in the filling of the arrows for the electron affinity variations.  
 See the note in varR color.

**vareaff font** default: \footnotesize\bfseries  
 Sets the font for the text displayed inside the arrow, describing the variation of the electron affinity.

**vareaff font color** default:      (value of vareaff color)!50!black  
 Sets the color of the text showing the electron affinity variations displayed inside the corresponding arrows.  
 See the note in varR color.

**var font** default: \footnotesize\bfseries  
 Style to set a common font for the variations along the Periodic Table.  
 Setting var font=<font commands> is equivalent to setting {varR font=<font commands>, varEi font=<font commands>, vareaff font=<font commands>}.


\pgfPT[show periodic variations,cell style=pgfPTREi,var font=\small\itshape]



**var color** default:      RGB: 128,191,191  
 Style to set a common color for the variations along the Periodic Table.  
 Setting var color=<color> is equivalent to setting {varR color=<color>, varEi color=<color>, vareaff color=<color>}.

**NOTE:**  
 The color provided to var color could be any defined color via the command \definecolor or by mixing colors, using, for instance, the syntax color1!value!color2, as explained in the xcolor package documentation.  
 Keep in mind that setting the variations colors also changes the default text colors for them.

\pgfPT[show periodic variations,cell style=pgfPTREi,var color=blue!50!white]



**varR**

default: {c=colorvariations,f=\footnotesize\bfseries}


Pseudo style to set the keys: varR color, varR font and/or varR font color. One of the keys - c, f and fc - are mandatory.

**NOTE:**

The color provided to varR color could be any defined color via the command \definecolor or by mixing colors, using, for instance, the syntax color1!value!color2, as explained in the xcolor package documentation.

**USAGE:** varR={c=<color>,f=<font commands>,fc=<color>}

\pgfPT[show periodic variations,cell style=pgfPTREi, varR={c=green!70!black,f=\small\bfseries}]



**varEi**

default:  $\{c=colorvariations,f=\footnotesize\bfseries\}$


Pseudo style to set the keys: varEi color, varEi font and/or varEi font color. None of the keys – c, f and fc – are mandatory.

**NOTE:**

The color provided to varEi color could be any defined color via the command \definecolor or by mixing colors, using, for instance, the syntax color1!value!color2, as explained in the xcolor package documentation.

**USAGE:** varEi={c=<color>,f=<font commands>,fc=<color>}

\pgfPT[show periodic variations,cell style=pgfPTREi,  
varR={c=green!70!black,f=\small\bfseries},  
varEi={c=lime!70!black,f=\small\bfseries}]



**vareaff**

default:  $\{c=colorvariations,f=\footnotesize\bfseries\}$


Pseudo style to set the keys: vareaff color, vareaff font and/or vareaff font color. None of the keys – c, f and fc – are mandatory.

**NOTE:**

The color provided to vareaff color could be any defined color via the command \definecolor or by mixing colors, using, for instance, the syntax color1!value!color2, as explained in the xcolor package documentation.

**USAGE:** vareaff={c=<color>,f=<font commands>,fc=<color>}

\pgfPT[show periodic variations,cell style=pgfPTEaff,  
vareaff={c=purple!70!white,f=\small\bfseries,fc=white}]



\pgfPTresetstyle


Dark mode

**dark mode** default: *no value*

Style to change the overall appearance of the Periodic Table to a dark mode suitable for on-screen viewing.

*This style sets the following keys with the values:*  
*back color scheme=solid, back color=black!80, cell line color=black!10, CS outline color=white, cell color=white, Z backcolor=black!30, Z color=black, background={fill=black}, varR font color=black!20, varEi font color=black!20, vareaff font color=black!20, per+gr={c=white}, title color=white, other languages color=black!40, legend={bc=black!70,radio=white,CS=white,Z=white,pins style={draw=white,right color=black!75, left color=black!60,line width=.05pt,rounded corners=2pt},extra style={draw=white,fill=black!70,line width=.05pt, rounded corners=2pt},box={left color=black!70,right color=black!40,draw=white}}*

\pgfPT[dark mode]



### ► **Exercise layout**

The **keys** described in this section enable the *exercise layout* of the Periodic Table, *i.e.*, in this mode the *structure* of the Periodic Table is drawn, but there are only a few contents available in the cells.

#### **only cells**

default: *false*

When set to **true** the Periodic Table is drawn with only the cells without any contents.

#### **NOTE:**

The following **keys** are also set: `back color scheme=solid`, `show title=false`, `show period numbers=false`, `show group numbers=false`, `show legend=false`, `show MNM line=false`

`\pgfPT[only cells]`

`\pgfPT[Z list={1,...,54},only cells]`

#### **only cells plus Z**

default: *false*

When set to **true** the Periodic Table is drawn with only the cells without any contents, except the atomic number (Z).

#### **NOTE:**

The following **keys** are also set: `back color scheme=solid`, `show title=false`, `show period numbers=false`, `show group numbers=false`, `show legend=false`, `show MNM line=false`

`\pgfPT[only cells plus Z]`

The image displays a periodic table where each cell contains only its atomic number. The Z-block elements (lanthanides and actinides) are shown as separate rows below the main body of the table. The main body includes elements from Hydrogen (1) to Oganesson (118).

`\pgfPT[only cells plus Z,IUPAC=false]`

This image shows a periodic table similar to the first one, but with the IUPAC symbols for the elements placed within the cells. The Z-block elements are also present as separate rows below the main table.

**only cells with periods and group numbers** default: *false*

When set to **true** the Periodic Table is drawn with only the cells without any contents. The period and group numbers are shown.

**NOTE:**  
 The following keys are also set: `back color scheme=solid`, `show title=false`, `show legend=false`, `show MNM line=false`

```
\pgfPT[Z list={1,...,36},only cells with periods and group numbers]
```

**only cells with periods and group numbers plus Z** default: *false*

When set to **true** the Periodic Table is drawn with only the cells without any contents, except the atomic number (Z). The period and group numbers are shown.

**NOTE:**

The following keys are also set: `back color scheme=solid`, `show title=false`, `show legend=false`, `show MNM line=false`

```
\pgfPT[Z list={1,...,36},only cells with periods and group numbers plus Z]
```

**Z exercise list** default: `{}`

Sets the list of atomic numbers to display as letters instead of their chemicals symbols.

**NOTES:**

- ✓ When values are provided to the *Z exercise list* and none of the above *exercise layout* is set, the *exercise layout only cells* is used.
- ✓ The line dots - ... - notation is not available in the *Z exercise list*, mainly to avoid *errors* on the desired list. For example `{1,...,4,8,...,16}` is expanded by the `\foreach` statement of `TikZ` to `{1,2,3,4,8,15}` instead of `{1,2,3,4,8,9,10,11,12,13,14,15,16}`. For achieving that purpose it must be typed `{1,...,4,8,9,...,16}`. Since the goal of *Z exercise list* is typing only a list of specific elements, it will often be easier to type element by element.

```
\pgfPT[Z exercise list={1,2,3,4,9,12,17,18,19,20,25,27,32,34,35,49,54,74,86,87}, cell size=3em,Z list={1,...,36}]
```

A																B	
C	D															E	
	F															G	H
I	J					K	L					M	N	O			

`\pgfPT[Z exercise list={1,2,3,4,9,12,17,18,19,20,25,27,32,34,35,49,54,74,86,87}, cell size=3em,Z list={1,...,36},only cells with periods and group numbers]`

	1																18	
1	A																B	
2	C	D															E	
3		F															G	H
4	I	J					K		L					M		N	O	

**exercise list in capitals**

default: *true*

When set to *true* the *letters* are typed in capitals, otherwise they are typed as lowercase letters.

`\pgfPT[Z exercise list={1,2,3,4,9,12,17,18,19,20,25,27,32,34,35,49,54,74,86,87}, cell size=3em,Z list={1,...,36},exercise list in capitals=false]`

	a																b	
1	c	d															e	
2		f															g	h
3	i	j					k		l					m		n	o	

**exercise list color**

default: *black*

Sets the color of the displayed *letters* in the *exercise layout*.

`\pgfPT[Z exercise list={1,2,3,4,9,12,17,18,19,20,25,27,32,34,35,49,54,74,86,87}, cell size=3em,Z list={1,...,36}, exercise list color=blue!50!black]`

	A																B	
1	C	D															E	
2		F															G	H
3	I	J					K		L					M		N	O	

**exercise list font**

default: `\bfseries\large`

Sets the font of the displayed *letters* in the *exercise layout*.

`\pgfPT[Z exercise list={1,2,3,4,9,12,17,18,19,20,25,27,32,34,35,49,54,74,86,87}, cell size=3em,Z list={1,...,36}, exercise list font=\fontfamily{fmm}\selectfont]`

	<i>A</i>																<i>B</i>	
1	<i>C</i>	<i>D</i>															<i>E</i>	
2		<i>F</i>															<i>G</i>	<i>H</i>
3	<i>I</i>	<i>J</i>					<i>K</i>		<i>L</i>					<i>M</i>		<i>N</i>	<i>O</i>	

**cells+Z**

*no value*

Style to set the key **only cells plus Z** to true.

```
\pgfPT[cells+Z]
```



**cells+p+g**

*no value*


Style to set the key **only cells with periods and group numbers** to true.

```
\pgfPT[cells+p+g]
```




**cells+p+g+Z** *no value*  
 Style to set the key only cells with periods and group numbers plus Z to true.

```
\pgfPT[cells+p+g+Z]
```




**exnocaps** *no value*  
 Style to set the key exercise list in capitals to false.

```
\pgfPT[Z exercise list={1,2,3,4,9,12,17,18,19,20,25,27,32,34,35,49,54,74,86,87}, cell size=3em,Z list={1,...,36},exnocaps]
```



**exColor** default: *black*  
 Style to set the key exercise list color.

```
\pgfPT[Z exercise list={1,2,3,4,9,12,17,18,19,20,25,27,32,34,35,49,54,74,86,87}, cell size=3em,Z list={1,...,36},exColor=red!50!black]
```



**exFont** default: \bfseries\large

Style to set the key exercise list font.

```
\pgfPT[Z exercise list={1,2,3,4,9,12,17,18,19,20,25,27,32,34,35,49,54,74,86,87},
cell size=3em,Z list={1,...,36},exFont=\Large]
```

A															B						
C	D											E									
	F											G	H								
I	J												K	L					M	N	O

**ex** default: {caps=true,c=black,f=\bfseries\large}

Pseudo style to set the keys: exercise list in **capitals**, exercise list **color** and/or exercise list **font**. None of the keys – caps, c and f – are mandatory.

```
USAGE: ex={caps=<true|false>,c=<color>,f=<font commands>}
```

```
\pgfPT[Z exercise list={1,2,3,4,9,12,17,18,19,20,25,27,32,34,35,49,54,74,86,87},
cell size=3em,Z list={1,...,36},ex={c=blue,f=\Large\bfseries}]
```

A															B						
C	D											E									
	F											G	H								
I	J												K	L					M	N	O

### ✂ Cell contents options: keys, styles and pseudo styles

The following options and styles are used for customizing the contents available in each individual cell of the Periodic Table, like the fonts or the colors used in the shown contents.


#### ➡ The atomic number

**Z bgcolor** default: black

Sets the background color of the box where the atomic number is displayed.

```
\pgfPT[Z list={1,...,36},Z bgcolor=blue!70!black]
```


Periodic Table of Elements



**Z color** default: *white*

Sets the color of the atomic number.


```
\pgfPT[Z list={1,...,36},Z bgcolor=black!30,Z color=black]
```



**Z font** default: *\tiny\bfseries*

Sets the font of the atomic number.


```
\pgfPT[Z list={1,...,36},Z font=\fontfamily{pag}\selectfont\tiny]
```



**Z use box width** default: *false*

If true, the width specified in the constructed cell is used, otherwise, the *natural* width of the box containing Z value is used.

```
\pgfPT[Z list={1,...,36},Z use box width]
```



**Z align** default: *left*

Sets the alignment of the atomic number value to *left*, *center* or *right* with respect to its containing box. It only takes effect when *Z use box width* is true.

```
\pgfPT[Z list={1,...,36},Z use box width,Z align=center]
```

**Periodic Table of Elements**

**Z padding** default: 0.25ex

Sets the padding between the atomic number value and the box that contains it. It only takes effect when **Z use box width** is true.

```
\pgfPT[Z list={1,...,36},Z use box width,Z align=right, Z padding=1em]
```

**Periodic Table of Elements**

**Z box** no value

Style equivalent to **Z use box width=true**.

```
\pgfPT[Z list={1,...,36},Z box]
```

**Periodic Table of Elements**

**Z** default: {bc=black,c=white,f=\tiny\bfseries,boxwd=false,align=left,space=.25ex}

Pseudo style to set the keys: **Z backcolor**, **Z color**, **Z font**, **Z use box width**, **Z align** and/or **Z pad**. None of the keys – bc, c, f, boxwd, align and pad – are mandatory.

**USAGE:** Z={bc=<color>,c=<color>,f=<font commands>,boxwd=<true|false>,align=<left|center|right>,pad=<length>}

```
\pgfPT[Z list={1,...,36},Z={bc=blue,f=\tiny\bfseries\itshape}]
```

Periodic Table of Elements

► The chemical symbol

**CS solid** default:  RGB: 255,166,51  
 Sets the color of the chemical symbol for elements that are in the solid state at normal temperature and pressure (NTP).

```
\pgfPT[Z list={1,...,54},CS solid=red]
```

Periodic Table of Elements

**CS liquid** default:  RGB: 0,204,204  
 Sets the color of the chemical symbol for elements that are in a liquid state at normal temperature and pressure (NTP).

```
\pgfPT[Z list={1,...,54},CS liquid=red]
```

Periodic Table of Elements

**CS gas**

default: CS RGB: 0,102,153

Sets the color of the chemical symbol for elements that are in a gaseous state at normal temperature and pressure (NTP).

```
\pgfPT[Z list={1,...,54},CS gas=red]
```

Periodic Table of Elements

**CS synt**

default: CS RGB: 236,236,236

Sets the color of the chemical symbol for elements that are synthetic.

```
\pgfPT[CS synt=red]
```

Periodic Table of Elements

**CS all**

default: black

Style to set a common color to the chemical symbols, equivalent to CS solid=<color>, CS liquid=<color>,CS gas=<color>,CS synt=<color>.

```
\pgfPT[CS all=red]
```

Periodic Table of Elements

**CS font**

Sets the font for the chemical symbol.

default: `\small\bfseries`

```
\pgfPT[Z list={1,...,36},CS font=\small\fontfamily{fmm}\selectfont]
```

Periodic Table of Elements

**CS render mode**

Sets the chemical symbol render mode. Available modes are *fill*, *outline* or *fill and outline*.

default: *fill and outline*

```
\pgfPT[Z list={1,...,36}]
```

Periodic Table of Elements

```
\pgfPT[Z list={1,...,36},CS render mode=fill]
```

Periodic Table of Elements

The image shows a standard periodic table of elements. Each element's cell contains its symbol, name, atomic number, and relative atomic mass. A legend box in the upper left shows the chemical symbols for Hydrogen (H), Carbon (C), Sodium (Na), Nitrogen (N), and Argon (Ar) with their respective states: solid, liquid, gaseous, and radioactive. The table is color-coded by groups.

```
\pgfPT[Z list={1,...,36},CS render mode=outline]
```

Periodic Table of Elements

This version of the periodic table is identical to the first one, but the chemical symbols in each cell are outlined in red. The legend box also shows the symbols with red outlines.

**CS outline color**

default: *black*

Sets the outline color for the chemical symbol.

```
\pgfPT[Z list={1,...,36},CS outline color=red]
```

Periodic Table of Elements

This version of the periodic table has the chemical symbols outlined in black, but the outlines are significantly thicker than in the standard version. The legend box also shows the symbols with thick black outlines.

**CS outline width**

default: *0.05*

Sets the outline width of the chemical symbol. It is any positive numerical value **without dimensions** (1.0 is roughly 1.0pt).

```
\pgfPT[Z list={1,...,36},CS outline width=.2]
```

Periodic Table of Elements

This version of the periodic table has the chemical symbols outlined in black, but the outlines are thinner than in the standard version. The legend box also shows the symbols with thin black outlines.


**CS** default:  $\{r=fill\ and\ outline,c=black,w=.05,f=\small\bfseries,s=solido,l=liquido,g=gasoso,sy=sintetico\}$

Pseudo style to set the keys: CS **render mode**, CS **outline color**, CS **outline width**, CS **font**, CS **solid**, CS **liquid**, CS **gas** and/or CS **synt** and/or the style CS **all**. None of the keys – r, olc, olw , f, s, l, g, sy and all – are mandatory.

**USAGE:** CS={r=<fill|outline|fill and outline>,olc=<color>,olw=<positive numerical value>f=<font commands>,s=<color>,l=<color>,g=<color>,sy=<color>,all=<color>}

`\pgfPT[Z list={1,...,36},CS={r=outline,olc=red,olw=.4},show legend pins=false]`

Periodic Table of Elements



► The atomic weight


**Ar color**

Sets the relative atomic mass color.

default: *black*

`\pgfPT[Z list={1,...,36},Ar color=red]`

Periodic Table of Elements




**Ar font**

Sets the relative atomic mass font.

default:  $\small\bfseries$

`\pgfPT[Z list={1,...,36},Ar font=\scriptsize\bfseries]`

Periodic Table of Elements




**Ar label**


default: *m*

Sets the label to be used within the relative atomic mass description. When set to 'm' the term **mass** is used and when set to 'w' the term **weight** is used, resulting in *Relative Atomic Mass* and *Atomic Weight* labels respectively.

```
\pgfPT[Z list={1,...,36}]
```



```
\pgfPT[Z list={1,...,36},Ar label=w]
```



**Ar precision**

default: *-1*


Sets the relative atomic mass precision, *i.e.*, the decimal places displayed in the relative atomic mass value, performing the respective rounding, without zero padding the value.

**NOTE:**

Rounding is performed over the relative atomic mass data values which actually have a maximum of 4 decimal places. So giving this key a value of -1 (the value of relative atomic mass as-is) or 4 has the same effect.

Therefore the values provided to this key should be any integer between -1 and 3, *i.e.*, -1, 0, 1, 2 or 3. Any other integer provided will be processed as -1.

```
\pgfPT[Z list={1,...,36}]
```



`\pgfPT[Z list={1,...,36},Ar precision=2]`

Periodic Table of Elements

A periodic table of elements with 2 decimal precision for atomic weights. The table is color-coded by groups. A legend box shows the following fields: Z (Atomic Number), Ra (Radioactive), CS (Chemical Symbol), N (Name), and Ar (Relative Atomic Mass). The atomic weights are rounded to two decimal places.

`\pgfPT[Z list={1,...,36},Ar precision=1]`

Periodic Table of Elements

A periodic table of elements with 1 decimal precision for atomic weights. The table is color-coded by groups. A legend box shows the following fields: Z (Atomic Number), Ra (Radioactive), CS (Chemical Symbol), N (Name), and Ar (Relative Atomic Mass). The atomic weights are rounded to one decimal place.

**Ar** default:  $\{c=black,f=\tiny\bfseries,l=m,p=-1\}$

*Pseudo style* to set the keys: Ar color, Ar font, Ar label and/or Ar precision. None of the keys – c, f, l and p – are mandatory.

**USAGE:** `Ar={c=<color>,f=<font commands>,l=<m|w>p=<integer value>}`

`\pgfPT[Z list={1,...,36},Ar={c=red!50!black,p=2}]`

Periodic Table of Elements

A periodic table of elements with a red!50!black color scheme and 2 decimal precision for atomic weights. The table is color-coded by groups. A legend box shows the following fields: Z (Atomic Number), Ra (Radioactive), CS (Chemical Symbol), N (Name), and Ar (Relative Atomic Mass). The atomic weights are rounded to two decimal places.

`\pgfPT[Z list={1,...,36},Ar={c=red!50!black,p=1,l=w}]`

Periodic Table of Elements

A periodic table of elements with a red!50!black color scheme, 1 decimal precision for atomic weights, and l=w. The table is color-coded by groups. A legend box shows the following fields: Z (Atomic Number), Ra (Radioactive), CS (Chemical Symbol), N (Name), and Ar (Atomic Weight). The atomic weights are rounded to one decimal place.

► The lattice structure


Is

default: fig

Sets what is displayed for the lattice structure: a figure (fig) or text (txt) or both (fig+txt or txt+fig).


```
\pgfPT[Z list={1,...,36},cell style=pgfPTIs]
```

Periodic Table of Elements




```
\pgfPT[Z list={1,...,36},cell style=pgfPTIs,Is=txt]
```

Periodic Table of Elements




```
\pgfPT[Z list={1,...,36},cell style=pgfPTIs,Is=fig+txt]
```

Periodic Table of Elements



```
\pgfPT[Z list={1,...,36},cell style=pgfPTIs,Is=txt+fig]
```

Periodic Table of Elements




**Is color**

default: *black*

Sets the lattice structure text color.

```
\pgfPT[Z list={1,...,36},cell style=pgfPTIs,Is=txt+fig,Is color=red]
```

Periodic Table of Elements




**Is font**

default: *\tiny*

Sets the lattice structure text font.

```
\pgfPT[Z list={1,...,36},cell style=pgfPTIs,Is=txt+fig,Is font=\tiny\bfseries]
```

Periodic Table of Elements




**Is align**

default: *right*

Sets the alignment of the lattice structure to *left* or *center* or *right*.

```
\pgfPT[Z list={1,...,36},cell style=pgfPTIs,Is align=center]
```

Periodic Table of Elements



➡ **The discovery year**

**DiscY color**

default: *black*

Sets the discovery year color.

```
\pgfPT[Z list={1,...,36},cell style=pgfPTdisc,DiscY color=red]
```

Periodic Table of Elements




**DiscY font**

Sets the discovery year font.

default: `\tiny\bfseries`

```
\pgfPT[Z list={1,...,36},cell style=pgfPTdisc,DiscY font=\fontfamily{pbk}\selectfont\tiny\bfseries]
```

Periodic Table of Elements



**DiscY BC scale**

Sets the font factor scaling for the Before Christ (BC) acronym in the discovery year.

default: `1`

```
\pgfPT[Z list={1,...,36},cell style=pgfPTdisc,DiscY BC scale=.8]
```

Periodic Table of Elements



➡ **The electron distribution**

```
\pgfPTbuilcellstyle{electron}(6,3)% 6 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),
(5;1-3;eDist),(6;1-3;eConfigl)]
```

**eDist color**

default: *black*

Sets the electron distribution color.

```
\pgfPT[Z list={1,...,54},cell style=electron,eDist color=red]
```

**Periodic Table of Elements**

The periodic table shows elements with their symbols, atomic numbers, and names. The electron distribution text is colored red. A legend box for element 2 (Helium) shows: Ra, CS, N, ed, ec, and a color key for solid (black), liquid (blue), gaseous (green), and synthetic (red).

**eDist font**

default: *\tiny\bfseries*

Sets the electron distribution font.

```
\pgfPT[Z list={1,...,54},cell style=electron,eDist font=\fontfamily{pbk}\selectfont\tiny\bfseries]
```

**Periodic Table of Elements**

The periodic table shows elements with their symbols, atomic numbers, and names. The electron distribution text is in a bold black font. A legend box for element 2 (Helium) shows: Ra, CS, N, ed, ec, and a color key for solid (black), liquid (blue), gaseous (green), and synthetic (red).

**eDist sep**

default: *,*

Sets the separator character between energy levels in electron distribution. *If the separator character is a comma it must be provided between curly braces - {,}.*

```
\pgfPT[Z list={1,...,54},cell style=electron,eDist sep=-]
```

**Periodic Table of Elements**

The periodic table shows elements with their symbols, atomic numbers, and names. The electron distribution text uses a hyphen as a separator between energy levels. A legend box for element 2 (Helium) shows: Ra, CS, N, ed, ec, and a color key for solid (black), liquid (blue), gaseous (green), and synthetic (red).

\pgfPT[Z list={1,...,54},cell style=electron,eDist sep={,}]

Periodic Table of Elements

➡ **The other contents**

For all the *other contents* available for the cells of the periodic table, two keys can be set: `<content name> color` and `<content name> font`.

**The <content name>'s list:**

- ✓ **name**: element name
- ✓ **R**: atomic radius
- ✓ **Rcov**: covalente radius
- ✓ **Rion**: ionic radius
- ✓ **Ei**: first ionization energy
- ✓ **eneg**: electronegativity (Pauling)
- ✓ **eaff**: electroaffnity
- ✓ **O**: oxidation states
- ✓ **Tmelt**: melting point (Kelvin)
- ✓ **TmeltC**: melting point (Celsius degrees)
- ✓ **Tboil**: boiling point (Kelvin)
- ✓ **TboilC**: boiling point (Celsius degrees)
- ✓ **eConfig**: electronic configuration (increasing n)
- ✓ **eConfignl**: electronic configuration (increasing n+l)
- ✓ **d**: density
- ✓ **Cp**: specific heat capacity
- ✓ **kT**: thermal conductivity
- ✓ **lsa**: lattice constant – a
- ✓ **lsb**: lattice constant – b
- ✓ **lsc**: lattice constant – c
- ✓ **lsca**: lattice c/a ratio
- ✓ **DiscC**: discover country
- ✓ **spectra**: visible range spectral lines


`<content name> color` default: *black*  
Sets the `<content name>` color.

\pgfPT[Z list={1,...,36},name color=blue]

Periodic Table of Elements


**<content name> font** default: \tiny\bfseries  
 Sets the <content name> font.

```
\pgfPT[Z list={1,...,36},name font=\tiny\itshape]
```




**cell font** default: \bfseries\tiny  
 Style to set the font for all cell contents, except for the Z and Chemical Symbol fonts.

```
\pgfPT[Z list={1,...,36},cell font=\tiny\itshape]
```



**cell color** default: black  
 Style to set the color for all cell contents, except for the Z and Chemical Symbol colors.

```
\pgfPT[Z list={1,...,36},cell color=blue]
```



The precision of the *other contents*, which have numerical values, can also be set by a key. Atomic radius, covalent radius, and ionic radius all have integer values, so precision does not apply to them.

**E precision**

default: -1

Sets the first ionization energy and the electroaffnity precision, *i.e.*, the decimal places displayed in their value, performing the respective rounding, without zero padding the value.

**NOTE:**

Rounding is performed over energy values witch actually have a maximum of 3 decimal places. So giving this key a value of -1 (the value of the energy as-is) or 3 has the same effect. Therefore the values provided to this key should be any integer between -1 and 2, *i.e.*, -1, 0, 1 or 2. Any other integer provided will be processed as -1.

```
\pgfPTbuilcellstyle{myE}(5,3)% 5 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-2.5;Ei), (5;2.5-3;eaff)]
\pgfPTstyle[Z list={1,...,54},cell style=myE,show title=false]
\pgfPT
```

\pgfPT[E precision=0]

\pgfPT[E precision=1]

`\pgfPT[E precision=2]`

`\pgfPT[E precision=3]`

**T precision**

default: -1

Sets the melting point an boiling point precision, *i.e.*, the decimal places displayed in their value, performing the respective rounding, without zero padding the value.

**NOTE:**

Rounding is performed over melting or boiling point values witch actually have a maximum, respectively, of 4 or 2 decimal places. So giving this key a value of -1 (the value of the melting or boiling point as-is) or, respectively, 4 or 2 has the same effect. *Therefore the values provided to this key should be any integer between -1 and 3 or 2. Any other integer provided will be processed as -1.*

```
\pgfPTbuilcellstyle{myT}(6,3)% 6 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-2.5;Tmelt),
(5;2.5-3;Tboil),(6;1-2.5;TmeltC),(6;2.5-3;TboilC)]
\pgfPTstyle[Z list={1,...,36},cell style=myT,Tmelt color=blue!50!black,TmeltC
color=blue,Tboil color=red!50!black,TboilC color=red,show title=false]
\pgfPT
```

\pgfPT[T precision=0]

1	2											13	14	15	16	17	18				
1	H																			2	He
2	Li	Be											B	C	N	O	F	Ne			
3	Na	Mg											Al	Si	P	S	Cl	Ar			
4	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr			

\pgfPT[T precision=1]

1	2											13	14	15	16	17	18				
1	H																			2	He
2	Li	Be											B	C	N	O	F	Ne			
3	Na	Mg											Al	Si	P	S	Cl	Ar			
4	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr			

\pgfPT[T precision=2]

1	2											13	14	15	16	17	18				
1	H																			2	He
2	Li	Be											B	C	N	O	F	Ne			
3	Na	Mg											Al	Si	P	S	Cl	Ar			
4	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr			

\pgfPT[T precision=3]

1	2											13	14	15	16	17	18				
1	H																			2	He
2	Li	Be											B	C	N	O	F	Ne			
3	Na	Mg											Al	Si	P	S	Cl	Ar			
4	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr			

\pgfPT[T precision=4]

1	2											13	14	15	16	17	18				
1	H																			2	He
2	Li	Be											B	C	N	O	F	Ne			
3	Na	Mg											Al	Si	P	S	Cl	Ar			
4	K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr			

**d precision**

default: -1

Sets the density precision, *i.e.*, the decimal places displayed in their value, performing the respective rounding, without zero padding the value.

**NOTE:**

Rounding is performed over density values with actually have a maximum 5 decimal places. So giving this key a value of -1 (the value of the melting or boiling point as-is) or 5 has the same effect.

Therefore the values provided to this key should be any integer between -1 and 4. Any other integer provided will be processed as -1.

```
\pgfPTbuilcellstyle{myd}(5,3)% 5 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;d)]
\pgfPTstyle[Z list={1,...,54},cell style=myd,show title=false]
\pgfPT
```

```
\pgfPT[d precision=0]
```

```
\pgfPT[d precision=1]
```

\pgfPT[d precision=2]

1																	2	
1	H																	He
	hydrogen																	helium
	0.89																	0.18
2	3	4											13	14	15	16	17	18
3	5	6	7	8	9	10	11	12	13	14	15	16	17	18				
4	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
5	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54
	Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe
	rubidium	strontium	yttrium	zirconium	niobium	molybdenum	technetium	ruthenium	rhodium	palladium	silver	cadmium	indium	tin	antimony	tellurium	iodine	xenon
	1532	2640	4472	6520	8570	10280	11000	12450	12410	12023	10490	8650	7310	7265	6897	6240	4933	5.89

\pgfPT[d precision=3]

1																	2	
1	H																	He
	hydrogen																	helium
	0.090																	0.179
2	3	4											13	14	15	16	17	18
3	5	6	7	8	9	10	11	12	13	14	15	16	17	18				
4	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
5	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54
	Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe
	rubidium	strontium	yttrium	zirconium	niobium	molybdenum	technetium	ruthenium	rhodium	palladium	silver	cadmium	indium	tin	antimony	tellurium	iodine	xenon
	1532	2640	4472	6520	8570	10280	11000	12450	12410	12023	10490	8650	7310	7265	6897	6240	4933	5.894

\pgfPT[d precision=4]

1																	2	
1	H																	He
	hydrogen																	helium
	0.0899																	0.1796
2	3	4											13	14	15	16	17	18
3	5	6	7	8	9	10	11	12	13	14	15	16	17	18				
4	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
5	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54
	Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe
	rubidium	strontium	yttrium	zirconium	niobium	molybdenum	technetium	ruthenium	rhodium	palladium	silver	cadmium	indium	tin	antimony	tellurium	iodine	xenon
	1532	2640	4472	6520	8570	10280	11000	12450	12410	12023	10490	8650	7310	7265	6897	6240	4933	5.894

\pgfPT[d precision=5]

1																	2	
1	H																	He
	hydrogen																	helium
	0.08988																	0.1786
2	3	4											13	14	15	16	17	18
3	5	6	7	8	9	10	11	12	13	14	15	16	17	18				
4	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
5	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54
	Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe
	rubidium	strontium	yttrium	zirconium	niobium	molybdenum	technetium	ruthenium	rhodium	palladium	silver	cadmium	indium	tin	antimony	tellurium	iodine	xenon
	1532	2640	4472	6520	8570	10280	11000	12450	12410	12023	10490	8650	7310	7265	6897	6240	4933	5.894

**Cp precision**

default: -1

Sets the specific heat capacity precision, *i.e.*, the decimal places displayed in their value, performing the respective rounding, without zero padding the value.

**NOTE:**

Rounding is performed over density values with actually have a maximum 3 decimal places. So giving this key a value of -1 (the value of the melting or boiling point as-is) or 3 has the same effect.

*Therefore the values provided to this key should be any integer between -1 and 2. Any other integer provided will be processed as -1.*

```
\pgfPTbuilcellstyle{myCp}(5,3)% 5 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;Cp)]
\pgfPTstyle[Z list={1,...,36},cell style=myCp]
\pgfPT
```

Periodic Table of Elements

```
\pgfPT[Cp precision=0]
```

Periodic Table of Elements

```
\pgfPT[Cp precision=1]
```

Periodic Table of Elements

\pgfPT[Cp precision=2]

Periodic Table of Elements

\pgfPT[Cp precision=3]

Periodic Table of Elements

**KT precision**

default: -1

Sets the thermal conductivity precision, *i.e.*, the decimal places displayed in their value, performing the respective rounding, without zero padding the value.

**NOTE:**

Rounding is performed over density values which actually have a maximum 5 decimal places. So giving this key a value of -1 (the value of the melting or boiling point as-is) or 5 has the same effect.

*Therefore the values provided to this key should be any integer between -1 and 4. Any other integer provided will be processed as -1.*

```
\pgfPTbuilcellstyle{mykT}(5,3)% 5 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;kT)]
\pgfPTstyle[Z list={1,...,36},cell style=mykT,show title=false]
\pgfPT
```

\pgfPT[kT precision=0]

Periodic table showing thermal conductivity values for various elements, rounded to 0 decimal places. A callout box for Carbon (C) shows its properties: Z: Atomic Number, Ra: Radioactive, CS: Chemical Symbol, N: Name, KT: Thermal Conductivity (Wm<sup>-1</sup>K<sup>-1</sup>). The callout box contains the text: "CS", "Ra", "N", "KT", "solid", "liquid", "gaseous", "synthetic".

\pgfPT[kT precision=1]

Periodic table showing thermal conductivity values for various elements, rounded to 1 decimal place. A callout box for Carbon (C) shows its properties: Z: Atomic Number, Ra: Radioactive, CS: Chemical Symbol, N: Name, KT: Thermal Conductivity (Wm<sup>-1</sup>K<sup>-1</sup>). The callout box contains the text: "CS", "Ra", "N", "KT", "solid", "liquid", "gaseous", "synthetic".

\pgfPT[kT precision=2]

Periodic table showing thermal conductivity values for various elements, rounded to 2 decimal places. A callout box for Carbon (C) shows its properties: Z: Atomic Number, Ra: Radioactive, CS: Chemical Symbol, N: Name, KT: Thermal Conductivity (Wm<sup>-1</sup>K<sup>-1</sup>). The callout box contains the text: "CS", "Ra", "N", "KT", "solid", "liquid", "gaseous", "synthetic".

\pgfPT[kT precision=3]

Periodic table showing thermal conductivity values for various elements, rounded to 3 decimal places. A callout box for Carbon (C) shows its properties: Z: Atomic Number, Ra: Radioactive, CS: Chemical Symbol, N: Name, KT: Thermal Conductivity (Wm<sup>-1</sup>K<sup>-1</sup>). The callout box contains the text: "CS", "Ra", "N", "KT", "solid", "liquid", "gaseous", "synthetic".

\pgfPT[kT precision=4]

Periodic table showing thermal conductivity values for various elements, rounded to 4 decimal places. A callout box for Carbon (C) shows its properties: Z: Atomic Number, Ra: Radioactive, CS: Chemical Symbol, N: Name, KT: Thermal Conductivity (Wm<sup>-1</sup>K<sup>-1</sup>). The callout box contains the text: "CS", "Ra", "N", "KT", "solid", "liquid", "gaseous", "synthetic".

\pgfPT[kT precision=5]

**Is precision**

default: -1

Sets the lattice structure constants - a, b, and c - precision, as also the lattice c/a ratio, *i.e.*, the decimal places displayed in their value, performing the respective rounding, without zero padding the value.

**NOTE:**

Rounding is performed over the constants data or c/a ratio values which actually have a maximum of 2 decimal places. So giving this key a value of -1 (the value of the constants or c/a ratio as-is) or 2 has the same effect.

*Therefore the values provided to this key should be any integer between -1 and 1. Any other integer provided will be processed as -1.*

\pgfPTbuilcellstyle{mysl}(6,3)% 6 rows by 3 columns  
 [(1;1-2;Z),(1;2-3;Is),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-2.5;Isa),  
 (5;2.5-3;Isb),(6;1-2.5;Is c),(6;2.5-3;Isca)]  
 \pgfPTstyle[Z list={1,...,36},cell={w=36pt,h=42pt,style=mysl}]  
 \pgfPT


Periodic Table of Elements

\pgfPT[Is precision=0]

Periodic Table of Elements


\pgfPT[Is precision=1]

Periodic Table of Elements



\pgfPT[Is precision=2]

Periodic Table of Elements




\pgfPTresetstyle

## Designing cells with `\pgfPTbuildcell`

To start designing the *base cell* of the Periodic Table it is necessary to keep in mind that each cell will be split into **n** rows and **k** columns.

As a running example, 5 rows and 3 columns will be used:




The next task is to assign contents to the cell by typing *trios* with the structure


- **(row;column;content)**
- or **(start row-end row;start column-end column;content)**
- or a combination of both.

The available **contents** are: Z, name, CS, Ar, Ar\*, radio, R, Rcov, Rion, Ei, eneg, eaff, O, Tmelt, TmeltC, Tboil, TboilC, eDist, eConfig, eConfigI, d, Cp, kT, Is, Isa, Isb, Isc, Isca, DiscY, DiscC and spectra.


Assigning, for instance, **(1;1;Z)** will show the atomic number in the first row and in the first column,




while the assignment **(1;1-2;Z)** will show the atomic number in the first row and filling the first and second columns,



It is also possible to start at a *fraction* of a line or column. If it is intended to start a line at the middle of the first column the value used should be **1.5**, which means that the start value is at the half ( $0.5$ ) of the first column ( $1$ ), observing that  $1.5$  is  $0.5$  plus  $1$ :



As in the second example above it is possible to end up in a specified *fraction* of a line or column:



### The row, column syntax

Both lines and columns share the same syntax, where  $n$  is any integer between 1 and the number of rows and  $f$  is the fractional part of any number between 0 and 1:

- (1) If only the row number  $n$  is provided the *content* is placed at the row  $n$ .
- (2) If the row number  $n$  is provided followed by a *dot* and a number  $f$ , the *content* is placed at the fraction  $f$  of the row  $n$ .
- (3) If the start row  $n_s$  and the end row  $n_e$  are provided separated by a *dash*, i.e.,  $n_s-n_e$ , the *content* is placed filling all the rows from  $n_s$  to  $n_e$ .  
The *dot* notation described in (2) can be used both on  $n_s$  and  $n_e$ .
- (4) All of the items above apply to columns in the same way.

### ✂ The cell contents

- ✓ **Z** – the atomic number of the elements.
- ✓ **name** – the name of the elements.
- ✓ **CS** – the chemical symbol of the elements.
- ✓ **Ar** – the relative atomic mass (atomic weight) of the elements.
- ✓ **Ar\*** – the standard relative atomic mass (standard atomic weight) of the elements.

- ✓ **radio** – radioactivity of the elements. If the element is radioactive the figure ☼ is placed in the cell, otherwise nothing is shown.
- ✓ **R** – the atomic radius of the elements. The atomic radius shown is the calculated radius and is expressed in picometers.
- ✓ **Rcov** – the covalent radius of the elements. The covalent radius shown is for single bonds and is expressed in picometers.
- ✓ **Rion** – the ionic radius of the elements. The radius shown is the effective ionic radius in picometers.
- ✓ **Ei** – the first ionization energy of the elements, measured in  $\text{kJ} \cdot \text{mol}^{-1}$ . All data from rutherfordium onwards is predicted.
- ✓ **eneg** – the Pauling electronegativity of the elements.
- ✓ **eaff** – the electroaffinity (electron affinity) of the elements, measured in  $\text{kJ} \cdot \text{mol}^{-1}$ . Estimated negative values have been replaced by zero, since the negative ions formed in these cases are always unstable (they may have lifetimes of the order of microseconds to milliseconds, and invariably autodetach after some time).
- ✓ **O** – the common oxidation states of the elements.
- ✓ **Tmelt** – the melting point, in Kelvin, of the elements.
- ✓ **TmeltC** – the melting point, in degrees Celsius, of the elements.
- ✓ **Tboil** – the boiling point, in Kelvin, of the elements.
- ✓ **TboilC** – the boiling point, in degrees Celsius, of the elements.
- ✓ **eDist** – the electron distribution of the elements.
- ✓ **eConfig** – the electronic configuration, in increasing  $n$  (principal quantum number), of the element, corresponding to the *spectroscopic* order of orbital energies, that is, the reverse of the order in which electrons are removed from a given atom to form positive ions.
 

*Note: the short version of the electronic configuration is used, i.e., [previous noble gas]remaining electrons. For example, for scandium it is: [Ar]3d<sup>4</sup>4s<sup>2</sup>*
- ✓ **eConfigl** – the electronic configuration, in increasing sum of  $n$  and  $\ell$  (azimuthal quantum number), of the element, following the order based on the Madelung rule.
 

*Note: the short version of the electronic configuration is used, i.e., [previous noble gas]remaining electrons. For example, for scandium it is: [Ar]4s<sup>2</sup>3d<sup>1</sup>*
- ✓ **d** – the density of the elements, in the corresponding physical state, at 25°C and 1 atm.
- ✓ **Cp** – the specific heat capacity of the elements in  $\text{J} \cdot \text{mol}^{-1} \cdot \text{K}^{-1}$  at 25°C and 100 kPa.
- ✓ **kT** – the thermal conductivity of the elements in  $\text{J} \cdot \text{m}^{-1} \cdot \text{K}^{-1}$  at 25°C.
- ✓ **Is** – the lattice structure of the elements at 1 bar and mostly at 25°C.
- ✓ **Isa** – the lattice constant  $a$  of the elements in picometers at 1 bar and mostly at 25°C.
- ✓ **Isb** – the lattice constant  $b$  of the eligible elements in picometers at 1 bar and mostly at 25°C.
- ✓ **Isc** – the lattice constant  $c$  of the eligible elements in picometers at 1 bar and mostly at 25°C.
- ✓ **Isca** – the lattice  $c/a$  ratio of the eligible elements at 1 bar and mostly at 25°C.
- ✓ **DiscY** – the discovery year of the elements.
- ✓ **DiscC** – the discovery country or in, a few cases, region (Middle East or Asia Minor) of the elements.
- ✓ **spectra** – the emission spectrum of the elements. The spectrum is only shown if available. The spectra are pre-built using the package `pgf-spectra` via the commands:

```
\pgfspectraStyle[back=visible40,line width=1pt,width=180pt,height=45pt,%
  relative intensity,relative intensity threshold=.375,%
  brightness=.5,charge=all,Imin=.125,gamma=1]
\foreach \SQ in {H,He,...,Bi,Po,Rn,Fr,...,Es}% Z=1,2,...,83,84,86,87,...,99
  {%
  \pgfspectra[element=\SQ]%
  }%
```

## ✧ Built-in cell styles


There is a set of *built-in* cell styles that could be used for the described purposes:

- ✓ **pgfPT2lang** – a cell layout to use with the name in two languages.

*Built-in style* **pgfPT2lang**

The build command:

```
\pgfPTbuildcell(6,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4-5;1-3;name),(6;1-3;Ar)]
```




- ✓ **pgfPT3lang** – a cell layout to use with the name in three languages.

*Built-in style* **pgfPT3lang**

The build command:

```
\pgfPTbuildcell(7,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4-6;1-3;name),(7;1-3;Ar)]
```




- ✓ **pgfPTR** – a cell layout to display the atomic radius and its periodic variations (if of course the **show periodic variations** key is set to true).

*Built-in style* **pgfPTR**

The build command:

```
\pgfPTbuildcell(5,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;R)]
```




- ✓ **pgfPTEi** – a cell layout to display the first ionization energy and its periodic variations (if of course the **show periodic variations** key is set to true).

**Built-in style pgfPTEi**

The build command:

```
\pgfPTbuildcell(5,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;Ei)]
```




- ✓ **pgfPTEaff** – a cell layout to display the electron affinity and its periodic variations (if of course the **show periodic variations** key is set to true).

**Built-in style pgfPTEaff**

The build command:

```
\pgfPTbuildcell(5,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;eaff)]
```




- ✓ **pgfPTREi** – a cell layout to display the atomic radius and first ionization energy and their periodic variations (if of course the **show periodic variations** key is set to true).

**Built-in style pgfPTREi**

The build command:

```
\pgfPTbuildcell(6,3)%
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;R),(6;1-3;Ei)]
```




- ✓ **pgfPTIs** – a cell layout to display the lattice system.

**Built-in style pgfPTIs**

The build command:

```
\pgfPTbuildcell(5,3)%
[(1;1-2.5;Z),(1;2.5-3;Is),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;Ar)]
```



✓ **pgfPTdisc** – a cell layout to display the discovery country and discovery year.

*Built-in style* **pgfPTdisc**

The build command:

```
\pgfPTbuildcell(6,3)%
```

```
[(1;1-2;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4;1-3;name),(5;1-3;DiscC),(6;1-3;DiscY)]
```

	1	2	3
1	Z		radio
2		CS	
3		CS	
4	name	name	name
5	DiscC	DiscC	DiscC
6	DiscY	DiscY	DiscY

scale 1.6:1

## Designing color schemes

There are two ways to make a new color scheme:

- with the command `\pgfPTnewColorScheme`
- and using the *script* in the file [pgfPTcolorSchemes.html](#)

### ✧ Designing a color scheme with `\pgfPTnewColorScheme`


This command provides a way to set the cell background color of each of the 118 elements of the Periodic Table. *If the intention is to set the background color for all of them, it is highly recommended to use the file [pgfPTcolorSchemes.html](#), unless the trailing color begin at a small atomic number.*

Despite that, this command can always be used taking into account:

1. It has the form `\pgfPTnewColorScheme[trailing color]{name}{color list}` where:
  - the first argument (enclosed by square brackets) is optional. If provided, the specified trailing color will be used, otherwise the default color (white) will be used as trailing color.
  - the second and third arguments are mandatory and specify, respectively, the color scheme name and the color list.
2. The **name** is any name made up of letters (only the characters a,...,z and A,...,Z).
3. The **color list** is a comma-separated list where each entry has the format `r/g/b`, representing the red, blue and green values, between 0 and 1, of the color: the first entry of the list will be the background color used in the cell of the element with atomic number 1, the second entry, the background color of the cell of the element with atomic number 2, and so on.


*If the color list has ten entries, these entries will set the background colors of the elements with atomic numbers from 1 to 10. For the following atomic numbers, greater than or equal to 11, the **trailing color** will be used in the color background.*

### ✧ Designing a color scheme with [pgfPTcolorSchemes.html](#)




The [pgfPTcolorSchemes.html](#) *designer* is an *html* file with a little *javascript* code to perform the task of building a color scheme to use with the **back color scheme** key associated with the `\pgfPT` command.


The Periodic Table of the Elements is displayed on the page and clicking on an element opens a color dialog:



Clicking on the Color picker:  button opens a color dialog, where there is the possibility to choose the desired color or manually enter one color using one of the three models available (RGB, HSL or HEX):



After changing the desired colors it is possible to save the color scheme in a file by clicking on **Write CS to file...**:




To use a color scheme saved in a file there are two possible ways:


- loading the file in the working document via the  $\input$   $\LaTeX$  command, for instance,  $\input{myCSname.tex}$ .
- or by opening the file and copying and pasting its contents into the working document.

In either case, the operation can be performed at any location in the document, but before the named color scheme is used.

Note that in the previous example there is only one color that has been defined (for hydrogen). In that case, it is useful to set the trailing color in helium by clicking in **Set trailing color** (which automatically changes to **Remove trailing color**). After that only the hydrogen and helium are clickable, all the other elements are locked to click:



Then the saved color scheme will have the optional trailing color and the size will be smaller as only the color codes of the changed elements are stored:



To remove the trailing color click on the last enabled element (in the above case helium) and then click on **Remove trailing color**. After that, all elements can be clicked again.

It is also possible to load a color scheme saved to a file by clicking on **Choose File** and then clicking on **Update Periodic Table** for the color scheme to take effect:

pgf-PeriodicTable ColorScheme Designer

Choose pgfPTColorScheme: default Set selected Color Scheme

Name for the Color Scheme: myCSname Write CS to file...

Load a Color Scheme:

Choose File CStemp.tex

```

\pgfPTnewColorScheme[0.5/.25/.333]{(colortest)}
{1/0.5987,.5/.33/0.25,.25/.25/.57}
    
```

Update Periodic Table

Part of pgf-PeriodicTable v1.0 package

Finally its possible to load a built-in color scheme by choosing a named *pgfPTColorScheme* in the corresponding combo box and then clicking on **Set selected Color Scheme**:

pgf-PeriodicTable ColorScheme Designer

Choose pgfPTColorScheme: Soft Set selected Color Scheme

Name for the Color Scheme: myCSname Write CS to file...

Load a Color Scheme:

Choose File No file chosen

Update Periodic Table

Part of pgf-PeriodicTable v1.0 package


*All the operations described are always available.*

# A few more examples

The following examples could be used for students or for any other purposes.


```
\pgfPTbuildcell(8,3)% 8 rows by 3 columns
[(1;1.4-2.8;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4.2;1-3;name),
(5.4;1-3;Ar),(6.5;1-3;eDist),(7.55-8.95;1-2.25;DiscC),(7.55-8.95;2.25-3.8;DiscY)]
\pgfPT
```

Periodic Table of Elements




```
\pgfPT[eDist color=blue!70!black,Ar precision=2,DiscC
font=\fontsize{4}{4}\selectfont,DiscY font=\fontsize{4}{4}\selectfont\bfseries]
```


Periodic Table of Elements



```
\pgfPTbuildcell(8,3)% 8 rows by 3 columns
[(1;1-2;Z),(1;3;radio),(2-3;1-3;CS),(4;1-3;name),(5;1-2.5;Ar),(5;2.5-3;spectra),
(7;1-2.5;DiscY),(7;2.5-3;DiscC),(8;1-3;eDist)]
\pgfPT[csPS,Ar label=w,background={left color=black!20}]
```



```
\pgfPTbuildcell(8,3)% 8 rows by 3 columns
[(1;1-3;Z),(1;3;radio),(2-3;1.5-3.5;CS),(4.2;1-3;name),(5.4;1-3;Ar),
(6.5;1-3;eConfigl),(7.55-8.95;1-2.45;DiscC),(7.55-8.95;2.45-3;DiscY)]
\pgfPT[eConfigl color=blue!70!black,Ar precision=2,DiscC
font=\fontsize{4}{4}\selectfont,DiscY font=\fontsize{4}{4}\selectfont\bfseries]
```



Representative elements: element families 

For the **representative elements** (groups **1**, **2** and **13** to **18**) it is common to speak of families that reflect their common characteristics. So we have **the families**:

**GROUP 1: Alkali metals**

▶ *lithium, sodium, potassium, rubidium, cesium and francium.*

The atoms of these elements **have only one valence electron.**

- ✓ They react violently with water to form hydroxides.
- ✓ They have a silver-gray color, with the exception of cesium, which has a golden hue.

**GROUP 2: Alkaline earth metals**

▶ *beryllium, magnesium, calcium, strontium, barium and radium.*

The atoms of these elements **have two valence electrons.**

- ✓ Their oxides remain solid at high temperatures and form alkaline solutions.
- ✓ They react violently with water to form hydroxides.
- ✓ When they burn, they have reddish flames, excluding barium, which presents a greenish flame.

**GROUP 13: Boron group**

▶ *boron, aluminium, gallium, indium, thallium and nihonium.*

The atoms of these elements **have three valence electrons.**

- ✓ Boron is a metalloid and the other are metals.
- ✓ Boron, aluminium, gallium, indium and thallium are often used as p-type silicon dopants.
- ✓ Aluminium is the third most abundant element in the Earth's crust (7.4%)

**GROUP 14: Carbon group**

▶ *carbon, silicon, germanium, tin, lead and flerovium.*

The atoms of these elements **have four valence electrons.**

- ✓ Carbon is a non-metal, silicon and germanium are metalloids, and tin and lead are metals.
- ✓ Silicon and germanium are used in semiconductors.

### GROUP 15: Pnictogens

► *nitrogen, phosphorus, arsenic, antimony, bismuth and moscovium.*

The atoms of these elements **have five valence electrons.**

- ✓ Nitrogen and phosphorus are non-metals, arsenic and antimony are metalloids and bismuth is a metal.
- ✓ Phosphorus, arsenic, antimony and bismuth are often used as n-type silicon dopants.
- ✓ Diatomic nitrogen is the main constituent of the Earth's atmosphere (78%).

### GROUP 16: Chalcogens

► *oxygen, sulfur, selenium, tellurium, polonium and livermorium.*

The atoms of these elements **have six valence electrons.**

- ✓ Oxygen, sulfur and selenium are non-metals, tellurium is a metalloid and polonium is a metal.
- ✓ Diatomic oxygen is the second constituent of the Earth's atmosphere (21%).

### GROUP 17: Halogens

► *fluorine, chlorine, bromine, iodine, astatine and tennessine.*

The atoms of these elements **have seven valence electrons.**

- ✓ They are extremely reactive elements, as they are very electronegative.
- ✓ Fluorine is able to *attack* inert substances, including the heavier noble gas atoms.

### GROUP 18: Noble gases

► *helium, neon, argon, krypton, xenon, radon and oganesson.*

The atoms of these elements have the valence shell fully filled, which corresponds to **eight valence electrons**, with the exception Helium, which has only one shell and, consequently, has **two valence electrons.**

- ✓ They are extremely inert elements, that is, they do not react with other elements, as they are the most stable elements in Nature.

**EXERCISE:**

In the following scheme of the Periodic Table, the positions of some chemical elements are represented by letters:

*THE LETTERS DO NOT CORRESPOND TO THE CHEMICAL SYMBOLS OF THE ELEMENTS.*

A																			B			
C	D																		E			
	F																		G	H		
I	J																		M	N	O	
																			P		Q	
																						S
T																						

**Using the letters shown:**

1. identify group 2 elements of the Periodic Table.
2. identify the elements of the 2<sup>nd</sup> period of the Periodic Table.
3. identify group 17 elements of the Periodic Table.
4. identify the elements of block s.
5. identify the elements of block p.
6. identify the elements of block d.
7. identify the metallic elements.
8. identify the non-metallic elements.
9. identify the transition metals.
10. identify the alkaline earth metals.
11. identify the noble gases.
12. tell which element belongs, simultaneously, to the 4<sup>th</sup> period and to group 14.
13. identify the representative elements that tend to generate positive ions.
14. indicate an element that forms bivalent ions.
15. indicate the halogen whose mononegative ion has the largest radius.
16. write the chemical formula of the compound formed by the elements **F** and **O**.
17. identify, justifying, the element with the largest atomic radius.
18. identify, justifying, the element with the lowest 1<sup>st</sup> ionization energy.

*For the source of this example please see the file pgf-PeriodicTableManual\_Examples.tex*



# Index

## BUILT-IN

cell styles ..... 96  
 color schemes ..... 9

## COMMANDS

\pgfPT ..... 3  
 \pgfPTbuildcell ..... 6  
     designing cells with ..... 93  
     row, column syntax ..... 94  
 \pgfPTbuildcellstyle ..... 6  
 \pgfPTnewColorScheme ..... 7  
 \pgfPTnewZlist ..... 9  
 \pgfPTpreviewcell ..... 6  
 \pgfPTpreviewcellstyle ..... 7  
 \pgfPTresetcell ..... 6  
 \pgfPTresetstyle ..... 5  
 \pgfPTstyle ..... 4

## OPTIONS

<content name> color ..... 81  
 <content name> font ..... 82  
 Ar color ..... 74  
 Ar font ..... 74  
 Ar label ..... 75  
 Ar precision ..... 75  
 back color ..... 15  
 back color scheme ..... 14  
 blocks font ..... 46  
 capitalize element names ..... 25  
 cell height ..... 11  
 cell line color ..... 12  
 cell line width ..... 12  
 cell style ..... 12  
 cell width ..... 11  
 Cp precision ..... 88  
 CS font ..... 72  
 CS gas ..... 71  
 CS liquid ..... 70  
 CS outline color ..... 73  
 CS outline width ..... 73  
 CS render mode ..... 72  
 CS solid ..... 70  
 CS synt ..... 71  
 d block color ..... 47  
 d block font color ..... 47  
 d block line width ..... 47  
 d precision ..... 86  
 DiscY BC scale ..... 79  
 DiscY color ..... 78  
 DiscY font ..... 79  
 E precision ..... 83  
 eDist color ..... 80  
 eDist font ..... 80  
 eDist sep ..... 80  
 exercise list color ..... 64  
 exercise list font ..... 64  
 exercise list in capitals ..... 64

f block color ..... 47  
 f block font color ..... 47  
 f block line width ..... 47  
 families font ..... 50  
 font ..... 13  
 group label color ..... 43  
 itm family color ..... 51  
 itm family font color ..... 51  
 itm family line width ..... 51  
 IUPAC ..... 22  
 kT precision ..... 89  
 label font ..... 43  
 label LaAc font ..... 25  
 languages ..... 26  
 legend acronyms ..... 33  
 legend back color ..... 34  
 legend CS color ..... 36  
 legend radio color ..... 35  
 legend Z color ..... 37  
 ls ..... 77  
 ls align ..... 78  
 ls color ..... 77  
 ls font ..... 78  
 ls precision ..... 91  
 MNM line color ..... 29  
 MNM line width ..... 29  
 only cells ..... 61  
 only cells plus Z ..... 61  
 only cells with periods and group numbers  
     plus Z ..... 63  
 only cells with periods and group numbers  
     62  
 other languages color ..... 27  
 other languages font ..... 27  
 p block color ..... 46  
 p block font color ..... 46  
 p block line width ..... 46  
 period label color ..... 42  
 r family color ..... 51  
 r family font color ..... 51  
 r family line width ..... 51  
 s block color ..... 46  
 s block font color ..... 46  
 s block line width ..... 46  
 show blocks ..... 44  
 show extra legend ..... 39  
 show families ..... 49  
 show group numbers ..... 42  
 show label LaAc ..... 24  
 show legend ..... 32  
 show legend pins ..... 37  
 show MNM line ..... 28  
 show period numbers ..... 41  
 show periodic variations ..... 54  
 show title ..... 31  
 T precision ..... 84  
 title color ..... 31

title font .....	31	MNM .....	30
tm family color .....	51	Name .....	25
tm family font color .....	51	name .....	25
tm family line width .....	51	other lang .....	28
vareaff color .....	57	per .....	43
vareaff font .....	57	per+gr .....	44
vareaff font color .....	57	title .....	32
varEi color .....	56	var color .....	57
varEi font .....	56	var font .....	57
varEi font color .....	56	vareaff .....	59
varR color .....	55	varEi .....	58
varR font .....	56	varR .....	58
varR font color .....	56	Z .....	69
Z align .....	68	Z box .....	69
Z backcolor .....	67		
Z color .....	67		
Z exercise list .....	63		
Z font .....	68		
Z list .....	10		
Z padding .....	69		
Z use box width .....	68		

**STYLES**

Ar .....	76
background .....	22
blocks .....	48
blocks font color .....	47
blocks line width .....	47
cell .....	13
cell color .....	82
cell font .....	82
cell size .....	11
cells+p+g .....	65
cells+p+g+Z .....	66
cells+Z .....	65
CS .....	74
CS all .....	71
csBlocks .....	21
csCPK .....	18
csJmol .....	17
csMNM .....	20
csPS .....	20
csRadio .....	21
csRasmol .....	18
csRasmolNew .....	19
csSoft .....	17
csSolid .....	16
csWikipedia .....	19
dark mode .....	60
ex .....	67
exColor .....	66
exFont .....	67
exnocaps .....	66
extra legend .....	39
families .....	53
families font color .....	52
families line width .....	52
gr .....	44
legend .....	40
legend box .....	33
legend pins .....	38