

ACRO

v2.1OC 2019/10/12

Typeset Acronyms and other Abbreviations

Clemens NIEDERBERGER

<https://bitbucket.org/cgnieder/acro/>

contact@mychemistry.eu

ACRO allows you to define and use abbreviations in a simple way. Abbreviations can be divided into different classes of abbreviations. Lists of abbreviations can be created (also of separate classes of abbreviations) and printed wherever you want the lists to appear.

ACRO provides an option `single` which ignores abbreviations that are used only once in the whole document.

As an experimental feature **ACRO** also offers the option `sort` which automatically sorts the list created by `\printacronyms`.

ACRO also has the feature of creating *local* lists

Table of Contents

1. Licence and Requirements	2	3.4. Fetching the Single Appearance	14
2. Basics	2	3.5. Using Classes	14
2.1. Creating New Acronyms	2	3.6. Reset or Mark as Used, Test if Acronym Has Been Used	15
2.2. Logging of Acronyms	6	3.7. <code>\ac</code> and Friends in PDF Bookmarks, Accessibility Support, Tooltips	16
2.3. Using the Acronyms – the Commands	7	3.7.1. PDF Bookmarks	16
2.4. Plural Forms	9	3.7.2. Accessibility Support .	17
2.5. Alternative Short Forms	10	3.7.3. Tooltips	17
2.6. Extra Information for the List Entry	11	3.8. Adding Acronyms to the Index	18
2.7. Foreign Language Acronyms .	12	4. Printing the List	18
3. Additional Commands and Possibilities	12	5. Options and Customization	20
3.1. Indefinite Forms	12	5.1. General Options	20
3.2. Uppercasing	13	5.2. Options Regarding Acronyms	22
3.3. Simulating the First Appearance	13	5.3. Options Regarding the List . .	24

1. Licence and Requirements

6. Trailing Tokens and Special Action	25	13. More on Customization	36
7. About Page Ranges	28	13.1. Background Information	36
8. Dividing Your Document Into Pieces – Creating Local Lists	28	13.2. Lists	36
9. Language Support	29	13.2.1. Own List Style	36
10. hyperref Support	29	13.2.2. Own List Heading Command	39
11. Defining Own Acronym Macros	29	13.3. First Styles	39
12. About Plural Forms, Possessive Forms and Similar Constructs – the Concept of Endings	34	13.4. Extra Styles	40
		13.5. Page Number Styles	41
		13.6. Configuration Files	42
		A. All Acronyms Used in this Documentation	42
		B. References	43
		C. Index	44

1. Licence and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the L^AT_EX Project Public License (LPPL), version 1.3 or later (<http://www.latex-project.org/lppl.txt>). The software has the status “maintained.”

ACRO loads and needs the following packages: `expl3`,¹ `xparse`, `xtemplate`, `l3keys2e`,² `zref-abspospage`³ and `translations`⁴ [Nie17].

2. Basics

2.1. Creating New Acronyms

Acronyms are created with the command `\DeclareAcronym`.

`\DeclareAcronym{\langle id \rangle}{\langle list of keys \rangle}`

The basic command for declaring an acronym.

This command understands a number of keys which are listed below. Some of them are not described immediately but at appropriate places in the documentation.

`short = {\langle text \rangle}` (required)

The short form of the acronym. This option is required: an acronym must have a short form. If this is set it *must* be set as first option! If another option is set first and notices the `short`

1. on CTAN as l3kernel: <http://mirrors.ctan.org/macros/latex/contrib/l3kernel/>
2. on CTAN as l3packages: <http://mirrors.ctan.org/macros/latex/contrib/l3packages/>
3. on CTAN as oberdiek: <http://mirrors.ctan.org/macros/latex/contrib/oberdiek/>
4. on CTAN as translations: <http://mirrors.ctan.org/macros/latex/contrib/translations/>

option missing it assumes that the ID should be used as short version and sets it accordingly. A warning will be written to the log then.

`long = {<text>}` (required)

The long form of the acronym. This option is required: an acronym must have a description.

`short-plural = {<text>}` Default: s

The plural ending appended to the short form.

`short-plural-form = {<text>}`

Introduced in
version 2.0

The plural short form of the acronym; replaces the short form when used instead of appending the plural ending.

`long-plural = {<text>}` Default: s

The plural ending appended to the long form.

`long-plural-form = {<text>}`

Plural long form of the acronym; replaces the long form when used instead of appending the plural ending.

`alt-plural = {<text>}` Default: s

Introduced in
version 2.0

The plural ending appended to the alternative form.

`alt-plural-form = {<text>}`

Introduced in
version 2.0

The plural alternative form of the acronym; replaces the alternative form when used instead of appending the plural ending.

`foreign-plural = {<text>}` Default: s

Introduced in
version 2.9

The plural ending appended to the foreign form.

`foreign-plural-form = {<text>}`

Introduced in
version 2.9

Plural foreign form of the acronym; replaces the foreign form when used instead of appending the plural ending.

`list = {<text>}` Default: s

If specified this will be written in the list as description instead of the long form.

`short-indefinite = {<text>}` Default: a

Indefinite article for the short form.

`long-indefinite = {<text>}` Default: a

Indefinite article for the long form.

`long-pre = {<text>}` Default: a

$\langle text \rangle$ is prepended to the long form in the text but not in the list of acronyms.

`long-post = {<text>}` Default: a

$\langle text \rangle$ is appended to the long form in the text but not in the list of acronyms.

post = {⟨text⟩}

⟨text⟩ is appended to the acronym in the text but not in the list of acronyms.

Introduced in
version 2.8**alt** = {⟨text⟩}

Alternative short form.

alt-indefinite = {⟨text⟩}

Default: a

Indefinite article for the alternative form.

extra = {⟨text⟩}

Extra information to be added in the list of acronyms.

foreign = {⟨original long form⟩}

Can be useful when dealing with acronyms in foreign languages, see section 2.7 on page 12 for details.

foreign-lang = {⟨language⟩}Introduced in
version 2.3

The babel [Bra19] or polyglossia [Cha19] language of the foreign form. This language is used to wrap the entry with \foreignlanguage{⟨language⟩} if either babel or polyglossia is loaded. You'll need to take care that the corresponding language is loaded by babel or polyglossia.

single = {⟨text⟩}Introduced in
version 2.3

If provided ⟨text⟩ will be used instead of the long form if the acronym is only used a single time and the option **single** = {true} is active.

sort = {⟨text⟩}

If used the acronym will be sorted according to this key instead of its ID.

class = {⟨csv list⟩}Changed in
version 2.4

The class(es) the acronym belongs to.

cite = {[⟨prenote⟩][⟨postnote⟩]{⟨citation keys⟩}}

A citation that is printed to the acronym according to an option explained later.

short-format = {⟨*T*_EX code⟩}

The format used for the short form of the acronym.

long-format = {⟨*T*_EX code⟩}

The format used for the long form of the acronym.

alt-format = {⟨*T*_EX code⟩}Introduced in
version 2.10

The format used for the alternative form of the acronym. If this is not given the short format will be used.

first-long-format = {⟨*T*_EX code⟩}

The format used for the first long form of the acronym as set with \ac, \acf or \acflike and their uppercase, plural and indefinite forms.

single-format = {⟨*TeX code*⟩}

Introduced in
version 2.3

The format used for the acronym if the acronym is only used a single time.

first-style = default|empty|square|short|long|reversed|footnote| sidenote| footnote-reversed|
sidenote-reversed

Introduced in
version 2.3

The style of the first appearance of the acronym, see also section 5.2.

pdfstring = {⟨*text*⟩/⟨*plural ending*⟩}

Changed in
version 2.4b

Used as PDF string replacement in bookmarks when used together with the hyperref package.
The appended plural ending is optional. If you leave it (*and the /*) the default ending is used.
⟨*text*⟩ is expanded before it is saved.

accsupp = {⟨*text*⟩}

Sets the ActualText key as presented by the accsupp package for the acronym.

tooltip = {⟨*text*⟩}

Introduced in
version 2.1

Sets the tooltip description for an acronym. For actually getting tooltips you also need an appropriate setting of the **tooltip-cmd** option or to set the package option **tooltip**.

index-sort = {⟨*text*⟩}

If you use the package option **index** every occurrence of an acronym is recorded to the index and sorted by its **ID** or (if set) by the value of the **sort** key. This key allows to set an individual sorting option for the index. See section 3.8 on page 18 for details.

index = {⟨*text*⟩}

This key allows to overwrite the automatic index entry with an arbitrary one. See section 3.8 on page 18 for details.

index-cmd = {⟨*control sequence*⟩}

This key let's you set an individual index creating command for this acronym. It should be a command that takes one mandatory argument. See section 3.8 on page 18 for details.

In its simplest form an acronym needs a short and a long form. Please note that both keys *must* be set and that the **short** key *must* always be the **first** key that is set.

```

1 % preamble:
2 \DeclareAcronym{test}{
3   short = ST ,
4   long  = Some Test
5 }
```

This creates the acronym “ST” with the ID “test” and the long form “Some Test.”

The **format** key allows you to choose a specific format for the short form of an acronym:

```

1 % preamble:
2 \DeclareAcronym{ot}{
3   short      = ot ,
4   long       = Other Test ,
5   short-format = \scshape
6 }
```

The short form now looks like this: OT.

The `cite` key needs a bit explaining. It expects arguments like the standard `\cite` command, *i.e.*, two optional arguments setting the `<prenote>` and `<postnote>` and one mandatory argument setting the citation key.

```

1 % preamble:
2 \DeclareAcronym{ny}{
3   short      = NY ,
4   short-plural = ,
5   long       = New York ,
6   long-plural = ,
7   cite       = {NewYork}
8 }
```

```

1 % bib file for use with biber/biblatex:
2 @online{NewYork,
3   author  = {Wikipedia},
4   title   = {New York City},
5   urldate = {2012-09-27},
6   url     = {http://en.wikipedia.org/wiki/New_York_City},
7   year    = {2012}
8 }
```

The first appearance now looks as follows⁵: New York (NY) [Wik12].

2.2. Logging of Acronyms

Introduced in
version 2.5

When you activate `ACRO`'s option `log` `ACRO`' writes information about the acronyms it defines to the log file.

⁵ The appearance of the citation of course depends on the citation style you're using.

`log = true|false|silent|verbose` Default: false

When set to `true`/`silent` `ACRO` writes the main properties of an acronym to the log file. When set to `verbose` `ACRO` writes all properties of an acronym to the log file.

This is an example of the logging info with `log = {true}` or `log = {silent}`.

```

1 =====
2 | Package acro Info -- defining new acronym:
3 |   ID = {jpg}
4 |   short = {JPEG}
5 |   long = {Joint Photographic Experts Group}
6 |   alt = {JPG}
7 |   sort = {jpeg}
8 |   class = {}
9 |   list = {}
10 |  extra = {}
11 |  foreign = {}
12 |  pdfstring = {}
13 |  cite = {}
14 =====

```

2.3. Using the Acronyms – the Commands

Acronyms are used with one of the following commands:

`\ac*{<id>}`

basic command; the first output is different from subsequent ones.

`\Ac*{<id>}`

same as `\ac` but capitalizes the first letter. Obeys the option `uppercase-short`.

`\acs*{<id>}`

short form; the actual acronym.

`\Acs*{<id>}`

same as `\acs` but capitalizes the first letter.

`\acl*{<id>}`

long form; the meaning of the acronym.

`\Acl*{<id>}`

same as `\acl` but capitalizes first letter.

`\aca*{<id>}`

alternative short form as specified in the `alt` key of `\DeclareAcronym`; if it hasn't been specified this is identical to `\acs`.

Introduced in
version 2.10

`\Aca*{⟨id⟩}`

same as `\aca` but capitalizes the first letter.

Introduced in
version 2.10

`\acf*{⟨id⟩}`

first form; output like the first time `\ac` is output.

`\Acf*{⟨id⟩}`

same as `\acf` but capitalizes first letter. Obeys the option `uppercase-short`.

`\acp*{⟨id⟩}`

plural form of `\ac`;

`\Acp*{⟨id⟩}`

same as `\acp` but capitalizes first letter. Obeys the option `uppercase-short`.

`\acsp*{⟨id⟩}`

plural form of `\acs`;

`\Acsp*{⟨id⟩}`

same as `\acsp` but capitalizes the first letter.

Introduced in
version 2.10

`\aclp*{⟨id⟩}`

plural form of `\acl`;

`\Aclp*{⟨id⟩}`

same as `\aclp` but capitalizes first letter.

`\acap*{⟨id⟩}`

plural form of `\aca`;

`\Acap*{⟨id⟩}`

same as `\acap` but capitalizes the first letter.

Introduced in
version 2.10

`\acf*{⟨id⟩}`

plural form of `\acf`;

`\Acfp*{⟨id⟩}`

same as `\acf` but capitalizes first letter of the long form. Obeys the option `uppercase-short`.

If an acronym is used the first time with `\ac` its output is different from subsequent uses. To be clear on this: the first time! If the acronym has been used with *any* of the output commands before it is *not* the first time any more.

If you use the starred variant an acronym will not be marked as used. This proves useful if an acronym is typeset in a section title, for example, since then the appearance in the table of contents won't mark it as used.

```

1 % preamble:
2 % \DeclareAcronym{cd}{
3 %   short      = cd ,
4 %   long       = Compact Disc ,
5 %   short-format = \scshape
6 %
7 first time: \ac{cd} \\
8 second time: \acs{cd} \\
9 short: \acs{cd} \\
10 alternative: \aca{cd} \\
11 first again: \acf{cd} \\
12 long: \acl{cd} \\
13 short plural: \acsp{cd} \\
14 long plural: \aclp{cd}

```

first time: Compact Disc (CD)
 second time: CD
 short: CD
 alternative: cd
 first again: Compact Disc (CD)
 long: Compact Disc
 short plural: CDs
 long plural: Compact Disks

2.4. Plural Forms

If an acronym is defined in the standard way ACRO uses an ‘s’ that’s appended to both the short and the long form when one of the plural commands is used. However, that is not always the best solution. For one thing not all acronyms may have a plural form. Second, the plural form especially of the long forms may be formed differently. And third, other languages can have other plural endings.

For these reasons `\DeclareAcronym` can get the following keys:

<code>short-plural</code> = { <i>text</i> }	Default: s
The plural ending of the short form.	
<code>long-plural</code> = { <i>text</i> }	Default: s
The plural ending of the long form.	
<code>long-plural-form</code> = { <i>text</i> }	
An alternative plural form for the long form.	

These keys are optional. If they’re not used, the default setting is s. If you use `long-plural-form` the long form will be replaced by the specified plural form when necessary.

Suppose we define the following acronyms:

```

1 \DeclareAcronym{cd}{
2   short      = cd ,
3   long       = Compact Disc ,
4   short-format = \scshape
5 }
6 \DeclareAcronym{ny}{
7   short      = NY ,
8   short-plural = ,

```

```

9 long           = New York ,
10 long-plural   =
11 }
12 \DeclareAcronym{sw}{
13 short          = SW ,
14 long           = Sammelwerk ,
15 long-plural   = e
16 }
17 \DeclareAcronym{MP}{
18 short          = MP ,
19 long           = Member of Parliament ,
20 long-plural-form = Members of Parliament
21 }

```

These acronyms now have the following plural appearances:

<code>1 \acsp{cd}, \aclp{cd} \\</code>	CDS, Compact Discs
<code>2 \acsp{ny}, \aclp{ny} \\</code>	NY, New York
<code>3 \acsp{sw}, \aclp{sw} \\</code>	SWs, Sammelwerke
<code>4 \acsp{MP}, \aclp{MP}</code>	MPs, Members of Parliament

In the default setting the format of the long or short form is not extended to the plural ending which might look strange if you choose bold weight as format, for example. In this case you can tell **ACRO** to extend the format.

format-include-endings = true|false Default: false

Introduced in
version 2.8

Tell **ACRO** to use the format of the base form for the endings, too.

For a more general view on endings please read section 12 on page 34.

2.5. Alternative Short Forms

For some acronyms it might be useful to have alternative forms. For this `\DeclareAcronym` has another key:

alt = {<text>}
Alternative short form.

```

1 % preamble:
2 % \DeclareAcronym{jpg}{
3 % short = JPEG ,
4 % sort  = jpeg ,
5 % alt   = JPG ,

```

```

6 % long = Joint Photographic Experts Group
7 %
8 default: \acs{jpg} \\
9 alt.: \aca{jpg}

```

default: JPEG
alt.: JPG

The alternative form uses the same plural ending as the default short form and is formatted in the same way.

2.6. Extra Information for the List Entry

Of course you can print a list of acronyms where their meaning is explained. Sometimes it can be useful to add additional information there. This is done with another key to \DeclareAcronym:

`extra = {<text>}`

Additional information for the list of acronyms.

These information will only be displayed in the list. See section 4 on page 18 for the impact of the following example.

```

1 % preamble:
2 % \DeclareAcronym{nato} {
3 %   short      = nato ,
4 %   long       = North Atlantic Treaty Organization ,
5 %   extra      = \textit{deutsch}: Organisation des Nordatlantikvertrags ,
6 %   short-format = \scshape
7 %
8 The \ac{nato} is an intergovernmental military alliance based on the
9 North Atlantic Treaty which was signed on 4~April 1949. \ac{nato}
10 headquarters are in Brussels, Belgium, one of the 28 member states
11 across North America and Europe, the newest of which, Albania and
12 Croatia, joined in April 2009.

```

The North Atlantic Treaty Organization (**NATO**) is an intergovernmental military alliance based on the North Atlantic Treaty which was signed on 4 April 1949. NATO headquarters are in Brussels, Belgium, one of the 28 member states across North America and Europe, the newest of which, Albania and Croatia, joined in April 2009.

2.7. Foreign Language Acronyms

I repeatedly read the wish for being able to add translations to acronyms when the acronyms stem from another language than the document language, *i.e.*, something like the following in a German document:

```
1 \ac{ecu}\  
2 \ac{ecu}
```

Steuergerät (Electronic Control Unit, ECU)
ECU

That's why I decided to add the following properties:

foreign = {⟨original long form⟩}

A description for an acronym originating in another language than the document language.

foreign-lang = {⟨language⟩}

Introduced in
version 2.3

The babel [Bra19] or polyglossia [Cha19] language of the foreign form. This language is used to wrap the entry with \foreignlanguage{⟨language⟩}.

Here is the definition of the above mentioned ECU acronym:

```
1 \DeclareAcronym{ecu}{  
2   short   = ECU ,  
3   long    = Steuergerät ,  
4   foreign = Electronic Control Unit ,  
5   foreign-lang = english  
6 }
```

As you have seen this adds the **foreign** entry to the first appearance of an acronym. It is also added in parentheses to the list of acronyms after the **long** entry. Actually the entry there is the argument to the following command:

\acroenparen{⟨argument⟩}

Places ⟨argument⟩ in parentheses: \acroenparen{example}: (example). See page 23 for a way to customize this other than redefining it.

3. Additional Commands and Possibilities

3.1. Indefinite Forms

Unlike many other languages⁶ in English the indefinite article is not determined by the grammatical case, gender or number but by the pronunciation of the following word. This means

6. Let's better say: unlike the other languages where I know at least the basics.

that the short and the long form of an acronym can have different indefinite articles. For these cases **ACRO** offers the keys `short-indefinite`, `alt-indefinite` and `long-indefinite` whose default is `a`. For every lowercase singular command two alternatives exist, preceded by `i` and `I`, respectively, which output the lowercase and uppercase version of the corresponding indefinite article.

```

1 % preamble:
2 % \DeclareAcronym{ufo}{
3 %   short           = UFO ,
4 %   long            = unidentified flying object ,
5 %   long-indefinite = an
6 %
7 \Iac{ufo}; \iacs{ufo}; \iacl{ufo}

```

An unidentified flying object (UFO); a UFO; an unidentified flying object

3.2. Uppercasing

`\acfistupper{\langle token list \rangle}`

This command uppercases the first token in `\langle token list \rangle`. The command is less powerful than `\makefirststuc` that is provided by the `mfirststuc` package [Tal17] but it is expandable. Obvious downsides are for example that it does not uppercase accented letters.

The following options control the behaviour of the uppercasing commands:

`uc-cmd = {\langle control sequence \rangle}` Default: `\acfistupper`

The command that is used to capitalize the first word in the `\Ac` and the like commands. You can change it to another one like for example `\makefirststuc`⁷ or `\MakeTextUppercase`.⁸

`uppercase-short = true|false` Default: `true`

Introduced in
version 2.10

If set to `true` commands like `\Ac` or `\Acp` will uppercase the first letter of the short form. Commands like `\Acs` or `\Acsp` will uppercase the short form in any case.

3.3. Simulating the First Appearance

Users told me⁹ that there are cases when it might be useful to have the the acronym typeset according to the `first-style` but with another text than the long form. For such cases **ACRO** offers the following commands.

7. from the `mfirststuc` package

8. from the `textcase` package

9. Well – one, to be precise ;)

`\acflike*{\langle id\rangle}{\langle instead of long form\rangle}`

Write some alternative long form for acronym with ID `\langle id\rangle` as if it were the first time the acronym was used.

`\acfplike*{\langle id\rangle}{\langle instead of long form\rangle}`

Plural form of `\acflike`.

```
1 \acsetup{first-style=footnote}
2 \acflike{ny}{the big apple}
```

NY^a

a. the big apple [Wik12]

The plural ending in `\acfplike` is only appended to the short form. It makes no sense to append it to the text that is inserted manually anyway. Note that whatever text you're inserting might be gobbled depending on the `first-style` you're using.

3.4. Fetching the Single Appearance

Introduced in
version 2.3

There are macros that fetch the *single* appearance of an acronym even if it has been used more than once and the `single` option is active.

`\acsingle*{\langle id\rangle}`

Write acronym as if it were used only a single time.

`\Acsingle*{\langle id\rangle}`

Uppercase form of `\acsingle`.

```
1 \acsingle{ny}
```

New York [Wik12]

3.5. Using Classes

The acronyms of `ACRO` can be divided into different classes. This doesn't change the output but allows different acronym lists, see section 4 on page 18. For this `\DeclareAcronym` has an additional key:

`class = {\langle csv list\rangle}`

Associated class(es) for an acronym.

Changed in
version 2.4

This might be useful if you can and want to divide your acronyms into different types, technical and grammatical ones, say, that shall be listed in different lists. Since every acronym can get a list of associated classes those classes can effectively be used like tags for filtering acronyms.

```

1 % preamble:
2 % \DeclareAcronym{la} {
3 %   short      = LA ,
4 %   short-plural = ,
5 %   long       = Los Angeles ,
6 %   long-plural = ,
7 %   class      = city
8 %
9 % \DeclareAcronym{ny} {
10 %   short     = NY ,
11 %   short-plural = ,
12 %   long      = New York ,
13 %   long-plural = ,
14 %   class     = city ,
15 %   cite      = NewYork
16 %
17 \acl{la} (\acs{la}) \\
18 \acl{ny} (\acs{ny})

```

Los Angeles (LA)
New York (NY)

3.6. Reset or Mark as Used, Test if Acronym Has Been Used

If you want for some reason to fool **ACRO** into thinking that an acronym is used for the first time you can call one of these commands:

\acreset{<comma separated list of ids>}

This will reset a used acronym such that the next use of **\ac** will again print it as if it were used the first time. This will *not* remove an acronym from being printed in the list if it actually *has* been used before.

\acresetall

Reset all acronyms.

\acifused{<id>}{{<true>}{<false>}}

This command tests if the acronym with ID *<id>* has already been used and either puts *true* or *false* in the input stream.

\aciffirst{<true>}{{<false>}}

Introduced in
version 2.8

To be used inside of acronym definitions in order to test if we are inside the first instance of the acronym or not.

1 \acreset{ny}\ac{ny}

New York (NY) [Wik12]

Beware that both commands act *globally!* There are also commands that effectively do the opposite of **\acreset**, *i.e.*, mark acronyms as used:

\acuse{\<comma separated list of ids>}

This has the same effect as if an acronym had been used twice, that is, further uses of \ac will print the short form and the acronym will in any case be printed in the list (as long as its class is not excluded).

\acuseall

Mark all acronyms as used.

Then there are two further commands related to using acronyms:

\acsswitchoff

Introduced in
version 2.6

This command is for patching in certain situations. For example some table environments like tabularx or tabu pass their content two or more times for determining the width of the table columns. Those can be patched to add \acsswitchoff to their trial phase.

\acsswitchon

Introduced in
version 2.6

Effectively the opposite of \acsswitchoff – this command should probably never be needed.

3.7. \ac and Friends in PDF Bookmarks, Accessibility Support, Tooltips

3.7.1. PDF Bookmarks

ACRO's commands usually are not expandable which means they'd leave unallowed tokens in PDF bookmarks. hyperref offers \texorpdfstring to circumvent that issue manually but that isn't really a nice solution. What's the point of having macros to get output for you if you have to specify it manually after all?

That is why **ACRO** offers a preliminary solution for this. In a bookmark every \ac like command falls back to a simple text string typesetting what \acs would do (or \acsp for plural forms). These text strings both can accessed manually and can be modified to an output reserved for PDF bookmarks.

\acpdfstring{\<id>}

Access the text string used in PDF bookmarks.

\acpdfstringplural{\<id>}

Access the plural form of the text string used in PDF bookmarks.

pdfstring = {{\<pdfstring>}/{\<plural ending>}}

Key for \DeclareAcronym to declare a custom text string for PDF bookmarks. The plural ending can be set optionally.

For example the PDF acronym used in the title for this section is defined as follows:

```

1 \DeclareAcronym{pdf}{
2   short      = pdf ,
3   long       = Portable Document Format ,
4   format     = \scshape ,
```

```

5 pdfstring = PDF ,
6 accsupp   = PDF
7 }
```

3.7.2. Accessibility Support

The last example also demonstrates the `accsupp` key. The idea is to have something different visible in the `PDF` file compared to what you get when you select and copy the corresponding string. In the example visible string is a lowercase `pdf` in small caps while the string copied is an uppercase `PDF`.

For this to work you need to use the *package option* `accsupp`, too, which will load the package `accsupp` if it isn't loaded by the user already. Then the key `accsupp` will set the `ActualText` property of `\BeginAccSupp`. Please refer to `accsupp`'s documentation for details. To see its effect copy `PDF` and paste it into a text file. You should get uppercase letters instead of lowercase ones.

`accsupp = {<text>}`

Key for `\DeclareAcronym` to set the `ActualText` property of `\BeginAccSupp` (see `accsupp`'s documentation for details) to be used for an acronym. It only has an effect when the package option `accsupp` is used, too.

3.7.3. Tooltips

The idea of a tooltip is to have some text shown when you hover with the mouse over the short form of an acronym. This is only available in some `PDF` viewers, though. One possibility for such tooltips is loading the `pdfcomment` package [Kle18] and using its `\pdftooltip` macro.

`tooltip = true|false`

Default: `false`

This option loads the `pdfcomment` package and sets the command for creating tooltips to `\pdftooltip`.

`tooltip-cmd = {<control sequence>}`

Default: `\@firstoftwo`

This allows users using another macro for tooltips – maybe one provided by another package or some own macro. It needs to be a macro with two mandatory arguments, the first being the string typeset in the `PDF`, the second being the tooltip description text.

For using this with acronyms they have a property `tooltip` which can be used inside `\DeclareAcronym` for specifying the description text of the tooltip. If the `tooltip` package option is used but the property is not set for an acronym then the `long` property is used instead.

If an acronym is used inside of another acronym then the tooltips of the “inner” acronyms are disabled.

3.8. Adding Acronyms to the Index

ACRO has the package option `index`. If it is used an index entry will be recorded every time an *unstarred* acronym command is used. The index entry will be $\langle id \rangle @ \langle short \rangle$, $\langle sort \rangle @ \langle short \rangle$ if the `sort` key has been set, $\langle index-sort \rangle @ \langle short \rangle$ if the `index-sort` has been set, or $\langle index \rangle$ if the key `index` has been set for the specific acronym. The short versions appearing there are formatted according to the chosen format of the corresponding acronym, of course.

This document demonstrates the feature. You can find every acronym that has been declared in the index. In order to allow flexibility the indexing command can be chosen both globally via package option and individually for every acronym. This would allow to add acronyms to a specific index if more than one index is used, for example with help of the `imakeidx` package.

I'm not yet convinced this is a feature many people if anyone needs and if they do if it is flexible enough. If you have any thoughts on this I'd appreciate an email.

4. Printing the List

Printing the whole list of acronyms is easy: just place `\printacronyms` where ever you want the list to be.

`\printacronyms[<options>]`

Print the list of acronyms.

The commands takes a few options, namely the following ones:

`include-classes = {<list of classes>}`

Takes a comma-separated list of the classes of acronyms that should be in the list.

`exclude-classes = {<list of classes>}`

Takes a comma-separated list of the classes of acronyms that should *not* be in the list. *Note that this list overwrites any entries in `include-classes`!* If a class is both included and excluded then the corresponding acronyms will not be added to the list.

`name = {<name of the list>}`

sets the name for the list.

`heading = {<sectioning command without leading backslash>}`

Default: `section*`

Sets the sectioning command for the heading of the list. A special value is `none` which suppresses the heading.

`sort = true|false`

Default: `true`

Set sorting for this list only.

`local-to-barriers = true|false`

Default: `false`

This option can be used to create a list of only the acronyms of the current “barrier group”, see section 8.

Introduced in
version 2.4

```
1 \acsetup{extra-style=comma}
2 \printacronyms[exclude-classes=city]
3
4 \printacronyms[include-classes=city, name={City Acronyms}]
```

Acronyms

CD

Compact Disc

CTAN

Comprehensive TeX Archive Network

ECU

Steuergerät (Electronic Control Unit)

ID

identification string

JPEG

Joint Photographic Experts Group

LPPL

L^AT_EX Project Public License

MP

Member of Parliament

NATO

North Atlantic Treaty Organization, *deutsch*: Organisation des Nordatlantikvertrags

PDF

Portable Document Format

SW

Sammelwerk

ST

Some Test

UFO

unidentified flying object

City Acronyms

LA

Los Angeles

NY

New York

You can see that the default layout is a description list with a \texttt{section*} title. Both can be changed, see section 5 on the next page.

The command \texttt{printacronyms} needs two L^AT_EX runs. This is a precaution to avoid error messages with a possibly empty list. But since almost all documents need at least two runs and often are compiled much more often than that, this fact shouldn't cause too much inconvenience.

5. Options and Customization

5.1. General Options

There are a few options which change the general behaviour of **ACRO**. Underlined values are used if no value is given.

messages = silent|loud Default: **loud**

Setting **messages** = {silent} will turn all of **ACRO**'s error messages into warnings and all of **ACRO**'s warnings into info messages. Be sure to check the log file carefully if you decide to set this option.

single = true|false Default: **false**

If set to **true** an acronym that's used only once (with \ac) in a document will only print the acronym in a specified form and will not be printed in the list.

single-form = long|short|alt|first Default: **long**

Introduced in
version 2.0

Determines how a single appearance of an acronym is printed if **single** = {**true**} has been chosen.

hyperref = true|false Default: **false**

If set to **true** the short forms of the acronyms will be linked to their list entry.

label = true|false Default: **false**

If set to **true** this option will place \label{{prefix}<*id*>} the first time the acronym with ID <*id*> is used.

label-prefix = {<text>} Default: **ac:**

The prefix for the \label that is placed when option **label** = {**true**} is used.

only-used = true|false Default: **true**

This option is **true** as default. It means that only acronyms that are actually used in the document are printed in the list. If **false**, all acronyms defined with \DeclareAcronym will be written to the list.

mark-as-used = first|any Default: **any**

This option determines whether an acronym is marked as used when the *first* form is used the first time (with \ac, \acf or \acflike and their uppercase, plural and indefinite forms) or when any of the \ac-like commands is used.

macros = true|false Default: **false**

If set to **true** this option will create a macro \<*id*> for each acronym as a shortcut for \ac{{<*id*>}}. Already existing macros will *not* be overwritten.

xspace = true|false Default: **false**

If set to **true** this option will append \xspace from the xspace package to the commands created with the **macros** option.

<code>strict = true false</code>	Default: false
If set to <code>true</code> and the option <code>macros = {true}</code> is in effect then already existing macros will be overwritten.	
<code>sort = true false</code>	Default: true
If set to <code>true</code> the acronym list will be sorted alphabetically. The entries are sorted by their ID ignoring upper and lower case. This option needs the experimental package <code>l3sort</code> (from the <code>l3experimental</code> bundle) and can only be set in the preamble. If set to <code>false</code> the acronyms are listed in order of their declaration.	
<code>display-foreign = true false</code>	Default: true
When set to <code>false</code> any <code>foreign</code> option is ignored and foreign forms are not displayed.	
<code>cite = all first none</code>	Default: first
This option decides whether citations that are added via <code>cite</code> are added to each first, every or no appearance of an acronym. If <code>first</code> is chosen, the option <code>single = {true}</code> is active and an acronym appears only once it still will get the citation.	
<code>cite-cmd = {\langle control sequence \rangle}</code>	Default: <code>\cite</code>
This option determines which command is used for the citation. Each citation command that takes the <code>cite</code> key as argument is valid, for example biblatex's <code>\footcite</code> .	
<code>cite-connect = {\langle code \rangle}</code>	Default: <code>\nobreakspace</code>
Depending on the citation command in use a space should be inserted before the citation or maybe not (e.g. <code>\footcite...</code>). This option allows you to set this. Actually it can be used to place arbitrary code right before the citation.	
<code>group-citation = true false</code>	Default: false
Introduced in version 2.0	If set to <code>true</code> the short form (or the long form) and the citation of an acronym will be printed together in parentheses when an acronym is used the first time.
<code>group-cite-cmd = {\langle control sequence \rangle}</code>	Default: <code>\cite</code>
Introduced in version 2.0	This option determines which command is used for the citation when an acronym is used the first time <i>and</i> <code>group-citation = {true}</code> . Each citation command that takes the <code>cite</code> key as argument is valid, for example biblatex's <code>\footcite</code> .
<code>group-cite-connect = {\langle code \rangle}</code>	Default: <code>,\nobreakspace</code>
Introduced in version 2.0	When <code>group-citation = {true}</code> this is inserted between the long/short form of the acronym and the citation within the parentheses.
<code>index = true false</code>	Default: false
If set to <code>true</code> an index entry will be recorded every time an <i>unstarred</i> acronym command is used for the corresponding acronym.	
<code>index-cmd = {\langle control sequence \rangle}</code>	Default: <code>\index</code>
Chooses the index command that is used when option <code>index</code> has been set to <code>true</code> .	

`accsupp = true|false` Default: false
 Activates the access support as provided by the accsupp package.

`tooltip = true|false` Default: false
 Activates tooltip support for ACRO using the pdfcomment package.

`tooltip-cmd = {<control sequence>}` Default: \@firstoftwo
 A macro taking two mandatory arguments, the first being the short form of the acronym and the second being some tooltip description.

`uc-cmd = {<control sequence>}` Default: \acfirstupper
 The command that is used to capitalize the first word in the \Ac and the like commands. You can change it to another one like for example \makefirstruc¹⁰ or \MakeTextUppercase.¹¹

`uppercase-short = true|false` Default: true
 If set to true commands like \Ac or \Acp will uppercase the first letter of the short version.

All options of this and the following sections can be set via the setup command:

`\acsetup{<options>}`
 Set up ACRO anywhere in the document. Or separate package loading from setup.

They might work as package options as well but *I do not recommend it.*

¹ % with \acsetup{macros}
² we could have used these before: \nato, \ny

we could have used these before: NATO, NY

5.2. Options Regarding Acronyms

The options described in this section all influence the layout of one of the possible output forms of the acronyms.

`short-format = {<format>}` (initially empty)
 Sets a format for all short forms. For example `short-format = {\scshape}` would print all short forms in small caps.

`long-format = {<format>}` (initially empty)
 The same for the long forms.

`foreign-format = {<format>}` (initially empty)
 The format for the foreign entry when it appears as part of the first appearance of an acronym.

¹⁰. from the mfirstuc package
¹¹. from the textcase package

5. Options and Customization

<code>single-format = {\langle format \rangle}</code>	(initially empty)
Introduced in version 2.3	The format for the acronym when it is used only once. If not specified the formatting according to <code>singl-form</code> is used.
<code>first-long-format = {\langle format \rangle}</code>	(initially empty)
	The format for the long form on first usage (with <code>\ac</code> , <code>\acf</code> or <code>\acflike</code> and their uppercase, plural and indefinite forms).
<code>list-short-format = {\langle format \rangle}</code>	(initially empty)
Introduced in version 2.1	An extra format for the short entries in the list. If not used this is the same as <code>short-format</code> . Please be aware that a call of <code>short-format</code> after this one will overwrite it again.
<code>list-short-width = {\langle dim \rangle}</code>	Default: 3em
	This option controls the width reserved for the short forms of the acronyms in the <code>lof</code> list style.
<code>list-long-format = {\langle format \rangle}</code>	(initially empty)
	An extra format for the long entries in the list. If not used this is the same as <code>long-format</code> . Please be aware that a call of <code>long-format</code> after this one will overwrite it again.
<code>list-foreign-format = {\langle format \rangle}</code>	Default: <code>\acroenparen</code>
	The format for the <code>foreign</code> entry as it appears in the list. This may be code that ends with a macro that takes a mandatory argument.
<code>extra-format = {\langle format \rangle}</code>	(initially empty)
	The same for the extra information.
<code>first-style = default empty square short long reversed footnote sidenote footnote-reversed sidenote-reversed</code>	Default: default
	The basic style of the first appearance of an acronym. The value <code>sidenote</code> needs the command <code>\sidenote</code> to be defined (for example by the <code>sidenotes</code> package).
<code>extra-style = default plain comma paren bracket</code>	Default: default
	Defines the way the extra information is printed in the list.
<code>plural-ending = {\langle short \rangle / \langle long \rangle}</code>	Default: s/s
Changed in version 2.4b	With this option the default plural ending can be set. The appended <code>\langle long \rangle</code> ending is optional. If you leave it (<i>and</i> the <code>/</code>) the <code>\langle short \rangle</code> ending is used for both short and long versions.

```

1 % (Keep in mind that we're in
2 a minipage here!)
3 \acsetup{first-style=empty}
4 empty: \acf{ny} \\
5 \acsetup{first-style=footnote}
6 footnote: \acf{ny} \\
7 \acsetup{first-style=square}
8 square: \acf{ny} \\
9 \acsetup{first-style=short}
10 short: \acf{ny} \\
11 \acsetup{first-style=long}
12 long: \acf{ny} \\
13 \acsetup{first-style=reversed}
14 reversed: \acf{ny} \\
15 \acsetup{
16   first-style = footnote-reversed
17 }
18 footnote-reversed: \acf{ny}
```

empty: NY
 footnote: NY^a
 square: New York [NY] [Wik12]
 short: NY [Wik12]
 long: New York [Wik12]
 reversed: NY (New York) [Wik12]
 footnote-reversed: New York^b

a. New York [Wik12]
b. NY [Wik12]

5.3. Options Regarding the List

`page-style` = none|plain|comma|paren

Default: none

If this option is set to a value other than none the page numbers of the an acronym appeared on are printed in the list. Please note that this is an experimental feature and might fail in quite a number of cases. If you notice anything please send me an email!

`pages` = all|first

Default: all

If the option `page-style` has any value other than none this option determines wether all usages of the acronyms are listed or only the first time. Implicitly sets `label` = {true}.

`page-name` = {*<page name>*}

Default: p.\@\\,

The “name” of the page label. This is automatically translated to the active language. However for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`pages-name` = {*<page name plural>*}

Default: pp.\@\\,

The “name” of the page label when there are more than one page. This is automatically translated to the active language. However for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`following-page` = true|false

Default: false

If set to true a page range in the list of acronyms that consists of two pages will be written by the first page and an appended f. This depends on the option `next-page`.

`following-pages` = true|false

Default: false

If set to true a page range in the list of acronyms that set consists of more than two pages will be written by the first page and an appended ff. This depends on the option `next-pages`.

6. Trailing Tokens and Special Action

`following-pages*` = `true|false` Default: `false`

Introduced in
version 2.5

If set to `true` this sets both options `following-page = {true}` and `following-pages = {true}`. `false` sets `following-page = {false}` and `following-pages = {false}`.

`next-page` = `{<text>}` Default: `\, f. \@`

Appended to a page number when `following-page` is set to `true` and the range is only 2 pages long. This is automatically translated to the active language. However, for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`next-pages` = `{<text>}` Default: `\, ff. \@`

Appended to a page number when `following-pages` is set to `true` and the range is more than 2 pages long. This is automatically translated to the active language. However, for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`list-style` = `description|lof|longtable|extra-longtable|extra-longtable-rev|extra-tabular|extra-tabular-rev|tabular|toc` Default: `description`

Changed in
version 2.2

Choose with which style the list of acronyms should be typeset. If you choose `<longtable>`, `extra-longtable` or `extra-longtable-rev` you have to load the `longtable` [Car19] package in your preamble. The values `extra-<something>` put the extra information in a column of its own. *Be aware that per default all extra-table styles only use 1 columns. Since acronym descriptions can easily get longer than a line you should probably define your own style if you want to use them.* See section 13.2 on page 36 for details.

`list-heading` = `chapter|chapter*|section|section*|subsection|subsection*|subsubsection|subsubsection*|addchap|addsec|none` Default: `section*`

Changed in
version 2.0

The heading type of the list. The last two only work with a KOMA-Script class that also defines the appropriate command. A special value is `none` which suppresses the heading.

`list-name` = `{<list name>}` Default: `Acronyms`

The name of the list. This is what's written in the list-heading. This is automatically translated to the active language. However, for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`list-caps` = `true|false` Default: `false`

Print the first letters of the long form capitalized.

6. Trailing Tokens and Special Action

Introduced in
version 2.0

ACRO has the possibility to look ahead for certain tokens and switch a boolean if it finds them. Per default **ACRO** knows about three tokens: the “dot” (.), the “dash” (-) and the “babel-hyphen” (`\babelhyphen`).

A token is made known to **ACRO** with the following macro:

`\AcroRegisterTrailing<token>{<name>}`

This registers the token `<token>` so **ACRO** looks if it follows directly after an acronym macro. `<name>` is the internal name for this token.

6. Trailing Tokens and Special Action

The **ACRO** package already registers the above mentioned tokens:

```
1 \AcroRegisterTrailing . {dot}
2 \AcroRegisterTrailing - {dash}
3 \AcroRegisterTrailing \babelhyphen {babel-hyphen}
```

If a token is registered it doesn't mean that **ACRO** looks for it. The token must first be activated for this:

activate-trailing-tokens = {⟨csv list of token names⟩}

Tell **ACRO** to look for trailing tokens. This is done by giving a csv list of the internal *names* of the tokens. Per default only **dot** is activated.

deactivate-trailing-tokens = {⟨csv list of token names⟩}

Tell **ACRO** not to look for trailing tokens. This is done by giving a csv list of the internal *names* of the tokens.

All of the above on its own does nothing visible. However: inside of an acronym, *i. e.*, for example inside the long or the short form it can be tested for those trailing tokens:

\aciftrailing{⟨csv list of token names⟩}{⟨true⟩}{⟨false⟩}

Check if one of the tokens listed in ⟨csv list of token names⟩ is following and either place ⟨true⟩ or ⟨false⟩ in the input stream.

ACRO uses this to define two further macros:

\acdot

Inserts a **.** if no dot follows.

\acspace

Inserts a **\space** if no dash or babel-hyphen follows.

The definitions are equivalent¹² to the following code:

```
1 \newcommand*\acdot{\aciftrailing{dot}{}{.\@{}}
2 \newcommand*\acspace{\aciftrailing{dash,babel-hyphen}{}{\space}}
```

This could be used to define an acronym as follows:

¹². Not quite: **ACRO**'s definitions are engine protected.

6. Trailing Tokens and Special Action

```
1 \DeclareAcronym{etc}{  
2   short = {\textit{etc}\acdot} ,  
3   long = {\textit{et cetera}} ,  
4   short-plural = , long-plural =  
5 }
```

If now you somewhere use

```
1 \ac{etc}.
```

there won't be two dots printed.

The command `\acspace` is used already in the definition of the first appearance of a macro. Let's say you're a German chemist and you have

```
1 \DeclareAcronym{PU}{  
2   long = Polyurethan ,  
3   long-plural = e  
4 }
```

and you use it the first time like this:

```
1 \ac{PU}-Hartschaum
```

then according to German orthography and typesetting rules this should be printed as

“Polyurethan(PU)-Hartschaum”

i. e., with *no* space between long and short form. This is exactly what happens if you say

```
1 \acsetup{activate-trailing-tokens = {dash,babel-hyphen}}
```

in the preamble.

7. About Page Ranges

If you enable the `page-style` option **ACRO** adds page numbers to the list of acronyms. In version 0.* it would add a page reference for an acronym in the list of acronyms that used `\pageref` to refer to the first appearance of an acronym. This is retained using `pages = {first}`. Version 1.0 uses a different approach that doesn't use a label but instead will list *all* pages an acronym appeared on. With `hyperref` the pages are referenced using `\hyperpage`.

There are some options that control how this list will be typeset, e.g., `following-page`, `next-pages` or the option `page-style` itself. It is important to mention that the page list will always take at least two compilation runs until changes in the options or the actual page numbers affect it. This is due to the fact that the updated sequence is first written to the aux file and only read in during the next run.

8. Dividing Your Document Into Pieces – Creating Local Lists

Introduced in
version 2.4

ACRO introduces the concept of *barriers* which can divide the document into parts. It is possible to create lists of only those acronyms used between two such barriers.

`\acbarrier`

Sets a barrier at the point of use in the document. The begin and the end of the document mark implicit barriers.

`use-barriers = true|false`

Default: `false`

Introduced in
version 2.5

If you want to use barriers and local lists you have to activate the feature first. This should be set in the preamble in order to work reliably. Make sure to watch out for log file messages asking you to rerun.

`reset-at-barriers = true|false`

Default: `false`

If this option is set to `true` `\acbarrier` implicitly calls `\acresetall`.

`local-to-barriers = true|false`

Default: `false`

This option can *only* be used as option to the `\printacronyms` command. It then prints a list of only the acronyms of the current "barrier group".

```

1 \acbarrier
2 \printacronyms[local-to-barriers]
3 \ac{ctan} and \ac{lppl}
4 \acbarrier

```

Acronyms

CTAN Comprehensive TeX Archive Network

LPPL L^AT_EX Project Public License

CTAN and LPPL

9. Language Support

ACRO detects if packages babel [Bra19] or polyglossia [Bra19] are being loaded and tries to adapt certain strings to match the chosen language. However, due to my limited language knowledge only a few translations are provided. I'll show how the English translations are defined so you can add the translations to your preamble if needed. Even better would be you'd send me a short email to contact@mychemistry.eu with the appropriate translations for your language and I'll add them to **ACRO**.

```
1 \DeclareTranslation{English}{acronym-list-name}{Acronyms}
2 \DeclareTranslation{English}{acronym-page-name}{p.}
3 \DeclareTranslation{English}{acronym-pages-name}{pp.}
4 \DeclareTranslation{English}{acronym-next-page}{f.}
5 \DeclareTranslation{English}{acronym-next-pages}{ff.}
```

10. hyperref Support

The option **hyperref** = {true} adds internal links from all short (or alternative) forms to their respective list entries. Of course this only works if you have loaded the hyperref package in your preamble. You should use this option with care: if you don't use **\printacronyms** anywhere this option will result in loads of hyperref warnings. Also printing several lists can result in warnings if don't clearly separate the lists into different classes. If an acronym appears in more than one list there will also be more than one hypertarget for this acronym.

Using hyperref will also add **\hyperpage** to the page numbers in the list (provided they are displayed in the style chosen). Like with an index the references will thus not point to the acronyms directly but to the page they're on.

11. Defining Own Acronym Macros

Introduced in
version 2.0

The commands explained in section 2.3 on page 7 have all been defined with a dedicated command – there is a family of dedicated commands, actually:

`\NewAcroCommand{\⟨cs⟩}{\⟨code⟩}`

Defines a new **ACRO** acronym command `\⟨cs⟩`. This sets up the necessary framework needed by acronym commands and defines `\⟨cs⟩` with an optional star argument and a mandatory argument for the acronym id using xparse's `\NewDocumentCommand`. Inside `\⟨code⟩` one can refer to the ID `\⟨id⟩` with `\#1`.

`\RenewAcroCommand{\⟨cs⟩}{\⟨code⟩}`

Defines a new **ACRO** acronym command `\⟨cs⟩`. This sets up the necessary framework needed by acronym commands and defines `\⟨cs⟩` with an optional star argument and a mandatory argument for the acronym id using xparse's `\RenewDocumentCommand`. Inside `\⟨code⟩` one can refer to the ID `\⟨id⟩` with `\#1`.

`\DeclareAcroCommand{\⟨cs⟩}{\⟨code⟩}`

Defines a new **ACRO** acronym command `\⟨cs⟩`. This sets up the necessary framework needed by acronym commands and defines `\⟨cs⟩` with an optional star argument and a mandatory argument for the acronym id using xparse's `\DeclareDocumentCommand`. Inside `\⟨code⟩` one can refer to the ID `\⟨id⟩` with `\#1`.

`\ProvideAcroCommand{\⟨cs⟩}{\⟨code⟩}`

Defines a new **ACRO** acronym command `\⟨cs⟩`. This sets up the necessary framework needed by acronym commands and defines `\⟨cs⟩` with an optional star argument and a mandatory argument for the acronym id using xparse's `\ProvideDocumentCommand`. Inside `\⟨code⟩` one can refer to the ID `\⟨id⟩` with `\#1`.

Inside these macros one can use a number of low-level `\Expl3` commands.¹³

Acronym fetching commands

`\acro_use:n {\⟨id⟩}`

Fetches the acronym using either the first or the short form depending on earlier uses.

`\acro_short:n {\⟨id⟩}`

Fetches the short form of the acronym.

`\acro_long:n {\⟨id⟩}`

Fetches the long form of the acronym.

`\acro_alt:n {\⟨id⟩}`

Fetches the alternative short form of the acronym.

`\acro_foreign:n {\⟨id⟩}`

Fetches the foreign property of the acronym if available.

`\acro_extra:n {\⟨id⟩}`

Fetches the extra property of the acronym if available.

¹³. Which is why you need to use them inside an `\Expl3` programming environment. This means in the preamble surround the definitions with `\ExplSyntaxOn` and `\ExplSyntaxOff`.

Acronym setup commands

`\acro_first_upper:`

ACRO setup command which tells the macros above that we want to uppercase the first letter of the long version. Should be used *before* one of the acronym fetching commands.

`\acro_plural:`

ACRO setup command which tells the macros above that we want to use plural forms. Should be used *before* one of the acronym fetching commands.

`\acro_indefinite:`

ACRO setup command which tells the macros above that we want to add the indefinite article. Should be used *before* one of the acronym fetching commands.

`\acro_cite:`

ACRO setup command which tells the macros above that we want to add the citation in any case independent of the option `cite`. Should be used *before* one of the acronym fetching commands.

`\acro_no_cite:`

ACRO setup command which tells the macros above that we want to have no citation independent of the option `cite`. Should be used *before* one of the acronym fetching commands.

`\acro_index:`

ACRO setup command which tells the macros above that we want to add an index entry in any case independent of the option `index`. Should be used *before* one of the acronym fetching commands.

`\acro_reset_specials:`

Introduced in
version 2.0b

This macro is called implicitly by `\NewAcroCommand` and `\NewPseudoAcroCommand`. If you plan to define an **ACRO** command by yourself using `\NewDocumentCommand` this should be the first macro after `\acro_begin:`. It ensures that in nested acronyms the inner acronyms don't inherit indefinite articles, uppercasing, endings...

Additional macros for further uses

`\acro_begin:`

When an acronym macro is defined “by hand”, *i.e.*, *not using* `\NewAcroCommand` then this must be the first macro in the code. *Must have a matching \acro_end:*.

`\acro_end:`

When an acronym macro is defined “by hand”, *i.e.*, *not using* `\NewAcroCommand` then this must be the last macro in the code. *Must have a matching \acro_begin:*.

`\acro_check_and_mark_if:nn {<boolean expression>} {<id>}`

Checks if the acronym with the ID `<id>` exists and marks it as used when `<boolean>` expression evaluates to `true`. This macro is used inside `\NewAcroCommand` and friends implicitly.

`\acro_check_acronym:nn {⟨id⟩} {true|false}`

Checks if the acronym with the ID `⟨id⟩` exists and marks it as used if `true` or doesn't. This macro is used inside `\acro_check_and_mark_if:nn`.

`\acro_use_acronym:n {true|false}`

Tell `\acro_use:n` and similar commands whether to mark the acronym as used or not. This macro is used inside `\acro_check_acronym:nn`. If this macro is used explicitly it should be used before `\acro_use:n` (or a similar command) otherwise it has no effect. An acronym marked as used cannot be unmarked.

`\acro_mark_as_used:n {⟨id⟩}`

Explicitly use the acronym with the ID `⟨id⟩`. This is the `expl3` macro applied to all entries in `\acuse`.

* `\acro_if_acronym_used:nTF {⟨id⟩} {⟨true⟩} {⟨false⟩}`

The code-level version of `\acifused`. This macro is expandable.

`\acro_for_all_acronyms_do:n {⟨code⟩}`

Loops over all acronyms known when the macro is used. Inside of `⟨code⟩` you can refer to the ID `⟨id⟩` of an acronym with `#1`.

`\acro_barrier:`

The code-level version of `\acbarrier`.

`\acro_switch_off:`

The `expl3` version of `\acswoff`.

Introduced in
version 2.6

`\acro_switch_on:`

The `expl3` version of `\acswon`.

Introduced in
version 2.6

`\acro_add_action:n {⟨code⟩}`

Adds code to `\acro_get:n`. Inside of `⟨code⟩` you can refer to the ID of the acronym with `#1`. The `\acro_get:n` command is called the first macro that is called by `\acro_use:n` which for example enables conditionals to test for certain acronym properties.

`\acro_get_property:nnTF {⟨id⟩} {⟨property⟩} {⟨true⟩} {⟨false⟩}`

Fetches the property `⟨property⟩` of the acronym `⟨id⟩` and stores it in a tokenlist variable `\l__acro_⟨property⟩_tl` where all dashes in the property names are replaced with underscores. `⟨true⟩` is placed in the input stream if the property had been set, `⟨false⟩` otherwise.

`\acro_get_property:nn {⟨id⟩} {⟨property⟩}`

Like `\acro_get_property:nnTF`, but without the `⟨true⟩` and `⟨false⟩` arguments.

Introduced in
version 2.7

`\acro_if_property:nnTF {⟨id⟩} {⟨property⟩} {⟨true⟩} {⟨false⟩}`

Checks if the property `⟨property⟩` of the acronym `⟨id⟩` is set and places `⟨true⟩` in the input stream if yes and `⟨false⟩` otherwise.

Introduced in
version 2.7

Examples The usage of above macros is best explained with a few examples. The following definition is done by **ACRO**:

```
1 \NewAcroCommand \ac { \acro_use:n {#1} }
```

An equivalent definition for **\ac** would be

```
1 \NewDocumentCommand \ac {sm}
2 {
3     \acro_begin:
4         \acro_reset_specials:
5         \acro_check_and_mark_if:nn {#1} {#2}
6         \acro_use:n {#2}
7     \acro_end:
8 }
```

which should explain what the actual framework is which **\NewAcroCommand** adds.

Other definitions by **ACRO** are for example the following ones:

```
1 \NewAcroCommand \Ac
2 {
3     \acro_first_upper:
4     \acro_use:n {#1}
5 }
6 \NewAcroCommand \iac
7 {
8     \acro_indefinite:
9     \acro_use:n {#1}
10 }
11 \NewAcroCommand \acp
12 {
13     \acro_plural:
14     \acro_use:n {#1}
15 }
16 \NewAcroCommand \Acp
17 {
18     \acro_plural:
19     \acro_first_upper:
20     \acro_use:n {#1}
```

```
21     }
22 \NewAcroCommand \Aclp
23 {
24     \acro_plural:
25     \acro_first_upper:
26     \acro_long:n {\#1}
27 }
```

12. About Plural Forms, Possessive Forms and Similar Constructs – the Concept of Endings

ACRO has a concept of *endings*. All of ACRO's plural options are defined by saying

```
1 \ProvideAcroEnding {plural} {s} {s}
```

The command's syntax and what it does is as follows:

\ProvideAcroEnding{<name>}{<short default>}{<long default>}

This macro defines the options

- <name>-ending,
- short-<name>-ending,
- alt-<name>-ending,
- long-<name>-ending and
- foreign-<name>-ending.

It also defines the acronym properties

- short-<name>,
- short-<name>-form,
- alt-<name>,
- alt-<name>-form,
- long-<name>,
- long-<name>-form,
- foreign-<name> and
- foreign-<name>-form.

12. About Plural Forms, Possessive Forms and Similar Constructs – the Concept of Endings

Changed in
version 2.4b

Additionally it defines a setup macro as described in section 11 on page 29, `\acro_{name}`:. If `\acro_{name}` contains a - (dash) it is replaced by _ before `\acro_{name}`: is built. So if you choose `my-name` the corresponding macro is named `\acro_my_name`:. If you use any other non-letters you are on your own. If you use the command with the same `\acro_{name}` a second time the command only resets the defaults.

Note that you *must use* `\ProvideAcroEnding` before any acronym definition!

This could be used together with the macros described in section 11 on page 29 for adding support for possessive forms:

```
1 \ExplSyntaxOn
2 % this now only works because I've used the same already in the preamble so
3 % it does nothing here:
4 \ProvideAcroEnding {possessive} {'s} {'s}
5
6 \ProvideAcroCommand \acg
7 {
8     \acro_possessive:
9     \acro_use:n {#1}
10 }
11 \ExplSyntaxOff
12 The \acg{cd} booklet says\ldots
```

The CD's booklet says...

Please note that different endings are cumulative which you probably want to avoid! Imagine a macro

```
1 \NewAcroCommand \acgp
2 {
3     \acro_possessive:
4     \acro_plural:
5     \acro_use:n {#1}
6 }
```

This would give “cd’s” instead of “cds”. To solve this you might want to consider

```

1 \ProvideAcroEnding {possessive-singular} {'s} {'s}
2 \ProvideAcroEnding {possessive-plural} {s'} {s'}

```

13. More on Customization

13.1. Background Information

Several of **ACRO**'s objects are customized using templates. For each of these objects it is possible to define own templates.¹⁴ Possibly more interesting: it is easily possible to define further instances of an object using a certain template. How this works is explained in the following sections. However, the basics are always the same. There is a command

`\DeclareAcro<object type>Style{<name>}{{<template>}}{<options>}`

which allows to define a new style (*i. e.*, instance) for the object `<object type>` using the template `{<template>}`.

13.2. Lists

13.2.1. Own List Style

The different existing list styles are all built from four different templates, `list`, `list-of`, `table` and `extra-table`. Those templates are defined with the help of the `xtemplate` package (from [L3P]). Each of these templates has a few options which are described in table 1 on the following page. New list styles now are defined via the following macro:

`\DeclareAcroListStyle{<name>}{{<template>}}{<options>}`

Declares a new **ACRO** list style `<name>`. `<name>` will be the value which can be chosen in the option `list-style`. `<template>` is the name of the template to be used by the style. Available templates are listed in table 1. `<options>` are the option settings for the corresponding template.

For defining new styles you need some information on what the different templates and options do:

- The option `list` of the `list` template sets the list environment. This must be a classic `LATEX` list where items are listed with `\item`. In those lists short entries will always be fed as optional argument to `\item`:
`\item[<short>]<long><extra><page>`
- The template `list-of` simulates a table of contents or a list of figures. This can be chosen by setting the option `style` to either `toc` or `lof`.

¹⁴. This requires some knowledge of `xtemplate` and `expl3`. Plans are to provide a documented interface for users of **ACRO** in the future.

TABLE 1: Available List Templates and Their Options

Template	Option	Option Type	Default
list	list	tokenlist	description
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	
list-of	style	tokenlist	toc
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	
table	table	tokenlist	tabular
	table-spec	tokenlist	lp{.7\linewidth}
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	
extra-table	table	tokenlist	tabular
	table-spec	tokenlist	llll
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	

- The template `table` typesets the list in a table with two columns:
 $\langle short \rangle \ \& \ \langle long \rangle \langle extra \rangle \langle page \rangle \ \backslash tabularnewline$
- The template `extra-table` typesets the list in a table with four columns:
 $\langle short \rangle \ \& \ \langle long \rangle \ \& \ \langle extra \rangle \ \& \ \langle page \rangle \ \backslash tabularnewline$
- The option `foreign-sep` is the code inserted between long form and foreign entry (if a foreign entry is present).
- The options `before` and `after` are inserted directly before and after the complete list.
- The option `reverse` switches the place of $\langle long \rangle$ with $\langle extra \rangle$.
- The option `table-spec` sets the column types for the table templates. It must correspond to the number of columns the corresponding template uses.

As an example let's define a style `longtabu` which uses the corresponding table environment from the package `tabu` [Che19]:

```

1 \usepackage{tabu,longtable}
2 \DeclareAcroListStyle{longtabu}{table}{
3   table = longtabu ,
4   table-spec = @{}>{\bfseries}{lX@{}}
5 }
6 \acsetup{list-style=longtabu}
```

As another example let's define a new list with the help of the `enumitem` package [Bez19]:

```

1 % preamble:
2 % \usepackage{enumitem}
3 \newlist{acronyms}{description}{1}
4 \newcommand*\addcolon[1]{#1:}
5 \setlist[acronyms]{
6   labelwidth = 3em,
7   leftmargin = 3.5em,
8   noitemsep,
9   itemindent = 0pt,
10  font=\addcolon}
11 \DeclareAcroListStyle{mystyle}{list}{ list = acronyms }
12 \acsetup{ list-style = mystyle }
```

This would look as follows:

Acronyms

CD:	Compact Disc
CTAN:	Comprehensive TeX Archive Network
ECU:	Steuergerät (Electronic Control Unit)
ID:	identification string
JPEG:	Joint Photographic Experts Group
LA:	Los Angeles
LPPL:	LATeX Project Public License
MP:	Member of Parliament
NATO:	North Atlantic Treaty Organization. <i>deutsch:</i> Organisation des Nordatlantikvertrags
NY:	New York
PDF:	Portable Document Format
SW:	Sammelwerk
ST:	Some Test
UFO:	unidentified flying object

13.2.2. Own List Heading Command

With the option `list-heading` you can choose which command prints the heading of the list. If you need a different choice than what's already provided you can use the following command to define a new option:

```
\DeclareAcroListHeading{\<name>}{\<control sequence>}
```

Defines a new value `<name>` for the option `list-heading`. `<control sequence>` must be a control sequence which takes one mandatory argument.

As an example here is how the value `section` is defined:

```
1 \DeclareAcroListHeading{section}{\section}
```

13.3. First Styles

The first styles define how an acronym is typeset when it is used for the first time. It is set with the option `first-style`. Legal values for this option are defined with the following command:

```
\DeclareAcroFirstStyle{\<name>}{\<template>}{\<options>}
```

Declares a new `ACRO` first style `<name>`. `<name>` will be the value which can be chosen in the option `first-style`. `<template>` is the name of the template to be used by the style. Available templates are listed in table 2. `<options>` are the option settings for the corresponding template.

Here are two examples of the already available styles and how they are defined:

```

1 \DeclareAcroFirstStyle{short}{inline}{
2   only-short = true ,
3   brackets    = false
4 }
5 \DeclareAcroFirstStyle{sidenote-reversed}{note}{
6   note-command = \sidenote{#1} ,
7   reversed      = true
8 }

```

TABLE 2: Available First Style Templates and Their Options

Template	Option	Option Type	Default
inline	brackets	boolean	true
	brackets-type	tokenlist	()
	only-short	boolean	false
	only-long	boolean	false
	reversed	boolean	false
	between	tokenlist	
	foreign-sep	tokenlist	,~
note	use-note	boolean	true
	note-command	function	\footnote{#1}
	reversed	boolean	false
	foreign-sep	tokenlist	,~

13.4. Extra Styles

The extra styles define how the extra information of an acronym is typeset in the list. It is set with the option `extra-style`. Legal values for this option are defined with the following command:

`\DeclareAcroExtraStyle{<name>}{{<template>}}{<options>}`

Declares a new **ACRO** extra style `<name>`. `<name>` will be the value which can be chosen in the option `extra-style`. `<template>` is the name of the template to be used by the style. Available templates are listed in table 3. `<options>` are the option settings for the corresponding template.

Here are two examples of the already available styles and how they are defined:

```

1 \DeclareAcroExtraStyle{default}{inline}{
2   brackets    = false ,

```

TABLE 3: Available Extra Style Templates and Their Options

Template	Option	Option Type	Default
inline	punct	boolean	true
	punct-symbol	tokenlist	,
	brackets	boolean	true
	brackets-type	tokenlist	()

```

3   punct      = true ,
4   punct-symbol = .
5 }
6 \DeclareAcroExtraStyle{paren}{inline}{
7   brackets    = true ,
8   punct       = true ,
9   punct-symbol =
10 }
```

13.5. Page Number Styles

The page number styles define how the page numbers where acronyms have been used are typeset in the list. It is set with the option `page-style`. Legal values for this option are defined with the following command:

```
\DeclareAcroPageStyle{\<name>}{\<template>}{\<options>}
```

Declares a new `ACRO` extra style `<name>`. `<name>` will be the value which can be chosen in the option `page-style`. `<template>` is the name of the template to be used by the style. Available templates are listed in table 4. `<options>` are the option settings for the corresponding template.

Here are two examples of the already available styles and how they are defined:

```

1 \DeclareAcroPageStyle{default}{inline}{
2   punct = true ,
3   punct-symbol = .
4 }
5 \DeclareAcroPageStyle{paren}{inline}{
6   brackets=true ,
7   punct-symbol = ~
8 }
```

Introduced in
version 2.2

13.6. Configuration Files

If you repeatedly have the same setup and definitions for **ACRO** in your preamble¹⁵ you might want to place those in a configuration file. If **ACRO** finds a file named `acro.cfg` present it inputs it at the end of the package. The only thing to be aware of is that this file is input like a package which means that @ is treated as a letter (category code 11).

A. All Acronyms Used in this Documentation

CD Compact Disc, pp. 8, 10, 35

CTAN Comprehensive TeX Archive Network, pp. 2, 28

ECU Steuergerät (Electronic Control Unit), p. 12

ID identification string, pp. 2, 4 f., 13, 15, 20 f., 29 ff.

JPEG Joint Photographic Experts Group, p. 10

LA Los Angeles, p. 14

LPPL L^AT_EX Project Public License, pp. 2, 28

MP Member of Parliament, p. 10

NATO North Atlantic Treaty Organization, *deutsch*: Organisation des Nordatlantikvertrags, pp. 11, 22

NY New York, pp. 6, 10, 14 f., 22 f.

PDF Portable Document Format, pp. 5, 16 f.

SW Sammelwerk, p. 10

¹⁵. For example defining new endings, **ACRO** commands, list styles, ...

TABLE 4: Available Page Number Style Templates and Their Options

Template	Option	Option Type	Default
inline	display	boolean	true
	punct	boolean	false
	punct-symbol	tokenlist	,
	brackets	boolean	false
	brackets-type	tokenlist	()
	space	skip	.333333em plus .166666em minus .111111em

B. References

ST Some Test, p.5

UFO unidentified flying object, p.13

B. References

- [Bez19] Javier BEZOS. enumitem. version 3.9, June 20, 2019 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/enumitem/>.
- [Bra19] Johannes BRAAMS, current maintainer: Javier BEZOS.
babel. version 3.33, July 19, 2019 (or newer).
URL: <http://mirror.ctan.org/macros/latex/required/babel/>.
- [Car19] David CARLISLE. longtable. version 4.12, Feb. 6, 2019 (or newer).
URL: <http://mirror.ctan.org/macros/latex/required/tools/>.
- [Cha19] François CHARETTE, current maintainer: Arthur REUTENAUER.
polyglossia. version 1.44, Apr. 4, 2019 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/polyglossia/>.
- [Che19] Florent CHERVET. tabu. version 2.8+, Jan. 12, 2019 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/tabu/>.
- [Kle18] Josef KLEBER. pdfcomment. version 2.4a, Nov. 1, 2018 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/pdfcomment/>.
- [L3P] THE LATEX3 PROJECT TEAM. l3packages. Sept. 19, 2019 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/l3packages/>.
- [Nie17] Clemens NIEDERBERGER. translations. version 1.7a, Aug. 31, 2017 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/translations/>.
- [Tal17] Nicola L.C. TALBOT. mfistuc. version 2.06, Nov. 14, 2017 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/glossaries/>.
- [Wik12] WIKIPEDIA. *New York City*. 2012.
URL: http://en.wikipedia.org/wiki/New_York_City (visited on 09/27/2012).

C. Index

A	
\Ac	7, 13, 22, 33
\ac	4, 7 ff., 11 f., 15 f., 20, 23, 27 f., 33
\Aca	8
\aca	7 ff., 11
\Acap	8
\acap	8
\acbarrier	28, 32
accsupp	5, 17, 22
accsupp (package)	5, 17, 22
\acdot	26 f.
\Acf	8
\acf	4, 8 f., 20, 23 f.
\acffirstupper	13, 22
\acflike	4, 14, 20, 23
\Acfp	8
\acffp	8
\acflike	14
\acg	35
\aciffirst	15
\aciftrailing	26
\acifused	15, 32
\Acl	7
\acl	7 ff., 15
\Aclp	8, 34
\aclp	8 ff.
\Acp	8, 13, 22, 33
\acp	8, 33
\acpdfstring	16
\acpdfstringplural	16
\acreset	15
\acresetall	15, 28
\acroenparen	12, 23
\AcroRegisterTrailing	25 f.
\Acs	7, 13
\acs	7 ff., 11, 15 f.
\acsetup	14, 19, 22, 24, 27, 38
\Acsingle	14
\acsingle	14
\Acsp	8, 13
\acsp	8 ff., 16
\acspace	26 f.
\acsitchoff	16, 32
\acsitchon	16, 32
activate-trailing-tokens	26
\acuse	16, 32
\acuseall	16
\alt	4, 7, 10
\alt-format	4
\alt-indefinite	4, 13
\alt-plural	3
\alt-plural-form	3
B	
babel (package)	4, 12, 29
BEZOS, Javier	4, 12, 29, 38
BRAAMS, Johannes	4, 12, 29
C	
CARLISLE, David	25
CD	9 f., 35
CHARETTE, François	4, 12
CHERVET, Florent	38
\cite	4, 6, 21, 31
\cite-cmd	21
\cite-connect	21
\class	4, 14
CTAN	2, 29
D	
deactivate-trailing-tokens	26
\DeclareAcroCommand	30
\DeclareAcroExtraStyle	40 f.
\DeclareAcroFirstStyle	39 f.
\DeclareAcroListHeading	39
\DeclareAcroListStyle	36, 38
\DeclareAcronym	2, 5 ff., 9–12, 14, 16 f., 20, 27
\DeclareAcroPageStyle	41
\display-foreign	21
E	
ECU	12
enumitem (package)	38

exclude-classes	18	L		
expl3 (package)	2	l3experimental (package)	21	
extra	4, 11	l3keys2e (package)	2	
extra-format	23	l3packages (bundle)	36	
extra-style	23, 40	l3sort (package)	21	
F				
first-long-format	4, 23	LA	15	
first-style	5, 13 f., 23, 39	label	20, 24	
following-page	24 f., 28	label-prefix	20	
following-pages	24 f.	list	3	
following-pages*	25	list-caps	25	
foreign	4, 12, 21 ff.	list-foreign-format	23	
foreign-format	22	list-heading	25, 39	
foreign-lang	4, 12	list-long-format	23	
foreign-plural	3	list-name	25	
foreign-plural-form	3	list-short-format	23	
format	5	list-short-width	23	
format-include-endings	10	list-style	25, 36	
G				
group-citation	21	local-to-barriers	18, 28	
group-cite-cmd	21	log	6 f.	
group-cite-connect	21	long	3, 12, 17	
H				
heading	18	long-format	4, 22 f.	
hyperref	20, 29	long-indefinite	3, 13	
hyperref (package)	5, 16, 28 f.	long-plural	3, 9	
I				
\Iac	13	long-plural-form	3, 9	
\iac	33	long-post	3	
\iacl	13	long-pre	3	
\iacs	13	longtable (package)	25	
ID	3 ff., 14 f., 20 f., 30 ff.	LPPL	2	
include-classes	18	M		
index	5, 18, 21, 31	macros	20 f.	
index-cmd	5, 21	\makefirstuc	13	
index-sort	5, 18	mark-as-used	20	
J				
JPEG	11	messages	20	
K				
KLEBER, Josef	17	mfirstruc (package)	13, 22	
N				
name	18	MP	10	
NATO	11, 22	N		
New York City	6, 14 f., 24	name	18	
\NewAcroCommand	30 f., 33 ff.	NATO	11, 22	
\NewPseudoAcroCommand	31	New York City	6, 14 f., 24	
next-page	24 f.	\NewAcroCommand	30 f., 33 ff.	

- next-pages 24 f., 28
NIEDERBERGER, Clemens 2
NY 6, 10, 14 f., 22, 24
- O**
only-used 20
OT 6
- P**
page-name 24
page-style 24, 28, 41
pages 24, 28
pages-name 24
PDF 5, 16 f.
pdfcomment (package) 17, 22
pdfstring 5, 16
plural-ending 23
polyglossia (package) 4, 12, 29
post 4
\printacronyms 1, 18 f., 28 f.
\ProvideAcroCommand 30, 35
\ProvideAcroEnding 34 ff.
- R**
\RenewAcroCommand 30
reset-at-barriers 28
REUTENAUER, Arthur 4, 12
- S**
short 2, 5
short-format 4, 22 f.
short-indefinite 3, 13
short-plural 3, 9
- short-plural-form 3
single 1, 4, 14, 20 f.
single-form 20, 23
single-format 5, 23
sort 1, 4 f., 18, 21
strict 21
SW 10
- T**
tabu (package) 38
TALBOT, Nicola L.C. 13
ST 5
THE LATEX3 PROJECT TEAM 36
tooltip 5, 17, 22
tooltip-cmd 5, 17, 22
translations (package) 2
- U**
uc-cmd 13, 22
UFO 13
uppercase-short 7 f., 13, 22
use-barriers 28
- W**
WIKIPEDIA 6, 14 f., 24
- X**
xparse (package) 2, 30
xspace 20
xtemplate (package) 2, 36
- Z**
zref-abspage (package) 2