

The `altsupsub` package*

Julien Labb  

`Julien.Labbe@univ-grenoble-alpes.fr`

January 23, 2022

Abstract

A LATEX package to write alternative and customisable subscripts and superscripts, with square brackets.

Typical use:

$$\begin{aligned} \text{x_}\{\text{roman}\}\text{^}\{\text{italic}\} &\longrightarrow x_{\text{roman}}^{\text{italic}} \\ \text{x_}\{\text{italic}\}\text{^}\{\text{roman}\} &\longrightarrow x_{\text{italic}}^{\text{roman}} \end{aligned}$$

Contents

1	Introduction	2
2	Motivations	2
3	Usage	2
4	Options	3
5	Example	3
6	Known issues	4
7	Alternatives	4
8	Implementation	4

*This document corresponds to `altsupsub` v1.0, dated 2022/01/23.

1 Introduction

The `altsupsub` package allows to write alternate subscripts and superscripts, in math mode, with square brackets :

`x_[my subscript]` or `x^*[my superscript]`.

These alternate superscripts and superscripts are formatted by the commands set, respectively, with `\SetAltSubscriptCommand` and `\SetAltSuperscriptCommand`. By default, the `\text` command, from `amstext` (part of `amsmath`) is used. This gives:

$x_{\text{my subscript}}$ or $x^{\text{my superscript}}$.

This package redefine `_` and `^` symbols. Options allow to redefine both (by default), only subscript `_` symbol, or only superscript `^` symbol.

2 Motivations

Common typographic conventions¹ use italic (sloping) type for physical quantities or mathematical variables and roman (upright) type for words or fixed numbers. For example, heat capacity at constant pressure should be printed C_P , but kinetic energy E_k (instead of E_k) and relative permeability μ_r (instead of μ_r). This can be obtained in L^AT_EX with `E_{\mathit{k}}` and `\mu_{\mathit{r}}`. This package allows to write them simply `E_[k]` and `\mu_[r]`.

3 Usage

`\SetAltSubscriptCommand{<cmd>}`

Set the command `<cmd>` used to format square brackets subscripts `_ [...]`. By default, `<cmd>` is the `\text` command, provided by the `amstext` package (part of `amsmath` package).

`\SetAltSuperscriptCommand{<cmd>}`

Set the command `<cmd>` used to format square brackets superscripts `^ [...]`. By default, `<cmd>` is the `\text` command, provided by the `amstext` package (part of `amsmath` package).

`\SetAltSubSupCommands{<cmd>}`

Set both square brackets subscripts and square brackets superscripts, with the same command `<cmd>`.

¹See, for example: International Organization for Standardization. (2009). *Quantities and units - Part 1: General* (ISO Standard No. 80000-1:2009). <https://www.iso.org/standard/30669.html>.

4 Options

To load the package, add in your preamble:

```
\usepackage[<option>]{altsupsub}
```

Available values for *<option>*:

subscript redefine only the $_$ subscript symbol.
superscript redefine only the $^$ superscript symbol.
both redefine both $_$ and $^$ symbols (default).

5 Example

The following input:

```
Default:  
\begin{displaymath}  
x_a^b \quad  
x_{braces sub}^{braces sup} \quad  
x_{brackets sub}^{brackets sup} \quad  
x_{braces sub}^{brackets sup} \quad  
x_{brackets sub}^{brackets sup}  
\end{displaymath}  
  
New formats:  
% \text from amstext package  
% \color from xcolor package  
\newcommand{\bluecolor}[1]{\text{\color{blue}#1}}  
\newcommand{\redcolor}[1]{\text{\color{red}#1}}  
\SetAltSubscriptCommand{\bluecolor}  
\SetAltSuperscriptCommand{\redcolor}  
\begin{displaymath}  
x_a^b \quad  
x_{braces sub}^{braces sup} \quad  
x_{brackets sub}^{brackets sup} \quad  
x_{braces sub}^{brackets sup} \quad  
x_{brackets sub}^{brackets sup}  
\end{displaymath}  
  
Same command for subscripts and superscripts:  
\SetAltSubSupCommands{\mathbf}  
\begin{displaymath}  
x_a^b \quad  
x_{braces sub}^{braces sup} \quad  
x_{brackets sub}^{brackets sup} \quad  
x_{braces sub}^{brackets sup} \quad  
x_{brackets sub}^{brackets sup}  
\end{displaymath}
```

gives:

Default:

x_a^b $x_{bracesup}^{bracesup}$ $x_{brackets sub}^{bracesup}$ $x_{bracesub}^{brackets sup}$ $x_{brackets sub}^{brackets sup}$

New formats:

x_a^b $x_{bracesup}^{bracesup}$ $x_{\text{brackets sub}}^{bracesup}$ $x_{bracesub}^{\text{brackets sup}}$ $x_{\text{brackets sub}}^{\text{brackets sup}}$

Same command for subscripts and superscripts:

x_a^b $x_{bracesup}^{bracesup}$ $x_{\text{bracketssub}}^{bracesup}$ $x_{bracesub}^{\text{bracketssup}}$ $x_{\text{bracketssub}}^{\text{bracketssup}}$

6 Known issues

The use of the prime symbol ' can raise the *Double superscript* error message. This is normally fixed (x'^2 gives x'^2 correctly). If needed, enclose the expression with $\{\dots\}$. In particular, $x'^{[sup]}$ doesn't work, and should be written: $\{x'\}^{[sup]}$.

7 Alternatives

Two other packages give similar functionalities:

the subtext package (<https://www.ctan.org/pkg/subtext>), by Palle Jørgensen, formats $_{[\dots]}$ subscripts with $\text{\texttt{text}}$ (the differences, is that the `altsupsub` package works both for subscripts and superscripts, allows to customise the commands, and redefine symbols only in math mode);

the spbmark package (<https://www.ctan.org/pkg/spbmark>), by Qu Yi, allows a complete customisation of subscripts and superscripts.

8 Implementation

Package declaration

```
1 \ProvidesPackage{altsupsub}[2022/01/23, v1.0, Alternative and customisable  
2 subscripts and superscripts, with square brackets.]
```

Flags declaration

Determine the commands that will be redefined.

```
3 \newif\ifaltsbsp@subscript \altsbsp@subscripttrue  
4 \newif\ifaltsbsp@superscript \altsbsp@superscripttrue
```

Options declarations and processing

```
5 \DeclareOption{subscript} {\altsbsp@subscripttrue \altsbsp@superscriptfalse}
6 \DeclareOption{superscript} {\altsbsp@subscriptfalse \altsbsp@superscripttrue }
7 \DeclareOption{both} {\altsbsp@subscripttrue \altsbsp@superscripttrue }
8 \DeclareOption*{\PackageWarning{altsup}{Unknown option \CurrentOption.}}
9 \ProcessOptions\relax
```

Redefine catcodes and make symbols active in mathmode

```
10 \AtBeginDocument{%
11   \ifaltsbsp@subscript \catcode`\_=12 \mathcode`\_="8000 \fi%
12   \ifaltsbsp@superscript \catcode`\^=12 \mathcode`\^="8000 \fi%
13 }
```

Redefinition of the subscript symbol

```
14 \ifaltsbsp@subscript%
15 \begingroup\lccode`\~=`\_\lowercase{\endgroup%
16 \def`}{\ifnextchar[% dummy bracket ]
17 {\altsbsp@subwrapper}% bracket wrapper
18 {\sb}}% standard form
19 }%
20 \fi
```

Redefinition of the superscript symbol

```
21 \ifaltsbsp@superscript%
22 \begingroup\lccode`\~=`\^\lowercase{\endgroup%
23 \def`}{\ifnextchar[% dummy bracket ]
24 {\altsbsp@supwrapper}% bracket wrapper
25 {\sp}}% standard form
26 }%
27 \fi
```

User macros

```
\SetAltSubscriptCommand
28 \def\SetAltSubscriptCommand#1{\let\altsbsp@altsubcmd#1}%
29 \def\altsbsp@subwrapper[#1]{\sb{\altsbsp@altsubcmd{#1}}}%
```

```
\SetAltSuperscriptCommand
30 \def\SetAltSuperscriptCommand#1{\let\altsbsp@altsupcmd#1}%
31 \def\altsbsp@supwrapper[#1]{\sp{\altsbsp@altsupcmd{#1}}}%
```

```
\SetAltSubSupCommands
32 \newcommand{\SetAltSubSupCommands}[1]{%
33   \SetAltSubscriptCommand{#1}%
34   \SetAltSuperscriptCommand{#1}%
35 }
```

Set default commands

```
36 \RequirePackage{amstext}%
37 \SetAltSubSupCommands{\text}{}
```

Fix prime symbol

```
38 \ifaltsbsp@superscript%
39 \begingroup \catcode`^=12%
40 \gdef\altsbsp@pr@m@s{\% copy of \pr@m@s code from latex.ltx
41   \ifx`\@let@token
42     \expandafter\pr@ccs
43   \else
44     \ifx`^@\let@token
45       \expandafter\expandafter\expandafter\pr@cc@t
46     \else
47       \egroup
48     \fi
49   \fi}
50 \endgroup
51 \let\pr@m@s\altsbsp@pr@m@s
52 \fi
```

End of the package

```
53 \endinput
```

Change History

v1.0

General: Initial version 1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	\altsbsp@subscriptfalse	\altsbsp@supwrapper
\pr@m@s	40	6 24, 31
\~	15, 22	\altsbsp@subscripttrue 3, 5, 7
A	\altsbsp@subwrapper	C
\altsbsp@altsubcmd	17, 29	\CurrentOption 8
. 28, 29	\altsbsp@supscriptfalse	
\altsbsp@altsupcmd	5	D
. 30, 31	\altsbsp@supscripttrue	
\altsbsp@pr@m@s 40, 51	4, 6, 7	\DeclareOption 5–8

I	R	S
\ifaltsbsp@subscript	\pr@@@s	42
3, 11, 14	\pr@@@t	45
\ifaltsbsp@superscript	\pr@m@s	51
4, 12, 21, 38	\ProcessOptions	9
	\ProvidesPackage ...	1
P	R	S
\PackageWarning	\RequirePackage ...	36
		\SetAltSuperscriptCommand
	 <u>30</u> , 34