

COLORIST, WRITE YOUR ARTICLES OR BOOKS IN A COLORFUL WAY

JINWEN XU
ProjLib@outlook.com

July 2021, Beijing

ABSTRACT

colorist is a series of styles and classes for you to typeset your articles or books in a colorful manner. The original intention in designing this series was to write drafts and notes that look colorful yet not dazzling. With the help of the ProjLib toolkit, also developed by the author, the classes provided here have multi-language support, preset theorem-like environments with clever reference support, and many other functionalities. Notably, using these classes, one can organize the author information in the $\mathcal{A}\mathcal{M}\mathcal{S}$ fashion, makes it easy to switch to journal classes later for publication.

Finally, this documentation is typeset using the colorart class (with the option `allowbf`). You can think of it as a short introduction and demonstration.

CONTENTS

Before you start	1
1 Introduction	2
2 Usage and examples	2
2.1 How to load it	2
2.2 Example - colorart	2
2.3 Example - colorbook	5
3 The options	6
4 Instructions by topic	7
4.1 Language configuration	7
4.2 Theorems and how to reference them	7
4.3 Define a new theorem-like environment	8
4.4 Draft mark	9
4.5 Title, abstract and keywords	10
5 Known issues	10

BEFORE YOU START

In order to use the package or classes described here, you need to:

- install TeX Live or MikTeX of the latest possible version, and make sure that colorist and projlib are correctly installed in your T_EX system.
- be familiar with the basic usage of L^AT_EX, and knows how to compile your document with pdfL^AT_EX, X_YL^AT_EX or LuaL^AT_EX.

Corresponding to: colorist 2021/07/15

1 INTRODUCTION

colorist is a series of styles and classes for you to typeset your articles or books in a colorful manner. The original intention in designing this series was to write drafts and notes that look colorful yet not dazzling.

The entire collection includes `colorist.sty`, which is the main style shared by all of the following classes; `colorart.cls` for typesetting articles and `colorbook.cls` for typesetting books. They compile with any major \TeX engine, with native support to English, French, German, Italian, Portuguese (European and Brazilian) and Spanish typesetting via `\UseLanguage` (see the instruction below for detail).

You can also found `lebhart` and `beaulivre` on CTAN. They are the enhanced version of `colorart` and `colorbook` with unicode support. With this, they can access to more beautiful fonts, and additionally have native support for Chinese, Japanese and Russian typesetting. On the other hand, they need to be compiled with \XeLaTeX or \LuaLaTeX (not \pdfLaTeX).

With the help of the `ProjLib` toolkit, also developed by the author, the classes provided here have multi-language support, preset theorem-like environments with clever reference support, and many other functionalities such as draft marks, enhanced author information block, mathematical symbols and shortcuts, etc. Notably, using these classes, one can organize the author information in the \mathcal{AMS} fashion, makes it easy to switch to journal classes later for publication. For more detailed information, you can refer to the documentation of `ProjLib` by running `texdoc projlib` in the command line.

2 USAGE AND EXAMPLES

2.1 HOW TO LOAD IT

You can directly use `colorart` or `colorbook` as your document class. In this way, you can directly begin writing your document, without having to worry about the configurations.

```
\documentclass{colorart} or \documentclass{colorbook}
```

TIP

You may wish to use `lebhart` or `beaulivre` instead, which should produce better result. All the examples later using `colorart` or `colorbook` can be adopted to `lebhart` and `beaulivre` respectively, without further modification.

You can also use the default classes `article` or `book`, and load the `colorist` package. This way, only the basic styles are set, and you can thus use your preferred fonts and page layout. All the features mentioned in this article are provided.

```
\documentclass{article} or \documentclass{book}
\usepackage{colorist}
```

2.2 EXAMPLE - COLORART

Let's first look at a complete example of `colorart` (the same works for `lebhart`).

```
1 \documentclass{colorart}
2 \usepackage{ProjLib}
3
4 \UseLanguage{French}
5
6 \begin{document}
7
8 \title{\langle title \rangle}
9 \author{\langle author \rangle}
```

```

10 \date{\PLdate{2022-04-01}}
11
12 \maketitle
13
14 \begin{abstract}
15     Ceci est un résumé. \dnf<Plus de contenu est nécessaire.>
16 \end{abstract}
17 \begin{keyword}
18     AAA, BBB, CCC, DDD, EEE
19 \end{keyword}
20
21 \section{Un théorème}
22
23 \begin{theorem}\label{thm:abc}
24     Ceci est un théorème.
25 \end{theorem}
26 Référence du théorème: \cref{thm:abc}
27
28 \end{document}

```

If you find this example a little complicated, don't worry. Let's now look at this example piece by piece.

2.2.1 Initialization

```

\documentclass{colorart}
\usepackage{ProjLib}

```

Initialization is straightforward. The first line loads the document class `colorart`, and the second line loads the `ProjLib` toolkit to obtain some additional functionalities.

2.2.2 Set the language

```

\UseLanguage{French}

```

This line indicates that French will be used in the document (by the way, if only English appears in your article, then there is no need to set the language). You can also switch the language in the same way later in the middle of the text. Supported languages include Simplified Chinese, Traditional Chinese, Japanese, English, French, German, Spanish, Portuguese, Brazilian Portuguese and Russian¹.

For detailed description of this command and more related commands, please refer to the section on the multi-language support.

2.2.3 Title, author information, abstract and keywords

```

\title{\<title>}
\author{\<author>}
\date{\PLdate{2022-04-01}}
\maketitle

\begin{abstract}
    \<abstract>

```

¹The language Simplified Chinese, Traditional Chinese, Japanese and Russian requires Unicode support, thus the classes `lebhart` or `beaulivre`.

```
\end{abstract}
\begin{keyword}
  \langle keywords \rangle
\end{keyword}
```

This part begins with the title and author information block. The example shows the basic usage, but in fact, you can also write:

```
\author{\langle author 1 \rangle}
\address{\langle address 1 \rangle}
\email{\langle email 1 \rangle}
\author{\langle author 2 \rangle}
\address{\langle address 2 \rangle}
\email{\langle email 2 \rangle}
...
```

In addition, you may also write in the \mathcal{AMS} fashion, i.e.:

```
\title{\langle title \rangle}
\author{\langle author 1 \rangle}
\address{\langle address 1 \rangle}
\email{\langle email 1 \rangle}
\author{\langle author 2 \rangle}
\address{\langle address 2 \rangle}
\email{\langle email 2 \rangle}
\date{\PLdate{2022-04-01}}
\subjclass{*****}
\keywords{\langle keywords \rangle}

\begin{abstract}
  \langle abstract \rangle
\end{abstract}

\maketitle
```

2.2.4 Draft marks

```
\dnf<\langle some hint \rangle>
```

When you have some places that have not yet been finished yet, you can mark them with this command, which is especially useful during the draft stage.

2.2.5 Theorem-like environments

```
\begin{theorem}\label{thm:abc}
  Ceci est un théorème.
\end{theorem}
Référence du théorème: \cref{thm:abc}
```

Commonly used theorem-like environments have been pre-defined. Also, when referencing a theorem-like environment, it is recommended to use `\cref{\langle label \rangle}` — in this way, there is no need to explicitly write down the name of the corresponding environment every time.

TIP

If you wish to switch to the standard class later, just replace the first two lines with:

```
\documentclass{article}
\usepackage[a4paper,margin=1in]{geometry}
\usepackage[hidelinks]{hyperref}
\usepackage[palatino,amsfashion]{ProjLib}
```

or to use the \mathcal{MS} class:

```
\documentclass{amsart}
\usepackage[a4paper,margin=1in]{geometry}
\usepackage[hidelinks]{hyperref}
\usepackage[palatino]{ProjLib}
```

TIP

If you like the current document class, but want a more “plain” style, then you can use the option `classical`, like this:

```
\documentclass[classical]{colorart}
```

2.3 EXAMPLE - COLORBOOK

Now let’s look at an example of `colorbook` (the same works for `beaulivre`).

```
1 \documentclass{colorbook}
2 \usepackage{ProjLib}
3
4 \UseLanguage{French}
5
6 \begin{document}
7
8 \frontmatter
9
10 \begin{titlepage}
11   <code for titlepage>
12 \end{titlepage}
13
14 \tableofcontents
15
16 \mainmatter
17
18 \part{<part title>}
19 \parttext{<text after part title>}
20
21 \chapter{<chapter title>}
22
23 \section{<section title>}
24
25 ...
26
```

```

27 \backmatter
28
29 ...
30
31 \end{document}

```

There is no much differences with colorart, only that the title and author information should be typeset within the `titlepage` environment. Currently no default titlepage style is given, since the design of the title page is a highly personalized thing, and it is difficult to achieve a result that satisfies everyone.

In the next section, we will go through the options available.

3 THE OPTIONS

colorist offers the following options:

- The language options `EN / english / English`, `FR / french / French`, etc.
 - For the option names of a specific language, please refer to `\language name` in the next section. The first specified language will be used as the default language.
 - The language options are optional, mainly for increasing the compilation speed. Without them the result would be the same, only slower.
- `draft` or `fast`
 - The option `fast` enables a faster but slightly rougher style, main differences are:
 - * Use simpler math font configuration;
 - * Do not use `hyperref`;
 - * Enable the fast mode of `ProjLib` toolkit.

TIP

During the draft stage, it is recommended to use the `fast` option to speed up compilation. When in `fast` mode, there will be a watermark “DRAFT” to indicate that you are currently in the draft mode.

- `allowbf`
 - Allow boldface. When this option is enabled, the main title, the titles of all levels and the names of theorem-like environments will be bolded.
- `runin`
 - Use the “runin” style for `\subsubsection`
- `puretext` or `nothms`
 - Pure text mode. Does not load theorem-like environments.
- `nothmmum`
 - Theorem-like environments will not be numbered.

Additionally, `colorart` and `colorbook` offers the following options:

- `a4paper` or `b5paper`
 - Optional paper size. The default paper size is 8.5in × 11in.
- `palatino`, `times`, `garamond`, `biolinum` | `useosf`
 - Font options. As the name suggest, font with corresponding name will be loaded.
 - The `useosf` option is used to enable the old-style figures.

4 INSTRUCTIONS BY TOPIC

4.1 LANGUAGE CONFIGURATION

colorart has multi-language support, including English, French, German, Italian, Portuguese (European and Brazilian) and Spanish. The language can be selected by the following macros:

- `\UseLanguage{⟨language name⟩}` is used to specify the language. The corresponding setting of the language will be applied after it. It can be used either in the preamble or in the main body. When no language is specified, “English” is selected by default.
- `\UseOtherLanguage{⟨language name⟩}{⟨content⟩}`, which uses the specified language settings to typeset `⟨content⟩`. Compared with `\UseLanguage`, it will not modify the line spacing, so line spacing would remain stable when CJK and Western texts are mixed.

`⟨language name⟩` can be (it is not case sensitive, for example, French and french have the same effect):

- Simplified Chinese: CN, Chinese, SChinese or SimplifiedChinese
- Traditional Chinese: TC, TChinese or TraditionalChinese
- English: EN or English
- French: FR or French
- German: DE, German or ngerman
- Italian: IT or Italian
- Portuguese: PT or Portuguese
- Portuguese (Brazilian): BR or Brazilian
- Spanish: ES or Spanish
- Japanese: JP or Japanese
- Russian: RU or Russian

In addition, you can also add new settings to selected language:

- `\AddLanguageSetting{⟨settings⟩}`
 - Add `⟨settings⟩` to all supported languages.
- `\AddLanguageSetting(⟨language name⟩){⟨settings⟩}`
 - Add `⟨settings⟩` to the selected language `⟨language name⟩`.

For example, `\AddLanguageSetting(German){\color{orange}}` can make all German text displayed in orange (of course, one then need to add `\AddLanguageSetting{\color{black}}` in order to correct the color of the text in other languages).

4.2 THEOREMS AND HOW TO REFERENCE THEM

Environments such as `definition` and `theorem` have been preset and can be used directly.

More specifically, preset environments include: `assumption`, `axiom`, `conjecture`, `convention`, `corollary`, `definition`, `definition-proposition`, `definition-theorem`, `example`, `exercise`, `fact`, `hypothesis`, `lemma`, `notation`, `observation`, `problem`, `property`, `proposition`, `question`, `remark`, `theorem`, and the corresponding unnumbered version with an asterisk `*` in the name. The titles will change with the current language. For example, `theorem` will be displayed as “Theorem” in English mode and “Théorème” in French mode.

When referencing a theorem-like environment, it is recommended to use `\cref{⟨label⟩}`. In this way, there is no need to explicitly write down the name of the corresponding environment every time.

EXAMPLE

```
\begin{definition}[Strange things] \label{def: strange} ...
```

will produce

DEFINITION 4.1 (Strange things) This is the definition of some strange objects. There is approximately an one-line space before and after the theorem environment, and there will be a symbol to mark the end of the environment.

`\cref{def: strange}` will be displayed as: **DEFINITION 4.1**.

After using `\UseLanguage{French}`, a theorem will be displayed as:

THÉORÈME 4.2 (Inutile) Un théorème en français.

By default, when referenced, the name of the theorem always matches the language of the context in which the theorem is located. For example, the definition above is still displayed in English in the current French mode : **DEFINITION 4.1** and **THÉORÈME 4.2**. If you want the name of the theorem to match the current context when referencing, you can add `regionalref` to the global options.

The following are the main styles of theorem-like environments:

THEOREM 4.3 Theorem style: theorem, proposition, lemma, corollary, ...

Proof | Proof style



Remark style



CONJECTURE 4.4 Conjecture style

EXAMPLE Example style: example, fact, ...

PROBLEM 4.5 Problem style: problem, question, ...

For aesthetics, adjacent definitions will be connected together automatically:

DEFINITION 4.6 First definition.

DEFINITION 4.7 Second definition.

4.3 DEFINE A NEW THEOREM-LIKE ENVIRONMENT

If you need to define a new theorem-like environment, you must first define the name of the environment in the language to use:

- `\NameTheorem[⟨language name⟩]{⟨name of environment⟩}{⟨name string⟩}`

For `⟨language name⟩`, please refer to the section on language configuration. When `⟨language name⟩` is not specified, the name will be set for all supported languages. In addition, environments with or without asterisk share the same name, therefore, `\NameTheorem{envname*}{...}` has the same effect as `\NameTheorem{envname}{...}`.

And then define this environment in one of following five ways:

- `\CreateTheorem*{⟨name of environment⟩}`
 - Define an unnumbered environment `⟨name of environment⟩`
- `\CreateTheorem{⟨name of environment⟩}`
 - Define a numbered environment `⟨name of environment⟩`, numbered in order 1,2,3,...
- `\CreateTheorem{⟨name of environment⟩}[⟨numbered like⟩]`
 - Define a numbered environment `⟨name of environment⟩`, which shares the counter `⟨numbered like⟩`
- `\CreateTheorem{⟨name of environment⟩}<⟨numbered within⟩>`
 - Define a numbered environment `⟨name of environment⟩`, numbered within the counter `⟨numbered within⟩`
- `\CreateTheorem{⟨name of environment⟩}(⟨existed environment⟩)`
`\CreateTheorem*{⟨name of environment⟩}(⟨existed environment⟩)`
 - Identify `⟨name of environment⟩` with `⟨existed environment⟩` or `⟨existed environment⟩*`.
 - This method is usually useful in the following two situations:
 1. To use a more concise name. For example, with `\CreateTheorem{thm}(theorem)`, one can then use the name `thm` to write theorem.
 2. To remove the numbering of some environments. For example, one can remove the numbering of the `remark` environment with `\CreateTheorem{remark}(remark*)`.

TIP

This macro utilizes the feature of `amsthm` internally, so the traditional `theoremstyle` is also applicable to it. One only needs declare the style before the relevant definitions.

Here is an example. The following code:

```
\NameTheorem[EN]{proofidea}{Idea}
\CreateTheorem*{proofidea*}
\CreateTheorem{proofidea}<subsection>
```

defines an unnumbered environment `proofidea*` and a numbered environment `proofidea` (numbered within subsection) respectively. They can be used in English context. The effect is as follows:

Idea | The `proofidea*` environment. ☐

Idea 4.3.1 | The `proofidea` environment. ☐

4.4 DRAFT MARK

You can use `\dnf` to mark the unfinished part. For example:

- `\dnf` or `\dnf<...>`. The effect is: `To be finished #1` or `To be finished #2: ...`.

The prompt text changes according to the current language. For example, it will be displayed as `Pas encore fini #3` in French mode.

Similarly, there is `\needgraph`:

- `\needgraph` or `\needgraph<...>`. The effect is:

`A graph is needed here #1`

or

`A graph is needed here #2: ...`

The prompt text changes according to the current language. For example, in French mode, it will be displayed as

`Il manque une image ici #3`

4.5 TITLE, ABSTRACT AND KEYWORDS

colorart has both the features of standard classes and that of the \mathcal{AMS} classes.

Therefore, the title part can either be written in the usual way, in accordance with the standard class article:

```
\title{\langle title \rangle}
\author{\langle author \rangle \thanks{\langle text \rangle}}
\date{\langle date \rangle}
\maketitle
\begin{abstract}
  \langle abstract \rangle
\end{abstract}
\begin{keyword}
  \langle keywords \rangle
\end{keyword}
```

or written in the way of \mathcal{AMS} classes:

```
\title{\langle title \rangle}
\author{\langle author \rangle}
\thanks{\langle text \rangle}
\address{\langle address \rangle}
\email{\langle email \rangle}
\date{\langle date \rangle}
\keywords{\langle keywords \rangle}
\subjclass{\langle subclass \rangle}
\begin{abstract}
  \langle abstract \rangle
\end{abstract}
\maketitle
```

The author information can contain multiple groups, written as:

```
\author{\langle author 1 \rangle}
\address{\langle address 1 \rangle}
\email{\langle email 1 \rangle}
\author{\langle author 2 \rangle}
\address{\langle address 2 \rangle}
\email{\langle email 2 \rangle}
...
```

Among them, the mutual order of `\address`, `\curraddr`, `\email` is not important.

5 KNOWN ISSUES

- The font settings are still not perfect.
- Since many features are based on the ProjLib toolkit, colorist (and hence colorart, lebhart and colorbook, beaulivre) inherits all its problems. For details, please refer to the “Known Issues” section of the ProjLib documentation.
- The error handling mechanism is incomplete: there is no corresponding error prompt when some problems occur.
- There are still many things that can be optimized in the code.