

# **eqexam: An Exam Construction Package**

D. P. Story  
Email: dpstory@uakron.edu

Processed January 7, 2020

## **Contents**

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Package options and Process Options</b>	<b>4</b>
2.1	Early inclusion of packages . . . . .	4
2.2	Options New to eqexam . . . . .	4
2.3	Options from and for web . . . . .	9
2.4	Options from and for exerquiz . . . . .	9
2.4.1	Title page options . . . . .	10
2.5	Drivers Recognized . . . . .	11
2.6	Bring in Config Files . . . . .	12
2.7	Process Options . . . . .	12
2.8	Save Switch Values . . . . .	15
<b>3</b>	<b>Required Packages</b>	<b>15</b>
<b>4</b>	<b>Page Layout</b>	<b>18</b>
<b>5</b>	<b>Counters, Lengths and Tokens</b>	<b>19</b>
<b>6</b>	<b>Some Macros to Support the Options</b>	<b>20</b>
<b>7</b>	<b>Colors</b>	<b>21</b>
<b>8</b>	<b>Version Control</b>	<b>22</b>
<b>9</b>	<b>Title Definitions from Web</b>	<b>30</b>
<b>10</b>	<b>Identification Information</b>	<b>31</b>
<b>11</b>	<b>Stand alone Code</b>	<b>39</b>
<b>12</b>	<b>Switching proofing symbols</b>	<b>39</b>

<b>13 The Main Code</b>	<b>41</b>
13.1 Running Heads and Feet . . . . .	44
13.2 <code>\maketitle</code> definitions . . . . .	46
13.3 The cover page definitions . . . . .	47
13.4 Insert Points in Margins and Compute Page Totals . . . . .	52
13.5 Computing Number of Points within a Segment of the Exam . . . . .	58
13.6 Useful Commands to Write Problems . . . . .	61
13.6.1 The <code>\placeAtxy</code> command . . . . .	61
13.6.2 The <code>workarea</code> environment . . . . .	61
13.6.3 The <code>splitsolution</code> environment . . . . .	62
13.7 The <code>exam</code> Environment . . . . .	71
13.8 <code>problem</code> Environments . . . . .	77
<b>14 Vertical Space Filling Options</b>	<b>97</b>
14.1 General filler lines commands and controls . . . . .	97
14.2 Utility commands used with the <code>flextended</code> option . . . . .	111
14.3 Filler lines with <code>answerkey</code> option . . . . .	114
14.4 Filler lines with <code>nosolutions</code> option . . . . .	116
<b>15 Concerning the <code>fortextbook</code> option</b>	<b>118</b>
15.1 Setting options with <code>\textbookOpts</code> . . . . .	119
15.2 Macros to display answers/shortsolns . . . . .	121
15.3 Marginal Matter . . . . .	129
15.4 In support of solutions at end of document and chapter . . . . .	137
15.5 Modifying and restoring the Layout . . . . .	138
15.6 We shipout in support of <code>fortextbook</code> . . . . .	140
15.7 Modify <code>equestions</code> environment . . . . .	140
15.8 Modifications for solutions page . . . . .	141
15.9 Some Convenience/Formatting Commands . . . . .	143
15.10 The <code>probset</code> and <code>example</code> environments . . . . .	144
15.11 Commands in support of Solution Manuals . . . . .	145
<b>16 <code>fortextbook</code> Style File</b>	<b>147</b>
<b>17 <code>xkeyval</code> Extensions</b>	<b>148</b>
<b>18 Index</b>	<b>160</b>

## 1 Introduction

This package is my attempt at writing a set of macros for creating exams. The package can be used with or without `web` or `exerquiz`. When used without, what is produced is a document suitable for printing. When `exerquiz` is used, the same document is produced, but with hypertext links to solutions. This may be useful for publishing solutions on the web, or publishing pretests with/without solutions.

The package must be as flexible as possible vis-à-vis PDF. (1) `web` only does not add much, it does input hyperref and test info such as `\title`, `\subject`, etc are placed in the Document Info fields of the PDF. (2) If `exerquiz` is also input (prior to `eqexam`), then hyperlinks will be created to the solutions to the test, if solutions are included at the end of the document. (3) If `web` and `exerquiz` are input, and the `online` option is taken, then the checkboxes will be come interactive, the space left to work the problems will be multi-line text boxes, fill-ins limited to True/False and simple text fill-in the blank will also become text boxes.

When in `online` mode, the student can take the test in a computer lab, the completed exam can be printed and handed in, or perhaps submitted server-side script.

(2011/05/13) The version of `eqexam` is a departure from previous versions. Previously, the list of problems were not in list, they were left-justified, with the problem number extending out into a little area determined by `\oddsidemargin`. This makes it hard to reformat a list of problems to fit into a custom book format. This new version defines a new environment, `equestions`, that makes each problem into a list. The list environment allows for an easy redesign of the formatting of the problems. The purpose of this new scheme, is to open up `eqexam` as a format package that can be used by author for writing a textbook.

The `fortextbook` option supplies support for authors writing a textbook. The `exam` environment is re-cast into the `probset` environment, it can be used to write problem sets within the text. there is a version for the instructor and the student. The instructors version writes answers to the problem sets to the margins (or inline). Two solutions are offered, short and long. The short solutions appear in the back of the book (odd-numbered ones for the student edition. The long solutions are used to build the stand-alone solutions manuals for both the student and the instructor. More details are found in ‘Concerning the `fortextbook` option’ on page 118, see also ‘`fortextbook` Style File’ on page 147.

## 2 Package options and Process Options

Let us catalog the options of this package.

### 2.1 Early inclusion of packages

We include these packages early in the process of loading.

```
1 <*package>
2 \RequirePackage{ifpdf}[2006/02/20]
3 \RequirePackage{ifxetex}[2006/08/21]
```

Very useful package for defining key-values.

```
4 \usepackage{xkeyval}
```

### 2.2 Options New to `eqexam`

`usecustomdesign` Here are some options unique to this package. Use this option to avoid `eqexam` from setting up the “standard” page layout.

```
5 \DeclareOptionX{usecustomdesign}{\eqcustomdesigntrue}
6 \newif\ifeqcustomdesign \eqcustomdesignfalse
7 \DeclareOptionX{nocustomdesign}{\let\eqe@nocustomdesign=1}
8 \let\eqe@nocustomdesign=0
```

`fortextbook` An option to extend the application of `eqexam` to provide support (exercises, providing solutions, short solutions, answers, and hints) for authors writing textbooks. See ‘Concerning the `fortextbook` option’ on page 118.

```
9 \DeclareOptionX{fortextbook}{\eqfortextbooktrue}
10 \newif\ifeqfortextbook \eqfortextbookfalse
```

`forinstr` `forstudent` These two options simply set a switch to signal the intention of the document author.

```
11 \DeclareOptionX{forinstr}{\eqforinstrtrue}
12 \DeclareOptionX{forstudent}{\eqforinstrfalse}
13 \newif\ifeqforinstr \eqforinstrfalse
```

`nomarginwrite` The switch `\ifeqwritetomargins` is used by the `fortextbook` option. It is normally `true`, but if set to `false`, the `\AddToShipoutPicture` is not generated at the beginning of the document. Here is the code taken from below:

```
\ifeqfortextbook\ifeqwritetomargins
\AtBeginDocument{\chkmarginboxwidth
    \AddToShipoutPicture{\eqe@tb@shipout}}
\fi\fi
```

Using this option, the check for the margin width is not done, and writing to the margins is turned off. (`\marginpar` still works)

```
14 \DeclareOptionX{nomarginwrite}{\eqwritetomarginsfalse}
15 \newif\ifeqwritetomargins \eqwritetomarginstrue
```

**Configuration Files.** This section contains options for the configuration files.

cfg The cfg option is used to specify a named configuration file, extension must be .cfg; usage cfg=hwdoc.

```

16 \define@key{eqexam.sty}{cfg}[]{%
17   \def\arg@if{\#1}\ifx\arg@i\empty
18   \PackageWarning{eqexam}{No value for 'cfg' specified}\else
19   \def\ifeqexamCFG{true}\def\eqexamCFG{\#1.cfg}%
20   \AtEndOfPackage{\InputIfFileExists{\#1.cfg}
21   {\typeout{Inputting #1.cfg}}{\PackageWarning{eqexam}{%
22     Cannot find configuration file #1.cfg}}}\fi
23 }
24 \def\ifeqexamCFG{false}
25 \let\eqexamCFG\empty
```

myconfig We offer seven sets of configuration files, that should be enough, especially light of the new cfg option, defined above.

```

26 \for{\eqe@tmp@i:={},i,ii,iii,iv,v,vi}{\do{%
27   \edef\eqe@tmp@exp{%
28     \noexpand\DeclareOptionX{myconfig}\eqe@tmp@i}%
29     {\noexpand\AtEndOfPackage{\expandafter\noexpand
30       \csname eqemyconfig\eqe@tmp@i\endcsname}}%
31   }\eqe@tmp@exp
32 }
```

**Point options.** Options relating to points, points on left, right, both, no points, totals on left and right. We offer options for points and totals.

```

pointsonleft 33 \DeclareOptionX{pointsonleft}{\AtEndOfPackage{\PointsOnLeft}}
pointsonright 34 \DeclareOptionX{pointsonright}{\AtEndOfPackage{\PointsOnRight}}
pointsonboth 35 \DeclareOptionX{pointsonboth}{\AtEndOfPackage{\PointsOnBothSides}}
nopoints 36 \DeclareOptionX{nopoints}{\AtEndOfPackage{\NoPoints}}
totalsonleft 37 \DeclareOptionX{totalsonleft}{\AtEndOfPackage{\TotalsOnLeft}}
totalsonright 38 \DeclareOptionX{totalsonright}{\AtEndOfPackage{\TotalsOnRight}}
nozerototals 39 \DeclareOptionX{nozerototals}{\AtEndOfPackage{\noZeroTotals}}
```

nototals  
noperptotals

parttotalsonright 40 \let\eqe@YES=y \let\eqe@NO=n
parttotalsonleft 41 \let\eqe@One=1 \let\eqe@Zero=0
noseparationrule 42 \let\eqe@Two=2 \let\eqe@Three=3 \let\eqe@Four=4
nosummarytotals 43 \def\eqe@h{h}
44 \DeclareOptionX{nototals}{\AtEndOfPackage{\NoTotals}}
45 \DeclareOptionX{noperptotals}{%
46 \AtEndOfPackage{\let\eqe@parttotals\eqe@NO}}
47 \DeclareOptionX{parttotalsonright}{%
48 \def\eqeomarginbox{\eqeomarginboxright}}
49 \DeclareOptionX{parttotalsonleft}{%
50 \def\eqeomarginbox{\eqeomarginboxleft}}
51 \def\eqeomarginbox{\eqeomarginboxright}
52 \DeclareOptionX{noseparationrule}{%

```

53      \AtEndOfPackage{\separationruleOff}}
54 %     \AtEndOfPackage{\let\separationrule\relax}
55 \DeclareOptionX{nosummarytotals}{\let\eq@nosummarytotals\eq@YES}

coverpage cover page options. There are two such options, coverpage and coverpagesumry. If this option is taken, a cover page is generate.
56 \DeclareOptionX{coverpage}{\def\eqex@coverpage{\eqex@coverpage}%
57   \setcounter{page}{0}}
If this option is taken, an Exam Record is generated on the cover page, provided the coverpage option is taken. Possible values aer byparts, bypages, or none.
58 \define@choicekey+{\eqexam.sty}{coverpagesumry}[\val\nr]%
59   {byparts,bypages,none}%
60   \ifcase\nr\relax
61     \def\sumryAnnots{\cpSumrybyparts}\or
62     \def\sumryAnnots{\cpSumrybypages}\or
63     \let\sumryAnnots\relax
64   \fi
65 }{\PackageWarning{aeb}{Bad choice for coverpagesumry, permissible values
66   are byparts, bypages, and none. Try again}}
67 \let\sumryAnnots\relax

nospacetowork Options related to how the document is built. The vertical space defined by the solution environment is removed.
68 \DeclareOptionX{nospacetowork}{%
69   \AtEndOfPackage{\let\eq@insertverticalspace\eq@NO}}
answerkey Equivalent to solutionsafter and proofing.
70 \@ifundefined{ifanswerkey}{\newif\ifanswerkey\answerkeyfalse}{}
71 \@ifundefined{ifsolutionsAtEnd}{%
72   {\newif\ifsolutionsAtEnd\solutionsAtEndtrue}{}
A more intelligent processing of certain options is deployed: Now, we allow only one of the options answerkey, nosolutions, vspacewithsolns, solutionsafter, and solutionsonly at a time.
73 \let>thisOpt@OK \eqe@YES
74 \def\w@rningBadOpts{\PackageWarningNoLine{\eqexam}{You've chosen two
75   conflicting options, \MessageBreak \l@stP0\space and \CurrentOption.
76   We will recognize\MessageBreak the \l@stP0\space option.
77   Please correct\MessageBreak this if my guess is wrong}}
78 \def\eqe@option@kenMsg{\PackageInfo{\eqexam}{%
79   {Option \CurrentOption\space taken}}}
80 \DeclareOptionX{answerkey}{\ifx>thisOpt@OK\eqe@YES
81   \def\l@stP0{answerkey}\let>thisOpt@OK\eqe@NO
82   \eqe@option@kenMsg\expandafter\AnswerKey\else
83   \w@rningBadOpts\fi}
84 \def\AnswerKey{\solutionsAtEndfalse\answerkeytrue
85   \eq@proofingtrue\eq@solutionsaftertrue\displayworkareafalse}

```

**vspacewithsolns**

**ftbsolns**

**\ifkeyalt**

When `vspacewithsolns` is used, vertical space is created by the solutions environment, and the solutions are written to the end of the file. Added `ftbsolns` as an alias for `vspacewithsolns`. This is implemented through a Boolean switch `\ifvspacewithsolns`, which I'm sorry now I've made so long. To make up for that bad decision, I also define `\fkeyalt` to be `\ifvspacewithsolns` with making conditional decisions, of course, one cannot say `\keyalttrue`.

```

86 \newif\ifvspacewithsolns\vspacewithsolnsfalse
87 \def\ifkeyalt{\csname ifvspacewithsolns\endcsname}
88   \let\keyalttrue\vspacewithsolnstrue
89   \let\keyaltfalse\vspacewithsolnsfalse
90 \%def\ifkeyalt{\csname ifvspacewithsolns\endcsname}
91 \def\ifkeyOrkeyalt{\ifanswerkey
92   \def\eqe@next{\csname iftrue\endcsname}\else
93   \ifvspacewithsolns\def\eqe@next{\csname iftrue\endcsname}\else
94   \def\eqe@next{\csname iffalse\endcsname}\fi\fi\eqe@next}
95 \DeclareOptionX{vspacewithsolns}{\ifx\thisOpt@OK\eqe@YES
96   \def\l@stP@{vspacewithsolns}\let\thisOpt@OK\eqe@NO
97   \eqe@optiont@kenMsg
98   \vspacewithsolnstrue\expandafter\displayworkareatru
99   \else\w@rningBadOpts\fi}
100 \DeclareOptionX{ftbsolns}{\ExecuteOptionsX{vspacewithsolns}}

```

**flextended**

The `flextended` is an (experimental) option to allow filler lines (`fl`) to be superimposed under the solutions, when the `answerkey` option is taken.

```

101 \DeclareOptionX{flextended}{\AtEndOfPackage{\flextendedInput}}
102 \def\flextendedInput{\eqe@flextendedtrue
103   \InputIfFileExists{flextended.def}
104     {\PackageInfo{eqexam}{Inputting flextended.def for
105       flextended\MessageBreak option}}
106     {\eqe@flextendedfalse\PackageWarning{eqexam}
107      {Cannot find flextended.def for flextended\MessageBreak
108       option. You should rebuild the package. Removing\MessageBreak
109       flextended for now}}}
110 \Qifundefined{\flextended}
111   {\newif\ifeq@flextended \eqe@flextendedfalse}{}

```

**useforms**

Use forms (if online option is taken); otherwise draw rectangles for multiple choice/multiple selection questions.

```

112 \DeclareOptionX{useforms}{\AtEndOfPackage{\def\sqstar{*}}}
113 \newif\ifallowcirc4mc \allowcirc4mcfalse
114 \DeclareOptionX{allowcirc4mc}{\allowcirc4mctrue}

```

**online** **PDF Options** The various options to go beyond paper!

**pdf** Options related to the interactive capability of `eqexam`. For each of the PDF

**links** options, we auto-check for `pdftex` and `xetex`.

**email**

```

115 \def\eqe@auto@chk@drivers{\ifpdf\ExecuteOptionsX{pdftex}\else

```

```

116      \ifxetex\ExecuteOptionsX{xetex}\fi\fi}
117 \newif\ifeqeonline \eqeonlinefalse
118 \DeclareOptionX{online}{\eqe@auto@chk@drivers
119   \let\eq@online\eq@YES\eq@onlinetrue\ExecuteOptionsX{links}}
120 \DeclareOptionX{pdf}{\eqe@auto@chk@drivers\let\load@web\eq@YES}
121 \DeclareOptionX{links}{\eqe@auto@chk@drivers
122   \let\load@web\eq@YES\let\load@exerquiz\eq@YES}
123 \DeclareOptionX{email}{\eqe@auto@chk@drivers
124   \let\use@email\eq@YES\ExecuteOptionsX{online}}
obeylocalversions This option is used for multiple versions of a document.
125 \newif\ifeqobeylocalversion \eqobeylocalversionfalse
126 \DeclareOptionX{obeylocalversions}{\eqobeylocalversiontrue}
usexkv Causes the xkeyval package to be input, this option extends the option list of
\fillIn.
127 \DeclareOptionX{usexkv}{\let\eq@usexkeys\eq@YES}
2014/12/19 Now, the usexkeys is on by default.
128 \let\eq@usexkeys\eq@YES

max Renditions Options relating to renditions. The max and rendition option
rendition can be used instead of the \numVersions{2} and \forVersion{a}, respectively.
These options allow you to set the version information through a package option.
This allows us, for example, to use a cfg file such as rendition.cfg to dynamically
set the version. This feature is used primarily by AeB Exam Builder.
129 \let\eq@renditionOptions@\empty
130 \let\eq@max@selected@\empty \let\eq@ren@selected@\empty
131 \DeclareOptionX{max}{\def\eq@max@selected{\#1}%
132   \g@addto@macro\eq@renditionOptions{\numVersions{\#1}}}
133 \DeclareOptionX{rendition}{\def\eq@ren@selected{\#1}%
134   \g@addto@macro\eq@renditionOptions{\forVersion{\#1}}}

allowrandomize Randomization Options relating to randomization. Use this option to ran-
domize the choices of a multiple choice question.
135 \DeclareOptionX{allowrandomize}{\AtEndOfPackage{\inputRandomizeChoices}}
136 \def\inputRandomizeChoices{\InputIfFileExists{aebrandom.def}%
137   {\typeout{inputting aebrandom.def}}{cannot find aebrandom.def}}

Set Misc. Defaults and Helper Macros. We set some defaults, and define
macros for use by the document author.
138 \let\eq@online\eq@NO
139 \def\ifisOnline{\ifx\eq@online\eq@YES}
140 \let\use@email\eq@NO
141 \let\load@web\eq@NO
142 \let\load@exerquiz\eq@NO
143 \def\sqLinks{\def\sqstar{}}\sqLinks
144 \def\sqForms{\def\sqstar{*}}
```

```

145 \def\NoSpaceToWork{\let\eq@insertverticalspace\eqe@NO}
146 \def\SpaceToWork{\let\eq@insertverticalspace\eqe@YES}
147 \let\eq@nototals\eqe@NO
148 \let\eq@nosummarytotals\eqe@NO
149 \let\eq@parttotals\eqe@YES
150 \let\eqx@separationrule\eqe@YES
151 \let\eq@insertverticalspace\eqe@YES
152 \let\eqex@coverpage\relax
153 \def@reportpoints{0}
154 \let\marginpoints\empty
155 \let\totalsbox=\hfil

```

## 2.3 Options from and for web

**forpaper**

**forcolorpaper**

**forcolorpaper\***

**preview**

**web0pts**

```

156 \ifundefined{ifequusecolor}{\newif\ifequusecolor\equusecolorfalse}{}
157 \DeclareOptionX{forpaper}{\equusecolorfalse\eqfornpapertrue
158     \PassOptionsToPackage{monochrome}{\eq@ColorPackage}}
159 \DeclareOptionX{forcolorpaper}{\equusecolortrue\eqfornpapertrue}
160 \newif\ifForceNoColor\ForceNoColorfalse
161 \DeclareOptionX{forcolorpaper*}{\equusecolortrue\eqfornpapertrue
162     \ForceNoColortrue} % for print
163 \DeclareOptionX{preview}{\previewtrue}
164 \define@key{eqexam.sty}[web0pts][]{\def\eqe@web0pts{\#1,\eqDriverName}}
165 \def\eqe@web0pts{\eqDriverName}

```

## 2.4 Options from and for exerquiz

**exerquiz0pts**

Options from exerquiz that are useful for this package. Pass options to exerquiz, when links or higher is used.

**nosolutions**

**nohiddensolutions**

**noHiddensolutions**

**solutionsafter**

**solutionsonly**

```

166 \define@key{eqexam.sty}[exerquiz0pts][]{\def\eqe@eq0pts{\#1,nodljs}}
167 \def\eqe@eq0pts{\nodljs}
168 \DeclareOptionX{nosolutions}{\ifx\thisOpt@OK\eqe@YES
169     \def\l@stP0{nosolutions}\let\thisOpt@OK\eqe@NO
170     \eqe@optiont@kenMsg\eq@nolinktrue\eq@nosolutionstrue
171     \expandafter\displayworkareatrue
172     \else\w@rningBad0pts\fi}
173 \DeclareOptionX{nohiddensolutions}{\eq@globalshowsolutionstrue}
174 \DeclareOptionX{noHiddensolutions}%
175     {\eq@globalshowsolutionstrue\AtBeginDocument{\def\Hidesymbol{h}}}
176 \DeclareOptionX{solutionsafter}{\ifx\thisOpt@OK\eqe@YES
177     \def\l@stP0{solutionsafter}\let\thisOpt@OK\eqe@NO
178     \eqe@optiont@kenMsg
179     \eq@solutionsaftertrue\expandafter

```

```

180      \displayworkareafalse\else\w@rningBadOpts\fi}
181 \DeclareOptionX{solutionsonly}{\ifx\thisOpt@OK\eqe@YES
182     \def\l@stPO[solutionsafter]{\let\thisOpt@OK\eqe@NO
183     \eqe@option@kenMsg\AtEndOfPackage{\therearesolutiontrue
184         \let\exerSolnsHeadnToc\relax}
185         \solutionsonlytrue\answerkeytrue\expandafter
186         \displayworkareafalse\else\w@rningBadOpts\fi}

```

#### proofing

The `proofing` option sets a switch that controls whether the checkbox for multiple choice questions appears, and whether the answer for the `\fillin` command appears. `\ifeq@proofing` is set to true when the `answerkey` option is taken.

```
187 \DeclareOptionX{proofing}{\eq@proofingtrue}
```

We provide two helper commands for turning on or off proofing. These are `\showproofing` for turning on proofing and `\hideproofing` for turning off proofing. There was some reason for defining these two, but can't remember now.

```
188 \newcommand{\showproofing}{\eq@proofingtrue}
```

```
189 \newcommand{\hideproofing}{\eq@proofingfalse}
```

#### showgrayletters

When this option is in effect, capital letters in gray appear under the multiple choice question boxes.

```
190 \newif\ifaebshowgrayletters\aebsshowgraylettersfalse
```

```
191 \DeclareOptionX{showgrayletters}{%
```

```
192     {\AtEndOfPackage{\aebsshowgrayletterstrue}}
```

#### \ifdisplayworkareaOn

Define `\ifdisplayworkarea` and user commands to turn off and on.

#### \ifdisplayworkareaOff

```
193 \@ifundefined{ifdisplayworkarea}{\newif\ifdisplayworkarea
```

```
194     \displayworkareafalse}{}%
```

```
195 \providecommand\displayworkareaOn{\displayworkareatrue}
```

```
196 \providecommand\displayworkareaOff{\displayworkareafalse}
```

**Color packages** We set the color package, `xcolor` preferred.

```
197 \IfFileExists{xcolor.sty}{%
```

```
198 {\def\eq@ColorPackage{xcolor}\def\eqe@color@opt{table}}%
```

```
199     \PassOptionsToPackage{xcolor}{table}}
```

```
200 {\def\eq@ColorPackage{color}\let\eqe@color@opt\empty}
```

#### noxcolor

`noxcolor` forces the use of the color package.

```
201 \DeclareOptionX{noxcolor}{\def\eq@ColorPackage{color}}
```

### 2.4.1 Title page options

#### useclassmaketitle

To support the use of `eqexam` outside a straight exam document, we allow the user to bypass the redefinition of `\maketitle`. This is automatic with the `fortextbook` option.

```
202 \newif\if@eqeuseclassmaketitle \eqeuseclassmaketitlefalse
```

```
203 \DeclareOptionX{useclassmaketitle}{\eqeuseclassmaketitletrue}
```

```
204 \newif\if@bypasseqexamheading \bypasseqexamheadingfalse
```

```
205 \DeclareOptionX{bypasspkpgpagestyle}{\bypasseqexamheadingtrue}
```

```
206     \ExecuteOptionsX{nototals}}
```

## 2.5 Drivers Recognized

These drivers are only relevant when a PDF option is taken (pdf, links, online, email). For ordinary paper documents, it is not necessary to specify the driver.

If you put the assignment/homework/test (solns) on the web, suggested option is dvipsone pdf, this inputs hyperref, and the document info dialog is filled in.

```

dvips 207 \DeclareOptionX{dvipsone}{%
pdftex 208   \def\eqe@drivernum{0}\def\eqDriverName{dvipsone}%
dvipdfm 209   \PassOptionsToPackage{\eq@ColorPackage}{dvipsone}%
dvipdfmx 210 \DeclareOptionX{dvips}{\def\eqe@drivernum{0}\def\eqDriverName{dvips}}%
xetex 211   \PassOptionsToPackage{\eq@ColorPackage}{dvips}%
textures 212 \DeclareOptionX{pdftex}{\def\eqe@drivernum{1}\def\eqDriverName{pdftex}%
213   \PassOptionsToPackage{\eq@ColorPackage}{pdftex}%
214 \DeclareOptionX{dvipdfm}{%
215   \def\eqe@drivernum{2}\def\eqDriverName{dvipdfm}%
216   \PassOptionsToPackage{\eq@ColorPackage}{dvipdfm}%
217 \DeclareOptionX{dvipdfmx}{\def\eqe@drivernum{2}%
218   \def\eqDriverName{dvipdfmx}%
219   \PassOptionsToPackage{\eq@ColorPackage}{dvipdfmx}%
220 \DeclareOptionX{xetex}{\def\eqe@drivernum{2}\def\eqDriverName{xetex}%
221   \PassOptionsToPackage{\eq@ColorPackage}{xetex}%
222 \DeclareOptionX{textures}{%
223   \def\eqe@drivernum{3}\def\eqDriverName{textures}%
224   \PassOptionsToPackage{\eq@ColorPackage}{textures}%
225 \DeclareOptionX{*}{%
226   \PassOptionsToPackage{\CurrentOption}{\eq@ColorPackage}%
227 \def\eqe@drivernum{5}%
228 \let\eqDriverName\empty

```

If exerquiz is not loaded, when we need to define some of the switches that were defined in exerquiz.

The following switches are used in the options above, and are also defined in web, exerquiz, or eforms.

```

229 \newif\ifeq@solutionsafter \eq@solutionsafterfalse
230 \def\ifsolutionsafter{\csname ifeq@solutionsafter\endcsname}%
231   \let\solutionsaftertrue\eq@solutionsaftertrue
232   \let\solutionsafterfalse\eq@solutionsafterfalse
233 \newif\ifsolutionsonly \solutionsonlyfalse
234 \newif\ifeq@hidesolution \eq@hidesolutionfalse
235 \newif\ifeq@globalshowsolutions \eq@globalshowsolutionsfalse
236 \newif\ifeq@nosolutions \eq@nosolutionsfalse
237 \newif\ifeq@proofing \eq@proofingfalse
238 \newif\ifeq@nolink \eq@nolinkfalse
239 \ifundefined{ifpreview}{\newif\ifpreview \previewfalse{}}
240 \newif\ifeqforpaper \eqforpaperfalse

```

We define the commands for inputting the CFG files.

```

241 \def\eqe@csarg#1#2{\expandafter#1\csname#2\endcsname}%
242 @for\eqe@tmp@i:={} ,i,ii,iii,iv,v,vi\dof{\eqe@csarg
243   \edef\eqemyconfig\eqe@tmp@i}{\noexpand

```

```

244      \InputIfFileExists{eqexam\eqe@tmp@i.cfg}{}{}%
245      \eqe@tmp@exp
246 }

```

## 2.6 Bring in Config Files

First read `web.cfg`, to possibly get the driver, then input `eqecus.opt`, which is used to create convenient custom options.

Here is an example of usage for defining your own custom options, must be based on current options, this code would be in the file `eqecus.opt`.

```

\DeclareOptionX{atbdbopts}
{%
    \ExecuteOptionsX{online}
    \ExecuteOptionsX{forcolorpaper}
    \ExecuteOptionsX{nosolutions}
    \ExecuteOptionsX{nopoints}
    \ExecuteOptionsX{nototals}
    \ExecuteOptionsX{nospacetowork}
    \ExecuteOptionsX{obeylocalversions}
    \ExecuteOptionsX{myconfig}
}

```

The following config files are input prior to `\ProcessOptionsX`, and can, therefore, contain declaration of options. `web.cfg` usually only specifies the default driver. `eqecus.opt` is used by @EASE, but can be used locally.

```

247 \let\bWebCustomize\endinput
248 \let\eWebCustomize\relax
249 \InputIfFileExists{web.cfg}{}{}
250 \InputIfFileExists{eqecus.opt}{}{}

```

These two are used by the rendition package and the exam builder utility.

```

251 \InputIfFileExists{rendition.cfg}{}{}
252 \InputIfFileExists{exambuilder.cfg}{}{}

```

## 2.7 Process Options

Now process the options.

```
253 \ProcessOptionsX
```

When the online or email option is taken, as well as answwserkey, we cancel the `flextended` option.

```

254 \ifeqeonline
255     \ifanswerkey
256         \def\flextendedInput{\let\turnf1@nskeyMsg\@empty
257             \PackageWarningNoLine{eqexam}
258             {You've chosen the online or email option\MessageBreak
259             with the flextended option. This is not\MessageBreak
260             supported, removing the flextended option}}\fi
261 \fi

```

The `\selectedMC` command contains the choice for the styling for the region multiple choice questions: rectangles or circles. The default is rectangles.

```
262 \AtEndOfPackage{\selectedMC}
```

(2015/07/12) Move the inclusion of the color package prior to loading many of the other required packages.

```
263 \edef\eqe@tmpexp{\noexpand
264 \RequirePackage{\eq@ColorPackage}}\eqe@tmpexp
```

We require a minimal version for `xcolor`.

```
265 \@ifpackagelloaded{xcolor}{\AtEndOfPackage{\let\CT@cell@color\relax
266   \let\CT@arc@\relax}%
267   \@ifpackagelater{xcolor}{2004/07/04}{}{\PackageError{eqexam}{%
268     ****\MessageBreak
269     * Your Version of 'xcolor.sty' is too old!\MessageBreak
270     * You need the version from 2004/07/04 or newer\MessageBreak
271     * or use: \string\usepackage[noxcolor]{eqexam}\MessageBreak
272     * or \string\documentclass[noxcolor]{article}\MessageBreak
273     ****\MessageBreak}{}%
274   }%
275 }{}}
```

If `nocustomdesign` option is taken, we set the switch `\eqcustomdesignfalse`.

```
276 \if\eqe@nocustomdesign\eqcustomdesignfalse\fi
```

Define a `\immediate\write` helper macro.

```
277 \long\def\eqe@I#1{\immediate\write#1}
```

### **Early definitions for the `fortextbook` option.**

`\showAllAnsAtEnd` If the user has chosen the `vspacewithsolns` option, we must turn off all other solution options, namely `answerkey`. This command is used internally.

(2016/10/02) Include `\eqTopOfSolnPage` from `exerquiz` to support copying question to solution page.

```
278 \newcommand{\showAllAnsAtEnd}{%
279   \makeAnsEnvForSolnsAtEnd\eqTopOfSolnPage
280   \answerkeytrue\eq@proofingtrue
281   \eq@solutionsaftertrue\vspacewithsolnstrue
282   \displayworkareafalse
283 }
```

`\makeAnsEnvForSolnsAtEnd` One user wanted to be able to use the `answers` environment in the solutions section at the end of the document (when the `vspacewithsolns` is used). Here it is. This definition is added to the definition of `\showAllAnsAtEnd`.

```
284 \newcommand{\makeAnsEnvForSolnsAtEnd}{%
285 %  \proofingsymbol{\ding{52}}%
286   \let\answers\answers@sq
287   \let\endanswers\endanswers@sq
288   \let\manswers\manswers@sq
```

```

289   \let\endmanswers\endmanswers@sq
290 }

291 \newcommand{\solAtEndFormatting}[1]{\def\eqeAEFormatting{#1}}
292 \let\eqeAEFormatting\empty

  \writeAllAnsAtEnd writes the \showAllAnsAtEnd command to the solutions file.

293 \def\writeAllAnsAtEnd{\ifsolutionsonly\else
294   \let\quiz@solns\ex@solns
295   \eqe@IWO\quiz@solns{\string\showAllAnsAtEnd}%
296   \ifx\eqeAEFormatting\empty\else
297     \eqe@IWO\quiz@solns{\string\eqeAEFormatting}\fi
298   \fi
299 }
300 \def\writeWithSolDocTrue{\writeT@SolnFile{\protect\withinsoldoctrue}}


\setSolnMargins Sets the value of \eqemargin in the context of the solution file, this command is
redefined later.
301 \newcommand{\setSolnMargins}[1]{\setlength\eqemargin{#1}\ignorespaces}

(2011/05/08) In the new version of eqexam, the one that makes the problems
within an exam environment, into a list, the solutions file that appears at the end
of the document also needs to be put into a list. Here, we define the command
that writes the beginning of the eqequestions environment to the beginning of
the \jobname.sol file. We hard-wire write \setSolnMargins{\the\eqemargin}
to the solution file, but leave a back door open to write an alternate string.

\altSetSolnMargins (2014/03/20) \altSetSolnMargins allows you, through its argument to pass an
alternate string.
302 \def\altSetSolnMargins#1{\def\alt@SetSolnMargins{#1}}
303 \let\alt@SetSolnMargins\empty
304 \def\writeBeginEqeQuestions{\solutionsonly\else
305   \ifOKToWriteExamData
306     \let\quiz@solns\ex@solns
307     \ifx\alt@SetSolnMargins\empty
308       \writeT@SolnFile{\string\setSolnMargins{\the\eqemargin}}\else
309       \writeT@SolnFile{\alt@SetSolnMargins}\fi
310     \writeT@SolnFile{\protect\eqgrii\string\noindent
311       \string\begin{eqequestions}}\%
312   \fi
313 \fi
314 }

(2011/05/08) We define the command that writes the end of the eqequestions
environment to the beginning of the \jobname.sol file.
315 \newcommand{\setBtwnExamSkip}[1]{\gdef\btwnExamSkipAmt{#1}%
316   \def\btwnExamSkip{\ifdim#1=0pt\else
317     \vskip#1\relax\fi}%
318 \setBtwnExamSkip{6pt}
319 \def\writeEndEqeQuestions{%
320   \solutionsonly\else

```

```

321      \ifOKToWriteExamData
322      \let\quiz@solns\ex@solns
323      \eqe@IWO\quiz@solns{\string\eqgri
324          \string\end{eqequestions}^^J}%
325      \writeT@SolnFile{\string\btwnExamSkip^^J}%
326      \fi\fi
327 }

If \ifvspacewithsolns we set the switches need to simulate nosolutions.

328 \def\csarg#1#2{\expandafter#1\csname#2\endcsname}
329 \def\saveIFEQE#1{\def\ARG{#1ifSave}%
330   \expandafter\csarg\expandafter
331   \let\expandafter\ARG\csname#1\if#1true\else false\fi\endcsname}
332 \saveIFEQE{vspacewithsolns}\saveIFEQE{answerkey}
333 \saveIFEQE{eq@proofing}\saveIFEQE{eq@solutionsafter}
334 \saveIFEQE{eq@nolink}\saveIFEQE{eq@nosolutions}
335 \saveIFEQE{displayworkarea}
336 \def\vpwsSimulateNoSolns{\% dps28
337   \ifvspacewithsolns
338     \answerkeyfalse\eq@proofingfalse\eq@solutionsafterfalse
339     \eq@nolinkfalse\eq@nosolutionsfalse\displayworkareatrue
340   \fi}
341 \def\reverseVSWS{\vspacewithsolnsfalse
342   \answerkeyifSave\eq@proofingifSave
343   \eq@solutionsafterifSave\eq@nolinkifSave
344   \eq@nosolutionsifSave\displayworkareaifSave
345 }
346 \vpwsSimulateNoSolns

```

## 2.8 Save Switch Values

Now, save the current state of the switches defined above. When, and if, the packages web, exerquiz and eforms are loaded, they will overwrite the choices set by the author, so we save them.

```

347 \let\savedeq@online\eq@online
348 \let\savedifeq@solutionsafter\ifeq@solutionsafter
349 \let\savedifeq@hidesolution\ifeq@hidesolution
350 \let\savedifeq@globalshowsolutions\ifeq@globalshowsolutions
351 \let\savedifeq@nosolutions\ifeq@nosolutions
352 \let\savedifeq@proofing\ifeq@proofing
353 \let\savedifeq@nolink\ifeq@nolink
354 \let\savedifpreview\ifpreview
355 \let\savedifeqforpaper\ifeqforpaper
356 \let\ifnosolutions\ifeq@nosolutions

```

## 3 Required Packages

The following are the required packages for eqexam.

```

357 \RequirePackage{amstext,amssymb}
358 \@ifundefined{if@fleqn}{\let\fleqnOn\relax\let\fleqnOff\relax}
359     {\def\fleqnOn{@fleqntrue}\def\fleqnOff{@fleqnfalse}}

```

Bring the `comment` package in early, before `verbatim`, these two clash a bit.

```
360 \RequirePackage{aeb-comment}
```

If `\BeforeIncludedComment` is defined, the old version of `aeb-comment` is used; otherwise, the new version of `aeb-comment` is being used. The new version supports utf-8.

```

361 \@ifundefined{BeforeIncludedComment}{\let\aebc@end\endgroup}
362     {\let\aebc@end\relax}
363 \def\eqe@commentChkMsg{\@ifpackageloaded{comment}}
364     {\PackageWarningNoLine{eqexam}
365         {The comment package is incompatible with the\MessageBreak
366             aeb-comment package, do not use the comment package}{}}
367 \AtBeginDocument{\eqe@commentChkMsg}

```

The macro `\includeexersolutions` is defined in `eqexam.def`. We execute the command `\include@solutions` before the `web` package is loaded. The `web` package has a `\AtEndDocument` as well, and inserts a new page that we don't want.

```
368 \AtEndDocument{\includeexersolutions}
```

If user has specified one of the pdf options (pdf, links, online, email), we bring in the `web` package.

```

369 \@ifpackageloaded{web}{\let\load@web\eqe@YES}{%
370     \ifx\load@web\eqe@YES\ifnum\eqe@drivernum=5
371         \PackageInfo{eqexam}{You have not selected a driver %
372             for eqexam. Perhaps the\MessageBreak
373             driver is introduced through web.cfg}\fi
374     \expandafter\RequirePackage\expandafter[\eqe@webOpts]{web}%
375     \edef\@pdfcreator{@pdfcreator, The eqexam Package}\fi
376 }

```

If user has specified links, online or email, we bring in the `exerquiz` package.

```

377 \@ifpackageloaded{exerquiz}{\let\load@exerquiz\eqe@YES}{%
378     \let\symbolchoice@gobble
379     \ifx\load@exerquiz\eqe@YES\expandafter
380         \RequirePackage\expandafter[\eqe@eqOpts]{exerquiz}[2011/08/30]

```

We input `exerquiz` with the `nodljs`, we don't need all the JavaScript to process interactive shortquizzes or quizzes, but we do want the option of adding in document JavaScript, so after we input `exerquiz`, we set the switches to allow these features.

```

381     \let\importdljs\eqe@YES\let\execjs\eqe@YES
382     \fi
383 }
384 \@ifpackageloaded{eforms}{}{%

```

If `eforms` is not loaded, we define `\symbolchoice`, which is defined in `eforms` to gobble up its argument, we don't need it.

```

385     \let\symbolchoice\@gobble
386 }

```

Here is a fix to a problem I've been having previewing in dviwindo. I've traced the problem down to `\@pdfviewparams`. Redefining `\@pdfviewparams` as follows.

```

387 \def\eqDvipsone{dvipsone}
388 \@ifpackageloaded{hyperref}
389   {\ifx\eqDriverName\eqDvipsone
390     \renewcommand{\@pdfviewparams}{ null null null}\fi
391   }{\let\textorpdfstring{\firstoftwo}}

```

Now that we have possibly input `web` or `exerquiz`, we need to restore the authors options.

```

392 \let\eq@online\savedeq@online
393 \let\ifeq@solutionssafter\savedifeq@solutionssafter
394 \def\ifsolutionssafter{\ifeq@solutionssafter} % user interface
395 \let\ifeq@hidesolution\savedifeq@hidesolution
396 \let\ifeq@globalshowsolutions\savedifeq@globalshowsolutions
397 \let\ifeq@nosolutions\savedifeq@nosolutions
398 \let\ifeq@proofing\savedifeq@proofing
399 \let\ifeq@nolink\savedifeq@nolink
400 \let\ifpreview\savedifpreview
401 \let\ifeqforpaper\savedifeqforpaper

```

Other packages of interest.

```

402 \RequirePackage{calc}
403 \RequirePackage{pifont}
404 \RequirePackage{array}

```

Here, I input the `verbatim` package after the `comment` package.

```

405 \RequirePackage{verbatim}
406 \@ifundefined{dlcomment}{\typeout{!! defining dlcomment}%
407   \let\dlcomment\comment
408   \let\enddlcomment\endcomment
409   \let\eqSavedComment\dlcomment
410   \let\endeqSavedComment\enddlcomment
411 }{}}

```

When constructing paper tests, I often use a multi-column format for some of the questions, so let's require this package

```

412 \RequirePackage{multicol}
413 \setlength{\columnseprule}{.4pt}
414 \raggedcolumns\multicolsep=3pt
415 \newcommand{\setmulticolprob}{%
416   \setlength{\linewidth}{\linewidth+\eqemargin}}

```

For the `fortextbook` option, we require `eso-pic`.

```

417 \edef\eqe@reqPack{\ifeqfortextbook\noexpand\RequirePackage{eso-pic}\else
418 \relax\fi}
419 \eqe@reqPack

```

We've processed the options, I need to detect whether the document author has not chosen any solutions options.

```
420 \ifvspacewithsolns\solutionsAtEndtrue\fi
421 \ifanswerkey\solutionsAtEndfalse\fi
422 \ifeq@nosolutions\solutionsAtEndfalse\fi
423 \ifeq@solutionsafter\solutionsAtEndfalse\fi
```

## 4 Page Layout

(2011/05/08) The revised version of `eqexam` allows the document author to more easily design the size of the page; the new version makes all content inside the `exam` environment into a list, this gives us better control over the margins and spacing.

`\eqexammargin` (2011/05/08) Use this command to set the margin for the `exam` environment.

```
424 \@ifundefined{\eqemargin}{\newlength{\eqemargin}}{%
425 \providecommand{\prbDecPt}[1]{\def\eqe@decPointPrb{\#1}}
426 \def\eqe@decPointPrb{. }\def\eqe@dpsepPrb{\ }
427 \providecommand{\prbPrtsep}[1]{\def\eqe@prtsepPrb{\#1}}
428 \def\eqe@prtsepPrb{\ }
429 \providecommand{\prbNumPrtsep}[1]{\def\eqe@hspannerPrb{\#1}}
430 \def\eqe@hspannerPrb{\ }
431 \newcommand{\eqexammargin}[2][\normalsize\normalfont\bfseries]{%
432 \settowidth{\eqemargin}{#1#2\eqe@decPointPrb\eqe@hspannerPrb}}}
```

(2011/05/08) The default margin for the `eqexam` environment, two digits and a space.

```
433 \eqexammargin{00}
```

```
434 \def\eqe@hspannerSoln{\ } % space after prob number
435 \providecommand{\solNumPrtsep}[1]{\def\eqe@hspannerSoln{\#1}}
```

`\eqeSetExamPageParams` (2011/05/08) The default spacing maximizes the amount of space on the page.

```
436 \newcommand{\eqeSetExamPageParams}{%
437 \setlength{\headheight}{12pt}
438 \setlength{\topmargin}{-.5in}
439 \setlength{\headsep}{20pt}
440 \setlength{\oddsidemargin}{0pt}
441 \setlength{\evensidemargin}{0pt}
442 \setlength{\marginparsep}{11pt}
443 \setlength{\marginparwidth}{35pt}
444 \setlength{\footskip}{11pt}
445 }
```

`\eqExamPageLayout` Set the basic parameters of this exam page package

```
446 \newcommand{\eqExamPageLayout}{%
447 \setlength{\textwidth}{\paperwidth}
448 \addtolength{\textwidth}{-2in}
449 \addtolength{\textwidth}{-\oddsidemargin}}
```

```

450      \setlength{\textheight}{\paperheight}
451      \addtolength{\textheight}{-2in}
452      \addtolength{\textheight}{-\headheight}
453      \addtolength{\textheight}{-\headsep}
454      \addtolength{\textheight}{-\topmargin}
455      \addtolength{\textheight}{-\footskip}
456 }

(2011/05/08) If \usecustomdesign is used it is expected that \eqeSetExamPageParams and \eqeSetExamPageLayout are redefined in the preamble, otherwise, we set up the standard parameters; otherwise

457 \ifeqcustomdesign\else
458 \eqeSetExamPageParams
459 \eqExamPageLayout
460 \fi

```

A simple page layout scheme for this exam.

```

461 \newcommand{\ps@eqExamheadings}
462 {%
463     \renewcommand{\@oddhead}{%
464         \normalfont\normalsize\ifnum\value{page}<2
465             \hfil\else\eqExamRunHead\fi}%
466     \renewcommand{\@evenhead}{\@oddhead}
467     \renewcommand{\@oddfoot}{\settotalsbox\runExamFooter}
468     \renewcommand{\@evenfoot}{\@oddfoot}
469 }
470 \raggedbottom

```

## 5 Counters, Lengths and Tokens

`\eqpointsofar`  
`\eqpointsthispage`  
`\eq@numparts`

Some counters to keep track of things. The first two counters keep track, respectively, of the total points so far up the current page, and the number of points on the current page. The counter `\eq@numparts` holds the number of parts of the multi-part question.

```

471 \newcount\eqe@tempcpta
472 \newcounter{eqpointsofar}
473 \newcounter{eqpointsthispage}
474 \newcounter{eq@numparts}
475 \newcounter{eq@count}
476 \newtoks\partNames \partNames={}
477 \newlength{\eq@tmpLengthA}
478 \newlength{\eq@tmpLengthB}
479 \newbox{\eq@pointbox}
480 \newlength{\eq@pointboxtotalheight}

```

Some scratch registers to do calc calculations.

```

481 \newlength{\eqetmpLengthA}
482 \newlength{\eqetmpLengthB}

```

## 6 Some Macros to Support the Options

We make a few definitions to support various options.

```

483 \def\PointsOnLeft{\def\@reportpoints{1}\let\marginpoints\eqleftmargin}
484 \def\PointsOnRight{\def\@reportpoints{2}\relax
485   \let\marginpoints\eqrightmarginbox}
486 \def\PointsOnBothSides{\def\@reportpoints{3}\relax
487   \let\marginpoints\eqbothmargins}
488 \newif\ifeqe@nopoints \eqe@nopointsfalse
489 \def\NoPoints{\if\isInExamEnv\eqe@NO
490   \eqe@nopointstrue\def\@reporttotals{0}\let\totalsbox=\hfil
491   \let\marginpoints\empty\let\eq@nosummarytotals\eqe@YES\else
492   \PackageWarning{eqexam}{The \string\NoPoints\space ignored;
493   it needs to be executed\MessageBreak outside of an
494   exam environment}\fi}
495 \def\TotalsOnLeft{\def\@reporttotals{1}\def\totalsbox{\totalsboxleft}}
496 \def\TotalsOnRight{\def\@reporttotals{2}\def\totalsbox{\totalsboxright}}
497 \def\noZeroTotals{\let\eqe@zerototalsallowed\eqe@NO}
498 \def\allowZeroTotals{\let\eqe@zerototalsallowed\eqe@YES}
499 \allowZeroTotals
500 \def\NoTotals{\def\@reporttotals{0}\let\totalsbox=\hfil}
501 \def\SummaryTotalsOn{\let\eq@nosummarytotals\eqe@NO}
502 \def\SummaryTotalsOff{\let\eq@nosummarytotals\eqe@YES}
503 \def\eoetotal0ff{\let\eq@parttotals\eqe@NO}
504 \def\eoetotal0n{\let\eq@parttotals\eqe@YES}
505 \def\separationrule0n{\let\eqx@separationrule\eqe@YES}
506 \def\separationrule0ff{\let\eqx@separationrule\eqe@NO}
507 \def\AllowFitItIn{\global\let\eq@fititin\eqfittitin}
508 \def\DoNotFitItIn{\global\let\eq@fititin@gobble}

509 \def\NoSolutions{\eq@nolinktrue\eq@nosolutionstrue
510   \displayworkareatruer
511 \onlypreamble\NoSolutions

```

Added `\chngToNoSolns`, useful for book authors that want to switch between `\AnswerKey`, `\chngToNoSolns`, and `\SolutionsAtEnd`.

```

512 \def\chngToNoSolns{\solutionsAtEndfalse\answerkeyfalse
513   \eq@proofingfalse\eq@solutionsafterfalse
514   \eq@nosolutionstrue\displayworkareatruer}

```

`\vspacewithkeyOn` User interface to keeping the declare vspace, even when the `answerkey` (or `solutionsafter`) option is taken. The switch `\ifkeepdeclaredvspacing` is defined in `eqexam.def/exerquiz`.

```

515 \def\vspacewithkeyOn{\keepdeclaredvspacingtrue}
516 \def\vspacewithkeyOff{\keepdeclaredvspacingfalse}

```

`\displayPointsOn` `\displayPointsOn` displays the points, if not otherwise overridden and the command `\displayPointsOff` turns off the display of points. In either case, points are calculated.

```

517 \newif\ifdisplay@yPoints\display@yPointstrue
518 \newcommand{\displayPointsOn}{\display@yPointstrue}
519 \newcommand{\displayPointsOff}{\display@yPointsfalse}
520 \newif\ifl@stDispl@yPoints\l@stDispl@yPointsfalse

\encloseProblemsWith \encloseProblemsWith to support the solutionsonly option
521 \def\encloseProblemsWith#1{%
522     \ifsolutionsonly\excludedcomment{#1}\else
523     \includecomment{#1}\fi
524 }

```

## 7 Colors

\proofingsymbolColor Here we list commands for controlling colors. There are some other colors defined in the stand alone code.

```

\eqCommentsColor 525 \providecommand{\proofingsymbolColor}[1]{\def\@proofingsymbolColor{#1}}
\universityColor 526 \proofingsymbolColor{red}
\titleColor 527 \providecommand{\instructionsColor}[1]{\def\@instructionsColor{#1}}
\authorColor 528 \instructionsColor{blue}
\subjectColor 529 \providecommand{\eqCommentsColor}[1]{\def\@eqCommentsColor{#1}}
\linkcolor 530 \eqCommentsColor{blue}
\nolinkcolor 531 \providecommand{\eqCommentsColorBody}[1]{\def\@eqCommentsColorBody{#1}}
\fillinColor 532 \eqCommentsColorBody{black}
\forceNoColor 533 \providecommand{\universityColor}[1]{\def\webuniversity@color{#1}}
\forceNoColor 534 \universityColor{blue}

\eqEndExamTotalColor 535 \providecommand{\titleColor}[1]{\def\webtitle@color{#1}}
\titleColor 536 \titleColor{black}
\providecommand{\authorColor}[1]{\def\webauthor@color{#1}}
\authorColor 538 \authorColor{black}
\providecommand{\subjectColor}[1]{\def\websubject@color{#1}}
\subjectColor 540 \subjectColor{blue}
\providecommand{\linkcolor}[1]{\def\@linkcolor{#1}}
\linkcolor 542 \linkcolor{blue}
\providecommand{\nolinkcolor}[1]{\def\@nolinkcolor{#1}}
\nolinkcolor 544 \nolinkcolor{black}
\providecommand{\eqEndExamTotalColor}[1]{\def\endexamtotal@color{#1}}
\eqEndExamTotalColor 546 \eqEndExamTotalColor{black}
\fillinColor 547 \newcommand\fillinColor[1]{\def\eq@fillinColor{#1}}\fillinColor{red}
\providecommand{\sectionColor}[1]{\def\web@sectionsColorOld{#1}}
\sectionColor 549 \def\aeb@sectioncolor{#1}
\sectionColor 550 \sectionColor{blue}
\def\forceNoColorSet{\proofingsymbolColor{black}%
\instructionsColor{black}%
\eqCommentsColor{black}\universityColor{black}%
\titleColor{black}\authorColor{black}%
\subjectColor{black}\linkcolor{black}%
\nolinkcolor{black}\fillinColor{black}%
\instructionsColor{black}\eqCommentsColor{black}%

```

```

558     \eqCommentsColorBody{black}%
559     \eqEndExamTotalColor{black}\ckboxColor{}%
560     \ckcirColor{}\if\load@web\eqe@YES
561         \sectionColor{black}\fi
562 }
563 \ifForceNoColor
564     \AtBeginDocument{\forceNoColorSet}
565 \fi
566 \newcommand{\forceNoColor}{\ifForceNoColor\else\ForceNoColortrue
567     \AtBeginDocument{\forceNoColorSet}\fi}

\ckboxColor The \ckboxColor provides color for the MC and MS boxes, then a PDF-related
\ckcirColor option is not in effect, while \ckcirColor provides color for circular checkboxes.
Usually, these are black or both the same color.

568 \providecommand{\ckboxColor}[1]{\def\@rgi{#1}\ifx\@rgi\@empty
569     \let\ckbox@Color\relax\else
570     \def\ckbox@Color{\color{#1}}\fi}\ckboxColor{}
571 \providecommand{\ckcirColor}[1]{\def\eq@rgi{#1}\ifx\eq@rgi\@empty
572     \let\ckcir@Color\relax\else
573     \def\ckcir@Color{\color{#1}}\fi}\ckcirColor{}

```

## 8 Version Control

Here are some simple macros use to create two versions, version A and version B, of the same test.

\examNum Convenience macro for holding the exam number. It sets the value of \nExam.

```

574 \def\examNum#1{\def\nExam{#1}}
575 \examNum{1}

```

\Exam Convenience macros for titling the exam. Usage:  
\sExam \VersionAtext{Test~\nExam--Version A}  
\VersionBtext{Test~\nExam--Version B}  
\shortVersionAtext{T\nExam A}  
\shortVersionBtext{T\nExam B}

```

\examNum{1}
\forVersion{c}
\subject[C3]{Calculus III}
\title[\sExam]{\Exam}
\author{Dr.\ D. P. Story}

```

These next two definitions are overwritten by the two commands \longTitleText and \shortTitleText.

```

576 \def\Exam{\ifAB{\eq@VersionAtext}{\eq@VersionBtext}}
577 \def\sExam{\ifAB{\eq@shortVersionAtext}{\eq@shortVersionBtext}}

```

\VersionAtext Convenience macros for entering the text for the title, long and short for versions  
A and B.

\shortVersionAtext  
\shortVersionBtext

```

578 \def\VersionAtext{\def\eq@VersionAtext{#1}}
579 \def\VersionBtext{\def\eq@VersionBtext{#1}}
580 \def\shortVersionAtext{\def\eq@shortVersionAtext{#1}}
581 \def\shortVersionBtext{\def\eq@shortVersionBtext{#1}}
582 \VersionAtext{Exam~\nExam--Version A}
583 \VersionBtext{Exam~\nExam--Version B}
584 \shortVersionAtext{Exam~\nExam A}
585 \shortVersionBtext{Exam~\nExam B}

```

In this section we introduce a new set of commands that supersedes the commands defined above. Those commands were limited to only two versions. The ones below can handle up to 26 versions.

```

586 \newtoks\eqtemptokena
587 \newtoks\eqtempokenb

```

`\numVersions` In the preamble, declare the number of versions for this document using `\numVersions`, e.g., `\numVersions{3}`. This sets the value of `\eq@nVersions`

```

588 \def\numVersions#1{\ifnum#1>26\def\eq@nVersions{26}%
589   \PackageWarning{eqexam}{The value of \string\numVersions\space is
590   too large. \MessageBreak Choose a natural number less than 27}%
591   \else\def\eq@nVersions{#1}\fi}

```

`\longTitleText` Next we state the long and short titles for our document, one for each of our declared number of versions given earlier. For example, we can use the value `\nExam` in our titles. Usage:

```

\endshortTitleText
\longTitleText
  {Test~\nExam--Version A}
  {Test~\nExam--Version B}
  {Test~\nExam--Make Up}
\endlongTitleText
\shortTitleText
  {T\nExam A}
  {T\nExam B}
  {T\nExam MU}
\endshortTitleText

```

I've added markers that delimit the end of the arguments. In this way, the end of the list of titles can be detected, even though the number of titles is not the same as what is declared by the `\numVersions`.

If there are more titles than what is declared, the rest are absorbed (gobbled). If there are fewer titles than declared, a L<sup>A</sup>T<sub>E</sub>X package error is generated, and substitute titles are generated. Modified `\longTitleText` and `\shortTitleText` to have an optional argument (A-Z;a-z). You can select a particular title from a list of titles. If no optional argument is passed, then the title determined by `\forVersion` is used.

```

592 \newcommand{\longTitleText}[1][]{%
593   \ifeqglobalversion\let\eq@selectedVersion@save\eq@selectedVersion
594   \else\let\eq@selectedVersion@save\relax\fi

```

```

595      \uppercase{\def\eqe@localTextTitle{#1}}%
596      \ifx\eqe@localTextTitle\empty\else
597      \expandafter\forVersion\expandafter{\eqe@localTextTitle}\fi
598      \eqe@contTitleText{\Exam}{\endlongTitleText}%
599 }
600 \def\endlongTitleText{l}
601 \newcommand{\shortTitleText}[1][]{%
602     \ifeqglobalversion\let\eq@selectedVersion@save\eq@selectedVersion
603     \else\let\eq@selectedVersion@save\relax\fi
604     \uppercase{\def\eqe@localTextTitle{#1}}%
605     \ifx\eqe@localTextTitle\empty\else
606     \expandafter\forVersion\expandafter{\eqe@localTextTitle}\fi
607     \eqe@contTitleText{\sExam}{\endshortTitleText}%
608 }
609 \def\endshortTitleText{s}

```

Both title commands, above, call this macro which sets the environment for `\@gatherTitleText`, which gathers the list of titles.

```

610 \def\eqe@contTitleText#1#2{%
611     \setcounter{eq@count}{0}%
612     \eqtemptokena={}\\let\\endtitleMarker#2
613     \@gatherTitleText{#1}%
614 }

```

This command gathers each title and places it as the argument of a `\v<LETTTER>` command. These are accumulated in token registers then saved in `\Exam` and `\sExam`.

```

615 \def\@gatherTitleText#1#2{%
616     \def\eqe@argii{#2}
617     \if\endtitleMarker\eqe@argii

```

Encountered the end marker. See if we have collected the correct number of titles declared. If we have collected too few, we note an warning in the log, and create titles.

```

618     \ifnum\value{eq@count}>\eq@nVersions\let\eqe@next\relax
619     \else\def\eqe@next{\eq@shortTitlesFix{#1}}\fi
620 \else
621 \stepcounter{eq@count}
622     \eqtemptokenb=\expandafter{#2}
623     \xdef#1{\the\eqtemptokena\expandafter\noexpand
624     \csname v\Alph{eq@count}\endcsname{\the\eqtemptokenb}}
625     \xdef\sExam{\the\eqtemptokena\expandafter\noexpand
626     \csname v\Alph{eq@count}\endcsname{\the\eqtemptokenb}}
627     \eqtemptokena=\expandafter{#1}
628     \ifnum\value{eq@count}<\eq@nVersions
629         \def\eqe@next{\@gatherTitleText{#1}}%
630     \else
631         \def\eqe@next{%
632             \if\endtitleMarker\endlongTitleText
633                 \expandafter\eqe@absorbTokensLong

```

```

634          \else
635              \expandafter\eqe@absorbTokensShort
636          \fi
637      }%
638      \fi
639  \fi
640  \eqe@next
641 }
642 \long\def\eqe@absorbTokensLong#1\endlongTitleText{%
643     \protected@xdef{\Exam}\ifx\eq@selectedVersion@save\relax
644     \eqe@offVersion\else\expandafter\forVersion\expandafter
645     {\eq@selectedVersion@save}\fi}
646 \long\def\eqe@absorbTokensShort#1\endshortTitleText{%
647     \protected@xdef{\sExam}\ifx\eq@selectedVersion@save\relax
648     \eqe@offVersion\else\expandafter\forVersion\expandafter
649     {\eq@selectedVersion@save}\fi}

```

We have reached `\endtitleMarker`, but the count is still less than `\eq@nVersions`, so we'll warn the user, and create titles for user.

```

650 \def\eq@shortTitlesFix#1{%
651     \PackageWarning{eqexam}{You have defined an insufficient number
652     of titles\MessageBreak for the number of versions declared in
653     \string\numVersions.\MessageBreak Please fix the problem}%
654     \stepcounter{eq@count}%
655     \if\endtitleMarker\endlongTitleText
656         \edef\eqe@tmp{\noexpand\gatherTitleText{\noexpand#1}
657             {??---Title \# \the\value{eq@count}---??}%
658             \noexpand\endlongTitleText}
659     \else
660         \edef\eqe@tmp{\noexpand\gatherTitleText{\noexpand#1}
661             {T\#\the\value{eq@count}??}\noexpand\endshortTitleText}
662     \fi
663     \addtocounter{eq@count}{-1}%
664     \eqe@tmp
665 }

```

Here, we define `\ifAB` so that document under the old system still work properly, I hope. Usage of `\ifAB` at this point is discouraged.

```

666 \def\ifAB#1#2{\if\eq@selectedVersion A#1%
667     \else\if\eq@selectedVersion B#2\fi\fi}
668 \def\eq@replaceToken#1{#1}

```

`\forVersion` Here is the command that does all the work. It creates alternate text macros for each of the versions declared using `\numVersions`.

For example, assuming `\numVersions{3}` appeared earlier, the command `\forVersion{a}` (or `\forVersion{A}`) defines 3 text commands `\vA`, `\vB` and `\vC`, each taking one argument, the text you want to display:

Name the `\vA{place}\vB{date}\vC{year}` of the signing of the Declaration of independence.

Since we said `forVersion{a}` only the `\vA` text is displayed, the others are gobbled up, etc. But wait, the `\forVersion` does more than that! It also creates a series of comment environments `\begin{verA}/\end{verA}`, `\begin{verB}/\end{verB}`, `\begin{verC}/\end{verC}`, etc., where only the version for which this compile applies will be typeset, the others are commented out.

```
\numVersions{3}
\forVersion{b}
...
\begin{document}
...
Solve the equation for $\vA{x}\vB{y}\vC{z}$:
\[
\begin{verA}
    2x + 4 = 7
\end{verA}
\begin{verB}
    5y + 2 = 4
\end{verB}
\begin{verC}
    3z - 2 = 2
\end{verC}
\]
669 \newif\ifeqglobalversion \eqglobalversionfalse
670 \newif\ifeqlocalversion \eqlocalversionfalse
671 \newif\if@templocalversion \templocalversionfalse
672 \def\eqe@initializeMultiVersions{%
673   \let\save@message\message\let\message\@gobble
674   \cftfor\eqe@tmp:=ABCDEFGHIJKLMNOPQRSTUVWXYZ\do{%
675     \csarg\let{\v\eqe@tmp}\@gobble
676     \edef\exp@temp{\noexpand\excludecomment{ver\eqe@tmp}}\exp@temp
677     \csarg\let{Afterver\eqe@tmp Comment}\aebc@end
678   }\let\message\save@message
679 }
680 \AtBeginDocument{\let\eqe@initializeMultiVersions\relax}
```

(09/10/04) Trying to fix a bug in the case when the version selected is greater than the number of versions available for a given problem; that is, when modular arithmetic occurs (in `\selectVersion`).

```
681 \let\eqe@onVersion\@empty
682 \def\eqe@onVersion{\g@addto@macro\eqe@onVersion}
683 \let\eqe@offVersion\@empty
684 \def\eqe@offVersion{\g@addto@macro\eqe@offVersion}
685 \let\eqe@holdTemp\@empty
686 \def\eqe@holdTemp{\g@addto@macro\eqe@holdTemp}
```

Two commands to turn on and off versions (the `\v<LETTER>` and the `ver<LETTER>` environment).

Throughout the definitions below, we use `\csarg`, a command that is defined in the `comment` package.

```

687 \def\eqe@showArg#1{#1}
688 \def\eqe@turnOnComment#1{%
689 %   \csarg\let{v#1}\empty
690   \csarg\let{v#1}\eqe@showArg
691   \edef\exp@temp{\noexpand\includecomment{ver#1}}\exp@temp
692 }
693 \def\eqe@turnOffComment#1{%
694   \csarg\let{v#1}\gobble
695   \edef\exp@temp{\noexpand\excludecomment{ver#1}}\exp@temp
696   \csarg\let{Afterver#1Comment}\aebc@end
697 }

```

`\selVersion` Finally, the `\forVersion` command. `\selVersion` holds the version selected in upper-case.

```

698 \def\forVersion#1%
699 {%
700   \eqe@initializeMultiVersions
701   \let\eqe@@onVersion\empty
702   \let\eqe@@offVersion\empty
703   \global\eqglocalversiontrue
704   \setcounter{eq@count}{0}%
705   \uppercase{\edef\eq@selectedVersion{#1}}%
706   \edef\selVersion{\eq@selectedVersion}%
707   \@ifundefined{eq@nVersions}{\PackageInfo{eqexam}{%
708     \string\numVersions\space has not been declared, \MessageBreak
709     taking the number of versions to be 2.}\def\eq@nVersions{2}}{%
710   \loop
711     \stepcounter{eq@count}%
712     \expandafter\if\Alph{eq@count}\eq@selectedVersion
713       \xdef\eq@nSelectedVersion{\the\value{eq@count}}%
714       \setcounter{eq@count}{27}\fi
715     \ifnum\value{eq@count}<26\repeat
716     \ifnum\eq@nSelectedVersion >\eq@nVersions
717       \PackageError{eqexam}{%
718         The value of \string\forVersion
719         \space(\eq@selectedVersion)\MessageBreak
720         exceeds the value of \string\numVersions\space
721         (\eq@nVersions)}%
722       {Decrease the value of \string\forVersion.}%
723     \fi
724     \setcounter{eq@count}{0}%
725     \let\save@message\message\let\message\gobble
726   \loop
727     \stepcounter{eq@count}%
728     \csarg\let{After\Alph{eq@count}Comment}\relax
729     \lowercase{%
730       \if#1\alph{eq@count}%

```

```

732           \eqe@turnOnComment{\Alph{eq@count}}%
(09/10/04) Save the commands for turning on the version with \eqe@onVersion,
and for turning it off with \eqe@offVeresion.
733           \edef\temp@exp{\noexpand
734             \eqe@turnOnComment{\Alph{eq@count}}%
735             \expandafter\eqe@onVersion\expandafter{\temp@exp}%
736             \edef\temp@exp{\noexpand
737               \eqe@turnOffComment{\Alph{eq@count}}%
738               \expandafter\eqe@offVersion\expandafter{\temp@exp}%
739             \else
740               \eqe@turnOffComment{\Alph{eq@count}}%
741             \fi
742           }%
743           \ifnum\value{eq@count}<\eq@nVersions\repeat
744           \let\message\save@message
745 }

```

Let us assume version A initially, user with reset this in document.

```

746 \AtEndOfPackage{\numVersions{26}\forVersion{A}%
747   \eq@renditionOptions}

```

**\selectVersion** When an exam has questions in which the number of variations are not all the same, then you can locally change the version between problems. If the first argument is empty, the first variation is chosen. The syntax is

```
\selectVersion{2}{3}
```

This command says that the next problem has 3 variations, and here we select the second one.

```

748 \def\selectVersion#1#2{%
749   #1 \le #2
    \xdef\nLocalSelection{#1}\xdef\nLocalVersions{#2}%

```

If obey local version is in effect and the local selection is not empty, no modular arithmetic is needed in the first loop below of \nLocalSelection.

```

750   \let\needsModArith\eqe@YES
751   \ifeqobeylocalversion\ifx\nLocalSelection\empty\else
752     \let\needsModArith\eqe@NO\fi\fi

```

When the solutions appear at the end of the document, the version may not match the version for the question. We need to use a private hook defined in *exerquiz* (and *eqexam.def*) to reproduce the same settings going into each solution at the end. So, we write the \selectVersion to the solution file.

```

753   \edef\exer@solnheadhook{%
754     \string\selectVersion{#1}{#2}%

```

Turn off messaging.

```
755   \let\save@message\message\let\message\@gobble
```

Reset the selected version, the one selected in the preamble. A previous problem may have changed the version due to modular arithmetic.

```

756   \eqe@@onVersion
757   \ifx\eqe@@holdTemp\empty\else

```

If `\eqe@holdTemp` is non-empty, this means that modular arithmetic was performed on the previous problem. We need to turn on the original choice, and turn off the temporary choice, then clear the command `\eqe@@holdTemp`.

```
758      \eqe@@onVersion\eqe@@holdTemp
759      \let\eqe@@holdTemp\@empty
760  \fi
```

If `\eqglobalversion` is true, then a `\forVersion` has been executed. If the number of versions declared by `\numVersions` is greater than the number of local versions for this problem, then we perform modular arithmetic to get an appropriate alternative. It may be necessary to temporarily put `\eqobeylocalversion` to true to accomplish, but we use change it back at the end.

```
761 \ifx\needsModArith\eqe@YES
762   \ifeqglobalversion\ifnum\eq@nSelectedVersion>\nLocalVersions
```

If we perform modular arithmetic, turn off original choice.

```
763   \eqe@@offVersion
```

Now perform mod arithmetic

```
764   {\count0=\eq@nSelectedVersion \count2=\count0
765     \advance\count0by-1 \divide\count0by\nLocalVersions
766     \multiply\count0by\nLocalVersions \% \count2=\eq@nSelectedVersion
767     \advance\count2by-\count0
768     \xdef\nLocalSelection{\the\count2 }%
769     \ifeqobeylocalversion\else
770       \global\@templocalversiontrue
771       \global\eqobeylocalversiontrue\fi}%
772   \global\let\eqe@@holdTemp\@empty
773 \fi\fi
774 \fi
775 \ifeqobeylocalversion
776   \global\eqlocalversiontrue
777   \setcounter{eq@count}{0}%
```

If local selection is empty, use the version requested by `\forVersion`, modular arithmetic may have to be performed. arithmetic to resolve the matter

```
778   \ifx\nLocalSelection\@empty
779     \def\nLocalSelection{\eq@nSelectedVersion}%
780   \fi
```

If local selection exceeds number of local versions, use modular arithmetic to resolve the matter

```
781   \ifnum\nLocalSelection>\nLocalVersions
782     {\count0=\nLocalSelection
783      \count2=\count0
784      \advance\count0by-1 \divide\count0by\nLocalVersions
785      \multiply\count0by\nLocalVersions
786      \advance\count2by-\count0
787      \xdef\nLocalSelection{\the\count2 }%}
788   \fi
789   \let\save@message\message\let\message\@gobble
```

```

790     \loop
791         \stepcounter{eq@count}%
792         \csarg\let{Afterver}\Alph{eq@count}Comment}\aebc@end
793         \lowercase
794         {%
795             \ifnum\value{eq@count}=\nLocalSelection
796                 \eqe@turnOnComment{\Alph{eq@count}}%
797                 \edef\temp@exp{\noexpand
798                     \eqe@turnOffComment{\Alph{eq@count}}}%
799                 \expandafter\eqe@holdTemp\expandafter{\temp@exp}%
800             \else
801                 \eqe@turnOffComment{\Alph{eq@count}}%
802             \fi
803         }%
804         \ifnum\value{eq@count}<\nLocalVersions\repeat
805         \let\message\save@message
806     \fi
807     \if@templocalversion\global\eqobeylocalversionfalse\fi
added 09/10/03 reset back to default
808     \templocalversionfalse
809     \let\message\save@message
810 }

```

## 9 Title Definitions from Web

```

\ttitle Make Title Definitions taken from the Web package. This is to maintain compatibility with Web.
\subject
\author 811 \@ifpackageloaded{web}{}{%
\email 812   \ifpackageloaded{hyperref}{}{\let\texorpdfstring\@firstoftwo}%
\keywords 813   \let\web@save@title\title
\university 814   \def\title{\@ifnextchar[\{@web@title\}@web@title[]}}
815   \def@web@title[#1]#2{\gdef\webtitle{#2}%
816     \ifundefined{hypersetup}{}{\hypersetup{pdftitle={#2}}%}
817     \def\webArg[#1]\ifx\webArg\empty\gdef\shortwebtitle{#2}\else
818       \gdef\shortwebtitle{#1}\fi\web@save@title{#2}}
819   \let\web@saved@author\author
820   \def@author#1{\gdef\webauthor{#1}%
821     \ifundefined{hypersetup}{}{\hypersetup{pdfauthor={#1}}%}
822     \web@saved@author{#1}}
823   \def\subject{\@ifnextchar[\{@subject\}@subject[]}}
824   \def@subject[#1]#2{\def\webArg{#1}%
825     \ifx\webArg\empty\gdef\shortwebsubject{#2}\else
826       \gdef\shortwebsubject{#1}\fi\gdef\websubject{#2}%
827       \ifundefined{hypersetup}{}{\hypersetup{pdfsubject={#2}}%}
828   \def@email#1{\gdef\webemail{#1}}
829   \def\keywords#1{\gdef\webkeywords{#1}%
830     \ifundefined{hypersetup}{}{\hypersetup{pdfkeywords={#1}}%}
831   \def\university#1{\gdef\webuniversity{#1}}

```

```

832     \def\copyrightyears{\gdef\webcopyrightyears{#1}}
833     \def\version#1{\gdef\web@version@value{#1}%
834         \edef\webversion{\ifx\web@version@value\empty\else
835             \noexpand\web@versionlabel\noexpand\
836             \noexpand\web@version@value\fi}%
837     }
838     \let\web@version@value\empty
839     \def\versionLabel#1{\def\web@versionlabel{#1}%
840         \versionLabel{Version}
841         \def\web@toc{Table of Contents}
842         \def\web@continued{cont.}%
843 % set some defaults
844         \title{}\author{}\email{}\subject{}\keywords{}\university{}%
845         \providecommand{\optionalPageMatter}[2][]{%
846             \def\optionalpagematter{#2}%
847         \def\optionalpagematter{}%
848 }

```

**\date** L<sup>A</sup>T<sub>E</sub>X (T<sub>E</sub>X) defines a **\date** command that is also used by eqexam.

```

849 \def\duedate#1{\def\theduedate{#1}%
850 \duedate{}}

```

**\duedate** In addition to these, we also define a **\duedate** macro, may be useful for writing assignments with a due date.

```

851 \def\duedate#1{\def\theduedate{#1}%
852 \duedate{}}

```

**\thisterm** The command **\thisterm** can be used in the **\date** field to indicate the term of this test, for example, **\date{\thisterm, \the\year}** This command may be redefined to conform to your own academic terms.

```

853 \newcommand\thisterm{%
854 % if prior to June (Jan--May)
855   \ifnum\month<6Spring\else
856 % if prior to August (June-July)
857   \ifnum\month<8Summer\else
858 % August or later; if Sept--Dec
859   \ifnum\month>8Fall\else
860 % Month of August; if after 25th
861   \ifnum\day>25Fall\else
862 % if it's 25th or earlier in month of August
863   Summer\fi\fi\fi\fi
864 }

```

## 10 Identification Information

We define a series of commands in support of building an exam: Lines to identify the student and his/her student id (SID), the instructors email address, the name of the test and the course.

`\eqExamName` provides a line for the student to enter his/her name into the exam. The command `\examNameLabel` can be used to define the name label, the default is Name:

Will insert a text box as well if the `option` is taken in addition to `nosolutions` and with `solutionsafter` not taken. This macro defines `\eq@ExamName`, which actually contains the code. The first (optional) parameter is passed to `\insTxtFieldIdInfo`, and can be used to change the appearance of the text field created; the second required parameter is the width of the field.

```
865 \newcommand{\examAnsKeyLabel}[1]{%
866     \def\@examAnsKeyLabel{\ifanswerkey\space #1\fi}}
867 \examAnsKeyLabel{Answer Key}
868 \newcommand\examNameLabel[1]{\gdef\@examNameLabel{\#1\@examAnsKeyLabel}}
869 \examNameLabel{Name:}
870 \newcommand{\idinfoHighlight}[1]{\def\eqe@idinfohl{\#1}}
871 \idinfoHighlight{\underbar}
872 \newcommand\eqExamName[2][]{%
873     \def\eqExamName@argi{\#1}\def\eqExamName@argii{\#2}}
874 \def\eq@ExamName{\bgroup
875     \settowidth\eq@tmplengthA{\@examNameLabel\ }%
876     \tempdima=\eqExamName@argii\relax
877     \advance\tempdima by-\eq@tmplengthA
878     \eqe@idinfohl{\makebox[\eqExamName@argii][1]{\@examNameLabel}}%
879     \expandafter\insTxtFieldIdInfo\expandafter[\eqExamName@argi]%
880         {\tempdima}{\IdInfo.Name}\egroup}
```

Here we set the field to be a required field with width of 2.25 inches

```
881 \eqExamName[\Ff\FfRequired]{2.25in}
```

`\eqSID` provides a line for the student to enter his/her ID number (SID).

Will insert a text box as well if the `option` is taken in addition to `nosolutions` and with `solutionsafter` not taken. The first (optional) parameter is passed to `\insTxtFieldIdInfo`, and can be used to change the appearance of the text field created; the second required parameter is the width of the field.

```
882 \newcommand\examSIDLabel[1]{\gdef\@examSIDLabel{\#1}}
883 \examSIDLabel{SID:}
884 \newcommand\eqSID[2][]{\def\eqSID@argi{\#1}\def\eqSID@argii{\#2}}
885 \def\eq@SID{\bgroup\settowidth\eq@tmplengthA{\@examSIDLabel\ }%
886     \tempdima=\eqSID@argii\relax\advance\tempdima by-\eq@tmplengthA
887     \eqe@idinfohl{\makebox[\eqSID@argii][1]{\@examSIDLabel}}%
888     \expandafter\insTxtFieldIdInfo\expandafter[\eqSID@argi]%
889         {\tempdima}{\IdInfo.SID}\egroup}
```

Here we set the field to be a required field with width of 2.25 inches

```
890 \eqSID[\Ff\FfRequired]{2.25in}
```

`\eqEmail` provides a line for the student to enter his/her email address. Useful for documents submitted by email, the instructor can reply.

Will insert a text box as well if the `option` is taken in addition to `nosolutions` and with `solutionsafter` not taken. The first (optional) parameter is passed to `\insTxtFieldIdInfo`, and can be used to change the appearance of the text field created; the second required parameter is the width of the field.

```

891 \newcommand\examEmailLabel[1]{\gdef\@examEmailLabel{\#1}}
892 \examEmailLabel{Email:}
893 \newcommand\eqEmail[2][]{\%
894   \def\eqExam@argi{\#1}\def\eqEmail@argii{\#2}%
895   \gdef\eq@email{\bgroup\settowidth\eq@tmplengthA{\@examEmailLabel\ }%
896     \tempdima=\eqEmail@argii\relax\advance\tempdima by-\eq@tmplengthA
897     \underbar{\makebox[\eqEmail@argii][1]{\@examEmailLabel}}%
898     \expandafter\insTxtFieldIdInfo\expandafter[\eqEmail@argi]%
899     {\tempdima}{\IdInfo.email}\egroup}

```

Here we set the field to be a field with width of 2.25 inches. (Not set to be a required field.)

```
900 \eqEmail{2.25in}
```

**\insTxtFieldIdInfo** The above macros (\eqExamName, \eqSID and \eqEmail) all call this macro, which inserts a Acroforms text field if the option is taken in addition to **nosolutions** and with **solutionsafter** not taken.

The first (optional) parameter is used to change the appearance of the text field. The second parameter is the width of the field, and the third is the field name.

```

901 \def\insTxtFieldIdInfo[#1]#2#3{%
902   @ifundefined{@quiz}{}{\if\eq@online\eq@YES
903     \ifeq@nosolutions\ifeq@solutionsafter\else
904       \raisebox{-1bp}{\makebox[0pt][r]{%
905         \textField[\BC{\#1}{\#3}{\#2}{11bp}]}}%
906     \fi\fi\fi
907   }%
908 }
```

**\SubmitInfo** is required when the **email** option is taken, and should appear in the preamble. The first argument is the URL to the **eqAttach.asp** code on the server, and the second is the email of the instructor is to receive the results. (Multiple recipients can be specified by separating each with a comma.)

```

909 \def\SubmitInfo#1#2{%
910   \def\EqExam@SubmitURL{\#1}\def\@EmailInstr{\#2}%
911 }
```

**\EmailCourseName** is used to specify the course name of the course. The default value for this is **\websubject**, obtained from the **\subject** macro used in the preamble; however, if you want a different name in the email, perhaps with more information included, you can redefine the value using this macro.

```
912 \def\EmailCourseName#1{\def\@EmailCourseName{\#1}}
```

Here's the default value.

```
913 \EmailCourseName{\websubject}
```

**\EmailExamName** is used to specify the exam name of the course. The default value for this is **\webtitle**, obtained from the **\title** macro used in the preamble; however, if you want a different name in the email, perhaps with more information included, you can redefine the value using this macro. (Multiple recipients can be specified by separating each with a comma.)

```

914 \def\EmailExamName#1{\def\@EmailExamName{#1}}
Here's the default value.
915 \EmailExamName{\webtitle}

\EmailSubject The document author mail want a custom subject in the email, instead of the standard one. By using this macro, he can design his own email subject.
916 \def\EmailSubject#1{\def\@EmailSubject{#1}}
Here's the default value, which generates no custom subject line.
917 \EmailSubject{}

In this case eqAttach.asp inserts the standard one.

Exam Results: \webtitle of \websubject

The email would read like "Exam Results: Test 1 of Calculus I", for example.

\ServerRetnMsg Unless submitted in silent mode, the eqAttach.asp returns a message acknowledging the receipt of the data. \ServerRetnMsg is used to customize this message.
918 \def\ServerRetnMsg#1{\def\@ServerRetnMsg{#1}}
Here's the default value, which generates no custom return message
919 \ServerRetnMsg{}


\SubmitButtonLabel is the label that appears on the submit button.
920 \def\SubmitButtonLabel#1{\def\@SubmitButtonLabel{#1}}
Here's the default value.
921 \SubmitButtonLabel{Submit}

\SubmitButton is the macro that provides the submit button when the email option is taken. It appears automatically at the top of the first page of the exam, and appears only if nosolutions has been taken, and solutionsafter has not been taken.
922 \let\priorSubmitJS\@gobble
923 \let\postSubmitJS\@empty
924 \def\SubmitButton
925 {%
926   \ifx\use@email\eqe@YES\ifeq@nosolutions\ifeq@solutionsafter\else
927     \makebox[Opt][1]{\pushButton
928       [\CA\@SubmitButtonLabel]\Af\JS{%
929         var _eqEok2Submit = true;\r
930         var aSubmitFields = new Array("eqexam", "IdInfo");\r
931         \priorSubmitJS\r
932         if(_eqEok2Submit) this.submitForm("\EqExam@SubmitURL",
933           true, false, aSubmitFields);\r
934         \postSubmitJS
935       }]{Submit}{1.5in}{16bp}}%
936     \makebox[Opt][1]{\textField[\F\FFHidden\DV{\@EmailInstr}
937       \V{\@EmailInstr}]{IdInfo.mailTo}{11bp}{11bp}}%
938     \makebox[Opt][1]{\textField[\F\FFHidden\DV{\@EmailCourseName}
939       \V{\@EmailCourseName}]{IdInfo.courseName}{11bp}{11bp}}%

```

```

940     \makebox[Opt][l]{\textField[\F\FFHidden\DV{@EmailExamName}]
941         \V{@EmailExamName}{IdInfo.examName}{11bp}{11bp}}%
942     \makebox[Opt][l]{\textField[\F\FFHidden\DV{@EmailSubject}]
943         \V{@EmailSubject}{IdInfo.subject}{11bp}{11bp}}%
944     \makebox[Opt][l]{\textField[\F\FFHidden\DV{@ServerRetnMsg}]
945         \V{@ServerRetnMsg}{IdInfo.retnmsg}{11bp}{11bp}}%
946     \fi\fi\fi
947 }
948 \def\thequizno{\if\probstar*\Alph{quizno}\else\alph{quizno}\fi}
949 \def\linkContentFormat{%
950     \if\probstar*\Alph{quizno}\else\alph{quizno}\fi
951 \def\linkContentWrapper{(\hfil\linkContentFormat\hfil)}%
952 \def\Ans@r@l@Defaults
953 {%
954     \BC{}{S{S}}{W{1}}{Ff}{FfNoToggleToOff}
955     \textSize{12}\textColor{0 g}
956 }
(2014/03/12) Added \eq@hspanner\ignorespaces, in the next two commands.
Fixes problems with spacing following the choice box.
957 \newcommand{\optsRadioBtnd}{[1]{\def\eqe@optsRadiof{#1}}
958 \newcommand{\optsRadioBtndl}{[1]{\def\eqe@optsRadiol{#1}}
959 \let\eqe@optsRadiof\empty\let\eqe@optsRadiol\empty
960 \def\eqExam@Ans@s@l{\leavevmode
961     \if\eqe@listType1\stepcounter{quizno}\else\ifwithinoldoc
962         \stepcounter{quizno}\else\refstepcounter{quizno}\fi\fi
963         \PBS\raggedright\settowidth{\eq@tmpdima}{\eq@lw@l}%
964         \sbox{\eq@tmpbox}{\eq@l@l}\eq@tmpdima=\wd\eq@tmpbox
965         \def\link@@Content{\linkContentWrapper}%
966         \hangindent=\eq@tmpdima\hangafter=1\relax
967         \edef\fieldName{%
968             \if\probstar*\eqexam.\curr@quiz.\theequationno.part\thepartno%
969             \else
970                 \eqexam.\curr@quiz.\theequationno%
971             \fi
972         }%
973         \if\eq@online\eqe@YES\relax
974             \makebox[Opt][l]{%
975                 \radio@@Button{\presets{\eqe@optsRadiol}}{\fieldName}%
976                 {\eq@tmpdima}{\RadioFieldSize}{\Ans@choice\alph{quizno}}%
977                 {\eq@protect\A}{\eq@addWidgetProps\eq@l@check@driver}%
978                 {\Ans@r@l@Defaults\every@RadioButton\every@qRadioButton}}%
979             \else
980                 \edef\@linkcolor{\@nolinkcolor}%
981             \fi
982             \ifeq@nosolutions\edef\@linkcolor{\@nolinkcolor}\fi
983             \textcolor{@linkcolor}{\makebox[\eq@tmpdima]{\link@@Content}}%
984             \Ans@proofing{\eq@tmpdima}%
985             \eq@hspanner\ignorespaces
986 }

```

(2019/10/28) Legacy assignment, in case eqexam.def/exerquiz are still using \eq@RadioCheck@driver.

```

987 \@ifundefined{eq@RadioCheck@driver}{}%
988   {\let\eq@Radio@driver\eq@RadioCheck@driver}%
989 \def\eqExam@Ans@sq@f{\if\eq@listType1\stepcounter{quizno}\else
990   \ifwithinoldoc\stepcounter{quizno}\else
991     \refstepcounter{quizno}\fi\fi
992   \PBS\raggedright\settowidth{\eq@tmplength}{\eq@lw@f}%
993   \eq@tmpdima=\wd\eq@tmpbox%
994   \hangindent=\eq@tmplength\hangafter=1\relax
995   \if\eq@online\eqe@N0\previewtrue
996     \insertGrayLetters
997     \Ans@sq@f@driver
998   \else
999     \ifanswerkey\previewtrue
1000       \Ans@sq@f@driver
1001   \else
1002     \edef\fieldName{%
1003       \if\probstar*eqexam.\curr@quiz.\theeqquestionnoi.%%
1004         part\thepartno%
1005       \else
1006         eqexam.\curr@quiz.\theeqquestionnoi%
1007       \fi
1008     }\insertGrayLetters
1009     \radio@Button{\presets{\eqe@optsRadiof}}%
1010     {\fieldName}{\RadioFieldSize}%
1011     {\RadioFieldSize}{\Ans@choice\alph{quizno}}{\eq@protect\A}%
1012     {\eq@setWidgetProps\eq@Radio@driver}%
1013     {\@Ans@sq@f@Defaults\Ans@sq@f@Actions\every@RadioButton
1014       \every@sqRadioButton\insert@circlesymbol}%
1015     \fi
1016   \fi
1017   \Ans@proofing{\RadioFieldSize}%
1018   \eq@hspanner\ignorespaces
1019 }
1020 \newcommand{\optsCkBxf}[1]{\def\eqe@optscbf{#1}}
1021 \newcommand{\optsCkBx1}[1]{\def\eqe@optscbl{#1}}
1022 \let\eqe@optscbl\empty\let\eqe@optscbf\empty
1023 \def\eqExam@Ans@ck@sq@l{\leavevmode
1024   \if\eq@listType1\stepcounter{quizno}\else
1025   \ifwithinoldoc\stepcounter{quizno}\else
1026     \refstepcounter{quizno}\fi\fi
1027   \PBS\raggedright\settowidth{\eq@tmplength}{\eq@lw@l}%
1028   \sbox{\eq@tmpbox}{\eq@l@l}\eq@tmpdima=\wd\eq@tmpbox
1029   \def\link@@Content{\linkContentWrapper}%
1030   \hangindent=\eq@tmplength\hangafter=1\relax
1031   \edef\fieldName{%
1032     \if\probstar*eqexam.\curr@quiz.\theeqquestionnoi.%%
1033       part\thepartno.\alph{quizno}%

```

```

1034     \else
1035         eqexam.\curr@quiz.\theeqquestionnoi.\alph{quizno}%
1036     \fi
1037 }%
1038 \if\eq@online\eqe@YES\relax
1039 \makebox[0pt][1]{\check@@Box{\presets{\eqe@optsc1}}{\fieldName}%
1040     {\eq@tmpdima}{\RadioFieldSize}{\Ans@choice\alph{quizno}}%
1041     {\eq@protect\A}{\eq@setWidgetProps\eq@l@check@driver}%
1042     {\Ans@r@l@Defaults\every@RadioButton\every@qRadioButton}}%
1043 \else
1044     \edef\@linkcolor{\@nolinkcolor}%
1045 \fi
1046 \ifeq@nosolutions\def\@linkcolor{\@nolinkcolor}\fi
1047 \textcolor{\@linkcolor}{\makebox[\eq@tmpdima]{\link@@Content}}%
1048 \Ans@proofing{\eq@tmpdima}%
1049 \eq@hspanner\ignorespaces
1050 }
1051 \def\eqExam@Ans@ck@sq@f{\if\eq@listType1\stepcounter{quizno}\else
1052     \ifwithinoldoc\stepcounter{quizno}\else
1053         \refstepcounter{quizno}\fi\fi
1054     \PBS\raggedright\settowidth{\eq@tmplength}{\eq@lw@f}%
1055     \eq@tmpdima=\wd\eq@tmpbox%
1056     \hangindent=\eq@tmplength\hangafter=1\relax
1057     \if\eq@online\eqe@NO\previewtrue
1058         \insertGrayLetters
1059         \Ans@sq@f@driver
1060     \else
1061         \ifanswerkey\previewtrue
1062             \Ans@sq@f@driver
1063         \else
1064             \edef\fieldName{%
1065                 \if\probstar*eqexam.\curr@quiz.\theeqquestionnoi.%
1066                     part\thepartno.\alph{quizno}}%
1067                 \else
1068                     eqexam.\curr@quiz.\theeqquestionnoi.\alph{quizno}%
1069                 \fi
1070             }\insertGrayLetters
1071             \mbox{\check@@Box{\presets{\eqe@optscbf}}{\fieldName}%
1072                 {\RadioFieldSize}{\RadioFieldSize}%
1073                 {\Ans@choice\alph{quizno}}{\eq@protect\A}%
1074                 {\eq@setWidgetProps\eq@Radio@driver}%
1075                 {\Ans@sq@f@Defaults\Ans@sq@f@Actions\every@RadioButton
1076                     \every@sqRadioButton}}%
1077             \fi
1078         \fi
1079         \Ans@proofing{\RadioFieldSize}%
1080         \eq@hspanner\ignorespaces
1081 }

```

\optsMlTextField is used to pass options to the multi-line text field.

```

1082 \def\optsM1TextField#1{\def\eqe@optsmltf{#1}}
1083 \let\eqe@optsmltf\empty
1084 \def\eqExamPriorVspace#1{%
1085   \edef\fieldName{%
1086     \if\probstar*eqexam.\curr@quiz.%
1087       \theeqquestionno.part\thepartno.solution%
1088     \else
1089       eqexam.\curr@quiz.\theeqquestionno.solution%
1090     \fi
1091   }%
1092   \nobreak\noindent\textField[\BC{}]\presets{\eqe@optsmltf}%
1093   \FfMultiline[\fieldName]{\linewidth}{#1}\gobble
1094 }

```

Test to see if `exerquiz` is loaded. If not, we input the ‘stand alone’, `eqalone.def`, followed by `eqexam.def`. The latter definition file is maintained in `exerquiz.dtx` under the `eqexam` option.

```

1095 \@ifpackageloaded{exerquiz}{%
1096   \let\Ans@sq@l\eqExam@Ans@sq@l
1097   \let\Ans@sq@f\eqExam@Ans@sq@f
1098   \let\Ans@ck@sq@l\eqExam@Ans@ck@sq@l
1099   \let\Ans@ck@sq@f\eqExam@Ans@ck@sq@f
1100   \def\eqexheader@wrapper{\makebox[0pt][r]{%
1101     \hypertarget{qex.\the@exno}{\eqexheader}}}%
1102   \if\eq@online\eqe@YES\relax
1103     \newcounter{@cntfillin}%
1104     \let\eqPriorVspace\eqExamPriorVspace
1105   \fi
1106 }%
1107 {%
1108   \input{eqalone.def}
1109   \input{eqexam.def}

1110   \@ifl@ter{def}{eqexam}{\eqexamdefReq}{%
1111     {\PackageWarningNoLine{eqexam}%
1112      {This version of eqexam requires eqexam.def\MessageBreak
1113       dated \eqexamdefReq\space or later}}%
1114     \def\eqexheader@wrapper{\makebox[0pt][r]{\eqexheader}}%
1115   }

```

We wrote `\begin{eqquestions}` to the top of the solutions file (`\jobname.sol`).  
1116 %\writeBeginEqQuestions

If the `vspacewithsolns` is in effect, we write solutions to the end of the document.

```

1117 \AtBeginDocument{%
1118   \ifvspacewithsolns\writeAllAnsAtEnd\else
1119   \ifeqfortextbook\writeAllAnsAtEnd\else
1120   \writeWithSolDocTrue\fi\fi
1121 }

```

We execute `\vspacewithkeyOff`, which sets `\ifkeepdeclaredvspacing` to false, the default behavior of `eqexam` before the new feature.

```
1122 \vspacewithkeyOff
1123 </package>
```

## 11 Stand alone Code

```
1124 <*standalone>
```

Now we begin the listing of the stand alone code. This code is necessary if `exerquiz` has not been loaded, which is the case if there is no PDF options or if the `pdf` option is taken.

Many of the following definitions are given in `eforms`, which was recently separated from `exerquiz` and is now maintained as a separate package.

```
1125 \ProvidesFile{eqalone.def}
1126 [2012/25/01 v3.0t Minimal code used by eqexam (dps)]
1127 \CIfundefined{eq@tmpbox}{\newsavebox{\eq@tmpbox}{}% defined in eforms
1128 \CIfundefined{eq@tmpdima}{\newdimen\eq@tmpdima}{} % defined in eforms
1129 \def\RadioFieldSize{11bp}
1130 \newdimen\eqcenterWidget
```

This macro is used to vertically center the response box on the line. Seems to work well.

```
1131 \def\centerWidget
1132 #1{%
1133     \eqcenterWidget=#1
1134     \eqcenterWidget=.5\eqcenterWidget
1135     \advance\eqcenterWidget by-4bp
1136 }
```

`\eqe@Bbox` When the `preview` option has been used, draw a frame box around the bounding rectangle.

```
1137 \def\eqe@BboxRect#1#2{\hbox{\ckbox@Color\vbox{\hrule width #1
1138   \hbox to#1{\vrule height#2\hfill\vrule height#2}\vfill\hrule}}}
1139 \def\useRectForMC{\let\Bbox\eqe@BboxRect}
1140 \def\selectedMC{\useRectForMC}
```

`\Rect` is used internally to color a link.

```
1141 \def\Rect#1{\textcolor{\@linkcolor}{#1}}
```

`\ReturnTo` The auxiliary file `eqexam.def`, created by `exerquiz`, writes `\ReturnTo` to the `SOL` file in the form `\ReturnTo{page.1}{\mbox{}}`. We want to remove the `\mbox` because it causes, at times, more vertical space that is wanted in an exam document.

```
1142 \def\eqe@striphbox{\mbox#1{#1}}
1143 \newcommand{\ReturnTo}[2]{\eq@fititin{\eqe@striphbox#2}}
```

## 12 Switching proofing symbols

`\proofingsymbol` The definition of the proofing symbol, this symbol marks the correct answer of a

multiple choice question when the `proofing` option is used.

```
1144 \newcommand{\proofingsymbol}[1]{%
1145     \def\@proofingsymbol{\textcolor{\@proofingsymbolColor}{#1}}}
```

This is the answers macro for the link-style and is called from the `eqexam.def` file.

```
1146 </standalone>
1147 <*package>
```

In response to the `allowcircmc`, we load `lcircle10` and use the ‘h’ and ‘x’ glyph.

```
1148 \def\selectedMC{\useRectForMC}
1149 \ifallowcircmc
1150     \font\eqe@lcir=lcircle10 at 12pt
1151     \bgroup
```

Get the width of the ‘h’, the circle has zero height and depth. Set the diameter and radius of the circle.

```
1152     \setbox0=\hbox{\eqe@lcir h}
1153     \xdef\eqe@cirDiam{\the\wd0}
1154     \tempdima=.5\wd0
1155     \xdef\eqe@cirRadius{\the\tempdima}
1156 \egroup
```

A command to use the circle (h) and the filled circle (x).

```
1157 \def\circ@Glyph#1#2{\hbox{\smash{\raisebox{\eqe@cirRadius}{%
1158     {\makebox[\eqe@cirDiam]{\llap{\ckcir@Color
1159         \rlap{\eqe@lcir#1}\hskip#2\relax}}}}}}}}
```

Added preview color to the circle version of the bounding box. The color accessed through `\previewColor`, its default is `black`.

```
1160 \def\eqe@BboxCirc#1#2{\hbox{\ckcir@Color\circ@Glyph{h}{0pt}}}}
```

For proofing purposes, prepare the filled circle in the form of the command `\circProofingForCirc`.

```
1161 \def\circProofingForCirc{\centerWidget\RadioFieldSize
1162     \lower\eqcenterWidget\circ@Glyph{x}{1.4pt}}
1163 \if\eq@online\eq@YES
```

If online (`online` or `email` option), we cancel these commands.

```
1164 \def\useCircForMC{\let\Bbox\eqe@BboxCirc\useMCCircles}
1165 \def\selectedMC{\useCircForMC}
1166 \ifundefined{\eqe@BboxRect}
1167     {\def\useRectForMC{\let\Bbox\ef@Bbox\useMCRects}}
1168     {\def\useRectForMC{\let\Bbox\eqe@BboxRect\useMCRects}}
1169 %
1170 \else % if not online
1171     \ifundefined{\eqe@BboxRect}
1172         {\def\useRectForMC{\let\Bbox\ef@Bbox}}
1173         {\def\useRectForMC{\let\Bbox\eqe@BboxRect}}
1174 \def\useCircForMC{\let\Bbox\eqe@BboxCirc}
1175 \def\selectedMC{\useCircForMC}
1176 \fi
```

```

1177      \def\useCircForProof{\symbolchoice{circle}%
1178          \proofingsymbol{\circProofingForCirc}}
1179 \else
    If allowcircmc is not taken
1180     \if\eq@online\eqe@YES
1181         \def\useCircForMC{\let\Bbox\eqe@BboxCirc\useMCCircles}
1182         \@ifundefined{\eqe@BboxRect}
1183             {\def\useRectForMC{\let\Bbox\ef@Bbox\useMRects}}
1184             {\def\useRectForMC{\let\Bbox\eqe@BboxRect\useMRects}}
1185     \else
1186         \@ifundefined{\eqe@BboxRect}
1187             {\def\useRectForMC{\let\Bbox\ef@Bbox}}
1188             {\def\useRectForMC{\let\Bbox\eqe@BboxRect}}
1189         \def\useCircForMC{\useRectForMC}
1190         \def\selectedMC{\useRectForMC}
1191     \fi
1192     \let\useCircForProof\relax
1193 \fi
\useRectForMS  \useRectForMS When declared, rectangles are used for multiple selection, simi-
\useCircForMS  larly, \useCircForMS uses circles if allowcirc4mc is in effect.
1194 \newif\ifuserectforms
1195 \def\useRectForMS{\userectformstrue}
1196 \def\useCircForMS{\userectformsfalse}

1197 \newcommand{\useCheckForProof}{\symbolchoice{check}%
1198     \proofingsymbol{\ding{52}}}
1199 \useCheckForProof

Similarly, for a cross, we get a nice ‘handwritten’ cross \ding{56}, !when we latex
the document; for the online or email option, we get a simple cross in the active
radio button field.
1200 \newcommand{\useCrossForProof}{\symbolchoice{cross}%
1201     \proofingsymbol{\raisebox{-1pt}{\rlap{\kern-1pt\Large\ding{56}}}}}

```

## 13 The Main Code

We now continue with the main package. Mostly, we define macros specific to the `eqexam` package: define the `problem` and `problem*` environments, macros for calculating totals per page, etc.

```

1202 \def\MCcolor{black}
1203 \def\Ans@sq@l@driver{\edef\@linkcolor{\MCcolor}%
1204     \Rect{\makebox[\eq@tmpdima]{\linkContentWrapper}}%
1205     \Ans@proofing{\eq@tmpdima}%
1206 }

```

This is the answers macro for the form-style and is called from the `eqexam.def` file.

```

1207 \def\Ans@sq@f@driver{%
1208     \centerWidget\RadioFieldSize
1209     \leavevmode\lower\eqcenterWidget\Bbox \% \eqe@Bbox
1210     {\RadioFieldSize}{\RadioFieldSize}%
1211     \Ans@proofing{\RadioFieldSize}%
1212 }

    Write quiz solutions to the exercise solutions file

1213 \def\eq@sqsllabel{\string\textbf{Solution to Quiz:}}
1214 \def\sqsllabel{\eq@sqsllabel}

\writeToSolnFile General purpose command for writing to the solution file.

\preExamSolnHead Executed just before a user friendly name

\examSolnHeadFmt Format for the user friendly name

\postExamSolnHead Executed just after a user friendly name

1215 \let\quiz@solns\ex@solns
1216 \newcommand{\preExamSolnHead}{\goodbreak\noindent}
1217 \newcommand{\examSolnHeadFmt}[1]{\textbf{#1}}
1218 \newcommand{\postExamSolnHead}{\par\medskip}

    Write to solution file if not solutions-only

1219 \@ifundefined{ifOKToWriteExamData}{\newif\ifOKToWriteExamData
1220   \OKToWriteExamDatatrue}{}
1221 \newcommand{\writeToSolnFile}[1]{%
1222   \ifsolutionsonly\else\ifOKToWriteExamData
1223     \let\quiz@solns\ex@solns
1224     \set@display@protect
1225     \eqe@IWO\quiz@solns{#1}%
1226     \set@typeset@protect
1227   \fi\fi}
1228 \let\writeT@SolnFile\writeToSolnFile

    We will write all solutions to the .sol auxiliary file.

1229 \def\eqe@writetoSolns#1{%
1230   \ifsolutionsonly\else
1231   \ifOKToWriteExamData
1232   \set@display@protect
1233   \eqe@IWO\quiz@solns{\string\preExamSolnHead
1234   \string\examSolnHeadFmt{#1}\string\postExamSolnHead}%
1235   \set@typeset@protect\fi\fi}
1236 \def\eqe@writetoAux#1{%
1237   \set@display@protect
1238   \eqe@IWO\@auxout{#1}%
1239   \set@typeset@protect}

```

Turn off interactivity of short quiz.

This macro is defined in `exerquiz`, but has a little different definition for `eqexam`.

```
1240 \def\Ans@proofing
1241 #1{%
1242     \ifeq@proofing\if\Ans@choice1\relax
1243         \llap{\rlap{\,\,}\@proofingsymbol}\hskip#1\relax}%
1244     \fi\fi
1245 }
```

`\eq@ExamLastPage` This macro gets the page number of the last page of the exam. It is read in through a macro definition made and written to the `.aux` file.

```
1246 \def\eq@ExamLastPage{\csname eqExamLastPage\endcsname}
```

`\nPagesOnExam` is the number of pages in the exam.

```
1247 \newcommand{\nPagesOnExam}{\csname eqExamLastPage\endcsname}
```

`\nPagesOnQues` is the number of pages in the questions.

```
1248 \newcommand{\nPagesOfQues}{\ifvspacewithsolns
1249     \csname eqExamQuesLastPage\endcsname\else
1250     \csname eqExamLastPage\endcsname\fi}
```

`\nPagesOnSols` is the number of pages of solutions.

```
1251 \newcommand{\nPagesOfSols}{\def\eqExamNumPagesSolns{0}%
1252     \csarg\ifx{\eqExamLastPage}\relax\else
1253     \csarg\ifx{\eqExamLastPage}\relax\else
1254     {\count\z@=\nPagesOnExam\relax\advance
1255     \count\z@\nPagesOfQues\relax
1256     \xdef\eqExamNumPagesSolns{\the\count\z@}}\fi\fi
1257     \eqExamNumPagesSolns}
```

`\lastPageOfExam` Returns the page number of the end of the exam with a name of #1.

`\firstPageOfExam` Returns the page number of the beginning of the exam with a name of #1.

```
1258 \newcommand{\lastPageOfExam}[1]{\pageref{#1PageEnd}}
1259 \newcommand{\firstPageOfExam}[1]{\pageref{#1PageBegin}}
```

The last two commands are meant to produce typeset numbers; however, there is a need to convert these to numbers that `tex`'s registers can manipulate. Here goes. `\eqe@defNumRefii` takes its argument and strips away the other arguments of `\pageref`; it picks off the second of two or five, depending if `hyperref` is loaded. It defines a macro `\csname nRefii@#1\endcsname` whose value is a page number of the referenced object.

```
1260 \newcommand{\eqe@defNumRefii}[1]{%
1261     \@ifundefined{hyperref}{\let\@getsecondof\@secondoftwo}{%
1262     {\let\@getsecondof\@secondoffive}%
1263     \ifundefined{r@#1}{%
```

If the reference `r@#1` is undefined, define the value to be 0

```
1264     \csarg\gdef{nRefii@#1}{0}}{%
```

If the reference `\r@#1` is defined, define the value to be the second argument of `\r@#1` expanded

```

1265   \expandafter\xdef\csname nRefii@#1\endcsname
1266     {\expandafter\expandafter\expandafter
1267       \c@getsecondof\csname r@#1\endcsname}%
1268     }%
1269 }
```

`\eqe@numRefii` takes one argument, the control name. Its value is zero or `\nRefii@#1`. This expands to a number in all cases. It can be used in tex comparisons.

```

1270 \def\eqe@numRefii#1{%
1271   \csarg\ifx{nRefii@#1}\relax 0\else
1272   \c@nameuse{nRefii@#1}\fi}
```

`\numLastPageOfExam` This is the user-interface to acquiring the first and last page numbers of the exam  
`\numFirstPageOfExam` with name #1. These can be used in comparisons, e.g.

```

\rfooteqe{\ifnum\value{page}<\numLastPageOfExam{<myTest>}%
           \textbf{Test Continues}\fi}

1273 \newcommand{\numLastPageOfExam}[1]{\eqe@numRefii{#1PageEnd}}
1274 \newcommand{\numFirstPageOfExam}[1]{\eqe@numRefii{#1PageBegin}}

1275 \newcommand{\makeRefsNums}{%
1276   \@ifundefined{thePartNames}{}{\begingroup
1277     \def\##1{\PackageInfo{eqexam}{processing exam: ##1}%
1278       \eqe@defNumRefii
1279       {##1PageEnd}\eqe@defNumRefii{##1PageBegin}}%
1280     \thePartNames
1281   \endgroup}%
1282 }
1283 \AtBeginDocument{\makeRefsNums}
```

### 13.1 Running Heads and Feet

We develop a series of macros for creating running headers and footers for the exam.

`\lheadeqe` Set the left, center, and right running headers.

```

\cheadeqe 1284 \newcommand{\lheadeqe}[1]{\def\eq@lhead{#1}}
\rheadeqe 1285 \lheadeqe{\shortwebsubject/\shortwebtitle}
1286 \newcommand{\cheadeqe}[1]{\def\eq@chead{#1}}
1287 \cheadeqe{-- Page \arabic{page} of \nPagesOnExam --}
1288 \newcommand{\rheadeqe}[1]{\def\eq@rhead{#1}}
```

The default is `\eq@ExamName`, which is defined by `\eqExamName`, the default displays the word "Name" and an underlined horizontal space for the student to enter his/her name.

```
1289 \rheadeqe{\eq@ExamName}
```

\lhead These are the original names for the headers, we'll keep them if `fancyhdr` is not already loaded to maintain compatibility with previous versions of `eqexam`. The use of these commands is *discouraged*.

```
1290 \@ifpackageloaded{fancyhdr}{}{%
1291     \let\lhead\lheadeqe
1292     \let\chead\cheadeqe
1293     \let\rhead\rheadeqe
1294 }
```

`\runExamHeader` The running header of the exam, may be redefined.

```
1295 \newcommand{\runExamHeader}{\eq@lhead\hfill\eq@chead\hfill\eq@rhead}
1296 \newcommand\eqExamRunHead{%
1297     \addtolength\textwidth{\oddsidemargin}%
1298     \noindent\hspace*{-\oddsidemargin}\makebox[\textwidth]{%
1299     {\runExamHeader}}%
1300 }
```

**Running footers.** One or two users wanted to use running footers, so here they are.

\lfooteqe There has been some demand for running footers. You have to be a little careful, \cfooteqe `eqexam` uses the footer for the command `\settotsbox`, which puts in the totals \rfooteqe for the pages either on the left (`totalsonleft`) or right (`totalsonright`) side, depending on the option.

```
1301 \newcommand{\lfooteqe}[1]{\def\eq@lfoot{\#1}}
1302 \lfooteqe{}
1303 \newcommand{\cfooteqe}[1]{\def\eq@cfoot{\#1}}
1304 \cfooteqe{}
1305 \newcommand{\rfooteqe}[1]{\def\eq@rfoot{\#1}}
1306 \rfooteqe{}
```

`\runExamFooter` Considering the defaults for the left, center, and right footer elements, the default footer contributes nothing, except inserting `\settotsbox` (see the definition of `\@oddfoot`)

```
1307 \newcommand{\runExamFooter}{\eq@lfoot\hfill\eq@cfoot\hfill\eq@rfoot}
```

**Running headers for solutions.** We provide a special set of headers for the solution pages. The document author needs to manage running footers for the solution pages.

\lheadSol The running header of the exam, when solutions are included at the end of the document, perhaps for posting the solutions to the exam, or publication of a “pretest”. \rheadSol Note that `\eqsolutionshook` is defined in `exerquiz/eqexam.def`. May be redefined.

```
\runExamHeaderSol
1308 \newcommand{\lheadSol}[1]{\def\eq@lheadSol{\#1}}
1309 \lheadSol{\shortwebsubject/\shortwebtitle}
1310 \newcommand{\cheadSol}[1]{\def\eq@cheadSol{\#1}}
1311 \cheadSol{-- Page \arabic{page} of \eq@ExamLastPage} --}
```

```

1312 \newcommand{\rheadSol}[1]{\def\eq@rheadSol{#1}}
1313 \rheadSol{SOLUTIONS}

The \runExamHeaderSol distributes the three solution headers across the page.

1314 \newcommand{\runExamHeaderSol}{%
1315     {\eq@lheadSol\hfill\eq@cheadSol\hfill\eq@rheadSol}

The solutions headers are inserted using the \eq@solutionshook, see the definition of \exerSolnInput.

1316 \def\eq@solutionshook
1317 {%
1318     \gdef\eqExamRunHead{\addtolength{\textwidth}{\oddsidemargin}%
1319     \noindent\hspace*{-\oddsidemargin}\makebox[\textwidth]{%
1320     {\runExamHeaderSol}}%
1321 }

```

### 13.2 \maketitle definitions

**\maketitle** Standard L<sup>A</sup>T<sub>E</sub>X macro, but this time it is used to create the header at the top of the first page of the exam. Typically, consisting of two rows of info. (1) first row has course name, exam name, and a place for the student to put his/her name. (2) second row has date and instructor. May be redefined.

Modify the title by redefining \maketitledesign, the \maketitle command itself has L<sup>A</sup>T<sub>E</sub>X commands in it that should not be changed.

```

1322 \newcommand\maketitledesign
1323 {%
1324     \makebox[\textwidth]{\normalsize
1325         \shortstack[l]{\strut\websubject\\@\date}\hfill
1326         \shortstack[c]{\webtitle\\\strut@\altTitle}\hfill
1327         \shortstack[l]{\strut\eq@ExamName\\@\webauthor}}%
1328 }
1329 \def\altTitle#1{\def\@altTitle{#1}}
1330 \let\@altTitle\empty
1331 \def\eqemaketitle
1332 {%

```

**\EQEcalculateAllTotals:** We don't actually calculate all totals, just some of them. We do calculate the grade total of all the **exam** environments in the document, we also calculate the percentage that each exam contributes to the total. If \maketitle is not used, for whatever reason, this command should be calculated explicitly just after \begin{document}.

```

1333     \EQEcalculateAllTotals
1334     \begingroup
1335     \addtolength{\textwidth}{\oddsidemargin}%
1336     \noindent%\hspace*{-\oddsidemargin}%
1337     \raisebox{.7in}[0pt][0pt]{\SubmitButton}%
1338     \maketitledesign
1339     \endgroup
1340 }

```

If the `fortextbook` option is not taken, we set up the usual `\maketitle` definition.  
If the `useclassmaketitle` option is taken, we don't redefine either.

```

1341 \ifeq{fortextbook}
1342     \@ifpackageloaded{web}{\let\maketitle\@makeatother\@nameuse{maketitle}{}}
1343 \else
1344     \if@equseclassmaketitle
1345         \@ifpackageloaded{web}{\let\maketitle\@makeatother\@nameuse{maketitle}{}}
1346     \else
1347         \let\maketitle\@nameuse{maketitle}
1348     \fi
1349 \fi

```

### 13.3 The cover page definitions

- `\eqexcoverpage` The `eqexam` package allows for the possibility of a cover page, if the `coverpage` option is taken.
- `\placeCoverPageLogo` A simple command to insert a logo on the cover page. The logo can be used to cover the score in the next page, if the instructor places the score under the logo.  
Example of usage

```
\placeCoverPageLogo{5in}{-1.5in}{\includegraphics{nwfsc_logo}}
```

Working from the upper left corner, the first parameter is the amount to move to logo to the right, the second parameter is the amount to move the logo vertically. The Third parameter is the content; perhaps an `\includegraphics` command.

```

1350 \newcommand{\placeCoverPageLogo}[3]{%
1351     \def\eqe@insertLogo{\hbox{to0pt{%
1352         \hspace*{\#1}\smash{\raisebox{\#2}{\#3}}}\hss}}
1353 \let\eqe@insertLogo\relax

```

Define `\eqexcoverpage`, this command places `\eqe@insertLogo` and `\eqexcoverpagedesign` in a group. It is this command that gets executed when the user calls for the `coverpage` option.

```

1354 \def\eqexcoverpage{%
1355     \begingroup
1356     \pagenumbering{roman}
1357     \eqe@insertLogo
1358     \eqexcoverpagedesign
1359     \endgroup\newpage
1360     \pagenumbering{arabic}
1361 }

```

- `\eqexcoverpagedesign` The `eqexam` package allows for the possibility of a cover page, if the `coverpage` option is taken. This macro can and should be redefined to fit your needs. The definition below is just a representative example.

`\coverpagesubject` The following four commands are used with the cover page. The `\coverpage-`  
`\coverpageUniversityFmt` subject is used to provide a special subject for the cover page, different from  
`\coverpageSubjectFmt`. The others are used for formatting.  
`\coverpageTitleFmt`

```

1362 \newcommand{\coverpagesubject}[1]{\def\coverpage@subject{#1}}
1363 \let\coverpage@subject@\empty
1364 \def\eqexamssubject{\ifx\coverpage@subject\empty\websubject
1365     \else\coverpage@subject\fi}
1366 \newcommand{\coverpageUniversityFmt}[1]{%
1367     \def\eqex@coverpageUniversityFmt{#1}}
1368 \coverpageUniversityFmt{\bfseries\large}
1369 \newcommand{\coverpageSubjectFmt}[1]{%
1370     \def\eqex@coverpageSubjectFmt{#1}}
1371 \coverpageSubjectFmt{\bfseries\large}
1372 \newcommand{\coverpageTitleFmt}[1]{%
1373     \def\eqex@coverpageTitleFmt{#1}}
1374 \coverpageTitleFmt{\bfseries\large}
1375 \newcommand\cpCID[1]{\def\cp@@CID{#1}}
1376 \let\cp@@CID@\empty
1377 %\newcommand\coverpageCID[1]{\def\cpCID@argi{#1}}
1378 \newcommand{\cpSetCIDWidth}[1]{\bgroup\setlength{\tempdima}{#1}
1379     \xdef\cpCID@argi{\the\tempdima}\egroup}
1380 \def\cp@CID{\bgroup\settowidth\eq@tmpwidthA{\cp@@CID}%
1381     \tempdima=\cpCID@argi\relax
1382     \advance\tempdima-\eq@tmpwidthA
1383     \eqe@idinfohl{\makebox[\cpCID@argi][l]{\cp@@CID}}\egroup}
1384 \cpSetCIDWidth{2.25in}
1385 %\coverpageCID{2.25in}

```

When `coverpage` and `coverpagesumry` are used, an **Exam Record** is generated, just a summary may appear beneath the name and ID section of the cover page

`\qeSumryVert` (`\qeSumryVert`) or to the right (`\qeSumryHoriz`).

```

\qeSumryHoriz 1386 \def\qeSumryVert{\def\qe@SumryVert{\par\vfill}%
1387     \let\qe@SumryHoriz\relax
1388     \def\qe@SumryVert{\vspace{\stretch{-1}}\bigskip}
1389 \def\qeSumryHoriz{\def\qe@SumryHoriz{\hfill}\let\qe@SumryVert\relax
1390     \let\qe@SumryVert\relax}

```

The default is a horizontal orientation.

`1391 \qeSumryHoriz`

We can name the components of the **Exam Record** by page or by parts. For the case they are named by parts, there are three options: You can use the exam name (the default); you can use the friendly name of the exam (the optional argument), executing `\useUIPartNames` invokes this option; you can use custom names (useful if the friendly names are too long), execute the command `\useCustomPartNames` for this option.

```

1392 \def\qe@coverPageNaming{0}
1393 \newcommand{\useUIPartNames}{\def\qe@coverPageNaming{1}}
1394 \newcommand{\useCustomPartNames}{\def\qe@coverPageNaming{2}}

```

`\customNaming` When there is custom naming (`\customNaming`), we need to provide the user with a way of defining these custom names. `\customNaming` provides that mechanism. The command takes two arguments, the first is `name`, the second

is the associated `text` the text that is to appear in the **Exam Record**

```
1395 \newcommand{\customNaming}[2]{\@namedef{userCustom#1}{#2}}
1396 \newcommand{\cpSetNameAndIDWidth}[1]{\bgroup
1397     \setlength{\@tempdima}{#1}%
1398     \xdef\cp@SetNameAndIDWidth{\the\@tempdima}\egroup}
1399 \cpSetNameAndIDWidth{.45\textwidth}
1400 \newcommand{\cpEnclNameAndID}[1]{\def\cp@EnclNameAndID{#1}}
1401 \let\cp@EnclNameAndID@\empty
1402 \newcommand{\cpSetHghtFrstLn}[1]{\def\cp@HghtFrstLn{#1}}
1403 \def\cp@HghtFrstLn{Opt}
1404 \def\cp@setHghtFrstLn{\rule[\cp@HghtFrstLn]{Opt}{Opt}}
1405 \newcommand\cpNameAndID{\noindent
1406     \edef\eqExamName@argii{\cp@SetNameAndIDWidth}%
1407     \edef\eqSID@argii{\cp@SetNameAndIDWidth}%
1408     \edef\cpCID@argii{\cp@SetNameAndIDWidth}%
1409     \cp@EnclNameAndID{\parbox[b]{\cp@SetNameAndIDWidth}{\parindent0pt
1410         \cp@setHghtFrstLn\eq@ExamName\\[2ex]
1411         \ifx\cp@@CID\empty\eq@SID\else\cp@CID\fi\\[2ex]
1412         \ifx\use@email\eqe@YES\eq@Email\\[2ex]\fi
1413         \textcolor{\webauthor@color}{\webauthor}, \date\vskip0pt}}}
```

Now we present the definition of `\eqexcoverpagedesign`.

```
1414 \newcommand{\eqexcoverpagedesign}
1415 {%
1416     \begingroup
1417     \parindent0pt
1418     \thispagestyle{empty}
1419     \addtolength{\textwidth}{\oddsidemargin}
1420     \vspace*{.1\textheight}
1421     \noindent\hspace*{-\oddsidemargin}%
1422     \makebox[\ linewidth]{\parbox{\ linewidth}%
1423         {\eqex@coverpageUniversityFmt
1424             \color{\webuniversity@color}%
1425             \centering\webuniversity}}
1426     \par\vspace{.1\textheight}
1427     \noindent\hspace*{-\oddsidemargin}%
1428     \makebox[\ linewidth]{\parbox{\ linewidth}%
1429         {\eqex@coverpageSubjectFmt
1430             \color{\websubject@color}%
1431             \centering\eqexamsubject}}
1432     \par\vspace{\bigskipamount}
1433     \noindent\hspace*{-\oddsidemargin}%
1434     \makebox[\ linewidth]{\parbox{\ linewidth}%
1435         {\eqex@coverpageTitleFmt
1436             \color{\webtitle@color}%
1437             \centering\webtitle}}
1438     \par\vspace{\stretch{1}}
1439     \optionalpagematter
1440     \par\vspace{\stretch{1}}\cpNameAndID
```

```

1441     \eqe@SumryHoriz\eqe@SumryVert
1442     \sumryAnnots
1443     \endgroup
1444 }

```

The following are various local strings used in the **Exam Record**, the default is to use English words.

**\cpSumryHeader** The header that appears at the top of the box

**\cpSumryPts** The formatting for the number of points

**\cpSumryPage** The word for “Page”

**\cpSumryTotal** The word for “Total”

**\cpSumryGrade** The word for “Grade”

**\cpSetSumryWidth** The width of the summary box

**\cpUsefbox** Enclose in an **\fbox**? The default is yes

**\cpNofbox** Do not enclose in an **\fbox**

```

1445 \newcommand{\cpSumryHeader}{\textbf{Exam Record}}
1446 \newcommand{\cpSumryPts}{\text{pts}}
1447 \newcommand{\cpSumryPage}{Page}
1448 \newcommand{\cpSumryTotal}{Total}
1449 \newcommand{\cpSumryGrade}{Grade}
1450 \newcommand{\cpSetSumryWidth}[1]{\bgroup\setlength{\tempdima}{#1}
1451     \xdef\cp@SetSumryWidth{\the\tempdima}\egroup}
1452 \cpSetSumryWidth{.5\textwidth}
1453 \newcommand{\cpUsefbox}{\let\cp@Usefbox\fbox}
1454 \cpUsefbox
1455 \newcommand{\cpNofbox}{\let\cp@Usefbox\mbox}
1456 \newcommand{\cprulelength}{1.5in}

```

A helper command used in **\cpSumrybyparts**

```

1457 \def\cp@InsertNaming#1{%
1458     \ifcase\eqe@coverPageNaming
1459         #1\or\@nameuse{userFriendly#1}\or
1460         \@nameuse{userCustom#1}\else#1\fi
1461 }

```

**\cpSumrybyparts** The routine for building the summary box, where we list the statistics for each part.

```

1462 \newcommand{\cpSumrybyparts}{%
1463     \eqe@SumryVert\cp@Usefbox{%
1464         \ifx\cp@Usefbox\fbox
1465             \def\cp@sumryWdth{\cp@SetSumryWidth-2\fboxrule-2\fboxsep}\else
1466             \def\cp@sumryWdth{\cp@SetSumryWidth}\fi
1467             \begin{minipage}[b]{\cp@sumryWdth}\kern0pt
1468                 \begin{flushleft}

```

```

1469      \setlength{\eqetmplengtha}{\cprulelength}%
1470      \edef\eqe@cprulelength{\the\eqetmplengtha}%
1471      \csarg\ifx{NumberOfParts}\relax
1472      \else
1473      \count2=0
1474      \medskip
1475      \cpSumryHeader\par\parskip\bigsipamount
1476      \def\\#1{\advance\count2by\csname ##1total\endcsname
1477      \underbar{\makebox[0pt][1]{%
1478      \cp@InsertNaming{##1}\hspace*{\eqe@cprulelength}}%}
1479      / $ \eqe@ptsFmt{\csname ##1total\endcsname}%
1480      \cpSumryPts$\par}\thePartNames
1481      \fi
1482      \underbar{\makebox[0pt][1]{\cpSumryTotal}}%
1483      \hspace{\eqe@cprulelength}%
1484      \$ \eqe@ptsFmt{\the\count2\relax}\cpSumryPts$ \par
1485      \underbar{\makebox[0pt][1]{\cpSumryGrade}}%
1486      \hspace{\eqe@cprulelength}%
1487      \ifx\cp@Usebox\fbox\medskip\fi
1488      \end{flushleft}\kern0pt
1489      \end{minipage}}\par
1490 }

```

\cpSumrybypages The routine for building the summary box, where we list the statistics for each page.

```

1491 \newcommand{\cpSumrybypages}{%
1492   \eqe@@SumryVert\cp@Usebox{%
1493     \ifx\cp@Usebox\fbox
1494       \def\cp@sumryWdth{\cp@SetSumryWidth-2\fboxrule-2\fboxsep}\else
1495       \def\cp@sumryWdth{\cp@SetSumryWidth}\fi
1496     \begin{minipage}[b]{\cp@sumryWdth}\kern0pt
1497     \begin{flushleft}
1498       \setlength{\eqetmplengtha}{\cprulelength}%
1499       \edef\eqe@cprulelength{\the\eqetmplengtha}%
1500       \csarg\ifx{NumberOfParts}\relax
1501       \else\medskip\count0=0\relax\count2=0\relax
1502       \cpSumryHeader\par\parskip\bigsipamount
1503       \ifsolutionsAtEnd
1504         \@ifundefined{eqExamQuesLastPage}{\def\NUMPAGES{0}}%
1505         {\edef\NUMPAGES{\@nameuse{eqExamQuesLastPage}}}%
1506       \else
1507         \@ifundefined{eqExamLastPage}{\def\NUMPAGES{0}}%
1508         {\edef\NUMPAGES{\@nameuse{eqExamLastPage}}}%
1509       \fi
1510       \@whilenum\count0<\NUMPAGES\relax\do{%
1511         \advance\count0by1\relax
1512         \@ifundefined{Page}{\the\count0total}{\count4=0\relax}
1513         {\count4=\@nameuse{Page}\the\count0total}\relax}%
1514         \csarg\ifx{Page}{\the\count0spilltotal}\relax
1515         \else\advance\count4by\csname%

```

```

1516     Page\the\count0spilltotal\endcsname\relax\fi
1517     \advance\count2by\count4\relax\underbar{%
1518     \makebox[0pt][1]{\cpSumryPage`^{\the\count0}}%
1519     \hspace*{\eqe@cprulelength}}/
1520     \$\eqe@ptsFmt{\the\count4\relax}%
1521     \cpSumryPts$\csarg\ifx{Page\the\count0spilltotal}\relax
1522     \else\$(@nameuse{Page\the\count0spilltotal}%
1523     \cpSumryPts+\@nameuse{Page\the\count0total}%
1524     \cpSumryPts)\$\\fi\\par
1525   }% while
1526   \\fi
1527   \underbar{\makebox[0pt][1]{\cpSumryTotal}}%
1528   \hspace*{\eqe@cprulelength}}/
1529   \$\eqe@ptsFmt{\the\count2\relax}\cpSumryPts$\\par
1530   \underbar{\makebox[0pt][1]{\cpSumryGrade}}%
1531   \hspace*{\eqe@cprulelength}}/
1532   \\ifx\cp@Usefbox\fbox\medskip\\fi
1533   \\end{flushleft}\\kern0pt
1534 \\end{minipage}}\\par
1535 }

```

If the author takes the `coverpage` option, `\eqex@coverpage` is set equal to `\eqexcoverpagedesign`, otherwise, it is set equal to `\relax`.

```
1536 \\AtBeginDocument{\eqex@coverpage}
```

### 13.4 Insert Points in Margins and Compute Page Totals

Here we attempt to place point values of a problem in the margins and to compute the page totals.

`\probvalue` This is a fundamental macro for keeping track of the points of the problem. It increments the counter `eqpointvalue`, which keeps a running total of the points of the current part of the exam, puts the value in the margins, and sets a `mark`, so that at the end of the page, we can compute the number of points on the current page. This macro is used in several situations, for example, in the `problem` environment, `\manualcalcparts` and in `\autocaleparts`. **Should not be redefined.**

Parameters

```
#1 = total points for this problem
#2 = 0 if total points, otherwise, #2 is the number of points each
      problem.
```

```

1537 \\def\\@marktotalvalue{\\global\\let\\eqe@innermarkpts\\relax
1538   \\if@bypasseqexamheading\\else\\def\\eqe@marktxt{%
1539     \\theeqpointvalue\\nameuse{eqExam}\\theeq@numparts}%
1540   \\ifx\\endparts\\endexercise@parts@tabular
1541     \\xdef\\eqe@innermarkpts{\\noexpand\\mark{\\eqe@marktxt}}\\else
1542     \\mark{\\eqe@marktxt}\\fi\\fi
1543 \\def\\probvalue#1#2{\\addtocounter{eqpointvalue}{#1}%
1544   \\ifdispl@yPoints\\marginpoints{#1}{#2}\\fi

```

```

1545      \@marktotalvalue}

\widhtpboxes is the width of the box in the margins that contains the points or totals. The
design of the box keys off this width.

1546 \newcommand{\widhtpboxes}{35pt}

\marginboxdesign is the basic box that encloses the points on the right, and the totals. This box may
be redefined as desired, in which case, \measurePtBoxHt should be re-executed.

1547 \newcommand{\marginboxdesign}[2][]{%
1548   \parbox{\widhtpboxes}{\tabcolsep=0pt\relax
1549     \begin{tabular}{|c|}\hline
1550       \vrule height15pt width0pt#1\\\hline
1551       \makebox[\widhtpboxes-2\fboxrule]{#2}\\\hline
1552     \end{tabular}%
1553   }%
1554 }

```

\eqleftmarginbox This macro places the problem value in the left margin, can be redefined, if you dare.

#### Parameters

```

#1 = total points for this problem
#2 = 0 if total points, otherwise, #2 is the number of points each
problem.

```

Currently, this macro is not used so I'll make it into verbatim text.

```

\newcommand{\eqleftmarginbox}[2]{\makebox[0pt][r]{%
  \setlength{\tabcolsep}{0pt}%
  \raisebox{-.5\height}[0pt][0pt]{%
    \marginboxdesign{\marginpointsboxtext{#1}{#2}}%
  }\hspace*{\marginparsep}\hspace*{\eqemargin}}%
}

```

### Formatting the points

\ptsLabel The following three convenience commands can be used to localize some of the  
\eachLabel strings to other languages.

```

\pointsLabel 1555 \providecommand{\ptsLabel}[1]{\def\eqptsLabel{\#1}\ptsLabel{pts}}
1556 \providecommand{\ptLabel}[1]{\def\eqptLabel{\#1}\ptLabel{pt}}
1557 \newcommand{\eachLabel}[1]{\def\eqeachLabel{\#1}\eachLabel{ea.}}

```

These next two are used by the `instructions` environment to display the points for the exam.

```

1558 \newcommand{\pointsLabel}[1]{%
1559   \def\eqpointsLabel{\#1}\pointsLabel{points}%
1560 \newcommand{\pointLabel}[1]{%
1561   \def\eqpointLabel{\#1}\pointLabel{point}%
}

```

### **pointsonleft or pointsonboth**

- \marginpointtext Creates the text for \eqleftmargin to use. From the macro definition, if #2 is 0, then we write the points for the problem, else, we write the points each for the problem. \leftmarginPtsTxt is the formatting for the total points for the problem; while \leftmarginPtsEaTxt is the formatting for the {problem\*}{<num>ea}-type problems.
- \pointsAsText We begin by giving the user a choice, typeset the points in math mode (the default) or typeset in the normal font.
- ```
1562 \def\pointsAsText{\def\eqe@ptsFmt{\text{}}  
1563 \let\eqe@ptsFmt\relax  
1564 \onlypreamble\pointsAsText}
```
- \marginpointtext determines, based on #2 whether the points are ‘points each’ or not, and calls either \leftmarginPtsTxt or \leftmarginPtsTxt, as appropriate.
- ```
1565 \newcommand{\marginpointtext}[2]{\ifnum#2=0\leftmarginPtsTxt{\#1}\else  
1566 \leftmarginPtsEaTxt{\#2}\fi  
1567 }
```
- \leftmarginPtsTxt displays points in the left margin: (#1<sup>pt</sup>) or (#1<sup>pts</sup>), where #1 is the number of points for this problem.
- ```
1568 \newcommand{\leftmarginPtsTxt}[1]{(\small\eqe@ptsFmt{\#1}^{\text{\%}}  
1569 \ifnum#1=1\relax\eqptLabel\else\eqptsLabel\fi})$)}
```
- \leftmarginPtsEaTxt displays ‘points each’ in the left margin: (#1<sub>ea.</sub><sup>pt</sup>) or (#1<sub>ea.</sub><sup>pts</sup>), where #1 is the number of points for each part of this problem.
- ```
1570 \newcommand{\leftmarginPtsEaTxt}[1]{(\small\eqe@ptsFmt{\#1}_{\text{\%}}  
1571 \eqeachLabel}^{\text{\%}}\ifnum#1=1\relax\eqptLabel\else  
1572 \eqptsLabel\fi})$)}
```
- \eqleftmargin Places the number of points (or points each) in the left margin. Can be redefined as desired. This macro is used when author chooses the `pointsonleft` or `pointsonbothsides` option. The text for the points is defined above, \marginpointtext.
- ```
1573 \newcommand{\eqleftmargin}[2]{\makebox[0pt][r]{\marginpointtext{\#1}{\#2}}%  
1574 \setlength{\@tempdima}{\marginparsep+\eqemargin} %  
1575 \hspace*{\@tempdima}}
```

### **pointsonright or pointsonboth**

- \marginpointsboxtext When the author selects `pointsonright` or `pointsonbothsides`, a box appears in the right margin containing problem totals, this is the text for the box.
- ```
1576 \newcommand{\marginpointsboxtext}[2]{\small\eqe@ptsFmt{\#1},\text{\%}  
1577 \ifnum#1=1\relax\eqptLabel\else\eqptsLabel\fi})$}
```
- \eqrightmarginbox When the author selects `pointsonright` or `pointsonbothsides`, a box appears in the right margin containing problem totals, this is the box that appears.

\insertPointsBoxPDF These two commands are \letting them be either a form field (that the document author can fill in during online grading, or as \relax. It depends on whether the email option is taken or not.

```

1578 \def\@insertPointsBoxPDF
1579 {
1580     \def\fieldName{pointsgiven.\curr@quiz.page\thepage.%
1581             \theeqquestionno}%
1582     \calcTextField[\F\FFHidden\BC{}\Q1\textColor{1 0 0 rg}]
1583         {\fieldName}{\widthtpboxes}{15pt}%
1584 }
1585 \def\@insertTotalsBoxPDF
1586 {
1587     \def\fieldName{pagetotals.\curr@quiz.page\thepage}%
1588     \calcTextField[\F\FFHidden\BC{}\Q1\textColor{1 0 0 rg}
1589             \AA{\AACalculate[AFSimple_Calculate("SUM",
1590                 new Array("pointsgiven.\curr@quiz.page\thepage"));}]%
1591         {\fieldName}{\widthtpboxes}{15pt}%
1592 }
1593 \ifx\use@email y
1594     \let\insertPointsBoxPDF\@insertPointsBoxPDF
1595     \let\insertTotalsBoxPDF\@insertTotalsBoxPDF
1596 \else
1597     \let\insertPointsBoxPDF\@empty
1598     \let\insertTotalsBoxPDF\@empty
1599 \fi

```

The points box that appears in the left margin, may be re-defined, if you dare. At the bottom of the box goes the points for the problem, if the email option is used, in the top, a text field is inserted.

```

1600 \newcommand{\eqrightmarginbox}[2]{\makebox[0pt][1]{%
1601     \setlength{\tabcolsep}{0pt}%
(2011/05/08) new calculation for the right point box.
1602     \setlength{\tempdima}{\textwidth-\eqemargin+\marginparsep}%
1603     \hspace*{\tempdima}%
1604     \raisebox{-.5\height}[0pt][0pt]{%
1605         \marginboxdesign[\insertPointsBoxPDF]%
1606         {\marginpointsboxtext{\#1}{\#2}}%
1607     }\hfil
1608 }%
1609 }

```

At the end of each exam \end{exam} the part totals can be optionally displayed on the right. This is the box for doing that.

```

1610 \newcommand{\eqemarginboxright}[2]{\makebox[0pt][1]{%
1611     \setlength{\tabcolsep}{0pt}%
1612     \setlength{\tempdima}{\textwidth+\marginparsep-\parindent}%
1613     \hspace*{\tempdima}%
1614     \raisebox{-.5\height}[0pt][0pt]{%
1615         \marginboxdesign[\insertTotalsBoxPDF]%

```

```

1616           {\marginpointsboxtext{#1}{#2}}%
1617       }\hfil
1618   }%
1619 }

```

At the end of each exam `\end{exam}` the part totals can be optionally displayed on the left. This is the box for doing that.

```

1620 \newcommand{\eqemarginboxleft}[2]{\noindent\makebox[0pt][r]{%
1621     \raisebox{-.5\height}[0pt][0pt]{%
1622         \marginboxdesign[\insertTotalsBoxPDF]%
1623         {\marginpointsboxtext{#1}{#2}}%
1624     }{\settowidth{\@tempdima}{\eqe@hspannerPrb}%
1625     \setlength{\@tempdima}{\marginparsep+\eqemargin-\@tempdima}%
1626     \hspace*{\@tempdima}\hfil
1627 }

```

`\measurePtBoxHt` We measure the height of our point/total boxes and store it in the length `\eq@pointboxtotalheight`, which is used to separate the boxes so they don't overlap.

```

1628 \newcommand{\measurePtBoxHt}{\setbox\eq@pointbox\hbox{%
1629     \marginboxdesign{\marginpointsboxtext{00}{0}}%
1630     \setlength\eq@pointboxtotalheight{.5\ht\eq@pointbox}%
1631     \xdef\halfHtPtBox{\the\eq@pointboxtotalheight}%
1632     \setlength\eq@pointboxtotalheight{\dp\eq@pointbox+\ht\eq@pointbox}%
1633     \xdef\totHtPtBox{\the\eq@pointboxtotalheight}%
1634     \xdef\dpPtBox{\the\dp\eq@pointbox}%
1635     \xdef\htPtBox{\the\ht\eq@pointbox}%
1636 }
1637 \measurePtBoxHt

```

A helper command to set both margin boxes.

```

1638 \newcommand{\eqbothmargins}[2]{\eqleftmargin{#1}{#2}%
1639     \eqrightmarginbox{#1}{#2}}

```

The macro `\probvalue`, defined above, says

```
\mark{\theeqpointvalue\csname eqExam\endcsname\theeq@numparts}
```

so the `\botmark` contains the point value of this page and the part number for this page.

```
1640 \def\lastparttotaled{0}
```

The `botmark` looks like 18`\eqExam0`, where 18 will be the total number of points accumulated for this exam part. We need to retrieve these numbers, I don't remember why I save them this way.

`\parsetotals` The `\parsetotals` macro is called in `\settotsbox` to retrieve the ongoing point values from `\botmark`, and returns two parameters, contained in `\argi` and `\argii`. Whereas, `\stripeqExam` just retrieves the first parameter only.

```

1641 \def\parsetotals#1\eqExam#2\end{\def\argi{#1}\def\argii{#2}}
1642 \def\stripeqExam#1\eqExam{\def\argii{#1}}

```

**\settotsbox** This is the box containing the page total, it may appear on the left or right side bottom corner.

```

1643 \def\settotsbox{%
1644   \expandafter\parsetotals\botmark\eqExam\end
1645   \ifx\argi\empty\hfil
1646   \else\ifx\argii\empty\hfil
1647   \else
1648     \expandafter\stripeqExam\argii

```

Set `eqpointsthispage` equal to `\argi`, which should be the accumulated total for this part of the test so far.

```
1649   \setcounter{eqpointsthispage}{\argi}%
```

This subtract `eqpointsofar`, which should be the total for this test part through the previous page. The difference is the number of points for this page.

```
1650   \addtocounter{eqpointsthispage}{-\value{eqpointsofar}}%
```

Now we set `eqpointsofar` to the new accumulated total `\argi`.

```
1651   \setcounter{eqpointsofar}{\argi}%
```

And save to the auxiliary file for later usage.

```

1652   \xdef\lastparttotal{\argii}%
1653   \eqe@IWO\@auxout{\string\csarg\string
1654   \gdef{Page\thepage total}%
1655   {\theeqpointsthispage}}%

```

Finally, place the totals box.

```

1656   \totalsbox
1657   \fi
1658   \fi
1659 }
```

**\totalsboxtext** This is the text that appears in the totals boxes

```

1660 \newcommand\totalsboxtext{\small$%
1661   \eqe@ptsFmt{\theeqpointsthispage}\,,\text{%
1662   \ifnum\theeqpointsthispage=1\relax\eqptLabel\else
1663   \eqptsLabel\fi}$}

```

**\eqevtranstotbox** `\eqevtranstotbox` is a length that can be used to raise or lower the position of the total boxes in the left/right bottom corner. The default is `0pt`.

```

1664 \newlength\eqevtranstotbox
1665 \setlength{\eqevtranstotbox}{0pt}
```

**\totalsboxleft** There are two totals boxes, one for the left and one for the right side. These can be redefined as desired.

```

1666 \def\eqe@chkZeroTotals{\let\eqe@allow\eqe@YES
1667   \ifx\eqe@zeroTotalsAllowed\eqe@NO
1668   \ifnum\theeqpointsthispage=0 \let\eqe@allow\eqe@NO\fi\fi}
1669 \newcommand{\totalsboxleft}{\eqe@chkZeroTotals
1670   \ifx\eqe@allow\eqe@YES
1671   \makebox[0pt][r]{\setlength\tabcolsep{0pt}%
1672     \raisebox{-\height+\eqevtranstotbox}[0pt][0pt]{%
```

```

1673           \marginboxdesign[\insertTotalsBoxPDF]{\totalsboxtext}%
1674       } \hspace*{\marginparsep}%
1675   }\fi\hfil
1676 }
1677 \newcommand{\totalsboxright}{\eqe@chkZeroTotals
1678   \ifx\eqe@allow\eqe@YES
1679     \makebox[0pt][l]{\setlength{\tabcolsep}{0pt}%
1680       \hspace*{\textwidth}\hspace*{\marginparsep}%
1681       \raisebox{-\height+\eqevtranshtbox}[0pt][0pt]{%
1682         \marginboxdesign[\insertTotalsBoxPDF]{\totalsboxtext}%
1683       }%
1684     }\fi\hfil
1685 }

```

We begin the document by declaring the current part is part 0 with 0 points. This is the default, in case the author writes a document with no parts or points!

```

1686 \ifeqe@nopoints\else\if@bypassesqexamheading\else
1687 \AtBeginDocument{\mark{0}\csname eqExam\endcsname0}}
1688 \fi\fi

```

At the end of the document, we write out the number of parts for this test, and the names of the parts the author has given each part.

```

1689 \AtEndDocument{%
1690   \eqe@IWO\@auxout{\string\csarg\string\gdef{NumberOfParts}%
1691     {\arabic{eq@numparts}}}}%
1692   \eqe@IWO\@auxout{\string\csarg\string\gdef{thePartNames}%
1693     {\the\partNames}}%
1694   \clearpage\addtocounter{page}{-1}\writelastpage\relax
1695   \addtocounter{page}{1}%
1696 }

```

**\theGrandTotal** When an exam has multiple parts, the total of each part is computed and the grand total is computed with \theGrandTotal.

```

1697 \newcommand{\theGrandTotal}{%
1698   \$\eqe@ptsFmt{\csname eqeGrandTotal\endcsname}\$}

```

**\totalForPart** User access to the total for a exam environment, one argument, the name of the exam.

**\percentForPart** Attempts to calculate the percent of the total that the referenced exam (#1) contributes to the grand total.

```

1699 \newcommand{\totalForPart}[1]{\$\eqe@ptsFmt{\csname#1total\endcsname}\$}
1700 \def\tot@lForPart#1{\csname#1total\endcsname}
1701 \newcommand{\percentForPart}[1]{\$\eqe@ptsFmt
1702   {\csname#1percent\endcsname}\$ \%}

```

### 13.5 Computing Number of Points within a Segment of the Exam

We add some commands for calculating number of points in a segment of the exam. A segment being defined subset of consecutive problems within an exam.

We can define segments by placing markers (using `\placeMarkerHere`) between problems. We can then calculate the total number of points between markers.

The counter below is a scratch counter for making the calculations. We assume the `calc` package is loaded, it does the work for us.

```
1703 \newcounter{markerCnt}
```

`\placeMarkerHere` Placed outside of any `problem/problem*` environment, this command takes one argument, the symbolic name for this marker. We write to the auxiliary file and define a command whose name is based on #1, and whose value is the cumulative total `\theeqpointvalue`.

```
1704 \def\placeMarkerHere#1{%
1705   \eqe@IWO\@auxout{\string\csarg\string\gdef
1706     {#1SaveTotalHere}{\theeqpointvalue}}%
1707 }
```

`\calcFromMarkers` Once the markers are in place, we can calculate the number of points defined between two such markers. The `\calcFromMarkers` takes three arguments, #2 and #3 are the symbolic names of the two markers. While, #1 is an optional argument for formatting the calculation. The default is `\@markerTotalFmt`, defined below in `\markerTotalFmt`. The value of the total is `\themarkerCnt`.

```
1708 \newcommand{\calcFromMarkers}[3]{[\@markerTotalFmt]{%
1709   \ifundefined{#2SaveTotalHere}{}{%
1710     {\@ifundefined{#3SaveTotalHere}{}{\setcounter{markerCnt}{%
1711       {\@nameuse{#2SaveTotalHere}-\@nameuse{#3SaveTotalHere}}}}%
1712       \ifnum\value{markerCnt}<0\relax
1713         \setcounter{markerCnt}{-\value{markerCnt}}\fi#1}}%
1714 }}
```

`\markerTotalFmt` Used to set the global format of the marker totals. The value of the marker total is `\themarkerCnt`. The default follows the definition of `\markerTotalFmt`

```
1715 \newcommand{\markerTotalFmt}[1]{\def\@markerTotalFmt{#1}}
1716 \markerTotalFmt{\space(\themarkerCnt\space points)}
```

`\calcQsBtwMarkers` `\calcQsBtwMarkers[Mrk2]{Mrk1}` does a number of things; primarily, it determines the range of the questions between the two marks. The names of the commands produced are all based in the first marker name `Mrk1`. `\Mrk1Start` is the first question number that follows the placement of `\calcQsBtwMarkers`.

`\Mrk1End` Similarly, `\Mrk1End` is the last question number between the two marks `Mrk1` and `Mrk2`.

`\Mrk1nQs` We also calculate `\Mrk1nQs`, the number of questions appearing between `Mrk1` and `Mrk2`.

```
1717 \newcommand{\calcQsBtwMarkers}[2][]{\setcounter{markerCnt}{0}%
1718   \def\@eqc@argi{#1}}
```

`\Mrk1thisQnum` is the question number in effect at the point where the command `\calcQsBtwMarkers` is inserted.

```
1719   \eqe@IWO\@auxout{\string\csarg\string\gdef
1720     {#2thisQnum}{\theeqquestionnoi}}%
```

```

\Mrk1Start is 0 if undefined.

1721      \@ifundefined{#2thisQnum}{\csarg\xdef{#2Start}{0}%
1722          \eqe@IWO\@auxout{\string\csarg\string\gdef
1723              {#2Start}{0}}%
1724      }{%

```

\Mrk1Start is the current question number plus 1.

```

1725      \setcounter{markerCnt}{\value{equestionnoi}+1}\csarg
1726          \xdef{#2Start}{\the\value{markerCnt}}%
1727          \eqe@IWO\@auxout{\string\csarg\string\gdef
1728              {#2Start}{\@nameuse{#2Start}}}}%
1729      }

```

Using now both *Mrk1* and *Mrk2* we calculate the difference in the two. Result held in `markerCnt`. If there is no optional parameter, *Mrk2*, do not produce the `\Mrk1thisQnum`.

```

1730      \ifx\eqe@argi\empty\else
1731          \@ifundefined{#2thisQnum}{\setcounter{markerCnt}{0}}%
1732              {\@ifundefined{#1thisQnum}{\setcounter{markerCnt}{0}}{%
1733                  \setcounter{markerCnt}{%
1734                      {\@nameuse{#1thisQnum}-\@nameuse{#2thisQnum}}}}%
1735      }{%
1736      \fi

```

\Mrk1nQs is the number of questions that appear between *Mrk1* and *Mrk2*.

```

1737      \csarg\xdef{#2nQs}{\the\value{markerCnt}}%
1738      \eqe@IWO\@auxout{\string\csarg\string\gdef
1739          {#2nQs}{\the\value{markerCnt}}}}%

```

\Mrk1End is 0 if undefined. If there is no optional parameter, *Mrk2*, do not produce the `\Mrk1End`

```

1740      \ifx\eqe@argi\empty\else
1741          \@ifundefined{#1thisQnum}{\csarg\xdef{#2End}{0}}%
1742              \eqe@IWO\@auxout{\string
1743                  \csarg\string\gdef{#2End}{0}}%
1744      }{%

```

\Mrk1End is \Mrk2thisQnum.

```

1745      \csarg\xdef{#2End}{\@nameuse{#1thisQnum}}%
1746      \eqe@IWO\@auxout{\string\csarg\string\gdef
1747          {#2End}{\@nameuse{#2End}}}}%
1748      }%
1749      \fi
1750 }

```

`\markStartFor` We provide a user interface to the three macros defined above. The required parameter is a mark (a name that was used as the first argument of `\markNumQsFor` `\calcQsBtwMarkers`).

```

1751 \newcommand{\markStartFor}[1]{\@nameuse{#1Start}}
1752 \newcommand{\markEndFor}[1]{\@nameuse{#1End}}
1753 \newcommand{\markNumQsFor}[1]{\@nameuse{#1nQs}}

```

## 13.6 Useful Commands to Write Problems

### 13.6.1 The `\placeAtxy` command

`\placeAtxy` Use to place material within the solutions area that is visible to the student on the test document. Syntax:

```
\placeAtxy{x_dim}{y_dim}{content}

\placeAtxy goes immediately after \end{solution}
1754 \newcommand{\placeAtxy}[3]{%
1755   \par\nointerlineskip
1756   \ifdisplayworkarea
1757     \ifx\eq@insertverticalspace\eqe@YES
1758       \makebox[0pt][l]{\hspace*{-\parindent}\hspace*{#1}%
1759       \raisebox{#2}[0pt][#3]\fi
1760   \fi
1761 }%
```

### 13.6.2 The workarea environment

As of this writing, 2012/12/09, this segment of code has been re-written. The `splitsolution` and `panel` environments have a new syntax. I've never gotten any feedback from user who use these environments, so I suspect the impact of these changes are minimal.

`workarea` A work area is an environment used when we display vertical space such as when  
`\workareasb` the `nosolutions` and `vspacewithsolns` options are in effect. `\workareasb` is a save box used in the argument of `lrbox` to save the contents of the `minipage`.

```
\begin{workarea}[width]{depth}
...
\end{workarea}

1762 \newsavebox{\workareasb}

\workareaVadj{\langle skip\rangle} adjusts the vertical skip of the first line that appears in the workarea
environment.
1763 \def\workareaVadj#1{\bgroup\def\eqe@rgi{#1}\ifx\eqe@rgi\empty
1764   \def\eqe@rgi{0pt}\fi\setlength{\tempdima}{\eqe@rgi}%
1765   \xdef\workareaV@dj{\the\tempdima}\egroup
1766 } % dps1
1767 \workareaVadj{3pt}
1768 \def\workareaCmds#1{\def\@rgi{#1}\ifx\@rgi\empty
1769   \let\work@reaCmds\relax\else
1770   \def\work@reaCmds{#1}%
1771 \let\work@reaCmds\relax
1772 \def\priorworkareaCmds#1{\def\@rgi{#1}\ifx\@rgi\empty % dpsj6
1773   \let\priorWorkAreaCmds\relax\else
1774   \def\priorWorkAreaCmds{#1}\fi}
1775 \let\priorWorkAreaCmds\relax
```

```

1776 \newenvironment{workarea}[2][\linewidth]
1777 {%
1778     \removelastparskip
1779     \edef\workareadepth{\if\currhideopt H0pt\else#2\fi}%
1780     \begin{lrbox}{\workareasb}\setlength{\eqetmplengtha}{#1}%

```

A change in support of `\fillTypeGrid`. When `\ifforceEqualCells` is true, we adjust the width of this `minipage` to conform to the shorter line produced by the grid.

```

1781     \ifx\makeVgrid\relax\else % dps2
1782         \ifforceEqualCells
1783             \ifx\fillLinesLineWidth\empty\else
1784                 \setlength{\eqetmplengtha}{\fillLinesLineWidth}\fi
1785             \fi
1786         \fi
1787     \begin{minipage}[b][\workareadepth][t]{\eqetmplengtha}%

```

Apply vertical skip `\workareaV@dj` here, set by `\workareaVadj`.

```
1788     \vglue\workareaV@dj
```

Adjust `\leftskip` when the problem is a lead-in.

```

1789     \@ifundefined{leadinIndentPrtSep}{}{\ifx\solutionparshape\empty
1790         \else\leftskip\leadinIndentPrtSep\fi}\workareaCmds
1791 }{%
1792     \end{minipage}\end{lrbox}%

```

4/5/11 Changed the logic here, so the `workarea` is available for the `vspacewith-solns` option.

```

1793     \ifeq@solutionsafter\else
1794     \par\ifdisplayworkarea
1795         \ifx\eq@insertverticalspace\eq@YES
1796             \removelastparskip
1797             \vglue-\baselineskip
1798             \if\currhideopt H\else
1799                 \noindent\strut\smash{\usebox{\workareasb}}%
1800             \fi\fi
1801     \fi\fi
1802 }

```

### 13.6.3 The `splitsolution` environment

`splitsolution` This is a special solution environment designed for use with the `online` or `email` options, but it is compatible with all other options as well.

New Syntax	Old Syntax
<code>\begin{splitsolution}[width][depth]</code>	<code>\begin{splitsolution}{depth}</code>
<code>\begin{panel}[l r]</code>	<code>\begin{panel}[l r]{width}</code>
<code>...</code>	<code>...</code>
<code>\end{panel}</code>	<code>\end{panel}</code>
<code>\begin{solution}</code>	<code>\begin{solution}</code>
<code>...</code>	<code>...</code>
<code>\end{solution}</code>	<code>\end{solution}</code>
<code>\end{splitsolution}</code>	<code>\end{splitsolution}</code>

The `panel` writes its contents to a CUT file, then inputs it back in to get its dimensions, it places the contents in the box `\eqpanelbox`.

Below is an example of the use of the `splitsolution` environment (which is defined well below here).

```
\begin{problem}[5]
This is a question worth $5$ points.
\begin{splitsolution}
\begin{panel}\relax
\includegraphics[scale=.2]{fig1}
\end{panel}
\begin{solution}
This a really good solution and worthy of a $5$ points.
\end{solution}
\end{splitsolution}
\end{problem}
```

Here, we include a graphic. We put it into a box, `\eqpanelbox` to get its dimensions. The `splitsolution` environment has one required argument, the total height of the solution. We then place the graphic in the `panel` environment, and write the solution in the usual way.

`splitsolution` We arrive at the `splitsolution` environment.

```
1803 \def\splitsolution{%
1804     \@ifnextchar[{\splitsolutioni}%
1805         {\splitsolutioniii{\panelwidth}{\panelheight}}%
1806 }
1807 \def\splitsolutioni[#1]{%
1808     \@ifnextchar[{\splitsolutionii{#1}}%
1809         {\splitsolutioniii{\panelwidth}{#1}}%
1810 }
1811 \def\splitsolutionii[#1][#2]{%
1812     \splitsolutioniii{#1}{#2}%
1813 }
1814 \def\splitsolutioniii[#1][#2]{%
1815     \@ifundefined{panel@write}{\newwrite\panel@write}{}%
1816     \gdef\ss@Argiii{#1}\gdef\ss@Argii{#2}%
}
```

Here, we `\let \solution` to `\@sssolution` and replace it with `\@ssSolution`

```
1817     \let\@sssolution\solution
1818     \let\end@sssolution\endsolution
```

```

1819      \let\solution\@ssSolution
1820      \let\endsolution\end@ssSolution
1821      \par\noindent\ignorespaces

```

The `panel` environment should appear next, just after the `\begin{splitsolution}`

```

1822 }
1823 \def\endsplitsolution{%
1824     \ifeq@solutionsafter\solutionsafterSkip\fi % dpsj10
1825     \ifx\solutionparshape\empty\else
1826         \advance\linewidth-\leadinIndentPrtSep\fi %%dps
1827     \edef\eqe@workwidth{\if\ss@Argi 1\noexpand\ss@Argii
1828         \else\noexpand\linewidth\fi}%
1829     \edef\eqe@workfill{\if\ss@Argi 1\else\hfill\fi}%
1830     \ifeq@solutionsafter\else
1831         \begin{workarea}[\eqe@workwidth]{\eqedepth}%
1832             \let\panelGetDimen\relax%
1833             \eqe@workfill\input{panel\thepanel@cnt.cut}%
1834         \end{workarea}
1835     \fi\ifeq@solutionsafter\else\solutionsafterSkip\fi
1836 }

```

`\panelgap` `\panelgap` is the separation between solution area and the panel. `\panelgap` is a box to `\eqpanelbox` put things into, to measure their dimensions. The user accessible commands `\panelwidth` `\panelwidth` returns the width and `\panelheight` the height. There is a special `\panelheight` counter `panel@cnt` to keep track of the panels generated.

`panel@cnt`

```

1837 \newcommand\panelgap{3pt}
1838 \newsavebox{\eqpanelbox}
1839 \newdimen\eqpanelwidth
1840 \newdimen\eqpanelheight

```

`\getDimSSPanel` The `\getDimSSPanel` is an internal command. It places its argument in the box `\eqpanelbox` and gets its dimensions. It saves the dimensions as `\eqpanelwidth` and `\eqpanelheight` (the total height).

```

1841 \newcommand{\getDimSSPanel}[1]{%
1842     \sbox{\eqpanelbox}{#1}%
1843     \eqpanelwidth=\wd\eqpanelbox
1844     \eqpanelheight=\ht\eqpanelbox
1845     \advance\eqpanelheight by\the\dp\eqpanelbox
1846 }

```

`\panelwidth` `\panelwidth` and `\panelheight` are aliases for the dimension registers. This is `\panelheight` for compatibility with previous versions.

```

1847 \def\panelwidth{\eqpanelwidth}
1848 \def\panelheight{\eqpanelheight}
1849 \newcounter{panel@cnt}

```

`panel` environment goes inside the `splitsolution` environment. Permissible values of the first parameter are `r` and `l`, the default being `l`. This is the alignment parameter. The second argument is the width of the panel.

```

1850 \def\panel{\def\eqe@panelir{\eqe@paneli[r]}%

```

```

1851      \@ifnextchar [{\eqe@paneli}
1852          {\@ifnextchar \relax {\expandafter \eqe@panelir \gobble}%
1853              {\eqe@paneli[r]} }%
1854 }

```

We continue the `panel` environment.

```

1855 \def \eqe@paneli [#1]{%
1856     \gdef \ss@Argi [#1]\def \eqe@l {1}\def \eqe@r {r}%
1857     \ifx \ss@Argi \empty \gdef \ss@Argi {r} \else
1858     \ifx \eqe@l \ss@Argi \else \ifx \eqe@r \ss@Argi \else
1859     \PackageError {eqexam}{Permissible arguments for panel are l and r}%
1860     {Use l or r for the argument of panel.} \fi \fi \fi
1861     \stepcounter {panel@cnt}%
1862     \immediate \openout \panel@write panel\thepanel@cnt.cut

```

Manage the `h`, `H`, and global overrides.

```

1863     \if \currhideopt H%
1864         \eqe@IWO \panel@write {\vfill}%
1865         \immediate \closeout \panel@write
1866         \gdef \ss@Argii {0pt}%
1867     \else
1868         \if \currhideopt h \ifeq @solutionsafter \else
1869             \ifeq @globalshowsolutions \else
1870                 \eqe@IWO \panel@write {\vfill}%
1871                 \immediate \closeout \panel@write
1872                 \gdef \ss@Argii {0pt}%
1873             \fi \fi
1874         \fi
1875     \fi
1876     \begingroup

```

Write the contents of this environment to the file `panel\thepanel@cnt.cut`.

```
1877 \let \verbatim@out \panel@write
```

We begin by writing `\panelGetDimen{}` to the CUT file

```

1878 {\lccode `C=`\%\lccode `P=\%
1879 \lowercase{\eqe@IWO \verbatim@out{\string \panelGetDimen PC}} }%

```

Followed by the verbatim listing of the `panel` environment.

```

1880 \verbatimwrite
1881 }
1882 \def \endpanel {%
1883 \endverbatimwrite

```

After the verbatim write, we write `}` to close off the argument of `\panelGetDimen`.

```

1884 {\lccode `P=\}\lowercase{\eqe@IWO \verbatim@out{P}} }%
1885 \immediate \closeout \panel@write
1886 \endgroup

```

The command `\eqePANEL` cut does all the work at the end of this environment. We first `\let \panelGetDimen` to `\getDimenSSPanel` and input the CUT file. This loads the panel contents into `\eqpanelbox`, and gets their dimensions. We

set the value of `\ss@Argiii` which is the width parameter of the `splitsolution` environment. `\mp@Width` calculates the width.

```

1887      \gdef\eqePANELCUT{%
1888          \let\panelGetDimen\getDimSSPanel
1889          \input{panel\thepanel@cnt.cut}%
1890          \setlength{\eq@tmpdima}{\ss@Argiii}%
1891          \xdef\ss@Argiii{\the\eq@tmpdima}%
1892          \xdef\mp@Width{\ifeq@solutionsafter\linewidth
1893              \else\linewidth-\ss@Argiii-\panelgap\fi}%
1894      }\aftergroup\eqePANELCUT
1895 }
```

`\eqe@IW` is a macro that either writes verbatim text (#1), or it gobbles the argument, depending on whether have `solutionsafter`, `nosolutions`, hidden or not hidden.

```

1896 \long\def\eqe@IW#1{%
1897     \ifeq@solutionsafter
1898         \let\eqe@next\@empty
1899     \else
1900         \def\eqe@next{\eqe@IWO\verbatim@out{#1}}%
1901         \ifeq@nosolutions\else
1902             \if\currhideopt H%
1903                 \gdef\ss@Argii{0pt}\let\eqe@next\@empty
1904             \else
1905                 \if\currhideopt h%
1906                     \ifeq@globalshowsolutions\else
1907                         \gdef\ss@Argii{0pt}\let\eqe@next\@empty
1908                     \fi
1909                 \fi
1910             \fi
1911         \fi
1912     \fi
1913     \eqe@next
1914 }
```

The `splitsolution` environment `\lets` the solution environment to the internal `@ssSolution` environment. It performs various tasks then turns it over to the old solution environment, which has been `\let` to `\@sssolution`.

```

1915 \newenvironment{@ssSolution}[1][\ss@Argii]{%
1916 {%
1917     \def\eqe@argi{#1}\ifx\eqe@argi\@empty\else
1918         \let\soln@keys@nLines\@empty
1919         \edef\panelheight{\the\panelheight}%
1920         \edef\panelwidth{\the\panelwidth}%
1921         \edef\temp@exp{\noexpand
1922             \setkeys*\soln@keys{#1}\temp@exp
1923             \ifx\soln@keys@nLines\@empty
1924                 \edef\ss@Argii{\XKV@rm}%
1925             \else
1926                 \c@tempdima\wlVspace\relax
```

```

1927      @tempdima=\soln@keys@nLines@tempdima
1928      \edef\ss@Argii{\the@tempdima}%
1929      \ifx\XKV@rm\empty\else
1930          \if@equsedim\edef\ss@Argii{\XKV@rm}\fi\fi
1931      \fi
1932      \setlength{\eq@tmpdima}{\ss@Argii}%
1933 %      \ifx\sameVspace\empty\gdef\sameVspace{0pt}\fi

```

If the `panelheight` is greater than the requested height, we make the requested height equal to `panelheight`.

```

1934      \ifdim\eqepanelheight>\eq@tmpdima
1935          \eq@tmpdima\eqepanelheight\fi
1936      \xdef\ss@Argii{\the\eq@tmpdima}%
1937      \fi

```

We calculate the depth of the solutions; this is generally the values passed to use as the optional argument, and encapsuled by `\ss@Argii`.

```

1938      \xdef\eqedepth{%
1939          \ifvspacewithsolns\ss@Argii\else
1940              \ifeq@nosolutions\ss@Argii\else
1941                  \ifeq@solutionsafter\ss@Argii\else0pt\fi\fi\fi}%

```

The width is either `\linewidth` or `\linewidth-\ss@Argiii-\panelgap`, where `\ss@Argiii` is the width of the panel.

```

1942      \xdef\mp@Width{\ifeq@solutionsafter\noexpand\linewidth\else
1943          \noexpand\linewidth-\ss@Argiii-\panelgap\fi}%

```

If its a left panel...

```

1944      \if\ss@Argi 1%
1945          \ifeq@solutionsafter
1946              \def\eqe@lPanel{\parbox[b]{\eqedepth}[t]{\ss@Argiii}}

```

Here, and elsewhere, we `\let \panelGetDimen` to `\relax` when we want to purely input the CUT file in the solution.

```

1947          {\let\panelGetDimen\relax
1948              \input{panel\thepanel@cnt.cut}\vfill}\hfill}%
1949          \def\eqe@rPanel{\empty}%
1950      \else

```

For the left panel, we need to subtract `\eqemargin`

```

1951          \def\eqe@subleftgutter{-\string\eqemargin}%
1952          \def\eqe@lPanel{%
1953              \string\parbox[b]{\string\eqedepth}{\ss@Argiii}%
1954              {\string\let\string\panelGetDimen\string\relax
1955                  \string\input{panel\thepanel@cnt.cut}%
1956                  \string\vfill}\string\hfill^J}%
1957          \def\eqe@rPanel{\empty}%
1958      \fi
1959  \else

```

If its a right panel...

```

1960      \ifeq@solutionsafter

```

```

1961      \def\eqe@lPanel{\emptyset}%
1962      \def\eqe@rPanel{%
1963          \hfill\parbox[b]{\eqedepth}[t]{\ss@Argiii}%
1964          {\let\panelGetDimen\relax%
1965              \hfill\input{panel\thepanel@cnt.cut}\vfill}}%
1966      \else

```

For the right panel, we do not subtract `\eqemargin` as above.

```

1967          \let\eqe@sueleftgutter\emptyset
1968          \def\eqe@lPanel{\emptyset}%
1969          \def\eqe@rPanel{%
1970              \string\hfill\string\parbox[b]{\string\eqedepth}%
1971              {\ss@Argiii}\{\string\endgraf%
1972                  \string\noindent\string\hfill\%
1973                  \string\let\string\panelGetDimen\string\relax%
1974                  \string\input{panel\thepanel@cnt.cut}%
1975                  \string\vfill}}%
1976          \fi
1977      \fi
1978      \let\verbatim@out\ex@solns
1979      \par\ifeq@solutionsafter\smallskip\fi

```

Since everything is put a box, we set the `\linewidth`, and set `\solutionparshape` to `\emptyset`.

```

1980      \ifx\solutionparshape\emptyset\else
1981          \advance\linewidth-\leadinIndentPrtSep\fi %%dps
1982      \let\solutionparshape\emptyset
1983      \noindent\minipage{\linewidth}%
1984      \if\ss@Argi 1\noindent\parbox[b]{\eqedepth}[t]{\ss@Argiii}%
1985          \vfill\hfill\fi
1986      \minipage[b]{\eqedepth}[t]{\mp@Width}%
1987      {\lccode`C='`\%lowercase{\eqe@IW{%
1988          \string\def\string\panelgap{\panelgap}%
1989          \string\setlength{\string\panelwidth}{\ss@Argiii}%
1990          \string\def\string\eqedepth
1991              {\ifeq@nosolutions\ss@Argii\else\ss@Argii\fi}C}}%
1992      {\lccode`C='`\%lowercase{\eqe@IW{%
1993          \string\strut\string\noindent%
1994          \string\strut\par\string\nobreak\string\noindent%
1995          \string\hbox\space to\string\linewidth\bgroup^J%
1996          \eqe@lPanel\string\minipage[b]{\string\eqedepth}[t]%
1997          {\string\linewidth\eqe@sueleftgutter%
1998              -\string\panelwidth-\string\panelgap}C
1999      }}}%
2000      \ifeq@solutionsafter
2001          \noindent\strut\hbox to\linewidth\bgroup
2002          \eqe@lPanel
2003          \minipage[b]{\eqedepth}[t]{\linewidth-\ss@Argiii-\panelgap}%
2004          \def\solutionsafterSkip{}%
2005      \fi

```

Here, we start the original definition of the solutions environment, which was \let to \@sssolution.

```
2006     \ifx\soln@keys@nLines\@empty
2007         \edef\passedss@Argii{\ss@Argii}\else
2008         \edef\passedss@Argii{\ss@Argii,nLines=\soln@keys@nLines}\fi
```

For a split solution, cannot allow align left

```
2009     \if\ss@Argi 1\fillerLinesAlignDef\fi % dpsj10
```

I cannot get the filler lines to work when the anserkey is in effect. The next few lines locally turns off filler lines for this problem.

```
2010     \ifanswerkey % dpsj10
2011         \gdef\p@ssToFLs{\let\eq@insertverticalspace\eq@NO
2012             \eq@linedfillerfalse}\fi % dpsj10
2013     \eq@flexextendedfalse
2014     \expandafter\@sssolution\expandafter[\passedss@Argii]%
2015 }%{
2016     \eq@IW{\string\endminipage\eq@rPanel\egroup}%
2017     \ifeq@solutionsafter\endminipage\eq@rPanel\egroup\fi
2018     \end@sssolution
2019     \endminipage\endminipage
2020 }
2021 % Redefine the \cs{paragraph} command
2022 %
2023 \begin{macrocode}
2024 \renewcommand{\paragraph}{%
2025     \startsection{paragraph}{4}{0pt}{12pt}{-3pt}{\bfseries}}
```

**\defaultInstructions** For the instructions environment, defined next, the default string for the instructions is \eq@default@Instructions, this command is defined using \defaultInstructions.

```
2025 \newcommand{\defaultInstructions}[1]{\def\eq@default@Instructions{\#1}}
2026 \defaultInstructions{Instructions.}
```

**instructions** Each test, or a part of a test usually have instructions. This instruction environment is used in this purpose. Normally, the number of points for the part is displayed following the heading (the default is **Instructions.**). You can eliminate the total points from the instructions by taking the nosummarytotals option.

```
2027 \newcommand{\beforeInstrSkip}{1ex}
2028 \newcommand{\afterInstrSkip}{-0em}
2029 \newcommand{\hInstrSpace}{\ }
2030 \newcommand{\styleInstr}{\bfseries}
2031 \newenvironment{instructions}[1][\eq@default@Instructions]{%
```

If \summaryPointTotal is zero, show no summary points.

```
2032     \ifundefined{\thisexamlabel total}{\let\eq@nosummarytotals\eq@YES}
2033     {\ifnum\summaryPointTotal=0 \let\eq@nosummarytotals\eq@YES\fi}%
2034     \expandafter\def\expandafter\eq@argi\expandafter{\#1}%
2035     \def\hspace{\hInstrSpace}%
```

We start a paragraph environment

```

2036  \@startsection{paragraph}{4}{\z@}%
2037  {\beforeInstrSkip\space\plus1ex \minus.2ex}%
2038  {\afterInstrSkip}{\normalfont\normalsize\styleInstr}*%
2039  {\textcolor{@instructionsColor}{\#1}\normalcolor}%
2040  \ifx\eq@nosummarytotals\eqe@YES\else\ifx\eq@argi\empty\else\hspace\fi
2041    {\normalfont\summaryTotalsTxt}\hspace\fi\hspace-\lastskip
2042  \ifx\eq@nosummarytotals\eqe@YES\ifx\eq@argi\empty\else\hspace\fi\fi
2043  \normalfont\normalsize\ignorespaces
2044 }{\par\vskip\beforeInstrSkip\relax}

```

`\summaryPointTotal` `\summaryPointTotal` contains the total points for the current exam; the command `\summaryTotalsTxt` defines its the formatting for the points. The command `\nQuesInExam` is the total number of questions in the exam.

```

2045 \newcommand\summaryPointTotal{\csname\thisexamlabel total\endcsname}%
2046 \newcommand\summaryTotalsTxt{($\eqe@ptsFmt{\summaryPointTotal}\,,\text{%
2047   \ifundefined{\thisexamlabel total}{\eqpointsLabel}%
2048   {\ifnum\summaryPointTotal=1\relax\eqpointLabel\else
2049     \eqpointsLabel\fi}{}$)}%
2050 \newcommand{\nQuesInExam}[1][\thisexamlabel]{%
2051   \def\eqe@argi{\#1}%
2052   \ifx\thisexamlabel\empty\ifx\eqe@argi\thisexamlabel
2053     \PackageError{eqexam}{The optional argument for
2054     \string\nQuesInExam\MessageBreak must be specified}{}\fi\fi
2055   \csname#1nQuestions\endcsname}

```

Make this definition for `hyperref`, so its anchors will be unique. Useful when there are multiple parts of the test.

```

2056 \ifx\hyper@anchor\undefined\else
2057   \renewcommand\theHquestionno{%
2058     \curr@quiz.\theeqquestionno\eqe@fpmrk}
2059   \renewcommand\theQuizno{%
2060     \if\probstar*\curr@quiz.%
2061       \theeqquestionno.part\thepartno.\arabic{quizno}%
2062     \else
2063       \curr@quiz.%
2064       \theeqquestionno.\arabic{quizno}%
2065     \fi
2066   }
2067   \renewcommand\theHpartno{\curr@quiz.%
2068     \theeqquestionno.part\thepartno}
2069 \fi

```

`eqComments` Often, I want to make additional instructions between problems, you can use this comment environment.

```

2070 \newcommand{\beforeCommentSkip}{1.25ex}
2071 \newcommand{\afterCommentSkip}{-1ex}
2072 \newcommand\hCommSpace{\ }
2073 \newcommand\styleComm{\bfseries}

```

```

2074 \newenvironment{eqComments}[1][\strut]{\removelastskip
2075     \def\eqe@argi{\#1}\def\eqe@Strut{\strut}\def\hsc{\styleComm}%
2076     \startsection[paragraph]{4}{\z@}%
2077     {\beforeCommentSkip\space\@plus1ex \@minus.2ex}%
2078     {\afterCommentSkip}{\normalfont\normalsize\styleComm}*%
2079     {\textcolor{\eqCommentsColor}{\#1}}%
2080     \ifx\eqe@argi\eqe@Strut\hskip\afterCommentSkip
2081     \else\ifx\eqe@argi\empty\hskip\afterCommentSkip\else
2082     \hsc\strut\fi\fi\normalfont\normalsize
2083     \color{\eqCommentsColorBody}\ignorespaces
2084 }{\par\vskip\beforeCommentSkip\space\@plus1ex \@minus.2ex}

```

### 13.7 The exam Environment

Each part of the exam is enclosed in an `exam` environment. The environment is a customized version of the `shortquiz` environment.

`\exambegdef` Some definitions that are executed at the beginning of each exam environment.

```

2085 \let\tb@beginexam@code\relax
2086 \def\partialspillovertotals{0}
2087 \def\exambegdef
2088 {%
2089     \csname\thisexamlabel pagemark\endcsname
2090     \ifundefined{partialtotalpg}{}{%
2091         \ifnum\partialtotalpg=\arabic{page}%
2092             \count0=\partialspillovertotals
2093             \advance\count0by\partialtotaleoe
2094             \xdef\partialspillovertotals{\the\count0}%
2095             \eqe@IWO\auxout{\string\csarg\string\gdef
2096                 {Page\partialtotalpg spilltotal}{\partialtotaleoe}}%
2097         }%
2098         \fi
2099     }%
2100     \csarg\ifx{\thisexamlabel pageno}\relax
2101     \else
2102         \csarg\ifx{pagenofirstprob\thisexamlabel}\relax
2103         \else
2104             \csarg\ifnum{\thisexamlabel pageno}%
2105                 < \nameuse{pagenofirstprob\thisexamlabel}%
2106             \else
2107                 \csarg\ifx{\thisexamlabel pagemark}\relax
2108                 \else
2109                     \ifnum\value{page}=%
2110                         \csname\thisexamlabel pageno\endcsname
2111                         \eqe@IWO\auxout{\string\csarg\string\gdef
2112                             {\thisexamlabel pagemark}{\string\newpage}}%
2113                         \fi
2114                         \fi
2115                     \fi
2116     \fi

```

```

2117     \fi
2118     \setcounter{eqquestionnoi}{0}\setcounter{eqpointvalue}{0}%
2119     \setcounter{eqpointsofar}{0}\setcounter{eqpointsthispage}{0}%
2120     \setcounter{eq@count}{0}%

```

We wrote `\begin{eqequestions}` to the top of the solutions file (`\jobname.sol`.

```

2121     \writeBeginEqeQuestions
2122     \label{\thisexamlabel PageBegin}%
2123     \eqe@IWO\@auxout{\string\csarg{string}\gdef
2124     {\thisexamlabel pageno}{\thepage}}%
2125 %     \let\sq@priorhook\empty
2126     \ifeqfortextbook
2127         \global\examenvtrue\tb@beginexam@code
2128     \fi
2129 }

```

`\examenddef` Some definitions that are executed at the end of each exam environment. We place a totals box to report the total since the last page.

```

2130 \def\tb@insmargmark{\ifisinstred\ifismarginans
2131     \insMidMarg{\mark{} }\fi\fi}
2132 \def\eqe@adjForSepRule{\if\eq@parttotals\eqe@YES
2133     \eq@pointboxtotalheight\halfHtPtBox\relax
2134     \advance\eq@pointboxtotalheight\dpPtBox\relax
2135     \advance\eq@pointboxtotalheight\pointsmarginparpush
2136     \vspace*{\eq@pointboxtotalheight}\fi}
2137 \def\eqe@afterexamsepcode{%
2138     \if\eq@parttotals\eqe@YES
2139         \actionsAtPageBreak{\global\let\@spacetobreak1}%
2140         {\global\let\@spacetobreak0}%
2141         \ifx\@spacetobreak0\relax
2142             \bgroup\@tempdima=\pagetotal
2143             \advance\@tempdima\eq@pointboxtotalheight
2144             \ifdim\@tempdima>\pagegoal\aftergroup\newpage
2145             \else\ifnum\arabic{eq@count}>0\relax
2146                 \removelastskip\vskip6pt\kern0pt
2147                 \if\@reportpoints\eqe@One\else\@checkSpacing{0}\fi
2148                 \textcolor{\endexamtotal@color}%
2149                 {\egeomarginbox{\arabic{eq@count}}{0}}\fi
2150             \ifx\eqx@separationrule\eqe@YES
2151                 \separationrule\eqe@adjForSepRule\fi
2152             \egroup\fi
2153         \fi
2154     \else\ifx\eqx@separationrule\eqe@YES
2155         \separationrule\eqe@adjForSepRule\fi
2156     \fi
2157 }
2158 \def\examenddef
2159 {%
2160     \global\let\partialtotaleoe\relax
2161     \global\let\partialtotalpg\relax

```

```

2162     \global\let\afterexamsepcode\relax
2163     \csarg\ifx{NumberOfParts}\relax
2164     \else
2165         \ifnum\value{eq@numparts}<\NumberOfParts
2166             \setcounter{eq@count}{\value{eqpointvalue}}%
2167             \addtocounter{eq@count}{-\value{eqpointsofar}}%
2168             \xdef\partialtotaleof{\arabic{eq@count}}%
2169             \xdef\partialtotalpg{\arabic{page}}%

```

See if there is enough room at the bottom of the page to place the end of exam totals and to start a new exam, if any. If not, forget it, and start a new page.

```

2170         \global\let\afterexamsepcode\eqe@afterexamsepcode
2171         \fi
2172     \fi
2173 \ifeqfortextbook\global\examenvfalse\fi

```

(2011/05/08) Just before the file is closed and input, we write the end of the `eqquestions` environment, `\end{eqquestions}`.

```

2174 \writeEndEqeQuestions
2175 \writetotalsiaux
2176 \addtocounter{page}{-1}%
2177 \writelastpage[\thisexamlabel]\addtocounter{page}{1}%
2178 \ifeqfortextbook\tb@insmargmark\fi
2179 }
2180 \def\@actionsAtPageBreak#1#2{%
2181   \bgroup\@tempdima\pagegoal\advance\@tempdima-\pagetotal
2182   \@tempdimb\@fvsizeskip\vsizer
2183   \ifdim\@tempdima < \@tempdimb #1\else #2\fi\egroup
2184 }

```

**\separationrule** For an exam with multiple parts, a separation rule is created, unless absorbed into a page break. The command `\separationrule` defines this separation rule, it can be redefined as desired.

```

2185 \newcommand{\separationrule}{\makebox[\linewidth-\eqemargin][c]{
2186   {\rule{.67\linewidth}{.4pt}}}

```

(2011/05/08) This is a new environment that makes an exam into a list of problems. This is an attempt to expand the use of `eqexam` to L<sup>A</sup>T<sub>E</sub>X documents. We give control over the page layout so an `eqexam` document can be used within a textbook.

```

2187 \def\eqe@hspannerPrb{\ }
2188 \@ifundefined{ifwithinsoldoc}{\newif\ifwithinsoldoc\withinsoldocfalse}{}
2189 \newcommand{\eqequestopsep}[1]{\def\eqeques@topsep{#1}}
2190 \providecommand{\eqequesparsep}[1]{\def\eqeques@parsep{#1}}
2191 \newcommand{\eqequesitemsep}[1]{\def\eqeques@itemsep{#1}}
2192 \newcommand{\eqequeslistparindent}[1]{\def\eqeques@listparindent{#1}}
2193 \eqequestopsep{0pt}
2194 \eqequesparsep{0pt}
2195 \eqequesitemsep{0pt}

```

```

2196 \eqequeslistparindent{0pt}
2197 \newif\iffirstitem
2198 \def\eqeSolnItemMngt{\iffirstitem\global\firstitemfalse
2199   \let\eqe@next\empty\else\let\eqe@next\item\fi\eqe@next\relax}
2200 \newenvironment{eqequestions}{%
2201   \begin{list}{}{%
2202     \ifwithinoldoc\let\solnItemMngt\eqeSolnItemMngt\fi
2203     \setlength{\labelwidth}{\eqemargin}%
2204     \setlength{\parsep}{\eqeques@parsep}%
2205     \setlength{\itemsep}{\eqeques@itemsep}%
2206     \setlength{\topsep}{\eqeques@topsep}%
2207     \setlength{\itemindent}{0pt}%
2208     \setlength{\listparindent}{\eqeques@listparindent}\dps\%
2209     \ifwithinoldoc\settowidth{\labelsep}{\eqe@hspannerSoln}\else
2210     \settowidth{\labelsep}{\eqe@hspannerPrb}\fi
2211     \setlength{\leftmargin}{\labelwidth}%
2212   }\ifwithinoldoc\global\firstitemtrue\fi\item\relax\end{list}}

```

**exam** Each part of the exam is enclosed in an **exam** environment. The one required parameter is the name of the part, for example, ‘Part1’, ‘Part2’. These should be one word, no white spaces, just letters and possibly numbers.

```

2213 \def\setDefaultfvsizeskip#1{\def\default@fvsizeskip{#1}%
2214   \def\@fvsizeskip{#1}%
2215 \def\default@fvsizeskip{.3}
2216 \edef\@fvsizeskip{\default@fvsizeskip}
2217 \newcommand{\fvsizeskip}[1]{\def\@fvsizeskip{#1}}
2218 \def\autoExamName{exam}\the\value{eq@numparts}
2219 \def\nNumberOfP@rts{\csname NumberOfParts\endcsname}
2220 \aboveskip{0pt}
2221 \let\eqeWrtExamTitleToSolns\eqe@YES
2222 \def\wrtExamTitleInSolns{\let\eqeWrtExamTitleToSolns\eqe@YES}
2223 \def\noExamTitleInSolns{\let\eqeWrtExamTitleToSolns\eqe@NO}
2224 \let\thisexamlabel\empty
2225 \let\isInExamEnv\eqe@NO

```

**\RecordThisExamOff** causes **eqexam** to place **\iffalse** and **\fi** around the solutions to this exam in the solution file. This makes the solution results of this exam invisible. **\RecordThisExamOff** sets an internal switch **\ifDoNotRecordThisExam** to **true**. This switch is set back to **false** at the end of the environment.

```

2226 \newif\ifDoNotRecordThisExam \DoNotRecordThisExamfalse % dpsf02
2227 \def\RecordThisExamOff{\DoNotRecordThisExamtrue} % dpsf02
2228 \def\bIFFalseWrtSolns{\writeT@SolnFile{\protect\iffalse^\J}}}
2229 \def\eiFFalseWrtSolns{\writeT@SolnFile{\protect\fi^\J}}

```

The beginning of the **exam** environment.

```

2230 \newenvironment{exam}[2] []
2231 {%
2232   \ifDoNotRecordThisExam % dpsf02
2233     \expandafter\bIFFalseWrtSolns\fi
2234     \makeRoomForProb{\@fvsizeskip\textheight}{0}%

```

```

2235      \let\isInExamEnv\eqe@YES
2236      \stepcounter{eq@numparts}%
2237      If #2 is empty, use \autoExamName
2238          \def\eqexamargii{#2}\ifx\eqexamargii\empty
2239              \edef\eqexamargii{\autoExamName}\fi
2240          \xdef\thisexamlabel{\eqexamargii}\xdef\curr@quiz{\eqexamargii}%
2241          \def\eqexamargi{#1}\ifx\eqexamargi\empty
2242              \edef\eqexamargi{\eqexamargi}\fi
2243          \expandafter\gdef\expandafter\thisUFexamlabell
2244          \expandafter{\eqexamargi}%
2245          \edef\eq@tmp{\the\partNames\string\\{\eqexamargi}}%
2246          \global\partNames=\expandafter{\eq@tmp}%
2247          \csarg\ifx{NumberOfParts}\relax\else
2248          \ifx\eqeWrtExamTitleToSolns\eqe@YES
2249              \ifnum\numberOfP@rts=1\relax\else
2250                  \def\eqe@argi{#1}\ifx\eqe@argi\empty
2251                      \eqe@writetoSolns{\eqexamargii}\eqe@writetoAux{\string
2252                          \csarg\string\gdef{userFriendly}\eqexamargi{\eqexamargii}}%
2253                  \else
2254                      \eqe@writetoSolns{#1}\eqe@writetoAux{\string
2255                          \csarg\string\gdef{userFriendly#2}{#1}}
2256                  \fi
2257              \fi\fi
2258          \exambegdef
2259          \edef\temp@Exp{\noexpand\shortquiz\sqstar[\eqexamargii]}\temp@Exp
2260          \expandafter\shortquiz\sqstar[\eqexamargii]%
2261      }{%
2262          \examenddef
2263          \vskip\eqeques@parsep\relax\kern0pt %dps88
2264          \endshortquiz
2265          \aftergroup\afterexamsepcode
2266          \par\penalty-100\vskip0pt
2267          \ifDoNotRecordThisExam % dpsf02
2268              \expandafter\eqe@IFFalseWrtSolns\fi
2269          \global\DoNotRecordThisExamfalse
2270      }

```

\EQEcalculateAllTotals (4/22/11) Added the command \EQEcalculateAllTotals. The command is executed as part of the \maketitle command. If \maketitle is not used for some reason \EQEcalculateAllTotals can be executed just after \begin{document}.  
2271 \newcommand{\EQEcalculateAllTotals}{%
2272 \begingroup

We calculate the grand total of all the parts of the exam environments, and we define \eqeGrandTotal, which contains the total.

```

2273      \count\z@=0\relax
2274      \def\##1{\csarg\ifx{\##1total}\relax\else
2275          \advance\count\z@\csname\##1total\endcsname

```

`\thePartNames` list all named exam environments in the document, e.g.,

```
2276      \fi}\csname thePartNames\endcsname  
2277      \xdef\eqeGrandTotal{\the\count\z@}%  
2278      \ifnum\eqeGrandTotal=0 \else
```

If there is a nonzero grandtotal, we move on to calculate the percentages.

```
2279      \def\##1{\eqe@calc@percent{##1}}%  
2280      \csname thePartNames\endcsname\fi  
2281      \endgroup  
2282 }
```

`\eqe@calc@percent` We go through the parts listed in `\thePartNames` and create a calculation of the percentage for that part, and leave it in `\csname#1percent\endcsname`, which can be accessed through the `\percentForPart` command, for example `\percentForPart{<part_name>}` might expand to 45.6%.

`\nPctDecPts` The number of decimal points to carry in the representation of the percentage.

```
2283 \newcommand{\nPctDecPts}{1}  
2284 \def\eqe@calc@percent#1{\@ifundefined{#1total}{%  
2285         \csarg\gdef{#1percent}{??}}{%
```

If the `fp` package is not loaded, we use register arithmetic, percentages are truncated to integers.

```
2286         \csarg\ifx{FPdiv}\relax  
2287         \count2=\tot@lForPart{#1}%  
2288         \edef\expGT{\csname eqeGrandTotal\endcsname} %  
2289         \multiply\count2by100\relax\divide\count2by\expGT\relax  
2290         \csarg\xdef{#1percent}{\the\count2 }\else
```

If the `fp` package is loaded, we use this package to calculate the percentage, accurate to one decimal place.

```
2291         \FPdiv{\eqe@pForPart}{\csname#1total\endcsname}{%  
2292             \csname eqeGrandTotal\endcsname}%  
2293             \FPMul{\eqe@pForPart}{\eqe@pForPart}{100} %  
2294             \FPround{\eqe@pForPart}{\eqe@pForPart}{\nPctDecPts} %  
2295             \csarg\xdef{#1percent}{\eqe@pForPart}\fi  
2296         }%  
2297 }  
  
2298 \def\writetotalstoaux{\eqe@IWO\@auxout{\string  
2299             \csarg\string\gdef{\thisexamlabel total}{\theeqpointvalue}}%  
2300     \eqe@IWO\@auxout{\string\csarg  
2301             \string\gdef{\thisexamlabel nQuestions}{\theeqquestionno}}%  
2302 }  
2303 \newcommand{\writelastpage}[1][]{\def\eqe@argi{#1}}%  
2304     \ifx\eqe@argi\empty\else\label{#1PageEnd}\fi  
2305     \eqe@IWO\@auxout{\string\csarg  
2306             \string\gdef{eqExamLastPage}{\arabic{page}}}}%
```

```

2307 }
2308 \def\exlabel{}
2309 \def\sqlabel{}
2310 \def\exsolafter{\textit{Solution}:}
2311 \def\sqsolafter{\textit{Solution}:}

The exercise labels in the body of the text. (2015/02/27) changed the command
\exlabelformatwp to incorporate other parameters.

2312 \%def\exlabelformat{\textbf{\theeqquestionnoi.\ }}}
2313 \def\exlabelformat{\textbf{%
2314   \theeqquestionnoi\eqe@decPointPrb\eqe@hspannerPrb}}
2315 \def\exlabelformatwp{\exlabelformat}

The exercise labels for solutions at the end of the document

2316 \def\exsllabelformat
2317   {\string\makebox[0pt][r]{\string\textbf{%
2318     \theeqquestionnoi\eqe@decPointPrb\eqe@hspannerSoln}}}
2319 \def\exsllabelformatwp
2320   {\string\makebox[0pt][r]{\string\textbf{%
2321     \theeqquestionnoi\eqe@decPointPrb\eqe@hspannerSoln}}%
2322     (\thepartno)\eqe@hspannerSoln}
2323 \ifanswerkey
2324   \def\exrtnlabelformat{}
2325   \def\exrtnlabelformatwp{}
2326   \def\eq@sqslrtnlabel{}
2327 \else
2328   \def\exrtnlabelformat{$\square$}
2329   \def\exrtnlabelformatwp{$\square$}
2330   \def\eq@sqslrtnlabel{$\square$}
2331 \fi
2332 \def\sqslrtnlabel{\eq@sqslrtnlabel}

(2010/08/21) Enable some localizations of strings

2333 \newcommand{\exsectitletext}{Solutions to \webtitle}
2334 \def\exsectitle{\normalsize\exsectitletext}
2335 \%def\exsectitle{\normalsize\hspace*%
2336 % {-\oddsidemargin}\exsectitletext}
2337 \ifpackageloaded{exerquiz}{{\Solutions to \websubject}}
2338   \renewcommand{\exsecrunhead}{}{\newcommand{\exsecrunhead}{}}
2339 \%providecommand{\exsecrunhead}{Solutions to \websubject}%
2340 \def\eq@sqslsectitle{}
2341 \def\eq@sqslsecrunhead{}
2342 \def\eq@sqsllabel{{\string\llap{\string\textbf{\theeqquestionnoi.\ }}}}
2343 \def\eq@sqlabel{}
2344 \let\include@quizsolutions\relax
2345 \let\solnhspace\empty

```

### 13.8 problem Environments

A single question is posed with the `problem` environment, and a question with multiple parts with the `problem*` environment.

**\fillin** This macro is used for fill-in type questions. The first argument is the length of the underline blank to leave to fill-in, the second argument is the correct answer.

```

2346 \newcommand{\optsFillIn}[1]{\def\eqe@optsFillIn{#1}}
2347 \let\eqe@optsFillIn\empty
2348 \newcommand{\fillin}[3][u]{%
2349     \ifx#1u\let\@fillinFmt\underbar
2350     \else\ifx#1b\let\@fillinFmt\relax
2351     \else\let\@fillinFmt\relax\fi\fi
2352     \ifeq@proofing
2353         \@fillinFmt{\makebox[#2]{%
2354             \strut\hfil\bfseries\color{red}\#3\hfil}}%
2355     \else
2356         \@fillinFmt{\makebox[#2]{\strut\hfil}}%
2357         \cifundefined{@quiz}{}{%
2358             \if\eq@online\eqe@YES\relax
2359                 \ifeq@nosolutions
2360                     \ifeq@solutionsafter\else
2361                         \ifx\eq@insertverticalspace\eqe@YES\relax
2362                             \stepcounter{@cntfillin}%
2363                             \edef\fieldName{%
2364                                 \if\probstar*\eqexam.\curr@quiz.fillin.%
2365                                     \theeqquestionnoi.part\thepartno.%
2366                                     fi\the@cntfillin%
2367                                 \else
2368                                     eqexam.\curr@quiz.fillin.%
2369                                     \theeqquestionnoi.fi\the@cntfillin%
2370                                 \fi
2371                             }\makebox[0pt][r]{\textField[\BC{}]
2372                                 \presets{\eqe@optsFillIn}}{%
2373                                     \(fieldName){#2}{11bp}}%
2374                             \fi
2375                         \fi
2376                     \fi
2377                 \fi
2378             }%
2379         \fi\space\ignorespaces}

```

**\TF** A specialized version of \fillin for True/False questions.

```

2380 \newcommand\defaultTFwidth{30pt}
2381 \newcommand\TF[2][\defaultTFwidth]{%
2382     \def\eqe@next{\fillin{#1}{#2}}%
2383     \ifdim\eq@extralabelsep=0pt\relax\else
2384         \if\probstar*\relax\if\exerwparts@cols0
2385             \def\eqe@next{\makebox[0pt][r]{%
2386                 \fillin{#1}{#2}}\ignorespaces}%
2387         \fi\fi\fi
2388     \eqe@next}
2389 \def\fillinWidth#1{%
2390     \if\probstar*

```

```

2391      \settowidth{\eq@tmpLengthA}{\normalfont\ }%
2392      \addtolength{\eq@tmpLengthA}{#1}%
2393      \edef\eq@extraLabelsep{\the\eq@tmpLengthA}%
2394  \fi
2395 }
2396 \let\fillInFormatDefault\empty

```

\Do<num> The following commands supports the optional argument \Do<num>. When I teach senior or graduate-level classes, I often give a problem with multiple parts (each of equal value) and ask them to “do 3 of the following 5” parts.

```

2397 \def\eqe@DoWarning#1{\PackageWarning{eqexam}{\string#1\space
2398   requires the first argument\MessageBreak of problem* to be <num>ea}}
2399 \def\eqe@DoNum{\textbf{??}\eqe@DoWarning{\DoNum}}
2400 \def\eqe@nDoNum{\textbf{??}\eqe@DoWarning{\nDoNum}}
2401 \let\DoNum\eqe@DoNum
2402 \let\nDoNum\eqe@nDoNum
2403 \def\makeDoNum#1{\xdef\nDoNum{#1}%
2404   \def\ifc@sewrep{\ifcase#1?\or}%
2405   \xdef\DoNum{\expandafter\ifc@sewrep\eqe@wordNums\else
2406     \eqe@wordNumsError\fi}%
2407 \def\makeOutOfNum#1{\xdef\nOutOfNum{#1}%
2408   \def\ifc@sewrep{\ifcase#1?\or}%
2409   \xdef\OutOfNum{\expandafter\ifc@sewrep\eqe@wordNums\else
2410     \eqe@wordNumsError\fi}%
2411 \def\eqe@OutOfNum{\textbf{??}\eqe@DoWarning{\OutOfNum}}
2412 \def\eqe@nOutOfNum{\textbf{??}\eqe@DoWarning{\nOutOfNum}}
2413 \let\OutOfNum\eqe@OutOfNum
2414 \let\nOutOfNum\eqe@nOutOfNum

```

\eqe@wordNums is used to typeset the English word for the numbers (1–10). This command may be redefined to other languages.

```

2415 \newcommand{\eqe@wordNums}{one\or two\or three\or
2416   four\or five\or six\or seven\or eight\or nine\or ten}
2417 \newcommand{\eqe@wordNumsError}{\noexpand\PackageError{eqexam}%
2418   {Number out of range, 1–10}%
2419   {Use a smaller number, or redefine the command
2420     \string\eqe@wordNums.}}

```

Added two hooks \priorPNPAction and \postPNPAction to \makeRoomForProb to allow some defined actions before and after a page break generated by \makeRoomForProb. Examples of usage are found in \vspaceFillerLines and \eq@linesXPGs.

```

2421 \let\priorPNPAction\relax % dps1
2422 \let\postPNPAction\relax
2423 \def\eqe@mkRoomPgBrk{\priorPNPAction\newpage\postPNPAction}
2424 \def\makeRoomForProb#1#2{\par %\endgraf % dps 11/11/10
2425   \bgroup\nobreakfalse\addpenalty{-500}%
2426   \setlength{\tempdimb}{#1}%
2427   \tempdima \pagegoal \advance \tempdima -\pagetotal

```

```

2428     \ifdim \@tempdima<\@tempdimb\ifnum\col@number>\@ne\columnbreak
2429         \else\aftergroup\eqe@mkRoomPgBrk\fi\fi\egroup
2430     \ifnum@\reportpoints>1
2431         \ifx\eqe@prevProbZero\eqe@YES
2432             \if\eqe@isPts0\else\vskip-\halfHtPtBox\relax\fi
2433         \else
2434             \ifl@stDispl@yPoints
2435                 \if\eqe@isPts0\@checkSpacing{1}\else
2436                     \if#21\@checkSpacing{0}\fi
2437                 \fi\fi
2438             \fi
2439         \fi
2440     }

```

\emitMessageNearBottom The syntax for this command is

```
\emitMessageNearBottom*[vspace]{msg}
```

If there is less than `vspace` remaining on the page, a message, `msg`, is emitted. Then the optional `*` appears, a `\newpage` is also emitted just after the `msg` and `\insertContAnnot` is expanded just after `\newpage`.

```

2441 \newcommand{\emitMessageNearBottom}{\ifstar
2442     {\def\eqe@emnb{\ifnum\col@number>\@ne\columnbreak
2443         \else\newpage\fi\insertContAnnot}\eq@emitMessageNearBottom}
2444     {\let\eqe@emnb\relax\eq@emitMessageNearBottom}}
2445 \newcommand{\eq@emitMessageNearBottom}[2][2\wlVspace]{%
2446     \eq@emitMessageNearBottom{#1}{#2}}
2447 \def\eq@emitMessageNearBottom#1#2{\par
2448     \bgroup\nobreakfalse\addpenalty{-500}%
2449     \setlength{\@tempdimb}{#1}%
2450     \atempdima \pagegoal \advance \atempdima -\pagetotal
2451     \ifdim \atempdima<\@tempdimb #2 \eqe@emnb
2452     \xdef\eq@currProbStartPage{0}\fi\egroup} % dps4

```

\getSpaceLeftOnPage \getSpaceLeftOnPage calculates the amount of space left on the current page. It \amtSpaceLeftOnPage saves the calculation in the text macro \amtSpaceLeftOnPage.

```

2453 \newcommand{\getSpaceLeftOnPage}{\par\bgroup
2454     \atempdima \pagegoal \advance \atempdima -\pagetotal
2455     \xdef\amtSpaceLeftOnPage{\the\atempdima}\egroup}

```

\promoteNewPage A simple variation on \makeRoomForProb designed for user use.

```

2456 \newcommand{\pnpDfl}[1]{\@fvsizeskip\textheight}
2457 \newcommand{\promoteNewPage}[1]{\pnpDfl{#1}}
2458     \makeRoomForProb{#1}{0}

```

\pointsmarginparpush Used in \makeRoomForProb and elsewhere. \pointsmarginparpush adds a little more separation between point boxes. \checkSpacing is the algorithm for adjusting the vertical spaces between problems when points are on the right.

```
2459 \def\pointsmarginparpush{3pt}
```

```

2460 \def\@checkSpacing#1{\bgroup\ifinner\else
2461     \tempdima\lastPageTotal
2462     \tempdimb\pagetotal
2463     If \lastPageTotal is less than \pagetotal, continue
2464     \ifdim\tempdima < \tempdimb
2465         Compute \pagetotal - \lastPageTotal
2466         \advance\tempdimb by-\tempdima
2467         \ifdim\tempdimb < \eq@pointboxtotalheight
2468             \if#11%
2469                 \eq@pointboxtotalheight\halfHtPtBox\relax
2470                 \advance\eq@pointboxtotalheight\dpPtBox\relax
2471             \tempdima=\eq@pointboxtotalheight
2472             \advance\tempdima\pointsmarginparpush\relax
2473             \advance\tempdima by-\tempdimb
2474             \vspace*{\tempdima}%
2475         \fi
2476     \egroup}
2477 \def\@checkSpacingi{\bgroup
2478     \tempdima = \lastPageTotal
2479     \tempdimb = \pagetotal
2480     \ifdim\tempdima < \tempdimb
2481         \advance\tempdimb by-\tempdima
2482         \eq@pointboxtotalheight\halfHtPtBox\relax
2483         \advance\eq@pointboxtotalheight\dpPtBox\relax
2484         \ifdim\tempdimb < \eq@pointboxtotalheight
2485             \tempdima=\eq@pointboxtotalheight
2486             \advance\tempdima\pointsmarginparpush\relax
2487             \advance\tempdima by-\tempdimb
2488             \vspace*{\tempdima}%
2489         \fi
2490     \fi
2491 \egroup}
2492 \newcommand{\setDefaultnbaselineskip}[1]{\def\defaultnbaselineskip{#1}}
2493 \setDefaultnbaselineskip{6}
2494 \def\nbaselineskip#1{\def\nbaselineskip{#1}}
2495 \def\nbaselineskipReset{\edef\nbaselineskip{\defaultnbaselineskip}}
2496 \nbaselineskipReset

problem The problem is used to pose a single—non-multi-part—question. The optional argument is the number of points for this problem.
2497 \def\eqe@gobbletoend#1\end{}
2498 \def\eqe@grabarg#1\end{\def\numpoints{#1}}
2499 \def\eqe@isPts{1}

```

We reset some exerquiz parameters for eqexam

```
2500 \aboveexskip{3pt}\belowexskip{3pt}
2501 \partstopsep{3pt}\partsitemsep{3pt}\partsparsep{0pt}
2502 \rowsepDefault{3pt}\partstabcolsep{1.5pt}%
2503 \partstabtopsep{3pt}\partstabrowsep{3pt}
2504 \renewcommand\belowexsolnskip{\relax}%
2505 \let\isProbEnv\eqe@NO
2506 \let\topofprobhook\relax
```

Normally, you don't leave a blank line between the beginning of `problem` and the statement of problem. If you're in the habit of doing that, we can absorb that blank space. See similar command above the definition of `problem*` for more information.

```
2507 \def\eqe@p@gobnxtp@rDef{\ifnextchar{p}{\gobtop@rnext}{}}
2508 \def\eqe@p@gobtop@rnext#1{\par{}}
2509 \def\applyparfixesp{\let\eqe@p@gobnxtp@r\eqe@p@gobnxtp@rDef}
2510 %\def\cancelparfixesp{\let\eqe@p@gobnxtp@r\relax}
2511 \def\cancelparfixesp{\let\eqe@p@gobnxtp@r\ignorespaces}
```

The `problem` environment now begins.

```
2512 \newcommand{\problem}[1][]{\lowercase{\def\@rgi{#1}}%
```

Support for h and H argument when it is the first argument.

```
2513 \ifx\@rgi\eqe@h
2514   \def\hidden@ttr[#1]{\let\numpoints\empty\else
2515   \let\hidden@ttr\relax\def\numpoints{#1}\fi
2516 \problem@cont}
2517 \newcommand{\problem@cont}[1][]{\let\isProbEnv\eqe@YES
2518 \def\@rgi{#1}\ifx\hidden@ttr\relax % assume a number or empty
2519   \ifx\@rgi\empty\else\def\hidden@ttr{#1}\fi\fi
2520   \if\eqe@isPts0\global\let\eqe@prevProbZero\eqe@YES\else
2521     \global\let\eqe@prevProbZero\eqe@NO\fi
2522   \global\thereissolutionfalse
2523   \def\numpointsEmpty{0}%
2524   \ifx\numpoints\empty\def\numpoints{0}\def\numpointsEmpty{1}%
2525     \gdef\eqe@isPts0\else\gdef\eqe@isPts1\fi
2526   \makeRoomForProb{\nobaselineskip\baselineskip}{\eqe@isPts}%
2527   \gdef\probstar{x}\let\afterlabelhskip\empty
2528   \ifx\marginpoints\empty\else
2529     \if\numpointsEmpty\eqe@One\let\marginpoints\gobbletwo\fi
```

(2011/5/13) We add a \* feature. When the author types [\*3], it is a three point problem, but the value is expressed in-line, not in the margins.

```
2530   \def\@lti{\let\@isitstar\eqe@One\eqe@grabarg}%
2531   \def\@ltii{\let\@isitstar\eqe@Zero\eqe@gobbletoend}%
2532   \expandafter\@ifstar\expandafter\@lti
2533   \expandafter\@ltii\numpoints\end
2534   \if\@isitstar\eqe@One\addtocounter{eqpointvalue}{\numpoints}%
2535     \marktotalvalue
2536     \ifdispl@yPoints
2537       \def\marginparafterhook{\PTs{\numpoints}\space}\else
```

```

2538      \def\marginparafterhook{\PTs*\{\numpoints\}\space}\fi\else
2539      \def\marginparpriorhook{\noindent
2540          \probvalue{\numpoints}{0}}\fi
2541  \fi
2542  \setcounter{eq@count}{\value{eqquestionnoi}}%
2543  \addtocounter{eq@count}{1}%
2544  \ifnum\value{eq@count}=1\relax
2545      \eqe@IWO@auxout{\string
2546          \csarg\string\gdef\pagenofirstprob{thisexamlabel}{\thepage}}%
2547  \fi

```

\topofprobhook is a general purpose hook at the top of the problem environment, before the beginning of the nested eqquestions environment.

```

2548  \topofprobhook
2549  \begin{eqquestions}%

```

**Begin exercise env.** Insert h or H when it is the first argument through \hidden@ttr, then begin the exercise environment using eqquestionnoi.

```

2550  \edef\ctrld@exp@exercise{\noexpand
2551      \begin{exercise}[eqquestionnoi]\hidden@ttr}%
2552  \ctrld@exp@exercise\ignorespaces\eqe@p@gobnxt@r}

```

**end problem env.** The code for the end of the problem environment.

```

2553 \def\endproblem{\end{exercise}%
2554  \end{eqquestions}%
2555  \ifeqllocalversion\ifeqglobalversion
2556      \xdef\eqe@tmp{\noexpand\forVersion{\eq@selectedVersion}}%
2557      \aftergroup\eqe@tmp
2558  \fi\fi
2559  \global\eqlocalversionfalse
2560  \ifdispl@yPoints\global\l@stDispl@yPointstrue
2561  \else\global\l@stDispl@yPointsfals\fi
2562  \global\let\eqe@fpmrk\empty}

```

**\PTs** When you specify \auto for the optional argument of the problem\* environment, **\itemPTsTxt** when each item must have the command \PTs to assign the value of that question. **\itemPTsFormated** The \PTs has one optional star-parameter, and one required parameter. The required parameter is the number of points for this item, if the \* is specified, then the point value is not typeset in the document.

The command \itemPTsTxt has one argument, the number of points for this item. This argument is passed from the \PTs command. You can redefine the way the points appear in the document using \itemPTsTxt. As separate command \itemPTsFormated is used to put parentheses around \itemPTsTxt. If the \* option is taken with \PTs, then you are free to place \itemPTsTxt anywhere in the problem statement.

```

2563 \newcommand\itemPTsTxt[1]{\$\\eqe@ptsFmt{\#1}\\,\\text{%
2564     \\ifnum#1=1\\relax\\eqptLabel\\else\\eqptsLabel\\fi\$}%
2565 \newcommand\itemPTsEaTxt[1]{\$\\eqe@ptsFmt{\#1}\\,\\text{%
2566     \\ifnum#1=1\\relax\\eqptLabel\\else\\eqptsLabel\\fi\\space\\eqeachLabel\$}%
2567 \newcommand{\itemPTsFormated}[1]{(\#1)}

```

\obeyPTsStar (2013/12/04) Added \obeyPTsStar and \ignorePTsStar. The former is the default. if \ignorePTsStar is in effect, \PTs\* is treated as \PTs. Useful for assigning points to parts of a question, but not explicitly telling the student. when you compile for the key (with answerkey option), you can include \ignorePTsStar so the instructor can see the assigned points for each part.

```

2568 \newif\ifObeyPTsStar \ObeyPTsStartrue
2569 \def\obeyPTsStar{\global\ObeyPTsStartrue}
2570 \def\ignorePTsStar{\global\ObeyPTsStarfalse}
2571 \def\PTs{\leavevmode@ifstar{\@PTs{*}}{\@PTs{x}}}
2572 \def\@PTs#1#2{%
2573   \if\@reportpoints\eqe@Zero\ignorespaces\else
2574     \if\eqe@pointsPartsId\eqe@One
2575       \addtocounter{eqpointvalue}{#2}\@marktotalvalue
2576     \addtocounter{eq@count}{#2}\fi

```

\ignorePTsStar If \ignorePTsStar is in effect (\ObeyPTsStarfalse), we gobble the \else and let the code flow through.

```

2577   \if#1*\ifObeyPTsStar\ignorespaces\else\expandafter\@gobble\fi
2578   \else

```

(2012/04/26) Wrapped \itemPTsFormated{\itemPTsTxt{#2}} as the argument of \eqe@movePTs. \eqe@movePTs does nothing by default, but may be redefined, for example, to place the value of each part on the margin. The default definition of \eqe@movePTs follows.

```

2579   \eqe@movePTs{\itemPTsFormated{\itemPTsTxt{#2}}}\fi
2580   \fi
2581 }
2582 \def\eqe@movePTs#1{#1}

```

\Do<num> The \isItD@ tests to see if the next token is \Do, if yes, it marks it and calls \y@st@Do, which gets the argument of the \Do token.

```

2583 \let\auto\relax
2584 \def\isItD@{\@ifnextchar\Do{\let\yest@D@\eqe@YES\y@st@Do}%
2585   {\let\yest@D@\eqe@NO\@gobble@end}}
2586 \let\yest@D@\eqe@NO
2587 \let\D@Num\@empty
2588 \def\y@st@Do\Do#1\end{\gdef\D@Num{#1}}
2589 \def\@gobble@end#1\end{}}

```

Test the argument to see if it is the \auto token

```

2590 \def\is@uto#1\auto#2\@nil{\def\eqe@argi{#1}\def\eqe@argii{#2}%
2591   \ifx\eqe@argi\@empty\let\isit@uto\eqe@Zero\else
2592     \let\isit@uto\eqe@One\fi
2593 }

```

**problem\*** The **problem\*** environment is used to pose a multi-part question. The **parts** environment is used to enumerate the parts.

We create a Id for the points specified by the first (and second) optional parameters: 0 (total points specified); 1 (\auto specified); 2 (points each specified); 4

(\Do second optional parameter); a value of \relax means no points specified (the default).

```

2594 \let\eqe@pointsPartsId\relax
2595 \def\leadinitemWarningStar{\PackageWarning{eqexam}
2596   {Using the star (*) in front of the points\MessageBreak
2597    designator is not allowed when there is a
2598    \MessageBreak/string\leadinitem}}
2599 \def\tableadinWarningStar{\PackageWarning{eqexam}
2600   {Using the star (*) in front of the points\MessageBreak
2601    designator is not allowed when there is a
2602    \MessageBreak/string\tableadin}}
2603 \let\isProbStarEnv\eqe@NO
2604 \let\topofprobstarhook\relax

```

Added \eqe@gobnxtpar to hopefully, eliminate the need to leave no pars (blank lines) between \begin{parblem\*} and either \leadinitem or \tableadin. The default is to not affect the old behavior. You have to declare \applyparfixes to apply the fix; revert back to the old behavior with \cancelparfixes

```

2605 \def\eqe@ps@gobtop@r#1\par{\eqe@isle@dinnext}
2606 \def\eqe@isle@dinnext{\@ifnextchar\leadinitem{}{\vskip-\baselineskip}}
2607 \def\restorele@dinpfixDef{\@ifnextchar\par{\eqe@ps@gobtop@r}{}}
2608 \let\eqe@ps@gobnxtpar\restorele@dinpfixDef
2609 \def\applyleadinfix{\let\eqe@gobnxtpar\restorele@dinpfixDef}
2610 \def\cancelleadinfix{\let\eqe@gobnxtpar\relax}
2611 \def\applyparfixes{\PackageInfo{eqexam}
2612   {Applying paragraph fixes to problem\MessageBreak
2613    and problem* environments}\applyparfixesp\applyleadinfix}
2614 \def\cancelparfixes{\PackageInfo{eqexam}
2615   {Cancelling paragraph fixes to problem\MessageBreak
2616    and problem* environments}\cancelparfixesp
2617 \cancelleadinfix}

```

The default behavior is to do nothing about blank lines.

```

2618 \cancelparfixesp\cancelleadinfix
2619 \let\neutralizeparfixes\cancelparfixes

```

We now begin the code for the problem\* environment.

```

2620 \csarg\def{problem*}{\let\isProbEnv\eqe@YES
2621   \let\isProbStarEnv\eqe@YES
2622   \global\thereissolutionfalse
2623   \@ifnextchar[{\pr@bl@m@star}{\pr@bl@m@star[]}}
2624 \def\pr@bl@m@star[#1]{%
2625   \@ifnextchar[{\pr@blem@star[#1]}{\pr@blem@star[#1][]}}
2626 \def\pr@blem@star[#2]{%
2627   \if\eqe@isPts0\global\let\eqe@prevProbZero\eqe@YES\else
2628     \global\let\eqe@prevProbZero\eqe@NO\fi
2629   \def\numpoints{\#1}\ifx\numpoints\empty
2630     \gdef\eqe@isPts{0}\else\gdef\eqe@isPts{1}\fi
2631   \makeRoomForProb{\@baselineskip\baselineskip}\eqe@isPts%

```

Let the \Do commands to internal versions

```
2632      \let\DoNum\eqe@DoNum\let\nDoNum\eqe@nDoNum
2633      \let\OutOfNum\eqe@OutOfNum\let\nOutOfNum\eqe@nOutOfNum
2634 %     \proofingsymbol{\ding{52}}%
2635     \gdef\probstar{*}%
2636     \gdef\pr@b@secondarg{\#2}\setcounter{eq@count}{0}%
2637     \let\afterlabelhskip\empty
2638     \global\let\probpointsearch\empty\def\numpoints{\#1}%
```

Determine if the argument begins with \*

```
2639     \@ifstar{\let@isitstar\eqe@One\eqe@grabarg}%
2640         {\let@isitstar\eqe@Zero\eqe@gobbletoend}#1\end
```

If this **problem\*** environment has a \leadinitem, the \* option is not allowed

```
2641     \if@isitstar\eqe@One
2642         \@tempcnta=\theeqquestionno\relax
2643         \advance@\tempcnta\relax
2644         \@ifundefined{leadinitem}{\thisexamlabel-\the@\tempcnta}{}%
2645             {\leadinitemWarningStar\let@isitstar\eqe@Zero}%
2646         \@ifundefined{tableadin}{\thisexamlabel-\the@\tempcnta}{}%
2647             {\tableadinWarningStar\let@isitstar\eqe@Zero}%
2648     \fi
```

Check for the \auto keyword . There are problems when the first two digits are the same, the old comparison would say that the first parameter is \auto, which is it not. Replace the old comparison with a more robust method.

```
2649     \expandafter\is@uto\numpoints\auto@nil
2650     \if\is@uto\eqe@One\let\eqe@pointsPartsId\eqe@One
2651         \global\let\probpointsearch\relax
```

The author has requested \auto

```
2652     \def\eqe@next{\autocalcparts}%
2653     \else
2654         \ifx\pr@b@secondarg\empty\else
2655             \let\eqe@pointsPartsId\eqe@Four
2656             \isItD@#2\end\fi
```

Not \auto so either <num>ea or <num>

```
2657     \def\eqe@next{\manualcalcparts{\numpoints}}%
2658     \fi\eqe@next
```

2012/11/30 added \leadinitem defined **eqexam.def** as a dummy command, which we the \let here to \eqe@leadinitem.

```
2659     \let\leadinitem\eqe@leadinitem
```

2015/05/31 added \tableadin defined **eqexam.def** as a dummy command, which we the \let here to \eqe@tableadin.

```
2660     \let\tableadin\eqe@tableadin
```

\topofprobstarhook is a general purpose hook at the top of the **problem\*** environment, before the beginning of the nested **eqquestions** environment.

```

2661      \topofprobstarhook
2662      \ifeqfortextbook
2663      \writeT@SolnFile{\protect\global
2664          \protect\frstProbNumShownfalse}\fi
2665      \begin{eqquestions}%
2666      \begin{exercise}[eqquestionnoi]*\eqe@gobnxtpar}%
2667 \def\ftb@endprobstarCks{%
2668     \ifWithinANSGrp
2669         \PackageError{eqexam}{\string\bGrpANS\space is still open}
2670         {You need to match it with an \string\bGrpANS,
2671          or remove it.}%
2672     \fi
2673 }

```

\endproblem\* begins here.

```

2674 \csarg\def\endproblem*{%
2675     \eqe@IWO\auxout{\string\csarg\string
2676         \gdef{nPartsThisProb\thisexamlabel.\theeqquestionnoi}%
2677         {\arabic{partno}}}%
2678     \ifx\probpointseach\empty\else
2679     \ifx\probpointseach\auto
2680         \eqe@IWO\auxout{\string\csarg\string
2681             \gdef{prob\thisexamlabel.\theeqquestionnoi}%
2682             {\theeq@count}}%
2683     \else
2684         \setcounter{eq@count}{\value{partno}}%
2685         \ifx\pr@b@secondarg\empty\else
2686             \bgroup\toks0=\expandafter\{\pr@b@secondarg}%
2687             \expandafter\isItD@\the\toks0 \end

```

If there is a \Do, we write this info to AUX.

```

2688     \ifx\yest@D@\eqe@YES\ifx\eqe@pointsEach\eqe@YES
2689         \eqe@IWO\auxout{\string
2690             \csarg\string\gdef{DoNumThisProb\thisexamlabel.%%
2691             \theeqquestionnoi}{\D@Num}}%
2692             \tempcnda = \value{eq@count}%
2693             \advance\tempcnda -\D@Num
2694             \global\advance\value{eq@count}-\tempcnda
2695 % 3.0k
2696             \tempcnda=\value{partno}%
2697             \advance\tempcnda -\D@Num
2698             \multiply\tempcnda by\argi
2699             \addtocounter{eqpointvalue}{-\tempcnda}%
2700             \fi\fi
2701             \egroup
2702         \fi
2703         \multiply\value{eq@count}\argi
2704         \eqe@IWO\auxout{\string\csarg\string
2705             \gdef{prob\thisexamlabel.\theeqquestionnoi}{\theeq@count}}%
2706 \fi\fi

```

```

2707   \end{exercise}%
2708   \end{eqequestions}%
2709   \ifeqfortextbook\ftb@endprobstarCks\fi
2710   \ifeqlocalversion\ifeqglobalversion
2711     \xdef\eqe@tmp{\noexpand\forVersion{\eq@selectedVersion}}%
2712     \aftergroup\eqe@tmp
2713   \fi\fi
2714   \global\eqlocalversionfalse

2715   \@marktotalvalue
2716   \ifdispl@yPoints\global\l@stDispl@yPointstrue
2717   \else\global\l@stDispl@yPointsfals\fi
2718 }

```

\leadinitem Some authors, no me among them, want to post a question with parts (**problem\***) without an introductory sentence. Scandalous!

```

\begin{problem*}\relax
\leadinitem Prove that  $4x^2 \geq (x+1)^2$  for  $x \geq 1$ .
\begin{solution} soln\end{solution}
\begin{parts}
\item Use the principle of mathematical induction to prove that
 $4^n \geq 3n^2$  for all positive integers  $n$ .
\begin{solution} soln\end{solution}
\end{parts}
\end{problem*}

```

Below is my solution to this problem. There were changes in both **eqexam** and **exerquiz** (**eqexam.def**). Here are the listing of changes for my future reference.

- Defined **\eqe@leadinitem**, **\eqe@@leadinitem**, and **\leadinitem** below. The first one mostly tests whether we are permitted to use the **\leadinitem** command. If **\solutionparshape** is empty, the command may be used. (This gives a restriction of only one use per a single **problem\*** environment.) Control is passed to **\eqe@leadinitem** which does all the work.
- In the definition of **\pr@blem@star** (part of the startup for **problem\*** we say **\let\leadinitem=\eqe@leadinitem**
- In the startup code for **exercise@parts@list** (**exerquiz**) lines containing **\solutionparshape** and **\let\leadinitem\eq@leaditemparts** are found. Also, when the **parts** environment is complete, we restore the default definition of **\leadinitem**, **\let\leadinitem\leadinitem@external**.
- In the definition of **\eqe@@leadinitem**, we also define **\solutionparshape** to help control the paragraphs for this delicate problem of a lead-in item. Its normal definition is **\@empty**, and this fact used to detect whether the document author is trying to use two **\leadinitem**s in one **problem\*** environment.

- At the beginning of the definition of the command `\@exercise` (in `exerquiz` we `\let \solutionparshape` to `\@empty`.
- So too does `\solutionparshape` appear in the definition of `\vspaceFmt` (`exerquiz`).
- `\solutionparshape` is used to correctly format in the `solutionsafter`, found in `\solnexe@@@woparts` (`exerquiz`).

As can be seen, this simple feature is not so simple.

Set the default value of `\solutionparshape`.

```
2719 \let\solutionparshape\@empty
```

`\leadinitem` This is the beginning of `\leadinitem`, at least the active definition within the `problem*` environment, and outside the `parts` environment.

```
2720 \def\eqe@leadinitem{%
2721     \ifx\solutionparshape\@empty
```

`\solutionparshape` empty means `\leadinitem` hasn't been used yet, so we can use it here by passing control to `\eqe@@leadinitem`, otherwise, we toss an exception.

```
2722     \def\eqe@next{\eqe@@leadinitem}%
2723         \ifeqfor{textbook}\writeT@SolnFile{\protect\bpartsmrk}\fi
2724     \else
2725         \def\eqe@next{\PackageError{eqexam}%
2726             {The \string\leadinitem\space command may
2727             only be used\MessageBreak once per problem* environment}
2728             {Remove all but one of the \string\leadinitem\space
2729             commands.}}%
2730     \fi\eqe@next
2731 }
2732 \newif\ifisleadin \isleadinfalse
2733 \let\isparshapeExpanded\eqe@NO
2734 \def\eqe@@leadinitem{\if\itsforleadinitem\eqe@NO
2735     \setcounter{partno}{0}\fi\refstepcounter{partno}}%
```

After initializing the counter, we make various calculations

```
2736     \eq@initializeContAnnot
2737     \isleadintrue\let\isitleadin\eqe@YES
```

We signal a `\leadinitem` by writing a special command to the AUX file, this is used to disallow the use of the `*` option of points.

```
2738     \eqe@writetoAux{\string\csarg\string
2739         \gdef\leadinitem\thisexamlabel-\theeqquestionno{}{}%
2740         \settowidth{\eq@tmpdima}{\normalfont\parts@indent\eqe@prtsepPrb}%
2741         \xdef\leadinIndentPrtSep{\the\eq@tmpdima}%
2742         \setlength{\eq@tmpdima}{\eqemargin+\eq@tmpdima}%
2743         \xdef\leadinIndent{\the\eq@tmpdima}%
2744         \settowidth{\eq@tmpLength}{\parts@indent}%
2745         \edef\partsleadinIndent{\the\eq@tmpLength}%
```

```

2746      \setlength{\eq@tmpLength}{\linewidth-\leadinIndentPrtSep}%
2747      \edef\leadinIndentLength{\the\eq@tmpLength}%

```

Modify `\@listii` from core LaTeX: Increase `\leftmarginii` and `\ linewidth` appropriately.

```

2748 \@ifundefined{@listii@SAVE}{\global\let@listii@SAVE\@listii}{}%
2749     \expandafter\def\expandafter\expandafter{\@listii@SAVE
2750     \advance\leftmarginii\leadinIndentPrtSep\relax
2751     \leftmargin\leftmarginii \labelwidth\leftmarginii
2752     \advance\labelwidth-\labelsep
2753 }%
2754 }%

```

The `parshape` for the first paragraph of the `\leadinitem`.

```

2755     \parshape=2 \eqemargin \linewidth \leadinIndent \leadinIndentLength

```

Here is the definition of `\solutionparshape`, we use the shape of subsequent paragraphs.

```

2756     \xdef\solutionparshape{%\noexpand\linewidth\leadinIndentLength
2757             \noexpand\parshape=1 \leadinIndent\space\leadinIndentLength}%

```

After the current paragraph, we execute `\solutionparshape`, then empty out `\everypar`. Seems to work.

```

2758     \global\let\isparshapeExpanded\eq@NO
2759     \everypar{\solutionparshape
2760             \global\let\isparshapeExpanded\eq@YES\everypar{}}

```

These next lines were taken from `\eq@item@common` in `exerquiz`. The command `\eq@insertContAnnot` was removed from the `\eq@item@common` code, it is not needed here and caused trouble. We `\let \eq@item` to `\eq@leadin@item` to continue the flow. `\@ckhide` checks for an optional argument (`h` or `H`) and sets switches as appropriate.

```

2761     \let\eq@item\eq@leadin@item\eqp@rtc@lcm@rk
2762     \def\currhideopt{x}\eq@hidesolutionfalse\eq@nolinkfalse
2763     \@ifnextchar[{\@ckhide}{\eq@item}%
2764 }

```

The final step. If the solution is hidden, we do not write the header.

```

2765 \def\eq@leadin@item{\eq@ckglobalhide\ifeq@hidesolution\else
2766     \global\let\eqExerSolnHeader\eq@writexheaderlist\fi
2767     \ifeq@nosolutions\eq@nolinktrue\fi
2768     \ifeq@solutionsafter\eq@nolinktrue\fi
2769     \unskip\noindent\makebox[\partsleadinIndent]{\eqexlisttabheader}%
2770     \eqe@prtsepPrb\ignorespaces
2771 }

```

`\tableadin` `\tableadin` is `\let` to `\eqe@tableadin` within the `problem*` env. The switch `\if@tableadinitem` is defined in `exerquiz`.

```

2772 \def\eqe@tableadin{\@tableadinitemtrue\eqe@writetoAux{\protect
2773   \csarg\protect\gdef\tableadin\thisexamlabel-\theeqquestionnoi}{}}
2774 }

```

\pushProblem There may be an occasion when a multi-part question needs to be broken between parts. use the \pushProblem and \popProblem for this purpose. The push saves the counter value, and ends the parts environment. The pop restarts the parts, and resets the parts counter.

In the example below, we have our parts in a `multicols` environment, we \pushProblem, close `multicols`, \popProblem and continue with the multi-parts in single column.

```

\item Compute $\lim_{x\rightarrow 2} \{ \text{$-$}\} f(x)$
\begin{solution}[1in]\end{solution}
\pushProblem
\end{multicols}
\popProblem
\item What value(s) of $c$ make the function $f$ continuous at $x=2$?
\begin{solution}[.5in]\end{solution}
\end{parts}

2775 \newcommand\pushProblem{\xdef\nlastItem{\arabic{partno}}\end{parts}}
(2013/05/30) Adding an optional parameter to \popProblem to match the option argument of the parts environment. This enables you to push a list environment and push a tabular environment.

```

```

2776 \newcommand\popProblem[1][]{%
2777     \def\@argi{\#1}\ifx\@argi\@empty
2778     \def\eqe@bParts{\begin{parts}}\else
2779     \def\eqe@bParts{\begin{parts}[\#1]}\fi
2780     \eqe@bParts\setcounter{partno}{\nlastItem}}

```

```

2781 \def\lastPageTotal{0pt}
2782 \def\marginparafterhook{\xdef\lastPageTotal{\the\pagetotal}}

```

\manualcalcparts is the command calculates points when the argument is *not* \auto. The macro \prob@Arg determines if the points argument passed is of the form <num>ea.

```
2783 \def\prob@Arg#1ea#2\end{\def\argi{\#1}\def\argii{\#2}}
```

Now begin \manualcalcparts; #1 is the number of points, which may be of the form <num>ea, or just <num>.

```

2784 \let\eqe@pointsEach\eqe@NO
2785 \def\manualcalcparts#1{%
2786     \expandafter\prob@Arg#1ea\end
2787     \ifx\argii\@empty\edef\numpoints{\#1}%
2788         \let\eqe@pointsEach\eqe@NO

```

Argument form is <num> assumed: Total points specified, we should ignore any \PTs commands.

```

2789         \let\eqe@pointsPartsId\eqe@Zero
2790     \else

```

Argument form is <num>ea assumed: Again we should ignore any \PTs commands.

```

2791         \gdef\probpointseach{x}\let\eqe@pointsPartsId\eqe@Two
2792         \let\eqe@pointsEach\eqe@YES

```

Points each specified

```
2793      \setcounter{eq@count}{\value{eqquestionnoi}}%
2794      \addtocounter{eq@count}{1}\csarg
2795      \ifx{\prob\thisexamlabel.\theeq@count}\relax
2796          \def\numpoints{\argi}\else
2797          \def\numpoints{\expandafter
2798              \csname prob\thisexamlabel.\theeq@count\endcsname}%
2799      \fi
2800
2801      \ifx\yest@D@\eqe@YES
2802          \setcounter{eq@count}{\value{eqquestionnoi}}%
2803          \addtocounter{eq@count}{1}%
2804          \@ifundefined{nPartsThisProb\thisexamlabel.\theeq@count}
2805              {\makeOutOfNum{0}\makeDoNum{0}}%
2806              \expandafter\makeOutOfNum{%
2807                  \csname nPartsThisProb\thisexamlabel.%\theeq@count\endcsname}%
2808              \expandafter\makeDoNum{%
2809                  \csname DoNumThisProb\thisexamlabel.%\theeq@count\endcsname}%
2810          \fi
2811      \fi
2812  \fi
```

If `\marginpoints` is `\empty`, the author has chosen the `nopoints` option or used the `\NoPoints` command.

```
2813  \ifx\marginpoints\empty
```

No points for this exam

```
2814  \else
2815  \ifx\argi\empty
```

If `\argi` is empty, no points were specified, so we `\let \marginpoints` to `\empty`

```
2816      \let\marginpoints\empty
2817  \else
```

Points are displayed in margins or inline

```
2818  \ifx\argii\empty
```

### Total points specified

```
2819  \ifx\marginpoints\empty\else
2820      \if\@isitstar\eqe@One
```

Points to appear “in-line” rather than in the margins

```
2821          \addtocounter{eqpointvalue}{#1}%
2822          \markttotalvalue\ifdispl@yPoints
2823          \def\marginparafterhook{\itemPTsFormated{%
2824              \itemPTsTxt{\numpoints}\space}\fi
2825      \else
```

Points appear in the margins

```
2826  \def\marginparpriorhook{\noindent}
```

```

2827                               \probvalue{\numpoints}{0}%
2828                         \fi
2829                         \fi
2830                   \else
2831           \ifx\marginpoints\empty\else
2832               \if@isitstar\eqe@One\ifdispl@yPoints
2833                   \def\marginparafterhook{%
2834                       \itemPTsFormated{\itemPTsEaTxt{\argi}}\space}\fi
2835               \else
2836                   \ifdispl@yPoints
2837                       \def\marginparpriorhook{\noindent
2838                           \marginpoints{\numpoints}{\argi}}\fi
2839                   \fi
2840
2841           \edef\eqp@rtc@lcm@rk{\noexpand
2842               \addtocounter{eqpointvalue}{\argi}%
2843               \noexpand\@marktotalvalue}%
2844           \fi
2845           \fi
2846       \fi
2847       \ifnum\value{eq@count}=1\relax
2848           \eqe@IWO\auxout{\string\csarg\string
2849               \gdef\pagenofirstprob{\thisexamlabel}{\thepage}}%
2850       \fi
2851   }

\autocalcparts is the command that computes the total points when the author specifies \auto as the optional argument of problem*. The commands \acp@mpah and \acp@mpph were recently (2012/04/21) separated out to allow for additional customization, without re-defining the whole of \autocalcparts.

2852 \def\acp@mpah{\itemPTsFormated{\itemPTsTxt{\numpoints}}\space}
2853 \def\acp@mpph{\noindent\marginpoints{\numpoints}{0}}
2854 \def\autocalcparts{%
2855     \setcounter{eq@count}{\value{eqquestionno}}%
2856     \addtocounter{eq@count}{1}%
2857     \csarg\ifx{prob}{\thisexamlabel.\theeq@count}\relax
2858         \def\numpoints{0}%
2859     \else
2860         \edef\numpoints{@nameuse{prob}{\thisexamlabel.\theeq@count}}%
2861     \fi
2862 %     \addtocounter{eqpointvalue}{\numpoints}\@marktotalvalue

```

```

2863      \ifx\marginpoints\@empty\else
2864          \ifdispl@yPoints
2865              \if@isitstar\eq@\@One

```

If we have \*\auto, the total is to appear inline.

```

2866          \def\marginparafterhook{\acp@mpah}\else

```

Otherwise, the total will appear in the margin.

```

2867          \def\marginparpriorhook{\acp@mpah}\fi
2868      \fi
2869  \fi
2870  \setcounter{eq@count}{0}%
2871 }

```

\forproblem When typing solutions from assigned problems in a textbook, the problems assigned are not consecutive. You can set the problem number before the problem environments by using the \forproblem command. The one required argument is the problem number: \forproblem{10}.

```

2872 \let\eqe@fpmrk\@empty
2873 \newcommand{\forproblem}[1]{\def\eqe@fpmrk{-\the@exno}%
2874   \setcounter{eqquestionno}{#1 - 1}}

```

A similar comment for \item. These are useful for making out solution sets to homework assignments where problems are assigned from the textbook and you want to give a solution to problem 12, part (b), An example of usage is

```

\forproblem{12}
\begin{problem*}
Factor each.
\begin{parts}
\foritem{b} $ x^2 + 2x + 1 = ( x + 1 )^2 $
\item $ x^2 - x - 2 = ( x - 2 )( x + 1 ) $ % this is part (c)
\foritem{e} $ x^2 + 7x + 10 = ( x - 2 )( x + 7 ) $
\item ... % this will be part (f)
\end{parts}
\end{problem*}

```

```

2875 \newcommand{\foritem}[2][]{%
2876   \setcounter{partno}{0}\def\@rgi{\#1}\ifx\@rgi\@empty
2877     \def\eqe@nextitem{\item}\else
2878     \def\eqe@nextitem{\item[\#1]}\fi
2879   \foritem@cont{\#2}}
2880 \newcommand{\forleadinitem}[2][]{%
2881   \setcounter{partno}{0}\def\@rgi{\#1}\ifx\@rgi\@empty
2882     \def\eqe@nextitem{\leadinitem}\else
2883     \def\eqe@nextitem{\leadinitem[\#1]}\fi
2884   \foritem@cont{\#2}}

```

(2017/01/04) Modified \foritem@cont to allow for numbering parts.

```

2885 \def\foritem@cont{\ifuseNumForParts
2886   \edef\fliPartNo{\#1}\setcounter{partno}{\#1-1}\else
2887   \lowercase{\def\eq@selectedItem{\#1}}%

```

```

2888     \let\eq@initLoop\eq@NO
2889     \loop
2890         \stepcounter{partno}\expandafter
2891         \if\alph{partno}\eq@selectedItem
2892             \let\eq@initLoop\eq@YES\fi
2893         \ifx\eq@initLoop\eq@NO\repeat
2894         \edef\fliPartNo{\the\c@partno}%
2895         \addtocounter{partno}{-1}\fi\let\itsforleaditem\eq@YES
2896         \eq@nextitem

```

The command `\eq@insertContAnnot` attempts to insert a string just prior to a part, if that part begins a new page. To get it right, it promotes a new page using the default of .25in. The optional parameter allows you to insert a new value; this may be needed to get the string `\annotContStr` placed properly. The commands

`\annotContStr` The string that is typeset by the `\eq@insertContAnnot` command.

`\acvspace` User access to changing the vertical spacing `\promoteNewPage` uses within `\eq@insertContAnnot`.

`\resetacvspace` Resets the vertical spacing back to its default.

```

2897 \newcommand{\annotContStr}{%
2898     \textbf{Problem~}\{\eq@currProb\} continued\strut\}
2899 \newcommand{\acvspace}[1]{\def\ic@vspace{\#1}\setlength\iacvspace{\#1}}

```

`\ic@vspacedefault` is the default vertical spacing used by `\eq@insertContAnnot`

```

2900 \newlength\iacvspace
2901 \newcommand{\ic@vspacedefault}{1in} % changed .25in to 1in 2012/12/04
2902 \newcommand{\resetacvspace}{\setlength\iacvspace{\ic@vspacedefault}}
2903 \resetacvspace

```

`\eq@insertContAnnot` promotes a new page, and if the current page is different than the starting page, `\eq@currProbStartPage`, we insert `\annotContStr`.

```

2904 \def\cnotContStrSkip{\vskip3pt}
2905 \newcommand{\eq@insertContAnnot}[1]{\iacvspace\promoteNewPage[\#1]%
2906     \ifnum\arabic{page}>\eq@currProbStartPage
2907         \xdef\eq@currProbStartPage{\arabic{page}}%
2908         {\settowidth{\eq@tmpLength}{\parts@indent\eq@prtsepPrb}}%
2909         \xdef\eq@partsIndent{\the\eq@tmpLength}}%
2910     \ifwithinparts

```

`\eq@item` is the list definition of `\item` which has been `\let` to `\eq@item` within the `parts` environment.

```

2911     \ifundefined{\eq@item@latex}{\item[]\hspace*{-\eqemargin}%
2912         \ifx\solutionparshape\empty\else\hspace*{-\eqe@partsIndent}\fi}%
2913         {\eq@item@latex[]\hspace*{-\eqemargin}%
2914         \hspace*{-\eqe@partsIndent}}\else

```

If placed between problem sets, we indent as appropriate.

```

2915     \hspace*{-\eqemargin}\fi
2916     \annotContStr\cnotContStrSkip % dpsj20
2917 \fi

```

```
2918 }
2919 \edef\eq@currProbStartPage{\arabic{page}}
```

\turnContAnnotOff Turn off and on this feature. The default is off.

```
2920 \newif\ifcont@nnot \cont@nnotfalse
2921 \%newcommand{\gobblloptone}[1] []
2922 \newcommand{\turnContAnnotOff}{\global\cont@nnotfalse
2923     \global\let\eq@insertContAnnot\relax}
2924 \newcommand{\turnContAnnotOn}{\global\cont@nnottrue
2925     \global\let\eq@insertContAnnot\eqe@insertContAnnot}
2926 \turnContAnnotOff
```

Used for manually inserting annot

```
2927 \def\insertContAnnot{\eq@insertContAnnot}
```

\aNewPage A simple command for inserting \newpage, only if the \answerkey option has \qNewPage been taken.

```
2928 \newcommand{\aNewPage}{\ifanswerkey\newpage\fi}
2929 \newcommand{\qNewPage}{\ifanswerkey\else\newpage\fi}
```

\OnBackOfPage In an effort to make maximum use of the paper, I sometimes ask the students to solve the problem on the back of a page. The following command is an automated instruction. Generally, we work on the back of the previous page, unless we are on page 1, in this case we work on the back of page 1.

```
2930 \newcounter{backofpage}
2931 \newcommand{\bopText}{on the back of page~\boPage}
2932 \newcommand{\bopCoverPageText}{on the back of the cover page}
2933 \newcommand{\OnBackOfPage}[1][\bopText]{%
2934     \refstepcounter{backofpage}\label{\bop{thebackofpage}}
2935     \begingroup
2936     \csarg\ifx{r@\bop{thebackofpage}}\relax
2937         \def\boPage{??}\else
2938             \edef\eqe@temp{\csname r@\bop{thebackofpage}\endcsname}%
2939             \ifx\hyper@anchor\undefined
2940                 \edef\boPage{\expandafter\@secondoftwo\eqe@temp}\else
2941                 \edef\boPage{\expandafter\@secondoffive\eqe@temp}\fi
2942             \c@eq@count\boPage
2943             \advance\c@eq@count-1\relax
2944 }
```

If on page 1, we work on the back of page 1, otherwise, we work on the back of the previous page.

```
2944     \edef\boPage
2945     {%
2946         \ifx\eqex@coverpage\relax
2947             \ifnum\value{eq@count}=0
2948                 %
2949             \else
2950                 \the\value{eq@count}%
2951             \fi
2952 }
```

```

2952         \else
2953             \ifnum\value{eq@count}=0
2954                 -1%
2955             \else
2956                 \the\value{eq@count}%
2957             \fi
2958         \fi
2959     }%
2960     \fi
2961     \csarg\ifx{r@bop\thebackofpage}\relax#1\else
2962     \ifnum\boPage=-1\relax\bopCoverPageText\else#1\fi\fi
2963     \endgroup
2964 }

```

## 14 Vertical Space Filling Options

When the `nosolutions` or the `vspacewithsolns` is used, a vertical space is generated by the `solution` environment. Previously, this has just been a vertical white space, now, we provide the ability to fill the space with horizontal rules of different types. Below is the implementation of this.

### 14.1 General filler lines commands and controls

`\useFillerLines` When used, the vertical space is written with lines (rules, dashes, dots, grids ).

```

2965 \newcommand{\useFillerLines}{\ifx\vspaceFiller % dpsj8
2966   \vspaceFillerLines\else@\eqlinedfillertrue
2967   \let\vspaceFiller\vspaceFiller\fillTypeDefault
2968 \fi}

```

`\useFillerDefault` Resets the vertical space to the original white space.

```

2969 \newcommand{\useFillerDefault}{\eqlinedfillerfalse
2970   \let\vspaceFiller\vspaceFillerDefault
2971   \let\eqWriteLine\hfill}

```

`\fillTypeHRule` Writes the line as a solid line (`\rule{width}{height}`).

```

2972 \newcommand{\fillTypeHRule}{\let\eqWriteLine\eqWriteLineFill
2973   \let\makeVgrid\relax}

```

`\fillTypeDots` Writes the line as a dotted line (`\dotfill`).

```

2974 \newcommand{\fillTypeDots}{\let\eqWriteLine\eqWriteLineDots
2975   \let\makeVgrid\relax}

```

`\fillTypeDashLine` Writes the line as a dotted line (`\eqdashrulefill`).

```

2976 \newcommand{\fillTypeDashLine}{\let\eqWriteLine\eqWriteLineDashFill
2977   \let\makeVgrid\relax}

```

```

\fillTypeBlankLine Fills the line
2978 \newcommand{\fillTypeBlankLine}{\let\eqWriteLine\eqWriteLineBlankFill
2979   \let\makeVgrid\relax}

\fillTypeDefault Resets fill type back to the default, \hrulefill.
2980 \newcommand{\fillTypeDefault}{\let\eqWriteLine\eqWriteLineFill
2981   \let\makeVgrid\relax}

\fillTypeGrid Fills the space with a grid, horizontal and vertical lines.
2982 \newcommand{\fillTypeGrid}{\ifx\vspaceFiller\vspaceFillerLines
2983   \let\eqWriteLine\eqWriteLineFill\let\makeVgrid\eqe@makeVgrid\f}
2984 \newcommand{\eqWriteLineColor}[1]{\def\eq@WriteLineColor{#1}}
2985 \eqWriteLineColor{gray}

\eqWLSpacing The line spacing between the rules.
2986 \newlength\wlVspace
2987 \newcommand{\eqWLSpacing}[1]{\setlength\wlVspace{#1}}
2988 \eqWLSpacing[14.0pt]

Fill Types. We have three types of line fill: \hrulefill, \dotfill, and a custom rule \eqdashrulefill. The commands three \eqWriteLineFill, \eqWriteLineDots, and \eqWriteLineDashFill implements these three types. They are \let to \eqWriteLine, which is used in \vspaceFillerLines.
2989 \newcommand{\eqWriteLineFill}{%
2990   \textcolor{\eq@WriteLineColor}{\leaders
2991     \hrule height \flfboxrule\hfill}}}

The first box is used in \eqdotrulefill, whereas the second two are used to split off content using \vsplit. These are active when the options fextended and answerkey are in force, and when \useFillerLines and \turnflanskeyOn have been expanded.
2992 \newbox\eqe@tempbox
2993 \newbox\eqe@nskeyflsplit
2994 \newbox\eqe@nskeyfltop
2995 \def\eqdotrulefill{\leavevmode
2996   \cleaders\hb@xt@ .44em{\copy\eqe@tempbox\hss}\hfill} % dps16
2997 % \cleaders\hb@xt@ .44em{\unhcopy\eqe@tempbox\hss}\hfill} % dps8
2998 \newcommand{\eqWriteLineDots}{%
2999   \textcolor{\eq@WriteLineColor}{\eqdotrulefill}}
3000 \def\eqdashrulefill{\leavevmode
3001   \cleaders\hb@xt@ .44em{\rule{.22em}{\flfboxrule}\hss}\hfill\kern\z@}
3002 \newcommand{\eqWriteLineDashFill}{%
3003   \textcolor{\eq@WriteLineColor}{\eqdashrulefill}}
3004 %\newcommand{\eqWriteLineBlankFill}{\hfill}
3005 \newcommand{\eqWriteLineBlankFill}{\vphantom{\hrulefill}}

```

Vertical counterparts to those above, excepting blank fill.

```

3006 \newcommand{\eqWriteLineVFill}{\leaders\vrule width\fboxrule\vfill}
3007 \def\eqdotruleVfill{\cleaders\vbox to .44em{\vss
3008   \hbox to0pt{\hss.\hss}\vfill}}
3009 \newcommand{\eqWriteLineVDots}{\eqdotruleVfill}
3010 \def\eqdashruleVfill{\cleaders\vbox to .44em{\vss
3011   \hbox to0pt{\hss\rule{\fboxrule}{.22em}\hss}\vfill}}
3012 \newcommand{\eqWriteLineDashVFill}{\eqdashruleVfill}
```

`\usenLineDimen` When the `solution` environment contains both an `nLines` and a dimension, by default, the dimension is used; however, if `\usenLineDimen` is specified, we force the use of the `nLines` specification. Switch back to the default using `\useVspaceDimen` `\useVspaceDimen`.

```

3013 \newif\if@equsedim \equsedimtrue
3014 \newcommand{\useVspaceDimen}{\equsedimtrue}
3015 \newcommand{\usenLineDimen}{\equsedimfalse}
3016 \newif\if@eqalignfilllinestoleft \eqalignfilllinestoleftfalse
```

`\fillerLinesAlignDef` Use `\fillerLinesAlignDef` and `\fillerLinesOnLeftMargin` to adjust the alignment of the rule lines for this feature. The first is the default, the second one aligns rule lines to the left margin.

```

3017 \newcommand{\fillerLinesOnLeftMargin}{\eqalignfilllinestolefttrue}
3018 \newcommand{\fillerLinesAlignDef}{\eqalignfilllinestoleftfalse}
3019 \newcommand{\priorPageBreakMsg}[1]{\def\priorP@geBre@kMsg{#1}}
3020 \let\priorP@geBre@kMsg@\empty
3021 \newcommand{\f1PageBreakMsg}[1]{%
3022   \priorPageBreakMsg{\emitMessageNearBottom[\iacvspace]
3023   {\eqfititin{\Large\strut}{#1}}}}
3024 }
```

The command `\makeVgrid` is an internal macro that is let to either `\relax`, as below, or to `\eqe@makeVgrid`. The latter creates a grid of fill lines.

```
3025 \let\makeVgrid\relax %dps1
```

**Key-values for fill lines** We define the `eqefillLines` `xkeyval` family, the keys are set through the command `\setFillLinesFmt`. We define nine keys `numbers`, `numbersep`, `color`, `topline`, `gridtype`, `fltype`, `align`, `outlineonly`, `bgonly`, and `bgcolor`. The first two are used to number the fill lines, the `color` is to color the fill lines, the last two concerning the grid type filler lines.

`numbers=⟨none|left|right⟩` This is a `numbers` is a choice key with possible values of `none`, `left` and `right`. It places a line numbering to the left or right of the line, or no line number is used if `none` is selected.

```

3026 \define@choicekey+{eqefillLines}{numbers}{[val\nr]}%
3027 {none,left,right}[none]{\ifcase\nr\relax
3028   \let\eqe@numLinesL\relax\let\eqe@numLinesR\relax\or
3029   \let\eqe@numLinesL\eqe@@numLinesL\let\eqe@numLinesR\relax\or
3030   \let\eqe@numLinesL\relax\let\eqe@numLinesR\eqe@@numLinesR
3031 \fi}
```

```

3032 }{\PackageWarning{aeb}{Bad choice for numbers, permissible values
3033   are none, left, and right. Try again}}
3034 \let\eqe@numLinesL\relax\let\eqe@numLinesR\relax

numbersep=dimen When numbers is either left or right, the separation between the line
and the number is numbersep. The default value is 2pt.
3035 \define@key{eqefillLines}{numbersep}[2pt]{%
3036   \setlength{\eqetmplengtha}{#1}%
3037   \edef\eqe@numbersep{\the\eqetmplengtha}%
3038 \def\eqe@numbersep{2pt}

color=color-spec The color key paints the lines the specified color, for example,
color=red!20. It simply defines \eq@WriteLineColor to be this color.
3039 \define@key{eqefillLines}{color}[]{\def\eq@WriteLineColor{#1}}

topline=true|false When \fillTypeGrid is in effect, topline=true writes an additional
line above the top most line, this line is not numbered.
3040 \define@boolkey{eqefillLines}{topline}[true]{}
3041 \KV@eqefillLines@toplinefalse

gridtype=line|dash|dots The gridtype key determines the line style for the grid, choices
are line (the default), dash, and dots. This key also sets the line style when the
outlineonly key is specified.
3042 \let\eqe@usedeffboxrule\eqe@NO % dps20
3043 \let\gridtypeselected\@empty % dps26
3044 \define@choicekey+{eqefillLines}{gridtype}[\val\nr]{%
3045   {line,dash,dots}[line]\{\edef\gridtypeselected{\val}\% dps26
3046   \ifcase\nr\relax
3047     \let\gridHLineFill\eqWriteLineFill
3048     \let\gridVLineFill\eqWriteLineVFill
3049   \or
3050     \let\gridHLineFill\eqWriteLineDashFill
3051     \let\gridVLineFill\eqWriteLineDashVFill
3052   \or
3053     \let\gridHLineFill\eqWriteLineDots
3054     \let\gridVLineFill\eqWriteLineVDots
3055     \let\eqe@usedeffboxrule\eqe@YES %dps20
3056   \fi
3057 }{\PackageWarning{aeb}{Bad choice for numbers, permissible values
3058   are line, dash, and dots. Try again}}
3059 \let\gridHLineFill\eqWriteLineFill
3060 \let\gridVLineFill\eqWriteLineVFill

fltype=line|dash|dots|blank The fltype key determines the type of line style for the
horizontal rendering. This key simply executes the various command versions.
3061 \define@choicekey+{eqefillLines}{fltype}[\val\nr]{%
3062   {line,dash,dots,blank,grid}[line]\{\ifcase\nr\relax
3063     \fillTypeHRule\or
3064     \fillTypeDashLine\or
3065     \fillTypeDots
3066     \let\eqe@usedeffboxrule\eqe@YES\or % dps20

```

```

3067      \fillTypeBlankLine\or
3068      \fillTypeGrid\fi
3069 }{\PackageWarning{aeb}{Bad choice for numbers, permissible values
3070   are line, dash, dots, blank, and grid. Try again}}
align=<left|default> Another convenience key, align simply executes the command
               versions.
3071 \define@choicekey+{eqefillLines}{align}[\val\nr]%
3072   {default, left}[default]{\ifcase\nr\relax
3073     \fillerLinesAlignDef\or
3074     \fillerLinesOnLeftMargin\fi
3075 }{\PackageWarning{aeb}{Bad choice for numbers, permissible values
3076   are line, dash, dots, blank, and grid. Try again}}
3077 \define@choicekey*{eqefillLines}{equalcells}[\val\nr]%
3078   {true, false}[true]{\ifcase\nr\relax
3079     \equalCellSizesOn\or
3080     \equalCellSizesOff\fi
3081 }

outlineonly*=<true|false> outlines the work area only, does not create horizontal or vertical
               lines, other than the lines to outline the region. Obeys the gridtype key.
3082 \define@boolkey{eqefillLines}{outlineonly}[true]{}
3083 \KV@eqefillLines@outlineonlyfalse
3084 \define@choicekey{eqefillLines}{outlineonly*}[true, false][true]{% dps26
3085   @nameuse{KV@eqefillLines@outlineonly#1}%
3086   \def\eqefillLines@outlineonlystar{\#1}%
3087 \let\eqefillLines@outlineonlystar\empty

bgonly*=<true|false> colors the work area with a color of your choice, see bgcolor below.
3088 \define@boolkey{eqefillLines}{bgonly}[true]{% dps11
3089 \KV@eqefillLines@bgonlyfalse
3090 \define@choicekey{eqefillLines}{bgonly*}[true, false][true]{% dps26
3091   @nameuse{KV@eqefillLines@bgonly#1}%
3092   \def\eqefillLines@bgonlystar{\#1}%
3093 \let\eqefillLines@bgonlystar\empty

bgcolor=<color-spec> The color to be used when bgcolor is in force. If no color has been
               assigned, the color will be white.
3094 \define@key{eqefillLines}{bgcolor}[] {\def\eqe@BGColor{\#1}} % dps11
3095 \let\eqe@BGColor\empty

\fillLinesNumFmt{<cmds>} is used to specify the format for line numbers. Within the <cmds> argument,
               use #1 to indicate the placement of the number. For example, the code
\fillLinesNumFmt{\textbf{\#1}} puts the line numbers in bold font.
3096 \def\fillLinesNumFmt#1{\def\eqe@fillLinesNumFmt##1{\def\flnum{\##1#1}}
3097 \fillLinesNumFmt{\flnum} % set to default values
3098 \define@key{eqefillLines}{numfmt}[] {\fillLinesNumFmt{\#1}} % dps21
3099 \define@key{eqefillLines}{linegap}[14pt]{\def\f1@wlspace{\#1}} % dps21
3100 \def\f1@wlspace{14pt}

\setFillLinesFmt{<KV-pairs>} Set the format of the fill lines, use the keys from the eqefillLines

```

defined and described above. Changes outside a group are global. An example of the usage is given here: `\setFillLinesFmt{numbers=left,color=red}`.

Other important notes: To produce horizontal lines only, use `fltype=line|dash|dots`, to produce blank space, use `fltype=blank` and to produce a grid `fltype=grid`.

```

3101 \newcommand{\setFillLinesFmt}[1]{\def\@rgi{#1}%
3102   \let\eqe@usedeffboxrule\eqe@NO %dps20
3103   \let\gridtypeselected\empty
3104   \ifx\@rgi\empty
3105     \setkeys{eqefillLines}{numbers,numbersep,color,
3106       gridtype,fltype,align}%
3107   \else
3108     \let\is@outlineonly\eqe@NO\let\is@bgonly\eqe@NO
3109     \ifKV@eqefillLines@outlineonly\let\is@outlineonly\eqe@YES\fi
3110     \ifKV@eqefillLines@bgonly\let\is@bgonly\eqe@YES\fi
3111     \setkeys{eqefillLines}{#1}%
3112     \eqWLSpacing{\fl@wlspacing}%
3113     \ifx\makeVgrid\relax
3114       \KV@eqefillLines@toplinefalse
3115     \forceEqualCellsfalse % dps21
3116     \equalCellSizesOff % dpsj15
3117     \ifx\is@bgonly\eqe@YES % carryover from prev prob
3118       \ifKV@eqefillLines@bgonly
3119         \KV@eqefillLines@bgonlyfalse
3120       \else
3121         \PackageWarning{eqexam}{You must specify fltype=grid for
3122           bgonly to work.\MessageBreak
3123           Ignoring this key for now}%
3124         \KV@eqefillLines@bgonlyfalse
3125         \let\is@bgonly\eqe@NO
3126       \fi
3127     \else % not continuation
3128       \ifKV@eqefillLines@bgonly
3129         \PackageWarning{eqexam}{You must specify fltype=grid for
3130           bgonly to work.\MessageBreak
3131           Ignoring this key for now}%
3132         \KV@eqefillLines@bgonlyfalse
3133         \let\is@bgonly\eqe@NO
3134       \fi
3135     \fi
3136   % same for outline
3137   \ifx\is@outlineonly\eqe@YES % carryover from prev prob
3138     \ifKV@eqefillLines@outlineonly
3139       \KV@eqefillLines@outlineonlyfalse
3140     \else % dps18
3141       \PackageWarning{eqexam}{You must specify fltype=grid for
3142         outlineonly to work.\MessageBreak
3143         Ignoring this key for now}%
3144       \KV@eqefillLines@outlineonlyfalse

```

```

3145      \let\is@outlineonly\eqe@N0
3146      \fi
3147      \else % not continuation
3148      \ifKV@eqefillLines@outlineonly
3149          \PackageWarning{eqexam}{You must specify fltype=grid for
3150          outlineonly to work.\MessageBreak
3151          Ignoring this key for now}%
3152          \KV@eqefillLines@outlineonlyfalse
3153          \let\is@outlineonly\eqe@N0
3154      \fi
3155      \fi
3156      \let\gridHLineFill\eqWriteLine
3157      \let\gridVLineFill\eqWriteLine
3158      \else
3159          \ifx\gridtypeselected\@empty % dps26
3160              \let\gridHLineFill\eqWriteLineFill
3161              \let\gridVLineFill\eqWriteLineVFill
3162          \fi
3163      \fi
3164  \fi
3165 }

```

The next two definitions place line numbers on the left and right, respectively.

```

3166 \def\eqe@numLinesL{\ifKV@eqefillLines@topline\ifnum\@tempcntb>0 % dps5
3167   \smash{\llap{\tiny
3168     \eqe@fillLinesNumFmt{\the\@tempcntb}\hglue\eqe@numbersep\relax}}\fi
3169   \else\smash{\llap{\tiny
3170     \eqe@fillLinesNumFmt{\the\@tempcntb}\hglue\eqe@numbersep\relax}}\fi}
3171 \def\eqe@numLinesR{\smash{\rlap{\tiny
3172   \hglue\eqe@numbersep\relax\eqe@fillLinesNumFmt{\the\@tempcntb}}}}

```

The `\fillLinesLineWidth` is a special command used for adjusting the length of the horizontal lines, and is used only when `\fillTypeGrid` is in effect and when `\forceEqualCells` is true.

```
3173 \let\fillLinesLineWidth\@empty
```

A switch to signal that a grid has broken across pages. This is only set to true when the `topline=true` is specified through `\setFillLinesFmt`.

```
3174 \newif\ifgridpgbrk\gridpgbrkfalse % dps7
```

`\vspaceFillerLines{<dimen>}` This is an internal command, though we declare it publicly. It writes the horizontal lines (lines, dots, dashes) when the `solution` environment uses a `<dimen>` to specify space (as opposed to using the `nLines` key).

```

3175 \newif\ifwriteVertic@lFLines \writeVertic@lFLinestrue % dps16
3176 \def\f1@set@notContStrSkip{\def\@notContStrSkip{\vskip6pt}} % dpsj23
3177 \let\p@ssToFLs\relax
3178 \newif\iff1@firstpass % dps27
3179 \newcommand{\vspaceFillerLines}[1]{\begingroup\offinterlineskip %dps1
3180   \global\f1@firstpasstrue % dps27
3181   \f1@set@notContStrSkip % dpsj20

```

```

3182 \p@ssToFLs\if@eqlinedfiller
3183   \def\eqe@next{\vspaceFillerLines@i{\#1}}\else
3184   \expandafter\def\expandafter\eqe@next
3185   \expandafter{\expandafter\endgroup\p@ssToFLs}\fi
3186   \global\let\p@ssToFLs\relax\eqe@next}
3187 \def\vspaceFillerLines@i#1{\advance\wlVspace-\flfboxrule % dps25
3188   \ifx\eqe@usedeffboxrule\eqe@YES\flfboxrule=.4pt\fi % dps20
3189   \ifKV@eqefillLines@outlineonly\KV@eqefillLines@toplinetrue %dps10
3190     \KV@eqefillLines@bgonlyfalse % dps11
3191 %   \forceEqualCellsfalse % dpsj15
3192   \equalCellSizes0ff\let\makeVgrid\eqe@makeVgrid\fi %dps10
3193   \ifKV@eqefillLines@bgonly\KV@eqefillLines@toplinetrue
3194     \KV@eqefillLines@outlineonlyfalse\flfboxrule=.4pt % dps20
3195 %   \forceEqualCellsfalse % dpsj15
3196   \equalCellSizes0ff\let\makeVgrid\eqe@makeVgrid\fi %dps11
3197   \parindent0pt\relax\parskip0pt
3198   \atempdima\wlVspace\eqetmplengtha0pt
3199   \atempcnda=0 \atempcntb=1

```

`\eqe@fillwidth` is the width of the line, it is `\linewidth` plus a fudge factor, which is determined dynamically by `\eqe@wrtLineKernal`.

```
3200 \def\eqe@fillwidth{\linewidth+\eqetmplengtha}%

```

If we are creating a grid (`\fillTypeGrid`), and `\forceEqualCells` is true, we modify the length of the line to make equal cell sizes. `\forceEq@lCells` determines the value of `\fillLinesLineWidth`.

```

3201 \eqe@wrtLineKernal
3202 \setbox\eqe@tempbox\hbox{\hb@xt@0pt{\hss.\hss}}\ht\eqe@tempbox.33pt
3203   \dp\eqe@tempbox0pt % dps16
3204 \ifx\makeVgrid\relax
3205 %   \forceEqualCellsfalse % dpsj15
3206   \equalCellSizes0ff
3207 \else % dps2
3208   \let\eqWriteLine\gridHLineFill
3209   \forceEq@lCells % dps2
3210   \ifx\f1Equ@lLineWidth\empty\else
3211     \linewidth=\f1Equ@lLineWidth\relax\fi
3212   \ifKV@eqefillLines@bgonly\else
3213     \ifKV@eqefillLines@topline\bgroup\atempcntb=0% dps5
3214       \makebox[0pt][1]{\eqe@x
3215         \makebox[\eqe@fillwidth]{\eqWriteLine}}\egroup
3216     \fi\fi % dps5
3217 \fi
3218 \settowidth{\eqetmplengthb}{\eqe@decPointPrb}\def\vfGo@l{\#1}%
3219 \ifx\makeVgrid\relax\else
3220   \def\priorPNPAction{\xdef\f1@nRows{\the\atempcnda} % dps27
3221     \if@eqalignfilllinesleft\eqe@x\fi % dpsj12
3222     \makeVgrid\priorP@geBre@kMsg\global\f1@firstpassfalse} % dps4
3223   \def\postPNPAction{\global\gridpgbrktrue % dps27
3224   \setlength{\atempdima}

```

```

3225      {(\vfGo@l+\wlVspace)-\depthtodate}%
3226      \edef\vfGo@l{\the\@tempdima}\@tempdima=\wlVspace\relax
3227      \@tempcpta=0\relax}%
3228      \fi
3229      \@whiledim\@tempdima<\vfGo@l\relax\do
3230      {\edef\depthtodate{\the\@tempdima}%
3231      \ifx\eqe@insert@more@content\relax\ifx\makeVgrid\relax
3232      \priorP@geBre@kMsg\fi\fi %dps15
3233      \eq@insertContAnnot\vskip\wlVspace\eqe@x

```

Draw the horizontal line: a rule, dotted line, dashed line

```

3234      \ifKV@eqefillLines@bgonly\vglue\fboxrule\else % dpsj11 dpsj21
3235      \ifKV@eqefillLines@outlineonly\vglue\fboxrule\else %dps10
3236      \makebox[0pt][1]{\eqe@numLinesL
3237      \makebox[\eqe@fillwidth]{\eqWriteLine}\eqe@numLinesR}\fi
3238      \fi
3239      \advance\@tempcpta1\relax\advance\@tempcntb1\relax
3240      \edef\depthtodate{\the\@tempdima}%
3241      \addtolength{\@tempdima}{\wlVspace}\par dps25

```

At the conclusion of the `\do` loop, we insert `\makeVgrid`, which is either `\relax` or is `\eqe@makeVgrid`, the latter is a complicated command to draw vertical lines across the horizontal ones, and to perform other tasks.

```

3242  }\xdef\f1@nRows{\the\@tempcpta}\makeVgrid % dps27
3243  \ifx\makeVgrid\relax\else %dps15

```

When there is insufficient space to accommodate the content, we place a small blank box in the lower left corner, put a information message in the log, and reset the color.

```

3244  \ifvoid\eqe@nskeyflsplit\else\PackageWarning{eqexam}%
3245  {Some material from a solution environment does not\MessageBreak
3246  appear. Increase space allotted}\normalcolor
3247  \llap{\smash{\rule{5pt}{5pt}}}\aftergroup
3248  \reset@color\fi % dpsj24
3249  \fi

```

We conclude by adding some vertical space to better align the `workarea` environment. When a fill type is used, the space created by not be exactly  $\langle dimen \rangle$  the dimension specified.

```

3250  \setlength{\@tempdima}{\vfGo@l-\depthtodate}\vskip\@tempdima
3251  % \vskip\fboxrule\vskip3pt
3252  \dimen0=\sameVspace\relax
3253  \dimen2=\fboxrule\advance\dimen0by\dimen2
3254  \xdef\sameVspace{\the\dimen0 }\endgroup
3255  \global\fblrstsplittrue
3256 }

```

`\eq@linesXPgs` Does the same as `\vspaceFillerLines` but is used instead of that command when the optional argument for `solution` specified a value for `nLines`. Code comments are the same as those just given for `\vspaceFillerLines`.

```

3257 \def\eq@linesXPgs{\@tempdimb\wlVspace % dpsj20
3258   \advance\@tempdimb-\flfboxrule
3259   \atempdimb=\soln@keys@nLines\@tempdimb
3260   \advance\@tempdimb\flfboxrule
3261   \expandafter\vspaceFillerLines\expandafter{\the\@tempdimb}

\eqe@wrtLineKernal, based on a case analysis, sets the register \eqetmplengtha
and makes some horizontal glue adjustments as well.

3262 \% \def\eq@linesXPgs{\@tempdimb\wlVspace
3263 %   \atempdimb=\soln@keys@nLines\@tempdimb
3264 %   \expandafter\vspaceFillerLines\expandafter{\the\@tempdimb}}
3265 \def\eqe@wrtLineKernal{\let\eqe@x\relax\let\eqe@y\relax % dpsj9
3266   \ifx\solutionparshape\empty % not lead-in
3267     \if@eqalignfilllinestoleft % align on left
3268       \setlength{\eqetmplengtha}{\labelwidth+\eqemargin}%
3269       \setlength{\eqetmplengtha}
3270         {\eqetmplengtha+\eqetmplengthb}%
3271     \ifwithinparts
3272       \ifx\istabularexer\eq@YES % tabular mode
3273         \setlength{\eqetmplengtha}{\prtsIndntSep}%
3274         \eq@tmpLengthA\eqetmplengtha
3275         \def\eqe@x{\hglue-\prtsIndntSep}%
3276         \ifKV@eqefillLines@outlineonly\let\eqe@y\eqe@x\fi
3277       \else
3278         \settowidth{\eqetmplengtha}{\eqe@prtsepPrb}%
3279         \setlength{\eqetmplengtha}{\eqetmplengtha+\widthOfParts}%
3280         \setlength{\eq@tmpLengthA}{\eqetmplengtha}%
3281         \def\eqe@x{\hspace*{-\eqetmplengtha}\hglue-\flfboxrule}%
3282       \fi
3283     \else % not parts, still align left
3284       \def\eqe@x{\hspace*{-\eqemargin}}%
3285       \eqetmplengtha\eqemargin
3286       \eq@tmpLengthA\eqemargin
3287     \fi
3288   \else % not lead-in, not align on left
3289     \ifwithinparts
3290       \setlength{\eqetmplengtha}{\labelwidth}%
3291       \setlength{\eqetmplengtha}
3292         {\eqetmplengtha+\eqetmplengthb}%
3293       \ifx\istabularexer\eq@YES % tabular mode
3294         \eqetmplengthaOpt
3295         \eq@tmpLengthA\eqetmplengtha %
3296       \else %dps2
3297         \def\eqe@x{\hglue-\flfboxrule}%
3298         \eqetmplengthaOpt
3299         \eq@tmpLengthA\eqetmplengtha
3300       \fi
3301     \else % not parts, not align left
3302       \eqetmplengthaOpt
3303       \eq@tmpLengthA\eqetmplengtha

```

```

3304      \fi
3305      \fi
3306  \else % lead-in
3307      \if@eqalignfilllinestoleft
3308          \setlength{\eqetmplengtha}{\leadinIndentPrtSep}\dps27
3309          \eq@tmplengthA\eqetmplengtha
3310      \else
3311          \eqetmplengtha0pt
3312          \eq@tmplengthA\eqetmplengtha
3313      \fi
3314  \fi
3315 }

```

`\equalCellSizesOn` set the switch `\ifforceEqualCells` to true, while `\equalCellSizesOff` sets the same switch to false. Additionally, the latter command resets `\fillLinesLineWidth` to its default value of `\@empty`. It is therefore important not to use the switch directly, but to use these two convenience commands.

```

3316 \newif\ifforceEqualCells
3317 \def\equalCellSizesOn{\global\let\f1Equ@lLineWidth\@empty
3318     \global\forceEqualCellstrue}
3319 \def\equalCellSizesOff{\global\let\f1Equ@lLineWidth\@empty
3320     \global\forceEqualCellsfalse}
3321 \equalCellSizesOff

```

`\forceEqu@lCells` determines the value of `\fillLinesLineWidth`. It successively adds `\wlVspace` until it exceeds `\linewidth`, it then subtracts off one `\wlVspace` to get the value for `\fillLinesLineWidth`.

```

3322 \def\forceEqu@lCells{\bgroup
3323   \ifforceEqualCells
3324   \dimen6\wlVspace % reduced from \vspaceFillerLines
3325   \advance\dimen6\flfboxrule
3326   \dimen2=\z@
3327   \dimen4\linewidth
3328   \advance\dimen4by-\flfboxrule
3329   \if@eqalignfilllinestoleft % dps8
3330       \advance\dimen4\eq@tmplengthA
3331   \fi
3332   \tempcnta0
3333   \whiledim \dimen2 < \dimen4 \do{%
3334       \advance\tempcnta1
3335       \advance\dimen2by\dimen6
3336   }%
3337   \advance\tempcnta-1
3338   \advance\dimen2-\dimen6
3339   \advance\dimen2\flfboxrule
3340   \advance\dimen2by-\eq@tmplengthA
3341   \xdef\f1Equ@lLineWidth{\the\dimen2}%
3342   \fi
3343 \egroup}
3344 \let\eqe@insert@more@content\relax

```

```

3345 \def\gobtodot#1.#2@nil{\def\intPrt{#1}\def\fracPrt{#2}}
\eqe@makeVgrid A command that is executed when the document author expands \fillTypeGrid. The command itself draws vertical rule lines, which intersect with horizontal rule lines to form a grid. When \fillTypeGrid is active, \makeVgrid is \let to \eqe@makeVgrid. \makeVgrid appears twice in each of the macros \vspaceFillerLines and \eq@linesXPgs. The first instance of \makeVgrid draws the vertical line, assuming there is no page break. If there is a page break, the second instance of \makeVgrid continues to draw vertical lines with the correct height and number. To make the grid break across a page, the low level command \makeRoomForProb was modified; now prior and post actions (\priorPNAction and \priorPNAction) can be defined.

The \dbMrk is used to debug this portion of the code, view the debugging marks by setting \ifeqedb to true.
3346 \def\dbMrk#1{\textsf{\footnotesize#1}}
3347 @ifundefined{ifeqedb}{\newif\ifeqedb \eqedbfalse}{}}

\fillerCustomBg{\alt{-bg}} Add a custom background feature, only available when the key bgonly is active. The argument \alt{-bg} uses #1 and #2 to refer to the width and height of the work area. Use \resetFillerCustomBg to reset the method of coloring the background to its default method.
\resetFillerCustomBg
3348 \def\fillerCustomBg#1{\def\fillerBgIm@ge##1##2{#1}}
3349 \def\resetFillerCustomBg{\let\fillerBgIm@ge\empty}
3350 \resetFillerCustomBg

\gridIndentAdj{\dimen} is an adjustment in the horizontal positioning of the vertical lines of the grid. Under normal conditions, \gridIndentAdj is not needed. If the exam environment is embedded in environments that change some basic parameters, the alignment of the grid may not be right, in which case you can use \gridIndentAdj to shift the grid horizontally.
3351 \def\gridIndentAdj#1{\def\rgi{#1}\ifx\rgi\empty
3352   \let\gridIndent@dj\relax\else % dps4
3353   \setlength{\tempdima}{#1}\edef\gridIndent@dj{\the\tempdima}\fi}
3354 \let\gridIndent@dj\relax
3355 \def\eqe@makeVgrid{\begingroup
3356   \tempcpta=\f1@nRows\relax
3357   \advance\wlVspace\flfboxrule % dps25
3358   \setlength{\tempdima}{\eqe@fillwidth}%
3359   \setlength{\tempdimb}{\wlVspace}%
3360   \edef\eqe@tmp{\strip@pt\tempdimb}%
3361   \expandafter\gobtodot\eqe@tmp.\@nil
3362   \divide\tempdima by\intPrt\relax
3363   \dimen2=\tempdima
3364   \dimen4=1pt
3365   \advance\dimen2 by 0.5\dimen4
3366   \divide\dimen2 by \dimen4
3367   \multiply\dimen2 by \dimen4
3368   \edef\eqe@tmp{\strip@pt\dimen2}%
3369   \expandafter\gobtodot\eqe@tmp.\@nil

```

```

3370  \advance\@tempcnta-1\relax % dps21
3371  \multiply\@tempdimb\@tempcnta
3372  \edef\eqe@HOfVrule{\the\@tempdimb}%
3373  \ifKV@eqefillLines@topline % dps21
3374    \advance\@tempdimb\wlVspace
3375    \advance\@tempdimb\flfboxrule
3376    \edef\eqe@HOfVruleFrstRow{\the\@tempdimb}%
3377    \def\eqe@setVRule{\vbox
3378      to\eqe@HOfVruleFrstRow\relax{\gridVLineFill}}% dps8
3379  \else
3380    \def\eqe@setVRule{\vbox
3381      to\eqe@HOfVrule\relax{\gridVLineFill}}% dps8
3382  \fi
3383  \eqe@tempcnta=0
3384  \dimen2=\wlVspace
3385  \count4=\intPrt\relax
3386  \setlength{\dimen4}{\eqe@fillwidth}%
3387  \multiply\dimen2by\count4
3388  \whiledim \dimen2 > \dimen4 \do{%
3389    \advance\count4by-1\relax
3390    \edef\intPrt{\the\count4 }%
3391    \dimen2\wlVspace
3392    \multiply\dimen2by\count4
3393  }%
3394  \dimen2\wlVspace
3395  \if@eqalignfilllinestoleft % dps27
3396    \let\f1@oSmash\smash\let\f1@iSmash\relax
3397  \else
3398    \let\f1@iSmash\smash\let\f1@oSmash\relax
3399  \fi
3400  \f1@oSmash{%
3401  \makebox[0pt][1]{\makebox[\eqe@fillwidth][1]{\f1@iSmash{}% dps27
3402    \ifx\gridIndent@\dj\relax\else
3403      \hglue\gridIndent@\dj\relax\fi
3404    \eqe@y\ifeqedb\rlap{\dbMrk{D}}\fi % dpsj9 \eqe@y (fudge)
3405    \rlap{\ifeqedb\rlap{\dbMrk{B}}\fi
3406    \ifwriteVertic@1FLines % dps16
3407      \setlength{\tempdima}{\eqe@fillwidth}%
3408      \ifKV@eqefillLines@bgonly % dps11
3409        \ifx\fillerBgIm@\empty
3410          \ifx\eqe@BGColor@\empty\else
3411            \rlap{\textcolor{\eqe@BGColor}{\rule{\eqe@fillwidth}{\eqe@HOfVruleFrstRow}}}\fi
3412          \rule{\eqe@fillwidth}{\eqe@HOfVruleFrstRow}}\fi
3413        \else
3414          \rlap{\fillerBgIm@\eqe@fillwidth\eqe@HOfVruleFrstRow}\fi
3415      \else
3416        \dimen2=\wlVspace
3417        \dimen0=0pt
3418        \whilenum\eqe@tempcnta<\count4\do{\rlap{\hglue\dimen0
3419          \ifKV@eqefillLines@outlineonly %dps10

```

```

3420           \ifnum\eqe@tempcnta=0 \else\let\gridVLineFill\vfill\fi\fi
3421           \textcolor{\eq@WriteLineColor}{\eqe@setVRule % dps27
3422           \ifeqedb\rlap{\advance\eqe@tempcnta by1\relax\scriptsize
3423               \raisebox{1pt}{\kern1pt\the\eqe@tempcnta}}\fi}%
3424           \advance\dimen0by\dimen2
3425           \advance\eqe@tempcnta by1
3426       }% dps27
3427   \fi % dps11
3428   \advance\dimen2by\flfboxrule
3429   \ifKV@eqefillLines@bgonly\else % dps11
3430       \rlap{\hglue\@tempdima
3431           \textcolor{\eq@WriteLineColor}{\eqe@setVRule
3432           \ifeqedb\rlap{\thinspace\dbMrk{R}}\fi}%
3433       \ifKV@eqefillLines@outlineonly %dps10
3434           \makebox[0pt][1]{\makebox[\eqe@fillwidth]{\eqWriteLine}}}%dps10
3435       \fi
3436   \ifKV@eqefillLines@topline% dps7
3437       \ifgridpgbrk\@tempdima\eqe@HOfVruleFrstRow\relax % dps21
3438           \raise\@tempdima\hbox{\makebox[0pt][1]{%
3439               \makebox[\eqe@fillwidth]{\eqWriteLine}}}%
3440           \global\gridpgbrkfal
3441       \fi
3442   \fi
3443   \fi
3444   \ifx\eqefillLines@outlineonlystar\@empty\else % dps26
3445       \global\let\eqefillLines@outlineonlystar\@empty
3446       \global\KV@eqefillLines@outlineonlyfalse
3447   \fi
3448   \ifx\eqefillLines@bgonlystar\@empty\else % dps26
3449       \global\let\eqefillLines@bgonlystar\@empty
3450       \global\KV@eqefillLines@bgonlyfalse
3451   \fi
3452   \fi % ifwriteVertic@lFLines
3453   \eqe@insert@more@content
3454 }% rlap
3455 }% smash (f1@iSmash)
3456 }}}} makeboxes and \f1@oSmash
3457 \endgroup
3458 }% \eqe@makeVgrid

```

In preparation for the `flextended` option, we define several commands and one environment that emit a package warning if the `flextended` option is not taken.

```

3459 \def\turnfl@nskeyMsg{\PackageWarning{eqexam}
3460 {You must first take the flextended\MessageBreak
3461 option for this command to have any\MessageBreak effect}}
3462 \def\turnflanskeyOn{\turnfl@nskeyMsg
3463 \def\priorw@Msg{\PackageWarningNoLine{eqexam}
3464 {The priorworkarea environment does nothing\MessageBreak
3465 without the flextended option. All such content\MessageBreak in these
3466 environments are absorbed}\global\let\priorw@Msg\@empty}

```

```

3467 \newenvironment{priorworkarea}{\priorw@Msg
3468     \setbox\eqe@nskeyflssplit\vbox\bgroup
3469     {\egroup\setbox\eqe@nskeyflssplit\box\voidb@x}
3470 \let\turnflanskeyOff\turnflanskeyOn
3471 \newif\iff\frsts\flfrsts\true
3472 \newif\ifeq\eqe@fnosolns \eqe@fnosolns\false
3473 \def\turnfnosolnsOn{\eqe@fnosolns\true\turnflanskeyOn}
3474 \def\turnfnosolnsOff{\eqe@fnosolns\false\turnflanskeyOn}
3475 %\let\turnfnosolnsOn\turnflanskeyOn
3476 %\let\turnfnosolnsOff\turnflanskeyOn
3477 \newdimen\f\lboxrule \f\lboxrule=.4pt
3478 \def\tweakBreakPoint#1{\def\rgi{#1}\ifx\rgi\empty
3479   \gdef\twe@kBre@kPoint{#1}\else
3480   {\setlength{\tempdima}{#1}%
3481     \xdef\twe@kBre@kPoint{\the\tempdima}}\fi}
3482 \def\twe@kBre@kPoint{#1}

When flextended option is not loaded, we make a minimal definition of
\eq@b@ddCodeSpecial. This redefinition is needed when bgonly is in effect.
3483 \def\eq@b@ddCodeSpecial#1{\if@eqlinedfiller
3484   \ifKV@eqefillLines@bgonly\leavevmode
3485   \vskip-\baselineskip\kern\lineskip\fi\fi#1}

```

**\fSeparateCutNames** For debug, or whatever reason, **\fSeparateCutNames** gives each flx cut file a distinct name.

```

3486 \def\fSeparateCutNames{\def\f@CutName{flx\f@Cnt-\jobname.cut}}
3487 </package>
3488 {*flextended}

```

## 14.2 Utility commands used with the flextended option

```

3489 \def\f@ls@vebaselinelineskip{%
3490   \xdef\f@baselinekip{\the\baselineskip}}
3491 \def\f@Cnt{0}
3492 \def\f@CutName{flx-\jobname.cut}
3493 \def\f@writeexsol@fter{%
3494   \ifx\exsolafter\empty
3495     \immediate\write\verbatim@out{\string\ignorespaces}%
3496   \else
3497     \immediate\write\verbatim@out{\string\exsolafter
3498     \string\space\string\ignorespaces}%
3499   \fi
3500 }
3501 \def\f@getcontent#1{\begingroup
3502   {\count0=\f@Cnt\relax
3503     \advance\count0by1\relax
3504     \xdef\f@Cnt{\the\count0}%
3505 % \let\save@wlog\wlog\let\wlog@gobble
3506 % \let\save@message\message\let\message@gobble
3507   \global\let\verbatim@out\CommentStream

```

```

3508  \immediate\openout\verbatim@out=\#1
3509  \ifwithinparts
3510    \ifx\istabularexer\eq@YES
3511      \immediate\write\verbatim@out{\string\hfuzz\string\hsize}%
3512      \immediate\write\verbatim@out{\string\minipage[t]{\string\hsize}}%
3513      \ifanswerkey
3514        \immediate\write\verbatim@out{\string\expandafter
3515          \string\noindent\string\eqSolnExCmds}%
3516          \dps{23}
3517          \fwriteexsol@fter
3518      \else
3519        \immediate\write\verbatim@out{\string\expandafter
3520          \string\noindent\string\priorWorkAreaCmds
3521          \string\ignorespaces}%
3522          \dps{23}
3523      \fi
3524    \else
3525      \ifanswerkey\fwriteexsol@fter\fi
3526    \fi
3527  \else
3528    \verbatimimwrite
3529  }
3530 \def\f@vsplitandplace#1{%
3531   \iff@firstpass
3532     \global\setbox\eqe@nskeyflsplit\color@vbox
3533       \normalbaselines
3534       \predisplaypenalty=-50
3535       \postdisplaypenalty=-50
3536       \setlength{\hsize}{\eqe@fillwidth}%
3537       \expandafter\noindent %
3538       \dps{j}{23}
3539       \ifanswerkey\expandafter\eqSolnExCmds\else
3540         \expandafter\priorWorkAreaCmds\fi
3541       \ignorespaces\input{#1}\f@vbaseline@skip
3542       \color@endbox\global\f@firstpassfalse\fi
3543     \tempdima\eqe@HOfVrule\relax

```

I'm getting a black box when there is one line left on the second page and there is less than one line of text. The following three lines attempt to get that last line to appear when there is enough room for it.

```

3543   \advance\tempdima\f@fboxrule
3544   \advance\tempdima\lineskip
3545   \ifflfrstsplit\else\advance\tempdima\wlVspace\fi
3546   \advance\tempdima\maxdepth
3547   \advance\tempdima by\twe@kBre@kPoint\relax
3548   \eq@tmplengthB\tempdima % target height
3549   \split@topskip\wlVspace
3550   \split@maxdepth\maxdepth
3551   \advance\split@maxdepth by\twe@kBre@kPoint\relax
3552   \setbox\eq@pointbox=\copy\eqe@nskeyflsplit
3553   \setbox\eqe@nskeyfltop=\vsplit\eq@pointbox to \tempdima

```

```

3554 \setbox\eqe@nskeyfltop=\vbox{\unvbox\eqe@nskeyfltop}%
3555 \ifvoid\eq@pointbox\else
3556   \setlength{\@tempdimb}
3557     {\eq@tlengthB-\dp\eqe@nskeyfltop}%
3558   \ifdim\@tempdimb<0pt
3559     \@tempdimb=-\@tempdimb
3560     \ifdim\@tempdimb>\maxdepth
3561       \advance\@tempdima-\fbskip\relax
3562     \else
3563     \fi
3564   \else
3565     \setbox\eq@pointbox=\copy\eqe@nskeyflsplit
3566     \advance\@tempdima by\fbskip\relax
3567     \setbox\eqe@nskeyfltop=\vsplit\eq@pointbox to \@tempdima
3568     \setbox\eqe@nskeyfltop=\vtop{\unvbox\eqe@nskeyfltop}%
3569     \setlength{\@tempdimb}{\eq@tlengthB-\dp\eqe@nskeyfltop}%
3570     \ifdim\@tempdimb<0pt % too much
3571       \advance\@tempdima-\fbskip\relax
3572     \else
3573     \fi
3574   \fi
3575 \fi
3576 \splittopskip\wlVspace
3577 \lineskip1pt
3578 \setbox\eq@pointbox=\copy\eqe@nskeyflsplit
3579 \global\setbox\eqe@nskeyfltop=\vsplit\eqe@nskeyflsplit to \@tempdima
3580 \global\setbox\eqe@nskeyfltop\vtop{\unvbox\eqe@nskeyfltop\vskip0pt}%
3581 \ifvoid\eqe@nskeyflsplit
3582   \ifeqedb\llap{Bot}\fi
3583   \ifeqedb\raise\eqe@HOfVrule\llap{Top}\fi
3584   \ifeqedb\llap{V\qquad}\fi
3585   \iffirstsplit\global\fifirstsplitfalse
3586   \ifeqedb\llap{FP\hskip.5in}\fi
3587   \rlap{\raisebox{\eqe@HOfVrule+\fboxrule+\lineskip}%
3588     {\vtop{\vsize=\eqe@HOfVrule\relax
3589       \unvbox\eqe@nskeyfltop\vfil}}}\else
3590   \ifeqedb\llap{SP\hskip.5in}\fi
3591   \rlap{\raisebox{\eqe@HOfVrule+\fboxrule+\wlVspace+\lineskip}%
3592     {\vtop{\vsize=\eqe@HOfVrule\relax
3593       \unvbox\eq@pointbox\vfil}}}\%
3594   \global\setbox\eqe@nskeyflsplit\box\voidb@x
3595 \fi
3596 \else
3597   \ifeqedb\llap{Bot}\fi
3598   \ifeqedb\raise\eqe@HOfVrule\llap{Top}\fi
3599   \ifeqedb\llap{nV\qquad}\fi
3600   \iffirstsplit\global\fifirstsplitfalse
3601   \ifeqedb\llap{FP\hskip.5in}\fi
3602   \rlap{\raisebox{\eqe@HOfVrule+\fboxrule+\lineskip}%
3603     {\vtop{\vsize=\eqe@HOfVrule\relax

```

```

3604      \unvbox\eqe@nskeyfltop\vfil}}}\else
3605      \ifeqedb\llap{SP\hskip.5in}\fi
3606      \rlap{\raisebox{\eqe@HOfVrule+\flfboxrule+\wlVspace+\lineskip}
3607          {\vtop{\vsize=\eqe@HOfVrule\relax

```

To have the filler lines/grid with prior and solution content to space more than one page, we unbox \eqe@nskeyfltop but do not void it.

```

3608      \unvbox\eqe@nskeyfltop\vfil}}\%
3609 %      \unvbox\eq@pointbox\vfil}}\%
3610 %      \global\setbox\eqe@nskeyflsplit\box\voidb@x
3611      \fi
3612  \fi
3613  \setbox\eq@pointbox\box\voidb@x
3614 % \gdef\twe@kBre@kPoint{Opt}\% dpsj21
3615 }

```

### 14.3 Filler lines with answerkey option

When using the `flextended` option and the `\turnflanskeyOn` command, we always use the grid filler type. In the case of the basic filler types of line, dash, dots, and blank, the code threads passes to `\makeVgrid`, but in the case of the `answerkey` option, `\makeVgrid` writes no vertical lines. Hopefully, the spacing between the statement of the question and the solution are then consistent.

```
3616 \let\turnfl@nskeyOnOff\relax
```

`\turnflanskeyOn` The `\turnflanskeyOn` command turns *on* the feature of superimposing the solution over the filler lines. Does nothing unless the `answerkey` option is in force.

```

3617 \def\turnflnosolnsOn{\eqe@flnosolntrue}
3618 \def\turnflnosolnsOff{\eqe@flnosolnfalse}
3619 \def\turnflanskeyOn{%
3620   \def\turnfl@nskeyOnOff{%
3621     \ifanswerkey
3622       \ifx\makeVgrid\relax % already in grid mode, do nothing
3623         \ifwriteVertic@lFLines\KV@eqefillLines@toplinefalse\fi % dps16
3624         \writeVertic@lFLinesfalse
3625         \let\makeVgrid\eqe@makeVgrid % dpsj5
3626       \fi % dps17
3627       \let\eqe@insert@more@content\eqe@insertSolns % dpsj5
3628       \eqe@flextendedtrue % dps16
3629       \fillTypeGrid % dps16
3630       \global\let\eq@insertverticalspace\eq@YES
3631       \global\vspacewithsolntrue
3632     \fi
3633   }%
3634 }

```

`\turnflanskeyOff` The `\turnflanskeyOff` command turns *off* the feature of superimposing the solution over the filler lines. Does nothing unless the `answerkey` option is in force.

```

3635 \def\turnflanskeyOff{%
3636   \def\turnfl@nskeyOnOff{%
3637     \ifanswerkey

```

```

3638      \writeVertic@lFLinestrue
3639      \eqe@flextendedfalse
3640      \let\eq@insertverticalspace\eq@NO
3641      \eqlinedfillerfalse
3642      \global\let\eqe@insert@more@content\relax
3643      \global\let\eq@insertverticalspace\eq@YES
3644      \ifvspacewithsolns\else
3645      \global\vspacewithsolnsfalse\fi
3646      \global\displayworkareafalse
3647  \fi
3648 }%
3649 }
3650 \turnflanskeyOff
3651 \let\p@ssToSolns\relax % dps30
3652 \def\eqe@insertSolns{\clubpenalty=50
3653   \widowpenalty=50 \vbadness=10000
3654   \f@vsplitandplace{s\f@CutName}}
3655 \def\eq@b@ddCodeSpecial#1{\global\gridpgbrkfalse % dpsj15
3656   \global\let\eq@e@ddCodeSpecial\relax
3657   \gdef\eqe@flnexti{#1}%
3658   \if@eqlinedfiller
3659     \ifKV@eqefillLines@bgonly\leavevmode
3660     \vskip-\baselineskip\kern\lineskip\fi % dpsj11
3661     \ifKV@eqefillLines@outlineonly\leavevmode
3662     \vskip-\baselineskip\kern\lineskip\fi
3663     \ifanswerkey \% \turnfl@nskeyOnOff % dps16
3664     \ifeqe@flextended
3665       \ifcont@nnot
3666         \ifx\makeVgrid\relax
3667           \gdef\p@ssToFLs{\turnfl@nskeyOnOff
3668             \let\eqe@insert@more@content\eqe@insertSolns
3669             \writeVertic@lFLinestrue
3670             \KV@eqefillLines@toplinefalse
3671             \let\makeVgrid\eqe@makeVgrid
3672           }%
3673       \else
3674         \gdef\p@ssToFLs{\turnfl@nskeyOnOff
3675           \let\eqe@insert@more@content\eqe@insertSolns
3676           \writeVertic@lFLinestrue}%
3677       \fi
3678       \gdef\eqe@flnexti{\turnfl@nskeyOnOff
3679         \global\f@irstpasstrue % dpsj5
3680         \p@ssToSolns
3681         \global\gridpgbrkfalse
3682         \eqe@setStartSolns

```

We are with a good two deep, but we need to pass `\vspacewithkeyOff`, so we save its current state and declare a global call to `\vspacewithkeyOff`. The state is restored by `\eq@e@ddCodeSpecial`.

```

3683          \xdef\kdvsp@SAVE{\ifkeepdeclaredvspacing
3684              true\else false\fi}%
3685          \gdef\kdvsp@Restore{\cnameuse
3686              {keepdeclaredvspacing}\kdvsp@SAVE}%
3687          \gdef\twe@kBre@kPoint{Opt}\global
3688              \let\kdvsp@Restore\relax}%
3689          \expandafter\global\vspacewithkeyOff
3690          \vbadness=10000
3691          \f@getContent{s\f@CutName}%
3692          \gdef\eq@e@ddCodeSpecial{\endverbatim\endgroup
3693 }%
3694          \kdvsp@Restore %
3695          \ifwithinparts{ifx\istabular}{\eq@YES}
3696          \immediate\write\verb@out{\string\endminipage}\fi\fi
3697          \immediate\closeout\verb@out
3698          \global\let\eq@e@ddCodeSpecial\relax
3699 }%
3700 \else
3701     \PackageWarning{eqexam}{For solutions to appear
3702         using filler lines\MessageBreak
3703         (with flexteded and answerkey options),\MessageBreak
3704         you must first expand \string\turnContAnnotOn\MessageBreak
3705         prior to line \the\inputlineno.\MessageBreak
3706         Switching to \string\useFillerDefault}%
3707         \useFillerDefault
3708         \let\eq@insertverticalspace\eq@NO
3709     \fi
3710     \fi
3711     \fi
3712     \eqe@flnexti
3713 }% dpsj4

```

#### 14.4 Filler lines with nosolutions option

Just as we can supply filler lines for the `answerkey` option, we can do the same for the `nosolutions` option and superimpose content on the filler lines.

`priorworkarea` Place the `priorworkarea` environment *prior to* the solution environment. It has not arguments, but gets dimensions from the `solution` environment that follows.

```

3714 \def\eqe@priorw@content{%
3715     \clubpenalty=50 %
3716     \widowpenalty=50
3717     \vbadness=10000
3718     \f@vsplitandplace{p\f@CutName}%
3719 }%
3720 \renewenvironment{priorworkarea}{\par
3721     \ifx\solutionparshape\empty\else %
3722     \pushEnvir
3723         \everypar{}{if@eqalignfilllinestoleft\else

```

```

3724      \parshape=1 \leadinIndent \linewidth\fi
3725      \popEnvir
3726      \fi
3727      \global\let\p@ssToFLs\relax
3728      \global\let\p@ssToSolns\relax
3729      \vspacewithkeyOff
3730      \ifeq@nosolutions\else\sloppy\fi
3731      \def\eqe@flnexti{\eqSavedComment}%
3732      \ifeqe@flnosolns\ifdisplayworkarea
3733          \def\eqe@flnexti{\f@getContent{p\f@CutName}}\fi\fi % dpsj21
3734      \gdef\eqe@flnexti{\endeqSavedComment}%
3735      \ifeqe@flnosolns\ifdisplayworkarea
3736          \gdef\eqe@flnexti{\endverbatim\endgroup}
3737          \ifwithinparts\ifx\istabularexer\eq@YES
3738              \immediate\write\verbatim@out{\string\endminipage}\fi\fi
3739          \immediate\closeout\verbatim@out}\fi\fi
3740      \eqe@flnexti
3741  }{%
3742      \eqe@flnextii
3743      \ifcont@nnot
3744          \ifeqe@flnosolns
3745              \ifdisplayworkarea
3746                  \ifx\eq@insertverticalspace\eqe@YES
3747                      \ifx\makeVgrid\relax
3748                          \gdef\p@ssToFLs{%
3749                              \let\eqe@insert@more@content\eqe@priorw@content
3750                              \writeVertic@lFLinesfalse
3751                              \KV@eqefillLines@toplinefalse
3752                              \let\makeVgrid\eqe@makeVgrid}%
3753              \else
3754                  \gdef\p@ssToFLs{%
3755                      \let\eqe@insert@more@content\eqe@priorw@content
3756                      \writeVertic@lLinestrue}%
3757          \fi
3758          \gdef\kdvsp@Restore{\gdef\twe@kBRe@kPoint{Opt}\global
3759              \let\kdvsp@Restore\relax}%
3760      \fi
3761      \fi
3762  \else
3763      \global\setbox\eqe@nskeyflsplit\box\voidb@x
3764      \global\setbox\eqe@nskeyfltop\box\voidb@x
3765  \fi
3766  \else
3767      \PackageWarningNoLine{eqexam}{For priorworkarea to appear
3768      using filler lines\MessageBreak
3769      (with flexed and nosolutions options),\MessageBreak
3770      you must first expand \string\turnContAnnotOn\MessageBreak
3771      prior to line \the\inputlineno.\MessageBreak
3772      Switching to \string\useFillerDefault}%
3773  \gdef\p@ssToSolns{\useFillerDefault}%

```

```

3774 \fi
3775 }

3776 % end of segment
3777 </flextended>
3778 <*package>

Set the eqexam page style, if not otherwise indicated.

3779 \ifeqfortextbook\else
3780   \if@bypassqexamheading\else
3781     \pagestyle{eqExamheadings}\fi\fi
3782 </package>
3783 <*textbook>
3784 \ProvidesFile{eqtextb.def}
3785 [2016/01/18 v4.6 Cmds used by the fortextbook option (dps)]

```

## 15 Concerning the fortextbook option

What are my goals/desired features? Modern (U.S.) textbooks—at least the ones I’m familiar with—consist of some or all of the following resources:

- **Student Edition:** Answers to odd-numbered problems appear in the back of the text.

We need to have a scheme where odd-numbered problems, under suitable options, are compiled. **Goal:** It does not need to be restricted to odd-numbered, however, need to latex only those problems that meet the “include” criteria.

For chapter review problem sets, odd-number problems are have solutions in the back of the book.

For chapter quizzes, odd-numbered (optionally all) solutions are in the back of the book.

- **Instructor Edition:** Answers to all problems appear in the back of the book. Answers may also appear in the body of the text, in the margins of the text, or immediately after the statement of the problem. If the answer is too long, there is a cross-reference to the solution in the appendix.

Some publishers I’ve seen have wide margins where additional material can be inserted (historical sketches, instructor notes, pictures, etc.). In these margins, the answers to the problems can appear. Other publishers put answer immediately following the questions. The latter is easy to do; just have a macro, say `\ANS{$12.5$}`, which only expands when the “instructor” option is used.

- **Student Solution Manual:** Contains solutions to all odd-problems, as well as any review problems and chapter quizzes. Some publishers include all solutions to chapter quizzes.

A solution manual is a separate publication. This document would be created by latexing one or more of the auxiliary file (`.sol`) These files might have to be edited before the final compile. We include only the solutions that meet the include criteria (i.e., odd-numbered ones).

The current features of `eqexam` is what is needed here. The authors need only include solutions to each problem in a `solution` environment. Now, I realize that often times the authors create the solutions, but someone else, possibly a grade student or contractor, solves the problems. In the latter case, the authors would probably not like to turn over the source files to the one solving and typesetting the problems.

- **Instructor Solution Manual:** Contains solutions to all problems, review problems, chapter quizzes.

Similar comments for the instructor solution manual.

Some other thoughts by a contributor:

- Often there is a diagram or graphic within the problem – this has some figure caption and after the running counter of the figure it is named the NUMBER of the problem (cross-reference to the problem number)
- Often the probs with soln are setup in two-column style.
- Often the PROBLEM NUMBER has a special formatting (not only bold and black), maybe with a colorframebox around or some special formatting from the author
- Of course I have seen in some EXAMPLES that there is a wide margin to put in additional graphics etc. setup in two-side style – wide left margin on even pages, wide right margins on odd pages. Here as well are captions setup and cross-references.

### 15.1 Setting options with `\textbookOpts`

`\textbookOpts` We set up a command for setting the options for the `fortextbook` option.

```
marginans 3786 \define@boolkey{eqe@tbopts}[is]{instred}[true]{}  
inlineans 3787 \define@boolkey{eqe@tbopts}[is]{studented}[true]{%  
marginsonleft 3788 \ifisstudented  
ssols Now let's try to filter out the even-numbered problems for the student edition.  
lsols 3789 \tbfilterOutEvenNums
```

The above command is normally `\let` to `\@gobble`.

```
3790 \fi  
3791 }
```

This code is executed in `\exambegdef`, the start up code of the `exam` environment. This enables problems with fill-ins, true/false, or multiple choice, to have the answer appear in the space provided.

```
3792 \def\tb@beginexam@code{\%
3793     \ifisinstred\answerkeytrue\eq@proofingtrue\fi}
    \eqEXt{\theeqquestionno} and \endeqEXt\tok1\tok2 enclose each solution,
    \tbfilterOutEvenNums redefines \eqEXt to gobble everything, when the page
    number is even, through \endeqEXt and the two tokens it follows. This leaves
    only the odd-numbered problems.

3794 \newcommand{\tbfilterOutEvenNums}{%
    exerquiz changed \eqEXt to two variables, so we make the same change here
3795     \def\eqEXt##1##2{\ifodd##1\let\eqe@next\relax\else
3796         \def\eqe@next{\gobbletoEndEXt}\fi\eqe@next}%
3797 }
3798 \newcommand{\tballowAllNums}{%
    exerquiz changed \eqEXt to two variables, so we make the same change here
3799 \%     \let\eqEXt@gobble
3800     \let\eqEXt@gobbletwo
3801     \let\endeqEXt\relax
3802 }
3803 \define@boolkey{eqe@tbopts}[is]{marginans}[true]{}
3804 \define@boolkey{eqe@tbopts}[is]{inlineans}[true]{}
3805 \define@boolkey{eqe@tbopts}[] {marginsonleft}[true]
```

If margins are always on left, we turn off switching of margin notes as placed by `\marginpar`, and use `\reversemarginpar` to get them on the left.

```
3806     {\@mparswitchfalse\reversemarginpar}
3807 \define@boolkey{eqe@tbopts}[show]{ssols}[true]{}
3808 \define@boolkey{eqe@tbopts}[show]{lsols}[true]{%
3809     \ifshowlsols\let\tb@soln@choice\tb@showlsols\fi}
```

The default settings are `true` for `studented` and `false` for `instred`.

```
3810 \newcommand{\textbookOpts}[1]{\setkeys{eqe@tbopts}{#1}}%
```

We do not allow both `instred` and `studented` to be true.

```
3811     \ifisinstred\global\isstudentedfalse\else
3812         \ifisstudented\global\isinstredfalse
3813     \fi\fi
```

Added this part in in case `\textbookOpts` comes after `\marparboxwidth`.

```
3814     \ifdim\tbmarparboxwidth=1sp\else
3815         \expandafter\tbMakeFinalCalcs\fi
3816 }
```

As mentioned above, the default settings are `true` for `studented` and `false` for `instred`.

```
3817 \isstudentedtrue
3818 \isinstredfalse
3819 \ismarginansfalse
3820 \isinlineansfalse
```

The command is available only in the preamble.

```
3821 \onlypreamble{\textbookOpts}
```

- \turnOffMarAnsOnAnsInline These three command may not be useful in the creation of a textbook, but you never know, I used them in my demo doc `fortextbook.tex` to turn off and on \turnOnMarAnsOffAnsInline the display of the answers (change margin to inline, change inline to margin, and toggle margin and inline).

```
3822 \newcommand{\turnOffMarAnsOnAnsInline}{%
3823   \global\ismarginansfalse\global\isinlineantrue
3824   \insMidMarg{\global\ismarginansfalse
3825     \global\isinlineantrue}%
3826 }
3827 \newcommand{\turnOnMarAnsOffAnsInline}{%
3828   \global\ismarginantrue\global\isinlineansfalse
3829   \insMidMarg{\global\ismarginantrue
3830     \global\isinlineansfalse}%
3831 }
3832 \newcommand{\toggleInstrAns}{%
3833   \ifisinstred\ifismarginans
3834     \global\ismarginansfalse\global\isinlineantrue
3835     \insMidMarg{\global\ismarginansfalse
3836       \global\isinlineantrue}%
3837   \else
3838     \global\ismarginantrue\global\isinlineansfalse
3839     \insMidMarg{\global\ismarginantrue
3840       \global\isinlineansfalse}%
3841   \fi\fi
3842 }
```

## 15.2 Macros to display answers/shortsolns

In this section, we develop some commands to display answers or short solutions. These would appear if `instred=true`, in-line, or in the margins.

- \ANS Let us begin by creating a simple macro for saving an answer. The answer is displayed “in-line.” No verbatim-type text allowed, no unbalanced braces unless escaped. \ANS displays the answer if the `instred` option of the `eqe@tbopts` family, i.e., by executing

```
\bGrpANS Two macros used to group answers in the margins.
\bGrpANS 3843 \newif\ifWithinANSGrp\WithinANSGrpfalse
3844 \newif\iffbt@isANSListOpen\ftb@isANSListOpenfalse
3845 \newcommand{\bGrpANS}{%
3846   \if\probstar*\else
3847     \PackageError{eqexam}{Use of \string\bGrpANS\space
3848       only applies\MessageBreak to the problem* environment}{Please
3849       remove this \string\bGrpANS.}%
3850   \fi
3851   \ifWithinANSGrp
```

```

3852      \global\WithinANSGrpfalse
3853      \let\tb@next\relax
3854      \PackageError{eqexam}{\string\bGrpANS\space already open}
3855      {You issued an earlier \string\bGrpANS,
3856       but did not close it.}%
3857      \else
3858          \global\WithinANSGrptrue
3859          \global\ftb@isANSListOpenfalse
3860          \def\tb@next{\ANS}%
3861      \fi
3862      \tb@next
3863 }
3864 \newcommand{\eGrpANS}{%
3865     \if\probstar*\else
3866         \PackageError{eqexam}{Use of \string\eGrpANS\space
3867         only applies\MessageBreak to the problem* environment}{Please
3868         remove this \string\eGrpANS.}%
3869     \fi
3870     \ifWithinANSGrp
3871         \global\WithinANSGrpfalse
3872         \def\tb@next{\ANS}%
3873     \else
3874         \let\tb@next\relax
3875         \PackageError{eqexam}{\string\eGrpANS\space already closed}
3876         {You've issued two consecutive \string\eGrpANS\space
3877         commands,\MessageBreak either remove this one
3878         or the previous one.}%
3879     \fi
3880     \tb@next
3881 }

```

\ANS begin by checking to see if there is a star that follows the command, this is used for inline answers. If \* is present, we do not put the answer inline, but will put it in the margins if the option call for it.

```

3882 \newcommand{\ANS}{\@ifstar{\let\tb@istart=1\tb@ANS}
3883     {\let\tb@istart=0\tb@ANS}}

```

(10/13/2011) The following is the original definition of \tb@ANS before the creation of the commands \bGrpANS and \bGrpANS. We keep this to revert to this definition if this new feature causes problems.

```

\newcommand{\tb@ANS}[1]{%
\ifininstred
\ifisinlineans\if\tb@istart0\ANSFmt{\theeqquestionnoi}{#1}\fi\fi
\ifismarginans
\edef\eqe@prehold{\noexpand\par\kern0pt\noindent
\if\probstar*
\begin{eqeList}[\tb@wparts@len]{%
\noexpand\begin{eqeList}[\tb@wparts@len]{%
\noexpand\eqedsplonlyFrst{\theeqquestionnoi}%
{\thepartno}\noexpand\eqe@hspannerMrg

```

```

    \noexpand\makebox[\noexpand\tbmrgpartwdth]%
    {\noexpand\tb@mrgPartFmt{\thepartno}}}%
\else
    \noexpand\begin{eqeList}%
    {\noexpand\tb@mrgDigitFmt{%
        \thequestionnoi\eqe@decPointMrg}}}%
\fi
}\expandafter\insMidMarg%
\expandafter{\eqe@prehold#1\end{eqeList}}%
\fi
\fi
}

```

**\ftb@defineInsSpan** is used when there is an optional argument for **\ANS**. It formats the range of parts, for example, (a)–(c). This macro can be redefined, I suppose, to meet the needs of the author.

```

3884 \def\ftb@defineInsSpan#1{\def\ftb@argi{#1}\ifx\ftb@argi\empty
3885     \def\ftb@InsSpan{} \else\ftb@spanPrts{#1}%
3886     \def\ftb@InsSpan{\noexpand\hspace{-\labelsep}%
3887         \noexpand\textcolor{MRGPARTcolor}{--}\noexpand
3888         \makebox[\noexpand\tbmrgpartwdth]{\noexpand
3889             \tb@mrgPartFmt{\ftb@EndSpanPrts}}\eqe@hspannerMrg}\fi
3890 }

```

**\ftb@spanPrts** calculates the letter of the end of the range. #1 is passed by **\ANS** (**\tb@ANS**, actually). For example if we have **\ANS[2]{...}**, #1=2.

```

3891 \def\ftb@spanPrts#1{%
3892     \advance\value{partno}by#1\relax
3893     \xdef\ftb@EndSpanPrts{\thepartno}%
3894 }

```

**\ftb@EqeListPrtsFmt** is the internal formatting used within the **eqeList** for the part letter.

```

3895 \def\ftb@EqeListPrtsFmt{\noexpand
3896     \makebox[\noexpand\tbmrgpartwdth]{\noexpand
3897         \tb@mrgPartFmt{\thepartno}}\nobreak
3898 }

```

**\ftb@OpenEqeListPrts** opens an **eqeList** environment, and displays the question number (optionally) and the part number.

```

3899 \def\ftb@OpenEqeListPrts{\noexpand
3900     \begin{eqeList}[\tb@wparts@len]{\noexpand
3901         \eqedsplyOnlyFrst{\thequestionnoi}%
3902         {\thepartno}\noexpand\eqe@hspannerMrg\ftb@EqeListPrtsFmt}%
3903 }

```

**\ftb@CloseEqeList** closes the **eqeList** after inserting **\eqe@prehold** and the content, #1.

```

3904 \def\ftb@CloseEqeList#1{\expandafter\insMidMarg%
3905     \expandafter{\eqe@prehold#1\end{eqeList}}%
3906 }

```

**\grpANSDelimiter** delimits the parts when **\bGrpANS/\eGrpANS** is used. May be redefined.

```

3907 \newcommand{\grpANSDelimiter}{\textcolor{MRGPARTcolor}{,}\space}

```

\tb@ANS does the main work of \ANS.

```
3908 \newcommand{\tb@ANS}[2] []{%
3909     \ifisinstred
3910         \ifisinlineans
3911             \if\tb@istart0\ANSFmt{\thequestionnoi}{#2}\fi
3912         \fi
3913         \ifismarginans
3914             \ftb@defineInsSpan{#1}%

```

We create the code that we will introduce into \insMidMarg, this will be introduced prior to #2.

```
3915         \edef\eqe@prehold{%
3916             \if\probstar*%
```

If this question is one with parts...

```
3917             \iffbt@isANSListOpen
```

If the list is already open (\iffbt@isANSListOpen), we just add content to the eqeList environment.

```
3918             \ftb@EqeListPrtsFmt\noexpand\eqe@hspannerMrg
3919         \else
```

If the list is not open, we start the eqeList environment in the usual way, this also includes the case where \bGrpAns is not uses, which is normally the case.

```
3920             \noexpand\par\kern0pt\noindent
3921             \ftb@OpenEqeListPrts\ftb@InsSpan
3922         \fi
3923     \else
```

This is a question without parts.

```
3924             \noexpand\begin{eqeList}%
3925                 \noexpand\tb@mrgDigitFmt{%
3926                     \thequestionnoi\eqe@decPointMrg}%
3927             \fi
3928         }%
```

We have finished constructing \eqe@prehold. We next set \ftb@isANSListOpen to true, if \WithinANSGrp is true.

```
3929         \ifWithinANSGrp\global\ftb@isANSListOpentrue\fi
```

If we are within an open group, we emit \insMidMarg with the \eqe@prehold, followed by #2, and a comma-space combo, but we do not close the eqeList environment.

```
3930         \ifWithinANSGrp
3931             \expandafter\insMidMarg\expandafter
3932                 {\eqe@prehold#2\grpANSDelimiter}%
3933         \else
```

This is the normal case, we insert \eqe@prehold, #2, and close the eqeList environment.

```
3934             \expandafter\insMidMarg%
```

```

3935           \expandafter{\eqe@prehold#2\end{eqeList}}%
3936           \global\ftb@isANSListOpenfalse
3937       \fi
3938   \fi % \ifismarginans
3939 \fi %\ifisinstred
3940 }

```

End (10/13)

**eqeList** An environment used to format the answers in the margins, when `marginans` is in effect.

```

3941 \newenvironment{eqeList}[2]{\tb@woparts@len}{\begin{list}{#2}{%
3942   \def\argi{#1}\setlength{\labelwidth}{#1}%
3943   \ifx\argi\tb@wparts@len
3944     \settowidth{\labelsep}{\eqe@prtsepMrg}\else
3945     \settowidth{\labelsep}{\eqe@hspannerMrg}\fi
3946   \setlength{\leftmargin}{\labelwidth+\labelsep}%
3947   \setlength{\parskip}{0pt}\setlength{\partopsep}{0pt}%
3948   \setlength{\topsep}{1pt}\setlength{\parsep}{0pt}%
3949   \setlength{\itemindent}{0pt}\setlength{\itemsep}{3pt}%
3950 }\item\relax\end{list}}

```

### Formatting Answers and Solutions

**\mrgDigitFmt** Format of the digit (and the decimal point) for the answers in the margins.

```

\mrgDigitFmt{\textbf{#1}}
\mrgPartFmt{\textbf{(\hfil#1\hfil)}}
\setMarIndents[\bfseries\normalsize\normalfont]{00}{(d)}

3951 \newcommand{\mrgDigitFmt}[1]{\def\tb@mrgDigitFmt##1{#1}}
3952 \mrgDigitFmt{#1}

```

**\mrgPartFmt** Format of the part (including possibly the parentheses), example give above.

```

3953 \definecolor{MRGPARTcolor}{named}{black}
3954 \newcommand{\mrgPartFmt}[1]{\def\tb@mrgPartFmt##1{#1}}
3955 \mrgPartFmt{\textcolor{MRGPARTcolor}{(\hfil#1\hfil)}}

```

**ANScolor** The default color of the answers that appear in the margins or inline.

```
3956 \definecolor{ANScolor}{rgb}{0,0,.8}
```

**\ANSFmt** The command that sets the format, may be redefined as needed. Used in the `\ANS` command above.

```
3957 \newcommand{\ANSFmt}[2]{\textcolor{ANScolor}{#2}}
```

We have two environments that we use in three different situations:

- **equestions** environment: (1) Used to control the display of the `probset` environment within the body of the textbook; (2) used to control the display of the solutions “in the back of the book.”

- `eqlist` environment: Used for displaying answers in the margin of the book, when the appropriate options allow it.

We want to be able to manipulate some of the parameters of these three situations, independently of each other. There are several issues, setting what I have been calling the gutter width, and the display of the problem numbers.

We define four commands for each of the three situations described above. The names have a pattern to them, and similarly named commands have the same use.

The numbering of the problems has the pattern: `dd. (a)`. We provide convenience commands to give these internal macros values

`\prbDecPt` Basic parameters for the problems in the body of the text.

```
\prbPrtsep 3958 \def\eqe@decPointPrb{.}      % decimal point of prob number
\prbNumPrtsep 3959 \def\eqe@prtsepPrb{\ }    % prob with parts, space after part
3960 \def\eqe@hspannerPrb{\ }      % space after prob number
3961 \providecommand{\prbDecPt}[1]{\def\eqe@decPointPrb{#1}}
3962 \providecommand{\prbPrtsep}[1]{\def\eqe@prtsepPrb{#1}}
3963 \providecommand{\exPrtsep}[1]{\def\eqe@prtsepPrb{#1}}
3964 \providecommand{\prbNumPrtsep}[1]{\def\eqe@hspannerPrb{#1}}
```

`\solDecPt` Basic parameters for the problems in the solution sets.

```
\solPrtsep 3965 \def\eqedecPointSoln{.}      % decimal point of prob number
\solNumPrtsep 3966 \def\eqe@prtsepSoln{\ }    % prob with parts, space after part
3967 \def\eqe@hspannerSoln{\ }      % space after prob number
3968 \newcommand{\solDecPt}[1]{\def\eqedecPointSoln{#1}}
3969 \newcommand{\solPrtsep}[1]{\def\eqe@prtsepSoln{#1}}
3970 \providecommand{\solNumPrtsep}[1]{\def\eqe@hspannerSoln{#1}}
```

`\mrgDecPt` Basic parameters for the problems in the margins.

```
\mrgPrtsep 3971 \def\eqe@decPointMrg{.}      % decimal point of prob number
\mrgNumPrtsep 3972 \def\eqe@prtsepMrg{\ }    % prob with parts, space after part
3973 \def\eqe@hspannerMrg{\ }      % space after prob number
3974 \newcommand{\mrgDecPt}[1]{\def\eqe@decPointMrg{#1}}
3975 \newcommand{\mrgPrtsep}[1]{\def\eqe@prtsepMrg{#1}}
3976 \newcommand{\mrgNumPrtsep}[1]{\def\eqe@hspannerMrg{#1}}
```

`\setMarIndents` Sets some dimensions used by the `eqlist` environment. `\tb@wparts@len` is calculated and is used as the default gutter width in `eqlist`. `\tb@wparts@len` is used for the gutter width for the gutter width when there is a problem with parts. Finally, `\tbmrgpartwdth` in `\ANS` and is used for the width of a `\makebox` that enclosed the part letter.

```
3977 \newcommand{\setMarIndents}[3]{\normalsize\normalfont}{%
3978   \settowidth{\tempdima}{#1#2\eqe@decPointMrg}%
3979   \xdef\tb@wparts@len{\the\tempdima}%
3980   \settowidth{\tempdima}%
3981   {#1#2\eqe@decPointMrg\eqe@hspannerMrg#3}%
3982   \xdef\tb@wparts@len{\the\tempdima}%
3983   \settowidth{\tempdima}{#1#3}%
```

```

3984     \xdef\tbmrgpartwdth{\the\@tempdima}%
3985 }%
3986 \setMarIndents{00}{(d)}

```

**\setSolnIndent** Used to set the some parameters used by `\eqequestions`, in the solutions file.

```

3987 \newdimen\solnGutter
3988 \newcommand{\setSolnIndent}[3]{\normalsize\normalfont\bfseries}{%
3989     {\settowidth{\@tempdima}{#1#2\eqedecPointSoln\eqe@hspannerSoln}}%
3990     \global\solnGutter\@tempdima
3991     \settowidth{\@tempdima}{#1#3}%
3992     \xdef\tbsolnpartwdth{\the\@tempdima}%
3993 }%
3994 \setSolnIndent{00}{(d)}

```

**\setSolnMargins** This command is written to the solution file, and expanded when that file is input back in. If `\solnGutter` is not Opt, we set the length of `\eqemargin` using the current value; otherwise, we use the value determined by `\setSolnIndent`, above.

```

3995 \renewcommand{\setSolnMargins}[1]{%
3996     \ifdim\solnGutter=Opt \setlength\eqemargin{#1}\else
3997     \setlength\eqemargin{\solnGutter}\fi\ignorespaces}
3998 %\newcommand{\defaultSolnIndent}{\gdef\solnGutter{Opt}}
3999 \newcommand{\defaultSolnIndent}{\global\solnGutter=Opt}
4000 \defaultSolnIndent

```

**\prbNumFmt** We redefine `\exlabelformat`, `\exsllabelformat`, and `\exsllabelformatwp`.

**\solWoPrtsFmt** They are defined in such a way as to simply their modification through a series of  
**\solWPrtsFmt** simple formatting commands. The defaults are

```

\prbNumFmt{\textbf{#1}}
\solWoPrtsFmt{\textbf{#1}}
\solWPrtsFmt{\textbf{#1}}{(\hfil#2\hfil)}

4001 \renewcommand{\exlabelformat}{%
4002     \tbprbNumFmt{\theeqquestionnoi\eqe@decPointPrb}}

```

`\prbNumFmt` is the format for the number of the problems in the body of the text.  
The argument #1 is a symbolic argument for the question number.

```

4003 \newcommand{\prbNumFmt}[1]{\def\tbprbNumFmt##1{#1\eqe@hspannerPrb}}
4004 \prbNumFmt{\textbf{#1}}

```

Redefine `\exsllabelformat`, and `\exsllabelformatwp`

```

4005 \renewcommand{\exsllabelformat}{\string\tbsolWoPrtsFmt{%
4006     \theeqquestionnoi\string\eqedecPointSoln}}
4007 \renewcommand{\exsllabelformatwp}{\string\tbsolWPrtsFmt{%
4008     \string\eqedsplyOnlyFrst{\theeqquestionnoi}{\thepartno}}{%
4009     \thepartno}}
4010 }

```

`\solWoPrtsFmt` is the format for the number of the problems in the solution set.  
The argument #1 is a symbolic argument for the question number. `\solWPrtsFmt`

is the format for a problem with parts in the solution file. #1 is symbolically the question number, and #2 is a symbolic for the part letter.

```

4011 \newcommand{\solWoPrtsFmt}[1]{\def\tbsolWoPrtsFmt##1{%
4012     \makebox[0pt][r]{#1\eqe@hspannerSoln}}}
4013 \solWoPrtsFmt{\textbf{\#1}}
4014 \newcommand{\solWPrtsFmt}[2]{\def\tbsolWPrtsFmt##1##2{%
4015     \makebox[0pt][r]{#1\eqe@hspannerSoln}%
4016     \makebox[\tbsolnpartwdth][1]{#2}\eqe@prtsepSoln%
4017 }%
4018 \solWPrtsFmt{\textbf{\#1}}{(\hfil#2\hfil)}}

```

An alternate definition for `\solWPrtsFmt`, used by `\hangSolWPrtsFmt`.

```

4019 \newcommand{\solWPrtsFmt@hang}[2]{%
4020     \def\tbsolWPrtsFmt##1##2{%
4021         \makebox[0pt][r]{#1\eqe@prtsepSoln}%
4022         \makebox[\tbsolnpartwdth][1]{#2}\eqe@hspannerSoln}%
4023 }

```

`\hangSolWPrtsFmt` The command takes two arguments, the same as `\solWPrtsFmt`. When this command is executed in the preamble, we get hanging indentation for problems with parts.

```

4024 \let\bpartsmrk\relax
4025 \let\epartsmrk\relax
4026 \newcommand{\hangSolWPrtsFmt}[2]{%

```

At the beginning and ending of a parts environment, we begin and end a special `eqepartsquestions` environment, designed to give the desired indentation.

```

4027     \def\prior@parts@hook{%
4028         \ifisleadin\else
4029             \writeT@SolnFile{^J\protect\bpartsmrk\fi}%
4030     \def\post@parts@hook{%
4031         \writeT@SolnFile{\protect\epartsmrk^J}%
4032     \def\bpartsmrk{\global\firstitemtrue\begin{eqepartsquestions}}%
4033     \def\epartsmrk{\end{eqepartsquestions}\global\firstitemfalse}%

```

We must also redefine `\solWPrtsFmt` by letting it to `\solWPrtsFmt@hang`, then executing it using the parameters passed.

```

4034     \let\solWPrtsFmt\solWPrtsFmt@hang
4035     \solWPrtsFmt[#1]{#2}%
4036 }
4037 %\onlypreamble\hangSolWPrtsFmt

```

Define some switches, token registers, and boxes for managing the answers and marginal notes.

```

4038 \newif\ifexamenv \examenvfalse
4039 \newif\iffirstemitt \firstemitttrue
4040 \newtoks\txtbkt@ks \txtbkt@ks={}
4041 \newtoks\txtbkt@ksi \txtbkt@ksi={}
4042 \newbox\txtbkb@xb@t
4043 \newbox\txtbkb@xt@p

```

```

4044 \newbox\txtbkb@xh@ld
4045 \let\tbTopMargin\relax
4046 \let\tbBotMargin\relax
4047 \long\def\tb@addtoTopMargin#1{\txtbkt@ksi={#1}%
4048     \edef\eqe@tmphold{\the\txtbkt@ksi\the\txtbkt@ks}%
4049     \global\txtbkt@ks=\expandafter{\eqe@tmphold}%
4050 }
4051 \newcommand{\tb@addtoMargin}[1]{%
4052     \edef\eqe@tmphold{\the\txtbkt@ks}%
4053     \global\txtbkt@ks=\expandafter{\eqe@tmphold#1}%
4054 }

```

As my first attempt, let's create two comment environments to be used within the `solution` environment.

```

\begin{solution}
\begin{ssol}
<short solution/answer>
\end{ssol}
\begin{lsol}
<long solution>
\end{lsol}
\end{solution}

```

The control of these environments are made through

`lsol` Place full (or long) solutions in this environment.  
`\tb@showlsols` 4055 `\newcommand{\tb@showlsols}{\includecomment{lsol}\excludecomment{ssol}}`

`ssol` Place short solutions in this environment.  
`\tb@showssols` 4056 `\newcommand{\tb@showssols}{\includecomment{ssol}\excludecomment{lsol}}`

The default is to show the short solutions.

```

4057 \let\tb@soln@choice\tb@showssols
4058 %\let\tb@sols@choice\tb@showssols

```

### 15.3 Marginal Matter.

There are three levels in the margins:

1. **Top level:** This is a command `\tbTopMargin` with may be redefined between pages. It should have the width of the `\parbox` that contains all the content of the margin, this width is `\tb@marparboxwidth` (`\oddsidemargin-\marginparsep`). The content *must* be unbreakable across pages. The content of `\tbTopMargin` will appear *on every page subsequent to its definition*.

`\clearTopMargin` We can clear the top level using the following command

```

4059 \newcommand{\clearTopMargin}{\global\let\tbTopMargin\relax}

```

Clearing will take effect on the following page.

\setTopMargin

As a convenience macro, we can create top margin content. Redefinitions will appear on the next page from where the definition was made.

```
4060 \newcommand{\setTopMargin}[1]{%
4061   \gdef\tbTopMargin{\color@begingroup\normalcolor
4062     #1\color@endgroup}%
4063   \gdef\tbSaveTopMargin{\color@begingroup\normalcolor
4064     #1\color@endgroup}%
4065   \let\tbTopMargin\@empty
4066   \let\tbSaveTopMargin\@empty
```

2. **Middle level:** The middle level is the most interesting. You write to it using \insMidMarg. Normally, this is text. If there is too much text, it will be split off and placed in the middle level of the next page. The command \ANS also writes to the middle level when the `instred` and `marginans` options are taken.
3. **Bottom level:** This is similar to the top level, but on the bottom. The command is named \tbBotMargin and follows the same rules as \tbTopMargin. Again, the content of \tbBotMargin will appear *on every page subsequent to its definition*.

\clearBotMargin

We can clear the bottom level using the following command

```
4067 \newcommand{\clearBotMargin}{\global\let\tbBotMargin\relax}
```

Clearing will take effect on the following page.

\setBotMargin

As a convenience macro, we can create bottom margin content. Redefinitions will appear on the next page from where the definition was made.

```
4068 \newcommand{\setBotMargin}[1]{\gdef\tbBotMargin{\#1}%
4069   \gdef\tbSaveBotMargin{\#1}%
4070   \let\tbBotMargin\@empty
4071   \let\tbSaveBotMargin\@empty
4072 
4073 \newcommand{\restoreLastTopMargin}{\expandafter\setTopMargin
4074   \expandafter{\tbSaveTopMargin}}
4075 \newcommand{\restoreLastBotMargin}{\expandafter\setBotMargin
4076   \expandafter{\tbSaveBotMargin}}
```

\insMidMarg \insMidMarg is a \parbox that will hold the material in the margin.

\MarParBoxFmt The formatting for the marginal \parbox

```
4076 \newcommand{\MarParBoxFmt}{\normalsfcode
4077   \normalfont\normalsize\normalbaselines\parindent0pt
4078   \vbadness@Mi \hbadness5000 \tolerance9999
4079   \parskip0pt\raggedright \%\\spaceskip=0pt\\xspaceskip=0pt
4080   \\setlength{\\linewidth}{\\tbmarparboxwidth}%
4081 }
```

**\tbmarparboxwidth** The width of the margin box. Initial value of `1sp`, if the user does not reset the value, it is a package error.

```
4082 \newlength\tbmarparboxwidth  
4083 \setlength\tbmarparboxwidth{1sp}
```

**MidMargcolor** The default color of text of the middle level

```
4084 \definecolor{MidMargcolor}{rgb}{0,0,.8}  
4085 \newcommand{\midMargFmt}[1]{%  
4086   \def\tb@midMargFmt{\normalfont\normalsize\normalcolor#1}}  
4087 \midMargFmt{\color{MidMargcolor}}
```

**\eqe@MarParBox** This is the actual `\parbox` that holds the marginal material. I have two versions of this box, the first one has height `\textheight`, the second one has height `\textheight+\footskip`.

```
4088 \% \def\eqe@MarParBox#1{\parbox[b]{\textheight}[t] %  
4089 \%   {\tbmarparboxwidth}{\color{MidMargcolor}#1}}  
4090 \def\eqe@MarParBox#1{\lower\footskip\hbox{ %  
4091   \leavevmode\parbox[b]{\textheight+\footskip}[t] %  
4092   {\tbmarparboxwidth}{\tb@midMargFmt#1}}} %
```

Finally, we get to the `\insMidMarg`, this is used to write to the middle level.

```
4093 \newcommand{\insMidMarg}[1]{%  
4094   \let\eqe@margininsert\empty  
4095   \expandafter\tb@addtoMargin\expandafter{\eqe@margininsert#1}}%  
4096 }
```

**\tbPreMarginHeader** Executed prior to the marginal heading

**\tbPostMarginHeader** Executed after the marginal heading

**HEADERcolor** Default color of a marginal header

**\cngMargHeadColorTo** Changes the marginal header to a named color

**\resetMargHeadColor** Reset the marginal header color to the default, `HEADERcolor`

**\tbMarginHeaderFmt** Formatting for a marginal header. Format the marginal header, the default is `HEADERcolor` in bold

```
4097 \newcommand{\tbPreMarginHeader}{\par\penalty0 \kern3pt}  
4098 \newcommand{\tbPostMarginHeader}{\par\nobreak}  
4099 \definecolor{HEADERcolor}{named}{black}  
4100 \newcommand{\cngMargHeadColorTo}[1]{\insMidMarg{\gdef\tb@MHC{#1}}}  
4101 \newcommand{\resetMargHeadColor}{\insMidMarg{\gdef\tb@MHC{HEADERcolor}}}  
4102 \resetMargHeadColor  
4103 \newcommand{\tbMarginHeaderFmt}[1]{\textcolor{\tb@MHC}{\textbf{#1}}}
```

**\insMargHead** Used to insert a general marginal heading into the middle level. The optional parameter allows you to set a mark.

**\insProbHead** Used to insert a marginal heading for a problem set into the middle level. The optional parameter allows you to insert a mark, the default mark is #1 \tbcontinued.

```
4104 \newcommand{\insMargHead}[2][]{%
4105   \insMidMarg{\tb@marginHeader{#1}{#2}}%
4106 \newcommand{\insProbHead}[2][]{%
4107   \def\tb@argi{#1}\ifx\tb@argi\empty
4108     \protected@xdef\currProbHead{#2} \tbcontinued\else
4109     \protected@xdef\currProbHead{#1}\fi
4110   \ifisinstred\ifismarginans
4111     \insMidMarg{\tb@marginProbHeader{#1}{#2}}\fi\fi
4112 }
4113 \newcommand{\tb@marginProbHeader}[2]{%
4114   \def\tb@argi{#1}\ifx\tb@argi\empty
4115   \tb@marginHeader{#2} \tbcontinued{#2}\else
4116   \tb@marginHeader{#1}{#2}\fi
4117 }
4118 \newcommand{\tb@marginHeader}[2]{\tbPreMarginHeader
4119   \tbMarginHeaderFmt{#2}\def\tb@argi{#1}\ifx\tb@argi\empty
4120   \mark{#2}\else\mark{#1}\fi\tbPostMarginHeader
4121 }
```

**\tbcontinued** The continue annot that appear when a problem set flows over to the next page.

```
4122 \newcommand{\tbcontinued}{(cont.)}
```

**\tbplaceMargins** Redefine this macro to set the locations of the margins we are writing to.

```
4123 \newcommand{\marparboxwidth}[1]{%
4124   \setlength\tbmarparboxwidth{#1}%
4125   \setlength{\marginparwidth}{\tbmarparboxwidth}%
4126   \tbMakeFinalCalcs
4127 }
4128 \onlypreamble\marparboxwidth
4129 \newcommand{\chkmarginboxwidth}{%
4130   \ifdim\tbmarparboxwidth=1sp \PackageError{eqexam}%
4131   {You have not set the value of\MessageBreak
4132     \string\marparboxwidth}%
4133   {Define the \string\marparboxwidth\space command}\fi
4134 }
```

**\ifmarginsonleft** A Boolean switch, if true, all margins are on the left; otherwise, they alternate

```
4135 \newif\ifmarginsonleft \marginsonleftfalse
```

**\tbSetupForMargins** We compute \oddsidemargin, \evensidemargin, and \textwidth

```
4136 \newcommand{\tbSetupForMargins}{%
4137   \ifmarginsonleft
4138     \setlength{\oddsidemargin}{\tbmarparboxwidth+\marginparsep}%
4139     \setlength{\evensidemargin}{\oddsidemargin}%
4140     \setlength{\textwidth}{\paperwidth-2in-\oddsidemargin}%
4141   \else
```

```

4142      \setlength{\oddsidemargin}{0pt}%
4143      \setlength{\evensidemargin}{\tbmarparboxwidth+\marginparsep}%
4144      \setlength{\textwidth}{%
4145          \paperwidth-2in-\oddsidemargin-\evensidemargin}%
4146  \fi
4147 }

```

**\tbplaceMargins** We calculate the coordinates of the lower left hand corner of the margin \parbox depending on the value of \ifmarginsonleft.

```

4148 \newcommand{\tbplaceMargins}{%
4149   \setlength{\@tempdima}{%
4150     \paperheight-1in-\topmargin-\headheight-\headsep-\textheight}%
4151   \xdef\@evenly{\strip@pt\@tempdima}%
4152   \xdef\@oddly{\@evenly}%
4153   \setlength{\@tempdima}{1in}%
4154   \xdef\@evenllx{\strip@pt\@tempdima}%
4155   \ifmarginsonleft\else
4156     \setlength{\@tempdima}{1in+\textwidth+\marginparsep}\fi
4157   \xdef\@oddllx{\strip@pt\@tempdima}%
4158 }

```

**\tbMakeFinalCalcs** Executed by \marparboxwidth

```

4159 \newcommand{\tbMakeFinalCalcs}{%
4160   \tbSetupForMargins
4161   \tbplaceMargins
4162 }

```

**\tbminskipbtnlayers** \tbminskipbtnlayers is the minimum skip between layers (top, middle, bottom)  
Executed by \marparboxwidth

```

4163 \newlength\tbminskipbtnlayers
4164 \setlength{\tbminskipbtnlayers}{6pt}
4165 \newif\ifiscarryover \iscarryoverfalse

```

**carryoverFmt** is a work-around for the color problem experienced with carry over text: Suppose there is a change of color of the text on the previous page, the carry over text will naturally be colored the default color, `MidMargcolor`. To continue the text with the same color as the one the previous page, we enclose the text in the `carryoverFmt` environment.

```

4166 \newenvironment{carryOverFmt}[1]{#1\let\tb@carryoverFmt\empty
4167   \c@rryoverFmt{#1}}{}}

```

This command is called by the `carryOverFmt` environment. it takes its argument, which is a change in color or style, and defines `\tb@carryoverFmt`, which will be executed on the next page.

```

4168 \def\c@rryoverFmt#1{%
4169   \ifx\tb@carryoverFmt\empty
4170     \global\let\tb@carryoverFmt\empty
4171     \xdef\tb@co@page{\thepage}%

```

```

4172      \gdef\tb@carryoverFmt{\ifnum\thepage>\tb@co@page\relax
4173          #1\global\let\tb@carryoverFmt\@empty\fi}%
4174      \fi
4175 }
4176 \let\tb@carryoverFmt\@empty

\tb@insertCarryOver takes its argument, that is always \unvbox\xtbkb@xb@t}, and if there is any carryover content, will insert its argument followed by a copy, \tb@rest@reMarginFmt of the default margin format. This seems to work for recovering from a change of text or style over a page boundary.

4177 \let\tb@rest@reMarginFmt\relax
4178 \def\tb@insertCarryOver#1{%
4179     \let\tb@rest@reMarginFmt\relax
4180     \ifiscarryover\ifx\tb@carryoverFmt\@empty\else
4181         \let\tb@rest@reMarginFmt\tb@midMargFmt
4182         \tb@carryoverFmt\fi\fi
4183     #1 \tb@rest@reMarginFmt
4184 }

```

\eqe@tb@shipout We define the shipout to the margins.

**Bug:** When I use graphicxsp, embed the picture (such as a logo), and use that picture as the \setTopMargin, the shipout routine is executed twice for each page. I haven't figured out what causes this, but here is a work around. We record the most recent page number, if it equals the page number of the last iteration of \eqe@tb@shipout, we do nothing; otherwise, execute the shipout code.

```

4185 \newif\iftb@shipoutPermitted \tb@shipoutPermittedtrue
4186 \newcommand{\turnOnFTBShipout}{\global\tb@shipoutPermittedtrue}
4187 \newcommand{\turnOffFTBShipout}{\global\tb@shipoutPermittedfalse}

```

\turnOnFTBShipout \turnOnFTBShipout turns on the shipout, the default, and \turnOffFTBShipout \turnOffFTBShipout turns it off.

```

4188 \newcommand{\eqe@tb@shipout}{\iftb@shipoutPermitted
4189     \ifnum\arabic{page}=\tblastpageshipped
4190     \let\tb@so@next\relax\else
4191     \xdef\tblastpageshipped{\arabic{page}}%
4192     \def\tb@so@next{\eqe@tb@ship@ut}\fi
4193     \expandafter\tb@so@next\fi
4194 }
4195 \def\tblastpageshipped{-100}

```

Here is the actual shipout code for writing to the margins.

```

4196 \newcommand{\eqe@tb@ship@ut}{%
4197     \fboxsep=0pt\setlength{\unitlength}{1pt}%
4198     \global\setbox\xtbkb@xb@t=\vbox\bgroup
4199         \color@begingroup
4200         \hsize=\tbmarparboxwidth
4201         \vsize=\textheight
4202         \MarParBoxFmt
4203         \csname tbTopMargin\endcsname

```

```

4204          \vskip\tbminskipbtnlayers
4205 \set@typeset@protect
4206         \the\txtbkt@ks
4207         \color@endgroup\vfil
4208     \egroup
4209     \global\setbox\txtbkb@xt@p=\vsplit\txtbkb@xb@t to\textheight
4210     \ifvoid\txtbkb@xb@t\global\iscarryoverfalse
4211     \else\global\iscarryovertrue\fi

```

We have three levels the top (`\tbTopMargin`), the bottom (`\tbBotMargin`), and the middle (`\txtbkt@ks`). `\tbTopMargin` is no problem but `\tbBotMargin` requires some special attention.

```
4212 \ifx\tbBotMargin\relax\else
```

If `\tbBotMargin` is not `\relax`, we begin by putting `\tbBotMargin` into a `\vbox` under the same assumptions, and get its height.

```

4213     \bgroup\setbox2=\vbox{%
4214         \color@begingroup\normalcolor
4215         \hsize=\tbmarparboxwidth\kern0pt
4216         \MarParBoxFmt\csname tbBotMargin\endcsname
4217         \color@endgroup
4218         \kern0pt
4219     }%

```

We reduce `\textheight` by the height of `\tbBotMargin`

```

4220     \dimen0=\textheight
4221     \advance\dimen0-\ht\txtbkb@xh@ld
4222     \advance\dimen0-\tbminskipbtnlayers

```

We split off the top material by this amount, the new bottom is in `\txtbkb@xt@p` the new top is in `\box0`

```
4223     \setbox0=\vsplit\txtbkb@xt@p to \dimen0
```

The new bottom (which will overflow to the next page) is the content we clipped off bottom of `\txtbkb@xt@p` and the original overflow material still in `\txtbkb@xb@t`.

```

4224     \global\setbox\txtbkb@xb@t=\vbox{%
4225         \unvbox\txtbkb@xt@p\unvbox\txtbkb@xb@t}%

```

We then patch everything together the new top is in `\txtbkb@xt@p` the new top is in `\@tempboxa` followed by `\tbBotMargin` (in `\box\txtbkb@xh@ld`).

```

4226     \global\setbox\txtbkb@xt@p=\vbox{\unvbox0
4227         \vfill\vskip\tbminskipbtnlayers
4228         \vfil\unvbox2\relax}\egroup
4229     \fi
4230     \ifodd\value{page}%
4231         \put(\@oddllx,\@oddly){%
4232             \eqe@MarParBox{\unvbox\txtbkb@xt@p}}\else
4233         \put(\@evenlx,\@evenly){%
4234             \eqe@MarParBox{\unvbox\txtbkb@xt@p}}\fi

```

We see if there is any carry over, if yes, we insert into `\txtbkt@ks` for use on the next page, along with a heading, if any.

```
4235 \global\txtbkt@ks={} \ifvoid\txtbkb@xb@t \else
```

We test whether these is a `\splitbotmark`, if yes, then we will insert it at the top of the next page with formatting.

```
4236 \if!\splitbotmark! \global\let\tb@sbm@exp\relax \else
4237   \xdef\tb@sbm@exp{\noexpand\tbPreMarginHeader
4238     \noexpand\tbMarginHeaderFmt{\splitbotmark}%
4239     \noexpand\tbPostMarginHeader
4240     \noexpand\par\kern3pt}%
4241 \fi
```

Here is the content that will be carried over to the next page, we insert a `\splitbotmark` if it is non-empty (`\tb@tmp@exp`).

```
4242 \global\txtbkt@ks=\expandafter{\tb@sbm@exp
4243   \tb@insertCarryOver{\unvbox\txtbkb@xb@t}}%
4244 \fi
4245 }
```

`\insertpageifcarryover` This macro is use to generate a blank page if there is carry over from the previous page. It is place just after the exercises, and before a new chapter or section. The optional argument allows you to insert something into the new page, if one is automatically created. The default is `\null`.

```
4246 \newcommand{\insertpageifcarryover}[1][\null]{%
```

We begin by starting a new page, the shipout routine of previous page will be initialized and can then get an accurate result for `\ifiscarryover`.

```
4247 \newpage
```

If there is carryover, we create a new page by inserting a content into the page. If there is no carry over, we do now insert any content, and the page will not be created.

```
4248 \ifiscarryover\def\eqeifnext{\csname iftrue\endcsname}%
4249 \PackageInfo{eqexam}{Carry over of content in margin
4250 from page \thepage.\MessageBreak Creating a blank page}\else
4251 \def\eqeifnext{\csname ifffalse\endcsname}\fi\eqeifnext#1\fi}
```

`\setFullWidthHeader` Makes the running header full width.

```
4252 \newcommand{\setFullWidthHeader}%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
4253   \setlength{@tempdima}{%
4254     \evensidemargin+\tbmarparboxwidth+\marginparsep}%
4255   \edef@headoffset{\the@tempdima}%
4256   \def@evenhead{\makebox[0pt]{\makebox[0pt][1]
4257     {\thepage}\hspace{\@headoffset}\hfil\slshape\leftmark}%
4258   \ifmarginsonleft
4259     \def@oddhead{\makebox[0pt]{\makebox[0pt][1]
4260       {\slshape\rightmark}\hspace{\@headoffset}\hfil\thepage}%
4261   \else
4262     \def@oddhead{\slshape\rightmark}\hfil\makebox[0pt]
```

```

4263           {\hspace{\headoffset}\makebox[0pt][r]{\thepage}}}%%
4264     \fi
4265 }

```

## 15.4 In support of solutions at end of document and chapter

A feature that may not be used much is to have solutions at the end of each chapter.

**\chaptersolutions** If `\tb@EndOfChapterExercises` is executed, and `\chaptersolutions` is placed between chapters, we can generate solutions at the end of the chapters, instead of at the end of the book. `\chaptersolutions` is `\let` to `\relax` unless `\tb@EndOfChapterExercises` is executed. In this case `\chaptersolutions` inputs the the .sol file, then then opens it

```

4266 \newif\ifchapterexercises \chapterexercisesfalse
4267 \let\chaptersolutions\relax
4268 \def\tb@EndOfChapterExercises{%
4269   \let\include@solutions@chapter\include@solutions
4270   \def\includeexersolutions{%
4271     \include@solutions@chapter
4272     \global\let\include@solutions\relax
4273   }%
}

```

`\chaptersolutions` is redefined from `\relax`. Input current solutions, close stream, open stream.

```

4274 \def\chaptersolutions{%
4275   \includeexersolutions
4276   \immediate\closeout\ex@solns
4277   \newwrite\ex@solns \global\let\quiz@solns\ex@solns
4278   \immediate\openout\ex@solns \jobname.sol
4279   \ifvspacewithsolns\writeAllAnsAtEnd\fi
4280 }%
4281 }

```

```
4282 \def\writeallsolutions{\let\chaptersolutions\relax}
```

**\exercisesAtEndOfChapter** If you want solutions at the end of each chapter, you'll have to execute this command in the preamble. See `\initChapAfterSolns` for an example of usage.

**afterChapSolns** This comment environment is a convenience for placing content between chapters.

```

4283 \excludecomment{afterChapSolns}
4284 %\includecomment{solnsAtEnd}

```

(2014/05/08) There is a problem with nested comment environments when `solnsAtEnd` contains within it the `\includeexersolutions` command, especially when `multicols` is used. The fix seems to redefine things so that `solnsAtEnd` writes to a different CUT file

```

4285 \def\NewCommentCutFile{\def\CommentCutFile{solnsAtEnd.cut}}
4286 \def\RestoreCommentCutFile{\def\CommentCutFile{comment.cut}}
4287 @ifundefined{BeforeIncludedComment}{%
}

```

```

4288 \long\def\solnsAtEndcomment
4289 #1{\message{Special comment '#1'}%
4290   \csarg\def{\#1}{\endgroup \message{Processing '#1' comment.}%
4291           \NewCommentCutFile\SetUpCutFile
4292           % #2 before SetUp, so we can do renaming.
4293           \message{Comment '#1' writing to \CommentCutFile.}%
4294           \ProcessComment{\#1}}%
4295 \csarg\def{After#1Comment}{\immediate\closeout\CommentStream
4296           \RestoreCommentCutFile\input{\solnsAtEnd.cut}\relax}%
4297 \CommentEndDef{\#1}}
4298 }{\long\def\solnsAtEndcomment
4299 #1{\message{Special comment '#1'}%
4300   \csarg\def{After#1Comment}{\immediate\closeout\CommentStream
4301           \RestoreCommentCutFile\input{\solnsAtEnd.cut}\relax}%
4302   \csarg\def{\#1}{\NewCommentCutFile\BeforeIncludedComment\relax
4303           \ProcessComment{\#1}}%
4304   \CommentEndDef{\#1}}
4305 }
4306 \solnsAtEndcomment{\solnsAtEnd}
4307 \newcommand{\exercisesAtEndOfChapter}{%
4308   \ifeq@nosolutions{\else
4309     \typeout{^^J!!!!!Executing in chapter solutions!!!!^J}
4310     \chapterexercisestrue\tb@EndOfChapterExercises
4311     \ifchapterexercises
4312       \csarg\let{\solnsAtEnd}\@gobble
4313       \excludecomment{\solnsAtEnd}%
4314       \csarg\let{\AftersolnsAtEndComment}\relax
4315       \includecomment{afterChapSolns}\else
4316       \excludecomment{afterChapSolns}\fi
4317   \fi
4318 }
4319 \onlypreamble\exercisesAtEndOfChapter

```

## 15.5 Modifying and restoring the Layout

The book may need a wide page format and use multi-columns to display homework sets, or solutions at the end if the book.

`\setFullWidthLayout` A command to set the page layout for the solutions in the back of the book. Typically, we do away with the wide margins. We also save the current values of the parameters we are changing so we can restore them later.

```

4320 \newcommand{\setFullWidthLayout}{%
4321   \saveBasicLayoutParams
4322   \setlength{\oddsidemargin}{0in}%
4323   \setlength{\evensidemargin}{\oddsidemargin}%
4324   \setlength{\textwidth}{\paperwidth-2in}%
4325   \setlength{\ linewidth}{\paperwidth-2in}%
4326   \setlength{\columnseprule}{0pt}%
4327   \def\evenhead{\thepage\hfil\slshape\leftmark}%

```

```

4328     \def\@oddhead{{\slshape\rightmark}\hfil\thepage}%
4329 }

```

**fullwidhttext** When `\setFullWidthLayout` is in effect, we have the problem of writing text. Originally, I used a `\parbox` with width of `\ linewidth`, but this has its problems when breaking across pages. We have instead an environment for writing; the list environment obeys the current `\ linewidth`, which is set to `\paperwidth-2in`, this latter value may not always be correct (especially when the margins are smaller than 2in).

```

4330 \newenvironment{fullwidhttext}{%
4331 \begin{list}{}{%
4332   \setlength{\labelwidth}{0pt}\setlength{\labelsep}{0pt}%
4333   \setlength{\itemindent}{0pt}\setlength{\itemsep}{0pt}%
4334   \setlength{\topsep}{0pt}\setlength{\parsep}{0pt}%
4335   \setlength{\listparindent}{\parindent}%
4336   \setlength{\leftmargin}{0pt}\setlength{\rightmargin}{0pt}%
4337 }\item\relax\end{list}}

```

**\restorePageLayout** Restore the last saved page parameters.

```

4338 \newcommand{\restorePageLayout}{\newpage
4339   \setlength{\oddsidemargin}{\tb@osms}
4340   \setlength\evensidemargin{\tb@esms}
4341   \setlength{\textwidth}{\tb@tws}
4342   \setlength{\linewidth}{\tb@lws}
4343   \setlength{\columnseprule}{\tb@csr}
4344 }

```

Used by `\setFullWidthLayout` just before the page layout parameters are changed.

```

4345 \newcommand{\saveBasicLayoutParams}{%
4346   \xdef\tb@osms{\the\oddsidemargin}%
4347   \xdef\tb@esms{\the\evensidemargin}%
4348   \xdef\tb@tws{\the\textwidth}%
4349   \xdef\tb@lws{\the\linewidth}%
4350   \xdef\tb@csr{\the\columnseprule}%
4351 }

```

**\initChapAfterSolns** Initializes the environment when solutions appear after each chapter. Example of usage, taken from `fortextbook.ltx`,

```

\begin{afterChapSolns}
\initChapAfterSolns
\section{Solutions to Chapter Exercises}
\begin{fullwidhttext}
We present short solutions to the problems.
\end{fullwidhttext}
\bigskip

```

```

\begin{multicols}{2}\forceNoColor
\chaptersolutions
\end{multicols}
\restoreFromChapAfterSolns
\end{afterChapSolns}

4352 \newcommand{\initChapAfterSolns}{\newpage
4353     \clearTopMargin\clearBotMargin
4354     \setFullWidthLayout
4355 }

\restoreFromChapAfterSolns Restores the saved parameters at the end of the chapter solutions, see above for
an example.

4356 \newcommand{\restoreFromChapAfterSolns}{\newpage
4357     \restorePageLayout\setFullWidthHeader
4358 }

4359 % End of textbook segment
4360 /textbook
4361 *package

```

## 15.6 We shipout in support of *fortextbook*

We shipout *\eqe@tb@shipout* to be placed in the margins on every page.

```

4362 \ifeqfortextbook
4363 \AtBeginDocument{\tb@soln@choice
4364     \ifeqwritetomargins\chkmarginboxwidth
4365     \AddToShipoutPicture{\eqe@tb@shipout}\fi}
4366 \fi
4367 /package
4368 *textbook

```

## 15.7 Modify *eqequestions* environment

We adjust the *eqequestions* environment to minimize spacing between problems.

```

4369 \eqequestionssep{0pt}
4370 \eqequesparsep{0pt}
4371 \eqequesitemsep{0pt}
4372 \eqequeslistparindent{0pt}
4373 \renewenvironment{eqequestions}{%
4374     \begin{list}{}{%
4375         \ifwithinoldoc\let\solnItemMngt\eqeSolnItemMngt\fi
4376         \setlength{\labelwidth}{\eqemargin}%
4377         \setlength{\parsep}{\eqeques@parsep}%
4378         \setlength{\itemsep}{\eqeques@itemsep}%
4379         \setlength{\topsep}{\eqeques@topsep}%
4380         \setlength{\itemindent}{0pt}%
4381         \setlength{\listparindent}{\eqeques@listparindent}%
4382         \ifwithinoldoc\settowidth{\labelsep}{\eqehspannerSoln}\else

```

```

4383     \settowidth{\labelsep}{\eqe@hspannerPrb}\fi
4384     \setlength{\leftmargin}{\labelwidth}%
4385 } \ifwithinsoldoc\global\firstitemtrue\fi\item\relax\{\end{list}}

```

`eqpartsquestions` This environment is used in the SOL file with problems with parts to hang indent the solutions with parts.

```

4386 \newcommand{\eqepquestopsep}[1]{\def\eqepques@topsep{\#1}}
4387 \newcommand{\eqepquesparsesep}[1]{\def\eqepques@parsep{\#1}}
4388 \newcommand{\eqepquesitemsep}[1]{\def\eqepques@itemsep{\#1}}
4389 \eqepquestopsep{\eqepques@itemsep}
4390 \eqepquesparsesep{\eqepques@parsep}
4391 \eqepquesitemsep{\eqepques@itemsep}
4392 \newenvironment{eqpartsquestions}{%
4393     \begin{list}{}
4394     \settowidth{\labelwidth}{\eqe@prtsepSoln\hspace{\tbsolnpartwdth}}
4395     \setlength{\parsep}{\eqepques@parsep}%
4396     \setlength{\itemsep}{\eqepques@itemsep}%
4397     \setlength{\topsep}{\eqepques@topsep}%
4398     \setlength{\itemindent}{0pt}%
4399     \settowidth{\labelsep}{\eqe@hspannerSoln}
4400     \setlength{\leftmargin}{\labelwidth}%
4401 } \item\relax\{\end{list}}

```

## 15.8 Modifications for solutions page

`\gobbletoEndExt` is a command to gobble all content from the current position `\eqExt` down to `\endeqExt`. In the solutions file ends with `\par\medskip`, which we gobble up too. We define `\eqExtArg` to `\thequestionno` so we can use the problem number to filter out the even-problems.

```

4402 \long\def\gobbletoEndExt#1\endeqExt{\gobbletwo}
4403 \def\eqExtArg{\thequestionno}

```

`\autoInsSolns` When creating a book, we can manually create a chapter and insert the solutions, or we can automatically have it done. The manual method is the default, emit `\autoInsSolns` in the preamble to have the solutions inserted automatically. Use `\InputExrSolnsLevel` to tune the section level (`eqexam.def`).

```

4404 \if\load@exerquiz\eqe@NO\DoNotFitItIn\fi
4405 \let\fillInFormatDefault\empty
4406 \def\fbInsSolnsStyle{\def\exerSolnsHeadnToc{}}
4407 \def\autoInsSolns{\let\fbInsSolnsStyle\relax}
4408 \AtBeginDocument{\fbInsSolnsStyle}
4409 \renewcommand{\exerSolnInput}{%
4410     \global\let\webnewpage\relax
4411     \ifsolutionsonly\else\immediate\closeout\ex@solns\fi
4412     \ifeq@nosolutions\else\newpage % 2012-03-14
4413         \iftherearesolutions\eq@solutionshook\eqsolutionshook
4414             \ifsolutionsonly\else\newpage\eq@solutionshook
4415             \eqsolutionshook\fi
4416         \ifx\webnewpage\relax

```

```

4417           \gdef\webnewpage{\global\let\webnewpage\newpage}%
4418           \fi
4419           \priorexsectitle\exerSolnsHeadnToc\priorexslinput
4420           \InputIfFileExists{\jobname.sol}{}{\PackageWarning{exerquiz}
4421             {!!! Solutions to exercises not found}}%
4422           \fi
4423       \fi
4424 }

```

\eqedsplyOnlyFrst The default listing of a problem with multiple parts is to typeset <num>. (<part>). Here, we do not typeset the number after the first time.

```

4425 \setcounter{partno}{1}\edef\firstPartLtr{\the partno}
???? 6/2/11 When part (a) is hidden we need to generate the questions number for the the first non-hidden part. Created \iffrstProbNumShown to help but it not working yet.
4426 \newif\iffrstProbNumShown\frstProbNumShownfalse
4427 \def\tb@insertDecPoint{\ifwithinoldoc\eqedecPointSoln\else
4428   \eqe@decPointMrg\fi}
4429 \newcommand{\eqedsplyOnlyFrst}[2]{\def>thisPart{#2}%
4430   \ifx>thisPart\firstPartLtr\global\frstProbNumShowntrue
4431   \tb@mrgDigitFmt{#1}\tb@insertDecPoint\else
4432   \iffrstProbNumShown\tb@GenProbNum{#1}\else
4433   \global\frstProbNumShowntrue\tb@mrgDigitFmt{#1}%
4434   \tb@insertDecPoint\fi\fi\global\eqeGenProbNumfalse
4435 }

```

\displayProbNumOnce If a part is carried over to the next page, it may be necessary to manually force the display of the first digit.

```

\insMidMarg{\displayProbNumOnce}

4436 \newif\ifeqeGenProbNum \eqeGenProbNumfalse
4437 \newcommand{\displayProbNumOnce}{\global\eqeGenProbNumtrue} %
4438 \% \def\tb@GenProbNum#1{\ifeqeGenProbNum#1\eqe@decPointMrg\else
4439 \def\tb@GenProbNum#1{\ifeqeGenProbNum#1\tb@insertDecPoint\else
4440   \phantom{#1\tb@insertDecPoint}\fi}%

```

4441 \def\sq@priorhook{\medskip}

Adjustments of spacing between problems \eqexerskip, and the check for enough room for the next problem.

4442 \def\default@fvsizeskip{.1}

The skip prior to the beginning of an exercise

4443 \aboveexskip{0pt}

The skip after the end of an exercise

4444 \belowexskip{0pt}

The skip in the solutions file following an exercise OR a part of an exercise The text of this command should be a single token, that's why I've enclosed it in braces. (There is a \gobbletwo that gobbles it up for the `studented` option.)

```
4445 \renewcommand\belowexsolnskip{}}
```

We remove the `\mark` from this definition, see original definition in `eqexam.def`

```
4446 \renewcommand\exerSolnHeader[3]{%
4447   \ifeqforpaper\else\webnewpage\fi%\par
4448   \noindent\@ifundefined{hypertarget}%
4449     {\#3}{\hypertarget{\#2}{\#3}\relax}\solnhskip
4450 }
```

This causes the `eqexam` environment to write the user friendly name of the exam even if there is only one exam.

```
4451 \def\numberOfP@rts{0}
```

## 15.9 Some Convenience/Formatting Commands

`\preExamSolnHead` These are redefinitions of commands defined in `eqexam`, They control the vertical  
`\examSolnHeadFmt` spacing before and after a heading in the solutions at the end of the book, as well  
`\postExamSolnHead` as the formatting.

```
4452 \renewcommand{\preExamSolnHead}{\medbreak\noindent}
4453 \renewcommand{\examSolnHeadFmt}[1]{\textbf{\#1}}
4454 \renewcommand{\postExamSolnHead}{\smallskip}
```

`\wrtChapSolnHead` Writes a chapter heading to the solution file, usage,

```
\wrtChapSolnHead{The New {\eqexam}}
4455 \newcommand{\wrtChapSolnHead}[1]{%
4456   \writeT@SolnFile{%
4457     \protect\preChapSolnHead
4458     \protect\chapHeadSolnFmt{\protect\ftbFmtChapter{\thechapter}\#1}%
4459     \protect\postChapSolnHead
4460 }}
```

`\preChapSolnHead` Same as above, except for chapter headings.

```
\chapHeadSolnFmt 4461 \newcommand{\preChapSolnHead}{\bigbreak\noindent}
\postChapSolnHead 4462 \newcommand{\chapHeadSolnFmt}[1]{\large\textbf{\#1}}
4463 \newcommand{\postChapSolnHead}{\medbreak}
```

`\ftbFmtChapter` This command may (optionally) insert the chapter number into the chapter title passed to `\wrtChapSolnHead`. The default is to pass the chapter name ("Chapter") and chapter number. If you say `\let\ftbFmtChapter\gobble`, the chapter name and number will not appear. You can redefine this command as desired.

```
4464 \newcommand{\ftbFmtChapter}[1]{\chapname\space#\#1.\space\ignorespaces}
```

In the solution manual, all these chapter commands may be redefined like so

```
\let\preChapSolnHead\relax
\let\chapHeadSolnFmt\chapter
```

```
\let\ftbFmtChapter@gobble
\let\postChapSolnHead\relax
```

In fact, let's make this into a command.

- \convertChapHeadToChapters** In the solutions manual, the chapter headings will become chapters of the manual, rather than just a bold faced heading.

```
4465 \newcommand{\convertChapHeadToChapters}{%
4466   \let\preChapSolnHead\relax
4467   \let\chapHeadSolnFmt\chapter
4468   \let\ftbFmtChapter@gobble
4469   \let\postChapSolnHead\relax
4470 }
```

- \probSet** A simple command to announce the problem set.

```
\subsection*{\probSet{\thesection}}
```

See also the definition for the `probset` environment below.

```
4471 \newcommand{\probSet}[1]{Problem Set #1}
```

- \annotPage** Use to annotation the page number onto a solution heading, for example,

```
\begin{exam}[\thesection. Another Section\annotPage]{\autoExamName}
```

or using the `probset` environment defined below

```
\begin{probset}{\thesection} Setting the page layout\annotPage
```

```
4472 \newcommand{\annotPage}{\protect\annotThePage{\thepage}}
```

```
4473 \newcommand{\annotThePage}[1]{\space(page\protect^#1)}
```

## 15.10 The probset and example environments

We define two environments based. The first (`probset`) is based on the `exam` environment; the second (`example`) is based on the `exercise` environment.

- probset** A convenience environment, it is the `exam` environment, renamed, with different arguments. #1 is the heading that will appear in the margins, and #2 is the heading to appear in the back of the book.

```
4474 \def\noProbHeader{NPH}
4475 \newenvironment{probset}[2][\probSet{\thesection}]{%
4476   \exam[#2]{\autoExamName}\ifx#1\noProbHeader\else
4477   \protected@edef\ftb@tmp@exp{\noexpand\insProbHead{#1}}%
4478   \ftb@tmp@exp\fi}{\endexam}

4479 \newcounter{exempleno}[section]
4480 \renewcommand{\theexempleno}{\arabic{section}.\arabic{exempleno}}
```

**Note:** The counter is `exempleno` and is designed to show the section number and example number, and to reset at each section. To change the definition of

`\theexamplenumber` to reflect the chapter number followed by the example number, and resetting at the beginning of each new chapter, the following code is needed.

```
\usepackage{remreset}
\@removefromreset{examplenumber}{section}
\renewcommand{\theexamplenumber}{\arabic{chapter}.\arabic{examplenumber}}
\@addtoreset{examplenumber}{chapter}
```

`\examplenumber` is the label placed on the example.

```
4481 \newcommand{\examplenumber}{Example}
```

`example` A simple example environment, based on the `exercise` environment.

```
4482 \newenvironment{example}{\medskip
4483   \belowexskip{\medskipamount}\aboveexskip{\medskipamount}%
4484   \makeRoomForProb{\@baselineskip\baselineskip}{}%
4485   \renewcommand\exlabel{Example}%
4486   \renewcommand\exlabelformat{\textbf{\exlabel~\theexamplenumber.}}%
4487   \let\eq@fititin\eqfititin
4488   \renewcommand\exrtnlabelformat{$\square$}%
4489   \def\eqexheader@wrapper{\eqexheader}%
4490   \SolutionsAfter
4491   \begin{exercise}[\examplenumber]\end{exercise}}
```

`example*` An example environment with parts.

```
4492 \newenvironment{example*}{\medskip
4493   \belowexskip{\medskipamount}\aboveexskip{\medskipamount}%
4494   \makeRoomForProb{\@baselineskip\baselineskip}{}%
4495   \renewcommand\exlabel{Example}%
4496   \renewcommand\exlabelformat{\textbf{\exlabel~\theexamplenumber.}}%
4497   \let\eq@fititin\eqfititin
4498   \renewcommand\exrtnlabelformat{$\square$}%
4499   \def\eqexheader@wrapper{\eqexheader}%
4500   \SolutionsAfter
4501   \begin{exercise*}[\examplenumber]\end{exercise*}}
```

We set some parameters, to values better suited for the option.

```
4502 \setDefaultfvsizeskip{.1}
4503 \nbaselineskip{4}
```

## 15.11 Commands in support of Solution Manuals

Generally, the solution manual source file should have the same packages as the source file for the book itself, perhaps with a few exceptions, but definitely the `eqexam` package is required with its `fortextbook` option.

At this time, we provide only two commands, these are `\ftbInputBookAux` and `\ftbInputSolnFiles`.

`\ftbInputBookAux` This command is used to input the auxiliary files of the master source file. It takes one argument, the name of the master source file (`myBook.ltx` or `myBook.tex`). If the extension is not present, it is assumed to be `.tex`.

```

4504 \newcommand{\ftbInputBookAux}[1]{%
4505     \filename@parse{#1}\@ifundefined{filename@ext}{%
4506         {\def\filename@ext{tex}}{}%
4507     \xdef\tbBaseName{\filename@base}%
4508     \xdef\tbSourceFile{\filename@base.\filename@ext}%

```

In the next 4 lines, we save `\@writefile` and `\@setckpt`, and `\let` them to `\@gobbletwo`. We restore their definitions after we input the aux files. We include the aux files of the source file in case there are some cross references in the solution files, or the body of the text would like to refer back to the original book. (Seems unlikely.)

```

4509     \let\save@writefile\@writefile
4510     \let\@writefile\@gobbletwo
4511     \let\save@setckpt\@setckpt
4512     \let\@setckpt\@gobbletwo
4513     \makeatletter
4514     \InputIfFileExists{\tbBaseName.aux}{%
4515         \PackageInfo{eqexam}{%
4516             {Inputting auxiliary files of\MessageBreak\tbSourceFile}%
4517         }%
4518         \PackageError{eqexam}{%
4519             {Auxiliary files for \tbSourceFile\space were not found}%
4520             {Compile the source file \tbSourceFile\space
4521                 three times\MessageBreak%
4522                 to create the required auxiliary files.}%
4523         }%
4524     \makeatother

```

The solution files really shouldn't have a label, but if we do we'll save the L<sup>A</sup>T<sub>E</sub>X definition of `\label`, and `\let` it two `\@gobble`. Within the body of the solutions, the command `\ftblabel` may be used to cross reference, if needed.

```

4525     \global\let\ftblabel\label
4526     \let\label\@gobble
4527     \let\@writefile\save@writefile
4528     \let\@setckpt\save@setckpt
4529 }
4530 \onlypreamble\ftbInputBookAux

```

`\restorelabel` These two are used to restore the usual definition of `\label`, and to cancel it out `\gobblelabel` by letting it to `\@gobble`.

```

4531 \newcommand{\restorelabel}{\global\let\label\ftblabel}
4532 \newcommand{\gobblelabel}{\let\label\@gobble}

```

`\ftbInputSolnFiles` In the body of the text, place `\ftbInputSolnFiles` in vertical mode. This will input the `.sol` file of the master source document. The optional argument is the name of the solution file. The default name is `\tbBaseName.sol`, where `\tbBaseName` was defined in `\ftbInputBookAux`. If no extension is specified, an extension of `.sol` is assumed. The original `.sol` may have changed its name, if

someone renamed it (to keep it from being overwritten). The solution file may be editing (by hand) as needed.

```

4533 \newcommand{\ftbInputSolnFiles}[1][\tbBaseName.sol]{%
4534   \filename@parse{#1}@\ifundefined{\filename@ext}{%
4535     {\def\filename@ext{sol}}{}%
4536   \xdef\tbBaseName{\filename@base}%
4537   \xdef\tbSourceFile{\filename@base.\filename@ext}%
4538   \InputIfFileExists{\tbBaseName.sol}{%
4539     \PackageInfo{eqexam}%
4540       {Inputting solutions file \tbBaseName.sol\MessageBreak}%
4541     }{%
4542       \PackageError{eqexam}%
4543         {Solutions file for \tbSourceFile\space was not found}%
4544         {Compile the source files three times}%
4545     }%
4546   }%
4547 % End of textbook segment
4548 </textbook>
4549 <*ftbsty>
```

## 16 **fortextbook** Style File

One person said it would be nice to separate `eqexam` from the `fortextbook` option, and have `fortextbook` as a `separate` style (package). Rather than spending tens of hours separating them I create a simple “wrapper” package, which simply calls `eqexam` with the `fortextbook` option along with all the recommended options.

**Usage:**

```
\documentclass[twoside,letterpaper]{book}
\usepackage[fleqn]{amsmath}
\usepackage{fortextbook}
...
```

Below is the style.

```

4550 \NeedsTeXFormat{LaTeX2e}
4551 \ProvidesPackage{fortextbook}
4552 [2012/03/14 v1.0 A fortetextbook Package (dps)]
4553 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{eqexam}}
4554 \ProcessOptions
4555 \RequirePackage[%]
4556   ftbsolns,fortetextbook,usecustomdesign,
4557   forcolorpaper,noseparationrule,usexkv
4558 ]{eqexam}
```

In support of this style, I’ve also defined `\NoSolutions` to compile the document without creating the solutions at the end of the file (this reduces the amount of IO when compiling). I’ve also defined a special option `nocustomdesign` which cancels out the `usecustomdesign` option.

```
4559 % End of ftbsty segment
4560 
```

```
4561 <*package>
```

---

**Input eqtextb.def.** Back in the main package, we choose this point to input the `fortextbook` code (`eqtextb.def`) if the `fortextbook` option is taken.

```
4562 \edef\ftbInputEqTextb{\ifeqfortextbook\noexpand
4563     \InputIfFileExists{eqtextb.def}{}{}\fi}
4564 \ftbInputEqTextb
```

---

## 17 `xkeyval` Extensions

We load this material if `xkeyval` exists, and if the document author has specified the `usexkv` option.

2014/12/19 Now, the `usexkeys` is on by default.

```
4565 \%\\IfFileExists{xkeyval}{%
4566 %     \\if\\eq@usexkeys\\eqe@YES\\RequirePackage{xkeyval}\\else
4567 %     \\endinput\\fi}{\\endinput}
```

We redefine selected commands if the user has specified the `usexkv` option.

### New options for `\fillin`

`underline` Underline the fillin

`u, b` Legacy parameters, underlines (u) or leaves a blank space (b)

`boxed` Boxes in the response region

`boxpretext` When boxed is use, use this to insert text in front of the answer, for example, x=

`boxsize` When boxed is taken, use boxsize to set the size of the box; permissible choices are tiny, scriptsize, footnotesize, small, normalsize, large, Large, LARGE, huge, Huge

`align` Align the answer within the response region, permissible values are l, c, r.

`color` The color of the response (named color)

`format` Special formatting for the answer, the default is `\bfseries`

`enclosesoln` This Boolean key only takes effect when the `boxed` key is used, and when either the `nosolutions` or the `vspacewithsolns` option is taken. When these conditions are met, a box is created around the solution (the third parameter of `\fillin`); the solution is enclosed in a `\phantom` so it is not seen, but the dimensions of the solution are used. This key allows you to create a box of arbitrary dimension.

- fitwidth** The `fitwidth` option uses the natural width of the answer to create the fillin when the `answerkey` option is in effect; otherwise it uses the second parameter #2.
- parbox** The `parbox` parameter may be used to create a multiline `\fillin` box. The value of `parbox` is the same as the first three parameters of the L<sup>A</sup>T<sub>E</sub>X command `\parbox`, e.g., `parbox={[t] [.5in] [t]}`. The value needs to be enclosed in braces.
- hiddenbox** When the `boxed` option is used, this option resets the `\fbox` parameters to `0pt`, making the box “hidden.”

Below are the `xkeyval` definitions of the keys recognized by `\fillin`. Add some logic to the `underline` key, now it is equivalent to the `b` key.

```

4568 \define@boolkey{eqFillin}{underline}[true]{}
4569 \define@key{eqFillin}{u}[]{\KV@eqFillin@underline true}
4570 \define@key{eqFillin}{b}[]{\KV@eqFillin@underline false}
4571 \define@boolkey{eqFillin}{boxed}[true]{}
4572 \define@key{eqFillin}{boxpretext}[]{\def\eq@fillintext{\#1}}
4573 \let\eq@fillintext\empty

```

If the user just says `parbox`,... the value of `\eq@fillinparbox` is `\relax`. If `parbox` does not appear in the option list, `\eq@fillinparbox` has a default value of `\empty`. In this way, we can distinguish between `parbox` with the empty value, and `parbox` not present at all.

```

4574 \define@key{eqFillin}{parbox}[\relax]{\def\eq@fillinparbox{\#1}}
4575 \let\eq@fillinparbox\empty
4576 \define@key{eqFillin}{hiddenbox}[]{%
4577   \def\eq@fillinhiddenbox{%
4578     \setlength{\fboxrule}{0pt}\setlength{\fboxsep}{0pt}}}
4579 \let\eq@fillinhiddenbox\empty
4580 \define@boolkey{eqFillin}{enclosesoln}[true]{}
4581 \define@choicekey+{eqFillin}{boxsize}{tiny,scriptsize,footnotesize,%
4582   small,normalsize,large,Large,LARGE,huge,Huge}[normalsize]{%
4583   \def\eq@eqFillin@boxsize{\text{\csname#1\endcsname\strut}}}{%
4584 }{\PackageWarning{eqexam}{Bad choice for boxsize, permissible values
4585   are tiny, scriptsize, footnotesize, small, normalsize,
4586   large, Large, LARGE, huge and Huge. Try again}}
4587 \def\eq@eqFillin@boxsize{\text{\normalsize\strut}}
4588 \define@key{eqFillin}{fboxsep}[3pt]{\def\eq@fillin@fboxsep{\#1}}
4589 \def\eq@fillin@fboxsep{3pt}
4590 \define@choicekey+{eqFillin}{fontsize}{tiny,scriptsize,footnotesize,%
4591   small,normalsize,large,Large,LARGE,huge,Huge}[normalsize]{%
4592   \def\eq@eqFillin@fontsize{\text{\csname#1\endcsname}}}{%
4593 }{\PackageWarning{eqexam}{Bad choice for boxsize, permissible values
4594   are tiny, scriptsize, footnotesize, small, normalsize,
4595   large, Large, LARGE, huge and Huge. Try again}}
4596 \def\eq@eqFillin@fontsize{\ifmmode\else\normalsize\fi}
4597 \define@key{eqFillin}{color}{\eq@fillinColor}{\edef\eq@fillin@color{\#1}}
4598 \define@choicekey+{eqFillin}{align}{\val\nr}{%
4599   {l,r,c}}{\eq@eqFillin@align@default}{%

```

```

4600      \def\eq@eqFillin@align{\#1}%
4601      \ifcase\nr\relax
4602          \def\eqe@align@hfill{}\or
4603          \def\eqe@align@hfill{\hfill}\or
4604          \def\eqe@align@hfill{\hfil}\fi
4605      }%
4606      \PackageWarning{eqexam}{Bad choice for align, permissible values
4607      are l, r, and c. Try again}%
4608 \let\eqe@align@hfill\relax

```

`defaultalign` is used to change the values of the default macros `\eq@eqFillin@align@default` and `\eqe@align@hfill@default` for the `align` key together.

```

4609 \define@choicekey+{eqFillin}{defaultalign}[\val\nr]{l,r,c}[c]%
4610     \def\eq@eqFillin@align@default{\#1}%
4611     \ifcase\nr\relax
4612         \def\eqe@align@hfill@default{}\or
4613         \def\eqe@align@hfill@default{\hfill}\or
4614         \def\eqe@align@hfill@default{\hfil}\fi
4615     }%
4616     \PackageWarning{eqexam}{Bad choice for defaultalign, permissible
4617     values are l, r, and c. Try again}%
4618 \setkeys{eqFillin}{defaultalign=c}

```

`\fillInFormatDefault` is the default fill-in format

```

4619 \renewcommand{\fillInFormatDefault}{\normalfont}
4620 \define@key{eqFillin}{format}[\fillInFormatDefault]{%
4621     \def\eq@fillin@format{\#1}%
4622 \def\eq@fillin@format{\bfseries}
4623 \def\eqe@fbox@corr{\#1-2\fboxsep-2\fboxrule}
4624 \define@boolkey{eqFillin}{fitwidth}[true]{}

```

`boxcmd` The `boxcmd` key is used to define a boxing command. The default is either `\boxed` or `\fbox`. You can say `boxcmd={\fboxcolor{blue}{yellow}}` to obtain a box with a blue frame and yellow background.

```

4625 \@ifundefined{boxed}{%
4626     \def\eq@fillin@defaultbox{\fbox}%
4627     \def\eq@fillin@boxcmd{\fbox}%
4628 }%
4629     \def\eq@fillin@defaultbox{\boxed}%
4630     \def\eq@fillin@boxcmd{\boxed}%
4631 }

```

`ulcmd` The `ulcmd` key is used to define a underlining command. The default is either `underline` or `underbar`. You can say `ulcmd=underline` to obtained an underline using `\underline`.

```

4632 \define@key{eqFillin}{boxcmd}%
4633     [\eq@fillin@defaultbox]{\def\eq@fillin@boxcmd{\#1}}
4634 \ifundefined{underbar}{%
4635     \def\eq@fillin@defaultul{\underline}%
4636     \def\eq@fillin@ulcmd{\underline}%

```

```

4637      }{%
4638          \def\eq@fillin@defaultul{\underbar}%
4639          \def\eq@fillin@ulcmd{\underbar}%
4640      }
(2017/01/28) Added custom underline option, the author must define \ulcustom
and specify ulcmd=custom.

4641 \edef\ulcustom{\expandafter\noexpand\eq@fillin@ulcmd}
4642 \edef\temp@exp{\noexpand
4643 \define@choicekey{eqFillin}{ulcmd}
4644     {underbar,underline,custom}[\eq@fillin@defaultul]}
4645 \temp@exp{\def\@rgi{#1}\def\eq@custom{custom}\ifx\@rgi\eq@custom
4646     \def\eq@fillin@ulcmd{\@nameuse{ulcustom}}\else
4647     \def\eq@fillin@ulcmd{\@nameuse{#1}}\fi
4648 }{\PackageWarning{aeb}{Bad choice for ulcmd, permissible values
4649     are underbar and underline. Try again}}
lift (2013/02/16) lift lifts (actually lowers) the underline by the amount specified.
autolift autolift measures the depth of the content and lifts (actually lowers) the under-
addtoautolift line by that amount. addtoautolift works with autolift to add the specified
amount to the amount of lift as calculated by autolift.

4650 \define@key{eqFillin}{lift}[-1sp]{\def\eq@fillin@lift{#1}}
4651 \define@boolkey{eqFillin}{autolift}[true]{} %
4652 \define@key{eqFillin}{addtoautolift}[Opt]{%
4653     \def\eq@fillin@addtoautolift{#1}}

```

The macro `\eqe@getiiiOpts` is based on early parsing code of `\parbox`. It picks up three optional parameters and saves their values under the commands `\eqe@opts@argi`, `\eqe@opts@argii`, `\eqe@opts@argiii`. We are interested in `\eqe@opts@argiii`, which specifies the depth of the `\parbox`. If the `boxed` option is taken, we reduce the value of `\eqe@opts@argiii` by `2\fboxsep+2\fboxrule` so that the height will be exactly as specified. The macro `\eqe@getiiiOpts` is used with the `parbox` option of `\fillin`. The macro `\eqe@getiiiOpts` has syntax:

```

\eqe@getiiiOpts[pos][height][inner-pos]

4654 \def\eqe@getiiiOpts{%
4655     \@ifnextchar[%
4656         \i@eqe@getiiiOpts
4657         {\iii@eqe@getiiiOpts{c}{\relax}[s]}}
Get pos
4658 \def\i@eqe@getiiiOpts[#1]{%
4659     \@ifnextchar[%
4660         {\iii@eqe@getiiiOpts{#1}}%
4661         {\iii@eqe@getiiiOpts{#1}{\relax}[s]}}
Get height
4662 \def\iii@eqe@getiiiOpts[#1][#2]{%
4663     \@ifnextchar[%
4664         {\iii@eqe@getiiiOpts{#1}{#2}}%
4665         {\iii@eqe@getiiiOpts{#1}{#2}[#1]}}

```

Get *inner-pos*

```
4666 \def\iii@eqe@getiii@opts#1#2[#3]{%
4667   \def\eqe@opts@argi{#1}%
4668   \def\eqe@opts@argii{#2}%
4669   \def\eqe@opts@argiii{#3}}
```

### Redefine the `\fillin` command

`\fillin` Re-worked `\fillin` to have `xkeyval` in the optional first parameter. The syntax is illustrated below.

```
\fillin[
    underline=true|false,u,b,boxed=true|false,boxpretext=<text>,
    align=l|r|c,boxsize=\tiny|\normalsize|\large|\Huge|,
    color=<namedcolor>,format=<\bfseries|\ttfamily|\Large|whatever>
]{<width>}{<ans>}
```

`\setfillinDefaults` `\setfillinDefaults` sets any default options for `\fillin` the document author wants.

```
4670 \newcommand{\setfillinDefaults}[1]{\def\eqe@argi{#1}\ifx\eqe@argi\empty
4671   \let\eqe@setfillinDefaults\empty\else
4672   \def\eqe@setfillinDefaults{#1}\fi}
4673 \let\eqe@setfillinDefaults\empty
```

`\fillineol` The `\fillineol` command is used to extend the `\fillin` box or line to the end of the line.

```
\fillineol*{\langle phrase \rangle}[\langle opts \rangle]{\langle ans \rangle}
```

Normally, `\fillineol` is placed at the beginning of a line. The command measures the length of `\langle phrase \rangle`, subtracts this from `\ linewidth` and uses this value as the width of the underlying `\fillin`. When the star-form is used, the `collectbox` package is required; in the star-form, `\langle phrase \rangle` can contain verbatim text.

```
4674 \AtBeginDocument{\ifpackageloaded{collectbox}
4675   {\let\eqe@cb\eqe@YES}{\let\eqe@cb\eqe@NO}}
4676 \def\fillineolTooLongMsg{\PackageWarning{eqexam}{%
4677   The 'phrase' you are measuring is longer than\MessageBreak
4678   \string\linewidth. Changing length to Opt in hopes you\MessageBreak
4679   can fix things}}
4680 \def\fillineolNoCBMsg{\PackageWarning{eqexam}{%
4681   For the \string\fillineol* space form, the
4682   collectbox package\MessageBreak
4683   is required, but not loaded at this time.\MessageBreak
4684   Switching to \string\fillineol\space in hopes you
4685   load collectbox\MessageBreak
4686   next time or you remove the star-option if not\MessageBreak
4687   really needed}}
4688 \newcommand\fillineol{\@ifstar{\ifx\eqe@cb\eqe@YES
4689   \let\eqe@next\cbfillineol\else
4690   \def\eqe@next{\fillineolNoCBMsg\fillineol@i}\fi}
```

```

4691 \eqe@next}{\fillineol@i}}
4692 \newcommand{\fillineol@i}[1]{\bgroup\setbox\z@\hbox{#1}\fillineol@ii}
4693 \newcommand\fillineol@ii[2][]{%
4694 \setlength\eqetmplengthb{\linewidth-\wd\z@}%
4695 \ifdim\eqetmplengthb<0pt\eqetmplengthb0pt\fillineolTooLongMsg\fi
4696 \unhbox\z@\fillin[#1]{\eqetmplengthb}{#2}\egroup}

```

Allow the third argument to have verbatim text as well.

```

4697 \newcommand\cbfillineol{\bgroup\collectbox{\@tempboxa}%
4698 {\setlength{\eqetmplengthb}{\linewidth-\wd\@tempboxa}%
4699 \ifdim\eqetmplengthb<0pt\eqetmplengthb0pt\fillineolTooLongMsg\fi
4700 \unhbox\@tempboxa\cbfillineol@ia}%
4701 \newcommand\cbfillineol@ia[1][]{\def\@rgi{#1}\cbfillineol@ib}%
4702 \newcommand\cbfillineol@ib{\collectbox{\@tempboxa}%
4703 {\cbfillineol@i[\@rgi]}%
4704 \newcommand\cbfillineol@i[1][]{\fillin[#1]{\eqetmplengthb}%
4705 {\unhbox\@tempboxa}\egroup}

```

\fillin We finally begin the \fillin command.

```

4706 \renewcommand{\fillin}[3][]{\begingroup
\ifsp@expand is defined in spdef package. This is a version if \ifsp that expands
correctly in an \edef.

```

```
4707 \expandafter\let\expandafter\ifsp\csname ifsp@expand\endcsname
```

Get the keys indicated by the document author.

```

4708 \setkeys{eqFillin}{boxsize,underline=true,boxed=false,%
4709 boxpretext,color,format,enclosesoln=false,fitwidth=false,lift,%
4710 autolift=false,addtoautolift}%
4711 \ifx\eqe@setfillinDefaults\empty\else
4712 \protected@edef\eq@temp@exp{\noexpand
4713 \setkeys{eqFillin}{\eqe@setfillinDefaults}}%
4714 \eq@temp@exp
4715 \fi
4716 \protected@edef\eq@temp@exp{\noexpand\setkeys{eqFillin}{#1}}%
4717 \eq@temp@exp
4718 \fboxsep\eq@fillin\fboxsep\relax

```

If boxed, we turn underlining off

```
4719 \ifKV@eqFillin@boxed\KV@eqFillin@underlinefalse\fi
```

Put \eq@fillin@lift to -2sp as a signal not to use the lift value in the case  
the author specified autofill and lift.

```
4720 \ifKV@eqFillin@autolift\def\eq@fillin@lift{-2sp}\fi
```

Get the second parameter.

```

4721 \edef\eqe@argii{#2}\ifx\eqe@argii\empty\else
4722 \ifdim\eqe@argii=0pt\let\eqe@argii\empty\fi\fi

```

We reset \fboxrule and \fboxsep as needed.

```
4723 \eq@fillinhiddbbox
```

If the document author uses the `hiddenbox` option, this option assumes the `boxed` option as well so we'll set `\KV@eqFillin@boxedtrue` to signal the `boxed` option.

```
4724     \ifx\eq@fillinhiddenbox\empty\else
4725         \KV@eqFillin@boxedtrue\fi
```

If the `parbox` option is taken, we define the third parameter to be wrapped in a `\parbox`.

```
4726     \ifx\eq@fillinparbox\empty\def\eqe@argiii{\#3}\else
```

If `parbox` is specified, we make `align=l` the default.

```
4727     \ifx\eqe@align@hfill\relax
4728         \def\eqe@eqFillin@align{l}\def\eqe@align@hfill{}\fi
```

If `parbox` is specified, we get its three optional parameters so we can manipulate the width parameter.

```
4729     \expandafter\eqe@getiii0pts\eq@fillinparbox\relax
```

Now, if this is to be `boxed`, we reduce the height of the box (`\boxed` increases the height by  $2\text{fboxrule}+2\text{fboxrule}$

```
4730     \ifKV@eqFillin@boxed
```

`\eqe@opts@argii` has a value of `\relax` if the document author did not specify a height for the box.

```
4731     \expandafter\ifx\eqe@opts@argii\relax\else
4732         \edef\eqe@opts@argii{\expandafter
4733             \eqe@fbox@corr\expandafter{\eqe@opts@argii}}\fi
4734     \fi
```

We need to feed `\parbox` the parameters it expects, so, if the height parameter is not given, we just pass the first argument; otherwise, we pass all three parameters.

```
4735     \edef\eqe@parboxOptArgs{[\eqe@opts@argi]%
4736         \expandafter\ifx\eqe@opts@argii\relax\else
4737             [\eqe@opts@argii][\eqe@opts@argiii]\fi}%
```

Now we build the third parameter, `\eqe@argiii`.

```
4738     \def\eqe@argiii{\expandafter\parbox\eqe@parboxOptArgs[\eqe@bw]}%
```

We insert `\eqe@align@hfill`, which is synchronized to the value of the `align` key to move the `\parbox` contents to left aligned, centered, or right aligned. `\eqe@align@hfill` will only be effective if #3 is enclosed in a narrower box.

```
4739     {\eqe@align@hfill\ifKV@eqFillin@boxed\eq@fillintext\fi#3}%
4740     \fi
```

If `\eqe@align@hfill` is still equal to `\relax`, give it the default value.

```
4741     \ifx\eqe@align@hfill\relax
4742         \def\eqe@eqFillin@align{c}%
4743         \edef\eqe@align@hfill{\eqe@align@hfill@default}\fi
4744     \ifmmode\let\@eqmath\ensuremath\else\let\@eqmath\text\fi
```

We re-calculate the width of the formatted box

```
4745     \ifx\eq@fillinparbox\empty
4746         \ifx\eqe@argii\empty
```

If no `parbox` option and if the second argument is empty, we set width based on the natural width of #3

```

4747      \settowidth{\eqetmplengthb}{\eq@eqFillin@fontsize
4748          \eq@fillin@format\ifKV@eqFillin@boxed\eq@fillintext\fi
4749          \eqe@argiii}\}%
4750          \ifKV@eqFillin@boxed
4751              \setlength{\eqetmplengthb}{%
4752                  \eqetmplengthb+2\fboxsep+2\fboxrule}\}%
4753          \fi
4754      \else

```

If #2 is nonempty, we use this value.

```

4755      \setlength{\eqetmplengthb}{#2}\}%
4756      \fi
4757  \else

```

`parbox` option with empty second argument, use `\linewidth`. for width

```

4758      \ifx\eqe@argii\@empty
4759          \setlength{\eqetmplengthb}{\linewidth}\%
4760          \PackageWarning{eqexam}{Parameter '#2
4761              is empty with parbox option,\MessageBreak
4762              using \string\linewidth\space for width\}%
4763          }%
4764      \else

```

`parbox` option with second argument, use #2 for width

```

4765      \setlength{\eqetmplengthb}{#2}\}%
4766      \fi
4767  \fi

```

Return `\ifsp` to its default definition.

```
4768  \expandafter\let\expandafter\ifsp\csname ifsp@default\endcsname
```

Save the final calculated width as `\eqe@bw`.

```
4769  \edef\eqe@bw{\the\eqetmplengthb}\%
```

Set the underline option, ...

```

4770  \ifKV@eqFillin@underline\let\@fillinFmt\eq@fillin@ulcmd
4771  \else\let\@fillinFmt\relax\fi

```

however, if `parbox` is specified, we remove the underlining, if any.

```

4772  \ifx\eq@fillinparbox\@empty\else
4773      \ifKV@eqFillin@underline\let\@fillinFmt\relax
4774  %
4775      \ltx\@fillinFmt\underbar\let\@fillinFmt\relax
4776      \PackageInfo{eqexam}{Removing underline option, not permissible
4777      \MessageBreak with parbox option}\%
4778  \fi\fi

```

**Build the `\fillin` box.** After the preliminaries, we create the requested answer field. We begin by building the answer field for the case of `\ifeq@proofing` is true (which occurs when the `answerkey` is used).

```

4778      \ifeq@proofing
4779          \ifKV@eqFillin@fitwidth

```

If the `fitwidth` option is taken, we measure the width of the box. Ignored when the `parbox` option is used.

```

4780          \settowidth{\eqetmplengthb}{\eqmath{\eq@fillin@format
4781              \ifx\eq@fillinparbox\empty\ifKV@eqFillin@boxed
4782                  \eq@fillintext\fi\fi\eqe@argiii}}%

```

If boxed, we increase the width by  $2\fboxsep+2\fboxrule$ ; when content is `boxed`, the dimensions are reduced.

```

4783          \ifKV@eqFillin@boxed
4784              \setlength{\eqetmplengthb}{%
4785                  \eqetmplengthb+2\fboxsep+2\fboxrule}%
4786          \fi
4787          \edef\eqe@bw{\the\eqetmplengthb}%
4788      \fi

```

We build the fill-in field for the case of `boxed`.

```

4789          \ifKV@eqFillin@boxed
4790              \ifmmode\let\eqmath\ensuremath\else\let\eqmath\text\fi
4791 %
4792              \mbox{\eq@fillin@format\ensuremath{\boxed{%
4793 %
4794                  \eq@fillin@format\ensuremath{\eq@fillin@boxcmd{%
4795                      \eq@fillin@format\ensuremath{\eq@fillin@boxsize
4796                      \eq@fillinFmt{\eq@eqFillin@fontsize % dpsf0214
4797                      \ifKV@eqFillin@boxed
4798                          \edef\eqe@bw{\eqe@fbox@corr{\eqe@bw}}%

```

When the boxed option is taken, we adjust the width of the `\makebox` to get the desired width #2.

```

4799          \makebox[\eqe@bw]{\eq@eqFillin@align}{\strut
4800              \eqmath{\eq@fillin@format\color{\eq@fillin@color}}%
4801              \ifx\eq@fillinparbox\empty
4802                  \eq@fillintext\fi\eqe@argiii}}%
4803          }% end \eq@fillinFmt
4804      }%} end \mbox
4805      \setlength{\tempdima}{\ht0+\dp0}%
4806      \xdef\fillinTotalHeight{\the\tempdima}%
4807      \mbox{\unhbox\z@}%
4808  \else

```

The content is not to be boxed.

```

4809          \ifmmode\let\eqmath\ensuremath\else\let\eqmath\relax\fi
4810          \setbox\z@\hbox{\eq@eqFillin@fontsize % dpsf0214

```

A value of `-1sp` signals that `lift` has not been specified, nor has `autofill` been specified. So we use the usual code for underlining.

```

4811          \ifdim\eq@fillin@lift=-1sp\relax
4812              \eq@fillinFmt{\makebox[\eqe@bw]{\eq@eqFillin@align}{\strut
4813                  \color{\eq@fillin@color}}%

```

```

4814           \@eqmath{\eq@fillin@format\eqe@argiii}}}}%
4815           \else

```

(2014/02/16) The `autolift` or `lift` keys are specified. If `autofill`, put contents in a box. Set `\tempdima` to `\dp2+\eq@fillin@addtoautolift`, the latter normally has a value of `Opt` unless specified on the option list.

```

4816           \ifKV@eqFillin@autolift
4817               \setbox2=\hbox{\@eqmath{\eq@fillin@format\eqe@argiii}}%
4818               \setlength{\tempdima}{\dp2+\eq@fillin@addtoautolift}%
4819               \edef\eq@fillin@lift{\the\tempdima}\fi

```

(2014/02/16) We lower by an amount of `\eq@fillin@lift`, but raise the context by that same amount.

```

4820           \raisebox{-\eq@fillin@lift}{\@fillinFmt{%
4821               \makebox[\eqe@bw]{\eq@fillin@align}{\strut
4822               \color{\eq@fillin@color}}%
4823               \raisebox{\eq@fillin@lift}{\@eqmath{\eq@fillin@format
4824                   \eqe@argiii}}}}}}%
4825           \fi
4826           }\setlength{\tempdima}{\ht0+\dp0}%
4827           \xdef\fillinTotalHeight{\the\tempdima}%
4828           \mbox{\unhbox\z@}%
4829       \fi
4830   \else

```

We begin the case of not `\ifeq@proofing`, that is, the document author is not compiling with the `answerkey` option.

```

4831   \ifKV@eqFillin@boxed
4832 %       \mbox{\eq@fillin@format\ensuremath{\boxed{%
4833 %           \eq@fillin@format\ensuremath{\eq@fillin@boxcmd{%
4834 %               \setbox\z@\hbox{\eq@eqFillin@fontsize % dpsf0214
4835 %                   \@eqmath{\eq@fillin@format
4836 %                       \eq@fillin@boxcmd{\eq@eqFillin@boxsize\ifeq@nosolutions
4837 %                           \rlap{\@eqmath{\eq@eqFillin@fontsize % dpsf0214
4838 %                               \eq@fillintext}}\fi
4839 %                           \ifvspacewithsolns % dpsf0214 \eq@eqFillin@fontsize
4840 %                               \rlap{\@eqmath{\eq@eqFillin@fontsize\eq@fillintext}}\fi
4841 %                           \@fillinFmt\%}

```

We do a similar thing if proofing is not active (`nosolutions` is taken).

```

4842       \makebox[\eqe@fbox\corr{\eqe@bw}]{%
4843           \ifKV@eqFillin@enclosesoln\phantom
4844               \setlength\eqetmplengthb{\eqe@bw-2\fboxsep}%
4845               \edef\eqe@bw{\the\eqetmplengthb}%
4846               \@eqmath{\eqe@argiii}}\else
4847               \strut\hfill\fi
4848           }%
4849       }%\end \@fillinFmt
4850   }%\end \hbox
4851   }\setlength{\tempdima}{\ht0+\dp0}%
4852   \xdef\fillinTotalHeight{\the\tempdima}%

```

```

4853           \mbox{\unhbox\z@}%
4854     \else
4855         \setbox\z@\hbox{\eq@eqFillin@fontsize % dpsf0214
4856         \ifdim\eq@fillin@lift=-1sp\relax
4857             \eq@fillinFmt{\makebox[\eqe@bw]{%
4858               \phantom{@eqmath{\eqe@argiii}}%
4859               \strut\hfil}}%
4860         \else
4861             \ifKV@eqFillin@autolift
4862                 \setbox2=\hbox{@eqmath{\eq@fillin@format
4863                   \eqe@argiii}}%
4864                 \setlength{\tempdima}%
4865                   {(\dp2+\eq@fillin@addtoautolift)%
4866                   \edef\eq@fillin@lift{\the\tempdima}\fi
4867                   \raisebox{-\eq@fillin@lift}{\eq@fillinFmt{%
4868                     \makebox[\eqe@bw]{\raisebox{\eq@fillin@lift}
4869                       {\phantom{@eqmath{\eq@fillin@format
4870                         \eqe@argiii}}\strut\hfil}}}}%
4871             \fi
4872             \setlength{\tempdima}{\ht0+\dp0}%
4873             \xdef\fillinTotalHeight{\the\tempdima}%
4874             \mbox{\unhbox\z@}%
4875         \fi

```

**Online Code.** If the `quiz` environment is defined, and the user has asked for `online` option we build a text field.

```

4876     @ifundefined{@quiz}{}{%
4877       \if\eq@online\eqe@YES\relax
4878         \ifeq@nosolutions
4879           \ifeq@solutionsafter\else
4880             \ifx\eq@insertverticalspace\eqe@YES\relax

```

OK, we get this far if we choose `online` (or higher) and if `nosolutions` (which includes the `vspacewithsolns` option). We require `\eq@insertverticalspace` to be `y`. This last value is the default (`\SpaceToWork`).

```

4881           \stepcounter{cntfillin}%
4882           \edef\fieldName{%
4883             \if\probstar*eqexam.\curr@quiz.fillin.%
4884               \theeqquestionnoi.part\thepartno.%
4885               fi\the@cntfillin%
4886             \else
4887               eqexam.\curr@quiz.fillin.%
4888               \theeqquestionnoi.fi\the@cntfillin%
4889             \fi
4890           }\ifx\eq@fillinparbox\empty

```

If the `parbox` option is not taken, we build a text field with height `11bp`

```

4891           \raisebox{-1bp}{\makebox[0pt][r]{%

```

```
4892           \textField[\BC{}]\presets{\eqe@optsFillIn}]{%
4893             {\fieldName}{#2}{\fillinTotalHeight}}}\else
```

If the user has taken the `parbox` option, then the text field becomes a multiline field, with height equal to the requested height.

```
4894           \setlength{\tempdima}{%
4895             \eqe@opts@argii+2\fboxrule+2\fboxsep}%
4896             \raisebox{-1bp}{\makebox[Opt][r]{%
4897               \textField[\BC{}]\presets{\eqe@optsFillIn}]{%
4898                 \Ff{\FfMultiline}}{\fieldName}{#2}{\fillinTotalHeight}}}}\fi
4899           \fi
4900         \fi
4901       \fi
4902     \fi
4903   }%
4904 }
```

(2018/02/02) Removed `\space\ignorespaces` from `\fillin`

```
4905 \fi\endgroup}
```

`\TF` The `\TF` command depends on `\fillin`, so we make the appropriate changes.

```
4906 \renewcommand\TF[2][\defaultTFwidth]{%
4907   \def\eqe@next{\fillin[underline]{#1}{#2}}%
4908   \ifdim\eqe@extralabelsep=0pt\relax\else
4909     \if\probstar*\relax\if\exerwparts@cols0
4910       \def\eqe@next{\makebox[Opt][r]{%
4911         \fillin[underline]{#1}{#2}\ignorespaces}}%
4912     \fi\fi\fi\eqe@next
4913 }
```

This marks the end of the `eqexam` package. dps

```
4914 </package>
```

## 18 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\# . . . . .	657, 661, 4760
\% . . . . .	1702, 1878, 1987, 1992
\@Ans@sq@f@Defaults . . . . .	1013, 1075
\@EmailCourseName . . . . .	912, 938, 939
\@EmailExamName . . . . .	914, 940, 941
\@EmailInstr . . . . .	910, 936, 937
\@EmailSubject . . . . .	916, 942, 943
\@Mi . . . . .	4078
\@PTs . . . . .	2571, 2572
\@ServerRetnMsg . . . . .	918, 944, 945
\@SubmitButtonLabel . . . . .	920, 928
\@actionsAtPageBreak . . . . .	2139, 2180
\@altTitle . . . . .	1326, 1329, 1330
\@argi . . . . .	2777
\@auxout . . . . .	1238, 1653, 1690, 1692, 1705, 1719, 1722, 1727, 1738, 1742, 1746, 2095, 2111, 2123, 2298, 2300, 2305, 2545, 2675, 2680, 2689, 2704, 2848
\@bypassseqexamheadingfalse . . . . .	204
\@bypassseqexamheadingtrue . . . . .	205
\@checkSpacing . . . . .	80, 2147, 2435, 2436, 2460
\@checkSpacingi . . . . .	2477
\@ckhide . . . . .	2763
\@date . . . . .	1325, 1413
\@eqCommentsColor . . . . .	529, 2079
\@eqCommentsColorBody . . . . .	531, 2083
\@eqalignfilllinestoleftfalse . . . . .	3016, 3018
\@eqalignfilllinestolefttrue . . . . .	3017
\@equseseclassmaketitlefalse . . . . .	202
\@equseseclassmaketitletrue . . . . .	203
\@eqlinedfillerfalse . . . . .	2012, 2969, 3641
\@eqlinedfillertrue . . . . .	2966
\@eqmath . . . . .	4744, 4747, 4780, 4790, 4792, 4800, 4809, 4814, 4817, 4823, 4835, 4837, 4840, 4846, 4858, 4862, 4869
\@equsedimfalse . . . . .	3015
\@equsedimtrue . . . . .	3013, 3014
\@evenfoot . . . . .	468
\@evenhead . . . . .	466, 4256, 4327
\@evenllx . . . . .	4154, 4233
\@evenly . . . . .	4151, 4152, 4233
\@examAnsKeyLabel . . . . .	866, 868
\@examEmailLabel . . . . .	891, 895, 897
\@examNameLabel . . . . .	868, 875, 878
\@examSIDLabel . . . . .	882, 885, 887
\@fillinFmt . . . . .	2349– 2351, 2353, 2356, 4770, 4771, 4773, 4774, 4795, 4803, 4812, 4820, 4841, 4849, 4857, 4867
\@fvsizeskip . . . . .	2182, 2214, 2216, 2217, 2234, 2456
\@gatherTitleText . . . . .	613, 615, 629, 656, 660
\@getsecondOf . . . . .	1261, 1262, 1267
\@gobblet@end . . . . .	2585, 2589
\@gobbletoptone . . . . .	2921
\@headoffset . . . . .	4255, 4257, 4260, 4263
\@ifl@ter . . . . .	1110
\@insertPointsBoxPDF . . . . .	1578, 1594
\@insertTotalsBoxPDF . . . . .	1585, 1595
\@instructionsColor . . . . .	527, 2039
\@isitstar . . . . .	2530, 2531, 2534, 2639–2641, 2645, 2647, 2820, 2832, 2865
\@linkcolor . . . . .	541, 980, 982, 983, 1044, 1046, 1047, 1141, 1203
\@listii . . . . .	2748, 2749
\@listii@SAVE . . . . .	2748, 2749
\@lti . . . . .	2530, 2532
\@ltii . . . . .	2531, 2533
\@markerTotalFmt . . . . .	1708, 1715
\@marktotalvalue . . . . .	. 1537, 1545, 2535, 2575, 2715, 2822, 2842, 2862
\@minus . . . . .	2037, 2077, 2084
\@mparswitchfalse . . . . .	3806
\@nbaselineskip . . . . .	2494, 2495, 2526, 2631, 4484, 4494
\@nnotContStrSkip . . . . .	2904, 2916, 3176
\@nobreakfalse . . . . .	2425, 2448
\@nolinkcolor . . . . .	543, 980, 982, 1044, 1046
\@oddfoot . . . . .	467, 468
\@oddhead . . . . .	463, 466, 4259, 4262, 4328
\@oddllx . . . . .	4157, 4231
\@oddly . . . . .	4152, 4231
\@onlypreamble . . . . .	511, 1564, 3821, 4037, 4128, 4319, 4530
\@pdfcreator . . . . .	375
\@pdfviewparams . . . . .	390
\@plus . . . . .	2037, 2077, 2084
\@proofingsymbol . . . . .	1145, 1243
\@proofingsymbolColor . . . . .	525, 1145
\@reportpoints . . . . .	153, 483, 484, 486, 2147, 2430, 2573
\@reporttotals . . . . .	490, 495, 496, 500
\@rgi . . . . .	568, 1768, 1772, 2512, 2513, 2518, 2519, 2876, 2881, 3101, 3104, 3351, 3478, 4645, 4701, 4703
\@secondoffive . . . . .	1262, 2941

\@secondoftwo	1261, 2940	allowcirc4mc (option)	7
\@setckpt	4511, 4512, 4528	\allowcircmcfalse	113
\@spacetobreak	2139–2141	\allowcircmctrue	114
\@ssSolution	1819	\AllowFitItIn	507
\@sssolution	1817, 2014	allowrandomize (option)	8
\@startsection	2024, 2036, 2076	\allowZeroTotals	498, 499
\@subject	823, 824	\Alpha	624, 626, 712, 728, 732, 734, 737, 740, 792, 796, 798, 801, 948, 950
\@tableadinitemtrue	2772	\alt@SetSlnMargins	302, 303, 307, 309
\@tempboxa	4697, 4698, 4700, 4702, 4705	\altSetSlnMargins	14, 302
\@templocalversionfalse	671, 808	\altTitle	1322
\@templocalversiontrue	770	\amtSpaceLeftOnPage	80, 2455
\@undefined	2056, 2939	\aNewPage	2928
\@web@title	814, 815	\annotContStr	2897
\@whiledim	3229, 3333, 3388	\annotPage	4472
\@writefile	4509, 4510, 4527	\annotThePage	4472, 4473
\{	1878	\ANS	3843
\}	1884	\Ans@choice	976, 1011, 1040, 1073, 1242
\_u	426, 428, 430, 434, 835, 875, 885, 895, 1522, 2029, 2072, 2187, 2312, 2342, 2391, 3959, 3960, 3966, 3967, 3972, 3973	\Ans@ck@sq@f	1099
<b>A</b>			
\A	928, 977, 1011, 1041, 1073	\Ans@ck@sq@l	1098
\AA	1589	\Ans@proofing	984, 1017, 1048, 1079, 1205, 1211, 1240
\AACalculate	1589	\Ans@rcl@Defaults	952, 978, 1042
\aboveexskip	2500, 4443, 4483, 4493	\Ans@sq@f	1097
\abovesqskip	2220	\Ans@sq@f@Actions	1013, 1075
\acp@mpah	2852, 2866	\Ans@sq@f@driver	997, 1000, 1059, 1062, 1207
\acp@mpph	2853, 2867	\Ans@sq@l	1096
\acvspace	2897	\Ans@sq@l@driver	1203
\addpenalty	2425, 2448	\ANScolor	3956
\addtoautolift	151	\ANSFmt	3911, 3957
\addtocounter	663, 1543, 1650, 1694, 1695, 2167, 2176, 2177, 2534, 2543, 2575, 2576, 2699, 2794, 2802, 2821, 2841, 2856, 2862, 2895	\AnswerKey	82, 84
\AddToShipoutPicture	4365	answerkey (option)	6
\aeb@sectioncolor	549	\answerkeyfalse	70, 338, 512
\aebc@end	361, 362, 677, 696, 792	\answerkeyifSave	342
\aebshowgraylettersfalse	190	\answerkeytrue	84, 185, 280, 3793
\aebshowgrayletterstrue	192	\answers	286
afterChapSols (environment)	4283	\answers@sq	286
\afterCommentSkip	2071, 2078, 2080, 2081	\applyleadinfix	2609, 2613
\afterexamsepcode	2162, 2170, 2265	\applyparfixes	85, 2611
\aftergroup	1894, 2144, 2265, 2429, 2557, 2712, 3247	\applyparfixesp	2509, 2613
\afterInstrSkip	2028, 2038	\ARG	329, 331
\afterlabelhskip	2527, 2637	\arg@i	17
\align	4568	\argi	1641, 1645, 1649, 1651, 2698, 2703, 2783, 2796, 2815, 2834, 2838, 2841, 3942, 3943
align (key)	101	\argii	1641, 1642, 1646, 1648, 1652, 2783, 2787, 2818
\AtBeginDocument			
175, 367, 564, 567, 680, 1117, 1283, 1536, 1687, 4363, 4408, 4674			
\AtEndDocument			
368, 1689			
\AtEndOfPackage			
20, 29, 33–39, 44, 46, 53, 54, 69, 101, 112, 135, 183, 192, 262, 265, 746			
\author			
811			

\authorColor	525	\cancelleadinfix	2610, 2617, 2618
\auto	2583, 2590, 2649, 2679	\cancelparfixes	85, 2614, 2619
\autocalcparts	93, 2652, 2854	\cancelparfixesp	2510, 2511, 2616, 2618
\autoExamName	2218, 2238, 4476	carryoverFmt (environment)	4166
\autoInsSolns	141, 4407	\cbfillineol	4689, 4697
\autolift	151	\cbfillineol@i	4703, 4704
<b>B</b>			
\baselineskip	1797, 2526, 2606, 2631, 3485, 3490, 3660, 3662, 4484, 4494	\cbfillineol@ia	4700, 4701
\Bbox	1139, 1164, 1167, 1168, 1172–1174, 1181, 1183, 1184, 1187, 1188, 1209	\cbfillineol@ib	4701, 4702
\BC	905, 954, 1092, 1582, 1588, 2371, 4892, 4897	\centering	1425, 1431, 1437
\beforeCommentSkip	2070, 2077, 2084	\centerWidget	1131, 1161, 1208
\BeforeIncludedComment	4302	cfg (option)	5
\beforeInstrSkip	2027, 2037, 2044	\cfooteqe	1301
\belowexskip	2500, 4444, 4483, 4493	\chapHeadSolnFmt	4458, 4461
\belowexsolnskip	2504, 4445	\chapter	4467
bgcolor (key)	101	\chapterexercisesfalse	4266
bgonly* (key)	101	\chapterexercisestrue	4310
\bGrpANS	2669, 2670, 3843	\chaptername	4464
\bIFFalseWrtSolns	2228, 2233	\chaptersolutions	4266, 4282
\bigbreak	4461	\chead	1290
\bigskip	1388	\cheadeqe	1284
\bigskipamount	1432, 1475, 1502	\cheadSol	1308
\boPage	2931, 2937, 2940–2942, 2944, 2962	\check@@Box	1039, 1071
\bopCoverPageText	2932, 2962	\chkmarginboxwidth	4129, 4364
\bopText	2931, 2933	\chngToNoSolns	512
\botmark	1644	\circ@Glyph	1157, 1160, 1162
\box	3469, 3594, 3610, 3613, 3763, 3764	\circProofingForCirc	1161, 1178
\boxcmd	4625	\ckbox@Color	569, 570, 1137
\boxed	4568, 4629, 4630, 4791, 4832	\ckboxColor	22, 559, 568, 570
\boxpretext	4568	\ckcir@Color	572, 573, 1158, 1160
\boxsize	4568	\ckcirColor	22, 560, 571, 573
\bpartsrmk	2723, 4024, 4029, 4032	\cleaders	2996, 2997, 3001, 3007, 3010
\bslash{textsl{\texttt{\{Mrk1\}}}}End	59	\clearBotMargin	130, 4067, 4353
\bslash{textsl{\texttt{\{Mrk1\}}}}nQs	59	\clearpage	1694
\bslash{textsl{\texttt{\{Mrk1\}}}}Start	59	\clearTopMargin	129, 4059, 4353
\btwnExamSkip	316, 325	\clubpenalty	3652, 3715
\btwnExamSkipAmt	315	\cngMargHeadColorTo	4097
\bWebCustomize	247	\col@number	2428, 2442
<b>C</b>			
\c@eq@count	2942, 2943	\collectboxto	4697, 4702
\c@partno	2894	\color	570, 573, 1424, 1430, 1436, 2083, 2354, 4087, 4089, 4568, 4800, 4813, 4822
\c@rryoverFmt	4167, 4168	color (key)	100
\CA	928	\color@begingroup	4061, 4063, 4199, 4214
\calcFromMarkers	1708	\color@endbox	3541
\calcQsBtwnMarkers	1717	\color@endgroup	4062, 4064, 4207, 4217
\calcTextField	1582, 1588	\color@vbox	3532
		\columnbreak	2428, 2442
		\columnseprule	413, 4326, 4343, 4350
		\comment	407
		\CommentCutFile	4285, 4286, 4293
		\CommentEndDef	4297, 4304

\CommentStream . . . . . 3507, 4295, 4300  
 \cont@nnotfalse . . . . . 2920, 2922  
 \cont@nnottrue . . . . . 2924  
 \convertChapHeadToChapters . . . . . 4465  
 \copy . . . . . 2996, 3552, 3565, 3578  
 \copyrightyears . . . . . 832  
 coverpage (option) . . . . . 6  
 \coverpage@subject . . . . . 1362–1365  
 \coverpageCID . . . . . 1377, 1385  
 \coverpagesubject . . . . . 1362  
 \coverpageSubjectFmt . . . . . 1362  
 coverpagesumry (option) . . . . . 6  
 \coverpageTitleFmt . . . . . 1362  
 \coverpageUniversityFmt . . . . . 1362  
 \cp@@CID . . . . . 1375, 1376, 1380, 1383, 1411  
 \cp@CID . . . . . 1380, 1411  
 \cp@EnclNameAndID . . . . . 1400, 1401, 1409  
 \cp@HghtFrstLn . . . . . 1402–1404  
 \cp@InsertNaming . . . . . 1457, 1478  
 \cp@setHghtFrstLn . . . . . 1404, 1410  
 \cp@SetNameAndIDWidth . . . . . 1398, 1406–1409  
 \cp@SetSumryWidth . . . . . 1451, 1465, 1466, 1494, 1495  
 \cp@sumryWdth . . . . . 1465–1467, 1494–1496  
 \cp@Usefbox . . . . .  
     . . . . . 1453, 1455, 1463, 1464, 1487, 1492, 1493, 1532  
 \cpCID . . . . . 1375  
 \cpCID@argi . . . . . 1377, 1379, 1381, 1383, 1408  
 \cpEnclNameAndID . . . . . 1400  
 \cpNameAndID . . . . . 1405, 1440  
 \cpNofbox . . . . . 1445  
 \cprulelength . . . . . 1456, 1469, 1498  
 \cpSetCIDWidth . . . . . 1378, 1384  
 \cpSetHghtFrstLn . . . . . 1402  
 \cpSetNameAndIDWidth . . . . . 1396, 1399  
 \cpSetSumryWidth . . . . . 1445  
 \cpSumrybypages . . . . . 51, 62, 1491  
 \cpSumrybyparts . . . . . 50, 61, 1462  
 \cpSumryGrade . . . . . 1445, 1485, 1530  
 \cpSumryHeader . . . . . 1445, 1475, 1502  
 \cpSumryPage . . . . . 1445, 1518  
 \cpSumryPts . . . . . 1445, 1480, 1484, 1521, 1523, 1524, 1529  
 \cpSumryTotal . . . . . 1445, 1482, 1527  
 \cpUsefbox . . . . . 1445  
 \csarg . . . . . 328, 330, 675, 677, 689, 690, 694, 696,  
     728, 792, 1252, 1253, 1264, 1271, 1471, 1500,  
     1514, 1521, 1653, 1690, 1692, 1705, 1719, 1721,  
     1722, 1725, 1727, 1737, 1738, 1741, 1743, 1745,  
     1746, 2095, 2100, 2102, 2104, 2107, 2111, 2123,  
     2163, 2246, 2251, 2254, 2274, 2285, 2286, 2290,  
     2295, 2299, 2300, 2305, 2546, 2620, 2674, 2675,  
     2680, 2690, 2704, 2738, 2773, 2794, 2848, 2857,  
     2936, 2961, 4290, 4295, 4300, 4302, 4312, 4314  
 \CT@arc@ . . . . . 266  
 \CT@cell@color . . . . . 265  
 \ctrld@exp@exercise . . . . . 2550, 2552  
 \curr@quiz . . . . . 968, 970, 1003, 1006, 1032, 1035,  
     1065, 1068, 1086, 1580, 1587, 1590, 2058,  
     2060, 2063, 2067, 2239, 2364, 2368, 4883, 4887  
 \CurrentOption . . . . . 75, 79, 226, 4553  
 \currhideopt . . . . . 1779, 1798, 1863, 1868, 1902, 1905, 2762  
 \currProbHead . . . . . 4108, 4109  
 \customNaming . . . . . 48, 1395

## D

\D@Num . . . . . 2587, 2588, 2691, 2693, 2697  
 \date . . . . . 849  
 \day . . . . . 861  
 \dbMrk . . . . . 3346, 3404, 3405, 3432  
 \DeclareOption . . . . . 4553  
 \DeclareOptionX . . . . . 5, 7, 9,  
     11, 12, 14, 28, 33–39, 44, 45, 47, 49, 52, 55, 56,  
     68, 80, 95, 100, 101, 112, 114, 118, 120, 121,  
     123, 126, 127, 131, 133, 135, 157, 159, 161,  
     163, 168, 173, 174, 176, 181, 187, 191, 201,  
     203, 205, 207, 210, 212, 214, 217, 220, 222, 225  
 \default@fvsizeskip . . . . . 2213, 2215, 2216, 4442  
 \default@nbaselineskip . . . . . 81, 2492, 2495  
 \defaultalign . . . . . 150  
 \defaultInstructions . . . . . 2025  
 \defaultSolnIndent . . . . . 3998–4000  
 \defaultTFwidth . . . . . 2380, 2381, 4906  
 \define@boolkey 3040, 3082, 3088, 3786, 3787, 3803–  
     3805, 3807, 3808, 4568, 4571, 4580, 4624, 4651  
 \define@choicekey . . . . . 58, 3026, 3044, 3061, 3071,  
     3077, 3084, 3090, 4581, 4590, 4598, 4609, 4643  
 \definecolor . . . . . 3953, 3956, 4084, 4099  
 \depthtodate . . . . . 3225, 3230, 3240, 3250  
 \dimen . . . . . 3252–3254, 3324–3328, 3330, 3333, 3335,  
     3338–3341, 3363–3368, 3384, 3386–3388, 3391,  
     3392, 3394, 3416–3418, 3424, 3428, 4220–4223  
 \ding . . . . . 285, 1198, 1201, 2634  
 \displ@yPointsfalse . . . . . 519  
 \displ@yPointstrue . . . . . 517, 518  
 \displayPointsOff . . . . . 20, 519  
 \displayPointsOn . . . . . 20, 518  
 \displayProbNumOnce . . . . . 4436  
 \displayworkareafalse 85, 180, 186, 194, 196, 282, 3646  
 \displayworkareaifSave . . . . . 344  
 \displayworkareaOff . . . . . 196  
 \displayworkareaOn . . . . . 195

\displayworkarea@true	98, 171, 195, 339, 510, 514	\endminipage	2016, 2017, 2019, 3695, 3738
\divide	765, 784, 2289, 3362, 3366	\endpanel	1882
\dlcomment	407, 409	\endparts	1540
\Do	2584, 2588	\endproblem	2553
\documentclass	272	\endproblem*	87
\DoNotFitItIn	508, 4404	\endshortquiz	2264
\DoNotRecordThisExam@false	2226, 2269	\endshortTitleText	592, 646, 661
\DoNotRecordThisExam@true	2227	\endsolution	1818, 1820
\DoNum	2399, 2401, 2405, 2632	\endsplitSolution	1823
\dpPtBox	1634, 2134, 2468, 2483	\endtitleMarker	612, 617, 632, 655
\duedate	849, 850, 851	\endverbatimwrite	1883, 3692, 3736
\DV	936, 938, 940, 942, 944	\ensuremath	4744, 4790, 4791, 4793, 4809, 4832, 4833
dvipdfm (option)	11	environments:	
dvipdfmx (option)	11	afterChapSolns	4283
dvips (option)	11	carryoverFmt	4166
dvipsone (option)	11	eq@numparts	19
		eqComments	2070
		eqeList	3941
		eqepartsquestions	4386
		eqpointsofar	19
		eqpointsthispage	19
		exam	2213
		example	4482
		example*	4492
		fullwidhttext	4330
		instructions	2027
		lsol	4055
		priorworkarea	3714
		problem	2497
		problem*	2594
		probset	4474
		splitsolution	63, 1803
		ssol	4056
		workarea	1762
		\eoetotalOff	503
		\eoetotalOn	504
		\epartsmrk	4025, 4031, 4033
		\eq@emitMessageNearBottom	2446, 2447
		\eq@writeexheaderlist	2766
		\eq@cargi	2034, 2040, 2042
		\eq@cddCodeSpecial	3483, 3655
		\eq@cfoot	1303, 1307
		\eq@chead	1286, 1295
		\eq@cheadSol	1310, 1315
		\eq@ckglobalhide	2765
		\eq@ColorPackage	158, 198, 200, 201, 209, 211, 213, 216, 219, 221, 224, 226, 264
		\eq@currProbStartPage	2452, 2906, 2907, 2919
		\eq@custom	4645
		\eq@default@Instructions	2025, 2031

\eq@e@ddCodeSpecial ..... 3656, 3692, 3697  
\eq@Email ..... 895, 1412  
\eq@emitMessageNearBottom ..... 2443–2445  
\eq@eqFillin@align 4600, 4728, 4742, 4799, 4812, 4821  
\eq@eqFillin@align@default ..... 4599, 4610  
\eq@eqFillin@boxsize ..... 4583, 4587, 4794, 4836  
\eq@eqFillin@fontsize ..... 4592, 4596,  
    4747, 4795, 4810, 4834, 4837, 4839, 4840, 4855  
\eq@ExamLastPage ..... 43, 1246, 1311  
\eq@ExamName ..... 874, 1289, 1327, 1410  
\eq@extralabelsep ..... 2383, 2393, 4908  
\eq@fillin@addtoautolift ..... 4653, 4818, 4865  
\eq@fillin@boxcmd .....  
    4627, 4630, 4633, 4792, 4793, 4833, 4836  
\eq@fillin@color ..... 4597, 4800, 4813, 4822  
\eq@fillin@defaultbox ..... 4626, 4629, 4633  
\eq@fillin@defaultul ..... 4635, 4638, 4644  
\eq@fillin@fboxsep ..... 4588, 4589, 4718  
\eq@fillin@format .....  
    4621, 4622, 4748, 4780, 4791, 4793, 4800,  
    4814, 4817, 4823, 4832, 4833, 4835, 4862, 4869  
\eq@fillin@lift ..... 4650,  
    4720, 4811, 4819, 4820, 4823, 4856, 4866–4868  
\eq@fillin@ulcmd 4636, 4639, 4641, 4646, 4647, 4770  
\eq@fillinColor ..... 547, 4597  
\eq@fillinhiddenbox ..... 4577, 4579, 4723, 4724  
\eq@fillinparbox ..... 4574,  
    4575, 4726, 4729, 4745, 4772, 4781, 4801, 4890  
\eq@fillintext .....  
    4572, 4573, 4739, 4748, 4782, 4802, 4838, 4840  
\eq@fititin ..... 507, 508, 1143, 4487, 4497  
\eq@globalshowsolutionsfalse ..... 235  
\eq@globalshowsolutionstrue ..... 173, 175  
\eq@hidesolutionfalse ..... 234, 2762  
\eq@hspanner ..... 985, 1018, 1049, 1080  
\eq@initializeContAnnot ..... 2736  
\eq@initLoop ..... 2888, 2892, 2893  
\eq@insertContAnnot ..... 2923, 2925, 2927, 3233  
\eq@insertverticalspace .....  
    69, 145, 146, 151, 1757, 1795,  
    2011, 2361, 3630, 3640, 3643, 3707, 3746, 4880  
\eq@item ..... 2761, 2763  
\eq@item@latex ..... 2913  
\eq@l@check@driver ..... 977, 1041  
\eq@l@l ..... 964, 1028  
\eq@leadin@item ..... 2761, 2765  
\eq@lfloor ..... 1301, 1307  
\eq@lhead ..... 1284, 1295  
\eq@lheadSol ..... 1308, 1315  
\eq@linesXPgs ..... 3257, 3262  
\eq@listType ..... 961, 989, 1024, 1051  
\eq@lw@f ..... 992, 1054  
\eq@lw@l ..... 963, 1027  
\eq@max@selected ..... 130, 131  
\eq@NO ..... 3640, 3707  
\eq@nolinkfalse ..... 238, 339, 2762  
\eq@nolinkifSave ..... 343  
\eq@nolinktrue ..... 170, 509, 2767, 2768  
\eq@nosolutionsfalse ..... 236, 339  
\eq@nosolutionsifSave ..... 344  
\eq@nosolutionstrue ..... 170, 509, 514  
\eq@nosummarytotals .....  
    55, 148, 491, 501, 502, 2032, 2033, 2040, 2042  
\eq@nototals ..... 147  
\eq@nSelectedVersion .. 713, 716, 762, 764, 766, 779  
\eq@numparts (environment) ..... 19  
\eq@nVersions . 588, 591, 618, 628, 709, 716, 721, 743  
\eq@online ..... 119, 138, 139, 347, 392, 902,  
    973, 995, 1038, 1057, 1102, 1163, 1180, 2358, 4877  
\eq@parttotals ..... 46, 149, 503, 504, 2132, 2138  
\eq@pointbox .....  
    479, 1628, 1630, 1632, 1634, 1635, 3552,  
    3553, 3555, 3565, 3567, 3578, 3593, 3609, 3613  
\eq@pointboxtotalheight 480, 1630–1633, 2133–  
    2136, 2143, 2465, 2467, 2468, 2470, 2482–2485  
\eq@proofingfalse ..... 189, 237, 338, 513  
\eq@proofingifSave ..... 342  
\eq@proofingtrue ..... 85, 187, 188, 280, 3793  
\eq@protect ..... 977, 1011, 1041, 1073  
\eq@Radio@driver ..... 988, 1012, 1074  
\eq@RadioCheck@driver ..... 988  
\eq@ren@selected ..... 130, 133  
\eq@renditionOptions ..... 129, 132, 134, 747  
\eq@replaceToken ..... 668  
\eq@rfoot ..... 1305, 1307  
\eq@rgi ..... 571  
\eq@rhead ..... 1288, 1295  
\eq@rheadSol ..... 1312, 1315  
\eq@selectedItem ..... 2887, 2891  
\eq@selectedVersion .....  
    593,  
    602, 666, 667, 705, 706, 712, 719, 2556, 2711  
\eq@selectedVersion@save .....  
    593, 594, 602, 603, 643, 645, 647, 649  
\eq@setWidgetProps ..... 977, 1012, 1041, 1074  
\eq@shortTitlesFix ..... 619, 650  
\eq@shortVersionAtext ..... 577, 580  
\eq@shortVersionBtext ..... 577, 581  
\eq@SID ..... 885, 1411  
\eq@solutionsafterfalse ..... 229, 232, 338, 513  
\eq@solutionsafterifSave ..... 343

\eq@solutionsaftertrue . . . . . 85, 179, 231, 281  
\eq@solutionshook . . . . . 1316, 4413, 4414  
\eq@sqlabel . . . . . 2343  
\eq@sqslabel . . . . . 1213, 1214, 2342  
\eq@sqslrtnlabel . . . . . 2326, 2330, 2332  
\eq@sqslsecrunhead . . . . . 2341  
\eq@sqslsectitle . . . . . 2340  
\eq@temp@exp . . . . . 4712, 4714, 4716, 4717  
\eq@tmp . . . . . 2244, 2245  
\eq@tmpbox . . . . . 964, 993, 1028, 1055, 1127  
\eq@tmpdima . . . . . 964, 976, 983, 984,  
993, 1028, 1040, 1047, 1048, 1055, 1128, 1204,  
1205, 1890, 1891, 1932, 1934–1936, 2740–2743  
\eq@tmplength . . . . . 963, 966, 992, 994,  
1027, 1030, 1054, 1056, 2744–2747, 2908, 2909  
\eq@tmplengthA . . . . . 477, 875, 877, 885, 886,  
895, 896, 1380, 1382, 2391–2393, 3274, 3280,  
3286, 3295, 3299, 3303, 3309, 3312, 3330, 3340  
\eq@tmplengthB . . . . . 478, 3548, 3557, 3569  
\eq@usexkeys . . . . . 127, 128, 4566  
\eq@VersionAtext . . . . . 576, 578  
\eq@VersionBtext . . . . . 576, 579  
\eq@WriteLineColor . . . . .  
. . . . . 2984, 2990, 2999, 3003, 3039, 3421, 3431  
\eq@YES . . . . . 3272, 3293, 3510, 3630, 3643, 3694, 3737  
\eqbothmargins . . . . . 487, 1638  
\eqcenterWidget . . . . . 1130, 1133–1135, 1162, 1209  
eqComments (environment) . . . . . 2070  
\eqCommentsColor . . . . . 525  
\eqCommentsColorBody . . . . . 531, 532, 558  
\eqcustomdesignfalse . . . . . 6, 276  
\eqcustomdesigntrue . . . . . 5  
\eqdashrulefill . . . . . 3000, 3003  
\eqdashruleVfill . . . . . 3010, 3012  
\eqdotrulefill . . . . . 2995, 2999  
\eqdotruleVfill . . . . . 3007, 3009  
\eqDriverName . . . . . 164,  
165, 208, 210, 212, 215, 218, 220, 223, 228, 389  
\eqDvipsone . . . . . 387, 389  
\eqe@holdTemp . . . . . 685, 686, 757–759, 772  
\eqe@leadinitem . . . . . 2722, 2734  
\eqe@numLinesL . . . . . 3029, 3166  
\eqe@numLinesR . . . . . 3030, 3171  
\eqe@offVersion . . . . . 683, 684, 702, 763  
\eqe@onVersion . . . . . 681, 682, 701, 756, 758  
\eqe@SumryVert . . . . . 1388, 1390, 1463, 1492  
\eqe@absorbTokensLong . . . . . 633, 642  
\eqe@absorbTokensShort . . . . . 635, 646  
\eqe@adjForSepRule . . . . . 2132, 2151, 2155  
\eqe@afterexamsepcode . . . . . 2137, 2170  
\eqe@align@hfill . . . . .  
. . . . . 4602–4604, 4608, 4727, 4728, 4739, 4741, 4743  
\eqe@align@hfill@default . . . . . 4612–4614, 4743  
\eqe@allow . . . . . 1666, 1668, 1670, 1678  
\eqe@argi . . . . . 1718, 1730, 1740, 1917, 2051, 2052,  
2075, 2080, 2081, 2249, 2303, 2304, 2590, 4670  
\eqe@argii . . . . . 616, 617, 2590, 2591, 4721, 4722, 4746, 4758  
\eqe@argiii . . . . . 4726, 4738, 4749, 4782,  
4802, 4814, 4817, 4824, 4846, 4858, 4863, 4870  
\eqe@auto@chk@drivers . . . . . 115, 118, 120, 121, 123  
\eqe@Bbox . . . . . 39, 1209  
\eqe@BboxCirc . . . . . 1160, 1164, 1174, 1181  
\eqe@BboxRect . . . . . 1137, 1139, 1168, 1173, 1184, 1188  
\eqe@BGColor . . . . . 3094, 3095, 3410, 3411  
\eqe@bParts . . . . . 2778–2780  
\eqe@bw . . . . . 4738, 4769, 4787, 4797,  
4799, 4812, 4821, 4842, 4844, 4845, 4857, 4868  
\eqe@calc@percent . . . . . 2279, 2283  
\eqe@cb . . . . . 4675, 4688  
\eqe@chkZeroTotals . . . . . 1666, 1669, 1677  
\eqe@cirDiam . . . . . 1153, 1158  
\eqe@cirRadius . . . . . 1155, 1157  
\eqe@color@opt . . . . . 198, 200  
\eqe@commentChkMsg . . . . . 363, 367  
\eqe@contTitleText . . . . . 598, 607, 610  
\eqe@coverPageNaming . . . . . 1392–1394, 1458  
\eqe@cprulelength . . . . .  
. . . . . 1470, 1478, 1483, 1486, 1499, 1519, 1528, 1531  
\eqe@csarg . . . . . 241, 242  
\eqe@decPointMrg . . . . .  
. . . . . 3926, 3971, 3974, 3978, 3981, 4428, 4438  
\eqe@decPointPrb . . . . . 425,  
426, 432, 2314, 2318, 2321, 3218, 3958, 3961, 4002  
\eqe@defNumRefii . . . . . 43, 1260, 1278, 1279  
\eqe@DoNum . . . . . 2399, 2401, 2632  
\eqe@DoWarning . . . . . 2397, 2399, 2400, 2411, 2412  
\eqe@dpsepPrb . . . . . 426  
\eqe@drivernum . . . . .  
. . . . . 208, 210, 212, 215, 217, 220, 223, 227, 370  
\eqe@emnb . . . . . 2442, 2444, 2451  
\eqe@eqOpts . . . . . 166, 167, 380  
\eqe@fbox@corr . . . . . 4623, 4733, 4797, 4842  
\eqe@fillLinesNumFmt . . . . . 3096, 3168, 3170, 3172  
\eqe@fillwidth . . . . . 3200, 3215, 3237, 3358,  
3386, 3401, 3407, 3412, 3414, 3434, 3439, 3536  
\eqe@flextendedfalse . . . . . 106, 111, 2013, 3639  
\eqe@flextendedtrue . . . . . 102, 3628  
\eqe@flnnexti . . . . . 3657, 3678, 3712, 3731, 3733, 3740  
\eqe@flnnextii . . . . . 3734, 3736, 3742  
\eqe@flnosolnsfalse . . . . . 3472, 3474, 3618

\eqe@flnosolnstrue ..... 3473, 3617  
 \eqe@Four ..... 42, 2655  
 \eqe@fpmrk ..... 2058, 2562, 2872, 2873  
 \eqe@getiiiOpts ..... 4654, 4729  
 \eqe@gobbletoend ..... 2497, 2531, 2640  
 \eqe@gobnxtpar ..... 2609, 2610, 2666  
 \eqe@grabarg ..... 2498, 2530, 2639  
 \eqe@h ..... 43, 2513  
 \eqe@HOfVrule ..... 3372, 3381, 3542, 3583, 3587,  
     3588, 3591, 3592, 3598, 3602, 3603, 3606, 3607  
 \eqe@HOfVruleFrstRow .. 3376, 3378, 3412, 3414, 3437  
 \eqe@holdTemp ..... 686, 799  
 \eqe@hspannerMrg .....  
     3889, 3902, 3918, 3945, 3973, 3976, 3981  
 \eqe@hspannerPrb ..... 429, 430, 432,  
     1624, 2187, 2210, 2314, 3960, 3964, 4003, 4383  
 \eqe@hspannerSoln 434, 435, 2209, 2318, 2321, 2322,  
     3967, 3970, 3989, 4012, 4015, 4022, 4382, 4399  
 \eqe@idinfohl ..... 870, 878, 887, 1383  
 \eqe@initializeMultiVersions ..... 672, 680, 700  
 \eqe@innermarkpts ..... 1537, 1541  
 \eqe@insert@more@content ..... 3231,  
     3344, 3453, 3627, 3642, 3668, 3675, 3749, 3755  
 \eqe@insertContAnnot ..... 2905, 2925  
 \eqe@insertLogo ..... 1351, 1353, 1357  
 \eqe@insertSolns ..... 3627, 3652, 3668, 3675  
 \eqe@isle@dinnext ..... 2605, 2606  
 \eqe@isPts ..... 2432,  
     2435, 2499, 2520, 2525, 2526, 2627, 2630, 2631  
 \eqe@IW ..... 1896, 1987, 1992, 2016  
 \eqe@IWO ..... 277, 295,  
     297, 323, 1225, 1233, 1238, 1653, 1690, 1692,  
     1705, 1719, 1722, 1727, 1738, 1742, 1746, 1864,  
     1870, 1879, 1884, 1900, 2095, 2111, 2123, 2298,  
     2300, 2305, 2545, 2675, 2680, 2689, 2704, 2848  
 \eqe@l ..... 1856, 1858  
 \eqe@lcir ..... 1150, 1152, 1159  
 \eqe@leadinitem ..... 2659, 2720  
 \eqe@localTextTitle ..... 595–597, 604–606  
 \eqe@lPanel ..... 1946, 1952, 1961, 1968, 1996, 2002  
 \eqe@makeVgrid ..... 108,  
     2983, 3192, 3196, 3355, 3458, 3625, 3671, 3752  
 \eqe@margininsert ..... 4094, 4095  
 \eqe@marktxt ..... 1538, 1541, 1542  
 \eqe@MarParBox ..... 4088, 4232, 4234  
 \eqe@mkRoomPgBrk ..... 2423, 2429  
 \eqe@movePTs ..... 2579, 2582  
 \eqe@nDoNum ..... 2400, 2402, 2632  
 \eqe@next .. 92–94, 618, 619, 629, 631, 640, 1898,  
     1900, 1903, 1907, 1913, 2199, 2382, 2385, 2388,  
     2652, 2657, 2658, 2722, 2725, 2730, 3183, 3184,  
     3186, 3795, 3796, 4689–4691, 4907, 4910, 4912  
 \eqe@nextitem ..... 2877, 2878, 2882, 2883, 2896  
 \eqe@NO ..... 40, 46, 69, 81, 96, 138,  
     140–142, 145, 147, 148, 169, 177, 182, 489, 497,  
     501, 503, 506, 752, 995, 1057, 1667, 1668, 2011,  
     2223, 2225, 2505, 2521, 2585, 2586, 2603, 2628,  
     2733, 2734, 2758, 2784, 2788, 2888, 2893, 3042,  
     3102, 3108, 3125, 3133, 3145, 3153, 4404, 4675  
 \eqe@nocustomdesign ..... 7, 8, 276  
 \eqe@nopointfalse ..... 488  
 \eqe@noPointstrue ..... 490  
 \eqe@nOutOfNum ..... 2412, 2414, 2633  
 \eqe@nskeyflsplit 2993, 3244, 3468, 3469, 3532,  
     3552, 3565, 3578, 3579, 3581, 3594, 3610, 3763  
 \eqe@nskeyfltop ..... 2994, 3553, 3554, 3557,  
     3567–3569, 3579, 3580, 3589, 3604, 3608, 3764  
 \eqe@numbersep ..... 3037, 3038, 3168, 3170, 3172  
 \eqe@numLinesL ..... 3028–3030, 3034, 3236  
 \eqe@numLinesR ..... 3028–3030, 3034, 3237  
 \eqe@numRefii ..... 44, 1270, 1273, 1274  
 \eqe@offVersion ..... 644, 648, 684, 738  
 \eqe@One ..... 41, 2147, 2529, 2530, 2534,  
     2574, 2592, 2639, 2641, 2650, 2820, 2832, 2865  
 \eqe@onVersion ..... 682, 735  
 \eqe@optiont@kenMsg ..... 78, 82, 97, 170, 178, 183  
 \eqe@opts@argi ..... 4667, 4735  
 \eqe@opts@argii .. 4668, 4731–4733, 4736, 4737, 4895  
 \eqe@opts@argiii ..... 4669, 4737  
 \eqe@optscbf ..... 1020, 1022, 1071  
 \eqe@optscbl ..... 1021, 1022, 1039  
 \eqe@optsFillIn ..... 2346, 2347, 2372, 4892, 4897  
 \eqe@optsmltf ..... 1082, 1083, 1092  
 \eqe@optsRadiof ..... 957, 959, 1009  
 \eqe@optsRadio1 ..... 958, 959, 975  
 \eqe@OutOfNum ..... 2411, 2413, 2633  
 \eqe@p@gobnxtp@r ..... 2509–2511, 2552  
 \eqe@p@gobnxtp@rDef ..... 2507, 2509  
 \eqe@p@gobtop@rnext ..... 2507, 2508  
 \eqe@paneli ..... 1850, 1851, 1853, 1855  
 \eqe@panelir ..... 1850, 1852  
 \eqe@parboxOptArgs ..... 4735, 4738  
 \eqe@partsIndent ..... 2909, 2912, 2914  
 \eqe@pForPart ..... 2291, 2293–2295  
 \eqe@pointsEach ..... 2688, 2784, 2788, 2792  
 \eqe@pointsPartsId 2574, 2594, 2650, 2655, 2789, 2791  
 \eqe@prehold ..... 3905, 3915, 3932, 3935  
 \eqe@prevProbZero ..... 2431, 2520, 2521, 2627, 2628  
 \eqe@priorw@content ..... 3714, 3749, 3755  
 \eqe@prtsepMrg ..... 3944, 3972, 3975

\eqe@prtsepPrb . . . . . 427,  
     428, 2740, 2770, 2908, 3278, 3959, 3962, 3963  
 \eqe@prtsepSoln . . . . . 3966, 3969, 4016, 4021, 4394  
 \eqe@ps@gobnxtpar . . . . . 2608  
 \eqe@ps@gobtop@r . . . . . 2605, 2607  
 \eqe@ptsFmt . . . . . 1479,  
     1484, 1520, 1529, 1562, 1563, 1568, 1570,  
     1576, 1661, 1698, 1699, 1701, 2046, 2563, 2565  
 \eqe@r . . . . . 1856, 1858  
 \eqe@reqPack . . . . . 417, 419  
 \eqe@rgi . . . . . 1763, 1764  
 \eqe@rPanel . . . . . 1949, 1957, 1962, 1969, 2016, 2017  
 \eqe@setfillinDefaults . . . . . 4671–4673, 4711, 4713  
 \eqe@setStartSolns . . . . . 3682  
 \eqe@setVRule . . . . . 3377, 3380, 3421, 3431  
 \eqe@showArg . . . . . 687, 690  
 \eqe@striphbox . . . . . 1142, 1143  
 \eqe@Strut . . . . . 2075, 2080  
 \eqe@subleftgutter . . . . . 1951, 1967, 1997  
 \eqe@SumryHoriz . . . . . 1387, 1389, 1441  
 \eqe@SumryVert . . . . . 1386, 1389, 1441  
 \eqe@tableadin . . . . . 2660, 2772  
 \eqe@tb@ship@out . . . . . 4192, 4196  
 \eqe@tb@ship@out . . . . . 4185, 4365  
 \eqe@temp . . . . . 2938, 2940, 2941  
 \eqe@tempbox . . . . . 2992, 2996, 2997, 3202, 3203  
 \eqe@tempcnta . . . . . 471, 3383, 3418, 3420, 3422, 3423, 3425  
 \eqe@Three . . . . . 42  
 \eqe@tmp . . . . . 656, 660, 664, 674–677,  
     2556, 2557, 2711, 2712, 3360, 3361, 3368, 3369  
 \eqe@tmp@exp . . . . . 27, 31, 245  
 \eqe@tmp@i . . . . . 26, 28, 30, 242–244  
 \eqe@tmpexp . . . . . 263, 264  
 \eqe@tmphold . . . . . 4048, 4049, 4052, 4053  
 \eqe@turnOffComment . . . . . 693, 737, 740, 798, 801  
 \eqe@turnOnComment . . . . . 688, 732, 734, 796  
 \eqe@Two . . . . . 42, 2791  
 \eqe@usedeffboxrule . . . . . 3042, 3055, 3066, 3102, 3188  
 \eqe@web0pts . . . . . 164, 165, 374  
 \eqe@wordNumbError . . . . . 2406, 2410, 2417  
 \eqe@wordNumb . . . . . 79, 2405, 2409, 2415, 2420  
 \eqe@workfill . . . . . 1829, 1833  
 \eqe@width . . . . . 1827, 1831  
 \eqe@writetoAux . . . . . 1236, 2250, 2253, 2738, 2772  
 \eqe@writetoSolns . . . . . 1229, 2250, 2253  
 \eqe@wrtLineKernal . . . . . 3201, 3265  
 \eqe@x . . . . . 3214,  
     3221, 3233, 3265, 3275, 3276, 3281, 3284, 3297  
 \eqe@y . . . . . 3265, 3276, 3404  
 \eqe@YES . . . . . 40, 55, 73, 80, 95, 119, 120, 122, 124, 127,  
     128, 139, 146, 149–151, 168, 176, 181, 369,  
     370, 377, 379, 381, 491, 498, 502, 504, 505,  
     560, 750, 761, 902, 926, 973, 1038, 1102, 1163,  
     1180, 1412, 1666, 1670, 1678, 1757, 1795, 2032,  
     2033, 2040, 2042, 2132, 2138, 2150, 2154, 2221,  
     2222, 2235, 2247, 2358, 2361, 2431, 2517, 2520,  
     2584, 2620, 2621, 2627, 2688, 2737, 2760, 2792,  
     2800, 2892, 2895, 3055, 3066, 3109, 3110, 3117,  
     3137, 3188, 3746, 4566, 4675, 4688, 4877, 4880  
 \eqe@Zero . . . . . 41, 2531, 2573, 2591, 2640, 2645, 2647, 2789  
 \eqe@zeroTotalsAllowed . . . . . 497, 498, 1667  
 \eqe@eachLabel . . . . . 1557, 1571, 2566  
 \eqe@AEFormatting . . . . . 291, 292, 296, 297  
 \eQE@calculateAllTotals . . . . . 1333, 2271  
 \eqe@currProb . . . . . 2898  
 \eqedbfalse . . . . . 3347  
 \eqedecPointSoln . . . . . 3965, 3968, 3989, 4006, 4427  
 \eqedepth . . . . . 1831, 1938, 1946,  
     1953, 1963, 1970, 1984, 1986, 1990, 1996, 2003  
 \eqedsplyOnlyFrst . . . . . 3901, 4008, 4425  
 \eqe@fillLines@bgonlystar . . . . . 3092, 3093, 3448, 3449  
 \eqe@fillLines@outlineonlystar . . . . . 3086, 3087, 3444, 3445  
 \eqe@GenProbNumfalse . . . . . 4434, 4436  
 \eqe@GenProbNumtrue . . . . . 4437  
 \eqe@GrandTotal . . . . . 2277, 2278  
 \eqe@ifnext . . . . . 4248, 4251  
 \eqlist (environment) . . . . . 3941  
 \eqEmail . . . . . 32, 893, 900  
 \eqEmail@argi . . . . . 898  
 \eqEmail@argii . . . . . 894, 896, 897  
 \eqemakeatitle . . . . . 1331, 1347  
 \eqemargin . . . . . 301, 308, 416, 424, 432, 1574,  
     1602, 1625, 1951, 2185, 2203, 2742, 2755, 2911,  
     2913, 2915, 3268, 3284–3286, 3996, 3997, 4376  
 \eqEndExamTotalColor . . . . . 525  
 \eqe@marginbox . . . . . 48, 50, 51, 2149  
 \eqe@marginboxleft . . . . . 50, 1620  
 \eqe@marginboxright . . . . . 48, 51, 1610  
 \eqe@onlinefalse . . . . . 117  
 \eqe@onlinetrue . . . . . 119  
 \eqe@PANELCUT . . . . . 1887, 1894  
 \eqepanelheight . . . . . 1840, 1844, 1845, 1848, 1934, 1935  
 \eqepanelwidth . . . . . 1839, 1843, 1847  
 \eqepartsquestions (environment) . . . . . 4386  
 \eqepques@itemsep . . . . . 4388, 4396  
 \eqepques@parsep . . . . . 4387, 4395  
 \eqepques@topsep . . . . . 4386, 4397  
 \eqepquesitemsep . . . . . 4388, 4391  
 \eqepquesparsep . . . . . 4387, 4390

\eqepquestopsep	4386, 4389	\eqExerSolnHeader	2766
\eqeques@itemsep	2191, 2205, 4378, 4389, 4391	\eqexheader	1101, 1114, 4489, 4499
\eqeques@listparindent	2192, 2208, 4381	\eqexheader@wrapper	1100, 1114, 4489, 4499
\eqeques@parsep	2190, 2204, 2263, 4377, 4390	\eqexlisttabheader	2769
\eqeques@topsep	2189, 2206, 4379	\eqExt	3795, 3799, 3800
\eqequesitemsep	2191, 2195, 4371	\eqExtArg	141, 4403
\eqequeslistparindent	2192, 2196, 4372	\eqfititin	507, 3023, 4487, 4497
\eqequesparsep	2190, 2194, 4370	\eqforinstrfalse	12, 13
\eqequestopsep	2189, 2193, 4369	\eqforinstrtrue	11
\eqeSetExamPageParams	436, 458	\eqforpaperfalse	240
\eqeSolnItemMngt	2198, 2202, 4375	\eqforpapertrue	157, 159, 161
\eqeSumryHoriz	48, 1389, 1391	\eqfortextbookfalse	10
\eqeSumryVert	1386	\eqfortextbooktrue	9
\eqetmplengtha	481, 1469, 1470, 1498, 1499, 1780, 1784, 1787, 3036, 3037, 3198, 3200, 3268–3270, 3273, 3274, 3278–3281, 3285, 3290–3292, 3294, 3295, 3298, 3299, 3302, 3303, 3308, 3309, 3311, 3312	\eqglobalversionfalse	669
\eqetmplengthb	482, 3218, 3270, 3292, 4694–4696, 4698, 4699, 4704, 4747, 4751, 4752, 4755, 4759, 4765, 4769, 4780, 4784, 4785, 4787, 4844, 4845	\eqglobalversiontrue	703
\eqevtranstobox	57, 1664, 1665, 1672, 1681	\eqgrii	323
\eqeWrtExamTitleToSolns	2221–2223, 2247	\eqgriii	310
\eqex@coverpage	56, 152, 1536, 2946	\eqleftmargin	483, 1573, 1638
\eqex@coverpageSubjectFmt	1370, 1429	\eqleftmarginbox	1555
\eqex@coverpageTitleFmt	1373, 1435	\eqlocalversionfalse	670, 2559, 2714
\eqex@coverpageUniversityFmt	1367, 1423	\eqlocalversiontrue	776
\eqExam	1641, 1642, 1644	\eqobeylocalversionfalse	125, 807
\eqExam@Ans@ck@sq@f	1051, 1099	\eqobeylocalversiontrue	126, 771
\eqExam@Ans@ck@sq@l	1023, 1098	\eqp@rtc@lcm@rk	2761, 2840
\eqExam@Ans@sq@f	989, 1097	\eqpanelbox	64, 1838, 1842–1845
\eqExam@Ans@sq@l	960, 1096	\eqpointLabel	1561, 2048
\eqExam@argi	894	\eqpointsLabel	1559, 2047, 2049
\EqExam@SubmitURL	910, 932	\eqpointsofar (environment)	19
\eqexamargi	2240, 2241, 2243	\eqpointsthispage (environment)	19
\eqexamargii	2237–2239, 2241, 2244, 2250, 2251, 2259, 2260	\eqPriorVspace	1104
\eqexamCFG	19, 25	\eqptLabel	1556, 1569, 1571, 1577, 1662, 2564, 2566
\eqexamdefReq	1110, 1113	\eqptsLabel	1555, 1569, 1572, 1577, 1663, 2564, 2566
\eqexammargin	424	\eqrightmarginbox	485, 1578, 1639
\eqExamName	32, 872, 881	\eqSavedComment	409, 3731
\eqExamName@argi	873, 879	\eqSID	32, 884, 890
\eqExamName@argii	873, 876, 878, 1406	\eqSID@argi	884, 888
\eqExamNumPagesSolns	1251, 1256, 1257	\eqSID@argii	884, 886, 887, 1407
\eqExamPageLayout	446	\eqSolvExCmds	3515, 3538
\eqExamPriorVspace	1084, 1104	\eqsolutionshook	1308, 4413, 4415
\eqExamRunHead	465, 1295, 1318	\eqtemptokena	586, 612, 623, 625, 627
\eqexamssubject	1364, 1431	\eqtemptokenb	587, 622, 624, 626
\eqexcoverpage	56, 1350	\eqTopOfSolnPage	279
\eqexcoverpagedesign	1358, 1362	\equalCellSizesOff	107, 3080, 3116, 3192, 3196, 3206, 3319, 3321
		\equalCellSizesOn	107, 3079, 3317
		\equsecolorfalse	156, 157
		\equsecolortrue	159, 161
		\eqWLSpacing	2986, 3112
		\eqWriteLine	2971, 2972, 2974, 2976, 2978, 2980, 2983, 3156, 3157, 3208, 3215, 3237, 3434, 3439

\eqWriteLineBlankFill .....	2978, 3004, 3005	\exlabelformatwp .....	2315
\eqWriteLineColor .....	2984	\exp@temp .....	676, 691, 695
\eqWriteLineDashFill .....	2976, 3002, 3050	\expGT .....	2288, 2289
\eqWriteLineDashVFill .....	3012, 3051	\exPrtsep .....	3963
\eqWriteLineDots .....	2974, 2998, 3053	\ex rtnlabelformat .....	2324, 2328, 4488, 4498
\eqWriteLineFill .....	2972, 2980, 2983, 2989, 3047, 3059, 3160	\ex rtnlabelformatwp .....	2325, 2329
\eqWriteLineVDots .....	3009, 3054	\exsecrunhead .....	2338, 2339
\eqWriteLineVFill .....	3006, 3048, 3060, 3161	\exsectitle .....	2334, 2335
\eqwritetomarginsfalse .....	14	\exsectitletext .....	2333, 2334, 2336
\eqwritetomarginstrue .....	15	\exsllabelformat .....	2316, 4005
\eqx@separationrule .....	150, 505, 506, 2150, 2154	\exsllabelformatwp .....	2319, 4007
\evensidemargin .....	441, 4139, 4143, 4145, 4254, 4323, 4340, 4347	\exsolafter .....	2310, 3494, 3497
\every@qRadioButton .....	978, 1042		
\every@RadioButton .....	978, 1013, 1042, 1075		
\every@sqRadioButton .....	1014, 1076		
\everypar .....	2759, 2760, 3723		
\eWebCustomize .....	248		
\ex@solns .....	294, 306, 322, 1215, 1223, 1978, 4276–4278, 4411		
\Exam .....	576, 598, 643		
\exam .....	4476		
exam (environment) .....	2213		
\examAnsKeyLabel .....	865, 867		
\exambegdef .....	2085, 2258		
\examEmailLabel .....	891, 892		
\examenddef .....	2130, 2262		
\examenvfalse .....	2173, 4038		
\examenvtrue .....	2127		
\examNameLabel .....	32, 868, 869		
\examNum .....	574		
example (environment) .....	4482		
example* (environment) .....	4492		
\examplenoname .....	145, 4481		
\examSIDLabel .....	882, 883		
\examSolnHeadFmt .....	1215, 4452		
\excludecomment .....	522, 676, 695, 4055, 4056, 4283, 4313, 4316		
\execjs .....	381		
\ExecuteOptionsX .....	100, 115, 116, 119, 124, 206		
\exer@solnheadhook .....	753		
\exercisesAtEndOfChapter .....	4283		
exerquiz0pts (option) .....	9		
\exerSolnHeader .....	4446		
\exerSolnInput .....	4409		
\exerSolnsHeadnToc .....	184, 4406, 4419		
\exerwparts@cols .....	2384, 4909		
\exlabel .....	2308, 4485, 4486, 4495, 4496		
\exlabelformat .....	2312, 2313, 2315, 4001, 4486, 4496		
			<b>F</b>
		\F .....	936, 938, 940, 942, 944, 1582, 1588
		\fbInsSolnsStyle .....	4406–4408
		\fbox .....	1453, 1464, 1487, 1493, 1532, 4626, 4627
		\fboxrule .....	1465,
			1494, 1551, 3253, 4578, 4623, 4752, 4785, 4895
		\fboxsep .....	1465, 1494,
			4197, 4578, 4623, 4718, 4752, 4785, 4844, 4895
		\Ff .....	881, 890, 954, 1093, 4898
		\FfMultiline .....	1093, 4898
		\FfNoToggleToOff .....	954
		\FfRequired .....	881, 890
		\FHidden .....	936, 938, 940, 942, 944, 1582, 1588
		\fieldName .....	967, 975, 1002,
			1010, 1031, 1039, 1064, 1071, 1085, 1093, 1580,
			1583, 1587, 1591, 2363, 2373, 4882, 4893, 4898
		\filename@base .....	4507, 4508, 4536, 4537
		\filename@ext .....	4506, 4508, 4535, 4537
		\filename@parse .....	4505, 4534
		\fillerBgIm@ge .....	3348, 3349, 3409, 3414
		\fillerCustomBg .....	108, 3348
		\fillerLinesAlignDef .....	99, 2009, 3018, 3073
		\fillerLinesOnLeftMargin .....	99, 3017, 3074
		\fillin .....	153, 2346, 2382, 2386, 4670, 4907, 4911
		\fillinColor .....	525
		\fillineol .....	152, 4681, 4684, 4688
		\fillineol@i .....	4690–4692
		\fillineol@ii .....	4692, 4693
		\fillineolNoCBMsg .....	4680, 4690
		\fillineolTooLongMsg .....	4676, 4695, 4699
		\fillInFormatDefault ..	150, 2396, 4405, 4619, 4620
		\fillinTotalHeight ..	4806, 4827, 4852, 4873, 4893, 4899
		\fillinWidth .....	2389
		\fillLinesLineWidth .....	1783, 1784, 3173
		\fillLinesNumFmt .....	101, 3096–3098
		\fillTypeBlankLine .....	2978, 3067
		\fillTypeDashLine .....	2976, 3064

\fillTypeDefault	2967, 2980	forcolorpaper (option)	9
\fillTypeDots	2974, 3065	forcolorpaper* (option)	9
\fillTypeGrid	2982, 3068, 3629	forinstr (option)	4
\fillTypeHRule	2972, 3063	\foritem	2872
\firstemittrue	4039	\foritem@cont	2879, 2884, 2885
\firstitemfalse	2198, 4033	\forleadinitem	2872
\firstitemtrue	2212, 4032, 4385	\format	4568
\firstPageOfExam	1258	forpaper (option)	9
\firstPartLtr	4425, 4430	\forproblem	2872
\fitwidth	4568	forstudent (option)	4
\fl@Cnt	3486, 3491, 3502, 3504	fortextbook (option)	4
\fl@CutName	3486, 3492, 3654, 3691, 3718, 3733	\forVersion	134, 597, 606, 644, 648, 669, 2556, 2711
\fl@firstpassfalse	3222, 3541	\FPdiv	2291
\fl@firstpasstrue	3180, 3679	\FPmul	2293
\fl@getcontent	3501, 3691, 3733	\FPround	2294
\fl@iSmash	3396, 3398, 3401	\fracPrt	3345
\fl@nRows	3220, 3242, 3356	\frstProbNumShownfalse	2664, 4426
\fl@oSmash	3396, 3398, 3400, 3456	\frstProbNumShowntrue	4430, 4433
\fl@set@nnotContStrSkip	3176, 3181	\ftb@argi	3884
\fl@vsplitandplace	3530, 3654, 3718	\ftb@CloseEqeList	123, 3904
\fl@wlspacing	3099, 3100, 3112	\ftb@defineInsSpan	123, 3884, 3914
\flbaselineskip	3490, 3561, 3566, 3571	\ftb@endprobstarCks	2667, 2709
\fleqnOff	358, 359	\ftb@EndSpanPrts	3889, 3893
\fleqnOn	358, 359	\ftb@EqeListPrtsFmt	123, 3895, 3902, 3918
\fLEqu@lLineWidth	3210, 3211, 3317, 3319, 3341	\ftb@InsSpan	3885, 3886, 3921
flextended (key)	7	\ftb@isANSListOpenfalse	3844, 3859, 3936
\flextendedInput	101, 102, 256	\ftb@isANSListOpentrue	3929
\flfboxrule	2991, 3001, 3006, 3011, 3187, 3188, 3194, 3234, 3235, 3251, 3258, 3260, 3281, 3297, 3325, 3328, 3339, 3357, 3375, 3428, 3477, 3543, 3587, 3591, 3602, 3606	\ftb@OpenEqeListPrts	123, 3899, 3921
\flfrstspltfalse	3585, 3600	\ftb@spanPrts	123, 3885, 3891
\flfrstspltrue	3255, 3471	\ftb@tmp@exp	4477, 4478
\fliPartNo	2886, 2894	\ftbFmtChapter	4458, 4464
\flnum	3096, 3097	\ftbInputBookAux	4504
\flPageBreakMsg	3021	\ftbInputEqTextb	4562, 4564
\fls@vebaselinelineskip	3489, 3540	\ftbInputSolnFiles	4533
\flSeparateCutNames	111, 3486	\ftblabel	4525, 4531
flytype (key)	100	ftbsolns (option)	7
\flwriteexsol@fter	3493, 3516, 3523, 3526	fullwidhttext (environment)	4330
\font	1150	\fvsizeskip	2217
\footnotesize	3346		
\footskip	444, 455, 4090, 4091	<b>G</b>	
\forceEqu@lCells	3209, 3322	\g@addto@macro	132, 134, 682, 684, 686
\forceEqualCellsfalse	3115, 3191, 3195, 3205, 3320	\getDimSSPanel	64, 1841, 1888
\forceEqualCellstrue	3318	\getSpaceLeftOnPage	80, 2453
\forceNoColor	525	\gobblelabel	4531
\ForceNoColorfalse	160	\gobbletoEndEXt	141, 3796, 4402
\forceNoColorSet	551, 564, 567	\gobtdot	3345, 3361, 3369
\ForceNoColortrue	162, 566	\goodbreak	1216
		\gridHLineFill	3047, 3050, 3053, 3059, 3156, 3160, 3208
		\gridIndent@dj	3352–3354, 3402, 3403
		\gridIndentAdj	108, 3351

\gridpgbrkfalse	3174, 3440, 3655, 3681	\ifAB	576, 577, 666
\gridpgbrktrue	3223	\ifaebshowgrayletters	190
gridtype (key)	100	\ifallowcircmc	113, 1149
\gridtypeselected	3043, 3045, 3103, 3159	\ifanswerkey	70,
\gridVLineFill	3048,	91, 255, 421, 866, 999, 1061, 2010, 2323, 2928,	
	3051, 3054, 3060, 3157, 3161, 3378, 3381, 3420	2929, 3513, 3523, 3526, 3538, 3621, 3637, 3663	
\grpANSDelimiter	123, 3907, 3932	\ifc@sewrep	2404, 2405, 2408, 2409
<b>H</b>			
\halfHtPtBox	1631, 2133, 2432, 2467, 2482	\ifchapterexercises	4266, 4311
\hangafter	966, 994, 1030, 1056	\ifcont@nnot	2920, 3665, 3743
\hangindent	966, 994, 1030, 1056	\ifdim	316, 1934, 2144, 2183, 2383, 2428, 2451,
\hangSolWPrtsFmt	4024	2463, 2465, 2480, 2484, 3558, 3560, 3570, 3814,	
\hb@xt@	2996, 2997, 3001, 3202	3996, 4130, 4695, 4699, 4722, 4811, 4856, 4908	
\hbadness	4078	\ifdispl@yPoints	517,
\hCommSpace	2072	1544, 2536, 2560, 2716, 2822, 2832, 2836, 2864	
\HEADERcolor	4097	\ifdisplayworkarea	193, 1756, 1794, 3732, 3735, 3745
\headheight	437, 452, 4150	\ifdisplayworkareaOff	10
\headsep	439, 453, 4150	\ifdisplayworkareaOn	10
\height	1604, 1614, 1621, 1672, 1681	\ifDoNotRecordThisExam	2226, 2232, 2267
\glue	3168,	\ifeq@globalshowsolutions	235, 350, 396, 1869, 1906
	3170, 3172, 3275, 3281, 3297, 3403, 3418, 3430	\ifeq@hidesolution	234, 349, 395, 2765
\hidden@ttr	2514, 2515, 2518, 2519, 2551	\ifeq@nolink	238, 353, 399
\hiddenbox	4568	\ifeq@nosolutions	236, 351,
\hideproofing	10, 189	356, 397, 422, 903, 926, 982, 1046, 1901, 1940,	
\Hidesymbol	175	1991, 2359, 2767, 3730, 4308, 4412, 4836, 4878	
\hInstrSpace	2029, 2035	\ifeq@proofing	237, 352, 398, 1242, 2352, 4778
\hline	1549–1551	\ifeq@solutionsafter	....
\hrule	1137, 1138, 2991	229, 348, 393, 394, 423, 903, 926, 1793,	
\hrulefill	3005	1824, 1830, 1835, 1868, 1892, 1897, 1941, 1942,	
\hsc	2075, 2082	1945, 1960, 1979, 2000, 2017, 2360, 2768, 4879	
\hspace	2035, 2040–2042	\ifeqcusomdesign	6, 457
\htPtBox	1635	\ifeqe@flexended	111, 3664
\hyper@anchor	2056, 2939	\ifeqe@fnosolns	3472, 3732, 3735, 3744
\hypersetup	816, 821, 827, 830	\ifeqe@nopoints	488, 1686
\hypertarget	1101, 4449	\ifeqedb	3347, 3404, 3405, 3422, 3432,
<b>I</b>		3582–3584, 3586, 3590, 3597–3599, 3601, 3605	
\i@eqe@getiii@pts	4656, 4658	\ifeqeGenProbNum	4436, 4438, 4439
\iacvspace	2899, 2900, 2902, 2905, 3022	\ifeqeonline	117, 254
\ic@vspace	2899	\ifeqexamCFG	19, 24
\ic@vspacedefault	95, 2901, 2902	\ifeqforinstr	13
\idinfoHighlight	870, 871	\ifeqforpaper	240, 355, 401, 4447
\if@bypasseqexamheading	204, 1538, 1686, 3780	\ifeqfortextbook	10, 417, 1119, 1341, 2126,
\if@eqalignfilllinestoleft	....	2173, 2178, 2662, 2709, 2723, 3779, 4362, 4562	
	3016, 3221, 3267, 3307, 3329, 3395, 3723	\ifeqglobalversion	593, 602, 669, 762, 2555, 2710
\if@eqeuseclassmaketitle	202, 1344	\ifeqlocalversion	670, 2555, 2710
\if@eqlinedfiller	3182, 3483, 3658	\ifeqbeylocalversion	125, 751, 769, 775
\if@equsedim	1930, 3013	\ifequsecolor	156
\if@templocalversion	671, 807	\ifeqwritetomargins	15, 4364
		\ifexamenv	4038
		\iffalse	2228
		\IfFileExists	197, 4565

\iffirstemit ..... 4039  
\iffirstitem ..... 2197, 2198  
\iffirstpass ..... 3178, 3531  
\iffirstsplit ..... 3471, 3545, 3585, 3600  
\ifforceEqualCells ..... 1782, 3316, 3323  
\ifForceNoColor ..... 160, 563, 566  
\iffirstProbNumShown ..... 4426, 4432  
\iftb@isANSListOpen ..... 3844, 3917  
\ifgridpgbrk ..... 3174, 3437  
\ifiscarryover ..... 4165, 4180, 4248  
\ifisinlineans ..... 3910  
\ifisinstred 2130, 3793, 3811, 3833, 3909, 3939, 4110  
\ifisleadin ..... 2732, 4028  
\ifismarginans ..... 2130, 3833, 3913, 3938, 4110  
\ifisOnline ..... 139  
\ifisstudented ..... 3788, 3812  
\ifkeepdeclaredvspacing ..... 3683  
\ifkeyalt ..... 7, 87, 90  
\ifkeyOrkeyalt ..... 91  
\ifKV@eqefillLines@bgonly ..... 3110, 3118,  
  3128, 3193, 3212, 3234, 3408, 3429, 3484, 3659  
\ifKV@eqefillLines@outlineonly ..... 3109,  
  3138, 3148, 3189, 3235, 3276, 3419, 3433, 3661  
\ifKV@eqefillLines@topline ..... 3166, 3213, 3373, 3436  
\ifKV@eqFillin@autolift ..... 4720, 4816, 4861  
\ifKV@eqFillin@boxed ..... 4719, 4730,  
  4739, 4748, 4750, 4781, 4783, 4789, 4796, 4831  
\ifKV@eqFillin@enclosesoln ..... 4843  
\ifKV@eqFillin@fitwidth ..... 4779  
\ifKV@eqFillin@underline ..... 4770, 4773  
\ifl@stDispl@yPoints ..... 520, 2434  
\ifmarginsonleft ..... 4135, 4137, 4155, 4258  
\ifmmode ..... 4596, 4744, 4790, 4809  
\ifnosolutions ..... 356  
\ifObeyPTsStar ..... 2568, 2577  
\ifOKToWriteExamData ..... 305, 321, 1219, 1222, 1231  
\ifpdf ..... 115  
\ifpreview ..... 239, 354, 400  
\ifshowlsols ..... 3809  
\ifsolutionsafter ..... 230, 394  
\ifsolutionsAtEnd ..... 72, 1503  
\ifsolutionsonly .....  
  233, 293, 304, 320, 522, 1222, 1230, 4411, 4414  
\ifsp ..... 4707, 4768  
\iftb@shipoutPermitted ..... 4185, 4188  
\iftherearesolutions ..... 4413  
\ifuseNumForParts ..... 2885  
\ifuserectforms ..... 1194  
\ifvoid ..... 3244, 3555, 3581, 4210, 4235  
\ifvspacewithsolns ..... 86,  
  93, 337, 420, 1118, 1248, 1939, 3644, 4279, 4839  
\ifWithinANSGrp ..... 2668, 3843, 3851, 3870, 3929, 3930  
\ifwithinparts ..... 2910, 3271, 3289, 3509, 3694, 3737  
\ifwithinoldoc ..... 961, 990, 1025, 1052,  
  2188, 2202, 2209, 2212, 4375, 4382, 4385, 4427  
\ifwriteVertic@lFLines ..... 3175, 3406, 3623  
\ifxetex ..... 116  
\ignorePTsStar ..... 84, 2570  
\ii@eqe@getiiiOpt ..... 4660, 4662  
\iii@eqe@getiiiOpt ..... 4657, 4661, 4664–4666  
\importdljs ..... 381  
\include@quizsolutions ..... 2344  
\include@solutions ..... 4269, 4272  
\include@solutions@chapter ..... 4269, 4271  
\includecomment ..... 523, 691, 4055, 4056, 4284, 4315  
\includeexersolutions ..... 368, 4270, 4275  
\initChapAfterSolns ..... 4352  
\inlineans ..... 3786  
\input ..... 1108, 1109, 1833,  
  1889, 1948, 1955, 1965, 1974, 3540, 4296, 4301  
\InputIfFileExists ..... 20,  
  103, 136, 244, 249–252, 4420, 4514, 4538, 4563  
\inputlineno ..... 3704, 3771  
\inputRandomizeChoices ..... 135, 136  
\insert@circlesymbol ..... 1014  
\insertContAnnot ..... 2443, 2927  
\insertGrayLetters ..... 996, 1008, 1058, 1070  
\insertpageifcarryover ..... 4246  
\insertPointsBoxPDF ..... 1578, 1605  
\insertTotalsBoxPDF ..... 1578, 1615, 1622, 1673, 1682  
\insMargHead ..... 4104  
\insMidMarg ..... 2131, 3824, 3829, 3835, 3839,  
  3904, 3931, 3934, 4076, 4100, 4101, 4105, 4111  
\insProbHead ..... 4104, 4477  
instructions (environment) ..... 2027  
\instructionsColor ..... 525  
\insTxtFieldIdInfo ..... 33, 879, 888, 898, 901  
\intPrt ..... 3345, 3362, 3385, 3390  
\is@bgonly ..... 3108, 3110, 3117, 3125, 3133  
\is@outlineonly ..... 3108, 3109, 3137, 3145, 3153  
\is@uto ..... 2590, 2649  
\iscarryoverfalse ..... 4165, 4210  
\iscarryovertrue ..... 4211  
\isInExamEnv ..... 489, 2225, 2235  
\isinlineansfalse ..... 3820, 3828, 3830, 3838, 3840  
\isinlineanstrue ..... 3823, 3825, 3834, 3836  
\isinstredfalse ..... 3812, 3818  
\isit@uto ..... 2591, 2592, 2650  
\isItD@ ..... 2584, 2656, 2687

\isitleadin ..... 2737 \KV@eqefillLines@toplinefalse ..... 3041, 3114, 3623, 3670, 3751  
 \isleadinfalse ..... 2732 \KV@eqefillLines@toplinetrue ..... 3189, 3193  
 \isleadintrue ..... 2737 \KV@eqFillin@boxedtrue ..... 4725  
 \ismarginansfalse ..... 3819, 3823, 3824, 3834, 3835 \KV@eqFillin@underlinefalse ..... 4570, 4719  
 \ismarginanstrue ..... 3828, 3829, 3838, 3839 \KV@eqFillin@underlinetrue ..... 4569  
 \isparshapeExpanded ..... 2733, 2758, 2760  
 \isProbEnv ..... 2505, 2517, 2620  
 \isProbStarEnv ..... 2603, 2621  
 \isstudentedfalse ..... 3811  
 \isstudentedtrue ..... 3817  
 \istabularexer ..... 3272, 3293, 3510, 3694, 3737  
 \item ..... 2199,  
     2212, 2877, 2878, 2911, 3950, 4337, 4385, 4401  
 \itemindent ..... 2207, 3949, 4333, 4380, 4398  
 \itemPTsEaTxt ..... 2565, 2834  
 \itemPTsFormated ..... 2563, 2823, 2834, 2852  
 \itemPTsTxt ..... 2563, 2824, 2852  
 \itemsep ..... 2205, 3949, 4333, 4378, 4396  
 \itsforleadinitem ..... 2734, 2895

**J**

\JS ..... 928

**K**

\kdvsp@Restore ..... 3685, 3688, 3693, 3758, 3759  
 \kdvsp@SAVE ..... 3683, 3686  
 \keepdeclaredvspacingfalse ..... 516  
 \keepdeclaredvspacingtrue ..... 515  
 \kern ..... 1201,  
     1467, 1488, 1496, 1533, 2146, 2263, 3001, 3423,  
     3485, 3660, 3662, 3920, 4097, 4215, 4218, 4240  
 \keyaltfalse ..... 89  
 \keyalttrue ..... 88  
 keys:  
     align ..... 101  
     bgcolor ..... 101  
     bgonly\* ..... 101  
     color ..... 100  
     flextended ..... 7  
     fltype ..... 100  
     gridtype ..... 100  
     numbers ..... 99  
     numbersep ..... 100  
     outlineonly\* ..... 101  
     topline ..... 100  
 \keywords ..... 811  
 \KV@eqefillLines@bgonlyfalse ..... 3089, 3119, 3124, 3132, 3190, 3450  
 \KV@eqefillLines@outlineonlyfalse ..... 3083, 3139, 3144, 3152, 3194, 3446

\KV@eqefillLines@toplinefalse ..... 3041, 3114, 3623, 3670, 3751  
 \KV@eqefillLines@toplinetrue ..... 3189, 3193  
 \KV@eqFillin@boxedtrue ..... 4725  
 \KV@eqFillin@underlinefalse ..... 4570, 4719  
 \KV@eqFillin@underlinetrue ..... 4569

**L**

\l@stDispl@yPointsfalse ..... 520, 2561, 2717  
 \l@stDispl@yPointstrue ..... 2560, 2716  
 \l@stPO ..... 75, 76, 81, 96, 169, 177, 182  
 \label ..... 2122, 2304, 2934, 4525, 4526, 4531, 4532  
 \labelsep ..... 2209, 2210,  
     2752, 3886, 3944–3946, 4332, 4382, 4383, 4399  
 \labelwidth ..... 2203, 2211, 2751, 2752, 3268,  
     3290, 3942, 3946, 4332, 4376, 4384, 4394, 4400  
 \Large ..... 1201, 3023  
 \large ..... 1368, 1371, 1374, 4462  
 \lastPageOfExam ..... 1258  
 \lastPageTotal ..... 2461, 2478, 2781, 2782  
 \lastparttotaled ..... 1640, 1652  
 \lastskip ..... 2041  
 \lccode ..... 1878, 1884, 1987, 1992  
 \le ..... 748  
 \leaders ..... 2990, 3006  
 \leadinIndent ..... 2743, 2755, 2757, 3724  
 \leadinIndentLength ..... 2747, 2755–2757  
 \leadinIndentPrtSep ..... 1790, 1826, 1981, 2741, 2746, 2750, 2753, 3308  
 \leadinitem ..... 89, 2598, 2606, 2659, 2719, 2882, 2883  
 \leadinitemWarningStar ..... 2595, 2645  
 \leftmargin ..... 2211, 2751, 3946, 4336, 4384, 4400  
 \leftmarginii ..... 2750, 2751  
 \leftmarginPtsEaTxt ..... 54, 1566, 1570  
 \leftmarginPtsTxt ..... 54, 1565, 1568  
 \leftmark ..... 4257, 4327  
 \leftskip ..... 1790  
 \lfooteqe ..... 1301  
 \lhead ..... 1290  
 \lheadeqe ..... 1284  
 \lheadSol ..... 1308  
 \lift ..... 151  
 \lineskip ..... 3485,  
     3544, 3577, 3587, 3591, 3602, 3606, 3660, 3662  
 \link@Content ..... 965, 983, 1029, 1047  
 \linkcolor ..... 525  
 \linkContentFormat ..... 949, 951  
 \linkContentWrapper ..... 951, 965, 1029, 1204  
 links (option) ..... 7  
 \listparindent ..... 2208, 4335, 4381

\llap	1158, 1243, 2342, 3167, 3169, 3247, 3582–3584, 3586, 3590, 3597–3599, 3601, 3605	
\load@exerquiz	122, 142, 377, 379, 4404	
\load@web	120, 122, 141, 369, 370, 560	
\longTitleText	592	
\loop	710, 726, 790, 2889	
\lower	1162, 1209, 4090	
\lowercase	729, 793, 1879, 1884, 1987, 1992, 2512, 2887	
lsol (environment)	4055	
\lsols	3786	
<b>M</b>		
\makeAnsEnvForSolnsAtEnd	279, 284	
\makeatletter	4513	
\makeatother	4524	
\makeDoNum	2403, 2804, 2808	
\makeOutOfNum	2407, 2804, 2805	
\makeRefsNums	1275, 1283	
\makeRoomForProb	2234, 2424, 2458, 2526, 2631, 4484, 4494	
\maketitle	1322	
\maketitledesign	1322	
\makeVgrid	1781, 2973, 2975, 2977, 2979, 2981, 2983, 3025, 3113, 3192, 3196, 3204, 3219, 3222, 3231, 3242, 3243, 3622, 3625, 3666, 3671, 3747, 3752	
\manswers	288	
\manswers@sq	288	
\manualcalcparts	91, 2657, 2785	
\marginans	3786	
\marginboxdesign	... 53, 1547, 1605, 1615, 1622, 1629, 1673, 1682	
\marginparafterhook	2537, 2538, 2782, 2823, 2833, 2866	
\marginparpriorhook	2539, 2826, 2837, 2867	
\marginparsep	442, 1574, 1602, 1612, 1625, 1674, 1680, 4138, 4143, 4156, 4254	
\marginparwidth	443, 4125	
\marginpoints	154, 483, 485, 487, 491, 1544, 2528, 2529, 2813, 2816, 2819, 2831, 2838, 2853, 2863	
\marginpointsboxtext	1576, 1606, 1616, 1623, 1629	
\marginpointtext	54, 1562, 1573	
\marginsonleft	3786	
\marginsonleftfalse	4135	
\mark	1541, 1542, 1687, 2131, 4120	
\markEndFor	1752	
\markEndtFor	1751	
\markerTotalFmt	1715	
\markNumQsFor	1751	
\markStartFor	1751	
\MarParBoxFmt	4076, 4202, 4216	
\marparboxwidth	4123, 4128, 4132, 4133	
\max (option)	8	
\maxdepth	3546, 3550, 3560	
\MCcolor	1202, 1203	
\measurePtBoxHt	56, 1628, 1637	
\medbreak	4452, 4463	
\medskipamount	4483, 4493	
\MidMargcolor	4084	
\midMargFmt	4085, 4087	
\minipage	1983, 1986, 1996, 2003, 3512	
\month	855, 857, 859	
\mp@Width	1892, 1942, 1986	
\mrgDecPt	3971	
\mrgDigitFmt	3951	
\mrgNumPrtsep	3971	
\mrgPartFmt	3953	
\mrgPrtsep	3971	
\multicolsep	414	
\multiply	766, 785, 2289, 2698, 2703, 3367, 3371, 3387, 3392	
myconfig (option)	5	
myconfigi...myconfigvi (option)	5	
<b>N</b>		
\nbaselineskip	81, 2494, 4503	
\nbaselineskipReset	2495, 2496	
\nDoNum	2400, 2402, 2403, 2632	
\needsModArith	750, 752, 761	
\NeedsTeXFormat	4550	
\neutralizeparfixes	2619	
\newbox	479, 2992–2994, 4042–4044	
\NewCommentCutFile	4285, 4291, 4302	
\newdimen	1128, 1130, 1839, 1840, 3477, 3987	
\newsavebox	1127, 1762, 1838	
\newwrite	1815, 4277	
\nExam	574, 582–585	
\nlastItem	2775, 2780	
\nLocalSelection	... 749, 751, 768, 778, 779, 781, 782, 787, 795	
\nLocalVersions	749, 762, 765, 766, 781, 784, 785, 804	
\nNumberOfP@rts	2219, 2248, 4451	
\nobreak	1092, 1994, 3897, 4098	
\noExamTitleInSolns	2223	
noHiddensolutions (option)	9	
nohiddensolutions (option)	9	
\nointerlineskip	1755	
\nolinkcolor	525	
nomarginwrite (option)	4	
noparttotals (option)	5	
\NoPoints	36, 489, 492	
nopoints (option)	5	

\noProbHeader	4474, 4476	\OKToWriteExamData	true	1220
\normalbaselines	3533, 4077	\OnBackOfPage		2930
\normalcolor	2039, 3246, 4061, 4063, 4086, 4214	online (option)		7
\normalfont	431, 464, 2038, 2041, 2043, 2078, 2082, 2391, 2740, 3977, 3988, 4077, 4086, 4619	\openout		1862, 3508, 4278
\normalsfcodes	4076	\optionalPageMatter		845
\normalsize	431, 464, 1324, 2038, 2043, 2078, 2082, 2334, 2335, 3977, 3988, 4077, 4086, 4587, 4596	\optionalpagematter		846, 847, 1439
noseparationrule (option)	5	options:		
\NoSolutions	509, 511	allowcirc4mc		7
nosolutions (option)	9	allowrandomize		8
\NoSpaceToWork	145	answerkey		6
nospacetowork (option)	6	cfg		5
nosummarytotals (option)	5	coverpage		6
\NoTotals	44, 500	coverpagesumry		6
nototals (option)	5	dvipdfm		11
\nOutOfNum	2407, 2412, 2414, 2633	dvipdfmx		11
\noxcolor	10	dvips		11
\noZeroTotals	39, 497	dvipsone		11
nozerototals (option)	5	email		7
\nPAGESofQues	1248, 1255	exerquizOpts		9
\nPAGESofSols	1251	forcolorpaper		9
\nPAGESonExam	43, 1247, 1254, 1287	forcolorpaper*		9
\nPAGESonQues	43	forinstr		4
\nPAGESonSols	43	forpaper		9
\nPctDecPts	2283	forstudent		4
\nQuesInExam	70, 2050, 2054	fortextbook		4
\null	4246	ftbsolns		7
\NumberOfParts	2165	links		7
numbers (key)	99	max		8
numbersep (key)	100	myconfig		5
\numFirstPageOfExam	1273	myconfigi...myconfigvi		5
\numLastPageOfExam	1273	noHiddensolutions		9
\NUMPAGES	1504, 1505, 1507, 1508, 1510	nohiddensolutions		9
\numpoints	2498, 2514, 2515, 2524, 2533, 2534, 2537, 2538, 2540, 2629, 2638, 2649, 2657, 2787, 2796, 2797, 2824, 2827, 2838, 2852, 2853, 2858, 2860, 2862	nomarginwrite		4
\numpointsEmpty	2523, 2524, 2529	noparttotals		5
\numVersions	132, <u>588</u> , 653, 708, 720, 746	nopoints		5
<b>O</b>				
obeylocalversions (option)	8	noseparationrule		5
\obeyPTsStar	84, 2569	nosolutions		9
\ObeyPTsStarfalse	2570	nospacetowork		6
\ObeyPTsStartrue	2568, 2569	nosummarytotals		5
\oddsidemargin	440, 449, 1297, 1298, 1318, 1319, 1335, 1336, 1419, 1421, 1427, 1433, 2336, 4138–4140, 4142, 4145, 4322, 4323, 4339, 4346	nototals		5
\offinterlineskip	3179	nozerototals		5
obeylocalversions		online		7
parttotalsonleft		parttotalsonright		5
pdf		pdftex		7
pointsonboth		pointsonleft		5
pointsonleft		pointsonright		5

preview	9	\panelheight	64, 1805, 1848, 1919
proofing	10	\panelwidth	64, 1805, 1809, 1847, 1920, 1989, 1998
rendition	8	\paperheight	450, 4150
showgrayletters	10	\paperwidth	447, 4140, 4145, 4324, 4325
solutionsafter	9	\paragraph	2023
solutionsonly	9	\parbox	4568
textures	11	\parindent	1409, 1417, 1612, 1758, 3197, 4077, 4335
totalsonleft	5	\parsep	2204, 3948, 4334, 4377, 4395
totalsonright	5	\parsetotals	56, 1641, 1644
usecustomdesign	4	\parshape	2755, 2757, 3724
useforms	7	\parskip	1475, 1502, 3197, 3947, 4079
usexkv	8	\partialspillovertotals	2086, 2092, 2094
vspacewithsolns	7	\partaltotaleoe	2093, 2096, 2160, 2168
webOpts	9	\partialltotalpg	2091, 2096, 2161, 2169
xetex	11	\partNames	476, 1693, 2244, 2245
\optsCkBxf	1020	\partopsep	3947
\optsCkBxl	1021	\parts@indent	2740, 2744, 2908
\optsFillIn	2346	\partsitemsep	2501
\optsMlTextField	37, 1082	\partsleadinIndent	2745, 2769
\optsRadioBtnf	957	\partsparsep	2501
\optsRadioBtnl	958	\partstabcolsep	2502
outlineonly* (key)	101	\partstabrowsep	2503
\OutOfNum	2409, 2411, 2413, 2633	\partstabtopsep	2503
		\partstopsep	2501
		\parttotalsonleft (option)	5
		\parttotalsonright (option)	5
		\passedss@Argii	2007, 2008, 2014
		\PassOptionsToPackage	158, 199, 209, 211, 213, 216, 219, 221, 224, 226, 4553
		\PBS	963, 992, 1027, 1054
		pdf (option)	7
		\pdftex (option)	11
		\penalty	2266, 4097
		\percentForPart	1699
		\phantom	4440, 4843, 4858, 4869
		\placeAtxy	1754
		\placeCoverPageLogo	1350
		\placeMarkerHere	1704
		\pnpDflt	2456, 2457
		\pointLabel	1560, 1561
		\pointsAsText	1562
		\pointsLabel	1555
		\pointsmarginparpush	80, 2135, 2459, 2471, 2486
		pointsonboth (option)	5
		\PointsOnBothSides	35, 486
		\PointsOnLeft	33, 483
		pointsonleft (option)	5
		\PointsOnRight	34, 484
		pointsonright (option)	5
		\popEnvir	3725

\popProblem	2775	\proofingSymbolColor	525
\post@parts@hook	4030	\protected@edef	4477, 4712, 4716
\postChapSolnHead	4459, 4461	\protected@xdef	643, 647, 4108, 4109
\postdisplaypenalty	3535	\providecommand	195, 196, 425, 427, 429, 435, 525, 527, 529, 531, 533, 535, 537, 539, 541, 543, 545, 548, 568, 571, 845, 1555, 1556, 2190, 2339, 3961–3964, 3970
\postExamSolnHead	1215, 4452	\ProvidesFile	1125, 3784
\postPNPAction	2422, 2423, 3223	\ProvidesPackage	4551
\postSubmitJS	923, 934	\prtsIndntSep	3273, 3275
\pr@b@secondarg	2636, 2654, 2685, 2686	\ps@eqExamheadings	461
\pr@obl@m@star	2623, 2624	\ptLabel	1556
\pr@blem@star	2625, 2626	\PTs	2537, 2538, 2563
\prbDecPt	425, 3958	\ptsLabel	1555
\prbNumFmt	4001	\pushButton	927
\prbNumPrtsep	429, 3958	\pushEnvir	3722
\prbPrtsep	427, 3958	\pushProblem	2775
\preChapSolnHead	4457, 4461	\put	4231, 4233
\predisplaypenalty	3534		
\preExamSolnHead	1215, 4452		
\presets	975, 1009, 1039, 1071, 1092, 2372, 4892, 4897		
preview (option)	9		
\previewfalse	239		
\previewtrue	163, 995, 999, 1057, 1061		
\prior@parts@hook	4027	<b>Q</b>	
\priorexsectitle	4419	\Q	1582, 1588
\priorexslinput	4419	\qeSumryVert	48
\priorP@geBre@kMsg	3019, 3020, 3222, 3232	\qNewPage	2928
\priorPageBreakMsg	3019, 3022	\quiz@solns	294, 295, 297, 306, 322, 323, 1215, 1223, 1225, 1233, 4277
\priorPNPAction	2421, 2423, 3220		
\priorSubmitJS	922, 931	<b>R</b>	
\priorw@Msg	3463, 3466, 3467	\r	929–931, 933
priorworkarea (environment)	3714	\radio@@Button	975, 1009
\priorWorkAreaCmds	1773–1775, 3519, 3539	\RadioFieldSize	976, 1010, 1011, 1017, 1040, 1072, 1079, 1129, 1161, 1208, 1210, 1211
\priorworkareaCmds	1772	\raggedbottom	470
\prob@Arg	2783, 2786	\raggedcolumns	414
\problem	2512	\raggedright	963, 992, 1027, 1054, 4079
problem (environment)	2497	\raise	3438, 3583, 3598
problem* (environment)	2594	\raisebox	904, 1157, 1201, 1337, 1352, 1604, 1614, 1621, 1672, 1681, 1759, 3423, 3587, 3591, 3602, 3606, 4820, 4823, 4867, 4868, 4891, 4896
\problem@cont	2516, 2517	\RecordThisExamOff	74, 2227
\probpointseach	2638, 2651, 2678, 2679, 2791	\Rect	39, 1141, 1204
\probSet	4471, 4475	\refstepcounter	962, 991, 1026, 1053, 2735, 2934
\probset (environment)	4474	\removelastparskip	1778, 1796
\probstar	948, 950, 968, 1003, 1032, 1065, 1086, 2060, 2364, 2384, 2390, 2527, 2635, 3846, 3865, 3916, 4883, 4909	\removelastskip	2074, 2146
\probvalue	1537, 2540, 2827	rendition (option)	8
\ProcessComment	4294, 4303	\repeat	715, 743, 804, 2893
\ProcessOptions	4554	\RequirePackage	2, 3, 264, 357, 360, 374, 380, 402–405, 412, 417, 4555, 4566
\ProcessOptionsX	253	\reset@color	3248
\promoteNewPage	2456, 2905	\resetacvspace	2897
proofing (option)	10	\resetFillerCustomBg	108, 3349, 3350
\proofingSymbol	39, 285, 1144, 1178, 1198, 1201, 2634		

```

\resetMargHeadColor ..... 4097
\RestoreCommentCutFile ..... 4286, 4296, 4301
\restoreFromChapAfterSolns ..... 4356
\restorelabel ..... 4531
\restoreLastBotMargin ..... 4074
\restoreLastTopMargin ..... 4072
\restorele@d infixDef ..... 2608
\restorele@d npfxDef ..... 2607, 2609
\restorePageLayout ..... 4338
\ReturnTo ..... 39, 1143
\reversemarginpar ..... 3806
\reverseVSWs ..... 341
\rfooteqe ..... 1301
\rhead ..... 1290
\rheadeqe ..... 1284
\rheadSol ..... 1308
\rightmargin ..... 4336
\rightmark ..... 4260, 4262, 4328
\rlap ..... 1159, 1201,
           1243, 3171, 3404, 3405, 3411, 3414, 3418, 3422,
           3430, 3432, 3587, 3591, 3602, 3606, 4837, 4840
\rowsepDefault ..... 2502
\rule ..... 1404, 2186, 3001, 3011, 3247, 3412
\runExamFooter ..... 45, 467, 1307
\runExamHeader ..... 1295
\runExamHeaderSol ..... 1308

S
\S ..... 954
\sameVspace ..... 1933, 3252, 3254
\save@message
  ... 673, 678, 725, 744, 755, 789, 805, 809, 3506
\save@setckpt ..... 4511, 4528
\save@wlog ..... 3505
\save@writefile ..... 4509, 4527
\saveBasicLayoutParams ..... 4321, 4345
\savedeq@online ..... 347, 392
\savedifeq@globalshowsolutions ..... 350, 396
\savedifeq@hidesolution ..... 349, 395
\savedifeq@nolink ..... 353, 399
\savedifeq@nosolutions ..... 351, 397
\savedifeq@proofing ..... 352, 398
\savedifeq@solutionsafter ..... 348, 393
\savedifeqforpaper ..... 355, 401
\savedifpreview ..... 354, 400
\saveIFEQE ..... 329, 332–335
\sbox ..... 964, 1028, 1842
\scriptsize ..... 3422
\sectionColor ..... 548, 550, 561
\selectedMC ..... 262, 1140, 1148, 1165, 1175, 1190
\selectVersion ..... 748
\selVersion ..... 27, 706
\separationrule ..... 54, 2151, 2155, 2185
\separationruleOff ..... 53, 506
\separationruleOn ..... 505
\ServerRetnMsg ..... 34, 918, 919
\set@display@protect ..... 1224, 1232, 1237
\set@typeset@protect ..... 1226, 1235, 1239, 4205
\setBotMargin ..... 130, 4068, 4074
\setbox ..... 1152, 1628, 3202, 3468, 3469, 3532, 3552–
           3554, 3565, 3567, 3568, 3578–3580, 3594, 3610,
           3613, 3763, 3764, 4198, 4209, 4213, 4223, 4224,
           4226, 4692, 4792, 4810, 4817, 4834, 4855, 4862
\setBtwnExamSkip ..... 315, 318
\setcounter ..... 57, 611, 704, 714, 724, 777, 1649, 1651,
           1710, 1713, 1717, 1725, 1731–1733, 2118–2120,
           2166, 2542, 2636, 2684, 2735, 2780, 2793,
           2801, 2855, 2870, 2874, 2876, 2881, 2886, 4425
\setDefaultfvsizekip ..... 2213, 4502
\setDefaultnbaselineskip ..... 2492, 2493
\setfillinDefaults ..... 152, 4670
\setFillLinesFmt ..... 101, 3101
\setFullWidthHeader ..... 4252, 4357
\setFullWidthLayout ..... 4320
\setMarIndents ..... 3977
\setmulticolprob ..... 415
\setSolnIndent ..... 3987
\setSolnMargins ..... 301, 308, 3995
\setTopMargin ..... 130, 4060, 4072
\settotsbox ..... 467, 1643
\SetUpCutFile ..... 4291
\sExam ..... 576, 607, 625, 647
\shortquiz ..... 2259, 2260
\shortstack ..... 1325–1327
\shortTitleText ..... 592
\shortVersionAtext ..... 578
\shortVersionBtext ..... 578
\shortwebsubject ..... 825, 826, 1285, 1309
\shortwebtitle ..... 817, 818, 1285, 1309
\showAllAnsAtEnd ..... 278
showgrayletters (option) ..... 10
\showproofing ..... 10, 188
\sloppy ..... 3730
\sllshape ..... 4257, 4260, 4262, 4327, 4328
\small ..... 1568, 1570, 1576, 1660
\smallskip ..... 1979, 4454
\smash ..... 1157,
           1352, 1799, 3167, 3169, 3171, 3247, 3396, 3398
\solAtEndFormatting ..... 291
\solDecPt ..... 3965

```

\soln@keys@nLines	3786
.....	1918, 1923, 1927, 2006, 2008, 3259, 3263
\solnGutter	621
.....	3987, 3990, 3996–3999
\solnhSpace	2345, 4449
\solnItemMngt	2202, 4375
\solnsAtEndcomment	4288, 4298, 4306
\solNumPrtsep	435, 3965
\solPrtsep	3965
\solution	1817, 1819
\solutionparshape	1789, 1825, 1980, 1982, 2719, 2721, 2756, 2759, 2912, 3266, 3721
\SolutionsAfter	4490, 4500
solutionsafter (option)	9
\solutionsafterfalse	232
\solutionsafterSkip	1824, 1835, 2004
\solutionsaftertrue	231
\solutionsAtEndfalse	84, 421–423, 512
\solutionsAtEndtrue	72, 420
solutionsonly (option)	9
\solutionsonlyfalse	233
\solutionsonlytrue	185
\solWoPrtsFmt	4001
\solWPrtsFmt	4001, 4034, 4035
\solWPrtsFmt@hang	4019, 4034
\spaceskip	4079
\SpaceToWork	146
\splitbotmark	4236, 4238
\splitmaxdepth	3550, 3551
\splitsolution	1803
splitsolution (environment)	63, 1803
\splitsolutioni	1804, 1807
\splitsolutionii	1808, 1811
\splitsolutioniii	1805, 1809, 1812, 1814
\splittopskip	3549, 3576
\sq@priorhook	2125, 4441
\sqForms	144
\sqlabel	2309
\sqLinks	143
\sqSllabel	1214
\sqSrltnlabel	2332
\sqSolafter	2311
\sqstar	112, 143, 144, 2259, 2260
\square	2328–2330, 4488, 4498
\ss@Argi	1827, 1829, 1856–1858, 1944, 1984, 2009
\ss@Argii	1816, 1866, 1872, 1903, 1907, 1915, 1924, 1928, 1930, 1932, 1936, 1939–1941, 1991, 2007, 2008
\ss@Argiii	1816, 1827, 1890, 1891, 1893, 1943, 1946, 1953, 1963, 1971, 1984, 1989, 2003
ssol (environment)	4056
\ssols	3786
\stepcounter	621, 654, 711, 727, 791, 961, 962, 989, 990, 1024, 1025, 1051, 1052, 1861, 2236, 2362, 2890, 4881
\stretch	1388, 1438, 1440
\strip@pt	3360, 3368, 4151, 4154, 4157
\stripeqExam	56, 1642, 1648
\strut	1325–1327, 1799, 1993, 1994, 2001, 2074, 2075, 2082, 2354, 2356, 2898, 3023, 4583, 4587, 4799, 4812, 4821, 4847, 4859, 4870
\styleComm	2073, 2075, 2078
\styleInstr	2030, 2038
\subject	811
\subjectColor	525
\SubmitButton	34, 924, 1337
\SubmitButtonLabel	34, 920, 921
\SubmitInfo	33, 909
\summaryPointTotal	70, 2033, 2045, 2046, 2048
\SummaryTotalsOff	502
\SummaryTotalsOn	501
\summaryTotalsTxt	70, 2041, 2046
\sumryAnnots	61–63, 67, 1442
\symbolchoice	378, 385, 1177, 1197, 1200
<b>T</b>	
\tabcolsep	1548, 1601, 1611, 1671, 1679
\tableadin	90, 2602, 2660
\tableadinWarningStar	2599, 2647
\tb@addtoMargin	4051, 4095
\tb@addtoTopMargin	4047
\tb@ANS	124, 3882, 3883, 3908
\tb@argi	4107, 4114, 4119
\tb@beginexam@code	2085, 2127, 3792
\tb@carryoverFmt	4166, 4169, 4170, 4172, 4173, 4176, 4180, 4182
\tb@co@page	4171, 4172
\tb@csr	4343, 4350
\tb@EndOfChapterExercises	4268, 4310
\tb@esms	4340, 4347
\tb@GenProbNum	4432, 4438, 4439
\tb@insertCarryOver	4178, 4243
\tb@insertDecPoint	4427, 4431, 4434, 4439, 4440
\tb@insmargmark	2130, 2178
\tb@istart	3882, 3883, 3911
\tb@lws	4342, 4349
\tb@marginHeader	4105, 4115, 4116, 4118
\tb@marginProbHeader	4111, 4113
\tb@MHC	4100, 4101, 4103
\tb@midMargFmt	4086, 4092, 4181
\tb@mrgDigitFmt	3925, 3951, 4431, 4433

\tb@mrgPartFmt . . . . . 3889, 3897, 3954  
\tb@next . . . . . 3853, 3860, 3862, 3872, 3874, 3880  
\tb@osms . . . . . 4339, 4346  
\tb@rest@reMarginFmt . . . . . 4177, 4179, 4181, 4183  
\tb@sbm@exp . . . . . 4236, 4237, 4242  
\tb@shipoutPermittedfalse . . . . . 4187  
\tb@shipoutPermittedtrue . . . . . 4185, 4186  
\tb@showlsols . . . . . 3809, 4055  
\tb@showssols . . . . . 4056, 4057, 4058  
\tb@so@next . . . . . 4190, 4192, 4193  
\tb@soln@choice . . . . . 3809, 4057, 4363  
\tb@sols@choice . . . . . 4058  
\tb@tws . . . . . 4341, 4348  
\tb@woparts@len . . . . . 3941, 3979  
\tb@wparts@len . . . . . 3900, 3943, 3982  
\tballowAllNums . . . . . 3798  
\tbBaseName . . . . . 4507, 4514, 4533, 4536, 4538, 4540  
\tbBotMargin . . . . . 4046, 4067, 4068, 4070, 4212  
\tbcontinued . . . . . 4108, 4115, 4122  
\tbfilterOutEvenNums . . . . . 3789, 3794  
\tblastpageshipped . . . . . 4189, 4191, 4195  
\tbMakeFinalCalcs . . . . . 3815, 4126, 4159  
\tbMarginHeaderFmt . . . . . 4097, 4119, 4238  
\tbmarparboxwidth . . . . . 3814, 4080, 4082, 4089, 4092,  
  4124, 4125, 4130, 4138, 4143, 4200, 4215, 4254  
\tbminskipbtnlayers . . . . . 4163, 4204, 4222, 4227  
\tbmrgpartwdth . . . . . 3888, 3896, 3984  
\tbplaceMargins . . . . . 4123, 4148, 4161  
\tbPostMarginHeader . . . . . 4097, 4120, 4239  
\tbprbNumFmt . . . . . 4002, 4003  
\tbPreMarginHeader . . . . . 4097, 4118, 4237  
\tbSaveBotMargin . . . . . 4069, 4071, 4075  
\tbSaveTopMargin . . . . . 4063, 4066, 4073  
\tbSetupForMargins . . . . . 4136, 4160  
\tbsolnpartwdth . . . . . 3992, 4016, 4022, 4394  
\tsolWoPrtsFmt . . . . . 4005, 4011  
\tsolWPrtsFmt . . . . . 4007, 4014, 4020  
\tbSourceFile . . . . . 4508, 4516, 4519, 4520, 4537, 4543  
\tbTopMargin . . . . . 4045, 4059, 4061, 4065  
\temp@Exp . . . . . 2259  
\temp@exp . . . . . 733,  
  735, 736, 738, 797, 799, 1921, 1922, 4642, 4645  
\texorpdfstring . . . . . 812  
\text . . . . . 1446, 1562, 1568, 1570, 1571, 1576,  
  1661, 2046, 2563, 2565, 4583, 4587, 4744, 4790  
\textbf . . . . . 1213, 1217, 1445, 2312, 2313,  
  2317, 2320, 2342, 2399, 2400, 2411, 2412, 2898,  
  4004, 4013, 4018, 4103, 4453, 4462, 4486, 4496  
\textbook0pts . . . . . 3786  
\textColor . . . . . 955, 1582, 1588  
\textcolor . . . . . 983, 1047, 1141,  
  1145, 1413, 2039, 2079, 2148, 2990, 2999, 3003,  
  3411, 3421, 3431, 3887, 3907, 3955, 3957, 4103  
\textField . . . . . 905,  
  936, 938, 940, 942, 944, 1092, 2371, 4892, 4897  
\textheight . . . . . 450–455, 1420, 1426,  
  2234, 2456, 4088, 4091, 4150, 4201, 4209, 4220  
\textit . . . . . 2310, 2311  
\textorpdfstring . . . . . 391  
\textsf . . . . . 3346  
\textSize . . . . . 955  
textures (option) . . . . . 11  
\textwidth . . . . . 447–449, 1297, 1298,  
  1318, 1319, 1324, 1335, 1399, 1419, 1452, 1602,  
  1612, 1680, 4140, 4144, 4156, 4324, 4341, 4348  
\TF . . . . . 2380, 4906  
\the@cntfillin . . . . . 2366, 2369, 4885, 4888  
\the@exno . . . . . 1101, 2873  
\thebackofpage . . . . . 2934, 2936, 2938, 2961  
\thechapter . . . . . 4458  
\theduodate . . . . . 849, 851  
\theeq@count . . . . . 2682,  
  2705, 2795, 2798, 2803, 2807, 2810, 2857, 2860  
\theeq@numparts . . . . . 1539  
\theeqpointsthispage . . . . . 1655, 1661, 1662, 1668  
\theeqpointvalue . . . . . 1539, 1706, 2299  
\theeqquestionnoi . . . . . 968,  
  970, 1003, 1006, 1032, 1035, 1065, 1068, 1087,  
  1089, 1581, 1720, 2058, 2061, 2064, 2068, 2301,  
  2312, 2314, 2318, 2321, 2342, 2365, 2369, 2642,  
  2676, 2681, 2691, 2705, 2739, 2773, 3901,  
  3911, 3926, 4002, 4006, 4008, 4403, 4884, 4888  
\theexampleno . . . . . 4480, 4486, 4496  
\theGrandTotal . . . . . 1697  
\theHquestionnoi . . . . . 2057  
\theHpartno . . . . . 2067  
\theQuizno . . . . . 2059  
\themarkerCnt . . . . . 1716  
\thepage . . . . . 1580,  
  1587, 1590, 1654, 2124, 2546, 2849, 4171,  
  4172, 4250, 4257, 4260, 4263, 4327, 4328, 4472  
\thepanel@cnt . . . . . 1833, 1862, 1889, 1948, 1955, 1965, 1974  
\thePartNames . . . . . 1280, 1480  
\thepartno . . . . . 968,  
  1004, 1033, 1066, 1087, 2061, 2068, 2322,  
  2365, 3893, 3897, 3902, 4008, 4009, 4425, 4884  
\thequizno . . . . . 948  
\therearesolutiontrue . . . . . 183  
\thereissolutionfalse . . . . . 2522, 2622  
\thesection . . . . . 4475

\thinspace	3432	\tweakBreakPoint	3478
\thisexamlabel	2032, 2045, 2047, 2050, 2052, 2089, 2100, 2102, 2104, 2105, 2107, 2110, 2112, 2122, 2124, 2177, 2224, 2239, 2299, 2301, 2546, 2644, 2646, 2676, 2681, 2690, 2705, 2739, 2773, 2795, 2798, 2803, 2806, 2809, 2849, 2857, 2860	\txtbkb@xb@t	4042, 4198, 4209, 4210, 4224, 4225, 4235, 4243
\thisOpt@OK	73, 80, 81, 95, 96, 168, 169, 176, 177, 181, 182	\txtbkb@xh@ld	4044, 4221
\thispagestyle	1418	\txtbkb@xt@p	4043, 4209, 4223, 4225, 4226, 4232, 4234
\thisPart	4429, 4430	\txtbkt@ks	4040, 4048, 4049, 4052, 4053, 4206, 4235, 4242
\thisterm	853	\txtbkt@ksi	4041, 4047, 4048
\thisUFexamlabel	2242		
\tiny	3167, 3169, 3171	<b>U</b>	
\title	811	\u,b	4568
\titleColor	525	\ulcmd	4632
\toggleInstrAns	3822	\ulcustom	4641
\toks	2686, 2687	\underline	871, 897, 1477, 1482, 1485, 1517, 1527, 1530, 2349, 4639, 4774
\tolerance	4078	\unhbox	4696, 4700, 4705, 4807, 4828, 4853, 4874
topline (key)	100	\unhcopy	2997
\topmargin	438, 454, 4150	\unitlength	4197
\topofprobhook	83, 2506, 2548	\university	811
\topofprobstarhook	86, 2604, 2661	\universityColor	525
\topsep	2206, 3948, 4334, 4379, 4397	\unvbox	3554, 3568, 3580, 3589, 3593, 3604, 3608, 3609, 4225, 4226, 4228, 4232, 4234, 4243
\tot@lForPart	1700, 2287	\uppercase	595, 604, 705
\totalForPart	1699	\use@email	124, 140, 926, 1412, 1593
\totalsbox	155, 490, 495, 496, 500, 1656	\usebox	1799
\totalsboxleft	57, 495, 1669	\useCheckForProof	1197, 1199
\totalsboxright	57, 496, 1677	\useCircForMC	1164, 1165, 1174, 1175, 1181, 1189
\totalsboxtext	57, 1660, 1673, 1682	\useCircForMS	41, 1196
\TotalsOnLeft	37, 495	\useCircForProof	1177, 1192
totalsonleft (option)	5	\useclassmaketitle	10
\TotalsOnRight	38, 496	\useCrossForProof	1200
totalsonright (option)	5	usecustomdesign (option)	4
\totHtPtBox	1633	\useCustomPartNames	48, 1394
\turnContAnnotOff	2920	\useFillerDefault	2969, 3705, 3706, 3772, 3773
\turnContAnnotOn	2920, 3703, 3770	\useFillerLines	2965
\turnfl@nskeyMsg	256, 3459, 3462	useforms (option)	7
\turnfl@nskeyOnOff	3616, 3620, 3636, 3663, 3667, 3674, 3678	\useMCCircles	1164, 1181
\turnflanskeyOff	114, 3470, 3635, 3650	\useMCRects	1167, 1168, 1183, 1184
\turnflanskeyOn	114, 3462, 3470, 3473–3476, 3619	\usenLineDimen	99, 3015
\turnflnosolnOff	3476	\usepackage	4, 271
\turnflnosolnOff	3474, 3618	\useRectForMC	1139, 1140, 1148, 1167–1169, 1172, 1173, 1183, 1184, 1187–1190
\turnflnosolnOn	3473, 3475, 3617	\useRectForMS	41, 1195
\turnOffFTBShipout	134, 4187	\userectformsfalse	1196
\turnOffMarAnsOnAnsInline	3822	\userectformstrue	1195
\turnOnFTBShipout	134, 4186	\useUIPartNames	48, 1393
\turnOnMarAnsOffAnsInline	3822	\useVspaceDimen	99, 3014
\twe@kBre@kPoint	. 3479, 3481, 3482, 3547, 3551, 3614, 3687, 3758	usekv (option)	8

**V**

\V ..... 937, 939, 941, 943, 945  
 \vbadness ..... 3653, 3690, 3717, 4078  
 \verbatim@out ..... 1877,  
     1879, 1884, 1900, 1978, 3495, 3497, 3507, 3508,  
     3511, 3512, 3514, 3518, 3695, 3696, 3738, 3739  
 \verbatimwrite ..... 1880, 3528  
 \version ..... 833  
 \VersionAtext ..... 578  
 \VersionBtext ..... 578  
 \versionLabel ..... 839, 840  
 \vfo@l ..... 3218, 3225, 3226, 3229, 3250  
 \vfil ..... 3589, 3593, 3604, 3608, 3609, 4207, 4228  
 \voidb@x ..... 3469, 3594, 3610, 3613, 3763, 3764  
 \vphantom ..... 3005  
 \vpswSimulateNoSolns ..... 336, 346  
 \vrule ..... 1138, 1550, 3006  
 \vsize ..... 2182, 3588, 3592, 3603, 3607, 4201  
 \vspaceFiller ..... 2965, 2967, 2970, 2982  
 \vspaceFillerDefault ..... 2970  
 \vspaceFillerLines .....  
     ..... 2966, 2967, 2982, 3175, 3261, 3264, 3324  
 \vspaceFillerLines@i ..... 3183, 3187  
 \vspacewithkeyOff ..... 515, 1122, 3689, 3729  
 \vspacewithkeyOn ..... 515  
 \vspacewithsolns (option) ..... 7  
 \vspacewithsolnsfalse ..... 86, 89, 341, 3645  
 \vspacewithsolnstrue ..... 88, 98, 281, 3631  
 \vsplit ..... 3553, 3567, 3579, 4209, 4223  
 \vss ..... 3007, 3010

**W**

\W ..... 954  
 \w@rningBadOpts ..... 74, 83, 99, 172, 180, 186  
 \web@continued ..... 842  
 \web@save@maketitle ..... 1342, 1345  
 \web@save@title ..... 813, 818  
 \web@saved@author ..... 819, 822  
 \web@sectionsColorOld ..... 548  
 \web@toc ..... 841  
 \web@version@value ..... 833, 834, 836, 838  
 \web@versionlabel ..... 835, 839  
 \webArg ..... 817, 824, 825  
 \webauthor ..... 820, 1327, 1413  
 \webauthor@color ..... 537, 1413  
 \webcopyrightyears ..... 832  
 \webemail ..... 828  
 \webkeywords ..... 829  
 \webnewpage ..... 4410, 4416, 4417, 4447  
 webOpt (option) ..... 9

\websubject ..... 826, 913, 1325, 1364, 2337, 2339  
 \websubject@color ..... 539, 1430  
 \webtitle ..... 815, 915, 1326, 1437, 2333  
 \webtitle@color ..... 535, 1436  
 \webuniversity ..... 831, 1425  
 \webuniversity@color ..... 533, 1424  
 \webversion ..... 834  
 \widowpenalty ..... 3653, 3716  
 \widthOfParts ..... 3279  
 \widthPboxes ..... 53, 1546, 1548, 1551, 1583, 1591  
 \WithinANSGrpfalse ..... 3843, 3852, 3871  
 \WithinANSGrptrue ..... 3858  
 \withinoldocfalse ..... 2188  
 \withinoldoctrue ..... 300  
 \wlog ..... 3505  
 \wlVspace .....  
     ..... 1926,  
         2445, 2986, 2987, 3187, 3198, 3225, 3226, 3233,  
         3241, 3257, 3262, 3324, 3357, 3359, 3374, 3384,  
         3391, 3394, 3416, 3545, 3549, 3576, 3591, 3606  
 \work@reaCmds ..... 1769–1771, 1790  
 workarea (environment) ..... 1762  
 \workareaCmds ..... 1768  
 \workareadepth ..... 1779, 1787  
 \workareasb ..... 61, 1762, 1780, 1799  
 \workareaV@dj ..... 1765, 1788  
 \workareaVadj ..... 61, 1763, 1767  
 \write ..... 277,  
     3495, 3497, 3511, 3512, 3514, 3518, 3695, 3738  
 \writeAllAnsAtEnd ..... 293, 1118, 1119, 4279  
 \writeallsolutions ..... 4282  
 \writeBeginEqeQuestions ..... 304, 1116, 2121  
 \writeEndEqeQuestions ..... 319, 2174  
 \writelnlastpage ..... 1694, 2177, 2303  
 \writeT@SolnFile ..... 300, 308–310, 325,  
     1228, 2228, 2229, 2663, 2723, 4029, 4031, 4456  
 \writeToSolnFile ..... 1215  
 \writetotalstoaux ..... 2175, 2298  
 \writeVertic@1FLinesfalse ..... 3624, 3669, 3750  
 \writeVertic@1FLinestrue ..... 3175, 3638, 3676, 3756  
 \writeWithSolDocTrue ..... 300, 1120  
 \wrtChapSolnHead ..... 4455  
 \wrtExamTitleInSolns ..... 2222

**X**

xetex (option) ..... 11  
 \XKV@rm ..... 1924, 1929, 1930  
 \xspaceskip ..... 4079

**Y**

\y@st@Do ..... 2584, 2588  
 \yest@D@ ..... 2584–2586, 2688, 2800

## 19 Change History

1.6a (2006/01/22)		file should contain one or more custom options. ....	12
	\selectVersion: added \selectVersion command, also the command was fixed \forVersion so that it can be changed within the document, added switches to control new selection. ....	28	
1.6b (2006/04/03)	\forVersion: Changed the alphabet environments A, B, etc. due to a conflict with \S, the control sequence for the amsmath package for a section: \S expands to §. Names changed to verA, verB, etc. ....	26	\eqEndExamTotalColor: Added easy user access to various colors, \proofingSymbolColor, \instructionsColor, \eqCommentsColor, \authorColor, \titleColor, \universityColor and \subjectColor ... 21
1.6b (2006/3/12)	\popProblem: Added \pushProblem and \popProblem to grant the ability to interrupt a parts environment for, for example, a multicolumn environment. ....	91	v1.6f (2006/10/24) \forVersion: Fixed a bug in the \eqe@initializeMultiVersions command, made sure that any already defined comment environments are set to relax. .... 26
1.6c (2006/05/02)	\forVersion: At the end of the package, set the initial value of \selectVersion to \selectVersion{26} and set the initial value of \forVersion to \forVersion{A}. ....	28	v1.6g (2006/11/29) \itemPTsFormated: Added \itemPTsTxt and \itemPTsFormated to work with \PTs. Also added a * option, to \PTs, in this case the points are not typeset. .... 83
2.0a (2010/05/06)	\rheadeqe: Changed the definitions of \lhead, \chead, and \rhead so they don't clash with the fancyhdr package. If fancyhdr is not loaded at the time eqexam is loaded, we \let the old names to the new names. Therefore, when fancyhdr is loaded first use the new definitions. ....	44	v1.6h (2007/01/24) \forleadinitem: Added \forproblem, \foritem, \aNewPage .... 94
4.4a (2015/06/01)	problem: Added the hook \topofprobstarhook .	83	\qNewPage: Added \aNewPage and \qNewPage ... 96
(2015/06/01)			v1.6i (2007/09/18) \altTitle: Added the command \altTitle as an alternate title for the exam document. This alternate title appear centered under the title of the document. .... 46
(2015/06/02)	problem*: Added the hook \topofprobstarhook	86	v1.7a (2007/12/10) \separationrule: Added \separationrule so user's can redesign the separation rule that is created between two parts of an exam. .... 73
	problem*: Added \@marktotalvalue which seems to solve a problem with multicols. Sometimes the totals are not correct, they do not 'migrate' out as they should. ....	88	v1.7b (2007/21/07) General: Added a solutionsonly option .... 9
(2015/07/21)	General: add \let\CT@arc@relax .....	13	\encloseProblemsWith: Added \encloseProblemsWith to support the solutionsonly option .... 21
v1.6e (2006/05/07)	General: Added a custom option feature. Just before the options are processed, the tex compiler looks for the file eqecus.opt. This		v1.7c (2008/08/21) General: Added the showgrayletters option to eqexam (ported from exerquiz) .... 10
			v1.8 (2008/11/02) \placeMarkerHere: Added a set of commands \placeMarkerHere, \calcFromMarkers, and \markerTotalFmt to enable the calculation of totals of segments of the exam. .... 59
			v1.9a (2009/28/09) \coverpageTitleFmt: Added these various Fmt commands for coverpage. .... 47

v1.9b (2009/09/29)		
\placeCoverPageLogo: Added		
\placeCoverPageLogo to insert a logo on the		
cover page. . . . .	47	
v1.9f (2009/10/06)		
\endshortTitleText: Modified \longTitleText,		
\shortTitleText to have an optional		
argument (A–Z;a–z). You can select a		
particular title from a list of titles. If no		
optional argument is passed, then the title		
determined by \forVersion is used. . . . .	23	
v2.0 (2010/03/05)		
General: Added exambuilder.cfg for use by AeB		
Exam Builder, to pass the values of the		
options max and rendition to eqexam. . . . .	12	
Switched over to xkeyval, added max and		
rendition to be consistent with the renditions		
package, though we don't use the rendition		
package itself. eqexam has a more extensive		
renditions system already. Introduced this		
mostly for use AeB Exam Builder. . . . .	8	
v2.0c (2011/01/11)		
problem*: Changed \cnext to \eqe@cnext. There		
was conflict in the use of this command with		
one of the float environments. When user		
used the table environment inside the		
problem* environment, the compiled stopped		
because \cnext was overwritten. . . . .	84	
v2.0d (2011/03/04)		
General: Added the vspacewithsolns option . . .	7	
v2.0e (2011/03/07)		
\useFillerLines: Added the feature of filling		
the vertical space with ruled lines of different		
types. This feature is available for paper		
options and for nosolutions and		
vspacewithsolution options. . . . .	97	
v2.0h (2011/04/14)		
\fillin: Modified the calculation of the width of		
\fillin, the width of enclosing box now		
equals the requested width . . . . .	156	
v2.0i (2011/04/17)		
General: Added the switch \ifdisplayworkarea		
to better control when the work area is to be		
displayed. . . . .	10	
v2.0j (2011/04/19)		
\enclosesoln: added the enclosesoln key to		
eqFillin family. . . . .	148	
v2.0k (2011/04/29)		
\vspacewithkeyOff: Added user interface to the		
switch \ifkeepdeclaredvspacing, which is		
	defined in eqexam.def/exerquiz. . . . .	20
v2.0l (2011/05/05)		
\firstPageOfExam: Returns the page number of		
the beginning of the exam with a given name. . .	43	
\lastPageOfExam: Returns the page number of		
the end of the exam with a given name. . . . .	43	
v2.0n (2011/05/13)		
\promoteNewPage: A simple variation on		
\makeRoomForProb designed for user use. . .	80	
problem: Added *<num> to signal in-line display		
of points. . . . .	82	
v3.0f (2011/08/13)		
\ftbInputBookAux: Added \ftbInputBookAux to		
support solution manual . . . . .	145	
\ftbInputSolnFiles: Added		
\ftbInputSolnFiles to support solution		
manual . . . . .	147	
v3.0g (2011/08/15)		
\hangSolWPrtsFmt: Use this to use "hanging"		
indentation" for the parts for problems with		
parts in the solutions file. . . . .	128	
v3.0h (2011/08/17)		
General: 2011/08/17 v3.0h Added the		
vspacewithsolns option . . . . .	7	
v3.0i (2011/08/18)		
\fitwidth: added the fitwidth key to eqFillin		
family. . . . .	149	
v3.0l (2011/08/22)		
\annotContStr: Defined \eqe@insertContAnnot		
and related commands . . . . .	95	
v3.0n (2011/09/18)		
\probset: Added an \edef in case \thesection		
does not get expanded early enough to		
display correctly in the margins. . . . .	144	
v3.0o (2011/09/20)		
\cngMargHeadColorTo: Added		
\cngMargHeadColorTo and		
\resetMargHeadColor to make it easier to		
change the color of the header globally, or		
just once. . . . .	131	
v3.0p (2011/09/22)		
General: Added \NoSolutions to be executed in		
preamble, needed with the fortextbook		
package. . . . .	20	
Added the wrapper package fortextbook. . . . .	147	
v3.0q (2011/14/22)		
\eqGrpANS: Added \bGrpANS and \eGrpANS . . .	121	
v3.0s (2012/01/01)		
\eqexammargin: Moved a copy of		
\eqe@spannerSoln out of the ftbsty to the		

package section, its needed here as well. . . .	18
v3.0t (2012/01/25)	
General: Added four more CFG files are the request of a user. . . . .	5
v3.0u (2012/09/03)	
General: Added the <code>cfg</code> option for inputting a custom config file. . . . .	5
v3.0v (2012/03/14)	
\textbookOpts: Include <code>\tbMakeFinalCalcs</code> at end of <code>\textbookOpts</code> . . . . .	120
v3.0w (2012/03/27)	
parbox: Added <code>parbox</code> . . . . .	149
hiddenbox: Added <code>hiddenbox</code> options . . . . .	149
v3.0x (2012/04/03)	
hiddenbox: Added <code>\eqe@align@hfill</code> to <code>align</code> property. used to set position of content when <code>parbox</code> is used. . . . .	149
v3.0y (2012/04/20)	
\altTitle: Moved <code>\EQEcalculateAllTotals</code> from the bottom to the top of <code>\eqemaketitle</code> . In case the author wants the grand total of the exam in the title, we need to make all calculations before <code>\maketitledesign</code> . . . . .	46
v3.1 (2012/05/16)	
\calcQsBtwnMarkers: Added <code>\calcQsBtwnMarkers</code> . . . . .	59
v3.1a (2012/05/21)	
problem*: Using a more robust method of detecting the presence of <code>\auto</code> . . . . .	86
v3.1b (2012/06/18)	
General: Added <code>\eqe@auto@chk@drivers</code> . . . . .	7
New requirement ifpdf . . . . .	4
v3.1c (2012/07/30)	
ulcmd: Added ulcmd to <code>\fillin</code> . . . . .	150
boxcmd: Added boxcmd to <code>\fillin</code> . . . . .	150
v3.1d (2012/09/29)	
General: Added <code>\ifeqexamCFG</code> and <code>cseqexamCFG</code> ; these are used by ATB to attached the configuration file. . . . .	5
v3.1e (2012/11/10)	
General: Changed default for <code>\proofingsymbol</code> .	41
\makeAnsEnvForSolnsAtEnd: Removed hard-wired <code>\proofingsymbol</code> . . . . .	13
problem*: Removed hard-wired <code>\proofingsymbol</code> . . . . .	86
v3.1f (2012/11/27)	
\leadinitem: Created <code>\leadinitem</code> command for a lead in question for the <code>parts*</code> environment. . . . .	88
v3.2 (2012/12/10)	
splitsolution: Rewrote splitsolution and related code to change the syntax. . . . .	62
v3.2c (2013/02/23)	
General: Added <code>\selectedMC</code> at end of package .	13
v3.3 (2013/04/07)	
lsols: exerquiz changed <code>\eqExt</code> to two variables, so we make the same change here. . . . .	120
v3.3a (2013/05/03)	
\leadinitem: Changed name of <code>\eq@writeexheader</code> to <code>\eqExerSolnHeader</code>	90
v3.5a (2014/12/19)	
General: Made <code>usekeys</code> as default . . . . .	8
v3.6a (2015/01/31)	
\forleadinitem: Added <code>\eqe@fpmrk</code> to add to the uniqueness of <code>\theHquestionno</code> . . . . .	94
v3.7 (2015/02/11)	
\selectVersion: Worked on the logic . . . . .	28
v3.7a (2015/02/26)	
\eqe@tb@shipout: Added a new Boolean switch <code>\iftb@shipoutPermitted</code> to turn off the shipout. Two convenience commands in support are also added, <code>\turnOffFTBShipout</code> and <code>\turnOffFTBShipout</code> . . . . .	134
v3.8 (2015/03/17)	
\leadinitem: Spacing is not correct with standard itemize and enumerate environments, this is a fix. . . . .	90
v4.1 (2015/04/23)	
General: Moved this segment of code to <code>\manualcalcparts</code> , it is taken from the main problem* env. . . . .	92
v4.4 (2015/05/24)	
exam: Finish with a <code>\vskip</code> to clear the last item or problem. . . . .	75
v4.5 (2015/11/10)	
\fillin: Added <code>\setfillinDefaults</code> . . . . .	152
v4.5a (2015/11/10)	
hiddenbox: Added some logic to the underline key . . . . .	149
v4.6 (2016/01/18)	
\eqe@tb@shipout: Removed <code>\vfil</code> between unboxing, this allows correct breaking of margin content across pages. . . . .	135
v4.6a (2016/06/04)	
General: Added <code>\ifequsecolor</code> to easily distinguish between <code>forpaper</code> and <code>forcolorpaper</code> options. . . . .	9

v4.6b (2016/10/02)	
\showAllAnsAtEnd: Include \eqTopOfSolnPage	
from exerquiz to support copying question to	
solution page. . . . .	13
v4.6c (2017/01/28)	
\underlinecmd: added custom underline option . . . . .	151
v4.7 (2017/01/04)	
\forleadinitem: Modified \foritem@cont to	
allow for numbering parts . . . . .	94
v4.9 (2017/03/16)	
General: Updated eqexam to reflect changes in	
eqexam.def. . . . .	38
v4.9a (2017/04/05)	
\leadinitem: Added a test for solutions after	
within lead-in item . . . . .	90
v4.9b (2017/10/10)	
\eqEndExamTotalColor: Provides color for check	
boxes when a PDF-related option is not taken . . . . .	22
v4.9c (2017/11/03)	
\fillTypeGrid: Added \fillTypeGrid . . . . .	98
v5.0 (2017/11/08)	
General: Added \setFillLinesFmt . . . . .	102
Added hooks \priorPNPAction and	
\postPNPAction to \makeRoomForProb . . . . .	79
Added support for \fillTypeGrid, added keys	
numbers, numbersep, and color as well . . . . .	99
Added switch \ifgridpgbrk . . . . .	103
Added vertical rules . . . . .	99
workarea: Added \workareaVadj . . . . .	61
Changes in workarea to support	
\fillTypeGrid . . . . .	62
Within workarea, adjust \leftskip when the	
problem is a lead-in type . . . . .	62
v5.0a (2017/11/14)	
General: Placed \eqe@makeVgrid in a group,	
\count0 was leaking out. . . . .	108
v5.0c (2017/11/18)	
General: Added the outlineonly, bgonly, and	
bgcolor keys to the eqfileLines family. . . . .	101
v5.0d (2017/11/19)	
General: Added a custom background feature .	108
v5.0g (2017/12/05)	
General: Added filler lines with nosolutions	
option . . . . .	116
Added option flextended. . . . .	7
priorworkarea: Added the priorworkarea	
environment . . . . .	116
v5.0o (2017/12/26)	
General: Added \chngToNoSolns . . . . .	20
v5.1.1 (2018/12/05)	
General: Added \eqprior . . . . .	14
v5.1.2 (2018/12/05)	
General: Use version 3.2 of comment style under	
the name of aeb-comment . . . . .	16
v5.1.3 (2018/12/13)	
General: \ifdisplayworkarea conditionally	
defined; defined \displayworkareaOn and	
\displayworkareaOff. Consistent with	
exerquiz. . . . .	10
workarea: added solutions-after condition to	
displaying workarea . . . . .	62
\postExamSolnHead: Write to solution file if not	
solutions-only . . . . .	42
v5.1.4 (2019/01/31)	
General: \let \comment and \endcomment to	
\relax we use the definition of the comment	
environment given in verbatim. . . . .	16
v5.1.5 (2019/10/28)	
General: Define \eq@Radio@driver in case	
eqexam.def/exerquiz still use	
\eq@RadioCheck@driver . . . . .	36
Insert \bWebCustomize and \eWebCustomize	
to conform with web dated 2019/10/23. . . . .	12
Replace \eq@RadioCheck@driver by	
\eq@Radio@driver . . . . .	36
v5.1.6 (2019/10/29)	
\fillin: Allow the third argument of	
\fillineol* to have verbatim text as well. . . . .	153
v5.1.7 (2019/12/17)	
General: Added \autoInsSolns . . . . .	141
v5.1.8 (2020/01/06)	
General: Define \aebc@end as a work around for	
aeb-comment . . . . .	16
v5.1a (2018/01/21)	
problem: added \eqe@p@gobnxtp@r . . . . .	82
problem*: added \eqe@gobnxtpar . . . . .	85
v5.1b (2018/01/24)	
\vspaceFillerLines: Added . . . . .	105
v5.1c (2018/01/31)	
General: Added additional lines to get a better	
break point . . . . .	112
v5.1d (2018/02/02)	
\fillin: removed \space\ignorespaces from	
\fillin . . . . .	159
exam: Added \RecordThisExamOff . . . . .	74
v5.1e (2018/02/09)	
problem: Support for h and H argument . . . . .	82, 83

v5.1f (2018/02/09)	v5.1i (2018/02/19)
<b>problem:</b> modify problem env to analyze two optional args ..... 82	<b>\fillin:</b> Changed name to <b>\fillineol</b> and changed order of arguments ..... 152
v5.1g (2018/02/14)	v5.1j (2018/04/15)
<b>hiddenbox:</b> Added <b>fontsize</b> and <b>fboxsep</b> keys 149	<b>problem:</b> Change comparison to <b>\ifx</b> , <b>\if</b> give incorrect result when points are of the form 11, 22, 33, etc. ..... 82
v5.1h (2018/02/18)	
<b>\fillin:</b> Added <b>\mtoeol</b> ..... 152	
Added test, 0pt same as empty width ..... 153	