

The etl package expandable token list operations

Jonathan P. Spratte[†]

2021-08-20 v0.1

Contents

1	Documentation	1
1.1	A general loop	2
1.2	Conditionals	4
1.3	Modifying token lists	5
1.4	New expandable fast tests	6
1.5	Bugs and Feature Requests	6
2	Implementation	7
2.1	Primitives	7
2.2	Variables	7
2.3	Small auxiliaries	7
2.4	The act loop	9
2.5	Expandable tests	13
	Index	25

1 Documentation

The etl package provides a few *slow but expandable* alternatives to unexpandable functions found inside the l3tl module of expl3. All user functions must not contain the tokens `\s__etl_stop†` or `__etl_act_result:n†` in any argument (but there might be other forbidden tokens, all of which are internals to this package, and usually shouldn't somehow end up inside the input stream by accident).

There is another limitation of this package: There are tokens which cannot expandably be differentiated from each other, those are active characters let to the same character with a different category code, something like the following:

[†]jspratte@yahoo.de

[†]At any nesting level of groups

[†]Outside of some local brace groups

```
\char_set_catcode_letter:N a
\char_set_active_eq:NN a a
\char_set_catcode_active:N a
```

After this the active ‘a’s couldn’t be told apart from non-active ‘a’s of category letter by the parsers in this package.[†] In general two tokens are considered equal if `\etl_token_if_eq:NNTF` yields true (see there). Another limitation is that the parser doesn’t consider the character code of tokens with category 1 or 2 (group begin and group end, typically `{}`), instead all tokens found with these two category codes are normalised to `{1}` and `{2}`.

The core macro `\etl_act:nnnnnnn` is modelled after an internal of `l3tl` called `__tl_act:NNNn` but with some more possibilities added.

1.1 A general loop

<code>\etl_act:nnnnnnn</code>	★	<code>\etl_act:nnnnnnn {<normal>} {<space>} {<group>} {<final>} {<status>} {<output>}</code>
<code>\etl_act:nnnnnn</code>	★	<code>{<token list>}</code>
<code>\etl_act:nnnnnn</code>	★	<code>\etl_act:nnnnnn {<normal>} {<space>} {<group>} {<final>} {<status>} {<token list>}</code>
<code>\etl_act:nnnnn</code>	★	<code>\etl_act:nnnnn {<normal>} {<space>} {<group>} {<status>} {<token list>}</code>

This function will act on the `<token list>` (somewhat a `map_tokens`-function). Both `<normal>` and `<group>` should be code that expects two following arguments (the first being the `<status>`, the second the next N-type token or the contents of the next group in the `<token list>`), and `<space>` should expect only the `<status>` as a following argument.

You can also specify `<final>` code which will receive the `<status>` followed by the output (which you can assign with `\etl_act_output:n` and `\etl_act_output_pre:n`), and will be used inside an e-expansion context (so you’ll want to protect anything you want to output from further expansion using `\exp_not:n`). Also you can specify some `<output>` which should be there from the beginning.

Functions without the argument `<output>` will start with an empty output, and those without `<final>` will just output the results at the end.

T_EXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an x- or e-type argument expansion. The result will be returned after exactly two steps of expansion. If you don’t need the `<final>` argument processor and don’t have to reorder some of the output you can also use `\exp_not:n` to directly output tokens where you currently are, this might be faster.

<code>\etl_act_output:n</code>	★	<code>\etl_act_output:n {<token list>}</code>
<code>\etl_act_output_pre:n</code>	★	This will add <code><token list></code> to the output of <code>\etl_act:nnnnnnn</code> . The normal version will add <code><token list></code> after the current output, the <code>pre</code> variant will put it before the current output. Might be used inside of the <code><normal></code> , <code><space></code> , or <code><group></code> code of <code>\etl_act:nnnnnnn</code> .

[†]Thanks to Bruno Le Floch for pointing that out.

<code>\etl_act_output_rest:</code>	★	<code>\etl_act_output_rest:</code>
<code>\etl_act_output_rest_pre:</code>	★	

After this macro was used all remaining things inside the `<token list>` argument of `\etl_act:nnnnnnn` will be added to the output. The normal version will add it to the end of the output, the pre variant will put the remainder before the current output in reversed order. Might be used inside of the `<normal>`, `<space>`, or `<group>` code of `\etl_act:nnnnnnn`.

<code>\etl_act_status:n</code>	★	<code>\etl_act_status:n {<status>}</code>
--------------------------------	---	---

This will change the current status of `\etl_act:nnnnnnn` to `<status>`. Might be used inside of the `<normal>`, `<space>`, or `<group>` code of `\etl_act:nnnnnnn`.

<code>\etl_act_put_back:n</code>	★	<code>\etl_act_put_back:n {<token list>}</code>
----------------------------------	---	---

You can put `<token list>` back into the input stream to be reconsidered by the current `\etl_act:nnnnnnn` loop (of course this doesn't have to be literally put back, you might add completely new contents with this). Might be used inside of the `<normal>`, `<space>`, or `<group>` code of `\etl_act:nnnnnnn`.

<code>\etl_act_switch:nnn</code>	★	<code>\etl_act_switch:nnn {<normal>} {<space>} {<group>}</code>
<code>\etl_act_switch_normal:n</code>	★	<code>\etl_act_switch_normal:n {<normal>}</code>
<code>\etl_act_switch_space:n</code>	★	<code>\etl_act_switch_space:n {<space>}</code>
<code>\etl_act_switch_group:n</code>	★	<code>\etl_act_switch_group:n {<group>}</code>

With these functions you can change the provided code to act on `<normal>` (so N-type) tokens, `<space>`s, and `<group>`s. Might be used inside of the `<normal>`, `<space>`, or `<group>` code of `\etl_act:nnnnnnn`.

<code>\etl_act_do_final:</code>	★	<code>\etl_act_do_final:</code>
---------------------------------	---	---------------------------------

This will immediately stop the current `\etl_act:nnnnnnn` invocation and execute the provided `<final>` code (or if a variant without the `<final>` code was used, the output). The `<final>` code will receive the current status followed by the current output as two arguments (just like it would when the end of the `<token list>` was reached). Might be used inside of the `<normal>`, `<space>`, or `<group>` code of `\etl_act:nnnnnnn`.

<code>\etl_act_break:</code>	★	<code>\etl_act_break:</code>
<code>\etl_act_break_discard:</code>	★	

This will immediately stop the current `\etl_act:nnnnnnn` invocation and leave the current output in the input stream. The discard variant will gobble the current output and leave nothing in the input stream. Might be used inside of the `<normal>`, `<space>`, or `<group>` code of `\etl_act:nnnnnnn`.

<code>\etl_act_break:n</code>	★	<code>\etl_act_break:n {<token list>}</code>
-------------------------------	---	--

This will immediately stop the current `\etl_act:nnnnnnn` invocation, gobble the current output and leave `<token list>` in the input stream. Might be used inside of the `<normal>`, `<space>`, or `<group>` code of `\etl_act:nnnnnnn`.

<code>\etl_act_break_pre:n</code>	★	<code>\etl_act_break_pre:n {<token list>}</code>
<code>\etl_act_break_post:n</code>	★	

This will immediately stop the current `\etl_act:nnnnnnn` invocation and leave the current output in the input stream, and in the case of the normal variant followed by `<token list>`, in the pre-case preceded by `<token list>`.

1.2 Conditionals

\etl_token_if_eq_p:NN ★	\etl_token_if_eq_p:NN <token ₁ > <token ₂ >
\etl_token_if_eq:NNTF ★	\etl_token_if_eq:NNTF <token ₁ > <token ₂ > {\true code} {\false code}

Compares <token₁> and <token₂> and yields true if the two are equal. Two tokens are considered equal if they have the same meaning (so if \if_meaning:w is true) and the same string representation (so if \str_if_eq:nnTF is true).

\etl_if_eq_p:nn ★	\etl_if_eq_p:nn {\token list ₁ } {\token list ₂ }
\etl_if_eq:nnTF ★	\etl_if_eq:nnTF {\token list ₁ } {\token list ₂ } {\true code} {\false code}

Compares <token list₁> and <token list₂> with each other on a token-by-token basis. Keep in mind that there are tokens which can't be told apart from each other, and that groups are normalised. If both token lists match (modulo the mentioned limitations) the <true code> is left in the input stream, else the <false code>.

\etl_token_if_in_p:nN ★	\etl_token_if_in_p:nN {\token list} <token>
\etl_token_if_in:nNTF ★	\etl_token_if_in:nNTF {\token list} <token> {\true code} {\false code}

Searches for <token> inside the <token list>. If it is found returns true. Brace groups inside the <token list> are ignored.

\etl_token_if_in_deep_p:nN ★	\etl_token_if_in_deep_p:nN {\token list} <token>
\etl_token_if_in_deep:nNTF ★	\etl_token_if_in_deep:nNTF {\token list} <token> {\true code} {\false code}

Searches for <token> inside the <token list>. If it is found returns true. Brace groups inside the <token list> are recursively searched as well.

\etl_if_in_p:nn ★	\etl_if_in_p:nn {\token list} {\search text}
\etl_if_in:nnTF ★	\etl_if_in:nnTF {\token list} {\search text} {\true code} {\false code}

Searches for <search text> inside of <token list>. If it is found the <true code> is left in the input stream, else the <false code>. Both macro parameter tokens as well as tokens with category code 1 and 2 (normally { }) can be part of <search text> (unlike for the similar function \etl_if_in:nnTF). Material inside of groups in <token list> is ignored (except for the groups contained in <search text>). So the following would first yield true and then false:

```
\etl_if_in:nnTF { a{b{c}} } { {b{c}} } { true } { false }
\etl_if_in:nnTF { a{b{c}} } { b{c} } { true } { false }
```

\etl_if_in_deep_p:nn ★	\etl_if_in_deep_p:nn {\token list} {\search text}
\etl_if_in_deep:nnTF ★	\etl_if_in_deep:nnTF {\token list} {\search text} {\true code} {\false code}

Does the same as \etl_if_in:nnTF but also recursively searches inside of groups in <token list>. So this would yield true in both of the cases in above example.

1.3 Modifying token lists

`\etl_token_replace_once:nNn` ★ `\etl_token_replace_once:nNn {<token list>} <token> {<replacement>}`

This function will replace the first occurrence of `<token>` inside of `<token list>` that is not hidden inside a group with `<replacement>`. The `<token>` has to be a valid N-type argument.

T_EXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an x- or e-type argument expansion. The result will be returned after exactly two steps of expansion.

`\etl_token_replace_all:nNn` ★ `\etl_token_replace_all:nNn {<token list>} <token> {<replacement>}`

This function will replace each occurrence of `<token>` inside of `<token list>` that is not hidden inside a group with `<replacement>`. The `<token>` has to be a valid N-type argument.

T_EXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an x- or e-type argument expansion. The result will be returned after exactly two steps of expansion.

`\etl_token_replace_all_deep:nNn` ★ `\etl_token_replace_all_deep:nNn {<token list>} <token> {<replacement>}`

This function will replace each occurrence of `<token>` inside of `<token list>` with `<replacement>`. The `<token>` has to be a valid N-type argument.

T_EXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an x- or e-type argument expansion. The result will be returned after exactly two steps of expansion.

`\etl_replace_once:nnn` ★ `\etl_replace_once:nnn <token list> <search text> <replacement>`

This function will replace the first occurrence of `<search text>` inside of `<token list>` that is not hidden inside a group with `<replacement>`.

T_EXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an x- or e-type argument expansion. The result will be returned after exactly two steps of expansion.

`\etl_replace_all:nnn` ★ `\etl_replace_all:nnn <token list> <search text> <replacement>`

This function will replace all occurrences of `<search text>` inside of `<token list>` that are not hidden inside a group with `<replacement>`.

T_EXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an x- or e-type argument expansion. The result will be returned after exactly two steps of expansion.

```
\etl_replace_all_deep:nnn ★ \etl_replace_all_deep:nnn <token list> <search text> <replacement>
```

This function will replace all occurrences of $\langle search\ text \rangle$ inside of $\langle token\ list \rangle$ with $\langle replacement \rangle$.

TeXhackers note: The result is returned within $\exp_not:n$, which means that the token list does not expand further when appearing in an x- or e-type argument expansion. The result will be returned after exactly two steps of expansion.

1.4 New expandable fast tests

Functions generated with the means in this section are as fast as the `l3tl` variants of them, but have at least one fixed argument.

```
\etl_new_if_in:Nnn \etl_new_if_in:Nnn <function> <search text> <conditions>
```

This will define a new $\langle function \rangle$ which will act as a conditional and search for $\langle search\ text \rangle$ inside of an n-type argument completely expandable. The $\langle conditions \rangle$ should be a comma-separated list containing one or more of p, T, F and TF (just like for `\prg_new_conditional:Npnn`). The $\langle search\ text \rangle$ must not contain tokens with category code 1 or 2 (normally `{}`) and can't contain macro parameter tokens (normally `#`). Unlike for the conditionals in [subsection 1.2](#), the $\langle search\ text \rangle$ of functions created with `\etl_new_if_in:Nnn` might contain `\s_etl_stop` tokens.

So the following would yield true followed by false:

```
\etl_new_if_in:Nnn \my_if_a_in:n { a } { TF }
\my_if_a_in:nTF { a text } { true } { false }
\my_if_a_in:nTF {   text } { true } { false }
```

1.5 Bugs and Feature Requests

If you find bugs or want to request features you can do so either via email (see the first page) or via Github at https://github.com/Skillmon/ltx_etl/issues.

2 Implementation

```

1 <*pkg>
2 <@@=etl>

   Tell who we are:
3 \ProvidesExplPackage{etl}
4   {2021-08-20} {0.1}
5   {expandable token list manipulation}

   Ensure dependencies are met:
6 \cs_if_exist:NF \tex_expanded:D
7   {
8     \msg_new:nnn { etl } { expanded-missing }
9     { The expanded primitive is required. }
10    \msg_fatal:nn { etl } { expanded-missing }
11  }

```

2.1 Primitives

```

\__etl_expanded:w Private copies of a few primitives (evil code for expl3).
\__etl_unexpanded:w
\__etl_detokenize:w
12 \cs_new_eq:NN \__etl_expanded:w \tex_expanded:D
13 \cs_new_eq:NN \__etl_unexpanded:w \tex_unexpanded:D
14 \cs_new_eq:NN \__etl_detokenize:w \tex_detokenize:D

(End definition for \__etl_expanded:w, \__etl_unexpanded:w, and \__etl_detokenize:w.)

```

2.2 Variables

```

\s__etl_stop Scan marks.
\s__etl_mark
15 \scan_new:N \s__etl_stop
16 \scan_new:N \s__etl_mark

(End definition for \s__etl_stop and \s__etl_mark.)

```

2.3 Small auxiliaries

```

\__etl_if_mark:nTF A small check whether some argument contains the scan mark \s__etl_mark, the mark
\__etl_if_mark:w should always be the last token of the argument (and only a single such mark should be
\__etl_if_mark_true:w contained) to ensure correct behaviour.
17 \cs_new:Npn \__etl_if_mark:nTF #1
18   { \__etl_if_mark:w #1 \__etl_if_mark_true:w \s__etl_mark \use_ii:nn }
19 \cs_new:Npn \__etl_if_mark:w #1 \s__etl_mark {}
20 \cs_new:Npn \__etl_if_mark_true:w \s__etl_mark \use_ii:nn #1#2 {#1}

(End definition for \__etl_if_mark:nTF, \__etl_if_mark:w, and \__etl_if_mark_true:w.)

\__etl_split_first:w Can be used to extract the first element from a token list, it should always be used like
this: \exp_after:wN <function> \@@_expanded:w { \@@_split_first:w <arg> }.
21 \cs_new:Npn \__etl_split_first:w #1
22   {
23     { \__etl_unexpanded:w {#1} }
24     \if_false: { \fi: \exp_after:wN } \exp_after:wN { \if_false: } \fi:
25   }

```

(End definition for `__etl_split_first:w`.)

```

\__etl_turn_true:w Fast ways to change the outcome of a test.
\__etl_fi_turn_false:w 26 \cs_new:Npn \__etl_turn_true:w \if_false: { \if_true: }
27 \cs_new:Npn \__etl_fi_turn_false:w \fi: \if_true: { \fi: \if_false: }

(End definition for \__etl_turn_true:w and \__etl_fi_turn_false:w.)

```

```

\__etl_rm_space:w Fast macro to gobble an immediately following single space.
28 \use:n { \cs_new:Npn \__etl_rm_space:w } ~ {}

(End definition for \__etl_rm_space:w.)

```

```

\__etl_if_empty:nTF This is a fast test whether something is empty or not. The argument must not contain
\__etl_if_empty:nT \s__etl_stop for this to work (but since that limitation is true for most if not all user
\__etl_if_empty:w facing functions of this module, this is fine to gain a bit of speed).
\__etl_if_empty_true:w 29 \cs_new:Npn \__etl_if_empty:nT #1
\__etl_if_empty_true_TF:w 30 {
31 \__etl_if_empty:w
32 \s__etl_stop #1 \s__etl_stop \__etl_if_empty_true:w
33 \s__etl_stop \s__etl_stop \use_none:n
34 }
35 \cs_new:Npn \__etl_if_empty:nTF #1
36 {
37 \__etl_if_empty:w
38 \s__etl_stop #1 \s__etl_stop \__etl_if_empty_true_TF:w
39 \s__etl_stop \s__etl_stop \use_ii:nn
40 }
41 \cs_new:Npn \__etl_if_empty:w #1 \s__etl_stop \s__etl_stop {}
42 \cs_new:Npn \__etl_if_empty_true:w \s__etl_stop \s__etl_stop \use_none:n #1
43 {#1}
44 \cs_new:Npn \__etl_if_empty_true_TF:w \s__etl_stop \s__etl_stop \use_ii:nn #1#2
45 {#1}

(End definition for \__etl_if_empty:nTF and others.)

```

```

\__etl_if_head_is_group:nTF This test works pretty much the same way \tl_if_head_is_group:nTF works, but it is
\__etl_if_head_is_group:nT faster because it gets rid of the unnecessary \if:w and instead only works by argument
gobbling. Drawback is that if you only expand the macro twice you could end up with
unbalanced braces.

```

```

46 \cs_new:Npn \__etl_if_head_is_group:nTF #1
47 {
48 \exp_after:wN \use_none:n \exp_after:wN
49 {
50 \exp_after:wN { \token_to_str:N #1 ? }
51 \exp_after:wN \use_iii:nnnn \token_to_str:N
52 }
53 \use_ii:nn
54 }
55 \cs_new:Npn \__etl_if_head_is_group:nT #1
56 {
57 \exp_after:wN \use_none:n \exp_after:wN
58 {
59 \exp_after:wN { \token_to_str:N #1 ? }

```



```

60         \exp_after:wN \use_iii:nnn \token_to_str:N
61     }
62     \use_none:n
63 }

```

(End definition for `__etl_if_head_is_group:nTF` and `__etl_if_head_is_group:nT`.)

2.4 The act loop

```

\etl_act:nnnnnnn
\etl_act:nnnnnnn
\etl_act:nnnnnn
\__etl_act:nnnnnnn
\__etl_act_just_result:nn

```

The act loop is modelled after the `expl3` internal `__tl_act:NNNn` but with a few more features making it more general. Those are (argument to `\etl_act:nnnnnnn` in parentheses): a status (#5), n-type mapping instead of just N-type functions, a final result processing (#4), and the possibility to preset some output (#6). The other arguments are: #7 the token list on which we should act, #1 function to use for N-type elements in that list, #2 function to use for spaces in that list, and #3 function to use on groups in that list.

Just like the `__tl_act:NNNn` function, this has a token which must not occur in the arguments, in this case that token is `\s__etl_stop`. The result is stored as an argument to the (undefined) function `__etl_act_result:n`.

```

64 \cs_new:Npn \etl_act:nnnnnnn #1#2#3#4#5#6#7
65 {
66     \__etl_unexpanded:w \__etl_expanded:w
67     {
68         {
69             \__etl_act:w #7 {\s__etl_stop} . \s__etl_stop {#5} {#1} {#2} {#3}
70             \__etl_act_result:n {#6} {#4}
71         }
72     }
73 }

```

We also provide a version without the `__etl_unexpanded:w` around it for internal purposes, in which we'd otherwise have to remove it for correct behaviour.

```

74 \cs_new:Npn \__etl_act:nnnnnnn #1#2#3#4#5#6#7
75 {
76     \__etl_expanded:w
77     {
78         \__etl_act:w #7 {\s__etl_stop} . \s__etl_stop {#5} {#1} {#2} {#3}
79         \__etl_act_result:n {#6} {#4}
80     }
81 }

```

We also provide two reduced function variants, the first without presetting some output, the second also without the final processor.

```

82 \exp_args:Nno \use:n { \cs_new:Npn \etl_act:nnnnnnn #1#2#3#4#5#6 }
83 { \etl_act:nnnnnnn {#1} {#2} {#3} {#4} {#5} {} {#6} }
84 \exp_args:Nno \use:n { \cs_new:Npn \etl_act:nnnnn #1#2#3#4#5 }
85 { \etl_act:nnnnnnn {#1} {#2} {#3} \__etl_act_just_result:nn {#4} {} {#5} }

```

The final processor is provided with two n-type arguments (both in braces) the first being the status, the second the output. To just get the output we gobble the status and put `__etl_unexpanded:w` there to protect the final output from further expanding.

```

86 \cs_new:Npn \__etl_act_just_result:nn #1 { \__etl_unexpanded:w }

```

(End definition for `\etl_act:nnnnnnn` and others. These functions are documented on page 2.)

`__etl_if_head_is_space:nTF` We need a few macros with spaces at weird places so define them here. Since we got the
`__etl_if_head_is_space_true:w` limitation of not allowing `\s__etl_stop` we can use that token to get some fast tests.
`__etl_if_head_is_N_type:nTF` The first tests for a space at the front, and since that one is pretty fast we can use it to
`__etl_if_head_is_N_type_false:w` build a faster alternative to check for a starting N-type as well (with the drawback that
`__etl_act:w` this would yield true for an empty argument, something we have to keep in mind).
`__etl_act_if_space:w`
`__etl_act_space:w`

```

87 \group_begin:
88 \cs_set:Npn \__etl_tmp:n #1
89 {
90   \cs_new:Npn \__etl_if_head_is_space:nTF ##1
91   {
92     \__etl_act_if_space:w
93     \s__etl_stop ##1 \s__etl_stop \__etl_if_head_is_space_true:w
94     \s__etl_stop #1 \s__etl_stop \use_ii:nn
95   }
96   \cs_new:Npn \__etl_if_head_is_space_true:w
97   \s__etl_stop #1 \s__etl_stop \use_ii:nn ##1##2
98   {##1}
99   \cs_new:Npn \__etl_if_head_is_N_type:nTF ##1
100   {
101     \__etl_act_if_space:w
102     \s__etl_stop ##1 \s__etl_stop \__etl_if_head_is_N_type_false:w
103     \s__etl_stop #1 \s__etl_stop
104     \__etl_if_head_is_group:nT {##1} \use_iii:nnn
105     \use_i:nn
106   }
107   \cs_new:Npn \__etl_if_head_is_N_type_false:w
108   \s__etl_stop #1 \s__etl_stop
109   \__etl_if_head_is_group:nT ##1 \use_iii:nnn
110   \use_i:nn
111   ##2##3
112   {##3}

```

The act loop `__etl_act:w` grabs the remainder of the list, delimited by `\s__etl_stop`, picks up the status (`##2`), and the user provided functions for N-types (`##3`), spaces (`##4`), and groups (`##5`). We need to check which type is at the head of the token list (the space test is a bit stripped down, and very fast this way).

```

113 \cs_new:Npn \__etl_act:w ##1 \s__etl_stop ##2##3##4##5
114 {
115   \__etl_act_if_space:w
116   \s__etl_stop ##1 \s__etl_stop \__etl_act_space:w {##4}
117   \s__etl_stop #1 \s__etl_stop
118   \__etl_if_head_is_group:nT {##1} \__etl_act_group:w
119   \__etl_act_normal:w {##3} {##5}
120   {##2} ##1 \s__etl_stop {##2} {##3} {##4} {##5}
121 }

```

The check for spaces just gobbles everything up to the first `\s__etl_stop`. If we found a space at the head we remove that space and leave in the input the space function, the status, and `__etl_act:w` for the next iteration.

```

122 \cs_new:Npn \__etl_act_if_space:w ##1 \s__etl_stop #1 ##2 \s__etl_stop {}
123 \cs_new:Npn \__etl_act_space:w
124   ##1 \s__etl_stop #1 \s__etl_stop
125   \__etl_if_head_is_group:nT ##2 \__etl_act_group:w \__etl_act_normal:w ##3 ##4
126   ##5 #1

```

```

127         { ##1 {##5} \_etl_act:w }
128     }
129     \_etl_tmp:n { ~ }
130 \group_end:

(End definition for \_etl_if_head_is_space:nTF and others.)

```

_etl_act_normal:w For a normal token we can act quite easy, just pick up that token and leave the next iteration in the input stream (#2 is the group code, which is gobbled).

```

131 \cs_new:Npn \_etl_act_normal:w #1#2#3#4 { #1 {#3} #4 \_etl_act:w }

(End definition for \_etl_act_normal:w.)

```

_etl_act_group:w Since the end marker is a single \s_etl_stop in a group, we have to test whether that end marker is found. The test here leads to undefined behaviour if the user supplied token list contains such a marker at an any point. If the end marker is found we call the final handler (for which we have to remove the \s_etl_stop to correctly grab its arguments), else we provide the user supplied function the next group and input the next iteration. #1 is the normal function, which is gobbled.

```

132 \cs_new:Npn \_etl_act_group:w \_etl_act_normal:w #1#2#3#4
133 {
134     \_etl_act_if_end:w #4 \use_i:nn \etl_act_do_final: \s\_etl_stop
135     #2 {#3} {#4} \_etl_act:w
136 }
137 \cs_new:Npn \_etl_act_if_end:w #1 \s\_etl_stop {}

(End definition for \_etl_act_group:w and \_etl_act_if_end:w.)

```

\etl_act_output:n To allow reordering the output we unfortunately can't just use _etl_unexpanded:w and be done, so we have to shift a few tokens around instead. All the output macros work by the same idea, except for \etl_act_output_rest: and \etl_act_output_rest_pre:, since it's a non-trivial task to get the remainder of the argument. Instead these two swap out the user provided functions for some that only pass through the input as output, for which we need six internal output macros.

In those cases in which we don't need reordering, we can internally shortcut using _etl_unexpanded:w.

```

138 \cs_new:Npn \etl_act_output:n #1 #2 \_etl_act_result:n #3
139 { #2 \_etl_act_result:n { #3 #1 } }
140 \cs_new:Npn \etl_act_output_pre:n #1 #2 \_etl_act_result:n #3
141 { #2 \_etl_act_result:n { #1 #3 } }
142 \cs_new:Npn \etl_act_output_rest: #1 \s\_etl_stop #2#3#4#5
143 {
144     #1 \s\_etl_stop {#2}
145     \_etl_act_output_normal:nN \_etl_act_output_space:n \_etl_act_output_group:nn
146 }
147 \cs_new:Npn \etl_act_output_rest_pre: #1 \s\_etl_stop #2#3#4#5
148 {
149     #1 \s\_etl_stop {#2}
150     \_etl_act_output_normal_pre:nN
151     \_etl_act_output_space_pre:n
152     \_etl_act_output_group_pre:nn
153 }
154 \cs_new:Npn \_etl_act_output_normal:nN #1#2 #3 \_etl_act_result:n #4
155 { #3 \_etl_act_result:n { #4 #2 } }

```

```

156 \cs_new:Npn \__etl_act_output_space:n #1 #2 \__etl_act_result:n #3
157   { #2 \__etl_act_result:n { #3 ~ } }
158 \cs_new:Npn \__etl_act_output_group:nn #1#2 #3 \__etl_act_result:n #4
159   { #3 \__etl_act_result:n { #4 {#2} } }
160 \cs_new:Npn \__etl_act_output_normal_pre:nN #1#2 #3 \__etl_act_result:n #4
161   { #3 \__etl_act_result:n { #2 #4 } }
162 \cs_new:Npn \__etl_act_output_space_pre:n #1 #2 \__etl_act_result:n #3
163   { #2 \__etl_act_result:n { ~ #3 } }
164 \cs_new:Npn \__etl_act_output_group_pre:nn #1#2 #3 \__etl_act_result:n #4
165   { #3 \__etl_act_result:n { {#2} #4 } }
166 \cs_new:Npn \__etl_act_unexpanded_normal:nN #1 { \exp_not:N }
167 \cs_new:Npn \__etl_act_unexpanded_space:n #1 { ~ }
168 \cs_new:Npn \__etl_act_unexpanded_group:nn #1#2 { { \__etl_unexpanded:w {#2} } }

```

(End definition for `\etl_act_output:n` and others. These functions are documented on page 2.)

`\etl_act_status:n` Just switch out the status which is stored immediately after `\s__etl_stop`.

```

169 \cs_new:Npn \etl_act_status:n #1 #2 \s__etl_stop #3
170   { #2 \s__etl_stop {#1} }

```

(End definition for `\etl_act_status:n`. This function is documented on page 3.)

`\etl_act_put_back:n` Place the first argument after the next iteration of the loop. This macro might strip a set of braces around #2, because it could happen that the user provided code only leaves one group between this functions argument and `__etl_act:w`, but that would arguably be wrong input anyway, an easy fix would be to use

```

\cs_new:Npn \etl_act_put_back:n #1
  { \@_act_put_back:nw {#1} \prg_do_nothing: }
\cs_new:Npn \@_act_put_back:nw #1 #2 \@_act:w { #2 \@_act:w #1 }

```

instead of:

```

171 \cs_new:Npn \etl_act_put_back:n #1 #2 \__etl_act:w { #2 \__etl_act:w #1 }

```

(End definition for `\etl_act_put_back:n`. This function is documented on page 3.)

`\etl_act_switch:nnn` Pretty straight forward, just switch out the user provided functions for the new argument.

```

\etl_act_switch_normal:n
\etl_act_switch_space:n
\etl_act_switch_group:n
172 \cs_new:Npn \etl_act_switch:nnn #1#2#3 #4 \s__etl_stop #5#6#7#8
173   { #4 \s__etl_stop {#5} {#1} {#2} {#3} }
174 \cs_new:Npn \etl_act_switch_normal:n #1 #2 \s__etl_stop #3#4
175   { #2 \s__etl_stop {#3} {#1} }
176 \cs_new:Npn \etl_act_switch_space:n #1 #2 \s__etl_stop #3#4#5
177   { #2 \s__etl_stop {#3} {#4} {#1} }
178 \cs_new:Npn \etl_act_switch_group:n #1 #2 \s__etl_stop #3#4#5#6
179   { #2 \s__etl_stop {#3} {#4} {#5} {#1} }

```

(End definition for `\etl_act_switch:nnn` and others. These functions are documented on page 3.)

`\etl_act_do_final:` These are different forms to end the loop. The first will gobble the remainder and apply the final action on the token list currently stored for output.

`\etl_act_break:` The break variants will gobble the final action and output what's currently there (except for the discard variant).

```

\etl_act_break_discard:
\etl_act_break:n
\etl_act_break_pre:n
\etl_act_break_post:n
180 \cs_new:Npn \etl_act_do_final: #1 \s__etl_stop #2#3 \__etl_act_result:n #4#5
181   { #5 {#2} {#4} }

```

```

182 \cs_new:Npn \etl_act_break: #1 \__etl_act_result:n #2#3 { \__etl_unexpanded:w {#2} }
183 \cs_new:Npn \etl_act_break_discard: #1 \__etl_act_result:n #2#3 {}
184 \cs_new:Npn \etl_act_break:n #1 #2 \__etl_act_result:n #3#4
185 { \__etl_unexpanded:w {#1} }
186 \cs_new:Npn \etl_act_break_pre:n #1 #2 \__etl_act_result:n #3#4
187 { \__etl_unexpanded:w { #1 #3 } }
188 \cs_new:Npn \etl_act_break_post:n #1 #2 \__etl_act_result:n #3#4
189 { \__etl_unexpanded:w { #3 #1 } }

```

(End definition for `\etl_act_do_final:` and others. These functions are documented on page 3.)

2.5 Expandable tests

`\etl_token_if_eq_p:NN`
`\etl_token_if_eq:NNTF`

We consider two tokens equal when they have the same meaning and the same string representation. This isn't always correct. If an active character is let to the same character with a different category code those two tokens aren't distinguishable by expansion, *afaik*. To get the optimisation of `\prg_new_conditional:Npnn` we use `\if_false:` and turn it true if both tests are true (this is easier than coding all four variants by hand, even though that could give slightly better performance). The exception being the TF variant, since that is used in the inner loop of many functions. The braces around the arguments of `\token_if_eq_meaning:NNT` are necessary because of the first step of expansion applied to that function.

```

190 \exp_args:Nno \use:n { \cs_new:Npn \etl_token_if_eq:NNTF #1#2 }
191 {
192   \token_if_eq_meaning:NNT {#1} {#2} { \str_if_eq:nnT #1#2 \use_ii:nnn }
193   \use_ii:nn
194 }
195 \exp_args:Nno
196 \use:n { \prg_new_conditional:Npnn \etl_token_if_eq:NN #1#2 { T , F , p } }
197 {
198   \token_if_eq_meaning:NNT {#1} {#2} { \str_if_eq:nnT #1#2 \__etl_turn_true:w }
199   \if_false:
200     \prg_return_true:
201   \else:
202     \prg_return_false:
203   \fi:
204 }

```

(End definition for `\etl_token_if_eq:NNTF`. This function is documented on page 4.)

`\etl_token_if_in_p:nN`
`\etl_token_if_in:nNTF`
`__etl_token_if_in:NnN`

Searching for just a single token is rather easy, we just loop over the list and compare the N-type tokens to the one token provided. If we find a match we break and return true, else we'll return false eventually.

```

205 \exp_args:Nno
206 \use:n { \prg_new_conditional:Npnn \etl_token_if_in:nN #1#2 { TF , T , F , p } }
207 {
208   \__etl_act:nnnnnnn
209   \__etl_token_if_in:NN \use_none:n \use_none:nn
210   \__etl_act_just_result:nn
211   {#2}
212   \if_false:
213     {#1}
214   \prg_return_true:

```

```

215     \else:
216         \prg_return_false:
217     \fi:
218 }
219 \exp_args:Nno \use:n { \cs_new:Npn \__etl_token_if_in:NN #1#2 }
220 {
221     \etl_token_if_eq:NNTF {#1} {#2} { \etl_act_break:n \if_true: } {}
222 }

```

(End definition for \etl_token_if_in:nNTF and __etl_token_if_in:NnN. This function is documented on page 4.)

\etl_token_if_in_deep_p:nN
\etl_token_if_in_deep:nNTF
__etl_token_if_in_deep:Nn

The deep variant just has to recursively call itself on groups to also search those.

```

223 \exp_args:Nno \use:n
224 { \prg_new_conditional:Npnn \etl_token_if_in_deep:nN #1#2 { TF , T , F , p } }
225 {
226     \__etl_act:nnnnnnn
227     \__etl_token_if_in:NN \use_none:n \__etl_token_if_in_deep:Nn
228     \__etl_act_just_result:nn
229     {#2}
230     \if_false:
231     {#1}
232     \prg_return_true:
233     \else:
234     \prg_return_false:
235     \fi:
236 }
237 \exp_args:Nno \use:n { \cs_new:Npn \__etl_token_if_in_deep:Nn #1#2 }
238 { \etl_token_if_in_deep:nNT {#2} {#1} { \etl_act_break:n \if_true: } }

```

(End definition for \etl_token_if_in_deep:nNTF and __etl_token_if_in_deep:Nn. This function is documented on page 4.)

\etl_if_eq_p:nn
\etl_if_eq:nnTF
__etl_if_eq_normal:nN
__etl_if_eq_normal:NnN
__etl_if_eq_space:n
__etl_if_eq_group:nn
__etl_if_eq_group:nnn
__etl_if_eq_final:nn

The test needs to compare the full lists on a token-by-token basis. One of the two lists is stored inside the status the other is processed. The act code will then leave either \if_false: or \if_true: in the input stream.

```

239 \exp_args:Nno
240 \use:n { \prg_new_conditional:Npnn \etl_if_eq:nn #1#2 { TF , T , F , p } }
241 {
242     \__etl_act:nnnnnnn
243     \__etl_if_eq_normal:nN
244     \__etl_if_eq_space:n
245     \__etl_if_eq_group:nn
246     \__etl_if_eq_final:nn
247     {#2}
248     {}
249     {#1}
250     \prg_return_true:
251     \else:
252     \prg_return_false:
253     \fi:
254 }

```

To compare the next token we need to check whether the status is already empty (which would mean that token list is longer, hence not equal), if it's not empty and the head is

N-type we compare these two (the test here for N-type fails for empty arguments, hence we have to test this separately). If they are equal we store the rest of the second token list in the status and go on with the loop, else we break out and return false.

```

255 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_eq_normal:nN #1#2 }
256 {
257   \__etl_if_empty:nT {#1} { \etl_act_break:n \if_false: }
258   \__etl_if_head_is_N_type:nTF {#1}
259   {
260     \exp_after:wN \__etl_if_eq_normal:NnN
261     \__etl_expanded:w { \__etl_split_first:w #1 }
262     #2
263   }
264   { \etl_act_break:n \if_false: }
265 }
266 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_eq_normal:NnN #1#2#3 }
267 {
268   \etl_token_if_eq:NNTF {#1} {#3}
269   { \etl_act_status:n {#2} }
270   { \etl_act_break:n \if_false: }
271 }

```

Spaces are pretty similar, but easier, we don't need to split of the first token in a complicated manner, instead we just gobble a leading space.

```

272 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_eq_space:n #1 }
273 {
274   \__etl_if_head_is_space:nTF {#1}
275   { \exp_after:wN \etl_act_status:n \exp_after:wN { \__etl_rm_space:w #1 } }
276   { \etl_act_break:n \if_false: }
277 }

```

Groups are similarly handled to normal arguments, but instead of comparing only two tokens we have to compare by recursion.

```

278 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_eq_group:nn #1 }
279 {
280   \__etl_if_head_is_group:nTF {#1}
281   {
282     \exp_after:wN \__etl_if_eq_group:nnn
283     \__etl_expanded:w { \__etl_split_first:w #1 }
284   }
285   { \etl_act_break:n \if_false: }
286 }
287 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_eq_group:nnn #1#2#3 }
288 {
289   \etl_if_eq:nnTF {#1} {#3}
290   { \etl_act_status:n {#2} }
291   { \etl_act_break:n \if_false: }
292 }

```

Finally, if the loop didn't break until the first token list is empty we just have to make sure that the second list is also empty by now. If that's the case the two are equal, else not. We need to leave either true or false (protected against the __etl_expanded:w expansion) in the input.

```

293 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_eq_final:nn #1#2 }
294 {

```

```

295 \exp_after:wN
296 \__etl_unexpanded:w
297 \__etl_if_empty:nT {#1} { { \if_true: } \use_none:n } { \if_false: }
298 }

```

(End definition for `\etl_if_eq:nnTF` and others. This function is documented on page 4.)

```

\etl_if_in_p:nn \etl_if_in:nn has to reevaluate every token but the very first in order to compare
\etl_if_in:nnTF them, else something like aab wouldn't contain ab according to the test, because the
\__etl_if_in_normal:nN second a would've been gobbled. For this we need \__etl_if_in_put_back:n which
\__etl_if_in_normal:nnnN will remove the first token (we need to watch out for spaces) and puts the rest back
\__etl_if_in_normal:NnnnN using \etl_act_put_back:n.
\__etl_if_in_space:n 299 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_put_back:n #1 }
\__etl_if_in_space:nnn 300 {
\__etl_if_in_group:nn 301 \__etl_if_head_is_space:nTF {#1}
\__etl_if_in_group:nnnn 302 { \exp_after:wN \etl_act_put_back:n \exp_after:wN { \__etl_rm_space:w #1 } }
\__etl_if_in_group:nnnnn 303 { \exp_after:wN \etl_act_put_back:n \exp_after:wN { \use_none:n #1 } }
\__etl_if_in_put_back:n 304 }

```

As already said, we'll need to reinsert some tokens, and we'll might have to revert what was already matched, so inside of the status we store the remainder of the pattern which needs to be matched, followed by the entire pattern, followed by the tokens which were already matched (and might need to be put back). As soon as the pattern is matched the remainder will be empty and we'll leave `\if_true:` in the input, at the end of the entire list we'll leave `\if_false:`, which we store in the prefilled output. The emptiness of the pattern will be checked before the next token is evaluated, so the trailing space after #1 does no harm but allows the token list to end in the pattern.

All of the macros used as arguments to `__etl_act:nnnnnnn` will need to unbrace the status which will then lead to three arguments. Else this is pretty much the same idea as `\etl_if_eq:nnTF`.

```

305 \exp_args:Nno
306 \use:n { \prg_new_conditional:Npnn \etl_if_in:nn #1#2 { TF , T , F , p } }
307 {
308 \__etl_act:nnnnnnn
309 \__etl_if_in_normal:nN \__etl_if_in_space:n \__etl_if_in_group:nn
310 \__etl_act_just_result:nn
311 { { #2 } { #2 } {} }
312 \if_false:
313 { #1 ~ }
314 \prg_return_true:
315 \else:
316 \prg_return_false:
317 \fi:
318 }

```

Just like `__etl_if_in_group:nn`, `__etl_if_in_normal:nN` needs to split off the first token of the pattern, for which `__etl_split_first:w` is used, and `__etl_if_in_space:n` needs to trim off a leading space.

```

319 \cs_new:Npn \__etl_if_in_normal:nN #1 { \__etl_if_in_normal:nnnN #1 }
320 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_normal:nnnN #1#2#3#4 }
321 {
322 \__etl_if_empty:nT {#1} { \etl_act_break:n \if_true: }
323 \__etl_if_head_is_N_type:nTF {#1}
324 {

```



```

325         \exp_after:wN \__etl_if_in_normal:NnnnN
326         \__etl_expanded:w { \__etl_split_first:w #1 } {#2} {#3} #4
327     }
328     {
329         \etl_act_status:n { {#2} {#2} {} }
330         \__etl_if_in_put_back:n { #3 #4 }
331     }
332 }
333 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_normal:NnnnN #1#2#3#4#5 }
334 {
335     \etl_token_if_eq:NNTF {#1} {#5}
336     { \etl_act_status:n { {#2} {#3} {#4#5} } }
337     {
338         \__etl_if_in_put_back:n { #4 #5 }
339         \etl_act_status:n { {#3} {#3} {} }
340     }
341 }
342 \cs_new:Npn \__etl_if_in_space:n #1 { \__etl_if_in_space:nnn #1 }
343 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_space:nnn #1#2#3 }
344 {
345     \__etl_if_empty:nT {#1} { \etl_act_break:n \if_true: }
346     \__etl_if_head_is_space:nTF {#1}
347     {
348         \exp_after:wN \etl_act_status:n \exp_after:wN
349         { \exp_after:wN { \__etl_rm_space:w #1 } {#2} { #3 ~ } }
350     }
351     {
352         \__etl_if_in_put_back:n { #3 ~ }
353         \etl_act_status:n { {#2} {#2} {} }
354     }
355 }
356 \cs_new:Npn \__etl_if_in_group:nn #1 { \__etl_if_in_group:nnnn #1 }
357 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_group:nnnn #1 }
358 {
359     \__etl_if_empty:nT {#1} { \etl_act_break:n \if_true: }
360     \__etl_if_head_is_group:nTF {#1}
361     {
362         \exp_after:wN \__etl_if_in_group:nnnn
363         \__etl_expanded:w { \__etl_split_first:w #1 }
364     }
365     { \__etl_if_in_group_false:nnn }
366 }
367 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_group:nnnn #1#2#3#4#5 }
368 {
369     \etl_if_eq:nnTF {#1} {#5}
370     { \etl_act_status:n { {#2} {#3} { #4 {#5} } } }
371     {
372         \__etl_if_in_put_back:n { #4 {#5} }
373         \etl_act_status:n { {#3} {#3} {} }
374     }
375 }
376 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_group_false:nnn #1#2#3 }
377 {
378     \__etl_if_in_put_back:n { #2 {#3} }

```

```

379     \etl_act_status:n { {#1} {#1} {} }
380 }

```

(End definition for \etl_if_in:nnTF and others. This function is documented on page 4.)

\etl_if_in_deep_p:nn
\etl_if_in_deep:nnTF

In essence this is the same as \etl_if_in:nnTF, but additionally every time a group is encountered we need to search that group by recursion as well after directly comparing it to the pattern.

__etl_if_in_group_deep:nn
__etl_if_in_group_deep:nnnn
__etl_if_in_group_deep:nnnnn
__etl_if_in_group_deep_false:nnn

```

381 \exp_args:Nno
382 \use:n { \prg_new_conditional:Npn \etl_if_in_deep:nn #1#2 { TF , T , F , p } }
383 {
384   \__etl_act:nnnnnnn
385   \__etl_if_in_normal:nN \__etl_if_in_space:n \__etl_if_in_group_deep:nn
386   \__etl_act_just_result:nn
387   { { #2 } { #2 } {} }
388   \if_false:
389   { #1 ~ }
390   \prg_return_true:
391   \else:
392   \prg_return_false:
393   \fi:
394 }
395 \cs_new:Npn \__etl_if_in_group_deep:nn #1 { \__etl_if_in_group_deep:nnnn #1 }
396 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_group_deep:nnnn #1 }
397 {
398   \__etl_if_empty:nT {#1} { \etl_act_break:n \if_true: }
399   \__etl_if_head_is_group:nTF {#1}
400   {
401     \exp_after:wN \__etl_if_in_group_deep:nnnnn
402     \__etl_expanded:w { \__etl_split_first:w #1 }
403   }
404   { \__etl_if_in_group_deep_false:nnn }
405 }
406 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_group_deep:nnnnn #1#2#3#4#5 }
407 {
408   \etl_if_eq:nnTF {#1} {#5}
409   { \etl_act_status:n { {#2} {#3} { #4 {#5} } } }
410   {
411     \etl_if_in_deep:nnT {#5} {#3} { \etl_act_break:n \if_true: }
412     \__etl_if_in_put_back:n { #4 {#5} }
413     \etl_act_status:n { {#3} {#3} {} }
414   }
415 }
416 \exp_args:Nno \use:n { \cs_new:Npn \__etl_if_in_group_deep_false:nnn #1#2#3 }
417 {
418   \etl_if_in_deep:nnT {#3} {#1} { \etl_act_break:n \if_true: }
419   \__etl_if_in_put_back:n { #2 {#3} }
420   \etl_act_status:n { {#1} {#1} {} }
421 }

```

(End definition for \etl_if_in_deep:nnTF and others. This function is documented on page 4.)

\etl_token_replace_all:nNn
__etl_token_replace:NnnN

Replacing a single token (and in fact the same is true for all the replacement actions in this package) doesn't need reordering and no post processing, so we can use in place output using __etl_unexpanded:w. We store the token we want to replace inside the act

function, as well as an additional argument which will be executed once a replacement was done (this is used for the `\etl_token_replace_once:nNn` function).

```

422 \exp_args:Nno \use:n { \cs_new:Npn \etl_token_replace_all:nNn #1#2#3 }
423 {
424   \etl_act:nnnnnn
425   { \__etl_token_replace:NnnN #2 {} }
426   \__etl_act_unexpanded_space:n
427   \__etl_act_unexpanded_group:nn
428   \use_none:nn
429   {#3}
430   {#1}
431 }
432 \exp_args:Nno \use:n { \cs_new:Npn \__etl_token_replace:NnnN #1#2#3#4 }
433 {
434   \etl_token_if_eq:NNTF {#1} {#4}
435   { \__etl_unexpanded:w {#3} #2 }
436   { \__etl_unexpanded:w {#4} }
437 }

```

(End definition for `\etl_token_replace_all:nNn` and `__etl_token_replace:NnnN`. This function is documented on page 5.)

`\etl_token_replace_all_deep:nNn`
`__etl_token_replace_deep:Nnn`

Deep replacement is done by recursion. Since the deep variant will not execute any additional code we omit such an additional argument for it.

```

438 \exp_args:Nno \use:n { \cs_new:Npn \etl_token_replace_all_deep:nNn #1#2#3 }
439 {
440   \etl_act:nnnnnn
441   { \__etl_token_replace:NnnN #2 {} }
442   \__etl_act_unexpanded_space:n
443   { \__etl_token_replace_deep:Nnn #2 }
444   \use_none:nn
445   {#3}
446   {#1}
447 }

```

Here `{#1}` is used to get correct results from the first step of expansion done directly.

```

448 \exp_args:Nno \use:n { \cs_new:Npn \__etl_token_replace_deep:Nnn #1#2#3 }
449 { \exp_after:wN { \etl_token_replace_all_deep:nNn {#3} {#1} {#2} } }

```

(End definition for `\etl_token_replace_all_deep:nNn` and `__etl_token_replace_deep:Nnn`. This function is documented on page 5.)

`\etl_token_replace_once:nNn`

To only handle the first matching token we just let the replacement internal exchange the function to directly output any token.

```

450 \exp_args:Nno \use:n { \cs_new:Npn \etl_token_replace_once:nNn #1#2#3 }
451 {
452   \etl_act:nnnnnn
453   {
454     \__etl_token_replace:NnnN #2
455     { \etl_act_switch_normal:n \__etl_act_unexpanded_normal:nN }
456   }
457   \__etl_act_unexpanded_space:n
458   \__etl_act_unexpanded_group:nn
459   \use_none:nn
460   {#3}

```

```

461     {#1}
462 }

```

(End definition for `\etl_token_replace_once:nNn`. This function is documented on page 5.)

\etl_replace_all:nnn

Replacing an arbitrary number of tokens (which might include braces and spaces) is quite a bit harder than a single N-type. We place in the status the remainder of the pattern, the full pattern, delayed tokens (those which matched the pattern), the replacement, and a marker which should tell us whether we want to only replace the first match (if so use `\s__etl_mark`, else any other single token).

```

463 \exp_args:Nno \use:n { \cs_new:Npn \etl_replace_all:nnn #1#2#3 }
464 {
465     \etl_act:nnnnnn
466     \__etl_replace_normal:nN
467     \__etl_replace_space:n
468     \__etl_replace_group:nn
469     \__etl_replace_final:nn
470     { {#2} {#2} {} {#3} \scan_stop: }
471     {#1}
472 }

```

We again need to be able to put back a few tokens, but this time we also need to know whether the first token is an N-type or group, because we can't just gobble the first element but need to output it unchanged.

```

473 \exp_args:Nno \use:n { \cs_new:Npn \__etl_replace_put_back:nnnN #1#2#3#4 }
474 {
475     \__etl_if_head_is_space:nTF {#1}
476     {
477         \exp_after:wN \etl_act_put_back:n \exp_after:wN { \__etl_rm_space:w #1 } ~
478     }
479     {
480         \__etl_if_head_is_group:nTF {#1}
481         { \exp_after:wN \__etl_replace_put_back_group:nn }
482         { \exp_after:wN \__etl_replace_put_back_normal:Nn }
483         \__etl_expanded:w { \__etl_split_first:w #1 }
484     }
485     \etl_act_status:n { {#2} {#2} {} {#3} #4 }
486 }
487 \cs_new:Npn \__etl_replace_put_back_group:nn #1
488 {
489     \__etl_unexpanded:w { {#1} }
490     \etl_act_put_back:n
491 }
492 \cs_new:Npn \__etl_replace_put_back_normal:Nn #1
493 {
494     \__etl_unexpanded:w {#1}
495     \etl_act_put_back:n
496 }
497 \cs_new:Npn \__etl_replace_normal:nN #1 { \__etl_replace_normal:nnnnN #1 }
498 \exp_args:Nno \use:n { \cs_new:Npn \__etl_replace_normal:nnnnN #1 }
499 {
500     \__etl_if_head_is_N_type:nTF {#1}
501     {
502         \exp_after:wN \__etl_replace_normal:NnnnnN

```

```

503     \_etl_expanded:w { \_etl_split_first:w #1 }
504   }
505   { \_etl_replace_normal_false:nnnNN }
506 }

```

Just to keep track of the different arguments here: #1 is the next token in the pattern, #2 is the remainder of the pattern, #3 is the full pattern stored for reuse, #4 are the delayed tokens, which might need to be put back, #5 is the replacement text, #6 is the marker which might indicate the once function, and #7 is the next token of the input.

```

507 \exp_args:Nno
508 \use:n { \cs_new:Npn \_etl_replace_normal:NnnnnNN #1#2#3#4#5#6#7 }
509 {
510   \etl_token_if_eq:NNTF {#1} {#7}
511   {
512     \_etl_if_empty:nTF {#2}
513     {
514       \_etl_unexpanded:w {#5}
515       \_etl_if_mark:nTF {#6}
516       {
517         \etl_act_switch:nnn
518         \_etl_act_unexpanded_normal:nN
519         \_etl_act_unexpanded_space:n
520         \_etl_act_unexpanded_group:nn
521         \etl_act_status:n { {} {} {} {} {} #6 }
522       }
523       { \etl_act_status:n { {#3} {#3} {} {#5} #6 } }
524     }
525     { \etl_act_status:n { {#2} {#3} { #4 #7 } {#5} #6 } }
526   }
527   { \_etl_replace_put_back:nnnN { #4 #7 } {#3} {#5} #6 }
528 }
529 \exp_args:Nno
530 \use:n { \cs_new:Npn \_etl_replace_normal_false:nnnNN #1#2#3#4#5 }
531 { \_etl_replace_put_back:nnnN { #2 #5 } {#1} {#3} {#4} }
532 \cs_new:Npn \_etl_replace_space:n #1 { \_etl_replace_space:nnnnN #1 }
533 \exp_args:Nno \use:n { \cs_new:Npn \_etl_replace_space:nnnnN #1 }
534 {
535   \_etl_if_head_is_space:nTF {#1}
536   {
537     \exp_after:wN \_etl_replace_space_aux:nnnnN \exp_after:wN
538     { \_etl_rm_space:w #1 }
539   }
540   { \_etl_replace_space_false:nnnN }
541 }

```

Again, to keep track, #1 is the remainder of the pattern, #2 is the full pattern, #3 the delayed tokens, #4 the replacement text, #5 the marker for the once function.

```

542 \exp_args:Nno \use:n { \cs_new:Npn \_etl_replace_space_aux:nnnnN #1#2#3#4#5 }
543 {
544   \_etl_if_empty:nTF {#1}
545   {
546     \_etl_unexpanded:w {#4}
547     \_etl_if_mark:nTF {#5}
548     {
549       \etl_act_switch:nnn

```

```

550         \_etl_act_unexpanded_normal:nN
551         \_etl_act_unexpanded_space:n
552         \_etl_act_unexpanded_group:nn
553         \etl_act_status:n { {} {} {} {} #5 }
554     }
555     { \etl_act_status:n { {#2} {#2} {} {#4} #5 } }
556 }
557 { \etl_act_status:n { {#1} {#2} { #3 ~ } {#4} #5 } }
558 }
559 \exp_args:Nno \use:n { \cs_new:Npn \_etl_replace_space_false:nnnN #1#2#3#4 }
560 { \_etl_replace_put_back:nnnN { #2 ~ } {#1} {#3} {#4} }
561 \cs_new:Npn \_etl_replace_group:nn #1 { \_etl_replace_group:nnnnNn #1 }
562 \exp_args:Nno \use:n { \cs_new:Npn \_etl_replace_group:nnnnNn #1 }
563 {
564     \_etl_if_head_is_group:nTF {#1}
565     {
566         \exp_after:wN \_etl_replace_group:nnnnNn
567         \_etl_expanded:w { \_etl_split_first:w #1 }
568     }
569     { \_etl_replace_group_false:nnnNn }
570 }

```

And again, #1 the next group of the pattern, #2 the remainder of the pattern, #3 the full pattern, #4 the delayed stuff, #5 the replacement text, #6 the marker for the once function, #7 the next group in the input.

```

571 \exp_args:Nno \use:n { \cs_new:Npn \_etl_replace_group:nnnnNn #1#2#3#4#5#6#7 }
572 {
573     \etl_if_eq:nnTF {#1} {#7}
574     {
575         \_etl_if_empty:nTF {#2}
576         {
577             \_etl_unexpanded:w {#5}
578             \_etl_if_mark:nTF {#6}
579             {
580                 \etl_act_switch:nnn
581                 \_etl_act_unexpanded_normal:nN
582                 \_etl_act_unexpanded_space:n
583                 \_etl_act_unexpanded_group:nn
584                 \etl_act_status:n { {} {} {} {} #6 }
585             }
586             { \etl_act_status:n { {#3} {#3} {} {#5} #6 } }
587         }
588         { \etl_act_status:n { {#2} {#3} { #4 {#7} } {#5} #6 } }
589     }
590     { \_etl_replace_put_back:nnnN { #4 {#7} } {#3} {#5} #6 }
591 }
592 \exp_args:Nno \use:n { \cs_new:Npn \_etl_replace_group_false:nnnNn #1#2#3#4#5 }
593 { \_etl_replace_put_back:nnnN { #2 {#5} } {#1} {#3} {#4} }
594 \cs_new:Npn \_etl_replace_final:nn #1 { \_etl_replace_final:nnnnNn #1 }
595 \cs_new:Npn \_etl_replace_final:nnnnNn #1#2#3#4#5#6 { \_etl_unexpanded:w { #6#3 } }

```

(End definition for `\etl_replace_all:nnn` and others. This function is documented on page 5.)

```

\etl_replace_all_deep:nnn
\_etl_replace_group_deep:nn
  \_etl_replace_group_deep:nnnnNn
    \_etl_replace_group_deep:nnnnNn
      \_etl_replace_group_deep_false:nnnNn

```

The deep variant works again pretty much the same as the all variant, except that it searches groups recursively.

```

596 \exp_args:Nno \use:n { \cs_new:Npn \etl_replace_all_deep:nnn #1#2#3 }
597 {
598   \etl_act:nnnnnn
599   \__etl_replace_normal:nN
600   \__etl_replace_space:n
601   \__etl_replace_group_deep:nn
602   \__etl_replace_final:nn
603   { {#2} {#2} {} {#3} \scan_stop: }
604   {#1}
605 }
606 \cs_new:Npn \__etl_replace_group_deep:nn #1
607 { \__etl_replace_group_deep:nnnnNn #1 }
608 \exp_args:Nno \use:n { \cs_new:Npn \__etl_replace_group_deep:nnnnNn #1 }
609 {
610   \__etl_if_head_is_group:nTF {#1}
611   {
612     \exp_after:wN \__etl_replace_group_deep:nnnnNn
613     \__etl_expanded:w { \__etl_split_first:w #1 }
614   }
615   { \__etl_replace_group_deep_false:nnnNn }
616 }
617 \exp_args:Nno
618 \use:n { \cs_new:Npn \__etl_replace_group_deep:nnnnNn #1#2#3#4#5#6#7 }
619 {
620   \etl_if_eq:nnTF {#1} {#7}
621   {
622     \__etl_if_empty:nTF {#2}
623     {
624       \__etl_unexpanded:w {#5}
625       \etl_act_status:n { {#3} {#3} {} {#5} #6 }
626     }
627     { \etl_act_status:n { {#2} {#3} { #4 {#7} } {#5} #6 } }
628   }
629   {
630     \__etl_if_empty:nTF {#4}
631     {
632       { \etl_replace_all_deep:nnn {#7} {#3} {#5} }
633       \etl_act_status:n { {#3} {#3} {} {#5} #6 }
634     }
635     { \__etl_replace_put_back:nnnN { #4 {#7} } {#3} {#5} #6 }
636   }
637 }
638 \exp_args:Nno
639 \use:n { \cs_new:Npn \__etl_replace_group_deep_false:nnnNn #1#2#3#4#5 }
640 {
641   \__etl_if_empty:nTF {#2}
642   {
643     { \etl_replace_all_deep:nnn {#5} {#1} {#3} }
644     \etl_act_status:n { {#1} {#1} {} {#3} #4 }
645   }
646   { \__etl_replace_put_back:nnnN { #2 {#5} } {#1} {#3} #4 }
647 }

```

(End definition for `\etl_replace_all_deep:nnn` and others. This function is documented on page 6.)

`\etl_replace_once:nnn` And this is the same as the `all` variant except that we now use the `\s__etl_mark` marker inside the status.

```

648 \exp_args:Nno \use:n { \cs_new:Npn \etl_replace_once:nnn #1#2#3 }
649 {
650   \etl_act:nnnnnn
651   \__etl_replace_normal:nN
652   \__etl_replace_space:n
653   \__etl_replace_group:nn
654   \__etl_replace_final:nn
655   { {#2} {#2} {} {#3} \s__etl_mark }
656   {#1}
657 }

```

(End definition for `\etl_replace_once:nnn`. This function is documented on page 5.)

`\etl_new_if_in:Nnn` These tests work essentially in the same way as `\tl_if_in:nnTF`, but instead they use a predefined internal macro so that no definition at use time is necessary.

`__etl_new_if_in:NNnn`

```

658 \exp_args:Nno \use:n { \cs_new_protected:Npn \etl_new_if_in:Nnn #1#2 }
659 {
660   \exp_args:Nc \__etl_new_if_in:NNnn
661   { \__etl_user_function ~ \cs_to_str:N #1 ~ \tl_to_str:n {#2} :w }
662   #1 {#2}
663 }
664 \cs_new_protected:Npn \__etl_new_if_in:NNnn #1#2#3#4
665 {
666   \scan_stop:
667   \if_false: { \fi:
668     \cs_new:Npn #1 ##1 #3 {}
669     \prg_new_conditional:Npnn #2 ##1 {#4}
670     {
671       \if:w
672         \scan_stop:
673         \__etl_detokenize:w \exp_after:wN { #1 ##1 {}{} } #3 }
674       \scan_stop:
675       \__etl_fi_turn_false:w
676       \fi:
677       \if_true:
678         \prg_return_true:
679       \else:
680         \prg_return_false:
681       \fi:
682     }
683   \if_false: } \fi:
684 }

```

(End definition for `\etl_new_if_in:Nnn` and `__etl_new_if_in:NNnn`. This function is documented on page 6.)

685 `</pkg>`

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

C

cs commands:

\cs_if_exist:NTF 6
 \cs_new:Npn 17, 19,
 20, 21, 26, 27, 28, 29, 35, 41, 42, 44,
 46, 55, 64, 74, 82, 84, 86, 90, 96, 99,
 107, 113, 122, 123, 131, 132, 137,
 138, 140, 142, 147, 154, 156, 158,
 160, 162, 164, 166, 167, 168, 169,
 171, 172, 174, 176, 178, 180, 182,
 183, 184, 186, 188, 190, 219, 237,
 255, 266, 272, 278, 287, 293, 299,
 319, 320, 333, 342, 343, 356, 357,
 367, 376, 395, 396, 406, 416, 422,
 432, 438, 448, 450, 463, 473, 487,
 492, 497, 498, 508, 530, 532, 533,
 542, 559, 561, 562, 571, 592, 594,
 595, 596, 606, 608, 618, 639, 648, 668
 \cs_new_eq:NN 12, 13, 14
 \cs_new_protected:Npn 658, 664
 \cs_set:Npn 88
 \cs_to_str:N 661

E

else commands:

\else: . 201, 215, 233, 251, 315, 391, 679

etl commands:

\etl_act:nnnnn 2, 64
 \etl_act:nnnnnn
 ... 2, 64, 424, 440, 452, 465, 598, 650
 \etl_act:nnnnnnn 2, 3, 9, 64
 \etl_act_break: 3, 180
 \etl_act_break:n 3,
 180, 221, 238, 257, 264, 270, 276,
 285, 291, 322, 345, 359, 398, 411, 418
 \etl_act_break_discard: 3, 180
 \etl_act_break_post:n 3, 180
 \etl_act_break_pre:n 3, 180
 \etl_act_do_final: 3, 134, 180
 \etl_act_output:n 2, 138
 \etl_act_output_pre:n 2, 138
 \etl_act_output_rest: 3, 11, 138
 \etl_act_output_rest_pre: . 3, 11, 138
 \etl_act_put_back:n
 ... 3, 16, 171, 302, 303, 477, 490, 495
 \etl_act_status:n 3,
 169, 269, 275, 290, 329, 336, 339,

348, 353, 370, 373, 379, 409, 413,
 420, 485, 521, 523, 525, 553, 555,
 557, 584, 586, 588, 625, 627, 633, 644

\etl_act_switch:nnn
 3, 172, 517, 549, 580
 \etl_act_switch_group:n 3, 172
 \etl_act_switch_normal:n . 3, 172, 455
 \etl_act_switch_space:n 3, 172
 \etl_if_eq:nnTF
 4, 16, 239, 369, 408, 573, 620
 \etl_if_eq_p:nn 4, 239
 \etl_if_in:nn 16
 \etl_if_in:nnTF 4, 18, 299
 \etl_if_in_deep:nnTF . 4, 381, 411, 418
 \etl_if_in_deep_p:nn 4, 381
 \etl_if_in_p:nn 4, 299
 \etl_new_if_in:Nnn 6, 658
 \etl_replace_all:nnn 5, 463
 \etl_replace_all_deep:nnn ... 6, 596
 \etl_replace_once:nnn 5, 648
 \etl_token_if_eq:NNTF
 2, 4, 190, 221, 268, 335, 434, 510

\etl_token_if_eq_p:NN 4, 190
 \etl_token_if_in:nNTF 4, 205
 \etl_token_if_in_deep:nNTF 4, 223, 238
 \etl_token_if_in_deep_p:nN ... 4, 223
 \etl_token_if_in_p:nN 4, 205
 \etl_token_replace_all:nNn ... 5, 422
 \etl_token_replace_all_deep:nNn
 5, 438
 \etl_token_replace_once:nNn 5, 19, 450

etl internal commands:

__etl_act:nnnnnn
 16, 64, 208, 226, 242, 308, 384
 __etl_act:w
 10, 12, 69, 78, 87, 131, 135, 171
 __etl_act_group:w 118, 125, 132
 __etl_act_if_end:w 132
 __etl_act_if_space:w 87
 __etl_act_just_result:nn
 64, 210, 228, 310, 386
 __etl_act_normal:w 119, 125, 131, 132
 __etl_act_output_group:nn 138

_etl_act_output_group_pre:nn	138	_etl_if_in_group_false:nnn	365, 376
_etl_act_output_normal:nN	138	_etl_if_in_normal:nN	16, 299, 385
_etl_act_output_normal_pre:nN	138	_etl_if_in_normal:nnnN	299
_etl_act_output_space:n	138	_etl_if_in_normal:NnnnN	299
_etl_act_output_space_pre:n	138	_etl_if_in_put_back:n	16, 299, 412, 419
_etl_act_result:n	1, 9, 70, 79, 138, 139, 140, 141, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 180, 182, 183, 184, 186, 188	_etl_if_in_space:n	16, 299, 385
_etl_act_space:w	87	_etl_if_in_space:nnn	299
_etl_act_unexpanded_group:nn	138, 427, 458, 520, 552, 583	_etl_if_mark:nTF	17, 515, 547, 578
_etl_act_unexpanded_normal:nN	138, 455, 518, 550, 581	_etl_if_mark:w	17
_etl_act_unexpanded_space:n	138, 426, 442, 457, 519, 551, 582	_etl_if_mark_true:w	17
_etl_detokenize:w	12, 673	_etl_new_if_in:Nnn	658
_etl_expanded:w	15, 12, 66, 76, 261, 283, 326, 363, 402, 483, 503, 567, 613	_etl_replace_final:nn	463, 602, 654
_etl_fi_turn_false:w	26, 675	_etl_replace_final:nnnnNn	463
_etl_if_empty:nTF	29, 257, 297, 322, 345, 359, 398, 512, 544, 575, 622, 630, 641	_etl_replace_group:nn	463, 653
_etl_if_empty:w	29	_etl_replace_group:nnnnNn	463
_etl_if_empty_true:w	29	_etl_replace_group:nnnnnNn	463
_etl_if_empty_true_TF:w	29	_etl_replace_group_deep:nn	596
_etl_if_eq_final:nn	239	_etl_replace_group_deep:nnnnNn	596
_etl_if_eq_group:nn	239	_etl_replace_group_deep:nnnnnNn	596
_etl_if_eq_group:nnn	239	_etl_replace_group_deep_-false:nnnNn	596
_etl_if_eq_normal:nN	239	_etl_replace_group_false:nnnNn	463
_etl_if_eq_normal:NnN	239	_etl_replace_normal:nN	463, 599, 651
_etl_if_eq_space:n	239	_etl_replace_normal:nnnnNn	463
_etl_if_head_is_group:nTF	46, 104, 109, 118, 125, 280, 360, 399, 480, 564, 610	_etl_replace_normal:NnnnnNn	463
_etl_if_head_is_N_type:nTF	87, 258, 323, 500	_etl_replace_normal_false:nnnNn	463
_etl_if_head_is_N_type_false:w	87	_etl_replace_put_back:nnnN	463, 635, 646
_etl_if_head_is_space:nTF	87, 274, 301, 346, 475, 535	_etl_replace_put_back_group:nn	463
_etl_if_head_is_space_true:w	87	_etl_replace_put_back_normal:Nn	463
_etl_if_in_group:nn	16, 299	_etl_replace_space:n	463, 600, 652
_etl_if_in_group:nnnn	299	_etl_replace_space:nnnnN	463
_etl_if_in_group:nnnnn	299	_etl_replace_space_aux:nnnnN	463
_etl_if_in_group_deep:nn	381	_etl_replace_space_false:nnnN	463
_etl_if_in_group_deep:nnnn	381	_etl_rm_space:w	28, 275, 302, 349, 477, 538
_etl_if_in_group_deep:nnnnn	381	_etl_split_first:w	16, 21, 261, 283, 326, 363, 402, 483, 503, 567, 613
_etl_if_in_group_deep_false:nnn	381	_etl_tmp:n	88, 129
		_etl_token_if_in:NN	209, 219, 227
		_etl_token_if_in:NnN	205
		_etl_token_if_in_deep:Nn	223
		_etl_token_replace:NnnN	422, 441, 454
		_etl_token_replace_deep:Nnn	438

`__etl_turn_true:w` 26, 198
`__etl_unexpanded:w`
..... 9, 11, 18, 12, 23, 66, 86,
168, 182, 185, 187, 189, 296, 435,
436, 489, 494, 514, 546, 577, 595, 624
exp commands:
`\exp_after:wN` 24, 48, 50, 51,
57, 59, 60, 260, 275, 282, 295, 302,
303, 325, 348, 349, 362, 401, 449,
477, 481, 482, 502, 537, 566, 612, 673
`\exp_args:Nc` 660
`\exp_args:Nno`
..... 82, 84, 190, 195, 205, 219,
223, 237, 239, 255, 266, 272, 278,
287, 293, 299, 305, 320, 333, 343,
357, 367, 376, 381, 396, 406, 416,
422, 432, 438, 448, 450, 463, 473,
498, 507, 529, 533, 542, 559, 562,
571, 592, 596, 608, 617, 638, 648, 658
`\exp_not:N` 166
`\exp_not:n` 2, 5, 6

F
fi commands:
`\fi` 24, 27, 203, 217,
235, 253, 317, 393, 667, 676, 681, 683

G
group commands:
`\group_begin:` 87
`\group_end:` 130

I
if commands:
`\if:w` 8, 671
`\if_false:` 13, 14, 16, 24,
26, 27, 199, 212, 230, 257, 264, 270,
276, 285, 291, 297, 312, 388, 667, 683
`\if_meaning:w` 4
`\if_true:` .. 14, 16, 26, 27, 221, 238,
297, 322, 345, 359, 398, 411, 418, 677

M
msg commands:
`\msg_fatal:nn` 10
`\msg_new:nnn` 8

P
prg commands:
`\prg_new_conditional:Npnn` 6,
13, 196, 206, 224, 240, 306, 382, 669
`\prg_return_false:`
..... 202, 216, 234, 252, 316, 392, 680

`\prg_return_true:`
..... 200, 214, 232, 250, 314, 390, 678
`\ProvidesExplPackage` 3

S
scan commands:
`\scan_new:N` 15, 16
`\scan_stop:` 470, 603, 666, 672, 674
scan internal commands:
`\s__etl_mark` 7, 20, 24, 15, 18, 19, 20, 655
`\s__etl_stop` 1, 6, 8–
12, 15, 32, 33, 38, 39, 41, 42, 44, 69,
78, 93, 94, 97, 102, 103, 108, 113,
116, 117, 120, 122, 124, 134, 137,
142, 144, 147, 149, 169, 170, 172,
173, 174, 175, 176, 177, 178, 179, 180
str commands:
`\str_if_eq:nnTF` 4, 192, 198

T
tex commands:
`\tex_detokenize:D` 14
`\tex_expanded:D` 6, 12
`\tex_unexpanded:D` 13
tl commands:
`\tl_if_head_is_group:nTF` 8
`\tl_if_in:nnTF` 4, 24
`\tl_to_str:n` 661
tl internal commands:
`__tl_act:NNNn` 2, 9
token commands:
`\token_if_eq_meaning:NNTF` 13, 192, 198
`\token_to_str:N` 50, 51, 59, 60

U
use commands:
`\use:n` 28, 82, 84, 190, 196, 206, 219,
223, 237, 240, 255, 266, 272, 278,
287, 293, 299, 306, 320, 333, 343,
357, 367, 376, 382, 396, 406, 416,
422, 432, 438, 448, 450, 463, 473,
498, 508, 530, 533, 542, 559, 562,
571, 592, 596, 608, 618, 639, 648, 658
`\use_i:nn` 105, 110, 134
`\use_ii:nn` 18, 20, 39, 44, 53, 94, 97, 193
`\use_ii:nnn` 192
`\use_iii:nnn` 60, 104, 109
`\use_iii:nnnn` 51
`\use_none:n`
. 33, 42, 48, 57, 62, 209, 227, 297, 303
`\use_none:nn` 209, 428, 444, 459