

The L^AT_EX3 Sources

The L^AT_EX3 Project*

Released 2020-05-14

Abstract

This is the reference documentation for the `expl3` programming environment. The `expl3` modules set up an experimental naming scheme for L^AT_EX commands, which allow the L^AT_EX programmer to systematically name functions and variables, and specify the argument types of functions.

The T_EX and ϵ -T_EX primitives are all given a new name according to these conventions. However, in the main direct use of the primitives is not required or encouraged: the `expl3` modules define an independent low-level L^AT_EX3 programming language.

At present, the `expl3` modules are designed to be loaded on top of L^AT_EX 2 ϵ . In time, a L^AT_EX3 format will be produced based on this code. This allows the code to be used in L^AT_EX 2 ϵ packages *now* while a stand-alone L^AT_EX3 is developed.

While `expl3` is still experimental, the bundle is now regarded as broadly stable. The syntax conventions and functions provided are now ready for wider use. There may still be changes to some functions, but these will be minor when compared to the scope of `expl3`.

New modules will be added to the distributed version of `expl3` as they reach maturity.

*E-mail: latex-team@latex-project.org

Contents

I	Introduction to <code>expl3</code> and this document	1
1	Naming functions and variables	1
1.1	Terminological inexactitude	3
2	Documentation conventions	4
3	Formal language conventions which apply generally	5
4	<code>TeX</code> concepts not supported by <code>LaTeX3</code>	6
II	The <code>l3bootstrap</code> package: Bootstrap code	7
1	Using the <code>LaTeX3</code> modules	7
III	The <code>l3names</code> package: Namespace for primitives	8
1	Setting up the <code>LaTeX3</code> programming language	8
IV	The <code>l3basics</code> package: Basic definitions	9
1	No operation functions	9
2	Grouping material	9
3	Control sequences and functions	10
3.1	Defining functions	10
3.2	Defining new functions using parameter text	11
3.3	Defining new functions using the signature	12
3.4	Copying control sequences	15
3.5	Deleting control sequences	15
3.6	Showing control sequences	15
3.7	Converting to and from control sequences	16
4	Analysing control sequences	17
5	Using or removing tokens and arguments	18
5.1	Selecting tokens from delimited arguments	20
6	Predicates and conditionals	21
6.1	Tests on control sequences	22
6.2	Primitive conditionals	22
7	Starting a paragraph	24
7.1	Debugging support	24

V	The <code>l3expan</code> package: Argument expansion	25
1	Defining new variants	25
2	Methods for defining variants	26
3	Introducing the variants	27
4	Manipulating the first argument	29
5	Manipulating two arguments	31
6	Manipulating three arguments	32
7	Unbraced expansion	33
8	Preventing expansion	33
9	Controlled expansion	35
10	Internal functions	37
VI	The <code>l3quark</code> package: Quarks	38
1	Quarks	38
2	Defining quarks	38
3	Quark tests	39
4	Recursion	39
5	An example of recursion with quarks	40
6	Scan marks	41
VII	The <code>l3tl</code> package: Token lists	43
1	Creating and initialising token list variables	43
2	Adding data to token list variables	44
3	Modifying token list variables	45
4	Reassigning token list category codes	45
5	Token list conditionals	46
6	Mapping to token lists	48
7	Using token lists	51

8	Working with the content of token lists	51
9	The first token from a token list	53
10	Using a single item	56
11	Viewing token lists	58
12	Constant token lists	58
13	Scratch token lists	59
VIII	The <code>l3str</code> package: Strings	60
1	Building strings	60
2	Adding data to string variables	61
3	Modifying string variables	62
4	String conditionals	63
5	Mapping to strings	64
6	Working with the content of strings	66
7	String manipulation	69
8	Viewing strings	70
9	Constant token lists	71
10	Scratch strings	71
IX	The <code>l3str-convert</code> package: string encoding conversions	72
1	Encoding and escaping schemes	72
2	Conversion functions	72
3	Creating 8-bit mappings	74
4	Possibilities, and things to do	74
X	The <code>l3seq</code> package: Sequences and stacks	75
1	Creating and initialising sequences	75
2	Appending data to sequences	76
3	Recovering items from sequences	76

4	Recovering values from sequences with branching	78
5	Modifying sequences	79
6	Sequence conditionals	80
7	Mapping to sequences	80
8	Using the content of sequences directly	82
9	Sequences as stacks	83
10	Sequences as sets	84
11	Constant and scratch sequences	85
12	Viewing sequences	86
XI	The l3int package: Integers	87
1	Integer expressions	88
2	Creating and initialising integers	89
3	Setting and incrementing integers	90
4	Using integers	91
5	Integer expression conditionals	91
6	Integer expression loops	93
7	Integer step functions	95
8	Formatting integers	96
9	Converting from other formats to integers	97
10	Random integers	98
11	Viewing integers	99
12	Constant integers	99
13	Scratch integers	99
	13.1 Direct number expansion	100
14	Primitive conditionals	100
XII	The l3flag package: Expandable flags	102
1	Setting up flags	102

2	Expandable flag commands	103
XIII	The <code>l3prg</code> package: Control structures	104
1	Defining a set of conditional functions	104
2	The boolean data type	106
3	Boolean expressions	108
4	Logical loops	110
5	Producing multiple copies	111
6	Detecting $\mathrm{T}_{\mathrm{E}}\mathrm{X}$'s mode	111
7	Primitive conditionals	112
8	Nestable recursions and mappings	112
	8.1 Simple mappings	112
9	Internal programming functions	113
XIV	The <code>l3sys</code> package: System/runtime functions	114
1	The name of the job	114
2	Date and time	114
3	Engine	114
4	Output format	115
5	Platform	115
6	Random numbers	115
7	Access to the shell	116
	7.1 Loading configuration data	117
	7.2 Final settings	117
XV	The <code>l3clist</code> package: Comma separated lists	118
1	Creating and initialising comma lists	118
2	Adding data to comma lists	120
3	Modifying comma lists	120
4	Comma list conditionals	122

5	Mapping to comma lists	122
6	Using the content of comma lists directly	124
7	Comma lists as stacks	125
8	Using a single item	126
9	Viewing comma lists	126
10	Constant and scratch comma lists	127
XVI	The l3token package: Token manipulation	128
1	Creating character tokens	128
2	Manipulating and interrogating character tokens	130
3	Generic tokens	133
4	Converting tokens	133
5	Token conditionals	134
6	Peeking ahead at the next token	137
7	Description of all possible tokens	140
XVII	The l3prop package: Property lists	143
1	Creating and initialising property lists	143
2	Adding entries to property lists	144
3	Recovering values from property lists	144
4	Modifying property lists	145
5	Property list conditionals	145
6	Recovering values from property lists with branching	146
7	Mapping to property lists	147
8	Viewing property lists	148
9	Scratch property lists	148
10	Constants	149
XVIII	The l3msg package: Messages	150

1	Creating new messages	150
2	Contextual information for messages	151
3	Issuing messages	152
4	Redirecting messages	154
XIX	The l3file package: File and I/O operations	156
1	Input–output stream management	156
1.1	Reading from files	157
1.2	Writing to files	160
1.3	Wrapping lines in output	162
1.4	Constant input–output streams, and variables	163
1.5	Primitive conditionals	163
2	File operation functions	163
XX	The l3skip package: Dimensions and skips	168
1	Creating and initialising dim variables	168
2	Setting dim variables	169
3	Utilities for dimension calculations	169
4	Dimension expression conditionals	170
5	Dimension expression loops	172
6	Dimension step functions	173
7	Using dim expressions and variables	174
8	Viewing dim variables	175
9	Constant dimensions	176
10	Scratch dimensions	176
11	Creating and initialising skip variables	176
12	Setting skip variables	177
13	Skip expression conditionals	178
14	Using skip expressions and variables	178
15	Viewing skip variables	178

16	Constant skips	179
17	Scratch skips	179
18	Inserting skips into the output	179
19	Creating and initialising muskip variables	180
20	Setting muskip variables	180
21	Using muskip expressions and variables	181
22	Viewing muskip variables	181
23	Constant muskips	182
24	Scratch muskips	182
25	Primitive conditional	182
XXI	The l3keys package: Key–value interfaces	183
1	Creating keys	184
2	Sub-dividing keys	188
3	Choice and multiple choice keys	189
4	Setting keys	191
5	Handling of unknown keys	191
6	Selective key setting	192
7	Utility functions for keys	193
8	Low-level interface for parsing key–val lists	194
XXII	The l3intarray package: fast global integer arrays	196
1	l3intarray documentation	196
1.1	Implementation notes	197
XXIII	The l3fp package: Floating points	198
1	Creating and initialising floating point variables	199
2	Setting floating point variables	200
3	Using floating points	200

4	Floating point conditionals	202
5	Floating point expression loops	203
6	Some useful constants, and scratch variables	205
7	Floating point exceptions	206
8	Viewing floating points	207
9	Floating point expressions	208
9.1	Input of floating point numbers	208
9.2	Precedence of operators	209
9.3	Operations	209
10	Disclaimer and roadmap	216
XXIV	The l3farray package: fast global floating point arrays	219
1	l3farray documentation	219
XXV	The l3sort package: Sorting functions	220
1	Controlling sorting	220
XXVI	The l3tl-analysis package: Analysing token lists	221
1	l3tl-analysis documentation	221
XXVII	The l3regex package: Regular expressions in T_EX	222
1	Syntax of regular expressions	222
2	Syntax of the replacement text	227
3	Pre-compiling regular expressions	229
4	Matching	229
5	Submatch extraction	230
6	Replacement	231
7	Constants and variables	231
8	Bugs, misfeatures, future work, and other possibilities	232
XXVIII	The l3box package: Boxes	235

1	Creating and initialising boxes	235
2	Using boxes	235
3	Measuring and setting box dimensions	236
4	Box conditionals	237
5	The last box inserted	237
6	Constant boxes	237
7	Scratch boxes	238
8	Viewing box contents	238
9	Boxes and color	238
10	Horizontal mode boxes	238
11	Vertical mode boxes	240
12	Using boxes efficiently	241
13	Affine transformations	242
14	Primitive box conditionals	245
 XXIX The <code>l3coffins</code> package: Coffin code layer		246
1	Creating and initialising coffins	246
2	Setting coffin content and poles	246
3	Coffin affine transformations	248
4	Joining and using coffins	248
5	Measuring coffins	249
6	Coffin diagnostics	249
7	Constants and variables	250
 XXX The <code>l3color-base</code> package: Color support		251
1	Color in boxes	251
 XXXI The <code>l3luatex</code> package: Lua_{TeX}-specific functions		252
1	Breaking out to Lua	252

2	Lua interfaces	253
XXXII	The <code>l3unicode</code> package: Unicode support functions	254
XXXIII	The <code>l3text</code> package: text processing	255
1	<code>l3text</code> documentation	255
1.1	Expanding text	255
1.2	Case changing	257
1.3	Removing formatting from text	258
1.4	Control variables	258
XXXIV	The <code>l3legacy</code> package: Interfaces to legacy concepts	259
XXXV	The <code>l3candidates</code> package: Experimental additions to <code>l3kernel</code>	260
1	Important notice	260
2	Additions to <code>l3box</code>	260
2.1	Viewing part of a box	260
3	Additions to <code>l3expan</code>	261
4	Additions to <code>l3fp</code>	261
5	Additions to <code>l3file</code>	261
6	Additions to <code>l3flag</code>	262
7	Additions to <code>l3intarray</code>	262
7.1	Working with contents of integer arrays	262
8	Additions to <code>l3msg</code>	263
9	Additions to <code>l3prg</code>	264
10	Additions to <code>l3prop</code>	265
11	Additions to <code>l3seq</code>	265
12	Additions to <code>l3sys</code>	267
13	Additions to <code>l3tl</code>	268
14	Additions to <code>l3token</code>	269
XXXVI	Implementation	270

1	l3bootstrap implementation	270
1.1	Format-specific code	270
1.2	The <code>\pdfstrcmp</code> primitive in \LaTeX	271
1.3	Loading support Lua code	271
1.4	Engine requirements	272
1.5	Extending allocators	274
1.6	Character data	274
1.7	The \LaTeX 3 code environment	276
2	l3names implementation	277
2.1	Deprecated functions	301
3	Internal kernel functions	313
4	Kernel backend functions	319
5	l3basics implementation	320
5.1	Renaming some \TeX primitives (again)	320
5.2	Defining some constants	322
5.3	Defining functions	323
5.4	Selecting tokens	323
5.5	Gobbling tokens from input	325
5.6	Debugging and patching later definitions	325
5.7	Conditional processing and definitions	326
5.8	Dissecting a control sequence	332
5.9	Exist or free	334
5.10	Preliminaries for new functions	336
5.11	Defining new functions	337
5.12	Copying definitions	339
5.13	Undefining functions	339
5.14	Generating parameter text from argument count	340
5.15	Defining functions from a given number of arguments	341
5.16	Using the signature to define functions	342
5.17	Checking control sequence equality	344
5.18	Diagnostic functions	344
5.19	Decomposing a macro definition	346
5.20	Doing nothing functions	346
5.21	Breaking out of mapping functions	347
5.22	Starting a paragraph	347
6	l3expan implementation	348
6.1	General expansion	348
6.2	Hand-tuned definitions	351
6.3	Last-unbraced versions	355
6.4	Preventing expansion	357
6.5	Controlled expansion	358
6.6	Emulating \e -type expansion	358
6.7	Defining function variants	365
6.8	Definitions with the automated technique	376

7	l3quark implementation	377
7.1	Quarks	377
7.2	Scan marks	386
8	l3tl implementation	387
8.1	Functions	387
8.2	Constant token lists	388
8.3	Adding to token list variables	389
8.4	Internal quarks and quark-query functions	390
8.5	Reassigning token list category codes	391
8.6	Modifying token list variables	394
8.7	Token list conditionals	397
8.8	Mapping to token lists	402
8.9	Using token lists	404
8.10	Working with the contents of token lists	405
8.11	Token by token changes	407
8.12	The first token from a token list	409
8.13	Using a single item	414
8.14	Viewing token lists	417
8.15	Internal scan marks	418
8.16	Scratch token lists	418
9	l3str implementation	419
9.1	Internal auxiliaries	419
9.2	Creating and setting string variables	419
9.3	Modifying string variables	420
9.4	String comparisons	422
9.5	Mapping to strings	425
9.6	Accessing specific characters in a string	426
9.7	Counting characters	431
9.8	The first character in a string	432
9.9	String manipulation	434
9.10	Viewing strings	435
10	l3str-convert implementation	435
10.1	Helpers	435
10.1.1	Variables and constants	435
10.2	String conditionals	437
10.3	Conversions	438
10.3.1	Producing one byte or character	438
10.3.2	Mapping functions for conversions	439
10.3.3	Error-reporting during conversion	440
10.3.4	Framework for conversions	441
10.3.5	Byte unescape and escape	445
10.3.6	Native strings	446
10.3.7	clist	447
10.3.8	8-bit encodings	448
10.4	Messages	450
10.5	Escaping definitions	451
10.5.1	Unescape methods	451

10.5.2	Escape methods	456
10.6	Encoding definitions	458
10.6.1	UTF-8 support	458
10.6.2	UTF-16 support	463
10.6.3	UTF-32 support	468
10.6.4	ISO 8859 support	471
11	l3seq implementation	487
11.1	Allocation and initialisation	488
11.2	Appending data to either end	491
11.3	Modifying sequences	492
11.4	Sequence conditionals	494
11.5	Recovering data from sequences	496
11.6	Mapping to sequences	500
11.7	Using sequences	502
11.8	Sequence stacks	503
11.9	Viewing sequences	504
11.10	Scratch sequences	505
12	l3int implementation	505
12.1	Integer expressions	506
12.2	Creating and initialising integers	508
12.3	Setting and incrementing integers	510
12.4	Using integers	511
12.5	Integer expression conditionals	511
12.6	Integer expression loops	515
12.7	Integer step functions	516
12.8	Formatting integers	518
12.9	Converting from other formats to integers	523
12.10	Viewing integer	526
12.11	Random integers	526
12.12	Constant integers	527
12.13	Scratch integers	527
12.14	Integers for earlier modules	527
13	l3flag implementation	528
13.1	Non-expandable flag commands	528
13.2	Expandable flag commands	529
14	l3prg implementation	530
14.1	Primitive conditionals	530
14.2	Defining a set of conditional functions	530
14.3	The boolean data type	530
14.4	Internal auxiliaries	531
14.5	Boolean expressions	533
14.6	Logical loops	537
14.7	Producing multiple copies	538
14.8	Detecting T _E X's mode	540
14.9	Internal programming functions	541

15	l3sys implementation	541
15.1	Kernel code	541
15.1.1	Detecting the engine	541
15.1.2	Randomness	542
15.1.3	Platform	542
15.1.4	Configurations	543
15.1.5	Access to the shell	544
15.2	Dynamic (every job) code	546
15.2.1	The name of the job	546
15.2.2	Time and date	547
15.2.3	Random numbers	547
15.2.4	Access to the shell	548
15.2.5	Held over from l3file	549
15.3	Last-minute code	549
15.3.1	Detecting the output	549
15.3.2	Configurations	550
16	l3clist implementation	551
16.1	Removing spaces around items	552
16.2	Allocation and initialisation	553
16.3	Adding data to comma lists	555
16.4	Comma lists as stacks	556
16.5	Modifying comma lists	558
16.6	Comma list conditionals	561
16.7	Mapping to comma lists	562
16.8	Using comma lists	565
16.9	Using a single item	566
16.10	Viewing comma lists	568
16.11	Scratch comma lists	568
17	l3token implementation	569
17.1	Internal auxiliaries	569
17.2	Manipulating and interrogating character tokens	569
17.3	Creating character tokens	571
17.4	Generic tokens	580
17.5	Token conditionals	581
17.6	Peeking ahead at the next token	588
18	l3prop implementation	594
18.1	Internal auxiliaries	596
18.2	Allocation and initialisation	596
18.3	Accessing data in property lists	598
18.4	Property list conditionals	603
18.5	Recovering values from property lists with branching	604
18.6	Mapping to property lists	604
18.7	Viewing property lists	606

19	l3msg implementation	606
19.1	Internal auxiliaries	607
19.2	Creating messages	607
19.3	Messages: support functions and text	608
19.4	Showing messages: low level mechanism	609
19.5	Displaying messages	611
19.6	Kernel-specific functions	620
19.7	Expandable errors	628
20	l3file implementation	629
20.1	Input operations	630
20.1.1	Variables and constants	630
20.1.2	Stream management	631
20.1.3	Reading input	633
20.2	Output operations	636
20.2.1	Variables and constants	636
20.2.2	Internal auxiliaries	637
20.3	Stream management	638
20.3.1	Deferred writing	639
20.3.2	Immediate writing	640
20.3.3	Special characters for writing	640
20.3.4	Hard-wrapping lines to a character count	641
20.4	File operations	650
20.4.1	Internal auxiliaries	652
20.5	GetIfInfo	668
20.6	Messages	669
20.7	Functions delayed from earlier modules	670
21	l3skip implementation	671
21.1	Length primitives renamed	671
21.2	Internal auxiliaries	671
21.3	Creating and initialising <code>dim</code> variables	671
21.4	Setting <code>dim</code> variables	672
21.5	Utilities for dimension calculations	673
21.6	Dimension expression conditionals	674
21.7	Dimension expression loops	676
21.8	Dimension step functions	677
21.9	Using <code>dim</code> expressions and variables	679
21.10	Viewing <code>dim</code> variables	680
21.11	Constant dimensions	681
21.12	Scratch dimensions	681
21.13	Creating and initialising <code>skip</code> variables	681
21.14	Setting <code>skip</code> variables	682
21.15	Skip expression conditionals	683
21.16	Using <code>skip</code> expressions and variables	684
21.17	Inserting skips into the output	684
21.18	Viewing <code>skip</code> variables	684
21.19	Constant skips	685
21.20	Scratch skips	685
21.21	Creating and initialising <code>muskip</code> variables	685

21.22	Setting muskip variables	686
21.23	Using muskip expressions and variables	687
21.24	Viewing muskip variables	687
21.25	Constant muskips	687
21.26	Scratch muskips	687
22	l3keys Implementation	688
22.1	Low-level interface	688
22.2	Constants and variables	694
22.2.1	Internal auxiliaries	696
22.3	The key defining mechanism	697
22.4	Turning properties into actions	699
22.5	Creating key properties	705
22.6	Setting keys	709
22.7	Utilities	718
22.8	Messages	720
23	l3intarray implementation	721
23.1	Allocating arrays	721
23.2	Array items	722
23.3	Working with contents of integer arrays	724
23.4	Random arrays	726
24	l3fp implementation	727
25	l3fp-aux implementation	727
25.1	Access to primitives	727
25.2	Internal representation	728
25.3	Using arguments and semicolons	729
25.4	Constants, and structure of floating points	730
25.5	Overflow, underflow, and exact zero	732
25.6	Expanding after a floating point number	732
25.7	Other floating point types	734
25.8	Packing digits	737
25.9	Decimate (dividing by a power of 10)	739
25.10	Functions for use within primitive conditional branches	741
25.11	Integer floating points	743
25.12	Small integer floating points	743
25.13	Fast string comparison	744
25.14	Name of a function from its l3fp-parse name	744
25.15	Messages	745
26	l3fp-traps Implementation	745
26.1	Flags	745
26.2	Traps	745
26.3	Errors	749
26.4	Messages	749
27	l3fp-round implementation	750
27.1	Rounding tools	750
27.2	The round function	754

28	l3fp-parse implementation	758
28.1	Work plan	758
28.1.1	Storing results	759
28.1.2	Precedence and infix operators	760
28.1.3	Prefix operators, parentheses, and functions	763
28.1.4	Numbers and reading tokens one by one	764
28.2	Main auxiliary functions	766
28.3	Helpers	766
28.4	Parsing one number	767
28.4.1	Numbers: trimming leading zeros	774
28.4.2	Number: small significand	775
28.4.3	Number: large significand	777
28.4.4	Number: beyond 16 digits, rounding	779
28.4.5	Number: finding the exponent	781
28.5	Constants, functions and prefix operators	785
28.5.1	Prefix operators	785
28.5.2	Constants	788
28.5.3	Functions	789
28.6	Main functions	789
28.7	Infix operators	792
28.7.1	Closing parentheses and commas	793
28.7.2	Usual infix operators	795
28.7.3	Juxtaposition	796
28.7.4	Multi-character cases	796
28.7.5	Ternary operator	797
28.7.6	Comparisons	797
28.8	Tools for functions	799
28.9	Messages	801
29	l3fp-assign implementation	802
29.1	Assigning values	802
29.2	Updating values	803
29.3	Showing values	804
29.4	Some useful constants and scratch variables	804
30	l3fp-logic Implementation	805
30.1	Syntax of internal functions	805
30.2	Tests	805
30.3	Comparison	806
30.4	Floating point expression loops	809
30.5	Extrema	812
30.6	Boolean operations	814
30.7	Ternary operator	815

31	l3fp-basics Implementation	816
31.1	Addition and subtraction	816
31.1.1	Sign, exponent, and special numbers	817
31.1.2	Absolute addition	819
31.1.3	Absolute subtraction	821
31.2	Multiplication	825
31.2.1	Signs, and special numbers	825
31.2.2	Absolute multiplication	826
31.3	Division	829
31.3.1	Signs, and special numbers	829
31.3.2	Work plan	830
31.3.3	Implementing the significand division	832
31.4	Square root	837
31.5	About the sign and exponent	844
31.6	Operations on tuples	845
32	l3fp-extended implementation	846
32.1	Description of fixed point numbers	847
32.2	Helpers for numbers with extended precision	847
32.3	Multiplying a fixed point number by a short one	848
32.4	Dividing a fixed point number by a small integer	849
32.5	Adding and subtracting fixed points	850
32.6	Multiplying fixed points	851
32.7	Combining product and sum of fixed points	852
32.8	Extended-precision floating point numbers	854
32.9	Dividing extended-precision numbers	857
32.10	Inverse square root of extended precision numbers	860
32.11	Converting from fixed point to floating point	862
33	l3fp-expo implementation	864
33.1	Logarithm	864
33.1.1	Work plan	864
33.1.2	Some constants	865
33.1.3	Sign, exponent, and special numbers	865
33.1.4	Absolute ln	865
33.2	Exponential	873
33.2.1	Sign, exponent, and special numbers	873
33.3	Power	877
33.4	Factorial	883

34	l3fp-trig Implementation	885
34.1	Direct trigonometric functions	886
34.1.1	Filtering special cases	886
34.1.2	Distinguishing small and large arguments	889
34.1.3	Small arguments	890
34.1.4	Argument reduction in degrees	890
34.1.5	Argument reduction in radians	892
34.1.6	Computing the power series	899
34.2	Inverse trigonometric functions	902
34.2.1	Arctangent and arccotangent	903
34.2.2	Arcsine and arccosine	908
34.2.3	Arccosecant and arcsecant	910
35	l3fp-convert implementation	911
35.1	Dealing with tuples	911
35.2	Trimming trailing zeros	912
35.3	Scientific notation	912
35.4	Decimal representation	913
35.5	Token list representation	915
35.6	Formatting	916
35.7	Convert to dimension or integer	917
35.8	Convert from a dimension	917
35.9	Use and eval	918
35.10	Convert an array of floating points to a comma list	919
36	l3fp-random Implementation	920
36.1	Engine support	920
36.2	Random floating point	924
36.3	Random integer	924
37	l3fparray implementation	929
37.1	Allocating arrays	929
37.2	Array items	930
38	l3sort implementation	933
38.1	Variables	933
38.2	Finding available \toks registers	935
38.3	Protected user commands	937
38.4	Merge sort	939
38.5	Expandable sorting	942
38.6	Messages	947

39	l3tl-analysis implementation	948
39.1	Internal functions	948
39.2	Internal format	948
39.3	Variables and helper functions	949
39.4	Plan of attack	951
39.5	Disabling active characters	952
39.6	First pass	952
39.7	Second pass	957
39.8	Mapping through the analysis	960
39.9	Showing the results	961
39.10	Messages	963
40	l3regex implementation	964
40.1	Plan of attack	964
40.2	Helpers	965
40.2.1	Constants and variables	967
40.2.2	Testing characters	968
40.2.3	Internal auxiliaries	968
40.2.4	Character property tests	972
40.2.5	Simple character escape	973
40.3	Compiling	979
40.3.1	Variables used when compiling	979
40.3.2	Generic helpers used when compiling	981
40.3.3	Mode	982
40.3.4	Framework	984
40.3.5	Quantifiers	987
40.3.6	Raw characters	990
40.3.7	Character properties	991
40.3.8	Anchoring and simple assertions	992
40.3.9	Character classes	993
40.3.10	Groups and alternations	996
40.3.11	Catcodes and csnames	999
40.3.12	Raw token lists with \u	1003
40.3.13	Other	1005
40.3.14	Showing regexes	1005
40.4	Building	1009
40.4.1	Variables used while building	1009
40.4.2	Framework	1010
40.4.3	Helpers for building an NFA	1011
40.4.4	Building classes	1013
40.4.5	Building groups	1014
40.4.6	Others	1019
40.5	Matching	1020
40.5.1	Variables used when matching	1021
40.5.2	Matching: framework	1023
40.5.3	Using states of the NFA	1027
40.5.4	Actions when matching	1027
40.6	Replacement	1030
40.6.1	Variables and helpers used in replacement	1030
40.6.2	Query and brace balance	1031

40.6.3	Framework	1032
40.6.4	Submatches	1034
40.6.5	Csnames in replacement	1036
40.6.6	Characters in replacement	1037
40.6.7	An error	1041
40.7	User functions	1041
40.7.1	Variables and helpers for user functions	1043
40.7.2	Matching	1044
40.7.3	Extracting submatches	1044
40.7.4	Replacement	1048
40.7.5	Storing and showing compiled patterns	1050
40.8	Messages	1050
40.9	Code for tracing	1056
41	l3box implementation	1057
41.1	Support code	1057
41.2	Creating and initialising boxes	1057
41.3	Measuring and setting box dimensions	1058
41.4	Using boxes	1059
41.5	Box conditionals	1059
41.6	The last box inserted	1059
41.7	Constant boxes	1060
41.8	Scratch boxes	1060
41.9	Viewing box contents	1060
41.10	Horizontal mode boxes	1061
41.11	Vertical mode boxes	1063
41.12	Affine transformations	1066
42	l3coffins Implementation	1075
42.1	Coffins: data structures and general variables	1075
42.2	Basic coffin functions	1076
42.3	Measuring coffins	1082
42.4	Coffins: handle and pole management	1082
42.5	Coffins: calculation of pole intersections	1085
42.6	Affine transformations	1088
42.7	Aligning and typesetting of coffins	1096
42.8	Coffin diagnostics	1101
42.9	Messages	1107
43	l3color-base Implementation	1107
44	l3luatex implementation	1109
44.1	Breaking out to Lua	1109
44.2	Messages	1110
44.3	Lua functions for internal use	1110
44.4	Generic Lua and font support	1114
45	l3unicode implementation	1114

46	l3text implementation	1118
46.1	Internal auxiliaries	1118
46.2	Utilities	1119
46.3	Configuration variables	1121
46.4	Expansion to formatted text	1123
47	l3text-case implementation	1130
47.1	Case changing	1130
47.2	Case changing data for 8-bit engines	1147
48	l3text-purify implementation	1154
48.1	Purifying text	1154
48.2	Accent and letter-like data for purifying text	1159
49	l3legacy Implementation	1166
50	l3candidates Implementation	1166
50.1	Additions to l3box	1166
50.1.1	Viewing part of a box	1166
50.2	Additions to l3flag	1169
50.3	Additions to l3msg	1169
50.4	Additions to l3prg	1170
50.5	Additions to l3prop	1171
50.6	Additions to l3seq	1172
50.7	Additions to l3sys	1174
50.8	Additions to l3file	1176
50.8.1	Building a token list	1176
50.8.2	Other additions to l3tl	1179
50.9	Additions to l3token	1180
51	l3deprecation implementation	1182
51.1	Helpers and variables	1182
51.2	Patching definitions to deprecate	1183
51.3	Removed functions	1186
51.4	Deprecated primitives	1188
51.5	Loading the patches	1189
51.6	Deprecated l3box functions	1190
51.7	Deprecated l3int functions	1191
51.8	Deprecated l3luatex functions	1192
51.9	Deprecated l3msg functions	1192
51.10	Deprecated l3prg functions	1194
51.11	Deprecated l3str functions	1194
51.11.1	Deprecated l3tl functions	1195
51.12	Deprecated l3tl-analysis functions	1196
51.13	Deprecated l3token functions	1196
51.14	Deprecated l3file functions	1197
	Index	1198

Part I

Introduction to `expl3` and this document

This document is intended to act as a comprehensive reference manual for the `expl3` language. A general guide to the L^AT_EX3 programming language is found in [expl3.pdf](#).

1 Naming functions and variables

L^AT_EX3 does not use `@` as a “letter” for defining internal macros. Instead, the symbols `_` and `:` are used in internal macro names to provide structure. The name of each *function* is divided into logical units using `_`, while `:` separates the *name* of the function from the *argument specifier* (“arg-spec”). This describes the arguments expected by the function. In most cases, each argument is represented by a single letter. The complete list of arg-spec letters for a function is referred to as the *signature* of the function.

Each function name starts with the *module* to which it belongs. Thus apart from a small number of very basic functions, all `expl3` function names contain at least one underscore to divide the module name from the descriptive name of the function. For example, all functions concerned with comma lists are in module `clist` and begin `\clist_`.

Every function must include an argument specifier. For functions which take no arguments, this will be blank and the function name will end `:`. Most functions take one or more arguments, and use the following argument specifiers:

- N and n** These mean *no manipulation*, of a single token for `N` and of a set of tokens given in braces for `n`. Both pass the argument through exactly as given. Usually, if you use a single token for an `n` argument, all will be well.
- c** This means *csname*, and indicates that the argument will be turned into a *csname* before being used. So `\foo:c {ArgumentOne}` will act in the same way as `\foo:N \ArgumentOne`.
- V and v** These mean *value of variable*. The `V` and `v` specifiers are used to get the content of a variable without needing to worry about the underlying T_EX structure containing the data. A `V` argument will be a single token (similar to `N`), for example `\foo:V \MyVariable`; on the other hand, using `v` a *csname* is constructed first, and then the value is recovered, for example `\foo:v {MyVariable}`.
- o** This means *expansion once*. In general, the `V` and `v` specifiers are favoured over `o` for recovering stored information. However, `o` is useful for correctly processing information with delimited arguments.
- x** The `x` specifier stands for *exhaustive expansion*: every token in the argument is fully expanded until only unexpandable ones remain. The T_EX `\edef` primitive carries out this type of expansion. Functions which feature an `x`-type argument are *not* expandable.
- e** The `e` specifier is in many respects identical to `x`, but with a very different implementation. Functions which feature an `e`-type argument may be expandable. The drawback is that `e` is extremely slow (often more than 200 times slower) in older engines, more precisely in non-LuaT_EX engines older than 2019.

- f** The **f** specifier stands for *full expansion*, and in contrast to **x** stops at the first non-expandable token (reading the argument from left to right) without trying to expand it. If this token is a *space token*, it is gobbled, and thus won't be part of the resulting argument. For example, when setting a token list variable (a macro used for storage), the sequence

```
\tl_set:Nn \l_my_a_tl { A }
\tl_set:Nn \l_my_b_tl { B }
\tl_set:Nf \l_my_a_tl { \l_my_a_tl \l_my_b_tl }
```

will leave `\l_my_a_tl` with the content `A\l_my_b_tl`, as `A` cannot be expanded and so terminates expansion before `\l_my_b_tl` is considered.

- T and F** For logic tests, there are the branch specifiers **T** (*true*) and **F** (*false*). Both specifiers treat the input in the same way as **n** (no change), but make the logic much easier to see.
- p** The letter **p** indicates *TeX parameters*. Normally this will be used for delimited functions as `expl3` provides better methods for creating simple sequential arguments.
- w** Finally, there is the **w** specifier for *weird* arguments. This covers everything else, but mainly applies to delimited values (where the argument must be terminated by some specified string).
- D** The **D** specifier means *do not use*. All of the *TeX* primitives are initially `\let` to a **D** name, and some are then given a second name. Only the kernel team should use anything with a **D** specifier!

Notice that the argument specifier describes how the argument is processed prior to being passed to the underlying function. For example, `\foo:c` will take its argument, convert it to a control sequence and pass it to `\foo:N`.

Variables are named in a similar manner to functions, but begin with a single letter to define the type of variable:

- c** Constant: global parameters whose value should not be changed.
- g** Parameters whose value should only be set globally.
- l** Parameters whose value should only be set locally.

Each variable name is then build up in a similar way to that of a function, typically starting with the module¹ name and then a descriptive part. Variables end with a short identifier to show the variable type:

clist Comma separated list.

dim "Rigid" lengths.

fp Floating-point values;

int Integer-valued count register.

¹The module names are not used in case of generic scratch registers defined in the data type modules, e.g., the **int** module contains some scratch variables called `\l_tmpa_int`, `\l_tmpb_int`, and so on. In such a case adding the module name up front to denote the module and in the back to indicate the type, as in `\l_int_tmpa_int` would be very unreadable.

muskip “Rubber” lengths for use in mathematics.

seq “Sequence”: a data-type used to implement lists (with access at both ends) and stacks.

skip “Rubber” lengths.

str String variables: contain character data.

tl Token list variables: placeholder for a token list.

Applying V-type or v-type expansion to variables of one of the above types is supported, while it is not supported for the following variable types:

bool Either true or false.

box Box register.

coffin A “box with handles” — a higher-level data type for carrying out **box** alignment operations.

flag Integer that can be incremented expandably.

farray Fixed-size array of floating point values.

intarray Fixed-size array of integers.

ior/iow An input or output stream, for reading from or writing to, respectively.

prop Property list: analogue of dictionary or associative arrays in other languages.

regex Regular expression.

1.1 Terminological inexactitude

A word of warning. In this document, and others referring to the `expl3` programming modules, we often refer to “variables” and “functions” as if they were actual constructs from a real programming language. In truth, `TeX` is a macro processor, and functions are simply macros that may or may not take arguments and expand to their replacement text. Many of the common variables are *also* macros, and if placed into the input stream will simply expand to their definition as well — a “function” with no arguments and a “token list variable” are almost the same.² On the other hand, some “variables” are actually registers that must be initialised and their values set and retrieved with specific functions.

The conventions of the `expl3` code are designed to clearly separate the ideas of “macros that contain data” and “macros that contain code”, and a consistent wrapper is applied to all forms of “data” whether they be macros or actually registers. This means that sometimes we will use phrases like “the function returns a value”, when actually we just mean “the macro expands to something”. Similarly, the term “execute” might be used in place of “expand” or it might refer to the more specific case of “processing in `TeX`’s stomach” (if you are familiar with the `TeXbook` parlance).

If in doubt, please ask; chances are we’ve been hasty in writing certain definitions and need to be told to tighten up our terminology.

²`TeX`nically, functions with no arguments are `\long` while token list variables are not.

2 Documentation conventions

This document is typeset with the experimental `l3doc` class; several conventions are used to help describe the features of the code. A number of conventions are used here to make the documentation clearer.

Each group of related functions is given in a box. For a function with a “user” name, this might read:

```
\ExplSyntaxOn
\ExplSyntaxOff
```

```
\ExplSyntaxOn ... \ExplSyntaxOff
```

The textual description of how the function works would appear here. The syntax of the function is shown in mono-spaced text to the right of the box. In this example, the function takes no arguments and so the name of the function is simply reprinted.

For programming functions, which use `_` and `:` in their name there are a few additional conventions: If two related functions are given with identical names but different argument specifiers, these are termed *variants* of each other, and the latter functions are printed in grey to show this more clearly. They will carry out the same function but will take different types of argument:

```
\seq_new:N
\seq_new:c
```

```
\seq_new:N <sequence>
```

When a number of variants are described, the arguments are usually illustrated only for the base function. Here, `<sequence>` indicates that `\seq_new:N` expects the name of a sequence. From the argument specifier, `\seq_new:c` also expects a sequence name, but as a name rather than as a control sequence. Each argument given in the illustration should be described in the following text.

Fully expandable functions Some functions are fully expandable, which allows them to be used within an `x`-type or `e`-type argument (in plain \TeX terms, inside an `\edef` or `\expanded`), as well as within an `f`-type argument. These fully expandable functions are indicated in the documentation by a star:

```
\cs_to_str:N ☆
```

```
\cs_to_str:N <cs>
```

As with other functions, some text should follow which explains how the function works. Usually, only the star will indicate that the function is expandable. In this case, the function expects a `<cs>`, shorthand for a `<control sequence>`.

Restricted expandable functions A few functions are fully expandable but cannot be fully expanded within an `f`-type argument. In this case a hollow star is used to indicate this:

```
\seq_map_function:NN ☆
```

```
\seq_map_function:NN <seq> <function>
```

Conditional functions Conditional (`if`) functions are normally defined in three variants, with `T`, `F` and `TF` argument specifiers. This allows them to be used for different “true”/“false” branches, depending on which outcome the conditional is being used to test. To indicate this without repetition, this information is given in a shortened form:

<code>\sys_if_engine_xetex:<i><u>TF</u></i> *</code>	<code>\sys_if_engine_xetex:TF {\langle true code \rangle} {\langle false code \rangle}</code>
--	---

The underlining and italic of TF indicates that three functions are available:

- `\sys_if_engine_xetex:T`
- `\sys_if_engine_xetex:F`
- `\sys_if_engine_xetex:TF`

Usually, the illustration will use the TF variant, and so both $\langle true code \rangle$ and $\langle false code \rangle$ will be shown. The two variant forms T and F take only $\langle true code \rangle$ and $\langle false code \rangle$, respectively. Here, the star also shows that this function is expandable. With some minor exceptions, *all* conditional functions in the `expl3` modules should be defined in this way.

Variables, constants and so on are described in a similar manner:

<code>\l_tmpa_tl</code>	
-------------------------	--

A short piece of text will describe the variable: there is no syntax illustration in this case.

In some cases, the function is similar to one in $\text{\LaTeX} 2_{\epsilon}$ or plain \TeX . In these cases, the text will include an extra “ **\TeX hackers note**” section:

<code>\token_to_str:N *</code>	<code>\token_to_str:N \langle token \rangle</code>
--------------------------------	--

The normal description text.

\TeX hackers note: Detail for the experienced \TeX or $\text{\LaTeX} 2_{\epsilon}$ programmer. In this case, it would point out that this function is the \TeX primitive `\string`.

Changes to behaviour When new functions are added to `expl3`, the date of first inclusion is given in the documentation. Where the documented behaviour of a function changes after it is first introduced, the date of the update will also be given. This means that the programmer can be sure that any release of `expl3` after the date given will contain the function of interest with expected behaviour as described. Note that changes to code internals, including bug fixes, are not recorded in this way *unless* they impact on the expected behaviour.

3 Formal language conventions which apply generally

As this is a formal reference guide for $\text{\LaTeX} 3$ programming, the descriptions of functions are intended to be reasonably “complete”. However, there is also a need to avoid repetition. Formal ideas which apply to general classes of function are therefore summarised here.

For tests which have a TF argument specification, the test is evaluated to give a logically TRUE or FALSE result. Depending on this result, either the $\langle true code \rangle$ or the $\langle false code \rangle$ will be left in the input stream. In the case where the test is expandable, and a predicate (`_p`) variant is available, the logical value determined by the test is left in the input stream: this will typically be part of a larger logical construct.

4 \TeX concepts not supported by $\text{\LaTeX}3$

The \TeX concept of an “`\outer`” macro is *not supported* at all by $\text{\LaTeX}3$. As such, the functions provided here may break when used on top of $\text{\LaTeX}2_{\epsilon}$ if `\outer` tokens are used in the arguments.

Part II

The l3bootstrap package

Bootstrap code

1 Using the L^AT_EX3 modules

The modules documented in `source3` are designed to be used on top of L^AT_EX 2_ε and are loaded all as one with the usual `\usepackage{expl3}` or `\RequirePackage{expl3}` instructions. These modules will also form the basis of the L^AT_EX3 format, but work in this area is incomplete and not included in this documentation at present.

As the modules use a coding syntax different from standard L^AT_EX 2_ε it provides a few functions for setting it up.

`\ExplSyntaxOn`
`\ExplSyntaxOff`

Updated: 2011-08-13

`\ExplSyntaxOn` *<code>* `\ExplSyntaxOff`

The `\ExplSyntaxOn` function switches to a category code régime in which spaces are ignored and in which the colon (:) and underscore (_) are treated as “letters”, thus allowing access to the names of code functions and variables. Within this environment, ~ is used to input a space. The `\ExplSyntaxOff` reverts to the document category code régime.

`\ProvidesExplPackage`
`\ProvidesExplClass`
`\ProvidesExplFile`

Updated: 2017-03-19

`\RequirePackage{expl3}`
`\ProvidesExplPackage` *{<package>}* *{<date>}* *{<version>}* *{<description>}*

These functions act broadly in the same way as the corresponding L^AT_EX 2_ε kernel functions `\ProvidesPackage`, `\ProvidesClass` and `\ProvidesFile`. However, they also implicitly switch `\ExplSyntaxOn` for the remainder of the code with the file. At the end of the file, `\ExplSyntaxOff` will be called to reverse this. (This is the same concept as L^AT_EX 2_ε provides in turning on `\makeatletter` within package and class code.) The *<date>* should be given in the format *<year>/<month>/<day>*. If the *<version>* is given then it will be prefixed with v in the package identifier line.

`\GetIdInfo`

Updated: 2012-06-04

`\RequirePackage{l3bootstrap}`
`\GetIdInfo` *\$Id: <SVN info field> \$* *{<description>}*

Extracts all information from a SVN field. Spaces are not ignored in these fields. The information pieces are stored in separate control sequences with `\ExplFileName` for the part of the file name leading up to the period, `\ExplFileDate` for date, `\ExplFileVersion` for version and `\ExplFileDescription` for the description.

To summarize: Every single package using this syntax should identify itself using one of the above methods. Special care is taken so that every package or class file loaded with `\RequirePackage` or similar are loaded with usual L^AT_EX 2_ε category codes and the L^AT_EX3 category code scheme is reloaded when needed afterwards. See implementation for details. If you use the `\GetIdInfo` command you can use the information when loading a package with

```
\ProvidesExplPackage{\ExplFileName}
  {\ExplFileDate}{\ExplFileVersion}{\ExplFileDescription}
```

Part III

The l3names package

Namespace for primitives

1 Setting up the L^AT_EX3 programming language

This module is at the core of the L^AT_EX3 programming language. It performs the following tasks:

- defines new names for all T_EX primitives;
- switches to the category code régime for programming;
- provides support settings for building the code as a T_EX format.

This module is entirely dedicated to primitives, which should not be used directly within L^AT_EX3 code (outside of “kernel-level” code). As such, the primitives are not documented here: *The T_EXbook*, *T_EX by Topic* and the manuals for pdfT_EX, X_YT_EX, LuaT_EX, pT_EX and upT_EX should be consulted for details of the primitives. These are named `\tex_⟨name⟩:D`, typically based on the primitive’s *⟨name⟩* in pdfT_EX and omitting a leading `pdf` when the primitive is not related to pdf output.

Part IV

The l3basics package

Basic definitions

As the name suggest this package holds some basic definitions which are needed by most or all other packages in this set.

Here we describe those functions that are used all over the place. With that we mean functions dealing with the construction and testing of control sequences. Furthermore the basic parts of conditional processing are covered; conditional processing dealing with specific data types is described in the modules specific for the respective data types.

1 No operation functions

`\prg_do_nothing: *`

`\prg_do_nothing:`

An expandable function which does nothing at all: leaves nothing in the input stream after a single expansion.

`\scan_stop:`

`\scan_stop:`

A non-expandable function which does nothing. Does not vanish on expansion but produces no typeset output.

2 Grouping material

`\group_begin:`

`\group_begin:`**`\group_end:`**

`\group_end:`

These functions begin and end a group for definition purposes. Assignments are local to groups unless carried out in a global manner. (A small number of exceptions to this rule will be noted as necessary elsewhere in this document.) Each `\group_begin:` must be matched by a `\group_end:`, although this does not have to occur within the same function. Indeed, it is often necessary to start a group within one function and finish it within another, for example when seeking to use non-standard category codes.

`\group_insert_after:N`

`\group_insert_after:N` $\langle token \rangle$

Adds $\langle token \rangle$ to the list of $\langle tokens \rangle$ to be inserted when the current group level ends. The list of $\langle tokens \rangle$ to be inserted is empty at the beginning of a group: multiple applications of `\group_insert_after:N` may be used to build the inserted list one $\langle token \rangle$ at a time. The current group level may be closed by a `\group_end:` function or by a token with category code 2 (close-group), namely a `}` if standard category codes apply.

3 Control sequences and functions

As \TeX is a macro language, creating new functions means creating macros. At point of use, a function is replaced by the replacement text (“code”) in which each parameter in the code (`#1`, `#2`, *etc.*) is replaced the appropriate arguments absorbed by the function. In the following, *code* is therefore used as a shorthand for “replacement text”.

Functions which are not “protected” are fully expanded inside an `x` expansion. In contrast, “protected” functions are not expanded within `x` expansions.

3.1 Defining functions

Functions can be created with no requirement that they are declared first (in contrast to variables, which must always be declared). Declaring a function before setting up the code means that the name chosen is checked and an error raised if it is already in use. The name of a function can be checked at the point of definition using the `\cs_new...` functions: this is recommended for all functions which are defined for the first time.

There are three ways to define new functions. All classes define a function to expand to the substitution text. Within the substitution text the actual parameters are substituted for the formal parameters (`#1`, `#2`, ...).

new Create a new function with the **new** scope, such as `\cs_new:Npn`. The definition is global and results in an error if it is already defined.

set Create a new function with the **set** scope, such as `\cs_set:Npn`. The definition is restricted to the current \TeX group and does not result in an error if the function is already defined.

gset Create a new function with the **gset** scope, such as `\cs_gset:Npn`. The definition is global and does not result in an error if the function is already defined.

Within each set of scope there are different ways to define a function. The differences depend on restrictions on the actual parameters and the expandability of the resulting function.

nopar Create a new function with the **nopar** restriction, such as `\cs_set_nopar:Npn`. The parameter may not contain `\par` tokens.

protected Create a new function with the **protected** restriction, such as `\cs_set_protected:Npn`. The parameter may contain `\par` tokens but the function will not expand within an `x`-type or `e`-type expansion.

Finally, the functions in Subsections 3.2 and 3.3 are primarily meant to define *base functions* only. Base functions can only have the following argument specifiers:

N and n No manipulation.

T and F Functionally equivalent to **n** (you are actually encouraged to use the family of `\prg_new_conditional:` functions described in Section 1).

p and w These are special cases.

The `\cs_new:` functions below (and friends) do not stop you from using other argument specifiers in your function names, but they do not handle expansion for you. You should define the base function and then use `\cs_generate_variant:Nn` to generate custom variants as described in Section 2.

3.2 Defining new functions using parameter text

<code>\cs_new:Npn</code>	<code>\cs_new:Npn <function> <parameters> {<code>}</code>
<code>\cs_new:cpn</code>	Creates <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_new:Npx</code>	<code><parameters></code> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_new:cpx</code>	definition is global and an error results if the <code><function></code> is already defined.

<code>\cs_new_nopar:Npn</code>	<code>\cs_new_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_nopar:cpn</code>	Creates <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_new_nopar:Npx</code>	<code><parameters></code> (#1, #2, etc.) will be replaced by those absorbed by the function. When the
<code>\cs_new_nopar:cpx</code>	<code><function></code> is used the <code><parameters></code> absorbed cannot contain <code>\par</code> tokens. The definition
	is global and an error results if the <code><function></code> is already defined.

<code>\cs_new_protected:Npn</code>	<code>\cs_new_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_protected:cpn</code>	Creates <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_new_protected:Npx</code>	<code><parameters></code> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_new_protected:cpx</code>	<code><function></code> will not expand within an x-type argument. The definition is global and an
	error results if the <code><function></code> is already defined.

<code>\cs_new_protected_nopar:Npn</code>	<code>\cs_new_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_protected_nopar:cpn</code>	
<code>\cs_new_protected_nopar:Npx</code>	
<code>\cs_new_protected_nopar:cpx</code>	

Creates `<function>` to expand to `<code>` as replacement text. Within the `<code>`, the `<parameters>` (#1, #2, etc.) will be replaced by those absorbed by the function. When the `<function>` is used the `<parameters>` absorbed cannot contain `\par` tokens. The `<function>` will not expand within an x-type or e-type argument. The definition is global and an error results if the `<function>` is already defined.

<code>\cs_set:Npn</code>	<code>\cs_set:Npn <function> <parameters> {<code>}</code>
<code>\cs_set:cpn</code>	Sets <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_set:Npx</code>	<code><parameters></code> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_set:cpx</code>	assignment of a meaning to the <code><function></code> is restricted to the current \TeX group level.

<code>\cs_set_nopar:Npn</code>	<code>\cs_set_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_nopar:cpn</code>	Sets <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_set_nopar:Npx</code>	<code><parameters></code> (#1, #2, etc.) will be replaced by those absorbed by the function. When the
<code>\cs_set_nopar:cpx</code>	<code><function></code> is used the <code><parameters></code> absorbed cannot contain <code>\par</code> tokens. The assignment
	of a meaning to the <code><function></code> is restricted to the current \TeX group level.

<code>\cs_set_protected:Npn</code>	<code>\cs_set_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_protected:cpn</code>	Sets <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_set_protected:Npx</code>	<code><parameters></code> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_set_protected:cpx</code>	assignment of a meaning to the <code><function></code> is restricted to the current \TeX group level.
	The <code><function></code> will not expand within an x-type or e-type argument.

<code>\cs_set_protected_nopar:Npn</code>	<code>\cs_set_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_protected_nopar:cpn</code>	
<code>\cs_set_protected_nopar:Npx</code>	
<code>\cs_set_protected_nopar:cpx</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level. The $\langle function \rangle$ will not expand within an **x**-type or **e**-type argument.

<code>\cs_gset:Npn</code>	<code>\cs_gset:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset:cpn</code>	
<code>\cs_gset:Npx</code>	
<code>\cs_gset:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global.

<code>\cs_gset_nopar:Npn</code>	<code>\cs_gset_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset_nopar:cpn</code>	
<code>\cs_gset_nopar:Npx</code>	
<code>\cs_gset_nopar:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global.

<code>\cs_gset_protected:Npn</code>	<code>\cs_gset_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset_protected:cpn</code>	
<code>\cs_gset_protected:Npx</code>	
<code>\cs_gset_protected:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global. The $\langle function \rangle$ will not expand within an **x**-type or **e**-type argument.

<code>\cs_gset_protected_nopar:Npn</code>	<code>\cs_gset_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset_protected_nopar:cpn</code>	
<code>\cs_gset_protected_nopar:Npx</code>	
<code>\cs_gset_protected_nopar:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global. The $\langle function \rangle$ will not expand within an **x**-type argument.

3.3 Defining new functions using the signature

<code>\cs_new:Nn</code>	<code>\cs_new:Nn <function> {<code>}</code>
<code>\cs_new:(cn Nx cx)</code>	

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The definition is global and an error results if the $\langle function \rangle$ is already defined.

<hr/> <code>\cs_new_nopar:Nn</code> <code>\cs_new_nopar:(cn Nx cx)</code> <hr/>	<code>\cs_new_nopar:Nn <function> {<code>}</code> <p>Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain <code>\par</code> tokens. The definition is global and an error results if the $\langle function \rangle$ is already defined.</p>
<hr/> <code>\cs_new_protected:Nn</code> <code>\cs_new_protected:(cn Nx cx)</code> <hr/>	<code>\cs_new_protected:Nn <function> {<code>}</code> <p>Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The definition is global and an error results if the $\langle function \rangle$ is already defined.</p>
<hr/> <code>\cs_new_protected_nopar:Nn</code> <code>\cs_new_protected_nopar:(cn Nx cx)</code> <hr/>	<code>\cs_new_protected_nopar:Nn <function> {<code>}</code> <p>Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain <code>\par</code> tokens. The $\langle function \rangle$ will not expand within an x-type or e-type argument. The definition is global and an error results if the $\langle function \rangle$ is already defined.</p>
<hr/> <code>\cs_set:Nn</code> <code>\cs_set:(cn Nx cx)</code> <hr/>	<code>\cs_set:Nn <function> {<code>}</code> <p>Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.</p>
<hr/> <code>\cs_set_nopar:Nn</code> <code>\cs_set_nopar:(cn Nx cx)</code> <hr/>	<code>\cs_set_nopar:Nn <function> {<code>}</code> <p>Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain <code>\par</code> tokens. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.</p>
<hr/> <code>\cs_set_protected:Nn</code> <code>\cs_set_protected:(cn Nx cx)</code> <hr/>	<code>\cs_set_protected:Nn <function> {<code>}</code> <p>Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.</p>

<code>\cs_set_protected_nopar:Nn</code>	<code>\cs_set_protected_nopar:Nn <function> {<code>}</code>
<code>\cs_set_protected_nopar:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an *x*-type or *e*-type argument. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current T_EX group level.

<code>\cs_gset:Nn</code>	<code>\cs_gset:Nn <function> {<code>}</code>
<code>\cs_gset:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_gset_nopar:Nn</code>	<code>\cs_gset_nopar:Nn <function> {<code>}</code>
<code>\cs_gset_nopar:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_gset_protected:Nn</code>	<code>\cs_gset_protected:Nn <function> {<code>}</code>
<code>\cs_gset_protected:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an *x*-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_gset_protected_nopar:Nn</code>	<code>\cs_gset_protected_nopar:Nn <function> {<code>}</code>
<code>\cs_gset_protected_nopar:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an *x*-type or *e*-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_generate_from_arg_count:NNnn</code>	<code>\cs_generate_from_arg_count:NNnn <function> <creator> {<number>}</code>
<code>\cs_generate_from_arg_count:(cNnn Ncnn)</code>	<code>{<code>}</code>

Updated: 2012-01-14

Uses the $\langle creator \rangle$ function (which should have signature Npn , for example `\cs_new:Npn`) to define a $\langle function \rangle$ which takes $\langle number \rangle$ arguments and has $\langle code \rangle$ as replacement text. The $\langle number \rangle$ of arguments is an integer expression, evaluated as detailed for `\int_eval:n`.

3.4 Copying control sequences

Control sequences (not just functions as defined above) can be set to have the same meaning using the functions described here. Making two control sequences equivalent means that the second control sequence is a *copy* of the first (rather than a pointer to it). Thus the old and new control sequence are not tied together: changes to one are not reflected in the other.

In the following text “cs” is used as an abbreviation for “control sequence”.

```
\cs_new_eq:NN
\cs_new_eq:(Nc|cN|cc)
```

```
\cs_new_eq:NN <cs1> <cs2>
\cs_new_eq:NN <cs1> <token>
```

Globally creates $\langle control\ sequence_1 \rangle$ and sets it to have the same meaning as $\langle control\ sequence_2 \rangle$ or $\langle token \rangle$. The second control sequence may subsequently be altered without affecting the copy.

```
\cs_set_eq:NN
\cs_set_eq:(Nc|cN|cc)
```

```
\cs_set_eq:NN <cs1> <cs2>
\cs_set_eq:NN <cs1> <token>
```

Sets $\langle control\ sequence_1 \rangle$ to have the same meaning as $\langle control\ sequence_2 \rangle$ (or $\langle token \rangle$). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the $\langle control\ sequence_1 \rangle$ is restricted to the current T_EX group level.

```
\cs_gset_eq:NN
\cs_gset_eq:(Nc|cN|cc)
```

```
\cs_gset_eq:NN <cs1> <cs2>
\cs_gset_eq:NN <cs1> <token>
```

Globally sets $\langle control\ sequence_1 \rangle$ to have the same meaning as $\langle control\ sequence_2 \rangle$ (or $\langle token \rangle$). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the $\langle control\ sequence_1 \rangle$ is *not* restricted to the current T_EX group level: the assignment is global.

3.5 Deleting control sequences

There are occasions where control sequences need to be deleted. This is handled in a very simple manner.

```
\cs_undefine:N
\cs_undefine:c
```

```
\cs_undefine:N <control sequence>
```

Sets $\langle control\ sequence \rangle$ to be globally undefined.

Updated: 2011-09-15

3.6 Showing control sequences

```
\cs_meaning:N ★
\cs_meaning:c ★
```

```
\cs_meaning:N <control sequence>
```

This function expands to the *meaning* of the $\langle control\ sequence \rangle$ control sequence. For a macro, this includes the $\langle replacement\ text \rangle$.

Updated: 2011-12-22

T_EXhackers note: This is T_EX’s `\meaning` primitive. For tokens that are not control sequences, it is more logical to use `\token_to_meaning:N`. The `c` variant correctly reports undefined arguments.

`\cs_show:N`
`\cs_show:c`

Updated: 2017-02-14

`\cs_show:N` $\langle control\ sequence \rangle$
Displays the definition of the $\langle control\ sequence \rangle$ on the terminal.

T_EXhackers note: This is similar to the T_EX primitive `\show`, wrapped to a fixed number of characters per line.

`\cs_log:N`
`\cs_log:c`

New: 2014-08-22
Updated: 2017-02-14

`\cs_log:N` $\langle control\ sequence \rangle$
Writes the definition of the $\langle control\ sequence \rangle$ in the log file. See also `\cs_show:N` which displays the result in the terminal.

3.7 Converting to and from control sequences

`\use:c` ★

`\use:c` $\{ \langle control\ sequence\ name \rangle \}$

Expands the $\langle control\ sequence\ name \rangle$ until only characters remain, and then converts this into a control sequence. This process requires two expansions. As in other `c`-type arguments the $\langle control\ sequence\ name \rangle$ must, when fully expanded, consist of character tokens, typically a mixture of category code 10 (space), 11 (letter) and 12 (other).

T_EXhackers note: Protected macros that appear in a `c`-type argument are expanded despite being protected; `\exp_not:n` also has no effect. An internal error occurs if non-characters or active characters remain after full expansion, as the conversion to a control sequence is not possible.

As an example of the `\use:c` function, both

`\use:c { a b c }`

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { a b c }
\use:c { \tl_use:N \l_my_tl }
```

would be equivalent to

`\abc`

after two expansions of `\use:c`.

`\cs_if_exist_use:N` ★
`\cs_if_exist_use:c` ★
`\cs_if_exist_use:NTF` ★
`\cs_if_exist_use:cTF` ★

New: 2012-11-10

`\cs_if_exist_use:N` $\langle control\ sequence \rangle$
`\cs_if_exist_use:NTF` $\langle control\ sequence \rangle$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$
Tests whether the $\langle control\ sequence \rangle$ is currently defined according to the conditional `\cs_if_exist:NTF` (whether as a function or another control sequence type), and if it is inserts the $\langle control\ sequence \rangle$ into the input stream followed by the $\langle true\ code \rangle$. Otherwise the $\langle false\ code \rangle$ is used.

<code>\cs:w</code>	★	<code>\cs:w</code> \langle <i>control sequence name</i> \rangle <code>\cs_end:</code>
<code>\cs_end:</code>	★	

Converts the given \langle *control sequence name* \rangle into a single control sequence token. This process requires one expansion. The content for \langle *control sequence name* \rangle may be literal material or from other expandable functions. The \langle *control sequence name* \rangle must, when fully expanded, consist of character tokens which are not active: typically of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

T_EXhackers note: These are the T_EX primitives `\csname` and `\endcsname`.

As an example of the `\cs:w` and `\cs_end:` functions, both

`\cs:w a b c \cs_end:`

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { a b c }
\cs:w \tl_use:N \l_my_tl \cs_end:
```

would be equivalent to

`\abc`

after one expansion of `\cs:w`.

<code>\cs_to_str:N</code>	★	<code>\cs_to_str:N</code> \langle <i>control sequence</i> \rangle
---------------------------	---	---

Converts the given \langle *control sequence* \rangle into a series of characters with category code 12 (other), except spaces, of category code 10. The result does *not* include the current escape token, contrarily to `\token_to_str:N`. Full expansion of this function requires exactly 2 expansion steps, and so an x-type or e-type expansion, or two o-type expansions are required to convert the \langle *control sequence* \rangle to a sequence of characters in the input stream. In most cases, an f-expansion is correct as well, but this loses a space at the start of the result.

4 Analysing control sequences

<code>\cs_split_function:N</code>	★	<code>\cs_split_function:N</code> \langle <i>function</i> \rangle
-----------------------------------	---	---

New: 2018-04-06

Splits the \langle *function* \rangle into the \langle *name* \rangle (*i.e.* the part before the colon) and the \langle *signature* \rangle (*i.e.* after the colon). This information is then placed in the input stream in three parts: the \langle *name* \rangle , the \langle *signature* \rangle and a logic token indicating if a colon was found (to differentiate variables from function names). The \langle *name* \rangle does not include the escape character, and both the \langle *name* \rangle and \langle *signature* \rangle are made up of tokens with category code 12 (other).

The next three functions decompose T_EX macros into their constituent parts: if the \langle *token* \rangle passed is not a macro then no decomposition can occur. In the latter case, all three functions leave `\scan_stop:` in the input stream.

\cs_prefix_spec:N ★

New: 2019-02-27

\cs_prefix_spec:N $\langle token \rangle$

If the $\langle token \rangle$ is a macro, this function leaves the applicable \TeX prefixes in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example

```
\cs_set:Npn \next:nn #1#2 { x #1~y #2 }
\cs_prefix_spec:N \next:nn
```

leaves $\backslash\text{long}$ in the input stream. If the $\langle token \rangle$ is not a macro then $\backslash\text{scan_stop}$: is left in the input stream.

\TeX hackers note: The prefix can be empty, $\backslash\text{long}$, $\backslash\text{protected}$ or $\backslash\text{protected}\backslash\text{long}$ with backslash replaced by the current escape character.

\cs_argument_spec:N ★

New: 2019-02-27

\cs_argument_spec:N $\langle token \rangle$

If the $\langle token \rangle$ is a macro, this function leaves the primitive \TeX argument specification in input stream as a string of character tokens of category code 12 (with spaces having category code 10). Thus for example

```
\cs_set:Npn \next:nn #1#2 { x #1 y #2 }
\cs_argument_spec:N \next:nn
```

leaves $\text{\#1}\text{\#2}$ in the input stream. If the $\langle token \rangle$ is not a macro then $\backslash\text{scan_stop}$: is left in the input stream.

\TeX hackers note: If the argument specification contains the string \rightarrow , then the function produces incorrect results.

\cs_replacement_spec:N ★

New: 2019-02-27

\cs_replacement_spec:N $\langle token \rangle$

If the $\langle token \rangle$ is a macro, this function leaves the replacement text in input stream as a string of character tokens of category code 12 (with spaces having category code 10). Thus for example

```
\cs_set:Npn \next:nn #1#2 { x #1~y #2 }
\cs_replacement_spec:N \next:nn
```

leaves $\text{x}\text{\#1}_\text{y}\text{\#2}$ in the input stream. If the $\langle token \rangle$ is not a macro then $\backslash\text{scan_stop}$: is left in the input stream.

\TeX hackers note: If the argument specification contains the string \rightarrow , then the function produces incorrect results.

5 Using or removing tokens and arguments

Tokens in the input can be read and used or read and discarded. If one or more tokens are wrapped in braces then when absorbing them the outer set is removed. At the same time, the category code of each token is set when the token is read by a function (if it

is read more than once, the category code is determined by the situation in force when first function absorbs the token).

<code>\use:n</code>	*	<code>\use:n</code>	<code>{\group₁}</code>
<code>\use:nn</code>	*	<code>\use:nn</code>	<code>{\group₁}</code> <code>{\group₂}</code>
<code>\use:nnn</code>	*	<code>\use:nnn</code>	<code>{\group₁}</code> <code>{\group₂}</code> <code>{\group₃}</code>
<code>\use:nnnn</code>	*	<code>\use:nnnn</code>	<code>{\group₁}</code> <code>{\group₂}</code> <code>{\group₃}</code> <code>{\group₄}</code>

As illustrated, these functions absorb between one and four arguments, as indicated by the argument specifier. The braces surrounding each argument are removed and the remaining tokens are left in the input stream. The category code of these tokens is also fixed by this process (if it has not already been by some other absorption). All of these functions require only a single expansion to operate, so that one expansion of

`\use:nn { abc } { { def } }`

results in the input stream containing

`abc { def }`

i.e. only the outer braces are removed.

T_EXhackers note: The `\use:n` function is equivalent to L^AT_EX 2_ε's `\@firstofone`.

<code>\use_i:nn</code>	*	<code>\use_i:nn</code>	<code>{\arg₁}</code> <code>{\arg₂}</code>
<code>\use_ii:nn</code>	*		

These functions absorb two arguments from the input stream. The function `\use_i:nn` discards the second argument, and leaves the content of the first argument in the input stream. `\use_ii:nn` discards the first argument and leaves the content of the second argument in the input stream. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.

T_EXhackers note: These are equivalent to L^AT_EX 2_ε's `\@firstoftwo` and `\@secondoftwo`.

<code>\use_i:nnn</code>	*	<code>\use_i:nnn</code>	<code>{\arg₁}</code> <code>{\arg₂}</code> <code>{\arg₃}</code>
<code>\use_ii:nnn</code>	*		
<code>\use_iii:nnn</code>	*		

These functions absorb three arguments from the input stream. The function `\use_i:nnn` discards the second and third arguments, and leaves the content of the first argument in the input stream. `\use_ii:nnn` and `\use_iii:nnn` work similarly, leaving the content of second or third arguments in the input stream, respectively. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.

<code>\use_i:nnnn</code>	*	<code>\use_i:nnnn</code>	<code>{\arg₁}</code> <code>{\arg₂}</code> <code>{\arg₃}</code> <code>{\arg₄}</code>
<code>\use_ii:nnnn</code>	*		
<code>\use_iii:nnnn</code>	*		
<code>\use_iv:nnnn</code>	*		

These functions absorb four arguments from the input stream. The function `\use_i:nnnn` discards the second, third and fourth arguments, and leaves the content of the first argument in the input stream. `\use_ii:nnnn`, `\use_iii:nnnn` and `\use_iv:nnnn` work similarly, leaving the content of second, third or fourth arguments in the input stream, respectively. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.

<code>\use_i_ii:nnn</code>	★	<code>\use_i_ii:nnn {\langle arg_1 \rangle} {\langle arg_2 \rangle} {\langle arg_3 \rangle}</code>
----------------------------	---	--

This function absorbs three arguments and leaves the content of the first and second in the input stream. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the function to take effect. An example:

```
\use_i_ii:nnn { abc } { { def } } { ghi }
```

results in the input stream containing

```
abc { def }
```

i.e. the outer braces are removed and the third group is removed.

<code>\use_ii_i:nn</code>	★	<code>\use_ii_i:nn {\langle arg_1 \rangle} {\langle arg_2 \rangle}</code>
---------------------------	---	---

New: 2019-06-02

This function absorbs two arguments and leaves the content of the second and first in the input stream. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the function to take effect.

<code>\use_none:n</code>	★	<code>\use_none:n {\langle group_1 \rangle}</code>
--------------------------	---	--

<code>\use_none:nn</code>	★
---------------------------	---

<code>\use_none:nnn</code>	★
----------------------------	---

<code>\use_none:nnnn</code>	★
-----------------------------	---

<code>\use_none:nnnnn</code>	★
------------------------------	---

<code>\use_none:nnnnnn</code>	★
-------------------------------	---

<code>\use_none:nnnnnnn</code>	★
--------------------------------	---

<code>\use_none:nnnnnnnn</code>	★
---------------------------------	---

<code>\use_none:nnnnnnnnn</code>	★
----------------------------------	---

These functions absorb between one and nine groups from the input stream, leaving nothing on the resulting input stream. These functions work after a single expansion. One or more of the `n` arguments may be an unbraced single token (*i.e.* an `N` argument).

TeXhackers note: These are equivalent to L^AT_EX 2_ε's `\@gobble`, `\@gobbletwo`, *etc.*

<code>\use:e</code>	★	<code>\use:e {\langle expandable tokens \rangle}</code>
---------------------	---	---

New: 2018-06-18

Fully expands the `\langle token list \rangle` in an `x`-type manner, *but* the function remains fully expandable, and parameter character (usually `#`) need not be doubled.

TeXhackers note: `\use:e` is a wrapper around the primitive `\expanded` where it is available: it requires two expansions to complete its action. When `\expanded` is not available this function is very slow.

<code>\use:x</code>		<code>\use:x {\langle expandable tokens \rangle}</code>
---------------------	--	---

Updated: 2011-12-31

Fully expands the `\langle expandable tokens \rangle` and inserts the result into the input stream at the current location. Any hash characters (`#`) in the argument must be doubled.

5.1 Selecting tokens from delimited arguments

A different kind of function for selecting tokens from the token stream are those that use delimited arguments.

<code>\use_none_delimit_by_q_nil:w</code>	<code>*</code>	<code>\use_none_delimit_by_q_nil:w <balanced text> \q_nil</code>
<code>\use_none_delimit_by_q_stop:w</code>	<code>*</code>	<code>\use_none_delimit_by_q_stop:w <balanced text> \q_stop</code>
<code>\use_none_delimit_by_q_recursion_stop:w</code>	<code>*</code>	<code>\use_none_delimit_by_q_recursion_stop:w <balanced text></code>

Absorb the *<balanced text>* from the input stream delimited by the marker given in the function name, leaving nothing in the input stream.

<code>\use_i_delimit_by_q_nil:nw</code>	<code>*</code>	<code>\use_i_delimit_by_q_nil:nw {<inserted tokens>} <balanced text></code>
<code>\use_i_delimit_by_q_stop:nw</code>	<code>*</code>	<code>\q_nil</code>
<code>\use_i_delimit_by_q_recursion_stop:nw</code>	<code>*</code>	<code>\use_i_delimit_by_q_stop:nw {<inserted tokens>} <balanced text> \q_stop</code>
		<code>\use_i_delimit_by_q_recursion_stop:nw {<inserted tokens>}</code>
		<code><balanced text> \q_recursion_stop</code>

Absorb the *<balanced text>* from the input stream delimited by the marker given in the function name, leaving *<inserted tokens>* in the input stream for further processing.

6 Predicates and conditionals

L^AT_EX3 has three concepts for conditional flow processing:

Branching conditionals Functions that carry out a test and then execute, depending on its result, either the code supplied as the *<true code>* or the *<false code>*. These arguments are denoted with T and F, respectively. An example would be

`\cs_if_free:cTF {abc} {<true code>} {<false code>}`

a function that turns the first argument into a control sequence (since it's marked as c) then checks whether this control sequence is still free and then depending on the result carries out the code in the second argument (true case) or in the third argument (false case).

These type of functions are known as “conditionals”; whenever a TF function is defined it is usually accompanied by T and F functions as well. These are provided for convenience when the branch only needs to go a single way. Package writers are free to choose which types to define but the kernel definitions always provide all three versions.

Important to note is that these branching conditionals with *<true code>* and/or *<false code>* are always defined in a way that the code of the chosen alternative can operate on following tokens in the input stream.

These conditional functions may or may not be fully expandable, but if they are expandable they are accompanied by a “predicate” for the same test as described below.

Predicates “Predicates” are functions that return a special type of boolean value which can be tested by the boolean expression parser. All functions of this type are expandable and have names that end with `_p` in the description part. For example,

`\cs_if_free_p:N`

would be a predicate function for the same type of test as the conditional described above. It would return “true” if its argument (a single token denoted by N) is still free for definition. It would be used in constructions like

```

\bool_if:nTF {
  \cs_if_free_p:N \l_tmpz_tl || \cs_if_free_p:N \g_tmpz_tl
} {\true code} {\false code}

```

For each predicate defined, a “branching conditional” also exists that behaves like a conditional described above.

Primitive conditionals There is a third variety of conditional, which is the original concept used in plain T_EX and L^AT_EX 2_ε. Their use is discouraged in expl3 (although still used in low-level definitions) because they are more fragile and in many cases require more expansion control (hence more code) than the two types of conditionals described above.

```

\c_true_bool
\c_false_bool

```

Constants that represent `true` and `false`, respectively. Used to implement predicates.

6.1 Tests on control sequences

```

\cs_if_eq_p:NN *
\cs_if_eq:NNTF *

```

```

\cs_if_eq_p:NN <cs1> <cs2>
\cs_if_eq:NNTF <cs1> <cs2> {\true code} {\false code}

```

Compares the definition of two *<control sequences>* and is logically `true` if they are the same, *i.e.* if they have exactly the same definition when examined with `\cs_show:N`.

```

\cs_if_exist_p:N *
\cs_if_exist_p:c *
\cs_if_exist:NTF *
\cs_if_exist:cTF *

```

```

\cs_if_exist_p:N <control sequence>
\cs_if_exist:NNTF <control sequence> {\true code} {\false code}

```

Tests whether the *<control sequence>* is currently defined (whether as a function or another control sequence type). Any definition of *<control sequence>* other than `\relax` evaluates as `true`.

```

\cs_if_free_p:N *
\cs_if_free_p:c *
\cs_if_free:NTF *
\cs_if_free:cTF *

```

```

\cs_if_free_p:N <control sequence>
\cs_if_free:NNTF <control sequence> {\true code} {\false code}

```

Tests whether the *<control sequence>* is currently free to be defined. This test is `false` if the *<control sequence>* currently exists (as defined by `\cs_if_exist:N`).

6.2 Primitive conditionals

The ε -T_EX engine itself provides many different conditionals. Some expand whatever comes after them and others don’t. Hence the names for these underlying functions often contains a `:w` part but higher level functions are often available. See for instance `\int_compare_p:nNn` which is a wrapper for `\if_int_compare:w`.

Certain conditionals deal with specific data types like boxes and fonts and are described there. The ones described below are either the universal conditionals or deal with control sequences. We prefix primitive conditionals with `\if_`.

<code>\if_true:</code>	★	<code>\if_true: <true code> \else: <false code> \fi:</code>
<code>\if_false:</code>	★	<code>\if_false: <true code> \else: <false code> \fi:</code>
<code>\else:</code>	★	<code>\reverse_if:N <primitive conditional></code>
<code>\fi:</code>	★	<code>\if_true:</code> always executes <i><true code></i> , while <code>\if_false:</code> always executes <i><false code></i> .
<code>\reverse_if:N</code>	★	<code>\reverse_if:N</code> reverses any two-way primitive conditional. <code>\else:</code> and <code>\fi:</code> delimit the branches of the conditional. The function <code>\or:</code> is documented in <code>l3int</code> and used in case switches.

TeXhackers note: These are equivalent to their corresponding TeX primitive conditionals; `\reverse_if:N` is ε -TeX's `\unless`.

<code>\if_meaning:w</code>	★	<code>\if_meaning:w <arg₁> <arg₂> <true code> \else: <false code> \fi:</code>
----------------------------	---	---

`\if_meaning:w` executes *<true code>* when *<arg₁>* and *<arg₂>* are the same, otherwise it executes *<false code>*. *<arg₁>* and *<arg₂>* could be functions, variables, tokens; in all cases the *unexpanded* definitions are compared.

TeXhackers note: This is TeX's `\ifx`.

<code>\if:w</code>	★	<code>\if:w <token₁> <token₂> <true code> \else: <false code> \fi:</code>
<code>\if_charcode:w</code>	★	<code>\if_catcode:w <token₁> <token₂> <true code> \else: <false code> \fi:</code>
<code>\if_catcode:w</code>	★	These conditionals expand any following tokens until two unexpandable tokens are left. If you wish to prevent this expansion, prefix the token in question with <code>\exp_not:N</code> . <code>\if_catcode:w</code> tests if the category codes of the two tokens are the same whereas <code>\if:w</code> tests if the character codes are identical. <code>\if_charcode:w</code> is an alternative name for <code>\if:w</code> .

<code>\if_cs_exist:N</code>	★	<code>\if_cs_exist:N <cs> <true code> \else: <false code> \fi:</code>
<code>\if_cs_exist:w</code>	★	<code>\if_cs_exist:w <tokens> \cs_end: <true code> \else: <false code> \fi:</code>

Check if *<cs>* appears in the hash table or if the control sequence that can be formed from *<tokens>* appears in the hash table. The latter function does not turn the control sequence in question into `\scan_stop:!` This can be useful when dealing with control sequences which cannot be entered as a single token.

<code>\if_mode_horizontal:</code>	★	<code>\if_mode_horizontal: <true code> \else: <false code> \fi:</code>
<code>\if_mode_vertical:</code>	★	Execute <i><true code></i> if currently in horizontal mode, otherwise execute <i><false code></i> . Similar for the other functions.
<code>\if_mode_math:</code>	★	
<code>\if_mode_inner:</code>	★	

7 Starting a paragraph

`\mode_leave_vertical:`

New: 2017-07-04

`\mode_leave_vertical:`

Ensures that `\TeX` is not in vertical (inter-paragraph) mode. In horizontal or math mode this command has no effect, in vertical mode it switches to horizontal mode, and inserts a box of width `\parindent`, followed by the `\everypar` token list.

`\TeX`hackers note: This results in the contents of the `\everypar` token register being inserted, after `\mode_leave_vertical:` is complete. Notice that in contrast to the `\LaTeX 2ε` `\leavevmode` approach, no box is used by the method implemented here.

7.1 Debugging support

`\debug_on:n`
`\debug_off:n`

New: 2017-07-16
Updated: 2017-08-02

`\debug_on:n { <comma-separated list> }`
`\debug_off:n { <comma-separated list> }`

Turn on and off within a group various debugging code, some of which is also available as `expl3` load-time options. The items that can be used in the `<list>` are

- **`check-declarations`** that checks all `expl3` variables used were previously declared and that local/global variables (based on their name or on their first assignment) are only locally/globally assigned;
- **`check-expressions`** that checks integer, dimension, skip, and muskip expressions are not terminated prematurely;
- **`deprecation`** that makes soon-to-be-deprecated commands produce errors;
- **`log-functions`** that logs function definitions;
- **`all`** that does all of the above.

Providing these as switches rather than options allows testing code even if it relies on other packages: load all other packages, call `\debug_on:n`, and load the code that one is interested in testing. These functions can only be used in `\LaTeX 2ε` package mode loaded with `enable-debug` or another option implying it.

`\debug_suspend:`
`\debug_resume:`

New: 2017-11-28

`\debug_suspend: ... \debug_resume:`

Suppress (locally) errors and logging from `debug` commands, except for the **`deprecation`** errors or warnings. These pairs of commands can be nested. This can be used around pieces of code that are known to fail checks, if such failures should be ignored. See for instance `l3coffins`.

Part V

The l3expan package

Argument expansion

This module provides generic methods for expanding T_EX arguments in a systematic manner. The functions in this module all have prefix `exp`.

Not all possible variations are implemented for every base function. Instead only those that are used within the L^AT_EX3 kernel or otherwise seem to be of general interest are implemented. Consult the module description to find out which functions are actually defined. The next section explains how to define missing variants.

1 Defining new variants

The definition of variant forms for base functions may be necessary when writing new functions or when applying a kernel function in a situation that we haven't thought of before.

Internally preprocessing of arguments is done with functions of the form `\exp_....`. They all look alike, an example would be `\exp_args:NNo`. This function has three arguments, the first and the second are a single tokens, while the third argument should be given in braces. Applying `\exp_args:NNo` expands the content of third argument once before any expansion of the first and second arguments. If `\seq_gpush:No` was not defined it could be coded in the following way:

```
\exp_args:NNo \seq_gpush:Nn
  \g_file_name_stack
  { \l_tmpa_tl }
```

In other words, the first argument to `\exp_args:NNo` is the base function and the other arguments are preprocessed and then passed to this base function. In the example the first argument to the base function should be a single token which is left unchanged while the second argument is expanded once. From this example we can also see how the variants are defined. They just expand into the appropriate `\exp_` function followed by the desired base function, *e.g.*

```
\cs_generate_variant:Nn \seq_gpush:Nn { No }
```

results in the definition of `\seq_gpush:No`

```
\cs_new:Npn \seq_gpush:No { \exp_args:NNo \seq_gpush:Nn }
```

Providing variants in this way in style files is safe as the `\cs_generate_variant:Nn` function will only create new definitions if there is not already one available. Therefore adding such definition to later releases of the kernel will not make such style files obsolete.

The steps above may be automated by using the function `\cs_generate_variant:Nn`, described next.

2 Methods for defining variants

We recall the set of available argument specifiers.

- `N` is used for single-token arguments while `c` constructs a control sequence from its name and passes it to a parent function as an `N`-type argument.
- Many argument types extract or expand some tokens and provide it as an `n`-type argument, namely a braced multiple-token argument: `V` extracts the value of a variable, `v` extracts the value from the name of a variable, `n` uses the argument as it is, `o` expands once, `f` expands fully the front of the token list, `e` and `x` expand fully all tokens (differences are explained later).
- A few odd argument types remain: `T` and `F` for conditional processing, otherwise identical to `n`-type arguments, `p` for the parameter text in definitions, `w` for arguments with a specific syntax, and `D` to denote primitives that should not be used directly.

`\cs_generate_variant:Nn`
`\cs_generate_variant:cn`

Updated: 2017-11-28

`\cs_generate_variant:Nn` $\langle parent\ control\ sequence \rangle$ $\{ \langle variant\ argument\ specifiers \rangle \}$

This function is used to define argument-specifier variants of the $\langle parent\ control\ sequence \rangle$ for L^AT_EX3 code-level macros. The $\langle parent\ control\ sequence \rangle$ is first separated into the $\langle base\ name \rangle$ and $\langle original\ argument\ specifier \rangle$. The comma-separated list of $\langle variant\ argument\ specifiers \rangle$ is then used to define variants of the $\langle original\ argument\ specifier \rangle$ if these are not already defined. For each $\langle variant \rangle$ given, a function is created that expands its arguments as detailed and passes them to the $\langle parent\ control\ sequence \rangle$. So for example

```
\cs_set:Npn \foo:Nn #1#2 { code here }
\cs_generate_variant:Nn \foo:Nn { c }
```

creates a new function `\foo:cn` which expands its first argument into a control sequence name and passes the result to `\foo:Nn`. Similarly

```
\cs_generate_variant:Nn \foo:Nn { NV , cV }
```

generates the functions `\foo:NV` and `\foo:cV` in the same way. The `\cs_generate_variant:Nn` function can only be applied if the $\langle parent\ control\ sequence \rangle$ is already defined. If the $\langle parent\ control\ sequence \rangle$ is protected or if the $\langle variant \rangle$ involves any **x** argument, then the $\langle variant\ control\ sequence \rangle$ is also protected. The $\langle variant \rangle$ is created globally, as is any `\exp_args:N` $\langle variant \rangle$ function needed to carry out the expansion.

Only **n** and **N** arguments can be changed to other types. The only allowed changes are

- **c** variant of an **N** parent;
- **o**, **V**, **v**, **f**, **e**, or **x** variant of an **n** parent;
- **N**, **n**, **T**, **F**, or **p** argument unchanged.

This means the $\langle parent \rangle$ of a $\langle variant \rangle$ form is always unambiguous, even in cases where both an **n**-type parent and an **N**-type parent exist, such as for `\tl_count:n` and `\tl_count:N`.

For backward compatibility it is currently possible to make **n**, **o**, **V**, **v**, **f**, **e**, or **x**-type variants of an **N**-type argument or **N** or **c**-type variants of an **n**-type argument. Both are deprecated. The first because passing more than one token to an **N**-type argument will typically break the parent function's code. The second because programmers who use that most often want to access the value of a variable given its name, hence should use a **V**-type or **v**-type variant instead of **c**-type. In those cases, using the lower-level `\exp_args:No` or `\exp_args:Nc` functions explicitly is preferred to defining confusing variants.

3 Introducing the variants

The **V** type returns the value of a register, which can be one of `tl`, `clist`, `int`, `skip`, `dim`, `muskip`, or built-in T_EX registers. The **v** type is the same except it first creates a control sequence out of its argument before returning the value.

In general, the programmer should not need to be concerned with expansion control. When simply using the content of a variable, functions with a **V** specifier should be used. For those referred to by (cs)name, the **v** specifier is available for the same purpose. Only

when specific expansion steps are needed, such as when using delimited arguments, should the lower-level functions with `o` specifiers be employed.

The `e` type expands all tokens fully, starting from the first. More precisely the expansion is identical to that of T_EX’s `\message` (in particular `#` needs not be doubled). It was added in May 2018. In recent enough engines (starting around 2019) it relies on the primitive `\expanded` hence is fast. In older engines it is very much slower. As a result it should only be used in performance critical code if typical users will have a recent installation of the T_EX ecosystem.

The `x` type expands all tokens fully, starting from the first. In contrast to `e`, all macro parameter characters `#` must be doubled, and omitting this leads to low-level errors. In addition this type of expansion is not expandable, namely functions that have `x` in their signature do not themselves expand when appearing inside `x` or `e` expansion.

The `f` type is so special that it deserves an example. It is typically used in contexts where only expandable commands are allowed. Then `x`-expansion cannot be used, and `f`-expansion provides an alternative that expands the front of the token list as much as can be done in such contexts. For instance, say that we want to evaluate the integer expression `3 + 4` and pass the result 7 as an argument to an expandable function `\example:n`. For this, one should define a variant using `\cs_generate_variant:Nn \example:n { f }`, then do

```
\example:f { \int_eval:n { 3 + 4 } }
```

Note that `x`-expansion would also expand `\int_eval:n` fully to its result 7, but the variant `\example:x` cannot be expandable. Note also that `o`-expansion would not expand `\int_eval:n` fully to its result since that function requires several expansions. Besides the fact that `x`-expansion is protected rather than expandable, another difference between `f`-expansion and `x`-expansion is that `f`-expansion expands tokens from the beginning and stops as soon as a non-expandable token is encountered, while `x`-expansion continues expanding further tokens. Thus, for instance

```
\example:f { \int_eval:n { 1 + 2 } , \int_eval:n { 3 + 4 } }
```

results in the call

```
\example:n { 3 , \int_eval:n { 3 + 4 } }
```

while using `\example:x` or `\example:e` instead results in

```
\example:n { 3 , 7 }
```

at the cost of being protected (for `x` type) or very much slower in old engines (for `e` type). If you use `f` type expansion in conditional processing then you should stick to using TF type functions only as the expansion does not finish any `\if... \fi`: itself!

It is important to note that both `f`- and `o`-type expansion are concerned with the expansion of tokens from left to right in their arguments. In particular, `o`-type expansion applies to the first *token* in the argument it receives: it is conceptually similar to

```
\exp_after:wN <base function> \exp_after:wN { <argument> }
```

At the same time, `f`-type expansion stops at the *first* non-expandable token. This means for example that both

```
\tl_set:No \l_tmpa_tl { { \g_tmpb_tl } }
```

and

```
\tl_set:Nf \l_tmpa_tl { { \g_tmpb_tl } }
```

leave `\g_tmpb_tl` unchanged: `{` is the first token in the argument and is non-expandable. It is usually best to keep the following in mind when using variant forms.

- Variants with `x`-type arguments (that are fully expanded before being passed to the `n`-type base function) are never expandable even when the base function is. Such variants cannot work correctly in arguments that are themselves subject to expansion. Consider using `f` or `e` expansion.
- In contrast, `e` expansion (full expansion, almost like `x` except for the treatment of `#`) does not prevent variants from being expandable (if the base function is). The drawback is that `e` expansion is very much slower in old engines (before 2019). Consider using `f` expansion if that type of expansion is sufficient to perform the required expansion, or `x` expansion if the variant will not itself need to be expandable.
- Finally `f` expansion only expands the front of the token list, stopping at the first non-expandable token. This may fail to fully expand the argument.

When speed is essential (for functions that do very little work and whose variants are used numerous times in a document) the following considerations apply because internal functions for argument expansion come in two flavours, some faster than others.

- Arguments that might need expansion should come first in the list of arguments.
- Arguments that should consist of single tokens `N`, `c`, `V`, or `v` should come first among these.
- Arguments that appear after the first multi-token argument `n`, `f`, `e`, or `o` require slightly slower special processing to be expanded. Therefore it is best to use the optimized functions, namely those that contain only `N`, `c`, `V`, and `v`, and, in the last position, `o`, `f`, `e`, with possible trailing `N` or `n` or `T` or `F`, which are not expanded. Any `x`-type argument causes slightly slower processing.

4 Manipulating the first argument

These functions are described in detail: expansion of multiple tokens follows the same rules but is described in a shorter fashion.

```
\exp_args:Nc ★ \exp_args:Nc <function> {<tokens>}  
\exp_args:cc ★
```

This function absorbs two arguments (the `<function>` name and the `<tokens>`). The `<tokens>` are expanded until only characters remain, and are then turned into a control sequence. The result is inserted into the input stream *after* reinsertion of the `<function>`. Thus the `<function>` may take more than one argument: all others are left unchanged.

The `:cc` variant constructs the `<function>` name in the same manner as described for the `<tokens>`.

T_EXhackers note: Protected macros that appear in a `c`-type argument are expanded despite being protected; `\exp_not:n` also has no effect. An internal error occurs if non-characters or active characters remain after full expansion, as the conversion to a control sequence is not possible.

`\exp_args:No` ★ `\exp_args:No` $\langle function \rangle$ $\{\langle tokens \rangle\}$...

This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are expanded once, and the result is inserted in braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

`\exp_args:Nv` ★ `\exp_args:Nv` $\langle function \rangle$ $\langle variable \rangle$

This function absorbs two arguments (the names of the $\langle function \rangle$ and the $\langle variable \rangle$). The content of the $\langle variable \rangle$ are recovered and placed inside braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

`\exp_args:Nv` ★ `\exp_args:Nv` $\langle function \rangle$ $\{\langle tokens \rangle\}$

This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are expanded until only characters remain, and are then turned into a control sequence. This control sequence should be the name of a $\langle variable \rangle$. The content of the $\langle variable \rangle$ are recovered and placed inside braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

TeXhackers note: Protected macros that appear in a v-type argument are expanded despite being protected; `\exp_not:n` also has no effect. An internal error occurs if non-characters or active characters remain after full expansion, as the conversion to a control sequence is not possible.

`\exp_args:Ne` ★ `\exp_args:Ne` $\langle function \rangle$ $\{\langle tokens \rangle\}$

New: 2018-05-15

This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$) and exhaustively expands the $\langle tokens \rangle$. The result is inserted in braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

TeXhackers note: This relies on the `\expanded` primitive when available (in LuaTeX and starting around 2019 in other engines). Otherwise it uses some fall-back code that is very much slower. As a result it should only be used in performance-critical code if typical users have a recent installation of the TeX ecosystem.

`\exp_args:Nf` ★ `\exp_args:Nf` $\langle function \rangle$ $\{\langle tokens \rangle\}$

This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are fully expanded until the first non-expandable token is found (if that is a space it is removed), and the result is inserted in braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

<code>\exp_args:Nx</code>	<code>\exp_args:Nx</code>	$\langle function \rangle$	$\{\langle tokens \rangle\}$
---------------------------	---------------------------	----------------------------	------------------------------

This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$) and exhaustively expands the $\langle tokens \rangle$. The result is inserted in braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

5 Manipulating two arguments

<code>\exp_args:NNc</code>	<code>\exp_args:NNc</code>	$\langle token_1 \rangle$	$\langle token_2 \rangle$	$\{\langle tokens \rangle\}$
----------------------------	----------------------------	---------------------------	---------------------------	------------------------------

These optimized functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments.

`\exp_args:NNv` *
`\exp_args:NNe` *
`\exp_args:NNf` *
`\exp_args:Ncc` *
`\exp_args:Nco` *
`\exp_args:NcV` *
`\exp_args:Ncv` *
`\exp_args:Ncf` *
`\exp_args:NVV` *

Updated: 2018-05-15

<code>\exp_args:Nnc</code>	<code>\exp_args:Noo</code>	$\langle token \rangle$	$\{\langle tokens_1 \rangle\}$	$\{\langle tokens_2 \rangle\}$
----------------------------	----------------------------	-------------------------	--------------------------------	--------------------------------

These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions need slower processing.

`\exp_args:Noc` *
`\exp_args:Noo` *
`\exp_args:Nof` *
`\exp_args:NVo` *
`\exp_args:Nfo` *
`\exp_args:Nff` *
`\exp_args:Nee` *

Updated: 2018-05-15

<code>\exp_args:NNx</code>	<code>\exp_args:NNx</code>	$\langle token_1 \rangle$	$\langle token_2 \rangle$	$\{\langle tokens \rangle\}$
----------------------------	----------------------------	---------------------------	---------------------------	------------------------------

These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions are not expandable due to their x-type argument.

`\exp_args:Ncx`
`\exp_args:Nnx`
`\exp_args:Nox`
`\exp_args:Nxo`
`\exp_args:Nxx`

6 Manipulating three arguments

<code>\exp_args:NNNo</code>	*	<code>\exp_args:NNNo</code>	$\langle token_1 \rangle$	$\langle token_2 \rangle$	$\langle token_3 \rangle$	$\{\langle tokens \rangle\}$
<code>\exp_args:NNNV</code>	*	These optimized functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i>				
<code>\exp_args:Nccc</code>	*					
<code>\exp_args:NcNc</code>	*					
<code>\exp_args:NcNo</code>	*					
<code>\exp_args:Ncco</code>	*					

<code>\exp_args:NNcf</code>	*	<code>\exp_args:NNoo</code>	$\langle token_1 \rangle$	$\langle token_2 \rangle$	$\{\langle token_3 \rangle\}$	$\{\langle tokens \rangle\}$
<code>\exp_args:NNno</code>	*	These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i> These functions need slower processing.				
<code>\exp_args:NNnV</code>	*					
<code>\exp_args:NNoo</code>	*					
<code>\exp_args:NNVV</code>	*					
<code>\exp_args:Ncno</code>	*					
<code>\exp_args:NcnV</code>	*					
<code>\exp_args:Ncoo</code>	*					
<code>\exp_args:NcVV</code>	*					
<code>\exp_args:Nnnc</code>	*					
<code>\exp_args:Nnno</code>	*					
<code>\exp_args:Nnnf</code>	*					
<code>\exp_args:Nnff</code>	*					
<code>\exp_args:Nooo</code>	*					
<code>\exp_args:Noof</code>	*					
<code>\exp_args:Nffo</code>	*					
<code>\exp_args:Neee</code>	*					

<code>\exp_args:NNNx</code>	<code>\exp_args:NNNx</code>	$\langle token_1 \rangle$	$\langle token_2 \rangle$	$\{\langle tokens_1 \rangle\}$	$\{\langle tokens_2 \rangle\}$
<code>\exp_args:NNnx</code>	These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i>				
<code>\exp_args:NNox</code>					
<code>\exp_args:Nccx</code>					
<code>\exp_args:Ncnx</code>					
<code>\exp_args:NNnx</code>					
<code>\exp_args:Nnox</code>					
<code>\exp_args:Noox</code>					

New: 2015-08-12

7 Unbraced expansion

```

\exp_last_unbraced:No  *
\exp_last_unbraced:Nv  *
\exp_last_unbraced:Nf  *
\exp_last_unbraced:NNo *
\exp_last_unbraced:NNv *
\exp_last_unbraced:NNf *
\exp_last_unbraced:Nco *
\exp_last_unbraced:NcV *
\exp_last_unbraced:Nno *
\exp_last_unbraced:Noo *
\exp_last_unbraced:Nfo *
\exp_last_unbraced:NNNo *
\exp_last_unbraced:NNNV *
\exp_last_unbraced:NNNf *
\exp_last_unbraced:NnNo *
\exp_last_unbraced:NNNNo *
\exp_last_unbraced:NNNNf *

```

Updated: 2018-05-15

```
\exp_last_unbraced:Nno <token> {\tokens_1} {\tokens_2}
```

These functions absorb the number of arguments given by their specification, carry out the expansion indicated and leave the results in the input stream, with the last argument not surrounded by the usual braces. Of these, the :Nno, :Noo, :Nfo and :NnNo variants need slower processing.

T_EXhackers note: As an optimization, the last argument is unbraced by some of those functions before expansion. This can cause problems if the argument is empty: for instance, `\exp_last_unbraced:Nf \foo_bar:w { } \q_stop` leads to an infinite loop, as the quark is f-expanded.

```
\exp_last_unbraced:Nx \exp_last_unbraced:Nx <function> {\tokens}
```

This function fully expands the `<tokens>` and leaves the result in the input stream after reinsertion of the `<function>`. This function is not expandable.

```
\exp_last_two_unbraced:Noo * \exp_last_two_unbraced:Noo <token> {\tokens_1} {\tokens_2}
```

This function absorbs three arguments and expands the second and third once. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments, which are not wrapped in braces. This function needs special (slower) processing.

```
\exp_after:wN * \exp_after:wN <token_1> <token_2>
```

Carries out a single expansion of `<token_2>` (which may consume arguments) prior to the expansion of `<token_1>`. If `<token_2>` has no expansion (for example, if it is a character) then it is left unchanged. It is important to notice that `<token_1>` may be *any* single token, including group-opening and -closing tokens (`{` or `}` assuming normal T_EX category codes). Unless specifically required this should be avoided: expansion should be carried out using an appropriate argument specifier variant or the appropriate `\exp_arg:N` function.

T_EXhackers note: This is the T_EX primitive `\expandafter` renamed.

8 Preventing expansion

Despite the fact that the following functions are all about preventing expansion, they're designed to be used in an expandable context and hence are all marked as being 'expand-

able' since they themselves disappear after the expansion has completed.

`\exp_not:N` ★ `\exp_not:N` $\langle token \rangle$

Prevents expansion of the $\langle token \rangle$ in a context where it would otherwise be expanded, for example an **x**-type argument or the first token in an **o** or **e** or **f** argument.

T_EXhackers note: This is the T_EX `\noexpand` primitive. It only prevents expansion. At the beginning of an **f**-type argument, a space $\langle token \rangle$ is removed even if it appears as `\exp_not:N \c_space_token`. In an **x**-expanding definition (`\cs_new:Npx`), a macro parameter introduces an argument even if it appears as `\exp_not:N # 1`. This differs from `\exp_not:n`.

`\exp_not:c` ★ `\exp_not:c` $\{\langle tokens \rangle\}$

Expands the $\langle tokens \rangle$ until only characters remain, and then converts this into a control sequence. Further expansion of this control sequence is then inhibited using `\exp_not:N`.

T_EXhackers note: Protected macros that appear in a **c**-type argument are expanded despite being protected; `\exp_not:n` also has no effect. An internal error occurs if non-characters or active characters remain after full expansion, as the conversion to a control sequence is not possible.

`\exp_not:n` ★ `\exp_not:n` $\{\langle tokens \rangle\}$

Prevents expansion of the $\langle tokens \rangle$ in an **e** or **x**-type argument. In all other cases the $\langle tokens \rangle$ continue to be expanded, for example in the input stream or in other types of arguments such as **c**, **f**, **v**. The argument of `\exp_not:n` *must* be surrounded by braces.

T_EXhackers note: This is the ε -T_EX `\unexpanded` primitive. In an **x**-expanding definition (`\cs_new:Npx`), `\exp_not:n {\#1}` is equivalent to `##1` rather than to `#1`, namely it inserts the two characters `#` and `1`. In an **e**-type argument `\exp_not:n {\#}` is equivalent to `#`, namely it inserts the character `#`.

`\exp_not:o` ★ `\exp_not:o` $\{\langle tokens \rangle\}$

Expands the $\langle tokens \rangle$ once, then prevents any further expansion in **x**-type or **e**-type arguments using `\exp_not:n`.

`\exp_not:V` ★ `\exp_not:V` $\langle variable \rangle$

Recovers the content of the $\langle variable \rangle$, then prevents expansion of this material in **x**-type or **e**-type arguments using `\exp_not:n`.

<hr/> <hr/>	<code>\exp_not:v</code> *	<code>\exp_not:v {<tokens>}</code>	Expands the <i><tokens></i> until only characters remains, and then converts this into a control sequence which should be a <i><variable></i> name. The content of the <i><variable></i> is recovered, and further expansion in <i>x</i> -type or <i>e</i> -type arguments is prevented using <code>\exp_not:n</code> .
<hr/> <hr/>	<code>\exp_not:e</code> *	<code>\exp_not:e {<tokens>}</code>	Expands <i><tokens></i> exhaustively, then protects the result of the expansion (including any tokens which were not expanded) from further expansion in <i>e</i> or <i>x</i> -type arguments using <code>\exp_not:n</code> . This is very rarely useful but is provided for consistency.
<hr/> <hr/>	<code>\exp_not:f</code> *	<code>\exp_not:f {<tokens>}</code>	Expands <i><tokens></i> fully until the first unexpandable token is found (if it is a space it is removed). Expansion then stops, and the result of the expansion (including any tokens which were not expanded) is protected from further expansion in <i>x</i> -type or <i>e</i> -type arguments using <code>\exp_not:n</code> .
<hr/> <hr/>	<code>\exp_stop_f:</code> *	<code>\foo_bar:f { <tokens> \exp_stop_f: <more tokens> }</code>	This function terminates an <i>f</i> -type expansion. Thus if a function <code>\foo_bar:f</code> starts an <i>f</i> -type expansion and all of <i><tokens></i> are expandable <code>\exp_stop_f:</code> terminates the expansion of tokens even if <i><more tokens></i> are also expandable. The function itself is an implicit space token. Inside an <i>x</i> -type expansion, it retains its form, but when typeset it produces the underlying space (␣).

Updated: 2011-06-03

9 Controlled expansion

The `expl3` language makes all efforts to hide the complexity of `TeX` expansion from the programmer by providing concepts that evaluate/expand arguments of functions prior to calling the “base” functions. Thus, instead of using many `\expandafter` calls and other trickery it is usually a matter of choosing the right variant of a function to achieve a desired result.

Of course, deep down `TeX` is using expansion as always and there are cases where a programmer needs to control that expansion directly; typical situations are basic data manipulation tools. This section documents the functions for that level. These commands are used throughout the kernel code, but we hope that outside the kernel there will be little need to resort to them. Instead the argument manipulation methods document above should usually be sufficient.

While `\exp_after:wN` expands one token (out of order) it is sometimes necessary to expand several tokens in one go. The next set of commands provide this functionality. Be aware that it is absolutely required that the programmer has full control over the tokens to be expanded, i.e., it is not possible to use these functions to expand unknown input as part of *<expandable-tokens>* as that will break badly if unexpandable tokens are encountered in that place!

<code>\exp:w</code>	★	<code>\exp:w <expandable tokens> \exp_end:</code>
<code>\exp_end:</code>	★	Expands <code><expandable-tokens></code> until reaching <code>\exp_end:</code> at which point expansion stops. The full expansion of <code><expandable tokens></code> has to be empty. If any token in <code><expandable tokens></code> or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result <code>\exp_end:</code> will be misinterpreted later on. ³
New: 2015-08-23		

In typical use cases the `\exp_end:` is hidden somewhere in the replacement text of `<expandable-tokens>` rather than being on the same expansion level than `\exp:w`, e.g., you may see code such as

```
\exp:w \@@_case:NnTF #1 {#2} { } { }
```

where somewhere during the expansion of `\@@_case:NnTF` the `\exp_end:` gets generated.

T_EXhackers note: The current implementation uses `\romannumeral` hence ignores space tokens and explicit signs + and - in the expansion of the `<expandable tokens>`, but this should not be relied upon.

<code>\exp:w</code>	★	<code>\exp:w <expandable-tokens> \exp_end_continue_f:w <further-tokens></code>
<code>\exp_end_continue_f:w</code>	★	Expands <code><expandable-tokens></code> until reaching <code>\exp_end_continue_f:w</code> at which point expansion continues as an f-type expansion expanding <code><further-tokens></code> until an unexpandable token is encountered (or the f-type expansion is explicitly terminated by <code>\exp_stop_f:</code>). As with all f-type expansions a space ending the expansion gets removed. The full expansion of <code><expandable-tokens></code> has to be empty. If any token in <code><expandable-tokens></code> or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result <code>\exp_end_continue_f:w</code> will be misinterpreted later on. ⁴
New: 2015-08-23		

The full expansion of `<expandable-tokens>` has to be empty. If any token in `<expandable-tokens>` or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result `\exp_end_continue_f:w` will be misinterpreted later on.⁴

In typical use cases `<expandable-tokens>` contains no tokens at all, e.g., you will see code such as

```
\exp_after:wN { \exp:w \exp_end_continue_f:w #2 }
```

where the `\exp_after:wN` triggers an f-expansion of the tokens in #2. For technical reasons this has to happen using two tokens (if they would be hidden inside another command `\exp_after:wN` would only expand the command but not trigger any additional f-expansion).

You might wonder why there are two different approaches available, after all the effect of

```
\exp:w <expandable-tokens> \exp_end:
```

can be alternatively achieved through an f-type expansion by using `\exp_stop_f:`, i.e.

```
\exp:w \exp_end_continue_f:w <expandable-tokens> \exp_stop_f:
```

The reason is simply that the first approach is slightly faster (one less token to parse and less expansion internally) so in places where such performance really matters and where we want to explicitly stop the expansion at a defined point the first form is preferable.

³Due to the implementation you might get the character in position 0 in the current font (typically “”) in the output without any error message!

⁴In this particular case you may get a character into the output as well as an error message.

<code>\exp:w</code>	★
<code>\exp_end_continue_f:nw</code>	★

New: 2015-08-23

`\exp:w` *<expandable-tokens>* `\exp_end_continue_f:nw` *<further-tokens>*

The difference to `\exp_end_continue_f:w` is that we first we pick up an argument which is then returned to the input stream. If *<further-tokens>* starts with space tokens then these space tokens are removed while searching for the argument. If it starts with a brace group then the braces are removed. Thus such spaces or braces will not terminate the f-type expansion.

10 Internal functions

`\::n` `\cs_new:Npn \exp_args:Ncof { \::c \::o \::f \::: }`

`\::N` Internal forms for the base expansion types. These names do *not* conform to the general \LaTeX 3 approach as this makes them more readily visible in the log and so forth. They should not be used outside this module.

`\::c`
`\::o`
`\::e`
`\::f`
`\::x`
`\::v`
`\::V`
`\:::`

`\::o_unbraced` `\cs_new:Npn \exp_last_unbraced:Nno { \::n \::o_unbraced \::: }`

`\::e_unbraced` Internal forms for the expansion types which leave the terminal argument unbraced. These names do *not* conform to the general \LaTeX 3 approach as this makes them more readily visible in the log and so forth. They should not be used outside this module.

`\::f_unbraced`
`\::x_unbraced`
`\::v_unbraced`
`\::V_unbraced`

Part VI

The l3quark package

Quarks

Two special types of constants in L^AT_EX3 are “quarks” and “scan marks”. By convention all constants of type quark start out with `\q_`, and scan marks start with `\s_`.

1 Quarks

Quarks are control sequences that expand to themselves and should therefore *never* be executed directly in the code. This would result in an endless loop!

They are meant to be used as delimiter in weird functions, the most common use case being the ‘stop token’ (*i.e.* `\q_stop`). For example, when writing a macro to parse a user-defined date

```
\date_parse:n {19/June/1981}
```

one might write a command such as

```
\cs_new:Npn \date_parse:n #1 { \date_parse_aux:w #1 \q_stop }
\cs_new:Npn \date_parse_aux:w #1 / #2 / #3 \q_stop
{ <do something with the date> }
```

Quarks are sometimes also used as error return values for functions that receive erroneous input. For example, in the function `\prop_get:NnN` to retrieve a value stored in some key of a property list, if the key does not exist then the return value is the quark `\q_no_value`. As mentioned above, such quarks are extremely fragile and it is imperative when using such functions that code is carefully written to check for pathological cases to avoid leakage of a quark into an uncontrolled environment.

Quarks also permit the following ingenious trick when parsing tokens: when you pick up a token in a temporary variable and you want to know whether you have picked up a particular quark, all you have to do is compare the temporary variable to the quark using `\tl_if_eq:NNTF`. A set of special quark testing functions is set up below. All the quark testing functions are expandable although the ones testing only single tokens are much faster. An example of the quark testing functions and their use in recursion can be seen in the implementation of `\clist_map_function:NN`.

2 Defining quarks

`\quark_new:N`

`\quark_new:N <quark>`

Creates a new `<quark>` which expands only to `<quark>`. The `<quark>` is defined globally, and an error message is raised if the name was already taken.

`\q_stop`

Used as a marker for delimited arguments, such as

```
\cs_set:Npn \tmp:w #1#2 \q_stop {#1}
```

<u><u>\q_mark</u></u>	Used as a marker for delimited arguments when <code>\q_stop</code> is already in use.
<u><u>\q_nil</u></u>	Quark to mark a null value in structured variables or functions. Used as an end delimiter when this may itself need to be tested (in contrast to <code>\q_stop</code> , which is only ever used as a delimiter).
<u><u>\q_no_value</u></u>	A canonical value for a missing value, when one is requested from a data structure. This is therefore used as a “return” value by functions such as <code>\prop_get:NnN</code> if there is no data to return.

3 Quark tests

The method used to define quarks means that the single token (N) tests are faster than the multi-token (n) tests. The latter should therefore only be used when the argument can definitely take more than a single token.

<u><u>\quark_if_nil_p:N</u></u> *	<code>\quark_if_nil_p:N <token></code>
<u><u>\quark_if_nil:NTF</u></u> *	<code>\quark_if_nil:NTF <token> {\true code} {\false code}</code>
	Tests if the <code><token></code> is equal to <code>\q_nil</code> .
<u><u>\quark_if_nil_p:n</u></u> *	<code>\quark_if_nil_p:n {\token list}</code>
<u><u>\quark_if_nil_p:(o V)</u></u> *	<code>\quark_if_nil:nTF {\token list} {\true code} {\false code}</code>
<u><u>\quark_if_nil:nTF</u></u> *	Tests if the <code><token list></code> contains only <code>\q_nil</code> (distinct from <code><token list></code> being empty or
<u><u>\quark_if_nil:(o V)TF</u></u> *	containing <code>\q_nil</code> plus one or more other tokens).
<u><u>\quark_if_no_value_p:N</u></u> *	<code>\quark_if_no_value_p:N <token></code>
<u><u>\quark_if_no_value_p:c</u></u> *	<code>\quark_if_no_value:NTF <token> {\true code} {\false code}</code>
<u><u>\quark_if_no_value:NTF</u></u> *	Tests if the <code><token></code> is equal to <code>\q_no_value</code> .
<u><u>\quark_if_no_value:cTF</u></u> *	
<u><u>\quark_if_no_value_p:n</u></u> *	<code>\quark_if_no_value_p:n {\token list}</code>
<u><u>\quark_if_no_value:nTF</u></u> *	<code>\quark_if_no_value:nTF {\token list} {\true code} {\false code}</code>
	Tests if the <code><token list></code> contains only <code>\q_no_value</code> (distinct from <code><token list></code> being empty or containing <code>\q_no_value</code> plus one or more other tokens).

4 Recursion

This module provides a uniform interface to intercepting and terminating loops as when one is doing tail recursion. The building blocks follow below and an example is shown in Section 5.

<u><u>\q_recursion_tail</u></u>	This quark is appended to the data structure in question and appears as a real element there. This means it gets any list separators around it.
---------------------------------	---

<code>\q_recursion_stop</code>	This quark is added <i>after</i> the data structure. Its purpose is to make it possible to terminate the recursion at any point easily.
--------------------------------	---

<code>\quark_if_recursion_tail_stop:N *</code>	<code>\quark_if_recursion_tail_stop:N <token></code>
--	--

Tests if $\langle token \rangle$ contains only the marker `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items.

<code>\quark_if_recursion_tail_stop:n *</code>	<code>\quark_if_recursion_tail_stop:n {<token list>}</code>
<code>\quark_if_recursion_tail_stop:o *</code>	

Updated: 2011-09-06

Tests if the $\langle token list \rangle$ contains only `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items.

<code>\quark_if_recursion_tail_stop_do:Nn *</code>	<code>\quark_if_recursion_tail_stop_do:Nn <token> {<insertion>}</code>
--	--

Tests if $\langle token \rangle$ contains only the marker `\q_recursion_tail`, and if so uses `\use_i_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items. The $\langle insertion \rangle$ code is then added to the input stream after the recursion has ended.

<code>\quark_if_recursion_tail_stop_do:nn *</code>	<code>\quark_if_recursion_tail_stop_do:nn {<token list>} {<insertion>}</code>
<code>\quark_if_recursion_tail_stop_do:on *</code>	

Updated: 2011-09-06

Tests if the $\langle token list \rangle$ contains only `\q_recursion_tail`, and if so uses `\use_i_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items. The $\langle insertion \rangle$ code is then added to the input stream after the recursion has ended.

<code>\quark_if_recursion_tail_break:NN *</code>	<code>\quark_if_recursion_tail_break:nN {<token list>}</code>
<code>\quark_if_recursion_tail_break:nN *</code>	<code>\<type>_map_break:</code>

New: 2018-04-10

Tests if $\langle token list \rangle$ contains only `\q_recursion_tail`, and if so terminates the recursion using `\<type>_map_break:.` The recursion end should be marked by `\prg_break_point:Nn \<type>_map_break:.`

5 An example of recursion with quarks

Quarks are mainly used internally in the `expl3` code to define recursion functions such as `\tl_map_inline:nn` and so on. Here is a small example to demonstrate how to

use quarks in this fashion. We shall define a command called `\my_map_dbl:nn` which takes a token list and applies an operation to every *pair* of tokens. For example, `\my_map_dbl:nn {abcd} {[--#1--#2--]~}` would produce “[-a-b-] [-c-d-]”. Using quarks to define such functions simplifies their logic and ensures robustness in many cases.

Here’s the definition of `\my_map_dbl:nn`. First of all, define the function that does the processing based on the inline function argument `#2`. Then initiate the recursion using an internal function. The token list `#1` is terminated using `\q_recursion_tail`, with delimiters according to the type of recursion (here a pair of `\q_recursion_tail`), concluding with `\q_recursion_stop`. These quarks are used to mark the end of the token list being operated upon.

```
\cs_new:Npn \my_map_dbl:nn #1#2
{
  \cs_set:Npn \__my_map_dbl_fn:nn ##1 ##2 {#2}
  \__my_map_dbl:nn #1 \q_recursion_tail \q_recursion_tail
  \q_recursion_stop
}
```

The definition of the internal recursion function follows. First check if either of the input tokens are the termination quarks. Then, if not, apply the inline function to the two arguments.

```
\cs_new:Nn \__my_map_dbl:nn
{
  \quark_if_recursion_tail_stop:n {#1}
  \quark_if_recursion_tail_stop:n {#2}
  \__my_map_dbl_fn:nn {#1} {#2}
}
```

Finally, recurse:

```
\__my_map_dbl:nn
}
```

Note that contrarily to L^AT_EX3 built-in mapping functions, this mapping function cannot be nested, since the second map would overwrite the definition of `__my_map_dbl_fn:nn`.

6 Scan marks

Scan marks are control sequences set equal to `\scan_stop:`, hence never expand in an expansion context and are (largely) invisible if they are encountered in a typesetting context.

Like quarks, they can be used as delimiters in weird functions and are often safer to use for this purpose. Since they are harmless when executed by T_EX in non-expandable contexts, they can be used to mark the end of a set of instructions. This allows to skip to that point if the end of the instructions should not be performed (see l3regex).

`\scan_new:N`

New: 2018-04-01

`\scan_new:N` *<scan mark>*

Creates a new *<scan mark>* which is set equal to `\scan_stop:`. The *<scan mark>* is defined globally, and an error message is raised if the name was already taken by another scan mark.

<hr/> \s_stop <hr/>	Used at the end of a set of instructions, as a marker that can be jumped to using \use_
New: 2018-04-01	none_delimit_by_s_stop:w.

<hr/> \use_none_delimit_by_s_stop:w ★	\use_none_delimit_by_s_stop:w <i><tokens></i> \s_stop
--	---

New: 2018-04-01

Removes the *<tokens>* and **\s_stop** from the input stream. This leads to a low-level T_EX error if **\s_stop** is absent.

Part VII

The l3tl package

Token lists

T_EX works with tokens, and L^AT_EX3 therefore provides a number of functions to deal with lists of tokens. Token lists may be present directly in the argument to a function:

```
\foo:n { a collection of \tokens }
```

or may be stored in a so-called “token list variable”, which have the suffix `tl`: a token list variable can also be used as the argument to a function, for example

```
\foo:N \l_some_tl
```

In both cases, functions are available to test and manipulate the lists of tokens, and these have the module prefix `tl`. In many cases, functions which can be applied to token list variables are paired with similar functions for application to explicit lists of tokens: the two “views” of a token list are therefore collected together here.

A token list (explicit, or stored in a variable) can be seen either as a list of “items”, or a list of “tokens”. An item is whatever `\use:n` would grab as its argument: a single non-space token or a brace group, with optional leading explicit space characters (each item is thus itself a token list). A token is either a normal `N` argument, or `␣`, `{`, or `}` (assuming normal T_EX category codes). Thus for example

```
{ Hello } ~ world
```

contains six items (Hello, w, o, r, l and d), but thirteen tokens (`{`, H, e, l, l, o, `}`, `␣`, w, o, r, l and d). Functions which act on items are often faster than their analogue acting directly on tokens.

1 Creating and initialising token list variables

<code>\tl_new:N</code>	<code>\tl_new:N <tl var></code>
<code>\tl_new:c</code>	

Creates a new `<tl var>` or raises an error if the name is already taken. The declaration is global. The `<tl var>` is initially empty.

<code>\tl_const:Nn</code>	<code>\tl_const:Nn <tl var> {<token list>}</code>
<code>\tl_const:(Nx cn cx)</code>	

Creates a new constant `<tl var>` or raises an error if the name is already taken. The value of the `<tl var>` is set globally to the `<token list>`.

<code>\tl_clear:N</code>	<code>\tl_clear:N <tl var></code>
<code>\tl_clear:c</code>	
<code>\tl_gclear:N</code>	Cleares all entries from the <code><tl var></code> .
<code>\tl_gclear:c</code>	

<hr/>	
<code>\tl_clear_new:N</code>	<code>\tl_clear_new:N <tl var></code>
<code>\tl_clear_new:c</code>	
<code>\tl_gclear_new:N</code>	Ensures that the <code><tl var></code> exists globally by applying <code>\tl_new:N</code> if necessary, then applies
<code>\tl_gclear_new:c</code>	<code>\tl_(g)clear:N</code> to leave the <code><tl var></code> empty.
<hr/>	
<code>\tl_set_eq:NN</code>	<code>\tl_set_eq:NN <tl var_1> <tl var_2></code>
<code>\tl_set_eq:(cN Nc cc)</code>	Sets the content of <code><tl var_1></code> equal to that of <code><tl var_2></code> .
<code>\tl_gset_eq:NN</code>	
<code>\tl_gset_eq:(cN Nc cc)</code>	
<hr/>	
<code>\tl_concat:NNN</code>	<code>\tl_concat:NNN <tl var_1> <tl var_2> <tl var_3></code>
<code>\tl_concat:ccc</code>	
<code>\tl_gconcat:NNN</code>	Concatenates the content of <code><tl var_2></code> and <code><tl var_3></code> together and saves the result in
<code>\tl_gconcat:ccc</code>	<code><tl var_1></code> . The <code><tl var_2></code> is placed at the left side of the new token list.
<hr/>	
New: 2012-05-18	
<hr/>	
<code>\tl_if_exist_p:N *</code>	<code>\tl_if_exist_p:N <tl var></code>
<code>\tl_if_exist_p:c *</code>	<code>\tl_if_exist:NTF <tl var> {<true code>} {<false code>}</code>
<code>\tl_if_exist:N\overline{TF} *</code>	
<code>\tl_if_exist:c\overline{TF} *</code>	Tests whether the <code><tl var></code> is currently defined. This does not check that the <code><tl var></code> really is a token list variable.
<hr/>	
New: 2012-03-03	

2 Adding data to token list variables

<hr/>	
<code>\tl_set:Nn</code>	<code>\tl_set:Nn <tl var> {<tokens>}</code>
<code>\tl_set:(NV Nv No Nf Nx cn cV cv co cf cx)</code>	
<code>\tl_gset:Nn</code>	
<code>\tl_gset:(NV Nv No Nf Nx cn cV cv co cf cx)</code>	
<hr/>	
Sets <code><tl var></code> to contain <code><tokens></code> , removing any previous content from the variable.	
<hr/>	
<code>\tl_put_left:Nn</code>	<code>\tl_put_left:Nn <tl var> {<tokens>}</code>
<code>\tl_put_left:(NV No Nx cn cV co cx)</code>	
<code>\tl_gput_left:Nn</code>	
<code>\tl_gput_left:(NV No Nx cn cV co cx)</code>	
<hr/>	
Appends <code><tokens></code> to the left side of the current content of <code><tl var></code> .	
<hr/>	
<code>\tl_put_right:Nn</code>	<code>\tl_put_right:Nn <tl var> {<tokens>}</code>
<code>\tl_put_right:(NV No Nx cn cV co cx)</code>	
<code>\tl_gput_right:Nn</code>	
<code>\tl_gput_right:(NV No Nx cn cV co cx)</code>	
<hr/>	
Appends <code><tokens></code> to the right side of the current content of <code><tl var></code> .	

3 Modifying token list variables

```
\tl_replace_once:Nnn
\tl_replace_once:cnn
\tl_greplace_once:Nnn
\tl_greplace_once:cnn
```

Updated: 2011-08-11

```
\tl_replace_once:Nnn <tl var> {{<old tokens>}} {{<new tokens>}}
```

Replaces the first (leftmost) occurrence of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_replace_all:Nnn
\tl_replace_all:cnn
\tl_greplace_all:Nnn
\tl_greplace_all:cnn
```

Updated: 2011-08-11

```
\tl_replace_all:Nnn <tl var> {{<old tokens>}} {{<new tokens>}}
```

Replaces all occurrences of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<old tokens>* may remain after the replacement (see `\tl_remove_all:Nn` for an example).

```
\tl_remove_once:Nn
\tl_remove_once:cn
\tl_gremove_once:Nn
\tl_gremove_once:cn
```

Updated: 2011-08-11

```
\tl_remove_once:Nn <tl var> {{<tokens>}}
```

Removes the first (leftmost) occurrence of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_remove_all:Nn
\tl_remove_all:cn
\tl_gremove_all:Nn
\tl_gremove_all:cn
```

Updated: 2011-08-11

```
\tl_remove_all:Nn <tl var> {{<tokens>}}
```

Removes all occurrences of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<tokens>* may remain after the removal, for instance,

```
\tl_set:Nn \l_tmpa_tl {abbccd} \tl_remove_all:Nn \l_tmpa_tl {bc}
```

results in `\l_tmpa_tl` containing `abcd`.

4 Reassigning token list category codes

These functions allow the rescanning of tokens: re-apply T_EX's tokenization process to apply category codes different from those in force when the tokens were absorbed. Whilst this functionality is supported, it is often preferable to find alternative approaches to achieving outcomes rather than rescanning tokens (for example construction of token lists token-by-token with intervening category code changes or using `\char_generate:nn`).

<code>\tl_set_rescan:Nnn</code>	<code>\tl_set_rescan:Nnn <tl var> {<setup>} {<tokens>}</code>
<code>\tl_set_rescan:(Nno Nnx cnn cno cnx)</code>	
<code>\tl_gset_rescan:Nnn</code>	
<code>\tl_gset_rescan:(Nno Nnx cnn cno cnx)</code>	

Updated: 2015-08-11

Sets $\langle tl\ var \rangle$ to contain $\langle tokens \rangle$, applying the category code régime specified in the $\langle setup \rangle$ before carrying out the assignment. (Category codes applied to tokens not explicitly covered by the $\langle setup \rangle$ are those in force at the point of use of `\tl_set_rescan:Nnn`.) This allows the $\langle tl\ var \rangle$ to contain material with category codes other than those that apply when $\langle tokens \rangle$ are absorbed. The $\langle setup \rangle$ is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_rescan:nn`.

T_EXhackers note: The $\langle tokens \rangle$ are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user $\langle setup \rangle$), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file.

<code>\tl_rescan:nn</code>	<code>\tl_rescan:nn {<setup>} {<tokens>}</code>
----------------------------	---

Updated: 2015-08-11

Rescans $\langle tokens \rangle$ applying the category code régime specified in the $\langle setup \rangle$, and leaves the resulting tokens in the input stream. (Category codes applied to tokens not explicitly covered by the $\langle setup \rangle$ are those in force at the point of use of `\tl_rescan:nn`.) The $\langle setup \rangle$ is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_set_rescan:Nnn`, which is more robust than using `\tl_set:Nn` in the $\langle tokens \rangle$ argument of `\tl_rescan:nn`.

T_EXhackers note: The $\langle tokens \rangle$ are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user $\langle setup \rangle$), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file.

5 Token list conditionals

<code>\tl_if_blank_p:n</code>	★	<code>\tl_if_blank_p:n {<token list>}</code>
<code>\tl_if_blank_p:(e V o)</code>	★	<code>\tl_if_blank:nTF {<token list>} {<true code>} {<false code>}</code>
<code>\tl_if_blank:nTF</code>	★	
<code>\tl_if_blank:(e V o)TF</code>	★	

Updated: 2019-09-04

Tests if the $\langle token\ list \rangle$ consists only of blank spaces (*i.e.* contains no item). The test is **true** if $\langle token\ list \rangle$ is zero or more explicit space characters (explicit tokens with character code 32 and category code 10), and is **false** otherwise.

<code>\tl_if_empty_p:N</code>	★	<code>\tl_if_empty_p:N <tl var></code>
<code>\tl_if_empty_p:c</code>	★	<code>\tl_if_empty:NNTF <tl var> {<true code>} {<false code>}</code>
<code>\tl_if_empty:nTF</code>	★	Tests if the <i><token list variable></i> is entirely empty (<i>i.e.</i> contains no tokens at all).
<code>\tl_if_empty:cTF</code>	★	

<code>\tl_if_empty_p:n</code>	★	<code>\tl_if_empty_p:n {<token list>}</code>
<code>\tl_if_empty_p:(V o)</code>	★	<code>\tl_if_empty:NNTF {<token list>} {<true code>} {<false code>}</code>
<code>\tl_if_empty:nTF</code>	★	Tests if the <i><token list></i> is entirely empty (<i>i.e.</i> contains no tokens at all).
<code>\tl_if_empty:(V o)TF</code>	★	

New: 2012-05-24
Updated: 2012-06-05

<code>\tl_if_eq_p:NN</code>	★	<code>\tl_if_eq_p:NN <tl var₁> <tl var₂></code>
<code>\tl_if_eq_p:(Nc cN cc)</code>	★	<code>\tl_if_eq:NNTF <tl var₁> <tl var₂> {<true code>} {<false code>}</code>
<code>\tl_if_eq:NNTF</code>	★	Compares the content of two <i><token list variables></i> and is logically true if the two contain the same list of tokens (<i>i.e.</i> identical in both the list of characters they contain and the category codes of those characters). Thus for example
<code>\tl_if_eq:(Nc cN cc)TF</code>	★	

```

\tl_set:Nn \l_tmpa_tl { abc }
\tl_set:Nx \l_tmpb_tl { \tl_to_str:n { abc } }
\tl_if_eq:NNTF \l_tmpa_tl \l_tmpb_tl { true } { false }

```

yields **false**.

<code>\tl_if_eq:nnTF</code>	★	<code>\tl_if_eq:nnTF {<token list₁>} {<token list₂>} {<true code>} {<false code>}</code>
-----------------------------	---	--

Tests if *<token list₁>* and *<token list₂>* contain the same list of tokens, both in respect of character codes and category codes.

<code>\tl_if_in:NnTF</code>	★	<code>\tl_if_in:NnTF <tl var> {<token list>} {<true code>} {<false code>}</code>
<code>\tl_if_in:cnTF</code>	★	Tests if the <i><token list></i> is found in the content of the <i><tl var></i> . The <i><token list></i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

<code>\tl_if_in:nnTF</code>	★	<code>\tl_if_in:nnTF {<token list₁>} {<token list₂>} {<true code>} {<false code>}</code>
<code>\tl_if_in:(Vn on no)TF</code>	★	Tests if <i><token list₂></i> is found inside <i><token list₁></i> . The <i><token list₂></i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

<code>\tl_if_novalue_p:n</code>	★	<code>\tl_if_novalue_p:n {<token list>}</code>
<code>\tl_if_novalue:nTF</code>	★	<code>\tl_if_novalue:nTF {<token list>} {<true code>} {<false code>}</code>

New: 2017-11-14

Tests if the *<token list>* is exactly equal to the special `\c_novalue_tl` marker. This function is intended to allow construction of flexible document interface structures in which missing optional arguments are detected.

<code>\tl_if_single_p:N</code> ★ <code>\tl_if_single_p:c</code> ★ <code>\tl_if_single:N\overline{TF}</code> ★ <code>\tl_if_single:c\overline{TF}</code> ★	<code>\tl_if_single_p:N</code> <tl var> <code>\tl_if_single:N\overline{TF}</code> <tl var> {<true code>} {<false code>}
--	---

Updated: 2011-08-13

Tests if the content of the <tl var> consists of a single item, *i.e.* is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to `\tl_count:N`.

<code>\tl_if_single_p:n</code> ★ <code>\tl_if_single:n\overline{TF}</code> ★	<code>\tl_if_single_p:n</code> {<token list>} <code>\tl_if_single:n\overline{TF}</code> {<token list>} {<true code>} {<false code>}
--	---

Updated: 2011-08-13

Tests if the <token list> has exactly one item, *i.e.* is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to `\tl_count:n`.

<code>\tl_if_single_token_p:n</code> ★ <code>\tl_if_single_token:n\overline{TF}</code> ★	<code>\tl_if_single_token_p:n</code> {<token list>} <code>\tl_if_single_token:n\overline{TF}</code> {<token list>} {<true code>} {<false code>}
--	---

Tests if the token list consists of exactly one token, *i.e.* is either a single space character or a single “normal” token. Token groups { \dots } are not single tokens.

<code>\tl_case:Nn</code> ★ <code>\tl_case:cn</code> ★ <code>\tl_case:Nn\overline{TF}</code> ★ <code>\tl_case:cn\overline{TF}</code> ★	<code>\tl_case:Nn\overline{TF}</code> <test token list variable> { <token list variable case ₁ > {<code case ₁ >} <token list variable case ₂ > {<code case ₂ >} ... <token list variable case _n > {<code case _n >} } {<true code>} {<false code>}
--	---

New: 2013-07-24

This function compares the <test token list variable> in turn with each of the <token list variable cases>. If the two are equal (as described for `\tl_if_eq:Nn \overline{TF}`) then the associated <code> is left in the input stream and other cases are discarded. If any of the cases are matched, the <true code> is also inserted into the input stream (after the code for the appropriate case), while if none match then the <false code> is inserted. The function `\tl_case:Nn`, which does nothing if there is no match, is also available.

6 Mapping to token lists

All mappings are done at the current group level, *i.e.* any local assignments made by the <function> or <code> discussed below remain in effect after the loop.

<code>\tl_map_function:NN</code> ☆ <code>\tl_map_function:cN</code> ☆	<code>\tl_map_function:NN</code> <tl var> <function>
--	--

Updated: 2012-06-29

Applies <function> to every <item> in the <tl var>. The <function> receives one argument for each iteration. This may be a number of tokens if the <item> was stored within braces. Hence the <function> should anticipate receiving n-type arguments. See also `\tl_map_function:nN`.

<hr/> <code>\tl_map_function:nN</code> ☆ <hr/>	<code>\tl_map_function:nN {<token list>} <function></code>
Updated: 2012-06-29	Applies <i><function></i> to every <i><item></i> in the <i><token list></i> , The <i><function></i> receives one argument for each iteration. This may be a number of tokens if the <i><item></i> was stored within braces. Hence the <i><function></i> should anticipate receiving n-type arguments. See also <code>\tl_map_function:NN</code> .
<hr/> <code>\tl_map_inline:Nn</code> <code>\tl_map_inline:cn</code> <hr/>	<code>\tl_map_inline:Nn <tl var> {<inline function>}</code>
Updated: 2012-06-29	Applies the <i><inline function></i> to every <i><item></i> stored within the <i><tl var></i> . The <i><inline function></i> should consist of code which receives the <i><item></i> as #1. See also <code>\tl_map_function:NN</code> .
<hr/> <code>\tl_map_inline:nn</code> <hr/>	<code>\tl_map_inline:nn {<token list>} {<inline function>}</code>
Updated: 2012-06-29	Applies the <i><inline function></i> to every <i><item></i> stored within the <i><token list></i> . The <i><inline function></i> should consist of code which receives the <i><item></i> as #1. See also <code>\tl_map_function:nN</code> .
<hr/> <code>\tl_map_tokens:Nn</code> ☆ <code>\tl_map_tokens:cn</code> ☆ <code>\tl_map_tokens:nn</code> ☆ <hr/>	<code>\tl_map_tokens:Nn <tl var> {<code>}</code> <code>\tl_map_tokens:nn <tokens> {<code>}</code>
New: 2019-09-02	Analogue of <code>\tl_map_function:NN</code> which maps several tokens instead of a single function. The <i><code></i> receives each item in the <i><tl var></i> or <i><tokens></i> as two trailing brace groups. For instance, <div style="text-align: center;"><code>\tl_map_tokens:Nn \l_my_tl { \prg_replicate:nn { 2 } }</code></div> expands to twice each item in the <i><sequence></i> : for each item in <code>\l_my_tl</code> the function <code>\prg_replicate:nn</code> receives 2 and <i><item></i> as its two arguments. The function <code>\tl_map_inline:Nn</code> is typically faster but is not expandable.
<hr/> <code>\tl_map_variable:NNn</code> <code>\tl_map_variable:cNn</code> <hr/>	<code>\tl_map_variable:NNn <tl var> <variable> {<code>}</code>
Updated: 2012-06-29	Stores each <i><item></i> of the <i><tl var></i> in turn in the (token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. Its value after the loop is the last <i><item></i> in the <i><tl var></i> , or its original value if the <i><tl var></i> is blank. See also <code>\tl_map_inline:Nn</code> .
<hr/> <code>\tl_map_variable:nNn</code> <hr/>	<code>\tl_map_variable:nNn {<token list>} <variable> {<code>}</code>
Updated: 2012-06-29	Stores each <i><item></i> of the <i><token list></i> in turn in the (token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. Its value after the loop is the last <i><item></i> in the <i><tl var></i> , or its original value if the <i><tl var></i> is blank. See also <code>\tl_map_inline:nn</code> .

<hr/> <code>\tl_map_break:</code> ☆	<code>\tl_map_break:</code>
<hr/> Updated: 2012-06-29 <hr/>	Used to terminate a <code>\tl_map...</code> function before all entries in the <i>⟨token list variable⟩</i> have been processed. This normally takes place within a conditional statement, for example

```

\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo } { \tl_map_break: }
  % Do something useful
}

```

See also `\tl_map_break:n`. Use outside of a `\tl_map...` scenario leads to low level \TeX errors.

\TeX hackers note: When the mapping is broken, additional tokens may be inserted before the *⟨tokens⟩* are inserted into the input stream. This depends on the design of the mapping function.

<hr/> <code>\tl_map_break:n</code> ☆	<code>\tl_map_break:n {⟨code⟩}</code>
<hr/> Updated: 2012-06-29 <hr/>	Used to terminate a <code>\tl_map...</code> function before all entries in the <i>⟨token list variable⟩</i> have been processed, inserting the <i>⟨code⟩</i> after the mapping has ended. This normally takes place within a conditional statement, for example

```

\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo }
  { \tl_map_break:n { <code> } }
  % Do something useful
}

```

Use outside of a `\tl_map...` scenario leads to low level \TeX errors.

\TeX hackers note: When the mapping is broken, additional tokens may be inserted before the *⟨code⟩* is inserted into the input stream. This depends on the design of the mapping function.

7 Using token lists

<code>\tl_to_str:n</code>	★	<code>\tl_to_str:n {⟨token list⟩}</code>
<code>\tl_to_str:V</code>	★	

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, leaving the resulting character tokens in the input stream. A $\langle string \rangle$ is a series of tokens with category code 12 (other) with the exception of spaces, which retain category code 10 (space). This function requires only a single expansion. Its argument *must* be braced.

TeXhackers note: This is the ε -TeX primitive `\detokenize`. Converting a $\langle token\ list \rangle$ to a $\langle string \rangle$ yields a concatenation of the string representations of every token in the $\langle token\ list \rangle$. The string representation of a control sequence is

- an escape character, whose character code is given by the internal parameter `\escapechar`, absent if the `\escapechar` is negative or greater than the largest character code;
- the control sequence name, as defined by `\cs_to_str:N`;
- a space, unless the control sequence name is a single character whose category at the time of expansion of `\tl_to_str:n` is not “letter”.

The string representation of an explicit character token is that character, doubled in the case of (explicit) macro parameter characters (normally `#`). In particular, the string representation of a token list may depend on the category codes in effect when it is evaluated, and the value of the `\escapechar`: for instance `\tl_to_str:n {\a}` normally produces the three character “backslash”, “lower-case a”, “space”, but it may also produce a single “lower-case a” if the escape character is negative and `a` is currently not a letter.

<code>\tl_to_str:N</code>	★	<code>\tl_to_str:N ⟨tl var⟩</code>
<code>\tl_to_str:c</code>	★	

Converts the content of the $\langle tl\ var \rangle$ into a series of characters with category code 12 (other) with the exception of spaces, which retain category code 10 (space). This $\langle string \rangle$ is then left in the input stream. For low-level details, see the notes given for `\tl_to_str:n`.

<code>\tl_use:N</code>	★	<code>\tl_use:N ⟨tl var⟩</code>
<code>\tl_use:c</code>	★	

Recovers the content of a $\langle tl\ var \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Note that it is possible to use a $\langle tl\ var \rangle$ directly without an accessor function.

8 Working with the content of token lists

<code>\tl_count:n</code>	★	<code>\tl_count:n {⟨tokens⟩}</code>
<code>\tl_count:(V o)</code>	★	

New: 2012-05-13

Counts the number of $\langle items \rangle$ in $\langle tokens \rangle$ and leaves this information in the input stream. Unbraced tokens count as one element as do each token group (`{...}`). This process ignores any unprotected spaces within $\langle tokens \rangle$. See also `\tl_count:N`. This function requires three expansions, giving an $\langle integer\ denotation \rangle$.

<hr/>	
<code>\tl_count:N</code> ★	<code>\tl_count:N</code> $\langle tl\ var \rangle$
<code>\tl_count:c</code> ★	
<hr/> New: 2012-05-13 <hr/>	Counts the number of token groups in the $\langle tl\ var \rangle$ and leaves this information in the input stream. Unbraced tokens count as one element as do each token group $\{...\}$. This process ignores any unprotected spaces within the $\langle tl\ var \rangle$. See also <code>\tl_count:n</code> . This function requires three expansions, giving an <i>integer denotation</i> .

<hr/>	
<code>\tl_count_tokens:n</code> ★	<code>\tl_count_tokens:n</code> $\{\langle tokens \rangle\}$
<hr/> New: 2019-02-25 <hr/>	Counts the number of \TeX tokens in the $\langle tokens \rangle$ and leaves this information in the input stream. Every token, including spaces and braces, contributes one to the total; thus for instance, the token count of <code>a~{bc}</code> is 6.

<hr/>	
<code>\tl_reverse:n</code> ★	<code>\tl_reverse:n</code> $\{\langle token\ list \rangle\}$
<code>\tl_reverse:(V o)</code> ★	
<hr/> Updated: 2012-01-08 <hr/>	Reverses the order of the $\langle items \rangle$ in the $\langle token\ list \rangle$, so that $\langle item_1 \rangle \langle item_2 \rangle \langle item_3 \rangle \dots \langle item_n \rangle$ becomes $\langle item_n \rangle \dots \langle item_3 \rangle \langle item_2 \rangle \langle item_1 \rangle$. This process preserves unprotected space within the $\langle token\ list \rangle$. Tokens are not reversed within braced token groups, which keep their outer set of braces. In situations where performance is important, consider <code>\tl_reverse_items:n</code> . See also <code>\tl_reverse:N</code> .

\TeX hackers note: The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an \mathbf{x} -type argument expansion.

<hr/>	
<code>\tl_reverse:N</code>	<code>\tl_reverse:N</code> $\langle tl\ var \rangle$
<code>\tl_reverse:c</code>	
<code>\tl_greverse:N</code>	Reverses the order of the $\langle items \rangle$ stored in $\langle tl\ var \rangle$, so that $\langle item_1 \rangle \langle item_2 \rangle \langle item_3 \rangle \dots \langle item_n \rangle$ becomes $\langle item_n \rangle \dots \langle item_3 \rangle \langle item_2 \rangle \langle item_1 \rangle$. This process preserves unprotected spaces within the $\langle token\ list\ variable \rangle$. Braced token groups are copied without reversing the order of tokens, but keep the outer set of braces. See also <code>\tl_reverse:n</code> , and, for improved performance, <code>\tl_reverse_items:n</code> .
<code>\tl_greverse:c</code>	
<hr/> Updated: 2012-01-08 <hr/>	

<hr/>	
<code>\tl_reverse_items:n</code> ★	<code>\tl_reverse_items:n</code> $\{\langle token\ list \rangle\}$
<hr/> New: 2012-01-08 <hr/>	Reverses the order of the $\langle items \rangle$ stored in $\langle tl\ var \rangle$, so that $\{\langle item_1 \rangle\} \{\langle item_2 \rangle\} \{\langle item_3 \rangle\} \dots \{\langle item_n \rangle\}$ becomes $\{\langle item_n \rangle\} \dots \{\langle item_3 \rangle\} \{\langle item_2 \rangle\} \{\langle item_1 \rangle\}$. This process removes any unprotected space within the $\langle token\ list \rangle$. Braced token groups are copied without reversing the order of tokens, and keep the outer set of braces. Items which are initially not braced are copied with braces in the result. In cases where preserving spaces is important, consider the slower function <code>\tl_reverse:n</code> .

\TeX hackers note: The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an \mathbf{x} -type argument expansion.

<hr/>	
<code>\tl_trim_spaces:n</code> ★	<code>\tl_trim_spaces:n</code> $\{\langle token\ list \rangle\}$
<code>\tl_trim_spaces:o</code> ★	
<hr/> New: 2011-07-09 Updated: 2012-06-25 <hr/>	Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the $\langle token\ list \rangle$ and leaves the result in the input stream.

\TeX hackers note: The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an \mathbf{x} -type argument expansion.

<code>\tl_trim_spaces_apply:nN</code> ★	<code>\tl_trim_spaces_apply:nN</code> $\{ \langle token\ list \rangle \}$ $\langle function \rangle$
<code>\tl_trim_spaces_apply:oN</code> ★	
New: 2018-04-12	Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the $\langle token\ list \rangle$ and passes the result to the $\langle function \rangle$ as an <i>n</i> -type argument.

<code>\tl_trim_spaces:N</code>	<code>\tl_trim_spaces:N</code> $\langle tl\ var \rangle$
<code>\tl_trim_spaces:c</code>	
<code>\tl_gtrim_spaces:N</code>	Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the content of the $\langle tl\ var \rangle$. Note that this therefore <i>resets</i> the content of the variable.
<code>\tl_gtrim_spaces:c</code>	
New: 2011-07-09	

<code>\tl_sort:Nn</code>	<code>\tl_sort:Nn</code> $\langle tl\ var \rangle$ $\{ \langle comparison\ code \rangle \}$
<code>\tl_sort:cn</code>	
<code>\tl_gsort:Nn</code>	Sorts the items in the $\langle tl\ var \rangle$ according to the $\langle comparison\ code \rangle$, and assigns the result to $\langle tl\ var \rangle$. The details of sorting comparison are described in Section 1.
<code>\tl_gsort:cn</code>	
New: 2017-02-06	

<code>\tl_sort:nN</code> ★	<code>\tl_sort:nN</code> $\{ \langle token\ list \rangle \}$ $\langle conditional \rangle$
New: 2017-02-06	Sorts the items in the $\langle token\ list \rangle$, using the $\langle conditional \rangle$ to compare items, and leaves the result in the input stream. The $\langle conditional \rangle$ should have signature <code>:nnTF</code> , and return true if the two items being compared should be left in the same order, and false if the items should be swapped. The details of sorting comparison are described in Section 1.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type or *e*-type argument expansion.

9 The first token from a token list

Functions which deal with either only the very first item (balanced text or single normal token) in a token list, or the remaining tokens.

<hr/>	
<code>\tl_head:N</code>	★
<code>\tl_head:n</code>	★
<code>\tl_head:(V v f)</code>	★
<hr/>	
Updated: 2012-09-09	
<hr/>	

`\tl_head:n {⟨token list⟩}`

Leaves in the input stream the first *⟨item⟩* in the *⟨token list⟩*, discarding the rest of the *⟨token list⟩*. All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded; for example

`\tl_head:n { abc }`

and

`\tl_head:n { ~ abc }`

both leave `a` in the input stream. If the “head” is a brace group, rather than a single token, the braces are removed, and so

`\tl_head:n { ~ { ~ ab } c }`

yields `▯ab`. A blank *⟨token list⟩* (see `\tl_if_blank:nTF`) results in `\tl_head:n` leaving nothing in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

<hr/>	
<code>\tl_head:w</code>	★
<hr/>	

`\tl_head:w ⟨token list⟩ { } \q_stop`

Leaves in the input stream the first *⟨item⟩* in the *⟨token list⟩*, discarding the rest of the *⟨token list⟩*. All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded. A blank *⟨token list⟩* (which consists only of space characters) results in a low-level TeX error, which may be avoided by the inclusion of an empty group in the input (as shown), without the need for an explicit test. Alternatively, `\tl_if_blank:nF` may be used to avoid using the function with a “blank” argument. This function requires only a single expansion, and thus is suitable for use within an *o*-type expansion. In general, `\tl_head:n` should be preferred if the number of expansions is not critical.

<hr/>	
<code>\tl_tail:N</code>	★
<code>\tl_tail:n</code>	★
<code>\tl_tail:(V v f)</code>	★
<hr/>	
Updated: 2012-09-01	
<hr/>	

`\tl_tail:n {⟨token list⟩}`

Discards all leading explicit space characters (explicit tokens with character code 32 and category code 10) and the first *⟨item⟩* in the *⟨token list⟩*, and leaves the remaining tokens in the input stream. Thus for example

`\tl_tail:n { a ~ {bc} d }`

and

`\tl_tail:n { ~ a ~ {bc} d }`

both leave `▯{bc}d` in the input stream. A blank *⟨token list⟩* (see `\tl_if_blank:nTF`) results in `\tl_tail:n` leaving nothing in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

```

\tl_if_head_eq_catcode_p:nN * \tl_if_head_eq_catcode_p:nN {\token list} \test token
\tl_if_head_eq_catcode_p:oN * \tl_if_head_eq_catcode:nNTF {\token list} \test token
\tl_if_head_eq_catcode:nNTF * {\true code} {\false code}
\tl_if_head_eq_catcode:oNTF *

```

Updated: 2012-07-09

Tests if the first $\langle token \rangle$ in the $\langle token list \rangle$ has the same category code as the $\langle test token \rangle$. In the case where the $\langle token list \rangle$ is empty, the test is always **false**.

```

\tl_if_head_eq_charcode_p:nN * \tl_if_head_eq_charcode_p:nN {\token list} \test token
\tl_if_head_eq_charcode_p:fN * \tl_if_head_eq_charcode:nNTF {\token list} \test token
\tl_if_head_eq_charcode:nNTF * {\true code} {\false code}
\tl_if_head_eq_charcode:fNTF *

```

Updated: 2012-07-09

Tests if the first $\langle token \rangle$ in the $\langle token list \rangle$ has the same character code as the $\langle test token \rangle$. In the case where the $\langle token list \rangle$ is empty, the test is always **false**.

```

\tl_if_head_eq_meaning_p:nN * \tl_if_head_eq_meaning_p:nN {\token list} \test token
\tl_if_head_eq_meaning:nNTF * \tl_if_head_eq_meaning:nNTF {\token list} \test token
\tl_if_head_eq_meaning:nNTF * {\true code} {\false code}

```

Updated: 2012-07-09

Tests if the first $\langle token \rangle$ in the $\langle token list \rangle$ has the same meaning as the $\langle test token \rangle$. In the case where $\langle token list \rangle$ is empty, the test is always **false**.

```

\tl_if_head_is_group_p:n * \tl_if_head_is_group_p:n {\token list}
\tl_if_head_is_group:nTF * \tl_if_head_is_group:nTF {\token list} {\true code} {\false code}

```

New: 2012-07-08

Tests if the first $\langle token \rangle$ in the $\langle token list \rangle$ is an explicit begin-group character (with category code 1 and any character code), in other words, if the $\langle token list \rangle$ starts with a brace group. In particular, the test is **false** if the $\langle token list \rangle$ starts with an implicit token such as `\c_group_begin_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

```

\tl_if_head_is_N_type_p:n * \tl_if_head_is_N_type_p:n {\token list}
\tl_if_head_is_N_type:nTF * \tl_if_head_is_N_type:nTF {\token list} {\true code} {\false code}

```

New: 2012-07-08

Tests if the first $\langle token \rangle$ in the $\langle token list \rangle$ is a normal N-type argument. In other words, it is neither an explicit space character (explicit token with character code 32 and category code 10) nor an explicit begin-group character (with category code 1 and any character code). An empty argument yields **false**, as it does not have a “normal” first token. This function is useful to implement actions on token lists on a token by token basis.

```

\tl_if_head_is_space_p:n * \tl_if_head_is_space_p:n {\token list}
\tl_if_head_is_space:nTF * \tl_if_head_is_space:nTF {\token list} {\true code} {\false code}

```

Updated: 2012-07-08

Tests if the first $\langle token \rangle$ in the $\langle token list \rangle$ is an explicit space character (explicit token with character code 12 and category code 10). In particular, the test is **false** if the $\langle token list \rangle$ starts with an implicit token such as `\c_space_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

10 Using a single item

<code>\tl_item:nn</code> *	<code>\tl_item:nn {(token list)} {(integer expression)}</code>
<code>\tl_item:Nn</code> *	Indexing items in the $\langle token list \rangle$ from 1 on the left, this function evaluates the $\langle integer expression \rangle$ and leaves the appropriate item from the $\langle token list \rangle$ in the input stream. If the $\langle integer expression \rangle$ is negative, indexing occurs from the right of the token list, starting at -1 for the right-most item. If the index is out of bounds, then the function expands to nothing.
<code>\tl_item:cn</code> *	

New: 2014-07-17

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

<code>\tl_rand_item:N</code> *	<code>\tl_rand_item:N <tl var></code>
<code>\tl_rand_item:c</code> *	<code>\tl_rand_item:n {(token list)}</code>
<code>\tl_rand_item:n</code> *	Selects a pseudo-random item of the $\langle token list \rangle$. If the $\langle token list \rangle$ is blank, the result is empty. This is not available in older versions of XeTeX.

New: 2016-12-06

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

<code>\tl_range:Nnn</code>	★	<code>\tl_range:Nnn <tl var> {<start index>} {<end index>}</code>
<code>\tl_range:nnn</code>	★	<code>\tl_range:nnn {<token list>} {<start index>} {<end index>}</code>

New: 2017-02-17
Updated: 2017-07-15

Leaves in the input stream the items from the $\langle start\ index \rangle$ to the $\langle end\ index \rangle$ inclusive. Spaces and braces are preserved between the items returned (but never at either end of the list). Here $\langle start\ index \rangle$ and $\langle end\ index \rangle$ should be *integer expressions*. For describing in detail the functions' behavior, let m and n be the start and end index respectively. If either is 0, the result is empty. A positive index means 'start counting from the left end', and a negative index means 'from the right end'. Let l be the count of the token list.

The *actual start point* is determined as $M = m$ if $m > 0$ and as $M = l + m + 1$ if $m < 0$. Similarly the *actual end point* is $N = n$ if $n > 0$ and $N = l + n + 1$ if $n < 0$. If $M > N$, the result is empty. Otherwise it consists of all items from position M to position N inclusive; for the purpose of this rule, we can imagine that the token list extends at infinity on either side, with void items at positions s for $s \leq 0$ or $s > l$.

Spaces in between items in the actual range are preserved. Spaces at either end of the token list will be removed anyway (think to the token list being passed to `\tl_trim_spaces:n` to begin with).

Thus, with $l = 7$ as in the examples below, all of the following are equivalent and result in the whole token list

```
\tl_range:nnn { abcd~{e{}}fg } { 1 } { 7 }
\tl_range:nnn { abcd~{e{}}fg } { 1 } { 12 }
\tl_range:nnn { abcd~{e{}}fg } { -7 } { 7 }
\tl_range:nnn { abcd~{e{}}fg } { -12 } { 7 }
```

Here are some more interesting examples. The calls

```
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { 2 } { 5 } }
\tl_range:nnn { abcd~{e{}}fg } { 2 } { -3 } }
\tl_range:nnn { abcd~{e{}}fg } { -6 } { 5 } }
\tl_range:nnn { abcd~{e{}}fg } { -6 } { -3 } }
```

are all equivalent and will print `bcd{e{}}` on the terminal; similarly

```
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { 2 } { 5 } }
\tl_range:nnn { abcd~{e{}}fg } { 2 } { -3 } }
\tl_range:nnn { abcd~{e{}}fg } { -6 } { 5 } }
\tl_range:nnn { abcd~{e{}}fg } { -6 } { -3 } }
```

are all equivalent and will print `bcd {e{}}` on the terminal (note the space in the middle). To the contrary,

```
\tl_range:nnn { abcd~{e{}}f } { 2 } { 4 }
```

will discard the space after 'd'.

If we want to get the items from, say, the third to the last in a token list $\langle tl \rangle$, the call is `\tl_range:nnn { <tl> } { 3 } { -1 }`. Similarly, for discarding the last item, we can do `\tl_range:nnn { <tl> } { 1 } { -2 }`.

For better performance, see `\tl_range_braced:nnn` and `\tl_range_unbraced:nnn`.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an `x`-type argument expansion.

11 Viewing token lists

`\tl_show:N`
`\tl_show:c`

Updated: 2015-08-01

`\tl_show:N <tl var>`

Displays the content of the `<tl var>` on the terminal.

T_EXhackers note: This is similar to the T_EX primitive `\show`, wrapped to a fixed number of characters per line.

`\tl_show:n`

Updated: 2015-08-07

`\tl_show:n <{token list}>`

Displays the `<token list>` on the terminal.

T_EXhackers note: This is similar to the ϵ -T_EX primitive `\showtokens`, wrapped to a fixed number of characters per line.

`\tl_log:N`
`\tl_log:c`

New: 2014-08-22
Updated: 2015-08-01

`\tl_log:N <tl var>`

Writes the content of the `<tl var>` in the log file. See also `\tl_show:N` which displays the result in the terminal.

`\tl_log:n`

New: 2014-08-22
Updated: 2015-08-07

`\tl_log:n <{token list}>`

Writes the `<token list>` in the log file. See also `\tl_show:n` which displays the result in the terminal.

12 Constant token lists

`\c_empty_tl`

Constant that is always empty.

`\c_novalue_tl`

New: 2017-11-14

A marker for the absence of an argument. This constant `tl` can safely be typeset (*cf.* `\q_nil`), with the result being `-NoValue-`. It is important to note that `\c_novalue_tl` is constructed such that it will *not* match the simple text input `-NoValue-`, *i.e.* that

```
\tl_if_eq:VnTF \c_novalue_tl { -NoValue- }
```

is logically **false**. The `\c_novalue_tl` marker is intended for use in creating document-level interfaces, where it serves as an indicator that an (optional) argument was omitted. In particular, it is distinct from a simple empty `tl`.

`\c_space_tl`

An explicit space character contained in a token list (compare this with `\c_space_token`). For use where an explicit space is required.

13 Scratch token lists

<hr/> <hr/>	
<code>\l_tmpa_tl</code>	
<code>\l_tmpb_tl</code>	
<hr/> <hr/>	

Scratch token lists for local assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

<hr/> <hr/>	
<code>\g_tmpa_tl</code>	
<code>\g_tmpb_tl</code>	
<hr/> <hr/>	

Scratch token lists for global assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

Part VIII

The l3str package: Strings

TeX associates each character with a category code: as such, there is no concept of a “string” as commonly understood in many other programming languages. However, there are places where we wish to manipulate token lists while in some sense “ignoring” category codes: this is done by treating token lists as strings in a TeX sense.

A TeX string (and thus an expl3 string) is a series of characters which have category code 12 (“other”) with the exception of space characters which have category code 10 (“space”). Thus at a technical level, a TeX string is a token list with the appropriate category codes. In this documentation, these are simply referred to as strings.

String variables are simply specialised token lists, but by convention should be named with the suffix `...str`. Such variables should contain characters with category code 12 (other), except spaces, which have category code 10 (blank space). All the functions in this module which accept a token list argument first convert it to a string using `\tl_to_str:n` for internal processing, and do not treat a token list or the corresponding string representation differently.

As a string is a subset of the more general token list, it is sometimes unclear when one should be used over the other. Use a string variable for data that isn’t primarily intended for typesetting and for which a level of protection from unwanted expansion is suitable. This data type simplifies comparison of variables since there are no concerns about expansion of their contents.

The functions `\cs_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N` and `\token_to_str:N` (and variants) generate strings from the appropriate input: these are documented in `l3basics`, `l3tl` and `l3token`, respectively.

Most expandable functions in this module come in three flavours:

- `\str_...:N`, which expect a token list or string variable as their argument;
- `\str_...:n`, taking any token list (or string) as an argument;
- `\str_..._ignore_spaces:n`, which ignores any space encountered during the operation: these functions are typically faster than those which take care of escaping spaces appropriately.

1 Building strings

`\str_new:N``\str_new:c`

`New: 2015-09-18`

`\str_new:N <str var>`

Creates a new `<str var>` or raises an error if the name is already taken. The declaration is global. The `<str var>` is initially empty.

`\str_const:Nn``\str_const:(NV|Nx|cn|cV|cx)`

`New: 2015-09-18``Updated: 2018-07-28`

`\str_const:Nn <str var> {<token list>}`

Creates a new constant `<str var>` or raises an error if the name is already taken. The value of the `<str var>` is set globally to the `<token list>`, converted to a string.

<code>\str_clear:N</code>	<code>\str_clear:N</code> $\langle str\ var \rangle$
<code>\str_clear:c</code>	
<code>\str_gclear:N</code>	Clears the content of the $\langle str\ var \rangle$.
<code>\str_gclear:c</code>	
<hr/>	
New: 2015-09-18	

<code>\str_clear_new:N</code>	<code>\str_clear_new:N</code> $\langle str\ var \rangle$
<code>\str_clear_new:c</code>	
	Ensures that the $\langle str\ var \rangle$ exists globally by applying <code>\str_new:N</code> if necessary, then applies <code>\str_(g)clear:N</code> to leave the $\langle str\ var \rangle$ empty.
<hr/>	
New: 2015-09-18	

<code>\str_set_eq:NN</code>	<code>\str_set_eq:NN</code> $\langle str\ var_1 \rangle$ $\langle str\ var_2 \rangle$
<code>\str_set_eq:(cN Nc cc)</code>	
<code>\str_gset_eq:NN</code>	Sets the content of $\langle str\ var_1 \rangle$ equal to that of $\langle str\ var_2 \rangle$.
<code>\str_gset_eq:(cN Nc cc)</code>	
<hr/>	
New: 2015-09-18	

<code>\str_concat:NNN</code>	<code>\str_concat:NNN</code> $\langle str\ var_1 \rangle$ $\langle str\ var_2 \rangle$ $\langle str\ var_3 \rangle$
<code>\str_concat:ccc</code>	
<code>\str_gconcat:NNN</code>	Concatenates the content of $\langle str\ var_2 \rangle$ and $\langle str\ var_3 \rangle$ together and saves the result in $\langle str\ var_1 \rangle$. The $\langle str\ var_2 \rangle$ is placed at the left side of the new string variable. The $\langle str\ var_2 \rangle$ and $\langle str\ var_3 \rangle$ must indeed be strings, as this function does not convert their contents to a string.
<code>\str_gconcat:ccc</code>	
<hr/>	
New: 2017-10-08	

2 Adding data to string variables

<code>\str_set:Nn</code>	<code>\str_set:Nn</code> $\langle str\ var \rangle$ $\{ \langle token\ list \rangle \}$
<code>\str_set:(NV Nx cn cV cx)</code>	
<code>\str_gset:Nn</code>	Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and stores the result in $\langle str\ var \rangle$.
<code>\str_gset:(NV Nx cn cV cx)</code>	
<hr/>	
New: 2015-09-18	
Updated: 2018-07-28	

<code>\str_put_left:Nn</code>	<code>\str_put_left:Nn</code> $\langle str\ var \rangle$ $\{ \langle token\ list \rangle \}$
<code>\str_put_left:(NV Nx cn cV cx)</code>	
<code>\str_gput_left:Nn</code>	
<code>\str_gput_left:(NV Nx cn cV cx)</code>	
<hr/>	
New: 2015-09-18	
Updated: 2018-07-28	

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and prepends the result to $\langle str\ var \rangle$. The current contents of the $\langle str\ var \rangle$ are not automatically converted to a string.

<code>\str_put_right:Nn</code> <code>\str_put_right:(NV Nx cn cV cx)</code> <code>\str_gput_right:Nn</code> <code>\str_gput_right:(NV Nx cn cV cx)</code>	<code>\str_put_right:Nn <str var> {(token list)}</code>
--	---

New: 2015-09-18

Updated: 2018-07-28

Converts the $\langle token list \rangle$ to a $\langle string \rangle$, and appends the result to $\langle str var \rangle$. The current contents of the $\langle str var \rangle$ are not automatically converted to a string.

3 Modifying string variables

<code>\str_replace_once:Nnn</code> <code>\str_replace_once:cnn</code> <code>\str_greplace_once:Nnn</code> <code>\str_greplace_once:cnn</code>	<code>\str_replace_once:Nnn <str var> {(old)} {(new)}</code> <p>Converts the $\langle old \rangle$ and $\langle new \rangle$ token lists to strings, then replaces the first (leftmost) occurrence of $\langle old string \rangle$ in the $\langle str var \rangle$ with $\langle new string \rangle$.</p>
--	--

New: 2017-10-08

<code>\str_replace_all:Nnn</code> <code>\str_replace_all:cnn</code> <code>\str_greplace_all:Nnn</code> <code>\str_greplace_all:cnn</code>	<code>\str_replace_all:Nnn <str var> {(old)} {(new)}</code> <p>Converts the $\langle old \rangle$ and $\langle new \rangle$ token lists to strings, then replaces all occurrences of $\langle old string \rangle$ in the $\langle str var \rangle$ with $\langle new string \rangle$. As this function operates from left to right, the pattern $\langle old string \rangle$ may remain after the replacement (see <code>\str_remove_all:Nn</code> for an example).</p>
--	--

New: 2017-10-08

<code>\str_remove_once:Nn</code> <code>\str_remove_once:cn</code> <code>\str_gremove_once:Nn</code> <code>\str_gremove_once:cn</code>	<code>\str_remove_once:Nn <str var> {(token list)}</code> <p>Converts the $\langle token list \rangle$ to a $\langle string \rangle$ then removes the first (leftmost) occurrence of $\langle string \rangle$ from the $\langle str var \rangle$.</p>
--	--

New: 2017-10-08

<code>\str_remove_all:Nn</code> <code>\str_remove_all:cn</code> <code>\str_gremove_all:Nn</code> <code>\str_gremove_all:cn</code>	<code>\str_remove_all:Nn <str var> {(token list)}</code> <p>Converts the $\langle token list \rangle$ to a $\langle string \rangle$ then removes all occurrences of $\langle string \rangle$ from the $\langle str var \rangle$. As this function operates from left to right, the pattern $\langle string \rangle$ may remain after the removal, for instance,</p>
--	---

New: 2017-10-08

```
\str_set:Nn \l_tmpa_str {abbccd} \str_remove_all:Nn \l_tmpa_str
{bc}
```

results in `\l_tmpa_str` containing `abcd`.

4 String conditionals

<code>\str_if_exist_p:N</code> *	<code>\str_if_exist_p:N <str var></code>
<code>\str_if_exist_p:c</code> *	<code>\str_if_exist:NTF <str var> {\<true code>} {\<false code>}</code>
<code>\str_if_exist:N\underline{TF}</code> *	Tests whether the $\langle str var \rangle$ is currently defined. This does not check that the $\langle str var \rangle$ really is a string.
<code>\str_if_exist:c\underline{TF}</code> *	

New: 2015-09-18

<code>\str_if_empty_p:N</code> *	<code>\str_if_empty_p:N <str var></code>
<code>\str_if_empty_p:c</code> *	<code>\str_if_empty:NTF <str var> {\<true code>} {\<false code>}</code>
<code>\str_if_empty:N\underline{TF}</code> *	Tests if the $\langle string variable \rangle$ is entirely empty (<i>i.e.</i> contains no characters at all).
<code>\str_if_empty:c\underline{TF}</code> *	

New: 2015-09-18

<code>\str_if_eq_p:NN</code> *	<code>\str_if_eq_p:NN <str var₁> <str var₂></code>
<code>\str_if_eq_p:(Nc cN cc)</code> *	<code>\str_if_eq:NNTF <str var₁> <str var₂> {\<true code>} {\<false code>}</code>
<code>\str_if_eq:N\underline{NTF}</code> *	Compares the content of two $\langle str variables \rangle$ and is logically true if the two contain the same characters in the same order.
<code>\str_if_eq:(Nc cN cc)\underline{TF}</code> *	

New: 2015-09-18

<code>\str_if_eq_p:nn</code> *	<code>\str_if_eq_p:nn {\<tl₁>} {\<tl₂>}</code>
<code>\str_if_eq_p:(Vn on no nV VV vn nv ee)</code> *	<code>\str_if_eq:nnTF {\<tl₁>} {\<tl₂>} {\<true code>} {\<false code>}</code>
<code>\str_if_eq:nn\underline{TF}</code> *	
<code>\str_if_eq:(Vn on no nV VV vn nv ee)\underline{TF}</code> *	

Updated: 2018-06-18

Compares the two $\langle token lists \rangle$ on a character by character basis (namely after converting them to strings), and is **true** if the two $\langle strings \rangle$ contain the same characters in the same order. Thus for example

`\str_if_eq_p:no { abc } { \tl_to_str:n { abc } }`

is logically **true**.

<code>\str_if_in:Nn\underline{TF}</code>	<code>\str_if_in:NnTF <str var> {\<token list>} {\<true code>} {\<false code>}</code>
<code>\str_if_in:cn\underline{TF}</code>	Converts the $\langle token list \rangle$ to a $\langle string \rangle$ and tests if that $\langle string \rangle$ is found in the content of the $\langle str var \rangle$.

New: 2017-10-08

<code>\str_if_in:nn\underline{TF}</code>	<code>\str_if_in:nnTF <tl₁> {\<tl₂>} {\<true code>} {\<false code>}</code>
	Converts both $\langle token lists \rangle$ to $\langle strings \rangle$ and tests whether $\langle string_2 \rangle$ is found inside $\langle string_1 \rangle$.

New: 2017-10-08

<code>\str_case:nn</code>	★	<code>\str_case:nnTF {⟨test string⟩}</code>
<code>\str_case:(Vn on nV nv)</code>	★	{
<code>\str_case:nnTF</code>	★	{⟨string case ₁ ⟩} {⟨code case ₁ ⟩}
<code>\str_case:(Vn on nV nv)TF</code>	★	{⟨string case ₂ ⟩} {⟨code case ₂ ⟩}
		...
		{⟨string case _n ⟩} {⟨code case _n ⟩}
		}
		{⟨true code⟩}
		{⟨false code⟩}

New: 2013-07-24
Updated: 2015-02-28

Compares the *⟨test string⟩* in turn with each of the *⟨string cases⟩* (all token lists are converted to strings). If the two are equal (as described for `\str_if_eq:nnTF`) then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\str_case:nn`, which does nothing if there is no match, is also available.

<code>\str_case_e:nn</code>	★	<code>\str_case_e:nnTF {⟨test string⟩}</code>
<code>\str_case_e:nnTF</code>	★	{
		{⟨string case ₁ ⟩} {⟨code case ₁ ⟩}
		{⟨string case ₂ ⟩} {⟨code case ₂ ⟩}
		...
		{⟨string case _n ⟩} {⟨code case _n ⟩}
		}
		{⟨true code⟩}
		{⟨false code⟩}

New: 2018-06-19

Compares the full expansion of the *⟨test string⟩* in turn with the full expansion of the *⟨string cases⟩* (all token lists are converted to strings). If the two full expansions are equal (as described for `\str_if_eq:nnTF`) then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\str_case_e:nn`, which does nothing if there is no match, is also available. The *⟨test string⟩* is expanded in each comparison, and must always yield the same result: for example, random numbers must not be used within this string.

5 Mapping to strings

All mappings are done at the current group level, *i.e.* any local assignments made by the *⟨function⟩* or *⟨code⟩* discussed below remain in effect after the loop.

<code>\str_map_function:NN</code>	☆	<code>\str_map_function:NN ⟨str var⟩ ⟨function⟩</code>
<code>\str_map_function:cN</code>	☆	Applies <i>⟨function⟩</i> to every <i>⟨character⟩</i> in the <i>⟨str var⟩</i> including spaces. See also <code>\str_map_function:nN</code> .
<code>\str_map_function:nN</code>	☆	<code>\str_map_function:nN {⟨token list⟩} ⟨function⟩</code>
		Converts the <i>⟨token list⟩</i> to a <i>⟨string⟩</i> then applies <i>⟨function⟩</i> to every <i>⟨character⟩</i> in the <i>⟨string⟩</i> including spaces. See also <code>\str_map_function:NN</code> .

New: 2017-11-14

<hr/> <code>\str_map_inline:Nn</code> <code>\str_map_inline:cn</code> <hr/> New: 2017-11-14	<code>\str_map_inline:Nn <str var> {<inline function>}</code> <p>Applies the <i><inline function></i> to every <i><character></i> in the <i><str var></i> including spaces. The <i><inline function></i> should consist of code which receives the <i><character></i> as #1. See also <code>\str_map_function:NN</code>.</p>
<hr/> <code>\str_map_inline:nn</code> <hr/> New: 2017-11-14	<code>\str_map_inline:nn {<token list>} {<inline function>}</code> <p>Converts the <i><token list></i> to a <i><string></i> then applies the <i><inline function></i> to every <i><character></i> in the <i><string></i> including spaces. The <i><inline function></i> should consist of code which receives the <i><character></i> as #1. See also <code>\str_map_function:NN</code>.</p>
<hr/> <code>\str_map_variable:NNn</code> <code>\str_map_variable:cNn</code> <hr/> New: 2017-11-14	<code>\str_map_variable:NNn <str var> <variable> {<code>}</code> <p>Stores each <i><character></i> of the <i><string></i> (including spaces) in turn in the (string or token list) <i><variable></i> and applies the <i><code></i>. The <i><code></i> will usually make use of the <i><variable></i>, but this is not enforced. The assignments to the <i><variable></i> are local. Its value after the loop is the last <i><character></i> in the <i><string></i>, or its original value if the <i><string></i> is empty. See also <code>\str_map_inline:Nn</code>.</p>
<hr/> <code>\str_map_variable:nNn</code> <hr/> New: 2017-11-14	<code>\str_map_variable:nNn {<token list>} <variable> {<code>}</code> <p>Converts the <i><token list></i> to a <i><string></i> then stores each <i><character></i> in the <i><string></i> (including spaces) in turn in the (string or token list) <i><variable></i> and applies the <i><code></i>. The <i><code></i> will usually make use of the <i><variable></i>, but this is not enforced. The assignments to the <i><variable></i> are local. Its value after the loop is the last <i><character></i> in the <i><string></i>, or its original value if the <i><string></i> is empty. See also <code>\str_map_inline:Nn</code>.</p>
<hr/> <code>\str_map_break: ☆</code> <hr/> New: 2017-10-08	<code>\str_map_break:</code> <p>Used to terminate a <code>\str_map...</code> function before all characters in the <i><string></i> have been processed. This normally takes place within a conditional statement, for example</p> <pre> \str_map_inline:Nn \l_my_str { \str_if_eq:nnT { #1 } { bingo } { \str_map_break: } % Do something useful } </pre> <p>See also <code>\str_map_break:n</code>. Use outside of a <code>\str_map...</code> scenario leads to low level \TeX errors.</p>

\TeX hackers note: When the mapping is broken, additional tokens may be inserted before continuing with the code that follows the loop. This depends on the design of the mapping function.

`\str_map_break:n` ☆

New: 2017-10-08

`\str_map_break:n {⟨code⟩}`

Used to terminate a `\str_map...` function before all characters in the *⟨string⟩* have been processed, inserting the *⟨code⟩* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\str_map_inline:Nn \l_my_str
{
  \str_if_eq:nnT { #1 } { bingo }
  { \str_map_break:n { <code> } }
  % Do something useful
}
```

Use outside of a `\str_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *⟨code⟩* is inserted into the input stream. This depends on the design of the mapping function.

6 Working with the content of strings

`\str_use:N` ★

`\str_use:c` ★

New: 2015-09-18

`\str_use:N ⟨str var⟩`

Recovers the content of a *⟨str var⟩* and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Note that it is possible to use a *⟨str⟩* directly without an accessor function.

<code>\str_count:N</code>	★	<code>\str_count:n {⟨token list⟩}</code>
<code>\str_count:c</code>	★	
<code>\str_count:n</code>	★	
<code>\str_count_ignore_spaces:n</code>	★	

New: 2015-09-18

Leaves in the input stream the number of characters in the string representation of *⟨token list⟩*, as an integer denotation. The functions differ in their treatment of spaces. In the case of `\str_count:N` and `\str_count:n`, all characters including spaces are counted. The `\str_count_ignore_spaces:n` function leaves the number of non-space characters in the input stream.

`\str_count_spaces:N` ★

`\str_count_spaces:c` ★

`\str_count_spaces:n` ★

New: 2015-09-18

`\str_count_spaces:n {⟨token list⟩}`

Leaves in the input stream the number of space characters in the string representation of *⟨token list⟩*, as an integer denotation. Of course, this function has no `_ignore_spaces` variant.

<code>\str_head:N</code>	★	<code>\str_head:n {⟨token list⟩}</code>
<code>\str_head:c</code>	★	
<code>\str_head:n</code>	★	
<code>\str_head_ignore_spaces:n</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ into a $\langle string \rangle$. The first character in the $\langle string \rangle$ is then left in the input stream, with category code “other”. The functions differ if the first character is a space: `\str_head:N` and `\str_head:n` return a space token with category code 10 (blank space), while the `\str_head_ignore_spaces:n` function ignores this space character and leaves the first non-space character in the input stream. If the $\langle string \rangle$ is empty (or only contains spaces in the case of the `_ignore_spaces` function), then nothing is left on the input stream.

<code>\str_tail:N</code>	★	<code>\str_tail:n {⟨token list⟩}</code>
<code>\str_tail:c</code>	★	
<code>\str_tail:n</code>	★	
<code>\str_tail_ignore_spaces:n</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, removes the first character, and leaves the remaining characters (if any) in the input stream, with category codes 12 and 10 (for spaces). The functions differ in the case where the first character is a space: `\str_tail:N` and `\str_tail:n` only trim that space, while `\str_tail_ignore_spaces:n` removes the first non-space character and any space before it. If the $\langle token\ list \rangle$ is empty (or blank in the case of the `_ignore_spaces` variant), then nothing is left on the input stream.

<code>\str_item:Nn</code>	★	<code>\str_item:nn {⟨token list⟩} {⟨integer expression⟩}</code>
<code>\str_item:nn</code>	★	
<code>\str_item_ignore_spaces:nn</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and leaves in the input stream the character in position $\langle integer\ expression \rangle$ of the $\langle string \rangle$, starting at 1 for the first (left-most) character. In the case of `\str_item:Nn` and `\str_item:nn`, all characters including spaces are taken into account. The `\str_item_ignore_spaces:nn` function skips spaces when counting characters. If the $\langle integer\ expression \rangle$ is negative, characters are counted from the end of the $\langle string \rangle$. Hence, -1 is the right-most character, *etc.*

<code>\str_range:Nnn</code>	<code>*</code>	<code>\str_range:nnn {⟨token list⟩} {⟨start index⟩} {⟨end index⟩}</code>
<code>\str_range:cnn</code>	<code>*</code>	
<code>\str_range:nnn</code>	<code>*</code>	
<code>\str_range_ignore_spaces:nnn</code>	<code>*</code>	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and leaves in the input stream the characters from the $\langle start\ index \rangle$ to the $\langle end\ index \rangle$ inclusive. Spaces are preserved and counted as items (contrast this with `\tl_range:nnn` where spaces are not counted as items and are possibly discarded from the output).

Here $\langle start\ index \rangle$ and $\langle end\ index \rangle$ should be integer denotations. For describing in detail the functions' behavior, let m and n be the start and end index respectively. If either is 0, the result is empty. A positive index means 'start counting from the left end', a negative index means 'start counting from the right end'. Let l be the count of the token list.

The *actual start point* is determined as $M = m$ if $m > 0$ and as $M = l + m + 1$ if $m < 0$. Similarly the *actual end point* is $N = n$ if $n > 0$ and $N = l + n + 1$ if $n < 0$. If $M > N$, the result is empty. Otherwise it consists of all items from position M to position N inclusive; for the purpose of this rule, we can imagine that the token list extends at infinity on either side, with void items at positions s for $s \leq 0$ or $s > l$. For instance,

```
\iow_term:x { \str_range:nnn { abcdef } { 2 } { 5 } }
\iow_term:x { \str_range:nnn { abcdef } { -4 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { -2 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { 0 } { -1 } }
```

prints bcde, cdef, ef, and an empty line to the terminal. The $\langle start\ index \rangle$ must always be smaller than or equal to the $\langle end\ index \rangle$: if this is not the case then no output is generated. Thus

```
\iow_term:x { \str_range:nnn { abcdef } { 5 } { 2 } }
\iow_term:x { \str_range:nnn { abcdef } { -1 } { -4 } }
```

both yield empty strings.

The behavior of `\str_range_ignore_spaces:nnn` is similar, but spaces are removed before starting the job. The input

```
\iow_term:x { \str_range:nnn { abcdefg } { 2 } { 5 } }
\iow_term:x { \str_range:nnn { abcdefg } { 2 } { -3 } }
\iow_term:x { \str_range:nnn { abcdefg } { -6 } { 5 } }
\iow_term:x { \str_range:nnn { abcdefg } { -6 } { -3 } }

\iow_term:x { \str_range:nnn { abc~efg } { 2 } { 5 } }
\iow_term:x { \str_range:nnn { abc~efg } { 2 } { -3 } }
\iow_term:x { \str_range:nnn { abc~efg } { -6 } { 5 } }
\iow_term:x { \str_range:nnn { abc~efg } { -6 } { -3 } }

\iow_term:x { \str_range_ignore_spaces:nnn { abcdefg } { 2 } { 5 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcdefg } { 2 } { -3 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcdefg } { -6 } { 5 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcdefg } { -6 } { -3 } }
```

```

\iow_term:x { \str_range_ignore_spaces:nnn { abcd~efg } { 2 } { 5 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcd~efg } { 2 } { -3 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcd~efg } { -6 } { 5 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcd~efg } { -6 } { -3 } }

```

will print four instances of `bcde`, four instances of `bc e` and eight instances of `bcde`.

7 String manipulation

```

\str_lowercase:n * \str_lowercase:n {<tokens>}
\str_lowercase:f * \str_uppercase:n {<tokens>}
\str_uppercase:n *
\str_uppercase:f *

```

New: 2019-11-26

Converts the input `<tokens>` to their string representation, as described for `\tl_to_str:n`, and then to the lower or upper case representation using a one-to-one mapping as described by the Unicode Consortium file `UnicodeData.txt`.

These functions are intended for case changing programmatic data in places where upper/lower case distinctions are meaningful. One example would be automatically generating a function name from user input where some case changing is needed. In this situation the input is programmatic, not textual, case does have meaning and a language-independent one-to-one mapping is appropriate. For example

```

\cs_new_protected:Npn \myfunc:nn #1#2
{
  \cs_set_protected:cpn
  {
    user
    \str_uppercase:f { \tl_head:n {#1} }
    \str_lowercase:f { \tl_tail:n {#1} }
  }
  { #2 }
}

```

would be used to generate a function with an auto-generated name consisting of the upper case equivalent of the supplied name followed by the lower case equivalent of the rest of the input.

These functions should *not* be used for

- Caseless comparisons: use `\str_foldcase:n` for this situation (case folding is distinct from lower casing).
- Case changing text for typesetting: see the `\text_lowercase:n(n)`, `\text_uppercase:n(n)` and `\text_titlecase:n(n)` functions which correctly deal with context-dependence and other factors appropriate to text case changing.

T_EXhackers note: As with all `expl3` functions, the input supported by `\str_foldcase:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with `pdfTEX` *only* the Latin alphabet characters A–Z are case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both `XYTEX` and `LuaTEX`.

<code>\str_foldcase:n</code> *	<code>\str_foldcase:n {<tokens>}</code>
--------------------------------	---

<code>\str_foldcase:V</code> *

New: 2019-11-26

Converts the input $\langle tokens \rangle$ to their string representation, as described for `\tl_to_str:n`, and then folds the case of the resulting $\langle string \rangle$ to remove case information. The result of this process is left in the input stream.

String folding is a process used for material such as identifiers rather than for “text”. The folding provided by `\str_foldcase:n` follows the mappings provided by the [Unicode Consortium](#), who [state](#):

Case folding is primarily used for caseless comparison of text, such as identifiers in a computer program, rather than actual text transformation. Case folding in Unicode is based on the lowercase mapping, but includes additional changes to the source text to help make it language-insensitive and consistent. As a result, case-folded text should be used solely for internal processing and generally should not be stored or displayed to the end user.

The folding approach implemented by `\str_foldcase:n` follows the “full” scheme defined by the Unicode Consortium (*e.g.* SSfolds to SS). As case-folding is a language-insensitive process, there is no special treatment of Turkic input (*i.e.* I always folds to i and not to ı).

TeXhackers note: As with all `expl3` functions, the input supported by `\str_foldcase:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with `pdfTeX` *only* the Latin alphabet characters A–Z are case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both `XƎTeX` and `LuaTeX`, subject only to the fact that `XƎTeX` in particular has issues with characters of code above hexadecimal 0xFFFF when interacting with `\tl_to_str:n`.

8 Viewing strings

<code>\str_show:N</code>	<code>\str_show:N <str var></code>
--------------------------	--

<code>\str_show:c</code>

<code>\str_show:n</code>

Displays the content of the $\langle str var \rangle$ on the terminal.

New: 2015-09-18

<code>\str_log:N</code>	<code>\str_log:N <str var></code>
-------------------------	---

<code>\str_log:c</code>

<code>\str_log:n</code>

Writes the content of the $\langle str var \rangle$ in the log file.

New: 2019-02-15

9 Constant token lists

`\c_ampersand_str`
`\c_atsign_str`
`\c_backslash_str`
`\c_left_brace_str`
`\c_right_brace_str`
`\c_circumflex_str`
`\c_colon_str`
`\c_dollar_str`
`\c_hash_str`
`\c_percent_str`
`\c_tilde_str`
`\c_underscore_str`

New: 2015-09-19

Constant strings, containing a single character token, with category code 12.

10 Scratch strings

`\l_tmpa_str`
`\l_tmpb_str`

Scratch strings for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_str`
`\g_tmpb_str`

Scratch strings for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

Part IX

The `l3str-convert` package: string encoding conversions

1 Encoding and escaping schemes

Traditionally, string encodings only specify how strings of characters should be stored as bytes. However, the resulting lists of bytes are often to be used in contexts where only a restricted subset of bytes are permitted (*e.g.*, PDF string objects, URLs). Hence, storing a string of characters is done in two steps.

- The code points (“character codes”) are expressed as bytes following a given “encoding”. This can be UTF-16, ISO 8859-1, *etc.* See Table 1 for a list of supported encodings.⁵
- Bytes are translated to \TeX tokens through a given “escaping”. Those are defined for the most part by the pdf file format. See Table 2 for a list of escaping methods supported.⁵

2 Conversion functions

`\str_set_convert:Nnnn`
`\str_gset_convert:Nnnn`

`\str_set_convert:Nnnn <str var> {<string>} {<name 1>} {<name 2>}`

This function converts the $\langle string \rangle$ from the encoding given by $\langle name 1 \rangle$ to the encoding given by $\langle name 2 \rangle$, and stores the result in the $\langle str var \rangle$. Each $\langle name \rangle$ can have the form $\langle encoding \rangle$ or $\langle encoding \rangle / \langle escaping \rangle$, where the possible values of $\langle encoding \rangle$ and $\langle escaping \rangle$ are given in Tables 1 and 2, respectively. The default escaping is to input and output bytes directly. The special case of an empty $\langle name \rangle$ indicates the use of “native” strings, 8-bit for pdf \TeX , and Unicode strings for the other two engines.

For example,

```
\str_set_convert:Nnnn \l_foo_str { Hello! } { } { utf16/hex }
```

results in the variable `\l_foo_str` holding the string `FEFF00480065006C006C006F0021`. This is obtained by converting each character in the (native) string `Hello!` to the UTF-16 encoding, and expressing each byte as a pair of hexadecimal digits. Note the presence of a (big-endian) byte order mark “FEFF”, which can be avoided by specifying the encoding `utf16be/hex`.

An error is raised if the $\langle string \rangle$ is not valid according to the $\langle escaping 1 \rangle$ and $\langle encoding 1 \rangle$, or if it cannot be reencoded in the $\langle encoding 2 \rangle$ and $\langle escaping 2 \rangle$ (for instance, if a character does not exist in the $\langle encoding 2 \rangle$). Erroneous input is replaced by the Unicode replacement character “FFFD”, and characters which cannot be reencoded are replaced by either the replacement character “FFFD if it exists in the $\langle encoding 2 \rangle$, or an encoding-specific replacement character, or the question mark character.

⁵Encodings and escapings will be added as they are requested.

Table 1: Supported encodings. Non-alphanumeric characters are ignored, and capital letters are lower-cased before searching for the encoding in this list.

$\langle Encoding \rangle$	description
<code>utf8</code>	UTF-8
<code>utf16</code>	UTF-16, with byte-order mark
<code>utf16be</code>	UTF-16, big-endian
<code>utf16le</code>	UTF-16, little-endian
<code>utf32</code>	UTF-32, with byte-order mark
<code>utf32be</code>	UTF-32, big-endian
<code>utf32le</code>	UTF-32, little-endian
<code>iso88591, latin1</code>	ISO 8859-1
<code>iso88592, latin2</code>	ISO 8859-2
<code>iso88593, latin3</code>	ISO 8859-3
<code>iso88594, latin4</code>	ISO 8859-4
<code>iso88595</code>	ISO 8859-5
<code>iso88596</code>	ISO 8859-6
<code>iso88597</code>	ISO 8859-7
<code>iso88598</code>	ISO 8859-8
<code>iso88599, latin5</code>	ISO 8859-9
<code>iso885910, latin6</code>	ISO 8859-10
<code>iso885911</code>	ISO 8859-11
<code>iso885913, latin7</code>	ISO 8859-13
<code>iso885914, latin8</code>	ISO 8859-14
<code>iso885915, latin9</code>	ISO 8859-15
<code>iso885916, latin10</code>	ISO 8859-16
<code>clist</code>	comma-list of integers
$\langle empty \rangle$	native (Unicode) string

Table 2: Supported escapings. Non-alphanumeric characters are ignored, and capital letters are lower-cased before searching for the escaping in this list.

$\langle Escaping \rangle$	description
<code>bytes</code> , or <code>empty</code>	arbitrary bytes
<code>hex</code> , <code>hexadecimal</code>	byte = two hexadecimal digits
<code>name</code>	see <code>\pdfescapename</code>
<code>string</code>	see <code>\pdfescapestring</code>
<code>url</code>	encoding used in URLs

<code>\str_set_convert:NnnnTF</code> <code>\str_gset_convert:NnnnTF</code>	<code>\str_set_convert:NnnnTF <str var> {<string>} {<name 1>} {<name 2>} {<true code>} {<false code>}</code>
---	--

As `\str_set_convert:Nnnn`, converts the $\langle string \rangle$ from the encoding given by $\langle name 1 \rangle$ to the encoding given by $\langle name 2 \rangle$, and assigns the result to $\langle str var \rangle$. Contrarily to `\str_set_convert:Nnnn`, the conditional variant does not raise errors in case the $\langle string \rangle$ is not valid according to the $\langle name 1 \rangle$ encoding, or cannot be expressed in the $\langle name 2 \rangle$ encoding. Instead, the $\langle false code \rangle$ is performed.

3 Creating 8-bit mappings

<code>\str_declare_eight_bit_encoding:nnn</code>	<code>\str_declare_eight_bit_encoding:nnn {<name>} {<mapping>} {<missing>}</code>
--	---

Declares the encoding $\langle name \rangle$ to map bytes to Unicode characters according to the $\langle mapping \rangle$, and map those bytes which are not mentioned in the $\langle mapping \rangle$ either to the replacement character (if they appear in $\langle missing \rangle$), or to themselves.

4 Possibilities, and things to do

Encoding/escaping-related tasks.

- In XeTeX/LuaTeX, would it be better to use the `^^^~....` approach to build a string from a given list of character codes? Namely, within a group, assign 0-9a-f and all characters we want to category “other”, then assign `^` the category superscript, and use `\scantokens`.
- Change `\str_set_convert:Nnnn` to expand its last two arguments.
- Describe the internal format in the code comments. Refuse code points in ["D800,"DFFF] in the internal representation?
- Add documentation about each encoding and escaping method, and add examples.
- The `hex` unescaping should raise an error for odd-token count strings.
- Decide what bytes should be escaped in the `url` escaping. Perhaps the characters `! ' () * - . / 0 1 2 3 4 5 6 7 8 9 _` are safe, and all other characters should be escaped?
- Automate generation of 8-bit mapping files.
- Change the framework for 8-bit encodings: for decoding from 8-bit to Unicode, use 256 integer registers; for encoding, use a tree-box.
- More encodings (see Heiko’s `stringenc`). CESU?
- More escapings: ASCII85, shell escapes, lua escapes, *etc.*?

Part X

The l3seq package

Sequences and stacks

L^AT_EX3 implements a “sequence” data type, which contain an ordered list of entries which may contain any *balanced text*. It is possible to map functions to sequences such that the function is applied to every item in the sequence.

Sequences are also used to implement stack functions in L^AT_EX3. This is achieved using a number of dedicated stack functions.

1 Creating and initialising sequences

<code>\seq_new:N</code>	<code>\seq_new:N <sequence></code>
<code>\seq_new:c</code>	

Creates a new *<sequence>* or raises an error if the name is already taken. The declaration is global. The *<sequence>* initially contains no items.

<code>\seq_clear:N</code>	<code>\seq_clear:N <sequence></code>
<code>\seq_clear:c</code>	
<code>\seq_gclear:N</code>	
<code>\seq_gclear:c</code>	

Clears all items from the *<sequence>*.

<code>\seq_clear_new:N</code>	<code>\seq_clear_new:N <sequence></code>
<code>\seq_clear_new:c</code>	
<code>\seq_gclear_new:N</code>	
<code>\seq_gclear_new:c</code>	

Ensures that the *<sequence>* exists globally by applying `\seq_new:N` if necessary, then applies `\seq_(g)clear:N` to leave the *<sequence>* empty.

<code>\seq_set_eq:NN</code>	<code>\seq_set_eq:NN <sequence₁> <sequence₂></code>
<code>\seq_set_eq:(cN Nc cc)</code>	
<code>\seq_gset_eq:NN</code>	
<code>\seq_gset_eq:(cN Nc cc)</code>	

Sets the content of *<sequence₁>* equal to that of *<sequence₂>*.

<code>\seq_set_from_clist:NN</code>	<code>\seq_set_from_clist:NN <sequence> <comma-list></code>
<code>\seq_set_from_clist:(cN Nc cc)</code>	
<code>\seq_set_from_clist:Nn</code>	
<code>\seq_set_from_clist:cn</code>	
<code>\seq_gset_from_clist:NN</code>	
<code>\seq_gset_from_clist:(cN Nc cc)</code>	
<code>\seq_gset_from_clist:Nn</code>	
<code>\seq_gset_from_clist:cn</code>	

New: 2014-07-17

Converts the data in the *<comma list>* into a *<sequence>*: the original *<comma list>* is unchanged.

`\seq_const_from_clist:Nn`
`\seq_const_from_clist:cn`

New: 2017-11-28

`\seq_const_from_clist:Nn` $\langle seq\ var \rangle$ $\{\langle comma-list \rangle\}$

Creates a new constant $\langle seq\ var \rangle$ or raises an error if the name is already taken. The $\langle seq\ var \rangle$ is set globally to contain the items in the $\langle comma\ list \rangle$.

`\seq_set_split:Nnn`
`\seq_set_split:NnV`
`\seq_gset_split:Nnn`
`\seq_gset_split:NnV`

New: 2011-08-15
Updated: 2012-07-02

`\seq_set_split:Nnn` $\langle sequence \rangle$ $\{\langle delimiter \rangle\}$ $\{\langle token\ list \rangle\}$

Splits the $\langle token\ list \rangle$ into $\langle items \rangle$ separated by $\langle delimiter \rangle$, and assigns the result to the $\langle sequence \rangle$. Spaces on both sides of each $\langle item \rangle$ are ignored, then one set of outer braces is removed (if any); this space trimming behaviour is identical to that of `\l3clist` functions. Empty $\langle items \rangle$ are preserved by `\seq_set_split:Nnn`, and can be removed afterwards using `\seq_remove_all:Nn` $\langle sequence \rangle$ $\{\langle \rangle\}$. The $\langle delimiter \rangle$ may not contain `{`, `}` or `#` (assuming \TeX 's normal category code régime). If the $\langle delimiter \rangle$ is empty, the $\langle token\ list \rangle$ is split into $\langle items \rangle$ as a $\langle token\ list \rangle$.

`\seq_concat:NNN`
`\seq_concat:ccc`
`\seq_gconcat:NNN`
`\seq_gconcat:ccc`

`\seq_concat:NNN` $\langle sequence_1 \rangle$ $\langle sequence_2 \rangle$ $\langle sequence_3 \rangle$

Concatenates the content of $\langle sequence_2 \rangle$ and $\langle sequence_3 \rangle$ together and saves the result in $\langle sequence_1 \rangle$. The items in $\langle sequence_2 \rangle$ are placed at the left side of the new sequence.

`\seq_if_exist_p:N` \star
`\seq_if_exist_p:c` \star
`\seq_if_exist:NTF` \star
`\seq_if_exist:cTF` \star

New: 2012-03-03

`\seq_if_exist_p:N` $\langle sequence \rangle$

`\seq_if_exist:NTF` $\langle sequence \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests whether the $\langle sequence \rangle$ is currently defined. This does not check that the $\langle sequence \rangle$ really is a sequence variable.

2 Appending data to sequences

`\seq_put_left:Nn`
`\seq_put_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`
`\seq_gput_left:Nn`
`\seq_gput_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`

`\seq_put_left:Nn` $\langle sequence \rangle$ $\{\langle item \rangle\}$

Appends the $\langle item \rangle$ to the left of the $\langle sequence \rangle$.

`\seq_put_right:Nn`
`\seq_put_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`
`\seq_gput_right:Nn`
`\seq_gput_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`

`\seq_put_right:Nn` $\langle sequence \rangle$ $\{\langle item \rangle\}$

Appends the $\langle item \rangle$ to the right of the $\langle sequence \rangle$.

3 Recovering items from sequences

Items can be recovered from either the left or the right of sequences. For implementation reasons, the actions at the left of the sequence are faster than those acting on the right. These functions all assign the recovered material locally, *i.e.* setting the $\langle token\ list\ variable \rangle$ used with `\tl_set:Nn` and *never* `\tl_gset:Nn`.

<hr/> <code>\seq_get_left:NN</code> <code>\seq_get_left:cN</code> <hr/> Updated: 2012-05-14 <hr/>	<code>\seq_get_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Stores the left-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_get_right:NN</code> <code>\seq_get_right:cN</code> <hr/> Updated: 2012-05-19 <hr/>	<code>\seq_get_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Stores the right-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_pop_left:NN</code> <code>\seq_pop_left:cN</code> <hr/> Updated: 2012-05-14 <hr/>	<code>\seq_pop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_gpop_left:NN</code> <code>\seq_gpop_left:cN</code> <hr/> Updated: 2012-05-14 <hr/>	<code>\seq_gpop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_pop_right:NN</code> <code>\seq_pop_right:cN</code> <hr/> Updated: 2012-05-19 <hr/>	<code>\seq_pop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_gpop_right:NN</code> <code>\seq_gpop_right:cN</code> <hr/> Updated: 2012-05-19 <hr/>	<code>\seq_gpop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_item:Nn</code> ★ <code>\seq_item:cn</code> ★ <hr/> New: 2014-07-17 <hr/>	<code>\seq_item:Nn</code> $\langle sequence \rangle$ $\{ \langle integer expression \rangle \}$ Indexing items in the $\langle sequence \rangle$ from 1 at the top (left), this function evaluates the $\langle integer expression \rangle$ and leaves the appropriate item from the sequence in the input stream. If the $\langle integer expression \rangle$ is negative, indexing occurs from the bottom (right) of the sequence. If the $\langle integer expression \rangle$ is larger than the number of items in the $\langle sequence \rangle$ (as calculated by <code>\seq_count:N</code>) then the function expands to nothing.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

`\seq_rand_item:N` ★
`\seq_rand_item:c` ★

New: 2016-12-06

`\seq_rand_item:N` $\langle seq\ var \rangle$

Selects a pseudo-random item of the $\langle sequence \rangle$. If the $\langle sequence \rangle$ is empty the result is empty. This is not available in older versions of XeTeX.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

4 Recovering values from sequences with branching

The functions in this section combine tests for non-empty sequences with recovery of an item from the sequence. They offer increased readability and performance over separate testing and recovery phases.

`\seq_get_left:NNTF`
`\seq_get_left:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_get_left:NNTF` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false\ code \rangle$ in the input stream. The value of the $\langle token\ list\ variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, stores the left-most item from the $\langle sequence \rangle$ in the $\langle token\ list\ variable \rangle$ without removing it from the $\langle sequence \rangle$, then leaves the $\langle true\ code \rangle$ in the input stream. The $\langle token\ list\ variable \rangle$ is assigned locally.

`\seq_get_right:NNTF`
`\seq_get_right:cNTF`

New: 2012-05-19

`\seq_get_right:NNTF` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false\ code \rangle$ in the input stream. The value of the $\langle token\ list\ variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, stores the right-most item from the $\langle sequence \rangle$ in the $\langle token\ list\ variable \rangle$ without removing it from the $\langle sequence \rangle$, then leaves the $\langle true\ code \rangle$ in the input stream. The $\langle token\ list\ variable \rangle$ is assigned locally.

`\seq_pop_left:NNTF`
`\seq_pop_left:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_pop_left:NNTF` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false\ code \rangle$ in the input stream. The value of the $\langle token\ list\ variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the left-most item from the $\langle sequence \rangle$ in the $\langle token\ list\ variable \rangle$, *i.e.* removes the item from the $\langle sequence \rangle$, then leaves the $\langle true\ code \rangle$ in the input stream. Both the $\langle sequence \rangle$ and the $\langle token\ list\ variable \rangle$ are assigned locally.

`\seq_gpop_left:NNTF`
`\seq_gpop_left:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_gpop_left:NNTF` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false\ code \rangle$ in the input stream. The value of the $\langle token\ list\ variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the left-most item from the $\langle sequence \rangle$ in the $\langle token\ list\ variable \rangle$, *i.e.* removes the item from the $\langle sequence \rangle$, then leaves the $\langle true\ code \rangle$ in the input stream. The $\langle sequence \rangle$ is modified globally, while the $\langle token\ list\ variable \rangle$ is assigned locally.

<code>\seq_pop_right:nnTF</code>	<code>\seq_pop_right:nnTF <sequence> <token list variable> {<true code>} {<false code>}</code>
<code>\seq_pop_right:cnnTF</code>	
New: 2012-05-19	

If the *<sequence>* is empty, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<sequence>* is non-empty, pops the right-most item from the *<sequence>* in the *<token list variable>*, *i.e.* removes the item from the *<sequence>*, then leaves the *<true code>* in the input stream. Both the *<sequence>* and the *<token list variable>* are assigned locally.

<code>\seq_gpop_right:nnTF</code>	<code>\seq_gpop_right:nnTF <sequence> <token list variable> {<true code>} {<false code>}</code>
<code>\seq_gpop_right:cnnTF</code>	
New: 2012-05-19	

If the *<sequence>* is empty, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<sequence>* is non-empty, pops the right-most item from the *<sequence>* in the *<token list variable>*, *i.e.* removes the item from the *<sequence>*, then leaves the *<true code>* in the input stream. The *<sequence>* is modified globally, while the *<token list variable>* is assigned locally.

5 Modifying sequences

While sequences are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update sequences, while retaining the order of the unaffected entries.

<code>\seq_remove_duplicates:n</code>	<code>\seq_remove_duplicates:n <sequence></code>
<code>\seq_remove_duplicates:c</code>	
<code>\seq_gremove_duplicates:n</code>	Removes duplicate items from the <i><sequence></i> , leaving the left most copy of each item in the <i><sequence></i> . The <i><item></i> comparison takes place on a token basis, as for <code>\tl_if_eq:nnTF</code> .
<code>\seq_gremove_duplicates:c</code>	

TeXhackers note: This function iterates through every item in the *<sequence>* and does a comparison with the *<items>* already checked. It is therefore relatively slow with large sequences.

<code>\seq_remove_all:nn</code>	<code>\seq_remove_all:nn <sequence> {<item>}</code>
<code>\seq_remove_all:cn</code>	
<code>\seq_gremove_all:nn</code>	Removes every occurrence of <i><item></i> from the <i><sequence></i> . The <i><item></i> comparison takes place on a token basis, as for <code>\tl_if_eq:nnTF</code> .
<code>\seq_gremove_all:cn</code>	

<code>\seq_reverse:n</code>	<code>\seq_reverse:n <sequence></code>
<code>\seq_reverse:c</code>	
<code>\seq_greverse:n</code>	Reverses the order of the items stored in the <i><sequence></i> .
<code>\seq_greverse:c</code>	

New: 2014-07-18

<code>\seq_sort:nn</code>	<code>\seq_sort:nn <sequence> {<comparison code>}</code>
<code>\seq_sort:cn</code>	
<code>\seq_gsort:nn</code>	Sorts the items in the <i><sequence></i> according to the <i><comparison code></i> , and assigns the result to <i><sequence></i> . The details of sorting comparison are described in Section 1.
<code>\seq_gsort:cn</code>	

New: 2017-02-06

```
\seq_shuffle:N
\seq_shuffle:c
\seq_gshuffle:N
\seq_gshuffle:c
```

New: 2018-04-29

```
\seq_shuffle:N <seq var>
```

Sets the $\langle seq\ var \rangle$ to the result of placing the items of the $\langle seq\ var \rangle$ in a random order. Each item is (roughly) as likely to end up in any given position.

T_EXhackers note: For sequences with more than 13 items or so, only a small proportion of all possible permutations can be reached, because the random seed `\sys_rand_seed` only has 28-bits. The use of `\toks` internally means that sequences with more than 32767 or 65535 items (depending on the engine) cannot be shuffled.

6 Sequence conditionals

```
\seq_if_empty_p:N *
\seq_if_empty_p:c *
\seq_if_empty:NTF *
\seq_if_empty:cTF *
```

```
\seq_if_empty_p:N <sequence>
```

```
\seq_if_empty:NTF <sequence> {\true code} {\false code}
```

Tests if the $\langle sequence \rangle$ is empty (containing no items).

```
\seq_if_in:NnTF
```

```
\seq_if_in:NnTF <sequence> {\item} {\true code} {\false code}
```

```
\seq_if_in:(NV|Nv|No|Nx|cn|cV|cv|co|cx)TF
```

Tests if the $\langle item \rangle$ is present in the $\langle sequence \rangle$.

7 Mapping to sequences

All mappings are done at the current group level, *i.e.* any local assignments made by the $\langle function \rangle$ or $\langle code \rangle$ discussed below remain in effect after the loop.

```
\seq_map_function:NN ☆
\seq_map_function:cN ☆
```

Updated: 2012-06-29

```
\seq_map_function:NN <sequence> <function>
```

Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle sequence \rangle$. The $\langle function \rangle$ will receive one argument for each iteration. The $\langle items \rangle$ are returned from left to right. To pass further arguments to the $\langle function \rangle$, see `\seq_map_tokens:Nn`. The function `\seq_map_inline:Nn` is faster than `\seq_map_function:NN` for sequences with more than about 10 items.

```
\seq_map_inline:Nn
\seq_map_inline:cn
```

Updated: 2012-06-29

```
\seq_map_inline:Nn <sequence> {\inline function}
```

Applies $\langle inline\ function \rangle$ to every $\langle item \rangle$ stored within the $\langle sequence \rangle$. The $\langle inline\ function \rangle$ should consist of code which will receive the $\langle item \rangle$ as #1. The $\langle items \rangle$ are returned from left to right.

`\seq_map_tokens:Nn` ☆

`\seq_map_tokens:cn` ☆

New: 2019-08-30

`\seq_map_tokens:Nn` $\langle sequence \rangle$ $\{\langle code \rangle\}$

Analogue of `\seq_map_function:NN` which maps several tokens instead of a single function. The $\langle code \rangle$ receives each item in the $\langle sequence \rangle$ as two trailing brace groups. For instance,

`\seq_map_tokens:Nn \l_my_seq { \prg_replicate:nn { 2 } }`

expands to twice each item in the $\langle sequence \rangle$: for each item in `\l_my_seq` the function `\prg_replicate:nn` receives 2 and $\langle item \rangle$ as its two arguments. The function `\seq_map_inline:Nn` is typically faster but is not expandable.

`\seq_map_variable:NNn`

`\seq_map_variable:(Ncn|cNn|ccn)`

Updated: 2012-06-29

`\seq_map_variable:NNn` $\langle sequence \rangle$ $\langle variable \rangle$ $\{\langle code \rangle\}$

Stores each $\langle item \rangle$ of the $\langle sequence \rangle$ in turn in the (token list) $\langle variable \rangle$ and applies the $\langle code \rangle$. The $\langle code \rangle$ will usually make use of the $\langle variable \rangle$, but this is not enforced. The assignments to the $\langle variable \rangle$ are local. Its value after the loop is the last $\langle item \rangle$ in the $\langle sequence \rangle$, or its original value if the $\langle sequence \rangle$ is empty. The $\langle items \rangle$ are returned from left to right.

`\seq_map_break:` ☆

Updated: 2012-06-29

`\seq_map_break:`

Used to terminate a `\seq_map...` function before all entries in the $\langle sequence \rangle$ have been processed. This normally takes place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\seq_map...` scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

`\seq_map_break:n` ☆

Updated: 2012-06-29

`\seq_map_break:n {<code>}`

Used to terminate a `\seq_map...` function before all entries in the *<sequence>* have been processed, inserting the *<code>* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break:n { <code> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\seq_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *<code>* is inserted into the input stream. This depends on the design of the mapping function.

`\seq_count:N` ★

`\seq_count:c` ★

New: 2012-07-13

`\seq_count:N <sequence>`

Leaves the number of items in the *<sequence>* in the input stream as an *<integer denotation>*. The total number of items in a *<sequence>* includes those which are empty and duplicates, *i.e.* every item in a *<sequence>* is unique.

8 Using the content of sequences directly

`\seq_use:Nnnn` ★

`\seq_use:cnnn` ★

New: 2013-05-26

`\seq_use:Nnnn <seq var> {<separator between two>}`

`{<separator between more than two>} {<separator between final two>}`

Places the contents of the *<seq var>* in the input stream, with the appropriate *<separator>* between the items. Namely, if the sequence has more than two items, the *<separator between more than two>* is placed between each pair of items except the last, for which the *<separator between final two>* is used. If the sequence has exactly two items, then they are placed in the input stream separated by the *<separator between two>*. If the sequence has a single item, it is placed in the input stream, and an empty sequence produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nnnn \l_tmpa_seq { ~and~ } { ,~ } { ,~and~ }
```

inserts “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the sequence has more than 2 items.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<items>* do not expand further when appearing in an x-type argument expansion.

`\seq_use:Nn` ★

`\seq_use:cn` ★

New: 2013-05-26

`\seq_use:Nn` $\langle seq\ var \rangle$ $\{\langle separator \rangle\}$

Places the contents of the $\langle seq\ var \rangle$ in the input stream, with the $\langle separator \rangle$ between the items. If the sequence has a single item, it is placed in the input stream with no $\langle separator \rangle$, and an empty sequence produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nn \l_tmpa_seq { ~and~ }
```

inserts “a and b and c and de and f” in the input stream.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle items \rangle$ do not expand further when appearing in an `x`-type argument expansion.

9 Sequences as stacks

Sequences can be used as stacks, where data is pushed to and popped from the top of the sequence. (The left of a sequence is the top, for performance reasons.) The stack functions for sequences are not intended to be mixed with the general ordered data functions detailed in the previous section: a sequence should either be used as an ordered data type or as a stack, but not in both ways.

`\seq_get:NN`

`\seq_get:cn`

Updated: 2012-05-14

`\seq_get:NN` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$

Reads the top item from a $\langle sequence \rangle$ into the $\langle token\ list\ variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token\ list\ variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token\ list\ variable \rangle$ is set to the special marker `\q_no_value`.

`\seq_pop:NN`

`\seq_pop:cn`

Updated: 2012-05-14

`\seq_pop:NN` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$

Pops the top item from a $\langle sequence \rangle$ into the $\langle token\ list\ variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token\ list\ variable \rangle$ is set to the special marker `\q_no_value`.

`\seq_gpop:NN`

`\seq_gpop:cn`

Updated: 2012-05-14

`\seq_gpop:NN` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$

Pops the top item from a $\langle sequence \rangle$ into the $\langle token\ list\ variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the $\langle token\ list\ variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token\ list\ variable \rangle$ is set to the special marker `\q_no_value`.

`\seq_get:NNTF`

`\seq_get:cNTF`

New: 2012-05-14

Updated: 2012-05-19

`\seq_get:NNTF` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false\ code \rangle$ in the input stream. The value of the $\langle token\ list\ variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, stores the top item from a $\langle sequence \rangle$ in the $\langle token\ list\ variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token\ list\ variable \rangle$ is assigned locally.

`\seq_pop:NNTF`
`\seq_pop:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_pop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. Both the `<sequence>` and the `<token list variable>` are assigned locally.

`\seq_gpop:NNTF`
`\seq_gpop:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_gpop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. The `<sequence>` is modified globally, while the `<token list variable>` is assigned locally.

`\seq_push:Nn`
`\seq_push:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`
`\seq_gpush:Nn`
`\seq_gpush:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`

`\seq_push:Nn <sequence> {\item}`

Adds the `{\item}` to the top of the `<sequence>`.

10 Sequences as sets

Sequences can also be used as sets, such that all of their items are distinct. Usage of sequences as sets is not currently widespread, hence no specific set function is provided. Instead, it is explained here how common set operations can be performed by combining several functions described in earlier sections. When using sequences to implement sets, one should be careful not to rely on the order of items in the sequence representing the set.

Sets should not contain several occurrences of a given item. To make sure that a `<sequence variable>` only has distinct items, use `\seq_remove_duplicates:N <sequence variable>`. This function is relatively slow, and to avoid performance issues one should only use it when necessary.

Some operations on a set `<seq var>` are straightforward. For instance, `\seq_count:N <seq var>` expands to the number of items, while `\seq_if_in:NnTF <seq var> {\item}` tests if the `<item>` is in the set.

Adding an `<item>` to a set `<seq var>` can be done by appending it to the `<seq var>` if it is not already in the `<seq var>`:

```
\seq_if_in:NnF <seq var> {\item}
{ \seq_put_right:Nn <seq var> {\item} }
```

Removing an `<item>` from a set `<seq var>` can be done using `\seq_remove_all:Nn,`

```
\seq_remove_all:Nn <seq var> {\item}
```

The intersection of two sets `<seq var1 and <seq var2 can be stored into <seq var3 by collecting items of <seq var1 which are in <seq var2.`

```

\seq_clear:N <seq var3>
\seq_map_inline:Nn <seq var1>
{
\seq_if_in:NnT <seq var2> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The code as written here only works if $\langle seq\ var_3 \rangle$ is different from the other two sequence variables. To cover all cases, items should first be collected in a sequence $\backslash l_ \langle pkg \rangle_internal_seq$, then $\langle seq\ var_3 \rangle$ should be set equal to this internal sequence. The same remark applies to other set functions.

The union of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ through

```

\seq_concat:NNN <seq var3> <seq var1> <seq var2>
\seq_remove_duplicates:N <seq var3>

```

or by adding items to (a copy of) $\langle seq\ var_1 \rangle$ one by one

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{
\seq_if_in:NnF <seq var3> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The second approach is faster than the first when the $\langle seq\ var_2 \rangle$ is short compared to $\langle seq\ var_1 \rangle$.

The difference of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ by removing items of the $\langle seq\ var_2 \rangle$ from (a copy of) the $\langle seq\ var_1 \rangle$ one by one.

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn <seq var3> {#1} }

```

The symmetric difference of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ by computing the difference between $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ and storing the result as $\backslash l_ \langle pkg \rangle_internal_seq$, then the difference between $\langle seq\ var_2 \rangle$ and $\langle seq\ var_1 \rangle$, and finally concatenating the two differences to get the symmetric differences.

```

\seq_set_eq:NN \l\_ \langle pkg \rangle\_internal\_seq <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn \l\_ \langle pkg \rangle\_internal\_seq {#1} }
\seq_set_eq:NN <seq var3> <seq var2>
\seq_map_inline:Nn <seq var1>
{ \seq_remove_all:Nn <seq var3> {#1} }
\seq_concat:NNN <seq var3> <seq var3> \l\_ \langle pkg \rangle\_internal\_seq

```

11 Constant and scratch sequences

$\backslash c_empty_seq$

Constant that is always empty.

New: 2012-07-02

`\l_tmpa_seq`
`\l_tmpb_seq`

New: 2012-04-26

Scratch sequences for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_seq`
`\g_tmpb_seq`

New: 2012-04-26

Scratch sequences for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

12 Viewing sequences

`\seq_show:N`
`\seq_show:c`

Updated: 2015-08-01

`\seq_show:N` $\langle sequence \rangle$
Displays the entries in the $\langle sequence \rangle$ in the terminal.

`\seq_log:N`
`\seq_log:c`

New: 2014-08-12
Updated: 2015-08-01

`\seq_log:N` $\langle sequence \rangle$
Writes the entries in the $\langle sequence \rangle$ in the log file.

Part XI

The l3int package

Integers

Calculation and comparison of integer values can be carried out using literal numbers, `int` registers, constants and integers stored in token list variables. The standard operators `+`, `-`, `/` and `*` and parentheses can be used within such expressions to carry arithmetic operations. This module carries out these functions on *integer expressions* (“`intexpr`”).

1 Integer expressions

`\int_eval:n *` `\int_eval:n {(integer expression)}`

Evaluates the *integer expression* and leaves the result in the input stream as an integer denotation: for positive results an explicit sequence of decimal digits not starting with 0, for negative results - followed by such a sequence, and 0 for zero. The *integer expression* should consist, after expansion, of +, -, *, /, (,) and of course integer operands. The result is calculated by applying standard mathematical rules with the following peculiarities:

- / denotes division rounded to the closest integer with ties rounded away from zero;
- there is an error and the overall expression evaluates to zero whenever the absolute value of any intermediate result exceeds $2^{31} - 1$, except in the case of scaling operations $a*b/c$, for which $a*b$ may be arbitrarily large;
- parentheses may not appear after unary + or -, namely placing +(or -(at the start of an expression or after +, -, *, / or (leads to an error.

Each integer operand can be either an integer variable (with no need for `\int_use:N`) or an integer denotation. For example both

```
\int_eval:n { 5 + 4 * 3 - ( 3 + 4 * 5 ) }
```

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { 5 }
\int_new:N \l_my_int
\int_set:Nn \l_my_int { 4 }
\int_eval:n { \l_my_tl + \l_my_int * 3 - ( 3 + 4 * 5 ) }
```

evaluate to -6 because `\l_my_tl` expands to the integer denotation 5. As the *integer expression* is fully expanded from left to right during evaluation, fully expandable and restricted-expandable functions can both be used, and `\exp_not:n` and its variants have no effect while `\exp_not:N` may incorrectly interrupt the expression.

T_EXhackers note: Exactly two expansions are needed to evaluate `\int_eval:n`. The result is *not* an *internal integer*, and therefore requires suitable termination if used in a T_EX-style integer assignment.

As all T_EX integers, integer operands can also be dimension or skip variables, converted to integers in `sp`, or octal numbers given as ' followed by digits other than 8 and 9, or hexadecimal numbers given as " followed by digits or upper case letters from A to F, or the character code of some character or one-character control sequence, given as 'char'.

<hr/> <code>\int_eval:w</code> ★ <hr/>	<code>\int_eval:w</code> $\langle integer\ expression \rangle$
New: 2018-03-30	Evaluates the $\langle integer\ expression \rangle$ as described for <code>\int_eval:n</code> . The end of the expression is the first token encountered that cannot form part of such an expression. If that token is <code>\scan_stop</code> : it is removed, otherwise not. Spaces do <i>not</i> terminate the expression. However, spaces terminate explicit integers, and this may terminate the expression: for instance, <code>\int_eval:w 1_+1_9</code> expands to 29 since the digit 9 is not part of the expression.
<hr/> <code>\int_sign:n</code> ★ <hr/>	<code>\int_sign:n</code> $\{\langle intexpr \rangle\}$
New: 2018-11-03	Evaluates the $\langle integer\ expression \rangle$ then leaves 1 or 0 or -1 in the input stream according to the sign of the result.
<hr/> <code>\int_abs:n</code> ★ <hr/>	<code>\int_abs:n</code> $\{\langle integer\ expression \rangle\}$
Updated: 2012-09-26	Evaluates the $\langle integer\ expression \rangle$ as described for <code>\int_eval:n</code> and leaves the absolute value of the result in the input stream as an $\langle integer\ denotation \rangle$ after two expansions.
<hr/> <code>\int_div_round:nn</code> ★ <hr/>	<code>\int_div_round:nn</code> $\{\langle intexpr_1 \rangle\} \{\langle intexpr_2 \rangle\}$
Updated: 2012-09-26	Evaluates the two $\langle integer\ expressions \rangle$ as described earlier, then divides the first value by the second, and rounds the result to the closest integer. Ties are rounded away from zero. Note that this is identical to using <code>/</code> directly in an $\langle integer\ expression \rangle$. The result is left in the input stream as an $\langle integer\ denotation \rangle$ after two expansions.
<hr/> <code>\int_div_truncate:nn</code> ★ <hr/>	<code>\int_div_truncate:nn</code> $\{\langle intexpr_1 \rangle\} \{\langle intexpr_2 \rangle\}$
Updated: 2012-02-09	Evaluates the two $\langle integer\ expressions \rangle$ as described earlier, then divides the first value by the second, and rounds the result towards zero. Note that division using <code>/</code> rounds to the closest integer instead. The result is left in the input stream as an $\langle integer\ denotation \rangle$ after two expansions.
<hr/> <code>\int_max:nn</code> ★ <hr/>	<code>\int_max:nn</code> $\{\langle intexpr_1 \rangle\} \{\langle intexpr_2 \rangle\}$
<code>\int_min:nn</code> ★ <hr/>	<code>\int_min:nn</code> $\{\langle intexpr_1 \rangle\} \{\langle intexpr_2 \rangle\}$
Updated: 2012-09-26	Evaluates the $\langle integer\ expressions \rangle$ as described for <code>\int_eval:n</code> and leaves either the larger or smaller value in the input stream as an $\langle integer\ denotation \rangle$ after two expansions.
<hr/> <code>\int_mod:nn</code> ★ <hr/>	<code>\int_mod:nn</code> $\{\langle intexpr_1 \rangle\} \{\langle intexpr_2 \rangle\}$
Updated: 2012-09-26	Evaluates the two $\langle integer\ expressions \rangle$ as described earlier, then calculates the integer remainder of dividing the first expression by the second. This is obtained by subtracting <code>\int_div_truncate:nn</code> $\{\langle intexpr_1 \rangle\} \{\langle intexpr_2 \rangle\}$ times $\langle intexpr_2 \rangle$ from $\langle intexpr_1 \rangle$. Thus, the result has the same sign as $\langle intexpr_1 \rangle$ and its absolute value is strictly less than that of $\langle intexpr_2 \rangle$. The result is left in the input stream as an $\langle integer\ denotation \rangle$ after two expansions.

2 Creating and initialising integers

<hr/> <code>\int_new:N</code> <hr/>	<code>\int_new:N</code> $\langle integer \rangle$
<code>\int_new:c</code> <hr/>	Creates a new $\langle integer \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle integer \rangle$ is initially equal to 0.

<code>\int_const:Nn</code>	<code>\int_const:Nn <integer> {<integer expression>}</code>
<code>\int_const:cn</code>	Creates a new constant $\langle integer \rangle$ or raises an error if the name is already taken. The value of the $\langle integer \rangle$ is set globally to the $\langle integer expression \rangle$.
Updated: 2011-10-22	

<code>\int_zero:N</code>	<code>\int_zero:N <integer></code>
<code>\int_zero:c</code>	
<code>\int_gzero:N</code>	Sets $\langle integer \rangle$ to 0.
<code>\int_gzero:c</code>	

<code>\int_zero_new:N</code>	<code>\int_zero_new:N <integer></code>
<code>\int_zero_new:c</code>	
<code>\int_gzero_new:N</code>	Ensures that the $\langle integer \rangle$ exists globally by applying <code>\int_new:N</code> if necessary, then applies <code>\int_(g)zero:N</code> to leave the $\langle integer \rangle$ set to zero.
<code>\int_gzero_new:c</code>	
New: 2011-12-13	

<code>\int_set_eq:NN</code>	<code>\int_set_eq:NN <integer₁₂</code>
<code>\int_set_eq:(cN Nc cc)</code>	Sets the content of $\langle integer_1 \rangle$ equal to that of $\langle integer_2 \rangle$.
<code>\int_gset_eq:NN</code>	
<code>\int_gset_eq:(cN Nc cc)</code>	

<code>\int_if_exist_p:N *</code>	<code>\int_if_exist_p:N <int></code>
<code>\int_if_exist_p:c *</code>	<code>\int_if_exist:NTF <int> {<true code>} {<false code>}</code>
<code>\int_if_exist:NTF *</code>	
<code>\int_if_exist:cTF *</code>	Tests whether the $\langle int \rangle$ is currently defined. This does not check that the $\langle int \rangle$ really is an integer variable.
New: 2012-03-03	

3 Setting and incrementing integers

<code>\int_add:Nn</code>	<code>\int_add:Nn <integer> {<integer expression>}</code>
<code>\int_add:cn</code>	Adds the result of the $\langle integer expression \rangle$ to the current content of the $\langle integer \rangle$.
<code>\int_gadd:Nn</code>	
<code>\int_gadd:cn</code>	
Updated: 2011-10-22	

<code>\int_decr:N</code>	<code>\int_decr:N <integer></code>
<code>\int_decr:c</code>	
<code>\int_gdecr:N</code>	Decreases the value stored in $\langle integer \rangle$ by 1.
<code>\int_gdecr:c</code>	

<code>\int_incr:N</code>	<code>\int_incr:N <integer></code>
<code>\int_incr:c</code>	
<code>\int_gincr:N</code>	Increases the value stored in $\langle integer \rangle$ by 1.
<code>\int_gincr:c</code>	

<code>\int_set:Nn</code>	<code>\int_set:Nn <integer> {<integer expression>}</code>
<code>\int_set:cn</code>	Sets <i><integer></i> to the value of <i><integer expression></i> , which must evaluate to an integer (as described for <code>\int_eval:n</code>).
<code>\int_gset:Nn</code>	
<code>\int_gset:cn</code>	

Updated: 2011-10-22

<code>\int_sub:Nn</code>	<code>\int_sub:Nn <integer> {<integer expression>}</code>
<code>\int_sub:cn</code>	Subtracts the result of the <i><integer expression></i> from the current content of the <i><integer></i> .
<code>\int_gsub:Nn</code>	
<code>\int_gsub:cn</code>	

Updated: 2011-10-22

4 Using integers

<code>\int_use:N</code> *	<code>\int_use:N <integer></code>
<code>\int_use:c</code> *	Recovers the content of an <i><integer></i> and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where an <i><integer></i> is required (such as in the first and third arguments of <code>\int_compare:nNnTF</code>).

Updated: 2011-10-22

TeXhackers note: `\int_use:N` is the TeX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

5 Integer expression conditionals

<code>\int_compare_p:nNn</code> *	<code>\int_compare_p:nNn {<intexpr₁>} <relation> {<intexpr₂>}</code>
<code>\int_compare:nNnTF</code> *	<code>\int_compare:nNnTF {<intexpr₁>} <relation> {<intexpr₂>} {<true code>} {<false code>}</code>

This function first evaluates each of the *<integer expressions>* as described for `\int_eval:n`. The two results are then compared using the *<relation>*:

Equal	=
Greater than	>
Less than	<

This function is less flexible than `\int_compare:nTF` but around 5 times faster.

```

\int_compare_p:n * \int_compare_p:n
\int_compare:nTF * {
    <intexpr1> <relation1>
    ...
    <intexprN> <relationN>
    <intexprN+1>
}
\int_compare:nTF
{
    <intexpr1> <relation1>
    ...
    <intexprN> <relationN>
    <intexprN+1>
}
{<true code>} {<false code>}

```

Updated: 2013-01-13

This function evaluates the *<integer expressions>* as described for `\int_eval:n` and compares consecutive result using the corresponding *<relation>*, namely it compares *<intexpr₁>* and *<intexpr₂>* using the *<relation₁>*, then *<intexpr₂>* and *<intexpr₃>* using the *<relation₂>*, until finally comparing *<intexpr_N>* and *<intexpr_{N+1}>* using the *<relation_N>*. The test yields **true** if all comparisons are **true**. Each *<integer expression>* is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is **false**, then no other *<integer expression>* is evaluated and no other comparison is performed. The *<relations>* can be any of the following:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

This function is more flexible than `\int_compare:nNnTF` but around 5 times slower.

<code>\int_case:nn</code> ★	<code>\int_case:nnTF {⟨test integer expression⟩}</code>
<code>\int_case:nnTF</code> ★	<code>{</code>
	<code>{⟨intexpr case₁⟩} {⟨code case₁⟩}</code>
	<code>{⟨intexpr case₂⟩} {⟨code case₂⟩}</code>
	<code>...</code>
	<code>{⟨intexpr case_n⟩} {⟨code case_n⟩}</code>
	<code>}</code>
	<code>{⟨true code⟩}</code>
	<code>{⟨false code⟩}</code>

New: 2013-07-24

This function evaluates the *⟨test integer expression⟩* and compares this in turn to each of the *⟨integer expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\int_case:nn`, which does nothing if there is no match, is also available. For example

```
\int_case:nnF
{ 2 * 5 }
{
  { 5 }      { Small }
  { 4 + 6 }   { Medium }
  { -2 * 10 } { Negative }
}
{ No idea! }
```

leaves “Medium” in the input stream.

<code>\int_if_even_p:n</code> ★	<code>\int_if_odd_p:n {⟨integer expression⟩}</code>
<code>\int_if_even:nTF</code> ★	<code>\int_if_odd:nTF {⟨integer expression⟩}</code>
<code>\int_if_odd_p:n</code> ★	<code>{⟨true code⟩} {⟨false code⟩}</code>
<code>\int_if_odd:nTF</code> ★	

This function first evaluates the *⟨integer expression⟩* as described for `\int_eval:n`. It then evaluates if this is odd or even, as appropriate.

6 Integer expression loops

<code>\int_do_until:nNnn</code> ☆	<code>\int_do_until:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **false** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **true**.

<code>\int_do_while:nNnn</code> ☆	<code>\int_do_while:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **true** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **false**.

<hr/> <code>\int_until_do:nNnn</code> ☆ <hr/>	<code>\int_until_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
	Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is false . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\int_while_do:nNnn</code> ☆ <hr/>	<code>\int_while_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
	Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is true . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .
<hr/> <code>\int_do_until:nn</code> ☆ <hr/>	<code>\int_do_until:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Places the <i>⟨code⟩</i> in the input stream for T _E X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is false then the <i>⟨code⟩</i> is inserted into the input stream again and a loop occurs until the <i>⟨relation⟩</i> is true .
<hr/> <code>\int_do_while:nn</code> ☆ <hr/>	<code>\int_do_while:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Places the <i>⟨code⟩</i> in the input stream for T _E X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is true then the <i>⟨code⟩</i> is inserted into the input stream again and a loop occurs until the <i>⟨relation⟩</i> is false .
<hr/> <code>\int_until_do:nn</code> ☆ <hr/>	<code>\int_until_do:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is false . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\int_while_do:nn</code> ☆ <hr/>	<code>\int_while_do:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is true . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .

7 Integer step functions

<code>\int_step_function:nN</code>	☆	<code>\int_step_function:nN {⟨final value⟩} ⟨function⟩</code>
<code>\int_step_function:nnN</code>	☆	<code>\int_step_function:nnN {⟨initial value⟩} {⟨final value⟩} ⟨function⟩</code>
<code>\int_step_function:nnnN</code>	☆	<code>\int_step_function:nnnN {⟨initial value⟩} {⟨step⟩} {⟨final value⟩} ⟨function⟩</code>

New: 2012-06-04
Updated: 2018-04-22

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. The $\langle function \rangle$ is then placed in front of each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$). The $\langle step \rangle$ must be non-zero. If the $\langle step \rangle$ is positive, the loop stops when the $\langle value \rangle$ becomes larger than the $\langle final\ value \rangle$. If the $\langle step \rangle$ is negative, the loop stops when the $\langle value \rangle$ becomes smaller than the $\langle final\ value \rangle$. The $\langle function \rangle$ should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\int_step_function:nnnN { 1 } { 1 } { 5 } \my_func:n
```

would print

```
[I saw 1]   [I saw 2]   [I saw 3]   [I saw 4]   [I saw 5]
```

The functions `\int_step_function:nN` and `\int_step_function:nnN` both use a fixed $\langle step \rangle$ of 1, and in the case of `\int_step_function:nN` the $\langle initial\ value \rangle$ is also fixed as 1. These functions are provided as simple short-cuts for code clarity.

<code>\int_step_inline:nn</code>	<code>\int_step_inline:nn {⟨final value⟩} {⟨code⟩}</code>
<code>\int_step_inline:nnn</code>	<code>\int_step_inline:nnn {⟨initial value⟩} {⟨final value⟩} {⟨code⟩}</code>
<code>\int_step_inline:nnnn</code>	<code>\int_step_inline:nnnn {⟨initial value⟩} {⟨step⟩} {⟨final value⟩} {⟨code⟩}</code>

New: 2012-06-04
Updated: 2018-04-22

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream with `#1` replaced by the current $\langle value \rangle$. Thus the $\langle code \rangle$ should define a function of one argument (`#1`).

The functions `\int_step_inline:nn` and `\int_step_inline:nnn` both use a fixed $\langle step \rangle$ of 1, and in the case of `\int_step_inline:nn` the $\langle initial\ value \rangle$ is also fixed as 1. These functions are provided as simple short-cuts for code clarity.

<code>\int_step_variable:nNn</code>	<code>\int_step_variable:nNn {⟨final value⟩} ⟨tl var⟩ {⟨code⟩}</code>
<code>\int_step_variable:nnNn</code>	<code>\int_step_variable:nnNn {⟨initial value⟩} {⟨final value⟩} ⟨tl var⟩ {⟨code⟩}</code>
<code>\int_step_variable:nnnNn</code>	<code>\int_step_variable:nnnNn {⟨initial value⟩} {⟨step⟩} {⟨final value⟩} ⟨tl var⟩ {⟨code⟩}</code>

New: 2012-06-04
Updated: 2018-04-22

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream, with the $\langle tl\ var \rangle$ defined as the current $\langle value \rangle$. Thus the $\langle code \rangle$ should make use of the $\langle tl\ var \rangle$.

The functions `\int_step_variable:nNn` and `\int_step_variable:nnNn` both use a fixed $\langle step \rangle$ of 1, and in the case of `\int_step_variable:nNn` the $\langle initial\ value \rangle$ is also fixed as 1. These functions are provided as simple short-cuts for code clarity.

8 Formatting integers

Integers can be placed into the output stream with formatting. These conversions apply to any integer expressions.

<code>\int_to_arabic:n</code> *	<code>\int_to_arabic:n {⟨integer expression⟩}</code>
---------------------------------	--

Updated: 2011-10-22

Places the value of the $\langle integer\ expression \rangle$ in the input stream as digits, with category code 12 (other).

<code>\int_to_alph:n</code> *	<code>\int_to_alph:n {⟨integer expression⟩}</code>
<code>\int_to_Alph:n</code> *	

Updated: 2011-09-17

Evaluates the $\langle integer\ expression \rangle$ and converts the result into a series of letters, which are then left in the input stream. The conversion rule uses the 26 letters of the English alphabet, in order, adding letters when necessary to increase the total possible range of representable numbers. Thus

```
\int_to_alph:n { 1 }
```

places a in the input stream,

```
\int_to_alph:n { 26 }
```

is represented as z and

```
\int_to_alph:n { 27 }
```

is converted to aa. For conversions using other alphabets, use `\int_to_symbols:nnn` to define an alphabet-specific function. The basic `\int_to_alph:n` and `\int_to_Alph:n` functions should not be modified. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).

<code>\int_to_symbols:nnn</code> *	<code>\int_to_symbols:nnn</code> <code>{⟨integer expression⟩} {⟨total symbols⟩}</code> <code>{⟨value to symbol mapping⟩}</code>
------------------------------------	---

Updated: 2011-09-17

This is the low-level function for conversion of an $\langle integer\ expression \rangle$ into a symbolic form (often letters). The $\langle total\ symbols \rangle$ available should be given as an integer expression. Values are actually converted to symbols according to the $\langle value\ to\ symbol\ mapping \rangle$. This should be given as $\langle total\ symbols \rangle$ pairs of entries, a number and the appropriate symbol. Thus the `\int_to_alph:n` function is defined as

```
\cs_new:Npn \int_to_alph:n #1
{
  \int_to_symbols:nnn {#1} { 26 }
  {
    { 1 } { a }
    { 2 } { b }
    ...
    { 26 } { z }
  }
}
```


<hr/>	
<code>\int_to_bin:n *</code>	<code>\int_to_bin:n {⟨integer expression⟩}</code>
<hr/>	
<code>New: 2014-02-11</code>	Calculates the value of the $\langle integer\ expression \rangle$ and places the binary representation of the result in the input stream.
<hr/>	
<code>\int_to_hex:n *</code>	<code>\int_to_hex:n {⟨integer expression⟩}</code>
<code>\int_to_Hex:n *</code>	Calculates the value of the $\langle integer\ expression \rangle$ and places the hexadecimal (base 16) representation of the result in the input stream. Letters are used for digits beyond 9: lower case letters for <code>\int_to_hex:n</code> and upper case ones for <code>\int_to_Hex:n</code> . The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).
<hr/>	
<code>New: 2014-02-11</code>	
<hr/>	
<code>\int_to_oct:n *</code>	<code>\int_to_oct:n {⟨integer expression⟩}</code>
<hr/>	
<code>New: 2014-02-11</code>	Calculates the value of the $\langle integer\ expression \rangle$ and places the octal (base 8) representation of the result in the input stream. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).
<hr/>	
<code>\int_to_base:nn *</code>	<code>\int_to_base:nn {⟨integer expression⟩} {⟨base⟩}</code>
<code>\int_to_Base:nn *</code>	Calculates the value of the $\langle integer\ expression \rangle$ and converts it into the appropriate representation in the $\langle base \rangle$; the later may be given as an integer expression. For bases greater than 10 the higher “digits” are represented by letters from the English alphabet: lower case letters for <code>\int_to_base:n</code> and upper case ones for <code>\int_to_Base:n</code> . The maximum $\langle base \rangle$ value is 36. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).
<hr/>	
<code>Updated: 2014-02-11</code>	
<hr/>	
TeXhackers note: This is a generic version of <code>\int_to_bin:n</code> , <i>etc.</i>	
<hr/>	
<code>\int_to_roman:n ☆</code>	<code>\int_to_roman:n {⟨integer expression⟩}</code>
<code>\int_to_Roman:n ☆</code>	Places the value of the $\langle integer\ expression \rangle$ in the input stream as Roman numerals, either lower case (<code>\int_to_roman:n</code>) or upper case (<code>\int_to_Roman:n</code>). If the value is negative or zero, the output is empty. The Roman numerals are letters with category code 11 (letter). The letters used are <code>mdclxvi</code> , repeated as needed: the notation with bars (such as \bar{v} for 5000) is <i>not</i> used. For instance <code>\int_to_roman:n { 8249 }</code> expands to <code>mmmmmmmmccxlix</code> .
<hr/>	
<code>Updated: 2011-10-22</code>	
<hr/>	

9 Converting from other formats to integers

<hr/>	
<code>\int_from_alph:n *</code>	<code>\int_from_alph:n {⟨letters⟩}</code>
<hr/>	
<code>Updated: 2014-08-25</code>	Converts the $\langle letters \rangle$ into the integer (base 10) representation and leaves this in the input stream. The $\langle letters \rangle$ are first converted to a string, with no expansion. Lower and upper case letters from the English alphabet may be used, with “a” equal to 1 through to “z” equal to 26. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_alph:n</code> and <code>\int_to_Alph:n</code> .
<hr/>	

<hr/> <code>\int_from_bin:n</code> ★ <hr/>	<code>\int_from_bin:n {⟨binary number⟩}</code>
New: 2014-02-11 Updated: 2014-08-25	Converts the <i>⟨binary number⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨binary number⟩</i> is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by binary digits. This is the inverse function of <code>\int_to_bin:n</code> .
<hr/> <code>\int_from_hex:n</code> ★ <hr/>	<code>\int_from_hex:n {⟨hexadecimal number⟩}</code>
New: 2014-02-11 Updated: 2014-08-25	Converts the <i>⟨hexadecimal number⟩</i> into the integer (base 10) representation and leaves this in the input stream. Digits greater than 9 may be represented in the <i>⟨hexadecimal number⟩</i> by upper or lower case letters. The <i>⟨hexadecimal number⟩</i> is first converted to a string, with no expansion. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_hex:n</code> and <code>\int_to_Hex:n</code> .
<hr/> <code>\int_from_oct:n</code> ★ <hr/>	<code>\int_from_oct:n {⟨octal number⟩}</code>
New: 2014-02-11 Updated: 2014-08-25	Converts the <i>⟨octal number⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨octal number⟩</i> is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by octal digits. This is the inverse function of <code>\int_to_oct:n</code> .
<hr/> <code>\int_from_roman:n</code> ★ <hr/>	<code>\int_from_roman:n {⟨roman numeral⟩}</code>
Updated: 2014-08-25	Converts the <i>⟨roman numeral⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨roman numeral⟩</i> is first converted to a string, with no expansion. The <i>⟨roman numeral⟩</i> may be in upper or lower case; if the numeral contains characters besides <code>mdclxvi</code> or <code>MDCLXVI</code> then the resulting value is -1. This is the inverse function of <code>\int_to_roman:n</code> and <code>\int_to_Roman:n</code> .
<hr/> <code>\int_from_base:nn</code> ★ <hr/>	<code>\int_from_base:nn {⟨number⟩} {⟨base⟩}</code>
Updated: 2014-08-25	Converts the <i>⟨number⟩</i> expressed in <i>⟨base⟩</i> into the appropriate value in base 10. The <i>⟨number⟩</i> is first converted to a string, with no expansion. The <i>⟨number⟩</i> should consist of digits and letters (either lower or upper case), plus optionally a leading sign. The maximum <i>⟨base⟩</i> value is 36. This is the inverse function of <code>\int_to_base:nn</code> and <code>\int_to_Base:nn</code> .

10 Random integers

<hr/> <code>\int_rand:nn</code> ★ <hr/>	<code>\int_rand:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
New: 2016-12-06 Updated: 2018-04-27	Evaluates the two <i>⟨integer expressions⟩</i> and produces a pseudo-random number between the two (with bounds included). This is not available in older versions of X _Y TeX.
<hr/> <code>\int_rand:n</code> ★ <hr/>	<code>\int_rand:n {⟨intexpr⟩}</code>
New: 2018-05-05	Evaluates the <i>⟨integer expression⟩</i> then produces a pseudo-random number between 1 and the <i>⟨intexpr⟩</i> (included). This is not available in older versions of X _Y TeX.

11 Viewing integers

<hr/> <code>\int_show:N</code> <code>\int_show:c</code> <hr/>	<code>\int_show:N <integer></code> Displays the value of the <i><integer></i> on the terminal.
<hr/> <code>\int_show:n</code> <hr/> <div>New: 2011-11-22 Updated: 2015-08-07</div>	<code>\int_show:n {(integer expression)}</code> Displays the result of evaluating the <i><integer expression></i> on the terminal.
<hr/> <code>\int_log:N</code> <code>\int_log:c</code> <hr/> <div>New: 2014-08-22 Updated: 2015-08-03</div>	<code>\int_log:N <integer></code> Writes the value of the <i><integer></i> in the log file.
<hr/> <code>\int_log:n</code> <hr/> <div>New: 2014-08-22 Updated: 2015-08-07</div>	<code>\int_log:n {(integer expression)}</code> Writes the result of evaluating the <i><integer expression></i> in the log file.

12 Constant integers

<hr/> <code>\c_zero_int</code> <code>\c_one_int</code> <hr/> <div>New: 2018-05-07</div>	Integer values used with primitive tests and assignments: their self-terminating nature makes these more convenient and faster than literal numbers.
<hr/> <code>\c_max_int</code> <hr/>	The maximum value that can be stored as an integer.
<hr/> <code>\c_max_register_int</code> <hr/>	Maximum number of registers.
<hr/> <code>\c_max_char_int</code> <hr/>	Maximum character code completely supported by the engine.

13 Scratch integers

<hr/> <code>\l_tmpa_int</code> <code>\l_tmpb_int</code> <hr/>	Scratch integer for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_int</code> <code>\g_tmpb_int</code> <hr/>	Scratch integer for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

13.1 Direct number expansion

`\int_value:w` ★
 New: 2018-03-27

`\int_value:w` $\langle integer \rangle$
`\int_value:w` $\langle integer\ denotation \rangle$ $\langle optional\ space \rangle$

Expands the following tokens until an $\langle integer \rangle$ is formed, and leaves a normalized form (no leading sign except for negative numbers, no leading digit 0 except for zero) in the input stream as category code 12 (other) characters. The $\langle integer \rangle$ can consist of any number of signs (with intervening spaces) followed by

- an integer variable (in fact, any T_EX register except `\toks`) or
- explicit digits (or by ‘ $\langle octal\ digits \rangle$ ’ or “ $\langle hexadecimal\ digits \rangle$ ” or ‘ $\langle character \rangle$ ’).

In this last case expansion stops once a non-digit is found; if that is a space it is removed as in `f`-expansion, and so `\exp_stop_f:` may be employed as an end marker. Note that protected functions *are* expanded by this process.

This function requires exactly one expansion to produce a value, and so is suitable for use in cases where a number is required “directly”. In general, `\int_eval:n` is the preferred approach to generating numbers.

T_EXhackers note: This is the T_EX primitive `\number`.

14 Primitive conditionals

`\if_int_compare:w` ★

`\if_int_compare:w` $\langle integer_1 \rangle$ $\langle relation \rangle$ $\langle integer_2 \rangle$
 $\langle true\ code \rangle$
`\else:`
 $\langle false\ code \rangle$
`\fi:`

Compare two integers using $\langle relation \rangle$, which must be one of =, < or > with category code 12. The `\else:` branch is optional.

T_EXhackers note: These are both names for the T_EX primitive `\ifnum`.

`\if_case:w` ★
`\or:` ★

`\if_case:w` $\langle integer \rangle$ $\langle case_0 \rangle$
`\or:` $\langle case_1 \rangle$
`\or:` ...
`\else:` $\langle default \rangle$
`\fi:`

Selects a case to execute based on the value of the $\langle integer \rangle$. The first case ($\langle case_0 \rangle$) is executed if $\langle integer \rangle$ is 0, the second ($\langle case_1 \rangle$) if the $\langle integer \rangle$ is 1, *etc.* The $\langle integer \rangle$ may be a literal, a constant or an integer expression (*e.g.* using `\int_eval:n`).

T_EXhackers note: These are the T_EX primitives `\ifcase` and `\or`.

<u>\if_int_odd:w</u> *	<u>\if_int_odd:w</u> $\langle tokens \rangle$ $\langle optional\ space \rangle$ $\langle true\ code \rangle$ \else: $\langle true\ code \rangle$ \fi:
------------------------	---

Expands $\langle tokens \rangle$ until a non-numeric token or a space is found, and tests whether the resulting $\langle integer \rangle$ is odd. If so, $\langle true\ code \rangle$ is executed. The `\else:` branch is optional.

TeXhackers note: This is the TeX primitive `\ifodd`.

Part XII

The l3flag package: Expandable flags

Flags are the only data-type that can be modified in expansion-only contexts. This module is meant mostly for kernel use: in almost all cases, booleans or integers should be preferred to flags because they are very significantly faster.

A flag can hold any non-negative value, which we call its *height*. In expansion-only contexts, a flag can only be “raised”: this increases the *height* by 1. The *height* can also be queried expandably. However, decreasing it, or setting it to zero requires non-expandable assignments.

Flag variables are always local. They are referenced by a *flag name* such as `str_missing`. The *flag name* is used as part of `\use:c` constructions hence is expanded at point of use. It must expand to character tokens only, with no spaces.

A typical use case of flags would be to keep track of whether an exceptional condition has occurred during expandable processing, and produce a meaningful (non-expandable) message after the end of the expandable processing. This is exemplified by `l3str-convert`, which for performance reasons performs conversions of individual characters expandably and for readability reasons produces a single error message describing incorrect inputs that were encountered.

Flags should not be used without carefully considering the fact that raising a flag takes a time and memory proportional to its height. Flags should not be used unless unavoidable.

1 Setting up flags

<code>\flag_new:n</code>	<code>\flag_new:n {<flag name>}</code>
--------------------------	--

Creates a new flag with a name given by *flag name*, or raises an error if the name is already taken. The *flag name* may not contain spaces. The declaration is global, but flags are always local variables. The *flag* initially has zero height.

<code>\flag_clear:n</code>	<code>\flag_clear:n {<flag name>}</code>
----------------------------	--

The *flag*’s height is set to zero. The assignment is local.

<code>\flag_clear_new:n</code>	<code>\flag_clear_new:n {<flag name>}</code>
--------------------------------	--

Ensures that the *flag* exists globally by applying `\flag_new:n` if necessary, then applies `\flag_clear:n`, setting the height to zero locally.

<code>\flag_show:n</code>	<code>\flag_show:n {<flag name>}</code>
---------------------------	---

Displays the *flag*’s height in the terminal.

<code>\flag_log:n</code>	<code>\flag_log:n {<flag name>}</code>
--------------------------	--

Writes the *flag*’s height to the log file.

2 Expandable flag commands

<hr/> <hr/>	<code>\flag_if_exist:n</code> $\{ \langle flag\ name \rangle \}$
<code>\flag_if_exist:n\underline{TF}</code> *	This function returns <code>true</code> if the $\langle flag\ name \rangle$ references a flag that has been defined previously, and <code>false</code> otherwise.
<hr/> <hr/>	
<code>\flag_if_raised_p:n</code> *	<code>\flag_if_raised:n</code> $\{ \langle flag\ name \rangle \}$
<code>\flag_if_raised:n\underline{TF}</code> *	This function returns <code>true</code> if the $\langle flag \rangle$ has non-zero height, and <code>false</code> if the $\langle flag \rangle$ has zero height.
<hr/> <hr/>	
<code>\flag_height:n</code> *	<code>\flag_height:n</code> $\{ \langle flag\ name \rangle \}$
	Expands to the height of the $\langle flag \rangle$ as an integer denotation.
<hr/> <hr/>	
<code>\flag_raise:n</code> *	<code>\flag_raise:n</code> $\{ \langle flag\ name \rangle \}$
	The $\langle flag \rangle$'s height is increased by 1 locally.

Part XIII

The l3prg package

Control structures

Conditional processing in L^AT_EX3 is defined as something that performs a series of tests, possibly involving assignments and calling other functions that do not read further ahead in the input stream. After processing the input, a *state* is returned. The states returned are *⟨true⟩* and *⟨false⟩*.

L^AT_EX3 has two forms of conditional flow processing based on these states. The first form is predicate functions that turn the returned state into a boolean *⟨true⟩* or *⟨false⟩*. For example, the function `\cs_if_free_p:N` checks whether the control sequence given as its argument is free and then returns the boolean *⟨true⟩* or *⟨false⟩* values to be used in testing with `\if_predicate:w` or in functions to be described below. The second form is the kind of functions choosing a particular argument from the input stream based on the result of the testing as in `\cs_if_free:NTF` which also takes one argument (the *N*) and then executes either **true** or **false** depending on the result.

T_EXhackers note: The arguments are executed after exiting the underlying `\if... \fi` structure.

1 Defining a set of conditional functions

```
\prg_new_conditional:Npnn
\prg_set_conditional:Npnn
\prg_new_conditional:Nnn
\prg_set_conditional:Nnn
```

Updated: 2012-02-06

```
\prg_new_conditional:Npnn \<name>:<arg spec> <parameters> {\<conditions>} {\<code>}
\prg_new_conditional:Nnn \<name>:<arg spec> {\<conditions>} {\<code>}
```

These functions create a family of conditionals using the same *{⟨code⟩}* to perform the test created. Those conditionals are expandable if *⟨code⟩* is. The **new** versions check for existing definitions and perform assignments globally (cf. `\cs_new:Npn`) whereas the **set** versions do no check and perform assignments locally (cf. `\cs_set:Npn`). The conditionals created are dependent on the comma-separated list of *⟨conditions⟩*, which should be one or more of **p**, **T**, **F** and **TF**.

```
\prg_new_protected_conditional:Npnn \prg_new_protected_conditional:Npnn \<name>:<arg spec> <parameters>
\prg_set_protected_conditional:Npnn {\<conditions>} {\<code>}
\prg_new_protected_conditional:Nnn \prg_new_protected_conditional:Nnn \<name>:<arg spec>
\prg_set_protected_conditional:Nnn {\<conditions>} {\<code>}
```

Updated: 2012-02-06

These functions create a family of protected conditionals using the same *{⟨code⟩}* to perform the test created. The *⟨code⟩* does not need to be expandable. The **new** version check for existing definitions and perform assignments globally (cf. `\cs_new:Npn`) whereas the **set** version do not (cf. `\cs_set:Npn`). The conditionals created are depended on the comma-separated list of *⟨conditions⟩*, which should be one or more of **T**, **F** and **TF** (not **p**).

The conditionals are defined by `\prg_new_conditional:Npnn` and friends as:

- `\<name>_p:<arg spec>` — a predicate function which will supply either a logical `true` or logical `false`. This function is intended for use in cases where one or more logical tests are combined to lead to a final outcome. This function cannot be defined for `protected` conditionals.
- `\<name>:<arg spec>T` — a function with one more argument than the original `<arg spec>` demands. The `<true branch>` code in this additional argument will be left on the input stream only if the test is `true`.
- `\<name>:<arg spec>F` — a function with one more argument than the original `<arg spec>` demands. The `<false branch>` code in this additional argument will be left on the input stream only if the test is `false`.
- `\<name>:<arg spec>TF` — a function with two more argument than the original `<arg spec>` demands. The `<true branch>` code in the first additional argument will be left on the input stream if the test is `true`, while the `<false branch>` code in the second argument will be left on the input stream if the test is `false`.

The `<code>` of the test may use `<parameters>` as specified by the second argument to `\prg_set_conditional:Npnn`: this should match the `<argument specification>` but this is not enforced. The `Nnn` versions infer the number of arguments from the argument specification given (cf. `\cs_new:Nn`, etc.). Within the `<code>`, the functions `\prg_return_true:` and `\prg_return_false:` are used to indicate the logical outcomes of the test.

An example can easily clarify matters here:

```
\prg_set_conditional:Npnn \foo_if_bar:NN #1#2 { p , T , TF }
{
  \if_meaning:w \l_tmpa_tl #1
  \prg_return_true:
\else:
  \if_meaning:w \l_tmpa_tl #2
  \prg_return_true:
\else:
  \prg_return_false:
\fi:
\fi:
}
```

This defines the function `\foo_if_bar_p:NN`, `\foo_if_bar:NNTF` and `\foo_if_bar:NNT` but not `\foo_if_bar:NNF` (because `F` is missing from the `<conditions>` list). The return statements take care of resolving the remaining `\else:` and `\fi:` before returning the state. There must be a return statement for each branch; failing to do so will result in erroneous output if that branch is executed.

<code>\prg_new_eq_conditional:Nnn</code>	<code>\prg_new_eq_conditional:Nnn \<name1>:<arg spec1> \<name2>:<arg spec2></code>
<code>\prg_set_eq_conditional:Nnn</code>	<code>{<conditions>}</code>

These functions copy a family of conditionals. The `new` version checks for existing definitions (cf. `\cs_new_eq:NN`) whereas the `set` version does not (cf. `\cs_set_eq:NN`). The conditionals copied are depended on the comma-separated list of `<conditions>`, which should be one or more of `p`, `T`, `F` and `TF`.

<code>\prg_return_true:</code>	<code>*</code>	<code>\prg_return_true:</code>
<code>\prg_return_false:</code>	<code>*</code>	<code>\prg_return_false:</code>

These “return” functions define the logical state of a conditional statement. They appear within the code for a conditional function generated by `\prg_set_conditional:Npnn`, *etc.*, to indicate when a true or false branch should be taken. While they may appear multiple times each within the code of such conditionals, the execution of the conditional must result in the expansion of one of these two functions *exactly once*.

The return functions trigger what is internally an **f**-expansion process to complete the evaluation of the conditional. Therefore, after `\prg_return_true:` or `\prg_return_false:` there must be no non-expandable material in the input stream for the remainder of the expansion of the conditional code. This includes other instances of either of these functions.

<code>\prg_generate_conditional_variant:Nnn</code>	<code>\prg_generate_conditional_variant:Nnn \<name>:\<arg spec></code>
	<code>{\<variant argument specifiers>} {\<condition specifiers>}</code>

New: 2017-12-12

Defines argument-specifier variants of conditionals. This is equivalent to running `\cs_generate_variant:Nn \<conditional> {\<variant argument specifiers>}` on each `\<conditional>` described by the `\<condition specifiers>`. These base-form `\<conditionals>` are obtained from the `\<name>` and `\<arg spec>` as described for `\prg_new_conditional:Npnn`, and they should be defined.

2 The boolean data type

This section describes a boolean data type which is closely connected to conditional processing as sometimes you want to execute some code depending on the value of a switch (*e.g.*, draft/final) and other times you perhaps want to use it as a predicate function in an `\if_predicate:w` test. The problem of the primitive `\if_false:` and `\if_true:` tokens is that it is not always safe to pass them around as they may interfere with scanning for termination of primitive conditional processing. Therefore, we employ two canonical booleans: `\c_true_bool` or `\c_false_bool`. Besides preventing problems as described above, it also allows us to implement a simple boolean parser supporting the logical operations And, Or, Not, *etc.* which can then be used on both the boolean type and predicate functions.

All conditional `\bool_` functions except assignments are expandable and expect the input to also be fully expandable (which generally means being constructed from predicate functions and booleans, possibly nested).

T_EXhackers note: The `bool` data type is not implemented using the `\iffalse/\iftrue` primitives, in contrast to `\newif`, *etc.*, in plain T_EX, L^AT_EX 2_ε and so on. Programmers should not base use of `bool` switches on any particular expectation of the implementation.

<code>\bool_new:N</code>	<code>\bool_new:N \<boolean></code>
<code>\bool_new:c</code>	

Creates a new `\<boolean>` or raises an error if the name is already taken. The declaration is global. The `\<boolean>` is initially **false**.

<hr/> \bool_const:Nn \bool_const:cn <hr/> New: 2017-11-28	\bool_const:Nn <boolean> {<boolexpr>} Creates a new constant <boolean> or raises an error if the name is already taken. The value of the <boolean> is set globally to the result of evaluating the <boolexpr>.
<hr/> \bool_set_false:N \bool_set_false:c \bool_gset_false:N \bool_gset_false:c <hr/>	\bool_set_false:N <boolean> Sets <boolean> logically false.
<hr/> \bool_set_true:N \bool_set_true:c \bool_gset_true:N \bool_gset_true:c <hr/>	\bool_set_true:N <boolean> Sets <boolean> logically true.
<hr/> \bool_set_eq:NN \bool_set_eq:(cN Nc cc) \bool_gset_eq:NN \bool_gset_eq:(cN Nc cc) <hr/>	\bool_set_eq:NN <boolean ₁ > <boolean ₂ > Sets <boolean ₁ > to the current value of <boolean ₂ >.
<hr/> \bool_set:Nn \bool_set:cn \bool_gset:Nn \bool_gset:cn <hr/> Updated: 2017-07-15	\bool_set:Nn <boolean> {<boolexpr>} Evaluates the <boolean expression> as described for \bool_if:nTF, and sets the <boolean> variable to the logical truth of this evaluation.
<hr/> \bool_if_p:N ★ \bool_if_p:c ★ \bool_if:nTF ★ \bool_if:cTF ★ <hr/> Updated: 2017-07-15	\bool_if_p:N <boolean> \bool_if:NTF <boolean> {<true code>} {<false code>} Tests the current truth of <boolean>, and continues expansion based on this result.
<hr/> \bool_show:N \bool_show:c <hr/> New: 2012-02-09 Updated: 2015-08-01	\bool_show:N <boolean> Displays the logical truth of the <boolean> on the terminal.
<hr/> \bool_show:n <hr/> New: 2012-02-09 Updated: 2017-07-15	\bool_show:n {<boolean expression>} Displays the logical truth of the <boolean expression> on the terminal.
<hr/> \bool_log:N \bool_log:c <hr/> New: 2014-08-22 Updated: 2015-08-03	\bool_log:N <boolean> Writes the logical truth of the <boolean> in the log file.

<code>\bool_log:n</code>	<code>\bool_log:n {⟨boolean expression⟩}</code>
--------------------------	---

New: 2014-08-22	Writes the logical truth of the $\langle boolean\ expression \rangle$ in the log file.
Updated: 2017-07-15	

<code>\bool_if_exist_p:N *</code>	<code>\bool_if_exist_p:N ⟨boolean⟩</code>
<code>\bool_if_exist_p:c *</code>	<code>\bool_if_exist:NTF ⟨boolean⟩ {⟨true code⟩} {⟨false code⟩}</code>
<code>\bool_if_exist:NTF *</code>	Tests whether the $\langle boolean \rangle$ is currently defined. This does not check that the $\langle boolean \rangle$ really is a boolean variable.
<code>\bool_if_exist:cTF *</code>	

New: 2012-03-03

<code>\l_tmpa_bool</code>	A scratch boolean for local assignment. It is never used by the kernel code, and so is safe for use with any L ^A T _E X3-defined function. However, it may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\l_tmpb_bool</code>	

<code>\g_tmpa_bool</code>	A scratch boolean for global assignment. It is never used by the kernel code, and so is safe for use with any L ^A T _E X3-defined function. However, it may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\g_tmpb_bool</code>	

3 Boolean expressions

As we have a boolean datatype and predicate functions returning boolean $\langle true \rangle$ or $\langle false \rangle$ values, it seems only fitting that we also provide a parser for $\langle boolean\ expressions \rangle$.

A boolean expression is an expression which given input in the form of predicate functions and boolean variables, return boolean $\langle true \rangle$ or $\langle false \rangle$. It supports the logical operations And, Or and Not as the well-known infix operators `&&` and `||` and prefix `!` with their usual precedences (namely, `&&` binds more tightly than `||`). In addition to this, parentheses can be used to isolate sub-expressions. For example,

```
\int_compare_p:n { 1 = 1 } &&
(
  \int_compare_p:n { 2 = 3 } ||
  \int_compare_p:n { 4 <= 4 } ||
  \str_if_eq_p:nn { abc } { def }
) &&
! \int_compare_p:n { 2 = 4 }
```

is a valid boolean expression.

Contrarily to some other programming languages, the operators `&&` and `||` evaluate both operands in all cases, even when the first operand is enough to determine the result. This “eager” evaluation should be contrasted with the “lazy” evaluation of `\bool_lazy_...` functions.

T_EXhackers note: The eager evaluation of boolean expressions is unfortunately necessary in T_EX. Indeed, a lazy parser can get confused if `&&` or `||` or parentheses appear as (unbraced) arguments of some predicates. For instance, the innocuous-looking expression below would break (in a lazy parser) if `#1` were a closing parenthesis and `\l_tmpa_bool` were `true`.

```
( \l_tmpa_bool || \token_if_eq_meaning_p:NN X #1 )
```

Minimal (lazy) evaluation can be obtained using the conditionals `\bool_lazy_all:nTF`, `\bool_lazy_and:nnTF`, `\bool_lazy_any:nTF`, or `\bool_lazy_or:nnTF`, which only evaluate their boolean expression arguments when they are needed to determine the resulting truth value. For example, when evaluating the boolean expression

```
\bool_lazy_and_p:nn
{
  \bool_lazy_any_p:n
  {
    { \int_compare_p:n { 2 = 3 } }
    { \int_compare_p:n { 4 <= 4 } }
    { \int_compare_p:n { 1 = \error } } % skipped
  }
}
{ ! \int_compare_p:n { 2 = 4 } }
```

the line marked with `skipped` is not expanded because the result of `\bool_lazy_any_p:n` is known once the second boolean expression is found to be logically `true`. On the other hand, the last line is expanded because its logical value is needed to determine the result of `\bool_lazy_and_p:nn`.

<code>\bool_if_p:n</code> ★ <code>\bool_if:nTF</code> ★	<code>\bool_if_p:n {<boolean expression>}</code> <code>\bool_if:nTF {<boolean expression>} {<true code>} {<false code>}</code>
--	---

Updated: 2017-07-15

Tests the current truth of *<boolean expression>*, and continues expansion based on this result. The *<boolean expression>* should consist of a series of predicates or boolean variables with the logical relationship between these defined using `&&` (“And”), `||` (“Or”), `!` (“Not”) and parentheses. The logical Not applies to the next predicate or group.

<code>\bool_lazy_all_p:n</code> ★ <code>\bool_lazy_all:nTF</code> ★	<code>\bool_lazy_all_p:n { {<boolexpr₁>} {<boolexpr₂>} ... {<boolexpr_N>} }</code> <code>\bool_lazy_all:nTF { {<boolexpr₁>} {<boolexpr₂>} ... {<boolexpr_N>} } {<true code>} {<false code>}</code>
--	---

New: 2015-11-15

Updated: 2017-07-15

Implements the “And” operation on the *<boolean expressions>*, hence is `true` if all of them are `true` and `false` if any of them is `false`. Contrarily to the infix operator `&&`, only the *<boolean expressions>* which are needed to determine the result of `\bool_lazy_all:nTF` are evaluated. See also `\bool_lazy_and:nnTF` when there are only two *<boolean expressions>*.

<code>\bool_lazy_and_p:nn</code> ★ <code>\bool_lazy_and:nnTF</code> ★	<code>\bool_lazy_and_p:nn {<boolexpr₁>} {<boolexpr₂>}</code> <code>\bool_lazy_and:nnTF {<boolexpr₁>} {<boolexpr₂>} {<true code>} {<false code>}</code>
--	---

New: 2015-11-15

Updated: 2017-07-15

Implements the “And” operation between two boolean expressions, hence is `true` if both are `true`. Contrarily to the infix operator `&&`, the *<boolexpr₂>* is only evaluated if it is needed to determine the result of `\bool_lazy_and:nnTF`. See also `\bool_lazy_all:nTF` when there are more than two *<boolean expressions>*.

<hr/> \bool_lazy_any_p:n ☆ \bool_lazy_any:nTF ☆ <hr/> New: 2015-11-15 Updated: 2017-07-15	\bool_lazy_any_p:n { {<boolean expr ₁ >} {<boolean expr ₂ >} ... {<boolean expr _N >} } \bool_lazy_any:nTF { {<boolean expr ₁ >} {<boolean expr ₂ >} ... {<boolean expr _N >} } {<true code>} {<false code>} <hr/> Implements the “Or” operation on the <i><boolean expressions></i> , hence is true if any of them is true and false if all of them are false . Contrarily to the infix operator <code> </code> , only the <i><boolean expressions></i> which are needed to determine the result of <code>\bool_lazy_any:nTF</code> are evaluated. See also <code>\bool_lazy_or:nnTF</code> when there are only two <i><boolean expressions></i> .
<hr/> \bool_lazy_or_p:nn ☆ \bool_lazy_or:nnTF ☆ <hr/> New: 2015-11-15 Updated: 2017-07-15	\bool_lazy_or_p:nn {<boolean expr ₁ >} {<boolean expr ₂ >} \bool_lazy_or:nnTF {<boolean expr ₁ >} {<boolean expr ₂ >} {<true code>} {<false code>} <hr/> Implements the “Or” operation between two boolean expressions, hence is true if either one is true . Contrarily to the infix operator <code> </code> , the <i><boolean expr₂></i> is only evaluated if it is needed to determine the result of <code>\bool_lazy_or:nnTF</code> . See also <code>\bool_lazy_any:nTF</code> when there are more than two <i><boolean expressions></i> .
<hr/> \bool_not_p:n ☆ <hr/> Updated: 2017-07-15	\bool_not_p:n {<boolean expression>} <hr/> Function version of <code>!(<boolean expression>)</code> within a boolean expression.
<hr/> \bool_xor_p:nn ☆ \bool_xor:nnTF ☆ <hr/> New: 2018-05-09	\bool_xor_p:nn {<boolean expr ₁ >} {<boolean expr ₂ >} \bool_xor:nnTF {<boolean expr ₁ >} {<boolean expr ₂ >} {<true code>} {<false code>} <hr/> Implements an “exclusive or” operation between two boolean expressions. There is no infix operation for this logical operation.

4 Logical loops

Loops using either boolean expressions or stored boolean values.

<hr/> \bool_do_until:Nn ☆ \bool_do_until:cn ☆ <hr/> Updated: 2017-07-15	\bool_do_until:Nn <boolean> {<code>} <hr/> Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean></i> . If it is false then the <i><code></i> is inserted into the input stream again and the process loops until the <i><boolean></i> is true .
<hr/> \bool_do_while:Nn ☆ \bool_do_while:cn ☆ <hr/> Updated: 2017-07-15	\bool_do_while:Nn <boolean> {<code>} <hr/> Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean></i> . If it is true then the <i><code></i> is inserted into the input stream again and the process loops until the <i><boolean></i> is false .
<hr/> \bool_until_do:Nn ☆ \bool_until_do:cn ☆ <hr/> Updated: 2017-07-15	\bool_until_do:Nn <boolean> {<code>} <hr/> This function firsts checks the logical value of the <i><boolean></i> . If it is false the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean></i> is re-evaluated. The process then loops until the <i><boolean></i> is true .
<hr/> \bool_while_do:Nn ☆ \bool_while_do:cn ☆ <hr/> Updated: 2017-07-15	\bool_while_do:Nn <boolean> {<code>} <hr/> This function firsts checks the logical value of the <i><boolean></i> . If it is true the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean></i> is re-evaluated. The process then loops until the <i><boolean></i> is false .

<hr/> <code>\bool_do_until:nn</code> ☆ <hr/>	<code>\bool_do_until:nn {<boolean expression>} {<code>}</code>
Updated: 2017-07-15	Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean expression></i> as described for <code>\bool_if:nTF</code> . If it is false then the <i><code></i> is inserted into the input stream again and the process loops until the <i><boolean expression></i> evaluates to true .
<hr/> <code>\bool_do_while:nn</code> ☆ <hr/>	<code>\bool_do_while:nn {<boolean expression>} {<code>}</code>
Updated: 2017-07-15	Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean expression></i> as described for <code>\bool_if:nTF</code> . If it is true then the <i><code></i> is inserted into the input stream again and the process loops until the <i><boolean expression></i> evaluates to false .
<hr/> <code>\bool_until_do:nn</code> ☆ <hr/>	<code>\bool_until_do:nn {<boolean expression>} {<code>}</code>
Updated: 2017-07-15	This function firsts checks the logical value of the <i><boolean expression></i> (as described for <code>\bool_if:nTF</code>). If it is false the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean expression></i> is re-evaluated. The process then loops until the <i><boolean expression></i> is true .
<hr/> <code>\bool_while_do:nn</code> ☆ <hr/>	<code>\bool_while_do:nn {<boolean expression>} {<code>}</code>
Updated: 2017-07-15	This function firsts checks the logical value of the <i><boolean expression></i> (as described for <code>\bool_if:nTF</code>). If it is true the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean expression></i> is re-evaluated. The process then loops until the <i><boolean expression></i> is false .

5 Producing multiple copies

<hr/> <code>\prg_replicate:nn</code> ☆ <hr/>	<code>\prg_replicate:nn {<integer expression>} {<tokens>}</code>
Updated: 2011-07-04	Evaluates the <i><integer expression></i> (which should be zero or positive) and creates the resulting number of copies of the <i><tokens></i> . The function is both expandable and safe for nesting. It yields its result after two expansion steps.

6 Detecting T_EX's mode

<hr/> <code>\mode_if_horizontal_p:</code> ☆ <code>\mode_if_horizontal:TF</code> ☆ <hr/>	<code>\mode_if_horizontal_p:</code> <code>\mode_if_horizontal:TF {<true code>} {<false code>}</code>
	Detects if T _E X is currently in horizontal mode.
<hr/> <code>\mode_if_inner_p:</code> ☆ <code>\mode_if_inner:TF</code> ☆ <hr/>	<code>\mode_if_inner_p:</code> <code>\mode_if_inner:TF {<true code>} {<false code>}</code>
	Detects if T _E X is currently in inner mode.
<hr/> <code>\mode_if_math_p:</code> ☆ <code>\mode_if_math:TF</code> ☆ <hr/>	<code>\mode_if_math:TF {<true code>} {<false code>}</code>
Updated: 2011-09-05	Detects if T _E X is currently in maths mode.

<code>\mode_if_vertical_p: *</code>	<code>\mode_if_vertical_p:</code>
<code>\mode_if_vertical:TF *</code>	<code>\mode_if_vertical:TF {\langle true code \rangle} {\langle false code \rangle}</code>

Detects if T_EX is currently in vertical mode.

7 Primitive conditionals

<code>\if_predicate:w *</code>	<code>\if_predicate:w \langle predicate \rangle \langle true code \rangle \else: \langle false code \rangle \fi:</code>
--------------------------------	---

This function takes a predicate function and branches according to the result. (In practice this function would also accept a single boolean variable in place of the $\langle predicate \rangle$ but to make the coding clearer this should be done through `\if_bool:N`.)

<code>\if_bool:N *</code>	<code>\if_bool:N \langle boolean \rangle \langle true code \rangle \else: \langle false code \rangle \fi:</code>
---------------------------	--

This function takes a boolean variable and branches according to the result.

8 Nestable recursions and mappings

There are a number of places where recursion or mapping constructs are used in `expl3`. At a low-level, these typically require insertion of tokens at the end of the content to allow “clean up”. To support such mappings in a nestable form, the following functions are provided.

<code>\prg_break_point:Nn *</code>	<code>\prg_break_point:Nn \langle type \rangle_map_break: {\langle code \rangle}</code>
------------------------------------	---

New: 2018-03-26

Used to mark the end of a recursion or mapping: the functions `\langle type \rangle_map_break:` and `\langle type \rangle_map_break:n` use this to break out of the loop (see `\prg_map_break:Nn` for how to set these up). After the loop ends, the $\langle code \rangle$ is inserted into the input stream. This occurs even if the break functions are *not* applied: `\prg_break_point:Nn` is functionally-equivalent in these cases to `\use_ii:nn`.

<code>\prg_map_break:Nn *</code>	<code>\prg_map_break:Nn \langle type \rangle_map_break: {\langle user code \rangle}</code>
----------------------------------	--

New: 2018-03-26

`...`
`\prg_break_point:Nn \langle type \rangle_map_break: {\langle ending code \rangle}`

Breaks a recursion in mapping contexts, inserting in the input stream the $\langle user code \rangle$ after the $\langle ending code \rangle$ for the loop. The function breaks loops, inserting their $\langle ending code \rangle$, until reaching a loop with the same $\langle type \rangle$ as its first argument. This `\langle type \rangle_map_break:` argument must be defined; it is simply used as a recognizable marker for the $\langle type \rangle$.

For types with mappings defined in the kernel, `\langle type \rangle_map_break:` and `\langle type \rangle_map_break:n` are defined as `\prg_map_break:Nn \langle type \rangle_map_break: {}` and the same with `{}` omitted.

8.1 Simple mappings

In addition to the more complex mappings above, non-nestable mappings are used in a number of locations and support is provided for these.

<code>\prg_break_point:</code> *	This copy of <code>\prg_do_nothing:</code> is used to mark the end of a fast short-term recursion:
New: 2018-03-27	the function <code>\prg_break:n</code> uses this to break out of the loop.

<code>\prg_break:</code> *	<code>\prg_break:n {<code>} ... \prg_break_point:</code>
<code>\prg_break:n</code> *	Breaks a recursion which has no <i><ending code></i> and which is not a user-breakable mapping
New: 2018-03-27	(see for instance <code>\prop_get:Nn</code>), and inserts the <i><code></i> in the input stream.

9 Internal programming functions

<code>\group_align_safe_begin:</code> *	<code>\group_align_safe_begin:</code>
<code>\group_align_safe_end:</code> *	...
Updated: 2011-08-11	<code>\group_align_safe_end:</code>

These functions are used to enclose material in a T_EX alignment environment within a specially-constructed group. This group is designed in such a way that it does not add brace groups to the output but does act as a group for the `&` token inside `\halign`. This is necessary to allow grabbing of tokens for testing purposes, as T_EX uses group level to determine the effect of alignment tokens. Without the special grouping, the use of a function such as `\peek_after:Nw` would result in a forbidden comparison of the internal `\endtemplate` token, yielding a fatal error. Each `\group_align_safe_begin:` must be matched by a `\group_align_safe_end:`, although this does not have to occur within the same function.

Part XIV

The l3sys package: System/runtime functions

1 The name of the job

`\c_sys_jobname_str`

New: 2015-09-19
Updated: 2019-10-27

Constant that gets the “job name” assigned when T_EX starts.

T_EXhackers note: This copies the contents of the primitive `\jobname`. For technical reasons, the string here is not of the same internal form as other, but may be manipulated using normal string functions.

2 Date and time

`\c_sys_minute_int`
`\c_sys_hour_int`
`\c_sys_day_int`
`\c_sys_month_int`
`\c_sys_year_int`

New: 2015-09-22

The date and time at which the current job was started: these are all reported as integers.

T_EXhackers note: Whilst the underlying primitives can be altered by the user, this interface to the time and date is intended to be the “real” values.

3 Engine

`\sys_if_engine luatex_p:` \star
`\sys_if_engine luatex:` *TF* \star
`\sys_if_engine pdftex_p:` \star
`\sys_if_engine pdftex:` *TF* \star
`\sys_if_engine ptex_p:` \star
`\sys_if_engine ptex:` *TF* \star
`\sys_if_engine uptex_p:` \star
`\sys_if_engine uptex:` *TF* \star
`\sys_if_engine xetex_p:` \star
`\sys_if_engine xetex:` *TF* \star

New: 2015-09-07

`\sys_if_engine pdftex:TF` $\{(true\ code)\} \{(false\ code)\}$

Conditionals which allow engine-specific code to be used. The names follow naturally from those of the engine binaries: note that the (u)ptex tests are for ε -pT_EX and ε -upT_EX as expl3 requires the ε -T_EX extensions. Each conditional is true for *exactly one* supported engine. In particular, `\sys_if_engine ptex_p:` is true for ε -pT_EX but false for ε -upT_EX.

`\c_sys_engine_str`

New: 2015-09-19

The current engine given as a lower case string: one of `luatex`, `pdftex`, `ptex`, `uptex` or `xetex`.

4 Output format

```
\sys_if_output_dvi_p: *
\sys_if_output_dvi:TF *
\sys_if_output_pdf_p: *
\sys_if_output_pdf:TF *
```

New: 2015-09-19

```
\sys_if_output_dvi:TF {\true code} {\false code}
```

Conditionals which give the current output mode the TeX run is operating in. This is always one of two outcomes, DVI mode or PDF mode. The two sets of conditionals are thus complementary and are both provided to allow the programmer to emphasise the most appropriate case.

```
\c_sys_output_str
```

New: 2015-09-19

The current output mode given as a lower case string: one of `dvi` or `pdf`.

5 Platform

```
\sys_if_platform_unix_p: * \sys_if_platform_unix:TF {\true code} {\false code}
\sys_if_platform_unix:TF *
\sys_if_platform_windows_p: *
\sys_if_platform_windows:TF *
```

New: 2018-07-27

Conditionals which allow platform-specific code to be used. The names follow the Lua `os.type()` function, *i.e.* all Unix-like systems are `unix` (including Linux and MacOS).

```
\c_sys_platform_str
```

New: 2018-07-27

The current platform given as a lower case string: one of `unix`, `windows` or `unknown`.

6 Random numbers

```
\sys_rand_seed: *
```

New: 2017-05-27

```
\sys_rand_seed:
```

Expands to the current value of the engine's random seed, a non-negative integer. In engines without random number support this expands to 0.

```
\sys_gset_rand_seed:n
```

New: 2017-05-27

```
\sys_gset_rand_seed:n {\intexpr}
```

Globally sets the seed for the engine's pseudo-random number generator to the *integer expression*. This random seed affects all `\..._rand` functions (such as `\int_rand:nn` or `\clist_rand_item:n`) as well as other packages relying on the engine's random number generator. In engines without random number support this produces an error.

TeXhackers note: While a 32-bit (signed) integer can be given as a seed, only the absolute value is used and any number beyond 2^{28} is divided by an appropriate power of 2. We recommend using an integer in $[0, 2^{28} - 1]$.

7 Access to the shell

<code>\sys_get_shell:nnN</code>	<code>\sys_get_shell:nnN {<shell command>} {<setup>} <tl var></code>
<code>\sys_get_shell:nnNTF</code>	<code>\sys_get_shell:nnNTF {<shell command>} {<setup>} <tl var> {<true code>} {<false code>}</code>

New: 2019-09-20

Defines `<tl>` to the text returned by the `<shell command>`. The `<shell command>` is converted to a string using `\tl_to_str:n`. Category codes may need to be set appropriately via the `<setup>` argument, which is run just before running the `<shell command>` (in a group). If shell escape is disabled, the `<tl var>` will be set to `\q_no_value` in the non-branching version. Note that quote characters (") *cannot* be used inside the `<shell command>`. The `\sys_get_shell:nnNTF` conditional returns `true` if the shell is available and no quote is detected, and `false` otherwise.

<code>\c_sys_shell_escape_int</code>

New: 2017-05-27

This variable exposes the internal triple of the shell escape status. The possible values are

- 0 Shell escape is disabled
- 1 Unrestricted shell escape is enabled
- 2 Restricted shell escape is enabled

<code>\sys_if_shell_p: *</code>	<code>\sys_if_shell_p:</code>
<code>\sys_if_shell:TF *</code>	<code>\sys_if_shell:TF {<true code>} {<false code>}</code>

New: 2017-05-27

Performs a check for whether shell escape is enabled. This returns true if either of restricted or unrestricted shell escape is enabled.

<code>\sys_if_shell_unrestricted_p: *</code>	<code>\sys_if_shell_unrestricted_p:</code>
<code>\sys_if_shell_unrestricted:TF *</code>	<code>\sys_if_shell_unrestricted:TF {<true code>} {<false code>}</code>

New: 2017-05-27

Performs a check for whether *unrestricted* shell escape is enabled.

<code>\sys_if_shell_restricted_p: *</code>	<code>\sys_if_shell_restricted_p:</code>
<code>\sys_if_shell_restricted:TF *</code>	<code>\sys_if_shell_restricted:TF {<true code>} {<false code>}</code>

New: 2017-05-27

Performs a check for whether *restricted* shell escape is enabled. This returns false if unrestricted shell escape is enabled. Unrestricted shell escape is not considered a superset of restricted shell escape in this case. To find whether any shell escape is enabled use `\sys_if_shell:`.

<code>\sys_shell_now:n</code>	<code>\sys_shell_now:n {<tokens>}</code>
<code>\sys_shell_now:x</code>	

New: 2017-05-27

Execute `<tokens>` through shell escape immediately.

<code>\sys_shell_shipout:n</code>	<code>\sys_shell_shipout:n {<tokens>}</code>
<code>\sys_shell_shipout:x</code>	

New: 2017-05-27

Execute `<tokens>` through shell escape at shipout.

7.1 Loading configuration data

<hr/> <code>\sys_load_backend:n</code> <hr/>	<code>\sys_load_backend:n {<backend>}</code>
<hr/> New: 2019-09-12 <hr/>	Loads the additional configuration file needed for backend support. If the <i><backend></i> is empty, the standard backend for the engine in use will be loaded. This command may only be used once.
<hr/> <code>\c_sys_backend_str</code> <hr/>	Set to the name of the backend in use by <code>\sys_load_backend:n</code> when issued.
<hr/> <code>\sys_load_debug:</code> <code>\sys_load_deprecation:</code> <hr/>	<code>\sys_load_debug:</code> <code>\sys_load_deprecation:</code>
<hr/> New: 2019-09-12 <hr/>	Load the additional configuration files for debugging support and rolling back deprecations, respectively.

7.2 Final settins

<hr/> <code>\sys_finalise:</code> <hr/>	<code>\sys_finalise:</code>
<hr/> New: 2019-10-06 <hr/>	Finalises all system-dependent functionality: required before loading a backend.

Part XV

The `l3clist` package

Comma separated lists

Comma lists contain ordered data where items can be added to the left or right end of the list. This data type allows basic list manipulations such as adding/removing items, applying a function to every item, removing duplicate items, extracting a given item, using the comma list with specified separators, and so on. Sequences (defined in `l3seq`) are safer, faster, and provide more features, so they should often be preferred to comma lists. Comma lists are mostly useful when interfacing with L^AT_EX 2_ε or other code that expects or provides comma list data.

Several items can be added at once. To ease input of comma lists from data provided by a user outside an `\ExplSyntaxOn ... \ExplSyntaxOff` block, spaces are removed from both sides of each comma-delimited argument upon input. Blank arguments are ignored, to allow for trailing commas or repeated commas (which may otherwise arise when concatenating comma lists “by hand”). In addition, a set of braces is removed if the result of space-trimming is braced: this allows the storage of any item in a comma list. For instance,

```
\clist_new:N \l_my_clist
\clist_put_left:Nn \l_my_clist { ~a~ , ~{b}~ , c~\d }
\clist_put_right:Nn \l_my_clist { ~{e}~ , , {{f}} , }
```

results in `\l_my_clist` containing `a,b,c~\d,{e~},{f}}` namely the five items `a`, `b`, `c~\d`, `e~` and `{f}`. Comma lists normally do not contain empty items so the following gives an empty comma list:

```
\clist_clear_new:N \l_my_clist
\clist_put_right:Nn \l_my_clist { , ~ , , }
\clist_if_empty:NTF \l_my_clist { true } { false }
```

and it leaves `true` in the input stream. To include an “unsafe” item (empty, or one that contains a comma, or starts or ends with a space, or is a single brace group), surround it with braces.

Almost all operations on comma lists are noticeably slower than those on sequences so converting the data to sequences using `\seq_set_from_clist:Nn` (see `l3seq`) may be advisable if speed is important. The exception is that `\clist_if_in:NnTF` and `\clist_remove_duplicates:N` may be faster than their sequence analogues for large lists. However, these functions work slowly for “unsafe” items that must be braced, and may produce errors when their argument contains `{`, `}` or `#` (assuming the usual T_EX category codes apply). The sequence data type should thus certainly be preferred to comma lists to store such items.

1 Creating and initialising comma lists

<code>\clist_new:N</code>	<code>\clist_new:N <comma list></code>
<code>\clist_new:c</code>	

Creates a new *<comma list>* or raises an error if the name is already taken. The declaration is global. The *<comma list>* initially contains no items.

<hr/> <code>\clist_const:Nn</code> <code>\clist_const:(Nx cn cx)</code> <hr/> New: 2014-07-05	<code>\clist_const:Nn <clist var> {<comma list>}</code> Creates a new constant <code><clist var></code> or raises an error if the name is already taken. The value of the <code><clist var></code> is set globally to the <code><comma list></code> .
<hr/> <code>\clist_clear:N</code> <code>\clist_clear:c</code> <code>\clist_gclear:N</code> <code>\clist_gclear:c</code> <hr/>	<code>\clist_clear:N <comma list></code> Clears all items from the <code><comma list></code> .
<hr/> <code>\clist_clear_new:N</code> <code>\clist_clear_new:c</code> <code>\clist_gclear_new:N</code> <code>\clist_gclear_new:c</code> <hr/>	<code>\clist_clear_new:N <comma list></code> Ensures that the <code><comma list></code> exists globally by applying <code>\clist_new:N</code> if necessary, then applies <code>\clist_(g)clear:N</code> to leave the list empty.
<hr/> <code>\clist_set_eq:NN</code> <code>\clist_set_eq:(cN Nc cc)</code> <code>\clist_gset_eq:NN</code> <code>\clist_gset_eq:(cN Nc cc)</code> <hr/>	<code>\clist_set_eq:NN <comma list_{12 Sets the content of <code><comma list_{1 equal to that of <code><comma list_{2.}</code>}</code>}</code>
<hr/> <code>\clist_set_from_seq:NN</code> <code>\clist_set_from_seq:(cN Nc cc)</code> <code>\clist_gset_from_seq:NN</code> <code>\clist_gset_from_seq:(cN Nc cc)</code> <hr/> New: 2014-07-17	<code>\clist_set_from_seq:NN <comma list> <sequence></code> Converts the data in the <code><sequence></code> into a <code><comma list></code> : the original <code><sequence></code> is unchanged. Items which contain either spaces or commas are surrounded by braces.
<hr/> <code>\clist_concat:NNN</code> <code>\clist_concat:ccc</code> <code>\clist_gconcat:NNN</code> <code>\clist_gconcat:ccc</code> <hr/>	<code>\clist_concat:NNN <comma list_{123 Concatenates the content of <code><comma list_{2 and <code><comma list_{3 together and saves the result in <code><comma list_{1. The items in <code><comma list_{2 are placed at the left side of the new comma list.}</code>}</code>}</code>}</code>}</code>
<hr/> <code>\clist_if_exist_p:N *</code> <code>\clist_if_exist_p:c *</code> <code>\clist_if_exist:N\overline{TF} *</code> <code>\clist_if_exist:c\overline{TF} *</code> <hr/> New: 2012-03-03	<code>\clist_if_exist_p:N <comma list></code> <code>\clist_if_exist:NTF <comma list> {<true code>} {<false code>}</code> Tests whether the <code><comma list></code> is currently defined. This does not check that the <code><comma list></code> really is a comma list.

2 Adding data to comma lists

<code>\clist_set:Nn</code>	<code>\clist_set:Nn <comma list> {\langle item_1\rangle,\dots,\langle item_n\rangle}</code>
<code>\clist_set:(NV No Nx cn cV co cx)</code>	
<code>\clist_gset:Nn</code>	
<code>\clist_gset:(NV No Nx cn cV co cx)</code>	

New: 2011-09-06

Sets $\langle comma list \rangle$ to contain the $\langle items \rangle$, removing any previous content from the variable. Blank items are omitted, spaces are removed from both sides of each item, then a set of braces is removed if the resulting space-trimmed item is braced. To store some $\langle tokens \rangle$ as a single $\langle item \rangle$ even if the $\langle tokens \rangle$ contain commas or spaces, add a set of braces: `\clist_set:Nn <comma list> { {\langle tokens \rangle} }`.

<code>\clist_put_left:Nn</code>	<code>\clist_put_left:Nn <comma list> {\langle item_1\rangle,\dots,\langle item_n\rangle}</code>
<code>\clist_put_left:(NV No Nx cn cV co cx)</code>	
<code>\clist_gput_left:Nn</code>	
<code>\clist_gput_left:(NV No Nx cn cV co cx)</code>	

Updated: 2011-09-05

Appends the $\langle items \rangle$ to the left of the $\langle comma list \rangle$. Blank items are omitted, spaces are removed from both sides of each item, then a set of braces is removed if the resulting space-trimmed item is braced. To append some $\langle tokens \rangle$ as a single $\langle item \rangle$ even if the $\langle tokens \rangle$ contain commas or spaces, add a set of braces: `\clist_put_left:Nn <comma list> { {\langle tokens \rangle} }`.

<code>\clist_put_right:Nn</code>	<code>\clist_put_right:Nn <comma list> {\langle item_1\rangle,\dots,\langle item_n\rangle}</code>
<code>\clist_put_right:(NV No Nx cn cV co cx)</code>	
<code>\clist_gput_right:Nn</code>	
<code>\clist_gput_right:(NV No Nx cn cV co cx)</code>	

Updated: 2011-09-05

Appends the $\langle items \rangle$ to the right of the $\langle comma list \rangle$. Blank items are omitted, spaces are removed from both sides of each item, then a set of braces is removed if the resulting space-trimmed item is braced. To append some $\langle tokens \rangle$ as a single $\langle item \rangle$ even if the $\langle tokens \rangle$ contain commas or spaces, add a set of braces: `\clist_put_right:Nn <comma list> { {\langle tokens \rangle} }`.

3 Modifying comma lists

While comma lists are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update comma lists, while retaining the order of the unaffected entries.

<code>\clist_remove_duplicates:N</code>	<code>\clist_remove_duplicates:N <comma list></code>
<code>\clist_remove_duplicates:c</code>	
<code>\clist_gremove_duplicates:N</code>	
<code>\clist_gremove_duplicates:c</code>	

Removes duplicate items from the $\langle comma list \rangle$, leaving the left most copy of each item in the $\langle comma list \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

T_EXhackers note: This function iterates through every item in the $\langle comma list \rangle$ and does a comparison with the $\langle items \rangle$ already checked. It is therefore relatively slow with large comma lists. Furthermore, it may fail if any of the items in the $\langle comma list \rangle$ contains `{`, `}`, or `#` (assuming the usual T_EX category codes apply).

<code>\clist_remove_all:Nn</code>	<code>\clist_remove_all:Nn <comma list> {<item>}</code>
<code>\clist_remove_all:cn</code>	
<code>\clist_gremove_all:Nn</code>	
<code>\clist_gremove_all:cn</code>	

Removes every occurrence of $\langle item \rangle$ from the $\langle comma list \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

Updated: 2011-09-06

T_EXhackers note: The function may fail if the $\langle item \rangle$ contains `{`, `}`, or `#` (assuming the usual T_EX category codes apply).

<code>\clist_reverse:N</code>	<code>\clist_reverse:N <comma list></code>
<code>\clist_reverse:c</code>	
<code>\clist_greverse:N</code>	
<code>\clist_greverse:c</code>	

New: 2014-07-18

Reverses the order of items stored in the $\langle comma list \rangle$.

<code>\clist_reverse:n</code>	<code>\clist_reverse:n {<comma list>}</code>
-------------------------------	--

New: 2014-07-18

Leaves the items in the $\langle comma list \rangle$ in the input stream in reverse order. Contrarily to other what is done for other n-type $\langle comma list \rangle$ arguments, braces and spaces are preserved by this process.

T_EXhackers note: The result is returned within `\unexpanded`, which means that the comma list does not expand further when appearing in an x-type or e-type argument expansion.

<code>\clist_sort:Nn</code>	<code>\clist_sort:Nn <clist var> {<comparison code>}</code>
<code>\clist_sort:cn</code>	
<code>\clist_gsort:Nn</code>	
<code>\clist_gsort:cn</code>	

New: 2017-02-06

Sorts the items in the $\langle clist var \rangle$ according to the $\langle comparison code \rangle$, and assigns the result to $\langle clist var \rangle$. The details of sorting comparison are described in Section 1.

4 Comma list conditionals

<code>\clist_if_empty_p:N</code> *	<code>\clist_if_empty_p:N</code> $\langle comma list \rangle$
<code>\clist_if_empty_p:c</code> *	<code>\clist_if_empty:N</code> $\langle comma list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
<code>\clist_if_empty:N</code> <u><i>TF</i></u> *	Tests if the $\langle comma list \rangle$ is empty (containing no items).
<code>\clist_if_empty:c</code> <u><i>TF</i></u> *	

<code>\clist_if_empty_p:n</code> *	<code>\clist_if_empty_p:n</code> $\{\langle comma list \rangle\}$
<code>\clist_if_empty:n</code> <u><i>TF</i></u> *	<code>\clist_if_empty:n</code> $\{\langle comma list \rangle\}$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

New: 2014-07-05

Tests if the $\langle comma list \rangle$ is empty (containing no items). The rules for space trimming are as for other n-type comma-list functions, hence the comma list $\{\sim, \sim, \sim\}$ (without outer braces) is empty, while $\{\sim, \{ \}, \}$ (without outer braces) contains one element, which happens to be empty: the comma-list is not empty.

<code>\clist_if_in:Nn</code> <u><i>TF</i></u>	<code>\clist_if_in:Nn</code> $\langle comma list \rangle$ $\langle item \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
<code>\clist_if_in:(NV No cn cV co)</code> <u><i>TF</i></u>	
<code>\clist_if_in:nn</code> <u><i>TF</i></u>	
<code>\clist_if_in:(nV no)</code> <u><i>TF</i></u>	

Updated: 2011-09-06

Tests if the $\langle item \rangle$ is present in the $\langle comma list \rangle$. In the case of an n-type $\langle comma list \rangle$, the usual rules of space trimming and brace stripping apply. Hence,

`\clist_if_in:nn` $\{ a , \{b\} \sim , \{b\} , c \} \{ b \} \{ true \} \{ false \}$

yields true.

T_EXhackers note: The function may fail if the $\langle item \rangle$ contains $\{$, $\}$, or $\#$ (assuming the usual T_EX category codes apply).

5 Mapping to comma lists

The functions described in this section apply a specified function to each item of a comma list. All mappings are done at the current group level, *i.e.* any local assignments made by the $\langle function \rangle$ or $\langle code \rangle$ discussed below remain in effect after the loop.

When the comma list is given explicitly, as an n-type argument, spaces are trimmed around each item. If the result of trimming spaces is empty, the item is ignored. Otherwise, if the item is surrounded by braces, one set is removed, and the result is passed to the mapped function. Thus, if the comma list that is being mapped is $\{a_{\sim},_{\sim}\{b\}_{\sim},_{\sim}\{ \},_{\sim}\{c\},_{\sim}\}$ then the arguments passed to the mapped function are ‘a’, ‘ $\{b\}_{\sim}$ ’, an empty argument, and ‘c’.

When the comma list is given as an N-type argument, spaces have already been trimmed on input, and items are simply stripped of one set of braces if any. This case is more efficient than using n-type comma lists.

<code>\clist_map_function:NN</code> ☆	<code>\clist_map_function:NN</code> $\langle comma list \rangle$ $\langle function \rangle$
<code>\clist_map_function:cN</code> ☆	Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle comma list \rangle$. The $\langle function \rangle$ receives one argument for each iteration. The $\langle items \rangle$ are returned from left to right. The function
<code>\clist_map_function:nN</code> ☆	<code>\clist_map_inline:Nn</code> is in general more efficient than <code>\clist_map_function:NN</code> .

Updated: 2012-06-29

```
\clist_map_inline:Nn
\clist_map_inline:cn
\clist_map_inline:nn
```

Updated: 2012-06-29

```
\clist_map_inline:Nn <comma list> {<inline function>}
```

Applies *<inline function>* to every *<item>* stored within the *<comma list>*. The *<inline function>* should consist of code which receives the *<item>* as #1. The *<items>* are returned from left to right.

```
\clist_map_variable:NNn
\clist_map_variable:cNn
\clist_map_variable:nNn
```

Updated: 2012-06-29

```
\clist_map_variable:NNn <comma list> <variable> {<code>}
```

Stores each *<item>* of the *<comma list>* in turn in the (token list) *<variable>* and applies the *<code>*. The *<code>* will usually make use of the *<variable>*, but this is not enforced. The assignments to the *<variable>* are local. Its value after the loop is the last *<item>* in the *<comma list>*, or its original value if there were no *<item>*. The *<items>* are returned from left to right.

```
\clist_map_break: ☆
```

Updated: 2012-06-29

```
\clist_map_break:
```

Used to terminate a `\clist_map_...` function before all entries in the *<comma list>* have been processed. This normally takes place within a conditional statement, for example

```
\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\clist_map_...` scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

`\clist_map_break:n` ☆

Updated: 2012-06-29

`\clist_map_break:n` {<code>}

Used to terminate a `\clist_map_...` function before all entries in the <comma list> have been processed, inserting the <code> after the mapping has ended. This normally takes place within a conditional statement, for example

```
\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break:n { <code> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\clist_map_...` scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before the <code> is inserted into the input stream. This depends on the design of the mapping function.

`\clist_count:N` ★

`\clist_count:c` ★

`\clist_count:n` ★

New: 2012-07-13

`\clist_count:N` <comma list>

Leaves the number of items in the <comma list> in the input stream as an <integer denotation>. The total number of items in a <comma list> includes those which are duplicates, *i.e.* every item in a <comma list> is counted.

6 Using the content of comma lists directly

`\clist_use:Nnnn` ★

`\clist_use:cnnn` ★

New: 2013-05-26

`\clist_use:Nnnn` <clist var> {<separator between two>}

{<separator between more than two>} {<separator between final two>}

Places the contents of the <clist var> in the input stream, with the appropriate <separator> between the items. Namely, if the comma list has more than two items, the <separator between more than two> is placed between each pair of items except the last, for which the <separator between final two> is used. If the comma list has exactly two items, then they are placed in the input stream separated by the <separator between two>. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nnnn \l_tmpa_clist { ~and~ } { ,~ } { ,~and~ }
```

inserts “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the comma list has more than 2 items.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the <items> do not expand further when appearing in an x-type argument expansion.

`\clist_use:Nn` ★
`\clist_use:cn` ★

New: 2013-05-26

`\clist_use:Nn` $\langle\textit{clist var}\rangle$ $\{\langle\textit{separator}\rangle\}$

Places the contents of the $\langle\textit{clist var}\rangle$ in the input stream, with the $\langle\textit{separator}\rangle$ between the items. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nn \l_tmpa_clist { ~and~ }
```

inserts “a and b and c and de and f” in the input stream.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle\textit{items}\rangle$ do not expand further when appearing in an `x`-type argument expansion.

7 Comma lists as stacks

Comma lists can be used as stacks, where data is pushed to and popped from the top of the comma list. (The left of a comma list is the top, for performance reasons.) The stack functions for comma lists are not intended to be mixed with the general ordered data functions detailed in the previous section: a comma list should either be used as an ordered data type or as a stack, but not in both ways.

`\clist_get:NN`
`\clist_get:cn`
`\clist_get:NNTF`
`\clist_get:cNTF`

New: 2012-05-14
Updated: 2019-02-16

`\clist_get:NN` $\langle\textit{comma list}\rangle$ $\langle\textit{token list variable}\rangle$

Stores the left-most item from a $\langle\textit{comma list}\rangle$ in the $\langle\textit{token list variable}\rangle$ without removing it from the $\langle\textit{comma list}\rangle$. The $\langle\textit{token list variable}\rangle$ is assigned locally. In the non-branching version, if the $\langle\textit{comma list}\rangle$ is empty the $\langle\textit{token list variable}\rangle$ is set to the marker value `\q_no_value`.

`\clist_pop:NN`
`\clist_pop:cn`

Updated: 2011-09-06

`\clist_pop:NN` $\langle\textit{comma list}\rangle$ $\langle\textit{token list variable}\rangle$

Pops the left-most item from a $\langle\textit{comma list}\rangle$ into the $\langle\textit{token list variable}\rangle$, *i.e.* removes the item from the comma list and stores it in the $\langle\textit{token list variable}\rangle$. Both of the variables are assigned locally.

`\clist_gpop:NN`
`\clist_gpop:cn`

`\clist_gpop:NN` $\langle\textit{comma list}\rangle$ $\langle\textit{token list variable}\rangle$

Pops the left-most item from a $\langle\textit{comma list}\rangle$ into the $\langle\textit{token list variable}\rangle$, *i.e.* removes the item from the comma list and stores it in the $\langle\textit{token list variable}\rangle$. The $\langle\textit{comma list}\rangle$ is modified globally, while the assignment of the $\langle\textit{token list variable}\rangle$ is local.

`\clist_pop:NNTF`
`\clist_pop:cNTF`

New: 2012-05-14

`\clist_pop:NNTF` $\langle\textit{comma list}\rangle$ $\langle\textit{token list variable}\rangle$ $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

If the $\langle\textit{comma list}\rangle$ is empty, leaves the $\langle\textit{false code}\rangle$ in the input stream. The value of the $\langle\textit{token list variable}\rangle$ is not defined in this case and should not be relied upon. If the $\langle\textit{comma list}\rangle$ is non-empty, pops the top item from the $\langle\textit{comma list}\rangle$ in the $\langle\textit{token list variable}\rangle$, *i.e.* removes the item from the $\langle\textit{comma list}\rangle$. Both the $\langle\textit{comma list}\rangle$ and the $\langle\textit{token list variable}\rangle$ are assigned locally.

<hr/> <code>\clist_gpop:NNTF</code> <hr/>	<code>\clist_gpop:NNTF <comma list> <token list variable> {<true code>} {<false code>}</code>
<code>\clist_gpop:cNTF</code> <hr/>	
New: 2012-05-14	

If the *<comma list>* is empty, leaves the *<false code>* in the input stream. The value of the *<token list variable>* is not defined in this case and should not be relied upon. If the *<comma list>* is non-empty, pops the top item from the *<comma list>* in the *<token list variable>*, *i.e.* removes the item from the *<comma list>*. The *<comma list>* is modified globally, while the *<token list variable>* is assigned locally.

<hr/> <code>\clist_push:Nn</code> <hr/>	<code>\clist_push:Nn <comma list> {<items>}</code>
<code>\clist_push:(NV No Nx cn cV co cx)</code>	
<code>\clist_gpush:Nn</code>	
<code>\clist_gpush:(NV No Nx cn cV co cx)</code> <hr/>	

Adds the *{<items>}* to the top of the *<comma list>*. Spaces are removed from both sides of each item as for any n-type comma list.

8 Using a single item

<hr/> <code>\clist_item:Nn *</code> <hr/>	<code>\clist_item:Nn <comma list> {<integer expression>}</code>
<code>\clist_item:cn *</code>	
<code>\clist_item:nn *</code> <hr/>	
New: 2014-07-17	

Indexing items in the *<comma list>* from 1 at the top (left), this function evaluates the *<integer expression>* and leaves the appropriate item from the comma list in the input stream. If the *<integer expression>* is negative, indexing occurs from the bottom (right) of the comma list. When the *<integer expression>* is larger than the number of items in the *<comma list>* (as calculated by `\clist_count:N`) then the function expands to nothing.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an x-type argument expansion.

<hr/> <code>\clist_rand_item:N *</code> <hr/>	<code>\clist_rand_item:N <clist var></code>
<code>\clist_rand_item:c *</code>	<code>\clist_rand_item:n {<comma list>}</code>
<code>\clist_rand_item:n *</code> <hr/>	
New: 2016-12-06	

Selects a pseudo-random item of the *<comma list>*. If the *<comma list>* has no item, the result is empty.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an x-type argument expansion.

9 Viewing comma lists

<hr/> <code>\clist_show:N</code> <hr/>	<code>\clist_show:N <comma list></code>
<code>\clist_show:c</code> <hr/>	
Updated: 2015-08-03	

Displays the entries in the *<comma list>* in the terminal.

<hr/> <code>\clist_show:n</code> <hr/>	<code>\clist_show:n {\tokens}</code>
Updated: 2013-08-03	Displays the entries in the comma list in the terminal.
<hr/>	
<code>\clist_log:N</code> <code>\clist_log:c</code> <hr/>	<code>\clist_log:N <comma list></code>
New: 2014-08-22 Updated: 2015-08-03	Writes the entries in the <i><comma list></i> in the log file. See also <code>\clist_show:N</code> which displays the result in the terminal.
<hr/>	
<code>\clist_log:n</code> <hr/>	<code>\clist_log:n {\tokens}</code>
New: 2014-08-22	Writes the entries in the comma list in the log file. See also <code>\clist_show:n</code> which displays the result in the terminal.

10 Constant and scratch comma lists

<hr/> <code>\c_empty_clist</code> <hr/>	Constant that is always empty.
New: 2012-07-02	
<hr/>	
<code>\l_tmpa_clist</code> <code>\l_tmpb_clist</code> <hr/>	Scratch comma lists for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
New: 2011-09-06	
<hr/>	
<code>\g_tmpa_clist</code> <code>\g_tmpb_clist</code> <hr/>	Scratch comma lists for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
New: 2011-09-06	

Part XVI

The l3token package

Token manipulation

This module deals with tokens. Now this is perhaps not the most precise description so let's try with a better description: When programming in T_EX, it is often desirable to know just what a certain token is: is it a control sequence or something else. Similarly one often needs to know if a control sequence is expandable or not, a macro or a primitive, how many arguments it takes etc. Another thing of great importance (especially when it comes to document commands) is looking ahead in the token stream to see if a certain character is present and maybe even remove it or disregard other tokens while scanning. This module provides functions for both and as such has two primary function categories: `\token_` for anything that deals with tokens and `\peek_` for looking ahead in the token stream.

Most functions we describe here can be used on control sequences, as those are tokens as well.

It is important to distinguish two aspects of a token: its “shape” (for lack of a better word), which affects the matching of delimited arguments and the comparison of token lists containing this token, and its “meaning”, which affects whether the token expands or what operation it performs. One can have tokens of different shapes with the same meaning, but not the converse.

For instance, `\if:w`, `\if_charcode:w`, and `\tex_if:D` are three names for the same internal operation of T_EX, namely the primitive testing the next two characters for equality of their character code. They have the same meaning hence behave identically in many situations. However, T_EX distinguishes them when searching for a delimited argument. Namely, the example function `\show_until_if:w` defined below takes everything until `\if:w` as an argument, despite the presence of other copies of `\if:w` under different names.

```
\cs_new:Npn \show_until_if:w #1 \if:w { \tl_show:n {#1} }
\show_until_if:w \tex_if:D \if_charcode:w \if:w
```

A list of all possible shapes and a list of all possible meanings are given in section 7.

1 Creating character tokens

```
\char_set_active_eq:NN
\char_set_active_eq:Nc
\char_gset_active_eq:NN
\char_gset_active_eq:Nc
```

Updated: 2015-11-12

```
\char_set_active_eq:NN <char> <function>
```

Sets the behaviour of the `<char>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

```
\char_set_active_eq:nN
\char_set_active_eq:nc
\char_gset_active_eq:nN
\char_gset_active_eq:nc
```

New: 2015-11-12

```
\char_set_active_eq:nN {<integer expression>} <function>
```

Sets the behaviour of the `<char>` which has character code as given by the `<integer expression>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

<hr/> <code>\char_generate:nn</code> ★ <hr/>	<code>\char_generate:nn</code> { $\langle charcode \rangle$ } { $\langle catcode \rangle$ }
New: 2015-09-09 Updated: 2019-01-16	Generates a character token of the given $\langle charcode \rangle$ and $\langle catcode \rangle$ (both of which may be integer expressions). The $\langle catcode \rangle$ may be one of

- 1 (begin group)
- 2 (end group)
- 3 (math toggle)
- 4 (alignment)
- 6 (parameter)
- 7 (math superscript)
- 8 (math subscript)
- 11 (letter)
- 12 (other)
- 13 (active)

and other values raise an error. The $\langle charcode \rangle$ may be any one valid for the engine in use. Active characters cannot be generated in older versions of X_YTeX.

T_EXhackers note: Exactly two expansions are needed to produce the character.

<hr/> <code>\char_lowercase:N</code> ★ <hr/>	<code>\char_lowercase:N</code> $\langle char \rangle$
<code>\char_uppercase:N</code> ★	Converts the $\langle char \rangle$ to the equivalent case-changed character as detailed by the function name (see <code>\str_foldcase:n</code> and <code>\text_titlecase:n</code> for details of these terms). The case mapping is carried out with no context-dependence (<i>cf.</i> <code>\text_uppercase:n</code> , <i>etc.</i>) The str versions always generate “other” (category code 12) characters, whilst the standard versions generate characters with the category code of the $\langle char \rangle$ (i.e. only the character code changes).
<code>\char_titlecase:N</code> ★	
<code>\char_foldcase:N</code> ★	
<code>\char_str_lowercase:N</code> ★	
<code>\char_str_uppercase:N</code> ★	
<code>\char_str_titlecase:N</code> ★	
<code>\char_str_foldcase:N</code> ★	
New: 2020-01-09	

<hr/> <code>\c_catcode_other_space_tl</code> <hr/>	Token list containing one character with category code 12, (“other”), and character code 32 (space).
New: 2011-09-05	

2 Manipulating and interrogating character tokens

<code>\char_set_catcode_escape:N</code>	<code>\char_set_catcode_letter:N</code> $\langle character \rangle$
<code>\char_set_catcode_group_begin:N</code>	
<code>\char_set_catcode_group_end:N</code>	
<code>\char_set_catcode_math_toggle:N</code>	
<code>\char_set_catcode_alignment:N</code>	
<code>\char_set_catcode_end_line:N</code>	
<code>\char_set_catcode_parameter:N</code>	
<code>\char_set_catcode_math_superscript:N</code>	
<code>\char_set_catcode_math_subscript:N</code>	
<code>\char_set_catcode_ignore:N</code>	
<code>\char_set_catcode_space:N</code>	
<code>\char_set_catcode_letter:N</code>	
<code>\char_set_catcode_other:N</code>	
<code>\char_set_catcode_active:N</code>	
<code>\char_set_catcode_comment:N</code>	
<code>\char_set_catcode_invalid:N</code>	

Updated: 2015-11-11

Sets the category code of the $\langle character \rangle$ to that indicated in the function name. Depending on the current category code of the $\langle token \rangle$ the escape token may also be needed:

`\char_set_catcode_other:N \%`

The assignment is local.

<code>\char_set_catcode_escape:n</code>	<code>\char_set_catcode_letter:n</code> $\{ \langle integer\ expression \rangle \}$
<code>\char_set_catcode_group_begin:n</code>	
<code>\char_set_catcode_group_end:n</code>	
<code>\char_set_catcode_math_toggle:n</code>	
<code>\char_set_catcode_alignment:n</code>	
<code>\char_set_catcode_end_line:n</code>	
<code>\char_set_catcode_parameter:n</code>	
<code>\char_set_catcode_math_superscript:n</code>	
<code>\char_set_catcode_math_subscript:n</code>	
<code>\char_set_catcode_ignore:n</code>	
<code>\char_set_catcode_space:n</code>	
<code>\char_set_catcode_letter:n</code>	
<code>\char_set_catcode_other:n</code>	
<code>\char_set_catcode_active:n</code>	
<code>\char_set_catcode_comment:n</code>	
<code>\char_set_catcode_invalid:n</code>	

Updated: 2015-11-11

Sets the category code of the $\langle character \rangle$ which has character code as given by the $\langle integer\ expression \rangle$. This version can be used to set up characters which cannot otherwise be given (*cf.* the N-type variants). The assignment is local.

<hr/> <code>\char_set_catcode:nn</code> <hr/>	<code>\char_set_catcode:nn {⟨integer₁⟩} {⟨integer₂⟩}</code>
<hr/> Updated: 2015-11-11 <hr/>	These functions set the category code of the <i>⟨character⟩</i> which has character code as given by the <i>⟨integer expression⟩</i> . The first <i>⟨integer expression⟩</i> is the character code and the second is the category code to apply. The setting applies within the current T _E X group. In general, the symbolic functions <code>\char_set_catcode_⟨type⟩</code> should be preferred, but there are cases where these lower-level functions may be useful.
<hr/> <code>\char_value_catcode:n</code> ★ <hr/>	<code>\char_value_catcode:n {⟨integer expression⟩}</code>
	Expands to the current category code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <code>\char_show_value_catcode:n</code> <hr/>	<code>\char_show_value_catcode:n {⟨integer expression⟩}</code>
	Displays the current category code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\char_set_lccode:nn</code> <hr/>	<code>\char_set_lccode:nn {⟨integer₁⟩} {⟨integer₂⟩}</code>
<hr/> Updated: 2015-08-06 <hr/>	Sets up the behaviour of the <i>⟨character⟩</i> when found inside <code>\text_lowercase:n</code> , such that <i>⟨character₁⟩</i> will be converted into <i>⟨character₂⟩</i> . The two <i>⟨characters⟩</i> may be specified using an <i>⟨integer expression⟩</i> for the character code concerned. This may include the T _E X ‘ <i>⟨character⟩</i> ’ method for converting a single character into its character code:
	<pre> \char_set_lccode:nn { ‘\A } { ‘a } % Standard behaviour \char_set_lccode:nn { ‘\A } { ‘\A + 32 } \char_set_lccode:nn { 50 } { 60 } </pre>
	The setting applies within the current T _E X group.
<hr/> <code>\char_value_lccode:n</code> ★ <hr/>	<code>\char_value_lccode:n {⟨integer expression⟩}</code>
	Expands to the current lower case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <code>\char_show_value_lccode:n</code> <hr/>	<code>\char_show_value_lccode:n {⟨integer expression⟩}</code>
	Displays the current lower case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\char_set_uccode:nn</code> <hr/>	<code>\char_set_uccode:nn {⟨integer₁⟩} {⟨integer₂⟩}</code>
<hr/> Updated: 2015-08-06 <hr/>	Sets up the behaviour of the <i>⟨character⟩</i> when found inside <code>\text_uppercase:n</code> , such that <i>⟨character₁⟩</i> will be converted into <i>⟨character₂⟩</i> . The two <i>⟨characters⟩</i> may be specified using an <i>⟨integer expression⟩</i> for the character code concerned. This may include the T _E X ‘ <i>⟨character⟩</i> ’ method for converting a single character into its character code:
	<pre> \char_set_uccode:nn { ‘a } { ‘\A } % Standard behaviour \char_set_uccode:nn { ‘\A } { ‘\A - 32 } \char_set_uccode:nn { 60 } { 50 } </pre>
	The setting applies within the current T _E X group.

<hr/> <hr/> <code>\char_value_uccode:n</code> ★	<code>\char_value_uccode:n {⟨integer expression⟩}</code>
	Expands to the current upper case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <hr/> <code>\char_show_value_uccode:n</code>	<code>\char_show_value_uccode:n {⟨integer expression⟩}</code>
	Displays the current upper case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <hr/> <code>\char_set_mathcode:nn</code>	<code>\char_set_mathcode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
Updated: 2015-08-06	This function sets up the math code of <i>⟨character⟩</i> . The <i>⟨character⟩</i> is specified as an <i>⟨integer expression⟩</i> which will be used as the character code of the relevant character. The setting applies within the current T _E X group.
<hr/> <hr/> <code>\char_value_mathcode:n</code> ★	<code>\char_value_mathcode:n {⟨integer expression⟩}</code>
	Expands to the current math code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <hr/> <code>\char_show_value_mathcode:n</code>	<code>\char_show_value_mathcode:n {⟨integer expression⟩}</code>
	Displays the current math code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <hr/> <code>\char_set_sfcode:nn</code>	<code>\char_set_sfcode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
Updated: 2015-08-06	This function sets up the space factor for the <i>⟨character⟩</i> . The <i>⟨character⟩</i> is specified as an <i>⟨integer expression⟩</i> which will be used as the character code of the relevant character. The setting applies within the current T _E X group.
<hr/> <hr/> <code>\char_value_sfcode:n</code> ★	<code>\char_value_sfcode:n {⟨integer expression⟩}</code>
	Expands to the current space factor for the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <hr/> <code>\char_show_value_sfcode:n</code>	<code>\char_show_value_sfcode:n {⟨integer expression⟩}</code>
	Displays the current space factor for the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <hr/> <code>\l_char_active_seq</code>	Used to track which tokens may require special handling at the document level as they are (or have been at some point) of category <i>⟨active⟩</i> (catcode 13). Each entry in the sequence consists of a single escaped token, for example <code>\~</code> . Active tokens should be added to the sequence when they are defined for general document use.
New: 2012-01-23 Updated: 2015-11-11	
<hr/> <hr/> <code>\l_char_special_seq</code>	Used to track which tokens will require special handling when working with verbatim-like material at the document level as they are not of categories <i>⟨letter⟩</i> (catcode 11) or <i>⟨other⟩</i> (catcode 12). Each entry in the sequence consists of a single escaped token, for example <code>\</code> for the backslash or <code>\{</code> for an opening brace. Escaped tokens should be added to the sequence when they are defined for general document use.
New: 2012-01-23 Updated: 2015-11-11	

3 Generic tokens

```
\c_group_begin_token
\c_group_end_token
\c_math_toggle_token
\c_alignment_token
\c_parameter_token
\c_math_superscript_token
\c_math_subscript_token
\c_space_token
```

These are implicit tokens which have the category code described by their name. They are used internally for test purposes but are also available to the programmer for other uses.

```
\c_catcode_letter_token
\c_catcode_other_token
```

These are implicit tokens which have the category code described by their name. They are used internally for test purposes and should not be used other than for category code tests.

```
\c_catcode_active_tl
```

A token list containing an active token. This is used internally for test purposes and should not be used other than in appropriately-constructed category code tests.

4 Converting tokens

```
\token_to_meaning:N ★
\token_to_meaning:c ★
```

`\token_to_meaning:N` $\langle token \rangle$

Inserts the current meaning of the $\langle token \rangle$ into the input stream as a series of characters of category code 12 (other). This is the primitive \TeX description of the $\langle token \rangle$, thus for example both functions defined by `\cs_set_nopar:Npn` and token list variables defined using `\tl_new:N` are described as macros.

\TeX hackers note: This is the \TeX primitive `\meaning`. The $\langle token \rangle$ can thus be an explicit space tokens or an explicit begin-group or end-group character token (`{` or `}` when normal \TeX category codes apply) even though these are not valid N-type arguments.

```
\token_to_str:N ★
\token_to_str:c ★
```

`\token_to_str:N` $\langle token \rangle$

Converts the given $\langle token \rangle$ into a series of characters with category code 12 (other). If the $\langle token \rangle$ is a control sequence, this will start with the current escape character with category code 12 (the escape character is part of the $\langle token \rangle$). This function requires only a single expansion.

\TeX hackers note: `\token_to_str:N` is the \TeX primitive `\string` renamed. The $\langle token \rangle$ can thus be an explicit space tokens or an explicit begin-group or end-group character token (`{` or `}` when normal \TeX category codes apply) even though these are not valid N-type arguments.

5 Token conditionals

<code>\token_if_group_begin_p:N</code>	<code>*</code>	<code>\token_if_group_begin_p:N</code>	<code><token></code>
<code>\token_if_group_begin:NTF</code>	<code>*</code>	<code>\token_if_group_begin:NTF</code>	<code><token> {\true code} {\false code}</code>

Tests if `<token>` has the category code of a begin group token (`{` when normal `TEX` category codes are in force). Note that an explicit begin group token cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_group_end_p:N</code>	<code>*</code>	<code>\token_if_group_end_p:N</code>	<code><token></code>
<code>\token_if_group_end:NTF</code>	<code>*</code>	<code>\token_if_group_end:NTF</code>	<code><token> {\true code} {\false code}</code>

Tests if `<token>` has the category code of an end group token (`}` when normal `TEX` category codes are in force). Note that an explicit end group token cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_math_toggle_p:N</code>	<code>*</code>	<code>\token_if_math_toggle_p:N</code>	<code><token></code>
<code>\token_if_math_toggle:NTF</code>	<code>*</code>	<code>\token_if_math_toggle:NTF</code>	<code><token> {\true code} {\false code}</code>

Tests if `<token>` has the category code of a math shift token (`$` when normal `TEX` category codes are in force).

<code>\token_if_alignment_p:N</code>	<code>*</code>	<code>\token_if_alignment_p:N</code>	<code><token></code>
<code>\token_if_alignment:NTF</code>	<code>*</code>	<code>\token_if_alignment:NTF</code>	<code><token> {\true code} {\false code}</code>

Tests if `<token>` has the category code of an alignment token (`&` when normal `TEX` category codes are in force).

<code>\token_if_parameter_p:N</code>	<code>*</code>	<code>\token_if_parameter_p:N</code>	<code><token></code>
<code>\token_if_parameter:NTF</code>	<code>*</code>	<code>\token_if_parameter:NTF</code>	<code><token> {\true code} {\false code}</code>

Tests if `<token>` has the category code of a macro parameter token (`#` when normal `TEX` category codes are in force).

<code>\token_if_math_superscript_p:N</code>	<code>*</code>	<code>\token_if_math_superscript_p:N</code>	<code><token></code>
<code>\token_if_math_superscript:NTF</code>	<code>*</code>	<code>\token_if_math_superscript:NTF</code>	<code><token> {\true code} {\false code}</code>

Tests if `<token>` has the category code of a superscript token (`^` when normal `TEX` category codes are in force).

<code>\token_if_math_subscript_p:N</code>	<code>*</code>	<code>\token_if_math_subscript_p:N</code>	<code><token></code>
<code>\token_if_math_subscript:NTF</code>	<code>*</code>	<code>\token_if_math_subscript:NTF</code>	<code><token> {\true code} {\false code}</code>

Tests if `<token>` has the category code of a subscript token (`_` when normal `TEX` category codes are in force).

<code>\token_if_space_p:N</code>	<code>*</code>	<code>\token_if_space_p:N</code>	<code><token></code>
<code>\token_if_space:NTF</code>	<code>*</code>	<code>\token_if_space:NTF</code>	<code><token> {\true code} {\false code}</code>

Tests if `<token>` has the category code of a space token. Note that an explicit space token with character code 32 cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_letter_p:N</code>	<code>\token_if_letter_p:N</code>	<code>\token</code>
<code>\token_if_letter:NTF</code>	<code>\token_if_letter:NTF</code>	<code>\token</code> <code>{\true code}</code> <code>{\false code}</code>

Tests if `\token` has the category code of a letter token.

<code>\token_if_other_p:N</code>	<code>\token_if_other_p:N</code>	<code>\token</code>
<code>\token_if_other:NTF</code>	<code>\token_if_other:NTF</code>	<code>\token</code> <code>{\true code}</code> <code>{\false code}</code>

Tests if `\token` has the category code of an “other” token.

<code>\token_if_active_p:N</code>	<code>\token_if_active_p:N</code>	<code>\token</code>
<code>\token_if_active:NTF</code>	<code>\token_if_active:NTF</code>	<code>\token</code> <code>{\true code}</code> <code>{\false code}</code>

Tests if `\token` has the category code of an active character.

<code>\token_if_eq_catcode_p:NN</code>	<code>\token_if_eq_catcode_p:NN</code>	<code>\token₁</code>	<code>\token₂</code>
<code>\token_if_eq_catcode:NNTF</code>	<code>\token_if_eq_catcode:NNTF</code>	<code>\token₁</code>	<code>\token₂</code> <code>{\true code}</code> <code>{\false code}</code>

Tests if the two `\tokens` have the same category code.

<code>\token_if_eq_charcode_p:NN</code>	<code>\token_if_eq_charcode_p:NN</code>	<code>\token₁</code>	<code>\token₂</code>
<code>\token_if_eq_charcode:NNTF</code>	<code>\token_if_eq_charcode:NNTF</code>	<code>\token₁</code>	<code>\token₂</code> <code>{\true code}</code> <code>{\false code}</code>

Tests if the two `\tokens` have the same character code.

<code>\token_if_eq_meaning_p:NN</code>	<code>\token_if_eq_meaning_p:NN</code>	<code>\token₁</code>	<code>\token₂</code>
<code>\token_if_eq_meaning:NNTF</code>	<code>\token_if_eq_meaning:NNTF</code>	<code>\token₁</code>	<code>\token₂</code> <code>{\true code}</code> <code>{\false code}</code>

Tests if the two `\tokens` have the same meaning when expanded.

<code>\token_if_macro_p:N</code>	<code>\token_if_macro_p:N</code>	<code>\token</code>
<code>\token_if_macro:NTF</code>	<code>\token_if_macro:NTF</code>	<code>\token</code> <code>{\true code}</code> <code>{\false code}</code>

Updated: 2011-05-23 Tests if the `\token` is a T_EX macro.

<code>\token_if_cs_p:N</code>	<code>\token_if_cs_p:N</code>	<code>\token</code>
<code>\token_if_cs:NTF</code>	<code>\token_if_cs:NTF</code>	<code>\token</code> <code>{\true code}</code> <code>{\false code}</code>

Tests if the `\token` is a control sequence.

<code>\token_if_expandable_p:N</code>	<code>\token_if_expandable_p:N</code>	<code>\token</code>
<code>\token_if_expandable:NTF</code>	<code>\token_if_expandable:NTF</code>	<code>\token</code> <code>{\true code}</code> <code>{\false code}</code>

Tests if the `\token` is expandable. This test returns `\false` for an undefined token.

<code>\token_if_long_macro_p:N</code>	<code>\token_if_long_macro_p:N</code>	<code>\token</code>
<code>\token_if_long_macro:NTF</code>	<code>\token_if_long_macro:NTF</code>	<code>\token</code> <code>{\true code}</code> <code>{\false code}</code>

Updated: 2012-01-20 Tests if the `\token` is a long macro.

<code>\token_if_protected_macro_p:N</code>	<code>\token_if_protected_macro_p:N</code>	<code>\token</code>
<code>\token_if_protected_macro:NTF</code>	<code>\token_if_protected_macro:NTF</code>	<code>\token</code> <code>{\true code}</code> <code>{\false code}</code>

Updated: 2012-01-20

Tests if the `\token` is a protected macro: for a macro which is both protected and long this returns `false`.

<code>\token_if_protected_long_macro_p:N</code>	<code>*</code>	<code>\token_if_protected_long_macro_p:N</code>	<code><token></code>
<code>\token_if_protected_long_macro:N</code>	<code>\token_if_protected_long_macro:N</code>	<code>NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is a protected long macro.

<code>\token_if_chardef_p:N</code>	<code>*</code>	<code>\token_if_chardef_p:N</code>	<code><token></code>
<code>\token_if_chardef:N</code>	<code>\token_if_chardef:N</code>	<code>NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a chardef.

TeXhackers note: Booleans, boxes and small integer constants are implemented as `\chardefs`.

<code>\token_if_mathchardef_p:N</code>	<code>*</code>	<code>\token_if_mathchardef_p:N</code>	<code><token></code>
<code>\token_if_mathchardef:N</code>	<code>\token_if_mathchardef:N</code>	<code>NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a mathchardef.

<code>\token_if_dim_register_p:N</code>	<code>*</code>	<code>\token_if_dim_register_p:N</code>	<code><token></code>
<code>\token_if_dim_register:N</code>	<code>\token_if_dim_register:N</code>	<code>NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a dimension register.

<code>\token_if_int_register_p:N</code>	<code>*</code>	<code>\token_if_int_register_p:N</code>	<code><token></code>
<code>\token_if_int_register:N</code>	<code>\token_if_int_register:N</code>	<code>NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a integer register.

TeXhackers note: Constant integers may be implemented as integer registers, `\chardefs`, or `\mathchardefs` depending on their value.

<code>\token_if_muskip_register_p:N</code>	<code>*</code>	<code>\token_if_muskip_register_p:N</code>	<code><token></code>
<code>\token_if_muskip_register:N</code>	<code>\token_if_muskip_register:N</code>	<code>NTF</code>	<code><token> {\true code} {\false code}</code>

New: 2012-02-15

Tests if the $\langle token \rangle$ is defined to be a muskip register.

<code>\token_if_skip_register_p:N</code>	<code>*</code>	<code>\token_if_skip_register_p:N</code>	<code><token></code>
<code>\token_if_skip_register:N</code>	<code>\token_if_skip_register:N</code>	<code>NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a skip register.

<code>\token_if_toks_register_p:N</code>	<code>*</code>	<code>\token_if_toks_register_p:N</code>	$\langle token \rangle$
<code>\token_if_toks_register:NTF</code>	<code>*</code>	<code>\token_if_toks_register:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a toks register (not used by L^AT_EX3).

<code>\token_if_primitive_p:N</code>	<code>*</code>	<code>\token_if_primitive_p:N</code>	$\langle token \rangle$
<code>\token_if_primitive:NTF</code>	<code>*</code>	<code>\token_if_primitive:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2011-05-23

Tests if the $\langle token \rangle$ is an engine primitive.

6 Peeking ahead at the next token

There is often a need to look ahead at the next token in the input stream while leaving it in place. This is handled using the “peek” functions. The generic `\peek_after:Nw` is provided along with a family of predefined tests for common cases. As peeking ahead does *not* skip spaces the predefined tests include both a space-respecting and space-skipping version.

<code>\peek_after:Nw</code>	<code>\peek_after:Nw</code>	$\langle function \rangle$	$\langle token \rangle$
-----------------------------	-----------------------------	----------------------------	-------------------------

Locally sets the test variable `\l_peek_token` equal to $\langle token \rangle$ (as an implicit token, *not* as a token list), and then expands the $\langle function \rangle$. The $\langle token \rangle$ remains in the input stream as the next item after the $\langle function \rangle$. The $\langle token \rangle$ here may be \sqcup , $\{$ or $\}$ (assuming normal T_EX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

<code>\peek_gafter:Nw</code>	<code>\peek_gafter:Nw</code>	$\langle function \rangle$	$\langle token \rangle$
------------------------------	------------------------------	----------------------------	-------------------------

Globally sets the test variable `\g_peek_token` equal to $\langle token \rangle$ (as an implicit token, *not* as a token list), and then expands the $\langle function \rangle$. The $\langle token \rangle$ remains in the input stream as the next item after the $\langle function \rangle$. The $\langle token \rangle$ here may be \sqcup , $\{$ or $\}$ (assuming normal T_EX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

<code>\l_peek_token</code>	Token set by <code>\peek_after:Nw</code> and available for testing as described above.
----------------------------	--

<code>\g_peek_token</code>	Token set by <code>\peek_gafter:Nw</code> and available for testing as described above.
----------------------------	---

<code>\peek_catcode:NTF</code>	<code>\peek_catcode:NTF</code>	$\langle test\ token \rangle$	$\{\langle true\ code \rangle\}$	$\{\langle false\ code \rangle\}$
--------------------------------	--------------------------------	-------------------------------	----------------------------------	-----------------------------------

Updated: 2012-12-20

Tests if the next $\langle token \rangle$ in the input stream has the same category code as the $\langle test\ token \rangle$ (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the $\langle token \rangle$ is left in the input stream after the $\langle true\ code \rangle$ or $\langle false\ code \rangle$ (as appropriate to the result of the test).

<code>\peek_catcode_ignore_spaces:NTF</code>	<code>\peek_catcode_ignore_spaces:NTF <test token> {(true code)} {(false code)}</code>
--	--

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same category code as the *<test token>* (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_catcode_remove:NTF</code>	<code>\peek_catcode_remove:NTF <test token> {(true code)} {(false code)}</code>
---------------------------------------	---

Updated: 2012-12-20

Tests if the next *<token>* in the input stream has the same category code as the *<test token>* (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_catcode_remove_ignore_spaces:NTF</code>	<code>\peek_catcode_remove_ignore_spaces:NTF <test token> {(true code)} {(false code)}</code>
---	---

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same category code as the *<test token>* (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_charcode:NTF</code>	<code>\peek_charcode:NTF <test token> {(true code)} {(false code)}</code>
---------------------------------	---

Updated: 2012-12-20

Tests if the next *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_charcode_ignore_spaces:NTF</code>	<code>\peek_charcode_ignore_spaces:NTF <test token> {(true code)} {(false code)}</code>
---	---

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_charcode_remove:NTF</code>	<code>\peek_charcode_remove:NTF <test token> {(true code)} {(false code)}</code>
--	--

Updated: 2012-12-20

Tests if the next *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_charcode_remove_ignore_spaces:NTF</code>	<code>\peek_charcode_remove_ignore_spaces:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2012-12-20	

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_meaning:NTF</code>	<code>\peek_meaning:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2011-07-02	

Tests if the next *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_meaning_ignore_spaces:NTF</code>	<code>\peek_meaning_ignore_spaces:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2012-12-05	

Tests if the next non-space *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_meaning_remove:NTF</code>	<code>\peek_meaning_remove:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2011-07-02	

Tests if the next *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_meaning_remove_ignore_spaces:NTF</code>	<code>\peek_meaning_remove_ignore_spaces:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2012-12-05	

Tests if the next non-space *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

`\peek_N_type:TF`

Updated: 2012-12-20

`\peek_N_type:TF` $\{\langle true\ code\rangle\}$ $\{\langle false\ code\rangle\}$

Tests if the next $\langle token\rangle$ in the input stream can be safely grabbed as an N-type argument. The test is $\langle false\rangle$ if the next $\langle token\rangle$ is either an explicit or implicit begin-group or end-group token (with any character code), or an explicit or implicit space character (with character code 32 and category code 10), or an outer token (never used in L^AT_EX3) and $\langle true\rangle$ in all other cases. Note that a $\langle true\rangle$ result ensures that the next $\langle token\rangle$ is a valid N-type argument. However, if the next $\langle token\rangle$ is for instance `\c_space_token`, the test takes the $\langle false\rangle$ branch, even though the next $\langle token\rangle$ is in fact a valid N-type argument. The $\langle token\rangle$ is left in the input stream after the $\langle true\ code\rangle$ or $\langle false\ code\rangle$ (as appropriate to the result of the test).

7 Description of all possible tokens

Let us end by reviewing every case that a given token can fall into. This section is quite technical and some details are only meant for completeness. We distinguish the meaning of the token, which controls the expansion of the token and its effect on T_EX's state, and its shape, which is used when comparing token lists such as for delimited arguments. Two tokens of the same shape must have the same meaning, but the converse does not hold.

A token has one of the following shapes.

- A control sequence, characterized by the sequence of characters that constitute its name: for instance, `\use:n` is a five-letter control sequence.
- An active character token, characterized by its character code (between 0 and 1114111 for LuaT_EX and X_ƎT_EX and less for other engines) and category code 13.
- A character token, characterized by its character code and category code (one of 1, 2, 3, 4, 6, 7, 8, 10, 11 or 12 whose meaning is described below).⁶

There are also a few internal tokens. The following list may be incomplete in some engines.

- Expanding `\the\font` results in a token that looks identical to the command that was used to select the current font (such as `\tenrm`) but it differs from it in shape.
- A “frozen” `\relax`, which differs from the primitive in shape (but has the same meaning), is inserted when the closing `\fi` of a conditional is encountered before the conditional is evaluated.
- Expanding `\noexpand` $\langle token\rangle$ (when the $\langle token\rangle$ is expandable) results in an internal token, displayed (temporarily) as `\notexpanded: $\langle token\rangle$` , whose shape coincides with the $\langle token\rangle$ and whose meaning differs from `\relax`.
- An `\outer endtemplate:` can be encountered when peeking ahead at the next token; this expands to another internal token, `end of alignment template`.
- Tricky programming might access a frozen `\endwrite`.

⁶In LuaT_EX, there is also the case of “bytes”, which behave as character tokens of category code 12 (other) and character code between 1114112 and 1114366. They are used to output individual bytes to files, rather than UTF-8.

- Some frozen tokens can only be accessed in interactive sessions: `\cr`, `\right`, `\endgroup`, `\fi`, `\inaccessible`.

The meaning of a (non-active) character token is fixed by its category code (and character code) and cannot be changed. We call these tokens *explicit* character tokens. Category codes that a character token can have are listed below by giving a sample output of the \TeX primitive `\meaning`, together with their \LaTeX 3 names and most common example:

- 1 begin-group character (`group_begin`, often `{`),
- 2 end-group character (`group_end`, often `}`),
- 3 math shift character (`math_toggle`, often `$`),
- 4 alignment tab character (`alignment`, often `&`),
- 6 macro parameter character (`parameter`, often `#`),
- 7 superscript character (`math_superscript`, often `^`),
- 8 subscript character (`math_subscript`, often `_`),
- 10 blank space (`space`, often character code 32),
- 11 the letter (`letter`, such as `A`),
- 12 the character (`other`, such as `0`).

Category code 13 (`active`) is discussed below. Input characters can also have several other category codes which do not lead to character tokens for later processing: 0 (`escape`), 5 (`end_line`), 9 (`ignore`), 14 (`comment`), and 15 (`invalid`).

The meaning of a control sequence or active character can be identical to that of any character token listed above (with any character code), and we call such tokens *implicit* character tokens. The meaning is otherwise in the following list:

- a macro, used in \LaTeX 3 for most functions and some variables (`tl`, `fp`, `seq`, ...),
- a primitive such as `\def` or `\topmark`, used in \LaTeX 3 for some functions,
- a register such as `\count123`, used in \LaTeX 3 for the implementation of some variables (`int`, `dim`, ...),
- a constant integer such as `\char"56` or `\mathchar"121`,
- a font selection command,
- undefined.

Macros be `\protected` or not, `\long` or not (the opposite of what \LaTeX 3 calls `nopar`), and `\outer` or not (unused in \LaTeX 3). Their `\meaning` takes the form

$\langle properties \rangle$ **macro:** $\langle parameters \rangle \rightarrow \langle replacement \rangle$

where *properties* is among `\protected\long\outer`, *parameters* describes parameters that the macro expects, such as `#1#2#3`, and *replacement* describes how the parameters are manipulated, such as `#2/#1/#3`.

Now is perhaps a good time to mention some subtleties relating to tokens with category code 10 (space). Any input character with this category code (normally, space and tab characters) becomes a normal space, with character code 32 and category code 10.

When a macro takes an undelimited argument, explicit space characters (with character code 32 and category code 10) are ignored. If the following token is an explicit character token with category code 1 (begin-group) and an arbitrary character code, then `TEX` scans ahead to obtain an equal number of explicit character tokens with category code 1 (begin-group) and 2 (end-group), and the resulting list of tokens (with outer braces removed) becomes the argument. Otherwise, a single token is taken as the argument for the macro: we call such single tokens “N-type”, as they are suitable to be used as an argument for a function with the signature `:N`.

Part XVII

The l3prop package

Property lists

L^AT_EX3 implements a “property list” data type, which contain an unordered list of entries each of which consists of a $\langle key \rangle$ and an associated $\langle value \rangle$. The $\langle key \rangle$ and $\langle value \rangle$ may both be any $\langle balanced\ text \rangle$. It is possible to map functions to property lists such that the function is applied to every key–value pair within the list.

Each entry in a property list must have a unique $\langle key \rangle$: if an entry is added to a property list which already contains the $\langle key \rangle$ then the new entry overwrites the existing one. The $\langle keys \rangle$ are compared on a string basis, using the same method as `\str_if_eq:nn`.

Property lists are intended for storing key-based information for use within code. This is in contrast to key–value lists, which are a form of *input* parsed by the `keys` module.

1 Creating and initialising property lists

```
\prop_new:N
\prop_new:c
```

```
\prop_new:N <property list>
```

Creates a new $\langle property\ list \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle property\ list \rangle$ initially contains no entries.

```
\prop_clear:N
\prop_clear:c
\prop_gclear:N
\prop_gclear:c
```

```
\prop_clear:N <property list>
```

Clears all entries from the $\langle property\ list \rangle$.

```
\prop_clear_new:N
\prop_clear_new:c
\prop_gclear_new:N
\prop_gclear_new:c
```

```
\prop_clear_new:N <property list>
```

Ensures that the $\langle property\ list \rangle$ exists globally by applying `\prop_new:N` if necessary, then applies `\prop_(g)clear:N` to leave the list empty.

```
\prop_set_eq:NN
\prop_set_eq:(cN|Nc|cc)
\prop_gset_eq:NN
\prop_gset_eq:(cN|Nc|cc)
```

```
\prop_set_eq:NN <property list1> <property list2>
```

Sets the content of $\langle property\ list_1 \rangle$ equal to that of $\langle property\ list_2 \rangle$.

```
\prop_set_from_keyval:Nn
\prop_set_from_keyval:cn
\prop_gset_from_keyval:Nn
\prop_gset_from_keyval:cn
```

```
\prop_set_from_keyval:Nn <prop var>
```

```
{
  <key1> = <value1> ,
  <key2> = <value2> , ...
}
```

Sets $\langle prop\ var \rangle$ to contain key–value pairs given in the second argument. If duplicate keys appear only one of the values is kept.

New: 2017-11-28
Updated: 2019-08-25

```
\prop_const_from_keyval:Nn
\prop_const_from_keyval:cn
```

New: 2017-11-28
Updated: 2019-08-25

```
\prop_const_from_keyval:Nn <prop var>
{
  <key1> = <value1> ,
  <key2> = <value2> , ...
}
```

Creates a new constant *<prop var>* or raises an error if the name is already taken. The *<prop var>* is set globally to contain key–value pairs given in the second argument. If duplicate keys appear only one of the values is kept.

2 Adding entries to property lists

```
\prop_put:Nnn
\prop_put:(NnV|Nno|Nnx|NVn|NVV|Non|Noo|cnn|cnV|cno|cnx|cVn|cVV|con|coo)
\prop_gput:Nnn
\prop_gput:(NnV|Nno|Nnx|NVn|NVV|Non|Noo|cnn|cnV|cno|cnx|cVn|cVV|con|coo)
```

Updated: 2012-07-09

```
\prop_put:Nnn <property list>
{<key>} {<value>}
```

Adds an entry to the *<property list>* which may be accessed using the *<key>* and which has *<value>*. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored. If the *<key>* is already present in the *<property list>*, the existing entry is overwritten by the new *<value>*.

```
\prop_put_if_new:Nnn
\prop_put_if_new:cnn
\prop_gput_if_new:Nnn
\prop_gput_if_new:cnn
```

```
\prop_put_if_new:Nnn <property list> {<key>} {<value>}
```

If the *<key>* is present in the *<property list>* then no action is taken. If the *<key>* is not present in the *<property list>* then a new entry is added. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored.

3 Recovering values from property lists

```
\prop_get:NnN
\prop_get:(NVN|NoN|cnN|cVN|coN)
```

Updated: 2011-08-28

```
\prop_get:NnN <property list> {<key>} <tl var>
```

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<token list variable>* is set within the current T_EX group. See also `\prop_get:NnNTF`.

```
\prop_pop:NnN
\prop_pop:(NoN|cnN|coN)
```

Updated: 2011-08-18

```
\prop_pop:NnN <property list> {<key>} <tl var>
```

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. Both assignments are local. See also `\prop_pop:NnNTF`.

<code>\prop_gpop:NnN</code>
<code>\prop_gpop:(NoN cnN coN)</code> ★
Updated: 2011-08-18

`\prop_gpop:NnN` $\langle property list \rangle$ $\{\langle key \rangle\}$ $\langle tl var \rangle$

Recovers the $\langle value \rangle$ stored with $\langle key \rangle$ from the $\langle property list \rangle$, and places this in the $\langle token list variable \rangle$. If the $\langle key \rangle$ is not found in the $\langle property list \rangle$ then the $\langle token list variable \rangle$ is set to the special marker `\q_no_value`. The $\langle key \rangle$ and $\langle value \rangle$ are then deleted from the property list. The $\langle property list \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. See also `\prop_gpop:NnNTF`.

<code>\prop_item:Nn</code> ★
<code>\prop_item:cn</code> ★
New: 2014-07-17

`\prop_item:Nn` $\langle property list \rangle$ $\{\langle key \rangle\}$

Expands to the $\langle value \rangle$ corresponding to the $\langle key \rangle$ in the $\langle property list \rangle$. If the $\langle key \rangle$ is missing, this has an empty expansion.

TeXhackers note: This function is slower than the non-expandable analogue `\prop_get:NnN`. The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle value \rangle$ does not expand further when appearing in an **x**-type argument expansion.

<code>\prop_count:N</code> ★
<code>\prop_count:c</code> ★

`\prop_count:N` $\langle property list \rangle$

Leaves the number of key–value pairs in the $\langle property list \rangle$ in the input stream as an $\langle integer denotation \rangle$.

4 Modifying property lists

<code>\prop_remove:Nn</code>
<code>\prop_remove:(NV cn cV)</code>
<code>\prop_gremove:Nn</code>
<code>\prop_gremove:(NV cn cV)</code>
New: 2012-05-12

`\prop_remove:Nn` $\langle property list \rangle$ $\{\langle key \rangle\}$

Removes the entry listed under $\langle key \rangle$ from the $\langle property list \rangle$. If the $\langle key \rangle$ is not found in the $\langle property list \rangle$ no change occurs, *i.e.* there is no need to test for the existence of a key before deleting it.

5 Property list conditionals

<code>\prop_if_exist_p:N</code> ★
<code>\prop_if_exist_p:c</code> ★
<code>\prop_if_exist:NTF</code> ★
<code>\prop_if_exist:cTF</code> ★
New: 2012-03-03

`\prop_if_exist_p:N` $\langle property list \rangle$

`\prop_if_exist:NTF` $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests whether the $\langle property list \rangle$ is currently defined. This does not check that the $\langle property list \rangle$ really is a property list variable.

<code>\prop_if_empty_p:N</code> ★
<code>\prop_if_empty_p:c</code> ★
<code>\prop_if_empty:NTF</code> ★
<code>\prop_if_empty:cTF</code> ★

`\prop_if_empty_p:N` $\langle property list \rangle$

`\prop_if_empty:NTF` $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if the $\langle property list \rangle$ is empty (containing no entries).

<code>\prop_if_in_p:Nn</code>	<code>*</code>	<code>\prop_if_in:NnTF</code>	<code><property list> {<key>} {<true code>} {<false code>}</code>
<code>\prop_if_in_p:(NV No cn cV co)</code>	<code>*</code>		
<code>\prop_if_in:NnTF</code>	<code>*</code>		
<code>\prop_if_in:(NV No cn cV co)TF</code>	<code>*</code>		

Updated: 2011-09-15

Tests if the $\langle key \rangle$ is present in the $\langle property list \rangle$, making the comparison using the method described by `\str_if_eq:nNTF`.

TeXhackers note: This function iterates through every key-value pair in the $\langle property list \rangle$ and is therefore slower than using the non-expandable `\prop_get:NnNTF`.

6 Recovering values from property lists with branching

The functions in this section combine tests for the presence of a key in a property list with recovery of the associated valued. This makes them useful for cases where different cases follow dependent on the presence or absence of a key in a property list. They offer increased readability and performance over separate testing and recovery phases.

<code>\prop_get:NnNTF</code>	<code>\prop_get:NnNTF</code>	<code><property list> {<key>} <token list variable></code>
<code>\prop_get:(NVN NoN cnN cVN coN)TF</code>		<code>{<true code>} {<false code>}</code>

Updated: 2012-05-19

If the $\langle key \rangle$ is not present in the $\langle property list \rangle$, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle key \rangle$ is present in the $\langle property list \rangle$, stores the corresponding $\langle value \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle property list \rangle$, then leaves the $\langle true code \rangle$ in the input stream. The $\langle token list variable \rangle$ is assigned locally.

<code>\prop_pop:NnNTF</code>	<code>\prop_pop:NnNTF</code>	<code><property list> {<key>} <token list variable> {<true code>}</code>
<code>\prop_pop:cnNTF</code>		<code>{<false code>}</code>

New: 2011-08-18
Updated: 2012-05-19

If the $\langle key \rangle$ is not present in the $\langle property list \rangle$, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle key \rangle$ is present in the $\langle property list \rangle$, pops the corresponding $\langle value \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from the $\langle property list \rangle$. Both the $\langle property list \rangle$ and the $\langle token list variable \rangle$ are assigned locally.

<code>\prop_gpop:NnNTF</code>	<code>\prop_gpop:NnNTF</code>	<code><property list> {<key>} <token list variable> {<true code>}</code>
<code>\prop_gpop:cnNTF</code>		<code>{<false code>}</code>

New: 2011-08-18
Updated: 2012-05-19

If the $\langle key \rangle$ is not present in the $\langle property list \rangle$, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle key \rangle$ is present in the $\langle property list \rangle$, pops the corresponding $\langle value \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from the $\langle property list \rangle$. The $\langle property list \rangle$ is modified globally, while the $\langle token list variable \rangle$ is assigned locally.

7 Mapping to property lists

All mappings are done at the current group level, *i.e.* any local assignments made by the $\langle function \rangle$ or $\langle code \rangle$ discussed below remain in effect after the loop.

$\backslash prop_map_function:Nn$	☆
$\backslash prop_map_function:cN$	☆
Updated: 2013-01-08	

$\backslash prop_map_function:Nn$ $\langle property\ list \rangle$ $\langle function \rangle$

Applies $\langle function \rangle$ to every $\langle entry \rangle$ stored in the $\langle property\ list \rangle$. The $\langle function \rangle$ receives two arguments for each iteration: the $\langle key \rangle$ and associated $\langle value \rangle$. The order in which $\langle entries \rangle$ are returned is not defined and should not be relied upon. To pass further arguments to the $\langle function \rangle$, see $\backslash prop_map_tokens:Nn$.

$\backslash prop_map_inline:Nn$	
$\backslash prop_map_inline:cN$	
Updated: 2013-01-08	

$\backslash prop_map_inline:Nn$ $\langle property\ list \rangle$ $\{ \langle inline\ function \rangle \}$

Applies $\langle inline\ function \rangle$ to every $\langle entry \rangle$ stored within the $\langle property\ list \rangle$. The $\langle inline\ function \rangle$ should consist of code which receives the $\langle key \rangle$ as #1 and the $\langle value \rangle$ as #2. The order in which $\langle entries \rangle$ are returned is not defined and should not be relied upon.

$\backslash prop_map_tokens:Nn$	☆
$\backslash prop_map_tokens:cN$	☆

$\backslash prop_map_tokens:Nn$ $\langle property\ list \rangle$ $\{ \langle code \rangle \}$

Analogue of $\backslash prop_map_function:Nn$ which maps several tokens instead of a single function. The $\langle code \rangle$ receives each key–value pair in the $\langle property\ list \rangle$ as two trailing brace groups. For instance,

```
 $\backslash prop\_map\_tokens:Nn \backslash l\_my\_prop \{ \backslash str\_if\_eq:nnT \{ mykey \} \}$ 
```

expands to the value corresponding to `mykey`: for each pair in $\backslash l_my_prop$ the function $\backslash str_if_eq:nnT$ receives `mykey`, the $\langle key \rangle$ and the $\langle value \rangle$ as its three arguments. For that specific task, $\backslash prop_item:Nn$ is faster.

$\backslash prop_map_break:$	☆
Updated: 2012-06-29	

$\backslash prop_map_break:$

Used to terminate a $\backslash prop_map_...$ function before all entries in the $\langle property\ list \rangle$ have been processed. This normally takes place within a conditional statement, for example

```
 $\backslash prop\_map\_inline:Nn \backslash l\_my\_prop$ 
{
   $\backslash str\_if\_eq:nnTF \{ \#1 \} \{ bingo \}$ 
  {  $\backslash prop\_map\_break:$  }
  {
    % Do something useful
  }
}
```

Use outside of a $\backslash prop_map_...$ scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

<hr/> <code>\prop_map_break:n</code> ☆ <hr/>	<code>\prop_map_break:n {<code>}</code>
Updated: 2012-06-29 <hr/>	Used to terminate a <code>\prop_map_...</code> function before all entries in the <i><property list></i> have been processed, inserting the <i><code></i> after the mapping has ended. This normally takes place within a conditional statement, for example

```

\prop_map_inline:Nn \l_my_prop
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \prop_map_break:n { <code> } }
  {
    % Do something useful
  }
}

```

Use outside of a `\prop_map_...` scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before the *<code>* is inserted into the input stream. This depends on the design of the mapping function.

8 Viewing property lists

<hr/> <code>\prop_show:N</code> <code>\prop_show:c</code> <hr/>	<code>\prop_show:N <property list></code>
Updated: 2015-08-01 <hr/>	Displays the entries in the <i><property list></i> in the terminal.

<hr/> <code>\prop_log:N</code> <code>\prop_log:c</code> <hr/>	<code>\prop_log:N <property list></code>
New: 2014-08-12 Updated: 2015-08-01 <hr/>	Writes the entries in the <i><property list></i> in the log file.

9 Scratch property lists

<hr/> <code>\l_tmpa_prop</code> <code>\l_tmpb_prop</code> <hr/>	Scratch property lists for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
New: 2012-06-23 <hr/>	

<hr/> <code>\g_tmpa_prop</code> <code>\g_tmpb_prop</code> <hr/>	Scratch property lists for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
New: 2012-06-23 <hr/>	

10 Constants

<u><u>\c_empty_prop</u></u>	A permanently-empty property list used for internal comparisons.
-----------------------------	--

Part XVIII

The l3msg package

Messages

Messages need to be passed to the user by modules, either when errors occur or to indicate how the code is proceeding. The `l3msg` module provides a consistent method for doing this (as opposed to writing directly to the terminal or log).

The system used by `l3msg` to create messages divides the process into two distinct parts. Named messages are created in the first part of the process; at this stage, no decision is made about the type of output that the message will produce. The second part of the process is actually producing a message. At this stage a choice of message *class* has to be made, for example `error`, `warning` or `info`.

By separating out the creation and use of messages, several benefits are available. First, the messages can be altered later without needing details of where they are used in the code. This makes it possible to alter the language used, the detail level and so on. Secondly, the output which results from a given message can be altered. This can be done on a message class, module or message name basis. In this way, message behaviour can be altered and messages can be entirely suppressed.

1 Creating new messages

All messages have to be created before they can be used. The text of messages is automatically wrapped to the length available in the console. As a result, formatting is only needed where it helps to show meaning. In particular, `\` may be used to force a new line and `_` forces an explicit space. Additionally, `\{`, `\#`, `\}`, `\%` and `\~` can be used to produce the corresponding character.

Messages may be subdivided *by one level* using the `/` character. This is used within the message filtering system to allow for example the L^AT_EX kernel messages to belong to the module `LaTeX` while still being filterable at a more granular level. Thus for example

```
\msg_new:nnnn { mymodule } { submodule / message } ...
```

will allow to filter out specifically messages from the `submodule`.

```
\msg_new:nnnn
\msg_new:nnn
Updated: 2011-08-16
```

```
\msg_new:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Creates a *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied at the time the message is used. An error is raised if the *<message>* already exists.

```
\msg_set:nnnn
\msg_set:nnn
\msg_gset:nnnn
\msg_gset:nnn
```

```
\msg_set:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Sets up the text for a *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied at the time the message is used.

<hr/> <code>\msg_if_exist_p:nn</code> *	<code>\msg_if_exist_p:nn {<module>} {<message>}</code>
<code>\msg_if_exist:nnTF</code> *	<code>\msg_if_exist:nnTF {<module>} {<message>} {<true code>} {<false code>}</code>
<hr/> New: 2012-03-03	Tests whether the <i><message></i> for the <i><module></i> is currently defined.

2 Contextual information for messages

<hr/> <code>\msg_line_context:</code> ☆	<code>\msg_line_context:</code>
	Prints the current line number when a message is given, and thus suitable for giving context to messages. The number itself is proceeded by the text <code>on line</code> .

<hr/> <code>\msg_line_number:</code> *	<code>\msg_line_number:</code>
	Prints the current line number when a message is given.

<hr/> <code>\msg_fatal_text:n</code> *	<code>\msg_fatal_text:n {<module>}</code>
	Produces the standard text
	Fatal Package <i><module></i> Error
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

<hr/> <code>\msg_critical_text:n</code> *	<code>\msg_critical_text:n {<module>}</code>
	Produces the standard text
	Critical Package <i><module></i> Error
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

<hr/> <code>\msg_error_text:n</code> *	<code>\msg_error_text:n {<module>}</code>
	Produces the standard text
	Package <i><module></i> Error
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

<hr/> <code>\msg_warning_text:n</code> *	<code>\msg_warning_text:n {<module>}</code>
	Produces the standard text
	Package <i><module></i> Warning
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included. The <i><type></i> of <i><module></i> may be adjusted: Package is the standard outcome: see <code>\msg_module_type:n</code> .

<hr/> <code>\msg_info_text:n</code> ★ <hr/>	<code>\msg_info_text:n {⟨module⟩}</code> Produces the standard text: <div style="text-align: center;"><code>Package ⟨module⟩ Info</code></div> This function can be redefined to alter the language in which the message is given, using #1 as the name of the ⟨module⟩ to be included. The ⟨type⟩ of ⟨module⟩ may be adjusted: <code>Package</code> is the standard outcome: see <code>\msg_module_type:n</code> .
<hr/> <code>\msg_module_name:n</code> ★ <hr/> <div style="text-align: right;">New: 2018-10-10</div>	<code>\msg_module_name:n {⟨module⟩}</code> Expands to the public name of the ⟨module⟩ as defined by <code>\g_msg_module_name_prop</code> (or otherwise leaves the ⟨module⟩ unchanged).
<hr/> <code>\msg_module_type:n</code> ★ <hr/> <div style="text-align: right;">New: 2018-10-10</div>	<code>\msg_module_type:n {⟨module⟩}</code> Expands to the description which applies to the ⟨module⟩, for example a <code>Package</code> or <code>Class</code> . The information here is defined in <code>\g_msg_module_type_prop</code> , and will default to <code>Package</code> if an entry is not present.
<hr/> <code>\msg_see_documentation_text:n</code> ★ <hr/> <div style="text-align: right;">Updated: 2018-09-30</div>	<code>\msg_see_documentation_text:n {⟨module⟩}</code> Produces the standard text <div style="text-align: center;"><code>See the ⟨module⟩ documentation for further information.</code></div> This function can be redefined to alter the language in which the message is given, using #1 as the name of the ⟨module⟩ to be included. The name of the ⟨module⟩ may be altered by use of <code>\g_msg_module_documentation_prop</code>
<hr/> <code>\g_msg_module_name_prop</code> <hr/> <div style="text-align: right;">New: 2018-10-10</div>	Provides a mapping between the module name used for messages, and that for documentation. For example, <code>L^AT_EX3</code> core messages are stored in the reserved <code>L^AT_EX</code> tree, but are printed as <code>L^AT_EX3</code> .
<hr/> <code>\g_msg_module_type_prop</code> <hr/> <div style="text-align: right;">New: 2018-10-10</div>	Provides a mapping between the module name used for messages, and that type of module. For example, for <code>L^AT_EX3</code> core messages, an empty entry is set here meaning that they are not described using the standard <code>Package</code> text.

3 Issuing messages

Messages behave differently depending on the message class. In all cases, the message may be issued supplying 0 to 4 arguments. If the number of arguments supplied here does not match the number in the definition of the message, extra arguments are ignored, or empty arguments added (of course the sense of the message may be impaired). The four arguments are converted to strings before being added to the message text: the `x`-type variants should be used to expand material.

```

\msg_fatal:nnnnnn
\msg_fatal:nnxxxx
\msg_fatal:nnnnn
\msg_fatal:nnxxx
\msg_fatal:nnnn
\msg_fatal:nnxx
\msg_fatal:nnn
\msg_fatal:nnx
\msg_fatal:nn

```

Updated: 2012-08-11

```

\msg_fatal:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg three}
{\arg four}

```

Issues $\langle module \rangle$ error $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. After issuing a fatal error the T_EX run halts. No PDF file will be produced in this case (DVI mode runs may produce a truncated DVI file).

```

\msg_critical:nnnnnn
\msg_critical:nnxxxx
\msg_critical:nnnnn
\msg_critical:nnxxx
\msg_critical:nnnn
\msg_critical:nnxx
\msg_critical:nnn
\msg_critical:nnx
\msg_critical:nn

```

Updated: 2012-08-11

```

\msg_critical:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg three}
{\arg four}

```

Issues $\langle module \rangle$ error $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. After issuing a critical error, T_EX stops reading the current input file. This may halt the T_EX run (if the current file is the main file) or may abort reading a sub-file.

T_EXhackers note: The T_EX `\endinput` primitive is used to exit the file. In particular, the rest of the current line remains in the input stream.

```

\msg_error:nnnnnn
\msg_error:nnxxxx
\msg_error:nnnnn
\msg_error:nnxxx
\msg_error:nnnn
\msg_error:nnxx
\msg_error:nnn
\msg_error:nnx
\msg_error:nn

```

Updated: 2012-08-11

```

\msg_error:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg three}
{\arg four}

```

Issues $\langle module \rangle$ error $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The error interrupts processing and issues the text at the terminal. After user input, the run continues.

```

\msg_warning:nnnnnn
\msg_warning:nnxxxx
\msg_warning:nnnnn
\msg_warning:nnxxx
\msg_warning:nnnn
\msg_warning:nnxx
\msg_warning:nnn
\msg_warning:nnx
\msg_warning:nn

```

Updated: 2012-08-11

```

\msg_warning:nnxxxx {\module} {\message} {\arg one} {\arg two} {\arg three}
{\arg four}

```

Issues $\langle module \rangle$ warning $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The warning text is added to the log file and the terminal, but the T_EX run is not interrupted.

<code>\msg_info:nnnnnn</code>	<code>\msg_info:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_info:nnxxxx</code>	
<code>\msg_info:nnnnn</code>	Issues <i><module></i> information <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The information text is added to the log file.
<code>\msg_info:nnxxx</code>	
<code>\msg_info:nnnn</code>	
<code>\msg_info:nnxx</code>	
<code>\msg_info:nnn</code>	
<code>\msg_info:nnx</code>	
<code>\msg_info:nn</code>	

Updated: 2012-08-11

<code>\msg_log:nnnnnn</code>	<code>\msg_log:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_log:nnxxxx</code>	
<code>\msg_log:nnnnn</code>	Issues <i><module></i> information <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The information text is added to the log file: the output is briefer than <code>\msg_info:nnnnnn</code> .
<code>\msg_log:nnxxx</code>	
<code>\msg_log:nnnn</code>	
<code>\msg_log:nnxx</code>	
<code>\msg_log:nnn</code>	
<code>\msg_log:nnx</code>	
<code>\msg_log:nn</code>	

Updated: 2012-08-11

<code>\msg_none:nnnnnn</code>	<code>\msg_none:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_none:nnxxxx</code>	
<code>\msg_none:nnnnn</code>	Does nothing: used as a message class to prevent any output at all (see the discussion of message redirection).
<code>\msg_none:nnxxx</code>	
<code>\msg_none:nnnn</code>	
<code>\msg_none:nnxx</code>	
<code>\msg_none:nnn</code>	
<code>\msg_none:nnx</code>	
<code>\msg_none:nn</code>	

Updated: 2012-08-11

4 Redirecting messages

Each message has a “name”, which can be used to alter the behaviour of the message when it is given. Thus we might have

```
\msg_new:nnnn { module } { my-message } { Some-text } { Some-more-text }
```

to define a message, with

```
\msg_error:nn { module } { my-message }
```

when it is used. With no filtering, this raises an error. However, we could alter the behaviour with

```
\msg_redirect_class:nn { error } { warning }
```

to turn all errors into warnings, or with

```
\msg_redirect_module:nnn { module } { error } { warning }
```

to alter only messages from that module, or even

```
\msg_redirect_name:nnn { module } { my-message } { warning }
```

to target just one message. Redirection applies first to individual messages, then to messages from one module and finally to messages of one class. Thus it is possible to select out an individual message for special treatment even if the entire class is already redirected.

Multiple redirections are possible. Redirections can be cancelled by providing an empty argument for the target class. Redirection to a missing class raises an error immediately. Infinite loops are prevented by eliminating the redirection starting from the target of the redirection that caused the loop to appear. Namely, if redirections are requested as $A \rightarrow B$, $B \rightarrow C$ and $C \rightarrow A$ in this order, then the $A \rightarrow B$ redirection is cancelled.

```
\msg_redirect_class:nn
```

Updated: 2012-04-27

```
\msg_redirect_class:nn {<class one>} {<class two>}
```

Changes the behaviour of messages of *<class one>* so that they are processed using the code for those of *<class two>*.

```
\msg_redirect_module:nnn
```

Updated: 2012-04-27

```
\msg_redirect_module:nnn {<module>} {<class one>} {<class two>}
```

Redirects message of *<class one>* for *<module>* to act as though they were from *<class two>*. Messages of *<class one>* from sources other than *<module>* are not affected by this redirection. This function can be used to make some messages “silent” by default. For example, all of the **warning** messages of *<module>* could be turned off with:

```
\msg_redirect_module:nnn { module } { warning } { none }
```

```
\msg_redirect_name:nnn
```

Updated: 2012-04-27

```
\msg_redirect_name:nnn {<module>} {<message>} {<class>}
```

Redirects a specific *<message>* from a specific *<module>* to act as a member of *<class>* of messages. No further redirection is performed. This function can be used to make a selected message “silent” without changing global parameters:

```
\msg_redirect_name:nnn { module } { annoying-message } { none }
```

Part XIX

The l3file package

File and I/O operations

This module provides functions for working with external files. Some of these functions apply to an entire file, and have prefix `\file_...`, while others are used to work with files on a line by line basis and have prefix `\ior_...` (reading) or `\iow_...` (writing).

It is important to remember that when reading external files \TeX attempts to locate them using both the operating system path and entries in the \TeX file database (most \TeX systems use such a database). Thus the “current path” for \TeX is somewhat broader than that for other programs.

For functions which expect a $\langle file\ name \rangle$ argument, this argument may contain both literal items and expandable content, which should on full expansion be the desired file name. Active characters (as declared in `\l_char_active_seq`) are *not* expanded, allowing the direct use of these in file names. Quote tokens (") are not permitted in file names as they are reserved for internal use by some \TeX primitives.

Spaces are trimmed at the beginning and end of the file name: this reflects the fact that some file systems do not allow or interact unpredictably with spaces in these positions. When no extension is given, this will trim spaces from the start of the name only.

1 Input–output stream management

As \TeX engines have a limited number of input and output streams, direct use of the streams by the programmer is not supported in \LaTeX 3. Instead, an internal pool of streams is maintained, and these are allocated and deallocated as needed by other modules. As a result, the programmer should close streams when they are no longer needed, to release them for other processes.

Note that I/O operations are global: streams should all be declared with global names and treated accordingly.

`\ior_new:N`
`\ior_new:c`
`\iow_new:N`
`\iow_new:c`

New: 2011-09-26
Updated: 2011-12-27

`\ior_new:N` $\langle stream \rangle$
`\iow_new:N` $\langle stream \rangle$

Globally reserves the name of the $\langle stream \rangle$, either for reading or for writing as appropriate. The $\langle stream \rangle$ is not opened until the appropriate `\..._open:Nn` function is used. Attempting to use a $\langle stream \rangle$ which has not been opened is an error, and the $\langle stream \rangle$ will behave as the corresponding `\c_term_....`

`\ior_open:Nn`
`\ior_open:cn`

Updated: 2012-02-10

`\ior_open:Nn` $\langle stream \rangle$ $\{ \langle file\ name \rangle \}$

Opens $\langle file\ name \rangle$ for reading using $\langle stream \rangle$ as the control sequence for file access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle file\ name \rangle$ until a `\ior_close:N` instruction is given or the \TeX run ends. If the file is not found, an error is raised.

<hr/> <code>\ior_open:NnTF</code> <hr/>	<code>\ior_open:NnTF <stream> {<file name>} {<true code>} {<false code>}</code>
<code>\ior_open:cnTF</code> <hr/>	
<hr/> New: 2013-01-12 <hr/>	Opens <i><file name></i> for reading using <i><stream></i> as the control sequence for file access. If the <i><stream></i> was already open it is closed before the new operation begins. The <i><stream></i> is available for access immediately and will remain allocated to <i><file name></i> until a <code>\ior_close:N</code> instruction is given or the TeX run ends. The <i><true code></i> is then inserted into the input stream. If the file is not found, no error is raised and the <i><false code></i> is inserted into the input stream.
<hr/>	
<code>\iow_open:Nn</code> <hr/>	<code>\iow_open:Nn <stream> {<file name>}</code>
<code>\iow_open:cn</code> <hr/>	
<hr/> Updated: 2012-02-09 <hr/>	Opens <i><file name></i> for writing using <i><stream></i> as the control sequence for file access. If the <i><stream></i> was already open it is closed before the new operation begins. The <i><stream></i> is available for access immediately and will remain allocated to <i><file name></i> until a <code>\iow_close:N</code> instruction is given or the TeX run ends. Opening a file for writing clears any existing content in the file (<i>i.e.</i> writing is <i>not</i> additive).
<hr/>	
<code>\ior_close:N</code> <hr/>	<code>\ior_close:N <stream></code>
<code>\ior_close:c</code> <hr/>	<code>\iow_close:N <stream></code>
<code>\iow_close:N</code> <hr/>	Closes the <i><stream></i> . Streams should always be closed when they are finished with as this ensures that they remain available to other programmers.
<code>\iow_close:c</code> <hr/>	
<hr/> Updated: 2012-07-31 <hr/>	
<hr/>	
<code>\ior_show_list:</code> <hr/>	<code>\ior_show_list:</code>
<code>\ior_log_list:</code> <hr/>	<code>\ior_log_list:</code>
<code>\iow_show_list:</code> <hr/>	<code>\iow_show_list:</code>
<code>\iow_log_list:</code> <hr/>	<code>\iow_log_list:</code>
<hr/> New: 2017-06-27 <hr/>	Display (to the terminal or log file) a list of the file names associated with each open (read or write) stream. This is intended for tracking down problems.

1.1 Reading from files

Reading from files and reading from the terminal are separate processes in `expl3`. The functions `\ior_get:NN` and `\ior_str_get:NN`, and their branching equivalents, are designed to work with *files*.

<code>\ior_get:NN</code>
<code>\ior_get:NNTF</code>
New: 2012-06-24
Updated: 2019-03-23

`\ior_get:NN` $\langle stream \rangle$ $\langle token\ list\ variable \rangle$
`\ior_get:NNTF` $\langle stream \rangle$ $\langle token\ list\ variable \rangle$ $\langle true\ code \rangle$ $\langle false\ code \rangle$

Function that reads one or more lines (until an equal number of left and right braces are found) from the file input $\langle stream \rangle$ and stores the result locally in the $\langle token\ list \rangle$ variable. The material read from the $\langle stream \rangle$ is tokenized by T_EX according to the category codes and `\endlinechar` in force when the function is used. Assuming normal settings, any lines which do not end in a comment character % have the line ending converted to a space, so for example input

```
a b c
```

results in a token list `a_b_c_`. Any blank line is converted to the token `\par`. Therefore, blank lines can be skipped by using a test such as

```
\ior_get:NN \l_my_stream \l_tmpa_tl
\tl_set:Nn \l_tmpb_tl { \par }
\tl_if_eq:NMF \l_tmpa_tl \l_tmpb_tl
...
```

Also notice that if multiple lines are read to match braces then the resulting token list can contain `\par` tokens. In the non-branching version, where the $\langle stream \rangle$ is not open the $\langle tl\ var \rangle$ is set to `\q_no_value`.

T_EXhackers note: This protected macro is a wrapper around the T_EX primitive `\read`. Regardless of settings, T_EX replaces trailing space and tab characters (character codes 32 and 9) in each line by an end-of-line character (character code `\endlinechar`, omitted if `\endlinechar` is negative or too large) before turning characters into tokens according to current category codes. With default settings, spaces appearing at the beginning of lines are also ignored.

<code>\ior_str_get:NN</code>
<code>\ior_str_get:NNTF</code>
New: 2016-12-04
Updated: 2019-03-23

`\ior_str_get:NN` $\langle stream \rangle$ $\langle token\ list\ variable \rangle$
`\ior_str_get:NNTF` $\langle stream \rangle$ $\langle token\ list\ variable \rangle$ $\langle true\ code \rangle$ $\langle false\ code \rangle$

Function that reads one line from the file input $\langle stream \rangle$ and stores the result locally in the $\langle token\ list \rangle$ variable. The material is read from the $\langle stream \rangle$ as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). Multiple whitespace characters are retained by this process. It always only reads one line and any blank lines in the input result in the $\langle token\ list\ variable \rangle$ being empty. Unlike `\ior_get:NN`, line ends do not receive any special treatment. Thus input

```
a b c
```

results in a token list `a b c` with the letters `a`, `b`, and `c` having category code 12. In the non-branching version, where the $\langle stream \rangle$ is not open the $\langle tl\ var \rangle$ is set to `\q_no_value`.

T_EXhackers note: This protected macro is a wrapper around the ε -T_EX primitive `\readline`. Regardless of settings, T_EX removes trailing space and tab characters (character codes 32 and 9). However, the end-line character normally added by this primitive is not included in the result of `\ior_str_get:NN`.

All mappings are done at the current group level, *i.e.* any local assignments made by the $\langle function \rangle$ or $\langle code \rangle$ discussed below remain in effect after the loop.

<hr/> <code>\ior_map_inline:Nn</code> <hr/> New: 2012-02-11 <hr/>	<code>\ior_map_inline:Nn <stream> {<inline function>}</code> Applies the <i><inline function></i> to each set of <i><lines></i> obtained by calling <code>\ior_get:NN</code> until reaching the end of the file. \TeX ignores any trailing new-line marker from the file it reads. The <i><inline function></i> should consist of code which receives the <i><line></i> as <code>#1</code> .
<hr/> <code>\ior_str_map_inline:Nn</code> <hr/> New: 2012-02-11 <hr/>	<code>\ior_str_map_inline:Nn <stream> {<inline function>}</code> Applies the <i><inline function></i> to every <i><line></i> in the <i><stream></i> . The material is read from the <i><stream></i> as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). The <i><inline function></i> should consist of code which receives the <i><line></i> as <code>#1</code> . Note that \TeX removes trailing space and tab characters (character codes 32 and 9) from every line upon input. \TeX also ignores any trailing new-line marker from the file it reads.
<hr/> <code>\ior_map_variable:NNn</code> <hr/> New: 2019-01-13 <hr/>	<code>\ior_map_variable:NNn <stream> <tl var> {<code>}</code> For each set of <i><lines></i> obtained by calling <code>\ior_get:NN</code> until reaching the end of the file, stores the <i><lines></i> in the <i><tl var></i> then applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. Its value after the loop is the last set of <i><lines></i> , or its original value if the <i><stream></i> is empty. \TeX ignores any trailing new-line marker from the file it reads. This function is typically faster than <code>\ior_map_inline:Nn</code> .
<hr/> <code>\ior_str_map_variable:NNn</code> <hr/> New: 2019-01-13 <hr/>	<code>\ior_str_map_variable:NNn <stream> <variable> {<code>}</code> For each <i><line></i> in the <i><stream></i> , stores the <i><line></i> in the <i><variable></i> then applies the <i><code></i> . The material is read from the <i><stream></i> as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. Its value after the loop is the last <i><line></i> , or its original value if the <i><stream></i> is empty. Note that \TeX removes trailing space and tab characters (character codes 32 and 9) from every line upon input. \TeX also ignores any trailing new-line marker from the file it reads. This function is typically faster than <code>\ior_str_map_inline:Nn</code> .
<hr/> <code>\ior_map_break:</code> <hr/> New: 2012-06-29 <hr/>	<code>\ior_map_break:</code> Used to terminate a <code>\ior_map_...</code> function before all lines from the <i><stream></i> have been processed. This normally takes place within a conditional statement, for example

```

\ior_map_inline:Nn \l_my_ior
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \ior_map_break: }
  {
    % Do something useful
  }
}

```

Use outside of a `\ior_map_...` scenario leads to low level \TeX errors.

\TeX hackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

`\ior_map_break:n`

`New: 2012-06-29`

`\ior_map_break:n {<code>}`

Used to terminate a `\ior_map_...` function before all lines in the `<stream>` have been processed, inserting the `<code>` after the mapping has ended. This normally takes place within a conditional statement, for example

```
\ior_map_inline:Nn \l_my_ior
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \ior_map_break:n { <code> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\ior_map_...` scenario leads to low level `TeX` errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the `<code>` is inserted into the input stream. This depends on the design of the mapping function.

`\ior_if_eof_p:N *``\ior_if_eof:NTF *`

`Updated: 2012-02-10`

`\ior_if_eof_p:N <stream>``\ior_if_eof:NTF <stream> {<true code>} {<false code>}`

Tests if the end of a file `<stream>` has been reached during a reading operation. The test also returns a `true` value if the `<stream>` is not open.

1.2 Writing to files

`\iow_now:Nn``\iow_now:(Nx|cn|cx)`

`Updated: 2012-06-05`

`\iow_now:Nn <stream> {<tokens>}`

This functions writes `<tokens>` to the specified `<stream>` immediately (*i.e.* the write operation is called on expansion of `\iow_now:Nn`).

`\iow_log:n``\iow_log:x``\iow_log:n {<tokens>}`

This function writes the given `<tokens>` to the log (transcript) file immediately: it is a dedicated version of `\iow_now:Nn`.

`\iow_term:n``\iow_term:x``\iow_term:n {<tokens>}`

This function writes the given `<tokens>` to the terminal file immediately: it is a dedicated version of `\iow_now:Nn`.

<hr/>	
<code>\iow_shipout:Nn</code>	<code>\iow_shipout:Nn <stream> {\tokens}</code>
<code>\iow_shipout:(Nx cn cx)</code>	This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised (<i>i.e.</i> at shipout). The x -type variants expand the $\langle tokens \rangle$ at the point where the function is used but <i>not</i> when the resulting tokens are written to the $\langle stream \rangle$ (<i>cf.</i> <code>\iow_shipout_x:Nn</code>).
<hr/>	

T_EXhackers note: When using `expl3` with a format other than L^AT_EX, new line characters inserted using `\iow_newline:` or using the line-wrapping code `\iow_wrap:nnnN` are not recognized in the argument of `\iow_shipout:Nn`. This may lead to the insertion of additional unwanted line-breaks.

<hr/>	
<code>\iow_shipout_x:Nn</code>	<code>\iow_shipout_x:Nn <stream> {\tokens}</code>
<code>\iow_shipout_x:(Nx cn cx)</code>	This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised (<i>i.e.</i> at shipout). The $\langle tokens \rangle$ are expanded at the time of writing in addition to any expansion when the function is used. This makes these functions suitable for including material finalised during the page building process (such as the page number integer).
Updated: 2012-09-08	
<hr/>	

T_EXhackers note: This is a wrapper around the T_EX primitive `\write`. When using `expl3` with a format other than L^AT_EX, new line characters inserted using `\iow_newline:` or using the line-wrapping code `\iow_wrap:nnnN` are not recognized in the argument of `\iow_shipout:Nn`. This may lead to the insertion of additional unwanted line-breaks.

<hr/>	
<code>\iow_char:N *</code>	<code>\iow_char:N \<char></code>
	Inserts $\langle char \rangle$ into the output stream. Useful when trying to write difficult characters such as %, {, }, <i>etc.</i> in messages, for example:

`\iow_now:Nx \g_my_iow { \iow_char:N \{ text \iow_char:N \} }`

The function has no effect if writing is taking place without expansion (*e.g.* in the second argument of `\iow_now:Nn`).

<hr/>	
<code>\iow_newline: *</code>	<code>\iow_newline:</code>
	Function to add a new line within the $\langle tokens \rangle$ written to a file. The function has no effect if writing is taking place without expansion (<i>e.g.</i> in the second argument of <code>\iow_now:Nn</code>).

T_EXhackers note: When using `expl3` with a format other than L^AT_EX, the character inserted by `\iow_newline:` is not recognized by T_EX, which may lead to the insertion of additional unwanted line-breaks. This issue only affects `\iow_shipout:Nn`, `\iow_shipout_x:Nn` and direct uses of primitive operations.

1.3 Wrapping lines in output

`\iow_wrap:nnnN`
`\iow_wrap:nxnN`

New: 2012-06-28
Updated: 2017-12-04

`\iow_wrap:nnnN` $\{\langle text \rangle\}$ $\{\langle run-on text \rangle\}$ $\{\langle set up \rangle\}$ $\langle function \rangle$

This function wraps the $\langle text \rangle$ to a fixed number of characters per line. At the start of each line which is wrapped, the $\langle run-on text \rangle$ is inserted. The line character count targeted is the value of `\l_iow_line_count_int` minus the number of characters in the $\langle run-on text \rangle$ for all lines except the first, for which the target number of characters is simply `\l_iow_line_count_int` since there is no run-on text. The $\langle text \rangle$ and $\langle run-on text \rangle$ are exhaustively expanded by the function, with the following substitutions:

- `\` or `\iow_newline`: may be used to force a new line,
- `_` may be used to represent a forced space (for example after a control sequence),
- `\#`, `\%`, `\{`, `\}`, `\~` may be used to represent the corresponding character,
- `\iow_allow_break`: may be used to allow a line-break without inserting a space (this is experimental),
- `\iow_indent:n` may be used to indent a part of the $\langle text \rangle$ (not the $\langle run-on text \rangle$).

Additional functions may be added to the wrapping by using the $\langle set up \rangle$, which is executed before the wrapping takes place: this may include overriding the substitutions listed.

Any expandable material in the $\langle text \rangle$ which is not to be expanded on wrapping should be converted to a string using `\token_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N`, *etc.*

The result of the wrapping operation is passed as a braced argument to the $\langle function \rangle$, which is typically a wrapper around a write operation. The output of `\iow_wrap:nnnN` (*i.e.* the argument passed to the $\langle function \rangle$) consists of characters of category “other” (category code 12), with the exception of spaces which have category “space” (category code 10). This means that the output does *not* expand further when written to a file.

T_EXhackers note: Internally, `\iow_wrap:nnnN` carries out an x-type expansion on the $\langle text \rangle$ to expand it. This is done in such a way that `\exp_not:N` or `\exp_not:n` *could* be used to prevent expansion of material. However, this is less conceptually clear than conversion to a string, which is therefore the supported method for handling expandable material in the $\langle text \rangle$.

`\iow_indent:n`

New: 2011-09-21

`\iow_indent:n` $\{\langle text \rangle\}$

In the first argument of `\iow_wrap:nnnN` (for instance in messages), indents $\langle text \rangle$ by four spaces. This function does not cause a line break, and only affects lines which start within the scope of the $\langle text \rangle$. In case the indented $\langle text \rangle$ should appear on separate lines from the surrounding text, use `\` to force line breaks.

`\l_iow_line_count_int`

New: 2012-06-24

The maximum number of characters in a line to be written by the `\iow_wrap:nnnN` function. This value depends on the T_EX system in use: the standard value is 78, which is typically correct for unmodified T_EXlive and MiK_T_EX systems.

1.4 Constant input–output streams, and variables

<code>\g_tmpa_iow</code> <code>\g_tmpb_iow</code>	Scratch input stream for global use. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> New: 2017-12-11 <hr/>	

<code>\c_log_iow</code> <code>\c_term_iow</code>	Constant output streams for writing to the log and to the terminal (plus the log), respectively.
<hr/>	

<code>\g_tmpa_iow</code> <code>\g_tmpb_iow</code>	Scratch output stream for global use. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> New: 2017-12-11 <hr/>	

1.5 Primitive conditionals

<code>\if_eof:w ★</code>	<code>\if_eof:w <stream></code> <code><true code></code> <code>\else:</code> <code><false code></code> <code>\fi:</code> Tests if the <code><stream></code> returns “end of file”, which is true for non-existent files. The <code>\else:</code> branch is optional.
<hr/>	

T_EXhackers note: This is the T_EX primitive `\ifeof`.

2 File operation functions

<code>\g_file_curr_dir_str</code> <code>\g_file_curr_name_str</code> <code>\g_file_curr_ext_str</code>	Contain the directory, name and extension of the current file. The directory is empty if the file was loaded without an explicit path (<i>i.e.</i> if it is in the T _E X search path), and does <i>not</i> end in / other than the case that it is exactly equal to the root directory. The <code><name></code> and <code><ext></code> parts together make up the file name, thus the <code><name></code> part may be thought of as the “job name” for the current file. Note that T _E X does not provide information on the <code><ext></code> part for the main (top level) file and that this file always has an empty <code><dir></code> component. Also, the <code><name></code> here will be equal to <code>\c_sys_jobname_str</code> , which may be different from the real file name (if set using <code>--jobname</code> , for example).
<hr/> New: 2017-06-21 <hr/>	

<hr/> <code>\l_file_search_path_seq</code> <hr/> New: 2017-06-18	<p>Each entry is the path to a directory which should be searched when seeking a file. Each path can be relative or absolute, and should not include the trailing slash. The entries are not expanded when used so may contain active characters but should not feature any variable content. Spaces need not be quoted.</p> <p>T_EXhackers note: When working as a package in L^AT_EX 2_ε, <code>expl3</code> will automatically append the current <code>\input@path</code> to the set of values from <code>\l_file_search_path_seq</code>.</p>
<hr/> <code>\file_if_exist:nTF</code> <hr/> Updated: 2012-02-10	<code>\file_if_exist:nTF {<file name>} {<true code>} {<false code>}</code> <p>Searches for <code><file name></code> using the current T_EX search path and the additional paths controlled by <code>\l_file_search_path_seq</code>.</p>
<hr/> <code>\file_get:nnN</code> <code>\file_get:nnNTF</code> <hr/> New: 2019-01-16 Updated: 2019-02-16	<code>\file_get:nnN {<filename>} {<setup>} <tl></code> <code>\file_get:nnNTF {<filename>} {<setup>} <tl> {<true code>} {<false code>}</code> <p>Defines <code><tl></code> to the contents of <code><filename></code>. Category codes may need to be set appropriately via the <code><setup></code> argument. The non-branching version sets the <code><tl></code> to <code>\q_no_value</code> if the file is not found. The branching version runs the <code><true code></code> after the assignment to <code><tl></code> if the file is found, and <code><false code></code> otherwise.</p>
<hr/> <code>\file_get_full_name:nN</code> <code>\file_get_full_name:VN</code> <code>\file_get_full_name:nNTF</code> <code>\file_get_full_name:VNTF</code> <hr/> Updated: 2019-02-16	<code>\file_get_full_name:nN {<file name>} <tl></code> <code>\file_get_full_name:nNTF {<file name>} <tl> {<true code>} {<false code>}</code> <p>Searches for <code><file name></code> in the path as detailed for <code>\file_if_exist:nTF</code>, and if found sets the <code><tl var></code> the fully-qualified name of the file, <i>i.e.</i> the path and file name. This includes an extension <code>.tex</code> when the given <code><file name></code> has no extension but the file found has that extension. In the non-branching version, the <code><tl var></code> will be set to <code>\q_no_value</code> in the case that the file does not exist.</p>
<hr/> <code>\file_full_name:n</code> ☆ <code>\file_full_name:V</code> ☆ <hr/> New: 2019-09-03	<code>\file_full_name:n {<file name>}</code> <p>Searches for <code><file name></code> in the path as detailed for <code>\file_if_exist:nTF</code>, and if found leaves the fully-qualified name of the file, <i>i.e.</i> the path and file name, in the input stream. This includes an extension <code>.tex</code> when the given <code><file name></code> has no extension but the file found has that extension. If the file is not found on the path, the expansion is empty.</p>

<code>\file_parse_full_name:nNNN</code>
<code>\file_parse_full_name:VNNN</code>
New: 2017-06-23
Updated: 2017-06-26

`\file_parse_full_name:nNNN` $\{\langle full\ name\rangle\}$ $\langle dir\rangle$ $\langle name\rangle$ $\langle ext\rangle$

Parses the $\langle full\ name\rangle$ and splits it into three parts, each of which is returned by setting the appropriate local string variable:

- The $\langle dir\rangle$: everything up to the last / (path separator) in the $\langle file\ path\rangle$. As with system PATH variables and related functions, the $\langle dir\rangle$ does *not* include the trailing / unless it points to the root directory. If there is no path (only a file name), $\langle dir\rangle$ is empty.
- The $\langle name\rangle$: everything after the last / up to the last ., where both of those characters are optional. The $\langle name\rangle$ may contain multiple . characters. It is empty if $\langle full\ name\rangle$ consists only of a directory name.
- The $\langle ext\rangle$: everything after the last . (including the dot). The $\langle ext\rangle$ is empty if there is no . after the last /.

This function does not expand the $\langle full\ name\rangle$ before turning it to a string. It assume that the $\langle full\ name\rangle$ either contains no quote (") characters or is surrounded by a pair of quotes.

<code>\file_hex_dump:n</code>	☆
<code>\file_hex_dump:nnn</code>	☆
New: 2019-11-19	

`\file_hex_dump:n` $\{\langle file\ name\rangle\}$
`\file_hex_dump:nnn` $\{\langle file\ name\rangle\}$ $\{\langle start\ index\rangle\}$ $\{\langle end\ index\rangle\}$

Searches for $\langle file\ name\rangle$ using the current T_EX search path and the additional paths controlled by `\l_file_search_path_seq`. It then expands to leave the hexadecimal dump of the file content in the input stream. The file is read as bytes, which means that in contrast to most T_EX behaviour there will be a difference in result depending on the line endings used in text files. The same file will produce the same result between different engines: the algorithm used is the same in all cases. When the file is not found, the result of expansion is empty. The $\{\langle start\ index\rangle\}$ and $\{\langle end\ index\rangle\}$ values work as described for `\str_range:nnn`.

<code>\file_get_hex_dump:nN</code>
<code>\file_get_hex_dump:nNTF</code>
<code>\file_get_hex_dump:nnnN</code>
<code>\file_get_hex_dump:nnnNTF</code>
New: 2019-11-19

`\file_get_hex_dump:nN` $\{\langle file\ name\rangle\}$ $\langle tl\ var\rangle$
`\file_get_hex_dump:nnnN` $\{\langle file\ name\rangle\}$ $\{\langle start\ index\rangle\}$ $\{\langle end\ index\rangle\}$ $\langle tl\ var\rangle$

Sets the $\langle tl\ var\rangle$ to the result of applying `\file_hex_dump:n/\file_hex_dump:nnn` to the $\langle file\rangle$. If the file is not found, the $\langle tl\ var\rangle$ will be set to `\q_no_value`.

<code>\file_md5five_hash:n</code>	☆
New: 2019-09-03	

`\file_md5five_hash:n` $\{\langle file\ name\rangle\}$

Searches for $\langle file\ name\rangle$ using the current T_EX search path and the additional paths controlled by `\l_file_search_path_seq`. It then expands to leave the MD5 sum generated from the contents of the file in the input stream. The file is read as bytes, which means that in contrast to most T_EX behaviour there will be a difference in result depending on the line endings used in text files. The same file will produce the same result between different engines: the algorithm used is the same in all cases. When the file is not found, the result of expansion is empty.

<code>\file_get_md5five_hash:nN</code>
<code>\file_get_md5five_hash:nNTF</code>
New: 2017-07-11
Updated: 2019-02-16

`\file_get_md5five_hash:nN` $\{\langle file\ name\rangle\}$ $\langle tl\ var\rangle$

Sets the $\langle tl\ var\rangle$ to the result of applying `\file_md5five_hash:n` to the $\langle file\rangle$. If the file is not found, the $\langle tl\ var\rangle$ will be set to `\q_no_value`.

`\file_size:n` ☆

New: 2019-09-03

`\file_size:n` $\{\langle file\ name\rangle\}$

Searches for $\langle file\ name\rangle$ using the current \TeX search path and the additional paths controlled by `\l_file_search_path_seq`. It then expands to leave the size of the file in bytes in the input stream. When the file is not found, the result of expansion is empty.

`\file_get_size:nN`

`\file_get_size:nNTF`

New: 2017-07-09

Updated: 2019-02-16

`\file_get_size:nN` $\{\langle file\ name\rangle\}$ $\langle tl\ var\rangle$

Sets the $\langle tl\ var\rangle$ to the result of applying `\file_size:n` to the $\langle file\rangle$. If the file is not found, the $\langle tl\ var\rangle$ will be set to `\q_no_value`. This is not available in older versions of \XeTeX .

`\file_timestamp:n` ☆

New: 2019-09-03

`\file_timestamp:n` $\{\langle file\ name\rangle\}$

Searches for $\langle file\ name\rangle$ using the current \TeX search path and the additional paths controlled by `\l_file_search_path_seq`. It then expands to leave the modification timestamp of the file in the input stream. The timestamp is of the form $D:\langle year\rangle\langle month\rangle\langle day\rangle\langle hour\rangle\langle minute\rangle\langle second\rangle\langle offset\rangle$, where the latter may be Z (UTC) or $\langle plus-minus\rangle\langle hours\rangle'\langle minutes\rangle'$. When the file is not found, the result of expansion is empty. This is not available in older versions of \XeTeX .

`\file_get_timestamp:nN`

`\file_get_timestamp:nNTF`

New: 2017-07-09

Updated: 2019-02-16

`\file_get_timestamp:nN` $\{\langle file\ name\rangle\}$ $\langle tl\ var\rangle$

Sets the $\langle tl\ var\rangle$ to the result of applying `\file_timestamp:n` to the $\langle file\rangle$. If the file is not found, the $\langle tl\ var\rangle$ will be set to `\q_no_value`. This is not available in older versions of \XeTeX .

`\file_compare_timestamp_p:nNn` ☆

`\file_compare_timestamp:nNnTF` ☆

New: 2019-05-13

Updated: 2019-09-20

`\file_compare_timestamp:nNn` $\{\langle file-1\rangle\}$ $\langle comparator\rangle$ $\{\langle file-2\rangle\}$ $\{\langle true\ code\rangle\}$ $\{\langle false\ code\rangle\}$

Compares the file stamps on the two $\langle files\rangle$ as indicated by the $\langle comparator\rangle$, and inserts either the $\langle true\ code\rangle$ or $\langle false\ case\rangle$ as required. A file which is not found is treated as older than any file which is found. This allows for example the construct

```
\file_compare_timestamp:nNnT { source-file } > { derived-file }
{
  % Code to regenerate derived file
}
```

to work when the derived file is entirely absent. The timestamp of two absent files is regarded as different. This is not available in older versions of \XeTeX .

`\file_input:n`

Updated: 2017-06-26

`\file_input:n` $\{\langle file\ name\rangle\}$

Searches for $\langle file\ name\rangle$ in the path as detailed for `\file_if_exist:nTF`, and if found reads in the file as additional \LaTeX source. All files read are recorded for information and the file name stack is updated by this function. An error is raised if the file is not found.

<code>\file_if_exist_input:n</code>	<code>\file_if_exist_input:n {<file name>}</code>
<code>\file_if_exist_input:nF</code>	<code>\file_if_exist_input:nF {<file name>} {<false code>}</code>
New: 2014-07-02	Searches for <code><file name></code> using the current <code>TeX</code> search path and the additional paths controlled by <code>\file_path_include:n</code> . If found then reads in the file as additional <code>LaTeX</code> source as described for <code>\file_input:n</code> , otherwise inserts the <code><false code></code> . Note that these functions do not raise an error if the file is not found, in contrast to <code>\file_input:n</code> .

<code>\file_input_stop:</code>	<code>\file_input_stop:</code>
New: 2017-07-07	Ends the reading of a file started by <code>\file_input:n</code> or similar before the end of the file is reached. Where the file reading is being terminated due to an error, <code>\msg_critical:nn(nn)</code> should be preferred.

TeXhackers note: This function must be used on a line on its own: `TeX` reads files line-by-line and so any additional tokens in the “current” line will still be read.

This is also true if the function is hidden inside another function (which will be the normal case), i.e., all tokens on the same line in the source file are still processed. Putting it on a line by itself in the definition doesn’t help as it is the line where it is used that counts!

<code>\file_show_list:</code>	<code>\file_show_list:</code>
<code>\file_log_list:</code>	<code>\file_log_list:</code>
	These functions list all files loaded by <code>LaTeX 2_ε</code> commands that populate <code>\@filelist</code> or by <code>\file_input:n</code> . While <code>\file_show_list:</code> displays the list in the terminal, <code>\file_log_list:</code> outputs it to the log file only.

Part XX

The l3skip package

Dimensions and skips

L^AT_EX3 provides two general length variables: `dim` and `skip`. Lengths stored as `dim` variables have a fixed length, whereas `skip` lengths have a rubber (stretch/shrink) component. In addition, the `muskip` type is available for use in math mode: this is a special form of `skip` where the lengths involved are determined by the current math font (in μ). There are common features in the creation and setting of length variables, but for clarity the functions are grouped by variable type.

1 Creating and initialising `dim` variables

<code>\dim_new:N</code>
<code>\dim_new:c</code>

`\dim_new:N` $\langle dimension \rangle$

Creates a new $\langle dimension \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle dimension \rangle$ is initially equal to 0pt.

<code>\dim_const:Nn</code>
<code>\dim_const:cn</code>

`\dim_const:Nn` $\langle dimension \rangle$ $\{ \langle dimension expression \rangle \}$

Creates a new constant $\langle dimension \rangle$ or raises an error if the name is already taken. The value of the $\langle dimension \rangle$ is set globally to the $\langle dimension expression \rangle$.

New: 2012-03-05

<code>\dim_zero:N</code>
<code>\dim_zero:c</code>
<code>\dim_gzero:N</code>
<code>\dim_gzero:c</code>

`\dim_zero:N` $\langle dimension \rangle$

Sets $\langle dimension \rangle$ to 0pt.

<code>\dim_zero_new:N</code>
<code>\dim_zero_new:c</code>
<code>\dim_gzero_new:N</code>
<code>\dim_gzero_new:c</code>

`\dim_zero_new:N` $\langle dimension \rangle$

Ensures that the $\langle dimension \rangle$ exists globally by applying `\dim_new:N` if necessary, then applies `\dim_(g)zero:N` to leave the $\langle dimension \rangle$ set to zero.

New: 2012-01-07

<code>\dim_if_exist_p:N</code> \star
<code>\dim_if_exist_p:c</code> \star
<code>\dim_if_exist:N\overline{TF}</code> \star
<code>\dim_if_exist:c\overline{TF}</code> \star

`\dim_if_exist_p:N` $\langle dimension \rangle$

`\dim_if_exist:N \overline{TF}` $\langle dimension \rangle$ $\{ \langle true code \rangle \} \{ \langle false code \rangle \}$

Tests whether the $\langle dimension \rangle$ is currently defined. This does not check that the $\langle dimension \rangle$ really is a dimension variable.

New: 2012-03-03

2 Setting dim variables

<code>\dim_add:Nn</code>	<code>\dim_add:Nn <dimension> {<dimension expression>}</code>
<code>\dim_add:cn</code>	
<code>\dim_gadd:Nn</code>	Adds the result of the $\langle dimension expression \rangle$ to the current content of the $\langle dimension \rangle$.
<code>\dim_gadd:cn</code>	

Updated: 2011-10-22

<code>\dim_set:Nn</code>	<code>\dim_set:Nn <dimension> {<dimension expression>}</code>
<code>\dim_set:cn</code>	
<code>\dim_gset:Nn</code>	Sets $\langle dimension \rangle$ to the value of $\langle dimension expression \rangle$, which must evaluate to a length with units.
<code>\dim_gset:cn</code>	

Updated: 2011-10-22

<code>\dim_set_eq:NN</code>	<code>\dim_set_eq:NN <dimension₁₂</code>
<code>\dim_set_eq:(cN Nc cc)</code>	
<code>\dim_gset_eq:NN</code>	Sets the content of $\langle dimension_1 \rangle$ equal to that of $\langle dimension_2 \rangle$.
<code>\dim_gset_eq:(cN Nc cc)</code>	

<code>\dim_sub:Nn</code>	<code>\dim_sub:Nn <dimension> {<dimension expression>}</code>
<code>\dim_sub:cn</code>	
<code>\dim_gsub:Nn</code>	Subtracts the result of the $\langle dimension expression \rangle$ from the current content of the $\langle dimension \rangle$.
<code>\dim_gsub:cn</code>	

Updated: 2011-10-22

3 Utilities for dimension calculations

<code>\dim_abs:n</code>	★	<code>\dim_abs:n {<dimexpr>}</code>
Updated: 2012-09-26		Converts the $\langle dimexpr \rangle$ to its absolute value, leaving the result in the input stream as a $\langle dimension denotation \rangle$.

<code>\dim_max:nn</code>	★	<code>\dim_max:nn {<dimexpr₁>} {<dimexpr₂>}</code>
<code>\dim_min:nn</code>	★	<code>\dim_min:nn {<dimexpr₁>} {<dimexpr₂>}</code>
New: 2012-09-09		Evaluates the two $\langle dimension expressions \rangle$ and leaves either the maximum or minimum value in the input stream as appropriate, as a $\langle dimension denotation \rangle$.
Updated: 2012-09-26		

`\dim_ratio:nn` ☆

Updated: 2011-10-22

`\dim_ratio:nn {⟨dimexpr1⟩} {⟨dimexpr2⟩}`

Parses the two *⟨dimension expressions⟩* and converts the ratio of the two to a form suitable for use inside a *⟨dimension expression⟩*. This ratio is then left in the input stream, allowing syntax such as

```
\dim_set:Nn \l_my_dim
{ 10 pt * \dim_ratio:nn { 5 pt } { 10 pt } }
```

The output of `\dim_ratio:nn` on full expansion is a ratio expression between two integers, with all distances converted to scaled points. Thus

```
\tl_set:Nx \l_my_tl { \dim_ratio:nn { 5 pt } { 10 pt } }
\tl_show:N \l_my_tl
```

displays 327680/655360 on the terminal.

4 Dimension expression conditionals

`\dim_compare_p:nNn` ★

`\dim_compare:nNnTF` ★

`\dim_compare_p:nNn {⟨dimexpr1⟩} <relation> {⟨dimexpr2⟩}`

`\dim_compare:nNnTF`

`{⟨dimexpr1⟩} <relation> {⟨dimexpr2⟩}`

`{⟨true code⟩} {⟨false code⟩}`

This function first evaluates each of the *⟨dimension expressions⟩* as described for `\dim_eval:n`. The two results are then compared using the *⟨relation⟩*:

Equal	=
Greater than	>
Less than	<

This function is less flexible than `\dim_compare:nTF` but around 5 times faster.

```

\dim_compare_p:n * \dim_compare_p:n
\dim_compare:nTF * {
    <dimexpr1> <relation1>
    ...
    <dimexprN> <relationN>
    <dimexprN+1>
}
\dim_compare:nTF
{
    <dimexpr1> <relation1>
    ...
    <dimexprN> <relationN>
    <dimexprN+1>
}
{{true code}} {{false code}}

```

Updated: 2013-01-13

This function evaluates the *<dimension expressions>* as described for `\dim_eval:n` and compares consecutive result using the corresponding *<relation>*, namely it compares *<dimexpr₁>* and *<dimexpr₂>* using the *<relation₁>*, then *<dimexpr₂>* and *<dimexpr₃>* using the *<relation₂>*, until finally comparing *<dimexpr_N>* and *<dimexpr_{N+1}>* using the *<relation_N>*. The test yields `true` if all comparisons are `true`. Each *<dimension expression>* is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is `false`, then no other *<dimension expression>* is evaluated and no other comparison is performed. The *<relations>* can be any of the following:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

This function is more flexible than `\dim_compare:nNnTF` but around 5 times slower.

<code>\dim_case:nn</code> ☆	<code>\dim_case:nnTF {⟨test dimension expression⟩}</code>
<code>\dim_case:nnTF</code> ☆	<code>{</code>
New: 2013-07-24	<code>{⟨dimexpr case₁⟩} {⟨code case₁⟩}</code>
	<code>{⟨dimexpr case₂⟩} {⟨code case₂⟩}</code>
	<code>...</code>
	<code>{⟨dimexpr case_n⟩} {⟨code case_n⟩}</code>
	<code>}</code>
	<code>{⟨true code⟩}</code>
	<code>{⟨false code⟩}</code>

This function evaluates the *⟨test dimension expression⟩* and compares this in turn to each of the *⟨dimension expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\dim_case:nn`, which does nothing if there is no match, is also available. For example

```

\dim_set:Nn \l_tmpa_dim { 5 pt }
\dim_case:nnF
{ 2 \l_tmpa_dim }
{
  { 5 pt }      { Small }
  { 4 pt + 6 pt } { Medium }
  { - 10 pt }   { Negative }
}
{ No idea! }

```

leaves “Medium” in the input stream.

5 Dimension expression loops

<code>\dim_do_until:nNnn</code> ☆	<code>\dim_do_until:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **false** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **true**.

<code>\dim_do_while:nNnn</code> ☆	<code>\dim_do_while:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **true** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **false**.

<code>\dim_until_do:nNnn</code> ☆	<code>\dim_until_do:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`, and then places the *⟨code⟩* in the input stream if the *⟨relation⟩* is **false**. After the *⟨code⟩* has been processed by T_EX the test is repeated, and a loop occurs until the test is **true**.

<hr/> <code>\dim_while_do:nNnn</code> ☆ <hr/>	<code>\dim_while_do:nNnn {<dimexpr₁>} <relation> {<dimexpr₂>} {<code>}</code>
	Evaluates the relationship between the two <i><dimension expressions></i> as described for <code>\dim_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .
<hr/> <code>\dim_do_until:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div> <hr/>	<code>\dim_do_until:nn {<dimension relation>} {<code>}</code>
	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> . If the test is false then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is true .
<hr/> <code>\dim_do_while:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div> <hr/>	<code>\dim_do_while:nn {<dimension relation>} {<code>}</code>
	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> . If the test is true then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is false .
<hr/> <code>\dim_until_do:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div> <hr/>	<code>\dim_until_do:nn {<dimension relation>} {<code>}</code>
	Evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\dim_while_do:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div> <hr/>	<code>\dim_while_do:nn {<dimension relation>} {<code>}</code>
	Evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .

6 Dimension step functions

<hr/> <code>\dim_step_function:nnnN</code> ☆ <hr/> <div>New: 2018-02-18</div> <hr/>	<code>\dim_step_function:nnnN {<initial value>} {<step>} {<final value>} <function></code>
	This function first evaluates the <i><initial value></i> , <i><step></i> and <i><final value></i> , all of which should be dimension expressions. The <i><function></i> is then placed in front of each <i><value></i> from the <i><initial value></i> to the <i><final value></i> in turn (using <i><step></i> between each <i><value></i>). The <i><step></i> must be non-zero. If the <i><step></i> is positive, the loop stops when the <i><value></i> becomes larger than the <i><final value></i> . If the <i><step></i> is negative, the loop stops when the <i><value></i> becomes smaller than the <i><final value></i> . The <i><function></i> should absorb one argument.
<hr/> <code>\dim_step_inline:nnnn</code> <hr/> <div>New: 2018-02-18</div> <hr/>	<code>\dim_step_inline:nnnn {<initial value>} {<step>} {<final value>} {<code>}</code>
	This function first evaluates the <i><initial value></i> , <i><step></i> and <i><final value></i> , all of which should be dimension expressions. Then for each <i><value></i> from the <i><initial value></i> to the <i><final value></i> in turn (using <i><step></i> between each <i><value></i>), the <i><code></i> is inserted into the input stream with #1 replaced by the current <i><value></i> . Thus the <i><code></i> should define a function of one argument (#1).

`\dim_step_variable:nnnNn`
 New: 2018-02-18

`\dim_step_variable:nnnNn`
`{\langle initial value \rangle}{\langle step \rangle}{\langle final value \rangle}{\langle tl var \rangle}{\langle code \rangle}`

This function first evaluates the $\langle initial value \rangle$, $\langle step \rangle$ and $\langle final value \rangle$, all of which should be dimension expressions. Then for each $\langle value \rangle$ from the $\langle initial value \rangle$ to the $\langle final value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream, with the $\langle tl var \rangle$ defined as the current $\langle value \rangle$. Thus the $\langle code \rangle$ should make use of the $\langle tl var \rangle$.

7 Using dim expressions and variables

`\dim_eval:n` ★
 Updated: 2011-10-22

`\dim_eval:n` $\{\langle dimension expression \rangle\}$

Evaluates the $\langle dimension expression \rangle$, expanding any dimensions and token list variables within the $\langle expression \rangle$ to their content (without requiring `\dim_use:N/\tl_use:N`) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a $\langle dimension denotation \rangle$ after two expansions. This is expressed in points (`pt`), and requires suitable termination if used in a TeX-style assignment as it is *not* an $\langle internal dimension \rangle$.

`\dim_sign:n` ★
 New: 2018-11-03

`\dim_sign:n` $\{\langle dimexpr \rangle\}$

Evaluates the $\langle dimexpr \rangle$ then leaves 1 or 0 or -1 in the input stream according to the sign of the result.

`\dim_use:N` ★
`\dim_use:c` ★

`\dim_use:N` $\langle dimension \rangle$

Recovers the content of a $\langle dimension \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a $\langle dimension \rangle$ is required (such as in the argument of `\dim_eval:n`).

TeXhackers note: `\dim_use:N` is the TeX primitive `\the`: this is one of several L^ATeX3 names for this primitive.

`\dim_to_decimal:n` ★
 New: 2014-07-15

`\dim_to_decimal:n` $\{\langle dimexpr \rangle\}$

Evaluates the $\langle dimension expression \rangle$, and leaves the result, expressed in points (`pt`) in the input stream, with *no units*. The result is rounded by TeX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal:n { 1bp }`

leaves 1.00374 in the input stream, *i.e.* the magnitude of one “big point” when converted to (TeX) points.

<hr/> <code>\dim_to_decimal_in_bp:n</code> ★ <hr/>	<code>\dim_to_decimal_in_bp:n {⟨dimexpr⟩}</code>
<hr/> New: 2014-07-15 <hr/>	Evaluates the <i>⟨dimension expression⟩</i> , and leaves the result, expressed in big points (bp) in the input stream, with <i>no units</i> . The result is rounded by T _E X to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

```
\dim_to_decimal_in_bp:n { 1pt }
```

leaves 0.99628 in the input stream, *i.e.* the magnitude of one (T_EX) point when converted to big points.

<hr/> <code>\dim_to_decimal_in_sp:n</code> ★ <hr/>	<code>\dim_to_decimal_in_sp:n {⟨dimexpr⟩}</code>
<hr/> New: 2015-05-18 <hr/>	Evaluates the <i>⟨dimension expression⟩</i> , and leaves the result, expressed in scaled points (sp) in the input stream, with <i>no units</i> . The result is necessarily an integer.

<hr/> <code>\dim_to_decimal_in_unit:nn</code> ★ <hr/>	<code>\dim_to_decimal_in_unit:nn {⟨dimexpr₁⟩} {⟨dimexpr₂⟩}</code>
<hr/> New: 2014-07-15 <hr/>	

Evaluates the *⟨dimension expressions⟩*, and leaves the value of *⟨dimexpr₁⟩*, expressed in a unit given by *⟨dimexpr₂⟩*, in the input stream. The result is a decimal number, rounded by T_EX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

```
\dim_to_decimal_in_unit:nn { 1bp } { 1mm }
```

leaves 0.35277 in the input stream, *i.e.* the magnitude of one big point when converted to millimetres.

Note that this function is not optimised for any particular output and as such may give different results to `\dim_to_decimal_in_bp:n` or `\dim_to_decimal_in_sp:n`. In particular, the latter is able to take a wider range of input values as it is not limited by the ability to calculate a ratio using ε -T_EX primitives, which is required internally by `\dim_to_decimal_in_unit:nn`.

<hr/> <code>\dim_to_fp:n</code> ★ <hr/>	<code>\dim_to_fp:n {⟨dimexpr⟩}</code>
<hr/> New: 2012-05-08 <hr/>	Expands to an internal floating point number equal to the value of the <i>⟨dimexpr⟩</i> in pt. Since dimension expressions are evaluated much faster than their floating point equivalent, <code>\dim_to_fp:n</code> can be used to speed up parts of a computation where a low precision and a smaller range are acceptable.

8 Viewing dim variables

<hr/> <code>\dim_show:N</code> <hr/>	<code>\dim_show:N ⟨dimension⟩</code>
<code>\dim_show:c</code>	Displays the value of the <i>⟨dimension⟩</i> on the terminal.

<hr/> <code>\dim_show:n</code> <hr/>	<code>\dim_show:n {⟨<i>dimension expression</i>⟩}</code>
New: 2011-11-22 Updated: 2015-08-07	Displays the result of evaluating the $\langle dimension\ expression \rangle$ on the terminal.
<hr/> <code>\dim_log:N</code> <code>\dim_log:c</code> <hr/>	<code>\dim_log:N ⟨<i>dimension</i>⟩</code>
New: 2014-08-22 Updated: 2015-08-03	Writes the value of the $\langle dimension \rangle$ in the log file.
<hr/> <code>\dim_log:n</code> <hr/>	<code>\dim_log:n {⟨<i>dimension expression</i>⟩}</code>
New: 2014-08-22 Updated: 2015-08-07	Writes the result of evaluating the $\langle dimension\ expression \rangle$ in the log file.

9 Constant dimensions

<hr/> <code>\c_max_dim</code> <hr/>	The maximum value that can be stored as a dimension. This can also be used as a component of a skip.
<hr/> <code>\c_zero_dim</code> <hr/>	A zero length as a dimension. This can also be used as a component of a skip.

10 Scratch dimensions

<hr/> <code>\l_tmpa_dim</code> <code>\l_tmpb_dim</code> <hr/>	Scratch dimension for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_dim</code> <code>\g_tmpb_dim</code> <hr/>	Scratch dimension for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

11 Creating and initialising skip variables

<hr/> <code>\skip_new:N</code> <code>\skip_new:c</code> <hr/>	<code>\skip_new:N ⟨<i>skip</i>⟩</code>
	Creates a new $\langle skip \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle skip \rangle$ is initially equal to 0 pt.

<code>\skip_const:Nn</code>	<code>\skip_const:Nn <skip> {<skip expression>}</code>
<code>\skip_const:cn</code>	Creates a new constant <i><skip></i> or raises an error if the name is already taken. The value of the <i><skip></i> is set globally to the <i><skip expression></i> .
New: 2012-03-05	

<code>\skip_zero:N</code>	<code>\skip_zero:N <skip></code>
<code>\skip_zero:c</code>	Sets <i><skip></i> to 0 pt.
<code>\skip_gzero:N</code>	
<code>\skip_gzero:c</code>	

<code>\skip_zero_new:N</code>	<code>\skip_zero_new:N</code> $\langle skip \rangle$
<code>\skip_zero_new:c</code>	Ensures that the $\langle skip \rangle$ exists globally by applying <code>\skip_new:N</code> if necessary, then applies <code>\skip_(g)zero:N</code> to leave the $\langle skip \rangle$ set to zero.
<code>\skip_gzero_new:N</code>	
<code>\skip_gzero_new:c</code>	
<hr/>	
New: 2012-01-07	

<code>\skip_if_exist_p:N *</code>	<code>\skip_if_exist_p:N <skip></code>
<code>\skip_if_exist_p:c *</code>	<code>\skip_if_exist:NTF <skip> {<true code>} {<false code>}</code>
<code>\skip_if_exist:NTF *</code>	Tests whether the <code><skip></code> is currently defined. This does not check that the <code><skip></code> really is a skip variable.
<code>\skip_if_exist:cTF *</code>	
<hr/> New: 2012-03-03	

12 Setting skip variables

<code>\skip_add:Nn</code>	<code>\skip_add:Nn <skip> {<skip expression>}</code>
<code>\skip_add:cn</code>	Adds the result of the <i><skip expression></i> to the current content of the <i><skip></i> .
<code>\skip_gadd:Nn</code>	
<code>\skip_gadd:cn</code>	

Updated: 2011-10-22

<code>\skip_set:Nn</code>	<code>\skip_set:Nn <skip> {<skip expression>}</code>
<code>\skip_set:cn</code>	Sets <code><skip></code> to the value of <code><skip expression></code> , which must evaluate to a length with units and may include a rubber component (for example 1 cm plus 0.5 cm).
<code>\skip_gset:Nn</code>	
<code>\skip_gset:cn</code>	
Updated: 2011-10-22	

<code>\skip_set_eq:NN</code>	<code>\skip_set_eq:NN <skip₁₂</code>
<code>\skip_set_eq:(cN Nc cc)</code>	Sets the content of <i><skip_{1 equal to that of <i><skip_{2.}</i>}</i>
<code>\skip_gset_eq:NN</code>	
<code>\skip_gset_eq:(cN Nc cc)</code>	

<code>\skip_sub:Nn</code>	<code>\skip_sub:Nn <skip> {<skip expression>}</code>
<code>\skip_sub:cn</code>	Subtracts the result of the <i><skip expression></i> from the current content of the <i><skip></i> .
<code>\skip_gsub:Nn</code>	
<code>\skip_gsub:cn</code>	
<hr/>	
Updated: 2011-10-22	

13 Skip expression conditionals

<code>\skip_if_eq_p:nn</code> *	<code>\skip_if_eq_p:nn {\langle skipexpr_1 \rangle} {\langle skipexpr_2 \rangle}</code>
<code>\skip_if_eq:nnTF</code> *	<code>\skip_if_eq:nnTF</code> <code> {\langle skipexpr_1 \rangle} {\langle skipexpr_2 \rangle}</code> <code> {\langle true code \rangle} {\langle false code \rangle}</code>

This function first evaluates each of the $\langle skip\ expressions \rangle$ as described for `\skip_eval:n`. The two results are then compared for exact equality, *i.e.* both the fixed and rubber components must be the same for the test to be true.

<code>\skip_if_finite_p:n</code> *	<code>\skip_if_finite_p:n {\langle skipexpr \rangle}</code>
<code>\skip_if_finite:nTF</code> *	<code>\skip_if_finite:nTF {\langle skipexpr \rangle} {\langle true code \rangle} {\langle false code \rangle}</code>

New: 2012-03-05

Evaluates the $\langle skip\ expression \rangle$ as described for `\skip_eval:n`, and then tests if all of its components are finite.

14 Using skip expressions and variables

<code>\skip_eval:n</code> *	<code>\skip_eval:n {\langle skip expression \rangle}</code>
-----------------------------	---

Updated: 2011-10-22

Evaluates the $\langle skip\ expression \rangle$, expanding any skips and token list variables within the $\langle expression \rangle$ to their content (without requiring `\skip_use:N/\tl_use:N`) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a $\langle glue\ denotation \rangle$ after two expansions. This is expressed in points (`pt`), and requires suitable termination if used in a \TeX -style assignment as it is *not* an $\langle internal\ glue \rangle$.

<code>\skip_use:N</code> *	<code>\skip_use:N \langle skip \rangle</code>
<code>\skip_use:c</code> *	

Recovers the content of a $\langle skip \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a $\langle dimension \rangle$ or $\langle skip \rangle$ is required (such as in the argument of `\skip_eval:n`).

\TeX hackers note: `\skip_use:N` is the \TeX primitive `\the`: this is one of several \LaTeX 3 names for this primitive.

15 Viewing skip variables

<code>\skip_show:N</code>	<code>\skip_show:N \langle skip \rangle</code>
<code>\skip_show:c</code>	

Updated: 2015-08-03

Displays the value of the $\langle skip \rangle$ on the terminal.

<code>\skip_show:n</code>	<code>\skip_show:n {\langle skip expression \rangle}</code>
---------------------------	---

New: 2011-11-22
Updated: 2015-08-07

Displays the result of evaluating the $\langle skip\ expression \rangle$ on the terminal.

<code>\skip_log:N</code>	<code>\skip_log:N <skip></code>
<code>\skip_log:c</code>	Writes the value of the <code><skip></code> in the log file.
New: 2014-08-22	
Updated: 2015-08-03	

<code>\skip_log:n</code>	<code>\skip_log:n {\<skip expression>}</code>
	Writes the result of evaluating the <code><skip expression></code> in the log file.
New: 2014-08-22	
Updated: 2015-08-07	

16 Constant skips

<code>\c_max_skip</code>	The maximum value that can be stored as a skip (equal to <code>\c_max_dim</code> in length), with no stretch nor shrink component.
Updated: 2012-11-02	

<code>\c_zero_skip</code>	A zero length as a skip, with no stretch nor shrink component.
Updated: 2012-11-01	

17 Scratch skips

<code>\l_tmpa_skip</code> <code>\l_tmpb_skip</code>	Scratch skip for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

<code>\g_tmpa_skip</code> <code>\g_tmpb_skip</code>	Scratch skip for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

18 Inserting skips into the output

<code>\skip_horizontal:N</code>	<code>\skip_horizontal:N <skip></code>
<code>\skip_horizontal:c</code>	<code>\skip_horizontal:n {\<skipexpr>}</code>
<code>\skip_horizontal:n</code>	Inserts a horizontal <code><skip></code> into the current list. The argument can also be a <code><dim></code> .
Updated: 2011-10-22	

T_EXhackers note: `\skip_horizontal:N` is the T_EX primitive `\hskip` renamed.

<hr/> <code>\skip_vertical:N</code>	<code>\skip_vertical:N <skip></code>
<code>\skip_vertical:c</code>	<code>\skip_vertical:n {<skipexpr>}</code>
<code>\skip_vertical:n</code>	Inserts a vertical <code><skip></code> into the current list. The argument can also be a <code><dim></code> .
<hr/> Updated: 2011-10-22 <hr/>	

T_EXhackers note: `\skip_vertical:N` is the T_EX primitive `\vskip` renamed.

19 Creating and initialising muskip variables

<hr/> <code>\muskip_new:N</code>	<code>\muskip_new:N <muskip></code>
<code>\muskip_new:c</code>	Creates a new <code><muskip></code> or raises an error if the name is already taken. The declaration is global. The <code><muskip></code> is initially equal to 0 mu.

<hr/> <code>\muskip_const:Nn</code>	<code>\muskip_const:Nn <muskip> {<muskip expression>}</code>
<code>\muskip_const:cn</code>	Creates a new constant <code><muskip></code> or raises an error if the name is already taken. The value of the <code><muskip></code> is set globally to the <code><muskip expression></code> .
<hr/> New: 2012-03-05 <hr/>	

<hr/> <code>\muskip_zero:N</code>	<code>\skip_zero:N <muskip></code>
<code>\muskip_zero:c</code>	Sets <code><muskip></code> to 0 mu.
<code>\muskip_gzero:N</code>	
<code>\muskip_gzero:c</code>	

<code>\muskip_zero_new:N</code>	<code>\muskip_zero_new:N <muskip></code>
<code>\muskip_zero_new:c</code>	Ensures that the <code><muskip></code> exists globally by applying <code>\muskip_new:N</code> if necessary, then applies <code>\muskip_(g)zero:N</code> to leave the <code><muskip></code> set to zero.
<code>\muskip_gzero_new:N</code>	
<code>\muskip_gzero_new:c</code>	
<hr/>	
New: 2012-01-07	

<hr/> <code>\muskip_if_exist_p:N</code> *	<code>\muskip_if_exist_p:N <muskip></code>
<code>\muskip_if_exist_p:c</code> *	<code>\muskip_if_exist:NTF <muskip> {\langle true code \rangle} {\langle false code \rangle}</code>
<code>\muskip_if_exist:NTF</code> *	Tests whether the $\langle muskip \rangle$ is currently defined. This does not check that the $\langle muskip \rangle$ really is a muskip variable.
<code>\muskip_if_exist:cTF</code> *	
<hr/> New: 2012-03-03 <hr/>	

20 Setting muskip variables

<code>\muskip_add:Nn</code>	<code>\muskip_add:Nn <muskip> {<muskip expression>}</code>
<code>\muskip_add:cn</code>	Adds the result of the <i><muskip expression></i> to the current content of the <i><muskip></i> .
<code>\muskip_gadd:Nn</code>	
<code>\muskip_gadd:cn</code>	
<hr/>	
Updated: 2011-10-22	

<hr/> <code>\muskip_set:Nn</code>	<code>\muskip_set:Nn <muskip> {<muskip expression>}</code>
<code>\muskip_set:cn</code>	
<code>\muskip_gset:Nn</code>	Sets <i><muskip></i> to the value of <i><muskip expression></i> , which must evaluate to a math length with units and may include a rubber component (for example 1 mu plus 0.5 mu).
<code>\muskip_gset:cn</code>	
<hr/> Updated: 2011-10-22 <hr/>	

<hr/> <code>\muskip_set_eq:NN</code>	<code>\muskip_set_eq:NN <muskip₁> <muskip₂></code>
<code>\muskip_set_eq:(cN Nc cc)</code>	
<code>\muskip_gset_eq:NN</code>	Sets the content of <i><muskip₁></i> equal to that of <i><muskip₂></i> .
<code>\muskip_gset_eq:(cN Nc cc)</code>	

<hr/> <code>\muskip_sub:Nn</code>	<code>\muskip_sub:Nn <muskip> {<muskip expression>}</code>
<code>\muskip_sub:cn</code>	
<code>\muskip_gsub:Nn</code>	Subtracts the result of the <i><muskip expression></i> from the current content of the <i><muskip></i> .
<code>\muskip_gsub:cn</code>	
<hr/> Updated: 2011-10-22 <hr/>	

21 Using muskip expressions and variables

<hr/> <code>\muskip_eval:n *</code>	<code>\muskip_eval:n {<muskip expression>}</code>
<hr/> Updated: 2011-10-22 <hr/>	
	Evaluates the <i><muskip expression></i> , expanding any skips and token list variables within the <i><expression></i> to their content (without requiring <code>\muskip_use:N/\tl_use:N</code>) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a <i><mu glue denotation></i> after two expansions. This is expressed in mu , and requires suitable termination if used in a T _E X-style assignment as it is <i>not</i> an <i><internal mu glue></i> .

<hr/> <code>\muskip_use:N *</code>	<code>\muskip_use:N <muskip></code>
<code>\muskip_use:c *</code>	
	Recovers the content of a <i><skip></i> and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a <i><dimension></i> is required (such as in the argument of <code>\muskip_eval:n</code>).

T_EXhackers note: `\muskip_use:N` is the T_EX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

22 Viewing muskip variables

<hr/> <code>\muskip_show:N</code>	<code>\muskip_show:N <muskip></code>
<code>\muskip_show:c</code>	
	Displays the value of the <i><muskip></i> on the terminal.
<hr/> Updated: 2015-08-03 <hr/>	

<hr/> <code>\muskip_show:n</code> <hr/>	<code>\muskip_show:n {⟨<i>muskip expression</i>⟩}</code>
New: 2011-11-22 Updated: 2015-08-07	Displays the result of evaluating the $\langle muskip expression \rangle$ on the terminal.
<hr/> <code>\muskip_log:N</code> <code>\muskip_log:c</code> <hr/>	<code>\muskip_log:N ⟨<i>muskip</i>⟩</code>
New: 2014-08-22 Updated: 2015-08-03	Writes the value of the $\langle muskip \rangle$ in the log file.
<hr/> <code>\muskip_log:n</code> <hr/>	<code>\muskip_log:n {⟨<i>muskip expression</i>⟩}</code>
New: 2014-08-22 Updated: 2015-08-07	Writes the result of evaluating the $\langle muskip expression \rangle$ in the log file.

23 Constant muskips

<hr/> <code>\c_max_muskip</code> <hr/>	The maximum value that can be stored as a muskip, with no stretch nor shrink component.
<hr/> <code>\c_zero_muskip</code> <hr/>	A zero length as a muskip, with no stretch nor shrink component.

24 Scratch muskips

<hr/> <code>\l_tmpa_muskip</code> <code>\l_tmpb_muskip</code> <hr/>	Scratch muskip for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_muskip</code> <code>\g_tmpb_muskip</code> <hr/>	Scratch muskip for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

25 Primitive conditional

<hr/> <code>\if_dim:w ★</code> <hr/>	<code>\if_dim:w ⟨<i>dimen</i>₁⟩ ⟨<i>relation</i>⟩ ⟨<i>dimen</i>₂⟩</code> <code> ⟨<i>true code</i>⟩</code> <code> \else:</code> <code> ⟨<i>false</i>⟩</code> <code> \fi:</code>
	Compare two dimensions. The $\langle relation \rangle$ is one of $<$, $=$ or $>$ with category code 12.

T_EXhackers note: This is the T_EX primitive `\ifdim`.

Part XXI

The l3keys package

Key–value interfaces

The key–value method is a popular system for creating large numbers of settings for controlling function or package behaviour. The system normally results in input of the form

```
\MyModuleSetup{
  key-one = value one,
  key-two = value two
}
```

or

```
\MyModuleMacro[
  key-one = value one,
  key-two = value two
]{argument}
```

for the user.

The high level functions here are intended as a method to create key–value controls. Keys are themselves created using a key–value interface, minimising the number of functions and arguments required. Each key is created by setting one or more *properties* of the key:

```
\keys_define:nn { mymodule }
{
  key-one .code:n = code including parameter #1,
  key-two .tl_set:N = \l_mymodule_store_tl
}
```

These values can then be set as with other key–value approaches:

```
\keys_set:nn { mymodule }
{
  key-one = value one,
  key-two = value two
}
```

At a document level, `\keys_set:nn` is used within a document function, for example

```
\DeclareDocumentCommand \MyModuleSetup { m }
{ \keys_set:nn { mymodule } { #1 } }
\DeclareDocumentCommand \MyModuleMacro { o m }
{
  \group_begin:
    \keys_set:nn { mymodule } { #1 }
    % Main code for \MyModuleMacro
  \group_end:
}
```

Key names may contain any tokens, as they are handled internally using `\tl_to_str:n`. As discussed in section 2, it is suggested that the character `/` is reserved for sub-division of keys into logical groups. Functions and variables are *not* expanded when creating key names, and so

```
\tl_set:Nn \l_mymodule_tmp_tl { key }
\keys_define:nn { mymodule }
{
  \l_mymodule_tmp_tl .code:n = code
}
```

creates a key called `\l_mymodule_tmp_tl`, and not one called `key`.

1 Creating keys

`\keys_define:nn`

Updated: 2017-11-14

`\keys_define:nn {<module>} {<keyval list>}`

Parses the *<keyval list>* and defines the keys listed there for *<module>*. The *<module>* name is treated as a string. In practice the *<module>* should be chosen to be unique to the module in question (unless deliberately adding keys to an existing module).

The *<keyval list>* should consist of one or more key names along with an associated key *property*. The properties of a key determine how it acts. The individual properties are described in the following text; a typical use of `\keys_define:nn` might read

```
\keys_define:nn { mymodule }
{
  keyname .code:n = Some~code~using~#1,
  keyname .value_required:n = true
}
```

where the properties of the key begin from the `.` after the key name.

The various properties available take either no arguments at all, or require one or more arguments. This is indicated in the name of the property using an argument specification. In the following discussion, each property is illustrated attached to an arbitrary *<key>*, which when used may be supplied with a *<value>*. All key *definitions* are local.

Key properties are applied in the reading order and so the ordering is significant. Key properties which define “actions”, such as `.code:n`, `.tl_set:N`, *etc.*, override one another. Some other properties are mutually exclusive, notably `.value_required:n` and `.value_forbidden:n`, and so they replace one another. However, properties covering non-exclusive behaviours may be given in any order. Thus for example the following definitions are equivalent.

```
\keys_define:nn { mymodule }
{
  keyname .code:n          = Some~code~using~#1,
  keyname .value_required:n = true
}
\keys_define:nn { mymodule }
{
```



```

    keyname .value_required:n = true,
    keyname .code:n           = Some~code~using~#1
}

```

Note that with the exception of the special `.undefine:` property, all key properties define the key within the current \TeX scope.

```

.bool_set:N
.bool_set:c
.bool_gset:N
.bool_gset:c

```

Updated: 2013-07-08

$\langle key \rangle$ `.bool_set:N` = $\langle boolean \rangle$

Defines $\langle key \rangle$ to set $\langle boolean \rangle$ to $\langle value \rangle$ (which must be either `true` or `false`). If the variable does not exist, it will be created globally at the point that the key is set up.

```

.bool_set_inverse:N
.bool_set_inverse:c
.bool_gset_inverse:N
.bool_gset_inverse:c

```

New: 2011-08-28
Updated: 2013-07-08

$\langle key \rangle$ `.bool_set_inverse:N` = $\langle boolean \rangle$

Defines $\langle key \rangle$ to set $\langle boolean \rangle$ to the logical inverse of $\langle value \rangle$ (which must be either `true` or `false`). If the $\langle boolean \rangle$ does not exist, it will be created globally at the point that the key is set up.

`.choice:`

$\langle key \rangle$ `.choice:`

Sets $\langle key \rangle$ to act as a choice key. Each valid choice for $\langle key \rangle$ must then be created, as discussed in section 3.

```

.choices:nn
.choices:(Vn|on|xn)

```

New: 2011-08-21
Updated: 2013-07-10

$\langle key \rangle$ `.choices:nn` = $\{\langle choices \rangle\} \{\langle code \rangle\}$

Sets $\langle key \rangle$ to act as a choice key, and defines a series $\langle choices \rangle$ which are implemented using the $\langle code \rangle$. Inside $\langle code \rangle$, `\l_keys_choice_tl` will be the name of the choice made, and `\l_keys_choice_int` will be the position of the choice in the list of $\langle choices \rangle$ (indexed from 1). Choices are discussed in detail in section 3.

```

.clist_set:N
.clist_set:c
.clist_gset:N
.clist_gset:c

```

New: 2011-09-11

$\langle key \rangle$ `.clist_set:N` = $\langle comma list variable \rangle$

Defines $\langle key \rangle$ to set $\langle comma list variable \rangle$ to $\langle value \rangle$. Spaces around commas and empty items will be stripped. If the variable does not exist, it is created globally at the point that the key is set up.

```

.code:n

```

Updated: 2013-07-10

$\langle key \rangle$ `.code:n` = $\{\langle code \rangle\}$

Stores the $\langle code \rangle$ for execution when $\langle key \rangle$ is used. The $\langle code \rangle$ can include one parameter (`#1`), which will be the $\langle value \rangle$ given for the $\langle key \rangle$.

```

.cs_set:Np
.cs_set:cp
.cs_set_protected:Np
.cs_set_protected:cp
.cs_gset:Np
.cs_gset:cp
.cs_gset_protected:Np
.cs_gset_protected:cp

```

New: 2020-01-11

$\langle key \rangle$ `.cs_set:Np` = $\langle control sequence \rangle \langle arg. spec. \rangle$

Defines $\langle key \rangle$ to set $\langle control sequence \rangle$ to have $\langle arg. spec. \rangle$ and replacement text $\langle value \rangle$.

```
.default:n
.default:(V|o|x)
Updated: 2013-07-09
```

`<key> .default:n = {<default>}`

Creates a *<default>* value for *<key>*, which is used if no value is given. This will be used if only the key name is given, but not if a blank *<value>* is given:

```
\keys_define:nn { mymodule }
{
    key .code:n      = Hello~#1,
    key .default:n = World
}
\keys_set:nn { mymodule }
{
    key = Fred, % Prints 'Hello Fred'
    key,      % Prints 'Hello World'
    key = ,    % Prints 'Hello '
}
```

The default does not affect keys where values are required or forbidden. Thus a required value cannot be supplied by a default value, and giving a default value for a key which cannot take a value does not trigger an error.

```
.dim_set:N
.dim_set:c
.dim_gset:N
.dim_gset:c
Updated: 2020-01-17
```

`<key> .dim_set:N = <dimension>`

Defines *<key>* to set *<dimension>* to *<value>* (which must a dimension expression). If the variable does not exist, it is created globally at the point that the key is set up. The key will require a value at point-of-use unless a default is set.

```
.fp_set:N
.fp_set:c
.fp_gset:N
.fp_gset:c
Updated: 2020-01-17
```

`<key> .fp_set:N = <floating point>`

Defines *<key>* to set *<floating point>* to *<value>* (which must a floating point expression). If the variable does not exist, it is created globally at the point that the key is set up. The key will require a value at point-of-use unless a default is set.

```
.groups:n
New: 2013-07-14
```

`<key> .groups:n = {<groups>}`

Defines *<key>* as belonging to the *<groups>* declared. Groups provide a “secondary axis” for selectively setting keys, and are described in Section 6.

```
.inherit:n
New: 2016-11-22
```

`<key> .inherit:n = {<parents>}`

Specifies that the *<key>* path should inherit the keys listed as *<parents>*. For example, after setting

```
\keys_define:nn { foo } { test .code:n = \tl_show:n {#1} }
\keys_define:nn { } { bar .inherit:n = foo }
```

setting

```
\keys_set:nn { bar } { test = a }
```

will be equivalent to

```
\keys_set:nn { foo } { test = a }
```

<hr/> <code>.initial:n</code> <hr/>	<code><key> .initial:n = {<value>}</code>
<code>.initial:(V o x)</code>	Initialises the <code><key></code> with the <code><value></code> , equivalent to
<hr/> Updated: 2013-07-09 <hr/>	<code>\keys_set:nn {<module>} { <key> = <value> }</code>
<hr/> <code>.int_set:N</code> <hr/>	<code><key> .int_set:N = <integer></code>
<code>.int_set:c</code>	Defines <code><key></code> to set <code><integer></code> to <code><value></code> (which must be an integer expression). If the
<code>.int_gset:N</code>	variable does not exist, it is created globally at the point that the key is set up. The key
<code>.int_gset:c</code>	will require a value at point-of-use unless a default is set.
<hr/> Updated: 2020-01-17 <hr/>	
<hr/> <code>.meta:n</code> <hr/>	<code><key> .meta:n = {<keyval list>}</code>
<hr/> Updated: 2013-07-10 <hr/>	Makes <code><key></code> a meta-key, which will set <code><keyval list></code> in one go. The <code><keyval list></code> can refer
	as <code>#1</code> to the value given at the time the <code><key></code> is used (or, if no value is given, the <code><key></code> 's
	default value).
<hr/> <code>.meta:nn</code> <hr/>	<code><key> .meta:nn = {<path>} {<keyval list>}</code>
<hr/> New: 2013-07-10 <hr/>	Makes <code><key></code> a meta-key, which will set <code><keyval list></code> in one go using the <code><path></code> in place of
	the current one. The <code><keyval list></code> can refer as <code>#1</code> to the value given at the time the <code><key></code>
	is used (or, if no value is given, the <code><key></code> 's default value).
<hr/> <code>.multichoice:</code> <hr/>	<code><key> .multichoice:</code>
<hr/> New: 2011-08-21 <hr/>	Sets <code><key></code> to act as a multiple choice key. Each valid choice for <code><key></code> must then be
	created, as discussed in section 3.
<hr/> <code>.multichoices:nn</code> <hr/>	<code><key> .multichoices:nn {<choices>} {<code>}</code>
<code>.multichoices:(Vn on xn)</code>	Sets <code><key></code> to act as a multiple choice key, and defines a series <code><choices></code> which are im-
<hr/> New: 2011-08-21 <hr/>	plemented using the <code><code></code> . Inside <code><code></code> , <code>\l_keys_choice_tl</code> will be the name of the
<hr/> Updated: 2013-07-10 <hr/>	choice made, and <code>\l_keys_choice_int</code> will be the position of the choice in the list of
	<code><choices></code> (indexed from 1). Choices are discussed in detail in section 3.
<hr/> <code>.muskip_set:N</code> <hr/>	<code><key> .muskip_set:N = <muskip></code>
<code>.muskip_set:c</code>	Defines <code><key></code> to set <code><muskip></code> to <code><value></code> (which must be a muskip expression). If the
<code>.muskip_gset:N</code>	variable does not exist, it is created globally at the point that the key is set up. The key
<code>.muskip_gset:c</code>	will require a value at point-of-use unless a default is set.
<hr/> New: 2019-05-05 <hr/>	
<hr/> Updated: 2020-01-17 <hr/>	
<hr/> <code>.prop_put:N</code> <hr/>	<code><key> .prop_put:N = <property list></code>
<code>.prop_put:c</code>	Defines <code><key></code> to put the <code><value></code> onto the <code><property list></code> stored under the <code><key></code> . If the
<code>.prop_gput:N</code>	variable does not exist, it is created globally at the point that the key is set up.
<code>.prop_gput:c</code>	
<hr/> New: 2019-01-31 <hr/>	

`.skip_set:N` $\langle key \rangle$ `.skip_set:N = $\langle skip \rangle$`

`.skip_set:c`
`.skip_gset:N`
`.skip_gset:c`
Defines $\langle key \rangle$ to set $\langle skip \rangle$ to $\langle value \rangle$ (which must be a skip expression). If the variable does not exist, it is created globally at the point that the key is set up. The key will require a value at point-of-use unless a default is set.

Updated: 2020-01-17

`.tl_set:N` $\langle key \rangle$ `.tl_set:N = $\langle token list variable \rangle$`

`.tl_set:c`
`.tl_gset:N`
`.tl_gset:c`
Defines $\langle key \rangle$ to set $\langle token list variable \rangle$ to $\langle value \rangle$. If the variable does not exist, it is created globally at the point that the key is set up.

`.tl_set_x:N` $\langle key \rangle$ `.tl_set_x:N = $\langle token list variable \rangle$`

`.tl_set_x:c`
`.tl_gset_x:N`
`.tl_gset_x:c`
Defines $\langle key \rangle$ to set $\langle token list variable \rangle$ to $\langle value \rangle$, which will be subjected to an x-type expansion (*i.e.* using `\tl_set:Nx`). If the variable does not exist, it is created globally at the point that the key is set up.

`.undefine:` $\langle key \rangle$ `.undefine:`

New: 2015-07-14 Removes the definition of the $\langle key \rangle$ within the current scope.

`.value_forbidden:n` $\langle key \rangle$ `.value_forbidden:n = true|false`

New: 2015-07-14 Specifies that $\langle key \rangle$ cannot receive a $\langle value \rangle$ when used. If a $\langle value \rangle$ is given then an error will be issued. Setting the property `false` cancels the restriction.

`.value_required:n` $\langle key \rangle$ `.value_required:n = true|false`

New: 2015-07-14 Specifies that $\langle key \rangle$ must receive a $\langle value \rangle$ when used. If a $\langle value \rangle$ is not given then an error will be issued. Setting the property `false` cancels the restriction.

2 Sub-dividing keys

When creating large numbers of keys, it may be desirable to divide them into several sub-groups for a given module. This can be achieved either by adding a sub-division to the module name:

```
\keys_define:nn { mymodule / subgroup }
  { key .code:n = code }
```

or to the key name:

```
\keys_define:nn { mymodule }
  { subgroup / key .code:n = code }
```

As illustrated, the best choice of token for sub-dividing keys in this way is `/`. This is because of the method that is used to represent keys internally. Both of the above code fragments set the same key, which has full name `mymodule/subgroup/key`.

As illustrated in the next section, this subdivision is particularly relevant to making multiple choices.

3 Choice and multiple choice keys

The `l3keys` system supports two types of choice key, in which a series of pre-defined input values are linked to varying implementations. Choice keys are usually created so that the various values are mutually-exclusive: only one can apply at any one time. “Multiple” choice keys are also supported: these allow a selection of values to be chosen at the same time.

Mutually-exclusive choices are created by setting the `.choice:` property:

```
\keys_define:nn { mymodule }
  { key .choice: }
```

For keys which are set up as choices, the valid choices are generated by creating sub-keys of the choice key. This can be carried out in two ways.

In many cases, choices execute similar code which is dependant only on the name of the choice or the position of the choice in the list of all possibilities. Here, the keys can share the same code, and can be rapidly created using the `.choices:nn` property.

```
\keys_define:nn { mymodule }
{
  key .choices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~\int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}
```

The index `\l_keys_choice_int` in the list of choices starts at 1.

`\l_keys_choice_int`
`\l_keys_choice_tl`

Inside the code block for a choice generated using `.choices:nn`, the variables `\l_keys_choice_tl` and `\l_keys_choice_int` are available to indicate the name of the current choice, and its position in the comma list. The position is indexed from 1. Note that, as with standard key code generated using `.code:n`, the value passed to the key (i.e. the choice name) is also available as `#1`.

On the other hand, it is sometimes useful to create choices which use entirely different code from one another. This can be achieved by setting the `.choice:` property of a key, then manually defining sub-keys.

```
\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}
```

It is possible to mix the two methods, but manually-created choices should *not* use `\l_keys_choice_tl` or `\l_keys_choice_int`. These variables do not have defined

behaviour when used outside of code created using `.choices:nn` (*i.e.* anything might happen).

It is possible to allow choice keys to take values which have not previously been defined by adding code for the special `unknown` choice. The general behavior of the `unknown` key is described in Section 5. A typical example in the case of a choice would be to issue a custom error message:

```
\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
  key / unknown .code:n =
    \msg_error:nnxxx { mymodule } { unknown-choice }
    { key } % Name of choice key
    { choice-a , choice-b , choice-c } % Valid choices
    { \exp_not:n {#1} } % Invalid choice given
  %
  %
}
```

Multiple choices are created in a very similar manner to mutually-exclusive choices, using the properties `.multichoice:` and `.multichoices:nn`. As with mutually exclusive choices, multiple choices are define as sub-keys. Thus both

```
\keys_define:nn { mymodule }
{
  key .multichoices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~
      \int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}
```

and

```
\keys_define:nn { mymodule }
{
  key .multichoice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}
```

are valid.

When a multiple choice key is set

```
\keys_set:nn { mymodule }
{
  key = { a , b , c } % 'key' defined as a multiple choice
}
```

each choice is applied in turn, equivalent to a `clist` mapping or to applying each value individually:

```
\keys_set:nn { mymodule }
{
  key = a ,
  key = b ,
  key = c ,
}
```

Thus each separate choice will have passed to it the `\l_keys_choice_tl` and `\l_keys_choice_int` in exactly the same way as described for `.choices:nn`.

4 Setting keys

```
\keys_set:nn
\keys_set:(nV|nv|no)
```

Updated: 2017-11-14

```
\keys_set:nn {<module>} {<keyval list>}
```

Parses the `<keyval list>`, and sets those keys which are defined for `<module>`. The behaviour on finding an unknown key can be set by defining a special `unknown` key: this is illustrated later.

```
\l_keys_key_str
\l_keys_path_str
\l_keys_value_tl
```

Updated: 2020-02-08

For each key processed, information of the full *path* of the key, the *name* of the key and the *value* of the key is available within three token list variables. These may be used within the code of the key.

The *value* is everything after the `=`, which may be empty if no value was given. This is stored in `\l_keys_value_tl`, and is not processed in any way by `\keys_set:nn`.

The *path* of the key is a “full” description of the key, and is unique for each key. It consists of the module and full key name, thus for example

```
\keys_set:nn { mymodule } { key-a = some-value }
```

has path `mymodule/key-a` while

```
\keys_set:nn { mymodule } { subset / key-a = some-value }
```

has path `mymodule/subset/key-a`. This information is stored in `\l_keys_path_str`.

The *name* of the key is the part of the path after the last `/`, and thus is not unique. In the preceding examples, both keys have name `key-a` despite having different paths. This information is stored in `\l_keys_key_str`.

5 Handling of unknown keys

If a key has not previously been defined (is unknown), `\keys_set:nn` looks for a special `unknown` key for the same module, and if this is not defined raises an error indicating that

the key name was unknown. This mechanism can be used for example to issue custom error texts.

```
\keys_define:nn { mymodule }
{
  unknown .code:n =
    You~tried~to~set~key~'\l_keys_key_str'~to~'#1'.
}
```

<code>\keys_set_known:nn</code>	<code>\keys_set_known:nn {<module>} {<keyval list>}</code>
<code>\keys_set_known:(nV nv no)</code>	<code>\keys_set_known:nnN {<module>} {<keyval list>} <tl></code>
<code>\keys_set_known:nnN</code>	<code>\keys_set_known:nnnN {<module>} {<keyval list>} {<root>} <tl></code>
<code>\keys_set_known:(nVN nvN noN)</code>	
<code>\keys_set_known:nnnN</code>	
<code>\keys_set_known:(nVnN nvN nonN)</code>	

New: 2011-08-23

Updated: 2019-01-29

These functions set keys which are known for the $\langle module \rangle$, and simply ignore other keys. The `\keys_set_known:nn` function parses the $\langle keyval list \rangle$, and sets those keys which are defined for $\langle module \rangle$. Any keys which are unknown are not processed further by the parser. In addition, `\keys_set_known:nnN` stores the key–value pairs in the $\langle tl \rangle$ in comma-separated form (*i.e.* an edited version of the $\langle keyval list \rangle$). When a $\langle root \rangle$ is given (`\keys_set_known:nnnN`), the key–value entries are returned relative to this point in the key tree. When it is absent, only the key name and value are provided. The correct list is returned by nested calls.

6 Selective key setting

In some cases it may be useful to be able to select only some keys for setting, even though these keys have the same path. For example, with a set of keys defined using

```
\keys_define:nn { mymodule }
{
  key-one .code:n = { \my_func:n {#1} } ,
  key-two .tl_set:N = \l_my_a_tl ,
  key-three .tl_set:N = \l_my_b_tl ,
  key-four .fp_set:N = \l_my_a_fp ,
}
```

the use of `\keys_set:nn` attempts to set all four keys. However, in some contexts it may only be sensible to set some keys, or to control the order of setting. To do this, keys may be assigned to *groups*: arbitrary sets which are independent of the key tree. Thus modifying the example to read

```
\keys_define:nn { mymodule }
{
  key-one .code:n = { \my_func:n {#1} } ,
  key-one .groups:n = { first } ,
  key-two .tl_set:N = \l_my_a_tl ,
}
```



```

key-two    .groups:n = { first }           ,
key-three  .tl_set:N = \l_my_b_tl          ,
key-three  .groups:n = { second }          ,
key-four   .fp_set:N = \l_my_a_fp          ,
}

```

assigns `key-one` and `key-two` to group `first`, `key-three` to group `second`, while `key-four` is not assigned to a group.

Selective key setting may be achieved either by selecting one or more groups to be made “active”, or by marking one or more groups to be ignored in key setting.

<code>\keys_set_filter:nnn</code>	<code>\keys_set_filter:nnn {<module>} {<groups>} {<keyval list>}</code>
<code>\keys_set_filter:(nnV nnv nno)</code>	<code>\keys_set_filter:nnnN {<module>} {<groups>} {<keyval list>} <tl></code>
<code>\keys_set_filter:nnnN</code>	<code>\keys_set_filter:nnnnN {<module>} {<groups>} {<keyval list>} <root></code>
<code>\keys_set_filter:(nnVN nnvN nnoN)</code>	<code><tl></code>
<code>\keys_set_filter:nnnnN</code>	
<code>\keys_set_filter:(nnVnN nnvnN nnonN)</code>	

New: 2013-07-14

Updated: 2019-01-29

Activates key filtering in an “opt-out” sense: keys assigned to any of the `<groups>` specified are ignored. The `<groups>` are given as a comma-separated list. Unknown keys are not assigned to any group and are thus always set. The key–value pairs for each key which is filtered out are stored in the `<tl>` in a comma-separated form (*i.e.* an edited version of the `<keyval list>`). The `\keys_set_filter:nnn` version skips this stage.

Use of `\keys_set_filter:nnnN` can be nested, with the correct residual `<keyval list>` returned at each stage. In the version which takes a `<root>` argument, the key list is returned relative to that point in the key tree. In the cases without a `<root>` argument, only the key names and values are returned.

<code>\keys_set_groups:nnn</code>	<code>\keys_set_groups:nnn {<module>} {<groups>} {<keyval list>}</code>
<code>\keys_set_groups:(nnV nnv nno)</code>	

New: 2013-07-14

Updated: 2017-05-27

Activates key filtering in an “opt-in” sense: only keys assigned to one or more of the `<groups>` specified are set. The `<groups>` are given as a comma-separated list. Unknown keys are not assigned to any group and are thus never set.

7 Utility functions for keys

<code>\keys_if_exist_p:nn *</code>	<code>\keys_if_exist_p:nn {<module>} {<key>}</code>
<code>\keys_if_exist:nnTF *</code>	<code>\keys_if_exist:nnTF {<module>} {<key>} {<true code>} {<false code>}</code>

Updated: 2017-11-14

Tests if the `<key>` exists for `<module>`, *i.e.* if any code has been defined for `<key>`.

<code>\keys_if_choice_exist_p:nnn *</code>	<code>\keys_if_choice_exist_p:nnn {<module>} {<key>} {<choice>}</code>
<code>\keys_if_choice_exist:nnnTF *</code>	<code>\keys_if_choice_exist:nnnTF {<module>} {<key>} {<choice>} {<true code>}</code>
	<code>{<false code>}</code>

New: 2011-08-21

Updated: 2017-11-14

Tests if the $\langle choice \rangle$ is defined for the $\langle key \rangle$ within the $\langle module \rangle$, *i.e.* if any code has been defined for $\langle key \rangle / \langle choice \rangle$. The test is **false** if the $\langle key \rangle$ itself is not defined.

<code>\keys_show:nn</code>	<code>\keys_show:nn {<module>} {<key>}</code>
----------------------------	---

Updated: 2015-08-09

Displays in the terminal the information associated to the $\langle key \rangle$ for a $\langle module \rangle$, including the function which is used to actually implement it.

<code>\keys_log:nn</code>	<code>\keys_log:nn {<module>} {<key>}</code>
---------------------------	--

New: 2014-08-22

Updated: 2015-08-09

Writes in the log file the information associated to the $\langle key \rangle$ for a $\langle module \rangle$. See also `\keys_show:nn` which displays the result in the terminal.

8 Low-level interface for parsing key–val lists

To re-cap from earlier, a key–value list is input of the form

```
KeyOne = ValueOne ,
KeyTwo = ValueTwo ,
KeyThree
```

where each key–value pair is separated by a comma from the rest of the list, and each key–value pair does not necessarily contain an equals sign or a value! Processing this type of input correctly requires a number of careful steps, to correctly account for braces, spaces and the category codes of separators.

While the functions described earlier are used as a high-level interface for processing such input, in special circumstances you may wish to use a lower-level approach. The low-level parsing system converts a $\langle key\text{--}value\text{ list} \rangle$ into $\langle keys \rangle$ and associated $\langle values \rangle$. After the parsing phase is completed, the resulting keys and values (or keys alone) are available for further processing. This processing is not carried out by the low-level parser itself, and so the parser requires the names of two functions along with the key–value list. One function is needed to process key–value pairs (it receives two arguments), and a second function is required for keys given without any value (it is called with a single argument).

The parser does not double `#` tokens or expand any input. Active tokens `=` and `,` appearing at the outer level of braces are converted to category “other” (12) so that the parser does not “miss” any due to category code changes. Spaces are removed from the ends of the keys and values. Keys and values which are given in braces have exactly one set removed (after space trimming), thus

```
key = {value here},
```

and

```
key = value here,
```

are treated identically.

`\keyval_parse:NNn` ★

Updated: 2020-02-20

`\keyval_parse:NNn` $\langle function_1 \rangle$ $\langle function_2 \rangle$ $\{ \langle key-value list \rangle \}$

Parses the $\langle key-value list \rangle$ into a series of $\langle keys \rangle$ and associated $\langle values \rangle$, or keys alone (if no $\langle value \rangle$ was given). $\langle function_1 \rangle$ should take one argument, while $\langle function_2 \rangle$ should absorb two arguments. After `\keyval_parse:NNn` has parsed the $\langle key-value list \rangle$, $\langle function_1 \rangle$ is used to process keys given with no value and $\langle function_2 \rangle$ is used to process keys given with a value. The order of the $\langle keys \rangle$ in the $\langle key-value list \rangle$ is preserved. Thus

```
\keyval_parse:NNn \function:n \function:nn
{ key1 = value1 , key2 = value2, key3 = , key4 }
```

is converted into an input stream

```
\function:nn { key1 } { value1 }
\function:nn { key2 } { value2 }
\function:nn { key3 } { }
\function:n { key4 }
```

Note that there is a difference between an empty value (an equals sign followed by nothing) and a missing value (no equals sign at all). Spaces are trimmed from the ends of the $\langle key \rangle$ and $\langle value \rangle$, then one *outer* set of braces is removed from the $\langle key \rangle$ and $\langle value \rangle$ as part of the processing.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the converted input stream does not expand further when appearing in an **x**-type or **e**-type argument expansion.

Part XXII

The l3intarray package: fast global integer arrays

1 l3intarray documentation

For applications requiring heavy use of integers, this module provides arrays which can be accessed in constant time (contrast l3seq, where access time is linear). These arrays have several important features

- The size of the array is fixed and must be given at point of initialisation
- The absolute value of each entry has maximum $2^{30} - 1$ (*i.e.* one power lower than the usual `\c_max_int` ceiling of $2^{31} - 1$)

The use of `intarray` data is therefore recommended for cases where the need for fast access is of paramount importance.

`\intarray_new:Nn`
`\intarray_new:cn`

New: 2018-03-29

`\intarray_new:Nn` $\langle\textit{intarray var}\rangle$ $\{\langle\textit{size}\rangle\}$

Evaluates the integer expression $\langle\textit{size}\rangle$ and allocates an $\langle\textit{integer array variable}\rangle$ with that number of (zero) entries. The variable name should start with `\g_` because assignments are always global.

`\intarray_count:N *`
`\intarray_count:c *`

New: 2018-03-29

`\intarray_count:N` $\langle\textit{intarray var}\rangle$

Expands to the number of entries in the $\langle\textit{integer array variable}\rangle$. Contrarily to `\seq-count:N` this is performed in constant time.

`\intarray_gset:Nnn`
`\intarray_gset:cnn`

New: 2018-03-29

`\intarray_gset:Nnn` $\langle\textit{intarray var}\rangle$ $\{\langle\textit{position}\rangle\}$ $\{\langle\textit{value}\rangle\}$

Stores the result of evaluating the integer expression $\langle\textit{value}\rangle$ into the $\langle\textit{integer array variable}\rangle$ at the (integer expression) $\langle\textit{position}\rangle$. If the $\langle\textit{position}\rangle$ is not between 1 and the `\intarray_count:N`, or the $\langle\textit{value}\rangle$'s absolute value is bigger than $2^{30} - 1$, an error occurs. Assignments are always global.

`\intarray_const_from_clist:Nn`
`\intarray_const_from_clist:cn`

New: 2018-05-04

`\intarray_const_from_clist:Nn` $\langle\textit{intarray var}\rangle$ $\langle\textit{intexpr clist}\rangle$

Creates a new constant $\langle\textit{integer array variable}\rangle$ or raises an error if the name is already taken. The $\langle\textit{integer array variable}\rangle$ is set (globally) to contain as its items the results of evaluating each $\langle\textit{integer expression}\rangle$ in the $\langle\textit{comma list}\rangle$.

`\intarray_gzero:N`
`\intarray_gzero:c`

New: 2018-05-04

`\intarray_gzero:N` $\langle\textit{intarray var}\rangle$

Sets all entries of the $\langle\textit{integer array variable}\rangle$ to zero. Assignments are always global.

<hr/>	
<code>\intarray_item:Nn</code> *	<code>\intarray_item:Nn <intarray var> {<position>}</code>
<code>\intarray_item:cn</code> *	Expands to the integer entry stored at the (integer expression) <i><position></i> in the <i><integer array variable></i> . If the <i><position></i> is not between 1 and the <code>\intarray_count:N</code> , an error occurs.
<hr/>	
New: 2018-03-29	
<hr/>	
<code>\intarray_rand_item:N</code> *	<code>\intarray_rand_item:N <intarray var></code>
<code>\intarray_rand_item:c</code> *	Selects a pseudo-random item of the <i><integer array></i> . If the <i><integer array></i> is empty, produce an error.
<hr/>	
New: 2018-05-05	
<hr/>	
<code>\intarray_show:N</code>	<code>\intarray_show:N <intarray var></code>
<code>\intarray_show:c</code>	<code>\intarray_log:N <intarray var></code>
<code>\intarray_log:N</code>	Displays the items in the <i><integer array variable></i> in the terminal or writes them in the log file.
<code>\intarray_log:c</code>	
<hr/>	
New: 2018-05-04	
<hr/>	

1.1 Implementation notes

It is a wrapper around the `\fontdimen` primitive, used to store arrays of integers (with a restricted range: absolute value at most $2^{30} - 1$). In contrast to `l3seq` sequences the access to individual entries is done in constant time rather than linear time, but only integers can be stored. More precisely, the primitive `\fontdimen` stores dimensions but the `l3intarray` package transparently converts these from/to integers. Assignments are always global.

While LuaTeX’s memory is extensible, other engines can “only” deal with a bit less than 4×10^6 entries in all `\fontdimen` arrays combined (with default TeXLive settings).

Part XXIII

The l3fp package: Floating points

A decimal floating point number is one which is stored as a significand and a separate exponent. The module implements expandably a wide set of arithmetic, trigonometric, and other operations on decimal floating point numbers, to be used within floating point expressions. Floating point expressions support the following operations with their usual precedence.

- Basic arithmetic: addition $x + y$, subtraction $x - y$, multiplication $x * y$, division x / y , square root \sqrt{x} , and parentheses.
 - Comparison operators: $x < y$, $x \leq y$, $x > y$, $x \neq y$ etc.
 - Boolean logic: sign $\text{sign } x$, negation $!x$, conjunction $x \&\& y$, disjunction $x || y$, ternary operator $x ? y : z$.
 - Exponentials: $\exp x$, $\ln x$, x^y , $\log b x$.
 - Integer factorial: $\text{fact } x$.
 - Trigonometry: $\sin x$, $\cos x$, $\tan x$, $\cot x$, $\sec x$, $\csc x$ expecting their arguments in radians, and $\text{sind } x$, $\text{cosd } x$, $\text{tand } x$, $\text{cotd } x$, $\text{secd } x$, $\text{cscd } x$ expecting their arguments in degrees.
 - Inverse trigonometric functions: $\text{asin } x$, $\text{acos } x$, $\text{atan } x$, $\text{acot } x$, $\text{asec } x$, $\text{acsc } x$ giving a result in radians, and $\text{asind } x$, $\text{acosd } x$, $\text{atand } x$, $\text{acotd } x$, $\text{asecd } x$, $\text{acscd } x$ giving a result in degrees.
- (not yet) Hyperbolic functions and their inverse functions: $\sinh x$, $\cosh x$, $\tanh x$, $\coth x$, $\text{sech } x$, $\text{csch } x$, and $\text{asinh } x$, $\text{acosh } x$, $\text{atanh } x$, $\text{acoth } x$, $\text{asech } x$, $\text{acsch } x$.
- Extrema: $\max(x_1, x_2, \dots)$, $\min(x_1, x_2, \dots)$, $\text{abs}(x)$.
 - Rounding functions, controlled by two optional values, n (number of places, 0 by default) and t (behavior on a tie, NaN by default):
 - $\text{trunc}(x, n)$ rounds towards zero,
 - $\text{floor}(x, n)$ rounds towards $-\infty$,
 - $\text{ceil}(x, n)$ rounds towards $+\infty$,
 - $\text{round}(x, n, t)$ rounds to the closest value, with ties rounded to an even value by default, towards zero if $t = 0$, towards $+\infty$ if $t > 0$ and towards $-\infty$ if $t < 0$.
- And (not yet) modulo, and “quantize”.
- Random numbers: $\text{rand}()$, $\text{randint}(m, n)$.
 - Constants: pi , deg (one degree in radians).
 - Dimensions, automatically expressed in points, e.g., pc is 12.

- Automatic conversion (no need for `\langle type \rangle_{use:N}`) of integer, dimension, and skip variables to floating point numbers, expressing dimensions in points and ignoring the stretch and shrink components of skips.
- Tuples: (x_1, \dots, x_n) that can be stored in variables, added together, multiplied or divided by a floating point number, and nested.

Floating point numbers can be given either explicitly (in a form such as $1.234\text{e-}34$, or $-.0001$), or as a stored floating point variable, which is automatically replaced by its current value. A “floating point” is a floating point number or a tuple thereof. See section 9.1 for a description of what a floating point is, section 9.2 for details about how an expression is parsed, and section 9.3 to know what the various operations do. Some operations may raise exceptions (error messages), described in section 7.

An example of use could be the following.

`\LaTeX{} can now compute: $\frac{\sin(3.5)}{2} + 2 \cdot 10^{-3}$`
`= \ExplSyntaxOn \fp_to_decimal:n {sin(3.5)/2 + 2e-3} $.`

The operation `round` can be used to limit the result’s precision. Adding `+0` avoids the possibly undesirable output `-0`, replacing it by `+0`. However, the `l3fp` module is mostly meant as an underlying tool for higher-level commands. For example, one could provide a function to typeset nicely the result of floating point computations.

```
\documentclass{article}
\usepackage{xparse, siunitx}
\ExplSyntaxOn
\NewDocumentCommand { \calcnun } { m }
{ \num { \fp_to_scientific:n {#1} } }
\ExplSyntaxOff
\begin{document}
\calcnun { 2 pi * sin ( 2.3 ^ 5 ) }
\end{document}
```

See the documentation of `siunitx` for various options of `\num`.

1 Creating and initialising floating point variables

<code>\fp_new:N</code>	<code>\fp_new:N <fp var></code>
<code>\fp_new:c</code>	Creates a new <code><fp var></code> or raises an error if the name is already taken. The declaration is global. The <code><fp var></code> is initially <code>+0</code> .
Updated: 2012-05-08	
<code>\fp_const:Nn</code>	<code>\fp_const:Nn <fp var> {<floating point expression>}</code>
<code>\fp_const:cn</code>	Creates a new constant <code><fp var></code> or raises an error if the name is already taken. The <code><fp var></code> is set globally equal to the result of evaluating the <code><floating point expression></code> .
Updated: 2012-05-08	
<code>\fp_zero:N</code>	<code>\fp_zero:N <fp var></code>
<code>\fp_zero:c</code>	Sets the <code><fp var></code> to <code>+0</code> .
<code>\fp_gzero:N</code>	
<code>\fp_gzero:c</code>	
Updated: 2012-05-08	

```

\fp_zero_new:N
\fp_zero_new:c
\fp_gzero_new:N
\fp_gzero_new:c

```

Updated: 2012-05-08

```
\fp_zero_new:N <fp var>
```

Ensures that the $\langle fp\ var \rangle$ exists globally by applying $\backslash fp_new:N$ if necessary, then applies $\backslash fp_(\mathfrak{g})zero:N$ to leave the $\langle fp\ var \rangle$ set to $+0$.

2 Setting floating point variables

```

\fp_set:Nn
\fp_set:cn
\fp_gset:Nn
\fp_gset:cn

```

Updated: 2012-05-08

```
\fp_set:Nn <fp var> {<floating point expression>}
```

Sets $\langle fp\ var \rangle$ equal to the result of computing the $\langle floating\ point\ expression \rangle$.

```

\fp_set_eq:Nn
\fp_set_eq:(cN|Nc|cc)
\fp_gset_eq:Nn
\fp_gset_eq:(cN|Nc|cc)

```

Updated: 2012-05-08

```
\fp_set_eq:Nn <fp var1> <fp var2>
```

Sets the floating point variable $\langle fp\ var_1 \rangle$ equal to the current value of $\langle fp\ var_2 \rangle$.

```

\fp_add:Nn
\fp_add:cn
\fp_gadd:Nn
\fp_gadd:cn

```

Updated: 2012-05-08

```
\fp_add:Nn <fp var> {<floating point expression>}
```

Adds the result of computing the $\langle floating\ point\ expression \rangle$ to the $\langle fp\ var \rangle$. This also applies if $\langle fp\ var \rangle$ and $\langle floating\ point\ expression \rangle$ evaluate to tuples of the same size.

```

\fp_sub:Nn
\fp_sub:cn
\fp_gsub:Nn
\fp_gsub:cn

```

Updated: 2012-05-08

```
\fp_sub:Nn <fp var> {<floating point expression>}
```

Subtracts the result of computing the $\langle floating\ point\ expression \rangle$ from the $\langle fp\ var \rangle$. This also applies if $\langle fp\ var \rangle$ and $\langle floating\ point\ expression \rangle$ evaluate to tuples of the same size.

3 Using floating points

```

\fp_eval:n  ★

```

New: 2012-05-08
Updated: 2012-07-08

```
\fp_eval:n {<floating point expression>}
```

Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. For a tuple, each item is converted using $\backslash fp_eval:n$ and they are combined as $(\langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle)$ if $n > 1$ and $(\langle fp_1 \rangle,)$ or $()$ for fewer items. This function is identical to $\backslash fp_to_decimal:n$.

<code>\fp_sign:N</code> *	<code>\fp_sign:n {<fpexpr>}</code>
---------------------------	--

New: 2018-11-03

Evaluates the $\langle fpexpr \rangle$ and leaves its sign in the input stream using `\fp_eval:n {sign(<result>)}`: +1 for positive numbers and for $+\infty$, -1 for negative numbers and for $-\infty$, ± 0 for ± 0 . If the operand is a tuple or is NaN, then “invalid operation” occurs and the result is 0.

<code>\fp_to_decimal:N</code> *	<code>\fp_to_decimal:N <fp var></code>
<code>\fp_to_decimal:c</code> *	<code>\fp_to_decimal:n {<floating point expression>}</code>
<code>\fp_to_decimal:n</code> *	

New: 2012-05-08

Updated: 2012-07-08

Evaluates the $\langle floating point expression \rangle$ and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. For a tuple, each item is converted using `\fp_to_decimal:n` and they are combined as $\langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle$ if $n > 1$ and $\langle fp_1 \rangle,)$ or $()$ for fewer items.

<code>\fp_to_dim:N</code> *	<code>\fp_to_dim:N <fp var></code>
<code>\fp_to_dim:c</code> *	<code>\fp_to_dim:n {<floating point expression>}</code>
<code>\fp_to_dim:n</code> *	

Updated: 2016-03-22

Evaluates the $\langle floating point expression \rangle$ and expresses the result as a dimension (in pt) suitable for use in dimension expressions. The output is identical to `\fp_to_decimal:n`, with an additional trailing pt (both letter tokens). In particular, the result may be outside the range $[-2^{14} + 2^{-17}, 2^{14} - 2^{-17}]$ of valid T_EX dimensions, leading to overflow errors if used as a dimension. Tuples, as well as the values $\pm\infty$ and NaN, trigger an “invalid operation” exception.

<code>\fp_to_int:N</code> *	<code>\fp_to_int:N <fp var></code>
<code>\fp_to_int:c</code> *	<code>\fp_to_int:n {<floating point expression>}</code>
<code>\fp_to_int:n</code> *	

Updated: 2012-07-08

Evaluates the $\langle floating point expression \rangle$, and rounds the result to the closest integer, rounding exact ties to an even integer. The result may be outside the range $[-2^{31} + 1, 2^{31} - 1]$ of valid T_EX integers, leading to overflow errors if used in an integer expression. Tuples, as well as the values $\pm\infty$ and NaN, trigger an “invalid operation” exception.

<code>\fp_to_scientific:N</code> *	<code>\fp_to_scientific:N <fp var></code>
<code>\fp_to_scientific:c</code> *	<code>\fp_to_scientific:n {<floating point expression>}</code>
<code>\fp_to_scientific:n</code> *	

New: 2012-05-08

Updated: 2016-03-22

Evaluates the $\langle floating point expression \rangle$ and expresses the result in scientific notation:

$\langle optional - \rangle \langle digit \rangle . \langle 15 digits \rangle e \langle optional sign \rangle \langle exponent \rangle$

The leading $\langle digit \rangle$ is non-zero except in the case of ± 0 . The values $\pm\infty$ and NaN trigger an “invalid operation” exception. Normal category codes apply: thus the `e` is category code 11 (a letter). For a tuple, each item is converted using `\fp_to_scientific:n` and they are combined as $\langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle$ if $n > 1$ and $\langle fp_1 \rangle,)$ or $()$ for fewer items.

<code>\fp_to_tl:N</code>	★	<code>\fp_to_tl:N <fp var></code>
<code>\fp_to_tl:c</code>	★	<code>\fp_to_tl:n {\floating point expression}</code>
<code>\fp_to_tl:n</code>	★	Evaluates the <i><floating point expression></i> and expresses the result in (almost) the shortest possible form. Numbers in the ranges $(0, 10^{-3})$ and $[10^{16}, \infty)$ are expressed in scientific notation with trailing zeros trimmed and no decimal separator when there is a single significant digit (this differs from <code>\fp_to_scientific:n</code>). Numbers in the range $[10^{-3}, 10^{16})$ are expressed in a decimal notation without exponent, with trailing zeros trimmed, and no decimal separator for integer values (see <code>\fp_to_decimal:n</code> . Negative numbers start with <code>-</code> . The special values ± 0 , $\pm \infty$ and NaN are rendered as <code>0</code> , <code>-0</code> , <code>inf</code> , <code>-inf</code> , and <code>nan</code> respectively. Normal category codes apply and thus <code>inf</code> or <code>nan</code> , if produced, are made up of letters. For a tuple, each item is converted using <code>\fp_to_tl:n</code> and they are combined as $\langle \langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle \rangle$ if $n > 1$ and $\langle \langle fp_1 \rangle, \rangle$ or $\langle \rangle$ for fewer items.

Updated: 2016-03-22

<code>\fp_use:N</code>	★	<code>\fp_use:N <fp var></code>
<code>\fp_use:c</code>	★	Inserts the value of the <i><fp var></i> into the input stream as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed. Integers are expressed without a decimal separator. The values $\pm \infty$ and NaN trigger an “invalid operation” exception. For a tuple, each item is converted using <code>\fp_to_decimal:n</code> and they are combined as $\langle \langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle \rangle$ if $n > 1$ and $\langle \langle fp_1 \rangle, \rangle$ or $\langle \rangle$ for fewer items. This function is identical to <code>\fp_to_decimal:N</code> .

Updated: 2012-07-08

4 Floating point conditionals

<code>\fp_if_exist_p:N</code>	★	<code>\fp_if_exist_p:N <fp var></code>
<code>\fp_if_exist_p:c</code>	★	<code>\fp_if_exist:N\TF <fp var> {\true code} {\false code}</code>
<code>\fp_if_exist:N\TF</code>	★	Tests whether the <i><fp var></i> is currently defined. This does not check that the <i><fp var></i> really is a floating point variable.
<code>\fp_if_exist:c\TF</code>	★	

Updated: 2012-05-08

<code>\fp_compare_p:nNn</code>	★	<code>\fp_compare_p:nNn {\fpexpr₁} <relation> {\fpexpr₂}</code>
<code>\fp_compare:nNn\TF</code>	★	<code>\fp_compare:nNn\TF {\fpexpr₁} <relation> {\fpexpr₂} {\true code} {\false code}</code>

Updated: 2012-05-08

Compares the *<fpexpr₁>* and the *<fpexpr₂>*, and returns `true` if the *<relation>* is obeyed. Two floating points x and y may obey four mutually exclusive relations: $x < y$, $x = y$, $x > y$, or $x?y$ (“not ordered”). The last case occurs exactly if one or both operands is NaN or is a tuple, unless they are equal tuples. Note that a NaN is distinct from any value, even another NaN, hence $x = x$ is not true for a NaN. To test if a value is NaN, compare it to an arbitrary number with the “not ordered” relation.

```

\fp_compare:nNn\TF { <value> } ? { 0 }
{ } % <value> is nan
{ } % <value> is not nan

```

Tuples are equal if they have the same number of items and items compare equal (in particular there must be no NaN). At present any other comparison with tuples yields ? (not ordered). This is experimental.

This function is less flexible than `\fp_compare:n\TF` but slightly faster. It is provided for consistency with `\int_compare:nNn\TF` and `\dim_compare:nNn\TF`.

<code>\fp_compare_p:n</code> ☆	<code>\fp_compare_p:n</code>
<code>\fp_compare:nTF</code> ☆	{
Updated: 2013-12-14	$\langle fpexpr_1 \rangle$ $\langle relation_1 \rangle$
	...
	$\langle fpexpr_N \rangle$ $\langle relation_N \rangle$
	$\langle fpexpr_{N+1} \rangle$
	}
	<code>\fp_compare:nTF</code>
	{
	$\langle fpexpr_1 \rangle$ $\langle relation_1 \rangle$
	...
	$\langle fpexpr_N \rangle$ $\langle relation_N \rangle$
	$\langle fpexpr_{N+1} \rangle$
	}
	{ $\langle true\ code \rangle$ } { $\langle false\ code \rangle$ }

Evaluates the $\langle floating\ point\ expressions \rangle$ as described for `\fp_eval:n` and compares consecutive result using the corresponding $\langle relation \rangle$, namely it compares $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$ using the $\langle relation_1 \rangle$, then $\langle fpexpr_2 \rangle$ and $\langle fpexpr_3 \rangle$ using the $\langle relation_2 \rangle$, until finally comparing $\langle fpexpr_N \rangle$ and $\langle fpexpr_{N+1} \rangle$ using the $\langle relation_N \rangle$. The test yields **true** if all comparisons are **true**. Each $\langle floating\ point\ expression \rangle$ is evaluated only once. Contrarily to `\int_compare:nTF`, all $\langle floating\ point\ expressions \rangle$ are computed, even if one comparison is **false**. Two floating points x and y may obey four mutually exclusive relations: $x < y$, $x = y$, $x > y$, or $x?y$ (“not ordered”). The last case occurs exactly if one or both operands is NaN or is a tuple, unless they are equal tuples. Each $\langle relation \rangle$ can be any (non-empty) combination of $<$, $=$, $>$, and $?$, plus an optional leading $!$ (which negates the $\langle relation \rangle$), with the restriction that the $\langle relation \rangle$ may not start with $?$, as this symbol has a different meaning (in combination with $:$) within floating point expressions. The comparison $x \langle relation \rangle y$ is then **true** if the $\langle relation \rangle$ does not start with $!$ and the actual relation ($<$, $=$, $>$, or $?$) between x and y appears within the $\langle relation \rangle$, or on the contrary if the $\langle relation \rangle$ starts with $!$ and the relation between x and y does not appear within the $\langle relation \rangle$. Common choices of $\langle relation \rangle$ include $>=$ (greater or equal), $!=$ (not equal), $!?$ or $<=>$ (comparable).

This function is more flexible than `\fp_compare:nNnTF` and only slightly slower.

5 Floating point expression loops

<code>\fp_do_until:nNnn</code> ☆	<code>\fp_do_until:nNnn {$\langle fpexpr_1 \rangle$} $\langle relation \rangle$ {$\langle fpexpr_2 \rangle$} {$\langle code \rangle$}</code>
New: 2012-08-16	Places the $\langle code \rangle$ in the input stream for \TeX to process, and then evaluates the relationship between the two $\langle floating\ point\ expressions \rangle$ as described for <code>\fp_compare:nNnTF</code> . If the test is false then the $\langle code \rangle$ is inserted into the input stream again and a loop occurs until the $\langle relation \rangle$ is true .
<code>\fp_do_while:nNnn</code> ☆	<code>\fp_do_while:nNnn {$\langle fpexpr_1 \rangle$} $\langle relation \rangle$ {$\langle fpexpr_2 \rangle$} {$\langle code \rangle$}</code>
New: 2012-08-16	Places the $\langle code \rangle$ in the input stream for \TeX to process, and then evaluates the relationship between the two $\langle floating\ point\ expressions \rangle$ as described for <code>\fp_compare:nNnTF</code> . If the test is true then the $\langle code \rangle$ is inserted into the input stream again and a loop occurs until the $\langle relation \rangle$ is false .

<hr/>	
<code>\fp_until_do:nNnn</code> ☆	<code>\fp_until_do:nNnn {<fpexpr1>} <relation> {<fpexpr2>} {<code>}</code>
New: 2012-08-16	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false. After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/>	
<code>\fp_while_do:nNnn</code> ☆	<code>\fp_while_do:nNnn {<fpexpr1>} <relation> {<fpexpr2>} {<code>}</code>
New: 2012-08-16	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true. After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .
<hr/>	
<code>\fp_do_until:nn</code> ☆	<code>\fp_do_until:nn { <fpexpr1> <relation> <fpexpr2> } {<code>}</code>
New: 2012-08-16 Updated: 2013-12-14	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> . If the test is false then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is true .
<hr/>	
<code>\fp_do_while:nn</code> ☆	<code>\fp_do_while:nn { <fpexpr1> <relation> <fpexpr2> } {<code>}</code>
New: 2012-08-16 Updated: 2013-12-14	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> . If the test is true then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is false .
<hr/>	
<code>\fp_until_do:nn</code> ☆	<code>\fp_until_do:nn { <fpexpr1> <relation> <fpexpr2> } {<code>}</code>
New: 2012-08-16 Updated: 2013-12-14	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false. After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/>	
<code>\fp_while_do:nn</code> ☆	<code>\fp_while_do:nn { <fpexpr1> <relation> <fpexpr2> } {<code>}</code>
New: 2012-08-16 Updated: 2013-12-14	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true. After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .

`\fp_step_function:nnnN` ☆
`\fp_step_function:nnnc` ☆

New: 2016-11-21
Updated: 2016-12-06

`\fp_step_function:nnnN` { $\langle initial\ value \rangle$ } { $\langle step \rangle$ } { $\langle final\ value \rangle$ } $\langle function \rangle$

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, each of which should be a floating point expression evaluating to a floating point number, not a tuple. The $\langle function \rangle$ is then placed in front of each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$). The $\langle step \rangle$ must be non-zero. If the $\langle step \rangle$ is positive, the loop stops when the $\langle value \rangle$ becomes larger than the $\langle final\ value \rangle$. If the $\langle step \rangle$ is negative, the loop stops when the $\langle value \rangle$ becomes smaller than the $\langle final\ value \rangle$. The $\langle function \rangle$ should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\fp_step_function:nnnN { 1.0 } { 0.1 } { 1.5 } \my_func:n
```

would print

```
[I saw 1.0]   [I saw 1.1]   [I saw 1.2]   [I saw 1.3]   [I saw 1.4]   [I saw 1.5]
```

TpXhackers note: Due to rounding, it may happen that adding the $\langle step \rangle$ to the $\langle value \rangle$ does not change the $\langle value \rangle$; such cases give an error, as they would otherwise lead to an infinite loop.

`\fp_step_inline:nnnn`

New: 2016-11-21
Updated: 2016-12-06

`\fp_step_inline:nnnn` { $\langle initial\ value \rangle$ } { $\langle step \rangle$ } { $\langle final\ value \rangle$ } { $\langle code \rangle$ }

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be floating point expressions evaluating to a floating point number, not a tuple. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream with `#1` replaced by the current $\langle value \rangle$. Thus the $\langle code \rangle$ should define a function of one argument (`#1`).

`\fp_step_variable:nnnNn`

New: 2017-04-12

`\fp_step_variable:nnnNn`
{ $\langle initial\ value \rangle$ } { $\langle step \rangle$ } { $\langle final\ value \rangle$ } $\langle tl\ var \rangle$ { $\langle code \rangle$ }

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be floating point expressions evaluating to a floating point number, not a tuple. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream, with the $\langle tl\ var \rangle$ defined as the current $\langle value \rangle$. Thus the $\langle code \rangle$ should make use of the $\langle tl\ var \rangle$.

6 Some useful constants, and scratch variables

`\c_zero_fp`
`\c_minus_zero_fp`

New: 2012-05-08

Zero, with either sign.

`\c_one_fp`

New: 2012-05-08

One as an fp: useful for comparisons in some places.

<hr/> <code>\c_inf_fp</code> <code>\c_minus_inf_fp</code> <hr/> New: 2012-05-08 <hr/>	<p>Infinity, with either sign. These can be input directly in a floating point expression as <code>inf</code> and <code>-inf</code>.</p>
<hr/> <code>\c_e_fp</code> <hr/> Updated: 2012-05-08 <hr/>	<p>The value of the base of the natural logarithm, $e = \exp(1)$.</p>
<hr/> <code>\c_pi_fp</code> <hr/> Updated: 2013-11-17 <hr/>	<p>The value of π. This can be input directly in a floating point expression as <code>pi</code>.</p>
<hr/> <code>\c_one_degree_fp</code> <hr/> New: 2012-05-08 Updated: 2013-11-17 <hr/>	<p>The value of 1° in radians. Multiply an angle given in degrees by this value to obtain a result in radians. Note that trigonometric functions expecting an argument in radians or in degrees are both available. Within floating point expressions, this can be accessed as <code>deg</code>.</p>
<hr/> <code>\l_tmpa_fp</code> <code>\l_tmpb_fp</code> <hr/>	<p>Scratch floating points for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.</p>
<hr/> <code>\g_tmpa_fp</code> <code>\g_tmpb_fp</code> <hr/>	<p>Scratch floating points for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.</p>

7 Floating point exceptions

The functions defined in this section are experimental, and their functionality may be altered or removed altogether.

“Exceptions” may occur when performing some floating point operations, such as $0 / 0$, or $10 ** 1e9999$. The relevant IEEE standard defines 5 types of exceptions, of which we implement 4.

- *Overflow* occurs whenever the result of an operation is too large to be represented as a normal floating point number. This results in $\pm\infty$.
- *Underflow* occurs whenever the result of an operation is too close to 0 to be represented as a normal floating point number. This results in ± 0 .
- *Invalid operation* occurs for operations with no defined outcome, for instance $0/0$ or $\sin(\infty)$, and results in a NaN. It also occurs for conversion functions whose target type does not have the appropriate infinite or NaN value (*e.g.*, `\fp_to_dim:n`).
- *Division by zero* occurs when dividing a non-zero number by 0, or when evaluating functions at poles, *e.g.*, $\ln(0)$ or $\cot(0)$. This results in $\pm\infty$.

(*not yet*) *Inexact* occurs whenever the result of a computation is not exact, in other words, almost always. At the moment, this exception is entirely ignored in L^AT_EX3.

To each exception we associate a “flag”: `fp_overflow`, `fp_underflow`, `fp_invalid_operation` and `fp_division_by_zero`. The state of these flags can be tested and modified with commands from `l3flag`

By default, the “invalid operation” exception triggers an (expandable) error, and raises the corresponding flag. Other exceptions raise the corresponding flag but do not trigger an error. The behaviour when an exception occurs can be modified (using `\fp_trap:nn`) to either produce an error and raise the flag, or only raise the flag, or do nothing at all.

<code>\fp_trap:nn</code>	<code>\fp_trap:nn {<exception>} {<trap type>}</code>
New: 2012-07-19 Updated: 2017-02-13	All occurrences of the <code><exception></code> (<code>overflow</code> , <code>underflow</code> , <code>invalid_operation</code> or <code>division_by_zero</code>) within the current group are treated as <code><trap type></code> , which can be <ul style="list-style-type: none"> • none: the <code><exception></code> will be entirely ignored, and leave no trace; • flag: the <code><exception></code> will turn the corresponding flag on when it occurs; • error: additionally, the <code><exception></code> will halt the T_EX run and display some information about the current operation in the terminal.

This function is experimental, and may be altered or removed.

`flag_fp_overflow`
`flag_fp_underflow`
`flag_fp_invalid_operation`
`flag_fp_division_by_zero`

Flags denoting the occurrence of various floating-point exceptions.

8 Viewing floating points

<code>\fp_show:N</code>	<code>\fp_show:N <fp var></code>
<code>\fp_show:c</code>	<code>\fp_show:n {<floating point expression>}</code>
<code>\fp_show:n</code>	Evaluates the <code><floating point expression></code> and displays the result in the terminal.

New: 2012-05-08
Updated: 2015-08-07

<code>\fp_log:N</code>	<code>\fp_log:N <fp var></code>
<code>\fp_log:c</code>	<code>\fp_log:n {<floating point expression>}</code>
<code>\fp_log:n</code>	Evaluates the <code><floating point expression></code> and writes the result in the log file.

New: 2014-08-22
Updated: 2015-08-07

9 Floating point expressions

9.1 Input of floating point numbers

We support four types of floating point numbers:

- $\pm m \cdot 10^n$, a floating point number, with integer $1 \leq m \leq 10^{16}$, and $-10000 \leq n \leq 10000$;
- ± 0 , zero, with a given sign;
- $\pm \infty$, infinity, with a given sign;
- NaN, is “not a number”, and can be either quiet or signalling (*not yet*: this distinction is currently unsupported);

Normal floating point numbers are stored in base 10, with up to 16 significant figures.

On input, a normal floating point number consists of:

- $\langle sign \rangle$: a possibly empty string of + and - characters;
- $\langle significand \rangle$: a non-empty string of digits together with zero or one dot;
- $\langle exponent \rangle$ optionally: the character e or E, followed by a possibly empty string of + and - tokens, and a non-empty string of digits.

The sign of the resulting number is + if $\langle sign \rangle$ contains an even number of -, and - otherwise, hence, an empty $\langle sign \rangle$ denotes a non-negative input. The stored significand is obtained from $\langle significand \rangle$ by omitting the decimal separator and leading zeros, and rounding to 16 significant digits, filling with trailing zeros if necessary. In particular, the value stored is exact if the input $\langle significand \rangle$ has at most 16 digits. The stored $\langle exponent \rangle$ is obtained by combining the input $\langle exponent \rangle$ (0 if absent) with a shift depending on the position of the significand and the number of leading zeros.

A special case arises if the resulting $\langle exponent \rangle$ is either too large or too small for the floating point number to be represented. This results either in an overflow (the number is then replaced by $\pm \infty$), or an underflow (resulting in ± 0).

The result is thus ± 0 if and only if $\langle significand \rangle$ contains no non-zero digit (*i.e.*, consists only in characters 0, and an optional period), or if there is an underflow. Note that a single dot is currently a valid floating point number, equal to +0, but that is not guaranteed to remain true.

The $\langle significand \rangle$ must be non-empty, so e1 and e-1 are not valid floating point numbers. Note that the latter could be mistaken with the difference of “e” and 1. To avoid confusions, the base of natural logarithms cannot be input as e and should be input as exp(1) or \c_e_fp (which is faster).

Special numbers are input as follows:

- inf represents $+\infty$, and can be preceded by any $\langle sign \rangle$, yielding $\pm \infty$ as appropriate.
- nan represents a (quiet) non-number. It can be preceded by any sign, but that sign is ignored.
- Any unrecognizable string triggers an error, and produces a NaN.
- Note that commands such as \infy, \pi, or \sin *do not* work in floating point expressions. They may silently be interpreted as completely unexpected numbers, because integer constants (allowed in expressions) are commonly stored as mathematical characters.

9.2 Precedence of operators

We list here all the operations supported in floating point expressions, in order of decreasing precedence: operations listed earlier bind more tightly than operations listed below them.

- Function calls (`sin`, `ln`, *etc*).
- Binary `**` and `^` (right associative).
- Unary `+`, `-`, `!`.
- Implicit multiplication by juxtaposition (`2pi`) when neither factor is in parentheses.
- Binary `*` and `/`, implicit multiplication by juxtaposition with parentheses (for instance `3(4+5)`).
- Binary `+` and `-`.
- Comparisons `>=`, `!=`, `<?`, *etc*.
- Logical `and`, denoted by `&&`.
- Logical `or`, denoted by `||`.
- Ternary operator `?:` (right associative).
- Comma (to build tuples).

The precedence of operations can be overridden using parentheses. In particular, the precedence of juxtaposition implies that

$$\begin{aligned}1/2\text{pi} &= 1/(2\pi), \\1/2\text{pi}(\text{pi} + \text{pi}) &= (2\pi)^{-1}(\pi + \pi) \simeq 1, \\ \sin 2\text{pi} &= \sin(2)\pi \neq 0, \\ 2^{\text{2max}(3,5)} &= 2^2 \max(3,5) = 20, \\ 1\text{in}/1\text{cm} &= (1\text{in})/(1\text{cm}) = 2.54.\end{aligned}$$

Functions are called on the value of their argument, contrarily to `TeX` macros.

9.3 Operations

We now present the various operations allowed in floating point expressions, from the lowest precedence to the highest. When used as a truth value, a floating point expression is `false` if it is ± 0 , and `true` otherwise, including when it is `NaN` or a tuple such as `(0, 0)`. Tuples are only supported to some extent by operations that work with truth values (`?:`, `||`, `&&`, `!`), by comparisons (`!<=>?`), and by `+`, `-`, `*`, `/`. Unless otherwise specified, providing a tuple as an argument of any other operation yields the “invalid operation” exception and a `NaN` result.

```
?: \fp_eval:n { <operand1> ? <operand2> : <operand3> }
```

The ternary operator `?:` results in $\langle operand_2 \rangle$ if $\langle operand_1 \rangle$ is true (not ± 0), and $\langle operand_3 \rangle$ if $\langle operand_1 \rangle$ is false (± 0). All three $\langle operands \rangle$ are evaluated in all cases; they may be tuples. The operator is right associative, hence

```
\fp_eval:n
{
  1 + 3 > 4 ? 1 :
  2 + 4 > 5 ? 2 :
  3 + 5 > 6 ? 3 : 4
}
```

first tests whether $1 + 3 > 4$; since this isn't true, the branch following `:` is taken, and $2 + 4 > 5$ is compared; since this is true, the branch before `:` is taken, and everything else is (evaluated then) ignored. That allows testing for various cases in a concise manner, with the drawback that all computations are made in all cases.

```
|| \fp_eval:n { <operand1> || <operand2> }
```

If $\langle operand_1 \rangle$ is true (not ± 0), use that value, otherwise the value of $\langle operand_2 \rangle$. Both $\langle operands \rangle$ are evaluated in all cases; they may be tuples. In $\langle operand_1 \rangle || \langle operand_2 \rangle || \dots || \langle operand_n \rangle$, the first true (nonzero) $\langle operand \rangle$ is used and if all are zero the last one (± 0) is used.

```
&& \fp_eval:n { <operand1> && <operand2> }
```

If $\langle operand_1 \rangle$ is false (equal to ± 0), use that value, otherwise the value of $\langle operand_2 \rangle$. Both $\langle operands \rangle$ are evaluated in all cases; they may be tuples. In $\langle operand_1 \rangle \&\& \langle operand_2 \rangle \&\& \dots \&\& \langle operand_n \rangle$, the first false (± 0) $\langle operand \rangle$ is used and if none is zero the last one is used.

```
< \fp_eval:n
= {
>   <operand1> <relation1>
?   ...
    <operand_N> <relation_N>
    <operand_{N+1}>
}
```

Updated: 2013-12-14

Each $\langle relation \rangle$ consists of a non-empty string of `<`, `=`, `>`, and `?`, optionally preceded by `!`, and may not start with `?`. This evaluates to $+1$ if all comparisons $\langle operand_i \rangle \langle relation_i \rangle \langle operand_{i+1} \rangle$ are true, and $+0$ otherwise. All $\langle operands \rangle$ are evaluated (once) in all cases. See `\fp_compare:nTF` for details.

```
+ \fp_eval:n { <operand1> + <operand2> }
- \fp_eval:n { <operand1> - <operand2> }
```

Computes the sum or the difference of its two $\langle operands \rangle$. The “invalid operation” exception occurs for $\infty - \infty$. “Underflow” and “overflow” occur when appropriate. These operations supports the itemwise addition or subtraction of two tuples, but if they have a different number of items the “invalid operation” exception occurs and the result is NaN.

```

* \fp_eval:n { <operand1> * <operand2> }
/ \fp_eval:n { <operand1> / <operand2> }

```

Computes the product or the ratio of its two $\langle \text{operands} \rangle$. The “invalid operation” exception occurs for ∞/∞ , $0/0$, or $0 * \infty$. “Division by zero” occurs when dividing a finite non-zero number by ± 0 . “Underflow” and “overflow” occur when appropriate. When $\langle \text{operand}_1 \rangle$ is a tuple and $\langle \text{operand}_2 \rangle$ is a floating point number, each item of $\langle \text{operand}_1 \rangle$ is multiplied or divided by $\langle \text{operand}_2 \rangle$. Multiplication also supports the case where $\langle \text{operand}_1 \rangle$ is a floating point number and $\langle \text{operand}_2 \rangle$ a tuple. Other combinations yield an “invalid operation” exception and a NaN result.

```

+ \fp_eval:n { + <operand> }
- \fp_eval:n { - <operand> }
! \fp_eval:n { ! <operand> }

```

The unary $+$ does nothing, the unary $-$ changes the sign of the $\langle \text{operand} \rangle$ (for a tuple, of all its components), and $!$ $\langle \text{operand} \rangle$ evaluates to 1 if $\langle \text{operand} \rangle$ is false (is ± 0) and 0 otherwise (this is the `not` boolean function). Those operations never raise exceptions.

```

** \fp_eval:n { <operand1> ** <operand2> }
^ \fp_eval:n { <operand1> ^ <operand2> }

```

Raises $\langle \text{operand}_1 \rangle$ to the power $\langle \text{operand}_2 \rangle$. This operation is right associative, hence $2^{**} 2^{**} 3$ equals $2^{2^3} = 256$. If $\langle \text{operand}_1 \rangle$ is negative or -0 then: the result’s sign is $+$ if the $\langle \text{operand}_2 \rangle$ is infinite and $(-1)^p$ if the $\langle \text{operand}_2 \rangle$ is $p/5^q$ with p, q integers; the result is $+0$ if $\text{abs}(\langle \text{operand}_1 \rangle)^{\langle \text{operand}_2 \rangle}$ evaluates to zero; in other cases the “invalid operation” exception occurs because the sign cannot be determined. “Division by zero” occurs when raising ± 0 to a finite strictly negative power. “Underflow” and “overflow” occur when appropriate. If either operand is a tuple, “invalid operation” occurs.

```

abs \fp_eval:n { abs( <fpexpr> ) }

```

Computes the absolute value of the $\langle \text{fpexpr} \rangle$. If the operand is a tuple, “invalid operation” occurs. This operation does not raise exceptions in other cases. See also `\fp_abs:n`.

```

exp \fp_eval:n { exp( <fpexpr> ) }

```

Computes the exponential of the $\langle \text{fpexpr} \rangle$. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

```

fact \fp_eval:n { fact( <fpexpr> ) }

```

Computes the factorial of the $\langle \text{fpexpr} \rangle$. If the $\langle \text{fpexpr} \rangle$ is an integer between -0 and 3248 included, the result is finite and correctly rounded. Larger positive integers give $+\infty$ with “overflow”, while $\text{fact}(+\infty) = +\infty$ and $\text{fact}(\text{nan}) = \text{nan}$ with no exception. All other inputs give NaN with the “invalid operation” exception.

```

ln \fp_eval:n { ln( <fpexpr> ) }

```

Computes the natural logarithm of the $\langle \text{fpexpr} \rangle$. Negative numbers have no (real) logarithm, hence the “invalid operation” is raised in that case, including for $\ln(-0)$. “Division by zero” occurs when evaluating $\ln(+0) = -\infty$. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

<hr/> logb <hr/>	★	<code>\fp_eval:n { logb(<fpexpr>) }</code>	
<hr/> New: 2018-11-03 <hr/>			Determines the exponent of the $\langle fpexpr \rangle$, namely the floor of the base-10 logarithm of its absolute value. “Division by zero” occurs when evaluating $\logb(\pm 0) = -\infty$. Other special values are $\logb(\pm\infty) = +\infty$ and $\logb(\text{NaN}) = \text{NaN}$. If the operand is a tuple or is NaN, then “invalid operation” occurs and the result is NaN.
<hr/> max <hr/>		<code>\fp_eval:n { max(<fpexpr₁> , <fpexpr₂> , ...) }</code>	
<hr/> min <hr/>		<code>\fp_eval:n { min(<fpexpr₁> , <fpexpr₂> , ...) }</code>	
			Evaluates each $\langle fpexpr \rangle$ and computes the largest (smallest) of those. If any of the $\langle fpexpr \rangle$ is a NaN or tuple, the result is NaN. If any operand is a tuple, “invalid operation” occurs; these operations do not raise exceptions in other cases.
<hr/> round <hr/>		<code>\fp_eval:n { round (<fpexpr>) }</code>	
trunc		<code>\fp_eval:n { round (<fpexpr₁> , <fpexpr₂>) }</code>	
ceil		<code>\fp_eval:n { round (<fpexpr₁> , <fpexpr₂> , <fpexpr₃>) }</code>	
floor			
<hr/> New: 2013-12-14 <hr/>			Only round accepts a third argument. Evaluates $\langle fpexpr_1 \rangle = x$ and $\langle fpexpr_2 \rangle = n$ and $\langle fpexpr_3 \rangle = t$ then rounds x to n places. If n is an integer, this rounds x to a multiple of 10^{-n} ; if $n = +\infty$, this always yields x ; if $n = -\infty$, this yields one of ± 0 , $\pm\infty$, or NaN; if $n = \text{NaN}$, this yields NaN; if n is neither $\pm\infty$ nor an integer, then an “invalid operation” exception is raised. When $\langle fpexpr_2 \rangle$ is omitted, $n = 0$, <i>i.e.</i> , $\langle fpexpr_1 \rangle$ is rounded to an integer. The rounding direction depends on the function.
<hr/> Updated: 2015-08-08 <hr/>			
			<ul style="list-style-type: none"> • round yields the multiple of 10^{-n} closest to x, with ties (x half-way between two such multiples) rounded as follows. If t is nan (or not given) the even multiple is chosen (“ties to even”), if $t = \pm 0$ the multiple closest to 0 is chosen (“ties to zero”), if t is positive/negative the multiple closest to $\infty/-\infty$ is chosen (“ties towards positive/negative infinity”). • floor yields the largest multiple of 10^{-n} smaller or equal to x (“round towards negative infinity”); • ceil yields the smallest multiple of 10^{-n} greater or equal to x (“round towards positive infinity”); • trunc yields a multiple of 10^{-n} with the same sign as x and with the largest absolute value less than that of x (“round towards zero”).
			“Overflow” occurs if x is finite and the result is infinite (this can only happen if $\langle fpexpr_2 \rangle < -9984$). If any operand is a tuple, “invalid operation” occurs.
<hr/> sign <hr/>		<code>\fp_eval:n { sign(<fpexpr>) }</code>	
			Evaluates the $\langle fpexpr \rangle$ and determines its sign: +1 for positive numbers and for $+\infty$, -1 for negative numbers and for $-\infty$, ± 0 for ± 0 , and NaN for NaN. If the operand is a tuple, “invalid operation” occurs. This operation does not raise exceptions in other cases.

<code>sin</code>	<code>\fp_eval:n { sin(<fpexpr>) }</code>
<code>cos</code>	<code>\fp_eval:n { cos(<fpexpr>) }</code>
<code>tan</code>	<code>\fp_eval:n { tan(<fpexpr>) }</code>
<code>cot</code>	<code>\fp_eval:n { cot(<fpexpr>) }</code>
<code>csc</code>	<code>\fp_eval:n { csc(<fpexpr>) }</code>
<code>sec</code>	<code>\fp_eval:n { sec(<fpexpr>) }</code>

Updated: 2013-11-17

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the $\langle fpexpr \rangle$ given in radians. For arguments given in degrees, see `sind`, `cosd`, *etc.* Note that since π is irrational, `sin(8pi)` is not quite zero, while its analogue `sind(8 × 180)` is exactly zero. The trigonometric functions are undefined for an argument of $\pm\infty$, leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

<code>sind</code>	<code>\fp_eval:n { sind(<fpexpr>) }</code>
<code>cosd</code>	<code>\fp_eval:n { cosd(<fpexpr>) }</code>
<code>tand</code>	<code>\fp_eval:n { tand(<fpexpr>) }</code>
<code>cotd</code>	<code>\fp_eval:n { cotd(<fpexpr>) }</code>
<code>cscd</code>	<code>\fp_eval:n { cscd(<fpexpr>) }</code>
<code>secd</code>	<code>\fp_eval:n { secd(<fpexpr>) }</code>

New: 2013-11-02

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the $\langle fpexpr \rangle$ given in degrees. For arguments given in radians, see `sin`, `cos`, *etc.* Note that since π is irrational, `sin(8pi)` is not quite zero, while its analogue `sind(8 × 180)` is exactly zero. The trigonometric functions are undefined for an argument of $\pm\infty$, leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

<code>asin</code>	<code>\fp_eval:n { asin(<fpexpr>) }</code>
<code>acos</code>	<code>\fp_eval:n { acos(<fpexpr>) }</code>
<code>acsc</code>	<code>\fp_eval:n { acsc(<fpexpr>) }</code>
<code>asec</code>	<code>\fp_eval:n { asec(<fpexpr>) }</code>

New: 2013-11-02

Computes the arcsine, arccosine, arccosecant, or arcsecant of the $\langle fpexpr \rangle$ and returns the result in radians, in the range $[-\pi/2, \pi/2]$ for `asin` and `acsc` and $[0, \pi]$ for `acos` and `asec`. For a result in degrees, use `asind`, *etc.* If the argument of `asin` or `acos` lies outside the range $[-1, 1]$, or the argument of `acsc` or `asec` inside the range $(-1, 1)$, an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

<code>asind</code>	<code>\fp_eval:n { asind(<fpexpr>) }</code>
<code>acosd</code>	<code>\fp_eval:n { acosd(<fpexpr>) }</code>
<code>acscd</code>	<code>\fp_eval:n { acscd(<fpexpr>) }</code>
<code>asecd</code>	<code>\fp_eval:n { asecd(<fpexpr>) }</code>

New: 2013-11-02

Computes the arcsine, arccosine, arccosecant, or arcsecant of the $\langle fpexpr \rangle$ and returns the result in degrees, in the range $[-90, 90]$ for `asin` and `acsc` and $[0, 180]$ for `acos` and `asec`. For a result in radians, use `asin`, *etc.* If the argument of `asin` or `acos` lies outside the range $[-1, 1]$, or the argument of `acsc` or `asec` inside the range $(-1, 1)$, an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

atan	<code>\fp_eval:n { atan(<fpexpr>) }</code>
acot	<code>\fp_eval:n { atan(<fpexpr₁> , <fpexpr₂>) }</code>
<hr/>	
New: 2013-11-02	<code>\fp_eval:n { acot(<fpexpr>) }</code>
	<code>\fp_eval:n { acot(<fpexpr₁> , <fpexpr₂>) }</code>

Those functions yield an angle in radians: **atand** and **acotd** are their analogs in degrees. The one-argument versions compute the arctangent or arccotangent of the $\langle fpexpr \rangle$: arctangent takes values in the range $[-\pi/2, \pi/2]$, and arccotangent in the range $[0, \pi]$. The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$: this is the arctangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by π depending on the signs of $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$. The two-argument arccotangent computes the angle in polar coordinates of the point $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$, equal to the arccotangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by π . Both two-argument functions take values in the wider range $[-\pi, \pi]$. The ratio $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ need not be defined for the two-argument arctangent: when both expressions yield ± 0 , or when both yield $\pm \infty$, the resulting angle is one of $\{\pm\pi/4, \pm 3\pi/4\}$ depending on signs. The “underflow” exception can occur. If any operand is a tuple, “invalid operation” occurs.

atand	<code>\fp_eval:n { atand(<fpexpr>) }</code>
acotd	<code>\fp_eval:n { atand(<fpexpr₁> , <fpexpr₂>) }</code>
<hr/>	
New: 2013-11-02	<code>\fp_eval:n { acotd(<fpexpr>) }</code>
	<code>\fp_eval:n { acotd(<fpexpr₁> , <fpexpr₂>) }</code>

Those functions yield an angle in degrees: **atand** and **acotd** are their analogs in radians. The one-argument versions compute the arctangent or arccotangent of the $\langle fpexpr \rangle$: arctangent takes values in the range $[-90, 90]$, and arccotangent in the range $[0, 180]$. The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$: this is the arctangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by 180 depending on the signs of $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$. The two-argument arccotangent computes the angle in polar coordinates of the point $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$, equal to the arccotangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by 180. Both two-argument functions take values in the wider range $[-180, 180]$. The ratio $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ need not be defined for the two-argument arctangent: when both expressions yield ± 0 , or when both yield $\pm \infty$, the resulting angle is one of $\{\pm 45, \pm 135\}$ depending on signs. The “underflow” exception can occur. If any operand is a tuple, “invalid operation” occurs.

sqrt	<code>\fp_eval:n { sqrt(<fpexpr>) }</code>
-------------	--

New: 2013-12-14 Computes the square root of the $\langle fpexpr \rangle$. The “invalid operation” is raised when the $\langle fpexpr \rangle$ is negative or is a tuple; no other exception can occur. Special values yield $\sqrt{-0} = -0$, $\sqrt{+0} = +0$, $\sqrt{+\infty} = +\infty$ and $\sqrt{\text{NaN}} = \text{NaN}$.

<hr/> rand <hr/>	<code>\fp_eval:n { rand() }</code>
<hr/> <small>New: 2016-12-05</small> <hr/>	<p>Produces a pseudo-random floating-point number (multiple of 10^{-16}) between 0 included and 1 excluded. This is not available in older versions of $\text{X}\text{_}\text{T}\text{E}\text{X}$. The random seed can be queried using <code>\sys_rand_seed:</code> and set using <code>\sys_gset_rand_seed:n</code>.</p> <p>TEXhackers note: This is based on pseudo-random numbers provided by the engine’s primitive <code>\pdfuniformdeviate</code> in $\text{pdf}\text{_}\text{T}\text{E}\text{X}$, $\text{p}\text{T}\text{E}\text{X}$, $\text{up}\text{T}\text{E}\text{X}$ and <code>\uniformdeviate</code> in $\text{Lua}\text{_}\text{T}\text{E}\text{X}$ and $\text{X}\text{_}\text{T}\text{E}\text{X}$. The underlying code is based on Metapost, which follows an additive scheme recommended in Section 3.6 of “The Art of Computer Programming, Volume 2”.</p> <p>While we are more careful than <code>\uniformdeviate</code> to preserve uniformity of the underlying stream of 28-bit pseudo-random integers, these pseudo-random numbers should of course not be relied upon for serious numerical computations nor cryptography.</p>
<hr/> randint <hr/>	<code>\fp_eval:n { randint(<fpexpr>) }</code>
<hr/> <small>New: 2016-12-05</small> <hr/>	<code>\fp_eval:n { randint(<fpexpr₁> , <fpexpr₂>) }</code> <p>Produces a pseudo-random integer between 1 and $\langle fpexpr \rangle$ or between $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$ inclusive. The bounds must be integers in the range $(-10^{16}, 10^{16})$ and the first must be smaller or equal to the second. See rand for important comments on how these pseudo-random numbers are generated.</p>
<hr/> inf nan <hr/>	The special values $+\infty$, $-\infty$, and NaN are represented as inf , -inf and nan (see <code>\c_minus_inf_fp</code> , <code>\c_minus_inf_fp</code> and <code>\c_nan_fp</code>).
<hr/> pi <hr/>	The value of π (see <code>\c_pi_fp</code>).
<hr/> deg <hr/>	The value of 1° in radians (see <code>\c_one_degree_fp</code>).

<hr/>	Those units of measurement are equal to their values in <code>pt</code> , namely
<code>em</code>	
<code>ex</code>	
<code>in</code>	$1\text{in} = 72.27\text{pt}$
<code>pt</code>	$1\text{pt} = 1\text{pt}$
<code>pc</code>	
<code>cm</code>	$1\text{pc} = 12\text{pt}$
<code>mm</code>	
<code>dd</code>	$1\text{cm} = \frac{1}{2.54}\text{in} = 28.45275590551181\text{pt}$
<code>cc</code>	
<code>nd</code>	$1\text{mm} = \frac{1}{25.4}\text{in} = 2.845275590551181\text{pt}$
<code>nc</code>	
<code>bp</code>	$1\text{dd} = 0.376065\text{mm} = 1.07000856496063\text{pt}$
<code>sp</code>	
<hr/>	
	$1\text{cc} = 12\text{dd} = 12.84010277952756\text{pt}$
	$1\text{nd} = 0.375\text{mm} = 1.066978346456693\text{pt}$
	$1\text{nc} = 12\text{nd} = 12.80374015748031\text{pt}$
	$1\text{bp} = \frac{1}{72}\text{in} = 1.00375\text{pt}$
	$1\text{sp} = 2^{-16}\text{pt} = 1.52587890625e - 5\text{pt}.$

The values of the (font-dependent) units `em` and `ex` are gathered from \TeX when the surrounding floating point expression is evaluated.

<hr/>	
<code>true</code>	Other names for 1 and +0.
<code>false</code>	
<hr/>	

<hr/>	
<code>\fp_abs:n</code> *	<code>\fp_abs:n</code> $\{\langle\textit{floating point expression}\rangle\}$
New: 2012-05-14	Evaluates the $\langle\textit{floating point expression}\rangle$ as described for <code>\fp_eval:n</code> and leaves the absolute value of the result in the input stream. If the argument is $\pm\infty$, <code>NaN</code> or a tuple, “invalid operation” occurs. Within floating point expressions, <code>abs()</code> can be used; it accepts $\pm\infty$ and <code>NaN</code> as arguments.
Updated: 2012-07-08	
<hr/>	

<hr/>	
<code>\fp_max:nn</code> *	<code>\fp_max:nn</code> $\{\langle\textit{fp expression 1}\rangle\} \{\langle\textit{fp expression 2}\rangle\}$
<code>\fp_min:nn</code> *	Evaluates the $\langle\textit{floating point expressions}\rangle$ as described for <code>\fp_eval:n</code> and leaves the resulting larger (<code>max</code>) or smaller (<code>min</code>) value in the input stream. If the argument is a tuple, “invalid operation” occurs, but no other case raises exceptions. Within floating point expressions, <code>max()</code> and <code>min()</code> can be used.
New: 2012-09-26	
<hr/>	

10 Disclaimer and roadmap

The package may break down if the escape character is among `0123456789_+`, or if it receives a \TeX primitive conditional affected by `\exp_not:N`.

The following need to be done. I’ll try to time-order the items.

- Function to count items in a tuple (and to determine if something is a tuple).
- Decide what exponent range to consider.

- Support signalling `nan`.
- Modulo and remainder, and rounding function `quantize` (and its friends analogous to `trunc`, `ceil`, `floor`).
- `\fp_format:nn {<fpepr>} {<format>}`, but what should `<format>` be? More general pretty printing?
- Add `and`, `or`, `xor`? Perhaps under the names `all`, `any`, and `xor`?
- Add `log(x, b)` for logarithm of x in base b .
- `hypot` (Euclidean length). Cartesian-to-polar transform.
- Hyperbolic functions `cosh`, `sinh`, `tanh`.
- Inverse hyperbolics.
- Base conversion, input such as `0xAB.CDEF`.
- Factorial (not with `!`), gamma function.
- Improve coefficients of the `sin` and `tan` series.
- Treat upper and lower case letters identically in identifiers, and ignore underscores.
- Add an `array(1,2,3)` and `i=complex(0,1)`.
- Provide an experimental `map` function? Perhaps easier to implement if it is a single character, `@sin(1,2)`?
- Provide an `isnan` function analogue of `\fp_if_nan:nTF`?
- Support keyword arguments?

`Pgfmath` also provides box-measurements (depth, height, width), but boxes are not possible expandably.

Bugs, and tests to add.

- Check that functions are monotonic when they should.
- Add exceptions to `?:`, `!<=>?`, `&&`, `||`, and `!`.
- Logarithms of numbers very close to 1 are inaccurate.
- When rounding towards $-\infty$, `\dim_to_fp:n {Opt}` should return -0 , not $+0$.
- The result of $(\pm 0) + (\pm 0)$, of $x + (-x)$, and of $(-x) + x$ should depend on the rounding mode.
- `0e9999999999` gives a \TeX “number too large” error.
- Subnormals are not implemented.

Possible optimizations/improvements.

- Document that `l3trial/l3fp-types` introduces tools for adding new types.
- In subsection 9.1, write a grammar.

- It would be nice if the `parse` auxiliaries for each operation were set up in the corresponding module, rather than centralizing in `l3fp-parse`.
- Some functions should get an `_o` ending to indicate that they expand after their result.
- More care should be given to distinguish expandable/restricted expandable (auxiliary and internal) functions.
- The code for the `ternary` set of functions is ugly.
- There are many `~` missing in the doc to avoid bad line-breaks.
- The algorithm for computing the logarithm of the significand could be made to use a 5 terms Taylor series instead of 10 terms by taking $c = 2000/([200x]+1) \in [10, 95]$ instead of $c \in [1, 10]$. Also, it would then be possible to simplify the computation of t . However, we would then have to hard-code the logarithms of 44 small integers instead of 9.
- Improve notations in the explanations of the division algorithm (`l3fp-basics`).
- Understand and document `_fp_basics_pack_weird_low:NNNNw` and `_fp_basics_pack_weird_high:NNNNNNNNw` better. Move the other `basics_pack` auxiliaries to `l3fp-aux` under a better name.
- Find out if underflow can really occur for trigonometric functions, and redoc as appropriate.
- Add bibliography. Some of Kahan’s articles, some previous TeX fp packages, the international standards,...
- Also take into account the “inexact” exception?
- Support multi-character prefix operators (*e.g.*, `@/` or whatever)?

Part XXIV

The l3farray package: fast global floating point arrays

1 l3farray documentation

For applications requiring heavy use of floating points, this module provides arrays which can be accessed in constant time (contrast l3seq, where access time is linear). The interface is very close to that of l3intarray. The size of the array is fixed and must be given at point of initialisation

<code>\farray_new:Nn</code>	<code>\farray_new:Nn <farray var> {<size>}</code>
-----------------------------	---

New: 2018-05-05

Evaluates the integer expression *<size>* and allocates an *<floating point array variable>* with that number of (zero) entries. The variable name should start with `\g_` because assignments are always global.

<code>\farray_count:N</code> ★	<code>\farray_count:N <farray var></code>
--------------------------------	---

New: 2018-05-05

Expands to the number of entries in the *<floating point array variable>*. This is performed in constant time.

<code>\farray_gset:Nnn</code>	<code>\farray_gset:Nnn <farray var> {<position>} {<value>}</code>
-------------------------------	---

New: 2018-05-05

Stores the result of evaluating the floating point expression *<value>* into the *<floating point array variable>* at the (integer expression) *<position>*. If the *<position>* is not between 1 and the `\farray_count:N`, an error occurs. Assignments are always global.

<code>\farray_gzero:N</code>	<code>\farray_gzero:N <farray var></code>
------------------------------	---

New: 2018-05-05

Sets all entries of the *<floating point array variable>* to +0. Assignments are always global.

<code>\farray_item:Nn</code> ★	<code>\farray_item:Nn <farray var> {<position>}</code>
--------------------------------	--

`\farray_item_to_tl:Nn` ★

New: 2018-05-05

Applies `\fp_use:N` or `\fp_to_tl:N` (respectively) to the floating point entry stored at the (integer expression) *<position>* in the *<floating point array variable>*. If the *<position>* is not between 1 and the `\farray_count:N`, an error occurs.

Part XXV

The l3sort package

Sorting functions

1 Controlling sorting

L^AT_EX3 comes with a facility to sort list variables (sequences, token lists, or comma-lists) according to some user-defined comparison. For instance,

```
\clist_set:Nn \l_foo_clist { 3 , 01 , -2 , 5 , +1 }
\clist_sort:Nn \l_foo_clist
{
  \int_compare:nNnTF { #1 } > { #2 }
  { \sort_return_swapped: }
  { \sort_return_same: }
}
```

results in `\l_foo_clist` holding the values `{ -2 , 01 , +1 , 3 , 5 }` sorted in non-decreasing order.

The code defining the comparison should call `\sort_return_swapped:` if the two items given as `#1` and `#2` are not in the correct order, and otherwise it should call `\sort_return_same:` to indicate that the order of this pair of items should not be changed.

For instance, a *comparison code* consisting only of `\sort_return_same:` with no test yields a trivial sort: the final order is identical to the original order. Conversely, using a *comparison code* consisting only of `\sort_return_swapped:` reverses the list (in a fairly inefficient way).

T_EXhackers note: The current implementation is limited to sorting approximately 20000 items (40000 in LuaT_EX), depending on what other packages are loaded.

Internally, the code from l3sort stores items in `\toks` registers allocated locally. Thus, the *comparison code* should not call `\newtoks` or other commands that allocate new `\toks` registers. On the other hand, altering the value of a previously allocated `\toks` register is not a problem.

```
\sort_return_same:
\sort_return_swapped:
```

New: 2017-02-06

```
\seq_sort:Nn <seq var>
{ ... \sort_return_same: or \sort_return_swapped: ... }
```

Indicates whether to keep the order or swap the order of two items that are compared in the sorting code. Only one of the `\sort_return_...` functions should be used by the code, according to the results of some tests on the items `#1` and `#2` to be compared.

Part XXVI

The l3tl-analysis package: Analysing token lists

1 l3tl-analysis documentation

This module mostly provides internal functions for use in the l3regex module. However, it provides as a side-effect a user debugging function, very similar to the \ShowTokens macro from the ted package.

```
\tl_analysis_show:N
\tl_analysis_show:n
```

New: 2018-04-09

```
\tl_analysis_show:n {\token list}
```

Displays to the terminal the detailed decomposition of the $\langle token list \rangle$ into tokens, showing the category code of each character token, the meaning of control sequences and active characters, and the value of registers.

```
\tl_analysis_map_inline:nn
\tl_analysis_map_inline:Nn
```

New: 2018-04-09

```
\tl_analysis_map_inline:nn {\token list} {\inline function}
```

Applies the $\langle inline function \rangle$ to each individual $\langle token \rangle$ in the $\langle token list \rangle$. The $\langle inline function \rangle$ receives three arguments:

- $\langle tokens \rangle$, which both o-expand and x-expand to the $\langle token \rangle$. The detailed form of $\langle token \rangle$ may change in later releases.
- $\langle char code \rangle$, a decimal representation of the character code of the token, -1 if it is a control sequence (with $\langle catcode \rangle$ 0).
- $\langle catcode \rangle$, a capital hexadecimal digit which denotes the category code of the $\langle token \rangle$ (0: control sequence, 1: begin-group, 2: end-group, 3: math shift, 4: alignment tab, 6: parameter, 7: superscript, 8: subscript, A: space, B: letter, C:other, D:active).

As all other mappings the mapping is done at the current group level, *i.e.* any local assignments made by the $\langle inline function \rangle$ remain in effect after the loop.

Part XXVII

The `l3regex` package: Regular expressions in `TEX`

The `l3regex` package provides regular expression testing, extraction of submatches, splitting, and replacement, all acting on token lists. The syntax of regular expressions is mostly a subset of the PCRE syntax (and very close to POSIX), with some additions due to the fact that `TEX` manipulates tokens rather than characters. For performance reasons, only a limited set of features are implemented. Notably, back-references are not supported.

Let us give a few examples. After

```
\tl_set:Nn \l_my_tl { That~cat. }
\regex_replace_once:nnN { at } { is } \l_my_tl
```

the token list variable `\l_my_tl` holds the text “`This cat.`”, where the first occurrence of “`at`” was replaced by “`is`”. A more complicated example is a pattern to emphasize each word and add a comma after it:

```
\regex_replace_all:nnN { \w+ } { \c{emph}\cB\{ \0 \cE\} , } \l_my_tl
```

The `\w` sequence represents any “word” character, and `+` indicates that the `\w` sequence should be repeated as many times as possible (at least once), hence matching a word in the input token list. In the replacement text, `\0` denotes the full match (here, a word). The command `\emph` is inserted using `\c{emph}`, and its argument `\0` is put between braces `\cB\{` and `\cE\}`.

If a regular expression is to be used several times, it can be compiled once, and stored in a regex variable using `\regex_const:Nn`. For example,

```
\regex_const:Nn \c_foo_regex { \c{begin} \cB. (\c[~BE].*) \cE. }
```

stores in `\c_foo_regex` a regular expression which matches the starting marker for an environment: `\begin`, followed by a begin-group token (`\cB.`), then any number of tokens which are neither begin-group nor end-group character tokens (`\c[~BE].*`), ending with an end-group token (`\cE.`). As explained in the next section, the parentheses “capture” the result of `\c[~BE].*`, giving us access to the name of the environment when doing replacements.

1 Syntax of regular expressions

We start with a few examples, and encourage the reader to apply `\regex_show:n` to these regular expressions.

- `Cat` matches the word “Cat” capitalized in this way, but also matches the beginning of the word “Cattle”: use `\bCat\b` to match a complete word only.
- `[abc]` matches one letter among “a”, “b”, “c”; the pattern `(a|b|c)` matches the same three possible letters (but see the discussion of submatches below).
- `[A-Za-z]*` matches any number (due to the quantifier `*`) of Latin letters (not accented).

- `\c{[A-Za-z]*}` matches a control sequence made of Latin letters.
- `_[^_]*_` matches an underscore, any number of characters other than underscore, and another underscore; it is equivalent to `_.*?_` where `.` matches arbitrary characters and the lazy quantifier `*?` means to match as few characters as possible, thus avoiding matching underscores.
- `[\+|-]?[d+]` matches an explicit integer with at most one sign.
- `[\+|-_]*[d+_]*` matches an explicit integer with any number of `+` and `-` signs, with spaces allowed except within the mantissa, and surrounded by spaces.
- `[\+|-_]*(\d+|\d*\.\d+)_*` matches an explicit integer or decimal number; using `[.,]` instead of `\.` would allow the comma as a decimal marker.
- `[\+|-_]*(\d+|\d*\.\d+)_*((?i)pt|in|[cem]m|ex|[bs]p|[dn]d|[pcn]c)_*` matches an explicit dimension with any unit that T_EX knows, where `(?i)` means to treat lowercase and uppercase letters identically.
- `[\+|-_]*((?i)nan|inf|(\d+|\d*\.\d+)_*e[\+|-_] *[d+]?)_*` matches an explicit floating point number or the special values `nan` and `inf` (with signs and spaces allowed).
- `[\+|-_]*(\d+|\dC.)_*` matches an explicit integer or control sequence (without checking whether it is an integer variable).
- `\G.*?\K` at the beginning of a regular expression matches and discards (due to `\K`) everything between the end of the previous match (`\G`) and what is matched by the rest of the regular expression; this is useful in `\regex_replace_all:nnN` when the goal is to extract matches or submatches in a finer way than with `\regex_extract_all:nnN`.

While it is impossible for a regular expression to match only integer expressions, `[\+|-\(\)*\d+\)*(\+|-*/)[\+|-\(\)*\d+\)\]*` matches among other things all valid integer expressions (made only with explicit integers). One should follow it with further testing.

Most characters match exactly themselves, with an arbitrary category code. Some characters are special and must be escaped with a backslash (*e.g.*, `*` matches a star character). Some escape sequences of the form backslash-letter also have a special meaning (for instance `\d` matches any digit). As a rule,

- every alphanumeric character (`A-Z`, `a-z`, `0-9`) matches exactly itself, and should not be escaped, because `\A`, `\B`, ... have special meanings;
- non-alphanumeric printable ascii characters can (and should) always be escaped: many of them have special meanings (*e.g.*, use `\(`, `\)`, `\?`, `\.`);
- spaces should always be escaped (even in character classes);
- any other character may be escaped or not, without any effect: both versions match exactly that character.

Note that these rules play nicely with the fact that many non-alphanumeric characters are difficult to input into T_EX under normal category codes. For instance, `\abc%` matches the characters `\abc%` (with arbitrary category codes), but does not match the control sequence `\abc` followed by a percent character. Matching control sequences can be done using the `\c{<regex>}` syntax (see below).

Any special character which appears at a place where its special behaviour cannot apply matches itself instead (for instance, a quantifier appearing at the beginning of a string), after raising a warning.

Characters.

`\x{hh...}` Character with hex code `hh...`

`\xhh` Character with hex code `hh`.

`\a` Alarm (hex 07).

`\e` Escape (hex 1B).

`\f` Form-feed (hex 0C).

`\n` New line (hex 0A).

`\r` Carriage return (hex 0D).

`\t` Horizontal tab (hex 09).

Character types.

`.` A single period matches any token.

`\d` Any decimal digit.

`\h` Any horizontal space character, equivalent to `[\ \^^I]`: space and tab.

`\s` Any space character, equivalent to `[\ \^^I\^^J\^^L\^^M]`.

`\v` Any vertical space character, equivalent to `[\^^J\^^K\^^L\^^M]`. Note that `\^^K` is a vertical space, but not a space, for compatibility with Perl.

`\w` Any word character, *i.e.*, alphanumerics and underscore, equivalent to the explicit class `[A-Za-z0-9_]`.

`\D` Any token not matched by `\d`.

`\H` Any token not matched by `\h`.

`\N` Any token other than the `\n` character (hex 0A).

`\S` Any token not matched by `\s`.

`\V` Any token not matched by `\v`.

`\W` Any token not matched by `\w`.

Of those, `.`, `\D`, `\H`, `\N`, `\S`, `\V`, and `\W` match arbitrary control sequences.

Character classes match exactly one token in the subject.

`[...]` Positive character class. Matches any of the specified tokens.

[**^...**] Negative character class. Matches any token other than the specified characters.

x-y Within a character class, this denotes a range (can be used with escaped characters).

[:**<name>**:] Within a character class (one more set of brackets), this denotes the POSIX character class **<name>**, which can be **alnum**, **alpha**, **ascii**, **blank**, **cntrl**, **digit**, **graph**, **lower**, **print**, **punct**, **space**, **upper**, **word**, or **xdigit**.

[:**~<name>**:] Negative POSIX character class.

For instance, [**a-oq-z\cC.**] matches any lowercase latin letter except **p**, as well as control sequences (see below for a description of **\c**).

Quantifiers (repetition).

? 0 or 1, greedy.

?? 0 or 1, lazy.

***** 0 or more, greedy.

***?** 0 or more, lazy.

+ 1 or more, greedy.

+? 1 or more, lazy.

{n} Exactly *n*.

{n,} *n* or more, greedy.

{n,}? *n* or more, lazy.

{n,m} At least *n*, no more than *m*, greedy.

{n,m}? At least *n*, no more than *m*, lazy.

Anchors and simple assertions.

\b Word boundary: either the previous token is matched by **\w** and the next by **\W**, or the opposite. For this purpose, the ends of the token list are considered as **\W**.

\B Not a word boundary: between two **\w** tokens or two **\W** tokens (including the boundary).

^ or **\A** Start of the subject token list.

\$, **\Z** or **\z** End of the subject token list.

\G Start of the current match. This is only different from **^** in the case of multiple matches: for instance **\regex_count:nnN { \G a } { aaba } \l_tmpa_int** yields 2, but replacing **\G** by **^** would result in **\l_tmpa_int** holding the value 1.

Alternation and capturing groups.

A|B|C Either one of **A**, **B**, or **C**.

(...) Capturing group.

(?:...) Non-capturing group.

(?<|...)) Non-capturing group which resets the group number for capturing groups in each alternative. The following group is numbered with the first unused group number.

The `\c` escape sequence allows to test the category code of tokens, and match control sequences. Each character category is represented by a single uppercase letter:

- C for control sequences;
- B for begin-group tokens;
- E for end-group tokens;
- M for math shift;
- T for alignment tab tokens;
- P for macro parameter tokens;
- U for superscript tokens (up);
- D for subscript tokens (down);
- S for spaces;
- L for letters;
- O for others; and
- A for active characters.

The `\c` escape sequence is used as follows.

`\c{<regex>}` A control sequence whose *cname* matches the *<regex>*, anchored at the beginning and end, so that `\c{begin}` matches exactly `\begin`, and nothing else.

`\cX` Applies to the next object, which can be a character, character property, class, or group, and forces this object to only match tokens with category **X** (any of CBEMTPUDSLOA). For instance, `\cL[A-Z\d]` matches uppercase letters and digits of category code letter, `\cC.` matches any control sequence, and `\cO(abc)` matches `abc` where each character has category other.

`\c[XYZ]` Applies to the next object, and forces it to only match tokens with category **X**, **Y**, or **Z** (each being any of CBEMTPUDSLOA). For instance, `\c[LSO](..)` matches two tokens of category letter, space, or other.

`\c[^XYZ]` Applies to the next object and prevents it from matching any token with category **X**, **Y**, or **Z** (each being any of CBEMTPUDSLOA). For instance, `\c[^O]\d` matches digits which have any category different from other.

The category code tests can be used inside classes; for instance, `[\cO\d \c[LO][A-F]]` matches what \TeX considers as hexadecimal digits, namely digits with category other, or uppercase letters from **A** to **F** with category either letter or other. Within a group affected by a category code test, the outer test can be overridden by a nested test: for instance, `\cL(ab\cO*cd)` matches `ab*cd` where all characters are of category letter, except `*` which has category other.

The `\u` escape sequence allows to insert the contents of a token list directly into a regular expression or a replacement, avoiding the need to escape special characters.

Namely, `\u{<tl var name>}` matches the exact contents of the token list `<tl var>`. Within a `\c{...}` control sequence matching, the `\u` escape sequence only expands its argument once, in effect performing `\tl_to_str:v`. Quantifiers are not supported directly: use a group.

The option `(?i)` makes the match case insensitive (identifying A–Z with a–z; no Unicode support yet). This applies until the end of the group in which it appears, and can be reverted using `(?-i)`. For instance, in `(?i)(a(?-i)b|c)d`, the letters `a` and `d` are affected by the `i` option. Characters within ranges and classes are affected individually: `(?i)[Y-\]` is equivalent to `[YZ\[\]yz]`, and `(?i)[^aeiou]` matches any character which is not a vowel. Neither character properties, nor `\c{...}` nor `\u{...}` are affected by the `i` option.

In character classes, only `[`, `^`, `-`, `]`, `\` and spaces are special, and should be escaped. Other non-alphanumeric characters can still be escaped without harm. Any escape sequence which matches a single character (`\d`, `\D`, *etc.*) is supported in character classes. If the first character is `^`, then the meaning of the character class is inverted; `^` appearing anywhere else in the range is not special. If the first character (possibly following a leading `^`) is `]` then it does not need to be escaped since ending the range there would make it empty. Ranges of characters can be expressed using `-`, for instance, `[\D 0–5]` and `[^6–9]` are equivalent.

Capturing groups are a means of extracting information about the match. Parenthesized groups are labelled in the order of their opening parenthesis, starting at 1. The contents of those groups corresponding to the “best” match (leftmost longest) can be extracted and stored in a sequence of token lists using for instance `\regex_extract_once:nnTF`.

The `\K` escape sequence resets the beginning of the match to the current position in the token list. This only affects what is reported as the full match. For instance,

```
\regex_extract_all:nnN { a \K . } { a123aaxyz } \l_foo_seq
```

results in `\l_foo_seq` containing the items `{1}` and `{a}`: the true matches are `{a1}` and `{aa}`, but they are trimmed by the use of `\K`. The `\K` command does not affect capturing groups: for instance,

```
\regex_extract_once:nnN { (. \K c)+ \d } { acbc3 } \l_foo_seq
```

results in `\l_foo_seq` containing the items `{c3}` and `{bc}`: the true match is `{acbc3}`, with first submatch `{bc}`, but `\K` resets the beginning of the match to the last position where it appears.

2 Syntax of the replacement text

Most of the features described in regular expressions do not make sense within the replacement text. Backslash introduces various special constructions, described further below:

- `\0` is the whole match;
- `\1` is the submatch that was matched by the first (capturing) group `(...)`; similarly for `\2`, ..., `\9` and `\g{<number>}`;
- `_` inserts a space (spaces are ignored when not escaped);

- `\a, \e, \f, \n, \r, \t, \xhh, \x{hhh}` correspond to single characters as in regular expressions;
- `\c{<cs name>}` inserts a control sequence;
- `\c{<category>}<character>` (see below);
- `\u{<tl var name>}` inserts the contents of the `<tl var>` (see below).

Characters other than backslash and space are simply inserted in the result (but since the replacement text is first converted to a string, one should also escape characters that are special for T_EX, for instance use `\#`). Non-alphanumeric characters can always be safely escaped with a backslash.

For instance,

```
\tl_set:Nn \l_my_tl { Hello,~world! }
\regex_replace_all:nnN { ([er]?l|o) . } { (\0--\1) } \l_my_tl
```

results in `\l_my_tl` holding `H(e1l--e1)(o,--o) w(or--o)(ld--l)!`

The submatches are numbered according to the order in which the opening parenthesis of capturing groups appear in the regular expression to match. The n -th submatch is empty if there are fewer than n capturing groups or for capturing groups that appear in alternatives that were not used for the match. In case a capturing group matches several times during a match (due to quantifiers) only the last match is used in the replacement text. Submatches always keep the same category codes as in the original token list.

The characters inserted by the replacement have category code 12 (other) by default, with the exception of space characters. Spaces inserted through `_` have category code 10, while spaces inserted through `\x20` or `\x{20}` have category code 12. The escape sequence `\c` allows to insert characters with arbitrary category codes, as well as control sequences.

`\cX(...)` Produces the characters “...” with category `X`, which must be one of `CBEMTPUDSLOA` as in regular expressions. Parentheses are optional for a single character (which can be an escape sequence). When nested, the innermost category code applies, for instance `\cL(Hello\cS\ world)!` gives this text with standard category codes.

`\c{<text>}` Produces the control sequence with csname `<text>`. The `<text>` may contain references to the submatches `\0`, `\1`, and so on, as in the example for `\u` below.

The escape sequence `\u{<tl var name>}` allows to insert the contents of the token list with name `<tl var name>` directly into the replacement, giving an easier control of category codes. When nested in `\c{...}` and `\u{...}` constructions, the `\u` and `\c` escape sequences perform `\tl_to_str:v`, namely extract the value of the control sequence and turn it into a string. Matches can also be used within the arguments of `\c` and `\u`. For instance,

```
\tl_set:Nn \l_my_one_tl { first }
\tl_set:Nn \l_my_two_tl { \emph{second} }
\tl_set:Nn \l_my_tl { one , two , one , one }
\regex_replace_all:nnN { [,]+ } { \u{1_my_\0_tl} } \l_my_tl
```

results in `\l_my_tl` holding `first,\emph{second},first,first`.

3 Pre-compiling regular expressions

If a regular expression is to be used several times, it is better to compile it once rather than doing it each time the regular expression is used. The compiled regular expression is stored in a variable. All of the `l3regex` module's functions can be given their regular expression argument either as an explicit string or as a compiled regular expression.

`\regex_new:N`

New: 2017-05-26

`\regex_new:N` $\langle regex\ var \rangle$

Creates a new $\langle regex\ var \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle regex\ var \rangle$ is initially such that it never matches.

`\regex_set:Nn`
`\regex_gset:Nn`
`\regex_const:Nn`

New: 2017-05-26

`\regex_set:Nn` $\langle regex\ var \rangle$ $\{ \langle regex \rangle \}$

Stores a compiled version of the $\langle regular\ expression \rangle$ in the $\langle regex\ var \rangle$. For instance, this function can be used as

```
\regex_new:N \l_my_regex
\regex_set:Nn \l_my_regex { my\ (simple\ )? reg(ex|ular\ expression) }
```

The assignment is local for `\regex_set:Nn` and global for `\regex_gset:Nn`. Use `\regex_const:Nn` for compiled expressions which never change.

`\regex_show:n`
`\regex_show:N`

New: 2017-05-26

`\regex_show:n` $\{ \langle regex \rangle \}$

Shows how `l3regex` interprets the $\langle regex \rangle$. For instance, `\regex_show:n {\A X|Y}` shows

```
+--branch
  anchor at start (\A)
  char code 88
+--branch
  char code 89
```

indicating that the anchor `\A` only applies to the first branch: the second branch is not anchored to the beginning of the match.

4 Matching

All regular expression functions are available in both `:n` and `:N` variants. The former require a “standard” regular expression, while the later require a compiled expression as generated by `\regex_(g)set:Nn`.

`\regex_match:nnTF`
`\regex_match:NnTF`

New: 2017-05-26

`\regex_match:nnTF` $\{ \langle regex \rangle \}$ $\{ \langle token\ list \rangle \}$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$

Tests whether the $\langle regular\ expression \rangle$ matches any part of the $\langle token\ list \rangle$. For instance,

```
\regex_match:nnTF { b [cde]* } { abecdxcx } { TRUE } { FALSE }
\regex_match:nnTF { [b-dq-w] } { example } { TRUE } { FALSE }
```

leaves TRUE then FALSE in the input stream.

<code>\regex_count:nnN</code>
<code>\regex_count:NnN</code>
New: 2017-05-26

`\regex_count:nnN` $\{ \langle \textit{regex} \rangle \}$ $\{ \langle \textit{token list} \rangle \}$ $\langle \textit{int var} \rangle$

Sets $\langle \textit{int var} \rangle$ within the current T_EX group level equal to the number of times $\langle \textit{regular expression} \rangle$ appears in $\langle \textit{token list} \rangle$. The search starts by finding the left-most longest match, respecting greedy and lazy (non-greedy) operators. Then the search starts again from the character following the last character of the previous match, until reaching the end of the token list. Infinite loops are prevented in the case where the regular expression can match an empty token list: then we count one match between each pair of characters. For instance,

```
\int_new:N \l_foo_int
\regex_count:nnN { (b+|c) } { abbababcb } \l_foo_int
```

results in `\l_foo_int` taking the value 5.

5 Submatch extraction

<code>\regex_extract_once:nnN</code>
<code>\regex_extract_once:nnNTF</code>
<code>\regex_extract_once:NnN</code>
<code>\regex_extract_once:NnNTF</code>
New: 2017-05-26

`\regex_extract_once:nnN` $\{ \langle \textit{regex} \rangle \}$ $\{ \langle \textit{token list} \rangle \}$ $\langle \textit{seq var} \rangle$
`\regex_extract_once:nnNTF` $\{ \langle \textit{regex} \rangle \}$ $\{ \langle \textit{token list} \rangle \}$ $\langle \textit{seq var} \rangle$ $\{ \langle \textit{true code} \rangle \}$ $\{ \langle \textit{false code} \rangle \}$

Finds the first match of the $\langle \textit{regular expression} \rangle$ in the $\langle \textit{token list} \rangle$. If it exists, the match is stored as the first item of the $\langle \textit{seq var} \rangle$, and further items are the contents of capturing groups, in the order of their opening parenthesis. The $\langle \textit{seq var} \rangle$ is assigned locally. If there is no match, the $\langle \textit{seq var} \rangle$ is cleared. The testing versions insert the $\langle \textit{true code} \rangle$ into the input stream if a match was found, and the $\langle \textit{false code} \rangle$ otherwise.

For instance, assume that you type

```
\regex_extract_once:nnNTF { \A(La)?TeX(!*)\Z } { LaTeX!!! } \l_foo_seq
{ true } { false }
```

Then the regular expression (anchored at the start with `\A` and at the end with `\Z`) must match the whole token list. The first capturing group, `(La)?`, matches `La`, and the second capturing group, `(!*)`, matches `!!!`. Thus, `\l_foo_seq` contains as a result the items `{LaTeX!!!}`, `{La}`, and `{!!!}`, and the `true` branch is left in the input stream. Note that the n -th item of `\l_foo_seq`, as obtained using `\seq_item:Nn`, correspond to the submatch numbered $(n - 1)$ in functions such as `\regex_replace_once:nnN`.

<code>\regex_extract_all:nnN</code>
<code>\regex_extract_all:nnNTF</code>
<code>\regex_extract_all:NnN</code>
<code>\regex_extract_all:NnNTF</code>
New: 2017-05-26

`\regex_extract_all:nnN` $\{ \langle \textit{regex} \rangle \}$ $\{ \langle \textit{token list} \rangle \}$ $\langle \textit{seq var} \rangle$
`\regex_extract_all:nnNTF` $\{ \langle \textit{regex} \rangle \}$ $\{ \langle \textit{token list} \rangle \}$ $\langle \textit{seq var} \rangle$ $\{ \langle \textit{true code} \rangle \}$ $\{ \langle \textit{false code} \rangle \}$

Finds all matches of the $\langle \textit{regular expression} \rangle$ in the $\langle \textit{token list} \rangle$, and stores all the submatch information in a single sequence (concatenating the results of multiple `\regex_extract_once:nnN` calls). The $\langle \textit{seq var} \rangle$ is assigned locally. If there is no match, the $\langle \textit{seq var} \rangle$ is cleared. The testing versions insert the $\langle \textit{true code} \rangle$ into the input stream if a match was found, and the $\langle \textit{false code} \rangle$ otherwise. For instance, assume that you type

```
\regex_extract_all:nnNTF { \w+ } { Hello,~world! } \l_foo_seq
{ true } { false }
```

Then the regular expression matches twice, the resulting sequence contains the two items `{Hello}` and `{world}`, and the `true` branch is left in the input stream.

```
\regex_split:nnN
\regex_split:nnNTF
\regex_split:NnN
\regex_split:NnNTF
```

New: 2017-05-26

```
\regex_split:nnN {<regular expression>} {<token list>} <seq var>
\regex_split:nnNTF {<regular expression>} {<token list>} <seq var> {<true code>}
{<false code>}
```

Splits the *<token list>* into a sequence of parts, delimited by matches of the *<regular expression>*. If the *<regular expression>* has capturing groups, then the token lists that they match are stored as items of the sequence as well. The assignment to *<seq var>* is local. If no match is found the resulting *<seq var>* has the *<token list>* as its sole item. If the *<regular expression>* matches the empty token list, then the *<token list>* is split into single tokens. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise. For example, after

```
\seq_new:N \l_path_seq
\regex_split:nnNTF { / } { the/path/for/this/file.tex } \l_path_seq
{ true } { false }
```

the sequence `\l_path_seq` contains the items `{the}`, `{path}`, `{for}`, `{this}`, and `{file.tex}`, and the `true` branch is left in the input stream.

6 Replacement

```
\regex_replace_once:nnN
\regex_replace_once:nnNTF
\regex_replace_once:NnN
\regex_replace_once:NnNTF
```

New: 2017-05-26

```
\regex_replace_once:nnN {<regular expression>} {<replacement>} <tl var>
\regex_replace_once:nnNTF {<regular expression>} {<replacement>} <tl var> {<true
code>} {<false code>}
```

Searches for the *<regular expression>* in the *<token list>* and replaces the first match with the *<replacement>*. The result is assigned locally to *<tl var>*. In the *<replacement>*, `\0` represents the full match, `\1` represent the contents of the first capturing group, `\2` of the second, *etc.*

```
\regex_replace_all:nnN
\regex_replace_all:nnNTF
\regex_replace_all:NnN
\regex_replace_all:NnNTF
```

New: 2017-05-26

```
\regex_replace_all:nnN {<regular expression>} {<replacement>} <tl var>
\regex_replace_all:nnNTF {<regular expression>} {<replacement>} <tl var> {<true
code>} {<false code>}
```

Replaces all occurrences of the *<regular expression>* in the *<token list>* by the *<replacement>*, where `\0` represents the full match, `\1` represent the contents of the first capturing group, `\2` of the second, *etc.* Every match is treated independently, and matches cannot overlap. The result is assigned locally to *<tl var>*.

7 Constants and variables

```
\l_tmpa_regex
\l_tmpb_regex
```

New: 2017-12-11

Scratch regex for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

```
\g_tmpa_regex
\g_tmpb_regex
```

New: 2017-12-11

Scratch regex for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

8 Bugs, misfeatures, future work, and other possibilities

The following need to be done now.

- Rewrite the documentation in a more ordered way, perhaps add a BNF?
Additional error-checking to come.
- Clean up the use of messages.
- Cleaner error reporting in the replacement phase.
- Add tracing information.
- Detect attempts to use back-references and other non-implemented syntax.
- Test for the maximum register `\c_max_register_int`.
- Find out whether the fact that `\W` and friends match the end-marker leads to bugs.
Possibly update `__regex_item_reverse:n`.
- The empty `cs` should be matched by `\c{}`, not by `\c{csname.?endcsname\s?}`.

Code improvements to come.

- Shift arrays so that the useful information starts at position 1.
- Only build `\c{...}` once.
- Use arrays for the left and right state stacks when compiling a regex.
- Should `__regex_action_free_group:n` only be used for greedy `{n,}` quantifier? (I think not.)
- Quantifiers for `\u` and assertions.
- When matching, keep track of an explicit stack of `current_state` and `current_submatches`.
- If possible, when a state is reused by the same thread, kill other subthreads.
- Use an array rather than `\l__regex_balance_tl` to build the function `__regex_replacement_balance_one_match:n`.
- Reduce the number of epsilon-transitions in alternatives.
- Optimize simple strings: use less states (`abcade` should give two states, for `abc` and `ade`). [Does that really make sense?]
- Optimize groups with no alternative.
- Optimize states with a single `__regex_action_free:n`.
- Optimize the use of `__regex_action_success:` by inserting it in state 2 directly instead of having an extra transition.
- Optimize the use of `\int_step_...` functions.

- Groups don't capture within regexes for csnames; optimize and document.
- Better “show” for anchors, properties, and catcode tests.
- Does \K really need a new state for itself?
- When compiling, use a boolean `in_cs` and less magic numbers.
- Instead of checking whether the character is special or alphanumeric using its character code, check if it is special in regexes with `\cs_if_exist` tests.

The following features are likely to be implemented at some point in the future.

- General look-ahead/behind assertions.
- Regex matching on external files.
- Conditional subpatterns with look ahead/behind: “if what follows is [...], then [...]”.
- `(*..)` and `(?..)` sequences to set some options.
- UTF-8 mode for pdfTeX.
- Newline conventions are not done. In particular, we should have an option for `.` not to match newlines. Also, `\A` should differ from `^`, and `\Z`, `\z` and `$` should differ.
- Unicode properties: `\p{..}` and `\P{..}`; `\X` which should match any “extended” Unicode sequence. This requires to manipulate a lot of data, probably using tree-boxes.
- Provide a syntax such as `\ur{1_my_regex}` to use an already-compiled regex in a more complicated regex. This makes regexes more easily composable.
- Allowing `\u{1_my_t1}` in more places, for instance as the number of repetitions in a quantifier.

The following features of PCRE or Perl may or may not be implemented.

- Callout with `(?C...)` or other syntax: some internal code changes make that possible, and it can be useful for instance in the replacement code to stop a regex replacement when some marker has been found; this raises the question of a potential `\regex_break`: and then of playing well with `\t1_map_break`: called from within the code in a regex. It also raises the question of nested calls to the regex machinery, which is a problem since `\fontdimen` are global.
- Conditional subpatterns (other than with a look-ahead or look-behind condition): this is non-regular, isn't it?
- Named subpatterns: TeX programmers have lived so far without any need for named macro parameters.

The following features of PCRE or Perl will definitely not be implemented.

- Back-references: non-regular feature, this requires backtracking, which is prohibitively slow.

- Recursion: this is a non-regular feature.
- Atomic grouping, possessive quantifiers: those tools, mostly meant to fix catastrophic backtracking, are unnecessary in a non-backtracking algorithm, and difficult to implement.
- Subroutine calls: this syntactic sugar is difficult to include in a non-backtracking algorithm, in particular because the corresponding group should be treated as atomic.
- Backtracking control verbs: intrinsically tied to backtracking.
- `\ddd`, matching the character with octal code `ddd`: we already have `\x{...}` and the syntax is confusingly close to what we could have used for backreferences (`\1`, `\2`, ...), making it harder to produce useful error message.
- `\cx`, similar to $\mathrm{T}_{\mathrm{E}}\mathrm{X}$'s own `\^^x`.
- Comments: $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ already has its own system for comments.
- `\Q...\E` escaping: this would require to read the argument verbatim, which is not in the scope of this module.
- `\C` single byte in UTF-8 mode: $\mathrm{X}_{\mathrm{Y}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ and $\mathrm{LuaT}_{\mathrm{E}}\mathrm{X}$ serve us characters directly, and splitting those into bytes is tricky, encoding dependent, and most likely not useful anyways.

Part XXVIII

The l3box package

Boxes

There are three kinds of box operations: horizontal mode denoted with prefix `\hbox_`, vertical mode with prefix `\vbox_`, and the generic operations working in both modes with prefix `\box_`.

1 Creating and initialising boxes

<code>\box_new:N</code>	<code>\box_new:N</code> $\langle box \rangle$
<code>\box_new:c</code>	Creates a new $\langle box \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle box \rangle$ is initially void.

<code>\box_clear:N</code>	<code>\box_clear:N</code> $\langle box \rangle$
<code>\box_clear:c</code>	Clears the content of the $\langle box \rangle$ by setting the box equal to <code>\c_empty_box</code> .
<code>\box_gclear:N</code>	
<code>\box_gclear:c</code>	

<code>\box_clear_new:N</code>	<code>\box_clear_new:N</code> $\langle box \rangle$
<code>\box_clear_new:c</code>	Ensures that the $\langle box \rangle$ exists globally by applying <code>\box_new:N</code> if necessary, then applies <code>\box_(g)clear:N</code> to leave the $\langle box \rangle$ empty.
<code>\box_gclear_new:N</code>	
<code>\box_gclear_new:c</code>	

<code>\box_set_eq:NN</code>	<code>\box_set_eq:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$
<code>\box_set_eq:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$.
<code>\box_gset_eq:NN</code>	
<code>\box_gset_eq:(cN Nc cc)</code>	

<code>\box_if_exist_p:N</code> *	<code>\box_if_exist_p:N</code> $\langle box \rangle$
<code>\box_if_exist_p:c</code> *	<code>\box_if_exist:NTF</code> $\langle box \rangle$ $\{ \langle true\ code \rangle \} \{ \langle false\ code \rangle \}$
<code>\box_if_exist:NTF</code> *	Tests whether the $\langle box \rangle$ is currently defined. This does not check that the $\langle box \rangle$ really is a box.
<code>\box_if_exist:cTF</code> *	

New: 2012-03-03

2 Using boxes

<code>\box_use:N</code>	<code>\box_use:N</code> $\langle box \rangle$
<code>\box_use:c</code>	Inserts the current content of the $\langle box \rangle$ onto the current list for typesetting. An error is raised if the variable does not exist or if it is invalid.

T_EXhackers note: This is the T_EX primitive `\copy`.

<hr/> <code>\box_move_right:nn</code> <hr/>	<code>\box_move_right:nn {<dimexpr>} {<box function>}</code>
<code>\box_move_left:nn</code> <hr/>	This function operates in vertical mode, and inserts the material specified by the <i><box function></i> such that its reference point is displaced horizontally by the given <i><dimexpr></i> from the reference point for typesetting, to the right or left as appropriate. The <i><box function></i> should be a box operation such as <code>\box_use:N \<box></code> or a “raw” box specification such as <code>\vbox:n { xyz }</code> .

<hr/> <code>\box_move_up:nn</code> <hr/>	<code>\box_move_up:nn {<dimexpr>} {<box function>}</code>
<code>\box_move_down:nn</code> <hr/>	This function operates in horizontal mode, and inserts the material specified by the <i><box function></i> such that its reference point is displaced vertically by the given <i><dimexpr></i> from the reference point for typesetting, up or down as appropriate. The <i><box function></i> should be a box operation such as <code>\box_use:N \<box></code> or a “raw” box specification such as <code>\vbox:n { xyz }</code> .

3 Measuring and setting box dimensions

<hr/> <code>\box_dp:N</code> <hr/>	<code>\box_dp:N <box></code>
<code>\box_dp:c</code> <hr/>	Calculates the depth (below the baseline) of the <i><box></i> in a form suitable for use in a <i><dimension expression></i> .

TeXhackers note: This is the TeX primitive `\dp`.

<hr/> <code>\box_ht:N</code> <hr/>	<code>\box_ht:N <box></code>
<code>\box_ht:c</code> <hr/>	Calculates the height (above the baseline) of the <i><box></i> in a form suitable for use in a <i><dimension expression></i> .

TeXhackers note: This is the TeX primitive `\ht`.

<hr/> <code>\box_wd:N</code> <hr/>	<code>\box_wd:N <box></code>
<code>\box_wd:c</code> <hr/>	Calculates the width of the <i><box></i> in a form suitable for use in a <i><dimension expression></i> .

TeXhackers note: This is the TeX primitive `\wd`.

<hr/> <code>\box_set_dp:Nn</code> <hr/>	<code>\box_set_dp:Nn <box> {<dimension expression>}</code>
<code>\box_set_dp:cn</code> <hr/>	Set the depth (below the baseline) of the <i><box></i> to the value of the <i>{<dimension expression>}</i> .
<code>\box_gset_dp:Nn</code> <hr/>	
<code>\box_gset_dp:cn</code> <hr/>	

Updated: 2019-01-22

<hr/> <code>\box_set_ht:Nn</code> <hr/>	<code>\box_set_ht:Nn <box> {<dimension expression>}</code>
<code>\box_set_ht:cn</code> <hr/>	Set the height (above the baseline) of the <i><box></i> to the value of the <i>{<dimension expression>}</i> .
<code>\box_gset_ht:Nn</code> <hr/>	
<code>\box_gset_ht:cn</code> <hr/>	

Updated: 2019-01-22

<code>\box_set_wd:Nn</code>	<code>\box_set_wd:Nn <box> {<dimension expression>}</code>
<code>\box_set_wd:cn</code>	
<code>\box_gset_wd:Nn</code>	Set the width of the <code><box></code> to the value of the <code>{<dimension expression>}</code> .
<code>\box_gset_wd:cn</code>	

Updated: 2019-01-22

4 Box conditionals

<code>\box_if_empty_p:N</code> *	<code>\box_if_empty_p:N <box></code>
<code>\box_if_empty_p:c</code> *	<code>\box_if_empty:NTF <box> {<true code>} {<false code>}</code>
<code>\box_if_empty:NTF</code> *	
<code>\box_if_empty:cTF</code> *	Tests if <code><box></code> is a empty (equal to <code>\c_empty_box</code>).

<code>\box_if_horizontal_p:N</code> *	<code>\box_if_horizontal_p:N <box></code>
<code>\box_if_horizontal_p:c</code> *	<code>\box_if_horizontal:NTF <box> {<true code>} {<false code>}</code>
<code>\box_if_horizontal:NTF</code> *	
<code>\box_if_horizontal:cTF</code> *	Tests if <code><box></code> is a horizontal box.

<code>\box_if_vertical_p:N</code> *	<code>\box_if_vertical_p:N <box></code>
<code>\box_if_vertical_p:c</code> *	<code>\box_if_vertical:NTF <box> {<true code>} {<false code>}</code>
<code>\box_if_vertical:NTF</code> *	
<code>\box_if_vertical:cTF</code> *	Tests if <code><box></code> is a vertical box.

5 The last box inserted

<code>\box_set_to_last:N</code>	<code>\box_set_to_last:N <box></code>
<code>\box_set_to_last:c</code>	
<code>\box_gset_to_last:N</code>	Sets the <code><box></code> equal to the last item (box) added to the current partial list, removing the item from the list at the same time. When applied to the main vertical list, the <code><box></code> is always void as it is not possible to recover the last added item.
<code>\box_gset_to_last:c</code>	

6 Constant boxes

<code>\c_empty_box</code>	This is a permanently empty box, which is neither set as horizontal nor vertical.
---------------------------	---

Updated: 2012-11-04

TeXhackers note: At the TeX level this is a void box.

7 Scratch boxes

`\l_tmpa_box`
`\l_tmpb_box`

Updated: 2012-11-04

Scratch boxes for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_box`
`\g_tmpb_box`

Scratch boxes for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

8 Viewing box contents

`\box_show:N`
`\box_show:c`

Updated: 2012-05-11

`\box_show:N` $\langle box \rangle$

Shows full details of the content of the $\langle box \rangle$ in the terminal.

`\box_show:Nnn`
`\box_show:cnn`

New: 2012-05-11

`\box_show:Nnn` $\langle box \rangle$ $\{\langle intexpr_1 \rangle\}$ $\{\langle intexpr_2 \rangle\}$

Display the contents of $\langle box \rangle$ in the terminal, showing the first $\langle intexpr_1 \rangle$ items of the box, and descending into $\langle intexpr_2 \rangle$ group levels.

`\box_log:N`
`\box_log:c`

New: 2012-05-11

`\box_log:N` $\langle box \rangle$

Writes full details of the content of the $\langle box \rangle$ to the log.

`\box_log:Nnn`
`\box_log:cnn`

New: 2012-05-11

`\box_log:Nnn` $\langle box \rangle$ $\{\langle intexpr_1 \rangle\}$ $\{\langle intexpr_2 \rangle\}$

Writes the contents of $\langle box \rangle$ to the log, showing the first $\langle intexpr_1 \rangle$ items of the box, and descending into $\langle intexpr_2 \rangle$ group levels.

9 Boxes and color

All L^AT_EX3 boxes are “color safe”: a color set inside the box stops applying after the end of the box has occurred.

10 Horizontal mode boxes

`\hbox:n`

Updated: 2017-04-05

`\hbox:n` $\{\langle contents \rangle\}$

Typesets the $\langle contents \rangle$ into a horizontal box of natural width and then includes this box in the current list for typesetting.

<hr/> <code>\hbox_to_wd:nn</code> <hr/>	<code>\hbox_to_wd:nn {<dimexpr>} {<contents>}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of width $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting.
<hr/> <code>\hbox_to_zero:n</code> <hr/>	<code>\hbox_to_zero:n {<contents>}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width and then includes this box in the current list for typesetting.
<hr/> <code>\hbox_set:Nn</code> <code>\hbox_set:cn</code> <code>\hbox_gset:Nn</code> <code>\hbox_gset:cn</code> <hr/>	<code>\hbox_set:Nn <box> {<contents>}</code> Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$.
Updated: 2017-04-05	
<hr/> <code>\hbox_set_to_wd:Nnn</code> <code>\hbox_set_to_wd:cnn</code> <code>\hbox_gset_to_wd:Nnn</code> <code>\hbox_gset_to_wd:cnn</code> <hr/>	<code>\hbox_set_to_wd:Nnn <box> {<dimexpr>} {<contents>}</code> Typesets the $\langle contents \rangle$ to the width given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$.
Updated: 2017-04-05	
<hr/> <code>\hbox_overlap_right:n</code> <hr/>	<code>\hbox_overlap_right:n {<contents>}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material protrudes to the right of the insertion point.
<hr/> <code>\hbox_overlap_left:n</code> <hr/>	<code>\hbox_overlap_left:n {<contents>}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material protrudes to the left of the insertion point.
<hr/> <code>\hbox_set:Nw</code> <code>\hbox_set:cw</code> <code>\hbox_set_end:</code> <code>\hbox_gset:Nw</code> <code>\hbox_gset:cw</code> <code>\hbox_gset_end:</code> <hr/>	<code>\hbox_set:Nw <box> <contents> \hbox_set_end:</code> Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$. In contrast to <code>\hbox_set:Nn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument.
Updated: 2017-04-05	
<hr/> <code>\hbox_set_to_wd:Nnw</code> <code>\hbox_set_to_wd:cnw</code> <code>\hbox_gset_to_wd:Nnw</code> <code>\hbox_gset_to_wd:cnw</code> <hr/>	<code>\hbox_set_to_wd:Nnw <box> {<dimexpr>} <contents> \hbox_set_end:</code> Typesets the $\langle contents \rangle$ to the width given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$. In contrast to <code>\hbox_set_to_wd:Nnn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument
New: 2017-06-08	
<hr/> <code>\hbox_unpack:N</code> <code>\hbox_unpack:c</code> <hr/>	<code>\hbox_unpack:N <box></code> Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set.

T_EXhackers note: This is the T_EX primitive `\unhcopy`.

11 Vertical mode boxes

Vertical boxes inherit their baseline from their contents. The standard case is that the baseline of the box is at the same position as that of the last item added to the box. This means that the box has no depth unless the last item added to it had depth. As a result most vertical boxes have a large height value and small or zero depth. The exception are `_top` boxes, where the reference point is that of the first item added. These tend to have a large depth and small height, although the latter is typically non-zero.

<hr/> <code>\vbox:n</code> <hr/>	<code>\vbox:n {<contents>}</code>
<hr/> Updated: 2017-04-05 <hr/>	Typesets the <code><contents></code> into a vertical box of natural height and includes this box in the current list for typesetting.
<hr/> <code>\vbox_top:n</code> <hr/>	<code>\vbox_top:n {<contents>}</code>
<hr/> Updated: 2017-04-05 <hr/>	Typesets the <code><contents></code> into a vertical box of natural height and includes this box in the current list for typesetting. The baseline of the box is equal to that of the <i>first</i> item added to the box.
<hr/> <code>\vbox_to_ht:nn</code> <hr/>	<code>\vbox_to_ht:nn {<dimexpr>} {<contents>}</code>
<hr/> Updated: 2017-04-05 <hr/>	Typesets the <code><contents></code> into a vertical box of height <code><dimexpr></code> and then includes this box in the current list for typesetting.
<hr/> <code>\vbox_to_zero:n</code> <hr/>	<code>\vbox_to_zero:n {<contents>}</code>
<hr/> Updated: 2017-04-05 <hr/>	Typesets the <code><contents></code> into a vertical box of zero height and then includes this box in the current list for typesetting.
<hr/> <code>\vbox_set:Nn</code> <code>\vbox_set:cn</code> <code>\vbox_gset:Nn</code> <code>\vbox_gset:cn</code> <hr/>	<code>\vbox_set:Nn <box> {<contents>}</code> Typesets the <code><contents></code> at natural height and then stores the result inside the <code><box></code> .
<hr/> Updated: 2017-04-05 <hr/>	
<hr/> <code>\vbox_set_top:Nn</code> <code>\vbox_set_top:cn</code> <code>\vbox_gset_top:Nn</code> <code>\vbox_gset_top:cn</code> <hr/>	<code>\vbox_set_top:Nn <box> {<contents>}</code> Typesets the <code><contents></code> at natural height and then stores the result inside the <code><box></code> . The baseline of the box is equal to that of the <i>first</i> item added to the box.
<hr/> Updated: 2017-04-05 <hr/>	
<hr/> <code>\vbox_set_to_ht:Nnn</code> <code>\vbox_set_to_ht:cnn</code> <code>\vbox_gset_to_ht:Nnn</code> <code>\vbox_gset_to_ht:cnn</code> <hr/>	<code>\vbox_set_to_ht:Nnn <box> {<dimexpr>} {<contents>}</code> Typesets the <code><contents></code> to the height given by the <code><dimexpr></code> and then stores the result inside the <code><box></code> .
<hr/> Updated: 2017-04-05 <hr/>	

```

\ vbox_set:Nw
\ vbox_set:cw
\ vbox_set:end:
\ vbox_gset:Nw
\ vbox_gset:cw
\ vbox_gset:end:

```

Updated: 2017-04-05

```

\ vbox_set_to_ht:Nnw
\ vbox_set_to_ht:cnw
\ vbox_gset_to_ht:Nnw
\ vbox_gset_to_ht:cnw

```

New: 2017-06-08

```
\ vbox_set:Nw <box> <contents> \ vbox_set:end:
```

Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$. In contrast to $\backslash vbox_set:Nn$ this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument.

```
\ vbox_set_to_ht:Nnw <box> {<dimexpr>} <contents> \ vbox_set:end:
```

Typesets the $\langle contents \rangle$ to the height given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$. In contrast to $\backslash vbox_set_to_ht:Nnn$ this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument

```

\ vbox_set_split_to_ht:NNn
\ vbox_set_split_to_ht:(cNn|Ncn|ccn)
\ vbox_gset_split_to_ht:NNn
\ vbox_gset_split_to_ht:(cNn|Ncn|ccn)

```

Updated: 2018-12-29

```
\ vbox_set_split_to_ht:NNn <box1> <box2> {<dimexpr>}
```

Sets $\langle box_1 \rangle$ to contain material to the height given by the $\langle dimexpr \rangle$ by removing content from the top of $\langle box_2 \rangle$ (which must be a vertical box).

```

\ vbox_unpack:N
\ vbox_unpack:c

```

```
\ vbox_unpack:N <box>
```

Unpacks the content of the vertical $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set.

TeXhackers note: This is the TeX primitive $\backslash unvcopy$.

12 Using boxes efficiently

The functions above for using box contents work in exactly the same way as for any other expl3 variable. However, for efficiency reasons, it is also useful to have functions which *drop* box contents on use. When a box is dropped, the box becomes empty at the group level *where the box was originally set* rather than necessarily *at the current group level*. For example, with

```

\ hbox_set:Nn \l_tmpa_box { A }
\ group_begin:
  \ hbox_set:Nn \l_tmpa_box { B }
  \ group_begin:
    \ box_use_drop:N \l_tmpa_box
  \ group_end:
  \ box_show:N \l_tmpa_box
\ group_end:
\ box_show:N \l_tmpa_box

```

the first use of `\box_show:N` will show an entirely cleared (void) box, and the second will show the letter **A** in the box.

These functions should be preferred when the content of the box is no longer required after use. Note that due to the unusual scoping behaviour of `drop` functions they may be applied to both local and global boxes: the latter will naturally be set and thus cleared at a global level.

`\box_use_drop:N`
`\box_use_drop:c`

`\box_use_drop:N` $\langle box \rangle$

Inserts the current content of the $\langle box \rangle$ onto the current list for typesetting then drops the box content. An error is raised if the variable does not exist or if it is invalid. This function may be applied to local or global boxes.

T_EXhackers note: This is the `\box` primitive.

`\box_set_eq_drop:NN`
`\box_set_eq_drop:(cN|Nc|cc)`

New: 2019-01-17

`\box_set_eq_drop:NN` $\langle box_1 \rangle$ $\langle box_2 \rangle$

Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$, then drops $\langle box_2 \rangle$.

`\box_gset_eq_drop:NN`
`\box_gset_eq_drop:(cN|Nc|cc)`

New: 2019-01-17

`\box_gset_eq_drop:NN` $\langle box_1 \rangle$ $\langle box_2 \rangle$

Sets the content of $\langle box_1 \rangle$ globally equal to that of $\langle box_2 \rangle$, then drops $\langle box_2 \rangle$.

`\hbox_unpack_drop:N`
`\hbox_unpack_drop:c`

New: 2019-01-17

`\hbox_unpack_drop:N` $\langle box \rangle$

Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set. The original $\langle box \rangle$ is then dropped.

T_EXhackers note: This is the T_EX primitive `\unhbox`.

`\vbox_unpack_drop:N`
`\vbox_unpack_drop:c`

New: 2019-01-17

`\vbox_unpack_drop:N` $\langle box \rangle$

Unpacks the content of the vertical $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set. The original $\langle box \rangle$ is then dropped.

T_EXhackers note: This is the T_EX primitive `\unvbox`.

13 Affine transformations

Affine transformations are changes which (informally) preserve straight lines. Simple translations are affine transformations, but are better handled in T_EX by doing the translation first, then inserting an unmodified box. On the other hand, rotation and resizing of boxed material can best be handled by modifying boxes. These transformations are described here.

<code>\box_autosize_to_wd_and_ht:Nnn</code>	<code>\box_autosize_to_wd_and_ht:Nnn <box> {<x-size>} {<y-size>}</code>
<code>\box_autosize_to_wd_and_ht:cnn</code>	
<code>\box_gautosize_to_wd_and_ht:Nnn</code>	
<code>\box_gautosize_to_wd_and_ht:cnn</code>	

New: 2017-04-04

Updated: 2019-01-22

Resizes the $\langle box \rangle$ to fit within the given $\langle x-size \rangle$ (horizontally) and $\langle y-size \rangle$ (vertically); both of the sizes are dimension expressions. The $\langle y-size \rangle$ is the height only: it does not include any depth. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. The final size of the $\langle box \rangle$ is the smaller of $\{ \langle x-size \rangle \}$ and $\{ \langle y-size \rangle \}$, *i.e.* the result fits within the dimensions specified. Negative sizes cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*.

<code>\box_autosize_to_wd_and_ht_plus_dp:Nnn</code>	<code>\box_autosize_to_wd_and_ht_plus_dp:Nnn <box> {<x-size>}</code>
<code>\box_autosize_to_wd_and_ht_plus_dp:cnn</code>	<code>{<y-size>}</code>
<code>\box_gautosize_to_wd_and_ht_plus_dp:Nnn</code>	
<code>\box_gautosize_to_wd_and_ht_plus_dp:cnn</code>	

New: 2017-04-04

Updated: 2019-01-22

Resizes the $\langle box \rangle$ to fit within the given $\langle x-size \rangle$ (horizontally) and $\langle y-size \rangle$ (vertically); both of the sizes are dimension expressions. The $\langle y-size \rangle$ is the total vertical size (height plus depth). The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. The final size of the $\langle box \rangle$ is the smaller of $\{ \langle x-size \rangle \}$ and $\{ \langle y-size \rangle \}$, *i.e.* the result fits within the dimensions specified. Negative sizes cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*.

<code>\box_resize_to_ht:Nn</code>	<code>\box_resize_to_ht:Nn <box> {<y-size>}</code>
<code>\box_resize_to_ht:cn</code>	
<code>\box_gresize_to_ht:Nn</code>	
<code>\box_gresize_to_ht:cn</code>	

Updated: 2019-01-22

Resizes the $\langle box \rangle$ to $\langle y-size \rangle$ (vertically), scaling the horizontal size by the same amount; $\langle y-size \rangle$ is a dimension expression. The $\langle y-size \rangle$ is the height only: it does not include any depth. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative $\langle y-size \rangle$ causes the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*.

<code>\box_resize_to_ht_plus_dp:Nn</code>	<code>\box_resize_to_ht_plus_dp:Nn <box> {<y-size>}</code>
<code>\box_resize_to_ht_plus_dp:cn</code>	
<code>\box_gresize_to_ht_plus_dp:Nn</code>	
<code>\box_gresize_to_ht_plus_dp:cn</code>	

Updated: 2019-01-22

Resizes the $\langle box \rangle$ to $\langle y-size \rangle$ (vertically), scaling the horizontal size by the same amount; $\langle y-size \rangle$ is a dimension expression. The $\langle y-size \rangle$ is the total vertical size (height plus depth). The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative $\langle y-size \rangle$ causes the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*.

<code>\box_resize_to_wd:Nn</code>	<code>\box_resize_to_wd:Nn <box> {<x-size>}</code>
<code>\box_resize_to_wd:cn</code>	
<code>\box_gresize_to_wd:Nn</code>	
<code>\box_gresize_to_wd:cn</code>	

Updated: 2019-01-22

Resizes the $\langle box \rangle$ to $\langle x-size \rangle$ (horizontally), scaling the vertical size by the same amount; $\langle x-size \rangle$ is a dimension expression. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative $\langle x-size \rangle$ causes the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle x-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*.

<code>\box_resize_to_wd_and_ht:Nnn</code>	<code>\box_resize_to_wd_and_ht:Nnn <box> {<x-size>} {<y-size>}</code>
<code>\box_resize_to_wd_and_ht:cnn</code>	
<code>\box_gresize_to_wd_and_ht:Nnn</code>	
<code>\box_gresize_to_wd_and_ht:cnn</code>	

New: 2014-07-03

Updated: 2019-01-22

Resizes the $\langle box \rangle$ to $\langle x-size \rangle$ (horizontally) and $\langle y-size \rangle$ (vertically): both of the sizes are dimension expressions. The $\langle y-size \rangle$ is the height only and does not include any depth. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. Negative sizes cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*.

<code>\box_resize_to_wd_and_ht_plus_dp:Nnn</code>	<code>\box_resize_to_wd_and_ht_plus_dp:Nnn <box> {<x-size>} {<y-size>}</code>
<code>\box_resize_to_wd_and_ht_plus_dp:cnn</code>	
<code>\box_gresize_to_wd_and_ht_plus_dp:Nnn</code>	
<code>\box_gresize_to_wd_and_ht_plus_dp:cnn</code>	

New: 2017-04-06

Updated: 2019-01-22

Resizes the $\langle box \rangle$ to $\langle x-size \rangle$ (horizontally) and $\langle y-size \rangle$ (vertically): both of the sizes are dimension expressions. The $\langle y-size \rangle$ is the total vertical size (height plus depth). The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. Negative sizes cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*.

<code>\box_rotate:Nn</code>	<code>\box_rotate:Nn <box> {<angle>}</code>
<code>\box_rotate:cn</code>	
<code>\box_grotate:Nn</code>	Rotates the $\langle box \rangle$ by $\langle angle \rangle$ (in degrees) anti-clockwise about its reference point. The reference point of the updated box is moved horizontally such that it is at the left side of the smallest rectangle enclosing the rotated material. The updated $\langle box \rangle$ is an hbox , irrespective of the nature of the $\langle box \rangle$ before the rotation is applied.
<code>\box_grotate:cn</code>	
<hr/> Updated: 2019-01-22 <hr/>	

<code>\box_scale:Nnn</code>	<code>\box_scale:Nnn <box> {<x-scale>} {<y-scale>}</code>
<code>\box_scale:cnn</code>	
<code>\box_gscale:Nnn</code>	Scales the $\langle box \rangle$ by factors $\langle x-scale \rangle$ and $\langle y-scale \rangle$ in the horizontal and vertical directions, respectively (both scales are integer expressions). The updated $\langle box \rangle$ is an hbox , irrespective of the nature of the $\langle box \rangle$ before the scaling is applied. Negative scalings cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-scale \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and <i>vice versa</i> .
<code>\box_gscale:cnn</code>	
<hr/> Updated: 2019-01-22 <hr/>	

14 Primitive box conditionals

<code>\if_hbox:N *</code>	<code>\if_hbox:N <box></code>
	<code><true code></code>
	<code>\else:</code>
	<code><false code></code>
	<code>\fi:</code>
	Tests is $\langle box \rangle$ is a horizontal box.
	T_EXhackers note: This is the T _E X primitive <code>\ifhbox</code> .

<code>\if_vbox:N *</code>	<code>\if_vbox:N <box></code>
	<code><true code></code>
	<code>\else:</code>
	<code><false code></code>
	<code>\fi:</code>
	Tests is $\langle box \rangle$ is a vertical box.
	T_EXhackers note: This is the T _E X primitive <code>\ifvbox</code> .

<code>\if_box_empty:N *</code>	<code>\if_box_empty:N <box></code>
	<code><true code></code>
	<code>\else:</code>
	<code><false code></code>
	<code>\fi:</code>
	Tests is $\langle box \rangle$ is an empty (void) box.
	T_EXhackers note: This is the T _E X primitive <code>\ifvoid</code> .

Part XXIX

The l3coffins package

Coffin code layer

The material in this module provides the low-level support system for coffins. For details about the design concept of a coffin, see the xcoffins module (in the l3experimental bundle).

1 Creating and initialising coffins

<code>\coffin_new:N</code>
<code>\coffin_new:c</code>
<code>New: 2011-08-17</code>

`\coffin_new:N` $\langle coffin \rangle$

Creates a new $\langle coffin \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle coffin \rangle$ is initially empty.

<code>\coffin_clear:N</code>
<code>\coffin_clear:c</code>
<code>\coffin_gclear:N</code>
<code>\coffin_gclear:c</code>
<code>New: 2011-08-17</code>
<code>Updated: 2019-01-21</code>

`\coffin_clear:N` $\langle coffin \rangle$

Clears the content of the $\langle coffin \rangle$.

<code>\coffin_set_eq:NN</code>
<code>\coffin_set_eq:(Nc cN cc)</code>
<code>\coffin_gset_eq:NN</code>
<code>\coffin_gset_eq:(Nc cN cc)</code>
<code>New: 2011-08-17</code>
<code>Updated: 2019-01-21</code>

`\coffin_set_eq:NN` $\langle coffin_1 \rangle$ $\langle coffin_2 \rangle$

Sets both the content and poles of $\langle coffin_1 \rangle$ equal to those of $\langle coffin_2 \rangle$.

<code>\coffin_if_exist_p:N *</code>
<code>\coffin_if_exist_p:c *</code>
<code>\coffin_if_exist:N\overline{TF} *</code>
<code>\coffin_if_exist:c\overline{TF} *</code>
<code>New: 2012-06-20</code>

`\coffin_if_exist_p:N` $\langle box \rangle$

`\coffin_if_exist:NTF` $\langle box \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests whether the $\langle coffin \rangle$ is currently defined.

2 Setting coffin content and poles

<code>\hcoffin_set:Nn</code>
<code>\hcoffin_set:cn</code>
<code>\hcoffin_gset:Nn</code>
<code>\hcoffin_gset:cn</code>
<code>New: 2011-08-17</code>
<code>Updated: 2019-01-21</code>

`\hcoffin_set:Nn` $\langle coffin \rangle$ $\{\langle material \rangle\}$

Typesets the $\langle material \rangle$ in horizontal mode, storing the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material.

```

\hcoffin_set:Nw
\hcoffin_set:cw
\hcoffin_set_end:
\hcoffin_gset:Nw
\hcoffin_gset:cw
\hcoffin_gset_end:

```

New: 2011-09-10
Updated: 2019-01-21

```

\vcoffin_set:Nnn
\vcoffin_set:cnn
\vcoffin_gset:Nnn
\vcoffin_gset:cnn

```

New: 2011-08-17
Updated: 2019-01-21

```

\vcoffin_set:Nnw
\vcoffin_set:cnw
\vcoffin_set_end:
\vcoffin_gset:Nnw
\vcoffin_gset:cnw
\vcoffin_gset_end:

```

New: 2011-09-10
Updated: 2019-01-21

`\hcoffin_set:Nw <coffin> <material> \hcoffin_set_end:`

Typesets the $\langle material \rangle$ in horizontal mode, storing the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

`\vcoffin_set:Nnn <coffin> {\<width>} {\<material>}`

Typesets the $\langle material \rangle$ in vertical mode constrained to the given $\langle width \rangle$ and stores the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material.

`\vcoffin_set:Nnw <coffin> {\<width>} <material> \vcoffin_set_end:`

Typesets the $\langle material \rangle$ in vertical mode constrained to the given $\langle width \rangle$ and stores the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

```

\coffin_set_horizontal_pole:Nnn
\coffin_set_horizontal_pole:cnn
\coffin_gset_horizontal_pole:Nnn
\coffin_gset_horizontal_pole:cnn

```

New: 2012-07-20
Updated: 2019-01-21

`\coffin_set_horizontal_pole:Nnn <coffin> {\<pole>} {\<offset>}`

Sets the $\langle pole \rangle$ to run horizontally through the $\langle coffin \rangle$. The $\langle pole \rangle$ is placed at the $\langle offset \rangle$ from the bottom edge of the bounding box of the $\langle coffin \rangle$. The $\langle offset \rangle$ should be given as a dimension expression.

```

\coffin_set_vertical_pole:Nnn
\coffin_set_vertical_pole:cnn
\coffin_gset_vertical_pole:Nnn
\coffin_gset_vertical_pole:cnn

```

New: 2012-07-20
Updated: 2019-01-21

`\coffin_set_vertical_pole:Nnn <coffin> {\<pole>} {\<offset>}`

Sets the $\langle pole \rangle$ to run vertically through the $\langle coffin \rangle$. The $\langle pole \rangle$ is placed at the $\langle offset \rangle$ from the left-hand edge of the bounding box of the $\langle coffin \rangle$. The $\langle offset \rangle$ should be given as a dimension expression.

3 Coffin affine transformations

<code>\coffin_resize:Nnn</code>	<code>\coffin_resize:Nnn <coffin> {\width} {\total-height}</code>
<code>\coffin_resize:cnn</code>	
<code>\coffin_gresize:Nnn</code>	Resized the $\langle coffin \rangle$ to $\langle width \rangle$ and $\langle total-height \rangle$, both of which should be given as dimension expressions.
<code>\coffin_gresize:cnn</code>	
Updated: 2019-01-23	
<code>\coffin_rotate:Nn</code>	<code>\coffin_rotate:Nn <coffin> {\angle}</code>
<code>\coffin_rotate:cn</code>	
<code>\coffin_grotate:Nn</code>	Rotates the $\langle coffin \rangle$ by the given $\langle angle \rangle$ (given in degrees counter-clockwise). This process rotates both the coffin content and poles. Multiple rotations do not result in the bounding box of the coffin growing unnecessarily.
<code>\coffin_grotate:cn</code>	
<code>\coffin_scale:Nnn</code>	<code>\coffin_scale:Nnn <coffin> {\x-scale} {\y-scale}</code>
<code>\coffin_scale:cnn</code>	
<code>\coffin_gscale:Nnn</code>	Scales the $\langle coffin \rangle$ by a factors $\langle x-scale \rangle$ and $\langle y-scale \rangle$ in the horizontal and vertical directions, respectively. The two scale factors should be given as real numbers.
<code>\coffin_gscale:cnn</code>	
Updated: 2019-01-23	

4 Joining and using coffins

<code>\coffin_attach:NnnNnnnn</code>	<code>\coffin_attach:NnnNnnnn</code>
<code>\coffin_attach:(cnnNnnnn Nnnncnnnn cnnncnnnn)</code>	$\langle coffin_1 \rangle$ $\{\langle coffin_1-pole_1 \rangle\}$ $\{\langle coffin_1-pole_2 \rangle\}$
<code>\coffin_gattach:NnnNnnnn</code>	$\langle coffin_2 \rangle$ $\{\langle coffin_2-pole_1 \rangle\}$ $\{\langle coffin_2-pole_2 \rangle\}$
<code>\coffin_gattach:(cnnNnnnn Nnnncnnnn cnnncnnnn)</code>	$\{\langle x-offset \rangle\}$ $\{\langle y-offset \rangle\}$
Updated: 2019-01-22	
<p>This function attaches $\langle coffin_2 \rangle$ to $\langle coffin_1 \rangle$ such that the bounding box of $\langle coffin_1 \rangle$ is not altered, <i>i.e.</i> $\langle coffin_2 \rangle$ can protrude outside of the bounding box of the coffin. The alignment is carried out by first calculating $\langle handle_1 \rangle$, the point of intersection of $\langle coffin_1-pole_1 \rangle$ and $\langle coffin_1-pole_2 \rangle$, and $\langle handle_2 \rangle$, the point of intersection of $\langle coffin_2-pole_1 \rangle$ and $\langle coffin_2-pole_2 \rangle$. $\langle coffin_2 \rangle$ is then attached to $\langle coffin_1 \rangle$ such that the relationship between $\langle handle_1 \rangle$ and $\langle handle_2 \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions.</p>	

<code>\coffin_join:NnnNnnnn</code>	<code>\coffin_join:NnnNnnnn</code>
<code>\coffin_join:(cnnNnnnn Nnnncnnnn cnnncnnnn)</code>	$\langle coffin_1 \rangle$ $\{\langle coffin_1-pole_1 \rangle\}$ $\{\langle coffin_1-pole_2 \rangle\}$
<code>\coffin_gjoin:NnnNnnnn</code>	$\langle coffin_2 \rangle$ $\{\langle coffin_2-pole_1 \rangle\}$ $\{\langle coffin_2-pole_2 \rangle\}$
<code>\coffin_gjoin:(cnnNnnnn Nnnncnnnn cnnncnnnn)</code>	$\{\langle x-offset \rangle\}$ $\{\langle y-offset \rangle\}$
Updated: 2019-01-22	

This function joins $\langle coffin_2 \rangle$ to $\langle coffin_1 \rangle$ such that the bounding box of $\langle coffin_1 \rangle$ may expand. The new bounding box covers the area containing the bounding boxes of the two original coffins. The alignment is carried out by first calculating $\langle handle_1 \rangle$, the point of intersection of $\langle coffin_1-pole_1 \rangle$ and $\langle coffin_1-pole_2 \rangle$, and $\langle handle_2 \rangle$, the point of intersection of $\langle coffin_2-pole_1 \rangle$ and $\langle coffin_2-pole_2 \rangle$. $\langle coffin_2 \rangle$ is then attached to $\langle coffin_1 \rangle$ such that the relationship between $\langle handle_1 \rangle$ and $\langle handle_2 \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions.

```
\coffin_typeset:Nnnnn
\coffin_typeset:cnnnn
```

Updated: 2012-07-20

```
\coffin_typeset:Nnnnn <coffin> {\pole_1} {\pole_2}
{\<x-offset>} {\<y-offset>}
```

Typesetting is carried out by first calculating $\langle handle \rangle$, the point of intersection of $\langle pole_1 \rangle$ and $\langle pole_2 \rangle$. The coffin is then typeset in horizontal mode such that the relationship between the current reference point in the document and the $\langle handle \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions. Typesetting a coffin is therefore analogous to carrying out an alignment where the “parent” coffin is the current insertion point.

5 Measuring coffins

```
\coffin_dp:N
\coffin_dp:c
```

```
\coffin_dp:N <coffin>
```

Calculates the depth (below the baseline) of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

```
\coffin_ht:N
\coffin_ht:c
```

```
\coffin_ht:N <coffin>
```

Calculates the height (above the baseline) of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

```
\coffin_wd:N
\coffin_wd:c
```

```
\coffin_wd:N <coffin>
```

Calculates the width of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

6 Coffin diagnostics

```
\coffin_display_handles:Nn
\coffin_display_handles:cn
```

Updated: 2011-09-02

```
\coffin_display_handles:Nn <coffin> {\color}
```

This function first calculates the intersections between all of the $\langle poles \rangle$ of the $\langle coffin \rangle$ to give a set of $\langle handles \rangle$. It then prints the $\langle coffin \rangle$ at the current location in the source, with the position of the $\langle handles \rangle$ marked on the coffin. The $\langle handles \rangle$ are labelled as part of this process: the locations of the $\langle handles \rangle$ and the labels are both printed in the $\langle color \rangle$ specified.

```
\coffin_mark_handle:Nnnn
\coffin_mark_handle:cnnn
```

Updated: 2011-09-02

```
\coffin_mark_handle:Nnnn <coffin> {\pole_1} {\pole_2} {\color}
```

This function first calculates the $\langle handle \rangle$ for the $\langle coffin \rangle$ as defined by the intersection of $\langle pole_1 \rangle$ and $\langle pole_2 \rangle$. It then marks the position of the $\langle handle \rangle$ on the $\langle coffin \rangle$. The $\langle handle \rangle$ are labelled as part of this process: the location of the $\langle handle \rangle$ and the label are both printed in the $\langle color \rangle$ specified.

```
\coffin_show_structure:N
\coffin_show_structure:c
```

Updated: 2015-08-01

```
\coffin_show_structure:N <coffin>
```

This function shows the structural information about the $\langle coffin \rangle$ in the terminal. The width, height and depth of the typeset material are given, along with the location of all of the poles of the coffin.

Notice that the poles of a coffin are defined by four values: the x and y co-ordinates of a point that the pole passes through and the x - and y -components of a vector denoting the direction of the pole. It is the ratio between the later, rather than the absolute values, which determines the direction of the pole.

`\coffin_log_structure:N`
`\coffin_log_structure:c`

New: 2014-08-22
Updated: 2015-08-01

`\coffin_log_structure:N` $\langle coffin \rangle$

This function writes the structural information about the $\langle coffin \rangle$ in the log file. See also

`\coffin_show_structure:N` which displays the result in the terminal.

7 Constants and variables

`\c_empty_coffin`

A permanently empty coffin.

`\l_tmpa_coffin`
`\l_tmpb_coffin`

New: 2012-06-19

Scratch coffins for local assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_coffin`
`\g_tmpb_coffin`

New: 2019-01-24

Scratch coffins for global assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

Part XXX

The l3color-base package

Color support

This module provides support for color in L^AT_EX3. At present, the material here is mainly intended to support a small number of low-level requirements in other l3kernel modules.

1 Color in boxes

Controlling the color of text in boxes requires a small number of control functions, so that the boxed material uses the color at the point where it is set, rather than where it is used.

```
\color_group_begin:  
\color_group_end:
```

New: 2011-09-03

```
\color_group_begin:  
...  
\color_group_end:
```

Creates a color group: one used to “trap” color settings.

```
\color_ensure_current:
```

New: 2011-09-03

```
\color_ensure_current:
```

Ensures that material inside a box uses the foreground color at the point where the box is set, rather than that in force when the box is used. This function should usually be used within a `\color_group_begin: ... \color_group_end: group`.

Part XXXI

The l3luatex package: LuaTeX-specific functions

The LuaTeX engine provides access to the Lua programming language, and with it access to the “internals” of TeX. In order to use this within the framework provided here, a family of functions is available. When used with pdfTeX, pTeX, upTeX or XeTeX these raise an error: use `\sys_if_engine luatex:T` to avoid this. Details on using Lua with the LuaTeX engine are given in the LuaTeX manual.

1 Breaking out to Lua

<code>\lua_now:n</code> ★	<code>\lua_now:n</code> $\{ \langle token\ list \rangle \}$
---------------------------	---

<code>\lua_now:e</code> ★

<code>New: 2018-06-18</code>

The $\langle token\ list \rangle$ is first tokenized by TeX, which includes converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting $\langle Lua\ input \rangle$ is passed to the Lua interpreter for processing. Each `\lua_now:n` block is treated by Lua as a separate chunk. The Lua interpreter executes the $\langle Lua\ input \rangle$ immediately, and in an expandable manner.

TeXhackers note: `\lua_now:e` is a macro wrapper around `\directlua:` when LuaTeX is in use two expansions are required to yield the result of the Lua code.

<code>\lua_shipout_e:n</code> ★

<code>\lua_shipout:n</code>

<code>New: 2018-06-18</code>

<code>\lua_shipout:n</code> $\{ \langle token\ list \rangle \}$

The $\langle token\ list \rangle$ is first tokenized by TeX, which includes converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting $\langle Lua\ input \rangle$ is passed to the Lua interpreter when the current page is finalised (*i.e.* at shipout). Each `\lua_shipout:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the $\langle Lua\ input \rangle$ during the page-building routine: no TeX expansion of the $\langle Lua\ input \rangle$ will occur at this stage.

In the case of the `\lua_shipout_e:n` version the input is fully expanded by TeX in an e-type manner during the shipout operation.

TeXhackers note: At a TeX level, the $\langle Lua\ input \rangle$ is stored as a “whatsit”.

<code>\lua_escape:n</code> ★

<code>\lua_escape:e</code> ★

<code>New: 2015-06-29</code>

<code>\lua_escape:n</code> $\{ \langle token\ list \rangle \}$
--

Converts the $\langle token\ list \rangle$ such that it can safely be passed to Lua: embedded backslashes, double and single quotes, and newlines and carriage returns are escaped. This is done by prepending an extra token consisting of a backslash with category code 12, and for the line endings, converting them to `\n` and `\r`, respectively.

TeXhackers note: `\lua_escape:e` is a macro wrapper around `\luaescapestring:` when LuaTeX is in use two expansions are required to yield the result of the Lua code.

2 Lua interfaces

As well as interfaces for \TeX , there are a small number of Lua functions provided here.

<u>13kernel</u>	All public interfaces provided by the module are stored within the <code>13kernel</code> table.
<u>13kernel.charcat</u>	<p><code>13kernel.charcat($\langle charcode \rangle$, $\langle catcode \rangle$)</code></p> <p>Constructs a character of $\langle charcode \rangle$ and $\langle catcode \rangle$ and returns the result to \TeX.</p>
<u>13kernel.elapsedtime</u>	<p><code>13kernel.elapsedtime()</code></p> <p>Returns the CPU time in $\langle scaled\ seconds \rangle$ since the start of the \TeX run or since <code>13kernel.resettimer</code> was issued. This only measures the time used by the CPU, not the real time, e.g., waiting for user input.</p>
<u>13kernel.filedump</u>	<p><code>13kernel.filedump($\langle file \rangle$, $\langle offset \rangle$, $\langle length \rangle$)</code></p> <p>Returns the uppercase hexadecimal representation of the content of the $\langle file \rangle$ read as bytes. If the $\langle length \rangle$ is given, only this part of the file is returned; similarly, one may specify the $\langle offset \rangle$ from the start of the file. If the $\langle length \rangle$ is not given, the entire file is read starting at the $\langle offset \rangle$.</p>
<u>13kernel.filemdfivesum</u>	<p><code>13kernel.filemdfivesum($\langle file \rangle$)</code></p> <p>Returns the MD5 sum of the file contents read as bytes; note that the result will depend on the nature of the line endings used in the file, in contrast to normal \TeX behaviour. If the $\langle file \rangle$ is not found, nothing is returned with <i>no error raised</i>.</p>
<u>13kernel.filemoddate</u>	<p><code>13kernel.filemoddate($\langle file \rangle$)</code></p> <p>Returns the date/time of last modification of the $\langle file \rangle$ in the format</p> <p style="text-align: center;">$D:\langle year \rangle\langle month \rangle\langle day \rangle\langle hour \rangle\langle minute \rangle\langle second \rangle\langle offset \rangle$</p> <p>where the latter may be Z (UTC) or $\langle plus-minus \rangle\langle hours \rangle'\langle minutes \rangle'$. If the $\langle file \rangle$ is not found, nothing is returned with <i>no error raised</i>.</p>
<u>13kernel.filesize</u>	<p><code>13kernel.filesize($\langle file \rangle$)</code></p> <p>Returns the size of the $\langle file \rangle$ in bytes. If the $\langle file \rangle$ is not found, nothing is returned with <i>no error raised</i>.</p>
<u>13kernel.resettimer</u>	<p><code>13kernel.resettimer()</code></p> <p>Resets the timer used by <code>13kernel.elapsedtime</code>.</p>
<u>13kernel.shellescape</u>	<p><code>13kernel.shellescape($\langle cmd \rangle$)</code></p> <p>Executes the $\langle cmd \rangle$ and prints to the log as for pdf\TeX.</p>
<u>13kernel.strcmp</u>	<p><code>13kernel.strcmp($\langle str\ one \rangle$, $\langle str\ two \rangle$)</code></p> <p>Compares the two strings and returns 0 to \TeX if the two are identical.</p>

Part XXXII

The l3unicode package: Unicode support functions

This module provides Unicode-specific functions along with loading data from a range of Unicode Consortium files. At present, it provides no public functions.

Part XXXIII

The l3text package: text processing

1 l3text documentation

This module deals with manipulation of (formatted) text; such material is comprised of a restricted set of token list content. The functions provided here concern conversion of textual content for example in case changing, generation of bookmarks and extraction to tags. All of the major functions operate by expansion. Begin-group and end-group tokens in the $\langle text \rangle$ are normalized and become { and }, respectively.

1.1 Expanding text

<code>\text_expand:n</code> *	<code>\text_expand:n {$\langle text \rangle$}</code>
-------------------------------	---

New: 2020-01-02

Takes user input $\langle text \rangle$ and expands the content. Protected commands (typically formatting) are left in place, and no processing takes place of math mode material (as delimited by pairs given in `\l_text_math_delims_tl` or as the argument to commands listed in `\l_text_math_arg_tl`). Commands which are neither engine- nor L^AT_EX protected are expanded exhaustively. Any commands listed in `\l_text_expand_exclude_tl`, `\l_text_accents_tl` and `\l_text_letterlike_tl` are excluded from expansion.

<code>\text_declare_expand_equivalent:Nn</code>	<code>\text_declare_expand_equivalent:Nn $\langle cmd \rangle$ {$\langle replacement \rangle$}</code>
<code>\text_declare_expand_equivalent:cn</code>	

New: 2020-01-22

Declares that the $\langle replacement \rangle$ tokens should be used whenever the $\langle cmd \rangle$ (a single token) is encountered. The $\langle replacement \rangle$ tokens should be expandable.

1.2 Case changing

<code>\text_lowercase:n</code>	*
<code>\text_uppercase:n</code>	*
<code>\text_titlecase:n</code>	*
<code>\text_titlecase_first:n</code>	*
<code>\text_lowercase:nn</code>	*
<code>\text_uppercase:nn</code>	*
<code>\text_titlecase:nn</code>	*
<code>\text_titlecase_first:nn</code>	*

New: 2019-11-20
Updated: 2020-02-24

`\text_uppercase:n` $\{\langle tokens \rangle\}$
`\text_uppercase:nn` $\{\langle language \rangle\} \{\langle tokens \rangle\}$
Takes user input $\langle text \rangle$ first applies `\text_expand`, then transforms the case of character tokens as specified by the function name. The category code of letters are not changed by this process (at least where they can be represented by the engine as a single token: 8-bit engines may require active characters).

Upper- and lowercase have the obvious meanings. Titlecasing may be regarded informally as converting the first character of the $\langle tokens \rangle$ to uppercase and the rest to lowercase. However, the process is more complex than this as there are some situations where a single lowercase character maps to a special form, for example *ij* in Dutch which becomes *IJ*. The `titlecase_first` variant does not attempt any case changing at all after the first letter has been processed.

Importantly, notice that these functions are intended for working with user *text for typesetting*. For case changing programmatic data see the `l3str` module and discussion there of `\str_lowercase:n`, `\str_uppercase:n` and `\str_foldcase:n`.

Case changing does not take place within math mode material so for example

`\text_uppercase:n { Some~text~$y = mx + c$~with~{Braces} }`

becomes

SOME TEXT \$y = mx + c\$ WITH {BRACES}

The arguments of commands listed in `\l_text_case_exclude_arg_tl` are excluded from case changing; the latter are entirely non-textual content (such as labels).

As is generally true for `expl3`, these functions are designed to work with Unicode input only. As such, UTF-8 input is assumed for *all* engines. When used with Xe_{La}TeX or Lua_{La}TeX a full range of Unicode transformations are enabled. Specifically, the standard mappings here follow those defined by the [Unicode Consortium](#) in `UnicodeData.txt` and `SpecialCasing.txt`. In the case of 8-bit engines, mappings are provided for characters which can be represented in output typeset using the T1, T2 and LGR font encodings. Thus for example *ä* can be case-changed using pdf_{La}TeX. For p_{La}TeX only the ASCII range is covered as the engine treats input outside of this range as east Asian.

Language-sensitive conversions are enabled using the $\langle language \rangle$ argument, and follow Unicode Consortium guidelines. Currently, the languages recognised for special handling are as follows.

- Azeri and Turkish (`az` and `tr`). The case pairs I/i-dotless and I-dot/i are activated for these languages. The combining dot mark is removed when lowercasing I-dot and introduced when upper casing i-dotless.
- German (`de-alt`). An alternative mapping for German in which the lowercase *Eszett* maps to a *großes Eszett*. Since there is a T1 slot for the *großes Eszett* in T1, this tailoring *is* available with pdf_{La}TeX as well as in the Unicode ₂₅₇TeX engines.
- Greek (`el`). Removes accents from Greek letters when uppercasing; titlecasing leaves accents in place.
- Lithuanian (`lt`). The lowercase letters i and j should retain a dot above when the accents grave, acute or tilde are present. This is implemented for lowercasing of the relevant uppercase letters both when input as single Unicode codepoints and when using combining accents. The combining dot is removed when uppercasing in these cases. Note that *only* the accents used in Lithuanian are covered: the behaviour of other accents are not modified.
- Dutch (`nl`). Capitalisation of *ij* at the beginning of titlecased input produces *IJ* rather than *Ij*. The output retains two separate letters, thus this transformation *is* available using pdf_{La}TeX.

For titlecasing, note that there are two functions available. The function `\text_`
`titlecase:n` applies (broadly) uppercasing to the first letter of the input, then lower-

1.3 Removing formatting from text

`\text_purify:n` ☆ `\text_purify:n {<text>}`

New: 2020-03-05

Takes user input $\langle text \rangle$ and expands as described for `\text_expand:n`, then removes all functions from the resulting text. Math mode material (as delimited by pairs given in `\l_text_math_delims_tl` or as the argument to commands listed in `\l_text_math_arg_tl`) is left contained in a pair of \$ delimiters. Non-expandable functions present in the $\langle text \rangle$ must either have a defined equivalent (see `\text_declare_purify_equivalent:Nn`) or will be removed from the result. Implicit tokens are converted to their explicit equivalent.

`\text_declare_purify_equivalent:Nn` `\text_declare_purify_equivalent:Nn <cmd> {<replacement>}`
`\text_declare_purify_equivalent:Nx`

New: 2020-03-05

Declares that the $\langle replacement \rangle$ tokens should be used whenever the $\langle cmd \rangle$ (a single token) is encountered. The $\langle replacement \rangle$ tokens should be expandable.

1.4 Control variables

`\l_text_accents_tl` Lists commands which represent accents, and which are left unchanged by expansion. (Defined only for the L^AT_EX 2_ε package.)

`\l_text_letterlike_tl` Lists commands which represent letters; these are left unchanged by expansion. (Defined only for the L^AT_EX 2_ε package.)

`\l_text_math_arg_tl` Lists commands present in the $\langle text \rangle$ where the argument of the command should be treated as math mode material. The treatment here is similar to `\l_text_math_delims_tl` but for a command rather than paired delimiters.

`\l_text_math_delims_tl` Lists pairs of tokens which delimit (in-line) math mode content; such content *may* be excluded from processing.

`\l_text_case_exclude_arg_tl`

Lists commands which are excluded from case changing.

`\l_text_expand_exclude_tl` Lists commands which are excluded from expansion.

`\l_text_titlecase_check_letter_bool`

Controls how the start of titlecasing is handled: when **true**, the first *letter* in text is considered. The standard setting is **true**.

Part XXXIV

The l3legacy package

Interfaces to legacy concepts

There are a small number of T_EX or L^AT_EX 2_ε concepts which are not used in `expl3` code but which need to be manipulated when working as a L^AT_EX 2_ε package. To allow these to be integrated cleanly into `expl3` code, a set of legacy interfaces are provided here.

<code>\legacy_if_p:n</code> *	<code>\legacy_if:nTF</code> { <i>⟨name⟩</i> } { <i>⟨true code⟩</i> } { <i>⟨false code⟩</i> }
<code>\legacy_if:nTF</code> *	Tests if the L ^A T _E X 2 _ε /plain T _E X conditional (generated by <code>\newif</code>) if <code>true</code> or <code>false</code> and branches accordingly. The <i>⟨name⟩</i> of the conditional should <i>omit</i> the leading <code>if</code> .

Part XXXV

The l3candidates package

Experimental additions to l3kernel

1 Important notice

This module provides a space in which functions can be added to l3kernel (expl3) while still being experimental.

As such, the functions here may not remain in their current form, or indeed at all, in l3kernel in the future.

In contrast to the material in l3experimental, the functions here are all *small* additions to the kernel. We encourage programmers to test them out and report back on the LaTeX-L mailing list.

Thus, if you intend to use any of these functions from the candidate module in a public package offered to others for productive use (e.g., being placed on CTAN) please consider the following points carefully:

- Be prepared that your public packages might require updating when such functions are being finalized.
- Consider informing us that you use a particular function in your public package, e.g., by discussing this on the LaTeX-L mailing list. This way it becomes easier to coordinate any updates necessary without issues for the users of your package.
- Discussing and understanding use cases for a particular addition or concept also helps to ensure that we provide the right interfaces in the final version so please give us feedback if you consider a certain candidate function useful (or not).

We only add functions in this space if we consider them being serious candidates for a final inclusion into the kernel. However, real use sometimes leads to better ideas, so functions from this module are **not necessarily stable** and we may have to adjust them!

2 Additions to l3box

2.1 Viewing part of a box

```
\box_clip:N  
\box_clip:c  
\box_gclip:N  
\box_gclip:c
```

Updated: 2019-01-23

```
\box_clip:N <box>
```

Clips the $\langle box \rangle$ in the output so that only material inside the bounding box is displayed in the output. The updated $\langle box \rangle$ is an hbox, irrespective of the nature of the $\langle box \rangle$ before the clipping is applied.

These functions require the L^AT_EX3 native drivers: they do not work with the L^AT_EX 2_ε graphics drivers!

T_EXhackers note: Clipping is implemented by the driver, and as such the full content of the box is placed in the output file. Thus clipping does not remove any information from the raw output, and hidden material can therefore be viewed by direct examination of the file.

```
\box_set_trim:Nnnnn
\box_set_trim:cnnnn
\box_gset_trim:Nnnnn
\box_gset_trim:cnnnn
```

New: 2019-01-23

```
\box_set_trim:Nnnnn <box> {\left} {\bottom} {\right} {\top}
```

Adjusts the bounding box of the $\langle box \rangle$ $\langle left \rangle$ is removed from the left-hand edge of the bounding box, $\langle right \rangle$ from the right-hand edge and so fourth. All adjustments are *$\langle dimension expressions \rangle$* . Material outside of the bounding box is still displayed in the output unless `\box_clip:N` is subsequently applied. The updated $\langle box \rangle$ is an hbox, irrespective of the nature of the $\langle box \rangle$ before the trim operation is applied. The behavior of the operation where the trims requested is greater than the size of the box is undefined.

```
\box_set_viewport:Nnnnn
\box_set_viewport:cnnnn
\box_gset_viewport:Nnnnn
\box_gset_viewport:cnnnn
```

New: 2019-01-23

```
\box_set_viewport:Nnnnn <box> {\llx} {\lly} {\urx} {\ury}
```

Adjusts the bounding box of the $\langle box \rangle$ such that it has lower-left co-ordinates ($\langle llx \rangle$, $\langle lly \rangle$) and upper-right co-ordinates ($\langle urx \rangle$, $\langle ury \rangle$). All four co-ordinate positions are *$\langle dimension expressions \rangle$* . Material outside of the bounding box is still displayed in the output unless `\box_clip:N` is subsequently applied. The updated $\langle box \rangle$ is an hbox, irrespective of the nature of the $\langle box \rangle$ before the viewport operation is applied.

3 Additions to l3expan

```
\exp_args_generate:n
```

New: 2018-04-04
Updated: 2019-02-08

```
\exp_args_generate:n {\variant argument specifiers}
```

Defines `\exp_args:N<variant>` functions for each $\langle variant \rangle$ given in the comma list $\{\langle variant argument specifiers \rangle\}$. Each $\langle variant \rangle$ should consist of the letters N, c, n, V, v, o, f, e, x, p and the resulting function is protected if the letter x appears in the $\langle variant \rangle$. This is only useful for cases where `\cs_generate_variant:Nn` is not applicable.

4 Additions to l3fp

```
\fp_if_nan_p:n ★
\fp_if_nan:nTF ★
```

New: 2019-08-25

```
\fp_if_nan:n {\fpexpr}
```

Evaluates the $\langle fpexpr \rangle$ and tests whether the result is exactly NaN. The test returns **false** for any other result, even a tuple containing NaN.

5 Additions to l3file

```
\iow_allow_break:
```

New: 2018-12-29

```
\iow_allow_break:
```

In the first argument of `\iow_wrap:nnnn` (for instance in messages), inserts a break-point that allows a line break. In other words this is a zero-width breaking space.

<code>\ior_get_term:nN</code>
<code>\ior_str_get_term:nN</code>
New: 2019-03-23

`\ior_get_term:nN` $\langle prompt \rangle$ $\langle token list variable \rangle$

Function that reads one or more lines (until an equal number of left and right braces are found) from the terminal and stores the result locally in the $\langle token list \rangle$ variable. Tokenization occurs as described for `\ior_get:NN` or `\ior_str_get:NN`, respectively. When the $\langle prompt \rangle$ is empty, T_EX will wait for input without any other indication: typically the programmer will have provided a suitable text using e.g. `\iow_term:n`. Where the $\langle prompt \rangle$ is given, it will appear in the terminal followed by an =, e.g.

prompt=

<code>\ior_shell_open:Nn</code>
New: 2019-05-08

`\ior_shell_open:nN` $\langle stream \rangle$ $\{ \langle shell command \rangle \}$

Opens the *pseudo*-file created by the output of the $\langle shell command \rangle$ for reading using $\langle stream \rangle$ as the control sequence for access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle shell command \rangle$ until a `\ior_close:N` instruction is given or the T_EX run ends. If piped system calls are disabled an error is raised.

For details of handling of the $\langle shell command \rangle$, see `\sys_get_shell:nnN(TF)`.

6 Additions to l3flag

<code>\flag_raise_if_clear:n</code> ☆
New: 2018-04-02

`\flag_raise_if_clear:n` $\{ \langle flag name \rangle \}$

Ensures the $\langle flag \rangle$ is raised by making its height at least 1, locally.

7 Additions to l3intarray

<code>\intarray_gset_rand:Nnn</code>
<code>\intarray_gset_rand:cnn</code>
<code>\intarray_gset_rand:Nn</code>
<code>\intarray_gset_rand:cn</code>
New: 2018-05-05

`\intarray_gset_rand:Nnn` $\langle intarray var \rangle$ $\{ \langle minimum \rangle \}$ $\{ \langle maximum \rangle \}$
`\intarray_gset_rand:Nn` $\langle intarray var \rangle$ $\{ \langle maximum \rangle \}$

Evaluates the integer expressions $\langle minimum \rangle$ and $\langle maximum \rangle$ then sets each entry (independently) of the $\langle integer array variable \rangle$ to a pseudo-random number between the two (with bounds included). If the absolute value of either bound is bigger than $2^{30} - 1$, an error occurs. Entries are generated in the same way as repeated calls to `\int_rand:nn` or `\int_rand:n` respectively, in particular for the second function the $\langle minimum \rangle$ is 1. Assignments are always global. This is not available in older versions of X_YT_EX.

7.1 Working with contents of integer arrays

<code>\intarray_to_clist:N</code> ☆
New: 2018-05-04

`\intarray_to_clist:N` $\langle intarray var \rangle$

Converts the $\langle intarray \rangle$ to integer denotations separated by commas. All tokens have category code other. If the $\langle intarray \rangle$ has no entry the result is empty; otherwise the result has one fewer comma than the number of items.

8 Additions to l3msg

In very rare cases it may be necessary to produce errors in an expansion-only context. The functions in this section should only be used if there is no alternative approach using `\msg_error:nnnnnn` or other non-expandable commands from the previous section. Despite having a similar interface as non-expandable messages, expandable errors must be handled internally very differently from normal error messages, as none of the tools to print to the terminal or the log file are expandable. As a result, short-hands such as `\{` or `\` do not work, and messages must be very short (with default settings, they are truncated after approximately 50 characters). It is advisable to ensure that the message is understandable even when truncated, by putting the most important information up front. Another particularity of expandable messages is that they cannot be redirected or turned off by the user.

<code>\msg_expandable_error:nnnnnn</code>	★	<code>\msg_expandable_error:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_expandable_error:nnffff</code>	★	
<code>\msg_expandable_error:nnnnn</code>	★	
<code>\msg_expandable_error:nnfff</code>	★	
<code>\msg_expandable_error:nnnn</code>	★	
<code>\msg_expandable_error:nnff</code>	★	
<code>\msg_expandable_error:nnn</code>	★	
<code>\msg_expandable_error:nnf</code>	★	
<code>\msg_expandable_error:nn</code>	★	

New: 2015-08-06

Updated: 2019-02-28

Issues an “Undefined error” message from T_EX itself using the undefined control sequence `\::error` then prints “! *<module>*: ”*<error message>*”, which should be short. With default settings, anything beyond approximately 60 characters long (or bytes in some engines) is cropped. A leading space might be removed as well.

<code>\msg_show_eval:Nn</code>	<code>\msg_show_eval:Nn {<function>} {<expression>}</code>
<code>\msg_log_eval:Nn</code>	

New: 2017-12-04

Shows or logs the *<expression>* (turned into a string), an equal sign, and the result of applying the *<function>* to the *{<expression>}* (with *f*-expansion). For instance, if the *<function>* is `\int_eval:n` and the *<expression>* is `1+2` then this logs `> 1+2=3`.

<code>\msg_show:nnnnnn</code>	<code>\msg_show:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_show:nnxxxx</code>	
<code>\msg_show:nnnnn</code>	
<code>\msg_show:nnxxx</code>	
<code>\msg_show:nnnn</code>	
<code>\msg_show:nnxx</code>	
<code>\msg_show:nnn</code>	
<code>\msg_show:nnx</code>	
<code>\msg_show:nn</code>	

New: 2017-12-04

Issues *<module>* information *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The information text is shown on the terminal and the T_EX run is interrupted in a manner similar to `\tl_show:n`. This is used in conjunction with `\msg_show_item:n` and similar functions to print complex variable contents completely. If the formatted text does not contain `>~` at the start of a line, an additional line `>~`. will be put at the end. In addition, a final period is added if not present.

```

\msg_show_item:n      * \seq_map_function:NN <seq> \msg_show_item:n
\msg_show_item_unbraced:n * \prop_map_function:NN <prop> \msg_show_item:nn
\msg_show_item:nn      *
\msg_show_item_unbraced:nn *

```

New: 2017-12-04

Used in the text of messages for `\msg_show:nnxxxx` to show or log a list of items or key-value pairs. The one-argument functions are used for sequences, clist or token lists and the others for property lists. These functions turn their arguments to strings.

9 Additions to `l3prg`

```

\bool_set_inverse:N \bool_set_inverse:N <boolean>
\bool_set_inverse:c
\bool_gset_inverse:N
\bool_gset_inverse:c

```

New: 2018-05-10

```

\bool_case_true:n      * \bool_case_true:nTF
\bool_case_true:nTF    * {
\bool_case_false:n      *   {<boolexpr case1>} {<code case1>}
\bool_case_false:nTF    *   {<boolexpr case2>} {<code case2>}
\bool_case_false:nTF    *   ...
\bool_case_false:nTF    *   {<boolexpr casen>} {<code casen>}
\bool_case_false:nTF    * }
\bool_case_false:nTF    * {<true code>}
\bool_case_false:nTF    * {<false code>}

```

New: 2019-02-10

Evaluates in turn each of the *<boolean expression cases>* until the first one that evaluates to `true` or to `false`, for `\bool_case_true:n` and `\bool_case_false:n`, respectively. The *<code>* associated to this first case is left in the input stream, followed by the *<true code>*, and other cases are discarded. If none of the cases match then only the *<false code>* is inserted. The functions `\bool_case_true:n` and `\bool_case_false:n`, which do nothing if there is no match, are also available. For example

```

\bool_case_true:nF
{
  { \dim_compare_p:n { \l__mypkg_wd_dim <= 10pt } }
  { Fits }
  { \int_compare_p:n { \l__mypkg_total_int >= 10 } }
  { Many }
  { \l__mypkg_special_bool }
  { Special }
}
{ No idea! }

```

leaves “Fits” or “Many” or “Special” or “No idea!” in the input stream, in a way similar to some other language’s “if ... elseif ... elseif ... else ...”.

10 Additions to l3prop

`\prop_rand_key_value:N` ☆
`\prop_rand_key_value:c` ☆

New: 2016-12-06

`\prop_rand_key_value:N` $\langle prop\ var \rangle$

Selects a pseudo-random key–value pair from the $\langle property\ list \rangle$ and returns $\{\langle key \rangle\}$ and $\{\langle value \rangle\}$. If the $\langle property\ list \rangle$ is empty the result is empty. This is not available in older versions of Xe_{La}TeX.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle value \rangle$ does not expand further when appearing in an x-type argument expansion.

11 Additions to l3seq

`\seq_mapthread_function:NNN` ☆
`\seq_mapthread_function:(NcN|cNN|ccN)` ☆

`\seq_mapthread_function:NNN` $\langle seq_1 \rangle$ $\langle seq_2 \rangle$ $\langle function \rangle$

Applies $\langle function \rangle$ to every pair of items $\langle seq_1\text{-}item \rangle$ – $\langle seq_2\text{-}item \rangle$ from the two sequences, returning items from both sequences from left to right. The $\langle function \rangle$ receives two n-type arguments for each iteration. The mapping terminates when the end of either sequence is reached (*i.e.* whichever sequence has fewer items determines how many iterations occur).

`\seq_set_filter:NNn`
`\seq_gset_filter:NNn`

`\seq_set_filter:NNn` $\langle sequence_1 \rangle$ $\langle sequence_2 \rangle$ $\{\langle inline\ boolexpr \rangle\}$

Evaluates the $\langle inline\ boolexpr \rangle$ for every $\langle item \rangle$ stored within the $\langle sequence_2 \rangle$. The $\langle inline\ boolexpr \rangle$ receives the $\langle item \rangle$ as #1. The sequence of all $\langle items \rangle$ for which the $\langle inline\ boolexpr \rangle$ evaluated to `true` is assigned to $\langle sequence_1 \rangle$.

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and would lead to low-level TeX errors.

`\seq_set_map:NNn`
`\seq_gset_map:NNn`

New: 2011-12-22

`\seq_set_map:NNn` $\langle sequence_1 \rangle$ $\langle sequence_2 \rangle$ $\{\langle inline\ function \rangle\}$

Applies $\langle inline\ function \rangle$ to every $\langle item \rangle$ stored within the $\langle sequence_2 \rangle$. The $\langle inline\ function \rangle$ should consist of code which will receive the $\langle item \rangle$ as #1. The sequence resulting from x-expanding $\langle inline\ function \rangle$ applied to each $\langle item \rangle$ is assigned to $\langle sequence_1 \rangle$. As such, the code in $\langle inline\ function \rangle$ should be expandable.

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and would lead to low-level TeX errors.

<code>\seq_set_from_function:NnN</code>	<code>\seq_set_from_function:NnN <seq var> {(loop code)} <function></code>
<code>\seq_gset_from_function:NnN</code>	

New: 2018-04-06

Sets the *<seq var>* equal to a sequence whose items are obtained by **x**-expanding *<loop code>* *<function>*. This expansion must result in successive calls to the *<function>* with no nonexpandable tokens in between. More precisely the *<function>* is replaced by a wrapper function that inserts the appropriate separators between items in the sequence. The *<loop code>* must be expandable; it can be for example `\tl_map_function:NN <tl var>` or `\clist_map_function:nN {(clist)}` or `\int_step_function:nnnN {(initial value)} {(step)} {(final value)}`.

<code>\seq_set_from_inline_x:Nnn</code>	<code>\seq_set_from_inline_x:Nnn <seq var> {(loop code)} {(inline code)}</code>
<code>\seq_gset_from_inline_x:Nnn</code>	

New: 2018-04-06

Sets the *<seq var>* equal to a sequence whose items are obtained by **x**-expanding *<loop code>* applied to a *<function>* derived from the *<inline code>*. A *<function>* is defined, that takes one argument, **x**-expands the *<inline code>* with that argument as #1, then adds appropriate separators to turn the result into an item of the sequence. The **x**-expansion of *<loop code>* *<function>* must result in successive calls to the *<function>* with no nonexpandable tokens in between. The *<loop code>* must be expandable; it can be for example `\tl_map_function:NN <tl var>` or `\clist_map_function:nN {(clist)}` or `\int_step_function:nnnN {(initial value)} {(step)} {(final value)}`, but not the analogous “inline” mappings.

<code>\seq_indexed_map_function:NN ☆</code>	<code>\seq_indexed_map_function:NN <seq var> <function></code>
---	--

New: 2018-05-03

Applies *<function>* to every entry in the *<sequence variable>*. The *<function>* should have signature `:nn`. It receives two arguments for each iteration: the *<index>* (namely 1 for the first entry, then 2 and so on) and the *<item>*.

<code>\seq_indexed_map_inline:Nn</code>	<code>\seq_indexed_map_inline:Nn <seq var> {(inline function)}</code>
---	---

New: 2018-05-03

Applies *<inline function>* to every entry in the *<sequence variable>*. The *<inline function>* should consist of code which receives the *<index>* (namely 1 for the first entry, then 2 and so on) as #1 and the *<item>* as #2.

12 Additions to l3sys

`\c_sys_engine_version_str`

New: 2018-05-02

The version string of the current engine, in the same form as given in the banner issued when running a job. For pdfTeX and LuaTeX this is of the form

$$\langle major \rangle . \langle minor \rangle . \langle revision \rangle$$

For XeTeX, the form is

$$\langle major \rangle . \langle minor \rangle$$

For pTeX and upTeX, only releases since TeX Live 2018 make the data available, and the form is more complex, as it comprises the pTeX version, the upTeX version and the e-pTeX version.

$$p \langle major \rangle . \langle minor \rangle . \langle revision \rangle - u \langle major \rangle . \langle minor \rangle - \langle epTeX \rangle$$

where the u part is only present for upTeX.

`\sys_if_rand_exist_p: *`
`\sys_if_rand_exist:TF *`

New: 2017-05-27

`\sys_if_rand_exist_p:`
`\sys_if_rand_exist:TF {<true code>} {<false code>}`

Tests if the engine has a pseudo-random number generator. Currently this is the case in pdfTeX, LuaTeX, pTeX, upTeX and recent releases of XeTeX.

13 Additions to l3tl

<code>\tl_range_braced:Nnn</code>	★	<code>\tl_range_braced:Nnn <tl var> {<start index>} {<end index>}</code>
<code>\tl_range_braced:cnn</code>	★	<code>\tl_range_braced:nnn {<token list>} {<start index>} {<end index>}</code>
<code>\tl_range_braced:nnn</code>	★	<code>\tl_range_unbraced:Nnn <tl var> {<start index>} {<end index>}</code>
<code>\tl_range_unbraced:Nnn</code>	★	<code>\tl_range_unbraced:nnn {<token list>} {<start index>} {<end index>}</code>
<code>\tl_range_unbraced:cnn</code>	★	Leaves in the input stream the items from the <i><start index></i> to the <i><end index></i> inclusive, using the same indexing as <code>\tl_range:nnn</code> . Spaces are ignored. Regardless of whether items appear with or without braces in the <i><token list></i> , the <code>\tl_range_braced:nnn</code> function wraps each item in braces, while <code>\tl_range_unbraced:nnn</code> does not (overall it removes an outer set of braces). For instance,
<code>\tl_range_unbraced:nnn</code>	★	

New: 2017-07-15

```

\tl_iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { 2 } { 5 } }
\tl_iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { -4 } { -1 } }
\tl_iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { -2 } { -1 } }
\tl_iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { 0 } { -1 } }

```

prints `{b}{c}{d}{e}}`, `{c}{d}{e}}{f}`, `{e}}{f}`, and an empty line to the terminal, while

```

\tl_iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { 2 } { 5 } }
\tl_iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { -4 } { -1 } }
\tl_iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { -2 } { -1 } }
\tl_iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { 0 } { -1 } }

```

prints `bcde{}`, `cde{f}`, `e{f}`, and an empty line to the terminal. Because braces are removed, the result of `\tl_range_unbraced:nnn` may have a different number of items as for `\tl_range:nnn` or `\tl_range_braced:nnn`. In cases where preserving spaces is important, consider the slower function `\tl_range:nnn`.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an x-type argument expansion.

<code>\tl_build_begin:N</code>	<code>\tl_build_begin:N <tl var></code>
<code>\tl_build_gbegin:N</code>	Clears the <i><tl var></i> and sets it up to support other <code>\tl_build_...</code> functions, which allow accumulating large numbers of tokens piece by piece much more efficiently than standard l3tl functions. Until <code>\tl_build_end:N <tl var></code> is called, applying any function from l3tl other than <code>\tl_build_...</code> will lead to incorrect results. The <code>begin</code> and <code>gbegin</code> functions must be used for local and global <i><tl var></i> respectively.

New: 2018-04-01

<code>\tl_build_clear:N</code>	<code>\tl_build_clear:N <tl var></code>
<code>\tl_build_gclear:N</code>	Clears the <i><tl var></i> and sets it up to support other <code>\tl_build_...</code> functions. The <code>clear</code> and <code>gclear</code> functions must be used for local and global <i><tl var></i> respectively.

New: 2018-04-01

```

\tl_build_put_left:Nn
\tl_build_put_left:Nx
\tl_build_gput_left:Nn
\tl_build_gput_left:Nx
\tl_build_put_right:Nn
\tl_build_put_right:Nx
\tl_build_gput_right:Nn
\tl_build_gput_right:Nx

```

New: 2018-04-01

```

\tl_build_get:NN

```

New: 2018-04-01

```

\tl_build_end:N
\tl_build_gend:N

```

New: 2018-04-01

```

\tl_build_put_left:Nn <tl var> {<tokens>}
\tl_build_put_right:Nn <tl var> {<tokens>}

```

Adds *<tokens>* to the left or right side of the current contents of *<tl var>*. The *<tl var>* must have been set up with `\tl_build_begin:N` or `\tl_build_gbegin:N`. The `put` and `gput` functions must be used for local and global *<tl var>* respectively. The `right` functions are about twice faster than the `left` functions.

```

\tl_build_get:N <tl var1> <tl var2>

```

Stores the contents of the *<tl var₁>* in the *<tl var₂>*. The *<tl var₁>* must have been set up with `\tl_build_begin:N` or `\tl_build_gbegin:N`. The *<tl var₂>* is a “normal” token list variable, assigned locally using `\tl_set:Nn`.

```

\tl_build_end:N <tl var>

```

Gets the contents of *<tl var>* and stores that into the *<tl var>* using `\tl_set:Nn`. The *<tl var>* must have been set up with `\tl_build_begin:N` or `\tl_build_gbegin:N`. The `end` and `gend` functions must be used for local and global *<tl var>* respectively. These functions completely remove the setup code that enabled *<tl var>* to be used for other `\tl_build_...` functions.

14 Additions to l3token

```

\c_catcode_active_space_tl

```

New: 2017-08-07

```

\char_to_utfviii_bytes:n ★

```

New: 2020-01-09

Token list containing one character with category code 13, (“active”), and character code 32 (space).

```

\char_to_utfviii_bytes:n {<codepoint>}

```

Converts the (Unicode) *<codepoint>* to UTF-8 bytes. The expansion of this function comprises four brace groups, each of which will contain a hexadecimal value: the appropriate byte. As UTF-8 is a variable-length, one or more of the groups may be empty: the bytes read in the logical order, such that a two-byte codepoint will have groups **#1** and **#2** filled and **#3** and **#4** empty.

```

\char_to_nfd:N ☆

```

New: 2020-01-02

```

\char_to_nfd:N <char>

```

Converts the *<char>* to the Unicode Normalization Form Canonical Decomposition. The category code of the generated character is the same as the *<char>*. With 8-bit engines, no change is made to the character.

<code>\peek_catcode_collect_inline:Nn</code>	<code>\peek_catcode_collect_inline:Nn <test token> {<inline code>}</code>
<code>\peek_charcode_collect_inline:Nn</code>	<code>\peek_charcode_collect_inline:Nn <test token> {<inline code>}</code>
<code>\peek_meaning_collect_inline:Nn</code>	<code>\peek_meaning_collect_inline:Nn <test token> {<inline code>}</code>

New: 2018-09-23

Collects and removes tokens from the input stream until finding a token that does not match the `<test token>` (as defined by the test `\token_if_eq_catcode:NNTF` or `\token_if_eq_charcode:NNTF` or `\token_if_eq_meaning:NNTF`). The collected tokens are passed to the `<inline code>` as #1. When begin-group or end-group tokens (usually { or }) are collected they are replaced by implicit `\c_group_begin_token` and `\c_group_end_token`, and when spaces (including `\c_space_token`) are collected they are replaced by explicit spaces.

For example the following code prints “Hello” to the terminal and leave “, world!” in the input stream.

```
\peek_catcode_collect_inline:Nn A { \iow_term:n {#1} } Hello,~world!
```

Another example is that the following code tests if the next token is *, ignoring intervening spaces, but putting them back using #1 if there is no *.

```
\peek_meaning_collect_inline:Nn \c_space_token
{ \peek_charcode:NNTF * { star } { no~star #1 } }
```

<code>\peek_remove_spaces:n</code>	<code>\peek_remove_spaces:n {<code>}</code>
------------------------------------	---

New: 2018-10-01

Removes explicit and implicit space tokens (category code 10 and character code 32) from the input stream, then inserts `<code>`.

Part XXXVI

Implementation

1 l3bootstrap implementation

```
1 <*initex | package>
2 <@@=kernel>
```

1.1 Format-specific code

The very first thing to do is to bootstrap the `iniTeX` system so that everything else will actually work. `TeX` does not start with some pretty basic character codes set up.

```
3 <*initex>
4 \catcode '\{ = 1 %
5 \catcode '\} = 2 %
6 \catcode '\# = 6 %
7 \catcode '\^ = 7 %
8 </initex>
```

Tab characters should not show up in the code, but to be on the safe side.

```
9 <*initex>
10 \catcode '\^^I = 10 %
```

```
11 </initex>
```

For LuaTeX, the extra primitives need to be enabled. This is not needed in package mode: common formats have the primitives enabled.

```
12 <*initex>
13 \begingroup\expandafter\expandafter\expandafter\endgroup
14 \expandafter\ifx\csname directlua\endcsname\relax
15 \else
16 \directlua{tex.enableprimitives("", tex.extraprimitives())}%
17 \fi
18 </initex>
```

Depending on the versions available, the L^AT_EX format may not have the raw `\Umath` primitive names available. We fix that globally: it should cause no issues. Older LuaTeX versions do not have a pre-built table of the primitive names here so sort one out ourselves. These end up globally-defined but at that is true with a newer format anyway and as they all start `\U` this should be reasonably safe.

```
19 <*package>
20 \begingroup
21 \expandafter\ifx\csname directlua\endcsname\relax
22 \else
23 \directlua{%
24     local i
25     local t = { }
26     for _,i in pairs(tex.extraprimitives("luatex")) do
27         if string.match(i,"^U") then
28             if not string.match(i,"^Uchar$") then %$
29                 table.insert(t,i)
30             end
31         end
32     end
33     tex.enableprimitives("", t)
34 }%
35 \fi
36 \endgroup
37 </package>
```

1.2 The `\pdfstrcmp` primitive in X_YTeX

Only pdfTeX has a primitive called `\pdfstrcmp`. The X_YTeX version is just `\strcmp`, so there is some shuffling to do. As this is still a real primitive, using the pdfTeX name is “safe”.

```
38 \begingroup\expandafter\expandafter\expandafter\endgroup
39 \expandafter\ifx\csname pdfstrcmp\endcsname\relax
40 \let\pdfstrcmp\strcmp
41 \fi
```

1.3 Loading support Lua code

When LuaTeX is used there are various pieces of Lua code which need to be loaded. The code itself is defined in `l3luatex` and is extracted into a separate file. Thus here the task is to load the Lua code both now and (if required) at the start of each job.

```
42 \begingroup\expandafter\expandafter\expandafter\endgroup
```

```

43 \expandafter\ifx\csname directlua\endcsname\relax
44 \else
45 \ifnum\luatexversion<95 %
46 \else

```

In package mode for LuaTeX we make sure the basic support is loaded: this is only necessary in plain.

```

47 (*package)
48 \begingroup\expandafter\expandafter\expandafter\endgroup
49 \expandafter\ifx\csname newcatcodetable\endcsname\relax
50 \input{ltluatex}%
51 \fi
52 \endpackage
53 \directlua{require("expl3")}%

```

As the user might be making a custom format, no assumption is made about matching package mode with only loading the Lua code once. Instead, a query to Lua reveals what mode is in operation.

```

54 \ifnum 0%
55 \directlua{
56   if status.ini_version then
57     tex.write("1")
58   end
59 }>0 %
60 \everyjob\expandafter{%
61   \the\expandafter\everyjob
62   \csname\detokenize{lua_now:n}\endcsname{require("expl3")}%
63 }%
64 \fi
65 \fi
66 \fi

```

1.4 Engine requirements

The code currently requires ϵ -TeX and functionality equivalent to `\pdfstrcmp`, and also driver and Unicode character support. This is available in a reasonably-wide range of engines.

```

67 \begingroup
68 \def\next{\endgroup}%
69 \def\ShortText{Required primitives not found}%
70 \def\LongText%
71 {%
72   LaTeX3 requires the e-TeX primitives and additional functionality as
73   described in the README file.
74   \LineBreak
75   These are available in the engines\LineBreak
76   - pdfTeX v1.40\LineBreak
77   - XeTeX v0.99992\LineBreak
78   - LuaTeX v0.95\LineBreak
79   - e-(u)pTeX mid-2012\LineBreak
80   or later.\LineBreak
81   \LineBreak
82 }%
83 \ifnum0%

```



```

84 \expandafter\ifx\csname pdfstrcmp\endcsname\relax
85 \else
86 \expandafter\ifx\csname pdftexversion\endcsname\relax
87 \expandafter\ifx\csname Ucharcat\endcsname\relax
88 \expandafter\ifx\csname kanjiskip\endcsname\relax
89 \else
90 1%
91 \fi
92 \else
93 1%
94 \fi
95 \else
96 \ifnum\pdftexversion<140 \else 1\fi
97 \fi
98 \fi
99 \expandafter\ifx\csname directlua\endcsname\relax
100 \else
101 \ifnum\luatexversion<76 \else 1\fi
102 \fi
103 =0 %
104 \newlinechar'\^^J %
105 (*initex)
106 \def\LineBreak{^^J}%
107 \edef\next
108 {%
109 \errhelp
110 {%
111 \LongText
112 For pdfTeX and XeTeX the '-etex' command-line switch is also
113 needed.\LineBreak
114 \LineBreak
115 Format building will abort!\LineBreak
116 }%
117 \errmessage{\ShortText}%
118 \endgroup
119 \noexpand\end
120 }%
121 \end{initex}
122 (*package)
123 \def\LineBreak{\noexpand\MessageBreak}%
124 \expandafter\ifx\csname PackageError\endcsname\relax
125 \def\LineBreak{^^J}%
126 \def\PackageError#1#2#3%
127 {%
128 \errhelp{#3}%
129 \errmessage{#1 Error: #2}%
130 }%
131 \fi
132 \edef\next
133 {%
134 \noexpand\PackageError{expl3}{\ShortText}
135 {\LongText Loading of expl3 will abort!}%
136 \endgroup
137 \noexpand\endinput

```

```

138         }%
139     </package>
140     \fi
141 \next

```

1.5 Extending allocators

In format mode, allocating registers is handled by `l3alloc`. However, in package mode it's much safer to rely on more general code. For example, the ability to extend \TeX 's allocation routine to allow for $\varepsilon\text{-}\text{\TeX}$ has been around since 1997 in the `etex` package.

Loading this support is delayed until here as we are now sure that the $\varepsilon\text{-}\text{\TeX}$ extensions and `\pdfstrcmp` or equivalent are available. Thus there is no danger of an “uncontrolled” error if the engine requirements are not met.

For $\text{\LaTeX}2_\varepsilon$ we need to make sure that the extended pool is being used: `expl3` uses a lot of registers. For formats from 2015 onward there is nothing to do as this is automatic. For older formats, the `etex` package needs to be loaded to do the job. In that case, some inserts are reserved also as these have to be from the standard pool. Note that `\reserveinserts` is `\outer` and so is accessed here by `csname`. In earlier versions, loading `etex` was done directly and so `\reserveinserts` appeared in the code: this then required a `\relax` after `\RequirePackage` to prevent an error with “unsafe” definitions as seen for example with `capoptions`. The optional loading here is done using a group and `\ifx` test as we are not quite in the position to have a single name for `\pdfstrcmp` just yet.

```

142 <*package>
143 \begingroup
144   \def\@tempa{LaTeX2e}%
145   \def\next{}%
146   \ifx\fmtname\@tempa
147     \expandafter\ifx\csname extrafloats\endcsname\relax
148       \def\next
149         {%
150           \RequirePackage{etex}%
151           \csname reserveinserts\endcsname{32}%
152         }%
153     \fi
154   \fi
155 \expandafter\endgroup
156 \next
157 </package>

```

1.6 Character data

\TeX needs various pieces of data to be set about characters, in particular which ones to treat as letters and which `\lccode` values apply as these affect hyphenation. It makes most sense to set this and related information up in one place. Whilst for \LuaTeX hyphenation patterns can be read anywhere, other engines have to build them into the format and so we *must* do this set up before reading the patterns. For the Unicode engines, there are shared loaders available to obtain the relevant information directly from the Unicode Consortium data files. These need standard (Ini) \TeX category codes and primitive availability and must therefore be loaded *very* early. This has a knock-on

effect on the 8-bit set up: it makes sense to do the definitions for those here as well so it is all in one place.

For Xe_LTeX and Lua_TEX, which are natively Unicode engines, simply load the Unicode data.

```

158 <*initex>
159 \ifdefined\Umathcode
160   \input load-unicode-data %
161   \input load-unicode-math-classes %
162 \else

```

For the 8-bit engines a font encoding scheme must be chosen. At present, this is the EC (T1) scheme, with the assumption that languages for which this is not appropriate will be used with one of the Unicode engines.

```

163   \begingroup

```

Lower case chars: map to themselves when lower casing and down by "20 when upper casing. (The characters a–z are set up correctly by ini_TEX.)

```

164   \def\temp{%
165     \ifnum\count0>\count2 %
166     \else
167       \global\lccode\count0 = \count0 %
168       \global\uccode\count0 = \numexpr\count0 - "20\relax
169       \advance\count0 by 1 %
170       \expandafter\temp
171     \fi
172   }
173   \count0 = "A0 %
174   \count2 = "BC %
175   \temp
176   \count0 = "E0 %
177   \count2 = "FF %
178   \temp

```

Upper case chars: map up by "20 when lower casing, to themselves when upper casing and require an \sfcode of 999. (The characters A–Z are set up correctly by ini_TEX.)

```

179   \def\temp{%
180     \ifnum\count0>\count2 %
181     \else
182       \global\lccode\count0 = \numexpr\count0 + "20\relax
183       \global\uccode\count0 = \count0 %
184       \global\sfcode\count0 = 999 %
185       \advance\count0 by 1 %
186       \expandafter\temp
187     \fi
188   }
189   \count0 = "80 %
190   \count2 = "9C %
191   \temp
192   \count0 = "C0 %
193   \count2 = "DF %
194   \temp

```

A few special cases where things are not as one might expect using the above pattern: dotless-I, dotless-J, dotted-I and d-bar.

```

195   \global\lccode'\^^Y = '\^^Y %

```

```

196 \global\uccode'\^^Y = '\I %
197 \global\lccode'\^^Z = '\^^Z %
198 \global\uccode'\^^Y = '\J %
199 \global\lccode"9D = '\i %
200 \global\uccode"9D = "9D %
201 \global\lccode"9E = "9E %
202 \global\uccode"9E = "D0 %

```

Allow hyphenation at a zero-width glyph (used to break up ligatures or to place accents between characters).

```

203 \global\lccode23 = 23 %
204 \endgroup
205 \fi
206 \</initex>

```

1.7 The L^AT_EX3 code environment

The code environment is now set up.

\ExplSyntaxOff Before changing any category codes, in package mode we need to save the situation before loading. Note the set up here means that once applied `\ExplSyntaxOff` becomes a “do nothing” command until `\ExplSyntaxOn` is used. For format mode, there is no need to save category codes so that step is skipped.

```

207 \protected\def\ExplSyntaxOff{}%
208 \*package)
209 \protected\edef\ExplSyntaxOff
210 {%
211 \protected\def\ExplSyntaxOff{}%
212 \catcode 9 = \the\catcode 9\relax
213 \catcode 32 = \the\catcode 32\relax
214 \catcode 34 = \the\catcode 34\relax
215 \catcode 38 = \the\catcode 38\relax
216 \catcode 58 = \the\catcode 58\relax
217 \catcode 94 = \the\catcode 94\relax
218 \catcode 95 = \the\catcode 95\relax
219 \catcode 124 = \the\catcode 124\relax
220 \catcode 126 = \the\catcode 126\relax
221 \endlinechar = \the\endlinechar\relax
222 \chardef\csname\detokenize{l__kernel_expl_bool}\endcsname = 0\relax
223 }%
224 \</package>

```

(End definition for `\ExplSyntaxOff`. This function is documented on page 7.)

The code environment is now set up.

```

225 \catcode 9 = 9\relax
226 \catcode 32 = 9\relax
227 \catcode 34 = 12\relax
228 \catcode 38 = 4\relax
229 \catcode 58 = 11\relax
230 \catcode 94 = 7\relax
231 \catcode 95 = 11\relax
232 \catcode 124 = 12\relax
233 \catcode 126 = 10\relax
234 \endlinechar = 32\relax

```

`\l__kernel_expl_bool` The status for experimental code syntax: this is on at present.

```
235 \chardef\l__kernel_expl_bool = 1\relax
```

(End definition for `\l__kernel_expl_bool`.)

\ExplSyntaxOn The idea here is that multiple `\ExplSyntaxOn` calls are not going to mess up category codes, and that multiple calls to `\ExplSyntaxOff` are also not wasting time. Applying `\ExplSyntaxOn` alters the definition of `\ExplSyntaxOff` and so in package mode this function should not be used until after the end of the loading process!

```
236 \protected \def \ExplSyntaxOn
237 {
238   \bool_if:NF \l__kernel_expl_bool
239   {
240     \cs_set_protected:Npx \ExplSyntaxOff
241     {
242       \char_set_catcode:nn { 9 } { \char_value_catcode:n { 9 } }
243       \char_set_catcode:nn { 32 } { \char_value_catcode:n { 32 } }
244       \char_set_catcode:nn { 34 } { \char_value_catcode:n { 34 } }
245       \char_set_catcode:nn { 38 } { \char_value_catcode:n { 38 } }
246       \char_set_catcode:nn { 58 } { \char_value_catcode:n { 58 } }
247       \char_set_catcode:nn { 94 } { \char_value_catcode:n { 94 } }
248       \char_set_catcode:nn { 95 } { \char_value_catcode:n { 95 } }
249       \char_set_catcode:nn { 124 } { \char_value_catcode:n { 124 } }
250       \char_set_catcode:nn { 126 } { \char_value_catcode:n { 126 } }
251       \tex_endlinechar:D =
252       \tex_the:D \tex_endlinechar:D \scan_stop:
253       \bool_set_false:N \l__kernel_expl_bool
254       \cs_set_protected:Npn \ExplSyntaxOff { }
255     }
256   }
257   \char_set_catcode_ignore:n { 9 } % tab
258   \char_set_catcode_ignore:n { 32 } % space
259   \char_set_catcode_other:n { 34 } % double quote
260   \char_set_catcode_alignment:n { 38 } % ampersand
261   \char_set_catcode_letter:n { 58 } % colon
262   \char_set_catcode_math_superscript:n { 94 } % circumflex
263   \char_set_catcode_letter:n { 95 } % underscore
264   \char_set_catcode_other:n { 124 } % pipe
265   \char_set_catcode_space:n { 126 } % tilde
266   \tex_endlinechar:D = 32 \scan_stop:
267   \bool_set_true:N \l__kernel_expl_bool
268 }
```

(End definition for `\ExplSyntaxOn`. This function is documented on page 7.)

```
269 </initex | package>
```

2 l3names implementation

```
270 <*initex | package>
```

The prefix here is `kernel`. A few places need `@@` to be left as is; this is obtained as `@@@`.

```
271 <@@=kernel>
```

The code here simply renames all of the primitives to new, internal, names. In format mode, it also deletes all of the existing names (although some do come back later).

The `\let` primitive is renamed by hand first as it is essential for the entire process to follow. This also uses `\global`, as that way we avoid leaving an unneeded csname in the hash table.

```
272 \let \tex_global:D \global
273 \let \tex_let:D \let
```

Everything is inside a (rather long) group, which keeps `_kernel_primitive:NN` trapped.

```
274 \begingroup
```

`_kernel_primitive:NN` A temporary function to actually do the renaming. This also allows the original names to be removed in format mode.

```
275 \long \def \_kernel\_primitive:NN #1#2
276 {
277   \tex_global:D \tex_let:D #2 #1
278   \*initex
279   \tex_global:D \tex_let:D #1 \tex_undefined:D
280   \*initex
281 }
```

(End definition for `_kernel_primitive:NN`.)

To allow extracting “just the names”, a bit of DocStrip fiddling.

```
282 \*initex | package)
283 \*initex | names | package)
```

In the current incarnation of this package, all \TeX primitives are given a new name of the form `\tex_oldname:D`. But first three special cases which have symbolic original names. These are given modified new names, so that they may be entered without catcode tricks.

```
284 \_kernel\_primitive:NN \ \tex_space:D
285 \_kernel\_primitive:NN \ / \tex_italiccorrection:D
286 \_kernel\_primitive:NN \- \tex_hyphen:D
```

Now all the other primitives.

```
287 \_kernel\_primitive:NN \above \tex_above:D
288 \_kernel\_primitive:NN \abovedisplayshortskip \tex_abovedisplayshortskip:D
289 \_kernel\_primitive:NN \abovedisplayskip \tex_abovedisplayskip:D
290 \_kernel\_primitive:NN \abovewithdelims \tex_abovewithdelims:D
291 \_kernel\_primitive:NN \accent \tex_accent:D
292 \_kernel\_primitive:NN \adjdemerits \tex_adjdemerits:D
293 \_kernel\_primitive:NN \advance \tex_advance:D
294 \_kernel\_primitive:NN \afterassignment \tex_afterassignment:D
295 \_kernel\_primitive:NN \aftergroup \tex_aftergroup:D
296 \_kernel\_primitive:NN \atop \tex_atop:D
297 \_kernel\_primitive:NN \atopwithdelims \tex_atopwithdelims:D
298 \_kernel\_primitive:NN \badness \tex_badness:D
299 \_kernel\_primitive:NN \baselineskip \tex_baselineskip:D
300 \_kernel\_primitive:NN \batchmode \tex_batchmode:D
301 \_kernel\_primitive:NN \begingroup \tex_begingroup:D
302 \_kernel\_primitive:NN \belowdisplayshortskip \tex_belowdisplayshortskip:D
303 \_kernel\_primitive:NN \belowdisplayskip \tex_belowdisplayskip:D
304 \_kernel\_primitive:NN \binoppenalty \tex_binoppenalty:D
305 \_kernel\_primitive:NN \botmark \tex_botmark:D
```

306	_kernel_primitive:NN	\box	\tex_box:D
307	_kernel_primitive:NN	\boxmaxdepth	\tex_boxmaxdepth:D
308	_kernel_primitive:NN	\brokenpenalty	\tex_brokenpenalty:D
309	_kernel_primitive:NN	\catcode	\tex_catcode:D
310	_kernel_primitive:NN	\char	\tex_char:D
311	_kernel_primitive:NN	\chardef	\tex_chardef:D
312	_kernel_primitive:NN	\cleaders	\tex_cleaders:D
313	_kernel_primitive:NN	\closein	\tex_closein:D
314	_kernel_primitive:NN	\closeout	\tex_closeout:D
315	_kernel_primitive:NN	\clubpenalty	\tex_clubpenalty:D
316	_kernel_primitive:NN	\copy	\tex_copy:D
317	_kernel_primitive:NN	\count	\tex_count:D
318	_kernel_primitive:NN	\countdef	\tex_countdef:D
319	_kernel_primitive:NN	\cr	\tex_cr:D
320	_kernel_primitive:NN	\crrcr	\tex_crrcr:D
321	_kernel_primitive:NN	\csname	\tex_csname:D
322	_kernel_primitive:NN	\day	\tex_day:D
323	_kernel_primitive:NN	\deadcycles	\tex_deadcycles:D
324	_kernel_primitive:NN	\def	\tex_def:D
325	_kernel_primitive:NN	\defaultthyphenchar	\tex_defaultthyphenchar:D
326	_kernel_primitive:NN	\defaultskewchar	\tex_defaultskewchar:D
327	_kernel_primitive:NN	\delcode	\tex_delcode:D
328	_kernel_primitive:NN	\delimiter	\tex_delimiter:D
329	_kernel_primitive:NN	\delimiterfactor	\tex_delimiterfactor:D
330	_kernel_primitive:NN	\delimitershortfall	\tex_delimitershortfall:D
331	_kernel_primitive:NN	\dimen	\tex_dimen:D
332	_kernel_primitive:NN	\dimendef	\tex_dimendef:D
333	_kernel_primitive:NN	\discretionary	\tex_discretionary:D
334	_kernel_primitive:NN	\displayindent	\tex_displayindent:D
335	_kernel_primitive:NN	\displaylimits	\tex_displaylimits:D
336	_kernel_primitive:NN	\displaystyle	\tex_displaystyle:D
337	_kernel_primitive:NN	\displaywidowpenalty	\tex_displaywidowpenalty:D
338	_kernel_primitive:NN	\displaywidth	\tex_displaywidth:D
339	_kernel_primitive:NN	\divide	\tex_divide:D
340	_kernel_primitive:NN	\doublehyphendemerits	\tex_doublehyphendemerits:D
341	_kernel_primitive:NN	\dp	\tex_dp:D
342	_kernel_primitive:NN	\dump	\tex_dump:D
343	_kernel_primitive:NN	\edef	\tex_edef:D
344	_kernel_primitive:NN	\else	\tex_else:D
345	_kernel_primitive:NN	\emergencystretch	\tex_emergencystretch:D
346	_kernel_primitive:NN	\end	\tex_end:D
347	_kernel_primitive:NN	\endcsname	\tex_endcsname:D
348	_kernel_primitive:NN	\endgroup	\tex_endgroup:D
349	_kernel_primitive:NN	\endinput	\tex_endinput:D
350	_kernel_primitive:NN	\endlinechar	\tex_endlinechar:D
351	_kernel_primitive:NN	\eqno	\tex_eqno:D
352	_kernel_primitive:NN	\errhelp	\tex_errhelp:D
353	_kernel_primitive:NN	\errmessage	\tex_errmessage:D
354	_kernel_primitive:NN	\errorcontextlines	\tex_errorcontextlines:D
355	_kernel_primitive:NN	\errorstopmode	\tex_errorstopmode:D
356	_kernel_primitive:NN	\escapechar	\tex_escapechar:D
357	_kernel_primitive:NN	\everycr	\tex_everycr:D
358	_kernel_primitive:NN	\everydisplay	\tex_everydisplay:D
359	_kernel_primitive:NN	\everyhbox	\tex_everyhbox:D

360	_kernel_primitive:NN	\everyjob	\tex_everyjob:D
361	_kernel_primitive:NN	\everymath	\tex_everymath:D
362	_kernel_primitive:NN	\everypar	\tex_everypar:D
363	_kernel_primitive:NN	\everyvbox	\tex_everyvbox:D
364	_kernel_primitive:NN	\exhyphenpenalty	\tex_exhyphenpenalty:D
365	_kernel_primitive:NN	\expandafter	\tex_expandafter:D
366	_kernel_primitive:NN	\fam	\tex_fam:D
367	_kernel_primitive:NN	\fi	\tex_fi:D
368	_kernel_primitive:NN	\finalhyphendemerits	\tex_finalhyphendemerits:D
369	_kernel_primitive:NN	\firstmark	\tex_firstmark:D
370	_kernel_primitive:NN	\floatingpenalty	\tex_floatingpenalty:D
371	_kernel_primitive:NN	\font	\tex_font:D
372	_kernel_primitive:NN	\fontdimen	\tex_fontdimen:D
373	_kernel_primitive:NN	\fontname	\tex_fontname:D
374	_kernel_primitive:NN	\futurelet	\tex_futurelet:D
375	_kernel_primitive:NN	\gdef	\tex_gdef:D
376	_kernel_primitive:NN	\global	\tex_global:D
377	_kernel_primitive:NN	\globaldefs	\tex_globaldefs:D
378	_kernel_primitive:NN	\halign	\tex_halign:D
379	_kernel_primitive:NN	\hangafter	\tex_hangafter:D
380	_kernel_primitive:NN	\hangindent	\tex_hangindent:D
381	_kernel_primitive:NN	\hbadness	\tex_hbadness:D
382	_kernel_primitive:NN	\hbox	\tex_hbox:D
383	_kernel_primitive:NN	\hfil	\tex_hfil:D
384	_kernel_primitive:NN	\hfill	\tex_hfill:D
385	_kernel_primitive:NN	\hfilneg	\tex_hfilneg:D
386	_kernel_primitive:NN	\hfuzz	\tex_hfuzz:D
387	_kernel_primitive:NN	\hoffset	\tex_hoffset:D
388	_kernel_primitive:NN	\holdinginserts	\tex_holdinginserts:D
389	_kernel_primitive:NN	\hrule	\tex_hrule:D
390	_kernel_primitive:NN	\hsize	\tex_hsize:D
391	_kernel_primitive:NN	\hskip	\tex_hskip:D
392	_kernel_primitive:NN	\hss	\tex_hss:D
393	_kernel_primitive:NN	\ht	\tex_ht:D
394	_kernel_primitive:NN	\hyphenation	\tex_hyphenation:D
395	_kernel_primitive:NN	\hyphenchar	\tex_hyphenchar:D
396	_kernel_primitive:NN	\hyphenpenalty	\tex_hyphenpenalty:D
397	_kernel_primitive:NN	\if	\tex_if:D
398	_kernel_primitive:NN	\ifcase	\tex_ifcase:D
399	_kernel_primitive:NN	\ifcat	\tex_ifcat:D
400	_kernel_primitive:NN	\ifdim	\tex_ifdim:D
401	_kernel_primitive:NN	\ifeof	\tex_ifeof:D
402	_kernel_primitive:NN	\iffalse	\tex_iffalse:D
403	_kernel_primitive:NN	\ifhbox	\tex_ifhbox:D
404	_kernel_primitive:NN	\ifhmode	\tex_ifhmode:D
405	_kernel_primitive:NN	\ifinner	\tex_ifinner:D
406	_kernel_primitive:NN	\ifmmode	\tex_ifmmode:D
407	_kernel_primitive:NN	\ifnum	\tex_ifnum:D
408	_kernel_primitive:NN	\ifodd	\tex_ifodd:D
409	_kernel_primitive:NN	\iftrue	\tex_iftrue:D
410	_kernel_primitive:NN	\ifvbox	\tex_ifvbox:D
411	_kernel_primitive:NN	\ifvmode	\tex_ifvmode:D
412	_kernel_primitive:NN	\ifvoid	\tex_ifvoid:D
413	_kernel_primitive:NN	\ifx	\tex_ifx:D

414	<code>_kernel_primitive:NN \ignorespaces</code>	<code>\tex_ignorespaces:D</code>
415	<code>_kernel_primitive:NN \immediate</code>	<code>\tex_immediate:D</code>
416	<code>_kernel_primitive:NN \indent</code>	<code>\tex_indent:D</code>
417	<code>_kernel_primitive:NN \input</code>	<code>\tex_input:D</code>
418	<code>_kernel_primitive:NN \inputlineno</code>	<code>\tex_inputlineno:D</code>
419	<code>_kernel_primitive:NN \insert</code>	<code>\tex_insert:D</code>
420	<code>_kernel_primitive:NN \insertpenalties</code>	<code>\tex_insertpenalties:D</code>
421	<code>_kernel_primitive:NN \interlinepenalty</code>	<code>\tex_interlinepenalty:D</code>
422	<code>_kernel_primitive:NN \jobname</code>	<code>\tex_jobname:D</code>
423	<code>_kernel_primitive:NN \kern</code>	<code>\tex_kern:D</code>
424	<code>_kernel_primitive:NN \language</code>	<code>\tex_language:D</code>
425	<code>_kernel_primitive:NN \lastbox</code>	<code>\tex_lastbox:D</code>
426	<code>_kernel_primitive:NN \lastkern</code>	<code>\tex_lastkern:D</code>
427	<code>_kernel_primitive:NN \lastpenalty</code>	<code>\tex_lastpenalty:D</code>
428	<code>_kernel_primitive:NN \lastskip</code>	<code>\tex_lastskip:D</code>
429	<code>_kernel_primitive:NN \lccode</code>	<code>\tex_lccode:D</code>
430	<code>_kernel_primitive:NN \leaders</code>	<code>\tex_leaders:D</code>
431	<code>_kernel_primitive:NN \left</code>	<code>\tex_left:D</code>
432	<code>_kernel_primitive:NN \lefthyphenmin</code>	<code>\tex_lefthyphenmin:D</code>
433	<code>_kernel_primitive:NN \leftskip</code>	<code>\tex_leftskip:D</code>
434	<code>_kernel_primitive:NN \leqno</code>	<code>\tex_leqno:D</code>
435	<code>_kernel_primitive:NN \let</code>	<code>\tex_let:D</code>
436	<code>_kernel_primitive:NN \limits</code>	<code>\tex_limits:D</code>
437	<code>_kernel_primitive:NN \linepenalty</code>	<code>\tex_linepenalty:D</code>
438	<code>_kernel_primitive:NN \lineskip</code>	<code>\tex_lineskip:D</code>
439	<code>_kernel_primitive:NN \lineskiplimit</code>	<code>\tex_lineskiplimit:D</code>
440	<code>_kernel_primitive:NN \long</code>	<code>\tex_long:D</code>
441	<code>_kernel_primitive:NN \looseness</code>	<code>\tex_looseness:D</code>
442	<code>_kernel_primitive:NN \lower</code>	<code>\tex_lower:D</code>
443	<code>_kernel_primitive:NN \lowercase</code>	<code>\tex_lowercase:D</code>
444	<code>_kernel_primitive:NN \mag</code>	<code>\tex_mag:D</code>
445	<code>_kernel_primitive:NN \mark</code>	<code>\tex_mark:D</code>
446	<code>_kernel_primitive:NN \mathaccent</code>	<code>\tex_mathaccent:D</code>
447	<code>_kernel_primitive:NN \mathbin</code>	<code>\tex_mathbin:D</code>
448	<code>_kernel_primitive:NN \mathchar</code>	<code>\tex_mathchar:D</code>
449	<code>_kernel_primitive:NN \mathchardef</code>	<code>\tex_mathchardef:D</code>
450	<code>_kernel_primitive:NN \mathchoice</code>	<code>\tex_mathchoice:D</code>
451	<code>_kernel_primitive:NN \mathclose</code>	<code>\tex_mathclose:D</code>
452	<code>_kernel_primitive:NN \mathcode</code>	<code>\tex_mathcode:D</code>
453	<code>_kernel_primitive:NN \mathinner</code>	<code>\tex_mathinner:D</code>
454	<code>_kernel_primitive:NN \mathop</code>	<code>\tex_mathop:D</code>
455	<code>_kernel_primitive:NN \mathopen</code>	<code>\tex_mathopen:D</code>
456	<code>_kernel_primitive:NN \mathord</code>	<code>\tex_mathord:D</code>
457	<code>_kernel_primitive:NN \mathpunct</code>	<code>\tex_mathpunct:D</code>
458	<code>_kernel_primitive:NN \mathrel</code>	<code>\tex_mathrel:D</code>
459	<code>_kernel_primitive:NN \mathsurround</code>	<code>\tex_mathsurround:D</code>
460	<code>_kernel_primitive:NN \maxdeadcycles</code>	<code>\tex_maxdeadcycles:D</code>
461	<code>_kernel_primitive:NN \maxdepth</code>	<code>\tex_maxdepth:D</code>
462	<code>_kernel_primitive:NN \meaning</code>	<code>\tex_meaning:D</code>
463	<code>_kernel_primitive:NN \medmuskip</code>	<code>\tex_medmuskip:D</code>
464	<code>_kernel_primitive:NN \message</code>	<code>\tex_message:D</code>
465	<code>_kernel_primitive:NN \mkern</code>	<code>\tex_mkern:D</code>
466	<code>_kernel_primitive:NN \month</code>	<code>\tex_month:D</code>
467	<code>_kernel_primitive:NN \moveleft</code>	<code>\tex_moveleft:D</code>

468	_kernel_primitive:NN	\moveright	\tex_moveright:D
469	_kernel_primitive:NN	\mskip	\tex_mskip:D
470	_kernel_primitive:NN	\multiply	\tex_multiply:D
471	_kernel_primitive:NN	\muskip	\tex_muskip:D
472	_kernel_primitive:NN	\muskipdef	\tex_muskipdef:D
473	_kernel_primitive:NN	\newlinechar	\tex_newlinechar:D
474	_kernel_primitive:NN	\noalign	\tex_noalign:D
475	_kernel_primitive:NN	\noboundary	\tex_noboundary:D
476	_kernel_primitive:NN	\noexpand	\tex_noexpand:D
477	_kernel_primitive:NN	\noindent	\tex_noindent:D
478	_kernel_primitive:NN	\nolimits	\tex_nolimits:D
479	_kernel_primitive:NN	\nonscript	\tex_nonscript:D
480	_kernel_primitive:NN	\nonstopmode	\tex_nonstopmode:D
481	_kernel_primitive:NN	\nulldelimiterspace	\tex_nulldelimiterspace:D
482	_kernel_primitive:NN	\nullfont	\tex_nullfont:D
483	_kernel_primitive:NN	\number	\tex_number:D
484	_kernel_primitive:NN	\omit	\tex_omit:D
485	_kernel_primitive:NN	\openin	\tex_openin:D
486	_kernel_primitive:NN	\openout	\tex_openout:D
487	_kernel_primitive:NN	\or	\tex_or:D
488	_kernel_primitive:NN	\outer	\tex_outer:D
489	_kernel_primitive:NN	\output	\tex_output:D
490	_kernel_primitive:NN	\outputpenalty	\tex_outputpenalty:D
491	_kernel_primitive:NN	\over	\tex_over:D
492	_kernel_primitive:NN	\overfullrule	\tex_overfullrule:D
493	_kernel_primitive:NN	\overline	\tex_overline:D
494	_kernel_primitive:NN	\overwithdelims	\tex_overwithdelims:D
495	_kernel_primitive:NN	\pagedepth	\tex_pagedepth:D
496	_kernel_primitive:NN	\pagefilllstretch	\tex_pagefilllstretch:D
497	_kernel_primitive:NN	\pagefillstretch	\tex_pagefillstretch:D
498	_kernel_primitive:NN	\pagefilstretch	\tex_pagefilstretch:D
499	_kernel_primitive:NN	\pagegoal	\tex_pagegoal:D
500	_kernel_primitive:NN	\pageshrink	\tex_pageshrink:D
501	_kernel_primitive:NN	\pagestretch	\tex_pagestretch:D
502	_kernel_primitive:NN	\pagetotal	\tex_pagetotal:D
503	_kernel_primitive:NN	\par	\tex_par:D
504	_kernel_primitive:NN	\parfillskip	\tex_parfillskip:D
505	_kernel_primitive:NN	\parindent	\tex_parindent:D
506	_kernel_primitive:NN	\parshape	\tex_parshape:D
507	_kernel_primitive:NN	\parskip	\tex_parskip:D
508	_kernel_primitive:NN	\patterns	\tex_patterns:D
509	_kernel_primitive:NN	\pausing	\tex_pausing:D
510	_kernel_primitive:NN	\penalty	\tex_penalty:D
511	_kernel_primitive:NN	\postdisplaypenalty	\tex_postdisplaypenalty:D
512	_kernel_primitive:NN	\predisdisplaypenalty	\tex_predisdisplaypenalty:D
513	_kernel_primitive:NN	\predisplaysize	\tex_predisplaysize:D
514	_kernel_primitive:NN	\pretolerance	\tex_pretolerance:D
515	_kernel_primitive:NN	\prevdepth	\tex_prevdepth:D
516	_kernel_primitive:NN	\prevgraf	\tex_prevgraf:D
517	_kernel_primitive:NN	\radical	\tex_radical:D
518	_kernel_primitive:NN	\raise	\tex_raise:D
519	_kernel_primitive:NN	\read	\tex_read:D
520	_kernel_primitive:NN	\relax	\tex_relax:D
521	_kernel_primitive:NN	\relpenalty	\tex_relpenalty:D

522	_kernel_primitive:NN	\right	\tex_right:D
523	_kernel_primitive:NN	\righthyphenmin	\tex_righthyphenmin:D
524	_kernel_primitive:NN	\rightskip	\tex_rightskip:D
525	_kernel_primitive:NN	\romannumeral	\tex_romannumeral:D
526	_kernel_primitive:NN	\scriptfont	\tex_scriptfont:D
527	_kernel_primitive:NN	\scriptscriptfont	\tex_scriptscriptfont:D
528	_kernel_primitive:NN	\scriptscriptstyle	\tex_scriptscriptstyle:D
529	_kernel_primitive:NN	\scriptspace	\tex_scriptspace:D
530	_kernel_primitive:NN	\scriptstyle	\tex_scriptstyle:D
531	_kernel_primitive:NN	\scrollmode	\tex_scrollmode:D
532	_kernel_primitive:NN	\setbox	\tex_setbox:D
533	_kernel_primitive:NN	\setlanguage	\tex_setlanguage:D
534	_kernel_primitive:NN	\sfcode	\tex_sfcode:D
535	_kernel_primitive:NN	\shipout	\tex_shipout:D
536	_kernel_primitive:NN	\show	\tex_show:D
537	_kernel_primitive:NN	\showbox	\tex_showbox:D
538	_kernel_primitive:NN	\showboxbreadth	\tex_showboxbreadth:D
539	_kernel_primitive:NN	\showboxdepth	\tex_showboxdepth:D
540	_kernel_primitive:NN	\showlists	\tex_showlists:D
541	_kernel_primitive:NN	\showthe	\tex_showthe:D
542	_kernel_primitive:NN	\skewchar	\tex_skewchar:D
543	_kernel_primitive:NN	\skip	\tex_skip:D
544	_kernel_primitive:NN	\skipdef	\tex_skipdef:D
545	_kernel_primitive:NN	\spacefactor	\tex_spacefactor:D
546	_kernel_primitive:NN	\spaceskip	\tex_spaceskip:D
547	_kernel_primitive:NN	\span	\tex_span:D
548	_kernel_primitive:NN	\special	\tex_special:D
549	_kernel_primitive:NN	\splitbotmark	\tex_splitbotmark:D
550	_kernel_primitive:NN	\splitfirstmark	\tex_splitfirstmark:D
551	_kernel_primitive:NN	\splitmaxdepth	\tex_splitmaxdepth:D
552	_kernel_primitive:NN	\splittopskip	\tex_splittopskip:D
553	_kernel_primitive:NN	\string	\tex_string:D
554	_kernel_primitive:NN	\tabskip	\tex_tabskip:D
555	_kernel_primitive:NN	\textfont	\tex_textfont:D
556	_kernel_primitive:NN	\textstyle	\tex_textstyle:D
557	_kernel_primitive:NN	\the	\tex_the:D
558	_kernel_primitive:NN	\thickmuskip	\tex_thickmuskip:D
559	_kernel_primitive:NN	\thinmuskip	\tex_thinmuskip:D
560	_kernel_primitive:NN	\time	\tex_time:D
561	_kernel_primitive:NN	\toks	\tex_toks:D
562	_kernel_primitive:NN	\toksdef	\tex_toksdef:D
563	_kernel_primitive:NN	\tolerance	\tex_tolerance:D
564	_kernel_primitive:NN	\topmark	\tex_topmark:D
565	_kernel_primitive:NN	\topskip	\tex_topskip:D
566	_kernel_primitive:NN	\tracingcommands	\tex_tracingcommands:D
567	_kernel_primitive:NN	\tracinglostchars	\tex_tracinglostchars:D
568	_kernel_primitive:NN	\tracingmacros	\tex_tracingmacros:D
569	_kernel_primitive:NN	\tracingonline	\tex_tracingonline:D
570	_kernel_primitive:NN	\tracingoutput	\tex_tracingoutput:D
571	_kernel_primitive:NN	\tracingpages	\tex_tracingpages:D
572	_kernel_primitive:NN	\tracingparagraphs	\tex_tracingparagraphs:D
573	_kernel_primitive:NN	\tracingrestores	\tex_tracingrestores:D
574	_kernel_primitive:NN	\tracingstats	\tex_tracingstats:D
575	_kernel_primitive:NN	\uccode	\tex_uccode:D

576	_kernel_primitive:NN	\uchyph	\tex_uchyph:D
577	_kernel_primitive:NN	\underline	\tex_underline:D
578	_kernel_primitive:NN	\unhbox	\tex_unhbox:D
579	_kernel_primitive:NN	\unhcopy	\tex_unhcopy:D
580	_kernel_primitive:NN	\unkern	\tex_unkern:D
581	_kernel_primitive:NN	\unpenalty	\tex_unpenalty:D
582	_kernel_primitive:NN	\unskip	\tex_unskip:D
583	_kernel_primitive:NN	\unvbox	\tex_unvbox:D
584	_kernel_primitive:NN	\unvcopy	\tex_unvcopy:D
585	_kernel_primitive:NN	\uppercase	\tex_uppercase:D
586	_kernel_primitive:NN	\vadjust	\tex_vadjust:D
587	_kernel_primitive:NN	\valign	\tex_valign:D
588	_kernel_primitive:NN	\vbadness	\tex_vbadness:D
589	_kernel_primitive:NN	\vbox	\tex_vbox:D
590	_kernel_primitive:NN	\vcenter	\tex_vcenter:D
591	_kernel_primitive:NN	\vfil	\tex_vfil:D
592	_kernel_primitive:NN	\vfill	\tex_vfill:D
593	_kernel_primitive:NN	\vfилneg	\tex_vfилneg:D
594	_kernel_primitive:NN	\vfuzz	\tex_vfuzz:D
595	_kernel_primitive:NN	\voffset	\tex_voffset:D
596	_kernel_primitive:NN	\vrule	\tex_vrule:D
597	_kernel_primitive:NN	\vsize	\tex_vsize:D
598	_kernel_primitive:NN	\vskip	\tex_vskip:D
599	_kernel_primitive:NN	\vsplit	\tex_vsplit:D
600	_kernel_primitive:NN	\vss	\tex_vss:D
601	_kernel_primitive:NN	\vtop	\tex_vtop:D
602	_kernel_primitive:NN	\wd	\tex_wd:D
603	_kernel_primitive:NN	\widowpenalty	\tex_widowpenalty:D
604	_kernel_primitive:NN	\write	\tex_write:D
605	_kernel_primitive:NN	\xdef	\tex_xdef:D
606	_kernel_primitive:NN	\xleaders	\tex_xleaders:D
607	_kernel_primitive:NN	\xspaceskip	\tex_xspaceskip:D
608	_kernel_primitive:NN	\year	\tex_year:D

Primitives introduced by ε -TeX.

609	_kernel_primitive:NN	\beginL	\tex_beginL:D
610	_kernel_primitive:NN	\beginR	\tex_beginR:D
611	_kernel_primitive:NN	\botmarks	\tex_botmarks:D
612	_kernel_primitive:NN	\clubpenalties	\tex_clubpenalties:D
613	_kernel_primitive:NN	\currentgrouplevel	\tex_currentgrouplevel:D
614	_kernel_primitive:NN	\currentgrouptype	\tex_currentgrouptype:D
615	_kernel_primitive:NN	\currentifbranch	\tex_currentifbranch:D
616	_kernel_primitive:NN	\currentiflevel	\tex_currentiflevel:D
617	_kernel_primitive:NN	\currentifttype	\tex_currentifttype:D
618	_kernel_primitive:NN	\detokenize	\tex_detokenize:D
619	_kernel_primitive:NN	\dimexpr	\tex_dimexpr:D
620	_kernel_primitive:NN	\displaywidowpenalties	\tex_displaywidowpenalties:D
621	_kernel_primitive:NN	\endL	\tex_endL:D
622	_kernel_primitive:NN	\endR	\tex_endR:D
623	_kernel_primitive:NN	\eTeXrevision	\tex_eTeXrevision:D
624	_kernel_primitive:NN	\eTeXversion	\tex_eTeXversion:D
625	_kernel_primitive:NN	\everyeof	\tex_everyeof:D
626	_kernel_primitive:NN	\firstmarks	\tex_firstmarks:D
627	_kernel_primitive:NN	\fontchardp	\tex_fontchardp:D
628	_kernel_primitive:NN	\fontcharht	\tex_fontcharht:D

629	<code>__kernel_primitive:NN \fontcharic</code>	<code>\tex_fontcharic:D</code>
630	<code>__kernel_primitive:NN \fontcharwd</code>	<code>\tex_fontcharwd:D</code>
631	<code>__kernel_primitive:NN \glueexpr</code>	<code>\tex_glueexpr:D</code>
632	<code>__kernel_primitive:NN \glueshrink</code>	<code>\tex_glueshrink:D</code>
633	<code>__kernel_primitive:NN \glueshrinkorder</code>	<code>\tex_glueshrinkorder:D</code>
634	<code>__kernel_primitive:NN \gluestretch</code>	<code>\tex_gluestretch:D</code>
635	<code>__kernel_primitive:NN \gluestretchorder</code>	<code>\tex_gluestretchorder:D</code>
636	<code>__kernel_primitive:NN \gluetomu</code>	<code>\tex_gluetomu:D</code>
637	<code>__kernel_primitive:NN \ifcsname</code>	<code>\tex_ifcsname:D</code>
638	<code>__kernel_primitive:NN \ifdefined</code>	<code>\tex_ifdefined:D</code>
639	<code>__kernel_primitive:NN \iffontchar</code>	<code>\tex_iffontchar:D</code>
640	<code>__kernel_primitive:NN \interactionmode</code>	<code>\tex_interactionmode:D</code>
641	<code>__kernel_primitive:NN \interlinepenalties</code>	<code>\tex_interlinepenalties:D</code>
642	<code>__kernel_primitive:NN \lastlinefit</code>	<code>\tex_lastlinefit:D</code>
643	<code>__kernel_primitive:NN \lastnodetype</code>	<code>\tex_lastnodetype:D</code>
644	<code>__kernel_primitive:NN \marks</code>	<code>\tex_marks:D</code>
645	<code>__kernel_primitive:NN \middle</code>	<code>\tex_middle:D</code>
646	<code>__kernel_primitive:NN \muexpr</code>	<code>\tex_muexpr:D</code>
647	<code>__kernel_primitive:NN \mutoglu</code>	<code>\tex_mutoglu:D</code>
648	<code>__kernel_primitive:NN \numexpr</code>	<code>\tex_numexpr:D</code>
649	<code>__kernel_primitive:NN \pagediscards</code>	<code>\tex_pagediscards:D</code>
650	<code>__kernel_primitive:NN \parshapedimen</code>	<code>\tex_parshapedimen:D</code>
651	<code>__kernel_primitive:NN \parshapeindent</code>	<code>\tex_parshapeindent:D</code>
652	<code>__kernel_primitive:NN \parshapelength</code>	<code>\tex_parshapelength:D</code>
653	<code>__kernel_primitive:NN \predisplaydirection</code>	<code>\tex_predisplaydirection:D</code>
654	<code>__kernel_primitive:NN \protected</code>	<code>\tex_protected:D</code>
655	<code>__kernel_primitive:NN \readline</code>	<code>\tex_readline:D</code>
656	<code>__kernel_primitive:NN \savinghyphcodes</code>	<code>\tex_savinghyphcodes:D</code>
657	<code>__kernel_primitive:NN \savingvdiscards</code>	<code>\tex_savingvdiscards:D</code>
658	<code>__kernel_primitive:NN \scantokens</code>	<code>\tex_scantokens:D</code>
659	<code>__kernel_primitive:NN \showgroups</code>	<code>\tex_showgroups:D</code>
660	<code>__kernel_primitive:NN \showifs</code>	<code>\tex_showifs:D</code>
661	<code>__kernel_primitive:NN \showtokens</code>	<code>\tex_showtokens:D</code>
662	<code>__kernel_primitive:NN \splitbotmarks</code>	<code>\tex_splitbotmarks:D</code>
663	<code>__kernel_primitive:NN \splitdiscards</code>	<code>\tex_splitdiscards:D</code>
664	<code>__kernel_primitive:NN \splitfirstmarks</code>	<code>\tex_splitfirstmarks:D</code>
665	<code>__kernel_primitive:NN \TeXXeTstate</code>	<code>\tex_TeXeTstate:D</code>
666	<code>__kernel_primitive:NN \topmarks</code>	<code>\tex_topmarks:D</code>
667	<code>__kernel_primitive:NN \tracingassigns</code>	<code>\tex_tracingassigns:D</code>
668	<code>__kernel_primitive:NN \tracinggroups</code>	<code>\tex_tracinggroups:D</code>
669	<code>__kernel_primitive:NN \tracingifs</code>	<code>\tex_tracingifs:D</code>
670	<code>__kernel_primitive:NN \tracingnesting</code>	<code>\tex_tracingnesting:D</code>
671	<code>__kernel_primitive:NN \tracingscantokens</code>	<code>\tex_tracingscantokens:D</code>
672	<code>__kernel_primitive:NN \unexpanded</code>	<code>\tex_unexpanded:D</code>
673	<code>__kernel_primitive:NN \unless</code>	<code>\tex_unless:D</code>
674	<code>__kernel_primitive:NN \widowpenalties</code>	<code>\tex_widowpenalties:D</code>

Post- ϵ - \TeX primitives do not always end up with the same name in all engines, if indeed they are available cross-engine anyway. We therefore take the approach of preferring the shortest name that makes sense. First, we deal with the primitives introduced by pdf \TeX which directly relate to PDF output: these are copied with the names unchanged.

675	<code>__kernel_primitive:NN \pdfannot</code>	<code>\tex_pdfannot:D</code>
676	<code>__kernel_primitive:NN \pdfcatalog</code>	<code>\tex_pdfcatalog:D</code>
677	<code>__kernel_primitive:NN \pdfcompresslevel</code>	<code>\tex_pdfcompresslevel:D</code>

678	_kernel_primitive:NN	\pdfcolorstack	\tex_pdfcolorstack:D
679	_kernel_primitive:NN	\pdfcolorstackinit	\tex_pdfcolorstackinit:D
680	_kernel_primitive:NN	\pdfcreationdate	\tex_pdfcreationdate:D
681	_kernel_primitive:NN	\pdfdecimaldigits	\tex_pdfdecimaldigits:D
682	_kernel_primitive:NN	\pdfdest	\tex_pdfdest:D
683	_kernel_primitive:NN	\pdfdestmargin	\tex_pdfdestmargin:D
684	_kernel_primitive:NN	\pdfendlink	\tex_pdfendlink:D
685	_kernel_primitive:NN	\pdfendthread	\tex_pdfendthread:D
686	_kernel_primitive:NN	\pdffontattr	\tex_pdffontattr:D
687	_kernel_primitive:NN	\pdffontname	\tex_pdffontname:D
688	_kernel_primitive:NN	\pdffontobjnum	\tex_pdffontobjnum:D
689	_kernel_primitive:NN	\pdfgamma	\tex_pdfgamma:D
690	_kernel_primitive:NN	\pdfimageapplygamma	\tex_pdfimageapplygamma:D
691	_kernel_primitive:NN	\pdfimagegamma	\tex_pdfimagegamma:D
692	_kernel_primitive:NN	\pdfgentounicode	\tex_pdfgentounicode:D
693	_kernel_primitive:NN	\pdfglyphtounicode	\tex_pdfglyphtounicode:D
694	_kernel_primitive:NN	\pdfhorigin	\tex_pdfhorigin:D
695	_kernel_primitive:NN	\pdfimagehicolor	\tex_pdfimagehicolor:D
696	_kernel_primitive:NN	\pdfimageresolution	\tex_pdfimageresolution:D
697	_kernel_primitive:NN	\pdfincludechars	\tex_pdfincludechars:D
698	_kernel_primitive:NN	\pdfinclusioncopyfonts	\tex_pdfinclusioncopyfonts:D
699	_kernel_primitive:NN	\pdfinclusionerrorlevel	
700		\tex_pdfinclusionerrorlevel:D	
701	_kernel_primitive:NN	\pdfinfo	\tex_pdfinfo:D
702	_kernel_primitive:NN	\pdflastannot	\tex_pdflastannot:D
703	_kernel_primitive:NN	\pdflastlink	\tex_pdflastlink:D
704	_kernel_primitive:NN	\pdflastobj	\tex_pdflastobj:D
705	_kernel_primitive:NN	\pdflastxform	\tex_pdflastxform:D
706	_kernel_primitive:NN	\pdflastximage	\tex_pdflastximage:D
707	_kernel_primitive:NN	\pdflastximagecolordepth	
708		\tex_pdflastximagecolordepth:D	
709	_kernel_primitive:NN	\pdflastximagepages	\tex_pdflastximagepages:D
710	_kernel_primitive:NN	\pdflinkmargin	\tex_pdflinkmargin:D
711	_kernel_primitive:NN	\pdfliteral	\tex_pdfliteral:D
712	_kernel_primitive:NN	\pdfmajorversion	\tex_pdfmajorversion:D
713	_kernel_primitive:NN	\pdfminorversion	\tex_pdfminorversion:D
714	_kernel_primitive:NN	\pdfnames	\tex_pdfnames:D
715	_kernel_primitive:NN	\pdfobj	\tex_pdfobj:D
716	_kernel_primitive:NN	\pdfobjcompresslevel	\tex_pdfobjcompresslevel:D
717	_kernel_primitive:NN	\pdfoutline	\tex_pdfoutline:D
718	_kernel_primitive:NN	\pdfoutput	\tex_pdfoutput:D
719	_kernel_primitive:NN	\pdfpageattr	\tex_pdfpageattr:D
720	_kernel_primitive:NN	\pdfpagesattr	\tex_pdfpagesattr:D
721	_kernel_primitive:NN	\pdfpagebox	\tex_pdfpagebox:D
722	_kernel_primitive:NN	\pdfpageref	\tex_pdfpageref:D
723	_kernel_primitive:NN	\pdfpageresources	\tex_pdfpageresources:D
724	_kernel_primitive:NN	\pdfpagesattr	\tex_pdfpagesattr:D
725	_kernel_primitive:NN	\pdfrefobj	\tex_pdfrefobj:D
726	_kernel_primitive:NN	\pdfrefxform	\tex_pdfrefxform:D
727	_kernel_primitive:NN	\pdfrefximage	\tex_pdfrefximage:D
728	_kernel_primitive:NN	\pdfrestore	\tex_pdfrestore:D
729	_kernel_primitive:NN	\pdfretval	\tex_pdfretval:D
730	_kernel_primitive:NN	\pdfsave	\tex_pdfsave:D
731	_kernel_primitive:NN	\pdfsetmatrix	\tex_pdfsetmatrix:D

732	<code>__kernel_primitive:NN</code>	<code>\pdfstartlink</code>	<code>\tex_pdfstartlink:D</code>
733	<code>__kernel_primitive:NN</code>	<code>\pdfstartthread</code>	<code>\tex_pdfstartthread:D</code>
734	<code>__kernel_primitive:NN</code>	<code>\pdfsuppressptexinfo</code>	<code>\tex_pdfsuppressptexinfo:D</code>
735	<code>__kernel_primitive:NN</code>	<code>\pdfthread</code>	<code>\tex_pdfthread:D</code>
736	<code>__kernel_primitive:NN</code>	<code>\pdfthreadmargin</code>	<code>\tex_pdfthreadmargin:D</code>
737	<code>__kernel_primitive:NN</code>	<code>\pdftrailer</code>	<code>\tex_pdftrailer:D</code>
738	<code>__kernel_primitive:NN</code>	<code>\pdfuniqueresname</code>	<code>\tex_pdfuniqueresname:D</code>
739	<code>__kernel_primitive:NN</code>	<code>\pdfvorigin</code>	<code>\tex_pdfvorigin:D</code>
740	<code>__kernel_primitive:NN</code>	<code>\pdfxform</code>	<code>\tex_pdfxform:D</code>
741	<code>__kernel_primitive:NN</code>	<code>\pdfxformattr</code>	<code>\tex_pdfxformattr:D</code>
742	<code>__kernel_primitive:NN</code>	<code>\pdfxformname</code>	<code>\tex_pdfxformname:D</code>
743	<code>__kernel_primitive:NN</code>	<code>\pdfxformresources</code>	<code>\tex_pdfxformresources:D</code>
744	<code>__kernel_primitive:NN</code>	<code>\pdfximage</code>	<code>\tex_pdfximage:D</code>
745	<code>__kernel_primitive:NN</code>	<code>\pdfximagebbox</code>	<code>\tex_pdfximagebbox:D</code>

These are not related to PDF output and either already appear in other engines without the `\pdf` prefix, or might reasonably do so at some future stage. We therefore drop the leading `pdf` here.

746	<code>__kernel_primitive:NN</code>	<code>\ifpdfabsdim</code>	<code>\tex_ifabsdim:D</code>
747	<code>__kernel_primitive:NN</code>	<code>\ifpdfabsnum</code>	<code>\tex_ifabsnum:D</code>
748	<code>__kernel_primitive:NN</code>	<code>\ifpdfprimitive</code>	<code>\tex_ifprimitive:D</code>
749	<code>__kernel_primitive:NN</code>	<code>\pdfadjustspacing</code>	<code>\tex_adjustspacing:D</code>
750	<code>__kernel_primitive:NN</code>	<code>\pdfcopyfont</code>	<code>\tex_copyfont:D</code>
751	<code>__kernel_primitive:NN</code>	<code>\pdfdraftmode</code>	<code>\tex_draftmode:D</code>
752	<code>__kernel_primitive:NN</code>	<code>\pdfeachlinedepth</code>	<code>\tex_eachlinedepth:D</code>
753	<code>__kernel_primitive:NN</code>	<code>\pdfeachlineheight</code>	<code>\tex_eachlineheight:D</code>
754	<code>__kernel_primitive:NN</code>	<code>\pdfelapsedtime</code>	<code>\tex_elapsedtime:D</code>
755	<code>__kernel_primitive:NN</code>	<code>\pdffiledump</code>	<code>\tex_filedump:D</code>
756	<code>__kernel_primitive:NN</code>	<code>\pdffilemoddate</code>	<code>\tex_filemoddate:D</code>
757	<code>__kernel_primitive:NN</code>	<code>\pdffilesize</code>	<code>\tex_filesize:D</code>
758	<code>__kernel_primitive:NN</code>	<code>\pdffirstlineheight</code>	<code>\tex_firstlineheight:D</code>
759	<code>__kernel_primitive:NN</code>	<code>\pdffontexpand</code>	<code>\tex_fontexpand:D</code>
760	<code>__kernel_primitive:NN</code>	<code>\pdffontsize</code>	<code>\tex_fontsize:D</code>
761	<code>__kernel_primitive:NN</code>	<code>\pdfignoreddimen</code>	<code>\tex_ignoreddimen:D</code>
762	<code>__kernel_primitive:NN</code>	<code>\pdfinsertht</code>	<code>\tex_insertht:D</code>
763	<code>__kernel_primitive:NN</code>	<code>\pdflastlinedepth</code>	<code>\tex_lastlinedepth:D</code>
764	<code>__kernel_primitive:NN</code>	<code>\pdflastxpos</code>	<code>\tex_lastxpos:D</code>
765	<code>__kernel_primitive:NN</code>	<code>\pdflastypos</code>	<code>\tex_lastypos:D</code>
766	<code>__kernel_primitive:NN</code>	<code>\pdfmapfile</code>	<code>\tex_mapfile:D</code>
767	<code>__kernel_primitive:NN</code>	<code>\pdfmapline</code>	<code>\tex_mapline:D</code>
768	<code>__kernel_primitive:NN</code>	<code>\pdfmdfivesum</code>	<code>\tex_mdfivesum:D</code>
769	<code>__kernel_primitive:NN</code>	<code>\pdfnoligatures</code>	<code>\tex_noligatures:D</code>
770	<code>__kernel_primitive:NN</code>	<code>\pdfnormaldeviate</code>	<code>\tex_normaldeviate:D</code>
771	<code>__kernel_primitive:NN</code>	<code>\pdfpageheight</code>	<code>\tex_pageheight:D</code>
772	<code>__kernel_primitive:NN</code>	<code>\pdfpagewidth</code>	<code>\tex_pagewidth:D</code>
773	<code>__kernel_primitive:NN</code>	<code>\pdfpkmode</code>	<code>\tex_pkmode:D</code>
774	<code>__kernel_primitive:NN</code>	<code>\pdfpkresolution</code>	<code>\tex_pkresolution:D</code>
775	<code>__kernel_primitive:NN</code>	<code>\pdfprimitive</code>	<code>\tex_primitive:D</code>
776	<code>__kernel_primitive:NN</code>	<code>\pdfprotrudechars</code>	<code>\tex_protrudechars:D</code>
777	<code>__kernel_primitive:NN</code>	<code>\pdfpxdimen</code>	<code>\tex_pxdimen:D</code>
778	<code>__kernel_primitive:NN</code>	<code>\pdfrandomseed</code>	<code>\tex_randomseed:D</code>
779	<code>__kernel_primitive:NN</code>	<code>\pdfresettimer</code>	<code>\tex_resettimer:D</code>
780	<code>__kernel_primitive:NN</code>	<code>\pdfsavepos</code>	<code>\tex_savepos:D</code>
781	<code>__kernel_primitive:NN</code>	<code>\pdfstrcmp</code>	<code>\tex_strcmp:D</code>

```

782 \__kernel_primitive:NN \pdfsetrandomseed \tex_setrandomseed:D
783 \__kernel_primitive:NN \pdfshellescape \tex_shellescape:D
784 \__kernel_primitive:NN \pdftracingfonts \tex_tracingfonts:D
785 \__kernel_primitive:NN \pdfuniformdeviate \tex_uniformdeviate:D

```

The version primitives are not related to PDF mode but are pdfTeX-specific, so again are carried forward unchanged.

```

786 \__kernel_primitive:NN \pdfTeXbanner \tex_pdfTeXbanner:D
787 \__kernel_primitive:NN \pdfTeXrevision \tex_pdfTeXrevision:D
788 \__kernel_primitive:NN \pdfTeXversion \tex_pdfTeXversion:D

```

These ones appear in pdfTeX but don't have pdf in the name at all: no decisions to make.

```

789 \__kernel_primitive:NN \efcode \tex_efcode:D
790 \__kernel_primitive:NN \ifincsname \tex_ifincsname:D
791 \__kernel_primitive:NN \leftmarginkern \tex_leftmarginkern:D
792 \__kernel_primitive:NN \letterspacefont \tex_letterspacefont:D
793 \__kernel_primitive:NN \lpcode \tex_lpcode:D
794 \__kernel_primitive:NN \quitvmode \tex_quitvmode:D
795 \__kernel_primitive:NN \rightmarginkern \tex_rightmarginkern:D
796 \__kernel_primitive:NN \rptide \tex_rptide:D
797 \__kernel_primitive:NN \synctex \tex_synctex:D
798 \__kernel_primitive:NN \tagcode \tex_tagcode:D

```

Post pdfTeX primitive availability gets more complex. Both XeTeX and LuaTeX have varying names for some primitives from pdfTeX. Particularly for LuaTeX tracking all of that would be hard. Instead, we now check that we only save primitives if they actually exist.

```

799 </initex | names | package>
800 <*initex | package>
801 \tex_long:D \tex_def:D \use_ii:nn #1#2 {#2}
802 \tex_long:D \tex_def:D \use_none:n #1 { }
803 \tex_long:D \tex_def:D \__kernel_primitive:NN #1#2
804 {
805   \tex_ifdefined:D #1
806   \tex_expandafter:D \use_ii:nn
807   \tex_fi:D
808   \use_none:n { \tex_global:D \tex_let:D #2 #1 }
809 <*initex>
810   \tex_global:D \tex_let:D #1 \tex_undefined:D
811 </initex>
812 }
813 </initex | package>
814 <*initex | names | package>

```

XeTeX-specific primitives. Note that XeTeX's `\strcmp` is handled earlier and is “rolled up” into `\pdfstrcmp`. A few cross-compatibility names which lack the pdf of the original are handled later.

```

815 \__kernel_primitive:NN \suppressfontnotfounderror
816 \tex_suppressfontnotfounderror:D
817 \__kernel_primitive:NN \XeTeXcharclass \tex_XeTeXcharclass:D
818 \__kernel_primitive:NN \XeTeXcharglyph \tex_XeTeXcharglyph:D
819 \__kernel_primitive:NN \XeTeXcountfeatures \tex_XeTeXcountfeatures:D
820 \__kernel_primitive:NN \XeTeXcountglyphs \tex_XeTeXcountglyphs:D
821 \__kernel_primitive:NN \XeTeXcountselectors \tex_XeTeXcountselectors:D

```



```

822 \__kernel_primitive:NN \XeTeXcountvariations \tex_XeTeXcountvariations:D
823 \__kernel_primitive:NN \XeTeXdefaultencoding \tex_XeTeXdefaultencoding:D
824 \__kernel_primitive:NN \XeTeXdashbreakstate \tex_XeTeXdashbreakstate:D
825 \__kernel_primitive:NN \XeTeXfeaturecode \tex_XeTeXfeaturecode:D
826 \__kernel_primitive:NN \XeTeXfeaturename \tex_XeTeXfeaturename:D
827 \__kernel_primitive:NN \XeTeXfindfeaturebyname
828 \tex_XeTeXfindfeaturebyname:D
829 \__kernel_primitive:NN \XeTeXfindselectorbyname
830 \tex_XeTeXfindselectorbyname:D
831 \__kernel_primitive:NN \XeTeXfindvariationbyname
832 \tex_XeTeXfindvariationbyname:D
833 \__kernel_primitive:NN \XeTeXfirstfontchar \tex_XeTeXfirstfontchar:D
834 \__kernel_primitive:NN \XeTeXfonttype \tex_XeTeXfonttype:D
835 \__kernel_primitive:NN \XeTeXgenerateactualtext
836 \tex_XeTeXgenerateactualtext:D
837 \__kernel_primitive:NN \XeTeXglyph \tex_XeTeXglyph:D
838 \__kernel_primitive:NN \XeTeXglyphbounds \tex_XeTeXglyphbounds:D
839 \__kernel_primitive:NN \XeTeXglyphindex \tex_XeTeXglyphindex:D
840 \__kernel_primitive:NN \XeTeXglyphname \tex_XeTeXglyphname:D
841 \__kernel_primitive:NN \XeTeXinputencoding \tex_XeTeXinputencoding:D
842 \__kernel_primitive:NN \XeTeXinputnormalization
843 \tex_XeTeXinputnormalization:D
844 \__kernel_primitive:NN \XeTeXinterchartokenstate
845 \tex_XeTeXinterchartokenstate:D
846 \__kernel_primitive:NN \XeTeXinterchartoks \tex_XeTeXinterchartoks:D
847 \__kernel_primitive:NN \XeTeXisdefaultselector
848 \tex_XeTeXisdefaultselector:D
849 \__kernel_primitive:NN \XeTeXisexclusivefeature
850 \tex_XeTeXisexclusivefeature:D
851 \__kernel_primitive:NN \XeTeXlastfontchar \tex_XeTeXlastfontchar:D
852 \__kernel_primitive:NN \XeTeXlinebreakskip \tex_XeTeXlinebreakskip:D
853 \__kernel_primitive:NN \XeTeXlinebreaklocale \tex_XeTeXlinebreaklocale:D
854 \__kernel_primitive:NN \XeTeXlinebreakpenalty \tex_XeTeXlinebreakpenalty:D
855 \__kernel_primitive:NN \XeTeXOTcountfeatures \tex_XeTeXOTcountfeatures:D
856 \__kernel_primitive:NN \XeTeXOTcountlanguages \tex_XeTeXOTcountlanguages:D
857 \__kernel_primitive:NN \XeTeXOTcountscripts \tex_XeTeXOTcountscripts:D
858 \__kernel_primitive:NN \XeTeXOTfeaturetag \tex_XeTeXOTfeaturetag:D
859 \__kernel_primitive:NN \XeTeXOTlanguagetag \tex_XeTeXOTlanguagetag:D
860 \__kernel_primitive:NN \XeTeXOTscripttag \tex_XeTeXOTscripttag:D
861 \__kernel_primitive:NN \XeTeXpdffile \tex_XeTeXpdffile:D
862 \__kernel_primitive:NN \XeTeXpdfpagecount \tex_XeTeXpdfpagecount:D
863 \__kernel_primitive:NN \XeTeXpicfile \tex_XeTeXpicfile:D
864 \__kernel_primitive:NN \XeTeXrevision \tex_XeTeXrevision:D
865 \__kernel_primitive:NN \XeTeXselectorname \tex_XeTeXselectorname:D
866 \__kernel_primitive:NN \XeTeXtracingfonts \tex_XeTeXtracingfonts:D
867 \__kernel_primitive:NN \XeTeXupwardsmode \tex_XeTeXupwardsmode:D
868 \__kernel_primitive:NN \XeTeXuseglyphmetrics \tex_XeTeXuseglyphmetrics:D
869 \__kernel_primitive:NN \XeTeXvariation \tex_XeTeXvariation:D
870 \__kernel_primitive:NN \XeTeXvariationdefault \tex_XeTeXvariationdefault:D
871 \__kernel_primitive:NN \XeTeXvariationmax \tex_XeTeXvariationmax:D
872 \__kernel_primitive:NN \XeTeXvariationmin \tex_XeTeXvariationmin:D
873 \__kernel_primitive:NN \XeTeXvariationname \tex_XeTeXvariationname:D
874 \__kernel_primitive:NN \XeTeXversion \tex_XeTeXversion:D

```

Primitives from pdfTeX that XeTeX renames: also helps with LuaTeX.

875	<code>__kernel_primitive:NN \creationdate</code>	<code>\tex_creationdate:D</code>
876	<code>__kernel_primitive:NN \elapsedtime</code>	<code>\tex_elapsedtime:D</code>
877	<code>__kernel_primitive:NN \filedump</code>	<code>\tex_filedump:D</code>
878	<code>__kernel_primitive:NN \filemoddate</code>	<code>\tex_filemoddate:D</code>
879	<code>__kernel_primitive:NN \filesize</code>	<code>\tex_filesize:D</code>
880	<code>__kernel_primitive:NN \mdfivesum</code>	<code>\tex_mdfivesum:D</code>
881	<code>__kernel_primitive:NN \ifprimitive</code>	<code>\tex_ifprimitive:D</code>
882	<code>__kernel_primitive:NN \primitive</code>	<code>\tex_primitive:D</code>
883	<code>__kernel_primitive:NN \resettimer</code>	<code>\tex_resettimer:D</code>
884	<code>__kernel_primitive:NN \shellescape</code>	<code>\tex_shellescape:D</code>

Primitives from LuaTeX, some of which have been ported back to XeTeX.

885	<code>__kernel_primitive:NN \alignmark</code>	<code>\tex_alignmark:D</code>
886	<code>__kernel_primitive:NN \aligntab</code>	<code>\tex_aligntab:D</code>
887	<code>__kernel_primitive:NN \attribute</code>	<code>\tex_attribute:D</code>
888	<code>__kernel_primitive:NN \attributedef</code>	<code>\tex_attributedef:D</code>
889	<code>__kernel_primitive:NN \automaticdiscretionary</code>	
890	<code>\tex_automaticdiscretionary:D</code>	
891	<code>__kernel_primitive:NN \automatichyphenmode</code>	<code>\tex_automatichyphenmode:D</code>
892	<code>__kernel_primitive:NN \automatichyphenpenalty</code>	
893	<code>\tex_automatichyphenpenalty:D</code>	
894	<code>__kernel_primitive:NN \beginscename</code>	<code>\tex_beginscename:D</code>
895	<code>__kernel_primitive:NN \bodydir</code>	<code>\tex_bodydir:D</code>
896	<code>__kernel_primitive:NN \bodydirection</code>	<code>\tex_bodydirection:D</code>
897	<code>__kernel_primitive:NN \boxdir</code>	<code>\tex_boxdir:D</code>
898	<code>__kernel_primitive:NN \boxdirection</code>	<code>\tex_boxdirection:D</code>
899	<code>__kernel_primitive:NN \breakafterdirmode</code>	<code>\tex_breakafterdirmode:D</code>
900	<code>__kernel_primitive:NN \catcodetable</code>	<code>\tex_catcodetable:D</code>
901	<code>__kernel_primitive:NN \clearmarks</code>	<code>\tex_clearmarks:D</code>
902	<code>__kernel_primitive:NN \crampeddisplaystyle</code>	<code>\tex_crampeddisplaystyle:D</code>
903	<code>__kernel_primitive:NN \crampedscriptscriptstyle</code>	
904	<code>\tex_crampedscriptscriptstyle:D</code>	
905	<code>__kernel_primitive:NN \crampedscriptstyle</code>	<code>\tex_crampedscriptstyle:D</code>
906	<code>__kernel_primitive:NN \crampedtextstyle</code>	<code>\tex_crampedtextstyle:D</code>
907	<code>__kernel_primitive:NN \csstring</code>	<code>\tex_csstring:D</code>
908	<code>__kernel_primitive:NN \directlua</code>	<code>\tex_directlua:D</code>
909	<code>__kernel_primitive:NN \dviextension</code>	<code>\tex_dviextension:D</code>
910	<code>__kernel_primitive:NN \dvifedback</code>	<code>\tex_dvifedback:D</code>
911	<code>__kernel_primitive:NN \dvivariable</code>	<code>\tex_dvivariable:D</code>
912	<code>__kernel_primitive:NN \eTeXglueshrinkorder</code>	<code>\tex_eTeXglueshrinkorder:D</code>
913	<code>__kernel_primitive:NN \eTeXgluestretchorder</code>	<code>\tex_eTeXgluestretchorder:D</code>
914	<code>__kernel_primitive:NN \etoksapp</code>	<code>\tex_etoksapp:D</code>
915	<code>__kernel_primitive:NN \etokspre</code>	<code>\tex_etokspre:D</code>
916	<code>__kernel_primitive:NN \exceptionpenalty</code>	<code>\tex_exceptionpenalty:D</code>
917	<code>__kernel_primitive:NN \explicithyphenpenalty</code>	<code>\tex_explicithyphenpenalty:D</code>
918	<code>__kernel_primitive:NN \expanded</code>	<code>\tex_expanded:D</code>
919	<code>__kernel_primitive:NN \explicitdiscretionary</code>	<code>\tex_explicitdiscretionary:D</code>
920	<code>__kernel_primitive:NN \firstvalidlanguage</code>	<code>\tex_firstvalidlanguage:D</code>
921	<code>__kernel_primitive:NN \fontid</code>	<code>\tex_fontid:D</code>
922	<code>__kernel_primitive:NN \formatname</code>	<code>\tex_formatname:D</code>
923	<code>__kernel_primitive:NN \hjcode</code>	<code>\tex_hjcode:D</code>
924	<code>__kernel_primitive:NN \hpack</code>	<code>\tex_hpack:D</code>
925	<code>__kernel_primitive:NN \hyphenationbounds</code>	<code>\tex_hyphenationbounds:D</code>

926	_kernel_primitive:NN	\hyphenationmin	\tex_hyphenationmin:D
927	_kernel_primitive:NN	\hyphenpenaltymode	\tex_hyphenpenaltymode:D
928	_kernel_primitive:NN	\gleaders	\tex_gleaders:D
929	_kernel_primitive:NN	\ifcondition	\tex_ifcondition:D
930	_kernel_primitive:NN	\immediateassigned	\tex_immediateassigned:D
931	_kernel_primitive:NN	\immediateassignment	\tex_immediateassignment:D
932	_kernel_primitive:NN	\initcatcodetable	\tex_initcatcodetable:D
933	_kernel_primitive:NN	\lastnamedcs	\tex_lastnamedcs:D
934	_kernel_primitive:NN	\latelua	\tex_latelua:D
935	_kernel_primitive:NN	\lateluafunction	\tex_lateluafunction:D
936	_kernel_primitive:NN	\leftghost	\tex_leftghost:D
937	_kernel_primitive:NN	\letcharcode	\tex_letcharcode:D
938	_kernel_primitive:NN	\linedir	\tex_linedir:D
939	_kernel_primitive:NN	\linedirection	\tex_linedirection:D
940	_kernel_primitive:NN	\localbrokenpenalty	\tex_localbrokenpenalty:D
941	_kernel_primitive:NN	\localinterlinepenalty	\tex_localinterlinepenalty:D
942	_kernel_primitive:NN	\luabytecode	\tex_luabytecode:D
943	_kernel_primitive:NN	\luabytecodecall	\tex_luabytecodecall:D
944	_kernel_primitive:NN	\luacopyinputnodes	\tex_luacopyinputnodes:D
945	_kernel_primitive:NN	\luadef	\tex_luadef:D
946	_kernel_primitive:NN	\localleftbox	\tex_localleftbox:D
947	_kernel_primitive:NN	\localrightbox	\tex_localrightbox:D
948	_kernel_primitive:NN	\luaescapestring	\tex_luaescapestring:D
949	_kernel_primitive:NN	\luafunction	\tex_luafunction:D
950	_kernel_primitive:NN	\luafunctioncall	\tex_luafunctioncall:D
951	_kernel_primitive:NN	\luatexbanner	\tex_luatexbanner:D
952	_kernel_primitive:NN	\luatexrevision	\tex_luatexrevision:D
953	_kernel_primitive:NN	\luatexversion	\tex_luatexversion:D
954	_kernel_primitive:NN	\mathdelimitersmode	\tex_mathdelimitersmode:D
955	_kernel_primitive:NN	\mathdir	\tex_mathdir:D
956	_kernel_primitive:NN	\mathdirection	\tex_mathdirection:D
957	_kernel_primitive:NN	\mathdisplayskipmode	\tex_mathdisplayskipmode:D
958	_kernel_primitive:NN	\matheqnogapstep	\tex_matheqnogapstep:D
959	_kernel_primitive:NN	\mathnolimitsmode	\tex_mathnolimitsmode:D
960	_kernel_primitive:NN	\mathoption	\tex_mathoption:D
961	_kernel_primitive:NN	\mathpenaltiesmode	\tex_mathpenaltiesmode:D
962	_kernel_primitive:NN	\mathrulesfam	\tex_mathrulesfam:D
963	_kernel_primitive:NN	\mathscriptsmode	\tex_mathscriptsmode:D
964	_kernel_primitive:NN	\mathscriptboxmode	\tex_mathscriptboxmode:D
965	_kernel_primitive:NN	\mathscriptcharmode	\tex_mathscriptcharmode:D
966	_kernel_primitive:NN	\mathstyle	\tex_mathstyle:D
967	_kernel_primitive:NN	\mathsurroundmode	\tex_mathsurroundmode:D
968	_kernel_primitive:NN	\mathsurroundskip	\tex_mathsurroundskip:D
969	_kernel_primitive:NN	\nohrule	\tex_nohrule:D
970	_kernel_primitive:NN	\nokerns	\tex_nokerns:D
971	_kernel_primitive:NN	\noligs	\tex_noligs:D
972	_kernel_primitive:NN	\nospaces	\tex_nospaces:D
973	_kernel_primitive:NN	\novrule	\tex_novrule:D
974	_kernel_primitive:NN	\outputbox	\tex_outputbox:D
975	_kernel_primitive:NN	\pagebottomoffset	\tex_pagebottomoffset:D
976	_kernel_primitive:NN	\pagedir	\tex_pagedir:D
977	_kernel_primitive:NN	\pagedirection	\tex_pagedirection:D
978	_kernel_primitive:NN	\pageleftoffset	\tex_pageleftoffset:D
979	_kernel_primitive:NN	\pagerightoffset	\tex_pagerightoffset:D

980	_kernel_primitive:NN	\pagetopoffset	\tex_pagetopoffset:D
981	_kernel_primitive:NN	\pardir	\tex_pardir:D
982	_kernel_primitive:NN	\pardirection	\tex_pardirection:D
983	_kernel_primitive:NN	\pdfextension	\tex_pdfextension:D
984	_kernel_primitive:NN	\pdffeedback	\tex_pdffeedback:D
985	_kernel_primitive:NN	\pdfvariable	\tex_pdfvariable:D
986	_kernel_primitive:NN	\postexhyphenchar	\tex_postexhyphenchar:D
987	_kernel_primitive:NN	\posthyphenchar	\tex_posthyphenchar:D
988	_kernel_primitive:NN	\prebinoppenalty	\tex_prebinoppenalty:D
989	_kernel_primitive:NN	\predisplaygapfactor	\tex_predisplaygapfactor:D
990	_kernel_primitive:NN	\preexhyphenchar	\tex_preexhyphenchar:D
991	_kernel_primitive:NN	\prehyphenchar	\tex_prehyphenchar:D
992	_kernel_primitive:NN	\prerelpenalty	\tex_prerelpenalty:D
993	_kernel_primitive:NN	\rightghost	\tex_rightghost:D
994	_kernel_primitive:NN	\savecatcodetable	\tex_savecatcodetable:D
995	_kernel_primitive:NN	\scantextokens	\tex_scantextokens:D
996	_kernel_primitive:NN	\setfontid	\tex_setfontid:D
997	_kernel_primitive:NN	\shapemode	\tex_shapemode:D
998	_kernel_primitive:NN	\suppressifcsnameerror	\tex_suppressifcsnameerror:D
999	_kernel_primitive:NN	\suppresslongerror	\tex_suppresslongerror:D
1000	_kernel_primitive:NN	\suppressmathparerror	\tex_suppressmathparerror:D
1001	_kernel_primitive:NN	\suppressoutererror	\tex_suppressoutererror:D
1002	_kernel_primitive:NN	\suppressprimitiveerror	
1003		\tex_suppressprimitiveerror:D	
1004	_kernel_primitive:NN	\texdir	\tex_texdir:D
1005	_kernel_primitive:NN	\texdirection	\tex_texdirection:D
1006	_kernel_primitive:NN	\toksapp	\tex_toksapp:D
1007	_kernel_primitive:NN	\tokspre	\tex_tokspre:D
1008	_kernel_primitive:NN	\tpack	\tex_tpack:D
1009	_kernel_primitive:NN	\vpack	\tex_vpack:D

Primitives from pdfTeX that LuaTeX renames.

1010	_kernel_primitive:NN	\adjustspacing	\tex_adjustspacing:D
1011	_kernel_primitive:NN	\copyfont	\tex_copyfont:D
1012	_kernel_primitive:NN	\draftmode	\tex_draftmode:D
1013	_kernel_primitive:NN	\expandglyphsinfont	\tex_fontexpand:D
1014	_kernel_primitive:NN	\ifabsdim	\tex_ifabsdim:D
1015	_kernel_primitive:NN	\ifabsnum	\tex_ifabsnum:D
1016	_kernel_primitive:NN	\ignoreligaturesinfont	\tex_ignoreligaturesinfont:D
1017	_kernel_primitive:NN	\insertht	\tex_insertht:D
1018	_kernel_primitive:NN	\lastsavedboxresourceindex	
1019		\tex_pdflastxform:D	
1020	_kernel_primitive:NN	\lastsavedimageresourceindex	
1021		\tex_pdflastximage:D	
1022	_kernel_primitive:NN	\lastsavedimageresourcepages	
1023		\tex_pdflastximagepages:D	
1024	_kernel_primitive:NN	\lastxpos	\tex_lastxpos:D
1025	_kernel_primitive:NN	\lastypos	\tex_lastypos:D
1026	_kernel_primitive:NN	\normaldeviate	\tex_normaldeviate:D
1027	_kernel_primitive:NN	\outputmode	\tex_pdfoutput:D
1028	_kernel_primitive:NN	\pageheight	\tex_pageheight:D
1029	_kernel_primitive:NN	\pagewidth	\tex_pagewidth:D
1030	_kernel_primitive:NN	\protrudechars	\tex_protrudechars:D
1031	_kernel_primitive:NN	\pxdimen	\tex_pxdimen:D
1032	_kernel_primitive:NN	\randomseed	\tex_randomseed:D

1033	<code>__kernel_primitive:NN</code>	<code>\useboxresource</code>	<code>\tex_pdfrefxform:D</code>
1034	<code>__kernel_primitive:NN</code>	<code>\useimageresource</code>	<code>\tex_pdfrefximage:D</code>
1035	<code>__kernel_primitive:NN</code>	<code>\savepos</code>	<code>\tex_savepos:D</code>
1036	<code>__kernel_primitive:NN</code>	<code>\saveboxresource</code>	<code>\tex_pdfxform:D</code>
1037	<code>__kernel_primitive:NN</code>	<code>\saveimageresource</code>	<code>\tex_pdfximage:D</code>
1038	<code>__kernel_primitive:NN</code>	<code>\setrandomseed</code>	<code>\tex_setrandomseed:D</code>
1039	<code>__kernel_primitive:NN</code>	<code>\tracingfonts</code>	<code>\tex_tracingfonts:D</code>
1040	<code>__kernel_primitive:NN</code>	<code>\uniformdeviate</code>	<code>\tex_uniformdeviate:D</code>

The set of Unicode math primitives were introduced by \XeTeX and \LuaTeX in a somewhat complex fashion: a few first as \XeTeX ... which were then renamed with \LuaTeX having a lot more. These names now all start \U... and mainly \Umath... .

1041	<code>__kernel_primitive:NN</code>	<code>\Uchar</code>	<code>\tex_Uchar:D</code>
1042	<code>__kernel_primitive:NN</code>	<code>\Ucharcat</code>	<code>\tex_Ucharcat:D</code>
1043	<code>__kernel_primitive:NN</code>	<code>\Udelcode</code>	<code>\tex_Udelcode:D</code>
1044	<code>__kernel_primitive:NN</code>	<code>\Udelcodenum</code>	<code>\tex_Udelcodenum:D</code>
1045	<code>__kernel_primitive:NN</code>	<code>\Udelimiter</code>	<code>\tex_Udelimiter:D</code>
1046	<code>__kernel_primitive:NN</code>	<code>\Udelimiterover</code>	<code>\tex_Udelimiterover:D</code>
1047	<code>__kernel_primitive:NN</code>	<code>\Udelimiterunder</code>	<code>\tex_Udelimiterunder:D</code>
1048	<code>__kernel_primitive:NN</code>	<code>\Uhextensible</code>	<code>\tex_Uhextensible:D</code>
1049	<code>__kernel_primitive:NN</code>	<code>\Umathaccent</code>	<code>\tex_Umathaccent:D</code>
1050	<code>__kernel_primitive:NN</code>	<code>\Umathaxis</code>	<code>\tex_Umathaxis:D</code>
1051	<code>__kernel_primitive:NN</code>	<code>\Umathbinbinspacing</code>	<code>\tex_Umathbinbinspacing:D</code>
1052	<code>__kernel_primitive:NN</code>	<code>\Umathbinclosespacing</code>	<code>\tex_Umathbinclosespacing:D</code>
1053	<code>__kernel_primitive:NN</code>	<code>\Umathbininnerspacing</code>	<code>\tex_Umathbininnerspacing:D</code>
1054	<code>__kernel_primitive:NN</code>	<code>\Umathbinopenspacing</code>	<code>\tex_Umathbinopenspacing:D</code>
1055	<code>__kernel_primitive:NN</code>	<code>\Umathbinopspacing</code>	<code>\tex_Umathbinopspacing:D</code>
1056	<code>__kernel_primitive:NN</code>	<code>\Umathbinordspacing</code>	<code>\tex_Umathbinordspacing:D</code>
1057	<code>__kernel_primitive:NN</code>	<code>\Umathbinpunctspacing</code>	<code>\tex_Umathbinpunctspacing:D</code>
1058	<code>__kernel_primitive:NN</code>	<code>\Umathbinrelspacing</code>	<code>\tex_Umathbinrelspacing:D</code>
1059	<code>__kernel_primitive:NN</code>	<code>\Umathchar</code>	<code>\tex_Umathchar:D</code>
1060	<code>__kernel_primitive:NN</code>	<code>\Umathcharclass</code>	<code>\tex_Umathcharclass:D</code>
1061	<code>__kernel_primitive:NN</code>	<code>\Umathchardef</code>	<code>\tex_Umathchardef:D</code>
1062	<code>__kernel_primitive:NN</code>	<code>\Umathcharfam</code>	<code>\tex_Umathcharfam:D</code>
1063	<code>__kernel_primitive:NN</code>	<code>\Umathcharnum</code>	<code>\tex_Umathcharnum:D</code>
1064	<code>__kernel_primitive:NN</code>	<code>\Umathcharnumdef</code>	<code>\tex_Umathcharnumdef:D</code>
1065	<code>__kernel_primitive:NN</code>	<code>\Umathcharslot</code>	<code>\tex_Umathcharslot:D</code>
1066	<code>__kernel_primitive:NN</code>	<code>\Umathclosebinspacing</code>	<code>\tex_Umathclosebinspacing:D</code>
1067	<code>__kernel_primitive:NN</code>	<code>\Umathcloseclosespacing</code>	
1068		<code>\tex_Umathcloseclosespacing:D</code>	
1069	<code>__kernel_primitive:NN</code>	<code>\Umathcloseinnerspacing</code>	
1070		<code>\tex_Umathcloseinnerspacing:D</code>	
1071	<code>__kernel_primitive:NN</code>	<code>\Umathcloseopenspacing</code>	<code>\tex_Umathcloseopenspacing:D</code>
1072	<code>__kernel_primitive:NN</code>	<code>\Umathcloseopspacing</code>	<code>\tex_Umathcloseopspacing:D</code>
1073	<code>__kernel_primitive:NN</code>	<code>\Umathcloseordspacing</code>	<code>\tex_Umathcloseordspacing:D</code>
1074	<code>__kernel_primitive:NN</code>	<code>\Umathclosepunctspacing</code>	
1075		<code>\tex_Umathclosepunctspacing:D</code>	
1076	<code>__kernel_primitive:NN</code>	<code>\Umathcloserelspacing</code>	<code>\tex_Umathcloserelspacing:D</code>
1077	<code>__kernel_primitive:NN</code>	<code>\Umathcode</code>	<code>\tex_Umathcode:D</code>
1078	<code>__kernel_primitive:NN</code>	<code>\Umathcodenum</code>	<code>\tex_Umathcodenum:D</code>
1079	<code>__kernel_primitive:NN</code>	<code>\Umathconnectoroverlapmin</code>	
1080		<code>\tex_Umathconnectoroverlapmin:D</code>	
1081	<code>__kernel_primitive:NN</code>	<code>\Umathfractiondelsize</code>	<code>\tex_Umathfractiondelsize:D</code>
1082	<code>__kernel_primitive:NN</code>	<code>\Umathfractiondenomdown</code>	

```

1083 \tex_Umathfractiondenomdown:D
1084 \__kernel_primitive:NN \Umathfractiondenomvgap
1085 \tex_Umathfractiondenomvgap:D
1086 \__kernel_primitive:NN \Umathfractionnumup \tex_Umathfractionnumup:D
1087 \__kernel_primitive:NN \Umathfractionnumvgap \tex_Umathfractionnumvgap:D
1088 \__kernel_primitive:NN \Umathfractionrule \tex_Umathfractionrule:D
1089 \__kernel_primitive:NN \Umathinnerbinspacing \tex_Umathinnerbinspacing:D
1090 \__kernel_primitive:NN \Umathinnerclosespacing
1091 \tex_Umathinnerclosespacing:D
1092 \__kernel_primitive:NN \Umathinnerinnerspacing
1093 \tex_Umathinnerinnerspacing:D
1094 \__kernel_primitive:NN \Umathinneropenspacing \tex_Umathinneropenspacing:D
1095 \__kernel_primitive:NN \Umathinneropspacing \tex_Umathinneropspacing:D
1096 \__kernel_primitive:NN \Umathinnerordspacing \tex_Umathinnerordspacing:D
1097 \__kernel_primitive:NN \Umathinnerpunctspacing
1098 \tex_Umathinnerpunctspacing:D
1099 \__kernel_primitive:NN \Umathinnerrelspacing \tex_Umathinnerrelspacing:D
1100 \__kernel_primitive:NN \Umathlimitabovebgap \tex_Umathlimitabovebgap:D
1101 \__kernel_primitive:NN \Umathlimitabovekern \tex_Umathlimitabovekern:D
1102 \__kernel_primitive:NN \Umathlimitabovevgap \tex_Umathlimitabovevgap:D
1103 \__kernel_primitive:NN \Umathlimitbelowbgap \tex_Umathlimitbelowbgap:D
1104 \__kernel_primitive:NN \Umathlimitbelowkern \tex_Umathlimitbelowkern:D
1105 \__kernel_primitive:NN \Umathlimitbelowvgap \tex_Umathlimitbelowvgap:D
1106 \__kernel_primitive:NN \Umathnolimitsubfactor \tex_Umathnolimitsubfactor:D
1107 \__kernel_primitive:NN \Umathnolimitsupfactor \tex_Umathnolimitsupfactor:D
1108 \__kernel_primitive:NN \Umathopbinspacing \tex_Umathopbinspacing:D
1109 \__kernel_primitive:NN \Umathopclosespacing \tex_Umathopclosespacing:D
1110 \__kernel_primitive:NN \Umathopenbinspacing \tex_Umathopenbinspacing:D
1111 \__kernel_primitive:NN \Umathopenclosespacing \tex_Umathopenclosespacing:D
1112 \__kernel_primitive:NN \Umathopeninnerspacing \tex_Umathopeninnerspacing:D
1113 \__kernel_primitive:NN \Umathopenopenspacing \tex_Umathopenopenspacing:D
1114 \__kernel_primitive:NN \Umathopenopspacing \tex_Umathopenopspacing:D
1115 \__kernel_primitive:NN \Umathopenordspacing \tex_Umathopenordspacing:D
1116 \__kernel_primitive:NN \Umathopenpunctspacing \tex_Umathopenpunctspacing:D
1117 \__kernel_primitive:NN \Umathopenrelspacing \tex_Umathopenrelspacing:D
1118 \__kernel_primitive:NN \Umathoperatorsize \tex_Umathoperatorsize:D
1119 \__kernel_primitive:NN \Umathopinnerspacing \tex_Umathopinnerspacing:D
1120 \__kernel_primitive:NN \Umathopopenspacing \tex_Umathopopenspacing:D
1121 \__kernel_primitive:NN \Umathopopspacing \tex_Umathopopspacing:D
1122 \__kernel_primitive:NN \Umathopordspacing \tex_Umathopordspacing:D
1123 \__kernel_primitive:NN \Umathoppunctspacing \tex_Umathoppunctspacing:D
1124 \__kernel_primitive:NN \Umathoprelspacing \tex_Umathoprelspacing:D
1125 \__kernel_primitive:NN \Umathordbinspacing \tex_Umathordbinspacing:D
1126 \__kernel_primitive:NN \Umathordclosespacing \tex_Umathordclosespacing:D
1127 \__kernel_primitive:NN \Umathordinnerspacing \tex_Umathordinnerspacing:D
1128 \__kernel_primitive:NN \Umathordopenspacing \tex_Umathordopenspacing:D
1129 \__kernel_primitive:NN \Umathordopspacing \tex_Umathordopspacing:D
1130 \__kernel_primitive:NN \Umathordordspacing \tex_Umathordordspacing:D
1131 \__kernel_primitive:NN \Umathordpunctspacing \tex_Umathordpunctspacing:D
1132 \__kernel_primitive:NN \Umathordrelspacing \tex_Umathordrelspacing:D
1133 \__kernel_primitive:NN \Umathoverbarkern \tex_Umathoverbarkern:D
1134 \__kernel_primitive:NN \Umathoverbarrule \tex_Umathoverbarrule:D
1135 \__kernel_primitive:NN \Umathoverbarvgap \tex_Umathoverbarvgap:D
1136 \__kernel_primitive:NN \Umathoverdelimeterbgap

```

```

1137     \tex_Umathoverdelimiterbgap:D
1138 \__kernel_primitive:NN \Umathoverdelimitervgap
1139     \tex_Umathoverdelimitervgap:D
1140 \__kernel_primitive:NN \Umathpunctbinspacing \tex_Umathpunctbinspacing:D
1141 \__kernel_primitive:NN \Umathpunctclosespacing
1142     \tex_Umathpunctclosespacing:D
1143 \__kernel_primitive:NN \Umathpunctinnerspacing
1144     \tex_Umathpunctinnerspacing:D
1145 \__kernel_primitive:NN \Umathpunctopenspacing \tex_Umathpunctopenspacing:D
1146 \__kernel_primitive:NN \Umathpuncttopspacing \tex_Umathpuncttopspacing:D
1147 \__kernel_primitive:NN \Umathpunctordspacing \tex_Umathpunctordspacing:D
1148 \__kernel_primitive:NN \Umathpunctpunctspacing
1149     \tex_Umathpunctpunctspacing:D
1150 \__kernel_primitive:NN \Umathpunctrelspacing \tex_Umathpunctrelspacing:D
1151 \__kernel_primitive:NN \Umathquad \tex_Umathquad:D
1152 \__kernel_primitive:NN \Umathradicaldegreeafter
1153     \tex_Umathradicaldegreeafter:D
1154 \__kernel_primitive:NN \Umathradicaldegreebefore
1155     \tex_Umathradicaldegreebefore:D
1156 \__kernel_primitive:NN \Umathradicaldegreeraise
1157     \tex_Umathradicaldegreeraise:D
1158 \__kernel_primitive:NN \Umathradicalkern \tex_Umathradicalkern:D
1159 \__kernel_primitive:NN \Umathradicalrule \tex_Umathradicalrule:D
1160 \__kernel_primitive:NN \Umathradicalvgap \tex_Umathradicalvgap:D
1161 \__kernel_primitive:NN \Umathrelbinspacing \tex_Umathrelbinspacing:D
1162 \__kernel_primitive:NN \Umathrelclosespacing \tex_Umathrelclosespacing:D
1163 \__kernel_primitive:NN \Umathrelinnerspacing \tex_Umathrelinnerspacing:D
1164 \__kernel_primitive:NN \Umathrelopenspacing \tex_Umathrelopenspacing:D
1165 \__kernel_primitive:NN \Umathreltopspacing \tex_Umathreltopspacing:D
1166 \__kernel_primitive:NN \Umathrelordspacing \tex_Umathrelordspacing:D
1167 \__kernel_primitive:NN \Umathrelpunctspacing \tex_Umathrelpunctspacing:D
1168 \__kernel_primitive:NN \Umathrelrelspacing \tex_Umathrelrelspacing:D
1169 \__kernel_primitive:NN \Umathskewedfractionhgap
1170     \tex_Umathskewedfractionhgap:D
1171 \__kernel_primitive:NN \Umathskewedfractionvgap
1172     \tex_Umathskewedfractionvgap:D
1173 \__kernel_primitive:NN \Umathspaceafterscript \tex_Umathspaceafterscript:D
1174 \__kernel_primitive:NN \Umathstackdenomdown \tex_Umathstackdenomdown:D
1175 \__kernel_primitive:NN \Umathstacknumup \tex_Umathstacknumup:D
1176 \__kernel_primitive:NN \Umathstackvgap \tex_Umathstackvgap:D
1177 \__kernel_primitive:NN \Umathsubshiftdown \tex_Umathsubshiftdown:D
1178 \__kernel_primitive:NN \Umathsubshiftdrop \tex_Umathsubshiftdrop:D
1179 \__kernel_primitive:NN \Umathsubsupshiftdown \tex_Umathsubsupshiftdown:D
1180 \__kernel_primitive:NN \Umathsubsupvgap \tex_Umathsubsupvgap:D
1181 \__kernel_primitive:NN \Umathsubtopmax \tex_Umathsubtopmax:D
1182 \__kernel_primitive:NN \Umathsupbottommin \tex_Umathsupbottommin:D
1183 \__kernel_primitive:NN \Umathsupshiftdrop \tex_Umathsupshiftdrop:D
1184 \__kernel_primitive:NN \Umathsupshiftup \tex_Umathsupshiftup:D
1185 \__kernel_primitive:NN \Umathsupsubbottommax \tex_Umathsupsubbottommax:D
1186 \__kernel_primitive:NN \Umathunderbarkern \tex_Umathunderbarkern:D
1187 \__kernel_primitive:NN \Umathunderbarrule \tex_Umathunderbarrule:D
1188 \__kernel_primitive:NN \Umathunderbarvgap \tex_Umathunderbarvgap:D
1189 \__kernel_primitive:NN \Umathunderdelimeterbgap
1190     \tex_Umathunderdelimeterbgap:D

```

1191	<code>__kernel_primitive:NN \Umathunderdelimitervgap</code>	
1192	<code>\tex_Umathunderdelimitervgap:D</code>	
1193	<code>__kernel_primitive:NN \Unosubscript</code>	<code>\tex_Unosubscript:D</code>
1194	<code>__kernel_primitive:NN \Unosuperscript</code>	<code>\tex_Unosuperscript:D</code>
1195	<code>__kernel_primitive:NN \Uoverdelimiter</code>	<code>\tex_Uoverdelimiter:D</code>
1196	<code>__kernel_primitive:NN \Uradical</code>	<code>\tex_Uradical:D</code>
1197	<code>__kernel_primitive:NN \Uroot</code>	<code>\tex_Uroot:D</code>
1198	<code>__kernel_primitive:NN \Uskewed</code>	<code>\tex_Uskewed:D</code>
1199	<code>__kernel_primitive:NN \Uskewedwithdelims</code>	<code>\tex_Uskewedwithdelims:D</code>
1200	<code>__kernel_primitive:NN \Ustack</code>	<code>\tex_Ustack:D</code>
1201	<code>__kernel_primitive:NN \Ustartdisplaymath</code>	<code>\tex_Ustartdisplaymath:D</code>
1202	<code>__kernel_primitive:NN \Ustartmath</code>	<code>\tex_Ustartmath:D</code>
1203	<code>__kernel_primitive:NN \Ustopdisplaymath</code>	<code>\tex_Ustopdisplaymath:D</code>
1204	<code>__kernel_primitive:NN \Ustopmath</code>	<code>\tex_Ustopmath:D</code>
1205	<code>__kernel_primitive:NN \Usubscript</code>	<code>\tex_Usubscript:D</code>
1206	<code>__kernel_primitive:NN \Usuperscript</code>	<code>\tex_Usuperscript:D</code>
1207	<code>__kernel_primitive:NN \Uunderdelimiter</code>	<code>\tex_Uunderdelimiter:D</code>
1208	<code>__kernel_primitive:NN \Uvextensible</code>	<code>\tex_Uvextensible:D</code>

Primitives from pTeX.

1209	<code>__kernel_primitive:NN \autospaceing</code>	<code>\tex_autospaceing:D</code>
1210	<code>__kernel_primitive:NN \autoxspaceing</code>	<code>\tex_autoxspaceing:D</code>
1211	<code>__kernel_primitive:NN \currentcjktoken</code>	<code>\tex_currentcjktoken:D</code>
1212	<code>__kernel_primitive:NN \currentspacingmode</code>	<code>\tex_currentspacingmode:D</code>
1213	<code>__kernel_primitive:NN \currentxspacingmode</code>	<code>\tex_currentxspacingmode:D</code>
1214	<code>__kernel_primitive:NN \disinhibitglue</code>	<code>\tex_disinhibitglue:D</code>
1215	<code>__kernel_primitive:NN \dtou</code>	<code>\tex_dtou:D</code>
1216	<code>__kernel_primitive:NN \epTeXinputencoding</code>	<code>\tex_epTeXinputencoding:D</code>
1217	<code>__kernel_primitive:NN \epTeXversion</code>	<code>\tex_epTeXversion:D</code>
1218	<code>__kernel_primitive:NN \euc</code>	<code>\tex_euc:D</code>
1219	<code>__kernel_primitive:NN \hfi</code>	<code>\tex_hfi:D</code>
1220	<code>__kernel_primitive:NN \ifdbbox</code>	<code>\tex_ifdbbox:D</code>
1221	<code>__kernel_primitive:NN \ifddir</code>	<code>\tex_ifddir:D</code>
1222	<code>__kernel_primitive:NN \ifjfont</code>	<code>\tex_ifjfont:D</code>
1223	<code>__kernel_primitive:NN \ifmbox</code>	<code>\tex_ifmbox:D</code>
1224	<code>__kernel_primitive:NN \ifmdir</code>	<code>\tex_ifmdir:D</code>
1225	<code>__kernel_primitive:NN \iftbox</code>	<code>\tex_iftbox:D</code>
1226	<code>__kernel_primitive:NN \iftfont</code>	<code>\tex_iftfont:D</code>
1227	<code>__kernel_primitive:NN \iftdir</code>	<code>\tex_iftdir:D</code>
1228	<code>__kernel_primitive:NN \ifybox</code>	<code>\tex_ifybox:D</code>
1229	<code>__kernel_primitive:NN \ifydir</code>	<code>\tex_ifydir:D</code>
1230	<code>__kernel_primitive:NN \inhibitglue</code>	<code>\tex_inhibitglue:D</code>
1231	<code>__kernel_primitive:NN \inhibitxspcode</code>	<code>\tex_inhibitxspcode:D</code>
1232	<code>__kernel_primitive:NN \jcharwidowpenalty</code>	<code>\tex_jcharwidowpenalty:D</code>
1233	<code>__kernel_primitive:NN \jfam</code>	<code>\tex_jfam:D</code>
1234	<code>__kernel_primitive:NN \jfont</code>	<code>\tex_jfont:D</code>
1235	<code>__kernel_primitive:NN \jis</code>	<code>\tex_jis:D</code>
1236	<code>__kernel_primitive:NN \kanjiskip</code>	<code>\tex_kanjiskip:D</code>
1237	<code>__kernel_primitive:NN \kansuji</code>	<code>\tex_kansuji:D</code>
1238	<code>__kernel_primitive:NN \kansujichar</code>	<code>\tex_kansujichar:D</code>
1239	<code>__kernel_primitive:NN \kcatcode</code>	<code>\tex_kcatcode:D</code>
1240	<code>__kernel_primitive:NN \kuten</code>	<code>\tex_kuten:D</code>
1241	<code>__kernel_primitive:NN \lastnodechar</code>	<code>\tex_lastnodechar:D</code>
1242	<code>__kernel_primitive:NN \lastnodesubtype</code>	<code>\tex_lastnodesubtype:D</code>
1243	<code>__kernel_primitive:NN \noautospaceing</code>	<code>\tex_noautospaceing:D</code>


```

1244 \__kernel_primitive:NN \noautoxspacing \tex_noautoxspacing:D
1245 \__kernel_primitive:NN \pagefistretch \tex_pagefistretch:D
1246 \__kernel_primitive:NN \postbreakpenalty \tex_postbreakpenalty:D
1247 \__kernel_primitive:NN \prebreakpenalty \tex_prebreakpenalty:D
1248 \__kernel_primitive:NN \ptexminorversion \tex_ptexminorversion:D
1249 \__kernel_primitive:NN \ptexrevision \tex_ptexrevision:D
1250 \__kernel_primitive:NN \ptexversion \tex_ptexversion:D
1251 \__kernel_primitive:NN \readpapersizespecial \tex_readpapersizespecial:D
1252 \__kernel_primitive:NN \scriptbaselineshiftfactor
1253 \tex_scriptbaselineshiftfactor:D
1254 \__kernel_primitive:NN \scriptscriptbaselineshiftfactor
1255 \tex_scriptscriptbaselineshiftfactor:D
1256 \__kernel_primitive:NN \showmode \tex_showmode:D
1257 \__kernel_primitive:NN \sjis \tex_sjis:D
1258 \__kernel_primitive:NN \tate \tex_tate:D
1259 \__kernel_primitive:NN \tbaselineshift \tex_tbaselineshift:D
1260 \__kernel_primitive:NN \textbaselineshiftfactor
1261 \tex_textbaselineshiftfactor:D
1262 \__kernel_primitive:NN \tfont \tex_tfont:D
1263 \__kernel_primitive:NN \xkanjiskip \tex_xkanjiskip:D
1264 \__kernel_primitive:NN \xspcode \tex_xspcode:D
1265 \__kernel_primitive:NN \ybaselineshift \tex_ybaselineshift:D
1266 \__kernel_primitive:NN \yoko \tex_yoko:D
1267 \__kernel_primitive:NN \vfi \tex_vfi:D

```

Primitives from up $\mathsf{\TeX}$.

```

1268 \__kernel_primitive:NN \currentcjktoken \tex_currentcjktoken:D
1269 \__kernel_primitive:NN \disablecjktoken \tex_disablecjktoken:D
1270 \__kernel_primitive:NN \enablecjktoken \tex_enablecjktoken:D
1271 \__kernel_primitive:NN \forcecjktoken \tex_forcecjktoken:D
1272 \__kernel_primitive:NN \kchar \tex_kchar:D
1273 \__kernel_primitive:NN \kchardef \tex_kchardef:D
1274 \__kernel_primitive:NN \kuten \tex_kuten:D
1275 \__kernel_primitive:NN \ucs \tex_ucs:D
1276 \__kernel_primitive:NN \uptexrevision \tex_uptexrevision:D
1277 \__kernel_primitive:NN \uptexversion \tex_uptexversion:D

```

Omega primitives provided by p $\mathsf{\TeX}$ (listed separately mainly to allow understanding of their source).

```

1278 \__kernel_primitive:NN \odelcode \tex_odelcode:D
1279 \__kernel_primitive:NN \odelimiter \tex_odelimiter:D
1280 \__kernel_primitive:NN \omathaccent \tex_omathaccent:D
1281 \__kernel_primitive:NN \omathchar \tex_omathchar:D
1282 \__kernel_primitive:NN \omathchardef \tex_omathchardef:D
1283 \__kernel_primitive:NN \omathcode \tex_omathcode:D
1284 \__kernel_primitive:NN \oradical \tex_oradical:D

```

End of the “just the names” part of the source.

```

1285 </initex | names | package>
1286 <*initex | package>

```

The job is done: close the group (using the primitive renamed!).

```

1287 \tex_endgroup:D

```

$\mathsf{\LaTeX} 2_{\epsilon}$ moves a few primitives, so these are sorted out. A convenient test for $\mathsf{\LaTeX} 2_{\epsilon}$ is the `\@@end` saved primitive.

```

1288 \*package\
1289 \tex_ifdefined:D \@@end
1290 \tex_let:D \tex_end:D \@@end
1291 \tex_let:D \tex_everydisplay:D \frozen@everydisplay
1292 \tex_let:D \tex_everymath:D \frozen@everymath
1293 \tex_let:D \tex_hyphen:D \@@hyph
1294 \tex_let:D \tex_input:D \@@input
1295 \tex_let:D \tex_italiccorrection:D \@@italiccorr
1296 \tex_let:D \tex_underline:D \@@underline

```

The `\shipout` primitive is particularly tricky as a number of packages want to hook in here. First, we see if a sufficiently-new kernel has saved a copy: if it has, just use that. Otherwise, we need to check each of the possible packages/classes that might move it: here, we are looking for those which do *not* delay action to the `\AtBeginDocument` hook. (We cannot use `\primitive` as that doesn't allow us to make a direct copy of the primitive *itself*.) As we know that L^AT_EX 2_ε is in use, we use its `\@tfor` loop here.

```

1297 \tex_ifdefined:D \@@shipout
1298 \tex_let:D \tex_shipout:D \@@shipout
1299 \tex_fi:D
1300 \tex_begingroup:D
1301 \tex_edef:D \l_tmpa_tl { \tex_string:D \shipout }
1302 \tex_edef:D \l_tmpb_tl { \tex_meaning:D \shipout }
1303 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1304 \tex_else:D
1305 \tex_expandafter:D \@tfor \tex_expandafter:D \@tempa \tex_string:D :=
1306 \CROP@shipout
1307 \dup@shipout
1308 \GPTorg@shipout
1309 \LL@shipout
1310 \mem@oldshipout
1311 \opem@shipout
1312 \pgfpages@originalshipout
1313 \pr@shipout
1314 \Shipout
1315 \verso@orig@shipout
1316 \do
1317 {
1318 \tex_edef:D \l_tmpb_tl
1319 { \tex_expandafter:D \tex_meaning:D \@tempa }
1320 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1321 \tex_global:D \tex_expandafter:D \tex_let:D
1322 \tex_expandafter:D \tex_shipout:D \@tempa
1323 \tex_fi:D
1324 }
1325 \tex_fi:D
1326 \tex_endgroup:D

```

Some tidying up is needed for `\(pdf)tracingfonts`. Newer L^AT_EX has this simply as `\tracingfonts`, but that is overwritten by the L^AT_EX 2_ε kernel. So any spurious definition has to be removed, then the real version saved either from the pdfT_EX name or from L^AT_EX. In the latter case, we leave `\@@tracingfonts` available: this might be useful and almost all L^AT_EX 2_ε users will have `expl3` loaded by `fontspec`. (We follow the usual kernel convention that `@@` is used for saved primitives.)

```

1327 \tex_let:D \tex_tracingfonts:D \tex_undefined:D

```

```

1328 \tex_ifdefined:D \pdftracingfonts
1329 \tex_let:D \tex_tracingfonts:D \pdftracingfonts
1330 \tex_else:D
1331 \tex_ifdefined:D \tex_directlua:D
1332 \tex_directlua:D { tex.enableprimitives("@@", {"tracingfonts"}) }
1333 \tex_let:D \tex_tracingfonts:D \@@tracingfonts
1334 \tex_fi:D
1335 \tex_fi:D
1336 \tex_fi:D

```

That is also true for the LuaTeX primitives under L^AT_EX 2_ε (depending on the format-building date). There are a few primitives that get the right names anyway so are missing here!

```

1337 \tex_ifdefined:D \luatexsuppressfontnotfounderror
1338 \tex_let:D \tex_alignmark:D \luatexalignmark
1339 \tex_let:D \tex_aligntab:D \luatexaligntab
1340 \tex_let:D \tex_attribute:D \luatexattribute
1341 \tex_let:D \tex_attributedef:D \luatexattributedef
1342 \tex_let:D \tex_catcodetable:D \luatexcatcodetable
1343 \tex_let:D \tex_clearmarks:D \luatexclearmarks
1344 \tex_let:D \tex_crampeddisplaystyle:D \luatexcrampeddisplaystyle
1345 \tex_let:D \tex_crampedscriptscriptstyle:D
1346 \luatexcrampedscriptscriptstyle
1347 \tex_let:D \tex_crampedscriptstyle:D \luatexcrampedscriptstyle
1348 \tex_let:D \tex_crampedtextstyle:D \luatexcrampedtextstyle
1349 \tex_let:D \tex_fontid:D \luatexfontid
1350 \tex_let:D \tex_formatname:D \luatexformatname
1351 \tex_let:D \tex_gleaders:D \luatexgleaders
1352 \tex_let:D \tex_initcatcodetable:D \luatexinitcatcodetable
1353 \tex_let:D \tex_latelua:D \luatexlatelua
1354 \tex_let:D \tex_luaescapestring:D \luatexluaescapestring
1355 \tex_let:D \tex_luafunction:D \luatexluafunction
1356 \tex_let:D \tex_mathstyle:D \luatexmathstyle
1357 \tex_let:D \tex_nokerns:D \luatexnokerns
1358 \tex_let:D \tex_noligs:D \luatexnoligs
1359 \tex_let:D \tex_outputbox:D \luatexoutputbox
1360 \tex_let:D \tex_pageleftoffset:D \luatexpageleftoffset
1361 \tex_let:D \tex_pagetopoffset:D \luatexpagetopoffset
1362 \tex_let:D \tex_postexhyphenchar:D \luatexpostexhyphenchar
1363 \tex_let:D \tex_posthyphenchar:D \luatexposthyphenchar
1364 \tex_let:D \tex_preexhyphenchar:D \luatexpreexhyphenchar
1365 \tex_let:D \tex_prehyphenchar:D \luatexprehyphenchar
1366 \tex_let:D \tex_savecatcodetable:D \luatexsavecatcodetable
1367 \tex_let:D \tex_scantextokens:D \luatexscantextokens
1368 \tex_let:D \tex_suppressifcsnameerror:D
1369 \luatexsuppressifcsnameerror
1370 \tex_let:D \tex_suppresslongerror:D \luatexsuppresslongerror
1371 \tex_let:D \tex_suppressmathparerror:D
1372 \luatexsuppressmathparerror
1373 \tex_let:D \tex_suppressoutererror:D \luatexsuppressoutererror
1374 \tex_let:D \tex_Uchar:D \luatexUchar
1375 \tex_let:D \tex_suppressfontnotfounderror:D
1376 \luatexsuppressfontnotfounderror

```

Which also covers those slightly odd ones.

```

1377 \tex_let:D \tex_bodydir:D \luatexbodydir
1378 \tex_let:D \tex_boxdir:D \luatexboxdir
1379 \tex_let:D \tex_leftghost:D \luatexleftghost
1380 \tex_let:D \tex_localbrokenpenalty:D \luatexlocalbrokenpenalty
1381 \tex_let:D \tex_localinterlinepenalty:D
1382 \luatexlocalinterlinepenalty
1383 \tex_let:D \tex_localleftbox:D \luatexlocalleftbox
1384 \tex_let:D \tex_localrightbox:D \luatexlocalrightbox
1385 \tex_let:D \tex_mathdir:D \luatexmathdir
1386 \tex_let:D \tex_pagebottomoffset:D \luatexpagebottomoffset
1387 \tex_let:D \tex_pagedir:D \luatexpagedir
1388 \tex_let:D \tex_pageheight:D \luatexpageheight
1389 \tex_let:D \tex_pagerightoffset:D \luatexpagerightoffset
1390 \tex_let:D \tex_pagewidth:D \luatexpagewidth
1391 \tex_let:D \tex_pardir:D \luatexpardir
1392 \tex_let:D \tex_rightghost:D \luatexrightghost
1393 \tex_let:D \tex_textdir:D \luatextextdir
1394 \tex_fi:D

```

Only pdfTeX and LuaTeX define \pdfmapfile and \pdfmapline: Tidy up the fact that some format-building processes leave a couple of questionable decisions about that!

```

1395 \tex_ifnum:D 0
1396 \tex_ifdefined:D \tex_pdftexversion:D 1 \tex_fi:D
1397 \tex_ifdefined:D \tex_luatexversion:D 1 \tex_fi:D
1398 = 0 %
1399 \tex_let:D \tex_mapfile:D \tex_undefined:D
1400 \tex_let:D \tex_mapline:D \tex_undefined:D
1401 \tex_fi:D
1402 </package>

```

A few packages do unfortunate things to date-related primitives.

```

1403 \tex_begingroup:D
1404 \tex_edef:D \l_tmpa_tl { \tex_meaning:D \tex_time:D }
1405 \tex_edef:D \l_tmpb_tl { \tex_string:D \time }
1406 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1407 \tex_else:D
1408 \tex_global:D \tex_let:D \tex_time:D \tex_undefined:D
1409 \tex_fi:D
1410 \tex_edef:D \l_tmpa_tl { \tex_meaning:D \tex_day:D }
1411 \tex_edef:D \l_tmpb_tl { \tex_string:D \day }
1412 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1413 \tex_else:D
1414 \tex_global:D \tex_let:D \tex_day:D \tex_undefined:D
1415 \tex_fi:D
1416 \tex_edef:D \l_tmpa_tl { \tex_meaning:D \tex_month:D }
1417 \tex_edef:D \l_tmpb_tl { \tex_string:D \month }
1418 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1419 \tex_else:D
1420 \tex_global:D \tex_let:D \tex_month:D \tex_undefined:D
1421 \tex_fi:D
1422 \tex_edef:D \l_tmpa_tl { \tex_meaning:D \tex_year:D }
1423 \tex_edef:D \l_tmpb_tl { \tex_string:D \year }
1424 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1425 \tex_else:D
1426 \tex_global:D \tex_let:D \tex_year:D \tex_undefined:D

```

```

1427 \tex_fi:D
1428 \tex_endgroup:D

```

Up to v0.80, LuaTeX defines the pdfTeX version data: rather confusing. Removing them means that `\tex_pdftexversion:D` is a marker for pdfTeX alone: useful in engine-dependent code later.

```

1429 (*initex | package)
1430 \tex_ifdefined:D \tex luatexversion:D
1431 \tex_let:D \tex_pdftexbanner:D \tex_undefined:D
1432 \tex_let:D \tex_pdftexrevision:D \tex_undefined:D
1433 \tex_let:D \tex_pdftexversion:D \tex_undefined:D
1434 \tex_fi:D
1435 </initex | package>

```

For ConTeXt, two tests are needed. Both Mark II and Mark IV move several primitives: these are all covered by the first test, again using `\end` as a marker. For Mark IV, a few more primitives are moved: they are implemented using some Lua code in the current ConTeXt.

```

1436 <*package>
1437 \tex_ifdefined:D \normalend
1438 \tex_let:D \tex_end:D \normalend
1439 \tex_let:D \tex_everyjob:D \normaleveryjob
1440 \tex_let:D \tex_input:D \normalinput
1441 \tex_let:D \tex_language:D \normallanguage
1442 \tex_let:D \tex_mathop:D \normalmathop
1443 \tex_let:D \tex_month:D \normalmonth
1444 \tex_let:D \tex_outer:D \normalouter
1445 \tex_let:D \tex_over:D \normalover
1446 \tex_let:D \tex_vcenter:D \normalvcenter
1447 \tex_let:D \tex_unexpanded:D \normalunexpanded
1448 \tex_let:D \tex_expanded:D \normalexpanded
1449 \tex_fi:D
1450 \tex_ifdefined:D \normalitaliccorrection
1451 \tex_let:D \tex_hoffset:D \normalhoffset
1452 \tex_let:D \tex_italiccorrection:D \normalitaliccorrection
1453 \tex_let:D \tex_voffset:D \normalvoffset
1454 \tex_let:D \tex_showtokens:D \normalshowtokens
1455 \tex_let:D \tex_bodydir:D \spac_directions_normal_body_dir
1456 \tex_let:D \tex_pagedir:D \spac_directions_normal_page_dir
1457 \tex_fi:D
1458 \tex_ifdefined:D \normalleft
1459 \tex_let:D \tex_left:D \normalleft
1460 \tex_let:D \tex_middle:D \normalmiddle
1461 \tex_let:D \tex_right:D \normalright
1462 \tex_fi:D
1463 </package>

```

2.1 Deprecated functions

Older versions of expl3 divided up primitives by “source”: that becomes very tricky with multiple parallel engine developments, so has been dropped. To cover the transition, we provide the older names here for a limited period (until the end of 2019).

To allow `\debug_on:n {<deprecation>}` to work we save the list of primitives into `__kernel_primitives:`

```

1464 \*package\
1465 \tex_begingroup:D
1466 \tex_long:D \tex_def:D \use_ii:nn #1#2 {#2}
1467 \tex_long:D \tex_def:D \use_none:n #1 { }
1468 \tex_long:D \tex_def:D \__kernel_primitive:NN #1#2
1469 {
1470 \tex_ifdefined:D #1
1471 \tex_expandafter:D \use_ii:nn
1472 \tex_fi:D
1473 \use_none:n { \tex_global:D \tex_let:D #2 #1 }
1474 }
1475 \tex_xdef:D \__kernel_primitives:
1476 {
1477 \tex_unexpanded:D
1478 {
1479 \__kernel_primitive:NN \beginL \etex_beginL:D
1480 \__kernel_primitive:NN \beginR \etex_beginR:D
1481 \__kernel_primitive:NN \botmarks \etex_botmarks:D
1482 \__kernel_primitive:NN \clubpenalties \etex_clubpenalties:D
1483 \__kernel_primitive:NN \currentgrouplevel \etex_currentgrouplevel:D
1484 \__kernel_primitive:NN \currentgrouptype \etex_currentgrouptype:D
1485 \__kernel_primitive:NN \currentifbranch \etex_currentifbranch:D
1486 \__kernel_primitive:NN \currentiflevel \etex_currentiflevel:D
1487 \__kernel_primitive:NN \currentifttype \etex_currentifttype:D
1488 \__kernel_primitive:NN \detokenize \etex_detokenize:D
1489 \__kernel_primitive:NN \dimexpr \etex_dimexpr:D
1490 \__kernel_primitive:NN \displaywidowpenalties
1491 \etex_displaywidowpenalties:D
1492 \__kernel_primitive:NN \endL \etex_endL:D
1493 \__kernel_primitive:NN \endR \etex_endR:D
1494 \__kernel_primitive:NN \eTeXrevision \etex_eTeXrevision:D
1495 \__kernel_primitive:NN \eTeXversion \etex_eTeXversion:D
1496 \__kernel_primitive:NN \everyeof \etex_everyeof:D
1497 \__kernel_primitive:NN \firstmarks \etex_firstmarks:D
1498 \__kernel_primitive:NN \fontchardp \etex_fontchardp:D
1499 \__kernel_primitive:NN \fontcharht \etex_fontcharht:D
1500 \__kernel_primitive:NN \fontcharic \etex_fontcharic:D
1501 \__kernel_primitive:NN \fontcharwd \etex_fontcharwd:D
1502 \__kernel_primitive:NN \glueexpr \etex_glueexpr:D
1503 \__kernel_primitive:NN \glueshrink \etex_glueshrink:D
1504 \__kernel_primitive:NN \glueshrinkorder \etex_glueshrinkorder:D
1505 \__kernel_primitive:NN \gluestretch \etex_gluestretch:D
1506 \__kernel_primitive:NN \gluestretchorder \etex_gluestretchorder:D
1507 \__kernel_primitive:NN \gluetomu \etex_gluetomu:D
1508 \__kernel_primitive:NN \ifcsname \etex_ifcsname:D
1509 \__kernel_primitive:NN \ifdefined \etex_ifdefined:D
1510 \__kernel_primitive:NN \iffontchar \etex_iffontchar:D
1511 \__kernel_primitive:NN \interactionmode \etex_interactionmode:D
1512 \__kernel_primitive:NN \interlinepenalties \etex_interlinepenalties:D
1513 \__kernel_primitive:NN \lastlinefit \etex_lastlinefit:D
1514 \__kernel_primitive:NN \lastnodetype \etex_lastnodetype:D
1515 \__kernel_primitive:NN \marks \etex_marks:D
1516 \__kernel_primitive:NN \middle \etex_middle:D
1517 \__kernel_primitive:NN \muexpr \etex_muexpr:D

```

1518	_kernel_primitive:NN	\mutoglue	\etex_mutoglue:D
1519	_kernel_primitive:NN	\numexpr	\etex_numexpr:D
1520	_kernel_primitive:NN	\pagediscards	\etex_pagediscards:D
1521	_kernel_primitive:NN	\parshapedimen	\etex_parshapedimen:D
1522	_kernel_primitive:NN	\parshapeindent	\etex_parshapeindent:D
1523	_kernel_primitive:NN	\parshapelength	\etex_parshapelength:D
1524	_kernel_primitive:NN	\predisplaydirection	\etex_predisplaydirection:D
1525	_kernel_primitive:NN	\protected	\etex_protected:D
1526	_kernel_primitive:NN	\readline	\etex_readline:D
1527	_kernel_primitive:NN	\savinghyphcodes	\etex_savinghyphcodes:D
1528	_kernel_primitive:NN	\savingvdiscards	\etex_savingvdiscards:D
1529	_kernel_primitive:NN	\scantokens	\etex_scantokens:D
1530	_kernel_primitive:NN	\showgroups	\etex_showgroups:D
1531	_kernel_primitive:NN	\showifs	\etex_showifs:D
1532	_kernel_primitive:NN	\showtokens	\etex_showtokens:D
1533	_kernel_primitive:NN	\splitbotmarks	\etex_splitbotmarks:D
1534	_kernel_primitive:NN	\splitdiscards	\etex_splitdiscards:D
1535	_kernel_primitive:NN	\splitfirstmarks	\etex_splitfirstmarks:D
1536	_kernel_primitive:NN	\TeXeTstate	\etex_TeXeTstate:D
1537	_kernel_primitive:NN	\topmarks	\etex_topmarks:D
1538	_kernel_primitive:NN	\tracingassigns	\etex_tracingassigns:D
1539	_kernel_primitive:NN	\tracinggroups	\etex_tracinggroups:D
1540	_kernel_primitive:NN	\tracingifs	\etex_tracingifs:D
1541	_kernel_primitive:NN	\tracingnesting	\etex_tracingnesting:D
1542	_kernel_primitive:NN	\tracingscantokens	\etex_tracingscantokens:D
1543	_kernel_primitive:NN	\unexpanded	\etex_unexpanded:D
1544	_kernel_primitive:NN	\unless	\etex_unless:D
1545	_kernel_primitive:NN	\widowpenalties	\etex_widowpenalties:D
1546	_kernel_primitive:NN	\pdfannot	\pdfTEX_pdfannot:D
1547	_kernel_primitive:NN	\pdfcatalog	\pdfTEX_pdfcatalog:D
1548	_kernel_primitive:NN	\pdfcompresslevel	\pdfTEX_pdfcompresslevel:D
1549	_kernel_primitive:NN	\pdfcolorstack	\pdfTEX_pdfcolorstack:D
1550	_kernel_primitive:NN	\pdfcolorstackinit	\pdfTEX_pdfcolorstackinit:D
1551	_kernel_primitive:NN	\pdfcreationdate	\pdfTEX_pdfcreationdate:D
1552	_kernel_primitive:NN	\pdfdecimaldigits	\pdfTEX_pdfdecimaldigits:D
1553	_kernel_primitive:NN	\pdfdest	\pdfTEX_pdfdest:D
1554	_kernel_primitive:NN	\pdfdestmargin	\pdfTEX_pdfdestmargin:D
1555	_kernel_primitive:NN	\pdfendlink	\pdfTEX_pdfendlink:D
1556	_kernel_primitive:NN	\pdfendthread	\pdfTEX_pdfendthread:D
1557	_kernel_primitive:NN	\pdffontattr	\pdfTEX_pdffontattr:D
1558	_kernel_primitive:NN	\pdffontname	\pdfTEX_pdffontname:D
1559	_kernel_primitive:NN	\pdffontobjnum	\pdfTEX_pdffontobjnum:D
1560	_kernel_primitive:NN	\pdfgamma	\pdfTEX_pdfgamma:D
1561	_kernel_primitive:NN	\pdfimageapplygamma	\pdfTEX_pdfimageapplygamma:D
1562	_kernel_primitive:NN	\pdfimagegamma	\pdfTEX_pdfimagegamma:D
1563	_kernel_primitive:NN	\pdfgentounicode	\pdfTEX_pdfgentounicode:D
1564	_kernel_primitive:NN	\pdfglyphtounicode	\pdfTEX_pdfglyphtounicode:D
1565	_kernel_primitive:NN	\pdfhorigin	\pdfTEX_pdfhorigin:D
1566	_kernel_primitive:NN	\pdfimagehicolor	\pdfTEX_pdfimagehicolor:D
1567	_kernel_primitive:NN	\pdfimageresolution	\pdfTEX_pdfimageresolution:D
1568	_kernel_primitive:NN	\pdfincludechars	\pdfTEX_pdfincludechars:D
1569	_kernel_primitive:NN	\pdfinclusioncopyfonts	\pdfTEX_pdfinclusioncopyfonts:D
1570		\pdfTEX_pdfinclusioncopyfonts:D	
1571	_kernel_primitive:NN	\pdfinclusionerrorlevel	

1572	\pdfTex_pdfinclusionerrorlevel:D	
1573	_kernel_primitive:NN \pdfinfo	\pdfTex_pdfinfo:D
1574	_kernel_primitive:NN \pdfLastannot	\pdfTex_pdfLastannot:D
1575	_kernel_primitive:NN \pdfLastlink	\pdfTex_pdfLastlink:D
1576	_kernel_primitive:NN \pdfLastobj	\pdfTex_pdfLastobj:D
1577	_kernel_primitive:NN \pdfLastxform	\pdfTex_pdfLastxform:D
1578	_kernel_primitive:NN \pdfLastximage	\pdfTex_pdfLastximage:D
1579	_kernel_primitive:NN \pdfLastximagecolordepth	
1580	\pdfTex_pdfLastximagecolordepth:D	
1581	_kernel_primitive:NN \pdfLastximagepages	\pdfTex_pdfLastximagepages:D
1582	_kernel_primitive:NN \pdfLinkmargin	\pdfTex_pdfLinkmargin:D
1583	_kernel_primitive:NN \pdfLiteral	\pdfTex_pdfLiteral:D
1584	_kernel_primitive:NN \pdfMinorversion	\pdfTex_pdfMinorversion:D
1585	_kernel_primitive:NN \pdfNames	\pdfTex_pdfNames:D
1586	_kernel_primitive:NN \pdfObj	\pdfTex_pdfObj:D
1587	_kernel_primitive:NN \pdfObjcompresslevel	
1588	\pdfTex_pdfObjcompresslevel:D	
1589	_kernel_primitive:NN \pdfOutline	\pdfTex_pdfOutline:D
1590	_kernel_primitive:NN \pdfOutput	\pdfTex_pdfOutput:D
1591	_kernel_primitive:NN \pdfPageattr	\pdfTex_pdfPageattr:D
1592	_kernel_primitive:NN \pdfPagebox	\pdfTex_pdfPagebox:D
1593	_kernel_primitive:NN \pdfPageRef	\pdfTex_pdfPageRef:D
1594	_kernel_primitive:NN \pdfPageResources	\pdfTex_pdfPageResources:D
1595	_kernel_primitive:NN \pdfPagesattr	\pdfTex_pdfPagesattr:D
1596	_kernel_primitive:NN \pdfRefObj	\pdfTex_pdfRefObj:D
1597	_kernel_primitive:NN \pdfRefxform	\pdfTex_pdfRefxform:D
1598	_kernel_primitive:NN \pdfRefximage	\pdfTex_pdfRefximage:D
1599	_kernel_primitive:NN \pdfRestore	\pdfTex_pdfRestore:D
1600	_kernel_primitive:NN \pdfRetVal	\pdfTex_pdfRetVal:D
1601	_kernel_primitive:NN \pdfSave	\pdfTex_pdfSave:D
1602	_kernel_primitive:NN \pdfSetMatrix	\pdfTex_pdfSetMatrix:D
1603	_kernel_primitive:NN \pdfStartLink	\pdfTex_pdfStartLink:D
1604	_kernel_primitive:NN \pdfStartThread	\pdfTex_pdfStartThread:D
1605	_kernel_primitive:NN \pdfSuppressptexinfo	
1606	\pdfTex_pdfSuppressptexinfo:D	
1607	_kernel_primitive:NN \pdfThread	\pdfTex_pdfThread:D
1608	_kernel_primitive:NN \pdfThreadmargin	\pdfTex_pdfThreadmargin:D
1609	_kernel_primitive:NN \pdfTrailer	\pdfTex_pdfTrailer:D
1610	_kernel_primitive:NN \pdfUniqueresname	\pdfTex_pdfUniqueresname:D
1611	_kernel_primitive:NN \pdfVorigin	\pdfTex_pdfVorigin:D
1612	_kernel_primitive:NN \pdfXform	\pdfTex_pdfXform:D
1613	_kernel_primitive:NN \pdfXformattr	\pdfTex_pdfXformattr:D
1614	_kernel_primitive:NN \pdfXformname	\pdfTex_pdfXformname:D
1615	_kernel_primitive:NN \pdfXformResources	\pdfTex_pdfXformResources:D
1616	_kernel_primitive:NN \pdfXimage	\pdfTex_pdfXimage:D
1617	_kernel_primitive:NN \pdfXimagebbox	\pdfTex_pdfXimagebbox:D
1618	_kernel_primitive:NN \ifpdfabsdim	\pdfTex_ifabsdim:D
1619	_kernel_primitive:NN \ifpdfabsnum	\pdfTex_ifabsnum:D
1620	_kernel_primitive:NN \ifpdfprimitive	\pdfTex_ifprimitive:D
1621	_kernel_primitive:NN \pdfAdjustSpacing	\pdfTex_pdfAdjustSpacing:D
1622	_kernel_primitive:NN \pdfCopyFont	\pdfTex_copyFont:D
1623	_kernel_primitive:NN \pdfDraftMode	\pdfTex_draftMode:D
1624	_kernel_primitive:NN \pdfEachLineDepth	\pdfTex_eachLineDepth:D
1625	_kernel_primitive:NN \pdfEachLineHeight	\pdfTex_eachLineHeight:D

1626	_kernel_primitive:NN	\pdffilemoddate	\pdfTEX_filemoddate:D
1627	_kernel_primitive:NN	\pdffilesize	\pdfTEX_filesize:D
1628	_kernel_primitive:NN	\pdffirstlineheight	\pdfTEX_firstlineheight:D
1629	_kernel_primitive:NN	\pdffontexpand	\pdfTEX_fontexpand:D
1630	_kernel_primitive:NN	\pdffontsize	\pdfTEX_fontsize:D
1631	_kernel_primitive:NN	\pdfignoreddimen	\pdfTEX_ignoreddimen:D
1632	_kernel_primitive:NN	\pdfinsertht	\pdfTEX_insertht:D
1633	_kernel_primitive:NN	\pdflastlinedepth	\pdfTEX_lastlinedepth:D
1634	_kernel_primitive:NN	\pdflastxpos	\pdfTEX_lastxpos:D
1635	_kernel_primitive:NN	\pdflastypos	\pdfTEX_lastypos:D
1636	_kernel_primitive:NN	\pdfmapfile	\pdfTEX_mapfile:D
1637	_kernel_primitive:NN	\pdfmapline	\pdfTEX_mapline:D
1638	_kernel_primitive:NN	\pdfmdfivesum	\pdfTEX_mdfivesum:D
1639	_kernel_primitive:NN	\pdfnoligatures	\pdfTEX_noligatures:D
1640	_kernel_primitive:NN	\pdfnormaldeviate	\pdfTEX_normaldeviate:D
1641	_kernel_primitive:NN	\pdfpageheight	\pdfTEX_pageheight:D
1642	_kernel_primitive:NN	\pdfpagewidth	\pdfTEX_pagewidth:D
1643	_kernel_primitive:NN	\pdfpkmode	\pdfTEX_pkmode:D
1644	_kernel_primitive:NN	\pdfpkresolution	\pdfTEX_pkresolution:D
1645	_kernel_primitive:NN	\pdfprimitive	\pdfTEX_primitive:D
1646	_kernel_primitive:NN	\pdfprotrudechars	\pdfTEX_protrudechars:D
1647	_kernel_primitive:NN	\pdfpxdimen	\pdfTEX_pxdimen:D
1648	_kernel_primitive:NN	\pdfrandomseed	\pdfTEX_randomseed:D
1649	_kernel_primitive:NN	\pdfsavepos	\pdfTEX_savepos:D
1650	_kernel_primitive:NN	\pdfstrcmp	\pdfTEX_strcmp:D
1651	_kernel_primitive:NN	\pdfsetrandomseed	\pdfTEX_setrandomseed:D
1652	_kernel_primitive:NN	\pdfshellescape	\pdfTEX_shellescape:D
1653	_kernel_primitive:NN	\pdftracingfonts	\pdfTEX_tracingfonts:D
1654	_kernel_primitive:NN	\pdfuniformdeviate	\pdfTEX_uniformdeviate:D
1655	_kernel_primitive:NN	\pdfTEXbanner	\pdfTEX_pdfTEXbanner:D
1656	_kernel_primitive:NN	\pdfTEXrevision	\pdfTEX_pdfTEXrevision:D
1657	_kernel_primitive:NN	\pdfTEXversion	\pdfTEX_pdfTEXversion:D
1658	_kernel_primitive:NN	\efcode	\pdfTEX_efcode:D
1659	_kernel_primitive:NN	\ifincsname	\pdfTEX_ifincsname:D
1660	_kernel_primitive:NN	\leftmarginkern	\pdfTEX_leftmarginkern:D
1661	_kernel_primitive:NN	\letterspacefont	\pdfTEX_letterspacefont:D
1662	_kernel_primitive:NN	\lpcode	\pdfTEX_lpcode:D
1663	_kernel_primitive:NN	\quitvmode	\pdfTEX_quitvmode:D
1664	_kernel_primitive:NN	\rightmarginkern	\pdfTEX_rightmarginkern:D
1665	_kernel_primitive:NN	\rpcode	\pdfTEX_rpcode:D
1666	_kernel_primitive:NN	\synctex	\pdfTEX_synctex:D
1667	_kernel_primitive:NN	\tagcode	\pdfTEX_tagcode:D
1668	_kernel_primitive:NN	\mdfivesum	\pdfTEX_mdfivesum:D
1669	_kernel_primitive:NN	\ifprimitive	\pdfTEX_ifprimitive:D
1670	_kernel_primitive:NN	\primitive	\pdfTEX_primitive:D
1671	_kernel_primitive:NN	\shellescape	\pdfTEX_shellescape:D
1672	_kernel_primitive:NN	\adjustspacing	\pdfTEX_adjustspacing:D
1673	_kernel_primitive:NN	\copyfont	\pdfTEX_copyfont:D
1674	_kernel_primitive:NN	\draftmode	\pdfTEX_draftmode:D
1675	_kernel_primitive:NN	\expandglyphsinfont	\pdfTEX_fontexpand:D
1676	_kernel_primitive:NN	\ifabsdim	\pdfTEX_ifabsdim:D
1677	_kernel_primitive:NN	\ifabsnum	\pdfTEX_ifabsnum:D
1678	_kernel_primitive:NN	\ignoreligaturesinfont	\pdfTEX_ignoreligaturesinfont:D
1679		\pdfTEX_ignoreligaturesinfont:D	

```

1680 \__kernel_primitive:NN \insertht \pdfTeX_insertht:D
1681 \__kernel_primitive:NN \lastsavedboxresourceindex
1682 \pdfTeX_pdflastxform:D
1683 \__kernel_primitive:NN \lastsavedimageresourceindex
1684 \pdfTeX_pdflastximage:D
1685 \__kernel_primitive:NN \lastsavedimageresourcepages
1686 \pdfTeX_pdflastximagepages:D
1687 \__kernel_primitive:NN \lastxpos \pdfTeX_lastxpos:D
1688 \__kernel_primitive:NN \lastypos \pdfTeX_lastypos:D
1689 \__kernel_primitive:NN \normaldeviate \pdfTeX_normaldeviate:D
1690 \__kernel_primitive:NN \outputmode \pdfTeX_pdfoutput:D
1691 \__kernel_primitive:NN \pageheight \pdfTeX_pageheight:D
1692 \__kernel_primitive:NN \pagewidth \pdfTeX_pagewidth:D
1693 \__kernel_primitive:NN \protrudechars \pdfTeX_protrudechars:D
1694 \__kernel_primitive:NN \pxdimen \pdfTeX_pxdimen:D
1695 \__kernel_primitive:NN \randomseed \pdfTeX_randomseed:D
1696 \__kernel_primitive:NN \useboxresource \pdfTeX_pdfrefxform:D
1697 \__kernel_primitive:NN \useimageresource \pdfTeX_pdfrefximage:D
1698 \__kernel_primitive:NN \savepos \pdfTeX_savepos:D
1699 \__kernel_primitive:NN \saveboxresource \pdfTeX_pdfxform:D
1700 \__kernel_primitive:NN \saveimageresource \pdfTeX_pdfximage:D
1701 \__kernel_primitive:NN \setrandomseed \pdfTeX_setrandomseed:D
1702 \__kernel_primitive:NN \tracingfonts \pdfTeX_tracingfonts:D
1703 \__kernel_primitive:NN \uniformdeviate \pdfTeX_uniformdeviate:D
1704 \__kernel_primitive:NN \suppressfontnotfounderror
1705 \xetex_suppressfontnotfounderror:D
1706 \__kernel_primitive:NN \XeTeXcharclass \xetex_charclass:D
1707 \__kernel_primitive:NN \XeTeXcharglyph \xetex_charglyph:D
1708 \__kernel_primitive:NN \XeTeXcountfeatures \xetex_countfeatures:D
1709 \__kernel_primitive:NN \XeTeXcountglyphs \xetex_countglyphs:D
1710 \__kernel_primitive:NN \XeTeXcountselectors \xetex_countselectors:D
1711 \__kernel_primitive:NN \XeTeXcountvariations \xetex_countvariations:D
1712 \__kernel_primitive:NN \XeTeXdefaultencoding \xetex_defaultencoding:D
1713 \__kernel_primitive:NN \XeTeXdashbreakstate \xetex_dashbreakstate:D
1714 \__kernel_primitive:NN \XeTeXfeaturecode \xetex_featurecode:D
1715 \__kernel_primitive:NN \XeTeXfeaturename \xetex_featurename:D
1716 \__kernel_primitive:NN \XeTeXfindfeaturebyname
1717 \xetex_findfeaturebyname:D
1718 \__kernel_primitive:NN \XeTeXfindselectorbyname
1719 \xetex_findselectorbyname:D
1720 \__kernel_primitive:NN \XeTeXfindvariationbyname
1721 \xetex_findvariationbyname:D
1722 \__kernel_primitive:NN \XeTeXfirstfontchar \xetex_firstfontchar:D
1723 \__kernel_primitive:NN \XeTeXfonttype \xetex_fonttype:D
1724 \__kernel_primitive:NN \XeTeXgenerateactualtext
1725 \xetex_generateactualtext:D
1726 \__kernel_primitive:NN \XeTeXglyph \xetex_glyph:D
1727 \__kernel_primitive:NN \XeTeXglyphbounds \xetex_glyphbounds:D
1728 \__kernel_primitive:NN \XeTeXglyphindex \xetex_glyphindex:D
1729 \__kernel_primitive:NN \XeTeXglyphname \xetex_glyphname:D
1730 \__kernel_primitive:NN \XeTeXinputencoding \xetex_inputencoding:D
1731 \__kernel_primitive:NN \XeTeXinputnormalization
1732 \xetex_inputnormalization:D
1733 \__kernel_primitive:NN \XeTeXinterchartokenstate

```

```

1734 \xetex_interchartokenstate:D
1735 \__kernel_primitive:NN \XeTeXinterchartoks \xetex_interchartoks:D
1736 \__kernel_primitive:NN \XeTeXisdefaultselector
1737 \xetex_isdefaultselector:D
1738 \__kernel_primitive:NN \XeTeXisexclusivefeature
1739 \xetex_isexclusivefeature:D
1740 \__kernel_primitive:NN \XeTeXlastfontchar \xetex_lastfontchar:D
1741 \__kernel_primitive:NN \XeTeXlinebreakskip \xetex_linebreakskip:D
1742 \__kernel_primitive:NN \XeTeXlinebreaklocale \xetex_linebreaklocale:D
1743 \__kernel_primitive:NN \XeTeXlinebreakpenalty \xetex_linebreakpenalty:D
1744 \__kernel_primitive:NN \XeTeXOTcountfeatures \xetex_OTcountfeatures:D
1745 \__kernel_primitive:NN \XeTeXOTcountlanguages \xetex_OTcountlanguages:D
1746 \__kernel_primitive:NN \XeTeXOTcountscripts \xetex_OTcountscripts:D
1747 \__kernel_primitive:NN \XeTeXOTfeaturetag \xetex_OTfeaturetag:D
1748 \__kernel_primitive:NN \XeTeXOTlanguagetag \xetex_OTlanguagetag:D
1749 \__kernel_primitive:NN \XeTeXOTscripttag \xetex_OTscripttag:D
1750 \__kernel_primitive:NN \XeTeXpdffile \xetex_pdffile:D
1751 \__kernel_primitive:NN \XeTeXpdfpagecount \xetex_pdfpagecount:D
1752 \__kernel_primitive:NN \XeTeXpicfile \xetex_picfile:D
1753 \__kernel_primitive:NN \XeTeXselectorname \xetex_selectorname:D
1754 \__kernel_primitive:NN \XeTeXtracingfonts \xetex_tracingfonts:D
1755 \__kernel_primitive:NN \XeTeXupwardsmode \xetex_upwardsmode:D
1756 \__kernel_primitive:NN \XeTeXuseglyphmetrics \xetex_useglyphmetrics:D
1757 \__kernel_primitive:NN \XeTeXvariation \xetex_variation:D
1758 \__kernel_primitive:NN \XeTeXvariationdefault \xetex_variationdefault:D
1759 \__kernel_primitive:NN \XeTeXvariationmax \xetex_variationmax:D
1760 \__kernel_primitive:NN \XeTeXvariationmin \xetex_variationmin:D
1761 \__kernel_primitive:NN \XeTeXvariationname \xetex_variationname:D
1762 \__kernel_primitive:NN \XeTeXrevision \xetex_XeTeXrevision:D
1763 \__kernel_primitive:NN \XeTeXversion \xetex_XeTeXversion:D
1764 \__kernel_primitive:NN \alignmark \luatex_alignmark:D
1765 \__kernel_primitive:NN \aligntab \luatex_aligntab:D
1766 \__kernel_primitive:NN \attribute \luatex_attribute:D
1767 \__kernel_primitive:NN \attributedef \luatex_attributedef:D
1768 \__kernel_primitive:NN \automaticdiscretionary
1769 \luatex_automaticdiscretionary:D
1770 \__kernel_primitive:NN \automatichyphenmode
1771 \luatex_automatichyphenmode:D
1772 \__kernel_primitive:NN \automatichyphenpenalty
1773 \luatex_automatichyphenpenalty:D
1774 \__kernel_primitive:NN \beginsname \luatex_beginsname:D
1775 \__kernel_primitive:NN \breakafterdirmode \luatex_breakafterdirmode:D
1776 \__kernel_primitive:NN \catcodetable \luatex_catcodetable:D
1777 \__kernel_primitive:NN \clearmarks \luatex_clearmarks:D
1778 \__kernel_primitive:NN \crampeddisplaystyle
1779 \luatex_crampeddisplaystyle:D
1780 \__kernel_primitive:NN \crampedscriptscriptstyle
1781 \luatex_crampedscriptscriptstyle:D
1782 \__kernel_primitive:NN \crampedscriptstyle \luatex_crampedscriptstyle:D
1783 \__kernel_primitive:NN \crampedtextstyle \luatex_crampedtextstyle:D
1784 \__kernel_primitive:NN \directlua \luatex_directlua:D
1785 \__kernel_primitive:NN \dviextension \luatex_dviextension:D
1786 \__kernel_primitive:NN \dvifedback \luatex_dvifedback:D
1787 \__kernel_primitive:NN \dvivariable \luatex_dvivariable:D

```

1788	_kernel_primitive:NN	\etoksapp	\luatex_etoksapp:D
1789	_kernel_primitive:NN	\etokspre	\luatex_etokspre:D
1790	_kernel_primitive:NN	\explicithyphenpenalty	
1791		\luatex_explicithyphenpenalty:D	
1792	_kernel_primitive:NN	\expanded	\luatex_expanded:D
1793	_kernel_primitive:NN	\explicitdiscretionary	
1794		\luatex_explicitdiscretionary:D	
1795	_kernel_primitive:NN	\firstvalidlanguage	\luatex_firstvalidlanguage:D
1796	_kernel_primitive:NN	\fontid	\luatex_fontid:D
1797	_kernel_primitive:NN	\formatname	\luatex_formatname:D
1798	_kernel_primitive:NN	\hjcode	\luatex_hjcode:D
1799	_kernel_primitive:NN	\hpack	\luatex_hpack:D
1800	_kernel_primitive:NN	\hyphenationbounds	\luatex_hyphenationbounds:D
1801	_kernel_primitive:NN	\hyphenationmin	\luatex_hyphenationmin:D
1802	_kernel_primitive:NN	\hyphenpenaltymode	\luatex_hyphenpenaltymode:D
1803	_kernel_primitive:NN	\gleaders	\luatex_gleaders:D
1804	_kernel_primitive:NN	\initcatcodetable	\luatex_initcatcodetable:D
1805	_kernel_primitive:NN	\lastnamedcs	\luatex_lastnamedcs:D
1806	_kernel_primitive:NN	\latelua	\luatex_latelua:D
1807	_kernel_primitive:NN	\letcharcode	\luatex_letcharcode:D
1808	_kernel_primitive:NN	\luaescapestring	\luatex_luaescapestring:D
1809	_kernel_primitive:NN	\luafunction	\luatex_luafunction:D
1810	_kernel_primitive:NN	\luatexbanner	\luatex_luatexbanner:D
1811	_kernel_primitive:NN	\luatexrevision	\luatex_luatexrevision:D
1812	_kernel_primitive:NN	\luatexversion	\luatex_luatexversion:D
1813	_kernel_primitive:NN	\mathdelimitersmode	\luatex_mathdelimitersmode:D
1814	_kernel_primitive:NN	\mathdisplayskipmode	
1815		\luatex_mathdisplayskipmode:D	
1816	_kernel_primitive:NN	\matheqnogapstep	\luatex_matheqnogapstep:D
1817	_kernel_primitive:NN	\mathnolimitsmode	\luatex_mathnolimitsmode:D
1818	_kernel_primitive:NN	\mathoption	\luatex_mathoption:D
1819	_kernel_primitive:NN	\mathpenaltiesmode	\luatex_mathpenaltiesmode:D
1820	_kernel_primitive:NN	\mathrulesfam	\luatex_mathrulesfam:D
1821	_kernel_primitive:NN	\mathscriptsmode	\luatex_mathscriptsmode:D
1822	_kernel_primitive:NN	\mathscriptboxmode	\luatex_mathscriptboxmode:D
1823	_kernel_primitive:NN	\mathstyle	\luatex_mathstyle:D
1824	_kernel_primitive:NN	\mathsurroundmode	\luatex_mathsurroundmode:D
1825	_kernel_primitive:NN	\mathsurroundskip	\luatex_mathsurroundskip:D
1826	_kernel_primitive:NN	\nohrule	\luatex_nohrule:D
1827	_kernel_primitive:NN	\nokerns	\luatex_nokerns:D
1828	_kernel_primitive:NN	\noligs	\luatex_noligs:D
1829	_kernel_primitive:NN	\nospaces	\luatex_nospaces:D
1830	_kernel_primitive:NN	\novrule	\luatex_novrule:D
1831	_kernel_primitive:NN	\outputbox	\luatex_outputbox:D
1832	_kernel_primitive:NN	\pagebottomoffset	\luatex_pagebottomoffset:D
1833	_kernel_primitive:NN	\pageleftoffset	\luatex_pageleftoffset:D
1834	_kernel_primitive:NN	\pagerightoffset	\luatex_pagerightoffset:D
1835	_kernel_primitive:NN	\pagetopoffset	\luatex_pagetopoffset:D
1836	_kernel_primitive:NN	\pdfextension	\luatex_pdfextension:D
1837	_kernel_primitive:NN	\pdffeedback	\luatex_pdffeedback:D
1838	_kernel_primitive:NN	\pdfvariable	\luatex_pdfvariable:D
1839	_kernel_primitive:NN	\postexhyphenchar	\luatex_postexhyphenchar:D
1840	_kernel_primitive:NN	\posthyphenchar	\luatex_posthyphenchar:D
1841	_kernel_primitive:NN	\prebinoppenalty	\luatex_prebinoppenalty:D

1842	_kernel_primitive:NN \predisplaygapfactor	
1843	_luatex_predisplaygapfactor:D	
1844	_kernel_primitive:NN \preexhyphenchar	_luatex_preexhyphenchar:D
1845	_kernel_primitive:NN \prehyphenchar	_luatex_prehyphenchar:D
1846	_kernel_primitive:NN \prerelpenalty	_luatex_prerelpenalty:D
1847	_kernel_primitive:NN \savecatcodetable	_luatex_savecatcodetable:D
1848	_kernel_primitive:NN \scantextokens	_luatex_scantextokens:D
1849	_kernel_primitive:NN \setfontid	_luatex_setfontid:D
1850	_kernel_primitive:NN \shapemode	_luatex_shapemode:D
1851	_kernel_primitive:NN \suppressifcsnameerror	
1852	_luatex_suppressifcsnameerror:D	
1853	_kernel_primitive:NN \suppresslongerror	_luatex_suppresslongerror:D
1854	_kernel_primitive:NN \suppressmathparerror	
1855	_luatex_suppressmathparerror:D	
1856	_kernel_primitive:NN \suppressoutererror	_luatex_suppressoutererror:D
1857	_kernel_primitive:NN \suppressprimitiveerror	
1858	_luatex_suppressprimitiveerror:D	
1859	_kernel_primitive:NN \toksapp	_luatex_toksapp:D
1860	_kernel_primitive:NN \tokspre	_luatex_tokspre:D
1861	_kernel_primitive:NN \tpack	_luatex_tpack:D
1862	_kernel_primitive:NN \vpack	_luatex_vpack:D
1863	_kernel_primitive:NN \bodydir	_luatex_bodydir:D
1864	_kernel_primitive:NN \boxdir	_luatex_boxdir:D
1865	_kernel_primitive:NN \leftghost	_luatex_leftghost:D
1866	_kernel_primitive:NN \linedir	_luatex_linedir:D
1867	_kernel_primitive:NN \localbrokenpenalty	_luatex_localbrokenpenalty:D
1868	_kernel_primitive:NN \localinterlinepenalty	
1869	_luatex_localinterlinepenalty:D	
1870	_kernel_primitive:NN \localleftbox	_luatex_localleftbox:D
1871	_kernel_primitive:NN \localrightbox	_luatex_localrightbox:D
1872	_kernel_primitive:NN \mathdir	_luatex_mathdir:D
1873	_kernel_primitive:NN \pagedir	_luatex_pagedir:D
1874	_kernel_primitive:NN \pardir	_luatex_pardir:D
1875	_kernel_primitive:NN \rightghost	_luatex_rightghost:D
1876	_kernel_primitive:NN \textdir	_luatex_textdir:D
1877	_kernel_primitive:NN \Uchar	_utex_char:D
1878	_kernel_primitive:NN \Ucharcat	_utex_charcat:D
1879	_kernel_primitive:NN \Udelcode	_utex_delcode:D
1880	_kernel_primitive:NN \Udelcodenum	_utex_delcodenum:D
1881	_kernel_primitive:NN \Udelimiter	_utex_delimiter:D
1882	_kernel_primitive:NN \Udelimiterover	_utex_delimiterover:D
1883	_kernel_primitive:NN \Udelimiterunder	_utex_delimiterunder:D
1884	_kernel_primitive:NN \Uhextensible	_utex_hextensible:D
1885	_kernel_primitive:NN \Umathaccent	_utex_mathaccent:D
1886	_kernel_primitive:NN \Umathaxis	_utex_mathaxis:D
1887	_kernel_primitive:NN \Umathbinbinspacing	_utex_binbinspacing:D
1888	_kernel_primitive:NN \Umathbinclosespacing	_utex_binclosespacing:D
1889	_kernel_primitive:NN \Umathbininnerspacing	_utex_bininnerspacing:D
1890	_kernel_primitive:NN \Umathbinopenspacing	_utex_binopenspacing:D
1891	_kernel_primitive:NN \Umathbinopspacing	_utex_binopspacing:D
1892	_kernel_primitive:NN \Umathbinordspacing	_utex_binordspacing:D
1893	_kernel_primitive:NN \Umathbinpunctspacing	_utex_binpunctspacing:D
1894	_kernel_primitive:NN \Umathbinrelspacing	_utex_binrelspacing:D
1895	_kernel_primitive:NN \Umathchar	_utex_mathchar:D

1896 __kernel_primitive:NN \Umathcharclass \utex_mathcharclass:D
1897 __kernel_primitive:NN \Umathchardef \utex_mathchardef:D
1898 __kernel_primitive:NN \Umathcharfam \utex_mathcharfam:D
1899 __kernel_primitive:NN \Umathcharnum \utex_mathcharnum:D
1900 __kernel_primitive:NN \Umathcharnumdef \utex_mathcharnumdef:D
1901 __kernel_primitive:NN \Umathcharslot \utex_mathcharslot:D
1902 __kernel_primitive:NN \Umathclosebinspacing \utex_closebinspacing:D
1903 __kernel_primitive:NN \Umathcloseclosespacing
1904 \utex_closeclosespacing:D
1905 __kernel_primitive:NN \Umathcloseinnerspacing
1906 \utex_closeinnerspacing:D
1907 __kernel_primitive:NN \Umathcloseopenspacing \utex_closeopenspacing:D
1908 __kernel_primitive:NN \Umathcloseopspacing \utex_closeopspacing:D
1909 __kernel_primitive:NN \Umathcloseordspacing \utex_closeordspacing:D
1910 __kernel_primitive:NN \Umathclosepunctspacing
1911 \utex_closepunctspacing:D
1912 __kernel_primitive:NN \Umathcloserelspacing \utex_closerelspacing:D
1913 __kernel_primitive:NN \Umathcode \utex_mathcode:D
1914 __kernel_primitive:NN \Umathcodenum \utex_mathcodenum:D
1915 __kernel_primitive:NN \Umathconnectoroverlapmin
1916 \utex_connectoroverlapmin:D
1917 __kernel_primitive:NN \Umathfractiondelsize \utex_fractiondelsize:D
1918 __kernel_primitive:NN \Umathfractiondenomdown
1919 \utex_fractiondenomdown:D
1920 __kernel_primitive:NN \Umathfractiondenomvgap
1921 \utex_fractiondenomvgap:D
1922 __kernel_primitive:NN \Umathfractionnumup \utex_fractionnumup:D
1923 __kernel_primitive:NN \Umathfractionnumvgap \utex_fractionnumvgap:D
1924 __kernel_primitive:NN \Umathfractionrule \utex_fractionrule:D
1925 __kernel_primitive:NN \Umathinnerbinspacing \utex_innerbinspacing:D
1926 __kernel_primitive:NN \Umathinnerclosespacing
1927 \utex_innerclosespacing:D
1928 __kernel_primitive:NN \Umathinnerinnerspacing
1929 \utex_innerinnerspacing:D
1930 __kernel_primitive:NN \Umathinneropenspacing \utex_inneropenspacing:D
1931 __kernel_primitive:NN \Umathinneropspacing \utex_inneropspacing:D
1932 __kernel_primitive:NN \Umathinnerordspacing \utex_innerordspacing:D
1933 __kernel_primitive:NN \Umathinnerpunctspacing
1934 \utex_innerpunctspacing:D
1935 __kernel_primitive:NN \Umathinnerrelspacing \utex_innerrelspacing:D
1936 __kernel_primitive:NN \Umathlimitabovebgap \utex_limitabovebgap:D
1937 __kernel_primitive:NN \Umathlimitabovekern \utex_limitabovekern:D
1938 __kernel_primitive:NN \Umathlimitabovevgap \utex_limitabovevgap:D
1939 __kernel_primitive:NN \Umathlimitbelowbgap \utex_limitbelowbgap:D
1940 __kernel_primitive:NN \Umathlimitbelowkern \utex_limitbelowkern:D
1941 __kernel_primitive:NN \Umathlimitbelowvgap \utex_limitbelowvgap:D
1942 __kernel_primitive:NN \Umathnolimitsubfactor \utex_nolimitsubfactor:D
1943 __kernel_primitive:NN \Umathnolimitsupfactor \utex_nolimitsupfactor:D
1944 __kernel_primitive:NN \Umathopbinspacing \utex_opbinspacing:D
1945 __kernel_primitive:NN \Umathopclosespacing \utex_opclosespacing:D
1946 __kernel_primitive:NN \Umathopenbinspacing \utex_openbinspacing:D
1947 __kernel_primitive:NN \Umathopenclosespacing \utex_openclosespacing:D
1948 __kernel_primitive:NN \Umathopeninnerspacing \utex_openinnerspacing:D
1949 __kernel_primitive:NN \Umathopenopenspacing \utex_openopenspacing:D

1950 __kernel_primitive:NN \Umathopenopspacing \utex_openopspacing:D
1951 __kernel_primitive:NN \Umathopenordspacing \utex_openordspacing:D
1952 __kernel_primitive:NN \Umathopenpunctspacing \utex_openpunctspacing:D
1953 __kernel_primitive:NN \Umathopenrelspacing \utex_openrelspacing:D
1954 __kernel_primitive:NN \Umathoperatorsize \utex_operatorsize:D
1955 __kernel_primitive:NN \Umathopinnerspacing \utex_opinnerspacing:D
1956 __kernel_primitive:NN \Umathopopenspacing \utex_opopenspacing:D
1957 __kernel_primitive:NN \Umathopopspacing \utex_opopspacing:D
1958 __kernel_primitive:NN \Umathopordspacing \utex_opordspacing:D
1959 __kernel_primitive:NN \Umathoppunctspacing \utex_oppunctspacing:D
1960 __kernel_primitive:NN \Umathoprelspacing \utex_oprelspacing:D
1961 __kernel_primitive:NN \Umathordbinspacing \utex_ordbinspacing:D
1962 __kernel_primitive:NN \Umathordclosespacing \utex_ordclosespacing:D
1963 __kernel_primitive:NN \Umathordinnerspacing \utex_ordinnerspacing:D
1964 __kernel_primitive:NN \Umathordopenspacing \utex_ordopenspacing:D
1965 __kernel_primitive:NN \Umathordopspacing \utex_ordopspacing:D
1966 __kernel_primitive:NN \Umathordordspacing \utex_ordordspacing:D
1967 __kernel_primitive:NN \Umathordpunctspacing \utex_ordpunctspacing:D
1968 __kernel_primitive:NN \Umathordreldspacing \utex_ordreldspacing:D
1969 __kernel_primitive:NN \Umathoverbarkern \utex_overbarkern:D
1970 __kernel_primitive:NN \Umathoverbarrule \utex_overbarrule:D
1971 __kernel_primitive:NN \Umathoverbarvgap \utex_overbarvgap:D
1972 __kernel_primitive:NN \Umathoverdelimeterbgap
1973 \utex_overdelimeterbgap:D
1974 __kernel_primitive:NN \Umathoverdelimitervgap
1975 \utex_overdelimitervgap:D
1976 __kernel_primitive:NN \Umathpunctbinspacing \utex_punctbinspacing:D
1977 __kernel_primitive:NN \Umathpunctclosespacing
1978 \utex_punctclosespacing:D
1979 __kernel_primitive:NN \Umathpunctinnerspacing
1980 \utex_punctinnerspacing:D
1981 __kernel_primitive:NN \Umathpunctopenspacing \utex_punctopenspacing:D
1982 __kernel_primitive:NN \Umathpunctopspacing \utex_punctopspacing:D
1983 __kernel_primitive:NN \Umathpunctordspacing \utex_punctordspacing:D
1984 __kernel_primitive:NN \Umathpunctpunctspacing \utex_punctpunctspacing:D
1985 __kernel_primitive:NN \Umathpunctrelspacing \utex_punctrelspacing:D
1986 __kernel_primitive:NN \Umathquad \utex_quad:D
1987 __kernel_primitive:NN \Umathradicaldegreeafter
1988 \utex_radicaldegreeafter:D
1989 __kernel_primitive:NN \Umathradicaldegreebefore
1990 \utex_radicaldegreebefore:D
1991 __kernel_primitive:NN \Umathradicaldegreeraise
1992 \utex_radicaldegreeraise:D
1993 __kernel_primitive:NN \Umathradicalkern \utex_radicalkern:D
1994 __kernel_primitive:NN \Umathradicalrule \utex_radicalrule:D
1995 __kernel_primitive:NN \Umathradicalvgap \utex_radicalvgap:D
1996 __kernel_primitive:NN \Umathrelbinspacing \utex_relbinspacing:D
1997 __kernel_primitive:NN \Umathrelclosespacing \utex_relclosespacing:D
1998 __kernel_primitive:NN \Umathrelinnerspacing \utex_relinnerspacing:D
1999 __kernel_primitive:NN \Umathrelopenspacing \utex_reloppenspacing:D
2000 __kernel_primitive:NN \Umathrelopspacing \utex_reloppspacing:D
2001 __kernel_primitive:NN \Umathrelordspacing \utex_relordspacing:D
2002 __kernel_primitive:NN \Umathrelpunctspacing \utex_relpunctspacing:D
2003 __kernel_primitive:NN \Umathrelrelspacing \utex_relrelspacing:D

2004	<code>__kernel_primitive:NN \Umathskewedfractionhgap</code>	
2005	<code>\utex_skewedfractionhgap:D</code>	
2006	<code>__kernel_primitive:NN \Umathskewedfractionvgap</code>	
2007	<code>\utex_skewedfractionvgap:D</code>	
2008	<code>__kernel_primitive:NN \Umathspaceafterscript</code>	<code>\utex_spaceafterscript:D</code>
2009	<code>__kernel_primitive:NN \Umathstackdenomdown</code>	<code>\utex_stackdenomdown:D</code>
2010	<code>__kernel_primitive:NN \Umathstacknumup</code>	<code>\utex_stacknumup:D</code>
2011	<code>__kernel_primitive:NN \Umathstackvgap</code>	<code>\utex_stackvgap:D</code>
2012	<code>__kernel_primitive:NN \Umathsubshiftdown</code>	<code>\utex_subshiftdown:D</code>
2013	<code>__kernel_primitive:NN \Umathsubshiftdrop</code>	<code>\utex_subshiftdrop:D</code>
2014	<code>__kernel_primitive:NN \Umathsubsupshiftdown</code>	<code>\utex_subsupshiftdown:D</code>
2015	<code>__kernel_primitive:NN \Umathsubsupvgap</code>	<code>\utex_subsupvgap:D</code>
2016	<code>__kernel_primitive:NN \Umathsubtopmax</code>	<code>\utex_subtopmax:D</code>
2017	<code>__kernel_primitive:NN \Umathsupbottommin</code>	<code>\utex_supbottommin:D</code>
2018	<code>__kernel_primitive:NN \Umathsupshiftdrop</code>	<code>\utex_supshiftdrop:D</code>
2019	<code>__kernel_primitive:NN \Umathsupshiftdown</code>	<code>\utex_supshiftdown:D</code>
2020	<code>__kernel_primitive:NN \Umathsupsubbottommax</code>	<code>\utex_supsubbottommax:D</code>
2021	<code>__kernel_primitive:NN \Umathunderbarkern</code>	<code>\utex_underbarkern:D</code>
2022	<code>__kernel_primitive:NN \Umathunderbarrule</code>	<code>\utex_underbarrule:D</code>
2023	<code>__kernel_primitive:NN \Umathunderbarvgap</code>	<code>\utex_underbarvgap:D</code>
2024	<code>__kernel_primitive:NN \Umathunderdelimiterbgap</code>	
2025	<code>\utex_underdelimiterbgap:D</code>	
2026	<code>__kernel_primitive:NN \Umathunderdelimitervgap</code>	
2027	<code>\utex_underdelimitervgap:D</code>	
2028	<code>__kernel_primitive:NN \Unosubscript</code>	<code>\utex_nosubscript:D</code>
2029	<code>__kernel_primitive:NN \Unosuperscript</code>	<code>\utex_nosuperscript:D</code>
2030	<code>__kernel_primitive:NN \Uoverdelimiter</code>	<code>\utex_overdelimiter:D</code>
2031	<code>__kernel_primitive:NN \Uradical</code>	<code>\utex_radical:D</code>
2032	<code>__kernel_primitive:NN \Uroot</code>	<code>\utex_root:D</code>
2033	<code>__kernel_primitive:NN \Uskewed</code>	<code>\utex_skewed:D</code>
2034	<code>__kernel_primitive:NN \Uskewedwithdelims</code>	<code>\utex_skewedwithdelims:D</code>
2035	<code>__kernel_primitive:NN \Ustack</code>	<code>\utex_stack:D</code>
2036	<code>__kernel_primitive:NN \Ustartdisplaymath</code>	<code>\utex_startdisplaymath:D</code>
2037	<code>__kernel_primitive:NN \Ustartmath</code>	<code>\utex_startmath:D</code>
2038	<code>__kernel_primitive:NN \Ustopdisplaymath</code>	<code>\utex_stopdisplaymath:D</code>
2039	<code>__kernel_primitive:NN \Ustopmath</code>	<code>\utex_stopmath:D</code>
2040	<code>__kernel_primitive:NN \Usubscript</code>	<code>\utex_subscript:D</code>
2041	<code>__kernel_primitive:NN \Usuperscript</code>	<code>\utex_superscript:D</code>
2042	<code>__kernel_primitive:NN \Uunderdelimiter</code>	<code>\utex_underdelimiter:D</code>
2043	<code>__kernel_primitive:NN \Uvextensible</code>	<code>\utex_vextensible:D</code>
2044	<code>__kernel_primitive:NN \autospaceing</code>	<code>\ptex_autospaceing:D</code>
2045	<code>__kernel_primitive:NN \autoxspaceing</code>	<code>\ptex_autoxspaceing:D</code>
2046	<code>__kernel_primitive:NN \dtou</code>	<code>\ptex_dtou:D</code>
2047	<code>__kernel_primitive:NN \epTeXinputencoding</code>	<code>\ptex_inputencoding:D</code>
2048	<code>__kernel_primitive:NN \epTeXversion</code>	<code>\ptex_epTeXversion:D</code>
2049	<code>__kernel_primitive:NN \euc</code>	<code>\ptex_euc:D</code>
2050	<code>__kernel_primitive:NN \ifdbbox</code>	<code>\ptex_ifdbbox:D</code>
2051	<code>__kernel_primitive:NN \ifddir</code>	<code>\ptex_ifddir:D</code>
2052	<code>__kernel_primitive:NN \ifmdir</code>	<code>\ptex_ifmdir:D</code>
2053	<code>__kernel_primitive:NN \iftbox</code>	<code>\ptex_iftbox:D</code>
2054	<code>__kernel_primitive:NN \iftdir</code>	<code>\ptex_iftdir:D</code>
2055	<code>__kernel_primitive:NN \ifybox</code>	<code>\ptex_ifybox:D</code>
2056	<code>__kernel_primitive:NN \ifydir</code>	<code>\ptex_ifydir:D</code>
2057	<code>__kernel_primitive:NN \inhibitglue</code>	<code>\ptex_inhibitglue:D</code>


```

2058 \__kernel_primitive:NN \inhibitxspcode \ptex_inhibitxspcode:D
2059 \__kernel_primitive:NN \jcharwidowpenalty \ptex_jcharwidowpenalty:D
2060 \__kernel_primitive:NN \jfam \ptex_jfam:D
2061 \__kernel_primitive:NN \jfont \ptex_jfont:D
2062 \__kernel_primitive:NN \jis \ptex_jis:D
2063 \__kernel_primitive:NN \kanjiskip \ptex_kanjiskip:D
2064 \__kernel_primitive:NN \kansuji \ptex_kansuji:D
2065 \__kernel_primitive:NN \kansujichar \ptex_kansujichar:D
2066 \__kernel_primitive:NN \kcatcode \ptex_kcatcode:D
2067 \__kernel_primitive:NN \kuten \ptex_kuten:D
2068 \__kernel_primitive:NN \noautospadding \ptex_noautospadding:D
2069 \__kernel_primitive:NN \noautoxspacing \ptex_noautoxspacing:D
2070 \__kernel_primitive:NN \postbreakpenalty \ptex_postbreakpenalty:D
2071 \__kernel_primitive:NN \prebreakpenalty \ptex_prebreakpenalty:D
2072 \__kernel_primitive:NN \ptexminorversion \ptex_ptexminorversion:D
2073 \__kernel_primitive:NN \ptexrevision \ptex_ptexrevision:D
2074 \__kernel_primitive:NN \ptexversion \ptex_ptexversion:D
2075 \__kernel_primitive:NN \showmode \ptex_showmode:D
2076 \__kernel_primitive:NN \sjis \ptex_sjis:D
2077 \__kernel_primitive:NN \tate \ptex_tate:D
2078 \__kernel_primitive:NN \tbaselineshift \ptex_tbaselineshift:D
2079 \__kernel_primitive:NN \tfont \ptex_tfont:D
2080 \__kernel_primitive:NN \xkanjiskip \ptex_xkanjiskip:D
2081 \__kernel_primitive:NN \xspcode \ptex_xspcode:D
2082 \__kernel_primitive:NN \ybaselineshift \ptex_ybaselineshift:D
2083 \__kernel_primitive:NN \yoko \ptex_yoko:D
2084 \__kernel_primitive:NN \disablecjktoken \uptex_disablecjktoken:D
2085 \__kernel_primitive:NN \enablecjktoken \uptex_enablecjktoken:D
2086 \__kernel_primitive:NN \forcecjktoken \uptex_forcecjktoken:D
2087 \__kernel_primitive:NN \kchar \uptex_kchar:D
2088 \__kernel_primitive:NN \kchardef \uptex_kchardef:D
2089 \__kernel_primitive:NN \kuten \uptex_kuten:D
2090 \__kernel_primitive:NN \ucs \uptex_ucs:D
2091 \__kernel_primitive:NN \uptexrevision \uptex_uptexrevision:D
2092 \__kernel_primitive:NN \uptexversion \uptex_uptexversion:D
2093 }
2094 }
2095 \__kernel_primitives:
2096 \tex_endgroup:D
2097 </package>
2098 </initex | package>

```

3 Internal kernel functions

```

\__kernel_chk_cs_exist:N
\__kernel_chk_cs_exist:c

```

```
\__kernel_chk_cs_exist:N <cs>
```

This function is only created if debugging is enabled. It checks that $\langle cs \rangle$ exists according to the criteria for $\backslash cs_if_exist_p:N$, and if not raises a kernel-level error.

```
\__kernel_chk_defined:NT
```

```
\__kernel_chk_defined:NT <variable> {<true code>}
```

If $\langle variable \rangle$ is not defined (according to $\backslash cs_if_exist:NTF$), this triggers an error, otherwise the $\langle true code \rangle$ is run.

<u><code>__kernel_chk_expr:nNnN</code></u>	<code>__kernel_chk_expr:nNnN {<expr>} {<eval>} {<convert>} {<caller>}</code>
	This function is only created if debugging is enabled. By default it is equivalent to <code>\use_i:nnnn</code> . When expression checking is enabled, it leaves in the input stream the result of <code>\tex_the:D {<eval>} {<expr>} \tex_relax:D</code> after checking that no token was left over. If any token was not taken as part of the expression, there is an error message displaying the result of the evaluation as well as the <code><caller></code> . For instance <code><eval></code> can be <code>__int_eval:w</code> and <code><caller></code> can be <code>\int_eval:n</code> or <code>\int_set:Nn</code> . The argument <code><convert></code> is empty except for mu expressions where it is <code>\tex_mutoglu:D</code> , used for internal purposes.
<u><code>__kernel_cs_parm_from_arg_count:nnF</code></u>	<code>__kernel_cs_parm_from_arg_count:nnF {<follow-on>} {<args>} {<false code>}</code>
	Evaluates the number of <code><args></code> and leaves the <code><follow-on></code> code followed by a brace group containing the required number of primitive parameter markers (<code>#1</code> , <i>etc.</i>). If the number of <code><args></code> is outside the range $[0, 9]$, the <code><false code></code> is inserted <i>instead</i> of the <code><follow-on></code> .
<u><code>__kernel_deprecation_code:nn</code></u>	<code>__kernel_deprecation_code:nn {<error code>} {<working code>}</code>
	Stores both an <code><error></code> and <code><working></code> definition for given material such that they can be exchanged by <code>\debug_on:</code> and <code>\debug_off:</code> .
<u><code>__kernel_exp_not:w *</code></u>	<code>__kernel_exp_not:w {<expandable tokens>} {<content>}</code>
	Carries out expansion on the <code><expandable tokens></code> before preventing further expansion of the <code><content></code> as for <code>\exp_not:n</code> . Typically, the <code><expandable tokens></code> will alter the nature of the <code><content></code> , <i>i.e.</i> allow it to be generated in some way.
<code>\l__kernel_expl_bool</code>	A boolean which records the current code syntax status: true if currently inside a code environment. This variable should only be set by <code>\ExplSyntaxOn/\ExplSyntaxOff</code> . (End definition for <code>\l__kernel_expl_bool</code> .)
<u><code>__kernel_file_missing:n</code></u>	<code>__kernel_file_missing:n {<name>}</code>
	Expands the <code><name></code> as per <code>__kernel_file_name_sanitize:nN</code> then produces an error message indicating that this file was not found.
<u><code>__kernel_file_name_sanitize:nN</code></u>	<code>__kernel_file_name_sanitize:nN {<name>} {<str var>}</code>
	For converting a <code><name></code> to a string where active characters are treated as strings.
<u><code>__kernel_file_input_push:n</code></u>	<code>__kernel_file_input_push:n {<name>}</code>
<u><code>__kernel_file_input_pop:</code></u>	<code>__kernel_file_input_pop:</code>
	Used to push and pop data from the internal file stack: needed only in package mode, where interfacing with the L ^A T _E X 2 _ε kernel is necessary.
<u><code>__kernel_int_add:nnn *</code></u>	<code>__kernel_int_add:nnn {<integer₁>} {<integer₂>} {<integer₃>}</code>
	Expands to the result of adding the three <code><integers></code> (which must be suitable input for <code>\int_eval:w</code>), avoiding intermediate overflow. Overflow occurs only if the overall result is outside $[-2^{31}+1, 2^{31}-1]$. The <code><integers></code> may be of the form <code>\int_eval:w ... \scan_stop:</code> but may be evaluated more than once.

<code>_kernel_ior_open:Nn</code>	<code>_kernel_ior_open:Nn <stream> {\<file name>}</code>
<code>_kernel_ior_open:No</code>	

This function has identical syntax to the public version. However, it does not take precautions against active characters in the $\langle file\ name \rangle$, and it does not attempt to add a $\langle path \rangle$ to the $\langle file\ name \rangle$: it is therefore intended to be used by higher-level functions which have already fully expanded the $\langle file\ name \rangle$ and which need to perform multiple open or close operations. See for example the implementation of `\file_get_full_name:nN`,

<code>_kernel_iow_with:Nnn</code>	<code>_kernel_iow_with:Nnn <integer> {\<value>} {\<code>}</code>
------------------------------------	---

If the $\langle integer \rangle$ is equal to the $\langle value \rangle$ then this function simply runs the $\langle code \rangle$. Otherwise it saves the current value of the $\langle integer \rangle$, sets it to the $\langle value \rangle$, runs the $\langle code \rangle$, and restores the $\langle integer \rangle$ to its former value. This is used to ensure that the `\newlinechar` is 10 when writing to a stream, which lets `\iow_newline:` work, and that `\errorcontextlines` is -1 when displaying a message.

<code>_kernel_msg_new:nnnn</code>	<code>_kernel_msg_new:nnnn {\<module>} {\<message>} {\<text>} {\<more text>}</code>
<code>_kernel_msg_new:nnn</code>	

Creates a kernel $\langle message \rangle$ for a given $\langle module \rangle$. The message is defined to first give $\langle text \rangle$ and then $\langle more\ text \rangle$ if the user requests it. If no $\langle more\ text \rangle$ is available then a standard text is given instead. Within $\langle text \rangle$ and $\langle more\ text \rangle$ four parameters ($\#1$ to $\#4$) can be used: these will be supplied and expanded at the time the message is used. An error is raised if the $\langle message \rangle$ already exists.

<code>_kernel_msg_set:nnnn</code>	<code>_kernel_msg_set:nnnn {\<module>} {\<message>} {\<text>} {\<more text>}</code>
<code>_kernel_msg_set:nnn</code>	

Sets up the text for a kernel $\langle message \rangle$ for a given $\langle module \rangle$. The message is defined to first give $\langle text \rangle$ and then $\langle more\ text \rangle$ if the user requests it. If no $\langle more\ text \rangle$ is available then a standard text is given instead. Within $\langle text \rangle$ and $\langle more\ text \rangle$ four parameters ($\#1$ to $\#4$) can be used: these will be supplied and expanded at the time the message is used.

<code>_kernel_msg_fatal:nnnnnn</code>	<code>_kernel_msg_fatal:nnnnnn {\<module>} {\<message>} {\<arg one>} {\<arg two>} {\<arg three>} {\<arg four>}</code>
<code>_kernel_msg_fatal:nnxxxx</code>	
<code>_kernel_msg_fatal:nnnnnn</code>	
<code>_kernel_msg_fatal:nnxxx</code>	
<code>_kernel_msg_fatal:nnnn</code>	
<code>_kernel_msg_fatal:nnxx</code>	
<code>_kernel_msg_fatal:nnn</code>	
<code>_kernel_msg_fatal:nnx</code>	
<code>_kernel_msg_fatal:nn</code>	

Issues kernel $\langle module \rangle$ error $\langle message \rangle$, passing $\langle arg\ one \rangle$ to $\langle arg\ four \rangle$ to the text-creating functions. After issuing a fatal error the T_EX run halts. Cannot be redirected.

<code>_kernel_msg_error:nnnnnn</code>	<code>_kernel_msg_error:nnnnnn {\<module>} {\<message>} {\<arg one>} {\<arg two>} {\<arg three>} {\<arg four>}</code>
<code>_kernel_msg_error:nnxxxx</code>	
<code>_kernel_msg_error:nnnnnn</code>	
<code>_kernel_msg_error:nnxxx</code>	
<code>_kernel_msg_error:nnxx</code>	
<code>_kernel_msg_error:nnn</code>	
<code>_kernel_msg_error:nnx</code>	
<code>_kernel_msg_error:nn</code>	

Issues kernel $\langle module \rangle$ error $\langle message \rangle$, passing $\langle arg\ one \rangle$ to $\langle arg\ four \rangle$ to the text-creating functions. The error stops processing and issues the text at the terminal. After user input, the run continues. Cannot be redirected.

```

\__kernel_msg_warning:nnnnnn \__kernel_msg_warning:nnnnnn {\module} {\message} {\arg one} {\arg
\__kernel_msg_warning:nnxxxx two} {\arg three} {\arg four}
\__kernel_msg_warning:nnnnn
\__kernel_msg_warning:nnxxx
\__kernel_msg_warning:nnnn
\__kernel_msg_warning:nnxx
\__kernel_msg_warning:nnn
\__kernel_msg_warning:nnx
\__kernel_msg_warning:nn

```

Issues kernel $\langle module \rangle$ warning $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The warning text is added to the log file, but the \TeX run is not interrupted.

```

\__kernel_msg_info:nnnnnn \__kernel_msg_info:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
\__kernel_msg_info:nnxxxx three} {\arg four}
\__kernel_msg_info:nnnnn
\__kernel_msg_info:nnxxx
\__kernel_msg_info:nnnn
\__kernel_msg_info:nnxx
\__kernel_msg_info:nnn
\__kernel_msg_info:nnx
\__kernel_msg_info:nn

```

Issues kernel $\langle module \rangle$ information $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The information text is added to the log file.

```

\__kernel_msg_expandable_error:nnnnnn * \__kernel_msg_expandable_error:nnnnnn {\module} {\message}
\__kernel_msg_expandable_error:nnffff * {\arg one} {\arg two} {\arg three} {\arg four}
\__kernel_msg_expandable_error:nnnnn *
\__kernel_msg_expandable_error:nnfff *
\__kernel_msg_expandable_error:nnnn *
\__kernel_msg_expandable_error:nnff *
\__kernel_msg_expandable_error:nnn *
\__kernel_msg_expandable_error:nnf *
\__kernel_msg_expandable_error:nn *

```

Issues an error, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The resulting string must be much shorter than a line, otherwise it is cropped.

$\backslash g_kernel_prg_map_int$ This integer is used by non-expandable mapping functions to track the level of nesting in force. The functions $\backslash \langle type \rangle_map_1:w$, $\backslash \langle type \rangle_map_2:w$, *etc.*, labelled by $\backslash g_kernel_prg_map_int$ hold functions to be mapped over various list datatypes in inline and variable mappings.

(End definition for $\backslash g_kernel_prg_map_int$.)

`__kernel_quark_new_test:N`

`__kernel_quark_new_test:N \<name>:<arg spec>`

Defines a quark-test function `\<name>:<arg spec>` which tests if its argument is `\q__<namespace>_recursion_tail`, then acts accordingly, as described below for each possible `<arg spec>`.

The `<namespace>` is determined as the first (nonempty) `_`-delimited word in `<name>` and is used internally in the definition of auxiliaries. The function `__kernel_quark_new_test:N` does *not* define the `\q__<namespace>_recursion_tail` and `\q__<namespace>_recursion_stop` quarks. They should be manually defined with `\quark_new:N`.

There are 6 different types of quark-test functions. Which one is defined depends on the `<arg spec>`, which *must* be one of the options listed now. Four of them are modeled after `\quark_if_recursion_tail:(N|n)` and `\quark_if_recursion_tail_do:(N|n)n`.

`n` defines `\<name>:n` such that it checks if #1 contains only `\q__<namespace>_recursion_tail`, and if so consumes all tokens up to `\q__<namespace>_recursion_stop` (c.f. `\quark_if_recursion_tail_stop:n`).

`nn` defines `\<name>:nn` such that it checks if #1 contains only `\q__<namespace>_recursion_tail`, and if so consumes all tokens up to `\q__<namespace>_recursion_stop`, then executes the code #2 after that (c.f. `\quark_if_recursion_tail_stop_do:nn`).

`N` defines `\<name>:N` such that it checks if #1 is `\q__<namespace>_recursion_tail`, and if so consumes all tokens up to `\q__<namespace>_recursion_stop` (c.f. `\quark_if_recursion_tail_stop:N`).

`Nn` defines `\<name>:Nn` such that it checks if #1 is `\q__<namespace>_recursion_tail`, and if so consumes all tokens up to `\q__<namespace>_recursion_stop`, then executes the code #2 after that (c.f. `\quark_if_recursion_tail_stop_do:Nn`).

The last two are modeled after `\quark_if_recursion_tail_break:(n|N)N`, and in those cases the quark `\q__<namespace>_recursion_stop` is not used (and thus needs not be defined).

`nN` defines `\<name>:nN` such that it checks if #1 contains only `\q__<namespace>_recursion_tail`, and if so uses the `\<type>_map_break:` function #2.

`NN` defines `\<name>:NN` such that it checks if #1 is `\q__<namespace>_recursion_tail`, and if so uses the `\<type>_map_break:` function #2.

Any other signature, as well as a function without signature are errors, and in such case the definition is aborted.

<u><code>__kernel_quark_new_conditional:Nn</code></u>	<code>__kernel_quark_new_conditional:Nn</code> <code>__<namespace>_quark_if_<name>:<arg spec> {<conditions>}</code>
--	--

Defines a collection of quark conditionals that test if their argument is the quark `\q_`
`__<namespace>_<name>` and perform suitable actions. The `<conditions>` are a comma-separated list of one or more of p, T, F, and TF, and one conditional is defined for each `<condition>` in the list, as described for `\prg_new_conditional:Npnn`. The conditionals are defined using `\prg_new_conditional:Npnn`, so that their name is obtained by adding p, T, F, or TF to the base name `__<namespace>_quark_if_<name>:<arg spec>`.

The first argument of `__kernel_quark_new_conditional:Nn` must contain `_quark_if_` and `:`, as these markers are used to determine the `<name>` of the quark `\q_`
`__<namespace>_<name>` to be tested. This quark should be manually defined with `\quark_new:N`, as `__kernel_quark_new_conditional:Nn` does *not* define it.

The function `__kernel_quark_new_conditional:Nn` can define 2 different types of quark conditionals. Which one is defined depends on the `<arg spec>`, which *must* be one of the following options, modeled after `\quark_if_nil:(N|n)(TF)`.

`n` defines `__<namespace>_quark_if_<name>:n(TF)` such that it checks if #1 contains only `\q_`
`__<namespace>_<name>`, and executes the proper conditional branch.

`N` defines `__<namespace>_quark_if_<name>:N(TF)` such that it checks if #1 is `\q_`
`__<namespace>_<name>`, and executes the proper conditional branch.

Any other signature, as well as a function without signature are errors, and in such case the definition is aborted.

`\c__kernel_randint_max_int` Maximal allowed argument to `__kernel_randint:n`. Equal to $2^{17} - 1$.

(End definition for `\c__kernel_randint_max_int`.)

<u><code>__kernel_randint:n</code></u>	<code>__kernel_randint:n {<max>}</code>
---	--

Used in an integer expression this gives a pseudo-random number between 1 and `<max>` included. One must have $\langle max \rangle \leq 2^{17} - 1$. The `<max>` must be suitable for `\int_value:w` (and any `\int_eval:w` must be terminated by `\scan_stop:` or equivalent).

<u><code>__kernel_randint:nn</code></u>	<code>__kernel_randint:nn {<min>} {<max>}</code>
--	---

Used in an integer expression this gives a pseudo-random number between `<min>` and `<max>` included. The `<min>` and `<max>` must be suitable for `\int_value:w` (and any `\int_eval:w` must be terminated by `\scan_stop:` or equivalent). For small ranges $R = \langle max \rangle - \langle min \rangle + 1 \leq 2^{17} - 1$, `<min> - 1 + __kernel_randint:n{R}` is faster.

<u><code>__kernel_register_show:N</code></u> <u><code>__kernel_register_show:c</code></u>	<code>__kernel_register_show:N <register></code>
--	---

Used to show the contents of a T_EX register at the terminal, formatted such that internal parts of the mechanism are not visible.

<u><code>__kernel_register_log:N</code></u> <u><code>__kernel_register_log:c</code></u>	<code>__kernel_register_log:N <register></code>
--	--

Used to write the contents of a T_EX register to the log file in a form similar to `__kernel_register_show:N`.

<code>_kernel_str_to_other:n</code> ★	<code>_kernel_str_to_other:n</code> { <i>⟨token list⟩</i> }
--	--

Converts the *⟨token list⟩* to a *⟨other string⟩*, where spaces have category code “other”. This function can be f-expanded without fear of losing a leading space, since spaces do not have category code 10 in its result. It takes a time quadratic in the character count of the string.

<code>_kernel_str_to_other_fast:n</code> ☆	<code>_kernel_str_to_other_fast:n</code> { <i>⟨token list⟩</i> }
---	---

Same behaviour `_kernel_str_to_other:n` but only restricted-expandable. It takes a time linear in the character count of the string.

<code>_kernel_tl_to_str:w</code> ★	<code>_kernel_tl_to_str:w</code> <i>⟨expandable tokens⟩</i> { <i>⟨tokens⟩</i> }
-------------------------------------	--

Carries out expansion on the *⟨expandable tokens⟩* before conversion of the *⟨tokens⟩* to a string as describe for `\tl_to_str:n`. Typically, the *⟨expandable tokens⟩* will alter the nature of the *⟨tokens⟩*, *i.e.* allow it to be generated in some way. This function requires only a single expansion.

4 Kernel backend functions

These functions are required to pass information to the backend. The nature of these means that they are defined only when the relevant backend is in use.

<code>_kernel_backend_literal:n</code>	<code>_kernel_backend_literal:n</code> { <i>⟨content⟩</i> }
<code>_kernel_backend_literal:(e x)</code>	

Adds the *⟨content⟩* literally to the current vertical list as a whatsit. The nature of the *⟨content⟩* will depend on the backend in use.

<code>_kernel_backend_literal_postscript:n</code>	<code>_kernel_backend_literal_postscript:n</code> { <i>⟨PostScript⟩</i> }
<code>_kernel_backend_literal_postscript:x</code>	

Adds the *⟨PostScript⟩* literally to the current vertical list as a whatsit. No positioning is applied.

<code>_kernel_backend_literal_pdf:n</code>	<code>_kernel_backend_literal_pdf:n</code> { <i>⟨PDF instructions⟩</i> }
<code>_kernel_backend_literal_pdf:x</code>	

Adds the *⟨PDF instructions⟩* literally to the current vertical list as a whatsit. No positioning is applied.

<code>_kernel_backend_literal_svg:n</code>	<code>_kernel_backend_literal_svg:n</code> { <i>⟨SVG instructions⟩</i> }
<code>_kernel_backend_literal_svg:x</code>	

Adds the *⟨SVG instructions⟩* literally to the current vertical list as a whatsit. No positioning is applied.

<code>_kernel_backend_postscript:n</code>	<code>_kernel_backend_postscript:n</code> { <i>⟨PostScript⟩</i> }
<code>_kernel_backend_postscript:x</code>	

Adds the *⟨PostScript⟩* to the current vertical list as a whatsit. The PostScript reference point is adjusted to match the current position. The PostScript is inserted inside a `SDict begin/end` pair.

<code>_kernel_backend_align_begin:</code>	<code>_kernel_backend_align_begin:</code>
<code>_kernel_backend_align_end:</code>	<code>_kernel_backend_align_end:</code>

Arranges to align the PostScript and DVI current positions and scales.

<code>_kernel_backend_scope_begin:</code>	<code>_kernel_backend_scope_begin:</code>
<code>_kernel_backend_scope_end:</code>	<code>_kernel_backend_scope_end:</code>

Creates a scope for instructions at the backend level.

<code>_kernel_backend_matrix:n</code>	<code>_kernel_backend_matrix:n {<matrix>}</code>
<code>_kernel_backend_matrix:x</code>	Applies the <code><matrix></code> to the current transformation matrix.

`\g_kernel_backend_header_bool`

Specifies whether to write headers for the backend.

<code>\l_kernel_color_stack_int</code>	The color stack used in pdfTeX and LuaTeX for the main color.
--	---

5 l3basics implementation

2099 `<*initex | package>`

5.1 Renaming some TeX primitives (again)

Having given all the TeX primitives a consistent name, we need to give sensible names to the ones we actually want to use. These will be defined as needed in the appropriate modules, but we do a few now, just to get started.⁷

<code>\if_true:</code>	Then some conditionals.
<code>\if_false:</code>	2100 <code>\tex_let:D \if_true:</code> <code>\tex_iftrue:D</code>
<code>\or:</code>	2101 <code>\tex_let:D \if_false:</code> <code>\tex_iffalse:D</code>
<code>\else:</code>	2102 <code>\tex_let:D \or:</code> <code>\tex_or:D</code>
<code>\fi:</code>	2103 <code>\tex_let:D \else:</code> <code>\tex_else:D</code>
<code>\reverse_if:N</code>	2104 <code>\tex_let:D \fi:</code> <code>\tex_fi:D</code>
<code>\if:w</code>	2105 <code>\tex_let:D \reverse_if:N</code> <code>\tex_unless:D</code>
<code>\if_charcode:w</code>	2106 <code>\tex_let:D \if:w</code> <code>\tex_if:D</code>
<code>\if_catcode:w</code>	2107 <code>\tex_let:D \if_charcode:w</code> <code>\tex_if:D</code>
<code>\if_meaning:w</code>	2108 <code>\tex_let:D \if_catcode:w</code> <code>\tex_ifcat:D</code>
	2109 <code>\tex_let:D \if_meaning:w</code> <code>\tex_ifx:D</code>
	2110 <code>\tex_let:D \if_bool:N</code> <code>\tex_ifodd:D</code>

(End definition for `\if_true:` and others. These functions are documented on page 23.)

<code>\if_mode_math:</code>	TeX lets us detect some if its modes.
<code>\if_mode_horizontal:</code>	2111 <code>\tex_let:D \if_mode_math:</code> <code>\tex_ifmmode:D</code>
<code>\if_mode_vertical:</code>	2112 <code>\tex_let:D \if_mode_horizontal:</code> <code>\tex_ifhmode:D</code>
<code>\if_mode_inner:</code>	2113 <code>\tex_let:D \if_mode_vertical:</code> <code>\tex_ifvmode:D</code>
	2114 <code>\tex_let:D \if_mode_inner:</code> <code>\tex_ifinner:D</code>

⁷This renaming gets expensive in terms of csname usage, an alternative scheme would be to just use the `\tex_...:D` name in the cases where no good alternative exists.

(End definition for `\if_mode_math:` and others. These functions are documented on page 23.)

`\if_cs_exist:N` Building csnames and testing if control sequences exist.
`\if_cs_exist:w` 2115 `\tex_let:D \if_cs_exist:N \tex_ifdefined:D`
`\cs:w` 2116 `\tex_let:D \if_cs_exist:w \tex_ifcsname:D`
`\cs_end:n` 2117 `\tex_let:D \cs:w \tex_csname:D`
2118 `\tex_let:D \cs_end: \tex_endcsname:D`

(End definition for `\if_cs_exist:N` and others. These functions are documented on page 23.)

`\exp_after:wN` The five `\exp_` functions are used in the `l3expan` module where they are described.
`\exp_not:N` 2119 `\tex_let:D \exp_after:wN \tex_expandafter:D`
`\exp_not:n` 2120 `\tex_let:D \exp_not:N \tex_noexpand:D`
2121 `\tex_let:D \exp_not:n \tex_unexpanded:D`
2122 `\tex_let:D \exp:w \tex_romannumeral:D`
2123 `\tex_chardef:D \exp_end: = 0 ~`

(End definition for `\exp_after:wN`, `\exp_not:N`, and `\exp_not:n`. These functions are documented on page 33.)

`\token_to_meaning:N` Examining a control sequence or token.
`\cs_meaning:N` 2124 `\tex_let:D \token_to_meaning:N \tex_meaning:D`
2125 `\tex_let:D \cs_meaning:N \tex_meaning:D`

(End definition for `\token_to_meaning:N` and `\cs_meaning:N`. These functions are documented on page 133.)

`\tl_to_str:n` Making strings.
`\token_to_str:N` 2126 `\tex_let:D \tl_to_str:n \tex_detokenize:D`
`__kernel_tl_to_str:w` 2127 `\tex_let:D \token_to_str:N \tex_string:D`
2128 `\tex_let:D __kernel_tl_to_str:w \tex_detokenize:D`

(End definition for `\tl_to_str:n`, `\token_to_str:N`, and `__kernel_tl_to_str:w`. These functions are documented on page 51.)

`\scan_stop:` The next three are basic functions for which there also exist versions that are safe inside
`\group_begin:` alignments. These safe versions are defined in the `l3prg` module.
`\group_end:` 2129 `\tex_let:D \scan_stop: \tex_relax:D`
2130 `\tex_let:D \group_begin: \tex_begingroup:D`
2131 `\tex_let:D \group_end: \tex_endgroup:D`

(End definition for `\scan_stop:`, `\group_begin:`, and `\group_end:`. These functions are documented on page 9.)

2132 `<@@=int>`

`\if_int_compare:w` For integers.
`__int_to_roman:w` 2133 `\tex_let:D \if_int_compare:w \tex_ifnum:D`
2134 `\tex_let:D __int_to_roman:w \tex_romannumeral:D`

(End definition for `\if_int_compare:w` and `__int_to_roman:w`. This function is documented on page 100.)

`\group_insert_after:N` Adding material after the end of a group.
2135 `\tex_let:D \group_insert_after:N \tex_aftergroup:D`

(End definition for `\group_insert_after:N`. This function is documented on page 9.)

`\exp_args:Nc` Discussed in `l3expan`, but needed much earlier.

```
\exp_args:cc 2136 \tex_long:D \tex_def:D \exp_args:Nc #1#2
                { \exp_after:wN #1 \cs:w #2 \cs_end: }
2137
2138 \tex_long:D \tex_def:D \exp_args:cc #1#2
2139 { \cs:w #1 \exp_after:wN \cs_end: \cs:w #2 \cs_end: }
```

(End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 29.)

`\token_to_meaning:c` A small number of variants defined by hand. Some of the necessary functions (`\use_i:nn`, `\use_ii:nn`, and `\exp_args:Nnc`) are not defined at that point yet, but will be defined before those variants are used. The `\cs_meaning:c` command must check for an undefined control sequence to avoid defining it mistakenly.

```
2140 \tex_def:D \token_to_str:c { \exp_args:Nc \token_to_str:N }
2141 \tex_long:D \tex_def:D \cs_meaning:c #1
2142 {
2143   \if_cs_exist:w #1 \cs_end:
2144     \exp_after:wN \use_i:nn
2145   \else:
2146     \exp_after:wN \use_ii:nn
2147   \fi:
2148   { \exp_args:Nc \cs_meaning:N {#1} }
2149   { \tl_to_str:n {undefined} }
2150 }
2151 \tex_let:D \token_to_meaning:c = \cs_meaning:c
```

(End definition for `\token_to_meaning:N`. This function is documented on page 133.)

5.2 Defining some constants

`\c_zero_int` We need the constant `\c_zero_int` which is used by some functions in the `l3alloc` module. The rest are defined in the `l3int` module – at least for the ones that can be defined with `\tex_chardef:D` or `\tex_mathchardef:D`. For other constants the `l3int` module is required but it can't be used until the allocation has been set up properly!

```
2152 \tex_chardef:D \c_zero_int = 0 ~
```

(End definition for `\c_zero_int`. This variable is documented on page 99.)

`\c_max_register_int` This is here as this particular integer is needed both in package mode and to bootstrap `l3alloc`, and is documented in `l3int`. LuaTeX and those which contain parts of the Omega extensions have more registers available than ε -TeX.

```
2153 \tex_ifdefined:D \tex_luatexversion:D
2154 \tex_chardef:D \c_max_register_int = 65 535 ~
2155 \tex_else:D
2156 \tex_ifdefined:D \tex_omathchardef:D
2157 \tex_omathchardef:D \c_max_register_int = 65535 ~
2158 \tex_else:D
2159 \tex_mathchardef:D \c_max_register_int = 32767 ~
2160 \tex_fi:D
2161 \tex_fi:D
```

(End definition for `\c_max_register_int`. This variable is documented on page 99.)

5.3 Defining functions

We start by providing functions for the typical definition functions. First the local ones.

```
\cs_set_nopar:Npn All assignment functions in LATEX3 should be naturally protected; after all, the TEX
\cs_set_nopar:Npx primitives for assignments are and it can be a cause of problems if others aren't.
\cs_set:Npn
\cs_set:Npx
\cs_set_protected_nopar:Npn
\cs_set_protected_nopar:Npx
\cs_set_protected:Npn
\cs_set_protected:Npx
2162 \tex_let:D \cs_set_nopar:Npn \tex_def:D
2163 \tex_let:D \cs_set_nopar:Npx \tex_edef:D
2164 \tex_protected:D \tex_long:D \tex_def:D \cs_set:Npn
2165 { \tex_long:D \tex_def:D }
2166 \tex_protected:D \tex_long:D \tex_def:D \cs_set:Npx
2167 { \tex_long:D \tex_edef:D }
2168 \tex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npn
2169 { \tex_protected:D \tex_def:D }
2170 \tex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npx
2171 { \tex_protected:D \tex_edef:D }
2172 \tex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npn
2173 { \tex_protected:D \tex_long:D \tex_def:D }
2174 \tex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npx
2175 { \tex_protected:D \tex_long:D \tex_edef:D }
```

(End definition for `\cs_set_nopar:Npn` and others. These functions are documented on page 11.)

```
\cs_gset_nopar:Npn Global versions of the above functions.
\cs_gset_nopar:Npx
\cs_gset:Npn
\cs_gset:Npx
\cs_gset_protected_nopar:Npn
\cs_gset_protected_nopar:Npx
\cs_gset_protected:Npn
\cs_gset_protected:Npx
2176 \tex_let:D \cs_gset_nopar:Npn \tex_gdef:D
2177 \tex_let:D \cs_gset_nopar:Npx \tex_xdef:D
2178 \cs_set_protected:Npn \cs_gset:Npn
2179 { \tex_long:D \tex_gdef:D }
2180 \cs_set_protected:Npn \cs_gset:Npx
2181 { \tex_long:D \tex_xdef:D }
2182 \cs_set_protected:Npn \cs_gset_protected_nopar:Npn
2183 { \tex_protected:D \tex_gdef:D }
2184 \cs_set_protected:Npn \cs_gset_protected_nopar:Npx
2185 { \tex_protected:D \tex_xdef:D }
2186 \cs_set_protected:Npn \cs_gset_protected:Npn
2187 { \tex_protected:D \tex_long:D \tex_gdef:D }
2188 \cs_set_protected:Npn \cs_gset_protected:Npx
2189 { \tex_protected:D \tex_long:D \tex_xdef:D }
```

(End definition for `\cs_gset_nopar:Npn` and others. These functions are documented on page 12.)

5.4 Selecting tokens

```
2190 <@@=exp>
\l__exp_internal_tl Scratch token list variable for l3expan, used by \use:x, used in defining conditionals. We
don't use tl methods because l3basics is loaded earlier.
```

```
2191 \cs_set_nopar:Npn \l__exp_internal_tl { }
```

(End definition for `\l__exp_internal_tl`.)

\use:c This macro grabs its argument and returns a csname from it.

```
2192 \cs_set:Npn \use:c #1 { \cs:w #1 \cs_end: }
```

(End definition for `\use:c`. This function is documented on page 16.)

\use:x Fully expands its argument and passes it to the input stream. Uses the reserved `\l__exp_internal_tl` which we’ve set up above.

```
2193 \cs_set_protected:Npn \use:x #1
2194 {
2195   \cs_set_nopar:Npx \l__exp_internal_tl {#1}
2196   \l__exp_internal_tl
2197 }
```

(End definition for `\use:x`. This function is documented on page 20.)

```
2198 <@@=use>
```

\use:e In non-LuaTeX engines older than 2019, `\expanded` is emulated.

```
2199 \cs_set:Npn \use:e #1 { \tex_expanded:D {#1} }
2200 \tex_ifdefined:D \tex_expanded:D \tex_else:D
2201   \cs_set:Npn \use:e #1 { \exp_args:Ne \use:n {#1} }
2202 \tex_fi:D
```

(End definition for `\use:e`. This function is documented on page 20.)

```
2203 <@@=exp>
```

\use:n These macros grab their arguments and return them back to the input (with outer braces removed).

```
\use:nnn 2204 \cs_set:Npn \use:n #1 {#1}
\use:nnnn 2205 \cs_set:Npn \use:nn #1#2 {#1#2}
2206 \cs_set:Npn \use:nnn #1#2#3 {#1#2#3}
2207 \cs_set:Npn \use:nnnn #1#2#3#4 {#1#2#3#4}
```

(End definition for `\use:n` and others. These functions are documented on page 19.)

\use_i:nn The equivalent to L^AT_EX 2_ε’s `\@firstoftwo` and `\@secondoftwo`.

```
\use_ii:nn 2208 \cs_set:Npn \use_i:nn #1#2 {#1}
2209 \cs_set:Npn \use_ii:nn #1#2 {#2}
```

(End definition for `\use_i:nn` and `\use_ii:nn`. These functions are documented on page 19.)

\use_i:nnn We also need something for picking up arguments from a longer list.

```
\use_ii:nnn 2210 \cs_set:Npn \use_i:nnn #1#2#3 {#1}
\use_iii:nnn 2211 \cs_set:Npn \use_ii:nnn #1#2#3 {#2}
\use_i_ii:nnn 2212 \cs_set:Npn \use_iii:nnn #1#2#3 {#3}
\use_i:nnnn 2213 \cs_set:Npn \use_i_ii:nnn #1#2#3 {#1#2}
\use_ii:nnnn 2214 \cs_set:Npn \use_i:nnnn #1#2#3#4 {#1}
\use_iii:nnnn 2215 \cs_set:Npn \use_ii:nnnn #1#2#3#4 {#2}
\use_iv:nnnn 2216 \cs_set:Npn \use_iii:nnnn #1#2#3#4 {#3}
2217 \cs_set:Npn \use_iv:nnnn #1#2#3#4 {#4}
```

(End definition for `\use_i:nnn` and others. These functions are documented on page 19.)

\use_ii_i:nn

```
2218 \cs_set:Npn \use_ii_i:nn #1#2 { #2 #1 }
```

(End definition for `\use_ii_i:nn`. This function is documented on page 20.)

`\use_none_delimit_by_q_nil:w` Functions that gobble everything until they see either `\q_nil`, `\q_stop`, or `\q_recursion_stop`, respectively.

```

\use_none_delimit_by_q_stop:w
\use_none_delimit_by_q_recursion_stop:w
2219 \cs_set:Npn \use_none_delimit_by_q_nil:w #1 \q_nil { }
2220 \cs_set:Npn \use_none_delimit_by_q_stop:w #1 \q_stop { }
2221 \cs_set:Npn \use_none_delimit_by_q_recursion_stop:w #1 \q_recursion_stop { }

```

(End definition for `\use_none_delimit_by_q_nil:w`, `\use_none_delimit_by_q_stop:w`, and `\use_none_delimit_by_q_recursion_stop:w`. These functions are documented on page 21.)

`\use_i_delimit_by_q_nil:nw` Same as above but execute first argument after gobbling. Very useful when you need to skip the rest of a mapping sequence but want an easy way to control what should be expanded next.

```

\use_i_delimit_by_q_stop:nw
\use_i_delimit_by_q_recursion_stop:nw
2222 \cs_set:Npn \use_i_delimit_by_q_nil:nw #1#2 \q_nil {#1}
2223 \cs_set:Npn \use_i_delimit_by_q_stop:nw #1#2 \q_stop {#1}
2224 \cs_set:Npn \use_i_delimit_by_q_recursion_stop:nw
2225 #1#2 \q_recursion_stop {#1}

```

(End definition for `\use_i_delimit_by_q_nil:nw`, `\use_i_delimit_by_q_stop:nw`, and `\use_i_delimit_by_q_recursion_stop:nw`. These functions are documented on page 21.)

5.5 Gobbling tokens from input

`\use_none:n` To gobble tokens from the input we use a standard naming convention: the number of tokens gobbled is given by the number of n's following the : in the name. Although we could define functions to remove ten arguments or more using separate calls of `\use_none:nnnnn`, this is very non-intuitive to the programmer who will assume that expanding such a function once takes care of gobbling all the tokens in one go.

```

\use_none:nn
\use_none:nnn
\use_none:nnnn
\use_none:nnnnn
\use_none:nnnnnn
\use_none:nnnnnnn
\use_none:nnnnnnnn
2226 \cs_set:Npn \use_none:n #1 { }
2227 \cs_set:Npn \use_none:nn #1#2 { }
2228 \cs_set:Npn \use_none:nnn #1#2#3 { }
2229 \cs_set:Npn \use_none:nnnn #1#2#3#4 { }
2230 \cs_set:Npn \use_none:nnnnn #1#2#3#4#5 { }
2231 \cs_set:Npn \use_none:nnnnnn #1#2#3#4#5#6 { }
2232 \cs_set:Npn \use_none:nnnnnnn #1#2#3#4#5#6#7 { }
2233 \cs_set:Npn \use_none:nnnnnnnn #1#2#3#4#5#6#7#8 { }
2234 \cs_set:Npn \use_none:nnnnnnnnn #1#2#3#4#5#6#7#8#9 { }

```

(End definition for `\use_none:n` and others. These functions are documented on page 20.)

5.6 Debugging and patching later definitions

`_kernel_if_debug:TF` A more meaningful test of whether debugging is enabled than messing up with guards. We can also more easily change the logic in one place then. This is needed primarily for deprecations.

```

2235 <@@=debug>
2236 \cs_set_protected:Npn \_kernel_if_debug:TF #1#2 {#2}

```

(End definition for `_kernel_if_debug:TF`.)

`\debug_on:n` Stubs.

```
\debug_off:n 2237 \cs_set_protected:Npn \debug_on:n #1
2238 {
2239   \__kernel_msg_error:nnx { kernel } { enable-debug }
2240   { \tl_to_str:n { \debug_on:n {#1} } }
2241 }
2242 \cs_set_protected:Npn \debug_off:n #1
2243 {
2244   \__kernel_msg_error:nnx { kernel } { enable-debug }
2245   { \tl_to_str:n { \debug_off:n {#1} } }
2246 }
```

(End definition for `\debug_on:n` and `\debug_off:n`. These functions are documented on page 24.)

`\debug_suspend:`

`\debug_resume:`

```
2247 \cs_set_protected:Npn \debug_suspend: { }
2248 \cs_set_protected:Npn \debug_resume: { }
```

(End definition for `\debug_suspend:` and `\debug_resume:`. These functions are documented on page 24.)

`__kernel_deprecation_code:nn`

`\g__debug_deprecation_on_tl`

`\g__debug_deprecation_off_tl`

Some commands were more recently deprecated and not yet removed; only make these into errors if the user requests it. This relies on two token lists, filled up in `l3deprecation`.

```
2249 \cs_set_nopar:Npn \g__debug_deprecation_on_tl { }
2250 \cs_set_nopar:Npn \g__debug_deprecation_off_tl { }
2251 \cs_set_protected:Npn \__kernel_deprecation_code:nn #1#2
2252 {
2253   \tl_gput_right:Nn \g__debug_deprecation_on_tl {#1}
2254   \tl_gput_right:Nn \g__debug_deprecation_off_tl {#2}
2255 }
```

(End definition for `__kernel_deprecation_code:nn`, `\g__debug_deprecation_on_tl`, and `\g__debug_deprecation_off_tl`.)

5.7 Conditional processing and definitions

```
2256 <@@=prg>
```

Underneath any predicate function (`_p`) or other conditional forms (TF, etc.) is a built-in logic saying that it after all of the testing and processing must return the *state* it leaves \TeX in. Therefore, a simple user interface could be something like

```
\if_meaning:w #1#2
  \prg_return_true:
\else:
  \if_meaning:w #1#3
    \prg_return_true:
  \else:
    \prg_return_false:
\fi:
```

Usually, a \TeX programmer would have to insert a number of `\exp_after:wN`s to ensure the state value is returned at exactly the point where the last conditional is finished. However, that obscures the code and forces the \TeX programmer to prove that he/she knows the $2^n - 1$ table. We therefore provide the simpler interface.

`\prg_return_true:` The idea here is that `\exp:w` expands fully any `\else:` and `\fi:` that are waiting to be discarded, before reaching the `\exp_end:` which leaves an empty expansion. The code can then leave either the first or second argument in the input stream. This means that all of the branching code has to contain at least two tokens: see how the logical tests are actually implemented to see this.

```

2257 \cs_set:Npn \prg_return_true:
2258   { \exp_after:wN \use_i:nn \exp:w }
2259 \cs_set:Npn \prg_return_false:
2260   { \exp_after:wN \use_ii:nn \exp:w}

```

An extended state space could be implemented by including a more elaborate function in place of `\use_i:nn/\use_ii:nn`. Provided two arguments are absorbed then the code would work.

(End definition for \prg_return_true: and \prg_return_false:. These functions are documented on page 106.)

`\prg_use_none_delimit_by_q_recursion_stop:w` Private version of `\use_none_delimit_by_q_recursion_stop:w`.

```

2261 \cs_set:Npn \prg_use_none_delimit_by_q_recursion_stop:w
2262   #1 \q__prg_recursion_stop { }

```

(End definition for \prg_use_none_delimit_by_q_recursion_stop:w.)

`\prg_set_conditional:Npnn` The user functions for the types using parameter text from the programmer. The various functions only differ by which function is used for the assignment. For those `Npnn` type functions, we must grab the parameter text, reading everything up to a left brace before continuing. Then split the base function into name and signature, and feed `{\name}` `{\signature}` `\boolean` `{\set or new}` `{\maybe protected}` `{\parameters}` `{TF,...}` `{\code}` to the auxiliary function responsible for defining all conditionals. Note that `e` stands for expandable and `p` for protected.

```

2263 \cs_set_protected:Npn \prg_set_conditional:Npnn
2264   { \prg_generate_conditional_parm:NNNpnn \cs_set:Npn e }
2265 \cs_set_protected:Npn \prg_new_conditional:Npnn
2266   { \prg_generate_conditional_parm:NNNpnn \cs_new:Npn e }
2267 \cs_set_protected:Npn \prg_set_protected_conditional:Npnn
2268   { \prg_generate_conditional_parm:NNNpnn \cs_set_protected:Npn p }
2269 \cs_set_protected:Npn \prg_new_protected_conditional:Npnn
2270   { \prg_generate_conditional_parm:NNNpnn \cs_new_protected:Npn p }
2271 \cs_set_protected:Npn \prg_generate_conditional_parm:NNNpnn #1#2#3#4#
2272   {
2273     \use:x
2274     {
2275       \prg_generate_conditional:nnNNNnnn
2276       \cs_split_function:N #3
2277     }
2278     #1 #2 {#4}
2279   }

```

(End definition for \prg_set_conditional:Npnn and others. These functions are documented on page 104.)

`\prg_set_conditional:Nnn` The user functions for the types automatically inserting the correct parameter text based on the signature. The various functions only differ by which function is used for the assignment. Split the base function into name and signature. The second auxiliary

`\prg_generate_conditional_count:NNNnn`
`\prg_generate_conditional_count:nnNNNnn`

generates the parameter text from the number of letters in the signature. Then feed $\langle name \rangle$ $\langle signature \rangle$ $\langle boolean \rangle$ $\langle set \text{ or } new \rangle$ $\langle maybe \text{ protected} \rangle$ $\langle parameters \rangle$ $\{TF, \dots\}$ $\langle code \rangle$ to the auxiliary function responsible for defining all conditionals. If the $\langle signature \rangle$ has more than 9 letters, the definition is aborted since T_EX macros have at most 9 arguments. The erroneous case where the function name contains no colon is captured later.

```

2280 \cs_set_protected:Npn \prg_set_conditional:Nnn
2281   { \prg_generate_conditional_count:NNNnn \cs_set:Npn e }
2282 \cs_set_protected:Npn \prg_new_conditional:Nnn
2283   { \prg_generate_conditional_count:NNNnn \cs_new:Npn e }
2284 \cs_set_protected:Npn \prg_set_protected_conditional:Nnn
2285   { \prg_generate_conditional_count:NNNnn \cs_set_protected:Npn p }
2286 \cs_set_protected:Npn \prg_new_protected_conditional:Nnn
2287   { \prg_generate_conditional_count:NNNnn \cs_new_protected:Npn p }
2288 \cs_set_protected:Npn \prg_generate_conditional_count:NNNnn #1#2#3
2289   {
2290     \use:x
2291     {
2292       \prg_generate_conditional_count:nnNNNnn
2293       \cs_split_function:N #3
2294     }
2295     #1 #2
2296   }
2297 \cs_set_protected:Npn \prg_generate_conditional_count:nnNNNnn #1#2#3#4#5
2298   {
2299     \kernel_cs_parm_from_arg_count:nnF
2300     { \prg_generate_conditional:nnNNNnnn {#1} {#2} #3 #4 #5 }
2301     { \tl_count:n {#2} }
2302     {
2303       \kernel_msg_error:nxxx { kernel } { bad-number-of-arguments }
2304       { \token_to_str:c { #1 : #2 } }
2305       { \tl_count:n {#2} }
2306       \use_none:nn
2307     }
2308   }

```

(End definition for `\prg_set_conditional:Nnn` and others. These functions are documented on page 104.)

`\prg_generate_conditional:nnNNNnnn`
`\prg_generate_conditional:NNnnnnNw`
`\prg_generate_conditional_test:w`
`\prg_generate_conditional_fast:nw`

The workhorse here is going through a list of desired forms, *i.e.*, p, TF, T and F. The first three arguments come from splitting up the base form of the conditional, which gives the name, signature and a boolean to signal whether or not there was a colon in the name. In the absence of a colon, we throw an error and don't define any conditional. The fourth and fifth arguments build up the defining function. The sixth is the parameters to use (possibly empty), the seventh is the list of forms to define, the eighth is the replacement text which we will augment when defining the forms. The use of `\tl_to_str:n` makes the later loop more robust.

A large number of our low-level conditionals look like $\langle code \rangle$ `\prg_return_true:` `\else:` `\prg_return_false:` `\fi:` so we optimize this special case by calling `\prg_generate_conditional_fast:nw` $\langle code \rangle$. This passes `\use_i:nn` instead of `\use_ii:nnn` to functions such as `\prg_generate_p_form:wNNnnnnN`.

```

2309 \cs_set_protected:Npn \prg_generate_conditional:nnNNNnnn #1#2#3#4#5#6#7#8
2310   {

```



```

2311 \if_meaning:w \c_false_bool #3
2312 \__kernel_msg_error:nxx { kernel } { missing-colon }
2313 { \token_to_str:c {#1} }
2314 \exp_after:wN \use_none:nn
2315 \fi:
2316 \use:x
2317 {
2318 \exp_not:N \__prg_generate_conditional:NNnnnnNw
2319 \exp_not:n { #4 #5 {#1} {#2} {#6} }
2320 \__prg_generate_conditional_test:w
2321 #8 \s__prg_mark
2322 \__prg_generate_conditional_fast:nw
2323 \prg_return_true: \else: \prg_return_false: \fi: \s__prg_mark
2324 \use_none:n
2325 \exp_not:n { {#8} \use_i_ii:nnn }
2326 \tl_to_str:n {#7}
2327 \exp_not:n { , \q__prg_recursion_tail , \q__prg_recursion_stop }
2328 }
2329 }
2330 \cs_set:Npn \__prg_generate_conditional_test:w
2331 #1 \prg_return_true: \else: \prg_return_false: \fi: \s__prg_mark #2
2332 { #2 {#1} }
2333 \cs_set:Npn \__prg_generate_conditional_fast:nw #1#2 \exp_not:n #3
2334 { \exp_not:n { {#1} \use_i:nn } }

```

Looping through the list of desired forms. First are six arguments and seventh is the form. Use the form to call the correct type. If the form does not exist, the `\use:c` construction results in `\relax`, and the error message is displayed (unless the form is empty, to allow for {T, , F}), then `\use_none:nnnnnnnn` cleans up. Otherwise, the error message is removed by the variant form.

```

2335 \cs_set_protected:Npn \__prg_generate_conditional:NNnnnnNw #1#2#3#4#5#6#7#8 ,
2336 {
2337 \if_meaning:w \q__prg_recursion_tail #8
2338 \exp_after:wN \__prg_use_none_delimit_by_q_recursion_stop:w
2339 \fi:
2340 \use:c { __prg_generate_ #8 _form:wNNnnnnN }
2341 \tl_if_empty:nF {#8}
2342 {
2343 \__kernel_msg_error:nxxx
2344 { kernel } { conditional-form-unknown }
2345 {#8} { \token_to_str:c { #3 : #4 } }
2346 }
2347 \use_none:nnnnnnnn
2348 \s__prg_stop
2349 #1 #2 {#3} {#4} {#5} {#6} #7
2350 \__prg_generate_conditional:NNnnnnNw #1 #2 {#3} {#4} {#5} {#6} #7
2351 }

```

(End definition for `__prg_generate_conditional:nnNNnnnn` and others.)

`__prg_generate_p_form:wNNnnnnN` How to generate the various forms. Those functions take the following arguments: 1: junk, 2: `\cs_set:Npn` or similar, 3: p (for protected conditionals) or e, 4: function name, 5: signature, 6: parameter text, 7: replacement (possibly trimmed by `__prg_generate_conditional_fast:nw`), 8: `\use_i_ii:nnn` or `\use_i:nn` (for “fast” conditionals). Remember that the logic-returning functions expect two arguments to be present

after `\exp_end::` notice the construction of the different variants relies on this, and that the TF and F variants will be slightly faster than the T version. The `p` form is only valid for expandable tests, we check for that by making sure that the second argument is empty. For “fast” conditionals, #7 has an extra `\if_...` To optimize a bit further we could replace `\exp_after:wN \use_ii:nnn` and similar by a single macro similar to `__prg_p_true:w`. The drawback is that if the T or F arguments are actually missing, the recovery from the runaway argument would not insert `\fi:` back, messing up nesting of conditionals.

```

2352 \cs_set_protected:Npn \__prg_generate_p_form:wNNnnnnN
2353   #1 \s__prg_stop #2#3#4#5#6#7#8
2354   {
2355     \if_meaning:w e #3
2356     \exp_after:wN \use_i:nn
2357   \else:
2358     \exp_after:wN \use_ii:nn
2359   \fi:
2360     {
2361       #8
2362       { \exp_args:Nc #2 { #4 _p: #5 } #6 }
2363       { { #7 \exp_end: \c_true_bool \c_false_bool } }
2364       { #7 \__prg_p_true:w \fi: \c_false_bool }
2365     }
2366     {
2367       \__kernel_msg_error:nxx { kernel } { protected-predicate }
2368       { \token_to_str:c { #4 _p: #5 } }
2369     }
2370   }
2371 \cs_set_protected:Npn \__prg_generate_T_form:wNNnnnnN
2372   #1 \s__prg_stop #2#3#4#5#6#7#8
2373   {
2374     #8
2375     { \exp_args:Nc #2 { #4 : #5 T } #6 }
2376     { { #7 \exp_end: \use:n \use_none:n } }
2377     { #7 \exp_after:wN \use_ii:nn \fi: \use_none:n }
2378   }
2379 \cs_set_protected:Npn \__prg_generate_F_form:wNNnnnnN
2380   #1 \s__prg_stop #2#3#4#5#6#7#8
2381   {
2382     #8
2383     { \exp_args:Nc #2 { #4 : #5 F } #6 }
2384     { { #7 \exp_end: { } } }
2385     { #7 \exp_after:wN \use_none:nn \fi: \use:n }
2386   }
2387 \cs_set_protected:Npn \__prg_generate_TF_form:wNNnnnnN
2388   #1 \s__prg_stop #2#3#4#5#6#7#8
2389   {
2390     #8
2391     { \exp_args:Nc #2 { #4 : #5 TF } #6 }
2392     { { #7 \exp_end: { } } }
2393     { #7 \exp_after:wN \use_ii:nnn \fi: \use_ii:nn }
2394   }
2395 \cs_set:Npn \__prg_p_true:w \fi: \c_false_bool { \fi: \c_true_bool }

```

(End definition for `__prg_generate_p_form:wNNnnnnN` and others.)

`\prg_set_eq_conditional:NNn` The setting-equal functions. Split both functions and feed $\{\langle name_1 \rangle\}$ $\{\langle signature_1 \rangle\}$
`\prg_new_eq_conditional:NNn` $\langle boolean_1 \rangle$ $\{\langle name_2 \rangle\}$ $\{\langle signature_2 \rangle\}$ $\langle boolean_2 \rangle$ $\langle copying\ function \rangle$ $\langle conditions \rangle$, `\q__-`
`__prg_set_eq_conditional:NNNn` `prg_recursion_tail` , `\q__prg_recursion_stop` to a first auxiliary.

```

2396 \cs_set_protected:Npn \prg_set_eq_conditional:NNn
2397   { \__prg_set_eq_conditional:NNNn \cs_set_eq:cc }
2398 \cs_set_protected:Npn \prg_new_eq_conditional:NNn
2399   { \__prg_set_eq_conditional:NNNn \cs_new_eq:cc }
2400 \cs_set_protected:Npn \__prg_set_eq_conditional:NNNn #1#2#3#4
2401   {
2402     \use:x
2403     {
2404       \exp_not:N \__prg_set_eq_conditional:nnNnnNWw
2405       \cs_split_function:N #2
2406       \cs_split_function:N #3
2407       \exp_not:N #1
2408       \tl_to_str:n {#4}
2409       \exp_not:n { , \q__prg_recursion_tail , \q__prg_recursion_stop }
2410     }
2411   }

```

(End definition for `\prg_set_eq_conditional:NNn`, `\prg_new_eq_conditional:NNn`, and `__prg_set_eq_conditional:NNNn`. These functions are documented on page 105.)

`__prg_set_eq_conditional:nnNnnNWw` Split the function to be defined, and setup a manual clist loop over argument #6 of the
`__prg_set_eq_conditional_loop:nnnnNW` first auxiliary. The second auxiliary receives twice three arguments coming from splitting
`__prg_set_eq_conditional_p_form:nnn` the function to be defined and the function to copy. Make sure that both functions
`__prg_set_eq_conditional_TF_form:nnn` contained a colon, otherwise we don't know how to build conditionals, hence abort. Call
`__prg_set_eq_conditional_T_form:nnn` the looping macro, with arguments $\{\langle name_1 \rangle\}$ $\{\langle signature_1 \rangle\}$ $\{\langle name_2 \rangle\}$ $\{\langle signature_2 \rangle\}$
`__prg_set_eq_conditional_F_form:nnn` $\langle copying\ function \rangle$ and followed by the comma list. At each step in the loop, make sure
that the conditional form we copy is defined, and copy it, otherwise abort.

```

2412 \cs_set_protected:Npn \__prg_set_eq_conditional:nnNnnNWw #1#2#3#4#5#6
2413   {
2414     \if_meaning:w \c_false_bool #3
2415       \__kernel_msg_error:nnx { kernel } { missing-colon }
2416       { \token_to_str:c {#1} } }
2417     \exp_after:wN \__prg_use_none_delimit_by_q_recursion_stop:w
2418     \fi:
2419     \if_meaning:w \c_false_bool #6
2420       \__kernel_msg_error:nnx { kernel } { missing-colon }
2421       { \token_to_str:c {#4} } }
2422     \exp_after:wN \__prg_use_none_delimit_by_q_recursion_stop:w
2423     \fi:
2424     \__prg_set_eq_conditional_loop:nnnnNW {#1} {#2} {#4} {#5}
2425   }
2426 \cs_set_protected:Npn \__prg_set_eq_conditional_loop:nnnnNW #1#2#3#4#5#6 ,
2427   {
2428     \if_meaning:w \q__prg_recursion_tail #6
2429       \exp_after:wN \__prg_use_none_delimit_by_q_recursion_stop:w
2430       \fi:
2431     \use:c { __prg_set_eq_conditional_ #6 _form:wNnnnn }
2432     \tl_if_empty:nF {#6}
2433     {
2434       \__kernel_msg_error:nnxx

```

```

2435         { kernel } { conditional-form-unknown }
2436         {#6} { \token_to_str:c { #1 : #2 } }
2437     }
2438     \use_none:nnnnnn
2439     \s__prg_stop
2440     #5 {#1} {#2} {#3} {#4}
2441     \__prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#3} {#4} #5
2442 }
2443 \cs_set:Npn \__prg_set_eq_conditional_p_form:wNnnnn #1 \s__prg_stop #2#3#4#5#6
2444 { #2 { #3 _p : #4 } { #5 _p : #6 } }
2445 \cs_set:Npn \__prg_set_eq_conditional_TF_form:wNnnnn #1 \s__prg_stop #2#3#4#5#6
2446 { #2 { #3 : #4 TF } { #5 : #6 TF } }
2447 \cs_set:Npn \__prg_set_eq_conditional_T_form:wNnnnn #1 \s__prg_stop #2#3#4#5#6
2448 { #2 { #3 : #4 T } { #5 : #6 T } }
2449 \cs_set:Npn \__prg_set_eq_conditional_F_form:wNnnnn #1 \s__prg_stop #2#3#4#5#6
2450 { #2 { #3 : #4 F } { #5 : #6 F } }

```

(End definition for `__prg_set_eq_conditional:nnNnnNNw` and others.)

All that is left is to define the canonical boolean true and false. I think Michael originated the idea of expandable boolean tests. At first these were supposed to expand into either TT or TF to be tested using `\if:w` but this was later changed to 00 and 01, so they could be used in logical operations. Later again they were changed to being numerical constants with values of 1 for true and 0 for false. We need this from the get-go.

```

\c_true_bool Here are the canonical boolean values.
\c_false_bool
2451 \tex_chardef:D \c_true_bool = 1 ~
2452 \tex_chardef:D \c_false_bool = 0 ~

```

(End definition for `\c_true_bool` and `\c_false_bool`. These variables are documented on page 22.)

5.8 Dissecting a control sequence

```

2453 <@@=cs>

```

```

\__cs_count_signature:N \__cs_count_signature:N <function>

```

Splits the *<function>* into the *<name>* (i.e. the part before the colon) and the *<signature>* (i.e. after the colon). The *<number>* of tokens in the *<signature>* is then left in the input stream. If there was no *<signature>* then the result is the marker value `-1`.

```

\__cs_get_function_name:N * \__cs_get_function_name:N <function>

```

Splits the *<function>* into the *<name>* (i.e. the part before the colon) and the *<signature>* (i.e. after the colon). The *<name>* is then left in the input stream without the escape character present made up of tokens with category code 12 (other).

```

\__cs_get_function_signature:N * \__cs_get_function_signature:N <function>

```

Splits the *<function>* into the *<name>* (i.e. the part before the colon) and the *<signature>* (i.e. after the colon). The *<signature>* is then left in the input stream made up of tokens with category code 12 (other).

<code>__cs_tmp:w</code>	Function used for various short-term usages, for instance defining functions whose definition involves tokens which are hard to insert normally (spaces, characters with category other).
<code>\cs_to_str:N</code> <code>__cs_to_str:N</code> <code>__cs_to_str:w</code>	This converts a control sequence into the character string of its name, removing the leading escape character. This turns out to be a non-trivial matter as there are different cases:

- The usual case of a printable escape character;
- the case of a non-printable escape characters, e.g., when the value of the `\escapechar` is negative;
- when the escape character is a space.

One approach to solve this is to test how many tokens result from `\token_to_str:N \a`. If there are two tokens, then the escape character is printable, while if it is non-printable then only one is present.

However, there is an additional complication: the control sequence itself may start with a space. Clearly that should *not* be lost in the process of converting to a string. So the approach adopted is a little more intricate still. When the escape character is printable, `\token_to_str:N _` yields the escape character itself and a space. The character codes are different, thus the `\if:w` test is false, and TeX reads `__cs_to_str:N` after turning the following control sequence into a string; this auxiliary removes the escape character, and stops the expansion of the initial `\tex_romannumeral:D`. The second case is that the escape character is not printable. Then the `\if:w` test is unfinished after reading a the space from `\token_to_str:N _`, and the auxiliary `__cs_to_str:w` is expanded, feeding – as a second character for the test; the test is false, and TeX skips to `\fi:`, then performs `\token_to_str:N`, and stops the `\tex_romannumeral:D` with `\c_zero_int`. The last case is that the escape character is itself a space. In this case, the `\if:w` test is true, and the auxiliary `__cs_to_str:w` comes into play, inserting `-\int_value:w`, which expands `\c_zero_int` to the character 0. The initial `\tex_romannumeral:D` then sees 0, which is not a terminated number, followed by the escape character, a space, which is removed, terminating the expansion of `\tex_romannumeral:D`. In all three cases, `\cs_to_str:N` takes two expansion steps to be fully expanded.

```

2454 \cs_set:Npn \cs_to_str:N
2455 {

```

We implement the expansion scheme using `\tex_romannumeral:D` terminating it with `\c_zero_int` rather than using `\exp:w` and `\exp_end:` as we normally do. The reason is that the code heavily depends on terminating the expansion with `\c_zero_int` so we make this dependency explicit.

```

2456     \tex_romannumeral:D
2457     \if:w \token_to_str:N \ \__cs_to_str:w \fi:
2458     \exp_after:wN \__cs_to_str:N \token_to_str:N
2459 }
2460 \cs_set:Npn \__cs_to_str:N #1 { \c_zero_int }
2461 \cs_set:Npn \__cs_to_str:w #1 \__cs_to_str:N
2462 { - \int_value:w \fi: \exp_after:wN \c_zero_int }

```

If speed is a concern we could use `\csstring` in LuaTeX. For the empty csname that primitive gives an empty result while the current `\cs_to_str:N` gives incorrect results in all engines (this is impossible to fix without huge performance hit).

(End definition for `\cs_to_str:N`, `__cs_to_str:N`, and `__cs_to_str:w`. This function is documented on page 17.)

`\cs_split_function:N`

This function takes a function name and splits it into name with the escape char removed and argument specification. In addition to this, a third argument, a boolean $\langle true \rangle$ or $\langle false \rangle$ is returned with $\langle true \rangle$ for when there is a colon in the function and $\langle false \rangle$ if there is not.

We cannot use `:` directly as it has the wrong category code so an `x`-type expansion is used to force the conversion.

First ensure that we actually get a properly evaluated string by expanding `\cs_to_str:N` twice. If the function contained a colon, the auxiliary takes as `#1` the function name, delimited by the first colon, then the signature `#2`, delimited by `\s__cs_mark`, then `\c_true_bool` as `#3`, and `#4` cleans up until `\s__cs_stop`. Otherwise, the `#1` contains the function name and `\s__cs_mark \c_true_bool`, `#2` is empty, `#3` is `\c_false_bool`, and `#4` cleans up. The second auxiliary trims the trailing `\s__cs_mark` from the function name if present (that is, if the original function had no colon).

```

2463 \cs_set_protected:Npn \__cs_tmp:w #1
2464 {
2465   \cs_set:Npn \cs_split_function:N ##1
2466   {
2467     \exp_after:wN \exp_after:wN \exp_after:wN
2468     \__cs_split_function_auxi:w
2469     \cs_to_str:N ##1 \s__cs_mark \c_true_bool
2470     #1 \s__cs_mark \c_false_bool \s__cs_stop
2471   }
2472   \cs_set:Npn \__cs_split_function_auxi:w
2473   ##1 #1 ##2 \s__cs_mark ##3##4 \s__cs_stop
2474   { \__cs_split_function_auxii:w ##1 \s__cs_mark \s__cs_stop {##2} ##3 }
2475   \cs_set:Npn \__cs_split_function_auxii:w ##1 \s__cs_mark ##2 \s__cs_stop
2476   { {##1} }
2477 }
2478 \exp_after:wN \__cs_tmp:w \token_to_str:N :
```

(End definition for `\cs_split_function:N`, `__cs_split_function_auxi:w`, and `__cs_split_function_auxii:w`. This function is documented on page 17.)

5.9 Exist or free

A control sequence is said to *exist* (to be used) if has an entry in the hash table and its meaning is different from the primitive `\relax` token. A control sequence is said to be *free* (to be defined) if it does not already exist.

`\cs_if_exist_p:N`

`\cs_if_exist_p:c`

`\cs_if_exist:NTF`

`\cs_if_exist:cTF`

Two versions for checking existence. For the `N` form we firstly check for `\scan_stop:` and then if it is in the hash table. There is no problem when inputting something like `\else:` or `\fi:` as \TeX will only ever skip input in case the token tested against is `\scan_stop:`.

```

2479 \prg_set_conditional:Npnn \cs_if_exist:N #1 { p , T , F , TF }
2480 {
2481   \if_meaning:w #1 \scan_stop:
2482   \prg_return_false:
2483   \else:
2484     \if_cs_exist:N #1
2485     \prg_return_true:
2486     \else:
```

```

2487     \prg_return_false:
2488     \fi:
2489     \fi:
2490 }

```

For the `c` form we firstly check if it is in the hash table and then for `\scan_stop:` so that we do not add it to the hash table unless it was already there. Here we have to be careful as the text to be skipped if the first test is false may contain tokens that disturb the scanner. Therefore, we ensure that the second test is performed after the first one has concluded completely.

```

2491 \prg_set_conditional:Npnn \cs_if_exist:c #1 { p , T , F , TF }
2492 {
2493     \if_cs_exist:w #1 \cs_end:
2494     \exp_after:wN \use_i:nn
2495     \else:
2496     \exp_after:wN \use_ii:nn
2497     \fi:
2498     {
2499     \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
2500     \prg_return_false:
2501     \else:
2502     \prg_return_true:
2503     \fi:
2504     }
2505     \prg_return_false:
2506 }

```

(End definition for `\cs_if_exist:NTF`. This function is documented on page 22.)

`\cs_if_free_p:N`
`\cs_if_free_p:c`
`\cs_if_free:NTF`
`\cs_if_free:cTF`

The logical reversal of the above.

```

2507 \prg_set_conditional:Npnn \cs_if_free:N #1 { p , T , F , TF }
2508 {
2509     \if_meaning:w #1 \scan_stop:
2510     \prg_return_true:
2511     \else:
2512     \if_cs_exist:N #1
2513     \prg_return_false:
2514     \else:
2515     \prg_return_true:
2516     \fi:
2517     \fi:
2518 }
2519 \prg_set_conditional:Npnn \cs_if_free:c #1 { p , T , F , TF }
2520 {
2521     \if_cs_exist:w #1 \cs_end:
2522     \exp_after:wN \use_i:nn
2523     \else:
2524     \exp_after:wN \use_ii:nn
2525     \fi:
2526     {
2527     \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
2528     \prg_return_true:
2529     \else:
2530     \prg_return_false:

```

```

2531     \fi:
2532   }
2533   { \prg_return_true: }
2534 }

```

(End definition for `\cs_if_free:NTF`. This function is documented on page 22.)

`\cs_if_exist_use:N` The `\cs_if_exist_use:...` functions cannot be implemented as conditionals because
`\cs_if_exist_use:c` the true branch must leave both the control sequence itself and the true code in the input
`\cs_if_exist_use:NTF` stream. For the `c` variants, we are careful not to put the control sequence in the hash
`\cs_if_exist_use:cTF` table if it does not exist. In LuaTeX we could use the `\lastnamedcs` primitive.

```

2535 \cs_set:Npn \cs_if_exist_use:NTF #1#2
2536 { \cs_if_exist:NTF #1 { #1 #2 } }
2537 \cs_set:Npn \cs_if_exist_use:NF #1
2538 { \cs_if_exist:NTF #1 { #1 } }
2539 \cs_set:Npn \cs_if_exist_use:NT #1 #2
2540 { \cs_if_exist:NTF #1 { #1 #2 } { } }
2541 \cs_set:Npn \cs_if_exist_use:N #1
2542 { \cs_if_exist:NTF #1 { #1 } { } }
2543 \cs_set:Npn \cs_if_exist_use:cTF #1#2
2544 { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } }
2545 \cs_set:Npn \cs_if_exist_use:cF #1
2546 { \cs_if_exist:cTF {#1} { \use:c {#1} } }
2547 \cs_set:Npn \cs_if_exist_use:cT #1#2
2548 { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } { } }
2549 \cs_set:Npn \cs_if_exist_use:c #1
2550 { \cs_if_exist:cTF {#1} { \use:c {#1} } { } }

```

(End definition for `\cs_if_exist_use:NTF`. This function is documented on page 16.)

5.10 Preliminaries for new functions

We provide two kinds of functions that can be used to define control sequences. On the one hand we have functions that check if their argument doesn't already exist, they are called `\..._new`. The second type of defining functions doesn't check if the argument is already defined.

Before we can define them, we need some auxiliary macros that allow us to generate error messages. The next few definitions here are only temporary, they will be redefined later on.

`__kernel_msg_error:nxxx` If an internal error occurs before L^AT_EX3 has loaded `l3msg` then the code should issue a
`__kernel_msg_error:nxx` usable if terse error message and halt. This can only happen if a coding error is made by
`__kernel_msg_error:nn` the team, so this is a reasonable response. Setting the `\newlinechar` is needed, to turn
`^^J` into a proper line break in plain T_EX.

```

2551 \cs_set_protected:Npn \__kernel_msg_error:nxxx #1#2#3#4
2552 {
2553   \tex_newlinechar:D = '\^^J \scan_stop:
2554   \tex_errmessage:D
2555   {
2556     !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!~! ^^J
2557     Argh,~internal~LaTeX3~error! ^^J ^^J
2558     Module ~ #1 , ~ message~name~"#2": ^^J
2559     Arguments~'#3'~and~'#4' ^^J ^^J

```



```

2560         This~is~one~for~The~LaTeX3~Project:~bailing~out
2561     }
2562     \tex_end:D
2563 }
2564 \cs_set_protected:Npn \__kernel_msg_error:nxx #1#2#3
2565 { \__kernel_msg_error:nxxx {#1} {#2} {#3} { } }
2566 \cs_set_protected:Npn \__kernel_msg_error:nn #1#2
2567 { \__kernel_msg_error:nxxx {#1} {#2} { } { } }

```

(End definition for `__kernel_msg_error:nxxx`, `__kernel_msg_error:nxx`, and `__kernel_msg_error:nn`.)

`\msg_line_context:` Another one from `l3msg` which will be altered later.

```

2568 \cs_set:Npn \msg_line_context:
2569 { on~line~ \tex_the:D \tex_inputlineno:D }

```

(End definition for `\msg_line_context:`. This function is documented on page 151.)

`\iow_log:x` We define a routine to write only to the log file. And a similar one for writing to both
`\iow_term:x` the log file and the terminal. These will be redefined later by `l3io`.

```

2570 \cs_set_protected:Npn \iow_log:x
2571 { \tex_immediate:D \tex_write:D -1 }
2572 \cs_set_protected:Npn \iow_term:x
2573 { \tex_immediate:D \tex_write:D 16 }

```

(End definition for `\iow_log:n`. This function is documented on page 160.)

`__kernel_chk_if_free_cs:N` This command is called by `\cs_new_nopar:Npn` and `\cs_new_eq:NN` etc. to make sure
`__kernel_chk_if_free_cs:c` that the argument sequence is not already in use. If it is, an error is signalled. It checks
if `<csname>` is undefined or `\scan_stop:`. Otherwise an error message is issued. We have
to make sure we don't put the argument into the conditional processing since it may be
an `\if...` type function!

```

2574 \cs_set_protected:Npn \__kernel_chk_if_free_cs:N #1
2575 {
2576     \cs_if_free:NF #1
2577     {
2578         \__kernel_msg_error:nxxx { kernel } { command-already-defined }
2579         { \token_to_str:N #1 } { \token_to_meaning:N #1 }
2580     }
2581 }
2582 \cs_set_protected:Npn \__kernel_chk_if_free_cs:c
2583 { \exp_args:Nc \__kernel_chk_if_free_cs:N }

```

(End definition for `__kernel_chk_if_free_cs:N`.)

5.11 Defining new functions

```

2584 (@@=cs)

```

`\cs_new_nopar:Npn` Function which check that the control sequence is free before defining it.

```

\cs_new_nopar:Npx 2585 \cs_set:Npn \__cs_tmp:w #1#2
\cs_new:Npn       2586 {
\cs_new:Npx       2587     \cs_set_protected:Npn #1 ##1
\cs_new_protected_nopar:Npn 2588     {
\cs_new_protected_nopar:Npx 2589         \__kernel_chk_if_free_cs:N ##1
\cs_new_protected:Npn      2590         #2 ##1
\cs_new_protected:Npx

```

```

\__cs_tmp:w

```

```

2591     }
2592 }
2593 \__cs_tmp:w \cs_new_nopar:Npn          \cs_gset_nopar:Npn
2594 \__cs_tmp:w \cs_new_nopar:Npx          \cs_gset_nopar:Npx
2595 \__cs_tmp:w \cs_new:Npn                \cs_gset:Npn
2596 \__cs_tmp:w \cs_new:Npx                \cs_gset:Npx
2597 \__cs_tmp:w \cs_new_protected_nopar:Npn \cs_gset_protected_nopar:Npn
2598 \__cs_tmp:w \cs_new_protected_nopar:Npx \cs_gset_protected_nopar:Npx
2599 \__cs_tmp:w \cs_new_protected:Npn      \cs_gset_protected:Npn
2600 \__cs_tmp:w \cs_new_protected:Npx      \cs_gset_protected:Npx

```

(End definition for `\cs_new_nopar:Npn` and others. These functions are documented on page 11.)

`\cs_set_nopar:cpn` Like `\cs_set_nopar:Npn` and `\cs_new_nopar:Npn`, except that the first argument consists of the sequence of characters that should be used to form the name of the desired control sequence (the `c` stands for `csname` argument, see the expansion module). Global versions are also provided.

`\cs_set_nopar:cpn` $\langle string \rangle \langle rep-text \rangle$ turns $\langle string \rangle$ into a `csname` and then assigns $\langle rep-text \rangle$ to it by using `\cs_set_nopar:Npn`. This means that there might be a parameter string between the two arguments.

```

2601 \cs_set:Npn \__cs_tmp:w #1#2
2602 { \cs_new_protected_nopar:Npn #1 { \exp_args:Nc #2 } }
2603 \__cs_tmp:w \cs_set_nopar:cpn \cs_set_nopar:Npn
2604 \__cs_tmp:w \cs_set_nopar:cpx \cs_set_nopar:Npx
2605 \__cs_tmp:w \cs_gset_nopar:cpn \cs_gset_nopar:Npn
2606 \__cs_tmp:w \cs_gset_nopar:cpx \cs_gset_nopar:Npx
2607 \__cs_tmp:w \cs_new_nopar:cpn \cs_new_nopar:Npn
2608 \__cs_tmp:w \cs_new_nopar:cpx \cs_new_nopar:Npx

```

(End definition for `\cs_set_nopar:Npn`. This function is documented on page 11.)

`\cs_set:cpn` Variants of the `\cs_set:Npn` versions which make a `csname` out of the first arguments.
`\cs_set:cpx` We may also do this globally.

```

2609 \__cs_tmp:w \cs_set:cpn \cs_set:Npn
2610 \__cs_tmp:w \cs_set:cpx \cs_set:Npx
2611 \__cs_tmp:w \cs_gset:cpn \cs_gset:Npn
2612 \__cs_tmp:w \cs_gset:cpx \cs_gset:Npx
2613 \__cs_tmp:w \cs_new:cpn \cs_new:Npn
2614 \__cs_tmp:w \cs_new:cpx \cs_new:Npx

```

(End definition for `\cs_set:Npn`. This function is documented on page 11.)

`\cs_set_protected_nopar:cpn` Variants of the `\cs_set_protected_nopar:Npn` versions which make a `csname` out of the first arguments. We may also do this globally.

```

2615 \__cs_tmp:w \cs_set_protected_nopar:cpn \cs_set_protected_nopar:Npn
2616 \__cs_tmp:w \cs_set_protected_nopar:cpx \cs_set_protected_nopar:Npx
2617 \__cs_tmp:w \cs_gset_protected_nopar:cpn \cs_gset_protected_nopar:Npn
2618 \__cs_tmp:w \cs_gset_protected_nopar:cpx \cs_gset_protected_nopar:Npx
2619 \__cs_tmp:w \cs_new_protected_nopar:cpn \cs_new_protected_nopar:Npn
2620 \__cs_tmp:w \cs_new_protected_nopar:cpx \cs_new_protected_nopar:Npx

```

(End definition for `\cs_set_protected_nopar:Npn`. This function is documented on page 12.)

<code>\cs_set_protected:cpn</code>	2621	<code>__cs_tmp:w \cs_set_protected:cpn \cs_set_protected:Npn</code>
<code>\cs_set_protected:cpx</code>	2622	<code>__cs_tmp:w \cs_set_protected:cpx \cs_set_protected:Npx</code>
<code>\cs_gset_protected:cpn</code>	2623	<code>__cs_tmp:w \cs_gset_protected:cpn \cs_gset_protected:Npn</code>
<code>\cs_gset_protected:cpx</code>	2624	<code>__cs_tmp:w \cs_gset_protected:cpx \cs_gset_protected:Npx</code>
<code>\cs_new_protected:cpn</code>	2625	<code>__cs_tmp:w \cs_new_protected:cpn \cs_new_protected:Npn</code>
<code>\cs_new_protected:cpx</code>	2626	<code>__cs_tmp:w \cs_new_protected:cpx \cs_new_protected:Npx</code>

(End definition for `\cs_set_protected:Npn`. This function is documented on page 11.)

5.12 Copying definitions

<code>\cs_set_eq:NN</code>	These macros allow us to copy the definition of a control sequence to another control sequence.
<code>\cs_set_eq:cN</code>	The = sign allows us to define funny char tokens like = itself or <code>_</code> with this function.
<code>\cs_set_eq:Nc</code>	For the definition of <code>\c_space_char{~}</code> to work we need the ~ after the =.
<code>\cs_set_eq:cc</code>	
<code>\cs_gset_eq:NN</code>	<code>\cs_set_eq:NN</code> is long to avoid problems with a literal argument of <code>\par</code> . While
<code>\cs_gset_eq:cN</code>	<code>\cs_new_eq:NN</code> will probably never be correct with a first argument of <code>\par</code> , define it
<code>\cs_gset_eq:Nc</code>	long in order to throw an “already defined” error rather than “runaway argument”.
<code>\cs_gset_eq:cc</code>	2627 <code>\cs_new_protected:Npn \cs_set_eq:NN #1 { \tex_let:D #1 =~ }</code>
<code>\cs_new_eq:NN</code>	2628 <code>\cs_new_protected:Npn \cs_set_eq:cN { \exp_args:Nc \cs_set_eq:NN }</code>
<code>\cs_new_eq:cN</code>	2629 <code>\cs_new_protected:Npn \cs_set_eq:Nc { \exp_args:NNc \cs_set_eq:NN }</code>
<code>\cs_new_eq:Nc</code>	2630 <code>\cs_new_protected:Npn \cs_set_eq:cc { \exp_args:Ncc \cs_set_eq:NN }</code>
<code>\cs_new_eq:cc</code>	2631 <code>\cs_new_protected:Npn \cs_gset_eq:NN { \tex_global:D \cs_set_eq:NN }</code>
	2632 <code>\cs_new_protected:Npn \cs_gset_eq:Nc { \exp_args:NNc \cs_gset_eq:NN }</code>
	2633 <code>\cs_new_protected:Npn \cs_gset_eq:cN { \exp_args:Nc \cs_gset_eq:NN }</code>
	2634 <code>\cs_new_protected:Npn \cs_gset_eq:cc { \exp_args:Ncc \cs_gset_eq:NN }</code>
	2635 <code>\cs_new_protected:Npn \cs_new_eq:NN #1</code>
	2636 <code>{</code>
	2637 <code> _kernel_chk_if_free_cs:N #1</code>
	2638 <code> \tex_global:D \cs_set_eq:NN #1</code>
	2639 <code>}</code>
	2640 <code>\cs_new_protected:Npn \cs_new_eq:cN { \exp_args:Nc \cs_new_eq:NN }</code>
	2641 <code>\cs_new_protected:Npn \cs_new_eq:Nc { \exp_args:NNc \cs_new_eq:NN }</code>
	2642 <code>\cs_new_protected:Npn \cs_new_eq:cc { \exp_args:Ncc \cs_new_eq:NN }</code>

(End definition for `\cs_set_eq:NN`, `\cs_gset_eq:NN`, and `\cs_new_eq:NN`. These functions are documented on page 15.)

5.13 Undefined functions

<code>\cs_undefine:N</code>	The following function is used to free the main memory from the definition of some
<code>\cs_undefine:c</code>	function that isn’t in use any longer. The c variant is careful not to add the control
	sequence to the hash table if it isn’t there yet, and it also avoids nesting TeX conditionals
	in case #1 is unbalanced in this matter.
	2643 <code>\cs_new_protected:Npn \cs_undefine:N #1</code>
	2644 <code>{ \cs_gset_eq:NN #1 \tex_undefined:D }</code>
	2645 <code>\cs_new_protected:Npn \cs_undefine:c #1</code>
	2646 <code>{</code>
	2647 <code> \if_cs_exist:w #1 \cs_end:</code>
	2648 <code> \exp_after:wN \use:n</code>
	2649 <code> \else:</code>

```

2650     \exp_after:wN \use_none:n
2651   \fi:
2652   { \cs_gset_eq:cN {#1} \tex_undefined:D }
2653 }

```

(End definition for `\cs_undefine:N`. This function is documented on page 15.)

5.14 Generating parameter text from argument count

`_kernel_cs_parm_from_arg_count:nnF`
`_cs_parm_from_arg_count_test:nnF`

L^AT_EX3 provides shorthands to define control sequences and conditionals with a simple parameter text, derived directly from the signature, or more generally from knowing the number of arguments, between 0 and 9. This function expands to its first argument, untouched, followed by a brace group containing the parameter text `{#1...#n}`, where n is the result of evaluating the second argument (as described in `\int_eval:n`). If the second argument gives a result outside the range $[0, 9]$, the third argument is returned instead, normally an error message. Some of the functions use here are not defined yet, but will be defined before this function is called.

```

2655 \cs_set_protected:Npn \_kernel_cs_parm_from_arg_count:nnF #1#2
2656 {
2657   \exp_args:Nx \_cs_parm_from_arg_count_test:nnF
2658   {
2659     \exp_after:wN \exp_not:n
2660     \if_case:w \int_eval:n {#2}
2661       { }
2662       \or: { ##1 }
2663       \or: { ##1##2 }
2664       \or: { ##1##2##3 }
2665       \or: { ##1##2##3##4 }
2666       \or: { ##1##2##3##4##5 }
2667       \or: { ##1##2##3##4##5##6 }
2668       \or: { ##1##2##3##4##5##6##7 }
2669       \or: { ##1##2##3##4##5##6##7##8 }
2670       \or: { ##1##2##3##4##5##6##7##8##9 }
2671       \else: { \c_false_bool }
2672     \fi:
2673   }
2674   {#1}
2675 }
2676 \cs_set_protected:Npn \_cs_parm_from_arg_count_test:nnF #1#2
2677 {
2678   \if_meaning:w \c_false_bool #1
2679     \exp_after:wN \use_ii:nn
2680   \else:
2681     \exp_after:wN \use_i:nn
2682   \fi:
2683   { #2 {#1} }
2684 }

```

(End definition for `_kernel_cs_parm_from_arg_count:nnF` and `_cs_parm_from_arg_count_test:nnF`.)

5.15 Defining functions from a given number of arguments

2685 `<@@=cs>`

`_cs_count_signature:N` Counting the number of tokens in the signature, *i.e.*, the number of arguments the function should take. Since this is not used in any time-critical function, we simply use `\tl_count:n` if there is a signature, otherwise `-1` arguments to signal an error. We need a variant form right away.

```
2686 \cs_new:Npn \_cs_count_signature:N #1
2687 { \exp_args:Nf \_cs_count_signature:n { \cs_split_function:N #1 } }
2688 \cs_new:Npn \_cs_count_signature:n #1
2689 { \int_eval:n { \_cs_count_signature:nnN #1 } }
2690 \cs_new:Npn \_cs_count_signature:nnN #1#2#3
2691 {
2692   \if_meaning:w \c_true_bool #3
2693     \tl_count:n {#2}
2694   \else:
2695     -1
2696   \fi:
2697 }
2698 \cs_new:Npn \_cs_count_signature:c
2699 { \exp_args:Nc \_cs_count_signature:N }
```

(End definition for `_cs_count_signature:N`, `_cs_count_signature:n`, and `_cs_count_signature:nnN`.)

`\cs_generate_from_arg_count:NNnn`
`\cs_generate_from_arg_count:cNnn`
`\cs_generate_from_arg_count:Ncnn`

We provide a constructor function for defining functions with a given number of arguments. For this we need to choose the correct parameter text and then use that when defining. Since TeX supports from zero to nine arguments, we use a simple switch to choose the correct parameter text, ensuring the result is returned after finishing the conditional. If it is not between zero and nine, we throw an error.

1: function to define, 2: with what to define it, 3: the number of args it requires and 4: the replacement text

```
2700 \cs_new_protected:Npn \cs_generate_from_arg_count:NNnn #1#2#3#4
2701 {
2702   \_kernel_cs_parm_from_arg_count:nnF { \use:nnn #2 #1 } {#3}
2703   {
2704     \_kernel_msg_error:nxxx { kernel } { bad-number-of-arguments }
2705     { \token_to_str:N #1 } { \int_eval:n {#3} }
2706     \use_none:n
2707   }
2708   {#4}
2709 }
```

A variant form we need right away, plus one which is used elsewhere but which is most logically created here.

```
2710 \cs_new_protected:Npn \cs_generate_from_arg_count:cNnn
2711 { \exp_args:Nc \cs_generate_from_arg_count:NNnn }
2712 \cs_new_protected:Npn \cs_generate_from_arg_count:Ncnn
2713 { \exp_args:Nnc \cs_generate_from_arg_count:NNnn }
```

(End definition for `\cs_generate_from_arg_count:NNnn`. This function is documented on page 14.)

5.16 Using the signature to define functions

2714 <@@=cs>

We can now combine some of the tools we have to provide a simple interface for defining functions, where the number of arguments is read from the signature. For instance, `\cs_set:Nn \foo_bar:nn {#1,#2}`.

We want to define `\cs_set:Nn` as

```

\cs_set:Nn
\cs_set:Nx
\cs_set_nopar:Nn
\cs_set_nopar:Nx
\cs_set_protected:Nn
\cs_set_protected:Nx
\cs_set_protected_nopar:Nn
\cs_set_protected_nopar:Nx
\cs_gset:Nn
\cs_gset:Nx
\cs_gset_nopar:Nn
\cs_gset_nopar:Nx
\cs_gset_protected:Nn
\cs_gset_protected:Nx
\cs_gset_protected_nopar:Nn
\cs_gset_protected_nopar:Nx
\cs_new:Nn
\cs_new:Nx
\cs_new_nopar:Nn
\cs_new_nopar:Nx
\cs_new_protected:Nn
\cs_new_protected:Nx
\cs_new_protected_nopar:Nn
\cs_new_protected_nopar:Nx

```

In short, to define `\cs_set:Nn` we need just use `\cs_set:Npn`, everything else is the same for each variant. Therefore, we can make it simpler by temporarily defining a function to do this for us.

```

2715 \cs_set:Npn \__cs_tmp:w #1#2#3
2716 {
2717   \cs_new_protected:cpx { cs_ #1 : #2 }
2718   {
2719     \exp_not:N \__cs_generate_from_signature:NNn
2720     \exp_after:wN \exp_not:N \cs:w cs_ #1 : #3 \cs_end:
2721   }
2722 }
2723 \cs_new_protected:Npn \__cs_generate_from_signature:NNn #1#2
2724 {
2725   \use:x
2726   {
2727     \__cs_generate_from_signature:nnNNNn
2728     \cs_split_function:N #2
2729   }
2730   #1 #2
2731 }
2732 \cs_new_protected:Npn \__cs_generate_from_signature:nnNNNn #1#2#3#4#5#6
2733 {
2734   \bool_if:NTF #3
2735   {
2736     \str_if_eq:eeF { }
2737     { \tl_map_function:nN {#2} \__cs_generate_from_signature:n }
2738     {
2739       \__kernel_msg_error:nnx { kernel } { non-base-function }
2740       { \token_to_str:N #5 }
2741     }
2742     \cs_generate_from_arg_count:NNnn
2743     #5 #4 { \tl_count:n {#2} } {#6}
2744   }
2745   {
2746     \__kernel_msg_error:nnx { kernel } { missing-colon }
2747     { \token_to_str:N #5 }
2748   }
2749 }
2750 \cs_new:Npn \__cs_generate_from_signature:n #1

```

```

2751 {
2752     \if:w n #1 \else: \if:w N #1 \else:
2753     \if:w T #1 \else: \if:w F #1 \else: #1 \fi: \fi: \fi: \fi:
2754 }

```

Then we define the 24 variants beginning with N.

```

2755 \__cs_tmp:w { set } { Nn } { Npn }
2756 \__cs_tmp:w { set } { Nx } { Npx }
2757 \__cs_tmp:w { set_nopar } { Nn } { Npn }
2758 \__cs_tmp:w { set_nopar } { Nx } { Npx }
2759 \__cs_tmp:w { set_protected } { Nn } { Npn }
2760 \__cs_tmp:w { set_protected } { Nx } { Npx }
2761 \__cs_tmp:w { set_protected_nopar } { Nn } { Npn }
2762 \__cs_tmp:w { set_protected_nopar } { Nx } { Npx }
2763 \__cs_tmp:w { gset } { Nn } { Npn }
2764 \__cs_tmp:w { gset } { Nx } { Npx }
2765 \__cs_tmp:w { gset_nopar } { Nn } { Npn }
2766 \__cs_tmp:w { gset_nopar } { Nx } { Npx }
2767 \__cs_tmp:w { gset_protected } { Nn } { Npn }
2768 \__cs_tmp:w { gset_protected } { Nx } { Npx }
2769 \__cs_tmp:w { gset_protected_nopar } { Nn } { Npn }
2770 \__cs_tmp:w { gset_protected_nopar } { Nx } { Npx }
2771 \__cs_tmp:w { new } { Nn } { Npn }
2772 \__cs_tmp:w { new } { Nx } { Npx }
2773 \__cs_tmp:w { new_nopar } { Nn } { Npn }
2774 \__cs_tmp:w { new_nopar } { Nx } { Npx }
2775 \__cs_tmp:w { new_protected } { Nn } { Npn }
2776 \__cs_tmp:w { new_protected } { Nx } { Npx }
2777 \__cs_tmp:w { new_protected_nopar } { Nn } { Npn }
2778 \__cs_tmp:w { new_protected_nopar } { Nx } { Npx }

```

(End definition for \cs_set:Nn and others. These functions are documented on page 13.)

\cs_set:cn The 24 c variants simply use \exp_args:Nc.

\cs_set:cx 2779 \cs_set:Npn __cs_tmp:w #1#2

\cs_set_nopar:cn 2780 {

\cs_set_nopar:cx 2781 \cs_new_protected:cpx { cs_ #1 : c #2 }

\cs_set_protected:cn 2782 {

\cs_set_protected:cx 2783 \exp_not:N \exp_args:Nc

\cs_set_protected_nopar:cn 2784 \exp_after:wN \exp_not:N \cs:w cs_ #1 : N #2 \cs_end:

\cs_set_protected_nopar:cx 2785 }

\cs_gset:cn 2786 }

\cs_gset:cx 2787 __cs_tmp:w { set } { n }

\cs_gset_nopar:cn 2788 __cs_tmp:w { set } { x }

\cs_gset_nopar:cx 2789 __cs_tmp:w { set_nopar } { n }

\cs_gset_protected:cn 2790 __cs_tmp:w { set_nopar } { x }

\cs_gset_protected:cx 2791 __cs_tmp:w { set_protected } { n }

\cs_gset_protected_nopar:cn 2792 __cs_tmp:w { set_protected } { x }

\cs_gset_protected_nopar:cx 2793 __cs_tmp:w { set_protected_nopar } { n }

\cs_new:cn 2794 __cs_tmp:w { set_protected_nopar } { x }

\cs_new:cx 2795 __cs_tmp:w { gset } { n }

\cs_new_nopar:cn 2796 __cs_tmp:w { gset } { x }

\cs_new_nopar:cx 2797 __cs_tmp:w { gset_nopar } { n }

\cs_new_protected:cn 2798 __cs_tmp:w { gset_nopar } { x }

\cs_new_protected:cx 2799 __cs_tmp:w { gset_protected } { n }

\cs_new_protected_nopar:cn

\cs_new_protected_nopar:cx

```

2800 \__cs_tmp:w { gset_protected } { x }
2801 \__cs_tmp:w { gset_protected_nopar } { n }
2802 \__cs_tmp:w { gset_protected_nopar } { x }
2803 \__cs_tmp:w { new } { n }
2804 \__cs_tmp:w { new } { x }
2805 \__cs_tmp:w { new_nopar } { n }
2806 \__cs_tmp:w { new_nopar } { x }
2807 \__cs_tmp:w { new_protected } { n }
2808 \__cs_tmp:w { new_protected } { x }
2809 \__cs_tmp:w { new_protected_nopar } { n }
2810 \__cs_tmp:w { new_protected_nopar } { x }

```

(End definition for \cs_set:Nn. This function is documented on page 13.)

5.17 Checking control sequence equality

\cs_if_eq_p:NN Check if two control sequences are identical.

```

\cs_if_eq_p:cN 2811 \prg_new_conditional:Npnn \cs_if_eq:NN #1#2 { p , T , F , TF }
\cs_if_eq_p:Nc 2812 {
\cs_if_eq_p:cc 2813   \if_meaning:w #1#2
\cs_if_eq:NNTF 2814   \prg_return_true: \else: \prg_return_false: \fi:
\cs_if_eq:cNTF 2815 }
\cs_if_eq:NcTF 2816 \cs_new:Npn \cs_if_eq_p:cN { \exp_args:Nc \cs_if_eq_p:NN }
\cs_if_eq:ccTF 2817 \cs_new:Npn \cs_if_eq:cNTF { \exp_args:Nc \cs_if_eq:NNTF }
2818 \cs_new:Npn \cs_if_eq:cNT { \exp_args:Nc \cs_if_eq:NNT }
2819 \cs_new:Npn \cs_if_eq:cNF { \exp_args:Nc \cs_if_eq:NNF }
2820 \cs_new:Npn \cs_if_eq_p:Nc { \exp_args:NNc \cs_if_eq_p:NN }
2821 \cs_new:Npn \cs_if_eq:NcTF { \exp_args:NNc \cs_if_eq:NNTF }
2822 \cs_new:Npn \cs_if_eq:NcT { \exp_args:NNc \cs_if_eq:NNT }
2823 \cs_new:Npn \cs_if_eq:NcF { \exp_args:NNc \cs_if_eq:NNF }
2824 \cs_new:Npn \cs_if_eq_p:cc { \exp_args:Ncc \cs_if_eq_p:NN }
2825 \cs_new:Npn \cs_if_eq:ccTF { \exp_args:Ncc \cs_if_eq:NNTF }
2826 \cs_new:Npn \cs_if_eq:ccT { \exp_args:Ncc \cs_if_eq:NNT }
2827 \cs_new:Npn \cs_if_eq:ccF { \exp_args:Ncc \cs_if_eq:NNF }

```

(End definition for \cs_if_eq:NNTF. This function is documented on page 22.)

5.18 Diagnostic functions

```

2828 <@@=kernel>
\__kernel_chk_defined:NT Error if the variable #1 is not defined.
2829 \cs_new_protected:Npn \__kernel_chk_defined:NT #1#2
2830 {
2831   \cs_if_exist:NTF #1
2832   {#2}
2833   {
2834     \__kernel_msg_error:nxx { kernel } { variable-not-defined }
2835     { \token_to_str:N #1 }
2836   }
2837 }

```

(End definition for __kernel_chk_defined:NT.)

Simply using the `\show` primitive does not allow for line-wrapping, so instead use `\tl_show:n` and `\tl_log:n` (defined in `l3tl` and that performs line-wrapping). This displays `>~⟨variable⟩=⟨value⟩`. We expand the value before-hand as otherwise some integers (such as `\currentgrouplevel` or `\currentgrouptype`) altered by the line-wrapping code would show wrong values.

```

\__kernel_register_show:N
\__kernel_register_show:c
\__kernel_register_log:N
\__kernel_register_log:c
  \__kernel_register_show_aux:NN
  \__kernel_register_show_aux:nNN
2838 \cs_new_protected:Npn \__kernel_register_show:N
2839   { \__kernel_register_show_aux:NN \tl_show:n }
2840 \cs_new_protected:Npn \__kernel_register_show:c
2841   { \exp_args:Nc \__kernel_register_show:N }
2842 \cs_new_protected:Npn \__kernel_register_log:N
2843   { \__kernel_register_show_aux:NN \tl_log:n }
2844 \cs_new_protected:Npn \__kernel_register_log:c
2845   { \exp_args:Nc \__kernel_register_log:N }
2846 \cs_new_protected:Npn \__kernel_register_show_aux:NN #1#2
2847   {
2848     \__kernel_chk_defined:NT #2
2849     {
2850       \exp_args:No \__kernel_register_show_aux:nNN
2851       { \tex_the:D #2 } #2 #1
2852     }
2853   }
2854 \cs_new_protected:Npn \__kernel_register_show_aux:nNN #1#2#3
2855   { \exp_args:No #3 { \token_to_str:N #2 = #1 } }

```

(End definition for `__kernel_register_show:N` and others.)

Some control sequences have a very long name or meaning. Thus, simply using TeX's primitive `\show` could lead to overlong lines. The output of this primitive is mimicked to some extent, then the re-built string is given to `\tl_show:n` or `\tl_log:n` for line-wrapping. We must expand the meaning before passing it to the wrapping code as otherwise we would wrongly see the definitions that are in place there. To get correct escape characters, set the `\escapechar` in a group; this also localizes the assignment performed by x-expansion. The `\cs_show:c` and `\cs_log:c` commands convert their argument to a control sequence within a group to avoid showing `\relax` for undefined control sequences.

```

\cs_show:N
\cs_show:c
\cs_log:N
\cs_log:c
\__kernel_show:NN
2856 \cs_new_protected:Npn \cs_show:N { \__kernel_show:NN \tl_show:n }
2857 \cs_new_protected:Npn \cs_show:c
2858   { \group_begin: \exp_args:NNc \group_end: \cs_show:N }
2859 \cs_new_protected:Npn \cs_log:N { \__kernel_show:NN \tl_log:n }
2860 \cs_new_protected:Npn \cs_log:c
2861   { \group_begin: \exp_args:NNc \group_end: \cs_log:N }
2862 \cs_new_protected:Npn \__kernel_show:NN #1#2
2863   {
2864     \group_begin:
2865       \int_set:Nn \tex_escapechar:D { '\ }
2866       \exp_args:NNx
2867       \group_end:
2868       #1 { \token_to_str:N #2 = \cs_meaning:N #2 }
2869   }

```

(End definition for `\cs_show:N`, `\cs_log:N`, and `__kernel_show:NN`. These functions are documented on page 16.)

5.19 Decomposing a macro definition

`\cs_prefix_spec:N` We sometimes want to test if a control sequence can be expanded to reveal a hidden value.
`\cs_argument_spec:N` However, we cannot just expand the macro blindly as it may have arguments and none
`\cs_replacement_spec:N` might be present. Therefore we define these functions to pick either the prefix(es), the
`__kernel_prefix_arg_replacement:wN` argument specification, or the replacement text from a macro. All of this information is
returned as characters with catcode 12. If the token in question isn't a macro, the token
`\scan_stop:` is returned instead.

```

2870 \use:x
2871 {
2872   \exp_not:n { \cs_new:Npn \__kernel_prefix_arg_replacement:wN #1 }
2873   \tl_to_str:n { macro : } \exp_not:n { #2 -> #3 \s__kernel_stop #4 }
2874 }
2875 { #4 {#1} {#2} {#3} }
2876 \cs_new:Npn \cs_prefix_spec:N #1
2877 {
2878   \token_if_macro:NTF #1
2879   {
2880     \exp_after:wN \__kernel_prefix_arg_replacement:wN
2881     \token_to_meaning:N #1 \s__kernel_stop \use_i:nnn
2882   }
2883   { \scan_stop: }
2884 }
2885 \cs_new:Npn \cs_argument_spec:N #1
2886 {
2887   \token_if_macro:NTF #1
2888   {
2889     \exp_after:wN \__kernel_prefix_arg_replacement:wN
2890     \token_to_meaning:N #1 \s__kernel_stop \use_ii:nnn
2891   }
2892   { \scan_stop: }
2893 }
2894 \cs_new:Npn \cs_replacement_spec:N #1
2895 {
2896   \token_if_macro:NTF #1
2897   {
2898     \exp_after:wN \__kernel_prefix_arg_replacement:wN
2899     \token_to_meaning:N #1 \s__kernel_stop \use_iii:nnn
2900   }
2901   { \scan_stop: }
2902 }
```

(End definition for `\cs_prefix_spec:N` and others. These functions are documented on page 18.)

5.20 Doing nothing functions

`\prg_do_nothing:` This does not fit anywhere else!

```

2903 \cs_new:Npn \prg_do_nothing: { }
```

(End definition for `\prg_do_nothing:`. This function is documented on page 9.)

5.21 Breaking out of mapping functions

2904 `<@@=prg>`

`\prg_break_point:Nn` In inline mappings, the nesting level must be reset at the end of the mapping, even when the user decides to break out. This is done by putting the code that must be performed as an argument of `__prg_break_point:Nn`. The breaking functions are then defined to jump to that point and perform the argument of `__prg_break_point:Nn`, before the user's code (if any). There is a check that we close the correct loop, otherwise we continue breaking.

```
2905 \cs_new_eq:NN \prg_break_point:Nn \use_ii:nn
2906 \cs_new:Npn \prg_map_break:Nn #1#2#3 \prg_break_point:Nn #4#5
2907 {
2908   #5
2909   \if_meaning:w #1 #4
2910     \exp_after:wN \use_iii:nnn
2911   \fi:
2912   \prg_map_break:Nn #1 {#2}
2913 }
```

(End definition for `\prg_break_point:Nn` and `\prg_map_break:Nn`. These functions are documented on page 112.)

`\prg_break_point:` Very simple analogues of `\prg_break_point:Nn` and `\prg_map_break:Nn`, for use in fast short-term recursions which are not mappings, do not need to support nesting, and in `\prg_break:` which nothing has to be done at the end of the loop.

```
2914 \cs_new_eq:NN \prg_break_point: \prg_do_nothing:
2915 \cs_new:Npn \prg_break: #1 \prg_break_point: { }
2916 \cs_new:Npn \prg_break:n #1#2 \prg_break_point: {#1}
```

(End definition for `\prg_break_point:`, `\prg_break:`, and `\prg_break:n`. These functions are documented on page 113.)

5.22 Starting a paragraph

`\mode_leave_vertical:` The approach here is different to that used by L^AT_EX 2_ε or plain T_EX, which unbox a void box to force horizontal mode. That inserts the `\everypar` tokens *before* the re-inserted unboxing tokens. The approach here uses either the `\quitvmode` primitive or the equivalent protected macro. In vertical mode, the `\indent` primitive is inserted: this will switch to horizontal mode and insert `\everypar` tokens and nothing else. Unlike the L^AT_EX 2_ε version, the availability of ε -T_EX means using a mode test can be done at for example the start of an `\halign`.

```
2917 \cs_new_protected:Npn \mode_leave_vertical:
2918 {
2919   \if_mode_vertical:
2920     \exp_after:wN \tex_indent:D
2921   \fi:
2922 }
```

(End definition for `\mode_leave_vertical:`. This function is documented on page 24.)

2923 `</initex | package>`

6 l3expan implementation

2924 `*initex | package)`

2925 `\@@=exp)`

`\l__exp_internal_tl` The `\exp_` module has its private variable to temporarily store the result of `x`-type argument expansion. This is done to avoid interference with other functions using temporary variables.

(End definition for \l__exp_internal_tl.)

`\exp_after:wN` These are defined in `l3basics`, as they are needed “early”. This is just a reminder of that fact!

`\exp_not:N`

`\exp_not:n`

(End definition for \exp_after:wN, \exp_not:N, and \exp_not:n. These functions are documented on page 33.)

6.1 General expansion

In this section a general mechanism for defining functions that handle arguments is defined. These general expansion functions are expandable unless `x` is used. (Any version of `x` is going to have to use one of the L^AT_EX3 names for `\cs_set:Npx` at some point, and so is never going to be expandable.)

The definition of expansion functions with this technique happens in section 6.8. In section 6.2 some common cases are coded by a more direct method for efficiency, typically using calls to `\exp_after:wN`.

`\l__exp_internal_tl` This scratch token list variable is defined in `l3basics`.

(End definition for \l__exp_internal_tl.)

This code uses internal functions with names that start with `\::` to perform the expansions. All macros are `long` since the tokens undergoing expansion may be arbitrary user input.

An argument manipulator `\::⟨Z⟩` always has signature `#1\:::#2#3` where `#1` holds the remaining argument manipulations to be performed, `\:::` serves as an end marker for the list of manipulations, `#2` is the carried over result of the previous expansion steps and `#3` is the argument about to be processed. One exception to this rule is `\::p`, which has to grab an argument delimited by a left brace.

`__exp_arg_next:nnn` `#1` is the result of an expansion step, `#2` is the remaining argument manipulations and `#3` is the current result of the expansion chain. This auxiliary function moves `#1` back after `#3` in the input stream and checks if any expansion is left to be done by calling `#2`. In by far the most cases we need to add a set of braces to the result of an argument manipulation so it is more effective to do it directly here. Actually, so far only the `c` of the final argument manipulation variants does not require a set of braces.

2926 `\cs_new:Npn __exp_arg_next:nnn #1#2#3 { #2 \::: { #3 {#1} } }`

2927 `\cs_new:Npn __exp_arg_next:Nnn #1#2#3 { #2 \::: { #3 #1 } }`

(End definition for __exp_arg_next:nnn and __exp_arg_next:Nnn.)

`\:::` The end marker is just another name for the identity function.

2928 `\cs_new:Npn \::: #1 {#1}`

(End definition for \:::. This function is documented on page 37.)

\::n This function is used to skip an argument that doesn't need to be expanded.

```
2929 \cs_new:Npn \::n #1 \::: #2#3 { #1 \::: { #2 {#3} } }
```

(End definition for \::n. This function is documented on page 37.)

\::N This function is used to skip an argument that consists of a single token and doesn't need to be expanded.

```
2930 \cs_new:Npn \::N #1 \::: #2#3 { #1 \::: {#2#3} }
```

(End definition for \::N. This function is documented on page 37.)

\::p This function is used to skip an argument that is delimited by a left brace and doesn't need to be expanded. It is not wrapped in braces in the result.

```
2931 \cs_new:Npn \::p #1 \::: #2#3# { #1 \::: {#2#3} }
```

(End definition for \::p. This function is documented on page 37.)

\::c This function is used to skip an argument that is turned into a control sequence without expansion.

```
2932 \cs_new:Npn \::c #1 \::: #2#3
2933 { \exp_after:wN \__exp_arg_next:Nnn \cs:w #3 \cs_end: {#1} {#2} }
```

(End definition for \::c. This function is documented on page 37.)

\::o This function is used to expand an argument once.

```
2934 \cs_new:Npn \::o #1 \::: #2#3
2935 { \exp_after:wN \__exp_arg_next:nnn \exp_after:wN {#3} {#1} {#2} }
```

(End definition for \::o. This function is documented on page 37.)

\::e With the `\expanded` primitive available, just expand. Otherwise defer to `\exp_args:Ne` implemented later.

```
2936 \cs_if_exist:NTF \tex_expanded:D
2937 {
2938   \cs_new:Npn \::e #1 \::: #2#3
2939   { \tex_expanded:D { \exp_not:n { #1 \::: } { \exp_not:n {#2} {#3} } } }
2940 }
2941 {
2942   \cs_new:Npn \::e #1 \::: #2#3
2943   { \exp_args:Ne \__exp_arg_next:nnn {#3} {#1} {#2} }
2944 }
```

(End definition for \::e. This function is documented on page 37.)

\::f This function is used to expand a token list until the first unexpandable token is found. This is achieved through `\exp:w \exp_end_continue_f:w` that expands everything in its way following it. This scanning procedure is terminated once the expansion hits something non-expandable (if that is a space it is removed). We introduce `\exp_stop_f:` to mark such an end-of-expansion marker. For example, f-expanding `\cs_set_eq:Nc \aaa { b \l_tmpa_tl b }` where `\l_tmpa_tl` contains the characters `lur` gives `\tex_let:D \aaa = \blurb` which then turns out to start with the non-expandable token `\tex_let:D`. Since the expansion of `\exp:w \exp_end_continue_f:w` is empty, we wind up with a fully expanded list, only `TEX` has not tried to execute any of

the non-expandable tokens. This is what differentiates this function from the `x` argument type.

```

2945 \cs_new:Npn \::f #1 \::: #2#3
2946 {
2947   \exp_after:wN \__exp_arg_next:nnn
2948   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2949   {#1} {#2}
2950 }
2951 \use:nn { \cs_new_eq:NN \exp_stop_f: } { ~ }
```

(End definition for `\::f` and `\exp_stop_f:`. These functions are documented on page 37.)

\::x This function is used to expand an argument fully. We build in the expansion of `__exp_arg_next:nnn`.

```

2952 \cs_new_protected:Npn \::x #1 \::: #2#3
2953 {
2954   \cs_set_nopar:Npx \l__exp_internal_tl
2955   { \exp_not:n { #1 \::: } { \exp_not:n {#2} {#3} } }
2956   \l__exp_internal_tl
2957 }
```

(End definition for `\::x`. This function is documented on page 37.)

\::v These functions return the value of a register, i.e., one of `tl`, `clist`, `int`, `skip`, `dim`, **\::V** `muskip`, or built-in TeX register. The `V` version expects a single token whereas `v` like `c` creates a `csname` from its argument given in braces and then evaluates it as if it was a `V`. The `\exp:w` sets off an expansion similar to an `f`-type expansion, which we terminate using `\exp_end:`. The argument is returned in braces.

```

2958 \cs_new:Npn \::V #1 \::: #2#3
2959 {
2960   \exp_after:wN \__exp_arg_next:nnn
2961   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2962   {#1} {#2}
2963 }
2964 \cs_new:Npn \::v #1 \::: #2#3
2965 {
2966   \exp_after:wN \__exp_arg_next:nnn
2967   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
2968   {#1} {#2}
2969 }
```

(End definition for `\::v` and `\::V`. These functions are documented on page 37.)

`__exp_eval_register:N` This function evaluates a register. Now a register might exist as one of two things: A parameter-less macro or a built-in TeX register such as `\count`. For the TeX registers we have to utilize a `\the` whereas for the macros we merely have to expand them once. The trick is to find out when to use `\the` and when not to. What we want here is to find out whether the token expands to something else when hit with `\exp_after:wN`. The technique is to compare the meaning of the token in question when it has been prefixed with `\exp_not:N` and the token itself. If it is a macro, the prefixed `\exp_not:N` temporarily turns it into the primitive `\scan_stop:`.

```

2970 \cs_new:Npn \__exp_eval_register:N #1
2971 {
2972   \exp_after:wN \if_meaning:w \exp_not:N #1 #1
```

If the token was not a macro it may be a malformed variable from a `c` expansion in which case it is equal to the primitive `\scan_stop:`. In that case we throw an error. We could let `TeX` do it for us but that would result in the rather obscure

```
! You can't use '\relax' after \the.
```

which while quite true doesn't give many hints as to what actually went wrong. We provide something more sensible.

```
2973     \if_meaning:w \scan_stop: #1
2974     \__exp_eval_error_msg:w
2975     \fi:
```

The next bit requires some explanation. The function must be initiated by `\exp:w` and we want to terminate this expansion chain by inserting the `\exp_end:` token. However, we have to expand the register `#1` before we do that. If it is a `TeX` register, we need to execute the sequence `\exp_after:wN \exp_end: \tex_the:D #1` and if it is a macro we need to execute `\exp_after:wN \exp_end: #1`. We therefore issue the longer of the two sequences and if the register is a macro, we remove the `\tex_the:D`.

```
2976     \else:
2977     \exp_after:wN \use_i_ii:nnn
2978     \fi:
2979     \exp_after:wN \exp_end: \tex_the:D #1
2980   }
2981 \cs_new:Npn \__exp_eval_register:c #1
2982 { \exp_after:wN \__exp_eval_register:N \cs:w #1 \cs_end: }
```

Clean up nicely, then call the undefined control sequence. The result is an error message looking like this:

```
! Undefined control sequence.
<argument> \LaTeX3 error:
                               Erroneous variable used!
1.55 \tl_set:Nv \l_tmpa_tl {undefined_tl}

2983 \cs_new:Npn \__exp_eval_error_msg:w #1 \tex_the:D #2
2984 {
2985     \fi:
2986     \fi:
2987     \__kernel_msg_expandable_error:nnn { kernel } { bad-variable } {#2}
2988     \exp_end:
2989 }
```

(End definition for `__exp_eval_register:N` and `__exp_eval_error_msg:w`.)

6.2 Hand-tuned definitions

One of the most important features of these functions is that they are fully expandable.

`\exp_args:Nc` In `l3basics`.

`\exp_args:cc` *(End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 29.)*

`\exp_args:NNc` Here are the functions that turn their argument into csnames but are expandable.

```

\exp_args:Ncc
\exp_args:Nccc
2990 \cs_new:Npn \exp_args:NNc #1#2#3
2991 { \exp_after:wN #1 \exp_after:wN #2 \cs:w # 3\cs_end: }
2992 \cs_new:Npn \exp_args:Ncc #1#2#3
2993 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: \cs:w #3 \cs_end: }
2994 \cs_new:Npn \exp_args:Nccc #1#2#3#4
2995 {
2996   \exp_after:wN #1
2997   \cs:w #2 \exp_after:wN \cs_end:
2998   \cs:w #3 \exp_after:wN \cs_end:
2999   \cs:w #4 \cs_end:
3000 }
```

(End definition for `\exp_args:NNc`, `\exp_args:Ncc`, and `\exp_args:Nccc`. These functions are documented on page 31.)

`\exp_args:No` Those lovely runs of expansion!

```

\exp_args:NNo
\exp_args:NNNo
3001 \cs_new:Npn \exp_args:No #1#2 { \exp_after:wN #1 \exp_after:wN {#2} }
3002 \cs_new:Npn \exp_args:NNo #1#2#3
3003 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN {#3} }
3004 \cs_new:Npn \exp_args:NNNo #1#2#3#4
3005 { \exp_after:wN #1 \exp_after:wN#2 \exp_after:wN #3 \exp_after:wN {#4} }
```

(End definition for `\exp_args:No`, `\exp_args:NNo`, and `\exp_args:NNNo`. These functions are documented on page 30.)

`\exp_args:Ne` When the `\expanded` primitive is available, use it. Otherwise use `__exp_e:nn`, defined later, to fully expand tokens.

```

3006 \cs_if_exist:NTF \tex_expanded:D
3007 {
3008   \cs_new:Npn \exp_args:Ne #1#2
3009   { \exp_after:wN #1 \tex_expanded:D { {#2} } }
3010 }
3011 {
3012   \cs_new:Npn \exp_args:Ne #1#2
3013   {
3014     \exp_after:wN #1 \exp_after:wN
3015     { \exp:w \__exp_e:nn {#2} { } }
3016   }
3017 }
```

(End definition for `\exp_args:Ne`. This function is documented on page 30.)

`\exp_args:Nf`
`\exp_args:Nv`
`\exp_args:Nv`

```

3018 \cs_new:Npn \exp_args:Nf #1#2
3019 { \exp_after:wN #1 \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } }
3020 \cs_new:Npn \exp_args:Nv #1#2
3021 {
3022   \exp_after:wN #1 \exp_after:wN
3023   { \exp:w \__exp_eval_register:c {#2} }
3024 }
3025 \cs_new:Npn \exp_args:Nv #1#2
3026 {
3027   \exp_after:wN #1 \exp_after:wN
3028   { \exp:w \__exp_eval_register:N #2 }
3029 }
```


(End definition for `\exp_args:Nf`, `\exp_args:Nv`, and `\exp_args:Nv`. These functions are documented on page 30.)

`\exp_args:NNV` Some more hand-tuned function with three arguments. If we forced that an `o` argument always has braces, we could implement `\exp_args:Nco` with less tokens and only two arguments.

```

3030 \cs_new:Npn \exp_args:NNV #1#2#3
3031 {
3032   \exp_after:wN #1
3033   \exp_after:wN #2
3034   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
3035 }
3036 \cs_new:Npn \exp_args:NNv #1#2#3
3037 {
3038   \exp_after:wN #1
3039   \exp_after:wN #2
3040   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
3041 }
3042 \cs_if_exist:NTF \tex_expanded:D
3043 {
3044   \cs_new:Npn \exp_args:NNe #1#2#3
3045   {
3046     \exp_after:wN #1
3047     \exp_after:wN #2
3048     \tex_expanded:D { {#3} }
3049   }
3050 }
3051 { \cs_new:Npn \exp_args:NNe { \::N \::e \::: } }
3052 \cs_new:Npn \exp_args:NNf #1#2#3
3053 {
3054   \exp_after:wN #1
3055   \exp_after:wN #2
3056   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
3057 }
3058 \cs_new:Npn \exp_args:Nco #1#2#3
3059 {
3060   \exp_after:wN #1
3061   \cs:w #2 \exp_after:wN \cs_end:
3062   \exp_after:wN {#3}
3063 }
3064 \cs_new:Npn \exp_args:NcV #1#2#3
3065 {
3066   \exp_after:wN #1
3067   \cs:w #2 \exp_after:wN \cs_end:
3068   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
3069 }
3070 \cs_new:Npn \exp_args:Ncv #1#2#3
3071 {
3072   \exp_after:wN #1
3073   \cs:w #2 \exp_after:wN \cs_end:
3074   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
3075 }
3076 \cs_new:Npn \exp_args:Ncf #1#2#3
3077 {

```

```

3078     \exp_after:wN #1
3079     \cs:w #2 \exp_after:wN \cs_end:
3080     \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
3081   }
3082 \cs_new:Npn \exp_args:NVV #1#2#3
3083 {
3084     \exp_after:wN #1
3085     \exp_after:wN { \exp:w \exp_after:wN
3086         \__exp_eval_register:N \exp_after:wN #2 \exp_after:wN }
3087     \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
3088 }

```

(End definition for `\exp_args:NNV` and others. These functions are documented on page 31.)

`\exp_args:NNNV` A few more that we can hand-tune.

```

\exp_args:NcNc 3089 \cs_new:Npn \exp_args:NNNV #1#2#3#4
\exp_args:NcNo 3090 {
\exp_args:Ncco 3091     \exp_after:wN #1
3092     \exp_after:wN #2
3093     \exp_after:wN #3
3094     \exp_after:wN { \exp:w \__exp_eval_register:N #4 }
3095 }
3096 \cs_new:Npn \exp_args:NcNc #1#2#3#4
3097 {
3098     \exp_after:wN #1
3099     \cs:w #2 \exp_after:wN \cs_end:
3100     \exp_after:wN #3
3101     \cs:w #4 \cs_end:
3102 }
3103 \cs_new:Npn \exp_args:NcNo #1#2#3#4
3104 {
3105     \exp_after:wN #1
3106     \cs:w #2 \exp_after:wN \cs_end:
3107     \exp_after:wN #3
3108     \exp_after:wN {#4}
3109 }
3110 \cs_new:Npn \exp_args:Ncco #1#2#3#4
3111 {
3112     \exp_after:wN #1
3113     \cs:w #2 \exp_after:wN \cs_end:
3114     \cs:w #3 \exp_after:wN \cs_end:
3115     \exp_after:wN {#4}
3116 }

```

(End definition for `\exp_args:NNNV` and others. These functions are documented on page 32.)

`\exp_args:Nx`

```

3117 \cs_new_protected:Npn \exp_args:Nx #1#2
3118 { \use:x { \exp_not:N #1 {#2} } }

```

(End definition for `\exp_args:Nx`. This function is documented on page 31.)

6.3 Last-unbraced versions

There are a few places where the last argument needs to be available unbraced. First some helper macros.

```

\__exp_arg_last_unbraced:nn
\::o_unbraced
\::V_unbraced
\::v_unbraced
\::e_unbraced
\::f_unbraced
\::x_unbraced
3119 \cs_new:Npn \__exp_arg_last_unbraced:nn #1#2 { #2#1 }
3120 \cs_new:Npn \::o_unbraced \::: #1#2
3121 { \exp_after:wN \__exp_arg_last_unbraced:nn \exp_after:wN {#2} {#1} }
3122 \cs_new:Npn \::V_unbraced \::: #1#2
3123 {
3124   \exp_after:wN \__exp_arg_last_unbraced:nn
3125   \exp_after:wN { \exp:w \__exp_eval_register:N #2 } {#1}
3126 }
3127 \cs_new:Npn \::v_unbraced \::: #1#2
3128 {
3129   \exp_after:wN \__exp_arg_last_unbraced:nn
3130   \exp_after:wN { \exp:w \__exp_eval_register:c {#2} } {#1}
3131 }
3132 \cs_if_exist:NTF \tex_expanded:D
3133 {
3134   \cs_new:Npn \::e_unbraced \::: #1#2
3135   { \tex_expanded:D { \exp_not:n {#1} #2 } }
3136 }
3137 {
3138   \cs_new:Npn \::e_unbraced \::: #1#2
3139   { \exp:w \__exp_e:nn {#2} {#1} }
3140 }
3141 \cs_new:Npn \::f_unbraced \::: #1#2
3142 {
3143   \exp_after:wN \__exp_arg_last_unbraced:nn
3144   \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } {#1}
3145 }
3146 \cs_new_protected:Npn \::x_unbraced \::: #1#2
3147 {
3148   \cs_set_nopar:Npx \l__exp_internal_tl { \exp_not:n {#1} #2 }
3149   \l__exp_internal_tl
3150 }

```

(End definition for `__exp_arg_last_unbraced:nn` and others. These functions are documented on page 37.)

Now the business end: most of these are hand-tuned for speed, but the general system is in place.

```

\exp_last_unbraced:No
\exp_last_unbraced:Nv
\exp_last_unbraced:Nv
\exp_last_unbraced:Ne
\exp_last_unbraced:Nf
\exp_last_unbraced:NNo
\exp_last_unbraced:NNv
\exp_last_unbraced:NNf
\exp_last_unbraced:Nco
\exp_last_unbraced:NcV
\exp_last_unbraced:NNNo
\exp_last_unbraced:NNNV
\exp_last_unbraced:NNNf
\exp_last_unbraced:Nno
\exp_last_unbraced:Noo
\exp_last_unbraced:Nfo
\exp_last_unbraced:NnNo
\exp_last_unbraced:NNNNo
\exp_last_unbraced:NNNNf
\exp_last_unbraced:Nx
3151 \cs_new:Npn \exp_last_unbraced:No #1#2 { \exp_after:wN #1 #2 }
3152 \cs_new:Npn \exp_last_unbraced:Nv #1#2
3153 { \exp_after:wN #1 \exp:w \__exp_eval_register:N #2 }
3154 \cs_new:Npn \exp_last_unbraced:Nv #1#2
3155 { \exp_after:wN #1 \exp:w \__exp_eval_register:c {#2} }
3156 \cs_if_exist:NTF \tex_expanded:D
3157 {
3158   \cs_new:Npn \exp_last_unbraced:Ne #1#2
3159   { \exp_after:wN #1 \tex_expanded:D {#2} }
3160 }
3161 { \cs_new:Npn \exp_last_unbraced:Ne { \::e_unbraced \::: } }
3162 \cs_new:Npn \exp_last_unbraced:Nf #1#2

```

```

3163 { \exp_after:wN #1 \exp:w \exp_end_continue_f:w #2 }
3164 \cs_new:Npn \exp_last_unbraced:NNo #1#2#3
3165 { \exp_after:wN #1 \exp_after:wN #2 #3 }
3166 \cs_new:Npn \exp_last_unbraced:NNV #1#2#3
3167 {
3168   \exp_after:wN #1
3169   \exp_after:wN #2
3170   \exp:w \__exp_eval_register:N #3
3171 }
3172 \cs_new:Npn \exp_last_unbraced:NNf #1#2#3
3173 {
3174   \exp_after:wN #1
3175   \exp_after:wN #2
3176   \exp:w \exp_end_continue_f:w #3
3177 }
3178 \cs_new:Npn \exp_last_unbraced:Nco #1#2#3
3179 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: #3 }
3180 \cs_new:Npn \exp_last_unbraced:NcV #1#2#3
3181 {
3182   \exp_after:wN #1
3183   \cs:w #2 \exp_after:wN \cs_end:
3184   \exp:w \__exp_eval_register:N #3
3185 }
3186 \cs_new:Npn \exp_last_unbraced:NNNo #1#2#3#4
3187 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 #4 }
3188 \cs_new:Npn \exp_last_unbraced:NNNV #1#2#3#4
3189 {
3190   \exp_after:wN #1
3191   \exp_after:wN #2
3192   \exp_after:wN #3
3193   \exp:w \__exp_eval_register:N #4
3194 }
3195 \cs_new:Npn \exp_last_unbraced:NNNf #1#2#3#4
3196 {
3197   \exp_after:wN #1
3198   \exp_after:wN #2
3199   \exp_after:wN #3
3200   \exp:w \exp_end_continue_f:w #4
3201 }
3202 \cs_new:Npn \exp_last_unbraced:Nno { \::n \::o_unbraced \::: }
3203 \cs_new:Npn \exp_last_unbraced:Noo { \::o \::o_unbraced \::: }
3204 \cs_new:Npn \exp_last_unbraced:Nfo { \::f \::o_unbraced \::: }
3205 \cs_new:Npn \exp_last_unbraced:NnNo { \::n \::N \::o_unbraced \::: }
3206 \cs_new:Npn \exp_last_unbraced:NNNNo #1#2#3#4#5
3207 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 \exp_after:wN #4 #5 }
3208 \cs_new:Npn \exp_last_unbraced:NNNNf #1#2#3#4#5
3209 {
3210   \exp_after:wN #1
3211   \exp_after:wN #2
3212   \exp_after:wN #3
3213   \exp_after:wN #4
3214   \exp:w \exp_end_continue_f:w #5
3215 }
3216 \cs_new_protected:Npn \exp_last_unbraced:Nx { \::x_unbraced \::: }

```

(End definition for `\exp_last_unbraced:No` and others. These functions are documented on page 33.)

If #2 is a single token then this can be implemented as

```
\cs_new:Npn \exp_last_two_unbraced:Noo #1 #2 #3
{ \exp_after:wN \exp_after:wN \exp_after:wN #1 \exp_after:wN #2 #3 }
```

However, for robustness this is not suitable. Instead, a bit of a shuffle is used to ensure that #2 can be multiple tokens.

```
3217 \cs_new:Npn \exp_last_two_unbraced:Noo #1#2#3
3218 { \exp_after:wN \__exp_last_two_unbraced:noN \exp_after:wN {#3} {#2} #1 }
3219 \cs_new:Npn \__exp_last_two_unbraced:noN #1#2#3
3220 { \exp_after:wN #3 #2 #1 }
```

(End definition for `\exp_last_two_unbraced:Noo` and `__exp_last_two_unbraced:noN`. This function is documented on page 33.)

6.4 Preventing expansion

`__kernel_exp_not:w` At the kernel level, we need the primitive behaviour to allow expansion *before* the brace group.

```
3221 \cs_new_eq:NN \__kernel_exp_not:w \tex_unexpanded:D
```

(End definition for `__kernel_exp_not:w`.)

`\exp_not:c` All these except `\exp_not:c` call the kernel-internal `__kernel_exp_not:w` namely `\tex_unexpanded:D`.

```
\exp_not:o \tex_unexpanded:D.
\exp_not:e 3222 \cs_new:Npn \exp_not:c #1 { \exp_after:wN \exp_not:N \cs:w #1 \cs_end: }
\exp_not:f 3223 \cs_new:Npn \exp_not:o #1 { \__kernel_exp_not:w \exp_after:wN {#1} }
\exp_not:V 3224 \cs_if_exist:NTF \tex_expanded:D
\exp_not:v 3225 {
3226   \cs_new:Npn \exp_not:e #1
3227   { \__kernel_exp_not:w \tex_expanded:D { {#1} } }
3228 }
3229 {
3230   \cs_new:Npn \exp_not:e
3231   { \__kernel_exp_not:w \exp_args:Ne \prg_do_nothing: }
3232 }
3233 \cs_new:Npn \exp_not:f #1
3234 { \__kernel_exp_not:w \exp_after:wN { \exp:w \exp_end_continue_f:w #1 } }
3235 \cs_new:Npn \exp_not:V #1
3236 {
3237   \__kernel_exp_not:w \exp_after:wN
3238   { \exp:w \__exp_eval_register:N #1 }
3239 }
3240 \cs_new:Npn \exp_not:v #1
3241 {
3242   \__kernel_exp_not:w \exp_after:wN
3243   { \exp:w \__exp_eval_register:c {#1} }
3244 }
```

(End definition for `\exp_not:c` and others. These functions are documented on page 34.)

6.5 Controlled expansion

```
\exp:w
\exp_end:
\exp_end_continue_f:w
\exp_end_continue_f:nw
```

To trigger a sequence of “arbitrarily” many expansions we need a method to invoke T_EX’s expansion mechanism in such a way that (a) we are able to stop it in a controlled manner and (b) the result of what triggered the expansion in the first place is null, i.e., that we do not get any unwanted side effects. There aren’t that many possibilities in T_EX; in fact the one explained below might well be the only one (as normally the result of expansion is not null).

The trick here is to make use of the fact that `\tex_romannumeral:D` expands the tokens following it when looking for a number and that its expansion is null if that number turns out to be zero or negative. So we use that to start the expansion sequence: `\exp:w` is set equal to `\tex_romannumeral:D` in `l3basics`. To stop the expansion sequence in a controlled way all we need to provide is a constant integer zero as part of expanded tokens. As this is an integer constant it immediately stops `\tex_romannumeral:D`’s search for a number. Again, the definition of `\exp_end:` as the integer constant zero is in `l3basics`. (Note that according to our specification all tokens we expand initiated by `\exp:w` are supposed to be expandable (as well as their replacement text in the expansion) so we will not encounter a “number” that actually result in a roman numeral being generated. Or if we do then the programmer made a mistake.)

If on the other hand we want to stop the initial expansion sequence but continue with an `f`-type expansion we provide the alphabetic constant `^^@` that also represents 0 but this time T_EX’s syntax for a *⟨number⟩* continues searching for an optional space (and it continues expansion doing that) — see T_EXbook page 269 for details.

```
3245 \group_begin:
3246   \tex_catcode:D ‘^^@ = 13
3247   \cs_new_protected:Npn \exp_end_continue_f:w { ‘^^@ }
```

If the above definition ever appears outside its proper context the active character `^^@` will be executed so we turn this into an error. The test for existence covers the (unlikely) case that some other code has already defined `^^@`: this is true for example for `xmltex.tex`.

```
3248   \if_cs_exist:N ^^@
3249   \else:
3250     \cs_new:Npn ^^@
3251       { \__kernel_msg_expandable_error:nn { kernel } { bad-exp-end-f } }
3252   \fi:
```

The same but grabbing an argument to remove spaces and braces.

```
3253   \cs_new:Npn \exp_end_continue_f:nw #1 { ‘^^@ #1 }
3254 \group_end:
```

(End definition for `\exp:w` and others. These functions are documented on page 36.)

6.6 Emulating e-type expansion

When the `\expanded` primitive is available it is used to implement `e`-type expansion; otherwise we emulate it.

```
3255 \cs_if_exist:NF \tex_expanded:D
3256 {
```

```
\__exp_e:nn
\__exp_e_end:nn
```

Repeatedly expand tokens, keeping track of fully-expanded tokens in the second argument to `__exp_e:nn`; this function eventually calls `__exp_e_end:nn` to leave `\exp_end:` in the input stream, followed by the result of the expansion. There are many special cases:

spaces, brace groups, `\noexpand`, `\unexpanded`, `\the`, `\primitive`. While we use brace tricks `\if_false: { \fi:`, the expansion of this function is always triggered by `\exp:w` so brace balance is eventually restored after that is hit with a single step of expansion. Otherwise we could not nest e-type expansions within each other.

```

3257 \cs_new:Npn \__exp_e:nn #1
3258 {
3259   \if_false: { \fi:
3260     \tl_if_head_is_N_type:nTF {#1}
3261     { \__exp_e:N }
3262     {
3263       \tl_if_head_is_group:nTF {#1}
3264       { \__exp_e_group:n }
3265       {
3266         \tl_if_empty:nTF {#1}
3267         { \exp_after:wN \__exp_e_end:nn }
3268         { \exp_after:wN \__exp_e_space:nn }
3269         \exp_after:wN { \if_false: } \fi:
3270       }
3271     }
3272     #1
3273   }
3274 }
3275 \cs_new:Npn \__exp_e_end:nn #1#2 { \exp_end: #2 }

```

(End definition for `__exp_e:nn` and `__exp_e_end:nn`.)

`__exp_e_space:nn` For an explicit space character, remove it by f-expansion and put it in the (future) output.

```

3276 \cs_new:Npn \__exp_e_space:nn #1#2
3277 { \exp_args:Nf \__exp_e:nn {#1} { #2 ~ } }

```

(End definition for `__exp_e_space:nn`.)

`__exp_e_group:n` For a group, expand its contents, wrap it in two pairs of braces, and call `__exp_e_put:nn`. This function places the first item (the double-brace wrapped result) into the output. Importantly, `\tl_head:n` works even if the input contains quarks.

```

3278 \cs_new:Npn \__exp_e_group:n #1
3279 {
3280   \exp_after:wN \__exp_e_put:nn
3281   \exp_after:wN { \exp_after:wN { \exp_after:wN {
3282     \exp:w \if_false: } \fi: \__exp_e:nn {#1} { } } }
3283 }
3284 \cs_new:Npn \__exp_e_put:nn #1
3285 {
3286   \exp_args:NNo \exp_args:No \__exp_e_put:nnn
3287   { \tl_head:n {#1} } {#1}
3288 }
3289 \cs_new:Npn \__exp_e_put:nnn #1#2#3
3290 { \exp_args:No \__exp_e:nn { \use_none:n #2 } { #3 #1 } }

```

(End definition for `__exp_e_group:n`, `__exp_e_put:nn`, and `__exp_e_put:nnn`.)

`__exp_e:N` For an N-type token, call `__exp_e:Nnn` with arguments the *⟨first token⟩*, the remain-
`__exp_e:Nnn` ing tokens to expand and what’s already been expanded. If the *⟨first token⟩* is non-
`__exp_e_protected:Nnn` expandable, including `\protected` (`\long` or not) macros, it is put in the result by
`__exp_e_expandable:Nnn` `__exp_e_protected:Nnn`. The four special primitives `\unexpanded`, `\noexpand`, `\the`,
`\primitive` are detected; otherwise the token is expanded by `__exp_e_expandable:Nnn`.

```

3291 \cs_new:Npn \__exp_e:N #1
3292 {
3293   \exp_after:wN \__exp_e:Nnn
3294   \exp_after:wN #1
3295   \exp_after:wN { \if_false: } \fi:
3296 }
3297 \cs_new:Npn \__exp_e:Nnn #1
3298 {
3299   \if_case:w
3300     \exp_after:wN \if_meaning:w \exp_not:N #1 #1 1 ~ \fi:
3301     \token_if_protected_macro:NT #1 { 1 ~ }
3302     \token_if_protected_long_macro:NT #1 { 1 ~ }
3303     \if_meaning:w \exp_not:n #1 2 ~ \fi:
3304     \if_meaning:w \exp_not:N #1 3 ~ \fi:
3305     \if_meaning:w \tex_the:D #1 4 ~ \fi:
3306     \if_meaning:w \tex_primitive:D #1 5 ~ \fi:
3307     0 ~
3308     \exp_after:wN \__exp_e_expandable:Nnn
3309     \or: \exp_after:wN \__exp_e_protected:Nnn
3310     \or: \exp_after:wN \__exp_e_unexpanded:Nnn
3311     \or: \exp_after:wN \__exp_e_noexpand:Nnn
3312     \or: \exp_after:wN \__exp_e_the:Nnn
3313     \or: \exp_after:wN \__exp_e_primitive:Nnn
3314     \fi:
3315     #1
3316   }
3317   \cs_new:Npn \__exp_e_protected:Nnn #1#2#3
3318     { \__exp_e:nn {#2} { #3 #1 } }
3319   \cs_new:Npn \__exp_e_expandable:Nnn #1#2
3320     { \exp_args:No \__exp_e:nn { #1 #2 } }

```

(End definition for `__exp_e:N` and others.)

`__exp_e_primitive:Nnn` We don’t try hard to make sensible error recovery since the error recovery of `\tex_`
`__exp_e_primitive_aux:NNw` `primitive:D` when followed by something else than a primitive depends on the engine.
`__exp_e_primitive_aux:NNnn` The only valid case is when what follows is N-type. Then distinguish special primitives
`__exp_e_primitive_other:NNnn` `\unexpanded`, `\noexpand`, `\the`, `\primitive` from other primitives. In the “other” case,
`__exp_e_primitive_other_aux:nNNnn` the only reasonable way to check if the primitive that follows `\tex_primitive:D` is
expandable is to expand and compare the before-expansion and after-expansion results.
If they coincide then probably the primitive is non-expandable and should be put in the
output together with `\tex_primitive:D` (one can cook up contrived counter-examples
where the true `\expanded` would have an infinite loop), and otherwise one should continue
expanding.

```

3321 \cs_new:Npn \__exp_e_primitive:Nnn #1#2
3322 {
3323   \if_false: { \fi:
3324   \tl_if_head_is_N_type:nTF {#2}
3325     { \__exp_e_primitive_aux:NNw #1 }

```



```

3326         {
3327             \__kernel_msg_expandable_error:nnn { kernel } { e-type }
3328             { Missing~primitive~name }
3329             \__exp_e_primitive_aux:NNw #1 \c_empty_tl
3330         }
3331     #2
3332 }
3333 }
3334 \cs_new:Npn \__exp_e_primitive_aux:NNw #1#2
3335 {
3336     \exp_after:wN \__exp_e_primitive_aux:NNnn
3337     \exp_after:wN #1
3338     \exp_after:wN #2
3339     \exp_after:wN { \if_false: } \fi:
3340 }
3341 \cs_new:Npn \__exp_e_primitive_aux:NNnn #1#2
3342 {
3343     \exp_args:Nf \str_case_e:nnTF { \cs_to_str:N #2 }
3344     {
3345         { unexpanded } { \__exp_e_unexpanded:NNn \exp_not:n }
3346         { noexpand } { \__exp_e_noexpand:NNn \exp_not:N }
3347         { the } { \__exp_e_the:NNn \tex_the:D }
3348         {
3349             \sys_if_engine_xetex:T { pdf }
3350             \sys_if_engine luatex:T { pdf }
3351             primitive
3352         } { \__exp_e_primitive:NNn #1 }
3353     }
3354     { \__exp_e_primitive_other:NNnn #1 #2 }
3355 }
3356 \cs_new:Npn \__exp_e_primitive_other:NNnn #1#2#3
3357 {
3358     \exp_args:No \__exp_e_primitive_other_aux:nNNnn
3359     { #1 #2 #3 }
3360     #1 #2 {#3}
3361 }
3362 \cs_new:Npn \__exp_e_primitive_other_aux:nNNnn #1#2#3#4#5
3363 {
3364     \str_if_eq:nnTF {#1} { #2 #3 #4 }
3365     { \__exp_e:nn {#4} { #5 #2 #3 } }
3366     { \__exp_e:nn {#1} {#5} }
3367 }

```

(End definition for __exp_e_primitive:NNn and others.)

__exp_e_noexpand:NNn The \noexpand primitive has no effect when followed by a token that is not N-type; otherwise __exp_e_put:nn can grab the next token and put it in the result unchanged.

```

3368 \cs_new:Npn \__exp_e_noexpand:NNn #1#2
3369 {
3370     \tl_if_head_is_N_type:nTF {#2}
3371     { \__exp_e_put:nn } { \__exp_e:nn } {#2}
3372 }

```

(End definition for __exp_e_noexpand:NNn.)

`__exp_e_unexpanded:Nnn`
`__exp_e_unexpanded:nn`
`__exp_e_unexpanded:nN`
`__exp_e_unexpanded:N`

The `\unexpanded` primitive expands and ignores any space, `\scan_stop:`, or token affected by `\exp_not:N`, then expects a brace group. Since we only support brace-balanced token lists it is impossible to support the case where the argument of `\unexpanded` starts with an implicit brace. Even though we want to expand and ignore spaces we cannot blindly f-expand because tokens affected by `\exp_not:N` should be discarded without being expanded further.

As usual distinguish four cases: brace group (the normal case, where we just put the item in the result), space (just f-expand to remove the space), empty (an error), or N-type *<token>*. In the last case call `__exp_e_unexpanded:nN` triggered by an f-expansion. Having a non-expandable *<token>* after `\unexpanded` is an error (we recover by passing `{}` to `\unexpanded`; this is different from T_EX because the error recovery of `\unexpanded` changes the balance of braces), unless that *<token>* is `\scan_stop:` or a space (recall that we don't implement the case of an implicit begin-group token). An expandable *<token>* is instead expanded, unless it is `\noexpand`. The latter primitive can be followed by an expandable N-type token (removed), by a non-expandable one (kept and later causing an error), by a space (removed by f-expansion), or by a brace group or nothing (later causing an error).

```

3373 \cs_new:Npn \__exp_e_unexpanded:Nnn #1 { \__exp_e_unexpanded:nn }
3374 \cs_new:Npn \__exp_e_unexpanded:nn #1
3375 {
3376   \tl_if_head_is_N_type:nTF {#1}
3377   {
3378     \exp_args:Nf \__exp_e_unexpanded:nn
3379     { \__exp_e_unexpanded:nN {#1} #1 }
3380   }
3381   {
3382     \tl_if_head_is_group:nTF {#1}
3383     { \__exp_e_put:nn }
3384     {
3385       \tl_if_empty:nTF {#1}
3386       {
3387         \__kernel_msg_expandable_error:nnn
3388         { kernel } { e-type }
3389         { \unexpanded missing~brace }
3390         \__exp_e_end:nn
3391       }
3392       { \exp_args:Nf \__exp_e_unexpanded:nn }
3393     }
3394   } {#1}
3395 }
3396 }
3397 \cs_new:Npn \__exp_e_unexpanded:nN #1#2
3398 {
3399   \exp_after:wN \if_meaning:w \exp_not:N #2 #2
3400   \exp_after:wN \use_i:nn
3401   \else:
3402     \exp_after:wN \use_ii:nn
3403   \fi:
3404   {
3405     \token_if_eq_catcode:NNTF #2 \c_space_token
3406     { \exp_stop_f: }
3407     {

```

```

3408         \token_if_eq_meaning:NNTF #2 \scan_stop:
3409         { \exp_stop_f: }
3410         {
3411             \__kernel_msg_expandable_error:nnn
3412             { kernel } { e-type }
3413             { \unexpanded missing-brace }
3414             { }
3415         }
3416     }
3417 }
3418 {
3419     \token_if_eq_meaning:NNTF #2 \exp_not:N
3420     {
3421         \exp_args:No \tl_if_head_is_N_type:nT { \use_none:n #1 }
3422         { \__exp_e_unexpanded:N }
3423     }
3424     { \exp_after:wN \exp_stop_f: #2 }
3425 }
3426 }
3427 \cs_new:Npn \__exp_e_unexpanded:N #1
3428 {
3429     \exp_after:wN \if_meaning:w \exp_not:N #1 #1 \else:
3430     \exp_after:wN \use_i:nn
3431     \fi:
3432     \exp_stop_f: #1
3433 }

```

(End definition for `__exp_e_unexpanded:Nnn` and others.)

`__exp_e_the:Nnn`
`__exp_e_the:N`
`__exp_e_the_toks_reg:N`

Finally implement `\the`. Followed by anything other than an N-type *<token>* this causes an error (we just let T_EX make one), otherwise we test the *<token>*. If the *<token>* is expandable, expand it. Otherwise it could be any kind of register, or things like `\numexpr`, so there is no way to deal with all cases. Thankfully, only `\toks` data needs to be protected from expansion since everything else gives a string of characters. If the *<token>* is `\toks` we find a number and unpack using the `the_toks` functions. If it is a token register we unpack it in a brace group and call `__exp_e_put:nn` to move it to the result. Otherwise we unpack and continue expanding (useless but safe) since it is basically impossible to have a handle on where the result of `\the` ends.

```

3434     \cs_new:Npn \__exp_e_the:Nnn #1#2
3435     {
3436         \tl_if_head_is_N_type:nTF {#2}
3437         { \if_false: { \fi: \__exp_e_the:N #2 } }
3438         { \exp_args:No \__exp_e:nn { \tex_the:D #2 } }
3439     }
3440     \cs_new:Npn \__exp_e_the:N #1
3441     {
3442         \exp_after:wN \if_meaning:w \exp_not:N #1 #1
3443         \exp_after:wN \use_i:nn
3444         \else:
3445         \exp_after:wN \use_ii:nn
3446         \fi:
3447         {
3448             \if_meaning:w \tex_toks:D #1
3449             \exp_after:wN \__exp_e_the_toks:wnn \int_value:w

```

```

3450         \exp_after:wN \__exp_e_the_toks:n
3451         \exp_after:wN { \int_value:w \if_false: } \fi:
3452     \else:
3453         \__exp_e_if_toks_register:NTF #1
3454         { \exp_after:wN \__exp_e_the_toks_reg:N }
3455         {
3456             \exp_after:wN \__exp_e:nn \exp_after:wN {
3457                 \tex_the:D \if_false: } \fi:
3458         }
3459         \exp_after:wN #1
3460     \fi:
3461 }
3462 {
3463     \exp_after:wN \__exp_e_the:Nnn \exp_after:wN ?
3464     \exp_after:wN { \exp:w \if_false: } \fi:
3465     \exp_after:wN \exp_end: #1
3466 }
3467 }
3468 \cs_new:Npn \__exp_e_the_toks_reg:N #1
3469 {
3470     \exp_after:wN \__exp_e_put:nn \exp_after:wN {
3471         \exp_after:wN {
3472             \tex_the:D \if_false: } \fi: #1 }
3473 }

```

(End definition for `__exp_e_the:Nnn`, `__exp_e_the:N`, and `__exp_e_the_toks_reg:N`.)

`__exp_e_the_toks:wnn` The calling function has applied `\int_value:w` so we collect digits with `__exp_e_the_toks:n` (which gets the token list as an argument) and `__exp_e_the_toks:N` (which gets the first token in case it is N-type). The digits are themselves collected into an `\int_value:w` argument to `__exp_e_the_toks:wnn`. Then that function unpacks the `\toks<number>` into the result. We include `?` because `__exp_e_put:nnn` removes one item from its second argument. Note that our approach is rather crude: in cases like `\the\toks12~34` the first `\int_value:w` removes the space and we will incorrectly unpack the `\the\toks1234`.

```

3474     \cs_new:Npn \__exp_e_the_toks:wnn #1; #2
3475     {
3476         \exp_args:No \__exp_e_put:nnn
3477         { \tex_the:D \tex_toks:D #1 } { ? #2 }
3478     }
3479     \cs_new:Npn \__exp_e_the_toks:n #1
3480     {
3481         \tl_if_head_is_N_type:NTF {#1}
3482         { \exp_after:wN \__exp_e_the_toks:N \if_false: { \fi: #1 } }
3483         { ; {#1} }
3484     }
3485     \cs_new:Npn \__exp_e_the_toks:N #1
3486     {
3487         \if_int_compare:w 10 < 9 \token_to_str:N #1 \exp_stop_f:
3488         \exp_after:wN \use_i:nn
3489     \else:
3490         \exp_after:wN \use_ii:nn
3491     \fi:
3492     {

```

```

3493         #1
3494         \exp_after:wN \_exp_e_the_toks:n
3495         \exp_after:wN { \if_false: } \fi:
3496     }
3497     {
3498         \exp_after:wN ;
3499         \exp_after:wN { \if_false: } \fi: #1
3500     }
3501 }

```

(End definition for `_exp_e_the_toks:wnn`, `_exp_e_the_toks:n`, and `_exp_e_the_toks:N`.)

`_exp_e_if_toks_register:NTF` We need to detect both `\toks` registers like `\toks@` in L^AT_EX 2_ε and parameters such as `\everypar`, as the result of unpacking the register should not expand further. Registers are found by `\token_if_toks_register:NTF` by inspecting the meaning. The list of parameters is finite so we just use a `\cs_if_exist:cTF` test to look up in a table. We abuse `\cs_to_str:N`'s ability to remove a leading escape character whatever it is.

```

\__exp_e_the_everydisplay:
\__exp_e_the_everyeof: 3502 \prg_new_conditional:Npnn \_exp_e_if_toks_register:N #1 { TF }
\__exp_e_the_everyhbox: 3503 {
\__exp_e_the_everyjob: 3504   \token_if_toks_register:NTF #1 { \prg_return_true: }
\__exp_e_the_everymath: 3505   {
\__exp_e_the_everypar: 3506     \cs_if_exist:cTF
\__exp_e_the_everyvbox: 3507     {
\__exp_e_the_output: 3508       \_exp_e_the_
\__exp_e_the_pdfpageattr: 3509       \exp_after:wN \cs_to_str:N
\__exp_e_the_pdfpageresources: 3510       \token_to_meaning:N #1
\__exp_e_the_pdfpagesattr: 3511       :
\__exp_e_the_pdfpkmode: 3512     } { \prg_return_true: } { \prg_return_false: }
3513   }
3514 }
3515 \cs_new_eq:NN \_exp_e_the_XeTeXinterchartoks: ?
3516 \cs_new_eq:NN \_exp_e_the_errhelp: ?
3517 \cs_new_eq:NN \_exp_e_the_everycr: ?
3518 \cs_new_eq:NN \_exp_e_the_everydisplay: ?
3519 \cs_new_eq:NN \_exp_e_the_everyeof: ?
3520 \cs_new_eq:NN \_exp_e_the_everyhbox: ?
3521 \cs_new_eq:NN \_exp_e_the_everyjob: ?
3522 \cs_new_eq:NN \_exp_e_the_everymath: ?
3523 \cs_new_eq:NN \_exp_e_the_everypar: ?
3524 \cs_new_eq:NN \_exp_e_the_everyvbox: ?
3525 \cs_new_eq:NN \_exp_e_the_output: ?
3526 \cs_new_eq:NN \_exp_e_the_pdfpageattr: ?
3527 \cs_new_eq:NN \_exp_e_the_pdfpageresources: ?
3528 \cs_new_eq:NN \_exp_e_the_pdfpagesattr: ?
3529 \cs_new_eq:NN \_exp_e_the_pdfpkmode: ?

```

(End definition for `_exp_e_if_toks_register:NTF` and others.)

We are done emulating e-type argument expansion when `\expanded` is unavailable.

```

3530 }

```

6.7 Defining function variants

```

3531 <@@=cs>

```

`\s__cs_mark` Internal scan marks. No l3quark yet, so do things by hand.

`\s__cs_stop` 3532 `\cs_new_eq:NN \s__cs_mark \scan_stop:`
 3533 `\cs_new_eq:NN \s__cs_stop \scan_stop:`

(End definition for `\s__cs_mark` and `\s__cs_stop`.)

`\q__cs_recursion_stop` Internal recursion quarks. No l3quark yet, so do things by hand.

3534 `\cs_new:Npn \q__cs_recursion_stop { \q__cs_recursion_stop }`

(End definition for `\q__cs_recursion_stop`.)

`__cs_use_none_delimit_by_s_stop:w` Internal scan marks.

`__cs_use_i_delimit_by_s_stop:nw` 3535 `\cs_new:Npn __cs_use_none_delimit_by_s_stop:w #1 \s__cs_stop { }`
`__cs_use_none_delimit_by_q_recursion_stop:w` 3536 `\cs_new:Npn __cs_use_i_delimit_by_s_stop:nw #1 #2 \s__cs_stop {#1}`
 3537 `\cs_new:Npn __cs_use_none_delimit_by_q_recursion_stop:w`
 3538 `#1 \q__cs_recursion_stop { }`

(End definition for `__cs_use_none_delimit_by_s_stop:w`, `__cs_use_i_delimit_by_s_stop:nw`, and `__cs_use_none_delimit_by_q_recursion_stop:w`.)

`\cs_generate_variant:Nn` #1 : Base form of a function; e.g., `\tl_set:Nn`

`\cs_generate_variant:cn` #2 : One or more variant argument specifiers; e.g., `{Nx,c,cx}`

After making sure that the base form exists, test whether it is protected or not and define `__cs_tmp:w` as either `\cs_new:Npx` or `\cs_new_protected:Npx`, which is then used to define all the variants (except those involving x-expansion, always protected). Split up the original base function only once, to grab its name and signature. Then we wish to iterate through the comma list of variant argument specifiers, which we first convert to a string: the reason is explained later.

3539 `\cs_new_protected:Npn \cs_generate_variant:Nn #1#2`
 3540 `{`
 3541 `__cs_generate_variant:N #1`
 3542 `\use:x`
 3543 `{`
 3544 `__cs_generate_variant:nnNN`
 3545 `\cs_split_function:N #1`
 3546 `\exp_not:N #1`
 3547 `\tl_to_str:n {#2} ,`
 3548 `\exp_not:N \scan_stop: ,`
 3549 `\exp_not:N \q__cs_recursion_stop`
 3550 `}`
 3551 `}`
 3552 `\cs_new_protected:Npn \cs_generate_variant:cn`
 3553 `{ \exp_args:Nc \cs_generate_variant:Nn }`

(End definition for `\cs_generate_variant:Nn`. This function is documented on page 27.)

`__cs_generate_variant:N` The goal here is to pick up protected parent functions. There are four cases: the parent function can be a primitive or a macro, and can be expandable or not. For non-expandable primitives, all variants should be protected; skipping the `\else:` branch is safe because non-expandable primitives cannot be T_EX conditionals.

The other case where variants should be protected is when the parent function is a protected macro: then `protected` appears in the meaning before the first occurrence of `macro`. The `ww` auxiliary removes everything in the meaning string after the first `ma`. We use `ma` rather than the full `macro` because the meaning of the `\firstmark` primitive (and

four others) can contain an arbitrary string after a leading `firstmark:`. Then, look for `pr` in the part we extracted: no need to look for anything longer: the only strings we can have are an empty string, `\long`, `\protected`, `\protected\long`, `\first`, `\top`, `\bot`, `\splittop`, or `\splitbot`, with `\` replaced by the appropriate escape character. If `pr` appears in the part before `ma`, the first `\s__cs_mark` is taken as an argument of the `wwNw` auxiliary, and `#3` is `\cs_new_protected:Npx`, otherwise it is `\cs_new:Npx`.

```

3554 \cs_new_protected:Npx \__cs_generate_variant:N #1
3555 {
3556   \exp_not:N \exp_after:wN \exp_not:N \if_meaning:w
3557   \exp_not:N \exp_not:N #1 #1
3558   \cs_set_eq:NN \exp_not:N \__cs_tmp:w \cs_new_protected:Npx
3559   \exp_not:N \else:
3560   \exp_not:N \exp_after:wN \exp_not:N \__cs_generate_variant:ww
3561   \exp_not:N \token_to_meaning:N #1 \tl_to_str:n { ma }
3562   \s__cs_mark
3563   \s__cs_mark \cs_new_protected:Npx
3564   \tl_to_str:n { pr }
3565   \s__cs_mark \cs_new:Npx
3566   \s__cs_stop
3567   \exp_not:N \fi:
3568 }
3569 \exp_last_unbraced:NNNNo
3570 \cs_new_protected:Npn \__cs_generate_variant:ww
3571 #1 { \tl_to_str:n { ma } } #2 \s__cs_mark
3572 { \__cs_generate_variant:wwNw #1 }
3573 \exp_last_unbraced:NNNNo
3574 \cs_new_protected:Npn \__cs_generate_variant:wwNw
3575 #1 { \tl_to_str:n { pr } } #2 \s__cs_mark #3 #4 \s__cs_stop
3576 { \cs_set_eq:NN \__cs_tmp:w #3 }

```

(End definition for `__cs_generate_variant:N`, `__cs_generate_variant:ww`, and `__cs_generate_variant:wwNw`.)

```

\__cs_generate_variant:nnNN #1 : Base name.
#2 : Base signature.
#3 : Boolean.
#4 : Base function.

```

If the boolean is `\c_false_bool`, the base function has no colon and we abort with an error; otherwise, set off a loop through the desired variant forms. The original function is retained as `#4` for efficiency.

```

3577 \cs_new_protected:Npn \__cs_generate_variant:nnNN #1#2#3#4
3578 {
3579   \if_meaning:w \c_false_bool #3
3580   \__kernel_msg_error:nnx { kernel } { missing-colon }
3581   { \token_to_str:c {#1} }
3582   \exp_after:wN \__cs_use_none_delimit_by_q_recursion_stop:w
3583   \fi:
3584   \__cs_generate_variant:Nnnw #4 {#1}{#2}
3585 }

```

(End definition for `__cs_generate_variant:nnNN`.)

```

\__cs_generate_variant:Nnnw #1 : Base function.
#2 : Base name.

```

#3 : Base signature.

#4 : Beginning of variant signature.

First check whether to terminate the loop over variant forms. Then, for each variant form, construct a new function name using the original base name, the variant signature consisting of l letters and the last $k - l$ letters of the base signature (of length k). For example, for a base function `\prop_put:Nnn` which needs a `cV` variant form, we want the new signature to be `cVn`.

There are further subtleties:

- In `\cs_generate_variant:Nn \foo:nnTF {xxTF}`, we must define `\foo:xxTF` using `\exp_args:Nxx`, rather than a hypothetical `\exp_args:NxxTF`. Thus, we wish to trim a common trailing part from the base signature and the variant signature.
- In `\cs_generate_variant:Nn \foo:on {ox}`, the function `\foo:ox` must be defined using `\exp_args:Nnx`, not `\exp_args:Nox`, to avoid double `o` expansion.
- Lastly, `\cs_generate_variant:Nn \foo:on {xn}` must trigger an error, because we do not have a means to replace `o`-expansion by `x`-expansion. More generally, we can only convert `N` to `c`, or convert `n` to `V`, `v`, `o`, `f`, `x`.

All this boils down to a few rules. Only `n` and `N`-type arguments can be replaced by `\cs_generate_variant:Nn`. Other argument types are allowed to be passed unchanged from the base form to the variant: in the process they are changed to `n` except for `N` and `p`-type arguments. A common trailing part is ignored.

We compare the base and variant signatures one character at a time within `x`-expansion. The result is given to `__cs_generate_variant:wwNN` (defined later) in the form `<processed variant signature> \s__cs_mark <errors> \s__cs_stop <base function> <new function>`. If all went well, `<errors>` is empty; otherwise, it is a kernel error message and some clean-up code.

Note the space after #3 and after the following brace group. Those are ignored by `TEX` when fetching the last argument for `__cs_generate_variant_loop:nNwN`, but can be used as a delimiter for `__cs_generate_variant_loop_end:nwwwNNnn`.

```

3586 \cs_new_protected:Npn \__cs_generate_variant:Nnnw #1#2#3#4 ,
3587 {
3588   \if_meaning:w \scan_stop: #4
3589   \exp_after:wN \__cs_use_none_delimit_by_q_recursion_stop:w
3590   \fi:
3591   \use:x
3592   {
3593     \exp_not:N \__cs_generate_variant:wwNN
3594     \__cs_generate_variant_loop:nNwN { }
3595     #4
3596     \__cs_generate_variant_loop_end:nwwwNNnn
3597     \s__cs_mark
3598     #3 ~
3599     { ~ { } \fi: \__cs_generate_variant_loop_long:wNNnn } ~
3600     { }
3601     \s__cs_stop
3602     \exp_not:N #1 {#2} {#4}
3603   }
3604   \__cs_generate_variant:Nnnw #1 {#2} {#3}
3605 }
```


(End definition for `_cs_generate_variant:Nnnw`.)

<code>_cs_generate_variant_loop:nNwN</code>	#1 :	Last few consecutive letters common between the base and variant (more precisely,
<code>_cs_generate_variant_loop_base:N</code>		<code>_cs_generate_variant_same:N</code> <i><letter></i> for each letter).
<code>_cs_generate_variant_loop_same:w</code>	#2 :	Next variant letter.
<code>_cs_generate_variant_loop_end:nwwwNNnn</code>	#3 :	Remainder of variant form.
<code>_cs_generate_variant_loop_long:wNNnn</code>	#4 :	Next base letter.
<code>_cs_generate_variant_loop_invalid:NNwNNnn</code>		
<code>_cs_generate_variant_loop_special:NNwNNnn</code>		

The first argument is populated by `_cs_generate_variant_loop_same:w` when a variant letter and a base letter match. It is flushed into the input stream whenever the two letters are different: if the loop ends before, the argument is dropped, which means that trailing common letters are ignored.

The case where the two letters are different is only allowed if the base is N and the variant is c, or when the base is n and the variant is o, V, v, f or x. Otherwise, call `_cs_generate_variant_loop_invalid:NNwNNnn` to remove the end of the loop, get arguments at the end of the loop, and place an appropriate error message as a second argument of `_cs_generate_variant:wwNN`. If the letters are distinct and the base letter is indeed n or N, leave in the input stream whatever argument #1 was collected, and the next variant letter #2, then loop by calling `_cs_generate_variant_loop:nNwN`.

The loop can stop in three ways.

- If the end of the variant form is encountered first, #2 is `_cs_generate_variant_loop_end:nwwwNNnn` (expanded by the conditional `\if:w`), which inserts some tokens to end the conditional; grabs the *<base name>* as #7, the *<variant signature>* #8, the *<next base letter>* #1 and the part #3 of the base signature that wasn't read yet; and combines those into the *<new function>* to be defined.
- If the end of the base form is encountered first, #4 is `~{} \fi:` which ends the conditional (with an empty expansion), followed by `_cs_generate_variant_loop_long:wNNnn`, which places an error as the second argument of `_cs_generate_variant:wwNN`.
- The loop can be interrupted early if the requested expansion is unavailable, namely when the variant and base letters differ and the base is not the right one (n or N to support the variant). In that case too an error is placed as the second argument of `_cs_generate_variant:wwNN`.

Note that if the variant form has the same length as the base form, #2 is as described in the first point, and #4 as described in the second point above. The `_cs_generate_variant_loop_end:nwwwNNnn` breaking function takes the empty brace group in #4 as its first argument: this empty brace group produces the correct signature for the full variant.

```

3606 \cs_new:Npn \_cs_generate_variant_loop:nNwN #1#2#3 \s_cs_mark #4
3607 {
3608   \if:w #2 #4
3609     \exp_after:wN \_cs_generate_variant_loop_same:w
3610   \else:
3611     \if:w #4 \_cs_generate_variant_loop_base:N #2 \else:
3612       \if:w 0
3613         \if:w N #4 \else: \if:w n #4 \else: 1 \fi: \fi:
3614         \if:w \scan_stop: \_cs_generate_variant_loop_base:N #2 1 \fi:
3615         0
3616       \_cs_generate_variant_loop_special:NNwNNnn #4#2

```

```

3617         \else:
3618             \__cs_generate_variant_loop_invalid:NNwNNnn #4#2
3619         \fi:
3620     \fi:
3621 \fi:
3622 #1
3623 \prg_do_nothing:
3624 #2
3625 \__cs_generate_variant_loop:nNwN { } #3 \s__cs_mark
3626 }
3627 \cs_new:Npn \__cs_generate_variant_loop_base:N #1
3628 {
3629     \if:w c #1 N \else:
3630         \if:w o #1 n \else:
3631             \if:w V #1 n \else:
3632                 \if:w v #1 n \else:
3633                     \if:w f #1 n \else:
3634                         \if:w e #1 n \else:
3635                             \if:w x #1 n \else:
3636                                 \if:w n #1 n \else:
3637                                     \if:w N #1 N \else:
3638                                         \scan_stop:
3639                                         \fi:
3640                                     \fi:
3641                                 \fi:
3642                             \fi:
3643                         \fi:
3644                     \fi:
3645                 \fi:
3646             \fi:
3647         \fi:
3648     }
3649 \cs_new:Npn \__cs_generate_variant_loop_same:w
3650     #1 \prg_do_nothing: #2#3#4
3651     { #3 { #1 \__cs_generate_variant_same:N #2 } }
3652 \cs_new:Npn \__cs_generate_variant_loop_end:nwwwNNnn
3653     #1#2 \s__cs_mark #3 ~ #4 \s__cs_stop #5#6#7#8
3654 {
3655     \scan_stop: \scan_stop: \fi:
3656     \s__cs_mark \s__cs_stop
3657     \exp_not:N #6
3658     \exp_not:c { #7 : #8 #1 #3 }
3659 }
3660 \cs_new:Npn \__cs_generate_variant_loop_long:wNNnn #1 \s__cs_stop #2#3#4#5
3661 {
3662     \exp_not:n
3663     {
3664         \s__cs_mark
3665         \__kernel_msg_error:nxxx { kernel } { variant-too-long }
3666         {#5} { \token_to_str:N #3 }
3667         \use_none:nnn
3668         \s__cs_stop
3669         #3
3670         #3

```

```

3671     }
3672   }
3673   \cs_new:Npn \__cs_generate_variant_loop_invalid:NNwNNnn
3674     #1#2 \fi: \fi: \fi: #3 \s__cs_stop #4#5#6#7
3675   {
3676     \fi: \fi: \fi:
3677     \exp_not:n
3678     {
3679       \s__cs_mark
3680       \__kernel_msg_error:nnxxxx { kernel } { invalid-variant }
3681       {#7} { \token_to_str:N #5 } {#1} {#2}
3682       \use_none:nnn
3683       \s__cs_stop
3684       #5
3685       #5
3686     }
3687   }
3688   \cs_new:Npn \__cs_generate_variant_loop_special:NNwNNnn
3689     #1#2#3 \s__cs_stop #4#5#6#7
3690   {
3691     #3 \s__cs_stop #4 #5 {#6} {#7}
3692     \exp_not:n
3693     {
3694       \__kernel_msg_error:nnxxxx
3695       { kernel } { deprecated-variant }
3696       {#7} { \token_to_str:N #5 } {#1} {#2}
3697     }
3698   }

```

(End definition for __cs_generate_variant_loop:nNwN and others.)

__cs_generate_variant_same:N When the base and variant letters are identical, don't do any expansion. For most argument types, we can use the n-type no-expansion, but the N and p types require a slightly different behaviour with respect to braces. For V-type this function could output N to avoid adding useless braces but that is not a problem.

```

3699   \cs_new:Npn \__cs_generate_variant_same:N #1
3700   {
3701     \if:w N #1 #1 \else:
3702       \if:w p #1 #1 \else:
3703         \token_to_str:N n
3704         \if:w n #1 \else:
3705           \__cs_generate_variant_loop_special:NNwNNnn #1#1
3706         \fi:
3707       \fi:
3708     \fi:
3709   }

```

(End definition for __cs_generate_variant_same:N.)

__cs_generate_variant:wwNN If the variant form has already been defined, log its existence (provided log-functions is active). Otherwise, make sure that the \exp_args:N #3 form is defined, and if it contains x, change __cs_tmp:w locally to \cs_new_protected:Npx. Then define the variant by combining the \exp_args:N #3 variant and the base function.

```

3710   \cs_new_protected:Npn \__cs_generate_variant:wwNN

```

```

3711     #1 \s__cs_mark #2 \s__cs_stop #3#4
3712 {
3713     #2
3714     \cs_if_free:NT #4
3715     {
3716         \group_begin:
3717         \__cs_generate_internal_variant:n {#1}
3718         \__cs_tmp:w #4 { \exp_not:c { exp_args:N #1 } \exp_not:N #3 }
3719         \group_end:
3720     }
3721 }

```

(End definition for __cs_generate_variant:wwNN.)

__cs_generate_internal_variant:n
__cs_generate_internal_variant_loop:n

First test for the presence of x (this is where working with strings makes our lives easier), as the result should be protected, and the next variant to be defined using that internal variant should be protected (done by setting __cs_tmp:w). Then call __cs_generate_internal_variant:NNn with arguments \cs_new_protected:cpn \use:x (for protected) or \cs_new:cpn \tex_expanded:D (expandable) and the signature. If p appears in the signature, or if the function to be defined is expandable and the primitive \expanded is not available, or if there are more than 8 arguments, call some fall-back code that just puts the appropriate \:: commands. Otherwise, call __cs_generate_internal_one_go:NNn to construct the \exp_args:N... function as a macro taking up to 9 arguments and expanding them using \use:x or \tex_expanded:D.

```

3722 \cs_new_protected:Npx \__cs_generate_internal_variant:n #1
3723 {
3724     \exp_not:N \__cs_generate_internal_variant:wwnNwn
3725     #1 \s__cs_mark
3726     { \cs_set_eq:NN \exp_not:N \__cs_tmp:w \cs_new_protected:Npx }
3727     \cs_new_protected:cpn
3728     \use:x
3729     \token_to_str:N x \s__cs_mark
3730     { }
3731     \cs_new:cpn
3732     \exp_not:N \tex_expanded:D
3733     \s__cs_stop
3734     {#1}
3735 }
3736 \exp_last_unbraced:NNNNo
3737 \cs_new_protected:Npn \__cs_generate_internal_variant:wwnNwn #1
3738 { \token_to_str:N x } #2 \s__cs_mark #3#4#5#6 \s__cs_stop #7
3739 {
3740     #3
3741     \cs_if_free:cT { exp_args:N #7 }
3742     { \__cs_generate_internal_variant:NNn #4 #5 {#7} }
3743 }
3744 \cs_set_protected:Npn \__cs_tmp:w #1
3745 {
3746     \cs_new_protected:Npn \__cs_generate_internal_variant:NNn ##1##2##3
3747     {
3748         \if_catcode:w X \use_none:nnnnnnnn ##3
3749         \prg_do_nothing: \prg_do_nothing: \prg_do_nothing:
3750         \prg_do_nothing: \prg_do_nothing: \prg_do_nothing:
3751         \prg_do_nothing: \prg_do_nothing: X

```

```

3752         \exp_after:wN \_cs_generate_internal_test:Nw \exp_after:wN ##2
3753     \else:
3754         \exp_after:wN \_cs_generate_internal_test_aux:w \exp_after:wN #1
3755     \fi:
3756     ##3
3757     \s__cs_mark
3758     {
3759         \use:x
3760         {
3761             ##1 { exp_args:N ##3 }
3762             { \_cs_generate_internal_variant_loop:n ##3 { : \use_i:nn } }
3763         }
3764     }
3765     #1
3766     \s__cs_mark
3767     { \exp_not:n { \_cs_generate_internal_one_go:NNn ##1 ##2 {##3} } }
3768     \s__cs_stop
3769 }
3770 \cs_new_protected:Npn \_cs_generate_internal_test_aux:w
3771     ##1 #1 ##2 \s__cs_mark ##3 ##4 \s__cs_stop {##3}
3772 \cs_if_exist:NTF \tex_expanded:D
3773 {
3774     \cs_new_eq:NN \_cs_generate_internal_test:Nw
3775     \_cs_generate_internal_test_aux:w
3776 }
3777 {
3778     \cs_new_protected:Npn \_cs_generate_internal_test:Nw ##1
3779     {
3780         \if_meaning:w \tex_expanded:D ##1
3781         \exp_after:wN \_cs_generate_internal_test_aux:w
3782         \exp_after:wN #1
3783         \else:
3784         \exp_after:wN \_cs_generate_internal_test_aux:w
3785         \fi:
3786     }
3787 }
3788 }
3789 \exp_args:No \_cs_tmp:w { \token_to_str:N p }
3790 \cs_new_protected:Npn \_cs_generate_internal_one_go:NNn #1#2#3
3791 {
3792     \_cs_generate_internal_loop:nwnnw
3793     { \exp_not:N ##1 } 1 . { } { }
3794     #3 { ? \_cs_generate_internal_end:w } X ;
3795     23456789 { ? \_cs_generate_internal_long:w } ;
3796     #1 #2 {##3}
3797 }
3798 \cs_new_protected:Npn \_cs_generate_internal_loop:nwnnw #1#2 . #3#4#5#6 ; #7
3799 {
3800     \use_none:n #5
3801     \use_none:n #7
3802     \cs_if_exist_use:cF { \_cs_generate_internal_#5:NN }
3803     { \_cs_generate_internal_other:NN }
3804     #5 #7
3805     #7 .

```

```

3806     { #3 #1 } { #4 ## #2 }
3807     #6 ;
3808 }
3809 \cs_new_protected:Npn \__cs_generate_internal_N:NN #1#2
3810 { \__cs_generate_internal_loop:nwnnw { \exp_not:N ###2 } }
3811 \cs_new_protected:Npn \__cs_generate_internal_c:NN #1#2
3812 { \exp_args:No \__cs_generate_internal_loop:nwnnw { \exp_not:c {###2} } }
3813 \cs_new_protected:Npn \__cs_generate_internal_n:NN #1#2
3814 { \__cs_generate_internal_loop:nwnnw { { \exp_not:n {###2} } } }
3815 \cs_new_protected:Npn \__cs_generate_internal_x:NN #1#2
3816 { \__cs_generate_internal_loop:nwnnw { {###2} } }
3817 \cs_new_protected:Npn \__cs_generate_internal_other:NN #1#2
3818 {
3819     \exp_args:No \__cs_generate_internal_loop:nwnnw
3820     {
3821         \exp_after:wN
3822         {
3823             \exp:w \exp_args:NNc \exp_after:wN \exp_end:
3824             { exp_not:#1 } {###2}
3825         }
3826     }
3827 }
3828 \cs_new_protected:Npn \__cs_generate_internal_end:w #1 . #2#3#4 ; #5 ; #6#7#8
3829 { #6 { exp_args:N #8 } #3 { #7 {#2} } }
3830 \cs_new_protected:Npn \__cs_generate_internal_long:w #1 N #2#3 . #4#5#6#
3831 {
3832     \exp_args:Nx \__cs_generate_internal_long:nnnNnn
3833     { \__cs_generate_internal_variant_loop:n #2 #6 { : \use_i:nn } }
3834     {#4} {#5}
3835 }
3836 \cs_new:Npn \__cs_generate_internal_long:nnnNnn #1#2#3#4 ; ; #5#6#7
3837 { #5 { exp_args:N #7 } #3 { #6 { \exp_not:n {#1} {#2} } } }

```

This command grabs char by char outputting \::#1 (not expanded further). We avoid tests by putting a trailing : \use_i:nn, which leaves \cs_end: and removes the looping macro. The colon is in fact also turned into \::: so that the required structure for \exp_args:N... commands is correctly terminated.

```

3838 \cs_new:Npn \__cs_generate_internal_variant_loop:n #1
3839 {
3840     \exp_after:wN \exp_not:N \cs:w :: #1 \cs_end:
3841     \__cs_generate_internal_variant_loop:n
3842 }

```

(End definition for __cs_generate_internal_variant:n and __cs_generate_internal_variant_loop:n.)

\prg_generate_conditional_variant:Nnn

```

\__cs_generate_variant:nnNnn 3843 \cs_new_protected:Npn \prg_generate_conditional_variant:Nnn #1
\__cs_generate_variant:w      3844 {
\__cs_generate_variant:n      3845     \use:x
\__cs_generate_variant_p_form:nnn 3846     {
\__cs_generate_variant_T_form:nnn 3847         \__cs_generate_variant:nnNnn
\__cs_generate_variant_F_form:nnn 3848         \cs_split_function:N #1
\__cs_generate_variant_TF_form:nnn 3849     }
3850 }

```

```

3851 \cs_new_protected:Npn \__cs_generate_variant:nnNnn #1#2#3#4#5
3852 {
3853   \if_meaning:w \c_false_bool #3
3854     \__kernel_msg_error:nnx { kernel } { missing-colon }
3855     { \token_to_str:c {#1} }
3856     \__cs_use_i_delimit_by_s_stop:nw
3857   \fi:
3858   \exp_after:wN \__cs_generate_variant:w
3859   \tl_to_str:n {#5} , \scan_stop: , \q__cs_recursion_stop
3860   \__cs_use_none_delimit_by_s_stop:w \s__cs_mark {#1} {#2} {#4} \s__cs_stop
3861 }
3862 \cs_new_protected:Npn \__cs_generate_variant:w
3863   #1 , #2 \s__cs_mark #3#4#5
3864 {
3865   \if_meaning:w \scan_stop: #1 \scan_stop:
3866     \if_meaning:w \q__cs_nil #1 \q__cs_nil
3867     \use_i:nnn
3868   \fi:
3869   \exp_after:wN \__cs_use_none_delimit_by_q_recursion_stop:w
3870   \else:
3871     \cs_if_exist_use:cTF { __cs_generate_variant_#1_form:nnn }
3872     { {#3} {#4} {#5} }
3873     {
3874       \__kernel_msg_error:nnxx
3875       { kernel } { conditional-form-unknown }
3876       {#1} { \token_to_str:c { #3 : #4 } }
3877     }
3878   \fi:
3879   \__cs_generate_variant:w #2 \s__cs_mark {#3} {#4} {#5}
3880 }
3881 \cs_new_protected:Npn \__cs_generate_variant_p_form:nnn #1#2
3882 { \cs_generate_variant:cn { #1_p : #2 } }
3883 \cs_new_protected:Npn \__cs_generate_variant_T_form:nnn #1#2
3884 { \cs_generate_variant:cn { #1 : #2 T } }
3885 \cs_new_protected:Npn \__cs_generate_variant_F_form:nnn #1#2
3886 { \cs_generate_variant:cn { #1 : #2 F } }
3887 \cs_new_protected:Npn \__cs_generate_variant_TF_form:nnn #1#2
3888 { \cs_generate_variant:cn { #1 : #2 TF } }

```

(End definition for \prg_generate_conditional_variant:Nnn and others. This function is documented on page 106.)

\exp_args_generate:n This function is not used in the kernel hence we can use functions that are defined in later modules. It also does not need to be fast so use inline mappings. For each requested variant we check that there are no characters besides NnpcofVvx, in particular that there are no spaces. Then we just call the internal function.

```

3889 \cs_new_protected:Npn \exp_args_generate:n #1
3890 {
3891   \exp_args:No \clist_map_inline:nn { \tl_to_str:n {#1} }
3892   {
3893     \str_map_inline:nn {##1}
3894     {
3895       \str_if_in:nnF { NnpcofVvx } {####1}
3896       {

```

```

3897         \__kernel_msg_error:nnnn { kernel } { invalid-exp-args }
3898         {####1} {##1}
3899         \str_map_break:n { \use_none:nn }
3900     }
3901 }
3902 \__cs_generate_internal_variant:n {##1}
3903 }
3904 }

```

(End definition for `\exp_args_generate:n`. This function is documented on page 261.)

6.8 Definitions with the automated technique

Some of these could be done more efficiently, but the complexity of coding then becomes an issue. Notice that the auto-generated functions actually take no arguments themselves.

Here are the actual function definitions, using the helper functions above. The group is used because `__cs_generate_internal_variant:n` redefines `__cs_tmp:w` locally.

```

\exp_args:Nnc \exp_args:Nno \exp_args:NnV \exp_args:Nnv \exp_args:Nne
\exp_args:Nnf \exp_args:Noc \exp_args:Noo \exp_args:Nof \exp_args:NVo
\exp_args:Nfo \exp_args:Nff \exp_args:Nee \exp_args:NNx \exp_args:Ncx
\exp_args:Nnx \exp_args:Nox \exp_args:Nxo \exp_args:Nxx
3905 \cs_set_protected:Npn \__cs_tmp:w #1
3906 {
3907     \group_begin:
3908         \exp_args:No \__cs_generate_internal_variant:n
3909         { \tl_to_str:n {#1} }
3910     \group_end:
3911 }
3912 \__cs_tmp:w { nc }
3913 \__cs_tmp:w { no }
3914 \__cs_tmp:w { nV }
3915 \__cs_tmp:w { nv }
3916 \__cs_tmp:w { ne }
3917 \__cs_tmp:w { nf }
3918 \__cs_tmp:w { oc }
3919 \__cs_tmp:w { oo }
3920 \__cs_tmp:w { of }
3921 \__cs_tmp:w { Vo }
3922 \__cs_tmp:w { fo }
3923 \__cs_tmp:w { ff }
3924 \__cs_tmp:w { ee }
3925 \__cs_tmp:w { Nx }
3926 \__cs_tmp:w { cx }
3927 \__cs_tmp:w { nx }
3928 \__cs_tmp:w { ox }
3929 \__cs_tmp:w { xo }
3930 \__cs_tmp:w { xx }

```

(End definition for `\exp_args:Nnc` and others. These functions are documented on page 31.)

```

\exp_args:NNcf \exp_args:NNno \exp_args:NNnV \exp_args:NNoo
\exp_args:NNVV \exp_args:Ncno \exp_args:NcnV \exp_args:Ncoo
\exp_args:NcVV \exp_args:Nnnc \exp_args:Nnno \exp_args:Nnnf
\exp_args:Nnff \exp_args:Nooo \exp_args:Noof \exp_args:Nffo
\exp_args:Neee

```



```

3937 \__cs_tmp:w { cnV }
3938 \__cs_tmp:w { coo }
3939 \__cs_tmp:w { cVV }
3940 \__cs_tmp:w { nnc }
3941 \__cs_tmp:w { nno }
3942 \__cs_tmp:w { nnf }
3943 \__cs_tmp:w { nff }
3944 \__cs_tmp:w { ooo }
3945 \__cs_tmp:w { oof }
3946 \__cs_tmp:w { ffo }
3947 \__cs_tmp:w { eee }
3948 \__cs_tmp:w { NNx }
3949 \__cs_tmp:w { Nnx }
3950 \__cs_tmp:w { Nox }
3951 \__cs_tmp:w { nnx }
3952 \__cs_tmp:w { nox }
3953 \__cs_tmp:w { ccx }
3954 \__cs_tmp:w { cnx }
3955 \__cs_tmp:w { oox }

```

(End definition for `\exp_args:NNcf` and others. These functions are documented on page 32.)

```

3956 </initex | package>

```

7 l3quark implementation

The following test files are used for this code: `m3quark001.lvt`.

```

3957 < *initex | package>

```

7.1 Quarks

```

3958 <@@=quark>

```

\quark_new:N Allocate a new quark.

```

3959 \cs_new_protected:Npn \quark_new:N #1
3960 {
3961   \__kernel_chk_if_free_cs:N #1
3962   \cs_gset_nopar:Npn #1 {#1}
3963 }

```

(End definition for `\quark_new:N`. This function is documented on page 38.)

\q_nil Some “public” quarks. `\q_stop` is an “end of argument” marker, `\q_nil` is a empty value and `\q_no_value` marks an empty argument.

```

\q_mark
\q_no_value
\q_stop
3964 \quark_new:N \q_nil
3965 \quark_new:N \q_mark
3966 \quark_new:N \q_no_value
3967 \quark_new:N \q_stop

```

(End definition for `\q_nil` and others. These variables are documented on page 39.)

`\q_recursion_tail` Quarks for ending recursions. Only ever used there! `\q_recursion_tail` is appended to whatever list structure we are doing recursion on, meaning it is added as a proper list item with whatever list separator is in use. `\q_recursion_stop` is placed directly after the list.

```
3968 \quark_new:N \q_recursion_tail
3969 \quark_new:N \q_recursion_stop
```

(End definition for \q_recursion_tail and \q_recursion_stop. These variables are documented on page 39.)

`\s__quark` Private scan mark used in `l3quark`. We don't have `l3scan` yet, so we declare the scan mark here and add it to the scan mark pool later.

```
3970 \cs_new_eq:NN \s__quark \scan_stop:
```

(End definition for \s__quark.)

`\q__quark_nil` Private quark use for some tests.

```
3971 \quark_new:N \q__quark_nil
```

(End definition for \q__quark_nil.)

`\quark_if_recursion_tail_stop:N` When doing recursions, it is easy to spend a lot of time testing if the end marker has been found. To avoid this, a dedicated end marker is used each time a recursion is set up. Thus if the marker is found everything can be wrapper up and finished off. The simple case is when the test can guarantee that only a single token is being tested. In this case, there is just a dedicated copy of the standard quark test. Both a gobbling version and one inserting end code are provided.

```
3972 \cs_new:Npn \quark_if_recursion_tail_stop:N #1
3973 {
3974   \if_meaning:w \q_recursion_tail #1
3975   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
3976   \fi:
3977 }
3978 \cs_new:Npn \quark_if_recursion_tail_stop_do:Nn #1
3979 {
3980   \if_meaning:w \q_recursion_tail #1
3981   \exp_after:wN \use_i_delimit_by_q_recursion_stop:nw
3982   \else:
3983   \exp_after:wN \use_none:n
3984   \fi:
3985 }
```

(End definition for \quark_if_recursion_tail_stop:N and \quark_if_recursion_tail_stop_do:Nn. These functions are documented on page 40.)

`\quark_if_recursion_tail_stop:n` See `\quark_if_nil:nTF` for the details. Expanding `__quark_if_recursion_tail:w` once in front of the tokens chosen here gives an empty result if and only if `#1` is exactly `\q_recursion_tail`.

```
\quark_if_recursion_tail_stop:on
\__quark_if_recursion_tail:w
3986 \cs_new:Npn \quark_if_recursion_tail_stop:n #1
3987 {
3988   \tl_if_empty:oTF
3989   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
3990   { \use_none_delimit_by_q_recursion_stop:w }
3991   { }
```

```

3992 }
3993 \cs_new:Npn \quark_if_recursion_tail_stop_do:nn #1
3994 {
3995   \tl_if_empty:oTF
3996   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
3997   { \use_i_delimit_by_q_recursion_stop:nw }
3998   { \use_none:n }
3999 }
4000 \cs_new:Npn \__quark_if_recursion_tail:w
4001   #1 \q_recursion_tail #2 ? #3 ?! { #1 #2 }
4002 \cs_generate_variant:Nn \quark_if_recursion_tail_stop:n { o }
4003 \cs_generate_variant:Nn \quark_if_recursion_tail_stop_do:nn { o }

```

(End definition for `\quark_if_recursion_tail_stop:n`, `\quark_if_recursion_tail_stop_do:nn`, and `__quark_if_recursion_tail:w`. These functions are documented on page 40.)

`\quark_if_recursion_tail_break:NN`
`\quark_if_recursion_tail_break:nN`

Analogues of the `\quark_if_recursion_tail_stop...` functions. Break the mapping using #2.

```

4004 \cs_new:Npn \quark_if_recursion_tail_break:NN #1#2
4005 {
4006   \if_meaning:w \q_recursion_tail #1
4007   \exp_after:wN #2
4008   \fi:
4009 }
4010 \cs_new:Npn \quark_if_recursion_tail_break:nN #1#2
4011 {
4012   \tl_if_empty:oT
4013   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
4014   {#2}
4015 }

```

(End definition for `\quark_if_recursion_tail_break:NN` and `\quark_if_recursion_tail_break:nN`. These functions are documented on page 40.)

`\quark_if_nil_p:N`
`\quark_if_nil:N \underline{TF}`
`\quark_if_no_value_p:N`
`\quark_if_no_value_p:c`
`\quark_if_no_value:N \underline{TF}`
`\quark_if_no_value:c \underline{TF}`

Here we test if we found a special quark as the first argument. We better start with `\q_no_value` as the first argument since the whole thing may otherwise loop if #1 is wrongly given a string like `aabc` instead of a single token.⁸

```

4016 \prg_new_conditional:Npnn \quark_if_nil:N #1 { p, T , F , TF }
4017 {
4018   \if_meaning:w \q_nil #1
4019   \prg_return_true:
4020   \else:
4021     \prg_return_false:
4022   \fi:
4023 }
4024 \prg_new_conditional:Npnn \quark_if_no_value:N #1 { p, T , F , TF }
4025 {
4026   \if_meaning:w \q_no_value #1
4027   \prg_return_true:
4028   \else:
4029     \prg_return_false:
4030   \fi:
4031 }

```

⁸It may still loop in special circumstances however!

```

4032 \prg_generate_conditional_variant:Nnn \quark_if_no_value:N
4033 { c } { p , T , F , TF }

```

(End definition for \quark_if_nil:NTF and \quark_if_no_value:NTF. These functions are documented on page 39.)

\quark_if_nil_p:n Let us explain \quark_if_nil:n(TF). Expanding __quark_if_nil:w once is safe thanks to the trailing \q_nil ??. The result of expanding once is empty if and only if both delimited arguments #1 and #2 are empty and #3 is delimited by the last tokens ?. Thanks to the leading {}, the argument #1 is empty if and only if the argument of \quark_if_nil:n starts with \q_nil. The argument #2 is empty if and only if this \q_nil is followed immediately by ? or by {}, coming either from the trailing tokens in the definition of \quark_if_nil:n, or from its argument. In the first case, __quark_if_nil:w is followed by {} \q_nil {} ? ! \q_nil ? !, hence #3 is delimited by the final ?!, and the test returns true as wanted. In the second case, the result is not empty since the first ?! in the definition of \quark_if_nil:n stop #3. The auxiliary here is the same as __tl_if_empty_if:o, with the same comments applying.

```

4034 \prg_new_conditional:Npnn \quark_if_nil:n #1 { p , T , F , TF }
4035 {
4036   \__quark_if_empty_if:o
4037   { \__quark_if_nil:w {} #1 {} ? ! \q_nil ? ? ! }
4038   \prg_return_true:
4039   \else:
4040     \prg_return_false:
4041   \fi:
4042 }
4043 \cs_new:Npn \__quark_if_nil:w #1 \q_nil #2 ? #3 ? ! { #1 #2 }
4044 \prg_new_conditional:Npnn \quark_if_no_value:n #1 { p , T , F , TF }
4045 {
4046   \__quark_if_empty_if:o
4047   { \__quark_if_no_value:w {} #1 {} ? ! \q_no_value ? ? ! }
4048   \prg_return_true:
4049   \else:
4050     \prg_return_false:
4051   \fi:
4052 }
4053 \cs_new:Npn \__quark_if_no_value:w #1 \q_no_value #2 ? #3 ? ! { #1 #2 }
4054 \prg_generate_conditional_variant:Nnn \quark_if_nil:n
4055 { V , o } { p , TF , T , F }
4056 \cs_new:Npn \__quark_if_empty_if:o #1
4057 {
4058   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
4059   \__kernel_tl_to_str:w \exp_after:wN {#1} \q_nil
4060 }

```

(End definition for \quark_if_nil:nTF and others. These functions are documented on page 39.)

__kernel_quark_new_test:N The function __kernel_quark_new_test:N defines #1 in a similar way as \quark_if_recursion_tail... functions (as described below), using \q_<namespace>-recursion_tail as the test quark and \q_<namespace>-recursion_stop as the delimiter quark, where the <namespace> is determined as the first _-delimited part in #1.

There are six possible function types which this function can define, and which is defined depends on the signature of the function being defined:

:n gives an analogue of \quark_if_recursion_tail_stop:n
:nn gives an analogue of \quark_if_recursion_tail_stop_do:nn
:nN gives an analogue of \quark_if_recursion_tail_break:nN
:N gives an analogue of \quark_if_recursion_tail_stop:N
:Nn gives an analogue of \quark_if_recursion_tail_stop_do:Nn
:NN gives an analogue of \quark_if_recursion_tail_break:NN

Any other signature causes an error, as does a function without signature.

Similar to __kernel_quark_new_test:N, but defines quark branching conditionals like __kernel_quark_new_conditional:Nn \quark_if_nil:nTF that test for the quark \q_<namespace>_<name>. The <namespace> and <name> are determined from the conditional #1, which must take the rather rigid form __<namespace>_quark_if_<name>:<arg spec>. There are only two cases for the <arg spec> here:

:n gives an analogue of \quark_if_nil:n(TF)
:N gives an analogue of \quark_if_nil:N(TF)

Any other signature causes an error, as does a function without signature. We use low-level emptiness tests as l3tl is not available yet when these functions are used; thankfully we only care about whether strings are empty so a simple \if_meaning:w \q_nil <string> \q_nil suffices.

```

4061 \cs_new_protected:Npn \__kernel_quark_new_test:N #1
4062 { \__quark_new_test_aux:Nx #1 { \__quark_module_name:N #1 } }
4063 \cs_new_protected:Npn \__quark_new_test_aux:Nn #1 #2
4064 {
4065   \if_meaning:w \q_nil #2 \q_nil
4066     \__kernel_msg_error:nxx { kernel } { invalid-quark-function }
4067     { \token_to_str:N #1 }
4068   \else:
4069     \__quark_new_test:Nccn #1
4070     { q_#2_recursion_tail } { q_#2_recursion_stop } { __#2 }
4071   \fi:
4072 }
4073 \cs_generate_variant:Nn \__quark_new_test_aux:Nn { Nx }
4074 \cs_new_protected:Npn \__quark_new_test:NNNn #1
4075 {
4076   \exp_last_unbraced:Nf \__quark_new_test_aux:nnNNnnnn
4077   { \cs_split_function:N #1 }
4078   #1 { test }
4079 }
4080 \cs_generate_variant:Nn \__quark_new_test:NNNn { Ncc }
4081 \cs_new_protected:Npn \__kernel_quark_new_conditional:Nn #1
4082 {
4083   \__quark_new_conditional:Nxxn #1
4084   { \__quark_quark_conditional_name:N #1 }
4085   { \__quark_module_name:N #1 }

```

```

4086 }
4087 \cs_new_protected:Npn \__quark_new_conditional:Nnnn #1#2#3#4
4088 {
4089   \if_meaning:w \q_nil #2 \q_nil
4090   \__kernel_msg_error:nxx { kernel } { invalid-quark-function }
4091   { \token_to_str:N #1 }
4092   \else:
4093   \if_meaning:w \q_nil #3 \q_nil
4094   \__kernel_msg_error:nxx { kernel } { invalid-quark-function }
4095   { \token_to_str:N #1 }
4096   \else:
4097   \exp_last_unbraced:Nf \__quark_new_test_aux:nnNNnnnn
4098   { \cs_split_function:N #1 }
4099   #1 { conditional }
4100   {#2} {#3} {#4}
4101   \fi:
4102   \fi:
4103 }
4104 \cs_generate_variant:Nn \__quark_new_conditional:Nnnn { Nxx }
4105 \cs_new_protected:Npn \__quark_new_test_aux:nnNNnnnn #1 #2 #3 #4 #5
4106 {
4107   \cs_if_exist_use:cTF { __quark_new_#5_#2:Nnnn } { #4 }
4108   {
4109     \__kernel_msg_error:nxxx { kernel } { invalid-quark-function }
4110     { \token_to_str:N #4 } {#2}
4111     \use_none:nnn
4112   }
4113 }

```

(End definition for __kernel_quark_new_test:N and others.)

```

\__quark_new_test_n:Nnnn
\__quark_new_test_nn:Nnnn
\__quark_new_test_N:Nnnn
\__quark_new_test_Nn:Nnnn
\__quark_new_test_NN:Nnnn
\__quark_new_test_NN:Nnnn

```

These macros implement the six possibilities mentioned above, passing the right arguments to __quark_new_test_aux_do:nnNNnnnnNNn, which defines some auxiliaries, and then to __quark_new_test_define_tl:nNnNNn (:n(n) variants) or to __quark_new_test_define_ifx:nNnNNn (:N(n)) which define the main conditionals.

```

4114 \cs_new_protected:Npn \__quark_new_test_n:Nnnn #1 #2 #3 #4
4115 {
4116   \__quark_new_test_aux_do:nnNNnnnnNNn {#4} #2 #3 { none } { } { } { }
4117   \__quark_new_test_define_tl:nNnNNn #1 { }
4118 }
4119 \cs_new_protected:Npn \__quark_new_test_nn:Nnnn #1 #2 #3 #4
4120 {
4121   \__quark_new_test_aux_do:nnNNnnnnNNn {#4} #2 #3 { i } { n } {##1} {##2}
4122   \__quark_new_test_define_tl:nNnNNn #1 { \use_none:n }
4123 }
4124 \cs_new_protected:Npn \__quark_new_test_nN:Nnnn #1 #2 #3 #4
4125 {
4126   \__quark_new_test_aux_do:nnNNnnnnNNn {#4} #2 #3 { i } { n } {##1} {##2}
4127   \__quark_new_test_define_break_tl:nNNNNn #1 { }
4128 }
4129 \cs_new_protected:Npn \__quark_new_test_N:Nnnn #1 #2 #3 #4
4130 {
4131   \__quark_new_test_aux_do:nnNNnnnnNNn {#4} #2 #3 { none } { } { } { }
4132   \__quark_new_test_define_ifx:nNnNNn #1 { }

```

```

4133 }
4134 \cs_new_protected:Npn \__quark_new_test_Nn:Nnnn #1 #2 #3 #4
4135 {
4136   \__quark_new_test_aux_do:nNNnnnnNNn {#4} #2 #3 { i } { n } {##1} {##2}
4137   \__quark_new_test_define_ifx:nNnNNn #1
4138   { \else: \exp_after:wN \use_none:n }
4139 }
4140 \cs_new_protected:Npn \__quark_new_test_NN:Nnnn #1 #2 #3 #4
4141 {
4142   \__quark_new_test_aux_do:nNNnnnnNNn {#4} #2 #3 { i } { n } {##1} {##2}
4143   \__quark_new_test_define_break_ifx:nNNNNn #1 { }
4144 }

```

(End definition for __quark_new_test_n:Nnnn and others.)

__quark_new_test_aux_do:nNNnnnnNNn __quark_new_test_aux_do:nNNnnnnNNn makes the control sequence names which will be used by __quark_test_define_aux:NNNNnnNNn, and then later by __quark_new_test_define_tl:nNnNNn or __quark_new_test_define_ifx:nNnNNn. The control sequences defined here are analogous to __quark_if_recursion_tail:w and to \use_-(none|i)_delimit_by_q_recursion_stop:(|n)w.

The name is composed by the name-space and the name of the quarks. Suppose __kernel_quark_new_test:N was used with:

```
\__kernel_quark_new_test:N \__test_quark_tail:n
```

then the first auxiliary will be __test_quark_recursion_tail:w, and the second one will be __test_use_none_delimit_by_q_recursion_stop:w.

Note that the actual quarks are *not* defined here. They should be defined separately using \quark_new:N.

```

4145 \cs_new_protected:Npn \__quark_new_test_aux_do:nNNnnnnNNn #1 #2 #3 #4 #5
4146 {
4147   \exp_args:Ncc \__quark_test_define_aux:NNNNnnNNn
4148   { #1 \quark_recursion_tail:w }
4149   { #1 \use_#4_delimit_by_q_recursion_stop: #5 w }
4150   #2 #3
4151 }
4152 \cs_new_protected:Npn \__quark_test_define_aux:NNNNnnNNn #1 #2 #3 #4 #5 #6 #7
4153 {
4154   \cs_gset:Npn #1 ##1 #3 ##2 ? ##3 ?! { ##1 ##2 }
4155   \cs_gset:Npn #2 ##1 #6 #4 {#5}
4156   #7 {##1} #1 #2 #3
4157 }

```

(End definition for __quark_new_test_aux_do:nNNnnnnNNn and __quark_test_define_aux:NNNNnnNNn.)

```

\__quark_new_test_define_tl:nNnNNn
\__quark_new_test_define_ifx:nNnNNn
\__quark_new_test_define_break_tl:nNNNNn
\__quark_new_test_define_break_ifx:nNNNNn

```

Finally, these two macros define the main conditional function using what's been set up before.

```

4158 \cs_new_protected:Npn \__quark_new_test_define_tl:nNnNNn #1 #2 #3 #4 #5 #6
4159 {
4160   \cs_new:Npn #5 #1
4161   {
4162     \tl_if_empty:oTF
4163     { #2 {} ##1 {} ?! #4 ??! }
4164     {#3} {#6}

```

```

4165     }
4166   }
4167   \cs_new_protected:Npn \__quark_new_test_define_ifx:nNnNnNn #1 #2 #3 #4 #5 #6
4168   {
4169     \cs_new:Npn #5 #1
4170     {
4171       \if_meaning:w #4 ##1
4172       \exp_after:wN #3
4173       #6
4174       \fi:
4175     }
4176   }
4177   \cs_new_protected:Npn \__quark_new_test_define_break_tl:nNNNNn #1 #2 #3
4178   { \__quark_new_test_define_tl:nNnNnNn {##1##2} #2 {##2} }
4179   \cs_new_protected:Npn \__quark_new_test_define_break_ifx:nNNNNNn #1 #2 #3
4180   { \__quark_new_test_define_ifx:nNnNnNn {##1##2} #2 {##2} }

```

(End definition for __quark_new_test_define_tl:nNnNnNn and others.)

__quark_new_conditional_n:Nnnn These macros implement the two possibilities for branching quark conditionals, passing the right arguments to __quark_new_conditional_aux_do:NNnnn, which defines some auxiliaries and defines the main conditionals.

```

4181   \cs_new_protected:Npn \__quark_new_conditional_n:Nnnn
4182   { \__quark_new_conditional_aux_do:NNnnn \use_i:nn }
4183   \cs_new_protected:Npn \__quark_new_conditional_N:Nnnn
4184   { \__quark_new_conditional_aux_do:NNnnn \use_ii:nn }

```

(End definition for __quark_new_conditional_n:Nnnn and __quark_new_conditional_N:Nnnn.)

__quark_new_conditional_aux_do:NNnnn Similar to the previous macros, but branching conditionals only require one auxiliary, so we take a shortcut. In __quark_new_conditional_define:NNNNn, #4 is \use_i:nn to define the n-type function (which needs an auxiliary) and is \use_ii:nn to define the N-type function.

```

4185   \cs_new_protected:Npn \__quark_new_conditional_aux_do:NNnnn #1 #2 #3 #4
4186   {
4187     \exp_args:Ncc \__quark_new_conditional_define:NNNNn
4188     { __ #4 _if_quark_ #3 :w } { q__ #4 _ #3 } #2 #1
4189   }
4190   \cs_new_protected:Npn \__quark_new_conditional_define:NNNNn #1 #2 #3 #4 #5
4191   {
4192     #4 { \cs_gset:Npn #1 ##1 #2 ##2 ? ##3 ?! { ##1 ##2 } } { }
4193     \exp_args:Nno \use:n { \prg_new_conditional:Npnn #3 ##1 {#5} }
4194     {
4195       #4 { \__quark_if_empty_if:o { #1 {} ##1 {} ?! #2 ??! } }
4196       { \if_meaning:w #2 ##1 }
4197       \prg_return_true: \else: \prg_return_false: \fi:
4198     }
4199   }

```

(End definition for __quark_new_conditional_aux_do:NNnnn and __quark_new_conditional_define:NNNNn.)

__quark_module_name:N __quark_module_name:N takes a control sequence and returns its $\langle module \rangle$ name, determined as the first non-empty non-single-character word, separated by _ or :. These rules give the correct result for public functions \langle module \rangle_..., private functions __-\langle module \rangle_..., and variables such as \l_1\langle module \rangle_.... If no valid module is found the

result is an empty string. The approach is to first cut off everything after the (first) : if any is present, then repeatedly grab `_`-delimited words until finding one of length at least 2 (we use low-level tests as `l3tl` is not fully available when `__kernel_quark_new_test:N` is first used. If no $\langle module \rangle$ is found (such as in `\::n`) we get the trailing marker `\use_none:n {}`, which expands to nothing.

```

4200 \cs_set:Npn \__quark_tmp:w #1#2
4201 {
4202   \cs_new:Npn \__quark_module_name:N ##1
4203   {
4204     \exp_last_unbraced:Nf \__quark_module_name:w
4205     { \cs_to_str:N ##1 } #1 \s__quark
4206   }
4207   \cs_new:Npn \__quark_module_name:w ##1 #1 ##2 \s__quark
4208   { \__quark_module_name_loop:w ##1 #2 \use_none:n { } #2 \s__quark }
4209   \cs_new:Npn \__quark_module_name_loop:w ##1 #2
4210   {
4211     \use_i_ii:nnn \if_meaning:w \prg_do_nothing:
4212     ##1 \prg_do_nothing: \prg_do_nothing:
4213     \exp_after:wN \__quark_module_name_loop:w
4214     \else:
4215       \__quark_module_name_end:w ##1
4216     \fi:
4217   }
4218   \cs_new:Npn \__quark_module_name_end:w
4219   ##1 \fi: ##2 \s__quark { \fi: ##1 }
4220 }
4221 \exp_after:wN \__quark_tmp:w \tl_to_str:n { : _ }

```

(End definition for `__quark_module_name:N` and others.)

`__quark_quark_conditional_name:N` determines the quark name that the quark conditional function `##1` queries, as the part of the function name between `_quark_if_` and the trailing `:`. Again we define it through `__quark_tmp:w`, which receives `:` as `#1` and `_quark_if_` as `#2`. The auxiliary `__quark_quark_conditional_name:w` returns the part between the first `_quark_if_` and the next `:`, and we apply this auxiliary to the function name followed by `:` (in case the function name is lacking a signature), and `_quark_if_:` so that `__quark_quark_conditional_name:N` returns an empty string if `_quark_if_` is not present.

```

4222 \cs_set:Npn \__quark_tmp:w #1 #2 \s__quark
4223 {
4224   \cs_new:Npn \__quark_quark_conditional_name:N ##1
4225   {
4226     \exp_last_unbraced:Nf \__quark_quark_conditional_name:w
4227     { \cs_to_str:N ##1 } #1 #2 #1 \s__quark
4228   }
4229   \cs_new:Npn \__quark_quark_conditional_name:w
4230   ##1 #2 ##2 #1 ##3 \s__quark {##2}
4231 }
4232 \exp_after:wN \__quark_tmp:w \tl_to_str:n { : _quark_if_ } \s__quark

```

(End definition for `__quark_quark_conditional_name:N` and `__quark_quark_conditional_name:w`.)

7.2 Scan marks

4233 `<@@=scan>`

`\g__scan_marks_tl` The list of all scan marks currently declared. No `l3tl` yet, so define this by hand.

4234 `\cs_gset:Npn \g__scan_marks_tl { }`

(End definition for `\g__scan_marks_tl`.)

`\scan_new:N` Check whether the variable is already a scan mark, then declare it to be equal to `\scan_stop`: globally.

```
4235 \cs_new_protected:Npn \scan_new:N #1
4236 {
4237   \tl_if_in:NnTF \g__scan_marks_tl { #1 }
4238   {
4239     \__kernel_msg_error:nxx { kernel } { scanmark-already-defined }
4240     { \token_to_str:N #1 }
4241   }
4242   {
4243     \tl_gput_right:Nn \g__scan_marks_tl {#1}
4244     \cs_new_eq:NN #1 \scan_stop:
4245   }
4246 }
```

(End definition for `\scan_new:N`. This function is documented on page 41.)

`\s_stop` We only declare one scan mark here, more can be defined by specific modules. Can't use `\scan_new:N` yet because `l3tl` isn't loaded, so define `\s_stop` by hand and add it to `\g__scan_marks_tl`. We also add `\s__quark` (declared earlier) to the pool here. Since it lives in a different namespace, a little `l3docstrip` cheating is necessary.

```
4247 \cs_new_eq:NN \s_stop \scan_stop:
4248 \cs_gset_nopar:Npx \g__scan_marks_tl
4249 {
4250   \exp_not:o \g__scan_marks_tl
4251   \s_stop
4252   <@@=quark>
4253   \s__quark
4254   <@@=scan>
4255 }
```

(End definition for `\s_stop`. This variable is documented on page 42.)

`\use_none_delimit_by_s_stop:w` Similar to `\use_none_delimit_by_q_stop:w`.

4256 `\cs_new:Npn \use_none_delimit_by_s_stop:w #1 \s_stop { }`

(End definition for `\use_none_delimit_by_s_stop:w`. This function is documented on page 42.)

4257 `</initex | package>`

8 l3tl implementation

4258 $\langle *initex | package \rangle$

4259 $\langle @@=tl \rangle$

A token list variable is a \TeX macro that holds tokens. By using the $\varepsilon\text{-TeX}$ primitive \unexpanded inside a \TeX \edef it is possible to store any tokens, including $\#$, in this way.

8.1 Functions

\tl_new:N Creating new token list variables is a case of checking for an existing definition and doing the definition.

\tl_new:c

```

4260 \cs_new_protected:Npn \tl_new:N #1
4261 {
4262   \__kernel_chk_if_free_cs:N #1
4263   \cs_gset_eq:NN #1 \c_empty_tl
4264 }
4265 \cs_generate_variant:Nn \tl_new:N { c }
```

(End definition for \tl_new:N . This function is documented on page 43.)

\tl_const:Nn Constants are also easy to generate.

\tl_const:Nx

```

4266 \cs_new_protected:Npn \tl_const:Nn #1#2
4267 {
4268   \__kernel_chk_if_free_cs:N #1
4269   \cs_gset_nopar:Npx #1 { \exp_not:n {#2} }
4270 }
4271 \cs_new_protected:Npn \tl_const:Nx #1#2
4272 {
4273   \__kernel_chk_if_free_cs:N #1
4274   \cs_gset_nopar:Npx #1 {#2}
4275 }
4276 \cs_generate_variant:Nn \tl_const:Nn { c }
4277 \cs_generate_variant:Nn \tl_const:Nx { c }
```

(End definition for \tl_const:Nn . This function is documented on page 43.)

\tl_clear:N Clearing a token list variable means setting it to an empty value. Error checking is sorted out by the parent function.

\tl_clear:c

```

4278 \cs_new_protected:Npn \tl_clear:N #1
4279 { \tl_set_eq:NN #1 \c_empty_tl }
4280 \cs_new_protected:Npn \tl_gclear:N #1
4281 { \tl_gset_eq:NN #1 \c_empty_tl }
4282 \cs_generate_variant:Nn \tl_clear:N { c }
4283 \cs_generate_variant:Nn \tl_gclear:N { c }
```

(End definition for \tl_clear:N and \tl_gclear:N . These functions are documented on page 43.)

\tl_clear_new:N Clearing a token list variable means setting it to an empty value. Error checking is sorted out by the parent function.

\tl_clear_new:c

```

4284 \cs_new_protected:Npn \tl_clear_new:N #1
4285 { \tl_if_exist:NTF #1 { \tl_clear:N #1 } { \tl_new:N #1 } }
4286 \cs_new_protected:Npn \tl_gclear_new:N #1
4287 { \tl_if_exist:NTF #1 { \tl_gclear:N #1 } { \tl_new:N #1 } }
4288 \cs_generate_variant:Nn \tl_clear_new:N { c }
4289 \cs_generate_variant:Nn \tl_gclear_new:N { c }
```

(End definition for `\tl_clear_new:N` and `\tl_gclear_new:N`. These functions are documented on page 44.)

`\tl_set_eq:NN` For setting token list variables equal to each other. To allow for patching, the arguments have to be explicit.

`\tl_set_eq:Nc`

`\tl_set_eq:cN` 4290 `\cs_new_protected:Npn \tl_set_eq:NN #1#2 { \cs_set_eq:NN #1 #2 }`

`\tl_set_eq:cc` 4291 `\cs_new_protected:Npn \tl_gset_eq:NN #1#2 { \cs_gset_eq:NN #1 #2 }`

`\tl_gset_eq:NN` 4292 `\cs_generate_variant:Nn \tl_set_eq:NN { cN, Nc, cc }`

`\tl_gset_eq:Nc` 4293 `\cs_generate_variant:Nn \tl_gset_eq:NN { cN, Nc, cc }`

`\tl_gset_eq:cN`

`\tl_gset_eq:cc` (End definition for `\tl_set_eq:NN` and `\tl_gset_eq:NN`. These functions are documented on page 44.)

`\tl_concat:NNN` Concatenating token lists is easy. When checking is turned on, all three arguments must be checked: a token list #2 or #3 equal to `\scan_stop:` would lead to problems later on.

`\tl_concat:ccc`

`\tl_gconcat:NNN` 4294 `\cs_new_protected:Npn \tl_concat:NNN #1#2#3`

`\tl_gconcat:ccc` 4295 `{ \tl_set:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }`

4296 `\cs_new_protected:Npn \tl_gconcat:NNN #1#2#3`

4297 `{ \tl_gset:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }`

4298 `\cs_generate_variant:Nn \tl_concat:NNN { ccc }`

4299 `\cs_generate_variant:Nn \tl_gconcat:NNN { ccc }`

(End definition for `\tl_concat:NNN` and `\tl_gconcat:NNN`. These functions are documented on page 44.)

`\tl_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.

`\tl_if_exist_p:c` 4300 `\prg_new_eq_conditional:NNn \tl_if_exist:N \cs_if_exist:N { TF , T , F , p }`

`\tl_if_exist:N \underline{TF}` 4301 `\prg_new_eq_conditional:NNn \tl_if_exist:c \cs_if_exist:c { TF , T , F , p }`

`\tl_if_exist:c \underline{TF}`

(End definition for `\tl_if_exist:N \underline{TF}` . This function is documented on page 44.)

8.2 Constant token lists

`\c_empty_tl` Never full. We need to define that constant before using `\tl_new:N`.

4302 `\tl_const:Nn \c_empty_tl { }`

(End definition for `\c_empty_tl`. This variable is documented on page 58.)

`\c_novalue_tl` A special marker: as we don't have `\char_generate:nn` yet, has to be created the old-fashioned way.

4303 `\group_begin:`

4304 `\tex_lccode:D 'A = '-`

4305 `\tex_lccode:D 'N = 'N`

4306 `\tex_lccode:D 'V = 'V`

4307 `\tex_lowercase:D`

4308 `{`

4309 `\group_end:`

4310 `\tl_const:Nn \c_novalue_tl { ANoValue-`

4311 `}`

(End definition for `\c_novalue_tl`. This variable is documented on page 58.)

`\c_space_tl` A space as a token list (as opposed to as a character).

4312 `\tl_const:Nn \c_space_tl { ~ }`

(End definition for `\c_space_tl`. This variable is documented on page 58.)

8.3 Adding to token list variables

By using `\exp_not:n` token list variables can contain `#` tokens, which makes the token list registers provided by T_EX more or less redundant. The `\tl_set:No` version is done “by hand” as it is used quite a lot.

```

\tl_set:Nn 4313 \cs_new_protected:Npn \tl_set:Nn #1#2
\tl_set:NV 4314 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} } }
\tl_set:Nv
\tl_set:No
\tl_set:Nf 4315 \cs_new_protected:Npn \tl_set:No #1#2
\tl_set:Nx 4316 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} } }
\tl_set:cn 4317 \cs_new_protected:Npn \tl_set:Nx #1#2
\tl_set:cV 4318 { \cs_set_nopar:Npx #1 {#2} }
\tl_set:cV 4319 \cs_new_protected:Npn \tl_gset:Nn #1#2
\tl_set:co 4320 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} } }
\tl_set:cf 4321 \cs_new_protected:Npn \tl_gset:No #1#2
\tl_set:cx 4322 { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} } }
\tl_gset:Nn 4323 \cs_new_protected:Npn \tl_gset:Nx #1#2
\tl_gset:NV 4324 { \cs_gset_nopar:Npx #1 {#2} }
\tl_gset:Nv 4325 \cs_generate_variant:Nn \tl_set:Nn { NV , Nv , Nf }
\tl_gset:No 4326 \cs_generate_variant:Nn \tl_set:Nx { c }
\tl_gset:Nf 4327 \cs_generate_variant:Nn \tl_set:Nn { c , co , cV , cv , cf }
\tl_gset:Nx 4328 \cs_generate_variant:Nn \tl_gset:Nn { NV , Nv , Nf }
\tl_gset:cn 4329 \cs_generate_variant:Nn \tl_gset:Nx { c }
\tl_gset:cV 4330 \cs_generate_variant:Nn \tl_gset:Nn { c , co , cV , cv , cf }
\tl_gset:cV
\tl_gset:co

```

(End definition for `\tl_set:Nn` and `\tl_gset:Nn`. These functions are documented on page 44.)

Adding to the left is done directly to gain a little performance.

```

\tl_put_left:Nn 4331 \cs_new_protected:Npn \tl_put_left:Nn #1#2
\tl_put_left:NV 4332 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
\tl_put_left:No 4333 \cs_new_protected:Npn \tl_put_left:Nv #1#2
\tl_put_left:Nx 4334 { \cs_set_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
\tl_put_left:cn 4335 \cs_new_protected:Npn \tl_put_left:No #1#2
\tl_put_left:cV 4336 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
\tl_put_left:co 4337 \cs_new_protected:Npn \tl_put_left:Nx #1#2
\tl_put_left:cx 4338 { \cs_set_nopar:Npx #1 { #2 \exp_not:o #1 } }
\tl_gput_left:Nn 4339 \cs_new_protected:Npn \tl_gput_left:Nn #1#2
\tl_gput_left:NV 4340 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
\tl_gput_left:No 4341 \cs_new_protected:Npn \tl_gput_left:Nv #1#2
\tl_gput_left:Nx 4342 { \cs_gset_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
\tl_gput_left:cn 4343 \cs_new_protected:Npn \tl_gput_left:No #1#2
\tl_gput_left:cV 4344 { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
\tl_gput_left:co 4345 \cs_new_protected:Npn \tl_gput_left:Nx #1#2
\tl_gput_left:cx 4346 { \cs_gset_nopar:Npx #1 { #2 \exp_not:o {#1} } }
4347 \cs_generate_variant:Nn \tl_put_left:Nn { c }
4348 \cs_generate_variant:Nn \tl_put_left:Nv { c }
4349 \cs_generate_variant:Nn \tl_put_left:No { c }
4350 \cs_generate_variant:Nn \tl_put_left:Nx { c }
4351 \cs_generate_variant:Nn \tl_gput_left:Nn { c }
4352 \cs_generate_variant:Nn \tl_gput_left:Nv { c }
4353 \cs_generate_variant:Nn \tl_gput_left:No { c }
4354 \cs_generate_variant:Nn \tl_gput_left:Nx { c }

```

(End definition for `\tl_put_left:Nn` and `\tl_gput_left:Nn`. These functions are documented on page 44.)

\tl_put_right:Nn The same on the right.

```

\tl_put_right:NV 4355 \cs_new_protected:Npn \tl_put_right:Nn #1#2
\tl_put_right:No 4356 { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
\tl_put_right:Nx 4357 \cs_new_protected:Npn \tl_put_right:NV #1#2
\tl_put_right:cn 4358 { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
\tl_put_right:cV 4359 \cs_new_protected:Npn \tl_put_right:No #1#2
\tl_put_right:co 4360 { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
\tl_put_right:cx 4361 \cs_new_protected:Npn \tl_put_right:Nx #1#2
\tl_gput_right:Nn 4362 { \cs_set_nopar:Npx #1 { \exp_not:o #1 #2 } }
\tl_gput_right:NV 4363 \cs_new_protected:Npn \tl_gput_right:Nn #1#2
\tl_gput_right:No 4364 { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
\tl_gput_right:Nx 4365 \cs_new_protected:Npn \tl_gput_right:NV #1#2
\tl_gput_right:cn 4366 { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
\tl_gput_right:cV 4367 \cs_new_protected:Npn \tl_gput_right:No #1#2
\tl_gput_right:co 4368 { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
\tl_gput_right:cx 4369 \cs_new_protected:Npn \tl_gput_right:Nx #1#2
4370 { \cs_gset_nopar:Npx #1 { \exp_not:o {#1} #2 } }
4371 \cs_generate_variant:Nn \tl_put_right:Nn { c }
4372 \cs_generate_variant:Nn \tl_put_right:NV { c }
4373 \cs_generate_variant:Nn \tl_put_right:No { c }
4374 \cs_generate_variant:Nn \tl_put_right:Nx { c }
4375 \cs_generate_variant:Nn \tl_gput_right:Nn { c }
4376 \cs_generate_variant:Nn \tl_gput_right:NV { c }
4377 \cs_generate_variant:Nn \tl_gput_right:No { c }
4378 \cs_generate_variant:Nn \tl_gput_right:Nx { c }

```

(End definition for \tl_put_right:Nn and \tl_gput_right:Nn. These functions are documented on page 44.)

8.4 Internal quarks and quark-query functions

\q__tl_nil Internal quarks.

```

\q__tl_mark 4379 \quark_new:N \q__tl_nil
\q__tl_stop 4380 \quark_new:N \q__tl_mark
4381 \quark_new:N \q__tl_stop

```

(End definition for \q__tl_nil, \q__tl_mark, and \q__tl_stop.)

\q__tl_recursion_tail Internal recursion quarks.

```

\q__tl_recursion_stop 4382 \quark_new:N \q__tl_recursion_tail
4383 \quark_new:N \q__tl_recursion_stop

```

(End definition for \q__tl_recursion_tail and \q__tl_recursion_stop.)

_tl_if_recursion_tail_break:nN Functions to query recursion quarks.

```

\_tl_if_recursion_tail_stop_p:n 4384 \__kernel_quark_new_test:N \_tl_if_recursion_tail_break:nN
\_tl_if_recursion_tail_stop:nTF 4385 \__kernel_quark_new_conditional:Nn \_tl_quark_if_nil:n { TF }

```

(End definition for _tl_if_recursion_tail_break:nN and _tl_if_recursion_tail_stop:nTF.)

8.5 Reassigning token list category codes

`\c__tl_rescan_marker_tl`

The rescanning code needs a special token list containing the same character (chosen here to be a colon) with two different category codes: it cannot appear in the tokens being rescanned since all colons have the same category code.

```
4386 \tl_const:Nx \c__tl_rescan_marker_tl { : \token_to_str:N : }
```

(End definition for `\c__tl_rescan_marker_tl`.)

`\tl_set_rescan:Nnn`

In a group, after some initial setup explained below and the user setup #3 (followed by `\scan_stop:` to be safe), there is a call to `__tl_set_rescan:nNN`. This shared auxiliary defined later distinguishes single-line and multi-line “files”. In the simplest case of multi-line files, it calls (with the same arguments) `__tl_set_rescan_multi:nNN`, whose code is included here to help understand the approach. This function rescans its argument #1, closes the group, and performs the assignment.

`\tl_set_rescan:Nno`

One difficulty when rescanning is that `\scantokens` treats the argument as a file, and without the correct settings a T_EX error occurs:

`\tl_set_rescan:Nnx`

```
! File ended while scanning definition of ...
```

`\tl_set_rescan:cnn`

A related minor issue is a warning due to opening a group before the `\scantokens` and closing it inside that temporary file; we avoid that by setting `\tracingnesting`. The standard solution to the “File ended” error is to grab the rescanned tokens as a delimited argument of an auxiliary, here `__tl_rescan:NNw`, that performs the assignment, then let T_EX “execute” the end of file marker. As usual in delimited arguments we use `\prg_do_nothing:` to avoid stripping an outer set braces: this is removed by using `o`-expanding assignments. The delimiter cannot appear within the rescanned token list because it contains twice the same character, with different catcodes.

`\tl_set_rescan:cno`

`\tl_set_rescan:cnx`

`\tl_gset_rescan:Nnn`

`\tl_gset_rescan:Nno`

`\tl_gset_rescan:Nnx`

`\tl_gset_rescan:cnn`

`\tl_gset_rescan:cno`

`\tl_gset_rescan:cnx`

`\tl_rescan:nn`

`__tl_set_rescan:NNnn`

`__tl_set_rescan_multi:nNN`

`__tl_rescan:NNw`

For `\tl_rescan:nn` we cannot simply call `__tl_set_rescan:NNnn \prg_do_nothing: \use:n` because that would leave the end-of-file marker *after* the result of rescanning. If that rescanned result is code that looks further in the input stream for arguments, it would break.

For multi-line files the only subtlety is that `\newlinechar` should be equal to `\endlinechar` because `\newlinechar` characters become new lines and then become `\endlinechar` characters when writing to an abstract file and reading back. This equality is ensured by setting `\newlinechar` equal to `\endlinechar`. Prior to this, `\endlinechar` is set to `-1` if it was `32` (in particular true after `\ExplSyntaxOn`) to avoid unreasonable line-breaks at every space for instance in error messages triggered by the user setup. Another side effect of reading back from the file is that spaces (catcode 10) are ignored at the beginning of lines, and spaces and tabs (character code 32 and 9) are ignored at the end of lines.

The two `\if_false: ... \fi:` are there to prevent alignment tabs to cause a change of tabular cell while rescanning. We put the “opening” one after `\group_begin:` so that if one accidentally `f`-expands `\tl_set_rescan:Nnn` braces remain balanced. This is essential in `e`-type arguments when `\expanded` is not available.

```
4387 \cs_new_protected:Npn \tl_rescan:nn #1#2
4388 {
4389   \tl_set_rescan:Nnn \l__tl_internal_a_tl {#1} {#2}
4390   \exp_after:wN \tl_clear:N \exp_after:wN \l__tl_internal_a_tl
4391   \l__tl_internal_a_tl
4392 }
4393 \cs_new_protected:Npn \tl_set_rescan:Nnn
```

```

4394 { \_tl\_set\_rescan:NNnn \tl\_set:No }
4395 \cs\_new\_protected:Npn \tl\_gset\_rescan:Nnn
4396 { \_tl\_set\_rescan:NNnn \tl\_gset:No }
4397 \cs\_new\_protected:Npn \_tl\_set\_rescan:NNnn #1#2#3#4
4398 {
4399   \group\_begin:
4400   \if\_false: { \fi:
4401     \int\_set\_eq:NN \tex\_tracingnesting:D \c\_zero\_int
4402     \int\_compare:nNnT \tex\_endlinechar:D = { 32 }
4403     { \int\_set:Nn \tex\_endlinechar:D { -1 } }
4404     \int\_set\_eq:NN \tex\_newlinechar:D \tex\_endlinechar:D
4405     #3 \scan\_stop:
4406     \exp\_args:No \_tl\_set\_rescan:nNN { \tl\_to\_str:n {#4} } #1 #2
4407   \if\_false: } \fi:
4408 }
4409 \cs\_new\_protected:Npn \_tl\_set\_rescan\_multi:nNN #1#2#3
4410 {
4411   \exp\_args:No \tex\_everyeof:D { \c\_tl\_rescan\_marker\_tl }
4412   \exp\_after:wN \_tl\_rescan:NNw
4413   \exp\_after:wN #2
4414   \exp\_after:wN #3
4415   \exp\_after:wN \prg\_do\_nothing:
4416   \tex\_scantokens:D {#1}
4417 }
4418 \exp\_args:Nno \use:n
4419 { \cs\_new:Npn \_tl\_rescan:NNw #1#2#3 } \c\_tl\_rescan\_marker\_tl
4420 {
4421   \group\_end:
4422   #1 #2 {#3}
4423 }
4424 \cs\_generate\_variant:Nn \tl\_set\_rescan:Nnn { Nno , Nnx }
4425 \cs\_generate\_variant:Nn \tl\_set\_rescan:Nnn { c , cno , cnx }
4426 \cs\_generate\_variant:Nn \tl\_gset\_rescan:Nnn { Nno , Nnx }
4427 \cs\_generate\_variant:Nn \tl\_gset\_rescan:Nnn { c , cno }

```

(End definition for `\tl_set_rescan:Nnn` and others. These functions are documented on page 46.)

<pre> _tl_set_rescan:nNN _tl_set_rescan_single:nnNN _tl_set_rescan_single_aux:nnnNN _tl_set_rescan_single_aux:w </pre>	<p>The function <code>_tl_set_rescan:nNN</code> calls <code>_tl_set_rescan_multi:nNN</code> or <code>_tl_set_rescan_single:nnNN { ' }</code> depending on whether its argument is a single-line fragment of code/data or is made of multiple lines by testing for the presence of a <code>\newlinechar</code> character. If <code>\newlinechar</code> is out of range, the argument is assumed to be a single line.</p>
---	--

For a single line, no `\endlinechar` should be added, so it is set to `-1`, and spaces should not be removed. Trailing spaces and tabs are a difficult matter, as `TEX` removes these at a very low level. The only way to preserve them is to rescan not the argument but the argument followed by a character with a reasonable category code. Here, 11 (letter) and 12 (other) are accepted, as these are convenient, suitable for delimiting an argument, and it is very unlikely that none of the ASCII characters are in one of these categories. To avoid selecting one particular character to put at the end, whose category code may have been modified, there is a loop through characters from `'` (ASCII 39) to `~` (ASCII 127). The choice of starting point was made because this is the start of a very long range of characters whose standard category is letter or other, thus minimizing the

number of steps needed by the loop (most often just a single one). If no valid character is found (very rare), fall-back on `__tl_set_rescan_multi:nnN`.

Otherwise, once a valid character is found (let us use `'` in this explanation) run some code very similar to `__tl_set_rescan_multi:nnN` but with `'` added at both ends of the input. Of course, we need to define the auxiliary `__tl_set_rescan_single:NNww` on the fly to remove the additional `'` that is just before `::` (by which we mean `\c__tl_rescan_marker_tl`). Note that the argument must be delimited by `'` with the current catcode; this is done thanks to `\char_generate:nn`. Yet another issue is that the rescanned token list may contain a comment character, in which case the `'` we expected is not there. We fix this as follows: rather than just `::` we set `\everyeof` to `::{<code1>}` `'::<code2>}` `\s__tl_stop`. The auxiliary `__tl_set_rescan_single:NNww` runs the o-expanding assignment, expanding either `<code1>` or `<code2>` before its the main argument `#3`. In the typical case without comment character, `<code1>` is expanded, removing the leading `'`. In the rarer case with comment character, `<code2>` is expanded, calling `__tl_set_rescan_single_aux:w`, which removes the trailing `::{<code1>}` and the leading `'`.

```

4428 \cs_new_protected:Npn \__tl_set_rescan:nnN #1
4429 {
4430   \int_compare:nNnTF \tex_newlinechar:D < 0
4431   { \use_i:nn }
4432   {
4433     \exp_args:Nnf \tl_if_in:nnTF {#1}
4434     { \char_generate:nn { \tex_newlinechar:D } { 12 } }
4435   }
4436   { \__tl_set_rescan_multi:nnN }
4437   {
4438     \int_set:Nn \tex_endlinechar:D { -1 }
4439     \__tl_set_rescan_single:nnNN { ' ' }
4440   }
4441   {#1}
4442 }
4443 \cs_new_protected:Npn \__tl_set_rescan_single:nnNN #1
4444 {
4445   \int_compare:nNnTF
4446   { \char_value_catcode:n {#1} / 2 } = 6
4447   {
4448     \exp_args:Nof \__tl_set_rescan_single_aux:nnnNN
4449     \c__tl_rescan_marker_tl
4450     { \char_generate:nn {#1} { \char_value_catcode:n {#1} } }
4451   }
4452   {
4453     \int_compare:nNnTF {#1} < { '\~ }
4454     {
4455       \exp_args:Nf \__tl_set_rescan_single:nnNN
4456       { \int_eval:n { #1 + 1 } }
4457     }
4458     { \__tl_set_rescan_multi:nnN }
4459   }
4460 }
4461 \cs_new_protected:Npn \__tl_set_rescan_single_aux:nnnNN #1#2#3#4#5
4462 {
4463   \tex_everyeof:D

```

```

4464     {
4465       #1 \use_none:n
4466       #2 #1 { \exp:w \__tl_set_rescan_single_aux:w }
4467       \s__tl_stop
4468     }
4469 \cs_set:Npn \__tl_rescan:NNw ##1##2##3 #2 #1 ##4 ##5 \s__tl_stop
4470 {
4471   \group_end:
4472   ##1 ##2 { ##4 ##3 }
4473 }
4474 \exp_after:wN \__tl_rescan:NNw
4475 \exp_after:wN #4
4476 \exp_after:wN #5
4477 \tex_scantokens:D { #2 #3 #2 }
4478 }
4479 \exp_args:Nno \use:nn
4480 { \cs_new:Npn \__tl_set_rescan_single_aux:w #1 }
4481 \c__tl_rescan_marker_tl #2
4482 { \use_i:nn \exp_end: #1 }

```

(End definition for `__tl_set_rescan:nNN` and others.)

8.6 Modifying token list variables

`\tl_replace_all:Nnn` All of the `replace` functions call `__tl_replace:NnNNNnn` with appropriate arguments. The first two arguments are explained later. The next controls whether the replacement function calls itself (`__tl_replace_next:w`) or stops (`__tl_replace_wrap:w`) after the first replacement. Next comes an x-type assignment function `\tl_set:Nx` or `\tl_gset:Nx` for local or global replacements. Finally, the three arguments $\langle tl\ var \rangle \{ \langle pattern \rangle \} \{ \langle replacement \rangle \}$ provided by the user. When describing the auxiliary functions below, we denote the contents of the $\langle tl\ var \rangle$ by $\langle token\ list \rangle$.

```

\tl_replace_all:cnn
\tl_greplace_all:Nnn
\tl_replace_once:cnn
\tl_greplace_once:Nnn
\tl_greplace_once:cnn
4483 \cs_new_protected:Npn \tl_replace_once:Nnn
4484 { \__tl_replace:NnNNNnn \q__tl_mark ? \__tl_replace_wrap:w \tl_set:Nx }
4485 \cs_new_protected:Npn \tl_greplace_once:Nnn
4486 { \__tl_replace:NnNNNnn \q__tl_mark ? \__tl_replace_wrap:w \tl_gset:Nx }
4487 \cs_new_protected:Npn \tl_replace_all:Nnn
4488 { \__tl_replace:NnNNNnn \q__tl_mark ? \__tl_replace_next:w \tl_set:Nx }
4489 \cs_new_protected:Npn \tl_greplace_all:Nnn
4490 { \__tl_replace:NnNNNnn \q__tl_mark ? \__tl_replace_next:w \tl_gset:Nx }
4491 \cs_generate_variant:Nn \tl_replace_once:Nnn { c }
4492 \cs_generate_variant:Nn \tl_greplace_once:Nnn { c }
4493 \cs_generate_variant:Nn \tl_replace_all:Nnn { c }
4494 \cs_generate_variant:Nn \tl_greplace_all:Nnn { c }

```

(End definition for `\tl_replace_all:Nnn` and others. These functions are documented on page 45.)

`__tl_replace:NnNNNnn` To implement the actual replacement auxiliary `__tl_replace_auxii:nNNNnn` we need a $\langle delimiter \rangle$ with the following properties:

- all occurrences of the $\langle pattern \rangle$ #6 in “ $\langle token\ list \rangle \langle delimiter \rangle$ ” belong to the $\langle token\ list \rangle$ and have no overlap with the $\langle delimiter \rangle$,
- the first occurrence of the $\langle delimiter \rangle$ in “ $\langle token\ list \rangle \langle delimiter \rangle$ ” is the trailing $\langle delimiter \rangle$.

We first find the building blocks for the $\langle \text{delimiter} \rangle$, namely two tokens $\langle A \rangle$ and $\langle B \rangle$ such that $\langle A \rangle$ does not appear in $\#6$ and $\#6$ is not $\langle B \rangle$ (this condition is trivial if $\#6$ has more than one token). Then we consider the delimiters “ $\langle A \rangle$ ” and “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ”, for $n \geq 1$, where $\langle A \rangle^n$ denotes n copies of $\langle A \rangle$, and we choose as our $\langle \text{delimiter} \rangle$ the first one which is not in the $\langle \text{token list} \rangle$.

Every delimiter in the set obeys the first condition: $\#6$ does not contain $\langle A \rangle$ hence cannot be overlapping with the $\langle \text{token list} \rangle$ and the $\langle \text{delimiter} \rangle$, and it cannot be within the $\langle \text{delimiter} \rangle$ since it would have to be in one of the two $\langle B \rangle$ hence be equal to this single token (or empty, but this is an error case filtered separately). Given the particular form of these delimiters, for which no prefix is also a suffix, the second condition is actually a consequence of the weaker condition that the $\langle \text{delimiter} \rangle$ we choose does not appear in the $\langle \text{token list} \rangle$. Additionally, the set of delimiters is such that a $\langle \text{token list} \rangle$ of n tokens can contain at most $O(n^{1/2})$ of them, hence we find a $\langle \text{delimiter} \rangle$ with at most $O(n^{1/2})$ tokens in a time at most $O(n^{3/2})$. Bear in mind that these upper bounds are reached only in very contrived scenarios: we include the case “ $\langle A \rangle$ ” in the list of delimiters to try, so that the $\langle \text{delimiter} \rangle$ is simply $\backslash \text{q_tl_mark}$ in the most common situation where neither the $\langle \text{token list} \rangle$ nor the $\langle \text{pattern} \rangle$ contains $\backslash \text{q_tl_mark}$.

Let us now ahead, optimizing for this most common case. First, two special cases: an empty $\langle \text{pattern} \rangle$ $\#6$ is an error, and if $\#1$ is absent from both the $\langle \text{token list} \rangle$ $\#5$ and the $\langle \text{pattern} \rangle$ $\#6$ then we can use it as the $\langle \text{delimiter} \rangle$ through $\backslash \text{__tl_replace_auxii:nNNNnn} \{ \#1 \}$. Otherwise, we end up calling $\backslash \text{__tl_replace:NnNNNnn}$ repeatedly with the first two arguments $\backslash \text{q_tl_mark} \{ ? \}$, $\backslash ? \{ ?? \}$, $\backslash ?? \{ ??? \}$, and so on, until $\#6$ does not contain the control sequence $\#1$, which we take as our $\langle A \rangle$. The argument $\#2$ only serves to collect $?$ characters for $\#1$. Note that the order of the tests means that the first two are done every time, which is wasteful (for instance, we repeatedly test for the emptiness of $\#6$). However, this is rare enough not to matter. Finally, choose $\langle B \rangle$ to be $\backslash \text{q_tl_nil}$ or $\backslash \text{q_tl_stop}$ such that it is not equal to $\#6$.

The $\backslash \text{__tl_replace_auxi:NnnNNNnn}$ auxiliary receives $\{ \langle A \rangle \}$ and $\{ \langle A \rangle^n \langle B \rangle \}$ as its arguments, initially with $n = 1$. If “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ” is in the $\langle \text{token list} \rangle$ then increase n and try again. Once it is not anymore in the $\langle \text{token list} \rangle$ we take it as our $\langle \text{delimiter} \rangle$ and pass this to the auxii auxiliary.

```

4495 \cs_new_protected:Npn \__tl_replace:NnNNNnn #1#2#3#4#5#6#7
4496 {
4497   \tl_if_empty:nTF {#6}
4498   {
4499     \__kernel_msg_error:nxx { kernel } { empty-search-pattern }
4500     { \tl_to_str:n {#7} }
4501   }
4502   {
4503     \tl_if_in:onTF { #5 #6 } {#1}
4504     {
4505       \tl_if_in:nnTF {#6} {#1}
4506       { \exp_args:Nc \__tl_replace:NnNNNnn {#2} {#2?} }
4507       {
4508         \__tl_quark_if_nil:nTF {#6}
4509         { \__tl_replace_auxi:NnnNNNnn #5 {#1} { #1 \q_tl_stop } }
4510         { \__tl_replace_auxi:NnnNNNnn #5 {#1} { #1 \q_tl_nil } }
4511       }
4512     }
4513     { \__tl_replace_auxii:nNNNnn {#1} }
4514     #3#4#5 {#6} {#7}

```

```

4515     }
4516   }
4517   \cs_new_protected:Npn \__tl_replace_auxi:NnnNNNnn #1#2#3
4518   {
4519     \tl_if_in:NnTF #1 { #2 #3 #3 }
4520     { \__tl_replace_auxi:NnnNNNnn #1 { #2 #3 } {#2} }
4521     { \__tl_replace_auxii:nNNNnn { #2 #3 #3 } }
4522   }

```

The auxiliary `__tl_replace_auxii:nNNNnn` receives the following arguments:

```

{<delimiter>} <function> <assignment>
<tl var> {<pattern>} {<replacement>}

```

All of its work is done between `\group_align_safe_begin:` and `\group_align_safe_end:` to avoid issues in alignments. It does the actual replacement within `#3 #4 {...}`, an x-expanding `<assignment> #3` to the `<tl var> #4`. The auxiliary `__tl_replace_next:w` is called, followed by the `<token list>`, some tokens including the `<delimiter> #1`, followed by the `<pattern> #5`. This auxiliary finds an argument delimited by `#5` (the presence of a trailing `#5` avoids runaway arguments) and calls `__tl_replace_wrap:w` to test whether this `#5` is found within the `<token list>` or is the trailing one.

If on the one hand it is found within the `<token list>`, then `##1` cannot contain the `<delimiter> #1` that we worked so hard to obtain, thus `__tl_replace_wrap:w` gets `##1` as its own argument `##1`, and protects it against the x-expanding assignment. It also finds `\exp_not:n` as `##2` and does nothing to it, thus letting through `\exp_not:n {<replacement>}` into the assignment. Note that `__tl_replace_next:w` and `__tl_replace_wrap:w` are always called followed by two empty brace groups. These are safe because no delimiter can match them. They prevent losing braces when grabbing delimited arguments, but require the use of `\exp_not:o` and `\use_none:nn`, rather than simply `\exp_not:n`. Afterwards, `__tl_replace_next:w` is called to repeat the replacement, or `__tl_replace_wrap:w` if we only want a single replacement. In this second case, `##1` is the `<remaining tokens>` in the `<token list>` and `##2` is some `<ending code>` which ends the assignment and removes the trailing tokens `#5` using some `\if_false: { \fi: }` trickery because `#5` may contain any delimiter.

If on the other hand the argument `##1` of `__tl_replace_next:w` is delimited by the trailing `<pattern> #5`, then `##1` is “`{ } { } <token list> <delimiter> {<ending code>}`”, hence `__tl_replace_wrap:w` finds “`{ } { } <token list>`” as `##1` and the `<ending code>` as `##2`. It leaves the `<token list>` into the assignment and unbraces the `<ending code>` which removes what remains (essentially the `<delimiter>` and `<replacement>`).

```

4523   \cs_new_protected:Npn \__tl_replace_auxii:nNNNnn #1#2#3#4#5#6
4524   {
4525     \group_align_safe_begin:
4526     \cs_set:Npn \__tl_replace_wrap:w ##1 #1 ##2
4527     { \exp_not:o { \use_none:nn ##1 } ##2 }
4528     \cs_set:Npx \__tl_replace_next:w ##1 #5
4529     {
4530       \exp_not:N \__tl_replace_wrap:w ##1
4531       \exp_not:n { #1 }
4532       \exp_not:n { \exp_not:n {#6} }
4533       \exp_not:n { #2 { } { } }
4534     }
4535     #3 #4
4536     {

```

```

4537     \exp_after:wN \_tl_replace_next:w
4538     \exp_after:wN { \exp_after:wN }
4539     \exp_after:wN { \exp_after:wN }
4540     #4
4541     #1
4542     {
4543         \if_false: { \fi: }
4544         \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
4545     }
4546     #5
4547 }
4548 \group_align_safe_end:
4549 }
4550 \cs_new_eq:NN \_tl_replace_wrap:w ?
4551 \cs_new_eq:NN \_tl_replace_next:w ?

```

(End definition for `_tl_replace:NnNNNnn` and others.)

```

\tl_remove_once:Nn Removal is just a special case of replacement.
\tl_remove_once:cn 4552 \cs_new_protected:Npn \tl_remove_once:Nn #1#2
\tl_gremove_once:Nn 4553 { \tl_replace_once:Nnn #1 {#2} { } }
\tl_gremove_once:cn 4554 \cs_new_protected:Npn \tl_gremove_once:Nn #1#2
4555 { \tl_greplace_once:Nnn #1 {#2} { } }
4556 \cs_generate_variant:Nn \tl_remove_once:Nn { c }
4557 \cs_generate_variant:Nn \tl_gremove_once:Nn { c }

```

(End definition for `\tl_remove_once:Nn` and `\tl_gremove_once:Nn`. These functions are documented on page 45.)

```

\tl_remove_all:Nn Removal is just a special case of replacement.
\tl_remove_all:cn 4558 \cs_new_protected:Npn \tl_remove_all:Nn #1#2
\tl_gremove_all:Nn 4559 { \tl_replace_all:Nnn #1 {#2} { } }
\tl_gremove_all:cn 4560 \cs_new_protected:Npn \tl_gremove_all:Nn #1#2
4561 { \tl_greplace_all:Nnn #1 {#2} { } }
4562 \cs_generate_variant:Nn \tl_remove_all:Nn { c }
4563 \cs_generate_variant:Nn \tl_gremove_all:Nn { c }

```

(End definition for `\tl_remove_all:Nn` and `\tl_gremove_all:Nn`. These functions are documented on page 45.)

8.7 Token list conditionals

```

\tl_if_blank_p:n TeX skips spaces when reading a non-delimited arguments. Thus, a <token list> is blank
\tl_if_blank_p:V if and only if \use_none:n <token list> ? is empty after one expansion. The auxiliary
\tl_if_blank_p:o \_tl_if_empty_if:o is a fast emptyness test, converting its argument to a string (after
\tl_if_blank:nTF one expansion) and using the test \if_meaning:w \q__tl_nil ... \q__tl_nil.
\tl_if_blank:VTF 4564 \prg_new_conditional:Npnn \tl_if_blank:n #1 { p , T , F , TF }
\tl_if_blank:oTF 4565 {
\_tl_if_blank_p:NNw 4566 \_tl_if_empty_if:o { \use_none:n #1 ? }
4567 \prg_return_true:
4568 \else:
4569 \prg_return_false:
4570 \fi:
4571 }

```

```

4572 \prg_generate_conditional_variant:Nnn \tl_if_blank:n
4573 { e , V , o } { p , T , F , TF }

```

(End definition for `\tl_if_blank:nTF` and `__tl_if_blank_p:NNw`. This function is documented on page 46.)

`\tl_if_empty_p:N` These functions check whether the token list in the argument is empty and execute the proper code from their argument(s).

```

\__tl_if_empty_p:c
\__tl_if_empty:NTF
\__tl_if_empty:cTF
4574 \prg_new_conditional:Npnn \tl_if_empty:N #1 { p , T , F , TF }
4575 {
4576   \if_meaning:w #1 \c_empty_tl
4577   \prg_return_true:
4578   \else:
4579     \prg_return_false:
4580   \fi:
4581 }
4582 \prg_generate_conditional_variant:Nnn \tl_if_empty:N
4583 { c } { p , T , F , TF }

```

(End definition for `\tl_if_empty:NTF`. This function is documented on page 47.)

`\tl_if_empty_p:n` Convert the argument to a string: this is empty if and only if the argument is. Then
`\tl_if_empty_p:V` `\if_meaning:w \q_@@_nil ... \q_@@_nil` is true if and only if the string ... is empty.
`\tl_if_empty:nTF` It could be tempting to use `\if_meaning:w \q_@@_nil #1 \q_@@_nil` directly. This
`\tl_if_empty:VTF` fails on a token list starting with `\q__tl_nil` of course but more troubling is the case where argument is a complete conditional such as `\if_true: a \else: b \fi:` because then `\if_true:` is used by `\if_meaning:w`, the test turns out false, the `\else:` executes the false branch, the `\fi:` ends it and the `\q__tl_nil` at the end starts executing...

```

4584 \prg_new_conditional:Npnn \tl_if_empty:n #1 { p , TF , T , F }
4585 {
4586   \exp_after:wN \if_meaning:w \exp_after:wN \q__tl_nil
4587   \tl_to_str:n {#1} \q__tl_nil
4588   \prg_return_true:
4589   \else:
4590     \prg_return_false:
4591   \fi:
4592 }
4593 \prg_generate_conditional_variant:Nnn \tl_if_empty:n
4594 { V } { p , TF , T , F }

```

(End definition for `\tl_if_empty:nTF`. This function is documented on page 47.)

`\tl_if_empty_p:o` The auxiliary function `__tl_if_empty_if:o` is for use in various token list conditionals which reduce to testing if a given token list is empty after applying a simple function to it.
`\tl_if_empty:oTF` The test for emptiness is based on `\tl_if_empty:nTF`, but the expansion is hard-coded for efficiency, as this auxiliary function is used in several places. We don't put `\prg_return_true:` and so on in the definition of the auxiliary, because that would prevent an optimization applied to conditionals that end with this code.

```

4595 \cs_new:Npn \__tl_if_empty_if:o #1
4596 {
4597   \exp_after:wN \if_meaning:w \exp_after:wN \q__tl_nil
4598   \__kernel_tl_to_str:w \exp_after:wN {#1} \q__tl_nil
4599 }
4600 \prg_new_conditional:Npnn \tl_if_empty:o #1 { p , TF , T , F }

```

```

4601 {
4602   \__tl_if_empty_if:o {#1}
4603   \prg_return_true:
4604   \else:
4605     \prg_return_false:
4606   \fi:
4607 }

```

(End definition for \tl_if_empty:nTF and __tl_if_empty_if:o. This function is documented on page 47.)

\tl_if_eq_p:NN Returns \c_true_bool if and only if the two token list variables are equal.

```

\tl_if_eq_p:Nc 4608 \prg_new_conditional:Npnn \tl_if_eq:NN #1#2 { p , T , F , TF }
\tl_if_eq_p:cN 4609 {
\tl_if_eq_p:cc 4610   \if_meaning:w #1 #2
\tl_if_eq:NNTF 4611   \prg_return_true:
\tl_if_eq:NcTF 4612   \else:
\tl_if_eq:cNTF 4613   \prg_return_false:
\tl_if_eq:ccTF 4614   \fi:
4615 }
4616 \prg_generate_conditional_variant:Nnn \tl_if_eq:NN
4617 { Nc , c , cc } { p , TF , T , F }

```

(End definition for \tl_if_eq:NNTF. This function is documented on page 47.)

\tl_if_eq:nnTF A simple store and compare routine.

```

\l__tl_internal_a_tl 4618 \prg_new_protected_conditional:Npnn \tl_if_eq:nn #1#2 { T , F , TF }
\l__tl_internal_b_tl 4619 {
4620   \group_begin:
4621     \tl_set:Nn \l__tl_internal_a_tl {#1}
4622     \tl_set:Nn \l__tl_internal_b_tl {#2}
4623     \exp_after:wN
4624   \group_end:
4625   \if_meaning:w \l__tl_internal_a_tl \l__tl_internal_b_tl
4626     \prg_return_true:
4627   \else:
4628     \prg_return_false:
4629   \fi:
4630 }
4631 \tl_new:N \l__tl_internal_a_tl
4632 \tl_new:N \l__tl_internal_b_tl

```

(End definition for \tl_if_eq:nnTF, \l__tl_internal_a_tl, and \l__tl_internal_b_tl. This function is documented on page 47.)

\tl_if_in:NnTF See \tl_if_in:nnTF for further comments. Here we simply expand the token list variable and pass it to \tl_if_in:nnTF.

```

\tl_if_in:cnTF 4633 \cs_new_protected:Npn \tl_if_in:NnT { \exp_args:No \tl_if_in:nnT }
4634 \cs_new_protected:Npn \tl_if_in:NnF { \exp_args:No \tl_if_in:nnF }
4635 \cs_new_protected:Npn \tl_if_in:NnTF { \exp_args:No \tl_if_in:nnTF }
4636 \prg_generate_conditional_variant:Nnn \tl_if_in:Nn
4637 { c } { T , F , TF }

```

(End definition for \tl_if_in:NnTF. This function is documented on page 47.)

`\tl_if_in:nnTF` Once more, the test relies on the emptiness test for robustness. The function `__tl_tmp:w` removes tokens until the first occurrence of #2. If this does not appear in #1, then the final #2 is removed, leaving an empty token list. Otherwise some tokens remain, and the test is `false`. See `\tl_if_empty:nTF` for details on the emptiness test.

Treating correctly cases like `\tl_if_in:nnTF {a state}{states}`, where #1#2 contains #2 before the end, requires special care. To cater for this case, we insert `{ }{ }` between the two token lists. This marker may not appear in #2 because of \TeX limitations on what can delimit a parameter, hence we are safe. Using two brace groups makes the test work also for empty arguments. The `\if_false:` constructions are a faster way to do `\group_align_safe_begin:` and `\group_align_safe_end:`. The `\scan_stop:` ensures that f-expanding `\tl_if_in:nn` does not lead to unbalanced braces.

```

4638 \prg_new_protected_conditional:Npnn \tl_if_in:nn #1#2 { T , F , TF }
4639 {
4640   \scan_stop:
4641   \if_false: { \fi:
4642     \cs_set:Npn \__tl_tmp:w ##1 #2 { }
4643     \tl_if_empty:oTF { \__tl_tmp:w #1 {} {} #2 }
4644     { \prg_return_false: } { \prg_return_true: }
4645     \if_false: } \fi:
4646   }
4647 \prg_generate_conditional_variant:Nnn \tl_if_in:nn
4648 { V , o , no } { T , F , TF }

```

(End definition for `\tl_if_in:nnTF`. This function is documented on page 47.)

`\tl_if_novalue_p:n` Tests for `-NoValue-`: this is similar to `\tl_if_in:nn` but set up to be expandable and
`\tl_if_novalue:nTF` to check the value exactly. The question mark prevents the auxiliary from losing braces.
`__tl_if_novalue:w`

```

4649 \cs_set_protected:Npn \__tl_tmp:w #1
4650 {
4651   \prg_new_conditional:Npnn \tl_if_novalue:n ##1
4652   { p , T , F , TF }
4653   {
4654     \str_if_eq:onTF
4655     { \__tl_if_novalue:w ? ##1 { } #1 }
4656     { ? { } #1 }
4657     { \prg_return_true: }
4658     { \prg_return_false: }
4659   }
4660   \cs_new:Npn \__tl_if_novalue:w ##1 #1 {##1}
4661 }
4662 \exp_args:No \__tl_tmp:w { \c_novalue_tl }

```

(End definition for `\tl_if_novalue:nTF` and `__tl_if_novalue:w`. This function is documented on page 47.)

`\tl_if_single_p:N` Expand the token list and feed it to `\tl_if_single:n`.

```

4663 \cs_new:Npn \tl_if_single_p:N { \exp_args:No \tl_if_single_p:n }
4664 \cs_new:Npn \tl_if_single:NT { \exp_args:No \tl_if_single:nT }
4665 \cs_new:Npn \tl_if_single:NF { \exp_args:No \tl_if_single:nF }
4666 \cs_new:Npn \tl_if_single:NTF { \exp_args:No \tl_if_single:nTF }

```

(End definition for `\tl_if_single:NTF`. This function is documented on page 48.)

`\tl_if_single_p:n` This test is similar to `\tl_if_empty:nTF`. Expanding `\use_none:nn #1 ??` once yields an empty result if #1 is blank, a single ? if #1 has a single item, and otherwise yields some tokens ending with ??. Then, `\tl_to_str:n` makes sure there are no odd category codes.

`\tl_if_single:nTF` An earlier version would compare the result to a single ? using string comparison, but the Lua call is slow in LuaTeX. Instead, `__tl_if_single:nnw` picks the second token in front of it. If #1 is empty, this token is the trailing ? and the catcode test yields `false`. If #1 has a single item, the token is ^ and the catcode test yields `true`. Otherwise, it is one of the characters resulting from `\tl_to_str:n`, and the catcode test yields `false`. Note that `\if_catcode:w` and `__kernel_tl_to_str:w` are primitives that take care of expansion.

```

4667 \prg_new_conditional:Npnn \tl_if_single:n #1 { p , T , F , TF }
4668 {
4669   \if_catcode:w ^ \exp_after:wN \__tl_if_single:nnw
4670     \__kernel_tl_to_str:w
4671     \exp_after:wN { \use_none:nn #1 ?? } ^ ? \s_tl_stop
4672   \prg_return_true:
4673   \else:
4674     \prg_return_false:
4675   \fi:
4676 }
4677 \cs_new:Npn \__tl_if_single:nnw #1#2#3 \s_tl_stop {#2}

```

(End definition for `\tl_if_single:nTF` and `__tl_if_single:nTF`. This function is documented on page 48.)

`\tl_if_single_token_p:n` There are four cases: empty token list, token list starting with a normal token, with a brace group, or with a space token. If the token list starts with a normal token, remove it and check for emptiness. For the next case, an empty token list is not a single token. Finally, we have a non-empty token list starting with a space or a brace group. Applying f-expansion yields an empty result if and only if the token list is a single space.

`\tl_if_single_token:nTF`

```

4678 \prg_new_conditional:Npnn \tl_if_single_token:n #1 { p , T , F , TF }
4679 {
4680   \tl_if_head_is_N_type:nTF {#1}
4681   { \__tl_if_empty_if:o { \use_none:n #1 } }
4682   {
4683     \tl_if_empty:nTF {#1}
4684     { \if_false: }
4685     { \__tl_if_empty_if:o { \exp:w \exp_end_continue_f:w #1 } }
4686   }
4687   \prg_return_true:
4688   \else:
4689     \prg_return_false:
4690   \fi:
4691 }

```

(End definition for `\tl_if_single_token:nTF`. This function is documented on page 48.)

`\tl_case:Nn` The aim here is to allow the case statement to be evaluated using a known number of expansion steps (two), and without needing to use an explicit “end of recursion” marker.

`\tl_case:cn` That is achieved by using the test input as the final case, as this is always true. The

`\tl_case:NnTF` trick is then to tidy up the output such that the appropriate case code plus either the

`\tl_case:cnTF` true or false branch code is inserted.

`__tl_case:nnTF`

`__tl_case:Nw`

`__tl_case_end:nw`

```

4692 \cs_new:Npn \tl_case:Nn #1#2

```

```

4693 {
4694   \exp:w
4695   \__tl_case:NnTF #1 {#2} { } { }
4696 }
4697 \cs_new:Npn \tl_case:NnT #1#2#3
4698 {
4699   \exp:w
4700   \__tl_case:NnTF #1 {#2} {#3} { }
4701 }
4702 \cs_new:Npn \tl_case:NnF #1#2#3
4703 {
4704   \exp:w
4705   \__tl_case:NnTF #1 {#2} { } {#3}
4706 }
4707 \cs_new:Npn \tl_case:NnTF #1#2
4708 {
4709   \exp:w
4710   \__tl_case:NnTF #1 {#2}
4711 }
4712 \cs_new:Npn \__tl_case:NnTF #1#2#3#4
4713 { \__tl_case:Nw #1 #2 #1 { } \s__tl_mark {#3} \s__tl_mark {#4} \s__tl_stop }
4714 \cs_new:Npn \__tl_case:Nw #1#2#3
4715 {
4716   \tl_if_eq:NNTF #1 #2
4717   { \__tl_case_end:nw {#3} }
4718   { \__tl_case:Nw #1 }
4719 }
4720 \cs_generate_variant:Nn \tl_case:Nn { c }
4721 \prg_generate_conditional_variant:Nnn \tl_case:Nn
4722 { c } { T , F , TF }

```

To tidy up the recursion, there are two outcomes. If there was a hit to one of the cases searched for, then #1 is the code to insert, #2 is the *next* case to check on and #3 is all of the rest of the cases code. That means that #4 is the **true** branch code, and #5 tidies up the spare `\s__tl_mark` and the **false** branch. On the other hand, if none of the cases matched then we arrive here using the “termination” case of comparing the search with itself. That means that #1 is empty, #2 is the first `\s__tl_mark` and so #4 is the **false** code (the **true** code is mopped up by #3).

```

4723 \cs_new:Npn \__tl_case_end:nw #1#2#3 \s__tl_mark #4#5 \s__tl_stop
4724 { \exp_end: #1 #4 }

```

(End definition for `\tl_case:NnTF` and others. This function is documented on page 48.)

8.8 Mapping to token lists

`\tl_map_function:nN` Expandable loop macro for token lists. These have the advantage of not needing to test if the argument is empty, because if it is, the stop marker is read immediately and the loop terminated.

```

\__tl_map_function:Nn
4725 \cs_new:Npn \tl_map_function:Nn #1#2
4726 {
4727   \__tl_map_function:Nn #2 #1
4728   \q__tl_recursion_tail
4729   \prg_break_point:Nn \tl_map_break: { }
4730 }

```

```

4731 \cs_new:Npn \tl_map_function:NN
4732 { \exp_args:No \tl_map_function:nN }
4733 \cs_new:Npn \__tl_map_function:Nn #1#2
4734 {
4735   \__tl_if_recursion_tail_break:nN {#2} \tl_map_break:
4736   #1 {#2} \__tl_map_function:Nn #1
4737 }
4738 \cs_generate_variant:Nn \tl_map_function:NN { c }

```

(End definition for `\tl_map_function:nN`, `\tl_map_function:NN`, and `__tl_map_function:Nn`. These functions are documented on page 49.)

`\tl_map_inline:nn` The inline functions are straight forward by now. We use a little trick with the counter
`\tl_map_inline:Nn` `\g__kernel_prg_map_int` to make them nestable. We can also make use of `__tl_-`
`\tl_map_inline:cn` `map_function:Nn` from before.

```

4739 \cs_new_protected:Npn \tl_map_inline:nn #1#2
4740 {
4741   \int_gincr:N \g__kernel_prg_map_int
4742   \cs_gset_protected:cpn
4743   { \__tl_map_ \int_use:N \g__kernel_prg_map_int :w } ##1 {#2}
4744   \exp_args:Nc \__tl_map_function:Nn
4745   { \__tl_map_ \int_use:N \g__kernel_prg_map_int :w }
4746   #1 \q__tl_recursion_tail
4747   \prg_break_point:Nn \tl_map_break:
4748   { \int_gdecr:N \g__kernel_prg_map_int }
4749 }
4750 \cs_new_protected:Npn \tl_map_inline:Nn
4751 { \exp_args:No \tl_map_inline:nn }
4752 \cs_generate_variant:Nn \tl_map_inline:Nn { c }

```

(End definition for `\tl_map_inline:nn` and `\tl_map_inline:Nn`. These functions are documented on page 49.)

`\tl_map_tokens:nn` Much like the function mapping.
`\tl_map_tokens:Nn`
`\tl_map_tokens:cn`
`__tl_map_tokens:nn`

```

4753 \cs_new:Npn \tl_map_tokens:nn #1#2
4754 {
4755   \__tl_map_tokens:nn {#2} #1
4756   \q__tl_recursion_tail
4757   \prg_break_point:Nn \tl_map_break: { }
4758 }
4759 \cs_new:Npn \tl_map_tokens:Nn
4760 { \exp_args:No \tl_map_tokens:nn }
4761 \cs_generate_variant:Nn \tl_map_tokens:Nn { c }
4762 \cs_new:Npn \__tl_map_tokens:nn #1#2
4763 {
4764   \__tl_if_recursion_tail_break:nN {#2} \tl_map_break:
4765   \use:n {#1} {#2}
4766   \__tl_map_tokens:nn {#1}
4767 }

```

(End definition for `\tl_map_tokens:nn`, `\tl_map_tokens:Nn`, and `__tl_map_tokens:nn`. These functions are documented on page 49.)

`\tl_map_variable:nNn` `\tl_map_variable:NNn` `\tl_map_variable:cNn` `__tl_map_variable:Nnn` `\tl_map_variable:nNn` *<token list>* *<tl var>* *<action>* assigns *<tl var>* to each element and executes *<action>*. The assignment to *<tl var>* is done after the quark test so that this variable does not get set to a quark.

```

4768 \cs_new_protected:Npn \tl_map_variable:nNn #1#2#3
4769 {
4770     \__tl_map_variable:Nnn #2 {#3} #1
4771     \q__tl_recursion_tail
4772     \prg_break_point:Nn \tl_map_break: { }
4773 }
4774 \cs_new_protected:Npn \tl_map_variable:NNn
4775 { \exp_args:No \tl_map_variable:nNn }
4776 \cs_new_protected:Npn \__tl_map_variable:Nnn #1#2#3
4777 {
4778     \__tl_if_recursion_tail_break:nN {#3} \tl_map_break:
4779     \tl_set:Nn #1 {#3}
4780     \use:n {#2}
4781     \__tl_map_variable:Nnn #1 {#2}
4782 }
4783 \cs_generate_variant:Nn \tl_map_variable:NNn { c }

```

(End definition for `\tl_map_variable:nNn`, `\tl_map_variable:NNn`, and `__tl_map_variable:Nnn`. These functions are documented on page 49.)

`\tl_map_break:` The break statements use the general `\prg_map_break:Nn`.

`\tl_map_break:n`

```

4784 \cs_new:Npn \tl_map_break:
4785 { \prg_map_break:Nn \tl_map_break: { } }
4786 \cs_new:Npn \tl_map_break:n
4787 { \prg_map_break:Nn \tl_map_break: }

```

(End definition for `\tl_map_break:` and `\tl_map_break:n`. These functions are documented on page 50.)

8.9 Using token lists

`\tl_to_str:n` Another name for a primitive: defined in `l3basics`.

`\tl_to_str:V`

```

4788 \cs_generate_variant:Nn \tl_to_str:n { V }

```

(End definition for `\tl_to_str:n`. This function is documented on page 51.)

`\tl_to_str:N` These functions return the replacement text of a token list as a string.

`\tl_to_str:c`

```

4789 \cs_new:Npn \tl_to_str:N #1 { \__kernel_tl_to_str:w \exp_after:wN {#1} }
4790 \cs_generate_variant:Nn \tl_to_str:N { c }

```

(End definition for `\tl_to_str:N`. This function is documented on page 51.)

`\tl_use:N` Token lists which are simply not defined give a clear T_EX error here. No such luck for ones equal to `\scan_stop:` so instead a test is made and if there is an issue an error is forced.

`\tl_use:c`

```

4791 \cs_new:Npn \tl_use:N #1
4792 {
4793     \tl_if_exist:NTF #1 {#1}
4794     {
4795         \__kernel_msg_expandable_error:nnn
4796         { kernel } { bad-variable } {#1}

```

```

4797     }
4798   }
4799   \cs_generate_variant:Nn \tl_use:N { c }

```

(End definition for `\tl_use:N`. This function is documented on page 51.)

8.10 Working with the contents of token lists

`\tl_count:n` Count number of elements within a token list or token list variable. Brace groups within the list are read as a single element. Spaces are ignored. `__tl_count:n` grabs the element and replaces it by +1. The 0 ensures that it works on an empty list.

`\tl_count:N` `\cs_new:Npn \tl_count:n #1`

`\tl_count:c` `\cs_new:Npn \tl_count:N #1`

`__tl_count:n` `\int_eval:n`

```

4800   \cs_new:Npn \tl_count:n #1
4801   {
4802     \int_eval:n
4803     { 0 \tl_map_function:nN {#1} \__tl_count:n }
4804   }
4805   \cs_new:Npn \tl_count:N #1
4806   {
4807     \int_eval:n
4808     { 0 \tl_map_function:NN #1 \__tl_count:n }
4809   }
4810   \cs_new:Npn \__tl_count:n #1 { + 1 }
4811   \cs_generate_variant:Nn \tl_count:n { V , o }
4812   \cs_generate_variant:Nn \tl_count:N { c }

```

(End definition for `\tl_count:n`, `\tl_count:N`, and `__tl_count:n`. These functions are documented on page 51.)

`\tl_count_tokens:n` The token count is computed through an `\int_eval:n` construction. Each 1+ is output to the *left*, into the integer expression, and the sum is ended by the `\exp_end:` inserted by `__tl_act_end:wn` (which is technically implemented as `\c_zero_int`). Somewhat a hack!

`__tl_act_count_normal:nN`

`__tl_act_count_group:nn`

`__tl_act_count_space:n`

```

4813   \cs_new:Npn \tl_count_tokens:n #1
4814   {
4815     \int_eval:n
4816     {
4817       \__tl_act:NNNnn
4818       \__tl_act_count_normal:nN
4819       \__tl_act_count_group:nn
4820       \__tl_act_count_space:n
4821       { }
4822       {#1}
4823     }
4824   }
4825   \cs_new:Npn \__tl_act_count_normal:nN #1 #2 { 1 + }
4826   \cs_new:Npn \__tl_act_count_space:n #1 { 1 + }
4827   \cs_new:Npn \__tl_act_count_group:nn #1 #2
4828   { 2 + \tl_count_tokens:n {#2} + }

```

(End definition for `\tl_count_tokens:n` and others. This function is documented on page 52.)

`\tl_reverse_items:n` Reversal of a token list is done by taking one item at a time and putting it after `\s__tl_stop`.

`__tl_reverse_items:nwNwn`

`__tl_reverse_items:wn` `\cs_new:Npn \tl_reverse_items:n #1`

```

4830 {
4831   \_tl_reverse_items:nwNwn #1 ?
4832   \s__tl_mark \_tl_reverse_items:nwNwn
4833   \s__tl_mark \_tl_reverse_items:wn
4834   \s__tl_stop { }
4835 }
4836 \cs_new:Npn \_tl_reverse_items:nwNwn #1 #2 \s__tl_mark #3 #4 \s__tl_stop #5
4837 {
4838   #3 #2
4839   \s__tl_mark \_tl_reverse_items:nwNwn
4840   \s__tl_mark \_tl_reverse_items:wn
4841   \s__tl_stop { {#1} #5 }
4842 }
4843 \cs_new:Npn \_tl_reverse_items:wn #1 \s__tl_stop #2
4844 { \exp_not:o { \use_none:nn #2 } }

```

(End definition for `\tl_reverse_items:n`, `_tl_reverse_items:nwNwn`, and `_tl_reverse_items:wn`. This function is documented on page 52.)

`\tl_trim_spaces:n` Trimming spaces from around the input is deferred to an internal function whose first argument is the token list to trim, augmented by an initial `\s__tl_mark`, and whose second argument is a *<continuation>*, which receives as a braced argument `\use_none:n` `\s__tl_mark <trimmed token list>`. In the case at hand, we take `\exp_not:o` as our continuation, so that space trimming behaves correctly within an x-type expansion.

```

4845 \cs_new:Npn \tl_trim_spaces:n #1
4846 { \_tl_trim_spaces:nn { \s__tl_mark #1 } \exp_not:o }
4847 \cs_generate_variant:Nn \tl_trim_spaces:n { o }
4848 \cs_new:Npn \tl_trim_spaces_apply:nN #1#2
4849 { \_tl_trim_spaces:nn { \s__tl_mark #1 } { \exp_args:No #2 } }
4850 \cs_generate_variant:Nn \tl_trim_spaces_apply:nN { o }
4851 \cs_new_protected:Npn \tl_trim_spaces:N #1
4852 { \tl_set:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
4853 \cs_new_protected:Npn \tl_gtrim_spaces:N #1
4854 { \tl_gset:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
4855 \cs_generate_variant:Nn \tl_trim_spaces:N { c }
4856 \cs_generate_variant:Nn \tl_gtrim_spaces:N { c }

```

Trimming spaces from around the input is done using delimited arguments and quarks, and to get spaces at odd places in the definitions, we nest those in `_tl_tmp:w`, which then receives a single space as its argument: `#1` is `␣`. Removing leading spaces is done with `_tl_trim_spaces_auxi:w`, which loops until `\s__tl_mark␣` matches the end of the token list: then `##1` is the token list and `##3` is `_tl_trim_spaces_auxii:w`. This hands the relevant tokens to the loop `_tl_trim_spaces_auxiii:w`, responsible for trimming trailing spaces. The end is reached when `␣\s__tl_nil` matches the one present in the definition of `\tl_trim_spaces:n`. Then `_tl_trim_spaces_auxiv:w` puts the token list into a group, with `\use_none:n` placed there to gobble a lingering `\s__tl_mark`, and feeds this to the *<continuation>*.

```

4857 \cs_set:Npn \_tl_tmp:w #1
4858 {
4859   \cs_new:Npn \_tl_trim_spaces:nn ##1
4860   {
4861     \_tl_trim_spaces_auxi:w
4862     ##1

```

```

4863         \s__tl_nil
4864         \s__tl_mark #1 { }
4865         \s__tl_mark \__tl_trim_spaces_auxii:w
4866         \__tl_trim_spaces_auxiii:w
4867         #1 \s__tl_nil
4868         \__tl_trim_spaces_auxiv:w
4869         \s__tl_stop
4870     }
4871 \cs_new:Npn \__tl_trim_spaces_auxi:w ##1 \s__tl_mark #1 ##2 \s__tl_mark ##3
4872 {
4873     ##3
4874     \__tl_trim_spaces_auxi:w
4875     \s__tl_mark
4876     ##2
4877     \s__tl_mark #1 {##1}
4878 }
4879 \cs_new:Npn \__tl_trim_spaces_auxii:w
4880 \__tl_trim_spaces_auxi:w \s__tl_mark \s__tl_mark ##1
4881 {
4882     \__tl_trim_spaces_auxiii:w
4883     ##1
4884 }
4885 \cs_new:Npn \__tl_trim_spaces_auxiii:w ##1 #1 \s__tl_nil ##2
4886 {
4887     ##2
4888     ##1 \s__tl_nil
4889     \__tl_trim_spaces_auxiii:w
4890 }
4891 \cs_new:Npn \__tl_trim_spaces_auxiv:w ##1 \s__tl_nil ##2 \s__tl_stop ##3
4892 { ##3 { \use_none:n ##1 } }
4893 }
4894 \__tl_tmp:w { ~ }

```

(End definition for `\tl_trim_spaces:n` and others. These functions are documented on page 52.)

`\tl_sort:Nn` Implemented in `l3sort`.

`\tl_sort:cn`

`\tl_gsort:Nn` (End definition for `\tl_sort:Nn`, `\tl_gsort:Nn`, and `\tl_sort:nN`. These functions are documented on page 53.)

`\tl_gsort:cn`

`\tl_sort:nN`

8.11 Token by token changes

`\q__tl_act_mark`

`\q__tl_act_stop`

The `__tl_act_...` functions may be applied to any token list. Hence, we use two private quarks, to allow any token, even quarks, in the token list. Only `\q__tl_act_mark` and `\q__tl_act_stop` may not appear in the token lists manipulated by `__tl_act:NNNnn` functions.

```
4895 \quark_new:N \q__tl_act_mark
```

```
4896 \quark_new:N \q__tl_act_stop
```

(End definition for `\q__tl_act_mark` and `\q__tl_act_stop`.)

`__tl_act:NNNnn`

`__tl_act_output:n`

`__tl_act_reverse_output:n`

`__tl_act_loop:w`

`__tl_act_normal:NwnNNN`

`__tl_act_group:nwnNNN`

`__tl_act_space:wwnNNN`

`__tl_act_end:w`

To help control the expansion, `__tl_act:NNNnn` should always be preceded by `\exp:w` and ends by producing `\exp_end:` once the result has been obtained. Then loop over tokens, groups, and spaces in #5. The marker `\q__tl_act_mark` is used both to avoid

losing outer braces and to detect the end of the token list more easily. The result is stored as an argument for the dummy function `__tl_act_result:n`.

```

4897 \cs_new:Npn \__tl_act:NNNnn #1#2#3#4#5
4898 {
4899   \group_align_safe_begin:
4900   \__tl_act_loop:w #5 \q__tl_act_mark \q__tl_act_stop
4901   {#4} #1 #2 #3
4902   \__tl_act_result:n { }
4903 }

```

In the loop, we check how the token list begins and act accordingly. In the “normal” case, we may have reached `\q__tl_act_mark`, the end of the list. Then leave `\exp_end:` and the result in the input stream, to terminate the expansion of `\exp:w`. Otherwise, apply the relevant function to the “arguments”, `#3` and to the head of the token list. Then repeat the loop. The scheme is the same if the token list starts with a group or with a space. Some extra work is needed to make `__tl_act_space:wnnNNN` gobble the space.

```

4904 \cs_new:Npn \__tl_act_loop:w #1 \q__tl_act_stop
4905 {
4906   \tl_if_head_is_N_type:nTF {#1}
4907   { \__tl_act_normal:NwnNNN }
4908   {
4909     \tl_if_head_is_group:nTF {#1}
4910     { \__tl_act_group:nwnNNN }
4911     { \__tl_act_space:wnnNNN }
4912   }
4913   #1 \q__tl_act_stop
4914 }
4915 \cs_new:Npn \__tl_act_normal:NwnNNN #1 #2 \q__tl_act_stop #3#4
4916 {
4917   \if_meaning:w \q__tl_act_mark #1
4918   \exp_after:wN \__tl_act_end:wn
4919   \fi:
4920   #4 {#3} #1
4921   \__tl_act_loop:w #2 \q__tl_act_stop
4922   {#3} #4
4923 }
4924 \cs_new:Npn \__tl_act_end:wn #1 \__tl_act_result:n #2
4925 { \group_align_safe_end: \exp_end: #2 }
4926 \cs_new:Npn \__tl_act_group:nwnNNN #1 #2 \q__tl_act_stop #3#4#5
4927 {
4928   #5 {#3} {#1}
4929   \__tl_act_loop:w #2 \q__tl_act_stop
4930   {#3} #4 #5
4931 }
4932 \exp_last_unbraced:NNo
4933 \cs_new:Npn \__tl_act_space:wnnNNN \c_space_tl #1 \q__tl_act_stop #2#3#4#5
4934 {
4935   #5 {#2}
4936   \__tl_act_loop:w #1 \q__tl_act_stop
4937   {#2} #3 #4 #5
4938 }

```

Typically, the output is done to the right of what was already output, using `__tl_act_output:n`, but for the `__tl_act_reverse` functions, it should be done to the left.


```

4939 \cs_new:Npn \__tl_act_output:n #1 #2 \__tl_act_result:n #3
4940 { #2 \__tl_act_result:n { #3 #1 } }
4941 \cs_new:Npn \__tl_act_reverse_output:n #1 #2 \__tl_act_result:n #3
4942 { #2 \__tl_act_result:n { #1 #3 } }

```

(End definition for __tl_act:NNNnn and others.)

\tl_reverse:n The goal here is to reverse without losing spaces nor braces. This is done using the
\tl_reverse:o general internal function __tl_act:NNNnn. Spaces and “normal” tokens are output on
\tl_reverse:V the left of the current output. Grouped tokens are output to the left but without any
__tl_reverse_normal:nN reversal within the group. All of the internal functions here drop one argument: this is
__tl_reverse_group_preserve:nn needed by __tl_act:NNNnn when changing case (to record which direction the change
__tl_reverse_space:n is in), but not when reversing the tokens.

```

4943 \cs_new:Npn \tl_reverse:n #1
4944 {
4945   \__kernel_exp_not:w \exp_after:wN
4946   {
4947     \exp:w
4948     \__tl_act:NNNnn
4949     \__tl_reverse_normal:nN
4950     \__tl_reverse_group_preserve:nn
4951     \__tl_reverse_space:n
4952     { }
4953     {#1}
4954   }
4955 }
4956 \cs_generate_variant:Nn \tl_reverse:n { o , V }
4957 \cs_new:Npn \__tl_reverse_normal:nN #1#2
4958 { \__tl_act_reverse_output:n {#2} }
4959 \cs_new:Npn \__tl_reverse_group_preserve:nn #1#2
4960 { \__tl_act_reverse_output:n { {#2} } }
4961 \cs_new:Npn \__tl_reverse_space:n #1
4962 { \__tl_act_reverse_output:n { ~ } }

```

(End definition for \tl_reverse:n and others. This function is documented on page 52.)

\tl_reverse:N This reverses the list, leaving \exp_stop_f: in front, which stops the f-expansion.
\tl_reverse:c
\tl_greverse:N
\tl_greverse:c

```

4963 \cs_new_protected:Npn \tl_reverse:N #1
4964 { \tl_set:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
4965 \cs_new_protected:Npn \tl_greverse:N #1
4966 { \tl_gset:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
4967 \cs_generate_variant:Nn \tl_reverse:N { c }
4968 \cs_generate_variant:Nn \tl_greverse:N { c }

```

(End definition for \tl_reverse:N and \tl_greverse:N. These functions are documented on page 52.)

8.12 The first token from a token list

\tl_head:N Finding the head of a token list expandably always strips braces, which is fine as this
\tl_head:n is consistent with for example mapping to a list. The empty brace groups in \tl_
\tl_head:V head:n ensure that a blank argument gives an empty result. The result is returned
\tl_head:v within the \unexpanded primitive. The approach here is to use \if_false: to allow
\tl_head:f us to use } as the closing delimiter: this is the only safe choice, as any other token
__tl_head_auxi:nw would not be able to parse it’s own code. Using a marker, we can see if what we are
__tl_head_auxii:n
\tl_head:w
__tl_tl_head:w
\tl_tail:N
\tl_tail:n
\tl_tail:V
\tl_tail:v
\tl_tail:f

grabbing is exactly the marker, or there is anything else to deal with. If there is, there is a loop. If not, tidy up and leave the item in the output stream. More detail in <http://tex.stackexchange.com/a/70168>.

```

4969 \cs_new:Npn \tl_head:n #1
4970 {
4971   \__kernel_exp_not:w
4972   \if_false: { \fi: \__tl_head_auxi:nw #1 { } \s__tl_stop }
4973 }
4974 \cs_new:Npn \__tl_head_auxi:nw #1#2 \s__tl_stop
4975 {
4976   \exp_after:wN \__tl_head_auxii:n \exp_after:wN {
4977     \if_false: } \fi: {#1}
4978 }
4979 \cs_new:Npn \__tl_head_auxii:n #1
4980 {
4981   \exp_after:wN \if_meaning:w \exp_after:wN \q__tl_nil
4982   \__kernel_tl_to_str:w \exp_after:wN { \use_none:n #1 } \q__tl_nil
4983   \exp_after:wN \use_i:nn
4984   \else:
4985     \exp_after:wN \use_ii:nn
4986   \fi:
4987   {#1}
4988   { \if_false: { \fi: \__tl_head_auxi:nw #1 } }
4989 }
4990 \cs_generate_variant:Nn \tl_head:n { V , v , f }
4991 \cs_new:Npn \tl_head:w #1#2 \q_stop {#1}
4992 \cs_new:Npn \__tl_tl_head:w #1#2 \s__tl_stop {#1}
4993 \cs_new:Npn \tl_head:N { \exp_args:No \tl_head:n }

```

To correctly leave the tail of a token list, it's important *not* to absorb any of the tail part as an argument. For example, the simple definition

```

\cs_new:Npn \tl_tail:n #1 { \tl_tail:w #1 \q_stop }
\cs_new:Npn \tl_tail:w #1#2 \q_stop

```

would give the wrong result for `\tl_tail:n { a { bc } }` (the braces would be stripped). Thus the only safe way to proceed is to first check that there is an item to grab (*i.e.* that the argument is not blank) and assuming there is to dispose of the first item. As with `\tl_head:n`, the result is protected from further expansion by `\unexpanded`. While we could optimise the test here, this would leave some tokens “banned” in the input, which we do not have with this definition.

```

4994 \cs_new:Npn \tl_tail:n #1
4995 {
4996   \__kernel_exp_not:w
4997   \tl_if_blank:nTF {#1}
4998     { { } }
4999     { \exp_after:wN { \use_none:n #1 } }
5000 }
5001 \cs_generate_variant:Nn \tl_tail:n { V , v , f }
5002 \cs_new:Npn \tl_tail:N { \exp_args:No \tl_tail:n }

```

(End definition for `\tl_head:N` and others. These functions are documented on page 54.)

`\tl_if_head_eq_meaning_p:nN` Accessing the first token of a token list is tricky in three cases: when it has category code 1 (begin-group token), when it is an explicit space, with category code 10 and character code 32, or when the token list is empty (obviously).
`\tl_if_head_eq_meaning:nNTF`
`\tl_if_head_eq_charcode_p:nN`
`\tl_if_head_eq_charcode:nNTF`
`\tl_if_head_eq_charcode_p:fN` Forgetting temporarily about this issue we would use the following test in `\tl_if_head_eq_charcode:nN`. Here, `\tl_head:w` yields the first token of the token list, then passed to `\exp_not:N`.
`\tl_if_head_eq_charcode:fNTF`
`\tl_if_head_eq_catcode_p:nN`
`\tl_if_head_eq_catcode:nNTF`

```

\if_charcode:w
  \exp_after:wN \exp_not:N \tl_head:w #1 \q_nil \q_stop
  \exp_not:N #2

```

The two first special cases are detected by testing if the token list starts with an N-type token (the extra ? sends empty token lists to the `true` branch of this test). In those cases, the first token is a character, and since we only care about its character code, we can use `\str_head:n` to access it (this works even if it is a space character). An empty argument results in `\tl_head:w` leaving two tokens: ? which is taken in the `\if_charcode:w` test, and `\use_none:nn`, which ensures that `\prg_return_false:` is returned regardless of whether the charcode test was true or false.

```

5003 \prg_new_conditional:Npnn \tl_if_head_eq_charcode:nN #1#2 { p , T , F , TF }
5004 {
5005   \if_charcode:w
5006     \exp_not:N #2
5007     \tl_if_head_is_N_type:nTF { #1 ? }
5008     {
5009       \exp_after:wN \exp_not:N
5010       \__tl_tl_head:w #1 { ? \use_none:nn } \s__tl_stop
5011     }
5012     { \str_head:n {#1} }
5013     \prg_return_true:
5014   \else:
5015     \prg_return_false:
5016   \fi:
5017 }
5018 \prg_generate_conditional_variant:Nnn \tl_if_head_eq_charcode:nN
5019 { f } { p , TF , T , F }

```

For `\tl_if_head_eq_catcode:nN`, again we detect special cases with a `\tl_if_head_is_N_type:n`. Then we need to test if the first token is a begin-group token or an explicit space token, and produce the relevant token, either `\c_group_begin_token` or `\c_space_token`. Again, for an empty argument, a hack is used, removing `\prg_return_true:` and `\else:` with `\use_none:nn` in case the catcode test with the (arbitrarily chosen) ? is true.

```

5020 \prg_new_conditional:Npnn \tl_if_head_eq_catcode:nN #1 #2 { p , T , F , TF }
5021 {
5022   \if_catcode:w
5023     \exp_not:N #2
5024     \tl_if_head_is_N_type:nTF { #1 ? }
5025     {
5026       \exp_after:wN \exp_not:N
5027       \__tl_tl_head:w #1 { ? \use_none:nn } \s__tl_stop
5028     }
5029     {
5030       \tl_if_head_is_group:nTF {#1}

```

```

5031             { \c_group_begin_token }
5032             { \c_space_token }
5033         }
5034         \prg_return_true:
5035     \else:
5036         \prg_return_false:
5037     \fi:
5038 }
5039 \prg_generate_conditional_variant:Nnn \tl_if_head_eq_catcode:nN
5040 { o } { p , TF , T , F }

```

For `\tl_if_head_eq_meaning:nN`, again, detect special cases. In the normal case, use `\tl_head:w`, with no `\exp_not:N` this time, since `\if_meaning:w` causes no expansion. With an empty argument, the test is `true`, and `\use_none:nnn` removes `#2` and the usual `\prg_return_true:` and `\else:`. In the special cases, we know that the first token is a character, hence `\if_charcode:w` and `\if_catcode:w` together are enough. We combine them in some order, hopefully faster than the reverse. Tests are not nested because the arguments may contain unmatched primitive conditionals.

```

5041 \prg_new_conditional:Npnn \tl_if_head_eq_meaning:nN #1#2 { p , T , F , TF }
5042 {
5043     \tl_if_head_is_N_type:nTF { #1 ? }
5044     { \_tl_if_head_eq_meaning_normal:nN }
5045     { \_tl_if_head_eq_meaning_special:nN }
5046     {#1} #2
5047 }
5048 \cs_new:Npn \_tl_if_head_eq_meaning_normal:nN #1 #2
5049 {
5050     \exp_after:wN \if_meaning:w
5051     \_tl_tl_head:w #1 { ?? \use_none:nnn } \s__tl_stop #2
5052     \prg_return_true:
5053     \else:
5054         \prg_return_false:
5055     \fi:
5056 }
5057 \cs_new:Npn \_tl_if_head_eq_meaning_special:nN #1 #2
5058 {
5059     \if_charcode:w \str_head:n {#1} \exp_not:N #2
5060     \exp_after:wN \use:n
5061     \else:
5062         \prg_return_false:
5063     \exp_after:wN \use_none:n
5064     \fi:
5065     {
5066         \if_catcode:w \exp_not:N #2
5067         \tl_if_head_is_group:nTF {#1}
5068         { \c_group_begin_token }
5069         { \c_space_token }
5070         \prg_return_true:
5071     \else:
5072         \prg_return_false:
5073     \fi:
5074 }
5075 }

```

(End definition for `\tl_if_head_eq_meaning:nNTF` and others. These functions are documented on page

55.)

`\tl_if_head_is_N_type_p:n` A token list can be empty, can start with an explicit space character (catcode 10 and charcode 32), can start with a begin-group token (catcode 1), or start with an N-type argument. In the first two cases, the line involving `__tl_if_head_is_N_type:w` produces `~` (and otherwise nothing). In the third case (begin-group token), the lines involving `\exp_after:wN` produce a single closing brace. The category code test is thus true exactly in the fourth case, which is what we want. One cannot optimize by moving one of the `*` to the beginning: if `#1` contains primitive conditionals, all of its occurrences must be dealt with before the `\if_catcode:w` tries to skip the `true` branch of the conditional.

```

5076 \prg_new_conditional:Npnn \tl_if_head_is_N_type:n #1 { p , T , F , TF }
5077 {
5078   \if_catcode:w
5079     \if_false: { \fi: \__tl_if_head_is_N_type:w ? #1 ~ }
5080     \exp_after:wN \use_none:n
5081     \exp_after:wN { \exp_after:wN { \token_to_str:N #1 ? } }
5082     * *
5083     \prg_return_true:
5084   \else:
5085     \prg_return_false:
5086   \fi:
5087 }
5088 \cs_new:Npn \__tl_if_head_is_N_type:w #1 ~
5089 {
5090   \tl_if_empty:oTF { \use_none:n #1 } { ~ } { }
5091   \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
5092 }

```

(End definition for `\tl_if_head_is_N_type:nTF` and `__tl_if_head_is_N_type:w`. This function is documented on page 55.)

`\tl_if_head_is_group_p:n` Pass the first token of `#1` through `\token_to_str:N`, then check for the brace balance. The extra `?` caters for an empty argument. This could be made faster, but we need all brace tricks to happen in one step of expansion, keeping the token list brace balanced at all times.

`\tl_if_head_is_group:nTF`

```

5093 \prg_new_conditional:Npnn \tl_if_head_is_group:n #1 { p , T , F , TF }
5094 {
5095   \if_catcode:w
5096     \exp_after:wN \use_none:n
5097     \exp_after:wN { \exp_after:wN { \token_to_str:N #1 ? } }
5098     * *
5099     \prg_return_false:
5100   \else:
5101     \prg_return_true:
5102   \fi:
5103 }

```

(End definition for `\tl_if_head_is_group:nTF`. This function is documented on page 55.)

`\tl_if_head_is_space_p:n` The auxiliary's argument is all that is before the first explicit space in `?#1?~`. If that is a single `?` the test yields `true`. Otherwise, that is more than one token, and the test yields `false`. The work is done within braces (with an `\if_false: { \fi: ... }` construction) both to hide potential alignment tab characters from \TeX in a table, and to allow for removing what remains of the token list after its first space. The `\exp:w` and

`\exp_end`: ensure that the result of a single step of expansion directly yields a balanced token list (no trailing closing brace).

```

5104 \prg_new_conditional:Npnn \tl_if_head_is_space:n #1 { p , T , F , TF }
5105 {
5106   \exp:w \if_false: { \fi:
5107     \__tl_if_head_is_space:w ? #1 ? ~ }
5108 }
5109 \cs_new:Npn \__tl_if_head_is_space:w #1 ~
5110 {
5111   \tl_if_empty:oTF { \use_none:n #1 }
5112   { \exp_after:wN \exp_end: \exp_after:wN \prg_return_true: }
5113   { \exp_after:wN \exp_end: \exp_after:wN \prg_return_false: }
5114   \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
5115 }

```

(End definition for `\tl_if_head_is_space:nTF` and `__tl_if_head_is_space:w`. This function is documented on page 55.)

8.13 Using a single item

```

\tl_item:nn The idea here is to find the offset of the item from the left, then use a loop to grab
\tl_item:Nn the correct item. If the resulting offset is too large, then \__tl_if_recursion_tail_
\tl_item:cn break:nN terminates the loop, and returns nothing at all.
\__tl_item_aux:nn
\__tl_item:nn
5116 \cs_new:Npn \tl_item:nn #1#2
5117 {
5118   \exp_args:Nf \__tl_item:nn
5119   { \exp_args:Nf \__tl_item_aux:nn { \int_eval:n {#2} } {#1} }
5120   #1
5121   \q__tl_recursion_tail
5122   \prg_break_point:
5123 }
5124 \cs_new:Npn \__tl_item_aux:nn #1#2
5125 {
5126   \int_compare:nNnTF {#1} < 0
5127   { \int_eval:n { \tl_count:n {#2} + 1 + #1 } }
5128   {#1}
5129 }
5130 \cs_new:Npn \__tl_item:nn #1#2
5131 {
5132   \__tl_if_recursion_tail_break:nN {#2} \prg_break:
5133   \int_compare:nNnTF {#1} = 1
5134   { \prg_break:n { \exp_not:n {#2} } }
5135   { \exp_args:Nf \__tl_item:nn { \int_eval:n { #1 - 1 } } }
5136 }
5137 \cs_new:Npn \tl_item:Nn { \exp_args:No \tl_item:nn }
5138 \cs_generate_variant:Nn \tl_item:Nn { c }

```

(End definition for `\tl_item:nn` and others. These functions are documented on page 56.)

```

\tl_rand_item:n Importantly \tl_item:nn only evaluates its argument once.
\tl_rand_item:N
\tl_rand_item:c
5139 \cs_new:Npn \tl_rand_item:n #1
5140 {
5141   \tl_if_blank:nF {#1}
5142   { \tl_item:nn {#1} { \int_rand:nn { 1 } { \tl_count:n {#1} } } }

```

```

5143 }
5144 \cs_new:Npn \tl_rand_item:N { \exp_args:No \tl_rand_item:n }
5145 \cs_generate_variant:Nn \tl_rand_item:N { c }

```

(End definition for `\tl_rand_item:n` and `\tl_rand_item:N`. These functions are documented on page 56.)

```

\tl_range:Nnn To avoid checking for the end of the token list at every step, start by counting the number
\tl_range:cnn l of items and “normalizing” the bounds, namely clamping them to the interval  $[0, l]$  and
\tl_range:nnn dealing with negative indices. More precisely, \__tl_range_items:nnNn receives the
\__tl_range:Nnnn number of items to skip at the beginning of the token list, the index of the last item
\__tl_range:nnnNn to keep, a function which is either \__tl_range:w or the token list itself. If nothing
\__tl_range:nnNn should be kept, leave {}: this stops the f-expansion of \tl_head:f and that function
\__tl_range_skip:w produces an empty result. Otherwise, repeatedly call \__tl_range_skip:w to delete #1
\__tl_range:w items from the input stream (the extra brace group avoids an off-by-one shift). For the
\__tl_range_skip_spaces:n braced version \__tl_range_braced:w sets up \__tl_range_collect_braced:w which
\__tl_range_collect:nn stores items one by one in an argument after the semicolon. Depending on the first token
\__tl_range_collect:ff of the tail, either just move it (if it is a space) or also decrement the number of items left
\__tl_range_collect_space:nw to find. Eventually, the result is a brace group followed by the rest of the token list, and
\__tl_range_collect_N:nN \tl_head:f cleans up and gives the result in \exp_not:n.
\__tl_range_collect_group:nN
5146 \cs_new:Npn \tl_range:Nnn { \exp_args:No \tl_range:nnn }
5147 \cs_generate_variant:Nn \tl_range:Nnn { c }
5148 \cs_new:Npn \tl_range:nnn { \__tl_range:Nnnn \__tl_range:w }
5149 \cs_new:Npn \__tl_range:Nnnn #1#2#3#4
5150 {
5151   \tl_head:f
5152   {
5153     \exp_args:Nf \__tl_range:nnnNn
5154     { \tl_count:n {#2} } {#3} {#4} #1 {#2}
5155   }
5156 }
5157 \cs_new:Npn \__tl_range:nnnNn #1#2#3
5158 {
5159   \exp_args:Nff \__tl_range:nnNn
5160   {
5161     \exp_args:Nf \__tl_range_normalize:nn
5162     { \int_eval:n { #2 - 1 } } {#1}
5163   }
5164   {
5165     \exp_args:Nf \__tl_range_normalize:nn
5166     { \int_eval:n {#3} } {#1}
5167   }
5168 }
5169 \cs_new:Npn \__tl_range:nnNn #1#2#3#4
5170 {
5171   \if_int_compare:w #2 > #1 \exp_stop_f: \else:
5172     \exp_after:wN { \exp_after:wN }
5173   \fi:
5174   \exp_after:wN #3
5175   \int_value:w \int_eval:n { #2 - #1 } \exp_after:wN ;
5176   \exp_after:wN { \exp:w \__tl_range_skip:w #1 ; { } #4 }
5177 }
5178 \cs_new:Npn \__tl_range_skip:w #1 ; #2

```

```

5179 {
5180   \if_int_compare:w #1 > 0 \exp_stop_f:
5181     \exp_after:wN \__tl_range_skip:w
5182     \int_value:w \int_eval:n { #1 - 1 } \exp_after:wN ;
5183   \else:
5184     \exp_after:wN \exp_end:
5185   \fi:
5186 }
5187 \cs_new:Npn \__tl_range:w #1 ; #2
5188 {
5189   \exp_args:Nf \__tl_range_collect:nn
5190     { \__tl_range_skip_spaces:n {#2} } {#1}
5191 }
5192 \cs_new:Npn \__tl_range_skip_spaces:n #1
5193 {
5194   \tl_if_head_is_space:nTF {#1}
5195     { \exp_args:Nf \__tl_range_skip_spaces:n {#1} }
5196     { { } #1 }
5197 }
5198 \cs_new:Npn \__tl_range_collect:nn #1#2
5199 {
5200   \int_compare:nNnTF {#2} = 0
5201     {#1}
5202     {
5203       \exp_args:No \tl_if_head_is_space:nTF { \use_none:n #1 }
5204       {
5205         \exp_args:Nf \__tl_range_collect:nn
5206           { \__tl_range_collect_space:nw #1 }
5207           {#2}
5208       }
5209       {
5210         \__tl_range_collect:ff
5211         {
5212           \exp_args:No \tl_if_head_is_N_type:nTF { \use_none:n #1 }
5213           { \__tl_range_collect_N:nN }
5214           { \__tl_range_collect_group:nn }
5215           #1
5216         }
5217         { \int_eval:n { #2 - 1 } }
5218       }
5219     }
5220 }
5221 \cs_new:Npn \__tl_range_collect_space:nw #1 ~ { { #1 ~ } }
5222 \cs_new:Npn \__tl_range_collect_N:nN #1#2 { { #1 #2 } }
5223 \cs_new:Npn \__tl_range_collect_group:nn #1#2 { { #1 {#2} } }
5224 \cs_generate_variant:Nn \__tl_range_collect:nn { ff }

```

(End definition for `\tl_range:Nnn` and others. These functions are documented on page 57.)

`__tl_range_normalize:nn` This function converts an $\langle index \rangle$ argument into an explicit position in the token list (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the $\langle index \rangle$ #1 and the string count #2. If #1 is negative, replace it by $\#1 + \#2 + 1$, then limit to the range $[0, \#2]$.

```

5225 \cs_new:Npn \__tl_range_normalize:nn #1#2

```



```

5226 {
5227   \int_eval:n
5228   {
5229     \if_int_compare:w #1 < 0 \exp_stop_f:
5230     \if_int_compare:w #1 < -#2 \exp_stop_f:
5231       0
5232     \else:
5233       #1 + #2 + 1
5234     \fi:
5235   \else:
5236     \if_int_compare:w #1 < #2 \exp_stop_f:
5237       #1
5238     \else:
5239       #2
5240     \fi:
5241   \fi:
5242 }
5243 }

```

(End definition for `__tl_range_normalize:nn`.)

8.14 Viewing token lists

`\tl_show:N` Showing token list variables is done after checking that the variable is defined (see `__kernel_register_show:N`).

`\tl_log:N`

`\tl_log:c`

`__tl_show:NN`

```

5244 \cs_new_protected:Npn \tl_show:N { \__tl_show:NN \tl_show:n }
5245 \cs_generate_variant:Nn \tl_show:N { c }
5246 \cs_new_protected:Npn \tl_log:N { \__tl_show:NN \tl_log:n }
5247 \cs_generate_variant:Nn \tl_log:N { c }
5248 \cs_new_protected:Npn \__tl_show:NN #1#2
5249 {
5250   \__kernel_chk_defined:NT #2
5251   { \exp_args:Nx #1 { \token_to_str:N #2 = \exp_not:o {#2} } }
5252 }

```

(End definition for `\tl_show:N`, `\tl_log:N`, and `__tl_show:NN`. These functions are documented on page 58.)

`\tl_show:n` Many `show` functions are based on `\tl_show:n`. The argument of `\tl_show:n` is line-wrapped using `\iow_wrap:nnnN` but with a leading `>~` and trailing period, both removed before passing the wrapped text to the `\showtokens` primitive. This primitive shows the result with a leading `>~` and trailing period.

The token list `\l__tl_internal_a_tl` containing the result of all these manipulations is displayed to the terminal using `\tex_showtokens:D` and an odd `\exp_after:wN` which expand the closing brace to improve the output slightly. The calls to `__kernel_iow_with:Nnn` ensure that the `\newlinechar` is set to 10 so that the `\iow_newline:` inserted by the line-wrapping code are correctly recognized by \TeX , and that `\errorcontextlines` is `-1` to avoid printing irrelevant context.

```

5253 \cs_new_protected:Npn \tl_show:n #1
5254 { \iow_wrap:nnnN { >~ \tl_to_str:n {#1} . } { } { } \__tl_show:n }
5255 \cs_new_protected:Npn \__tl_show:n #1
5256 {
5257   \tl_set:Nf \l__tl_internal_a_tl { \__tl_show:w #1 \s__tl_stop }

```

```

5258     \__kernel_iow_with:Nnn \tex_newlinechar:D { 10 }
5259     {
5260         \__kernel_iow_with:Nnn \tex_errorcontextlines:D { -1 }
5261         {
5262             \tex_showtokens:D \exp_after:wN \exp_after:wN \exp_after:wN
5263             { \exp_after:wN \l__tl_internal_a_tl }
5264         }
5265     }
5266 }
5267 \cs_new:Npn \__tl_show:w #1 > #2 . \s__tl_stop {#2}

```

(End definition for `\tl_show:n`, `__tl_show:n`, and `__tl_show:w`. This function is documented on page 58.)

`\tl_log:n` Logging is much easier, simply line-wrap. The `>~` and trailing period is there to match the output of `\tl_show:n`.

```

5268 \cs_new_protected:Npn \tl_log:n #1
5269 { \iow_wrap:nnnN { > ~ \tl_to_str:n {#1} . } { } { } \iow_log:n }

```

(End definition for `\tl_log:n`. This function is documented on page 58.)

8.15 Internal scan marks

`\s__tl_nil` Internal scan marks. These are defined here at the end because the code for `\scan_new:N` depends on some `\l3tl` functions.

```

\s__tl_mark
\s__tl_stop
5270 \scan_new:N \s__tl_nil
5271 \scan_new:N \s__tl_mark
5272 \scan_new:N \s__tl_stop

```

(End definition for `\s__tl_nil`, `\s__tl_mark`, and `\s__tl_stop`.)

8.16 Scratch token lists

`\g_tmpa_tl` Global temporary token list variables. They are supposed to be set and used immediately, with no delay between the definition and the use because you can't count on other macros not to redefine them from under you.

`\g_tmpb_tl`

```

5273 \tl_new:N \g_tmpa_tl
5274 \tl_new:N \g_tmpb_tl

```

(End definition for `\g_tmpa_tl` and `\g_tmpb_tl`. These variables are documented on page 59.)

`\l_tmpa_tl` These are local temporary token list variables. Be sure not to assume that the value you put into them will survive for long—see discussion above.

`\l_tmpb_tl`

```

5275 \tl_new:N \l_tmpa_tl
5276 \tl_new:N \l_tmpb_tl

```

(End definition for `\l_tmpa_tl` and `\l_tmpb_tl`. These variables are documented on page 59.)

```

5277 </initex | package>

```

9 l3str implementation

5278 $\langle *initex | package \rangle$

5279 $\langle @@=str \rangle$

9.1 Internal auxiliaries

$\backslash s_str_mark$ Internal scan marks.

$\backslash s_str_stop$ 5280 $\backslash scan_new:N \backslash s_str_mark$

5281 $\backslash scan_new:N \backslash s_str_stop$

(End definition for $\backslash s_str_mark$ and $\backslash s_str_stop$.)

$\backslash_str_use_none_delimit_by_s_stop:w$ Functions to gobble up to a scan mark.

$\backslash_str_use_i_delimit_by_s_stop:nw$ 5282 $\backslash cs_new:Npn \backslash_str_use_none_delimit_by_s_stop:w \#1 \backslash s_str_stop \{ \}$

5283 $\backslash cs_new:Npn \backslash_str_use_i_delimit_by_s_stop:nw \#1 \#2 \backslash s_str_stop \{ \#1 \}$

(End definition for $\backslash_str_use_none_delimit_by_s_stop:w$ and $\backslash_str_use_i_delimit_by_s_stop:nw$.)

$\backslash q_str_recursion_tail$ Internal recursion quarks.

$\backslash q_str_recursion_stop$ 5284 $\backslash quark_new:N \backslash q_str_recursion_tail$

5285 $\backslash quark_new:N \backslash q_str_recursion_stop$

(End definition for $\backslash q_str_recursion_tail$ and $\backslash q_str_recursion_stop$.)

$\backslash_str_if_recursion_tail_break:NN$ Functions to query recursion quarks.

$\backslash_str_if_recursion_tail_stop_do:Nn$ 5286 $\backslash_kernel_quark_new_test:N \backslash_str_if_recursion_tail_break:NN$

5287 $\backslash_kernel_quark_new_test:N \backslash_str_if_recursion_tail_stop_do:Nn$

(End definition for $\backslash_str_if_recursion_tail_break:NN$ and $\backslash_str_if_recursion_tail_stop_do:Nn$.)

9.2 Creating and setting string variables

$\backslash str_new:N$ A string is simply a token list. The full mapping system isn't set up yet so do things by hand.

$\backslash str_new:c$

$\backslash str_use:N$

5288 $\backslash group_begin:$

$\backslash str_use:c$

5289 $\backslash cs_set_protected:Npn \backslash_str_tmp:n \#1$

$\backslash str_clear:N$

5290 $\{$
5291 $\backslash tl_if_blank:nF \{ \#1 \}$

$\backslash str_clear:c$

5292 $\{$

$\backslash str_gclear:N$

5293 $\backslash cs_new_eq:cc \{ str_ \#1 :N \} \{ tl_ \#1 :N \}$

$\backslash str_gclear:c$

5294 $\backslash exp_args:Nc \backslash cs_generate_variant:Nn \{ str_ \#1 :N \} \{ c \}$

$\backslash str_clear_new:N$

5295 $\backslash_str_tmp:n$

$\backslash str_clear_new:c$

5296 $\}$

$\backslash str_gclear_new:N$

5297 $\}$

$\backslash str_gclear_new:c$

5298 $\backslash_str_tmp:n$

$\backslash str_set_eq:NN$

5299 $\{ new \}$

$\backslash str_set_eq:cN$

5300 $\{ use \}$

$\backslash str_set_eq:Nc$

5301 $\{ clear \}$

$\backslash str_set_eq:cc$

5302 $\{ gclear \}$

$\backslash str_gset_eq:NN$

5303 $\{ clear_new \}$

$\backslash str_gset_eq:cN$

5304 $\{ gclear_new \}$

$\backslash str_gset_eq:Nc$

5305 $\{ \}$

$\backslash str_gset_eq:cc$

5306 $\backslash group_end:$

$\backslash str_gset_eq:cc$

5307 $\backslash cs_new_eq:NN \backslash str_set_eq:NN \backslash tl_set_eq:NN$

$\backslash str_concat:NNN$

$\backslash str_concat:ccc$

$\backslash str_gconcat:NNN$

$\backslash str_gconcat:ccc$

```

5308 \cs_new_eq:NN \str_gset_eq:NN \tl_gset_eq:NN
5309 \cs_generate_variant:Nn \str_set_eq:NN { c , Nc , cc }
5310 \cs_generate_variant:Nn \str_gset_eq:NN { c , Nc , cc }
5311 \cs_new_eq:NN \str_concat:NNN \tl_concat:NNN
5312 \cs_new_eq:NN \str_gconcat:NNN \tl_gconcat:NNN
5313 \cs_generate_variant:Nn \str_concat:NNN { ccc }
5314 \cs_generate_variant:Nn \str_gconcat:NNN { ccc }

```

(End definition for `\str_new:N` and others. These functions are documented on page 60.)

`\str_set:Nn` Simply convert the token list inputs to *strings*.

```

\str_set:NV      5315 \group_begin:
\str_set:Nx      5316 \cs_set_protected:Npn \__str_tmp:n #1
\str_set:cn      5317 {
\str_set:cV      5318   \tl_if_blank:nF {#1}
\str_set:cx      5319   {
\str_gset:Nn     5320     \cs_new_protected:cpx { str_ #1 :Nn } ##1##2
\str_gset:NV     5321     {
\str_gset:Nx     5322       \exp_not:c { tl_ #1 :Nx } ##1
\str_gset:cn     5323       { \exp_not:N \tl_to_str:n {##2} }
\str_gset:cV     5324     }
\str_gset:cx     5325     \cs_generate_variant:cn { str_ #1 :Nn } { NV , Nx , cn , cV , cx }
\str_gset:cx     5326     \__str_tmp:n
\str_const:Nn    5327   }
\str_const:NV    5328   }
\str_const:Nx    5329   \__str_tmp:n
\str_const:cn    5330   { set }
\str_const:cV    5331   { gset }
\str_const:cx    5332   { const }
\str_put_left:Nn 5333   { put_left }
\str_put_left:NV 5334   { gput_left }
\str_put_left:Nx 5335   { put_right }
\str_put_left:cn 5336   { gput_right }
\str_put_left:cV 5337   { }
\str_put_left:cx 5338 \group_end:

```

(End definition for `\str_set:Nn` and others. These functions are documented on page 61.)

9.3 Modifying string variables

Start by applying `\tl_to_str:n` to convert the old and new token lists to strings, and also apply `\tl_to_str:N` to avoid any issues if we are fed a token list variable. Then the code is a much simplified version of the token list code because neither the delimiter nor the replacement can contain macro parameters or braces. The delimiter `__str_`-mark cannot appear in the string to edit so it is used in all cases. Some x-expansion is unnecessary. There is no need to avoid losing braces nor to protect against expansion. The ending code is much simplified and does not need to hide in braces.

```

5339 \cs_new_protected:Npn \str_replace_once:Nnn
5340 { \__str_replace:NNNnn \prg_do_nothing: \tl_set:Nx }
5341 \cs_new_protected:Npn \str_greplace_once:Nnn
5342 { \__str_replace:NNNnn \prg_do_nothing: \tl_gset:Nx }
5343 \cs_new_protected:Npn \str_replace_all:Nnn
5344 { \__str_replace:NNNnn \__str_replace_next:w \tl_set:Nx }
5345 \cs_new_protected:Npn \str_greplace_all:Nnn

```

```

5346 { \__str_replace:NNNnn \__str_replace_next:w \tl_gset:Nx }
5347 \cs_generate_variant:Nn \str_replace_once:Nnn { c }
5348 \cs_generate_variant:Nn \str_greplace_once:Nnn { c }
5349 \cs_generate_variant:Nn \str_replace_all:Nnn { c }
5350 \cs_generate_variant:Nn \str_greplace_all:Nnn { c }
5351 \cs_new_protected:Npn \__str_replace:NNNnn #1#2#3#4#5
5352 {
5353   \tl_if_empty:nTF {#4}
5354   {
5355     \_kernel_msg_error:nnx { kernel } { empty-search-pattern } {#5}
5356   }
5357   {
5358     \use:x
5359     {
5360       \exp_not:n { \__str_replace_aux:NNNnnn #1 #2 #3 }
5361       { \tl_to_str:N #3 }
5362       { \tl_to_str:n {#4} } { \tl_to_str:n {#5} }
5363     }
5364   }
5365 }
5366 \cs_new_protected:Npn \__str_replace_aux:NNNnnn #1#2#3#4#5#6
5367 {
5368   \cs_set:Npn \__str_replace_next:w ##1 #5 { ##1 #6 #1 }
5369   #2 #3
5370   {
5371     \__str_replace_next:w
5372     #4
5373     \__str_use_none_delimit_by_s_stop:w
5374     #5
5375     \s__str_stop
5376   }
5377 }
5378 \cs_new_eq:NN \__str_replace_next:w ?

```

(End definition for `\str_replace_all:Nnn` and others. These functions are documented on page 62.)

```

\str_remove_once:Nn Removal is just a special case of replacement.
\str_remove_once:cn 5379 \cs_new_protected:Npn \str_remove_once:Nn #1#2
\str_gremove_once:Nn 5380 { \str_replace_once:Nnn #1 {#2} { } }
\str_gremove_once:cn 5381 \cs_new_protected:Npn \str_gremove_once:Nn #1#2
5382 { \str_greplace_once:Nnn #1 {#2} { } }
5383 \cs_generate_variant:Nn \str_remove_once:Nn { c }
5384 \cs_generate_variant:Nn \str_gremove_once:Nn { c }

```

(End definition for `\str_remove_once:Nn` and `\str_gremove_once:Nn`. These functions are documented on page 62.)

```

\str_remove_all:Nn Removal is just a special case of replacement.
\str_remove_all:cn 5385 \cs_new_protected:Npn \str_remove_all:Nn #1#2
\str_gremove_all:Nn 5386 { \str_replace_all:Nnn #1 {#2} { } }
\str_gremove_all:cn 5387 \cs_new_protected:Npn \str_gremove_all:Nn #1#2
5388 { \str_greplace_all:Nnn #1 {#2} { } }
5389 \cs_generate_variant:Nn \str_remove_all:Nn { c }
5390 \cs_generate_variant:Nn \str_gremove_all:Nn { c }

```

(End definition for `\str_remove_all:Nn` and `\str_gremove_all:Nn`. These functions are documented on page 62.)

9.4 String comparisons

```

\str_if_empty_p:N More copy-paste!
\str_if_empty_p:c 5391 \prg_new_eq_conditional:NNn \str_if_exist:N \tl_if_exist:N
\str_if_empty:NTF 5392 { p , T , F , TF }
\str_if_empty:cTF 5393 \prg_new_eq_conditional:NNn \str_if_exist:c \tl_if_exist:c
\str_if_exist_p:N 5394 { p , T , F , TF }
\str_if_exist_p:c 5395 \prg_new_eq_conditional:NNn \str_if_empty:N \tl_if_empty:N
\str_if_exist:NTF 5396 { p , T , F , TF }
\str_if_exist:cTF 5397 \prg_new_eq_conditional:NNn \str_if_empty:c \tl_if_empty:c
5398 { p , T , F , TF }

```

(End definition for `\str_if_empty:NTF` and `\str_if_exist:NTF`. These functions are documented on page 63.)

`__str_if_eq:nn` String comparisons rely on the primitive `\(pdf)strcmp` if available: LuaTeX does not have it, so emulation is required. As the net result is that we do not *always* use the primitive, the correct approach is to wrap up in a function with defined behaviour. That's done by providing a wrapper and then redefining in the LuaTeX case. Note that the necessary Lua code is loaded in `l3bootstrap`. The need to detokenize and force expansion of input arises from the case where a `#` token is used in the input, e.g. `__str_if_eq:nn {#} { \tl_to_str:n {#} }`, which otherwise would fail as `\tex_luaescapestring:D` does not double such tokens.

```

5399 \cs_new:Npn __str_if_eq:nn #1#2 { \tex_strcmp:D {#1} {#2} }
5400 \cs_if_exist:NT \tex_luatexversion:D
5401 {
5402   \cs_set_eq:NN \lua_escape:e \tex_luaescapestring:D
5403   \cs_set_eq:NN \lua_now:e \tex_directlua:D
5404   \cs_set:Npn __str_if_eq:nn #1#2
5405   {
5406     \lua_now:e
5407     {
5408       l3kernel_strcmp
5409       (
5410         " __str_escape:n {#1} " ,
5411         " __str_escape:n {#2} "
5412       )
5413     }
5414   }
5415   \cs_new:Npn __str_escape:n #1
5416   {
5417     \lua_escape:e
5418     { \__kernel_tl_to_str:w \use:e { {#1} } }
5419   }
5420 }

```

(End definition for `__str_if_eq:nn` and `__str_escape:n`.)

`\str_if_eq_p:nn` Modern engines provide a direct way of comparing two token lists, but returning a number. This set of conditionals therefore make life a bit clearer. The `nn` and `xx` versions are created directly as this is most efficient.

```

\str_if_eq_p:Vn
\str_if_eq_p:on
\str_if_eq_p:nV
\str_if_eq_p:no
\str_if_eq_p:VV
\str_if_eq_p:ee
\str_if_eq:nnTF
\str_if_eq:VnTF
\str_if_eq:onTF
\str_if_eq:nVTF
\str_if_eq:noTF
\str_if_eq:VVTF

```

```

5421 \prg_new_conditional:Npnn \str_if_eq:nn #1#2 { p , T , F , TF }
5422 {
5423   \if_int_compare:w
5424     \__str_if_eq:nn { \exp_not:n {#1} } { \exp_not:n {#2} }
5425     = 0 \exp_stop_f:
5426     \prg_return_true: \else: \prg_return_false: \fi:
5427 }
5428 \prg_generate_conditional_variant:Nnn \str_if_eq:nn
5429 { V , v , o , nV , no , VV , nv } { p , T , F , TF }
5430 \prg_new_conditional:Npnn \str_if_eq:ee #1#2 { p , T , F , TF }
5431 {
5432   \if_int_compare:w \__str_if_eq:nn {#1} {#2} = 0 \exp_stop_f:
5433   \prg_return_true: \else: \prg_return_false: \fi:
5434 }

```

(End definition for `\str_if_eq:nnTF`. This function is documented on page 63.)

`\str_if_eq_p:NN` Note that `\str_if_eq:NN` is different from `\tl_if_eq:NN` because it needs to ignore category codes.

```

\str_if_eq_p:Nc
\str_if_eq_p:cN
\str_if_eq_p:cc
\str_if_eq:NNTF
\str_if_eq:NcTF
\str_if_eq:cNTF
\str_if_eq:ccTF
5435 \prg_new_conditional:Npnn \str_if_eq:NN #1#2 { p , TF , T , F }
5436 {
5437   \if_int_compare:w
5438     \__str_if_eq:nn { \tl_to_str:N #1 } { \tl_to_str:N #2 }
5439     = 0 \exp_stop_f: \prg_return_true: \else: \prg_return_false: \fi:
5440 }
5441 \prg_generate_conditional_variant:Nnn \str_if_eq:NN
5442 { c , Nc , cc } { T , F , TF , p }

```

(End definition for `\str_if_eq:NNTF`. This function is documented on page 63.)

`\str_if_in:NnTF` Everything here needs to be detokenized but beyond that it is a simple token list test.
`\str_if_in:cnTF` It would be faster to fine-tune the T, F, TF variants by calling the appropriate variant of
`\str_if_in:nnTF` `\tl_if_in:nnTF` directly but that takes more code.

```

5443 \prg_new_protected_conditional:Npnn \str_if_in:Nn #1#2 { T , F , TF }
5444 {
5445   \use:x
5446   { \tl_if_in:nnTF { \tl_to_str:N #1 } { \tl_to_str:n {#2} } }
5447   { \prg_return_true: } { \prg_return_false: }
5448 }
5449 \prg_generate_conditional_variant:Nnn \str_if_in:Nn
5450 { c } { T , F , TF }
5451 \prg_new_protected_conditional:Npnn \str_if_in:nn #1#2 { T , F , TF }
5452 {
5453   \use:x
5454   { \tl_if_in:nnTF { \tl_to_str:n {#1} } { \tl_to_str:n {#2} } }
5455   { \prg_return_true: } { \prg_return_false: }
5456 }

```

(End definition for `\str_if_in:NnTF` and `\str_if_in:nnTF`. These functions are documented on page 63.)

`\str_case:nn` Much the same as `\tl_case:nn(TF)` here: just a change in the internal comparison.

```

\str_case:Vn
\str_case:on
\str_case:nV
\str_case:nv
5457 \cs_new:Npn \str_case:nn #1#2
5458 {
5459   \exp:w

```

`\str_case:nnTF`

`\str_case:VnTF`

`\str_case:onTF`

`\str_case:nVTF`

`\str_case:nvTF`

`\str_case_e:nn`

`\str_case_e:nnTF`

`__str_case:nnTF`

`__str_case_e:nnTF`

```

5460     \__str_case:nnTF {#1} {#2} { } { }
5461   }
5462 \cs_new:Npn \str_case:nnT #1#2#3
5463   {
5464     \exp:w
5465     \__str_case:nnTF {#1} {#2} {#3} { }
5466   }
5467 \cs_new:Npn \str_case:nnF #1#2
5468   {
5469     \exp:w
5470     \__str_case:nnTF {#1} {#2} { }
5471   }
5472 \cs_new:Npn \str_case:nnTF #1#2
5473   {
5474     \exp:w
5475     \__str_case:nnTF {#1} {#2}
5476   }
5477 \cs_new:Npn \__str_case:nnTF #1#2#3#4
5478   { \__str_case:nw {#1} #2 {#1} { } \s__str_mark {#3} \s__str_mark {#4} \s__str_stop }
5479 \cs_generate_variant:Nn \str_case:nn { V , o , nV , nv }
5480 \prg_generate_conditional_variant:Nnn \str_case:nn
5481   { V , o , nV , nv } { T , F , TF }
5482 \cs_new:Npn \__str_case:nw #1#2#3
5483   {
5484     \str_if_eq:nnTF {#1} {#2}
5485     { \__str_case_end:nw {#3} }
5486     { \__str_case:nw {#1} }
5487   }
5488 \cs_new:Npn \str_case_e:nn #1#2
5489   {
5490     \exp:w
5491     \__str_case_e:nnTF {#1} {#2} { } { }
5492   }
5493 \cs_new:Npn \str_case_e:nnT #1#2#3
5494   {
5495     \exp:w
5496     \__str_case_e:nnTF {#1} {#2} {#3} { }
5497   }
5498 \cs_new:Npn \str_case_e:nnF #1#2
5499   {
5500     \exp:w
5501     \__str_case_e:nnTF {#1} {#2} { }
5502   }
5503 \cs_new:Npn \str_case_e:nnTF #1#2
5504   {
5505     \exp:w
5506     \__str_case_e:nnTF {#1} {#2}
5507   }
5508 \cs_new:Npn \__str_case_e:nnTF #1#2#3#4
5509   { \__str_case_e:nw {#1} #2 {#1} { } \s__str_mark {#3} \s__str_mark {#4} \s__str_stop }
5510 \cs_new:Npn \__str_case_e:nw #1#2#3
5511   {
5512     \str_if_eq:eeTF {#1} {#2}
5513     { \__str_case_end:nw {#3} }

```



```

5514     { \_str_case_e:nw {#1} }
5515   }
5516 \cs_new:Npn \_str_case_end:nw #1#2#3 \s__str_mark #4#5 \s__str_stop
5517   { \exp_end: #1 #4 }

```

(End definition for `\str_case:nnTF` and others. These functions are documented on page 64.)

9.5 Mapping to strings

`\str_map_function:NN` The inline and variable mappings are similar to the usual token list mappings but start out by turning the argument to an “other string”. Doing the same for the expandable function mapping would require `_kernel_str_to_other:n`, quadratic in the string length. To deal with spaces in that case, `_str_map_function:w` replaces the following space by a braced space and a further call to itself. These are received by `_str_map_function:Nn`, which passes the space to `#1` and calls `_str_map_function:w` to deal with the next space. The space before the braced space allows to optimize the `\q__str_recursion_tail` test. Of course we need to include a trailing space (the question mark is needed to avoid losing the space when `TeX` tokenizes the line). At the cost of about three more auxiliaries this code could get a 9 times speed up by testing only every 9-th character for whether it is `\q__str_recursion_tail` (also by converting 9 spaces at a time in the `\str_map_function:nN` case).

For the `map_variable` functions we use a string assignment to store each character because spaces are made catcode 12 before the loop.

```

\str_map_function:cN
\str_map_function:nN
\str_map_inline:Nn
\str_map_inline:cN
\str_map_inline:nN
\str_map_variable:NNn
\str_map_variable:cNn
\str_map_variable:nNn
\str_map_break:
\str_map_break:n
\_str_map_function:w
\_str_map_function:Nn
\_str_map_inline:NN
\_str_map_variable:NnN
5518 \cs_new:Npn \str_map_function:nN #1#2
5519   {
5520     \exp_after:wN \_str_map_function:w
5521     \exp_after:wN \_str_map_function:Nn \exp_after:wN #2
5522     \_kernel_tl_to_str:w {#1}
5523     \q__str_recursion_tail ? ~
5524     \prg_break_point:Nn \str_map_break: { }
5525   }
5526 \cs_new:Npn \str_map_function:NN
5527   { \exp_args:No \str_map_function:nN }
5528 \cs_new:Npn \_str_map_function:w #1 ~
5529   { #1 { ~ { ~ } } \_str_map_function:w } }
5530 \cs_new:Npn \_str_map_function:Nn #1#2
5531   {
5532     \if_meaning:w \q__str_recursion_tail #2
5533     \exp_after:wN \str_map_break:
5534     \fi:
5535     #1 #2 \_str_map_function:Nn #1
5536   }
5537 \cs_generate_variant:Nn \str_map_function:NN { c }
5538 \cs_new_protected:Npn \str_map_inline:nn #1#2
5539   {
5540     \int_gincr:N \g__kernel_prg_map_int
5541     \cs_gset_protected:cpn
5542     { \_str_map_ \int_use:N \g__kernel_prg_map_int :w } ##1 {#2}
5543     \use:x
5544     {
5545       \exp_not:N \_str_map_inline:NN
5546       \exp_not:c { \_str_map_ \int_use:N \g__kernel_prg_map_int :w }
5547       \_kernel_str_to_other_fast:n {#1}

```

```

5548     }
5549     \q__str_recursion_tail
5550     \prg_break_point:Nn \str_map_break:
5551     { \int_gdecr:N \g__kernel_prg_map_int }
5552   }
5553   \cs_new_protected:Npn \str_map_inline:Nn
5554   { \exp_args:No \str_map_inline:nn }
5555   \cs_generate_variant:Nn \str_map_inline:Nn { c }
5556   \cs_new:Npn \__str_map_inline:NN #1#2
5557   {
5558     \__str_if_recursion_tail_break:NN #2 \str_map_break:
5559     \exp_args:No #1 { \token_to_str:N #2 }
5560     \__str_map_inline:NN #1
5561   }
5562   \cs_new_protected:Npn \str_map_variable:nNn #1#2#3
5563   {
5564     \use:x
5565     {
5566       \exp_not:n { \__str_map_variable:NnN #2 {#3} }
5567       \__kernel_str_to_other_fast:n {#1}
5568     }
5569     \q__str_recursion_tail
5570     \prg_break_point:Nn \str_map_break: { }
5571   }
5572   \cs_new_protected:Npn \str_map_variable:NNn
5573   { \exp_args:No \str_map_variable:nNn }
5574   \cs_new_protected:Npn \__str_map_variable:NnN #1#2#3
5575   {
5576     \__str_if_recursion_tail_break:NN #3 \str_map_break:
5577     \str_set:Nn #1 {#3}
5578     \use:n {#2}
5579     \__str_map_variable:NnN #1 {#2}
5580   }
5581   \cs_generate_variant:Nn \str_map_variable:NNn { c }
5582   \cs_new:Npn \str_map_break:
5583   { \prg_map_break:Nn \str_map_break: { } }
5584   \cs_new:Npn \str_map_break:n
5585   { \prg_map_break:Nn \str_map_break: }

```

(End definition for `\str_map_function:NN` and others. These functions are documented on page 64.)

9.6 Accessing specific characters in a string

`__kernel_str_to_other:n` First apply `\tl_to_str:n`, then replace all spaces by “other” spaces, 8 at a time, storing the converted part of the string between the `\s__str_mark` and `\s__str_stop` markers. The end is detected when `__str_to_other_loop:w` finds one of the trailing A, distinguished from any contents of the initial token list by their category. Then `__str_to_other_end:w` is called, and finds the result between `\s__str_mark` and the first A (well, there is also the need to remove a space).

```

5586   \cs_new:Npn \__kernel_str_to_other:n #1
5587   {
5588     \exp_after:wN \__str_to_other_loop:w
5589     \tl_to_str:n {#1} ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \s__str_mark \s__str_stop
5590   }

```

```

5591 \group_begin:
5592 \tex_lccode:D '\* = '\ %
5593 \tex_lccode:D '\A = '\A %
5594 \tex_lowercase:D
5595 {
5596   \group_end:
5597   \cs_new:Npn \__str_to_other_loop:w
5598     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 \s__str_stop
5599   {
5600     \if_meaning:w A #8
5601     \__str_to_other_end:w
5602     \fi:
5603     \__str_to_other_loop:w
5604     #9 #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * \s__str_stop
5605   }
5606   \cs_new:Npn \__str_to_other_end:w \fi: #1 \s__str_mark #2 * A #3 \s__str_stop
5607   { \fi: #2 }
5608 }

```

(End definition for __kernel_str_to_other:n, __str_to_other_loop:w, and __str_to_other_end:w.)

```

\__kernel_str_to_other_fast:n
\__kernel_str_to_other_fast_loop:w
\__str_to_other_fast_end:w

```

The difference with __kernel_str_to_other:n is that the converted part is left in the input stream, making these commands only restricted-expandable.

```

5609 \cs_new:Npn \__kernel_str_to_other_fast:n #1
5610 {
5611   \exp_after:wN \__str_to_other_fast_loop:w \tl_to_str:n {#1} ~
5612   A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \s__str_stop
5613 }
5614 \group_begin:
5615 \tex_lccode:D '\* = '\ %
5616 \tex_lccode:D '\A = '\A %
5617 \tex_lowercase:D
5618 {
5619   \group_end:
5620   \cs_new:Npn \__str_to_other_fast_loop:w
5621     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 ~
5622   {
5623     \if_meaning:w A #9
5624     \__str_to_other_fast_end:w
5625     \fi:
5626     #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * #9
5627     \__str_to_other_fast_loop:w *
5628   }
5629   \cs_new:Npn \__str_to_other_fast_end:w #1 * A #2 \s__str_stop {#1}
5630 }

```

(End definition for __kernel_str_to_other_fast:n, __kernel_str_to_other_fast_loop:w, and __str_to_other_fast_end:w.)

```

\str_item:Nn The \str_item:nn hands its argument with spaces escaped to \__str_item:nn, and
\str_item:cn makes sure to turn the result back into a proper string (with category code 10 spaces)
\str_item:nn eventually. The \str_item_ignore_spaces:nn function does not escape spaces, which
\str_item_ignore_spaces:nn are thus ignored by \__str_item:nn since everything else is done with undelimited arguments. Evaluate the <index> argument #2 and count characters in the string, passing
\__str_item:nn
\__str_item:w

```

those two numbers to `__str_item:w` for further analysis. If the $\langle index \rangle$ is negative, shift it by the $\langle count \rangle$ to know the how many character to discard, and if that is still negative give an empty result. If the $\langle index \rangle$ is larger than the $\langle count \rangle$, give an empty result, and otherwise discard $\langle index \rangle - 1$ characters before returning the following one. The shift by -1 is obtained by inserting an empty brace group before the string in that case: that brace group also covers the case where the $\langle index \rangle$ is zero.

```

5631 \cs_new:Npn \str_item:Nn { \exp_args:No \str_item:nn }
5632 \cs_generate_variant:Nn \str_item:Nn { c }
5633 \cs_new:Npn \str_item:nn #1#2
5634 {
5635     \exp_args:Nf \tl_to_str:n
5636     {
5637         \exp_args:Nf \__str_item:nn
5638         { \__kernel_str_to_other:n {#1} } {#2}
5639     }
5640 }
5641 \cs_new:Npn \str_item_ignore_spaces:nn #1
5642 { \exp_args:No \__str_item:nn { \tl_to_str:n {#1} } }
5643 \cs_new:Npn \__str_item:nn #1#2
5644 {
5645     \exp_after:wN \__str_item:w
5646     \int_value:w \int_eval:n {#2} \exp_after:wN ;
5647     \int_value:w \__str_count:n {#1} ;
5648     #1 \s__str_stop
5649 }
5650 \cs_new:Npn \__str_item:w #1; #2;
5651 {
5652     \int_compare:nNnTF {#1} < 0
5653     {
5654         \int_compare:nNnTF {#1} < {-#2}
5655         { \__str_use_none_delimit_by_s_stop:w }
5656         {
5657             \exp_after:wN \__str_use_i_delimit_by_s_stop:nw
5658             \exp:w \exp_after:wN \__str_skip_exp_end:w
5659             \int_value:w \int_eval:n { #1 + #2 } ;
5660         }
5661     }
5662     {
5663         \int_compare:nNnTF {#1} > {#2}
5664         { \__str_use_none_delimit_by_s_stop:w }
5665         {
5666             \exp_after:wN \__str_use_i_delimit_by_s_stop:nw
5667             \exp:w \__str_skip_exp_end:w #1 ; { }
5668         }
5669     }
5670 }

```

(End definition for `\str_item:Nn` and others. These functions are documented on page 67.)

<pre> __str_skip_exp_end:w __str_skip_loop:wNNNNNNNN __str_skip_end:w __str_skip_end:NNNNNNNN </pre>	<p>Removes $\max(\#1, 0)$ characters from the input stream, and then leaves <code>\exp_end:.</code> This should be expanded using <code>\exp:w</code>. We remove characters 8 at a time until there are at most 8 to remove. Then we do a dirty trick: the <code>\if_case:w</code> construction leaves between 0 and 8 times the <code>\or:</code> control sequence, and those <code>\or:</code> become arguments of <code>__str_skip_end:NNNNNNNN</code>. If the number of characters to remove is 6, say, then there</p>
--	--

are two `\or:` left, and the 8 arguments of `__str_skip_end:NNNNNNNN` are the two `\or:`, and 6 characters from the input stream, exactly what we wanted to remove. Then close the `\if_case:w` conditional with `\fi:`, and stop the initial expansion with `\exp_end:` (see places where `__str_skip_exp_end:w` is called).

```

5671 \cs_new:Npn \__str_skip_exp_end:w #1;
5672 {
5673   \if_int_compare:w #1 > 8 \exp_stop_f:
5674   \exp_after:wN \__str_skip_loop:wNNNNNNNN
5675   \else:
5676   \exp_after:wN \__str_skip_end:w
5677   \int_value:w \int_eval:w
5678   \fi:
5679   #1 ;
5680 }
5681 \cs_new:Npn \__str_skip_loop:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
5682 {
5683   \exp_after:wN \__str_skip_exp_end:w
5684   \int_value:w \int_eval:n { #1 - 8 } ;
5685 }
5686 \cs_new:Npn \__str_skip_end:w #1 ;
5687 {
5688   \exp_after:wN \__str_skip_end:NNNNNNNN
5689   \if_case:w #1 \exp_stop_f: \or: \or: \or: \or: \or: \or: \or: \or:
5690 }
5691 \cs_new:Npn \__str_skip_end:NNNNNNNN #1#2#3#4#5#6#7#8 { \fi: \exp_end: }

```

(End definition for `__str_skip_exp_end:w` and others.)

<code>\str_range:Nnn</code> <code>\str_range:nnn</code> <code>\str_range_ignore_spaces:nnn</code> <code>__str_range:nnn</code> <code>__str_range:w</code> <code>__str_range:nnw</code>	Sanitize the string. Then evaluate the arguments. At this stage we also decrement the <i><start index></i> , since our goal is to know how many characters should be removed. Then limit the range to be non-negative and at most the length of the string (this avoids needing to check for the end of the string when grabbing characters), shifting negative numbers by the appropriate amount. Afterwards, skip characters, then keep some more, and finally drop the end of the string.
--	--

```

5692 \cs_new:Npn \str_range:Nnn { \exp_args:No \str_range:nnn }
5693 \cs_generate_variant:Nn \str_range:Nnn { c }
5694 \cs_new:Npn \str_range:nnn #1#2#3
5695 {
5696   \exp_args:Nf \tl_to_str:n
5697   {
5698     \exp_args:Nf \__str_range:nnn
5699     { \__kernel_str_to_other:n {#1} } {#2} {#3}
5700   }
5701 }
5702 \cs_new:Npn \str_range_ignore_spaces:nnn #1
5703 { \exp_args:No \__str_range:nnn { \tl_to_str:n {#1} } }
5704 \cs_new:Npn \__str_range:nnn #1#2#3
5705 {
5706   \exp_after:wN \__str_range:w
5707   \int_value:w \__str_count:n {#1} \exp_after:wN ;
5708   \int_value:w \int_eval:n { (#2) - 1 } \exp_after:wN ;
5709   \int_value:w \int_eval:n {#3} ;
5710   #1 \s__str_stop

```

```

5711 }
5712 \cs_new:Npn \__str_range:w #1; #2; #3;
5713 {
5714   \exp_args:Nf \__str_range:nnw
5715   { \__str_range_normalize:nn {#2} {#1} }
5716   { \__str_range_normalize:nn {#3} {#1} }
5717 }
5718 \cs_new:Npn \__str_range:nnw #1#2
5719 {
5720   \exp_after:wN \__str_collect_delimit_by_q_stop:w
5721   \int_value:w \int_eval:n { #2 - #1 } \exp_after:wN ;
5722   \exp:w \__str_skip_exp_end:w #1 ;
5723 }

```

(End definition for `\str_range:Nnn` and others. These functions are documented on page 68.)

`__str_range_normalize:nn` This function converts an *<index>* argument into an explicit position in the string (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the *<index>* #1 and the string count #2. If #1 is negative, replace it by #1 + #2 + 1, then limit to the range [0, #2].

```

5724 \cs_new:Npn \__str_range_normalize:nn #1#2
5725 {
5726   \int_eval:n
5727   {
5728     \if_int_compare:w #1 < 0 \exp_stop_f:
5729     \if_int_compare:w #1 < -#2 \exp_stop_f:
5730     0
5731     \else:
5732     #1 + #2 + 1
5733     \fi:
5734     \else:
5735     \if_int_compare:w #1 < #2 \exp_stop_f:
5736     #1
5737     \else:
5738     #2
5739     \fi:
5740     \fi:
5741   }
5742 }

```

(End definition for `__str_range_normalize:nn`.)

`_str_collect_delimit_by_q_stop:w` Collects $\max(\#1, 0)$ characters, and removes everything else until `\s__str_stop`. This is somewhat similar to `__str_skip_exp_end:w`, but accepts integer expression arguments.
`__str_collect_loop:wn` This time we can only grab 7 characters at a time. At the end, we use an `\if_case:w` trick again, so that the 8 first arguments of `__str_collect_end:nnnnnnnnnw` are some `\or:`, followed by an `\fi:`, followed by #1 characters from the input stream. Simply leaving this in the input stream closes the conditional properly and the `\or:` disappear.
`__str_collect_loop:wnNNNNNNN`
`__str_collect_end:wn`
`__str_collect_end:nnnnnnnnnw`

```

5743 \cs_new:Npn \__str_collect_delimit_by_q_stop:w #1;
5744 { \__str_collect_loop:wn #1 ; { } }
5745 \cs_new:Npn \__str_collect_loop:wn #1 ;
5746 {
5747   \if_int_compare:w #1 > 7 \exp_stop_f:
5748   \exp_after:wN \__str_collect_loop:wnNNNNNNN

```

```

5749     \else:
5750         \exp_after:wN \__str_collect_end:wn
5751     \fi:
5752     #1 ;
5753 }
5754 \cs_new:Npn \__str_collect_loop:wnNNNNNNN #1; #2 #3#4#5#6#7#8#9
5755 {
5756     \exp_after:wN \__str_collect_loop:wn
5757     \int_value:w \int_eval:n { #1 - 7 } ;
5758     { #2 #3#4#5#6#7#8#9 }
5759 }
5760 \cs_new:Npn \__str_collect_end:wn #1 ;
5761 {
5762     \exp_after:wN \__str_collect_end:nnnnnnnnw
5763     \if_case:w \if_int_compare:w #1 > 0 \exp_stop_f:
5764         #1 \else: 0 \fi: \exp_stop_f:
5765     \or: \or: \or: \or: \or: \or: \or: \fi:
5766 }
5767 \cs_new:Npn \__str_collect_end:nnnnnnnnw #1#2#3#4#5#6#7#8 #9 \s__str_stop
5768 { #1#2#3#4#5#6#7#8 }

```

(End definition for __str_collect_delimit_by_q_stop:w and others.)

9.7 Counting characters

`\str_count_spaces:N` To speed up this function, we grab and discard 9 space-delimited arguments in each iteration of the loop. The loop stops when the last argument is one of the trailing `X⟨number⟩`, and that `⟨number⟩` is added to the sum of 9 that precedes, to adjust the result.

```

5769 \cs_new:Npn \str_count_spaces:N
5770 { \exp_args:No \str_count_spaces:n }
5771 \cs_generate_variant:Nn \str_count_spaces:N { c }
5772 \cs_new:Npn \str_count_spaces:n #1
5773 {
5774     \int_eval:n
5775     {
5776         \exp_after:wN \__str_count_spaces_loop:w
5777         \tl_to_str:n {#1} ~
5778         X 7 ~ X 6 ~ X 5 ~ X 4 ~ X 3 ~ X 2 ~ X 1 ~ X 0 ~ X -1 ~
5779         \s__str_stop
5780     }
5781 }
5782 \cs_new:Npn \__str_count_spaces_loop:w #1~#2~#3~#4~#5~#6~#7~#8~#9~
5783 {
5784     \if_meaning:w X #9
5785         \__str_use_i_delimit_by_s_stop:nw
5786     \fi:
5787     9 + \__str_count_spaces_loop:w
5788 }

```

(End definition for `\str_count_spaces:N`, `\str_count_spaces:n`, and `__str_count_spaces_loop:w`. These functions are documented on page 66.)

`\str_count:N` To count characters in a string we could first escape all spaces using `__kernel_str_to_other:n`, then pass the result to `\tl_count:n`. However, the escaping step would

```

\str_count:N
\str_count:c
\str_count:n
\str_count_ignore_spaces:n
\__str_count:n
\__str_count_aux:n
\__str_count_loop:NNNNNNNNN

```

be quadratic in the number of characters in the string, and we can do better. Namely, sum the number of spaces (`\str_count_spaces:n`) and the result of `\tl_count:n`, which ignores spaces. Since strings tend to be longer than token lists, we use specialized functions to count characters ignoring spaces. Namely, `loop`, grabbing 9 non-space characters at each step, and end as soon as we reach one of the 9 trailing items. The internal function `__str_count:n`, used in `\str_item:nn` and `\str_range:nnn`, is similar to `\str_count_ignore_spaces:n` but expects its argument to already be a string or a string with spaces escaped.

```

5789 \cs_new:Npn \str_count:N { \exp_args:No \str_count:n }
5790 \cs_generate_variant:Nn \str_count:N { c }
5791 \cs_new:Npn \str_count:n #1
5792 {
5793   \__str_count_aux:n
5794   {
5795     \str_count_spaces:n {#1}
5796     + \exp_after:wN \__str_count_loop:NNNNNNNNN \tl_to_str:n {#1}
5797   }
5798 }
5799 \cs_new:Npn \__str_count:n #1
5800 {
5801   \__str_count_aux:n
5802   { \__str_count_loop:NNNNNNNNN #1 }
5803 }
5804 \cs_new:Npn \str_count_ignore_spaces:n #1
5805 {
5806   \__str_count_aux:n
5807   { \exp_after:wN \__str_count_loop:NNNNNNNNN \tl_to_str:n {#1} }
5808 }
5809 \cs_new:Npn \__str_count_aux:n #1
5810 {
5811   \int_eval:n
5812   {
5813     #1
5814     { X 8 } { X 7 } { X 6 }
5815     { X 5 } { X 4 } { X 3 }
5816     { X 2 } { X 1 } { X 0 }
5817     \s__str_stop
5818   }
5819 }
5820 \cs_new:Npn \__str_count_loop:NNNNNNNNN #1#2#3#4#5#6#7#8#9
5821 {
5822   \if_meaning:w X #9
5823   \exp_after:wN \__str_use_none_delimit_by_s_stop:w
5824   \fi:
5825   9 + \__str_count_loop:NNNNNNNNN
5826 }

```

(End definition for `\str_count:N` and others. These functions are documented on page 66.)

9.8 The first character in a string

`\str_head:N` The `_ignore_spaces` variant applies `\tl_to_str:n` then grabs the first item, thus skipping spaces. As usual, `\str_head:N` expands its argument and hands it to `\str_head:n`.

`\str_head:n`

`\str_head_ignore_spaces:n`

`__str_head:w`

To circumvent the fact that \TeX skips spaces when grabbing undelimited macro parameters, `__str_head:w` takes an argument delimited by a space. If `#1` starts with a non-space character, `__str_use_i_delimit_by_s_stop:nw` leaves that in the input stream. On the other hand, if `#1` starts with a space, the `__str_head:w` takes an empty argument, and the single (initially braced) space in the definition of `__str_head:w` makes its way to the output. Finally, for an empty argument, the (braced) empty brace group in the definition of `\str_head:n` gives an empty result after passing through `__str_use_i_delimit_by_s_stop:nw`.

```

5827 \cs_new:Npn \str_head:N { \exp_args:No \str_head:n }
5828 \cs_generate_variant:Nn \str_head:N { c }
5829 \cs_new:Npn \str_head:n #1
5830 {
5831   \exp_after:wN \__str_head:w
5832   \tl_to_str:n {#1}
5833   { { } } ~ \s__str_stop
5834 }
5835 \cs_new:Npn \__str_head:w #1 ~ %
5836 { \__str_use_i_delimit_by_s_stop:nw #1 { ~ } }
5837 \cs_new:Npn \str_head_ignore_spaces:n #1
5838 {
5839   \exp_after:wN \__str_use_i_delimit_by_s_stop:nw
5840   \tl_to_str:n {#1} { } \s__str_stop
5841 }

```

(End definition for `\str_head:N` and others. These functions are documented on page 67.)

`\str_tail:N` Getting the tail is a little bit more convoluted than the head of a string. We hit the front of the string with `\reverse_if:N` `\if_charcode:w` `\scan_stop:.` This removes the first character, and necessarily makes the test true, since the character cannot match `\scan_stop:.` The auxiliary function then inserts the required `\fi:` to close the conditional, and leaves the tail of the string in the input stream. The details are such that an empty string has an empty tail (this requires in particular that the end-marker `X` be unexpandable and not a control sequence). The `_ignore_spaces` is rather simpler: after converting the input to a string, `__str_tail_auxii:w` removes one undelimited argument and leaves everything else until an end-marker `\s__str_mark`. One can check that an empty (or blank) string yields an empty tail.

```

5842 \cs_new:Npn \str_tail:N { \exp_args:No \str_tail:n }
5843 \cs_generate_variant:Nn \str_tail:N { c }
5844 \cs_new:Npn \str_tail:n #1
5845 {
5846   \exp_after:wN \__str_tail_auxi:w
5847   \reverse_if:N \if_charcode:w
5848   \scan_stop: \tl_to_str:n {#1} X X \s__str_stop
5849 }
5850 \cs_new:Npn \__str_tail_auxi:w #1 X #2 \s__str_stop { \fi: #1 }
5851 \cs_new:Npn \str_tail_ignore_spaces:n #1
5852 {
5853   \exp_after:wN \__str_tail_auxii:w
5854   \tl_to_str:n {#1} \s__str_mark \s__str_mark \s__str_stop
5855 }
5856 \cs_new:Npn \__str_tail_auxii:w #1 #2 \s__str_mark #3 \s__str_stop { #2 }

```

(End definition for `\str_tail:N` and others. These functions are documented on page 67.)

9.9 String manipulation

```

\str_foldcase:n Case changing for programmatic reasons is done by first detokenizing input then doing
\str_foldcase:V a simple loop that only has to worry about spaces and everything else. The output is
\str_lowercase:n detokenized to allow data sharing with text-based case changing.
\str_lowercase:f
\str_uppercase:n
\str_uppercase:f
  \__str_change_case:nn
  \__str_change_case_aux:nn
  \__str_change_case_result:n
  \__str_change_case_output:nw
  \__str_change_case_output:fw
  \__str_change_case_end:nw
  \__str_change_case_loop:nw
  \__str_change_case_space:n
  \__str_change_case_char:nN
5857 \cs_new:Npn \str_foldcase:n #1 { \__str_change_case:nn {#1} { fold } }
5858 \cs_new:Npn \str_lowercase:n #1 { \__str_change_case:nn {#1} { lower } }
5859 \cs_new:Npn \str_uppercase:n #1 { \__str_change_case:nn {#1} { upper } }
5860 \cs_generate_variant:Nn \str_foldcase:n { V }
5861 \cs_generate_variant:Nn \str_lowercase:n { f }
5862 \cs_generate_variant:Nn \str_uppercase:n { f }
5863 \cs_new:Npn \__str_change_case:nn #1
5864 {
5865   \exp_after:wN \__str_change_case_aux:nn \exp_after:wN
5866   { \tl_to_str:n {#1} }
5867 }
5868 \cs_new:Npn \__str_change_case_aux:nn #1#2
5869 {
5870   \__str_change_case_loop:nw {#2} #1 \q__str_recursion_tail \q__str_recursion_stop
5871   \__str_change_case_result:n { }
5872 }
5873 \cs_new:Npn \__str_change_case_output:nw #1#2 \__str_change_case_result:n #3
5874 { #2 \__str_change_case_result:n { #3 #1 } }
5875 \cs_generate_variant:Nn \__str_change_case_output:nw { f }
5876 \cs_new:Npn \__str_change_case_end:wn #1 \__str_change_case_result:n #2
5877 { \tl_to_str:n {#2} }
5878 \cs_new:Npn \__str_change_case_loop:nw #1#2 \q__str_recursion_stop
5879 {
5880   \tl_if_head_is_space:nTF {#2}
5881   { \__str_change_case_space:n }
5882   { \__str_change_case_char:nN }
5883   {#1} #2 \q__str_recursion_stop
5884 }
5885 \exp_last_unbraced:NNNNo
5886 \cs_new:Npn \__str_change_case_space:n #1 \c_space_tl
5887 {
5888   \__str_change_case_output:nw { ~ }
5889   \__str_change_case_loop:nw {#1}
5890 }
5891 \cs_new:Npn \__str_change_case_char:nN #1#2
5892 {
5893   \__str_if_recursion_tail_stop_do:Nn #2
5894   { \__str_change_case_end:wn }
5895   \__str_change_case_output:fw
5896   { \use:c { char_str_ #1 case:N } #2 }
5897   \__str_change_case_loop:nw {#1}
5898 }

```

(End definition for `\str_foldcase:n` and others. These functions are documented on page 70.)

```

\c_ampersand_str For all of those strings, use \cs_to_str:N to get characters with the correct category
\c_atsign_str    code without worries
\c_backslash_str
\c_left_brace_str
\c_right_brace_str
\c_circumflex_str
\c_colon_str
\c_dollar_str
\c_hash_str
\c_percent_str
\c_tilde_str
\c_underscore_str
5899 \str_const:Nx \c_ampersand_str { \cs_to_str:N & }
5900 \str_const:Nx \c_atsign_str { \cs_to_str:N @ }

```

```

5901 \str_const:Nx \c_backslash_str { \cs_to_str:N \ }
5902 \str_const:Nx \c_left_brace_str { \cs_to_str:N \{ }
5903 \str_const:Nx \c_right_brace_str { \cs_to_str:N \} }
5904 \str_const:Nx \c_circumflex_str { \cs_to_str:N \^ }
5905 \str_const:Nx \c_colon_str { \cs_to_str:N \: }
5906 \str_const:Nx \c_dollar_str { \cs_to_str:N \$ }
5907 \str_const:Nx \c_hash_str { \cs_to_str:N \# }
5908 \str_const:Nx \c_percent_str { \cs_to_str:N \% }
5909 \str_const:Nx \c_tilde_str { \cs_to_str:N \~ }
5910 \str_const:Nx \c_underscore_str { \cs_to_str:N \_ }

```

(End definition for `\c_ampersand_str` and others. These variables are documented on page 71.)

```

\l_tmpa_str Scratch strings.
\l_tmpb_str 5911 \str_new:N \l_tmpa_str
\g_tmpa_str 5912 \str_new:N \l_tmpb_str
\g_tmpb_str 5913 \str_new:N \g_tmpa_str
5914 \str_new:N \g_tmpb_str

```

(End definition for `\l_tmpa_str` and others. These variables are documented on page 71.)

9.10 Viewing strings

```

\str_show:n Displays a string on the terminal.
\str_show:N 5915 \cs_new_eq:NN \str_show:n \tl_show:n
\str_show:c 5916 \cs_new_eq:NN \str_show:N \tl_show:N
\str_log:n 5917 \cs_generate_variant:Nn \str_show:N { c }
\str_log:N 5918 \cs_new_eq:NN \str_log:n \tl_log:n
\str_log:c 5919 \cs_new_eq:NN \str_log:N \tl_log:N
5920 \cs_generate_variant:Nn \str_log:N { c }

```

(End definition for `\str_show:n` and others. These functions are documented on page 70.)

```
5921 </initex | package>
```

10 l3str-convert implementation

```

5922 <*initex | package>
5923 <@@=str>

```

10.1 Helpers

10.1.1 Variables and constants

```

\__str_tmp:w Internal scratch space for some functions.
\l__str_internal_int 5924 \cs_new_protected:Npn \__str_tmp:w { }
\l__str_internal_tl 5925 \tl_new:N \l__str_internal_tl
5926 \int_new:N \l__str_internal_int

```

(End definition for `__str_tmp:w`, `\l__str_internal_int`, and `\l__str_internal_tl`.)

`\g__str_result_tl` The `\g__str_result_tl` variable is used to hold the result of various internal string operations (mostly conversions) which are typically performed in a group. The variable is global so that it remains defined outside the group, to be assigned to a user-provided variable.

```
5927 \tl_new:N \g__str_result_tl
```

(End definition for `\g__str_result_tl`.)

`\c__str_replacement_char_int` When converting, invalid bytes are replaced by the Unicode replacement character "FFFD.

```
5928 \int_const:Nn \c__str_replacement_char_int { "FFFD }
```

(End definition for `\c__str_replacement_char_int`.)

`\c__str_max_byte_int` The maximal byte number.

```
5929 \int_const:Nn \c__str_max_byte_int { 255 }
```

(End definition for `\c__str_max_byte_int`.)

`\s__str` Internal scan marks.

```
5930 \scan_new:N \s__str
```

(End definition for `\s__str`.)

`\q__str_nil` Internal quarks.

```
5931 \quark_new:N \q__str_nil
```

(End definition for `\q__str_nil`.)

`\g__str_alias_prop` To avoid needing one file per encoding/escaping alias, we keep track of those in a property list.

```
5932 \prop_new:N \g__str_alias_prop
5933 \prop_gput:Nnn \g__str_alias_prop { latin1 } { iso88591 }
5934 \prop_gput:Nnn \g__str_alias_prop { latin2 } { iso88592 }
5935 \prop_gput:Nnn \g__str_alias_prop { latin3 } { iso88593 }
5936 \prop_gput:Nnn \g__str_alias_prop { latin4 } { iso88594 }
5937 \prop_gput:Nnn \g__str_alias_prop { latin5 } { iso88599 }
5938 \prop_gput:Nnn \g__str_alias_prop { latin6 } { iso885910 }
5939 \prop_gput:Nnn \g__str_alias_prop { latin7 } { iso885913 }
5940 \prop_gput:Nnn \g__str_alias_prop { latin8 } { iso885914 }
5941 \prop_gput:Nnn \g__str_alias_prop { latin9 } { iso885915 }
5942 \prop_gput:Nnn \g__str_alias_prop { latin10 } { iso885916 }
5943 \prop_gput:Nnn \g__str_alias_prop { utf16le } { utf16 }
5944 \prop_gput:Nnn \g__str_alias_prop { utf16be } { utf16 }
5945 \prop_gput:Nnn \g__str_alias_prop { utf32le } { utf32 }
5946 \prop_gput:Nnn \g__str_alias_prop { utf32be } { utf32 }
5947 \prop_gput:Nnn \g__str_alias_prop { hexadecimal } { hex }
```

(End definition for `\g__str_alias_prop`.)

`\g__str_error_bool` In conversion functions with a built-in conditional, errors are not reported directly to the user, but the information is collected in this boolean, used at the end to decide on which branch of the conditional to take.

```
5948 \bool_new:N \g__str_error_bool
```

(End definition for `\g__str_error_bool`.)

`str_byte` `str_error` Conversions from one *<encoding>*/*<escaping>* pair to another are done within x-expanding assignments. Errors are signalled by raising the relevant flag.

```
5949 \flag_new:n { str_byte }
5950 \flag_new:n { str_error }
```

(End definition for `str_byte` and `str_error`. These variables are documented on page ??.)

10.2 String conditionals

`_str_if_contains_char:NNT` `_str_if_contains_char:nNTF {<token list>} <char>`
`_str_if_contains_char:NNTF` Expects the *<token list>* to be an *<other string>*: the caller is responsible for ensuring
`_str_if_contains_char:nNTF` that no (too-)special catcodes remain. Spaces with catcode 10 are ignored. Loop over
`_str_if_contains_char_aux:NN` the characters of the string, comparing character codes. The loop is broken if character
`_str_if_contains_char_true:` codes match. Otherwise we return “false”.

```

5951 \prg_new_conditional:Npnn \_str_if_contains_char:NN #1#2 { T , TF }
5952 {
5953   \exp_after:wN \_str_if_contains_char_aux:NN \exp_after:wN #2
5954   #1 { \prg_break:n { ? \fi: } }
5955   \prg_break_point:
5956   \prg_return_false:
5957 }
5958 \prg_new_conditional:Npnn \_str_if_contains_char:nN #1#2 { TF }
5959 {
5960   \_str_if_contains_char_aux:NN #2 #1 { \prg_break:n { ? \fi: } }
5961   \prg_break_point:
5962   \prg_return_false:
5963 }
5964 \cs_new:Npn \_str_if_contains_char_aux:NN #1#2
5965 {
5966   \if_charcode:w #1 #2
5967   \exp_after:wN \_str_if_contains_char_true:
5968   \fi:
5969   \_str_if_contains_char_aux:NN #1
5970 }
5971 \cs_new:Npn \_str_if_contains_char_true:
5972 { \prg_break:n { \prg_return_true: \use_none:n } }

```

(End definition for `_str_if_contains_char:NNT` and others.)

`_str_octal_use:NTF` `_str_octal_use:NTF <token> {<true code>} {<false code>}`
 If the *<token>* is an octal digit, it is left in the input stream, *followed* by the *<true code>*. Otherwise, the *<false code>* is left in the input stream.

T_EXhackers note: This function will fail if the escape character is an octal digit. We are thus careful to set the escape character to a known value before using it. T_EX dutifully detects

octal digits for us: if #1 is an octal digit, then the right-hand side of the comparison is '1#1, greater than 1. Otherwise, the right-hand side stops as '1, and the conditional takes the false branch.

```

5973 \prg_new_conditional:Npnn \_str_octal_use:N #1 { TF }
5974 {
5975   \if_int_compare:w 1 < '1 \token_to_str:N #1 \exp_stop_f:
5976   #1 \prg_return_true:
5977   \else:
5978   \prg_return_false:
5979   \fi:
5980 }

```

(End definition for `_str_octal_use:NTF`.)

`__str_hexadecimal_use:N`TF TeX detects uppercase hexadecimal digits for us (see `__str_octal_use:N`TF), but not the lowercase letters, which we need to detect and replace by their uppercase counterpart.

```

5981 \prg_new_conditional:Npnn \__str_hexadecimal_use:N #1 { TF }
5982 {
5983   \if_int_compare:w 1 < "1 \token_to_str:N #1 \exp_stop_f:
5984     #1 \prg_return_true:
5985   \else:
5986     \if_case:w \int_eval:n { \exp_after:wN ' \token_to_str:N #1 - 'a }
5987       A
5988     \or: B
5989     \or: C
5990     \or: D
5991     \or: E
5992     \or: F
5993   \else:
5994     \prg_return_false:
5995     \exp_after:wN \use_none:n
5996   \fi:
5997   \prg_return_true:
5998 \fi:
5999 }
```

(End definition for `__str_hexadecimal_use:N`TF.)

10.3 Conversions

10.3.1 Producing one byte or character

`\c__str_byte_0_tl` For each integer N in the range $[0, 255]$, we create a constant token list which holds three character tokens with category code other: the character with character code N , followed by the representation of N as two hexadecimal digits. The value -1 is given a default token list which ensures that later functions give an empty result for the input -1 .

```

6000 \group_begin:
6001   \tl_set:Nx \l__str_internal_tl { \tl_to_str:n { 0123456789ABCDEF } }
6002   \tl_map_inline:Nn \l__str_internal_tl
6003     {
6004       \tl_map_inline:Nn \l__str_internal_tl
6005         {
6006           \tl_const:cx { c__str_byte_ \int_eval:n {"#1##1} _tl }
6007             { \char_generate:nn { "#1##1 } { 12 } #1 ##1 }
6008         }
6009     }
6010 \group_end:
6011 \tl_const:cn { c__str_byte_-1_tl } { { } \use_none:n { } }
```

(End definition for `\c__str_byte_0_tl` and others.)

`__str_output_byte:n` Those functions must be used carefully: feeding them a value outside the range $[-1, 255]$ will attempt to use the undefined token list variable `\c__str_byte_⟨number⟩_tl`. Assuming that the argument is in the right range, we expand the corresponding token list, and pick either the byte (first token) or the hexadecimal representations (second and third tokens). The value -1 produces an empty result in both cases.

```

6012 \cs_new:Npn \__str_output_byte:n #1
```

```

6013 { \__str_output_byte:w #1 \__str_output_end: }
6014 \cs_new:Npn \__str_output_byte:w
6015 {
6016   \exp_after:wN \exp_after:wN
6017   \exp_after:wN \use_i:nnn
6018   \cs:w c__str_byte_ \int_eval:w
6019 }
6020 \cs_new:Npn \__str_output_hexadecimal:n #1
6021 {
6022   \exp_after:wN \exp_after:wN
6023   \exp_after:wN \use_none:n
6024   \cs:w c__str_byte_ \int_eval:n {#1} _tl \cs_end:
6025 }
6026 \cs_new:Npn \__str_output_end:
6027 { \scan_stop: _tl \cs_end: }

```

(End definition for __str_output_byte:n and others.)

__str_output_byte_pair_be:n Convert a number in the range [0,65535] to a pair of bytes, either big-endian or little-endian.

```

\__str_output_byte_pair_le:n
\__str_output_byte_pair:nnN
6028 \cs_new:Npn \__str_output_byte_pair_be:n #1
6029 {
6030   \exp_args:Nf \__str_output_byte_pair:nnN
6031   { \int_div_truncate:nn { #1 } { "100 } } {#1} \use:nn
6032 }
6033 \cs_new:Npn \__str_output_byte_pair_le:n #1
6034 {
6035   \exp_args:Nf \__str_output_byte_pair:nnN
6036   { \int_div_truncate:nn { #1 } { "100 } } {#1} \use_ii_i:nn
6037 }
6038 \cs_new:Npn \__str_output_byte_pair:nnN #1#2#3
6039 {
6040   #3
6041   { \__str_output_byte:n { #1 } }
6042   { \__str_output_byte:n { #2 - #1 * "100 } }
6043 }

```

(End definition for __str_output_byte_pair_be:n, __str_output_byte_pair_le:n, and __str_output_byte_pair:nnN.)

10.3.2 Mapping functions for conversions

__str_convert_gmap:N This maps the function #1 over all characters in \g__str_result_tl, which should be a byte string in most cases, sometimes a native string.

```

\__str_convert_gmap_loop:NN
6044 \cs_new_protected:Npn \__str_convert_gmap:N #1
6045 {
6046   \tl_gset:Nx \g__str_result_tl
6047   {
6048     \exp_after:wN \__str_convert_gmap_loop:NN
6049     \exp_after:wN #1
6050     \g__str_result_tl { ? \prg_break: }
6051     \prg_break_point:
6052   }
6053 }

```

```

6054 \cs_new:Npn \__str_convert_gmap_loop:NN #1#2
6055 {
6056   \use_none:n #2
6057   #1#2
6058   \__str_convert_gmap_loop:NN #1
6059 }

```

(End definition for __str_convert_gmap:N and __str_convert_gmap_loop:NN.)

```

\__str_convert_gmap_internal:N
\__str_convert_gmap_internal_loop:Nw

```

This maps the function #1 over all character codes in \g__str_result_tl, which must be in the internal representation.

```

6060 \cs_new_protected:Npn \__str_convert_gmap_internal:N #1
6061 {
6062   \tl_gset:Nx \g__str_result_tl
6063   {
6064     \exp_after:wN \__str_convert_gmap_internal_loop:Nww
6065     \exp_after:wN #1
6066     \g__str_result_tl \s__str \s__str_stop \prg_break: \s__str
6067     \prg_break_point:
6068   }
6069 }
6070 \cs_new:Npn \__str_convert_gmap_internal_loop:Nww #1 #2 \s__str #3 \s__str
6071 {
6072   \__str_use_none_delimit_by_s_stop:w #3 \s__str_stop
6073   #1 {#3}
6074   \__str_convert_gmap_internal_loop:Nww #1
6075 }

```

(End definition for __str_convert_gmap_internal:N and __str_convert_gmap_internal_loop:Nw.)

10.3.3 Error-reporting during conversion

```

\__str_if_flag_error:nnx
\__str_if_flag_no_error:nnx

```

When converting using the function \str_set_convert:Nnnn, errors should be reported to the user after each step in the conversion. Errors are signalled by raising some flag (typically @@_error), so here we test that flag: if it is raised, give the user an error, otherwise remove the arguments. On the other hand, in the conditional functions \str_set_convert:NnnnTF, errors should be suppressed. This is done by changing __str_if_flag_error:nnx into __str_if_flag_no_error:nnx locally.

```

6076 \cs_new_protected:Npn \__str_if_flag_error:nnx #1
6077 {
6078   \flag_if_raised:nTF {#1}
6079   { \__kernel_msg_error:nnx { str } }
6080   { \use_none:nn }
6081 }
6082 \cs_new_protected:Npn \__str_if_flag_no_error:nnx #1#2#3
6083 { \flag_if_raised:nT {#1} { \bool_gset_true:N \g__str_error_bool } }

```

(End definition for __str_if_flag_error:nnx and __str_if_flag_no_error:nnx.)

```

\__str_if_flag_times:nT

```

At the end of each conversion step, we raise all relevant errors as one error message, built on the fly. The height of each flag indicates how many times a given error was encountered. This function prints #2 followed by the number of occurrences of an error if it occurred, nothing otherwise.

```

6084 \cs_new:Npn \__str_if_flag_times:nT #1#2
6085 { \flag_if_raised:nT {#1} { #2~(x \flag_height:n {#1} ) } }

```


(End definition for `_str_if_flag_times:nT`.)

10.3.4 Framework for conversions

Most functions in this module expect to be working with “native” strings. Strings can also be stored as bytes, in one of many encodings, for instance UTF8. The bytes themselves can be expressed in various ways in terms of \TeX tokens, for instance as pairs of hexadecimal digits. The questions of going from arbitrary Unicode code points to bytes, and from bytes to tokens are mostly independent.

Conversions are done in four steps:

- “unescape” produces a string of bytes;
- “decode” takes in a string of bytes, and converts it to a list of Unicode characters in an internal representation, with items of the form

$\langle bytes \rangle \backslash s_str \langle Unicode\ code\ point \rangle \backslash s_str$

where we have collected the $\langle bytes \rangle$ which combined to form this particular Unicode character, and the $\langle Unicode\ code\ point \rangle$ is in the range $[0, "10FFFF]$.

- “encode” encodes the internal list of code points as a byte string in the new encoding;
- “escape” escapes bytes as requested.

The process is modified in case one of the encoding is empty (or the conversion function has been set equal to the empty encoding because it was not found): then the unescape or escape step is ignored, and the decode or encode steps work on tokens instead of bytes. Otherwise, each step must ensure that it passes a correct byte string or internal string to the next step.

The input string is stored in `\g__str_result_tl`, then we: unescape and decode; encode and escape; exit the group and store the result in the user’s variable. The various conversion functions all act on `\g__str_result_tl`. Errors are silenced for the conditional functions by redefining `_str_if_flag_error:nxx` locally.

```

\str_set_convert:Nnnn
\str_gset_convert:Nnnn
\str_set_convert:NnnnTF
\str_gset_convert:NnnnTF
\_str_convert:nNNnnn
6086 \cs_new_protected:Npn \str_set_convert:Nnnn
6087 { \_str_convert:nNNnnn { } \tl_set_eq:NN }
6088 \cs_new_protected:Npn \str_gset_convert:Nnnn
6089 { \_str_convert:nNNnnn { } \tl_gset_eq:NN }
6090 \prg_new_protected_conditional:Npnn
6091 \str_set_convert:Nnnn #1#2#3#4 { T , F , TF }
6092 {
6093   \bool_gset_false:N \g__str_error_bool
6094   \_str_convert:nNNnnn
6095   { \cs_set_eq:NN \_str_if_flag_error:nxx \_str_if_flag_no_error:nxx }
6096   \tl_set_eq:NN #1 {#2} {#3} {#4}
6097   \bool_if:NTF \g__str_error_bool \prg_return_false: \prg_return_true:
6098 }
6099 \prg_new_protected_conditional:Npnn
6100 \str_gset_convert:Nnnn #1#2#3#4 { T , F , TF }
6101 {
6102   \bool_gset_false:N \g__str_error_bool
6103   \_str_convert:nNNnnn

```

```

6104     { \cs_set_eq:NN \__str_if_flag_error:nxx \__str_if_flag_no_error:nxx }
6105     \tl_gset_eq:NN #1 {#2} {#3} {#4}
6106     \bool_if:NTF \g__str_error_bool \prg_return_false: \prg_return_true:
6107   }
6108 \cs_new_protected:Npn \__str_convert:nNNnnn #1#2#3#4#5#6
6109 {
6110   \group_begin:
6111   #1
6112   \tl_gset:Nx \g__str_result_tl { \__kernel_str_to_other_fast:n {#4} }
6113   \exp_after:wN \__str_convert:wwwnn
6114   \tl_to_str:n {#5} /// \s__str_stop
6115   { decode } { unescape }
6116   \prg_do_nothing:
6117   \__str_convert_decode_:
6118   \exp_after:wN \__str_convert:wwwnn
6119   \tl_to_str:n {#6} /// \s__str_stop
6120   { encode } { escape }
6121   \use_ii_i:nn
6122   \__str_convert_encode_:
6123   \group_end:
6124   #2 #3 \g__str_result_tl
6125 }

```

(End definition for `\str_set_convert:Nnnn` and others. These functions are documented on page 72.)

`__str_convert:wwwnn` The task of `__str_convert:wwwnn` is to split $\langle encoding \rangle / \langle escaping \rangle$ pairs into their components, #1 and #2. Calls to `__str_convert:nnn` ensure that the corresponding conversion functions are defined. The third auxiliary does the main work.

- #1 is the encoding conversion function;
- #2 is the escaping function;
- #3 is the escaping name for use in an error message;
- #4 is `\prg_do_nothing:` for unescaping/decoding, and `\use_ii_i:nn` for encoding/escaping;
- #5 is the default encoding function (either “decode” or “encode”), for which there should be no escaping.

Let us ignore the native encoding for a second. In the unescaping/decoding phase, we want to do #2#1 in this order, and in the encoding/escaping phase, the order should be reversed: #4#2#1 does exactly that. If one of the encodings is the default (native), then the escaping should be ignored, with an error if any was given, and only the encoding, #1, should be performed.

```

6126 \cs_new_protected:Npn \__str_convert:wwwnn
6127   #1 / #2 // #3 \s__str_stop #4#5
6128 {
6129   \__str_convert:nnn {enc} {#4} {#1}
6130   \__str_convert:nnn {esc} {#5} {#2}
6131   \exp_args:Ncc \__str_convert:NNnNN
6132   { __str_convert_#4_#1: } { __str_convert_#5_#2: } {#2}
6133 }
6134 \cs_new_protected:Npn \__str_convert:NNnNN #1#2#3#4#5

```

```

6135 {
6136   \if_meaning:w #1 #5
6137   \tl_if_empty:nF {#3}
6138   { \__kernel_msg_error:nxx { str } { native-escaping } {#3} }
6139   #1
6140   \else:
6141     #4 #2 #1
6142   \fi:
6143 }

```

(End definition for __str_convert:wwwnn and __str_convert:NNnnN.)

__str_convert:nnn
__str_convert:nnnn

The arguments of __str_convert:nnn are: `enc` or `esc`, used to build filenames, the type of the conversion (unescape, decode, encode, escape), and the encoding or escaping name. If the function is already defined, no need to do anything. Otherwise, filter out all non-alphanumerics in the name, and lowercase it. Feed that, and the same three arguments, to __str_convert:nnnn. The task is then to make sure that the conversion function `#3_#1` corresponding to the type `#3` and filtered name `#1` is defined, then set our initial conversion function `#3_#4` equal to that.

How do we get the `#3_#1` conversion to be defined if it isn't? Two main cases.

First, if `#1` is a key in `\g__str_alias_prop`, then the value `\l__str_internal_tl` tells us what file to load. Loading is skipped if the file was already read, *i.e.*, if the conversion command based on `\l__str_internal_tl` already exists. Otherwise, try to load the file; if that fails, there is an error, use the default empty name instead.

Second, `#1` may be absent from the property list. The `\cs_if_exist:cF` test is automatically false, and we search for a file defining the encoding or escaping `#1` (this should allow third-party `.def` files). If the file is not found, there is an error, use the default empty name instead.

In all cases, the conversion based on `\l__str_internal_tl` is defined, so we can set the `#3_#1` function equal to that. In some cases (*e.g.*, `utf16be`), the `#3_#1` function is actually defined within the file we just loaded, and it is different from the `\l__str_internal_tl`-based function: we mustn't clobber that different definition.

```

6144 \cs_new_protected:Npn \__str_convert:nnn #1#2#3
6145 {
6146   \cs_if_exist:cF { __str_convert_#2_#3: }
6147   {
6148     \exp_args:Nx \__str_convert:nnnn
6149     { \__str_convert_lowercase_alphanum:n {#3} }
6150     {#1} {#2} {#3}
6151   }
6152 }
6153 \cs_new_protected:Npn \__str_convert:nnnn #1#2#3#4
6154 {
6155   \cs_if_exist:cF { __str_convert_#3_#1: }
6156   {
6157     \prop_get:NnNF \g__str_alias_prop {#1} \l__str_internal_tl
6158     { \tl_set:Nn \l__str_internal_tl {#1} }
6159     \cs_if_exist:cF { __str_convert_#3_ \l__str_internal_tl : }
6160     {
6161       \file_if_exist:nTF { l3str-#2- \l__str_internal_tl .def }
6162       {
6163         \group_begin:
6164         \__str_load_catcodes:

```

```

6165         \file_input:n { l3str-#2- \l__str_internal_tl .def }
6166     \group_end:
6167 }
6168 {
6169     \tl_clear:N \l__str_internal_tl
6170     \__kernel_msg_error:nxxx { str } { unknown-#2 } {#4} {#1}
6171 }
6172 }
6173 \cs_if_exist:cF { __str_convert_#3_#1: }
6174 {
6175     \cs_gset_eq:cc { __str_convert_#3_#1: }
6176     { __str_convert_#3_ \l__str_internal_tl : }
6177 }
6178 }
6179 \cs_gset_eq:cc { __str_convert_#3_#4: } { __str_convert_#3_#1: }
6180 }

```

(End definition for `__str_convert:nnn` and `__str_convert:nnnn`.)

`__str_convert_lowercase_alphanum:n` This function keeps only letters and digits, with upper case letters converted to lower case.

```

6181 \cs_new:Npn \__str_convert_lowercase_alphanum:n #1
6182 {
6183     \exp_after:wN \__str_convert_lowercase_alphanum_loop:N
6184     \tl_to_str:n {#1} { ? \prg_break: }
6185     \prg_break_point:
6186 }
6187 \cs_new:Npn \__str_convert_lowercase_alphanum_loop:N #1
6188 {
6189     \use_none:n #1
6190     \if_int_compare:w '#1 > 'Z \exp_stop_f:
6191     \if_int_compare:w '#1 > 'z \exp_stop_f: \else:
6192     \if_int_compare:w '#1 < 'a \exp_stop_f: \else:
6193         #1
6194     \fi:
6195     \fi:
6196 \else:
6197     \if_int_compare:w '#1 < 'A \exp_stop_f:
6198     \if_int_compare:w 1 < 1#1 \exp_stop_f:
6199         #1
6200     \fi:
6201     \else:
6202         \__str_output_byte:n { '#1 + 'a - 'A }
6203     \fi:
6204     \fi:
6205     \__str_convert_lowercase_alphanum_loop:N
6206 }

```

(End definition for `__str_convert_lowercase_alphanum:n` and `__str_convert_lowercase_alphanum_loop:N`.)

`__str_load_catcodes:` Since encoding files may be loaded at arbitrary places in a T_EX document, including within verbatim mode, we set the catcodes of all characters appearing in any encoding definition file.

```

6207 \cs_new_protected:Npn \__str_load_catcodes:
6208 {
6209   \char_set_catcode_escape:N \
6210   \char_set_catcode_group_begin:N \{
6211   \char_set_catcode_group_end:N \}
6212   \char_set_catcode_math_toggle:N \$
6213   \char_set_catcode_alignment:N \&
6214   \char_set_catcode_parameter:N \#
6215   \char_set_catcode_math_superscript:N ^
6216   \char_set_catcode_ignore:N \%
6217   \char_set_catcode_space:N ~
6218   \tl_map_function:nN { abcdefghijklmnopqrstuvwxyz_ABCDEFILNPSTUX }
6219   \char_set_catcode_letter:N
6220   \tl_map_function:nN { 0123456789"?'*+-.(),'!/<>[];= }
6221   \char_set_catcode_other:N
6222   \char_set_catcode_comment:N \%
6223   \int_set:Nn \tex_endlinechar:D {32}
6224 }

```

(End definition for __str_load_catcodes:.)

10.3.5 Byte unescape and escape

Strings of bytes may need to be stored in auxiliary files in safe “escaping” formats. Each such escaping is only loaded as needed. By default, on input any non-byte is filtered out, while the output simply consists in letting bytes through.

```

\__str_filter_bytes:n
\__str_filter_bytes_aux:N

```

In the case of 8-bit engines, every character is a byte. For Unicode-aware engines, test the character code; non-bytes cause us to raise the flag `str_byte`. Spaces have already been given the correct category code when this function is called.

```

6225 \bool_lazy_any:nTF
6226 {
6227   \sys_if_engine luatex_p:
6228   \sys_if_engine xetex_p:
6229 }
6230 {
6231   \cs_new:Npn \__str_filter_bytes:n #1
6232   {
6233     \__str_filter_bytes_aux:N #1
6234     { ? \prg_break: }
6235     \prg_break_point:
6236   }
6237   \cs_new:Npn \__str_filter_bytes_aux:N #1
6238   {
6239     \use_none:n #1
6240     \if_int_compare:w '#1 < 256 \exp_stop_f:
6241     #1
6242     \else:
6243       \flag_raise:n { str_byte }
6244     \fi:
6245     \__str_filter_bytes_aux:N
6246   }
6247 }
6248 { \cs_new_eq:NN \__str_filter_bytes:n \use:n }

```

(End definition for `_str_filter_bytes:n` and `_str_filter_bytes_aux:N`.)

`_str_convert_unescape_:` The simplest unescaping method removes non-bytes from `\g_str_result_tl`.

```

\__str_convert_unescape_bytes:
6249 \bool_lazy_any:nTF
6250 {
6251   \sys_if_engine luatex_p:
6252   \sys_if_engine xetex_p:
6253 }
6254 {
6255   \cs_new_protected:Npn \_str_convert_unescape_:
6256   {
6257     \flag_clear:n { str_byte }
6258     \tl_gset:Nx \g_str_result_tl
6259     { \exp_args:No \_str_filter_bytes:n \g_str_result_tl }
6260     \_str_if_flag_error:nmx { str_byte } { non-byte } { bytes }
6261   }
6262 }
6263 { \cs_new_protected:Npn \_str_convert_unescape_: { } }
6264 \cs_new_eq:NN \_str_convert_unescape_bytes: \_str_convert_unescape_:

```

(End definition for `_str_convert_unescape_:` and `_str_convert_unescape_bytes:.`)

`_str_convert_escape_:` The simplest form of escape leaves the bytes from the previous step of the conversion unchanged.

```

6265 \cs_new_protected:Npn \_str_convert_escape_: { }
6266 \cs_new_eq:NN \_str_convert_escape_bytes: \_str_convert_escape_:

```

(End definition for `_str_convert_escape_:` and `_str_convert_escape_bytes:.`)

10.3.6 Native strings

`_str_convert_decode_:` Convert each character to its character code, one at a time.

```

\__str_decode_native_char:N
6267 \cs_new_protected:Npn \_str_convert_decode_:
6268 { \_str_convert_gmap:N \_str_decode_native_char:N }
6269 \cs_new:Npn \_str_decode_native_char:N #1
6270 { #1 \s_str \int_value:w '#1 \s_str }

```

(End definition for `_str_convert_decode_:` and `_str_decode_native_char:N`.)

`_str_convert_encode_:` The conversion from an internal string to native character tokens basically maps `\char_generate:nn` through the code-points, but in non-Unicode-aware engines we use a fall-back character ? rather than nothing when given a character code outside [0,255]. We detect the presence of bad characters using a flag and only produce a single error after the x-expanding assignment.

```

6271 \bool_lazy_any:nTF
6272 {
6273   \sys_if_engine luatex_p:
6274   \sys_if_engine xetex_p:
6275 }
6276 {
6277   \cs_new_protected:Npn \_str_convert_encode_:
6278   { \_str_convert_gmap_internal:N \_str_encode_native_char:n }
6279   \cs_new:Npn \_str_encode_native_char:n #1
6280   { \char_generate:nn {#1} {12} }

```

```

6281 }
6282 {
6283   \cs_new_protected:Npn \__str_convert_encode_
6284   {
6285     \flag_clear:n { str_error }
6286     \__str_convert_gmap_internal:N \__str_encode_native_char:n
6287     \__str_if_flag_error:nnx { str_error }
6288     { native-overflow } { }
6289   }
6290   \cs_new:Npn \__str_encode_native_char:n #1
6291   {
6292     \if_int_compare:w #1 > \c__str_max_byte_int
6293     \flag_raise:n { str_error }
6294     ?
6295     \else:
6296     \char_generate:nn {#1} {12}
6297     \fi:
6298   }
6299   \__kernel_msg_new:nnnn { str } { native-overflow }
6300   { Character-code-too-large-for-this-engine. }
6301   {
6302     This-engine-only-support-8-bit-characters:~
6303     valid-character-codes-are-in-the-range-[0,255].~
6304     To-manipulate-arbitrary-Unicode,~use~LuaTeX-or~XeTeX.
6305   }
6306 }

```

(End definition for __str_convert_encode_ and __str_encode_native_char:n.)

10.3.7 clist

__str_convert_decode_clist: Convert each integer to the internal form. We first turn \g__str_result_tl into a clist variable, as this avoids problems with leading or trailing commas.

```

6307 \cs_new_protected:Npn \__str_convert_decode_clist:
6308 {
6309   \clist_gset:No \g__str_result_tl \g__str_result_tl
6310   \tl_gset:Nx \g__str_result_tl
6311   {
6312     \exp_args:No \clist_map_function:nN
6313     \g__str_result_tl \__str_decode_clist_char:n
6314   }
6315 }
6316 \cs_new:Npn \__str_decode_clist_char:n #1
6317 { #1 \s__str \int_eval:n {#1} \s__str }

```

(End definition for __str_convert_decode_clist: and __str_decode_clist_char:n.)

__str_convert_encode_clist: Convert the internal list of character codes to a comma-list of character codes. The first line produces a comma-list with a leading comma, removed in the next step (this also works in the empty case, since \tl_tail:N does not trigger an error in this case).

```

6318 \cs_new_protected:Npn \__str_convert_encode_clist:
6319 {
6320   \__str_convert_gmap_internal:N \__str_encode_clist_char:n
6321   \tl_gset:Nx \g__str_result_tl { \tl_tail:N \g__str_result_tl }

```

```

6322     }
6323 \cs_new:Npn \__str_encode_clist_char:n #1 { , #1 }

(End definition for \__str_convert_encode_clist: and \__str_encode_clist_char:n.)

```

10.3.8 8-bit encodings

This section will be entirely rewritten: it is not yet clear in what situations 8-bit encodings are used, hence I don't know what exactly should be optimized. The current approach is reasonably efficient to convert long strings, and it scales well when using many different encodings. An approach based on csnames would have a smaller constant load time for each individual conversion, but has a large hash table cost. Using a range of \count registers works for decoding, but not for encoding; one possibility there would be to use a binary tree for the mapping of Unicode characters to bytes, stored as a box, one per encoding.

Since the section is going to be rewritten, documentation lacks.

All the 8-bit encodings which l3str supports rely on the same internal functions.

`\str_declare_eight_bit_encoding:nnn` All the 8-bit encoding definition file start with `\str_declare_eight_bit_encoding:nnn` $\{ \langle \text{encoding name} \rangle \} \{ \langle \text{mapping} \rangle \} \{ \langle \text{missing bytes} \rangle \}$. The $\langle \text{mapping} \rangle$ argument is a token list of pairs $\{ \langle \text{byte} \rangle \} \{ \langle \text{Unicode} \rangle \}$ expressed in uppercase hexadecimal notation. The $\langle \text{missing} \rangle$ argument is a token list of $\{ \langle \text{byte} \rangle \}$. Every $\langle \text{byte} \rangle$ which does not appear in the $\langle \text{mapping} \rangle$ nor the $\langle \text{missing} \rangle$ lists maps to the same code point in Unicode.

```

6324 \cs_new_protected:Npn \str_declare_eight_bit_encoding:nnn #1#2#3
6325 {
6326   \tl_set:Nn \l__str_internal_tl {#1}
6327   \cs_new_protected:cpn { __str_convert_decode_#1: }
6328     { \__str_convert_decode_eight_bit:n {#1} }
6329   \cs_new_protected:cpn { __str_convert_encode_#1: }
6330     { \__str_convert_encode_eight_bit:n {#1} }
6331   \tl_const:cn { c__str_encoding_#1_tl } {#2}
6332   \tl_const:cn { c__str_encoding_#1_missing_tl } {#3}
6333 }

```

(End definition for `\str_declare_eight_bit_encoding:nnn`. This function is documented on page 74.)

```

\__str_convert_decode_eight_bit:n
\__str_decode_eight_bit_load:nn
\__str_decode_eight_bit_load_missing:n
\__str_decode_eight_bit_char:N
6334 \cs_new_protected:Npn \__str_convert_decode_eight_bit:n #1
6335 {
6336   \group_begin:
6337     \int_zero:N \l__str_internal_int
6338     \exp_last_unbraced:Nx \__str_decode_eight_bit_load:nn
6339       { \tl_use:c { c__str_encoding_#1_tl } }
6340     { \s__str_stop \prg_break: } { }
6341     \prg_break_point:
6342     \exp_last_unbraced:Nx \__str_decode_eight_bit_load_missing:n
6343       { \tl_use:c { c__str_encoding_#1_missing_tl } }
6344     { \s__str_stop \prg_break: }
6345     \prg_break_point:
6346     \flag_clear:n { str_error }
6347     \__str_convert_gmap:N \__str_decode_eight_bit_char:N
6348     \__str_if_flag_error:nnx { str_error } { decode-8-bit } {#1}
6349   \group_end:

```



```

6350 }
6351 \cs_new_protected:Npn \__str_decode_eight_bit_load:nn #1#2
6352 {
6353   \__str_use_none_delimit_by_s_stop:w #1 \s__str_stop
6354   \tex_dimen:D "#1 = \l__str_internal_int sp \scan_stop:
6355   \tex_skip:D \l__str_internal_int = "#1 sp \scan_stop:
6356   \tex_toks:D \l__str_internal_int \exp_after:wN { \int_value:w "#2 }
6357   \int_incr:N \l__str_internal_int
6358   \__str_decode_eight_bit_load:nn
6359 }
6360 \cs_new_protected:Npn \__str_decode_eight_bit_load_missing:n #1
6361 {
6362   \__str_use_none_delimit_by_s_stop:w #1 \s__str_stop
6363   \tex_dimen:D "#1 = \l__str_internal_int sp \scan_stop:
6364   \tex_skip:D \l__str_internal_int = "#1 sp \scan_stop:
6365   \tex_toks:D \l__str_internal_int \exp_after:wN
6366   { \int_use:N \c__str_replacement_char_int }
6367   \int_incr:N \l__str_internal_int
6368   \__str_decode_eight_bit_load_missing:n
6369 }
6370 \cs_new:Npn \__str_decode_eight_bit_char:N #1
6371 {
6372   #1 \s__str
6373   \if_int_compare:w \tex_dimen:D '#1 < \l__str_internal_int
6374   \if_int_compare:w \tex_skip:D \tex_dimen:D '#1 = '#1 \exp_stop_f:
6375   \tex_the:D \tex_toks:D \tex_dimen:D
6376   \fi:
6377   \fi:
6378   \int_value:w '#1 \s__str
6379 }

```

(End definition for __str_convert_decode_eight_bit:n and others.)

```

\__str_convert_encode_eight_bit:n
\__str_encode_eight_bit_load:nn
\__str_encode_eight_bit_char:n
\__str_encode_eight_bit_char_aux:n
6380 \cs_new_protected:Npn \__str_convert_encode_eight_bit:n #1
6381 {
6382   \group_begin:
6383   \int_zero:N \l__str_internal_int
6384   \exp_last_unbraced:Nx \__str_encode_eight_bit_load:nn
6385   { \tl_use:c { c__str_encoding_#1_tl } }
6386   { \s__str_stop \prg_break: } { }
6387   \prg_break_point:
6388   \flag_clear:n { str_error }
6389   \__str_convert_gmap_internal:N \__str_encode_eight_bit_char:n
6390   \__str_if_flag_error:nnx { str_error } { encode-8-bit } {#1}
6391   \group_end:
6392 }
6393 \cs_new_protected:Npn \__str_encode_eight_bit_load:nn #1#2
6394 {
6395   \__str_use_none_delimit_by_s_stop:w #1 \s__str_stop
6396   \tex_dimen:D "#2 = \l__str_internal_int sp \scan_stop:
6397   \tex_skip:D \l__str_internal_int = "#2 sp \scan_stop:
6398   \exp_args:NNf \tex_toks:D \l__str_internal_int
6399   { \__str_output_byte:n { "#1 } }

```

```

6400     \int_incr:N \l__str_internal_int
6401     \__str_encode_eight_bit_load:nn
6402   }
6403   \cs_new:Npn \__str_encode_eight_bit_char:n #1
6404   {
6405     \if_int_compare:w #1 > \c_max_register_int
6406       \flag_raise:n { str_error }
6407     \else:
6408       \if_int_compare:w \tex_dimen:D #1 < \l__str_internal_int
6409         \if_int_compare:w \tex_skip:D \tex_dimen:D #1 = #1 \exp_stop_f:
6410           \tex_the:D \tex_toks:D \tex_dimen:D #1 \exp_stop_f:
6411           \exp_after:wN \exp_after:wN \exp_after:wN \use_none:nn
6412         \fi:
6413       \fi:
6414       \__str_encode_eight_bit_char_aux:n {#1}
6415     \fi:
6416   }
6417   \cs_new:Npn \__str_encode_eight_bit_char_aux:n #1
6418   {
6419     \if_int_compare:w #1 > \c__str_max_byte_int
6420       \flag_raise:n { str_error }
6421     \else:
6422       \__str_output_byte:n {#1}
6423     \fi:
6424   }

```

(End definition for `__str_convert_encode_eight_bit:n` and others.)

10.4 Messages

General messages, and messages for the encodings and escapings loaded by default (“native”, and “bytes”).

```

6425 \__kernel_msg_new:nnn { str } { unknown-esc }
6426 { Escaping~scheme~'~#1'~(filtered:~'~#2')~unknown. }
6427 \__kernel_msg_new:nnn { str } { unknown-enc }
6428 { Encoding~scheme~'~#1'~(filtered:~'~#2')~unknown. }
6429 \__kernel_msg_new:nnnn { str } { native-escaping }
6430 { The~'native'~encoding~scheme~does~not~support~any~escaping. }
6431 {
6432   Since~native~strings~do~not~consist~in~bytes,~
6433   none~of~the~escaping~methods~make~sense.~
6434   The~specified~escaping,~'~#1',~will be ignored.
6435 }
6436 \__kernel_msg_new:nnn { str } { file-not-found }
6437 { File~'l3str-#1.def'~not~found. }

```

Message used when the “bytes” unescaping fails because the string given to `\str_set_convert:Nnnn` contains a non-byte. This cannot happen for the -8-bit engines. Messages used for other escapings and encodings are defined in each definition file.

```

6438 \bool_lazy_any:nT
6439 {
6440   \sys_if_engine luatex_p:
6441   \sys_if_engine xetex_p:
6442 }

```

```

6443 {
6444   \_kernel_msg_new:nnnn { str } { non-byte }
6445   { String~invalid~in~escaping~'#1':~it~may~only~contain~bytes. }
6446   {
6447     Some~characters~in~the~string~you~asked~to~convert~are~not~
6448     8-bit~characters.~Perhaps~the~string~is~a~'native'~Unicode~string?~
6449     If~it~is,~try~using\\
6450     \\
6451     \iow_indent:n
6452     {
6453       \iow_char:N\\str_set_convert:Nnnn \\
6454       \ \ <str-var>~\{<string>~\}~\{~native~\}~\{<target-encoding>~\}
6455     }
6456   }
6457 }

```

Those messages are used when converting to and from 8-bit encodings.

```

6458 \_kernel_msg_new:nnnn { str } { decode-8-bit }
6459 { Invalid~string~in~encoding~'#1'. }
6460 {
6461   LaTeX~came~across~a~byte~which~is~not~defined~to~represent~
6462   any~character~in~the~encoding~'#1'.
6463 }
6464 \_kernel_msg_new:nnnn { str } { encode-8-bit }
6465 { Unicode~string~cannot~be~converted~to~encoding~'#1'. }
6466 {
6467   The~encoding~'#1'~only~contains~a~subset~of~all~Unicode~characters.~
6468   LaTeX~was~asked~to~convert~a~string~to~that~encoding,~but~that~
6469   string~contains~a~character~that~'#1'~does~not~support.
6470 }

```

10.5 Escaping definitions

Several of those encodings are defined by the pdf file format. The following byte storage methods are defined:

- **bytes** (default), non-bytes are filtered out, and bytes are left untouched (this is defined by default);
- **hex** or **hexadecimal**, as per the pdfTeX primitive `\pdfescapehex`
- **name**, as per the pdfTeX primitive `\pdfescapename`
- **string**, as per the pdfTeX primitive `\pdfescapestring`
- **url**, as per the percent encoding of urls.

10.5.1 Unescape methods

`_str_convert_unescape_hex:` Take chars two by two, and interpret each pair as the hexadecimal code for a byte.
`_str_unescape_hex_auxi:N` Anything else than hexadecimal digits is ignored, raising the flag. A string which contains
`_str_unescape_hex_auxii:N` an odd number of hexadecimal digits gets 0 appended to it: this is equivalent to appending
 a 0 in all cases, and dropping it if it is alone.

```

6471 \cs_new_protected:Npn \_str_convert_unescape_hex:

```

```

6472 {
6473   \group_begin:
6474     \flag_clear:n { str_error }
6475     \int_set:Nn \tex_escapechar:D { 92 }
6476     \tl_gset:Nx \g__str_result_tl
6477       {
6478         \__str_output_byte:w "
6479         \exp_last_unbraced:Nf \__str_unescape_hex_auxi:N
6480         { \tl_to_str:N \g__str_result_tl }
6481         0 { ? 0 - 1 \prg_break: }
6482         \prg_break_point:
6483         \__str_output_end:
6484       }
6485     \__str_if_flag_error:nxn { str_error } { unescape-hex } { }
6486   \group_end:
6487 }
6488 \cs_new:Npn \__str_unescape_hex_auxi:N #1
6489 {
6490   \use_none:n #1
6491   \__str_hexadecimal_use:NTF #1
6492   { \__str_unescape_hex_auxii:N }
6493   {
6494     \flag_raise:n { str_error }
6495     \__str_unescape_hex_auxi:N
6496   }
6497 }
6498 \cs_new:Npn \__str_unescape_hex_auxii:N #1
6499 {
6500   \use_none:n #1
6501   \__str_hexadecimal_use:NTF #1
6502   {
6503     \__str_output_end:
6504     \__str_output_byte:w " \__str_unescape_hex_auxi:N
6505   }
6506   {
6507     \flag_raise:n { str_error }
6508     \__str_unescape_hex_auxii:N
6509   }
6510 }
6511 \__kernel_msg_new:nnnn { str } { unescape-hex }
6512 { String~invalid~in~escaping~'hex':~only~hexadecimal~digits~allowed. }
6513 {
6514   Some~characters~in~the~string~you~asked~to~convert~are~not~
6515   hexadecimal~digits~(0-9,~A-F,~a-f)~nor~spaces.
6516 }

```

(End definition for `__str_convert_unescape_hex:`, `__str_unescape_hex_auxi:N`, and `__str_unescape_hex_auxii:N`.)

```

\__str_convert_unescape_name:
\__str_unescape_name_loop:wNN
\__str_convert_unescape_url:
\__str_unescape_url_loop:wNN

```

The `__str_convert_unescape_name:` function replaces each occurrence of # followed by two hexadecimal digits in `\g__str_result_tl` by the corresponding byte. The `url` function is identical, with escape character % instead of #. Thus we define the two together. The arguments of `__str_tmp:w` are the character code of # or % in hexadecimal, the name of the main function to define, and the name of the auxiliary which performs the loop.

The looping auxiliary #3 finds the next escape character, reads the following two characters, and tests them. The test `__str_hexadecimal_use:NTF` leaves the upper-case digit in the input stream, hence we surround the test with `__str_output_byte:w` and `__str_output_end:.` If both characters are hexadecimal digits, they should be removed before looping: this is done by `\use_i:nnn`. If one of the characters is not a hexadecimal digit, then feed "#1 to `__str_output_byte:w` to produce the escape character, raise the flag, and call the looping function followed by the two characters (remove `\use_i:nnn`).

```

6517 \cs_set_protected:Npn \__str_tmp:w #1#2#3
6518 {
6519   \cs_new_protected:cpn { __str_convert_unescape_#2: }
6520   {
6521     \group_begin:
6522     \flag_clear:n { str_byte }
6523     \flag_clear:n { str_error }
6524     \int_set:Nn \tex_escapechar:D { 92 }
6525     \tl_gset:Nx \g__str_result_tl
6526     {
6527       \exp_after:wN #3 \g__str_result_tl
6528       #1 ? { ? \prg_break: }
6529       \prg_break_point:
6530     }
6531     \__str_if_flag_error:nnx { str_byte } { non-byte } { #2 }
6532     \__str_if_flag_error:nnx { str_error } { unescape-#2 } { }
6533   \group_end:
6534 }
6535 \cs_new:Npn #3 ##1#1##2##3
6536 {
6537   \__str_filter_bytes:n {##1}
6538   \use_none:n ##3
6539   \__str_output_byte:w "
6540   \__str_hexadecimal_use:NTF ##2
6541   {
6542     \__str_hexadecimal_use:NTF ##3
6543     { }
6544     {
6545       \flag_raise:n { str_error }
6546       * 0 + '#1 \use_i:nn
6547     }
6548   }
6549   {
6550     \flag_raise:n { str_error }
6551     0 + '#1 \use_i:nn
6552   }
6553   \__str_output_end:
6554   \use_i:nnn #3 ##2##3
6555 }
6556 \__kernel_msg_new:nnnn { str } { unescape-#2 }
6557 { String~invalid~in~escaping~'#2'. }
6558 {
6559   LaTeX~came~across~the~escape~character~'#1'~not~followed~by~
6560   two~hexadecimal~digits.~This~is~invalid~in~the~escaping~'#2'.
6561 }

```

```

6562     }
6563 \exp_after:wN \__str_tmp:w \c_hash_str { name }
6564 \__str_unescape_name_loop:wNN
6565 \exp_after:wN \__str_tmp:w \c_percent_str { url }
6566 \__str_unescape_url_loop:wNN

```

(End definition for `__str_convert_unescape_name:` and others.)

```

\__str_convert_unescape_string:
\__str_unescape_string_newlines:wN
\__str_unescape_string_loop:wNNN
\__str_unescape_string_repeat:NNNNNN

```

The **string** escaping is somewhat similar to the **name** and **url** escapings, with escape character `\`. The first step is to convert all three line endings, `^^J`, `^^M`, and `^^M^^J` to the common `^^J`, as per the PDF specification. This step cannot raise the flag.

Then the following escape sequences are decoded.

```

\n Line feed (10)
\r Carriage return (13)
\t Horizontal tab (9)
\b Backspace (8)
\f Form feed (12)
\( Left parenthesis
\) Right parenthesis
\\ Backslash

```

`\ddd` (backslash followed by 1 to 3 octal digits) Byte `ddd` (octal), subtracting 256 in case of overflow.

If followed by an end-of-line character, the backslash and the end-of-line are ignored. If followed by anything else, the backslash is ignored, raising the error flag.

```

6567 \group_begin:
6568 \char_set_catcode_other:N ^^J
6569 \char_set_catcode_other:N ^^M
6570 \cs_set_protected:Npn \__str_tmp:w #1
6571 {
6572   \cs_new_protected:Npn \__str_convert_unescape_string:
6573   {
6574     \group_begin:
6575     \flag_clear:n { str_byte }
6576     \flag_clear:n { str_error }
6577     \int_set:Nn \tex_escapechar:D { 92 }
6578     \tl_gset:Nx \g__str_result_tl
6579     {
6580       \exp_after:wN \__str_unescape_string_newlines:wN
6581       \g__str_result_tl \prg_break: ^^M ?
6582       \prg_break_point:
6583     }
6584     \tl_gset:Nx \g__str_result_tl
6585     {
6586       \exp_after:wN \__str_unescape_string_loop:wNNN
6587       \g__str_result_tl #1 ?? { ? \prg_break: }
6588       \prg_break_point:

```

```

6589         }
6590         \__str_if_flag_error:nmx { str_byte } { non-byte } { string }
6591         \__str_if_flag_error:nmx { str_error } { unescape-string } { }
6592     \group_end:
6593 }
6594 }
6595 \exp_args:No \__str_tmp:w { \c_backslash_str }
6596 \exp_last_unbraced:NNNNo
6597 \cs_new:Npn \__str_unescape_string_loop:wNNN #1 \c_backslash_str #2#3#4
6598 {
6599     \__str_filter_bytes:n {#1}
6600     \use_none:n #4
6601     \__str_output_byte:w '
6602     \__str_octal_use:NTF #2
6603     {
6604         \__str_octal_use:NTF #3
6605         {
6606             \__str_octal_use:NTF #4
6607             {
6608                 \if_int_compare:w #2 > 3 \exp_stop_f:
6609                 - 256
6610                 \fi:
6611                 \__str_unescape_string_repeat:NNNNNN
6612             }
6613             { \__str_unescape_string_repeat:NNNNNN ? }
6614         }
6615         { \__str_unescape_string_repeat:NNNNNN ?? }
6616     }
6617     {
6618         \str_case:e:nnF {#2}
6619         {
6620             { \c_backslash_str } { 134 }
6621             { ( ) } { 50 }
6622             { ) } { 51 }
6623             { r } { 15 }
6624             { f } { 14 }
6625             { n } { 12 }
6626             { t } { 11 }
6627             { b } { 10 }
6628             { ^^J } { 0 - 1 }
6629         }
6630         {
6631             \flag_raise:n { str_error }
6632             0 - 1 \use_i:nn
6633         }
6634     }
6635     \__str_output_end:
6636     \use_i:nn \__str_unescape_string_loop:wNNN #2#3#4
6637 }
6638 \cs_new:Npn \__str_unescape_string_repeat:NNNNNN #1#2#3#4#5#6
6639 { \__str_output_end: \__str_unescape_string_loop:wNNN }
6640 \cs_new:Npn \__str_unescape_string_newlines:wN #1 ^^M #2
6641 {
6642     #1

```

```

6643     \if_charcode:w ^^J #2 \else: ^^J \fi:
6644     \__str_unescape_string_newlines:wN #2
6645   }
6646   \__kernel_msg_new:nnnn { str } { unescape-string }
6647   { String~invalid~in~escaping~'string'. }
6648   {
6649     LaTeX~came~across~an~escape~character~'\c_backslash_str'~
6650     not~followed~by~any~of:~'n',~'r',~'t',~'b',~'f',~'(',~')',~
6651     '\c_backslash_str',~one~to~three~octal~digits,~or~the~end~
6652     of~a~line.
6653   }
6654 \group_end:

```

(End definition for `__str_convert_unescape_string`: and others.)

10.5.2 Escape methods

Currently, none of the escape methods can lead to errors, assuming that their input is made out of bytes.

`__str_convert_escape_hex`: Loop and convert each byte to hexadecimal.

```

\__str_escape_hex_char:N
6655 \cs_new_protected:Npn \__str_convert_escape_hex:
6656   { \__str_convert_gmap:N \__str_escape_hex_char:N }
6657 \cs_new:Npn \__str_escape_hex_char:N #1
6658   { \__str_output_hexadecimal:n { '#1' } }

```

(End definition for `__str_convert_escape_hex`: and `__str_escape_hex_char:N`.)

`__str_convert_escape_name`: For each byte, test whether it should be output as is, or be “hash-encoded”. Roughly, bytes outside the range [“2A”, “7E”] are hash-encoded. We keep two lists of exceptions: characters in `\c__str_escape_name_not_str` are not hash-encoded, and characters in the `\c__str_escape_name_str` are encoded.

```

\__str_escape_name_char:N
\__str_if_escape_name:NTF
\c__str_escape_name_str
\c__str_escape_name_not_str
6659 \str_const:Nn \c__str_escape_name_not_str { ! " $ & ' } %$
6660 \str_const:Nn \c__str_escape_name_str { }/ < > [ ] }
6661 \cs_new_protected:Npn \__str_convert_escape_name:
6662   { \__str_convert_gmap:N \__str_escape_name_char:N }
6663 \cs_new:Npn \__str_escape_name_char:N #1
6664   {
6665     \__str_if_escape_name:NTF #1 {#1}
6666     { \c_hash_str \__str_output_hexadecimal:n { '#1' } }
6667   }
6668 \prg_new_conditional:Npnn \__str_if_escape_name:N #1 { TF }
6669   {
6670     \if_int_compare:w '#1 < "2A \exp_stop_f:
6671     \__str_if_contains_char:NNTF \c__str_escape_name_not_str #1
6672     \prg_return_true: \prg_return_false:
6673   } else:
6674     \if_int_compare:w '#1 > "7E \exp_stop_f:
6675     \prg_return_false:
6676   } else:
6677     \__str_if_contains_char:NNTF \c__str_escape_name_str #1
6678     \prg_return_false: \prg_return_true:
6679   \fi:
6680 \fi:
6681 }

```


(End definition for `_str_convert_escape_name:` and others.)

`_str_convert_escape_string:` Any character below (and including) space, and any character above (and including) `del`,
`_str_escape_string_char:N` are converted to octal. One backslash is added before each parenthesis and backslash.
`_str_if_escape_string:NTF`
`\c_str_escape_string_str`

```

6682 \str_const:Nx \c\_str_escape_string_str
6683 { \c_backslash_str ( ) }
6684 \cs_new_protected:Npn \_str_convert_escape_string:
6685 { \_str_convert_gmap:N \_str_escape_string_char:N }
6686 \cs_new:Npn \_str_escape_string_char:N #1
6687 {
6688   \_str_if_escape_string:NTF #1
6689   {
6690     \_str_if_contains_char:NNT
6691     \c\_str_escape_string_str #1
6692     { \c_backslash_str }
6693     #1
6694   }
6695   {
6696     \c_backslash_str
6697     \int_div_truncate:nn {'#1} {64}
6698     \int_mod:nn { \int_div_truncate:nn {'#1} { 8 } } { 8 }
6699     \int_mod:nn {'#1} { 8 }
6700   }
6701 }
6702 \prg_new_conditional:Npnn \_str_if_escape_string:N #1 { TF }
6703 {
6704   \if_int_compare:w '#1 < "21 \exp_stop_f:
6705   \prg_return_false:
6706   \else:
6707     \if_int_compare:w '#1 > "7E \exp_stop_f:
6708     \prg_return_false:
6709     \else:
6710       \prg_return_true:
6711     \fi:
6712   \fi:
6713 }

```

(End definition for `_str_convert_escape_string:` and others.)

`_str_convert_escape_url:` This function is similar to `_str_convert_escape_name:`, escaping different characters.

```

\c\_str_escape_url_char:N
\_str_if_escape_url:NTF
6714 \cs_new_protected:Npn \_str_convert_escape_url:
6715 { \_str_convert_gmap:N \_str_escape_url_char:N }
6716 \cs_new:Npn \_str_escape_url_char:N #1
6717 {
6718   \_str_if_escape_url:NTF #1 {'#1}
6719   { \c_percent_str \_str_output_hexadecimal:n { '#1 } }
6720 }
6721 \prg_new_conditional:Npnn \_str_if_escape_url:N #1 { TF }
6722 {
6723   \if_int_compare:w '#1 < "41 \exp_stop_f:
6724   \_str_if_contains_char:nNTF { "-.<> } #1
6725   \prg_return_true: \prg_return_false:
6726   \else:
6727     \if_int_compare:w '#1 > "7E \exp_stop_f:

```

```

6728         \prg_return_false:
6729     \else:
6730         \__str_if_contains_char:nNTF { [ ] } #1
6731         \prg_return_false: \prg_return_true:
6732     \fi:
6733 \fi:
6734 }

```

(End definition for `__str_convert_escape_url:`, `__str_escape_url_char:N`, and `__str_if_escape_url:NTF`.)

10.6 Encoding definitions

The `native` encoding is automatically defined. Other encodings are loaded as needed. The following encodings are supported:

- UTF-8;
- UTF-16, big-, little-endian, or with byte order mark;
- UTF-32, big-, little-endian, or with byte order mark;
- the ISO 8859 code pages, numbered from 1 to 16, skipping the inexistent ISO 8859-12.

10.6.1 utf-8 support

`__str_convert_encode_utf8:` Loop through the internal string, and convert each character to its UTF-8 representation.
`__str_encode_utf_viii_char:n` The representation is built from the right-most (least significant) byte to the left-most (most significant) byte. Continuation bytes are in the range [128, 191], taking 64 different values, hence we roughly want to express the character code in base 64, shifting the first digit in the representation by some number depending on how many continuation bytes there are. In the range [0, 127], output the corresponding byte directly. In the range [128, 2047], output the remainder modulo 64, plus 128 as a continuation byte, then output the quotient (which is in the range [0, 31]), shifted by 192. In the next range, [2048, 65535], split the character code into residue and quotient modulo 64, output the residue as a first continuation byte, then repeat; this leaves us with a quotient in the range [0, 15], which we output shifted by 224. The last range, [65536, 1114111], follows the same pattern: once we realize that dividing twice by 64 leaves us with a number larger than 15, we repeat, producing a last continuation byte, and offset the quotient by 240 for the leading byte.

How is that implemented? `__str_encode_utf_vii_loop:wnnw` takes successive quotients as its first argument, the quotient from the previous step as its second argument (except in step 1), the bound for quotients that trigger one more step or not, and finally the offset used if this step should produce the leading byte. Leading bytes can be in the ranges [0, 127], [192, 223], [224, 239], and [240, 247] (really, that last limit should be 244 because Unicode stops at the code point 1114111). At each step, if the quotient #1 is less than the limit #3 for that range, output the leading byte (#1 shifted by #4) and stop. Otherwise, we need one more step: use the quotient of #1 by 64, and #1 as arguments for the looping auxiliary, and output the continuation byte corresponding to the remainder #2 - 64#1 + 128. The bizarre construction `- 1 + 0 *` removes the spurious initial continuation byte (better methods welcome).

```

6735 \cs_new_protected:cpn { __str_convert_encode_utf8: }
6736 { \__str_convert_gmap_internal:N \__str_encode_utf_viii_char:n }
6737 \cs_new:Npn \__str_encode_utf_viii_char:n #1
6738 {
6739   \__str_encode_utf_viii_loop:wwnnw #1 ; - 1 + 0 * ;
6740   { 128 } { 0 }
6741   { 32 } { 192 }
6742   { 16 } { 224 }
6743   { 8 } { 240 }
6744   \s__str_stop
6745 }
6746 \cs_new:Npn \__str_encode_utf_viii_loop:wwnnw #1; #2; #3#4 #5 \s__str_stop
6747 {
6748   \if_int_compare:w #1 < #3 \exp_stop_f:
6749     \__str_output_byte:n { #1 + #4 }
6750     \exp_after:wN \__str_use_none_delimit_by_s_stop:w
6751   \fi:
6752   \exp_after:wN \__str_encode_utf_viii_loop:wwnnw
6753   \int_value:w \int_div_truncate:nn {#1} {64} ; #1 ;
6754   #5 \s__str_stop
6755   \__str_output_byte:n { #2 - 64 * ( #1 - 2 ) }
6756 }

```

(End definition for `__str_convert_encode_utf8:`, `__str_encode_utf_viii_char:n`, and `__str_encode_utf_viii_loop:wwnnw`.)

`\l__str_missing_flag`
`\l__str_extra_flag`
`\l__str_overlong_flag`
`\l__str_overflow_flag`

When decoding a string that is purportedly in the UTF-8 encoding, four different errors can occur, signalled by a specific flag for each (we define those flags using `\flag_clear_new:n` rather than `\flag_new:n`, because they are shared with other encoding definition files).

- “Missing continuation byte”: a leading byte is not followed by the right number of continuation bytes.
- “Extra continuation byte”: a continuation byte appears where it was not expected, *i.e.*, not after an appropriate leading byte.
- “Overlong”: a Unicode character is expressed using more bytes than necessary, for instance, “C0”80 for the code point 0, instead of a single null byte.
- “Overflow”: this occurs when decoding produces Unicode code points greater than 1114111.

We only raise one L^AT_EX3 error message, combining all the errors which occurred. In the short message, the leading comma must be removed to get a grammatically correct sentence. In the long text, first remind the user what a correct UTF-8 string should look like, then add error-specific information.

```

6757 \flag_clear_new:n { str_missing }
6758 \flag_clear_new:n { str_extra }
6759 \flag_clear_new:n { str_overlong }
6760 \flag_clear_new:n { str_overflow }
6761 \__kernel_msg_new:nnnn { str } { utf8-decode }
6762 {
6763   Invalid-UTF-8-string:
6764   \exp_last_unbraced:Nf \use_none:n

```

```

6765     {
6766         \_str_if_flag_times:nT { str_missing } { ,~missing~continuation~byte }
6767         \_str_if_flag_times:nT { str_extra } { ,~extra~continuation~byte }
6768         \_str_if_flag_times:nT { str_overlong } { ,~overlong~form }
6769         \_str_if_flag_times:nT { str_overflow } { ,~code~point~too~large }
6770     }
6771 .
6772 }
6773 {
6774     In~the~UTF-8~encoding,~each~Unicode~character~consists~in~
6775     1~to~4~bytes,~with~the~following~bit~pattern: \
6776     \iow_indent:n
6777     {
6778         Code~point~\ \ \ \ <~128:~0xxxxxxx \
6779         Code~point~\ \ \ \ <~2048:~110xxxxx~10xxxxxx \
6780         Code~point~\ \ \ \ <~65536:~1110xxxx~10xxxxxx~10xxxxxx \
6781         Code~point~\ \ \ \ <~1114112:~11110xxx~10xxxxxx~10xxxxxx~10xxxxxx \
6782     }
6783     Bytes~of~the~form~10xxxxxx~are~called~continuation~bytes.
6784     \flag_if_raised:nT { str_missing }
6785     {
6786         \\\
6787         A~leading~byte~(in~the~range~[192,255])~was~not~followed~by~
6788         the~appropriate~number~of~continuation~bytes.
6789     }
6790     \flag_if_raised:nT { str_extra }
6791     {
6792         \\\
6793         LaTeX~came~across~a~continuation~byte~when~it~was~not~expected.
6794     }
6795     \flag_if_raised:nT { str_overlong }
6796     {
6797         \\\
6798         Every~Unicode~code~point~must~be~expressed~in~the~shortest~
6799         possible~form.~For~instance,~'0xC0'~'0x83'~is~not~a~valid~
6800         representation~for~the~code~point~3.
6801     }
6802     \flag_if_raised:nT { str_overflow }
6803     {
6804         \\\
6805         Unicode~limits~code~points~to~the~range~[0,1114111].
6806     }
6807 }

```

(End definition for \l__str_missing_flag and others.)

_str_convert_decode_utf8: Decoding is significantly harder than encoding. As before, lower some flags, which are tested at the end (in bulk, to trigger at most one L^AT_EX3 error, as explained above). We expect successive multi-byte sequences of the form *⟨start byte⟩ ⟨continuation bytes⟩*. The *_start* auxiliary tests the first byte:

- [0, "7F]: the byte stands alone, and is converted to its own character code;
- ["80, "BF]: unexpected continuation byte, raise the appropriate flag, and convert that byte to the replacement character "FFFD;

- ["C0, "FF]: this byte should be followed by some continuation byte(s).

In the first two cases, `\use_none_delimit_by_q_stop:w` removes data that only the third case requires, namely the limits of ranges of Unicode characters which can be expressed with 1, 2, 3, or 4 bytes.

We can now concentrate on the multi-byte case and the `_continuation` auxiliary. We expect `#3` to be in the range ["80, "BF]. The test for this goes as follows: if the character code is less than "80, we compare it to `—"C0`, yielding `false`; otherwise to `"C0`, yielding `true` in the range ["80, "BF] and `false` otherwise. If we find that the byte is not a continuation range, stop the current slew of bytes, output the replacement character, and continue parsing with the `_start` auxiliary, starting at the byte we just tested. Once we know that the byte is a continuation byte, leave it behind us in the input stream, compute what code point the bytes read so far would produce, and feed that number to the `_aux` function.

The `_aux` function tests whether we should look for more continuation bytes or not. If the number it receives as `#1` is less than the maximum `#4` for the current range, then we are done: check for an overlong representation by comparing `#1` with the maximum `#3` for the previous range. Otherwise, we call the `_continuation` auxiliary again, after shifting the “current code point” by `#4` (maximum from the range we just checked).

Two additional tests are needed: if we reach the end of the list of range maxima and we are still not done, then we are faced with an overflow. Clean up, and again insert the code point "FFFD for the replacement character. Also, every time we read a byte, we need to check whether we reached the end of the string. In a correct UTF-8 string, this happens automatically when the `_start` auxiliary leaves its first argument in the input stream: the end-marker begins with `\prg_break:`, which ends the loop. On the other hand, if the end is reached when looking for a continuation byte, the `\use_none:n #3` construction removes the first token from the end-marker, and leaves the `_end` auxiliary, which raises the appropriate error flag before ending the mapping.

```

6808 \cs_new_protected:cpn { __str_convert_decode_utf8: }
6809 {
6810     \flag_clear:n { str_error }
6811     \flag_clear:n { str_missing }
6812     \flag_clear:n { str_extra }
6813     \flag_clear:n { str_overlong }
6814     \flag_clear:n { str_overflow }
6815     \tl_gset:Nx \g__str_result_tl
6816     {
6817         \exp_after:wN \__str_decode_utf_viii_start:N \g__str_result_tl
6818         { \prg_break: \__str_decode_utf_viii_end: }
6819         \prg_break_point:
6820     }
6821     \__str_if_flag_error:nxx { str_error } { utf8-decode } { }
6822 }
6823 \cs_new:Npn \__str_decode_utf_viii_start:N #1
6824 {
6825     #1
6826     \if_int_compare:w ‘#1 < "C0 \exp_stop_f:
6827         \s__str
6828         \if_int_compare:w ‘#1 < "80 \exp_stop_f:
6829             \int_value:w ‘#1
6830         \else:
6831             \flag_raise:n { str_extra }

```

```

6832         \flag_raise:n { str_error }
6833         \int_use:N \c__str_replacement_char_int
6834         \fi:
6835     \else:
6836         \exp_after:wN \__str_decode_utf_viii_continuation:wwN
6837         \int_value:w \int_eval:n { '#1 - "CO } \exp_after:wN
6838         \fi:
6839         \s__str
6840         \__str_use_none_delimit_by_s_stop:w {"80} {"800} {"10000} {"110000} \s__str_stop
6841         \__str_decode_utf_viii_start:N
6842     }
6843 \cs_new:Npn \__str_decode_utf_viii_continuation:wwN
6844     #1 \s__str #2 \__str_decode_utf_viii_start:N #3
6845     {
6846         \use_none:n #3
6847         \if_int_compare:w '#3 <
6848             \if_int_compare:w '#3 < "80 \exp_stop_f: - \fi:
6849             "CO \exp_stop_f:
6850         #3
6851         \exp_after:wN \__str_decode_utf_viii_aux:wNnnwN
6852         \int_value:w \int_eval:n { #1 * "40 + '#3 - "80 } \exp_after:wN
6853     \else:
6854         \s__str
6855         \flag_raise:n { str_missing }
6856         \flag_raise:n { str_error }
6857         \int_use:N \c__str_replacement_char_int
6858         \fi:
6859         \s__str
6860         #2
6861         \__str_decode_utf_viii_start:N #3
6862     }
6863 \cs_new:Npn \__str_decode_utf_viii_aux:wNnnwN
6864     #1 \s__str #2#3#4 #5 \__str_decode_utf_viii_start:N #6
6865     {
6866         \if_int_compare:w #1 < #4 \exp_stop_f:
6867         \s__str
6868         \if_int_compare:w #1 < #3 \exp_stop_f:
6869             \flag_raise:n { str_overlong }
6870             \flag_raise:n { str_error }
6871             \int_use:N \c__str_replacement_char_int
6872         \else:
6873             #1
6874             \fi:
6875         \else:
6876             \if_meaning:w \s__str_stop #5
6877             \__str_decode_utf_viii_overflow:w #1
6878             \fi:
6879             \exp_after:wN \__str_decode_utf_viii_continuation:wwN
6880             \int_value:w \int_eval:n { #1 - #4 } \exp_after:wN
6881         \fi:
6882         \s__str
6883         #2 {#4} #5
6884         \__str_decode_utf_viii_start:N
6885     }

```

```

6886 \cs_new:Npn \__str_decode_utf_viii_overflow:w #1 \fi: #2 \fi:
6887 {
6888   \fi: \fi:
6889   \flag_raise:n { str_overflow }
6890   \flag_raise:n { str_error }
6891   \int_use:N \c__str_replacement_char_int
6892 }
6893 \cs_new:Npn \__str_decode_utf_viii_end:
6894 {
6895   \s__str
6896   \flag_raise:n { str_missing }
6897   \flag_raise:n { str_error }
6898   \int_use:N \c__str_replacement_char_int \s__str
6899   \prg_break:
6900 }

```

(End definition for `__str_convert_decode_utf8:` and others.)

10.6.2 utf-16 support

The definitions are done in a category code regime where the bytes 254 and 255 used by the byte order mark have catcode 12.

```

6901 \group_begin:
6902   \char_set_catcode_other:N ^^fe
6903   \char_set_catcode_other:N ^^ff

```

`__str_convert_encode_utf16:` When the endianness is not specified, it is big-endian by default, and we add a byte-order mark. Convert characters one by one in a loop, with different behaviours depending on the character code.

`__str_encode_utf_xvi_aux:N`
`__str_encode_utf_xvi_char:n`

- [0, "D7FF]: converted to two bytes;
- ["D800, "DFFF] are used as surrogates: they cannot be converted and are replaced by the replacement character;
- ["E000, "FFFF]: converted to two bytes;
- ["10000, "10FFFF]: converted to a pair of surrogates, each two bytes. The magic "D7C0 is "D800 – "10000/"400.

For the duration of this operation, `__str_tmp:w` is defined as a function to convert a number in the range [0, "FFFF] to a pair of bytes (either big endian or little endian), by feeding the quotient of the division of #1 by "100, followed by #1 to `__str_encode_utf_xvi_be:nn` or its `le` analog: those compute the remainder, and output two bytes for the quotient and remainder.

```

6904 \cs_new_protected:cpn { __str_convert_encode_utf16: }
6905 {
6906   \__str_encode_utf_xvi_aux:N \__str_output_byte_pair_be:n
6907   \tl_gput_left:Nx \g__str_result_tl { ^^fe ^^ff }
6908 }
6909 \cs_new_protected:cpn { __str_convert_encode_utf16be: }
6910 { \__str_encode_utf_xvi_aux:N \__str_output_byte_pair_be:n }
6911 \cs_new_protected:cpn { __str_convert_encode_utf16le: }
6912 { \__str_encode_utf_xvi_aux:N \__str_output_byte_pair_le:n }

```

```

6913 \cs_new_protected:Npn \__str_encode_utf_xvi_aux:N #1
6914 {
6915   \flag_clear:n { str_error }
6916   \cs_set_eq:NN \__str_tmp:w #1
6917   \__str_convert_gmap_internal:N \__str_encode_utf_xvi_char:n
6918   \__str_if_flag_error:nxx { str_error } { utf16-encode } { }
6919 }
6920 \cs_new:Npn \__str_encode_utf_xvi_char:n #1
6921 {
6922   \if_int_compare:w #1 < "D800 \exp_stop_f:
6923   \__str_tmp:w {#1}
6924   \else:
6925     \if_int_compare:w #1 < "10000 \exp_stop_f:
6926     \if_int_compare:w #1 < "E000 \exp_stop_f:
6927     \flag_raise:n { str_error }
6928     \__str_tmp:w { \c__str_replacement_char_int }
6929     \else:
6930       \__str_tmp:w {#1}
6931     \fi:
6932   \else:
6933     \exp_args:Nf \__str_tmp:w { \int_div_truncate:nn {#1} {"400} + "D7C0 }
6934     \exp_args:Nf \__str_tmp:w { \int_mod:nn {#1} {"400} + "DC00 }
6935   \fi:
6936   \fi:
6937 }

```

(End definition for __str_convert_encode_utf16: and others.)

\l__str_missing_flag When encoding a Unicode string to UTF-16, only one error can occur: code points in the range ["D800,"DFFF], corresponding to surrogates, cannot be encoded. We use the
 \l__str_extra_flag all-purpose flag @@_error to signal that error.
 \l__str_end_flag

When decoding a Unicode string which is purportedly in UTF-16, three errors can occur: a missing trail surrogate, an unexpected trail surrogate, and a string containing an odd number of bytes.

```

6938 \flag_clear_new:n { str_missing }
6939 \flag_clear_new:n { str_extra }
6940 \flag_clear_new:n { str_end }
6941 \__kernel_msg_new:nnnn { str } { utf16-encode }
6942 { Unicode-string-cannot-be-expressed-in-UTF-16:-surrogate. }
6943 {
6944   Surrogate-code-points~(in-the-range~[U+D800,-U+DFFF])~
6945   can~be~expressed~in~the~UTF-8~and~UTF-32~encodings,~
6946   but~not~in~the~UTF-16~encoding.
6947 }
6948 \__kernel_msg_new:nnnn { str } { utf16-decode }
6949 {
6950   Invalid-UTF-16-string:
6951   \exp_last_unbraced:Nf \use_none:n
6952   {
6953     \__str_if_flag_times:nT { str_missing } { ,~missing~trail~surrogate }
6954     \__str_if_flag_times:nT { str_extra } { ,~extra~trail~surrogate }
6955     \__str_if_flag_times:nT { str_end } { ,~odd~number~of~bytes }
6956   }
6957 .

```



```

6958     }
6959     {
6960         In~the~UTF-16~encoding,~each~Unicode~character~is~encoded~as~
6961         2~or~4~bytes:~\\
6962         \iow_indent:n
6963         {
6964             Code~point~in~[U+0000,~U+D7FF]:~two~bytes~\\
6965             Code~point~in~[U+D800,~U+DFFF]:~illegal~\\
6966             Code~point~in~[U+E000,~U+FFFF]:~two~bytes~\\
6967             Code~point~in~[U+10000,~U+10FFFF]:~
6968             a~lead~surrogate~and~a~trail~surrogate~\\
6969         }
6970         Lead~surrogates~are~pairs~of~bytes~in~the~range~[0xD800,~0xDBFF],~
6971         and~trail~surrogates~are~in~the~range~[0xDC00,~0xDFFF].
6972         \flag_if_raised:nT { str_missing }
6973         {
6974             \\
6975             A~lead~surrogate~was~not~followed~by~a~trail~surrogate.
6976         }
6977         \flag_if_raised:nT { str_extra }
6978         {
6979             \\
6980             LaTeX~came~across~a~trail~surrogate~when~it~was~not~expected.
6981         }
6982         \flag_if_raised:nT { str_end }
6983         {
6984             \\
6985             The~string~contained~an~odd~number~of~bytes.~This~is~invalid:~
6986             the~basic~code~unit~for~UTF-16~is~16~bits~(2~bytes).
6987         }
6988     }

```

(End definition for `\l__str_missing_flag`, `\l__str_extra_flag`, and `\l__str_end_flag`.)

`__str_convert_decode_utf16:` As for UTF-8, decoding UTF-16 is harder than encoding it. If the endianness is unknown, check the first two bytes: if those are "FE and "FF in either order, remove them and use the corresponding endianness, otherwise assume big-endianness. The three endianness cases are based on a common auxiliary whose first argument is 1 for big-endian and 2 for little-endian, and whose second argument, delimited by the scan mark `\s__str_stop`, is expanded once (the string may be long; passing `\g__str_result_tl` as an argument before expansion is cheaper).

The `__str_decode_utf_xvi:Nw` function defines `__str_tmp:w` to take two arguments and return the character code of the first one if the string is big-endian, and the second one if the string is little-endian, then loops over the string using `__str_decode_utf_xvi_pair:NN` described below.

```

6989     \cs_new_protected:cpn { __str_convert_decode_utf16be: }
6990     { \__str_decode_utf_xvi:Nw 1 \g__str_result_tl \s__str_stop }
6991     \cs_new_protected:cpn { __str_convert_decode_utf16le: }
6992     { \__str_decode_utf_xvi:Nw 2 \g__str_result_tl \s__str_stop }
6993     \cs_new_protected:cpn { __str_convert_decode_utf16: }
6994     {
6995         \exp_after:wN \__str_decode_utf_xvi_bom:NN
6996         \g__str_result_tl \s__str_stop \s__str_stop \s__str_stop

```

```

6997     }
6998     \cs_new_protected:Npn \__str_decode_utf_xvi_bom:NN #1#2
6999     {
7000         \str_if_eq:nnTF { #1#2 } { ^^ff ^^fe }
7001         { \__str_decode_utf_xvi:Nw 2 }
7002         {
7003             \str_if_eq:nnTF { #1#2 } { ^^fe ^^ff }
7004             { \__str_decode_utf_xvi:Nw 1 }
7005             { \__str_decode_utf_xvi:Nw 1 #1#2 }
7006         }
7007     }
7008     \cs_new_protected:Npn \__str_decode_utf_xvi:Nw #1#2 \s__str_stop
7009     {
7010         \flag_clear:n { str_error }
7011         \flag_clear:n { str_missing }
7012         \flag_clear:n { str_extra }
7013         \flag_clear:n { str_end }
7014         \cs_set:Npn \__str_tmp:w ##1 ##2 { ' ## #1 }
7015         \tl_gset:Nx \g__str_result_tl
7016         {
7017             \exp_after:wN \__str_decode_utf_xvi_pair:NN
7018             #2 \q__str_nil \q__str_nil
7019             \prg_break_point:
7020         }
7021         \__str_if_flag_error:nnx { str_error } { utf16-decode } { }
7022     }

```

(End definition for `__str_convert_decode_utf16:` and others.)

```

\__str_decode_utf_xvi_pair:NN
\__str_decode_utf_xvi_quad:NNwNN
\__str_decode_utf_xvi_pair_end:Nw
\__str_decode_utf_xvi_error:nnN
\__str_decode_utf_xvi_extra:NNw

```

Bytes are read two at a time. At this stage, `\@@_tmp:w #1#2` expands to the character code of the most significant byte, and we distinguish cases depending on which range it lies in:

- ["D8, "DB] signals a lead surrogate, and the integer expression yields 1 (ε -TEX rounds ties away from zero);
- ["DC, "DF] signals a trail surrogate, unexpected here, and the integer expression yields 2;
- any other value signals a code point in the Basic Multilingual Plane, which stands for itself, and the `\if_case:w` construction expands to nothing (cases other than 1 or 2), leaving the relevant material in the input stream, followed by another call to the `_pair` auxiliary.

The case of a lead surrogate is treated by the `_quad` auxiliary, whose arguments `#1`, `#2`, `#4` and `#5` are the four bytes. We expect the most significant byte of `#4#5` to be in the range ["DC, "DF] (trail surrogate). The test is similar to the test used for continuation bytes in the UTF-8 decoding functions. In the case where `#4#5` is indeed a trail surrogate, leave `#1#2#4#5 \s__str <code point> \s__str`, and remove the pair `#4#5` before looping with `__str_decode_utf_xvi_pair:NN`. Otherwise, of course, complain about the missing surrogate.

The magic number "D7F7 is such that `"D7F7*"400 = "D800*"400+"DC00–"10000`.

Every time we read a pair of bytes, we test for the end-marker `\q__str_nil`. When reaching the end, we additionally check that the string had an even length. Also, if the end is reached when expecting a trail surrogate, we treat that as a missing surrogate.

```

7023 \cs_new:Npn \__str_decode_utf_xvi_pair:NN #1#2
7024 {
7025   \if_meaning:w \q__str_nil #2
7026   \__str_decode_utf_xvi_pair_end:Nw #1
7027   \fi:
7028   \if_case:w
7029     \int_eval:n { ( \__str_tmp:w #1#2 - "D6 ) / 4 } \scan_stop:
7030   \or: \exp_after:wN \__str_decode_utf_xvi_quad:NNwNN
7031   \or: \exp_after:wN \__str_decode_utf_xvi_extra:NNw
7032   \fi:
7033   #1#2 \s__str
7034   \int_eval:n { "100 * \__str_tmp:w #1#2 + \__str_tmp:w #2#1 } \s__str
7035   \__str_decode_utf_xvi_pair:NN
7036 }
7037 \cs_new:Npn \__str_decode_utf_xvi_quad:NNwNN
7038   #1#2 #3 \__str_decode_utf_xvi_pair:NN #4#5
7039 {
7040   \if_meaning:w \q__str_nil #5
7041   \__str_decode_utf_xvi_error:nNN { missing } #1#2
7042   \__str_decode_utf_xvi_pair_end:Nw #4
7043   \fi:
7044   \if_int_compare:w
7045     \if_int_compare:w \__str_tmp:w #4#5 < "DC \exp_stop_f:
7046       0 = 1
7047     \else:
7048       \__str_tmp:w #4#5 < "E0
7049     \fi:
7050     \exp_stop_f:
7051     #1 #2 #4 #5 \s__str
7052     \int_eval:n
7053     {
7054       ( "100 * \__str_tmp:w #1#2 + \__str_tmp:w #2#1 - "D7F7 ) * "400
7055       + "100 * \__str_tmp:w #4#5 + \__str_tmp:w #5#4
7056     }
7057     \s__str
7058     \exp_after:wN \use_i:nnn
7059   \else:
7060     \__str_decode_utf_xvi_error:nNN { missing } #1#2
7061   \fi:
7062   \__str_decode_utf_xvi_pair:NN #4#5
7063 }
7064 \cs_new:Npn \__str_decode_utf_xvi_pair_end:Nw #1 \fi:
7065 {
7066   \fi:
7067   \if_meaning:w \q__str_nil #1
7068   \else:
7069     \__str_decode_utf_xvi_error:nNN { end } #1 \prg_do_nothing:
7070   \fi:
7071   \prg_break:
7072 }
7073 \cs_new:Npn \__str_decode_utf_xvi_extra:NNw #1#2 \s__str #3 \s__str

```

```

7074     { \__str_decode_utf_xvi_error:nn { extra } #1#2 }
7075 \cs_new:Npn \__str_decode_utf_xvi_error:nn #1#2#3
7076 {
7077     \flag_raise:n { str_error }
7078     \flag_raise:n { str_#1 }
7079     #2 #3 \s__str
7080     \int_use:N \c__str_replacement_char_int \s__str
7081 }

```

(End definition for __str_decode_utf_xvi_pair:nn and others.)

Restore the original catcodes of bytes 254 and 255.

```

7082 \group_end:

```

10.6.3 utf-32 support

The definitions are done in a category code regime where the bytes 0, 254 and 255 used by the byte order mark have catcode “other”.

```

7083 \group_begin:
7084 \char_set_catcode_other:N ^^00
7085 \char_set_catcode_other:N ^^fe
7086 \char_set_catcode_other:N ^^ff

```

__str_convert_encode_utf32: Convert each integer in the comma-list \g__str_result_tl to a sequence of four bytes. The functions for big-endian and little-endian encodings are very similar, but the __str_output_byte:n instructions are reversed.

```

\__str_convert_encode_utf32be:
\__str_convert_encode_utf32le:
\__str_encode_utf_xxxii_be:n
\__str_encode_utf_xxxii_be_aux:nn
\__str_encode_utf_xxxii_le:n
\__str_encode_utf_xxxii_le_aux:nn
7087 \cs_new_protected:cpn { __str_convert_encode_utf32: }
7088 {
7089     \__str_convert_gmap_internal:N \__str_encode_utf_xxxii_be:n
7090     \tl_gput_left:Nx \g__str_result_tl { ^^00 ^^00 ^^fe ^^ff }
7091 }
7092 \cs_new_protected:cpn { __str_convert_encode_utf32be: }
7093 { \__str_convert_gmap_internal:N \__str_encode_utf_xxxii_be:n }
7094 \cs_new_protected:cpn { __str_convert_encode_utf32le: }
7095 { \__str_convert_gmap_internal:N \__str_encode_utf_xxxii_le:n }
7096 \cs_new:Npn \__str_encode_utf_xxxii_be:n #1
7097 {
7098     \exp_args:Nf \__str_encode_utf_xxxii_be_aux:nn
7099     { \int_div_truncate:nn {#1} { "100 } } {#1}
7100 }
7101 \cs_new:Npn \__str_encode_utf_xxxii_be_aux:nn #1#2
7102 {
7103     ^^00
7104     \__str_output_byte_pair_be:n {#1}
7105     \__str_output_byte:n { #2 - #1 * "100 }
7106 }
7107 \cs_new:Npn \__str_encode_utf_xxxii_le:n #1
7108 {
7109     \exp_args:Nf \__str_encode_utf_xxxii_le_aux:nn
7110     { \int_div_truncate:nn {#1} { "100 } } {#1}
7111 }
7112 \cs_new:Npn \__str_encode_utf_xxxii_le_aux:nn #1#2
7113 {
7114     \__str_output_byte:n { #2 - #1 * "100 }

```

```

7115     \__str_output_byte_pair_le:n {#1}
7116     ^^00
7117 }

```

(End definition for `__str_convert_encode_utf32:` and others.)

str_overflow There can be no error when encoding in UTF-32. When decoding, the string may not
str_end have length $4n$, or it may contain code points larger than "10FFFF". The latter case often happens if the encoding was in fact not UTF-32, because most arbitrary strings are not valid in UTF-32.

```

7118 \flag_clear_new:n { str_overflow }
7119 \flag_clear_new:n { str_end }
7120 \__kernel_msg_new:nnnn { str } { utf32-decode }
7121 {
7122   Invalid-UTF-32-string:
7123   \exp_last_unbraced:Nf \use_none:n
7124   {
7125     \__str_if_flag_times:nT { str_overflow } { ,~code-point-too-large }
7126     \__str_if_flag_times:nT { str_end }      { ,~truncated-string }
7127   }
7128   .
7129 }
7130 {
7131   In~the~UTF-32~encoding,~every~Unicode~character~
7132   (in~the~range~[U+0000,~U+10FFFF])~is~encoded~as~4~bytes.
7133   \flag_if_raised:nT { str_overflow }
7134   {
7135     \\\
7136     LaTeX~came~across~a~code~point~larger~than~1114111,~
7137     the~maximum~code~point~defined~by~Unicode.~
7138     Perhaps~the~string~was~not~encoded~in~the~UTF-32~encoding?
7139   }
7140   \flag_if_raised:nT { str_end }
7141   {
7142     \\\
7143     The~length~of~the~string~is~not~a~multiple~of~4.~
7144     Perhaps~the~string~was~truncated?
7145   }
7146 }

```

(End definition for `str_overflow` and `str_end`. These variables are documented on page ??.)

`__str_convert_decode_utf32:` The structure is similar to UTF-16 decoding functions. If the endianness is not given, test
`_str_convert_decode_utf32be:` the first 4 bytes of the string (possibly `\s__str_stop` if the string is too short) for the
`_str_convert_decode_utf32le:` presence of a byte-order mark. If there is a byte-order mark, use that endianness, and
`_str_decode_utf_xxxii_bom:NNNN` remove the 4 bytes, otherwise default to big-endian, and leave the 4 bytes in place. The
`__str_decode_utf_xxxii:Nw` `__str_decode_utf_xxxii:Nw` auxiliary receives 1 or 2 as its first argument indicating
`_str_decode_utf_xxxii_loop:NNNN` endianness, and the string to convert as its second argument (expanded or not). It sets
`_str_decode_utf_xxxii_end:w` `__str_tmp:w` to expand to the character code of either of its two arguments depending
on endianness, then triggers the `_loop` auxiliary inside an `x`-expanding assignment to
`\g__str_result_tl`.

The `_loop` auxiliary first checks for the end-of-string marker `\s__str_stop`, calling the `_end` auxiliary if appropriate. Otherwise, leave the $\langle 4 \text{ bytes} \rangle$ `\s__str` behind, then

check that the code point is not overflowing: the leading byte must be 0, and the following byte at most 16.

In the ending code, we check that there remains no byte: there should be nothing left until the first `\s__str_stop`. Break the map.

```

7147 \cs_new_protected:cpn { __str_convert_decode_utf32be: }
7148 { \__str_decode_utf_xxxii:Nw 1 \g__str_result_tl \s__str_stop }
7149 \cs_new_protected:cpn { __str_convert_decode_utf32le: }
7150 { \__str_decode_utf_xxxii:Nw 2 \g__str_result_tl \s__str_stop }
7151 \cs_new_protected:cpn { __str_convert_decode_utf32: }
7152 {
7153   \exp_after:wN \__str_decode_utf_xxxii_bom:NNNN \g__str_result_tl
7154   \s__str_stop \s__str_stop \s__str_stop \s__str_stop \s__str_stop
7155 }
7156 \cs_new_protected:Npn \__str_decode_utf_xxxii_bom:NNNN #1#2#3#4
7157 {
7158   \str_if_eq:nnTF { #1#2#3#4 } { ^^ff ^^fe ^^00 ^^00 }
7159   { \__str_decode_utf_xxxii:Nw 2 }
7160   {
7161     \str_if_eq:nnTF { #1#2#3#4 } { ^^00 ^^00 ^^fe ^^ff }
7162     { \__str_decode_utf_xxxii:Nw 1 }
7163     { \__str_decode_utf_xxxii:Nw 1 #1#2#3#4 }
7164   }
7165 }
7166 \cs_new_protected:Npn \__str_decode_utf_xxxii:Nw #1#2 \s__str_stop
7167 {
7168   \flag_clear:n { str_overflow }
7169   \flag_clear:n { str_end }
7170   \flag_clear:n { str_error }
7171   \cs_set:Npn \__str_tmp:w ##1 ##2 { ' ## #1 }
7172   \tl_gset:Nx \g__str_result_tl
7173   {
7174     \exp_after:wN \__str_decode_utf_xxxii_loop:NNNN
7175     #2 \s__str_stop \s__str_stop \s__str_stop \s__str_stop
7176     \prg_break_point:
7177   }
7178   \__str_if_flag_error:nnx { str_error } { utf32-decode } { }
7179 }
7180 \cs_new:Npn \__str_decode_utf_xxxii_loop:NNNN #1#2#3#4
7181 {
7182   \if_meaning:w \s__str_stop #4
7183   \exp_after:wN \__str_decode_utf_xxxii_end:w
7184   \fi:
7185   #1#2#3#4 \s__str
7186   \if_int_compare:w \__str_tmp:w #1#4 > 0 \exp_stop_f:
7187     \flag_raise:n { str_overflow }
7188     \flag_raise:n { str_error }
7189     \int_use:N \c__str_replacement_char_int
7190   \else:
7191     \if_int_compare:w \__str_tmp:w #2#3 > 16 \exp_stop_f:
7192       \flag_raise:n { str_overflow }
7193       \flag_raise:n { str_error }
7194       \int_use:N \c__str_replacement_char_int
7195     \else:
7196       \int_eval:n

```

```

7197         { \_str_tmp:w #2#3*"10000 + \_str_tmp:w #3#2*"100 + \_str_tmp:w #4#1 }
7198     \fi:
7199     \fi:
7200     \s__str
7201     \_str_decode_utf_xxxii_loop:NNNN
7202 }
7203 \cs_new:Npn \_str_decode_utf_xxxii_end:w #1 \s__str_stop
7204 {
7205     \tl_if_empty:nF {#1}
7206     {
7207         \flag_raise:n { str_end }
7208         \flag_raise:n { str_error }
7209         #1 \s__str
7210         \int_use:N \c__str_replacement_char_int \s__str
7211     }
7212     \prg_break:
7213 }

```

(End definition for `_str_convert_decode_utf32:` and others.)

Restore the original catcodes of bytes 0, 254 and 255.

```

7214 \group_end:

```

```

7215 </initex | package>

```

10.6.4 iso 8859 support

The ISO-8859-1 encoding exactly matches with the 256 first Unicode characters. For other 8-bit encodings of the ISO-8859 family, we keep track only of differences, and of unassigned bytes.

```

7216 <*iso88591>
7217 \str_declare_eight_bit_encoding:nnn { iso88591 }
7218 {
7219 }
7220 {
7221 }
7222 </iso88591>
7223 <*iso88592>
7224 \str_declare_eight_bit_encoding:nnn { iso88592 }
7225 {
7226     { A1 } { 0104 }
7227     { A2 } { 02D8 }
7228     { A3 } { 0141 }
7229     { A5 } { 013D }
7230     { A6 } { 015A }
7231     { A9 } { 0160 }
7232     { AA } { 015E }
7233     { AB } { 0164 }
7234     { AC } { 0179 }
7235     { AE } { 017D }
7236     { AF } { 017B }
7237     { B1 } { 0105 }
7238     { B2 } { 02DB }
7239     { B3 } { 0142 }
7240     { B5 } { 013E }

```

```

7241     { B6 } { 015B }
7242     { B7 } { 02C7 }
7243     { B9 } { 0161 }
7244     { BA } { 015F }
7245     { BB } { 0165 }
7246     { BC } { 017A }
7247     { BD } { 02DD }
7248     { BE } { 017E }
7249     { BF } { 017C }
7250     { C0 } { 0154 }
7251     { C3 } { 0102 }
7252     { C5 } { 0139 }
7253     { C6 } { 0106 }
7254     { C8 } { 010C }
7255     { CA } { 0118 }
7256     { CC } { 011A }
7257     { CF } { 010E }
7258     { D0 } { 0110 }
7259     { D1 } { 0143 }
7260     { D2 } { 0147 }
7261     { D5 } { 0150 }
7262     { D8 } { 0158 }
7263     { D9 } { 016E }
7264     { DB } { 0170 }
7265     { DE } { 0162 }
7266     { E0 } { 0155 }
7267     { E3 } { 0103 }
7268     { E5 } { 013A }
7269     { E6 } { 0107 }
7270     { E8 } { 010D }
7271     { EA } { 0119 }
7272     { EC } { 011B }
7273     { EF } { 010F }
7274     { F0 } { 0111 }
7275     { F1 } { 0144 }
7276     { F2 } { 0148 }
7277     { F5 } { 0151 }
7278     { F8 } { 0159 }
7279     { F9 } { 016F }
7280     { FB } { 0171 }
7281     { FE } { 0163 }
7282     { FF } { 02D9 }
7283     }
7284     {
7285     }
7286     </iso88592>
7287     <*iso88593>
7288     \str_declare_eight_bit_encoding:nmn { iso88593 }
7289     {
7290         { A1 } { 0126 }
7291         { A2 } { 02D8 }
7292         { A6 } { 0124 }
7293         { A9 } { 0130 }
7294         { AA } { 015E }

```



```

7295     { AB } { 011E }
7296     { AC } { 0134 }
7297     { AF } { 017B }
7298     { B1 } { 0127 }
7299     { B6 } { 0125 }
7300     { B9 } { 0131 }
7301     { BA } { 015F }
7302     { BB } { 011F }
7303     { BC } { 0135 }
7304     { BF } { 017C }
7305     { C5 } { 010A }
7306     { C6 } { 0108 }
7307     { D5 } { 0120 }
7308     { D8 } { 011C }
7309     { DD } { 016C }
7310     { DE } { 015C }
7311     { E5 } { 010B }
7312     { E6 } { 0109 }
7313     { F5 } { 0121 }
7314     { F8 } { 011D }
7315     { FD } { 016D }
7316     { FE } { 015D }
7317     { FF } { 02D9 }
7318 }
7319 {
7320     { A5 }
7321     { AE }
7322     { BE }
7323     { C3 }
7324     { D0 }
7325     { E3 }
7326     { F0 }
7327 }
7328 </iso88593>
7329 <*:iso88594>
7330 \str_declare_eight_bit_encoding:nnn { iso88594 }
7331 {
7332     { A1 } { 0104 }
7333     { A2 } { 0138 }
7334     { A3 } { 0156 }
7335     { A5 } { 0128 }
7336     { A6 } { 013B }
7337     { A9 } { 0160 }
7338     { AA } { 0112 }
7339     { AB } { 0122 }
7340     { AC } { 0166 }
7341     { AE } { 017D }
7342     { B1 } { 0105 }
7343     { B2 } { 02DB }
7344     { B3 } { 0157 }
7345     { B5 } { 0129 }
7346     { B6 } { 013C }
7347     { B7 } { 02C7 }
7348     { B9 } { 0161 }

```

```

7349     { BA } { 0113 }
7350     { BB } { 0123 }
7351     { BC } { 0167 }
7352     { BD } { 014A }
7353     { BE } { 017E }
7354     { BF } { 014B }
7355     { C0 } { 0100 }
7356     { C7 } { 012E }
7357     { C8 } { 010C }
7358     { CA } { 0118 }
7359     { CC } { 0116 }
7360     { CF } { 012A }
7361     { D0 } { 0110 }
7362     { D1 } { 0145 }
7363     { D2 } { 014C }
7364     { D3 } { 0136 }
7365     { D9 } { 0172 }
7366     { DD } { 0168 }
7367     { DE } { 016A }
7368     { E0 } { 0101 }
7369     { E7 } { 012F }
7370     { E8 } { 010D }
7371     { EA } { 0119 }
7372     { EC } { 0117 }
7373     { EF } { 012B }
7374     { F0 } { 0111 }
7375     { F1 } { 0146 }
7376     { F2 } { 014D }
7377     { F3 } { 0137 }
7378     { F9 } { 0173 }
7379     { FD } { 0169 }
7380     { FE } { 016B }
7381     { FF } { 02D9 }
7382 }
7383 {
7384 }
7385 </iso88594>
7386 <iso88595>
7387 \str_declare_eight_bit_encoding:nnn { iso88595 }
7388 {
7389     { A1 } { 0401 }
7390     { A2 } { 0402 }
7391     { A3 } { 0403 }
7392     { A4 } { 0404 }
7393     { A5 } { 0405 }
7394     { A6 } { 0406 }
7395     { A7 } { 0407 }
7396     { A8 } { 0408 }
7397     { A9 } { 0409 }
7398     { AA } { 040A }
7399     { AB } { 040B }
7400     { AC } { 040C }
7401     { AE } { 040E }
7402     { AF } { 040F }

```

7403	{ B0 }	{ 0410 }
7404	{ B1 }	{ 0411 }
7405	{ B2 }	{ 0412 }
7406	{ B3 }	{ 0413 }
7407	{ B4 }	{ 0414 }
7408	{ B5 }	{ 0415 }
7409	{ B6 }	{ 0416 }
7410	{ B7 }	{ 0417 }
7411	{ B8 }	{ 0418 }
7412	{ B9 }	{ 0419 }
7413	{ BA }	{ 041A }
7414	{ BB }	{ 041B }
7415	{ BC }	{ 041C }
7416	{ BD }	{ 041D }
7417	{ BE }	{ 041E }
7418	{ BF }	{ 041F }
7419	{ C0 }	{ 0420 }
7420	{ C1 }	{ 0421 }
7421	{ C2 }	{ 0422 }
7422	{ C3 }	{ 0423 }
7423	{ C4 }	{ 0424 }
7424	{ C5 }	{ 0425 }
7425	{ C6 }	{ 0426 }
7426	{ C7 }	{ 0427 }
7427	{ C8 }	{ 0428 }
7428	{ C9 }	{ 0429 }
7429	{ CA }	{ 042A }
7430	{ CB }	{ 042B }
7431	{ CC }	{ 042C }
7432	{ CD }	{ 042D }
7433	{ CE }	{ 042E }
7434	{ CF }	{ 042F }
7435	{ D0 }	{ 0430 }
7436	{ D1 }	{ 0431 }
7437	{ D2 }	{ 0432 }
7438	{ D3 }	{ 0433 }
7439	{ D4 }	{ 0434 }
7440	{ D5 }	{ 0435 }
7441	{ D6 }	{ 0436 }
7442	{ D7 }	{ 0437 }
7443	{ D8 }	{ 0438 }
7444	{ D9 }	{ 0439 }
7445	{ DA }	{ 043A }
7446	{ DB }	{ 043B }
7447	{ DC }	{ 043C }
7448	{ DD }	{ 043D }
7449	{ DE }	{ 043E }
7450	{ DF }	{ 043F }
7451	{ E0 }	{ 0440 }
7452	{ E1 }	{ 0441 }
7453	{ E2 }	{ 0442 }
7454	{ E3 }	{ 0443 }
7455	{ E4 }	{ 0444 }
7456	{ E5 }	{ 0445 }

```

7457     { E6 } { 0446 }
7458     { E7 } { 0447 }
7459     { E8 } { 0448 }
7460     { E9 } { 0449 }
7461     { EA } { 044A }
7462     { EB } { 044B }
7463     { EC } { 044C }
7464     { ED } { 044D }
7465     { EE } { 044E }
7466     { EF } { 044F }
7467     { F0 } { 2116 }
7468     { F1 } { 0451 }
7469     { F2 } { 0452 }
7470     { F3 } { 0453 }
7471     { F4 } { 0454 }
7472     { F5 } { 0455 }
7473     { F6 } { 0456 }
7474     { F7 } { 0457 }
7475     { F8 } { 0458 }
7476     { F9 } { 0459 }
7477     { FA } { 045A }
7478     { FB } { 045B }
7479     { FC } { 045C }
7480     { FD } { 00A7 }
7481     { FE } { 045E }
7482     { FF } { 045F }
7483 }
7484 {
7485 }
7486 </iso88595>
7487 < *iso88596>
7488 \str_declare_eight_bit_encoding:nnn { iso88596 }
7489 {
7490     { AC } { 060C }
7491     { BB } { 061B }
7492     { BF } { 061F }
7493     { C1 } { 0621 }
7494     { C2 } { 0622 }
7495     { C3 } { 0623 }
7496     { C4 } { 0624 }
7497     { C5 } { 0625 }
7498     { C6 } { 0626 }
7499     { C7 } { 0627 }
7500     { C8 } { 0628 }
7501     { C9 } { 0629 }
7502     { CA } { 062A }
7503     { CB } { 062B }
7504     { CC } { 062C }
7505     { CD } { 062D }
7506     { CE } { 062E }
7507     { CF } { 062F }
7508     { D0 } { 0630 }
7509     { D1 } { 0631 }
7510     { D2 } { 0632 }

```

```

7511      { D3 } { 0633 }
7512      { D4 } { 0634 }
7513      { D5 } { 0635 }
7514      { D6 } { 0636 }
7515      { D7 } { 0637 }
7516      { D8 } { 0638 }
7517      { D9 } { 0639 }
7518      { DA } { 063A }
7519      { E0 } { 0640 }
7520      { E1 } { 0641 }
7521      { E2 } { 0642 }
7522      { E3 } { 0643 }
7523      { E4 } { 0644 }
7524      { E5 } { 0645 }
7525      { E6 } { 0646 }
7526      { E7 } { 0647 }
7527      { E8 } { 0648 }
7528      { E9 } { 0649 }
7529      { EA } { 064A }
7530      { EB } { 064B }
7531      { EC } { 064C }
7532      { ED } { 064D }
7533      { EE } { 064E }
7534      { EF } { 064F }
7535      { F0 } { 0650 }
7536      { F1 } { 0651 }
7537      { F2 } { 0652 }
7538      }
7539      {
7540          { A1 }
7541          { A2 }
7542          { A3 }
7543          { A5 }
7544          { A6 }
7545          { A7 }
7546          { A8 }
7547          { A9 }
7548          { AA }
7549          { AB }
7550          { AE }
7551          { AF }
7552          { B0 }
7553          { B1 }
7554          { B2 }
7555          { B3 }
7556          { B4 }
7557          { B5 }
7558          { B6 }
7559          { B7 }
7560          { B8 }
7561          { B9 }
7562          { BA }
7563          { BC }
7564          { BD }

```

```

7565     { BE }
7566     { CO }
7567     { DB }
7568     { DC }
7569     { DD }
7570     { DE }
7571     { DF }
7572 }
7573 </iso88596>
7574 <*iso88597>
7575 \str_declare_eight_bit_encoding:nnn { iso88597 }
7576 {
7577     { A1 } { 2018 }
7578     { A2 } { 2019 }
7579     { A4 } { 20AC }
7580     { A5 } { 20AF }
7581     { AA } { 037A }
7582     { AF } { 2015 }
7583     { B4 } { 0384 }
7584     { B5 } { 0385 }
7585     { B6 } { 0386 }
7586     { B8 } { 0388 }
7587     { B9 } { 0389 }
7588     { BA } { 038A }
7589     { BC } { 038C }
7590     { BE } { 038E }
7591     { BF } { 038F }
7592     { C0 } { 0390 }
7593     { C1 } { 0391 }
7594     { C2 } { 0392 }
7595     { C3 } { 0393 }
7596     { C4 } { 0394 }
7597     { C5 } { 0395 }
7598     { C6 } { 0396 }
7599     { C7 } { 0397 }
7600     { C8 } { 0398 }
7601     { C9 } { 0399 }
7602     { CA } { 039A }
7603     { CB } { 039B }
7604     { CC } { 039C }
7605     { CD } { 039D }
7606     { CE } { 039E }
7607     { CF } { 039F }
7608     { D0 } { 03A0 }
7609     { D1 } { 03A1 }
7610     { D3 } { 03A3 }
7611     { D4 } { 03A4 }
7612     { D5 } { 03A5 }
7613     { D6 } { 03A6 }
7614     { D7 } { 03A7 }
7615     { D8 } { 03A8 }
7616     { D9 } { 03A9 }
7617     { DA } { 03AA }
7618     { DB } { 03AB }

```

```

7619     { DC } { 03AC }
7620     { DD } { 03AD }
7621     { DE } { 03AE }
7622     { DF } { 03AF }
7623     { E0 } { 03B0 }
7624     { E1 } { 03B1 }
7625     { E2 } { 03B2 }
7626     { E3 } { 03B3 }
7627     { E4 } { 03B4 }
7628     { E5 } { 03B5 }
7629     { E6 } { 03B6 }
7630     { E7 } { 03B7 }
7631     { E8 } { 03B8 }
7632     { E9 } { 03B9 }
7633     { EA } { 03BA }
7634     { EB } { 03BB }
7635     { EC } { 03BC }
7636     { ED } { 03BD }
7637     { EE } { 03BE }
7638     { EF } { 03BF }
7639     { F0 } { 03C0 }
7640     { F1 } { 03C1 }
7641     { F2 } { 03C2 }
7642     { F3 } { 03C3 }
7643     { F4 } { 03C4 }
7644     { F5 } { 03C5 }
7645     { F6 } { 03C6 }
7646     { F7 } { 03C7 }
7647     { F8 } { 03C8 }
7648     { F9 } { 03C9 }
7649     { FA } { 03CA }
7650     { FB } { 03CB }
7651     { FC } { 03CC }
7652     { FD } { 03CD }
7653     { FE } { 03CE }
7654 }
7655 {
7656     { AE }
7657     { D2 }
7658 }
7659 </iso88597>
7660 <*iso88598>
7661 \str_declare_eight_bit_encoding:nnn { iso88598 }
7662 {
7663     { AA } { 00D7 }
7664     { BA } { 00F7 }
7665     { DF } { 2017 }
7666     { E0 } { 05D0 }
7667     { E1 } { 05D1 }
7668     { E2 } { 05D2 }
7669     { E3 } { 05D3 }
7670     { E4 } { 05D4 }
7671     { E5 } { 05D5 }
7672     { E6 } { 05D6 }

```

```

7673      { E7 } { 05D7 }
7674      { E8 } { 05D8 }
7675      { E9 } { 05D9 }
7676      { EA } { 05DA }
7677      { EB } { 05DB }
7678      { EC } { 05DC }
7679      { ED } { 05DD }
7680      { EE } { 05DE }
7681      { EF } { 05DF }
7682      { F0 } { 05E0 }
7683      { F1 } { 05E1 }
7684      { F2 } { 05E2 }
7685      { F3 } { 05E3 }
7686      { F4 } { 05E4 }
7687      { F5 } { 05E5 }
7688      { F6 } { 05E6 }
7689      { F7 } { 05E7 }
7690      { F8 } { 05E8 }
7691      { F9 } { 05E9 }
7692      { FA } { 05EA }
7693      { FD } { 200E }
7694      { FE } { 200F }
7695      }
7696      {
7697          { A1 }
7698          { BF }
7699          { C0 }
7700          { C1 }
7701          { C2 }
7702          { C3 }
7703          { C4 }
7704          { C5 }
7705          { C6 }
7706          { C7 }
7707          { C8 }
7708          { C9 }
7709          { CA }
7710          { CB }
7711          { CC }
7712          { CD }
7713          { CE }
7714          { CF }
7715          { D0 }
7716          { D1 }
7717          { D2 }
7718          { D3 }
7719          { D4 }
7720          { D5 }
7721          { D6 }
7722          { D7 }
7723          { D8 }
7724          { D9 }
7725          { DA }
7726          { DB }

```



```

7727     { DC }
7728     { DD }
7729     { DE }
7730     { FB }
7731     { FC }
7732 }
7733 </iso88598>
7734 <*iso88599>
7735 \str_declare_eight_bit_encoding:nnn { iso88599 }
7736 {
7737     { DO } { 011E }
7738     { DD } { 0130 }
7739     { DE } { 015E }
7740     { FO } { 011F }
7741     { FD } { 0131 }
7742     { FE } { 015F }
7743 }
7744 {
7745 }
7746 </iso88599>
7747 <*iso885910>
7748 \str_declare_eight_bit_encoding:nnn { iso885910 }
7749 {
7750     { A1 } { 0104 }
7751     { A2 } { 0112 }
7752     { A3 } { 0122 }
7753     { A4 } { 012A }
7754     { A5 } { 0128 }
7755     { A6 } { 0136 }
7756     { A8 } { 013B }
7757     { A9 } { 0110 }
7758     { AA } { 0160 }
7759     { AB } { 0166 }
7760     { AC } { 017D }
7761     { AE } { 016A }
7762     { AF } { 014A }
7763     { B1 } { 0105 }
7764     { B2 } { 0113 }
7765     { B3 } { 0123 }
7766     { B4 } { 012B }
7767     { B5 } { 0129 }
7768     { B6 } { 0137 }
7769     { B8 } { 013C }
7770     { B9 } { 0111 }
7771     { BA } { 0161 }
7772     { BB } { 0167 }
7773     { BC } { 017E }
7774     { BD } { 2015 }
7775     { BE } { 016B }
7776     { BF } { 014B }
7777     { C0 } { 0100 }
7778     { C7 } { 012E }
7779     { C8 } { 010C }

```

```

7780     { CA } { 0118 }
7781     { CC } { 0116 }
7782     { D1 } { 0145 }
7783     { D2 } { 014C }
7784     { D7 } { 0168 }
7785     { D9 } { 0172 }
7786     { E0 } { 0101 }
7787     { E7 } { 012F }
7788     { E8 } { 010D }
7789     { EA } { 0119 }
7790     { EC } { 0117 }
7791     { F1 } { 0146 }
7792     { F2 } { 014D }
7793     { F7 } { 0169 }
7794     { F9 } { 0173 }
7795     { FF } { 0138 }
7796 }
7797 {
7798 }
7799 </iso885910>
7800 <iso885911>
7801 \str_declare_eight_bit_encoding:nnn { iso885911 }
7802 {
7803     { A1 } { OE01 }
7804     { A2 } { OE02 }
7805     { A3 } { OE03 }
7806     { A4 } { OE04 }
7807     { A5 } { OE05 }
7808     { A6 } { OE06 }
7809     { A7 } { OE07 }
7810     { A8 } { OE08 }
7811     { A9 } { OE09 }
7812     { AA } { OE0A }
7813     { AB } { OE0B }
7814     { AC } { OE0C }
7815     { AD } { OE0D }
7816     { AE } { OE0E }
7817     { AF } { OE0F }
7818     { B0 } { OE10 }
7819     { B1 } { OE11 }
7820     { B2 } { OE12 }
7821     { B3 } { OE13 }
7822     { B4 } { OE14 }
7823     { B5 } { OE15 }
7824     { B6 } { OE16 }
7825     { B7 } { OE17 }
7826     { B8 } { OE18 }
7827     { B9 } { OE19 }
7828     { BA } { OE1A }
7829     { BB } { OE1B }
7830     { BC } { OE1C }
7831     { BD } { OE1D }
7832     { BE } { OE1E }
7833     { BF } { OE1F }

```

7834	{ C0 }	{ 0E20 }
7835	{ C1 }	{ 0E21 }
7836	{ C2 }	{ 0E22 }
7837	{ C3 }	{ 0E23 }
7838	{ C4 }	{ 0E24 }
7839	{ C5 }	{ 0E25 }
7840	{ C6 }	{ 0E26 }
7841	{ C7 }	{ 0E27 }
7842	{ C8 }	{ 0E28 }
7843	{ C9 }	{ 0E29 }
7844	{ CA }	{ 0E2A }
7845	{ CB }	{ 0E2B }
7846	{ CC }	{ 0E2C }
7847	{ CD }	{ 0E2D }
7848	{ CE }	{ 0E2E }
7849	{ CF }	{ 0E2F }
7850	{ D0 }	{ 0E30 }
7851	{ D1 }	{ 0E31 }
7852	{ D2 }	{ 0E32 }
7853	{ D3 }	{ 0E33 }
7854	{ D4 }	{ 0E34 }
7855	{ D5 }	{ 0E35 }
7856	{ D6 }	{ 0E36 }
7857	{ D7 }	{ 0E37 }
7858	{ D8 }	{ 0E38 }
7859	{ D9 }	{ 0E39 }
7860	{ DA }	{ 0E3A }
7861	{ DF }	{ 0E3F }
7862	{ E0 }	{ 0E40 }
7863	{ E1 }	{ 0E41 }
7864	{ E2 }	{ 0E42 }
7865	{ E3 }	{ 0E43 }
7866	{ E4 }	{ 0E44 }
7867	{ E5 }	{ 0E45 }
7868	{ E6 }	{ 0E46 }
7869	{ E7 }	{ 0E47 }
7870	{ E8 }	{ 0E48 }
7871	{ E9 }	{ 0E49 }
7872	{ EA }	{ 0E4A }
7873	{ EB }	{ 0E4B }
7874	{ EC }	{ 0E4C }
7875	{ ED }	{ 0E4D }
7876	{ EE }	{ 0E4E }
7877	{ EF }	{ 0E4F }
7878	{ F0 }	{ 0E50 }
7879	{ F1 }	{ 0E51 }
7880	{ F2 }	{ 0E52 }
7881	{ F3 }	{ 0E53 }
7882	{ F4 }	{ 0E54 }
7883	{ F5 }	{ 0E55 }
7884	{ F6 }	{ 0E56 }
7885	{ F7 }	{ 0E57 }
7886	{ F8 }	{ 0E58 }
7887	{ F9 }	{ 0E59 }

```

7888     { FA } { OE5A }
7889     { FB } { OE5B }
7890 }
7891 {
7892     { DB }
7893     { DC }
7894     { DD }
7895     { DE }
7896 }
7897 </iso885911>
7898 <*iso885913>
7899 \str_declare_eight_bit_encoding:nmn { iso885913 }
7900 {
7901     { A1 } { 201D }
7902     { A5 } { 201E }
7903     { A8 } { 00D8 }
7904     { AA } { 0156 }
7905     { AF } { 00C6 }
7906     { B4 } { 201C }
7907     { B8 } { 00F8 }
7908     { BA } { 0157 }
7909     { BF } { 00E6 }
7910     { C0 } { 0104 }
7911     { C1 } { 012E }
7912     { C2 } { 0100 }
7913     { C3 } { 0106 }
7914     { C6 } { 0118 }
7915     { C7 } { 0112 }
7916     { C8 } { 010C }
7917     { CA } { 0179 }
7918     { CB } { 0116 }
7919     { CC } { 0122 }
7920     { CD } { 0136 }
7921     { CE } { 012A }
7922     { CF } { 013B }
7923     { D0 } { 0160 }
7924     { D1 } { 0143 }
7925     { D2 } { 0145 }
7926     { D4 } { 014C }
7927     { D8 } { 0172 }
7928     { D9 } { 0141 }
7929     { DA } { 015A }
7930     { DB } { 016A }
7931     { DD } { 017B }
7932     { DE } { 017D }
7933     { E0 } { 0105 }
7934     { E1 } { 012F }
7935     { E2 } { 0101 }
7936     { E3 } { 0107 }
7937     { E6 } { 0119 }
7938     { E7 } { 0113 }
7939     { E8 } { 010D }
7940     { EA } { 017A }
7941     { EB } { 0117 }

```

```

7942     { EC } { 0123 }
7943     { ED } { 0137 }
7944     { EE } { 012B }
7945     { EF } { 013C }
7946     { F0 } { 0161 }
7947     { F1 } { 0144 }
7948     { F2 } { 0146 }
7949     { F4 } { 014D }
7950     { F8 } { 0173 }
7951     { F9 } { 0142 }
7952     { FA } { 015B }
7953     { FB } { 016B }
7954     { FD } { 017C }
7955     { FE } { 017E }
7956     { FF } { 2019 }
7957 }
7958 {
7959 }
7960 </iso885913>
7961 <*iso885914>
7962 \str_declare_eight_bit_encoding:mn { iso885914 }
7963 {
7964     { A1 } { 1E02 }
7965     { A2 } { 1E03 }
7966     { A4 } { 010A }
7967     { A5 } { 010B }
7968     { A6 } { 1E0A }
7969     { A8 } { 1E80 }
7970     { AA } { 1E82 }
7971     { AB } { 1E0B }
7972     { AC } { 1EF2 }
7973     { AF } { 0178 }
7974     { B0 } { 1E1E }
7975     { B1 } { 1E1F }
7976     { B2 } { 0120 }
7977     { B3 } { 0121 }
7978     { B4 } { 1E40 }
7979     { B5 } { 1E41 }
7980     { B7 } { 1E56 }
7981     { B8 } { 1E81 }
7982     { B9 } { 1E57 }
7983     { BA } { 1E83 }
7984     { BB } { 1E60 }
7985     { BC } { 1EF3 }
7986     { BD } { 1E84 }
7987     { BE } { 1E85 }
7988     { BF } { 1E61 }
7989     { D0 } { 0174 }
7990     { D7 } { 1E6A }
7991     { DE } { 0176 }
7992     { F0 } { 0175 }
7993     { F7 } { 1E6B }
7994     { FE } { 0177 }
7995 }

```

```

7996     {
7997     }
7998 </iso885914>
7999 <*iso885915>
8000 \str_declare_eight_bit_encoding:nnn { iso885915 }
8001     {
8002         { A4 } { 20AC }
8003         { A6 } { 0160 }
8004         { A8 } { 0161 }
8005         { B4 } { 017D }
8006         { B8 } { 017E }
8007         { BC } { 0152 }
8008         { BD } { 0153 }
8009         { BE } { 0178 }
8010     }
8011     {
8012     }
8013 </iso885915>
8014 <*iso885916>
8015 \str_declare_eight_bit_encoding:nnn { iso885916 }
8016     {
8017         { A1 } { 0104 }
8018         { A2 } { 0105 }
8019         { A3 } { 0141 }
8020         { A4 } { 20AC }
8021         { A5 } { 201E }
8022         { A6 } { 0160 }
8023         { A8 } { 0161 }
8024         { AA } { 0218 }
8025         { AC } { 0179 }
8026         { AE } { 017A }
8027         { AF } { 017B }
8028         { B2 } { 010C }
8029         { B3 } { 0142 }
8030         { B4 } { 017D }
8031         { B5 } { 201D }
8032         { B8 } { 017E }
8033         { B9 } { 010D }
8034         { BA } { 0219 }
8035         { BC } { 0152 }
8036         { BD } { 0153 }
8037         { BE } { 0178 }
8038         { BF } { 017C }
8039         { C3 } { 0102 }
8040         { C5 } { 0106 }
8041         { D0 } { 0110 }
8042         { D1 } { 0143 }
8043         { D5 } { 0150 }
8044         { D7 } { 015A }
8045         { D8 } { 0170 }
8046         { DD } { 0118 }
8047         { DE } { 021A }
8048         { E3 } { 0103 }

```

```

8049      { E5 } { 0107 }
8050      { F0 } { 0111 }
8051      { F1 } { 0144 }
8052      { F5 } { 0151 }
8053      { F7 } { 015B }
8054      { F8 } { 0171 }
8055      { FD } { 0119 }
8056      { FE } { 021B }
8057    }
8058    {
8059    }
8060  </iso885916>

```

11 l3seq implementation

The following test files are used for this code: *m3seq002*, *m3seq003*.

```

8061 <*initex | package>
8062 <@@=seq>

```

A sequence is a control sequence whose top-level expansion is of the form “\s__seq __seq_item:n {<item₁>} ... __seq_item:n {<item_n>}”, with a leading scan mark followed by *n* items of the same form. An earlier implementation used the structure “\seq_elt:w <item₁> \seq_elt_end: ... \seq_elt:w <item_n> \seq_elt_end:”. This allowed rapid searching using a delimited function, but was not suitable for items containing {, } and # tokens, and also lead to the loss of surrounding braces around items

```

\__seq_item:n ★ \__seq_item:n {<item>}

```

The internal token used to begin each sequence entry. If expanded outside of a mapping or manipulation function, an error is raised. The definition should always be set globally.

```

\__seq_push_item_def:n \__seq_push_item_def:n {<code>}
\__seq_push_item_def:x

```

Saves the definition of __seq_item:n and redefines it to accept one parameter and expand to <code>. This function should always be balanced by use of __seq_pop_item_def:.

```

\__seq_pop_item_def: \__seq_pop_item_def:

```

Restores the definition of __seq_item:n most recently saved by __seq_push_item_def:n. This function should always be used in a balanced pair with __seq_push_item_def:n.

```

\s__seq This private scan mark.
8063 \scan_new:N \s__seq
(End definition for \s__seq.)

```

```

\s__seq_mark Private scan marks.
\s__seq_stop 8064 \scan_new:N \s__seq_mark
8065 \scan_new:N \s__seq_stop

```

(End definition for \s__seq_mark and \s__seq_stop.)

`__seq_item:n` The delimiter is always defined, but when used incorrectly simply removes its argument and hits an undefined control sequence to raise an error.

```

8066 \cs_new:Npn \__seq_item:n
8067 {
8068     \__kernel_msg_expandable_error:nn { kernel } { misused-sequence }
8069     \use_none:n
8070 }

```

(End definition for `__seq_item:n`.)

`\l__seq_internal_a_tl` Scratch space for various internal uses.

```

\l__seq_internal_b_tl
8071 \tl_new:N \l__seq_internal_a_tl
8072 \tl_new:N \l__seq_internal_b_tl

```

(End definition for `\l__seq_internal_a_tl` and `\l__seq_internal_b_tl`.)

`__seq_tmp:w` Scratch function for internal use.

```

8073 \cs_new_eq:NN \__seq_tmp:w ?

```

(End definition for `__seq_tmp:w`.)

`\c_empty_seq` A sequence with no item, following the structure mentioned above.

```

8074 \tl_const:Nn \c_empty_seq { \s__seq }

```

(End definition for `\c_empty_seq`. This variable is documented on page 85.)

11.1 Allocation and initialisation

`\seq_new:N` Sequences are initialized to `\c_empty_seq`.

```

\seq_new:c
8075 \cs_new_protected:Npn \seq_new:N #1
8076 {
8077     \__kernel_chk_if_free_cs:N #1
8078     \cs_gset_eq:NN #1 \c_empty_seq
8079 }
8080 \cs_generate_variant:Nn \seq_new:N { c }

```

(End definition for `\seq_new:N`. This function is documented on page 75.)

`\seq_clear:N` Clearing a sequence is similar to setting it equal to the empty one.

```

\seq_clear:c
8081 \cs_new_protected:Npn \seq_clear:N #1
\seq_gclear:N
8082 { \seq_set_eq:NN #1 \c_empty_seq }
\seq_gclear:c
8083 \cs_generate_variant:Nn \seq_clear:N { c }
8084 \cs_new_protected:Npn \seq_gclear:N #1
8085 { \seq_gset_eq:NN #1 \c_empty_seq }
8086 \cs_generate_variant:Nn \seq_gclear:N { c }

```

(End definition for `\seq_clear:N` and `\seq_gclear:N`. These functions are documented on page 75.)

`\seq_clear_new:N` Once again we copy code from the token list functions.

```

\seq_clear_new:c
8087 \cs_new_protected:Npn \seq_clear_new:N #1
\seq_gclear_new:N
8088 { \seq_if_exist:NTF #1 { \seq_clear:N #1 } { \seq_new:N #1 } }
\seq_gclear_new:c
8089 \cs_generate_variant:Nn \seq_clear_new:N { c }
8090 \cs_new_protected:Npn \seq_gclear_new:N #1
8091 { \seq_if_exist:NTF #1 { \seq_gclear:N #1 } { \seq_new:N #1 } }
8092 \cs_generate_variant:Nn \seq_gclear_new:N { c }

```


(End definition for `\seq_clear_new:N` and `\seq_gclear_new:N`. These functions are documented on page 75.)

`\seq_set_eq:NN` Copying a sequence is the same as copying the underlying token list.

<code>\seq_set_eq:cN</code>	8093	<code>\cs_new_eq:NN \seq_set_eq:NN \tl_set_eq:NN</code>
<code>\seq_set_eq:Nc</code>	8094	<code>\cs_new_eq:NN \seq_set_eq:Nc \tl_set_eq:Nc</code>
<code>\seq_set_eq:cc</code>	8095	<code>\cs_new_eq:NN \seq_set_eq:cN \tl_set_eq:cN</code>
<code>\seq_gset_eq:NN</code>	8096	<code>\cs_new_eq:NN \seq_gset_eq:NN \tl_gset_eq:NN</code>
<code>\seq_gset_eq:cN</code>	8097	<code>\cs_new_eq:NN \seq_gset_eq:Nc \tl_gset_eq:Nc</code>
<code>\seq_gset_eq:Nc</code>	8098	<code>\cs_new_eq:NN \seq_gset_eq:cN \tl_gset_eq:cN</code>
<code>\seq_gset_eq:cc</code>	8099	<code>\cs_new_eq:NN \seq_gset_eq:cc \tl_gset_eq:cc</code>

(End definition for `\seq_set_eq:NN` and `\seq_gset_eq:NN`. These functions are documented on page 75.)

`\seq_set_from_clist:NN` Setting a sequence from a comma-separated list is done using a simple mapping.

<code>\seq_set_from_clist:cN</code>	8101	<code>\cs_new_protected:Npn \seq_set_from_clist:NN #1#2</code>
<code>\seq_set_from_clist:Nc</code>	8102	{
<code>\seq_set_from_clist:cc</code>	8103	<code>\tl_set:Nx #1</code>
<code>\seq_set_from_clist:Nn</code>	8104	{ <code>\s__seq \clist_map_function:NN #2 __seq_wrap_item:n</code> }
<code>\seq_set_from_clist:cn</code>	8105	}
<code>\seq_gset_from_clist:NN</code>	8106	<code>\cs_new_protected:Npn \seq_gset_from_clist:Nn #1#2</code>
<code>\seq_gset_from_clist:cN</code>	8107	{
<code>\seq_gset_from_clist:Nc</code>	8108	<code>\tl_set:Nx #1</code>
<code>\seq_gset_from_clist:Nc</code>	8109	{ <code>\s__seq \clist_map_function:nN {#2} __seq_wrap_item:n</code> }
<code>\seq_gset_from_clist:cc</code>	8110	}
<code>\seq_gset_from_clist:Nn</code>	8111	<code>\cs_new_protected:Npn \seq_gset_from_clist:NN #1#2</code>
<code>\seq_gset_from_clist:cn</code>	8112	{
	8113	<code>\tl_gset:Nx #1</code>
	8114	{ <code>\s__seq \clist_map_function:NN #2 __seq_wrap_item:n</code> }
	8115	}
	8116	<code>\cs_new_protected:Npn \seq_gset_from_clist:Nn #1#2</code>
	8117	{
	8118	<code>\tl_gset:Nx #1</code>
	8119	{ <code>\s__seq \clist_map_function:nN {#2} __seq_wrap_item:n</code> }
	8120	}
	8121	<code>\cs_generate_variant:Nn \seq_set_from_clist:NN { Nc }</code>
	8122	<code>\cs_generate_variant:Nn \seq_set_from_clist:NN { c , cc }</code>
	8123	<code>\cs_generate_variant:Nn \seq_set_from_clist:Nn { c }</code>
	8124	<code>\cs_generate_variant:Nn \seq_gset_from_clist:NN { Nc }</code>
	8125	<code>\cs_generate_variant:Nn \seq_gset_from_clist:NN { c , cc }</code>
	8126	<code>\cs_generate_variant:Nn \seq_gset_from_clist:Nn { c }</code>

(End definition for `\seq_set_from_clist:NN` and others. These functions are documented on page 75.)

`\seq_const_from_clist:Nn` Almost identical to `\seq_set_from_clist:Nn`.

<code>\seq_const_from_clist:cn</code>	8127	<code>\cs_new_protected:Npn \seq_const_from_clist:Nn #1#2</code>
	8128	{
	8129	<code>\tl_const:Nx #1</code>
	8130	{ <code>\s__seq \clist_map_function:nN {#2} __seq_wrap_item:n</code> }
	8131	}
	8132	<code>\cs_generate_variant:Nn \seq_const_from_clist:Nn { c }</code>

(End definition for `\seq_const_from_clist:Nn`. This function is documented on page 76.)

`\seq_set_split:Nnn` When the separator is empty, everything is very simple, just map `__seq_wrap_item:n`
`\seq_set_split:NnV` through the items of the last argument. For non-trivial separators, the goal is to split
`\seq_gset_split:Nnn` a given token list at the marker, strip spaces from each item, and remove one set of
`\seq_gset_split:NnV` outer braces if after removing leading and trailing spaces the item is enclosed within
`__seq_set_split:NNnn` braces. After `\tl_replace_all:Nnn`, the token list `\l__seq_internal_a_tl` is a repe-
`__seq_set_split_auxi:w` tition of the pattern `__seq_set_split_auxi:w \prg_do_nothing: <item with spaces>`
`__seq_set_split_auxii:w` `__seq_set_split_end:.` Then, x-expansion causes `__seq_set_split_auxi:w` to trim
`__seq_set_split_end:` spaces, and leaves its result as `__seq_set_split_auxii:w <trimmed item> __seq-`
`__seq_set_split_end:` `set_split_end:.` This is then converted to the `l3seq` internal structure by another x-
expansion. In the first step, we insert `\prg_do_nothing:` to avoid losing braces too early:
that would cause space trimming to act within those lost braces. The second step is solely
there to strip braces which are outermost after space trimming.

```

8133 \cs_new_protected:Npn \seq_set_split:Nnn
8134 { \__seq_set_split:NNnn \tl_set:Nx }
8135 \cs_new_protected:Npn \seq_gset_split:Nnn
8136 { \__seq_set_split:NNnn \tl_gset:Nx }
8137 \cs_new_protected:Npn \__seq_set_split:NNnn #1#2#3#4
8138 {
8139   \tl_if_empty:nTF {#3}
8140   {
8141     \tl_set:Nn \l__seq_internal_a_tl
8142     { \tl_map_function:nN {#4} \__seq_wrap_item:n }
8143   }
8144   {
8145     \tl_set:Nn \l__seq_internal_a_tl
8146     {
8147       \__seq_set_split_auxi:w \prg_do_nothing:
8148       #4
8149       \__seq_set_split_end:
8150     }
8151     \tl_replace_all:Nnn \l__seq_internal_a_tl { #3 }
8152     {
8153       \__seq_set_split_end:
8154       \__seq_set_split_auxi:w \prg_do_nothing:
8155     }
8156     \tl_set:Nx \l__seq_internal_a_tl { \l__seq_internal_a_tl }
8157   }
8158   #1 #2 { \s__seq \l__seq_internal_a_tl }
8159 }
8160 \cs_new:Npn \__seq_set_split_auxi:w #1 \__seq_set_split_end:
8161 {
8162   \exp_not:N \__seq_set_split_auxii:w
8163   \exp_args:No \tl_trim_spaces:n {#1}
8164   \exp_not:N \__seq_set_split_end:
8165 }
8166 \cs_new:Npn \__seq_set_split_auxii:w #1 \__seq_set_split_end:
8167 { \__seq_wrap_item:n {#1} }
8168 \cs_generate_variant:Nn \seq_set_split:Nnn { NnV }
8169 \cs_generate_variant:Nn \seq_gset_split:Nnn { NnV }

```

(End definition for `\seq_set_split:Nnn` and others. These functions are documented on page 76.)

`\seq_concat:NNN` When concatenating sequences, one must remove the leading `\s__seq` of the second
`\seq_concat:ccc`
`\seq_gconcat:NNN`
`\seq_gconcat:ccc`

sequence. The result starts with `\s__seq` (of the first sequence), which stops `f`-expansion.

```
8170 \cs_new_protected:Npn \seq_concat:NNN #1#2#3
8171 { \tl_set:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
8172 \cs_new_protected:Npn \seq_gconcat:NNN #1#2#3
8173 { \tl_gset:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
8174 \cs_generate_variant:Nn \seq_concat:NNN { ccc }
8175 \cs_generate_variant:Nn \seq_gconcat:NNN { ccc }
```

(End definition for `\seq_concat:NNN` and `\seq_gconcat:NNN`. These functions are documented on page 76.)

```
\seq_if_exist_p:N Copies of the cs functions defined in l3basics.
\seq_if_exist_p:c
\seq_if_exist:NTF
\seq_if_exist:cTF
\seq_if_exist:cTF
8176 \prg_new_eq_conditional:NNn \seq_if_exist:N \cs_if_exist:N
8177 { TF , T , F , p }
8178 \prg_new_eq_conditional:NNn \seq_if_exist:c \cs_if_exist:c
8179 { TF , T , F , p }
```

(End definition for `\seq_if_exist:NTF`. This function is documented on page 76.)

11.2 Appending data to either end

```
\seq_put_left:Nn When adding to the left of a sequence, remove \s__seq. This is done by \__seq_put_
\seq_put_left:NV left_aux:w, which also stops f-expansion.
\seq_put_left:Nv
\seq_put_left:No
\seq_put_left:Nx
\seq_put_left:cn
\seq_put_left:cV
\seq_put_left:cv
\seq_put_left:co
\seq_put_left:cx
\seq_gput_left:Nn
\seq_gput_left:NV
\seq_gput_left:Nv
\seq_gput_left:No
\seq_gput_left:Nx
\seq_gput_left:cn
\seq_gput_left:cV
\seq_gput_left:cv
\seq_gput_left:co
\seq_gput_left:cx
\__seq_put_left_aux:w
8180 \cs_new_protected:Npn \seq_put_left:Nn #1#2
8181 {
8182   \tl_set:Nx #1
8183   {
8184     \exp_not:n { \s__seq \__seq_item:n {#2} }
8185     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
8186   }
8187 }
8188 \cs_new_protected:Npn \seq_gput_left:Nn #1#2
8189 {
8190   \tl_gset:Nx #1
8191   {
8192     \exp_not:n { \s__seq \__seq_item:n {#2} }
8193     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
8194   }
8195 }
8196 \cs_new:Npn \__seq_put_left_aux:w \s__seq { \exp_stop_f: }
8197 \cs_generate_variant:Nn \seq_put_left:Nn { NV , Nv , No , Nx }
8198 \cs_generate_variant:Nn \seq_put_left:Nn { c , cV , cv , co , cx }
8199 \cs_generate_variant:Nn \seq_gput_left:Nn { NV , Nv , No , Nx }
8200 \cs_generate_variant:Nn \seq_gput_left:Nn { c , cV , cv , co , cx }
```

(End definition for `\seq_put_left:Nn`, `\seq_gput_left:Nn`, and `__seq_put_left_aux:w`. These functions are documented on page 76.)

```
\seq_put_right:Nn Since there is no trailing marker, adding an item to the right of a sequence simply means
\seq_put_right:NV wrapping it in \__seq_item:n.
\seq_put_right:Nv
\seq_put_right:No
\seq_put_right:Nx
\seq_put_right:cn
\seq_put_right:cV
\seq_put_right:cv
\seq_put_right:co
\seq_put_right:cx
\seq_gput_right:Nn
\seq_gput_right:NV
\seq_gput_right:Nv
\seq_gput_right:No
\seq_gput_right:Nx
\seq_gput_right:cn
```

```

8205 \cs_generate_variant:Nn \seq_gput_right:Nn { NV , Nv , No , Nx }
8206 \cs_generate_variant:Nn \seq_gput_right:Nn { c , cV , cv , co , cx }
8207 \cs_generate_variant:Nn \seq_put_right:Nn { NV , Nv , No , Nx }
8208 \cs_generate_variant:Nn \seq_put_right:Nn { c , cV , cv , co , cx }

```

(End definition for `\seq_put_right:Nn` and `\seq_gput_right:Nn`. These functions are documented on page 76.)

11.3 Modifying sequences

`__seq_wrap_item:n` This function converts its argument to a proper sequence item in an x-expansion context.

```

8209 \cs_new:Npn \__seq_wrap_item:n #1 { \exp_not:n { \__seq_item:n {#1} } }

```

(End definition for `__seq_wrap_item:n`.)

`\l__seq_remove_seq` An internal sequence for the removal routines.

```

8210 \seq_new:N \l__seq_remove_seq

```

(End definition for `\l__seq_remove_seq`.)

`\seq_remove_duplicates:N` Removing duplicates means making a new list then copying it.

`\seq_remove_duplicates:c`

`\seq_gremove_duplicates:N`

`\seq_gremove_duplicates:c`

`__seq_remove_duplicates:NN`

```

8211 \cs_new_protected:Npn \seq_remove_duplicates:N
8212 { \__seq_remove_duplicates:NN \seq_set_eq:NN }
8213 \cs_new_protected:Npn \seq_gremove_duplicates:N
8214 { \__seq_remove_duplicates:NN \seq_gset_eq:NN }
8215 \cs_new_protected:Npn \__seq_remove_duplicates:NN #1#2
8216 {
8217   \seq_clear:N \l__seq_remove_seq
8218   \seq_map_inline:Nn #2
8219   {
8220     \seq_if_in:NnF \l__seq_remove_seq {##1}
8221     { \seq_put_right:Nn \l__seq_remove_seq {##1} }
8222   }
8223   #1 #2 \l__seq_remove_seq
8224 }
8225 \cs_generate_variant:Nn \seq_remove_duplicates:N { c }
8226 \cs_generate_variant:Nn \seq_gremove_duplicates:N { c }

```

(End definition for `\seq_remove_duplicates:N`, `\seq_gremove_duplicates:N`, and `__seq_remove_duplicates:NN`. These functions are documented on page 79.)

`\seq_remove_all:Nn` The idea of the code here is to avoid a relatively expensive addition of items one at a time

`\seq_remove_all:cn` to an intermediate sequence. The approach taken is therefore similar to that in `__seq_`

`\seq_gremove_all:Nn` `pop_right:NNN`, using a “flexible” x-type expansion to do most of the work. As `\tl_`

`\seq_gremove_all:cn` `if_eq:nnT` is not expandable, a two-part strategy is needed. First, the x-type expansion

`__seq_remove_all_aux:NNn` uses `\str_if_eq:nnT` to find potential matches. If one is found, the expansion is halted

and the necessary set up takes place to use the `\tl_if_eq:NNT` test. The x-type is started

again, including all of the items copied already. This happens repeatedly until the entire

sequence has been scanned. The code is set up to avoid needing and intermediate scratch

list: the lead-off x-type expansion (`#1 #2 {#2}`) ensures that nothing is lost.

```

8227 \cs_new_protected:Npn \seq_remove_all:Nn
8228 { \__seq_remove_all_aux:NNn \tl_set:Nx }
8229 \cs_new_protected:Npn \seq_gremove_all:Nn
8230 { \__seq_remove_all_aux:NNn \tl_gset:Nx }

```

```

8231 \cs_new_protected:Npn \__seq_remove_all_aux:NNn #1#2#3
8232 {
8233   \__seq_push_item_def:n
8234   {
8235     \str_if_eq:nnT {##1} {#3}
8236     {
8237       \if_false: { \fi: }
8238       \tl_set:Nn \l__seq_internal_b_tl {##1}
8239       #1 #2
8240       { \if_false: } \fi:
8241       \exp_not:o {#2}
8242       \tl_if_eq:NNT \l__seq_internal_a_tl \l__seq_internal_b_tl
8243       { \use_none:nn }
8244     }
8245     \__seq_wrap_item:n {##1}
8246   }
8247   \tl_set:Nn \l__seq_internal_a_tl {#3}
8248   #1 #2 {#2}
8249   \__seq_pop_item_def:
8250 }
8251 \cs_generate_variant:Nn \seq_remove_all:Nn { c }
8252 \cs_generate_variant:Nn \seq_gremove_all:Nn { c }

```

(End definition for `\seq_remove_all:Nn`, `\seq_gremove_all:Nn`, and `__seq_remove_all_aux:NNn`. These functions are documented on page 79.)

<pre> \seq_reverse:N \seq_reverse:c \seq_greverse:N \seq_greverse:c __seq_reverse:NN __seq_reverse_item:nwn </pre>	<pre> Previously, \seq_reverse:N was coded by collecting the items in reverse order after an \exp_stop_f: marker. \cs_new_protected:Npn \seq_reverse:N #1 { \cs_set_eq:NN \@@_item:n \@@_reverse_item:nw \tl_set:Nf #2 { #2 \exp_stop_f: } } \cs_new:Npn \@@_reverse_item:nw #1 #2 \exp_stop_f: { #2 \exp_stop_f: \@@_item:n {#1} } </pre>
--	---

At first, this seems optimal, since we can forget about each item as soon as it is placed after `\exp_stop_f:`. Unfortunately, \TeX 's usual tail recursion does not take place in this case: since the following `__seq_reverse_item:nw` only reads tokens until `\exp_stop_f:`, and never reads the `\@@_item:n {#1}` left by the previous call, \TeX cannot remove that previous call from the stack, and in particular must retain the various macro parameters in memory, until the end of the replacement text is reached. The stack is thus only flushed after all the `__seq_reverse_item:nw` are expanded. Keeping track of the arguments of all those calls uses up a memory quadratic in the length of the sequence. \TeX can then not cope with more than a few thousand items.

Instead, we collect the items in the argument of `\exp_not:n`. The previous calls are cleanly removed from the stack, and the memory consumption becomes linear.

```

8253 \cs_new_protected:Npn \seq_reverse:N
8254 { \__seq_reverse:NN \tl_set:Nx }

```

```

8255 \cs_new_protected:Npn \seq_greverse:N
8256 { \__seq_reverse:NN \tl_gset:Nx }
8257 \cs_new_protected:Npn \__seq_reverse:NN #1 #2
8258 {
8259   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
8260   \cs_set_eq:NN \__seq_item:n \__seq_reverse_item:nwn
8261   #1 #2 { #2 \exp_not:n { } }
8262   \cs_set_eq:NN \__seq_item:n \__seq_tmp:w
8263 }
8264 \cs_new:Npn \__seq_reverse_item:nwn #1 #2 \exp_not:n #3
8265 {
8266   #2
8267   \exp_not:n { \__seq_item:n {#1} #3 }
8268 }
8269 \cs_generate_variant:Nn \seq_reverse:N { c }
8270 \cs_generate_variant:Nn \seq_greverse:N { c }

```

(End definition for `\seq_reverse:N` and others. These functions are documented on page 79.)

`\seq_sort:Nn` Implemented in `l3sort`.

`\seq_sort:cn`

`\seq_gsort:Nn` (End definition for `\seq_sort:Nn` and `\seq_gsort:Nn`. These functions are documented on page 79.)

`\seq_gsort:cn`

11.4 Sequence conditionals

`\seq_if_empty_p:N` Similar to token lists, we compare with the empty sequence.

`\seq_if_empty_p:c`

`\seq_if_empty:NTF`

`\seq_if_empty:cTF`

```

8271 \prg_new_conditional:Npnn \seq_if_empty:N #1 { p , T , F , TF }
8272 {
8273   \if_meaning:w #1 \c_empty_seq
8274   \prg_return_true:
8275   \else:
8276   \prg_return_false:
8277   \fi:
8278 }
8279 \prg_generate_conditional_variant:Nnn \seq_if_empty:N
8280 { c } { p , T , F , TF }

```

(End definition for `\seq_if_empty:N`. This function is documented on page 80.)

`\seq_shuffle:N` We apply the Fisher–Yates shuffle, storing items in `\toks` registers. We use the primitive

`\seq_shuffle:c` `\tex_uniformdeviate:D` for speed reasons. Its non-uniformity is of order its argument

`\seq_gshuffle:N` divided by 2^{28} , not too bad for small lists. For sequences with more than 13 elements

`\seq_gshuffle:c` there are more possible permutations than possible seeds ($13! > 2^{28}$) so the question

`__seq_shuffle:NN` of uniformity is somewhat moot. The integer variables are declared in `l3int: load-order`

`__seq_shuffle_item:n` issues.

`\g__seq_internal_seq`

```

8281 \cs_if_exist:NTF \tex_uniformdeviate:D
8282 {
8283   \seq_new:N \g__seq_internal_seq
8284   \cs_new_protected:Npn \seq_shuffle:N { \__seq_shuffle:NN \seq_set_eq:NN }
8285   \cs_new_protected:Npn \seq_gshuffle:N { \__seq_shuffle:NN \seq_gset_eq:NN }
8286   \cs_new_protected:Npn \__seq_shuffle:NN #1#2
8287   {
8288     \int_compare:nNnTF { \seq_count:N #2 } > \c_max_register_int
8289     {

```

```

8290         \__kernel_msg_error:nmx { kernel } { shuffle-too-large }
8291         { \token_to_str:N #2 }
8292     }
8293     {
8294         \group_begin:
8295         \int_zero:N \l__seq_internal_a_int
8296         \__seq_push_item_def:
8297         \cs_gset_eq:NN \__seq_item:n \__seq_shuffle_item:n
8298         #2
8299         \__seq_pop_item_def:
8300         \seq_gset_from_inline_x:Nnn \g__seq_internal_seq
8301         { \int_step_function:nN { \l__seq_internal_a_int } }
8302         { \tex_the:D \tex_toks:D ##1 }
8303     \group_end:
8304     #1 #2 \g__seq_internal_seq
8305     \seq_gclear:N \g__seq_internal_seq
8306 }
8307 }
8308 \cs_new_protected:Npn \__seq_shuffle_item:n
8309 {
8310     \int_incr:N \l__seq_internal_a_int
8311     \int_set:Nn \l__seq_internal_b_int
8312     { 1 + \tex_uniformdeviate:D \l__seq_internal_a_int }
8313     \tex_toks:D \l__seq_internal_a_int
8314     = \tex_toks:D \l__seq_internal_b_int
8315     \tex_toks:D \l__seq_internal_b_int
8316 }
8317 }
8318 {
8319     \cs_new_protected:Npn \seq_shuffle:N #1
8320     {
8321         \__kernel_msg_error:nnn { kernel } { fp-no-random }
8322         { \seq_shuffle:N #1 }
8323     }
8324     \cs_new_eq:NN \seq_gshuffle:N \seq_shuffle:N
8325 }
8326 \cs_generate_variant:Nn \seq_shuffle:N { c }
8327 \cs_generate_variant:Nn \seq_gshuffle:N { c }

```

(End definition for `\seq_shuffle:N` and others. These functions are documented on page 80.)

`\seq_if_in:NnTF` The approach here is to define `__seq_item:n` to compare its argument with the test sequence. If the two items are equal, the mapping is terminated and `\group_end: \prg_return_true:` is inserted after skipping over the rest of the recursion. On the other hand, if there is no match then the loop breaks, returning `\prg_return_false:`. Everything is inside a group so that `__seq_item:n` is preserved in nested situations.

```

8328 \prg_new_protected_conditional:Npnn \seq_if_in:Nn #1#2
8329 { T , F , TF }
8330 {
8331     \group_begin:
8332     \tl_set:Nn \l__seq_internal_a_tl {#2}
8333     \cs_set_protected:Npn \__seq_item:n ##1
8334     {
8335         \tl_set:Nn \l__seq_internal_b_tl {##1}

```

```

8336         \if_meaning:w \l__seq_internal_a_tl \l__seq_internal_b_tl
8337         \exp_after:wN \__seq_if_in:
8338         \fi:
8339     }
8340     #1
8341     \group_end:
8342     \prg_return_false:
8343     \prg_break_point:
8344 }
8345 \cs_new:Npn \__seq_if_in:
8346 { \prg_break:n { \group_end: \prg_return_true: } }
8347 \prg_generate_conditional_variant:Nnn \seq_if_in:Nn
8348 { NV , Nv , No , Nx , c , cV , cv , co , cx } { T , F , TF }

```

(End definition for `\seq_if_in:NnTF` and `__seq_if_in:..` This function is documented on page 80.)

11.5 Recovering data from sequences

```

\__seq_pop:NNNN
\__seq_pop_TF:NNNN

```

The two `pop` functions share their emptiness tests. We also use a common emptiness test for all branching `get` and `pop` functions.

```

8349 \cs_new_protected:Npn \__seq_pop:NNNN #1#2#3#4
8350 {
8351     \if_meaning:w #3 \c_empty_seq
8352     \tl_set:Nn #4 { \q_no_value }
8353     \else:
8354         #1#2#3#4
8355     \fi:
8356 }
8357 \cs_new_protected:Npn \__seq_pop_TF:NNNN #1#2#3#4
8358 {
8359     \if_meaning:w #3 \c_empty_seq
8360     % \tl_set:Nn #4 { \q_no_value }
8361     \prg_return_false:
8362     \else:
8363         #1#2#3#4
8364         \prg_return_true:
8365     \fi:
8366 }

```

(End definition for `__seq_pop:NNNN` and `__seq_pop_TF:NNNN`.)

```

\seq_get_left:NN
\seq_get_left:cN
\__seq_get_left:wnw

```

Getting an item from the left of a sequence is pretty easy: just trim off the first item after `__seq_item:n` at the start. We append a `\q_no_value` item to cover the case of an empty sequence

```

8367 \cs_new_protected:Npn \seq_get_left:NN #1#2
8368 {
8369     \tl_set:Nx #2
8370     {
8371         \exp_after:wN \__seq_get_left:wnw
8372         #1 \__seq_item:n { \q_no_value } \s__seq_stop
8373     }
8374 }
8375 \cs_new:Npn \__seq_get_left:wnw #1 \__seq_item:n #2#3 \s__seq_stop
8376 { \exp_not:n {#2} }
8377 \cs_generate_variant:Nn \seq_get_left:NN { c }

```


(End definition for `\seq_get_left:NN` and `__seq_get_left:wnw`. This function is documented on page 77.)

`\seq_pop_left:NN` The approach to popping an item is pretty similar to that to get an item, with the only difference being that the sequence itself has to be redefined. This makes it more sensible to use an auxiliary function for the local and global cases.

`\seq_pop_left:cN`

`\seq_gpop_left:NN`

`\seq_gpop_left:cN`

`__seq_pop_left:NNN`

`__seq_pop_left:wnwNNN`

```

8378 \cs_new_protected:Npn \seq_pop_left:NN
8379   { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_set:Nn }
8380 \cs_new_protected:Npn \seq_gpop_left:NN
8381   { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_gset:Nn }
8382 \cs_new_protected:Npn \__seq_pop_left:NNN #1#2#3
8383   { \exp_after:wN \__seq_pop_left:wnwNNN #2 \s__seq_stop #1#2#3 }
8384 \cs_new_protected:Npn \__seq_pop_left:wnwNNN
8385   #1 \__seq_item:n #2#3 \s__seq_stop #4#5#6
8386   {
8387     #4 #5 { #1 #3 }
8388     \tl_set:Nn #6 {#2}
8389   }
8390 \cs_generate_variant:Nn \seq_pop_left:NN { c }
8391 \cs_generate_variant:Nn \seq_gpop_left:NN { c }

```

(End definition for `\seq_pop_left:NN` and others. These functions are documented on page 77.)

`\seq_get_right:NN` First remove `\s__seq` and prepend `\q_no_value`. The first argument of `__seq_get_right_loop:nw` is the last item found, and the second argument is empty until the end of the loop, where it is code that applies `\exp_not:n` to the last item and ends the loop.

`\seq_get_right:cN`

`__seq_get_right_loop:nw`

`__seq_get_right_end:NnN`

```

8392 \cs_new_protected:Npn \seq_get_right:NN #1#2
8393   {
8394     \tl_set:Nx #2
8395     {
8396       \exp_after:wN \use_i_ii:nnn
8397       \exp_after:wN \__seq_get_right_loop:nw
8398       \exp_after:wN \q_no_value
8399       #1
8400       \__seq_get_right_end:NnN \__seq_item:n
8401     }
8402   }
8403 \cs_new:Npn \__seq_get_right_loop:nw #1#2 \__seq_item:n
8404   {
8405     #2 \use_none:n {#1}
8406     \__seq_get_right_loop:nw
8407   }
8408 \cs_new:Npn \__seq_get_right_end:NnN #1#2#3 { \exp_not:n {#2} }
8409 \cs_generate_variant:Nn \seq_get_right:NN { c }

```

(End definition for `\seq_get_right:NN`, `__seq_get_right_loop:nw`, and `__seq_get_right_end:NnN`. This function is documented on page 77.)

`\seq_pop_right:NN` The approach to popping from the right is a bit more involved, but does use some of the same ideas as getting from the right. What is needed is a “flexible length” way to set a token list variable. This is supplied by the `{\if_false:} \fi: ... \if_false: { \fi: }` construct. Using an x-type expansion and a “non-expanding” definition for `__seq_item:n`, the left-most $n - 1$ entries in a sequence of n items are stored back in the sequence. That needs a loop of unknown length, hence using the

`\seq_pop_right:cN`

`\seq_gpop_right:NN`

`\seq_gpop_right:cN`

`__seq_pop_right:NNN`

`__seq_pop_right_loop:nn`

strange `\if_false:` way of including braces. When the last item of the sequence is reached, the closing brace for the assignment is inserted, and `\tl_set:Nn #3` is inserted in front of the final entry. This therefore does the pop assignment. One more iteration is performed, with an empty argument and `\use_none:nn`, which finally stops the loop.

```

8410 \cs_new_protected:Npn \seq_pop_right:NN
8411 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_set:Nx }
8412 \cs_new_protected:Npn \seq_gpop_right:NN
8413 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_gset:Nx }
8414 \cs_new_protected:Npn \__seq_pop_right:NNN #1#2#3
8415 {
8416   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
8417   \cs_set_eq:NN \__seq_item:n \scan_stop:
8418   #1 #2
8419   { \if_false: } \fi: \s__seq
8420     \exp_after:wN \use_i:nnn
8421     \exp_after:wN \__seq_pop_right_loop:nn
8422     #2
8423     {
8424       \if_false: { \fi: }
8425       \tl_set:Nx #3
8426     }
8427     { } \use_none:nn
8428     \cs_set_eq:NN \__seq_item:n \__seq_tmp:w
8429   }
8430 \cs_new:Npn \__seq_pop_right_loop:nn #1#2
8431 {
8432   #2 { \exp_not:n {#1} }
8433   \__seq_pop_right_loop:nn
8434 }
8435 \cs_generate_variant:Nn \seq_pop_right:NN { c }
8436 \cs_generate_variant:Nn \seq_gpop_right:NN { c }

```

(End definition for `\seq_pop_right:NN` and others. These functions are documented on page 77.)

`\seq_get_left:NNTF` Getting from the left or right with a check on the results. The first argument to `__seq_pop_TF:NNNN` is left unused.

```

\seq_get_left:cNTF
\seq_get_right:NNTF
\seq_get_right:cNTF
8437 \prg_new_protected_conditional:Npnn \seq_get_left:NN #1#2 { T , F , TF }
8438 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_left:NN #1#2 }
8439 \prg_new_protected_conditional:Npnn \seq_get_right:NN #1#2 { T , F , TF }
8440 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_right:NN #1#2 }
8441 \prg_generate_conditional_variant:Nnn \seq_get_left:NN
8442 { c } { T , F , TF }
8443 \prg_generate_conditional_variant:Nnn \seq_get_right:NN
8444 { c } { T , F , TF }

```

(End definition for `\seq_get_left:NNTF` and `\seq_get_right:NNTF`. These functions are documented on page 78.)

`\seq_pop_left:NNTF` More or less the same for popping.

```

\seq_pop_left:cNTF
\seq_gpop_left:NNTF
\seq_gpop_left:cNTF
\seq_pop_right:NNTF
\seq_pop_right:cNTF
\seq_gpop_right:NNTF
\seq_gpop_right:cNTF
8445 \prg_new_protected_conditional:Npnn \seq_pop_left:NN #1#2
8446 { T , F , TF }
8447 { \__seq_pop_TF:NNNN \__seq_pop_left:NNN \tl_set:Nn #1 #2 }
8448 \prg_new_protected_conditional:Npnn \seq_gpop_left:NN #1#2
8449 { T , F , TF }

```

```

8450 { \__seq_pop_TF:NNNN \__seq_pop_left:NNN \tl_gset:Nn #1 #2 }
8451 \prg_new_protected_conditional:Npnn \seq_pop_right:NN #1#2
8452 { T , F , TF }
8453 { \__seq_pop_TF:NNNN \__seq_pop_right:NNN \tl_set:Nx #1 #2 }
8454 \prg_new_protected_conditional:Npnn \seq_gpop_right:NN #1#2
8455 { T , F , TF }
8456 { \__seq_pop_TF:NNNN \__seq_pop_right:NNN \tl_gset:Nx #1 #2 }
8457 \prg_generate_conditional_variant:Nnn \seq_pop_left:NN { c }
8458 { T , F , TF }
8459 \prg_generate_conditional_variant:Nnn \seq_gpop_left:NN { c }
8460 { T , F , TF }
8461 \prg_generate_conditional_variant:Nnn \seq_pop_right:NN { c }
8462 { T , F , TF }
8463 \prg_generate_conditional_variant:Nnn \seq_gpop_right:NN { c }
8464 { T , F , TF }

```

(End definition for `\seq_pop_left:NNTF` and others. These functions are documented on page 78.)

`\seq_item:Nn` The idea here is to find the offset of the item from the left, then use a loop to grab the correct item. If the resulting offset is too large, then the argument delimited by `__seq_item:n` is `\prg_break:` instead of being empty, terminating the loop and returning nothing at all.

```

\__seq_item:wNn
\__seq_item:nN
\__seq_item:nwn
8465 \cs_new:Npn \seq_item:Nn #1
8466 { \exp_after:wN \__seq_item:wNn #1 \s__seq_stop #1 }
8467 \cs_new:Npn \__seq_item:wNn \s__seq #1 \s__seq_stop #2#3
8468 {
8469   \exp_args:Nf \__seq_item:nwn
8470   { \exp_args:Nf \__seq_item:nN { \int_eval:n {#3} } #2 }
8471   #1
8472   \prg_break: \__seq_item:n { }
8473   \prg_break_point:
8474 }
8475 \cs_new:Npn \__seq_item:nN #1#2
8476 {
8477   \int_compare:nNnTF {#1} < 0
8478   { \int_eval:n { \seq_count:N #2 + 1 + #1 } }
8479   {#1}
8480 }
8481 \cs_new:Npn \__seq_item:nwn #1#2 \__seq_item:n #3
8482 {
8483   #2
8484   \int_compare:nNnTF {#1} = 1
8485   { \prg_break:n { \exp_not:n {#3} } }
8486   { \exp_args:Nf \__seq_item:nwn { \int_eval:n { #1 - 1 } } }
8487 }
8488 \cs_generate_variant:Nn \seq_item:Nn { c }

```

(End definition for `\seq_item:Nn` and others. This function is documented on page 77.)

`\seq_rand_item:N` Importantly, `\seq_item:Nn` only evaluates its argument once.

```

\seq_rand_item:c
8489 \cs_new:Npn \seq_rand_item:N #1
8490 {
8491   \seq_if_empty:NF #1
8492   { \seq_item:Nn #1 { \int_rand:nn { 1 } { \seq_count:N #1 } } }

```

```

8493 }
8494 \cs_generate_variant:Nn \seq_rand_item:N { c }

```

(End definition for `\seq_rand_item:N`. This function is documented on page 78.)

11.6 Mapping to sequences

`\seq_map_break:` To break a function, the special token `\prg_break_point:Nn` is used to find the end of the code. Any ending code is then inserted before the return value of `\seq_map_break:n` is inserted.

```

8495 \cs_new:Npn \seq_map_break:
8496 { \prg_map_break:Nn \seq_map_break: { } }
8497 \cs_new:Npn \seq_map_break:n
8498 { \prg_map_break:Nn \seq_map_break: }

```

(End definition for `\seq_map_break:` and `\seq_map_break:n`. These functions are documented on page 81.)

`\seq_map_function:NN` The idea here is to apply the code of #2 to each item in the sequence without altering the definition of `__seq_item:n`. The argument delimited by `__seq_item:n` is almost always empty, except at the end of the loop where it is `\prg_break:`. This allows to break the loop without needing to do a (relatively-expensive) quark test.

```

8499 \cs_new:Npn \seq_map_function:NN #1#2
8500 {
8501   \exp_after:wN \use_i_ii:nnn
8502   \exp_after:wN \__seq_map_function:Nw
8503   \exp_after:wN #2
8504   #1
8505   \prg_break: \__seq_item:n { } \prg_break_point:
8506   \prg_break_point:Nn \seq_map_break: { }
8507 }
8508 \cs_new:Npn \__seq_map_function:Nw #1#2 \__seq_item:n #3
8509 {
8510   #2
8511   #1 {#3}
8512   \__seq_map_function:Nw #1
8513 }
8514 \cs_generate_variant:Nn \seq_map_function:NN { c }

```

(End definition for `\seq_map_function:NN` and `__seq_map_function:Nw`. This function is documented on page 80.)

`__seq_push_item_def:n` The definition of `__seq_item:n` needs to be saved and restored at various points within the mapping and manipulation code. That is handled here: as always, this approach uses global assignments.

```

\__seq_push_item_def:
\__seq_pop_item_def:
8515 \cs_new_protected:Npn \__seq_push_item_def:n
8516 {
8517   \__seq_push_item_def:
8518   \cs_gset:Npn \__seq_item:n ##1
8519 }
8520 \cs_new_protected:Npn \__seq_push_item_def:x
8521 {
8522   \__seq_push_item_def:
8523   \cs_gset:Npx \__seq_item:n ##1

```

```

8524 }
8525 \cs_new_protected:Npn \__seq_push_item_def:
8526 {
8527   \int_gincr:N \g__kernel_prg_map_int
8528   \cs_gset_eq:cN { \__seq_map_ \int_use:N \g__kernel_prg_map_int :w }
8529   \__seq_item:n
8530 }
8531 \cs_new_protected:Npn \__seq_pop_item_def:
8532 {
8533   \cs_gset_eq:Nc \__seq_item:n
8534   { \__seq_map_ \int_use:N \g__kernel_prg_map_int :w }
8535   \int_gdecr:N \g__kernel_prg_map_int
8536 }

```

(End definition for __seq_push_item_def:n, __seq_push_item_def:, and __seq_pop_item_def:.)

\seq_map_inline:Nn The idea here is that __seq_item:n is already “applied” to each item in a sequence,
\seq_map_inline:cn and so an in-line mapping is just a case of redefining __seq_item:n.

```

8537 \cs_new_protected:Npn \seq_map_inline:Nn #1#2
8538 {
8539   \__seq_push_item_def:n {#2}
8540   #1
8541   \prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
8542 }
8543 \cs_generate_variant:Nn \seq_map_inline:Nn { c }

```

(End definition for \seq_map_inline:Nn. This function is documented on page 80.)

\seq_map_tokens:Nn This is based on the function mapping but using the same tricks as described for \prop_
\seq_map_tokens:cn map_tokens:Nn. The idea is to remove the leading \s__seq and apply the tokens such
__seq_map_tokens:nw that they are safe with the break points, hence the \use:n.

```

8544 \cs_new:Npn \seq_map_tokens:Nn #1#2
8545 {
8546   \exp_last_unbraced:Nno
8547   \use_i:nn { \__seq_map_tokens:nw {#2} } #1
8548   \prg_break: \__seq_item:n { } \prg_break_point:
8549   \prg_break_point:Nn \seq_map_break: { }
8550 }
8551 \cs_generate_variant:Nn \seq_map_tokens:Nn { c }
8552 \cs_new:Npn \__seq_map_tokens:nw #1#2 \__seq_item:n #3
8553 {
8554   #2
8555   \use:n {#1} {#3}
8556   \__seq_map_tokens:nw {#1}
8557 }

```

(End definition for \seq_map_tokens:Nn and __seq_map_tokens:nw. This function is documented on page 81.)

\seq_map_variable:NNn This is just a specialised version of the in-line mapping function, using an x-type expansion
\seq_map_variable:Ncn for the code set up so that the number of # tokens required is as expected.

```

8558 \cs_new_protected:Npn \seq_map_variable:NNn #1#2#3
8559 {
8560   \__seq_push_item_def:x

```

```

8561     {
8562         \tl_set:Nn \exp_not:N #2 {##1}
8563         \exp_not:n {#3}
8564     }
8565     #1
8566     \prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
8567 }
8568 \cs_generate_variant:Nn \seq_map_variable:NNn { Nc }
8569 \cs_generate_variant:Nn \seq_map_variable:NNn { c , cc }

```

(End definition for `\seq_map_variable:NNn`. This function is documented on page 81.)

\seq_count:N Since counting the items in a sequence is quite common, we optimize it by grabbing 8 items at a time and correspondingly adding 8 to an integer expression. At the end of the loop, #9 is `__seq_count_end:w` instead of being empty. It removes 8+ and instead places the number of `__seq_item:n` that `__seq_count:w` grabbed before reaching the end of the sequence.

```

8570 \cs_new:Npn \seq_count:N #1
8571 {
8572     \int_eval:n
8573     {
8574         \exp_after:wN \use_i:nn
8575         \exp_after:wN \__seq_count:w
8576         #1
8577         \__seq_count_end:w \__seq_item:n 7
8578         \__seq_count_end:w \__seq_item:n 6
8579         \__seq_count_end:w \__seq_item:n 5
8580         \__seq_count_end:w \__seq_item:n 4
8581         \__seq_count_end:w \__seq_item:n 3
8582         \__seq_count_end:w \__seq_item:n 2
8583         \__seq_count_end:w \__seq_item:n 1
8584         \__seq_count_end:w \__seq_item:n 0
8585         \prg_break_point:
8586     }
8587 }
8588 \cs_new:Npn \__seq_count:w
8589     #1 \__seq_item:n #2 \__seq_item:n #3 \__seq_item:n #4 \__seq_item:n
8590     #5 \__seq_item:n #6 \__seq_item:n #7 \__seq_item:n #8 #9 \__seq_item:n
8591     { #9 8 + \__seq_count:w }
8592 \cs_new:Npn \__seq_count_end:w 8 + \__seq_count:w #1#2 \prg_break_point: {#1}
8593 \cs_generate_variant:Nn \seq_count:N { c }

```

(End definition for `\seq_count:N`, `__seq_count:w`, and `__seq_count_end:w`. This function is documented on page 82.)

11.7 Using sequences

\seq_use:Nnnn See `\clist_use:Nnnn` for a general explanation. The main difference is that we use `__seq_item:n` as a delimiter rather than commas. We also need to add `__seq_item:n` at various places, and `\s__seq`.

\seq_use:cnnn

```

8594 \cs_new:Npn \seq_use:Nnnn #1#2#3#4
8595 {
8596     \seq_if_exist:NTF #1
8597     {

```

__seq_use:NNnNnn

```

8598     \__seq_use_setup:w
8599     \__seq_use:nwwwnwn
8600     \__seq_use:nwnn

```

\seq_use:Nn

```

8601     \seq_use:cn

```

```

8598 \int_case:nnF { \seq_count:N #1 }
8599 {
8600   { 0 } { }
8601   { 1 } { \exp_after:wN \__seq_use:NNnNnn #1 ? { } { } }
8602   { 2 } { \exp_after:wN \__seq_use:NNnNnn #1 {#2} }
8603 }
8604 {
8605   \exp_after:wN \__seq_use_setup:w #1 \__seq_item:n
8606   \s__seq_mark { \__seq_use:nwwwnwn {#3} }
8607   \s__seq_mark { \__seq_use:nwn {#4} }
8608   \s__seq_stop { }
8609 }
8610 }
8611 {
8612   \__kernel_msg_expandable_error:nnn
8613   { kernel } { bad-variable } {#1}
8614 }
8615 }
8616 \cs_generate_variant:Nn \seq_use:Nnnn { c }
8617 \cs_new:Npn \__seq_use:NNnNnn #1#2#3#4#5#6 { \exp_not:n { #3 #6 #5 } }
8618 \cs_new:Npn \__seq_use_setup:w \s__seq { \__seq_use:nwwwnwn { } }
8619 \cs_new:Npn \__seq_use:nwwwnwn
8620   #1 \__seq_item:n #2 \__seq_item:n #3 \__seq_item:n #4#5
8621   \s__seq_mark #6#7 \s__seq_stop #8
8622   {
8623     #6 \__seq_item:n {#3} \__seq_item:n {#4} #5
8624     \s__seq_mark {#6} #7 \s__seq_stop { #8 #1 #2 }
8625   }
8626 \cs_new:Npn \__seq_use:nwn #1 \__seq_item:n #2 #3 \s__seq_stop #4
8627   { \exp_not:n { #4 #1 #2 } }
8628 \cs_new:Npn \seq_use:Nn #1#2
8629   { \seq_use:Nnnn #1 {#2} {#2} {#2} }
8630 \cs_generate_variant:Nn \seq_use:Nn { c }

```

(End definition for `\seq_use:Nnnn` and others. These functions are documented on page 82.)

11.8 Sequence stacks

The same functions as for sequences, but with the correct naming.

\seq_push:Nn Pushing to a sequence is the same as adding on the left.

\seq_push:NV	8631 \cs_new_eq:NN \seq_push:Nn \seq_put_left:Nn
\seq_push:Nv	8632 \cs_new_eq:NN \seq_push:Nv \seq_put_left:Nv
\seq_push:No	8633 \cs_new_eq:NN \seq_push:No \seq_put_left:Nv
\seq_push:Nx	8634 \cs_new_eq:NN \seq_push:No \seq_put_left:No
\seq_push:cn	8635 \cs_new_eq:NN \seq_push:Nx \seq_put_left:Nx
\seq_push:cV	8636 \cs_new_eq:NN \seq_push:cn \seq_put_left:cn
\seq_push:cV	8637 \cs_new_eq:NN \seq_push:cV \seq_put_left:cV
\seq_push:co	8638 \cs_new_eq:NN \seq_push:cv \seq_put_left:cv
\seq_push:cx	8639 \cs_new_eq:NN \seq_push:co \seq_put_left:co
	8640 \cs_new_eq:NN \seq_push:cx \seq_put_left:cx
\seq_gpush:Nn	8641 \cs_new_eq:NN \seq_gpush:Nn \seq_gput_left:Nn
\seq_gpush:NV	8642 \cs_new_eq:NN \seq_gpush:Nv \seq_gput_left:Nv
\seq_gpush:Nv	8643 \cs_new_eq:NN \seq_gpush:Nv \seq_gput_left:Nv
\seq_gpush:No	
\seq_gpush:Nx	
\seq_gpush:cn	
\seq_gpush:cV	
\seq_gpush:cv	
\seq_gpush:co	
\seq_gpush:cx	

```

8644 \cs_new_eq:NN \seq_gpush:No \seq_gput_left:No
8645 \cs_new_eq:NN \seq_gpush:Nx \seq_gput_left:Nx
8646 \cs_new_eq:NN \seq_gpush:cn \seq_gput_left:cn
8647 \cs_new_eq:NN \seq_gpush:cV \seq_gput_left:cV
8648 \cs_new_eq:NN \seq_gpush:cv \seq_gput_left:cv
8649 \cs_new_eq:NN \seq_gpush:co \seq_gput_left:co
8650 \cs_new_eq:NN \seq_gpush:cx \seq_gput_left:cx

```

(End definition for `\seq_push:Nn` and `\seq_gpush:Nn`. These functions are documented on page 84.)

`\seq_get:NN` In most cases, getting items from the stack does not need to specify that this is from the
`\seq_get:cN` left. So alias are provided.

```

\seq_pop:NN      8651 \cs_new_eq:NN \seq_get:NN \seq_get_left:NN
\seq_pop:cN      8652 \cs_new_eq:NN \seq_get:cN \seq_get_left:cN
\seq_gpop:NN     8653 \cs_new_eq:NN \seq_pop:NN \seq_pop_left:NN
\seq_gpop:cN     8654 \cs_new_eq:NN \seq_pop:cN \seq_pop_left:cN
                 8655 \cs_new_eq:NN \seq_gpop:NN \seq_gpop_left:NN
                 8656 \cs_new_eq:NN \seq_gpop:cN \seq_gpop_left:cN

```

(End definition for `\seq_get:NN`, `\seq_pop:NN`, and `\seq_gpop:NN`. These functions are documented on page 83.)

`\seq_get:NNTF` More copies.
`\seq_get:cNTF` 8657 \prg_new_eq_conditional:NNn \seq_get:NN \seq_get_left:NN { T , F , TF }
`\seq_pop:NNTF` 8658 \prg_new_eq_conditional:NNn \seq_get:cN \seq_get_left:cN { T , F , TF }
`\seq_pop:cNTF` 8659 \prg_new_eq_conditional:NNn \seq_pop:NN \seq_pop_left:NN { T , F , TF }
`\seq_gpop:NNTF` 8660 \prg_new_eq_conditional:NNn \seq_pop:cN \seq_pop_left:cN { T , F , TF }
`\seq_gpop:cNTF` 8661 \prg_new_eq_conditional:NNn \seq_gpop:NN \seq_gpop_left:NN { T , F , TF }
8662 \prg_new_eq_conditional:NNn \seq_gpop:cN \seq_gpop_left:cN { T , F , TF }

(End definition for `\seq_get:NNTF`, `\seq_pop:NNTF`, and `\seq_gpop:NNTF`. These functions are documented on page 83.)

11.9 Viewing sequences

`\seq_show:N` Apply the general `\msg_show:nnnnnn`.
`\seq_show:c` 8663 \cs_new_protected:Npn \seq_show:N { __seq_show:NN \msg_show:nnxxxx }
`\seq_log:N` 8664 \cs_generate_variant:Nn \seq_show:N { c }
`\seq_log:c` 8665 \cs_new_protected:Npn \seq_log:N { __seq_show:NN \msg_log:nnxxxx }
`__seq_show:NN` 8666 \cs_generate_variant:Nn \seq_log:N { c }
8667 \cs_new_protected:Npn __seq_show:NN #1#2
8668 {
8669 __kernel_chk_defined:NT #2
8670 {
8671 #1 { LaTeX/kernel } { show-seq }
8672 { \token_to_str:N #2 }
8673 { \seq_map_function:NN #2 \msg_show_item:n }
8674 { } { }
8675 }
8676 }

(End definition for `\seq_show:N`, `\seq_log:N`, and `__seq_show:NN`. These functions are documented on page 86.)

11.10 Scratch sequences

`\l_tmpa_seq` Temporary comma list variables.

```

\l_tmpb_seq      8677 \seq_new:N \l_tmpa_seq
\g_tmpa_seq      8678 \seq_new:N \l_tmpb_seq
\g_tmpb_seq      8679 \seq_new:N \g_tmpa_seq
                  8680 \seq_new:N \g_tmpb_seq

```

(End definition for `\l_tmpa_seq` and others. These variables are documented on page 86.)

```
8681 </initex | package>
```

12 l3int implementation

```
8682 <*initex | package>
```

```
8683 <@@=int>
```

The following test files are used for this code: `m3int001,m3int002,m3int03`.

`\c_max_register_int` Done in l3basics.

(End definition for `\c_max_register_int`. This variable is documented on page 99.)

`__int_to_roman:w` Done in l3basics.

`\if_int_compare:w` (End definition for `__int_to_roman:w` and `\if_int_compare:w`. This function is documented on page 100.)

`\or:` Done in l3basics.

(End definition for `\or:`. This function is documented on page 100.)

`\int_value:w` Here are the remaining primitives for number comparisons and expressions.

```

\__int_eval:w      8684 \cs_new_eq:NN \int_value:w      \tex_number:D
\__int_eval_end:    8685 \cs_new_eq:NN \__int_eval:w      \tex_numexpr:D
\if_int_odd:w       8686 \cs_new_eq:NN \__int_eval_end:    \tex_relax:D
\if_case:w          8687 \cs_new_eq:NN \if_int_odd:w      \tex_ifodd:D
                    8688 \cs_new_eq:NN \if_case:w        \tex_ifcase:D

```

(End definition for `\int_value:w` and others. These functions are documented on page 100.)

`\s__int_mark` Scan marks used throughout the module.

```

\s__int_stop      8689 \scan_new:N \s__int_mark
                  8690 \scan_new:N \s__int_stop

```

(End definition for `\s__int_mark` and `\s__int_stop`.)

`__int_use_none_delimit_by_s_stop:w` Function to gobble until a scan mark.

```
8691 \cs_new:Npn \__int_use_none_delimit_by_s_stop:w #1 \s__int_stop { }
```

(End definition for `__int_use_none_delimit_by_s_stop:w`.)

`\q__int_recursion_tail` Quarks for recursion.

```

\q__int_recursion_stop 8692 \quark_new:N \q__int_recursion_tail
                        8693 \quark_new:N \q__int_recursion_stop

```

(End definition for `\q__int_recursion_tail` and `\q__int_recursion_stop`.)

```

\__int_if_recursion_tail_stop_do:Nn Functions to query quarks.
\__int_if_recursion_tail_stop:N
8694 \__kernel_quark_new_test:N \__int_if_recursion_tail_stop_do:Nn
8695 \__kernel_quark_new_test:N \__int_if_recursion_tail_stop:N

(End definition for \__int_if_recursion_tail_stop_do:Nn and \__int_if_recursion_tail_stop:N.)

```

12.1 Integer expressions

\int_eval:n Wrapper for **__int_eval:w**: can be used in an integer expression or directly in the input stream. When debugging, use parentheses to catch early termination.

```

8696 \cs_new:Npn \int_eval:n #1
8697 { \int_value:w \__int_eval:w #1 \__int_eval_end: }
8698 \cs_new:Npn \int_eval:w { \int_value:w \__int_eval:w }

```

(End definition for **\int_eval:n** and **\int_eval:w**. These functions are documented on page 88.)

\int_sign:n See **\int_abs:n**. Evaluate the expression once (and when debugging is enabled, check that the expression is well-formed), then test the first character to determine the sign. This is wrapped in **\int_value:w ... \exp_stop_f:** to ensure a fixed number of expansions and to avoid dealing with closing the conditionals.

__int_sign:Nw

```

8699 \cs_new:Npn \int_sign:n #1
8700 {
8701   \int_value:w \exp_after:wN \__int_sign:Nw
8702   \int_value:w \__int_eval:w #1 \__int_eval_end: ;
8703   \exp_stop_f:
8704 }
8705 \cs_new:Npn \__int_sign:Nw #1#2 ;
8706 {
8707   \if_meaning:w 0 #1
8708   0
8709   \else:
8710     \if_meaning:w - #1 - \fi: 1
8711   \fi:
8712 }

```

(End definition for **\int_sign:n** and **__int_sign:Nw**. This function is documented on page 89.)

\int_abs:n Functions for min, max, and absolute value with only one evaluation. The absolute value is obtained by removing a leading sign if any. All three functions expand in two steps.

__int_abs:N

\int_max:nn

\int_min:nn

__int_maxmin:wwN

```

8713 \cs_new:Npn \int_abs:n #1
8714 {
8715   \int_value:w \exp_after:wN \__int_abs:N
8716   \int_value:w \__int_eval:w #1 \__int_eval_end:
8717   \exp_stop_f:
8718 }
8719 \cs_new:Npn \__int_abs:N #1
8720 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
8721 \cs_set:Npn \int_max:nn #1#2
8722 {
8723   \int_value:w \exp_after:wN \__int_maxmin:wwN
8724   \int_value:w \__int_eval:w #1 \exp_after:wN ;
8725   \int_value:w \__int_eval:w #2 ;
8726   >
8727   \exp_stop_f:

```

```

8728 }
8729 \cs_set:Npn \int_min:nn #1#2
8730 {
8731   \int_value:w \exp_after:wN \__int_maxmin:wwN
8732   \int_value:w \__int_eval:w #1 \exp_after:wN ;
8733   \int_value:w \__int_eval:w #2 ;
8734   <
8735   \exp_stop_f:
8736 }
8737 \cs_new:Npn \__int_maxmin:wwN #1 ; #2 ; #3
8738 {
8739   \if_int_compare:w #1 #3 #2 ~
8740     #1
8741   \else:
8742     #2
8743   \fi:
8744 }

```

(End definition for `\int_abs:n` and others. These functions are documented on page 89.)

`\int_div_truncate:nn` As `__int_eval:w` rounds the result of a division we also provide a version that truncates the result. We use an auxiliary to make sure numerator and denominator are only evaluated once: this comes in handy when those are more expressions are expensive to evaluate (e.g., `\tl_count:n`). If the numerator `#1#2` is 0, then we divide 0 by the denominator (this ensures that 0/0 is correctly reported as an error). Otherwise, shift the numerator `#1#2` towards 0 by $(| \#3\#4 | - 1)/2$, which we round away from zero. It turns out that this quantity exactly compensates the difference between ε -TeX's rounding and the truncating behaviour that we want. The details are thanks to Heiko Oberdiek: getting things right in all cases is not so easy.

```

8745 \cs_new:Npn \int_div_truncate:nn #1#2
8746 {
8747   \int_value:w \__int_eval:w
8748   \exp_after:wN \__int_div_truncate:NwNw
8749   \int_value:w \__int_eval:w #1 \exp_after:wN ;
8750   \int_value:w \__int_eval:w #2 ;
8751   \__int_eval_end:
8752 }
8753 \cs_new:Npn \__int_div_truncate:NwNw #1#2; #3#4;
8754 {
8755   \if_meaning:w 0 #1
8756     0
8757   \else:
8758     (
8759       #1#2
8760       \if_meaning:w - #1 + \else: - \fi:
8761       ( \if_meaning:w - #3 - \fi: #3#4 - 1 ) / 2
8762     )
8763   \fi:
8764   / #3#4
8765 }

```

For the sake of completeness:

```

8766 \cs_new:Npn \int_div_round:nn #1#2
8767 { \int_value:w \__int_eval:w ( #1 ) / ( #2 ) \__int_eval_end: }

```

Finally there's the modulus operation.

```

8768 \cs_new:Npn \int_mod:nn #1#2
8769 {
8770   \int_value:w \__int_eval:w \exp_after:wN \__int_mod:ww
8771   \int_value:w \__int_eval:w #1 \exp_after:wN ;
8772   \int_value:w \__int_eval:w #2 ;
8773   \__int_eval_end:
8774 }
8775 \cs_new:Npn \__int_mod:ww #1; #2;
8776 { #1 - ( \__int_div_truncate:NwNw #1 ; #2 ; ) * #2 }

```

(End definition for `\int_div_truncate:nn` and others. These functions are documented on page 89.)

`__kernel_int_add:nnn` Equivalent to `\int_eval:n {#1+#2+#3}` except that overflow only occurs if the final result overflows $[-2^{31} + 1, 2^{31} - 1]$. The idea is to choose the order in which the three numbers are added together. If #1 and #2 have opposite signs (one is in $[-2^{31} + 1, -1]$ and the other in $[0, 2^{31} - 1]$) then #1+#2 cannot overflow so we compute the result as #1+#2+#3. If they have the same sign, then either #3 has the same sign and the order does not matter, or #3 has the opposite sign and any order in which #3 is not last will work. We use #1+#3+#2.

```

8777 \cs_new:Npn \__kernel_int_add:nnn #1#2#3
8778 {
8779   \int_value:w \__int_eval:w #1
8780   \if_int_compare:w #2 < \c_zero_int \exp_after:wN \reverse_if:N \fi:
8781   \if_int_compare:w #1 < \c_zero_int + #2 + #3 \else: + #3 + #2 \fi:
8782   \__int_eval_end:
8783 }

```

(End definition for `__kernel_int_add:nnn`.)

12.2 Creating and initialising integers

`\int_new:N` Two ways to do this: one for the format and one for the L^AT_EX 2_ε package. In plain T_EX, `\int_new:c` `\newcount` (and other allocators) are `\outer:` to allow the code here to work in “generic” mode this is therefore accessed by name. (The same applies to `\newbox`, `\newdimen` and so on.)

```

8784 \*package)
8785 \cs_new_protected:Npn \int_new:N #1
8786 {
8787   \__kernel_chk_if_free_cs:N #1
8788   \cs:w newcount \cs_end: #1
8789 }
8790 \*package)
8791 \cs_generate_variant:Nn \int_new:N { c }

```

(End definition for `\int_new:N`. This function is documented on page 89.)

`\int_const:Nn` As stated, most constants can be defined as `\chardef` or `\mathchardef` but that's engine dependent. As a result, there is some set up code to determine what can be done. No full engine testing just yet so everything is a little awkward. We cannot use `\int_gset:Nn` because (when `check-declarations` is enabled) this runs some checks that constants would fail.

```

8792 \cs_new_protected:Npn \int_const:Nn #1#2

```

```

8793 {
8794   \int_compare:nNnTF {#2} < \c_zero_int
8795   {
8796     \int_new:N #1
8797     \tex_global:D
8798   }
8799   {
8800     \int_compare:nNnTF {#2} > \c__int_max_constdef_int
8801     {
8802       \int_new:N #1
8803       \tex_global:D
8804     }
8805     {
8806       \__kernel_chk_if_free_cs:N #1
8807       \tex_global:D \__int_constdef:Nw
8808     }
8809   }
8810   #1 = \__int_eval:w #2 \__int_eval_end:
8811 }
8812 \cs_generate_variant:Nn \int_const:Nn { c }
8813 \if_int_odd:w 0
8814   \cs_if_exist:NT \tex_luatexversion:D { 1 }
8815   \cs_if_exist:NT \tex_omathchardef:D { 1 }
8816   \cs_if_exist:NT \tex_XeTeXversion:D { 1 } ~
8817   \cs_if_exist:NTF \tex_omathchardef:D
8818   { \cs_new_eq:NN \__int_constdef:Nw \tex_omathchardef:D }
8819   { \cs_new_eq:NN \__int_constdef:Nw \tex_chardef:D }
8820   \__int_constdef:Nw \c__int_max_constdef_int 1114111 ~
8821 \else:
8822   \cs_new_eq:NN \__int_constdef:Nw \tex_mathchardef:D
8823   \tex_mathchardef:D \c__int_max_constdef_int 32767 ~
8824 \fi:

```

(End definition for `\int_const:Nn`, `__int_constdef:Nw`, and `\c__int_max_constdef_int`. This function is documented on page 90.)

`\int_zero:N` Functions that reset an *integer* register to zero.

`\int_zero:c` 8825 `\cs_new_protected:Npn \int_zero:N #1 { #1 = \c_zero_int }`

`\int_gzero:N` 8826 `\cs_new_protected:Npn \int_gzero:N #1 { \tex_global:D #1 = \c_zero_int }`

`\int_gzero:c` 8827 `\cs_generate_variant:Nn \int_zero:N { c }`

8828 `\cs_generate_variant:Nn \int_gzero:N { c }`

(End definition for `\int_zero:N` and `\int_gzero:N`. These functions are documented on page 90.)

`\int_zero_new:N` Create a register if needed, otherwise clear it.

`\int_zero_new:c` 8829 `\cs_new_protected:Npn \int_zero_new:N #1`

`\int_gzero_new:N` 8830 `{ \int_if_exist:NTF #1 { \int_zero:N #1 } { \int_new:N #1 } }`

`\int_gzero_new:c` 8831 `\cs_new_protected:Npn \int_gzero_new:N #1`

8832 `{ \int_if_exist:NTF #1 { \int_gzero:N #1 } { \int_new:N #1 } }`

8833 `\cs_generate_variant:Nn \int_zero_new:N { c }`

8834 `\cs_generate_variant:Nn \int_gzero_new:N { c }`

(End definition for `\int_zero_new:N` and `\int_gzero_new:N`. These functions are documented on page 90.)

`\int_set_eq:NN` Setting equal means using one integer inside the set function of another. Check that assigned integer is local/global. No need to check that the other one is defined as `\TeX` does it for us.

```

\int_set_eq:cN
\int_set_eq:Nc
\int_set_eq:cc
\int_gset_eq:NN
\int_gset_eq:cN
\int_gset_eq:Nc
\int_gset_eq:cc

```

```

8835 \cs_new_protected:Npn \int_set_eq:NN #1#2 { #1 = #2 }
8836 \cs_generate_variant:Nn \int_set_eq:NN { c , Nc , cc }
8837 \cs_new_protected:Npn \int_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
8838 \cs_generate_variant:Nn \int_gset_eq:NN { c , Nc , cc }

```

(End definition for `\int_set_eq:NN` and `\int_gset_eq:NN`. These functions are documented on page 90.)

`\int_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.

```

\int_if_exist_p:c
\int_if_exist:NTF
\int_if_exist:cTF

```

```

8839 \prg_new_eq_conditional:NNn \int_if_exist:N \cs_if_exist:N
8840 { TF , T , F , p }
8841 \prg_new_eq_conditional:NNn \int_if_exist:c \cs_if_exist:c
8842 { TF , T , F , p }

```

(End definition for `\int_if_exist:NTF`. This function is documented on page 90.)

12.3 Setting and incrementing integers

`\int_add:Nn` Adding and subtracting to and from a counter.

```

\int_add:cn
\int_gadd:Nn
\int_gadd:cn
\int_sub:Nn
\int_sub:cn
\int_gsub:Nn
\int_gsub:cn

```

```

8843 \cs_new_protected:Npn \int_add:Nn #1#2
8844 { \tex_advance:D #1 by \__int_eval:w #2 \__int_eval_end: }
8845 \cs_new_protected:Npn \int_sub:Nn #1#2
8846 { \tex_advance:D #1 by - \__int_eval:w #2 \__int_eval_end: }
8847 \cs_new_protected:Npn \int_gadd:Nn #1#2
8848 { \tex_global:D \tex_advance:D #1 by \__int_eval:w #2 \__int_eval_end: }
8849 \cs_new_protected:Npn \int_gsub:Nn #1#2
8850 { \tex_global:D \tex_advance:D #1 by - \__int_eval:w #2 \__int_eval_end: }
8851 \cs_generate_variant:Nn \int_add:Nn { c }
8852 \cs_generate_variant:Nn \int_gadd:Nn { c }
8853 \cs_generate_variant:Nn \int_sub:Nn { c }
8854 \cs_generate_variant:Nn \int_gsub:Nn { c }

```

(End definition for `\int_add:Nn` and others. These functions are documented on page 90.)

`\int_incr:N` Incrementing and decrementing of integer registers is done with the following functions.

```

\int_incr:c
\int_gincr:N
\int_gincr:c
\int_decr:N
\int_decr:c
\int_gdecr:N
\int_gdecr:c

```

```

8855 \cs_new_protected:Npn \int_incr:N #1
8856 { \tex_advance:D #1 \c_one_int }
8857 \cs_new_protected:Npn \int_decr:N #1
8858 { \tex_advance:D #1 - \c_one_int }
8859 \cs_new_protected:Npn \int_gincr:N #1
8860 { \tex_global:D \tex_advance:D #1 \c_one_int }
8861 \cs_new_protected:Npn \int_gdecr:N #1
8862 { \tex_global:D \tex_advance:D #1 - \c_one_int }
8863 \cs_generate_variant:Nn \int_incr:N { c }
8864 \cs_generate_variant:Nn \int_decr:N { c }
8865 \cs_generate_variant:Nn \int_gincr:N { c }
8866 \cs_generate_variant:Nn \int_gdecr:N { c }

```

(End definition for `\int_incr:N` and others. These functions are documented on page 90.)

```

\int_set:Nn As integers are register-based TEX issues an error if they are not defined.
\int_set:cn 8867 \cs_new_protected:Npn \int_set:Nn #1#2
\int_gset:Nn 8868 { #1 ~ \__int_eval:w #2 \__int_eval_end: }
\int_gset:cn 8869 \cs_new_protected:Npn \int_gset:Nn #1#2
8870 { \tex_global:D #1 ~ \__int_eval:w #2 \__int_eval_end: }
8871 \cs_generate_variant:Nn \int_set:Nn { c }
8872 \cs_generate_variant:Nn \int_gset:Nn { c }

```

(End definition for `\int_set:Nn` and `\int_gset:Nn`. These functions are documented on page 91.)

12.4 Using integers

```

\int_use:N Here is how counters are accessed:
\int_use:c 8873 \cs_new_eq:NN \int_use:N \tex_the:D
We hand-code this for some speed gain:
8874 %\cs_generate_variant:Nn \int_use:N { c }
8875 \cs_new:Npn \int_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

```

(End definition for `\int_use:N`. This function is documented on page 91.)

12.5 Integer expression conditionals

```

\__int_compare_error: Those functions are used for comparison tests which use a simple syntax where only
\__int_compare_error:Nw one set of braces is required and additional operators such as != and >= are supported.
The tests first evaluate their left-hand side, with a trailing \__int_compare_error:.
This marker is normally not expanded, but if the relation symbol is missing from the
test's argument, then the marker inserts = (and itself) after triggering the relevant TEX
error. If the first token which appears after evaluating and removing the left-hand side is
not a known relation symbol, then a judiciously placed \__int_compare_error:Nw gets
expanded, cleaning up the end of the test and telling the user what the problem was.

```

```

8876 \cs_new_protected:Npn \__int_compare_error:
8877 {
8878   \if_int_compare:w \c_zero_int \c_zero_int \fi:
8879   =
8880   \__int_compare_error:
8881 }
8882 \cs_new:Npn \__int_compare_error:Nw
8883 #1#2 \s__int_stop
8884 {
8885   { }
8886   \c_zero_int \fi:
8887   \__kernel_msg_expandable_error:nnn
8888   { kernel } { unknown-comparison } {#1}
8889   \prg_return_false:
8890 }

```

(End definition for `__int_compare_error:` and `__int_compare_error:Nw`.)

```

\int_compare_p:n Comparison tests using a simple syntax where only one set of braces is required, additional
\int_compare:nTF operators such as != and >= are supported, and multiple comparisons can be performed
at once, for instance 0 < 5 <= 1. The idea is to loop through the argument, finding one
operand at a time, and comparing it to the previous one. The looping auxiliary \__-
\__int_compare:w int_compare:Nw reads one <operand> and one <comparison> symbol, and leaves roughly
\__int_compare:NNw
\__int_compare:nnN
\__int_compare_end=:NNw
\__int_compare=:NNw
\__int_compare<:NNw
\__int_compare>:NNw
\__int_compare==:NNw
\__int_compare!=:NNw
\__int_compare<=:NNw
\__int_compare>=:NNw

```

```

\operand\prg_return_false:\fi:
\reverse_if:N\if_int_compare:w\operand\comparison
\__int_compare:Nw

```

in the input stream. Each call to this auxiliary provides the second operand of the last call's `\if_int_compare:w`. If one of the *comparisons* is `false`, the `true` branch of the \TeX conditional is taken (because of `\reverse_if:N`), immediately returning `false` as the result of the test. There is no \TeX conditional waiting the first operand, so we add an `\if_false:` and expand by hand with `\int_value:w`, thus skipping `\prg_return_false:` on the first iteration.

Before starting the loop, the first step is to make sure that there is at least one relation symbol. We first let \TeX evaluate this left hand side of the (in)equality using `__int_eval:w`. Since the relation symbols `<`, `>`, `=` and `!` are not allowed in integer expressions, they would terminate the expression. If the argument contains no relation symbol, `__int_compare_error:` is expanded, inserting `=` and itself after an error. In all cases, `__int_compare:w` receives as its argument an integer, a relation symbol, and some more tokens. We then setup the loop, which is ended by the two odd-looking items `e` and `{=nd_}`, with a trailing `\s__int_stop` used to grab the entire argument when necessary.

```

8891 \prg_new_conditional:Npnn \int_compare:n #1 { p , T , F , TF }
8892 {
8893   \exp_after:wN \__int_compare:w
8894   \int_value:w \__int_eval:w #1 \__int_compare_error:
8895 }
8896 \cs_new:Npn \__int_compare:w #1 \__int_compare_error:
8897 {
8898   \exp_after:wN \if_false: \int_value:w
8899   \__int_compare:Nw #1 e { = nd_ } \s__int_stop
8900 }

```

The goal here is to find an *operand* and a *comparison*. The *operand* is already evaluated, but we cannot yet grab it as an argument. To access the following relation symbol, we remove the number by applying `__int_to_roman:w`, after making sure that the argument becomes non-positive: its roman numeral representation is then empty. Then probe the first two tokens with `__int_compare:NNw` to determine the relation symbol, building a control sequence from it (`\token_to_str:N` gives better errors if `#1` is not a character). All the extended forms have an extra `=` hence the test for that as a second token. If the relation symbol is unknown, then the control sequence is turned by \TeX into `\scan_stop:`, ignored thanks to `\unexpanded`, and `__int_compare_error:Nw` raises an error.

```

8901 \cs_new:Npn \__int_compare:Nw #1#2 \s__int_stop
8902 {
8903   \exp_after:wN \__int_compare:NNw
8904   \__int_to_roman:w - 0 #2 \s__int_mark
8905   #1#2 \s__int_stop
8906 }
8907 \cs_new:Npn \__int_compare:NNw #1#2#3 \s__int_mark
8908 {
8909   \__kernel_exp_not:w
8910   \use:c
8911   {
8912     __int_compare_ \token_to_str:N #1

```



```

8913         \if_meaning:w = #2 = \fi:
8914         :NNw
8915     }
8916     \__int_compare_error:Nw #1
8917 }

```

When the last $\langle operand \rangle$ is seen, `__int_compare:NNw` receives `e` and `=nd_` as arguments, hence calling `__int_compare_end_=:NNw` to end the loop: return the result of the last comparison (involving the operand that we just found). When a normal relation is found, the appropriate auxiliary calls `__int_compare:nnN` where `#1` is `\if_int_compare:w` or `\reverse_if:N \if_int_compare:w`, `#2` is the $\langle operand \rangle$, and `#3` is one of `<`, `=`, or `>`. As announced earlier, we leave the $\langle operand \rangle$ for the previous conditional. If this conditional is true the result of the test is known, so we remove all tokens and return `false`. Otherwise, we apply the conditional `#1` to the $\langle operand \rangle$ `#2` and the comparison `#3`, and call `__int_compare:Nw` to look for additional operands, after evaluating the following expression.

```

8918 \cs_new:cpn { __int_compare_end_=:NNw } #1#2#3 e #4 \s__int_stop
8919 {
8920     {#3} \exp_stop_f:
8921     \prg_return_false: \else: \prg_return_true: \fi:
8922 }
8923 \cs_new:Npn \__int_compare:nnN #1#2#3
8924 {
8925     {#2} \exp_stop_f:
8926     \prg_return_false: \exp_after:wN \__int_use_none_delimit_by_s_stop:w
8927     \fi:
8928     #1 #2 #3 \exp_after:wN \__int_compare:Nw \int_value:w \__int_eval:w
8929 }

```

The actual comparisons are then simple function calls, using the relation as delimiter for a delimited argument and discarding `__int_compare_error:Nw` $\langle token \rangle$ responsible for error detection.

```

8930 \cs_new:cpn { __int_compare=:NNw } #1#2#3 =
8931 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
8932 \cs_new:cpn { __int_compare:<:NNw } #1#2#3 <
8933 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} < }
8934 \cs_new:cpn { __int_compare:>:NNw } #1#2#3 >
8935 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} > }
8936 \cs_new:cpn { __int_compare=:NNw } #1#2#3 ==
8937 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
8938 \cs_new:cpn { __int_compare!=:NNw } #1#2#3 !=
8939 { \__int_compare:nnN { \if_int_compare:w } {#3} = }
8940 \cs_new:cpn { __int_compare<=:NNw } #1#2#3 <=
8941 { \__int_compare:nnN { \if_int_compare:w } {#3} > }
8942 \cs_new:cpn { __int_compare_>=:NNw } #1#2#3 >=
8943 { \__int_compare:nnN { \if_int_compare:w } {#3} < }

```

(End definition for `\int_compare:nTF` and others. This function is documented on page 92.)

`\int_compare_p:nNn` More efficient but less natural in typing.

```

\int_compare:nNnTF
8944 \prg_new_conditional:Npnn \int_compare:nNn #1#2#3 { p , T , F , TF }
8945 {
8946     \if_int_compare:w \__int_eval:w #1 #2 \__int_eval:w #3 \__int_eval_end:
8947     \prg_return_true:

```

```

8948     \else:
8949         \prg_return_false:
8950     \fi:
8951 }

```

(End definition for \int_compare:nNnTF. This function is documented on page 91.)

```

\int_case:nn For integer cases, the first task to fully expand the check condition. The over all idea is
\int_case:nnTF then much the same as for \tl_case:nn(TF) as described in l3tl.
\__int_case:nnTF
\__int_case:nw
\__int_case_end:nw
8952 \cs_new:Npn \int_case:nnTF #1
8953 {
8954     \exp:w
8955     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} }
8956 }
8957 \cs_new:Npn \int_case:nnT #1#2#3
8958 {
8959     \exp:w
8960     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} {#3} { }
8961 }
8962 \cs_new:Npn \int_case:nnF #1#2
8963 {
8964     \exp:w
8965     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { }
8966 }
8967 \cs_new:Npn \int_case:nn #1#2
8968 {
8969     \exp:w
8970     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { } { }
8971 }
8972 \cs_new:Npn \__int_case:nnTF #1#2#3#4
8973 { \__int_case:nw {#1} #2 {#1} { } \s__int_mark {#3} \s__int_mark {#4} \s__int_stop }
8974 \cs_new:Npn \__int_case:nw #1#2#3
8975 {
8976     \int_compare:nNnTF {#1} = {#2}
8977     { \__int_case_end:nw {#3} }
8978     { \__int_case:nw {#1} }
8979 }
8980 \cs_new:Npn \__int_case_end:nw #1#2#3 \s__int_mark #4#5 \s__int_stop
8981 { \exp_end: #1 #4 }

```

(End definition for \int_case:nnTF and others. This function is documented on page 93.)

```

\int_if_odd_p:n A predicate function.
\int_if_odd:nTF
\int_if_even_p:n
\int_if_even:nTF
8982 \prg_new_conditional:Npnn \int_if_odd:n #1 { p , T , F , TF}
8983 {
8984     \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
8985     \prg_return_true:
8986     \else:
8987     \prg_return_false:
8988     \fi:
8989 }
8990 \prg_new_conditional:Npnn \int_if_even:n #1 { p , T , F , TF}
8991 {
8992     \reverse_if:N \if_int_odd:w \__int_eval:w #1 \__int_eval_end:

```

```

8993     \prg_return_true:
8994 \else:
8995     \prg_return_false:
8996 \fi:
8997 }

```

(End definition for `\int_if_odd:nTF` and `\int_if_even:nTF`. These functions are documented on page 93.)

12.6 Integer expression loops

`\int_while_do:nn` These are quite easy given the above functions. The `while` versions test first and then execute the body. The `do_while` does it the other way round.

```

\int_until_do:nn
\int_do_while:nn
\int_do_until:nn
8998 \cs_new:Npn \int_while_do:nn #1#2
8999 {
9000     \int_compare:nT {#1}
9001     {
9002         #2
9003         \int_while_do:nn {#1} {#2}
9004     }
9005 }
9006 \cs_new:Npn \int_until_do:nn #1#2
9007 {
9008     \int_compare:nF {#1}
9009     {
9010         #2
9011         \int_until_do:nn {#1} {#2}
9012     }
9013 }
9014 \cs_new:Npn \int_do_while:nn #1#2
9015 {
9016     #2
9017     \int_compare:nT {#1}
9018     { \int_do_while:nn {#1} {#2} }
9019 }
9020 \cs_new:Npn \int_do_until:nn #1#2
9021 {
9022     #2
9023     \int_compare:nF {#1}
9024     { \int_do_until:nn {#1} {#2} }
9025 }

```

(End definition for `\int_while_do:nn` and others. These functions are documented on page 94.)

`\int_while_do:nNnn` As above but not using the more natural syntax.

```

\int_until_do:nNnn
\int_do_while:nNnn
\int_do_until:nNnn
9026 \cs_new:Npn \int_while_do:nNnn #1#2#3#4
9027 {
9028     \int_compare:nNnT {#1} #2 {#3}
9029     {
9030         #4
9031         \int_while_do:nNnn {#1} #2 {#3} {#4}
9032     }
9033 }
9034 \cs_new:Npn \int_until_do:nNnn #1#2#3#4

```

```

9035 {
9036   \int_compare:nNnF {#1} #2 {#3}
9037   {
9038     #4
9039     \int_until_do:nNnn {#1} #2 {#3} {#4}
9040   }
9041 }
9042 \cs_new:Npn \int_do_while:nNnn #1#2#3#4
9043 {
9044   #4
9045   \int_compare:nNnT {#1} #2 {#3}
9046   { \int_do_while:nNnn {#1} #2 {#3} {#4} }
9047 }
9048 \cs_new:Npn \int_do_until:nNnn #1#2#3#4
9049 {
9050   #4
9051   \int_compare:nNnF {#1} #2 {#3}
9052   { \int_do_until:nNnn {#1} #2 {#3} {#4} }
9053 }

```

(End definition for `\int_while_do:nNnn` and others. These functions are documented on page 94.)

12.7 Integer step functions

`\int_step_function:nnnN` Before all else, evaluate the initial value, step, and final value. Repeating a function by steps first needs a check on the direction of the steps. After that, do the function for the start value then step and loop around. It would be more symmetrical to test for a step size of zero before checking the sign, but we optimize for the most frequent case (positive step).

```

9054 \cs_new:Npn \int_step_function:nnnN #1#2#3
9055 {
9056   \exp_after:wN \__int_step:wwwN
9057   \int_value:w \__int_eval:w #1 \exp_after:wN ;
9058   \int_value:w \__int_eval:w #2 \exp_after:wN ;
9059   \int_value:w \__int_eval:w #3 ;
9060 }
9061 \cs_new:Npn \__int_step:wwwN #1; #2; #3; #4
9062 {
9063   \int_compare:nNnTF {#2} > \c_zero_int
9064   { \__int_step:NwnnnN > }
9065   {
9066     \int_compare:nNnTF {#2} = \c_zero_int
9067     {
9068       \__kernel_msg_expandable_error:nnn
9069       { kernel } { zero-step } {#4}
9070       \prg_break:
9071     }
9072     { \__int_step:NwnnnN < }
9073   }
9074   #1 ; {#2} {#3} #4
9075   \prg_break_point:
9076 }
9077 \cs_new:Npn \__int_step:NwnnnN #1#2 ; #3#4#5
9078 {

```

```

9079 \if_int_compare:w #2 #1 #4 \exp_stop_f:
9080 \prg_break:n
9081 \fi:
9082 #5 {#2}
9083 \exp_after:wN \__int_step:NwnnN
9084 \exp_after:wN #1
9085 \int_value:w \__int_eval:w #2 + #3 ; {#3} {#4} #5
9086 }
9087 \cs_new:Npn \int_step_function:nN
9088 { \int_step_function:nnnN { 1 } { 1 } }
9089 \cs_new:Npn \int_step_function:nnN #1
9090 { \int_step_function:nnnN {#1} { 1 } }

```

(End definition for `\int_step_function:nnnN` and others. These functions are documented on page 95.)

`\int_step_inline:nn` The approach here is to build a function, with a global integer required to make the
`\int_step_inline:nnn` nesting safe (as seen in other in line functions), and map that function using `\int_`
`\int_step_inline:nnnn` `step_function:nnnN`. We put a `\prg_break_point:Nn` so that `map_break` functions
`\int_step_variable:nNn` from other modules correctly decrement `\g__kernel_prg_map_int` before looking for
`\int_step_variable:nnNn` their own break point. The first argument is `\scan_stop:`, so that no breaking function
`\int_step_variable:nnnnNn` recognizes this break point as its own.

```

\__int_step:NNnnnn
9091 \cs_new_protected:Npn \int_step_inline:nn
9092 { \int_step_inline:nnnn { 1 } { 1 } }
9093 \cs_new_protected:Npn \int_step_inline:nnn #1
9094 { \int_step_inline:nnnn {#1} { 1 } }
9095 \cs_new_protected:Npn \int_step_inline:nnnn
9096 {
9097   \int_gincr:N \g__kernel_prg_map_int
9098   \exp_args:NNc \__int_step:NNnnnn
9099   \cs_gset_protected:Npn
9100     { __int_map_ \int_use:N \g__kernel_prg_map_int :w }
9101 }
9102 \cs_new_protected:Npn \int_step_variable:nNn
9103 { \int_step_variable:nnnNn { 1 } { 1 } }
9104 \cs_new_protected:Npn \int_step_variable:nnNn #1
9105 { \int_step_variable:nnnNn {#1} { 1 } }
9106 \cs_new_protected:Npn \int_step_variable:nnnnNn #1#2#3#4#5
9107 {
9108   \int_gincr:N \g__kernel_prg_map_int
9109   \exp_args:NNc \__int_step:NNnnnn
9110   \cs_gset_protected:Npx
9111     { __int_map_ \int_use:N \g__kernel_prg_map_int :w }
9112     {#1}{#2}{#3}
9113     {
9114       \tl_set:Nn \exp_not:N #4 {##1}
9115       \exp_not:n {#5}
9116     }
9117 }
9118 \cs_new_protected:Npn \__int_step:NNnnnn #1#2#3#4#5#6
9119 {
9120   #1 #2 ##1 {#6}
9121   \int_step_function:nnnN {#3} {#4} {#5} #2
9122   \prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__kernel_prg_map_int }
9123 }

```

(End definition for `\int_step_inline:nn` and others. These functions are documented on page 95.)

12.8 Formatting integers

`\int_to_arabic:n` Nothing exciting here.

```
9124 \cs_new_eq:NN \int_to_arabic:n \int_eval:n
```

(End definition for `\int_to_arabic:n`. This function is documented on page 96.)

`\int_to_symbols:nnn` For conversion of integers to arbitrary symbols the method is in general as follows. The input number (#1) is compared to the total number of symbols available at each place (#2). If the input is larger than the total number of symbols available then the modulus is needed, with one added so that the positions don't have to number from zero. Using an `f`-type expansion, this is done so that the system is recursive. The actual conversion function therefore gets a 'nice' number at each stage. Of course, if the initial input was small enough then there is no problem and everything is easy.

```
9125 \cs_new:Npn \int_to_symbols:nnn #1#2#3
9126 {
9127   \int_compare:nNnTF {#1} > {#2}
9128   {
9129     \exp_args:NNo \exp_args:No \__int_to_symbols:nnnn
9130     {
9131       \int_case:nn
9132       { 1 + \int_mod:nn { #1 - 1 } {#2} }
9133       {#3}
9134     }
9135     {#1} {#2} {#3}
9136   }
9137   { \int_case:nn {#1} {#3} }
9138 }
9139 \cs_new:Npn \__int_to_symbols:nnnn #1#2#3#4
9140 {
9141   \exp_args:Nf \int_to_symbols:nnn
9142   { \int_div_truncate:nn { #2 - 1 } {#3} } {#3} {#4}
9143   #1
9144 }
```

(End definition for `\int_to_symbols:nnn` and `__int_to_symbols:nnnn`. This function is documented on page 96.)

`\int_to_alph:n` These both use the above function with input functions that make sense for the alphabet
`\int_to_Alph:n` in English.

```
9145 \cs_new:Npn \int_to_alph:n #1
9146 {
9147   \int_to_symbols:nnn {#1} { 26 }
9148   {
9149     { 1 } { a }
9150     { 2 } { b }
9151     { 3 } { c }
9152     { 4 } { d }
9153     { 5 } { e }
9154     { 6 } { f }
9155     { 7 } { g }
```

```

9156     { 8 } { h }
9157     { 9 } { i }
9158     { 10 } { j }
9159     { 11 } { k }
9160     { 12 } { l }
9161     { 13 } { m }
9162     { 14 } { n }
9163     { 15 } { o }
9164     { 16 } { p }
9165     { 17 } { q }
9166     { 18 } { r }
9167     { 19 } { s }
9168     { 20 } { t }
9169     { 21 } { u }
9170     { 22 } { v }
9171     { 23 } { w }
9172     { 24 } { x }
9173     { 25 } { y }
9174     { 26 } { z }
9175 }
9176 }
9177 \cs_new:Npn \int_to_Alph:n #1
9178 {
9179     \int_to_symbols:nnn {#1} { 26 }
9180     {
9181         { 1 } { A }
9182         { 2 } { B }
9183         { 3 } { C }
9184         { 4 } { D }
9185         { 5 } { E }
9186         { 6 } { F }
9187         { 7 } { G }
9188         { 8 } { H }
9189         { 9 } { I }
9190         { 10 } { J }
9191         { 11 } { K }
9192         { 12 } { L }
9193         { 13 } { M }
9194         { 14 } { N }
9195         { 15 } { O }
9196         { 16 } { P }
9197         { 17 } { Q }
9198         { 18 } { R }
9199         { 19 } { S }
9200         { 20 } { T }
9201         { 21 } { U }
9202         { 22 } { V }
9203         { 23 } { W }
9204         { 24 } { X }
9205         { 25 } { Y }
9206         { 26 } { Z }
9207     }
9208 }

```

(End definition for `\int_to_alph:n` and `\int_to_Alph:n`. These functions are documented on page 96.)

`\int_to_base:nn` Converting from base ten (#1) to a second base (#2) starts with computing #1: if it is
`\int_to_Base:nn` a complicated calculation, we shouldn't perform it twice. Then check the sign, store it,
`__int_to_base:nn` either - or `\c_empty_tl`, and feed the absolute value to the next auxiliary function.
`__int_to_Base:nn` 9209 `\cs_new:Npn \int_to_base:nn #1`
`__int_to_base:nnN` 9210 `{ \exp_args:Nf __int_to_base:nn { \int_eval:n {#1} } }`
`__int_to_Base:nnN` 9211 `\cs_new:Npn \int_to_Base:nn #1`
`__int_to_base:nnnN` 9212 `{ \exp_args:Nf __int_to_Base:nn { \int_eval:n {#1} } }`
`__int_to_Base:nnnN` 9213 `\cs_new:Npn __int_to_base:nn #1#2`
`__int_to_letter:n` 9214 `{`
`__int_to_Letter:n` 9215 `\int_compare:nNnTF {#1} < 0`
9216 `{ \exp_args:No __int_to_base:nnN { \use_none:n #1 } {#2} - }`
9217 `{ __int_to_base:nnN {#1} {#2} \c_empty_tl }`
9218 `}`
9219 `\cs_new:Npn __int_to_Base:nn #1#2`
9220 `{`
9221 `\int_compare:nNnTF {#1} < 0`
9222 `{ \exp_args:No __int_to_Base:nnN { \use_none:n #1 } {#2} - }`
9223 `{ __int_to_Base:nnN {#1} {#2} \c_empty_tl }`
9224 `}`

Here, the idea is to provide a recursive system to deal with the input. The output is built up after the end of the function. At each pass, the value in #1 is checked to see if it is less than the new base (#2). If it is, then it is converted directly, putting the sign back in front. On the other hand, if the value to convert is greater than or equal to the new base then the modulus and remainder values are found. The modulus is converted to a symbol and put on the right, and the remainder is carried forward to the next round.

9225 `\cs_new:Npn __int_to_base:nnN #1#2#3`
9226 `{`
9227 `\int_compare:nNnTF {#1} < {#2}`
9228 `{ \exp_last_unbraced:Nf #3 { __int_to_letter:n {#1} } }`
9229 `{`
9230 `\exp_args:Nf __int_to_base:nnnN`
9231 `{ __int_to_letter:n { \int_mod:nn {#1} {#2} } }`
9232 `{#1}`
9233 `{#2}`
9234 `#3`
9235 `}`
9236 `}`
9237 `\cs_new:Npn __int_to_base:nnnN #1#2#3#4`
9238 `{`
9239 `\exp_args:Nf __int_to_base:nnN`
9240 `{ \int_div_truncate:nn {#2} {#3} }`
9241 `{#3}`
9242 `#4`
9243 `#1`
9244 `}`
9245 `\cs_new:Npn __int_to_Base:nnN #1#2#3`
9246 `{`
9247 `\int_compare:nNnTF {#1} < {#2}`
9248 `{ \exp_last_unbraced:Nf #3 { __int_to_Letter:n {#1} } }`
9249 `{`
9250 `\exp_args:Nf __int_to_Base:nnnN`
9251 `{ __int_to_Letter:n { \int_mod:nn {#1} {#2} } }`
9252 `{#1}`


```

9253         {#2}
9254         #3
9255     }
9256 }
9257 \cs_new:Npn \__int_to_Base:nnnN #1#2#3#4
9258 {
9259     \exp_args:Nf \__int_to_Base:nnN
9260     { \int_div_truncate:nn {#2} {#3} }
9261     {#3}
9262     #4
9263     #1
9264 }

```

Convert to a letter only if necessary, otherwise simply return the value unchanged. It would be cleaner to use `\int_case:nn`, but in our case, the cases are contiguous, so it is forty times faster to use the `\if_case:w` primitive. The first `\exp_after:wN` expands the conditional, jumping to the correct case, the second one expands after the resulting character to close the conditional. Since `#1` might be an expression, and not directly a single digit, we need to evaluate it properly, and expand the trailing `\fi:`.

```

9265 \cs_new:Npn \__int_to_letter:n #1
9266 {
9267     \exp_after:wN \exp_after:wN
9268     \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
9269         a
9270     \or: b
9271     \or: c
9272     \or: d
9273     \or: e
9274     \or: f
9275     \or: g
9276     \or: h
9277     \or: i
9278     \or: j
9279     \or: k
9280     \or: l
9281     \or: m
9282     \or: n
9283     \or: o
9284     \or: p
9285     \or: q
9286     \or: r
9287     \or: s
9288     \or: t
9289     \or: u
9290     \or: v
9291     \or: w
9292     \or: x
9293     \or: y
9294     \or: z
9295     \else: \int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
9296     \fi:
9297 }
9298 \cs_new:Npn \__int_to_Letter:n #1
9299 {

```

```

9300 \exp_after:wN \exp_after:wN
9301 \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
9302     A
9303 \or: B
9304 \or: C
9305 \or: D
9306 \or: E
9307 \or: F
9308 \or: G
9309 \or: H
9310 \or: I
9311 \or: J
9312 \or: K
9313 \or: L
9314 \or: M
9315 \or: N
9316 \or: O
9317 \or: P
9318 \or: Q
9319 \or: R
9320 \or: S
9321 \or: T
9322 \or: U
9323 \or: V
9324 \or: W
9325 \or: X
9326 \or: Y
9327 \or: Z
9328 \else: \int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
9329 \fi:
9330 }

```

(End definition for `\int_to_base:nn` and others. These functions are documented on page 97.)

```

\int_to_bin:n Wrappers around the generic function.
\int_to_hex:n 9331 \cs_new:Npn \int_to_bin:n #1
\int_to_Hex:n 9332 { \int_to_base:nn {#1} { 2 } }
\int_to_oct:n 9333 \cs_new:Npn \int_to_hex:n #1
9334 { \int_to_base:nn {#1} { 16 } }
9335 \cs_new:Npn \int_to_Hex:n #1
9336 { \int_to_Base:nn {#1} { 16 } }
9337 \cs_new:Npn \int_to_oct:n #1
9338 { \int_to_base:nn {#1} { 8 } }

```

(End definition for `\int_to_bin:n` and others. These functions are documented on page 97.)

```

\int_to_roman:n The \__int_to_roman:w primitive creates tokens of category code 12 (other). Usually,
\int_to_Roman:n what is actually wanted is letters. The approach here is to convert the output of the
\__int_to_roman:N primitive into letters using appropriate control sequence names. That keeps everything
\__int_to_roman:N expandable. The loop is terminated by the conversion of the Q.
\__int_to_roman_i:w 9339 \cs_new:Npn \int_to_roman:n #1
\__int_to_roman_v:w 9340 {
\__int_to_roman_x:w 9341 \exp_after:wN \__int_to_roman:N
\__int_to_roman_l:w 9342 \__int_to_roman:w \int_eval:n {#1} Q
\__int_to_roman_c:w
\__int_to_roman_d:w
\__int_to_roman_m:w
\__int_to_roman_Q:w
\__int_to_Roman_i:w
\__int_to_Roman_v:w
\__int_to_Roman_x:w
\__int_to_Roman_l:w
\__int_to_Roman_c:w
\__int_to_Roman_d:w

```

```

9343 }
9344 \cs_new:Npn \__int_to_roman:N #1
9345 {
9346   \use:c { __int_to_roman_ #1 :w }
9347   \__int_to_roman:N
9348 }
9349 \cs_new:Npn \int_to_Roman:n #1
9350 {
9351   \exp_after:wN \__int_to_Roman_aux:N
9352   \__int_to_roman:w \int_eval:n {#1} Q
9353 }
9354 \cs_new:Npn \__int_to_Roman_aux:N #1
9355 {
9356   \use:c { __int_to_Roman_ #1 :w }
9357   \__int_to_Roman_aux:N
9358 }
9359 \cs_new:Npn \__int_to_roman_i:w { i }
9360 \cs_new:Npn \__int_to_roman_v:w { v }
9361 \cs_new:Npn \__int_to_roman_x:w { x }
9362 \cs_new:Npn \__int_to_roman_l:w { l }
9363 \cs_new:Npn \__int_to_roman_c:w { c }
9364 \cs_new:Npn \__int_to_roman_d:w { d }
9365 \cs_new:Npn \__int_to_roman_m:w { m }
9366 \cs_new:Npn \__int_to_roman_Q:w #1 { }
9367 \cs_new:Npn \__int_to_Roman_i:w { I }
9368 \cs_new:Npn \__int_to_Roman_v:w { V }
9369 \cs_new:Npn \__int_to_Roman_x:w { X }
9370 \cs_new:Npn \__int_to_Roman_l:w { L }
9371 \cs_new:Npn \__int_to_Roman_c:w { C }
9372 \cs_new:Npn \__int_to_Roman_d:w { D }
9373 \cs_new:Npn \__int_to_Roman_m:w { M }
9374 \cs_new:Npn \__int_to_Roman_Q:w #1 { }

```

(End definition for `\int_to_roman:n` and others. These functions are documented on page 97.)

12.9 Converting from other formats to integers

`__int_pass_signs:wn` Called as `__int_pass_signs:wn <signs and digits> \s__int_stop {<code>}`, this function leaves in the input stream any sign it finds, then inserts the `<code>` before the first non-sign token (and removes `\s__int_stop`). More precisely, it deletes any + and passes any - to the input stream, hence should be called in an integer expression.

```

9375 \cs_new:Npn \__int_pass_signs:wn #1
9376 {
9377   \if:w + \if:w - \exp_not:N #1 + \fi: \exp_not:N #1
9378   \exp_after:wN \__int_pass_signs:wn
9379   \else:
9380     \exp_after:wN \__int_pass_signs_end:wn
9381     \exp_after:wN #1
9382   \fi:
9383 }
9384 \cs_new:Npn \__int_pass_signs_end:wn #1 \s__int_stop #2 { #2 #1 }

```

(End definition for `__int_pass_signs:wn` and `__int_pass_signs_end:wn`.)

`\int_from_alph:n` First take care of signs then loop through the input using the `recursion` quarks. The `__int_from_alph:nN` auxiliary collects in its first argument the value obtained so far, and the auxiliary `__int_from_alph:N` converts one letter to an expression which evaluates to the correct number.

```

9385 \cs_new:Npn \int_from_alph:n #1
9386 {
9387   \int_eval:n
9388   {
9389     \exp_after:wN \__int_pass_signs:wn \tl_to_str:n {#1}
9390     \s__int_stop { \__int_from_alph:nN { 0 } }
9391     \q__int_recursion_tail \q__int_recursion_stop
9392   }
9393 }
9394 \cs_new:Npn \__int_from_alph:nN #1#2
9395 {
9396   \__int_if_recursion_tail_stop_do:Nn #2 {#1}
9397   \exp_args:Nf \__int_from_alph:nN
9398   { \int_eval:n { #1 * 26 + \__int_from_alph:N #2 } }
9399 }
9400 \cs_new:Npn \__int_from_alph:N #1
9401 { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 64 } { 96 } }

```

(End definition for `\int_from_alph:n`, `__int_from_alph:nN`, and `__int_from_alph:N`. This function is documented on page 97.)

`\int_from_base:nn` Leave the signs into the integer expression, then loop through characters, collecting the value found so far in the first argument of `__int_from_base:nnN`. To convert a single character, `__int_from_base:N` checks first for digits, then distinguishes lower from upper case letters, turning them into the appropriate number. Note that this auxiliary does not use `\int_eval:n`, hence is not safe for general use.

```

9402 \cs_new:Npn \int_from_base:nn #1#2
9403 {
9404   \int_eval:n
9405   {
9406     \exp_after:wN \__int_pass_signs:wn \tl_to_str:n {#1}
9407     \s__int_stop { \__int_from_base:nnN { 0 } {#2} }
9408     \q__int_recursion_tail \q__int_recursion_stop
9409   }
9410 }
9411 \cs_new:Npn \__int_from_base:nnN #1#2#3
9412 {
9413   \__int_if_recursion_tail_stop_do:Nn #3 {#1}
9414   \exp_args:Nf \__int_from_base:nnN
9415   { \int_eval:n { #1 * #2 + \__int_from_base:N #3 } }
9416   {#2}
9417 }
9418 \cs_new:Npn \__int_from_base:N #1
9419 {
9420   \int_compare:nNnTF { '#1 } < { 58 }
9421   {#1}
9422   { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 55 } { 87 } }
9423 }

```

(End definition for `\int_from_base:nn`, `__int_from_base:nnN`, and `__int_from_base:N`. This function is documented on page 98.)

`\int_from_bin:n` Wrappers around the generic function.

```

\int_from_hex:n 9424 \cs_new:Npn \int_from_bin:n #1
\int_from_oct:n 9425 { \int_from_base:nn {#1} { 2 } }
9426 \cs_new:Npn \int_from_hex:n #1
9427 { \int_from_base:nn {#1} { 16 } }
9428 \cs_new:Npn \int_from_oct:n #1
9429 { \int_from_base:nn {#1} { 8 } }

```

(End definition for `\int_from_bin:n`, `\int_from_hex:n`, and `\int_from_oct:n`. These functions are documented on page 98.)

`\c_int_from_roman_i_int` Constants used to convert from Roman numerals to integers.

```

\c_int_from_roman_v_int 9430 \int_const:cn { c__int_from_roman_i_int } { 1 }
\c_int_from_roman_x_int 9431 \int_const:cn { c__int_from_roman_v_int } { 5 }
\c_int_from_roman_l_int 9432 \int_const:cn { c__int_from_roman_x_int } { 10 }
\c_int_from_roman_c_int 9433 \int_const:cn { c__int_from_roman_l_int } { 50 }
\c_int_from_roman_d_int 9434 \int_const:cn { c__int_from_roman_c_int } { 100 }
\c_int_from_roman_m_int 9435 \int_const:cn { c__int_from_roman_d_int } { 500 }
\c_int_from_roman_I_int 9436 \int_const:cn { c__int_from_roman_m_int } { 1000 }
\c_int_from_roman_V_int 9437 \int_const:cn { c__int_from_roman_I_int } { 1 }
\c_int_from_roman_X_int 9438 \int_const:cn { c__int_from_roman_V_int } { 5 }
\c_int_from_roman_L_int 9439 \int_const:cn { c__int_from_roman_X_int } { 10 }
\c_int_from_roman_C_int 9440 \int_const:cn { c__int_from_roman_L_int } { 50 }
\c_int_from_roman_D_int 9441 \int_const:cn { c__int_from_roman_C_int } { 100 }
\c_int_from_roman_M_int 9442 \int_const:cn { c__int_from_roman_D_int } { 500 }
9443 \int_const:cn { c__int_from_roman_M_int } { 1000 }

```

(End definition for `\c_int_from_roman_i_int` and others.)

`\int_from_roman:n` The method here is to iterate through the input, finding the appropriate value for each letter and building up a sum. This is then evaluated by \TeX . If any unknown letter is found, skip to the closing parenthesis and insert `*0-1` afterwards, to replace the value by `-1`.

```

\__int_from_roman:NN 9444 \cs_new:Npn \int_from_roman:n #1
\__int_from_roman_error:w 9445 {
9446   \int_eval:n
9447   {
9448     (
9449       0
9450       \exp_after:wN \__int_from_roman:NN \tl_to_str:n {#1}
9451       \q__int_recursion_tail \q__int_recursion_tail \q__int_recursion_stop
9452     )
9453   }
9454 }
9455 \cs_new:Npn \__int_from_roman:NN #1#2
9456 {
9457   \__int_if_recursion_tail_stop:N #1
9458   \int_if_exist:cF { c__int_from_roman_ #1 _int }
9459   { \__int_from_roman_error:w }
9460   \__int_if_recursion_tail_stop_do:Nn #2
9461   { + \use:c { c__int_from_roman_ #1 _int } }
9462   \int_if_exist:cF { c__int_from_roman_ #2 _int }
9463   { \__int_from_roman_error:w }
9464   \int_compare:nNnTF

```

```

9465     { \use:c { c__int_from_roman_ #1 _int } }
9466     <
9467     { \use:c { c__int_from_roman_ #2 _int } }
9468     {
9469       + \use:c { c__int_from_roman_ #2 _int }
9470       - \use:c { c__int_from_roman_ #1 _int }
9471       \__int_from_roman:NN
9472     }
9473     {
9474       + \use:c { c__int_from_roman_ #1 _int }
9475       \__int_from_roman:NN #2
9476     }
9477   }
9478   \cs_new:Npn \__int_from_roman_error:w #1 \q__int_recursion_stop #2
9479     { #2 * 0 - 1 }

```

(End definition for `\int_from_roman:n`, `__int_from_roman:NN`, and `__int_from_roman_error:w`. This function is documented on page 98.)

12.10 Viewing integer

`\int_show:N` Diagnostics.
`\int_show:c` 9480 `\cs_new_eq:NN \int_show:N __kernel_register_show:N`
`__int_show:nN` 9481 `\cs_generate_variant:Nn \int_show:N { c }`

(End definition for `\int_show:N` and `__int_show:nN`. This function is documented on page 99.)

`\int_show:n` We don't use the TeX primitive `\showthe` to show integer expressions: this gives a more unified output.

```

9482 \cs_new_protected:Npn \int_show:n
9483   { \msg_show_eval:Nn \int_eval:n }

```

(End definition for `\int_show:n`. This function is documented on page 99.)

`\int_log:N` Diagnostics.
`\int_log:c` 9484 `\cs_new_eq:NN \int_log:N __kernel_register_log:N`
9485 `\cs_generate_variant:Nn \int_log:N { c }`

(End definition for `\int_log:N`. This function is documented on page 99.)

`\int_log:n` Similar to `\int_show:n`.

```

9486 \cs_new_protected:Npn \int_log:n
9487   { \msg_log_eval:Nn \int_eval:n }

```

(End definition for `\int_log:n`. This function is documented on page 99.)

12.11 Random integers

`\int_rand:nn` Defined in `l3fp-random`.

(End definition for `\int_rand:nn`. This function is documented on page 98.)

12.12 Constant integers

`\c_zero_int` The zero is defined in `l3basics`.

`\c_one_int` 9488 `\int_const:Nn \c_one_int { 1 }`

(End definition for `\c_zero_int` and `\c_one_int`. These variables are documented on page 99.)

`\c_max_int` The largest number allowed is $2^{31} - 1$

9489 `\int_const:Nn \c_max_int { 2 147 483 647 }`

(End definition for `\c_max_int`. This variable is documented on page 99.)

`\c_max_char_int` The largest character code is 1114111 (hexadecimal 10FFFF) in XeTeX and LuaTeX and 255 in other engines. In many places pTeX and upTeX support larger character codes but for instance the values of `\lccode` are restricted to $[0, 255]$.

9490 `\int_const:Nn \c_max_char_int`
9491 `{`
9492 `\if_int_odd:w 0`
9493 `\cs_if_exist:NT \tex luatexversion:D { 1 }`
9494 `\cs_if_exist:NT \tex XeTeXversion:D { 1 } ~`
9495 `"10FFFF`
9496 `\else:`
9497 `"FF`
9498 `\fi:`
9499 `}`

(End definition for `\c_max_char_int`. This variable is documented on page 99.)

12.13 Scratch integers

`\l_tmpa_int` We provide two local and two global scratch counters, maybe we need more or less.

`\l_tmpb_int` 9500 `\int_new:N \l_tmpa_int`

`\g_tmpa_int` 9501 `\int_new:N \l_tmpb_int`

`\g_tmpb_int` 9502 `\int_new:N \g_tmpa_int`

9503 `\int_new:N \g_tmpb_int`

(End definition for `\l_tmpa_int` and others. These variables are documented on page 99.)

12.14 Integers for earlier modules

<@@=seq>

`\l__int_internal_a_int`

`\l__int_internal_b_int`

9504 `\int_new:N \l__int_internal_a_int`

9505 `\int_new:N \l__int_internal_b_int`

(End definition for `\l__int_internal_a_int` and `\l__int_internal_b_int`.)

9506 `</initex | package>`

13 l3flag implementation

9507 $\langle *initex | package \rangle$

9508 $\langle @@=flag \rangle$

The following test files are used for this code: m3flag001.

13.1 Non-expandable flag commands

The height h of a flag (initially zero) is stored by setting control sequences of the form $\backslash flag \langle name \rangle \langle integer \rangle$ to $\backslash relax$ for $0 \leq \langle integer \rangle < h$. When a flag is raised, a “trap” function $\backslash flag \langle name \rangle$ is called. The existence of this function is also used to test for the existence of a flag.

$\backslash flag_new:n$ For each flag, we define a “trap” function, which by default simply increases the flag by 1 by letting the appropriate control sequence to $\backslash relax$. This can be done expandably!

```
9509 \cs_new_protected:Npn \flag_new:n #1
9510 {
9511   \cs_new:cpn { flag~#1 } ##1 ;
9512   { \exp_after:wN \use_none:n \cs:w flag~#1~##1 \cs_end: }
9513 }
```

(End definition for $\backslash flag_new:n$. This function is documented on page 102.)

$\backslash flag_clear:n$ $\backslash _flag_clear:wn$ Undefine control sequences, starting from the 0 flag, upwards, until reaching an undefined control sequence. We don’t use $\backslash cs_undefine:c$ because that would act globally. When the option `check-declarations` is used, check for the function defined by $\backslash flag_new:n$.

```
9514 \cs_new_protected:Npn \flag_clear:n #1 { \_flag_clear:wn 0 ; {#1} }
9515 \cs_new_protected:Npn \_flag_clear:wn #1 ; #2
9516 {
9517   \if_cs_exist:w flag~#2~#1 \cs_end:
9518   \cs_set_eq:cN { flag~#2~#1 } \tex_undefined:D
9519   \exp_after:wN \_flag_clear:wn
9520   \int_value:w \int_eval:w 1 + #1
9521   \else:
9522     \use_i:nnn
9523   \fi:
9524   ; {#2}
9525 }
```

(End definition for $\backslash flag_clear:n$ and $\backslash _flag_clear:wn$. This function is documented on page 102.)

$\backslash flag_clear_new:n$ As for other datatypes, clear the $\langle flag \rangle$ or create a new one, as appropriate.

```
9526 \cs_new_protected:Npn \flag_clear_new:n #1
9527 { \flag_if_exist:nTF {#1} { \flag_clear:n } { \flag_new:n } {#1} }
```

(End definition for $\backslash flag_clear_new:n$. This function is documented on page 102.)

$\backslash flag_show:n$ $\backslash flag_log:n$ $\backslash _flag_show:Nn$ Show the height (terminal or log file) using appropriate `l3msg` auxiliaries.

```
9528 \cs_new_protected:Npn \flag_show:n { \_flag_show:Nn \tl_show:n }
9529 \cs_new_protected:Npn \flag_log:n { \_flag_show:Nn \tl_log:n }
9530 \cs_new_protected:Npn \_flag_show:Nn #1#2
9531 {
9532   \exp_args:Nc \_kernel_chk_defined:NT { flag~#2 }
9533   {
```



```

9534         \exp_args:Nx #1
9535         { \tl_to_str:n { flag~#2~height } = \flag_height:n {#2} }
9536     }
9537 }

```

(End definition for `\flag_show:n`, `\flag_log:n`, and `__flag_show:Nn`. These functions are documented on page 102.)

13.2 Expandable flag commands

`\flag_if_exist:p:n` A flag exist if the corresponding trap `\flag <flag name>:n` is defined.

```

\flag_if_exist:nTF
9538 \prg_new_conditional:Npnn \flag_if_exist:n #1 { p , T , F , TF }
9539 {
9540     \cs_if_exist:cTF { flag~#1 }
9541     { \prg_return_true: } { \prg_return_false: }
9542 }

```

(End definition for `\flag_if_exist:nTF`. This function is documented on page 103.)

`\flag_if_raised:p:n` Test if the flag has a non-zero height, by checking the 0 control sequence.

```

\flag_if_raised:nTF
9543 \prg_new_conditional:Npnn \flag_if_raised:n #1 { p , T , F , TF }
9544 {
9545     \if_cs_exist:w flag~#1~0 \cs_end:
9546     \prg_return_true:
9547     \else:
9548     \prg_return_false:
9549     \fi:
9550 }

```

(End definition for `\flag_if_raised:nTF`. This function is documented on page 103.)

`\flag_height:n` Extract the value of the flag by going through all of the control sequences starting from 0.

```

\__flag_height_loop:wn
\__flag_height_end:wn
9551 \cs_new:Npn \flag_height:n #1 { \__flag_height_loop:wn 0; {#1} }
9552 \cs_new:Npn \__flag_height_loop:wn #1 ; #2
9553 {
9554     \if_cs_exist:w flag~#2~#1 \cs_end:
9555     \exp_after:wN \__flag_height_loop:wn \int_value:w \int_eval:w 1 +
9556     \else:
9557     \exp_after:wN \__flag_height_end:wn
9558     \fi:
9559     #1 ; {#2}
9560 }
9561 \cs_new:Npn \__flag_height_end:wn #1 ; #2 {#1}

```

(End definition for `\flag_height:n`, `__flag_height_loop:wn`, and `__flag_height_end:wn`. This function is documented on page 103.)

`\flag_raise:n` Simply apply the trap to the height, after expanding the latter.

```

9562 \cs_new:Npn \flag_raise:n #1
9563 {
9564     \cs:w flag~#1 \exp_after:wN \cs_end:
9565     \int_value:w \flag_height:n {#1} ;
9566 }

```

(End definition for `\flag_raise:n`. This function is documented on page 103.)

```

9567 </initex | package>

```

14 l3prg implementation

The following test files are used for this code: *m3prg001.lvt, m3prg002.lvt, m3prg003.lvt.*

9568 $\langle *initex | package \rangle$

14.1 Primitive conditionals

$\backslash if_bool:N$ Those two primitive T_EX conditionals are synonyms. $\backslash if_bool:N$ is defined in l3basics, as it's needed earlier to define quark test functions.

9569 $\backslash cs_new_eq:NN \backslash if_predicate:w \backslash tex_ifodd:D$

(End definition for $\backslash if_bool:N$ and $\backslash if_predicate:w$. These functions are documented on page 112.)

14.2 Defining a set of conditional functions

These are all defined in l3basics, as they are needed “early”. This is just a reminder!

(End definition for $\backslash prg_set_conditional:Npnn$ and others. These functions are documented on page 104.)

14.3 The boolean data type

9570 $\langle @@=bool \rangle$

Boolean variables have to be initiated when they are created. Other than that there is not much to say here.

9571 $\backslash cs_new_protected:Npn \backslash bool_new:N \#1 \{ \backslash cs_new_eq:NN \#1 \backslash c_false_bool \}$
9572 $\backslash cs_generate_variant:Nn \backslash bool_new:N \{ c \}$

(End definition for $\backslash bool_new:N$. This function is documented on page 106.)

$\backslash bool_const:Nn$ A merger between $\backslash tl_const:Nn$ and $\backslash bool_set:Nn$.

$\backslash bool_const:cn$ 9573 $\backslash cs_new_protected:Npn \backslash bool_const:Nn \#1\#2$
9574 $\{$
9575 $\quad \backslash_kernel_chk_if_free_cs:N \#1$
9576 $\quad \backslash tex_global:D \backslash tex_chardef:D \#1 = \backslash bool_if_p:n \{ \#2 \}$
9577 $\}$
9578 $\backslash cs_generate_variant:Nn \backslash bool_const:Nn \{ c \}$

(End definition for $\backslash bool_const:Nn$. This function is documented on page 107.)

$\backslash bool_set_true:N$ Setting is already pretty easy. When check-declarations is active, the definitions are patched to make sure the boolean exists. This is needed because booleans are not based on token lists nor on T_EX registers.

$\backslash bool_set_true:c$ 9579 $\backslash cs_new_protected:Npn \backslash bool_set_true:N \#1$
 $\backslash bool_gset_true:N$ 9580 $\{ \backslash cs_set_eq:NN \#1 \backslash c_true_bool \}$
 $\backslash bool_set_false:N$ 9581 $\backslash cs_new_protected:Npn \backslash bool_set_false:N \#1$
 $\backslash bool_set_false:c$ 9582 $\{ \backslash cs_set_eq:NN \#1 \backslash c_false_bool \}$
 $\backslash bool_gset_false:N$ 9583 $\backslash cs_new_protected:Npn \backslash bool_gset_true:N \#1$
 $\backslash bool_gset_false:c$ 9584 $\{ \backslash cs_gset_eq:NN \#1 \backslash c_true_bool \}$
9585 $\backslash cs_new_protected:Npn \backslash bool_gset_false:N \#1$
9586 $\{ \backslash cs_gset_eq:NN \#1 \backslash c_false_bool \}$
9587 $\backslash cs_generate_variant:Nn \backslash bool_set_true:N \{ c \}$
9588 $\backslash cs_generate_variant:Nn \backslash bool_set_false:N \{ c \}$
9589 $\backslash cs_generate_variant:Nn \backslash bool_gset_true:N \{ c \}$
9590 $\backslash cs_generate_variant:Nn \backslash bool_gset_false:N \{ c \}$

(End definition for `\bool_set_true:N` and others. These functions are documented on page 107.)

`\bool_set_eq:NN` The usual copy code. While it would be cleaner semantically to copy the `\cs_set_eq:NN` family of functions, we copy `\tl_set_eq:NN` because that has the correct checking code.

`\bool_set_eq:cN`

`\bool_set_eq:Nc` 9591 `\cs_new_eq:NN \bool_set_eq:NN \tl_set_eq:NN`

`\bool_set_eq:cc` 9592 `\cs_new_eq:NN \bool_gset_eq:NN \tl_gset_eq:NN`

`\bool_gset_eq:NN` 9593 `\cs_generate_variant:Nn \bool_set_eq:NN { Nc, cN, cc }`

`\bool_gset_eq:cN` 9594 `\cs_generate_variant:Nn \bool_gset_eq:NN { Nc, cN, cc }`

`\bool_gset_eq:Nc` (End definition for `\bool_set_eq:NN` and `\bool_gset_eq:NN`. These functions are documented on page 107.)

`\bool_gset_eq:cc`

`\bool_set:Nn` This function evaluates a boolean expression and assigns the first argument the meaning

`\bool_set:cn` `\c_true_bool` or `\c_false_bool`. Again, we include some checking code. It is important

`\bool_gset:Nn` to evaluate the expression before applying the `\chardef` primitive, because that primitive

`\bool_gset:cn` sets the left-hand side to `\scan_stop:` before looking for the right-hand side.

9595 `\cs_new_protected:Npn \bool_set:Nn #1#2`
 9596 `{`
 9597 `\exp_last_unbraced:NNNf`
 9598 `\tex_chardef:D #1 = { \bool_if_p:n {#2} }`
 9599 `}`
 9600 `\cs_new_protected:Npn \bool_gset:Nn #1#2`
 9601 `{`
 9602 `\exp_last_unbraced:NNNNf`
 9603 `\tex_global:D \tex_chardef:D #1 = { \bool_if_p:n {#2} }`
 9604 `}`
 9605 `\cs_generate_variant:Nn \bool_set:Nn { c }`
 9606 `\cs_generate_variant:Nn \bool_gset:Nn { c }`

(End definition for `\bool_set:Nn` and `\bool_gset:Nn`. These functions are documented on page 107.)

14.4 Internal auxiliaries

`\q__bool_recursion_tail` Internal recursion quarks.

`\q__bool_recursion_stop` 9607 `\quark_new:N \q__bool_recursion_tail`
 9608 `\quark_new:N \q__bool_recursion_stop`

(End definition for `\q__bool_recursion_tail` and `\q__bool_recursion_stop`.)

`__bool_use_i_delimit_by_q_recursion_stop:nw` Functions to gobble up to a quark.

9609 `\cs_new:Npn __bool_use_i_delimit_by_q_recursion_stop:nw`
 9610 `#1 #2 \q__bool_recursion_stop {#1}`

(End definition for `__bool_use_i_delimit_by_q_recursion_stop:nw`.)

`__bool_if_recursion_tail_stop_do:nn` Functions to query recursion quarks.

9611 `__kernel_quark_new_test:N __bool_if_recursion_tail_stop_do:nn`

(End definition for `__bool_if_recursion_tail_stop_do:nn`.)

`\bool_if_p:N` Straight forward here. We could optimize here if we wanted to as the boolean can just be input directly.

```

\bool_if_p:c
\bool_if:N $\underline{TF}$  9612 \prg_new_conditional:Npnn \bool_if:N #1 { p , T , F , TF }
\bool_if:c $\underline{TF}$  9613 {
9614     \if_bool:N #1
9615     \prg_return_true:
9616     \else:
9617     \prg_return_false:
9618     \fi:
9619 }
9620 \prg_generate_conditional_variant:Nnn \bool_if:N { c } { p , T , F , TF }

```

(End definition for `\bool_if:N \underline{TF}` . This function is documented on page 107.)

`\bool_show:n` Show the truth value of the boolean, as true or false.

```

\bool_log:n 9621 \cs_new_protected:Npn \bool_show:n
\__bool_to_str:n 9622 { \msg_show_eval:Nn \__bool_to_str:n }
9623 \cs_new_protected:Npn \bool_log:n
9624 { \msg_log_eval:Nn \__bool_to_str:n }
9625 \cs_new:Npn \__bool_to_str:n #1
9626 { \bool_if:nTF {#1} { true } { false } }

```

(End definition for `\bool_show:n`, `\bool_log:n`, and `__bool_to_str:n`. These functions are documented on page 107.)

`\bool_show:N` Show the truth value of the boolean, as true or false.

```

\bool_show:c 9627 \cs_new_protected:Npn \bool_show:N { \__bool_show:NN \tl_show:n }
\bool_log:N 9628 \cs_generate_variant:Nn \bool_show:N { c }
\bool_log:c 9629 \cs_new_protected:Npn \bool_log:N { \__bool_show:NN \tl_log:n }
\__bool_show:NN 9630 \cs_generate_variant:Nn \bool_log:N { c }
9631 \cs_new_protected:Npn \__bool_show:NN #1#2
9632 {
9633     \__kernel_chk_defined:NT #2
9634     { \exp_args:Nx #1 { \token_to_str:N #2 = \__bool_to_str:n {#2} } }
9635 }

```

(End definition for `\bool_show:N`, `\bool_log:N`, and `__bool_show:NN`. These functions are documented on page 107.)

`\l_tmpa_bool` A few booleans just if you need them.

```

\l_tmpb_bool 9636 \bool_new:N \l_tmpa_bool
\g_tmpa_bool 9637 \bool_new:N \l_tmpb_bool
\g_tmpb_bool 9638 \bool_new:N \g_tmpa_bool
9639 \bool_new:N \g_tmpb_bool

```

(End definition for `\l_tmpa_bool` and others. These variables are documented on page 108.)

`\bool_if_exist_p:N` Copies of the cs functions defined in l3basics.

```

\bool_if_exist_p:c 9640 \prg_new_eq_conditional:NNn \bool_if_exist:N \cs_if_exist:N
\bool_if_exist:N $\underline{TF}$  9641 { TF , T , F , p }
\bool_if_exist:c $\underline{TF}$  9642 \prg_new_eq_conditional:NNn \bool_if_exist:c \cs_if_exist:c
9643 { TF , T , F , p }

```

(End definition for `\bool_if_exist:N \underline{TF}` . This function is documented on page 108.)

14.5 Boolean expressions

`\bool_if_p:n` Evaluating the truth value of a list of predicates is done using an input syntax somewhat similar to the one found in other programming languages with (and) for grouping, ! for logical “Not”, && for logical “And” and || for logical “Or”. However, they perform eager evaluation. We shall use the terms Not, And, Or, Open and Close for these operations.

`\bool_if:nTF`

Any expression is terminated by a Close operation. Evaluation happens from left to right in the following manner using a GetNext function:

- If an Open is seen, start evaluating a new expression using the Eval function and call GetNext again.
- If a Not is seen, remove the ! and call a GetNext function with the logic reversed.
- If none of the above, reinsert the token found (this is supposed to be a predicate function) in front of an Eval function, which evaluates it to the boolean value $\langle true \rangle$ or $\langle false \rangle$.

The Eval function then contains a post-processing operation which grabs the instruction following the predicate. This is either And, Or or Close. In each case the truth value is used to determine where to go next. The following situations can arise:

$\langle true \rangle$ **And** Current truth value is true, logical And seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

$\langle false \rangle$ **And** Current truth value is false, logical And seen, stop using the values of predicates within this sub-expression until the next Close. Then return $\langle false \rangle$.

$\langle true \rangle$ **Or** Current truth value is true, logical Or seen, stop using the values of predicates within this sub-expression until the nearest Close. Then return $\langle true \rangle$.

$\langle false \rangle$ **Or** Current truth value is false, logical Or seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

$\langle true \rangle$ **Close** Current truth value is true, Close seen, return $\langle true \rangle$.

$\langle false \rangle$ **Close** Current truth value is false, Close seen, return $\langle false \rangle$.

```

9644 \prg_new_conditional:Npnn \bool_if:n #1 { T , F , TF }
9645 {
9646   \if_predicate:w \bool_if_p:n {#1}
9647   \prg_return_true:
9648   \else:
9649     \prg_return_false:
9650   \fi:
9651 }
```

(End definition for `\bool_if:nTF`. This function is documented on page 109.)

`\bool_if_p:n` To speed up the case of a single predicate, f-expand and check whether the result is one token (possibly surrounded by spaces), which must be `\c_true_bool` or `\c_false_bool`. We use a version of `\tl_if_single:nTF` optimized for speed since we know that an empty #1 is an error. The auxiliary `__bool_if_p_aux:w` removes the trailing parenthesis and gets rid of any space. For the general case, first issue a `\group_align_safe_begin:` as we are using && as syntax shorthand for the And operation and we need to hide it for

`__bool_if_p:n`

`__bool_if_p_aux:w`

TeX. This group is closed after `__bool_get_next:NN` returns `\c_true_bool` or `\c_false_bool`. That function requires the trailing parenthesis to know where the expression ends.

```

9652 \cs_new:Npn \bool_if_p:n { \exp_args:Nf \__bool_if_p:n }
9653 \cs_new:Npn \__bool_if_p:n #1
9654 {
9655   \tl_if_empty:oT { \use_none:nn #1 . } { \__bool_if_p_aux:w }
9656   \group_align_safe_begin:
9657   \exp_after:wN
9658   \group_align_safe_end:
9659   \exp:w \exp_end_continue_f:w % (
9660   \__bool_get_next:NN \use_i:nnnn #1 )
9661 }
9662 \cs_new:Npn \__bool_if_p_aux:w #1 \use_i:nnnn #2#3 {#2}

```

(End definition for `\bool_if_p:n`, `__bool_if_p:n`, and `__bool_if_p_aux:w`. This function is documented on page 109.)

`__bool_get_next:NN` The GetNext operation. Its first argument is `\use_i:nnnn`, `\use_ii:nnnn`, `\use_iii:nnnn`, or `\use_iv:nnnn` (we call these “states”). In the first state, this function eventually expand to the truth value `\c_true_bool` or `\c_false_bool` of the expression which follows until the next unmatched closing parenthesis. For instance “`__bool_get_next:NN \use_i:nnnn \c_true_bool && \c_true_bool)`” (including the closing parenthesis) expands to `\c_true_bool`. In the second state (after a `!`) the logic is reversed. We call these two states “normal” and the next two “skipping”. In the third state (after `\c_true_bool||`) it always returns `\c_true_bool`. In the fourth state (after `\c_false_bool&&`) it always returns `\c_false_bool` and also stops when encountering `||`, not only parentheses. This code itself is a switch: if what follows is neither `!` nor `(`, we assume it is a predicate.

```

9663 \cs_new:Npn \__bool_get_next:NN #1#2
9664 {
9665   \use:c
9666   {
9667     __bool_
9668     \if_meaning:w !#2 ! \else: \if_meaning:w (#2 ( \else: p \fi: \fi:
9669     :Nw
9670   }
9671   #1 #2
9672 }

```

(End definition for `__bool_get_next:NN`.)

`__bool_!:Nw` The Not operation reverses the logic: it discards the `!` token and calls the GetNext operation with the appropriate first argument. Namely the first and second states are interchanged, but after `\c_true_bool||` or `\c_false_bool&&` the `!` is ignored.

```

9673 \cs_new:cpn { __bool_!:Nw } #1#2
9674 {
9675   \exp_after:wN \__bool_get_next:NN
9676   #1 \use_ii:nnnn \use_i:nnnn \use_iii:nnnn \use_iv:nnnn
9677 }

```

(End definition for `__bool_!:Nw`.)

`__bool_(:Nw` The Open operation starts a sub-expression after discarding the open parenthesis. This is done by calling `GetNext` (which eventually discards the corresponding closing parenthesis), with a post-processing step which looks for And, Or or Close after the group.

```

9678 \cs_new:cpn { __bool_(:Nw } #1#2
9679 {
9680   \exp_after:wN \__bool_choose:NNN \exp_after:wN #1
9681   \int_value:w \__bool_get_next:NN \use_i:nnnn
9682 }

```

(End definition for `__bool_(:Nw`.)

`__bool_p:Nw` If what follows `GetNext` is neither `!` nor `(`, evaluate the predicate using the primitive `\int_value:w`. The canonical `true` and `false` values have numerical values 1 and 0 respectively. Look for And, Or or Close afterwards.

```

9683 \cs_new:cpn { __bool_p:Nw } #1
9684 { \exp_after:wN \__bool_choose:NNN \exp_after:wN #1 \int_value:w }

```

(End definition for `__bool_p:Nw`.)

`__bool_choose:NNN` The arguments are `#1`: a function such as `\use_i:nnnn`, `#2`: 0 or 1 encoding the current truth value, `#3`: the next operation, And, Or or Close. We distinguish three cases according to a combination of `#1` and `#2`. Case 2 is when `#1` is `\use_iii:nnnn` (state 3), namely after `\c_true_bool ||`. Case 1 is when `#1` is `\use_i:nnnn` and `#2` is `true` or when `#1` is `\use_ii:nnnn` and `#2` is `false`, for instance for `!\c_false_bool`. Case 0 includes the same with `true/false` interchanged and the case where `#1` is `\use_iv:nnnn` namely after `\c_false_bool &&`.

`__bool_|_0:` When seeing `)` the current subexpression is done, leave the appropriate boolean.
`__bool_|_1:` When seeing `&` in case 0 go into state 4, equivalent to having seen `\c_false_bool &&`.
`__bool_|_2:` In case 1, namely when the argument is `true` and we are in a normal state continue in the normal state 1. In case 2, namely when skipping alternatives in an Or, continue in the same state. When seeing `|` in case 0, continue in a normal state; in particular stop skipping for `\c_false_bool &&` because that binds more tightly than `||`. In the other two cases start skipping for `\c_true_bool ||`.

```

9685 \cs_new:Npn \__bool_choose:NNN #1#2#3
9686 {
9687   \use:c
9688   {
9689     __bool_ \token_to_str:N #3 _
9690     #1 #2 { \if_meaning:w 0 #2 1 \else: 0 \fi: } 2 0 :
9691   }
9692 }
9693 \cs_new:cpn { __bool_)_0: } { \c_false_bool }
9694 \cs_new:cpn { __bool_)_1: } { \c_true_bool }
9695 \cs_new:cpn { __bool_)_2: } { \c_true_bool }
9696 \cs_new:cpn { __bool_&_0: } & { \__bool_get_next:NN \use_iv:nnnn }
9697 \cs_new:cpn { __bool_&_1: } & { \__bool_get_next:NN \use_i:nnnn }
9698 \cs_new:cpn { __bool_&_2: } & { \__bool_get_next:NN \use_iii:nnnn }
9699 \cs_new:cpn { __bool_|_0: } | { \__bool_get_next:NN \use_i:nnnn }
9700 \cs_new:cpn { __bool_|_1: } | { \__bool_get_next:NN \use_iii:nnnn }
9701 \cs_new:cpn { __bool_|_2: } | { \__bool_get_next:NN \use_iii:nnnn }

```

(End definition for `__bool_choose:NNN` and others.)

\bool_lazy_all_p:n Go through the list of expressions, stopping whenever an expression is **false**. If the end
\bool_lazy_all:nTF is reached without finding any **false** expression, then the result is **true**.

```

\__bool_lazy_all:n
9702 \cs_new:Npn \bool_lazy_all_p:n #1
9703 { \__bool_lazy_all:n #1 \q_bool_recursion_tail \q_bool_recursion_stop }
9704 \prg_new_conditional:Npnn \bool_lazy_all:n #1 { T , F , TF }
9705 {
9706   \if_predicate:w \bool_lazy_all_p:n {#1}
9707   \prg_return_true:
9708   \else:
9709   \prg_return_false:
9710   \fi:
9711 }
9712 \cs_new:Npn \__bool_lazy_all:n #1
9713 {
9714   \__bool_if_recursion_tail_stop_do:nn {#1} { \c_true_bool }
9715   \bool_if:nF {#1}
9716   { \__bool_use_i_delimit_by_q_recursion_stop:nw { \c_false_bool } }
9717   \__bool_lazy_all:n
9718 }

```

(End definition for **\bool_lazy_all:nTF** and **__bool_lazy_all:n**. This function is documented on page 109.)

\bool_lazy_and_p:nn Only evaluate the second expression if the first is **true**. Note that #2 must be removed
\bool_lazy_and:nnTF as an argument, not just by skipping to the **\else:** branch of the conditional since #2 may contain unbalanced **TeX** conditionals.

```

9719 \prg_new_conditional:Npnn \bool_lazy_and:nn #1#2 { p , T , F , TF }
9720 {
9721   \if_predicate:w
9722   \bool_if:nTF {#1} { \bool_if_p:n {#2} } { \c_false_bool }
9723   \prg_return_true:
9724   \else:
9725   \prg_return_false:
9726   \fi:
9727 }

```

(End definition for **\bool_lazy_and:nnTF**. This function is documented on page 109.)

\bool_lazy_any_p:n Go through the list of expressions, stopping whenever an expression is **true**. If the end
\bool_lazy_any:nTF is reached without finding any **true** expression, then the result is **false**.

```

\__bool_lazy_any:n
9728 \cs_new:Npn \bool_lazy_any_p:n #1
9729 { \__bool_lazy_any:n #1 \q_bool_recursion_tail \q_bool_recursion_stop }
9730 \prg_new_conditional:Npnn \bool_lazy_any:n #1 { T , F , TF }
9731 {
9732   \if_predicate:w \bool_lazy_any_p:n {#1}
9733   \prg_return_true:
9734   \else:
9735   \prg_return_false:
9736   \fi:
9737 }
9738 \cs_new:Npn \__bool_lazy_any:n #1
9739 {
9740   \__bool_if_recursion_tail_stop_do:nn {#1} { \c_false_bool }
9741   \bool_if:nT {#1}

```



```

9742     { \_bool_use_i_delimit_by_q_recursion_stop:nw { \c_true_bool } }
9743     \_bool_lazy_any:n
9744 }

```

(End definition for `\bool_lazy_any:nTF` and `_bool_lazy_any:n`. This function is documented on page 110.)

`\bool_lazy_or_p:nn` Only evaluate the second expression if the first is false.

`\bool_lazy_or:nnTF`

```

9745 \prg_new_conditional:Npnn \bool_lazy_or:nn #1#2 { p , T , F , TF }
9746 {
9747   \if_predicate:w
9748     \bool_if:nTF {#1} { \c_true_bool } { \bool_if_p:n {#2} }
9749     \prg_return_true:
9750   \else:
9751     \prg_return_false:
9752   \fi:
9753 }

```

(End definition for `\bool_lazy_or:nnTF`. This function is documented on page 110.)

`\bool_not_p:n` The Not variant just reverses the outcome of `\bool_if_p:n`. Can be optimized but this is nice and simple and according to the implementation plan. Not even particularly useful to have it when the infix notation is easier to use.

```

9754 \cs_new:Npn \bool_not_p:n #1 { \bool_if_p:n { ! ( #1 ) } }

```

(End definition for `\bool_not_p:n`. This function is documented on page 110.)

`\bool_xor_p:nn` Exclusive or. If the boolean expressions have same truth value, return false, otherwise return true.

`\bool_xor:nnTF`

```

9755 \prg_new_conditional:Npnn \bool_xor:nn #1#2 { p , T , F , TF }
9756 {
9757   \bool_if:nT {#1} \reverse_if:N
9758   \if_predicate:w \bool_if_p:n {#2}
9759     \prg_return_true:
9760   \else:
9761     \prg_return_false:
9762   \fi:
9763 }

```

(End definition for `\bool_xor:nnTF`. This function is documented on page 110.)

14.6 Logical loops

`\bool_while_do:Nn` A while loop where the boolean is tested before executing the statement. The “while” version executes the code as long as the boolean is true; the “until” version executes the code as long as the boolean is false.

`\bool_while_do:cn`

`\bool_until_do:Nn`

`\bool_until_do:cn`

```

9764 \cs_new:Npn \bool_while_do:Nn #1#2
9765   { \bool_if:NT #1 { #2 \bool_while_do:Nn #1 {#2} } }
9766 \cs_new:Npn \bool_until_do:Nn #1#2
9767   { \bool_if:NF #1 { #2 \bool_until_do:Nn #1 {#2} } }
9768 \cs_generate_variant:Nn \bool_while_do:Nn { c }
9769 \cs_generate_variant:Nn \bool_until_do:Nn { c }

```

(End definition for `\bool_while_do:Nn` and `\bool_until_do:Nn`. These functions are documented on page 110.)

\bool_do_while:Nn A do-while loop where the body is performed at least once and the boolean is tested after executing the body. Otherwise identical to the above functions.

\bool_do_while:cn

```

9770 \cs_new:Npn \bool_do_while:Nn #1#2
9771 { #2 \bool_if:NT #1 { \bool_do_while:Nn #1 {#2} } }
9772 \cs_new:Npn \bool_do_until:Nn #1#2
9773 { #2 \bool_if:NF #1 { \bool_do_until:Nn #1 {#2} } }
9774 \cs_generate_variant:Nn \bool_do_while:Nn { c }
9775 \cs_generate_variant:Nn \bool_do_until:Nn { c }

```

(End definition for \bool_do_while:Nn and \bool_do_until:Nn. These functions are documented on page 110.)

\bool_while_do:nn Loop functions with the test either before or after the first body expansion.

\bool_do_while:nn

```

9776 \cs_new:Npn \bool_while_do:nn #1#2
9777 {
9778   \bool_if:nT {#1}
9779   {
9780     #2
9781     \bool_while_do:nn {#1} {#2}
9782   }
9783 }
9784 \cs_new:Npn \bool_do_while:nn #1#2
9785 {
9786   #2
9787   \bool_if:nT {#1} { \bool_do_while:nn {#1} {#2} }
9788 }
9789 \cs_new:Npn \bool_until_do:nn #1#2
9790 {
9791   \bool_if:nF {#1}
9792   {
9793     #2
9794     \bool_until_do:nn {#1} {#2}
9795   }
9796 }
9797 \cs_new:Npn \bool_do_until:nn #1#2
9798 {
9799   #2
9800   \bool_if:nF {#1} { \bool_do_until:nn {#1} {#2} }
9801 }

```

(End definition for \bool_while_do:nn and others. These functions are documented on page 111.)

14.7 Producing multiple copies

9802 <@@=prg>

\prg_replicate:nn This function uses a cascading csname technique by David Kastrup (who else :-)

The idea is to make the input 25 result in first adding five, and then 20 copies of the code to be replicated. The technique uses cascading csnames which means that we start building several csnames so we end up with a list of functions to be called in reverse order. This is important here (and other places) because it means that we can for instance make the function that inserts five copies of something to also hand down ten to the next function in line. This is exactly what happens here: in the example with 25 then the next function is the one that inserts two copies but it sees the ten copies handed

```

\__prg_replicate_0:n
\__prg_replicate_1:n
\__prg_replicate_2:n
\__prg_replicate_3:n
\__prg_replicate_4:n
\__prg_replicate_5:n
\__prg_replicate_6:n
\__prg_replicate_7:n
\__prg_replicate_8:n
\__prg_replicate_9:n
\__prg_replicate_first_0:n
\__prg_replicate_first_1:n
\__prg_replicate_first_2:n

```

down by the previous function. In order to avoid the last function to insert say, 100 copies of the original argument just to gobble them again we define separate functions to be inserted first. These functions also close the expansion of `\exp:w`, which ensures that `\prg_replicate:nn` only requires two steps of expansion.

This function has one flaw though: Since it constantly passes down ten copies of its previous argument it severely affects the main memory once you start demanding hundreds of thousands of copies. Now I don't think this is a real limitation for any ordinary use, and if necessary, it is possible to write `\prg_replicate:nn {1000} { \prg_replicate:nn {1000} {<code>} }`. An alternative approach is to create a string of `m's` with `\exp:w` which can be done with just four macros but that method has its own problems since it can exhaust the string pool. Also, it is considerably slower than what we use here so the few extra csnames are well spent I would say.

```

9803 \cs_new:Npn \prg_replicate:nn #1
9804 {
9805   \exp:w
9806   \exp_after:wN \__prg_replicate_first:N
9807   \int_value:w \int_eval:n {#1}
9808   \cs_end:
9809 }
9810 \cs_new:Npn \__prg_replicate:N #1
9811 { \cs:w \__prg_replicate_#1 :n \__prg_replicate:N }
9812 \cs_new:Npn \__prg_replicate_first:N #1
9813 { \cs:w \__prg_replicate_first_#1 :n \__prg_replicate:N }

```

Then comes all the functions that do the hard work of inserting all the copies. The first function takes `:n` as a parameter.

```

9814 \cs_new:Npn \__prg_replicate_ :n #1 { \cs_end: }
9815 \cs_new:cpn { __prg_replicate_0:n } #1
9816 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} }
9817 \cs_new:cpn { __prg_replicate_1:n } #1
9818 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1 }
9819 \cs_new:cpn { __prg_replicate_2:n } #1
9820 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1 }
9821 \cs_new:cpn { __prg_replicate_3:n } #1
9822 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1 }
9823 \cs_new:cpn { __prg_replicate_4:n } #1
9824 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1 }
9825 \cs_new:cpn { __prg_replicate_5:n } #1
9826 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1 }
9827 \cs_new:cpn { __prg_replicate_6:n } #1
9828 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1 }
9829 \cs_new:cpn { __prg_replicate_7:n } #1
9830 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1 }
9831 \cs_new:cpn { __prg_replicate_8:n } #1
9832 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1#1 }
9833 \cs_new:cpn { __prg_replicate_9:n } #1
9834 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1#1#1 }

```

Users shouldn't ask for something to be replicated once or even not at all but...

```

9835 \cs_new:cpn { __prg_replicate_first_-:n } #1
9836 {
9837   \exp_end:
9838   \__kernel_msg_expandable_error:nn { kernel } { negative-replication }

```

```

9839 }
9840 \cs_new:cpn { __prg_replicate_first_0:n } #1 { \exp_end: }
9841 \cs_new:cpn { __prg_replicate_first_1:n } #1 { \exp_end: #1 }
9842 \cs_new:cpn { __prg_replicate_first_2:n } #1 { \exp_end: #1#1 }
9843 \cs_new:cpn { __prg_replicate_first_3:n } #1 { \exp_end: #1#1#1 }
9844 \cs_new:cpn { __prg_replicate_first_4:n } #1 { \exp_end: #1#1#1#1 }
9845 \cs_new:cpn { __prg_replicate_first_5:n } #1 { \exp_end: #1#1#1#1#1 }
9846 \cs_new:cpn { __prg_replicate_first_6:n } #1 { \exp_end: #1#1#1#1#1#1 }
9847 \cs_new:cpn { __prg_replicate_first_7:n } #1 { \exp_end: #1#1#1#1#1#1#1 }
9848 \cs_new:cpn { __prg_replicate_first_8:n } #1 { \exp_end: #1#1#1#1#1#1#1#1 }
9849 \cs_new:cpn { __prg_replicate_first_9:n } #1
9850 { \exp_end: #1#1#1#1#1#1#1#1#1 }

```

(End definition for `\prg_replicate:nn` and others. This function is documented on page 111.)

14.8 Detecting TeX's mode

`\mode_if_vertical_p:` For testing vertical mode. Strikes me here on the bus with David, that as long as we are just talking about returning true and false states, we can just use the primitive conditionals for this and gobbling the `\exp_end:` in the input stream. However this requires knowledge of the implementation so we keep things nice and clean and use the return statements.

```

9851 \prg_new_conditional:Npnn \mode_if_vertical: { p , T , F , TF }
9852 { \if_mode_vertical: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for `\mode_if_vertical:TF`. This function is documented on page 112.)

`\mode_if_horizontal_p:` For testing horizontal mode.

```

\mode_if_horizontal:TF
9853 \prg_new_conditional:Npnn \mode_if_horizontal: { p , T , F , TF }
9854 { \if_mode_horizontal: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for `\mode_if_horizontal:TF`. This function is documented on page 111.)

`\mode_if_inner_p:` For testing inner mode.

```

\mode_if_inner:TF
9855 \prg_new_conditional:Npnn \mode_if_inner: { p , T , F , TF }
9856 { \if_mode_inner: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for `\mode_if_inner:TF`. This function is documented on page 111.)

`\mode_if_math_p:` For testing math mode. At the beginning of an alignment cell, this should be used only inside a non-expandable function.

```

\mode_if_math:TF
9857 \prg_new_conditional:Npnn \mode_if_math: { p , T , F , TF }
9858 { \if_mode_math: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for `\mode_if_math:TF`. This function is documented on page 111.)

14.9 Internal programming functions

`\group_align_safe_begin:` `\group_align_safe_end:` T_EX’s alignment structures present many problems. As Knuth says himself in *T_EX: The Program*: “It’s sort of a miracle whenever `\halign` or `\valign` work, [...]” One problem relates to commands that internally issues a `\cr` but also peek ahead for the next character for use in, say, an optional argument. If the next token happens to be a `&` with category code 4 we get some sort of weird error message because the underlying `\futurelet` stores the token at the end of the alignment template. This could be a `&_4` giving a message like `! Misplaced \cr.` or even worse: it could be the `\endtemplate` token causing even more trouble! To solve this we have to open a special group so that T_EX still thinks it’s on safe ground but at the same time we don’t want to introduce any brace group that may find its way to the output. The following functions help with this by using code documented only in Appendix D of *The T_EXbook*... We place the `\if_false: { \fi:` part at that place so that the successive expansions of `\group_align_safe_begin/end:` are always brace balanced.

```

9859 \cs_new:Npn \group_align_safe_begin:
9860   { \if_int_compare:w \if_false: { \fi: ‘} = \c_zero_int \fi: }
9861 \cs_new:Npn \group_align_safe_end:
9862   { \if_int_compare:w ‘{ = \c_zero_int } \fi: }

```

(End definition for `\group_align_safe_begin:` and `\group_align_safe_end:`. These functions are documented on page 113.)

`\g__kernel_prg_map_int` A nesting counter for mapping.

```

9863 \int_new:N \g__kernel_prg_map_int

```

(End definition for `\g__kernel_prg_map_int:`.)

`\prg_break_point:Nn` `\prg_map_break:Nn` These are defined in `l3basics`, as they are needed “early”. This is just a reminder that is the case!

(End definition for `\prg_break_point:Nn` and `\prg_map_break:Nn`. These functions are documented on page 112.)

`\prg_break_point:` `\prg_break:` `\prg_break:n` Also done in `l3basics` as in format mode these are needed within `l3alloc`.

(End definition for `\prg_break_point:`, `\prg_break:`, and `\prg_break:n`. These functions are documented on page 113.)

```

9864 </initex | package>

```

15 l3sys implementation

```

9865 <@@=sys>

```

15.1 Kernel code

```

9866 <*initex | package>

```

15.1.1 Detecting the engine

`__sys_const:nn` Set the T, F, TF, p forms of #1 to be constants equal to the result of evaluating the boolean expression #2.

```

9867 \cs_new_protected:Npn \__sys_const:nn #1#2
9868   {
9869     \bool_if:nTF {#2}

```

```

9870     {
9871         \cs_new_eq:cN { #1 :T } \use:n
9872         \cs_new_eq:cN { #1 :F } \use_none:n
9873         \cs_new_eq:cN { #1 :TF } \use_i:nn
9874         \cs_new_eq:cN { #1 _p: } \c_true_bool
9875     }
9876     {
9877         \cs_new_eq:cN { #1 :T } \use_none:n
9878         \cs_new_eq:cN { #1 :F } \use:n
9879         \cs_new_eq:cN { #1 :TF } \use_ii:nn
9880         \cs_new_eq:cN { #1 _p: } \c_false_bool
9881     }
9882 }

```

(End definition for `_sys_const:nn`.)

`\sys_if_engine luatex_p:` Set up the engine tests on the basis exactly one test should be true. Mainly a case of looking for the appropriate marker primitive.

```

\sys_if_engine luatex:TF
\sys_if_engine pdftex_p:
\sys_if_engine pdftex:TF
\sys_if_engine ptex_p:
\sys_if_engine ptex:TF
\sys_if_engine uptex_p:
\sys_if_engine uptex:TF
\sys_if_engine xetex_p:
\sys_if_engine xetex:TF
\c_sys_engine_str
9883 \str_const:Nx \c_sys_engine_str
9884 {
9885     \cs_if_exist:NT \tex luatexversion:D { luatex }
9886     \cs_if_exist:NT \tex pdftexversion:D { pdftex }
9887     \cs_if_exist:NT \tex kanjiskip:D
9888     {
9889         \cs_if_exist:NTF \tex enableecjktoken:D
9890         { uptex }
9891         { ptex }
9892     }
9893     \cs_if_exist:NT \tex XeTeXversion:D { xetex }
9894 }
9895 \tl_map_inline:nn { { luatex } { pdftex } { ptex } { uptex } { xetex } }
9896 {
9897     \_sys_const:nn { sys_if_engine_ #1 }
9898     { \str_if_eq_p:Vn \c_sys_engine_str {#1} }
9899 }

```

(End definition for `\sys_if_engine luatex:TF` and others. These functions are documented on page 114.)

15.1.2 Randomness

This candidate function is placed there because `\sys_if_rand_exist:TF` is used in `l3fp-rand`.

`\sys_if_rand_exist_p:` Currently, randomness exists under pdfTeX, LuaTeX, pTeX and upTeX.

```

\sys_if_rand_exist:TF
9900 \_sys_const:nn { sys_if_rand_exist }
9901 { \cs_if_exist_p:N \tex uniformdeviate:D }

```

(End definition for `\sys_if_rand_exist:TF`. This function is documented on page 267.)

15.1.3 Platform

`\sys_if_platform_unix_p:` Setting these up requires the file module (file lookup), so is actually implemented there.

```

\sys_if_platform_unix:TF
\sys_if_platform_windows_p:
\sys_if_platform_windows:TF
\c_sys_platform_str

```

(End definition for `\sys_if_platform_unix:TF`, `\sys_if_platform_windows:TF`, and `\c_sys_platform-str`. These functions are documented on page 115.)

15.1.4 Configurations

`\sys_load_backend:n` Loading the backend code is pretty simply: check that the backend is valid, then load it up.

```

\__sys_load_backend_check:N
\c_sys_backend_str
9902 \cs_new_protected:Npn \sys_load_backend:n #1
9903 {
9904   \sys_finalise:
9905   \str_if_exist:NTF \c_sys_backend_str
9906   {
9907     \str_if_eq:VnF \c_sys_backend_str {#1}
9908     { \__kernel_msg_error:nn { sys } { backend-set } }
9909   }
9910   {
9911     \tl_if_blank:nF {#1}
9912     { \tl_set:Nn \g__sys_backend_tl {#1} }
9913     \__sys_load_backend_check:N \g__sys_backend_tl
9914     \str_const:Nx \c_sys_backend_str { \g__sys_backend_tl }
9915     \__kernel_sys_configuration_load:n
9916     { l3backend- \c_sys_backend_str }
9917   }
9918 }
9919 \cs_new_protected:Npn \__sys_load_backend_check:N #1
9920 {
9921   \sys_if_engine_xetex:TF
9922   {
9923     \str_case:VnF #1
9924     {
9925       { dvisvgm } { }
9926       { xdvipdfmx } { }
9927     }
9928     {
9929       \__kernel_msg_error:nxxx { sys } { wrong-backend }
9930       #1 { xdvipdfmx }
9931       \tl_gset:Nn #1 { xdvipdfmx }
9932     }
9933   }
9934   {
9935     \sys_if_output_pdf:TF
9936     {
9937       \str_if_eq:VnF #1 { pdfmode }
9938       {
9939         \__kernel_msg_error:nxxx { sys } { wrong-backend }
9940         #1 { pdfmode }
9941         \tl_gset:Nn #1 { pdfmode }
9942       }
9943     }
9944     {
9945       \str_case:VnF #1
9946       {
9947         { dvipdfmx } { }
9948         { dvips } { }
9949         { dvisvgm } { }
9950       }
9951       {

```

```

9952         \__kernel_msg_error:nxxx { sys } { wrong-backend }
9953         #1 { dvips }
9954         \tl_gset:Nn #1 { dvips }
9955     }
9956 }
9957 }
9958 }

```

(End definition for `\sys_load_backend:n`, `__sys_load_backend_check:N`, and `\c_sys_backend_str`. These functions are documented on page 117.)

```

\g__sys_debug_bool
\g__sys_deprecation_bool
9959 \bool_new:N \g__sys_debug_bool
9960 \bool_new:N \g__sys_deprecation_bool

```

(End definition for `\g__sys_debug_bool` and `\g__sys_deprecation_bool`.)

`\sys_load_debug:` Simple.
`\sys_load_deprecation:`

```

9961 \cs_new_protected:Npn \sys_load_debug:
9962 {
9963     \bool_if:NF \g__sys_debug_bool
9964     { \__kernel_sys_configuration_load:n { l3debug } }
9965     \bool_gset_true:N \g__sys_debug_bool
9966 }
9967 \cs_new_protected:Npn \sys_load_deprecation:
9968 {
9969     \bool_if:NF \g__sys_deprecation_bool
9970     { \__kernel_sys_configuration_load:n { l3deprecation } }
9971     \bool_gset_true:N \g__sys_deprecation_bool
9972 }

```

(End definition for `\sys_load_debug:` and `\sys_load_deprecation:`. These functions are documented on page 117.)

15.1.5 Access to the shell

```

\l__sys_internal_tl
9973 \tl_new:N \l__sys_internal_tl

```

(End definition for `\l__sys_internal_tl`.)

`\c__sys_marker_tl` The same idea as the marker for rescanning token lists.

```

9974 \tl_const:Nx \c__sys_marker_tl { : \token_to_str:N : }

```

(End definition for `\c__sys_marker_tl`.)

`\sys_get_shell:nnN`TF Setting using a shell is at this level just a slightly specialised file operation, with an additional check for quotes, as these are not supported.

```

\sys_get_shell:nnN
\__sys_get:nnN
\__sys_get_do:Nw
9975 \cs_new_protected:Npn \sys_get_shell:nnN #1#2#3
9976 {
9977     \sys_get_shell:nnNF {#1} {#2} #3
9978     { \tl_set:Nn #3 { \q_no_value } }
9979 }
9980 \prg_new_protected_conditional:Npnn \sys_get_shell:nnN #1#2#3 { T , F , TF }
9981 {

```



```

9982 \sys_if_shell:TF
9983 { \exp_args:No \__sys_get:nnN { \tl_to_str:n {#1} } {#2} #3 }
9984 { \prg_return_false: }
9985 }
9986 \cs_new_protected:Npn \__sys_get:nnN #1#2#3
9987 {
9988   \tl_if_in:nnTF {#1} { " }
9989   {
9990     \__kernel_msg_error:nnx
9991     { kernel } { quote-in-shell } {#1}
9992     \prg_return_false:
9993   }
9994   {
9995     \group_begin:
9996     \if_false: { \fi:
9997       \int_set_eq:NN \tex_tracingnesting:D \c_zero_int
9998       \exp_args:No \tex_everyeof:D { \c__sys_marker_tl }
9999       #2 \scan_stop:
10000       \exp_after:wN \__sys_get_do:Nw
10001       \exp_after:wN #3
10002       \exp_after:wN \prg_do_nothing:
10003       \tex_input:D | "#1" \scan_stop:
10004       \if_false: } \fi:
10005       \prg_return_true:
10006     }
10007   }
10008 \exp_args:Nno \use:nn
10009 { \cs_new_protected:Npn \__sys_get_do:Nw #1#2 }
10010 { \c__sys_marker_tl }
10011 {
10012   \group_end:
10013   \tl_set:No #1 {#2}
10014 }

```

(End definition for `\sys_get_shell:nnNTF` and others. These functions are documented on page 116.)

`\c__sys_shell_stream_int` This is not needed for LuaTeX: shell escape there isn't done using a T_EX interface.

```

10015 \sys_if_engine luatex:F
10016 { \int_const:Nn \c__sys_shell_stream_int { 18 } }

```

(End definition for `\c__sys_shell_stream_int`.)

`\sys_shell_now:n` Execute commands through shell escape immediately.

```

10017 \sys_if_engine luatex:TF
10018 {
10019   \cs_new_protected:Npn \sys_shell_now:n #1
10020   {
10021     \lua_now:e
10022     { l3kernel.shellescape(" \lua_escape:e { \tl_to_str:n {#1} } ") }
10023   }
10024 }
10025 {
10026   \cs_new_protected:Npn \sys_shell_now:n #1
10027   { \iow_now:Nn \c__sys_shell_stream_int {#1} }
10028 }

```

```
10029 \cs_generate_variant:Nn \sys_shell_now:n { x }
```

(End definition for `\sys_shell_now:n`. This function is documented on page 116.)

`\sys_shell_shipout:n` Execute commands through shell escape at shipout.

```
10030 \sys_if_engine luatex:TF
10031 {
10032   \cs_new_protected:Npn \sys_shell_shipout:n #1
10033   {
10034     \lua_shipout_e:n
10035     { l3kernel.shellescape(" \lua_escape:e { \tl_to_str:n {#1} } ") }
10036   }
10037 }
10038 {
10039   \cs_new_protected:Npn \sys_shell_shipout:n #1
10040   { \iow_shipout:Nn \c__sys_shell_stream_int {#1} }
10041 }
10042 \cs_generate_variant:Nn \sys_shell_shipout:n { x }
```

(End definition for `\sys_shell_shipout:n`. This function is documented on page 116.)

15.2 Dynamic (every job) code

```
\sys_everyjob:
\__sys_everyjob:n
\g__sys_everyjob_tl
10043 \cs_new_protected:Npn \sys_everyjob:
10044 {
10045   \tl_use:N \g__sys_everyjob_tl
10046   \tl_gclear:N \g__sys_everyjob_tl
10047 }
10048 \cs_new_protected:Npn \__sys_everyjob:n #1
10049 { \tl_gput_right:Nn \g__sys_everyjob_tl {#1} }
10050 \tl_new:N \g__sys_everyjob_tl
```

(End definition for `\sys_everyjob:`, `__sys_everyjob:n`, and `\g__sys_everyjob_tl`. This function is documented on page ??.)

15.2.1 The name of the job

`\c_sys_jobname_str` Inherited from the L^AT_EX3 name for the primitive. This *has* to be the primitive as it's set in `\everyjob`. If the user does

```
pdflatex \input some-file-name
```

then `\everyjob` is inserted *before* `\jobname` is changed from `texput`, and thus we would have the wrong result.

```
10051 \__sys_everyjob:n
10052 { \cs_new_eq:NN \c_sys_jobname_str \tex_jobname:D }
```

(End definition for `\c_sys_jobname_str`. This variable is documented on page 114.)

15.2.2 Time and date

`\c_sys_minute_int` `\c_sys_hour_int` `\c_sys_day_int` `\c_sys_month_int` `\c_sys_year_int` Copies of the information provided by T_EX. There is a lot of defensive code in package mode: someone may have moved the primitives, and they can only be recovered if we have `\primitive` and it is working correctly. For IniT_EX of course that is all redundant but does no harm.

```

10053 \__sys_everyjob:n
10054 {
10055   \group_begin:
10056   \cs_set:Npn \__sys_tmp:w #1
10057   {
10058     \str_if_eq:eeTF { \cs_meaning:N #1 } { \token_to_str:N #1 }
10059     { #1 }
10060     {
10061       \cs_if_exist:NTF \tex_primitive:D
10062       {
10063         \bool_lazy_and:nnTF
10064         { \sys_if_engine_xetex_p: }
10065         {
10066           \int_compare_p:nNn
10067           { \exp_after:wN \use_none:n \tex_XeTeXrevision:D }
10068           < { 99999 }
10069         }
10070         { 0 }
10071         { \tex_primitive:D #1 }
10072       }
10073       { 0 }
10074     }
10075   }
10076   \int_const:Nn \c_sys_minute_int
10077   { \int_mod:nn { \__sys_tmp:w \time } { 60 } }
10078   \int_const:Nn \c_sys_hour_int
10079   { \int_div_truncate:nn { \__sys_tmp:w \time } { 60 } }
10080   \int_const:Nn \c_sys_day_int { \__sys_tmp:w \day }
10081   \int_const:Nn \c_sys_month_int { \__sys_tmp:w \month }
10082   \int_const:Nn \c_sys_year_int { \__sys_tmp:w \year }
10083   \group_end:
10084 }

```

(End definition for `\c_sys_minute_int` and others. These variables are documented on page 114.)

15.2.3 Random numbers

`\sys_rand_seed:` Unpack the primitive. When random numbers are not available, we return zero after an error (and incidentally make sure the number of expansions needed is the same as with random numbers available).

```

10085 \__sys_everyjob:n
10086 {
10087   \sys_if_rand_exist:TF
10088   { \cs_new:Npn \sys_rand_seed: { \tex_the:D \tex_randomseed:D } }
10089   {
10090     \cs_new:Npn \sys_rand_seed:
10091     {
10092       \int_value:w

```

```

10093         \__kernel_msg_expandable_error:nnn { kernel } { fp-no-random }
10094         { \sys_rand_seed: }
10095         \c_zero_int
10096     }
10097 }
10098 }

```

(End definition for `\sys_rand_seed`:. This function is documented on page 115.)

`\sys_gset_rand_seed:n` The primitive always assigns the seed globally.

```

10099 \__sys_everyjob:n
10100 {
10101     \sys_if_rand_exist:TF
10102     {
10103         \cs_new_protected:Npn \sys_gset_rand_seed:n #1
10104         { \tex_setrandomseed:D \int_eval:n {#1} \exp_stop_f: }
10105     }
10106     {
10107         \cs_new_protected:Npn \sys_gset_rand_seed:n #1
10108         {
10109             \__kernel_msg_error:nnn { kernel } { fp-no-random }
10110             { \sys_gset_rand_seed:n {#1} }
10111         }
10112     }
10113 }

```

(End definition for `\sys_gset_rand_seed:n`. This function is documented on page 115.)

15.2.4 Access to the shell

`\c_sys_shell_escape_int` Expose the engine's shell escape status to the user.

```

10114 \__sys_everyjob:n
10115 {
10116     \int_const:Nn \c_sys_shell_escape_int
10117     {
10118         \sys_if_engine luatex:TF
10119         {
10120             \tex_directlua:D
10121             { \tex_sprint(status.shell_escape~or~os.execute()) }
10122         }
10123         { \tex_shellescape:D }
10124     }
10125 }

```

(End definition for `\c_sys_shell_escape_int`. This variable is documented on page 116.)

`\sys_if_shell_p:` Performs a check for whether shell escape is enabled. The first set of functions returns true if either of restricted or unrestricted shell escape is enabled, while the other two sets of functions return true in only one of these two cases.

`\sys_if_shell:` TF

`\sys_if_shell_unrestricted_p:`

`\sys_if_shell_unrestricted:` TF

`\sys_if_shell_restricted_p:`

`\sys_if_shell_restricted:` TF

```

10126 \__sys_everyjob:n
10127 {
10128     \__sys_const:nn { sys_if_shell }
10129     { \int_compare_p:nNn \c_sys_shell_escape_int > 0 }
10130     \__sys_const:nn { sys_if_shell_unrestricted }

```

```

10131     { \int_compare_p:nNn \c_sys_shell_escape_int = 1 }
10132     \__sys_const:nn { sys_if_shell_restricted }
10133     { \int_compare_p:nNn \c_sys_shell_escape_int = 2 }
10134 }

```

(End definition for `\sys_if_shell:TF`, `\sys_if_shell_unrestricted:TF`, and `\sys_if_shell_restricted:TF`. These functions are documented on page 116.)

15.2.5 Held over from l3file

`\g_file_curr_name_str` See comments about `\c_sys_jobname_str`: here, as soon as there is file input/output, things get “tided up”.

```

10135 \__sys_everyjob:n
10136 { \cs_gset_eq:NN \g_file_curr_name_str \tex_jobname:D }

```

(End definition for `\g_file_curr_name_str`. This variable is documented on page 163.)

15.3 Last-minute code

`\sys_finalise:` A simple hook to finalise the system-dependent layer. This is forced by the backend loader, which is forced by the main loader, so we do not need to include that here.

```

\__sys_finalise:n
\g__sys_finalise_tl
10137 \cs_new_protected:Npn \sys_finalise:
10138 {
10139     \sys_everyjob:
10140     \tl_use:N \g__sys_finalise_tl
10141     \tl_gclear:N \g__sys_finalise_tl
10142 }
10143 \cs_new_protected:Npn \__sys_finalise:n #1
10144 { \tl_gput_right:Nn \g__sys_finalise_tl {#1} }
10145 \tl_new:N \g__sys_finalise_tl

```

(End definition for `\sys_finalise:`, `__sys_finalise:n`, and `\g__sys_finalise_tl`. This function is documented on page 117.)

15.3.1 Detecting the output

`\sys_if_output_dvi_p:` This is a simple enough concept: the two views here are complementary.

```

\sys_if_output_dvi:TF
\sys_if_output_pdf_p:
\sys_if_output_pdf:TF
\c_sys_output_str
10146 \__sys_finalise:n
10147 {
10148     \str_const:Nx \c_sys_output_str
10149     {
10150         \int_compare:nNnTF
10151         { \cs_if_exist_use:NF \tex_pdfoutput:D { 0 } } > { 0 }
10152         { pdf }
10153         { dvi }
10154     }
10155     \__sys_const:nn { sys_if_output_dvi }
10156     { \str_if_eq_p:Vn \c_sys_output_str { dvi } }
10157     \__sys_const:nn { sys_if_output_pdf }
10158     { \str_if_eq_p:Vn \c_sys_output_str { pdf } }
10159 }

```

(End definition for `\sys_if_output_dvi:TF`, `\sys_if_output_pdf:TF`, and `\c_sys_output_str`. These functions are documented on page 115.)

15.3.2 Configurations

`\g__sys_backend_tl` As the backend has to be checked and possibly adjusted, the approach here is to create a variable and use that in a one-shot to set a constant.

```

10160 \tl_new:N \g__sys_backend_tl
10161 \__sys_finalise:n
10162 {
10163   \tl_gset:Nx \g__sys_backend_tl
10164   {
10165     \sys_if_engine_xetex:TF
10166     { xdvipdfmx }
10167     {
10168       \sys_if_output_pdf:TF
10169       { pdfmode }
10170       { dvips }
10171     }
10172   }
10173 }
```

If there is a class option set, and recognised, we pick it up: these will over-ride anything set automatically but will themselves be over-written if there is a package option.

```

10174 \__sys_finalise:n
10175 {
10176   \cs_if_exist:NT \@classoptionslist
10177   {
10178     \cs_if_eq:NNF \@classoptionslist \scan_stop:
10179     {
10180       \clist_map_inline:Nn \@classoptionslist
10181       {
10182         \str_case:nnT {#1}
10183         {
10184           { dvipdfmx }
10185           { \tl_gset:Nn \g__sys_backend_tl { dvipdfmx } }
10186           { dvips }
10187           { \tl_gset:Nn \g__sys_backend_tl { dvips } }
10188           { dvisvgm }
10189           { \tl_gset:Nn \g__sys_backend_tl { dvisvgm } }
10190           { pdftex }
10191           { \tl_gset:Nn \g__sys_backend_tl { pdfmode } }
10192           { xetex }
10193           { \tl_gset:Nn \g__sys_backend_tl { xdvipdfmx } }
10194         }
10195       { \clist_remove_all:Nn \@unusedoptionlist {#1} }
10196     }
10197   }
10198 }
10199 }
```

(End definition for `\g__sys_backend_tl`.)

```

10200 </initex | package>
```

16 l3clist implementation

The following test files are used for this code: *m3clist002*.

10201 `*initex | package)`

10202 `\@@=clist`

`\c_empty_clist` An empty comma list is simply an empty token list.

10203 `\cs_new_eq:NN \c_empty_clist \c_empty_tl`

(End definition for `\c_empty_clist`. This variable is documented on page 127.)

`\l__clist_internal_clist` Scratch space for various internal uses. This comma list variable cannot be declared as such because it comes before `\clist_new:N`

10204 `\tl_new:N \l__clist_internal_clist`

(End definition for `\l__clist_internal_clist`.)

`\s__clist_mark` Internal scan marks.

`\s__clist_stop` 10205 `\scan_new:N \s__clist_mark`

10206 `\scan_new:N \s__clist_stop`

(End definition for `\s__clist_mark` and `\s__clist_stop`.)

`__clist_use_none_delimit_by_s_stop:w` Functions to gobble up to a scan mark.

`__clist_use_i_delimit_by_s_stop:nw` 10207 `\cs_new:Npn __clist_use_none_delimit_by_s_stop:w #1 \s__clist_stop { }`

10208 `\cs_new:Npn __clist_use_i_delimit_by_s_stop:nw #1 #2 \s__clist_stop {#1}`

(End definition for `__clist_use_none_delimit_by_s_stop:w` and `__clist_use_i_delimit_by_s_stop:nw`.)

`\q__clist_recursion_tail` Internal recursion quarks.

`\q__clist_recursion_stop` 10209 `\quark_new:N \q__clist_recursion_tail`

10210 `\quark_new:N \q__clist_recursion_stop`

(End definition for `\q__clist_recursion_tail` and `\q__clist_recursion_stop`.)

`__clist_if_recursion_tail_break:nN` Functions to query recursion quarks.

`__clist_if_recursion_tail_stop:n` 10211 `__kernel_quark_new_test:N __clist_if_recursion_tail_break:nN`

10212 `__kernel_quark_new_test:N __clist_if_recursion_tail_stop:n`

(End definition for `__clist_if_recursion_tail_break:nN` and `__clist_if_recursion_tail_stop:n`.)

`__clist_tmp:w` A temporary function for various purposes.

10213 `\cs_new_protected:Npn __clist_tmp:w { }`

(End definition for `__clist_tmp:w`.)

16.1 Removing spaces around items

`__clist_trim_next:w` Called as `\exp:w __clist_trim_next:w \prg_do_nothing: <comma list> ...` it expands to `{<trimmed item>}` where the `<trimmed item>` is the first non-empty result from removing spaces from both ends of comma-delimited items in the `<comma list>`. The `\prg_do_nothing:` marker avoids losing braces. The test for blank items is a somewhat optimized `\tl_if_empty:oTF` construction; if blank, another item is sought, otherwise trim spaces.

```

10214 \cs_new:Npn \__clist_trim_next:w #1 ,
10215 {
10216     \tl_if_empty:oTF { \use_none:nn #1 ? }
10217     { \__clist_trim_next:w \prg_do_nothing: }
10218     { \tl_trim_spaces_apply:oN {#1} \exp_end: }
10219 }
```

(End definition for `__clist_trim_next:w`.)

`__clist_sanitize:n` The auxiliary `__clist_sanitize:Nn` receives a delimiter (`\c_empty_tl` the first time, afterwards a comma) and that item as arguments. Unless we are done with the loop it calls `__clist_wrap_item:w` to unbrace the item (using a comma delimiter is safe since `#2` came from removing spaces from an argument delimited by a comma) and possibly re-brace it if needed.

```

10220 \cs_new:Npn \__clist_sanitize:n #1
10221 {
10222     \exp_after:wN \__clist_sanitize:Nn \exp_after:wN \c_empty_tl
10223     \exp:w \__clist_trim_next:w \prg_do_nothing:
10224     #1 , \q__clist_recursion_tail , \q__clist_recursion_stop
10225 }
10226 \cs_new:Npn \__clist_sanitize:Nn #1#2
10227 {
10228     \__clist_if_recursion_tail_stop:n {#2}
10229     #1 \__clist_wrap_item:w #2 ,
10230     \exp_after:wN \__clist_sanitize:Nn \exp_after:wN ,
10231     \exp:w \__clist_trim_next:w \prg_do_nothing:
10232 }
```

(End definition for `__clist_sanitize:n` and `__clist_sanitize:Nn`.)

`__clist_if_wrap:nTF` True if the argument must be wrapped to avoid getting altered by some clist operations.
`__clist_if_wrap:w` That is the case whenever the argument

- starts or end with a space or contains a comma,
- is empty, or
- consists of a single braced group.

All `l3clist` functions go through the same test when they need to determine whether to brace an item, so it is not a problem that this test has false positives such as “`\s__clist_mark ?`”. If the argument starts or end with a space or contains a comma then one of the three arguments of `__clist_if_wrap:w` will have its end delimiter (partly) in one of the three copies of `#1` in `__clist_if_wrap:nTF`; this has a knock-on effect meaning that the result of the expansion is not empty; in that case, wrap. Otherwise,

the argument is safe unless it starts with a brace group (or is empty) and it is empty or consists of a single n-type argument.

```

10233 \prg_new_conditional:Npnn \__clist_if_wrap:n #1 { TF }
10234 {
10235   \tl_if_empty:oTF
10236   {
10237     \__clist_if_wrap:w
10238     \s__clist_mark ? #1 ~ \s__clist_mark ? ~ #1
10239     \s__clist_mark , ~ \s__clist_mark #1 ,
10240   }
10241   {
10242     \tl_if_head_is_group:nTF { #1 { } }
10243     {
10244       \tl_if_empty:nTF {#1}
10245       { \prg_return_true: }
10246       {
10247         \tl_if_empty:oTF { \use_none:n #1}
10248         { \prg_return_true: }
10249         { \prg_return_false: }
10250       }
10251     }
10252     { \prg_return_false: }
10253   }
10254   { \prg_return_true: }
10255 }
10256 \cs_new:Npn \__clist_if_wrap:w #1 \s__clist_mark ? ~ #2 ~ \s__clist_mark #3 , { }

```

(End definition for __clist_if_wrap:nTF and __clist_if_wrap:w.)

__clist_wrap_item:w Safe items are put in \exp_not:n, otherwise we put an extra set of braces.

```

10257 \cs_new:Npn \__clist_wrap_item:w #1 ,
10258 { \__clist_if_wrap:nTF {#1} { \exp_not:n { {#1} } } { \exp_not:n {#1} } }

```

(End definition for __clist_wrap_item:w.)

16.2 Allocation and initialisation

\clist_new:N Internally, comma lists are just token lists.

```

\clist_new:c
10259 \cs_new_eq:NN \clist_new:N \tl_new:N
10260 \cs_new_eq:NN \clist_new:c \tl_new:c

```

(End definition for \clist_new:N. This function is documented on page 118.)

\clist_const:Nn Creating and initializing a constant comma list is done by sanitizing all items (stripping spaces and braces).

```

\clist_const:cn
\clist_const:Nx
\clist_const:cx
10261 \cs_new_protected:Npn \clist_const:Nn #1#2
10262 { \tl_const:Nx #1 { \__clist_sanitize:n {#2} } }
10263 \cs_generate_variant:Nn \clist_const:Nn { c , Nx , cx }

```

(End definition for \clist_const:Nn. This function is documented on page 119.)

\clist_clear:N Clearing comma lists is just the same as clearing token lists.

```
\clist_clear:c 10264 \cs_new_eq:NN \clist_clear:N \tl_clear:N
\clist_gclear:N 10265 \cs_new_eq:NN \clist_clear:c \tl_clear:c
\clist_gclear:c 10266 \cs_new_eq:NN \clist_gclear:N \tl_gclear:N
10267 \cs_new_eq:NN \clist_gclear:c \tl_gclear:c
```

(End definition for \clist_clear:N and \clist_gclear:N. These functions are documented on page 119.)

\clist_clear_new:N Once again a copy from the token list functions.

```
\clist_clear_new:c 10268 \cs_new_eq:NN \clist_clear_new:N \tl_clear_new:N
\clist_gclear_new:N 10269 \cs_new_eq:NN \clist_clear_new:c \tl_clear_new:c
\clist_gclear_new:c 10270 \cs_new_eq:NN \clist_gclear_new:N \tl_gclear_new:N
10271 \cs_new_eq:NN \clist_gclear_new:c \tl_gclear_new:c
```

(End definition for \clist_clear_new:N and \clist_gclear_new:N. These functions are documented on page 119.)

\clist_set_eq:NN Once again, these are simple copies from the token list functions.

```
\clist_set_eq:cN 10272 \cs_new_eq:NN \clist_set_eq:NN \tl_set_eq:NN
\clist_set_eq:Nc 10273 \cs_new_eq:NN \clist_set_eq:Nc \tl_set_eq:Nc
\clist_set_eq:cc 10274 \cs_new_eq:NN \clist_set_eq:cN \tl_set_eq:cN
\clist_gset_eq:NN 10275 \cs_new_eq:NN \clist_set_eq:cc \tl_set_eq:cc
\clist_gset_eq:cN 10276 \cs_new_eq:NN \clist_gset_eq:NN \tl_gset_eq:NN
\clist_gset_eq:Nc 10277 \cs_new_eq:NN \clist_gset_eq:Nc \tl_gset_eq:Nc
\clist_gset_eq:cN 10278 \cs_new_eq:NN \clist_gset_eq:cN \tl_gset_eq:cN
\clist_gset_eq:cc 10279 \cs_new_eq:NN \clist_gset_eq:cc \tl_gset_eq:cc
```

(End definition for \clist_set_eq:NN and \clist_gset_eq:NN. These functions are documented on page 119.)

\clist_set_from_seq:NN Setting a comma list from a comma-separated list is done using a simple mapping. Safe items are put in \exp_not:n, otherwise we put an extra set of braces. The first comma must be removed, except in the case of an empty comma-list.

```
\clist_set_from_seq:cN 10280 \cs_new_protected:Npn \clist_set_from_seq:NN
\clist_set_from_seq:Nc 10281 { \__clist_set_from_seq:NNNN \clist_clear:N \tl_set:Nx }
\clist_set_from_seq:cc 10282 \cs_new_protected:Npn \clist_gset_from_seq:NN
\clist_gset_from_seq:cN 10283 { \__clist_set_from_seq:NNNN \clist_gclear:N \tl_gset:Nx }
\clist_gset_from_seq:Nc 10284 \cs_new_protected:Npn \__clist_set_from_seq:NNNN #1#2#3#4
\clist_gset_from_seq:cc 10285 {
\__clist_set_from_seq:NNNN 10286 \seq_if_empty:NTF #4
\__clist_set_from_seq:n 10287 { #1 #3 }
10288 {
10289 #2 #3
10290 {
10291 \exp_after:wN \use_none:n \exp:w \exp_end_continue_f:w
10292 \seq_map_function:NN #4 \__clist_set_from_seq:n
10293 }
10294 }
10295 }
10296 \cs_new:Npn \__clist_set_from_seq:n #1
10297 {
10298 ,
10299 \__clist_if_wrap:NTF {#1}
10300 { \exp_not:n { {#1} } } }
```

```

10301         { \exp_not:n {#1} }
10302     }
10303     \cs_generate_variant:Nn \clist_set_from_seq:NN { Nc }
10304     \cs_generate_variant:Nn \clist_set_from_seq:NN { c , cc }
10305     \cs_generate_variant:Nn \clist_gset_from_seq:NN { Nc }
10306     \cs_generate_variant:Nn \clist_gset_from_seq:NN { c , cc }

```

(End definition for `\clist_set_from_seq:NN` and others. These functions are documented on page 119.)

```

\clist_concat:NNN Concatenating comma lists is not quite as easy as it seems, as there needs to be the
\clist_concat:ccc correct addition of a comma to the output. So a little work to do.
\clist_gconcat:NNN
\clist_gconcat:ccc
\__clist_concat:NNNN
10307 \cs_new_protected:Npn \clist_concat:NNN
10308 { \__clist_concat:NNNN \tl_set:Nx }
10309 \cs_new_protected:Npn \clist_gconcat:NNN
10310 { \__clist_concat:NNNN \tl_gset:Nx }
10311 \cs_new_protected:Npn \__clist_concat:NNNN #1#2#3#4
10312 {
10313     #1 #2
10314     {
10315         \exp_not:o #3
10316         \clist_if_empty:NF #3 { \clist_if_empty:NF #4 { , } }
10317         \exp_not:o #4
10318     }
10319 }
10320 \cs_generate_variant:Nn \clist_concat:NNN { ccc }
10321 \cs_generate_variant:Nn \clist_gconcat:NNN { ccc }

```

(End definition for `\clist_concat:NNN`, `\clist_gconcat:NNN`, and `__clist_concat:NNNN`. These functions are documented on page 119.)

```

\clist_if_exist_p:N Copies of the cs functions defined in l3basics.
\clist_if_exist_p:c
\clist_if_exist:NTF
\clist_if_exist:cTF
10322 \prg_new_eq_conditional:NNn \clist_if_exist:N \cs_if_exist:N
10323 { TF , T , F , p }
10324 \prg_new_eq_conditional:NNn \clist_if_exist:c \cs_if_exist:c
10325 { TF , T , F , p }

```

(End definition for `\clist_if_exist:NTF`. This function is documented on page 119.)

16.3 Adding data to comma lists

```

\clist_set:Nn
\clist_set:NV
\clist_set:No
\clist_set:Nx
\clist_set:cn
\clist_set:cV
\clist_set:co
\clist_set:cx
10326 \cs_new_protected:Npn \clist_set:Nn #1#2
10327 { \tl_set:Nx #1 { \__clist_sanitiz:n {#2} } }
10328 \cs_new_protected:Npn \clist_gset:Nn #1#2
10329 { \tl_gset:Nx #1 { \__clist_sanitiz:n {#2} } }
10330 \cs_generate_variant:Nn \clist_set:Nn { NV , No , Nx , c , cV , co , cx }
10331 \cs_generate_variant:Nn \clist_gset:Nn { NV , No , Nx , c , cV , co , cx }

```

(End definition for `\clist_set:Nn` and `\clist_gset:Nn`. These functions are documented on page 120.)

```

\clist_gset:Nn
\clist_put_left:Nn
\clist_put_left:NV
\clist_put_left:No
\clist_put_left:Nx
\clist_put_left:cn
\clist_put_left:cV
\clist_put_left:co
\clist_put_left:cx
\clist_gput_left:Nn
\clist_gput_left:NV
\clist_gput_left:No
\clist_gput_left:Nx
\clist_gput_left:cn
\clist_gput_left:cV
\clist_gput_left:co

```

Everything is based on concatenation after storing in `\l__clist_internal_clist`. This avoids having to worry here about space-trimming and so on.

```

10332 \cs_new_protected:Npn \clist_put_left:Nn
10333 { \__clist_put_left:NNNN \clist_concat:NNN \clist_set:Nn }
10334 \cs_new_protected:Npn \clist_gput_left:Nn

```

```

10335 { \_clist_put_left:NNNn \clist_gconcat:NNN \clist_set:Nn }
10336 \cs_new_protected:Npn \_clist_put_left:NNNn #1#2#3#4
10337 {
10338   #2 \l__clist_internal_clist {#4}
10339   #1 #3 \l__clist_internal_clist #3
10340 }
10341 \cs_generate_variant:Nn \clist_put_left:Nn { NV , No , Nx }
10342 \cs_generate_variant:Nn \clist_put_left:Nn { c , cV , co , cx }
10343 \cs_generate_variant:Nn \clist_gput_left:Nn { NV , No , Nx }
10344 \cs_generate_variant:Nn \clist_gput_left:Nn { c , cV , co , cx }

```

(End definition for `\clist_put_left:Nn`, `\clist_gput_left:Nn`, and `_clist_put_left:NNNn`. These functions are documented on page 120.)

```

\_clist_put_right:Nn
\clist_put_right:NV
\clist_put_right:No
\clist_put_right:Nx
\clist_put_right:cn
\clist_put_right:cV
\clist_put_right:co
\clist_put_right:cx
\_clist_gput_right:Nn
\clist_gput_right:NV
\clist_gput_right:No
\clist_gput_right:Nx
\clist_gput_right:cn
\clist_gput_right:cV
\clist_gput_right:co
\clist_gput_right:cx
\_clist_put_right:NNNn

```

```

10345 \cs_new_protected:Npn \clist_put_right:Nn
10346 { \_clist_put_right:NNNn \clist_concat:NNN \clist_set:Nn }
10347 \cs_new_protected:Npn \clist_gput_right:Nn
10348 { \_clist_put_right:NNNn \clist_gconcat:NNN \clist_set:Nn }
10349 \cs_new_protected:Npn \_clist_put_right:NNNn #1#2#3#4
10350 {
10351   #2 \l__clist_internal_clist {#4}
10352   #1 #3 #3 \l__clist_internal_clist
10353 }
10354 \cs_generate_variant:Nn \clist_put_right:Nn { NV , No , Nx }
10355 \cs_generate_variant:Nn \clist_put_right:Nn { c , cV , co , cx }
10356 \cs_generate_variant:Nn \clist_gput_right:Nn { NV , No , Nx }
10357 \cs_generate_variant:Nn \clist_gput_right:Nn { c , cV , co , cx }

```

(End definition for `\clist_put_right:Nn`, `\clist_gput_right:Nn`, and `_clist_put_right:NNNn`. These functions are documented on page 120.)

16.4 Comma lists as stacks

`\clist_get:NN` Getting an item from the left of a comma list is pretty easy: just trim off the first item using the comma. No need to trim spaces as comma-list *variables* are assumed to have “cleaned-up” items. (Note that grabbing a comma-delimited item removes an outer pair of braces if present, exactly as needed to uncover the underlying item.)

```

10358 \cs_new_protected:Npn \clist_get:NN #1#2
10359 {
10360   \if_meaning:w #1 \c_empty_clist
10361     \tl_set:Nn #2 { \q_no_value }
10362   \else:
10363     \exp_after:wN \_clist_get:wN #1 , \s__clist_stop #2
10364   \fi:
10365 }
10366 \cs_new_protected:Npn \_clist_get:wN #1 , #2 \s__clist_stop #3
10367 { \tl_set:Nn #3 {#1} }
10368 \cs_generate_variant:Nn \clist_get:NN { c }

```

(End definition for `\clist_get:NN` and `_clist_get:wN`. This function is documented on page 125.)

`\clist_pop:NN` An empty clist leads to `\q_no_value`, otherwise grab until the first comma and assign to the variable. The second argument of `_clist_pop:wwNNN` is a comma list ending in a

```

\_clist_pop:NN
\clist_pop:cn
\_clist_gpop:NN
\clist_gpop:cn
\_clist_pop:NNN
\_clist_pop:wwNNN
\_clist_pop:wN

```

comma and `\s__clist_mark`, unless the original clist contained exactly one item: then the argument is just `\s__clist_mark`. The next auxiliary picks either `\exp_not:n` or `\use_none:n` as #2, ensuring that the result can safely be an empty comma list.

```

10369 \cs_new_protected:Npn \clist_pop:NN
10370 { \__clist_pop:NNN \tl_set:Nx }
10371 \cs_new_protected:Npn \clist_gpop:NN
10372 { \__clist_pop:NNN \tl_gset:Nx }
10373 \cs_new_protected:Npn \__clist_pop:NNN #1#2#3
10374 {
10375   \if_meaning:w #2 \c_empty_clist
10376     \tl_set:Nn #3 { \q_no_value }
10377   \else:
10378     \exp_after:wN \__clist_pop:wwNNN #2 , \s__clist_mark \s__clist_stop #1#2#3
10379   \fi:
10380 }
10381 \cs_new_protected:Npn \__clist_pop:wwNNN #1 , #2 \s__clist_stop #3#4#5
10382 {
10383   \tl_set:Nn #5 {#1}
10384   #3 #4
10385   {
10386     \__clist_pop:wN \prg_do_nothing:
10387       #2 \exp_not:o
10388       , \s__clist_mark \use_none:n
10389     \s__clist_stop
10390   }
10391 }
10392 \cs_new:Npn \__clist_pop:wN #1 , \s__clist_mark #2 #3 \s__clist_stop { #2 {#1} }
10393 \cs_generate_variant:Nn \clist_pop:NN { c }
10394 \cs_generate_variant:Nn \clist_gpop:NN { c }

```

(End definition for `\clist_pop:NN` and others. These functions are documented on page 125.)

```

\clist_get:NNTF The same, as branching code: very similar to the above.
\clist_get:cNTF 10395 \prg_new_protected_conditional:Npnn \clist_get:NN #1#2 { T , F , TF }
\clist_pop:NNTF 10396 {
\clist_pop:cNTF 10397   \if_meaning:w #1 \c_empty_clist
\clist_gpop:NNTF 10398   \prg_return_false:
\clist_gpop:cNTF 10399   \else:
\__clist_pop_TF:NNN 10400     \exp_after:wN \__clist_get:wN #1 , \s__clist_stop #2
10401     \prg_return_true:
10402   \fi:
10403 }
10404 \prg_generate_conditional_variant:Nnn \clist_get:NN { c } { T , F , TF }
10405 \prg_new_protected_conditional:Npnn \clist_pop:NN #1#2 { T , F , TF }
10406 { \__clist_pop_TF:NNN \tl_set:Nx #1 #2 }
10407 \prg_new_protected_conditional:Npnn \clist_gpop:NN #1#2 { T , F , TF }
10408 { \__clist_pop_TF:NNN \tl_gset:Nx #1 #2 }
10409 \cs_new_protected:Npn \__clist_pop_TF:NNN #1#2#3
10410 {
10411   \if_meaning:w #2 \c_empty_clist
10412     \prg_return_false:
10413   \else:
10414     \exp_after:wN \__clist_pop:wwNNN #2 , \s__clist_mark \s__clist_stop #1#2#3
10415     \prg_return_true:

```

```

10416     \fi:
10417   }
10418   \prg_generate_conditional_variant:Nnn \clist_pop:NN { c } { T , F , TF }
10419   \prg_generate_conditional_variant:Nnn \clist_gpop:NN { c } { T , F , TF }

```

(End definition for `\clist_get:NNTF` and others. These functions are documented on page 125.)

`\clist_push:Nn` Pushing to a comma list is the same as adding on the left.

```

\clist_push:NV 10420 \cs_new_eq:NN \clist_push:Nn \clist_put_left:Nn
\clist_push:No 10421 \cs_new_eq:NN \clist_push:NV \clist_put_left:NV
\clist_push:Nx 10422 \cs_new_eq:NN \clist_push:No \clist_put_left:No
\clist_push:cn 10423 \cs_new_eq:NN \clist_push:Nx \clist_put_left:Nx
\clist_push:cV 10424 \cs_new_eq:NN \clist_push:cn \clist_put_left:cn
\clist_push:co 10425 \cs_new_eq:NN \clist_push:cV \clist_put_left:cV
\clist_push:cx 10426 \cs_new_eq:NN \clist_push:co \clist_put_left:co
\clist_gpush:Nn 10427 \cs_new_eq:NN \clist_gpush:Nn \clist_gput_left:Nn
\clist_gpush:NV 10428 \cs_new_eq:NN \clist_gpush:NV \clist_gput_left:NV
\clist_gpush:No 10429 \cs_new_eq:NN \clist_gpush:No \clist_gput_left:No
\clist_gpush:Nx 10430 \cs_new_eq:NN \clist_gpush:Nx \clist_gput_left:Nx
\clist_gpush:cn 10431 \cs_new_eq:NN \clist_gpush:cn \clist_gput_left:cn
\clist_gpush:cV 10432 \cs_new_eq:NN \clist_gpush:cV \clist_gput_left:cV
\clist_gpush:co 10433 \cs_new_eq:NN \clist_gpush:co \clist_gput_left:co
\clist_gpush:cx 10434 \cs_new_eq:NN \clist_gpush:cx \clist_gput_left:cx

```

(End definition for `\clist_push:Nn` and `\clist_gpush:Nn`. These functions are documented on page 126.)

16.5 Modifying comma lists

`\l__clist_internal_remove_clist` An internal comma list and a sequence for the removal routines.
`\l__clist_internal_remove_seq`

```

10436 \clist_new:N \l__clist_internal_remove_clist
10437 \seq_new:N \l__clist_internal_remove_seq

```

(End definition for `\l__clist_internal_remove_clist` and `\l__clist_internal_remove_seq`.)

`\clist_remove_duplicates:N` Removing duplicates means making a new list then copying it.

```

\clist_remove_duplicates:c 10438 \cs_new_protected:Npn \clist_remove_duplicates:N
\clist_gremove_duplicates:N 10439 { \__clist_remove_duplicates:NN \clist_set_eq:NN }
\clist_gremove_duplicates:c 10440 \cs_new_protected:Npn \clist_gremove_duplicates:N
  \__clist_remove_duplicates:NN 10441 { \__clist_remove_duplicates:NN \clist_gset_eq:NN }
  10442 \cs_new_protected:Npn \__clist_remove_duplicates:NN #1#2
  10443 {
  10444   \clist_clear:N \l__clist_internal_remove_clist
  10445   \clist_map_inline:Nn #2
  10446   {
  10447     \clist_if_in:NnF \l__clist_internal_remove_clist {##1}
  10448     { \clist_put_right:Nn \l__clist_internal_remove_clist {##1} }
  10449   }
  10450   #1 #2 \l__clist_internal_remove_clist
  10451 }
10452 \cs_generate_variant:Nn \clist_remove_duplicates:N { c }
10453 \cs_generate_variant:Nn \clist_gremove_duplicates:N { c }

```

(End definition for `\clist_remove_duplicates:N`, `\clist_gremove_duplicates:N`, and `__clist_remove_duplicates:NN`. These functions are documented on page 121.)

`\clist_remove_all:Nn` The method used here for safe items is very similar to `\tl_replace_all:Nnn`. However, if the item contains commas or leading/trailing spaces, or is empty, or consists of a single brace group, we know that it can only appear within braces so the code would fail; instead just convert to a sequence and do the removal with `l3seq` code (it involves somewhat elaborate code to do most of the work expandably but the final token list comparisons non-expandably).

`\clist_remove_all:cn`

`\clist_gremove_all:Nn`

`\clist_gremove_all:cn`

`__clist_remove_all:NNNn`

`__clist_remove_all:w`

`__clist_remove_all:`

For “safe” items, build a function delimited by the $\langle item \rangle$ that should be removed, surrounded with commas, and call that function followed by the expanded comma list, and another copy of the $\langle item \rangle$. The loop is controlled by the argument grabbed by `__clist_remove_all:w`: when the item was found, the `\s__clist_mark` delimiter used is the one inserted by `__clist_tmp:w`, and `__clist_use_none_delimit_by_s_stop:w` is deleted. At the end, the final $\langle item \rangle$ is grabbed, and the argument of `__clist_tmp:w` contains `\s__clist_mark`: in that case, `__clist_remove_all:w` removes the second `\s__clist_mark` (inserted by `__clist_tmp:w`), and lets `__clist_use_none_delimit_by_s_stop:w` act.

No brace is lost because items are always grabbed with a leading comma. The result of the first assignment has an extra leading comma, which we remove in a second assignment. Two exceptions: if the clist lost all of its elements, the result is empty, and we shouldn’t remove anything; if the clist started up empty, the first step happens to turn it into a single comma, and the second step removes it.

```

10454 \cs_new_protected:Npn \clist_remove_all:Nn
10455   { \__clist_remove_all:NNNn \clist_set_from_seq:NN \tl_set:Nx }
10456 \cs_new_protected:Npn \clist_gremove_all:Nn
10457   { \__clist_remove_all:NNNn \clist_gset_from_seq:NN \tl_gset:Nx }
10458 \cs_new_protected:Npn \__clist_remove_all:NNNn #1#2#3#4
10459   {
10460     \__clist_if_wrap:nTF {#4}
10461     {
10462       \seq_set_from_clist:NN \l__clist_internal_remove_seq #3
10463       \seq_remove_all:Nn \l__clist_internal_remove_seq {#4}
10464       #1 #3 \l__clist_internal_remove_seq
10465     }
10466     {
10467       \cs_set:Npn \__clist_tmp:w ##1 , #4 ,
10468       {
10469         ##1
10470         , \s__clist_mark , \__clist_use_none_delimit_by_s_stop:w ,
10471         \__clist_remove_all:
10472       }
10473       #2 #3
10474       {
10475         \exp_after:wN \__clist_remove_all:
10476         #3 , \s__clist_mark , #4 , \s__clist_stop
10477       }
10478       \clist_if_empty:NF #3
10479       {
10480         #2 #3
10481         {
10482           \exp_args:No \exp_not:o

```

```

10483         { \exp_after:wN \use_none:n #3 }
10484     }
10485 }
10486 }
10487 }
10488 \cs_new:Npn \__clist_remove_all:
10489 { \exp_after:wN \__clist_remove_all:w \__clist_tmp:w , }
10490 \cs_new:Npn \__clist_remove_all:w #1 , \s__clist_mark , #2 , { \exp_not:n {#1} }
10491 \cs_generate_variant:Nn \clist_remove_all:Nn { c }
10492 \cs_generate_variant:Nn \clist_gremove_all:Nn { c }

```

(End definition for `\clist_remove_all:Nn` and others. These functions are documented on page 121.)

`\clist_reverse:N` Use `\clist_reverse:n` in an x-expanding assignment. The extra work that `\clist_reverse:n` does to preserve braces and spaces would not be needed for the well-controlled case of N-type comma lists, but the slow-down is not too bad.

`\clist_reverse:c`
`\clist_greverse:N`
`\clist_greverse:c`

```

10493 \cs_new_protected:Npn \clist_reverse:N #1
10494 { \tl_set:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
10495 \cs_new_protected:Npn \clist_greverse:N #1
10496 { \tl_gset:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
10497 \cs_generate_variant:Nn \clist_reverse:N { c }
10498 \cs_generate_variant:Nn \clist_greverse:N { c }

```

(End definition for `\clist_reverse:N` and `\clist_greverse:N`. These functions are documented on page 121.)

`\clist_reverse:n` The reversed token list is built one item at a time, and stored between `\s__clist_stop` and `\s__clist_mark`, in the form of ? followed by zero or more instances of “ $\langle item \rangle$,”. We start from a comma list “ $\langle item_1 \rangle, \dots, \langle item_n \rangle$ ”. During the loop, the auxiliary `__clist_reverse:wwNww` receives “ $\langle item_i \rangle$ ” as #1, “ $\langle item_{i+1} \rangle, \dots, \langle item_n \rangle$ ” as #2, `__clist_reverse:wwNww` as #3, what remains until `\s__clist_stop` as #4, and “ $\langle item_{i-1} \rangle, \dots, \langle item_1 \rangle$,” as #5. The auxiliary moves #1 just before #5, with a comma, and calls itself (#3). After the last item is moved, `__clist_reverse:wwNww` receives “`\s__clist_mark __clist_reverse:wwNww !`” as its argument #1, thus `__clist_reverse_end:ww` as its argument #3. This second auxiliary cleans up until the marker !, removes the trailing comma (introduced when the first item was moved after `\s__clist_stop`), and leaves its argument #1 within `\exp_not:n`. There is also a need to remove a leading comma, hence `\exp_not:o` and `\use_none:n`.

```

10499 \cs_new:Npn \clist_reverse:n #1
10500 {
10501     \__clist_reverse:wwNww ? #1 ,
10502     \s__clist_mark \__clist_reverse:wwNww ! ,
10503     \s__clist_mark \__clist_reverse_end:ww
10504     \s__clist_stop ? \s__clist_mark
10505 }
10506 \cs_new:Npn \__clist_reverse:wwNww
10507 #1 , #2 \s__clist_mark #3 #4 \s__clist_stop ? #5 \s__clist_mark
10508 { #3 ? #2 \s__clist_mark #3 #4 \s__clist_stop #1 , #5 \s__clist_mark }
10509 \cs_new:Npn \__clist_reverse_end:ww #1 ! #2 , \s__clist_mark
10510 { \exp_not:o { \use_none:n #2 } }

```

(End definition for `\clist_reverse:n`, `__clist_reverse:wwNww`, and `__clist_reverse_end:ww`. This function is documented on page 121.)

`\clist_sort:Nn` Implemented in `l3sort`.
`\clist_sort:cn`
`\clist_gsort:Nn` (End definition for `\clist_sort:Nn` and `\clist_gsort:Nn`. These functions are documented on page 121.)
`\clist_gsort:cn`

16.6 Comma list conditionals

`\clist_if_empty_p:N` Simple copies from the token list variable material.
`\clist_if_empty_p:c` 10511 `\prg_new_eq_conditional:Nn \clist_if_empty:N \tl_if_empty:N`
`\clist_if_empty:NTF` 10512 `{ p , T , F , TF }`
`\clist_if_empty:cTF` 10513 `\prg_new_eq_conditional:Nn \clist_if_empty:c \tl_if_empty:c`
10514 `{ p , T , F , TF }`

(End definition for `\clist_if_empty:N`. This function is documented on page 122.)

`\clist_if_empty_p:n` As usual, we insert a token (here ?) before grabbing any argument: this avoids losing braces. The argument of `\tl_if_empty:oTF` is empty if #1 is ? followed by blank spaces (besides, this particular variant of the emptiness test is optimized). If the item of the comma list is blank, grab the next one. As soon as one item is non-blank, exit: the second auxiliary grabs `\prg_return_false:` as #2, unless every item in the comma list was blank and the loop actually got broken by the trailing `\s__clist_mark \prg_return_false:` item.

10515 `\prg_new_conditional:Npnn \clist_if_empty:n #1 { p , T , F , TF }`
10516 `{`
10517 `__clist_if_empty_n:w ? #1`
10518 `, \s__clist_mark \prg_return_false:`
10519 `, \s__clist_mark \prg_return_true:`
10520 `\s__clist_stop`
10521 `}`
10522 `\cs_new:Npn __clist_if_empty_n:w #1 ,`
10523 `{`
10524 `\tl_if_empty:oTF { \use_none:nn #1 ? }`
10525 `{ __clist_if_empty_n:w ? }`
10526 `{ __clist_if_empty_n:wNw }`
10527 `}`
10528 `\cs_new:Npn __clist_if_empty_n:wNw #1 \s__clist_mark #2#3 \s__clist_stop {#2}`

(End definition for `\clist_if_empty:nTF`, `__clist_if_empty_n:w`, and `__clist_if_empty_n:wNw`. This function is documented on page 122.)

`\clist_if_in:NnTF` For “safe” items, we simply surround the comma list, and the item, with commas, then use the same code as for `\tl_if_in:Nn`. For “unsafe” items we follow the same route as `\seq_if_in:Nn`, mapping through the list a comparison function. If found, return `true` and remove `\prg_return_false:`.
`\clist_if_in:NVTf`
`\clist_if_in:NoTF`
`\clist_if_in:cnTF`
`\clist_if_in:cVTf` 10529 `\prg_new_protected_conditional:Npnn \clist_if_in:Nn #1#2 { T , F , TF }`
`\clist_if_in:coTF` 10530 `{`
`\clist_if_in:nnTF` 10531 `\exp_args:No __clist_if_in_return:nnN #1 {#2} #1`
`\clist_if_in:nVTf` 10532 `}`
`\clist_if_in:noTF` 10533 `\prg_new_protected_conditional:Npnn \clist_if_in:nn #1#2 { T , F , TF }`
`__clist_if_in_return:nnN` 10534 `{`
10535 `\clist_set:Nn \l__clist_internal_clist {#1}`
10536 `\exp_args:No __clist_if_in_return:nnN \l__clist_internal_clist {#2}`
10537 `\l__clist_internal_clist`
10538 `}`

```

10539 \cs_new_protected:Npn \__clist_if_in_return:nnN #1#2#3
10540 {
10541   \__clist_if_wrap:nTF {#2}
10542   {
10543     \cs_set:Npx \__clist_tmp:w ##1
10544     {
10545       \exp_not:N \tl_if_eq:nnT {##1}
10546       \exp_not:n
10547       {
10548         {#2}
10549         { \clist_map_break:n { \prg_return_true: \use_none:n } }
10550       }
10551     }
10552     \clist_map_function:NN #3 \__clist_tmp:w
10553     \prg_return_false:
10554   }
10555   {
10556     \cs_set:Npn \__clist_tmp:w ##1 ,#2, { }
10557     \tl_if_empty:oTF
10558     { \__clist_tmp:w ,#1, {} {} ,#2, }
10559     { \prg_return_false: } { \prg_return_true: }
10560   }
10561 }
10562 \prg_generate_conditional_variant:Nnn \clist_if_in:Nn
10563 { NV , No , c , cV , co } { T , F , TF }
10564 \prg_generate_conditional_variant:Nnn \clist_if_in:nn
10565 { nV , no } { T , F , TF }

```

(End definition for `\clist_if_in:NnTF`, `\clist_if_in:nnTF`, and `__clist_if_in_return:nnN`. These functions are documented on page 122.)

16.7 Mapping to comma lists

`\clist_map_function:NN` If the variable is empty, the mapping is skipped (otherwise, that comma-list would be seen as consisting of one empty item). Then loop over the comma-list, grabbing one comma-delimited item at a time. The end is marked by `\q__clist_recursion_tail`. The auxiliary function `__clist_map_function:Nw` is also used in `\clist_map_inline:Nn`.

```

10566 \cs_new:Npn \clist_map_function:NN #1#2
10567 {
10568   \clist_if_empty:NF #1
10569   {
10570     \exp_last_unbraced:NNo \__clist_map_function:Nw #2 #1
10571     , \q__clist_recursion_tail ,
10572     \prg_break_point:Nn \clist_map_break: { }
10573   }
10574 }
10575 \cs_new:Npn \__clist_map_function:Nw #1#2 ,
10576 {
10577   \__clist_if_recursion_tail_break:nN {#2} \clist_map_break:
10578   #1 {#2}
10579   \__clist_map_function:Nw #1
10580 }
10581 \cs_generate_variant:Nn \clist_map_function:NN { c }

```

(End definition for `\clist_map_function:Nn` and `__clist_map_function:Nw`. This function is documented on page 122.)

```

\clist_map_function:nN The n-type mapping function is a bit more awkward, since spaces must be trimmed from
\__clist_map_function_n:Nn each item. Space trimming is again based on \__clist_trim_next:w. The auxiliary
\__clist_map_unbrace:Nw \__clist_map_function_n:Nn receives as arguments the function, and the next non-
empty item (after space trimming but before brace removal). One level of braces is
removed by \__clist_map_unbrace:Nw.

10582 \cs_new:Npn \clist_map_function:nN #1#2
10583 {
10584     \exp_after:wN \__clist_map_function_n:Nn \exp_after:wN #2
10585     \exp:w \__clist_trim_next:w \prg_do_nothing: #1 , \q__clist_recursion_tail ,
10586     \prg_break_point:Nn \clist_map_break: { }
10587 }
10588 \cs_new:Npn \__clist_map_function_n:Nn #1 #2
10589 {
10590     \__clist_if_recursion_tail_break:nN {#2} \clist_map_break:
10591     \__clist_map_unbrace:Nw #1 #2,
10592     \exp_after:wN \__clist_map_function_n:Nn \exp_after:wN #1
10593     \exp:w \__clist_trim_next:w \prg_do_nothing:
10594 }
10595 \cs_new:Npn \__clist_map_unbrace:Nw #1 #2, { #1 {#2} }

```

(End definition for `\clist_map_function:nN`, `__clist_map_function_n:Nn`, and `__clist_map_unbrace:Nw`. This function is documented on page 122.)

`\clist_map_inline:Nn` Inline mapping is done by creating a suitable function “on the fly”: this is done globally
`\clist_map_inline:cn` to avoid any issues with \TeX ’s groups. We use a different function for each level of
`\clist_map_inline:nn` nesting.

Since the mapping is non-expandable, we can perform the space-trimming needed by the `n` version simply by storing the comma-list in a variable. We don’t need a different comma-list for each nesting level: the comma-list is expanded before the mapping starts.

```

10596 \cs_new_protected:Npn \clist_map_inline:Nn #1#2
10597 {
10598     \clist_if_empty:NF #1
10599     {
10600         \int_gincr:N \g__kernel_prg_map_int
10601         \cs_gset_protected:cpn
10602             { \__clist_map_ \int_use:N \g__kernel_prg_map_int :w } ##1 {#2}
10603         \exp_last_unbraced:Nco \__clist_map_function:Nw
10604             { \__clist_map_ \int_use:N \g__kernel_prg_map_int :w }
10605             #1 , \q__clist_recursion_tail ,
10606         \prg_break_point:Nn \clist_map_break:
10607             { \int_gdecr:N \g__kernel_prg_map_int }
10608     }
10609 }
10610 \cs_new_protected:Npn \clist_map_inline:nn #1
10611 {
10612     \clist_set:Nn \l__clist_internal_clist {#1}
10613     \clist_map_inline:Nn \l__clist_internal_clist
10614 }
10615 \cs_generate_variant:Nn \clist_map_inline:Nn { c }

```

(End definition for `\clist_map_inline:Nn` and `\clist_map_inline:nn`. These functions are documented on page 123.)

`\clist_map_variable:NNn` As for other comma-list mappings, filter out the case of an empty list. Same approach as
`\clist_map_variable:cNn` `\clist_map_function:Nn`, additionally we store each item in the given variable. As for
`\clist_map_variable:nNn` inline mappings, space trimming for the `n` variant is done by storing the comma list in
`__clist_map_variable:Nnw` a variable. The quark test is done before assigning the item to the variable: this avoids
storing a quark which the user wouldn't expect. The strange `\use:n` avoids unlikely
problems when `#2` would contain `\q__clist_recursion_stop`.

```

10616 \cs_new_protected:Npn \clist_map_variable:NNn #1#2#3
10617 {
10618   \clist_if_empty:NF #1
10619   {
10620     \exp_args:Nno \use:n
10621     { \__clist_map_variable:Nnw #2 {#3} }
10622     #1
10623     , \q__clist_recursion_tail , \q__clist_recursion_stop
10624     \prg_break_point:Nn \clist_map_break: { }
10625   }
10626 }
10627 \cs_new_protected:Npn \clist_map_variable:nNn #1
10628 {
10629   \clist_set:Nn \l__clist_internal_clist {#1}
10630   \clist_map_variable:NNn \l__clist_internal_clist
10631 }
10632 \cs_new_protected:Npn \__clist_map_variable:Nnw #1#2#3,
10633 {
10634   \__clist_if_recursion_tail_stop:n {#3}
10635   \tl_set:Nn #1 {#3}
10636   \use:n {#2}
10637   \__clist_map_variable:Nnw #1 {#2}
10638 }
10639 \cs_generate_variant:Nn \clist_map_variable:NNn { c }

```

(End definition for `\clist_map_variable:NNn`, `\clist_map_variable:nNn`, and `__clist_map_variable:Nnw`.
These functions are documented on page 123.)

`\clist_map_break:` The break statements use the general `\prg_map_break:Nn` mechanism.
`\clist_map_break:n`

```

10640 \cs_new:Npn \clist_map_break:
10641 { \prg_map_break:Nn \clist_map_break: { } }
10642 \cs_new:Npn \clist_map_break:n
10643 { \prg_map_break:Nn \clist_map_break: }

```

(End definition for `\clist_map_break:` and `\clist_map_break:n`. These functions are documented on
page 123.)

`\clist_count:N` Counting the items in a comma list is done using the same approach as for other token
`\clist_count:c` count functions: turn each entry into a `+1` then use integer evaluation to actually do the
`\clist_count:n` mathematics. In the case of an `n`-type comma-list, we could of course use `\clist_map_-`
`__clist_count:n` `function:nN`, but that is very slow, because it carefully removes spaces. Instead, we loop
`__clist_count:w` manually, and skip blank items (but not `{}`, hence the extra spaces).

```

10644 \cs_new:Npn \clist_count:N #1
10645 {
10646   \int_eval:n
10647   {
10648     0
10649     \clist_map_function:NN #1 \__clist_count:n

```

```

10650     }
10651   }
10652   \cs_generate_variant:Nn \clist_count:N { c }
10653   \cs_new:Npx \clist_count:n #1
10654   {
10655     \exp_not:N \int_eval:n
10656     {
10657       0
10658       \exp_not:N \__clist_count:w \c_space_tl
10659       #1 \exp_not:n { , \q__clist_recursion_tail , \q__clist_recursion_stop }
10660     }
10661   }
10662   \cs_new:Npn \__clist_count:n #1 { + 1 }
10663   \cs_new:Npx \__clist_count:w #1 ,
10664   {
10665     \exp_not:n { \exp_args:Nf \__clist_if_recursion_tail_stop:n } {#1}
10666     \exp_not:N \tl_if_blank:nF {#1} { + 1 }
10667     \exp_not:N \__clist_count:w \c_space_tl
10668   }

```

(End definition for `\clist_count:N` and others. These functions are documented on page 124.)

16.8 Using comma lists

`\clist_use:Nnnn` First check that the variable exists. Then count the items in the comma list. If it has none, output nothing. If it has one item, output that item, brace stripped (note that space-trimming has already been done when the comma list was assigned). If it has two, place the *<separator between two>* in the middle.

`\clist_use:cnnn` Otherwise, `__clist_use:nwwwnwn` takes the following arguments; 1: a *<separator>*, 2, 3, 4: three items from the comma list (or quarks), 5: the rest of the comma list, 6: a *<continuation>* function (`use_ii` or `use_iii` with its *<separator>* argument), 7: junk, and 8: the temporary result, which is built in a brace group following `\q__clist_stop`.

`__clist_use:wwn` The *<separator>* and the first of the three items are placed in the result, then we use the *<continuation>*, placing the remaining two items after it. When we begin this loop, the three items really belong to the comma list, the first `\q__clist_mark` is taken as a delimiter to the `use_ii` function, and the continuation is `use_ii` itself. When we reach the last two items of the original token list, `\q__clist_mark` is taken as a third item, and now the second `\q__clist_mark` serves as a delimiter to `use_ii`, switching to the other *<continuation>*, `use_iii`, which uses the *<separator between final two>*.

`__clist_use:nwwwn`

`\clist_use:Nn`

`\clist_use:cn`

```

10669   \cs_new:Npn \clist_use:Nnnn #1#2#3#4
10670   {
10671     \clist_if_exist:NTF #1
10672     {
10673       \int_case:nnF { \clist_count:N #1 }
10674       {
10675         { 0 } { }
10676         { 1 } { \exp_after:wN \__clist_use:wwn #1 , , { } }
10677         { 2 } { \exp_after:wN \__clist_use:wwn #1 , {#2} }
10678       }
10679       {
10680         \exp_after:wN \__clist_use:nwwwnwn
10681         \exp_after:wN { \exp_after:wN } #1 ,
10682         \s__clist_mark , { \__clist_use:nwwwnwn {#3} }

```

```

10683         \s__clist_mark , { \__clist_use:nwn {#4} }
10684         \s__clist_stop { }
10685     }
10686 }
10687 {
10688     \__kernel_msg_expandable_error:nnn
10689     { kernel } { bad-variable } {#1}
10690 }
10691 }
10692 \cs_generate_variant:Nn \clist_use:Nnnn { c }
10693 \cs_new:Npn \__clist_use:wn #1 , #2 , #3 { \exp_not:n { #1 #3 #2 } }
10694 \cs_new:Npn \__clist_use:nwnnnwn
10695     #1#2 , #3 , #4 , #5 \s__clist_mark , #6#7 \s__clist_stop #8
10696     { #6 {#3} , {#4} , #5 \s__clist_mark , {#6} #7 \s__clist_stop { #8 #1 #2 } }
10697 \cs_new:Npn \__clist_use:nwn #1#2 , #3 \s__clist_stop #4
10698     { \exp_not:n { #4 #1 #2 } }
10699 \cs_new:Npn \clist_use:Nn #1#2
10700     { \clist_use:Nnnn #1 {#2} {#2} {#2} }
10701 \cs_generate_variant:Nn \clist_use:Nn { c }

```

(End definition for `\clist_use:Nnnn` and others. These functions are documented on page 124.)

16.9 Using a single item

`\clist_item:Nn` To avoid needing to test the end of the list at each step, we first compute the $\langle length \rangle$ of the list. If the item number is 0, less than $-\langle length \rangle$, or more than $\langle length \rangle$, the result is empty. If it is negative, but not less than $-\langle length \rangle$, add $\langle length \rangle + 1$ to the item number before performing the loop. The loop itself is very simple, return the item if the counter reached 1, otherwise, decrease the counter and repeat.

`\clist_item:cn`

`__clist_item:nnnN`

`__clist_item:ffoN`

`__clist_item:ffnN`

`__clist_item_N_loop:nw`

```

10702 \cs_new:Npn \clist_item:Nn #1#2
10703     {
10704         \__clist_item:ffoN
10705         { \clist_count:N #1 }
10706         { \int_eval:n {#2} }
10707         #1
10708         \__clist_item_N_loop:nw
10709     }
10710 \cs_new:Npn \__clist_item:nnnN #1#2#3#4
10711     {
10712         \int_compare:nNnTF {#2} < 0
10713         {
10714             \int_compare:nNnTF {#2} < { - #1 }
10715             { \__clist_use_none_delimit_by_s_stop:w }
10716             { \exp_args:Nf #4 { \int_eval:n { #2 + 1 + #1 } } }
10717         }
10718         {
10719             \int_compare:nNnTF {#2} > {#1}
10720             { \__clist_use_none_delimit_by_s_stop:w }
10721             { #4 {#2} }
10722         }
10723         { } , #3 , \s__clist_stop
10724     }
10725 \cs_generate_variant:Nn \__clist_item:nnnN { ffo, ff }
10726 \cs_new:Npn \__clist_item_N_loop:nw #1 #2,

```

```

10727 {
10728   \int_compare:nNnTF {#1} = 0
10729     { \__clist_use_i_delimit_by_s_stop:nw { \exp_not:n {#2} } }
10730     { \exp_args:Nf \__clist_item_N_loop:nw { \int_eval:n { #1 - 1 } } }
10731   }
10732 \cs_generate_variant:Nn \clist_item:Nn { c }

```

(End definition for `\clist_item:Nn`, `__clist_item:nnnN`, and `__clist_item_N_loop:nw`. This function is documented on page 126.)

```

\clist_item:nn This starts in the same way as \clist_item:Nn by counting the items of the comma list.
\__clist_item_n:nw The final item should be space-trimmed before being brace-stripped, hence we insert a
\__clist_item_n_loop:nw couple of odd-looking \prg_do_nothing: to avoid losing braces. Blank items are ignored.
\__clist_item_n_end:n
\__clist_item_n_strip:n
\__clist_item_n_strip:w
10733 \cs_new:Npn \clist_item:nn #1#2
10734 {
10735   \__clist_item:ffnN
10736   { \clist_count:n {#1} }
10737   { \int_eval:n {#2} }
10738   {#1}
10739   \__clist_item_n:nw
10740 }
10741 \cs_new:Npn \__clist_item_n:nw #1
10742 { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
10743 \cs_new:Npn \__clist_item_n_loop:nw #1 #2,
10744 {
10745   \exp_args:No \tl_if_blank:nTF {#2}
10746   { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
10747   {
10748     \int_compare:nNnTF {#1} = 0
10749     { \exp_args:No \__clist_item_n_end:n {#2} }
10750     {
10751       \exp_args:Nf \__clist_item_n_loop:nw
10752       { \int_eval:n { #1 - 1 } }
10753       \prg_do_nothing:
10754     }
10755   }
10756 }
10757 \cs_new:Npn \__clist_item_n_end:n #1 #2 \s_clist_stop
10758 { \tl_trim_spaces_apply:nN {#1} \__clist_item_n_strip:n }
10759 \cs_new:Npn \__clist_item_n_strip:n #1 { \__clist_item_n_strip:w #1 , }
10760 \cs_new:Npn \__clist_item_n_strip:w #1 , { \exp_not:n {#1} }

```

(End definition for `\clist_item:nn` and others. This function is documented on page 126.)

```

\clist_rand_item:n The N-type function is not implemented through the n-type function for efficiency: for
\clist_rand_item:N instance comma-list variables do not require space-trimming of their items. Even testing
\clist_rand_item:c for emptiness of an n-type comma-list is slow, so we count items first and use that both
\__clist_rand_item:nn for the emptiness test and the pseudo-random integer. Importantly, \clist_item:Nn
and \clist_item:nn only evaluate their argument once.

```

```

10761 \cs_new:Npn \clist_rand_item:n #1
10762 { \exp_args:Nf \__clist_rand_item:nn { \clist_count:n {#1} } {#1} }
10763 \cs_new:Npn \__clist_rand_item:nn #1#2
10764 {
10765   \int_compare:nNnF {#1} = 0

```

```

10766     { \clist_item:nn {#2} { \int_rand:nn { 1 } {#1} } }
10767   }
10768   \cs_new:Npn \clist_rand_item:N #1
10769   {
10770     \clist_if_empty:NF #1
10771     { \clist_item:Nn #1 { \int_rand:nn { 1 } { \clist_count:N #1 } } }
10772   }
10773   \cs_generate_variant:Nn \clist_rand_item:N { c }

```

(End definition for `\clist_rand_item:n`, `\clist_rand_item:N`, and `__clist_rand_item:nn`. These functions are documented on page 126.)

16.10 Viewing comma lists

`\clist_show:N` Apply the general `__kernel_chk_defined:NT` and `\msg_show:nnnnnn`.
`\clist_show:c`
`\clist_log:N`
`\clist_log:c`
`__clist_show:NN`

```

10774 \cs_new_protected:Npn \clist_show:N { \__clist_show:NN \msg_show:nnxxxx }
10775 \cs_generate_variant:Nn \clist_show:N { c }
10776 \cs_new_protected:Npn \clist_log:N { \__clist_show:NN \msg_log:nnxxxx }
10777 \cs_generate_variant:Nn \clist_log:N { c }
10778 \cs_new_protected:Npn \__clist_show:NN #1#2
10779 {
10780   \__kernel_chk_defined:NT #2
10781   {
10782     #1 { LaTeX/kernel } { show-clist }
10783     { \token_to_str:N #2 }
10784     { \clist_map_function:NN #2 \msg_show_item:n }
10785     { } { }
10786   }
10787 }

```

(End definition for `\clist_show:N`, `\clist_log:N`, and `__clist_show:NN`. These functions are documented on page 126.)

`\clist_show:n` A variant of the above: no existence check, empty first argument for the message.
`\clist_log:n`
`__clist_show:Nn`

```

10788 \cs_new_protected:Npn \clist_show:n { \__clist_show:Nn \msg_show:nnxxxx }
10789 \cs_new_protected:Npn \clist_log:n { \__clist_show:Nn \msg_log:nnxxxx }
10790 \cs_new_protected:Npn \__clist_show:Nn #1#2
10791 {
10792   #1 { LaTeX/kernel } { show-clist }
10793   { } { \clist_map_function:nN {#2} \msg_show_item:n } { } { }
10794 }

```

(End definition for `\clist_show:n`, `\clist_log:n`, and `__clist_show:Nn`. These functions are documented on page 127.)

16.11 Scratch comma lists

`\l_tmpa_clist` Temporary comma list variables.
`\l_tmpb_clist`
`\g_tmpa_clist`
`\g_tmpb_clist`

```

10795 \clist_new:N \l_tmpa_clist
10796 \clist_new:N \l_tmpb_clist
10797 \clist_new:N \g_tmpa_clist
10798 \clist_new:N \g_tmpb_clist

```

(End definition for `\l_tmpa_clist` and others. These variables are documented on page 127.)

```

10799 </initex | package>

```


17 I3token implementation

10800 $\langle *initex | package \rangle$

10801 $\langle @@=char \rangle$

17.1 Internal auxiliaries

`\s__char_stop` Internal scan mark.

10802 `\scan_new:N \s__char_stop`

(End definition for `\s__char_stop`.)

`\q__char_no_value` Internal recursion quarks.

10803 `\quark_new:N \q__char_no_value`

(End definition for `\q__char_no_value`.)

`__char_quark_if_no_value p:N` Functions to query recursion quarks.

`__char_quark_if_no_value:NTF` 10804 `__kernel_quark_new_conditional:Nn __char_quark_if_no_value:N { TF }`

(End definition for `__char_quark_if_no_value:NTF`.)

17.2 Manipulating and interrogating character tokens

`\char_set_catcode:nn` Simple wrappers around the primitives.

`\char_value_catcode:n`

`\char_show_value_catcode:n`

10805 `\cs_new_protected:Npn \char_set_catcode:nn #1#2`

10806 `{ \tex_catcode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }`

10807 `\cs_new:Npn \char_value_catcode:n #1`

10808 `{ \tex_the:D \tex_catcode:D \int_eval:n {#1} \exp_stop_f: }`

10809 `\cs_new_protected:Npn \char_show_value_catcode:n #1`

10810 `{ \exp_args:Nf \tl_show:n { \char_value_catcode:n {#1} } }`

(End definition for `\char_set_catcode:nn`, `\char_value_catcode:n`, and `\char_show_value_catcode:n`.
These functions are documented on page 131.)

`\char_set_catcode_escape:N`

`\char_set_catcode_group_begin:N`

`\char_set_catcode_group_end:N`

`\char_set_catcode_math_toggle:N`

`\char_set_catcode_alignment:N`

10811 `\cs_new_protected:Npn \char_set_catcode_escape:N #1`

10812 `{ \char_set_catcode:nn { '#1 } { 0 } }`

10813 `\cs_new_protected:Npn \char_set_catcode_group_begin:N #1`

10814 `{ \char_set_catcode:nn { '#1 } { 1 } }`

10815 `\cs_new_protected:Npn \char_set_catcode_group_end:N #1`

10816 `{ \char_set_catcode:nn { '#1 } { 2 } }`

10817 `\cs_new_protected:Npn \char_set_catcode_math_toggle:N #1`

10818 `{ \char_set_catcode:nn { '#1 } { 3 } }`

10819 `\cs_new_protected:Npn \char_set_catcode_alignment:N #1`

10820 `{ \char_set_catcode:nn { '#1 } { 4 } }`

10821 `\cs_new_protected:Npn \char_set_catcode_end_line:N #1`

10822 `{ \char_set_catcode:nn { '#1 } { 5 } }`

10823 `\cs_new_protected:Npn \char_set_catcode_parameter:N #1`

10824 `{ \char_set_catcode:nn { '#1 } { 6 } }`

10825 `\cs_new_protected:Npn \char_set_catcode_math_superscript:N #1`

10826 `{ \char_set_catcode:nn { '#1 } { 7 } }`

10827 `\cs_new_protected:Npn \char_set_catcode_math_subscript:N #1`

10828 `{ \char_set_catcode:nn { '#1 } { 8 } }`

10829 `\cs_new_protected:Npn \char_set_catcode_ignore:N #1`

```

10830 { \char_set_catcode:nn { '#1 } { 9 } }
10831 \cs_new_protected:Npn \char_set_catcode_space:N #1
10832 { \char_set_catcode:nn { '#1 } { 10 } }
10833 \cs_new_protected:Npn \char_set_catcode_letter:N #1
10834 { \char_set_catcode:nn { '#1 } { 11 } }
10835 \cs_new_protected:Npn \char_set_catcode_other:N #1
10836 { \char_set_catcode:nn { '#1 } { 12 } }
10837 \cs_new_protected:Npn \char_set_catcode_active:N #1
10838 { \char_set_catcode:nn { '#1 } { 13 } }
10839 \cs_new_protected:Npn \char_set_catcode_comment:N #1
10840 { \char_set_catcode:nn { '#1 } { 14 } }
10841 \cs_new_protected:Npn \char_set_catcode_invalid:N #1
10842 { \char_set_catcode:nn { '#1 } { 15 } }

```

(End definition for `\char_set_catcode_escape:N` and others. These functions are documented on page 130.)

```

\char_set_catcode_escape:n
\char_set_catcode_group_begin:n
\char_set_catcode_group_end:n
\char_set_catcode_math_toggle:n
\char_set_catcode_alignment:n
\char_set_catcode_end_line:n
\char_set_catcode_parameter:n
\char_set_catcode_math_superscript:n
\char_set_catcode_math_subscript:n
\char_set_catcode_ignore:n
\char_set_catcode_space:n
\char_set_catcode_letter:n
\char_set_catcode_other:n
\char_set_catcode_active:n
\char_set_catcode_comment:n
\char_set_catcode_invalid:n

10843 \cs_new_protected:Npn \char_set_catcode_escape:n #1
10844 { \char_set_catcode:nn {#1} { 0 } }
10845 \cs_new_protected:Npn \char_set_catcode_group_begin:n #1
10846 { \char_set_catcode:nn {#1} { 1 } }
10847 \cs_new_protected:Npn \char_set_catcode_group_end:n #1
10848 { \char_set_catcode:nn {#1} { 2 } }
10849 \cs_new_protected:Npn \char_set_catcode_math_toggle:n #1
10850 { \char_set_catcode:nn {#1} { 3 } }
10851 \cs_new_protected:Npn \char_set_catcode_alignment:n #1
10852 { \char_set_catcode:nn {#1} { 4 } }
10853 \cs_new_protected:Npn \char_set_catcode_end_line:n #1
10854 { \char_set_catcode:nn {#1} { 5 } }
10855 \cs_new_protected:Npn \char_set_catcode_parameter:n #1
10856 { \char_set_catcode:nn {#1} { 6 } }
10857 \cs_new_protected:Npn \char_set_catcode_math_superscript:n #1
10858 { \char_set_catcode:nn {#1} { 7 } }
10859 \cs_new_protected:Npn \char_set_catcode_math_subscript:n #1
10860 { \char_set_catcode:nn {#1} { 8 } }
10861 \cs_new_protected:Npn \char_set_catcode_ignore:n #1
10862 { \char_set_catcode:nn {#1} { 9 } }
10863 \cs_new_protected:Npn \char_set_catcode_space:n #1
10864 { \char_set_catcode:nn {#1} { 10 } }
10865 \cs_new_protected:Npn \char_set_catcode_letter:n #1
10866 { \char_set_catcode:nn {#1} { 11 } }
10867 \cs_new_protected:Npn \char_set_catcode_other:n #1
10868 { \char_set_catcode:nn {#1} { 12 } }
10869 \cs_new_protected:Npn \char_set_catcode_active:n #1
10870 { \char_set_catcode:nn {#1} { 13 } }
10871 \cs_new_protected:Npn \char_set_catcode_comment:n #1
10872 { \char_set_catcode:nn {#1} { 14 } }
10873 \cs_new_protected:Npn \char_set_catcode_invalid:n #1
10874 { \char_set_catcode:nn {#1} { 15 } }

```

(End definition for `\char_set_catcode_escape:n` and others. These functions are documented on page 130.)

```

\char_set_mathcode:nn
\char_value_mathcode:n
\char_show_value_mathcode:n
\char_set_lccode:nn
\char_value_lccode:n
\char_show_value_lccode:n
\char_set_uccode:nn
\char_value_uccode:n
\char_show_value_uccode:n
\char_set_sfcode:nn
\char_value_sfcode:n

```

Pretty repetitive, but necessary!

```

10875 \cs_new_protected:Npn \char_set_mathcode:nn #1#2
10876 { \tex_mathcode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }
10877 \cs_new:Npn \char_value_mathcode:n #1
10878 { \tex_the:D \tex_mathcode:D \int_eval:n {#1} \exp_stop_f: }
10879 \cs_new_protected:Npn \char_show_value_mathcode:n #1
10880 { \exp_args:Nf \tl_show:n { \char_value_mathcode:n {#1} } }
10881 \cs_new_protected:Npn \char_set_lccode:nn #1#2
10882 { \tex_lccode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }
10883 \cs_new:Npn \char_value_lccode:n #1
10884 { \tex_the:D \tex_lccode:D \int_eval:n {#1} \exp_stop_f: }
10885 \cs_new_protected:Npn \char_show_value_lccode:n #1
10886 { \exp_args:Nf \tl_show:n { \char_value_lccode:n {#1} } }
10887 \cs_new_protected:Npn \char_set_uccode:nn #1#2
10888 { \tex_uccode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }
10889 \cs_new:Npn \char_value_uccode:n #1
10890 { \tex_the:D \tex_uccode:D \int_eval:n {#1} \exp_stop_f: }
10891 \cs_new_protected:Npn \char_show_value_uccode:n #1
10892 { \exp_args:Nf \tl_show:n { \char_value_uccode:n {#1} } }
10893 \cs_new_protected:Npn \char_set_sfcode:nn #1#2
10894 { \tex_sfcode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }
10895 \cs_new:Npn \char_value_sfcode:n #1
10896 { \tex_the:D \tex_sfcode:D \int_eval:n {#1} \exp_stop_f: }
10897 \cs_new_protected:Npn \char_show_value_sfcode:n #1
10898 { \exp_args:Nf \tl_show:n { \char_value_sfcode:n {#1} } }

```

(End definition for `\char_set_mathcode:nn` and others. These functions are documented on page 132.)

`\l_char_active_seq`
`\l_char_special_seq`

Two sequences for dealing with special characters. The first is characters which may be active, the second longer list is for “special” characters more generally. Both lists are escaped so that for example bulk code assignments can be carried out. In both cases, the order is by ASCII character code (as is done in for example `\ExplSyntaxOn`).

```

10899 \seq_new:N \l_char_special_seq
10900 \seq_set_split:Nnn \l_char_special_seq { }
10901 { \ \ " \# \$ \% \& \^ \_ \{ \} \~ }
10902 \seq_new:N \l_char_active_seq
10903 \seq_set_split:Nnn \l_char_active_seq { }
10904 { \ " \$ \& \^ \_ \~ }

```

(End definition for `\l_char_active_seq` and `\l_char_special_seq`. These variables are documented on page 132.)

17.3 Creating character tokens

`\char_set_active_eq:NN`
`\char_set_active_eq:Nc`
`\char_gset_active_eq:NN`
`\char_gset_active_eq:Nc`
`\char_set_active_eq:nN`
`\char_set_active_eq:nc`
`\char_gset_active_eq:nN`
`\char_gset_active_eq:nc`

Four simple functions with very similar definitions, so set up using an auxiliary. These are similar to LuaTeX’s `\letcharcode` primitive.

```

10905 \group_begin:
10906 \char_set_catcode_active:N \^^@
10907 \cs_set_protected:Npn \__char_tmp:nN #1#2
10908 {
10909 \cs_new_protected:cpn { #1 :nN } ##1
10910 {
10911 \group_begin:
10912 \char_set_lccode:nn { \^^@ } { ##1 }
10913 \tex_lowercase:D { \group_end: #2 ^^@ }

```

```

10914     }
10915     \cs_new_protected:cpx { #1 :NN } ##1
10916     { \exp_not:c { #1 : nN } { '##1 } }
10917   }
10918   \__char_tmp:nN { char_set_active_eq } \cs_set_eq:NN
10919   \__char_tmp:nN { char_gset_active_eq } \cs_gset_eq:NN
10920 \group_end:
10921 \cs_generate_variant:Nn \char_set_active_eq:NN { Nc }
10922 \cs_generate_variant:Nn \char_gset_active_eq:NN { Nc }
10923 \cs_generate_variant:Nn \char_set_active_eq:nN { nc }
10924 \cs_generate_variant:Nn \char_gset_active_eq:nN { nc }

```

(End definition for `\char_set_active_eq:NN` and others. These functions are documented on page 128.)

`__char_int_to_roman:w` For efficiency in 8-bit engines, we use the faster primitive approach to making roman numerals.

```

10925 \cs_new_eq:NN \__char_int_to_roman:w \tex_romannumeral:D

```

(End definition for `__char_int_to_roman:w`.)

`\char_generate:nn` The aim here is to generate characters of (broadly) arbitrary category code. Where possible, that is done using engine support (Xe_{La}TeX, Lua_{La}TeX). There are though various issues which are covered below. At the interface layer, turn the two arguments into integers up-front so this is only done once.

```

\__char_generate_aux:nn
\__char_generate_aux:nnw
\__char_generate_auxii:nnw
  \l__char_tmp_tl
  \__char_generate_invalid_catcode:
10926 \cs_new:Npn \char_generate:nn #1#2
10927 {
10928   \exp:w \exp_after:wN \__char_generate_aux:w
10929   \int_value:w \int_eval:n {#1} \exp_after:wN ;
10930   \int_value:w \int_eval:n {#2} ;
10931 }

```

Before doing any actual conversion, first some special case filtering. Spaces are out here as Lua_{La}TeX emulation only makes normal (charcode 32 spaces). However, `~@` is filtered out separately as that can't be done with macro emulation either, so is flagged up separately. That done, hand off to the engine-dependent part.

```

10932 \cs_new:Npn \__char_generate_aux:w #1 ; #2 ;
10933 {
10934   \if_int_compare:w #2 = 10 \exp_stop_f:
10935   \if_int_compare:w #1 = 0 \exp_stop_f:
10936     \__kernel_msg_expandable_error:nn { kernel } { char-null-space }
10937   \else:
10938     \__kernel_msg_expandable_error:nn { kernel } { char-space }
10939   \fi:
10940 \else:
10941   \if_int_odd:w 0
10942     \if_int_compare:w #2 < 1 \exp_stop_f: 1 \fi:
10943     \if_int_compare:w #2 = 5 \exp_stop_f: 1 \fi:
10944     \if_int_compare:w #2 = 9 \exp_stop_f: 1 \fi:
10945     \if_int_compare:w #2 > 13 \exp_stop_f: 1 \fi: \exp_stop_f:
10946     \__kernel_msg_expandable_error:nn { kernel }
10947     { char-invalid-catcode }
10948   \else:
10949     \if_int_odd:w 0
10950     \if_int_compare:w #1 < 0 \exp_stop_f: 1 \fi:

```

```

10951         \if_int_compare:w #1 > \c_max_char_int 1 \fi: \exp_stop_f:
10952         \__kernel_msg_expandable_error:nn { kernel }
10953         { char-out-of-range }
10954     \else:
10955         \__char_generate_aux:nnw {#1} {#2}
10956     \fi:
10957 \fi:
10958 \fi:
10959 \exp_end:
10960 }
10961 \tl_new:N \l__char_tmp_tl

```

Engine-dependent definitions are now needed for the implementation. For LuaTeX and XeTeX there is engine-level support. They can do cases that macro emulation can't. All of those are filtered out here using a primitive-based boolean expression to avoid fixing the category code of the null character used in the false branch (for 8-bit engines). The final level is the basic definition at the engine level: the arguments here are integers so there is no need to worry about them too much. Older versions of XeTeX cannot generate active characters so we filter that: at some future stage that may change: the slightly odd ordering of auxiliaries reflects that.

```

10962 \group_begin:
10963 (*package)
10964   \char_set_catcode_active:N ^^L
10965   \cs_set:Npn ^^L { }
10966 \group_end:
10967 \char_set_catcode_other:n { 0 }
10968 \if_int_odd:w 0
10969   \sys_if_engine luatex:T { 1 }
10970   \sys_if_engine xetex:T { 1 } \exp_stop_f:
10971   \sys_if_engine luatex:TF
10972   {
10973     \cs_new:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
10974     {
10975       #3
10976       \exp_after:wN \exp_after:wN \exp_after:wN \exp_end:
10977       \lua_now:e { l3kernel.charcat(#1, #2) }
10978     }
10979   }
10980   {
10981     \cs_new:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
10982     {
10983       #3
10984       \exp_after:wN \exp_end:
10985       \tex_Ucharcat:D #1 \exp_stop_f: #2 \exp_stop_f:
10986     }
10987     \cs_if_exist:NF \tex_expanded:D
10988     {
10989       \cs_new_eq:NN \__char_generate_auxii:nnw \__char_generate_aux:nnw
10990       \cs_gset:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
10991       {
10992         #3
10993         \if_int_compare:w #2 = 13 \exp_stop_f:
10994           \__kernel_msg_expandable_error:nn { kernel } { char-active }
10995         \else:

```

```

10996         \__char_generate_auxii:nw {#1} {#2}
10997         \fi:
10998         \exp_end:
10999     }
11000 }
11001 }
11002 \else:

```

For engines where `\Ucharcat` isn't available or emulated, we have to work in macros, and cover only the 8-bit range. The first stage is to build up a `tl` containing `^^@` with each category code that can be accessed in this way, with an error set up for the other cases. This is all done such that it can be quickly accessed using a `\if_case:w` low-level conditional. There are a few things to notice here. As `^^L` is `\outer` we need to locally set it to avoid a problem. To get open/close braces into the list, they are set up using `\if_false:` pairing and are then x-type expanded together into the desired form.

```

11003     \tl_set:Nn \l__char_tmp_tl { \exp_not:N \or: }
11004     \char_set_catcode_group_begin:n { 0 } % {
11005     \tl_put_right:Nn \l__char_tmp_tl { ^^@ \if_false: } }
11006     \char_set_catcode_group_end:n { 0 }
11007     \tl_put_right:Nn \l__char_tmp_tl { { \fi: \exp_not:N \or: ^^@ } % }
11008     \tl_set:Nx \l__char_tmp_tl { \l__char_tmp_tl }
11009     \char_set_catcode_math_toggle:n { 0 }
11010     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
11011     \char_set_catcode_alignment:n { 0 }
11012     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
11013     \tl_put_right:Nn \l__char_tmp_tl { \or: } }
11014     \char_set_catcode_parameter:n { 0 }
11015     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
11016     \char_set_catcode_math_superscript:n { 0 }
11017     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
11018     \char_set_catcode_math_subscript:n { 0 }
11019     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
11020     \tl_put_right:Nn \l__char_tmp_tl { \or: } }

```

For making spaces, there needs to be an o-type expansion of a `\use:n` (or some other tokenization) to avoid dropping the space.

```

11021     \char_set_catcode_space:n { 0 }
11022     \tl_put_right:No \l__char_tmp_tl { \use:n { \or: } ^^@ }
11023     \char_set_catcode_letter:n { 0 }
11024     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
11025     \char_set_catcode_other:n { 0 }
11026     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
11027     \char_set_catcode_active:n { 0 }
11028     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```

Convert the above temporary list into a series of constant token lists, one for each character code, using `\tex_lowercase:D` to convert `^^@` in each case. The x-type expansion ensures that `\tex_lowercase:D` receives the contents of the token list. In package mode, `^^L` is awkward hence this is done in three parts. Notice that at this stage `^^@` is active.

```

11029     \cs_set_protected:Npn \__char_tmp:n #1
11030     {
11031         \char_set_lccode:nn { 0 } {#1}
11032         \char_set_lccode:nn { 32 } {#1}
11033         \exp_args:Nx \tex_lowercase:D

```

```

11034         {
11035             \tl_const:Nn
11036             \exp_not:c { c__char_ \__char_int_to_roman:w #1 _tl }
11037             { \exp_not:o \l__char_tmp_tl }
11038         }
11039     }
11040 <*package>
11041     \int_step_function:nnN { 0 } { 11 } \__char_tmp:n
11042     \group_begin:
11043     \tl_replace_once:Nnn \l__char_tmp_tl { ^~@ } { \ERROR }
11044     \__char_tmp:n { 12 }
11045     \group_end:
11046     \int_step_function:nnN { 13 } { 255 } \__char_tmp:n
11047 </package>
11048 <*initex>
11049     \int_step_function:nnN { 0 } { 255 } \__char_tmp:n
11050 </initex>

```

As TeX is very unhappy if it finds an alignment character inside a primitive `\halign` even when skipping false branches, some precautions are required. TeX is happy if the token is hidden between braces within `\if_false: ... \fi:`.

```

11051     \cs_new:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
11052     {
11053         #3
11054         \if_false: { \fi:
11055             \exp_after:wN \exp_after:wN
11056             \exp_after:wN \exp_end:
11057             \exp_after:wN \exp_after:wN
11058             \if_case:w #2
11059             \exp_last_unbraced:Nv \exp_stop_f:
11060             { c__char_ \__char_int_to_roman:w #1 _tl }
11061             \or: }
11062             \fi:
11063         }
11064     \fi:
11065 \group_end:

```

(End definition for `\char_generate:nn` and others. This function is documented on page 129.)

`\char_to_utfviii_bytes:n`

This code converts a codepoint into the correct UTF-8 representation. In terms of the algorithm itself, see <https://en.wikipedia.org/wiki/UTF-8> for the octet pattern.

```

\__char_to_utfviii_bytes_auxi:n
\__char_to_utfviii_bytes_auxii:Nnn
\__char_to_utfviii_bytes_auxiii:n
\__char_to_utfviii_bytes_outputi:nw
\__char_to_utfviii_bytes_outputii:nw
\__char_to_utfviii_bytes_outputiii:nw
\__char_to_utfviii_bytes_outputiv:nw
\__char_to_utfviii_bytes_output:nwn
\__char_to_utfviii_bytes_output:fnn
\__char_to_utfviii_bytes_end:
11066 \cs_new:Npn \char_to_utfviii_bytes:n #1
11067 {
11068     \exp_args:Nf \__char_to_utfviii_bytes_auxi:n
11069     { \int_eval:n {#1} }
11070 }
11071 \cs_new:Npn \__char_to_utfviii_bytes_auxi:n #1
11072 {
11073     \if_int_compare:w #1 > "80 \exp_stop_f:
11074     \if_int_compare:w #1 < "800 \exp_stop_f:
11075     \__char_to_utfviii_bytes_outputi:nw
11076     { \__char_to_utfviii_bytes_auxii:Nnn C {#1} { 64 } }
11077     \__char_to_utfviii_bytes_outputii:nw
11078     { \__char_to_utfviii_bytes_auxiii:n {#1} }

```

```

11079 \else:
11080 \if_int_compare:w #1 < "10000 \exp_stop_f:
11081 \__char_to_utfviii_bytes_outputi:nw
11082 { \__char_to_utfviii_bytes_auxii:Nnn E {#1} { 64 * 64 } }
11083 \__char_to_utfviii_bytes_outputii:nw
11084 {
11085 \__char_to_utfviii_bytes_auxiii:n
11086 { \int_div_truncate:nn {#1} { 64 } }
11087 }
11088 \__char_to_utfviii_bytes_outputiii:nw
11089 { \__char_to_utfviii_bytes_auxiii:n {#1} }
11090 \else:
11091 \__char_to_utfviii_bytes_outputi:nw
11092 {
11093 \__char_to_utfviii_bytes_auxii:Nnn F
11094 {#1} { 64 * 64 * 64 }
11095 }
11096 \__char_to_utfviii_bytes_outputii:nw
11097 {
11098 \__char_to_utfviii_bytes_auxiii:n
11099 { \int_div_truncate:nn {#1} { 64 * 64 } }
11100 }
11101 \__char_to_utfviii_bytes_outputiii:nw
11102 {
11103 \__char_to_utfviii_bytes_auxiii:n
11104 { \int_div_truncate:nn {#1} { 64 } }
11105 }
11106 \__char_to_utfviii_bytes_outputiv:nw
11107 { \__char_to_utfviii_bytes_auxiii:n {#1} }
11108 \fi:
11109 \fi:
11110 \else:
11111 \__char_to_utfviii_bytes_outputi:nw {#1}
11112 \fi:
11113 \__char_to_utfviii_bytes_end: { } { } { } { } { }
11114 }
11115 \cs_new:Npn \__char_to_utfviii_bytes_auxii:Nnn #1#2#3
11116 { "#10 + \int_div_truncate:nn {#2} {#3} }
11117 \cs_new:Npn \__char_to_utfviii_bytes_auxiii:n #1
11118 { \int_mod:nn {#1} { 64 } + 128 }
11119 \cs_new:Npn \__char_to_utfviii_bytes_outputi:nw
11120 #1 #2 \__char_to_utfviii_bytes_end: #3
11121 { \__char_to_utfviii_bytes_output:fnn { \int_eval:n {#1} } { } {#2} }
11122 \cs_new:Npn \__char_to_utfviii_bytes_outputii:nw
11123 #1 #2 \__char_to_utfviii_bytes_end: #3#4
11124 { \__char_to_utfviii_bytes_output:fnn { \int_eval:n {#1} } { {#3} } {#2} }
11125 \cs_new:Npn \__char_to_utfviii_bytes_outputiii:nw
11126 #1 #2 \__char_to_utfviii_bytes_end: #3#4#5
11127 {
11128 \__char_to_utfviii_bytes_output:fnn
11129 { \int_eval:n {#1} } { {#3} {#4} } {#2}
11130 }
11131 \cs_new:Npn \__char_to_utfviii_bytes_outputiv:nw
11132 #1 #2 \__char_to_utfviii_bytes_end: #3#4#5#6

```



```

11133 {
11134     \__char_to_utfviii_bytes_output:fnn
11135     { \int_eval:n {#1} } { {#3} {#4} {#5} } {#2}
11136 }
11137 \cs_new:Npn \__char_to_utfviii_bytes_output:nnn #1#2#3
11138 {
11139     #3
11140     \__char_to_utfviii_bytes_end: #2 {#1}
11141 }
11142 \cs_generate_variant:Nn \__char_to_utfviii_bytes_output:nnn { f }
11143 \cs_new:Npn \__char_to_utfviii_bytes_end: { }

```

(End definition for `\char_to_utfviii_bytes:n` and others. This function is documented on page 269.)

```

\char_to_nfd:N Look up any NFD and recursively produce the result.
\__char_to_nfd:n 11144 \cs_new:Npn \char_to_nfd:N #1
\__char_to_nfd:Nw 11145 {
11146     \cs_if_exist:cTF { c__char_nfd_ \token_to_str:N #1 _ tl }
11147     {
11148         \exp_after:wN \exp_after:wN \exp_after:wN \__char_to_nfd:Nw
11149         \exp_after:wN \exp_after:wN \exp_after:wN #1
11150         \cs:w c__char_nfd_ \token_to_str:N #1 _ tl \cs_end:
11151         \s__char_stop
11152     }
11153     { \exp_not:n {#1} }
11154 }
11155 \cs_set_eq:NN \__char_to_nfd:n \char_to_nfd:N
11156 \cs_new:Npn \__char_to_nfd:Nw #1#2#3 \s__char_stop
11157 {
11158     \exp_args:Ne \__char_to_nfd:n
11159     { \char_generate:nn { '#2 } { \__char_change_case_catcode:N #1 } }
11160     \tl_if_blank:nF {#3}
11161     {
11162         \exp_args:Ne \__char_to_nfd:n
11163         { \char_generate:nn { '#3 } { \char_value_catcode:n { '#3 } } }
11164     }
11165 }

```

(End definition for `\char_to_nfd:N`, `__char_to_nfd:n`, and `__char_to_nfd:Nw`. This function is documented on page 269.)

`\char_lowercase:N` To ensure that the category codes produced are predictable, every character is re-generated even if it is otherwise unchanged. This makes life a little interesting when we might have multiple output characters: we have to grab each of them and case change them in reverse order to maintain f-type expandability.

```

\__char_change_case:nNN 11166 \cs_new:Npn \char_lowercase:N #1
\__char_change_case:nN 11167 { \__char_change_case:nNN { lower } \char_value_lccode:n #1 }
\__char_change_case_multi:nN 11168 \cs_new:Npn \char_uppercase:N #1
\__char_change_case_multi:vN 11169 { \__char_change_case:nNN { upper } \char_value_uccode:n #1 }
\__char_change_case_multi:NNNw 11170 \cs_new:Npn \char_titlecase:N #1
\__char_change_case:NNN 11171 {
11172     \tl_if_exist:cTF { c__char_titlecase_ \token_to_str:N #1 _ tl }
11173     {
11174         \__char_change_case_multi:vN

```

`\char_str_lowercase:N`
`\char_str_uppercase:N`
`\char_str_titlecase:N`
`\char_str_foldcase:N`
`__char_str_change_case:nNN`
`__char_str_change_case:nN`

```

11175         { c__char_titlecase_ \token_to_str:N #1 _tl } #1
11176     }
11177     { \char_uppercase:N #1 }
11178 }
11179 \cs_new:Npn \char_foldcase:N #1
11180 { \__char_change_case:nNN { fold } \char_value_lccode:n #1 }
11181 \cs_new:Npn \__char_change_case:nNN #1#2#3
11182 {
11183     \tl_if_exist:cTF { c__char_ #1 case_ \token_to_str:N #3 _tl }
11184     {
11185         \__char_change_case_multi:vN
11186         { c__char_ #1 case_ \token_to_str:N #3 _tl } #3
11187     }
11188     { \exp_args:Nf \__char_change_case:nN { #2 { '#3 } } #3 }
11189 }
11190 \cs_new:Npn \__char_change_case:nN #1#2
11191 {
11192     \int_compare:nNnTF {#1} = 0
11193     { #2 }
11194     { \char_generate:nn {#1} { \__char_change_case_catcode:N #2 } }
11195 }
11196 \cs_new:Npn \__char_change_case_multi:nN #1#2
11197 { \__char_change_case_multi:NNNNw #2 #1 \q__char_no_value \q__char_no_value \s__char_stop
11198 \cs_generate_variant:Nn \__char_change_case_multi:nN { v }
11199 \cs_new:Npn \__char_change_case_multi:NNNNw #1#2#3#4#5 \s__char_stop
11200 {
11201     \__char_quark_if_no_value:NTF #4
11202     {
11203         \__char_quark_if_no_value:NTF #3
11204         { \__char_change_case:NN #1 #2 }
11205         { \__char_change_case:NNN #1 #2#3 }
11206     }
11207     { \__char_change_case:NNNN #1 #2#3#4 }
11208 }
11209 \cs_new:Npn \__char_change_case:NNN #1#2#3
11210 {
11211     \exp_args:Nnf \use:nn
11212     { \__char_change_case:NN #1 #2 }
11213     { \__char_change_case:NN #1 #3 }
11214 }
11215 \cs_new:Npn \__char_change_case:NNNN #1#2#3#4
11216 {
11217     \exp_args:Nnff \use:nnn
11218     { \__char_change_case:NN #1 #2 }
11219     { \__char_change_case:NN #1 #3 }
11220     { \__char_change_case:NN #1 #4 }
11221 }
11222 \cs_new:Npn \__char_change_case:NN #1#2
11223 { \char_generate:nn { '#2 } { \__char_change_case_catcode:N #1 } }
11224 \cs_new:Npn \__char_change_case_catcode:N #1
11225 {
11226     \if_catcode:w \exp_not:N #1 \c_math_toggle_token
11227     3
11228     \else:

```

```

11229 \if_catcode:w \exp_not:N #1 \c_alignment_token
11230 4
11231 \else:
11232 \if_catcode:w \exp_not:N #1 \c_math_superscript_token
11233 7
11234 \else:
11235 \if_catcode:w \exp_not:N #1 \c_math_subscript_token
11236 8
11237 \else:
11238 \if_catcode:w \exp_not:N #1 \c_space_token
11239 10
11240 \else:
11241 \if_catcode:w \exp_not:N #1 \c_catcode_letter_token
11242 11
11243 \else:
11244 \if_catcode:w \exp_not:N #1 \c_catcode_other_token
11245 12
11246 \else:
11247 13
11248 \fi:
11249 \fi:
11250 \fi:
11251 \fi:
11252 \fi:
11253 \fi:
11254 \fi:
11255 }

```

Same story for the string version, except category code is easier to follow. This of course makes this version significantly faster.

```

11256 \cs_new:Npn \char_str_lowercase:N #1
11257 { \__char_str_change_case:nNN { lower } \char_value_lccode:n #1 }
11258 \cs_new:Npn \char_str_uppercase:N #1
11259 { \__char_str_change_case:nNN { upper } \char_value_uccode:n #1 }
11260 \cs_new:Npn \char_str_titlecase:N #1
11261 {
11262 \tl_if_exist:cTF { c__char_titlecase_ \token_to_str:N #1 _tl }
11263 { \tl_to_str:c { c__char_titlecase_ \token_to_str:N #1 _tl } }
11264 { \char_str_uppercase:N #1 }
11265 }
11266 \cs_new:Npn \char_str_foldcase:N #1
11267 { \__char_str_change_case:nNN { fold } \char_value_lccode:n #1 }
11268 \cs_new:Npn \__char_str_change_case:nNN #1#2#3
11269 {
11270 \tl_if_exist:cTF { c__char_ #1 case_ \token_to_str:N #3 _tl }
11271 { \tl_to_str:c { c__char_ #1 case_ \token_to_str:N #3 _tl } }
11272 { \exp_args:Nf \__char_str_change_case:nN { #2 { '#3 } } #3 }
11273 }
11274 \cs_new:Npn \__char_str_change_case:nN #1#2
11275 {
11276 \int_compare:nNnTF {#1} = 0
11277 { \tl_to_str:n {#2} }
11278 { \char_generate:nn {#1} { 12 } }
11279 }

```

```

11280 \bool_lazy_or:nnF
11281 { \cs_if_exist_p:N \tex_luatexversion:D }
11282 { \cs_if_exist_p:N \tex_XeTeXversion:D }
11283 {
11284   \cs_set:Npn \__char_str_change_case:nN #1#2
11285     { \tl_to_str:n {#2} }
11286 }

```

(End definition for `\char_lowercase:N` and others. These functions are documented on page 129.)

`\c_catcode_other_space_tl` Create a space with category code 12: an “other” space.

```

11287 \tl_const:Nx \c_catcode_other_space_tl { \char_generate:nn { '\ } { 12 } }

```

(End definition for `\c_catcode_other_space_tl`. This function is documented on page 129.)

17.4 Generic tokens

```

11288 <@@=token>

```

`\s__token_stop` Internal scan marks.

```

11289 \scan_new:N \s__token_stop

```

(End definition for `\s__token_stop`.)

`\token_to_meaning:N` These are all defined in `l3basics`, as they are needed “early”. This is just a reminder!

`\token_to_meaning:c`

`\token_to_str:N`

`\token_to_str:c`

(End definition for `\token_to_meaning:N` and `\token_to_str:N`. These functions are documented on page 133.)

`\c_group_begin_token`

`\c_group_end_token`

`\c_math_toggle_token`

`\c_alignment_token`

`\c_parameter_token`

`\c_math_superscript_token`

`\c_math_subscript_token`

`\c_space_token`

`\c_catcode_letter_token`

`\c_catcode_other_token`

We define these useful tokens. For the brace and space tokens things have to be done by hand: the formal argument spec. for `\cs_new_eq:NN` does not cover them so we do things by hand. (As currently coded it would *work* with `\cs_new_eq:NN` but that’s not really a great idea to show off: we want people to stick to the defined interfaces and that includes us.) So that these few odd names go into the log when appropriate there is a need to hand-apply the `__kernel_chk_if_free_cs:N` check.

```

11290 \group_begin:
11291   \__kernel_chk_if_free_cs:N \c_group_begin_token
11292   \tex_global:D \tex_let:D \c_group_begin_token {
11293     \__kernel_chk_if_free_cs:N \c_group_end_token
11294     \tex_global:D \tex_let:D \c_group_end_token }
11295   \char_set_catcode_math_toggle:N \*
11296   \cs_new_eq:NN \c_math_toggle_token *
11297   \char_set_catcode_alignment:N \*
11298   \cs_new_eq:NN \c_alignment_token *
11299   \cs_new_eq:NN \c_parameter_token #
11300   \cs_new_eq:NN \c_math_superscript_token ^
11301   \char_set_catcode_math_subscript:N \*
11302   \cs_new_eq:NN \c_math_subscript_token *
11303   \__kernel_chk_if_free_cs:N \c_space_token
11304   \use:n { \tex_global:D \tex_let:D \c_space_token = ~ } ~
11305   \cs_new_eq:NN \c_catcode_letter_token a
11306   \cs_new_eq:NN \c_catcode_other_token 1
11307 \group_end:

```

(End definition for `\c_group_begin_token` and others. These functions are documented on page 133.)

`\c_catcode_active_tl` Not an implicit token!

```
11308 \group_begin:
11309   \char_set_catcode_active:N \*
11310   \tl_const:Nn \c_catcode_active_tl { \exp_not:N * }
11311 \group_end:
```

(End definition for `\c_catcode_active_tl`. This variable is documented on page 133.)

17.5 Token conditionals

`\token_if_group_begin_p:N` Check if token is a begin group token. We use the constant `\c_group_begin_token` for this.
`\token_if_group_begin:NTF`

```
11312 \prg_new_conditional:Npnn \token_if_group_begin:N #1 { p , T , F , TF }
11313 {
11314   \if_catcode:w \exp_not:N #1 \c_group_begin_token
11315     \prg_return_true: \else: \prg_return_false: \fi:
11316 }
```

(End definition for `\token_if_group_begin:NTF`. This function is documented on page 134.)

`\token_if_group_end_p:N` Check if token is a end group token. We use the constant `\c_group_end_token` for this.
`\token_if_group_end:NTF`

```
11317 \prg_new_conditional:Npnn \token_if_group_end:N #1 { p , T , F , TF }
11318 {
11319   \if_catcode:w \exp_not:N #1 \c_group_end_token
11320     \prg_return_true: \else: \prg_return_false: \fi:
11321 }
```

(End definition for `\token_if_group_end:NTF`. This function is documented on page 134.)

`\token_if_math_toggle_p:N` Check if token is a math shift token. We use the constant `\c_math_toggle_token` for this.
`\token_if_math_toggle:NTF`

```
11322 \prg_new_conditional:Npnn \token_if_math_toggle:N #1 { p , T , F , TF }
11323 {
11324   \if_catcode:w \exp_not:N #1 \c_math_toggle_token
11325     \prg_return_true: \else: \prg_return_false: \fi:
11326 }
```

(End definition for `\token_if_math_toggle:NTF`. This function is documented on page 134.)

`\token_if_alignment_p:N` Check if token is an alignment tab token. We use the constant `\c_alignment_token` for this.
`\token_if_alignment:NTF`

```
11327 \prg_new_conditional:Npnn \token_if_alignment:N #1 { p , T , F , TF }
11328 {
11329   \if_catcode:w \exp_not:N #1 \c_alignment_token
11330     \prg_return_true: \else: \prg_return_false: \fi:
11331 }
```

(End definition for `\token_if_alignment:NTF`. This function is documented on page 134.)

`\token_if_parameter_p:N` Check if token is a parameter token. We use the constant `\c_parameter_token` for this.
`\token_if_parameter:N \underline{TF}` We have to trick $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ a bit to avoid an error message: within a group we prevent `\c_parameter_token` from behaving like a macro parameter character. The definitions of `\prg_new_conditional:Npnn` are global, so they remain after the group.

```

11332 \group_begin:
11333 \cs_set_eq:NN \c_parameter_token \scan_stop:
11334 \prg_new_conditional:Npnn \token_if_parameter:N #1 { p , T , F , TF }
11335 {
11336     \if_catcode:w \exp_not:N #1 \c_parameter_token
11337     \prg_return_true: \else: \prg_return_false: \fi:
11338 }
11339 \group_end:

```

(End definition for `\token_if_parameter:N \underline{TF}` . This function is documented on page 134.)

`\token_if_math_superscript_p:N` Check if token is a math superscript token. We use the constant `\c_math_superscript_token` for this.
`\token_if_math_superscript:N \underline{TF}`

```

11340 \prg_new_conditional:Npnn \token_if_math_superscript:N #1
11341 { p , T , F , TF }
11342 {
11343     \if_catcode:w \exp_not:N #1 \c_math_superscript_token
11344     \prg_return_true: \else: \prg_return_false: \fi:
11345 }

```

(End definition for `\token_if_math_superscript:N \underline{TF}` . This function is documented on page 134.)

`\token_if_math_subscript_p:N` Check if token is a math subscript token. We use the constant `\c_math_subscript_token` for this.
`\token_if_math_subscript:N \underline{TF}`

```

11346 \prg_new_conditional:Npnn \token_if_math_subscript:N #1 { p , T , F , TF }
11347 {
11348     \if_catcode:w \exp_not:N #1 \c_math_subscript_token
11349     \prg_return_true: \else: \prg_return_false: \fi:
11350 }

```

(End definition for `\token_if_math_subscript:N \underline{TF}` . This function is documented on page 134.)

`\token_if_space_p:N` Check if token is a space token. We use the constant `\c_space_token` for this.

```

11351 \prg_new_conditional:Npnn \token_if_space:N #1 { p , T , F , TF }
11352 {
11353     \if_catcode:w \exp_not:N #1 \c_space_token
11354     \prg_return_true: \else: \prg_return_false: \fi:
11355 }

```

(End definition for `\token_if_space:N \underline{TF}` . This function is documented on page 134.)

`\token_if_letter_p:N` Check if token is a letter token. We use the constant `\c_catcode_letter_token` for this.

```

11356 \prg_new_conditional:Npnn \token_if_letter:N #1 { p , T , F , TF }
11357 {
11358     \if_catcode:w \exp_not:N #1 \c_catcode_letter_token
11359     \prg_return_true: \else: \prg_return_false: \fi:
11360 }

```

(End definition for `\token_if_letter:N \underline{TF}` . This function is documented on page 135.)

`\token_if_other_p:N` Check if token is an other char token. We use the constant `\c_catcode_other_token`
`\token_if_other:N \underline{TF}` for this.

```
11361 \prg_new_conditional:Npnn \token_if_other:N #1 { p , T , F , TF }
11362 {
11363     \if_catcode:w \exp_not:N #1 \c_catcode_other_token
11364     \prg_return_true: \else: \prg_return_false: \fi:
11365 }
```

(End definition for `\token_if_other:N \underline{TF}` . This function is documented on page 135.)

`\token_if_active_p:N` Check if token is an active char token. We use the constant `\c_catcode_active_tl` for
`\token_if_active:N \underline{TF}` this. A technical point is that `\c_catcode_active_tl` is in fact a macro expanding to
`\exp_not:N *`, where `*` is active.

```
11366 \prg_new_conditional:Npnn \token_if_active:N #1 { p , T , F , TF }
11367 {
11368     \if_catcode:w \exp_not:N #1 \c_catcode_active_tl
11369     \prg_return_true: \else: \prg_return_false: \fi:
11370 }
```

(End definition for `\token_if_active:N \underline{TF}` . This function is documented on page 135.)

`\token_if_eq_meaning_p:NN` Check if the tokens #1 and #2 have same meaning.

`\token_if_eq_meaning:NN \underline{TF}`

```
11371 \prg_new_conditional:Npnn \token_if_eq_meaning:NN #1#2 { p , T , F , TF }
11372 {
11373     \if_meaning:w #1 #2
11374     \prg_return_true: \else: \prg_return_false: \fi:
11375 }
```

(End definition for `\token_if_eq_meaning:NN \underline{TF}` . This function is documented on page 135.)

`\token_if_eq_catcode_p:NN` Check if the tokens #1 and #2 have same category code.

`\token_if_eq_catcode:NN \underline{TF}`

```
11376 \prg_new_conditional:Npnn \token_if_eq_catcode:NN #1#2 { p , T , F , TF }
11377 {
11378     \if_catcode:w \exp_not:N #1 \exp_not:N #2
11379     \prg_return_true: \else: \prg_return_false: \fi:
11380 }
```

(End definition for `\token_if_eq_catcode:NN \underline{TF}` . This function is documented on page 135.)

`\token_if_eq_charcode_p:NN` Check if the tokens #1 and #2 have same character code.

`\token_if_eq_charcode:NN \underline{TF}`

```
11381 \prg_new_conditional:Npnn \token_if_eq_charcode:NN #1#2 { p , T , F , TF }
11382 {
11383     \if_charcode:w \exp_not:N #1 \exp_not:N #2
11384     \prg_return_true: \else: \prg_return_false: \fi:
11385 }
```

(End definition for `\token_if_eq_charcode:NN \underline{TF}` . This function is documented on page 135.)

`\token_if_macro_p:N` When a token is a macro, `\token_to_meaning:N` always outputs something like
`\token_if_macro:N \underline{TF}` `\long macro:#1->#1` so we could naively check to see if the meaning contains `->`.
`__token_if_macro_p:w` However, this can fail the five `\...mark` primitives, whose meaning has the form
`\...mark:<user material>`. The problem is that the `<user material>` can contain `->`.

However, only characters, macros, and marks can contain the colon character. The idea is thus to grab until the first `:`, and analyse what is left. However, macros can have

any combination of `\long`, `\protected` or `\outer` (not used in L^AT_EX3) before the string `macro:`. We thus only select the part of the meaning between the first `ma` and the first following `:`. If this string is `cro`, then we have a macro. If the string is `rk`, then we have a mark. The string can also be `cro parameter character` for a colon with a weird category code (namely the usual category code of `#`). Otherwise, it is empty.

This relies on the fact that `\long`, `\protected`, `\outer` cannot contain `ma`, regardless of the escape character, even if the escape character is `m...`.

Both `ma` and `:` must be of category code 12 (other), so are detokenized.

```

11386 \use:x
11387 {
11388   \prg_new_conditional:Npnn \exp_not:N \token_if_macro:N #1
11389   { p , T , F , TF }
11390   {
11391     \exp_not:N \exp_after:wN \exp_not:N \__token_if_macro_p:w
11392     \exp_not:N \token_to_meaning:N #1 \tl_to_str:n { ma : }
11393     \s__token_stop
11394   }
11395   \cs_new:Npn \exp_not:N \__token_if_macro_p:w
11396   ##1 \tl_to_str:n { ma } ##2 \c_colon_str ##3 \s__token_stop
11397 }
11398 {
11399   \str_if_eq:nnTF { #2 } { cro }
11400   { \prg_return_true: }
11401   { \prg_return_false: }
11402 }

```

(End definition for `\token_if_macro:N` and `__token_if_macro_p:w`. This function is documented on page 135.)

`\token_if_cs_p:N` Check if token has same catcode as a control sequence. This follows the same pattern as `\token_if_letter:N` etc. We use `\scan_stop:` for this.

`\token_if_cs:N` *TF*

```

11403 \prg_new_conditional:Npnn \token_if_cs:N #1 { p , T , F , TF }
11404 {
11405   \if_catcode:w \exp_not:N #1 \scan_stop:
11406   \prg_return_true: \else: \prg_return_false: \fi:
11407 }

```

(End definition for `\token_if_cs:N`. This function is documented on page 135.)

`\token_if_expandable_p:N` Check if token is expandable. We use the fact that T_EX temporarily converts `\exp_not:N` $\langle token \rangle$ into `\scan_stop:` if $\langle token \rangle$ is expandable. An undefined token is not considered as expandable. No problem nesting the conditionals, since the third `#1` is only skipped if it is non-expandable (hence not part of T_EX's conditional apparatus).

`\token_if_expandable:N` *TF*

```

11408 \prg_new_conditional:Npnn \token_if_expandable:N #1 { p , T , F , TF }
11409 {
11410   \exp_after:wN \if_meaning:w \exp_not:N #1 #1
11411   \prg_return_false:
11412   \else:
11413     \if_cs_exist:N #1
11414     \prg_return_true:
11415     \else:
11416     \prg_return_false:
11417   \fi:

```



```

11418     \fi:
11419   }

```

(End definition for `\token_if_expandable:NTF`. This function is documented on page 135.)

```

\__token_delimit_by_char:w These auxiliary functions are used below to define some conditionals which detect whether
\__token_delimit_by_count:w the \meaning of their argument begins with a particular string. Each auxiliary takes an
\__token_delimit_by_dimen:w argument delimited by a string, a second one delimited by \s__token_stop, and returns
\__token_delimit_by_macro:w the first one and its delimiter. This result is eventually compared to another string.
\__token_delimit_by_muskip:w
\__token_delimit_by_skip:w
\__token_delimit_by_toks:w
11420 \group_begin:
11421 \cs_set_protected:Npn \__token_tmp:w #1
11422 {
11423   \use:x
11424   {
11425     \cs_new:Npn \exp_not:c { __token_delimit_by_ #1 :w }
11426     #####1 \tl_to_str:n {#1} #####2 \s__token_stop
11427     { #####1 \tl_to_str:n {#1} }
11428   }
11429 }
11430 \__token_tmp:w { char" }
11431 \__token_tmp:w { count }
11432 \__token_tmp:w { dimen }
11433 \__token_tmp:w { macro }
11434 \__token_tmp:w { muskip }
11435 \__token_tmp:w { skip }
11436 \__token_tmp:w { toks }
11437 \group_end:

```

(End definition for `__token_delimit_by_char:w` and others.)

```

\token_if_chardef_p:N Each of these conditionals tests whether its argument's \meaning starts with a given
\token_if_chardef:NTF string. This is essentially done by having an auxiliary grab an argument delimited by the
\token_if_mathchardef_p:N string and testing whether the argument was empty. Of course, a copy of this string must
\token_if_mathchardef:NTF first be added to the end of the \meaning to avoid a runaway argument in case it does
\token_if_long_macro_p:N not contain the string. Two complications arise. First, the escape character is not fixed,
\token_if_long_macro:NTF and cannot be included in the delimiter of the auxiliary function (this function cannot be
\token_if_protected_macro_p:N defined on the fly because tests must remain expandable): instead the first argument of
\token_if_protected_macro:NTF the auxiliary (plus the delimiter to avoid complications with trailing spaces) is compared
\token_if_protected_long_macro_p:N using \str_if_eq:eeTF to the result of applying \token_to_str:N to a control sequence.
\token_if_protected_long_macro:NTF Second, the \meaning of primitives such as \dimen or \dimendef starts in the same way
\token_if_dim_register_p:N as registers such as \dimen123, so they must be tested for.
\token_if_dim_register:NTF
\token_if_int_register_p:N
\token_if_int_register:NTF
\token_if_muskip_register_p:N
\token_if_muskip_register:NTF
\token_if_skip_register_p:N
\token_if_skip_register:NTF
\token_if_toks_register_p:N
\token_if_toks_register:NTF

```

Characters used as delimiters must have catcode 12 and are obtained through `\tl_to_str:n`. This requires doing all definitions within `x`-expansion. The temporary function `__token_tmp:w` used to define each conditional receives three arguments: the name of the conditional, the auxiliary's delimiter (also used to name the auxiliary), and the string to which one compares the auxiliary's result. Note that the `\meaning` of a protected long macro starts with `\protected\long macro`, with no space after `\protected` but a space after `\long`, hence the mixture of `\token_to_str:N` and `\tl_to_str:n`.

For the first five conditionals, `\cs_if_exist:cT` turns out to be `false`, and the code boils down to a string comparison between the result of the auxiliary on the `\meaning` of the conditional's argument `#####1`, and `#3`. Both are evaluated at run-time, as this is important to get the correct escape character.

The other five conditionals have additional code that compares the argument #####1 to two T_EX primitives which would wrongly be recognized as registers otherwise. Despite using T_EX's primitive conditional construction, this does not break when #####1 is itself a conditional, because branches of the conditionals are only skipped if #####1 is one of the two primitives that are tested for (which are not T_EX conditionals).

```

11438 \group_begin:
11439 \cs_set_protected:Npn \__token_tmp:w #1#2#3
11440 {
11441   \use:x
11442   {
11443     \prg_new_conditional:Npnn \exp_not:c { token_if_ #1 :N } #####1
11444     { p , T , F , TF }
11445     {
11446       \cs_if_exist:cT { tex_ #2 :D }
11447       {
11448         \exp_not:N \if_meaning:w #####1 \exp_not:c { tex_ #2 :D }
11449         \exp_not:N \prg_return_false:
11450         \exp_not:N \else:
11451         \exp_not:N \if_meaning:w #####1 \exp_not:c { tex_ #2 def:D }
11452         \exp_not:N \prg_return_false:
11453         \exp_not:N \else:
11454       }
11455       \exp_not:N \str_if_eq:eeTF
11456       {
11457         \exp_not:N \exp_after:wN
11458         \exp_not:c { __token_delimit_by_ #2 :w }
11459         \exp_not:N \token_to_meaning:N #####1
11460         ? \tl_to_str:n {#2} \s_token_stop
11461       }
11462       { \exp_not:n {#3} }
11463       { \exp_not:N \prg_return_true: }
11464       { \exp_not:N \prg_return_false: }
11465       \cs_if_exist:cT { tex_ #2 :D }
11466       {
11467         \exp_not:N \fi:
11468         \exp_not:N \fi:
11469       }
11470     }
11471   }
11472 }
11473 \__token_tmp:w { chardef } { char" } { \token_to_str:N \char" }
11474 \__token_tmp:w { mathchardef } { char" } { \token_to_str:N \mathchar" }
11475 \__token_tmp:w { long_macro } { macro } { \tl_to_str:n { \long } macro }
11476 \__token_tmp:w { protected_macro } { macro }
11477   { \tl_to_str:n { \protected } macro }
11478 \__token_tmp:w { protected_long_macro } { macro }
11479   { \token_to_str:N \protected \tl_to_str:n { \long } macro }
11480 \__token_tmp:w { dim_register } { dimen } { \token_to_str:N \dimen }
11481 \__token_tmp:w { int_register } { count } { \token_to_str:N \count }
11482 \__token_tmp:w { muskip_register } { muskip } { \token_to_str:N \muskip }
11483 \__token_tmp:w { skip_register } { skip } { \token_to_str:N \skip }
11484 \__token_tmp:w { toks_register } { toks } { \token_to_str:N \toks }
11485 \group_end:

```

(End definition for `\token_if_chardef:NTF` and others. These functions are documented on page 136.)

`\token_if_primitive_p:N`

`\token_if_primitive:NTF`

`__token_if_primitive:NNw`

`__token_if_primitive_space:w`

`__token_if_primitive_nullfont:N`

`__token_if_primitive_loop:N`

`__token_if_primitive:Nw`

`__token_if_primitive_undefined:N`

We filter out macros first, because they cause endless trouble later otherwise.

Primitives are almost distinguished by the fact that the result of `\token_to_meaning:N` is formed from letters only. Every other token has either a space (e.g., the letter A), a digit (e.g., `\count123`) or a double quote (e.g., `\char"A`).

Ten exceptions: on the one hand, `\tex_undefined:D` is not a primitive, but its meaning is undefined, only letters; on the other hand, `\space`, `\italiccorr`, `\hyphen`, `\firstmark`, `\topmark`, `\botmark`, `\splitfirstmark`, `\splitbotmark`, and `\nullfont` are primitives, but have non-letters in their meaning.

We start by removing the two first (non-space) characters from the meaning. This removes the escape character (which may be nonexistent depending on `\endlinechar`), and takes care of three of the exceptions: `\space`, `\italiccorr` and `\hyphen`, whose meaning is at most two characters. This leaves a string terminated by some `:`, and `\s__token_stop`.

The meaning of each one of the five `\...mark` primitives has the form $\langle letters \rangle : \langle user material \rangle$. In other words, the first non-letter is a colon. We remove everything after the first colon.

We are now left with a string, which we must analyze. For primitives, it contains only letters. For non-primitives, it contains either `"`, or a space, or a digit. Two exceptions remain: `\tex_undefined:D`, which is not a primitive, and `\nullfont`, which is a primitive.

Spaces cannot be grabbed in an undelimited way, so we check them separately. If there is a space, we test for `\nullfont`. Otherwise, we go through characters one by one, and stop at the first character less than ‘A’ (this is not quite a test for “only letters”, but is close enough to work in this context). If this first character is `:` then we have a primitive, or `\tex_undefined:D`, and if it is `"` or a digit, then the token is not a primitive.

```

11486 \tex_chardef:D \c__token_A_int = 'A ~ %
11487 \use:x
11488 {
11489   \prg_new_conditional:Npnn \exp_not:N \token_if_primitive:N ##1
11490   { p , T , F , TF }
11491   {
11492     \exp_not:N \token_if_macro:NTF ##1
11493     \exp_not:N \prg_return_false:
11494     {
11495       \exp_not:N \exp_after:wN \exp_not:N \__token_if_primitive:NNw
11496       \exp_not:N \token_to_meaning:N ##1
11497       \tl_to_str:n { : : : } \s__token_stop ##1
11498     }
11499   }
11500   \cs_new:Npn \exp_not:N \__token_if_primitive:NNw
11501   ##1##2 ##3 \c_colon_str ##4 \s__token_stop
11502   {
11503     \exp_not:N \tl_if_empty:oTF
11504     { \exp_not:N \__token_if_primitive_space:w ##3 ~ }
11505     {
11506       \exp_not:N \__token_if_primitive_loop:N ##3
11507       \c_colon_str \s__token_stop
11508     }
11509     { \exp_not:N \__token_if_primitive_nullfont:N }
11510   }

```

```

11511 }
11512 \cs_new:Npn \__token_if_primitive_space:w #1 ~ { }
11513 \cs_new:Npn \__token_if_primitive_nullfont:N #1
11514 {
11515   \if_meaning:w \tex_nullfont:D #1
11516   \prg_return_true:
11517   \else:
11518   \prg_return_false:
11519   \fi:
11520 }
11521 \cs_new:Npn \__token_if_primitive_loop:N #1
11522 {
11523   \if_int_compare:w '#1 < \c__token_A_int %
11524   \exp_after:wN \__token_if_primitive:Nw
11525   \exp_after:wN #1
11526   \else:
11527   \exp_after:wN \__token_if_primitive_loop:N
11528   \fi:
11529 }
11530 \cs_new:Npn \__token_if_primitive:Nw #1 #2 \s__token_stop
11531 {
11532   \if:w : #1
11533   \exp_after:wN \__token_if_primitive_undefined:N
11534   \else:
11535   \prg_return_false:
11536   \exp_after:wN \use_none:n
11537   \fi:
11538 }
11539 \cs_new:Npn \__token_if_primitive_undefined:N #1
11540 {
11541   \if_cs_exist:N #1
11542   \prg_return_true:
11543   \else:
11544   \prg_return_false:
11545   \fi:
11546 }

```

(End definition for `\token_if_primitive:NTF` and others. This function is documented on page [137](#).)

17.6 Peeking ahead at the next token

```
11547 <@@=peek>
```

Peeking ahead is implemented using a two part mechanism. The outer level provides a defined interface to the lower level material. This allows a large amount of code to be shared. There are four cases:

1. peek at the next token;
2. peek at the next non-space token;
3. peek at the next token and remove it;
4. peek at the next non-space token and remove it.

\l_peek_token Storage tokens which are publicly documented: the token peeked.

\g_peek_token

```

11548 \cs_new_eq:NN \l_peek_token ?
11549 \cs_new_eq:NN \g_peek_token ?

```

(End definition for \l_peek_token and \g_peek_token. These variables are documented on page 137.)

\l__peek_search_token The token to search for as an implicit token: cf. \l__peek_search_tl.

```

11550 \cs_new_eq:NN \l__peek_search_token ?

```

(End definition for \l__peek_search_token.)

\l__peek_search_tl The token to search for as an explicit token: cf. \l__peek_search_token.

```

11551 \tl_new:N \l__peek_search_tl

```

(End definition for \l__peek_search_tl.)

__peek_true:w Functions used by the branching and space-stripping code.

```

\__peek_true_aux:w 11552 \cs_new:Npn \__peek_true:w { }
\__peek_false:w    11553 \cs_new:Npn \__peek_true_aux:w { }
\__peek_tmp:w      11554 \cs_new:Npn \__peek_false:w { }
                  11555 \cs_new:Npn \__peek_tmp:w { }

```

(End definition for __peek_true:w and others.)

\s__peek_mark Internal scan marks.

\s__peek_stop

```

11556 \scan_new:N \s__peek_mark
11557 \scan_new:N \s__peek_stop

```

(End definition for \s__peek_mark and \s__peek_stop.)

__peek_use_none_delimit_by_s_stop:w Functions to gobble up to a scan mark.

```

11558 \cs_new:Npn \__peek_use_none_delimit_by_s_stop:w #1 \s__peek_stop { }

```

(End definition for __peek_use_none_delimit_by_s_stop:w.)

\peek_after:Nw Simple wrappers for \futurelet: no arguments absorbed here.

\peek_gafter:Nw

```

11559 \cs_new_protected:Npn \peek_after:Nw
11560 { \tex_futurelet:D \l_peek_token }
11561 \cs_new_protected:Npn \peek_gafter:Nw
11562 { \tex_global:D \tex_futurelet:D \g_peek_token }

```

(End definition for \peek_after:Nw and \peek_gafter:Nw. These functions are documented on page 137.)

__peek_true_remove:w A function to remove the next token and then regain control.

```

11563 \cs_new_protected:Npn \__peek_true_remove:w
11564 {
11565   \tex_afterassignment:D \__peek_true_aux:w
11566   \cs_set_eq:NN \__peek_tmp:w
11567 }

```

(End definition for __peek_true_remove:w.)

`\peek_remove_spaces:n` Repeatedly use `__peek_true_remove:w` to remove a space and call `__peek_true_remove_spaces:w`.

```

11568 \cs_new_protected:Npn \peek_remove_spaces:n #1
11569 {
11570   \cs_set:Npx \__peek_false:w { \exp_not:n {#1} }
11571   \group_align_safe_begin:
11572   \cs_set:Npn \__peek_true_aux:w { \peek_after:Nw \__peek_remove_spaces: }
11573   \__peek_true_aux:w
11574 }
11575 \cs_new_protected:Npn \__peek_remove_spaces:
11576 {
11577   \if_meaning:w \l_peek_token \c_space_token
11578     \exp_after:wN \__peek_true_remove:w
11579   \else:
11580     \group_align_safe_end:
11581     \exp_after:wN \__peek_false:w
11582   \fi:
11583 }

```

(End definition for `\peek_remove_spaces:n` and `__peek_remove_spaces:..` This function is documented on page 270.)

`__peek_token_generic_aux:NNNTF` The generic functions store the test token in both implicit and explicit modes, and the `true` and `false` code as token lists, more or less. The two branches have to be absorbed here as the input stream needs to be cleared for the peek function itself. Here, `#1` is `__peek_true_remove:w` when removing the token and `__peek_true_aux:w` otherwise.

```

11584 \cs_new_protected:Npn \__peek_token_generic_aux:NNNTF #1#2#3#4#5
11585 {
11586   \group_align_safe_begin:
11587   \cs_set_eq:NN \l__peek_search_token #3
11588   \tl_set:Nn \l__peek_search_tl {#3}
11589   \cs_set:Npx \__peek_true_aux:w
11590   {
11591     \exp_not:N \group_align_safe_end:
11592     \exp_not:n {#4}
11593   }
11594   \cs_set_eq:NN \__peek_true:w #1
11595   \cs_set:Npx \__peek_false:w
11596   {
11597     \exp_not:N \group_align_safe_end:
11598     \exp_not:n {#5}
11599   }
11600   \peek_after:Nw #2
11601 }

```

(End definition for `__peek_token_generic_aux:NNNTF`.)

`__peek_token_generic:NNTF` For token removal there needs to be a call to the auxiliary function which does the work.

```

\__peek_token_remove_generic:NNTF
11602 \cs_new_protected:Npn \__peek_token_generic:NNTF
11603 { \__peek_token_generic_aux:NNNTF \__peek_true_aux:w }
11604 \cs_new_protected:Npn \__peek_token_generic:NNT #1#2#3
11605 { \__peek_token_generic:NNTF #1 #2 {#3} { } }
11606 \cs_new_protected:Npn \__peek_token_generic:NNTF #1#2#3
11607 { \__peek_token_generic:NNTF #1 #2 { } {#3} }

```

```

11608 \cs_new_protected:Npn \__peek_token_remove_generic:NNTF
11609 { \__peek_token_generic_aux:NNNTF \__peek_true_remove:w }
11610 \cs_new_protected:Npn \__peek_token_remove_generic:NNT #1#2#3
11611 { \__peek_token_remove_generic:NNTF #1 #2 {#3} { } }
11612 \cs_new_protected:Npn \__peek_token_remove_generic:NNTF #1#2#3
11613 { \__peek_token_remove_generic:NNTF #1 #2 { } {#3} }

```

(End definition for __peek_token_generic:NNTF and __peek_token_remove_generic:NNTF.)

__peek_execute_branches_meaning: The meaning test is straight forward.

```

11614 \cs_new:Npn \__peek_execute_branches_meaning:
11615 {
11616   \if_meaning:w \l_peek_token \l__peek_search_token
11617   \exp_after:wN \__peek_true:w
11618   \else:
11619     \exp_after:wN \__peek_false:w
11620   \fi:
11621 }

```

(End definition for __peek_execute_branches_meaning:.)

__peek_execute_branches_catcode: The catcode and charcode tests are very similar, and in order to use the same auxiliaries we do something a little bit odd, firing \if_catcode:w and \if_charcode:w before finding the operands for those tests, which are only given in the auxii:N and auxiii: auxiliaries. For our purposes, three kinds of tokens may follow the peeking function:

- control sequences which are not equal to a non-active character token (*e.g.*, macro, primitive);
- active characters which are not equal to a non-active character token (*e.g.*, macro, primitive);
- explicit non-active character tokens, or control sequences or active characters set equal to a non-active character token.

The first two cases are not distinguishable simply using T_EX's \futurelet, because we can only access the \meaning of tokens in that way. In those cases, detected thanks to a comparison with \scan_stop:, we grab the following token, and compare it explicitly with the explicit search token stored in \l__peek_search_tl. The \exp_not:N prevents outer macros (coming from non- \LaTeX 3 code) from blowing up. In the third case, \l_peek_token is good enough for the test, and we compare it again with the explicit search token. Just like the peek token, the search token may be of any of the three types above, hence the need to use the explicit token that was given to the peek function.

```

11622 \cs_new:Npn \__peek_execute_branches_catcode:
11623 { \if_catcode:w \__peek_execute_branches_catcode_aux: }
11624 \cs_new:Npn \__peek_execute_branches_charcode:
11625 { \if_charcode:w \__peek_execute_branches_catcode_aux: }
11626 \cs_new:Npn \__peek_execute_branches_catcode_aux:
11627 {
11628   \if_catcode:w \exp_not:N \l_peek_token \scan_stop:
11629   \exp_after:wN \exp_after:wN
11630   \exp_after:wN \__peek_execute_branches_catcode_auxii:N
11631   \exp_after:wN \exp_not:N
11632   \else:

```

```

11633         \exp_after:wN \__peek_execute_branches_catcode_auxiii:
11634     \fi:
11635 }
11636 \cs_new:Npn \__peek_execute_branches_catcode_auxii:N #1
11637 {
11638     \exp_not:N #1
11639     \exp_after:wN \exp_not:N \l__peek_search_tl
11640     \exp_after:wN \__peek_true:w
11641 \else:
11642     \exp_after:wN \__peek_false:w
11643 \fi:
11644 #1
11645 }
11646 \cs_new:Npn \__peek_execute_branches_catcode_auxiii:
11647 {
11648     \exp_not:N \l_peek_token
11649     \exp_after:wN \exp_not:N \l__peek_search_tl
11650     \exp_after:wN \__peek_true:w
11651 \else:
11652     \exp_after:wN \__peek_false:w
11653 \fi:
11654 }

```

(End definition for __peek_execute_branches_catcode: and others.)

\peek_catcode:N~~TF~~ The public functions themselves cannot be defined using \prg_new_conditional:Npnn. Instead, the TF, T, F variants are defined in terms of corresponding variants of __peek_token_generic:NNTF or __peek_token_remove_generic:NNTF, with first argument one of __peek_execute_branches_catcode:, __peek_execute_branches_charcode:, or __peek_execute_branches_meaning:.

\peek_catcode_remove:N~~TF~~
\peek_charcode:N~~TF~~
\peek_charcode_remove:N~~TF~~
\peek_meaning:N~~TF~~
\peek_meaning_remove:N~~TF~~

```

11655 \tl_map_inline:nn { { catcode } { charcode } { meaning } }
11656 {
11657     \tl_map_inline:nn { { } { _remove } }
11658     {
11659         \tl_map_inline:nn { { TF } { T } { F } }
11660         {
11661             \cs_new_protected:cpx { peek_ #1 ##1 :N ####1 }
11662             {
11663                 \exp_not:c { __peek_token ##1 _generic:NN ####1 }
11664                 \exp_not:c { __peek_execute_branches_ #1 : }
11665             }
11666         }
11667     }
11668 }

```

(End definition for \peek_catcode:N~~TF~~ and others. These functions are documented on page 137.)

\peek_catcode_ignore_spaces:N~~TF~~ To ignore spaces, remove them using \peek_remove_spaces:n before running the tests.
\peek_catcode_remove_ignore_spaces:N~~TF~~
\peek_charcode_ignore_spaces:N~~TF~~
\peek_charcode_remove_ignore_spaces:N~~TF~~
\peek_meaning_ignore_spaces:N~~TF~~
\peek_meaning_remove_ignore_spaces:N~~TF~~

```

11669 \tl_map_inline:nn
11670 {
11671     { catcode } { catcode_remove }
11672     { charcode } { charcode_remove }
11673     { meaning } { meaning_remove }
11674 }

```



```

11675 {
11676   \cs_new_protected:cpx { peek_#1_ignore_spaces:NTF } ##1##2##3
11677   {
11678     \peek_remove_spaces:n
11679     { \exp_not:c { peek_#1:NTF } ##1 {##2} {##3} }
11680   }
11681   \cs_new_protected:cpx { peek_#1_ignore_spaces:NT } ##1##2
11682   {
11683     \peek_remove_spaces:n
11684     { \exp_not:c { peek_#1:NT } ##1 {##2} }
11685   }
11686   \cs_new_protected:cpx { peek_#1_ignore_spaces:NF } ##1##2
11687   {
11688     \peek_remove_spaces:n
11689     { \exp_not:c { peek_#1:NF } ##1 {##2} }
11690   }
11691 }

```

(End definition for `\peek_catcode_ignore_spaces:NTF` and others. These functions are documented on page 138.)

\peek_N_type:TF
`__peek_execute_branches_N_type:`
`__peek_N_type:w`
`__peek_N_type_aux:nnw`

All tokens are N-type tokens, except in four cases: begin-group tokens, end-group tokens, space tokens with character code 32, and outer tokens. Since `\l_peek_token` might be outer, we cannot use the convenient `\bool_if:nTF` function, and must resort to the old trick of using `\ifodd` to expand a set of tests. The false branch of this test is taken if the token is one of the first three kinds of non-N-type tokens (explicit or implicit), thus we call `__peek_false:w`. In the true branch, we must detect outer tokens, without impacting performance too much for non-outer tokens. The first filter is to search for `outer` in the `\meaning` of `\l_peek_token`. If that is absent, `__peek_use_none_delimit_by_s_stop:w` cleans up, and we call `__peek_true:w`. Otherwise, the token can be a non-outer macro or a primitive mark whose parameter or replacement text contains `outer`, it can be the primitive `\outer`, or it can be an outer token. Macros and marks would have `ma` in the part before the first occurrence of `outer`; the meaning of `\outer` has nothing after `outer`, contrarily to outer macros; and that covers all cases, calling `__peek_true:w` or `__peek_false:w` as appropriate. Here, there is no *search token*, so we feed a dummy `\scan_stop:` to the `__peek_token_generic:NNTF` function.

```

11692 \group_begin:
11693   \cs_set_protected:Npn \__peek_tmp:w #1 \s__peek_stop
11694   {
11695     \cs_new_protected:Npn \__peek_execute_branches_N_type:
11696     {
11697       \if_int_odd:w
11698         \if_catcode:w \exp_not:N \l_peek_token { 0 \exp_stop_f: \fi:
11699         \if_catcode:w \exp_not:N \l_peek_token } 0 \exp_stop_f: \fi:
11700         \if_meaning:w \l_peek_token \c_space_token 0 \exp_stop_f: \fi:
11701         1 \exp_stop_f:
11702         \exp_after:wN \__peek_N_type:w
11703         \token_to_meaning:N \l_peek_token
11704         \s__peek_mark \__peek_N_type_aux:nnw
11705         #1 \s__peek_mark \__peek_use_none_delimit_by_s_stop:w
11706         \s__peek_stop
11707         \exp_after:wN \__peek_true:w
11708       \else:

```

```

11709         \exp_after:wN \__peek_false:w
11710     \fi:
11711 }
11712 \cs_new_protected:Npn \__peek_N_type:w ##1 #1 ##2 \s__peek_mark ##3
11713 { ##3 {##1} {##2} }
11714 }
11715 \exp_after:wN \__peek_tmp:w \tl_to_str:n { outer } \s__peek_stop
11716 \group_end:
11717 \cs_new_protected:Npn \__peek_N_type_aux:nw #1 #2 #3 \fi:
11718 {
11719     \fi:
11720     \tl_if_in:noTF {#1} { \tl_to_str:n {ma} }
11721     { \__peek_true:w }
11722     { \tl_if_empty:nTF {#2} { \__peek_true:w } { \__peek_false:w } }
11723 }
11724 \cs_new_protected:Npn \peek_N_type:TF
11725 {
11726     \__peek_token_generic:NNTF
11727     \__peek_execute_branches_N_type: \scan_stop:
11728 }
11729 \cs_new_protected:Npn \peek_N_type:T
11730 { \__peek_token_generic:NNT \__peek_execute_branches_N_type: \scan_stop: }
11731 \cs_new_protected:Npn \peek_N_type:F
11732 { \__peek_token_generic:NNTF \__peek_execute_branches_N_type: \scan_stop: }

```

(End definition for `\peek_N_type:TF` and others. This function is documented on page 140.)

```

11733 </initex | package>

```

18 l3prop implementation

The following test files are used for this code: `m3prop001`, `m3prop002`, `m3prop003`, `m3prop004`, `m3show001`.

```

11734 <*:initex | package>
11735 <@@=prop>

```

A property list is a macro whose top-level expansion is of the form

```

\s__prop \__prop_pair:wn <key1> \s__prop {<value1>}
...
\__prop_pair:wn <keyn> \s__prop {<valuen>}

```

where `\s__prop` is a scan mark (equal to `\scan_stop:`), and `__prop_pair:wn` can be used to map through the property list.

`\s__prop` The internal token used at the beginning of property lists. This is also used after each `<key>` (see `__prop_pair:wn`).

(End definition for `\s__prop`.)

`__prop_pair:wn` `__prop_pair:wn <key> \s__prop {<item>}`

The internal token used to begin each key–value pair in the property list. If expanded outside of a mapping or manipulation function, an error is raised. The definition should always be set globally.

(End definition for `_prop_pair:wn`.)

`\l_prop_internal_tl` Token list used to store new key–value pairs to be inserted by functions of the `\prop_put:Nnn` family.

(End definition for `\l_prop_internal_tl`.)

`__prop_split:NnTF`

Updated: 2013-01-08

`__prop_split:NnTF` $\langle\textit{property list}\rangle$ $\{\langle\textit{key}\rangle\}$ $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Splits the $\langle\textit{property list}\rangle$ at the $\langle\textit{key}\rangle$, giving three token lists: the $\langle\textit{extract}\rangle$ of $\langle\textit{property list}\rangle$ before the $\langle\textit{key}\rangle$, the $\langle\textit{value}\rangle$ associated with the $\langle\textit{key}\rangle$ and the $\langle\textit{extract}\rangle$ of the $\langle\textit{property list}\rangle$ after the $\langle\textit{value}\rangle$. Both $\langle\textit{extracts}\rangle$ retain the internal structure of a property list, and the concatenation of the two $\langle\textit{extracts}\rangle$ is a property list. If the $\langle\textit{key}\rangle$ is present in the $\langle\textit{property list}\rangle$ then the $\langle\textit{true code}\rangle$ is left in the input stream, with #1, #2, and #3 replaced by the first $\langle\textit{extract}\rangle$, the $\langle\textit{value}\rangle$, and the second $\langle\textit{extract}\rangle$. If the $\langle\textit{key}\rangle$ is not present in the $\langle\textit{property list}\rangle$ then the $\langle\textit{false code}\rangle$ is left in the input stream, with no trailing material. Both $\langle\textit{true code}\rangle$ and $\langle\textit{false code}\rangle$ are used in the replacement text of a macro defined internally, hence macro parameter characters should be doubled, except #1, #2, and #3 which stand in the $\langle\textit{true code}\rangle$ for the three extracts from the property list. The $\langle\textit{key}\rangle$ comparison takes place as described for `\str_if_eq:nn`.

`\s_prop` A private scan mark is used as a marker after each key, and at the very beginning of the property list.

11736 `\scan_new:N \s_prop`

(End definition for `\s_prop`.)

`_prop_pair:wn` The delimiter is always defined, but when misused simply triggers an error and removes its argument.

11737 `\cs_new:Npn _prop_pair:wn #1 \s_prop #2`

11738 `{ _kernel_msg_expandable_error:nn { kernel } { misused-prop } }`

(End definition for `_prop_pair:wn`.)

`\l_prop_internal_tl` Token list used to store the new key–value pair inserted by `\prop_put:Nnn` and friends.

11739 `\tl_new:N \l_prop_internal_tl`

(End definition for `\l_prop_internal_tl`.)

`\c_empty_prop` An empty prop.

11740 `\tl_const:Nn \c_empty_prop { \s_prop }`

(End definition for `\c_empty_prop`. This variable is documented on page 149.)

18.1 Internal auxiliaries

`\s__prop_mark` Internal scan marks.

`\s__prop_stop` 11741 `\scan_new:N \s__prop_mark`
11742 `\scan_new:N \s__prop_stop`

(End definition for `\s__prop_mark` and `\s__prop_stop`.)

`\q__prop_recursion_tail` Internal recursion quarks.

`\q__prop_recursion_stop` 11743 `\quark_new:N \q__prop_recursion_tail`
11744 `\quark_new:N \q__prop_recursion_stop`

(End definition for `\q__prop_recursion_tail` and `\q__prop_recursion_stop`.)

`_prop_if_recursion_tail_stop:n` Functions to query recursion quarks.

`_prop_if_recursion_tail_stop:o` 11745 `_kernel_quark_new_test:N _prop_if_recursion_tail_stop:n`
11746 `\cs_generate_variant:Nn _prop_if_recursion_tail_stop:n { o }`

(End definition for `_prop_if_recursion_tail_stop:n` and `_prop_if_recursion_tail_stop:o`.)

18.2 Allocation and initialisation

`\prop_new:N` Property lists are initialized with the value `\c_empty_prop`.

`\prop_new:c` 11747 `\cs_new_protected:Npn \prop_new:N #1`
11748 `{`
11749 `_kernel_chk_if_free_cs:N #1`
11750 `\cs_gset_eq:NN #1 \c_empty_prop`
11751 `}`
11752 `\cs_generate_variant:Nn \prop_new:N { c }`

(End definition for `\prop_new:N`. This function is documented on page 143.)

`\prop_clear:N` The same idea for clearing.

`\prop_clear:c` 11753 `\cs_new_protected:Npn \prop_clear:N #1`
`\prop_gclear:N` 11754 `{ \prop_set_eq:NN #1 \c_empty_prop }`
`\prop_gclear:c` 11755 `\cs_generate_variant:Nn \prop_clear:N { c }`
11756 `\cs_new_protected:Npn \prop_gclear:N #1`
11757 `{ \prop_gset_eq:NN #1 \c_empty_prop }`
11758 `\cs_generate_variant:Nn \prop_gclear:N { c }`

(End definition for `\prop_clear:N` and `\prop_gclear:N`. These functions are documented on page 143.)

`\prop_clear_new:N` Once again a simple variation of the token list functions.

`\prop_clear_new:c` 11759 `\cs_new_protected:Npn \prop_clear_new:N #1`
`\prop_gclear_new:N` 11760 `{ \prop_if_exist:NTF #1 { \prop_clear:N #1 } { \prop_new:N #1 } }`
`\prop_gclear_new:c` 11761 `\cs_generate_variant:Nn \prop_clear_new:N { c }`
11762 `\cs_new_protected:Npn \prop_gclear_new:N #1`
11763 `{ \prop_if_exist:NTF #1 { \prop_gclear:N #1 } { \prop_new:N #1 } }`
11764 `\cs_generate_variant:Nn \prop_gclear_new:N { c }`

(End definition for `\prop_clear_new:N` and `\prop_gclear_new:N`. These functions are documented on page 143.)

```

\prop_set_eq:NN These are simply copies from the token list functions.
\prop_set_eq:cN 11765 \cs_new_eq:NN \prop_set_eq:NN \tl_set_eq:NN
\prop_set_eq:Nc 11766 \cs_new_eq:NN \prop_set_eq:Nc \tl_set_eq:Nc
\prop_set_eq:cc 11767 \cs_new_eq:NN \prop_set_eq:cN \tl_set_eq:cN
\prop_gset_eq:NN 11768 \cs_new_eq:NN \prop_set_eq:cc \tl_set_eq:cc
\prop_gset_eq:cN 11769 \cs_new_eq:NN \prop_gset_eq:NN \tl_gset_eq:NN
\prop_gset_eq:Nc 11770 \cs_new_eq:NN \prop_gset_eq:Nc \tl_gset_eq:Nc
\prop_gset_eq:cN 11771 \cs_new_eq:NN \prop_gset_eq:cN \tl_gset_eq:cN
\prop_gset_eq:cc 11772 \cs_new_eq:NN \prop_gset_eq:cc \tl_gset_eq:cc

```

(End definition for `\prop_set_eq:NN` and `\prop_gset_eq:NN`. These functions are documented on page 143.)

```

\l_tmpa_prop We can now initialize the scratch variables.
\l_tmpb_prop
\g_tmpa_prop 11773 \prop_new:N \l_tmpa_prop
\g_tmpb_prop 11774 \prop_new:N \l_tmpb_prop
\g_tmpa_prop 11775 \prop_new:N \g_tmpa_prop
\g_tmpb_prop 11776 \prop_new:N \g_tmpb_prop

```

(End definition for `\l_tmpa_prop` and others. These variables are documented on page 148.)

```

\l__prop_internal_prop Property list used by \prop_set_from_keyval:Nn and others.
11777 \prop_new:N \l__prop_internal_prop

```

(End definition for `\l__prop_internal_prop`.)

```

\prop_set_from_keyval:Nn To avoid tracking throughout the loop the variable name and whether the assignment
\prop_set_from_keyval:cN is local/global, do everything in a scratch variable and empty it afterwards to avoid
\prop_gset_from_keyval:Nn wasting memory. Loop through items separated by commas, with \prg_do_nothing:
\prop_gset_from_keyval:cN to avoid losing braces. After checking for termination, split the item at the first and
\prop_const_from_keyval:Nn then at the second = (which ought to be the first of the trailing = that we added). For
\prop_const_from_keyval:cN both splits trim spaces and call a function (first \__prop_from_keyval_key:w then \__-
\__prop_from_keyval:n prop_from_keyval_value:w), followed by the trimmed material, \s__prop_mark, the
\__prop_from_keyval_loop:w subsequent part of the item, and the trailing ='s and \s__prop_stop. After finding
\__prop_from_keyval_split:Nw the <key> just store it after \s__prop_stop. After finding the <value> ignore completely
\__prop_from_keyval_key:n empty items (both trailing = were used as delimiters and all parts are empty); if the
\__prop_from_keyval_key:w remaining part #2 consists exactly of the second trailing = (namely there was exactly one
\__prop_from_keyval_value:n = in the item) then output one key–value pair for the property list; otherwise complain
\__prop_from_keyval_value:w about a missing or extra =.

```

```

11778 \cs_new_protected:Npn \prop_set_from_keyval:Nn #1#2
11779 {
11780   \prop_clear:N \l__prop_internal_prop
11781   \__prop_from_keyval:n {#2}
11782   \prop_set_eq:NN #1 \l__prop_internal_prop
11783   \prop_clear:N \l__prop_internal_prop
11784 }
11785 \cs_generate_variant:Nn \prop_set_from_keyval:Nn { c }
11786 \cs_new_protected:Npn \prop_gset_from_keyval:Nn #1#2
11787 {
11788   \prop_clear:N \l__prop_internal_prop
11789   \__prop_from_keyval:n {#2}
11790   \prop_gset_eq:NN #1 \l__prop_internal_prop
11791   \prop_clear:N \l__prop_internal_prop

```

```

11792 }
11793 \cs_generate_variant:Nn \prop_gset_from_keyval:Nn { c }
11794 \cs_new_protected:Npn \prop_const_from_keyval:Nn #1#2
11795 {
11796   \prop_clear:N \l__prop_internal_prop
11797   \__prop_from_keyval:n {#2}
11798   \tl_const:Nx #1 { \exp_not:o \l__prop_internal_prop }
11799   \prop_clear:N \l__prop_internal_prop
11800 }
11801 \cs_generate_variant:Nn \prop_const_from_keyval:Nn { c }
11802 \cs_new_protected:Npn \__prop_from_keyval:n #1
11803 {
11804   \__prop_from_keyval_loop:w \prg_do_nothing: #1 ,
11805   \q__prop_recursion_tail , \q__prop_recursion_stop
11806 }
11807 \cs_new_protected:Npn \__prop_from_keyval_loop:w #1 ,
11808 {
11809   \__prop_if_recursion_tail_stop:o {#1}
11810   \__prop_from_keyval_split:Nw \__prop_from_keyval_key:n
11811   #1 = = \s__prop_stop {#1}
11812   \__prop_from_keyval_loop:w \prg_do_nothing:
11813 }
11814 \cs_new_protected:Npn \__prop_from_keyval_split:Nw #1#2 =
11815 { \tl_trim_spaces_apply:oN {#2} #1 }
11816 \cs_new_protected:Npn \__prop_from_keyval_key:n #1
11817 { \__prop_from_keyval_key:w #1 \s__prop_mark }
11818 \cs_new_protected:Npn \__prop_from_keyval_key:w #1 \s__prop_mark #2 \s__prop_stop
11819 {
11820   \__prop_from_keyval_split:Nw \__prop_from_keyval_value:n
11821   \prg_do_nothing: #2 \s__prop_stop {#1}
11822 }
11823 \cs_new_protected:Npn \__prop_from_keyval_value:n #1
11824 { \__prop_from_keyval_value:w #1 \s__prop_mark }
11825 \cs_new_protected:Npn \__prop_from_keyval_value:w #1 \s__prop_mark #2 \s__prop_stop #3#4
11826 {
11827   \tl_if_empty:nF { #3 #1 #2 }
11828   {
11829     \str_if_eq:nnTF {#2} { = }
11830     { \prop_put:Nnn \l__prop_internal_prop {#3} {#1} }
11831     {
11832       \__kernel_msg_error:nnx { kernel } { prop-keyval }
11833       { \exp_not:o {#4} }
11834     }
11835   }
11836 }

```

(End definition for `\prop_set_from_keyval:Nn` and others. These functions are documented on page 143.)

18.3 Accessing data in property lists

`__prop_split:NnTF` This function is used by most of the module, and hence must be fast. It receives a *property list*, a *key*, a *true code* and a *false code*. The aim is to split the *property list* at the given *key* into the *extract₁* before the key–value pair, the *value* associated

with the $\langle key \rangle$ and the $\langle extract_2 \rangle$ after the key-value pair. This is done using a delimited function, whose definition is as follows, where the $\langle key \rangle$ is turned into a string.

```
\cs_set:Npn \__prop_split_aux:w #1
\__prop_pair:wn \langle key \rangle \s__prop #2
#3 \s__prop_mark #4 #5 \s__prop_stop
{ #4 {\langle true code \rangle} {\langle false code \rangle} }
```

If the $\langle key \rangle$ is present in the property list, $\backslash__prop_split_aux:w$'s #1 is the part before the $\langle key \rangle$, #2 is the $\langle value \rangle$, #3 is the part after the $\langle key \rangle$, #4 is $\backslash use_i:nn$, and #5 is additional tokens that we do not care about. The $\langle true code \rangle$ is left in the input stream, and can use the parameters #1, #2, #3 for the three parts of the property list as desired. Namely, the original property list is in this case #1 $\backslash__prop_pair:wn \langle key \rangle \backslash s_prop \{ \#2 \}$ #3.

If the $\langle key \rangle$ is not there, then the $\langle function \rangle$ is $\backslash use_ii:nn$, which keeps the $\langle false code \rangle$.

```
11837 \cs_new_protected:Npn \__prop_split:NnTF #1#2
11838 { \exp_args:NNo \__prop_split_aux:NnTF #1 { \tl_to_str:n {#2} } }
11839 \cs_new_protected:Npn \__prop_split_aux:NnTF #1#2#3#4
11840 {
11841   \cs_set:Npn \__prop_split_aux:w ##1
11842     \__prop_pair:wn #2 \s__prop ##2 ##3 \s__prop_mark ##4 ##5 \s__prop_stop
11843     { ##4 {#3} {#4} }
11844   \exp_after:wN \__prop_split_aux:w #1 \s__prop_mark \use_i:nn
11845   \__prop_pair:wn #2 \s__prop { } \s__prop_mark \use_ii:nn \s__prop_stop
11846 }
11847 \cs_new:Npn \__prop_split_aux:w { }
```

(End definition for $\backslash__prop_split:NnTF$, $\backslash__prop_split_aux:NnTF$, and $\backslash__prop_split_aux:w$.)

$\backslash prop_remove:Nn$ $\backslash prop_remove:NV$ $\backslash prop_remove:cn$ $\backslash prop_remove:cV$ $\backslash prop_gremove:Nn$ $\backslash prop_gremove:NV$ $\backslash prop_gremove:cn$ $\backslash prop_gremove:cV$	Deleting from a property starts by splitting the list. If the key is present in the property list, the returned value is ignored. If the key is missing, nothing happens. <pre>11848 \cs_new_protected:Npn \prop_remove:Nn #1#2 11849 { 11850 __prop_split:NnTF #1 {#2} 11851 { \tl_set:Nn #1 { ##1 ##3 } } 11852 { } 11853 } 11854 \cs_new_protected:Npn \prop_gremove:Nn #1#2 11855 { 11856 __prop_split:NnTF #1 {#2} 11857 { \tl_gset:Nn #1 { ##1 ##3 } } 11858 { } 11859 } 11860 \cs_generate_variant:Nn \prop_remove:Nn { NV } 11861 \cs_generate_variant:Nn \prop_remove:Nn { c , cV } 11862 \cs_generate_variant:Nn \prop_gremove:Nn { NV } 11863 \cs_generate_variant:Nn \prop_gremove:Nn { c , cV }</pre>
--	---

(End definition for $\backslash prop_remove:Nn$ and $\backslash prop_gremove:Nn$. These functions are documented on page 145.)

\prop_get:NnN Getting an item from a list is very easy: after splitting, if the key is in the property list, just set the token list variable to the return value, otherwise to `\q_no_value`.

```

\prop_get:NVN
\prop_get:NoN 11864 \cs_new_protected:Npn \prop_get:NnN #1#2#3
\prop_get:cnN 11865 {
\prop_get:cVN 11866   \__prop_split:NnTF #1 {#2}
\prop_get:coN 11867   { \tl_set:Nn #3 {##2} }
                { \tl_set:Nn #3 { \q_no_value } }
11869   }
11870 \cs_generate_variant:Nn \prop_get:NnN { NV , No }
11871 \cs_generate_variant:Nn \prop_get:NnN { c , cV , co }

```

(End definition for `\prop_get:NnN`. This function is documented on page 144.)

\prop_pop:NnN Popping a value also starts by doing the split. If the key is present, save the value in the token list and update the property list as when deleting. If the key is missing, save `\q_no_value` in the token list.

```

\prop_pop:NoN 11872 \cs_new_protected:Npn \prop_pop:NnN #1#2#3
\prop_pop:cnN 11873 {
\prop_pop:coN 11874   \__prop_split:NnTF #1 {#2}
\prop_gpop:NnN 11875   {
\prop_gpop:cnN 11876     \tl_set:Nn #3 {##2}
\prop_gpop:coN 11877     \tl_set:Nn #1 { ##1 ##3 }
11878   }
11879   { \tl_set:Nn #3 { \q_no_value } }
11880 }
11881 \cs_new_protected:Npn \prop_gpop:NnN #1#2#3
11882 {
11883   \__prop_split:NnTF #1 {#2}
11884   {
11885     \tl_set:Nn #3 {##2}
11886     \tl_gset:Nn #1 { ##1 ##3 }
11887   }
11888   { \tl_set:Nn #3 { \q_no_value } }
11889 }
11890 \cs_generate_variant:Nn \prop_pop:NnN { No }
11891 \cs_generate_variant:Nn \prop_pop:NnN { c , co }
11892 \cs_generate_variant:Nn \prop_gpop:NnN { No }
11893 \cs_generate_variant:Nn \prop_gpop:NnN { c , co }

```

(End definition for `\prop_pop:NnN` and `\prop_gpop:NnN`. These functions are documented on page 144.)

\prop_item:Nn Getting the value corresponding to a key in a property list in an expandable fashion is similar to mapping some tokens. Go through the property list one $\langle key \rangle$ – $\langle value \rangle$ pair at a time: the arguments of `__prop_item_Nn:nwn` are the $\langle key \rangle$ we are looking for, a $\langle key \rangle$ of the property list, and its associated value. The $\langle keys \rangle$ are compared (as strings). If they match, the $\langle value \rangle$ is returned, within `\exp_not:n`. The loop terminates even if the $\langle key \rangle$ is missing, and yields an empty value, because we have appended the appropriate $\langle key \rangle$ – $\langle empty\ value \rangle$ pair to the property list.

```

11894 \cs_new:Npn \prop_item:Nn #1#2
11895 {
11896   \exp_last_unbraced:Noo \__prop_item_Nn:nwn { \tl_to_str:n {#2} } #1
11897   \__prop_pair:wn \tl_to_str:n {#2} \s__prop { }
11898   \prg_break_point:

```



```

11899 }
11900 \cs_new:Npn \__prop_item:Nn:nwwn #1#2 \__prop_pair:wn #3 \s__prop #4
11901 {
11902   \str_if_eq:eeTF {#1} {#3}
11903   { \prg_break:n { \exp_not:n {#4} } }
11904   { \__prop_item:Nn:nwwn {#1} }
11905 }
11906 \cs_generate_variant:Nn \prop_item:Nn { c }

```

(End definition for `\prop_item:Nn` and `__prop_item:Nn:nwwn`. This function is documented on page 145.)

`\prop_count:N` Counting the key–value pairs in a property list is done using the same approach as for
`\prop_count:c` other count functions: turn each entry into a +1 then use integer evaluation to actually
`__prop_count:nn` do the mathematics.

```

11907 \cs_new:Npn \prop_count:N #1
11908 {
11909   \int_eval:n
11910   {
11911     0
11912     \prop_map_function:NN #1 \__prop_count:nn
11913   }
11914 }
11915 \cs_new:Npn \__prop_count:nn #1#2 { + 1 }
11916 \cs_generate_variant:Nn \prop_count:N { c }

```

(End definition for `\prop_count:N` and `__prop_count:nn`. This function is documented on page 145.)

`\prop_pop:NnTF` Popping an item from a property list, keeping track of whether the key was present or
`\prop_pop:cnTF` not, is implemented as a conditional. If the key was missing, neither the property list, nor
`\prop_gpop:NnTF` the token list are altered. Otherwise, `\prg_return_true:` is used after the assignments.
`\prop_gpop:cnTF`

```

11917 \prg_new_protected_conditional:Npnn \prop_pop:NnN #1#2#3 { T , F , TF }
11918 {
11919   \__prop_split:NnTF #1 {#2}
11920   {
11921     \tl_set:Nn #3 {##2}
11922     \tl_set:Nn #1 { ##1 ##3 }
11923     \prg_return_true:
11924   }
11925   { \prg_return_false: }
11926 }
11927 \prg_new_protected_conditional:Npnn \prop_gpop:NnN #1#2#3 { T , F , TF }
11928 {
11929   \__prop_split:NnTF #1 {#2}
11930   {
11931     \tl_set:Nn #3 {##2}
11932     \tl_gset:Nn #1 { ##1 ##3 }
11933     \prg_return_true:
11934   }
11935   { \prg_return_false: }
11936 }
11937 \prg_generate_conditional_variant:Nnn \prop_pop:NnN { c } { T , F , TF }
11938 \prg_generate_conditional_variant:Nnn \prop_gpop:NnN { c } { T , F , TF }

```

(End definition for `\prop_pop:NnTF` and `\prop_gpop:NnTF`. These functions are documented on page 146.)

`\prop_put:Nnn` Since the branches of `__prop_split:NnTF` are used as the replacement text of an internal macro, and since the $\langle key \rangle$ and new $\langle value \rangle$ may contain arbitrary tokens, it is not safe to include them in the argument of `__prop_split:NnTF`. We thus start by storing in `\l__prop_internal_tl` tokens which (after x-expansion) encode the key–value pair. This variable can safely be used in `__prop_split:NnTF`. If the $\langle key \rangle$ was absent, append the new key–value to the list. Otherwise concatenate the extracts `##1` and `##3` with the new key–value pair `\l__prop_internal_tl`. The updated entry is placed at the same spot as the original $\langle key \rangle$ in the property list, preserving the order of entries.

```

11939 \cs_new_protected:Npn \prop_put:Nnn { \__prop_put:NNnn \tl_set:Nx }
11940 \cs_new_protected:Npn \prop_gput:Nnn { \__prop_put:NNnn \tl_gset:Nx }
11941 \cs_new_protected:Npn \__prop_put:NNnn #1#2#3#4
11942 {
11943   \tl_set:Nn \l__prop_internal_tl
11944   {
11945     \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
11946     \s__prop { \exp_not:n {#4} }
11947   }

```

```

11948 \__prop_split:NnTF #2 {#3}
11949 { #1 #2 { \exp_not:n {##1} \l__prop_internal_tl \exp_not:n {##3} } }
11950 { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } }
11951 }
11952 \cs_generate_variant:Nn \prop_put:Nnn
11953 { NnV , Nno , Nnx , NV , NVV , No , Noo }
11954 \cs_generate_variant:Nn \prop_gput:Nnn
11955 { c , cnV , cno , cnx , cV , cVV , co , coo }
11956 \cs_generate_variant:Nn \prop_gput:Nnn
11957 { NnV , Nno , Nnx , NV , NVV , No , Noo }
11958 \cs_generate_variant:Nn \prop_gput:Nnn
11959 { c , cnV , cno , cnx , cV , cVV , co , coo }

```

(End definition for `\prop_put:Nnn`, `\prop_gput:Nnn`, and `__prop_put:NNnn`. These functions are documented on page 144.)

```

\prop_gput:con
\prop_put_if_new:Nnn
\prop_gput:coo
\prop_put_if_new:cnn
\__prop_put:NNnn
\prop_gput_if_new:Nnn
\prop_gput_if_new:cnn
\__prop_put_if_new:NNnn

```

Adding conditionally also splits. If the key is already present, the three brace groups given by `__prop_split:NnTF` are removed. If the key is new, then the value is added, being careful to convert the key to a string using `\tl_to_str:n`.

```

11960 \cs_new_protected:Npn \prop_put_if_new:Nnn
11961 { \__prop_put_if_new:NNnn \tl_set:Nx }
11962 \cs_new_protected:Npn \prop_gput_if_new:Nnn
11963 { \__prop_put_if_new:NNnn \tl_gset:Nx }
11964 \cs_new_protected:Npn \__prop_put_if_new:NNnn #1#2#3#4
11965 {
11966   \tl_set:Nn \l__prop_internal_tl
11967   {
11968     \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
11969     \s__prop \exp_not:n {#4} }
11970   }
11971   \__prop_split:NnTF #2 {#3}
11972   { }
11973   { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } }
11974 }

```

```

11975 \cs_generate_variant:Nn \prop_put_if_new:Nnn { c }
11976 \cs_generate_variant:Nn \prop_gput_if_new:Nnn { c }

```

(End definition for `\prop_put_if_new:Nnn`, `\prop_gput_if_new:Nnn`, and `__prop_put_if_new:NNnn`. These functions are documented on page 144.)

18.4 Property list conditionals

`\prop_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.
`\prop_if_exist_p:c` 11977 \prg_new_eq_conditional:NNn \prop_if_exist:N \cs_if_exist:N
`\prop_if_exist:N \underline{TF}` 11978 { TF , T , F , p }
`\prop_if_exist:c \underline{TF}` 11979 \prg_new_eq_conditional:NNn \prop_if_exist:c \cs_if_exist:c
11980 { TF , T , F , p }

(End definition for `\prop_if_exist:N \underline{TF}` . This function is documented on page 145.)

`\prop_if_empty_p:N` Same test as for token lists.
`\prop_if_empty_p:c` 11981 \prg_new_conditional:Npnn \prop_if_empty:N #1 { p , T , F , TF }
`\prop_if_empty:N \underline{TF}` 11982 {
`\prop_if_empty:c \underline{TF}` 11983 \tl_if_eq:NNTF #1 \c_empty_prop
11984 \prg_return_true: \prg_return_false:
11985 }
11986 \prg_generate_conditional_variant:Nnn \prop_if_empty:N
11987 { c } { p , T , F , TF }

(End definition for `\prop_if_empty:N \underline{TF}` . This function is documented on page 145.)

`\prop_if_in_p:Nn` Testing expandably if a key is in a property list requires to go through the key–value
`\prop_if_in_p:Nv` pairs one by one. This is rather slow, and a faster test would be
`\prop_if_in_p:No` \prg_new_protected_conditional:Npnn \prop_if_in:Nn #1 #2
`\prop_if_in_p:cn` {
`\prop_if_in_p:cV` \@@_split:NnTF #1 {#2}
`\prop_if_in_p:co` { \prg_return_true: }
`\prop_if_in:Nn \underline{TF}` { \prg_return_false: }
`\prop_if_in:Nv \underline{TF}` }
`\prop_if_in:No \underline{TF}` }
`\prop_if_in:cn \underline{TF}` but `__prop_split:NnTF` is non-expandable.
`\prop_if_in:cV \underline{TF}` Instead, the key is compared to each key in turn using `\str_if_eq:ee`, which is
`\prop_if_in:co \underline{TF}` expandable. To terminate the mapping, we append to the property list the key that is
`__prop_if_in:nwnn` searched for. This second `\tl_to_str:n` is not expanded at the start, but only when
`__prop_if_in:N` included in the `\str_if_eq:ee`. It cannot make the breaking mechanism choke, because
the arbitrary token list material is enclosed in braces. The second argument of `__prop_if_in:N`
receives `__prop_pair:wn`, and if it is found as the extra item, the function receives
`\q_prop_recursion_tail`, easily recognizable.

Here, `\prop_map_function:NN` is not sufficient for the mapping, since it can only map a single token, and cannot carry the key that is searched for.

```

11988 \prg_new_conditional:Npnn \prop_if_in:Nn #1#2 { p , T , F , TF }
11989 {
11990   \exp_last_unbraced:Noo \__prop_if_in:nwnn { \tl_to_str:n {#2} } #1
11991   \__prop_pair:wn \tl_to_str:n {#2} \s_prop { }
11992   \q_prop_recursion_tail
11993   \prg_break_point:

```

```

11994 }
11995 \cs_new:Npn \__prop_if_in:nwn #1#2 \__prop_pair:wn #3 \s__prop #4
11996 {
11997   \str_if_eq:eeTF {#1} {#3}
11998   { \__prop_if_in:N }
11999   { \__prop_if_in:nwn {#1} }
12000 }
12001 \cs_new:Npn \__prop_if_in:N #1
12002 {
12003   \if_meaning:w \q__prop_recursion_tail #1
12004   \prg_return_false:
12005   \else:
12006     \prg_return_true:
12007   \fi:
12008   \prg_break:
12009 }
12010 \prg_generate_conditional_variant:Nnn \prop_if_in:Nn
12011 { NV , No , c , cV , co } { p , T , F , TF }

```

(End definition for `\prop_if_in:NnTF`, `__prop_if_in:nwn`, and `__prop_if_in:N`. This function is documented on page 146.)

18.5 Recovering values from property lists with branching

`\prop_get:NnTF` Getting the value corresponding to a key, keeping track of whether the key was present or not, is implemented as a conditional (with side effects). If the key was absent, the token list is not altered.

```

12012 \prg_new_protected_conditional:Npnn \prop_get:NnN #1#2#3 { T , F , TF }
12013 {
12014   \__prop_split:NnTF #1 {#2}
12015   {
12016     \tl_set:Nn #3 {##2}
12017     \prg_return_true:
12018   }
12019   { \prg_return_false: }
12020 }
12021 \prg_generate_conditional_variant:Nnn \prop_get:NnN
12022 { NV , No , c , cV , co } { T , F , TF }

```

(End definition for `\prop_get:NnTF`. This function is documented on page 146.)

18.6 Mapping to property lists

The argument delimited by `__prop_pair:wn` is empty except at the end of the loop where it is `\prg_break:.` No need for any quark test.

```

\prop_map_function:NN The argument delimited by \__prop_pair:wn is empty except at the end of the loop
\prop_map_function:Nc where it is \prg_break:. No need for any quark test.
\prop_map_function:cN
\prop_map_function:cc
\__prop_map_function:Nwn
12023 \cs_new:Npn \prop_map_function:NN #1#2
12024 {
12025   \exp_after:wN \use_i_ii:nnn
12026   \exp_after:wN \__prop_map_function:Nwn
12027   \exp_after:wN #2
12028   #1
12029   \prg_break: \__prop_pair:wn \s__prop { } \prg_break_point:
12030   \prg_break_point:Nn \prop_map_break: { }
12031 }

```

```

12032 \cs_new:Npn \__prop_map_function:Nwwn #1#2 \__prop_pair:wn #3 \s__prop #4
12033 {
12034     #2
12035     #1 {#3} {#4}
12036     \__prop_map_function:Nwwn #1
12037 }
12038 \cs_generate_variant:Nn \prop_map_function:NN { Nc , c , cc }

```

(End definition for `\prop_map_function:NN` and `__prop_map_function:Nwwn`. This function is documented on page 147.)

`\prop_map_inline:Nn` Mapping in line requires a nesting level counter. Store the current definition of `__prop_pair:wn`, and define it anew. At the end of the loop, revert to the earlier definition. Note that besides pairs of the form `__prop_pair:wn <key> \s__prop {<value>}`, there are a leading and a trailing tokens, but both are equal to `\scan_stop:`, hence have no effect in such inline mapping. Such `\scan_stop:` could have affected ligatures if they appeared during the mapping.

`\prop_map_inline:cn`

```

12039 \cs_new_protected:Npn \prop_map_inline:Nn #1#2
12040 {
12041     \cs_gset_eq:cn
12042     { __prop_map_ \int_use:N \g__kernel_prg_map_int :wn } \__prop_pair:wn
12043     \int_gincr:N \g__kernel_prg_map_int
12044     \cs_gset_protected:Npn \__prop_pair:wn ##1 \s__prop ##2 {#2}
12045     #1
12046     \prg_break_point:Nn \prop_map_break:
12047     {
12048         \int_gdecr:N \g__kernel_prg_map_int
12049         \cs_gset_eq:Nc \__prop_pair:wn
12050         { __prop_map_ \int_use:N \g__kernel_prg_map_int :wn }
12051     }
12052 }
12053 \cs_generate_variant:Nn \prop_map_inline:Nn { c }

```

(End definition for `\prop_map_inline:Nn`. This function is documented on page 147.)

`\prop_map_tokens:Nn` The mapping is very similar to `\prop_map_function:NN`. The `\use_i:nn` removes the leading `\s__prop`. The odd construction `\use:n {#1}` allows #1 to contain any token without interfering with `\prop_map_break:`. The loop stops when the argument delimited by `__prop_pair:wn` is `\prg_break:` instead of being empty.

`\prop_map_tokens:cn`

`__prop_map_tokens:nwwn`

```

12054 \cs_new:Npn \prop_map_tokens:Nn #1#2
12055 {
12056     \exp_last_unbraced:Nno
12057     \use_i:nn { \__prop_map_tokens:nwwn {#2} } #1
12058     \prg_break: \__prop_pair:wn \s__prop { } \prg_break_point:
12059     \prg_break_point:Nn \prop_map_break: { }
12060 }
12061 \cs_new:Npn \__prop_map_tokens:nwwn #1#2 \__prop_pair:wn #3 \s__prop #4
12062 {
12063     #2
12064     \use:n {#1} {#3} {#4}
12065     \__prop_map_tokens:nwwn {#1}
12066 }
12067 \cs_generate_variant:Nn \prop_map_tokens:Nn { c }

```

(End definition for `\prop_map_tokens:Nn` and `_prop_map_tokens:nwn`. This function is documented on page 147.)

`\prop_map_break:` The break statements are based on the general `\prg_map_break:Nn`.
`\prop_map_break:n`

```
12068 \cs_new:Npn \prop_map_break:
12069   { \prg_map_break:Nn \prop_map_break: { } }
12070 \cs_new:Npn \prop_map_break:n
12071   { \prg_map_break:Nn \prop_map_break: }
```

(End definition for `\prop_map_break:` and `\prop_map_break:n`. These functions are documented on page 147.)

18.7 Viewing property lists

`\prop_show:N` Apply the general `_kernel_chk_defined:NT` and `\msg_show:nnnnnn`. Contrarily to sequences and comma lists, we use `\msg_show_item:nn` to format both the key and the value for each pair.
`\prop_show:c`
`\prop_log:N`
`\prop_log:c`

```
12072 \cs_new_protected:Npn \prop_show:N { \_prop_show:NN \msg_show:nnxxxx }
12073 \cs_generate_variant:Nn \prop_show:N { c }
12074 \cs_new_protected:Npn \prop_log:N { \_prop_show:NN \msg_log:nnxxxx }
12075 \cs_generate_variant:Nn \prop_log:N { c }
12076 \cs_new_protected:Npn \_prop_show:NN #1#2
12077   {
12078     \_kernel_chk_defined:NT #2
12079     {
12080       #1 { LaTeX/kernel } { show-prop }
12081       { \token_to_str:N #2 }
12082       { \prop_map_function:NN #2 \msg_show_item:nn }
12083       { } { }
12084     }
12085   }
```

(End definition for `\prop_show:N` and `\prop_log:N`. These functions are documented on page 148.)

```
12086 </initex | package>
```

19 l3msg implementation

```
12087 <*initex | package>
```

```
12088 <@@=msg>
```

`\l__msg_internal_tl` A general scratch for the module.

```
12089 \tl_new:N \l__msg_internal_tl
```

(End definition for `\l__msg_internal_tl`.)

`\l__msg_name_str` Used to save module info when creating messages.

```
\l__msg_text_str
12090 \str_new:N \l__msg_name_str
12091 \str_new:N \l__msg_text_str
```

(End definition for `\l__msg_name_str` and `\l__msg_text_str`.)

19.1 Internal auxiliaries

`\s__msg_mark` Internal scan marks.

`\s__msg_stop` 12092 `\scan_new:N \s__msg_mark`
12093 `\scan_new:N \s__msg_stop`

(End definition for `\s__msg_mark` and `\s__msg_stop`.)

`_msg_use_none_delimit_by_s_stop:w` Functions to gobble up to a scan mark.

12094 `\cs_new:Npn _msg_use_none_delimit_by_s_stop:w #1 \s__msg_stop { }`

(End definition for `_msg_use_none_delimit_by_s_stop:w`.)

19.2 Creating messages

Messages are created and used separately, so there two parts to the code here. First, a mechanism for creating message text. This is pretty simple, as there is not actually a lot to do.

`\c__msg_text_prefix_tl` Locations for the text of messages.

`\c__msg_more_text_prefix_tl` 12095 `\tl_const:Nn \c__msg_text_prefix_tl { msg~text~>~ }`
12096 `\tl_const:Nn \c__msg_more_text_prefix_tl { msg~extra~text~>~ }`

(End definition for `\c__msg_text_prefix_tl` and `\c__msg_more_text_prefix_tl`.)

`\msg_if_exist_p:nn` Test whether the control sequence containing the message text exists or not.

`\msg_if_exist:nnTF` 12097 `\prg_new_conditional:Npnn \msg_if_exist:nn #1#2 { p , T , F , TF }`
12098 `{`
12099 `\cs_if_exist:cTF { \c__msg_text_prefix_tl #1 / #2 }`
12100 `{ \prg_return_true: } { \prg_return_false: }`
12101 `}`

(End definition for `\msg_if_exist:nnTF`. This function is documented on page 151.)

`_msg_chk_if_free:nn` This auxiliary is similar to `_kernel_chk_if_free_cs:N`, and is used when defining messages with `\msg_new:nnnn`.

12102 `\cs_new_protected:Npn _msg_chk_free:nn #1#2`
12103 `{`
12104 `\msg_if_exist:nnT {#1} {#2}`
12105 `{`
12106 `_kernel_msg_error:nxxx { kernel } { message-already-defined }`
12107 `{#1} {#2}`
12108 `}`
12109 `}`

(End definition for `_msg_chk_if_free:nn`.)

`\msg_new:nnnn` Setting a message simply means saving the appropriate text into two functions. A sanity check first.

`\msg_new:nnn`
`\msg_gset:nnnn` 12110 `\cs_new_protected:Npn \msg_new:nnnn #1#2`
`\msg_gset:nnn` 12111 `{`
`\msg_set:nnnn` 12112 `_msg_chk_free:nn {#1} {#2}`
`\msg_set:nnn` 12113 `\msg_gset:nnnn {#1} {#2}`
12114 `}`
12115 `\cs_new_protected:Npn \msg_new:nnn #1#2#3`

```

12116 { \msg_new:nnnn {#1} {#2} {#3} { } }
12117 \cs_new_protected:Npn \msg_set:nnnn #1#2#3#4
12118 {
12119   \cs_set:cpn { \c__msg_text_prefix_tl #1 / #2 }
12120   ##1##2##3##4 {#3}
12121   \cs_set:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
12122   ##1##2##3##4 {#4}
12123 }
12124 \cs_new_protected:Npn \msg_set:nnn #1#2#3
12125 { \msg_set:nnnn {#1} {#2} {#3} { } }
12126 \cs_new_protected:Npn \msg_gset:nnnn #1#2#3#4
12127 {
12128   \cs_gset:cpn { \c__msg_text_prefix_tl #1 / #2 }
12129   ##1##2##3##4 {#3}
12130   \cs_gset:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
12131   ##1##2##3##4 {#4}
12132 }
12133 \cs_new_protected:Npn \msg_gset:nnn #1#2#3
12134 { \msg_gset:nnnn {#1} {#2} {#3} { } }

```

(End definition for `\msg_new:nnnn` and others. These functions are documented on page 150.)

19.3 Messages: support functions and text

```

\c__msg_coding_error_text_tl Simple pieces of text for messages.
\c__msg_continue_text_tl
\c__msg_critical_text_tl
\c__msg_fatal_text_tl
\c__msg_help_text_tl
\c__msg_no_info_text_tl
\c__msg_on_line_text_tl
\c__msg_return_text_tl
\c__msg_trouble_text_tl
12135 \tl_const:Nn \c__msg_coding_error_text_tl
12136 {
12137   This~is~a~coding~error.
12138   \\ \\
12139 }
12140 \tl_const:Nn \c__msg_continue_text_tl
12141 { Type~<return>~to~continue }
12142 \tl_const:Nn \c__msg_critical_text_tl
12143 { Reading~the~current~file~'\g_file_curr_name_str'~will~stop. }
12144 \tl_const:Nn \c__msg_fatal_text_tl
12145 { This~is~a~fatal~error:~LaTeX~will~abort. }
12146 \tl_const:Nn \c__msg_help_text_tl
12147 { For~immediate~help~type~H~<return> }
12148 \tl_const:Nn \c__msg_no_info_text_tl
12149 {
12150   LaTeX~does~not~know~anything~more~about~this~error,~sorry.
12151   \c__msg_return_text_tl
12152 }
12153 \tl_const:Nn \c__msg_on_line_text_tl { on~line }
12154 \tl_const:Nn \c__msg_return_text_tl
12155 {
12156   \\ \\
12157   Try~typing~<return>~to~proceed.
12158   \\
12159   If~that~doesn't~work,~type~X~<return>~to~quit.
12160 }
12161 \tl_const:Nn \c__msg_trouble_text_tl
12162 {
12163   \\ \\

```



```

12164     More~errors~will~almost~certainly~follow: \\
12165     the~LaTeX~run~should~be~aborted.
12166 }

```

(End definition for `\c__msg_coding_error_text_tl` and others.)

`\msg_line_number:` For writing the line number nicely. `\msg_line_context:` was set up earlier, so this is not new.

```

12167 \cs_new:Npn \msg_line_number: { \int_use:N \tex_inputlineno:D }
12168 \cs_gset:Npn \msg_line_context:
12169 {
12170     \c__msg_on_line_text_tl
12171     \c_space_tl
12172     \msg_line_number:
12173 }

```

(End definition for `\msg_line_number:` and `\msg_line_context:`. These functions are documented on page 151.)

19.4 Showing messages: low level mechanism

```

\__msg_interrupt:Nnnn
\__msg_no_more_text:nnnn

```

The low-level interruption macro is rather opaque, unfortunately. Depending on the availability of more information there is a choice of how to set up the further help. We feed the extra help text and the message itself to a wrapping auxiliary, in this order because we must first setup TeX's `\errhelp` register before issuing an `\errmessage`. To deal with the various cases of critical or fatal errors with and without help text, there is a bit of argument-passing to do.

```

12174 \cs_new_protected:Npn \__msg_interrupt:NnnnN #1#2#3#4#5
12175 {
12176     \str_set:Nx \l__msg_text_str { #1 {#2} }
12177     \str_set:Nx \l__msg_name_str { \msg_module_name:n {#2} }
12178     \cs_if_eq:cNTF
12179     { \c__msg_more_text_prefix_tl #2 / #3 }
12180     \__msg_no_more_text:nnnn
12181     {
12182         \__msg_interrupt_wrap:nnn
12183         { \use:c { \c__msg_text_prefix_tl #2 / #3 } #4 }
12184         { \c__msg_continue_text_tl }
12185         {
12186             \c__msg_no_info_text_tl
12187             \tl_if_empty:NF #5
12188             { \\ \\ #5 }
12189         }
12190     }
12191     {
12192         \__msg_interrupt_wrap:nnn
12193         { \use:c { \c__msg_text_prefix_tl #2 / #3 } #4 }
12194         { \c__msg_help_text_tl }
12195         {
12196             \use:c { \c__msg_more_text_prefix_tl #2 / #3 } #4
12197             \tl_if_empty:NF #5
12198             { \\ \\ #5 }
12199         }
12200     }
}

```

```

12201 }
12202 \cs_new:Npn \__msg_no_more_text:nnnn #1#2#3#4 { }

(End definition for \__msg_interrupt:Nnnn and \__msg_no_more_text:nnnn.)

```

```

\__msg_interrupt_wrap:nnn
\__msg_interrupt_text:n
\__msg_interrupt_more_text:n

```

First setup TeX's `\errhelp` register with the extra help #1, then build a nice-looking error message with #2. Everything is done using x-type expansion as the new line markers are different for the two type of text and need to be correctly set up. The auxiliary `__msg_interrupt_more_text:n` receives its argument as a line-wrapped string, which is thus unaffected by expansion. We have to split the main text into two parts as only the “message” itself is wrapped with a leader: the generic help is wrapped at full width. We also have to allow for the two characters used by `\errmessage` itself.

```

12203 \cs_new_protected:Npn \__msg_interrupt_wrap:nnn #1#2#3
12204 {
12205   \iow_wrap:nnnN { \ \ #3 } { } { } \__msg_interrupt_more_text:n
12206   \group_begin:
12207     \int_sub:Nn \l_iow_line_count_int { 2 }
12208     \iow_wrap:nxnN { \l__msg_text_str : ~ #1 }
12209     {
12210       ( \l__msg_name_str )
12211       \prg_replicate:nn
12212       {
12213         \str_count:N \l__msg_text_str
12214         - \str_count:N \l__msg_name_str
12215         + 2
12216       }
12217       { ~ }
12218     }
12219     { } \__msg_interrupt_text:n
12220     \iow_wrap:nnnN { \l__msg_internal_tl \ \ \ #2 } { } { }
12221     \__msg_interrupt:n
12222   }
12223 \cs_new_protected:Npn \__msg_interrupt_text:n #1
12224 {
12225   \group_end:
12226   \tl_set:Nn \l__msg_internal_tl {#1}
12227 }
12228 \cs_new_protected:Npn \__msg_interrupt_more_text:n #1
12229 { \exp_args:Nx \tex_errhelp:D { #1 \iow_newline: } }

```

(End definition for `__msg_interrupt_wrap:nnn`, `__msg_interrupt_text:n`, and `__msg_interrupt_more_text:n`.)

```
\__msg_interrupt:n
```

The business end of the process starts by producing some visual separation of the message from the main part of the log. The error message needs to be printed with everything made “invisible”: TeX's own information involves the macro in which `\errmessage` is called, and the end of the argument of the `\errmessage`, including the closing brace. We use an active `!` to call the `\errmessage` primitive, and end its argument with `\use_none:n {<spaces>}` which fills the output with spaces. Two trailing closing braces are turned into spaces to hide them as well. The group in which we alter the definition of the active `!` is closed before producing the message: this ensures that tokens inserted by typing `I` in the command-line are inserted after the message is entirely cleaned up.

The `__kernel_iow_with:Nnn` auxiliary, defined in `l3file`, expects an *integer variable*, an integer *value*, and some *code*. It runs the *code* after ensuring that the

$\langle integer\ variable \rangle$ takes the given $\langle value \rangle$, then restores the former value of the $\langle integer\ variable \rangle$ if needed. We use it to ensure that the `\newlinechar` is 10, as needed for `\iow_newline:` to work, and that `\errorcontextlines` is -1 , to avoid showing irrelevant context. Note that restoring the former value of these integers requires inserting tokens after the `\errmessage`, which go in the way of tokens which could be inserted by the user. This is unavoidable.

```

12230 \group_begin:
12231   \char_set_lccode:nn { 38 } { 32 } % &
12232   \char_set_lccode:nn { 46 } { 32 } % .
12233   \char_set_lccode:nn { 123 } { 32 } % {
12234   \char_set_lccode:nn { 125 } { 32 } % }
12235   \char_set_catcode_active:N \&
12236 \tex_lowercase:D
12237 {
12238   \group_end:
12239   \cs_new_protected:Npn \__msg_interrupt:n #1
12240   {
12241     \iow_term:n { }
12242     \__kernel_iow_with:Nnn \tex_newlinechar:D { ^^J }
12243     {
12244       \__kernel_iow_with:Nnn \tex_errorcontextlines:D { -1 }
12245       {
12246         \group_begin:
12247         \cs_set_protected:Npn &
12248         {
12249           \tex_errmessage:D
12250           {
12251             #1
12252             \use_none:n
12253             { ..... }
12254           }
12255         }
12256         \exp_after:wN
12257         \group_end:
12258         &
12259       }
12260     }
12261   }
12262 }

```

(End definition for `__msg_interrupt:n`.)

19.5 Displaying messages

L^AT_EX is handling error messages and so the T_EX ones are disabled. This is already done by the L^AT_EX 2_ε kernel, so to avoid messing up any deliberate change by a user this is only set in format mode.

```

12263 \*initex>
12264 \int_gset:Nn \tex_errorcontextlines:D { -1 }
12265 \</initex>

```

```

\msg_fatal_text:n
\msg_critical_text:n
\msg_error_text:n
\msg_warning_text:n
\msg_info_text:n
\__msg_text:nn
\__msg_text:n

```

A function for issuing messages: both the text and order could in principle vary. The module name may be empty for kernel messages, hence the slightly contorted code path

for a space.

```

12266 \cs_new:Npn \msg_fatal_text:n #1
12267 {
12268     Fatal ~
12269     \msg_error_text:n {#1}
12270 }
12271 \cs_new:Npn \msg_critical_text:n #1
12272 {
12273     Critical ~
12274     \msg_error_text:n {#1}
12275 }
12276 \cs_new:Npn \msg_error_text:n #1
12277 { \__msg_text:nn {#1} { Error } }
12278 \cs_new:Npn \msg_warning_text:n #1
12279 { \__msg_text:nn {#1} { Warning } }
12280 \cs_new:Npn \msg_info_text:n #1
12281 { \__msg_text:nn {#1} { Info } }
12282 \cs_new:Npn \__msg_text:nn #1#2
12283 {
12284     \exp_args:Nf \__msg_text:n { \msg_module_type:n {#1} }
12285     \msg_module_name:n {#1} ~
12286     #2
12287 }
12288 \cs_new:Npn \__msg_text:n #1
12289 {
12290     \tl_if_blank:nF {#1}
12291     { #1 ~ }
12292 }

```

(End definition for `\msg_fatal_text:n` and others. These functions are documented on page 151.)

`\g_msg_module_name_prop`
`\g_msg_module_type_prop`

For storing public module information: the kernel data is set up in advance.

```

12293 \prop_new:N \g_msg_module_name_prop
12294 \prop_gput:Nnn \g_msg_module_name_prop { LaTeX } { LaTeX3 }
12295 \prop_new:N \g_msg_module_type_prop
12296 \prop_gput:Nnn \g_msg_module_type_prop { LaTeX } { }

```

(End definition for `\g_msg_module_name_prop` and `\g_msg_module_type_prop`. These variables are documented on page 152.)

`\msg_module_type:n`

Contextual footer information, with the potential to give modules an alternative name.

```

12297 \cs_new:Npn \msg_module_type:n #1
12298 {
12299     \prop_if_in:NnTF \g_msg_module_type_prop {#1}
12300     { \prop_item:Nn \g_msg_module_type_prop {#1} }
12301     <*initex>
12302     { Module }
12303     </initex>
12304     <*package>
12305     { Package }
12306     </package>
12307 }

```

(End definition for `\msg_module_type:n`. This function is documented on page 152.)

`\msg_module_name:n` Contextual footer information, with the potential to give modules an alternative name.
`\msg_see_documentation_text:n`

```

12308 \cs_new:Npn \msg_module_name:n #1
12309 {
12310     \prop_if_in:NnTF \g_msg_module_name_prop {#1}
12311     { \prop_item:Nn \g_msg_module_name_prop {#1} }
12312     {#1}
12313 }
12314 \cs_new:Npn \msg_see_documentation_text:n #1
12315 {
12316     See~the~ \msg_module_name:n {#1} ~
12317     documentation~for~further~information.
12318 }

```

(End definition for `\msg_module_name:n` and `\msg_see_documentation_text:n`. These functions are documented on page 152.)

`__msg_class_new:nn`

```

12319 \group_begin:
12320 \cs_set_protected:Npn \__msg_class_new:nn #1#2
12321 {
12322     \prop_new:c { l__msg_redirect_ #1 _prop }
12323     \cs_new_protected:cpn { __msg_ #1 _code:nnnnnn }
12324     ##1##2##3##4##5##6 {#2}
12325     \cs_new_protected:cpn { msg_ #1 :nnnnnn } ##1##2##3##4##5##6
12326     {
12327         \use:x
12328         {
12329             \exp_not:n { \__msg_use:nnnnnn {#1} {##1} {##2} }
12330             { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
12331             { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
12332         }
12333     }
12334     \cs_new_protected:cpx { msg_ #1 :nnnnn } ##1##2##3##4##5
12335     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
12336     \cs_new_protected:cpx { msg_ #1 :nnnn } ##1##2##3##4
12337     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
12338     \cs_new_protected:cpx { msg_ #1 :nnn } ##1##2##3
12339     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
12340     \cs_new_protected:cpx { msg_ #1 :nn } ##1##2
12341     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} { } { } { } { } }
12342     \cs_new_protected:cpx { msg_ #1 :nnxxxx } ##1##2##3##4##5##6
12343     {
12344         \use:x
12345         {
12346             \exp_not:N \exp_not:n
12347             { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} }
12348             {##3} {##4} {##5} {##6}
12349         }
12350     }
12351     \cs_new_protected:cpx { msg_ #1 :nnxxx } ##1##2##3##4##5
12352     { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} {##5} { } }
12353     \cs_new_protected:cpx { msg_ #1 :nnxx } ##1##2##3##4
12354     { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} { } { } }
12355     \cs_new_protected:cpx { msg_ #1 :nnx } ##1##2##3

```

```

12356         { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} { } { } { } }
12357     }

```

(End definition for `_msg_class_new:nn`.)

`\msg_fatal:nnnnnn` For fatal errors, after the error message T_EX bails out. We force a bail out rather than using `\end` as this means it does not matter if we are in a context where normally the run cannot end.

```

\msg_fatal:nnxxx 12358 \_msg\_class\_new:nn { fatal }
\msg_fatal:nnnn 12359 {
\msg_fatal:nnxx 12360 \_msg\_interrupt:NnnnN
\msg_fatal:nnn 12361 \msg_fatal_text:n {#1} {#2}
\msg_fatal:nnx 12362 { {#3} {#4} {#5} {#6} }
\msg_fatal:nn 12363 \c\_msg_fatal_text_tl
\_msg_fatal_exit: 12364 \_msg_fatal_exit:
12365 }
12366 \cs\_new\_protected:Npn \_msg_fatal_exit:
12367 {
12368 \tex_batchmode:D
12369 \tex_read:D -1 to \l\_msg\_internal\_tl
12370 }

```

(End definition for `\msg_fatal:nnnnnn` and others. These functions are documented on page 153.)

`\msg_critical:nnnnnn` Not quite so bad: just end the current file.

```

\msg_critical:nnxxxx 12371 \_msg\_class\_new:nn { critical }
\msg_critical:nnnnn 12372 {
\msg_critical:nnxxx 12373 \_msg\_interrupt:NnnnN
\msg_critical:nnnn 12374 \msg_critical_text:n {#1} {#2}
\msg_critical:nnxx 12375 { {#3} {#4} {#5} {#6} }
\msg_critical:nnn 12376 \c\_msg\_critical\_text\_tl
\msg_critical:nnx 12377 \tex\_endinput:D
\msg_critical:nn 12378 }

```

(End definition for `\msg_critical:nnnnnn` and others. These functions are documented on page 153.)

`\msg_error:nnnnnn` For an error, the interrupt routine is called. We check if there is a “more text” by comparing that control sequence with a permanently empty text.

```

\msg_error:nnnnnn 12379 \_msg\_class\_new:nn { error }
\msg_error:nnxxx 12380 {
\msg_error:nnnn 12381 \_msg\_interrupt:NnnnN
\msg_error:nnxx 12382 \msg_error_text:n {#1} {#2}
\msg_error:nnn 12383 { {#3} {#4} {#5} {#6} }
\msg_error:nnx 12384 \c\_empty\_tl
\msg_error:nn 12385 }

```

(End definition for `\msg_error:nnnnnn` and others. These functions are documented on page 153.)

`\msg_warning:nnnnnn` Warnings are printed to the terminal.

```

\msg_warning:nnxxxx 12386 \_msg\_class\_new:nn { warning }
\msg_warning:nnnnn 12387 {
\msg_warning:nnxxx 12388 \str\_set:Nx \l\_msg\_text\_str { \msg\_warning\_text:n {#1} }
\msg_warning:nnnn 12389 \str\_set:Nx \l\_msg\_name\_str { \msg\_module\_name:n {#1} }
\msg_warning:nnxx 12390 \iow\_term:n { }
\msg_warning:nnn 12391 \iow\_wrap:nxnN
\msg_warning:nnx
\msg_warning:nn

```

```

12392     {
12393         \l__msg_text_str : ~
12394         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
12395     }
12396     {
12397         ( \l__msg_name_str )
12398         \prg_replicate:nn
12399         {
12400             \str_count:N \l__msg_text_str
12401             - \str_count:N \l__msg_name_str
12402         }
12403         { ~ }
12404     }
12405     { } \iow_term:n
12406     \iow_term:n { }
12407 }

```

(End definition for `\msg_warning:nnnnnn` and others. These functions are documented on page 153.)

```

\msg_info:nnnnnn Information only goes into the log.
\msg_info:nnxxxx 12408 \__msg_class_new:nn { info }
\msg_info:nnnnn 12409 {
\msg_info:nnxxx 12410     \str_set:Nx \l__msg_text_str { \msg_info_text:n {#1} }
\msg_info:nnnn 12411     \str_set:Nx \l__msg_name_str { \msg_module_name:n {#1} }
\msg_info:nnxx 12412     \iow_log:n { }
\msg_info:nnn 12413     \iow_wrap:nxnN
\msg_info:nnx 12414     {
12415         \l__msg_text_str : ~
12416         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
12417     }
12418     {
12419         ( \l__msg_name_str )
12420         \prg_replicate:nn
12421         {
12422             \str_count:N \l__msg_text_str
12423             - \str_count:N \l__msg_name_str
12424         }
12425         { ~ }
12426     }
12427     { } \iow_log:n
12428     \iow_log:n { }
12429 }

```

(End definition for `\msg_info:nnnnnn` and others. These functions are documented on page 154.)

```

\msg_log:nnnnnn “Log” data is very similar to information, but with no extras added.
\msg_log:nnxxxx 12430 \__msg_class_new:nn { log }
\msg_log:nnnnn 12431 {
\msg_log:nnxxx 12432     \iow_wrap:nnnN
\msg_log:nnnn 12433     { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
\msg_log:nnxx 12434     { } { } \iow_log:n
\msg_log:nnn 12435 }
\msg_log:nnx (End definition for \msg_log:nnnnnn and others. These functions are documented on page 154.)
\msg_log:nn

```

`\msg_none:nnnnnn` The `none` message type is needed so that input can be gobbled.

`\msg_none:nnxxxx` 12436 `__msg_class_new:nn { none } { }`

`\msg_none:nnnnn` (End definition for `\msg_none:nnnnnn` and others. These functions are documented on page 154.)

`\msg_none:nnxxx`

`\msg_show:nnxxx` The `show` message type is used for `\seq_show:N` and similar complicated data structures.

`\msg_show:nnnn` Wrap the given text with a trailing dot (important later) then pass it to `__msg_show:n`.

`\msg_show:nnnn` If there is `\>~` (or if the whole thing starts with `>~`) we split there, print the first part

`\msg_show:nnnn` and show the second part using `\showtokens` (the `\exp_after:wN` ensure a nice display).

`\msg_show:nnxx` Note that this primitive adds a leading `>~` and trailing dot. That is why we included a

`\msg_show:nnn` trailing dot before wrapping and removed it afterwards. If there is no `\>~` do the same

`\msg_show:nnx` but with an empty second part which adds a spurious but inevitable `>~`.

`\msg_show:nnx` 12437 `__msg_class_new:nn { show }`

`\msg_show:nn` 12438 `{`

`__msg_show:n` 12439 `\iow_wrap:nnnN`

`__msg_show:w` 12440 `{ \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }`

`__msg_show_dot:w` 12441 `{ } { } __msg_show:n`

`__msg_show:nn` 12442 `}`

12443 `\cs_new_protected:Npn __msg_show:n #1`

12444 `{`

12445 `\tl_if_in:nnTF { ^^J #1 } { ^^J > ~ }`

12446 `{`

12447 `\tl_if_in:nnTF { #1 \s__msg_mark } { . \s__msg_mark }`

12448 `{ __msg_show_dot:w } { __msg_show:w }`

12449 `^^J #1 \s__msg_stop`

12450 `}`

12451 `{ __msg_show:nn { ? #1 } { } }`

12452 `}`

12453 `\cs_new:Npn __msg_show_dot:w #1 ^^J > ~ #2 . \s__msg_stop`

12454 `{ __msg_show:nn {#1} {#2} }`

12455 `\cs_new:Npn __msg_show:w #1 ^^J > ~ #2 \s__msg_stop`

12456 `{ __msg_show:nn {#1} {#2} }`

12457 `\cs_new_protected:Npn __msg_show:nn #1#2`

12458 `{`

12459 `\tl_if_empty:nF {#1}`

12460 `{ \exp_args:No \iow_term:n { \use_none:n #1 } }`

12461 `\tl_set:Nn \l__msg_internal_tl {#2}`

12462 `__kernel_iow_with:Nnn \tex_newlinechar:D { 10 }`

12463 `{`

12464 `__kernel_iow_with:Nnn \tex_errorcontextlines:D { -1 }`

12465 `{`

12466 `\tex_showtokens:D \exp_after:wN \exp_after:wN \exp_after:wN`

12467 `{ \exp_after:wN \l__msg_internal_tl }`

12468 `}`

12469 `}`

12470 `}`

(End definition for `\msg_show:nnnnnn` and others. These functions are documented on page 263.)

End the group to eliminate `__msg_class_new:nn`.

12471 `\group_end:`

`__msg_class_chk_exist:nT` Checking that a message class exists. We build this from `\cs_if_free:cTF` rather than `\cs_if_exist:cTF` because that avoids reading the second argument earlier than necessary.


```

12472 \cs_new:Npn \__msg_class_chk_exist:nT #1
12473 {
12474   \cs_if_free:cTF { __msg_ #1 _code:nnnnnn }
12475   { \__kernel_msg_error:nnx { kernel } { message-class-unknown } {#1} }
12476 }

```

(End definition for __msg_class_chk_exist:nT.)

\l__msg_class_tl Support variables needed for the redirection system.

```

\l__msg_current_class_tl
12477 \tl_new:N \l__msg_class_tl
12478 \tl_new:N \l__msg_current_class_tl

```

(End definition for \l__msg_class_tl and \l__msg_current_class_tl.)

\l__msg_redirect_prop For redirection of individually-named messages

```

12479 \prop_new:N \l__msg_redirect_prop

```

(End definition for \l__msg_redirect_prop.)

\l__msg_hierarchy_seq During redirection, split the message name into a sequence: {/module/submodule}, {/module}, and {}.

```

12480 \seq_new:N \l__msg_hierarchy_seq

```

(End definition for \l__msg_hierarchy_seq.)

\l__msg_class_loop_seq Classes encountered when following redirections to check for loops.

```

12481 \seq_new:N \l__msg_class_loop_seq

```

(End definition for \l__msg_class_loop_seq.)

__msg_use:nnnnnn

Actually using a message is a multi-step process. First, some safety checks on the message and class requested. The code and arguments are then stored to avoid passing them around. The assignment to __msg_use_code: is similar to \tl_set:Nn. The message is eventually produced with whatever \l__msg_class_tl is when __msg_use_code: is called. Here is also a good place to suppress tracing output if the trace package is loaded since all (non-expandable) messages go through this auxiliary.

```

12482 \cs_new_protected:Npn \__msg_use:nnnnnn #1#2#3#4#5#6#7
12483 {
12484   <package> \cs_if_exist_use:N \conditionally@traceoff
12485   \msg_if_exist:nnTF {#2} {#3}
12486   {
12487     \__msg_class_chk_exist:nT {#1}
12488     {
12489       \tl_set:Nn \l__msg_current_class_tl {#1}
12490       \cs_set_protected:Npx \__msg_use_code:
12491       {
12492         \exp_not:n
12493         {
12494           \use:c { __msg_ \l__msg_class_tl _code:nnnnnn }
12495           {#2} {#3} {#4} {#5} {#6} {#7}
12496         }
12497       }
12498       \__msg_use_redirect_name:n { #2 / #3 }
12499     }
12500   }

```

```

12501         { \_kernel_msg_error:nxx { kernel } { message-unknown } {#2} {#3} }
12502 <package>      \cs_if_exist_use:N \conditionally@traceon
12503     }
12504 \cs_new_protected:Npn \_msg_use_code: { }

```

The first check is for a individual message redirection. If this applies then no further redirection is attempted. Otherwise, split the message name into $\langle module \rangle$, $\langle submodule \rangle$ and $\langle message \rangle$ (with an arbitrary number of slashes), and store $\{/module/submodule\}$, $\{/module\}$ and $\{\}$ into $_l_msg_hierarchy_seq$. We then map through this sequence, applying the most specific redirection.

```

12505 \cs_new_protected:Npn \_msg_use_redirect_name:n #1
12506 {
12507     \prop_get:NnNTF \_l\_msg_redirect_prop { / #1 } \_l\_msg_class_tl
12508     { \_msg_use_code: }
12509     {
12510         \seq_clear:N \_l\_msg_hierarchy_seq
12511         \_msg_use_hierarchy:nwwN { }
12512         #1 \s\_msg_mark \_msg_use_hierarchy:nwwN
12513         / \s\_msg_mark \_msg_use_none_delimit_by_s_stop:w
12514         \s\_msg_stop
12515         \_msg_use_redirect_module:n { }
12516     }
12517 }
12518 \cs_new_protected:Npn \_msg_use_hierarchy:nwwN #1#2 / #3 \s\_msg_mark #4
12519 {
12520     \seq_put_left:Nn \_l\_msg_hierarchy_seq {#1}
12521     #4 { #1 / #2 } #3 \s\_msg_mark #4
12522 }

```

At this point, the items of $_l_msg_hierarchy_seq$ are the various levels at which we should look for a redirection. Redirections which are less specific than the argument of $_msg_use_redirect_module:n$ are not attempted. This argument is empty for a class redirection, $/module$ for a module redirection, *etc.* Loop through the sequence to find the most specific redirection, with module **##1**. The loop is interrupted after testing for a redirection for **##1** equal to the argument **#1** (least specific redirection allowed). When a redirection is found, break the mapping, then if the redirection targets the same class, output the code with that class, and otherwise set the target as the new current class, and search for further redirections. Those redirections should be at least as specific as **##1**.

```

12523 \cs_new_protected:Npn \_msg_use_redirect_module:n #1
12524 {
12525     \seq_map_inline:Nn \_l\_msg_hierarchy_seq
12526     {
12527         \prop_get:cnNTF { \_l\_msg_redirect_ \_l\_msg_current_class_tl _prop }
12528         {##1} \_l\_msg_class_tl
12529         {
12530             \seq_map_break:n
12531             {
12532                 \tl_if_eq:NNTF \_l\_msg_current_class_tl \_l\_msg_class_tl
12533                 { \_msg_use_code: }
12534                 {
12535                     \tl_set_eq:NN \_l\_msg_current_class_tl \_l\_msg_class_tl
12536                     \_msg_use_redirect_module:n {##1}
12537                 }
12538             }
12539         }
12540     }
12541 }

```

```

12538         }
12539     }
12540     {
12541         \str_if_eq:nnT {##1} {#1}
12542     {
12543         \tl_set_eq:NN \l__msg_class_tl \l__msg_current_class_tl
12544         \seq_map_break:n { \__msg_use_code: }
12545     }
12546     }
12547 }
12548 }

```

(End definition for `__msg_use:nnnnnnn` and others.)

`\msg_redirect_name:nnn` Named message always use the given class even if that class is redirected further. An empty target class cancels any existing redirection for that message.

```

12549 \cs_new_protected:Npn \msg_redirect_name:nnn #1#2#3
12550 {
12551     \tl_if_empty:nTF {#3}
12552     { \prop_remove:Nn \l__msg_redirect_prop { / #1 / #2 } }
12553     {
12554         \__msg_class_chk_exist:nT {#3}
12555         { \prop_put:Nnn \l__msg_redirect_prop { / #1 / #2 } {#3} }
12556     }
12557 }

```

(End definition for `\msg_redirect_name:nnn`. This function is documented on page 155.)

`\msg_redirect_class:nn` If the target class is empty, eliminate the corresponding redirection. Otherwise, add the redirection. We must then check for a loop: as an initialization, we start by storing the initial class in `\l__msg_current_class_tl`.

`\msg_redirect_module:nnn`

`__msg_redirect:nnn`

`__msg_redirect_loop_chk:nnn`

`__msg_redirect_loop_list:n`

```

12558 \cs_new_protected:Npn \msg_redirect_class:nn
12559 { \__msg_redirect:nnn { } }
12560 \cs_new_protected:Npn \msg_redirect_module:nnn #1
12561 { \__msg_redirect:nnn { / #1 } }
12562 \cs_new_protected:Npn \__msg_redirect:nnn #1#2#3
12563 {
12564     \__msg_class_chk_exist:nT {#2}
12565     {
12566         \tl_if_empty:nTF {#3}
12567         { \prop_remove:cn { l__msg_redirect_ #2 _prop } {#1} }
12568         {
12569             \__msg_class_chk_exist:nT {#3}
12570             {
12571                 \prop_put:cnn { l__msg_redirect_ #2 _prop } {#1} {#3}
12572                 \tl_set:Nn \l__msg_current_class_tl {#2}
12573                 \seq_clear:N \l__msg_class_loop_seq
12574                 \__msg_redirect_loop_chk:nnn {#2} {#3} {#1}
12575             }
12576         }
12577     }
12578 }

```

Since multiple redirections can only happen with increasing specificity, a loop requires that all steps are of the same specificity. The new redirection can thus only create a loop with other redirections for the exact same module, #1, and not submodules. After some initialization above, follow redirections with `\l__msg_class_tl`, and keep track in `\l__msg_class_loop_seq` of the various classes encountered. A redirection from a class to itself, or the absence of redirection both mean that there is no loop. A redirection to the initial class marks a loop. To break it, we must decide which redirection to cancel. The user most likely wants the newly added redirection to hold with no further redirection. We thus remove the redirection starting from #2, target of the new redirection. Note that no message is emitted by any of the underlying functions: otherwise we may get an infinite loop because of a message from the message system itself.

```

12579 \cs_new_protected:Npn \__msg_redirect_loop_chk:nnn #1#2#3
12580 {
12581   \seq_put_right:Nn \l__msg_class_loop_seq {#1}
12582   \prop_get:cnNT { l__msg_redirect_ #1_prop } {#3} \l__msg_class_tl
12583   {
12584     \str_if_eq:VnF \l__msg_class_tl {#1}
12585     {
12586       \tl_if_eq:NNTF \l__msg_class_tl \l__msg_current_class_tl
12587       {
12588         \prop_put:cnn { l__msg_redirect_ #2_prop } {#3} {#2}
12589         \__kernel_msg_warning:nxxxx
12590         { kernel } { message-redirect-loop }
12591         { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
12592         { \seq_item:Nn \l__msg_class_loop_seq { 2 } }
12593         {#3}
12594         {
12595           \seq_map_function:NN \l__msg_class_loop_seq
12596             \__msg_redirect_loop_list:n
12597             { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
12598         }
12599       }
12600       { \__msg_redirect_loop_chk:onn \l__msg_class_tl {#2} {#3} }
12601     }
12602   }
12603 }
12604 \cs_generate_variant:Nn \__msg_redirect_loop_chk:nnn { o }
12605 \cs_new:Npn \__msg_redirect_loop_list:n #1 { {#1} ~ => ~ }

```

(End definition for `\msg_redirect_class:nn` and others. These functions are documented on page 155.)

19.6 Kernel-specific functions

`__kernel_msg_new:nnnn` The kernel needs some messages of its own. These are created using pre-built functions. Two functions are provided: one more general and one which only has the short text part.

```

\__kernel_msg_set:nnnn
\__kernel_msg_set:nnn
12606 \cs_new_protected:Npn \__kernel_msg_new:nnnn #1#2
12607 { \msg_new:nnnn { LaTeX } { #1 / #2 } }
12608 \cs_new_protected:Npn \__kernel_msg_new:nnn #1#2
12609 { \msg_new:nnn { LaTeX } { #1 / #2 } }
12610 \cs_new_protected:Npn \__kernel_msg_set:nnnn #1#2
12611 { \msg_set:nnnn { LaTeX } { #1 / #2 } }
12612 \cs_new_protected:Npn \__kernel_msg_set:nnn #1#2

```

(End definition for `_kernel_msg_new:nnnn` and others.)

All the functions for kernel messages come in variants ranging from 0 to 4 arguments. Those with less than 4 arguments are defined in terms of the 4-argument variant, in a way very similar to `_msg_class_new:nn`. This auxiliary is destroyed at the end of the group.

(End definition for `_msg_kernel_class_new:nN` and `_msg_kernel_class_new_aux:nN`.)

Neither fatal kernel errors nor kernel errors can be redirected. We directly use the code for (non-kernel) fatal errors and errors, adding the “`LATEX`” module name. Three functions are already defined by `l3basics`; we need to undefine them to avoid errors.

```
12652  \_msg_kernel_class_new:nN { fatal } \_msg_fatal_code:nnnnnn
12653  \cs_undefine:N \_kernel_msg_error:nnxx
```

```

12654 \cs_undefine:N \__kernel_msg_error:nnx
12655 \cs_undefine:N \__kernel_msg_error:nn
12656 \__msg_kernel_class_new:nN { error } \__msg_error_code:nnnnnn

```

(End definition for __kernel_msg_fatal:nnnnnn and others.)

Kernel messages which can be redirected simply use the machinery for normal messages, with the module name “`LATEX`”.

```

12657 \__msg_kernel_class_new:nN { warning } \msg_warning:nnxxxx
12658 \__msg_kernel_class_new:nN { info } \msg_info:nnxxxx

```

(End definition for __kernel_msg_warning:nnnnnn and others.)

End the group to eliminate __msg_kernel_class_new:nN.

```

12659 \group_end:

```

Error messages needed to actually implement the message system itself.

```

12660 \__kernel_msg_new:nnnn { kernel } { message-already-defined }
12661 { Message~'~#2'~for~module~'~#1'~already-defined. }
12662 {
12663   \c__msg_coding_error_text_tl
12664   LaTeX~was~asked~to~define~a~new~message~called~'~#2'~\
12665   by~the~module~'~#1'~:~this~message~already~exists.
12666   \c__msg_return_text_tl
12667 }
12668 \__kernel_msg_new:nnnn { kernel } { message-unknown }
12669 { Unknown~message~'~#2'~for~module~'~#1'~. }
12670 {
12671   \c__msg_coding_error_text_tl
12672   LaTeX~was~asked~to~display~a~message~called~'~#2'~\
12673   by~the~module~'~#1'~:~this~message~does~not~exist.
12674   \c__msg_return_text_tl
12675 }
12676 \__kernel_msg_new:nnnn { kernel } { message-class-unknown }
12677 { Unknown~message~class~'~#1'~. }
12678 {
12679   LaTeX~has~been~asked~to~redirect~messages~to~a~class~'~#1'~:~\
12680   this~was~never~defined.
12681   \c__msg_return_text_tl
12682 }
12683 \__kernel_msg_new:nnnn { kernel } { message-redirect-loop }
12684 {
12685   Message~redirection~loop~caused~by~ {#1} ~=>~ {#2}
12686   \tl_if_empty:nF {#3} { ~for~module~' \use_none:n #3 ' } .
12687 }
12688 {
12689   Adding~the~message~redirection~ {#1} ~=>~ {#2}
12690   \tl_if_empty:nF {#3} { ~for~the~module~' \use_none:n #3 ' } ~
12691   created~an~infinite~loop~\
12692   \iow_indent:n { #4 \\\ }
12693 }

```

Messages for earlier kernel modules plus a few for `l3keys` which cover coding errors.

```

12694 \__kernel_msg_new:nnnn { kernel } { bad-number-of-arguments }
12695 { Function~'~#1'~cannot~be~defined~with~#2~arguments. }
12696 {

```

```

12697 \c__msg_coding_error_text_tl
12698 LaTeX-has-been-asked-to-define-a-function-~'~#1'~with-
12699 #2~arguments.~
12700 TeX-allows-between-0~and~9~arguments~for~a~single~function.
12701 }
12702 \__kernel_msg_new:nnn { kernel } { char-active }
12703 { Cannot-generate-active-chars. }
12704 \__kernel_msg_new:nnn { kernel } { char-invalid-catcode }
12705 { Invalid-catcode-for-char-generation. }
12706 \__kernel_msg_new:nnn { kernel } { char-null-space }
12707 { Cannot-generate-null-char-as-a-space. }
12708 \__kernel_msg_new:nnn { kernel } { char-out-of-range }
12709 { Charcode-requested-out-of-engine-range. }
12710 \__kernel_msg_new:nnn { kernel } { char-space }
12711 { Cannot-generate-space-chars. }
12712 \__kernel_msg_new:nnnn { kernel } { command-already-defined }
12713 { Control-sequence-~#1~already-defined. }
12714 {
12715 \c__msg_coding_error_text_tl
12716 LaTeX-has-been-asked-to-create-a-new-control-sequence-~'~#1'~
12717 but-this-name-has-already-been-used-elsewhere. \\ \\
12718 The-current-meaning-is:\\
12719 \\ #2
12720 }
12721 \__kernel_msg_new:nnnn { kernel } { command-not-defined }
12722 { Control-sequence-~#1~undefined. }
12723 {
12724 \c__msg_coding_error_text_tl
12725 LaTeX-has-been-asked-to-use-a-control-sequence-~'~#1'::~\\
12726 this-has-not-been-defined-yet.
12727 }
12728 \__kernel_msg_new:nnnn { kernel } { empty-search-pattern }
12729 { Empty-search-pattern. }
12730 {
12731 \c__msg_coding_error_text_tl
12732 LaTeX-has-been-asked-to-replace-an-empty-pattern-by-~'~#1'::~~that-
12733 would-lead-to-an-infinite-loop!
12734 }
12735 \__kernel_msg_new:nnnn { kernel } { out-of-registers }
12736 { No-room-for-a-new-~#1. }
12737 {
12738 TeX-only-supports-~\int_use:N \c_max_register_int \ %
12739 of-each-type.~All-the-~#1~registers-have-been-used.~
12740 This-run-will-be-aborted-now.
12741 }
12742 \__kernel_msg_new:nnnn { kernel } { non-base-function }
12743 { Function-~'~#1'~is-not-a-base-function }
12744 {
12745 \c__msg_coding_error_text_tl
12746 Functions-defined-through-~\iow_char:N\\cs_new:Nn~must~have~
12747 a~signature~consisting-of-only~normal~arguments-~'~N'~and-~'~n'.~
12748 To-define-variants-use-~\iow_char:N\\cs_generate_variant:Nn~
12749 and-to-define-other-functions-use-~\iow_char:N\\cs_new:Npn.
12750 }

```

```

12751 \__kernel_msg_new:nnnn { kernel } { missing-colon }
12752 { Function~'#1'~contains~no~':'~. }
12753 {
12754   \c__msg_coding_error_text_tl
12755   Code-level-functions-must-contain~':'~to-separate-the~
12756   argument-specification-from-the-function-name.~This-is~
12757   needed-when-defining-conditionals-or-variants,~or-when-building-a~
12758   parameter-text-from-the-number-of-arguments-of-the-function.
12759 }
12760 \__kernel_msg_new:nnnn { kernel } { overflow }
12761 { Integers-larger-than-2^{30}-1-cannot-be-stored-in-arrays. }
12762 {
12763   An-attempt-was-made-to-store~#3~
12764   \tl_if_empty:nF {#2} { at-position~#2~ } in-the-array~'#1'~.~
12765   The-largest-allowed-value~#4~will-be-used-instead.
12766 }
12767 \__kernel_msg_new:nnnn { kernel } { out-of-bounds }
12768 { Access-to-an-entry-beyond-an-array's-bounds. }
12769 {
12770   An-attempt-was-made-to-access-or-store-data-at-position~#2~of-the~
12771   array~'#1',~but-this-array-has-entries-at-positions-from-1-to~#3.
12772 }
12773 \__kernel_msg_new:nnnn { kernel } { protected-predicate }
12774 { Predicate~'#1'~must-be-expandable. }
12775 {
12776   \c__msg_coding_error_text_tl
12777   LaTeX-has-been-asked-to-define~'#1'~as-a-protected-predicate.~
12778   Only-expandable-tests-can-have-a-predicate-version.
12779 }
12780 \__kernel_msg_new:nnn { kernel } { randint-backward-range }
12781 { Bounds-ordered-backwards-in-\iow_char:N\int_rand:nn~{#1}~{#2}. }
12782 \__kernel_msg_new:nnnn { kernel } { conditional-form-unknown }
12783 { Conditional-form~'#1'~for-function~'#2'~unknown. }
12784 {
12785   \c__msg_coding_error_text_tl
12786   LaTeX-has-been-asked-to-define-the-conditional-form~'#1'~of~
12787   the-function~'#2',~but-only~'TF',~'T',~'F',~and~'p'~forms-exist.
12788 }
12789 \__kernel_msg_new:nnnn { kernel } { key-no-property }
12790 { No-property-given-in-definition-of-key~'#1'. }
12791 {
12792   \c__msg_coding_error_text_tl
12793   Inside~\keys_define:nn each-key-name~
12794   needs-a-property: \ \ \
12795   \iow_indent:n { #1 .<property> } \ \ \
12796   LaTeX-did-not-find-a~'. '~to-indicate-the-start-of-a-property.
12797 }
12798 \__kernel_msg_new:nnnn { kernel } { key-property-boolean-values-only }
12799 { The-property~'#1'~accepts-boolean-values-only. }
12800 {
12801   \c__msg_coding_error_text_tl
12802   The-property~'#1'~only-accepts-the-values~'true'~and~'false'.
12803 }
12804 \__kernel_msg_new:nnnn { kernel } { key-property-requires-value }

```



```

12805 { The~property~'#1'~requires~a~value. }
12806 {
12807   \c__msg_coding_error_text_tl
12808   LaTeX~was~asked~to~set~property~'#1'~for~key~'#2'.\\
12809   No~value~was~given~for~the~property,~and~one~is~required.
12810 }
12811 \__kernel_msg_new:nnnn { kernel } { key-property-unknown }
12812 { The~key~property~'#1'~is~unknown. }
12813 {
12814   \c__msg_coding_error_text_tl
12815   LaTeX~has~been~asked~to~set~the~property~'#1'~for~key~'#2':~
12816   this~property~is~not~defined.
12817 }
12818 \__kernel_msg_new:nnnn { kernel } { quote-in-shell }
12819 { Quotes~in~shell~command~'#1'. }
12820 { Shell~commands~cannot~contain~quotes~("). }
12821 \__kernel_msg_new:nnnn { kernel } { invalid-quark-function }
12822 { Quark~test~function~'#1'~is~invalid. }
12823 {
12824   \c__msg_coding_error_text_tl
12825   LaTeX~has~been~asked~to~create~quark~test~function~'#1'~
12826   \tl_if_empty:nTF {#2}
12827   { but~that~name~ }
12828   { with~signature~'#2',~but~that~signature~ }
12829   is~not~valid.
12830 }
12831 \__kernel_msg_new:nnn { kernel } { invalid-quark }
12832 { Invalid~quark~variable~'#1'. }
12833 \__kernel_msg_new:nnnn { kernel } { scanmark-already-defined }
12834 { Scan~mark~#1~already~defined. }
12835 {
12836   \c__msg_coding_error_text_tl
12837   LaTeX~has~been~asked~to~create~a~new~scan~mark~'#1'~
12838   but~this~name~has~already~been~used~for~a~scan~mark.
12839 }
12840 \__kernel_msg_new:nnnn { kernel } { shuffle-too-large }
12841 { The~sequence~#1~is~too~long~to~be~shuffled~by~TeX. }
12842 {
12843   TeX~has~ \int_eval:n { \c_max_register_int + 1 } ~
12844   toks~registers:~this~only~allows~to~shuffle~up~to~
12845   \int_use:N \c_max_register_int \ items.~
12846   The~list~will~not~be~shuffled.
12847 }
12848 \__kernel_msg_new:nnnn { kernel } { variable-not-defined }
12849 { Variable~#1~undefined. }
12850 {
12851   \c__msg_coding_error_text_tl
12852   LaTeX~has~been~asked~to~show~a~variable~#1,~but~this~has~not~
12853   been~defined~yet.
12854 }
12855 \__kernel_msg_new:nnnn { kernel } { variant-too-long }
12856 { Variant~form~'#1'~longer~than~base~signature~of~'#2'. }
12857 {
12858   \c__msg_coding_error_text_tl

```

```

12859 LaTeX~has~been~asked~to~create~a~variant~of~the~function~'#2'~
12860 with~a~signature~starting~with~'#1',~but~that~is~longer~than~
12861 the~signature~(part~after~the~colon)~of~'#2'.
12862 }
12863 \__kernel_msg_new:nnnn { kernel } { invalid-variant }
12864 { Variant-form~'#1'~invalid~for~base-form~'#2'. }
12865 {
12866   \c__msg_coding_error_text_tl
12867   LaTeX~has~been~asked~to~create~a~variant~of~the~function~'#2'~
12868   with~a~signature~starting~with~'#1',~but~cannot~change~an~argument~
12869   from~type~'#3'~to~type~'#4'.
12870 }
12871 \__kernel_msg_new:nnnn { kernel } { invalid-exp-args }
12872 { Invalid-variant~specifier~'#1'~in~'#2'. }
12873 {
12874   \c__msg_coding_error_text_tl
12875   LaTeX~has~been~asked~to~create~an~\iow_char:N\exp_args:N...~
12876   function~with~signature~'N#2'~but~'#1'~is~not~a~valid~argument~
12877   specifier.
12878 }
12879 \__kernel_msg_new:nnn { kernel } { deprecated-variant }
12880 {
12881   Variant-form~'#1'~deprecated~for~base-form~'#2'.~
12882   One~should~not~change~an~argument~from~type~'#3'~to~type~'#4'
12883   \str_case:nnF {#3}
12884   {
12885     { n } { :~use~a~'\token_if_eq_charcode:NNTF #4 c v V'~variant? }
12886     { N } { :~base-form~only~accepts~a~single~token~argument. }
12887     {#4} { :~base-form~is~already~a~variant. }
12888     } { . }
12889 }

```

Some errors are only needed in package mode if debugging is enabled by one of the options `enable-debug`, `check-declarations`, `log-functions`, or on the contrary if debugging is turned off. In format mode the error is somewhat different.

```

12890 (*package)
12891 \__kernel_msg_new:nnnn { kernel } { enable-debug }
12892 { To~use~'#1'~load~expl3~with~the~'enable-debug'~option. }
12893 {
12894   The~function~'#1'~will~be~ignored~because~it~can~only~work~if~
12895   some~internal~functions~in~expl3~have~been~appropriately~
12896   defined.~This~only~happens~if~one~of~the~options~
12897   'enable-debug',~'check-declarations'~or~'log-functions'~was~
12898   given~when~loading~expl3.
12899 }
12900 </package>
12901 (*initex)
12902 \__kernel_msg_new:nnnn { kernel } { enable-debug }
12903 { '#1'~cannot~be~used~in~format~mode. }
12904 {
12905   The~function~'#1'~will~be~ignored~because~it~can~only~work~if~
12906   some~internal~functions~in~expl3~have~been~appropriately~
12907   defined.~This~only~happens~in~package~mode~(and~only~if~one~of~
12908   the~options~'enable-debug',~'check-declarations'~or~'log-functions'~

```

```

12909     was~given~when~loading~expl3.
12910 }
12911 </initex>

```

Some errors only appear in expandable settings, hence don't need a “more-text” argument.

```

12912 \__kernel_msg_new:nnn { kernel } { bad-exp-end-f }
12913 { Misused~\exp_end_continue_f:w or~:nw }
12914 \__kernel_msg_new:nnn { kernel } { bad-variable }
12915 { Erroneous~variable~#1 used! }
12916 \__kernel_msg_new:nnn { kernel } { misused-sequence }
12917 { A~sequence~was~misused. }
12918 \__kernel_msg_new:nnn { kernel } { misused-prop }
12919 { A~property~list~was~misused. }
12920 \__kernel_msg_new:nnn { kernel } { negative-replication }
12921 { Negative~argument~for~\iow_char:N\prg_replicate:nn. }
12922 \__kernel_msg_new:nnn { kernel } { prop-keyval }
12923 { Missing/extra~'=~in~'~#1'~(in~'..._keyval:Nn') }
12924 \__kernel_msg_new:nnn { kernel } { unknown-comparison }
12925 { Relation~'~#1'~unknown:~use~=,~<,~>,~==,~!=,~<=,~>=. }
12926 \__kernel_msg_new:nnn { kernel } { zero-step }
12927 { Zero~step~size~for~step~function~#1. }
12928 \cs_if_exist:NF \tex_expanded:D
12929 {
12930   \__kernel_msg_new:nnn { kernel } { e-type }
12931   { #1 ~ in~e-type~argument }
12932 }

```

Messages used by the “show” functions.

```

12933 \__kernel_msg_new:nnn { kernel } { show-clist }
12934 {
12935   The~comma~list~ \tl_if_empty:nF {#1} { #1 ~ }
12936   \tl_if_empty:nTF {#2}
12937   { is~empty \>~ . }
12938   { contains~the~items~(without~outer~braces): #2 . }
12939 }
12940 \__kernel_msg_new:nnn { kernel } { show-intarray }
12941 { The~integer~array~#1~contains~#2~items: \> #3 . }
12942 \__kernel_msg_new:nnn { kernel } { show-prop }
12943 {
12944   The~property~list~#1~
12945   \tl_if_empty:nTF {#2}
12946   { is~empty \>~ . }
12947   { contains~the~pairs~(without~outer~braces): #2 . }
12948 }
12949 \__kernel_msg_new:nnn { kernel } { show-seq }
12950 {
12951   The~sequence~#1~
12952   \tl_if_empty:nTF {#2}
12953   { is~empty \>~ . }
12954   { contains~the~items~(without~outer~braces): #2 . }
12955 }
12956 \__kernel_msg_new:nnn { kernel } { show-streams }
12957 {
12958   \tl_if_empty:nTF {#2} { No~ } { The~following~

```

```

12959 \str_case:nn {#1}
12960 {
12961   { ior } { input ~ }
12962   { iow } { output ~ }
12963 }
12964 streams-are~
12965 \tl_if_empty:nTF {#2} { open } { in~use: #2 . }
12966 }

```

System layer messages

```

12967 \__kernel_msg_new:nnnn { sys } { backend-set }
12968 { Backend~configuration~already~set. }
12969 {
12970   Run-time-backend-selection-may-only-be-carried-out-once-during-a-run.~
12971   This-second-attempt-to-set-them-will-be-ignored.
12972 }
12973 \__kernel_msg_new:nnnn { sys } { wrong-backend }
12974 { Backend-request~inconsistent~with~engine:~using~'#2'~backend. }
12975 {
12976   You-have-requested-backend~'#1',~but~this-is-not~suitable~for~use~with~the~
12977   active-engine.~LaTeX3-will-use~the~'#2'~backend~instead.
12978 }

```

19.7 Expandable errors

`__msg_expandable_error:n` In expansion only context, we cannot use the normal means of reporting errors. Instead, we feed TeX an undefined control sequence, `\LaTeX3 error:`. It is thus interrupted, and shows the context, which thanks to the odd-looking `\use:n` is

```

<argument> \LaTeX3 error:
                The error message.

```

In other words, TeX is processing the argument of `\use:n`, which is `\LaTeX3 error: <error message>`. Then `__msg_expandable_error:w` cleans up. In fact, there is an extra subtlety: if the user inserts tokens for error recovery, they should be kept. Thus we also use an odd space character (with category code 7) and keep tokens until that space character, dropping everything else until `\s__msg_stop`. The `\exp_end:` prevents losing braces around the user-inserted text if any, and stops the expansion of `\exp:w`. The group is used to prevent `\LaTeX3-error:` from being globally equal to `\scan_stop:`.

```

12979 \group_begin:
12980 \cs_set_protected:Npn \__msg_tmp:w #1#2
12981 {
12982   \cs_new:Npn \__msg_expandable_error:n ##1
12983   {
12984     \exp:w
12985     \exp_after:wN \exp_after:wN
12986     \exp_after:wN \__msg_expandable_error:w
12987     \exp_after:wN \exp_after:wN
12988     \exp_after:wN \exp_end:
12989     \use:n { #1 #2 ##1 } #2
12990   }
12991   \cs_new:Npn \__msg_expandable_error:w ##1 #2 ##2 #2 {##1}
12992 }
12993 \exp_args:Ncx \__msg_tmp:w { LaTeX3-error: }

```

```

12994 { \char_generate:nn { ‘\ } { 7 } }
12995 \group_end:

```

(End definition for _msg_expandable_error:n and _msg_expandable_error:w.)

The command built from the csname \c__msg_text_prefix_tl LaTeX / #1 / #2 takes four arguments and builds the error text, which is fed to _msg_expandable_error:n with appropriate expansion: just as for usual messages the arguments are first turned to strings, then the message is fully expanded.

```

12996 \exp_args_generate:n { oooo }
12997 \cs_new:Npn \_kernel_msg_expandable_error:nnnnnn #1#2#3#4#5#6
12998 {
12999   \exp_args:Ne \_msg_expandable_error:n
13000   {
13001     \exp_args:Nc \exp_args:Noooo
13002     { \c__msg_text_prefix_tl LaTeX / #1 / #2 }
13003     { \tl_to_str:n {#3} }
13004     { \tl_to_str:n {#4} }
13005     { \tl_to_str:n {#5} }
13006     { \tl_to_str:n {#6} }
13007   }
13008 }
13009 \cs_new:Npn \_kernel_msg_expandable_error:nnnnn #1#2#3#4#5
13010 {
13011   \_kernel_msg_expandable_error:nnnnnn
13012   {#1} {#2} {#3} {#4} {#5} { }
13013 }
13014 \cs_new:Npn \_kernel_msg_expandable_error:nnnn #1#2#3#4
13015 {
13016   \_kernel_msg_expandable_error:nnnnnn
13017   {#1} {#2} {#3} {#4} { } { }
13018 }
13019 \cs_new:Npn \_kernel_msg_expandable_error:nnn #1#2#3
13020 {
13021   \_kernel_msg_expandable_error:nnnnnn
13022   {#1} {#2} {#3} { } { } { }
13023 }
13024 \cs_new:Npn \_kernel_msg_expandable_error:nn #1#2
13025 {
13026   \_kernel_msg_expandable_error:nnnnnn
13027   {#1} {#2} { } { } { } { }
13028 }
13029 \cs_generate_variant:Nn \_kernel_msg_expandable_error:nnnnnn { nnffff }
13030 \cs_generate_variant:Nn \_kernel_msg_expandable_error:nnnnnn { nnfff }
13031 \cs_generate_variant:Nn \_kernel_msg_expandable_error:nnnn { nnff }
13032 \cs_generate_variant:Nn \_kernel_msg_expandable_error:nnn { nnf }

```

(End definition for _kernel_msg_expandable_error:nnnnnn and others.)

```

13033 </initex | package>

```

20 l3file implementation

The following test files are used for this code: m3file001.

```

13034 (*initex | package>

```

20.1 Input operations

13035 `<@@=ior>`

20.1.1 Variables and constants

`\l__ior_internal_tl` Used as a short-term scratch variable.

13036 `\tl_new:N \l__ior_internal_tl`

(End definition for `\l__ior_internal_tl`.)

`\c__ior_term_ior` Reading from the terminal (with a prompt) is done using a positive but non-existent stream number. Unlike writing, there is no concept of reading from the log.

13037 `\int_const:Nn \c__ior_term_ior { 16 }`

(End definition for `\c__ior_term_ior`.)

`\g__ior_streams_seq` A list of the currently-available input streams to be used as a stack. In format mode, all streams (from 0 to 15) are available, while the package requests streams to L^AT_EX 2_ε as they are needed (initially none are needed), so the starting point varies!

13038 `\seq_new:N \g__ior_streams_seq`

13039 `<*initex>`

13040 `\seq_gset_split:Nnn \g__ior_streams_seq { , }`

13041 `{ 0 , 1 , 2 , 3 , 4 , 5 , 6 , 7 , 8 , 9 , 10 , 11 , 12 , 13 , 14 , 15 }`

13042 `</initex>`

(End definition for `\g__ior_streams_seq`.)

`\l__ior_stream_tl` Used to recover the raw stream number from the stack.

13043 `\tl_new:N \l__ior_stream_tl`

(End definition for `\l__ior_stream_tl`.)

`\g__ior_streams_prop` The name of the file attached to each stream is tracked in a property list. To get the correct number of reserved streams in package mode the underlying mechanism needs to be queried. For L^AT_EX 2_ε and plain T_EX this data is stored in `\count16`: with the `etex` package loaded we need to subtract 1 as the register holds the number of the next stream to use. In ConT_EXt, we need to look at `\count38` but there is no subtraction: like the original plain T_EX/L^AT_EX 2_ε mechanism it holds the value of the *last* stream allocated.

13044 `\prop_new:N \g__ior_streams_prop`

13045 `<*package>`

13046 `\int_step_inline:nnn`

13047 `{ 0 }`

13048 `{`

13049 `\cs_if_exist:NTF \normalend`

13050 `{ \tex_count:D 38 ~ }`

13051 `{`

13052 `\tex_count:D 16 ~ %`

13053 `\cs_if_exist:NT \loccount { - 1 }`

13054 `}`

13055 `}`

13056 `{`

13057 `\prop_gput:Nnn \g__ior_streams_prop {#1} { Reserved-by~format }`

13058 `}`

13059 `</package>`

(End definition for `\g__ior_streams_prop`.)

20.1.2 Stream management

\ior_new:N Reserving a new stream is done by defining the name as equal to using the terminal.
\ior_new:c 13060 \cs_new_protected:Npn \ior_new:N #1 { \cs_new_eq:NN #1 \c_ior_term_ior }
 13061 \cs_generate_variant:Nn \ior_new:N { c }

(End definition for \ior_new:N. This function is documented on page 156.)

\g_tmpa_ior The usual scratch space.
\g_tmpb_ior 13062 \ior_new:N \g_tmpa_ior
 13063 \ior_new:N \g_tmpb_ior

(End definition for \g_tmpa_ior and \g_tmpb_ior. These variables are documented on page 163.)

\ior_open:Nn Use the conditional version, with an error if the file is not found.
\ior_open:cn 13064 \cs_new_protected:Npn \ior_open:Nn #1#2
 13065 { \ior_open:NnF #1 {#2} { _kernel_file_missing:n {#2} } }
 13066 \cs_generate_variant:Nn \ior_open:Nn { c }

(End definition for \ior_open:Nn. This function is documented on page 156.)

\l_ior_file_name_tl Data storage.
 13067 \tl_new:N \l_ior_file_name_tl

(End definition for \l_ior_file_name_tl.)

\ior_open:NnTF An auxiliary searches for the file in the T_EX, L^AT_EX 2_ε and L^AT_EX 3 paths. Then pass the
\ior_open:cnTF file found to the lower-level function which deals with streams. The full_name is empty
 when the file is not found.

```
13068 \prg_new_protected_conditional:Npnn \ior_open:Nn #1#2 { T , F , TF }
13069 {
13070   \file_get_full_name:nNTF {#2} \l_ior_file_name_tl
13071   {
13072     \_kernel_ior_open:No #1 \l_ior_file_name_tl
13073     \prg_return_true:
13074   }
13075   { \prg_return_false: }
13076 }
13077 \prg_generate_conditional_variant:Nnn \ior_open:Nn { c } { T , F , TF }
```

(End definition for \ior_open:NnTF. This function is documented on page 157.)

__ior_new:N In package mode, streams are reserved using \newread before they can be managed by
 ior. To prevent ior from being affected by redefinitions of \newread (such as done by
 the third-party package morewrites), this macro is saved here under a private name. The
 complicated code ensures that __ior_new:N is not \outer despite plain T_EX's \newread
 being \outer. For ConT_EXt, we have to deal with the fact that \newread works like our
 own: it actually checks before altering definition.

```
13078 \*package)
13079 \exp_args:NNf \cs_new_protected:Npn \__ior_new:N
13080 { \exp_args:NNc \exp_after:wN \exp_stop_f: { newread } }
13081 \cs_if_exist:NT \normalend
13082 {
13083   \cs_new_eq:NN \__ior_new_aux:N \__ior_new:N
13084   \cs_set_protected:Npn \__ior_new:N #1
```

```

13085     {
13086       \cs_undefine:N #1
13087       \__ior_new_aux:N #1
13088     }
13089   }
13090 </package>

```

(End definition for __ior_new:N.)

__kernel_ior_open:Nn The stream allocation itself uses the fact that there is a list of all of those available, so allocation is simply a question of using the number at the top of the list. In package mode, life gets more complex as it's important to keep things in sync. That is done using a two-part approach: any streams that have already been taken up by ior but are now free are tracked, so we first try those. If that fails, ask plain T_EX or L^AT_EX 2_ε for a new stream and use that number (after a bit of conversion).

```

13091 \cs_new_protected:Npn \__kernel_ior_open:Nn #1#2
13092 {
13093   \ior_close:N #1
13094   \seq_gpop:NNTF \g__ior_streams_seq \l__ior_stream_tl
13095   { \__ior_open_stream:Nn #1 {#2} }
13096 <*initex>
13097   { \__kernel_msg_fatal:nn { kernel } { input-streams-exhausted } }
13098 </initex>
13099 <*package>
13100 {
13101   \__ior_new:N #1
13102   \tl_set:Nx \l__ior_stream_tl { \int_eval:n {#1} }
13103   \__ior_open_stream:Nn #1 {#2}
13104 }
13105 </package>
13106 }
13107 \cs_generate_variant:Nn \__kernel_ior_open:Nn { No }

```

Here, we act defensively in case LuaT_EX is in use with an extensionless file name.

```

13108 \cs_new_protected:Npx \__ior_open_stream:Nn #1#2
13109 {
13110   \tex_global:D \tex_chardef:D #1 = \exp_not:N \l__ior_stream_tl \scan_stop:
13111   \prop_gput:NVn \exp_not:N \g__ior_streams_prop #1 {#2}
13112   \tex_openin:D #1
13113   \sys_if_engine luatex:TF
13114   { {#2} }
13115   { \exp_not:N \__kernel_file_name_quote:n {#2} \scan_stop: }
13116 }

```

(End definition for __kernel_ior_open:Nn and __ior_open_stream:Nn.)

\ior_close:N Closing a stream means getting rid of it at the T_EX level and removing from the various data structures. Unless the name passed is an invalid stream number (outside the range [0, 15]), it can be closed. On the other hand, it only gets added to the stack if it was not already there, to avoid duplicates building up.

\ior_close:c

```

13117 \cs_new_protected:Npn \ior_close:N #1
13118 {
13119   \int_compare:nT { -1 < #1 < \c__ior_term_ior }
13120   {

```



```

13121         \tex_closein:D #1
13122         \prop_gremove:NV \g__ior_streams_prop #1
13123         \seq_if_in:NVF \g__ior_streams_seq #1
13124         { \seq_gpush:NV \g__ior_streams_seq #1 }
13125         \cs_gset_eq:NN #1 \c__ior_term_ior
13126     }
13127 }
13128 \cs_generate_variant:Nn \ior_close:N { c }

```

(End definition for `\ior_close:N`. This function is documented on page 157.)

`\ior_show_list:` Show the property lists, but with some “pretty printing”. See the `l3msg` module. The first argument of the message is `ior` (as opposed to `iow`) and the second is empty if no read stream is open and non-empty (the list of streams formatted using `\msg_show_item_unbraced:nn`) otherwise. The code of the message `show-streams` takes care of translating `ior/iow` to English.

```

13129 \cs_new_protected:Npn \ior_show_list: { \__ior_list:N \msg_show:nnxxxx }
13130 \cs_new_protected:Npn \ior_log_list: { \__ior_list:N \msg_log:nnxxxx }
13131 \cs_new_protected:Npn \__ior_list:N #1
13132 {
13133     #1 { LaTeX / kernel } { show-streams }
13134     { ior }
13135     {
13136         \prop_map_function:NN \g__ior_streams_prop
13137         \msg_show_item_unbraced:nn
13138     }
13139     { } { }
13140 }

```

(End definition for `\ior_show_list:`, `\ior_log_list:`, and `__ior_list:N`. These functions are documented on page 157.)

20.1.3 Reading input

`\if_eof:w` The primitive conditional

```

13141 \cs_new_eq:NN \if_eof:w \tex_ifeof:D

```

(End definition for `\if_eof:w`. This function is documented on page 163.)

`\ior_if_eof_p:N` To test if some particular input stream is exhausted the following conditional is provided.
`\ior_if_eof:N \underline{TF}` The primitive test can only deal with numbers in the range $[0, 15]$ so we catch outliers (they are exhausted).

```

13142 \prg_new_conditional:Npnn \ior_if_eof:N #1 { p , T , F , TF }
13143 {
13144     \cs_if_exist:NTF #1
13145     {
13146         \int_compare:nTF { -1 < #1 < \c__ior_term_ior }
13147         {
13148             \if_eof:w #1
13149             \prg_return_true:
13150             \else:
13151                 \prg_return_false:
13152             \fi:
13153         }

```

```

13154         { \prg_return_true: }
13155     }
13156     { \prg_return_true: }
13157 }

```

(End definition for `\ior_if_eof:NTF`. This function is documented on page 160.)

`\ior_get:NN` And here we read from files.

```

\__ior_get:NN 13158 \cs_new_protected:Npn \ior_get:NN #1#2
\ior_get:NNTF 13159 { \ior_get:NNTF #1 #2 { \tl_set:Nn #2 { \q_no_value } } }
13160 \cs_new_protected:Npn \__ior_get:NN #1#2
13161 { \tex_read:D #1 to #2 }
13162 \prg_new_protected_conditional:Npnn \ior_get:NN #1#2 { T , F , TF }
13163 {
13164     \ior_if_eof:NTF #1
13165     { \prg_return_false: }
13166     {
13167         \__ior_get:NN #1 #2
13168         \prg_return_true:
13169     }
13170 }

```

(End definition for `\ior_get:NN`, `__ior_get:NN`, and `\ior_get:NNTF`. These functions are documented on page 158.)

`\ior_str_get:NN` Reading as strings is a more complicated wrapper, as we wish to remove the newline character and restore it afterwards.

```

\__ior_str_get:NN 13171 \cs_new_protected:Npn \ior_str_get:NN #1#2
\ior_str_get:NNTF 13172 { \ior_str_get:NNTF #1 #2 { \tl_set:Nn #2 { \q_no_value } } }
13173 \cs_new_protected:Npn \__ior_str_get:NN #1#2
13174 {
13175     \exp_args:Nno \use:n
13176     {
13177         \int_set:Nn \tex_endlinechar:D { -1 }
13178         \tex_readline:D #1 to #2
13179         \int_set:Nn \tex_endlinechar:D
13180         } { \int_use:N \tex_endlinechar:D }
13181     }
13182 \prg_new_protected_conditional:Npnn \ior_str_get:NN #1#2 { T , F , TF }
13183 {
13184     \ior_if_eof:NTF #1
13185     { \prg_return_false: }
13186     {
13187         \__ior_str_get:NN #1 #2
13188         \prg_return_true:
13189     }
13190 }

```

(End definition for `\ior_str_get:NN`, `__ior_str_get:NN`, and `\ior_str_get:NNTF`. These functions are documented on page 158.)

`\c__ior_term_noprompt_ior` For reading without a prompt.

```

13191 \int_const:Nn \c__ior_term_noprompt_ior { -1 }

```

(End definition for `\c__ior_term_noprompt_ior`.)

`\ior_get_term:nN` Getting from the terminal is better with pretty-printing.

```

\ior_str_get_term:nN
\__ior_get_term:NnN
13192 \cs_new_protected:Npn \ior_get_term:nN #1#2
13193 { \__ior_get_term:NnN \__ior_get:NN {#1} #2 }
13194 \cs_new_protected:Npn \ior_str_get_term:nN #1#2
13195 { \__ior_get_term:NnN \__ior_str_get:NN {#1} #2 }
13196 \cs_new_protected:Npn \__ior_get_term:NnN #1#2#3
13197 {
13198   \group_begin:
13199     \tex_escapechar:D = -1 \scan_stop:
13200     \tl_if_blank:nTF {#2}
13201       { \exp_args:NNc #1 \c__ior_term_noprompt_ior }
13202       { \exp_args:NNc #1 \c__ior_term_ior }
13203       {#2}
13204     \exp_args:NNNv \group_end:
13205     \tl_set:Nn #3 {#2}
13206   }

```

(End definition for `\ior_get_term:nN`, `\ior_str_get_term:nN`, and `__ior_get_term:NnN`. These functions are documented on page 262.)

`\ior_map_break:` Usual map breaking functions.

```

\ior_map_break:n
13207 \cs_new:Npn \ior_map_break:
13208 { \prg_map_break:Nn \ior_map_break: { } }
13209 \cs_new:Npn \ior_map_break:n
13210 { \prg_map_break:Nn \ior_map_break: }

```

(End definition for `\ior_map_break:` and `\ior_map_break:n`. These functions are documented on page 159.)

`\ior_map_inline:Nn` Mapping to an input stream can be done on either a token or a string basis, hence the
`\ior_str_map_inline:Nn` set up. Within that, there is a check to avoid reading past the end of a file, hence the two
`__ior_map_inline:NnN` applications of `\ior_if_eof:N` and its lower-level analogue `\if_eof:w`. This mapping
`__ior_map_inline:NNNn` cannot be nested with twice the same stream, as the stream has only one “current line”.
`__ior_map_inline_loop:NNN`

```

13211 \cs_new_protected:Npn \ior_map_inline:Nn
13212 { \__ior_map_inline:NNn \__ior_get:NN }
13213 \cs_new_protected:Npn \ior_str_map_inline:Nn
13214 { \__ior_map_inline:NNn \__ior_str_get:NN }
13215 \cs_new_protected:Npn \__ior_map_inline:NNn
13216 {
13217   \int_gincr:N \g__kernel_prg_map_int
13218   \exp_args:Nc \__ior_map_inline:NNNn
13219     { \__ior_map_ \int_use:N \g__kernel_prg_map_int :n }
13220 }
13221 \cs_new_protected:Npn \__ior_map_inline:NNNn #1#2#3#4
13222 {
13223   \cs_gset_protected:Npn #1 ##1 {#4}
13224   \ior_if_eof:NF #3 { \__ior_map_inline_loop:NNN #1#2#3 }
13225   \prg_break_point:Nn \ior_map_break:
13226     { \int_gdecr:N \g__kernel_prg_map_int }
13227 }
13228 \cs_new_protected:Npn \__ior_map_inline_loop:NNN #1#2#3
13229 {
13230   #2 #3 \l__ior_internal_tl
13231   \if_eof:w #3

```

```

13232     \exp_after:wN \ior_map_break:
13233   \fi:
13234   \exp_args:No #1 \l__ior_internal_tl
13235   \__ior_map_inline_loop:NNN #1#2#3
13236 }

```

(End definition for `\ior_map_inline:Nn` and others. These functions are documented on page 159.)

```

\ior_map_variable:NNn
\ior_str_map_variable:NNn
\__ior_map_variable:NNNn
  \__ior_map_variable_loop:NNNn

```

Since the TeX primitive (`\read` or `\readline`) assigns the tokens read in the same way as a token list assignment, we simply call the appropriate primitive. The end-of-loop is checked using the primitive conditional for speed.

```

13237 \cs_new_protected:Npn \ior_map_variable:NNn
13238 { \__ior_map_variable:NNNn \ior_get:NN }
13239 \cs_new_protected:Npn \ior_str_map_variable:NNn
13240 { \__ior_map_variable:NNNn \ior_str_get:NN }
13241 \cs_new_protected:Npn \__ior_map_variable:NNNn #1#2#3#4
13242 {
13243   \ior_if_eof:NF #2 { \__ior_map_variable_loop:NNNn #1#2#3 {#4} }
13244   \prg_break_point:Nn \ior_map_break: { }
13245 }
13246 \cs_new_protected:Npn \__ior_map_variable_loop:NNNn #1#2#3#4
13247 {
13248   #1 #2 #3
13249   \if_eof:w #2
13250     \exp_after:wN \ior_map_break:
13251   \fi:
13252   #4
13253   \__ior_map_variable_loop:NNNn #1#2#3 {#4}
13254 }

```

(End definition for `\ior_map_variable:NNn` and others. These functions are documented on page 159.)

20.2 Output operations

```

13255 <@@=iow>

```

There is a lot of similarity here to the input operations, at least for many of the basics. Thus quite a bit is copied from the earlier material with minor alterations.

20.2.1 Variables and constants

`\c_log_iow` Here we allocate two output streams for writing to the transcript file only (`\c_log_iow`) and to both the terminal and transcript file (`\c_term_iow`). Recent LuaTeX provide 128 write streams; we also use `\c_term_iow` as the first non-allowed write stream so its value depends on the engine.

```

13256 \int_const:Nn \c_log_iow { -1 }
13257 \int_const:Nn \c_term_iow
13258 {
13259   \bool_lazy_and:nnTF
13260     { \sys_if_engine luatex_p: }
13261     { \int_compare_p:nNn \tex_luatexversion:D > { 80 } }
13262     { 128 }
13263     { 16 }
13264 }

```

(End definition for `\c_log_iow` and `\c_term_iow`. These variables are documented on page 163.)

`\g__iow_streams_seq` A list of the currently-available output streams to be used as a stack. The stream 18 is special, as `\write18` is used to denote commands to be sent to the OS.

```

13265 \seq_new:N \g__iow_streams_seq
13266 \*initex
13267 \exp_args:Nnx \use:n
13268 { \seq_gset_split:Nnn \g__iow_streams_seq { } }
13269 {
13270   \int_step_function:nnN { 0 } { \c_term_iow }
13271   \prg_do_nothing:
13272 }
13273 \int_compare:nNnF \c_term_iow < { 18 }
13274 { \seq_gremove_all:Nn \g__iow_streams_seq { 18 } }
13275 \*initex

```

(End definition for `\g__iow_streams_seq`.)

`\l__iow_stream_tl` Used to recover the raw stream number from the stack.

```

13276 \tl_new:N \l__iow_stream_tl

```

(End definition for `\l__iow_stream_tl`.)

`\g__iow_streams_prop` As for reads with the appropriate adjustment of the register numbers to check on.

```

13277 \prop_new:N \g__iow_streams_prop
13278 \*package
13279 \int_step_inline:nnn
13280 { 0 }
13281 {
13282   \cs_if_exist:NTF \normalend
13283   { \tex_count:D 39 ~ }
13284   {
13285     \tex_count:D 17 ~
13286     \cs_if_exist:NT \loccount { - 1 }
13287   }
13288 }
13289 {
13290   \prop_gput:Nnn \g__iow_streams_prop {#1} { Reserved-by~format }
13291 }
13292 \*package

```

(End definition for `\g__iow_streams_prop`.)

20.2.2 Internal auxiliaries

`\s__iow_mark` Internal scan marks.

```

13293 \scan_new:N \s__iow_mark

```

```

13294 \scan_new:N \s__iow_stop

```

(End definition for `\s__iow_mark` and `\s__iow_stop`.)

`__iow_use_i_delimit_by_s_stop:nw` Functions to gobble up to a scan mark.

```

13295 \cs_new:Npn \__iow_use_i_delimit_by_s_stop:nw #1 #2 \s__iow_stop {#1}

```

(End definition for `__iow_use_i_delimit_by_s_stop:nw`.)

`\q__iow_nil` Internal quarks.

```

13296 \quark_new:N \q__iow_nil

```

(End definition for `\q__iow_nil`.)

20.3 Stream management

\iow_new:N Reserving a new stream is done by defining the name as equal to writing to the terminal:
\iow_new:c odd but at least consistent.

```
13297 \cs_new_protected:Npn \iow_new:N #1 { \cs_new_eq:NN #1 \c_term_iow }
13298 \cs_generate_variant:Nn \iow_new:N { c }
```

(End definition for \iow_new:N. This function is documented on page 156.)

\g_tmpa_iow The usual scratch space.

\g_tmpb_iow

```
13299 \iow_new:N \g_tmpa_iow
13300 \iow_new:N \g_tmpb_iow
```

(End definition for \g_tmpa_iow and \g_tmpb_iow. These variables are documented on page 163.)

__iow_new:N As for read streams, copy \newwrite in package mode, making sure that it is not \outer.

```
13301 \*package>
13302 \exp_args:NNf \cs_new_protected:Npn \__iow_new:N
13303   { \exp_args:NNc \exp_after:wN \exp_stop_f: { newwrite } }
13304 \*package>
```

(End definition for __iow_new:N.)

\l__iow_file_name_tl Data storage.

```
13305 \tl_new:N \l__iow_file_name_tl
```

(End definition for \l__iow_file_name_tl.)

\iow_open:Nn The same idea as for reading, but without the path and without the need to allow for a
\iow_open:cn conditional version.

```
\__iow_open_stream:Nn 13306 \cs_new_protected:Npn \iow_open:Nn #1#2
\__iow_open_stream:NV 13307   {
13308     \tl_set:Nx \l__iow_file_name_tl
13309       { \__kernel_file_name_sanitiz:n {#2} }
13310     \iow_close:N #1
13311     \seq_gpop:NNTF \g__iow_streams_seq \l__iow_stream_tl
13312       { \__iow_open_stream:NV #1 \l__iow_file_name_tl }
13313     \*initex>
13314     { \__kernel_msg_fatal:nn { kernel } { output-streams-exhausted } }
13315   \*initex>
13316   \*package>
13317   {
13318     \__iow_new:N #1
13319     \tl_set:Nx \l__iow_stream_tl { \int_eval:n {#1} }
13320     \__iow_open_stream:NV #1 \l__iow_file_name_tl
13321   }
13322 \*package>
13323 }
13324 \cs_generate_variant:Nn \iow_open:Nn { c }
13325 \cs_new_protected:Npn \__iow_open_stream:Nn #1#2
13326   {
13327     \tex_global:D \tex_chardef:D #1 = \l__iow_stream_tl \scan_stop:
13328     \prop_gput:Nvn \g__iow_streams_prop #1 {#2}
13329     \tex_immediate:D \tex_openout:D
13330       #1 \__kernel_file_name_quote:n {#2} \scan_stop:
```

```

13331 }
13332 \cs_generate_variant:Nn \__iow_open_stream:Nn { NV }

```

(End definition for `\iow_open:Nn` and `__iow_open_stream:Nn`. This function is documented on page 157.)

`\iow_close:N` Closing a stream is not quite the reverse of opening one. First, the close operation is easier than the open one, and second as the stream is actually a number we can use it directly to show that the slot has been freed up.

`\iow_close:c`

```

13333 \cs_new_protected:Npn \iow_close:N #1
13334 {
13335   \int_compare:nT { - \c_log_iow < #1 < \c_term_iow }
13336   {
13337     \tex_immediate:D \tex_closeout:D #1
13338     \prop_gremove:NV \g__iow_streams_prop #1
13339     \seq_if_in:NVF \g__iow_streams_seq #1
13340     { \seq_gpush:NV \g__iow_streams_seq #1 }
13341     \cs_gset_eq:NN #1 \c_term_iow
13342   }
13343 }
13344 \cs_generate_variant:Nn \iow_close:N { c }

```

(End definition for `\iow_close:N`. This function is documented on page 157.)

`\iow_show_list:` Done as for input, but with a copy of the auxiliary so the name is correct.

`\iow_log_list:`

`__iow_list:N`

```

13345 \cs_new_protected:Npn \iow_show_list: { \__iow_list:N \msg_show:nnxxxx }
13346 \cs_new_protected:Npn \iow_log_list: { \__iow_list:N \msg_log:nnxxxx }
13347 \cs_new_protected:Npn \__iow_list:N #1
13348 {
13349   #1 { LaTeX / kernel } { show-streams }
13350   { iow }
13351   {
13352     \prop_map_function:NN \g__iow_streams_prop
13353     \msg_show_item_unbraced:nn
13354   }
13355   { } { }
13356 }

```

(End definition for `\iow_show_list:`, `\iow_log_list:`, and `__iow_list:N`. These functions are documented on page 157.)

20.3.1 Deferred writing

`\iow_shipout_x:Nn` First the easy part, this is the primitive, which expects its argument to be braced.

`\iow_shipout_x:Nx`

`\iow_shipout_x:cn`

`\iow_shipout_x:cx`

```

13357 \cs_new_protected:Npn \iow_shipout_x:Nn #1#2
13358 { \tex_write:D #1 {#2} }
13359 \cs_generate_variant:Nn \iow_shipout_x:Nn { c, Nx, cx }

```

(End definition for `\iow_shipout_x:Nn`. This function is documented on page 161.)

`\iow_shipout:Nn` With ε -TEX available deferred writing without expansion is easy.

`\iow_shipout:Nx`

`\iow_shipout:cn`

`\iow_shipout:cx`

```

13360 \cs_new_protected:Npn \iow_shipout:Nn #1#2
13361 { \tex_write:D #1 { \exp_not:n {#2} } }
13362 \cs_generate_variant:Nn \iow_shipout:Nn { c, Nx, cx }

```

(End definition for `\iow_shipout:Nn`. This function is documented on page 161.)

20.3.2 Immediate writing

`__kernel_iow_with:Nnn` If the integer #1 is equal to #2, just leave #3 in the input stream. Otherwise, pass the old value to an auxiliary, which sets the integer to the new value, runs the code, and restores the integer.

```

13363 \cs_new_protected:Npn \__kernel_iow_with:Nnn #1#2
13364 {
13365   \int_compare:nNnTF {#1} = {#2}
13366     { \use:n }
13367     { \exp_args:No \__iow_with:nNnn { \int_use:N #1 } #1 {#2} }
13368 }
13369 \cs_new_protected:Npn \__iow_with:nNnn #1#2#3#4
13370 {
13371   \int_set:Nn #2 {#3}
13372   #4
13373   \int_set:Nn #2 {#1}
13374 }
```

(End definition for `__kernel_iow_with:Nnn` and `__iow_with:nNnn`.)

`\iow_now:Nn` This routine writes the second argument onto the output stream without expansion. If this stream isn't open, the output goes to the terminal instead. If the first argument is no output stream at all, we get an internal error. We don't use the expansion done by `\write` to get the `Nx` variant, because it differs in subtle ways from `x`-expansion, namely, macro parameter characters would not need to be doubled. We set the `\newlinechar` to 10 using `__kernel_iow_with:Nnn` to support formats such as plain `TEX`: otherwise, `\iow_newline:` would not work. We do not do this for `\iow_shipout:Nn` or `\iow_shipout_x:Nn`, as `TEX` looks at the value of the `\newlinechar` at shipout time in those cases.

```

13375 \cs_new_protected:Npn \iow_now:Nn #1#2
13376 {
13377   \__kernel_iow_with:Nnn \tex_newlinechar:D { '\^^J }
13378   { \tex_immediate:D \tex_write:D #1 { \exp_not:n {#2} } }
13379 }
13380 \cs_generate_variant:Nn \iow_now:Nn { c, Nx, cx }
```

(End definition for `\iow_now:Nn`. This function is documented on page 160.)

`\iow_log:n` Writing to the log and the terminal directly are relatively easy.

`\iow_log:x` `\iow_term:n` `\iow_term:x`

```

13381 \cs_set_protected:Npn \iow_log:x { \iow_now:Nx \c_log_iow }
13382 \cs_new_protected:Npn \iow_log:n { \iow_now:Nn \c_log_iow }
13383 \cs_set_protected:Npn \iow_term:x { \iow_now:Nx \c_term_iow }
13384 \cs_new_protected:Npn \iow_term:n { \iow_now:Nn \c_term_iow }
```

(End definition for `\iow_log:n` and `\iow_term:n`. These functions are documented on page 160.)

20.3.3 Special characters for writing

`\iow_newline:` Global variable holding the character that forces a new line when something is written to an output stream.

```

13385 \cs_new:Npn \iow_newline: { ^^J }
```

(End definition for `\iow_newline:`. This function is documented on page 161.)

\iow_char:N Function to write any escaped char to an output stream.

```
13386 \cs_new_eq:NN \iow_char:N \cs_to_str:N
```

(End definition for \iow_char:N. This function is documented on page 161.)

20.3.4 Hard-wrapping lines to a character count

The code here implements a generic hard-wrapping function. This is used by the messaging system, but is designed such that it is available for other uses.

\l_iow_line_count_int This is the “raw” number of characters in a line which can be written to the terminal. The standard value is the line length typically used by T_EXLive and MiK_TE_X.

```
13387 \int_new:N \l_iow_line_count_int
13388 \int_set:Nn \l_iow_line_count_int { 78 }
```

(End definition for \l_iow_line_count_int. This variable is documented on page 162.)

\l__iow_newline_tl The token list inserted to produce a new line, with the *<run-on text>*.

```
13389 \tl_new:N \l__iow_newline_tl
```

(End definition for \l__iow_newline_tl.)

\l__iow_line_target_int This stores the target line count: the full number of characters in a line, minus any part for a leader at the start of each line.

```
13390 \int_new:N \l__iow_line_target_int
```

(End definition for \l__iow_line_target_int.)

__iow_set_indent:n The **one_indent** variables hold one indentation marker and its length. The **__iow_unindent:w** auxiliary removes one indentation. The function **__iow_set_indent:n** (that could possibly be public) sets the indentation in a consistent way. We set it to four spaces by default.

```
13391 \tl_new:N \l__iow_one_indent_tl
13392 \int_new:N \l__iow_one_indent_int
13393 \cs_new:Npn \__iow_unindent:w { }
13394 \cs_new_protected:Npn \__iow_set_indent:n #1
13395 {
13396   \tl_set:Nx \l__iow_one_indent_tl
13397   { \exp_args:No \__kernel_str_to_other_fast:n { \tl_to_str:n {#1} } }
13398   \int_set:Nn \l__iow_one_indent_int
13399   { \str_count:N \l__iow_one_indent_tl }
13400   \exp_last_unbraced:NNo
13401   \cs_set:Npn \__iow_unindent:w \l__iow_one_indent_tl { }
13402 }
13403 \exp_args:Nx \__iow_set_indent:n { \prg_replicate:nn { 4 } { ~ } }
```

(End definition for __iow_set_indent:n and others.)

\l__iow_indent_tl The current indentation (some copies of **\l__iow_one_indent_tl**) and its number of characters.

```
13404 \tl_new:N \l__iow_indent_tl
13405 \int_new:N \l__iow_indent_int
```

(End definition for \l__iow_indent_tl and \l__iow_indent_int.)

`\l__iow_line_tl` These hold the current line of text and a partial line to be added to it, respectively.

`\l__iow_line_part_tl`

```

13406 \tl_new:N \l__iow_line_tl
13407 \tl_new:N \l__iow_line_part_tl

```

(End definition for `\l__iow_line_tl` and `\l__iow_line_part_tl`.)

`\l__iow_line_break_bool` Indicates whether the line was broken precisely at a chunk boundary.

```

13408 \bool_new:N \l__iow_line_break_bool

```

(End definition for `\l__iow_line_break_bool`.)

`\l__iow_wrap_tl` Used for the expansion step before detokenizing, and for the output from wrapping text: fully expanded and with lines which are not overly long.

```

13409 \tl_new:N \l__iow_wrap_tl

```

(End definition for `\l__iow_wrap_tl`.)

`\c__iow_wrap_marker_tl` Every special action of the wrapping code is starts with the same recognizable string,

`\c__iow_wrap_end_marker_tl` `\c__iow_wrap_marker_tl`. Upon seeing that “word”, the wrapping code reads one space-

`\c__iow_wrap_newline_marker_tl` delimited argument to know what operation to perform. The setting of `\escapechar` here

`\c__iow_wrap_allow_break_marker_tl` is not very important, but makes `\c__iow_wrap_marker_tl` look marginally nicer.

`\c__iow_wrap_indent_marker_tl`

`\c__iow_wrap_unindent_marker_tl`

```

13410 \group_begin:
13411   \int_set:Nn \tex_escapechar:D { -1 }
13412   \tl_const:Nx \c__iow_wrap_marker_tl
13413     { \tl_to_str:n { \^^I \^^O \^^W \^^_ \^^W \^^R \^^A \^^P } }
13414 \group_end:
13415 \tl_map_inline:nn
13416   { { end } { newline } { allow_break } { indent } { unindent } }
13417   {
13418     \tl_const:cx { c__iow_wrap_ #1 _marker_tl }
13419     {
13420       \c__iow_wrap_marker_tl
13421       #1
13422       \c_catcode_other_space_tl
13423     }
13424   }

```

(End definition for `\c__iow_wrap_marker_tl` and others.)

`\iow_allow_break:` We set `\iow_allow_break:n` to produce an error when outside messages. Within

`__iow_allow_break:` wrapped message, it is set to `__iow_allow_break:` when valid and otherwise to `__-`

`__iow_allow_break_error:` `iow_allow_break_error:`. The second produces an error expandably.

```

13425 \cs_new_protected:Npn \iow_allow_break:
13426   {
13427     \__kernel_msg_error:nnnn { kernel } { iow-indent }
13428     { \iow_wrap:nnnN } { \iow_allow_break: }
13429   }
13430 \cs_new:Npx \__iow_allow_break: { \c__iow_wrap_allow_break_marker_tl }
13431 \cs_new:Npn \__iow_allow_break_error:
13432   {
13433     \__kernel_msg_expandable_error:nnnn { kernel } { iow-indent }
13434     { \iow_wrap:nnnN } { \iow_allow_break: }
13435   }

```

(End definition for `\iow_allow_break:`, `__iow_allow_break:`, and `__iow_allow_break_error:`. This function is documented on page 261.)

`\iow_indent:n` We set `\iow_indent:n` to produce an error when outside messages. Within wrapped message, it is set to `__iow_indent:n` when valid and otherwise to `__iow_indent_error:n`.
`__iow_indent:n` The first places the instruction for increasing the indentation before its argument, and
`__iow_indent_error:n` the instruction for unindenting afterwards. The second produces an error expandably. Note that there are no forced line-break, so the indentation only changes when the next line is started.

```

13436 \cs_new_protected:Npn \iow_indent:n #1
13437 {
13438   \__kernel_msg_error:nnnnn { kernel } { iow-indent }
13439   { \iow_wrap:nnnN } { \iow_indent:n } {#1}
13440   #1
13441 }
13442 \cs_new:Npx \__iow_indent:n #1
13443 {
13444   \c__iow_wrap_indent_marker_tl
13445   #1
13446   \c__iow_wrap_unindent_marker_tl
13447 }
13448 \cs_new:Npn \__iow_indent_error:n #1
13449 {
13450   \__kernel_msg_expandable_error:nnnnn { kernel } { iow-indent }
13451   { \iow_wrap:nnnN } { \iow_indent:n } {#1}
13452   #1
13453 }
```

(End definition for `\iow_indent:n`, `__iow_indent:n`, and `__iow_indent_error:n`. This function is documented on page 162.)

`\iow_wrap:nnnN` The main wrapping function works as follows. First give `\`, `_` and other formatting commands the correct definition for messages and perform the given setup #3.
`\iow_wrap:nxnN` The definition of `_` uses an “other” space rather than a normal space, because the latter might be absorbed by \TeX to end a number or other f-type expansions. Use `\conditionally@traceoff` if defined; it is introduced by the `trace` package and suppresses uninteresting tracing of the wrapping code.

```

13454 \cs_new_protected:Npn \iow_wrap:nnnN #1#2#3#4
13455 {
13456   \group_begin:
13457   (package) \cs_if_exist_use:N \conditionally@traceoff
13458   \int_set:Nn \tex_escapechar:D { -1 }
13459   \cs_set:Npx \{ { \token_to_str:N \{ }
13460   \cs_set:Npx \# { \token_to_str:N \# }
13461   \cs_set:Npx \} { \token_to_str:N \} }
13462   \cs_set:Npx \% { \token_to_str:N \% }
13463   \cs_set:Npx \~ { \token_to_str:N \~ }
13464   \int_set:Nn \tex_escapechar:D { 92 }
13465   \cs_set_eq:NN \ \ \iow_newline:
13466   \cs_set_eq:NN \ \_ \c_catcode_other_space_tl
13467   \cs_set_eq:NN \iow_allow_break: \__iow_allow_break:
13468   \cs_set_eq:NN \iow_indent:n \__iow_indent:n
13469   #3
```

Then fully-expand the input: in package mode, the expansion uses L^AT_EX 2_ε’s `\protect` mechanism in the same way as `\typeout`. In generic mode this setting is useless but harmless. As soon as the expansion is done, reset `\iow_indent:n` to its error definition: it only works in the first argument of `\iow_wrap:nnnN`.

```

13470 (package)      \cs_set_eq:NN \protect \token_to_str:N
13471      \tl_set:Nx \l__iow_wrap_tl {#1}
13472      \cs_set_eq:NN \iow_allow_break: \__iow_allow_break_error:
13473      \cs_set_eq:NN \iow_indent:n \__iow_indent_error:n

```

Afterwards, set the newline marker (two assignments to fully expand, then convert to a string) and initialize the target count for lines (the first line has target count `\l_iow_line_count_int` instead).

```

13474      \tl_set:Nx \l__iow_newline_tl { \iow_newline: #2 }
13475      \tl_set:Nx \l__iow_newline_tl { \tl_to_str:N \l__iow_newline_tl }
13476      \int_set:Nn \l__iow_line_target_int
13477      { \l_iow_line_count_int - \str_count:N \l__iow_newline_tl + 1 }

```

Sanity check.

```

13478      \int_compare:nNnT { \l__iow_line_target_int } < 0
13479      {
13480          \tl_set:Nn \l__iow_newline_tl { \iow_newline: }
13481          \int_set:Nn \l__iow_line_target_int
13482          { \l_iow_line_count_int + 1 }
13483      }

```

There is then a loop over the input, which stores the wrapped result in `\l__iow_wrap_tl`. After the loop, the resulting text is passed on to the function which has been given as a post-processor. The `\tl_to_str:N` step converts the “other” spaces back to normal spaces. The f-expansion removes a leading space from `\l__iow_wrap_tl`.

```

13484      \__iow_wrap_do:
13485      \exp_args:NNf \group_end:
13486      #4 { \tl_to_str:N \l__iow_wrap_tl }
13487      }
13488      \cs_generate_variant:Nn \iow_wrap:nnnN { nx }

```

(End definition for `\iow_wrap:nnnN`. This function is documented on page 162.)

<pre> __iow_wrap_do: __iow_wrap_fix_newline:w __iow_wrap_start:w </pre>	<p>Escape spaces and change newlines to <code>\c__iow_wrap_newline_marker_tl</code>. Set up a few variables, in particular the initial value of <code>\l__iow_wrap_tl</code>: the space stops the f-expansion of the main wrapping function and <code>\use_none:n</code> removes a newline marker inserted by later code. The main loop consists of repeatedly calling the <code>chunk</code> auxiliary to wrap chunks delimited by (newline or indentation) markers.</p>
--	---

```

13489      \cs_new_protected:Npn \__iow_wrap_do:
13490      {
13491          \tl_set:Nx \l__iow_wrap_tl
13492          {
13493              \exp_args:No \__kernel_str_to_other_fast:n \l__iow_wrap_tl
13494              \c__iow_wrap_end_marker_tl
13495          }
13496          \tl_set:Nx \l__iow_wrap_tl
13497          {
13498              \exp_after:wN \__iow_wrap_fix_newline:w \l__iow_wrap_tl
13499              ^^J \q_iow_nil ^^J \s__iow_stop
13500          }

```

```

13501 \exp_after:wN \__iow_wrap_start:w \l__iow_wrap_tl
13502 }
13503 \cs_new:Npn \__iow_wrap_fix_newline:w #1 ^^J #2 ^^J
13504 {
13505     #1
13506     \if_meaning:w \q__iow_nil #2
13507     \__iow_use_i_delimit_by_s_stop:nw
13508     \fi:
13509     \c__iow_wrap_newline_marker_tl
13510     \__iow_wrap_fix_newline:w #2 ^^J
13511 }
13512 \cs_new_protected:Npn \__iow_wrap_start:w
13513 {
13514     \bool_set_false:N \l__iow_line_break_bool
13515     \tl_clear:N \l__iow_line_tl
13516     \tl_clear:N \l__iow_line_part_tl
13517     \tl_set:Nn \l__iow_wrap_tl { ~ \use_none:n }
13518     \int_zero:N \l__iow_indent_int
13519     \tl_clear:N \l__iow_indent_tl
13520     \__iow_wrap_chunk:nw { \l__iow_line_count_int }
13521 }

```

(End definition for __iow_wrap_do:, __iow_wrap_fix_newline:w, and __iow_wrap_start:w.)

__iow_wrap_chunk:nw The **chunk** and **next** auxiliaries are defined indirectly to obtain the expansions of \c_catcode_other_space_tl and \c__iow_wrap_marker_tl in their definition. The **next** auxiliary calls a function corresponding to the type of marker (its ##2), which can be **newline** or **indent** or **unindent** or **end**. The first argument of the **chunk** auxiliary is a target number of characters and the second is some string to wrap. If the chunk is empty simply call **next**. Otherwise, set up a call to __iow_wrap_line:nw, including the indentation if the current line is empty, and including a trailing space (#1) before the __iow_wrap_end_chunk:w auxiliary.

```

13522 \cs_set_protected:Npn \__iow_tmp:w #1#2
13523 {
13524     \cs_new_protected:Npn \__iow_wrap_chunk:nw ##1##2 #2
13525     {
13526         \tl_if_empty:NTF {##2}
13527         {
13528             \tl_clear:N \l__iow_line_part_tl
13529             \__iow_wrap_next:nw {##1}
13530         }
13531         {
13532             \tl_if_empty:NTF \l__iow_line_tl
13533             {
13534                 \__iow_wrap_line:nw
13535                 { \l__iow_indent_tl }
13536                 ##1 - \l__iow_indent_int ;
13537             }
13538             { \__iow_wrap_line:nw { } ##1 ; }
13539             ##2 #1
13540             \__iow_wrap_end_chunk:w 7 6 5 4 3 2 1 0 \s__iow_stop
13541         }
13542     }
13543     \cs_new_protected:Npn \__iow_wrap_next:nw ##1##2 #1

```

```

13544     { \use:c { __iow_wrap_##2:n } {##1} }
13545   }
13546 \exp_args:NVV \__iow_tmp:w \c_catcode_other_space_tl \c__iow_wrap_marker_tl

```

(End definition for __iow_wrap_chunk:nw and __iow_wrap_next:nw.)

```

\__iow_wrap_line:nw
\__iow_wrap_line_loop:w
\__iow_wrap_line_aux:Nw
\__iow_wrap_line_seven:nnnnnnn
\__iow_wrap_line_end:NnnnnnnnN
\__iow_wrap_line_end:nw
\__iow_wrap_end_chunk:w

```

This is followed by $\{\langle string \rangle\} \langle intexpr \rangle$; . It stores the $\langle string \rangle$ and up to $\langle intexpr \rangle$ characters from the current chunk into $\backslash l_iow_line_part_tl$. Characters are grabbed 8 at a time and left in $\backslash l_iow_line_part_tl$ by the `line_loop` auxiliary. When $k < 8$ remain to be found, the `line_aux` auxiliary calls the `line_end` auxiliary followed by (the single digit) k , then $7 - k$ empty brace groups, then the chunk's remaining characters. The `line_end` auxiliary leaves k characters from the chunk in the line part, then ends the assignment. Ignore the `\use_none:nnnnn` line for now. If the next character is a space the line can be broken there: store what we found into the result and get the next line. Otherwise some work is needed to find a break-point. So far we have ignored what happens if the chunk is shorter than the requested number of characters: this is dealt with by the `end_chunk` auxiliary, which gets treated like a character by the rest of the code. It ends up being called either as one of the arguments #2-#9 of the `line_loop` auxiliary or as one of the arguments #2-#8 of the `line_end` auxiliary. In both cases stop the assignment and work out how many characters are still needed. Notice that when we have exactly seven arguments to clean up, a `\exp_stop_f:` has to be inserted to stop the `\exp:w`. The weird `\use_none:nnnnn` ensures that the required data is in the right place.

```

13547 \cs_new_protected:Npn \__iow_wrap_line:nw #1
13548 {
13549   \tex_edef:D \l__iow_line_part_tl { \if_false: } \fi:
13550   #1
13551   \exp_after:wN \__iow_wrap_line_loop:w
13552   \int_value:w \int_eval:w
13553 }
13554 \cs_new:Npn \__iow_wrap_line_loop:w #1 ; #2#3#4#5#6#7#8#9
13555 {
13556   \if_int_compare:w #1 < 8 \exp_stop_f:
13557   \__iow_wrap_line_aux:Nw #1
13558   \fi:
13559   #2 #3 #4 #5 #6 #7 #8 #9
13560   \exp_after:wN \__iow_wrap_line_loop:w
13561   \int_value:w \int_eval:w #1 - 8 ;
13562 }
13563 \cs_new:Npn \__iow_wrap_line_aux:Nw #1#2#3 \exp_after:wN #4 ;
13564 {
13565   #2
13566   \exp_after:wN \__iow_wrap_line_end:NnnnnnnnN
13567   \exp_after:wN #1
13568   \exp:w \exp_end_continue_f:w
13569   \exp_after:wN \exp_after:wN
13570   \if_case:w #1 \exp_stop_f:
13571     \prg_do_nothing:
13572   \or: \use_none:n
13573   \or: \use_none:nn
13574   \or: \use_none:nnn
13575   \or: \use_none:nnnn
13576   \or: \use_none:nnnnn

```

```

13577 \or: \use_none:nnnnnn
13578 \or: \__iow_wrap_line_seven:nnnnnnn
13579 \fi:
13580 { } { } { } { } { } { } { } { } { } #3
13581 }
13582 \cs_new:Npn \__iow_wrap_line_seven:nnnnnnn #1#2#3#4#5#6#7 { \exp_stop_f: }
13583 \cs_new:Npn \__iow_wrap_line_end:NnnnnnnnN #1#2#3#4#5#6#7#8#9
13584 {
13585     #2 #3 #4 #5 #6 #7 #8
13586     \use_none:nnnnn \int_eval:w 8 - ; #9
13587     \token_if_eq_charcode:NNTF \c_space_token #9
13588     { \__iow_wrap_line_end:nw { } }
13589     { \if_false: { \fi: } \__iow_wrap_break:w #9 }
13590 }
13591 \cs_new:Npn \__iow_wrap_line_end:nw #1
13592 {
13593     \if_false: { \fi: }
13594     \__iow_wrap_store_do:n {#1}
13595     \__iow_wrap_next_line:w
13596 }
13597 \cs_new:Npn \__iow_wrap_end_chunk:w
13598 #1 \int_eval:w #2 - #3 ; #4#5 \s__iow_stop
13599 {
13600     \if_false: { \fi: }
13601     \exp_args:Nf \__iow_wrap_next:nw { \int_eval:n { #2 - #4 } }
13602 }

```

(End definition for __iow_wrap_line:nw and others.)

<pre> __iow_wrap_break:w __iow_wrap_break_first:w __iow_wrap_break_none:w __iow_wrap_break_loop:w __iow_wrap_break_end:w </pre>	<p>Functions here are defined indirectly: __iow_tmp:w is eventually called with an “other” space as its argument. The goal is to remove from \l__iow_line_part_tl the part after the last space. In most cases this is done by repeatedly calling the <code>break_loop</code> auxiliary, which leaves “words” (delimited by spaces) until it hits the trailing space: then its argument <code>##3</code> is ? __iow_wrap_break_end:w instead of a single token, and that <code>break_end</code> auxiliary leaves in the assignment the line until the last space, then calls __iow_wrap_line_end:nw to finish up the line and move on to the next. If there is no space in \l__iow_line_part_tl then the <code>break_first</code> auxiliary calls the <code>break_none</code> auxiliary. In that case, if the current line is empty, the complete word (including <code>##4</code>, characters beyond what we had grabbed) is added to the line, making it over-long. Otherwise, the word is used for the following line (and the last space of the line so far is removed because it was inserted due to the presence of a marker).</p>
--	---

```

13603 \cs_set_protected:Npn \__iow_tmp:w #1
13604 {
13605     \cs_new:Npn \__iow_wrap_break:w
13606     {
13607         \tex_edef:D \l__iow_line_part_tl
13608         { \if_false: } \fi:
13609         \exp_after:wN \__iow_wrap_break_first:w
13610         \l__iow_line_part_tl
13611         #1
13612         { ? \__iow_wrap_break_end:w }
13613         \s__iow_mark
13614     }

```

```

13615 \cs_new:Npn \__iow_wrap_break_first:w ##1 #1 ##2
13616 {
13617   \use_none:nn ##2 \__iow_wrap_break_none:w
13618   \__iow_wrap_break_loop:w ##1 #1 ##2
13619 }
13620 \cs_new:Npn \__iow_wrap_break_none:w ##1##2 #1 ##3 \s__iow_mark ##4 #1
13621 {
13622   \tl_if_empty:NTF \l__iow_line_tl
13623   { ##2 ##4 \__iow_wrap_line_end:nw { } }
13624   { \__iow_wrap_line_end:nw { \__iow_wrap_trim:N } ##2 ##4 #1 }
13625 }
13626 \cs_new:Npn \__iow_wrap_break_loop:w ##1 #1 ##2 #1 ##3
13627 {
13628   \use_none:n ##3
13629   ##1 #1
13630   \__iow_wrap_break_loop:w ##2 #1 ##3
13631 }
13632 \cs_new:Npn \__iow_wrap_break_end:w ##1 #1 ##2 ##3 #1 ##4 \s__iow_mark
13633 { ##1 \__iow_wrap_line_end:nw { } ##3 }
13634 }
13635 \exp_args:NV \__iow_tmp:w \c_catcode_other_space_tl

```

(End definition for __iow_wrap_break:w and others.)

__iow_wrap_next_line:w The special case where the end of a line coincides with the end of a chunk is detected here, to avoid a spurious empty line. Otherwise, call __iow_wrap_line:nw to find characters for the next line (remembering to account for the indentation).

```

13636 \cs_new_protected:Npn \__iow_wrap_next_line:w #1#2 \s__iow_stop
13637 {
13638   \tl_clear:N \l__iow_line_tl
13639   \token_if_eq_meaning:NNTF #1 \__iow_wrap_end_chunk:w
13640   {
13641     \tl_clear:N \l__iow_line_part_tl
13642     \bool_set_true:N \l__iow_line_break_bool
13643     \__iow_wrap_next:nw { \l__iow_line_target_int }
13644   }
13645   {
13646     \__iow_wrap_line:nw
13647     { \l__iow_indent_tl }
13648     \l__iow_line_target_int - \l__iow_indent_int ;
13649     #1 #2 \s__iow_stop
13650   }
13651 }

```

(End definition for __iow_wrap_next_line:w.)

__iow_wrap_allow_break:n This is called after a chunk has been wrapped. The \l__iow_line_part_tl typically ends with a space (except at the beginning of a line?), which we remove since the **allow-break** marker should not insert a space. Then move on with the next chunk, making sure to adjust the target number of characters for the line in case we did remove a space.

```

13652 \cs_new_protected:Npn \__iow_wrap_allow_break:n #1
13653 {
13654   \tl_set:Nx \l__iow_line_tl
13655   { \l__iow_line_tl \__iow_wrap_trim:N \l__iow_line_part_tl }

```



```

13656     \bool_set_false:N \l__iow_line_break_bool
13657     \tl_if_empty:NTF \l__iow_line_part_tl
13658       { \__iow_wrap_chunk:nw {#1} }
13659       { \exp_args:Nf \__iow_wrap_chunk:nw { \int_eval:n { #1 + 1 } } }
13660   }

```

(End definition for __iow_wrap_allow_break:n.)

__iow_wrap_indent:n These functions are called after a chunk has been wrapped, when encountering indent/unindent markers. Add the line part (last line part of the previous chunk) to the line so far and reset a boolean denoting the presence of a line-break. Most importantly, add or remove one indent from the current indent (both the integer and the token list). Finally, continue wrapping.

```

13661 \cs_new_protected:Npn \__iow_wrap_indent:n #1
13662 {
13663     \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
13664     \bool_set_false:N \l__iow_line_break_bool
13665     \int_add:Nn \l__iow_indent_int { \l__iow_one_indent_int }
13666     \tl_put_right:No \l__iow_indent_tl { \l__iow_one_indent_tl }
13667     \__iow_wrap_chunk:nw {#1}
13668 }
13669 \cs_new_protected:Npn \__iow_wrap_unindent:n #1
13670 {
13671     \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
13672     \bool_set_false:N \l__iow_line_break_bool
13673     \int_sub:Nn \l__iow_indent_int { \l__iow_one_indent_int }
13674     \tl_set:Nx \l__iow_indent_tl
13675       { \exp_after:wN \__iow_unindent:w \l__iow_indent_tl }
13676     \__iow_wrap_chunk:nw {#1}
13677 }

```

(End definition for __iow_wrap_indent:n and __iow_wrap_unindent:n.)

__iow_wrap_newline:n These functions are called after a chunk has been line-wrapped, when encountering a newline/end marker. Unless we just took a line-break, store the line part and the line so far into the whole \l__iow_wrap_tl, trimming a trailing space. In the newline case look for a new line (of length \l__iow_line_target_int) in a new chunk.

```

13678 \cs_new_protected:Npn \__iow_wrap_newline:n #1
13679 {
13680     \bool_if:NF \l__iow_line_break_bool
13681       { \__iow_wrap_store_do:n { \__iow_wrap_trim:N } }
13682     \bool_set_false:N \l__iow_line_break_bool
13683     \__iow_wrap_chunk:nw { \l__iow_line_target_int }
13684 }
13685 \cs_new_protected:Npn \__iow_wrap_end:n #1
13686 {
13687     \bool_if:NF \l__iow_line_break_bool
13688       { \__iow_wrap_store_do:n { \__iow_wrap_trim:N } }
13689     \bool_set_false:N \l__iow_line_break_bool
13690 }

```

(End definition for __iow_wrap_newline:n and __iow_wrap_end:n.)

`__iow_wrap_store_do:n` First add the last line part to the line, then append it to `\l__iow_wrap_tl` with the appropriate new line (with “run-on” text), possibly with its last space removed (`#1` is empty or `__iow_wrap_trim:N`).

```

13691 \cs_new_protected:Npn \__iow_wrap_store_do:n #1
13692 {
13693   \tl_set:Nx \l__iow_line_tl
13694     { \l__iow_line_tl \l__iow_line_part_tl }
13695   \tl_set:Nx \l__iow_wrap_tl
13696     {
13697       \l__iow_wrap_tl
13698       \l__iow_newline_tl
13699       #1 \l__iow_line_tl
13700     }
13701   \tl_clear:N \l__iow_line_tl
13702 }

```

(End definition for `__iow_wrap_store_do:n`.)

`__iow_wrap_trim:N` Remove one trailing “other” space from the argument if present.
`__iow_wrap_trim:w`
`__iow_wrap_trim_aux:w`

```

13703 \cs_set_protected:Npn \__iow_tmp:w #1
13704 {
13705   \cs_new:Npn \__iow_wrap_trim:N ##1
13706     { \exp_after:wN \__iow_wrap_trim:w ##1 \s__iow_mark #1 \s__iow_mark \s__iow_stop }
13707   \cs_new:Npn \__iow_wrap_trim:w ##1 #1 \s__iow_mark
13708     { \__iow_wrap_trim_aux:w ##1 \s__iow_mark }
13709   \cs_new:Npn \__iow_wrap_trim_aux:w ##1 \s__iow_mark ##2 \s__iow_stop {##1}
13710 }
13711 \exp_args:NV \__iow_tmp:w \c_catcode_other_space_tl

```

(End definition for `__iow_wrap_trim:N`, `__iow_wrap_trim:w`, and `__iow_wrap_trim_aux:w`.)

13712 `<@@=file>`

20.4 File operations

`\l__file_internal_tl` Used as a short-term scratch variable.

```

13713 \tl_new:N \l__file_internal_tl

```

(End definition for `\l__file_internal_tl`.)

`\g_file_curr_dir_str` The name of the current file should be available at all times: the name itself is set dynamically.
`\g_file_curr_ext_str`
`\g_file_curr_name_str`

```

13714 \str_new:N \g_file_curr_dir_str
13715 \str_new:N \g_file_curr_ext_str
13716 \str_new:N \g_file_curr_name_str

```

(End definition for `\g_file_curr_dir_str`, `\g_file_curr_ext_str`, and `\g_file_curr_name_str`. These variables are documented on page 163.)

`\g__file_stack_seq` The input list of files is stored as a sequence stack. In package mode we can recover the information from the details held by $\text{\LaTeX 2}_{\epsilon}$ (we must be in the preamble and loaded using `\usepackage` or `\RequirePackage`). As $\text{\LaTeX 2}_{\epsilon}$ doesn’t store directory and name separately, we stick to the same convention here. In pre-loading, `\@currnamestack` is empty so is skipped.

```

13717 \seq_new:N \g__file_stack_seq
13718 \<{*package}
13719 \group_begin:
13720   \cs_set_protected:Npn \__file_tmp:w #1#2#3
13721   {
13722     \tl_if_blank:nTF {#1}
13723     {
13724       \cs_set:Npn \__file_tmp:w ##1 " ##2 " ##3 \s__file_stop
13725       { { } {##2} { } }
13726       \seq_gput_right:Nx \g__file_stack_seq
13727       {
13728         \exp_after:wN \__file_tmp:w \tex_jobname:D
13729         " \tex_jobname:D " \s__file_stop
13730       }
13731     }
13732     {
13733       \seq_gput_right:Nn \g__file_stack_seq { { } {#1} {#2} }
13734       \__file_tmp:w
13735     }
13736   }
13737   \cs_if_exist:NT \@currnamestack
13738   {
13739     \tl_if_empty:NF \@currnamestack
13740     { \exp_after:wN \__file_tmp:w \@currnamestack }
13741   }
13742 \group_end:
13743 \</package>

```

(End definition for \g__file_stack_seq.)

\g__file_record_seq The total list of files used is recorded separately from the current file stack, as nothing is ever popped from this list. The current file name should be included in the file list! In format mode, this is done at the very start of the T_EX run. In package mode we will eventually copy the contents of \@filelist.

```

13744 \seq_new:N \g__file_record_seq
13745 \<{*initex}
13746 \tex_everyjob:D \exp_after:wN
13747 {
13748   \tex_the:D \tex_everyjob:D
13749   \seq_gput_right:NV \g__file_record_seq \g_file_curr_name_str
13750 }
13751 \</initex>

```

(End definition for \g__file_record_seq.)

\l__file_base_name_tl For storing the basename and full path whilst passing data internally.

```

\l__file_full_name_tl
13752 \tl_new:N \l__file_base_name_tl
13753 \tl_new:N \l__file_full_name_tl

```

(End definition for \l__file_base_name_tl and \l__file_full_name_tl.)

\l__file_dir_str Used in parsing a path into parts: in contrast to the above, these are never used outside of the current module.

```

\l__file_ext_str
\l__file_name_str
13754 \str_new:N \l__file_dir_str
13755 \str_new:N \l__file_ext_str
13756 \str_new:N \l__file_name_str

```

(End definition for \l__file_dir_str, \l__file_ext_str, and \l__file_name_str.)

\l_file_search_path_seq The current search path.

13757 \seq_new:N \l_file_search_path_seq

(End definition for \l_file_search_path_seq. This variable is documented on page 164.)

\l__file_tmp_seq Scratch space for comma list conversion in package mode.

13758 *package

13759 \seq_new:N \l__file_tmp_seq

13760 \package

(End definition for \l__file_tmp_seq.)

20.4.1 Internal auxiliaries

\s__file_stop Internal scan marks.

13761 \scan_new:N \s__file_stop

(End definition for \s__file_stop.)

\q__file_nil Internal quarks.

13762 \quark_new:N \q__file_nil

(End definition for \q__file_nil.)

__file_quark_if_nil_p:n Branching quark conditional.

__file_quark_if_nil:nTF 13763 __kernel_quark_new_conditional:Nn __file_quark_if_nil:n { TF }

(End definition for __file_quark_if_nil:nTF.)

\q__file_recursion_tail Internal recursion quarks.

\q__file_recursion_stop 13764 \quark_new:N \q__file_recursion_tail

13765 \quark_new:N \q__file_recursion_stop

(End definition for \q__file_recursion_tail and \q__file_recursion_stop.)

_file_if_recursion_tail_break:NN Functions to query recursion quarks.

_file_if_recursion_tail_stop_do:NN 13766 __kernel_quark_new_test:N _file_if_recursion_tail_stop:N

13767 __kernel_quark_new_test:N _file_if_recursion_tail_stop_do:nn

(End definition for _file_if_recursion_tail_break:NN and _file_if_recursion_tail_stop_do:NN.)

_kernel_file_name_sanitize:n Expanding the file name without expanding active characters is done using the same token-by-token approach as for example case changing. The final outcome only need be e-type expandable, so there is no need for the shuffling that is seen in other locations.

_kernel_file_name_expand_loop:w

_kernel_file_name_expand_N_type:Nw

_kernel_file_name_expand_group:nw

_kernel_file_name_expand_space:w

_kernel_file_name_strip_quotes:n

_kernel_file_name_strip_quotes:nnw

_kernel_file_name_strip_quotes:nnn

_kernel_file_name_trim_spaces:n

_kernel_file_name_trim_spaces:nw

_kernel_file_name_trim_spaces_aux:n

_kernel_file_name_trim_spaces_aux:w

13768 \cs_new:Npn _kernel_file_name_sanitize:n #1

13769 {

13770 \exp_args:Ne _kernel_file_name_trim_spaces:n

13771 {

13772 \exp_args:Ne _kernel_file_name_strip_quotes:n

13773 {

13774 _kernel_file_name_expand_loop:w #1

13775 \q__file_recursion_tail \q__file_recursion_stop

```

13776     }
13777   }
13778 }
13779 \cs_new:Npn \__kernel_file_name_expand_loop:w #1 \q__file_recursion_stop
13780 {
13781   \tl_if_head_is_N_type:nTF {#1}
13782   { \__kernel_file_name_expand_N_type:Nw }
13783   {
13784     \tl_if_head_is_group:nTF {#1}
13785     { \__kernel_file_name_expand_group:nw }
13786     { \__kernel_file_name_expand_space:w }
13787   }
13788   #1 \q__file_recursion_stop
13789 }
13790 \cs_new:Npn \__kernel_file_name_expand_N_type:Nw #1
13791 {
13792   \__file_if_recursion_tail_stop:N #1
13793   \bool_lazy_and:nnTF
13794   { \token_if_expandable_p:N #1 }
13795   {
13796     \bool_not_p:n
13797     {
13798       \bool_lazy_any_p:n
13799       {
13800         { \token_if_protected_macro_p:N #1 }
13801         { \token_if_protected_long_macro_p:N #1 }
13802         { \token_if_active_p:N #1 }
13803       }
13804     }
13805   }
13806   { \exp_after:wN \__kernel_file_name_expand_loop:w #1 }
13807   {
13808     \token_to_str:N #1
13809     \__kernel_file_name_expand_loop:w
13810   }
13811 }
13812 \cs_new:Npx \__kernel_file_name_expand_group:nw #1
13813 {
13814   \c_left_brace_str
13815   \exp_not:N \__kernel_file_name_expand_loop:w
13816   #1
13817   \c_right_brace_str
13818 }
13819 \exp_last_unbraced:NNo
13820 \cs_new:Npx \__kernel_file_name_expand_space:w \c_space_tl
13821 {
13822   \c_space_tl
13823   \exp_not:N \__kernel_file_name_expand_loop:w
13824 }

```

Quoting file name uses basically the same approach as for `luaquotejobname`: count the " tokens and remove them.

```

13825 \cs_new:Npn \__kernel_file_name_strip_quotes:n #1
13826 {

```

```

13827     \__kernel_file_name_strip_quotes:nnnw {#1} { 0 } { }
13828     #1 " \q__file_recursion_tail " \q__file_recursion_stop
13829 }
13830 \cs_new:Npn \__kernel_file_name_strip_quotes:nnnw #1#2#3#4 "
13831 {
13832     \__file_if_recursion_tail_stop_do:nn {#4}
13833     { \__kernel_file_name_strip_quotes:nnn {#1} {#2} {#3} }
13834     \__kernel_file_name_strip_quotes:nnnw {#1} { #2 + 1 } { #3#4 }
13835 }
13836 \cs_new:Npn \__kernel_file_name_strip_quotes:nnn #1#2#3
13837 {
13838     \int_if_even:nT {#2}
13839     {
13840         \__kernel_msg_expandable_error:nnn
13841         { kernel } { unbalanced-quote-in-filename } {#1}
13842     }
13843     #3
13844 }

```

Spaces need to be trimmed from the start of the name and from the end of any extension. However, the name we are passed might not have an extension: that means we have to look for one. If there is no extension, we still use the standard trimming function but deliberately prevent any spaces being removed at the end.

```

13845 \cs_new:Npn \__kernel_file_name_trim_spaces:n #1
13846 { \__kernel_file_name_trim_spaces:nw {#1} #1 . \q__file_nil . \s__file_stop }
13847 \cs_new:Npn \__kernel_file_name_trim_spaces:nw #1#2 . #3 . #4 \s__file_stop
13848 {
13849     \__file_quark_if_nil:nTF {#3}
13850     {
13851         \exp_args:Ne \__kernel_file_name_trim_spaces_aux:n
13852         { \tl_trim_spaces:n { #1 \s__file_stop } }
13853     }
13854     { \tl_trim_spaces:n {#1} }
13855 }
13856 \cs_new:Npn \__kernel_file_name_trim_spaces_aux:n #1
13857 { \__kernel_file_name_trim_spaces_aux:w #1 }
13858 \cs_new:Npn \__kernel_file_name_trim_spaces_aux:w #1 \s__file_stop {#1}

```

(End definition for __kernel_file_name_sanitiz:n and others.)

```

\__kernel_file_name_quote:n
\__kernel_file_name_quote:nw
13859 \cs_new:Npn \__kernel_file_name_quote:n #1
13860 { \__kernel_file_name_quote:nw {#1} #1 ~ \q__file_nil \s__file_stop }
13861 \cs_new:Npn \__kernel_file_name_quote:nw #1 #2 ~ #3 \s__file_stop
13862 {
13863     \__file_quark_if_nil:nTF {#3}
13864     { #1 }
13865     { "#1" }
13866 }

```

(End definition for __kernel_file_name_quote:n and __kernel_file_name_quote:nw.)

\c__file_marker_tl The same idea as the marker for rescanning token lists: this pair of tokens cannot appear in a file that is being input.

```

13867 \tl_const:Nx \c__file_marker_tl { : \token_to_str:N : }

```

(End definition for `\c__file_marker_tl`.)

`\file_get:nnN`TF The approach here is similar to that for `\tl_set_rescan:Nnn`. The file contents are
`\file_get:nnN` grabbed as an argument delimited by `\c__file_marker_tl`. A few subtleties: braces in
`__file_get_aux:nnN` `\if_false: ... \fi:` to deal with possible alignment tabs, `\tracingnesting` to avoid
`__file_get_do:Nw` a warning about a group being closed inside the `\scantokens`, and `\prg_return_true:`
is placed after the end-of-file marker.

```

13868 \cs_new_protected:Npn \file_get:nnN #1#2#3
13869 {
13870   \file_get:nnNF {#1} {#2} #3
13871   { \tl_set:Nn #3 { \q_no_value } }
13872 }
13873 \prg_new_protected_conditional:Npnn \file_get:nnN #1#2#3 { T , F , TF }
13874 {
13875   \file_get_full_name:nNTF {#1} \l__file_full_name_tl
13876   {
13877     \exp_args:NV \__file_get_aux:nnN
13878     \l__file_full_name_tl
13879     {#2} #3
13880     \prg_return_true:
13881   }
13882   { \prg_return_false: }
13883 }
13884 \cs_new_protected:Npx \__file_get_aux:nnN #1#2#3
13885 {
13886   \exp_not:N \if_false: { \exp_not:N \fi:
13887   \group_begin:
13888     \int_set_eq:NN \tex_tracingnesting:D \c_zero_int
13889     \exp_not:N \exp_args:No \tex_everyeof:D
13890     { \exp_not:N \c__file_marker_tl }
13891     #2 \scan_stop:
13892     \exp_not:N \exp_after:wN \exp_not:N \__file_get_do:Nw
13893     \exp_not:N \exp_after:wN #3
13894     \exp_not:N \exp_after:wN \exp_not:N \prg_do_nothing:
13895     \exp_not:N \tex_input:D
13896     \sys_if_engine luatex:TF
13897     { {#1} }
13898     { \exp_not:N \__kernel_file_name_quote:n {#1} \scan_stop: }
13899     \exp_not:N \if_false: } \exp_not:N \fi:
13900   }
13901   \exp_args:Nno \use:nn
13902   { \cs_new_protected:Npn \__file_get_do:Nw #1#2 }
13903   { \c__file_marker_tl }
13904   {
13905     \group_end:
13906     \tl_set:No #1 {#2}
13907   }

```

(End definition for `\file_get:nnNTF` and others. These functions are documented on page 164.)

`__file_size:n` A copy of the primitive where it's available, or the LuaTeX equivalent if relevant.

```

13908 \cs_new_eq:NN \__file_size:n \tex_filesize:D
13909 \sys_if_engine luatex:T
13910 {

```

```

13911 \cs_gset:Npn \__file_size:n #1
13912 {
13913   \lua_now:e
13914   { l3kernel.filesize ( " \lua_escape:e {#1} " ) }
13915 }
13916 }

```

(End definition for __file_size:n.)

```

\file_full_name:n
\__file_full_name:n
\__file_full_name_aux:nn
\__file_full_name_aux:n
\__file_name_cleanup:w
\__file_name_end:
\__file_name_ext_check:n
\__file_name_ext_check:nw
\__file_name_ext_check:nnw
\__file_name_ext_check:nn

```

File searching can be carried out if the `\pdffilesize` primitive or an equivalent is available. That of course means we need to arrange for everything else to here to be done by expansion too. We start off by sanitizing the name and quoting if required: we may need to remove those quotes, so the raw name is passed too.

```

13917 \cs_new:Npn \file_full_name:n #1
13918 {
13919   \exp_args:Ne \__file_full_name:n
13920   { \__kernel_file_name_sanitiz:n {#1} }
13921 }

```

First, we check if the file is just here: no mapping so we do not need the break part of the broader auxiliary. We are using the fact that the primitive here returns nothing if the file is entirely absent. For package mode, `\input@path` is a token list not a sequence.

```

13922 \cs_new:Npn \__file_full_name:n #1
13923 {
13924   \tl_if_blank:nF {#1}
13925   {
13926     \tl_if_blank:eTF { \__file_size:n {#1} }
13927     {
13928       \seq_map_tokens:Nn \l_file_search_path_seq
13929       { \__file_full_name_aux:nn {#1} }
13930     }
13931     (*package)
13932     \cs_if_exist:NT \input@path
13933     {
13934       \tl_map_tokens:Nn \input@path
13935       { \__file_full_name_aux:nn {#1} }
13936     }
13937   }
13938   \__file_name_end:
13939   { \__file_ext_check:n {#1} }
13940 }
13941 }

```

Two pars to the auxiliary here so we can avoid doing quoting twice in the event we find the right file.

```

13942 \cs_new:Npn \__file_full_name_aux:nn #1#2
13943 { \exp_args:Ne \__file_full_name_aux:n { \tl_to_str:n {#2} / #1 } }
13944 \cs_new:Npn \__file_full_name_aux:n #1
13945 {
13946   \tl_if_blank:eF { \__file_size:n {#1} }
13947   {
13948     \seq_map_break:n
13949     {
13950       \__file_ext_check:n {#1}
13951       \__file_name_cleanup:w

```



```

13952     }
13953   }
13954 }
13955 \cs_new:Npn \__file_name_cleanup:w #1 \__file_name_end: { }
13956 \cs_new:Npn \__file_name_end: { }

```

As T_EX automatically adds .tex if there is no extension, there is a little clean up to do here. First, make sure we are not in the directory part, saving that. Then check for an extension.

```

13957 \cs_new:Npn \__file_ext_check:n #1
13958 { \__file_ext_check:nw { / } #1 / \q__file_nil / \s__file_stop }
13959 \cs_new:Npn \__file_ext_check:nw #1 #2 / #3 / #4 \s__file_stop
13960 {
13961   \__file_quark_if_nil:nTF {#3}
13962   {
13963     \exp_args:No \__file_ext_check:nnw
13964     { \use_none:n #1 } {#2} #2 . \q__file_nil . \s__file_stop
13965   }
13966   { \__file_ext_check:nw { #1 #2 / } #3 / #4 \s__file_stop }
13967 }
13968 \cs_new:Npx \__file_ext_check:nnw #1#2#3 . #4 . #5 \s__file_stop
13969 {
13970   \exp_not:N \__file_quark_if_nil:nTF {#4}
13971   {
13972     \exp_not:N \__file_ext_check:nn
13973     { #1 #2 } { #1 #2 \tl_to_str:n { .tex } }
13974   }
13975   { #1 #2 }
13976 }
13977 \cs_new:Npn \__file_ext_check:nn #1#2
13978 {
13979   \tl_if_blank:eTF { \__file_size:n {#2} }
13980   {#1}
13981   {
13982     \int_compare:nNnTF
13983     { \__file_size:n {#1} } = { \__file_size:n {#2} }
13984     {#2}
13985     {#1}
13986   }
13987 }

```

Deal with the fact that the primitive might not be available.

```

13988 \bool_lazy_or:nnF
13989 { \cs_if_exist_p:N \tex_filesize:D }
13990 { \sys_if_engine luatex_p: }
13991 {
13992   \cs_gset:Npn \file_full_name:n #1
13993   {
13994     \__kernel_msg_expandable_error:nnn
13995     { kernel } { primitive-not-available }
13996     { \pdffilesize }
13997   }
13998 }
13999 \__kernel_msg_new:nnnn { kernel } { primitive-not-available }
14000 { Primitive~\token_to_str:N #1 not-available }

```

```

14001 {
14002   The-version-of-your-TeX-engine-does-not-provide-functionality-equivalent-to-
14003   the-#1-primitive.
14004 }

```

(End definition for `\file_full_name:n` and others. This function is documented on page 164.)

```

\file_get_full_name:nN
\file_get_full_name:VN
\file_get_full_name:nNTF
\file_get_full_name:VNTF
  \_file_get_full_name_search:nN

```

These functions pre-date using `\tex_filesize:D` for file searching, so are `get` functions with protection. To avoid having different search set ups, they are simply wrappers around the code above.

```

14005 \cs_new_protected:Npn \file_get_full_name:nN #1#2
14006 {
14007   \file_get_full_name:nNF {#1} #2
14008   { \tl_set:Nn #2 { \q_no_value } }
14009 }
14010 \cs_generate_variant:Nn \file_get_full_name:nN { V }
14011 \prg_new_protected_conditional:Npnn \file_get_full_name:nN #1#2 { T , F , TF }
14012 {
14013   \tl_set:Nx #2
14014   { \file_full_name:n {#1} }
14015   \tl_if_empty:NTF #2
14016   { \prg_return_false: }
14017   { \prg_return_true: }
14018 }
14019 \cs_generate_variant:Nn \file_get_full_name:nNT { V }
14020 \cs_generate_variant:Nn \file_get_full_name:nNF { V }
14021 \cs_generate_variant:Nn \file_get_full_name:nNTF { V }

```

If `\tex_filesize:D` is not available, the way to test if a file exists is to try to open it: if it does not exist then TeX reports end-of-file. A search is made looking at each potential path in turn (starting from the current directory). The first location is of course treated as the correct one: this is done by jumping to `\prg_break_point:.` If nothing is found, `#2` is returned empty. A special case when there is no extension is that once the first location is found we test the existence of the file with `.tex` extension in that directory, and if it exists we include the `.tex` extension in the result.

```

14022 \bool_lazy_or:nnF
14023 { \cs_if_exist_p:N \tex_filesize:D }
14024 { \sys_if_engine luatex_p: }
14025 {
14026   \prg_set_protected_conditional:Npnn \file_get_full_name:nN #1#2 { T , F , TF }
14027   {
14028     \tl_set:Nx \l__file_base_name_tl
14029     { \_kernel_file_name_sanitiz:n {#1} }
14030     \_file_get_full_name_search:nN { } \use:n
14031     \seq_map_inline:Nn \l_file_search_path_seq
14032     { \_file_get_full_name_search:nN { ##1 / } \seq_map_break:n }
14033     (*package)
14034     \cs_if_exist:NT \input@path
14035     {
14036       \tl_map_inline:Nn \input@path
14037       { \_file_get_full_name_search:nN { ##1 } \tl_map_break:n }
14038     }
14039     \tl_set:Nn \l__file_full_name_tl { \q_no_value }
14040

```

```

14041 \prg_break_point:
14042 \quark_if_no_value:NTF \l__file_full_name_tl
14043 {
14044   \ior_close:N \g__file_internal_ior
14045   \prg_return_false:
14046 }
14047 {
14048   \file_parse_full_name:VNNN \l__file_full_name_tl
14049   \l__file_dir_str \l__file_name_str \l__file_ext_str
14050   \str_if_empty:NT \l__file_ext_str
14051   {
14052     \__kernel_ior_open:No \g__file_internal_ior
14053     { \l__file_full_name_tl .tex }
14054     \ior_if_eof:NF \g__file_internal_ior
14055     { \tl_put_right:Nn \l__file_full_name_tl { .tex } }
14056   }
14057   \ior_close:N \g__file_internal_ior
14058   \tl_set_eq:NN #2 \l__file_full_name_tl
14059   \prg_return_true:
14060 }
14061 }
14062 }
14063 \cs_new_protected:Npn \__file_get_full_name_search:nN #1#2
14064 {
14065   \tl_set:Nx \l__file_full_name_tl
14066   { \tl_to_str:n {#1} \l__file_base_name_tl }
14067   \__kernel_ior_open:No \g__file_internal_ior \l__file_full_name_tl
14068   \ior_if_eof:NF \g__file_internal_ior { #2 { \prg_break: } }
14069 }

```

(End definition for \file_get_full_name:nN, \file_get_full_name:nNTF, and __file_get_full_name_search:nN. These functions are documented on page 164.)

\g__file_internal_ior A reserved stream to test for file existence, if required.

```

14070 \bool_lazy_or:nnF
14071 { \cs_if_exist_p:N \tex_filesize:D }
14072 { \sys_if_engine luatex_p: }
14073 { \ior_new:N \g__file_internal_ior }

```

(End definition for \g__file_internal_ior.)

\file_md5five_hash:n Getting file details by expansion is relatively easy if a bit repetitive. As the MD5 function has a slightly different syntax from the other commands, there is a little cleaning up to do.

```

\__file_details:nn
\__file_details_aux:nn
\__file_md5five_hash:n
14074 \cs_new:Npn \file_md5five_hash:n #1
14075 { \__file_details:nn {#1} { md5sum } }
14076 \cs_new:Npn \file_size:n #1
14077 { \__file_details:nn {#1} { size } }
14078 \cs_new:Npn \file_timestamp:n #1
14079 { \__file_details:nn {#1} { moddate } }
14080 \cs_new:Npn \__file_details:nn #1#2
14081 {
14082   \exp_args:Ne \__file_details_aux:nn
14083   { \file_full_name:n {#1} } {#2}

```

```

14084 }
14085 \cs_new:Npn \__file_details_aux:nn #1#2
14086 {
14087   \tl_if_blank:nF {#1}
14088   { \use:c { tex_file #2 :D } {#1} }
14089 }
14090 \sys_if_engine luatex:TF
14091 {
14092   \cs_gset:Npn \__file_details_aux:nn #1#2
14093   {
14094     \lua_now:e
14095     { l3kernel.file#2 ( " \lua_escape:e { #1 } " ) }
14096   }
14097 }
14098 {
14099   \cs_gset:Npn \file_md5five_hash:n #1
14100   { \exp_args:Ne \__file_md5five_hash:n { \file_full_name:n {#1} } }
14101   \cs_new:Npn \__file_md5five_hash:n #1
14102   { \tex_md5fivesum:D file {#1} }
14103 }

```

(End definition for `\file_md5five_hash:n` and others. These functions are documented on page 165.)

\file_hex_dump:nnn

These are separate as they need multiple arguments *or* the file size. For LuaTeX, the emulation does not need the file size so we save a little on expansion.

`__file_hex_dump_auxi:nnn`

`__file_hex_dump_auxii:nnnn`

`__file_hex_dump_auxiii:nnnn`

`__file_hex_dump_auxiiv:nnn`

\file_hex_dump:n

`__file_hex_dump:n`

```

14104 \cs_new:Npn \file_hex_dump:nnn #1#2#3
14105 {
14106   \exp_args:Neee \__file_hex_dump_auxi:nnn
14107   { \file_full_name:n {#1} }
14108   { \int_eval:n {#2} }
14109   { \int_eval:n {#3} }
14110 }
14111 \cs_new:Npn \__file_hex_dump_auxi:nnn #1#2#3
14112 {
14113   \bool_lazy_any:nF
14114   {
14115     { \tl_if_blank_p:n {#1} }
14116     { \int_compare_p:nNn {#2} = 0 }
14117     { \int_compare_p:nNn {#3} = 0 }
14118   }
14119   {
14120     \exp_args:Ne \__file_hex_dump_auxii:nnnn
14121     { \__file_details_aux:nn {#1} { size } }
14122     {#1} {#2} {#3}
14123   }
14124 }
14125 \cs_new:Npn \__file_hex_dump_auxii:nnnn #1#2#3#4
14126 {
14127   \int_compare:nNnTF {#3} > 0
14128   { \__file_hex_dump_auxiii:nnnn {#3} }
14129   {
14130     \exp_args:Ne \__file_hex_dump_auxiii:nnnn
14131     { \int_eval:n { #1 + #3 } }
14132   }

```

```

14133     {#1} {#2} {#4}
14134   }
14135 \cs_new:Npn \__file_hex_dump_auxiii:nnnn #1#2#3#4
14136 {
14137   \int_compare:nNnTF {#4} > 0
14138   { \__file_hex_dump_auxiv:nnn {#4} }
14139   {
14140     \exp_args:Ne \__file_hex_dump_auxiv:nnn
14141     { \int_eval:n { #2 + #4 } }
14142   }
14143   {#1} {#3}
14144 }
14145 \cs_new:Npn \__file_hex_dump_auxiv:nnn #1#2#3
14146 {
14147   \tex_dump:D
14148   offset ~ \int_eval:n { #2 - 1 } ~
14149   length ~ \int_eval:n { #1 - #2 + 1 }
14150   {#3}
14151 }
14152 \sys_if_engine luatex:T
14153 {
14154   \cs_gset:Npn \__file_hex_dump_auxiv:nnn #1#2#3
14155   {
14156     \lua_now:e
14157     {
14158       l3kernel.dump
14159       (
14160         " \lua_escape:e {#3} " ,
14161         \int_eval:n { #2 - 1 } ,
14162         \int_eval:n { #1 - #2 + 1 }
14163       )
14164     }
14165   }
14166 }
14167 \cs_new:Npn \file_hex_dump:n #1
14168 { \exp_args:Ne \__file_hex_dump:n { \file_full_name:n {#1} } }
14169 \cs_new:Npn \__file_hex_dump:n #1
14170 {
14171   \tl_if_blank:nF {#1}
14172   { \tex_dump:D length \tex_filesize:D {#1} {#1} }
14173 }
14174 \sys_if_engine luatex:T
14175 {
14176   \cs_gset:Npn \__file_hex_dump:n #1
14177   {
14178     \lua_now:e
14179     { l3kernel.dump ( " \lua_escape:e { #1 } " ) }
14180   }
14181 }

```

(End definition for `\file_hex_dump:nnn` and others. These functions are documented on page 165.)

`\file_get_hex_dump:nN` Non-expandable wrappers around the above in the case where appropriate primitive support exists.
`\file_get_hex_dump:nNTF`
`\file_get_md5_hash:nN`
`\file_get_md5_hash:nNTF`
`\file_get_timestamp:nN`
`\file_get_timestamp:nNTF`
`__file_get_details:nnN`

```

14182 \cs_new_protected:Npn \file_get_hex_dump:nN #1#2
14183 { \file_get_hex_dump:nNF {#1} #2 { \tl_set:Nn #2 { \q_no_value } } }
14184 \cs_new_protected:Npn \file_get_md5five_hash:nN #1#2
14185 { \file_get_md5five_hash:nNF {#1} #2 { \tl_set:Nn #2 { \q_no_value } } }
14186 \cs_new_protected:Npn \file_get_size:nN #1#2
14187 { \file_get_size:nNF {#1} #2 { \tl_set:Nn #2 { \q_no_value } } }
14188 \cs_new_protected:Npn \file_get_timestamp:nN #1#2
14189 { \file_get_timestamp:nNF {#1} #2 { \tl_set:Nn #2 { \q_no_value } } }
14190 \prg_new_protected_conditional:Npnn \file_get_hex_dump:nN #1#2 { T , F , TF }
14191 { \__file_get_details:nnN {#1} { hex_dump } #2 }
14192 \prg_new_protected_conditional:Npnn \file_get_md5five_hash:nN #1#2 { T , F , TF }
14193 { \__file_get_details:nnN {#1} { md5five_hash } #2 }
14194 \prg_new_protected_conditional:Npnn \file_get_size:nN #1#2 { T , F , TF }
14195 { \__file_get_details:nnN {#1} { size } #2 }
14196 \prg_new_protected_conditional:Npnn \file_get_timestamp:nN #1#2 { T , F , TF }
14197 { \__file_get_details:nnN {#1} { timestamp } #2 }
14198 \cs_new_protected:Npn \__file_get_details:nnN #1#2#3
14199 {
14200   \tl_set:Nx #3
14201   { \use:c { file_ #2 :n } {#1} }
14202   \tl_if_empty:NTF #3
14203   { \prg_return_false: }
14204   { \prg_return_true: }
14205 }

```

Where the primitive is not available, issue an error: this is a little more conservative than absolutely needed, but does work.

```

14206 \bool_lazy_or:nnF
14207 { \cs_if_exist_p:N \tex_filesize:D }
14208 { \sys_if_engine luatex_p: }
14209 {
14210   \cs_set_protected:Npn \__file_get_details:nnN #1#2#3
14211   {
14212     \tl_clear:N #3
14213     \__kernel_msg_error:nnx
14214     { kernel } { primitive-not-available }
14215     {
14216       \token_to_str:N \(\pdf)file
14217       \str_case:nn {#2}
14218       {
14219         { hex_dump } { dump }
14220         { md5five_hash } { md5fivesum }
14221         { timestamp } { moddate }
14222         { size } { size }
14223       }
14224     }
14225     \prg_return_false:
14226   }
14227 }

```

(End definition for \file_get_hex_dump:nNTF and others. These functions are documented on page 165.)

\file_get_hex_dump:nnnN
\file_get_hex_dump:nnnNTF

Custom code due to the additional arguments.

```

14228 \cs_new_protected:Npn \file_get_hex_dump:nnnN #1#2#3#4

```

```

14229 {
14230   \file_get_hex_dump:nnnNF {#1} {#2} {#3} #4
14231   { \tl_set:Nn #4 { \q_no_value } }
14232 }
14233 \prg_new_protected_conditional:Npnn \file_get_hex_dump:nnnN #1#2#3#4
14234 { T , F , TF }
14235 {
14236   \tl_set:Nx #4
14237   { \file_hex_dump:nnn {#1} {#2} {#3} }
14238   \tl_if_empty:NTF #4
14239   { \prg_return_false: }
14240   { \prg_return_true: }
14241 }

```

(End definition for `\file_get_hex_dump:nnnNTF`. This function is documented on page 165.)

`__file_str_cmp:nn` As we are doing a fixed-length “big” integer comparison, it is easiest to use the low-level
`__file_str_escape:n` behavior of string comparisons.

```

14242 \cs_new:Npn \__file_str_cmp:nn #1#2 { \tex_strcmp:D {#1} {#2} }
14243 \sys_if_engine luatex:T
14244 {
14245   \cs_set:Npn \__file_str_cmp:nn #1#2
14246   {
14247     \lua_now:e
14248     {
14249       l3kernel.strptime
14250       (
14251         " \__file_str_escape:n {#1}",
14252         " \__file_str_escape:n {#2}"
14253       )
14254     }
14255   }
14256   \cs_new:Npn \__file_str_escape:n #1
14257   {
14258     \lua_escape:e
14259     { \__kernel_tl_to_str:w \use:e { {#1} } }
14260   }
14261 }

```

(End definition for `__file_str_cmp:nn` and `__file_str_escape:n`.)

`\file_compare_timestamp:p:nN` Comparison of file date can be done by using the low-level nature of the string comparison
`\file_compare_timestamp:nNnTF` functions.

```

\__file_compare_timestamp:nnN
\__file_timestamp:n
14262 \prg_new_conditional:Npnn \file_compare_timestamp:nNn #1#2#3
14263 { p , T , F , TF }
14264 {
14265   \exp_args:Nee \__file_compare_timestamp:nnN
14266   { \file_full_name:n {#1} }
14267   { \file_full_name:n {#3} }
14268   #2
14269 }
14270 \cs_new:Npn \__file_compare_timestamp:nnN #1#2#3
14271 {
14272   \tl_if_blank:nTF {#1}

```

```

14273 {
14274   \if_charcode:w #3 <
14275   \prg_return_true:
14276   \else:
14277     \prg_return_false:
14278   \fi:
14279 }
14280 {
14281   \tl_if_blank:nTF {#2}
14282   {
14283     \if_charcode:w #3 >
14284     \prg_return_true:
14285     \else:
14286       \prg_return_false:
14287     \fi:
14288   }
14289   {
14290     \if_int_compare:w
14291       \__file_str_cmp:nn
14292       { \__file_timestamp:n {#1} }
14293       { \__file_timestamp:n {#2} }
14294       #3 0 \exp_stop_f:
14295       \prg_return_true:
14296       \else:
14297         \prg_return_false:
14298       \fi:
14299   }
14300 }
14301 }
14302 \sys_if_engine luatex:TF
14303 {
14304   \cs_new:Npn \__file_timestamp:n #1
14305   {
14306     \lua_now:e
14307     { l3kernel.filemoddate ( " \lua_escape:e {#1} " ) }
14308   }
14309 }
14310 { \cs_new_eq:NN \__file_timestamp:n \tex_filemoddate:D }
14311 \cs_if_exist:NF \tex_filemoddate:D
14312 {
14313   \prg_set_conditional:Npnn \file_compare_timestamp:nNn #1#2#3
14314   { p , T , F , TF }
14315   {
14316     \__kernel_msg_expandable_error:nnn
14317     { kernel } { primitive-not-available }
14318     { \(\pdf)filemoddate }
14319     \prg_return_false:
14320   }
14321 }

```

(End definition for `\file_compare_timestamp:nNnTF`, `__file_compare_timestamp:nnN`, and `__file_timestamp:n`. This function is documented on page 166.)

`\file_if_exist:nTF` The test for the existence of a file is a wrapper around the function to add a path to a file. If the file was found, the path contains something, whereas if the file was not located

then the return value is empty.

```

14322 \prg_new_protected_conditional:Npnn \file_if_exist:n #1 { T , F , TF }
14323 {
14324   \file_get_full_name:nNTF {#1} \l__file_full_name_tl
14325   { \prg_return_true: }
14326   { \prg_return_false: }
14327 }

```

(End definition for `\file_if_exist:nTF`. This function is documented on page 164.)

`\file_if_exist_input:n` Input of a file with a test for existence. We do not define the T or TF variants because the most useful place to place the *⟨true code⟩* would be inconsistent with other conditionals.

`\file_if_exist_input:nF`

```

14328 \cs_new_protected:Npn \file_if_exist_input:n #1
14329 {
14330   \file_get_full_name:nNT {#1} \l__file_full_name_tl
14331   { \__file_input:V \l__file_full_name_tl }
14332 }
14333 \cs_new_protected:Npn \file_if_exist_input:nF #1#2
14334 {
14335   \file_get_full_name:nNTF {#1} \l__file_full_name_tl
14336   { \__file_input:V \l__file_full_name_tl }
14337   {#2}
14338 }

```

(End definition for `\file_if_exist_input:n` and `\file_if_exist_input:nF`. These functions are documented on page 167.)

`\file_input_stop:` A simple rename.

```

14339 \cs_new_protected:Npn \file_input_stop: { \tex_endinput:D }

```

(End definition for `\file_input_stop:`. This function is documented on page 167.)

`__kernel_file_missing:n` An error message for a missing file, also used in `\ior_open:Nn`.

```

14340 \cs_new_protected:Npn \__kernel_file_missing:n #1
14341 {
14342   \__kernel_msg_error:nxx { kernel } { file-not-found }
14343   { \__kernel_file_name_sanitize:n {#1} }
14344 }

```

(End definition for `__kernel_file_missing:n`.)

`\file_input:n` Loading a file is done in a safe way, checking first that the file exists and loading only if it does. Push the file name on the `\g__file_stack_seq`, and add it to the file list, either `\g__file_record_seq`, or `\@filelist` in package mode.

`__file_input:n`

`__file_input:V`

`__file_input_push:n`

`__kernel_file_input_push:n`

`__file_input_pop:`

`__kernel_file_input_pop:`

`__file_input_pop:nnn`

```

14345 \cs_new_protected:Npn \file_input:n #1
14346 {
14347   \file_get_full_name:nNTF {#1} \l__file_full_name_tl
14348   { \__file_input:V \l__file_full_name_tl }
14349   { \__kernel_file_missing:n {#1} }
14350 }
14351 \cs_new_protected:Npx \__file_input:n #1
14352 {
14353   \*initex
14354   \seq_gput_right:Nn \exp_not:N \g__file_record_seq {#1}
14355   \*initex

```

```

14356 \<package>
14357   \exp_not:N \clist_if_exist:NTF \exp_not:N \@filelist
14358     { \exp_not:N \@addtofilelist {#1} }
14359     { \seq_gput_right:Nn \exp_not:N \g__file_record_seq {#1} }
14360 \</package>
14361   \exp_not:N \__file_input_push:n {#1}
14362   \exp_not:N \tex_input:D
14363   \sys_if_engine_luatex:TF
14364     { {#1} }
14365     { \exp_not:N \__kernel_file_name_quote:n {#1} \scan_stop: }
14366   \exp_not:N \__file_input_pop:
14367 }
14368 \cs_generate_variant:Nn \__file_input:n { V }

```

Keeping a track of the file data is easy enough: we store the separated parts so we do not need to parse them twice.

```

14369 \cs_new_protected:Npn \__file_input_push:n #1
14370 {
14371   \seq_gpush:Nx \g__file_stack_seq
14372   {
14373     { \g_file_curr_dir_str }
14374     { \g_file_curr_name_str }
14375     { \g_file_curr_ext_str }
14376   }
14377   \file_parse_full_name:nNNN {#1}
14378   \l__file_dir_str \l__file_name_str \l__file_ext_str
14379   \str_gset_eq:NN \g_file_curr_dir_str \l__file_dir_str
14380   \str_gset_eq:NN \g_file_curr_name_str \l__file_name_str
14381   \str_gset_eq:NN \g_file_curr_ext_str \l__file_ext_str
14382 }
14383 \<package>
14384 \cs_new_eq:NN \__kernel_file_input_push:n \__file_input_push:n
14385 \</package>
14386 \cs_new_protected:Npn \__file_input_pop:
14387 {
14388   \seq_gpop:NN \g__file_stack_seq \l__file_internal_tl
14389   \exp_after:wN \__file_input_pop:nnn \l__file_internal_tl
14390 }
14391 \<package>
14392 \cs_new_eq:NN \__kernel_file_input_pop: \__file_input_pop:
14393 \</package>
14394 \cs_new_protected:Npn \__file_input_pop:nnn #1#2#3
14395 {
14396   \str_gset:Nn \g_file_curr_dir_str {#1}
14397   \str_gset:Nn \g_file_curr_name_str {#2}
14398   \str_gset:Nn \g_file_curr_ext_str {#3}
14399 }

```

(End definition for `\file_input:n` and others. This function is documented on page 166.)

`\file_parse_full_name:nNNN` Parsing starts by stripping off any surrounding quotes. Then find the directory #4 by splitting at the last /. (The auxiliary returns true/false depending on whether it found the delimiter.) We correct for the case of a file in the root /, as in that case we wish to keep the trailing (and only) slash. Then split the base name #5 at the last dot. If there was indeed a dot, #5 contains the name and #6 the extension without the dot, which we

add back for convenience. In the special case of no extension given, the auxiliary stored the name into #6, we just have to move it to #5.

```

14400 \cs_new_protected:Npn \file_parse_full_name:nNNN #1#2#3#4
14401 {
14402   \exp_after:wN \__file_parse_full_name_auxi:w
14403   \tl_to_str:n { #1 " #1 " } \s__file_stop #2#3#4
14404 }
14405 \cs_generate_variant:Nn \file_parse_full_name:nNNN { V }
14406 \cs_new_protected:Npn \__file_parse_full_name_auxi:w
14407   #1 " #2 " #3 \s__file_stop #4#5#6
14408 {
14409   \__file_parse_full_name_split:nNNNTF {#2} / #4 #5
14410   { \str_if_empty:NT #4 { \str_set:Nn #4 { / } } }
14411   { }
14412   \exp_args:No \__file_parse_full_name_split:nNNNTF {#5} . #5 #6
14413   { \str_put_left:Nn #6 { . } }
14414   {
14415     \str_set_eq:NN #5 #6
14416     \str_clear:N #6
14417   }
14418 }
14419 \cs_new_protected:Npn \__file_parse_full_name_split:nNNNTF #1#2#3#4
14420 {
14421   \cs_set_protected:Npn \__file_tmp:w ##1 ##2 #2 ##3 \s__file_stop
14422   {
14423     \tl_if_empty:nTF {##3}
14424     {
14425       \str_set:Nn #4 {##2}
14426       \tl_if_empty:nTF {##1}
14427       {
14428         \str_clear:N #3
14429         \use_ii:nn
14430       }
14431       {
14432         \str_set:Nx #3 { \str_tail:n {##1} }
14433         \use_i:nn
14434       }
14435     }
14436     { \__file_tmp:w { ##1 #2 ##2 } ##3 \s__file_stop }
14437   }
14438   \__file_tmp:w { } #1 #2 \s__file_stop
14439 }

```

(End definition for `\file_parse_full_name:nNNN`, `__file_parse_full_name_auxi:w`, and `__file_parse_full_name_split:nNNNTF`. This function is documented on page 165.)

\file_show_list: A function to list all files used to the log, without duplicates. In package mode, if **\file_log_list:** `\@filelist` is still defined, we need to take this list of file names into account (we capture it `\AtBeginDocument` into `\g__file_record_seq`), turning it to a string (this does not affect the commas of this comma list).
`__file_list:N`
`__file_list_aux:n`

```

14440 \cs_new_protected:Npn \file_show_list: { \__file_list:N \msg_show:nnxxxx }
14441 \cs_new_protected:Npn \file_log_list: { \__file_list:N \msg_log:nnxxxx }
14442 \cs_new_protected:Npn \__file_list:N #1
14443 {

```

```

14444 \seq_clear:N \l__file_tmp_seq
14445 \*package)
14446 \clist_if_exist:NT \@filelist
14447 {
14448   \exp_args:NNx \seq_set_from_clist:Nn \l__file_tmp_seq
14449   { \tl_to_str:N \@filelist }
14450 }
14451 \*package)
14452 \seq_concat:NNN \l__file_tmp_seq \l__file_tmp_seq \g__file_record_seq
14453 \seq_remove_duplicates:N \l__file_tmp_seq
14454 #1 { LaTeX/kernel } { file-list }
14455 { \seq_map_function:NN \l__file_tmp_seq \__file_list_aux:n }
14456 { } { } { }
14457 }
14458 \cs_new:Npn \__file_list_aux:n #1 { \iow_newline: #1 }

```

(End definition for `\file_show_list:` and others. These functions are documented on page 167.)

When used as a package, there is a need to hold onto the standard file list as well as the new one here. File names recorded in `\@filelist` must be turned to strings before being added to `\g__file_record_seq`.

```

14459 \*package)
14460 \cs_if_exist:NT \@filelist
14461 {
14462   \AtBeginDocument
14463   {
14464     \exp_args:NNx \seq_set_from_clist:Nn \l__file_tmp_seq
14465     { \tl_to_str:N \@filelist }
14466     \seq_gconcat:NNN
14467     \g__file_record_seq
14468     \g__file_record_seq
14469     \l__file_tmp_seq
14470   }
14471 }
14472 \*package)

```

20.5 GetIfInfo

\GetIdInfo As documented in `expl3.dtx` this function extracts file name etc from an SVN Id line. This used to be how we got version number and so on in all modules, so it had to be defined in `l3bootstrap`. Now it's more convenient to define it after we have set up quite a lot of tools, and `l3file` seems the least unreasonable place for it.

The idea here is to extract out the information needed from a standard SVN Id line, but to avoid a line that would get changed when the file is checked in. Hence the fact that none of the lines here include both a dollar sign and the Id keyword!

```

14473 \cs_new_protected:Npn \GetIdInfo
14474 {
14475   \tl_clear_new:N \ExplFileDescription
14476   \tl_clear_new:N \ExplFileDate
14477   \tl_clear_new:N \ExplFileName
14478   \tl_clear_new:N \ExplFileExtension
14479   \tl_clear_new:N \ExplFileVersion
14480   \group_begin:
14481   \char_set_catcode_space:n { 32 }

```

```

14482     \exp_after:wN
14483     \group_end:
14484     \__file_id_info_auxi:w
14485 }

```

A first check for a completely empty SVN field. If that is not the case, there is a second case when a file created using `svn cp` but has not been checked in. That leaves a special marker `-1` version, which has no further data. Dealing correctly with that is the reason for the space in the line to use `__file_id_info_auxii:w`.

```

14486 \cs_new_protected:Npn \__file_id_info_auxi:w $ #1 $ #2
14487 {
14488     \tl_set:Nn \ExplFileDescription {#2}
14489     \str_if_eq:nnTF {#1} { Id }
14490     {
14491         \tl_set:Nn \ExplFileDate { 0000/00/00 }
14492         \tl_set:Nn \ExplFileName { [unknown] }
14493         \tl_set:Nn \ExplFileExtension { [unknown~extension] }
14494         \tl_set:Nn \ExplFileVersion {-1}
14495     }
14496     { \__file_id_info_auxii:w #1 ~ \s__file_stop }
14497 }

```

Here, `#1` is `Id`, `#2` is the file name, `#3` is the extension, `#4` is the version, `#5` is the check in date and `#6` is the check in time and user, plus some trailing spaces. If `#4` is the marker `-1` value then `#5` and `#6` are empty.

```

14498 \cs_new_protected:Npn \__file_id_info_auxii:w
14499     #1 ~ #2.#3 ~ #4 ~ #5 ~ #6 \s__file_stop
14500 {
14501     \tl_set:Nn \ExplFileName {#2}
14502     \tl_set:Nn \ExplFileExtension {#3}
14503     \tl_set:Nn \ExplFileVersion {#4}
14504     \str_if_eq:nnTF {#4} {-1}
14505     { \tl_set:Nn \ExplFileDate { 0000/00/00 } }
14506     { \__file_id_info_auxiii:w #5 - 0 - 0 - \s__file_stop }
14507 }

```

Convert an SVN-style date into a L^AT_EX-style one.

```

14508 \cs_new_protected:Npn \__file_id_info_auxiii:w #1 - #2 - #3 - #4 \s__file_stop
14509 { \tl_set:Nn \ExplFileDate { #1/#2/#3 } }

```

(End definition for `\GetIdInfo` and others. This function is documented on page 7.)

20.6 Messages

```

14510 \__kernel_msg_new:nnnn { kernel } { file-not-found }
14511 { File~'#1'~not~found. }
14512 {
14513     The~requested~file~could~not~be~found~in~the~current~directory,~
14514     in~the~TeX~search~path~or~in~the~LaTeX~search~path.
14515 }
14516 \__kernel_msg_new:nnn { kernel } { file-list }
14517 {
14518     >~File~List~<
14519     #1 \\
14520     .....

```

```

14521 }
14522 \__kernel_msg_new:nnnn { kernel } { input-streams-exhausted }
14523 { Input~streams-exhausted }
14524 {
14525   TeX~can~only~open~up~to~16~input~streams~at~one~time.\\
14526   All~16~are~currently~in~use,~and~something~wanted~to~open~
14527   another~one.
14528 }
14529 \__kernel_msg_new:nnnn { kernel } { output-streams-exhausted }
14530 { Output~streams-exhausted }
14531 {
14532   TeX~can~only~open~up~to~16~output~streams~at~one~time.\\
14533   All~16~are~currently~in~use,~and~something~wanted~to~open~
14534   another~one.
14535 }
14536 \__kernel_msg_new:nnnn { kernel } { unbalanced-quote-in-filename }
14537 { Unbalanced~quotes~in~file~name~'#1'. }
14538 {
14539   File~names~must~contain~balanced~numbers~of~quotes~(").
14540 }
14541 \__kernel_msg_new:nnnn { kernel } { iow-indent }
14542 { Only~#1 (arg-1)~allows~#2 }
14543 {
14544   The~command~#2 can~only~be~used~in~messages~
14545   which~will~be~wrapped~using~#1.
14546   \tl_if_empty:nF {#3} { ~ It~was~called~with~argument~'#3'. }
14547 }

```

20.7 Functions delayed from earlier modules

<@@=sys>

\c_sys_platform_str Detecting the platform on LuaTeX is easy: for other engines, we use the fact that the two common cases have special null files. It is possible to probe further (see package `platform`), but that requires shell escape and seems unlikely to be useful. This is set up here as it requires file searching.

```

14548 \sys_if_engine luatex:TF
14549 {
14550   \str_const:Nx \c_sys_platform_str
14551   { \tex_directlua:D { tex.print(os.type) } }
14552 }
14553 {
14554   \file_if_exist:nTF { nul: }
14555   {
14556     \file_if_exist:nF { /dev/null }
14557     { \str_const:Nn \c_sys_platform_str { windows } }
14558   }
14559   {
14560     \file_if_exist:nT { /dev/null }
14561     { \str_const:Nn \c_sys_platform_str { unix } }
14562   }
14563 }
14564 \cs_if_exist:NF \c_sys_platform_str
14565 { \str_const:Nn \c_sys_platform_str { unknown } }

```

(End definition for `\c_sys_platform_str`. This variable is documented on page 115.)

```

\sys_if_platform_unix_p: We can now set up the tests.
\sys_if_platform_unix:TF 14566 \clist_map_inline:nn { unix , windows }
\sys_if_platform_windows_p: 14567 {
\sys_if_platform_windows:TF 14568   \__file_const:nn { sys_if_platform_ #1 }
                             14569   { \str_if_eq_p:Vn \c_sys_platform_str { #1 } }
                             14570 }

```

(End definition for `\sys_if_platform_unix:TF` and `\sys_if_platform_windows:TF`. These functions are documented on page 115.)

```
14571 \</initex | package>
```

21 l3skip implementation

```
14572 \<*initex | package>
```

```
14573 \<@@=dim>
```

21.1 Length primitives renamed

```

\if_dim:w Primitives renamed.
\__dim_eval:w 14574 \cs_new_eq:NN \if_dim:w \tex_ifdim:D
\__dim_eval_end: 14575 \cs_new_eq:NN \__dim_eval:w \tex_dimexpr:D
                  14576 \cs_new_eq:NN \__dim_eval_end: \tex_relax:D

```

(End definition for `\if_dim:w`, `__dim_eval:w`, and `__dim_eval_end:`. This function is documented on page 182.)

21.2 Internal auxiliaries

```

\s__dim_mark Internal scan marks.
\s__dim_stop 14577 \scan_new:N \s__dim_mark
              14578 \scan_new:N \s__dim_stop

```

(End definition for `\s__dim_mark` and `\s__dim_stop`.)

```

\__dim_use_none_delimit_by_s_stop:w Functions to gobble up to a scan mark.
14579 \cs_new:Npn \__dim_use_none_delimit_by_s_stop:w #1 \s__dim_stop { }

```

(End definition for `__dim_use_none_delimit_by_s_stop:w`.)

21.3 Creating and initialising dim variables

```

\dim_new:N Allocating <dim> registers ...
\dim_new:c 14580 \<*package>
           14581 \cs_new_protected:Npn \dim_new:N #1
           14582 {
           14583   \__kernel_chk_if_free_cs:N #1
           14584   \cs:w newdimen \cs_end: #1
           14585 }
           14586 \</package>
           14587 \cs_generate_variant:Nn \dim_new:N { c }

```

(End definition for `\dim_new:N`. This function is documented on page 168.)

\dim_const:Nn Contrarily to integer constants, we cannot avoid using a register, even for constants. We cannot use **\dim_gset:Nn** because debugging code would complain that the constant is not a global variable. Since **\dim_const:Nn** does not need to be fast, use **\dim_eval:n** to avoid needing a debugging patch that wraps the expression in checking code.

```

14588 \cs_new_protected:Npn \dim_const:Nn #1#2
14589 {
14590   \dim_new:N #1
14591   \tex_global:D #1 ~ \dim_eval:n {#2} \scan_stop:
14592 }
14593 \cs_generate_variant:Nn \dim_const:Nn { c }

```

(End definition for **\dim_const:Nn**. This function is documented on page 168.)

\dim_zero:N Reset the register to zero. Using **\c_zero_skip** deals with the case where the variable passed is incorrectly a skip (for example a L^AT_EX 2_ε length).

```

14594 \cs_new_protected:Npn \dim_zero:N #1 { #1 \c_zero_skip }
14595 \cs_new_protected:Npn \dim_gzero:N #1
14596 { \tex_global:D #1 \c_zero_skip }
14597 \cs_generate_variant:Nn \dim_zero:N { c }
14598 \cs_generate_variant:Nn \dim_gzero:N { c }

```

(End definition for **\dim_zero:N** and **\dim_gzero:N**. These functions are documented on page 168.)

\dim_zero_new:N Create a register if needed, otherwise clear it.

```

14599 \cs_new_protected:Npn \dim_zero_new:N #1
14600 { \dim_if_exist:NTF #1 { \dim_zero:N #1 } { \dim_new:N #1 } }
14601 \cs_new_protected:Npn \dim_gzero_new:N #1
14602 { \dim_if_exist:NTF #1 { \dim_gzero:N #1 } { \dim_new:N #1 } }
14603 \cs_generate_variant:Nn \dim_zero_new:N { c }
14604 \cs_generate_variant:Nn \dim_gzero_new:N { c }

```

(End definition for **\dim_zero_new:N** and **\dim_gzero_new:N**. These functions are documented on page 168.)

\dim_if_exist_p:N Copies of the **cs** functions defined in l3basics.

```

14605 \prg_new_eq_conditional:Nnn \dim_if_exist:N \cs_if_exist:N
14606 { TF , T , F , p }
14607 \prg_new_eq_conditional:Nnn \dim_if_exist:c \cs_if_exist:c
14608 { TF , T , F , p }

```

(End definition for **\dim_if_exist:NTF**. This function is documented on page 168.)

21.4 Setting dim variables

\dim_set:Nn Setting dimensions is easy enough but when debugging we want both to check that the variable is correctly local/global and to wrap the expression in some code. The **\scan_stop:** deals with the case where the variable passed is a skip (for example a L^AT_EX 2_ε length).

```

14609 \cs_new_protected:Npn \dim_set:Nn #1#2
14610 { #1 ~ \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
14611 \cs_new_protected:Npn \dim_gset:Nn #1#2
14612 { \tex_global:D #1 ~ \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
14613 \cs_generate_variant:Nn \dim_set:Nn { c }
14614 \cs_generate_variant:Nn \dim_gset:Nn { c }

```


(End definition for `\dim_set:Nn` and `\dim_gset:Nn`. These functions are documented on page 169.)

```

\dim_set_eq:NN All straightforward, with a \scan_stop: to deal with the case where #1 is (incorrectly)
\dim_set_eq:cN a skip.
\dim_set_eq:Nc 14615 \cs_new_protected:Npn \dim_set_eq:NN #1#2
\dim_set_eq:cc 14616 { #1 = #2 \scan_stop: }
\dim_gset_eq:NN 14617 \cs_generate_variant:Nn \dim_set_eq:NN { c , Nc , cc }
\dim_gset_eq:cN 14618 \cs_new_protected:Npn \dim_gset_eq:NN #1#2
\dim_gset_eq:Nc 14619 { \tex_global:D #1 = #2 \scan_stop: }
\dim_gset_eq:cc 14620 \cs_generate_variant:Nn \dim_gset_eq:NN { c , Nc , cc }

```

(End definition for `\dim_set_eq:NN` and `\dim_gset_eq:NN`. These functions are documented on page 169.)

```

\dim_add:Nn Using by here deals with the (incorrect) case \dimen123. Using \scan_stop: deals with
\dim_add:cN skip variables. Since debugging checks that the variable is correctly local/global, the
\dim_gadd:Nn global versions cannot be defined as \tex_global:D followed by the local versions. The
\dim_gadd:cN debugging code is inserted by \__dim_tmp:w.
\dim_sub:Nn 14621 \cs_new_protected:Npn \dim_add:Nn #1#2
\dim_sub:cN 14622 { \tex_advance:D #1 by \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
\dim_gsub:Nn 14623 \cs_new_protected:Npn \dim_gadd:Nn #1#2
\dim_gsub:cN 14624 {
14625 \tex_global:D \tex_advance:D #1 by
14626 \__dim_eval:w #2 \__dim_eval_end: \scan_stop:
14627 }
14628 \cs_generate_variant:Nn \dim_add:Nn { c }
14629 \cs_generate_variant:Nn \dim_gadd:Nn { c }
14630 \cs_new_protected:Npn \dim_sub:Nn #1#2
14631 { \tex_advance:D #1 by - \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
14632 \cs_new_protected:Npn \dim_gsub:Nn #1#2
14633 {
14634 \tex_global:D \tex_advance:D #1 by
14635 -\__dim_eval:w #2 \__dim_eval_end: \scan_stop:
14636 }
14637 \cs_generate_variant:Nn \dim_sub:Nn { c }
14638 \cs_generate_variant:Nn \dim_gsub:Nn { c }

```

(End definition for `\dim_add:Nn` and others. These functions are documented on page 169.)

21.5 Utilities for dimension calculations

```

\dim_abs:n Functions for min, max, and absolute value with only one evaluation. The absolute value
\__dim_abs:N is evaluated by removing a leading - if present.
\dim_max:nn 14639 \cs_new:Npn \dim_abs:n #1
\dim_min:nn 14640 {
\__dim_maxmin:wwN 14641 \exp_after:wN \__dim_abs:N
14642 \dim_use:N \__dim_eval:w #1 \__dim_eval_end:
14643 }
14644 \cs_new:Npn \__dim_abs:N #1
14645 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
14646 \cs_new:Npn \dim_max:nn #1#2
14647 {
14648 \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
14649 \dim_use:N \__dim_eval:w #1 \exp_after:wN ;

```

```

14650     \dim_use:N \__dim_eval:w #2 ;
14651     >
14652     \__dim_eval_end:
14653   }
14654 \cs_new:Npn \dim_min:nn #1#2
14655 {
14656   \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
14657   \dim_use:N \__dim_eval:w #1 \exp_after:wN ;
14658   \dim_use:N \__dim_eval:w #2 ;
14659   <
14660   \__dim_eval_end:
14661 }
14662 \cs_new:Npn \__dim_maxmin:wwN #1 ; #2 ; #3
14663 {
14664   \if_dim:w #1 #3 #2 ~
14665     #1
14666   \else:
14667     #2
14668   \fi:
14669 }

```

(End definition for `\dim_abs:n` and others. These functions are documented on page 169.)

`\dim_ratio:nn` With dimension expressions, something like `10 pt * (5 pt / 10 pt)` does not work. **`__dim_ratio:n`** Instead, the ratio part needs to be converted to an integer expression. Using `\int_value:w` forces everything into `sp`, avoiding any decimal parts.

```

14670 \cs_new:Npn \dim_ratio:nn #1#2
14671 { \__dim_ratio:n {#1} / \__dim_ratio:n {#2} }
14672 \cs_new:Npn \__dim_ratio:n #1
14673 { \int_value:w \__dim_eval:w (#1) \__dim_eval_end: }

```

(End definition for `\dim_ratio:nn` and `__dim_ratio:n`. This function is documented on page 170.)

21.6 Dimension expression conditionals

`\dim_compare_p:nNn` Simple comparison.

`\dim_compare:nNnTF`

```

14674 \prg_new_conditional:Npnn \dim_compare:nNn #1#2#3 { p , T , F , TF }
14675 {
14676   \if_dim:w \__dim_eval:w #1 #2 \__dim_eval:w #3 \__dim_eval_end:
14677   \prg_return_true: \else: \prg_return_false: \fi:
14678 }

```

(End definition for `\dim_compare:nNnTF`. This function is documented on page 170.)

`\dim_compare_p:n` This code is adapted from the `\int_compare:nTF` function. First make sure that there is at least one relation operator, by evaluating a dimension expression with a trailing `__dim_compare_error:..` Just like for integers, the looping auxiliary `__dim_compare:wNN` closes a primitive conditional and opens a new one. It is actually easier to grab a dimension operand than an integer one, because once evaluated, dimensions all end with `pt` (with category other). Thus we do not need specific auxiliaries for the three “simple” relations `<`, `=`, and `>`.

`\dim_compare:nTF`

```

\__dim_compare:w
\__dim_compare:wNN
\__dim_compare:=:w
\__dim_compare!:w
\__dim_compare<:w
\__dim_compare>:w
\__dim_compare_error:
14679 \prg_new_conditional:Npnn \dim_compare:n #1 { p , T , F , TF }
14680 {
14681   \exp_after:wN \__dim_compare:w

```

```

14682 \dim_use:N \__dim_eval:w #1 \__dim_compare_error:
14683 }
14684 \cs_new:Npn \__dim_compare:w #1 \__dim_compare_error:
14685 {
14686 \exp_after:wN \if_false: \exp:w \exp_end_continue_f:w
14687 \__dim_compare:wNN #1 ? { = \__dim_compare_end:w \else: } \s__dim_stop
14688 }
14689 \exp_args:Nno \use:nn
14690 { \cs_new:Npn \__dim_compare:wNN #1 } { \tl_to_str:n {pt} #2#3 }
14691 {
14692 \if_meaning:w = #3
14693 \use:c { __dim_compare_#2:w }
14694 \fi:
14695 #1 pt \exp_stop_f:
14696 \prg_return_false:
14697 \exp_after:wN \__dim_use_none_delimit_by_s_stop:w
14698 \fi:
14699 \reverse_if:N \if_dim:w #1 pt #2
14700 \exp_after:wN \__dim_compare:wNN
14701 \dim_use:N \__dim_eval:w #3
14702 }
14703 \cs_new:cpn { __dim_compare_! :w }
14704 #1 \reverse_if:N #2 ! #3 = { #1 #2 = #3 }
14705 \cs_new:cpn { __dim_compare_ = :w }
14706 #1 \__dim_eval:w = { #1 \__dim_eval:w }
14707 \cs_new:cpn { __dim_compare_ < :w }
14708 #1 \reverse_if:N #2 < #3 = { #1 #2 > #3 }
14709 \cs_new:cpn { __dim_compare_ > :w }
14710 #1 \reverse_if:N #2 > #3 = { #1 #2 < #3 }
14711 \cs_new:Npn \__dim_compare_end:w #1 \prg_return_false: #2 \s__dim_stop
14712 { #1 \prg_return_false: \else: \prg_return_true: \fi: }
14713 \cs_new_protected:Npn \__dim_compare_error:
14714 {
14715 \if_int_compare:w \c_zero_int \c_zero_int \fi:
14716 =
14717 \__dim_compare_error:
14718 }

```

(End definition for `\dim_compare:nTF` and others. This function is documented on page 171.)

`\dim_case:nn` For dimension cases, the first task to fully expand the check condition. The over all idea is then much the same as for `\str_case:nn(TF)` as described in l3basics.

`\dim_case:nnTF`

```

14719 \cs_new:Npn \dim_case:nnTF #1
14720 {
14721 \exp:w
14722 \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} }
14723 }
14724 \cs_new:Npn \dim_case:nnT #1#2#3
14725 {
14726 \exp:w
14727 \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} } {#2} {#3} { }
14728 }
14729 \cs_new:Npn \dim_case:nnF #1#2
14730 {

```

```

14731     \exp:w
14732     \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} } {#2} { }
14733   }
14734   \cs_new:Npn \dim_case:nn #1#2
14735   {
14736     \exp:w
14737     \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} } {#2} { } { }
14738   }
14739   \cs_new:Npn \__dim_case:nnTF #1#2#3#4
14740   { \__dim_case:nw {#1} #2 {#1} { } \s__dim_mark {#3} \s__dim_mark {#4} \s__dim_stop }
14741   \cs_new:Npn \__dim_case:nw #1#2#3
14742   {
14743     \dim_compare:nNnTF {#1} = {#2}
14744     { \__dim_case_end:nw {#3} }
14745     { \__dim_case:nw {#1} }
14746   }
14747   \cs_new:Npn \__dim_case_end:nw #1#2#3 \s__dim_mark #4#5 \s__dim_stop
14748   { \exp_end: #1 #4 }

```

(End definition for `\dim_case:nnTF` and others. This function is documented on page [172](#).)

21.7 Dimension expression loops

`\dim_while_do:nn` `while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

\dim_until_do:nn
\dim_do_while:nn
\dim_do_until:nn
14749 \cs_new:Npn \dim_while_do:nn #1#2
14750 {
14751   \dim_compare:nT {#1}
14752   {
14753     #2
14754     \dim_while_do:nn {#1} {#2}
14755   }
14756 }
14757 \cs_new:Npn \dim_until_do:nn #1#2
14758 {
14759   \dim_compare:nF {#1}
14760   {
14761     #2
14762     \dim_until_do:nn {#1} {#2}
14763   }
14764 }
14765 \cs_new:Npn \dim_do_while:nn #1#2
14766 {
14767   #2
14768   \dim_compare:nT {#1}
14769   { \dim_do_while:nn {#1} {#2} }
14770 }
14771 \cs_new:Npn \dim_do_until:nn #1#2
14772 {
14773   #2
14774   \dim_compare:nF {#1}
14775   { \dim_do_until:nn {#1} {#2} }
14776 }

```

(End definition for `\dim_while_do:nN` and others. These functions are documented on page 173.)

`\dim_while_do:nNnn` `while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

14777 \cs_new:Npn \dim_while_do:nNnn #1#2#3#4
14778 {
14779   \dim_compare:nNnT {#1} #2 {#3}
14780   {
14781     #4
14782     \dim_while_do:nNnn {#1} #2 {#3} {#4}
14783   }
14784 }
14785 \cs_new:Npn \dim_until_do:nNnn #1#2#3#4
14786 {
14787   \dim_compare:nNnF {#1} #2 {#3}
14788   {
14789     #4
14790     \dim_until_do:nNnn {#1} #2 {#3} {#4}
14791   }
14792 }
14793 \cs_new:Npn \dim_do_while:nNnn #1#2#3#4
14794 {
14795   #4
14796   \dim_compare:nNnT {#1} #2 {#3}
14797   { \dim_do_while:nNnn {#1} #2 {#3} {#4} }
14798 }
14799 \cs_new:Npn \dim_do_until:nNnn #1#2#3#4
14800 {
14801   #4
14802   \dim_compare:nNnF {#1} #2 {#3}
14803   { \dim_do_until:nNnn {#1} #2 {#3} {#4} }
14804 }

```

(End definition for `\dim_while_do:nNnn` and others. These functions are documented on page 173.)

21.8 Dimension step functions

`\dim_step_function:nnnN` Before all else, evaluate the initial value, step, and final value. Repeating a function by steps first needs a check on the direction of the steps. After that, do the function for the start value then step and loop around. It would be more symmetrical to test for a step size of zero before checking the sign, but we optimize for the most frequent case (positive step).

```

\__dim_step:wwwN
\__dim_step:NnnnN

14805 \cs_new:Npn \dim_step_function:nnnN #1#2#3
14806 {
14807   \exp_after:wN \__dim_step:wwwN
14808   \tex_the:D \__dim_eval:w #1 \exp_after:wN ;
14809   \tex_the:D \__dim_eval:w #2 \exp_after:wN ;
14810   \tex_the:D \__dim_eval:w #3 ;
14811 }
14812 \cs_new:Npn \__dim_step:wwwN #1; #2; #3; #4
14813 {
14814   \dim_compare:nNnTF {#2} > \c_zero_dim
14815   { \__dim_step:NnnnN > }

```

```

14816     {
14817         \dim_compare:nNnTF {#2} = \c_zero_dim
14818         {
14819             \__kernel_msg_expandable_error:nnn { kernel } { zero-step } {#4}
14820             \use_none:nnnn
14821         }
14822         { \__dim_step:NnnnN < }
14823     }
14824     {#1} {#2} {#3} #4
14825 }
14826 \cs_new:Npn \__dim_step:NnnnN #1#2#3#4#5
14827 {
14828     \dim_compare:nNf {#2} #1 {#4}
14829     {
14830         #5 {#2}
14831         \exp_args:NNf \__dim_step:NnnnN
14832         #1 { \dim_eval:n { #2 + #3 } } {#3} {#4} #5
14833     }
14834 }

```

(End definition for `\dim_step_function:nnnN`, `__dim_step:wwwN`, and `__dim_step:NnnnN`. This function is documented on page 173.)

`\dim_step_inline:nnnn`
`\dim_step_variable:nnnNn`
`__dim_step:NNnnnn`

The approach here is to build a function, with a global integer required to make the nesting safe (as seen in other in line functions), and map that function using `\dim_step_function:nnnN`. We put a `\prg_break_point:Nn` so that `map_break` functions from other modules correctly decrement `\g__kernel_prg_map_int` before looking for their own break point. The first argument is `\scan_stop:`, so that no breaking function recognizes this break point as its own.

```

14835 \cs_new_protected:Npn \dim_step_inline:nnnn
14836 {
14837     \int_gincr:N \g__kernel_prg_map_int
14838     \exp_args:NNc \__dim_step:NNnnnn
14839     \cs_gset_protected:Npn
14840     { __dim_map_ \int_use:N \g__kernel_prg_map_int :w }
14841 }
14842 \cs_new_protected:Npn \dim_step_variable:nnnNn #1#2#3#4#5
14843 {
14844     \int_gincr:N \g__kernel_prg_map_int
14845     \exp_args:NNc \__dim_step:NNnnnn
14846     \cs_gset_protected:Npx
14847     { __dim_map_ \int_use:N \g__kernel_prg_map_int :w }
14848     {#1}{#2}{#3}
14849     {
14850         \tl_set:Nn \exp_not:N #4 {##1}
14851         \exp_not:n {#5}
14852     }
14853 }
14854 \cs_new_protected:Npn \__dim_step:NNnnnn #1#2#3#4#5#6
14855 {
14856     #1 #2 ##1 {#6}
14857     \dim_step_function:nnnN {#3} {#4} {#5} #2
14858     \prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__kernel_prg_map_int }
14859 }

```

(End definition for `\dim_step_inline:nnnn`, `\dim_step_variable:nnnNm`, and `_dim_step:NNnnnn`. These functions are documented on page 173.)

21.9 Using dim expressions and variables

`\dim_eval:n` Evaluating a dimension expression expandably.

```
14860 \cs_new:Npn \dim_eval:n #1
14861 { \dim_use:N \_dim_eval:w #1 \_dim_eval_end: }
```

(End definition for `\dim_eval:n`. This function is documented on page 174.)

`\dim_sign:n` See `\dim_abs:n`. Contrarily to `\int_sign:n` the case of a zero dimension cannot be distinguished from a positive dimension by looking only at the first character, since `0.2pt` and `0pt` start the same way. We need explicit comparisons. We start by distinguishing the most common case of a positive dimension.

```
14862 \cs_new:Npn \dim_sign:n #1
14863 {
14864   \int_value:w \exp_after:wN \_dim_sign:Nw
14865   \dim_use:N \_dim_eval:w #1 \_dim_eval_end: ;
14866   \exp_stop_f:
14867 }
14868 \cs_new:Npn \_dim_sign:Nw #1#2 ;
14869 {
14870   \if_dim:w #1#2 > \c_zero_dim
14871     1
14872   \else:
14873     \if_meaning:w - #1
14874       -1
14875     \else:
14876       0
14877     \fi:
14878   \fi:
14879 }
```

(End definition for `\dim_sign:n` and `_dim_sign:Nw`. This function is documented on page 174.)

`\dim_use:N` Accessing a $\langle dim \rangle$.

`\dim_use:c` `\cs_new_eq:NN \dim_use:N \tex_the:D`

We hand-code this for some speed gain:

```
14881 %\cs_generate_variant:Nn \dim_use:N { c }
14882 \cs_new:Npn \dim_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }
```

(End definition for `\dim_use:N`. This function is documented on page 174.)

`\dim_to_decimal:n` A function which comes up often enough to deserve a place in the kernel. Evaluate the dimension expression `#1` then remove the trailing `pt`. When debugging is enabled, the argument is put in parentheses as this prevents the dimension expression from terminating early and leaving extra tokens lying around. This is used a lot by low-level manipulations.

```
14883 \cs_new:Npn \dim_to_decimal:n #1
14884 {
14885   \exp_after:wN
14886   \_dim_to_decimal:w \dim_use:N \_dim_eval:w #1 \_dim_eval_end:
14887 }
```

```

14888 \use:x
14889 {
14890   \cs_new:Npn \exp_not:N \_dim_to_decimal:w
14891     ##1 . ##2 \tl_to_str:n { pt }
14892 }
14893 {
14894   \int_compare:nNnTF {#2} > { 0 }
14895     { #1 . #2 }
14896     { #1 }
14897 }

```

(End definition for `\dim_to_decimal:n` and `_dim_to_decimal:w`. This function is documented on page 174.)

`\dim_to_decimal_in_bp:n` Conversion to big points is done using a scaling inside `_dim_eval:w` as ε -TEX does that using 64-bit precision. Here, 800/803 is the integer fraction for 72/72.27. This is a common case so is hand-coded for accuracy (and speed).

```

14898 \cs_new:Npn \dim_to_decimal_in_bp:n #1
14899 { \dim_to_decimal:n { ( #1 ) * 800 / 803 } }

```

(End definition for `\dim_to_decimal_in_bp:n`. This function is documented on page 175.)

`\dim_to_decimal_in_sp:n` Another hard-coded conversion: this one is necessary to avoid things going off-scale.

```

14900 \cs_new:Npn \dim_to_decimal_in_sp:n #1
14901 { \int_value:w \_dim_eval:w #1 \_dim_eval_end: }

```

(End definition for `\dim_to_decimal_in_sp:n`. This function is documented on page 175.)

`\dim_to_decimal_in_unit:nn` An analogue of `\dim_ratio:nn` that produces a decimal number as its result, rather than a rational fraction for use within dimension expressions.

```

14902 \cs_new:Npn \dim_to_decimal_in_unit:nn #1#2
14903 {
14904   \dim_to_decimal:n
14905   {
14906     1pt *
14907     \dim_ratio:nn {#1} {#2}
14908   }
14909 }

```

(End definition for `\dim_to_decimal_in_unit:nn`. This function is documented on page 175.)

`\dim_to_fp:n` Defined in `l3fp-convert`, documented here.

(End definition for `\dim_to_fp:n`. This function is documented on page 175.)

21.10 Viewing dim variables

`\dim_show:N` Diagnostics.

```

\dim_show:c 14910 \cs_new_eq:NN \dim_show:N \_kernel_register_show:N
14911 \cs_generate_variant:Nn \dim_show:N { c }

```

(End definition for `\dim_show:N`. This function is documented on page 175.)

\dim_show:n Diagnostics. We don't use the TeX primitive `\showthe` to show dimension expressions: this gives a more unified output.

```
14912 \cs_new_protected:Npn \dim_show:n
14913 { \msg_show_eval:Nn \dim_eval:n }
```

(End definition for `\dim_show:n`. This function is documented on page 176.)

\dim_log:N Diagnostics. Redirect output of `\dim_show:n` to the log.

```
\dim_log:c 14914 \cs_new_eq:NN \dim_log:N \__kernel_register_log:N
\dim_log:n 14915 \cs_new_eq:NN \dim_log:c \__kernel_register_log:c
14916 \cs_new_protected:Npn \dim_log:n
14917 { \msg_log_eval:Nn \dim_eval:n }
```

(End definition for `\dim_log:N` and `\dim_log:n`. These functions are documented on page 176.)

21.11 Constant dimensions

\c_zero_dim Constant dimensions.

```
\c_max_dim 14918 \dim_const:Nn \c_zero_dim { 0 pt }
14919 \dim_const:Nn \c_max_dim { 16383.99999 pt }
```

(End definition for `\c_zero_dim` and `\c_max_dim`. These variables are documented on page 176.)

21.12 Scratch dimensions

\l_tmpa_dim We provide two local and two global scratch registers, maybe we need more or less.

```
\l_tmpb_dim 14920 \dim_new:N \l_tmpa_dim
\g_tmpa_dim 14921 \dim_new:N \l_tmpb_dim
\g_tmpb_dim 14922 \dim_new:N \g_tmpa_dim
14923 \dim_new:N \g_tmpb_dim
```

(End definition for `\l_tmpa_dim` and others. These variables are documented on page 176.)

21.13 Creating and initialising skip variables

```
14924 <@@=skip>
```

\s_skip_stop Internal scan marks.

```
14925 \scan_new:N \s_skip_stop
```

(End definition for `\s_skip_stop`.)

\skip_new:N Allocation of a new internal registers.

```
\skip_new:c 14926 <*package>
14927 \cs_new_protected:Npn \skip_new:N #1
14928 {
14929   \__kernel_chk_if_free_cs:N #1
14930   \cs:w newskip \cs_end: #1
14931 }
14932 </package>
14933 \cs_generate_variant:Nn \skip_new:N { c }
```

(End definition for `\skip_new:N`. This function is documented on page 176.)

\skip_const:Nn Contrarily to integer constants, we cannot avoid using a register, even for constants. See **\skip_const:cn** **\dim_const:Nn** for why we cannot use **\skip_gset:Nn**.

```

14934 \cs_new_protected:Npn \skip_const:Nn #1#2
14935 {
14936   \skip_new:N #1
14937   \tex_global:D #1 ~ \skip_eval:n {#2} \scan_stop:
14938 }
14939 \cs_generate_variant:Nn \skip_const:Nn { c }

```

(End definition for **\skip_const:Nn**. This function is documented on page 177.)

\skip_zero:N Reset the register to zero.

```

\skip_zero:c 14940 \cs_new_protected:Npn \skip_zero:N #1 { #1 \c_zero_skip }
\skip_gzero:N 14941 \cs_new_protected:Npn \skip_gzero:N #1 { \tex_global:D #1 \c_zero_skip }
\skip_gzero:c 14942 \cs_generate_variant:Nn \skip_zero:N { c }
14943 \cs_generate_variant:Nn \skip_gzero:N { c }

```

(End definition for **\skip_zero:N** and **\skip_gzero:N**. These functions are documented on page 177.)

\skip_zero_new:N Create a register if needed, otherwise clear it.

```

\skip_zero_new:c 14944 \cs_new_protected:Npn \skip_zero_new:N #1
\skip_gzero_new:N 14945 { \skip_if_exist:NTF #1 { \skip_zero:N #1 } { \skip_new:N #1 } }
\skip_gzero_new:c 14946 \cs_new_protected:Npn \skip_gzero_new:N #1
14947 { \skip_if_exist:NTF #1 { \skip_gzero:N #1 } { \skip_new:N #1 } }
14948 \cs_generate_variant:Nn \skip_zero_new:N { c }
14949 \cs_generate_variant:Nn \skip_gzero_new:N { c }

```

(End definition for **\skip_zero_new:N** and **\skip_gzero_new:N**. These functions are documented on page 177.)

\skip_if_exist_p:N Copies of the **cs** functions defined in **l3basics**.

```

\skip_if_exist_p:c 14950 \prg_new_eq_conditional:NNn \skip_if_exist:N \cs_if_exist:N
\skip_if_exist:NTF 14951 { TF , T , F , p }
\skip_if_exist:cTF 14952 \prg_new_eq_conditional:NNn \skip_if_exist:c \cs_if_exist:c
14953 { TF , T , F , p }

```

(End definition for **\skip_if_exist:NTF**. This function is documented on page 177.)

21.14 Setting skip variables

\skip_set:Nn Much the same as for dimensions.

```

\skip_set:cn 14954 \cs_new_protected:Npn \skip_set:Nn #1#2
\skip_gset:Nn 14955 { #1 ~ \tex_glueexpr:D #2 \scan_stop: }
\skip_gset:cn 14956 \cs_new_protected:Npn \skip_gset:Nn #1#2
14957 { \tex_global:D #1 ~ \tex_glueexpr:D #2 \scan_stop: }
14958 \cs_generate_variant:Nn \skip_set:Nn { c }
14959 \cs_generate_variant:Nn \skip_gset:Nn { c }

```

(End definition for **\skip_set:Nn** and **\skip_gset:Nn**. These functions are documented on page 177.)

\skip_set_eq:NN All straightforward.

```

\skip_set_eq:cn 14960 \cs_new_protected:Npn \skip_set_eq:NN #1#2 { #1 = #2 }
\skip_set_eq:Nc 14961 \cs_generate_variant:Nn \skip_set_eq:NN { c , Nc , cc }
\skip_set_eq:cc 14962 \cs_new_protected:Npn \skip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\skip_gset_eq:cn 14963 \cs_generate_variant:Nn \skip_gset_eq:NN { c , Nc , cc }
\skip_gset_eq:Nc
\skip_gset_eq:cc

```

(End definition for `\skip_set_eq:Nn` and `\skip_gset_eq:Nn`. These functions are documented on page 177.)

```

\skip_add:Nn Using by here deals with the (incorrect) case \skip123.
\skip_add:cn 14964 \cs_new_protected:Npn \skip_add:Nn #1#2
\skip_gadd:Nn 14965 { \tex_advance:D #1 by \tex_glueexpr:D #2 \scan_stop: }
\skip_gadd:cn 14966 \cs_new_protected:Npn \skip_gadd:Nn #1#2
\skip_sub:Nn 14967 { \tex_global:D \tex_advance:D #1 by \tex_glueexpr:D #2 \scan_stop: }
\skip_sub:cn 14968 \cs_generate_variant:Nn \skip_add:Nn { c }
\skip_gsub:Nn 14969 \cs_generate_variant:Nn \skip_gadd:Nn { c }
\skip_gsub:cn 14970 \cs_new_protected:Npn \skip_sub:Nn #1#2
14971 { \tex_advance:D #1 by - \tex_glueexpr:D #2 \scan_stop: }
14972 \cs_new_protected:Npn \skip_gsub:Nn #1#2
14973 { \tex_global:D \tex_advance:D #1 by - \tex_glueexpr:D #2 \scan_stop: }
14974 \cs_generate_variant:Nn \skip_sub:Nn { c }
14975 \cs_generate_variant:Nn \skip_gsub:Nn { c }

```

(End definition for `\skip_add:Nn` and others. These functions are documented on page 177.)

21.15 Skip expression conditionals

`\skip_if_eq_p:nn` Comparing skips means doing two expansions to make strings, and then testing them.
`\skip_if_eq:nnTF` As a result, only equality is tested.

```

14976 \prg_new_conditional:Npnn \skip_if_eq:nn #1#2 { p , T , F , TF }
14977 {
14978   \str_if_eq:eeTF { \skip_eval:n { #1 } } { \skip_eval:n { #2 } }
14979   { \prg_return_true: }
14980   { \prg_return_false: }
14981 }

```

(End definition for `\skip_if_eq:nnTF`. This function is documented on page 178.)

`\skip_if_finite_p:n` With ε -TeX, we have an easy access to the order of infinities of the stretch and shrink components of a skip. However, to access both, we either need to evaluate the expression twice, or evaluate it, then call an auxiliary to extract both pieces of information from the result. Since we are going to need an auxiliary anyways, it is quicker to make it search for the string `fil` which characterizes infinite glue.
`\skip_if_finite:nTF`
`__skip_if_finite:wwNw`

```

14982 \cs_set_protected:Npn \__skip_tmp:w #1
14983 {
14984   \prg_new_conditional:Npnn \skip_if_finite:n ##1 { p , T , F , TF }
14985   {
14986     \exp_after:wN \__skip_if_finite:wwNw
14987     \skip_use:N \tex_glueexpr:D ##1 ; \prg_return_false:
14988     #1 ; \prg_return_true: \s__skip_stop
14989   }
14990   \cs_new:Npn \__skip_if_finite:wwNw ##1 #1 ##2 ; ##3 ##4 \s__skip_stop {##3}
14991 }
14992 \exp_args:No \__skip_tmp:w { \tl_to_str:n { fil } }

```

(End definition for `\skip_if_finite:nTF` and `__skip_if_finite:wwNw`. This function is documented on page 178.)

21.16 Using skip expressions and variables

`\skip_eval:n` Evaluating a skip expression expandably.

```
14993 \cs_new:Npn \skip_eval:n #1
14994 { \skip_use:N \tex_glueexpr:D #1 \scan_stop: }
```

(End definition for `\skip_eval:n`. This function is documented on page 178.)

`\skip_use:N` Accessing a `\skip`.

```
\skip_use:c
14995 \cs_new_eq:NN \skip_use:N \tex_the:D
14996 %\cs_generate_variant:Nn \skip_use:N { c }
14997 \cs_new:Npn \skip_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }
```

(End definition for `\skip_use:N`. This function is documented on page 178.)

21.17 Inserting skips into the output

`\skip_horizontal:N` Inserting skips.

```
\skip_horizontal:c
14998 \cs_new_eq:NN \skip_horizontal:N \tex_hskip:D
\skip_horizontal:n
14999 \cs_new:Npn \skip_horizontal:n #1
\skip_vertical:N
15000 { \skip_horizontal:N \tex_glueexpr:D #1 \scan_stop: }
\skip_vertical:c
15001 \cs_new_eq:NN \skip_vertical:N \tex_vskip:D
\skip_vertical:n
15002 \cs_new:Npn \skip_vertical:n #1
15003 { \skip_vertical:N \tex_glueexpr:D #1 \scan_stop: }
15004 \cs_generate_variant:Nn \skip_horizontal:N { c }
15005 \cs_generate_variant:Nn \skip_vertical:N { c }
```

(End definition for `\skip_horizontal:N` and others. These functions are documented on page 179.)

21.18 Viewing skip variables

`\skip_show:N` Diagnostics.

```
\skip_show:c
15006 \cs_new_eq:NN \skip_show:N \__kernel_register_show:N
15007 \cs_generate_variant:Nn \skip_show:N { c }
```

(End definition for `\skip_show:N`. This function is documented on page 178.)

`\skip_show:n` Diagnostics. We don't use the TeX primitive `\showthe` to show skip expressions: this gives a more unified output.

```
15008 \cs_new_protected:Npn \skip_show:n
15009 { \msg_show_eval:Nn \skip_eval:n }
```

(End definition for `\skip_show:n`. This function is documented on page 178.)

`\skip_log:N` Diagnostics. Redirect output of `\skip_show:n` to the log.

```
\skip_log:c
15010 \cs_new_eq:NN \skip_log:N \__kernel_register_log:N
\skip_log:n
15011 \cs_new_eq:NN \skip_log:c \__kernel_register_log:c
15012 \cs_new_protected:Npn \skip_log:n
15013 { \msg_log_eval:Nn \skip_eval:n }
```

(End definition for `\skip_log:N` and `\skip_log:n`. These functions are documented on page 179.)

21.19 Constant skips

`\c_zero_skip` Skips with no rubber component are just dimensions but need to terminate correctly.

```
\c_max_skip 15014 \skip_const:Nn \c_zero_skip { \c_zero_dim }
15015 \skip_const:Nn \c_max_skip { \c_max_dim }
```

(End definition for `\c_zero_skip` and `\c_max_skip`. These functions are documented on page 179.)

21.20 Scratch skips

`\l_tmpa_skip` We provide two local and two global scratch registers, maybe we need more or less.

```
\l_tmpb_skip 15016 \skip_new:N \l_tmpa_skip
\g_tmpa_skip 15017 \skip_new:N \l_tmpb_skip
\g_tmpb_skip 15018 \skip_new:N \g_tmpa_skip
15019 \skip_new:N \g_tmpb_skip
```

(End definition for `\l_tmpa_skip` and others. These variables are documented on page 179.)

21.21 Creating and initialising muskip variables

`\muskip_new:N` And then we add muskips.

```
\muskip_new:c 15020 {*package}
15021 \cs_new_protected:Npn \muskip_new:N #1
15022 {
15023   \__kernel_chk_if_free_cs:N #1
15024   \cs:w newmuskip \cs_end: #1
15025 }
15026 \package}
15027 \cs_generate_variant:Nn \muskip_new:N { c }
```

(End definition for `\muskip_new:N`. This function is documented on page 180.)

`\muskip_const:Nn` See `\skip_const:Nn`.

```
\muskip_const:cn 15028 \cs_new_protected:Npn \muskip_const:Nn #1#2
15029 {
15030   \muskip_new:N #1
15031   \tex_global:D #1 ~ \muskip_eval:n {#2} \scan_stop:
15032 }
15033 \cs_generate_variant:Nn \muskip_const:Nn { c }
```

(End definition for `\muskip_const:Nn`. This function is documented on page 180.)

`\muskip_zero:N` Reset the register to zero.

```
\muskip_zero:c 15034 \cs_new_protected:Npn \muskip_zero:N #1
\muskip_gzero:N 15035 { #1 \c_zero_muskip }
\muskip_gzero:c 15036 \cs_new_protected:Npn \muskip_gzero:N #1
15037 { \tex_global:D #1 \c_zero_muskip }
15038 \cs_generate_variant:Nn \muskip_zero:N { c }
15039 \cs_generate_variant:Nn \muskip_gzero:N { c }
```

(End definition for `\muskip_zero:N` and `\muskip_gzero:N`. These functions are documented on page 180.)

`\muskip_zero_new:N` Create a register if needed, otherwise clear it.

```

\muskip_zero_new:c 15040 \cs_new_protected:Npn \muskip_zero_new:N #1
\muskip_gzero_new:N 15041 { \muskip_if_exist:NTF #1 { \muskip_zero:N #1 } { \muskip_new:N #1 } }
\muskip_gzero_new:c 15042 \cs_new_protected:Npn \muskip_gzero_new:N #1
15043 { \muskip_if_exist:NTF #1 { \muskip_gzero:N #1 } { \muskip_new:N #1 } }
15044 \cs_generate_variant:Nn \muskip_zero_new:N { c }
15045 \cs_generate_variant:Nn \muskip_gzero_new:N { c }

(End definition for \muskip_zero_new:N and \muskip_gzero_new:N. These functions are documented on
page 180.)

```

`\muskip_if_exist_p:N` Copies of the cs functions defined in l3basics.

```

\muskip_if_exist_p:c 15046 \prg_new_eq_conditional:NNn \muskip_if_exist:N \cs_if_exist:N
\muskip_if_exist:NTF 15047 { TF , T , F , p }
\muskip_if_exist:cTF 15048 \prg_new_eq_conditional:NNn \muskip_if_exist:c \cs_if_exist:c
15049 { TF , T , F , p }

(End definition for \muskip_if_exist:NTF. This function is documented on page 180.)

```

21.22 Setting muskip variables

`\muskip_set:Nn` This should be pretty familiar.

```

\muskip_set:cn 15050 \cs_new_protected:Npn \muskip_set:Nn #1#2
\muskip_gset:Nn 15051 { #1 ~ \tex_muexpr:D #2 \scan_stop: }
\muskip_gset:cn 15052 \cs_new_protected:Npn \muskip_gset:Nn #1#2
15053 { \tex_global:D #1 ~ \tex_muexpr:D #2 \scan_stop: }
15054 \cs_generate_variant:Nn \muskip_set:Nn { c }
15055 \cs_generate_variant:Nn \muskip_gset:Nn { c }

(End definition for \muskip_set:Nn and \muskip_gset:Nn. These functions are documented on page
181.)

```

`\muskip_set_eq:NN` All straightforward.

```

\muskip_set_eq:cN 15056 \cs_new_protected:Npn \muskip_set_eq:NN #1#2 { #1 = #2 }
\muskip_set_eq:Nc 15057 \cs_generate_variant:Nn \muskip_set_eq:NN { c , Nc , cc }
\muskip_set_eq:cc 15058 \cs_new_protected:Npn \muskip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\muskip_gset_eq:NN 15059 \cs_generate_variant:Nn \muskip_gset_eq:NN { c , Nc , cc }
\muskip_gset_eq:cN
\muskip_gset_eq:Nc
\muskip_gset_eq:cc

(End definition for \muskip_set_eq:NN and \muskip_gset_eq:NN. These functions are documented on
page 181.)

```

`\muskip_add:Nn` Using by here deals with the (incorrect) case `\muskip123`.

```

\muskip_add:cn 15060 \cs_new_protected:Npn \muskip_add:Nn #1#2
\muskip_gadd:Nn 15061 { \tex_advance:D #1 by \tex_muexpr:D #2 \scan_stop: }
\muskip_gadd:cn 15062 \cs_new_protected:Npn \muskip_gadd:Nn #1#2
\muskip_sub:Nn 15063 { \tex_global:D \tex_advance:D #1 by \tex_muexpr:D #2 \scan_stop: }
\muskip_sub:cn 15064 \cs_generate_variant:Nn \muskip_add:Nn { c }
\muskip_gsub:Nn 15065 \cs_generate_variant:Nn \muskip_gadd:Nn { c }
\muskip_gsub:cn 15066 \cs_new_protected:Npn \muskip_sub:Nn #1#2
15067 { \tex_advance:D #1 by - \tex_muexpr:D #2 \scan_stop: }
15068 \cs_new_protected:Npn \muskip_gsub:Nn #1#2
15069 { \tex_global:D \tex_advance:D #1 by - \tex_muexpr:D #2 \scan_stop: }
15070 \cs_generate_variant:Nn \muskip_sub:Nn { c }
15071 \cs_generate_variant:Nn \muskip_gsub:Nn { c }

(End definition for \muskip_add:Nn and others. These functions are documented on page 180.)

```

21.23 Using muskip expressions and variables

\muskip_eval:n Evaluating a muskip expression expandably.

```
15072 \cs_new:Npn \muskip_eval:n #1
15073 { \muskip_use:N \tex_muexpr:D #1 \scan_stop: }
```

(End definition for \muskip_eval:n. This function is documented on page 181.)

\muskip_use:N Accessing a $\langle muskip \rangle$.

\muskip_use:c

```
15074 \cs_new_eq:NN \muskip_use:N \tex_the:D
15075 \cs_generate_variant:Nn \muskip_use:N { c }
```

(End definition for \muskip_use:N. This function is documented on page 181.)

21.24 Viewing muskip variables

\muskip_show:N Diagnostics.

\muskip_show:c

```
15076 \cs_new_eq:NN \muskip_show:N \__kernel_register_show:N
15077 \cs_generate_variant:Nn \muskip_show:N { c }
```

(End definition for \muskip_show:N. This function is documented on page 181.)

\muskip_show:n Diagnostics. We don't use the TeX primitive \showthe to show muskip expressions: this gives a more unified output.

```
15078 \cs_new_protected:Npn \muskip_show:n
15079 { \msg_show_eval:Nn \muskip_eval:n }
```

(End definition for \muskip_show:n. This function is documented on page 182.)

\muskip_log:N Diagnostics. Redirect output of \muskip_show:n to the log.

\muskip_log:c

\muskip_log:n

```
15080 \cs_new_eq:NN \muskip_log:N \__kernel_register_log:N
15081 \cs_new_eq:NN \muskip_log:c \__kernel_register_log:c
15082 \cs_new_protected:Npn \muskip_log:n
15083 { \msg_log_eval:Nn \muskip_eval:n }
```

(End definition for \muskip_log:N and \muskip_log:n. These functions are documented on page 182.)

21.25 Constant muskips

\c_zero_muskip Constant muskips given by their value.

\c_max_muskip

```
15084 \muskip_const:Nn \c_zero_muskip { 0 mu }
15085 \muskip_const:Nn \c_max_muskip { 16383.99999 mu }
```

(End definition for \c_zero_muskip and \c_max_muskip. These functions are documented on page 182.)

21.26 Scratch muskips

\l_tmpa_muskip We provide two local and two global scratch registers, maybe we need more or less.

\l_tmpb_muskip

\g_tmpa_muskip

\g_tmpb_muskip

```
15086 \muskip_new:N \l_tmpa_muskip
15087 \muskip_new:N \l_tmpb_muskip
15088 \muskip_new:N \g_tmpa_muskip
15089 \muskip_new:N \g_tmpb_muskip
```

(End definition for \l_tmpa_muskip and others. These variables are documented on page 182.)

```
15090 </initex | package>
```

22 l3keys Implementation

15091 <(*initex | package)

22.1 Low-level interface

The low-level key parser’s implementation is based heavily on `expkv`. Compared to `keyval` it adds a number of additional “safety” requirements and allows to process the parsed list of key–value pairs in a variety of ways. The net result is that this code needs around one and a half the amount of time as `keyval` to parse the same list of keys. To optimise speed as far as reasonably practical, a number of lower-level approaches are taken rather than using the higher-level `expl3` interfaces.

15092 <@@=keyval>

```
\s__keyval_nil
\s__keyval_mark
\s__keyval_stop
\s__keyval_tail
15093 \scan_new:N \s__keyval_nil
15094 \scan_new:N \s__keyval_mark
15095 \scan_new:N \s__keyval_stop
15096 \scan_new:N \s__keyval_tail
```

(End definition for `\s__keyval_nil` and others.)

This temporary macro will be used since some of the definitions will need an active comma or equals sign. Inside of this macro `#1` will be the active comma and `#2` will be the active equals sign.

```
15097 \group_begin:
15098   \cs_set_protected:Npn \__keyval_tmp:NN #1#2
15099   {
```

\keyval_parse:NNn The main function starts the first of two loops. The outer loop splits the key–value list at active commas, the inner loop will do so at other commas. The use of `\s__keyval_mark` here prevents loss of braces from the key argument.

```
15100   \cs_new:Npn \keyval_parse:NNn ##1 ##2 ##3
15101   { \__keyval_loop_active:NNw ##1 ##2 \s__keyval_mark ##3 #1 \s__keyval_tail #1 }
```

(End definition for `\keyval_parse:NNn`. This function is documented on page 195.)

__keyval_loop_active:NNw First a fast test for the end of the loop is done, it’ll gobble everything up to a `\s__keyval_tail`. The loop ending macro will gobble everything to the last `\s__keyval_mark` in this definition. If the end isn’t reached yet, start the second loop splitting at other commas, and after that one iterate the current loop.

```
15102   \cs_new:Npn \__keyval_loop_active:NNw ##1 ##2 ##3 #1
15103   {
15104     \__keyval_if_recursion_tail:w ##3
15105     \__keyval_end_loop_active:w \s__keyval_tail
15106     \__keyval_loop_other:NNw ##1 ##2 ##3 , \s__keyval_tail ,
15107     \__keyval_loop_active:NNw ##1 ##2 \s__keyval_mark
15108   }
```

(End definition for `__keyval_loop_active:NNw`.)

`__keyval_split_other:w` These two macros allow to split at the first equals sign of category 12 or 13. At the same time they also execute branching by inserting the first token following `\s__keyval_mark` that followed the equals sign. Hence they also test for the presence of such an equals sign simultaneously.

```

15109     \cs_new:Npn \__keyval_split_other:w ##1 = ##2 \s__keyval_mark ##3 ##4 \s__keyval_stop
15110     { ##3 ##1 \s__keyval_stop \s__keyval_mark ##2 }
15111     \cs_new:Npn \__keyval_split_active:w ##1 #2 ##2 \s__keyval_mark ##3 ##4 \s__keyval_stop
15112     { ##3 ##1 \s__keyval_stop \s__keyval_mark ##2 }

```

(End definition for `__keyval_split_other:w` and `__keyval_split_active:w`.)

`__keyval_loop_other:NNw` The second loop uses the same test for its end as the first loop, next it splits at the first active equals sign using `__keyval_split_active:w`. The `\s__keyval_nil` prevents accidental brace stripping and acts as a delimiter in the next steps. First testing for an active equals sign will reduce the number of necessary expansion steps for the expected average use case of other equals signs and hence perform better on average.

```

15113     \cs_new:Npn \__keyval_loop_other:NNw ##1 ##2 ##3 ,
15114     {
15115         \__keyval_if_recursion_tail:w ##3
15116         \__keyval_end_loop_other:w \s__keyval_tail
15117         \__keyval_split_active:w ##3 \s__keyval_nil
15118         \s__keyval_mark \__keyval_split_active_auxi:w
15119         #2 \s__keyval_mark \__keyval_clean_up_active:w
15120         \s__keyval_stop
15121         ##1 ##2
15122         \__keyval_loop_other:NNw ##1 ##2 \s__keyval_mark
15123     }

```

(End definition for `__keyval_loop_other:NNw`.)

`__keyval_split_active_auxi:w` After `__keyval_split_active:w` the following will only be called if there was at least one active equals sign in the current key–value pair. Therefore this is the execution branch for a key–value pair with an active equals sign. `##1` will be everything up to the first active equals sign. First it tests for other equals signs in the key name, which will eventually throw an error via `__keyval_misplaced_equal_after_active_error:w`. If none was found we forward the key to `__keyval_split_active_auxii:w`.

```

15124     \cs_new:Npn \__keyval_split_active_auxi:w ##1 \s__keyval_stop
15125     {
15126         \__keyval_split_other:w ##1 \s__keyval_nil
15127         \s__keyval_mark \__keyval_misplaced_equal_after_active_error:w
15128         = \s__keyval_mark \__keyval_split_active_auxii:w
15129         \s__keyval_stop
15130     }

```

`__keyval_split_active_auxii:w` gets the correct key name with a leading `\s__keyval_mark` as `##1`. It has to sanitise the remainder of the previous test and trims the key name which will be forwarded to `__keyval_split_active_auxiii:w`.

```

15131     \cs_new:Npn \__keyval_split_active_auxii:w
15132     ##1 \s__keyval_nil \s__keyval_mark \__keyval_misplaced_equal_after_active_error:w
15133     \s__keyval_stop \s__keyval_mark
15134     { \__keyval_trim:nN { ##1 } \__keyval_split_active_auxiii:w }

```

Next we test for a misplaced active equals sign in the value, if none is found `__keyval_split_active_auxiv:w` will be called.

```

15135 \cs_new:Npn \__keyval_split_active_auxiii:w ##1 ##2 \s__keyval_nil
15136 {
15137     \__keyval_split_active:w ##2 \s__keyval_nil
15138     \s__keyval_mark \__keyval_misplaced_equal_in_split_error:w
15139     #2 \s__keyval_mark \__keyval_split_active_auxiv:w
15140     \s__keyval_stop
15141     { ##1 }
15142 }

```

This runs the last test after sanitising the remainder of the previous one. This time test for a misplaced equals sign of category 12 in the value. Finally the last auxiliary macro will be called.

```

15143 \cs_new:Npn \__keyval_split_active_auxiv:w
15144     ##1 \s__keyval_nil \s__keyval_mark \__keyval_misplaced_equal_in_split_error:w
15145     \s__keyval_stop \s__keyval_mark
15146 {
15147     \__keyval_split_other:w ##1 \s__keyval_nil
15148     \s__keyval_mark \__keyval_misplaced_equal_in_split_error:w
15149     = \s__keyval_mark \__keyval_split_active_auxv:w
15150     \s__keyval_stop
15151 }

```

This last macro in this execution branch sanitises the last test, trims the value and passes it to `__keyval_pair:nnNN`.

```

15152 \cs_new:Npn \__keyval_split_active_auxv:w
15153     ##1 \s__keyval_nil \s__keyval_mark \__keyval_misplaced_equal_in_split_error:w
15154     \s__keyval_stop \s__keyval_mark
15155     { \__keyval_trim:nN { ##1 } \__keyval_pair:nnNN }

```

(End definition for __keyval_split_active_auxi:w and others.)

`__keyval_clean_up_active:w` The following is the branch taken if the key-value pair doesn't contain an active equals sign. The remainder of that test will be cleaned up by `__keyval_clean_up_active:w` which will then split at an equals sign of category other.

```

15156 \cs_new:Npn \__keyval_clean_up_active:w
15157     ##1 \s__keyval_nil \s__keyval_mark \__keyval_split_active_auxi:w \s__keyval_stop
15158 {
15159     \__keyval_split_other:w ##1 \s__keyval_nil
15160     \s__keyval_mark \__keyval_split_other_auxi:w
15161     = \s__keyval_mark \__keyval_clean_up_other:w
15162     \s__keyval_stop
15163 }

```

(End definition for __keyval_clean_up_active:w.)

`__keyval_split_other_auxi:w` This is executed if the key-value pair doesn't contain an active equals sign but at least one other. `##1` of `__keyval_split_other_auxi:w` will contain the complete key name, which is trimmed and forwarded to the next auxiliary macro.

```

\__keyval_split_other_auxii:w
\__keyval_split_other_auxiii:w
15164 \cs_new:Npn \__keyval_split_other_auxi:w ##1 \s__keyval_stop
15165     { \__keyval_trim:nN { ##1 } \__keyval_split_other_auxii:w }

```

We know that the value doesn't contain misplaced active equals signs but we have to test for others.

```

15166     \cs_new:Npn \__keyval_split_other_auxii:w ##1 ##2 \s__keyval_nil
15167     {
15168         \__keyval_split_other:w ##2 \s__keyval_nil
15169         \s__keyval_mark \__keyval_misplaced_equal_in_split_error:w
15170         = \s__keyval_mark \__keyval_split_other_auxiii:w
15171         \s__keyval_stop
15172         { ##1 }
15173     }

```

__keyval_split_other_auxiii:w sanitises the test for other equals signs, trims the value and forwards it to __keyval_pair:nnNN.

```

15174     \cs_new:Npn \__keyval_split_other_auxiii:w
15175     ##1 \s__keyval_nil \s__keyval_mark \__keyval_misplaced_equal_in_split_error:w
15176     \s__keyval_stop \s__keyval_mark
15177     { \__keyval_trim:nN { ##1 } \__keyval_pair:nnNN }

```

(End definition for __keyval_split_other_auxi:w, __keyval_split_other_auxii:w, and __keyval_split_other_auxiii:w.)

__keyval_clean_up_other:w __keyval_clean_up_other:w is the last branch that might exist. It is called if no equals sign was found, hence the only possibilities left are a blank list element, which is to be skipped, or a lonely key. If it's no empty list element this will trim the key name and forward it to __keyval_key:nnN.

```

15178     \cs_new:Npn \__keyval_clean_up_other:w
15179     ##1 \s__keyval_nil \s__keyval_mark \__keyval_split_other_auxi:w \s__keyval_stop \
15180     {
15181         \__keyval_if_blank:w ##1 \s__keyval_nil \s__keyval_stop \__keyval_blank_true:w
15182         \s__keyval_mark \s__keyval_stop \use:n
15183         { \__keyval_trim:nN { ##1 } \__keyval_key:nnN }
15184     }

```

(End definition for __keyval_clean_up_other:w.)

__keyval_misplaced_equal_after_active_error:w All these two macros do is gobble the remainder of the current other loop execution and throw an error.

```

\__keyval_misplaced_equal_in_split_error:w
15185     \cs_new:Npn \__keyval_misplaced_equal_after_active_error:w
15186     \s__keyval_mark ##1 \s__keyval_stop \s__keyval_mark ##2 \s__keyval_nil
15187     \s__keyval_mark ##3 \s__keyval_nil ##4 ##5
15188     {
15189         \__kernel_msg_expandable_error:nn
15190         { kernel } { misplaced-equals-sign }
15191     }
15192     \cs_new:Npn \__keyval_misplaced_equal_in_split_error:w
15193     \s__keyval_mark ##1 \s__keyval_stop \s__keyval_mark ##2 \s__keyval_nil
15194     ##3 ##4 ##5
15195     {
15196         \__kernel_msg_expandable_error:nn
15197         { kernel } { misplaced-equals-sign }
15198     }

```

(End definition for __keyval_misplaced_equal_after_active_error:w and __keyval_misplaced_equal_in_split_error:w.)

```

\__keyval_end_loop_other:w
\__keyval_end_loop_active:w

```

All that's left for the parsing loops are the macros which end the recursion. Both just gobble the remaining tokens of the respective loop including the next recursion call.

```

15199 \cs_new:Npn \__keyval_end_loop_other:w
15200 \s__keyval_tail
15201 \__keyval_split_active:w ##1 \s__keyval_nil
15202 \s__keyval_mark \__keyval_split_active_auxi:w
15203 #2 \s__keyval_mark \__keyval_clean_up_active:w
15204 \s__keyval_stop
15205 ##2 ##3
15206 \__keyval_loop_other:NNw ##4 \s__keyval_mark
15207 { }
15208 \cs_new:Npn \__keyval_end_loop_active:w
15209 \s__keyval_tail
15210 \__keyval_loop_other:NNw ##1 , \s__keyval_tail ,
15211 \__keyval_loop_active:NNw ##2 \s__keyval_mark
15212 { }

```

(End definition for __keyval_end_loop_other:w and __keyval_end_loop_active:w.)

The parsing loops are done, so here ends the definition of __keyval_tmp:NN, which will finally set up the macros.

```

15213 }
15214 \char_set_catcode_active:n { '\, }
15215 \char_set_catcode_active:n { '\= }
15216 \__keyval_tmp:NN , =
15217 \group_end:

```

```

\__keyval_pair:nnNN
\__keyval_key:nNN

```

These macros will be called on the parsed keys and values of the key-value list. All arguments are completely trimmed. They test for blank key names and call the functions passed to \keyval_parse:NNn inside of \exp_not:n with the correct arguments.

```

15218 \cs_new:Npn \__keyval_pair:nnNN #1 #2 #3 #4
15219 {
15220 \__keyval_if_blank:w \s__keyval_mark #2 \s__keyval_nil \s__keyval_stop \__keyval_blank_
15221 \s__keyval_mark \s__keyval_stop
15222 \exp_not:n { #4 { #2 } { #1 } }
15223 }
15224 \cs_new:Npn \__keyval_key:nNN #1 #2 #3
15225 {
15226 \__keyval_if_blank:w \s__keyval_mark #1 \s__keyval_nil \s__keyval_stop \__keyval_blank_
15227 \s__keyval_mark \s__keyval_stop
15228 \exp_not:n { #2 { #1 } }
15229 }

```

(End definition for __keyval_pair:nnNN and __keyval_key:nNN.)

```

\__keyval_if_empty:w
\__keyval_if_blank:w
\__keyval_if_recursion_tail:w

```

All these tests work by gobbling tokens until a certain combination is met, which makes them pretty fast. The test for a blank argument should be called with an arbitrary token following the argument. Each of these utilize the fact that the argument will contain a leading \s__keyval_mark.

```

15230 \cs_new:Npn \__keyval_if_empty:w #1 \s__keyval_mark \s__keyval_stop { }
15231 \cs_new:Npn \__keyval_if_blank:w \s__keyval_mark #1 { \__keyval_if_empty:w \s__keyval_mark
15232 \cs_new:Npn \__keyval_if_recursion_tail:w \s__keyval_mark #1 \s__keyval_tail { }

```

(End definition for __keyval_if_empty:w, __keyval_if_blank:w, and __keyval_if_recursion_tail:w.)

```

    \__keyval_blank_true:w
    \__keyval_blank_key_error:w

```

These macros will be called if the tests above didn't gobble them, they execute the branching.

```

15233 \cs_new:Npn \__keyval_blank_true:w \s__keyval_mark \s__keyval_stop \use:n #1 #2 #3 { }
15234 \cs_new:Npn \__keyval_blank_key_error:w \s__keyval_mark \s__keyval_stop \exp_not:n #1
15235 {
15236     \__kernel_msg_expandable_error:nn
15237     { kernel } { blank-key-name }
15238 }

```

(End definition for __keyval_blank_true:w and __keyval_blank_key_error:w.)

Two messages for the low level parsing system.

```

15239 \__kernel_msg_new:nnn { kernel } { misplaced-equals-sign }
15240 { Misplaced-equals-sign-in-key-value-input~\msg_line_context: }
15241 \__kernel_msg_new:nnn { kernel } { blank-key-name }
15242 { Blank-key~name~in-key-value-input~\msg_line_context: }

```

```

    \__keyval_trim:nN
    \__keyval_trim_auxi:w
    \__keyval_trim_auxii:w
    \__keyval_trim_auxiii:w
    \__keyval_trim_auxiv:w

```

And an adapted version of __tl_trim_spaces:nn which is a bit faster for our use case, as it can strip the braces at the end. This is pretty much the same concept, so I won't comment on it here. The speed gain by using this instead of \tl_trim_spaces_apply:nN is about 10 % of the total time for \keyval_parse:NNn with one key and one key-value pair, so I think it's worth it.

```

15243 \group_begin:
15244     \cs_set_protected:Npn \__keyval_tmp:n #1
15245     {
15246         \cs_new:Npn \__keyval_trim:nN ##1
15247         {
15248             \__keyval_trim_auxi:w
15249             ##1
15250             \s__keyval_nil
15251             \s__keyval_mark #1 { }
15252             \s__keyval_mark \__keyval_trim_auxii:w
15253             \__keyval_trim_auxiii:w
15254             #1 \s__keyval_nil
15255             \__keyval_trim_auxiv:w
15256             \s__keyval_stop
15257         }
15258         \cs_new:Npn \__keyval_trim_auxi:w ##1 \s__keyval_mark #1 ##2 \s__keyval_mark ##3
15259         {
15260             ##3
15261             \__keyval_trim_auxi:w
15262             \s__keyval_mark
15263             ##2
15264             \s__keyval_mark #1 {##1}
15265         }
15266         \cs_new:Npn \__keyval_trim_auxii:w \__keyval_trim_auxi:w \s__keyval_mark \s__keyval_m
15267         {
15268             \__keyval_trim_auxiii:w
15269             ##1
15270         }
15271         \cs_new:Npn \__keyval_trim_auxiii:w ##1 #1 \s__keyval_nil ##2
15272         {
15273             ##2
15274             ##1 \s__keyval_nil

```

```

15275         \__keyval_trim_auxiii:w
15276     }

```

This is the one macro which differs from the original definition.

```

15277         \cs_new:Npn \__keyval_trim_auxiv:w \s__keyval_mark ##1 \s__keyval_nil ##2 \s__keyval_
15278             { ##3 { ##1 } }
15279     }
15280     \__keyval_tmp:n { ~ }
15281 \group_end:

```

(End definition for __keyval_trim:nN and others.)

22.2 Constants and variables

```

15282 <@@=keys>

```

Various storage areas for the different data which make up keys.

```

\c__keys_code_root_str
\c__keys_default_root_str
\c__keys_groups_root_str
\c__keys_inherit_root_str
\c__keys_type_root_str
\c__keys_validate_root_str
15283 \str_const:Nn \c__keys_code_root_str { key-code~>~ }
15284 \str_const:Nn \c__keys_default_root_str { key-default~>~ }
15285 \str_const:Nn \c__keys_groups_root_str { key-groups~>~ }
15286 \str_const:Nn \c__keys_inherit_root_str { key-inherit~>~ }
15287 \str_const:Nn \c__keys_type_root_str { key-type~>~ }
15288 \str_const:Nn \c__keys_validate_root_str { key-validate~>~ }

```

(End definition for \c__keys_code_root_str and others.)

\c__keys_props_root_str The prefix for storing properties.

```

15289 \str_const:Nn \c__keys_props_root_str { key-prop~>~ }

```

(End definition for \c__keys_props_root_str.)

\l_keys_choice_int **\l_keys_choice_tl** Publicly accessible data on which choice is being used when several are generated as a set.

```

15290 \int_new:N \l_keys_choice_int
15291 \tl_new:N \l_keys_choice_tl

```

(End definition for \l_keys_choice_int and \l_keys_choice_tl. These variables are documented on page 189.)

\l__keys_groups_clist Used for storing and recovering the list of groups which apply to a key: set as a comma list but at one point we have to use this for a token list recovery.

```

15292 \clist_new:N \l__keys_groups_clist

```

(End definition for \l__keys_groups_clist.)

\l_keys_key_str **\l_keys_key_tl** The name of a key itself: needed when setting keys. The tl version is deprecated but has to be handled manually.

```

15293 \str_new:N \l_keys_key_str
15294 \tl_new:N \l_keys_key_tl

```

(End definition for \l_keys_key_str and \l_keys_key_tl. These variables are documented on page 191.)

\l__keys_module_str The module for an entire set of keys.

```

15295 \str_new:N \l__keys_module_str

```

(End definition for `\l__keys_module_str`.)

`\l__keys_no_value_bool` A marker is needed internally to show if only a key or a key plus a value was seen: this is recorded here.

15296 `\bool_new:N \l__keys_no_value_bool`

(End definition for `\l__keys_no_value_bool`.)

`\l__keys_only_known_bool` Used to track if only “known” keys are being set.

15297 `\bool_new:N \l__keys_only_known_bool`

(End definition for `\l__keys_only_known_bool`.)

`\l_keys_path_str` The “path” of the current key is stored here: this is available to the programmer and so is public. The older version is deprecated but has to be handled manually.

`\l_keys_path_tl`

15298 `\str_new:N \l_keys_path_str`
15299 `\tl_new:N \l_keys_path_tl`

(End definition for `\l_keys_path_str` and `\l_keys_path_tl`. These variables are documented on page 191.)

`\l__keys_inherit_str`

15300 `\str_new:N \l__keys_inherit_str`

(End definition for `\l__keys_inherit_str`.)

`\l__keys_relative_tl` The relative path for passing keys back to the user. As this can be explicitly no-value, it must be a token list.

15301 `\tl_new:N \l__keys_relative_tl`
15302 `\tl_set:Nn \l__keys_relative_tl { \q__keys_no_value }`

(End definition for `\l__keys_relative_tl`.)

`\l__keys_property_str` The “property” begin set for a key at definition time is stored here.

15303 `\str_new:N \l__keys_property_str`

(End definition for `\l__keys_property_str`.)

`\l__keys_selective_bool` Two flags for using key groups: one to indicate that “selective” setting is active, a second to specify which type (“opt-in” or “opt-out”).

`\l__keys_filtered_bool`

15304 `\bool_new:N \l__keys_selective_bool`
15305 `\bool_new:N \l__keys_filtered_bool`

(End definition for `\l__keys_selective_bool` and `\l__keys_filtered_bool`.)

`\l__keys_selective_seq` The list of key groups being filtered in or out during selective setting.

15306 `\seq_new:N \l__keys_selective_seq`

(End definition for `\l__keys_selective_seq`.)

`\l__keys_unused_clist` Used when setting only some keys to store those left over.

15307 `\tl_new:N \l__keys_unused_clist`

(End definition for `\l__keys_unused_clist`.)

`\l_keys_value_tl` The value given for a key: may be empty if no value was given.
15308 `\tl_new:N \l_keys_value_tl`
(End definition for `\l_keys_value_tl`. This variable is documented on page 191.)

`\l__keys_tmp_bool` Scratch space.
`\l__keys_tmpa_tl` 15309 `\bool_new:N \l__keys_tmp_bool`
`\l__keys_tmpb_tl` 15310 `\tl_new:N \l__keys_tmpa_tl`
15311 `\tl_new:N \l__keys_tmpb_tl`
(End definition for `\l__keys_tmp_bool`, `\l__keys_tmpa_tl`, and `\l__keys_tmpb_tl`.)

22.2.1 Internal auxiliaries

`\s__keys_stop` Internal scan marks.
15312 `\scan_new:N \s__keys_stop`
(End definition for `\s__keys_stop`.)

`\q__keys_nil` Internal quarks.
`\q__keys_no_value` 15313 `\quark_new:N \q__keys_nil`
15314 `\quark_new:N \q__keys_no_value`
(End definition for `\q__keys_nil` and `\q__keys_no_value`.)

`__keys_quark_if_nil_p:n` Branching quark conditional.
`__keys_quark_if_nil:nTF` 15315 `__kernel_quark_new_conditional:Nn __keys_quark_if_nil:n { TF }`
15316 `__kernel_quark_new_conditional:Nn __keys_quark_if_no_value:N { TF }`
(End definition for `__keys_quark_if_nil:nTF`.)

`\q__keys_recursion_tail` Internal recursion quarks.
`\q__keys_recursion_stop` 15317 `\quark_new:N \q__keys_recursion_tail`
15318 `\quark_new:N \q__keys_recursion_stop`
(End definition for `\q__keys_recursion_tail` and `\q__keys_recursion_stop`.)

`_keys_if_recursion_tail_stop:n` Functions to query recursion quarks.
15319 `__kernel_quark_new_test:N _keys_if_recursion_tail_stop:n`
(End definition for `_keys_if_recursion_tail_stop:n`.)

22.3 The key defining mechanism

`\keys_define:nn` The public function for definitions is just a wrapper for the lower level mechanism, more or less. The outer function is designed to keep a track of the current module, to allow safe nesting. The module is set removing any leading / (which is not needed here).

```

15320 \cs_new_protected:Npn \keys_define:nn
15321 { \__keys_define:onn \l__keys_module_str }
15322 \cs_new_protected:Npn \__keys_define:nnn #1#2#3
15323 {
15324   \str_set:Nx \l__keys_module_str { \__keys_trim_spaces:n {#2} }
15325   \keyval_parse:NNn \__keys_define:n \__keys_define:nn {#3}
15326   \str_set:Nn \l__keys_module_str {#1}
15327 }
15328 \cs_generate_variant:Nn \__keys_define:nnn { o }

```

(End definition for `\keys_define:nn` and `__keys_define:nnn`. This function is documented on page 184.)

`__keys_define:n` The outer functions here record whether a value was given and then converge on a common internal mechanism. There is first a search for a property in the current key name, then a check to make sure it is known before the code hands off to the next step.

```

15329 \cs_new_protected:Npn \__keys_define:n #1
15330 {
15331   \bool_set_true:N \l__keys_no_value_bool
15332   \__keys_define_aux:nn {#1} { }
15333 }
15334 \cs_new_protected:Npn \__keys_define:nn #1#2
15335 {
15336   \bool_set_false:N \l__keys_no_value_bool
15337   \__keys_define_aux:nn {#1} {#2}
15338 }
15339 \cs_new_protected:Npn \__keys_define_aux:nn #1#2
15340 {
15341   \__keys_property_find:n {#1}
15342   \cs_if_exist:cTF { \c__keys_props_root_str \l__keys_property_str }
15343   { \__keys_define_code:n {#2} }
15344   {
15345     \str_if_empty:NF \l__keys_property_str
15346     {
15347       \__kernel_msg_error:nnxx { kernel } { key-property-unknown }
15348       { \l__keys_property_str } { \l_keys_path_str }
15349     }
15350   }
15351 }

```

(End definition for `__keys_define:n`, `__keys_define:nn`, and `__keys_define_aux:nn`.)

`__keys_property_find:n` Searching for a property means finding the last . in the input, and storing the text before and after it. Everything is turned into strings, so there is no problem using an x-type expansion.

```

15352 \cs_new_protected:Npn \__keys_property_find:n #1
15353 {
15354   \str_set:Nx \l__keys_property_str { \__keys_trim_spaces:n {#1} }
15355   \exp_after:wN \__keys_property_find:w \l__keys_property_str . .

```

```

15356     \s__keys_stop {#1}
15357 }
15358 \cs_new_protected:Npn \__keys_property_find:w #1 . #2 . #3 \s__keys_stop #4
15359 {
15360     \tl_if_blank:nTF {#3}
15361     {
15362         \str_clear:N \l__keys_property_str
15363         \__kernel_msg_error:nnn { kernel } { key-no-property } {#4}
15364     }
15365     {
15366         \str_if_eq:nnTF {#3} { . }
15367         {
15368             \str_set:Nx \l_keys_path_str
15369             {
15370                 \str_if_empty:NF \l__keys_module_str
15371                 { \l__keys_module_str / }
15372                 \tl_trim_spaces:n {#1}
15373             }
15374             \str_set:Nn \l__keys_property_str { . #2 }
15375         }
15376         {
15377             \str_set:Nx \l_keys_path_str { \l__keys_module_str / #1 . #2 }
15378             \__keys_property_search:w #3 \s__keys_stop
15379         }
15380         \tl_set_eq:NN \l_keys_path_tl \l_keys_path_str
15381     }
15382 }
15383 \cs_new_protected:Npn \__keys_property_search:w #1 . #2 \s__keys_stop
15384 {
15385     \str_if_eq:nnTF {#2} { . }
15386     {
15387         \str_set:Nx \l_keys_path_str { \l_keys_path_str }
15388         \str_set:Nn \l__keys_property_str { . #1 }
15389     }
15390     {
15391         \str_set:Nx \l_keys_path_str { \l_keys_path_str . #1 }
15392         \__keys_property_search:w #2 \s__keys_stop
15393     }
15394 }

```

(End definition for __keys_property_find:n and __keys_property_find:w.)

__keys_define_code:n Two possible cases. If there is a value for the key, then just use the function. If not, then
 __keys_define_code:w a check to make sure there is no need for a value with the property. If there should be
 one then complain, otherwise execute it. There is no need to check for a : as if it was
 missing the earlier tests would have failed.

```

15395 \cs_new_protected:Npn \__keys_define_code:n #1
15396 {
15397     \bool_if:NTF \l__keys_no_value_bool
15398     {
15399         \exp_after:wN \__keys_define_code:w
15400         \l__keys_property_str \s__keys_stop
15401         { \use:c { \c__keys_props_root_str \l__keys_property_str } }
15402     }

```

```

15403         \__kernel_msg_error:nxxx { kernel }
15404         { key-property-requires-value } { \l__keys_property_str }
15405         { \l_keys_path_str }
15406     }
15407 }
15408 { \use:c { \c__keys_props_root_str \l__keys_property_str } {#1} }
15409 }
15410 \exp_last_unbraced:NNNNo
15411 \cs_new:Npn \__keys_define_code:w #1 \c_colon_str #2 \s__keys_stop
15412 { \tl_if_empty:nTF {#2} }

```

(End definition for __keys_define_code:n and __keys_define_code:w.)

22.4 Turning properties into actions

__keys_bool_set:Nn Boolean keys are really just choices, but all done by hand. The second argument here is the scope: either empty or `g` for global.

```

15413 \cs_new_protected:Npn \__keys_bool_set:Nn #1#2
15414 {
15415     \bool_if_exist:NF #1 { \bool_new:N #1 }
15416     \__keys_choice_make:
15417     \__keys_cmd_set:nx { \l_keys_path_str / true }
15418     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
15419     \__keys_cmd_set:nx { \l_keys_path_str / false }
15420     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
15421     \__keys_cmd_set:nn { \l_keys_path_str / unknown }
15422     {
15423         \__kernel_msg_error:nxx { kernel } { boolean-values-only }
15424         { \l_keys_key_str }
15425     }
15426     \__keys_default_set:n { true }
15427 }
15428 \cs_generate_variant:Nn \__keys_bool_set:Nn { c }

```

(End definition for __keys_bool_set:Nn.)

__keys_bool_set_inverse:Nn Inverse boolean setting is much the same.

```

15429 \cs_new_protected:Npn \__keys_bool_set_inverse:Nn #1#2
15430 {
15431     \bool_if_exist:NF #1 { \bool_new:N #1 }
15432     \__keys_choice_make:
15433     \__keys_cmd_set:nx { \l_keys_path_str / true }
15434     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
15435     \__keys_cmd_set:nx { \l_keys_path_str / false }
15436     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
15437     \__keys_cmd_set:nn { \l_keys_path_str / unknown }
15438     {
15439         \__kernel_msg_error:nxx { kernel } { boolean-values-only }
15440         { \l_keys_key_str }
15441     }
15442     \__keys_default_set:n { true }
15443 }
15444 \cs_generate_variant:Nn \__keys_bool_set_inverse:Nn { c }

```

(End definition for __keys_bool_set_inverse:Nn.)

`__keys_choice_make:` To make a choice from a key, two steps: set the code, and set the unknown key. As
`__keys_multichoice_make:` multichoice and choices are essentially the same bar one function, the code is given
`__keys_choice_make:N` together.
`__keys_choice_make_aux:N`

```

15445 \cs_new_protected:Npn __keys_choice_make:
15446 { __keys_choice_make:N __keys_choice_find:n }
15447 \cs_new_protected:Npn __keys_multichoice_make:
15448 { __keys_choice_make:N __keys_multichoice_find:n }
15449 \cs_new_protected:Npn __keys_choice_make:N #1
15450 {
15451   \cs_if_exist:cTF
15452     { \c__keys_type_root_str __keys_parent:o \l_keys_path_str }
15453     {
15454       \str_if_eq:vnTF
15455         { \c__keys_type_root_str __keys_parent:o \l_keys_path_str }
15456         { choice }
15457         {
15458           \__kernel_msg_error:nxx { kernel } { nested-choice-key }
15459           { \l_keys_path_tl } { __keys_parent:o \l_keys_path_str }
15460         }
15461         { __keys_choice_make_aux:N #1 }
15462       }
15463     { __keys_choice_make_aux:N #1 }
15464   }
15465 \cs_new_protected:Npn __keys_choice_make_aux:N #1
15466 {
15467   \cs_set_nopar:cpn { \c__keys_type_root_str \l_keys_path_str }
15468   { choice }
15469   \__keys_cmd_set:nn { \l_keys_path_str } { #1 {##1} }
15470   \__keys_cmd_set:nn { \l_keys_path_str / unknown }
15471   {
15472     \__kernel_msg_error:nxx { kernel } { key-choice-unknown }
15473     { \l_keys_path_str } {##1}
15474   }
15475 }

```

(End definition for `__keys_choice_make:` and others.)

`__keys_choices_make:nn` Auto-generating choices means setting up the root key as a choice, then defining each
`__keys_multichoice_make:nn` choice in turn.
`__keys_choices_make:Nnn`

```

15476 \cs_new_protected:Npn __keys_choices_make:nn
15477 { __keys_choices_make:Nnn __keys_choice_make: }
15478 \cs_new_protected:Npn __keys_multichoice_make:nn
15479 { __keys_choices_make:Nnn __keys_multichoice_make: }
15480 \cs_new_protected:Npn __keys_choices_make:Nnn #1#2#3
15481 {
15482   #1
15483   \int_zero:N \l_keys_choice_int
15484   \clist_map_inline:nn {#2}
15485   {
15486     \int_incr:N \l_keys_choice_int
15487     \__keys_cmd_set:nx
15488     { \l_keys_path_str / __keys_trim_spaces:n {##1} }
15489     {
15490       \tl_set:Nn \exp_not:N \l_keys_choice_tl {##1}

```

```

15491         \int_set:Nn \exp_not:N \l_keys_choice_int
15492         { \int_use:N \l_keys_choice_int }
15493         \exp_not:n {#3}
15494     }
15495 }
15496 }

```

(End definition for `__keys_choices_make:nn`, `__keys_multichoices_make:nn`, and `__keys_choices_make:Nnn`.)

`__keys_cmd_set:nn` Setting the code for a key first logs if appropriate that we are defining a new key, then saves the code.

```

\__keys_cmd_set:nx
\__keys_cmd_set:Vn
\__keys_cmd_set:Vo
15497 \cs_new_protected:Npn \__keys_cmd_set:nn #1#2
15498 { \cs_set_protected:cpx { \c__keys_code_root_str #1 } ##1 {#2} }
15499 \cs_generate_variant:Nn \__keys_cmd_set:nn { nx , Vn , Vo }

```

(End definition for `__keys_cmd_set:nn`.)

`__keys_cs_set:NNpn` Creating control sequences is a bit more tricky than other cases as we need to pick up the `p` argument. To make the internals look clearer, the trailing `n` argument here is just for appearance.

```

\__keys_cs_set:Ncpn
15500 \cs_new_protected:Npn \__keys_cs_set:NNpn #1#2#3#
15501 {
15502     \cs_set_protected:cpx { \c__keys_code_root_str \l_keys_path_str } ##1
15503     { #1 \exp_not:N #2 \exp_not:n {#3} {##1} }
15504     \use_none:n
15505 }
15506 \cs_generate_variant:Nn \__keys_cs_set:NNpn { Nc }

```

(End definition for `__keys_cs_set:NNpn`.)

`__keys_default_set:n` Setting a default value is easy. These are stored using `\cs_set:cpx` as this avoids any worries about whether a token list exists.

```

15507 \cs_new_protected:Npn \__keys_default_set:n #1
15508 {
15509     \tl_if_empty:nTF {#1}
15510     {
15511         \cs_set_eq:cN
15512         { \c__keys_default_root_str \l_keys_path_str }
15513         \tex_undefined:D
15514     }
15515     {
15516         \cs_set_nopar:cpx
15517         { \c__keys_default_root_str \l_keys_path_str }
15518         { \exp_not:n {#1} }
15519         \__keys_value_requirement:nn { required } { false }
15520     }
15521 }

```

(End definition for `__keys_default_set:n`.)

`__keys_groups_set:n` Assigning a key to one or more groups uses comma lists. As the list of groups only exists if there is anything to do, the setting is done using a scratch list. For the usual grouping reasons we use the low-level approach to undefining a list. We also use the low-level approach for the other case to avoid tripping up the `check-declarations` code.

```

15522 \cs_new_protected:Npn \__keys_groups_set:n #1
15523 {
15524   \clist_set:Nn \l__keys_groups_clist {#1}
15525   \clist_if_empty:NTF \l__keys_groups_clist
15526   {
15527     \cs_set_eq:cN { \c__keys_groups_root_str \l_keys_path_str }
15528     \tex_undefined:D
15529   }
15530   {
15531     \cs_set_eq:cN { \c__keys_groups_root_str \l_keys_path_str }
15532     \l__keys_groups_clist
15533   }
15534 }

```

(End definition for __keys_groups_set:n.)

`__keys_inherit:n` Inheritance means ignoring anything already said about the key: zap the lot and set up.

```

15535 \cs_new_protected:Npn \__keys_inherit:n #1
15536 {
15537   \__keys_undefine:
15538   \cs_set_nopar:cpn { \c__keys_inherit_root_str \l_keys_path_str } {#1}
15539 }

```

(End definition for __keys_inherit:n.)

`__keys_initialise:n` A set up for initialisation: just run the code if it exists.

```

15540 \cs_new_protected:Npn \__keys_initialise:n #1
15541 {
15542   \cs_if_exist:cTF
15543   { \c__keys_inherit_root_str \__keys_parent:o \l_keys_path_str }
15544   { \__keys_execute_inherit: }
15545   {
15546     \str_clear:N \l__keys_inherit_str
15547     \cs_if_exist_use:cT { \c__keys_code_root_str \l_keys_path_str } { {#1} }
15548   }
15549 }

```

(End definition for __keys_initialise:n.)

`__keys_meta_make:n` To create a meta-key, simply set up to pass data through.

```

\__keys_meta_make:nn
15550 \cs_new_protected:Npn \__keys_meta_make:n #1
15551 {
15552   \__keys_cmd_set:Vo \l_keys_path_str
15553   {
15554     \exp_after:wN \keys_set:nn
15555     \exp_after:wN { \l__keys_module_str } {#1}
15556   }
15557 }
15558 \cs_new_protected:Npn \__keys_meta_make:nn #1#2
15559 { \__keys_cmd_set:Vn \l_keys_path_str { \keys_set:nn {#1} {#2} } }

```

(End definition for __keys_meta_make:n and __keys_meta_make:nn.)

`__keys_prop_put:Nn` Much the same as other variables, but needs a dedicated auxiliary.

```

\__keys_prop_put:cn
15560 \cs_new_protected:Npn \__keys_prop_put:Nn #1#2
15561 {
15562   \prop_if_exist:NF #1 { \prop_new:N #1 }
15563   \exp_after:wN \__keys_find_key_module:NNw
15564     \exp_after:wN \l__keys_tmpa_tl
15565     \exp_after:wN \l__keys_tmpb_tl
15566     \l_keys_path_str / \s__keys_stop
15567   \__keys_cmd_set:nx { \l_keys_path_str }
15568   {
15569     \exp_not:c { prop_ #2 put:Nnn }
15570     \exp_not:N #1
15571     { \l__keys_tmpb_tl }
15572     \exp_not:n { {##1} }
15573   }
15574 }
15575 \cs_generate_variant:Nn \__keys_prop_put:Nn { c }

```

(End definition for __keys_prop_put:Nn.)

`__keys_undefine:` Undefined a key has to be done without `\cs_undefine:c` as that function acts globally.

```

15576 \cs_new_protected:Npn \__keys_undefine:
15577 {
15578   \clist_map_inline:nn
15579     { code , default , groups , inherit , type , validate }
15580     {
15581       \cs_set_eq:cN
15582         { \tl_use:c { c__keys_ ##1 _root_str } \l_keys_path_str }
15583       \tex_undefined:D
15584     }
15585 }

```

(End definition for __keys_undefine:.)

`__keys_value_requirement:nn` Validating key input is done using a second function which runs before the main key code. Setting that up means setting it equal to a generic stub which does the check. This approach makes the lookup very fast at the cost of one additional csname per key that needs it. The cleanup here has to know the structure of the following code.

`__keys_validate_forbidden:`
`__keys_validate_required:`
`__keys_validate_cleanup:w`

```

15586 \cs_new_protected:Npn \__keys_value_requirement:nn #1#2
15587 {
15588   \str_case:nnF {#2}
15589   {
15590     { true }
15591     {
15592       \cs_set_eq:cc
15593         { \c__keys_validate_root_str \l_keys_path_str }
15594         { __keys_validate_ #1 : }
15595     }
15596   { false }
15597   {
15598     \cs_if_eq:ccT
15599       { \c__keys_validate_root_str \l_keys_path_str }
15600       { __keys_validate_ #1 : }
15601   }

```

```

15602         \cs_set_eq:cN
15603         { \c__keys_validate_root_str \l_keys_path_str }
15604         \tex_undefined:D
15605     }
15606 }
15607 }
15608 {
15609     \__kernel_msg_error:nxx { kernel }
15610     { key-property-boolean-values-only }
15611     { .value_ #1 :n }
15612 }
15613 }
15614 \cs_new_protected:Npn \__keys_validate_forbidden:
15615 {
15616     \bool_if:NF \l__keys_no_value_bool
15617     {
15618         \__kernel_msg_error:nxxx { kernel } { value-forbidden }
15619         { \l_keys_path_str } { \l_keys_value_tl }
15620         \__keys_validate_cleanup:w
15621     }
15622 }
15623 \cs_new_protected:Npn \__keys_validate_required:
15624 {
15625     \bool_if:NT \l__keys_no_value_bool
15626     {
15627         \__kernel_msg_error:nxx { kernel } { value-required }
15628         { \l_keys_path_str }
15629         \__keys_validate_cleanup:w
15630     }
15631 }
15632 \cs_new_protected:Npn \__keys_validate_cleanup:w #1 \cs_end: #2#3 { }

```

(End definition for __keys_value_requirement:nn and others.)

__keys_variable_set:NnnN Setting a variable takes the type and scope separately so that it is easy to make a new
__keys_variable_set:cnnN variable if needed.

```

\__keys_variable_set_required:NnnN
\__keys_variable_set_required:cnnN
15633 \cs_new_protected:Npn \__keys_variable_set:NnnN #1#2#3#4
15634 {
15635     \use:c { #2_if_exist:NF } #1 { \use:c { #2_new:N } #1 }
15636     \__keys_cmd_set:nx { \l_keys_path_str }
15637     {
15638         \exp_not:c { #2 _ #3 set:N #4 }
15639         \exp_not:N #1
15640         \exp_not:n { {##1} }
15641     }
15642 }
15643 \cs_generate_variant:Nn \__keys_variable_set:NnnN { c }
15644 \cs_new_protected:Npn \__keys_variable_set_required:NnnN #1#2#3#4
15645 {
15646     \__keys_variable_set:NnnN #1 {#2} {#3} #4
15647     \__keys_value_requirement:nn { required } { true }
15648 }
15649 \cs_generate_variant:Nn \__keys_variable_set_required:NnnN { c }

```

(End definition for __keys_variable_set:NnnN and __keys_variable_set_required:NnnN.)

22.5 Creating key properties

The key property functions are all wrappers for internal functions, meaning that things stay readable and can also be altered later on.

Importantly, while key properties have “normal” argument specs, the underlying code always supplies one braced argument to these. As such, argument expansion is handled by hand rather than using the standard tools. This shows up particularly for the two-argument properties, where things would otherwise go badly wrong.

```
.bool_set:N One function for this.
.bool_set:c 15650 \cs_new_protected:cpn { \c__keys_props_root_str .bool_set:N } #1
.bool_gset:N 15651 { \__keys_bool_set:Nn #1 { } }
.bool_gset:c 15652 \cs_new_protected:cpn { \c__keys_props_root_str .bool_set:c } #1
15653 { \__keys_bool_set:cn {#1} { } }
15654 \cs_new_protected:cpn { \c__keys_props_root_str .bool_gset:N } #1
15655 { \__keys_bool_set:Nn #1 { g } }
15656 \cs_new_protected:cpn { \c__keys_props_root_str .bool_gset:c } #1
15657 { \__keys_bool_set:cn {#1} { g } }
```

(End definition for .bool_set:N and .bool_gset:N. These functions are documented on page 185.)

```
.bool_set_inverse:N One function for this.
.bool_set_inverse:c 15658 \cs_new_protected:cpn { \c__keys_props_root_str .bool_set_inverse:N } #1
.bool_gset_inverse:N 15659 { \__keys_bool_set_inverse:Nn #1 { } }
.bool_gset_inverse:c 15660 \cs_new_protected:cpn { \c__keys_props_root_str .bool_set_inverse:c } #1
15661 { \__keys_bool_set_inverse:cn {#1} { } }
15662 \cs_new_protected:cpn { \c__keys_props_root_str .bool_gset_inverse:N } #1
15663 { \__keys_bool_set_inverse:Nn #1 { g } }
15664 \cs_new_protected:cpn { \c__keys_props_root_str .bool_gset_inverse:c } #1
15665 { \__keys_bool_set_inverse:cn {#1} { g } }
```

(End definition for .bool_set_inverse:N and .bool_gset_inverse:N. These functions are documented on page 185.)

.choice: Making a choice is handled internally, as it is also needed by .generate_choices:n.

```
15666 \cs_new_protected:cpn { \c__keys_props_root_str .choice: }
15667 { \__keys_choice_make: }
```

(End definition for .choice:. This function is documented on page 185.)

.choices:nn For auto-generation of a series of mutually-exclusive choices. Here, #1 consists of two separate arguments, hence the slightly odd-looking implementation.

```
.choices:Vn 15668 \cs_new_protected:cpn { \c__keys_props_root_str .choices:nn } #1
.choices:on 15669 { \__keys_choices_make:nn #1 }
.choices:xn 15670 \cs_new_protected:cpn { \c__keys_props_root_str .choices:Vn } #1
15671 { \exp_args:NV \__keys_choices_make:nn #1 }
15672 \cs_new_protected:cpn { \c__keys_props_root_str .choices:on } #1
15673 { \exp_args:No \__keys_choices_make:nn #1 }
15674 \cs_new_protected:cpn { \c__keys_props_root_str .choices:xn } #1
15675 { \exp_args:Nx \__keys_choices_make:nn #1 }
```

(End definition for .choices:nn. This function is documented on page 185.)

.code:n Creating code is simply a case of passing through to the underlying `set` function.

```
15676 \cs_new_protected:cpn { \c__keys_props_root_str .code:n } #1
15677 { \__keys_cmd_set:nn { \l_keys_path_str } {#1} }
```

(End definition for `.code:n`. This function is documented on page 185.)

.clist_set:N

```
.clist_set:c 15678 \cs_new_protected:cpn { \c__keys_props_root_str .clist_set:N } #1
.clist_gset:N 15679 { \__keys_variable_set:NnnN #1 { clist } { } n }
.clist_gset:c 15680 \cs_new_protected:cpn { \c__keys_props_root_str .clist_set:c } #1
15681 { \__keys_variable_set:cnN {#1} { clist } { } n }
15682 \cs_new_protected:cpn { \c__keys_props_root_str .clist_gset:N } #1
15683 { \__keys_variable_set:NnnN #1 { clist } { g } n }
15684 \cs_new_protected:cpn { \c__keys_props_root_str .clist_gset:c } #1
15685 { \__keys_variable_set:cnN {#1} { clist } { g } n }
```

(End definition for `.clist_set:N` and `.clist_gset:N`. These functions are documented on page 185.)

.cs_set:Np

```
.cs_set:cp 15686 \cs_new_protected:cpn { \c__keys_props_root_str .cs_set:Np } #1
.cs_set_protected:Np 15687 { \__keys_cs_set:NNpn \cs_set:Npn #1 { } }
.cs_set_protected:cp 15688 \cs_new_protected:cpn { \c__keys_props_root_str .cs_set:cp } #1
.cs_gset:Np 15689 { \__keys_cs_set:Ncpn \cs_set:Npn #1 { } }
.cs_gset:cp 15690 \cs_new_protected:cpn { \c__keys_props_root_str .cs_set_protected:Np } #1
.cs_gset_protected:Np 15691 { \__keys_cs_set:NNpn \cs_set_protected:Npn #1 { } }
.cs_gset_protected:cp 15692 \cs_new_protected:cpn { \c__keys_props_root_str .cs_set_protected:cp } #1
15693 { \__keys_cs_set:Ncpn \cs_set_protected:Npn #1 { } }
15694 \cs_new_protected:cpn { \c__keys_props_root_str .cs_gset:Np } #1
15695 { \__keys_cs_set:NNpn \cs_gset:Npn #1 { } }
15696 \cs_new_protected:cpn { \c__keys_props_root_str .cs_gset:cp } #1
15697 { \__keys_cs_set:Ncpn \cs_gset:Npn #1 { } }
15698 \cs_new_protected:cpn { \c__keys_props_root_str .cs_gset_protected:Np } #1
15699 { \__keys_cs_set:NNpn \cs_gset_protected:Npn #1 { } }
15700 \cs_new_protected:cpn { \c__keys_props_root_str .cs_gset_protected:cp } #1
15701 { \__keys_cs_set:Ncpn \cs_gset_protected:Npn #1 { } }
```

(End definition for `.cs_set:Np` and others. These functions are documented on page 185.)

.default:n Expansion is left to the internal functions.

```
.default:V 15702 \cs_new_protected:cpn { \c__keys_props_root_str .default:n } #1
.default:o 15703 { \__keys_default_set:n {#1} }
.default:x 15704 \cs_new_protected:cpn { \c__keys_props_root_str .default:V } #1
15705 { \exp_args:NV \__keys_default_set:n #1 }
15706 \cs_new_protected:cpn { \c__keys_props_root_str .default:o } #1
15707 { \exp_args:No \__keys_default_set:n {#1} }
15708 \cs_new_protected:cpn { \c__keys_props_root_str .default:x } #1
15709 { \exp_args:Nx \__keys_default_set:n {#1} }
```

(End definition for `.default:n`. This function is documented on page 186.)

.dim_set:N Setting a variable is very easy: just pass the data along.

```
.dim_set:c 15710 \cs_new_protected:cpn { \c__keys_props_root_str .dim_set:N } #1
.dim_gset:N 15711 { \__keys_variable_set_required:NnnN #1 { dim } { } n }
.dim_gset:c 15712 \cs_new_protected:cpn { \c__keys_props_root_str .dim_set:c } #1
15713 { \__keys_variable_set_required:cnN {#1} { dim } { } n }
```

```

15714 \cs_new_protected:cpn { \c__keys_props_root_str .dim_gset:N } #1
15715 { \__keys_variable_set_required:NnnN #1 { dim } { g } n }
15716 \cs_new_protected:cpn { \c__keys_props_root_str .dim_gset:c } #1
15717 { \__keys_variable_set_required:cnnN {#1} { dim } { g } n }

```

(End definition for `.dim_set:N` and `.dim_gset:N`. These functions are documented on page 186.)

.fp_set:N Setting a variable is very easy: just pass the data along.

```

15718 \cs_new_protected:cpn { \c__keys_props_root_str .fp_set:N } #1
15719 { \__keys_variable_set_required:NnnN #1 { fp } { } n }
15720 \cs_new_protected:cpn { \c__keys_props_root_str .fp_set:c } #1
15721 { \__keys_variable_set_required:cnnN {#1} { fp } { } n }
15722 \cs_new_protected:cpn { \c__keys_props_root_str .fp_gset:N } #1
15723 { \__keys_variable_set_required:NnnN #1 { fp } { g } n }
15724 \cs_new_protected:cpn { \c__keys_props_root_str .fp_gset:c } #1
15725 { \__keys_variable_set_required:cnnN {#1} { fp } { g } n }

```

(End definition for `.fp_set:N` and `.fp_gset:N`. These functions are documented on page 186.)

.groups:n A single property to create groups of keys.

```

15726 \cs_new_protected:cpn { \c__keys_props_root_str .groups:n } #1
15727 { \__keys_groups_set:n {#1} }

```

(End definition for `.groups:n`. This function is documented on page 186.)

.inherit:n Nothing complex: only one variant at the moment!

```

15728 \cs_new_protected:cpn { \c__keys_props_root_str .inherit:n } #1
15729 { \__keys_inherit:n {#1} }

```

(End definition for `.inherit:n`. This function is documented on page 186.)

.initial:n The standard hand-off approach.

```

15730 \cs_new_protected:cpn { \c__keys_props_root_str .initial:n } #1
15731 { \__keys_initialise:n {#1} }
15732 \cs_new_protected:cpn { \c__keys_props_root_str .initial:V } #1
15733 { \exp_args:NV \__keys_initialise:n #1 }
15734 \cs_new_protected:cpn { \c__keys_props_root_str .initial:o } #1
15735 { \exp_args:No \__keys_initialise:n {#1} }
15736 \cs_new_protected:cpn { \c__keys_props_root_str .initial:x } #1
15737 { \exp_args:Nx \__keys_initialise:n {#1} }

```

(End definition for `.initial:n`. This function is documented on page 187.)

.int_set:N Setting a variable is very easy: just pass the data along.

```

15738 \cs_new_protected:cpn { \c__keys_props_root_str .int_set:N } #1
15739 { \__keys_variable_set_required:NnnN #1 { int } { } n }
15740 \cs_new_protected:cpn { \c__keys_props_root_str .int_set:c } #1
15741 { \__keys_variable_set_required:cnnN {#1} { int } { } n }
15742 \cs_new_protected:cpn { \c__keys_props_root_str .int_gset:N } #1
15743 { \__keys_variable_set_required:NnnN #1 { int } { g } n }
15744 \cs_new_protected:cpn { \c__keys_props_root_str .int_gset:c } #1
15745 { \__keys_variable_set_required:cnnN {#1} { int } { g } n }

```

(End definition for `.int_set:N` and `.int_gset:N`. These functions are documented on page 187.)

.meta:n Making a meta is handled internally.

```
15746 \cs_new_protected:cpn { \c__keys_props_root_str .meta:n } #1
15747 { \__keys_meta_make:n {#1} }
```

(End definition for .meta:n. This function is documented on page 187.)

.meta:nn Meta with path: potentially lots of variants, but for the moment no so many defined.

```
15748 \cs_new_protected:cpn { \c__keys_props_root_str .meta:nn } #1
15749 { \__keys_meta_make:nn #1 }
```

(End definition for .meta:nn. This function is documented on page 187.)

.multichoice: The same idea as .choice: and .choices:nn, but where more than one choice is allowed.

```
.multichoices:nn 15750 \cs_new_protected:cpn { \c__keys_props_root_str .multichoice: }
                  15751 { \__keys_multichoice_make: }
.multichoices:Vn 15752 \cs_new_protected:cpn { \c__keys_props_root_str .multichoices:nn } #1
.multichoices:on 15753 { \__keys_multichoices_make:nn #1 }
                  15754 \cs_new_protected:cpn { \c__keys_props_root_str .multichoices:Vn } #1
                  15755 { \exp_args:NV \__keys_multichoices_make:nn #1 }
.multichoices:xn 15756 \cs_new_protected:cpn { \c__keys_props_root_str .multichoices:on } #1
                  15757 { \exp_args:No \__keys_multichoices_make:nn #1 }
                  15758 \cs_new_protected:cpn { \c__keys_props_root_str .multichoices:xn } #1
                  15759 { \exp_args:Nx \__keys_multichoices_make:nn #1 }
```

(End definition for .multichoice: and .multichoices:nn. These functions are documented on page 187.)

.muskip_set:N Setting a variable is very easy: just pass the data along.

```
.muskip_set:c 15760 \cs_new_protected:cpn { \c__keys_props_root_str .muskip_set:N } #1
.muskip_gset:N 15761 { \__keys_variable_set_required:NnnN #1 { muskip } { } n }
.muskip_gset:c 15762 \cs_new_protected:cpn { \c__keys_props_root_str .muskip_set:c } #1
                  15763 { \__keys_variable_set_required:cnnN {#1} { muskip } { } n }
                  15764 \cs_new_protected:cpn { \c__keys_props_root_str .muskip_gset:N } #1
                  15765 { \__keys_variable_set_required:NnnN #1 { muskip } { g } n }
                  15766 \cs_new_protected:cpn { \c__keys_props_root_str .muskip_gset:c } #1
                  15767 { \__keys_variable_set_required:cnnN {#1} { muskip } { g } n }
```

(End definition for .muskip_set:N and .muskip_gset:N. These functions are documented on page 187.)

.prop_put:N Setting a variable is very easy: just pass the data along.

```
.prop_put:c 15768 \cs_new_protected:cpn { \c__keys_props_root_str .prop_put:N } #1
.prop_gput:N 15769 { \__keys_prop_put:Nn #1 { } }
.prop_gput:c 15770 \cs_new_protected:cpn { \c__keys_props_root_str .prop_put:c } #1
                  15771 { \__keys_prop_put:cn {#1} { } }
                  15772 \cs_new_protected:cpn { \c__keys_props_root_str .prop_gput:N } #1
                  15773 { \__keys_prop_put:Nn #1 { g } }
                  15774 \cs_new_protected:cpn { \c__keys_props_root_str .prop_gput:c } #1
                  15775 { \__keys_prop_put:cn {#1} { g } }
```

(End definition for .prop_put:N and .prop_gput:N. These functions are documented on page 187.)

```

.skip_set:N Setting a variable is very easy: just pass the data along.
.skip_set:c 15776 \cs_new_protected:cpn { \c__keys_props_root_str .skip_set:N } #1
.skip_gset:N 15777 { \__keys_variable_set_required:NnnN #1 { skip } { } n }
.skip_gset:c 15778 \cs_new_protected:cpn { \c__keys_props_root_str .skip_set:c } #1
15779 { \__keys_variable_set_required:cnnN {#1} { skip } { } n }
15780 \cs_new_protected:cpn { \c__keys_props_root_str .skip_gset:N } #1
15781 { \__keys_variable_set_required:NnnN #1 { skip } { g } n }
15782 \cs_new_protected:cpn { \c__keys_props_root_str .skip_gset:c } #1
15783 { \__keys_variable_set_required:cnnN {#1} { skip } { g } n }

```

(End definition for `.skip_set:N` and `.skip_gset:N`. These functions are documented on page 188.)

```

.tl_set:N Setting a variable is very easy: just pass the data along.
.tl_set:c 15784 \cs_new_protected:cpn { \c__keys_props_root_str .tl_set:N } #1
.tl_gset:N 15785 { \__keys_variable_set:NnnN #1 { tl } { } n }
.tl_gset:c 15786 \cs_new_protected:cpn { \c__keys_props_root_str .tl_set:c } #1
.tl_set_x:N 15787 { \__keys_variable_set:cnnN {#1} { tl } { } n }
.tl_set_x:c 15788 \cs_new_protected:cpn { \c__keys_props_root_str .tl_set_x:N } #1
.tl_gset_x:N 15789 { \__keys_variable_set:NnnN #1 { tl } { } x }
.tl_gset_x:c 15790 \cs_new_protected:cpn { \c__keys_props_root_str .tl_set_x:c } #1
15791 { \__keys_variable_set:cnnN {#1} { tl } { } x }
15792 \cs_new_protected:cpn { \c__keys_props_root_str .tl_gset:N } #1
15793 { \__keys_variable_set:NnnN #1 { tl } { g } n }
15794 \cs_new_protected:cpn { \c__keys_props_root_str .tl_gset:c } #1
15795 { \__keys_variable_set:cnnN {#1} { tl } { g } n }
15796 \cs_new_protected:cpn { \c__keys_props_root_str .tl_gset_x:N } #1
15797 { \__keys_variable_set:NnnN #1 { tl } { g } x }
15798 \cs_new_protected:cpn { \c__keys_props_root_str .tl_gset_x:c } #1
15799 { \__keys_variable_set:cnnN {#1} { tl } { g } x }

```

(End definition for `.tl_set:N` and others. These functions are documented on page 188.)

```

.undefine: Another simple wrapper.
15800 \cs_new_protected:cpn { \c__keys_props_root_str .undefine: }
15801 { \__keys_undefine: }

```

(End definition for `.undefine:.` This function is documented on page 188.)

```

.value_forbidden:n These are very similar, so both call the same function.
.value_required:n 15802 \cs_new_protected:cpn { \c__keys_props_root_str .value_forbidden:n } #1
15803 { \__keys_value_requirement:nn { forbidden } {#1} }
15804 \cs_new_protected:cpn { \c__keys_props_root_str .value_required:n } #1
15805 { \__keys_value_requirement:nn { required } {#1} }

```

(End definition for `.value_forbidden:n` and `.value_required:n`. These functions are documented on page 188.)

22.6 Setting keys

```

\keys_set:nn A simple wrapper allowing for nesting.
\keys_set:nV 15806 \cs_new_protected:Npn \keys_set:nn #1#2
\keys_set:nv 15807 {
\keys_set:no 15808 \use:x
\__keys_set:nn 15809 {
\__keys_set:nnn

```

```

15810     \bool_set_false:N \exp_not:N \l__keys_only_known_bool
15811     \bool_set_false:N \exp_not:N \l__keys_filtered_bool
15812     \bool_set_false:N \exp_not:N \l__keys_selective_bool
15813     \tl_set:Nn \exp_not:N \l__keys_relative_tl
15814         { \exp_not:N \q__keys_no_value }
15815     \__keys_set:nn \exp_not:n { {#1} {#2} }
15816     \bool_if:NT \l__keys_only_known_bool
15817         { \bool_set_true:N \exp_not:N \l__keys_only_known_bool }
15818     \bool_if:NT \l__keys_filtered_bool
15819         { \bool_set_true:N \exp_not:N \l__keys_filtered_bool }
15820     \bool_if:NT \l__keys_selective_bool
15821         { \bool_set_true:N \exp_not:N \l__keys_selective_bool }
15822     \tl_set:Nn \exp_not:N \l__keys_relative_tl
15823         { \exp_not:o \l__keys_relative_tl }
15824     }
15825 }
15826 \cs_generate_variant:Nn \keys_set:nn { nV , nv , no }
15827 \cs_new_protected:Npn \__keys_set:nn #1#2
15828     { \exp_args:No \__keys_set:nnn \l__keys_module_str {#1} {#2} }
15829 \cs_new_protected:Npn \__keys_set:nnn #1#2#3
15830     {
15831         \str_set:Nx \l__keys_module_str { \__keys_trim_spaces:n {#2} }
15832         \keyval_parse:NNn \__keys_set_keyval:n \__keys_set_keyval:nn {#3}
15833         \str_set:Nn \l__keys_module_str {#1}
15834     }

```

(End definition for `\keys_set:nn`, `__keys_set:nn`, and `__keys_set:nnn`. This function is documented on page 191.)

`\keys_set_known:nnN` Setting known keys simply means setting the appropriate flag, then running the standard code. To allow for nested setting, any existing value of `\l__keys_unused_clist` is saved on the stack and reset afterwards. Note that for speed/simplicity reasons we use a `tl` operation to set the `clist` here!

```

15835 \cs_new_protected:Npn \keys_set_known:nnN #1#2#3
15836     {
15837         \exp_args:No \__keys_set_known:nnnnN
15838             \l__keys_unused_clist { \q__keys_no_value } {#1} {#2} #3
15839     }
15840 \cs_generate_variant:Nn \keys_set_known:nnN { nV , nv , no }
15841 \cs_new_protected:Npn \keys_set_known:nnnN #1#2#3#4
15842     {
15843         \exp_args:No \__keys_set_known:nnnnN
15844             \l__keys_unused_clist {#3} {#1} {#2} #4
15845     }
15846 \cs_generate_variant:Nn \keys_set_known:nnnN { nV , nv , no }
15847 \cs_new_protected:Npn \__keys_set_known:nnnnN #1#2#3#4#5
15848     {
15849         \clist_clear:N \l__keys_unused_clist
15850         \__keys_set_known:nnn {#2} {#3} {#4}
15851         \tl_set:Nx #5 { \exp_not:o { \l__keys_unused_clist } }
15852         \tl_set:Nn \l__keys_unused_clist {#1}
15853     }
15854 \cs_new_protected:Npn \keys_set_known:nn #1#2
15855     { \__keys_set_known:nnn { \q__keys_no_value } {#1} {#2} }

```

```

15856 \cs_generate_variant:Nn \keys_set_known:nn { nV , nv , no }
15857 \cs_new_protected:Npn \__keys_set_known:nnn #1#2#3
15858 {
15859     \use:x
15860     {
15861         \bool_set_true:N \exp_not:N \l__keys_only_known_bool
15862         \bool_set_false:N \exp_not:N \l__keys_filtered_bool
15863         \bool_set_false:N \exp_not:N \l__keys_selective_bool
15864         \tl_set:Nn \exp_not:N \l__keys_relative_tl { \exp_not:n {#1} }
15865         \__keys_set:nn \exp_not:n { {#2} {#3} }
15866         \bool_if:NF \l__keys_only_known_bool
15867         { \bool_set_false:N \exp_not:N \l__keys_only_known_bool }
15868         \bool_if:NT \l__keys_filtered_bool
15869         { \bool_set_true:N \exp_not:N \l__keys_filtered_bool }
15870         \bool_if:NT \l__keys_selective_bool
15871         { \bool_set_true:N \exp_not:N \l__keys_selective_bool }
15872         \tl_set:Nn \exp_not:N \l__keys_relative_tl
15873         { \exp_not:o \l__keys_relative_tl }
15874     }
15875 }

```

(End definition for `\keys_set_known:nnN` and others. These functions are documented on page 192.)

The idea of setting keys in a selective manner again uses flags wrapped around the basic code. The comments on `\keys_set_known:nnN` also apply here. We have a bit more shuffling to do to keep everything nestable.

```

\keys_set_filter:nnnN
\keys_set_filter:nnVN
\keys_set_filter:nnvN
\keys_set_filter:nnoN
\keys_set_filter:nnnnN
\keys_set_filter:nnVnN
\keys_set_filter:nnvnN
\keys_set_filter:nnonN
\__keys_set_filter:nnnnnN
\keys_set_filter:nnn
\keys_set_filter:nnV
\keys_set_filter:nnv
\keys_set_filter:nno
\__keys_set_filter:nnnn
\keys_set_groups:nnn
\keys_set_groups:nnV
\keys_set_groups:nnv
\keys_set_groups:nno
\__keys_set_selective:nnn
\__keys_set_selective:nnnn
15876 \cs_new_protected:Npn \keys_set_filter:nnnN #1#2#3#4
15877 {
15878     \exp_args:No \__keys_set_filter:nnnnnN
15879     \l__keys_unused_clist
15880     { \q__keys_no_value } {#1} {#2} {#3} #4
15881 }
15882 \cs_generate_variant:Nn \keys_set_filter:nnnN { nnV , nnv , nno }
15883 \cs_new_protected:Npn \keys_set_filter:nnnnN #1#2#3#4#5
15884 {
15885     \exp_args:No \__keys_set_filter:nnnnnN
15886     \l__keys_unused_clist {#4} {#1} {#2} {#3} #5
15887 }
15888 \cs_generate_variant:Nn \keys_set_filter:nnnnN { nnV , nnv , nno }
15889 \cs_new_protected:Npn \__keys_set_filter:nnnnnN #1#2#3#4#5#6
15890 {
15891     \clist_clear:N \l__keys_unused_clist
15892     \__keys_set_filter:nnnn {#2} {#3} {#4} {#5}
15893     \tl_set:Nx #6 { \exp_not:o { \l__keys_unused_clist } }
15894     \tl_set:Nn \l__keys_unused_clist {#1}
15895 }
15896 \cs_new_protected:Npn \keys_set_filter:nnn #1#2#3
15897 { \__keys_set_filter:nnnn { \q__keys_no_value } {#1} {#2} {#3} }
15898 \cs_generate_variant:Nn \keys_set_filter:nnn { nnV , nnv , nno }
15899 \cs_new_protected:Npn \__keys_set_filter:nnnn #1#2#3#4
15900 {
15901     \use:x
15902     {
15903         \bool_set_false:N \exp_not:N \l__keys_only_known_bool

```

```

15904     \bool_set_true:N \exp_not:N \l__keys_filtered_bool
15905     \bool_set_true:N \exp_not:N \l__keys_selective_bool
15906     \tl_set:Nn \exp_not:N \l__keys_relative_tl { \exp_not:n {#1} }
15907     \__keys_set_selective:nnn \exp_not:n { {#2} {#3} {#4} }
15908     \bool_if:NT \l__keys_only_known_bool
15909       { \bool_set_true:N \exp_not:N \l__keys_only_known_bool }
15910     \bool_if:NF \l__keys_filtered_bool
15911       { \bool_set_false:N \exp_not:N \l__keys_filtered_bool }
15912     \bool_if:NF \l__keys_selective_bool
15913       { \bool_set_false:N \exp_not:N \l__keys_selective_bool }
15914     \tl_set:Nn \exp_not:N \l__keys_relative_tl
15915       { \exp_not:o \l__keys_relative_tl }
15916   }
15917 }
15918 \cs_new_protected:Npn \keys_set_groups:nnn #1#2#3
15919 {
15920   \use:x
15921   {
15922     \bool_set_false:N \exp_not:N \l__keys_only_known_bool
15923     \bool_set_false:N \exp_not:N \l__keys_filtered_bool
15924     \bool_set_true:N \exp_not:N \l__keys_selective_bool
15925     \tl_set:Nn \exp_not:N \l__keys_relative_tl
15926       { \exp_not:N \q__keys_no_value }
15927     \__keys_set_selective:nnn \exp_not:n { {#1} {#2} {#3} }
15928     \bool_if:NT \l__keys_only_known_bool
15929       { \bool_set_true:N \exp_not:N \l__keys_only_known_bool }
15930     \bool_if:NF \l__keys_filtered_bool
15931       { \bool_set_true:N \exp_not:N \l__keys_filtered_bool }
15932     \bool_if:NF \l__keys_selective_bool
15933       { \bool_set_false:N \exp_not:N \l__keys_selective_bool }
15934     \tl_set:Nn \exp_not:N \l__keys_relative_tl
15935       { \exp_not:o \l__keys_relative_tl }
15936   }
15937 }
15938 \cs_generate_variant:Nn \keys_set_groups:nnn { nnV , nnv , nno }
15939 \cs_new_protected:Npn \__keys_set_selective:nnn
15940 { \exp_args:No \__keys_set_selective:nnnn \l__keys_selective_seq }
15941 \cs_new_protected:Npn \__keys_set_selective:nnnn #1#2#3#4
15942 {
15943   \seq_set_from_clist:Nn \l__keys_selective_seq {#3}
15944   \__keys_set:nn {#2} {#4}
15945   \tl_set:Nn \l__keys_selective_seq {#1}
15946 }

```

(End definition for `\keys_set_filter:nnnN` and others. These functions are documented on page 193.)

<pre> __keys_set_keyval:n __keys_set_keyval:nn __keys_set_keyval:nnn __keys_set_keyval:onn __keys_find_key_module:NNw __keys_set_selective: </pre>	<p>A shared system once again. First, set the current path and add a default if needed. There are then checks to see if the a value is required or forbidden. If everything passes, move on to execute the code.</p> <pre> 15947 \cs_new_protected:Npn __keys_set_keyval:n #1 15948 { 15949 \bool_set_true:N \l__keys_no_value_bool 15950 __keys_set_keyval:onn \l__keys_module_str {#1} { } 15951 } </pre>
--	---


```

15952 \cs_new_protected:Npn \__keys_set_keyval:nn #1#2
15953 {
15954   \bool_set_false:N \l__keys_no_value_bool
15955   \__keys_set_keyval:onn \l__keys_module_str {#1} {#2}
15956 }

```

The key path here can be fully defined, after which there is a search for the key and module names: the user may have passed them with part of what is actually the module (for our purposes) in the key name. As that happens on a per-key basis, we use the stack approach to restore the module name without a group.

```

15957 \cs_new_protected:Npn \__keys_set_keyval:nnn #1#2#3
15958 {
15959   \tl_set:Nx \l_keys_path_str
15960   {
15961     \tl_if_blank:nF {#1}
15962     { #1 / }
15963     \__keys_trim_spaces:n {#2}
15964   }
15965   \str_clear:N \l__keys_module_str
15966   \str_clear:N \l__keys_inherit_str
15967   \exp_after:wN \__keys_find_key_module:NNw
15968   \exp_after:wN \l__keys_module_str
15969   \exp_after:wN \l_keys_key_str
15970   \l_keys_path_str / \s__keys_stop
15971   \tl_set_eq:NN \l_keys_key_tl \l_keys_key_str
15972   \__keys_value_or_default:n {#3}
15973   \bool_if:NTF \l__keys_selective_bool
15974   { \__keys_set_selective: }
15975   { \__keys_execute: }
15976   \str_set:Nn \l__keys_module_str {#1}
15977 }
15978 \cs_generate_variant:Nn \__keys_set_keyval:nnn { o }
15979 \cs_new_protected:Npn \__keys_find_key_module:NNw #1#2#3 / #4 \s__keys_stop
15980 {
15981   \tl_if_blank:nTF {#4}
15982   { \str_set:Nn #2 {#3} }
15983   {
15984     \str_put_right:Nx #1
15985     {
15986       \str_if_empty:NF #1 { / }
15987       #3
15988     }
15989     \__keys_find_key_module:NNw #1#2 #4 \s__keys_stop
15990   }
15991 }

```

If selective setting is active, there are a number of possible sub-cases to consider. The key name may not be known at all or if it is, it may not have any groups assigned. There is then the question of whether the selection is opt-in or opt-out.

```

15992 \cs_new_protected:Npn \__keys_set_selective:
15993 {
15994   \cs_if_exist:cTF { \c__keys_groups_root_str \l_keys_path_str }
15995   {
15996     \clist_set_eq:Nc \l__keys_groups_clist

```

```

15997         { \c__keys_groups_root_str \l_keys_path_str }
15998     \__keys_check_groups:
15999 }
16000 {
16001     \bool_if:NTF \l__keys_filtered_bool
16002     { \__keys_execute: }
16003     { \__keys_store_unused: }
16004 }
16005 }

```

In the case where selective setting requires a comparison of the list of groups which apply to a key with the list of those which have been set active. That requires two mappings, and again a different outcome depending on whether opt-in or opt-out is set.

```

16006 \cs_new_protected:Npn \__keys_check_groups:
16007 {
16008     \bool_set_false:N \l__keys_tmp_bool
16009     \seq_map_inline:Nn \l__keys_selective_seq
16010     {
16011         \clist_map_inline:Nn \l__keys_groups_clist
16012         {
16013             \str_if_eq:nnT {##1} {####1}
16014             {
16015                 \bool_set_true:N \l__keys_tmp_bool
16016                 \clist_map_break:n { \seq_map_break: }
16017             }
16018         }
16019     }
16020     \bool_if:NTF \l__keys_tmp_bool
16021     {
16022         \bool_if:NTF \l__keys_filtered_bool
16023         { \__keys_store_unused: }
16024         { \__keys_execute: }
16025     }
16026     {
16027         \bool_if:NTF \l__keys_filtered_bool
16028         { \__keys_execute: }
16029         { \__keys_store_unused: }
16030     }
16031 }

```

(End definition for __keys_set_keyval:n and others.)

__keys_value_or_default:n If a value is given, return it as #1, otherwise send a default if available.

```

\__keys_default_inherit:
16032 \cs_new_protected:Npn \__keys_value_or_default:n #1
16033 {
16034     \bool_if:NTF \l__keys_no_value_bool
16035     {
16036         \cs_if_exist:cTF { \c__keys_default_root_str \l_keys_path_str }
16037         {
16038             \tl_set_eq:Nc
16039             \l_keys_value_tl
16040             { \c__keys_default_root_str \l_keys_path_str }
16041         }
16042         {
16043             \tl_clear:N \l_keys_value_tl

```

```

16044         \cs_if_exist:cT
16045         { \c__keys_inherit_root_str \__keys_parent:o \l_keys_path_str }
16046         { \__keys_default_inherit: }
16047     }
16048 }
16049 { \tl_set:Nn \l_keys_value_tl {#1} }
16050 }
16051 \cs_new_protected:Npn \__keys_default_inherit:
16052 {
16053     \clist_map_inline:cn
16054     { \c__keys_inherit_root_str \__keys_parent:o \l_keys_path_str }
16055     {
16056         \cs_if_exist:cT
16057         { \c__keys_default_root_str ##1 / \l_keys_key_str }
16058         {
16059             \tl_set_eq:Nc
16060             \l_keys_value_tl
16061             { \c__keys_default_root_str ##1 / \l_keys_key_str }
16062             \clist_map_break:
16063         }
16064     }
16065 }

```

(End definition for __keys_value_or_default:n and __keys_default_inherit:.)

__keys_execute: Actually executing a key is done in two parts. First, look for the key itself, then look for the **unknown** key with the same path. If both of these fail, complain. What exactly happens if a key is unknown depends on whether unknown keys are being skipped or if an error should be raised.

```

\__keys_execute:nn
\__keys_store_unused:
\__keys_store_unused_aux:
16066 \cs_new_protected:Npn \__keys_execute:
16067 {
16068     \cs_if_exist:cTF { \c__keys_code_root_str \l_keys_path_str }
16069     {
16070         \cs_if_exist_use:c { \c__keys_validate_root_str \l_keys_path_str }
16071         \cs:w \c__keys_code_root_str \l_keys_path_str \exp_after:wN \cs_end:
16072         \exp_after:wN { \l_keys_value_tl }
16073     }
16074     {
16075         \cs_if_exist:cTF
16076         { \c__keys_inherit_root_str \__keys_parent:o \l_keys_path_str }
16077         { \__keys_execute_inherit: }
16078         { \__keys_execute_unknown: }
16079     }
16080 }

```

To deal with the case where there is no hit, we leave __keys_execute_unknown: in the input stream and clean it up using the break function: that avoids needing a boolean.

```

16081 \cs_new_protected:Npn \__keys_execute_inherit:
16082 {
16083     \clist_map_inline:cn
16084     { \c__keys_inherit_root_str \__keys_parent:o \l_keys_path_str }
16085     {
16086         \cs_if_exist:cT
16087         { \c__keys_code_root_str ##1 / \l_keys_key_str }

```

```

16088         {
16089             \str_set:Nn \l__keys_inherit_str {##1}
16090             \cs_if_exist_use:c { \c__keys_validate_root_str ##1 / \l_keys_key_str }
16091             \cs:w \c__keys_code_root_str ##1 / \l_keys_key_str
16092             \exp_after:wN \cs_end: \exp_after:wN
16093             { \l_keys_value_tl }
16094             \clist_map_break:n { \use_none:n }
16095         }
16096     }
16097     \__keys_execute_unknown:
16098 }
16099 \cs_new_protected:Npn \__keys_execute_unknown:
16100 {
16101     \bool_if:NTF \l__keys_only_known_bool
16102     { \__keys_store_unused: }
16103     {
16104         \cs_if_exist:cTF
16105         { \c__keys_code_root_str \l__keys_module_str / unknown }
16106         {
16107             \cs:w \c__keys_code_root_str \l__keys_module_str / unknown
16108             \exp_after:wN \cs_end: \exp_after:wN { \l_keys_value_tl }
16109         }
16110         {
16111             \__kernel_msg_error:nxxx { kernel } { key-unknown }
16112             { \l_keys_path_str } { \l__keys_module_str }
16113         }
16114     }
16115 }
16116 \cs_new:Npn \__keys_execute:nn #1#2
16117 {
16118     \cs_if_exist:cTF { \c__keys_code_root_str #1 }
16119     {
16120         \cs:w \c__keys_code_root_str #1 \exp_after:wN \cs_end:
16121         \exp_after:wN { \l_keys_value_tl }
16122     }
16123     {#2}
16124 }

```

When there is no relative path, things here are easy: just save the key name and value. When we are working with a relative path, first we need to turn it into a string: that can't happen earlier as we need to store `\q__keys_no_value`. Then, use a standard delimited approach to fish out the partial path.

```

16125 \cs_new_protected:Npn \__keys_store_unused:
16126 {
16127     \__keys_quark_if_no_value:NTF \l__keys_relative_tl
16128     {
16129         \clist_put_right:Nx \l__keys_unused_clist
16130         {
16131             \exp_not:o \l_keys_key_str
16132             \bool_if:NF \l__keys_no_value_bool
16133             { = { \exp_not:o \l_keys_value_tl } }
16134         }
16135     }
16136 }

```

```

16137     \tl_if_empty:NTF \l__keys_relative_tl
16138     {
16139         \clist_put_right:Nx \l__keys_unused_clist
16140         {
16141             \exp_not:o \l_keys_path_str
16142             \bool_if:NF \l__keys_no_value_bool
16143             { = { \exp_not:o \l_keys_value_tl } }
16144         }
16145     }
16146     { \__keys_store_unused_aux: }
16147 }
16148 }
16149 \cs_new_protected:Npn \__keys_store_unused_aux:
16150 {
16151     \tl_set:Nx \l__keys_relative_tl
16152     { \exp_args:No \__keys_trim_spaces:n \l__keys_relative_tl }
16153     \use:x
16154     {
16155         \cs_set_protected:Npn \__keys_store_unused:w
16156         ###1 \l__keys_relative_tl /
16157         ###2 \l__keys_relative_tl /
16158         ###3 \s__keys_stop
16159     }
16160     {
16161         \tl_if_blank:nF {##1}
16162         {
16163             \__kernel_msg_error:nxxx { kernel } { bad-relative-key-path }
16164             \l_keys_path_str
16165             \l__keys_relative_tl
16166         }
16167         \clist_put_right:Nx \l__keys_unused_clist
16168         {
16169             \exp_not:n {##2}
16170             \bool_if:NF \l__keys_no_value_bool
16171             { = { \exp_not:o \l_keys_value_tl } }
16172         }
16173     }
16174     \use:x
16175     {
16176         \__keys_store_unused:w \l_keys_path_str
16177         \l__keys_relative_tl / \l__keys_relative_tl /
16178         \s__keys_stop
16179     }
16180 }
16181 \cs_new_protected:Npn \__keys_store_unused:w { }

```

(End definition for __keys_execute: and others.)

__keys_choice_find:n Executing a choice has two parts. First, try the choice given, then if that fails call the
 __keys_choice_find:nn unknown key. That always exists, as it is created when a choice is first made. So there
 __keys_multichoice_find:n is no need for any escape code. For multiple choices, the same code ends up used in a
 mapping.

```

16182 \cs_new:Npn \__keys_choice_find:n #1
16183 {

```

```

16184     \str_if_empty:NTF \l__keys_inherit_str
16185     { \__keys_choice_find:nn { \l_keys_path_str } {#1} }
16186     {
16187       \__keys_choice_find:nn
16188       { \l_keys_inherit_str / \l_keys_key_str } {#1}
16189     }
16190   }
16191   \cs_new:Npn \__keys_choice_find:nn #1#2
16192   {
16193     \cs_if_exist:cTF { \c__keys_code_root_str #1 / \__keys_trim_spaces:n {#2} }
16194     { \use:c { \c__keys_code_root_str #1 / \__keys_trim_spaces:n {#2} } {#2} }
16195     { \use:c { \c__keys_code_root_str #1 / unknown } {#2} }
16196   }
16197   \cs_new:Npn \__keys_multichoice_find:n #1
16198   { \clist_map_function:nN {#1} \__keys_choice_find:n }

```

(End definition for __keys_choice_find:n, __keys_choice_find:nn, and __keys_multichoice_find:n.)

22.7 Utilities

__keys_parent:n Used to strip off the ending part of the key path after the last /.

```

\__keys_parent:o
\__keys_parent:w
16199 \cs_new:Npn \__keys_parent:n #1
16200 { \__keys_parent:w #1 / / \s__keys_stop { } }
16201 \cs_generate_variant:Nn \__keys_parent:n { o }
16202 \cs_new:Npn \__keys_parent:w #1 / #2 / #3 \s__keys_stop #4
16203 {
16204   \tl_if_blank:nTF {#2}
16205   {
16206     \tl_if_blank:nF {#4}
16207     { \use_none:n #4 }
16208   }
16209   {
16210     \__keys_parent:w #2 / #3 \s__keys_stop { #4 / #1 }
16211   }
16212 }

```

(End definition for __keys_parent:n and __keys_parent:w.)

__keys_trim_spaces:n Space stripping has to allow for the fact that the key here might have several parts, and spaces need to be stripped from each part.

```

\__keys_trim_spaces_auxi:w
\__keys_trim_spaces_auxii:w
\__keys_trim_spaces_auxiii:w
16213 \cs_new:Npn \__keys_trim_spaces:n #1
16214 {
16215   \exp_after:wN \__keys_trim_spaces_auxi:w \tl_to_str:n {#1}
16216   / \q__keys_nil \s__keys_stop
16217 }
16218 \cs_new:Npn \__keys_trim_spaces_auxi:w #1 / #2 \s__keys_stop
16219 {
16220   \__keys_quark_if_nil:nTF {#2}
16221   { \tl_trim_spaces:n {#1} }
16222   { \__keys_trim_spaces_auxii:w #1 / #2 }
16223 }
16224 \cs_new:Npn \__keys_trim_spaces_auxii:w #1 / #2 / \q__keys_nil
16225 {

```

```

16226 \tl_trim_spaces:n {#1}
16227 \__keys_trim_spaces_auxiii:w #2 / \q__keys_recursion_tail / \q__keys_recursion_stop
16228 }
16229 \cs_set:Npn \__keys_trim_spaces_auxiii:w #1 /
16230 {
16231 \__keys_if_recursion_tail_stop:n {#1}
16232 / \tl_trim_spaces:n { #1 }
16233 \__keys_trim_spaces_auxiii:w
16234 }

```

(End definition for __keys_trim_spaces:n and others.)

\keys_if_exist_p:nn A utility for others to see if a key exists.

```

\keys_if_exist:nnTF 16235 \prg_new_conditional:Npnn \keys_if_exist:nn #1#2 { p , T , F , TF }
16236 {
16237 \cs_if_exist:cTF
16238 { \c__keys_code_root_str \__keys_trim_spaces:n { #1 / #2 } }
16239 { \prg_return_true: }
16240 { \prg_return_false: }
16241 }

```

(End definition for \keys_if_exist:nnTF. This function is documented on page 193.)

\keys_if_choice_exist_p:nnn Just an alternative view on \keys_if_exist:nnTF.

```

\keys_if_choice_exist:nnnTF 16242 \prg_new_conditional:Npnn \keys_if_choice_exist:nnn #1#2#3
16243 { p , T , F , TF }
16244 {
16245 \cs_if_exist:cTF
16246 { \c__keys_code_root_str \__keys_trim_spaces:n { #1 / #2 / #3 } }
16247 { \prg_return_true: }
16248 { \prg_return_false: }
16249 }

```

(End definition for \keys_if_choice_exist:nnnTF. This function is documented on page 194.)

\keys_show:nn To show a key, show its code using a message.

```

\keys_log:nn 16250 \cs_new_protected:Npn \keys_show:nn
\__keys_show:Nnn 16251 { \__keys_show:Nnn \msg_show:nnxxxxx }
16252 \cs_new_protected:Npn \keys_log:nn
16253 { \__keys_show:Nnn \msg_log:nnxxxxx }
16254 \cs_new_protected:Npn \__keys_show:Nnn #1#2#3
16255 {
16256 #1 { LaTeX / kernel } { show-key }
16257 { \__keys_trim_spaces:n { #2 / #3 } }
16258 {
16259 \keys_if_exist:nnT {#2} {#3}
16260 {
16261 \exp_args:Nnf \msg_show_item_unbraced:nn { code }
16262 {
16263 \exp_args:Nc \cs_replacement_spec:N
16264 {
16265 \c__keys_code_root_str
16266 \__keys_trim_spaces:n { #2 / #3 }
16267 }
16268 }

```

```

16269         }
16270     }
16271     { } { }
16272 }

```

(End definition for `\keys_show:nn`, `\keys_log:nn`, and `__keys_show:Nnn`. These functions are documented on page 194.)

22.8 Messages

For when there is a need to complain.

```

16273 \__kernel_msg_new:nnnn { kernel } { bad-relative-key-path }
16274 { The-key~'#1'~is-not~inside~the~'#2'~path. }
16275 { The-key~'#1'~cannot-be-expressed~relative~to~path~'#2'. }
16276 \__kernel_msg_new:nnnn { kernel } { boolean-values-only }
16277 { Key~'#1'~accepts~boolean-values-only. }
16278 { The-key~'#1'~only-accepts~the~values~'true'~and~'false'. }
16279 \__kernel_msg_new:nnnn { kernel } { key-choice-unknown }
16280 { Key~'#1'~accepts-only~a~fixed~set~of~choices. }
16281 {
16282     The-key~'#1'~only-accepts~predefined~values,~
16283     and~'#2'~is~not~one~of~these.
16284 }
16285 \__kernel_msg_new:nnnn { kernel } { key-unknown }
16286 { The-key~'#1'~is-unknown~and~is~being~ignored. }
16287 {
16288     The-module~'#2'~does~not~have~a~key~called~'#1'.\\
16289     Check~that~you~have~spelled~the~key~name~correctly.
16290 }
16291 \__kernel_msg_new:nnnn { kernel } { nested-choice-key }
16292 { Attempt~to~define~'#1'~as~a~nested~choice~key. }
16293 {
16294     The-key~'#1'~cannot-be-defined~as~a~choice~as~the~parent~key~'#2'~is~
16295     itself~a~choice.
16296 }
16297 \__kernel_msg_new:nnnn { kernel } { value-forbidden }
16298 { The-key~'#1'~does~not~take~a~value. }
16299 {
16300     The-key~'#1'~should-be-given~without~a~value.\\
16301     The-value~'#2'~was~present:~the~key~will~be~ignored.
16302 }
16303 \__kernel_msg_new:nnnn { kernel } { value-required }
16304 { The-key~'#1'~requires~a~value. }
16305 {
16306     The-key~'#1'~must~have~a~value.\\
16307     No~value~was~present:~the~key~will~be~ignored.
16308 }
16309 \__kernel_msg_new:nnn { kernel } { show-key }
16310 {
16311     The-key~'#1~
16312     \tl_if_empty:nTF {#2}
16313     { is~undefined. }
16314     { has~the~properties:~#2 . }
16315 }

```


16316 \langle /initex | package \rangle

23 l3intarray implementation

16317 \langle *initex | package \rangle

16318 \langle @@=intarray \rangle

23.1 Allocating arrays

\backslash __intarray_entry:w We use these primitives quite a lot in this module.

\backslash __intarray_count:w 16319 \backslash cs_new_eq:NN \backslash __intarray_entry:w \backslash tex_fontdimen:D

16320 \backslash cs_new_eq:NN \backslash __intarray_count:w \backslash tex_hyphenchar:D

(End definition for \backslash __intarray_entry:w and \backslash __intarray_count:w.)

\backslash l__intarray_loop_int A loop index.

16321 \backslash int_new:N \backslash l__intarray_loop_int

(End definition for \backslash l__intarray_loop_int.)

\backslash c__intarray_sp_dim Used to convert integers to dimensions fast.

16322 \backslash dim_const:Nn \backslash c__intarray_sp_dim { 1 sp }

(End definition for \backslash c__intarray_sp_dim.)

\backslash g__intarray_font_int Used to assign one font per array.

16323 \backslash int_new:N \backslash g__intarray_font_int

(End definition for \backslash g__intarray_font_int.)

16324 \backslash _kernel_msg_new:nnn { kernel } { negative-array-size }

16325 { Size-of-array-may-not-be-negative:~#1 }

\backslash intarray_new:Nn Declare #1 to be a font (arbitrarily cmr10 at a never-used size). Store the array's size as
 \backslash intarray_new:cn the \backslash hyphenchar of that font and make sure enough \backslash fontdimen are allocated, by setting
 \backslash __intarray_new:N the last one. Then clear any \backslash fontdimen that cmr10 starts with. It seems LuaTeX's
cmr10 has an extra \backslash fontdimen parameter number 8 compared to other engines (for a
math font we would replace 8 by 22 or some such). Every intarray must be global; it's
enough to run this check in \backslash intarray_new:Nn.

16326 \backslash cs_new_protected:Npn \backslash __intarray_new:N #1

16327 {

16328 \backslash _kernel_chk_if_free_cs:N #1

16329 \backslash int_gincr:N \backslash g__intarray_font_int

16330 \backslash tex_global:D \backslash tex_font:D #1

16331 = cmr10~at~ \backslash g__intarray_font_int \backslash c__intarray_sp_dim \backslash scan_stop:

16332 \backslash int_step_inline:nn { 8 }

16333 { \backslash _kernel_intarray_gset:Nnn #1 {##1} \backslash c_zero_int }

16334 }

16335 \backslash cs_new_protected:Npn \backslash intarray_new:Nn #1#2

16336 {

16337 \backslash __intarray_new:N #1

16338 \backslash __intarray_count:w #1 = \backslash int_eval:n {#2} \backslash scan_stop:

16339 \backslash int_compare:nNt { \backslash intarray_count:N #1 } < 0

16340 {

```

16341     \_kernel_msg_error:nxx { kernel } { negative-array-size }
16342     { \intarray_count:N #1 }
16343   }
16344   \int_compare:nNnT { \intarray_count:N #1 } > 0
16345   { \_kernel_intarray_gset:Nnn #1 { \intarray_count:N #1 } { 0 } }
16346 }
16347 \cs_generate_variant:Nn \intarray_new:Nn { c }

```

(End definition for `\intarray_new:Nn` and `__intarray_new:N`. This function is documented on page 196.)

`\intarray_count:N` Size of an array.

```

\intarray_count:c 16348 \cs_new:Npn \intarray_count:N #1 { \int_value:w \__intarray_count:w #1 }
16349 \cs_generate_variant:Nn \intarray_count:N { c }

```

(End definition for `\intarray_count:N`. This function is documented on page 196.)

23.2 Array items

`__intarray_signed_max_dim:n` Used when an item to be stored is larger than `\c_max_dim` in absolute value; it is replaced by $\pm\c_max_dim$.

```

16350 \cs_new:Npn \__intarray_signed_max_dim:n #1
16351 { \int_value:w \int_compare:nNnT {#1} < 0 { - } \c_max_dim }

```

(End definition for `__intarray_signed_max_dim:n`.)

`__intarray_bounds:NNnTF` The functions `\intarray_gset:Nnn` and `\intarray_item:Nn` share bounds checking. The T branch is used if #3 is within bounds of the array #2.

```

\__intarray_bounds_error:NNn 16352 \cs_new:Npn \__intarray_bounds:NNnTF #1#2#3#4#5
16353 {
16354   \if_int_compare:w 1 > #3 \exp_stop_f:
16355   \__intarray_bounds_error:NNn #1 #2 {#3}
16356   #5
16357   \else:
16358   \if_int_compare:w #3 > \intarray_count:N #2 \exp_stop_f:
16359   \__intarray_bounds_error:NNn #1 #2 {#3}
16360   #5
16361   \else:
16362   #4
16363   \fi:
16364 \fi:
16365 }
16366 \cs_new:Npn \__intarray_bounds_error:NNn #1#2#3
16367 {
16368   #1 { kernel } { out-of-bounds }
16369   { \token_to_str:N #2 } {#3} { \intarray_count:N #2 }
16370 }

```

(End definition for `__intarray_bounds:NNnTF` and `__intarray_bounds_error:NNn`.)

`\intarray_gset:Nnn` Set the appropriate `\fontdimen`. The `__kernel_intarray_gset:Nnn` function does not use `\int_eval:n`, namely its arguments must be suitable for `\int_value:w`. The user version checks the position and value are within bounds.

```

\intarray_gset:cnn  \__kernel_intarray_gset:Nnn
\__intarray_gset:Nnn 16371 \cs_new_protected:Npn \__kernel_intarray_gset:Nnn #1#2#3
\__intarray_gset_overflow:NNn

```

```

16372 { \_intarray_entry:w #2 #1 #3 \c\_intarray_sp_dim }
16373 \cs_new_protected:Npn \intarray_gset:Nnn #1#2#3
16374 {
16375   \exp_after:wN \_intarray_gset:Nww
16376   \exp_after:wN #1
16377   \int_value:w \int_eval:n {#2} \exp_after:wN ;
16378   \int_value:w \int_eval:n {#3} ;
16379 }
16380 \cs_generate_variant:Nn \intarray_gset:Nnn { c }
16381 \cs_new_protected:Npn \_intarray_gset:Nww #1#2 ; #3 ;
16382 {
16383   \_intarray_bounds:NNnTF \_kernel_msg_error:nxxxx #1 {#2}
16384   {
16385     \_intarray_gset_overflow_test:nw {#3}
16386     \_kernel_intarray_gset:Nnn #1 {#2} {#3}
16387   }
16388   { }
16389 }
16390 \cs_if_exist:NTF \tex_ifabsnum:D
16391 {
16392   \cs_new_protected:Npn \_intarray_gset_overflow_test:nw #1
16393   {
16394     \tex_ifabsnum:D #1 > \c_max_dim
16395     \exp_after:wN \_intarray_gset_overflow:NNnn
16396     \fi:
16397   }
16398 }
16399 {
16400   \cs_new_protected:Npn \_intarray_gset_overflow_test:nw #1
16401   {
16402     \if_int_compare:w \int_abs:n {#1} > \c_max_dim
16403     \exp_after:wN \_intarray_gset_overflow:NNnn
16404     \fi:
16405   }
16406 }
16407 \cs_new_protected:Npn \_intarray_gset_overflow:NNnn #1#2#3#4
16408 {
16409   \_kernel_msg_error:nxxxxx { kernel } { overflow }
16410   { \token_to_str:N #2 } {#3} {#4} { \_intarray_signed_max_dim:n {#4} }
16411   #1 #2 {#3} { \_intarray_signed_max_dim:n {#4} }
16412 }

```

(End definition for `\intarray_gset:Nnn` and others. This function is documented on page 196.)

`\intarray_gzero:N` Set the appropriate `\fontdimen` to zero. No bound checking needed. The `\prg_replicate:nn` possibly uses quite a lot of memory, but this is somewhat comparable to the size of the array, and it is much faster than an `\int_step_inline:nn` loop.

`\intarray_gzero:c`

```

16413 \cs_new_protected:Npn \intarray_gzero:N #1
16414 {
16415   \int_zero:N \l__intarray_loop_int
16416   \prg_replicate:nn { \intarray_count:N #1 }
16417   {
16418     \int_incr:N \l__intarray_loop_int
16419     \_intarray_entry:w \l__intarray_loop_int #1 \c_zero_dim

```

```

16420     }
16421   }
16422   \cs_generate_variant:Nn \intarray_gzero:N { c }

```

(End definition for `\intarray_gzero:N`. This function is documented on page 196.)

```

\intarray_item:Nn Get the appropriate \fontdimen and perform bound checks. The \__kernel_
\intarray_item:cn intarray_item:Nn function omits bound checks and omits \int_eval:n, namely its
\__kernel_intarray_item:Nn argument must be a TeX integer suitable for \int_value:w.
\__intarray_item:Nn
16423   \cs_new:Npn \__kernel_intarray_item:Nn #1#2
16424     { \int_value:w \__intarray_entry:w #2 #1 }
16425   \cs_new:Npn \intarray_item:Nn #1#2
16426     {
16427       \exp_after:wN \__intarray_item:Nw
16428       \exp_after:wN #1
16429       \int_value:w \int_eval:n {#2} ;
16430     }
16431   \cs_generate_variant:Nn \intarray_item:Nn { c }
16432   \cs_new:Npn \__intarray_item:Nw #1#2 ;
16433     {
16434       \__intarray_bounds:NNnTF \__kernel_msg_expandable_error:nfff #1 {#2}
16435       { \__kernel_intarray_item:Nn #1 {#2} }
16436       { 0 }
16437     }

```

(End definition for `\intarray_item:Nn`, `__kernel_intarray_item:Nn`, and `__intarray_item:Nn`. This function is documented on page 197.)

```

\intarray_rand_item:Nn Importantly, \intarray_item:Nn only evaluates its argument once.
\intarray_rand_item:c
16438   \cs_new:Npn \intarray_rand_item:N #1
16439     { \intarray_item:Nn #1 { \int_rand:n { \intarray_count:N #1 } } }
16440   \cs_generate_variant:Nn \intarray_rand_item:N { c }

```

(End definition for `\intarray_rand_item:N`. This function is documented on page 197.)

23.3 Working with contents of integer arrays

```

\intarray_const_from_clist:Nn Similar to \intarray_new:Nn (which we don't use because when debugging is enabled
\intarray_const_from_clist:cn that function checks the variable name starts with g_). We make use of the fact that TeX
\__intarray_const_from_clist:nN allows allocation of successive \fontdimen as long as no other font has been declared: no
need to count the comma list items first. We need the code in \intarray_gset:Nnn that
checks the item value is not too big, namely \__intarray_gset_overflow_test:nw, but
not the code that checks bounds. At the end, set the size of the intarray.

```

```

16441   \cs_new_protected:Npn \intarray_const_from_clist:Nn #1#2
16442     {
16443       \__intarray_new:N #1
16444       \int_zero:N \l__intarray_loop_int
16445       \clist_map_inline:nn {#2}
16446       { \exp_args:Nf \__intarray_const_from_clist:nN { \int_eval:n {##1} } #1 }
16447       \__intarray_count:w #1 \l__intarray_loop_int
16448     }
16449   \cs_generate_variant:Nn \intarray_const_from_clist:Nn { c }
16450   \cs_new_protected:Npn \__intarray_const_from_clist:nN #1#2
16451     {

```

```

16452 \int_incr:N \l__intarray_loop_int
16453 \__intarray_gset_overflow_test:nw {#1}
16454 \__kernel_intarray_gset:Nnn #2 \l__intarray_loop_int {#1}
16455 }

```

(End definition for `\intarray_const_from_clist:Nn` and `__intarray_const_from_clist:nN`. This function is documented on page 196.)

`\intarray_to_clist:N` Loop through the array, putting a comma before each item. Remove the leading comma with `f`-expansion. We also use the auxiliary in `\intarray_show:N` with argument comma, space.

```

\intarray_to_clist:c
\__intarray_to_clist:Nn
\__intarray_to_clist:w
16456 \cs_new:Npn \intarray_to_clist:N #1 { \__intarray_to_clist:Nn #1 { , } }
16457 \cs_generate_variant:Nn \intarray_to_clist:N { c }
16458 \cs_new:Npn \__intarray_to_clist:Nn #1#2
16459 {
16460   \int_compare:nNnF { \intarray_count:N #1 } = \c_zero_int
16461   {
16462     \exp_last_unbraced:Nf \use_none:n
16463     { \__intarray_to_clist:w 1 ; #1 {#2} \prg_break_point: }
16464   }
16465 }
16466 \cs_new:Npn \__intarray_to_clist:w #1 ; #2#3
16467 {
16468   \if_int_compare:w #1 > \__intarray_count:w #2
16469   \prg_break:n
16470   \fi:
16471   #3 \__kernel_intarray_item:Nn #2 {#1}
16472   \exp_after:wN \__intarray_to_clist:w
16473   \int_value:w \int_eval:w #1 + \c_one_int ; #2 {#3}
16474 }

```

(End definition for `\intarray_to_clist:N`, `__intarray_to_clist:Nn`, and `__intarray_to_clist:w`. This function is documented on page 262.)

`\intarray_show:N` Convert the list to a comma list (with spaces after each comma)

```

\intarray_show:c
\intarray_log:N
\intarray_log:c
16475 \cs_new_protected:Npn \intarray_show:N { \__intarray_show:NN \msg_show:nnxxxx }
16476 \cs_generate_variant:Nn \intarray_show:N { c }
16477 \cs_new_protected:Npn \intarray_log:N { \__intarray_show:NN \msg_log:nnxxxx }
16478 \cs_generate_variant:Nn \intarray_log:N { c }
16479 \cs_new_protected:Npn \__intarray_show:NN #1#2
16480 {
16481   \__kernel_chk_defined:NT #2
16482   {
16483     #1 { LaTeX/kernel } { show-intarray }
16484     { \token_to_str:N #2 }
16485     { \intarray_count:N #2 }
16486     { >~ \__intarray_to_clist:Nn #2 { , ~ } }
16487     { }
16488   }
16489 }

```

(End definition for `\intarray_show:N` and `\intarray_log:N`. These functions are documented on page 197.)

23.4 Random arrays

We only perform the bounds checks once. This is done by two `__intarray_gset_overflow_test:nw`, with an appropriate empty argument to avoid a spurious “at position #1” part in the error message. Then calculate the number of choices: this is at most $(2^{30} - 1) - (-(2^{30} - 1)) + 1 = 2^{31} - 1$, which just barely does not overflow. For small ranges use `__kernel_randint:n` (making sure to subtract 1 *before* adding the random number to the $\langle min \rangle$, to avoid overflow when $\langle min \rangle$ or $\langle max \rangle$ are $\pm \text{c_max_int}$), otherwise `__kernel_randint:nn`. Finally, if there are no random numbers do not define any of the auxiliaries.

```

16490 \cs_new_protected:Npn \intarray_gset_rand:Nn #1
16491   { \intarray_gset_rand:Nnn #1 { 1 } }
16492 \cs_generate_variant:Nn \intarray_gset_rand:Nn { c }
16493 \sys_if_rand_exist:TF
16494   {
16495     \cs_new_protected:Npn \intarray_gset_rand:Nnn #1#2#3
16496       {
16497         \__intarray_gset_rand:Nff #1
16498         { \int_eval:n {#2} } { \int_eval:n {#3} }
16499       }
16500     \cs_new_protected:Npn \__intarray_gset_rand:Nnn #1#2#3
16501       {
16502         \int_compare:nNnTF {#2} > {#3}
16503         {
16504           \__kernel_msg_expandable_error:nnnn
16505           { kernel } { randint-backward-range } {#2} {#3}
16506           \__intarray_gset_rand:Nnn #1 {#3} {#2}
16507         }
16508         {
16509           \__intarray_gset_overflow_test:nw {#2}
16510           \__intarray_gset_rand_auxi:Nnnn #1 { } {#2} {#3}
16511         }
16512       }
16513     \cs_generate_variant:Nn \__intarray_gset_rand:Nnn { Nff }
16514     \cs_new_protected:Npn \__intarray_gset_rand_auxi:Nnnn #1#2#3#4
16515       {
16516         \__intarray_gset_overflow_test:nw {#4}
16517         \__intarray_gset_rand_auxii:Nnnn #1 { } {#4} {#3}
16518       }
16519     \cs_new_protected:Npn \__intarray_gset_rand_auxii:Nnnn #1#2#3#4
16520       {
16521         \exp_args:NNf \__intarray_gset_rand_auxiii:Nnnn #1
16522         { \int_eval:n { #3 - #4 + 1 } } {#4} {#3}
16523       }
16524     \cs_new_protected:Npn \__intarray_gset_rand_auxiii:Nnnn #1#2#3#4
16525       {
16526         \exp_args:NNf \__intarray_gset_all_same:Nn #1
16527         {
16528           \int_compare:nNnTF {#2} > \c__kernel_randint_max_int
16529           {
16530             \exp_stop_f:
16531             \int_eval:n { \__kernel_randint:nn {#3} {#4} }
16532           }

```

```

16533         {
16534             \exp_stop_f:
16535             \int_eval:n { \__kernel_randint:n {#2} - 1 + #3 }
16536         }
16537     }
16538 }
16539 \cs_new_protected:Npn \__intarray_gset_all_same:Nn #1#2
16540 {
16541     \int_zero:N \l__intarray_loop_int
16542     \prg_replicate:nn { \intarray_count:N #1 }
16543     {
16544         \int_incr:N \l__intarray_loop_int
16545         \__kernel_intarray_gset:Nnn #1 \l__intarray_loop_int {#2}
16546     }
16547 }
16548 }
16549 {
16550     \cs_new_protected:Npn \intarray_gset_rand:Nnn #1#2#3
16551     {
16552         \__kernel_msg_error:nnn { kernel } { fp-no-random }
16553         { \intarray_gset_rand:Nnn #1 {#2} {#3} }
16554     }
16555 }
16556 \cs_generate_variant:Nn \intarray_gset_rand:Nnn { c }

```

(End definition for `\intarray_gset_rand:Nn` and others. These functions are documented on page 262.)

```
16557 </initex | package>
```

24 l3fp implementation

Nothing to see here: everything is in the subfiles!

25 l3fp-aux implementation

```

16558 <*initex | package>
16559 <@@=fp>

```

25.1 Access to primitives

`__fp_int_eval:w` Largely for performance reasons, we need to directly access primitives rather than use `\int_eval:n`. This happens *a lot*, so we use private names. The same is true for `__fp_int_eval_end:` `\romannumeral`, although it is used much less widely.

```

16560 \cs_new_eq:NN \__fp_int_eval:w \tex_numexpr:D
16561 \cs_new_eq:NN \__fp_int_eval_end: \scan_stop:
16562 \cs_new_eq:NN \__fp_int_to_roman:w \tex_romannumeral:D

```

(End definition for `__fp_int_eval:w`, `__fp_int_eval_end:`, and `__fp_int_to_roman:w`.)

25.2 Internal representation

Internally, a floating point number $\langle X \rangle$ is a token list containing

```
\s__fp \__fp_chk:w  $\langle case \rangle$   $\langle sign \rangle$   $\langle body \rangle$  ;
```

Let us explain each piece separately.

Internal floating point numbers are used in expressions, and in this context are subject to **f**-expansion. They must leave a recognizable mark after **f**-expansion, to prevent the floating point number from being re-parsed. Thus, `\s__fp` is simply another name for `\relax`.

When used directly without an accessor function, floating points should produce an error: this is the role of `__fp_chk:w`. We could make floating point variables be protected to prevent them from expanding under **x**-expansion, but it seems more convenient to treat them as a subcase of token list variables.

The (decimal part of the) IEEE-754-2008 standard requires the format to be able to represent special floating point numbers besides the usual positive and negative cases. We distinguish the various possibilities by their $\langle case \rangle$, which is a single digit:

- 0 zeros: `+0` and `-0`,
- 1 “normal” numbers (positive and negative),
- 2 infinities: `+inf` and `-inf`,
- 3 quiet and signalling `nan`.

The $\langle sign \rangle$ is 0 (positive) or 2 (negative), except in the case of `nan`, which have $\langle sign \rangle = 1$. This ensures that changing the $\langle sign \rangle$ digit to $2 - \langle sign \rangle$ is exactly equivalent to changing the sign of the number.

Special floating point numbers have the form

```
\s__fp \__fp_chk:w  $\langle case \rangle$   $\langle sign \rangle$  \s__fp_... ;
```

where `\s__fp_...` is a scan mark carrying information about how the number was formed (useful for debugging).

Normal floating point numbers ($\langle case \rangle = 1$) have the form

```
\s__fp \__fp_chk:w 1  $\langle sign \rangle$  { $\langle exponent \rangle$ } { $\langle X_1 \rangle$ } { $\langle X_2 \rangle$ } { $\langle X_3 \rangle$ } { $\langle X_4 \rangle$ } ;
```

Here, the $\langle exponent \rangle$ is an integer, between -10000 and 10000 . The body consists in four blocks of exactly 4 digits, $0000 \leq \langle X_i \rangle \leq 9999$, and the floating point is

$$(-1)^{\langle sign \rangle / 2} \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle X_4 \rangle \cdot 10^{\langle exponent \rangle - 16}$$

where we have concatenated the 16 digits. Currently, floating point numbers are normalized such that the $\langle exponent \rangle$ is minimal, in other words, $1000 \leq \langle X_1 \rangle \leq 9999$.

Calculations are done in base 10000, *i.e.* one myriad.

Table 3: Internal representation of floating point numbers.

Representation	Meaning
0 0 \s_fp_... ;	Positive zero.
0 2 \s_fp_... ;	Negative zero.
1 0 {\langle exponent\rangle} {\langle X ₁ \rangle} {\langle X ₂ \rangle} {\langle X ₃ \rangle} {\langle X ₄ \rangle} ;	Positive floating point.
1 2 {\langle exponent\rangle} {\langle X ₁ \rangle} {\langle X ₂ \rangle} {\langle X ₃ \rangle} {\langle X ₄ \rangle} ;	Negative floating point.
2 0 \s_fp_... ;	Positive infinity.
2 2 \s_fp_... ;	Negative infinity.
3 1 \s_fp_... ;	Quiet nan.
3 1 \s_fp_... ;	Signalling nan.

25.3 Using arguments and semicolons

_fp_use_none_stop_f:n This function removes an argument (typically a digit) and replaces it by \exp_stop_f:, a marker which stops f-type expansion.

```
16563 \cs_new:Npn \_fp\_use\_none\_stop\_f:n #1 { \exp\_stop\_f: }
```

(End definition for _fp_use_none_stop_f:n.)

_fp_use_s:n Those functions place a semicolon after one or two arguments (typically digits).

```
16564 \cs_new:Npn \_fp\_use\_s:n #1 { #1; }
16565 \cs_new:Npn \_fp\_use\_s:nn #1#2 { #1#2; }
```

(End definition for _fp_use_s:n and _fp_use_s:nn.)

_fp_use_none_until_s:w Those functions select specific arguments among a set of arguments delimited by a semicolon.

```
\_fp\_use\_i\_until\_s:nw
\_fp\_use\_ii\_until\_s:nnw
16566 \cs_new:Npn \_fp\_use\_none\_until\_s:w #1; { }
16567 \cs_new:Npn \_fp\_use\_i\_until\_s:nw #1#2; {#1}
16568 \cs_new:Npn \_fp\_use\_ii\_until\_s:nnw #1#2#3; {#2}
```

(End definition for _fp_use_none_until_s:w, _fp_use_i_until_s:nw, and _fp_use_ii_until_s:nnw.)

_fp_reverse_args:Nww Many internal functions take arguments delimited by semicolons, and it is occasionally useful to swap two such arguments.

```
16569 \cs_new:Npn \_fp\_reverse\_args:Nww #1 #2; #3; { #1 #3; #2; }
```

(End definition for _fp_reverse_args:Nww.)

_fp_rrot:www Rotate three arguments delimited by semicolons. This is the inverse (or the square) of the Forth primitive ROT, hence the name.

```
16570 \cs_new:Npn \_fp\_rrot:www #1; #2; #3; { #2; #3; #1; }
```

(End definition for _fp_rrot:www.)

_fp_use_i:ww Many internal functions take arguments delimited by semicolons, and it is occasionally useful to remove one or two such arguments.

```
\_fp\_use\_i:www
16571 \cs_new:Npn \_fp\_use\_i:ww #1; #2; { #1; }
16572 \cs_new:Npn \_fp\_use\_i:www #1; #2; #3; { #1; }
```

(End definition for _fp_use_i:ww and _fp_use_i:www.)

25.4 Constants, and structure of floating points

`__fp_misused:n` This receives a floating point object (floating point number or tuple) and generates an error stating that it was misused. This is called when for instance an `fp` variable is left in the input stream and its contents reach `TEX`'s stomach.

```
16573 \cs_new_protected:Npn \__fp_misused:n #1
16574 { \__kernel_msg_error:nnx { kernel } { misused-fp } { \fp_to_tl:n {#1} } }
```

(End definition for `__fp_misused:n`.)

`\s__fp` Floating points numbers all start with `\s__fp __fp_chk:w`, where `\s__fp` is equal to the `TEX` primitive `\relax`, and `__fp_chk:w` is protected. The rest of the floating point number is made of characters (or `\relax`). This ensures that nothing expands under `f`-expansion, nor under `x`-expansion. However, when typeset, `\s__fp` does nothing, and `__fp_chk:w` is expanded. We define `__fp_chk:w` to produce an error.

```
16575 \scan_new:N \s__fp
16576 \cs_new_protected:Npn \__fp_chk:w #1 ;
16577 { \__fp_misused:n { \s__fp \__fp_chk:w #1 ; } }
```

(End definition for `\s__fp` and `__fp_chk:w`.)

`\s__fp_expr_mark` Aliases of `\tex_relax:D`, used to terminate expressions.

```
\s__fp_expr_stop 16578 \scan_new:N \s__fp_expr_mark
16579 \scan_new:N \s__fp_expr_stop
```

(End definition for `\s__fp_expr_mark` and `\s__fp_expr_stop`.)

`\s__fp_mark` Generic scan marks used throughout the module.

```
\s__fp_stop 16580 \scan_new:N \s__fp_mark
16581 \scan_new:N \s__fp_stop
```

(End definition for `\s__fp_mark` and `\s__fp_stop`.)

`_fp_use_i_delimit_by_s_stop:nw` Functions to gobble up to a scan mark.

```
16582 \cs_new:Npn \_fp_use_i_delimit_by_s_stop:nw #1 #2 \s__fp_stop {#1}
```

(End definition for `_fp_use_i_delimit_by_s_stop:nw`.)

`\s__fp_invalid` A couple of scan marks used to indicate where special floating point numbers come from.

```
\s__fp_underflow 16583 \scan_new:N \s__fp_invalid
\s__fp_overflow 16584 \scan_new:N \s__fp_underflow
\s__fp_division 16585 \scan_new:N \s__fp_overflow
\s__fp_exact 16586 \scan_new:N \s__fp_division
16587 \scan_new:N \s__fp_exact
```

(End definition for `\s__fp_invalid` and others.)

`\c_zero_fp` The special floating points. We define the floating points here as “exact”.

```
\c_minus_zero_fp 16588 \tl_const:Nn \c_zero_fp { \s__fp \__fp_chk:w 0 0 \s__fp_exact ; }
\c_inf_fp 16589 \tl_const:Nn \c_minus_zero_fp { \s__fp \__fp_chk:w 0 2 \s__fp_exact ; }
\c_minus_inf_fp 16590 \tl_const:Nn \c_inf_fp { \s__fp \__fp_chk:w 2 0 \s__fp_exact ; }
\c_nan_fp 16591 \tl_const:Nn \c_minus_inf_fp { \s__fp \__fp_chk:w 2 2 \s__fp_exact ; }
16592 \tl_const:Nn \c_nan_fp { \s__fp \__fp_chk:w 3 1 \s__fp_exact ; }
```

(End definition for `\c_zero_fp` and others. These variables are documented on page 205.)

$\backslash c_fp_prec_int$ $\backslash c_fp_half_prec_int$ $\backslash c_fp_block_int$	<p>The number of digits of floating points.</p> <pre> 16593 \int_const:Nn \c_fp_prec_int { 16 } 16594 \int_const:Nn \c_fp_half_prec_int { 8 } 16595 \int_const:Nn \c_fp_block_int { 4 } </pre> <p>(End definition for $\backslash c_fp_prec_int$, $\backslash c_fp_half_prec_int$, and $\backslash c_fp_block_int$.)</p>
$\backslash c_fp_myriad_int$	<p>Blocks have 4 digits so this integer is useful.</p> <pre> 16596 \int_const:Nn \c_fp_myriad_int { 10000 } </pre> <p>(End definition for $\backslash c_fp_myriad_int$.)</p>
$\backslash c_fp_minus_min_exponent_int$ $\backslash c_fp_max_exponent_int$	<p>Normal floating point numbers have an exponent between $- \text{minus_min_exponent}$ and max_exponent inclusive. Larger numbers are rounded to $\pm\infty$. Smaller numbers are rounded to ± 0. It would be more natural to define a min_exponent with the opposite sign but that would waste one T_EX count.</p> <pre> 16597 \int_const:Nn \c_fp_minus_min_exponent_int { 10000 } 16598 \int_const:Nn \c_fp_max_exponent_int { 10000 } </pre> <p>(End definition for $\backslash c_fp_minus_min_exponent_int$ and $\backslash c_fp_max_exponent_int$.)</p>
$\backslash c_fp_max_exp_exponent_int$	<p>If a number's exponent is larger than that, its exponential overflows/underflows.</p> <pre> 16599 \int_const:Nn \c_fp_max_exp_exponent_int { 5 } </pre> <p>(End definition for $\backslash c_fp_max_exp_exponent_int$.)</p>
$\backslash c_fp_overflowing_fp$	<p>A floating point number that is bigger than all normal floating point numbers. This replaces infinities when converting to formats that do not support infinities.</p> <pre> 16600 \tl_const:Nx \c_fp_overflowing_fp 16601 { 16602 \s_fp _fp_chk:w 1 0 16603 { \int_eval:n { \c_fp_max_exponent_int + 1 } } 16604 {1000} {0000} {0000} {0000} ; 16605 } </pre> <p>(End definition for $\backslash c_fp_overflowing_fp$.)</p>
$\backslash _fp_zero_fp:N$ $\backslash _fp_inf_fp:N$	<p>In case of overflow or underflow, we have to output a zero or infinity with a given sign.</p> <pre> 16606 \cs_new:Npn _fp_zero_fp:N #1 16607 { \s_fp _fp_chk:w 0 #1 \s_fp_underflow ; } 16608 \cs_new:Npn _fp_inf_fp:N #1 16609 { \s_fp _fp_chk:w 2 #1 \s_fp_overflow ; } </pre> <p>(End definition for $\backslash _fp_zero_fp:N$ and $\backslash _fp_inf_fp:N$.)</p>
$\backslash _fp_exponent:w$	<p>For normal numbers, the function expands to the exponent, otherwise to 0. This is used in l3str-format.</p> <pre> 16610 \cs_new:Npn _fp_exponent:w \s_fp _fp_chk:w #1 16611 { 16612 \if_meaning:w 1 #1 16613 \exp_after:wN _fp_use_ii_until_s:nnw 16614 \else: 16615 \exp_after:wN _fp_use_i_until_s:nw 16616 \exp_after:wN 0 16617 \fi: 16618 } </pre>

(End definition for `_fp_exponent:w`.)

`_fp_neg_sign:N` When appearing in an integer expression or after `\int_value:w`, this expands to the sign opposite to #1, namely 0 (positive) is turned to 2 (negative), 1 (nan) to 1, and 2 to 0.

```
16619 \cs_new:Npn \_fp_neg_sign:N #1
16620 { \_fp_int_eval:w 2 - #1 \_fp_int_eval_end: }
```

(End definition for `_fp_neg_sign:N`.)

`_fp_kind:w` Expands to 0 for zeros, 1 for normal floating point numbers, 2 for infinities, 3 for NaN, 4 for tuples.

```
16621 \cs_new:Npn \_fp_kind:w #1
16622 {
16623   \_fp_if_type_fp:NTwFw
16624   #1 \_fp_use_ii_until_s:nnw
16625   \s__fp { \_fp_use_i_until_s:nw 4 }
16626   \s__fp_stop
16627 }
```

(End definition for `_fp_kind:w`.)

25.5 Overflow, underflow, and exact zero

`_fp_sanitize:Nw` `_fp_sanitize:wN` `_fp_sanitize_zero:w` Expects the sign and the exponent in some order, then the significand (which we don't touch). Outputs the corresponding floating point number, possibly underflowed to ± 0 or overflowed to $\pm\infty$. The functions `_fp_underflow:w` and `_fp_overflow:w` are defined in `l3fp-traps`.

```
16628 \cs_new:Npn \_fp_sanitize:Nw #1 #2;
16629 {
16630   \if_case:w
16631     \if_int_compare:w #2 > \c_fp_max_exponent_int 1 ~ \else:
16632     \if_int_compare:w #2 < - \c_fp_minus_min_exponent_int 2 ~ \else:
16633     \if_meaning:w 1 #1 3 ~ \fi: \fi: \fi: 0 ~
16634     \or: \exp_after:wN \_fp_overflow:w
16635     \or: \exp_after:wN \_fp_underflow:w
16636     \or: \exp_after:wN \_fp_sanitize_zero:w
16637     \fi:
16638     \s__fp \_fp_chk:w 1 #1 {#2}
16639   }
16640   \cs_new:Npn \_fp_sanitize:wN #1; #2 { \_fp_sanitize:Nw #2 #1; }
16641   \cs_new:Npn \_fp_sanitize_zero:w \s__fp \_fp_chk:w #1 #2 #3;
16642   { \c_zero_fp }
```

(End definition for `_fp_sanitize:Nw`, `_fp_sanitize:wN`, and `_fp_sanitize_zero:w`.)

25.6 Expanding after a floating point number

`_fp_exp_after_o:w` `_fp_exp_after_f:nw` `_fp_exp_after_f:nw` `_fp_exp_after_o:w` `_fp_exp_after_f:nw` `_fp_exp_after_f:nw` Places *tokens* (empty in the case of `_fp_exp_after_o:w`) between the *floating point* and the following tokens, then hits those tokens with `o` or `f`-expansion, and leaves the floating point number unchanged.

We first distinguish normal floating points, which have a significand, from the much simpler special floating points.

```

16643 \cs_new:Npn \__fp_exp_after_o:w \s__fp \__fp_chk:w #1
16644 {
16645   \if_meaning:w 1 #1
16646     \exp_after:wN \__fp_exp_after_normal:nNNw
16647   \else:
16648     \exp_after:wN \__fp_exp_after_special:nNNw
16649   \fi:
16650   { }
16651   #1
16652 }
16653 \cs_new:Npn \__fp_exp_after_f:nw #1 \s__fp \__fp_chk:w #2
16654 {
16655   \if_meaning:w 1 #2
16656     \exp_after:wN \__fp_exp_after_normal:nNNw
16657   \else:
16658     \exp_after:wN \__fp_exp_after_special:nNNw
16659   \fi:
16660   { \exp:w \exp_end_continue_f:w #1 }
16661   #2
16662 }

```

(End definition for __fp_exp_after_o:w and __fp_exp_after_f:nw.)

__fp_exp_after_special:nNNw

__fp_exp_after_special:nNNw {<after>} <case> <sign> <scan mark> ;
Special floating point numbers are easy to jump over since they contain few tokens.

```

16663 \cs_new:Npn \__fp_exp_after_special:nNNw #1#2#3#4;
16664 {
16665   \exp_after:wN \s__fp
16666   \exp_after:wN \__fp_chk:w
16667   \exp_after:wN #2
16668   \exp_after:wN #3
16669   \exp_after:wN #4
16670   \exp_after:wN ;
16671   #1
16672 }

```

(End definition for __fp_exp_after_special:nNNw.)

__fp_exp_after_normal:nNNw

For normal floating point numbers, life is slightly harder, since we have many tokens to jump over. Here it would be slightly better if the digits were not braced but instead were delimited arguments (for instance delimited by ,). That may be changed some day.

```

16673 \cs_new:Npn \__fp_exp_after_normal:nNNw #1 1 #2 #3 #4#5#6#7;
16674 {
16675   \exp_after:wN \__fp_exp_after_normal:Nwwwww
16676   \exp_after:wN #2
16677   \int_value:w #3 \exp_after:wN ;
16678   \int_value:w 1 #4 \exp_after:wN ;
16679   \int_value:w 1 #5 \exp_after:wN ;
16680   \int_value:w 1 #6 \exp_after:wN ;
16681   \int_value:w 1 #7 \exp_after:wN ; #1
16682 }
16683 \cs_new:Npn \__fp_exp_after_normal:Nwwwww

```

```

16684      #1 #2; 1 #3 ; 1 #4 ; 1 #5 ; 1 #6 ;
16685      { \s__fp \__fp_chk:w 1 #1 {#2} {#3} {#4} {#5} {#6} ; }

```

(End definition for __fp_exp_after_normal:nNNw.)

25.7 Other floating point types

\s__fp_tuple Floating point tuples take the form \s__fp_tuple __fp_tuple_chk:w { *<fp 1>* *<fp 2>* ... } ; where each *<fp>* is a floating point number or tuple, hence ends with ; itself. When a tuple is typeset, __fp_tuple_chk:w produces an error, just like usual floating point numbers. Tuples may have zero or one element.

```

16686 \scan_new:N \s__fp_tuple
16687 \cs_new_protected:Npn \__fp_tuple_chk:w #1 ;
16688 { \__fp_misused:n { \s__fp_tuple \__fp_tuple_chk:w #1 ; } }
16689 \tl_const:Nn \c__fp_empty_tuple_fp
16690 { \s__fp_tuple \__fp_tuple_chk:w { } ; }

```

(End definition for \s__fp_tuple, __fp_tuple_chk:w, and \c__fp_empty_tuple_fp.)

__fp_tuple_count:w Count the number of items in a tuple of floating points by counting semicolons. The technique is very similar to \tl_count:n, but with the loop built-in. Checking for the end of the loop is done with the \use_none:n #1 construction.

```

16691 \cs_new:Npn \__fp_array_count:n #1
16692 { \__fp_tuple_count:w \s__fp_tuple \__fp_tuple_chk:w {#1} ; }
16693 \cs_new:Npn \__fp_tuple_count:w \s__fp_tuple \__fp_tuple_chk:w #1 ;
16694 {
16695   \int_value:w \__fp_int_eval:w 0
16696   \__fp_tuple_count_loop:Nw #1 { ? \prg_break: } ;
16697   \prg_break_point:
16698   \__fp_int_eval_end:
16699 }
16700 \cs_new:Npn \__fp_tuple_count_loop:Nw #1#2;
16701 { \use_none:n #1 + 1 \__fp_tuple_count_loop:Nw }

```

(End definition for __fp_tuple_count:w, __fp_array_count:n, and __fp_tuple_count_loop:Nw.)

__fp_if_type_fp:NTwFw Used as __fp_if_type_fp:NTwFw *<marker>* {*<true code>*} \s__fp {*<false code>*} \s__fp_stop, this test whether the *<marker>* is \s__fp or not and runs the appropriate *<code>*. The very unusual syntax is for optimization purposes as that function is used for all floating point operations.

```

16702 \cs_new:Npn \__fp_if_type_fp:NTwFw #1 \s__fp #2 #3 \s__fp_stop {#2}

```

(End definition for __fp_if_type_fp:NTwFw.)

__fp_array_if_all_fp:nTF True if all items are floating point numbers. Used for min.

```

16703 \cs_new:Npn \__fp_array_if_all_fp:nTF #1
16704 {
16705   \__fp_array_if_all_fp_loop:w #1 { \s__fp \prg_break: } ;
16706   \prg_break_point: \use_i:nn
16707 }
16708 \cs_new:Npn \__fp_array_if_all_fp_loop:w #1#2 ;
16709 {
16710   \__fp_if_type_fp:NTwFw
16711   #1 \__fp_array_if_all_fp_loop:w

```

```

16712     \s__fp { \prg_break:n \use_iii:nnn }
16713     \s__fp_stop
16714 }

```

(End definition for _fp_array_if_all_fp:nTF and _fp_array_if_all_fp_loop:w.)

_fp_type_from_scan:N Used as _fp_type_from_scan:N *<token>*. Grabs the pieces of the stringified *<token>* which lies after the first s__fp. If the *<token>* does not contain that string, the result is _?.

```

16715 \cs_new:Npn \_fp_type_from_scan:N #1
16716 {
16717     \_fp_if_type_fp:NTwFw
16718     #1 { }
16719     \s__fp { \_fp_type_from_scan_other:N #1 }
16720     \s__fp_stop
16721 }
16722 \cs_new:Npx \_fp_type_from_scan_other:N #1
16723 {
16724     \exp_not:N \exp_after:wN \exp_not:N \_fp_type_from_scan:w
16725     \exp_not:N \token_to_str:N #1 \s__fp_mark
16726     \tl_to_str:n { s__fp _? } \s__fp_mark \s__fp_stop
16727 }
16728 \exp_last_unbraced:NNNNo
16729 \cs_new:Npn \_fp_type_from_scan:w #1
16730 { \tl_to_str:n { s__fp } } #2 \s__fp_mark #3 \s__fp_stop {#2}

```

(End definition for _fp_type_from_scan:N, _fp_type_from_scan_other:N, and _fp_type_from_scan:w.)

_fp_change_func_type:NNN Arguments are *<type marker>* *<function>* *<recovery>*. This gives the function obtained by placing the type after @@. If the function is not defined then *<recovery>* *<function>* is used instead; however that test is not run when the *<type marker>* is s__fp.

```

16731 \cs_new:Npn \_fp_change_func_type:NNN #1#2#3
16732 {
16733     \_fp_if_type_fp:NTwFw
16734     #1 #2
16735     \s__fp
16736     {
16737         \exp_after:wN \_fp_change_func_type_chk:NNN
16738         \cs:w
16739         __fp \_fp_type_from_scan_other:N #1
16740         \exp_after:wN \_fp_change_func_type_aux:w \token_to_str:N #2
16741         \cs_end:
16742         #2 #3
16743     }
16744     \s__fp_stop
16745 }
16746 \exp_last_unbraced:NNNNo
16747 \cs_new:Npn \_fp_change_func_type_aux:w #1 { \tl_to_str:n { __fp } } { }
16748 \cs_new:Npn \_fp_change_func_type_chk:NNN #1#2#3
16749 {
16750     \if_meaning:w \scan_stop: #1
16751     \exp_after:wN #3 \exp_after:wN #2
16752     \else:

```

```

16753     \exp_after:wN #1
16754     \fi:
16755 }

```

(End definition for _fp_change_func_type:NNN, _fp_change_func_type_aux:w, and _fp_change_func_type_chk:NNN.)

```

\_fp_exp_after_any_f:Nnw
\_fp_exp_after_any_f:nw
\_fp_exp_after_expr_stop_f:nw

```

The Nnw function simply dispatches to the appropriate _fp_exp_after..._f:nw with “...” (either empty or $\langle type \rangle$) extracted from #1, which should start with \s_fp. If it doesn’t start with \s_fp the function _fp_exp_after_?_f:nw defined in l3fp-parse gives an error; another special $\langle type \rangle$ is stop, useful for loops, see below. The nw function has an important optimization for floating points numbers; it also fetches its type marker #2 from the floating point.

```

16756 \cs_new:Npn \_fp_exp_after_any_f:Nnw #1
16757 { \cs:w \_fp_exp_after \_fp_type_from_scan_other:N #1 _f:nw \cs_end: }
16758 \cs_new:Npn \_fp_exp_after_any_f:nw #1#2
16759 {
16760     \_fp_if_type_fp:NTwFw
16761     #2 \_fp_exp_after_f:nw
16762     \s\_fp { \_fp_exp_after_any_f:Nnw #2 }
16763     \s\_fp_stop
16764     {#1} #2
16765 }
16766 \cs_new_eq:NN \_fp_exp_after_expr_stop_f:nw \use_none:nn

```

(End definition for _fp_exp_after_any_f:Nnw, _fp_exp_after_any_f:nw, and _fp_exp_after_expr_stop_f:nw.)

```

\_fp_exp_after_tuple_o:w
\_fp_exp_after_tuple_f:nw
\_fp_exp_after_array_f:w

```

The loop works by using the n argument of _fp_exp_after_any_f:nw to place the loop macro after the next item in the tuple and expand it.

```

\_fp_exp_after_array_f:w
 $\langle fp_1 \rangle$  ;
...
 $\langle fp_n \rangle$  ;
\s\_fp_expr_stop

```

```

16767 \cs_new:Npn \_fp_exp_after_tuple_o:w
16768 { \_fp_exp_after_tuple_f:nw { \exp_after:wN \exp_stop_f: } }
16769 \cs_new:Npn \_fp_exp_after_tuple_f:nw
16770 #1 \s\_fp_tuple \_fp_tuple_chk:w #2 ;
16771 {
16772     \exp_after:wN \s\_fp_tuple
16773     \exp_after:wN \_fp_tuple_chk:w
16774     \exp_after:wN {
16775         \exp:w \exp_end_continue_f:w
16776         \_fp_exp_after_array_f:w #2 \s\_fp_expr_stop
16777     }
16778     \exp_after:wN ;
16779     \exp:w \exp_end_continue_f:w #1
16780 }
16781 \cs_new:Npn \_fp_exp_after_array_f:w
16782 { \_fp_exp_after_any_f:nw { \_fp_exp_after_array_f:w } }

```

(End definition for _fp_exp_after_tuple_o:w, _fp_exp_after_tuple_f:nw, and _fp_exp_after_array_f:w.)

25.8 Packing digits

When a positive integer `#1` is known to be less than 10^8 , the following trick splits it into two blocks of 4 digits, padding with zeros on the left.

```
\cs_new:Npn \pack:NNNNNw #1 #2#3#4#5 #6; { {#2#3#4#5} {#6} }
\exp_after:wN \pack:NNNNNw
  \__fp_int_value:w \__fp_int_eval:w 1 0000 0000 + #1 ;
```

The idea is that adding 10^8 to the number ensures that it has exactly 9 digits, and can then easily find which digits correspond to what position in the number. Of course, this can be modified for any number of digits less or equal to 9 (we are limited by `TeX`'s integers). This method is very heavily relied upon in `l3fp-basics`.

More specifically, the auxiliary inserts `+ #1#2#3#4#5 ; {#6}`, which allows us to compute several blocks of 4 digits in a nested manner, performing carries on the fly. Say we want to compute 12345×66778899 . With simplified names, we would do

```
\exp_after:wN \post_processing:w
\__fp_int_value:w \__fp_int_eval:w - 5 0000
  \exp_after:wN \pack:NNNNNw
    \__fp_int_value:w \__fp_int_eval:w 4 9995 0000
      + 12345 * 6677
    \exp_after:wN \pack:NNNNNw
      \__fp_int_value:w \__fp_int_eval:w 5 0000 0000
        + 12345 * 8899 ;
```

The `\exp_after:wN` triggers `\int_value:w __fp_int_eval:w`, which starts a first computation, whose initial value is $-5\,0000$ (the “leading shift”). In that computation appears an `\exp_after:wN`, which triggers the nested computation `\int_value:w __fp_int_eval:w` with starting value $4\,9995\,0000$ (the “middle shift”). That, in turn, expands `\exp_after:wN` which triggers the third computation. The third computation's value is $5\,0000\,0000 + 12345 \times 8899$, which has 9 digits. Adding $5 \cdot 10^8$ to the product allowed us to know how many digits to expect as long as the numbers to multiply are not too big; it also works to some extent with negative results. The `pack` function puts the last 4 of those 9 digits into a brace group, moves the semi-colon delimiter, and inserts a `+`, which combines the carry with the previous computation. The shifts nicely combine into $5\,0000\,0000/10^4 + 4\,9995\,0000 = 5\,0000\,0000$. As long as the operands are in some range, the result of this second computation has 9 digits. The corresponding `pack` function, expanded after the result is computed, braces the last 4 digits, and leaves `+ <5 digits>` for the initial computation. The “leading shift” cancels the combination of the other shifts, and the `\post_processing:w` takes care of packing the last few digits.

Admittedly, this is quite intricate. It is probably the key in making `l3fp` as fast as other pure `TeX` floating point units despite its increased precision. In fact, this is used so much that we provide different sets of packing functions and shifts, depending on ranges of input.

This set of shifts allows for computations involving results in the range $[-4 \cdot 10^8, 5 \cdot 10^8 - 1]$. Shifted values all have exactly 9 digits.

```
\__fp_pack:NNNNNw
\c__fp_trailing_shift_int
\c__fp_middle_shift_int
\c__fp_leading_shift_int
16783 \int_const:Nn \c__fp_leading_shift_int { - 5 0000 }
16784 \int_const:Nn \c__fp_middle_shift_int { 5 0000 * 9999 }
16785 \int_const:Nn \c__fp_trailing_shift_int { 5 0000 * 10000 }
16786 \cs_new:Npn \__fp_pack:NNNNNw #1 #2#3#4#5 #6; { + #1#2#3#4#5 ; {#6} }
```

(End definition for `_fp_pack:NNNNNw` and others.)

`_fp_pack_big:NNNNNw`
`\c_fp_big_trailing_shift_int`
`\c_fp_big_middle_shift_int`
`\c_fp_big_leading_shift_int`

This set of shifts allows for computations involving results in the range $[-5 \cdot 10^8, 6 \cdot 10^8 - 1]$ (actually a bit more). Shifted values all have exactly 10 digits. Note that the upper bound is due to $\text{T}_{\text{E}}\text{X}$'s limit of $2^{31} - 1$ on integers. The shifts are chosen to be roughly the mid-point of 10^9 and 2^{31} , the two bounds on 10-digit integers in $\text{T}_{\text{E}}\text{X}$.

```
16787 \int_const:Nn \c_fp_big_leading_shift_int { - 15 2374 }
16788 \int_const:Nn \c_fp_big_middle_shift_int { 15 2374 * 9999 }
16789 \int_const:Nn \c_fp_big_trailing_shift_int { 15 2374 * 10000 }
16790 \cs_new:Npn \_fp_pack_big:NNNNNw #1#2 #3#4#5#6 #7;
16791 { + #1#2#3#4#5#6 ; {#7} }
```

(End definition for `_fp_pack_big:NNNNNw` and others.)

`_fp_pack_Bigg:NNNNNw`
`\c_fp_Bigg_trailing_shift_int`
`\c_fp_Bigg_middle_shift_int`
`\c_fp_Bigg_leading_shift_int`

This set of shifts allows for computations with results in the range $[-1 \cdot 10^9, 147483647]$; the end-point is $2^{31} - 1 - 2 \cdot 10^9 \simeq 1.47 \cdot 10^8$. Shifted values all have exactly 10 digits.

```
16792 \int_const:Nn \c_fp_Bigg_leading_shift_int { - 20 0000 }
16793 \int_const:Nn \c_fp_Bigg_middle_shift_int { 20 0000 * 9999 }
16794 \int_const:Nn \c_fp_Bigg_trailing_shift_int { 20 0000 * 10000 }
16795 \cs_new:Npn \_fp_pack_Bigg:NNNNNw #1#2 #3#4#5#6 #7;
16796 { + #1#2#3#4#5#6 ; {#7} }
```

(End definition for `_fp_pack_Bigg:NNNNNw` and others.)

`_fp_pack_twice_four:wNNNNNNNN`

`_fp_pack_twice_four:wNNNNNNNN` *(tokens)* ; $\langle \geq 8 \text{ digits} \rangle$

Grabs two sets of 4 digits and places them before the semi-colon delimiter. Putting several copies of this function before a semicolon packs more digits since each takes the digits packed by the others in its first argument.

```
16797 \cs_new:Npn \_fp_pack_twice_four:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
16798 { #1 {#2#3#4#5} {#6#7#8#9} ; }
```

(End definition for `_fp_pack_twice_four:wNNNNNNNN`.)

`_fp_pack_eight:wNNNNNNNN`

`_fp_pack_eight:wNNNNNNNN` *(tokens)* ; $\langle \geq 8 \text{ digits} \rangle$

Grabs one set of 8 digits and places them before the semi-colon delimiter as a single group. Putting several copies of this function before a semicolon packs more digits since each takes the digits packed by the others in its first argument.

```
16799 \cs_new:Npn \_fp_pack_eight:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
16800 { #1 {#2#3#4#5#6#7#8#9} ; }
```

(End definition for `_fp_pack_eight:wNNNNNNNN`.)

`_fp_basics_pack_low:NNNNNw`
`_fp_basics_pack_high:NNNNNw`
`_fp_basics_pack_high_carry:w`

Addition and multiplication of significands are done in two steps: first compute a (more or less) exact result, then round and pack digits in the final (braced) form. These functions take care of the packing, with special attention given to the case where rounding has caused a carry. Since rounding can only shift the final digit by 1, a carry always produces an exact power of 10. Thus, `_fp_basics_pack_high_carry:w` is always followed by four times `{0000}`.

This is used in `l3fp-basics` and `l3fp-extended`.

```
16801 \cs_new:Npn \_fp_basics_pack_low:NNNNNw #1 #2#3#4#5 #6;
16802 { + #1 - 1 ; {#2#3#4#5} {#6} ; }
16803 \cs_new:Npn \_fp_basics_pack_high:NNNNNw #1 #2#3#4#5 #6;
16804 {
```

```

16805     \if_meaning:w 2 #1
16806         \__fp_basics_pack_high_carry:w
16807     \fi:
16808     ; {#2#3#4#5} {#6}
16809 }
16810 \cs_new:Npn \__fp_basics_pack_high_carry:w \fi: ; #1
16811 { \fi: + 1 ; {1000} }

```

(End definition for `__fp_basics_pack_low:NNNNw`, `__fp_basics_pack_high:NNNNw`, and `__fp_basics_pack_high_carry:w`.)

`__fp_basics_pack_weird_low:NNNNw`
`__fp_basics_pack_weird_high:NNNNNNNNw`

This is used in `l3fp-basics` for additions and divisions. Their syntax is confusing, hence the name.

```

16812 \cs_new:Npn \__fp_basics_pack_weird_low:NNNNw #1 #2#3#4 #5;
16813 {
16814     \if_meaning:w 2 #1
16815         + 1
16816     \fi:
16817     \__fp_int_eval_end:
16818     #2#3#4; {#5} ;
16819 }
16820 \cs_new:Npn \__fp_basics_pack_weird_high:NNNNNNNNw
16821 1 #1#2#3#4 #5#6#7#8 #9; { ; {#1#2#3#4} {#5#6#7#8} {#9} }

```

(End definition for `__fp_basics_pack_weird_low:NNNNw` and `__fp_basics_pack_weird_high:NNNNNNNNw`.)

25.9 Decimate (dividing by a power of 10)

`__fp_decimate:nNnnnn`

`__fp_decimate:nNnnnn {⟨shift⟩} {f1}`
`{⟨X1⟩} {⟨X2⟩} {⟨X3⟩} {⟨X4⟩}`

Each $\langle X_i \rangle$ consists in 4 digits exactly, and $1000 \leq \langle X_1 \rangle < 9999$. The first argument determines by how much we shift the digits. $\langle f_1 \rangle$ is called as follows:

$\langle f_1 \rangle \langle \text{rounding} \rangle \{ \langle X'_1 \rangle \} \{ \langle X'_2 \rangle \} \langle \text{extra-digits} \rangle ;$

where $0 \leq \langle X'_i \rangle < 10^8 - 1$ are 8 digit integers, forming the truncation of our number. In other words,

$$\left(\sum_{i=1}^4 \langle X_i \rangle \cdot 10^{-4i} \cdot 10^{-\langle \text{shift} \rangle} \right) - (\langle X'_1 \rangle \cdot 10^{-8} + \langle X'_2 \rangle \cdot 10^{-16}) = 0. \langle \text{extra-digits} \rangle \cdot 10^{-16} \in [0, 10^{-16}).$$

To round properly later, we need to remember some information about the difference. The $\langle \text{rounding} \rangle$ digit is 0 if and only if the difference is exactly 0, and 5 if and only if the difference is exactly $0.5 \cdot 10^{-16}$. Otherwise, it is the (non-0, non-5) digit closest to 10^{17} times the difference. In particular, if the shift is 17 or more, all the digits are dropped, $\langle \text{rounding} \rangle$ is 1 (not 0), and $\langle X'_1 \rangle$ and $\langle X'_2 \rangle$ are both zero.

If the shift is 1, the $\langle \text{rounding} \rangle$ digit is simply the only digit that was pushed out of the brace groups (this is important for subtraction). It would be more natural for the $\langle \text{rounding} \rangle$ digit to be placed after the $\langle X'_i \rangle$, but the choice we make involves less reshuffling.

Note that this function treats negative $\langle \text{shift} \rangle$ as 0.

```

16822 \cs_new:Npn \__fp_decimate:nNnnnn #1
16823 {

```

```

16824 \cs:w
16825   __fp_decimate_
16826   \if_int_compare:w \__fp_int_eval:w #1 > \c__fp_prec_int
16827     tiny
16828   \else:
16829     \__fp_int_to_roman:w \__fp_int_eval:w #1
16830   \fi:
16831   :Nnnnn
16832 \cs_end:
16833 }

```

Each of the auxiliaries see the function $\langle f_1 \rangle$, followed by 4 blocks of 4 digits.

(End definition for `__fp_decimate:nNnnnn`.)

```

\__fp_decimate_:Nnnnn
\__fp_decimate_tiny:Nnnnn
16834 \cs_new:Npn \__fp_decimate_:Nnnnn #1 #2#3#4#5
16835   { #1 0 {#2#3} {#4#5} ; }
16836 \cs_new:Npn \__fp_decimate_tiny:Nnnnn #1 #2#3#4#5
16837   { #1 1 { 0000 0000 } { 0000 0000 } 0 #2#3#4#5 ; }

```

(End definition for `__fp_decimate_:Nnnnn` and `__fp_decimate_tiny:Nnnnn`.)

```

\__fp_decimate_auxi:Nnnnn
\__fp_decimate_auxii:Nnnnn
\__fp_decimate_auxiii:Nnnnn
\__fp_decimate_auxiv:Nnnnn
\__fp_decimate_auxv:Nnnnn
\__fp_decimate_auxvi:Nnnnn
\__fp_decimate_auxvii:Nnnnn
\__fp_decimate_auxviii:Nnnnn
\__fp_decimate_auxix:Nnnnn
\__fp_decimate_auxx:Nnnnn
\__fp_decimate_auxxi:Nnnnn
\__fp_decimate_auxxii:Nnnnn
\__fp_decimate_auxxiii:Nnnnn
\__fp_decimate_auxxiv:Nnnnn
\__fp_decimate_auxxv:Nnnnn
\__fp_decimate_auxxvi:Nnnnn

```

```

\__fp_decimate_auxi:Nnnnn <math>f_1</math> {<math>X_1</math>} {<math>X_2</math>} {<math>X_3</math>} {<math>X_4</math>}

```

Shifting happens in two steps: compute the $\langle \textit{rounding} \rangle$ digit, and repack digits into two blocks of 8. The sixteen functions are very similar, and defined through `__fp_tmp:w`. The arguments are as follows: #1 indicates which function is being defined; after one step of expansion, #2 yields the “extra digits” which are then converted by `__fp_round_digit:Nw` to the $\langle \textit{rounding} \rangle$ digit (note the + separating blocks of digits to avoid overflowing TeX’s integers). This triggers the f-expansion of `__fp_decimate_pack:nnnnnnnnnw`,⁹ responsible for building two blocks of 8 digits, and removing the rest. For this to work, #3 alternates between braced and unbraced blocks of 4 digits, in such a way that the 5 first and 5 next token groups yield the correct blocks of 8 digits.

```

16838 \cs_new:Npn \__fp_tmp:w #1 #2 #3
16839   {
16840     \cs_new:cpn { __fp_decimate_ #1 :Nnnnn } ##1 ##2##3##4##5
16841     {
16842       \exp_after:wN ##1
16843       \int_value:w
16844       \exp_after:wN \__fp_round_digit:Nw #2 ;
16845       \__fp_decimate_pack:nnnnnnnnnw #3 ;
16846     }
16847   }
16848 \__fp_tmp:w {i} {\use_none:nnn #50}{ 0{#2}#3{#4}#5 }
16849 \__fp_tmp:w {ii} {\use_none:nn #5 }{ 00{#2}#3{#4}#5 }
16850 \__fp_tmp:w {iii} {\use_none:n #5 }{ 000{#2}#3{#4}#5 }
16851 \__fp_tmp:w {iv} { #5 }{ {0000}#2{#3}#4 #5 }
16852 \__fp_tmp:w {v} {\use_none:nnn #4#5 }{ 0{0000}#2{#3}#4 #5 }
16853 \__fp_tmp:w {vi} {\use_none:nn #4#5 }{ 00{0000}#2{#3}#4 #5 }
16854 \__fp_tmp:w {vii} {\use_none:n #4#5 }{ 000{0000}#2{#3}#4 #5 }
16855 \__fp_tmp:w {viii}{ #4#5 }{ {0000}0000{#2}#3 #4 #5 }
16856 \__fp_tmp:w {ix} {\use_none:nnn #3#4+#5}{ 0{0000}0000{#2}#3 #4 #5 }

```

⁹No, the argument spec is not a mistake: the function calls an auxiliary to do half of the job.

```

16857 \__fp_tmp:w {x}    {\use_none:nn #3#4+#5}{ 00{0000}0000{#2}#3 #4 #5    }
16858 \__fp_tmp:w {xi}   {\use_none:n  #3#4+#5}{ 000{0000}0000{#2}#3 #4 #5    }
16859 \__fp_tmp:w {xii}  { #3#4+#5}{ {0000}0000{0000}#2 #3 #4 #5    }
16860 \__fp_tmp:w {xiii}{\use_none:nnn#2#3+#4#5}{ 0{0000}0000{0000}#2 #3 #4 #5    }
16861 \__fp_tmp:w {xiv}  {\use_none:nn #2#3+#4#5}{ 00{0000}0000{0000}#2 #3 #4 #5    }
16862 \__fp_tmp:w {xv}   {\use_none:n  #2#3+#4#5}{ 000{0000}0000{0000}#2 #3 #4 #5    }
16863 \__fp_tmp:w {xvi}  { #2#3+#4#5}{ {0000}0000{0000}0000 #2 #3 #4 #5    }

```

(End definition for __fp_decimate_auxi:Nnnnn and others.)

__fp_decimate_pack:nnnnnnnnnw

The computation of the *<rounding>* digit leaves an unfinished \int_value:w, which expands the following functions. This allows us to repack nicely the digits we keep. Those digits come as an alternation of unbraced and braced blocks of 4 digits, such that the first 5 groups of token consist in 4 single digits, and one brace group (in some order), and the next 5 have the same structure. This is followed by some digits and a semicolon.

```

16864 \cs_new:Npn \__fp_decimate_pack:nnnnnnnnnw #1#2#3#4#5
16865   { \__fp_decimate_pack:nnnnnw { #1#2#3#4#5 } }
16866 \cs_new:Npn \__fp_decimate_pack:nnnnnw #1 #2#3#4#5#6
16867   { {#1} {#2#3#4#5#6} }

```

(End definition for __fp_decimate_pack:nnnnnnnnnw.)

25.10 Functions for use within primitive conditional branches

The functions described in this section are not pretty and can easily be misused. When correctly used, each of them removes one \fi: as part of its parameter text, and puts one back as part of its replacement text.

Many computation functions in l3fp must perform tests on the type of floating points that they receive. This is often done in an \if_case:w statement or another conditional statement, and only a few cases lead to actual computations: most of the special cases are treated using a few standard functions which we define now. A typical use context for those functions would be

```

\if_case:w <integer> \exp_stop_f:
  \__fp_case_return_o:Nw <fp var>
\or: \__fp_case_use:nw {<some computation>}
\or: \__fp_case_return_same_o:w
\or: \__fp_case_return:nw {<something>}
\fi:
<junk>
<floating point>

```

In this example, the case 0 returns the floating point *<fp var>*, expanding once after that floating point. Case 1 does *<some computation>* using the *<floating point>* (presumably compute the operation requested by the user in that non-trivial case). Case 2 returns the *<floating point>* without modifying it, removing the *<junk>* and expanding once after. Case 3 closes the conditional, removes the *<junk>* and the *<floating point>*, and expands *<something>* next. In other cases, the “*<junk>*” is expanded, performing some other operation on the *<floating point>*. We provide similar functions with two trailing *<floating points>*.

`__fp_case_use:nw` This function ends a \TeX conditional, removes junk until the next floating point, and places its first argument before that floating point, to perform some operation on the floating point.

```
16868 \cs_new:Npn \__fp_case_use:nw #1#2 \fi: #3 \s__fp { \fi: #1 \s__fp }
```

(End definition for `__fp_case_use:nw`.)

`__fp_case_return:nw` This function ends a \TeX conditional, removes junk and a floating point, and places its first argument in the input stream. A quirk is that we don't define this function requiring a floating point to follow, simply anything ending in a semicolon. This, in turn, means that the *junk* may not contain semicolons.

```
16869 \cs_new:Npn \__fp_case_return:nw #1#2 \fi: #3 ; { \fi: #1 }
```

(End definition for `__fp_case_return:nw`.)

`__fp_case_return_o:Nw` This function ends a \TeX conditional, removes junk and a floating point, and returns its first argument (an *fp var*) then expands once after it.

```
16870 \cs_new:Npn \__fp_case_return_o:Nw #1#2 \fi: #3 \s__fp #4 ;
16871 { \fi: \exp_after:wN #1 }
```

(End definition for `__fp_case_return_o:Nw`.)

`__fp_case_return_same_o:w` This function ends a \TeX conditional, removes junk, and returns the following floating point, expanding once after it.

```
16872 \cs_new:Npn \__fp_case_return_same_o:w #1 \fi: #2 \s__fp
16873 { \fi: \__fp_exp_after_o:w \s__fp }
```

(End definition for `__fp_case_return_same_o:w`.)

`__fp_case_return_o:Nww` Same as `__fp_case_return_o:Nw` but with two trailing floating points.

```
16874 \cs_new:Npn \__fp_case_return_o:Nww #1#2 \fi: #3 \s__fp #4 ; #5 ;
16875 { \fi: \exp_after:wN #1 }
```

(End definition for `__fp_case_return_o:Nww`.)

`__fp_case_return_i_o:ww` Similar to `__fp_case_return_same_o:w`, but this returns the first or second of two trailing floating point numbers, expanding once after the result.

```
16876 \cs_new:Npn \__fp_case_return_i_o:ww #1 \fi: #2 \s__fp #3 ; \s__fp #4 ;
16877 { \fi: \__fp_exp_after_o:w \s__fp #3 ; }
16878 \cs_new:Npn \__fp_case_return_ii_o:ww #1 \fi: #2 \s__fp #3 ;
16879 { \fi: \__fp_exp_after_o:w }
```

(End definition for `__fp_case_return_i_o:ww` and `__fp_case_return_ii_o:ww`.)

25.11 Integer floating points

`_fp_int_p:w` Tests if the floating point argument is an integer. For normal floating point numbers, this holds if the rounding digit resulting from `_fp_decimate:nNnnnn` is 0.

`_fp_int:wTF`

```

16880 \prg_new_conditional:Npnn \_fp_int:w \s\_fp \_fp_chk:w #1 #2 #3 #4;
16881 { TF , T , F , p }
16882 {
16883   \if_case:w #1 \exp_stop_f:
16884     \prg_return_true:
16885   \or:
16886     \if_charcode:w 0
16887       \_fp_decimate:nNnnnn { \c\_fp_prec_int - #3 }
16888       \_fp_use_i_until_s:nw #4
16889       \prg_return_true:
16890     \else:
16891       \prg_return_false:
16892     \fi:
16893   \else: \prg_return_false:
16894   \fi:
16895 }

```

(End definition for `_fp_int:wTF`.)

25.12 Small integer floating points

`_fp_small_int:wTF` Tests if the floating point argument is an integer or $\pm\infty$. If so, it is clipped to an integer in the range $[-10^8, 10^8]$ and fed as a braced argument to the *⟨true code⟩*. Otherwise, the *⟨false code⟩* is performed.

`_fp_small_int_true:wTF`

`_fp_small_int_normal:NnwTF`

`_fp_small_int_test:NnnwNTF`

First filter special cases: zeros and infinities are integers, `nan` is not. For normal numbers, decimate. If the rounding digit is not 0 run the *⟨false code⟩*. If it is, then the integer is `#2 #3`; use `#3` if `#2` vanishes and otherwise `10^8`.

```

16896 \cs_new:Npn \_fp_small_int:wTF \s\_fp \_fp_chk:w #1#2
16897 {
16898   \if_case:w #1 \exp_stop_f:
16899     \_fp_case_return:nw { \_fp_small_int_true:wTF 0 ; }
16900   \or: \exp_after:wN \_fp_small_int_normal:NnwTF
16901   \or:
16902     \_fp_case_return:nw
16903     {
16904       \exp_after:wN \_fp_small_int_true:wTF \int_value:w
16905       \if_meaning:w 2 #2 - \fi: 1 0000 0000 ;
16906     }
16907   \else: \_fp_case_return:nw \use_ii:nn
16908   \fi:
16909   #2
16910 }
16911 \cs_new:Npn \_fp_small_int_true:wTF #1; #2#3 { #2 {#1} }
16912 \cs_new:Npn \_fp_small_int_normal:NnwTF #1#2#3;
16913 {
16914   \_fp_decimate:nNnnnn { \c\_fp_prec_int - #2 }
16915   \_fp_small_int_test:NnnwNw
16916   #3 #1
16917 }

```

```

16918 \cs_new:Npn \__fp_small_int_test:NnnwNw #1#2#3#4; #5
16919 {
16920   \if_meaning:w 0 #1
16921     \exp_after:wN \__fp_small_int_true:wTF
16922     \int_value:w \if_meaning:w 2 #5 - \fi:
16923     \if_int_compare:w #2 > 0 \exp_stop_f:
16924       1 0000 0000
16925     \else:
16926       #3
16927     \fi:
16928     \exp_after:wN ;
16929   \else:
16930     \exp_after:wN \use_ii:nn
16931   \fi:
16932 }

```

(End definition for `__fp_small_int:wTF` and others.)

25.13 Fast string comparison

`__fp_str_if_eq:nn` A private version of the low-level string comparison function. As the nature of the arguments is restricted and as speed is of the essence, this version does not seek to deal with `#` tokens. No `l3sys` or `l3luatex` just yet so we have to define in terms of primitives.

```

16933 \sys_if_engine luatex:TF
16934 {
16935   \cs_new:Npn \__fp_str_if_eq:nn #1#2
16936   {
16937     \tex_directlua:D
16938     {
16939       l3kernel.strcmp
16940       (
16941         " \tex_luaescapestring:D {#1}",
16942         " \tex_luaescapestring:D {#2}"
16943       )
16944     }
16945   }
16946 }
16947 { \cs_new_eq:NN \__fp_str_if_eq:nn \tex_strcmp:D }

```

(End definition for `__fp_str_if_eq:nn`.)

25.14 Name of a function from its `l3fp-parse` name

`__fp_func_to_name:N` The goal is to convert for instance `__fp_sin_o:w` to `sin`. This is used in error messages
`__fp_func_to_name_aux:w` hence does not need to be fast.

```

16948 \cs_new:Npn \__fp_func_to_name:N #1
16949 {
16950   \exp_last_unbraced:Nf
16951   \__fp_func_to_name_aux:w { \cs_to_str:N #1 } X
16952 }
16953 \cs_set_protected:Npn \__fp_tmp:w #1 #2
16954 { \cs_new:Npn \__fp_func_to_name_aux:w ##1 #1 ##2 #2 ##3 X {##2} }
16955 \exp_args:Nff \__fp_tmp:w { \tl_to_str:n { __fp_ } }
16956 { \tl_to_str:n { _o: } }

```


(End definition for `_fp_func_to_name:N` and `_fp_func_to_name_aux:w`.)

25.15 Messages

Using a floating point directly is an error.

```

16957 \__kernel_msg_new:nnnn { kernel } { misused-fp }
16958 { A~floating~point~with~value~'#1'~was~misused. }
16959 {
16960   To~obtain~the~value~of~a~floating~point~variable,~use~
16961   '\token_to_str:N \fp_to_decimal:N',~
16962   '\token_to_str:N \fp_to_tl:N',~or~other~
16963   conversion~functions.
16964 }
16965 </initex | package>

```

26 13fp-traps Implementation

```

16966 (*initex | package)
16967 <@@=fp>

```

Exceptions should be accessed by an `n`-type argument, among

- `invalid_operation`
- `division_by_zero`
- `overflow`
- `underflow`
- `inexact` (actually never used).

26.1 Flags

Flags to denote exceptions.

```

flag_fp_invalid_operation \flag_new:n { fp_invalid_operation }
flag_fp_division_by_zero \flag_new:n { fp_division_by_zero }
flag_fp_overflow         \flag_new:n { fp_overflow }
flag_fp_underflow        \flag_new:n { fp_underflow }

```

(End definition for flag `fp_invalid_operation` and others. These variables are documented on page 207.)

26.2 Traps

Exceptions can be trapped to obtain custom behaviour. When an invalid operation or a division by zero is trapped, the trap receives as arguments the result as an `N`-type floating point number, the function name (multiple letters for prefix operations, or a single symbol for infix operations), and the operand(s). When an overflow or underflow is trapped, the trap receives the resulting overly large or small floating point number if it is not too big, otherwise it receives $+\infty$. Currently, the `inexact` exception is entirely ignored.

The behaviour when an exception occurs is controlled by the definitions of the functions

- __fp_invalid_operation:nnw,
- __fp_invalid_operation_o:Nww,
- __fp_invalid_operation_tl_o:ff,
- __fp_division_by_zero_o:Nnw,
- __fp_division_by_zero_o:NNww,
- __fp_overflow:w,
- __fp_underflow:w.

Rather than changing them directly, we provide a user interface as \fp_trap:nn {*exception*} {*way of trapping*}, where the *way of trapping* is one of **error**, **flag**, or **none**.

We also provide __fp_invalid_operation_o:nw, defined in terms of __fp_invalid_operation:nnw.

\fp_trap:nn

```

16972 \cs_new_protected:Npn \fp_trap:nn #1#2
16973 {
16974   \cs_if_exist_use:cF { __fp_trap_#1_set_#2: }
16975   {
16976     \clist_if_in:nnTF
16977       { invalid_operation , division_by_zero , overflow , underflow }
16978       {#1}
16979       {
16980         \__kernel_msg_error:nnxx { kernel }
16981         { unknown-fpu-trap-type } {#1} {#2}
16982       }
16983       {
16984         \__kernel_msg_error:nnx
16985         { kernel } { unknown-fpu-exception } {#1}
16986       }
16987     }
16988   }

```

(End definition for \fp_trap:nn. This function is documented on page 207.)

\fp_trap_invalid_operation_set_error: We provide three types of trapping for invalid operations: either produce an error and raise the relevant flag; or only raise the flag; or don't even raise the flag. In most cases, the function produces as a result its first argument, possibly with post-expansion.

```

16989 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_error:
16990 { \__fp_trap_invalid_operation_set:N \prg_do_nothing: }
16991 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_flag:
16992 { \__fp_trap_invalid_operation_set:N \use_none:nnnnn }
16993 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_none:
16994 { \__fp_trap_invalid_operation_set:N \use_none:nnnnnnn }
16995 \cs_new_protected:Npn \__fp_trap_invalid_operation_set:N #1
16996 {
16997   \exp_args:Nno \use:n
16998   { \cs_set:Npn \__fp_invalid_operation:nnw ##1##2##3; }
16999   {

```

```

17000         #1
17001         \__fp_error:nmfn { fp-invalid } {##2} { \fp_to_tl:n { ##3; } } { }
17002         \flag_raise_if_clear:n { fp_invalid_operation }
17003         ##1
17004     }
17005     \exp_args:Nno \use:n
17006     { \cs_set:Npn \__fp_invalid_operation_o:Nnw ##1##2; ##3; }
17007     {
17008         #1
17009         \__fp_error:nffn { fp-invalid-ii }
17010         { \fp_to_tl:n { ##2; } } { \fp_to_tl:n { ##3; } } {##1}
17011         \flag_raise_if_clear:n { fp_invalid_operation }
17012         \exp_after:wN \c_nan_fp
17013     }
17014     \exp_args:Nno \use:n
17015     { \cs_set:Npn \__fp_invalid_operation_tl_o:ff ##1##2 }
17016     {
17017         #1
17018         \__fp_error:nffn { fp-invalid } {##1} {##2} { }
17019         \flag_raise_if_clear:n { fp_invalid_operation }
17020         \exp_after:wN \c_nan_fp
17021     }
17022 }

```

(End definition for __fp_trap_invalid_operation_set_error: and others.)

__fp_trap_division_by_zero_set_error: We provide three types of trapping for invalid operations and division by zero: either produce an error and raise the relevant flag; or only raise the flag; or don't even raise the flag. In all cases, the function must produce a result, namely its first argument, $\pm\infty$ or NaN.

```

17023 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_error:
17024 { \__fp_trap_division_by_zero_set:N \prg_do_nothing: }
17025 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_flag:
17026 { \__fp_trap_division_by_zero_set:N \use_none:nnnnn }
17027 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_none:
17028 { \__fp_trap_division_by_zero_set:N \use_none:nnnnnnn }
17029 \cs_new_protected:Npn \__fp_trap_division_by_zero_set:N #1
17030 {
17031     \exp_args:Nno \use:n
17032     { \cs_set:Npn \__fp_division_by_zero_o:Nnw ##1##2##3; }
17033     {
17034         #1
17035         \__fp_error:nmfn { fp-zero-div } {##2} { \fp_to_tl:n { ##3; } } { }
17036         \flag_raise_if_clear:n { fp_division_by_zero }
17037         \exp_after:wN ##1
17038     }
17039     \exp_args:Nno \use:n
17040     { \cs_set:Npn \__fp_division_by_zero_o:NNnw ##1##2##3; ##4; }
17041     {
17042         #1
17043         \__fp_error:nffn { fp-zero-div-ii }
17044         { \fp_to_tl:n { ##3; } } { \fp_to_tl:n { ##4; } } {##2}
17045         \flag_raise_if_clear:n { fp_division_by_zero }
17046         \exp_after:wN ##1

```

```

17047     }
17048 }

```

(End definition for `_fp_trap_division_by_zero_set_error:` and others.)

`_fp_trap_overflow_set_error:` Just as for invalid operations and division by zero, the three different behaviours are obtained by feeding `\prg_do_nothing:`, `\use_none:nnnnn` or `\use_none:nnnnnnn` to an auxiliary, with a further auxiliary common to overflow and underflow functions. In most cases, the argument of the `_fp_overflow:w` and `_fp_underflow:w` functions will be an (almost) normal number (with an exponent outside the allowed range), and the error message thus displays that number together with the result to which it overflowed or underflowed. For extreme cases such as `10 ** 1e9999`, the exponent would be too large for T_EX, and `_fp_overflow:w` receives $\pm\infty$ (`_fp_underflow:w` would receive ± 0); then we cannot do better than simply say an overflow or underflow occurred.

```

17049 \cs_new_protected:Npn \_fp_trap_overflow_set_error:
17050 { \_fp_trap_overflow_set:N \prg_do_nothing: }
17051 \cs_new_protected:Npn \_fp_trap_overflow_set_flag:
17052 { \_fp_trap_overflow_set:N \use_none:nnnnn }
17053 \cs_new_protected:Npn \_fp_trap_overflow_set_none:
17054 { \_fp_trap_overflow_set:N \use_none:nnnnnnn }
17055 \cs_new_protected:Npn \_fp_trap_overflow_set:N #1
17056 { \_fp_trap_overflow_set:NnNn #1 { overflow } \_fp_inf_fp:N { inf } }
17057 \cs_new_protected:Npn \_fp_trap_underflow_set_error:
17058 { \_fp_trap_underflow_set:N \prg_do_nothing: }
17059 \cs_new_protected:Npn \_fp_trap_underflow_set_flag:
17060 { \_fp_trap_underflow_set:N \use_none:nnnnn }
17061 \cs_new_protected:Npn \_fp_trap_underflow_set_none:
17062 { \_fp_trap_underflow_set:N \use_none:nnnnnnn }
17063 \cs_new_protected:Npn \_fp_trap_underflow_set:N #1
17064 { \_fp_trap_overflow_set:NnNn #1 { underflow } \_fp_zero_fp:N { 0 } }
17065 \cs_new_protected:Npn \_fp_trap_overflow_set:NnNn #1#2#3#4
17066 {
17067   \exp_args:Nno \use:n
17068   { \cs_set:cpn { \_fp_ #2 :w } \s__fp \_fp_chk:w ##1##2##3; }
17069   {
17070     #1
17071     \_fp_error:nffn
17072     { fp-flow \if_meaning:w 1 ##1 -to \fi: }
17073     { \fp_to_tl:n { \s__fp \_fp_chk:w ##1##2##3; } }
17074     { \token_if_eq_meaning:NNF 0 ##2 { - } #4 }
17075     {#2}
17076     \flag_raise_if_clear:n { fp_#2 }
17077     #3 ##2
17078   }
17079 }

```

(End definition for `_fp_trap_overflow_set_error:` and others.)

`_fp_invalid_operation:nnw` Initialize the control sequences (to log properly their existence). Then set invalid operations to trigger an error, and division by zero, overflow, and underflow to act silently on their flag.

```

\fp_division_by_zero_o:Nnw
\_fp_division_by_zero_o:NNww
\_fp_overflow:w
\_fp_underflow:w

```

```

17080 \cs_new:Npn \_fp_invalid_operation:nnw #1#2#3; { }
17081 \cs_new:Npn \_fp_invalid_operation_o:Nww #1#2; #3; { }
17082 \cs_new:Npn \_fp_invalid_operation_tl_o:ff #1 #2 { }

```

```

17083 \cs_new:Npn \__fp_division_by_zero_o:Nnw #1#2#3; { }
17084 \cs_new:Npn \__fp_division_by_zero_o:NNww #1#2#3; #4; { }
17085 \cs_new:Npn \__fp_overflow:w { }
17086 \cs_new:Npn \__fp_underflow:w { }
17087 \fp_trap:nn { invalid_operation } { error }
17088 \fp_trap:nn { division_by_zero } { flag }
17089 \fp_trap:nn { overflow } { flag }
17090 \fp_trap:nn { underflow } { flag }

```

(End definition for __fp_invalid_operation:nw and others.)

__fp_invalid_operation_o:nw Convenient short-hands for returning \c_nan_fp for a unary or binary operation, and
 __fp_invalid_operation_o:fw expanding after.

```

17091 \cs_new:Npn \__fp_invalid_operation_o:nw
17092   { \__fp_invalid_operation:nw { \exp_after:wN \c_nan_fp } }
17093 \cs_generate_variant:Nn \__fp_invalid_operation_o:nw { f }

```

(End definition for __fp_invalid_operation_o:nw.)

26.3 Errors

```

\__fp_error:nnnn
\__fp_error:nnfn
\__fp_error:nffn
\__fp_error:nfff
17094 \cs_new:Npn \__fp_error:nnnn
17095   { \__kernel_msg_expandable_error:nnnnn { kernel } }
17096 \cs_generate_variant:Nn \__fp_error:nnnn { nnf, nff , nfff }

```

(End definition for __fp_error:nnnn.)

26.4 Messages

Some messages.

```

17097 \__kernel_msg_new:nnnn { kernel } { unknown-fpu-exception }
17098   {
17099     The~FPU~exception~'#1'~is~not~known:~
17100     that~trap~will~never~be~triggered.
17101   }
17102   {
17103     The~only~exceptions~to~which~traps~can~be~attached~are \\
17104     \iow_indent:n
17105     {
17106       * ~ invalid_operation \\
17107       * ~ division_by_zero \\
17108       * ~ overflow \\
17109       * ~ underflow
17110     }
17111   }
17112 \__kernel_msg_new:nnnn { kernel } { unknown-fpu-trap-type }
17113   { The~FPU~trap~type~'#2'~is~not~known. }
17114   {
17115     The~trap~type~must~be~one~of \\
17116     \iow_indent:n
17117     {
17118       * ~ error \\
17119       * ~ flag \\

```

```

17120         * ~ none
17121     }
17122 }
17123 \__kernel_msg_new:nnn { kernel } { fp-flow }
17124 { An ~ #3 ~ occurred. }
17125 \__kernel_msg_new:nnn { kernel } { fp-flow-to }
17126 { #1 ~ #3 ed ~ to ~ #2 . }
17127 \__kernel_msg_new:nnn { kernel } { fp-zero-div }
17128 { Division-by-zero-in~ #1 (#2) }
17129 \__kernel_msg_new:nnn { kernel } { fp-zero-div-ii }
17130 { Division-by-zero-in~ (#1) #3 (#2) }
17131 \__kernel_msg_new:nnn { kernel } { fp-invalid }
17132 { Invalid-operation~ #1 (#2) }
17133 \__kernel_msg_new:nnn { kernel } { fp-invalid-ii }
17134 { Invalid-operation~ (#1) #3 (#2) }
17135 \__kernel_msg_new:nnn { kernel } { fp-unknown-type }
17136 { Unknown-type-for~' #1' }
17137 </initex | package>

```

27 13fp-round implementation

```

17138 <*initex | package>
17139 <@@=fp>

\__fp_parse_word_trunc:N
\__fp_parse_word_floor:N
\__fp_parse_word_ceil:N
17140 \cs_new:Npn \__fp_parse_word_trunc:N
17141 { \__fp_parse_function:NNN \__fp_round_o:Nw \__fp_round_to_zero:NNN }
17142 \cs_new:Npn \__fp_parse_word_floor:N
17143 { \__fp_parse_function:NNN \__fp_round_o:Nw \__fp_round_to_ninf:NNN }
17144 \cs_new:Npn \__fp_parse_word_ceil:N
17145 { \__fp_parse_function:NNN \__fp_round_o:Nw \__fp_round_to_pinf:NNN }

(End definition for \__fp_parse_word_trunc:N, \__fp_parse_word_floor:N, and \__fp_parse_word_ceil:N.)

```

```

\__fp_parse_word_round:N
\__fp_parse_round:Nw
17146 \cs_new:Npn \__fp_parse_word_round:N #1#2
17147 {
17148     \__fp_parse_function:NNN
17149     \__fp_round_o:Nw \__fp_round_to_nearest:NNN #1
17150     #2
17151 }
17152 \cs_new:Npn \__fp_parse_round:Nw #1 #2 \__fp_round_to_nearest:NNN #3#4
17153 { #2 #1 #3 }
17154

```

(End definition for __fp_parse_word_round:N and __fp_parse_round:Nw.)

27.1 Rounding tools

\c__fp_five_int This is used as the half-point for which numbers are rounded up/down.

```

17155 \int_const:Nn \c__fp_five_int { 5 }

```

(End definition for `\c_fp_five_int`.)

Floating point operations often yield a result that cannot be exactly represented in a significand with 16 digits. In that case, we need to round the exact result to a representable number. The IEEE standard defines four rounding modes:

- Round to nearest: round to the representable floating point number whose absolute difference with the exact result is the smallest. If the exact result lies exactly at the mid-point between two consecutive representable floating point numbers, round to the floating point number whose last digit is even.
- Round towards negative infinity: round to the greatest floating point number not larger than the exact result.
- Round towards zero: round to a floating point number with the same sign as the exact result, with the largest absolute value not larger than the absolute value of the exact result.
- Round towards positive infinity: round to the least floating point number not smaller than the exact result.

This is not fully implemented in `l3fp` yet, and transcendental functions fall back on the “round to nearest” mode. All rounding for basic algebra is done through the functions defined in this module, which can be redefined to change their rounding behaviour (but there is not interface for that yet).

The rounding tools available in this module are many variations on a base function `__fp_round:NNN`, which expands to `0\exp_stop_f:` or `1\exp_stop_f:` depending on whether the final result should be rounded up or down.

- `__fp_round:NNN <sign> <digit1> <digit2>` can expand to `0\exp_stop_f:` or `1\exp_stop_f:`.
- `__fp_round_s:NNNw <sign> <digit1> <digit2> <more digits>`; can expand to `0\exp_stop_f:` or `1\exp_stop_f:`.
- `__fp_round_neg:NNN <sign> <digit1> <digit2>` can expand to `0\exp_stop_f:` or `1\exp_stop_f:`.

See implementation comments for details on the syntax.

```
\__fp_round:NNN
\__fp_round_to_nearest:NNN
  \__fp_round_to_nearest_ninf:NNN
  \__fp_round_to_nearest_zero:NNN
  \__fp_round_to_nearest_pinf:NNN
\__fp_round_to_ninf:NNN
\__fp_round_to_zero:NNN
\__fp_round_to_pinf:NNN
```

```
\__fp_round:NNN <final sign> <digit1> <digit2>
```

If rounding the number $\langle final\ sign \rangle \langle digit_1 \rangle \langle digit_2 \rangle$ to an integer rounds it towards zero (truncates it), this function expands to `0\exp_stop_f:`, and otherwise to `1\exp_stop_f:`. Typically used within the scope of an `__fp_int_eval:w`, to add 1 if needed, and thereby round correctly. The result depends on the rounding mode.

It is very important that $\langle final\ sign \rangle$ be the final sign of the result. Otherwise, the result would be incorrect in the case of rounding towards $-\infty$ or towards $+\infty$. Also recall that $\langle final\ sign \rangle$ is 0 for positive, and 2 for negative.

By default, the functions below return `0\exp_stop_f:`, but this is superseded by `__fp_round_return_one:`, which instead returns `1\exp_stop_f:`, expanding everything and removing `0\exp_stop_f:` in the process. In the case of rounding towards $\pm\infty$ or towards 0, this is not really useful, but it prepares us for the “round to nearest, ties to even” mode.

The “round to nearest” mode is the default. If the $\langle digit_2 \rangle$ is larger than 5, then round up. If it is less than 5, round down. If it is exactly 5, then round such that $\langle digit_1 \rangle$ plus the result is even. In other words, round up if $\langle digit_1 \rangle$ is odd.

The “round to nearest” mode has three variants, which differ in how ties are rounded: down towards $-\infty$, truncated towards 0, or up towards $+\infty$.

```

17156 \cs_new:Npn \__fp_round_return_one:
17157 { \exp_after:wN 1 \exp_after:wN \exp_stop_f: \exp:w }
17158 \cs_new:Npn \__fp_round_to_ninf:NNN #1 #2 #3
17159 {
17160   \if_meaning:w 2 #1
17161   \if_int_compare:w #3 > 0 \exp_stop_f:
17162     \__fp_round_return_one:
17163   \fi:
17164   \fi:
17165   0 \exp_stop_f:
17166 }
17167 \cs_new:Npn \__fp_round_to_zero:NNN #1 #2 #3 { 0 \exp_stop_f: }
17168 \cs_new:Npn \__fp_round_to_pinf:NNN #1 #2 #3
17169 {
17170   \if_meaning:w 0 #1
17171   \if_int_compare:w #3 > 0 \exp_stop_f:
17172     \__fp_round_return_one:
17173   \fi:
17174   \fi:
17175   0 \exp_stop_f:
17176 }
17177 \cs_new:Npn \__fp_round_to_nearest:NNN #1 #2 #3
17178 {
17179   \if_int_compare:w #3 > \c__fp_five_int
17180     \__fp_round_return_one:
17181   \else:
17182     \if_meaning:w 5 #3
17183       \if_int_odd:w #2 \exp_stop_f:
17184       \__fp_round_return_one:
17185     \fi:
17186   \fi:
17187   \fi:
17188   0 \exp_stop_f:
17189 }
17190 \cs_new:Npn \__fp_round_to_nearest_ninf:NNN #1 #2 #3
17191 {
17192   \if_int_compare:w #3 > \c__fp_five_int
17193     \__fp_round_return_one:
17194   \else:
17195     \if_meaning:w 5 #3
17196       \if_meaning:w 2 #1
17197       \__fp_round_return_one:
17198     \fi:
17199   \fi:
17200   \fi:
17201   0 \exp_stop_f:
17202 }
17203 \cs_new:Npn \__fp_round_to_nearest_zero:NNN #1 #2 #3
17204 {
17205   \if_int_compare:w #3 > \c__fp_five_int
17206     \__fp_round_return_one:
17207   \fi:

```



```

17208     0 \exp_stop_f:
17209   }
17210 \cs_new:Npn \__fp_round_to_nearest_pinf:NNN #1 #2 #3
17211 {
17212   \if_int_compare:w #3 > \c__fp_five_int
17213     \__fp_round_return_one:
17214   \else:
17215     \if_meaning:w 5 #3
17216     \if_meaning:w 0 #1
17217       \__fp_round_return_one:
17218     \fi:
17219   \fi:
17220 \fi:
17221   0 \exp_stop_f:
17222 }
17223 \cs_new_eq:NN \__fp_round:NNN \__fp_round_to_nearest:NNN

```

(End definition for __fp_round:NNN and others.)

__fp_round_s:NNNw

__fp_round_s:NNNw <final sign> <digit> <more digits> ;

Similar to __fp_round:NNN, but with an extra semicolon, this function expands to 0\exp_stop_f:; if rounding <final sign><digit>.<more digits> to an integer truncates, and to 1\exp_stop_f:; otherwise. The <more digits> part must be a digit, followed by something that does not overflow a \int_use:N __fp_int_eval:w construction. The only relevant information about this piece is whether it is zero or not.

```

17224 \cs_new:Npn \__fp_round_s:NNNw #1 #2 #3 #4;
17225 {
17226   \exp_after:wN \__fp_round:NNN
17227   \exp_after:wN #1
17228   \exp_after:wN #2
17229   \int_value:w \__fp_int_eval:w
17230   \if_int_odd:w 0 \if_meaning:w 0 #3 1 \fi:
17231   \if_meaning:w 5 #3 1 \fi:
17232   \exp_stop_f:
17233   \if_int_compare:w \__fp_int_eval:w #4 > 0 \exp_stop_f:
17234   1 +
17235   \fi:
17236   \fi:
17237   #3
17238   ;
17239 }

```

(End definition for __fp_round_s:NNNw.)

__fp_round_digit:Nw

\int_value:w __fp_round_digit:Nw <digit> <intexpr> ;

This function should always be called within an \int_value:w or __fp_int_eval:w expansion; it may add an extra __fp_int_eval:w, which means that the integer or integer expression should not be ended with a synonym of \relax, but with a semi-colon for instance.

```

17240 \cs_new:Npn \__fp_round_digit:Nw #1 #2;
17241 {
17242   \if_int_odd:w \if_meaning:w 0 #1 1 \else:
17243   \if_meaning:w 5 #1 1 \else:
17244   0 \fi: \fi: \exp_stop_f:

```

```

17245     \if_int_compare:w \__fp_int_eval:w #2 > 0 \exp_stop_f:
17246         \__fp_int_eval:w 1 +
17247     \fi:
17248 \fi:
17249 #1
17250 }

```

(End definition for __fp_round_digit:Nw.)

```

\__fp_round_neg:NNN
\__fp_round_to_nearest_neg:NNN
\__fp_round_to_nearest_ninf_neg:NNN
\__fp_round_to_nearest_zero_neg:NNN
\__fp_round_to_nearest_pinf_neg:NNN
\__fp_round_to_ninf_neg:NNN
\__fp_round_to_zero_neg:NNN
\__fp_round_to_pinf_neg:NNN

```

__fp_round_neg:NNN $\langle final\ sign \rangle \langle digit_1 \rangle \langle digit_2 \rangle$
This expands to 0\exp_stop_f: or 1\exp_stop_f: after doing the following test. Starting from a number of the form $\langle final\ sign \rangle 0.\langle 15\ digits \rangle \langle digit_1 \rangle$ with exactly 15 (non-all-zero) digits before $\langle digit_1 \rangle$, subtract from it $\langle final\ sign \rangle 0.0\dots 0 \langle digit_2 \rangle$, where there are 16 zeros. If in the current rounding mode the result should be rounded down, then this function returns 1\exp_stop_f:. Otherwise, *i.e.*, if the result is rounded back to the first operand, then this function returns 0\exp_stop_f:.

It turns out that this negative “round to nearest” is identical to the positive one. And this is the default mode.

```

17251 \cs_new_eq:NN \__fp_round_to_ninf_neg:NNN \__fp_round_to_pinf:NNN
17252 \cs_new:Npn \__fp_round_to_zero_neg:NNN #1 #2 #3
17253 {
17254     \if_int_compare:w #3 > 0 \exp_stop_f:
17255         \__fp_round_return_one:
17256     \fi:
17257     0 \exp_stop_f:
17258 }
17259 \cs_new_eq:NN \__fp_round_to_pinf_neg:NNN \__fp_round_to_ninf:NNN
17260 \cs_new_eq:NN \__fp_round_to_nearest_neg:NNN \__fp_round_to_nearest:NNN
17261 \cs_new_eq:NN \__fp_round_to_nearest_ninf_neg:NNN
17262     \__fp_round_to_nearest_pinf:NNN
17263 \cs_new:Npn \__fp_round_to_nearest_zero_neg:NNN #1 #2 #3
17264 {
17265     \if_int_compare:w #3 < \c__fp_five_int \else:
17266         \__fp_round_return_one:
17267     \fi:
17268     0 \exp_stop_f:
17269 }
17270 \cs_new_eq:NN \__fp_round_to_nearest_pinf_neg:NNN
17271     \__fp_round_to_nearest_ninf:NNN
17272 \cs_new_eq:NN \__fp_round_neg:NNN \__fp_round_to_nearest_neg:NNN

```

(End definition for __fp_round_neg:NNN and others.)

27.2 The round function

```

\__fp_round_o:Nw
\__fp_round_aux_o:Nw

```

First check that all arguments are floating point numbers. The `trunc`, `ceil` and `floor` functions expect one or two arguments (the second is 0 by default), and the `round` function also accepts a third argument (`nan` by default), which changes #1 from `__fp_round_to_nearest:NNN` to one of its analogues.

```

17273 \cs_new:Npn \__fp_round_o:Nw #1
17274 {
17275     \__fp_parse_function_all_fp_o:fnw
17276     { \__fp_round_name_from_cs:N #1 }

```

```

17277     { \_fp_round_aux_o:Nw #1 }
17278   }
17279 \cs_new:Npn \_fp_round_aux_o:Nw #1#2 @
17280 {
17281   \if_case:w
17282     \_fp_int_eval:w \_fp_array_count:n {#2} \_fp_int_eval_end:
17283     \_fp_round_no_arg_o:Nw #1 \exp:w
17284   \or: \_fp_round:Nwn #1 #2 {0} \exp:w
17285   \or: \_fp_round:Nww #1 #2 \exp:w
17286   \else: \_fp_round:Nwww #1 #2 @ \exp:w
17287   \fi:
17288   \exp_after:wN \exp_end:
17289 }

```

(End definition for _fp_round_o:Nw and _fp_round_aux_o:Nw.)

_fp_round_no_arg_o:Nw

```

17290 \cs_new:Npn \_fp_round_no_arg_o:Nw #1
17291 {
17292   \cs_if_eq:NNTF #1 \_fp_round_to_nearest:NNN
17293   { \_fp_error:nnnn { fp-num-args } { round () } { 1 } { 3 } }
17294   {
17295     \_fp_error:nffn { fp-num-args }
17296     { \_fp_round_name_from_cs:N #1 () } { 1 } { 2 }
17297   }
17298   \exp_after:wN \c_nan_fp
17299 }

```

(End definition for _fp_round_no_arg_o:Nw.)

_fp_round:Nwww Having three arguments is only allowed for round, not trunc, ceil, floor, so check for that case. If all is well, construct one of _fp_round_to_nearest:NNN, _fp_round_to_nearest_zero:NNN, _fp_round_to_nearest_ninf:NNN, _fp_round_to_nearest_pinf:NNN and act accordingly.

```

17300 \cs_new:Npn \_fp_round:Nwww #1#2 ; #3 ; \s_fp \_fp_chk:w #4#5#6 ; #7 @
17301 {
17302   \cs_if_eq:NNTF #1 \_fp_round_to_nearest:NNN
17303   {
17304     \tl_if_empty:nTF {#7}
17305     {
17306       \exp_args:Nc \_fp_round:Nww
17307       {
17308         \_fp_round_to_nearest
17309         \if_meaning:w 0 #4 _zero \else:
17310         \if_case:w #5 \exp_stop_f: _pinf \or: \else: _ninf \fi: \fi:
17311         :NNN
17312       }
17313       #2 ; #3 ;
17314     }
17315     {
17316       \_fp_error:nnnn { fp-num-args } { round () } { 1 } { 3 }
17317       \exp_after:wN \c_nan_fp
17318     }
17319   }

```

```

17320     {
17321         \__fp_error:nffn { fp-num-args }
17322         { \__fp_round_name_from_cs:N #1 () } { 1 } { 2 }
17323         \exp_after:wN \c_nan_fp
17324     }
17325 }

```

(End definition for __fp_round:Nwww.)

__fp_round_name_from_cs:N

```

17326 \cs_new:Npn \__fp_round_name_from_cs:N #1
17327 {
17328     \cs_if_eq:NNTF #1 \__fp_round_to_zero:NNN { trunc }
17329     {
17330         \cs_if_eq:NNTF #1 \__fp_round_to_ninf:NNN { floor }
17331         {
17332             \cs_if_eq:NNTF #1 \__fp_round_to_pinf:NNN { ceil }
17333             { round }
17334         }
17335     }
17336 }

```

(End definition for __fp_round_name_from_cs:N.)

__fp_round:Nww

__fp_round:Nwn

If the number of digits to round to is an integer or infinity all is good; if it is `nan` then just produce a `nan`; otherwise invalid as we have something like `round(1,3.14)` where the number of digits is not an integer.

__fp_round_normal:NwNNnw

__fp_round_normal:NnnwNNnn

__fp_round_pack:Nw

__fp_round_normal:NNwNnn

__fp_round_normal_end:wwNnn

__fp_round_special:NwwNnn

__fp_round_special_aux:Nw

```

17337 \cs_new:Npn \__fp_round:Nww #1#2 ; #3 ;
17338 {
17339     \__fp_small_int:wTF #3; { \__fp_round:Nwn #1#2; }
17340     {
17341         \if:w 3 \__fp_kind:w #3 ;
17342         \exp_after:wN \use_i:nn
17343         \else:
17344             \exp_after:wN \use_ii:nn
17345         \fi:
17346         { \exp_after:wN \c_nan_fp }
17347         {
17348             \__fp_invalid_operation_tl_o:ff
17349             { \__fp_round_name_from_cs:N #1 }
17350             { \__fp_array_to_clist:n { #2; #3; } }
17351         }
17352     }
17353 }
17354 \cs_new:Npn \__fp_round:Nwn #1 \s__fp \__fp_chk:w #2#3#4; #5
17355 {
17356     \if_meaning:w 1 #2
17357         \exp_after:wN \__fp_round_normal:NwNNnw
17358         \exp_after:wN #1
17359         \int_value:w #5
17360     \else:
17361         \exp_after:wN \__fp_exp_after_o:w
17362     \fi:
17363     \s__fp \__fp_chk:w #2#3#4;

```

```

17364 }
17365 \cs_new:Npn \__fp_round_normal:NwNnnw #1#2 \s__fp \__fp_chk:w 1#3#4#5;
17366 {
17367   \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 - #2 }
17368   \__fp_round_normal:NnnwNnnn #5 #1 #3 {#4} {#2}
17369 }
17370 \cs_new:Npn \__fp_round_normal:NnnwNnnn #1#2#3#4; #5#6
17371 {
17372   \exp_after:wN \__fp_round_normal:NwNnnn
17373   \int_value:w \__fp_int_eval:w
17374   \if_int_compare:w #2 > 0 \exp_stop_f:
17375     1 \int_value:w #2
17376   \exp_after:wN \__fp_round_pack:Nw
17377   \int_value:w \__fp_int_eval:w 1#3 +
17378   \else:
17379     \if_int_compare:w #3 > 0 \exp_stop_f:
17380       1 \int_value:w #3 +
17381     \fi:
17382   \fi:
17383   \exp_after:wN #5
17384   \exp_after:wN #6
17385   \use_none:nnnnnnn #3
17386   #1
17387   \__fp_int_eval_end:
17388   0000 0000 0000 0000 ; #6
17389 }
17390 \cs_new:Npn \__fp_round_pack:Nw #1
17391 { \if_meaning:w 2 #1 + 1 \fi: \__fp_int_eval_end: }
17392 \cs_new:Npn \__fp_round_normal:NwNnnn #1 #2
17393 {
17394   \if_meaning:w 0 #2
17395     \exp_after:wN \__fp_round_special:NwNnnn
17396     \exp_after:wN #1
17397   \fi:
17398   \__fp_pack_twice_four:wNNNNNNNN
17399   \__fp_pack_twice_four:wNNNNNNNN
17400   \__fp_round_normal_end:wwNnn
17401   ; #2
17402 }
17403 \cs_new:Npn \__fp_round_normal_end:wwNnn #1;#2;#3#4#5
17404 {
17405   \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w
17406   \__fp_sanitizew:Nw #3 #4 ; #1 ;
17407 }
17408 \cs_new:Npn \__fp_round_special:NwNnnn #1#2;#3;#4#5#6
17409 {
17410   \if_meaning:w 0 #1
17411     \__fp_case_return:nw
17412     { \exp_after:wN \__fp_zero_fp:N \exp_after:wN #4 }
17413   \else:
17414     \exp_after:wN \__fp_round_special_aux:Nw
17415     \exp_after:wN #4
17416     \int_value:w \__fp_int_eval:w 1
17417     \if_meaning:w 1 #1 -#6 \else: +#5 \fi:

```

```

17418     \fi:
17419     ;
17420   }
17421   \cs_new:Npn \__fp_round_special_aux:Nw #1#2;
17422   {
17423     \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w
17424     \__fp_sanitizew:Nw #1#2; {1000}{0000}{0000}{0000};
17425   }

```

(End definition for `__fp_round:Nww` and others.)

```

17426 \</initex | package>

```

28 l3fp-parse implementation

```

17427 (*initex | package)

```

```

17428 <@@=fp>

```

28.1 Work plan

The task at hand is non-trivial, and some previous failed attempts show that the code leads to unreadable logs, so we had better get it (almost) right the first time. Let us first describe our goal, then discuss the design precisely before writing any code.

In this file at least, a *floating point object* is a floating point number or tuple. This can be extended to anything that starts with `\s__fp` or `\s__fp_⟨type⟩` and ends with `;` with some internal structure that depends on the *⟨type⟩*.

```

\__fp_parse:n     \__fp_parse:n {⟨fpexpr⟩}

```

Evaluates the *floating point expression* and leaves the result in the input stream as a floating point object. This function forms the basis of almost all public `l3fp` functions. During evaluation, each token is fully `f`-expanded.

`__fp_parse_o:n` does the same but expands once after its result.

T_EXhackers note: Registers (integers, toks, etc.) are automatically unpacked, without requiring a function such as `\int_use:N`. Invalid tokens remaining after `f`-expansion lead to unrecoverable low-level T_EX errors.

(End definition for `__fp_parse:n`.)

<pre> __fp_prec_func_int __fp_prec_hatii_int __fp_prec_hat_int __fp_prec_not_int __fp_prec_juxt_int __fp_prec_times_int __fp_prec_plus_int __fp_prec_comp_int __fp_prec_and_int __fp_prec_or_int __fp_prec_quest_int __fp_prec_colon_int __fp_prec_comma_int __fp_prec_tuple_int __fp_prec_end_int </pre>	<p>Floating point expressions are composed of numbers, given in various forms, infix operators, such as <code>+</code>, <code>**</code>, or <code>,</code> (which joins two numbers into a list), and prefix operators, such as the unary <code>-</code>, functions, or opening parentheses. Here is a list of precedences which control the order of evaluation (some distinctions are irrelevant for the order of evaluation, but serve as signals), from the tightest binding to the loosest binding.</p> <ul style="list-style-type: none"> 16 Function calls. 13/14 Binary <code>**</code> and <code>^</code> (right to left). 12 Unary <code>+</code>, <code>-</code>, <code>!</code> (right to left). 11 Juxtaposition (implicit <code>*</code>) with no parenthesis. 10 Binary <code>*</code> and <code>/</code>.
--	--

- 9 Binary + and -.
- 7 Comparisons.
- 6 Logical and, denoted by &&.
- 5 Logical or, denoted by ||.
- 4 Ternary operator ?:, piece ?.
- 3 Ternary operator ?:, piece :.
- 2 Commas.
- 1 Place where a comma is allowed and generates a tuple.
- 0 Start and end of the expression.

```

17429 \int_const:Nn \c__fp_prec_func_int { 16 }
17430 \int_const:Nn \c__fp_prec_hatii_int { 14 }
17431 \int_const:Nn \c__fp_prec_hat_int { 13 }
17432 \int_const:Nn \c__fp_prec_not_int { 12 }
17433 \int_const:Nn \c__fp_prec_juxt_int { 11 }
17434 \int_const:Nn \c__fp_prec_times_int { 10 }
17435 \int_const:Nn \c__fp_prec_plus_int { 9 }
17436 \int_const:Nn \c__fp_prec_comp_int { 7 }
17437 \int_const:Nn \c__fp_prec_and_int { 6 }
17438 \int_const:Nn \c__fp_prec_or_int { 5 }
17439 \int_const:Nn \c__fp_prec_quest_int { 4 }
17440 \int_const:Nn \c__fp_prec_colon_int { 3 }
17441 \int_const:Nn \c__fp_prec_comma_int { 2 }
17442 \int_const:Nn \c__fp_prec_tuple_int { 1 }
17443 \int_const:Nn \c__fp_prec_end_int { 0 }

```

(End definition for \c__fp_prec_func_int and others.)

28.1.1 Storing results

The main question in parsing expressions expandably is to decide where to put the intermediate results computed for various subexpressions.

One option is to store the values at the start of the expression, and carry them together as the first argument of each macro. However, we want to **f**-expand tokens one by one in the expression (as `\int_eval:n` does), and with this approach, expanding the next unread token forces us to jump with `\exp_after:wN` over every value computed earlier in the expression. With this approach, the run-time grows at least quadratically in the length of the expression, if not as its cube (inserting the `\exp_after:wN` is tricky and slow).

A second option is to place those values at the end of the expression. Then expanding the next unread token is straightforward, but this still hits a performance issue: for long expressions we would be reaching all the way to the end of the expression at every step of the calculation. The run-time is again quadratic.

A variation of the above attempts to place the intermediate results which appear when computing a parenthesized expression near the closing parenthesis. This still lets us expand tokens as we go, and avoids performance problems as long as there are enough parentheses. However, it would be better to avoid requiring the closing parenthesis to be

present as soon as the corresponding opening parenthesis is read: the closing parenthesis may still be hidden in a macro yet to be expanded.

Hence, we need to go for some fine expansion control: the result is stored *before* the start!

Let us illustrate this idea in a simple model: adding positive integers which may be resulting from the expansion of macros, or may be values of registers. Assume that one number, say, 12345, has already been found, and that we want to parse the next number. The current status of the code may look as follows.

```
\exp_after:wN \add:ww \int_value:w 12345 \exp_after:wN ;
\exp:w \operand:w <stuff>
```

One step of expansion expands `\exp_after:wN`, which triggers the primitive `\int_value:w`, which reads the five digits we have already found, 12345. This integer is unfinished, causing the second `\exp_after:wN` to expand, and to trigger the construction `\exp:w`, which expands `\operand:w`, defined to read what follows and make a number out of it, then leave `\exp_end:`, the number, and a semicolon in the input stream. Once `\operand:w` is done expanding, we obtain essentially

```
\exp_after:wN \add:ww \int_value:w 12345 ;
\exp:w \exp_end: 333444 ;
```

where in fact `\exp_after:wN` has already been expanded, `\int_value:w` has already seen 12345, and `\exp:w` is still looking for a number. It finds `\exp_end:`, hence expands to nothing. Now, `\int_value:w` sees the `;`, which cannot be part of a number. The expansion stops, and we are left with

```
\add:ww 12345 ; 333444 ;
```

which can safely perform the addition by grabbing two arguments delimited by `;`.

If we were to continue parsing the expression, then the following number should also be cleaned up before the next use of a binary operation such as `\add:ww`. Just like `\int_value:w 12345 \exp_after:wN ;` expanded what follows once, we need `\add:ww` to do the calculation, and in the process to expand the following once. This is also true in our real application: all the functions of the form `__fp_..._o:ww` expand what follows once. This comes at the cost of leaving tokens in the input stack, and we need to be careful not to waste this memory. All of our discussion above is nice but simplistic, as operations should not simply be performed in the order they appear.

28.1.2 Precedence and infix operators

The various operators we will encounter have different precedences, which influence the order of calculations: $1 + 2 \times 3 = 1 + (2 \times 3)$ because \times has a higher precedence than $+$. The true analog of our macro `\operand:w` must thus take care of that. When looking for an operand, it needs to perform calculations until reaching an operator which has lower precedence than the one which called `\operand:w`. This means that `\operand:w` must know what the previous binary operator is, or rather, its precedence: we thus rename it `\operand:Nw`. Let us describe as an example how we plan to do the calculation $41 - 2^3 * 4 + 5$. More precisely we describe how to perform the first operation in this expression. Here, we abuse notations: the first argument of `\operand:Nw` should be an integer constant (`\c__fp_prec_plus_int, ...`) equal to the precedence of the given operator, not directly the operator itself.

- Clean up 41 and find $-$. We call `\operand:Nw -` to find the second operand.
- Clean up 2 and find \wedge .
- Compare the precedences of $-$ and \wedge . Since the latter is higher, we need to compute the exponentiation. For this, find the second operand with a nested call to `\operand:Nw \wedge`.
- Clean up 3 and find $*$.
- Compare the precedences of \wedge and $*$. Since the former is higher, `\operand:Nw \wedge` has found the second operand of the exponentiation, which is computed: $2^3 = 8$.
- We now have $41-8*4+5$, and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 8?
- Compare the precedences of $-$ and $*$. Since the latter is higher, we are not done with 8. Call `\operand:Nw *` to find the second operand of the multiplication.
- Clean up 4, and find $+$.
- Compare the precedences of $*$ and $+$. Since the former is higher, `\operand:Nw *` has found the second operand of the multiplication, which is computed: $8*4 = 32$.
- We now have $41-32+5$, and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 32?
- Compare the precedences of $-$ and $+$. Since they are equal, `\operand:Nw -` has found the second operand for the subtraction, which is computed: $41 - 32 = 9$.
- We now have $9+5$.

The procedure above stops short of performing all computations, but adding a surrounding call to `\operand:Nw` with a very low precedence ensures that all computations are performed before `\operand:Nw` is done. Adding a trailing marker with the same very low precedence prevents the surrounding `\operand:Nw` from going beyond the marker.

The pattern above to find an operand for a given operator, is to find one number and the next operator, then compare precedences to know if the next computation should be done. If it should, then perform it after finding its second operand, and look at the next operator, then compare precedences to know if the next computation should be done. This continues until we find that the next computation should not be done. Then, we stop.

We are now ready to get a bit more technical and describe which of the `l3fp-parse` functions correspond to each step above.

First, `__fp_parse_operand:Nw` is the `\operand:Nw` function above, with small modifications due to expansion issues discussed later. We denote by $\langle precedence \rangle$ the argument of `__fp_parse_operand:Nw`, that is, the precedence of the binary operator whose operand we are trying to find. The basic action is to read numbers from the input stream. This is done by `__fp_parse_one:Nw`. A first approximation of this function is that it reads one $\langle number \rangle$, performing no computation, and finds the following binary $\langle operator \rangle$. Then it expands to

$$\langle number \rangle \\ __fp_parse_infix_ \langle operator \rangle : N \langle precedence \rangle$$

expanding the `infix` auxiliary before leaving the above in the input stream.

We now explain the `infix` auxiliaries. We need some flexibility in how we treat the case of equal precedences: most often, the first operation encountered should be performed, such as `1-2-3` being computed as `(1-2)-3`, but `2^3^4` should be evaluated as `2^(3^4)` instead. For this reason, and to support the equivalence between `**` and `^` more easily, each binary operator is converted to a control sequence `__fp_parse_infix_⟨operator⟩:N` when it is encountered for the first time. Instead of passing both precedences to a test function to do the comparison steps above, we pass the `⟨precedence⟩` (of the earlier operator) to the `infix` auxiliary for the following `⟨operator⟩`, to know whether to perform the computation of the `⟨operator⟩`. If it should not be performed, the `infix` auxiliary expands to

```
@ \use_none:n \__fp_parse_infix_⟨operator⟩:N
```

and otherwise it calls `__fp_parse_operand:Nw` with the precedence of the `⟨operator⟩` to find its second operand `⟨number₂⟩` and the next `⟨operator₂⟩`, and expands to

```
@ \__fp_parse_apply_binary:NwNwN
  ⟨operator⟩ ⟨number₂⟩
@ \__fp_parse_infix_⟨operator₂⟩:N
```

The `infix` function is responsible for comparing precedences, but cannot directly call the computation functions, because the first operand `⟨number⟩` is before the `infix` function in the input stream. This is why we stop the expansion here and give control to another function to close the loop.

A definition of `__fp_parse_operand:Nw ⟨precedence⟩` with some of the expansion control removed is

```
\exp_after:wN \__fp_parse_continue:NwN
\exp_after:wN ⟨precedence⟩
\exp:w \exp_end_continue_f:w
  \__fp_parse_one:Nw ⟨precedence⟩
```

This expands `__fp_parse_one:Nw ⟨precedence⟩` completely, which finds a number, wraps the next `⟨operator⟩` into an `infix` function, feeds this function the `⟨precedence⟩`, and expands it, yielding either

```
\__fp_parse_continue:NwN ⟨precedence⟩
⟨number⟩ @
\use_none:n \__fp_parse_infix_⟨operator⟩:N
```

or

```
\__fp_parse_continue:NwN ⟨precedence⟩
⟨number⟩ @
\__fp_parse_apply_binary:NwNwN
  ⟨operator⟩ ⟨number₂⟩
@ \__fp_parse_infix_⟨operator₂⟩:N
```

The definition of `__fp_parse_continue:NwN` is then very simple:

```
\cs_new:Npn \__fp_parse_continue:NwN #1#2@#3 { #3 #1 #2 @ }
```

In the first case, `#3` is `\use_none:n`, yielding

then $\langle number \rangle @__fp_parse_infix__operator : N$. In the second case, #3 is $__fp_parse_apply_binary : NwNwN$, whose role is to compute $\langle number \rangle \langle operator \rangle \langle number_2 \rangle$ and to prepare for the next comparison of precedences: first we get

then

where `_fp_operator_o:ww` computes $\langle number \rangle \langle operator \rangle \langle number_2 \rangle$ and expands after the result, thus triggers the comparison of the precedence of the $\langle operator_2 \rangle$ and the $\langle precedence \rangle$, continuing the loop.

28.1.3 Prefix operators, parentheses, and functions

Prefix operators (unary `-`, `+`, `!`) and parentheses are taken care of by the same mechanism, and functions (`sin`, `exp`, etc.) as well. Finding the argument of the unary `-`, for instance, is very similar to grabbing the second operand of a binary infix operator, with a subtle precedence explained below. Once that operand is found, the operator can be applied to it (for the unary `-`, this simply flips the sign). A left parenthesis is just a prefix operator with a very low precedence equal to that of the closing parenthesis (which is treated as an infix operator, since it normally appears just after numbers), so that all computations are performed until the closing parenthesis. The prefix operator associated to the left parenthesis does not alter its argument, but it removes the closing parenthesis (with some checks).

Prefix operators are the reason why we only summarily described the function `_fp_parse_one:Nw` earlier. This function is responsible for reading in the input stream the first possible *number* and the next infix *operator*. If what follows `_fp_parse_one:Nw` *precedence* is a prefix operator, then we must find the operand of this prefix operator through a nested call to `_fp_parse_operand:Nw` with the appropriate precedence, then apply the operator to the operand found to yield the result of `_fp_parse_one:Nw`. So far, all is simple.

The unary operators `+`, `-`, `!` complicate things a little bit: `-3**2` should be $-(3^2) = -9$, and not $(-3)^2 = 9$. This would easily be done by giving `-` a lower precedence, equal to that of the infix `+` and `-`. Unfortunately, this fails in cases such as `3**-2*4`, yielding $3^{-2 \times 4}$ instead of the correct $3^{-2} \times 4$. A second attempt would be to call `__fp_parse_operand:Nw` with the *precedence* of the previous operator, but `0>-2+3` is then parsed as `0>-(2+3)`: the addition is performed because it binds more tightly than the comparison which precedes `-`. The correct approach is for a unary `-` to perform

operations whose precedence is greater than both that of the previous operation, and that of the unary `-` itself. The unary `-` is given a precedence higher than multiplication and division. This does not lead to any surprising result, since $-(x/y) = (-x)/y$ and similarly for multiplication, and it reduces the number of nested calls to `__fp_parse_operand:Nw`.

Functions are implemented as prefix operators with very high precedence, so that their argument is the first number that can possibly be built.

Note that contrarily to the `infix` functions discussed earlier, the `prefix` functions do perform tests on the previous *precedence* to decide whether to find an argument or not, since we know that we need a number, and must never stop there.

28.1.4 Numbers and reading tokens one by one

So far, we have glossed over one important point: what is a “number”? A number is typically given in the form $\langle \textit{significand} \rangle \mathbf{e} \langle \textit{exponent} \rangle$, where the $\langle \textit{significand} \rangle$ is any non-empty string composed of decimal digits and at most one decimal separator (a period), the exponent “ $\mathbf{e} \langle \textit{exponent} \rangle$ ” is optional and is composed of an exponent mark `e` followed by a possibly empty string of signs `+` or `-` and a non-empty string of decimal digits. The $\langle \textit{significand} \rangle$ can also be an integer, dimension, skip, or muskip variable, in which case dimensions are converted from points (or mu units) to floating points, and the $\langle \textit{exponent} \rangle$ can also be an integer variable. Numbers can also be given as floating point variables, or as named constants such as `nan`, `inf` or `pi`. We may add more types in the future.

When `__fp_parse_one:Nw` is looking for a “number”, here is what happens.

- If the next token is a control sequence with the meaning of `\scan_stop:`, it can be: `\s__fp`, in which case our job is done, as what follows is an internal floating point number, or `\s__fp_expr_mark`, in which case the expression has come to an early end, as we are still looking for a number here, or something else, in which case we consider the control sequence to be a bad variable resulting from c-expansion.
- If the next token is a control sequence with a different meaning, we assume that it is a register, unpack it with `\tex_the:D`, and use its value (in `pt` for dimensions and skips, `mu` for muskips) as the $\langle \textit{significand} \rangle$ of a number: we look for an exponent.
- If the next token is a digit, we remove any leading zeros, then read a significand larger than 1 if the next character is a digit, read a significand smaller than 1 if the next character is a period, or we have found a significand equal to 0 otherwise, and look for an exponent.
- If the next token is a letter, we collect more letters until the first non-letter: the resulting word may denote a function such as `asin`, a constant such as `pi` or be unknown. In the first case, we call `__fp_parse_operand:Nw` to find the argument of the function, then apply the function, before declaring that we are done. Otherwise, we are done, either with the value of the constant, or with the value `nan` for unknown words.
- If the next token is anything else, we check whether it is a known prefix operator, in which case `__fp_parse_operand:Nw` finds its operand. If it is not known, then either a number is missing (if the token is a known infix operator) or the token is simply invalid in floating point expressions.

Once a number is found, `__fp_parse_one:Nw` also finds an infix operator. This goes as follows.

- If the next token is a control sequence, it could be the special marker `\s__fp_expr_mark`, and otherwise it is a case of juxtaposing numbers, such as `2\c_zero_int`, with an implied multiplication.
- If the next token is a letter, it is also a case of juxtaposition, as letters cannot be proper infix operators.
- Otherwise (including in the case of digits), if the token is a known infix operator, the appropriate `__fp_infix_⟨operator⟩:N` function is built, and if it does not exist, we complain. In particular, the juxtaposition `\c_zero_int 2` is disallowed.

In the above, we need to test whether a character token `#1` is a digit:

```
\if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
  is a digit
\else:
  not a digit
\fi:
```

To exclude 0, replace 9 by 10. The use of `\token_to_str:N` ensures that a digit with any catcode is detected. To test if a character token is a letter, we need to work with its character code, testing if ‘`#1`’ lies in [65, 90] (uppercase letters) or [97, 112] (lowercase letters)

```
\if_int_compare:w \__fp_int_eval:w
  ( ‘#1 \if_int_compare:w ‘#1 > ‘Z - 32 \fi: ) / 26 = 3 \exp_stop_f:
  is a letter
\else:
  not a letter
\fi:
```

At all steps, we try to accept all category codes: when `#1` is kept to be used later, it is almost always converted to category code other through `\token_to_str:N`. More precisely, catcodes {3, 6, 7, 8, 11, 12} should work without trouble, but not {1, 2, 4, 10, 13}, and of course {0, 5, 9} cannot become tokens.

Floating point expressions should behave as much as possible like ε -TeX-based integer expressions and dimension expressions. In particular, `f`-expansion should be performed as the expression is read, token by token, forcing the expansion of protected macros, and ignoring spaces. One advantage of expanding at every step is that restricted expandable functions can then be used in floating point expressions just as they can be in other kinds of expressions. Problematically, spaces stop `f`-expansion: for instance, the macro `\X` below would not be expanded if we simply performed `f`-expansion.

```
\DeclareDocumentCommand {\test} {m} { \fp_eval:n {#1} }
\ExplSyntaxOff
\test { 1 + \X }
```

Of course, spaces typically do not appear in a code setting, but may very easily come in document-level input, from which some expressions may come. To avoid this problem, at every step, we do essentially what `\use:f` would do: take an argument, put it back in the input stream, then `f`-expand it. This is not a complete solution, since a macro’s expansion could contain leading spaces which would stop the `f`-expansion before further macro calls are performed. However, in practice it should be enough: in particular, floating point numbers are correctly expanded to the underlying `\s__fp ...` structure. The `f`-expansion is performed by `__fp_parse_expand:w`.

28.2 Main auxiliary functions

`_fp_parse_operand:Nw` `\exp:w _fp_parse_operand:Nw <precedence> _fp_parse_expand:w`
 Reads the "...", performing every computation with a precedence higher than `<precedence>`, then expands to

`<result> @ _fp_parse_infix_<operation>:N ...`

where the `<operation>` is the first operation with a lower precedence, possibly `end`, and the "..." start just after the `<operation>`.

(End definition for `_fp_parse_operand:Nw`.)

`_fp_parse_infix_+:N` `_fp_parse_infix_+:N <precedence> ...`
 If `+` has a precedence higher than the `<precedence>`, cleans up a second `<operand>` and finds the `<operation2 which follows, and expands to`

`@ _fp_parse_apply_binary:NwNwN + <operand> @ _fp_parse_infix_<operation2
...`

Otherwise expands to

`@ \use_none:n _fp_parse_infix_+:N ...`

A similar function exists for each infix operator.

(End definition for `_fp_parse_infix_+:N`.)

`_fp_parse_one:Nw` `_fp_parse_one:Nw <precedence> ...`
 Cleans up one or two operands depending on how the precedence of the next operation compares to the `<precedence>`. If the following `<operation>` has a precedence higher than `<precedence>`, expands to

`<operand1> @ _fp_parse_apply_binary:NwNwN <operation> <operand2> @`
`_fp_parse_infix_<operation2`

and otherwise expands to

`<operand> @ \use_none:n _fp_parse_infix_<operation>:N ...`

(End definition for `_fp_parse_one:Nw`.)

28.3 Helpers

`_fp_parse_expand:w` `\exp:w _fp_parse_expand:w <tokens>`
 This function must always come within a `\exp:w` expansion. The `<tokens>` should be the part of the expression that we have not yet read. This requires in particular closing all conditionals properly before expanding.

17444 `\cs_new:Npn _fp_parse_expand:w #1 { \exp_end_continue_f:w #1 }`

(End definition for `_fp_parse_expand:w`.)

`_fp_parse_return_semicolon:w` This very odd function swaps its position with the following `\fi:` and removes `_fp_parse_expand:w` normally responsible for expansion. That turns out to be useful.

17445 `\cs_new:Npn _fp_parse_return_semicolon:w`
17446 `#1 \fi: _fp_parse_expand:w { \fi: ; #1 }`

```

\__fp_parse_digits_vii:N
\__fp_parse_digits_vi:N
\__fp_parse_digits_v:N
\__fp_parse_digits_iv:N
\__fp_parse_digits_iii:N
\__fp_parse_digits_ii:N
\__fp_parse_digits_i:N
\__fp_parse_digits_:N

```

 $\langle \text{digits} \rangle ; \langle \text{filling } 0 \rangle ; \langle \text{length} \rangle$

```

17447 \cs_set_protected:Npn \__fp_tmp:w #1 #2 #3
17448 {
17449   \cs_new:cpn { __fp_parse_digits_ #1 :N } ##1
17450   {
17451     \if_int_compare:w 9 < 1 \token_to_str:N ##1 \exp_stop_f:
17452     \token_to_str:N ##1 \exp_after:wN #2 \exp:w
17453     \else:
17454       \__fp_parse_return_semicolon:w #3 ##1
17455     \fi:
17456     \__fp_parse_expand:w
17457   }
17458 }
17459
17459 \__fp_tmp:w {vii}   \__fp_parse_digits_vi:N   { 0000000 ; 7 }
17460 \__fp_tmp:w {vi}    \__fp_parse_digits_v:N    { 000000 ; 6 }
17461 \__fp_tmp:w {v}     \__fp_parse_digits_iv:N   { 00000 ; 5 }
17462 \__fp_tmp:w {iv}    \__fp_parse_digits_iii:N  { 0000 ; 4 }
17463 \__fp_tmp:w {iii}   \__fp_parse_digits_ii:N   { 000 ; 3 }
17464 \__fp_tmp:w {ii}    \__fp_parse_digits_i:N    { 00 ; 2 }
17465 \__fp_tmp:w {i}     \__fp_parse_digits_N      { 0 ; 1 }
17466 \cs_new:Npn \__fp_parse_digits_N:N { ; ; 0 }

```

28.4 Parsing one number

__fp_parse_one:Nw

```
17467 \cs_new:Npn \__fp_parse_one:Nw #1 #2
17468 {
17469   \if_catcode:w \scan_stop: \exp_not:N #2
17470   \exp_after:wN \if_meaning:w \exp_not:N #2 #2 \else:
17471   \exp_after:wN \reverse if:N
```

```

17472 \fi:
17473 \if_meaning:w \scan_stop: #2
17474 \exp_after:wN \exp_after:wN
17475 \exp_after:wN \_fp_parse_one_fp:NN
17476 \else:
17477 \exp_after:wN \exp_after:wN
17478 \exp_after:wN \_fp_parse_one_register:NN
17479 \fi:
17480 \else:
17481 \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
17482 \exp_after:wN \exp_after:wN
17483 \exp_after:wN \_fp_parse_one_digit:NN
17484 \else:
17485 \exp_after:wN \exp_after:wN
17486 \exp_after:wN \_fp_parse_one_other:NN
17487 \fi:
17488 \fi:
17489 #1 #2
17490 }

```

(End definition for `_fp_parse_one:Nw`.)

`_fp_parse_one_fp:NN` This function receives a $\langle precedence \rangle$ and a control sequence equal to `\scan_stop:` in meaning. There are three cases.

`_fp_exp_after_expr_mark_f:nw`
`_fp_exp_after_?_f:nw`

- `\s__fp` starts a floating point number, and we call `_fp_exp_after_f:nw`, which f-expands after the floating point.
- `\s__fp_expr_mark` is a premature end, we call `_fp_exp_after_expr_mark_f:nw`, which triggers an fp-early-end error.
- For a control sequence not containing `\s__fp`, we call `_fp_exp_after_?_f:nw`, causing a bad-variable error.

This scheme is extensible: additional types can be added by starting the variables with a scan mark of the form `\s__fp_⟨type⟩` and defining `_fp_exp_after_⟨type⟩_f:nw`. In all cases, we make sure that the second argument of `_fp_parse_infix:NN` is correctly expanded. A special case only enabled in L^AT_EX 2_ε is that if `\protect` is encountered then the error message mentions the control sequence which follows it rather than `\protect` itself. The test for L^AT_EX 2_ε uses `\@unexpandable@protect` rather than `\protect` because `\protect` is often `\scan_stop:` hence “does not exist”.

```

17491 \cs_new:Npn \_fp_parse_one_fp:NN #1
17492 {
17493   \_fp_exp_after_any_f:nw
17494   {
17495     \exp_after:wN \_fp_parse_infix:NN
17496     \exp_after:wN #1 \exp:w \_fp_parse_expand:w
17497   }
17498 }
17499 \cs_new:Npn \_fp_exp_after_expr_mark_f:nw #1
17500 {
17501   \int_case:nnF { \exp_after:wN \use_i:nnn \use_none:nnn #1 }
17502   {
17503     \c__fp_prec_comma_int { }

```



```

17504     \c__fp_prec_tuple_int { }
17505     \c__fp_prec_end_int
17506     {
17507         \exp_after:wN \c__fp_empty_tuple_fp
17508         \exp:w \exp_end_continue_f:w
17509     }
17510 }
17511 {
17512     \_kernel_msg_expandable_error:nn { kernel } { fp-early-end }
17513     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
17514 }
17515 #1
17516 }
17517 \cs_new:cpn { __fp_exp_after_?_f:nw } #1#2
17518 {
17519     \_kernel_msg_expandable_error:nnn { kernel } { bad-variable }
17520     {#2}
17521     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w #1
17522 }
17523 \*package)
17524 \cs_set_protected:Npn \__fp_tmp:w #1
17525 {
17526     \cs_if_exist:NT #1
17527     {
17528         \cs_gset:cpn { __fp_exp_after_?_f:nw } ##1##2
17529         {
17530             \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w ##1
17531             \str_if_eq:nnTF {##2} { \protect }
17532             {
17533                 \cs_if_eq:NNTF ##2 #1 { \use_i:nn } { \use:n }
17534                 {
17535                     \_kernel_msg_expandable_error:nnn { kernel }
17536                     { fp-robust-cmd }
17537                 }
17538             }
17539             {
17540                 \_kernel_msg_expandable_error:nnn { kernel }
17541                 { bad-variable } {##2}
17542             }
17543         }
17544     }
17545 }
17546 \exp_args:Nc \__fp_tmp:w { @unexpandable@protect }
17547 \</package>

```

(End definition for __fp_parse_one_fp:NN, __fp_exp_after_expr_mark_f:nw, and __fp_exp_after_?_f:nw.)

__fp_parse_one_register:NN This is called whenever #2 is a control sequence other than \scan_stop: in meaning. We
 __fp_parse_one_register_aux:Nw special-case \wd, \ht, \dp (see later) and otherwise assume that it is a register, but care-
 __fp_parse_one_register_auxii:wwwNw fully unpack it with \tex_the:D within braces. First, we find the exponent following #2.
 __fp_parse_one_register_int:www Then we unpack #2 with \tex_the:D, and the auxii auxiliary distinguishes integer reg-
 __fp_parse_one_register_mu:www isters from dimensions/skips from muskips, according to the presence of a period and/or
 __fp_parse_one_register_dim:www of pt. For integers, simply convert $\langle value \rangle e \langle exponent \rangle$ to a floating point number with

`__fp_parse:n` (this is somewhat wasteful). For other registers, the decimal rounding provided by `TEX` does not accurately represent the binary value that it manipulates, so we extract this binary value as a number of scaled points with `\int_value:w \dim_to_decimal_in_sp:n { <decimal value> pt }`, and use an auxiliary of `\dim_to_fp:n`, which performs the multiplication by 2^{-16} , correctly rounded.

```

17548 \cs_new:Npn \__fp_parse_one_register:NN #1#2
17549 {
17550   \exp_after:wN \__fp_parse_infix_after_operand:NwN
17551   \exp_after:wN #1
17552   \exp:w \exp_end_continue_f:w
17553   \__fp_parse_one_register_special:N #2
17554   \exp_after:wN \__fp_parse_one_register_aux:Nw
17555   \exp_after:wN #2
17556   \int_value:w
17557   \exp_after:wN \__fp_parse_exponent:N
17558   \exp:w \__fp_parse_expand:w
17559 }
17560 \cs_new:Npx \__fp_parse_one_register_aux:Nw #1
17561 {
17562   \exp_not:n
17563   {
17564     \exp_after:wN \use:nn
17565     \exp_after:wN \__fp_parse_one_register_auxii:wwwNw
17566   }
17567   \exp_not:N \exp_after:wN { \exp_not:N \tex_the:D #1 }
17568   ; \exp_not:N \__fp_parse_one_register_dim:ww
17569   \tl_to_str:n { pt } ; \exp_not:N \__fp_parse_one_register_mu:www
17570   . \tl_to_str:n { pt } ; \exp_not:N \__fp_parse_one_register_int:www
17571   \s__fp_stop
17572 }
17573 \exp_args:Nno \use:nn
17574 { \cs_new:Npn \__fp_parse_one_register_auxii:wwwNw #1 . #2 }
17575 { \tl_to_str:n { pt } #3 ; #4#5 \s__fp_stop }
17576 { #4 #1.#2; }
17577 \exp_args:Nno \use:nn
17578 { \cs_new:Npn \__fp_parse_one_register_mu:www #1 }
17579 { \tl_to_str:n { mu } ; #2 ; }
17580 { \__fp_parse_one_register_dim:ww #1 ; }
17581 \cs_new:Npn \__fp_parse_one_register_int:www #1; #2.; #3;
17582 { \__fp_parse:n { #1 e #3 } }
17583 \cs_new:Npn \__fp_parse_one_register_dim:ww #1; #2;
17584 {
17585   \exp_after:wN \__fp_from_dim_test:ww
17586   \int_value:w #2 \exp_after:wN ,
17587   \int_value:w \dim_to_decimal_in_sp:n { #1 pt } ;
17588 }

```

(End definition for `__fp_parse_one_register:NN` and others.)

`__fp_parse_one_register_special:N`
`__fp_parse_one_register_math:NNw`
`__fp_parse_one_register_wd:w`
`__fp_parse_one_register_wd:Nw`

The `\wd`, `\dp`, `\ht` primitives expect an integer argument. We abuse the exponent parser to find the integer argument: simply include the exponent marker `e`. Once that “exponent” is found, use `\tex_the:D` to find the box dimension and then copy what we did for dimensions.

```

17589 \cs_new:Npn \__fp_parse_one_register_special:N #1
17590 {
17591   \if_meaning:w \box_wd:N #1 \__fp_parse_one_register_wd:w \fi:
17592   \if_meaning:w \box_ht:N #1 \__fp_parse_one_register_wd:w \fi:
17593   \if_meaning:w \box_dp:N #1 \__fp_parse_one_register_wd:w \fi:
17594   \if_meaning:w \infty #1
17595     \__fp_parse_one_register_math:NNw \infty #1
17596   \fi:
17597   \if_meaning:w \pi #1
17598     \__fp_parse_one_register_math:NNw \pi #1
17599   \fi:
17600 }
17601 \cs_new:Npn \__fp_parse_one_register_math:NNw
17602   #1#2#3#4 \__fp_parse_expand:w
17603 {
17604   #3
17605   \str_if_eq:nnTF {#1} {#2}
17606   {
17607     \__kernel_msg_expandable_error:nnn
17608     { kernel } { fp-infty-pi } {#1}
17609     \c_nan_fp
17610   }
17611   { #4 \__fp_parse_expand:w }
17612 }
17613 \cs_new:Npn \__fp_parse_one_register_wd:w
17614   #1#2 \exp_after:wN #3#4 \__fp_parse_expand:w
17615 {
17616   #1
17617   \exp_after:wN \__fp_parse_one_register_wd:Nw
17618   #4 \__fp_parse_expand:w e
17619 }
17620 \cs_new:Npn \__fp_parse_one_register_wd:Nw #1#2 ;
17621 {
17622   \exp_after:wN \__fp_from_dim_test:ww
17623   \exp_after:wN 0 \exp_after:wN ,
17624   \int_value:w \dim_to_decimal_in_sp:n { #1 #2 } ;
17625 }

```

(End definition for __fp_parse_one_register_special:N and others.)

__fp_parse_one_digit:NN A digit marks the beginning of an explicit floating point number. Once the number is found, we catch the case of overflow and underflow with __fp_sanitize:wN, then __fp_parse_infix_after_operand:NwN expands __fp_parse_infix:NN after the number we find, to wrap the following infix operator as required. Finding the number itself begins by removing leading zeros: further steps are described later.

```

17626 \cs_new:Npn \__fp_parse_one_digit:NN #1
17627 {
17628   \exp_after:wN \__fp_parse_infix_after_operand:NwN
17629   \exp_after:wN #1
17630   \exp:w \exp_end_continue_f:w
17631   \exp_after:wN \__fp_sanitize:wN
17632   \int_value:w \__fp_int_eval:w 0 \__fp_parse_trim_zeros:N
17633 }

```

(End definition for __fp_parse_one_digit:NN.)

_fp_parse_one_other:NN For this function, #2 is a character token which is not a digit. If it is an ASCII letter, _fp_parse_letters:N beyond this one and give the result to _fp_parse_word:Nw. Otherwise, the character is assumed to be a prefix operator, and we build _fp_parse_prefix_{operator}:Nw.

```

17634 \cs_new:Npn \_fp_parse_one_other:NN #1 #2
17635 {
17636   \if_int_compare:w
17637     \_fp_int_eval:w
17638     ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
17639     = 3 \exp_stop_f:
17640     \exp_after:wN \_fp_parse_word:Nw
17641     \exp_after:wN #1
17642     \exp_after:wN #2
17643     \exp:w \exp_after:wN \_fp_parse_letters:N
17644     \exp:w
17645   \else:
17646     \exp_after:wN \_fp_parse_prefix:NNN
17647     \exp_after:wN #1
17648     \exp_after:wN #2
17649     \cs:w
17650     \_fp_parse_prefix_ \token_to_str:N #2 :Nw
17651     \exp_after:wN
17652     \cs_end:
17653     \exp:w
17654   \fi:
17655   \_fp_parse_expand:w
17656 }

```

(End definition for _fp_parse_one_other:NN.)

_fp_parse_word:Nw Finding letters is a simple recursion. Once _fp_parse_letters:N has done its job, _fp_parse_letters:N we try to build a control sequence from the word #2. If it is a known word, then the corresponding action is taken, and otherwise, we complain about an unknown word, yield \c_nan_fp, and look for the following infix operator. Note that the unknown word could be a mistyped function as well as a mistyped constant, so there is no way to tell whether to look for arguments; we do not. The standard requires “inf” and “infinity” and “nan” to be recognized regardless of case, but we probably don’t want to allow every l3fp word to have an arbitrary mixture of lower and upper case, so we test and use a differently-named control sequence.

```

17657 \cs_new:Npn \_fp_parse_word:Nw #1#2;
17658 {
17659   \cs_if_exist_use:cF { \_fp_parse_word_#2:N }
17660   {
17661     \cs_if_exist_use:cF
17662     { \_fp_parse_caseless_ \str_foldcase:n {#2} :N }
17663     {
17664       \_kernel_msg_expandable_error:nnn
17665       { kernel } { unknown-fp-word } {#2}
17666       \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
17667       \_fp_parse_infix:NN
17668     }
17669   }
17670   #1

```

```

17671 }
17672 \cs_new:Npn \__fp_parse_letters:N #1
17673 {
17674   \exp_end_continue_f:w
17675   \if_int_compare:w
17676     \if_catcode:w \scan_stop: \exp_not:N #1
17677     0
17678   \else:
17679     \__fp_int_eval:w
17680     ( '#1 \if_int_compare:w '#1 > 'Z - 32 \fi: ) / 26
17681   \fi:
17682   = 3 \exp_stop_f:
17683   \exp_after:wN #1
17684   \exp:w \exp_after:wN \__fp_parse_letters:N
17685   \exp:w
17686   \else:
17687     \__fp_parse_return_semicolon:w #1
17688   \fi:
17689   \__fp_parse_expand:w
17690 }

```

(End definition for __fp_parse_word:Nw and __fp_parse_letters:N.)

__fp_parse_prefix:NNN For this function, #1 is the previous *<precedence>*, #2 is the operator just seen, and #3 is a control sequence which implements the operator if it is a known operator. If this control sequence is \scan_stop:, then the operator is in fact unknown. Either the expression is missing a number there (if the operator is valid as an infix operator), and we put `nan`, wrapping the infix operator in a csname as appropriate, or the character is simply invalid in floating point expressions, and we continue looking for a number, starting again from __fp_parse_one:Nw.

```

17691 \cs_new:Npn \__fp_parse_prefix:NNN #1#2#3
17692 {
17693   \if_meaning:w \scan_stop: #3
17694     \exp_after:wN \__fp_parse_prefix_unknown:NNN
17695     \exp_after:wN #2
17696   \fi:
17697   #3 #1
17698 }
17699 \cs_new:Npn \__fp_parse_prefix_unknown:NNN #1#2#3
17700 {
17701   \cs_if_exist:cTF { __fp_parse_infix_ \token_to_str:N #1 :N }
17702   {
17703     \__kernel_msg_expandable_error:nnn
17704     { kernel } { fp-missing-number } {#1}
17705     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
17706     \__fp_parse_infix:NN #3 #1
17707   }
17708   {
17709     \__kernel_msg_expandable_error:nnn
17710     { kernel } { fp-unknown-symbol } {#1}
17711     \__fp_parse_one:Nw #3
17712   }
17713 }

```

(End definition for __fp_parse_prefix:NNN and __fp_parse_prefix_unknown:NNN.)

28.4.1 Numbers: trimming leading zeros

Numbers are parsed as follows: first we trim leading zeros, then if the next character is a digit, start reading a significand ≥ 1 with the set of functions `__fp_parse_large...`; if it is a period, the significand is < 1 ; and otherwise it is zero. In the second case, trim additional zeros after the period, counting them for an exponent shift $\langle exp_1 \rangle < 0$, then read the significand with the set of functions `__fp_parse_small...`. Once the significand is read, read the exponent if `e` is present.

`__fp_parse_trim_zeros:N` This function expects an already expanded token. It removes any leading zero, then distinguishes three cases: if the first non-zero token is a digit, then call `__fp_parse_large:N` (the significand is ≥ 1); if it is `.`, then continue trimming zeros with `__fp_parse_strim_zeros:N`; otherwise, our number is exactly zero, and we call `__fp_parse_zero:` to take care of that case.

```

17714 \cs_new:Npn \__fp_parse_trim_zeros:N #1
17715 {
17716   \if:w 0 \exp_not:N #1
17717     \exp_after:wN \__fp_parse_trim_zeros:N
17718     \exp:w
17719   \else:
17720     \if:w . \exp_not:N #1
17721       \exp_after:wN \__fp_parse_strim_zeros:N
17722       \exp:w
17723     \else:
17724       \__fp_parse_trim_end:w #1
17725     \fi:
17726   \fi:
17727   \__fp_parse_expand:w
17728 }
17729 \cs_new:Npn \__fp_parse_trim_end:w #1 \fi: \fi: \__fp_parse_expand:w
17730 {
17731   \fi:
17732   \fi:
17733   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
17734     \exp_after:wN \__fp_parse_large:N
17735   \else:
17736     \exp_after:wN \__fp_parse_zero:
17737   \fi:
17738   #1
17739 }
```

(End definition for `__fp_parse_trim_zeros:N` and `__fp_parse_trim_end:w`.)

`__fp_parse_strim_zeros:N` If we have removed all digits until a period (or if the body started with a period), then enter the “small_trim” loop which outputs `-1` for each removed 0. Those `-1` are added to an integer expression waiting for the exponent. If the first non-zero token is a digit, call `__fp_parse_small:N` (our significand is smaller than 1), and otherwise, the number is an exact zero. The name `strim` stands for “small trim”.

```

17740 \cs_new:Npn \__fp_parse_strim_zeros:N #1
17741 {
17742   \if:w 0 \exp_not:N #1
17743     - 1
17744     \exp_after:wN \__fp_parse_strim_zeros:N \exp:w
```

```

17745     \else:
17746         \__fp_parse_strim_end:w #1
17747     \fi:
17748     \__fp_parse_expand:w
17749 }
17750 \cs_new:Npn \__fp_parse_strim_end:w #1 \fi: \__fp_parse_expand:w
17751 {
17752     \fi:
17753     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
17754         \exp_after:wN \__fp_parse_small:N
17755     \else:
17756         \exp_after:wN \__fp_parse_zero:
17757     \fi:
17758     #1
17759 }

```

(End definition for __fp_parse_strim_zeros:N and __fp_parse_strim_end:w.)

__fp_parse_zero: After reading a significand of 0, find any exponent, then put a sign of 1 for __fp-sanitize:wN, which removes everything and leaves an exact zero.

```

17760 \cs_new:Npn \__fp_parse_zero:
17761 {
17762     \exp_after:wN ; \exp_after:wN 1
17763     \int_value:w \__fp_parse_exponent:N
17764 }

```

(End definition for __fp_parse_zero:.)

28.4.2 Number: small significand

__fp_parse_small:N This function is called after we have passed the decimal separator and removed all leading zeros from the significand. It is followed by a non-zero digit (with any catcode). The goal is to read up to 16 digits. But we can't do that all at once, because \int_value:w (which allows us to collect digits and continue expanding) can only go up to 9 digits. Hence we grab digits in two steps of 8 digits. Since #1 is a digit, read seven more digits using __fp_parse_digits_vii:N. The small_leading auxiliary leaves those digits in the \int_value:w, and grabs some more, or stops if there are no more digits. Then the pack_leading auxiliary puts the various parts in the appropriate order for the processing further up.

```

17765 \cs_new:Npn \__fp_parse_small:N #1
17766 {
17767     \exp_after:wN \__fp_parse_pack_leading:NNNNnw
17768     \int_value:w \__fp_int_eval:w 1 \token_to_str:N #1
17769     \exp_after:wN \__fp_parse_small_leading:wwNN
17770     \int_value:w 1
17771     \exp_after:wN \__fp_parse_digits_vii:N
17772     \exp:w \__fp_parse_expand:w
17773 }

```

(End definition for __fp_parse_small:N.)

_fp_parse_small_leading:wwNN __fp_parse_small_leading:wwNN 1 <digits> ; <zeros> ; <number of zeros>
 We leave <digits> <zeros> in the input stream: the functions used to grab digits are such that this constitutes digits 1 through 8 of the significand. Then prepare to pack

8 more digits, with an exponent shift of zero (this shift is used in the case of a large significand). If #4 is a digit, leave it behind for the packing function, and read 6 more digits to reach a total of 15 digits: further digits are involved in the rounding. Otherwise put 8 zeros in to complete the significand, then look for an exponent.

```

17774 \cs_new:Npn \__fp_parse_small_leading:wwNN 1 #1 ; #2; #3 #4
17775 {
17776   #1 #2
17777   \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
17778   \exp_after:wN 0
17779   \int_value:w \__fp_int_eval:w 1
17780   \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
17781     \token_to_str:N #4
17782     \exp_after:wN \__fp_parse_small_trailing:wwNN
17783     \int_value:w 1
17784     \exp_after:wN \__fp_parse_digits_vi:N
17785     \exp:w
17786   \else:
17787     0000 0000 \__fp_parse_exponent:Nw #4
17788   \fi:
17789   \__fp_parse_expand:w
17790 }

```

(End definition for __fp_parse_small_leading:wwNN.)

```

\__fp_parse_small_trailing:wwNN \__fp_parse_small_trailing:wwNN 1 <digits> ; <zeros> ; <number of zeros>
<next token>

```

Leave digits 10 to 15 (arguments #1 and #2) in the input stream. If the *<next token>* is a digit, it is the 16th digit, we keep it, then the `small_round` auxiliary considers this digit and all further digits to perform the rounding: the function expands to nothing, to +0 or to +1. Otherwise, there is no 16-th digit, so we put a 0, and look for an exponent.

```

17791 \cs_new:Npn \__fp_parse_small_trailing:wwNN 1 #1 ; #2; #3 #4
17792 {
17793   #1 #2
17794   \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
17795     \token_to_str:N #4
17796     \exp_after:wN \__fp_parse_small_round:NN
17797     \exp_after:wN #4
17798     \exp:w
17799   \else:
17800     0 \__fp_parse_exponent:Nw #4
17801   \fi:
17802   \__fp_parse_expand:w
17803 }

```

(End definition for __fp_parse_small_trailing:wwNN.)

```

\__fp_parse_pack_trailing:NNNNNNww
\__fp_parse_pack_leading:NNNNNNww
\__fp_parse_pack_carry:w

```

Those functions are expanded after all the digits are found, we took care of the rounding, as well as the exponent. The last argument is the exponent. The previous five arguments are 8 digits which we pack in groups of 4, and the argument before that is 1, except in the rare case where rounding lead to a carry, in which case the argument is 2. The `trailing` function has an exponent shift as its first argument, which we add to the exponent found in the `e...` syntax. If the trailing digits cause a carry, the integer expression for the leading digits is incremented (+1 in the code below). If the leading digits propagate this

carry all the way up, the function `__fp_parse_pack_carry:w` increments the exponent, and changes the significand from 0000... to 1000...: this is simple because such a carry can only occur to give rise to a power of 10.

```

17804 \cs_new:Npn \__fp_parse_pack_trailing:NNNNNNww #1 #2 #3#4#5#6 #7; #8 ;
17805 {
17806   \if_meaning:w 2 #2 + 1 \fi:
17807   ; #8 + #1 ; {#3#4#5#6} {#7};
17808 }
17809 \cs_new:Npn \__fp_parse_pack_leading:NNNNNNww #1 #2#3#4#5 #6; #7;
17810 {
17811   + #7
17812   \if_meaning:w 2 #1 \__fp_parse_pack_carry:w \fi:
17813   ; 0 {#2#3#4#5} {#6}
17814 }
17815 \cs_new:Npn \__fp_parse_pack_carry:w \fi: ; 0 #1
17816 { \fi: + 1 ; 0 {1000} }

```

(End definition for `__fp_parse_pack_trailing:NNNNNNww`, `__fp_parse_pack_leading:NNNNNNww`, and `__fp_parse_pack_carry:w`.)

28.4.3 Number: large significand

Parsing a significand larger than 1 is a little bit more difficult than parsing small significands. We need to count the number of digits before the decimal separator, and add that to the final exponent. We also need to test for the presence of a dot each time we run out of digits, and branch to the appropriate `parse_small` function in those cases.

`__fp_parse_large:N` This function is followed by the first non-zero digit of a “large” significand (≥ 1). It is called within an integer expression for the exponent. Grab up to 7 more digits, for a total of 8 digits.

```

17817 \cs_new:Npn \__fp_parse_large:N #1
17818 {
17819   \exp_after:wN \__fp_parse_large_leading:wwNN
17820   \int_value:w 1 \token_to_str:N #1
17821   \exp_after:wN \__fp_parse_digits_vii:N
17822   \exp:w \__fp_parse_expand:w
17823 }

```

(End definition for `__fp_parse_large:N`.)

`__fp_parse_large_leading:wwNN` `__fp_parse_large_leading:wwNN 1 <digits> ; <zeros> ; <number of zeros> <next token>`

We shift the exponent by the number of digits in #1, namely the target number, 8, minus the *<number of zeros>* (number of digits missing). Then prepare to pack the 8 first digits. If the *<next token>* is a digit, read up to 6 more digits (digits 10 to 15). If it is a period, try to grab the end of our 8 first digits, branching to the `small` functions since the number of digit does not affect the exponent anymore. Finally, if this is the end of the significand, insert the *<zeros>* to complete the 8 first digits, insert 8 more, and look for an exponent.

```

17824 \cs_new:Npn \__fp_parse_large_leading:wwNN 1 #1 ; #2; #3 #4
17825 {
17826   + \c__fp_half_prec_int - #3
17827   \exp_after:wN \__fp_parse_pack_leading:NNNNNNww

```

```

17828 \int_value:w \_fp_int_eval:w 1 #1
17829 \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
17830 \exp_after:wN \_fp_parse_large_trailing:wwNN
17831 \int_value:w 1 \token_to_str:N #4
17832 \exp_after:wN \_fp_parse_digits_vi:N
17833 \exp:w
17834 \else:
17835 \if:w . \exp_not:N #4
17836 \exp_after:wN \_fp_parse_small_leading:wwNN
17837 \int_value:w 1
17838 \cs:w
17839 \_fp_parse_digits_
17840 \_fp_int_to_roman:w #3
17841 :N \exp_after:wN
17842 \cs_end:
17843 \exp:w
17844 \else:
17845 #2
17846 \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
17847 \exp_after:wN 0
17848 \int_value:w 1 0000 0000
17849 \_fp_parse_exponent:Nw #4
17850 \fi:
17851 \fi:
17852 \_fp_parse_expand:w
17853 }

```

(End definition for _fp_parse_large_leading:wwNN.)

```

\_fp_parse_large_trailing:wwNN \_fp_parse_large_trailing:wwNN 1 <digits> ; <zeros> ; <number of zeros>
<next token>

```

We have just read 15 digits. If the *<next token>* is a digit, then the exponent shift caused by this block of 8 digits is 8, first argument to the `pack_trailing` function. We keep the *<digits>* and this 16-th digit, and find how this should be rounded using `_fp_parse_large_round:NN`. Otherwise, the exponent shift is the number of *<digits>*, 7 minus the *<number of zeros>*, and we test for a decimal point. This case happens in 123451234512345.67 with exactly 15 digits before the decimal separator. Then branch to the appropriate `small` auxiliary, grabbing a few more digits to complement the digits we already grabbed. Finally, if this is truly the end of the significand, look for an exponent after using the *<zeros>* and providing a 16-th digit of 0.

```

17854 \cs_new:Npn \_fp_parse_large_trailing:wwNN 1 #1 ; #2; #3 #4
17855 {
17856 \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
17857 \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
17858 \exp_after:wN \c_fp_half_prec_int
17859 \int_value:w \_fp_int_eval:w 1 #1 \token_to_str:N #4
17860 \exp_after:wN \_fp_parse_large_round:NN
17861 \exp_after:wN #4
17862 \exp:w
17863 \else:
17864 \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
17865 \int_value:w \_fp_int_eval:w 7 - #3 \exp_stop_f:
17866 \int_value:w \_fp_int_eval:w 1 #1

```

```

17867         \if:w . \exp_not:N #4
17868         \exp_after:wN \__fp_parse_small_trailing:wwNN
17869         \int_value:w 1
17870         \cs:w
17871         __fp_parse_digits_
17872         \__fp_int_to_roman:w #3
17873         :N \exp_after:wN
17874         \cs_end:
17875         \exp:w
17876     \else:
17877         #2 0 \__fp_parse_exponent:Nw #4
17878     \fi:
17879 \fi:
17880 \__fp_parse_expand:w
17881 }

```

(End definition for __fp_parse_large_trailing:wwNN.)

28.4.4 Number: beyond 16 digits, rounding

__fp_parse_round_loop:N This loop is called when rounding a number (whether the mantissa is small or large).
 __fp_parse_round_up:N It should appear in an integer expression. This function reads digits one by one, until reaching a non-digit, and adds 1 to the integer expression for each digit. If all digits found are 0, the function ends the expression by ;0, otherwise by ;1. This is done by switching the loop to round_up at the first non-zero digit, thus we avoid to test whether digits are 0 or not once we see a first non-zero digit.

```

17882 \cs_new:Npn \__fp_parse_round_loop:N #1
17883 {
17884     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
17885     + 1
17886     \if:w 0 \token_to_str:N #1
17887     \exp_after:wN \__fp_parse_round_loop:N
17888     \exp:w
17889     \else:
17890     \exp_after:wN \__fp_parse_round_up:N
17891     \exp:w
17892     \fi:
17893     \else:
17894     \__fp_parse_return_semicolon:w 0 #1
17895     \fi:
17896     \__fp_parse_expand:w
17897 }
17898 \cs_new:Npn \__fp_parse_round_up:N #1
17899 {
17900     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
17901     + 1
17902     \exp_after:wN \__fp_parse_round_up:N
17903     \exp:w
17904     \else:
17905     \__fp_parse_return_semicolon:w 1 #1
17906     \fi:
17907     \__fp_parse_expand:w
17908 }

```

(End definition for `_fp_parse_round_loop:N` and `_fp_parse_round_up:N`.)

`_fp_parse_round_after:wN` After the loop `_fp_parse_round_loop:N`, this function fetches an exponent with `_fp_parse_exponent:N`, and combines it with the number of digits counted by `_fp_parse_round_loop:N`. At the same time, the result 0 or 1 is added to the surrounding integer expression.

```

17909 \cs_new:Npn \_fp_parse_round_after:wN #1; #2
17910 {
17911   + #2 \exp_after:wN ;
17912   \int_value:w \_fp_int_eval:w #1 + \_fp_parse_exponent:N
17913 }

```

(End definition for `_fp_parse_round_after:wN`.)

`_fp_parse_small_round:NN` Here, #1 is the digit that we are currently rounding (we only care whether it is even or odd). If #2 is not a digit, then fetch an exponent and expand to `;\exponent` only. Otherwise, we expand to `+0` or `+1`, then `;\exponent`. To decide which, call `_fp_round_s:NNNw` to know whether to round up, giving it as arguments a sign 0 (all explicit numbers are positive), the digit #1 to round, the first following digit #2, and either `+0` or `+1` depending on whether the following digits are all zero or not. This last argument is obtained by `_fp_parse_round_loop:N`, whose number of digits we discard by multiplying it by 0. The exponent which follows the number is also fetched by `_fp_parse_round_after:wN`.

```

17914 \cs_new:Npn \_fp_parse_small_round:NN #1#2
17915 {
17916   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
17917     +
17918     \exp_after:wN \_fp_round_s:NNNw
17919     \exp_after:wN 0
17920     \exp_after:wN #1
17921     \exp_after:wN #2
17922     \int_value:w \_fp_int_eval:w
17923     \exp_after:wN \_fp_parse_round_after:wN
17924     \int_value:w \_fp_int_eval:w 0 * \_fp_int_eval:w 0
17925     \exp_after:wN \_fp_parse_round_loop:N
17926     \exp:w
17927   \else:
17928     \_fp_parse_exponent:Nw #2
17929   \fi:
17930   \_fp_parse_expand:w
17931 }

```

(End definition for `_fp_parse_small_round:NN` and `_fp_parse_round_after:wN`.)

`_fp_parse_large_round:NN` Large numbers are harder to round, as there may be a period in the way. Again, #1 is the digit that we are currently rounding (we only care whether it is even or odd). If there are no more digits (#2 is not a digit), then we must test for a period: if there is one, then switch to the rounding function for small significands, otherwise fetch an exponent. If there are more digits (#2 is a digit), then round, checking with `_fp_parse_round_loop:N` if all further digits vanish, or some are non-zero. This loop is not enough, as it is stopped by a period. After the loop, the `aux` function tests for a period: if it is present, then we must continue looking for digits, this time discarding the number of digits we find.

```

\_fp_parse_large_round_test:NN
\_fp_parse_large_round_aux:wNN

```

```

17932 \cs_new:Npn \__fp_parse_large_round:NN #1#2
17933 {
17934   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
17935   +
17936   \exp_after:wN \__fp_round_s:NNNw
17937   \exp_after:wN 0
17938   \exp_after:wN #1
17939   \exp_after:wN #2
17940   \int_value:w \__fp_int_eval:w
17941   \exp_after:wN \__fp_parse_large_round_aux:wNN
17942   \int_value:w \__fp_int_eval:w 1
17943   \exp_after:wN \__fp_parse_round_loop:N
17944   \else: %^^A could be dot, or e, or other
17945   \exp_after:wN \__fp_parse_large_round_test:NN
17946   \exp_after:wN #1
17947   \exp_after:wN #2
17948   \fi:
17949 }
17950 \cs_new:Npn \__fp_parse_large_round_test:NN #1#2
17951 {
17952   \if:w . \exp_not:N #2
17953   \exp_after:wN \__fp_parse_small_round:NN
17954   \exp_after:wN #1
17955   \exp:w
17956   \else:
17957   \__fp_parse_exponent:Nw #2
17958   \fi:
17959   \__fp_parse_expand:w
17960 }
17961 \cs_new:Npn \__fp_parse_large_round_aux:wNN #1 ; #2 #3
17962 {
17963   + #2
17964   \exp_after:wN \__fp_parse_round_after:wN
17965   \int_value:w \__fp_int_eval:w #1
17966   \if:w . \exp_not:N #3
17967   + 0 * \__fp_int_eval:w 0
17968   \exp_after:wN \__fp_parse_round_loop:N
17969   \exp:w \exp_after:wN \__fp_parse_expand:w
17970   \else:
17971   \exp_after:wN ;
17972   \exp_after:wN 0
17973   \exp_after:wN #3
17974   \fi:
17975 }

```

(End definition for __fp_parse_large_round:NN, __fp_parse_large_round_test:NN, and __fp_parse_large_round_aux:wNN.)

28.4.5 Number: finding the exponent

Expansion is a little bit tricky here, in part because we accept input where multiplication is implicit.

```

\__fp_parse:n { 3.2 erf(0.1) }
\__fp_parse:n { 3.2 e\l_my_int }
\__fp_parse:n { 3.2 \c_pi_fp }

```

The first case indicates that just looking one character ahead for an “e” is not enough, since we would mistake the function `erf` for an exponent of “rf”. An alternative would be to look two tokens ahead and check if what follows is a sign or a digit, considering in that case that we must be finding an exponent. But taking care of the second case requires that we unpack registers after `e`. However, blindly expanding the two tokens ahead completely would break the third example (unpacking is even worse). Indeed, in the course of reading `3.2`, `\c_pi_fp` is expanded to `\s__fp __fp_chk:w 1 0 {-1} {3141} ...`; and `\s__fp` stops the expansion. Expanding two tokens ahead would then force the expansion of `__fp_chk:w` (despite it being protected), and that function tries to produce an error.

What can we do? Really, the reason why this last case breaks is that just as `TeX` does, we should read ahead as little as possible. Here, the only case where there may be an exponent is if the first token ahead is `e`. Then we expand (and possibly unpack) the second token.

`__fp_parse_exponent:Nw`

This auxiliary is convenient to smuggle some material through `\fi:` ending conditional processing. We place those `\fi:` (argument #2) at a very odd place because this allows us to insert `__fp_int_eval:w ...` there if needed.

```

17976 \cs_new:Npn \__fp_parse_exponent:Nw #1 #2 \__fp_parse_expand:w
17977 {
17978   \exp_after:wN ;
17979   \int_value:w #2 \__fp_parse_exponent:N #1
17980 }

```

(End definition for `__fp_parse_exponent:Nw`.)

`__fp_parse_exponent:N`
`__fp_parse_exponent_aux:N`

This function should be called within an `\int_value:w` expansion (or within an integer expression). It leaves digits of the exponent behind it in the input stream, and terminates the expansion with a semicolon. If there is no `e` (or `E`), leave an exponent of 0. If there is an `e` or `E`, expand the next token to run some tests on it. The first rough test is that if the character code of #1 is greater than that of 9 (largest code valid for an exponent, less than any code valid for an identifier), there was in fact no exponent; otherwise, we search for the sign of the exponent.

```

17981 \cs_new:Npn \__fp_parse_exponent:N #1
17982 {
17983   \if:w e \if:w E \exp_not:N #1 e \else: \exp_not:N #1 \fi:
17984   \exp_after:wN \__fp_parse_exponent_aux:N
17985   \exp:w
17986   \else:
17987     0 \__fp_parse_return_semicolon:w #1
17988   \fi:
17989   \__fp_parse_expand:w
17990 }
17991 \cs_new:Npn \__fp_parse_exponent_aux:N #1
17992 {
17993   \if_int_compare:w \if_catcode:w \scan_stop: \exp_not:N #1
17994     0 \else: '#1 \fi: > '9 \exp_stop_f:
17995     0 \exp_after:wN ; \exp_after:wN e
17996   \else:

```

```

17997     \exp_after:wN \__fp_parse_exponent_sign:N
17998     \fi:
17999     #1
18000   }

```

(End definition for __fp_parse_exponent:N and __fp_parse_exponent_aux:N.)

__fp_parse_exponent_sign:N Read signs one by one (if there is any).

```

18001 \cs_new:Npn \__fp_parse_exponent_sign:N #1
18002 {
18003   \if:w + \if:w - \exp_not:N #1 + \fi: \token_to_str:N #1
18004   \exp_after:wN \__fp_parse_exponent_sign:N
18005   \exp:w \exp_after:wN \__fp_parse_expand:w
18006   \else:
18007     \exp_after:wN \__fp_parse_exponent_body:N
18008     \exp_after:wN #1
18009   \fi:
18010 }

```

(End definition for __fp_parse_exponent_sign:N.)

__fp_parse_exponent_body:N An exponent can be an explicit integer (most common case), or various other things (most of which are invalid).

```

18011 \cs_new:Npn \__fp_parse_exponent_body:N #1
18012 {
18013   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
18014   \token_to_str:N #1
18015   \exp_after:wN \__fp_parse_exponent_digits:N
18016   \exp:w
18017   \else:
18018     \__fp_parse_exponent_keep:NTF #1
18019     { \__fp_parse_return_semicolon:w #1 }
18020     {
18021       \exp_after:wN ;
18022       \exp:w
18023     }
18024   \fi:
18025   \__fp_parse_expand:w
18026 }

```

(End definition for __fp_parse_exponent_body:N.)

__fp_parse_exponent_digits:N Read digits one by one, and leave them behind in the input stream. When finding a non-digit, stop, and insert a semicolon. Note that we do not check for overflow of the exponent, hence there can be a TeX error. It is mostly harmless, except when parsing 0e9876543210, which should be a valid representation of 0, but is not.

```

18027 \cs_new:Npn \__fp_parse_exponent_digits:N #1
18028 {
18029   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
18030   \token_to_str:N #1
18031   \exp_after:wN \__fp_parse_exponent_digits:N
18032   \exp:w
18033   \else:
18034     \__fp_parse_return_semicolon:w #1

```

```

18035     \fi:
18036     \__fp_parse_expand:w
18037 }

```

(End definition for __fp_parse_exponent_digits:N.)

__fp_parse_exponent_keep:NTF This is the last building block for parsing exponents. The argument #1 is already fully expanded, and neither + nor - nor a digit. It can be:

- \s__fp, marking the start of an internal floating point, invalid here;
- another control sequence equal to \relax, probably a bad variable;
- a register: in this case we make sure that it is an integer register, not a dimension;
- a character other than +, - or digits, again, an error.

```

18038 \prg_new_conditional:Npnn \__fp_parse_exponent_keep:N #1 { TF }
18039 {
18040     \if_catcode:w \scan_stop: \exp_not:N #1
18041     \if_meaning:w \scan_stop: #1
18042     \if_int_compare:w
18043         \__fp_str_if_eq:nn { \s__fp } { \exp_not:N #1 }
18044         = 0 \exp_stop_f:
18045         0
18046         \__kernel_msg_expandable_error:nnn
18047         { kernel } { fp-after-e } { floating-point~ }
18048         \prg_return_true:
18049     \else:
18050         0
18051         \__kernel_msg_expandable_error:nnn
18052         { kernel } { bad-variable } { #1 }
18053         \prg_return_false:
18054     \fi:
18055     \else:
18056     \if_int_compare:w
18057         \__fp_str_if_eq:nn { \int_value:w #1 } { \tex_the:D #1 }
18058         = 0 \exp_stop_f:
18059         \int_value:w #1
18060     \else:
18061         0
18062         \__kernel_msg_expandable_error:nnn
18063         { kernel } { fp-after-e } { dimension~#1 }
18064     \fi:
18065     \prg_return_false:
18066     \fi:
18067     \else:
18068         0
18069         \__kernel_msg_expandable_error:nnn
18070         { kernel } { fp-missing } { exponent }
18071     \prg_return_true:
18072     \fi:
18073 }

```

(End definition for __fp_parse_exponent_keep:NTF.)

28.5 Constants, functions and prefix operators

28.5.1 Prefix operators

`_fp_parse_prefix_+:Nw` A unary + does nothing: we should continue looking for a number.

```
18074 \cs_new_eq:cN { \_fp_parse_prefix_+:Nw } \_fp_parse_one:Nw
```

(End definition for `_fp_parse_prefix_+:Nw`.)

`_fp_parse_apply_function:NNNwN` Here, #1 is a precedence, #2 is some extra data used by some functions, #3 is *e.g.*, `_fp_sin_o:w`, and expands once after the calculation, #4 is the operand, and #5 is a `_fp_parse_infix_...:N` function. We feed the data #2, and the argument #4, to the function #3, which expands `\exp:w` thus the infix function #5.

```
18075 \cs_new:Npn \_fp_parse_apply_function:NNNwN #1#2#3#4#5
18076 {
18077   #3 #2 #4 @
18078   \exp:w \exp_end_continue_f:w #5 #1
18079 }
```

(End definition for `_fp_parse_apply_function:NNNwN`.)

`_fp_parse_apply_unary:NNNwN` In contrast to `_fp_parse_apply_function:NNNwN`, this checks that the operand #4 is a single argument (namely there is a single `;`). We use the fact that any floating point starts with a “safe” token like `\s__fp`. If there is no argument produce the `fp-no-arg` error; if there are at least two produce `fp-multi-arg`. For the error message extract the mathematical function name (such as `sin`) from the `expl3` function that computes it, such as `_fp_sin_o:w`.

`_fp_parse_apply_unary_chk:NwNw`
`_fp_parse_apply_unary_chk:nNNNw`
`_fp_parse_apply_unary_type:NNN`
`_fp_parse_apply_unary_error:NNw`

In addition, since there is a single argument we can dispatch on type and check that the resulting function exists. This catches things like `sin((1,2))` where it does not make sense to take the sine of a tuple.

```
18080 \cs_new:Npn \_fp_parse_apply_unary:NNNwN #1#2#3#4#5
18081 {
18082   \_fp_parse_apply_unary_chk:NwNw #4 @ ; . \s__fp_stop
18083   \_fp_parse_apply_unary_type:NNN
18084   #3 #2 #4 @
18085   \exp:w \exp_end_continue_f:w #5 #1
18086 }
18087 \cs_new:Npn \_fp_parse_apply_unary_chk:NwNw #1#2 ; #3#4 \s__fp_stop
18088 {
18089   \if_meaning:w @ #3 \else:
18090     \token_if_eq_meaning:NNTF . #3
18091     { \_fp_parse_apply_unary_chk:nNNNNw { no } }
18092     { \_fp_parse_apply_unary_chk:nNNNNw { multi } }
18093   \fi:
18094 }
18095 \cs_new:Npn \_fp_parse_apply_unary_chk:nNNNNw #1#2#3#4#5#6 @
18096 {
18097   #2
18098   \_fp_error:nffn { fp-#1-arg } { \_fp_func_to_name:N #4 } { } { }
18099   \exp_after:wN #4 \exp_after:wN #5 \c_nan_fp @
18100 }
18101 \cs_new:Npn \_fp_parse_apply_unary_type:NNN #1#2#3
18102 {
18103   \_fp_change_func_type:NNN #3 #1 \_fp_parse_apply_unary_error:NNw
```

```

18104     #2 #3
18105   }
18106 \cs_new:Npn \__fp_parse_apply_unary_error:NNw #1#2#3 @
18107   { \__fp_invalid_operation_o:fw { \__fp_func_to_name:N #1 } #3 }

```

(End definition for __fp_parse_apply_unary:NNwN and others.)

__fp_parse_prefix -:Nw
__fp_parse_prefix !:Nw

The unary - and boolean not are harder: we parse the operand using a precedence equal to the maximum of the previous precedence ##1 and the precedence \c__fp_prec_not_int of the unary operator, then call the appropriate __fp_⟨operation⟩_o:w function, where the ⟨operation⟩ is set_sign or not.

```

18108 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
18109   {
18110     \cs_new:cpn { \__fp_parse_prefix_ #1 :Nw } ##1
18111     {
18112       \exp_after:wN \__fp_parse_apply_unary:NNwN
18113       \exp_after:wN ##1
18114       \exp_after:wN #4
18115       \exp_after:wN #3
18116       \exp:w
18117       \if_int_compare:w #2 < ##1
18118         \__fp_parse_operand:Nw ##1
18119       \else:
18120         \__fp_parse_operand:Nw #2
18121       \fi:
18122       \__fp_parse_expand:w
18123     }
18124   }
18125 \__fp_tmp:w - \c__fp_prec_not_int \__fp_set_sign_o:w 2
18126 \__fp_tmp:w ! \c__fp_prec_not_int \__fp_not_o:w ?

```

(End definition for __fp_parse_prefix -:Nw and __fp_parse_prefix !:Nw.)

__fp_parse_prefix .:Nw

Numbers which start with a decimal separator (a period) end up here. Of course, we do not look for an operand, but for the rest of the number. This function is very similar to __fp_parse_one_digit:NN but calls __fp_parse_strim_zeros:N to trim zeros after the decimal point, rather than the trim_zeros function for zeros before the decimal point.

```

18127 \cs_new:cpn { \__fp_parse_prefix .:Nw } #1
18128   {
18129     \exp_after:wN \__fp_parse_infix_after_operand:NwN
18130     \exp_after:wN #1
18131     \exp:w \exp_end_continue_f:w
18132     \exp_after:wN \__fp_sanitize:wN
18133     \int_value:w \__fp_int_eval:w 0 \__fp_parse_strim_zeros:N
18134   }

```

(End definition for __fp_parse_prefix .:Nw.)

__fp_parse_prefix (:Nw
__fp_parse_lparen_after:NwN

The left parenthesis is treated as a unary prefix operator because it appears in exactly the same settings. If the previous precedence is \c__fp_prec_func_int we are parsing arguments of a function and commas should not build tuples; otherwise commas should build tuples. We distinguish these cases by precedence: \c__fp_prec_comma_int for the case of arguments, \c__fp_prec_tuple_int for the case of tuples. Once the operand

is found, the `lparen_after` auxiliary makes sure that there was a closing parenthesis (otherwise it complains), and leaves in the input stream an operand, fetching the following infix operator.

```

18135 \cs_new:cpn { __fp_parse_prefix_(:Nw } #1
18136 {
18137   \exp_after:wN \__fp_parse_lparen_after:NwN
18138   \exp_after:wN #1
18139   \exp:w
18140   \if_int_compare:w #1 = \c__fp_prec_func_int
18141     \__fp_parse_operand:Nw \c__fp_prec_comma_int
18142   \else:
18143     \__fp_parse_operand:Nw \c__fp_prec_tuple_int
18144   \fi:
18145   \__fp_parse_expand:w
18146 }
18147 \cs_new:Npx \__fp_parse_lparen_after:NwN #1#2 @ #3
18148 {
18149   \exp_not:N \token_if_eq_meaning:NNTF #3
18150   \exp_not:c { __fp_parse_infix_):N }
18151   {
18152     \exp_not:N \__fp_exp_after_array_f:w #2 \s__fp_expr_stop
18153     \exp_not:N \exp_after:wN
18154     \exp_not:N \__fp_parse_infix_after_paren:NN
18155     \exp_not:N \exp_after:wN #1
18156     \exp_not:N \exp:w
18157     \exp_not:N \__fp_parse_expand:w
18158   }
18159   {
18160     \exp_not:N \__kernel_msg_expandable_error:nnn
18161     { kernel } { fp-missing } { } }
18162     \exp_not:N \tl_if_empty:nT {#2} \exp_not:N \c__fp_empty_tuple_fp
18163     #2 @
18164     \exp_not:N \use_none:n #3
18165   }
18166 }

```

(End definition for `__fp_parse_prefix_(:Nw` and `__fp_parse_lparen_after:NwN`.)

`__fp_parse_prefix_):Nw` The right parenthesis can appear as a prefix in two similar cases: in an empty tuple or tuple ending with a comma, or in an empty argument list or argument list ending with a comma, such as in `max(1,2,)` or in `rand()`.

```

18167 \cs_new:cpn { __fp_parse_prefix_):Nw } #1
18168 {
18169   \if_int_compare:w #1 = \c__fp_prec_comma_int
18170   \else:
18171     \if_int_compare:w #1 = \c__fp_prec_tuple_int
18172     \exp_after:wN \c__fp_empty_tuple_fp \exp:w
18173   \else:
18174     \__kernel_msg_expandable_error:nnn
18175     { kernel } { fp-missing-number } { } }
18176     \exp_after:wN \c_nan_fp \exp:w
18177   \fi:
18178   \exp_end_continue_f:w
18179 \fi:

```

```

18180     \__fp_parse_infix_after_paren:NN #1 )
18181 }

```

(End definition for __fp_parse_prefix_):Nw.)

28.5.2 Constants

Some words correspond to constant floating points. The floating point constant is left as a result of __fp_parse_one:Nw after expanding __fp_parse_infix:NN.

```

\__fp_parse_word_inf:N
\__fp_parse_word_nan:N
\__fp_parse_word_pi:N
\__fp_parse_word_deg:N
\__fp_parse_word_true:N
\__fp_parse_word_false:N

```

```

18182 \cs_set_protected:Npn \__fp_tmp:w #1 #2
18183 {
18184     \cs_new:cpn { \__fp_parse_word_#1:N }
18185     { \exp_after:wN #2 \exp:w \exp_end_continue_f:w \__fp_parse_infix:NN }
18186 }
18187 \__fp_tmp:w { inf } \c_inf_fp
18188 \__fp_tmp:w { nan } \c_nan_fp
18189 \__fp_tmp:w { pi } \c_pi_fp
18190 \__fp_tmp:w { deg } \c_one_degree_fp
18191 \__fp_tmp:w { true } \c_one_fp
18192 \__fp_tmp:w { false } \c_zero_fp

```

(End definition for __fp_parse_word_inf:N and others.)

Copies of __fp_parse_word_...:N commands, to allow arbitrary case as mandated by the standard.

```

\__fp_parse_caseless_inf:N
\__fp_parse_caseless_infinity:N
\__fp_parse_caseless_nan:N

```

```

18193 \cs_new_eq:NN \__fp_parse_caseless_inf:N \__fp_parse_word_inf:N
18194 \cs_new_eq:NN \__fp_parse_caseless_infinity:N \__fp_parse_word_inf:N
18195 \cs_new_eq:NN \__fp_parse_caseless_nan:N \__fp_parse_word_nan:N

```

(End definition for __fp_parse_caseless_inf:N, __fp_parse_caseless_infinity:N, and __fp_parse_caseless_nan:N.)

Dimension units are also floating point constants but their value is not stored as a floating point constant. We give the values explicitly here.

```

\__fp_parse_word_pt:N
\__fp_parse_word_in:N
\__fp_parse_word_pc:N
\__fp_parse_word_cm:N
\__fp_parse_word_mm:N
\__fp_parse_word_dd:N
\__fp_parse_word_cc:N
\__fp_parse_word_nd:N
\__fp_parse_word_nc:N
\__fp_parse_word_bp:N
\__fp_parse_word_sp:N

```

```

18196 \cs_set_protected:Npn \__fp_tmp:w #1 #2
18197 {
18198     \cs_new:cpn { \__fp_parse_word_#1:N }
18199     {
18200         \__fp_exp_after_f:nw { \__fp_parse_infix:NN }
18201         \s__fp \__fp_chk:w 10 #2 ;
18202     }
18203 }
18204 \__fp_tmp:w {pt} { {1} {1000} {0000} {0000} {0000} }
18205 \__fp_tmp:w {in} { {2} {7227} {0000} {0000} {0000} }
18206 \__fp_tmp:w {pc} { {2} {1200} {0000} {0000} {0000} }
18207 \__fp_tmp:w {cm} { {2} {2845} {2755} {9055} {1181} }
18208 \__fp_tmp:w {mm} { {1} {2845} {2755} {9055} {1181} }
18209 \__fp_tmp:w {dd} { {1} {1070} {0085} {6496} {0630} }
18210 \__fp_tmp:w {cc} { {2} {1284} {0102} {7795} {2756} }
18211 \__fp_tmp:w {nd} { {1} {1066} {9783} {4645} {6693} }
18212 \__fp_tmp:w {nc} { {2} {1280} {3740} {1574} {8031} }
18213 \__fp_tmp:w {bp} { {1} {1003} {7500} {0000} {0000} }
18214 \__fp_tmp:w {sp} { {-4} {1525} {8789} {0625} {0000} }

```

(End definition for __fp_parse_word_pt:N and others.)

`__fp_parse_word_em:N` The font-dependent units `em` and `ex` must be evaluated on the fly. We reuse an auxiliary of `\dim_to_fp:n`.

```

18215 \tl_map_inline:nn { {em} {ex} }
18216 {
18217   \cs_new:cpn { __fp_parse_word_#1:N }
18218   {
18219     \exp_after:wN \__fp_from_dim_test:ww
18220     \exp_after:wN 0 \exp_after:wN ,
18221     \int_value:w \dim_to_decimal_in_sp:n { 1 #1 } \exp_after:wN ;
18222     \exp:w \exp_end_continue_f:w \__fp_parse_infix:NN
18223   }
18224 }
```

(End definition for `__fp_parse_word_em:N` and `__fp_parse_word_ex:N`.)

28.5.3 Functions

```

\__fp_parse_unary_function:NNN
\__fp_parse_function:NNN
18225 \cs_new:Npn \__fp_parse_unary_function:NNN #1#2#3
18226 {
18227   \exp_after:wN \__fp_parse_apply_unary:NNNwN
18228   \exp_after:wN #3
18229   \exp_after:wN #2
18230   \exp_after:wN #1
18231   \exp:w
18232   \__fp_parse_operand:Nw \c__fp_prec_func_int \__fp_parse_expand:w
18233 }
18234 \cs_new:Npn \__fp_parse_function:NNN #1#2#3
18235 {
18236   \exp_after:wN \__fp_parse_apply_function:NNNwN
18237   \exp_after:wN #3
18238   \exp_after:wN #2
18239   \exp_after:wN #1
18240   \exp:w
18241   \__fp_parse_operand:Nw \c__fp_prec_func_int \__fp_parse_expand:w
18242 }
```

(End definition for `__fp_parse_unary_function:NNN` and `__fp_parse_function:NNN`.)

28.6 Main functions

`__fp_parse:n` Start an `\exp:w` expansion so that `__fp_parse:n` expands in two steps. The `__fp_parse_operand:Nw` function performs computations until reaching an operation with precedence `\c__fp_prec_end_int` or less, namely, the end of the expression. The marker `\s__fp_expr_mark` indicates that the next token is an already parsed version of an infix operator, and `__fp_parse_infix_end:N` has infinitely negative precedence. Finally, clean up a (well-defined) set of extra tokens and stop the initial expansion with `\exp_end:.`

```

18243 \cs_new:Npn \__fp_parse:n #1
18244 {
18245   \exp:w
18246   \exp_after:wN \__fp_parse_after:ww
18247   \exp:w
```

```

18248         \_fp_parse_operand:Nw \c_fp_prec_end_int
18249         \_fp_parse_expand:w #1
18250         \s_fp_expr_mark \_fp_parse_infix_end:N
18251         \s_fp_expr_stop
18252     \exp_end:
18253 }
18254 \cs_new:Npn \_fp_parse_after:ww
18255     #1@ \_fp_parse_infix_end:N \s_fp_expr_stop #2 { #2 #1 }
18256 \cs_new:Npn \_fp_parse_o:n #1
18257 {
18258     \exp:w
18259     \exp_after:wN \_fp_parse_after:ww
18260     \exp:w
18261     \_fp_parse_operand:Nw \c_fp_prec_end_int
18262     \_fp_parse_expand:w #1
18263     \s_fp_expr_mark \_fp_parse_infix_end:N
18264     \s_fp_expr_stop
18265     {
18266         \exp_end_continue_f:w
18267         \_fp_exp_after_any_f:nw { \exp_after:wN \exp_stop_f: }
18268     }
18269 }

```

(End definition for _fp_parse:n, _fp_parse_o:n, and _fp_parse_after:ww.)

_fp_parse_operand:Nw This is just a shorthand which sets up both _fp_parse_continue:NwN and _fp_parse_one:Nw with the same precedence. Note the trailing \exp:w.

_fp_parse_continue:NwN

```

18270 \cs_new:Npn \_fp_parse_operand:Nw #1
18271 {
18272     \exp_end_continue_f:w
18273     \exp_after:wN \_fp_parse_continue:NwN
18274     \exp_after:wN #1
18275     \exp:w \exp_end_continue_f:w
18276     \exp_after:wN \_fp_parse_one:Nw
18277     \exp_after:wN #1
18278     \exp:w
18279 }
18280 \cs_new:Npn \_fp_parse_continue:NwN #1 #2 @ #3 { #3 #1 #2 @ }

```

(End definition for _fp_parse_operand:Nw and _fp_parse_continue:NwN.)

_fp_parse_apply_binary:NwNwN
_fp_parse_apply_binary_chk:NN
_fp_parse_apply_binary_error:NNN

Receives $\langle precedence \rangle \langle operand_1 \rangle @ \langle operation \rangle \langle operand_2 \rangle @ \langle infix command \rangle$. Builds the appropriate call to the $\langle operation \rangle$ #3, dispatching on both types. If the resulting control sequence does not exist, the operation is not allowed.

This is redefined in l3fp-extras.

```

18281 \cs_new:Npn \_fp_parse_apply_binary:NwNwN #1 #2#3@ #4 #5#6@ #7
18282 {
18283     \exp_after:wN \_fp_parse_continue:NwN
18284     \exp_after:wN #1
18285     \exp:w \exp_end_continue_f:w
18286     \exp_after:wN \_fp_parse_apply_binary_chk:NN
18287     \cs:w
18288         __fp
18289     \_fp_type_from_scan:N #2

```

```

18290         _#4
18291         \__fp_type_from_scan:N #5
18292         _o:ww
18293         \cs_end:
18294         #4
18295         #2#3 #5#6
18296         \exp:w \exp_end_continue_f:w #7 #1
18297     }
18298 \cs_new:Npn \__fp_parse_apply_binary_chk:NN #1#2
18299 {
18300     \if_meaning:w \scan_stop: #1
18301     \__fp_parse_apply_binary_error:NNN #2
18302     \fi:
18303     #1
18304 }
18305 \cs_new:Npn \__fp_parse_apply_binary_error:NNN #1#2#3
18306 {
18307     #2
18308     \__fp_invalid_operation_o:Nww #1
18309 }

```

(End definition for __fp_parse_apply_binary:NwNwN, __fp_parse_apply_binary_chk:NN, and __fp_parse_apply_binary_error:NNN.)

__fp_binary_type_o:Nww Applies the operator #1 to its two arguments, dispatching according to their types, and expands once after the result. The rev version swaps its arguments before doing this.

```

18310 \cs_new:Npn \__fp_binary_type_o:Nww #1 #2#3 ; #4
18311 {
18312     \exp_after:wN \__fp_parse_apply_binary_chk:NN
18313     \cs:w
18314     __fp
18315     \__fp_type_from_scan:N #2
18316     _ #1
18317     \__fp_type_from_scan:N #4
18318     _o:ww
18319     \cs_end:
18320     #1
18321     #2 #3 ; #4
18322 }
18323 \cs_new:Npn \__fp_binary_rev_type_o:Nww #1 #2#3 ; #4#5 ;
18324 {
18325     \exp_after:wN \__fp_parse_apply_binary_chk:NN
18326     \cs:w
18327     __fp
18328     \__fp_type_from_scan:N #4
18329     _ #1
18330     \__fp_type_from_scan:N #2
18331     _o:ww
18332     \cs_end:
18333     #1
18334     #4 #5 ; #2 #3 ;
18335 }

```

(End definition for __fp_binary_type_o:Nww and __fp_binary_rev_type_o:Nww.)

28.7 Infix operators

_fp_parse_infix_after_operand:NwN

```

18336 \cs_new:Npn \_fp_parse_infix_after_operand:NwN #1 #2;
18337 {
18338   \_fp_exp_after_f:nw { \_fp_parse_infix:NN #1 }
18339   #2;
18340 }
18341 \cs_new:Npn \_fp_parse_infix:NN #1 #2
18342 {
18343   \if_catcode:w \scan_stop: \exp_not:N #2
18344   \if_int_compare:w
18345     \_fp_str_if_eq:nn { \s__fp_expr_mark } { \exp_not:N #2 }
18346     = 0 \exp_stop_f:
18347     \exp_after:wN \exp_after:wN
18348     \exp_after:wN \_fp_parse_infix_mark:NNN
18349   \else:
18350     \exp_after:wN \exp_after:wN
18351     \exp_after:wN \_fp_parse_infix_juxt:N
18352   \fi:
18353 \else:
18354   \if_int_compare:w
18355     \_fp_int_eval:w
18356     ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
18357     = 3 \exp_stop_f:
18358     \exp_after:wN \exp_after:wN
18359     \exp_after:wN \_fp_parse_infix_juxt:N
18360   \else:
18361     \exp_after:wN \_fp_parse_infix_check:NNN
18362     \cs:w
18363     __fp_parse_infix_ \token_to_str:N #2 :N
18364     \exp_after:wN \exp_after:wN \exp_after:wN
18365     \cs_end:
18366   \fi:
18367 \fi:
18368 #1
18369 #2
18370 }
18371 \cs_new:Npn \_fp_parse_infix_check:NNN #1#2#3
18372 {
18373   \if_meaning:w \scan_stop: #1
18374     \__kernel_msg_expandable_error:nnn
18375     { kernel } { fp-missing } { * }
18376     \exp_after:wN \_fp_parse_infix_mul:N
18377     \exp_after:wN #2
18378     \exp_after:wN #3
18379   \else:
18380     \exp_after:wN #1
18381     \exp_after:wN #2
18382     \exp:w \exp_after:wN \_fp_parse_expand:w
18383   \fi:
18384 }
```

(End definition for _fp_parse_infix_after_operand:NwN.)

`_fp_parse_infix_after_paren:NN` Variant of `_fp_parse_infix:NN` for use after a closing parenthesis. The only difference is that `_fp_parse_infix_juxt:N` is replaced by `_fp_parse_infix_mul:N`.

```

18385 \cs_new:Npn \_fp_parse_infix_after_paren:NN #1 #2
18386 {
18387   \if_catcode:w \scan_stop: \exp_not:N #2
18388   \if_int_compare:w
18389     \_fp_str_if_eq:nn { \s_fp_expr_mark } { \exp_not:N #2 }
18390     = 0 \exp_stop_f:
18391     \exp_after:wN \exp_after:wN
18392     \exp_after:wN \_fp_parse_infix_mark:NNN
18393   \else:
18394     \exp_after:wN \exp_after:wN
18395     \exp_after:wN \_fp_parse_infix_mul:N
18396   \fi:
18397 \else:
18398   \if_int_compare:w
18399     \_fp_int_eval:w
18400     ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
18401     = 3 \exp_stop_f:
18402     \exp_after:wN \exp_after:wN
18403     \exp_after:wN \_fp_parse_infix_mul:N
18404   \else:
18405     \exp_after:wN \_fp_parse_infix_check:NNN
18406     \cs:w
18407       \_fp_parse_infix_ \token_to_str:N #2 :N
18408     \exp_after:wN \exp_after:wN \exp_after:wN
18409     \cs_end:
18410   \fi:
18411 \fi:
18412 #1
18413 #2
18414 }
```

(End definition for `_fp_parse_infix_after_paren:NN`.)

28.7.1 Closing parentheses and commas

`_fp_parse_infix_mark:NNN` As an infix operator, `\s_fp_expr_mark` means that the next token (#3) has already gone through `_fp_parse_infix:NN` and should be provided the precedence #1. The scan mark #2 is discarded.

```

18415 \cs_new:Npn \_fp_parse_infix_mark:NNN #1#2#3 { #3 #1 }
```

(End definition for `_fp_parse_infix_mark:NNN`.)

`_fp_parse_infix_end:N` This one is a little bit odd: force every previous operator to end, regardless of the precedence.

```

18416 \cs_new:Npn \_fp_parse_infix_end:N #1
18417 { @ \use_none:n \_fp_parse_infix_end:N }
```

(End definition for `_fp_parse_infix_end:N`.)

`_fp_parse_infix_):N` This is very similar to `_fp_parse_infix_end:N`, complaining about an extra closing parenthesis if the previous operator was the beginning of the expression, with precedence `\c_fp_prec_end_int`.

```

18418 \cs_set_protected:Npn \__fp_tmp:w #1
18419 {
18420   \cs_new:Npn #1 ##1
18421   {
18422     \if_int_compare:w ##1 > \c__fp_prec_end_int
18423     \exp_after:wN @
18424     \exp_after:wN \use_none:n
18425     \exp_after:wN #1
18426   \else:
18427     \__kernel_msg_expandable_error:nnn { kernel } { fp-extra } { ) }
18428     \exp_after:wN \__fp_parse_infix:NN
18429     \exp_after:wN ##1
18430     \exp:w \exp_after:wN \__fp_parse_expand:w
18431   \fi:
18432 }
18433 }
18434 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_):N }

```

(End definition for __fp_parse_infix_):N.)

```

\__fp_parse_infix_,:N
\__fp_parse_infix_comma:w
\__fp_parse_apply_comma:NwNwN

```

As for other infix operations, if the previous operations has higher precedence the comma waits. Otherwise we call __fp_parse_operand:Nw to read more comma-delimited arguments that __fp_parse_infix_comma:w simply concatenates into a @-delimited array. The first comma in a tuple that is not a function argument is distinguished: in that case call __fp_parse_apply_comma:NwNwN whose job is to convert the first item of the tuple and an array of the remaining items into a tuple. In contrast to __fp_parse_apply_binary:NwNwN this function's operands are not single-object arrays.

```

18435 \cs_set_protected:Npn \__fp_tmp:w #1
18436 {
18437   \cs_new:Npn #1 ##1
18438   {
18439     \if_int_compare:w ##1 > \c__fp_prec_comma_int
18440     \exp_after:wN @
18441     \exp_after:wN \use_none:n
18442     \exp_after:wN #1
18443   \else:
18444     \if_int_compare:w ##1 < \c__fp_prec_comma_int
18445     \exp_after:wN @
18446     \exp_after:wN \__fp_parse_apply_comma:NwNwN
18447     \exp_after:wN ,
18448     \exp:w
18449   \else:
18450     \exp_after:wN \__fp_parse_infix_comma:w
18451     \exp:w
18452   \fi:
18453   \__fp_parse_operand:Nw \c__fp_prec_comma_int
18454   \exp_after:wN \__fp_parse_expand:w
18455   \fi:
18456 }
18457 }
18458 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_,:N }
18459 \cs_new:Npn \__fp_parse_infix_comma:w #1 @
18460 { #1 @ \use_none:n }
18461 \cs_new:Npn \__fp_parse_apply_comma:NwNwN #1 #2@ #3 #4@ #5

```

```

18462 {
18463   \exp_after:wN \__fp_parse_continue:NwN
18464   \exp_after:wN #1
18465   \exp:w \exp_end_continue_f:w
18466   \__fp_exp_after_tuple_f:nw { }
18467   \s__fp_tuple \__fp_tuple_chk:w { #2 #4 } ;
18468   #5 #1
18469 }

```

(End definition for __fp_parse_infix_::N, __fp_parse_infix_comma:w, and __fp_parse_apply_comma:NwNwN.)

28.7.2 Usual infix operators

As described in the “work plan”, each infix operator has an associated \...infix... function, a computing function, and precedence, given as arguments to __fp_tmp:w. Using the general mechanism for arithmetic operations. The power operation must be associative in the opposite order from all others. For this, we use two distinct precedences.

```

\__fp_parse_infix_+:N
\__fp_parse_infix_-:N
\__fp_parse_infix_juxt:N
\__fp_parse_infix_/:N
\__fp_parse_infix_mul:N
\__fp_parse_infix_and:N
\__fp_parse_infix_or:N
\__fp_parse_infix_^:N
18470 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
18471 {
18472   \cs_new:Npn #1 ##1
18473   {
18474     \if_int_compare:w ##1 < #3
18475       \exp_after:wN @
18476       \exp_after:wN \__fp_parse_apply_binary:NwNwN
18477       \exp_after:wN #2
18478       \exp:w
18479       \__fp_parse_operand:Nw #4
18480       \exp_after:wN \__fp_parse_expand:w
18481     \else:
18482       \exp_after:wN @
18483       \exp_after:wN \use_none:n
18484       \exp_after:wN #1
18485     \fi:
18486   }
18487 }
18488 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_^:N } ^
18489 \c__fp_prec_hatii_int \c__fp_prec_hat_int
18490 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_juxt:N } *
18491 \c__fp_prec_juxt_int \c__fp_prec_juxt_int
18492 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_/:N } /
18493 \c__fp_prec_times_int \c__fp_prec_times_int
18494 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_mul:N } *
18495 \c__fp_prec_times_int \c__fp_prec_times_int
18496 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_-:N } -
18497 \c__fp_prec_plus_int \c__fp_prec_plus_int
18498 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_+:N } +
18499 \c__fp_prec_plus_int \c__fp_prec_plus_int
18500 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_and:N } &
18501 \c__fp_prec_and_int \c__fp_prec_and_int
18502 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_or:N } |
18503 \c__fp_prec_or_int \c__fp_prec_or_int

```

(End definition for __fp_parse_infix_+:N and others.)

28.7.3 Juxtaposition

`__fp_parse_infix_(:N` When an opening parenthesis appears where we expect an infix operator, we compute the product of the previous operand and the contents of the parentheses using `__fp_parse_infix_mul:N`.

```
18504 \cs_new:cpn { __fp_parse_infix_(:N } #1
18505   { \__fp_parse_infix_mul:N #1 ( }
```

(End definition for `__fp_parse_infix_(:N`.)

28.7.4 Multi-character cases

`__fp_parse_infix_*:N`

```
18506 \cs_set_protected:Npn \__fp_tmp:w #1
18507   {
18508     \cs_new:cpn { __fp_parse_infix_*:N } ##1##2
18509     {
18510       \if:w * \exp_not:N ##2
18511         \exp_after:wN #1
18512         \exp_after:wN ##1
18513       \else:
18514         \exp_after:wN \__fp_parse_infix_mul:N
18515         \exp_after:wN ##1
18516         \exp_after:wN ##2
18517       \fi:
18518     }
18519   }
18520 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix^:N }
```

(End definition for `__fp_parse_infix_*:N`.)

`__fp_parse_infix_|:Nw`

`__fp_parse_infix_&:Nw`

```
18521 \cs_set_protected:Npn \__fp_tmp:w #1#2#3
18522   {
18523     \cs_new:Npn #1 ##1##2
18524     {
18525       \if:w #2 \exp_not:N ##2
18526         \exp_after:wN #1
18527         \exp_after:wN ##1
18528         \exp:w \exp_after:wN \__fp_parse_expand:w
18529       \else:
18530         \exp_after:wN #3
18531         \exp_after:wN ##1
18532         \exp_after:wN ##2
18533       \fi:
18534     }
18535   }
18536 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_|:N } | \__fp_parse_infix_or:N
18537 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_&:N } & \__fp_parse_infix_and:N
```

(End definition for `__fp_parse_infix_|:Nw` and `__fp_parse_infix_&:Nw`.)

28.7.5 Ternary operator

```

__fp_parse_infix?:N
__fp_parse_infix_:N
18538 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
18539 {
18540   \cs_new:Npn #1 ##1
18541   {
18542     \if_int_compare:w ##1 < \c__fp_prec_quest_int
18543     #4
18544     \exp_after:wN @
18545     \exp_after:wN #2
18546     \exp:w
18547     \__fp_parse_operand:Nw #3
18548     \exp_after:wN \__fp_parse_expand:w
18549   \else:
18550     \exp_after:wN @
18551     \exp_after:wN \use_none:n
18552     \exp_after:wN #1
18553   \fi:
18554 }
18555 }
18556 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix?:N }
18557 \__fp_ternary:NwwN \c__fp_prec_quest_int { }
18558 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_:N }
18559 \__fp_ternary_auxii:NwwN \c__fp_prec_colon_int
18560 {
18561   \__kernel_msg_expandable_error:nnnn
18562   { kernel } { fp-missing } { ? } { ~for~?: }
18563 }

```

(End definition for __fp_parse_infix?:N and __fp_parse_infix_:N.)

28.7.6 Comparisons

```

__fp_parse_infix<:N
__fp_parse_infix=:N
__fp_parse_infix>:N
__fp_parse_infix!:N
__fp_parse_excl_error:
__fp_parse_compare:NNNNNNN
  __fp_parse_compare_auxi:NNNNNNN
  __fp_parse_compare_auxii:NNNNN
  __fp_parse_compare_end:NNNNw
  __fp_compare:wNNNNw
18564 \cs_new:cpn { __fp_parse_infix<:N } #1
18565 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 < }
18566 \cs_new:cpn { __fp_parse_infix=:N } #1
18567 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 = }
18568 \cs_new:cpn { __fp_parse_infix>:N } #1
18569 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 > }
18570 \cs_new:cpn { __fp_parse_infix!:N } #1
18571 {
18572   \exp_after:wN \__fp_parse_compare:NNNNNNN
18573   \exp_after:wN #1
18574   \exp_after:wN 0
18575   \exp_after:wN 1
18576   \exp_after:wN 1
18577   \exp_after:wN 1
18578   \exp_after:wN 1
18579 }
18580 \cs_new:Npn \__fp_parse_excl_error:
18581 {
18582   \__kernel_msg_expandable_error:nnnn

```

```

18583         { kernel } { fp-missing } { = } { ~after~!. }
18584     }
18585     \cs_new:Npn \__fp_parse_compare:NNNNNNN #1
18586     {
18587         \if_int_compare:w #1 < \c__fp_prec_comp_int
18588             \exp_after:wN \__fp_parse_compare_auxi:NNNNNNN
18589             \exp_after:wN \__fp_parse_excl_error:
18590         \else:
18591             \exp_after:wN @
18592             \exp_after:wN \use_none:n
18593             \exp_after:wN \__fp_parse_compare:NNNNNNN
18594         \fi:
18595     }
18596     \cs_new:Npn \__fp_parse_compare_auxi:NNNNNNN #1#2#3#4#5#6#7
18597     {
18598         \if_case:w
18599             \__fp_int_eval:w \exp_after:wN ' \token_to_str:N #7 - '<
18600             \__fp_int_eval_end:
18601             \__fp_parse_compare_auxii:NNNNN #2#2#4#5#6
18602         \or: \__fp_parse_compare_auxii:NNNNN #2#3#2#5#6
18603         \or: \__fp_parse_compare_auxii:NNNNN #2#3#4#2#6
18604         \or: \__fp_parse_compare_auxii:NNNNN #2#3#4#5#2
18605         \else: #1 \__fp_parse_compare_end:NNNNw #3#4#5#6#7
18606         \fi:
18607     }
18608     \cs_new:Npn \__fp_parse_compare_auxii:NNNNN #1#2#3#4#5
18609     {
18610         \exp_after:wN \__fp_parse_compare_auxi:NNNNNNN
18611         \exp_after:wN \prg_do_nothing:
18612         \exp_after:wN #1
18613         \exp_after:wN #2
18614         \exp_after:wN #3
18615         \exp_after:wN #4
18616         \exp_after:wN #5
18617         \exp:w \exp_after:wN \__fp_parse_expand:w
18618     }
18619     \cs_new:Npn \__fp_parse_compare_end:NNNNw #1#2#3#4#5 \fi:
18620     {
18621         \fi:
18622         \exp_after:wN @
18623         \exp_after:wN \__fp_parse_apply_compare:NwNNNNNNwN
18624         \exp_after:wN \c_one_fp
18625         \exp_after:wN #1
18626         \exp_after:wN #2
18627         \exp_after:wN #3
18628         \exp_after:wN #4
18629         \exp:w
18630         \__fp_parse_operand:Nw \c__fp_prec_comp_int \__fp_parse_expand:w #5
18631     }
18632     \cs_new:Npn \__fp_parse_apply_compare:NwNNNNNNwN
18633     #1 #2@ #3 #4#5#6#7 #8@ #9
18634     {
18635         \if_int_odd:w
18636             \if_meaning:w \c_zero_fp #3

```

```

18637         0
18638     \else:
18639         \if_case:w \__fp_compare_back_any:ww #8 #2 \exp_stop_f:
18640             #5 \or: #6 \or: #7 \else: #4
18641         \fi:
18642     \fi:
18643     \exp_stop_f:
18644     \exp_after:wN \__fp_parse_apply_compare_aux:NNwN
18645     \exp_after:wN \c_one_fp
18646 \else:
18647     \exp_after:wN \__fp_parse_apply_compare_aux:NNwN
18648     \exp_after:wN \c_zero_fp
18649 \fi:
18650 #1 #8 #9
18651 }
18652 \cs_new:Npn \__fp_parse_apply_compare_aux:NNwN #1 #2 #3; #4
18653 {
18654     \if_meaning:w \__fp_parse_compare:NNNNNNN #4
18655         \exp_after:wN \__fp_parse_continue_compare:NNwNN
18656         \exp_after:wN #1
18657         \exp_after:wN #2
18658         \exp:w \exp_end_continue_f:w
18659         \__fp_exp_after_o:w #3;
18660         \exp:w \exp_end_continue_f:w
18661     \else:
18662         \exp_after:wN \__fp_parse_continue:NwN
18663         \exp_after:wN #2
18664         \exp:w \exp_end_continue_f:w
18665         \exp_after:wN #1
18666         \exp:w \exp_end_continue_f:w
18667     \fi:
18668     #4 #2
18669 }
18670 \cs_new:Npn \__fp_parse_continue_compare:NNwNN #1#2 #3@ #4#5
18671 { #4 #2 #3@ #1 }

```

(End definition for __fp_parse_infix_<:N and others.)

28.8 Tools for functions

__fp_parse_function_all_fp_o:fnw Followed by {<function name>} {<code>} <float array> @ this checks all floats are floating point numbers (no tuples).

```

18672 \cs_new:Npn \__fp_parse_function_all_fp_o:fnw #1#2#3 @
18673 {
18674     \__fp_array_if_all_fp:nTF {#3}
18675     { #2 #3 @ }
18676     {
18677         \__fp_error:nffn { fp-bad-args }
18678         {#1}
18679         { \fp_to_tl:n { \s__fp_tuple \__fp_tuple_chk:w {#3} ; } }
18680         { }
18681         \exp_after:wN \c_nan_fp
18682     }
18683 }

```

(End definition for `_fp_parse_function_all_fp_o:fnw`.)

`_fp_parse_function_one_two:nnw` This is followed by `{(function name)}{(code)}{float array} @`. It checks that the `(float array)` consists of one or two floating point numbers (not tuples), then leaves the `(code)` (if there is one float) or its tail (if there are two floats) followed by the `(float array)`. The `(code)` should start with a single token such as `_fp_atan_default:w` that deals with the single-float case.

The first `_fp_if_type_fp:NTwFw` test catches the case of no argument and the case of a tuple argument. The next one distinguishes the case of a single argument (no error, just add `\c_one_fp`) from a tuple second argument. Finally check there is no further argument.

```

18684 \cs_new:Npn \_fp_parse_function_one_two:nnw #1#2#3
18685   {
18686     \_fp_if_type_fp:NTwFw
18687     #3 { } \s__fp \_fp_parse_function_one_two_error_o:w \s__fp_stop
18688     \_fp_parse_function_one_two_aux:nnw {#1} {#2} #3
18689   }
18690 \cs_new:Npn \_fp_parse_function_one_two_error_o:w #1#2#3#4 @
18691   {
18692     \_fp_error:nffn { fp-bad-args }
18693     {#2}
18694     { \fp_to_tl:n { \s__fp_tuple \_fp_tuple_chk:w {#4} ; } }
18695     { }
18696     \exp_after:wN \c_nan_fp
18697   }
18698 \cs_new:Npn \_fp_parse_function_one_two_aux:nnw #1#2 #3; #4
18699   {
18700     \_fp_if_type_fp:NTwFw
18701     #4 { }
18702     \s__fp
18703     {
18704       \if_meaning:w @ #4
18705       \exp_after:wN \use_iv:nnnn
18706       \fi:
18707       \_fp_parse_function_one_two_error_o:w
18708     }
18709     \s__fp_stop
18710     \_fp_parse_function_one_two_auxii:nnw {#1} {#2} #3; #4
18711   }
18712 \cs_new:Npn \_fp_parse_function_one_two_auxii:nnw #1#2#3; #4; #5
18713   {
18714     \if_meaning:w @ #5 \else:
18715     \exp_after:wN \_fp_parse_function_one_two_error_o:w
18716     \fi:
18717     \use_ii:nn {#1} { \use_none:n #2 } #3; #4; #5
18718   }

```

(End definition for `_fp_parse_function_one_two:nnw` and others.)

`_fp_tuple_map_o:nw` Apply #1 to all items in the following tuple and expand once afterwards. The code #1 should itself expand once after its result.

```

18719 \cs_new:Npn \_fp_tuple_map_o:nw #1 \s__fp_tuple \_fp_tuple_chk:w #2 ;
18720   {

```



```

18721 \exp_after:wN \s__fp_tuple
18722 \exp_after:wN \__fp_tuple_chk:w
18723 \exp_after:wN {
18724   \exp:w \exp_end_continue_f:w
18725   \__fp_tuple_map_loop_o:nw {#1} #2
18726   { \s__fp \prg_break: } ;
18727   \prg_break_point:
18728   \exp_after:wN } \exp_after:wN ;
18729 }
18730 \cs_new:Npn \__fp_tuple_map_loop_o:nw #1#2#3 ;
18731 {
18732   \use_none:n #2
18733   #1 #2 #3 ;
18734   \exp:w \exp_end_continue_f:w
18735   \__fp_tuple_map_loop_o:nw {#1}
18736 }

```

(End definition for __fp_tuple_map_o:nw and __fp_tuple_map_loop_o:nw.)

__fp_tuple_mapthread_o:nww Apply #1 to pairs of items in the two following tuples and expand once afterwards.

```

\__fp_tuple_mapthread_loop_o:nw
18737 \cs_new:Npn \__fp_tuple_mapthread_o:nww #1
18738   \s__fp_tuple \__fp_tuple_chk:w #2 ;
18739   \s__fp_tuple \__fp_tuple_chk:w #3 ;
18740 {
18741   \exp_after:wN \s__fp_tuple
18742   \exp_after:wN \__fp_tuple_chk:w
18743   \exp_after:wN {
18744     \exp:w \exp_end_continue_f:w
18745     \__fp_tuple_mapthread_loop_o:nw {#1}
18746     #2 { \s__fp \prg_break: } ; @
18747     #3 { \s__fp \prg_break: } ;
18748     \prg_break_point:
18749     \exp_after:wN } \exp_after:wN ;
18750 }
18751 \cs_new:Npn \__fp_tuple_mapthread_loop_o:nw #1#2#3 ; #4 @ #5#6 ;
18752 {
18753   \use_none:n #2
18754   \use_none:n #5
18755   #1 #2 #3 ; #5 #6 ;
18756   \exp:w \exp_end_continue_f:w
18757   \__fp_tuple_mapthread_loop_o:nw {#1} #4 @
18758 }

```

(End definition for __fp_tuple_mapthread_o:nww and __fp_tuple_mapthread_loop_o:nw.)

28.9 Messages

```

18759 \__kernel_msg_new:nnn { kernel } { fp-deprecated }
18760 { '#1'~deprecated;~use~'#2' }
18761 \__kernel_msg_new:nnn { kernel } { unknown-fp-word }
18762 { Unknown~fp~word~#1. }
18763 \__kernel_msg_new:nnn { kernel } { fp-missing }
18764 { Missing~#1~inserted #2. }
18765 \__kernel_msg_new:nnn { kernel } { fp-extra }
18766 { Extra~#1~ignored. }

```

```

18767 \__kernel_msg_new:nnn { kernel } { fp-early-end }
18768 { Premature-end-in-fp-expression. }
18769 \__kernel_msg_new:nnn { kernel } { fp-after-e }
18770 { Cannot~use~#1 after~'e'. }
18771 \__kernel_msg_new:nnn { kernel } { fp-missing-number }
18772 { Missing-number~before~'#1'. }
18773 \__kernel_msg_new:nnn { kernel } { fp-unknown-symbol }
18774 { Unknown-symbol~#1~ignored. }
18775 \__kernel_msg_new:nnn { kernel } { fp-extra-comma }
18776 { Unexpected~comma~turned~to~nan~result. }
18777 \__kernel_msg_new:nnn { kernel } { fp-no-arg }
18778 { #1~got~no~argument;~used~nan. }
18779 \__kernel_msg_new:nnn { kernel } { fp-multi-arg }
18780 { #1~got~more~than~one~argument;~used~nan. }
18781 \__kernel_msg_new:nnn { kernel } { fp-num-args }
18782 { #1~expects~between~#2~and~#3~arguments. }
18783 \__kernel_msg_new:nnn { kernel } { fp-bad-args }
18784 { Arguments~in~#1#2~are~invalid. }
18785 \__kernel_msg_new:nnn { kernel } { fp-infty-pi }
18786 { Math~command~#1 is~not~an~fp }
18787 (*package)
18788 \cs_if_exist:cT { @unexpandable@protect }
18789 {
18790   \__kernel_msg_new:nnn { kernel } { fp-robust-cmd }
18791   { Robust~command~#1 invalid-in-fp-expression! }
18792 }
18793 </package>
18794 </initex | package>

```

29 l3fp-assign implementation

```

18795 (*initex | package)
18796 <@@=fp>

```

29.1 Assigning values

\fp_new:N Floating point variables are initialized to be +0.

```

18797 \cs_new_protected:Npn \fp_new:N #1
18798 { \cs_new_eq:NN #1 \c_zero_fp }
18799 \cs_generate_variant:Nn \fp_new:N {c}

```

(End definition for \fp_new:N. This function is documented on page 199.)

\fp_set:Nn Simply use __fp_parse:n within various f-expanding assignments.

```

18800 \cs_new_protected:Npn \fp_set:Nn #1#2
18801 { \tl_set:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
\fp_gset:Nn 18802 \cs_new_protected:Npn \fp_gset:Nn #1#2
18803 { \tl_gset:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
\fp_const:Nn 18804 \cs_new_protected:Npn \fp_const:Nn #1#2
18805 { \tl_const:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
18806 \cs_generate_variant:Nn \fp_set:Nn {c}
18807 \cs_generate_variant:Nn \fp_gset:Nn {c}
18808 \cs_generate_variant:Nn \fp_const:Nn {c}

```

(End definition for `\fp_set:Nn`, `\fp_gset:Nn`, and `\fp_const:Nn`. These functions are documented on page 200.)

`\fp_set_eq:NN` Copying a floating point is the same as copying the underlying token list.
`\fp_set_eq:cN` 18809 `\cs_new_eq:NN \fp_set_eq:NN \tl_set_eq:NN`
`\fp_set_eq:Nc` 18810 `\cs_new_eq:NN \fp_gset_eq:NN \tl_gset_eq:NN`
`\fp_set_eq:cc` 18811 `\cs_generate_variant:Nn \fp_set_eq:NN { c , Nc , cc }`
`\fp_gset_eq:NN` 18812 `\cs_generate_variant:Nn \fp_gset_eq:NN { c , Nc , cc }`
`\fp_gset_eq:cN`
`\fp_gset_eq:Nc` (End definition for `\fp_set_eq:NN` and `\fp_gset_eq:NN`. These functions are documented on page 200.)
`\fp_gset_eq:cc`
`\fp_zero:N` Setting a floating point to zero: copy `\c_zero_fp`.

`\fp_zero:c` 18813 `\cs_new_protected:Npn \fp_zero:N #1 { \fp_set_eq:NN #1 \c_zero_fp }`
`\fp_gzero:N` 18814 `\cs_new_protected:Npn \fp_gzero:N #1 { \fp_gset_eq:NN #1 \c_zero_fp }`
`\fp_gzero:c` 18815 `\cs_generate_variant:Nn \fp_zero:N { c }`
18816 `\cs_generate_variant:Nn \fp_gzero:N { c }`

(End definition for `\fp_zero:N` and `\fp_gzero:N`. These functions are documented on page 199.)

`\fp_zero_new:N` Set the floating point to zero, or define it if needed.
`\fp_zero_new:c` 18817 `\cs_new_protected:Npn \fp_zero_new:N #1`
`\fp_gzero_new:N` 18818 `{ \fp_if_exist:NTF #1 { \fp_zero:N #1 } { \fp_new:N #1 } }`
`\fp_gzero_new:c` 18819 `\cs_new_protected:Npn \fp_gzero_new:N #1`
18820 `{ \fp_if_exist:NTF #1 { \fp_gzero:N #1 } { \fp_new:N #1 } }`
18821 `\cs_generate_variant:Nn \fp_zero_new:N { c }`
18822 `\cs_generate_variant:Nn \fp_gzero_new:N { c }`

(End definition for `\fp_zero_new:N` and `\fp_gzero_new:N`. These functions are documented on page 200.)

29.2 Updating values

These match the equivalent functions in `l3int` and `l3skip`.

`\fp_add:Nn` For the sake of error recovery we should not simply set `#1` to `#1 ± (#2)`: for instance, if `#2`
`\fp_add:cN` is 0)+2, the parsing error would be raised at the last closing parenthesis rather than at
`\fp_gadd:Nn` the closing parenthesis in the user argument. Thus we evaluate `#2` instead of just putting
`\fp_gadd:cN` parentheses. As an optimization we use `__fp_parse:n` rather than `\fp_eval:n`, which
`\fp_sub:Nn` would convert the result away from the internal representation and back.
`\fp_sub:cN` 18823 `\cs_new_protected:Npn \fp_add:Nn { __fp_add:NNNn \fp_set:Nn + }`
`\fp_gsub:Nn` 18824 `\cs_new_protected:Npn \fp_gadd:Nn { __fp_add:NNNn \fp_gset:Nn + }`
`\fp_gsub:cN` 18825 `\cs_new_protected:Npn \fp_sub:Nn { __fp_add:NNNn \fp_set:Nn - }`
`__fp_add:NNNn` 18826 `\cs_new_protected:Npn \fp_gsub:Nn { __fp_add:NNNn \fp_gset:Nn - }`
18827 `\cs_new_protected:Npn __fp_add:NNNn #1#2#3#4`
18828 `{ #1 #3 { #3 #2 __fp_parse:n {#4} } }`
18829 `\cs_generate_variant:Nn \fp_add:Nn { c }`
18830 `\cs_generate_variant:Nn \fp_gadd:Nn { c }`
18831 `\cs_generate_variant:Nn \fp_sub:Nn { c }`
18832 `\cs_generate_variant:Nn \fp_gsub:Nn { c }`

(End definition for `\fp_add:Nn` and others. These functions are documented on page 200.)

29.3 Showing values

`\fp_show:N` This shows the result of computing its argument by passing the right data to `\tl_show:n` or `\tl_log:n`.

`\fp_show:c`

`\fp_log:N` 18833 `\cs_new_protected:Npn \fp_show:N { __fp_show:NN \tl_show:n }`

`\fp_log:c` 18834 `\cs_generate_variant:Nn \fp_show:N { c }`

`__fp_show:NN` 18835 `\cs_new_protected:Npn \fp_log:N { __fp_show:NN \tl_log:n }`

18836 `\cs_generate_variant:Nn \fp_log:N { c }`

18837 `\cs_new_protected:Npn __fp_show:NN #1#2`

18838 `{`

18839 `__kernel_chk_defined:NT #2`

18840 `{ \exp_args:Nx #1 { \token_to_str:N #2 = \fp_to_tl:N #2 } }`

18841 `}`

(End definition for `\fp_show:N`, `\fp_log:N`, and `__fp_show:NN`. These functions are documented on page 207.)

`\fp_show:n` Use general tools.

`\fp_log:n` 18842 `\cs_new_protected:Npn \fp_show:n`

18843 `{ \msg_show_eval:Nn \fp_to_tl:n }`

18844 `\cs_new_protected:Npn \fp_log:n`

18845 `{ \msg_log_eval:Nn \fp_to_tl:n }`

(End definition for `\fp_show:n` and `\fp_log:n`. These functions are documented on page 207.)

29.4 Some useful constants and scratch variables

`\c_one_fp` Some constants.

`\c_e_fp` 18846 `\fp_const:Nn \c_e_fp { 2.718 2818 2845 9045 }`

18847 `\fp_const:Nn \c_one_fp { 1 }`

(End definition for `\c_one_fp` and `\c_e_fp`. These variables are documented on page 205.)

`\c_pi_fp` We simply round π to and $\pi/180$ to 16 significant digits.

`\c_one_degree_fp` 18848 `\fp_const:Nn \c_pi_fp { 3.141 5926 5358 9793 }`

18849 `\fp_const:Nn \c_one_degree_fp { 0.0 1745 3292 5199 4330 }`

(End definition for `\c_pi_fp` and `\c_one_degree_fp`. These variables are documented on page 206.)

`\l_tmpa_fp` Scratch variables are simply initialized there.

`\l_tmpb_fp` 18850 `\fp_new:N \l_tmpa_fp`

`\g_tmpa_fp` 18851 `\fp_new:N \l_tmpb_fp`

`\g_tmpb_fp` 18852 `\fp_new:N \g_tmpa_fp`

18853 `\fp_new:N \g_tmpb_fp`

(End definition for `\l_tmpa_fp` and others. These variables are documented on page 206.)

18854 `</initex | package>`

30 l3fp-logic Implementation

18855 $\langle *initex | package \rangle$

18856 $\langle @@=fp \rangle$

$\backslash_fp_parse_word_max:N$
 $\backslash_fp_parse_word_min:N$

Those functions may receive a variable number of arguments.

18857 $\backslash cs_new:Npn \backslash_fp_parse_word_max:N$
 18858 $\{ \backslash_fp_parse_function:NNN \backslash_fp_minmax_o:Nw 2 \}$
 18859 $\backslash cs_new:Npn \backslash_fp_parse_word_min:N$
 18860 $\{ \backslash_fp_parse_function:NNN \backslash_fp_minmax_o:Nw 0 \}$

(End definition for $\backslash_fp_parse_word_max:N$ and $\backslash_fp_parse_word_min:N$.)

30.1 Syntax of internal functions

- $\backslash_fp_compare_npos:nwnw \{ \langle expo_1 \rangle \} \langle body_1 \rangle ; \{ \langle expo_2 \rangle \} \langle body_2 \rangle ;$
- $\backslash_fp_minmax_o:Nw \langle sign \rangle \langle floating\ point\ array \rangle$
- $\backslash_fp_not_o:w ? \langle floating\ point\ array \rangle$ (with one floating point number only)
- $\backslash_fp_ \& _o:ww \langle floating\ point \rangle \langle floating\ point \rangle$
- $\backslash_fp_ | _o:ww \langle floating\ point \rangle \langle floating\ point \rangle$
- $\backslash_fp_ternary:NwwN, \backslash_fp_ternary_auxi:NwwN, \backslash_fp_ternary_auxii:NwwN$ have to be understood.

30.2 Tests

$\backslash fp_if_exist_p:N$
 $\backslash fp_if_exist_p:c$
 $\backslash fp_if_exist:N \underline{TF}$
 $\backslash fp_if_exist:c \underline{TF}$

Copies of the cs functions defined in l3basics.

18861 $\backslash prg_new_eq_conditional:NNn \backslash fp_if_exist:N \backslash cs_if_exist:N \{ TF , T , F , p \}$
 18862 $\backslash prg_new_eq_conditional:NNn \backslash fp_if_exist:c \backslash cs_if_exist:c \{ TF , T , F , p \}$

(End definition for $\backslash fp_if_exist:N \underline{TF}$. This function is documented on page 202.)

$\backslash fp_if_nan_p:n$
 $\backslash fp_if_nan:n \underline{TF}$

Evaluate and check if the result is a floating point of the same kind as NaN.

18863 $\backslash prg_new_conditional:Npnn \backslash fp_if_nan:n \#1 \{ TF , T , F , p \}$
 18864 $\{$
 18865 $\quad \backslash if:w 3 \backslash exp_last_unbraced:Nf \backslash_fp_kind:w \{ \backslash_fp_parse:n \{ \#1 \} \}$
 18866 $\quad \backslash prg_return_true:$
 18867 $\quad \backslash else:$
 18868 $\quad \backslash prg_return_false:$
 18869 $\quad \backslash fi:$
 18870 $\}$

(End definition for $\backslash fp_if_nan:n \underline{TF}$. This function is documented on page 261.)

30.3 Comparison

`\fp_compare_p:n` Within floating point expressions, comparison operators are treated as operations, so we evaluate #1, then compare with ± 0 . Tuples are true.

`\fp_compare:nTF`

`__fp_compare_return:w`

```

18871 \prg_new_conditional:Npnn \fp_compare:n #1 { p , T , F , TF }
18872 {
18873   \exp_after:wN \__fp_compare_return:w
18874   \exp:w \exp_end_continue_f:w \__fp_parse:n {#1}
18875 }
18876 \cs_new:Npn \__fp_compare_return:w #1#2#3;
18877 {
18878   \if_charcode:w 0
18879     \__fp_if_type_fp:NTwFw
18880     #1 { \__fp_use_i_delimit_by_s_stop:nw #3 \s__fp_stop }
18881     \s__fp 1 \s__fp_stop
18882     \prg_return_false:
18883   \else:
18884     \prg_return_true:
18885   \fi:
18886 }
```

(End definition for `\fp_compare:nTF` and `__fp_compare_return:w`. This function is documented on page 203.)

`\fp_compare_p:nNn`

`\fp_compare:nNnTF`

`__fp_compare_aux:wn`

Evaluate #1 and #3, using an auxiliary to expand both, and feed the two floating point numbers swapped to `__fp_compare_back_any:ww`, defined below. Compare the result with '`#2-'`', which is -1 for $<$, 0 for $=$, 1 for $>$ and 2 for $?$.

```

18887 \prg_new_conditional:Npnn \fp_compare:nNn #1#2#3 { p , T , F , TF }
18888 {
18889   \if_int_compare:w
18890     \exp_after:wN \__fp_compare_aux:wn
18891     \exp:w \exp_end_continue_f:w \__fp_parse:n {#1} {#3}
18892     = \__fp_int_eval:w '#2 - '=' \__fp_int_eval_end:
18893     \prg_return_true:
18894   \else:
18895     \prg_return_false:
18896   \fi:
18897 }
18898 \cs_new:Npn \__fp_compare_aux:wn #1; #2
18899 {
18900   \exp_after:wN \__fp_compare_back_any:ww
18901   \exp:w \exp_end_continue_f:w \__fp_parse:n {#2} #1;
18902 }
```

(End definition for `\fp_compare:nNnTF` and `__fp_compare_aux:wn`. This function is documented on page 202.)

`__fp_compare_back_any:ww`

`__fp_compare_back:ww`

`__fp_compare_nan:w`

`__fp_compare_back_any:ww` $\langle y \rangle$; $\langle x \rangle$;

Expands (in the same way as `\int_eval:n`) to -1 if $x < y$, 0 if $x = y$, 1 if $x > y$, and 2 otherwise (denoted as $x?y$). If either operand is `nan`, stop the comparison with `__fp_compare_nan:w` returning 2 . If x is negative, swap the outputs 1 and -1 (i.e., $>$ and $<$); we can henceforth assume that $x \geq 0$. If $y \geq 0$, and they have the same type, either they are normal and we compare them with `__fp_compare_npos:wnnw`, or they

are equal. If $y \geq 0$, but of a different type, the highest type is a larger number. Finally, if $y \leq 0$, then $x > y$, unless both are zero.

```

18903 \cs_new:Npn \__fp_compare_back_any:ww #1#2; #3
18904 {
18905   \__fp_if_type_fp:NTwFw
18906   #1 { \__fp_if_type_fp:NTwFw #3 \use_i:nn \s__fp \use_ii:nn \s__fp_stop }
18907   \s__fp \use_ii:nn \s__fp_stop
18908   \__fp_compare_back:ww
18909   {
18910     \cs:w
18911     __fp
18912     \__fp_type_from_scan:N #1
18913     _compare_back
18914     \__fp_type_from_scan:N #3
18915     :ww
18916     \cs_end:
18917   }
18918   #1#2 ; #3
18919 }
18920 \cs_new:Npn \__fp_compare_back:ww
18921   \s__fp \__fp_chk:w #1 #2 #3;
18922   \s__fp \__fp_chk:w #4 #5 #6;
18923 {
18924   \int_value:w
18925   \if_meaning:w 3 #1 \exp_after:wN \__fp_compare_nan:w \fi:
18926   \if_meaning:w 3 #4 \exp_after:wN \__fp_compare_nan:w \fi:
18927   \if_meaning:w 2 #5 - \fi:
18928   \if_meaning:w #2 #5
18929   \if_meaning:w #1 #4
18930   \if_meaning:w 1 #1
18931   \__fp_compare_npos:nwnw #6; #3;
18932   \else:
18933     0
18934   \fi:
18935   \else:
18936     \if_int_compare:w #4 < #1 - \fi: 1
18937   \fi:
18938   \else:
18939     \if_int_compare:w #1#4 = 0 \exp_stop_f:
18940     0
18941   \else:
18942     1
18943   \fi:
18944   \fi:
18945   \exp_stop_f:
18946 }
18947 \cs_new:Npn \__fp_compare_nan:w #1 \fi: \exp_stop_f: { 2 \exp_stop_f: }

```

(End definition for __fp_compare_back_any:ww, __fp_compare_back:ww, and __fp_compare_nan:w.)

__fp_compare_back_tuple:ww Tuple and floating point numbers are not comparable so return 2 in mixed cases or
 __fp_tuple_compare_back:ww when tuples have a different number of items. Otherwise compare pairs of items with
 __fp_tuple_compare_back_tuple:ww __fp_compare_back_any:ww and if any don't match return 2 (as \int_value:w 02
 __fp_tuple_compare_back_loop:w \exp_stop_f:).

```

18948 \cs_new:Npn \__fp_compare_back_tuple:ww #1; #2; { 2 }
18949 \cs_new:Npn \__fp_tuple_compare_back:ww #1; #2; { 2 }
18950 \cs_new:Npn \__fp_tuple_compare_back_tuple:ww
18951   \s__fp_tuple \__fp_tuple_chk:w #1;
18952   \s__fp_tuple \__fp_tuple_chk:w #2;
18953   {
18954     \int_compare:nNnTF { \__fp_array_count:n {#1} } =
18955       { \__fp_array_count:n {#2} }
18956       {
18957         \int_value:w 0
18958         \__fp_tuple_compare_back_loop:w
18959           #1 { \s__fp \prg_break: } ; @
18960           #2 { \s__fp \prg_break: } ;
18961         \prg_break_point:
18962         \exp_stop_f:
18963       }
18964       { 2 }
18965   }
18966 \cs_new:Npn \__fp_tuple_compare_back_loop:w #1#2 ; #3 @ #4#5 ;
18967 {
18968   \use_none:n #1
18969   \use_none:n #4
18970   \if_int_compare:w
18971     \__fp_compare_back_any:ww #1 #2 ; #4 #5 ; = 0 \exp_stop_f:
18972   \else:
18973     2 \exp_after:wN \prg_break:
18974   \fi:
18975   \__fp_tuple_compare_back_loop:w #3 @
18976 }

```

(End definition for __fp_compare_back_tuple:ww and others.)

__fp_compare_npos:nwnw
 __fp_compare_significand:nnnnnnnn

__fp_compare_npos:nwnw {<expo₁>} <body₁> ; {<expo₂>} <body₂> ;
 Within an \int_value:w ... \exp_stop_f: construction, this expands to 0 if the two numbers are equal, -1 if the first is smaller, and 1 if the first is bigger. First compare the exponents: the larger one denotes the larger number. If they are equal, we must compare significands. If both the first 8 digits and the next 8 digits coincide, the numbers are equal. If only the first 8 digits coincide, the next 8 decide. Otherwise, the first 8 digits are compared.

```

18977 \cs_new:Npn \__fp_compare_npos:nwnw #1#2; #3#4;
18978 {
18979   \if_int_compare:w #1 = #3 \exp_stop_f:
18980     \__fp_compare_significand:nnnnnnnn #2 #4
18981   \else:
18982     \if_int_compare:w #1 < #3 - \fi: 1
18983   \fi:
18984 }
18985 \cs_new:Npn \__fp_compare_significand:nnnnnnnn #1#2#3#4#5#6#7#8
18986 {
18987   \if_int_compare:w #1#2 = #5#6 \exp_stop_f:
18988   \if_int_compare:w #3#4 = #7#8 \exp_stop_f:
18989     0
18990   \else:
18991     \if_int_compare:w #3#4 < #7#8 - \fi: 1

```



```

18992     \fi:
18993   \else:
18994     \if_int_compare:w #1#2 < #5#6 - \fi: 1
18995   \fi:
18996 }

```

(End definition for `_fp_compare_npos:nwnw` and `_fp_compare_significand:nnnnnnnn`.)

30.4 Floating point expression loops

`\fp_do_until:nn` These are quite easy given the above functions. The `do_until` and `do_while` versions execute the body, then test. The `until_do` and `while_do` do it the other way round.

```

18997 \cs_new:Npn \fp_do_until:nn #1#2
18998 {
18999   #2
19000   \fp_compare:nF {#1}
19001   { \fp_do_until:nn {#1} {#2} }
19002 }
19003 \cs_new:Npn \fp_do_while:nn #1#2
19004 {
19005   #2
19006   \fp_compare:nT {#1}
19007   { \fp_do_while:nn {#1} {#2} }
19008 }
19009 \cs_new:Npn \fp_until_do:nn #1#2
19010 {
19011   \fp_compare:nF {#1}
19012   {
19013     #2
19014     \fp_until_do:nn {#1} {#2}
19015   }
19016 }
19017 \cs_new:Npn \fp_while_do:nn #1#2
19018 {
19019   \fp_compare:nT {#1}
19020   {
19021     #2
19022     \fp_while_do:nn {#1} {#2}
19023   }
19024 }

```

(End definition for `\fp_do_until:nn` and others. These functions are documented on page 204.)

`\fp_do_until:nNnn` As above but not using the `nNn` syntax.

```

19025 \cs_new:Npn \fp_do_until:nNnn #1#2#3#4
19026 {
19027   #4
19028   \fp_compare:nNnF {#1} #2 {#3}
19029   { \fp_do_until:nNnn {#1} #2 {#3} {#4} }
19030 }
19031 \cs_new:Npn \fp_do_while:nNnn #1#2#3#4
19032 {
19033   #4
19034   \fp_compare:nNnT {#1} #2 {#3}

```

```

19035     { \fp_do_while:nNnn {#1} #2 {#3} {#4} }
19036   }
19037 \cs_new:Npn \fp_until_do:nNnn #1#2#3#4
19038 {
19039   \fp_compare:nNnF {#1} #2 {#3}
19040   {
19041     #4
19042     \fp_until_do:nNnn {#1} #2 {#3} {#4}
19043   }
19044 }
19045 \cs_new:Npn \fp_while_do:nNnn #1#2#3#4
19046 {
19047   \fp_compare:nNnT {#1} #2 {#3}
19048   {
19049     #4
19050     \fp_while_do:nNnn {#1} #2 {#3} {#4}
19051   }
19052 }

```

(End definition for `\fp_do_until:nNnn` and others. These functions are documented on page 203.)

\fp_step_function:nnnN

\fp_step_function:nnnc

`__fp_step:wwwN`

`__fp_step_fp:wwwN`

`__fp_step:NnnnnN`

`__fp_step:NfnnnN`

The approach here is somewhat similar to `\int_step_function:nnnN`. There are two subtleties: we use the internal parser `__fp_parse:n` to avoid converting back and forth from the internal representation; and (due to rounding) even a non-zero step does not guarantee that the loop counter increases.

```

19053 \cs_new:Npn \fp_step_function:nnnN #1#2#3
19054 {
19055   \exp_after:wN \__fp_step:wwwN
19056   \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#1}
19057   \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#2}
19058   \exp:w \exp_end_continue_f:w \__fp_parse:n {#3}
19059 }
19060 \cs_generate_variant:Nn \fp_step_function:nnnN { nnnc }
19061 % \end{macrocode}
19062 % Only floating point numbers (not tuples) are allowed arguments.
19063 % Only \enquote{normal} floating points (not $\pm 0$,
19064 % $\pm\texttt{inf}$, $\texttt{nan}$) can be used as step; if positive,
19065 % call \cs{__fp_step:NnnnnN} with argument |>| otherwise~|<|. This
19066 % function has one more argument than its integer counterpart, namely
19067 % the previous value, to catch the case where the loop has made no
19068 % progress. Conversion to decimal is done just before calling the
19069 % user's function.
19070 % \begin{macrocode}
19071 \cs_new:Npn \__fp_step:wwwN #1#2; #3#4; #5#6; #7
19072 {
19073   \__fp_if_type_fp:NTwFw #1 { } \s__fp \prg_break: \s__fp_stop
19074   \__fp_if_type_fp:NTwFw #3 { } \s__fp \prg_break: \s__fp_stop
19075   \__fp_if_type_fp:NTwFw #5 { } \s__fp \prg_break: \s__fp_stop
19076   \use_i:nnnn { \__fp_step_fp:wwwN #1#2; #3#4; #5#6; #7 }
19077   \prg_break_point:
19078   \use:n
19079   {
19080     \__fp_error:nfff { fp-step-tuple } { \fp_to_tl:n { #1#2 ; } }
19081     { \fp_to_tl:n { #3#4 ; } } { \fp_to_tl:n { #5#6 ; } }

```

```

19082     }
19083   }
19084   \cs_new:Npn \__fp_step_fp:wwwN #1 ; \s__fp \__fp_chk:w #2#3#4 ; #5; #6
19085   {
19086     \token_if_eq_meaning:NNTF #2 1
19087     {
19088       \token_if_eq_meaning:NNTF #3 0
19089       { \__fp_step:NnnnnN > }
19090       { \__fp_step:NnnnnN < }
19091     }
19092     {
19093       \token_if_eq_meaning:NNTF #2 0
19094       {
19095         \__kernel_msg_expandable_error:nnn { kernel }
19096         { zero-step } {#6}
19097       }
19098       {
19099         \__fp_error:nnfn { fp-bad-step } { }
19100         { \fp_to_tl:n { \s__fp \__fp_chk:w #2#3#4 ; } } {#6}
19101       }
19102       \use_none:nnnnn
19103     }
19104     { #1 ; } { \c_nan_fp } { \s__fp \__fp_chk:w #2#3#4 ; } { #5 ; } #6
19105   }
19106   \cs_new:Npn \__fp_step:NnnnnN #1#2#3#4#5#6
19107   {
19108     \fp_compare:nNnTF {#2} = {#3}
19109     {
19110       \__fp_error:nffn { fp-tiny-step }
19111       { \fp_to_tl:n {#3} } { \fp_to_tl:n {#4} } {#6}
19112     }
19113     {
19114       \fp_compare:nNnF {#2} #1 {#5}
19115       {
19116         \exp_args:Nf #6 { \__fp_to_decimal_dispatch:w #2 }
19117         \__fp_step:NfnnnnN
19118         #1 { \__fp_parse:n { #2 + #4 } } {#2} {#4} {#5} #6
19119       }
19120     }
19121   }
19122   \cs_generate_variant:Nn \__fp_step:NnnnnN { Nf }

```

(End definition for \fp_step_function:nnnN and others. This function is documented on page 205.)

\fp_step_inline:nnnn As for \int_step_inline:nnnn, create a global function and apply it, following up with
\fp_step_variable:nnnNn a break point.

```

\__fp_step:NNnnnn
19123 \cs_new_protected:Npn \fp_step_inline:nnnn
19124 {
19125   \int_gincr:N \g__kernel_prg_map_int
19126   \exp_args:NNc \__fp_step:NNnnnn
19127   \cs_gset_protected:Npn
19128   { __fp_map_ \int_use:N \g__kernel_prg_map_int :w }
19129 }
19130 \cs_new_protected:Npn \fp_step_variable:nnnNn #1#2#3#4#5

```

```

19131 {
19132   \int_gincr:N \g__kernel_prg_map_int
19133   \exp_args:Nnc \__fp_step:NNnnnn
19134   \cs_gset_protected:Npx
19135   { \__fp_map_ \int_use:N \g__kernel_prg_map_int :w }
19136   {#1} {#2} {#3}
19137   {
19138     \tl_set:Nn \exp_not:N #4 {##1}
19139     \exp_not:n {#5}
19140   }
19141 }
19142 \cs_new_protected:Npn \__fp_step:NNnnnn #1#2#3#4#5#6
19143 {
19144   #1 #2 ##1 {#6}
19145   \fp_step_function:nnnN {#3} {#4} {#5} #2
19146   \prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__kernel_prg_map_int }
19147 }

```

(End definition for `\fp_step_inline:nnnn`, `\fp_step_variable:nnnNn`, and `__fp_step:NNnnnn`. These functions are documented on page 205.)

```

19148 \__kernel_msg_new:nnn { kernel } { fp-step-tuple }
19149 { Tuple~argument~in~fp_step...~{#1}{#2}{#3}. }
19150 \__kernel_msg_new:nnn { kernel } { fp-bad-step }
19151 { Invalid~step~size~#2~in~step~function~#3. }
19152 \__kernel_msg_new:nnn { kernel } { fp-tiny-step }
19153 { Tiny~step~size~(#{1}+#{2}=#{1})~in~step~function~#3. }

```

30.5 Extrema

```

\__fp_minmax_o:Nw
\__fp_minmax_aux_o:Nw

```

First check all operands are floating point numbers. The argument #1 is 2 to find the maximum of an array #2 of floating point numbers, and 0 to find the minimum. We read numbers sequentially, keeping track of the largest (smallest) number found so far. If numbers are equal (for instance ± 0), the first is kept. We append $-\infty$ (∞), for the case of an empty array. Since no number is smaller (larger) than that, this additional item only affects the maximum (minimum) in the case of `max()` and `min()` with no argument. The weird fp-like trailing marker breaks the loop correctly: see the precise definition of `__fp_minmax_loop:Nww`.

```

19154 \cs_new:Npn \__fp_minmax_o:Nw #1
19155 {
19156   \__fp_parse_function_all_fp_o:fnw
19157   { \token_if_eq_meaning:NNTF 0 #1 { min } { max } }
19158   { \__fp_minmax_aux_o:Nw #1 }
19159 }
19160 \cs_new:Npn \__fp_minmax_aux_o:Nw #1#2 @
19161 {
19162   \if_meaning:w 0 #1
19163     \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN +
19164   \else:
19165     \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN -
19166   \fi:
19167   #2
19168   \s__fp \__fp_chk:w 2 #1 \s__fp_exact ;
19169   \s__fp \__fp_chk:w { 3 \__fp_minmax_break_o:w } ;

```

19170 }

(End definition for _fp_minmax_o:Nw and _fp_minmax_aux_o:Nw.)

_fp_minmax_loop:Nww The first argument is $-$ or $+$ to denote the case where the currently largest (smallest) number found (first floating point argument) should be replaced by the new number (second floating point argument). If the new number is `nan`, keep that as the extremum, unless that extremum is already a `nan`. Otherwise, compare the two numbers. If the new number is larger (in the case of `max`) or smaller (in the case of `min`), the test yields `true`, and we keep the second number as a new maximum; otherwise we keep the first number. Then loop.

```

19171 \cs_new:Npn \_fp_minmax_loop:Nww
19172   #1 \s__fp \_fp_chk:w #2#3; \s__fp \_fp_chk:w #4#5;
19173   {
19174     \if_meaning:w 3 #4
19175     \if_meaning:w 3 #2
19176       \_fp_minmax_auxi:ww
19177     \else:
19178       \_fp_minmax_auxii:ww
19179     \fi:
19180   \else:
19181     \if_int_compare:w
19182       \_fp_compare_back:ww
19183       \s__fp \_fp_chk:w #4#5;
19184       \s__fp \_fp_chk:w #2#3;
19185       = #1 1 \exp_stop_f:
19186       \_fp_minmax_auxii:ww
19187     \else:
19188       \_fp_minmax_auxi:ww
19189     \fi:
19190   \fi:
19191   \_fp_minmax_loop:Nww #1
19192   \s__fp \_fp_chk:w #2#3;
19193   \s__fp \_fp_chk:w #4#5;
19194 }

```

(End definition for _fp_minmax_loop:Nww.)

_fp_minmax_auxi:ww Keep the first/second number, and remove the other.
_fp_minmax_auxii:ww

```

19195 \cs_new:Npn \_fp_minmax_auxi:ww #1 \fi: \fi: #2 \s__fp #3 ; \s__fp #4;
19196   { \fi: \fi: #2 \s__fp #3 ; }
19197 \cs_new:Npn \_fp_minmax_auxii:ww #1 \fi: \fi: #2 \s__fp #3 ;
19198   { \fi: \fi: #2 }

```

(End definition for _fp_minmax_auxi:ww and _fp_minmax_auxii:ww.)

_fp_minmax_break_o:w This function is called from within an `\if_meaning:w` test. Skip to the end of the tests, close the current test with `\fi:`, clean up, and return the appropriate number with one post-expansion.

```

19199 \cs_new:Npn \_fp_minmax_break_o:w #1 \fi: \fi: #2 \s__fp #3; #4;
19200   { \fi: \_fp_exp_after_o:w \s__fp #3; }

```

(End definition for _fp_minmax_break_o:w.)

30.6 Boolean operations

`__fp_not_o:w` Return true or false, with two expansions, one to exit the conditional, and one to please l3fp-parse. The first argument is provided by l3fp-parse and is ignored.

```

19201 \cs_new:Npn \__fp_not_o:w #1 \s__fp \__fp_chk:w #2#3; @
19202 {
19203   \if_meaning:w 0 #2
19204     \exp_after:wN \exp_after:wN \exp_after:wN \c_one_fp
19205   \else:
19206     \exp_after:wN \exp_after:wN \exp_after:wN \c_zero_fp
19207   \fi:
19208 }
19209 \cs_new:Npn \__fp_tuple_not_o:w #1 @ { \exp_after:wN \c_zero_fp }
```

(End definition for `__fp_not_o:w` and `__fp_tuple_not_o:w`.)

`__fp_&_o:ww` For and, if the first number is zero, return it (with the same sign). Otherwise, return the second one. For or, the logic is reversed: if the first number is non-zero, return it, otherwise return the second number: we achieve that by hi-jacking `__fp_&_o:ww`, inserting an extra argument, `\else:`, before `\s__fp`. In all cases, expand after the floating point number.

```

19210 \group_begin:
19211   \char_set_catcode_letter:N &
19212   \char_set_catcode_letter:N |
19213   \cs_new:Npn \__fp_&_o:ww #1 \s__fp \__fp_chk:w #2#3;
19214   {
19215     \if_meaning:w 0 #2 #1
19216       \__fp_and_return:wNw \s__fp \__fp_chk:w #2#3;
19217     \fi:
19218     \__fp_exp_after_o:w
19219   }
19220   \cs_new:Npn \__fp_&_tuple_o:ww #1 \s__fp \__fp_chk:w #2#3;
19221   {
19222     \if_meaning:w 0 #2 #1
19223       \__fp_and_return:wNw \s__fp \__fp_chk:w #2#3;
19224     \fi:
19225     \__fp_exp_after_tuple_o:w
19226   }
19227   \cs_new:Npn \__fp_tuple_&_o:ww #1; { \__fp_exp_after_o:w }
19228   \cs_new:Npn \__fp_tuple_&_tuple_o:ww #1; { \__fp_exp_after_tuple_o:w }
19229   \cs_new:Npn \__fp_|_o:ww { \__fp_&_o:ww \else: }
19230   \cs_new:Npn \__fp_|_tuple_o:ww { \__fp_&_tuple_o:ww \else: }
19231   \cs_new:Npn \__fp_tuple_|_o:ww #1; #2; { \__fp_exp_after_tuple_o:w #1; }
19232   \cs_new:Npn \__fp_tuple_|_tuple_o:ww #1; #2;
19233     { \__fp_exp_after_tuple_o:w #1; }
19234 \group_end:
19235 \cs_new:Npn \__fp_and_return:wNw #1; \fi: #2;
19236   { \fi: \__fp_exp_after_o:w #1; }
```

(End definition for `__fp_&_o:ww` and others.)

30.7 Ternary operator

`_fp_ternary:NwN`
`_fp_ternary_auxi:NwN`
`_fp_ternary_auxii:NwN`

The first function receives the test and the true branch of the `?:` ternary operator. It calls `_fp_ternary_auxii:NwN` if the test branch is a floating point number ± 0 , and otherwise calls `_fp_ternary_auxi:NwN`. These functions select one of their two arguments.

```

19237 \cs_new:Npn \_fp_ternary:NwN #1 #2#3@ #4@ #5
19238 {
19239   \if_meaning:w \_fp_parse_infix_:N #5
19240     \if_charcode:w 0
19241       \_fp_if_type_fp:NTwFw
19242       #2 { \use_i:nn \_fp_use_i_delimit_by_s_stop:nw #3 \s__fp_stop }
19243       \s__fp 1 \s__fp_stop
19244       \exp_after:wN \exp_after:wN \exp_after:wN \_fp_ternary_auxii:NwN
19245     \else:
19246       \exp_after:wN \exp_after:wN \exp_after:wN \_fp_ternary_auxi:NwN
19247     \fi:
19248     \exp_after:wN #1
19249     \exp:w \exp_end_continue_f:w
19250     \_fp_exp_after_array_f:w #4 \s__fp_expr_stop
19251     \exp_after:wN @
19252     \exp:w
19253     \_fp_parse_operand:Nw \c__fp_prec_colon_int
19254     \_fp_parse_expand:w
19255   \else:
19256     \__kernel_msg_expandable_error:nnnn
19257     { kernel } { fp-missing } { : } { ~for~?: }
19258     \exp_after:wN \_fp_parse_continue:NwN
19259     \exp_after:wN #1
19260     \exp:w \exp_end_continue_f:w
19261     \_fp_exp_after_array_f:w #4 \s__fp_expr_stop
19262     \exp_after:wN #5
19263     \exp_after:wN #1
19264   \fi:
19265 }
19266 \cs_new:Npn \_fp_ternary_auxi:NwN #1#2@#3@#4
19267 {
19268   \exp_after:wN \_fp_parse_continue:NwN
19269   \exp_after:wN #1
19270   \exp:w \exp_end_continue_f:w
19271   \_fp_exp_after_array_f:w #2 \s__fp_expr_stop
19272   #4 #1
19273 }
19274 \cs_new:Npn \_fp_ternary_auxii:NwN #1#2@#3@#4
19275 {
19276   \exp_after:wN \_fp_parse_continue:NwN
19277   \exp_after:wN #1
19278   \exp:w \exp_end_continue_f:w
19279   \_fp_exp_after_array_f:w #3 \s__fp_expr_stop
19280   #4 #1
19281 }

```

(End definition for `_fp_ternary:NwN`, `_fp_ternary_auxi:NwN`, and `_fp_ternary_auxii:NwN`.)

19282 `/\initex | package)`

31 l3fp-basics Implementation

19283 $\langle *initex | package \rangle$

19284 $\langle @@=fp \rangle$

The `l3fp-basics` module implements addition, subtraction, multiplication, and division of two floating points, and the absolute value and sign-changing operations on one floating point. All operations implemented in this module yield the outcome of rounding the infinitely precise result of the operation to the nearest floating point.

Some algorithms used below end up being quite similar to some described in “What Every Computer Scientist Should Know About Floating Point Arithmetic”, by David Goldberg, which can be found at <http://cr.yp.to/2005-590/goldberg.pdf>.

Unary functions.

```

\__fp_parse_word_abs:N
\__fp_parse_word_logb:N
\__fp_parse_word_sign:N
\__fp_parse_word_sqrt:N
19285 \cs_new:Npn \__fp_parse_word_abs:N
19286 { \__fp_parse_unary_function:NNN \__fp_set_sign_o:w 0 }
19287 \cs_new:Npn \__fp_parse_word_logb:N
19288 { \__fp_parse_unary_function:NNN \__fp_logb_o:w ? }
19289 \cs_new:Npn \__fp_parse_word_sign:N
19290 { \__fp_parse_unary_function:NNN \__fp_sign_o:w ? }
19291 \cs_new:Npn \__fp_parse_word_sqrt:N
19292 { \__fp_parse_unary_function:NNN \__fp_sqrt_o:w ? }

```

(End definition for `__fp_parse_word_abs:N` and others.)

31.1 Addition and subtraction

We define here two functions, `__fp_-_o:ww` and `__fp+_o:ww`, which perform the subtraction and addition of their two floating point operands, and expand the tokens following the result once.

A more obscure function, `__fp_add_big_i_o:wNww`, is used in `l3fp-expo`.

The logic goes as follows:

- `__fp_-_o:ww` calls `__fp+_o:ww` to do the work, with the sign of the second operand flipped;
- `__fp+_o:ww` dispatches depending on the type of floating point, calling specialized auxiliaries;
- in all cases except summing two normal floating point numbers, we return one or the other operands depending on the signs, or detect an invalid operation in the case of $\infty - \infty$;
- for normal floating point numbers, compare the signs;
- to add two floating point numbers of the same sign or of opposite signs, shift the significand of the smaller one to match the bigger one, perform the addition or subtraction of significands, check for a carry, round, and pack using the `__fp-basics_pack_...` functions.

The trickiest part is to round correctly when adding or subtracting normal floating point numbers.

31.1.1 Sign, exponent, and special numbers

`__fp_-_o:ww` The `__fp+_o:ww` auxiliary has a hook: it takes one argument between the first `\s__fp` and `__fp_chk:w`, which is applied to the sign of the second operand. Positioning the hook there means that `__fp+_o:ww` can still perform the sanity check that it was followed by `\s__fp`.

```

19293 \cs_new:cpx { __fp_-_o:ww } \s__fp
19294 {
19295     \exp_not:c { __fp+_o:ww }
19296     \exp_not:n { \s__fp \__fp_neg_sign:N }
19297 }

```

(End definition for `__fp_-_o:ww`.)

`__fp+_o:ww` This function is either called directly with an empty #1 to compute an addition, or it is called by `__fp_-_o:ww` with `__fp_neg_sign:N` as #1 to compute a subtraction, in which case the second operand's sign should be changed. If the *<types>* #2 and #4 are the same, dispatch to case #2 (0, 1, 2, or 3), where we call specialized functions: thanks to `\int_value:w`, those receive the tweaked *<sign₂>* (expansion of #1#5) as an argument. If the *<types>* are distinct, the result is simply the floating point number with the highest *<type>*. Since case 3 (used for two nan) also picks the first operand, we can also use it when *<type₁>* is greater than *<type₂>*. Also note that we don't need to worry about *<sign₂>* in that case since the second operand is discarded.

```

19298 \cs_new:cpn { __fp+_o:ww }
19299     \s__fp #1 \__fp_chk:w #2 #3 ; \s__fp \__fp_chk:w #4 #5
19300 {
19301     \if_case:w
19302         \if_meaning:w #2 #4
19303         #2
19304     \else:
19305         \if_int_compare:w #2 > #4 \exp_stop_f:
19306         3
19307     \else:
19308         4
19309     \fi:
19310     \fi:
19311     \exp_stop_f:
19312         \exp_after:wN \__fp_add_zeros_o:Nww \int_value:w
19313     \or: \exp_after:wN \__fp_add_normal_o:Nww \int_value:w
19314     \or: \exp_after:wN \__fp_add_inf_o:Nww \int_value:w
19315     \or: \__fp_case_return_i_o:ww
19316     \else: \exp_after:wN \__fp_add_return_ii_o:Nww \int_value:w
19317     \fi:
19318     #1 #5
19319     \s__fp \__fp_chk:w #2 #3 ;
19320     \s__fp \__fp_chk:w #4 #5
19321 }

```

(End definition for `__fp+_o:ww`.)

`__fp_add_return_ii_o:Nww` Ignore the first operand, and return the second, but using the sign #1 rather than #4. As usual, expand after the floating point.

```

19322 \cs_new:Npn \__fp_add_return_ii_o:Nww #1 #2 ; \s__fp \__fp_chk:w #3 #4
19323 { \__fp_exp_after_o:w \s__fp \__fp_chk:w #3 #1 }

```

(End definition for _fp_add_return_ii_o:Nww.)

_fp_add_zeros_o:Nww Adding two zeros yields \c_zero_fp, except if both zeros were -0 .

```

19324 \cs_new:Npn \_fp_add_zeros_o:Nww #1 \s__fp \_fp_chk:w 0 #2
19325 {
19326   \if_int_compare:w #2 #1 = 20 \exp_stop_f:
19327     \exp_after:wN \_fp_add_return_ii_o:Nww
19328   \else:
19329     \_fp_case_return_i_o:ww
19330   \fi:
19331   #1
19332   \s__fp \_fp_chk:w 0 #2
19333 }

```

(End definition for _fp_add_zeros_o:Nww.)

_fp_add_inf_o:Nww If both infinities have the same sign, just return that infinity, otherwise, it is an invalid operation. We find out if that invalid operation is an addition or a subtraction by testing whether the tweaked $\langle sign_2 \rangle$ (#1) and the $\langle sign_2 \rangle$ (#4) are identical.

```

19334 \cs_new:Npn \_fp_add_inf_o:Nww
19335   #1 \s__fp \_fp_chk:w 2 #2 #3; \s__fp \_fp_chk:w 2 #4
19336 {
19337   \if_meaning:w #1 #2
19338     \_fp_case_return_i_o:ww
19339   \else:
19340     \_fp_case_use:nw
19341     {
19342       \exp_last_unbraced:Nf \_fp_invalid_operation_o:Nww
19343       { \token_if_eq_meaning:NNTF #1 #4 + - }
19344     }
19345   \fi:
19346   \s__fp \_fp_chk:w 2 #2 #3;
19347   \s__fp \_fp_chk:w 2 #4
19348 }

```

(End definition for _fp_add_inf_o:Nww.)

_fp_add_normal_o:Nww _fp_add_normal_o:Nww $\langle sign_2 \rangle$ \s__fp _fp_chk:w 1 $\langle sign_1 \rangle$ $\langle exp_1 \rangle$
 $\langle body_1 \rangle$; \s__fp _fp_chk:w 1 $\langle initial\ sign_2 \rangle$ $\langle exp_2 \rangle$ $\langle body_2 \rangle$;

We now have two normal numbers to add, and we have to check signs and exponents more carefully before performing the addition.

```

19349 \cs_new:Npn \_fp_add_normal_o:Nww #1 \s__fp \_fp_chk:w 1 #2
19350 {
19351   \if_meaning:w #1#2
19352     \exp_after:wN \_fp_add_npos_o:NnwNnw
19353   \else:
19354     \exp_after:wN \_fp_sub_npos_o:NnwNnw
19355   \fi:
19356   #2
19357 }

```

(End definition for _fp_add_normal_o:Nww.)

31.1.2 Absolute addition

In this subsection, we perform the addition of two positive normal numbers.

`__fp_add_npos_o:NnwNnw` `__fp_add_npos_o:NnwNnw <sign1> <exp1> <body1> ; \s__fp __fp_chk:w 1
<initial sign2> <exp2> <body2> ;`

Since we are doing an addition, the final sign is $\langle sign_1 \rangle$. Start an `__fp_int_eval:w`, responsible for computing the exponent: the result, and the $\langle final\ sign \rangle$ are then given to `__fp_sanitize:Nw` which checks for overflow. The exponent is computed as the largest exponent #2 or #5, incremented if there is a carry. To add the significands, we decimate the smaller number by the difference between the exponents. This is done by `__fp_add_big_i:wNnw` or `__fp_add_big_ii:wNnw`. We need to bring the final sign with us in the midst of the calculation to round properly at the end.

```

19358 \cs_new:Npn \__fp_add_npos_o:NnwNnw #1#2#3 ; \s__fp \__fp_chk:w 1 #4 #5
19359 {
19360   \exp_after:wN \__fp_sanitize:Nw
19361   \exp_after:wN #1
19362   \int_value:w \__fp_int_eval:w
19363   \if_int_compare:w #2 > #5 \exp_stop_f:
19364     #2
19365   \exp_after:wN \__fp_add_big_i_o:wNnw \int_value:w -
19366   \else:
19367     #5
19368   \exp_after:wN \__fp_add_big_ii_o:wNnw \int_value:w
19369   \fi:
19370   \__fp_int_eval:w #5 - #2 ; #1 #3;
19371 }

```

(End definition for `__fp_add_npos_o:NnwNnw`.)

`__fp_add_big_i_o:wNnw` `__fp_add_big_i_o:wNnw <shift> ; <final sign> <body1> ; <body2> ;`
`__fp_add_big_ii_o:wNnw` Used in l3fp-expo. Shift the significand of the small number, then add with `__fp_add_significand_o:NnnwnnnnN`.

```

19372 \cs_new:Npn \__fp_add_big_i_o:wNnw #1; #2 #3; #4;
19373 {
19374   \__fp_decimate:Nnnnnn {#1}
19375   \__fp_add_significand_o:NnnwnnnnN
19376   #4
19377   #3
19378   #2
19379 }
19380 \cs_new:Npn \__fp_add_big_ii_o:wNnw #1; #2 #3; #4;
19381 {
19382   \__fp_decimate:Nnnnnn {#1}
19383   \__fp_add_significand_o:NnnwnnnnN
19384   #3
19385   #4
19386   #2
19387 }

```

(End definition for `__fp_add_big_i_o:wNnw` and `__fp_add_big_ii_o:wNnw`.)

```

\__fp_add_significand_o:NnnwnnnnN \__fp_add_significand_o:NnnwnnnnN <rounding digit> {\langle Y'_1 \rangle} {\langle Y'_2 \rangle}
\__fp_add_significand_pack:NNNNNNN <extra-digits> ; {\langle X_1 \rangle} {\langle X_2 \rangle} {\langle X_3 \rangle} {\langle X_4 \rangle} <final sign>
\__fp_add_significand_test_o:N

```

To round properly, we must know at which digit the rounding should occur. This requires to know whether the addition produces an overall carry or not. Thus, we do the computation now and check for a carry, then go back and do the rounding. The rounding may cause a carry in very rare cases such as $0.99\dots95 \rightarrow 1.00\dots0$, but this situation always give an exact power of 10, for which it is easy to correct the result at the end.

```

19388 \cs_new:Npn \__fp_add_significand_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
19389 {
19390   \exp_after:wN \__fp_add_significand_test_o:N
19391   \int_value:w \__fp_int_eval:w 1#5#6 + #2
19392   \exp_after:wN \__fp_add_significand_pack:NNNNNNN
19393   \int_value:w \__fp_int_eval:w 1#7#8 + #3 ; #1
19394 }
19395 \cs_new:Npn \__fp_add_significand_pack:NNNNNNN #1 #2#3#4#5#6#7
19396 {
19397   \if_meaning:w 2 #1
19398     + 1
19399   \fi:
19400   ; #2 #3 #4 #5 #6 #7 ;
19401 }
19402 \cs_new:Npn \__fp_add_significand_test_o:N #1
19403 {
19404   \if_meaning:w 2 #1
19405     \exp_after:wN \__fp_add_significand_carry_o:wwwNN
19406   \else:
19407     \exp_after:wN \__fp_add_significand_no_carry_o:wwwNN
19408   \fi:
19409 }

```

(End definition for `__fp_add_significand_o:NnnwnnnnN`, `__fp_add_significand_pack:NNNNNNN`, and `__fp_add_significand_test_o:N`.)

```

\__fp_add_significand_no_carry_o:wwwNN \__fp_add_significand_no_carry_o:wwwNN <8d> ; <6d> ; <2d> ; <rounding
digit> <sign>

```

If there's no carry, grab all the digits again and round. The packing function `__fp_basics_pack_high:NNNNNw` takes care of the case where rounding brings a carry.

```

19410 \cs_new:Npn \__fp_add_significand_no_carry_o:wwwNN
19411   #1; #2; #3#4 ; #5#6
19412 {
19413   \exp_after:wN \__fp_basics_pack_high:NNNNNw
19414   \int_value:w \__fp_int_eval:w 1 #1
19415   \exp_after:wN \__fp_basics_pack_low:NNNNNw
19416   \int_value:w \__fp_int_eval:w 1 #2 #3#4
19417   + \__fp_round:NNN #6 #4 #5
19418   \exp_after:wN ;
19419 }

```

(End definition for `__fp_add_significand_no_carry_o:wwwNN`.)

```

\__fp_add_significand_carry_o:wwwNN \__fp_add_significand_carry_o:wwwNN <8d> ; <6d> ; <2d> ; <rounding
digit> <sign>

```

The case where there is a carry is very similar. Rounding can even raise the first digit from 1 to 2, but we don't care.

```

19420 \cs_new:Npn \__fp_add_significand_carry_o:wwwNN
19421   #1; #2; #3#4; #5#6
19422   {
19423     + 1
19424     \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNNw
19425     \int_value:w \__fp_int_eval:w 1 1 #1
19426     \exp_after:wN \__fp_basics_pack_weird_low:NNNNw
19427     \int_value:w \__fp_int_eval:w 1 #2#3 +
19428     \exp_after:wN \__fp_round:NNN
19429     \exp_after:wN #6
19430     \exp_after:wN #3
19431     \int_value:w \__fp_round_digit:Nw #4 #5 ;
19432     \exp_after:wN ;
19433   }

```

(End definition for __fp_add_significand_carry_o:wwwNN.)

31.1.3 Absolute subtraction

```

\__fp_sub_npos_o:NnwNnw \__fp_sub_npos_o:NnwNnw <sign1> <exp1> <body1> ; \s__fp \__fp_chk:w 1
\__fp_sub_eq_o:Nwnnw <initial sign2> <exp2> <body2> ;
\__fp_sub_npos_ii_o:Nwnnw

```

Rounding properly in some modes requires to know what the sign of the result will be. Thus, we start by comparing the exponents and significands. If the numbers coincide, return zero. If the second number is larger, swap the numbers and call __fp_sub_npos_i_o:Nwnnw with the opposite of $\langle sign_1 \rangle$.

```

19434 \cs_new:Npn \__fp_sub_npos_o:NnwNnw #1#2#3; \s__fp \__fp_chk:w 1 #4#5#6;
19435   {
19436     \if_case:w \__fp_compare_npos:nwnw {#2} #3; {#5} #6; \exp_stop_f:
19437     \exp_after:wN \__fp_sub_eq_o:Nwnnw
19438     \or:
19439     \exp_after:wN \__fp_sub_npos_i_o:Nwnnw
19440     \else:
19441     \exp_after:wN \__fp_sub_npos_ii_o:Nwnnw
19442     \fi:
19443     #1 {#2} #3; {#5} #6;
19444   }
19445 \cs_new:Npn \__fp_sub_eq_o:Nwnnw #1#2; #3; { \exp_after:wN \c_zero_fp }
19446 \cs_new:Npn \__fp_sub_npos_ii_o:Nwnnw #1 #2; #3;
19447   {
19448     \exp_after:wN \__fp_sub_npos_i_o:Nwnnw
19449     \int_value:w \__fp_neg_sign:N #1
19450     #3; #2;
19451   }

```

(End definition for __fp_sub_npos_o:NnwNnw, __fp_sub_eq_o:Nwnnw, and __fp_sub_npos_ii_o:Nwnnw.)

```

\__fp_sub_npos_i_o:Nwnnw

```

After the computation is done, __fp_sanitize:Nw checks for overflow/underflow. It expects the $\langle final\ sign \rangle$ and the $\langle exponent \rangle$ (delimited by ;). Start an integer expression for the exponent, which starts with the exponent of the largest number, and may be decreased if the two numbers are very close. If the two numbers have the same exponent, call the `near` auxiliary. Otherwise, decimate y , then call the `far` auxiliary to evaluate

the difference between the two significands. Note that we decimate by 1 less than one could expect.

```

19452 \cs_new:Npn \__fp_sub_npos_i_o:Nnwnw #1 #2#3; #4#5;
19453 {
19454   \exp_after:wN \__fp_sanitizew
19455   \exp_after:wN #1
19456   \int_value:w \__fp_int_eval:w
19457   #2
19458   \if_int_compare:w #2 = #4 \exp_stop_f:
19459     \exp_after:wN \__fp_sub_back_near_o:nnnnnnnnN
19460   \else:
19461     \exp_after:wN \__fp_decimate:nNnnnn \exp_after:wN
19462     { \int_value:w \__fp_int_eval:w #2 - #4 - 1 \exp_after:wN }
19463     \exp_after:wN \__fp_sub_back_far_o:NnnwnnnnnN
19464   \fi:
19465   #5
19466   #3
19467   #1
19468 }

```

(End definition for __fp_sub_npos_i_o:Nnwnw.)

```

\__fp_sub_back_near_o:nnnnnnnnN \__fp_sub_back_near_o:nnnnnnnnN {<Y1>} {<Y2>} {<Y3>} {<Y4>} {<X1>}
\__fp_sub_back_near_pack:NNNNNNw {<X2>} {<X3>} {<X4>} {<final sign>}
\__fp_sub_back_near_after:wNNNNw

```

In this case, the subtraction is exact, so we discard the *<final sign>* #9. The very large shifts of 10^9 and $1.1 \cdot 10^9$ are unnecessary here, but allow the auxiliaries to be reused later. Each integer expression produces a 10 digit result. If the resulting 16 digits start with a 0, then we need to shift the group, padding with trailing zeros.

```

19469 \cs_new:Npn \__fp_sub_back_near_o:nnnnnnnnN #1#2#3#4 #5#6#7#8 #9
19470 {
19471   \exp_after:wN \__fp_sub_back_near_after:wNNNNw
19472   \int_value:w \__fp_int_eval:w 10#5#6 - #1#2 - 11
19473   \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
19474   \int_value:w \__fp_int_eval:w 11#7#8 - #3#4 \exp_after:wN ;
19475 }
19476 \cs_new:Npn \__fp_sub_back_near_pack:NNNNNNw #1#2#3#4#5#6#7 ;
19477 { + #1#2 ; {#3#4#5#6} {#7} ; }
19478 \cs_new:Npn \__fp_sub_back_near_after:wNNNNw 10 #1#2#3#4 #5 ;
19479 {
19480   \if_meaning:w 0 #1
19481     \exp_after:wN \__fp_sub_back_shift:wnnnn
19482   \fi:
19483   ; {#1#2#3#4} {#5}
19484 }

```

(End definition for __fp_sub_back_near_o:nnnnnnnnN, __fp_sub_back_near_pack:NNNNNNw, and __fp_sub_back_near_after:wNNNNw.)

```

\__fp_sub_back_shift:wnnnn \__fp_sub_back_shift:wnnnn ; {<Z1>} {<Z2>} {<Z3>} {<Z4>} ;
\__fp_sub_back_shift_ii:ww This function is called with <Z1> ≤ 999. Act with \number to trim leading zeros from
\__fp_sub_back_shift_iii:NNNNNNNNw <Z1> <Z2> (we don't do all four blocks at once, since non-zero blocks would then overflow
\__fp_sub_back_shift_iv:nnnnw TEX's integers). If the first two blocks are zero, the auxiliary receives an empty #1 and

```

trims #2#30 from leading zeros, yielding a total shift between 7 and 16 to the exponent. Otherwise we get the shift from #1 alone, yielding a result between 1 and 6. Once the

exponent is taken care of, trim leading zeros from #1#2#3 (when #1 is empty, the space before #2#3 is ignored), get four blocks of 4 digits and finally clean up. Trailing zeros are added so that digits can be grabbed safely.

```

19485 \cs_new:Npn \__fp_sub_back_shift:wnnnn ; #1#2
19486 {
19487   \exp_after:wN \__fp_sub_back_shift_ii:ww
19488   \int_value:w #1 #2 0 ;
19489 }
19490 \cs_new:Npn \__fp_sub_back_shift_ii:ww #1 0 ; #2#3 ;
19491 {
19492   \if_meaning:w @ #1 @
19493     - 7
19494     - \exp_after:wN \use_i:nnn
19495       \exp_after:wN \__fp_sub_back_shift_iii:NNNNNNNNw
19496       \int_value:w #2#3 0 ~ 123456789;
19497   \else:
19498     - \__fp_sub_back_shift_iii:NNNNNNNNw #1 123456789;
19499   \fi:
19500   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
19501   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
19502   \exp_after:wN \__fp_sub_back_shift_iv:nnnnw
19503   \exp_after:wN ;
19504   \int_value:w
19505   #1 ~ #2#3 0 ~ 0000 0000 0000 000 ;
19506 }
19507 \cs_new:Npn \__fp_sub_back_shift_iii:NNNNNNNNw #1#2#3#4#5#6#7#8#9; {#8}
19508 \cs_new:Npn \__fp_sub_back_shift_iv:nnnnw #1 ; #2 ; { ; #1 ; }

```

(End definition for __fp_sub_back_shift:wnnnn and others.)

__fp_sub_back_far_o:NnnwnnnnN $\langle \text{rounding} \rangle \{ \langle Y'_1 \rangle \} \{ \langle Y'_2 \rangle \}$
 $\langle \text{extra-digits} \rangle ; \{ \langle X_1 \rangle \} \{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \} \langle \text{final sign} \rangle$

If the difference is greater than $10^{\langle expo_x \rangle}$, call the `very_far` auxiliary. If the result is less than $10^{\langle expo_x \rangle}$, call the `not_far` auxiliary. If it is too close a call to know yet, namely if $1 \langle Y'_1 \rangle \langle Y'_2 \rangle = \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle X_4 \rangle 0$, then call the `quite_far` auxiliary. We use the odd combination of space and semi-colon delimiters to allow the `not_far` auxiliary to grab each piece individually, the `very_far` auxiliary to use `__fp_pack_eight:wNNNNNNNN`, and the `quite_far` to ignore the significands easily (using the `; delimiter`).

```

19509 \cs_new:Npn \__fp_sub_back_far_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
19510 {
19511   \if_case:w
19512     \if_int_compare:w 1 #2 = #5#6 \use_i:nnnn #7 \exp_stop_f:
19513     \if_int_compare:w #3 = \use_none:n #7#8 0 \exp_stop_f:
19514     0
19515     \else:
19516       \if_int_compare:w #3 > \use_none:n #7#8 0 - \fi: 1
19517       \fi:
19518     \else:
19519       \if_int_compare:w 1 #2 > #5#6 \use_i:nnnn #7 - \fi: 1
19520       \fi:
19521     \exp_stop_f:
19522     \exp_after:wN \__fp_sub_back_quite_far_o:wwNN
19523   \or: \exp_after:wN \__fp_sub_back_very_far_o:wwwNN

```

```

19524     \else: \exp_after:wN \__fp_sub_back_not_far_o:wwwNNN
19525     \fi:
19526     #2 ~ #3 ; #5 #6 ~ #7 #8 ; #1
19527 }

```

(End definition for __fp_sub_back_far_o:NnnwnnnnN.)

__fp_sub_back_quite_far_o:wwNN
__fp_sub_back_quite_far_ii:NN

The easiest case is when $x - y$ is extremely close to a power of 10, namely the first digit of x is 1, and all others vanish when subtracting y . Then the *rounding* #3 and the *final sign* #4 control whether we get 1 or 0.9999999999999999. In the usual round-to-nearest mode, we get 1 whenever the *rounding* digit is less than or equal to 5 (remember that the *rounding* digit is only equal to 5 if there was no further non-zero digit).

```

19528 \cs_new:Npn \__fp_sub_back_quite_far_o:wwNN #1; #2; #3#4
19529 {
19530     \exp_after:wN \__fp_sub_back_quite_far_ii:NN
19531     \exp_after:wN #3
19532     \exp_after:wN #4
19533 }
19534 \cs_new:Npn \__fp_sub_back_quite_far_ii:NN #1#2
19535 {
19536     \if_case:w \__fp_round_neg:NNN #2 0 #1
19537     \exp_after:wN \use_i:nn
19538     \else:
19539     \exp_after:wN \use_ii:nn
19540     \fi:
19541     { ; {1000} {0000} {0000} {0000} ; }
19542     { - 1 ; {9999} {9999} {9999} {9999} ; }
19543 }

```

(End definition for __fp_sub_back_quite_far_o:wwNN and __fp_sub_back_quite_far_ii:NN.)

__fp_sub_back_not_far_o:wwwNN

In the present case, x and y have different exponents, but y is large enough that $x - y$ has a smaller exponent than x . Decrement the exponent (with -1). Then proceed in a way similar to the **near** auxiliaries seen earlier, but multiplying x by 10 (#30 and #40 below), and with the added quirk that the *rounding* digit has to be taken into account. Namely, we may have to decrease the result by one unit if __fp_round_neg:NNN returns 1. This function expects the *final sign* #6, the last digit of 1100000000+#40-#2, and the *rounding* digit. Instead of redoing the computation for the second argument, we note that __fp_round_neg:NNN only cares about its parity, which is identical to that of the last digit of #2.

```

19544 \cs_new:Npn \__fp_sub_back_not_far_o:wwwNN #1 ~ #2; #3 ~ #4; #5#6
19545 {
19546     - 1
19547     \exp_after:wN \__fp_sub_back_near_after:wNNNNw
19548     \int_value:w \__fp_int_eval:w 1#30 - #1 - 11
19549     \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
19550     \int_value:w \__fp_int_eval:w 11 0000 0000 + #40 - #2
19551     - \exp_after:wN \__fp_round_neg:NNN
19552     \exp_after:wN #6
19553     \use_none:nnnnnnn #2 #5
19554     \exp_after:wN ;
19555 }

```

(End definition for __fp_sub_back_not_far_o:wwwNN.)

_fp_sub_back_very_far_o:wwwNN
_fp_sub_back_very_far_ii_o:nnNwwNN

The case where $x - y$ and x have the same exponent is a bit more tricky, mostly because it cannot reuse the same auxiliaries. Shift the y significand by adding a leading 0. Then the logic is similar to the `not_far` functions above. Rounding is a bit more complicated: we have two *rounding* digits #3 and #6 (from the decimation, and from the new shift) to take into account, and getting the parity of the main result requires a computation. The first `\int_value:w` triggers the second one because the number is unfinished; we can thus not use 0 in place of 2 there.

```

19556 \cs_new:Npn \__fp_sub_back_very_far_o:wwwNN #1#2#3#4#5#6#7
19557 {
19558   \__fp_pack_eight:wNNNNNNNN
19559   \__fp_sub_back_very_far_ii_o:nnNwwNN
19560   { 0 #1#2#3 #4#5#6#7 }
19561   ;
19562 }
19563 \cs_new:Npn \__fp_sub_back_very_far_ii_o:nnNwwNN #1#2 ; #3 ; #4 ~ #5; #6#7
19564 {
19565   \exp_after:wN \__fp_basics_pack_high:NNNNw
19566   \int_value:w \__fp_int_eval:w 1#4 - #1 - 1
19567   \exp_after:wN \__fp_basics_pack_low:NNNNw
19568   \int_value:w \__fp_int_eval:w 2#5 - #2
19569   - \exp_after:wN \__fp_round_neg:NNN
19570   \exp_after:wN #7
19571   \int_value:w
19572   \if_int_odd:w \__fp_int_eval:w #5 - #2 \__fp_int_eval_end:
19573   1 \else: 2 \fi:
19574   \int_value:w \__fp_round_digit:Nw #3 #6 ;
19575   \exp_after:wN ;
19576 }

```

(End definition for `__fp_sub_back_very_far_o:wwwNN` and `__fp_sub_back_very_far_ii_o:nnNwwNN`.)

31.2 Multiplication

31.2.1 Signs, and special numbers

_fp*_o:ww

We go through an auxiliary, which is common with `__fp/_o:ww`. The first argument is the operation, used for the invalid operation exception. The second is inserted in a formula to dispatch cases slightly differently between multiplication and division. The third is the operation for normal floating points. The fourth is there for extra cases needed in `__fp/_o:ww`.

```

19577 \cs_new:cpn { \__fp*_o:ww }
19578 {
19579   \__fp_mul_cases_o:NnNww
19580   *
19581   { - 2 + }
19582   \__fp_mul_npos_o:Nww
19583   { }
19584 }

```

(End definition for `__fp*_o:ww`.)

_fp_mul_cases_o:nNnnww

Split into 10 cases (12 for division). If both numbers are normal, go to case 0 (same sign) or case 1 (opposite signs): in both cases, call `__fp_mul_npos_o:Nww` to do the work. If

the first operand is `nan`, go to case 2, in which the second operand is discarded; if the second operand is `nan`, go to case 3, in which the first operand is discarded (note the weird interaction with the final test on signs). Then we separate the case where the first number is normal and the second is zero: this goes to cases 4 and 5 for multiplication, 10 and 11 for division. Otherwise, we do a computation which dispatches the products $0 \times 0 = 0 \times 1 = 1 \times 0 = 0$ to case 4 or 5 depending on the combined sign, the products $0 \times \infty$ and $\infty \times 0$ to case 6 or 7 (invalid operation), and the products $1 \times \infty = \infty \times 1 = \infty \times \infty = \infty$ to cases 8 and 9. Note that the code for these two cases (which return $\pm\infty$) is inserted as argument #4, because it differs in the case of divisions.

```

19585 \cs_new:Npn \__fp_mul_cases_o:NnNnw
19586   #1#2#3#4 \s__fp \__fp_chk:w #5#6#7; \s__fp \__fp_chk:w #8#9
19587   {
19588     \if_case:w \__fp_int_eval:w
19589       \if_int_compare:w #5 #8 = 11 ~
19590         1
19591       \else:
19592         \if_meaning:w 3 #8
19593         3
19594       \else:
19595         \if_meaning:w 3 #5
19596         2
19597       \else:
19598         \if_int_compare:w #5 #8 = 10 ~
19599         9 #2 - 2
19600       \else:
19601         (#5 #2 #8) / 2 * 2 + 7
19602       \fi:
19603     \fi:
19604     \fi:
19605     \fi:
19606     \if_meaning:w #6 #9 - 1 \fi:
19607     \__fp_int_eval_end:
19608     \__fp_case_use:nw { #3 0 }
19609     \or: \__fp_case_use:nw { #3 2 }
19610     \or: \__fp_case_return_i_o:ww
19611     \or: \__fp_case_return_ii_o:ww
19612     \or: \__fp_case_return_o:Nww \c_zero_fp
19613     \or: \__fp_case_return_o:Nww \c_minus_zero_fp
19614     \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
19615     \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
19616     \or: \__fp_case_return_o:Nww \c_inf_fp
19617     \or: \__fp_case_return_o:Nww \c_minus_inf_fp
19618     #4
19619     \fi:
19620     \s__fp \__fp_chk:w #5 #6 #7;
19621     \s__fp \__fp_chk:w #8 #9
19622   }

```

(End definition for `__fp_mul_cases_o:nNnnnw`.)

31.2.2 Absolute multiplication

In this subsection, we perform the multiplication of two positive normal numbers.

```

\__fp_mul_npos_o:Nww \__fp_mul_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign1> {<exp1>}
<body1> ; \s__fp \__fp_chk:w 1 <sign2> {<exp2>} <body2> ;

```

After the computation, `__fp_sanitizew` checks for overflow or underflow. As we did for addition, `__fp_int_eval:w` computes the exponent, catching any shift coming from the computation in the significand. The `<final sign>` is needed to do the rounding properly in the significand computation. We setup the post-expansion here, triggered by `__fp_mul_significand_o:nnnnNnnnn`.

This is also used in `l3fp-convert`.

```

19623 \cs_new:Npn \__fp_mul_npos_o:Nww
19624 #1 \s__fp \__fp_chk:w #2 #3 #4 #5 ; \s__fp \__fp_chk:w #6 #7 #8 #9 ;
19625 {
19626   \exp_after:wN \__fp_sanitizew
19627   \exp_after:wN #1
19628   \int_value:w \__fp_int_eval:w
19629     #4 + #8
19630     \__fp_mul_significand_o:nnnnNnnnn #5 #1 #9
19631 }

```

(End definition for `__fp_mul_npos_o:Nww`.)

```

\__fp_mul_significand_o:nnnnNnnnn \__fp_mul_significand_o:nnnnNnnnn {<X1>} {<X2>} {<X3>} {<X4>} <sign>
\__fp_mul_significand_drop:NNNNNw {<Y1>} {<Y2>} {<Y3>} {<Y4>}
\__fp_mul_significand_keep:NNNNNw

```

Note the three semicolons at the end of the definition. One is for the last `__fp_mul_significand_drop:NNNNNw`; one is for `__fp_round_digit:Nw` later on; and one, preceded by `\exp_after:wN`, which is correctly expanded (within an `__fp_int_eval:w`), is used by `__fp_basics_pack_low:NNNNNw`.

The product of two 16 digit integers has 31 or 32 digits, but it is impossible to know which one before computing. The place where we round depends on that number of digits, and may depend on all digits until the last in some rare cases. The approach is thus to compute the 5 first blocks of 4 digits (the first one is between 100 and 9999 inclusive), and a compact version of the remaining 3 blocks. Afterwards, the number of digits is known, and we can do the rounding within yet another set of `__fp_int_eval:w`.

```

19632 \cs_new:Npn \__fp_mul_significand_o:nnnnNnnnn #1#2#3#4 #5 #6#7#8#9
19633 {
19634   \exp_after:wN \__fp_mul_significand_test_f:NNN
19635   \exp_after:wN #5
19636   \int_value:w \__fp_int_eval:w 99990000 + #1*#6 +
19637   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
19638   \int_value:w \__fp_int_eval:w 99990000 + #1*#7 + #2*#6 +
19639   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
19640   \int_value:w \__fp_int_eval:w 99990000 + #1*#8 + #2*#7 + #3*#6 +
19641   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
19642   \int_value:w \__fp_int_eval:w 99990000 + #1*#9 + #2*#8 +
19643   #3*#7 + #4*#6 +
19644   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
19645   \int_value:w \__fp_int_eval:w 99990000 + #2*#9 + #3*#8 +
19646   #4*#7 +
19647   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
19648   \int_value:w \__fp_int_eval:w 99990000 + #3*#9 + #4*#8 +
19649   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
19650   \int_value:w \__fp_int_eval:w 100000000 + #4*#9 ;
19651   ; \exp_after:wN ;

```

```

19652 }
19653 \cs_new:Npn \__fp_mul_significand_drop:NNNNNw #1#2#3#4#5 #6;
19654 { #1#2#3#4#5 ; + #6 }
19655 \cs_new:Npn \__fp_mul_significand_keep:NNNNNw #1#2#3#4#5 #6;
19656 { #1#2#3#4#5 ; #6 ; }

```

(End definition for __fp_mul_significand_o:nnnnNnnnn, __fp_mul_significand_drop:NNNNNw, and __fp_mul_significand_keep:NNNNNw.)

```

\__fp_mul_significand_test_f:NNN \__fp_mul_significand_test_f:NNN <sign> 1 <digits 1-8> ; <digits 9-12> ;
<digits 13-16> ; + <digits 17-20> + <digits 21-24> + <digits 25-28> + <digits
29-32> ; \exp_after:wN ;

```

If the $\langle \text{digit } 1 \rangle$ is non-zero, then for rounding we only care about the digits 16 and 17, and whether further digits are zero or not (check for exact ties). On the other hand, if $\langle \text{digit } 1 \rangle$ is zero, we care about digits 17 and 18, and whether further digits are zero.

```

19657 \cs_new:Npn \__fp_mul_significand_test_f:NNN #1 #2 #3
19658 {
19659   \if_meaning:w 0 #3
19660     \exp_after:wN \__fp_mul_significand_small_f:NNwwwN
19661   \else:
19662     \exp_after:wN \__fp_mul_significand_large_f:NwwNNNN
19663   \fi:
19664   #1 #3
19665 }

```

(End definition for __fp_mul_significand_test_f:NNN.)

__fp_mul_significand_large_f:NwwNNNN In this branch, $\langle \text{digit } 1 \rangle$ is non-zero. The result is thus $\langle \text{digits } 1-16 \rangle$, plus some rounding which depends on the digits 16, 17, and whether all subsequent digits are zero or not. Here, __fp_round_digit:Nw takes digits 17 and further (as an integer expression), and replaces it by a $\langle \text{rounding digit} \rangle$, suitable for __fp_round:NNN.

```

19666 \cs_new:Npn \__fp_mul_significand_large_f:NwwNNNN #1 #2; #3; #4#5#6#7; +
19667 {
19668   \exp_after:wN \__fp_basics_pack_high:NNNNNw
19669   \int_value:w \__fp_int_eval:w 1#2
19670   \exp_after:wN \__fp_basics_pack_low:NNNNNw
19671   \int_value:w \__fp_int_eval:w 1#3#4#5#6#7
19672   + \exp_after:wN \__fp_round:NNN
19673   \exp_after:wN #1
19674   \exp_after:wN #7
19675   \int_value:w \__fp_round_digit:Nw
19676 }

```

(End definition for __fp_mul_significand_large_f:NwwNNNN.)

__fp_mul_significand_small_f:NNwwwN In this branch, $\langle \text{digit } 1 \rangle$ is zero. Our result is thus $\langle \text{digits } 2-17 \rangle$, plus some rounding which depends on the digits 17, 18, and whether all subsequent digits are zero or not. The 8 digits 1#3 are followed, after expansion of the small_pack auxiliary, by the next digit, to form a 9 digit number.

```

19677 \cs_new:Npn \__fp_mul_significand_small_f:NNwwwN #1 #2#3; #4#5; #6; + #7
19678 {
19679   - 1
19680   \exp_after:wN \__fp_basics_pack_high:NNNNNw
19681   \int_value:w \__fp_int_eval:w 1#3#4

```

```

19682     \exp_after:wN \__fp_basics_pack_low:NNNNw
19683     \int_value:w \__fp_int_eval:w 1#5#6#7
19684     + \exp_after:wN \__fp_round:NNN
19685     \exp_after:wN #1
19686     \exp_after:wN #7
19687     \int_value:w \__fp_round_digit:Nw
19688 }

```

(End definition for __fp_mul_significand_small_f:NNwwN.)

31.3 Division

31.3.1 Signs, and special numbers

Time is now ripe to tackle the hardest of the four elementary operations: division.

__fp/_o:ww Filtering special floating point is very similar to what we did for multiplications, with a few variations. Invalid operation exceptions display / rather than *. In the formula for dispatch, we replace - 2 + by -. The case of normal numbers is treated using __fp_div_npos_o:Nww rather than __fp_mul_npos_o:Nww. There are two additional cases: if the first operand is normal and the second is a zero, then the division by zero exception is raised: cases 10 and 11 of the \if_case:w construction in __fp_mul_cases_o:NnNww are provided as the fourth argument here.

```

19689 \cs_new:cpn { __fp/_o:ww }
19690 {
19691     \__fp_mul_cases_o:NnNww
19692     /
19693     { - }
19694     \__fp_div_npos_o:Nww
19695     {
19696         \or:
19697         \__fp_case_use:nw
19698         { \__fp_division_by_zero_o:NNww \c_inf_fp / }
19699         \or:
19700         \__fp_case_use:nw
19701         { \__fp_division_by_zero_o:NNww \c_minus_inf_fp / }
19702     }
19703 }

```

(End definition for __fp/_o:ww.)

```

\__fp_div_npos_o:Nww \__fp_div_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign_A> {\<exp A>}
{\<A_1>} {\<A_2>} {\<A_3>} {\<A_4>} ; \s__fp \__fp_chk:w 1 <sign_Z> {\<exp Z>}
{\<Z_1>} {\<Z_2>} {\<Z_3>} {\<Z_4>} ;

```

We want to compute A/Z . As for multiplication, __fp_sanitize:Nw checks for overflow or underflow; we provide it with the $\langle final\ sign \rangle$, and an integer expression in which we compute the exponent. We set up the arguments of __fp_div_significand_i_o:wnnw, namely an integer $\langle y \rangle$ obtained by adding 1 to the first 5 digits of Z (explanation given soon below), then the four $\{\langle A_i \rangle\}$, then the four $\{\langle Z_i \rangle\}$, a semi-colon, and the $\langle final\ sign \rangle$, used for rounding at the end.

```

19704 \cs_new:Npn \__fp_div_npos_o:Nww
19705 #1 \s__fp \__fp_chk:w 1 #2 #3 #4 ; \s__fp \__fp_chk:w 1 #5 #6 #7#8#9;
19706 {

```

```

19707 \exp_after:wN \__fp_sanitizew
19708 \exp_after:wN #1
19709 \int_value:w \__fp_int_eval:w
19710 #3 - #6
19711 \exp_after:wN \__fp_div_significand_i_o:wNnw
19712 \int_value:w \__fp_int_eval:w #7 \use_i:nnnn #8 + 1 ;
19713 #4
19714 {#7}{#8}#9 ;
19715 #1
19716 }

```

(End definition for __fp_div_npos_o:Nww.)

31.3.2 Work plan

In this subsection, we explain how to avoid overflowing \TeX 's integers when performing the division of two positive normal numbers.

We are given two numbers, $A = 0.A_1A_2A_3A_4$ and $Z = 0.Z_1Z_2Z_3Z_4$, in blocks of 4 digits, and we know that the first digits of A_1 and of Z_1 are non-zero. To compute A/Z , we proceed as follows.

- Find an integer $Q_A \simeq 10^4 A/Z$.
- Replace A by $B = 10^4 A - Q_A Z$.
- Find an integer $Q_B \simeq 10^4 B/Z$.
- Replace B by $C = 10^4 B - Q_B Z$.
- Find an integer $Q_C \simeq 10^4 C/Z$.
- Replace C by $D = 10^4 C - Q_C Z$.
- Find an integer $Q_D \simeq 10^4 D/Z$.
- Consider $E = 10^4 D - Q_D Z$, and ensure correct rounding.

The result is then $Q = 10^{-4}Q_A + 10^{-8}Q_B + 10^{-12}Q_C + 10^{-16}Q_D + \text{rounding}$. Since the Q_i are integers, B , C , D , and E are all exact multiples of 10^{-16} , in other words, computing with 16 digits after the decimal separator yields exact results. The problem is the risk of overflow: in general B , C , D , and E may be greater than 1.

Unfortunately, things are not as easy as they seem. In particular, we want all intermediate steps to be positive, since negative results would require extra calculations at the end. This requires that $Q_A \leq 10^4 A/Z$ etc. A reasonable attempt would be to define Q_A as

$$\text{\int_eval:n} \left\{ \frac{A_1 A_2}{Z_1 + 1} - 1 \right\} \leq 10^4 \frac{A}{Z}$$

Subtracting 1 at the end takes care of the fact that $\varepsilon\text{\TeX}$'s `__fp_int_eval:w` rounds divisions instead of truncating (really, $1/2$ would be sufficient, but we work with integers). We add 1 to Z_1 because $Z_1 \leq 10^4 Z < Z_1 + 1$ and we need Q_A to be an underestimate. However, we are now underestimating Q_A too much: it can be wrong by up to 100, for instance when $Z = 0.1$ and $A \simeq 1$. Then B could take values up to 10 (maybe more), and a few steps down the line, we would run into arithmetic overflow, since \TeX can only handle integers less than roughly $2 \cdot 10^9$.

A better formula is to take

$$Q_A = \backslash\text{int_eval:n}\left\{\frac{10 \cdot A_1 A_2}{\lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1} - 1\right\}.$$

This is always less than $10^9 A / (10^5 Z)$, as we wanted. In words, we take the 5 first digits of Z into account, and the 8 first digits of A , using 0 as a 9-th digit rather than the true digit for efficiency reasons. We shall prove that using this formula to define all the Q_i avoids any overflow. For convenience, let us denote

$$y = \lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1,$$

so that, taking into account the fact that $\varepsilon\text{-TeX}$ rounds ties away from zero,

$$\begin{aligned} Q_A &= \left\lfloor \frac{A_1 A_2 0}{y} - \frac{1}{2} \right\rfloor \\ &> \frac{A_1 A_2 0}{y} - \frac{3}{2}. \end{aligned}$$

Note that $10^4 < y \leq 10^5$, and $999 \leq Q_A \leq 99989$. Also note that this formula does not cause an overflow as long as $A < (2^{31} - 1)/10^9 \simeq 2.147 \dots$, since the numerator involves an integer slightly smaller than $10^9 A$.

Let us bound B :

$$\begin{aligned} 10^5 B &= A_1 A_2 0 + 10 \cdot 0.A_3 A_4 - 10 \cdot Z_1.Z_2 Z_3 Z_4 \cdot Q_A \\ &< A_1 A_2 0 \cdot \left(1 - 10 \cdot \frac{Z_1.Z_2 Z_3 Z_4}{y}\right) + \frac{3}{2} \cdot 10 \cdot Z_1.Z_2 Z_3 Z_4 + 10 \\ &\leq \frac{A_1 A_2 0 \cdot (y - 10 \cdot Z_1.Z_2 Z_3 Z_4)}{y} + \frac{3}{2}y + 10 \\ &\leq \frac{A_1 A_2 0 \cdot 1}{y} + \frac{3}{2}y + 10 \leq \frac{10^9 A}{y} + 1.6 \cdot y. \end{aligned}$$

At the last step, we hide 10 into the second term for later convenience. The same reasoning yields

$$\begin{aligned} 10^5 B &< 10^9 A / y + 1.6y, \\ 10^5 C &< 10^9 B / y + 1.6y, \\ 10^5 D &< 10^9 C / y + 1.6y, \\ 10^5 E &< 10^9 D / y + 1.6y. \end{aligned}$$

The goal is now to prove that none of B , C , D , and E can go beyond $(2^{31} - 1)/10^9 = 2.147 \dots$.

Combining the various inequalities together with $A < 1$, we get

$$\begin{aligned} 10^5 B &< 10^9 / y + 1.6y, \\ 10^5 C &< 10^{13} / y^2 + 1.6(y + 10^4), \\ 10^5 D &< 10^{17} / y^3 + 1.6(y + 10^4 + 10^8 / y), \\ 10^5 E &< 10^{21} / y^4 + 1.6(y + 10^4 + 10^8 / y + 10^{12} / y^2). \end{aligned}$$

All of those bounds are convex functions of y (since every power of y involved is convex, and the coefficients are positive), and thus maximal at one of the end-points of the allowed range $10^4 < y \leq 10^5$. Thus,

$$\begin{aligned} 10^5 B &< \max(1.16 \cdot 10^5, 1.7 \cdot 10^5), \\ 10^5 C &< \max(1.32 \cdot 10^5, 1.77 \cdot 10^5), \\ 10^5 D &< \max(1.48 \cdot 10^5, 1.777 \cdot 10^5), \\ 10^5 E &< \max(1.64 \cdot 10^5, 1.7777 \cdot 10^5). \end{aligned}$$

All of those bounds are less than $2.147 \cdot 10^5$, and we are thus within $\text{T}_{\text{E}}\text{X}$'s bounds in all cases!

We later need to have a bound on the Q_i . Their definitions imply that $Q_A < 10^9 A/y - 1/2 < 10^5 A$ and similarly for the other Q_i . Thus, all of them are less than 177770.

The last step is to ensure correct rounding. We have

$$A/Z = \sum_{i=1}^4 (10^{-4i} Q_i) + 10^{-16} E/Z$$

exactly. Furthermore, we know that the result is in $[0.1, 10)$, hence will be rounded to a multiple of 10^{-16} or of 10^{-15} , so we only need to know the integer part of E/Z , and a “rounding” digit encoding the rest. Equivalently, we need to find the integer part of $2E/Z$, and determine whether it was an exact integer or not (this serves to detect ties). Since

$$\frac{2E}{Z} = 2 \frac{10^5 E}{10^5 Z} \leq 2 \frac{10^5 E}{10^4} < 36,$$

this integer part is between 0 and 35 inclusive. We let $\varepsilon\text{-T}_{\text{E}}\text{X}$ round

$$P = \backslash\text{int_eval:n} \left\{ \frac{2 \cdot E_1 E_2}{Z_1 Z_2} \right\},$$

which differs from $2E/Z$ by at most

$$\frac{1}{2} + 2 \left| \frac{E}{Z} - \frac{E}{10^{-8} Z_1 Z_2} \right| + 2 \left| \frac{10^8 E - E_1 E_2}{Z_1 Z_2} \right| < 1,$$

($1/2$ comes from $\varepsilon\text{-T}_{\text{E}}\text{X}$'s rounding) because each absolute value is less than 10^{-7} . Thus P is either the correct integer part, or is off by 1; furthermore, if $2E/Z$ is an integer, $P = 2E/Z$. We will check the sign of $2E - PZ$. If it is negative, then $E/Z \in ((P-1)/2, P/2)$. If it is zero, then $E/Z = P/2$. If it is positive, then $E/Z \in (P/2, (P+1)/2)$. In each case, we know how to round to an integer, depending on the parity of P , and the rounding mode.

31.3.3 Implementing the significand division

`_fp_div_significand_i_o:wnnw`

`_fp_div_significand_i_o:wnnw <y> ; {<A1>} {<A2>} {<A3>} {<A4>}
{<Z1>} {<Z2>} {<Z3>} {<Z4>} ; <sign>`

Compute $10^6 + Q_A$ (a 7 digit number thanks to the shift), unbrace $\langle A_1 \rangle$ and $\langle A_2 \rangle$, and prepare the $\langle continuation \rangle$ arguments for 4 consecutive calls to `_fp_div_significand_calc:wnnnnnnn`. Each of these calls needs $\langle y \rangle$ (**#1**), and it turns out that

we need post-expansion there, hence the `\int_value:w`. Here, `#4` is six brace groups, which give the six first n-type arguments of the `calc` function.

```

19717 \cs_new:Npn \__fp_div_significand_i_o:wnnw #1 ; #2#3 #4 ;
19718 {
19719   \exp_after:wN \__fp_div_significand_test_o:w
19720   \int_value:w \__fp_int_eval:w
19721   \exp_after:wN \__fp_div_significand_calc:wnnnnnnn
19722   \int_value:w \__fp_int_eval:w 999999 + #2 #3 0 / #1 ;
19723   #2 #3 ;
19724   #4
19725   { \exp_after:wN \__fp_div_significand_ii:wN \int_value:w #1 }
19726   { \exp_after:wN \__fp_div_significand_ii:wN \int_value:w #1 }
19727   { \exp_after:wN \__fp_div_significand_ii:wN \int_value:w #1 }
19728   { \exp_after:wN \__fp_div_significand_iii:wnnnnnn \int_value:w #1 }
19729 }

```

(End definition for `__fp_div_significand_i_o:wnnw`.)

```

\__fp_div_significand_calc:wnnnnnnn \__fp_div_significand_calc:wnnnnnnn <106 + QA> ; <A1> <A2> ; {<A3>}
\__fp_div_significand_calc_i:wnnnnnnn {<A4>} {<Z1>} {<Z2>} {<Z3>} {<Z4>} {<continuation>}
\__fp_div_significand_calc_ii:wnnnnnnn expands to
<106 + QA> <continuation> ; <B1> <B2> ; {<B3>} {<B4>} {<Z1>} {<Z2>} {<Z3>}
{<Z4>}

```

where $B = 10^4 A - Q_A \cdot Z$. This function is also used to compute C , D , E (with the input shifted accordingly), and is used in `l3fp-expo`.

We know that $0 < Q_A < 1.8 \cdot 10^5$, so the product of Q_A with each Z_i is within $\text{T}_{\text{E}}\text{X}$'s bounds. However, it is a little bit too large for our purposes: we would not be able to use the usual trick of adding a large power of 10 to ensure that the number of digits is fixed.

The bound on Q_A , implies that $10^6 + Q_A$ starts with the digit 1, followed by 0 or 1. We test, and call different auxiliaries for the two cases. An earlier implementation did the tests within the computation, but since we added a `<continuation>`, this is not possible because the macro has 9 parameters.

The result we want is then (the overall power of 10 is arbitrary):

$$\begin{aligned}
& 10^{-4}(\#2 - \#1 \cdot \#5 - 10 \cdot \langle i \rangle \cdot \#5\#6) + 10^{-8}(\#3 - \#1 \cdot \#6 - 10 \cdot \langle i \rangle \cdot \#7) \\
& + 10^{-12}(\#4 - \#1 \cdot \#7 - 10 \cdot \langle i \rangle \cdot \#8) + 10^{-16}(-\#1 \cdot \#8),
\end{aligned}$$

where $\langle i \rangle$ stands for the 10^5 digit of Q_A , which is 0 or 1, and $\#1$, $\#2$, *etc.* are the parameters of either auxiliary. The factors of 10 come from the fact that $Q_A = 10 \cdot 10^4 \cdot \langle i \rangle + \#1$. As usual, to combine all the terms, we need to choose some shifts which must ensure that the number of digits of the second, third, and fourth terms are each fixed. Here, the positive contributions are at most 10^8 and the negative contributions can go up to 10^9 . Indeed, for the auxiliary with $\langle i \rangle = 1$, $\#1$ is at most 80000, leading to contributions of at worst $-8 \cdot 10^8 4$, while the other negative term is very small $< 10^6$ (except in the first expression, where we don't care about the number of digits); for the auxiliary with $\langle i \rangle = 0$, $\#1$ can go up to 99999, but there is no other negative term. Hence, a good choice is $2 \cdot 10^9$, which produces totals in the range $[10^9, 2.1 \cdot 10^9]$. We are flirting with $\text{T}_{\text{E}}\text{X}$'s limits once more.

```

19730 \cs_new:Npn \__fp_div_significand_calc:wnnnnnnn #1#

```

```

19731 {
19732   \if_meaning:w 1 #1
19733   \exp_after:wN \__fp_div_significand_calc_i:wwnnnnnnnn
19734   \else:
19735     \exp_after:wN \__fp_div_significand_calc_ii:wwnnnnnnnn
19736   \fi:
19737 }
19738 \cs_new:Npn \__fp_div_significand_calc_i:wwnnnnnnnn
19739 #1; #2;#3#4 #5#6#7#8 #9
19740 {
19741   1 1 #1
19742   #9 \exp_after:wN ;
19743   \int_value:w \__fp_int_eval:w \c__fp_Bigg_leading_shift_int
19744   + #2 - #1 * #5 - #5#60
19745   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
19746   \int_value:w \__fp_int_eval:w \c__fp_Bigg_middle_shift_int
19747   + #3 - #1 * #6 - #70
19748   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
19749   \int_value:w \__fp_int_eval:w \c__fp_Bigg_middle_shift_int
19750   + #4 - #1 * #7 - #80
19751   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
19752   \int_value:w \__fp_int_eval:w \c__fp_Bigg_trailing_shift_int
19753   - #1 * #8 ;
19754   {#5}{#6}{#7}{#8}
19755 }
19756 \cs_new:Npn \__fp_div_significand_calc_ii:wwnnnnnnnn
19757 #1; #2;#3#4 #5#6#7#8 #9
19758 {
19759   1 0 #1
19760   #9 \exp_after:wN ;
19761   \int_value:w \__fp_int_eval:w \c__fp_Bigg_leading_shift_int
19762   + #2 - #1 * #5
19763   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
19764   \int_value:w \__fp_int_eval:w \c__fp_Bigg_middle_shift_int
19765   + #3 - #1 * #6
19766   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
19767   \int_value:w \__fp_int_eval:w \c__fp_Bigg_middle_shift_int
19768   + #4 - #1 * #7
19769   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
19770   \int_value:w \__fp_int_eval:w \c__fp_Bigg_trailing_shift_int
19771   - #1 * #8 ;
19772   {#5}{#6}{#7}{#8}
19773 }

```

(End definition for __fp_div_significand_calc:wwnnnnnnnn, __fp_div_significand_calc_i:wwnnnnnnnn,
and __fp_div_significand_calc_ii:wwnnnnnnnn.)

__fp_div_significand_ii:wwn $\langle y \rangle$; $\langle B_1 \rangle$; $\{\langle B_2 \rangle\}$ $\{\langle B_3 \rangle\}$ $\{\langle B_4 \rangle\}$ $\{\langle Z_1 \rangle\}$
 $\{\langle Z_2 \rangle\}$ $\{\langle Z_3 \rangle\}$ $\{\langle Z_4 \rangle\}$ $\langle continuations \rangle$ $\langle sign \rangle$

Compute Q_B by evaluating $\langle B_1 \rangle \langle B_2 \rangle 0 / y - 1$. The result is output to the left, in an
 $\backslash_fp_int_eval:w$ which we start now. Once that is evaluated (and the other Q_i also,
since later expansions are triggered by this one), a packing auxiliary takes care of placing
the digits of Q_B in an appropriate way for the final addition to obtain Q . This auxiliary
is also used to compute Q_C and Q_D with the inputs C and D instead of B .

```

19774 \cs_new:Npn \__fp_div_significand_ii:wwn #1; #2;#3
19775 {
19776   \exp_after:wN \__fp_div_significand_pack:NNN
19777   \int_value:w \__fp_int_eval:w
19778   \exp_after:wN \__fp_div_significand_calc:wwnnnnnnn
19779   \int_value:w \__fp_int_eval:w 999999 + #2 #3 0 / #1 ; #2 #3 ;
19780 }

```

(End definition for __fp_div_significand_ii:wwn.)

```

\__fp_div_significand_iii:wwnnnnn <y> ; <E1> ; {<E2>} {<E3>} {<E4>}
{<Z1>} {<Z2>} {<Z3>} {<Z4>} <sign>

```

We compute $P \simeq 2E/Z$ by rounding $2E_1E_2/Z_1Z_2$. Note the first 0, which multiplies Q_D by 10: we later add (roughly) $5 \cdot P$, which amounts to adding $P/2 \simeq E/Z$ to Q_D , the appropriate correction from a hypothetical Q_E .

```

19781 \cs_new:Npn \__fp_div_significand_iii:wwnnnnn #1; #2;#3#4#5 #6#7
19782 {
19783   0
19784   \exp_after:wN \__fp_div_significand_iv:wwnnnnnnn
19785   \int_value:w \__fp_int_eval:w ( 2 * #2 #3 ) / #6 #7 ; % <- P
19786   #2 ; {#3} {#4} {#5}
19787   {#6} {#7}
19788 }

```

(End definition for __fp_div_significand_iii:wwnnnnn.)

```

\__fp_div_significand_iv:wwnnnnnnn <P> ; <E1> ; {<E2>} {<E3>} {<E4>}
\__fp_div_significand_v:NNw {<Z1>} {<Z2>} {<Z3>} {<Z4>} <sign>
\__fp_div_significand_vi:Nw

```

This adds to the current expression ($10^7 + 10 \cdot Q_D$) a contribution of $5 \cdot P + \text{sign}(T)$ with $T = 2E - PZ$. This amounts to adding $P/2$ to Q_D , with an extra *rounding* digit. This *rounding* digit is 0 or 5 if T does not contribute, *i.e.*, if $0 = T = 2E - PZ$, in other words if $10^{16}A/Z$ is an integer or half-integer. Otherwise it is in the appropriate range, $[1, 4]$ or $[6, 9]$. This is precise enough for rounding purposes (in any mode).

It seems an overkill to compute T exactly as I do here, but I see no faster way right now.

Once more, we need to be careful and show that the calculation $\#1 \cdot \#6\#7$ below does not cause an overflow: naively, P can be up to 35, and $\#6\#7$ up to 10^8 , but both cannot happen simultaneously. To show that things are fine, we split in two (non-disjoint) cases.

- For $P < 10$, the product obeys $P \cdot \#6\#7 < 10^8 \cdot P < 10^9$.
- For large $P \geq 3$, the rounding error on P , which is at most 1, is less than a factor of 2, hence $P \leq 4E/Z$. Also, $\#6\#7 \leq 10^8 \cdot Z$, hence $P \cdot \#6\#7 \leq 4E \cdot 10^8 < 10^9$.

Both inequalities could be made tighter if needed.

Note however that $P \cdot \#8\#9$ may overflow, since the two factors are now independent, and the result may reach $3.5 \cdot 10^9$. Thus we compute the two lower levels separately. The rest is standard, except that we use $+$ as a separator (ending integer expressions explicitly). T is negative if the first character is $-$, it is positive if the first character is neither 0 nor $-$. It is also positive if the first character is 0 and second argument of $__fp_div_significand_vi:Nw$, a sum of several terms, is also zero. Otherwise, there was an exact agreement: $T = 0$.

```

19789 \cs_new:Npn \__fp_div_significand_iv:wwnnnnnnn #1; #2;#3#4#5 #6#7#8#9
19790 {
19791   + 5 * #1
19792   \exp_after:wN \__fp_div_significand_vi:Nw
19793   \int_value:w \__fp_int_eval:w -20 + 2*#2#3 - #1*#6#7 +
19794   \exp_after:wN \__fp_div_significand_v:NN
19795   \int_value:w \__fp_int_eval:w 199980 + 2*#4 - #1*#8 +
19796   \exp_after:wN \__fp_div_significand_v:NN
19797   \int_value:w \__fp_int_eval:w 200000 + 2*#5 - #1*#9 ;
19798 }
19799 \cs_new:Npn \__fp_div_significand_v:NN #1#2 { #1#2 \__fp_int_eval_end: + }
19800 \cs_new:Npn \__fp_div_significand_vi:Nw #1#2;
19801 {
19802   \if_meaning:w 0 #1
19803     \if_int_compare:w \__fp_int_eval:w #2 > 0 + 1 \fi:
19804   \else:
19805     \if_meaning:w - #1 - \else: + \fi: 1
19806   \fi:
19807   ;
19808 }

```

(End definition for __fp_div_significand_iv:wwnnnnnnn, __fp_div_significand_v:NNw, and __fp_div_significand_vi:Nw.)

__fp_div_significand_pack:NNN At this stage, we are in the following situation: \TeX is in the process of expanding several integer expressions, thus functions at the bottom expand before those above.

$$\begin{aligned} & _ _ \text{fp_div_significand_test_o:w } 10^6 + Q_A _ _ \text{fp_div_significand_} \\ & \text{pack:NNN } 10^6 + Q_B _ _ \text{fp_div_significand_pack:NNN } 10^6 + Q_C _ _ \text{fp_} \\ & \text{div_significand_pack:NNN } 10^7 + 10 \cdot Q_D + 5 \cdot P + \varepsilon ; \langle \text{sign} \rangle \end{aligned}$$

Here, $\varepsilon = \text{sign}(T)$ is 0 in case $2E = PZ$, 1 in case $2E > PZ$, which means that P was the correct value, but not with an exact quotient, and -1 if $2E < PZ$, *i.e.*, P was an overestimate. The packing function we define now does nothing special: it removes the 10^6 and carries two digits (for the 10^5 's and the 10^4 's).

```

19809 \cs_new:Npn \__fp_div_significand_pack:NNN 1 #1 #2 { + #1 #2 ; }

```

(End definition for __fp_div_significand_pack:NNN.)

__fp_div_significand_test_o:w __fp_div_significand_test_o:w 1 0 $\langle 5d \rangle$; $\langle 4d \rangle$; $\langle 4d \rangle$; $\langle 5d \rangle$; $\langle \text{sign} \rangle$

The reason we know that the first two digits are 1 and 0 is that the final result is known to be between 0.1 (inclusive) and 10, hence \widetilde{Q}_A (the tilde denoting the contribution from the other Q_i) is at most 99999, and $10^6 + \widetilde{Q}_A = 10 \dots$.

It is now time to round. This depends on how many digits the final result will have.

```

19810 \cs_new:Npn \__fp_div_significand_test_o:w 10 #1
19811 {
19812   \if_meaning:w 0 #1
19813     \exp_after:wN \__fp_div_significand_small_o:wwwNNNNwN
19814   \else:
19815     \exp_after:wN \__fp_div_significand_large_o:wwwNNNNwN
19816   \fi:
19817   #1
19818 }

```

(End definition for __fp_div_significand_test_o:w.)

```

\__fp_div_significand_small_o:wwwNNNNwN \__fp_div_significand_small_o:wwwNNNNwN 0 <4d> ; <4d> ; <4d> ; <5d>
; <final sign>

```

Standard use of the functions `__fp_basics_pack_low:NNNNw` and `__fp_basics_pack_high:NNNNw`. We finally get to use the *<final sign>* which has been sitting there for a while.

```

19819 \cs_new:Npn \__fp_div_significand_small_o:wwwNNNNwN
19820 0 #1; #2; #3; #4#5#6#7#8; #9
19821 {
19822 \exp_after:wN \__fp_basics_pack_high:NNNNw
19823 \int_value:w \__fp_int_eval:w 1 #1#2
19824 \exp_after:wN \__fp_basics_pack_low:NNNNw
19825 \int_value:w \__fp_int_eval:w 1 #3#4#5#6#7
19826 + \__fp_round:NNN #9 #7 #8
19827 \exp_after:wN ;
19828 }

```

(End definition for `__fp_div_significand_small_o:wwwNNNNwN`.)

```

\__fp_div_significand_large_o:wwwNNNNwN \__fp_div_significand_large_o:wwwNNNNwN <5d> ; <4d> ; <4d> ; <5d> ;
<sign>

```

We know that the final result cannot reach 10, hence `1#1#2`, together with contributions from the level below, cannot reach $2 \cdot 10^9$. For rounding, we build the *<rounding digit>* from the last two of our 18 digits.

```

19829 \cs_new:Npn \__fp_div_significand_large_o:wwwNNNNwN
19830 #1; #2; #3; #4#5#6#7#8; #9
19831 {
19832 + 1
19833 \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNw
19834 \int_value:w \__fp_int_eval:w 1 #1 #2
19835 \exp_after:wN \__fp_basics_pack_weird_low:NNNNw
19836 \int_value:w \__fp_int_eval:w 1 #3 #4 #5 #6 +
19837 \exp_after:wN \__fp_round:NNN
19838 \exp_after:wN #9
19839 \exp_after:wN #6
19840 \int_value:w \__fp_round_digit:Nw #7 #8 ;
19841 \exp_after:wN ;
19842 }

```

(End definition for `__fp_div_significand_large_o:wwwNNNNwN`.)

31.4 Square root

`__fp_sqrt_o:w` Zeros are unchanged: $\sqrt{-0} = -0$ and $\sqrt{+0} = +0$. Negative numbers (other than -0) have no real square root. Positive infinity, and `nan`, are unchanged. Finally, for normal positive numbers, there is some work to do.

```

19843 \cs_new:Npn \__fp_sqrt_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
19844 {
19845 \if_meaning:w 0 #2 \__fp_case_return_same_o:w \fi:
19846 \if_meaning:w 2 #3
19847 \__fp_case_use:nw { \__fp_invalid_operation_o:nw { sqrt } }
19848 \fi:
19849 \if_meaning:w 1 #2 \else: \__fp_case_return_same_o:w \fi:
19850 \__fp_sqrt_npos_o:w

```

```

19851   \s__fp \__fp_chk:w #2 #3 #4;
19852   }

```

(End definition for __fp_sqrt_o:w.)

```

\__fp_sqrt_npos_o:w
\__fp_sqrt_npos_auxi_o:wNnnN
\__fp_sqrt_npos_auxii_o:wNNNNNNNNN

```

Prepare __fp_sanitize:Nw to receive the final sign 0 (the result is always positive) and the exponent, equal to half of the exponent #1 of the argument. If the exponent #1 is even, find a first approximation of the square root of the significand $10^8 a_1 + a_2 = 10^8 \#2\#3 + \#4\#5$ through Newton's method, starting at $x = 57234133 \simeq 10^{7.75}$. Otherwise, first shift the significand of the argument by one digit, getting $a'_1 \in [10^6, 10^7)$ instead of $[10^7, 10^8)$, then use Newton's method starting at $17782794 \simeq 10^{7.25}$.

```

19853 \cs_new:Npn \__fp_sqrt_npos_o:w \s__fp \__fp_chk:w 1 0 #1#2#3#4#5;
19854 {
19855   \exp_after:wN \__fp_sanitize:Nw
19856   \exp_after:wN 0
19857   \int_value:w \__fp_int_eval:w
19858   \if_int_odd:w #1 \exp_stop_f:
19859     \exp_after:wN \__fp_sqrt_npos_auxi_o:wNnnN
19860     \fi:
19861     #1 / 2
19862     \__fp_sqrt_Newton_o:wN 56234133; 0; {#2#3} {#4#5} 0
19863   }
19864 \cs_new:Npn \__fp_sqrt_npos_auxi_o:wNnnN #1 / 2 #2; 0; #3#4#5
19865 {
19866   ( #1 + 1 ) / 2
19867   \__fp_pack_eight:wNNNNNNNNN
19868   \__fp_sqrt_npos_auxii_o:wNNNNNNNNN
19869   ;
19870   0 #3 #4
19871 }
19872 \cs_new:Npn \__fp_sqrt_npos_auxii_o:wNNNNNNNNN #1; #2#3#4#5#6#7#8#9
19873 { \__fp_sqrt_Newton_o:wN 17782794; 0; {#1} {#2#3#4#5#6#7#8#9} }

```

(End definition for __fp_sqrt_npos_o:w, __fp_sqrt_npos_auxi_o:wNnnN, and __fp_sqrt_npos_auxii_o:wNNNNNNNNN.)

```

\__fp_sqrt_Newton_o:wN

```

Newton's method maps $x \mapsto [(x + [10^8 a_1/x])/2]$ in each iteration, where $[b/c]$ denotes ε -TeX's division. This division rounds the real number b/c to the closest integer, rounding ties away from zero, hence when c is even, $b/c - 1/2 + 1/c \leq [b/c] \leq b/c + 1/2$ and when c is odd, $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2 - 1/(2c)$. For all c , $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2$.

Let us prove that the method converges when implemented with ε -TeX integer division, for any $10^6 \leq a_1 < 10^8$ and starting value $10^6 \leq x < 10^8$. Using the inequalities above and the arithmetic-geometric inequality $(x + t)/2 \geq \sqrt{xt}$ for $t = 10^8 a_1/x$, we find

$$x' = \left\lceil \frac{x + [10^8 a_1/x]}{2} \right\rceil \geq \frac{x + 10^8 a_1/x - 1/2 + 1/(2x)}{2} \geq \sqrt{10^8 a_1} - \frac{1}{4} + \frac{1}{4x}.$$

After any step of iteration, we thus have $\delta = x - \sqrt{10^8 a_1} \geq -0.25 + 0.25 \cdot 10^{-8}$. The new difference $\delta' = x' - \sqrt{10^8 a_1}$ after one step is bounded above as

$$x' - \sqrt{10^8 a_1} \leq \frac{x + 10^8 a_1/x + 1/2}{2} + \frac{1}{2} - \sqrt{10^8 a_1} \leq \frac{\delta}{2} \frac{\delta}{\sqrt{10^8 a_1} + \delta} + \frac{3}{4}.$$

For $\delta > 3/2$, this last expression is $\leq \delta/2 + 3/4 < \delta$, hence δ decreases at each step: since all x are integers, δ must reach a value $-1/4 < \delta \leq 3/2$. In this range of values, we get $\delta' \leq \frac{3}{4} \frac{3}{2\sqrt{10^8 a_1}} + \frac{3}{4} \leq 0.75 + 1.125 \cdot 10^{-7}$. We deduce that the difference $\delta = x - \sqrt{10^8 a_1}$ eventually reaches a value in the interval $[-0.25 + 0.25 \cdot 10^{-8}, 0.75 + 11.25 \cdot 10^{-8}]$, whose width is $1 + 11 \cdot 10^{-8}$. The corresponding interval for x may contain two integers, hence x might oscillate between those two values.

However, the fact that $x \mapsto x - 1$ and $x - 1 \mapsto x$ puts stronger constraints, which are not compatible: the first implies

$$x + [10^8 a_1 / x] \leq 2x - 2$$

hence $10^8 a_1 / x \leq x - 3/2$, while the second implies

$$x - 1 + [10^8 a_1 / (x - 1)] \geq 2x - 1$$

hence $10^8 a_1 / (x - 1) \geq x - 1/2$. Combining the two inequalities yields $x^2 - 3x/2 \geq 10^8 a_1 \geq x - 3x/2 + 1/2$, which cannot hold. Therefore, the iteration always converges to a single integer x . To stop the iteration when two consecutive results are equal, the function `_fp_sqrt_Newton_o:wnn` receives the newly computed result as #1, the previous result as #2, and a_1 as #3. Note that ε -TeX combines the computation of a multiplication and a following division, thus avoiding overflow in `#3 * 100000000 / #1`. In any case, the result is within $[10^7, 10^8]$.

```

19874 \cs_new:Npn \_fp_sqrt_Newton_o:wnn #1; #2; #3
19875 {
19876   \if_int_compare:w #1 = #2 \exp_stop_f:
19877     \exp_after:wN \_fp_sqrt_auxi_o:NNNNwnnnN
19878     \int_value:w \_fp_int_eval:w 9999 9999 +
19879     \exp_after:wN \_fp_use_none_until_s:w
19880   \fi:
19881   \exp_after:wN \_fp_sqrt_Newton_o:wnn
19882   \int_value:w \_fp_int_eval:w (#1 + #3 * 1 0000 0000 / #1) / 2 ;
19883   #1; {#3}
19884 }

```

(End definition for `_fp_sqrt_Newton_o:wnn`.)

`_fp_sqrt_auxi_o:NNNNwnnnN` This function is followed by $10^8 + x - 1$, which has 9 digits starting with 1, then ; $\{a_1\} \{a_2\} \{a'\}$. Here, $x \simeq \sqrt{10^8 a_1}$ and we want to estimate the square root of $a = 10^{-8} a_1 + 10^{-16} a_2 + 10^{-17} a'$. We set up an initial underestimate

$$y = (x - 1)10^{-8} + 0.2499998875 \cdot 10^{-8} \lesssim \sqrt{a}.$$

From the inequalities shown earlier, we know that $y \leq \sqrt{10^{-8} a_1} \leq \sqrt{a}$ and that $\sqrt{10^{-8} a_1} \leq y + 10^{-8} + 11 \cdot 10^{-16}$ hence (using $0.1 \leq y \leq \sqrt{a} \leq 1$)

$$a - y^2 \leq 10^{-8} a_1 + 10^{-8} - y^2 \leq (y + 10^{-8} + 11 \cdot 10^{-16})^2 - y^2 + 10^{-8} < 3.2 \cdot 10^{-8},$$

and $\sqrt{a} - y = (a - y^2) / (\sqrt{a} + y) \leq 16 \cdot 10^{-8}$. Next, `_fp_sqrt_auxii_o:NnnnnnnnnN` is called several times to get closer and closer underestimates of \sqrt{a} . By construction, the underestimates y are always increasing, $a - y^2 < 3.2 \cdot 10^{-8}$ for all. Also, $y < 1$.

```

19885 \cs_new:Npn \_fp_sqrt_auxii_o:NnnnnnnnnN 1 #1#2#3#4#5;
19886 {

```

```

19887 \__fp_sqrt_auxii_o:NnnnnnnnN
19888 \__fp_sqrt_auxiii_o:wnnnnnnnn
19889 {#1#2#3#4} {#5} {2499} {9988} {7500}
19890 }

```

(End definition for __fp_sqrt_auxi_o:NNNNwnnnN.)

__fp_sqrt_auxii_o:NnnnnnnnN

This receives a continuation function #1, then five blocks of 4 digits for y , then two 8-digit blocks and a single digit for a . A common estimate of $\sqrt{a} - y = (a - y^2)/(\sqrt{a} + y)$ is $(a - y^2)/(2y)$, which leads to alternating overestimates and underestimates. We tweak this, to only work with underestimates (no need then to worry about signs in the computation). Each step finds the largest integer $j \leq 6$ such that $10^{4j}(a - y^2) < 2 \cdot 10^8$, then computes the integer (with ε -TeX's rounding division)

$$10^{4j}z = \left[\left(\lfloor 10^{4j}(a - y^2) \rfloor - 257 \right) \cdot (0.5 \cdot 10^8) \right] / \lfloor 10^8 y + 1 \rfloor.$$

The choice of j ensures that $10^{4j}z < 2 \cdot 10^8 \cdot 0.5 \cdot 10^8 / 10^7 = 10^9$, thus $10^9 + 10^{4j}z$ has exactly 10 digits, does not overflow TeX's integer range, and starts with 1. Incidentally, since all $a - y^2 \leq 3.2 \cdot 10^{-8}$, we know that $j \geq 3$.

Let us show that z is an underestimate of $\sqrt{a} - y$. On the one hand, $\sqrt{a} - y \leq 16 \cdot 10^{-8}$ because this holds for the initial y and values of y can only increase. On the other hand, the choice of j implies that $\sqrt{a} - y \leq 5(\sqrt{a} + y)(\sqrt{a} - y) = 5(a - y^2) < 10^{9-4j}$. For $j = 3$, the first bound is better, while for larger j , the second bound is better. For all $j \in [3, 6]$, we find $\sqrt{a} - y < 16 \cdot 10^{-2j}$. From this, we deduce that

$$10^{4j}(\sqrt{a} - y) = \frac{10^{4j}(a - y^2 - (\sqrt{a} - y)^2)}{2y} \geq \frac{\lfloor 10^{4j}(a - y^2) \rfloor - 257}{2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor} + \frac{1}{2}$$

where we have replaced the bound $10^{4j}(16 \cdot 10^{-2j}) = 256$ by 257 and extracted the corresponding term $1/(2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor) \geq 1/2$. Given that ε -TeX's integer division obeys $\lfloor b/c \rfloor \leq b/c + 1/2$, we deduce that $10^{4j}z \leq 10^{4j}(\sqrt{a} - y)$, hence $y + z \leq \sqrt{a}$ is an underestimate of \sqrt{a} , as claimed. One implementation detail: because the computation involves $-4*4 - 2*3*5 - 2*2*6$ which may be as low as $-5 \cdot 10^8$, we need to use the `pack_big` functions, and the big shifts.

```

19891 \cs_new:Npn \__fp_sqrt_auxii_o:NnnnnnnnN #1 #2#3#4#5#6 #7#8#9
19892 {
19893   \exp_after:wN #1
19894   \int_value:w \__fp_int_eval:w \c__fp_big_leading_shift_int
19895   + #7 - #2 * #2
19896   \exp_after:wN \__fp_pack_big:NNNNNNw
19897   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
19898   - 2 * #2 * #3
19899   \exp_after:wN \__fp_pack_big:NNNNNNw
19900   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
19901   + #8 - #3 * #3 - 2 * #2 * #4
19902   \exp_after:wN \__fp_pack_big:NNNNNNw
19903   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
19904   - 2 * #3 * #4 - 2 * #2 * #5
19905   \exp_after:wN \__fp_pack_big:NNNNNNw
19906   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
19907   + #9 000 0000 - #4 * #4 - 2 * #3 * #5 - 2 * #2 * #6
19908   \exp_after:wN \__fp_pack_big:NNNNNNw

```



```

19909         \int_value:w \_fp_int_eval:w \c\_fp\_big\_middle\_shift\_int
19910         - 2 * #4 * #5 - 2 * #3 * #6
19911         \exp_after:wN \_fp\_pack\_big:NNNNNNw
19912         \int_value:w \_fp_int_eval:w \c\_fp\_big\_middle\_shift\_int
19913         - #5 * #5 - 2 * #4 * #6
19914         \exp_after:wN \_fp\_pack\_big:NNNNNNw
19915         \int_value:w \_fp_int_eval:w
19916         \c\_fp\_big\_middle\_shift\_int
19917         - 2 * #5 * #6
19918         \exp_after:wN \_fp\_pack\_big:NNNNNNw
19919         \int_value:w \_fp_int_eval:w
19920         \c\_fp\_big\_trailing\_shift\_int
19921         - #6 * #6 ;
19922     % (
19923     - 257 ) * 5000 0000 / (#2#3 + 1) + 10 0000 0000 ;
19924     {#2}{#3}{#4}{#5}{#6} {#7}{#8}#9
19925 }

```

(End definition for _fp_sqrt_auxii_o:NnnnnnnnnN.)

```

\_fp\_sqrt\_auxiii\_o:wnnnnnnnnn
\_fp\_sqrt\_auxiv\_o:NNNNNNw
\_fp\_sqrt\_auxv\_o:NNNNNNw
\_fp\_sqrt\_auxvi\_o:NNNNNNw
\_fp\_sqrt\_auxvii\_o:NNNNNNw

```

We receive here the difference $a - y^2 = d = \sum_i d_i \cdot 10^{-4i}$, as $\langle d_2 \rangle$; $\{\langle d_3 \rangle\} \dots \{\langle d_{10} \rangle\}$, where each block has 4 digits, except $\langle d_2 \rangle$. This function finds the largest $j \leq 6$ such that $10^{4j}(a - y^2) < 2 \cdot 10^8$, then leaves an open parenthesis and the integer $\lfloor 10^{4j}(a - y^2) \rfloor$ in an integer expression. The closing parenthesis is provided by the caller _fp_sqrt_auxii_o:NnnnnnnnnN, which completes the expression

$$10^{4j}z = \left[(\lfloor 10^{4j}(a - y^2) \rfloor - 257) \cdot (0.5 \cdot 10^8) / \lfloor 10^8 y + 1 \rfloor \right]$$

for an estimate of $10^{4j}(\sqrt{a} - y)$. If $d_2 \geq 2$, $j = 3$ and the **auxiv** auxiliary receives $10^{12}z$. If $d_2 \leq 1$ but $10^4 d_2 + d_3 \geq 2$, $j = 4$ and the **auxv** auxiliary is called, and receives $10^{16}z$, and so on. In all those cases, the **auxviii** auxiliary is set up to add z to y , then go back to the **auxii** step with continuation **auxiii** (the function we are currently describing). The maximum value of j is 6, regardless of whether $10^{12}d_2 + 10^8 d_3 + 10^4 d_4 + d_5 \geq 1$. In this last case, we detect when $10^{24}z < 10^7$, which essentially means $\sqrt{a} - y \lesssim 10^{-17}$: once this threshold is reached, there is enough information to find the correctly rounded \sqrt{a} with only one more call to _fp_sqrt_auxii_o:NnnnnnnnnN. Note that the iteration cannot be stuck before reaching $j = 6$, because for $j < 6$, one has $2 \cdot 10^8 \leq 10^{4(j+1)}(a - y^2)$, hence

$$10^{4j}z \geq \frac{(20000 - 257)(0.5 \cdot 10^8)}{\lfloor 10^8 y + 1 \rfloor} \geq (20000 - 257) \cdot 0.5 > 0.$$

```

19926 \cs_new:Npn \_fp\_sqrt\_auxiii\_o:wnnnnnnnnn
19927   #1; #2#3#4#5#6#7#8#9
19928   {
19929     \if_int_compare:w #1 > 1 \exp_stop_f:
19930     \exp_after:wN \_fp\_sqrt\_auxiv\_o:NNNNNNw
19931     \int_value:w \_fp_int_eval:w (#1#2 %)
19932   \else:
19933     \if_int_compare:w #1#2 > 1 \exp_stop_f:
19934     \exp_after:wN \_fp\_sqrt\_auxv\_o:NNNNNNw
19935     \int_value:w \_fp_int_eval:w (#1#2#3 %)
19936   \else:
19937     \if_int_compare:w #1#2#3 > 1 \exp_stop_f:
19938     \exp_after:wN \_fp\_sqrt\_auxvi\_o:NNNNNNw

```

```

19939         \int_value:w \__fp_int_eval:w (#1#2#3#4 %)
19940     \else:
19941         \exp_after:wN \__fp_sqrt_auxvii_o:NNNNNw
19942         \int_value:w \__fp_int_eval:w (#1#2#3#4#5 %)
19943     \fi:
19944 \fi:
19945 \fi:
19946 }
19947 \cs_new:Npn \__fp_sqrt_auxiv_o:NNNNNw #1#2#3#4#5#6;
19948 { \__fp_sqrt_auxviii_o:nnnnnnnn {#1#2#3#4#5#6} {00000000} }
19949 \cs_new:Npn \__fp_sqrt_auxv_o:NNNNNw #1#2#3#4#5#6;
19950 { \__fp_sqrt_auxviii_o:nnnnnnnn {000#1#2#3#4#5} {#60000} }
19951 \cs_new:Npn \__fp_sqrt_auxvi_o:NNNNNw #1#2#3#4#5#6;
19952 { \__fp_sqrt_auxviii_o:nnnnnnnn {0000000#1} {#2#3#4#5#6} }
19953 \cs_new:Npn \__fp_sqrt_auxvii_o:NNNNNw #1#2#3#4#5#6;
19954 {
19955     \if_int_compare:w #1#2 = 0 \exp_stop_f:
19956     \exp_after:wN \__fp_sqrt_auxx_o:Nnnnnnnnn
19957     \fi:
19958     \__fp_sqrt_auxviii_o:nnnnnnnn {00000000} {000#1#2#3#4#5}
19959 }

```

(End definition for `__fp_sqrt_auxiii_o:wnnnnnnnn` and others.)

`__fp_sqrt_auxviii_o:nnnnnnnn` Simply add the two 8-digit blocks of z , aligned to the last four of the five 4-digit blocks of y , then call the `auxii` auxiliary to evaluate $y'^2 = (y + z)^2$.

```

19960 \cs_new:Npn \__fp_sqrt_auxviii_o:nnnnnnnn #1#2 #3#4#5#6#7
19961 {
19962     \exp_after:wN \__fp_sqrt_auxix_o:wnwnw
19963     \int_value:w \__fp_int_eval:w #3
19964     \exp_after:wN \__fp_basics_pack_low:NNNNNw
19965     \int_value:w \__fp_int_eval:w #1 + 1#4#5
19966     \exp_after:wN \__fp_basics_pack_low:NNNNNw
19967     \int_value:w \__fp_int_eval:w #2 + 1#6#7 ;
19968 }
19969 \cs_new:Npn \__fp_sqrt_auxix_o:wnwnw #1; #2#3; #4#5;
19970 {
19971     \__fp_sqrt_auxii_o:NnnnnnnnnN
19972     \__fp_sqrt_auxiii_o:wnnnnnnnnn {#1}{#2}{#3}{#4}{#5}
19973 }

```

(End definition for `__fp_sqrt_auxviii_o:nnnnnnnn` and `__fp_sqrt_auxix_o:wnwnw`.)

`__fp_sqrt_auxx_o:Nnnnnnnnn` At this stage, $j = 6$ and $10^{24}z < 10^7$, hence
`__fp_sqrt_auxxi_o:wnnnN`

$$10^7 + 1/2 > 10^{24}z + 1/2 \geq (10^{24}(a - y^2) - 258) \cdot (0.5 \cdot 10^8) / (10^8y + 1),$$

then $10^{24}(a - y^2) - 258 < 2(10^7 + 1/2)(y + 10^{-8})$, and

$$10^{24}(a - y^2) < (10^7 + 1290.5)(1 + 10^{-8}/y)(2y) < (10^7 + 1290.5)(1 + 10^{-7})(y + \sqrt{a}),$$

which finally implies $0 \leq \sqrt{a} - y < 0.2 \cdot 10^{-16}$. In particular, y is an underestimate of \sqrt{a} and $y + 0.5 \cdot 10^{-16}$ is a (strict) overestimate. There is at exactly one multiple m of $0.5 \cdot 10^{-16}$ in the interval $[y, y + 0.5 \cdot 10^{-16})$. If $m^2 > a$, then the square root is inexact and

is obtained by rounding $m - \epsilon$ to a multiple of 10^{-16} (the precise shift $0 < \epsilon < 0.5 \cdot 10^{-16}$ is irrelevant for rounding). If $m^2 = a$ then the square root is exactly m , and there is no rounding. If $m^2 < a$ then we round $m + \epsilon$. For now, discard a few irrelevant arguments #1, #2, #3, and find the multiple of $0.5 \cdot 10^{-16}$ within $[y, y + 0.5 \cdot 10^{-16})$; rather, only the last 4 digits #8 of y are considered, and we do not perform any carry yet. The `auxxi` auxiliary sets up `auxii` with a continuation function `auxxii` instead of `auxiii` as before. To prevent `auxii` from giving a negative results $a - m^2$, we compute $a + 10^{-16} - m^2$ instead, always positive since $m < \sqrt{a} + 0.5 \cdot 10^{-16}$ and $a \leq 1 - 10^{-16}$.

```

19974 \cs_new:Npn \__fp_sqrt_auxx_o:Nnnnnnnn #1#2#3 #4#5#6#7#8
19975 {
19976   \exp_after:wN \__fp_sqrt_auxxi_o:wwnnN
19977   \int_value:w \__fp_int_eval:w
19978     (#8 + 2499) / 5000 * 5000 ;
19979   {#4} {#5} {#6} {#7} ;
19980 }
19981 \cs_new:Npn \__fp_sqrt_auxxi_o:wwnnN #1; #2; #3#4#5
19982 {
19983   \__fp_sqrt_auxii_o:NnnnnnnnN
19984   \__fp_sqrt_auxxii_o:nnnnnnnnw
19985   #2 {#1}
19986   {#3} { #4 + 1 } #5
19987 }

```

(End definition for `__fp_sqrt_auxx_o:Nnnnnnnn` and `__fp_sqrt_auxxi_o:wwnnN`.)

`__fp_sqrt_auxxii_o:nnnnnnnnw`
`__fp_sqrt_auxxiii_o:w`

The difference $0 \leq a + 10^{-16} - m^2 \leq 10^{-16} + (\sqrt{a} - m)(\sqrt{a} + m) \leq 2 \cdot 10^{-16}$ was just computed: its first 8 digits vanish, as do the next four, #1, and most of the following four, #2. The guess m is an overestimate if $a + 10^{-16} - m^2 < 10^{-16}$, that is, #1#2 vanishes. Otherwise it is an underestimate, unless $a + 10^{-16} - m^2 = 10^{-16}$ exactly. For an underestimate, call the `auxxiv` function with argument 9998. For an exact result call it with 9999, and for an overestimate call it with 10000.

```

19988 \cs_new:Npn \__fp_sqrt_auxxii_o:nnnnnnnnw 0; #1#2#3#4#5#6#7#8 #9;
19989 {
19990   \if_int_compare:w #1#2 > 0 \exp_stop_f:
19991   \if_int_compare:w #1#2 = 1 \exp_stop_f:
19992   \if_int_compare:w #3#4 = 0 \exp_stop_f:
19993   \if_int_compare:w #5#6 = 0 \exp_stop_f:
19994   \if_int_compare:w #7#8 = 0 \exp_stop_f:
19995     \__fp_sqrt_auxxiii_o:w
19996   \fi:
19997   \fi:
19998   \fi:
19999   \fi:
20000   \exp_after:wN \__fp_sqrt_auxxiv_o:wnnnnnnnN
20001   \int_value:w 9998
20002 \else:
20003   \exp_after:wN \__fp_sqrt_auxxiv_o:wnnnnnnnN
20004   \int_value:w 10000
20005 \fi:
20006 ;
20007 }
20008 \cs_new:Npn \__fp_sqrt_auxxiii_o:w \fi: \fi: \fi: \fi: #1 \fi: ;
20009 {

```

```

20010      \fi: \fi: \fi: \fi: \fi:
20011      \__fp_sqrt_auxxiv_o:wnnnnnnnnN 9999 ;
20012    }

```

(End definition for `__fp_sqrt_auxxii_o:nnnnnnnnw` and `__fp_sqrt_auxxiii_o:w`.)

`__fp_sqrt_auxxiv_o:wnnnnnnnnN` This receives 9998, 9999 or 10000 as #1 when m is an underestimate, exact, or an overestimate, respectively. Then comes m as five blocks of 4 digits, but where the last block #6 may be 0, 5000, or 10000. In the latter case, we need to add a carry, unless m is an overestimate (#1 is then 10000). Then comes a as three arguments. Rounding is done by `__fp_round:NNN`, whose first argument is the final sign 0 (square roots are positive). We fake its second argument. It should be the last digit kept, but this is only used when ties are “rounded to even”, and only when the result is exactly half-way between two representable numbers rational square roots of numbers with 16 significant digits have: this situation never arises for the square root, as any exact square root of a 16 digit number has at most 8 significant digits. Finally, the last argument is the next digit, possibly shifted by 1 when there are further nonzero digits. This is achieved by `__fp_round_digit:Nw`, which receives (after removal of the 10000’s digit) one of 0000, 0001, 4999, 5000, 5001, or 9999, which it converts to 0, 1, 4, 5, 6, and 9, respectively.

```

20013 \cs_new:Npn \__fp_sqrt_auxxiv_o:wnnnnnnnnN #1; #2#3#4#5#6 #7#8#9
20014 {
20015   \exp_after:wN \__fp_basics_pack_high:NNNNNw
20016   \int_value:w \__fp_int_eval:w 1 0000 0000 + #2#3
20017   \exp_after:wN \__fp_basics_pack_low:NNNNNw
20018   \int_value:w \__fp_int_eval:w 1 0000 0000
20019   + #4#5
20020   \if_int_compare:w #6 > #1 \exp_stop_f: + 1 \fi:
20021   + \exp_after:wN \__fp_round:NNN
20022   \exp_after:wN 0
20023   \exp_after:wN 0
20024   \int_value:w
20025   \exp_after:wN \use_i:nn
20026   \exp_after:wN \__fp_round_digit:Nw
20027   \int_value:w \__fp_int_eval:w #6 + 19999 - #1 ;
20028   \exp_after:wN ;
20029 }

```

(End definition for `__fp_sqrt_auxxiv_o:wnnnnnnnnN`.)

31.5 About the sign and exponent

`__fp_logb_o:w` The exponent of a normal number is its *exponent* minus one.
`__fp_logb_aux_o:w`

```

20030 \cs_new:Npn \__fp_logb_o:w ? \s__fp \__fp_chk:w #1#2; @
20031 {
20032   \if_case:w #1 \exp_stop_f:
20033   \__fp_case_use:nw
20034   { \__fp_division_by_zero_o:Nnw \c_minus_inf_fp { logb } }
20035   \or: \exp_after:wN \__fp_logb_aux_o:w
20036   \or: \__fp_case_return_o:Nw \c_inf_fp
20037   \else: \__fp_case_return_same_o:w
20038   \fi:
20039   \s__fp \__fp_chk:w #1 #2;
20040 }

```

```

20041 \cs_new:Npn \__fp_logb_aux_o:w \s__fp \__fp_chk:w #1 #2 #3 #4 ;
20042 {
20043   \exp_after:wN \__fp_parse:n \exp_after:wN
20044     { \int_value:w \int_eval:w #3 - 1 \exp_after:wN }
20045 }

```

(End definition for __fp_logb_o:w and __fp_logb_aux_o:w.)

```

\__fp_sign_o:w Find the sign of the floating point: nan, +0, -0, +1 or -1.
\__fp_sign_aux_o:w
20046 \cs_new:Npn \__fp_sign_o:w ? \s__fp \__fp_chk:w #1#2; @
20047 {
20048   \if_case:w #1 \exp_stop_f:
20049     \__fp_case_return_same_o:w
20050   \or: \exp_after:wN \__fp_sign_aux_o:w
20051   \or: \exp_after:wN \__fp_sign_aux_o:w
20052   \else: \__fp_case_return_same_o:w
20053   \fi:
20054   \s__fp \__fp_chk:w #1 #2;
20055 }
20056 \cs_new:Npn \__fp_sign_aux_o:w \s__fp \__fp_chk:w #1 #2 #3 ;
20057 { \exp_after:wN \__fp_set_sign_o:w \exp_after:wN #2 \c_one_fp @ }

```

(End definition for __fp_sign_o:w and __fp_sign_aux_o:w.)

__fp_set_sign_o:w This function is used for the unary minus and for `abs`. It leaves the sign of `nan` invariant, turns negative numbers (sign 2) to positive numbers (sign 0) and positive numbers (sign 0) to positive or negative numbers depending on #1. It also expands after itself in the input stream, just like __fp_+o:ww.

```

20058 \cs_new:Npn \__fp_set_sign_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
20059 {
20060   \exp_after:wN \__fp_exp_after_o:w
20061   \exp_after:wN \s__fp
20062   \exp_after:wN \__fp_chk:w
20063   \exp_after:wN #2
20064   \int_value:w
20065   \if_case:w #3 \exp_stop_f: #1 \or: 1 \or: 0 \fi: \exp_stop_f:
20066   #4;
20067 }

```

(End definition for __fp_set_sign_o:w.)

31.6 Operations on tuples

__fp_tuple_set_sign_o:w Two cases: `abs(<tuple>)` for which #1 is 0 (invalid for tuples) and `-<tuple>` for which #1 is 2. In that case, map over all items in the tuple an auxiliary that dispatches to the type-appropriate sign-flipping function.

```

\__fp_tuple_set_sign_o:w
\__fp_tuple_set_sign_aux_o:Nnw
\__fp_tuple_set_sign_aux_o:w
20068 \cs_new:Npn \__fp_tuple_set_sign_o:w #1
20069 {
20070   \if_meaning:w 2 #1
20071     \exp_after:wN \__fp_tuple_set_sign_aux_o:Nnw
20072   \fi:
20073   \__fp_invalid_operation_o:nw { abs }
20074 }
20075 \cs_new:Npn \__fp_tuple_set_sign_aux_o:Nnw #1#2#3 @

```

```

20076 { \_fp_tuple_map_o:nw \_fp_tuple_set_sign_aux_o:w #3 }
20077 \cs_new:Npn \_fp_tuple_set_sign_aux_o:w #1#2 ;
20078 {
20079   \_fp_change_func_type:NNN #1 \_fp_set_sign_o:w
20080   \_fp_parse_apply_unary_error:NNw
20081   2 #1 #2 ; @
20082 }

```

(End definition for _fp_tuple_set_sign_o:w, _fp_tuple_set_sign_aux_o:Nnw, and _fp_tuple_set_sign_aux_o:w.)

_fp*_tuple_o:ww For $\langle number \rangle * \langle tuple \rangle$ and $\langle tuple \rangle * \langle number \rangle$ and $\langle tuple \rangle / \langle number \rangle$, loop through the
_fp_tuple*_o:ww $\langle tuple \rangle$ some code that multiplies or divides by the appropriate $\langle number \rangle$. Importantly
_fp_tuple/_o:ww we need to dispatch according to the type, and we make sure to apply the operator in
the correct order.

```

20083 \cs_new:cpn { \_fp*_tuple_o:ww } #1 ;
20084 { \_fp_tuple_map_o:nw { \_fp_binary_type_o:Nww * #1 ; } }
20085 \cs_new:cpn { \_fp_tuple*_o:ww } #1 ; #2 ;
20086 { \_fp_tuple_map_o:nw { \_fp_binary_rev_type_o:Nww * #2 ; } #1 ; }
20087 \cs_new:cpn { \_fp_tuple/_o:ww } #1 ; #2 ;
20088 { \_fp_tuple_map_o:nw { \_fp_binary_rev_type_o:Nww / #2 ; } #1 ; }

```

(End definition for _fp*_tuple_o:ww, _fp_tuple*_o:ww, and _fp_tuple/_o:ww.)

_fp_tuple+_tuple_o:ww Check the two tuples have the same number of items and map through these a helper
_fp_tuple-_tuple_o:ww that dispatches appropriately depending on the types. This means $(1,2) + ((1,1),2)$
gives $(\text{nan},4)$.

```

20089 \cs_set_protected:Npn \_fp_tmp:w #1
20090 {
20091   \cs_new:cpn { \_fp_tuple_#1_tuple_o:ww }
20092   \s_fp_tuple \_fp_tuple_chk:w ##1 ;
20093   \s_fp_tuple \_fp_tuple_chk:w ##2 ;
20094   {
20095     \int_compare:nNnTF
20096     { \_fp_array_count:n {##1} } = { \_fp_array_count:n {##2} }
20097     { \_fp_tuple_mapthread_o:nww { \_fp_binary_type_o:Nww #1 } }
20098     { \_fp_invalid_operation_o:nww #1 }
20099     \s_fp_tuple \_fp_tuple_chk:w {##1} ;
20100     \s_fp_tuple \_fp_tuple_chk:w {##2} ;
20101   }
20102 }
20103 \_fp_tmp:w +
20104 \_fp_tmp:w -

```

(End definition for _fp_tuple+_tuple_o:ww and _fp_tuple-_tuple_o:ww.)

```

20105 </initex | package>

```

32 l3fp-extended implementation

```

20106 (*initex | package)
20107 <@@=fp>

```

32.1 Description of fixed point numbers

This module provides a few functions to manipulate positive floating point numbers with extended precision (24 digits), but mostly provides functions for fixed-point numbers with this precision (24 digits). Those are used in the computation of Taylor series for the logarithm, exponential, and trigonometric functions. Since we eventually only care about the 16 first digits of the final result, some of the calculations are not performed with the full 24-digit precision. In other words, the last two blocks of each fixed point number may be wrong as long as the error is small enough to be rounded away when converting back to a floating point number. The fixed point numbers are expressed as

$$\{\langle a_1 \rangle\} \{\langle a_2 \rangle\} \{\langle a_3 \rangle\} \{\langle a_4 \rangle\} \{\langle a_5 \rangle\} \{\langle a_6 \rangle\} ;$$

where each $\langle a_i \rangle$ is exactly 4 digits (ranging from 0000 to 9999), except $\langle a_1 \rangle$, which may be any “not-too-large” non-negative integer, with or without leading zeros. Here, “not-too-large” depends on the specific function (see the corresponding comments for details). Checking for overflow is the responsibility of the code calling those functions. The fixed point number a corresponding to the representation above is $a = \sum_{i=1}^6 \langle a_i \rangle \cdot 10^{-4i}$.

Most functions we define here have the form

```
\__fp_fixed_⟨calculation⟩:wnn ⟨operand1⟩ ; ⟨operand2⟩ ; {⟨continuation⟩}
```

They perform the $\langle calculation \rangle$ on the two $\langle operands \rangle$, then feed the result (6 brace groups followed by a semicolon) to the $\langle continuation \rangle$, responsible for the next step of the calculation. Some functions only accept an N-type $\langle continuation \rangle$. This allows constructions such as

```
\__fp_fixed_add:wnn ⟨X1⟩ ; ⟨X2⟩ ;
\__fp_fixed_mul:wnn ⟨X3⟩ ;
\__fp_fixed_add:wnn ⟨X4⟩ ;
```

to compute $(X_1 + X_2) \cdot X_3 + X_4$. This turns out to be very appropriate for computing continued fractions and Taylor series.

At the end of the calculation, the result is turned back to a floating point number using `__fp_fixed_to_float_o:wn`. This function has to change the exponent of the floating point number: it must be used after starting an integer expression for the overall exponent of the result.

32.2 Helpers for numbers with extended precision

`\c__fp_one_fixed_t1` The fixed-point number 1, used in `l3fp-expo`.

```
20108 \tl_const:Nn \c__fp_one_fixed_t1
20109 { {10000} {0000} {0000} {0000} {0000} {0000} ; }
```

(End definition for `\c__fp_one_fixed_t1`.)

`__fp_fixed_continue:wn` This function simply calls the next function.

```
20110 \cs_new:Npn \__fp_fixed_continue:wn #1; #2 { #2 #1; }
```

(End definition for `__fp_fixed_continue:wn`.)

`__fp_fixed_add_one:wn`

`__fp_fixed_add_one:wn <a> ; <continuation>`

This function adds 1 to the fixed point $\langle a \rangle$, by changing a_1 to $10000 + a_1$, then calls the $\langle continuation \rangle$. This requires $a_1 + 10000 < 2^{31}$.

```
20111 \cs_new:Npn \__fp_fixed_add_one:wn #1#2; #3
20112 {
20113   \exp_after:wn #3 \exp_after:wn
20114   { \int_value:w \__fp_int_eval:w \c__fp_myriad_int + #1 } #2 ;
20115 }
```

(End definition for `__fp_fixed_add_one:wn`.)

`__fp_fixed_div_myriad:wn`

Divide a fixed point number by 10000. This is a little bit more subtle than just removing the last group and adding a leading group of zeros: the first group #1 may have any number of digits, and we must split #1 into the new first group and a second group of exactly 4 digits. The choice of shifts allows #1 to be in the range $[0, 5 \cdot 10^8 - 1]$.

```
20116 \cs_new:Npn \__fp_fixed_div_myriad:wn #1#2#3#4#5#6;
20117 {
20118   \exp_after:wn \__fp_fixed_mul_after:wnn
20119   \int_value:w \__fp_int_eval:w \c__fp_leading_shift_int
20120   \exp_after:wn \__fp_pack:NNNNnw
20121   \int_value:w \__fp_int_eval:w \c__fp_trailing_shift_int
20122   + #1 ; {#2}{#3}{#4}{#5};
20123 }
```

(End definition for `__fp_fixed_div_myriad:wn`.)

`__fp_fixed_mul_after:wnn`

The fixed point operations which involve multiplication end by calling this auxiliary. It braces the last block of digits, and places the $\langle continuation \rangle$ #3 in front.

```
20124 \cs_new:Npn \__fp_fixed_mul_after:wnn #1; #2; #3 { #3 {#1} #2; }
```

(End definition for `__fp_fixed_mul_after:wnn`.)

32.3 Multiplying a fixed point number by a short one

`__fp_fixed_mul_short:wnn`

```
\__fp_fixed_mul_short:wnn
{ \langle a_1 \rangle \langle a_2 \rangle \langle a_3 \rangle \langle a_4 \rangle \langle a_5 \rangle \langle a_6 \rangle ;
  \langle b_0 \rangle \langle b_1 \rangle \langle b_2 \rangle ; \langle continuation \rangle }
```

Computes the product $c = ab$ of $a = \sum_i \langle a_i \rangle 10^{-4i}$ and $b = \sum_i \langle b_i \rangle 10^{-4i}$, rounds it to the closest multiple of 10^{-24} , and leaves $\langle continuation \rangle \{ \langle c_1 \rangle \} \dots \{ \langle c_6 \rangle \}$; in the input stream, where each of the $\langle c_i \rangle$ are blocks of 4 digits, except $\langle c_1 \rangle$, which is any \TeX integer. Note that indices for $\langle b \rangle$ start at 0: for instance a second operand of $\{0001\}\{0000\}\{0000\}$ leaves the first operand unchanged (rather than dividing it by 10^4 , as `__fp_fixed_mul:wnn` would).

```
20125 \cs_new:Npn \__fp_fixed_mul_short:wnn #1#2#3#4#5#6; #7#8#9;
20126 {
20127   \exp_after:wn \__fp_fixed_mul_after:wnn
20128   \int_value:w \__fp_int_eval:w \c__fp_leading_shift_int
20129   + #1*#7
20130   \exp_after:wn \__fp_pack:NNNNnw
20131   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
20132   + #1*#8 + #2*#7
20133   \exp_after:wn \__fp_pack:NNNNnw
20134   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
```



```

20135         + #1*#9 + #2*#8 + #3*#7
20136         \exp_after:wN \__fp_pack:NNNNNw
20137         \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
20138         + #2*#9 + #3*#8 + #4*#7
20139         \exp_after:wN \__fp_pack:NNNNNw
20140         \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
20141         + #3*#9 + #4*#8 + #5*#7
20142         \exp_after:wN \__fp_pack:NNNNNw
20143         \int_value:w \__fp_int_eval:w \c__fp_trailing_shift_int
20144         + #4*#9 + #5*#8 + #6*#7
20145         + ( #5*#9 + #6*#8 + #6*#9 / \c__fp_myriad_int )
20146         / \c__fp_myriad_int ; ;
20147     }

```

(End definition for __fp_fixed_mul_short:wnn.)

32.4 Dividing a fixed point number by a small integer

```

\__fp_fixed_div_int:wnN \__fp_fixed_div_int:wnN <a> ; <n> ; <continuation>

```

Divides the fixed point number $\langle a \rangle$ by the (small) integer $0 < \langle n \rangle < 10^4$ and feeds the result to the $\langle continuation \rangle$. There is no bound on a_1 .

```

\__fp_fixed_div_int_auxi:wnn

```

The arguments of the **i** auxiliary are 1: one of the a_i , 2: n , 3: the **ii** or the **iii** auxiliary. It computes a (somewhat tight) lower bound Q_i for the ratio a_i/n .

```

\__fp_fixed_div_int_pack:Nw

```

The **ii** auxiliary receives Q_i , n , and a_i as arguments. It adds Q_i to a surrounding integer expression, and starts a new one with the initial value 9999, which ensures that the result of this expression has 5 digits. The auxiliary also computes $a_i - n \cdot Q_i$, placing the result in front of the 4 digits of a_{i+1} . The resulting $a'_{i+1} = 10^4(a_i - n \cdot Q_i) + a_{i+1}$ serves as the first argument for a new call to the **i** auxiliary.

```

\__fp_fixed_div_int_after:Nw

```

When the **iii** auxiliary is called, the situation looks like this:

```

\__fp_fixed_div_int_after:Nw <continuation>
-1 + Q1
\__fp_fixed_div_int_pack:Nw 9999 + Q2
\__fp_fixed_div_int_pack:Nw 9999 + Q3
\__fp_fixed_div_int_pack:Nw 9999 + Q4
\__fp_fixed_div_int_pack:Nw 9999 + Q5
\__fp_fixed_div_int_pack:Nw 9999
\__fp_fixed_div_int_auxii:wnn Q6 ; {<n>} {<a6

```

where expansion is happening from the last line up. The **iii** auxiliary adds $Q_6 + 2 \simeq a_6/n + 1$ to the last 9999, giving the integer closest to $10000 + a_6/n$.

Each **pack** auxiliary receives 5 digits followed by a semicolon. The first digit is added as a carry to the integer expression above, and the 4 other digits are braced. Each call to the **pack** auxiliary thus produces one brace group. The last brace group is produced by the **after** auxiliary, which places the $\langle continuation \rangle$ as appropriate.

```

20148 \cs_new:Npn \__fp_fixed_div_int:wnN #1#2#3#4#5#6 ; #7 ; #8
20149 {
20150     \exp_after:wN \__fp_fixed_div_int_after:Nw
20151     \exp_after:wN #8
20152     \int_value:w \__fp_int_eval:w - 1
20153     \__fp_fixed_div_int:wnN
20154     #1; {#7} \__fp_fixed_div_int_auxi:wnn

```

```

20155     #2; {#7} \__fp_fixed_div_int_auxi:wnn
20156     #3; {#7} \__fp_fixed_div_int_auxi:wnn
20157     #4; {#7} \__fp_fixed_div_int_auxi:wnn
20158     #5; {#7} \__fp_fixed_div_int_auxi:wnn
20159     #6; {#7} \__fp_fixed_div_int_auxii:wnn ;
20160 }
20161 \cs_new:Npn \__fp_fixed_div_int:wnN #1; #2 #3
20162 {
20163     \exp_after:wN #3
20164     \int_value:w \__fp_int_eval:w #1 / #2 - 1 ;
20165     {#2}
20166     {#1}
20167 }
20168 \cs_new:Npn \__fp_fixed_div_int_auxi:wnn #1; #2 #3
20169 {
20170     + #1
20171     \exp_after:wN \__fp_fixed_div_int_pack:Nw
20172     \int_value:w \__fp_int_eval:w 9999
20173     \exp_after:wN \__fp_fixed_div_int:wnN
20174     \int_value:w \__fp_int_eval:w #3 - #1*#2 \__fp_int_eval_end:
20175 }
20176 \cs_new:Npn \__fp_fixed_div_int_auxii:wnn #1; #2 #3 { + #1 + 2 ; }
20177 \cs_new:Npn \__fp_fixed_div_int_pack:Nw #1 #2; { + #1; {#2} }
20178 \cs_new:Npn \__fp_fixed_div_int_after:Nw #1 #2; { #1 {#2} }

```

(End definition for `__fp_fixed_div_int:wnN` and others.)

32.5 Adding and subtracting fixed points

`__fp_fixed_add:wnn` `__fp_fixed_add:wnn <a> ; ; {<continuation>}`
`__fp_fixed_sub:wnn` Computes $a + b$ (resp. $a - b$) and feeds the result to the $\langle continuation \rangle$. This function
`__fp_fixed_add:Nnnnnwnn` requires $0 \leq a_1, b_1 \leq 114748$, its result must be positive (this happens automatically for
`__fp_fixed_add:nnNnnwnn` addition) and its first group must have at most 5 digits: $(a \pm b)_1 < 100000$. The two
`__fp_fixed_add_pack:NNNNNwn` functions only differ by a sign, hence use a common auxiliary. It would be nice to grab
`__fp_fixed_add_after:NNNNNwn` the 12 brace groups in one go; only 9 parameters are allowed. Start by grabbing the sign,
 a_1, \dots, a_4 , the rest of a , and b_1 and b_2 . The second auxiliary receives the rest of a , the
 sign multiplying b , the rest of b , and the $\langle continuation \rangle$ as arguments. After going down
 through the various level, we go back up, packing digits and bringing the $\langle continuation \rangle$
 (#8, then #7) from the end of the argument list to its start.

```

20179 \cs_new:Npn \__fp_fixed_add:wnn { \__fp_fixed_add:Nnnnnwnn + }
20180 \cs_new:Npn \__fp_fixed_sub:wnn { \__fp_fixed_add:Nnnnnwnn - }
20181 \cs_new:Npn \__fp_fixed_add:Nnnnnwnn #1 #2#3#4#5 #6; #7#8
20182 {
20183     \exp_after:wN \__fp_fixed_add_after:NNNNNwn
20184     \int_value:w \__fp_int_eval:w 9 9999 9998 + #2#3 #1 #7#8
20185     \exp_after:wN \__fp_fixed_add_pack:NNNNNwn
20186     \int_value:w \__fp_int_eval:w 1 9999 9998 + #4#5
20187     \__fp_fixed_add:nnNnnwn #6 #1
20188 }
20189 \cs_new:Npn \__fp_fixed_add:nnNnnwn #1#2 #3 #4#5 #6#7 ; #8
20190 {
20191     #3 #4#5
20192     \exp_after:wN \__fp_fixed_add_pack:NNNNNwn

```

```

20193 \int_value:w \__fp_int_eval:w 2 0000 0000 #3 #6#7 + #1#2 ; {#8} ;
20194 }
20195 \cs_new:Npn \__fp_fixed_add_pack:NNNNNwn #1 #2#3#4#5 #6; #7
20196 { + #1 ; {#7} {#2#3#4#5} {#6} }
20197 \cs_new:Npn \__fp_fixed_add_after:NNNNNwn 1 #1 #2#3#4#5 #6; #7
20198 { #7 {#1#2#3#4#5} {#6} }

```

(End definition for `__fp_fixed_add:wnn` and others.)

32.6 Multiplying fixed points

```

\__fp_fixed_mul:wnn
\__fp_fixed_mul:nnnnnnnw

```

`__fp_fixed_mul:wnn` $\langle a \rangle$; $\langle b \rangle$; $\{\langle continuation \rangle\}$

Computes $a \times b$ and feeds the result to $\langle continuation \rangle$. This function requires $0 \leq a_1, b_1 < 10000$. Once more, we need to play around the limit of 9 arguments for $\text{T}_{\text{E}}\text{X}$ macros. Note that we don't need to obtain an exact rounding, contrarily to the `*` operator, so things could be harder. We wish to perform carries in

$$\begin{aligned}
a \times b = & a_1 \cdot b_1 \cdot 10^{-8} \\
& + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\
& + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1) \cdot 10^{-16} \\
& + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\
& + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\
& \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\
& \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 \right) \cdot 10^{-24} + O(10^{-24}),
\end{aligned}$$

where the $O(10^{-24})$ stands for terms which are at most $5 \cdot 10^{-24}$; ignoring those leads to an error of at most 5 ulp. Note how the first 15 terms only depend on a_1, \dots, a_4 and b_1, \dots, b_4 , while the last 6 terms only depend on a_1, a_2, a_5, a_6 , and the corresponding parts of b . Hence, the first function grabs a_1, \dots, a_4 , the rest of a , and b_1, \dots, b_4 , and writes the 15 first terms of the expression, including a left parenthesis for the fraction. The `i` auxiliary receives $a_5, a_6, b_1, b_2, a_1, a_2, b_5, b_6$ and finally the $\langle continuation \rangle$ as arguments. It writes the end of the expression, including the right parenthesis and the denominator of the fraction. The $\langle continuation \rangle$ is finally placed in front of the 6 brace groups by `__fp_fixed_mul_after:wnn`.

```

20199 \cs_new:Npn \__fp_fixed_mul:wnn #1#2#3#4 #5; #6#7#8#9
20200 {
20201   \exp_after:wN \__fp_fixed_mul_after:wnn
20202   \int_value:w \__fp_int_eval:w \c__fp_leading_shift_int
20203   \exp_after:wN \__fp_pack:NNNNNw
20204   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
20205   + #1*#6
20206   \exp_after:wN \__fp_pack:NNNNNw
20207   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
20208   + #1*#7 + #2*#6
20209   \exp_after:wN \__fp_pack:NNNNNw
20210   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
20211   + #1*#8 + #2*#7 + #3*#6
20212   \exp_after:wN \__fp_pack:NNNNNw

```

```

20213         \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
20214         + #1*#9 + #2*#8 + #3*#7 + #4*#6
20215         \exp_after:wN \__fp_pack:NNNNNw
20216         \int_value:w \__fp_int_eval:w \c__fp_trailing_shift_int
20217         + #2*#9 + #3*#8 + #4*#7
20218         + ( #3*#9 + #4*#8
20219         + \__fp_fixed_mul:nnnnnnnw #5 {#6}{#7} {#1}{#2}
20220     }
20221 \cs_new:Npn \__fp_fixed_mul:nnnnnnnw #1#2 #3#4 #5#6 #7#8 ;
20222 {
20223     #1*#4 + #2*#3 + #5*#8 + #6*#7 ) / \c__fp_myriad_int
20224     + #1*#3 + #5*#7 ; ;
20225 }

```

(End definition for `__fp_fixed_mul:wnn` and `__fp_fixed_mul:nnnnnnnw`.)

32.7 Combining product and sum of fixed points

```

\__fp_fixed_mul_add:wwwn
\__fp_fixed_mul_sub_back:wwwn
\__fp_fixed_one_minus_mul:wnn

```

Sometimes called FMA (fused multiply-add), these functions compute $a \times b + c$, $c - a \times b$, and $1 - a \times b$ and feed the result to the `\langle continuation \rangle`. Those functions require $0 \leq a_1, b_1, c_1 \leq 10000$. Since those functions are at the heart of the computation of Taylor expansions, we over-optimize them a bit, and in particular we do not factor out the common parts of the three functions.

For definiteness, consider the task of computing $a \times b + c$. We perform carries in

$$\begin{aligned}
 a \times b + c = & (a_1 \cdot b_1 + c_1 c_2) \cdot 10^{-8} \\
 & + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\
 & + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4) \cdot 10^{-16} \\
 & + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\
 & + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\
 & \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\
 & \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 + c_5 c_6 \right) \cdot 10^{-24} + O(10^{-24}),
 \end{aligned}$$

where $c_1 c_2$, $c_3 c_4$, $c_5 c_6$ denote the 8-digit number obtained by juxtaposing the two blocks of digits of c , and \cdot denotes multiplication. The task is obviously tough because we have 18 brace groups in front of us.

Each of the three function starts the first two levels (the first, corresponding to 10^{-4} , is empty), with $c_1 c_2$ in the first level, calls the `i` auxiliary with arguments described later, and adds a trailing $+ c_5 c_6 ; \{\langle continuation \rangle\}$; . The $+ c_5 c_6$ piece, which is omitted for `__fp_fixed_one_minus_mul:wnn`, is taken in the integer expression for the 10^{-24} level.

```

20226 \cs_new:Npn \__fp_fixed_mul_add:wwwn #1; #2; #3#4#5#6#7#8;
20227 {
20228     \exp_after:wN \__fp_fixed_mul_after:wwn
20229     \int_value:w \__fp_int_eval:w \c__fp_big_leading_shift_int
20230     \exp_after:wN \__fp_pack_big:NNNNNNw

```

```

20231      \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int + #3 #4
20232      \_fp_fixed_mul_add:Nwnnnwnnn +
20233      + #5 #6 ; #2 ; #1 ; #2 ; +
20234      + #7 #8 ; ;
20235    }
20236 \cs_new:Npn \_fp_fixed_mul_sub_back:wwn #1; #2; #3#4#5#6#7#8;
20237 {
20238   \exp_after:wN \_fp_fixed_mul_after:wwn
20239   \int_value:w \_fp_int_eval:w \c\_fp_big_leading_shift_int
20240   \exp_after:wN \_fp_pack_big:NNNNNNw
20241   \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int + #3 #4
20242   \_fp_fixed_mul_add:Nwnnnwnnn -
20243   + #5 #6 ; #2 ; #1 ; #2 ; -
20244   + #7 #8 ; ;
20245 }
20246 \cs_new:Npn \_fp_fixed_one_minus_mul:wwn #1; #2;
20247 {
20248   \exp_after:wN \_fp_fixed_mul_after:wwn
20249   \int_value:w \_fp_int_eval:w \c\_fp_big_leading_shift_int
20250   \exp_after:wN \_fp_pack_big:NNNNNNw
20251   \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int +
20252   1 0000 0000
20253   \_fp_fixed_mul_add:Nwnnnwnnn -
20254   ; #2 ; #1 ; #2 ; -
20255   ; ;
20256 }

```

(End definition for `_fp_fixed_mul_add:wwn`, `_fp_fixed_mul_sub_back:wwn`, and `_fp_fixed_mul_one_minus_mul:wwn`.)

```

\_fp_fixed_mul_add:Nwnnnwnnn
      \_fp_fixed_mul_add:Nwnnnwnnn <op> + <c3> <c4> ;
      <b> ; <a> ; <b> ; <op>
      + <c5> <c6> ;

```

Here, `<op>` is either `+` or `-`. Arguments `#3`, `#4`, `#5` are $\langle b_1 \rangle$, $\langle b_2 \rangle$, $\langle b_3 \rangle$; arguments `#7`, `#8`, `#9` are $\langle a_1 \rangle$, $\langle a_2 \rangle$, $\langle a_3 \rangle$. We can build three levels: $a_1 \cdot b_1$ for 10^{-8} , $(a_1 \cdot b_2 + a_2 \cdot b_1)$ for 10^{-12} , and $(a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4)$ for 10^{-16} . The a - b products use the sign `#1`. Note that `#2` is empty for `_fp_fixed_one_minus_mul:wwn`. We call the `ii` auxiliary for levels 10^{-20} and 10^{-24} , keeping the pieces of $\langle a \rangle$ we've read, but not $\langle b \rangle$, since there is another copy later in the input stream.

```

20257 \cs_new:Npn \_fp_fixed_mul_add:Nwnnnwnnn #1 #2; #3#4#5#6; #7#8#9
20258 {
20259   #1 #7*#3
20260   \exp_after:wN \_fp_pack_big:NNNNNNw
20261   \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int
20262   #1 #7*#4 #1 #8*#3
20263   \exp_after:wN \_fp_pack_big:NNNNNNw
20264   \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int
20265   #1 #7*#5 #1 #8*#4 #1 #9*#3 #2
20266   \exp_after:wN \_fp_pack_big:NNNNNNw
20267   \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int
20268   #1 \_fp_fixed_mul_add:nnnnwnnn {#7}{#8}{#9}
20269 }

```

(End definition for `_fp_fixed_mul_add:Nwnnnwnnn`.)

_fp_fixed_mul_add:nnnnwnnnn

_fp_fixed_mul_add:nnnnwnnnn $\langle a \rangle$; $\langle b \rangle$; $\langle op \rangle$
 $+ \langle c_5 \rangle \langle c_6 \rangle$;

Level 10^{-20} is $(a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1)$, multiplied by the sign, which was inserted by the *i* auxiliary. Then we prepare level 10^{-24} . We don't have access to all parts of $\langle a \rangle$ and $\langle b \rangle$ needed to make all products. Instead, we prepare the partial expressions

$$b_1 + a_4 \cdot b_2 + a_3 \cdot b_3 + a_2 \cdot b_4 + a_1$$

$$b_2 + a_4 \cdot b_3 + a_3 \cdot b_4 + a_2.$$

Obviously, those expressions make no mathematical sense: we complete them with $a_5 \cdot$ and $\cdot b_5$, and with $a_6 \cdot b_1 + a_5 \cdot$ and $\cdot b_5 + a_1 \cdot b_6$, and of course with the trailing $+ c_5 c_6$. To do all this, we keep a_1, a_5, a_6 , and the corresponding pieces of $\langle b \rangle$.

```

20270 \cs_new:Npn \_fp_fixed_mul_add:nnnnwnnnn #1#2#3#4#5; #6#7#8#9
20271 {
20272   ( #1*#9 + #2*#8 + #3*#7 + #4*#6 )
20273   \exp_after:wN \_fp_pack_big:NNNNNNw
20274   \int_value:w \_fp_int_eval:w \c__fp_big_trailing_shift_int
20275   \_fp_fixed_mul_add:nnnnwnnwN
20276   { #6 + #4*#7 + #3*#8 + #2*#9 + #1 }
20277   { #7 + #4*#8 + #3*#9 + #2 }
20278   {#1} #5;
20279   {#6}
20280 }

```

(End definition for _fp_fixed_mul_add:nnnnwnnnn.)

_fp_fixed_mul_add:nnnnwnnwN

_fp_fixed_mul_add:nnnnwnnwN $\{\langle partial_1 \rangle\} \{\langle partial_2 \rangle\}$
 $\{\langle a_1 \rangle\} \{\langle a_5 \rangle\} \{\langle a_6 \rangle\}$; $\{\langle b_1 \rangle\} \{\langle b_5 \rangle\} \{\langle b_6 \rangle\}$;
 $\langle op \rangle + \langle c_5 \rangle \langle c_6 \rangle$;

Complete the $\langle partial_1 \rangle$ and $\langle partial_2 \rangle$ expressions as explained for the *ii* auxiliary. The second one is divided by 10000: this is the carry from level 10^{-28} . The trailing $+ c_5 c_6$ is taken into the expression for level 10^{-24} . Note that the total of level 10^{-24} is in the interval $[-5 \cdot 10^8, 6 \cdot 10^8]$ (give or take a couple of 10000), hence adding it to the shift gives a 10-digit number, as expected by the packing auxiliaries. See *l3fp-aux* for the definition of the shifts and packing auxiliaries.

```

20281 \cs_new:Npn \_fp_fixed_mul_add:nnnnwnnwN #1#2 #3#4#5; #6#7#8; #9
20282 {
20283   #9 (#4* #1 *#7)
20284   #9 (#5*#6+#4* #2 *#7+#3*#8) / \c__fp_myriad_int
20285 }

```

(End definition for _fp_fixed_mul_add:nnnnwnnwN.)

32.8 Extended-precision floating point numbers

In this section we manipulate floating point numbers with roughly 24 significant figures (“extended-precision” numbers, in short, “ep”), which take the form of an integer exponent, followed by a comma, then six groups of digits, ending with a semicolon. The first group of digit may be any non-negative integer, while other groups of digits have 4 digits. In other words, an extended-precision number is an exponent ending in a comma, then a fixed point number. The corresponding value is $0.\langle digits \rangle \cdot 10^{\langle exponent \rangle}$. This convention differs from floating points.

`__fp_ep_to_fixed:wwn` Converts an extended-precision number with an exponent at most 4 and a first block less than 10^8 to a fixed point number whose first block has 12 digits, hopefully starting with many zeros.
`__fp_ep_to_fixed_auxi:www`
`__fp_ep_to_fixed_auxii:nnnnnnnwn`

```

20286 \cs_new:Npn __fp_ep_to_fixed:wwn #1,#2
20287 {
20288   \exp_after:wN __fp_ep_to_fixed_auxi:www
20289   \int_value:w __fp_int_eval:w 1 0000 0000 + #2 \exp_after:wN ;
20290   \exp:w \exp_end_continue_f:w
20291   \prg_replicate:nn { 4 - \int_max:nn {#1} { -32 } } { 0 } ;
20292 }
20293 \cs_new:Npn __fp_ep_to_fixed_auxi:www #1; #2; #3#4#5#6#7;
20294 {
20295   __fp_pack_eight:wnnnnnnnn
20296   __fp_pack_twice_four:wnnnnnnnn
20297   __fp_pack_twice_four:wnnnnnnnn
20298   __fp_pack_twice_four:wnnnnnnnn
20299   __fp_ep_to_fixed_auxii:nnnnnnnwn ;
20300   #2 #1#3#4#5#6#7 0000 !
20301 }
20302 \cs_new:Npn __fp_ep_to_fixed_auxii:nnnnnnnwn #1#2#3#4#5#6#7; #8! #9
20303 { #9 {#1#2}{#3}{#4}{#5}{#6}{#7}; }

```

(End definition for `__fp_ep_to_fixed:wwn`, `__fp_ep_to_fixed_auxi:www`, and `__fp_ep_to_fixed_auxii:nnnnnnnwn`.)

`__fp_ep_to_ep:wwN` Normalize an extended-precision number. More precisely, leading zeros are removed from the mantissa of the argument, decreasing its exponent as appropriate. Then the digits are packed into 6 groups of 4 (discarding any remaining digit, not rounding). Finally, the continuation #8 is placed before the resulting exponent-mantissa pair. The input exponent may in fact be given as an integer expression. The `loop` auxiliary grabs a digit: if it is 0, decrement the exponent and continue looping, and otherwise call the `end` auxiliary, which places all digits in the right order (the digit that was not 0, and any remaining digits), followed by some 0, then packs them up neatly in $3 \times 2 = 6$ blocks of four. At the end of the day, remove with `__fp_use_i:ww` any digit that did not make it in the final mantissa (typically only zeros, unless the original first block has more than 4 digits).
`__fp_ep_to_ep_loop:N`
`__fp_ep_to_ep_end:www`
`__fp_ep_to_ep_zero:ww`

```

20304 \cs_new:Npn __fp_ep_to_ep:wwN #1,#2#3#4#5#6#7; #8
20305 {
20306   \exp_after:wN #8
20307   \int_value:w __fp_int_eval:w #1 + 4
20308   \exp_after:wN \use_i:nn
20309   \exp_after:wN __fp_ep_to_ep_loop:N
20310   \int_value:w __fp_int_eval:w 1 0000 0000 + #2 __fp_int_eval_end:
20311   #3#4#5#6#7 ; ; !
20312 }
20313 \cs_new:Npn __fp_ep_to_ep_loop:N #1
20314 {
20315   \if_meaning:w 0 #1
20316   - 1
20317   \else:
20318     __fp_ep_to_ep_end:www #1
20319   \fi:
20320   __fp_ep_to_ep_loop:N

```

```

20321 }
20322 \cs_new:Npn \__fp_ep_to_ep_end:www
20323   #1 \fi: \__fp_ep_to_ep_loop:N #2; #3!
20324 {
20325   \fi:
20326   \if_meaning:w ; #1
20327     - 2 * \c_fp_max_exponent_int
20328     \__fp_ep_to_ep_zero:ww
20329   \fi:
20330   \__fp_pack_twice_four:wNNNNNNNN
20331   \__fp_pack_twice_four:wNNNNNNNN
20332   \__fp_pack_twice_four:wNNNNNNNN
20333   \__fp_use_i:ww , ;
20334   #1 #2 0000 0000 0000 0000 0000 0000 ;
20335 }
20336 \cs_new:Npn \__fp_ep_to_ep_zero:ww \fi: #1; #2; #3;
20337 { \fi: , {1000}{0000}{0000}{0000}{0000}{0000} ; }

```

(End definition for __fp_ep_to_ep:wwN and others.)

__fp_ep_compare:www
__fp_ep_compare_aux:www

In l3fp-trig we need to compare two extended-precision numbers. This is based on the same function for positive floating point numbers, with an extra test if comparing only 16 decimals is not enough to distinguish the numbers. Note that this function only works if the numbers are normalized so that their first block is in [1000,9999].

```

20338 \cs_new:Npn \__fp_ep_compare:www #1,#2#3#4#5#6#7;
20339 { \__fp_ep_compare_aux:www {#1}{#2}{#3}{#4}{#5}; #6#7; }
20340 \cs_new:Npn \__fp_ep_compare_aux:www #1;#2;#3;#4#5#6#7#8#9;
20341 {
20342   \if_case:w
20343     \__fp_compare_npos:nwnw #1; {#3}{#4}{#5}{#6}{#7}; \exp_stop_f:
20344     \if_int_compare:w #2 = #8#9 \exp_stop_f:
20345       0
20346     \else:
20347       \if_int_compare:w #2 < #8#9 - \fi: 1
20348     \fi:
20349   \or: 1
20350   \else: -1
20351   \fi:
20352 }

```

(End definition for __fp_ep_compare:www and __fp_ep_compare_aux:www.)

__fp_ep_mul:wwwN
__fp_ep_mul_raw:wwwN

Multiply two extended-precision numbers: first normalize them to avoid losing too much precision, then multiply the mantissas #2 and #4 as fixed point numbers, and sum the exponents #1 and #3. The result's first block is in [100,9999].

```

20353 \cs_new:Npn \__fp_ep_mul:wwwN #1,#2; #3,#4;
20354 {
20355   \__fp_ep_to_ep:wwN #3,#4;
20356   \__fp_fixed_continue:wn
20357   {
20358     \__fp_ep_to_ep:wwN #1,#2;
20359     \__fp_ep_mul_raw:wwwN
20360   }
20361   \__fp_fixed_continue:wn

```



```

20362 }
20363 \cs_new:Npn \__fp_ep_mul_raw:wwwN #1,#2; #3,#4; #5
20364 {
20365   \__fp_fixed_mul:wn #2; #4;
20366   { \exp_after:wN #5 \int_value:w \__fp_int_eval:w #1 + #3 , }
20367 }

```

(End definition for `__fp_ep_mul:wwwN` and `__fp_ep_mul_raw:wwwN`.)

32.9 Dividing extended-precision numbers

Divisions of extended-precision numbers are difficult to perform with exact rounding: the technique used in `l3fp-basics` for 16-digit floating point numbers does not generalize easily to 24-digit numbers. Thankfully, there is no need for exact rounding.

Let us call $\langle n \rangle$ the numerator and $\langle d \rangle$ the denominator. After a simple normalization step, we can assume that $\langle n \rangle \in [0.1, 1)$ and $\langle d \rangle \in [0.1, 1)$, and compute $\langle n \rangle / (10 \langle d \rangle) \in (0.01, 1)$. In terms of the 6 blocks of digits $\langle n_1 \rangle \cdots \langle n_6 \rangle$ and the 6 blocks $\langle d_1 \rangle \cdots \langle d_6 \rangle$, the condition translates to $\langle n_1 \rangle, \langle d_1 \rangle \in [1000, 9999]$.

We first find an integer estimate $a \simeq 10^8 / \langle d \rangle$ by computing

$$\alpha = \left\lceil \frac{10^9}{\langle d_1 \rangle + 1} \right\rceil$$

$$\beta = \left\lfloor \frac{10^9}{\langle d_1 \rangle} \right\rfloor$$

$$a = 10^3 \alpha + (\beta - \alpha) \cdot \left(10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) - 1250,$$

where $\left\lceil \cdot \right\rceil$ denotes ε -TEX's rounding division, which rounds ties away from zero. The idea is to interpolate between $10^3 \alpha$ and $10^3 \beta$ with a parameter $\langle d_2 \rangle / 10^4$, so that when $\langle d_2 \rangle = 0$ one gets $a = 10^3 \beta - 1250 \simeq 10^{12} / \langle d_1 \rangle \simeq 10^8 / \langle d \rangle$, while when $\langle d_2 \rangle = 9999$ one gets $a = 10^3 \alpha - 1250 \simeq 10^{12} / (\langle d_1 \rangle + 1) \simeq 10^8 / \langle d \rangle$. The shift by 1250 helps to ensure that a is an underestimate of the correct value. We shall prove that

$$1 - 1.755 \cdot 10^{-5} < \frac{\langle d \rangle a}{10^8} < 1.$$

We can then compute the inverse of $\langle d \rangle a / 10^8 = 1 - \epsilon$ using the relation $1 / (1 - \epsilon) \simeq (1 + \epsilon)(1 + \epsilon^2) + \epsilon^4$, which is correct up to a relative error of $\epsilon^5 < 1.6 \cdot 10^{-24}$. This allows us to find the desired ratio as

$$\frac{\langle n \rangle}{\langle d \rangle} = \frac{\langle n \rangle a}{10^8} ((1 + \epsilon)(1 + \epsilon^2) + \epsilon^4).$$

Let us prove the upper bound first (multiplied by 10^{15}). Note that $10^7 \langle d \rangle < 10^3 \langle d_1 \rangle + 10^{-1}(\langle d_2 \rangle + 1)$, and that ε -TEX's division $\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor$ underestimates $10^{-1}(\langle d_2 \rangle + 1)$ by 0.5 at

most, as can be checked for each possible last digit of $\langle d_2 \rangle$. Then,

$$10^7 \langle d \rangle a < \left(10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil + \frac{1}{2} \right) \left(\left(10^3 - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \right) \beta + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \alpha - 1250 \right) \quad (1)$$

$$< \left(10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil + \frac{1}{2} \right) \quad (2)$$

$$\left(\left(10^3 - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \right) \left(\frac{10^9}{\langle d_1 \rangle} + \frac{1}{2} \right) + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \left(\frac{10^9}{\langle d_1 \rangle + 1} + \frac{1}{2} \right) - 1250 \right) \quad (3)$$

$$< \left(10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil + \frac{1}{2} \right) \left(\frac{10^{12}}{\langle d_1 \rangle} - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \frac{10^9}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} - 750 \right) \quad (4)$$

We recognize a quadratic polynomial in $[\langle d_2 \rangle / 10]$ with a negative leading coefficient: this polynomial is bounded above, according to $([\langle d_2 \rangle / 10] + a)(b - c[\langle d_2 \rangle / 10]) \leq (b + ca)^2 / (4c)$. Hence,

$$10^7 \langle d \rangle a < \frac{10^{15}}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} \left(\langle d_1 \rangle + \frac{1}{2} + \frac{1}{4} 10^{-3} - \frac{3}{8} \cdot 10^{-9} \langle d_1 \rangle (\langle d_1 \rangle + 1) \right)^2$$

Since $\langle d_1 \rangle$ takes integer values within $[1000, 9999]$, it is a simple programming exercise to check that the squared expression is always less than $\langle d_1 \rangle (\langle d_1 \rangle + 1)$, hence $10^7 \langle d \rangle a < 10^{15}$. The upper bound is proven. We also find that $\frac{3}{8}$ can be replaced by slightly smaller numbers, but nothing less than $0.374563\dots$, and going back through the derivation of the upper bound, we find that 1250 is as small a shift as we can obtain without breaking the bound.

Now, the lower bound. The same computation as for the upper bound implies

$$10^7 \langle d \rangle a > \left(10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil - \frac{1}{2} \right) \left(\frac{10^{12}}{\langle d_1 \rangle} - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \frac{10^9}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} - 1750 \right)$$

This time, we want to find the minimum of this quadratic polynomial. Since the leading coefficient is still negative, the minimum is reached for one of the extreme values $[y/10] = 0$ or $[y/10] = 100$, and we easily check the bound for those values.

We have proven that the algorithm gives us a precise enough answer. Incidentally, the upper bound that we derived tells us that $a < 10^8 / \langle d \rangle \leq 10^9$, hence we can compute a safely as a $\text{T}_{\text{E}}\text{X}$ integer, and even add 10^9 to it to ease grabbing of all the digits. The lower bound implies $10^8 - 1755 < a$, which we do not care about.

`_fp_ep_div:wwwn` Compute the ratio of two extended-precision numbers. The result is an extended-precision number whose first block lies in the range $[100, 9999]$, and is placed after the $\langle continuation \rangle$ once we are done. First normalize the inputs so that both first block lie in $[1000, 9999]$, then call `_fp_ep_div_esti:wwwn $\langle denominator \rangle$ $\langle numerator \rangle$` , responsible for estimating the inverse of the denominator.

```

20368 \cs_new:Npn \_fp\_ep\_div:wwwn #1,#2; #3,#4;
20369 {
20370   \_fp\_ep\_to\_ep:wwN #1,#2;
20371   \_fp\_fixed\_continue:wn
20372   {
20373     \_fp\_ep\_to\_ep:wwN #3,#4;
20374     \_fp\_ep\_div\_esti:wwwn
20375   }
20376 }
```

(End definition for `_fp_ep_div:wwwn`.)

`_fp_ep_div_esti:wwwn`
`_fp_ep_div_estii:wwnnwn`
`_fp_ep_div_estiii:NNNNwwwn`

The **esti** function evaluates $\alpha = 10^9 / (\langle d_1 \rangle + 1)$, which is used twice in the expression for a , and combines the exponents **#1** and **#4** (with a shift by 1 because we later compute $\langle n \rangle / (10 \langle d \rangle)$). Then the **estii** function evaluates $10^9 + a$, and puts the exponent **#2** after the continuation **#7**: from there on we can forget exponents and focus on the mantissa. The **estiii** function multiplies the denominator **#7** by $10^{-8}a$ (obtained as a split into the single digit **#1** and two blocks of 4 digits, **#2#3#4#5** and **#6**). The result $10^{-8}a \langle d \rangle = (1 - \epsilon)$, and a partially packed $10^{-9}a$ (as a block of four digits, and five individual digits, not packed by lack of available macro parameters here) are passed to `_fp_ep_div_epsilon:wnNNNNn`, which computes $10^{-9}a / (1 - \epsilon)$, that is, $1 / (10 \langle d \rangle)$ and we finally multiply this by the numerator **#8**.

```
20377 \cs_new:Npn \_fp_ep_div_esti:wwwn #1,#2#3; #4,
20378 {
20379   \exp_after:wN \_fp_ep_div_estii:wwnnwn
20380   \int_value:w \_fp_int_eval:w 10 0000 0000 / ( #2 + 1 )
20381   \exp_after:wN ;
20382   \int_value:w \_fp_int_eval:w #4 - #1 + 1 ,
20383   {#2} #3;
20384 }
20385 \cs_new:Npn \_fp_ep_div_estii:wwnnwn #1; #2,#3#4#5; #6; #7
20386 {
20387   \exp_after:wN \_fp_ep_div_estiii:NNNNwwwn
20388   \int_value:w \_fp_int_eval:w 10 0000 0000 - 1750
20389   + #1 000 + (10 0000 0000 / #3 - #1) * (1000 - #4 / 10) ;
20390   {#3}{#4}#5; #6; { #7 #2, }
20391 }
20392 \cs_new:Npn \_fp_ep_div_estiii:NNNNwwwn 1#1#2#3#4#5#6; #7;
20393 {
20394   \_fp_fixed_mul_short:wwn #7; {#1}{#2#3#4#5}{#6};
20395   \_fp_ep_div_epsilon:wnNNNNn {#1#2#3#4}#5#6
20396   \_fp_fixed_mul:wwn
20397 }
```

(End definition for `_fp_ep_div_esti:wwwn`, `_fp_ep_div_estii:wwnnwn`, and `_fp_ep_div_estiii:NNNNwwwn`.)

`_fp_ep_div_epsilon:wnNNNNn`
`_fp_ep_div_eps_pack:NNNNw`
`_fp_ep_div_epsii:wwnnNNNNn`

The bounds shown above imply that the **epsi** function's first operand is $(1 - \epsilon)$ with $\epsilon \in [0, 1.755 \cdot 10^{-5}]$. The **epsi** function computes ϵ as $1 - (1 - \epsilon)$. Since $\epsilon < 10^{-4}$, its first block vanishes and there is no need to explicitly use **#1** (which is 9999). Then **epsii** evaluates $10^{-9}a / (1 - \epsilon)$ as $(1 + \epsilon^2)(1 + \epsilon)(10^{-9}a\epsilon) + 10^{-9}a$. Importantly, we compute $10^{-9}a\epsilon$ before multiplying it with the rest, rather than multiplying by ϵ and then $10^{-9}a$, as this second option loses more precision. Also, the combination of **short_mul** and **div_myriad** is both faster and more precise than a simple **mul**.

```
20398 \cs_new:Npn \_fp_ep_div_epsilon:wnNNNNn #1#2#3#4#5#6;
20399 {
20400   \exp_after:wN \_fp_ep_div_epsii:wwnnNNNNn
20401   \int_value:w \_fp_int_eval:w 1 9998 - #2
20402   \exp_after:wN \_fp_ep_div_eps_pack:NNNNw
20403   \int_value:w \_fp_int_eval:w 1 9999 9998 - #3#4
20404   \exp_after:wN \_fp_ep_div_eps_pack:NNNNw
20405   \int_value:w \_fp_int_eval:w 2 0000 0000 - #5#6 ; ;
20406 }
```

```

20407 \cs_new:Npn \__fp_ep_div_eps_pack:NNNNNw #1#2#3#4#5#6;
20408 { + #1 ; {#2#3#4#5} {#6} }
20409 \cs_new:Npn \__fp_ep_div_epsii:wnnnnnn 1#1; #2; #3#4#5#6#7#8
20410 {
20411   \__fp_fixed_mul:wnn {0000}{#1}#2; {0000}{#1}#2;
20412   \__fp_fixed_add_one:wn
20413   \__fp_fixed_mul:wnn {10000} {#1} #2 ;
20414   {
20415     \__fp_fixed_mul_short:wnn {0000}{#1}#2; {#3}{#4#5#6#7}{#8000};
20416     \__fp_fixed_div_myriad:wn
20417     \__fp_fixed_mul:wnn
20418   }
20419   \__fp_fixed_add:wnn {#3}{#4#5#6#7}{#8000}{0000}{0000}{0000};
20420 }

```

(End definition for `__fp_ep_div_epsilon:wnnnnnn`, `__fp_ep_div_eps_pack:NNNNNw`, and `__fp_ep_div_epsii:wnnnnnn`.)

32.10 Inverse square root of extended precision numbers

The idea here is similar to division. Normalize the input, multiplying by powers of 100 until we have $x \in [0.01, 1)$. Then find an integer approximation $r \in [101, 1003]$ of $10^2/\sqrt{x}$, as the fixed point of iterations of the Newton method: essentially $r \mapsto (r + 10^8/(x_1 r))/2$, starting from a guess that optimizes the number of steps before convergence. In fact, just as there is a slight shift when computing divisions to ensure that some inequalities hold, we replace 10^8 by a slightly larger number which ensures that $r^2 x \geq 10^4$. This also causes $r \in [101, 1003]$. Another correction to the above is that the input is actually normalized to $[0.1, 1)$, and we use either 10^8 or 10^9 in the Newton method, depending on the parity of the exponent. Skipping those technical hurdles, once we have the approximation r , we set $y = 10^{-4}r^2x$ (or rather, the correct power of 10 to get $y \simeq 1$) and compute $y^{-1/2}$ through another application of Newton's method. This time, the starting value is $z = 1$, each step maps $z \mapsto z(1.5 - 0.5yz^2)$, and we perform a fixed number of steps. Our final result combines r with $y^{-1/2}$ as $x^{-1/2} = 10^{-2}ry^{-1/2}$.

```

\__fp_ep_isqrt:wnn
\__fp_ep_isqrt_aux:wnn
\__fp_ep_isqrt_auxii:wnnnwnn

```

First normalize the input, then check the parity of the exponent #1. If it is even, the result's exponent will be $-\#1/2$, otherwise it will be $(\#1 - 1)/2$ (except in the case where the input was an exact power of 100). The `auxii` function receives as #1 the result's exponent just computed, as #2 the starting value for the iteration giving r (the values 168 and 535 lead to the least number of iterations before convergence, on average), as #3 and #4 one empty argument and one 0, depending on the parity of the original exponent, as #5 and #6 the normalized mantissa ($\#5 \in [1000, 9999]$), and as #7 the continuation. It sets up the iteration giving r : the `esti` function thus receives the initial two guesses #2 and 0, an approximation #5 of 10^4x (its first block of digits), and the empty/zero arguments #3 and #4, followed by the mantissa and an altered continuation where we have stored the result's exponent.

```

20421 \cs_new:Npn \__fp_ep_isqrt:wnn #1,#2;
20422 {
20423   \__fp_ep_to_ep:wnn #1,#2;
20424   \__fp_ep_isqrt_auxi:wnn
20425 }
20426 \cs_new:Npn \__fp_ep_isqrt_auxi:wnn #1,
20427 {

```

```

20428 \exp_after:wN \_fp_ep_isqrt_auxii:wwnnwn
20429 \int_value:w \_fp_int_eval:w
20430 \int_if_odd:nTF {#1}
20431 { (1 - #1) / 2 , 535 , { 0 } { } }
20432 { 1 - #1 / 2 , 168 , { } { 0 } }
20433 }
20434 \cs_new:Npn \_fp_ep_isqrt_auxii:wwnnwn #1, #2, #3#4 #5#6; #7
20435 {
20436 \_fp_ep_isqrt_esti:wwnnwn #2, 0, #5, {#3} {#4}
20437 {#5} #6 ; { #7 #1 , }
20438 }

```

(End definition for _fp_ep_isqrt:wn, _fp_ep_isqrt_aux:wn, and _fp_ep_isqrt_auxii:wwnnwn.)

```

\_fp_ep_isqrt_esti:wwnnwn
\_fp_ep_isqrt_estii:wwnnwn
\_fp_ep_isqrt_estiii:NNNNNwwwn

```

If the last two approximations gave the same result, we are done: call the `esti` function to clean up. Otherwise, evaluate $(\langle prev \rangle + 1.005 \cdot 10^8 \text{ or } 9 / (\langle prev \rangle \cdot x)) / 2$, as the next approximation: omitting the 1.005 factor, this would be Newton's method. We can check by brute force that if `#4` is empty (the original exponent was even), the process computes an integer slightly larger than $100/\sqrt{x}$, while if `#4` is 0 (the original exponent was odd), the result is an integer slightly larger than $100/\sqrt{x/10}$. Once we are done, we evaluate $100r^2/2$ or $10r^2/2$ (when the exponent is even or odd, respectively) and feed that to `estiii`. This third auxiliary finds $y_{\text{even}}/2 = 10^{-4}r^2x/2$ or $y_{\text{odd}}/2 = 10^{-5}r^2x/2$ (again, depending on earlier parity). A simple program shows that $y \in [1, 1.0201]$. The number $y/2$ is fed to `_fp_ep_isqrt_epsilon:wn`, which computes $1/\sqrt{y}$, and we finally multiply the result by r .

```

20439 \cs_new:Npn \_fp_ep_isqrt_esti:wwnnwn #1, #2, #3, #4
20440 {
20441 \if_int_compare:w #1 = #2 \exp_stop_f:
20442 \exp_after:wN \_fp_ep_isqrt_estii:wwnnwn
20443 \fi:
20444 \exp_after:wN \_fp_ep_isqrt_esti:wwnnwn
20445 \int_value:w \_fp_int_eval:w
20446 (#1 + 1 0050 0000 #4 / (#1 * #3)) / 2 ,
20447 #1, #3, {#4}
20448 }
20449 \cs_new:Npn \_fp_ep_isqrt_estii:wwnnwn #1, #2, #3, #4#5
20450 {
20451 \exp_after:wN \_fp_ep_isqrt_estiii:NNNNNwwwn
20452 \int_value:w \_fp_int_eval:w 1000 0000 + #2 * #2 #5 * 5
20453 \exp_after:wN , \int_value:w \_fp_int_eval:w 10000 + #2 ;
20454 }
20455 \cs_new:Npn \_fp_ep_isqrt_estiii:NNNNNwwwn 1#1#2#3#4#5#6, 1#7#8; #9;
20456 {
20457 \_fp_fixed_mul_short:wn #9; {#1} {#2#3#4#5} {#600} ;
20458 \_fp_ep_isqrt_epsilon:wn
20459 \_fp_fixed_mul_short:wn {#7} {#80} {0000} ;
20460 }

```

(End definition for _fp_ep_isqrt_esti:wwnnwn, _fp_ep_isqrt_estii:wwnnwn, and _fp_ep_isqrt_estiii:NNNNNwwwn.)

```

\_fp_ep_isqrt_epsilon:wn
\_fp_ep_isqrt_epsilonii:wn

```

Here, we receive a fixed point number $y/2$ with $y \in [1, 1.0201]$. Starting from $z = 1$ we iterate $z \mapsto z(3/2 - z^2y/2)$. In fact, we start from the first iteration $z = 3/2 - y/2$ to avoid useless multiplications. The `epsii` auxiliary receives z as `#1` and y as `#2`.

```

20461 \cs_new:Npn \__fp_ep_isqrt_epsi:wwN #1;
20462 {
20463   \__fp_fixed_sub:wwn {15000}{0000}{0000}{0000}{0000}{0000}; #1;
20464   \__fp_ep_isqrt_epsi:wwN #1;
20465   \__fp_ep_isqrt_epsi:wwN #1;
20466   \__fp_ep_isqrt_epsi:wwN #1;
20467 }
20468 \cs_new:Npn \__fp_ep_isqrt_epsi:wwN #1; #2;
20469 {
20470   \__fp_fixed_mul:wwn #1; #1;
20471   \__fp_fixed_mul_sub_back:wwwn #2;
20472   {15000}{0000}{0000}{0000}{0000}{0000};
20473   \__fp_fixed_mul:wwn #1;
20474 }

```

(End definition for __fp_ep_isqrt_epsi:wwN and __fp_ep_isqrt_epsi:wwN.)

32.11 Converting from fixed point to floating point

After computing Taylor series, we wish to convert the result from extended precision (with or without an exponent) to the public floating point format. The functions here should be called within an integer expression for the overall exponent of the floating point.

__fp_ep_to_float_o:wwN
 __fp_ep_inv_to_float_o:wwN

An extended-precision number is simply a comma-delimited exponent followed by a fixed point number. Leave the exponent in the current integer expression then convert the fixed point number.

```

20475 \cs_new:Npn \__fp_ep_to_float_o:wwN #1,
20476 { + \__fp_int_eval:w #1 \__fp_fixed_to_float_o:wwN }
20477 \cs_new:Npn \__fp_ep_inv_to_float_o:wwN #1,#2;
20478 {
20479   \__fp_ep_div:wwwn 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1,#2;
20480   \__fp_ep_to_float_o:wwN
20481 }

```

(End definition for __fp_ep_to_float_o:wwN and __fp_ep_inv_to_float_o:wwN.)

__fp_fixed_inv_to_float_o:wwN

Another function which reduces to converting an extended precision number to a float.

```

20482 \cs_new:Npn \__fp_fixed_inv_to_float_o:wwN
20483 { \__fp_ep_inv_to_float_o:wwN 0, }

```

(End definition for __fp_fixed_inv_to_float_o:wwN.)

__fp_fixed_to_float_rad_o:wwN

Converts the fixed point number #1 from degrees to radians then to a floating point number. This could perhaps remain in l3fp-trig.

```

20484 \cs_new:Npn \__fp_fixed_to_float_rad_o:wwN #1;
20485 {
20486   \__fp_fixed_mul:wwn #1; {5729}{5779}{5130}{8232}{0876}{7981};
20487   { \__fp_ep_to_float_o:wwN 2, }
20488 }

```

(End definition for __fp_fixed_to_float_rad_o:wwN.)

```

\__fp_fixed_to_float_o:wN      ... \__fp_int_eval:w <exponent> \__fp_fixed_to_float_o:wN {\langle a_1 \rangle} {\langle a_2 \rangle} {\langle a_3 \rangle}
\__fp_fixed_to_float_o:Nw      {\langle a_4 \rangle} {\langle a_5 \rangle} {\langle a_6 \rangle} ; <sign>
                                yields

```

```

                                <exponent'> ; {\langle a'_1 \rangle} {\langle a'_2 \rangle} {\langle a'_3 \rangle} {\langle a'_4 \rangle} ;

```

And the `to_fixed` version gives six brace groups instead of 4, ensuring that $1000 \leq \langle a'_1 \rangle \leq 9999$. At this stage, we know that $\langle a_1 \rangle$ is positive (otherwise, it is sign of an error before), and we assume that it is less than 10^8 .¹⁰

```

20489 \cs_new:Npn \__fp_fixed_to_float_o:Nw #1#2;
20490 { \__fp_fixed_to_float_o:wN #2; #1 }
20491 \cs_new:Npn \__fp_fixed_to_float_o:wN #1#2#3#4#5#6; #7
20492 { % for the 8-digit-at-the-start thing
20493   + \__fp_int_eval:w \c__fp_block_int
20494   \exp_after:wN \exp_after:wN
20495   \exp_after:wN \__fp_fixed_to_loop:N
20496   \exp_after:wN \use_none:n
20497   \int_value:w \__fp_int_eval:w
20498     1 0000 0000 + #1 \exp_after:wN \__fp_use_none_stop_f:n
20499     \int_value:w 1#2 \exp_after:wN \__fp_use_none_stop_f:n
20500     \int_value:w 1#3#4 \exp_after:wN \__fp_use_none_stop_f:n
20501     \int_value:w 1#5#6
20502   \exp_after:wN ;
20503   \exp_after:wN ;
20504 }
20505 \cs_new:Npn \__fp_fixed_to_loop:N #1
20506 {
20507   \if_meaning:w 0 #1
20508     - 1
20509     \exp_after:wN \__fp_fixed_to_loop:N
20510   \else:
20511     \exp_after:wN \__fp_fixed_to_loop_end:w
20512     \exp_after:wN #1
20513   \fi:
20514 }
20515 \cs_new:Npn \__fp_fixed_to_loop_end:w #1 #2 ;
20516 {
20517   \if_meaning:w ; #1
20518     \exp_after:wN \__fp_fixed_to_float_zero:w
20519   \else:
20520     \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
20521     \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
20522     \exp_after:wN \__fp_fixed_to_float_pack:ww
20523     \exp_after:wN ;
20524   \fi:
20525   #1 #2 0000 0000 0000 0000 ;
20526 }
20527 \cs_new:Npn \__fp_fixed_to_float_zero:w ; 0000 0000 0000 0000 ;
20528 {
20529   - 2 * \c__fp_max_exponent_int ;
20530   {0000} {0000} {0000} {0000} ;
20531 }

```

¹⁰Bruno: I must double check this assumption.

```

20532 \cs_new:Npn \__fp_fixed_to_float_pack:ww #1 ; #2#3 ; ;
20533 {
20534   \if_int_compare:w #2 > 4 \exp_stop_f:
20535     \exp_after:wN \__fp_fixed_to_float_round_up:wnnnnw
20536   \fi:
20537   ; #1 ;
20538 }
20539 \cs_new:Npn \__fp_fixed_to_float_round_up:wnnnnw ; #1#2#3#4 ;
20540 {
20541   \exp_after:wN \__fp_basics_pack_high:NNNNNw
20542   \int_value:w \__fp_int_eval:w 1 #1#2
20543   \exp_after:wN \__fp_basics_pack_low:NNNNNw
20544   \int_value:w \__fp_int_eval:w 1 #3#4 + 1 ;
20545 }

```

(End definition for __fp_fixed_to_float_o:wN and __fp_fixed_to_float_o:Nw.)

```

20546 </initex | package>

```

33 l3fp-expo implementation

```

20547 <*initex | package>
20548 <@@=fp>

```

__fp_parse_word_exp:N Unary functions.

```

\__fp_parse_word_ln:N
\__fp_parse_word_fact:N
20549 \cs_new:Npn \__fp_parse_word_exp:N
20550 { \__fp_parse_unary_function:NNN \__fp_exp_o:w ? }
20551 \cs_new:Npn \__fp_parse_word_ln:N
20552 { \__fp_parse_unary_function:NNN \__fp_ln_o:w ? }
20553 \cs_new:Npn \__fp_parse_word_fact:N
20554 { \__fp_parse_unary_function:NNN \__fp_fact_o:w ? }

```

(End definition for __fp_parse_word_exp:N, __fp_parse_word_ln:N, and __fp_parse_word_fact:N.)

33.1 Logarithm

33.1.1 Work plan

As for many other functions, we filter out special cases in __fp_ln_o:w. Then __fp_ln_npos_o:w receives a positive normal number, which we write in the form $a \cdot 10^b$ with $a \in [0.1, 1)$.

The rest of this section is actually not in sync with the code. Or is the code not in sync with the section? In the current code, $c \in [1, 10]$ is such that $0.7 \leq ac < 1.4$.

We are given a positive normal number, of the form $a \cdot 10^b$ with $a \in [0.1, 1)$. To compute its logarithm, we find a small integer $5 \leq c < 50$ such that $0.91 \leq ac/5 < 1.1$, and use the relation

$$\ln(a \cdot 10^b) = b \cdot \ln(10) - \ln(c/5) + \ln(ac/5).$$

The logarithms $\ln(10)$ and $\ln(c/5)$ are looked up in a table. The last term is computed using the following Taylor series of \ln near 1:

$$\ln\left(\frac{ac}{5}\right) = \ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + t^2 \left(\frac{1}{3} + t^2 \left(\frac{1}{5} + t^2 \left(\frac{1}{7} + t^2 \left(\frac{1}{9} + \dots\right)\right)\right)\right)\right)$$

where $t = 1 - 10/(ac + 5)$. We can now see one reason for the choice of $ac \sim 5$: then $ac + 5 = 10(1 - \epsilon)$ with $-0.05 < \epsilon \leq 0.045$, hence

$$t = \frac{\epsilon}{1 - \epsilon} = \epsilon(1 + \epsilon)(1 + \epsilon^2)(1 + \epsilon^4) \dots,$$

is not too difficult to compute.

33.1.2 Some constants

A few values of the logarithm as extended fixed point numbers. Those are needed in the implementation. It turns out that we don't need the value of $\ln(5)$.

```

\c__fp_ln_i_fixed_t1
\c__fp_ln_ii_fixed_t1
\c__fp_ln_iii_fixed_t1
\c__fp_ln_iv_fixed_t1
\c__fp_ln_vi_fixed_t1
\c__fp_ln_vii_fixed_t1
\c__fp_ln_viii_fixed_t1
\c__fp_ln_ix_fixed_t1
\c__fp_ln_x_fixed_t1
20555 \tl_const:Nn \c__fp_ln_i_fixed_t1 { {0000}{0000}{0000}{0000}{0000}{0000};}
20556 \tl_const:Nn \c__fp_ln_ii_fixed_t1 { {6931}{4718}{0559}{9453}{0941}{7232};}
20557 \tl_const:Nn \c__fp_ln_iii_fixed_t1 { {10986}{1228}{8668}{1096}{9139}{5245};}
20558 \tl_const:Nn \c__fp_ln_iv_fixed_t1 { {13862}{9436}{1119}{8906}{1883}{4464};}
20559 \tl_const:Nn \c__fp_ln_vi_fixed_t1 { {17917}{5946}{9228}{0550}{0081}{2477};}
20560 \tl_const:Nn \c__fp_ln_vii_fixed_t1 { {19459}{1014}{9055}{3133}{0510}{5353};}
20561 \tl_const:Nn \c__fp_ln_viii_fixed_t1 { {20794}{4154}{1679}{8359}{2825}{1696};}
20562 \tl_const:Nn \c__fp_ln_ix_fixed_t1 { {21972}{2457}{7336}{2193}{8279}{0490};}
20563 \tl_const:Nn \c__fp_ln_x_fixed_t1 { {23025}{8509}{2994}{0456}{8401}{7991};}

```

(End definition for `\c__fp_ln_i_fixed_t1` and others.)

33.1.3 Sign, exponent, and special numbers

The logarithm of negative numbers (including $-\infty$ and -0) raises the “invalid” exception. The logarithm of $+0$ is $-\infty$, raising a division by zero exception. The logarithm of $+\infty$ or a `nan` is itself. Positive normal numbers call `__fp_ln_npos_o:w`.

```

20564 \cs_new:Npn \__fp_ln_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
20565 {
20566   \if_meaning:w 2 #3
20567     \__fp_case_use:nw { \__fp_invalid_operation_o:nw { ln } }
20568   \fi:
20569   \if_case:w #2 \exp_stop_f:
20570     \__fp_case_use:nw
20571     { \__fp_division_by_zero_o:Nnw \c_minus_inf_fp { ln } }
20572   \or:
20573   \else:
20574     \__fp_case_return_same_o:w
20575   \fi:
20576   \__fp_ln_npos_o:w \s__fp \__fp_chk:w #2#3#4;
20577 }

```

(End definition for `__fp_ln_o:w`.)

33.1.4 Absolute ln

We catch the case of a significand very close to 0.1 or to 1. In all other cases, the final result is at least 10^{-4} , and then an error of $0.5 \cdot 10^{-20}$ is acceptable.

```

20578 \cs_new:Npn \__fp_ln_npos_o:w \s__fp \__fp_chk:w 10#1#2#3;
20579 { %%^A todo: ln(1) should be "exact zero", not "underflow"
20580   \exp_after:wN \__fp_sanitize:Nw
20581   \int_value:w % for the overall sign

```

```

20582     \if_int_compare:w #1 < 1 \exp_stop_f:
20583         2
20584     \else:
20585         0
20586     \fi:
20587     \exp_after:wN \exp_stop_f:
20588     \int_value:w \__fp_int_eval:w % for the exponent
20589     \__fp_ln_significand:NNNNnnnnN #2#3
20590     \__fp_ln_exponent:wn {#1}
20591 }

```

(End definition for __fp_ln_npos_o:w.)

__fp_ln_significand:NNNNnnnnN __fp_ln_significand:NNNNnnnnN $\langle X_1 \rangle$ $\{\langle X_2 \rangle\}$ $\{\langle X_3 \rangle\}$ $\{\langle X_4 \rangle\}$ $\langle continuation \rangle$
This function expands to

$\langle continuation \rangle$ $\{\langle Y_1 \rangle\}$ $\{\langle Y_2 \rangle\}$ $\{\langle Y_3 \rangle\}$ $\{\langle Y_4 \rangle\}$ $\{\langle Y_5 \rangle\}$ $\{\langle Y_6 \rangle\}$;

where $Y = -\ln(X)$ as an extended fixed point.

```

20592 \cs_new:Npn \__fp_ln_significand:NNNNnnnnN #1#2#3#4
20593 {
20594     \exp_after:wN \__fp_ln_x_ii:wnnnnn
20595     \int_value:w
20596     \if_case:w #1 \exp_stop_f:
20597     \or:
20598         \if_int_compare:w #2 < 4 \exp_stop_f:
20599             \__fp_int_eval:w 10 - #2
20600     \else:
20601         6
20602     \fi:
20603     \or: 4
20604     \or: 3
20605     \or: 2
20606     \or: 2
20607     \or: 2
20608     \else: 1
20609     \fi:
20610     ; { #1 #2 #3 #4 }
20611 }

```

(End definition for __fp_ln_significand:NNNNnnnnN.)

__fp_ln_x_ii:wnnnnn We have thus found $c \in [1, 10]$ such that $0.7 \leq ac < 1.4$ in all cases. Compute $1 + x = 1 + ac \in [1.7, 2.4)$.

```

20612 \cs_new:Npn \__fp_ln_x_ii:wnnnnn #1; #2#3#4#5
20613 {
20614     \exp_after:wN \__fp_ln_div_after:Nw
20615     \cs:w c__fp_ln_ \__fp_int_to_roman:w #1 _fixed_tl \exp_after:wN \cs_end:
20616     \int_value:w
20617     \exp_after:wN \__fp_ln_x_iv:wnnnnnnnnn
20618     \int_value:w \__fp_int_eval:w
20619     \exp_after:wN \__fp_ln_x_iii_var:NNNNNw
20620     \int_value:w \__fp_int_eval:w 9999 9990 + #1*#2#3 +
20621     \exp_after:wN \__fp_ln_x_iii:NNNNNNw
20622     \int_value:w \__fp_int_eval:w 10 0000 0000 + #1*#4#5 ;

```

```

20623     {20000} {0000} {0000} {0000}
20624   } %^A todo: reoptimize (a generalization attempt failed).
20625 \cs_new:Npn \__fp_ln_x_iii:NNNNNNw #1#2 #3#4#5#6 #7;
20626   { #1#2; {#3#4#5#6} {#7} }
20627 \cs_new:Npn \__fp_ln_x_iii_var:NNNNNNw #1 #2#3#4#5 #6;
20628   {
20629     #1#2#3#4#5 + 1 ;
20630     {#1#2#3#4#5} {#6}
20631   }

```

The Taylor series to be used is expressed in terms of $t = (x - 1)/(x + 1) = 1 - 2/(x + 1)$. We now compute the quotient with extended precision, reusing some code from `__fp_/_o:ww`. Note that $1 + x$ is known exactly.

To reuse notations from `l3fp-basics`, we want to compute A/Z with $A = 2$ and $Z = x + 1$. In `l3fp-basics`, we considered the case where both A and Z are arbitrary, in the range $[0.1, 1)$, and we had to monitor the growth of the sequence of remainders A , B , C , etc. to ensure that no overflow occurred during the computation of the next quotient. The main source of risk was our choice to define the quotient as roughly $10^9 \cdot A/10^5 \cdot Z$: then A was bound to be below $2.147 \dots$, and this limit was never far.

In our case, we can simply work with $10^8 \cdot A$ and $10^4 \cdot Z$, because our reason to work with higher powers has gone: we needed the integer $y \simeq 10^5 \cdot Z$ to be at least 10^4 , and now, the definition $y \simeq 10^4 \cdot Z$ suffices.

Let us thus define $y = \lfloor 10^4 \cdot Z \rfloor + 1 \in (1.7 \cdot 10^4, 2.4 \cdot 10^4]$, and

$$Q_1 = \left\lfloor \frac{\lfloor 10^8 \cdot A \rfloor}{y} - \frac{1}{2} \right\rfloor.$$

(The $1/2$ comes from how ε -TeX rounds.) As for division, it is easy to see that $Q_1 \leq 10^4 A/Z$, *i.e.*, Q_1 is an underestimate.

Exactly as we did for division, we set $B = 10^4 A - Q_1 Z$. Then

$$\begin{aligned}
10^4 B &\leq A_1 A_2 \cdot A_3 A_4 - \left(\frac{A_1 A_2}{y} - \frac{3}{2} \right) 10^4 Z \\
&\leq A_1 A_2 \left(1 - \frac{10^4 Z}{y} \right) + 1 + \frac{3}{2} y \\
&\leq 10^8 \frac{A}{y} + 1 + \frac{3}{2} y
\end{aligned}$$

In the same way, and using $1.7 \cdot 10^4 \leq y \leq 2.4 \cdot 10^4$, and convexity, we get

$$\begin{aligned}
10^4 A &= 2 \cdot 10^4 \\
10^4 B &\leq 10^8 \frac{A}{y} + 1.6y \leq 4.7 \cdot 10^4 \\
10^4 C &\leq 10^8 \frac{B}{y} + 1.6y \leq 5.8 \cdot 10^4 \\
10^4 D &\leq 10^8 \frac{C}{y} + 1.6y \leq 6.3 \cdot 10^4 \\
10^4 E &\leq 10^8 \frac{D}{y} + 1.6y \leq 6.5 \cdot 10^4 \\
10^4 F &\leq 10^8 \frac{E}{y} + 1.6y \leq 6.6 \cdot 10^4
\end{aligned}$$

Note that we compute more steps than for division: since t is not the end result, we need to know it with more accuracy (on the other hand, the ending is much simpler, as we don't need an exact rounding for transcendental functions, but just a faithful rounding).

`__fp_ln_x_iv:wnnnnnnnn <1 or 2> <8d> ; {<4d>} {<4d>} <fixed-t1>`

The number is x . Compute y by adding 1 to the five first digits.

```

20632 \cs_new:Npn __fp_ln_x_iv:wnnnnnnnn #1; #2#3#4#5 #6#7#8#9
20633 {
20634   \exp_after:wN __fp_div_significand_pack:NNN
20635   \int_value:w __fp_int_eval:w
20636   __fp_ln_div_i:w #1 ;
20637   #6 #7 ; {#8} {#9}
20638   {#2} {#3} {#4} {#5}
20639   { \exp_after:wN __fp_ln_div_ii:wnn \int_value:w #1 }
20640   { \exp_after:wN __fp_ln_div_ii:wnn \int_value:w #1 }
20641   { \exp_after:wN __fp_ln_div_ii:wnn \int_value:w #1 }
20642   { \exp_after:wN __fp_ln_div_ii:wnn \int_value:w #1 }
20643   { \exp_after:wN __fp_ln_div_vi:wnn \int_value:w #1 }
20644 }
20645 \cs_new:Npn __fp_ln_div_i:w #1;
20646 {
20647   \exp_after:wN __fp_div_significand_calc:wnnnnnnnn
20648   \int_value:w __fp_int_eval:w 999999 + 2 0000 0000 / #1 ; % Q1
20649 }
20650 \cs_new:Npn __fp_ln_div_ii:wnn #1; #2;#3 % y; B1;B2 <- for k=1
20651 {
20652   \exp_after:wN __fp_div_significand_pack:NNN
20653   \int_value:w __fp_int_eval:w
20654   \exp_after:wN __fp_div_significand_calc:wnnnnnnnn
20655   \int_value:w __fp_int_eval:w 999999 + #2 #3 / #1 ; % Q2
20656   #2 #3 ;
20657 }
20658 \cs_new:Npn __fp_ln_div_vi:wnn #1; #2;#3#4#5 #6#7#8#9 %y;F1;F2F3F4x1x2x3x4
20659 {
20660   \exp_after:wN __fp_div_significand_pack:NNN

```

```

20661 \int_value:w \_fp_int_eval:w 1000000 + #2 #3 / #1 ; % Q6
20662 }

```

We now have essentially

```

\_fp_ln_div_after:Nw <fixed t1>
\_fp_div_significand_pack:NNN 106 + Q1
\_fp_div_significand_pack:NNN 106 + Q2
\_fp_div_significand_pack:NNN 106 + Q3
\_fp_div_significand_pack:NNN 106 + Q4
\_fp_div_significand_pack:NNN 106 + Q5
\_fp_div_significand_pack:NNN 106 + Q6 ;
<exponent> ; <continuation>

```

where $\langle fixed\ t1 \rangle$ holds the logarithm of a number in $[1, 10]$, and $\langle exponent \rangle$ is the exponent. Also, the expansion is done backwards. Then $\backslash_fp_div_significand_pack:NNN$ puts things in the correct order to add the Q_i together and put semicolons between each piece. Once those have been expanded, we get

```

\_fp_ln_div_after:Nw <fixed-t1> <1d> ; <4d> ; <4d> ;
<4d> ; <4d> ; <4d> ; <4d> ; <exponent> ;

```

Just as with division, we know that the first two digits are 1 and 0 because of bounds on the final result of the division $2/(x+1)$, which is between roughly 0.8 and 1.2. We then compute $1 - 2/(x+1)$, after testing whether $2/(x+1)$ is greater than or smaller than 1.

```

20663 \cs_new:Npn \_fp_ln_div_after:Nw #1#2;
20664 {
20665   \if_meaning:w 0 #2
20666     \exp_after:wN \_fp_ln_t_small:Nw
20667   \else:
20668     \exp_after:wN \_fp_ln_t_large:NNw
20669     \exp_after:wN -
20670   \fi:
20671   #1
20672 }
20673 \cs_new:Npn \_fp_ln_t_small:Nw #1 #2; #3; #4; #5; #6; #7;
20674 {
20675   \exp_after:wN \_fp_ln_t_large:NNw
20676   \exp_after:wN + % <sign>
20677   \exp_after:wN #1
20678   \int_value:w \_fp_int_eval:w 9999 - #2 \exp_after:wN ;
20679   \int_value:w \_fp_int_eval:w 9999 - #3 \exp_after:wN ;
20680   \int_value:w \_fp_int_eval:w 9999 - #4 \exp_after:wN ;
20681   \int_value:w \_fp_int_eval:w 9999 - #5 \exp_after:wN ;
20682   \int_value:w \_fp_int_eval:w 9999 - #6 \exp_after:wN ;
20683   \int_value:w \_fp_int_eval:w 1 0000 - #7 ;
20684 }

```

```

\_fp_ln_t_large:NNw <sign> <fixed t1>
<t1>; <t2>; <t3>; <t4>; <t5>; <t6>;
<exponent> ; <continuation>

```

Compute the square t^2 , and keep t at the end with its sign. We know that $t < 0.1765$, so every piece has at most 4 digits. However, since we were not careful in $\backslash_fp_ln_t_small:w$, they can have less than 4 digits.

```

20685 \cs_new:Npn \__fp_ln_t_large:NNw #1 #2 #3; #4; #5; #6; #7; #8;
20686 {
20687   \exp_after:wN \__fp_ln_square_t_after:w
20688   \int_value:w \__fp_int_eval:w 9999 0000 + #3*#3
20689   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
20690   \int_value:w \__fp_int_eval:w 9999 0000 + 2*#3*#4
20691   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
20692   \int_value:w \__fp_int_eval:w 9999 0000 + 2*#3*#5 + #4*#4
20693   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
20694   \int_value:w \__fp_int_eval:w 9999 0000 + 2*#3*#6 + 2*#4*#5
20695   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
20696   \int_value:w \__fp_int_eval:w
20697     1 0000 0000 + 2*#3*#7 + 2*#4*#6 + #5*#5
20698     + (2*#3*#8 + 2*#4*#7 + 2*#5*#6) / 1 0000
20699     % ; ; ;
20700   \exp_after:wN \__fp_ln_twice_t_after:w
20701   \int_value:w \__fp_int_eval:w -1 + 2*#3
20702   \exp_after:wN \__fp_ln_twice_t_pack:Nw
20703   \int_value:w \__fp_int_eval:w 9999 + 2*#4
20704   \exp_after:wN \__fp_ln_twice_t_pack:Nw
20705   \int_value:w \__fp_int_eval:w 9999 + 2*#5
20706   \exp_after:wN \__fp_ln_twice_t_pack:Nw
20707   \int_value:w \__fp_int_eval:w 9999 + 2*#6
20708   \exp_after:wN \__fp_ln_twice_t_pack:Nw
20709   \int_value:w \__fp_int_eval:w 9999 + 2*#7
20710   \exp_after:wN \__fp_ln_twice_t_pack:Nw
20711   \int_value:w \__fp_int_eval:w 10000 + 2*#8 ; ;
20712   { \__fp_ln_c:NwNw #1 }
20713   #2
20714 }
20715 \cs_new:Npn \__fp_ln_twice_t_pack:Nw #1 #2; { + #1 ; {#2} }
20716 \cs_new:Npn \__fp_ln_twice_t_after:w #1; { ;; ; {#1} }
20717 \cs_new:Npn \__fp_ln_square_t_pack:NNNNNw #1 #2#3#4#5 #6;
20718   { + #1#2#3#4#5 ; {#6} }
20719 \cs_new:Npn \__fp_ln_square_t_after:w 1 0 #1#2#3 #4;
20720   { \__fp_ln_Taylor:wwNw {0#1#2#3} {#4} }

```

(End definition for __fp_ln_x_ii:wnnnn.)

__fp_ln_Taylor:wwNw Denoting $T = t^2$, we get

```

\__fp_ln_Taylor:wwNw
{ \langle T_1 \rangle } { \langle T_2 \rangle } { \langle T_3 \rangle } { \langle T_4 \rangle } { \langle T_5 \rangle } { \langle T_6 \rangle } ; ;
{ \langle (2t)_1 \rangle } { \langle (2t)_2 \rangle } { \langle (2t)_3 \rangle } { \langle (2t)_4 \rangle } { \langle (2t)_5 \rangle } { \langle (2t)_6 \rangle } ;
{ \__fp_ln_c:NwNw \langle sign \rangle }
\langle fixed t1 \rangle \langle exponent \rangle ; \langle continuation \rangle

```

And we want to compute

$$\ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + T \left(\frac{1}{3} + T \left(\frac{1}{5} + T \left(\frac{1}{7} + T \left(\frac{1}{9} + \cdots \right) \right) \right) \right) \right)$$

The process looks as follows

```

\loop 5; A;
\div_int 5; 1.0; \add A; \mul T; {\loop \eval 5-2;}
\add 0.2; A; \mul T; {\loop \eval 5-2;}
\mul B; T; {\loop 3;}
\loop 3; C;

```

This uses the routine for dividing a number by a small integer ($< 10^4$).

```

20721 \cs_new:Npn \__fp_ln_Taylor:wwNw
20722 { \__fp_ln_Taylor_loop:www 21 ; {0000}{0000}{0000}{0000}{0000}{0000} ; }
20723 \cs_new:Npn \__fp_ln_Taylor_loop:www #1; #2; #3;
20724 {
20725   \if_int_compare:w #1 = 1 \exp_stop_f:
20726   \__fp_ln_Taylor_break:w
20727   \fi:
20728   \exp_after:wN \__fp_fixed_div_int:wwN \c__fp_one_fixed_tl #1;
20729   \__fp_fixed_add:wwN #2;
20730   \__fp_fixed_mul:wwN #3;
20731   {
20732     \exp_after:wN \__fp_ln_Taylor_loop:www
20733     \int_value:w \__fp_int_eval:w #1 - 2 ;
20734   }
20735   #3;
20736 }
20737 \cs_new:Npn \__fp_ln_Taylor_break:w \fi: #1 \__fp_fixed_add:wwN #2#3; #4 ;;
20738 {
20739   \fi:
20740   \exp_after:wN \__fp_fixed_mul:wwN
20741   \exp_after:wN { \int_value:w \__fp_int_eval:w 10000 + #2 } #3;
20742 }

```

(End definition for $\backslash_fp_ln_Taylor:wwNw$.)

```

\__fp_ln_c:NwNw <sign>
{\langle r_1 \rangle} {\langle r_2 \rangle} {\langle r_3 \rangle} {\langle r_4 \rangle} {\langle r_5 \rangle} {\langle r_6 \rangle} ;
<fixed tl> <exponent> ; <continuation>

```

We are now reduced to finding $\ln(c)$ and $\langle exponent \rangle \ln(10)$ in a table, and adding it to the mixture. The first step is to get $\ln(c) - \ln(x) = -\ln(a)$, then we get $\mathbf{b} \ln(10)$ and add or subtract.

For now, $\ln(x)$ is given as $\cdot 10^0$. Unless both the exponent is 1 and $c = 1$, we shift to working in units of $\cdot 10^4$, since the final result is at least $\ln(10/7) \simeq 0.35$.

```

20743 \cs_new:Npn \__fp_ln_c:NwNw #1 #2; #3
20744 {
20745   \if_meaning:w + #1
20746   \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_sub:wwN
20747   \else:
20748   \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_add:wwN
20749   \fi:
20750   #3 #2 ;
20751 }

```

(End definition for $\backslash_fp_ln_c:NwNw$.)

```

    \_fp_ln_exponent:wn
    {<s1>} {<s2>} {<s3>} {<s4>} {<s5>} {<s6>} ;
    {<exponent>}

```

Compute $\langle exponent \rangle$ times $\ln(10)$. Apart from the cases where $\langle exponent \rangle$ is 0 or 1, the result is necessarily at least $\ln(10) \simeq 2.3$ in magnitude. We can thus drop the least significant 4 digits. In the case of a very large (positive or negative) exponent, we can (and we need to) drop 4 additional digits, since the result is of order 10^4 . Naively, one would think that in both cases we can drop 4 more digits than we do, but that would be slightly too tight for rounding to happen correctly. Besides, we already have addition and subtraction for 24 digits fixed point numbers.

```

20752 \cs_new:Npn \_fp_ln_exponent:wn #1; #2
20753 {
20754   \if_case:w #2 \exp_stop_f:
20755     0 \_fp_case_return:nw { \_fp_fixed_to_float_o:Nw 2 }
20756   \or:
20757     \exp_after:wN \_fp_ln_exponent_one:ww \int_value:w
20758   \else:
20759     \if_int_compare:w #2 > 0 \exp_stop_f:
20760     \exp_after:wN \_fp_ln_exponent_small:NNww
20761     \exp_after:wN 0
20762     \exp_after:wN \_fp_fixed_sub:wwn \int_value:w
20763   \else:
20764     \exp_after:wN \_fp_ln_exponent_small:NNww
20765     \exp_after:wN 2
20766     \exp_after:wN \_fp_fixed_add:wwn \int_value:w -
20767   \fi:
20768   \fi:
20769   #2; #1;
20770 }

```

Now we painfully write all the cases.¹¹ No overflow nor underflow can happen, except when computing $\ln(1)$.

```

20771 \cs_new:Npn \_fp_ln_exponent_one:ww 1; #1;
20772 {
20773   0
20774   \exp_after:wN \_fp_fixed_sub:wwn \c__fp_ln_x_fixed_tl #1;
20775   \_fp_fixed_to_float_o:wN 0
20776 }

```

For small exponents, we just drop one block of digits, and set the exponent of the log to 4 (minus any shift coming from leading zeros in the conversion from fixed point to floating point). Note that here the exponent has been made positive.

```

20777 \cs_new:Npn \_fp_ln_exponent_small:NNww #1#2#3; #4#5#6#7#8#9;
20778 {
20779   4
20780   \exp_after:wN \_fp_fixed_mul:wwn
20781     \c__fp_ln_x_fixed_tl
20782     {#3}{0000}{0000}{0000}{0000}{0000} ;
20783   #2
20784   {0000}{#4}{#5}{#6}{#7}{#8};
20785   \_fp_fixed_to_float_o:wN #1
20786 }

```

¹¹Bruno: do rounding.

(End definition for _fp_ln_exponent:wn.)

33.2 Exponential

33.2.1 Sign, exponent, and special numbers

_fp_exp_o:w

```
20787 \cs_new:Npn \_fp_exp_o:w #1 \s__fp \_fp_chk:w #2#3#4; @
20788 {
20789   \if_case:w #2 \exp_stop_f:
20790     \_fp_case_return_o:Nw \c_one_fp
20791   \or:
20792     \exp_after:wN \_fp_exp_normal_o:w
20793   \or:
20794     \if_meaning:w 0 #3
20795       \exp_after:wN \_fp_case_return_o:Nw
20796       \exp_after:wN \c_inf_fp
20797     \else:
20798       \exp_after:wN \_fp_case_return_o:Nw
20799       \exp_after:wN \c_zero_fp
20800     \fi:
20801   \or:
20802     \_fp_case_return_same_o:w
20803   \fi:
20804   \s__fp \_fp_chk:w #2#3#4;
20805 }
```

(End definition for _fp_exp_o:w.)

_fp_exp_normal_o:w

_fp_exp_pos_o:NNwnw

_fp_exp_overflow:NN

```
20806 \cs_new:Npn \_fp_exp_normal_o:w \s__fp \_fp_chk:w 1#1
20807 {
20808   \if_meaning:w 0 #1
20809     \_fp_exp_pos_o:NNwnw + \_fp_fixed_to_float_o:wN
20810   \else:
20811     \_fp_exp_pos_o:NNwnw - \_fp_fixed_inv_to_float_o:wN
20812   \fi:
20813 }
20814 \cs_new:Npn \_fp_exp_pos_o:NNwnw #1#2#3 \fi: #4#5;
20815 {
20816   \fi:
20817   \if_int_compare:w #4 > \c__fp_max_exp_exponent_int
20818     \token_if_eq_charcode:NNTF + #1
20819     { \_fp_exp_overflow:NN \_fp_overflow:w \c_inf_fp }
20820     { \_fp_exp_overflow:NN \_fp_underflow:w \c_zero_fp }
20821   \exp:w
20822   \else:
20823     \exp_after:wN \_fp_sanitize:Nw
20824     \exp_after:wN 0
20825     \int_value:w #1 \_fp_int_eval:w
20826     \if_int_compare:w #4 < 0 \exp_stop_f:
20827       \exp_after:wN \use_i:nn
20828     \else:
20829       \exp_after:wN \use_ii:nn
```

```

20830     \fi:
20831     {
20832         0
20833         \__fp_decimate:nNnnnn { - #4 }
20834         \__fp_exp_Taylor:Nnnwn
20835     }
20836     {
20837         \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 }
20838         \__fp_exp_pos_large:NnnNwn
20839     }
20840     #5
20841     {#4}
20842     #1 #2 0
20843     \exp:w
20844     \fi:
20845     \exp_after:wN \exp_end:
20846 }
20847 \cs_new:Npn \__fp_exp_overflow:NN #1#2
20848 {
20849     \exp_after:wN \exp_after:wN
20850     \exp_after:wN #1
20851     \exp_after:wN #2
20852 }

```

(End definition for __fp_exp_normal_o:w, __fp_exp_pos_o:Nnnwn, and __fp_exp_overflow:NN.)

```

\__fp_exp_Taylor:Nnnwn
\__fp_exp_Taylor_loop:www
\__fp_exp_Taylor_break:Nww

```

This function is called for numbers in the range $[10^{-9}, 10^{-1}]$. We compute 10 terms of the Taylor series. The first argument is irrelevant (rounding digit used by some other functions). The next three arguments, at least 16 digits, delimited by a semicolon, form a fixed point number, so we pack it in blocks of 4 digits.

```

20853 \cs_new:Npn \__fp_exp_Taylor:Nnnwn #1#2#3 #4; #5 #6
20854 {
20855     #6
20856     \__fp_pack_twice_four:wNNNNNNNN
20857     \__fp_pack_twice_four:wNNNNNNNN
20858     \__fp_pack_twice_four:wNNNNNNNN
20859     \__fp_exp_Taylor_ii:ww
20860     ; #2#3#4 0000 0000 ;
20861 }
20862 \cs_new:Npn \__fp_exp_Taylor_ii:ww #1; #2;
20863 { \__fp_exp_Taylor_loop:www 10 ; #1 ; #1 ; \s__fp_stop }
20864 \cs_new:Npn \__fp_exp_Taylor_loop:www #1; #2; #3;
20865 {
20866     \if_int_compare:w #1 = 1 \exp_stop_f:
20867     \exp_after:wN \__fp_exp_Taylor_break:Nww
20868     \fi:
20869     \__fp_fixed_div_int:wwN #3 ; #1 ;
20870     \__fp_fixed_add_one:wN
20871     \__fp_fixed_mul:wwN #2 ;
20872     {
20873         \exp_after:wN \__fp_exp_Taylor_loop:www
20874         \int_value:w \__fp_int_eval:w #1 - 1 ;
20875         #2 ;
20876     }

```

```

20877     }
20878 \cs_new:Npn \__fp_exp_Taylor_break:Nww #1 #2; #3 \s__fp_stop
20879 { \__fp_fixed_add_one:wN #2 ; }

```

(End definition for __fp_exp_Taylor:Nnnwn, __fp_exp_Taylor_loop:www, and __fp_exp_Taylor-break:Nww.)

\c__fp_exp_intarray The integer array has $6 \times 9 \times 4 = 216$ items encoding the values of $\exp(j \times 10^i)$ for $j = 1, \dots, 9$ and $i = -1, \dots, 4$. Each value is expressed as $\simeq 10^p \times 0.m_1m_2m_3$ with three 8-digit blocks m_1, m_2, m_3 and an integer exponent p (one more than the scientific exponent), and these are stored in the integer array as four items: $p, 10^8 + m_1, 10^8 + m_2, 10^8 + m_3$. The various exponentials are stored in increasing order of $j \times 10^i$.

Storing this data in an integer array makes it slightly harder to access (slower, too), but uses 16 bytes of memory per exponential stored, while storing as tokens used around 40 tokens; tokens have an especially large footprint in Unicode-aware engines.

```

20880 \intarray_const_from_clist:Nn \c__fp_exp_intarray
20881 {
20882     1 , 1 1105 1709 , 1 1807 5647 , 1 6248 1171 ,
20883     1 , 1 1221 4027 , 1 5816 0169 , 1 8339 2107 ,
20884     1 , 1 1349 8588 , 1 0757 6003 , 1 1039 8374 ,
20885     1 , 1 1491 8246 , 1 9764 1270 , 1 3178 2485 ,
20886     1 , 1 1648 7212 , 1 7070 0128 , 1 1468 4865 ,
20887     1 , 1 1822 1188 , 1 0039 0508 , 1 9748 7537 ,
20888     1 , 1 2013 7527 , 1 0747 0476 , 1 5216 2455 ,
20889     1 , 1 2225 5409 , 1 2849 2467 , 1 6045 7954 ,
20890     1 , 1 2459 6031 , 1 1115 6949 , 1 6638 0013 ,
20891     1 , 1 2718 2818 , 1 2845 9045 , 1 2353 6029 ,
20892     1 , 1 7389 0560 , 1 9893 0650 , 1 2272 3043 ,
20893     2 , 1 2008 5536 , 1 9231 8766 , 1 7740 9285 ,
20894     2 , 1 5459 8150 , 1 0331 4423 , 1 9078 1103 ,
20895     3 , 1 1484 1315 , 1 9102 5766 , 1 0342 1116 ,
20896     3 , 1 4034 2879 , 1 3492 7351 , 1 2260 8387 ,
20897     4 , 1 1096 6331 , 1 5842 8458 , 1 5992 6372 ,
20898     4 , 1 2980 9579 , 1 8704 1728 , 1 2747 4359 ,
20899     4 , 1 8103 0839 , 1 2757 5384 , 1 0077 1000 ,
20900     5 , 1 2202 6465 , 1 7948 0671 , 1 6516 9579 ,
20901     9 , 1 4851 6519 , 1 5409 7902 , 1 7796 9107 ,
20902     14 , 1 1068 6474 , 1 5815 2446 , 1 2146 9905 ,
20903     18 , 1 2353 8526 , 1 6837 0199 , 1 8540 7900 ,
20904     22 , 1 5184 7055 , 1 2858 7072 , 1 4640 8745 ,
20905     27 , 1 1142 0073 , 1 8981 5684 , 1 2836 6296 ,
20906     31 , 1 2515 4386 , 1 7091 9167 , 1 0062 6578 ,
20907     35 , 1 5540 6223 , 1 8439 3510 , 1 0525 7117 ,
20908     40 , 1 1220 4032 , 1 9431 7840 , 1 8020 0271 ,
20909     44 , 1 2688 1171 , 1 4181 6135 , 1 4484 1263 ,
20910     87 , 1 7225 9737 , 1 6812 5749 , 1 2581 7748 ,
20911     131 , 1 1942 4263 , 1 9524 1255 , 1 9365 8421 ,
20912     174 , 1 5221 4696 , 1 8976 4143 , 1 9505 8876 ,
20913     218 , 1 1403 5922 , 1 1785 2837 , 1 4107 3977 ,
20914     261 , 1 3773 0203 , 1 0092 9939 , 1 8234 0143 ,
20915     305 , 1 1014 2320 , 1 5473 5004 , 1 5094 5533 ,
20916     348 , 1 2726 3745 , 1 7211 2566 , 1 5673 6478 ,
20917     391 , 1 7328 8142 , 1 2230 7421 , 1 7051 8866 ,
20918     435 , 1 1970 0711 , 1 1401 7046 , 1 9938 8888 ,

```

```

20919      869 , 1 3881 1801 , 1 9428 4368 , 1 5764 8232 ,
20920      1303 , 1 7646 2009 , 1 8905 4704 , 1 8893 1073 ,
20921      1738 , 1 1506 3559 , 1 7005 0524 , 1 9009 7592 ,
20922      2172 , 1 2967 6283 , 1 8402 3667 , 1 0689 6630 ,
20923      2606 , 1 5846 4389 , 1 5650 2114 , 1 7278 5046 ,
20924      3041 , 1 1151 7900 , 1 5080 6878 , 1 2914 4154 ,
20925      3475 , 1 2269 1083 , 1 0850 6857 , 1 8724 4002 ,
20926      3909 , 1 4470 3047 , 1 3316 5442 , 1 6408 6591 ,
20927      4343 , 1 8806 8182 , 1 2566 2921 , 1 5872 6150 ,
20928      8686 , 1 7756 0047 , 1 2598 6861 , 1 0458 3204 ,
20929      13029 , 1 6830 5723 , 1 7791 4884 , 1 1932 7351 ,
20930      17372 , 1 6015 5609 , 1 3095 3052 , 1 3494 7574 ,
20931      21715 , 1 5297 7951 , 1 6443 0315 , 1 3251 3576 ,
20932      26058 , 1 4665 6719 , 1 0099 3379 , 1 5527 2929 ,
20933      30401 , 1 4108 9724 , 1 3326 3186 , 1 5271 5665 ,
20934      34744 , 1 3618 6973 , 1 3140 0875 , 1 3856 4102 ,
20935      39087 , 1 3186 9209 , 1 6113 3900 , 1 6705 9685 ,
20936    }

```

(End definition for \c_fp_exp_intarray.)

_fp_exp_pos_large:NnnNwn The first two arguments are irrelevant (a rounding digit, and a brace group with 8 zeros).
_fp_exp_large_after:wnn The third argument is the integer part of our number, then we have the decimal part
 _fp_exp_large:NwN delimited by a semicolon, and finally the exponent, in the range [0,5]. Remove leading
 _fp_exp_intarray:w zeros from the integer part: putting #4 in there too ensures that an integer part of 0 is
 _fp_exp_intarray_aux:w also removed. Then read digits one by one, looking up $\exp(\langle digit \rangle \cdot 10^{\langle exponent \rangle})$ in a table,
and multiplying that to the current total. The loop is done by _fp_exp_large:NwN,
whose #1 is the $\langle exponent \rangle$, #2 is the current mantissa, and #3 is the $\langle digit \rangle$. At the end,
_fp_exp_large_after:wnn moves on to the Taylor series, eventually multiplied with
the mantissa that we have just computed.

```

20937 \cs_new:Npn \_fp\_exp\_pos\_large:NnnNwn #1#2#3 #4#5; #6
20938 {
20939   \exp_after:wN \exp_after:wN \exp_after:wN \_fp\_exp\_large:NwN
20940   \exp_after:wN \exp_after:wN \exp_after:wN #6
20941   \exp_after:wN \c\_fp\_one\_fixed\_tl
20942   \int_value:w #3 #4 \exp_stop_f:
20943   #5 00000 ;
20944 }
20945 \cs_new:Npn \_fp\_exp\_large:NwN #1#2; #3
20946 {
20947   \if_case:w #3 ~
20948     \exp_after:wN \_fp\_fixed\_continue:wn
20949   \else:
20950     \exp_after:wN \_fp\_exp\_intarray:w
20951     \int_value:w \_fp\_int\_eval:w 36 * #1 + 4 * #3 \exp_after:wN ;
20952   \fi:
20953   #2;
20954   {
20955     \if_meaning:w 0 #1
20956       \exp_after:wN \_fp\_exp\_large\_after:wnn
20957     \else:
20958       \exp_after:wN \_fp\_exp\_large:NwN
20959       \int_value:w \_fp\_int\_eval:w #1 - 1 \exp_after:wN \scan_stop:
20960     \fi:

```

```

20961     }
20962   }
20963   \cs_new:Npn \__fp_exp_intarray:w #1 ;
20964   {
20965     +
20966     \__kernel_intarray_item:Nn \c__fp_exp_intarray
20967     { \__fp_int_eval:w #1 - 3 \scan_stop: }
20968     \exp_after:wN \use_i:nnn
20969     \exp_after:wN \__fp_fixed_mul:wwn
20970     \int_value:w 0
20971     \exp_after:wN \__fp_exp_intarray_aux:w
20972     \int_value:w \__kernel_intarray_item:Nn
20973     \c__fp_exp_intarray { \__fp_int_eval:w #1 - 2 }
20974     \exp_after:wN \__fp_exp_intarray_aux:w
20975     \int_value:w \__kernel_intarray_item:Nn
20976     \c__fp_exp_intarray { \__fp_int_eval:w #1 - 1 }
20977     \exp_after:wN \__fp_exp_intarray_aux:w
20978     \int_value:w \__kernel_intarray_item:Nn \c__fp_exp_intarray {#1} ; ;
20979   }
20980   \cs_new:Npn \__fp_exp_intarray_aux:w 1 #1#2#3#4#5 ; { ; {#1#2#3#4} {#5} }
20981   \cs_new:Npn \__fp_exp_large_after:wwn #1; #2; #3
20982   {
20983     \__fp_exp_Taylor:Nnnwn ? { } { } 0 #2; {} #3
20984     \__fp_fixed_mul:wwn #1;
20985   }

```

(End definition for `__fp_exp_pos_large:NnnNwn` and others.)

33.3 Power

Raising a number a to a power b leads to many distinct situations.

a^b	$-\infty$	$(-\infty, -0)$	$-\text{integer}$	± 0	$+\text{integer}$	$(0, \infty)$	$+\infty$	NaN
$+\infty$	$+0$		$+0$	$+1$	$+\infty$		$+\infty$	NaN
$(1, \infty)$	$+0$		$+ a ^b$	$+1$	$+ a ^b$		$+\infty$	NaN
$+1$	$+1$		$+1$	$+1$	$+1$		$+1$	$+1$
$(0, 1)$	$+\infty$		$+ a ^b$	$+1$	$+ a ^b$		$+0$	NaN
$+0$	$+\infty$		$+\infty$	$+1$	$+0$		$+0$	NaN
-0	$+\infty$	NaN	$(-1)^b \infty$	$+1$	$(-1)^b 0$	$+0$	$+0$	NaN
$(-1, 0)$	$+\infty$	NaN	$(-1)^b a ^b$	$+1$	$(-1)^b a ^b$	NaN	$+0$	NaN
-1	$+1$	NaN	$(-1)^b$	$+1$	$(-1)^b$	NaN	$+1$	NaN
$(-\infty, -1)$	$+0$	NaN	$(-1)^b a ^b$	$+1$	$(-1)^b a ^b$	NaN	$+\infty$	NaN
$-\infty$	$+0$	$+0$	$(-1)^b 0$	$+1$	$(-1)^b \infty$	NaN	$+\infty$	NaN
NaN	NaN	NaN	NaN	$+1$	NaN	NaN	NaN	NaN

We distinguished in this table the cases of finite (positive or negative) integer exponents, as $(-1)^b$ is defined in that case. One peculiarity of this operation is that $\text{NaN}^0 = 1^{\text{NaN}} = 1$, because this relation is obeyed for any number, even $\pm\infty$.

`__fp_~_o:ww` We cram most of the tests into a single function to save csnames. First treat the case $b = 0$: $a^0 = 1$ for any a , even `nan`. Then test the sign of a .

- If it is positive, and a is a normal number, call `__fp_pow_normal_o:ww` followed by the two `fp` a and b . For $a = +0$ or $+\infty$, call `__fp_pow_zero_or_inf:ww` instead, to return either $+0$ or $+\infty$ as appropriate.
- If a is a `nan`, then skip to the next semicolon (which happens to be conveniently the end of b) and return `nan`.
- Finally, if a is negative, compute a^b (`__fp_pow_normal_o:ww` which ignores the sign of its first operand), and keep an extra copy of a and b (the second brace group, containing $\{ b a \}$, is inserted between a and b). Then do some tests to find the final sign of the result if it exists.

```

20986 \cs_new:cpn { __fp_ \iow_char:N ^ _o:ww }
20987   \s__fp \__fp_chk:w #1#2#3; \s__fp \__fp_chk:w #4#5#6;
20988   {
20989     \if_meaning:w 0 #4
20990       \__fp_case_return_o:Nw \c_one_fp
20991     \fi:
20992     \if_case:w #2 \exp_stop_f:
20993       \exp_after:wN \use_i:nn
20994     \or:
20995       \__fp_case_return_o:Nw \c_nan_fp
20996     \else:
20997       \exp_after:wN \__fp_pow_neg:www
20998       \exp:w \exp_end_continue_f:w \exp_after:wN \use:nn
20999     \fi:
21000   {
21001     \if_meaning:w 1 #1
21002       \exp_after:wN \__fp_pow_normal_o:ww
21003     \else:
21004       \exp_after:wN \__fp_pow_zero_or_inf:ww
21005     \fi:
21006     \s__fp \__fp_chk:w #1#2#3;
21007   }
21008   { \s__fp \__fp_chk:w #4#5#6; \s__fp \__fp_chk:w #1#2#3; }
21009   \s__fp \__fp_chk:w #4#5#6;
21010 }

```

(End definition for `__fp_~_o:ww`.)

`__fp_pow_zero_or_inf:ww` Raising -0 or $-\infty$ to `nan` yields `nan`. For other powers, the result is $+0$ if 0 is raised to a positive power or ∞ to a negative power, and $+\infty$ otherwise. Thus, if the type of a and the sign of b coincide, the result is 0 , since those conveniently take the same possible values, 0 and 2 . Otherwise, either $a = \pm\infty$ and $b > 0$ and the result is $+\infty$, or $a = \pm 0$ with $b < 0$ and we have a division by zero unless $b = -\infty$.

```

21011 \cs_new:Npn \__fp_pow_zero_or_inf:ww
21012   \s__fp \__fp_chk:w #1#2; \s__fp \__fp_chk:w #3#4
21013   {
21014     \if_meaning:w 1 #4
21015       \__fp_case_return_same_o:w
21016     \fi:
21017     \if_meaning:w #1 #4
21018       \__fp_case_return_o:Nw \c_zero_fp
21019     \fi:

```

```

21020 \if_meaning:w 2 #1
21021 \__fp_case_return_o:Nw \c_inf_fp
21022 \fi:
21023 \if_meaning:w 2 #3
21024 \__fp_case_return_o:Nw \c_inf_fp
21025 \else:
21026 \__fp_case_use:nw
21027 {
21028 \__fp_division_by_zero_o:NNww \c_inf_fp ^
21029 \s__fp \__fp_chk:w #1 #2 ;
21030 }
21031 \fi:
21032 \s__fp \__fp_chk:w #3#4
21033 }

```

(End definition for `__fp_pow_zero_or_inf:ww`.)

`__fp_pow_normal_o:ww` We have in front of us a , and $b \neq 0$, we know that a is a normal number, and we wish to compute $|a|^b$. If $|a| = 1$, we return 1, unless $a = -1$ and b is `nan`. Indeed, returning 1 at this point would wrongly raise “invalid” when the sign is considered. If $|a| \neq 1$, test the type of b :

- 0 Impossible, we already filtered $b = \pm 0$.
- 1 Call `__fp_pow_npos_o:Nww`.
- 2 Return $+\infty$ or $+0$ depending on the sign of b and whether the exponent of a is positive or not.
- 3 Return b .

```

21034 \cs_new:Npn \__fp_pow_normal_o:ww
21035 \s__fp \__fp_chk:w 1 #1#2#3; \s__fp \__fp_chk:w #4#5
21036 {
21037 \if_int_compare:w \__fp_str_if_eq:nn { #2 #3 }
21038 { 1 {1000} {0000} {0000} {0000} } = 0 \exp_stop_f:
21039 \if_int_compare:w #4 #1 = 32 \exp_stop_f:
21040 \exp_after:wN \__fp_case_return_ii_o:ww
21041 \fi:
21042 \__fp_case_return_o:Nww \c_one_fp
21043 \fi:
21044 \if_case:w #4 \exp_stop_f:
21045 \or:
21046 \exp_after:wN \__fp_pow_npos_o:Nww
21047 \exp_after:wN #5
21048 \or:
21049 \if_meaning:w 2 #5 \exp_after:wN \reverse_if:N \fi:
21050 \if_int_compare:w #2 > 0 \exp_stop_f:
21051 \exp_after:wN \__fp_case_return_o:Nww
21052 \exp_after:wN \c_inf_fp
21053 \else:
21054 \exp_after:wN \__fp_case_return_o:Nww
21055 \exp_after:wN \c_zero_fp
21056 \fi:
21057 \or:

```

```

21058     \__fp_case_return_ii_o:ww
21059     \fi:
21060     \s__fp \__fp_chk:w 1 #1 {#2} #3 ;
21061     \s__fp \__fp_chk:w #4 #5
21062 }

```

(End definition for __fp_pow_normal_o:ww.)

__fp_pow_npos_o:Nww We now know that $a \neq \pm 1$ is a normal number, and b is a normal number too. We want to compute $|a|^b = (|x| \cdot 10^n)^{y \cdot 10^p} = \exp((\ln|x| + n \ln(10)) \cdot y \cdot 10^p) = \exp(z)$. To compute the exponential accurately, we need to know the digits of z up to the 16-th position. Since the exponential of 10^5 is infinite, we only need at most 21 digits, hence the fixed point result of __fp_ln_o:w is precise enough for our needs. Start an integer expression for the decimal exponent of $e^{|z|}$. If z is negative, negate that decimal exponent, and prepare to take the inverse when converting from the fixed point to the floating point result.

```

21063 \cs_new:Npn \__fp_pow_npos_o:Nww #1 \s__fp \__fp_chk:w 1#2#3
21064 {
21065     \exp_after:wN \__fp_sanitize:Nw
21066     \exp_after:wN 0
21067     \int_value:w
21068     \if:w #1 \if_int_compare:w #3 > 0 \exp_stop_f: 0 \else: 2 \fi:
21069     \exp_after:wN \__fp_pow_npos_aux:NNnww
21070     \exp_after:wN +
21071     \exp_after:wN \__fp_fixed_to_float_o:wN
21072     \else:
21073     \exp_after:wN \__fp_pow_npos_aux:NNnww
21074     \exp_after:wN -
21075     \exp_after:wN \__fp_fixed_inv_to_float_o:wN
21076     \fi:
21077     {#3}
21078 }

```

(End definition for __fp_pow_npos_o:Nww.)

__fp_pow_npos_aux:NNnww The first argument is the conversion function from fixed point to float. Then comes an exponent and the 4 brace groups of x , followed by b . Compute $-\ln(x)$.

```

21079 \cs_new:Npn \__fp_pow_npos_aux:NNnww #1#2#3#4#5; \s__fp \__fp_chk:w 1#6#7#8;
21080 {
21081     #1
21082     \__fp_int_eval:w
21083     \__fp_ln_significand:NNNNnnnnN #4#5
21084     \__fp_pow_exponent:wnN {#3}
21085     \__fp_fixed_mul:wwn #8 {0000}{0000} ;
21086     \__fp_pow_B:wwN #7;
21087     #1 #2 0 % fixed_to_float_o:wN
21088 }
21089 \cs_new:Npn \__fp_pow_exponent:wnN #1; #2
21090 {
21091     \if_int_compare:w #2 > 0 \exp_stop_f:
21092     \exp_after:wN \__fp_pow_exponent:Nwnnnnnw % n\ln(10) - (-\ln(x))
21093     \exp_after:wN +
21094     \else:
21095     \exp_after:wN \__fp_pow_exponent:Nwnnnnnw % -(\ln|\ln(10) + (-\ln(x)))
21096     \exp_after:wN -

```



```

21097     \fi:
21098     #2; #1;
21099 }
21100 \cs_new:Npn \__fp_pow_exponent:Nwnnnnnw #1#2; #3#4#5#6#7#8;
21101 { %^A todo: use that in ln.
21102     \exp_after:wN \__fp_fixed_mul_after:wwn
21103     \int_value:w \__fp_int_eval:w \c__fp_leading_shift_int
21104     \exp_after:wN \__fp_pack:NNNNNw
21105     \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
21106     #1#2*23025 - #1 #3
21107     \exp_after:wN \__fp_pack:NNNNNw
21108     \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
21109     #1 #2*8509 - #1 #4
21110     \exp_after:wN \__fp_pack:NNNNNw
21111     \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
21112     #1 #2*2994 - #1 #5
21113     \exp_after:wN \__fp_pack:NNNNNw
21114     \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
21115     #1 #2*0456 - #1 #6
21116     \exp_after:wN \__fp_pack:NNNNNw
21117     \int_value:w \__fp_int_eval:w \c__fp_trailing_shift_int
21118     #1 #2*8401 - #1 #7
21119     #1 ( #2*7991 - #8 ) / 1 0000 ; ;
21120 }
21121 \cs_new:Npn \__fp_pow_B:wwN #1#2#3#4#5#6; #7;
21122 {
21123     \if_int_compare:w #7 < 0 \exp_stop_f:
21124     \exp_after:wN \__fp_pow_C_neg:w \int_value:w -
21125     \else:
21126     \if_int_compare:w #7 < 22 \exp_stop_f:
21127     \exp_after:wN \__fp_pow_C_pos:w \int_value:w
21128     \else:
21129     \exp_after:wN \__fp_pow_C_overflow:w \int_value:w
21130     \fi:
21131     \fi:
21132     #7 \exp_after:wN ;
21133     \int_value:w \__fp_int_eval:w 10 0000 + #1 \__fp_int_eval_end:
21134     #2#3#4#5#6 0000 0000 0000 0000 0000 0000 ; %^A todo: how many 0?
21135 }
21136 \cs_new:Npn \__fp_pow_C_overflow:w #1; #2; #3
21137 {
21138     + 2 * \c__fp_max_exponent_int
21139     \exp_after:wN \__fp_fixed_continue:wn \c__fp_one_fixed_tl
21140 }
21141 \cs_new:Npn \__fp_pow_C_neg:w #1 ; 1
21142 {
21143     \exp_after:wN \exp_after:wN \exp_after:wN \__fp_pow_C_pack:w
21144     \prg_replicate:nn {#1} {0}
21145 }
21146 \cs_new:Npn \__fp_pow_C_pos:w #1; 1
21147 { \__fp_pow_C_pos_loop:wN #1; }
21148 \cs_new:Npn \__fp_pow_C_pos_loop:wN #1; #2
21149 {
21150     \if_meaning:w 0 #1

```

```

21151     \exp_after:wN \__fp_pow_C_pack:w
21152     \exp_after:wN #2
21153   \else:
21154     \if_meaning:w 0 #2
21155     \exp_after:wN \__fp_pow_C_pos_loop:wN \int_value:w
21156   \else:
21157     \exp_after:wN \__fp_pow_C_overflow:w \int_value:w
21158   \fi:
21159   \__fp_int_eval:w #1 - 1 \exp_after:wN ;
21160 \fi:
21161 }
21162 \cs_new:Npn \__fp_pow_C_pack:w
21163 {
21164   \exp_after:wN \__fp_exp_large:NwN
21165   \exp_after:wN 5
21166   \c__fp_one_fixed_tl
21167 }

```

(End definition for __fp_pow_npos_aux:Nnnww.)

__fp_pow_neg:www
__fp_pow_neg_aux:wNN

This function is followed by three floating point numbers: a^b , $a \in [-\infty, -0]$, and b . If b is an even integer (case -1), $a^b = a^b$. If b is an odd integer (case 0), $a^b = -a^b$, obtained by a call to __fp_pow_neg_aux:wNN. Otherwise, the sign is undefined. This is invalid, unless a^b turns out to be +0 or nan, in which case we return that as a^b . In particular, since the underflow detection occurs before __fp_pow_neg:www is called, $(-0.1)**(12345.67)$ gives +0 rather than complaining that the sign is not defined.

```

21168 \cs_new:Npn \__fp_pow_neg:www \s__fp \__fp_chk:w #1#2; #3; #4;
21169 {
21170   \if_case:w \__fp_pow_neg_case:w #4 ;
21171     \exp_after:wN \__fp_pow_neg_aux:wNN
21172   \or:
21173     \if_int_compare:w \__fp_int_eval:w #1 / 2 = 1 \exp_stop_f:
21174     \__fp_invalid_operation_o:Nww ^ #3; #4;
21175     \exp:w \exp_end_continue_f:w
21176     \exp_after:wN \exp_after:wN
21177     \exp_after:wN \__fp_use_none_until_s:w
21178   \fi:
21179 \fi:
21180 \__fp_exp_after_o:w
21181 \s__fp \__fp_chk:w #1#2;
21182 }
21183 \cs_new:Npn \__fp_pow_neg_aux:wNN #1 \s__fp \__fp_chk:w #2#3
21184 {
21185   \exp_after:wN \__fp_exp_after_o:w
21186   \exp_after:wN \s__fp
21187   \exp_after:wN \__fp_chk:w
21188   \exp_after:wN #2
21189   \int_value:w \__fp_int_eval:w 2 - #3 \__fp_int_eval_end:
21190 }

```

(End definition for __fp_pow_neg:www and __fp_pow_neg_aux:wNN.)

__fp_pow_neg_case:w
__fp_pow_neg_case_aux:nnnnn
__fp_pow_neg_case_aux:Nnnw

This function expects a floating point number, and determines its “parity”. It should be used after \if_case:w or in an integer expression. It gives -1 if the number is an

even integer, 0 if the number is an odd integer, and 1 otherwise. Zeros and $\pm\infty$ are even (because very large finite floating points are even), while `nan` is a non-integer. The sign of normal numbers is irrelevant to parity. After `__fp_decimate:nNnnnn` the argument #1 of `__fp_pow_neg_case_aux:Nnnw` is a rounding digit, 0 if and only if the number was an integer, and #3 is the 8 least significant digits of that integer.

```

21191 \cs_new:Npn \__fp_pow_neg_case:w \s__fp \__fp_chk:w #1#2#3;
21192 {
21193   \if_case:w #1 \exp_stop_f:
21194     -1
21195   \or:   \__fp_pow_neg_case_aux:nnnnn #3
21196   \or:   -1
21197   \else: 1
21198   \fi:
21199   \exp_stop_f:
21200 }
21201 \cs_new:Npn \__fp_pow_neg_case_aux:nnnnn #1#2#3#4#5
21202 {
21203   \if_int_compare:w #1 > \c__fp_prec_int
21204     -1
21205   \else:
21206     \__fp_decimate:nNnnnn { \c__fp_prec_int - #1 }
21207     \__fp_pow_neg_case_aux:Nnnw
21208     {#2} {#3} {#4} {#5}
21209   \fi:
21210 }
21211 \cs_new:Npn \__fp_pow_neg_case_aux:Nnnw #1#2#3#4 ;
21212 {
21213   \if_meaning:w 0 #1
21214     \if_int_odd:w #3 \exp_stop_f:
21215     0
21216   \else:
21217     -1
21218   \fi:
21219   \else:
21220     1
21221   \fi:
21222 }

```

(End definition for `__fp_pow_neg_case:w`, `__fp_pow_neg_case_aux:nnnnn`, and `__fp_pow_neg_case_aux:Nnnw`.)

33.4 Factorial

`\c__fp_fact_max_arg_int` The maximum integer whose factorial fits in the exponent range is 3248, as $3249! \sim 10^{10000.8}$

```

21223 \int_const:Nn \c__fp_fact_max_arg_int { 3248 }

```

(End definition for `\c__fp_fact_max_arg_int`.)

`__fp_fact_o:w` First detect ± 0 and $+\infty$ and `nan`. Then note that factorial of anything with a negative sign (except -0) is undefined. Then call `__fp_small_int:wTF` to get an integer as the argument, and start a loop. This is not the most efficient way of computing the factorial,

but it works all right. Of course we work with 24 digits instead of 16. It is easy to check that computing factorials with this precision is enough.

```

21224 \cs_new:Npn \__fp_fact_o:w #1 \s_fp \__fp_chk:w #2#3#4; @
21225 {
21226   \if_case:w #2 \exp_stop_f:
21227     \__fp_case_return_o:Nw \c_one_fp
21228   \or:
21229   \or:
21230     \if_meaning:w 0 #3
21231     \exp_after:wN \__fp_case_return_same_o:w
21232   \fi:
21233   \or:
21234     \__fp_case_return_same_o:w
21235   \fi:
21236   \if_meaning:w 2 #3
21237     \__fp_case_use:nw { \__fp_invalid_operation_o:fw { fact } }
21238   \fi:
21239   \__fp_fact_pos_o:w
21240   \s_fp \__fp_chk:w #2 #3 #4 ;
21241 }

```

(End definition for __fp_fact_o:w.)

__fp_fact_pos_o:w Then check the input is an integer, and call __fp_facorial_int_o:n with that int as
 __fp_fact_int_o:w an argument. If it's too big the factorial overflows. Otherwise call __fp_sanitize:Nw
 with a positive sign marker 0 and an integer expression that will mop up any exponent
 in the calculation.

```

21242 \cs_new:Npn \__fp_fact_pos_o:w #1;
21243 {
21244   \__fp_small_int:wTF #1;
21245   { \__fp_fact_int_o:n }
21246   { \__fp_invalid_operation_o:fw { fact } #1; }
21247 }
21248 \cs_new:Npn \__fp_fact_int_o:n #1
21249 {
21250   \if_int_compare:w #1 > \c__fp_fact_max_arg_int
21251     \__fp_case_return:nw
21252     {
21253       \exp_after:wN \exp_after:wN \exp_after:wN \__fp_overflow:w
21254       \exp_after:wN \c_inf_fp
21255     }
21256   \fi:
21257   \exp_after:wN \__fp_sanitize:Nw
21258   \exp_after:wN 0
21259   \int_value:w \__fp_int_eval:w
21260   \__fp_fact_loop_o:w #1 . 4 , { 1 } { } { } { } { } { } { } ;
21261 }

```

(End definition for __fp_fact_pos_o:w and __fp_fact_int_o:w.)

__fp_fact_loop_o:w The loop receives an integer #1 whose factorial we want to compute, which we progressively decrement, and the result so far as an extended-precision number #2 in the form $\langle \text{exponent} \rangle, \langle \text{mantissa} \rangle$; The loop goes in steps of two because we compute $\#1 \cdot \#1 - 1$ as an integer expression (it must fit since #1 is at most 3248), then multiply with the

result so far. We don't need to fill in most of the mantissa with zeros because `__fp_ep_mul:wwwn` first normalizes the extended precision number to avoid loss of precision. When reaching a small enough number simply use a table of factorials less than 10^8 . This limit is chosen because the normalization step cannot deal with larger integers.

```

21262 \cs_new:Npn \__fp_fact_loop_o:w #1 . #2 ;
21263 {
21264   \if_int_compare:w #1 < 12 \exp_stop_f:
21265     \__fp_fact_small_o:w #1
21266   \fi:
21267   \exp_after:wN \__fp_ep_mul:wwwn
21268   \exp_after:wN 4 \exp_after:wN ,
21269   \exp_after:wN { \int_value:w \__fp_int_eval:w #1 * (#1 - 1) }
21270   { } { } { } { } { } { } ;
21271   #2 ;
21272   {
21273     \exp_after:wN \__fp_fact_loop_o:w
21274     \int_value:w \__fp_int_eval:w #1 - 2 .
21275   }
21276 }
21277 \cs_new:Npn \__fp_fact_small_o:w #1 \fi: #2 ; #3 ; #4
21278 {
21279   \fi:
21280   \exp_after:wN \__fp_ep_mul:wwwn
21281   \exp_after:wN 4 \exp_after:wN ,
21282   \exp_after:wN
21283   {
21284     \int_value:w
21285     \if_case:w #1 \exp_stop_f:
21286       1 \or: 1 \or: 2 \or: 6 \or: 24 \or: 120 \or: 720 \or: 5040
21287       \or: 40320 \or: 362880 \or: 3628800 \or: 39916800
21288     \fi:
21289     } { } { } { } { } { } { } ;
21290   #3 ;
21291   \__fp_ep_to_float_o:wwN 0
21292 }

```

(End definition for `__fp_fact_loop_o:w`.)

```

21293 </initex | package>

```

34 l3fp-trig Implementation

```

21294 <*initex | package>

```

```

21295 <@@=fp>

```

Unary functions.

```

\__fp_parse_word_acos:N
\__fp_parse_word_acosd:N
\__fp_parse_word_acsc:N
\__fp_parse_word_acscd:N
\__fp_parse_word_asec:N
\__fp_parse_word_asecd:N
\__fp_parse_word_asin:N
\__fp_parse_word_asind:N
\__fp_parse_word_cos:N
\__fp_parse_word_cosd:N
\__fp_parse_word_cot:N
\__fp_parse_word_cotd:N
\__fp_parse_word_csc:N
\__fp_parse_word_cscd:N
\__fp_parse_word_sec:N
\__fp_parse_word_secd:N
\__fp_parse_word_sin:N
\__fp_parse_word_sind:N

```

```

21296 \tl_map_inline:nn
21297 {
21298   {acos} {acsc} {asec} {asin}
21299   {cos} {cot} {csc} {sec} {sin} {tan}
21300 }
21301 {
21302   \cs_new:cpx { __fp_parse_word_#1:N }

```

```

21303     {
21304         \exp_not:N \__fp_parse_unary_function:NNN
21305         \exp_not:c { __fp_#1_o:w }
21306         \exp_not:N \use_i:nn
21307     }
21308 \cs_new:cpx { __fp_parse_word_#1d:N }
21309 {
21310     \exp_not:N \__fp_parse_unary_function:NNN
21311     \exp_not:c { __fp_#1_o:w }
21312     \exp_not:N \use_ii:nn
21313 }
21314 }

```

(End definition for `__fp_parse_word_acos:N` and others.)

```

\__fp_parse_word_acot:N Those functions may receive a variable number of arguments.
\__fp_parse_word_acotd:N 21315 \cs_new:Npn \__fp_parse_word_acot:N
\__fp_parse_word_atan:N 21316 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_i:nn }
\__fp_parse_word_atand:N 21317 \cs_new:Npn \__fp_parse_word_acotd:N
21318 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_ii:nn }
21319 \cs_new:Npn \__fp_parse_word_atan:N
21320 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_i:nn }
21321 \cs_new:Npn \__fp_parse_word_atand:N
21322 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_ii:nn }

```

(End definition for `__fp_parse_word_acot:N` and others.)

34.1 Direct trigonometric functions

The approach for all trigonometric functions (sine, cosine, tangent, cotangent, cosecant, and secant), with arguments given in radians or in degrees, is the same.

- Filter out special cases (± 0 , $\pm \infty$ and NaN).
- Keep the sign for later, and work with the absolute value $|x|$ of the argument.
- Small numbers ($|x| < 1$ in radians, $|x| < 10$ in degrees) are converted to fixed point numbers (and to radians if $|x|$ is in degrees).
- For larger numbers, we need argument reduction. Subtract a multiple of $\pi/2$ (in degrees, 90) to bring the number to the range to $[0, \pi/2)$ (in degrees, $[0, 90)$).
- Reduce further to $[0, \pi/4]$ (in degrees, $[0, 45]$) using $\sin x = \cos(\pi/2 - x)$, and when working in degrees, convert to radians.
- Use the appropriate power series depending on the octant $\lfloor \frac{x}{\pi/4} \rfloor \bmod 8$ (in degrees, the same formula with $\pi/4 \rightarrow 45$), the sign, and the function to compute.

34.1.1 Filtering special cases

`__fp_sin_o:w` This function, and its analogs for `cos`, `csc`, `sec`, `tan`, and `cot` instead of `sin`, are followed either by `\use_i:nn` and a float in radians or by `\use_ii:nn` and a float in degrees. The sine of ± 0 or NaN is the same float. The sine of $\pm \infty$ raises an invalid operation exception with the appropriate function name. Otherwise, call the `trig` function to perform argument reduction and if necessary convert the reduced argument to radians.

Then, `__fp_sin_series_o:NNwww` is called to compute the Taylor series: this function receives a sign `#3`, an initial octant of 0, and the function `__fp_ep_to_float_o:wwN` which converts the result of the series to a floating point directly rather than taking its inverse, since $\sin(x) = \#3 \sin|x|$.

```

21323 \cs_new:Npn \__fp_sin_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
21324 {
21325     \if_case:w #2 \exp_stop_f:
21326         \__fp_case_return_same_o:w
21327     \or: \__fp_case_use:nw
21328         {
21329             \__fp_trig:NNNNwn #1 \__fp_sin_series_o:NNwww
21330             \__fp_ep_to_float_o:wwN #3 0
21331         }
21332     \or: \__fp_case_use:nw
21333         { \__fp_invalid_operation_o:fw { #1 { sin } { sind } } }
21334     \else: \__fp_case_return_same_o:w
21335     \fi:
21336     \s__fp \__fp_chk:w #2 #3 #4;
21337 }

```

(End definition for `__fp_sin_o:w`.)

`__fp_cos_o:w` The cosine of ± 0 is 1. The cosine of $\pm\infty$ raises an invalid operation exception. The cosine of NaN is itself. Otherwise, the `trig` function reduces the argument to at most half a right-angle and converts if necessary to radians. We then call the same series as for sine, but using a positive sign 0 regardless of the sign of x , and with an initial octant of 2, because $\cos(x) = +\sin(\pi/2 + |x|)$.

```

21338 \cs_new:Npn \__fp_cos_o:w #1 \s__fp \__fp_chk:w #2#3; @
21339 {
21340     \if_case:w #2 \exp_stop_f:
21341         \__fp_case_return_o:Nw \c_one_fp
21342     \or: \__fp_case_use:nw
21343         {
21344             \__fp_trig:NNNNwn #1 \__fp_sin_series_o:NNwww
21345             \__fp_ep_to_float_o:wwN 0 2
21346         }
21347     \or: \__fp_case_use:nw
21348         { \__fp_invalid_operation_o:fw { #1 { cos } { cosd } } }
21349     \else: \__fp_case_return_same_o:w
21350     \fi:
21351     \s__fp \__fp_chk:w #2 #3;
21352 }

```

(End definition for `__fp_cos_o:w`.)

`__fp_csc_o:w` The cosecant of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see `__fp_cot_zero_o:Nfw` defined below), which requires the function name. The cosecant of $\pm\infty$ raises an invalid operation exception. The cosecant of NaN is itself. Otherwise, the `trig` function performs the argument reduction, and converts if necessary to radians before calling the same series as for sine, using the sign `#3`, a starting octant of 0, and inverting during the conversion from the fixed point sine to the floating point result, because $\csc(x) = \#3(\sin|x|)^{-1}$.

```

21353 \cs_new:Npn \__fp_csc_o:w #1 \s__fp \__fp_chk:w #2#3#4; @

```

```

21354 {
21355     \if_case:w #2 \exp_stop_f:
21356         \__fp_cot_zero_o:Nfw #3 { #1 { csc } { cscd } }
21357     \or: \__fp_case_use:nw
21358         {
21359             \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
21360             \__fp_ep_inv_to_float_o:wwN #3 0
21361         }
21362     \or: \__fp_case_use:nw
21363         { \__fp_invalid_operation_o:fw { #1 { csc } { cscd } } }
21364     \else: \__fp_case_return_same_o:w
21365     \fi:
21366     \s__fp \__fp_chk:w #2 #3 #4;
21367 }

```

(End definition for __fp_csc_o:w.)

__fp_sec_o:w The secant of ± 0 is 1. The secant of $\pm\infty$ raises an invalid operation exception. The secant of NaN is itself. Otherwise, the `trig` function reduces the argument and turns it to radians before calling the same series as for sine, using a positive sign 0, a starting octant of 2, and inverting upon conversion, because $\sec(x) = +1/\sin(\pi/2 + |x|)$.

```

21368 \cs_new:Npn \__fp_sec_o:w #1 \s__fp \__fp_chk:w #2#3; @
21369 {
21370     \if_case:w #2 \exp_stop_f:
21371         \__fp_case_return_o:Nw \c_one_fp
21372     \or: \__fp_case_use:nw
21373         {
21374             \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
21375             \__fp_ep_inv_to_float_o:wwN 0 2
21376         }
21377     \or: \__fp_case_use:nw
21378         { \__fp_invalid_operation_o:fw { #1 { sec } { secd } } }
21379     \else: \__fp_case_return_same_o:w
21380     \fi:
21381     \s__fp \__fp_chk:w #2 #3;
21382 }

```

(End definition for __fp_sec_o:w.)

__fp_tan_o:w The tangent of ± 0 or NaN is the same floating point number. The tangent of $\pm\infty$ raises an invalid operation exception. Once more, the `trig` function does the argument reduction step and conversion to radians before calling `__fp_tan_series_o:NNwww`, with a sign #3 and an initial octant of 1 (this shift is somewhat arbitrary). See `__fp_cot_o:w` for an explanation of the 0 argument.

```

21383 \cs_new:Npn \__fp_tan_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
21384 {
21385     \if_case:w #2 \exp_stop_f:
21386         \__fp_case_return_same_o:w
21387     \or: \__fp_case_use:nw
21388         {
21389             \__fp_trig:NNNNNwn #1
21390             \__fp_tan_series_o:NNwww 0 #3 1
21391         }
21392     \or: \__fp_case_use:nw

```



```

21393         { \__fp_invalid_operation_o:fw { #1 { tan } { tand } } }
21394     \else: \__fp_case_return_same_o:w
21395     \fi:
21396     \s__fp \__fp_chk:w #2 #3 #4;
21397 }

```

(End definition for __fp_tan_o:w.)

__fp_cot_o:w The cotangent of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see
__fp_cot_zero_o:Nfw __fp_cot_zero_o:Nfw. The cotangent of $\pm\infty$ raises an invalid operation exception.
The cotangent of NaN is itself. We use $\cot x = -\tan(\pi/2 + x)$, and the initial octant
for the tangent was chosen to be 1, so the octant here starts at 3. The change in sign
is obtained by feeding __fp_tan_series_o:NNwww two signs rather than just the sign
of the argument: the first of those indicates whether we compute tangent or cotangent.
Those signs are eventually combined.

```

21398 \cs_new:Npn \__fp_cot_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
21399 {
21400     \if_case:w #2 \exp_stop_f:
21401         \__fp_cot_zero_o:Nfw #3 { #1 { cot } { cotd } }
21402     \or: \__fp_case_use:nw
21403         {
21404             \__fp_trig:NNNNwn #1
21405             \__fp_tan_series_o:NNwww 2 #3 3
21406         }
21407     \or: \__fp_case_use:nw
21408         { \__fp_invalid_operation_o:fw { #1 { cot } { cotd } } }
21409     \else: \__fp_case_return_same_o:w
21410     \fi:
21411     \s__fp \__fp_chk:w #2 #3 #4;
21412 }
21413 \cs_new:Npn \__fp_cot_zero_o:Nfw #1#2#3 \fi:
21414 {
21415     \fi:
21416     \token_if_eq_meaning:NNTF 0 #1
21417     { \exp_args:NNf \__fp_division_by_zero_o:Nnw \c_inf_fp }
21418     { \exp_args:NNf \__fp_division_by_zero_o:Nnw \c_minus_inf_fp }
21419     {#2}
21420 }

```

(End definition for __fp_cot_o:w and __fp_cot_zero_o:Nfw.)

34.1.2 Distinguishing small and large arguments

__fp_trig:NNNNwn The first argument is \use_i:nn if the operand is in radians and \use_ii:nn if it is in
degrees. Arguments #2 to #5 control what trigonometric function we compute, and #6
to #8 are pieces of a normal floating point number. Call the _series function #2, with
arguments #3, either a conversion function (__fp_ep_to_float_o:wN or __fp_ep_-
inv_to_float_o:wN) or a sign 0 or 2 when computing tangent or cotangent; #4, a sign
0 or 2; the octant, computed in an integer expression starting with #5 and stopped by a
period; and a fixed point number obtained from the floating point number by argument
reduction (if necessary) and conversion to radians (if necessary). Any argument reduction
adjusts the octant accordingly by leaving a (positive) shift into its integer expression. Let
us explain the integer comparison. Two of the four \exp_after:wN are expanded, the

expansion hits the test, which is true if the float is at least 1 when working in radians, and at least 10 when working in degrees. Then one of the remaining `\exp_after:wN` hits `#1`, which picks the `trig` or `trigd` function in whichever branch of the conditional was taken. The final `\exp_after:wN` closes the conditional. At the end of the day, a number is `large` if it is ≥ 1 in radians or ≥ 10 in degrees, and `small` otherwise. All four `trig/trigd` auxiliaries receive the operand as an extended-precision number.

```

21421 \cs_new:Npn \__fp_trig:NNNNwn #1#2#3#4#5 \s__fp \__fp_chk:w 1#6#7#8;
21422 {
21423   \exp_after:wN #2
21424   \exp_after:wN #3
21425   \exp_after:wN #4
21426   \int_value:w \__fp_int_eval:w #5
21427   \exp_after:wN \exp_after:wN \exp_after:wN \exp_after:wN
21428   \if_int_compare:w #7 > #1 0 1 \exp_stop_f:
21429     #1 \__fp_trig_large:ww \__fp_trigd_large:ww
21430   \else:
21431     #1 \__fp_trig_small:ww \__fp_trigd_small:ww
21432   \fi:
21433   #7,#8{0000}{0000};
21434 }

```

(End definition for `__fp_trig:NNNNwn`.)

34.1.3 Small arguments

`__fp_trig_small:ww` This receives a small extended-precision number in radians and converts it to a fixed point number. Some trailing digits may be lost in the conversion, so we keep the original floating point number around: when computing sine or tangent (or their inverses), the last step is to multiply by the floating point number (as an extended-precision number) rather than the fixed point number. The period serves to end the integer expression for the octant.

```

21435 \cs_new:Npn \__fp_trig_small:ww #1,#2;
21436 { \__fp_ep_to_fixed:wwn #1,#2; . #1,#2; }

```

(End definition for `__fp_trig_small:ww`.)

`__fp_trigd_small:ww` Convert the extended-precision number to radians, then call `__fp_trig_small:ww` to massage it in the form appropriate for the `_series` auxiliary.

```

21437 \cs_new:Npn \__fp_trigd_small:ww #1,#2;
21438 {
21439   \__fp_ep_mul_raw:wwwN
21440   -1,{1745}{3292}{5199}{4329}{5769}{2369}; #1,#2;
21441   \__fp_trig_small:ww
21442 }

```

(End definition for `__fp_trigd_small:ww`.)

34.1.4 Argument reduction in degrees

`__fp_trigd_large:ww` Note that $25 \times 360 = 9000$, so $10^{k+1} \equiv 10^k \pmod{360}$ for $k \geq 3$. When the exponent `#1` is very large, we can thus safely replace it by 22 (or even 19). We turn the floating point number into a fixed point number with two blocks of 8 digits followed by five blocks of 4 digits. The original float is $100 \times \langle block_1 \rangle \cdots \langle block_3 \rangle . \langle block_4 \rangle \cdots \langle block_7 \rangle$, or is equal to

`__fp_trigd_large_auxi:nnnwNNNN`
`__fp_trigd_large_auxii:wNw`
`__fp_trigd_large_auxiii:www`

it modulo 360 if the exponent #1 is very large. The first auxiliary finds $\langle block_1 \rangle + \langle block_2 \rangle$ (mod 9), a single digit, and prepends it to the 4 digits of $\langle block_3 \rangle$. It also unpacks $\langle block_4 \rangle$ and grabs the 4 digits of $\langle block_7 \rangle$. The second auxiliary grabs the $\langle block_3 \rangle$ plus any contribution from the first two blocks as #1, the first digit of $\langle block_4 \rangle$ (just after the decimal point in hundreds of degrees) as #2, and the three other digits as #3. It finds the quotient and remainder of #1#2 modulo 9, adds twice the quotient to the integer expression for the octant, and places the remainder (between 0 and 8) before #3 to form a new $\langle block_4 \rangle$. The resulting fixed point number is $x \in [0, 0.9]$. If $x \geq 0.45$, we add 1 to the octant and feed $0.9 - x$ with an exponent of 2 (to compensate the fact that we are working in units of hundreds of degrees rather than degrees) to `__fp_trigd_small:ww`. Otherwise, we feed it x with an exponent of 2. The third auxiliary also discards digits which were not packed into the various $\langle blocks \rangle$. Since the original exponent #1 is at least 2, those are all 0 and no precision is lost (#6 and #7 are four 0 each).

```

21443 \cs_new:Npn \__fp_trigd_large:ww #1, #2#3#4#5#6#7;
21444 {
21445   \exp_after:wN \__fp_pack_eight:wNNNNNNNN
21446   \exp_after:wN \__fp_pack_eight:wNNNNNNNN
21447   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
21448   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
21449   \exp_after:wN \__fp_trigd_large_auxi:nnnnwNNNN
21450   \exp_after:wN ;
21451   \exp:w \exp_end_continue_f:w
21452   \prg_replicate:nn { \int_max:nn { 22 - #1 } { 0 } } { 0 }
21453   #2#3#4#5#6#7 0000 0000 0000 !
21454 }
21455 \cs_new:Npn \__fp_trigd_large_auxi:nnnnwNNNN #1#2#3#4#5; #6#7#8#9
21456 {
21457   \exp_after:wN \__fp_trigd_large_auxii:wNw
21458   \int_value:w \__fp_int_eval:w #1 + #2
21459   - (#1 + #2 - 4) / 9 * 9 \__fp_int_eval_end:
21460   #3;
21461   #4; #5{#6#7#8#9};
21462 }
21463 \cs_new:Npn \__fp_trigd_large_auxii:wNw #1; #2#3;
21464 {
21465   + (#1#2 - 4) / 9 * 2
21466   \exp_after:wN \__fp_trigd_large_auxiii:www
21467   \int_value:w \__fp_int_eval:w #1#2
21468   - (#1#2 - 4) / 9 * 9 \__fp_int_eval_end: #3 ;
21469 }
21470 \cs_new:Npn \__fp_trigd_large_auxiii:www #1; #2; #3!
21471 {
21472   \if_int_compare:w #1 < 4500 \exp_stop_f:
21473   \exp_after:wN \__fp_use_i_until_s:nw
21474   \exp_after:wN \__fp_fixed_continue:wn
21475   \else:
21476     + 1
21477   \fi:
21478   \__fp_fixed_sub:wwn {9000}{0000}{0000}{0000}{0000}{0000};
21479   {#1}#2{0000}{0000};
21480   { \__fp_trigd_small:ww 2, }
21481 }

```

(End definition for `_fp_trigd_large:ww` and others.)

34.1.5 Argument reduction in radians

Arguments greater or equal to 1 need to be reduced to a range where we only need a few terms of the Taylor series. We reduce to the range $[0, 2\pi]$ by subtracting multiples of 2π , then to the smaller range $[0, \pi/2]$ by subtracting multiples of $\pi/2$ (keeping track of how many times $\pi/2$ is subtracted), then to $[0, \pi/4]$ by mapping $x \rightarrow \pi/2 - x$ if appropriate. When the argument is very large, say, 10^{100} , an equally large multiple of 2π must be subtracted, hence we must work with a very good approximation of 2π in order to get a sensible remainder modulo 2π .

Specifically, we multiply the argument by an approximation of $1/(2\pi)$ with 10048 digits, then discard the integer part of the result, keeping 52 digits of the fractional part. From the fractional part of $x/(2\pi)$ we deduce the octant (quotient of the first three digits by 125). We then multiply by 8 or -8 (the latter when the octant is odd), ignore any integer part (related to the octant), and convert the fractional part to an extended precision number, before multiplying by $\pi/4$ to convert back to a value in radians in $[0, \pi/4]$.

It is possible to prove that given the precision of floating points and their range of exponents, the 52 digits may start at most with 24 zeros. The 5 last digits are affected by carries from computations which are not done, hence we are left with at least $52 - 24 - 5 = 23$ significant digits, enough to round correctly up to $0.6 \cdot \text{ulp}$ in all cases.

`\c_fp_trig_intarray` This integer array stores blocks of 8 decimals of $10^{-16}/(2\pi)$. Each entry is 10^8 plus an 8 digit number storing 8 decimals. In total we store 10112 decimals of $10^{-16}/(2\pi)$. The number of decimals we really need is the maximum exponent plus the number of digits we later need, 52, plus 12 (4 – 1 groups of 4 digits). The memory footprint (1/2 byte per digit) is the same as an earlier method of storing the data as a control sequence name, but the major advantage is that we can unpack specific subsets of the digits without unpacking the 10112 decimals.

```

21482 \intarray_const_from_clist:Nn \c\_fp_trig_intarray
21483 {
21484     100000000, 100000000, 115915494, 130918953, 135768883, 176337251,
21485     143620344, 159645740, 145644874, 176673440, 158896797, 163422653,
21486     150901138, 102766253, 108595607, 128427267, 157958036, 189291184,
21487     161145786, 152877967, 141073169, 198392292, 139966937, 140907757,
21488     130777463, 196925307, 168871739, 128962173, 197661693, 136239024,
21489     117236290, 111832380, 111422269, 197557159, 140461890, 108690267,
21490     139561204, 189410936, 193784408, 155287230, 199946443, 140024867,
21491     123477394, 159610898, 132309678, 130749061, 166986462, 180469944,
21492     186521878, 181574786, 156696424, 110389958, 174139348, 160998386,
21493     180991999, 162442875, 158517117, 188584311, 117518767, 116054654,
21494     175369880, 109739460, 136475933, 137680593, 102494496, 163530532,
21495     171567755, 103220324, 177781639, 171660229, 146748119, 159816584,
21496     106060168, 103035998, 113391198, 174988327, 186654435, 127975507,
21497     100162406, 177564388, 184957131, 108801221, 199376147, 168137776,
21498     147378906, 133068046, 145797848, 117613124, 127314069, 196077502,
21499     145002977, 159857089, 105690279, 167851315, 125210016, 131774602,
21500     109248116, 106240561, 145620314, 164840892, 148459191, 143521157,
21501     154075562, 100871526, 160680221, 171591407, 157474582, 172259774,
21502     162853998, 175155329, 139081398, 117724093, 158254797, 107332871,
21503     190406999, 175907657, 170784934, 170393589, 182808717, 134256403,

```

21504 166895116, 162545705, 194332763, 112686500, 126122717, 197115321,
 21505 112599504, 138667945, 103762556, 108363171, 116952597, 158128224,
 21506 194162333, 143145106, 112353687, 185631136, 136692167, 114206974,
 21507 169601292, 150578336, 105311960, 185945098, 139556718, 170995474,
 21508 165104316, 123815517, 158083944, 129799709, 199505254, 138756612,
 21509 194458833, 106846050, 178529151, 151410404, 189298850, 163881607,
 21510 176196993, 107341038, 199957869, 118905980, 193737772, 106187543,
 21511 122271893, 101366255, 126123878, 103875388, 181106814, 106765434,
 21512 108282785, 126933426, 179955607, 107903860, 160352738, 199624512,
 21513 159957492, 176297023, 159409558, 143011648, 129641185, 157771240,
 21514 157544494, 157021789, 176979240, 194903272, 194770216, 164960356,
 21515 153181535, 144003840, 168987471, 176915887, 163190966, 150696440,
 21516 147769706, 187683656, 177810477, 197954503, 153395758, 130188183,
 21517 186879377, 166124814, 195305996, 155802190, 183598751, 103512712,
 21518 190432315, 180498719, 168687775, 194656634, 162210342, 104440855,
 21519 149785037, 192738694, 129353661, 193778292, 187359378, 143470323,
 21520 102371458, 137923557, 111863634, 119294601, 183182291, 196416500,
 21521 187830793, 131353497, 179099745, 186492902, 167450609, 189368909,
 21522 145883050, 133703053, 180547312, 132158094, 131976760, 132283131,
 21523 141898097, 149822438, 133517435, 169898475, 101039500, 168388003,
 21524 197867235, 199608024, 100273901, 108749548, 154787923, 156826113,
 21525 199489032, 168997427, 108349611, 149208289, 103776784, 174303550,
 21526 145684560, 183671479, 130845672, 133270354, 185392556, 120208683,
 21527 193240995, 162211753, 131839402, 109707935, 170774965, 149880868,
 21528 160663609, 168661967, 103747454, 121028312, 119251846, 122483499,
 21529 111611495, 166556037, 196967613, 199312829, 196077608, 127799010,
 21530 107830360, 102338272, 198790854, 102387615, 157445430, 192601191,
 21531 100543379, 198389046, 154921248, 129516070, 172853005, 122721023,
 21532 160175233, 113173179, 175931105, 103281551, 109373913, 163964530,
 21533 157926071, 180083617, 195487672, 146459804, 173977292, 144810920,
 21534 109371257, 186918332, 189588628, 139904358, 168666639, 175673445,
 21535 114095036, 137327191, 174311388, 106638307, 125923027, 159734506,
 21536 105482127, 178037065, 133778303, 121709877, 134966568, 149080032,
 21537 169885067, 141791464, 168350828, 116168533, 114336160, 173099514,
 21538 198531198, 119733758, 144420984, 116559541, 152250643, 139431286,
 21539 144403838, 183561508, 179771645, 101706470, 167518774, 156059160,
 21540 187168578, 157939226, 123475633, 117111329, 198655941, 159689071,
 21541 198506887, 144230057, 151919770, 156900382, 118392562, 120338742,
 21542 135362568, 108354156, 151729710, 188117217, 195936832, 156488518,
 21543 174997487, 108553116, 159830610, 113921445, 144601614, 188452770,
 21544 125114110, 170248521, 173974510, 138667364, 103872860, 109967489,
 21545 131735618, 112071174, 104788993, 168886556, 192307848, 150230570,
 21546 157144063, 163863202, 136852010, 174100574, 185922811, 115721968,
 21547 100397824, 175953001, 166958522, 112303464, 118773650, 143546764,
 21548 164565659, 171901123, 108476709, 193097085, 191283646, 166919177,
 21549 169387914, 133315566, 150669813, 121641521, 100895711, 172862384,
 21550 126070678, 145176011, 113450800, 169947684, 122356989, 162488051,
 21551 157759809, 153397080, 185475059, 175362656, 149034394, 145420581,
 21552 178864356, 183042000, 131509559, 147434392, 152544850, 167491429,
 21553 108647514, 142303321, 133245695, 111634945, 167753939, 142403609,
 21554 105438335, 152829243, 142203494, 184366151, 146632286, 102477666,
 21555 166049531, 140657343, 157553014, 109082798, 180914786, 169343492,
 21556 127376026, 134997829, 195701816, 119643212, 133140475, 176289748,
 21557 140828911, 174097478, 126378991, 181699939, 148749771, 151989818,

21558	172666294,	160183053,	195832752,	109236350,	168538892,	128468247,
21559	125997252,	183007668,	156937583,	165972291,	198244297,	147406163,
21560	181831139,	158306744,	134851692,	185973832,	137392662,	140243450,
21561	119978099,	140402189,	161348342,	173613676,	144991382,	171541660,
21562	163424829,	136374185,	106122610,	186132119,	198633462,	184709941,
21563	183994274,	129559156,	128333990,	148038211,	175011612,	111667205,
21564	119125793,	103552929,	124113440,	131161341,	112495318,	138592695,
21565	184904438,	146807849,	109739828,	108855297,	104515305,	139914009,
21566	188698840,	188365483,	166522246,	168624087,	125401404,	100911787,
21567	142122045,	123075334,	173972538,	114940388,	141905868,	142311594,
21568	163227443,	139066125,	116239310,	162831953,	123883392,	113153455,
21569	163815117,	152035108,	174595582,	101123754,	135976815,	153401874,
21570	107394340,	136339780,	138817210,	104531691,	182951948,	179591767,
21571	139541778,	179243527,	161740724,	160593916,	102732282,	187946819,
21572	136491289,	149714953,	143255272,	135916592,	198072479,	198580612,
21573	169007332,	118844526,	179433504,	155801952,	149256630,	162048766,
21574	116134365,	133992028,	175452085,	155344144,	109905129,	182727454,
21575	165911813,	122232840,	151166615,	165070983,	175574337,	129548631,
21576	120411217,	116380915,	160616116,	157320000,	183306114,	160618128,
21577	103262586,	195951602,	146321661,	138576614,	180471993,	127077713,
21578	116441201,	159496011,	106328305,	120759583,	148503050,	179095584,
21579	198298218,	167402898,	138551383,	123957020,	180763975,	150429225,
21580	198476470,	171016426,	197438450,	143091658,	164528360,	132493360,
21581	143546572,	137557916,	113663241,	120457809,	196971566,	134022158,
21582	180545794,	131328278,	100552461,	132088901,	187421210,	192448910,
21583	141005215,	149680971,	113720754,	100571096,	134066431,	135745439,
21584	191597694,	135788920,	179342561,	177830222,	137011486,	142492523,
21585	192487287,	113132021,	176673607,	156645598,	127260957,	141566023,
21586	143787436,	129132109,	174858971,	150713073,	191040726,	143541417,
21587	197057222,	165479803,	181512759,	157912400,	125344680,	148220261,
21588	173422990,	101020483,	106246303,	137964746,	178190501,	181183037,
21589	151538028,	179523433,	141955021,	135689770,	191290561,	143178787,
21590	192086205,	174499925,	178975690,	118492103,	124206471,	138519113,
21591	188147564,	102097605,	154895793,	178514140,	141453051,	151583964,
21592	128232654,	106020603,	131189158,	165702720,	186250269,	191639375,
21593	115278873,	160608114,	155694842,	110322407,	177272742,	116513642,
21594	134366992,	171634030,	194053074,	180652685,	109301658,	192136921,
21595	141431293,	171341061,	157153714,	106203978,	147618426,	150297807,
21596	186062669,	169960809,	118422347,	163350477,	146719017,	145045144,
21597	161663828,	146208240,	186735951,	102371302,	190444377,	194085350,
21598	134454426,	133413062,	163074595,	113830310,	122931469,	134466832,
21599	185176632,	182415152,	110179422,	164439571,	181217170,	121756492,
21600	119644493,	196532222,	118765848,	182445119,	109401340,	150443213,
21601	198586286,	121083179,	139396084,	143898019,	114787389,	177233102,
21602	186310131,	148695521,	126205182,	178063494,	157118662,	177825659,
21603	188310053,	151552316,	165984394,	109022180,	163144545,	121212978,
21604	197344714,	188741258,	126822386,	102360271,	109981191,	152056882,
21605	134723983,	158013366,	106837863,	128867928,	161973236,	172536066,
21606	185216856,	132011948,	197807339,	158419190,	166595838,	167852941,
21607	124187182,	117279875,	106103946,	106481958,	157456200,	160892122,
21608	184163943,	173846549,	158993202,	184812364,	133466119,	170732430,
21609	195458590,	173361878,	162906318,	150165106,	126757685,	112163575,
21610	188696307,	145199922,	100107766,	176830946,	198149756,	122682434,
21611	179367131,	108412102,	119520899,	148191244,	140487511,	171059184,

21612	141399078,	189455775,	118462161,	190415309,	134543802,	180893862,
21613	180732375,	178615267,	179711433,	123241969,	185780563,	176301808,
21614	184386640,	160717536,	183213626,	129671224,	126094285,	140110963,
21615	121826276,	151201170,	122552929,	128965559,	146082049,	138409069,
21616	107606920,	103954646,	119164002,	115673360,	117909631,	187289199,
21617	186343410,	186903200,	157966371,	103128612,	135698881,	176403642,
21618	152540837,	109810814,	183519031,	121318624,	172281810,	150845123,
21619	169019064,	166322359,	138872454,	163073727,	128087898,	130041018,
21620	194859136,	173742589,	141812405,	167291912,	138003306,	134499821,
21621	196315803,	186381054,	124578934,	150084553,	128031351,	118843410,
21622	107373060,	159565443,	173624887,	171292628,	198074235,	139074061,
21623	178690578,	144431052,	174262641,	176783005,	182214864,	162289361,
21624	192966929,	192033046,	169332843,	181580535,	164864073,	118444059,
21625	195496893,	153773183,	167266131,	130108623,	158802128,	180432893,
21626	144562140,	147978945,	142337360,	158506327,	104399819,	132635916,
21627	168734194,	136567839,	101281912,	120281622,	195003330,	112236091,
21628	185875592,	101959081,	122415367,	194990954,	148881099,	175891989,
21629	108115811,	163538891,	163394029,	123722049,	184837522,	142362091,
21630	100834097,	156679171,	100841679,	157022331,	178971071,	102928884,
21631	189701309,	195339954,	124415335,	106062584,	139214524,	133864640,
21632	134324406,	157317477,	155340540,	144810061,	177612569,	108474646,
21633	114329765,	143900008,	138265211,	145210162,	136643111,	197987319,
21634	102751191,	144121361,	169620456,	193602633,	161023559,	162140467,
21635	102901215,	167964187,	135746835,	187317233,	110047459,	163339773,
21636	124770449,	118885134,	141536376,	100915375,	164267438,	145016622,
21637	113937193,	106748706,	128815954,	164819775,	119220771,	102367432,
21638	189062690,	170911791,	194127762,	112245117,	123546771,	115640433,
21639	135772061,	166615646,	174474627,	130562291,	133320309,	153340551,
21640	138417181,	194605321,	150142632,	180008795,	151813296,	175497284,
21641	167018836,	157425342,	150169942,	131069156,	134310662,	160434122,
21642	105213831,	158797111,	150754540,	163290657,	102484886,	148697402,
21643	187203725,	198692811,	149360627,	140384233,	128749423,	132178578,
21644	177507355,	171857043,	178737969,	134023369,	102911446,	196144864,
21645	197697194,	134527467,	144296030,	189437192,	154052665,	188907106,
21646	162062575,	150993037,	199766583,	167936112,	181374511,	104971506,
21647	115378374,	135795558,	167972129,	135876446,	130937572,	103221320,
21648	124605656,	161129971,	131027586,	191128460,	143251843,	143269155,
21649	129284585,	173495971,	150425653,	199302112,	118494723,	121323805,
21650	116549802,	190991967,	168151180,	122483192,	151273721,	199792134,
21651	133106764,	121874844,	126215985,	112167639,	167793529,	182985195,
21652	185453921,	106957880,	158685312,	132775454,	133229161,	198905318,
21653	190537253,	191582222,	192325972,	178133427,	181825606,	148823337,
21654	160719681,	101448145,	131983362,	137910767,	112550175,	128826351,
21655	183649210,	135725874,	110356573,	189469487,	154446940,	118175923,
21656	106093708,	128146501,	185742532,	149692127,	164624247,	183221076,
21657	154737505,	168198834,	156410354,	158027261,	125228550,	131543250,
21658	139591848,	191898263,	104987591,	115406321,	103542638,	190012837,
21659	142615518,	178773183,	175862355,	117537850,	169565995,	170028011,
21660	158412588,	170150030,	117025916,	174630208,	142412449,	112839238,
21661	105257725,	114737141,	123102301,	172563968,	130555358,	132628403,
21662	183638157,	168682846,	143304568,	105994018,	170010719,	152092970,
21663	117799058,	132164175,	179868116,	158654714,	177489647,	116547948,
21664	183121404,	131836079,	184431405,	157311793,	149677763,	173989893,
21665	102277656,	107058530,	140837477,	152640947,	143507039,	152145247,

```

21666 101683884, 107090870, 161471944, 137225650, 128231458, 172995869,
21667 173831689, 171268519, 139042297, 111072135, 107569780, 137262545,
21668 181410950, 138270388, 198736451, 162848201, 180468288, 120582913,
21669 153390138, 135649144, 130040157, 106509887, 192671541, 174507066,
21670 186888783, 143805558, 135011967, 145862340, 180595327, 124727843,
21671 182925939, 157715840, 136885940, 198993925, 152416883, 178793572,
21672 179679516, 154076673, 192703125, 164187609, 162190243, 104699348,
21673 159891990, 160012977, 174692145, 132970421, 167781726, 115178506,
21674 153008552, 155999794, 102099694, 155431545, 127458567, 104403686,
21675 168042864, 184045128, 181182309, 179349696, 127218364, 192935516,
21676 120298724, 169583299, 148193297, 183358034, 159023227, 105261254,
21677 121144370, 184359584, 194433836, 138388317, 175184116, 108817112,
21678 151279233, 137457721, 193398208, 119005406, 132929377, 175306906,
21679 160741530, 149976826, 147124407, 176881724, 186734216, 185881509,
21680 191334220, 175930947, 117385515, 193408089, 157124410, 163472089,
21681 131949128, 180783576, 131158294, 100549708, 191802336, 165960770,
21682 170927599, 101052702, 181508688, 197828549, 143403726, 142729262,
21683 110348701, 139928688, 153550062, 106151434, 130786653, 196085995,
21684 100587149, 139141652, 106530207, 100852656, 124074703, 166073660,
21685 153338052, 163766757, 120188394, 197277047, 122215363, 138511354,
21686 183463624, 161985542, 159938719, 133367482, 104220974, 149956672,
21687 170250544, 164232439, 157506869, 159133019, 137469191, 142980999,
21688 134242305, 150172665, 121209241, 145596259, 160554427, 159095199,
21689 168243130, 184279693, 171132070, 121049823, 123819574, 171759855,
21690 119501864, 163094029, 175943631, 194450091, 191506160, 149228764,
21691 132319212, 197034460, 193584259, 126727638, 168143633, 109856853,
21692 127860243, 132141052, 133076065, 188414958, 158718197, 107124299,
21693 159592267, 181172796, 144388537, 196763139, 127431422, 179531145,
21694 100064922, 112650013, 132686230, 121550837,
21695 }

```

(End definition for \c__fp_trig_intarray.)

__fp_trig_large:ww The exponent #1 is between 1 and 10000. We wish to look up decimals $10^{\#1-16}/(2\pi)$ starting from the digit #1 + 1. Since they are stored in batches of 8, compute $\lfloor \#1/8 \rfloor$ and fetch blocks of 8 digits starting there. The numbering of items in \c__fp_trig_intarray starts at 1, so the block $\lfloor \#1/8 \rfloor + 1$ contains the digit we want, at one of the eight positions. Each call to \int_value:w __kernel_intarray_item:Nn expands the next, until being stopped by __fp_trig_large_auxiii:w using \exp_stop_f:. Once all these blocks are unpacked, the \exp_stop_f: and 0 to 7 digits are removed by \use_none:n...n. Finally, __fp_trig_large_auxii:w packs 64 digits (there are between 65 and 72 at this point) into groups of 4 and the auxv auxiliary is called.

```

21696 \cs_new:Npn \__fp_trig_large:ww #1, #2#3#4#5#6;
21697 {
21698   \exp_after:wN \__fp_trig_large_auxi:w
21699   \int_value:w \__fp_int_eval:w (#1 - 4) / 8 \exp_after:wN ,
21700   \int_value:w #1 , ;
21701   {#2}{#3}{#4}{#5} ;
21702 }
21703 \cs_new:Npn \__fp_trig_large_auxi:w #1, #2,
21704 {
21705   \exp_after:wN \exp_after:wN
21706   \exp_after:wN \__fp_trig_large_auxii:w
21707   \cs:w

```



```

21708     use_none:n \prg_replicate:nn { #2 - #1 * 8 } { n }
21709     \exp_after:wN
21710   \cs_end:
21711   \int_value:w
21712   \__kernel_intarray_item:Nn \c__fp_trig_intarray
21713     { \__fp_int_eval:w #1 + 1 \scan_stop: }
21714   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
21715   \__kernel_intarray_item:Nn \c__fp_trig_intarray
21716     { \__fp_int_eval:w #1 + 2 \scan_stop: }
21717   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
21718   \__kernel_intarray_item:Nn \c__fp_trig_intarray
21719     { \__fp_int_eval:w #1 + 3 \scan_stop: }
21720   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
21721   \__kernel_intarray_item:Nn \c__fp_trig_intarray
21722     { \__fp_int_eval:w #1 + 4 \scan_stop: }
21723   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
21724   \__kernel_intarray_item:Nn \c__fp_trig_intarray
21725     { \__fp_int_eval:w #1 + 5 \scan_stop: }
21726   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
21727   \__kernel_intarray_item:Nn \c__fp_trig_intarray
21728     { \__fp_int_eval:w #1 + 6 \scan_stop: }
21729   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
21730   \__kernel_intarray_item:Nn \c__fp_trig_intarray
21731     { \__fp_int_eval:w #1 + 7 \scan_stop: }
21732   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
21733   \__kernel_intarray_item:Nn \c__fp_trig_intarray
21734     { \__fp_int_eval:w #1 + 8 \scan_stop: }
21735   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
21736   \__kernel_intarray_item:Nn \c__fp_trig_intarray
21737     { \__fp_int_eval:w #1 + 9 \scan_stop: }
21738   \exp_stop_f:
21739 }
21740 \cs_new:Npn \__fp_trig_large_auxii:w
21741 {
21742   \__fp_pack_twice_four:wNNNNNNNN \__fp_pack_twice_four:wNNNNNNNN
21743   \__fp_pack_twice_four:wNNNNNNNN \__fp_pack_twice_four:wNNNNNNNN
21744   \__fp_pack_twice_four:wNNNNNNNN \__fp_pack_twice_four:wNNNNNNNN
21745   \__fp_pack_twice_four:wNNNNNNNN \__fp_pack_twice_four:wNNNNNNNN
21746   \__fp_trig_large_auxv:www ;
21747 }
21748 \cs_new:Npn \__fp_trig_large_auxiii:w 1 { \exp_stop_f: }

```

(End definition for __fp_trig_large:ww and others.)

$\backslash_fp_trig_large_auxv:www$
 $\backslash_fp_trig_large_auxvi:wNNNNNNNN$
 $\backslash_fp_trig_large_pack:NNNNNw$

First come the first 64 digits of the fractional part of $10^{1-16}/(2\pi)$, arranged in 16 blocks of 4, and ending with a semicolon. Then a few more digits of the same fractional part, ending with a semicolon, then 4 blocks of 4 digits holding the significand of the original argument. Multiply the 16-digit significand with the 64-digit fractional part: the `auxvi` auxiliary receives the significand as `#2#3#4#5` and 16 digits of the fractional part as `#6#7#8#9`, and computes one step of the usual ladder of `pack` functions we use for multiplication (see *e.g.*, `__fp_fixed_mul:wwn`), then discards one block of the fractional part to set things up for the next step of the ladder. We perform 13 such steps, replacing the last `middle` shift by the appropriate `trailing` shift, then discard the significand and remaining 3 blocks from the fractional part, as there are not enough digits to compute

any more step in the ladder. The last semicolon closes the ladder, and we return control to the `auxvii` auxiliary.

```

21749 \cs_new:Npn \__fp_trig_large_auxv:www #1; #2; #3;
21750 {
21751   \exp_after:wN \__fp_use_i_until_s:nw
21752   \exp_after:wN \__fp_trig_large_auxvii:w
21753   \int_value:w \__fp_int_eval:w \c__fp_leading_shift_int
21754   \prg_replicate:nn { 13 }
21755   { \__fp_trig_large_auxvi:wnnnnnnnn }
21756   + \c__fp_trailing_shift_int - \c__fp_middle_shift_int
21757   \__fp_use_i_until_s:nw
21758   ; #3 #1 ; ;
21759 }
21760 \cs_new:Npn \__fp_trig_large_auxvi:wnnnnnnnn #1; #2#3#4#5#6#7#8#9
21761 {
21762   \exp_after:wN \__fp_trig_large_pack:NNNNNw
21763   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
21764   + #2*#9 + #3*#8 + #4*#7 + #5*#6
21765   #1; {#2}{#3}{#4}{#5} {#7}{#8}{#9}
21766 }
21767 \cs_new:Npn \__fp_trig_large_pack:NNNNNw #1#2#3#4#5#6;
21768 { + #1#2#3#4#5 ; #6 }

```

(End definition for `__fp_trig_large_auxv:www`, `__fp_trig_large_auxvi:wnnnnnnnn`, and `__fp_trig_large_pack:NNNNNw`.)

```

\__fp_trig_large_auxvii:w
\__fp_trig_large_auxviii:w
\__fp_trig_large_auxix:Nw
\__fp_trig_large_auxx:wNNNNN
\__fp_trig_large_auxxi:w

```

The `auxvii` auxiliary is followed by 52 digits and a semicolon. We find the octant as the integer part of 8 times what follows, or equivalently as the integer part of $\#1\#2\#3/125$, and add it to the surrounding integer expression for the octant. We then compute 8 times the 52-digit number, with a minus sign if the octant is odd. Again, the last `middle` shift is converted to a `trailing` shift. Any integer part (including negative values which come up when the octant is odd) is discarded by `__fp_use_i_until_s:nw`. The resulting fractional part should then be converted to radians by multiplying by $2\pi/8$, but first, build an extended precision number by abusing `__fp_ep_to_ep_loop:N` with the appropriate trailing markers. Finally, `__fp_trig_small:ww` sets up the argument for the functions which compute the Taylor series.

```

21769 \cs_new:Npn \__fp_trig_large_auxvii:w #1#2#3
21770 {
21771   \exp_after:wN \__fp_trig_large_auxviii:ww
21772   \int_value:w \__fp_int_eval:w (#1#2#3 - 62) / 125 ;
21773   #1#2#3
21774 }
21775 \cs_new:Npn \__fp_trig_large_auxviii:ww #1;
21776 {
21777   + #1
21778   \if_int_odd:w #1 \exp_stop_f:
21779     \exp_after:wN \__fp_trig_large_auxix:Nw
21780     \exp_after:wN -
21781   \else:
21782     \exp_after:wN \__fp_trig_large_auxix:Nw
21783     \exp_after:wN +
21784   \fi:
21785 }

```

```

21786 \cs_new:Npn \__fp_trig_large_auxix:Nw
21787 {
21788   \exp_after:wN \__fp_use_i_until_s:nw
21789   \exp_after:wN \__fp_trig_large_auxxi:w
21790   \int_value:w \__fp_int_eval:w \c__fp_leading_shift_int
21791   \prg_replicate:nn { 13 }
21792   { \__fp_trig_large_auxx:wNNNNN }
21793   + \c__fp_trailing_shift_int - \c__fp_middle_shift_int
21794   ;
21795 }
21796 \cs_new:Npn \__fp_trig_large_auxx:wNNNNN #1; #2 #3#4#5#6
21797 {
21798   \exp_after:wN \__fp_trig_large_pack:NNNNNw
21799   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
21800   #2 8 * #3#4#5#6
21801   #1; #2
21802 }
21803 \cs_new:Npn \__fp_trig_large_auxxi:w #1;
21804 {
21805   \exp_after:wN \__fp_ep_mul_raw:wwwN
21806   \int_value:w \__fp_int_eval:w 0 \__fp_ep_to_ep_loop:N #1 ; ; !
21807   0,{7853}{9816}{3397}{4483}{0961}{5661};
21808   \__fp_trig_small:ww
21809 }

```

(End definition for __fp_trig_large_auxvii:w and others.)

34.1.6 Computing the power series

__fp_sin_series_o:NNwww Here we receive a conversion function __fp_ep_to_float_o:wwN or __fp_ep_inv_to_float_o:wwN, a *sign* (0 or 2), a (non-negative) *octant* delimited by a dot, a *fixed point* number delimited by a semicolon, and an extended-precision number. The auxiliary receives:

- the conversion function #1;
- the final sign, which depends on the octant #3 and the sign #2;
- the octant #3, which controls the series we use;
- the square #4 * #4 of the argument as a fixed point number, computed with __fp_fixed_mul:wwn;
- the number itself as an extended-precision number.

If the octant is in $\{1, 2, 5, 6, \dots\}$, we are near an extremum of the function and we use the series

$$\cos(x) = 1 - x^2 \left(\frac{1}{2!} - x^2 \left(\frac{1}{4!} - x^2 \left(\dots \right) \right) \right).$$

Otherwise, the series

$$\sin(x) = x \left(1 - x^2 \left(\frac{1}{3!} - x^2 \left(\frac{1}{5!} - x^2 \left(\dots \right) \right) \right) \right)$$

is used. Finally, the extended-precision number is converted to a floating point number with the given sign, and `__fp_sanitizew` checks for overflow and underflow.

```

21810 \cs_new:Npn \__fp_sin_series_o:NNwww #1#2#3. #4;
21811 {
21812   \__fp_fixed_mul:wwn #4; #4;
21813   {
21814     \exp_after:wN \__fp_sin_series_aux_o:NNwww
21815     \exp_after:wN #1
21816     \int_value:w
21817     \if_int_odd:w \__fp_int_eval:w (#3 + 2) / 4 \__fp_int_eval_end:
21818       #2
21819     \else:
21820       \if_meaning:w #2 0 2 \else: 0 \fi:
21821     \fi:
21822     {#3}
21823   }
21824 }
21825 \cs_new:Npn \__fp_sin_series_aux_o:NNwww #1#2#3 #4; #5,#6;
21826 {
21827   \if_int_odd:w \__fp_int_eval:w #3 / 2 \__fp_int_eval_end:
21828     \exp_after:wN \use_i:nn
21829   \else:
21830     \exp_after:wN \use_ii:nn
21831   \fi:
21832   { % 1/18!
21833     \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0001}{5619}{2070};
21834     #4;{0000}{0000}{0000}{0477}{9477}{3324};
21835     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0011}{4707}{4559}{7730};
21836     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{2087}{6756}{9878}{6810};
21837     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0027}{5573}{1922}{3985}{8907};
21838     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{2480}{1587}{3015}{8730}{1587};
21839     \__fp_fixed_mul_sub_back:wwwn #4;{0013}{8888}{8888}{8888}{8888}{8889};
21840     \__fp_fixed_mul_sub_back:wwwn #4;{0416}{6666}{6666}{6666}{6666}{6667};
21841     \__fp_fixed_mul_sub_back:wwwn #4;{5000}{0000}{0000}{0000}{0000}{0000};
21842     \__fp_fixed_mul_sub_back:wwwn#4;{10000}{0000}{0000}{0000}{0000}{0000};
21843     { \__fp_fixed_continue:wn 0, }
21844   }
21845   { % 1/17!
21846     \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0028}{1145}{7254};
21847     #4;{0000}{0000}{0000}{7647}{1637}{3182};
21848     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0160}{5904}{3836}{8216};
21849     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0002}{5052}{1083}{8544}{1719};
21850     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0275}{5731}{9223}{9858}{9065};
21851     \__fp_fixed_mul_sub_back:wwwn #4;{0001}{9841}{2698}{4126}{9841}{2698};
21852     \__fp_fixed_mul_sub_back:wwwn #4;{0083}{3333}{3333}{3333}{3333}{3333};
21853     \__fp_fixed_mul_sub_back:wwwn #4;{1666}{6666}{6666}{6666}{6666}{6667};
21854     \__fp_fixed_mul_sub_back:wwwn#4;{10000}{0000}{0000}{0000}{0000}{0000};
21855     { \__fp_ep_mul:wwwn 0, } #5,#6;
21856   }
21857   {
21858     \exp_after:wN \__fp_sanitizew
21859     \exp_after:wN #2
21860     \int_value:w \__fp_int_eval:w #1
21861   }

```

```

21862     #2
21863 }

```

(End definition for `_fp_sin_series_o:NNwww` and `_fp_sin_series_aux_o:NNwww`.)

```

\_fp_tan_series_o:NNwww
\_fp_tan_series_aux_o:Nnwww

```

Contrarily to `_fp_sin_series_o:NNwww` which received a conversion auxiliary as `#1`, here, `#1` is 0 for tangent and 2 for cotangent. Consider first the case of the tangent. The octant `#3` starts at 1, which means that it is 1 or 2 for $|x| \in [0, \pi/2]$, it is 3 or 4 for $|x| \in [\pi/2, \pi]$, and so on: the intervals on which $\tan|x| \geq 0$ coincide with those for which $\lfloor (\#3 + 1)/2 \rfloor$ is odd. We also have to take into account the original sign of x to get the sign of the final result; it is straightforward to check that the first `\int_value:w` expansion produces 0 for a positive final result, and 2 otherwise. A similar story holds for $\cot(x)$.

The auxiliary receives the sign, the octant, the square of the (reduced) input, and the (reduced) input (an extended-precision number) as arguments. It then computes the numerator and denominator of

$$\tan(x) \simeq \frac{x(1 - x^2(a_1 - x^2(a_2 - x^2(a_3 - x^2(a_4 - x^2a_5))))))}{1 - x^2(b_1 - x^2(b_2 - x^2(b_3 - x^2(b_4 - x^2b_5)))}.$$

The ratio is computed by `_fp_ep_div:wwwn`, then converted to a floating point number. For octants `#3` (really, quadrants) next to a pole of the functions, the fixed point numerator and denominator are exchanged before computing the ratio. Note that this `\if_int_odd:w` test relies on the fact that the octant is at least 1.

```

21864 \cs_new:Npn \_fp_tan_series_o:NNwww #1#2#3. #4;
21865 {
21866   \_fp_fixed_mul:wwn #4; #4;
21867   {
21868     \exp_after:wN \_fp_tan_series_aux_o:Nnwww
21869     \int_value:w
21870     \if_int_odd:w \_fp_int_eval:w #3 / 2 \_fp_int_eval_end:
21871     \exp_after:wN \reverse_if:N
21872     \fi:
21873     \if_meaning:w #1#2 2 \else: 0 \fi:
21874     {#3}
21875   }
21876 }
21877 \cs_new:Npn \_fp_tan_series_aux_o:Nnwww #1 #2 #3; #4,#5;
21878 {
21879   \_fp_fixed_mul_sub_back:wwwn {0000}{0000}{1527}{3493}{0856}{7059};
21880   #3; {0000}{0159}{6080}{0274}{5257}{6472};
21881   \_fp_fixed_mul_sub_back:wwwn #3; {0002}{4571}{2320}{0157}{2558}{8481};
21882   \_fp_fixed_mul_sub_back:wwwn #3; {0115}{5830}{7533}{5397}{3168}{2147};
21883   \_fp_fixed_mul_sub_back:wwwn #3; {1929}{8245}{6140}{3508}{7719}{2982};
21884   \_fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
21885   { \_fp_ep_mul:wwwn 0, } #4,#5;
21886   {
21887     \_fp_fixed_mul_sub_back:wwwn {0000}{0007}{0258}{0681}{9408}{4706};
21888     #3; {0000}{2343}{7175}{1399}{6151}{7670};
21889     \_fp_fixed_mul_sub_back:wwwn #3; {0019}{2638}{4588}{9232}{8861}{3691};
21890     \_fp_fixed_mul_sub_back:wwwn #3; {0536}{6357}{0691}{4344}{6852}{4252};
21891     \_fp_fixed_mul_sub_back:wwwn #3; {5263}{1578}{9473}{6842}{1052}{6315};
21892     \_fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};

```

```

21893     {
21894         \reverse_if:N \if_int_odd:w
21895         \__fp_int_eval:w (#2 - 1) / 2 \__fp_int_eval_end:
21896         \exp_after:wN \__fp_reverse_args:Nww
21897         \fi:
21898         \__fp_ep_div:wwwn 0,
21899     }
21900 }
21901 {
21902     \exp_after:wN \__fp_sanitizew
21903     \exp_after:wN #1
21904     \int_value:w \__fp_int_eval:w \__fp_ep_to_float_o:wwN
21905 }
21906 #1
21907 }

```

(End definition for `__fp_tan_series_o:NNwww` and `__fp_tan_series_aux_o:Nnwww`.)

34.2 Inverse trigonometric functions

All inverse trigonometric functions (arcsine, arccosine, arctangent, arccotangent, arcsecant, and arcsecant) are based on a function often denoted `atan2`. This function is accessed directly by feeding two arguments to arctangent, and is defined by $\text{atan}(y, x) = \text{atan}(y/x)$ for generic y and x . Its advantages over the conventional arctangent is that it takes values in $[-\pi, \pi]$ rather than $[-\pi/2, \pi/2]$, and that it is better behaved in boundary cases. Other inverse trigonometric functions are expressed in terms of `atan` as

$$\arccos x = \text{atan}(\sqrt{1 - x^2}, x) \quad (5)$$

$$\arcsin x = \text{atan}(x, \sqrt{1 - x^2}) \quad (6)$$

$$\text{asec } x = \text{atan}(\sqrt{x^2 - 1}, 1) \quad (7)$$

$$\text{acsc } x = \text{atan}(1, \sqrt{x^2 - 1}) \quad (8)$$

$$\text{atan } x = \text{atan}(x, 1) \quad (9)$$

$$\text{acot } x = \text{atan}(1, x). \quad (10)$$

Rather than introducing a new function, `atan2`, the arctangent function `atan` is overloaded: it can take one or two arguments. In the comments below, following many texts, we call the first argument y and the second x , because $\text{atan}(y, x) = \text{atan}(y/x)$ is the angular coordinate of the point (x, y) .

As for direct trigonometric functions, the first step in computing $\text{atan}(y, x)$ is argument reduction. The sign of y gives that of the result. We distinguish eight regions where the point $(x, |y|)$ can lie, of angular size roughly $\pi/8$, characterized by their “octant”, between 0 and 7 included. In each region, we compute an arctangent as a Taylor series, then shift this arctangent by the appropriate multiple of $\pi/4$ and sign to get the result. Here is a list of octants, and how we compute the arctangent (we assume $y > 0$; otherwise replace y by $-y$ below):

0 $0 < |y| < 0.41421x$, then $\text{atan } \frac{|y|}{x}$ is given by a nicely convergent Taylor series;

1 $0 < 0.41421x < |y| < x$, then $\text{atan } \frac{|y|}{x} = \frac{\pi}{4} - \text{atan } \frac{x - |y|}{x + |y|}$;

- 2 $0 < 0.41421|y| < x < |y|$, then $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{4} + \operatorname{atan} \frac{-x+|y|}{x+|y|}$;
- 3 $0 < x < 0.41421|y|$, then $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{2} - \operatorname{atan} \frac{x}{|y|}$;
- 4 $0 < -x < 0.41421|y|$, then $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{2} + \operatorname{atan} \frac{-x}{|y|}$;
- 5 $0 < 0.41421|y| < -x < |y|$, then $\operatorname{atan} \frac{|y|}{x} = \frac{3\pi}{4} - \operatorname{atan} \frac{x+|y|}{-x+|y|}$;
- 6 $0 < -0.41421x < |y| < -x$, then $\operatorname{atan} \frac{|y|}{x} = \frac{3\pi}{4} + \operatorname{atan} \frac{-x-|y|}{-x+|y|}$;
- 7 $0 < |y| < -0.41421x$, then $\operatorname{atan} \frac{|y|}{x} = \pi - \operatorname{atan} \frac{|y|}{-x}$.

In the following, we denote by z the ratio among $|\frac{y}{x}|$, $|\frac{x}{y}|$, $|\frac{x+y}{x-y}|$, $|\frac{x-y}{x+y}|$ which appears in the right-hand side above.

34.2.1 Arctangent and arccotangent

`__fp_atan_o:Nw`
`__fp_acot_o:Nw`
`__fp_atan_default:w`

The parsing step manipulates `atan` and `acot` like `min` and `max`, reading in an array of operands, but also leaves `\use_i:nn` or `\use_ii:nn` depending on whether the result should be given in radians or in degrees. The helper `__fp_parse_function_one_two:nnw` checks that the operand is one or two floating point numbers (not tuples) and leaves its second argument or its tail accordingly (its first argument is used for error messages). More precisely if we are given a single floating point number `__fp_atan_default:w` places `\c_one_fp` (expanded) after it; otherwise `__fp_atan_default:w` is omitted by `__fp_parse_function_one_two:nnw`.

```

21908 \cs_new:Npn \__fp_atan_o:Nw #1
21909 {
21910   \__fp_parse_function_one_two:nnw
21911     { #1 { atan } { atand } }
21912     { \__fp_atan_default:w \__fp_atanii_o:Nww #1 }
21913 }
21914 \cs_new:Npn \__fp_acot_o:Nw #1
21915 {
21916   \__fp_parse_function_one_two:nnw
21917     { #1 { acot } { acotd } }
21918     { \__fp_atan_default:w \__fp_acotii_o:Nww #1 }
21919 }
21920 \cs_new:Npx \__fp_atan_default:w #1#2#3 @ { #1 #2 #3 \c_one_fp @ }

```

(End definition for `__fp_atan_o:Nw`, `__fp_acot_o:Nw`, and `__fp_atan_default:w`.)

`__fp_atanii_o:Nww`
`__fp_acotii_o:Nww`

If either operand is `nan`, we return it. If both are normal, we call `__fp_atan_normal_o:NNnwNNw`. If both are zero or both infinity, we call `__fp_atan_inf_o:NNNw` with argument 2, leading to a result among $\{\pm\pi/4, \pm3\pi/4\}$ (in degrees, $\{\pm45, \pm135\}$). Otherwise, one is much bigger than the other, and we call `__fp_atan_inf_o:NNNw` with either an argument of 4, leading to the values $\pm\pi/2$ (in degrees, ±90), or 0, leading to $\{\pm0, \pm\pi\}$ (in degrees, $\{\pm0, \pm180\}$). Since $\operatorname{acot}(x, y) = \operatorname{atan}(y, x)$, `__fp_acotii_o:ww` simply reverses its two arguments.

```

21921 \cs_new:Npn \__fp_atanii_o:Nww
21922   #1 \s__fp \__fp_chk:w #2#3#4; \s__fp \__fp_chk:w #5 #6 @
21923 {
21924   \if_meaning:w 3 #2 \__fp_case_return_i_o:ww \fi:

```

```

21925 \if_meaning:w 3 #5 \__fp_case_return_ii_o:ww \fi:
21926 \if_case:w
21927   \if_meaning:w #2 #5
21928     \if_meaning:w 1 #2 10 \else: 0 \fi:
21929   \else:
21930     \if_int_compare:w #2 > #5 \exp_stop_f: 1 \else: 2 \fi:
21931   \fi:
21932   \exp_stop_f:
21933     \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 2 }
21934   \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 4 }
21935   \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 0 }
21936   \fi:
21937   \__fp_atan_normal_o:NNnwNnw #1
21938   \s__fp \__fp_chk:w #2#3#4;
21939   \s__fp \__fp_chk:w #5 #6
21940 }
21941 \cs_new:Npn \__fp_acotii_o:Nww #1#2; #3;
21942 { \__fp_atanii_o:Nww #1#3; #2; }

```

(End definition for __fp_atanii_o:Nww and __fp_acotii_o:Nww.)

__fp_atan_inf_o:NNNw This auxiliary is called whenever one number is ± 0 or $\pm \infty$ (and neither is NaN). Then the result only depends on the signs, and its value is a multiple of $\pi/4$. We use the same auxiliary as for normal numbers, __fp_atan_combine_o:NwwwwwN, with arguments the final sign #2; the octant #3; $\operatorname{atan} z/z = 1$ as a fixed point number; $z = 0$ as a fixed point number; and $z = 0$ as an extended-precision number. Given the values we provide, $\operatorname{atan} z$ is computed to be 0, and the result is $[#3/2] \cdot \pi/4$ if the sign #5 of x is positive, and $[(7 - #3)/2] \cdot \pi/4$ for negative x , where the divisions are rounded up.

```

21943 \cs_new:Npn \__fp_atan_inf_o:NNNw #1#2#3 \s__fp \__fp_chk:w #4#5#6;
21944 {
21945   \exp_after:wN \__fp_atan_combine_o:NwwwwwN
21946   \exp_after:wN #2
21947   \int_value:w \__fp_int_eval:w
21948   \if_meaning:w 2 #5 7 - \fi: #3 \exp_after:wN ;
21949   \c__fp_one_fixed_tl
21950   {0000}{0000}{0000}{0000}{0000}{0000};
21951   0,{0000}{0000}{0000}{0000}{0000}{0000}; #1
21952 }

```

(End definition for __fp_atan_inf_o:NNNw.)

__fp_atan_normal_o:NNnwNnw Here we simply reorder the floating point data into a pair of signed extended-precision numbers, that is, a sign, an exponent ending with a comma, and a six-block mantissa ending with a semi-colon. This extended precision is required by other inverse trigonometric functions, to compute things like $\operatorname{atan}(x, \sqrt{1 - x^2})$ without intermediate rounding errors.

```

21953 \cs_new_protected:Npn \__fp_atan_normal_o:NNnwNnw
21954   #1 \s__fp \__fp_chk:w 1#2#3#4; \s__fp \__fp_chk:w 1#5#6#7;
21955 {
21956   \__fp_atan_test_o:NwwNwwN
21957   #2 #3, #4{0000}{0000};
21958   #5 #6, #7{0000}{0000}; #1
21959 }

```


(End definition for _fp_atan_normal_o:NNwNnw.)

_fp_atan_test_o:NwwNwwN

This receives: the sign #1 of y , its exponent #2, its 24 digits #3 in groups of 4, and similarly for x . We prepare to call _fp_atan_combine_o:NwwwwwN which expects the sign #1, the octant, the ratio $(\operatorname{atan} z)/z = 1 - \dots$, and the value of z , both as a fixed point number and as an extended-precision floating point number with a mantissa in $[0.01, 1)$. For now, we place #1 as a first argument, and start an integer expression for the octant. The sign of x does not affect z , so we simply leave a contribution to the octant: $\langle \text{octant} \rangle \rightarrow 7 - \langle \text{octant} \rangle$ for negative x . Then we order $|y|$ and $|x|$ in a non-decreasing order: if $|y| > |x|$, insert 3- in the expression for the octant, and swap the two numbers. The finer test with 0.41421 is done by _fp_atan_div:wnwnnw after the operands have been ordered.

```

21960 \cs_new:Npn \_fp_atan_test_o:NwwNwwN #1#2,#3; #4#5,#6;
21961 {
21962   \exp_after:wN \_fp_atan_combine_o:NwwwwwN
21963   \exp_after:wN #1
21964   \int_value:w \_fp_int_eval:w
21965   \if_meaning:w 2 #4
21966     7 - \_fp_int_eval:w
21967   \fi:
21968   \if_int_compare:w
21969     \_fp_ep_compare:www #2,#3; #5,#6; > 0 \exp_stop_f:
21970     3 -
21971   \exp_after:wN \_fp_reverse_args:Nww
21972   \fi:
21973   \_fp_atan_div:wnwnnw #2,#3; #5,#6;
21974 }

```

(End definition for _fp_atan_test_o:NwwNwwN.)

_fp_atan_div:wnwnnw
_fp_atan_near:wwn
_fp_atan_near_aux:wn

This receives two positive numbers a and b (equal to $|x|$ and $|y|$ in some order), each as an exponent and 6 blocks of 4 digits, such that $0 < a < b$. If $0.41421b < a$, the two numbers are “near”, hence the point (y, x) that we started with is closer to the diagonals $\{|y| = |x|\}$ than to the axes $\{xy = 0\}$. In that case, the octant is 1 (possibly combined with the 7- and 3- inserted earlier) and we wish to compute $\operatorname{atan} \frac{b-a}{a+b}$. Otherwise, the octant is 0 (again, combined with earlier terms) and we wish to compute $\operatorname{atan} \frac{a}{b}$. In any case, call _fp_atan_auxi:ww followed by z , as a comma-delimited exponent and a fixed point number.

```

21975 \cs_new:Npn \_fp_atan_div:wnwnnw #1,#2#3; #4,#5#6;
21976 {
21977   \if_int_compare:w
21978     \_fp_int_eval:w 41421 * #5 < #2 000
21979     \if_case:w \_fp_int_eval:w #4 - #1 \_fp_int_eval_end:
21980     00 \or: 0 \fi:
21981   \exp_stop_f:
21982   \exp_after:wN \_fp_atan_near:wwn
21983   \fi:
21984   0
21985   \_fp_ep_div:wwwn #1,{#2}#3; #4,{#5}#6;
21986   \_fp_atan_auxi:ww
21987 }
21988 \cs_new:Npn \_fp_atan_near:wwn
21989   0 \_fp_ep_div:wwwn #1,#2; #3,

```

```

21990 {
21991   1
21992   \__fp_ep_to_fixed:wwn #1 - #3, #2;
21993   \__fp_atan_near_aux:wwn
21994 }
21995 \cs_new:Npn \__fp_atan_near_aux:wwn #1; #2;
21996 {
21997   \__fp_fixed_add:wwn #1; #2;
21998   { \__fp_fixed_sub:wwn #2; #1; { \__fp_ep_div:wwwn 0, } 0, }
21999 }

```

(End definition for __fp_atan_div:wwwnw, __fp_atan_near:wwwn, and __fp_atan_near_aux:wwn.)

__fp_atan_auxi:ww Convert z from a representation as an exponent and a fixed point number in $[0.01, 1)$ to a
 __fp_atan_auxii:w fixed point number only, then set up the call to __fp_atan_Taylor_loop:www, followed
 by the fixed point representation of z and the old representation.

```

22000 \cs_new:Npn \__fp_atan_auxi:ww #1,#2;
22001 { \__fp_ep_to_fixed:wwn #1,#2; \__fp_atan_auxii:w #1,#2; }
22002 \cs_new:Npn \__fp_atan_auxii:w #1;
22003 {
22004   \__fp_fixed_mul:wwn #1; #1;
22005   {
22006     \__fp_atan_Taylor_loop:www 39 ;
22007     {0000}{0000}{0000}{0000}{0000}{0000} ;
22008   }
22009   ! #1;
22010 }

```

(End definition for __fp_atan_auxi:ww and __fp_atan_auxii:w.)

__fp_atan_Taylor_loop:www We compute the series of $(\operatorname{atan} z)/z$. A typical intermediate stage has $\#1 = 2k - 1$,
 __fp_atan_Taylor_break:w $\#2 = \frac{1}{2k+1} - z^2(\frac{1}{2k+3} - z^2(\dots - z^2\frac{1}{39}))$, and $\#3 = z^2$. To go to the next step $k \rightarrow k - 1$,
 we compute $\frac{1}{2k-1}$, then subtract from it z^2 times $\#2$. The loop stops when $k = 0$: then
 $\#2$ is $(\operatorname{atan} z)/z$, and there is a need to clean up all the unnecessary data, end the integer
 expression computing the octant with a semicolon, and leave the result $\#2$ afterwards.

```

22011 \cs_new:Npn \__fp_atan_Taylor_loop:www #1; #2; #3;
22012 {
22013   \if_int_compare:w #1 = -1 \exp_stop_f:
22014   \__fp_atan_Taylor_break:w
22015   \fi:
22016   \exp_after:wN \__fp_fixed_div_int:wwN \c__fp_one_fixed_tl #1;
22017   \__fp_rrot:www \__fp_fixed_mul_sub_back:wwwn #2; #3;
22018   {
22019     \exp_after:wN \__fp_atan_Taylor_loop:www
22020     \int_value:w \__fp_int_eval:w #1 - 2 ;
22021   }
22022   #3;
22023 }
22024 \cs_new:Npn \__fp_atan_Taylor_break:w
22025 \fi: #1 \__fp_fixed_mul_sub_back:wwwn #2; #3 !
22026 { \fi: ; #2 ; }

```

(End definition for __fp_atan_Taylor_loop:www and __fp_atan_Taylor_break:w.)

`__fp_atan_combine_o:NwwwwN` This receives a $\langle sign \rangle$, an $\langle octant \rangle$, a fixed point value of $(\text{atan } z)/z$, a fixed point number z , and another representation of z , as an $\langle exponent \rangle$ and the fixed point number $10^{-\langle exponent \rangle} z$, followed by either `\use_i:nn` (when working in radians) or `\use_ii:nn` (when working in degrees). The function computes the floating point result

$$\langle sign \rangle \left(\left\lceil \frac{\langle octant \rangle}{2} \right\rceil \frac{\pi}{4} + (-1)^{\langle octant \rangle} \frac{\text{atan } z}{z} \cdot z \right), \quad (11)$$

multiplied by $180/\pi$ if working in degrees, and using in any case the most appropriate representation of z . The floating point result is passed to `__fp_sanitize:Nw`, which checks for overflow or underflow. If the octant is 0, leave the exponent #5 for `__fp_sanitize:Nw`, and multiply #3 = $\frac{\text{atan } z}{z}$ with #6, the adjusted z . Otherwise, multiply #3 = $\frac{\text{atan } z}{z}$ with #4 = z , then compute the appropriate multiple of $\frac{\pi}{4}$ and add or subtract the product #3 · #4. In both cases, convert to a floating point with `__fp_fixed_to_float_o:wN`.

```

22027 \cs_new:Npn \__fp_atan_combine_o:NwwwwN #1 #2; #3; #4; #5,#6; #7
22028 {
22029   \exp_after:wN \__fp_sanitize:Nw
22030   \exp_after:wN #1
22031   \int_value:w \__fp_int_eval:w
22032   \if_meaning:w 0 #2
22033     \exp_after:wN \use_i:nn
22034   \else:
22035     \exp_after:wN \use_ii:nn
22036   \fi:
22037   { #5 \__fp_fixed_mul:wwn #3; #6; }
22038   {
22039     \__fp_fixed_mul:wwn #3; #4;
22040     {
22041       \exp_after:wN \__fp_atan_combine_aux:ww
22042       \int_value:w \__fp_int_eval:w #2 / 2 ; #2;
22043     }
22044   }
22045   { #7 \__fp_fixed_to_float_o:wN \__fp_fixed_to_float_rad_o:wN }
22046   #1
22047 }
22048 \cs_new:Npn \__fp_atan_combine_aux:ww #1; #2;
22049 {
22050   \__fp_fixed_mul_short:wwn
22051   {7853}{9816}{3397}{4483}{0961}{5661};
22052   {#1}{0000}{0000};
22053   {
22054     \if_int_odd:w #2 \exp_stop_f:
22055     \exp_after:wN \__fp_fixed_sub:wwn
22056   \else:
22057     \exp_after:wN \__fp_fixed_add:wwn
22058   \fi:
22059   }
22060 }

```

(End definition for `__fp_atan_combine_o:NwwwwN` and `__fp_atan_combine_aux:ww`.)

34.2.2 Arcsine and arccosine

`__fp_asin_o:w` Again, the first argument provided by `l3fp-parse` is `\use_i:nn` if we are to work in radians and `\use_ii:nn` for degrees. Then comes a floating point number. The arcsine of ± 0 or NaN is the same floating point number. The arcsine of $\pm\infty$ raises an invalid operation exception. Otherwise, call an auxiliary common with `__fp_acos_o:w`, feeding it information about what function is being performed (for “invalid operation” exceptions).

```

22061 \cs_new:Npn \__fp_asin_o:w #1 \s__fp \__fp_chk:w #2#3; @
22062 {
22063   \if_case:w #2 \exp_stop_f:
22064     \__fp_case_return_same_o:w
22065   \or:
22066     \__fp_case_use:nw
22067     { \__fp_asin_normal_o:NfwNnnnnw #1 { #1 { asin } { asind } } }
22068   \or:
22069     \__fp_case_use:nw
22070     { \__fp_invalid_operation_o:fw { #1 { asin } { asind } } }
22071   \else:
22072     \__fp_case_return_same_o:w
22073   \fi:
22074   \s__fp \__fp_chk:w #2 #3;
22075 }

```

(End definition for `__fp_asin_o:w`.)

`__fp_acos_o:w` The arccosine of ± 0 is $\pi/2$ (in degrees, 90). The arccosine of $\pm\infty$ raises an invalid operation exception. The arccosine of NaN is itself. Otherwise, call an auxiliary common with `__fp_sin_o:w`, informing it that it was called by `acos` or `acosd`, and preparing to swap some arguments down the line.

```

22076 \cs_new:Npn \__fp_acos_o:w #1 \s__fp \__fp_chk:w #2#3; @
22077 {
22078   \if_case:w #2 \exp_stop_f:
22079     \__fp_case_use:nw { \__fp_atan_inf_o:NNNw #1 0 4 }
22080   \or:
22081     \__fp_case_use:nw
22082     {
22083       \__fp_asin_normal_o:NfwNnnnnw #1 { #1 { acos } { acosd } }
22084       \__fp_reverse_args:Nww
22085     }
22086   \or:
22087     \__fp_case_use:nw
22088     { \__fp_invalid_operation_o:fw { #1 { acos } { acosd } } }
22089   \else:
22090     \__fp_case_return_same_o:w
22091   \fi:
22092   \s__fp \__fp_chk:w #2 #3;
22093 }

```

(End definition for `__fp_acos_o:w`.)

`__fp_asin_normal_o:NfwNnnnnw` If the exponent #5 is at most 0, the operand lies within $(-1, 1)$ and the operation is permitted: call `__fp_asin_auxi_o:NnNw` with the appropriate arguments. If the number is exactly ± 1 (the test works because we know that $\#5 \geq 1$, $\#6\#7 \geq 10000000$, $\#8\#9 \geq 0$,

with equality only for ± 1), we also call `__fp_asin_auxi_o:NnNww`. Otherwise, `__fp_use_i:ww` gets rid of the `asin` auxiliary, and raises instead an invalid operation, because the operand is outside the domain of arcsine or arccosine.

```

22094 \cs_new:Npn \__fp_asin_normal_o:NfwNnnnnw
22095   #1#2#3 \s__fp \__fp_chk:w 1#4#5#6#7#8#9;
22096   {
22097     \if_int_compare:w #5 < 1 \exp_stop_f:
22098       \exp_after:wN \__fp_use_none_until_s:w
22099     \fi:
22100     \if_int_compare:w \__fp_int_eval:w #5 + #6#7 + #8#9 = 1000 0001 ~
22101       \exp_after:wN \__fp_use_none_until_s:w
22102     \fi:
22103     \__fp_use_i:ww
22104     \__fp_invalid_operation_o:fw {#2}
22105     \s__fp \__fp_chk:w 1#4#{#5}{#6}{#7}{#8}{#9};
22106     \__fp_asin_auxi_o:NnNww
22107     #1 {#3} #4 #5,{#6}{#7}{#8}{#9}{0000}{0000};
22108   }

```

(End definition for `__fp_asin_normal_o:NfwNnnnnw`.)

`__fp_asin_auxi_o:NnNww`
`__fp_asin_isqrt:wn`

We compute $x/\sqrt{1-x^2}$. This function is used by `asin` and `acos`, but also by `acsc` and `asec` after inverting the operand, thus it must manipulate extended-precision numbers. First evaluate $1-x^2$ as $(1+x)(1-x)$: this behaves better near $x = 1$. We do the addition/subtraction with fixed point numbers (they are not implemented for extended-precision floats), but go back to extended-precision floats to multiply and compute the inverse square root $1/\sqrt{1-x^2}$. Finally, multiply by the (positive) extended-precision float $|x|$, and feed the (signed) result, and the number $+1$, as arguments to the arctangent function. When computing the arccosine, the arguments $x/\sqrt{1-x^2}$ and $+1$ are swapped by `#2` (`__fp_reverse_args:Nww` in that case) before `__fp_atan_test_o:NwwNwwN` is evaluated. Note that the arctangent function requires normalized arguments, hence the need for `ep_to_ep` and continue after `ep_mul`.

```

22109 \cs_new:Npn \__fp_asin_auxi_o:NnNww #1#2#3#4,#5;
22110   {
22111     \__fp_ep_to_fixed:wwn #4,#5;
22112     \__fp_asin_isqrt:wn
22113     \__fp_ep_mul:wwwwn #4,#5;
22114     \__fp_ep_to_ep:wwN
22115     \__fp_fixed_continue:wn
22116     { #2 \__fp_atan_test_o:NwwNwwN #3 }
22117     0 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1
22118   }
22119 \cs_new:Npn \__fp_asin_isqrt:wn #1;
22120   {
22121     \exp_after:wN \__fp_fixed_sub:wwn \c__fp_one_fixed_tl #1;
22122     {
22123       \__fp_fixed_add_one:wn #1;
22124       \__fp_fixed_continue:wn { \__fp_ep_mul:wwwwn 0, } 0,
22125     }
22126     \__fp_ep_isqrt:wwn
22127   }

```

(End definition for `__fp_asin_auxi_o:NnNww` and `__fp_asin_isqrt:wn`.)

34.2.3 Arccosecant and arcsecant

`__fp_acsc_o:w` Cases are mostly labelled by #2, except when #2 is 2: then we use #3#2, which is 02 = 2 when the number is $+\infty$ and 22 when the number is $-\infty$. The arccosecant of ± 0 raises an invalid operation exception. The arccosecant of $\pm\infty$ is ± 0 with the same sign. The arcosecant of NaN is itself. Otherwise, `__fp_acsc_normal_o:NfwNnw` does some more tests, keeping the function name (acsc or acscd) as an argument for invalid operation exceptions.

```

22128 \cs_new:Npn \__fp_acsc_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
22129 {
22130     \if_case:w \if_meaning:w 2 #2 #3 \fi: #2 \exp_stop_f:
22131         \__fp_case_use:nw
22132         { \__fp_invalid_operation_o:fw { #1 { acsc } { acscd } } }
22133     \or: \__fp_case_use:nw
22134         { \__fp_acsc_normal_o:NfwNnw #1 { #1 { acsc } { acscd } } }
22135     \or: \__fp_case_return_o:Nw \c_zero_fp
22136     \or: \__fp_case_return_same_o:w
22137     \else: \__fp_case_return_o:Nw \c_minus_zero_fp
22138     \fi:
22139     \s__fp \__fp_chk:w #2 #3 #4;
22140 }

```

(End definition for `__fp_acsc_o:w`.)

`__fp_asec_o:w` The arcsecant of ± 0 raises an invalid operation exception. The arcsecant of $\pm\infty$ is $\pi/2$ (in degrees, 90). The arcosecant of NaN is itself. Otherwise, do some more tests, keeping the function name asec (or asecd) as an argument for invalid operation exceptions, and a `__fp_reverse_args:Nww` following precisely that appearing in `__fp_acos_o:w`.

```

22141 \cs_new:Npn \__fp_asec_o:w #1 \s__fp \__fp_chk:w #2#3; @
22142 {
22143     \if_case:w #2 \exp_stop_f:
22144         \__fp_case_use:nw
22145         { \__fp_invalid_operation_o:fw { #1 { asec } { asecd } } }
22146     \or:
22147         \__fp_case_use:nw
22148         {
22149             \__fp_acsc_normal_o:NfwNnw #1 { #1 { asec } { asecd } }
22150             \__fp_reverse_args:Nww
22151         }
22152     \or: \__fp_case_use:nw { \__fp_atan_inf_o:NNnw #1 0 4 }
22153     \else: \__fp_case_return_same_o:w
22154     \fi:
22155     \s__fp \__fp_chk:w #2 #3;
22156 }

```

(End definition for `__fp_asec_o:w`.)

`__fp_acsc_normal_o:NfwNnw` If the exponent is non-positive, the operand is less than 1 in absolute value, which is always an invalid operation: complain. Otherwise, compute the inverse of the operand, and feed it to `__fp_asin_auxi_o:NnNww` (with all the appropriate arguments). This computes what we want thanks to $\text{acsc}(x) = \text{asin}(1/x)$ and $\text{asec}(x) = \text{acos}(1/x)$.

```

22157 \cs_new:Npn \__fp_acsc_normal_o:NfwNnw #1#2#3 \s__fp \__fp_chk:w 1#4#5#6;
22158 {
22159     \int_compare:nNnTF {#5} < 1

```

```

22160     {
22161       \__fp_invalid_operation_o:fw {#2}
22162       \s__fp \__fp_chk:w 1#4{#5}#6;
22163     }
22164     {
22165       \__fp_ep_div:wwwwn
22166       1,{1000}{0000}{0000}{0000}{0000}{0000};
22167       #5,#6{0000}{0000};
22168     { \__fp_asin_auxi_o:NnNww #1 {#3} #4 }
22169     }
22170   }

```

(End definition for __fp_acsc_normal_o:NfwNnw.)

```

22171 </initex | package>

```

35 13fp-convert implementation

```

22172 <*initex | package>

```

```

22173 <@@=fp>

```

35.1 Dealing with tuples

__fp_tuple_convert:Nw The first argument is for instance __fp_to_tl_dispatch:w, which converts any floating point object to the appropriate representation. We loop through all items, putting ,~ between all of them and making sure to remove the leading ,~.

```

22174 \cs_new:Npn \__fp_tuple_convert:Nw #1 \s__fp_tuple \__fp_tuple_chk:w #2 ;
22175 {
22176   \int_case:nnF { \__fp_array_count:n {#2} }
22177   {
22178     { 0 } { ( ) }
22179     { 1 } { \__fp_tuple_convert_end:w @ { #1 #2 , } }
22180   }
22181   {
22182     \__fp_tuple_convert_loop:nNw { } #1
22183     #2 { ? \__fp_tuple_convert_end:w } ;
22184     @ { \use_none:nn }
22185   }
22186 }
22187 \cs_new:Npn \__fp_tuple_convert_loop:nNw #1#2#3#4; #5 @ #6
22188 {
22189   \use_none:n #3
22190   \exp_args:Nf \__fp_tuple_convert_loop:nNw { #2 #3#4 ; } #2 #5
22191   @ { #6 , ~ #1 }
22192 }
22193 \cs_new:Npn \__fp_tuple_convert_end:w #1 @ #2
22194 { \exp_after:wN ( \exp:w \exp_end_continue_f:w #2 ) }

```

(End definition for __fp_tuple_convert:Nw, __fp_tuple_convert_loop:nNw, and __fp_tuple_convert_end:w.)

35.2 Trimming trailing zeros

`__fp_trim_zeros:w` If #1 ends with a 0, the loop auxiliary takes that zero as an end-delimiter for its first argument, and the second argument is the same loop auxiliary. Once the last trailing zero is reached, the second argument is the dot auxiliary, which removes a trailing dot if any. We then clean-up with the end auxiliary, keeping only the number.

```

22195 \cs_new:Npn \__fp_trim_zeros:w #1 ;
22196 {
22197   \__fp_trim_zeros_loop:w #1
22198   ; \__fp_trim_zeros_loop:w 0; \__fp_trim_zeros_dot:w .; \s__fp_stop
22199 }
22200 \cs_new:Npn \__fp_trim_zeros_loop:w #1 0; #2 { #2 #1 ; #2 }
22201 \cs_new:Npn \__fp_trim_zeros_dot:w #1 .; { \__fp_trim_zeros_end:w #1 ; }
22202 \cs_new:Npn \__fp_trim_zeros_end:w #1 ; #2 \s__fp_stop { #1 }

```

(End definition for `__fp_trim_zeros:w` and others.)

35.3 Scientific notation

`\fp_to_scientific:N` The three public functions evaluate their argument, then pass it to `__fp_to_scientific_dispatch:w`.

```

\fp_to_scientific:c
\fp_to_scientific:n
22203 \cs_new:Npn \fp_to_scientific:N #1
22204 { \exp_after:wN \__fp_to_scientific_dispatch:w #1 }
22205 \cs_generate_variant:Nn \fp_to_scientific:N { c }
22206 \cs_new:Npn \fp_to_scientific:n
22207 {
22208   \exp_after:wN \__fp_to_scientific_dispatch:w
22209   \exp:w \exp_end_continue_f:w \__fp_parse:n
22210 }

```

(End definition for `\fp_to_scientific:N` and `\fp_to_scientific:n`. These functions are documented on page 201.)

`_fp_to_scientific_dispatch:w` We allow tuples.

```

\_fp_to_scientific_recover:w
\__fp_tuple_to_scientific:w
22211 \cs_new:Npn \__fp_to_scientific_dispatch:w #1
22212 {
22213   \__fp_change_func_type:NNN
22214   #1 \__fp_to_scientific:w \__fp_to_scientific_recover:w
22215   #1
22216 }
22217 \cs_new:Npn \__fp_to_scientific_recover:w #1 #2 ;
22218 {
22219   \__fp_error:nffn { fp-unknown-type } { \tl_to_str:n { #2 ; } } { } { }
22220   nan
22221 }
22222 \cs_new:Npn \__fp_tuple_to_scientific:w
22223 { \__fp_tuple_convert:Nw \__fp_to_scientific_dispatch:w }

```

(End definition for `__fp_to_scientific_dispatch:w`, `__fp_to_scientific_recover:w`, and `__fp_tuple_to_scientific:w`.)

`__fp_to_scientific:w` Expressing an internal floating point number in scientific notation is quite easy: no rounding, and the format is very well defined. First cater for the sign: negative numbers (#2 = 2) start with -; we then only need to care about positive numbers and `nan`. Then

filter the special cases: ± 0 are represented as 0; infinities are converted to a number slightly larger than the largest after an “invalid_operation” exception; `nan` is represented as 0 after an “invalid_operation” exception. In the normal case, decrement the exponent and unbrace the 4 brace groups, then in a second step grab the first digit (previously hidden in braces) to order the various parts correctly.

```

22224 \cs_new:Npn \__fp_to_scientific:w \s__fp \__fp_chk:w #1#2
22225 {
22226   \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
22227   \if_case:w #1 \exp_stop_f:
22228     \__fp_case_return:nw { 0.000000000000000e0 }
22229   \or: \exp_after:wN \__fp_to_scientific_normal:wnnnnn
22230   \or:
22231     \__fp_case_use:nw
22232     {
22233       \__fp_invalid_operation:nnw
22234       { \fp_to_scientific:N \c__fp_overflowing_fp }
22235       { fp_to_scientific }
22236     }
22237   \or:
22238     \__fp_case_use:nw
22239     {
22240       \__fp_invalid_operation:nnw
22241       { \fp_to_scientific:N \c_zero_fp }
22242       { fp_to_scientific }
22243     }
22244   \fi:
22245   \s__fp \__fp_chk:w #1 #2
22246 }
22247 \cs_new:Npn \__fp_to_scientific_normal:wnnnnn
22248 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
22249 {
22250   \exp_after:wN \__fp_to_scientific_normal:wNw
22251   \exp_after:wN e
22252   \int_value:w \__fp_int_eval:w #2 - 1
22253   ; #3 #4 #5 #6 ;
22254 }
22255 \cs_new:Npn \__fp_to_scientific_normal:wNw #1 ; #2#3;
22256 { #2.#3 #1 }

```

(End definition for `__fp_to_scientific:w`, `__fp_to_scientific_normal:wnnnnn`, and `__fp_to_scientific_normal:wNw`.)

35.4 Decimal representation

`\fp_to_decimal:N` All three public variants are based on the same `__fp_to_decimal_dispatch:w` after evaluating their argument to an internal floating point.

```

\fp_to_decimal:c
\fp_to_decimal:n
22257 \cs_new:Npn \fp_to_decimal:N #1
22258 { \exp_after:wN \__fp_to_decimal_dispatch:w #1 }
22259 \cs_generate_variant:Nn \fp_to_decimal:N { c }
22260 \cs_new:Npn \fp_to_decimal:n
22261 {
22262   \exp_after:wN \__fp_to_decimal_dispatch:w
22263   \exp:w \exp_end_continue_f:w \__fp_parse:n
22264 }

```

(End definition for `\fp_to_decimal:N` and `\fp_to_decimal:n`. These functions are documented on page 201.)

```
\__fp_to_decimal_dispatch:w
\__fp_to_decimal_recover:w
\__fp_tuple_to_decimal:w
```

We allow tuples.

```
22265 \cs_new:Npn \__fp_to_decimal_dispatch:w #1
22266 {
22267   \__fp_change_func_type:NNN
22268   #1 \__fp_to_decimal:w \__fp_to_decimal_recover:w
22269   #1
22270 }
22271 \cs_new:Npn \__fp_to_decimal_recover:w #1 #2 ;
22272 {
22273   \__fp_error:nffn { fp-unknown-type } { \tl_to_str:n { #2 ; } } { } { }
22274   nan
22275 }
22276 \cs_new:Npn \__fp_tuple_to_decimal:w
22277 { \__fp_tuple_convert:Nw \__fp_to_decimal_dispatch:w }
```

(End definition for `__fp_to_decimal_dispatch:w`, `__fp_to_decimal_recover:w`, and `__fp_tuple_to_decimal:w`.)

```
\__fp_to_decimal:w
\__fp_to_decimal_normal:wnnnnn
\__fp_to_decimal_large:Nnnw
\__fp_to_decimal_huge:wnnnn
```

The structure is similar to `__fp_to_scientific:w`. Insert `-` for negative numbers. Zero gives 0, $\pm\infty$ and NaN yield an “invalid operation” exception; note that $\pm\infty$ produces a very large output, which we don’t expand now since it most likely won’t be needed. Normal numbers with an exponent in the range $[1, 15]$ have that number of digits before the decimal separator: “decimate” them, and remove leading zeros with `\int_value:w`, then trim trailing zeros and dot. Normal numbers with an exponent 16 or larger have no decimal separator, we only need to add trailing zeros. When the exponent is non-positive, the result should be $0.\langle zeros \rangle\langle digits \rangle$, trimmed.

```
22278 \cs_new:Npn \__fp_to_decimal:w \s__fp \__fp_chk:w #1#2
22279 {
22280   \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
22281   \if_case:w #1 \exp_stop_f:
22282     \__fp_case_return:nw { 0 }
22283   \or: \exp_after:wN \__fp_to_decimal_normal:wnnnnn
22284   \or:
22285     \__fp_case_use:nw
22286     {
22287       \__fp_invalid_operation:nnw
22288       { \fp_to_decimal:N \c__fp_overflowing_fp }
22289       { fp_to_decimal }
22290     }
22291   \or:
22292     \__fp_case_use:nw
22293     {
22294       \__fp_invalid_operation:nnw
22295       { 0 }
22296       { fp_to_decimal }
22297     }
22298   \fi:
22299   \s__fp \__fp_chk:w #1 #2
22300 }
22301 \cs_new:Npn \__fp_to_decimal_normal:wnnnnn
22302 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
```

```

22303 {
22304   \int_compare:nNnTF {#2} > 0
22305   {
22306     \int_compare:nNnTF {#2} < \c__fp_prec_int
22307     {
22308       \__fp_decimate:nNnnnn { \c__fp_prec_int - #2 }
22309       \__fp_to_decimal_large:Nnnw
22310     }
22311     {
22312       \exp_after:wN \exp_after:wN
22313       \exp_after:wN \__fp_to_decimal_huge:wnnnn
22314       \prg_replicate:nn { #2 - \c__fp_prec_int } { 0 } ;
22315     }
22316     {#3} {#4} {#5} {#6}
22317   }
22318   {
22319     \exp_after:wN \__fp_trim_zeros:w
22320     \exp_after:wN 0
22321     \exp_after:wN .
22322     \exp:w \exp_end_continue_f:w \prg_replicate:nn { - #2 } { 0 }
22323     #3#4#5#6 ;
22324   }
22325 }
22326 \cs_new:Npn \__fp_to_decimal_large:Nnnw #1#2#3#4;
22327 {
22328   \exp_after:wN \__fp_trim_zeros:w \int_value:w
22329   \if_int_compare:w #2 > 0 \exp_stop_f:
22330   #2
22331   \fi:
22332   \exp_stop_f:
22333   #3.#4 ;
22334 }
22335 \cs_new:Npn \__fp_to_decimal_huge:wnnnn #1; #2#3#4#5 { #2#3#4#5 #1 }

```

(End definition for __fp_to_decimal:w and others.)

35.5 Token list representation

\fp_to_tl:N These three public functions evaluate their argument, then pass it to __fp_to_tl_dispatch:w.
\fp_to_tl:c dispatch:w.

\fp_to_tl:n

```

22336 \cs_new:Npn \fp_to_tl:N #1 { \exp_after:wN \__fp_to_tl_dispatch:w #1 }
22337 \cs_generate_variant:Nn \fp_to_tl:N { c }
22338 \cs_new:Npn \fp_to_tl:n
22339 {
22340   \exp_after:wN \__fp_to_tl_dispatch:w
22341   \exp:w \exp_end_continue_f:w \__fp_parse:n
22342 }

```

(End definition for \fp_to_tl:N and \fp_to_tl:n. These functions are documented on page 202.)

__fp_to_tl_dispatch:w We allow tuples.

```

22343 \cs_new:Npn \__fp_to_tl_dispatch:w #1
22344 { \__fp_change_func_type:NNN #1 \__fp_to_tl:w \__fp_to_tl_recover:w #1 }
22345 \cs_new:Npn \__fp_to_tl_recover:w #1 #2 ;

```

```

22346 {
22347     \__fp_error:nffn { fp-unknown-type } { \tl_to_str:n { #2 ; } } { } { }
22348     nan
22349 }
22350 \cs_new:Npn \__fp_tuple_to_tl:w
22351 { \__fp_tuple_convert:Nw \__fp_to_tl_dispatch:w }

```

(End definition for __fp_to_tl_dispatch:w, __fp_to_tl_recover:w, and __fp_tuple_to_tl:w.)

__fp_to_tl:w A structure similar to __fp_to_scientific_dispatch:w and __fp_to_decimal_dispatch:w, but without the “invalid operation” exception. First filter special cases. We express normal numbers in decimal notation if the exponent is in the range $[-2, 16]$, and otherwise use scientific notation.

```

22352 \cs_new:Npn \__fp_to_tl:w \s__fp \__fp_chk:w #1#2
22353 {
22354     \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
22355     \if_case:w #1 \exp_stop_f:
22356         \__fp_case_return:nw { 0 }
22357     \or: \exp_after:wN \__fp_to_tl_normal:nnnnn
22358     \or: \__fp_case_return:nw { inf }
22359     \else: \__fp_case_return:nw { nan }
22360     \fi:
22361 }
22362 \cs_new:Npn \__fp_to_tl_normal:nnnnn #1
22363 {
22364     \int_compare:nTF
22365     { -2 <= #1 <= \c__fp_prec_int }
22366     { \__fp_to_decimal_normal:wnnnnnn }
22367     { \__fp_to_tl_scientific:wnnnnnn }
22368     \s__fp \__fp_chk:w 1 0 {#1}
22369 }
22370 \cs_new:Npn \__fp_to_tl_scientific:wnnnnnn
22371 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
22372 {
22373     \exp_after:wN \__fp_to_tl_scientific:wNw
22374     \exp_after:wN e
22375     \int_value:w \__fp_int_eval:w #2 - 1
22376     ; #3 #4 #5 #6 ;
22377 }
22378 \cs_new:Npn \__fp_to_tl_scientific:wNw #1 ; #2#3;
22379 { \__fp_trim_zeros:w #2.#3 ; #1 }

```

(End definition for __fp_to_tl:w and others.)

35.6 Formatting

This is not implemented yet, as it is not yet clear what a correct interface would be, for this kind of structured conversion from a floating point (or other types of variables) to a string. Ideas welcome.

35.7 Convert to dimension or integer

\fp_to_dim:N All three public variants are based on the same **__fp_to_dim_dispatch:w** after evaluating their argument to an internal floating point. We only allow floating point numbers, not tuples.

```

\__fp_to_dim_dispatch:w 22380 \cs_new:Npn \fp_to_dim:N #1
\__fp_to_dim_recover:w 22381 { \exp_after:wN \__fp_to_dim_dispatch:w #1 }
\__fp_to_dim:w 22382 \cs_generate_variant:Nn \fp_to_dim:N { c }
22383 \cs_new:Npn \fp_to_dim:n
22384 {
22385     \exp_after:wN \__fp_to_dim_dispatch:w
22386     \exp:w \exp_end_continue_f:w \__fp_parse:n
22387 }
22388 \cs_new:Npn \__fp_to_dim_dispatch:w #1#2 ;
22389 {
22390     \__fp_change_func_type:NNN #1 \__fp_to_dim:w \__fp_to_dim_recover:w
22391     #1 #2 ;
22392 }
22393 \cs_new:Npn \__fp_to_dim_recover:w #1
22394 { \__fp_invalid_operation:nnw { Opt } { fp_to_dim } }
22395 \cs_new:Npn \__fp_to_dim:w #1 ; { \__fp_to_decimal:w #1 ; pt }
```

(End definition for **\fp_to_dim:N** and others. These functions are documented on page 201.)

\fp_to_int:N For the most part identical to **\fp_to_dim:N** but without pt, and where **__fp_to_int:w** does more work. To convert to an integer, first round to 0 places (to the nearest integer), then express the result as a decimal number: the definition of **__fp_to_decimal_dispatch:w** is such that there are no trailing dot nor zero.

```

\__fp_to_int_dispatch:w 22396 \cs_new:Npn \fp_to_int:N #1 { \exp_after:wN \__fp_to_int_dispatch:w #1 }
\__fp_to_int_recover:w 22397 \cs_generate_variant:Nn \fp_to_int:N { c }
22398 \cs_new:Npn \fp_to_int:n
22399 {
22400     \exp_after:wN \__fp_to_int_dispatch:w
22401     \exp:w \exp_end_continue_f:w \__fp_parse:n
22402 }
22403 \cs_new:Npn \__fp_to_int_dispatch:w #1#2 ;
22404 {
22405     \__fp_change_func_type:NNN #1 \__fp_to_int:w \__fp_to_int_recover:w
22406     #1 #2 ;
22407 }
22408 \cs_new:Npn \__fp_to_int_recover:w #1
22409 { \__fp_invalid_operation:nnw { 0 } { fp_to_int } }
22410 \cs_new:Npn \__fp_to_int:w #1;
22411 {
22412     \exp_after:wN \__fp_to_decimal:w \exp:w \exp_end_continue_f:w
22413     \__fp_round:Nwn \__fp_round_to_nearest:NNN #1; { 0 }
22414 }
```

(End definition for **\fp_to_int:N** and others. These functions are documented on page 201.)

35.8 Convert from a dimension

\dim_to_fp:n The dimension expression (which can in fact be a glue expression) is evaluated, converted to a number (*i.e.*, expressed in scaled points), then multiplied by $2^{-16} =$

```

\__fp_from_dim_test:ww
\__fp_from_dim:wNw
\__fp_from_dim:wNNnnnnnn
\__fp_from_dim:wnnnnwNw
```

0.0000152587890625 to give a value expressed in points. The auxiliary `__fp_mul_npos_o:Nww` expects the desired *final sign* and two floating point operands (of the form `\s__fp ... ;`) as arguments. This set of functions is also used to convert dimension registers to floating points while parsing expressions: in this context there is an additional exponent, which is the first argument of `__fp_from_dim_test:ww`, and is combined with the exponent -4 of 2^{-16} . There is also a need to expand afterwards: this is performed by `__fp_mul_npos_o:Nww`, and cancelled by `\prg_do_nothing:` here.

```

22415 \cs_new:Npn \dim_to_fp:n #1
22416 {
22417   \exp_after:wN \__fp_from_dim_test:ww
22418   \exp_after:wN 0
22419   \exp_after:wN ,
22420   \int_value:w \tex_glueexpr:D #1 ;
22421 }
22422 \cs_new:Npn \__fp_from_dim_test:ww #1, #2
22423 {
22424   \if_meaning:w 0 #2
22425     \__fp_case_return:nw { \exp_after:wN \c_zero_fp }
22426   \else:
22427     \exp_after:wN \__fp_from_dim:wNw
22428     \int_value:w \__fp_int_eval:w #1 - 4
22429     \if_meaning:w - #2
22430       \exp_after:wN , \exp_after:wN 2 \int_value:w
22431     \else:
22432       \exp_after:wN , \exp_after:wN 0 \int_value:w #2
22433     \fi:
22434   \fi:
22435 }
22436 \cs_new:Npn \__fp_from_dim:wNw #1,#2#3;
22437 {
22438   \__fp_pack_twice_four:wNNNNNNNN \__fp_from_dim:wNNnnnnnn ;
22439   #3 000 0000 00 {10}987654321; #2 {#1}
22440 }
22441 \cs_new:Npn \__fp_from_dim:wNNnnnnnn #1; #2#3#4#5#6#7#8#9
22442 { \__fp_from_dim:wnnnnwNn #1 {#2#300} {0000} ; }
22443 \cs_new:Npn \__fp_from_dim:wnnnnwNn #1; #2#3#4#5#6; #7#8
22444 {
22445   \__fp_mul_npos_o:Nww #7
22446   \s__fp \__fp_chk:w 1 #7 {#5} #1 ;
22447   \s__fp \__fp_chk:w 1 0 {#8} {1525} {8789} {0625} {0000} ;
22448   \prg_do_nothing:
22449 }

```

(End definition for `\dim_to_fp:n` and others. This function is documented on page 175.)

35.9 Use and eval

`\fp_use:N` Those public functions are simple copies of the decimal conversions.
`\fp_use:c` 22450 `\cs_new_eq:NN \fp_use:N \fp_to_decimal:N`
`\fp_eval:n` 22451 `\cs_generate_variant:Nn \fp_use:N { c }`
22452 `\cs_new_eq:NN \fp_eval:n \fp_to_decimal:n`

(End definition for `\fp_use:N` and `\fp_eval:n`. These functions are documented on page 202.)

\fp_sign:n Trivial but useful. See the implementation of `\fp_add:Nn` for an explanation of why to use `__fp_parse:n`, namely, for better error reporting.

```
22453 \cs_new:Npn \fp_sign:n #1
22454 { \fp_to_decimal:n { sign \__fp_parse:n {#1} } }
```

(End definition for `\fp_sign:n`. This function is documented on page 201.)

\fp_abs:n Trivial but useful. See the implementation of `\fp_add:Nn` for an explanation of why to use `__fp_parse:n`, namely, for better error reporting.

```
22455 \cs_new:Npn \fp_abs:n #1
22456 { \fp_to_decimal:n { abs \__fp_parse:n {#1} } }
```

(End definition for `\fp_abs:n`. This function is documented on page 216.)

\fp_max:nn Similar to `\fp_abs:n`, for consistency with `\int_max:nn`, etc.

\fp_min:nn

```
22457 \cs_new:Npn \fp_max:nn #1#2
22458 { \fp_to_decimal:n { max ( \__fp_parse:n {#1} , \__fp_parse:n {#2} ) } }
22459 \cs_new:Npn \fp_min:nn #1#2
22460 { \fp_to_decimal:n { min ( \__fp_parse:n {#1} , \__fp_parse:n {#2} ) } }
```

(End definition for `\fp_max:nn` and `\fp_min:nn`. These functions are documented on page 216.)

35.10 Convert an array of floating points to a comma list

`__fp_array_to_clist:n` Converts an array of floating point numbers to a comma-list. If speed here ends up irrelevant, we can simplify the code for the auxiliary to become

```
\cs_new:Npn \__fp_array_to_clist_loop:Nw #1#2;
{
  \use_none:n #1
  { , ~ } \fp_to_tl:n { #1 #2 ; }
  \__fp_array_to_clist_loop:Nw
}
```

The `\use_ii:nn` function is expanded after `__fp_expand:n` is done, and it removes `,~` from the start of the representation.

```
22461 \cs_new:Npn \__fp_array_to_clist:n #1
22462 {
22463   \tl_if_empty:nF {#1}
22464   {
22465     \exp_last_unbraced:Ne \use_ii:nn
22466     {
22467       \__fp_array_to_clist_loop:Nw #1 { ? \prg_break: } ;
22468       \prg_break_point:
22469     }
22470   }
22471 }
22472 \cs_new:Npn \__fp_array_to_clist_loop:Nw #1#2;
22473 {
22474   \use_none:n #1
22475   , ~
22476   \exp_not:f { \__fp_to_tl_dispatch:w #1 #2 ; }
22477   \__fp_array_to_clist_loop:Nw
22478 }
```

(End definition for `_fp_array_to_clist:n` and `_fp_array_to_clist_loop:Nw`.)

22479 `</initex | package>`

36 13fp-random Implementation

22480 `<*initex | package>`

22481 `<@@=fp>`

`_fp_parse_word_rand:N` Those functions may receive a variable number of arguments. We won't use the argument `?`.
`_fp_parse_word_randint:N`

22482 `\cs_new:Npn _fp_parse_word_rand:N`
 22483 `{ _fp_parse_function:NNN _fp_rand_o:Nw ? }`
 22484 `\cs_new:Npn _fp_parse_word_randint:N`
 22485 `{ _fp_parse_function:NNN _fp_randint_o:Nw ? }`

(End definition for `_fp_parse_word_rand:N` and `_fp_parse_word_randint:N`.)

36.1 Engine support

Most engines provide random numbers, but not all. We write the test twice simply in order to write the `false` branch first.

22486 `\sys_if_rand_exist:F`
 22487 `{`
 22488 `_kernel_msg_new:nnn { kernel } { fp-no-random }`
 22489 `{ Random-numbers-unavailable-for~#1 }`
 22490 `\cs_new:Npn _fp_rand_o:Nw ? #1 @`
 22491 `{`
 22492 `_kernel_msg_expandable_error:nnn { kernel } { fp-no-random }`
 22493 `{ fp-rand }`
 22494 `\exp_after:wN \c_nan_fp`
 22495 `}`
 22496 `\cs_new_eq:NN _fp_randint_o:Nw _fp_rand_o:Nw`
 22497 `\cs_new:Npn \int_rand:nn #1#2`
 22498 `{`
 22499 `_kernel_msg_expandable_error:nnn { kernel } { fp-no-random }`
 22500 `{ \int_rand:nn {#1} {#2} }`
 22501 `\int_eval:n {#1}`
 22502 `}`
 22503 `\cs_new:Npn \int_rand:n #1`
 22504 `{`
 22505 `_kernel_msg_expandable_error:nnn { kernel } { fp-no-random }`
 22506 `{ \int_rand:n {#1} }`
 22507 `1`
 22508 `}`
 22509 `}`
 22510 `\sys_if_rand_exist:T`
 22511 `{`

Obviously, every word “random” below means “pseudo-random”, as we have no access to entropy (except a very unreliable source of entropy: the time it takes to run some code).

The primitive random number generator (RNG) is provided as `\tex_uniformdeviate:D`. Under the hood, it maintains an array of 55 28-bit numbers, updated with a linear recursion relation (similar to Fibonacci numbers) modulo 2^{28} . When `\tex_uniformdeviate:D` $\langle integer \rangle$ is called (for brevity denote by N the $\langle integer \rangle$), the next 28-bit number is read from the array, scaled by $N/2^{28}$, and rounded. To prevent 0 and N from appearing half as often as other numbers, they are both mapped to the result 0.

This process means that `\tex_uniformdeviate:D` only gives a uniform distribution from 0 to $N-1$ if N is a divisor of 2^{28} , so we will mostly call the RNG with such power of 2 arguments. If N does not divide 2^{28} , then the relative non-uniformity (difference between probabilities of getting different numbers) is about $N/2^{28}$. This implies that detecting deviation from $1/N$ of the probability of a fixed value X requires about $2^{56}/N$ random trials. But collective patterns can reduce this to about $2^{56}/N^2$. For instance with $N = 3 \times 2^k$, the modulo 3 repartition of such random numbers is biased with a non-uniformity about $2^k/2^{28}$ (which is much worse than the circa $3/2^{28}$ non-uniformity from taking directly $N = 3$). This is detectable after about $2^{56}/2^{2k} = 9 \cdot 2^{56}/N^2$ random numbers. For $k = 15$, $N = 98304$, this means roughly 2^{26} calls to the RNG (experimentally this takes at the very least 16 seconds on a 2 giga-hertz processor). While this bias is not quite problematic, it is uncomfortably close to being so, and it becomes worse as N is increased. In our code, we shall thus combine several results from the RNG.

The RNG has three types of unexpected correlations. First, everything is linear modulo 2^{28} , hence the lowest k bits of the random numbers only depend on the lowest k bits of the seed (and of course the number of times the RNG was called since setting the seed). The recommended way to get a number from 0 to $N-1$ is thus to scale the raw 28-bit integer, as the engine's RNG does. We will go further and in fact typically we discard some of the lowest bits.

Second, suppose that we call the RNG with the same argument N to get a set of K integers in $[0, N-1]$ (throwing away repeats), and suppose that $N > K^3$ and $K > 55$. The recursion used to construct more 28-bit numbers from previous ones is linear: $x_n = x_{n-55} - x_{n-24}$ or $x_n = x_{n-55} - x_{n-24} + 2^{28}$. After rescaling and rounding we find that the result $N_n \in [0, N-1]$ is among $N_{n-55} - N_{n-24} + \{-1, 0, 1\}$ modulo N (a more detailed analysis shows that 0 appears with frequency close to $3/4$). The resulting set thus has more triplets (a, b, c) than expected obeying $a = b + c$ modulo N . Namely it will have of order $(K-55) \times 3/4$ such triplets, when one would expect $K^3/(6N)$. This starts to be detectable around $N = 2^{18} > 55^3$ (earlier if one keeps track of positions too, but this is more subtle than it looks because the array of 28-bit integers is read backwards by the engine). Hopefully the correlation is subtle enough to not affect realistic documents so we do not specifically mitigate against this. Since we typically use two calls to the RNG per `\int_rand:nn` we would need to investigate linear relations between the x_{2n} on the one hand and between the x_{2n+1} on the other hand. Such relations will have more complicated coefficients than ± 1 , which alleviates the issue.

Third, consider successive batches of 165 calls to the RNG (with argument 2^{28} or with argument 2 for instance), then most batches have more odd than even numbers. Note that this does not mean that there are more odd than even numbers overall. Similar issues are discussed in Knuth's TAOCP volume 2 near exercise 3.3.2-31. We do not have any mitigation strategy for this.

Ideally, our algorithm should be:

- Uniform. The result should be as uniform as possible assuming that the RNG's underlying 28-bit integers are uniform.

- Uncorrelated. The result should not have detectable correlations between different seeds, similar to the lowest-bit ones mentioned earlier.
- Quick. The algorithm should be fast in $\text{T}_{\text{E}}\text{X}$, so no “bit twiddling”, but “digit twiddling” is ok.
- Simple. The behaviour must be documentable precisely.
- Predictable. The number of calls to the RNG should be the same for any `\int_rand:nn`, because then the algorithm can be modified later without changing the result of other uses of the RNG.
- Robust. It should work even for `\int_rand:nn { - \c_max_int } { \c_max_int }` where the range is not representable as an integer. In fact, we also provide later a floating-point `randint` whose range can go all the way up to $2 \times 10^{16} - 1$ possible values.

Some of these requirements conflict. For instance, uniformity cannot be achieved with a fixed number of calls to the RNG.

Denote by $\text{random}(N)$ one call to `\tex_uniformdeviate:D` with argument N , and by $\text{ediv}(p, q)$ the $\varepsilon\text{-T}_{\text{E}}\text{X}$ rounding division giving $\lfloor p/q + 1/2 \rfloor$. Denote by $\langle \min \rangle$, $\langle \max \rangle$ and $R = \langle \max \rangle - \langle \min \rangle + 1$ the arguments of `\int_min:nn` and the number of possible outcomes. Note that $R \in [1, 2^{32} - 1]$ cannot necessarily be represented as an integer (however, $R - 2^{31}$ can). Our strategy is to get two 28-bit integers X and Y from the RNG, split each into 14-bit integers, as $X = X_1 \times 2^{14} + X_0$ and $Y = Y_1 \times 2^{14} + Y_0$ then return essentially $\langle \min \rangle + \lfloor R(X_1 \times 2^{-14} + Y_1 \times 2^{-28} + Y_0 \times 2^{-42} + X_0 \times 2^{-56}) \rfloor$. For small R the X_0 term has a tiny effect so we ignore it and we can compute $R \times Y/2^{28}$ much more directly by $\text{random}(R)$.

- If $R \leq 2^{17} - 1$ then return $\text{ediv}(R \text{random}(2^{14}) + \text{random}(R) + 2^{13}, 2^{14}) - 1 + \langle \min \rangle$. The shifts by 2^{13} and -1 convert $\varepsilon\text{-T}_{\text{E}}\text{X}$ division to truncated division. The bound on R ensures that the number obtained after the shift is less than `\c_max_int`. The non-uniformity is at most of order $2^{17}/2^{42} = 2^{-25}$.
- Split $R = R_2 \times 2^{28} + R_1 \times 2^{14} + R_0$, where $R_2 \in [0, 15]$. Compute $\langle \min \rangle + R_2 X_1 2^{14} + (R_2 Y_1 + R_1 X_1) + \text{ediv}(R_2 Y_0 + R_1 Y_1 + R_0 X_1 + \text{ediv}(R_2 X_0 + R_0 Y_1 + \text{ediv}((2^{14} R_1 + R_0)(2^{14} Y_0 + X_0), 2^{28}), 2^{14}), 2^{14})$ then map a result of $\langle \max \rangle + 1$ to $\langle \min \rangle$. Writing each ediv in terms of truncated division with a shift, and using $\lfloor (p + \lfloor r/s \rfloor)/q \rfloor = \lfloor (ps + r)/(sq) \rfloor$, what we compute is equal to $\lfloor \langle \text{exact} \rangle + 2^{-29} + 2^{-15} + 2^{-1} \rfloor$ with $\langle \text{exact} \rangle = \langle \min \rangle + R \times 0.X_1 Y_1 Y_0 X_0$. Given we map $\langle \max \rangle + 1$ to $\langle \min \rangle$, the shift has no effect on uniformity. The non-uniformity is bounded by $R/2^{56} < 2^{-24}$. It may be possible to speed up the code by dropping tiny terms such as $R_0 X_0$, but the analysis of non-uniformity proves too difficult.

To avoid the overflow when the computation yields $\langle \max \rangle + 1$ with $\langle \max \rangle = 2^{31} - 1$ (note that R is then arbitrary), we compute the result in two pieces. Compute $\langle \text{first} \rangle = \langle \min \rangle + R_2 X_1 2^{14}$ if $R_2 < 8$ or $\langle \min \rangle + 8 X_1 2^{14} + (R_2 - 8) X_1 2^{14}$ if $R_2 \geq 8$, the expressions being chosen to avoid overflow. Compute $\langle \text{second} \rangle = R_2 Y_1 + R_1 X_1 + \text{ediv}(\dots)$, at most $R_2 2^{14} + R_1 2^{14} + R_0 \leq 2^{28} + 15 \times 2^{14} - 1$, not at risk of overflowing. We have $\langle \text{first} \rangle + \langle \text{second} \rangle = \langle \max \rangle + 1 = \langle \min \rangle + R$ if and only if $\langle \text{second} \rangle = R 2^{14} + R_0 + R_2 2^{14}$ and $2^{14} R_2 X_1 = 2^{28} R_2 - 2^{14} R_2$ (namely $R_2 = 0$ or $X_1 = 2^{14} - 1$). In that case, return $\langle \min \rangle$, otherwise return $\langle \text{first} \rangle + \langle \text{second} \rangle$, which is safe because it is at most $\langle \max \rangle$. Note that the decision of what to return

does not need $\langle first \rangle$ explicitly so we don't actually compute it, just put it in an integer expression in which $\langle second \rangle$ is eventually added (or not).

- To get a floating point number in $[0, 1)$ just call the $R = 10000 \leq 2^{17} - 1$ procedure above to produce four blocks of four digits.
- To get an integer floating point number in a range (whose size can be up to $2 \times 10^{16} - 1$), work with fixed-point numbers: get six times four digits to build a fixed point number, multiply by R and add $\langle min \rangle$. This requires some care because l3fp-extended only supports non-negative numbers.

`\c__kernel_randint_max_int` Constant equal to $2^{17} - 1$, the maximal size of a range that `\int_range:nn` can do with its “simple” algorithm.

```
22512 \int_const:Nn \c__kernel_randint_max_int { 131071 }
```

(End definition for `\c__kernel_randint_max_int`.)

`__kernel_randint:n` Used in an integer expression, `__kernel_randint:n {R}` gives a random number $1 + \lfloor (R \text{random}(2^{14}) + \text{random}(R)) / 2^{14} \rfloor$ that is in $[1, R]$. Previous code was computing $\lfloor p / 2^{14} \rfloor$ as `ediv(p - 2^{13}, 2^{14})` but that wrongly gives -1 for $p = 0$.

```
22513 \cs_new:Npn \__kernel_randint:n #1
22514 {
22515   (#1 * \tex_uniformdeviate:D 16384
22516   + \tex_uniformdeviate:D #1 + 8192 ) / 16384
22517 }
```

(End definition for `__kernel_randint:n`.)

`__fp_rand_myriads:n` Used as `__fp_rand_myriads:n {XXX}` with one letter X (specifically) per block of four digit we want; it expands to `;` followed by the requested number of brace groups, each containing four (pseudo-random) digits. Digits are produced as a random number in $[10000, 19999]$ for the usual reason of preserving leading zeros.

```
22518 \cs_new:Npn \__fp_rand_myriads:n #1
22519 { \__fp_rand_myriads_loop:w #1 \prg_break: X \prg_break_point: ; }
22520 \cs_new:Npn \__fp_rand_myriads_loop:w #1 X
22521 {
22522   #1
22523   \exp_after:wN \__fp_rand_myriads_get:w
22524   \int_value:w \__fp_int_eval:w 9999 +
22525   \__kernel_randint:n { 10000 }
22526   \__fp_rand_myriads_loop:w
22527 }
22528 \cs_new:Npn \__fp_rand_myriads_get:w 1 #1 ; { ; {#1} }
```

(End definition for `__fp_rand_myriads:n`, `__fp_rand_myriads_loop:w`, and `__fp_rand_myriads_get:w`.)

36.2 Random floating point

`__fp_rand_o:Nw` First we check that `random` was called without argument. Then get four blocks of four digits and convert that fixed point number to a floating point number (this correctly sets the exponent). This has a minor bug: if all of the random numbers are zero then the result is correctly 0 but it raises the underflow flag; it should not do that.

`__fp_rand_o:w`

```

22529 \cs_new:Npn \__fp_rand_o:Nw ? #1 @
22530 {
22531   \tl_if_empty:nTF {#1}
22532   {
22533     \exp_after:wN \__fp_rand_o:w
22534     \exp:w \exp_end_continue_f:w
22535     \__fp_rand_myriads:n { XXXX } { 0000 } { 0000 } ; 0
22536   }
22537   {
22538     \__kernel_msg_expandable_error:nnnnn
22539     { kernel } { fp-num-args } { rand() } { 0 } { 0 }
22540     \exp_after:wN \c_nan_fp
22541   }
22542 }
22543 \cs_new:Npn \__fp_rand_o:w ;
22544 {
22545   \exp_after:wN \__fp_sanitizew:Nw
22546   \exp_after:wN 0
22547   \int_value:w \__fp_int_eval:w \c_zero_int
22548   \__fp_fixed_to_float_o:wN
22549 }

```

(End definition for `__fp_rand_o:Nw` and `__fp_rand_o:w`.)

36.3 Random integer

`__fp_randint_o:Nw` Enforce that there is one argument (then add first argument 1) or two arguments. Call `__fp_randint_default:w` on each; this function inserts 1 `\exp_stop_f:` to end the `\if_case:w` statement if either the argument is not an integer or if its absolute value is $\geq 10^{16}$. Also bail out if `__fp_compare_back:ww` yields 1, meaning that the bounds are not in the right order. Otherwise an auxiliary converts each argument times 10^{-16} (hence the shift in exponent) to a 24-digit fixed point number (see `l3fp-extended`). Then compute the number of choices, $\langle max \rangle + 1 - \langle min \rangle$. Create a random 24-digit fixed-point number with `__fp_rand_myriads:n`, then use a fused multiply-add instruction to multiply the number of choices to that random number and add it to $\langle min \rangle$. Then truncate to 16 digits (namely select the integer part of 10^{16} times the result) before converting back to a floating point number (`__fp_sanitizew:Nw` takes care of zero). To avoid issues with negative numbers, add 1 to all fixed point numbers (namely 10^{16} to the integers they represent), except of course when it is time to convert back to a float.

```

22550 \cs_new:Npn \__fp_randint_o:Nw ?
22551 {
22552   \__fp_parse_function_one_two:nnw
22553   { randint }
22554   { \__fp_randint_default:w \__fp_randint_o:w }
22555 }
22556 \cs_new:Npn \__fp_randint_default:w #1 { \exp_after:wN #1 \c_one_fp }
22557 \cs_new:Npn \__fp_randint_badarg:w \s__fp \__fp_chk:w #1#2#3;

```

```

22558 {
22559     \__fp_int:wTF \s__fp \__fp_chk:w #1#2#3;
22560     {
22561         \if_meaning:w 1 #1
22562         \if_int_compare:w
22563             \__fp_use_i_until_s:nw #3 ; > \c__fp_prec_int
22564             1 \exp_stop_f:
22565         \fi:
22566         \fi:
22567     }
22568     { 1 \exp_stop_f: }
22569 }
22570 \cs_new:Npn \__fp_randint_o:w #1; #2; @
22571 {
22572     \if_case:w
22573         \__fp_randint_badarg:w #1;
22574         \__fp_randint_badarg:w #2;
22575         \if:w 1 \__fp_compare_back:ww #2; #1; 1 \exp_stop_f: \fi:
22576         0 \exp_stop_f:
22577         \__fp_randint_auxi_o:ww #1; #2;
22578     \or:
22579         \__fp_invalid_operation_tl_o:ff
22580         { randint } { \__fp_array_to_clist:n { #1; #2; } }
22581     \exp:w
22582     \fi:
22583     \exp_after:wN \exp_end:
22584 }
22585 \cs_new:Npn \__fp_randint_auxi_o:ww #1 ; #2 ; #3 \exp_end:
22586 {
22587     \fi:
22588     \__fp_randint_auxii:wn #2 ;
22589     { \__fp_randint_auxii:wn #1 ; \__fp_randint_auxiii_o:ww }
22590 }
22591 \cs_new:Npn \__fp_randint_auxii:wn \s__fp \__fp_chk:w #1#2#3#4 ;
22592 {
22593     \if_meaning:w 0 #1
22594     \exp_after:wN \use_i:nn
22595     \else:
22596     \exp_after:wN \use_ii:nn
22597     \fi:
22598     { \exp_after:wN \__fp_fixed_continue:wn \c__fp_one_fixed_tl }
22599     {
22600         \exp_after:wN \__fp_ep_to_fixed:wwn
22601         \int_value:w \__fp_int_eval:w
22602         #3 - \c__fp_prec_int , #4 {0000} {0000} ;
22603         {
22604             \if_meaning:w 0 #2
22605             \exp_after:wN \use_i:nnnn
22606             \exp_after:wN \__fp_fixed_add_one:wN
22607             \fi:
22608             \exp_after:wN \__fp_fixed_sub:wwn \c__fp_one_fixed_tl
22609         }
22610         \__fp_fixed_continue:wn
22611     }

```

```

22612     }
22613     \cs_new:Npn \__fp_randint_auxiii_o:ww #1 ; #2 ;
22614     {
22615         \__fp_fixed_add:wwn #2 ;
22616         {0000} {0000} {0000} {0001} {0000} {0000} ;
22617         \__fp_fixed_sub:wwn #1 ;
22618         {
22619             \exp_after:wN \use_i:nn
22620             \exp_after:wN \__fp_fixed_mul_add:wwwn
22621             \exp:w \exp_end_continue_f:w \__fp_rand_myriads:n { XXXXXX } ;
22622         }
22623         #1 ;
22624         \__fp_randint_auxiv_o:ww
22625         #2 ;
22626         \__fp_randint_auxv_o:w #1 ; @
22627     }
22628     \cs_new:Npn \__fp_randint_auxiv_o:ww #1#2#3#4#5 ; #6#7#8#9
22629     {
22630         \if_int_compare:w
22631             \if_int_compare:w #1#2 > #6#7 \exp_stop_f: 1 \else:
22632             \if_int_compare:w #1#2 < #6#7 \exp_stop_f: - \fi: \fi:
22633             #3#4 > #8#9 \exp_stop_f:
22634             \__fp_use_i_until_s:nw
22635             \fi:
22636             \__fp_randint_auxv_o:w {#1}{#2}{#3}{#4}#5
22637     }
22638     \cs_new:Npn \__fp_randint_auxv_o:w #1#2#3#4#5 ; #6 @
22639     {
22640         \exp_after:wN \__fp_sanitize:Nw
22641         \int_value:w
22642         \if_int_compare:w #1 < 10000 \exp_stop_f:
22643             2
22644         \else:
22645             0
22646             \exp_after:wN \exp_after:wN
22647             \exp_after:wN \__fp_reverse_args:Nww
22648             \fi:
22649             \exp_after:wN \__fp_fixed_sub:wwn \c__fp_one_fixed_tl
22650             {#1} {#2} {#3} {#4} {0000} {0000} ;
22651             {
22652                 \exp_after:wN \exp_stop_f:
22653                 \int_value:w \__fp_int_eval:w \c__fp_prec_int
22654                 \__fp_fixed_to_float_o:wN
22655             }
22656             0
22657             \exp:w \exp_after:wN \exp_end:
22658     }

```

(End definition for __fp_randint_o:Nw and others.)

\int_rand:nn Evaluate the argument and filter out the case where the lower bound #1 is more than
__fp_randint:ww the upper bound #2. Then determine whether the range is narrower than **\c__kernel_-randint_max_int**; #2-#1 may overflow for very large positive #2 and negative #1. If the range is narrow, call **__kernel_randint:n {<choices>}** where <choices> is the number

of possible outcomes. If the range is wide, use somewhat slower code.

```

22659 \cs_new:Npn \int_rand:nn #1#2
22660 {
22661   \int_eval:n
22662   {
22663     \exp_after:wN \__fp_randint:ww
22664     \int_value:w \int_eval:n {#1} \exp_after:wN ;
22665     \int_value:w \int_eval:n {#2} ;
22666   }
22667 }
22668 \cs_new:Npn \__fp_randint:ww #1; #2;
22669 {
22670   \if_int_compare:w #1 > #2 \exp_stop_f:
22671   \__kernel_msg_expandable_error:nnnn
22672   { kernel } { randint-backward-range } {#1} {#2}
22673   \__fp_randint:ww #2; #1;
22674   \else:
22675     \if_int_compare:w \__fp_int_eval:w #2
22676     \if_int_compare:w #1 > \c_zero_int
22677     - #1 < \__fp_int_eval:w
22678     \else:
22679       < \__fp_int_eval:w #1 +
22680       \fi:
22681       \c_kernel_randint_max_int
22682       \__fp_int_eval_end:
22683       \__kernel_randint:n
22684       { \__fp_int_eval:w #2 - #1 + 1 \__fp_int_eval_end: }
22685       - 1 + #1
22686     \else:
22687       \__kernel_randint:nn {#1} {#2}
22688     \fi:
22689   \fi:
22690 }

```

(End definition for `\int_rand:nn` and `__fp_randint:ww`. This function is documented on page 98.)

```

\__kernel_randint:nn
\__fp_randint_split_o:Nw
\__fp_randint_split_aux:w
\__fp_randintat_wide_aux:w
\__fp_randintat_wide_auxii:w

```

Any $n \in [-2^{31} + 1, 2^{31} - 1]$ is uniquely written as $2^{14}n_1 + n_2$ with $n_1 \in [-2^{17}, 2^{17} - 1]$ and $n_2 \in [0, 2^{14} - 1]$. Calling `__fp_randint_split_o:Nw n` ; gives n_1 ; n_2 ; and expands the next token once. We do this for two random numbers and apply `__fp_randint_split_o:Nw` twice to fully decompose the range R . One subtlety is that we compute $R - 2^{31} = \langle \max \rangle - \langle \min \rangle - (2^{31} - 1) \in [-2^{31} + 1, 2^{31} - 1]$ rather than R to avoid overflow.

Then we have `__fp_randint_wide_aux:w` $\langle X_1 \rangle; \langle X_0 \rangle; \langle Y_1 \rangle; \langle Y_0 \rangle; \langle R_2 \rangle; \langle R_1 \rangle; \langle R_0 \rangle; .$ and we apply the algorithm described earlier.

```

22691 \cs_new:Npn \__kernel_randint:nn #1#2
22692 {
22693   #1
22694   \exp_after:wN \__fp_randint_wide_aux:w
22695   \int_value:w
22696   \exp_after:wN \__fp_randint_split_o:Nw
22697   \tex_uniformdeviate:D 268435456 ;
22698   \int_value:w
22699   \exp_after:wN \__fp_randint_split_o:Nw
22700   \tex_uniformdeviate:D 268435456 ;
22701   \int_value:w

```

```

22702         \exp_after:wN \__fp_randint_split_o:Nw
22703         \int_value:w \__fp_int_eval:w 131072 +
22704         \exp_after:wN \__fp_randint_split_o:Nw
22705         \int_value:w
22706         \__kernel_int_add:nnn {#2} { -#1 } { -\c_max_int } ;
22707     .
22708 }
22709 \cs_new:Npn \__fp_randint_split_o:Nw #1#2 ;
22710 {
22711     \if_meaning:w 0 #1
22712     0 \exp_after:wN ; \int_value:w 0
22713     \else:
22714         \exp_after:wN \__fp_randint_split_aux:w
22715         \int_value:w \__fp_int_eval:w (#1#2 - 8192) / 16384 ;
22716         + #1#2
22717     \fi:
22718     \exp_after:wN ;
22719 }
22720 \cs_new:Npn \__fp_randint_split_aux:w #1 ;
22721 {
22722     #1 \exp_after:wN ;
22723     \int_value:w \__fp_int_eval:w - #1 * 16384
22724 }
22725 \cs_new:Npn \__fp_randint_wide_aux:w #1;#2; #3;#4; #5;#6;#7; .
22726 {
22727     \exp_after:wN \__fp_randint_wide_auxii:w
22728     \int_value:w \__fp_int_eval:w #5 * #3 + #6 * #1 +
22729     (#5 * #4 + #6 * #3 + #7 * #1 +
22730     (#5 * #2 + #7 * #3 +
22731     (16384 * #6 + #7) * (16384 * #4 + #2) / 268435456) / 16384
22732     ) / 16384 \exp_after:wN ;
22733     \int_value:w \__fp_int_eval:w (#5 + #6) * 16384 + #7 ;
22734     #1 ; #5 ;
22735 }
22736 \cs_new:Npn \__fp_randint_wide_auxii:w #1; #2; #3; #4;
22737 {
22738     \if_int_odd:w 0
22739     \if_int_compare:w #1 = #2 \else: \exp_stop_f: \fi:
22740     \if_int_compare:w #4 = \c_zero_int 1 \fi:
22741     \if_int_compare:w #3 = 16383 ~ 1 \fi:
22742     \exp_stop_f:
22743     \exp_after:wN \prg_break:
22744     \fi:
22745     \if_int_compare:w #4 < 8 \exp_stop_f:
22746     + #4 * #3 * 16384
22747     \else:
22748     + 8 * #3 * 16384 + (#4 - 8) * #3 * 16384
22749     \fi:
22750     + #1
22751     \prg_break_point:
22752 }

```

(End definition for __kernel_randint:nn and others.)

\int_rand:n Similar to \int_rand:nn, but needs fewer checks.

```

\__fp_randint:n 22753 \cs_new:Npn \int_rand:n #1
22754 {
22755   \int_eval:n
22756   { \exp_args:Nf \__fp_randint:n { \int_eval:n {#1} } }
22757 }
22758 \cs_new:Npn \__fp_randint:n #1
22759 {
22760   \if_int_compare:w #1 < 1 \exp_stop_f:
22761   \__kernel_msg_expandable_error:nnnn
22762   { kernel } { randint-backward-range } { 1 } {#1}
22763   \__fp_randint:ww #1; 1;
22764   \else:
22765   \if_int_compare:w #1 > \c__kernel_randint_max_int
22766   \__kernel_randint:nn { 1 } {#1}
22767   \else:
22768   \__kernel_randint:n {#1}
22769   \fi:
22770   \fi:
22771 }

```

(End definition for \int_rand:n and __fp_randint:n. This function is documented on page 98.)

End the initial conditional that ensures these commands are only defined in engines that support random numbers.

```

22772 }
22773 </initex | package>

```

37 l3fparray implementation

```

22774 <*initex | package>
22775 <@@=fp>

```

In analogy to l3intarray it would make sense to have <@@=fparray>, but we need direct access to __fp_parse:n from l3fp-parse, and a few other (less crucial) internals of the l3fp family.

37.1 Allocating arrays

There are somewhat more than $(2^{31} - 1)^2$ floating point numbers so we store each floating point number as three entries in integer arrays. To avoid having to multiply indices by three or to add 1 etc, a floating point array is just a token list consisting of three tokens: integer arrays of the same size.

```

\g__fp_array_int Used to generate unique names for the three integer arrays.
22776 \int_new:N \g__fp_array_int

(End definition for \g__fp_array_int.)

\l__fp_array_loop_int Used to loop in \__fp_array_gzero:N.
22777 \int_new:N \l__fp_array_loop_int

(End definition for \l__fp_array_loop_int.)

```

\fparray_new:Nn Build a three-token token list, then define all three tokens to be integer arrays of the same size. No need to initialize the data: the integer arrays start with zeros, and three zeros denote precisely `\c_zero_fp`, as we want.

\fparray_new:cn

__fp_array_new:nNNN

```

22778 \cs_new_protected:Npn \fparray_new:Nn #1#2
22779 {
22780   \tl_new:N #1
22781   \prg_replicate:nn { 3 }
22782   {
22783     \int_gincr:N \g__fp_array_int
22784     \exp_args:NNc \tl_gput_right:Nn #1
22785     { g__fp_array_ \__fp_int_to_roman:w \g__fp_array_int _intarray }
22786   }
22787   \exp_last_unbraced:Nfo \__fp_array_new:nNNNN
22788   { \int_eval:n {#2} } #1 #1
22789 }
22790 \cs_generate_variant:Nn \fparray_new:Nn { c }
22791 \cs_new_protected:Npn \__fp_array_new:nNNNN #1#2#3#4#5
22792 {
22793   \int_compare:nNnTF {#1} < 0
22794   {
22795     \__kernel_msg_error:nnn { kernel } { negative-array-size } {#1}
22796     \cs_undefine:N #1
22797     \int_gsub:Nn \g__fp_array_int { 3 }
22798   }
22799   {
22800     \intarray_new:Nn #2 {#1}
22801     \intarray_new:Nn #3 {#1}
22802     \intarray_new:Nn #4 {#1}
22803   }
22804 }

```

(End definition for `\fparray_new:Nn` and `__fp_array_new:nNNN`. This function is documented on page 219.)

\fparray_count:N Size of any of the intarrays, here we pick the third.

\fparray_count:c

```

22805 \cs_new:Npn \fparray_count:N #1
22806 {
22807   \exp_after:wN \use_i:nnn
22808   \exp_after:wN \intarray_count:N #1
22809 }
22810 \cs_generate_variant:Nn \fparray_count:N { c }

```

(End definition for `\fparray_count:N`. This function is documented on page 219.)

37.2 Array items

__fp_array_bounds:NNnTF See the `l3intarray` analogue: only names change. The functions `\fparray_gset:Nnn` and `\fparray_item:Nn` share bounds checking. The T branch is used if #3 is within bounds of the array #2.

__fp_array_bounds_error:NNn

```

22811 \cs_new:Npn \__fp_array_bounds:NNnTF #1#2#3#4#5
22812 {
22813   \if_int_compare:w 1 > #3 \exp_stop_f:
22814   \__fp_array_bounds_error:NNn #1 #2 {#3}
22815   #5

```

```

22816     \else:
22817         \if_int_compare:w #3 > \fparray_count:N #2 \exp_stop_f:
22818             \__fp_array_bounds_error:NNn #1 #2 {#3}
22819             #5
22820         \else:
22821             #4
22822         \fi:
22823     \fi:
22824 }
22825 \cs_new:Npn \__fp_array_bounds_error:NNn #1#2#3
22826 {
22827     #1 { kernel } { out-of-bounds }
22828     { \token_to_str:N #2 } {#3} { \fparray_count:N #2 }
22829 }

```

(End definition for __fp_array_bounds:NNnTF and __fp_array_bounds_error:NNn.)

\fparray_gset:Nnn

Evaluate, then store exponent in one intarray, sign and 8 digits of mantissa in the next, and 8 trailing digits in the last.

\fparray_gset:cnn

__fp_array_gset:NNNNww

__fp_array_gset:w

__fp_array_gset_recover:Nw

__fp_array_gset_special:nnNNN

__fp_array_gset_normal:w

```

22830 \cs_new_protected:Npn \fparray_gset:Nnn #1#2#3
22831 {
22832     \exp_after:wN \exp_after:wN
22833     \exp_after:wN \__fp_array_gset:NNNNww
22834     \exp_after:wN #1
22835     \exp_after:wN #1
22836     \int_value:w \int_eval:n {#2} \exp_after:wN ;
22837     \exp:w \exp_end_continue_f:w \__fp_parse:n {#3}
22838 }
22839 \cs_generate_variant:Nn \fparray_gset:Nnn { c }
22840 \cs_new_protected:Npn \__fp_array_gset:NNNNww #1#2#3#4#5 ; #6 ;
22841 {
22842     \__fp_array_bounds:NNnTF \__kernel_msg_error:nnxxx #4 {#5}
22843     {
22844         \exp_after:wN \__fp_change_func_type:NNN
22845         \__fp_use_i_until:s:nw #6 ;
22846         \__fp_array_gset:w
22847         \__fp_array_gset_recover:Nw
22848         #6 ; {#5} #1 #2 #3
22849     }
22850     { }
22851 }
22852 \cs_new_protected:Npn \__fp_array_gset_recover:Nw #1#2 ;
22853 {
22854     \__fp_error:nffn { fp-unknown-type } { \tl_to_str:n { #2 ; } } { } { } { }
22855     \exp_after:wN #1 \c_nan_fp
22856 }
22857 \cs_new_protected:Npn \__fp_array_gset:w \s__fp \__fp_chk:w #1#2
22858 {
22859     \if_case:w #1 \exp_stop_f:
22860         \__fp_case_return:nw { \__fp_array_gset_special:nnNNN {#2} }
22861     \or: \exp_after:wN \__fp_array_gset_normal:w
22862     \or: \__fp_case_return:nw { \__fp_array_gset_special:nnNNN { #2 3 } }
22863     \or: \__fp_case_return:nw { \__fp_array_gset_special:nnNNN { 1 } }
22864     \fi:

```

```

22865     \s__fp \__fp_chk:w #1 #2
22866   }
22867 \cs_new_protected:Npn \__fp_array_gset_normal:w
22868   \s__fp \__fp_chk:w 1 #1 #2 #3#4#5 ; #6#7#8#9
22869   {
22870     \__kernel_intarray_gset:Nnn #7 {#6} {#2}
22871     \__kernel_intarray_gset:Nnn #8 {#6}
22872     { \if_meaning:w 2 #1 3 \else: 1 \fi: #3#4 }
22873     \__kernel_intarray_gset:Nnn #9 {#6} { 1 \use:nn #5 }
22874   }
22875 \cs_new_protected:Npn \__fp_array_gset_special:nnNNN #1#2#3#4#5
22876   {
22877     \__kernel_intarray_gset:Nnn #3 {#2} {#1}
22878     \__kernel_intarray_gset:Nnn #4 {#2} {0}
22879     \__kernel_intarray_gset:Nnn #5 {#2} {0}
22880   }

```

(End definition for \fpararray_gset:Nnn and others. This function is documented on page 219.)

\fpararray_gzero:N

\fpararray_gzero:c

```

22881 \cs_new_protected:Npn \fpararray_gzero:N #1
22882   {
22883     \int_zero:N \l__fp_array_loop_int
22884     \prg_replicate:nn { \fpararray_count:N #1 }
22885     {
22886       \int_incr:N \l__fp_array_loop_int
22887       \exp_after:wN \__fp_array_gset_special:nnNNN
22888       \exp_after:wN 0
22889       \exp_after:wN \l__fp_array_loop_int
22890       #1
22891     }
22892   }
22893 \cs_generate_variant:Nn \fpararray_gzero:N { c }

```

(End definition for \fpararray_gzero:N. This function is documented on page 219.)

\fpararray_item:Nn

\fpararray_item:cn

\fpararray_item_to_tl:Nn

\fpararray_item_to_tl:cn

__fp_array_item:NwN

__fp_array_item:NNNnN

__fp_array_item:N

__fp_array_item:w

__fp_array_item_special:w

__fp_array_item_normal:w

```

22894 \cs_new:Npn \fpararray_item:Nn #1#2
22895   {
22896     \exp_after:wN \__fp_array_item:NwN
22897     \exp_after:wN #1
22898     \int_value:w \int_eval:n {#2} ;
22899     \__fp_to_decimal:w
22900   }
22901 \cs_generate_variant:Nn \fpararray_item:Nn { c }
22902 \cs_new:Npn \fpararray_item_to_tl:Nn #1#2
22903   {
22904     \exp_after:wN \__fp_array_item:NwN
22905     \exp_after:wN #1
22906     \int_value:w \int_eval:n {#2} ;
22907     \__fp_to_tl:w
22908   }
22909 \cs_generate_variant:Nn \fpararray_item_to_tl:Nn { c }
22910 \cs_new:Npn \__fp_array_item:NwN #1#2 ; #3
22911   {

```

```

22912 \__fp_array_bounds:NNnTF \__kernel_msg_expandable_error:nnfff #1 {#2}
22913 { \exp_after:wN \__fp_array_item:NNNnN #1 {#2} #3 }
22914 { \exp_after:wN #3 \c_nan_fp }
22915 }
22916 \cs_new:Npn \__fp_array_item:NNNnN #1#2#3#4
22917 {
22918 \exp_after:wN \__fp_array_item:N
22919 \int_value:w \__kernel_intarray_item:Nn #2 {#4} \exp_after:wN ;
22920 \int_value:w \__kernel_intarray_item:Nn #3 {#4} \exp_after:wN ;
22921 \int_value:w \__kernel_intarray_item:Nn #1 {#4} ;
22922 }
22923 \cs_new:Npn \__fp_array_item:N #1
22924 {
22925 \if_meaning:w 0 #1 \exp_after:wN \__fp_array_item_special:w \fi:
22926 \__fp_array_item:w #1
22927 }
22928 \cs_new:Npn \__fp_array_item:w #1 #2#3#4#5 #6 ; 1 #7 ;
22929 {
22930 \exp_after:wN \__fp_array_item_normal:w
22931 \int_value:w \if_meaning:w #1 1 0 \else: 2 \fi: \exp_stop_f:
22932 #7 ; {#2#3#4#5} {#6} ;
22933 }
22934 \cs_new:Npn \__fp_array_item_special:w #1 ; #2 ; #3 ; #4
22935 {
22936 \exp_after:wN #4
22937 \exp:w \exp_end_continue_f:w
22938 \if_case:w #3 \exp_stop_f:
22939 \exp_after:wN \c_zero_fp
22940 \or: \exp_after:wN \c_nan_fp
22941 \or: \exp_after:wN \c_minus_zero_fp
22942 \or: \exp_after:wN \c_inf_fp
22943 \else: \exp_after:wN \c_minus_inf_fp
22944 \fi:
22945 }
22946 \cs_new:Npn \__fp_array_item_normal:w #1 #2#3#4#5 #6 ; #7 ; #8 ; #9
22947 { #9 \s__fp \__fp_chk:w 1 #1 {#8} #7 {#2#3#4#5} {#6} ; }

```

(End definition for `\fparray_item:Nn` and others. These functions are documented on page 219.)

```

22948 </initex | package>

```

38 l3sort implementation

```

22949 <*initex | package>

```

```

22950 <@@=sort>

```

38.1 Variables

```

\g__sort_internal_seq
\g__sort_internal_tl

```

Sorting happens in a group; the result is stored in those global variables before being copied outside the group to the proper places. For `seq` and `tl` this is more efficient than using `\use:x` (or some `\exp_args:NNNx`) to smuggle the definition outside the group since $\text{T}_{\text{E}}\text{X}$ does not need to re-read tokens. For `clist` we don't gain anything since the result is converted from `seq` to `clist` anyways.

```

22951 \seq_new:N \g__sort_internal_seq

```

22952 `\tl_new:N \g__sort_internal_tl`

(End definition for `\g__sort_internal_seq` and `\g__sort_internal_tl`.)

`\l__sort_length_int` The sequence has `\l__sort_length_int` items and is stored from `\l__sort_min_int` to `\l__sort_top_int - 1`. While reading the sequence in memory, we check that `\l__sort_min_int` remains at most `\l__sort_max_int`, precomputed by `__sort_compute_range:`. That bound is such that the merge sort only uses `\toks` registers less than `\l__sort_true_max_int`, namely those that have not been allocated for use in other code: the user's comparison code could alter these.

`\l__sort_min_int`

`\l__sort_top_int`

`\l__sort_max_int`

`\l__sort_true_max_int`

22953 `\int_new:N \l__sort_length_int`

22954 `\int_new:N \l__sort_min_int`

22955 `\int_new:N \l__sort_top_int`

22956 `\int_new:N \l__sort_max_int`

22957 `\int_new:N \l__sort_true_max_int`

(End definition for `\l__sort_length_int` and others.)

`\l__sort_block_int` Merge sort is done in several passes. In each pass, blocks of size `\l__sort_block_int` are merged in pairs. The block size starts at 1, and, for a length in the range $[2^k + 1, 2^{k+1}]$, reaches 2^k in the last pass.

22958 `\int_new:N \l__sort_block_int`

(End definition for `\l__sort_block_int`.)

`\l__sort_begin_int` When merging two blocks, `\l__sort_begin_int` marks the lowest index in the two blocks, and `\l__sort_end_int` marks the highest index, plus 1.

`\l__sort_end_int`

22959 `\int_new:N \l__sort_begin_int`

22960 `\int_new:N \l__sort_end_int`

(End definition for `\l__sort_begin_int` and `\l__sort_end_int`.)

`\l__sort_A_int` When merging two blocks (whose end-points are `beg` and `end`), `A` starts from the high end of the low block, and decreases until reaching `beg`. The index `B` starts from the top of the range and marks the register in which a sorted item should be put. Finally, `C` points to the copy of the high block in the interval of registers starting at `\l__sort_length_int`, upwards. `C` starts from the upper limit of that range.

`\l__sort_B_int`

`\l__sort_C_int`

22961 `\int_new:N \l__sort_A_int`

22962 `\int_new:N \l__sort_B_int`

22963 `\int_new:N \l__sort_C_int`

(End definition for `\l__sort_A_int`, `\l__sort_B_int`, and `\l__sort_C_int`.)

`\s__sort_mark` Internal scan marks.

`\s__sort_stop`

22964 `\scan_new:N \s__sort_mark`

22965 `\scan_new:N \s__sort_stop`

(End definition for `\s__sort_mark` and `\s__sort_stop`.)

38.2 Finding available \toks registers

`__sort_shrink_range:` After `__sort_compute_range:` (defined below) determines that `\toks` registers between `\l__sort_min_int` (included) and `\l__sort_true_max_int` (excluded) have not yet been assigned, `__sort_shrink_range:` computes `\l__sort_max_int` to reflect the need for a buffer when merging blocks in the merge sort. Given $2^n \leq A \leq 2^n + 2^{n-1}$ registers we can sort $\lfloor A/2 \rfloor + 2^{n-2}$ items while if we have $2^n + 2^{n-1} \leq A \leq 2^{n+1}$ registers we can sort $A - 2^{n-1}$ items. We first find out a power 2^n such that $2^n \leq A \leq 2^{n+1}$ by repeatedly halving `\l__sort_block_int`, starting at 2^{15} or 2^{14} namely half the total number of registers, then we use the formulas and set `\l__sort_max_int`.

```

22966 \cs_new_protected:Npn \__sort_shrink_range:
22967 {
22968   \int_set:Nn \l__sort_A_int
22969     { \l__sort_true_max_int - \l__sort_min_int + 1 }
22970   \int_set:Nn \l__sort_block_int { \c_max_register_int / 2 }
22971   \__sort_shrink_range_loop:
22972   \int_set:Nn \l__sort_max_int
22973     {
22974       \int_compare:nNnTF
22975         { \l__sort_block_int * 3 / 2 } > \l__sort_A_int
22976         {
22977           \l__sort_min_int
22978           + ( \l__sort_A_int - 1 ) / 2
22979           + \l__sort_block_int / 4
22980           - 1
22981         }
22982         { \l__sort_true_max_int - \l__sort_block_int / 2 }
22983     }
22984 }
22985 \cs_new_protected:Npn \__sort_shrink_range_loop:
22986 {
22987   \if_int_compare:w \l__sort_A_int < \l__sort_block_int
22988     \tex_divide:D \l__sort_block_int 2 \exp_stop_f:
22989     \exp_after:wN \__sort_shrink_range_loop:
22990   \fi:
22991 }

```

(End definition for `__sort_shrink_range:` and `__sort_shrink_range_loop:.`)

`__sort_compute_range:` First find out what `\toks` have not yet been assigned. There are many cases. In $\text{\LaTeX} 2_{\epsilon}$ with no package, available `\toks` range from `\count15 + 1` to `\c_max_register_int` included (this was not altered despite the 2015 changes). When `\loctoks` is defined, namely in plain (e) \TeX , or when the package `etex` is loaded in $\text{\LaTeX} 2_{\epsilon}$, redefine `__sort_compute_range:` to use the range `\count265` to `\count275 - 1`. The `elocalloc` package also defines `\loctoks` but uses yet another number for the upper bound, namely `\e@alloc@top` (minus one). We must check for `\loctoks` every time a sorting function is called, as `etex` or `elocalloc` could be loaded.

In \ConTeXt MkIV the range is from `\c_syst_last_allocated_toks+1` to `\c_max_register_int`, and in \MkII it is from `\lastallocatedtoks+1` to `\c_max_register_int`. In all these cases, call `__sort_shrink_range:.` The $\text{\LaTeX} 3$ format mode is easiest: no `\toks` are ever allocated so available `\toks` range from 0 to `\c_max_register_int` and we precompute the result of `__sort_shrink_range:.`

```

22992 (*package)

```

```

22993 \cs_new_protected:Npn \__sort_compute_range:
22994 {
22995   \int_set:Nn \l__sort_min_int { \tex_count:D 15 + 1 }
22996   \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
22997   \__sort_shrink_range:
22998   \if_meaning:w \loctoks \tex_undefined:D \else:
22999     \if_meaning:w \loctoks \scan_stop: \else:
23000       \__sort_redefine_compute_range:
23001       \__sort_compute_range:
23002     \fi:
23003   \fi:
23004 }
23005 \cs_new_protected:Npn \__sort_redefine_compute_range:
23006 {
23007   \cs_if_exist:cTF { ver@elocalloc.sty }
23008   {
23009     \cs_gset_protected:Npn \__sort_compute_range:
23010     {
23011       \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
23012       \int_set_eq:NN \l__sort_true_max_int \e@alloc@top
23013       \__sort_shrink_range:
23014     }
23015   }
23016   {
23017     \cs_gset_protected:Npn \__sort_compute_range:
23018     {
23019       \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
23020       \int_set:Nn \l__sort_true_max_int { \tex_count:D 275 }
23021       \__sort_shrink_range:
23022     }
23023   }
23024 }
23025 \cs_if_exist:NT \loctoks { \__sort_redefine_compute_range: }
23026 \tl_map_inline:nn { \lastallocatedtoks \c_syst_last_allocated_toks }
23027 {
23028   \cs_if_exist:NT #1
23029   {
23030     \cs_gset_protected:Npn \__sort_compute_range:
23031     {
23032       \int_set:Nn \l__sort_min_int { #1 + 1 }
23033       \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
23034       \__sort_shrink_range:
23035     }
23036   }
23037 }
23038 </package>
23039 <*:initex>
23040 \int_const:Nn \c__sort_max_length_int
23041 { ( \c_max_register_int + 1 ) * 3 / 4 }
23042 \cs_new_protected:Npn \__sort_compute_range:
23043 {
23044   \int_set:Nn \l__sort_min_int { 0 }
23045   \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
23046   \int_set:Nn \l__sort_max_int { \c__sort_max_length_int }

```



```

23047 }
23048 </initex>

```

(End definition for `__sort_compute_range:`, `__sort_redefine_compute_range:`, and `\c__sort_max_length_int`.)

38.3 Protected user commands

`__sort_main:NNNn` Sorting happens in three steps. First store items in `\toks` registers ranging from `\l__sort_min_int` to `\l__sort_top_int - 1`, while checking that the list is not too long. If we reach the maximum length, that's an error; exit the group. Secondly, sort the array of `\toks` registers, using the user-defined sorting function: `__sort_level:` calls `__sort_compare:nn` as needed. Finally, unpack the `\toks` registers (now sorted) into the target `tl`, or into `\g__sort_internal_seq` for `seq` and `clist`. This is done by `__sort_seq:NNNNn` and `__sort_tl:NNn`.

```

23049 \cs_new_protected:Npn \__sort_main:NNNn #1#2#3#4
23050 {
23051   \package{__sort_disable_toksdef:
23052     \__sort_compute_range:
23053     \int_set_eq:NN \l__sort_top_int \l__sort_min_int
23054     #1 #3
23055     {
23056       \if_int_compare:w \l__sort_top_int = \l__sort_max_int
23057         \__sort_too_long_error:NNw #2 #3
23058       \fi:
23059       \tex_toks:D \l__sort_top_int {##1}
23060       \int_incr:N \l__sort_top_int
23061     }
23062     \int_set:Nn \l__sort_length_int
23063     { \l__sort_top_int - \l__sort_min_int }
23064     \cs_set:Npn \__sort_compare:nn ##1 ##2 {#4}
23065     \int_set:Nn \l__sort_block_int { 1 }
23066     \__sort_level:
23067   }

```

(End definition for `__sort_main:NNNn`.)

`\tl_sort:Nn` Call the main sorting function then unpack `\toks` registers outside the group into the target token list. The unpacking is done by `__sort_tl_toks:w`; registers are numbered from `\l__sort_min_int` to `\l__sort_top_int - 1`. For expansion behaviour we need a couple of primitives. The `\tl_gclear:N` reduces memory usage. The `\prg_break_point:` is used by `__sort_main:NNNn` when the list is too long.

```

\__sort_tl:NNn
\__sort_tl_toks:w
23068 \cs_new_protected:Npn \tl_sort:Nn { \__sort_tl:NNn \tl_set_eq:NN }
23069 \cs_generate_variant:Nn \tl_sort:Nn { c }
23070 \cs_new_protected:Npn \tl_gsort:Nn { \__sort_tl:NNn \tl_gset_eq:NN }
23071 \cs_generate_variant:Nn \tl_gsort:Nn { c }
23072 \cs_new_protected:Npn \__sort_tl:NNn #1#2#3
23073 {
23074   \group_begin:
23075     \__sort_main:NNNn \tl_map_inline:Nn \tl_map_break:n #2 {#3}
23076     \tl_gset:Nx \g__sort_internal_tl
23077     { \__sort_tl_toks:w \l__sort_min_int ; }
23078   \group_end:

```

```

23079     #1 #2 \g__sort_internal_tl
23080     \tl_gclear:N \g__sort_internal_tl
23081     \prg_break_point:
23082   }
23083   \cs_new:Npn \__sort_tl_toks:w #1 ;
23084   {
23085     \if_int_compare:w #1 < \l__sort_top_int
23086       { \tex_the:D \tex_toks:D #1 }
23087       \exp_after:wN \__sort_tl_toks:w
23088       \int_value:w \int_eval:n { #1 + 1 } \exp_after:wN ;
23089     \fi:
23090   }

```

(End definition for `\tl_sort:Nn` and others. These functions are documented on page 53.)

```

\seq_sort:Nn Use the same general framework for seq and clist. Apply the general sorting code, then
\seq_sort:cn unpack \toks into \g__sort_internal_seq. Outside the group copy or convert (for
\seq_gsort:Nn clist) the data to the target variable. The \seq_gclear:N reduces memory usage. The
\seq_gsort:cn \prg_break_point: is used by \__sort_main:NNNn when the list is too long.
\clist_sort:Nn
\clist_sort:cn
\clist_gsort:Nn
\clist_gsort:cn
\__sort_seq:NNNNn
23091 \cs_new_protected:Npn \seq_sort:Nn
23092   { \__sort_seq:NNNNn \seq_map_inline:Nn \seq_map_break:n \seq_set_eq:NN }
23093 \cs_generate_variant:Nn \seq_sort:Nn { c }
23094 \cs_new_protected:Npn \seq_gsort:Nn
23095   { \__sort_seq:NNNNn \seq_map_inline:Nn \seq_map_break:n \seq_gset_eq:NN }
23096 \cs_generate_variant:Nn \seq_gsort:Nn { c }
23097 \cs_new_protected:Npn \clist_sort:Nn
23098   {
23099     \__sort_seq:NNNNn \clist_map_inline:Nn \clist_map_break:n
23100     \clist_set_from_seq:NN
23101   }
23102 \cs_generate_variant:Nn \clist_sort:Nn { c }
23103 \cs_new_protected:Npn \clist_gsort:Nn
23104   {
23105     \__sort_seq:NNNNn \clist_map_inline:Nn \clist_map_break:n
23106     \clist_gset_from_seq:NN
23107   }
23108 \cs_generate_variant:Nn \clist_gsort:Nn { c }
23109 \cs_new_protected:Npn \__sort_seq:NNNNn #1#2#3#4#5
23110   {
23111     \group_begin:
23112       \__sort_main:NNNn #1 #2 #4 {#5}
23113       \seq_gset_from_inline_x:Nnn \g__sort_internal_seq
23114       {
23115         \int_step_function:nnN
23116         { \l__sort_min_int } { \l__sort_top_int - 1 }
23117       }
23118       { \tex_the:D \tex_toks:D ##1 }
23119     \group_end:
23120     #3 #4 \g__sort_internal_seq
23121     \seq_gclear:N \g__sort_internal_seq
23122     \prg_break_point:
23123   }

```

(End definition for `\seq_sort:Nn` and others. These functions are documented on page 79.)

38.4 Merge sort

`__sort_level:` This function is called once blocks of size `\l__sort_block_int` (initially 1) are each sorted. If the whole list fits in one block, then we are done (this also takes care of the case of an empty list or a list with one item). Otherwise, go through pairs of blocks starting from 0, then double the block size, and repeat.

```

23124 \cs_new_protected:Npn \__sort_level:
23125 {
23126   \if_int_compare:w \l__sort_block_int < \l__sort_length_int
23127     \l__sort_end_int \l__sort_min_int
23128     \__sort_merge_blocks:
23129     \tex_advance:D \l__sort_block_int \l__sort_block_int
23130     \exp_after:wN \__sort_level:
23131   \fi:
23132 }
```

(End definition for `__sort_level:.`)

`__sort_merge_blocks:` This function is called to merge a pair of blocks, starting at the last value of `\l__sort_end_int` (end-point of the previous pair of blocks). If shifting by one block to the right we reach the end of the list, then this pass has ended: the end of the list is sorted already. Otherwise, store the result of that shift in *A*, which indexes the first block starting from the top end. Then locate the end-point (maximum) of the second block: shift *end* upwards by one more block, but keeping it \leq *top*. Copy this upper block of `\toks` registers in registers above *length*, indexed by *C*: this is covered by `__sort_copy_block:.` Once this is done we are ready to do the actual merger using `__sort_merge_blocks_aux:`, after shifting *A*, *B* and *C* so that they point to the largest index in their respective ranges rather than pointing just beyond those ranges. Of course, once that pair of blocks is merged, move on to the next pair.

```

23133 \cs_new_protected:Npn \__sort_merge_blocks:
23134 {
23135   \l__sort_begin_int \l__sort_end_int
23136   \tex_advance:D \l__sort_end_int \l__sort_block_int
23137   \if_int_compare:w \l__sort_end_int < \l__sort_top_int
23138     \l__sort_A_int \l__sort_end_int
23139     \tex_advance:D \l__sort_end_int \l__sort_block_int
23140     \if_int_compare:w \l__sort_end_int > \l__sort_top_int
23141       \l__sort_end_int \l__sort_top_int
23142     \fi:
23143     \l__sort_B_int \l__sort_A_int
23144     \l__sort_C_int \l__sort_top_int
23145     \__sort_copy_block:
23146     \int_decr:N \l__sort_A_int
23147     \int_decr:N \l__sort_B_int
23148     \int_decr:N \l__sort_C_int
23149     \exp_after:wN \__sort_merge_blocks_aux:
23150     \exp_after:wN \__sort_merge_blocks:
23151   \fi:
23152 }
```

(End definition for `__sort_merge_blocks:.`)

`__sort_copy_block:` We wish to store a copy of the “upper” block of `\toks` registers, ranging between the initial value of `\l__sort_B_int` (included) and `\l__sort_end_int` (excluded) into a new range starting at the initial value of `\l__sort_C_int`, namely `\l__sort_top_int`.

```

23153 \cs_new_protected:Npn \__sort_copy_block:
23154 {
23155     \tex_toks:D \l__sort_C_int \tex_toks:D \l__sort_B_int
23156     \int_incr:N \l__sort_C_int
23157     \int_incr:N \l__sort_B_int
23158     \if_int_compare:w \l__sort_B_int = \l__sort_end_int
23159         \use_i:nn
23160     \fi:
23161     \__sort_copy_block:
23162 }
```

(End definition for `__sort_copy_block:`.)

`__sort_merge_blocks_aux:` At this stage, the first block starts at `\l__sort_begin_int`, and ends at `\l__sort_A_int`, and the second block starts at `\l__sort_top_int` and ends at `\l__sort_C_int`. The result of the merger is stored at positions indexed by `\l__sort_B_int`, which starts at `\l__sort_end_int - 1` and decreases down to `\l__sort_begin_int`, covering the full range of the two blocks. In other words, we are building the merger starting with the largest values. The comparison function is defined to return either `swapped` or `same`. Of course, this means the arguments need to be given in the order they appear originally in the list.

```

23163 \cs_new_protected:Npn \__sort_merge_blocks_aux:
23164 {
23165     \exp_after:wN \__sort_compare:nn \exp_after:wN
23166     { \tex_the:D \tex_toks:D \exp_after:wN \l__sort_A_int \exp_after:wN }
23167     \exp_after:wN { \tex_the:D \tex_toks:D \l__sort_C_int }
23168     \prg_do_nothing:
23169     \__sort_return_mark:w
23170     \__sort_return_mark:w
23171     \s__sort_mark
23172     \__sort_return_none_error:
23173 }
```

(End definition for `__sort_merge_blocks_aux:`.)

`\sort_return_same:` Each comparison should call `\sort_return_same:` or `\sort_return_swapped:` exactly once. If neither is called, `__sort_return_none_error:` is called, since the `return_mark` removes tokens until `\s__sort_mark`. If one is called, the `return_mark` auxiliary removes everything except `__sort_return_same:w` (or its `swapped` analogue) followed by `__sort_return_none_error:.` Finally if two or more are called, `__sort_return_two_error:` ends up before any `__sort_return_mark:w`, so that it produces an error.

```

23174 \cs_new_protected:Npn \sort_return_same:
23175     #1 \__sort_return_mark:w #2 \s__sort_mark
23176 {
23177     #1
23178     #2
23179     \__sort_return_two_error:
23180     \__sort_return_mark:w
23181     \s__sort_mark
23182     \__sort_return_same:w
```

```

23183 }
23184 \cs_new_protected:Npn \sort_return_swapped:
23185   #1 \__sort_return_mark:w #2 \s__sort_mark
23186   {
23187     #1
23188     #2
23189     \__sort_return_two_error:
23190     \__sort_return_mark:w
23191     \s__sort_mark
23192     \__sort_return_swapped:w
23193   }
23194 \cs_new_protected:Npn \__sort_return_mark:w #1 \s__sort_mark { }
23195 \cs_new_protected:Npn \__sort_return_none_error:
23196   {
23197     \__kernel_msg_error:nnxx { kernel } { return-none }
23198     { \tex_the:D \tex_toks:D \l__sort_A_int }
23199     { \tex_the:D \tex_toks:D \l__sort_C_int }
23200     \__sort_return_same:w \__sort_return_none_error:
23201   }
23202 \cs_new_protected:Npn \__sort_return_two_error:
23203   {
23204     \__kernel_msg_error:nnxx { kernel } { return-two }
23205     { \tex_the:D \tex_toks:D \l__sort_A_int }
23206     { \tex_the:D \tex_toks:D \l__sort_C_int }
23207   }

```

(End definition for `\sort_return_same:` and others. These functions are documented on page 220.)

`__sort_return_same:w` If the comparison function returns `same`, then the second argument fed to `__sort_compare:nn` should remain to the right of the other one. Since we build the merger starting from the right, we copy that `\toks` register into the allotted range, then shift the pointers *B* and *C*, and go on to do one more step in the merger, unless the second block has been exhausted: then the remainder of the first block is already in the correct registers and we are done with merging those two blocks.

```

23208 \cs_new_protected:Npn \__sort_return_same:w #1 \__sort_return_none_error:
23209   {
23210     \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
23211     \int_decr:N \l__sort_B_int
23212     \int_decr:N \l__sort_C_int
23213     \if_int_compare:w \l__sort_C_int < \l__sort_top_int
23214       \use_i:nn
23215     \fi:
23216     \__sort_merge_blocks_aux:
23217   }

```

(End definition for `__sort_return_same:w`.)

`__sort_return_swapped:w` If the comparison function returns `swapped`, then the next item to add to the merger is the first argument, contents of the `\toks` register *A*. Then shift the pointers *A* and *B* to the left, and go for one more step for the merger, unless the left block was exhausted (*A* goes below the threshold). In that case, all remaining `\toks` registers in the second block, indexed by *C*, are copied to the merger by `__sort_merge_blocks_end:`.

```

23218 \cs_new_protected:Npn \__sort_return_swapped:w #1 \__sort_return_none_error:
23219   {

```

```

23220 \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_A_int
23221 \int_decr:N \l__sort_B_int
23222 \int_decr:N \l__sort_A_int
23223 \if_int_compare:w \l__sort_A_int < \l__sort_begin_int
23224 \__sort_merge_blocks_end: \use_i:nn
23225 \fi:
23226 \__sort_merge_blocks_aux:
23227 }

```

(End definition for __sort_return_swapped:w.)

__sort_merge_blocks_end: This function's task is to copy the \toks registers in the block indexed by C to the merger indexed by B . The end can equally be detected by checking when B reaches the threshold `begin`, or when C reaches top.

```

23228 \cs_new_protected:Npn \__sort_merge_blocks_end:
23229 {
23230 \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
23231 \int_decr:N \l__sort_B_int
23232 \int_decr:N \l__sort_C_int
23233 \if_int_compare:w \l__sort_B_int < \l__sort_begin_int
23234 \use_i:nn
23235 \fi:
23236 \__sort_merge_blocks_end:
23237 }

```

(End definition for __sort_merge_blocks_end:.)

38.5 Expandable sorting

Sorting expandably is very different from sorting and assigning to a variable. Since tokens cannot be stored, they must remain in the input stream, and be read through at every step. It is thus necessarily much slower (at best $O(n^2 \ln n)$) than non-expandable sorting functions ($O(n \ln n)$).

A prototypical version of expandable quicksort is as follows. If the argument has no item, return nothing, otherwise partition, using the first item as a pivot (argument #4 of __sort:nnNnn). The arguments of __sort:nnNnn are 1. items less than #4, 2. items greater or equal to #4, 3. comparison, 4. pivot, 5. next item to test. If #5 is the tail of the list, call \tl_sort:nN on #1 and on #2, placing #4 in between; \use:ff expands the parts to make \tl_sort:nN f-expandable. Otherwise, compare #4 and #5 using #3. If they are ordered, place #5 amongst the “greater” items, otherwise amongst the “lesser” items, and continue partitioning.

```

\cs_new:Npn \tl_sort:nN #1#2
{
\tl_if_blank:nF {#1}
{
\tl_sort:nnNnn { } { } #2
#1 \q__sort_recursion_tail \q__sort_recursion_stop
}
}
\cs_new:Npn \__sort:nnNnn #1#2#3#4#5
{
\quark_if_recursion_tail_stop_do:nn {#5}

```

```

    { \use:ff { \tl_sort:nN {#1} #3 {#4} } { \tl_sort:nN {#2} #3 } }
#3 {#4} {#5}
    { \__sort:nnNnn {#1} { #2 {#5} } #3 {#4} }
    { \__sort:nnNnn { #1 {#5} } {#2} #3 {#4} }
}
\cs_generate_variant:Nn \use:nn { ff }

```

There are quite a few optimizations available here: the code below is less legible, but more than twice as fast.

In the simple version of the code, `__sort:nnNnn` is called $O(n \ln n)$ times on average (the number of comparisons required by the quicksort algorithm). Hence most of our focus is on optimizing that function.

The first speed up is to avoid testing for the end of the list at every call to `__sort:nnNnn`. For this, the list is prepared by changing each *<item>* of the original token list into *<command>* `{<item>}`, just like sequences are stored. We arrange things such that the *<command>* is the *<conditional>* provided by the user: the loop over the *<prepared tokens>* then looks like

```

\cs_new:Npn \__sort_loop:wNn ... #6#7
{
  #6 {<pivot>} {#7} <loop big> <loop small>
  <extra arguments>
}
\__sort_loop:wNn ... <prepared tokens>
<end-loop> {} \s__sort_stop

```

In this example, which matches the structure of `__sort_quick_split_i:NnnnnNn` and a few other functions below, the `__sort_loop:wNn` auxiliary normally receives the user's *<conditional>* as `#6` and an *<item>* as `#7`. This is compared to the *<pivot>* (the argument `#5`, not shown here), and the *<conditional>* leaves the *<loop big>* or *<loop small>* auxiliary, which both have the same form as `__sort_loop:wNn`, receiving the next pair *<conditional>* `{<item>}` as `#6` and `#7`. At the end, `#6` is the *<end-loop>* function, which terminates the loop.

The second speed up is to minimize the duplicated tokens between the `true` and `false` branches of the conditional. For this, we introduce two versions of `__sort:nnNnn`, which receive the new item as `#1` and place it either into the list `#2` of items less than the pivot `#4` or into the list `#3` of items greater or equal to the pivot.

```

\cs_new:Npn \__sort_i:nnnnNn #1#2#3#4#5#6
{
  #5 {#4} {#6} \__sort_ii:nnnnNn \__sort_i:nnnnNn
  {#6} { #2 {#1} } {#3} {#4}
}
\cs_new:Npn \__sort_ii:nnnnNn #1#2#3#4#5#6
{
  #5 {#4} {#6} \__sort_ii:nnnnNn \__sort_i:nnnnNn
  {#6} {#2} { #3 {#1} } {#4}
}

```

Note that the two functions have the form of `__sort_loop:wNn` above, receiving as `#5` the conditional or a function to end the loop. In fact, the lists `#2` and `#3` must be made of pairs *<conditional>* `{<item>}`, so we have to replace `{#6}` above by `{ #5 {#6} }`, and

{#1} by #1. The actual functions have one more argument, so all argument numbers are shifted compared to this code.

The third speed up is to avoid `\use:ff` using a continuation-passing style: `__sort_quick_split:NnNn` expects a list followed by `\s__sort_mark {⟨code⟩}`, and expands to `⟨code⟩ ⟨sorted list⟩`. Sorting the two parts of the list around the pivot is done with

```
\__sort_quick_split:NnNn #2 ... \s__sort_mark
{
\__sort_quick_split:NnNn #1 ... \s__sort_mark {⟨code⟩}
{⟨pivot⟩}
}
```

Items which are larger than the `⟨pivot⟩` are sorted, then placed after code that sorts the smaller items, and after the (braced) `⟨pivot⟩`.

The fourth speed up is avoid the recursive call to `\tl_sort:nN` with an empty first argument. For this, we introduce functions similar to the `__sort_i:nnnnNn` of the last example, but aware of whether the list of `⟨conditional⟩ {⟨item⟩}` read so far that are less than the pivot, and the list of those greater or equal, are empty or not: see `__sort_quick_split:NnNn` and functions defined below. Knowing whether the lists are empty or not is useless if we do not use distinct ending codes as appropriate. The splitting auxiliaries communicate to the `⟨end-loop⟩` function (that is initially placed after the “prepared” list) by placing a specific ending function, ignored when looping, but useful at the end. In fact, the `⟨end-loop⟩` function does nothing but place the appropriate ending function in front of all its arguments. The ending functions take care of sorting non-empty sublists, placing the pivot in between, and the continuation before.

The final change in fact slows down the code a little, but is required to avoid memory issues: schematically, when `TEX` encounters

```
\use:n { \use:n { \use:n { ... } ... } ... }
```

the argument of the first `\use:n` is not completely read by the second `\use:n`, hence must remain in memory; then the argument of the second `\use:n` is not completely read when grabbing the argument of the third `\use:n`, hence must remain in memory, and so on. The memory consumption grows quadratically with the number of nested `\use:n`. In practice, this means that we must read everything until a trailing `\s__sort_stop` once in a while, otherwise sorting lists of more than a few thousand items would exhaust a typical `TEX`’s memory.

`\tl_sort:nN`

`__sort_quick_prepare:Nnnn`

`__sort_quick_prepare_end:NNNnw`

`__sort_quick_cleanup:w`

The code within the `\exp_not:f` sorts the list, leaving in most cases a leading `\exp_not:f`, which stops the expansion, letting the result be return within `\exp_not:n`. We filter out the case of a list with no item, which would otherwise cause problems. Then prepare the token list #1 by inserting the conditional #2 before each item. The `prepare` auxiliary receives the conditional as #1, the prepared token list so far as #2, the next prepared item as #3, and the item after that as #4. The loop ends when #4 contains `\prg_break_point:`, then the `prepare_end` auxiliary finds the prepared token list as #4. The scene is then set up for `__sort_quick_split:NnNn`, which sorts the prepared list and perform the post action placed after `\s__sort_mark`, namely removing the trailing `\s__sort_stop` and `\s__sort_stop` and leaving `\exp_stop_f:` to stop `f`-expansion.

```
23238 \cs_new:Npn \tl_sort:nN #1#2
```

```
23239 {
```



```

23240 \exp_not:f
23241 {
23242   \tl_if_blank:nF {#1}
23243   {
23244     \__sort_quick_prepare:Nnnn #2 { } { }
23245     #1
23246     { \prg_break_point: \__sort_quick_prepare_end:NNNnw }
23247     \s__sort_stop
23248   }
23249 }
23250 }
23251 \cs_new:Npn \__sort_quick_prepare:Nnnn #1#2#3#4
23252 {
23253   \prg_break: #4 \prg_break_point:
23254   \__sort_quick_prepare:Nnnn #1 { #2 #3 } { #1 {#4} }
23255 }
23256 \cs_new:Npn \__sort_quick_prepare_end:NNNnw #1#2#3#4#5 \s__sort_stop
23257 {
23258   \__sort_quick_split:NnNn #4 \__sort_quick_end:nnTFNn { }
23259   \s__sort_mark { \__sort_quick_cleanup:w \exp_stop_f: }
23260   \s__sort_mark \s__sort_stop
23261 }
23262 \cs_new:Npn \__sort_quick_cleanup:w #1 \s__sort_mark \s__sort_stop {#1}

```

(End definition for `\tl_sort:nN` and others. This function is documented on page 53.)

`__sort_quick_split:NnNn` The `only_i`, `only_ii`, `split_i` and `split_ii` auxiliaries receive a useless first argument, the new item #2 (that they append to either one of the next two arguments), the list #3 of items less than the pivot, bigger items #4, the pivot #5, a *function* #6, and an item #7. The *function* is the user's *conditional* except at the end of the list where it is `__sort_quick_end:nnTFNn`. The comparison is applied to the *pivot* and the *item*, and calls the `only_i` or `split_i` auxiliaries if the *item* is smaller, and the `only_ii` or `split_ii` auxiliaries otherwise. In both cases, the next auxiliary goes to work right away, with no intermediate expansion that would slow down operations. Note that the argument #2 left for the next call has the form *conditional* {*item*}, so that the lists #3 and #4 keep the right form to be fed to the next sorting function. The `split` auxiliary differs from these in that it is missing three of the arguments, which would be empty, and its first argument is always the user's *conditional* rather than an ending function.

```

23263 \cs_new:Npn \__sort_quick_split:NnNn #1#2#3#4
23264 {
23265   #3 {#2} {#4} \__sort_quick_only_ii:NnnnnNn
23266   \__sort_quick_only_i:NnnnnNn
23267   \__sort_quick_single_end:nnwnw
23268   { #3 {#4} } { } { } {#2}
23269 }
23270 \cs_new:Npn \__sort_quick_only_i:NnnnnNn #1#2#3#4#5#6#7
23271 {
23272   #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn
23273   \__sort_quick_only_i:NnnnnNn
23274   \__sort_quick_only_i_end:nnwnw
23275   { #6 {#7} } { #3 #2 } { } {#5}
23276 }
23277 \cs_new:Npn \__sort_quick_only_ii:NnnnnNn #1#2#3#4#5#6#7

```

```

23278 {
23279     #6 {#5} {#7} \__sort_quick_only_ii:NnnnnNn
23280     \__sort_quick_split_i:NnnnnNn
23281     \__sort_quick_only_ii_end:nnwnw
23282     { #6 {#7} } { } { #4 #2 } {#5}
23283 }
23284 \cs_new:Npn \__sort_quick_split_i:NnnnnNn #1#2#3#4#5#6#7
23285 {
23286     #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn
23287     \__sort_quick_split_i:NnnnnNn
23288     \__sort_quick_split_end:nnwnw
23289     { #6 {#7} } { #3 #2 } {#4} {#5}
23290 }
23291 \cs_new:Npn \__sort_quick_split_ii:NnnnnNn #1#2#3#4#5#6#7
23292 {
23293     #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn
23294     \__sort_quick_split_i:NnnnnNn
23295     \__sort_quick_split_end:nnwnw
23296     { #6 {#7} } {#3} { #4 #2 } {#5}
23297 }

```

(End definition for __sort_quick_split:NnNn and others.)

```

\__sort_quick_end:nnTFNn
  \__sort_quick_single_end:nnwnw
  \__sort_quick_only_i_end:nnwnw
  \__sort_quick_only_ii_end:nnwnw
  \__sort_quick_split_end:nnwnw

```

The __sort_quick_end:nnTFNn appears instead of the user's conditional, and receives as its arguments the pivot #1, a fake item #2, a true and a false branches #3 and #4, followed by an ending function #5 (one of the four auxiliaries here) and another copy #6 of the fake item. All those are discarded except the function #5. This function receives lists #1 and #2 of items less than or greater than the pivot #3, then a continuation code #5 just after \s__sort_mark. To avoid a memory problem described earlier, all of the ending functions read #6 until \s__sort_stop and place #6 back into the input stream. When the lists #1 and #2 are empty, the single auxiliary simply places the continuation #5 before the pivot {#3}. When #2 is empty, #1 is sorted and placed before the pivot {#3}, taking care to feed the continuation #5 as a continuation for the function sorting #1. When #1 is empty, #2 is sorted, and the continuation argument is used to place the continuation #5 and the pivot {#3} before the sorted result. Finally, when both lists are non-empty, items larger than the pivot are sorted, then items less than the pivot, and the continuations are done in such a way to place the pivot in between.

```

23298 \cs_new:Npn \__sort_quick_end:nnTFNn #1#2#3#4#5#6 {#5}
23299 \cs_new:Npn \__sort_quick_single_end:nnwnw #1#2#3#4 \s__sort_mark #5#6 \s__sort_stop
23300 { #5 {#3} #6 \s__sort_stop }
23301 \cs_new:Npn \__sort_quick_only_i_end:nnwnw #1#2#3#4 \s__sort_mark #5#6 \s__sort_stop
23302 {
23303     \__sort_quick_split:NnNn #1
23304     \__sort_quick_end:nnTFNn { } \s__sort_mark {#5}
23305     {#3}
23306     #6 \s__sort_stop
23307 }
23308 \cs_new:Npn \__sort_quick_only_ii_end:nnwnw #1#2#3#4 \s__sort_mark #5#6 \s__sort_stop
23309 {
23310     \__sort_quick_split:NnNn #2
23311     \__sort_quick_end:nnTFNn { } \s__sort_mark { #5 {#3} }
23312     #6 \s__sort_stop
23313 }

```

```

23314 \cs_new:Npn \__sort_quick_split_end:nnnwnw #1#2#3#4 \s__sort_mark #5#6 \s__sort_stop
23315 {
23316   \__sort_quick_split:NnNn #2 \__sort_quick_end:nnTFNn { } \s__sort_mark
23317   {
23318     \__sort_quick_split:NnNn #1
23319     \__sort_quick_end:nnTFNn { } \s__sort_mark {#5}
23320     {#3}
23321   }
23322   #6 \s__sort_stop
23323 }

```

(End definition for __sort_quick_end:nnTFNn and others.)

38.6 Messages

__sort_error: Bailing out of the sorting code is a bit tricky. It may not be safe to use a delimited argument, so instead we redefine many l3sort commands to be trivial, with __sort_level: jumping to the break point. This error recovery won't work in a group.

```

23324 \cs_new_protected:Npn \__sort_error:
23325 {
23326   \cs_set_eq:NN \__sort_merge_blocks_aux: \prg_do_nothing:
23327   \cs_set_eq:NN \__sort_merge_blocks: \prg_do_nothing:
23328   \cs_set_protected:Npn \__sort_level: { \group_end: \prg_break: }
23329 }

```

(End definition for __sort_error:.)

__sort_disable_toksdef: While sorting, \toksdef is locally disabled to prevent users from using \newtoks or similar commands in their comparison code: the \toks registers that would be assigned are in use by l3sort. In format mode, none of this is needed since there is no \toks allocator.

```

23330 (*package)
23331 \cs_new_protected:Npn \__sort_disable_toksdef:
23332 { \cs_set_eq:NN \toksdef \__sort_disabled_toksdef:n }
23333 \cs_new_protected:Npn \__sort_disabled_toksdef:n #1
23334 {
23335   \__kernel_msg_error:nnx { kernel } { toksdef }
23336   { \token_to_str:N #1 }
23337   \__sort_error:
23338   \tex_toksdef:D #1
23339 }
23340 \__kernel_msg_new:nnnn { kernel } { toksdef }
23341 { Allocation~of~\iow_char:N\toks~registers~impossible~while~sorting. }
23342 {
23343   The~comparison~code~used~for~sorting~a~list~has~attempted~to~
23344   define~#1~as~a~new~\iow_char:N\toks~register~using~
23345   \iow_char:N\newtoks~
23346   or~a~similar~command.~The~list~will~not~be~sorted.
23347 }
23348 \endpackage

```

(End definition for __sort_disable_toksdef: and __sort_disabled_toksdef:n.)

`__sort_too_long_error:NNw` When there are too many items in a sequence, this is an error, and we clean up properly the mapping over items in the list: break using the type-specific breaking function #1.

```

23349 \cs_new_protected:Npn \__sort_too_long_error:NNw #1#2 \fi:
23350 {
23351   \fi:
23352   \__kernel_msg_error:nnxxx { kernel } { too-large }
23353   { \token_to_str:N #2 }
23354   { \int_eval:n { \l__sort_true_max_int - \l__sort_min_int } }
23355   { \int_eval:n { \l__sort_top_int - \l__sort_min_int } }
23356   #1 \__sort_error:
23357 }
23358 \__kernel_msg_new:nnnn { kernel } { too-large }
23359 { The~list~#1~is~too~long~to~be~sorted~by~TeX. }
23360 {
23361   TeX~has~#2~toks~registers~still~available:~
23362   this~only~allows~to~sort~with~up~to~#3~
23363   items.~The~list~will~not~be~sorted.
23364 }

```

(End definition for `__sort_too_long_error:NNw`.)

```

23365 \__kernel_msg_new:nnnn { kernel } { return-none }
23366 { The~comparison~code~did~not~return. }
23367 {
23368   When~sorting~a~list,~the~code~to~compare~items~#1~and~#2~
23369   did~not~call~
23370   \iow_char:N\sort_return_same: ~nor~
23371   \iow_char:N\sort_return_swapped: .~
23372   Exactly~one~of~these~should~be~called.
23373 }
23374 \__kernel_msg_new:nnnn { kernel } { return-two }
23375 { The~comparison~code~returned~multiple~times. }
23376 {
23377   When~sorting~a~list,~the~code~to~compare~items~#1~and~#2~called~
23378   \iow_char:N\sort_return_same: ~or~
23379   \iow_char:N\sort_return_swapped: ~multiple~times.~
23380   Exactly~one~of~these~should~be~called.
23381 }
23382 </initex | package>

```

39 l3tl-analysis implementation

```

23383 <@@=tl>

```

39.1 Internal functions

`\s__tl` The format used to store token lists internally uses the scan mark `\s__tl` as a delimiter.

(End definition for `\s__tl`.)

39.2 Internal format

The task of the l3tl-analysis module is to convert token lists to an internal format which allows us to extract all the relevant information about individual tokens (category code,

character code), as well as reconstruct the token list quickly. This internal format is used in `l3regex` where we need to support arbitrary tokens, and it is used in conversion functions in `l3str-convert`, where we wish to support clusters of characters instead of single tokens.

We thus need a way to encode any $\langle token \rangle$ (even begin-group and end-group character tokens) in a way amenable to manipulating tokens individually. The best we can do is to find $\langle tokens \rangle$ which both *o*-expand and *x*-expand to the given $\langle token \rangle$. Collecting more information about the category code and character code is also useful for regular expressions, since most regexes are catcode-agnostic. The internal format thus takes the form of a succession of items of the form

$\langle tokens \rangle \backslash s_tl \langle catcode \rangle \langle char\ code \rangle \backslash s_tl$

The $\langle tokens \rangle$ *o*- and *x*-expand to the original token in the token list or to the cluster of tokens corresponding to one Unicode character in the given encoding (for `l3str-convert`). The $\langle catcode \rangle$ is given as a single hexadecimal digit, 0 for control sequences. The $\langle char\ code \rangle$ is given as a decimal number, -1 for control sequences.

Using delimited arguments lets us build the $\langle tokens \rangle$ progressively when doing an encoding conversion in `l3str-convert`. On the other hand, the delimiter `\s_tl` may not appear unbraced in $\langle tokens \rangle$. This is not a problem because we are careful to wrap control sequences in braces (as an argument to `\exp_not:n`) when converting from a general token list to the internal format.

The current rule for converting a $\langle token \rangle$ to a balanced set of $\langle tokens \rangle$ which both *o*-expands and *x*-expands to it is the following.

- A control sequence `\cs` becomes `\exp_not:n { \cs } \s_tl 0 -1 \s_tl`.
- A begin-group character `{` becomes `\exp_after:wN { \if_false: } \fi: \s_tl 1 \langle char\ code \rangle \s_tl`.
- An end-group character `}` becomes `\if_false: { \fi: } \s_tl 2 \langle char\ code \rangle \s_tl`.
- A character with any other category code becomes `\exp_not:n {\langle character \rangle} \s_tl \langle hex\ catcode \rangle \langle char\ code \rangle \s_tl`.

23384 `(*initex | package)`

39.3 Variables and helper functions

`\s_tl` The scan mark `\s_tl` is used as a delimiter in the internal format. This is more practical than using a quark, because we would then need to control expansion much more carefully: compare `\int_value:w '#1 \s_tl` with `\int_value:w '#1 \exp_stop_f: \exp_not:N \q_mark` to extract a character code followed by the delimiter in an *x*-expansion.

23385 `\scan_new:N \s_tl`

(End definition for `\s_tl`.)

`\l_tl_analysis_token` The tokens in the token list are probed with the TeX primitive `\futurelet`. We use `\l_tl_analysis_token` in that construction. In some cases, we convert the following token to a string before probing it: then the token variable used is `\l_tl_analysis_char_token`.

23386 `\cs_new_eq:NN \l_tl_analysis_token ?`

23387 `\cs_new_eq:NN \l_tl_analysis_char_token ?`

(End definition for \l__tl_analysis_token and \l__tl_analysis_char_token.)

\l__tl_analysis_normal_int The number of normal (N-type argument) tokens since the last special token.

23388 \int_new:N \l__tl_analysis_normal_int

(End definition for \l__tl_analysis_normal_int.)

\l__tl_analysis_index_int During the first pass, this is the index in the array being built. During the second pass, it is equal to the maximum index in the array from the first pass.

23389 \int_new:N \l__tl_analysis_index_int

(End definition for \l__tl_analysis_index_int.)

\l__tl_analysis_nesting_int Nesting depth of explicit begin-group and end-group characters during the first pass. This lets us detect the end of the token list without a reserved end-marker.

23390 \int_new:N \l__tl_analysis_nesting_int

(End definition for \l__tl_analysis_nesting_int.)

\l__tl_analysis_type_int When encountering special characters, we record their “type” in this integer.

23391 \int_new:N \l__tl_analysis_type_int

(End definition for \l__tl_analysis_type_int.)

\g__tl_analysis_result_tl The result of the conversion is stored in this token list, with a succession of items of the form

$\langle tokens \rangle \backslash s_tl \langle catcode \rangle \langle char\ code \rangle \backslash s_tl$

23392 \tl_new:N \g__tl_analysis_result_tl

(End definition for \g__tl_analysis_result_tl.)

_tl_analysis_extract_charcode: Extracting the character code from the meaning of \l__tl_analysis_token. This has no error checking, and should only be assumed to work for begin-group and end-group character tokens. It produces a number in the form ‘ $\langle char \rangle$ ’.

_tl_analysis_extract_charcode_aux:w

23393 \cs_new:Npn _tl_analysis_extract_charcode:

23394 {

23395 \exp_after:wN _tl_analysis_extract_charcode_aux:w

23396 \token_to_meaning:N \l__tl_analysis_token

23397 }

23398 \cs_new:Npn _tl_analysis_extract_charcode_aux:w #1 ~ #2 ~ { ‘ }

(End definition for _tl_analysis_extract_charcode: and _tl_analysis_extract_charcode_aux:w.)

_tl_analysis_cs_space_count:NN Counts the number of spaces in the string representation of its second argument, as well as the number of characters following the last space in that representation, and feeds the two numbers as semicolon-delimited arguments to the first argument. When this function is used, the escape character is printable and non-space.

_tl_analysis_cs_space_count:w

_tl_analysis_cs_space_count_end:w

23399 \cs_new:Npn _tl_analysis_cs_space_count:NN #1 #2

23400 {

23401 \exp_after:wN #1

23402 \int_value:w \int_eval:w 0

23403 \exp_after:wN _tl_analysis_cs_space_count:w

23404 \token_to_str:N #2

```

23405         \fi: \_tl_analysis_cs_space_count_end:w ; ~ !
23406     }
23407 \cs_new:Npn \_tl_analysis_cs_space_count:w #1 ~
23408 {
23409     \if_false: #1 #1 \fi:
23410     + 1
23411     \_tl_analysis_cs_space_count:w
23412 }
23413 \cs_new:Npn \_tl_analysis_cs_space_count_end:w ; #1 \fi: #2 !
23414 { \exp_after:wN ; \int_value:w \str_count_ignore_spaces:n {#1} ; }

(End definition for \_tl_analysis_cs_space_count:NN, \_tl_analysis_cs_space_count:w, and \_tl-
tl_analysis_cs_space_count_end:w.)

```

39.4 Plan of attack

Our goal is to produce a token list of the form roughly

```

⟨token 1⟩ \s@_ ⟨catcode 1⟩ ⟨char code 1⟩ \s@_
⟨token 2⟩ \s__tl ⟨catcode 2⟩ ⟨char code 2⟩ \s__tl
... ⟨token N⟩ \s__tl ⟨catcode N⟩ ⟨char code N⟩ \s__tl

```

Most but not all tokens can be grabbed as an undelimited (N-type) argument by $\text{T}_{\text{E}}\text{X}$. The plan is to have a two pass system. In the first pass, locate special tokens, and store them in various `\toks` registers. In the second pass, which is done within an `x`-expanding assignment, normal tokens are taken in as N-type arguments, and special tokens are retrieved from the `\toks` registers, and removed from the input stream by some means. The whole process takes linear time, because we avoid building the result one item at a time.

We make the escape character printable (backslash, but this later oscillates between slash and backslash): this allows us to distinguish characters from control sequences.

A token has two characteristics: its `\meaning`, and what it looks like for $\text{T}_{\text{E}}\text{X}$ when it is in scanning mode (*e.g.*, when capturing parameters for a macro). For our purposes, we distinguish the following meanings:

- begin-group token (category code 1), either space (character code 32), or non-space;
- end-group token (category code 2), either space (character code 32), or non-space;
- space token (category code 10, character code 32);
- anything else (then the token is always an N-type argument).

The token itself can “look like” one of the following

- a non-active character, in which case its meaning is automatically that associated to its character code and category code, we call it “true” character;
- an active character;
- a control sequence.

The only tokens which are not valid N-type arguments are true begin-group characters, true end-group characters, and true spaces. We detect those characters by scanning ahead with `\futurelet`, then distinguishing true characters from control sequences set equal to them using the `\string` representation.

The second pass is a simple exercise in expandable loops.

`__tl_analysis:n` Everything is done within a group, and all definitions are local. We use `\group_align_safe_begin/end:` to avoid problems in case `__tl_analysis:n` is used within an alignment and its argument contains alignment tab tokens.

```

23415 \cs_new_protected:Npn \__tl_analysis:n #1
23416 {
23417   \group_begin:
23418   \group_align_safe_begin:
23419     \__tl_analysis_a:n {#1}
23420     \__tl_analysis_b:n {#1}
23421   \group_align_safe_end:
23422   \group_end:
23423 }
```

(End definition for `__tl_analysis:n`.)

39.5 Disabling active characters

`__tl_analysis_disable:n` Active characters can cause problems later on in the processing, so we provide a way to disable them, by setting them to undefined. Since Unicode contains too many characters to loop over all of them, we instead do this whenever we encounter a character. For pTeX and upTeX we skip characters beyond [0, 255] because `\lccode` only allows those values.

```

23424 \group_begin:
23425   \char_set_catcode_active:N \^^@
23426   \cs_new_protected:Npn \__tl_analysis_disable:n #1
23427   {
23428     \tex_lccode:D 0 = #1 \exp_stop_f:
23429     \tex_lowercase:D { \tex_let:D \^^@ } \tex_undefined:D
23430   }
23431   \bool_lazy_or:nnT
23432     { \sys_if_engine_ptex_p: }
23433     { \sys_if_engine_uptex_p: }
23434   {
23435     \cs_gset_protected:Npn \__tl_analysis_disable:n #1
23436     {
23437       \if_int_compare:w 256 > #1 \exp_stop_f:
23438       \tex_lccode:D 0 = #1 \exp_stop_f:
23439       \tex_lowercase:D { \tex_let:D \^^@ } \tex_undefined:D
23440     }
23441   }
23442 }
23443 \group_end:
```

(End definition for `__tl_analysis_disable:n`.)

39.6 First pass

The goal of this pass is to detect special (non-N-type) tokens, and count how many N-type tokens lie between special tokens. Also, we wish to store some representation of each special token in a `\toks` register.

We have 11 types of tokens:

1. a true non-space begin-group character;
2. a true space begin-group character;

3. a true non-space end-group character;
4. a true space end-group character;
5. a true space blank space character;
6. an active character;
7. any other true character;
8. a control sequence equal to a begin-group token (category code 1);
9. a control sequence equal to an end-group token (category code 2);
10. a control sequence equal to a space token (character code 32, category code 10);
11. any other control sequence.

Our first tool is `\futurelet`. This cannot distinguish case 8 from 1 or 2, nor case 9 from 3 or 4, nor case 10 from case 5. Those cases are later distinguished by applying the `\string` primitive to the following token, after possibly changing the escape character to ensure that a control sequence’s string representation cannot be mistaken for the true character.

In cases 6, 7, and 11, the following token is a valid N-type argument, so we grab it and distinguish the case of a character from a control sequence: in the latter case, `\str_tail:n {\token}` is non-empty, because the escape character is printable.

`__tl_analysis_a:n` We read tokens one by one using `\futurelet`. While performing the loop, we keep track of the number of true begin-group characters minus the number of true end-group characters in `\l__tl_analysis_nesting_int`. This reaches -1 when we read the closing brace.

```

23444 \cs_new_protected:Npn \__tl_analysis_a:n #1
23445 {
23446   \__tl_analysis_disable:n { 32 }
23447   \int_set:Nn \tex_escapechar:D { 92 }
23448   \int_zero:N \l__tl_analysis_normal_int
23449   \int_zero:N \l__tl_analysis_index_int
23450   \int_zero:N \l__tl_analysis_nesting_int
23451   \if_false: { \fi: \__tl_analysis_a_loop:w #1 }
23452   \int_decr:N \l__tl_analysis_index_int
23453 }
```

(End definition for `__tl_analysis_a:n`.)

`__tl_analysis_a_loop:w` Read one character and check its type.

```

23454 \cs_new_protected:Npn \__tl_analysis_a_loop:w
23455 { \tex_futurelet:D \l__tl_analysis_token \__tl_analysis_a_type:w }
```

(End definition for `__tl_analysis_a_loop:w`.)

`__tl_analysis_a_type:w` At this point, `\l__tl_analysis_token` holds the meaning of the following token. We store in `\l__tl_analysis_type_int` information about the meaning of the token ahead:

- 0 space token;
- 1 begin-group token;

- -1 end-group token;
- 2 other.

The values 0, 1, -1 correspond to how much a true such character changes the nesting level (2 is used only here, and is irrelevant later). Then call the auxiliary for each case. Note that nesting conditionals here is safe because we only skip over `\l__tl_analysis_token` if it matches with one of the character tokens (hence is not a primitive conditional).

```

23456 \cs_new_protected:Npn \__tl_analysis_a_type:w
23457 {
23458   \l__tl_analysis_type_int =
23459   \if_meaning:w \l__tl_analysis_token \c_space_token
23460   0
23461   \else:
23462     \if_catcode:w \exp_not:N \l__tl_analysis_token \c_group_begin_token
23463     1
23464     \else:
23465       \if_catcode:w \exp_not:N \l__tl_analysis_token \c_group_end_token
23466       - 1
23467       \else:
23468         2
23469       \fi:
23470     \fi:
23471   \fi:
23472   \exp_stop_f:
23473   \if_case:w \l__tl_analysis_type_int
23474     \exp_after:wN \__tl_analysis_a_space:w
23475   \or: \exp_after:wN \__tl_analysis_a_bgroup:w
23476   \or: \exp_after:wN \__tl_analysis_a_safe:N
23477   \else: \exp_after:wN \__tl_analysis_a_egroup:w
23478   \fi:
23479 }

```

(End definition for `__tl_analysis_a_type:w`.)

`__tl_analysis_a_space:w`
`__tl_analysis_a_space_test:w`

In this branch, the following token's meaning is a blank space. Apply `\string` to that token: a true blank space gives a space, a control sequence gives a result starting with the escape character, an active character gives something else than a space since we disabled the space. We grab as `\l__tl_analysis_char_token` the first character of the string representation then test it in `__tl_analysis_a_space_test:w`. Also, since `__tl_analysis_a_store:` expects the special token to be stored in the relevant `\toks` register, we do that. The extra `\exp_not:n` is unnecessary of course, but it makes the treatment of all tokens more homogeneous. If we discover that the next token was actually a control sequence or an active character instead of a true space, then we step the counter of normal tokens. We now have in front of us the whole string representation of the control sequence, including potential spaces; those will appear to be true spaces later in this pass. Hence, all other branches of the code in this first pass need to consider the string representation, so that the second pass does not need to test the meaning of tokens, only strings.

```

23480 \cs_new_protected:Npn \__tl_analysis_a_space:w
23481 {
23482   \tex_afterassignment:D \__tl_analysis_a_space_test:w
23483   \exp_after:wN \cs_set_eq:NN

```

```

23484 \exp_after:wN \l__tl_analysis_char_token
23485 \token_to_str:N
23486 }
23487 \cs_new_protected:Npn \__tl_analysis_a_space_test:w
23488 {
23489 \if_meaning:w \l__tl_analysis_char_token \c_space_token
23490 \tex_toks:D \l__tl_analysis_index_int { \exp_not:n { ~ } }
23491 \__tl_analysis_a_store:
23492 \else:
23493 \int_incr:N \l__tl_analysis_normal_int
23494 \fi:
23495 \__tl_analysis_a_loop:w
23496 }

```

(End definition for __tl_analysis_a_space:w and __tl_analysis_a_space_test:w.)

```

\__tl_analysis_a_bgroup:w
\__tl_analysis_a_egroup:w
\__tl_analysis_a_group:nw
\__tl_analysis_a_group_aux:w
\__tl_analysis_a_group_auxii:w
\__tl_analysis_a_group_test:w

```

The token is most likely a true character token with catcode 1 or 2, but it might be a control sequence, or an active character. Optimizing for the first case, we store in a toks register some code that expands to that token. Since we will turn what follows into a string, we make sure the escape character is different from the current character code (by switching between solidus and backslash). To detect the special case of an active character let to the catcode 1 or 2 character with the same character code, we disable the active character with that character code and re-test: if the following token has become undefined we can in fact safely grab it. We are finally ready to turn what follows to a string and test it. This is one place where we need \l__tl_analysis_char_token to be a separate control sequence from \l__tl_analysis_token, to compare them.

```

23497 \group_begin:
23498 \char_set_catcode_group_begin:N \^^@ % {
23499 \cs_new_protected:Npn \__tl_analysis_a_bgroup:w
23500 { \__tl_analysis_a_group:nw { \exp_after:wN \^^@ \if_false: } \fi: } }
23501 \char_set_catcode_group_end:N \^^@
23502 \cs_new_protected:Npn \__tl_analysis_a_egroup:w
23503 { \__tl_analysis_a_group:nw { \if_false: { \fi: \^^@ } } % }
23504 \group_end:
23505 \cs_new_protected:Npn \__tl_analysis_a_group:nw #1
23506 {
23507 \tex_lccode:D 0 = \__tl_analysis_extract_charcode: \scan_stop:
23508 \tex_lowercase:D { \tex_toks:D \l__tl_analysis_index_int {#1} }
23509 \if_int_compare:w \tex_lccode:D 0 = \tex_escapechar:D
23510 \int_set:Nn \tex_escapechar:D { 139 - \tex_escapechar:D }
23511 \fi:
23512 \__tl_analysis_disable:n { \tex_lccode:D 0 }
23513 \tex_futurelet:D \l__tl_analysis_token \__tl_analysis_a_group_aux:w
23514 }
23515 \cs_new_protected:Npn \__tl_analysis_a_group_aux:w
23516 {
23517 \if_meaning:w \l__tl_analysis_token \tex_undefined:D
23518 \exp_after:wN \__tl_analysis_a_safe:N
23519 \else:
23520 \exp_after:wN \__tl_analysis_a_group_auxii:w
23521 \fi:
23522 }
23523 \cs_new_protected:Npn \__tl_analysis_a_group_auxii:w
23524 {

```

```

23525 \tex_afterassignment:D \_tl_analysis_a_group_test:w
23526 \exp_after:wN \cs_set_eq:NN
23527 \exp_after:wN \l__tl_analysis_char_token
23528 \token_to_str:N
23529 }
23530 \cs_new_protected:Npn \_tl_analysis_a_group_test:w
23531 {
23532   \if_charcode:w \l__tl_analysis_token \l__tl_analysis_char_token
23533     \_tl_analysis_a_store:
23534   \else:
23535     \int_incr:N \l__tl_analysis_normal_int
23536   \fi:
23537   \_tl_analysis_a_loop:w
23538 }

```

(End definition for `_tl_analysis_a_bgroup:w` and others.)

`_tl_analysis_a_store:` This function is called each time we meet a special token; at this point, the `\toks` register `\l__tl_analysis_index_int` holds a token list which expands to the given special token. Also, the value of `\l__tl_analysis_type_int` indicates which case we are in:

- -1 end-group character;
- 0 space character;
- 1 begin-group character.

We need to distinguish further the case of a space character (code 32) from other character codes, because those behave differently in the second pass. Namely, after testing the `\lccode` of 0 (which holds the present character code) we change the cases above to

- -2 space end-group character;
- -1 non-space end-group character;
- 0 space blank space character;
- 1 non-space begin-group character;
- 2 space begin-group character.

This has the property that non-space characters correspond to odd values of `\l__tl_analysis_type_int`. The number of normal tokens until here and the type of special token are packed into a `\skip` register. Finally, we check whether we reached the last closing brace, in which case we stop by disabling the looping function (locally).

```

23539 \cs_new_protected:Npn \_tl_analysis_a_store:
23540 {
23541   \tex_advance:D \l__tl_analysis_nesting_int \l__tl_analysis_type_int
23542   \if_int_compare:w \tex_lccode:D 0 = '\ \exp_stop_f:
23543     \tex_advance:D \l__tl_analysis_type_int \l__tl_analysis_type_int
23544   \fi:
23545   \tex_skip:D \l__tl_analysis_index_int
23546     = \l__tl_analysis_normal_int sp
23547     plus \l__tl_analysis_type_int sp \scan_stop:
23548   \int_incr:N \l__tl_analysis_index_int
23549   \int_zero:N \l__tl_analysis_normal_int

```

```

23550 \if_int_compare:w \l__tl_analysis_nesting_int = -1 \exp_stop_f:
23551 \cs_set_eq:NN \__tl_analysis_a_loop:w \scan_stop:
23552 \fi:
23553 }

```

(End definition for __tl_analysis_a_store:.)

```

\__tl_analysis_a_safe:N
\__tl_analysis_a_cs:ww

```

This should be the simplest case: since the upcoming token is safe, we can simply grab it in a second pass. If the token is a single character (including space), the `\if_charcode:w` test yields true; we disable a potentially active character (that could otherwise masquerade as the true character in the next pass) and we count one “normal” token. On the other hand, if the token is a control sequence, we should replace it by its string representation for compatibility with other code branches. Instead of slowly looping through the characters with the main code, we use the knowledge of how the second pass works: if the control sequence name contains no space, count that token as a number of normal tokens equal to its string length. If the control sequence contains spaces, they should be registered as special characters by increasing `\l__tl_analysis_index_int` (no need to carefully count character between each space), and all characters after the last space should be counted in the following sequence of “normal” tokens.

```

23554 \cs_new_protected:Npn \__tl_analysis_a_safe:N #1
23555 {
23556   \if_charcode:w
23557     \scan_stop:
23558     \exp_after:wN \use_none:n \token_to_str:N #1 \prg_do_nothing:
23559     \scan_stop:
23560     \exp_after:wN \use_i:nn
23561   \else:
23562     \exp_after:wN \use_ii:nn
23563   \fi:
23564   {
23565     \__tl_analysis_disable:n { '#1 }
23566     \int_incr:N \l__tl_analysis_normal_int
23567   }
23568   { \__tl_analysis_cs_space_count:NN \__tl_analysis_a_cs:ww #1 }
23569   \__tl_analysis_a_loop:w
23570 }
23571 \cs_new_protected:Npn \__tl_analysis_a_cs:ww #1; #2;
23572 {
23573   \if_int_compare:w #1 > 0 \exp_stop_f:
23574   \tex_skip:D \l__tl_analysis_index_int
23575   = \int_eval:n { \l__tl_analysis_normal_int + 1 } sp \exp_stop_f:
23576   \tex_advance:D \l__tl_analysis_index_int #1 \exp_stop_f:
23577   \else:
23578     \tex_advance:D
23579   \fi:
23580   \l__tl_analysis_normal_int #2 \exp_stop_f:
23581 }

```

(End definition for __tl_analysis_a_safe:N and __tl_analysis_a_cs:ww.)

39.7 Second pass

The second pass is an exercise in expandable loops. All the necessary information is stored in `\skip` and `\toks` registers.

`__tl_analysis_b:n` Start the loop with the index 0. No need for an end-marker: the loop stops by itself when
`__tl_analysis_b_loop:w` the last index is read. We repeatedly oscillate between reading long stretches of normal
tokens, and reading special tokens.

```

23582 \cs_new_protected:Npn \__tl_analysis_b:n #1
23583 {
23584   \tl_gset:Nx \g__tl_analysis_result_tl
23585   {
23586     \__tl_analysis_b_loop:w 0; #1
23587     \prg_break_point:
23588   }
23589 }
23590 \cs_new:Npn \__tl_analysis_b_loop:w #1;
23591 {
23592   \exp_after:wN \__tl_analysis_b_normals:ww
23593   \int_value:w \tex_skip:D #1 ; #1 ;
23594 }

```

(End definition for `__tl_analysis_b:n` and `__tl_analysis_b_loop:w`.)

`__tl_analysis_b_normals:ww` The first argument is the number of normal tokens which remain to be read, and the
`__tl_analysis_b_normal:wwN` second argument is the index in the array produced in the first step. A character's string
representation is always one character long, while a control sequence is always longer (we
have set the escape character to a printable value). In both cases, we leave `\exp_not:n`
`{⟨token⟩}` `\s__tl` in the input stream (after x-expansion). Here, `\exp_not:n` is used
rather than `\exp_not:N` because #3 could be a macro parameter character or could be
`\s__tl` (which must be hidden behind braces in the result).

```

23595 \cs_new:Npn \__tl_analysis_b_normals:ww #1;
23596 {
23597   \if_int_compare:w #1 = 0 \exp_stop_f:
23598   \__tl_analysis_b_special:w
23599   \fi:
23600   \__tl_analysis_b_normal:wwN #1;
23601 }
23602 \cs_new:Npn \__tl_analysis_b_normal:wwN #1; #2; #3
23603 {
23604   \exp_not:n { \exp_not:n { #3 } } \s__tl
23605   \if_charcode:w
23606     \scan_stop:
23607     \exp_after:wN \use_none:n \token_to_str:N #3 \prg_do_nothing:
23608     \scan_stop:
23609     \exp_after:wN \__tl_analysis_b_char:Nww
23610   \else:
23611     \exp_after:wN \__tl_analysis_b_cs:Nww
23612   \fi:
23613   #3 #1; #2;
23614 }

```

(End definition for `__tl_analysis_b_normals:ww` and `__tl_analysis_b_normal:wwN`.)

`__tl_analysis_b_char:Nww` If the normal token we grab is a character, leave `⟨catcode⟩` `⟨charcode⟩` followed by `\s__tl`
in the input stream, and call `__tl_analysis_b_normals:ww` with its first argument
decremented.

```

23615 \cs_new:Npx \__tl_analysis_b_char:Nww #1

```

```

23616 {
23617   \exp_not:N \if_meaning:w #1 \exp_not:N \tex_undefined:D
23618   \token_to_str:N D \exp_not:N \else:
23619   \exp_not:N \if_catcode:w #1 \c_catcode_other_token
23620   \token_to_str:N C \exp_not:N \else:
23621   \exp_not:N \if_catcode:w #1 \c_catcode_letter_token
23622   \token_to_str:N B \exp_not:N \else:
23623   \exp_not:N \if_catcode:w #1 \c_math_toggle_token      3
23624   \exp_not:N \else:
23625   \exp_not:N \if_catcode:w #1 \c_alignment_token        4
23626   \exp_not:N \else:
23627   \exp_not:N \if_catcode:w #1 \c_math_superscript_token 7
23628   \exp_not:N \else:
23629   \exp_not:N \if_catcode:w #1 \c_math_subscript_token   8
23630   \exp_not:N \else:
23631   \exp_not:N \if_catcode:w #1 \c_space_token
23632   \token_to_str:N A \exp_not:N \else:
23633   6
23634   \exp_not:n { \fi: \fi: \fi: \fi: \fi: \fi: \fi: \fi: }
23635   \exp_not:N \int_value:w '#1 \s__tl
23636   \exp_not:N \exp_after:wN \exp_not:N \__tl_analysis_b_normals:ww
23637   \exp_not:N \int_value:w \exp_not:N \int_eval:w - 1 +
23638 }

```

(End definition for __tl_analysis_b_char:Nww.)

__tl_analysis_b_cs:Nww If the token we grab is a control sequence, leave 0 -1 (as category code and character code) in the input stream, followed by \s__tl, and call __tl_analysis_b_normals:ww with updated arguments.

```

23639 \cs_new:Npn \__tl_analysis_b_cs:Nww #1
23640 {
23641   0 -1 \s__tl
23642   \__tl_analysis_cs_space_count:NN \__tl_analysis_b_cs_test:ww #1
23643 }
23644 \cs_new:Npn \__tl_analysis_b_cs_test:ww #1 ; #2 ; #3 ; #4 ;
23645 {
23646   \exp_after:wN \__tl_analysis_b_normals:ww
23647   \int_value:w \int_eval:w
23648   \if_int_compare:w #1 = 0 \exp_stop_f:
23649     #3
23650   \else:
23651     \tex_skip:D \int_eval:n { #4 + #1 } \exp_stop_f:
23652   \fi:
23653   - #2
23654   \exp_after:wN ;
23655   \int_value:w \int_eval:n { #4 + #1 } ;
23656 }

```

(End definition for __tl_analysis_b_cs:Nww and __tl_analysis_b_cs_test:ww.)

__tl_analysis_b_special:w Here, #1 is the current index in the array built in the first pass. Check now whether we reached the end (we shouldn't keep the trailing end-group character that marked the end of the token list in the first pass). Unpack the \toks register: when x-expanding again,

we will get the special token. Then leave the category code in the input stream, followed by the character code, and call `__tl_analysis_b_loop:w` with the next index.

```

23657 \group_begin:
23658   \char_set_catcode_other:N A
23659   \cs_new:Npn \__tl_analysis_b_special:w
23660     \fi: \__tl_analysis_b_normal:wwN 0 ; #1 ;
23661   {
23662     \fi:
23663     \if_int_compare:w #1 = \l__tl_analysis_index_int
23664       \exp_after:wN \prg_break:
23665     \fi:
23666     \tex_the:D \tex_toks:D #1 \s__tl
23667     \if_case:w \tex_gluestretch:D \tex_skip:D #1 \exp_stop_f:
23668       \token_to_str:N A
23669     \or: 1
23670     \or: 1
23671     \else: 2
23672     \fi:
23673     \if_int_odd:w \tex_gluestretch:D \tex_skip:D #1 \exp_stop_f:
23674       \exp_after:wN \__tl_analysis_b_special_char:wN \int_value:w
23675     \else:
23676       \exp_after:wN \__tl_analysis_b_special_space:w \int_value:w
23677     \fi:
23678     \int_eval:n { 1 + #1 } \exp_after:wN ;
23679     \token_to_str:N
23680   }
23681 \group_end:
23682 \cs_new:Npn \__tl_analysis_b_special_char:wN #1 ; #2
23683   {
23684     \int_value:w ‘#2 \s__tl
23685     \__tl_analysis_b_loop:w #1 ;
23686   }
23687 \cs_new:Npn \__tl_analysis_b_special_space:w #1 ; ~
23688   {
23689     32 \s__tl
23690     \__tl_analysis_b_loop:w #1 ;
23691   }

```

(End definition for `__tl_analysis_b_special:w`, `__tl_analysis_b_special_char:wN`, and `__tl_analysis_b_special_space:w`.)

39.8 Mapping through the analysis

`\tl_analysis_map_inline:nn` First obtain the analysis of the token list into `\g__tl_analysis_result_tl`. To allow nested mappings, increase the nesting depth `\g__kernel_prng_map_int` (shared between all modules), then define the looping macro, which has a name specific to that nesting depth. That looping grabs the $\langle tokens \rangle$, $\langle catcode \rangle$ and $\langle char code \rangle$; it checks for the end of the loop with `\use_none:n ##2`, normally empty, but which becomes `\tl_map_break:` at the end; it then performs the user’s code #2, and loops by calling itself. When the loop ends, remember to decrease the nesting depth.

```

23692 \cs_new_protected:Npn \tl_analysis_map_inline:nn #1
23693   {
23694     \__tl_analysis:n {#1}

```



```

23695 \int_gincr:N \g__kernel_prg_map_int
23696 \exp_args:Nc \__tl_analysis_map_inline_aux:Nn
23697 { \__tl_analysis_map_inline_ \int_use:N \g__kernel_prg_map_int :wNw }
23698 }
23699 \cs_new_protected:Npn \tl_analysis_map_inline:Nn #1
23700 { \exp_args:No \tl_analysis_map_inline:nn #1 }
23701 \cs_new_protected:Npn \__tl_analysis_map_inline_aux:Nn #1#2
23702 {
23703   \cs_gset_protected:Npn #1 ##1 \s__tl ##2 ##3 \s__tl
23704   {
23705     \use_none:n ##2
23706     \__tl_analysis_map_inline_aux:nnn {##1} {##3} {##2}
23707   }
23708   \cs_gset_protected:Npn \__tl_analysis_map_inline_aux:nnn ##1##2##3
23709   {
23710     #2
23711     #1
23712   }
23713   \exp_after:wN #1
23714   \g__tl_analysis_result_tl
23715   \s__tl { ? \tl_map_break: } \s__tl
23716   \prg_break_point:Nn \tl_map_break:
23717   { \int_gdecr:N \g__kernel_prg_map_int }
23718 }

```

(End definition for `\tl_analysis_map_inline:nn` and others. These functions are documented on page 221.)

39.9 Showing the results

`\tl_analysis_show:N` Add to `__tl_analysis:n` a third pass to display tokens to the terminal. If the token list variable is not defined, throw the same error as `\tl_show:N` by simply calling that function.

```

23719 \cs_new_protected:Npn \tl_analysis_show:N #1
23720 {
23721   \tl_if_exist:NTF #1
23722   {
23723     \exp_args:No \__tl_analysis:n {#1}
23724     \msg_show:nnxxxx { LaTeX / kernel } { show-tl-analysis }
23725     { \token_to_str:N #1 } { \__tl_analysis_show: } { } { }
23726   }
23727   { \tl_show:N #1 }
23728 }
23729 \cs_new_protected:Npn \tl_analysis_show:n #1
23730 {
23731   \__tl_analysis:n {#1}
23732   \msg_show:nnxxxx { LaTeX / kernel } { show-tl-analysis }
23733   { } { \__tl_analysis_show: } { } { }
23734 }

```

(End definition for `\tl_analysis_show:N` and `\tl_analysis_show:n`. These functions are documented on page 221.)

`__tl_analysis_show:` Here, #1 o- and x-expands to the token; #2 is the category code (one uppercase hexadecimal digit), 0 for control sequences; #3 is the character code, which we ignore. In the

cases of control sequences and active characters, the meaning may overflow one line, and we want to truncate it. Those cases are thus separated out.

```

23735 \cs_new:Npn \__tl_analysis_show:
23736 {
23737   \exp_after:wN \__tl_analysis_show_loop:wNw \g__tl_analysis_result_tl
23738   \s__tl { ? \prg_break: } \s__tl
23739   \prg_break_point:
23740 }
23741 \cs_new:Npn \__tl_analysis_show_loop:wNw #1 \s__tl #2 #3 \s__tl
23742 {
23743   \use_none:n #2
23744   \iow_newline: > \use:nn { ~ } { ~ }
23745   \if_int_compare:w "#2 = 0 \exp_stop_f:
23746     \exp_after:wN \__tl_analysis_show_cs:n
23747   \else:
23748     \if_int_compare:w "#2 = 13 \exp_stop_f:
23749     \exp_after:wN \exp_after:wN
23750     \exp_after:wN \__tl_analysis_show_active:n
23751   \else:
23752     \exp_after:wN \exp_after:wN
23753     \exp_after:wN \__tl_analysis_show_normal:n
23754   \fi:
23755   \fi:
23756   {#1}
23757   \__tl_analysis_show_loop:wNw
23758 }

```

(End definition for __tl_analysis_show: and __tl_analysis_show_loop:wNw.)

__tl_analysis_show_normal:n Non-active characters are a simple matter of printing the character, and its meaning. Our test suite checks that begin-group and end-group characters do not mess up TeX's alignment status.

```

23759 \cs_new:Npn \__tl_analysis_show_normal:n #1
23760 {
23761   \exp_after:wN \token_to_str:N #1 ~
23762   ( \exp_after:wN \token_to_meaning:N #1 )
23763 }

```

(End definition for __tl_analysis_show_normal:n.)

__tl_analysis_show_value:N This expands to the value of #1 if it has any.

```

23764 \cs_new:Npn \__tl_analysis_show_value:N #1
23765 {
23766   \token_if_expandable:NF #1
23767   {
23768     \token_if_chardef:NTF #1 \prg_break: { }
23769     \token_if_mathchardef:NTF #1 \prg_break: { }
23770     \token_if_dim_register:NTF #1 \prg_break: { }
23771     \token_if_int_register:NTF #1 \prg_break: { }
23772     \token_if_skip_register:NTF #1 \prg_break: { }
23773     \token_if_toks_register:NTF #1 \prg_break: { }
23774     \use_none:nnn
23775     \prg_break_point:
23776     \use:n { \exp_after:wN = \tex_the:D #1 }

```

```

23777     }
23778 }

```

(End definition for `_tl_analysis_show_value:N`.)

`_tl_analysis_show_cs:n` Control sequences and active characters are printed in the same way, making sure not to go beyond the `\l_iow_line_count_int`. In case of an overflow, we replace the last characters by `\c__tl_analysis_show_etc_str`.

```

\__tl_analysis_show_active:n
\__tl_analysis_show_long:nn
  \_tl_analysis_show_long_aux:nnnn
23779 \cs_new:Npn \_tl_analysis_show_cs:n #1
23780 { \exp_args:No \_tl_analysis_show_long:nn {#1} { control~sequence= } }
23781 \cs_new:Npn \_tl_analysis_show_active:n #1
23782 { \exp_args:No \_tl_analysis_show_long:nn {#1} { active~character= } }
23783 \cs_new:Npn \_tl_analysis_show_long:n #1
23784 {
23785   \_tl_analysis_show_long_aux:oofn
23786   { \token_to_str:N #1 }
23787   { \token_to_meaning:N #1 }
23788   { \_tl_analysis_show_value:N #1 }
23789 }
23790 \cs_new:Npn \_tl_analysis_show_long_aux:nnnn #1#2#3#4
23791 {
23792   \int_compare:nNnTF
23793   { \str_count:n { #1 ~ ( #4 #2 #3 ) } }
23794   > { \l_iow_line_count_int - 3 }
23795   {
23796     \str_range:nnn { #1 ~ ( #4 #2 #3 ) } { 1 }
23797     {
23798       \l_iow_line_count_int - 3
23799       - \str_count:N \c__tl_analysis_show_etc_str
23800     }
23801     \c__tl_analysis_show_etc_str
23802   }
23803   { #1 ~ ( #4 #2 #3 ) }
23804 }
23805 \cs_generate_variant:Nn \_tl_analysis_show_long_aux:nnnn { oof }

```

(End definition for `_tl_analysis_show_cs:n` and others.)

39.10 Messages

`\c__tl_analysis_show_etc_str` When a control sequence (or active character) and its meaning are too long to fit in one line of the terminal, the end is replaced by this token list.

```

23806 \tl_const:Nx \c__tl_analysis_show_etc_str % (
23807 { \token_to_str:N \ETC.) }

```

(End definition for `\c__tl_analysis_show_etc_str`.)

```

23808 \__kernel_msg_new:nnn { kernel } { show-tl-analysis }
23809 {
23810   The~token~list~ \tl_if_empty:nF {#1} { #1 ~ }
23811   \tl_if_empty:nTF {#2}
23812   { is~empty }
23813   { contains~the~tokens: #2 }
23814 }

```

23815 `</initex | package>`

40 l3regex implementation

23816 $\langle *initex \mid package \rangle$

23817 $\langle @@=regex \rangle$

40.1 Plan of attack

Most regex engines use backtracking. This allows to provide very powerful features (back-references come to mind first), but it is costly, and raises the problem of catastrophic backtracking. Since T_EX is not first and foremost a programming language, complicated code tends to run slowly, and we must use faster, albeit slightly more restrictive, techniques, coming from automata theory.

Given a regular expression of n characters, we do the following:

- (Compiling.) Analyse the regex, finding invalid input, and convert it to an internal representation.
- (Building.) Convert the compiled regex to a non-deterministic finite automaton (NFA) with $O(n)$ states which accepts precisely token lists matching that regex.
- (Matching.) Loop through the query token list one token (one “position”) at a time, exploring in parallel every possible path (“active thread”) through the NFA, considering active threads in an order determined by the quantifiers’ greediness.

We use the following vocabulary in the code comments (and in variable names).

- *Group*: index of the capturing group, -1 for non-capturing groups.
- *Position*: each token in the query is labelled by an integer $\langle position \rangle$, with $\text{min_pos} - 1 \leq \langle position \rangle \leq \text{max_pos}$. The lowest and highest positions correspond to imaginary begin and end markers (with inaccessible category code and character code).
- *Query*: the token list to which we apply the regular expression.
- *State*: each state of the NFA is labelled by an integer $\langle state \rangle$ with $\text{min_state} \leq \langle state \rangle < \text{max_state}$.
- *Active thread*: state of the NFA that is reached when reading the query token list for the matching. Those threads are ordered according to the greediness of quantifiers.
- *Step*: used when matching, starts at 0, incremented every time a character is read, and is not reset when searching for repeated matches. The integer $\backslash l_regex_step_int$ is a unique id for all the steps of the matching algorithm.

We use `l3intarray` to manipulate arrays of integers (stored into some dimension registers in scaled points). We also abuse T_EX’s `\toks` registers, by accessing them directly by number rather than tying them to control sequence using the `\newtoks` allocation functions. Specifically, these arrays and `\toks` are used as follows. When building, $\backslash toks \langle state \rangle$ holds the tests and actions to perform in the $\langle state \rangle$ of the NFA. When matching,

- $\backslash g_regex_state_active_intarray$ holds the last $\langle step \rangle$ in which each $\langle state \rangle$ was active.

- `\g__regex_thread_state_intarray` maps each $\langle thread \rangle$ (with `min_active` $\leq \langle thread \rangle < \text{max_active}$) to the $\langle state \rangle$ in which the $\langle thread \rangle$ currently is. The $\langle threads \rangle$ are ordered starting from the best to the least preferred.
- `\toks\langle thread \rangle` holds the submatch information for the $\langle thread \rangle$, as the contents of a property list.
- `\g__regex_charcode_intarray` and `\g__regex_catcode_intarray` hold the character codes and category codes of tokens at each $\langle position \rangle$ in the query.
- `\g__regex_balance_intarray` holds the balance of begin-group and end-group character tokens which appear before that point in the token list.
- `\toks\langle position \rangle` holds $\langle tokens \rangle$ which o- and x-expand to the $\langle position \rangle$ -th token in the query.
- `\g__regex_submatch_prev_intarray`, `\g__regex_submatch_begin_intarray` and `\g__regex_submatch_end_intarray` hold, for each submatch (as would be extracted by `\regex_extract_all:nnN`), the place where the submatch started to be looked for and its two end-points. For historical reasons, the minimum index is twice `max_state`, and the used registers go up to `\l__regex_submatch_int`. They are organized in blocks of `\l__regex_capturing_group_int` entries, each block corresponding to one match with all its submatches stored in consecutive entries.

The code is structured as follows. Variables are introduced in the relevant section. First we present some generic helper functions. Then comes the code for compiling a regular expression, and for showing the result of the compilation. The building phase converts a compiled regex to NFA states, and the automaton is run by the code in the following section. The only remaining brick is parsing the replacement text and performing the replacement. We are then ready for all the user functions. Finally, messages, and a little bit of tracing code.

40.2 Helpers

`__regex_int_eval:w` Access the primitive: performance is key here, so we do not use the slower route *via* `\int_eval:n`.

```

23818 \cs_new_eq:NN \__regex_int_eval:w \tex_numexpr:D
23819 %      \end{macrocode}
23820 % \end{macro}
23821 %
23822 % \begin{macro}{\__regex_standard_escapechar:}
23823 %   Make the \tn{escapechar} into the standard backslash.
23824 %   \begin{macrocode}
23825 \cs_new_protected:Npn \__regex_standard_escapechar:
23826   { \int_set:Nn \tex_escapechar:D { '\ } }
```

(End definition for `__regex_int_eval:w`.)

`__regex_toks_use:w` Unpack a `\toks` given its number.

```

23827 \cs_new:Npn \__regex_toks_use:w { \tex_the:D \tex_toks:D }
```

(End definition for `__regex_toks_use:w`.)

`__regex_toks_clear:N` Empty a `\toks` or set it to a value, given its number.
`__regex_toks_set:Nn` 23828 `\cs_new_protected:Npn __regex_toks_clear:N #1`
`__regex_toks_set:No` 23829 `{ __regex_toks_set:Nn #1 { } }`
23830 `\cs_new_eq:NN __regex_toks_set:Nn \tex_toks:D`
23831 `\cs_new_protected:Npn __regex_toks_set:No #1`
23832 `{ __regex_toks_set:Nn #1 \exp_after:wN }`

(End definition for `__regex_toks_clear:N` and `__regex_toks_set:Nn`.)

`__regex_toks_memcpy:NNn` Copy #3 `\toks` registers from #2 onwards to #1 onwards, like C's `memcpy`.

23833 `\cs_new_protected:Npn __regex_toks_memcpy:NNn #1#2#3`
23834 `{`
23835 `\prg_replicate:nn {#3}`
23836 `{`
23837 `\tex_toks:D #1 = \tex_toks:D #2`
23838 `\int_incr:N #1`
23839 `\int_incr:N #2`
23840 `}`
23841 `}`

(End definition for `__regex_toks_memcpy:NNn`.)

`__regex_toks_put_left:Nx` During the building phase we wish to add x-expanded material to `\toks`, either to the left
`__regex_toks_put_right:Nx` or to the right. The expansion is done “by hand” for optimization (these operations are
`__regex_toks_put_right:Nn` used quite a lot). The `Nn` version of `__regex_toks_put_right:Nx` is provided because
it is more efficient than x-expanding with `\exp_not:n`.

23842 `\cs_new_protected:Npn __regex_toks_put_left:Nx #1#2`
23843 `{`
23844 `\cs_set:Npx __regex_tmp:w { #2 }`
23845 `\tex_toks:D #1 \exp_after:wN \exp_after:wN \exp_after:wN`
23846 `{ \exp_after:wN __regex_tmp:w \tex_the:D \tex_toks:D #1 }`
23847 `}`
23848 `\cs_new_protected:Npn __regex_toks_put_right:Nx #1#2`
23849 `{`
23850 `\cs_set:Npx __regex_tmp:w {#2}`
23851 `\tex_toks:D #1 \exp_after:wN`
23852 `{ \tex_the:D \tex_toks:D \exp_after:wN #1 __regex_tmp:w }`
23853 `}`
23854 `\cs_new_protected:Npn __regex_toks_put_right:Nn #1#2`
23855 `{ \tex_toks:D #1 \exp_after:wN { \tex_the:D \tex_toks:D #1 #2 } }`

(End definition for `__regex_toks_put_left:Nx` and `__regex_toks_put_right:Nx`.)

`__regex_curr_cs_to_str:` Expands to the string representation of the token (known to be a control sequence) at
the current position `\l__regex_curr_pos_int`. It should only be used in x-expansion to
avoid losing a leading space.

23856 `\cs_new:Npn __regex_curr_cs_to_str:`
23857 `{`
23858 `\exp_after:wN \exp_after:wN \exp_after:wN \cs_to_str:N`
23859 `\tex_the:D \tex_toks:D \l__regex_curr_pos_int`
23860 `}`

(End definition for `__regex_curr_cs_to_str:.`)

40.2.1 Constants and variables

`__regex_tmp:w` Temporary function used for various short-term purposes.

```
23861 \cs_new:Npn \__regex_tmp:w { }
```

(End definition for __regex_tmp:w.)

`\l__regex_internal_a_tl` Temporary variables used for various purposes.

```
\l__regex_internal_b_tl 23862 \tl_new:N \l__regex_internal_a_tl
\l__regex_internal_a_int 23863 \tl_new:N \l__regex_internal_b_tl
\l__regex_internal_b_int 23864 \int_new:N \l__regex_internal_a_int
\l__regex_internal_c_int 23865 \int_new:N \l__regex_internal_b_int
\l__regex_internal_bool 23866 \int_new:N \l__regex_internal_c_int
\l__regex_internal_seq 23867 \bool_new:N \l__regex_internal_bool
\g__regex_internal_tl 23868 \seq_new:N \l__regex_internal_seq
23869 \tl_new:N \g__regex_internal_tl
```

(End definition for \l__regex_internal_a_tl and others.)

`\l__regex_build_tl` This temporary variable is specifically for use with the `tl_build` machinery.

```
23870 \tl_new:N \l__regex_build_tl
```

(End definition for \l__regex_build_tl.)

`\c__regex_no_match_regex` This regular expression matches nothing, but is still a valid regular expression. We could use a failing assertion, but I went for an empty class. It is used as the initial value for regular expressions declared using `\regex_new:N`.

```
23871 \tl_const:Nn \c__regex_no_match_regex
23872 {
23873   \__regex_branch:n
23874   { \__regex_class:NnnnN \c_true_bool { } { 1 } { 0 } \c_true_bool }
23875 }
```

(End definition for \c__regex_no_match_regex.)

`\g__regex_charcode_intarray` The first thing we do when matching is to go once through the query token list and store the information for each token into `\g__regex_charcode_intarray`, `\g__regex_catcode_intarray` and `\toks` registers. We also store the balance of begin-group/end-group characters into `\g__regex_balance_intarray`.

```
23876 \intarray_new:Nn \g__regex_charcode_intarray { 65536 }
23877 \intarray_new:Nn \g__regex_catcode_intarray { 65536 }
23878 \intarray_new:Nn \g__regex_balance_intarray { 65536 }
```

(End definition for \g__regex_charcode_intarray, \g__regex_catcode_intarray, and \g__regex_balance_intarray.)

`\l__regex_balance_int` During this phase, `\l__regex_balance_int` counts the balance of begin-group and end-group character tokens which appear before a given point in the token list. This variable is also used to keep track of the balance in the replacement text.

```
23879 \int_new:N \l__regex_balance_int
```

(End definition for \l__regex_balance_int.)

`\l__regex_cs_name_tl` This variable is used in `__regex_item_cs:n` to store the csname of the currently-tested token when the regex contains a sub-regex for testing csnames.

```
23880 \tl_new:N \l__regex_cs_name_tl
```

(End definition for \l__regex_cs_name_tl.)

40.2.2 Testing characters

```
\c__regex_ascii_min_int
    \c__regex_ascii_max_control_int 23881 \int_const:Nn \c__regex_ascii_min_int { 0 }
\c__regex_ascii_max_int             23882 \int_const:Nn \c__regex_ascii_max_control_int { 31 }
                                   23883 \int_const:Nn \c__regex_ascii_max_int { 127 }

(End definition for \c__regex_ascii_min_int, \c__regex_ascii_max_control_int, and \c__regex_
ascii_max_int.)
```

```
\c__regex_ascii_lower_int

23884 \int_const:Nn \c__regex_ascii_lower_int { ‘a - ‘A }

(End definition for \c__regex_ascii_lower_int.)
```

40.2.3 Internal auxiliaries

```
\q__regex_recursion_stop Internal recursion quarks.

23885 \quark_new:N \q__regex_recursion_stop

(End definition for \q__regex_recursion_stop.)
```

```
regex_use_none_delimit_by_q_recursion_stop:w Functions to gobble up to a quark.
__regex_use_i_delimit_by_q_recursion_stop:nw

23886 \cs_new:Npn \__regex_use_none_delimit_by_q_recursion_stop:w
23887     #1 \q__regex_recursion_stop { }
23888 \cs_new:Npn \__regex_use_i_delimit_by_q_recursion_stop:nw
23889     #1 #2 \q__regex_recursion_stop {#1}

(End definition for \__regex_use_none_delimit_by_q_recursion_stop:w and \__regex_use_i_delimit_
by_q_recursion_stop:nw.)
```

```
\q__regex_nil Internal quarks.

23890 \quark_new:N \q__regex_nil

(End definition for \q__regex_nil.)
```

```
\__regex_quark_if_nil_p:n Branching quark conditional.
\__regex_quark_if_nil:nTF

23891 \__kernel_quark_new_conditional:Nn \__regex_quark_if_nil:N { F }

(End definition for \__regex_quark_if_nil:nTF.)
```

```
\__regex_break_point:TF When testing whether a character of the query token list matches a given character class
    \__regex_break_true:w in the regular expression, we often have to test it against several ranges of characters,
checking if any one of those matches. This is done with a structure like
```

```

    <test1> ... <test_n>
    \__regex_break_point:TF {<true code>} {<false code>}
```

If any of the tests succeeds, it calls `__regex_break_true:w`, which cleans up and leaves `<true code>` in the input stream. Otherwise, `__regex_break_point:TF` leaves the `<false code>` in the input stream.

```
23892 \cs_new_protected:Npn \__regex_break_true:w
23893     #1 \__regex_break_point:TF #2 #3 {#2}
23894 \cs_new_protected:Npn \__regex_break_point:TF #1 #2 { #2 }

(End definition for \__regex_break_point:TF and \__regex_break_true:w.)
```


`__regex_item_reverse:n` This function makes showing regular expressions easier, and lets us define `\D` in terms of `\d` for instance. There is a subtlety: the end of the query is marked by `-2`, and thus matches `\D` and other negated properties; this case is caught by another part of the code.

```

23895 \cs_new_protected:Npn \__regex_item_reverse:n #1
23896 {
23897     #1
23898     \__regex_break_point:TF { } \__regex_break_true:w
23899 }

```

(End definition for __regex_item_reverse:n.)

`__regex_item_caseful_equal:n` Simple comparisons triggering `__regex_break_true:w` when true.

```

\__regex_item_caseful_range:nn
23900 \cs_new_protected:Npn \__regex_item_caseful_equal:n #1
23901 {
23902     \if_int_compare:w #1 = \l__regex_curr_char_int
23903     \exp_after:wN \__regex_break_true:w
23904     \fi:
23905 }
23906 \cs_new_protected:Npn \__regex_item_caseful_range:nn #1 #2
23907 {
23908     \reverse_if:N \if_int_compare:w #1 > \l__regex_curr_char_int
23909     \reverse_if:N \if_int_compare:w #2 < \l__regex_curr_char_int
23910     \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
23911     \fi:
23912     \fi:
23913 }

```

(End definition for __regex_item_caseful_equal:n and __regex_item_caseful_range:nn.)

`__regex_item_caseless_equal:n` For caseless matching, we perform the test both on the `current_char` and on the `case_`
`__regex_item_caseless_range:nn` `changed_char`. Before doing the second set of tests, we make sure that `case_changed_`
`char` has been computed.

```

23914 \cs_new_protected:Npn \__regex_item_caseless_equal:n #1
23915 {
23916     \if_int_compare:w #1 = \l__regex_curr_char_int
23917     \exp_after:wN \__regex_break_true:w
23918     \fi:
23919     \if_int_compare:w \l__regex_case_changed_char_int = \c_max_int
23920     \__regex_compute_case_changed_char:
23921     \fi:
23922     \if_int_compare:w #1 = \l__regex_case_changed_char_int
23923     \exp_after:wN \__regex_break_true:w
23924     \fi:
23925 }
23926 \cs_new_protected:Npn \__regex_item_caseless_range:nn #1 #2
23927 {
23928     \reverse_if:N \if_int_compare:w #1 > \l__regex_curr_char_int
23929     \reverse_if:N \if_int_compare:w #2 < \l__regex_curr_char_int
23930     \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
23931     \fi:
23932     \fi:
23933     \if_int_compare:w \l__regex_case_changed_char_int = \c_max_int
23934     \__regex_compute_case_changed_char:
23935     \fi:

```

```

23936 \reverse_if:N \if_int_compare:w #1 > \l__regex_case_changed_char_int
23937 \reverse_if:N \if_int_compare:w #2 < \l__regex_case_changed_char_int
23938 \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
23939 \fi:
23940 \fi:
23941 }

```

(End definition for __regex_item_caseless_equal:n and __regex_item_caseless_range:nn.)

__regex_compute_case_changed_char: This function is called when \l__regex_case_changed_char_int has not yet been computed (or rather, when it is set to the marker value \c_max_int). If the current character code is in the range [65,90] (upper-case), then add 32, making it lowercase. If it is in the lower-case letter range [97,122], subtract 32.

```

23942 \cs_new_protected:Npn \__regex_compute_case_changed_char:
23943 {
23944 \int_set_eq:NN \l__regex_case_changed_char_int \l__regex_curr_char_int
23945 \if_int_compare:w \l__regex_curr_char_int > 'Z \exp_stop_f:
23946 \if_int_compare:w \l__regex_curr_char_int > 'z \exp_stop_f: \else:
23947 \if_int_compare:w \l__regex_curr_char_int < 'a \exp_stop_f: \else:
23948 \int_sub:Nn \l__regex_case_changed_char_int
23949 { \c__regex_ascii_lower_int }
23950 \fi:
23951 \fi:
23952 \else:
23953 \if_int_compare:w \l__regex_curr_char_int < 'A \exp_stop_f: \else:
23954 \int_add:Nn \l__regex_case_changed_char_int
23955 { \c__regex_ascii_lower_int }
23956 \fi:
23957 \fi:
23958 }

```

(End definition for __regex_compute_case_changed_char:.)

__regex_item_equal:n Those must always be defined to expand to a **caseful** (default) or **caseless** version, and not be protected: they must expand when compiling, to hard-code which tests are caseless or caseful.

```

23959 \cs_new_eq:NN \__regex_item_equal:n ?
23960 \cs_new_eq:NN \__regex_item_range:nn ?

```

(End definition for __regex_item_equal:n and __regex_item_range:nn.)

__regex_item_catcode:nT The argument is a sum of powers of 4 with exponents given by the allowed category codes (between 0 and 13). Dividing by a given power of 4 gives an odd result if and only if that category code is allowed. If the catcode does not match, then skip the character code tests which follow.

```

23961 \cs_new_protected:Npn \__regex_item_catcode:
23962 {
23963 "
23964 \if_case:w \l__regex_curr_catcode_int
23965 1 \or: 4 \or: 10 \or: 40
23966 \or: 100 \or: \or: 1000 \or: 4000
23967 \or: 10000 \or: \or: 100000 \or: 400000
23968 \or: 1000000 \or: 4000000 \else: 1*0
23969 \fi:

```

```

23970 }
23971 \cs_new_protected:Npn \__regex_item_catcode:nT #1
23972 {
23973   \if_int_odd:w \int_eval:n { #1 / \__regex_item_catcode: } \exp_stop_f:
23974   \exp_after:wN \use:n
23975   \else:
23976   \exp_after:wN \use_none:n
23977   \fi:
23978 }
23979 \cs_new_protected:Npn \__regex_item_catcode_reverse:nT #1#2
23980 { \__regex_item_catcode:nT {#1} { \__regex_item_reverse:n {#2} } }

(End definition for \__regex_item_catcode:nT, \__regex_item_catcode_reverse:nT, and \__regex_
item_catcode:.)

```

`__regex_item_exact:nn` This matches an exact $\langle category \rangle$ - $\langle character code \rangle$ pair, or an exact control sequence, more precisely one of several possible control sequences.

```

23981 \cs_new_protected:Npn \__regex_item_exact:nn #1#2
23982 {
23983   \if_int_compare:w #1 = \l__regex_curr_catcode_int
23984   \if_int_compare:w #2 = \l__regex_curr_char_int
23985   \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
23986   \fi:
23987   \fi:
23988 }
23989 \cs_new_protected:Npn \__regex_item_exact_cs:n #1
23990 {
23991   \int_compare:nNnTF \l__regex_curr_catcode_int = 0
23992   {
23993     \tl_set:Nx \l__regex_internal_a_tl
23994     { \scan_stop: \__regex_curr_cs_to_str: \scan_stop: }
23995     \tl_if_in:noTF { \scan_stop: #1 \scan_stop: }
23996     \l__regex_internal_a_tl
23997     { \__regex_break_true:w } { }
23998   }
23999   { }
24000 }

```

(End definition for `__regex_item_exact:nn` and `__regex_item_exact_cs:n`.)

`__regex_item_cs:n` Match a control sequence (the argument is a compiled regex). First test the catcode of the current token to be zero. Then perform the matching test, and break if the csname indeed matches. The three `\exp_after:wN` expand the contents of the `\toks` $\langle current position \rangle$ (of the form `\exp_not:n { \langle control sequence \rangle }`) to $\langle control sequence \rangle$. We store the cs name before building states for the cs, as those states may overlap with `\toks` registers storing the user's input.

```

24001 \cs_new_protected:Npn \__regex_item_cs:n #1
24002 {
24003   \int_compare:nNnTF \l__regex_curr_catcode_int = 0
24004   {
24005     \group_begin:
24006     \tl_set:Nx \l__regex_cs_name_tl { \__regex_curr_cs_to_str: }
24007     \__regex_single_match:
24008     \__regex_disable_submatches:

```

```

24009         \__regex_build_for_cs:n {#1}
24010         \bool_set_eq:NN \l__regex_saved_success_bool
24011         \g__regex_success_bool
24012         \exp_args:NV \__regex_match_cs:n \l__regex_cs_name_tl
24013         \if_meaning:w \c_true_bool \g__regex_success_bool
24014         \group_insert_after:N \__regex_break_true:w
24015         \fi:
24016         \bool_gset_eq:NN \g__regex_success_bool
24017         \l__regex_saved_success_bool
24018     \group_end:
24019 }
24020 }

```

(End definition for __regex_item_cs:n.)

40.2.4 Character property tests

__regex_prop_d: Character property tests for \d, \W, etc. These character properties are not affected by the (?i) option. The characters recognized by each one are as follows: \d=[0-9], __regex_prop_h: \w=[0-9A-Z_a-z], \s=[_\^\^I\^\^J\^\^L\^\^M], \h=[_\^\^I], \v=[\^\^J-\^\^M], and the upper case counterparts match anything that the lower case does not match. The order in which the various tests appear is optimized for usual mostly lower case letter text.

```

\__regex_prop_v:
\__regex_prop_w:
\__regex_prop_N:
24021 \cs_new_protected:Npn \__regex_prop_d:
24022 { \__regex_item_caseful_range:nn { '0 } { '9 } }
24023 \cs_new_protected:Npn \__regex_prop_h:
24024 {
24025     \__regex_item_caseful_equal:n { '\ }
24026     \__regex_item_caseful_equal:n { '\^\^I }
24027 }
24028 \cs_new_protected:Npn \__regex_prop_s:
24029 {
24030     \__regex_item_caseful_equal:n { '\ }
24031     \__regex_item_caseful_equal:n { '\^\^I }
24032     \__regex_item_caseful_equal:n { '\^\^J }
24033     \__regex_item_caseful_equal:n { '\^\^L }
24034     \__regex_item_caseful_equal:n { '\^\^M }
24035 }
24036 \cs_new_protected:Npn \__regex_prop_v:
24037 { \__regex_item_caseful_range:nn { '\^\^J } { '\^\^M } } % lf, vtab, ff, cr
24038 \cs_new_protected:Npn \__regex_prop_w:
24039 {
24040     \__regex_item_caseful_range:nn { 'a } { 'z }
24041     \__regex_item_caseful_range:nn { 'A } { 'Z }
24042     \__regex_item_caseful_range:nn { '0 } { '9 }
24043     \__regex_item_caseful_equal:n { '_' }
24044 }
24045 \cs_new_protected:Npn \__regex_prop_N:
24046 {
24047     \__regex_item_reverse:n
24048     { \__regex_item_caseful_equal:n { '\^\^J } }
24049 }

```

(End definition for __regex_prop_d: and others.)

```

__regex_posix_alnum: POSIX properties. No surprise.
__regex_posix_alpha: 24050 \cs_new_protected:Npn \__regex_posix_alnum:
__regex_posix_ascii: 24051 { \__regex_posix_alpha: \__regex_posix_digit: }
__regex_posix_blank: 24052 \cs_new_protected:Npn \__regex_posix_alpha:
__regex_posix_cntrl: 24053 { \__regex_posix_lower: \__regex_posix_upper: }
__regex_posix_digit: 24054 \cs_new_protected:Npn \__regex_posix_ascii:
__regex_posix_graph: 24055 {
__regex_posix_lower: 24056   \__regex_item_caseful_range:nn
__regex_posix_print: 24057   \c__regex_ascii_min_int
__regex_posix_punct: 24058   \c__regex_ascii_max_int
__regex_posix_space: 24059 }
__regex_posix_upper: 24060 \cs_new_eq:NN \__regex_posix_blank: \__regex_prop_h:
__regex_posix_word: 24061 \cs_new_protected:Npn \__regex_posix_cntrl:
__regex_posix_xdigit: 24062 {
24063   \__regex_item_caseful_range:nn
24064   \c__regex_ascii_min_int
24065   \c__regex_ascii_max_control_int
24066   \__regex_item_caseful_equal:n \c__regex_ascii_max_int
24067 }
24068 \cs_new_eq:NN \__regex_posix_digit: \__regex_prop_d:
24069 \cs_new_protected:Npn \__regex_posix_graph:
24070 { \__regex_item_caseful_range:nn { '!' } { '\~ } }
24071 \cs_new_protected:Npn \__regex_posix_lower:
24072 { \__regex_item_caseful_range:nn { 'a' } { 'z' } }
24073 \cs_new_protected:Npn \__regex_posix_print:
24074 { \__regex_item_caseful_range:nn { '\ ' } { '\~ } }
24075 \cs_new_protected:Npn \__regex_posix_punct:
24076 {
24077   \__regex_item_caseful_range:nn { '!' } { '/' }
24078   \__regex_item_caseful_range:nn { ':' } { '@' }
24079   \__regex_item_caseful_range:nn { '[' } { '"' }
24080   \__regex_item_caseful_range:nn { '\{ ' } { '\~ }
24081 }
24082 \cs_new_protected:Npn \__regex_posix_space:
24083 {
24084   \__regex_item_caseful_equal:n { '\ ' }
24085   \__regex_item_caseful_range:nn { '\^^I } { '\^^M }
24086 }
24087 \cs_new_protected:Npn \__regex_posix_upper:
24088 { \__regex_item_caseful_range:nn { 'A' } { 'Z' } }
24089 \cs_new_eq:NN \__regex_posix_word: \__regex_prop_w:
24090 \cs_new_protected:Npn \__regex_posix_xdigit:
24091 {
24092   \__regex_posix_digit:
24093   \__regex_item_caseful_range:nn { 'A' } { 'F' }
24094   \__regex_item_caseful_range:nn { 'a' } { 'f' }
24095 }

```

(End definition for `__regex_posix_alnum:` and others.)

40.2.5 Simple character escape

Before actually parsing the regular expression or the replacement text, we go through them once, converting `\n` to the character 10, *etc.* In this pass, we also convert any special

character (*, ?, {, etc.) or escaped alphanumeric character into a marker indicating that this was a special sequence, and replace escaped special characters and non-escaped alphanumeric characters by markers indicating that those were “raw” characters. The rest of the code can then avoid caring about escaping issues (those can become quite complex to handle in combination with ranges in character classes).

Usage: `__regex_escape_use:nnnn` *<inline 1>* *<inline 2>* *<inline 3>* *{<token list>}*
The *<token list>* is converted to a string, then read from left to right, interpreting backslashes as escaping the next character. Unescaped characters are fed to the function *<inline 1>*, and escaped characters are fed to the function *<inline 2>* within an *x*-expansion context (typically those functions perform some tests on their argument to decide how to output them). The escape sequences `\a`, `\e`, `\f`, `\n`, `\r`, `\t` and `\x` are recognized, and those are replaced by the corresponding character, then fed to *<inline 3>*. The result is then left in the input stream. Spaces are ignored unless escaped.

The conversion is done within an *x*-expanding assignment.

`__regex_escape_use:nnnn` The result is built in `\l__regex_internal_a_tl`, which is then left in the input stream. Tracing code is added as appropriate inside this token list. Go through #4 once, applying #1, #2, or #3 as relevant to each character (after de-escaping it).

```

24096 \cs_new_protected:Npn \__regex_escape_use:nnnn #1#2#3#4
24097 {
24098   \group_begin:
24099     \tl_clear:N \l__regex_internal_a_tl
24100     \cs_set:Npn \__regex_escape_unescaped:N ##1 { #1 }
24101     \cs_set:Npn \__regex_escape_escaped:N ##1 { #2 }
24102     \cs_set:Npn \__regex_escape_raw:N ##1 { #3 }
24103     \__regex_standard_escapechar:
24104     \tl_gset:Nx \g__regex_internal_tl
24105       { \__kernel_str_to_other_fast:n {#4} }
24106     \tl_put_right:Nx \l__regex_internal_a_tl
24107       {
24108         \exp_after:wN \__regex_escape_loop:N \g__regex_internal_tl
24109         { break } \prg_break_point:
24110       }
24111     \exp_after:wN
24112   \group_end:
24113   \l__regex_internal_a_tl
24114 }

```

(End definition for `__regex_escape_use:nnnn`.)

`__regex_escape_loop:N` `__regex_escape_loop:N` reads one character: if it is special (space, backslash, or end-marker), perform the associated action, otherwise it is simply an unescaped character. After a backslash, the same is done, but unknown characters are “escaped”.

```

24115 \cs_new:Npn \__regex_escape_loop:N #1
24116 {
24117   \cs_if_exist_use:cF { __regex_escape\_token_to_str:N #1:w }
24118     { \__regex_escape_unescaped:N #1 }
24119   \__regex_escape_loop:N
24120 }
24121 \cs_new:cpn { __regex_escape\_c_backslash_str :w }
24122   \__regex_escape_loop:N #1
24123 {
24124   \cs_if_exist_use:cF { __regex_escape\_token_to_str:N #1:w }

```

```

24125         { \__regex_escape_escaped:N #1 }
24126     \__regex_escape_loop:N
24127 }

```

(End definition for __regex_escape_loop:N and __regex_escape_w.)

__regex_escape_unescaped:N Those functions are never called before being given a new meaning, so their definitions here don't matter.

```

\__regex_escape_escaped:N
\__regex_escape_raw:N
24128 \cs_new_eq:NN \__regex_escape_unescaped:N ?
24129 \cs_new_eq:NN \__regex_escape_escaped:N ?
24130 \cs_new_eq:NN \__regex_escape_raw:N ?

```

(End definition for __regex_escape_unescaped:N, __regex_escape_escaped:N, and __regex_escape_raw:N.)

__regex_escape_break:w The loop is ended upon seeing the end-marker “break”, with an error if the string ended in a backslash. Spaces are ignored, and \a, \e, \f, \n, \r, \t take their meaning here.

```

\__regex_escape_/break:w
\__regex_escape_/a:w
\__regex_escape_/e:w
\__regex_escape_/f:w
\__regex_escape_/n:w
\__regex_escape_/r:w
\__regex_escape_/t:w
\__regex_escape_\w:w
24131 \cs_new_eq:NN \__regex_escape_break:w \prg_break:
24132 \cs_new:cpn { \__regex_escape_/break:w }
24133 {
24134     \__kernel_msg_expandable_error:nn { kernel } { trailing-backslash }
24135     \prg_break:
24136 }
24137 \cs_new:cpn { \__regex_escape_\w:w } { }
24138 \cs_new:cpx { \__regex_escape_/a:w }
24139 { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^G }
24140 \cs_new:cpx { \__regex_escape_/t:w }
24141 { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^I }
24142 \cs_new:cpx { \__regex_escape_/n:w }
24143 { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^J }
24144 \cs_new:cpx { \__regex_escape_/f:w }
24145 { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^L }
24146 \cs_new:cpx { \__regex_escape_/r:w }
24147 { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^M }
24148 \cs_new:cpx { \__regex_escape_/e:w }
24149 { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^[ }

```

(End definition for __regex_escape_break:w and others.)

__regex_escape_/x:w When \x is encountered, __regex_escape_x_test:N is responsible for grabbing some hexadecimal digits, and feeding the result to __regex_escape_x_end:w. If the number is too big interrupt the assignment and produce an error, otherwise call __regex_escape_raw:N on the corresponding character token.

```

24150 \cs_new:cpn { \__regex_escape_/x:w } \__regex_escape_loop:N
24151 {
24152     \exp_after:wN \__regex_escape_x_end:w
24153     \int_value:w "0 \__regex_escape_x_test:N
24154 }
24155 \cs_new:Npn \__regex_escape_x_end:w #1 ;
24156 {
24157     \int_compare:nNnTF {#1} > \c_max_char_int
24158     {
24159         \__kernel_msg_expandable_error:nnff { kernel } { x-overflow }
24160         {#1} { \int_to_Hex:n {#1} }

```

```

24161     }
24162     {
24163         \exp_last_unbraced:Nf \__regex_escape_raw:N
24164         { \char_generate:nn {#1} { 12 } }
24165     }
24166 }

```

(End definition for __regex_escape_/x:w, __regex_escape_x_end:w, and __regex_escape_x_large:n.)

__regex_escape_x_test:N Find out whether the first character is a left brace (allowing any number of hexadecimal digits), or not (allowing up to two hexadecimal digits). We need to check for the end-of-string marker. Eventually, call either __regex_escape_x_loop:N or __regex_escape_x:N.

```

24167 \cs_new:Npn \__regex_escape_x_test:N #1
24168 {
24169     \str_if_eq:nnTF {#1} { break } { ; }
24170     {
24171         \if_charcode:w \c_space_token #1
24172         \exp_after:wN \__regex_escape_x_test:N
24173         \else:
24174         \exp_after:wN \__regex_escape_x_testii:N
24175         \exp_after:wN #1
24176         \fi:
24177     }
24178 }
24179 \cs_new:Npn \__regex_escape_x_testii:N #1
24180 {
24181     \if_charcode:w \c_left_brace_str #1
24182     \exp_after:wN \__regex_escape_x_loop:N
24183     \else:
24184     \__regex_hexadecimal_use:NTF #1
24185     { \exp_after:wN \__regex_escape_x:N }
24186     { ; \exp_after:wN \__regex_escape_loop:N \exp_after:wN #1 }
24187     \fi:
24188 }

```

(End definition for __regex_escape_x_test:N and __regex_escape_x_testii:N.)

__regex_escape_x:N This looks for the second digit in the unbraced case.

```

24189 \cs_new:Npn \__regex_escape_x:N #1
24190 {
24191     \str_if_eq:nnTF {#1} { break } { ; }
24192     {
24193         \__regex_hexadecimal_use:NTF #1
24194         { ; \__regex_escape_loop:N }
24195         { ; \__regex_escape_loop:N #1 }
24196     }
24197 }

```

(End definition for __regex_escape_x:N.)

__regex_escape_x_loop:N Grab hexadecimal digits, skip spaces, and at the end, check that there is a right brace, otherwise raise an error outside the assignment.

```

24198 \cs_new:Npn \__regex_escape_x_loop:N #1

```



```

24199 {
24200   \str_if_eq:nnTF {#1} { break }
24201   { ; \__regex_escape_x_loop_error:n { } {#1} }
24202   {
24203     \__regex_hexadecimal_use:NTF #1
24204     { \__regex_escape_x_loop:N }
24205     {
24206       \token_if_eq_charcode:NNTF \c_space_token #1
24207       { \__regex_escape_x_loop:N }
24208       {
24209         ;
24210         \exp_after:wN
24211         \token_if_eq_charcode:NNTF \c_right_brace_str #1
24212         { \__regex_escape_loop:N }
24213         { \__regex_escape_x_loop_error:n {#1} }
24214       }
24215     }
24216   }
24217 }
24218 \cs_new:Npn \__regex_escape_x_loop_error:n #1
24219 {
24220   \__kernel_msg_expandable_error:nnn { kernel } { x-missing-rbrace } {#1}
24221   \__regex_escape_loop:N #1
24222 }

```

(End definition for __regex_escape_x_loop:N and __regex_escape_x_loop_error:.)

__regex_hexadecimal_use:NTF T_EX detects uppercase hexadecimal digits for us but not the lowercase letters, which we need to detect and replace by their uppercase counterpart.

```

24223 \prg_new_conditional:Npnn \__regex_hexadecimal_use:N #1 { TF }
24224 {
24225   \if_int_compare:w 1 < "1 \token_to_str:N #1 \exp_stop_f:
24226   #1 \prg_return_true:
24227   \else:
24228     \if_case:w
24229     \int_eval:n { \exp_after:wN ‘ \token_to_str:N #1 - ‘a }
24230     A
24231     \or: B
24232     \or: C
24233     \or: D
24234     \or: E
24235     \or: F
24236     \else:
24237       \prg_return_false:
24238       \exp_after:wN \use_none:n
24239     \fi:
24240     \prg_return_true:
24241   \fi:
24242 }

```

(End definition for __regex_hexadecimal_use:NTF.)

__regex_char_if_alphanumeric:NTF These two tests are used in the first pass when parsing a regular expression. That pass is responsible for finding escaped and non-escaped characters, and recognizing which ones have special meanings and which should be interpreted as “raw” characters. Namely,

- alphanumerics are “raw” if they are not escaped, and may have a special meaning when escaped;
- non-alphanumeric printable ascii characters are “raw” if they are escaped, and may have a special meaning when not escaped;
- characters other than printable ascii are always “raw”.

The code is ugly, and highly based on magic numbers and the ascii codes of characters. This is mostly unavoidable for performance reasons. Maybe the tests can be optimized a little bit more. Here, “alphanumeric” means 0–9, A–Z, a–z; “special” character means non-alphanumeric but printable ascii, from space (hex 20) to del (hex 7E).

```

24243 \prg_new_conditional:Npnn \__regex_char_if_special:N #1 { TF }
24244 {
24245   \if_int_compare:w '#1 > 'Z \exp_stop_f:
24246   \if_int_compare:w '#1 > 'z \exp_stop_f:
24247   \if_int_compare:w '#1 < \c__regex_ascii_max_int
24248   \prg_return_true: \else: \prg_return_false: \fi:
24249   \else:
24250   \if_int_compare:w '#1 < 'a \exp_stop_f:
24251   \prg_return_true: \else: \prg_return_false: \fi:
24252   \fi:
24253   \else:
24254   \if_int_compare:w '#1 > '9 \exp_stop_f:
24255   \if_int_compare:w '#1 < 'A \exp_stop_f:
24256   \prg_return_true: \else: \prg_return_false: \fi:
24257   \else:
24258   \if_int_compare:w '#1 < '0 \exp_stop_f:
24259   \if_int_compare:w '#1 < '\' \exp_stop_f:
24260   \prg_return_false: \else: \prg_return_true: \fi:
24261   \else: \prg_return_false: \fi:
24262   \fi:
24263   \fi:
24264 }
24265 \prg_new_conditional:Npnn \__regex_char_if_alphanumeric:N #1 { TF }
24266 {
24267   \if_int_compare:w '#1 > 'Z \exp_stop_f:
24268   \if_int_compare:w '#1 > 'z \exp_stop_f:
24269   \prg_return_false:
24270   \else:
24271   \if_int_compare:w '#1 < 'a \exp_stop_f:
24272   \prg_return_false: \else: \prg_return_true: \fi:
24273   \fi:
24274   \else:
24275   \if_int_compare:w '#1 > '9 \exp_stop_f:
24276   \if_int_compare:w '#1 < 'A \exp_stop_f:
24277   \prg_return_false: \else: \prg_return_true: \fi:
24278   \else:
24279   \if_int_compare:w '#1 < '0 \exp_stop_f:
24280   \prg_return_false: \else: \prg_return_true: \fi:
24281   \fi:
24282   \fi:
24283 }

```

(End definition for __regex_char_if_alphanumeric:N and __regex_char_if_special:N.)

40.3 Compiling

A regular expression starts its life as a string of characters. In this section, we convert it to internal instructions, resulting in a “compiled” regular expression. This compiled expression is then turned into states of an automaton in the building phase. Compiled regular expressions consist of the following:

- `__regex_class:NnnnN` $\langle \text{boolean} \rangle \{ \langle \text{tests} \rangle \} \{ \langle \text{min} \rangle \} \{ \langle \text{more} \rangle \} \langle \text{lazyness} \rangle$
- `__regex_group:nnnN` $\{ \langle \text{branches} \rangle \} \{ \langle \text{min} \rangle \} \{ \langle \text{more} \rangle \} \langle \text{lazyness} \rangle$, also `__regex_group_no_capture:nnnN` and `__regex_group_resetting:nnnN` with the same syntax.
- `__regex_branch:n` $\{ \langle \text{contents} \rangle \}$
- `__regex_command_K:`
- `__regex_assertion:Nn` $\langle \text{boolean} \rangle \{ \langle \text{assertion test} \rangle \}$, where the $\langle \text{assertion test} \rangle$ is `__regex_b_test:` or $\{ \text{__regex_anchor:N} \langle \text{integer} \rangle \}$

Tests can be the following:

- `__regex_item_caseful_equal:n` $\{ \langle \text{char code} \rangle \}$
- `__regex_item_caseless_equal:n` $\{ \langle \text{char code} \rangle \}$
- `__regex_item_caseful_range:nn` $\{ \langle \text{min} \rangle \} \{ \langle \text{max} \rangle \}$
- `__regex_item_caseless_range:nn` $\{ \langle \text{min} \rangle \} \{ \langle \text{max} \rangle \}$
- `__regex_item_catcode:nT` $\{ \langle \text{catcode bitmap} \rangle \} \{ \langle \text{tests} \rangle \}$
- `__regex_item_catcode_reverse:nT` $\{ \langle \text{catcode bitmap} \rangle \} \{ \langle \text{tests} \rangle \}$
- `__regex_item_reverse:n` $\{ \langle \text{tests} \rangle \}$
- `__regex_item_exact:nn` $\{ \langle \text{catcode} \rangle \} \{ \langle \text{char code} \rangle \}$
- `__regex_item_exact_cs:n` $\{ \langle \text{csnames} \rangle \}$, more precisely given as $\langle \text{cname} \rangle \text{\scan_stop:} \langle \text{cname} \rangle \text{\scan_stop:} \langle \text{cname} \rangle$ and so on in a brace group.
- `__regex_item_cs:n` $\{ \langle \text{compiled regex} \rangle \}$

40.3.1 Variables used when compiling

`\l__regex_group_level_int`

We make sure to open the same number of groups as we close.

24284 `\int_new:N \l__regex_group_level_int`

(End definition for `\l__regex_group_level_int`.)

`\l__regex_mode_int`

While compiling, ten modes are recognized, labelled $-63, -23, -6, -2, 0, 2, 3, 6, 23, 63$.

`\c__regex_cs_in_class_mode_int`

See section 40.3.3. We only define some of these as constants.

`\c__regex_cs_mode_int`

24285 `\int_new:N \l__regex_mode_int`

`\c__regex_outer_mode_int`

24286 `\int_const:Nn \c__regex_cs_in_class_mode_int { -6 }`

`\c__regex_catcode_mode_int`

24287 `\int_const:Nn \c__regex_cs_mode_int { -2 }`

`\c__regex_class_mode_int`

24288 `\int_const:Nn \c__regex_outer_mode_int { 0 }`

`\c__regex_catcode_in_class_mode_int`

24289 `\int_const:Nn \c__regex_catcode_mode_int { 2 }`

24290 `\int_const:Nn \c__regex_class_mode_int { 3 }`

24291 `\int_const:Nn \c__regex_catcode_in_class_mode_int { 6 }`

(End definition for `\l__regex_mode_int` and others.)

`\l__regex_catcodes_int` We wish to allow constructions such as `\c[^BE](. . \cL[a-z] . .)`, where the outer catcode test applies to the whole group, but is superseded by the inner catcode test. For this to work, we need to keep track of lists of allowed category codes: `\l__regex_catcodes_int` and `\l__regex_default_catcodes_int` are bitmaps, sums of 4^c , for all allowed catcodes c . The latter is local to each capturing group, and we reset `\l__regex_catcodes_int` to that value after each character or class, changing it only when encountering a `\c` escape. The boolean records whether the list of categories of a catcode test has to be inverted: compare `\c[^BE]` and `\c[BE]`.

```
24292 \int_new:N \l__regex_catcodes_int
24293 \int_new:N \l__regex_default_catcodes_int
24294 \bool_new:N \l__regex_catcodes_bool
```

(End definition for `\l__regex_catcodes_int`, `\l__regex_default_catcodes_int`, and `\l__regex_catcodes_bool`.)

`\c__regex_catcode_C_int` Constants: 4^c for each category, and the sum of all powers of 4.

```

\c__regex_catcode_B_int
\c__regex_catcode_E_int
\c__regex_catcode_M_int
\c__regex_catcode_T_int
\c__regex_catcode_P_int
\c__regex_catcode_U_int
\c__regex_catcode_D_int
\c__regex_catcode_S_int
\c__regex_catcode_L_int
\c__regex_catcode_O_int
\c__regex_catcode_A_int
\c__regex_all_catcodes_int
```

```

24295 \int_const:Nn \c__regex_catcode_C_int { "1 }
24296 \int_const:Nn \c__regex_catcode_B_int { "4 }
24297 \int_const:Nn \c__regex_catcode_E_int { "10 }
24298 \int_const:Nn \c__regex_catcode_M_int { "40 }
24299 \int_const:Nn \c__regex_catcode_T_int { "100 }
24300 \int_const:Nn \c__regex_catcode_P_int { "1000 }
24301 \int_const:Nn \c__regex_catcode_U_int { "4000 }
24302 \int_const:Nn \c__regex_catcode_D_int { "10000 }
24303 \int_const:Nn \c__regex_catcode_S_int { "100000 }
24304 \int_const:Nn \c__regex_catcode_L_int { "400000 }
24305 \int_const:Nn \c__regex_catcode_O_int { "1000000 }
24306 \int_const:Nn \c__regex_catcode_A_int { "4000000 }
24307 \int_const:Nn \c__regex_all_catcodes_int { "5515155 }
```

(End definition for `\c__regex_catcode_C_int` and others.)

`\l__regex_internal_regex` The compilation step stores its result in this variable.

```
24308 \cs_new_eq:NN \l__regex_internal_regex \c__regex_no_match_regex
```

(End definition for `\l__regex_internal_regex`.)

`\l__regex_show_prefix_seq` This sequence holds the prefix that makes up the line displayed to the user. The various items must be removed from the right, which is tricky with a token list, hence we use a sequence.

```
24309 \seq_new:N \l__regex_show_prefix_seq
```

(End definition for `\l__regex_show_prefix_seq`.)

`\l__regex_show_lines_int` A hack. To know whether a given class has a single item in it or not, we count the number of lines when showing the class.

```
24310 \int_new:N \l__regex_show_lines_int
```

(End definition for `\l__regex_show_lines_int`.)

40.3.2 Generic helpers used when compiling

`_regex_two_if_eq:NNNTF` Used to compare pairs of things like `_regex_compile_special:N ?` together. It's often inconvenient to get the catcodes of the character to match so we just compare the character code. Besides, the expanding behaviour of `\\if:w` is very useful as that means we can use `\\c_left_brace_str` and the like.

```

24311 \\prg_new_conditional:Npnn \\_regex_two_if_eq:NNNN #1#2#3#4 { TF }
24312 {
24313     \\if_meaning:w #1 #3
24314     \\if:w #2 #4
24315     \\prg_return_true:
24316     \\else:
24317     \\prg_return_false:
24318     \\fi:
24319     \\else:
24320     \\prg_return_false:
24321     \\fi:
24322 }
```

(End definition for _regex_two_if_eq:NNNTF.)

`_regex_get_digits:NTFw` If followed by some raw digits, collect them one by one in the integer variable `#1`, and
`_regex_get_digits_loop:w` take the true branch. Otherwise, take the false branch.

```

24323 \\cs_new_protected:Npn \\_regex_get_digits:NTFw #1#2#3#4#5
24324 {
24325     \\_regex_if_raw_digit:NNTF #4 #5
24326     { #1 = #5 \\_regex_get_digits_loop:nw {#2} }
24327     { #3 #4 #5 }
24328 }
24329 \\cs_new:Npn \\_regex_get_digits_loop:nw #1#2#3
24330 {
24331     \\_regex_if_raw_digit:NNTF #2 #3
24332     { #3 \\_regex_get_digits_loop:nw {#1} }
24333     { \\scan_stop: #1 #2 #3 }
24334 }
```

(End definition for _regex_get_digits:NTFw and _regex_get_digits_loop:w.)

`_regex_if_raw_digit:NNTF` Test used when grabbing digits for the `{m,n}` quantifier. It only accepts non-escaped digits.

```

24335 \\prg_new_conditional:Npnn \\_regex_if_raw_digit:NN #1#2 { TF }
24336 {
24337     \\if_meaning:w \\_regex_compile_raw:N #1
24338     \\if_int_compare:w 1 < 1 #2 \\exp_stop_f:
24339     \\prg_return_true:
24340     \\else:
24341     \\prg_return_false:
24342     \\fi:
24343     \\else:
24344     \\prg_return_false:
24345     \\fi:
24346 }
```

(End definition for _regex_if_raw_digit:NNTF.)

40.3.3 Mode

When compiling the NFA corresponding to a given regex string, we can be in ten distinct modes, which we label by some magic numbers:

- 6 `[\c{...}]` control sequence in a class,
- 2 `\c{...}` control sequence,
- 0 ... outer,
- 2 `\c...` catcode test,
- 6 `[\c...]` catcode test in a class,
- 63 `[\c{[...]}]` class inside mode -6,
- 23 `\c{[...]}` class inside mode -2,
- 3 `[...]` class inside mode 0,
- 23 `\c[...]` class inside mode 2,
- 63 `[\c[...]]` class inside mode 6.

This list is exhaustive, because `\c` escape sequences cannot be nested, and character classes cannot be nested directly. The choice of numbers is such as to optimize the most useful tests, and make transitions from one mode to another as simple as possible.

- Even modes mean that we are not directly in a character class. In this case, a left bracket appends 3 to the mode. In a character class, a right bracket changes the mode as $m \rightarrow (m - 15)/13$, truncated.
- Grouping, assertion, and anchors are allowed in non-positive even modes (0, -2, -6), and do not change the mode. Otherwise, they trigger an error.
- A left bracket is special in even modes, appending 3 to the mode; in those modes, quantifiers and the dot are recognized, and the right bracket is normal. In odd modes (within classes), the left bracket is normal, but the right bracket ends the class, changing the mode from m to $(m - 15)/13$, truncated; also, ranges are recognized.
- In non-negative modes, left and right braces are normal. In negative modes, however, left braces trigger a warning; right braces end the control sequence, going from -2 to 0 or -6 to 3, with error recovery for odd modes.
- Properties (such as the `\d` character class) can appear in any mode.

`__regex_if_in_class:TF` Test whether we are directly in a character class (at the innermost level of nesting). There, many escape sequences are not recognized, and special characters are normal. Also, for every raw character, we must look ahead for a possible raw dash.

```
24347 \cs_new:Npn \__regex_if_in_class:TF
24348 {
24349   \if_int_odd:w \l__regex_mode_int
24350     \exp_after:wN \use_i:nn
24351   \else:
24352     \exp_after:wN \use_ii:nn
24353   \fi:
24354 }
```

(End definition for `_regex_if_in_class:TF`.)

`_regex_if_in_cs:TF` Right braces are special only directly inside control sequences (at the inner-most level of nesting, not counting groups).

```

24355 \cs_new:Npn \_regex_if_in_cs:TF
24356 {
24357   \if_int_odd:w \l__regex_mode_int
24358     \exp_after:wN \use_ii:nn
24359   \else:
24360     \if_int_compare:w \l__regex_mode_int < \c__regex_outer_mode_int
24361       \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
24362     \else:
24363       \exp_after:wN \exp_after:wN \exp_after:wN \use_ii:nn
24364     \fi:
24365   \fi:
24366 }
```

(End definition for `_regex_if_in_cs:TF`.)

`_regex_if_in_class_or_catcode:TF` Assertions are only allowed in modes 0, -2, and -6, *i.e.*, even, non-positive modes.

```

24367 \cs_new:Npn \_regex_if_in_class_or_catcode:TF
24368 {
24369   \if_int_odd:w \l__regex_mode_int
24370     \exp_after:wN \use_i:nn
24371   \else:
24372     \if_int_compare:w \l__regex_mode_int > \c__regex_outer_mode_int
24373       \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
24374     \else:
24375       \exp_after:wN \exp_after:wN \exp_after:wN \use_ii:nn
24376     \fi:
24377   \fi:
24378 }
```

(End definition for `_regex_if_in_class_or_catcode:TF`.)

`_regex_if_within_catcode:TF` This test takes the true branch if we are in a catcode test, either immediately following it (modes 2 and 6) or in a class on which it applies (modes 23 and 63). This is used to tweak how left brackets behave in modes 2 and 6.

```

24379 \cs_new:Npn \_regex_if_within_catcode:TF
24380 {
24381   \if_int_compare:w \l__regex_mode_int > \c__regex_outer_mode_int
24382     \exp_after:wN \use_i:nn
24383   \else:
24384     \exp_after:wN \use_ii:nn
24385   \fi:
24386 }
```

(End definition for `_regex_if_within_catcode:TF`.)

`_regex_chk_c_allowed:T` The `\c` escape sequence is only allowed in modes 0 and 3, *i.e.*, not within any other `\c` escape sequence.

```

24387 \cs_new_protected:Npn \_regex_chk_c_allowed:T
24388 {
24389   \if_int_compare:w \l__regex_mode_int = \c__regex_outer_mode_int
```

```

24390     \exp_after:wN \use:n
24391 \else:
24392   \if_int_compare:w \l__regex_mode_int = \c__regex_class_mode_int
24393     \exp_after:wN \exp_after:wN \exp_after:wN \use:n
24394   \else:
24395     \__kernel_msg_error:nn { kernel } { c-bad-mode }
24396     \exp_after:wN \exp_after:wN \exp_after:wN \use_none:n
24397   \fi:
24398 \fi:
24399 }

```

(End definition for __regex_chk_c_allowed:T.)

__regex_mode_quit_c: This function changes the mode as it is needed just after a catcode test.

```

24400 \cs_new_protected:Npn \__regex_mode_quit_c:
24401 {
24402   \if_int_compare:w \l__regex_mode_int = \c__regex_catcode_mode_int
24403     \int_set_eq:NN \l__regex_mode_int \c__regex_outer_mode_int
24404   \else:
24405     \if_int_compare:w \l__regex_mode_int =
24406       \c__regex_catcode_in_class_mode_int
24407     \int_set_eq:NN \l__regex_mode_int \c__regex_class_mode_int
24408   \fi:
24409 \fi:
24410 }

```

(End definition for __regex_mode_quit_c:.)

40.3.4 Framework

__regex_compile:w Used when compiling a user regex or a regex for the \c{...} escape sequence within another regex. Start building a token list within a group (with x-expansion at the outset), and set a few variables (group level, catcodes), then start the first branch. At the end, make sure there are no dangling classes nor groups, close the last branch: we are done building \l__regex_internal_regex.

```

24411 \cs_new_protected:Npn \__regex_compile:w
24412 {
24413   \group_begin:
24414     \tl_build_begin:N \l__regex_build_tl
24415     \int_zero:N \l__regex_group_level_int
24416     \int_set_eq:NN \l__regex_default_catcodes_int
24417       \c__regex_all_catcodes_int
24418     \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
24419     \cs_set:Npn \__regex_item_equal:n { \__regex_item_caseful_equal:n }
24420     \cs_set:Npn \__regex_item_range:nn { \__regex_item_caseful_range:nn }
24421     \tl_build_put_right:Nn \l__regex_build_tl
24422       { \__regex_branch:n { \if_false: } \fi: }
24423   }
24424 \cs_new_protected:Npn \__regex_compile_end:
24425 {
24426   \__regex_if_in_class:TF
24427   {
24428     \__kernel_msg_error:nn { kernel } { missing-rbrack }
24429     \use:c { __regex_compile_]: }

```



```

24430         \prg_do_nothing: \prg_do_nothing:
24431     }
24432     { }
24433     \if_int_compare:w \l__regex_group_level_int > 0 \exp_stop_f:
24434     \__kernel_msg_error:nxx { kernel } { missing-rparen }
24435     { \int_use:N \l__regex_group_level_int }
24436     \prg_replicate:nn
24437     { \l__regex_group_level_int }
24438     {
24439         \tl_build_put_right:Nn \l__regex_build_tl
24440         {
24441             \if_false: { \fi: }
24442             \if_false: { \fi: } { 1 } { 0 } \c_true_bool
24443         }
24444         \tl_build_end:N \l__regex_build_tl
24445         \exp_args:NNNo
24446         \group_end:
24447         \tl_build_put_right:Nn \l__regex_build_tl
24448         { \l__regex_build_tl }
24449     }
24450     \fi:
24451     \tl_build_put_right:Nn \l__regex_build_tl { \if_false: { \fi: } }
24452     \tl_build_end:N \l__regex_build_tl
24453     \exp_args:NNNx
24454     \group_end:
24455     \tl_set:Nn \l__regex_internal_regex { \l__regex_build_tl }
24456 }

```

(End definition for __regex_compile:w and __regex_compile_end:.)

__regex_compile:n The compilation is done between __regex_compile:w and __regex_compile_end:, starting in mode 0. Then __regex_escape_use:nnnn distinguishes special characters, escaped alphanumerics, and raw characters, interpreting \a, \x and other sequences. The 4 trailing \prg_do_nothing: are needed because some functions defined later look up to 4 tokens ahead. Before ending, make sure that any \c{...} is properly closed. No need to check that brackets are closed properly since __regex_compile_end: does that. However, catch the case of a trailing \cL construction.

```

24457 \cs_new_protected:Npn \__regex_compile:n #1
24458 {
24459     \__regex_compile:w
24460     \__regex_standard_escapechar:
24461     \int_set_eq:NN \l__regex_mode_int \c__regex_outer_mode_int
24462     \__regex_escape_use:nnnn
24463     {
24464         \__regex_char_if_special:NTF ##1
24465         \__regex_compile_special:N \__regex_compile_raw:N ##1
24466     }
24467     {
24468         \__regex_char_if_alphanumeric:NTF ##1
24469         \__regex_compile_escaped:N \__regex_compile_raw:N ##1
24470     }
24471     { \__regex_compile_raw:N ##1 }
24472     { #1 }
24473     \prg_do_nothing: \prg_do_nothing:

```

```

24474 \prg_do_nothing: \prg_do_nothing:
24475 \int_compare:nNnT \l__regex_mode_int = \c__regex_catcode_mode_int
24476 { \__kernel_msg_error:nn { kernel } { c-trailing } }
24477 \int_compare:nNnT \l__regex_mode_int < \c__regex_outer_mode_int
24478 {
24479   \__kernel_msg_error:nn { kernel } { c-missing-rbrace }
24480   \__regex_compile_end_cs:
24481   \prg_do_nothing: \prg_do_nothing:
24482   \prg_do_nothing: \prg_do_nothing:
24483 }
24484 \__regex_compile_end:
24485 }

```

(End definition for __regex_compile:n.)

__regex_compile_escaped:N If the special character or escaped alphanumeric has a particular meaning in regexes, the corresponding function is used. Otherwise, it is interpreted as a raw character. We distinguish special characters from escaped alphanumeric characters because they behave differently when appearing as an end-point of a range.

```

24486 \cs_new_protected:Npn \__regex_compile_special:N #1
24487 {
24488   \cs_if_exist_use:cF { __regex_compile_#1: }
24489   { \__regex_compile_raw:N #1 }
24490 }
24491 \cs_new_protected:Npn \__regex_compile_escaped:N #1
24492 {
24493   \cs_if_exist_use:cF { __regex_compile_/#1: }
24494   { \__regex_compile_raw:N #1 }
24495 }

```

(End definition for __regex_compile_escaped:N and __regex_compile_special:N.)

__regex_compile_one:n This is used after finding one “test”, such as \d, or a raw character. If that followed a catcode test (e.g., \cL), then restore the mode. If we are not in a class, then the test is “standalone”, and we need to add __regex_class:NnnnN and search for quantifiers. In any case, insert the test, possibly together with a catcode test if appropriate.

```

24496 \cs_new_protected:Npn \__regex_compile_one:n #1
24497 {
24498   \__regex_mode_quit_c:
24499   \__regex_if_in_class:TF { }
24500   {
24501     \tl_build_put_right:Nn \l__regex_build_tl
24502     { \__regex_class:NnnnN \c_true_bool { \if_false: } \fi: }
24503   }
24504   \tl_build_put_right:Nx \l__regex_build_tl
24505   {
24506     \if_int_compare:w \l__regex_catcodes_int <
24507     \c__regex_all_catcodes_int
24508     \__regex_item_catcode:nT { \int_use:N \l__regex_catcodes_int }
24509     { \exp_not:N \exp_not:n {#1} }
24510     \else:
24511     \exp_not:N \exp_not:n {#1}
24512     \fi:
24513   }

```

```

24514     \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
24515     \__regex_if_in_class:TF { } { \__regex_compile_quantifier:w }
24516 }

```

(End definition for __regex_compile_one:n.)

__regex_compile_abort_tokens:n This function places the collected tokens back in the input stream, each as a raw character.
 __regex_compile_abort_tokens:x Spaces are not preserved.

```

24517 \cs_new_protected:Npn \__regex_compile_abort_tokens:n #1
24518 {
24519     \use:x
24520     {
24521         \exp_args:No \tl_map_function:nN { \tl_to_str:n {#1} }
24522         \__regex_compile_raw:N
24523     }
24524 }
24525 \cs_generate_variant:Nn \__regex_compile_abort_tokens:n { x }

```

(End definition for __regex_compile_abort_tokens:n.)

40.3.5 Quantifiers

__regex_compile_quantifier:w This looks ahead and finds any quantifier (special character equal to either of ?+*{).

```

24526 \cs_new_protected:Npn \__regex_compile_quantifier:w #1#2
24527 {
24528     \token_if_eq_meaning:NNTF #1 \__regex_compile_special:N
24529     {
24530         \cs_if_exist_use:cF { \__regex_compile_quantifier_#2:w }
24531         { \__regex_compile_quantifier_none: #1 #2 }
24532     }
24533     { \__regex_compile_quantifier_none: #1 #2 }
24534 }

```

(End definition for __regex_compile_quantifier:w.)

__regex_compile_quantifier_none: Those functions are called whenever there is no quantifier, or a braced construction is
 __regex_compile_quantifier_abort:xNN invalid (equivalent to no quantifier, and whatever characters were grabbed are left raw).

```

24535 \cs_new_protected:Npn \__regex_compile_quantifier_none:
24536 {
24537     \tl_build_put_right:Nn \l__regex_build_tl
24538     { \if_false: { \fi: } { 1 } { 0 } \c_false_bool }
24539 }
24540 \cs_new_protected:Npn \__regex_compile_quantifier_abort:xNN #1#2#3
24541 {
24542     \__regex_compile_quantifier_none:
24543     \__kernel_msg_warning:nxx { kernel } { invalid-quantifier } {#1} {#3}
24544     \__regex_compile_abort_tokens:x {#1}
24545     #2 #3
24546 }

```

(End definition for __regex_compile_quantifier_none: and __regex_compile_quantifier_abort:xNN.)

`__regex_compile_quantifier_lazyness:nnNN` Once the “main” quantifier (`?`, `*`, `+` or a braced construction) is found, we check whether it is lazy (followed by a question mark). We then add to the compiled regex a closing brace (ending `__regex_class:NnnnN` and friends), the start-point of the range, its end-point, and a boolean, `true` for lazy and `false` for greedy operators.

```

24547 \cs_new_protected:Npn \__regex_compile_quantifier_lazyness:nnNN #1#2#3#4
24548 {
24549   \__regex_two_if_eq:NNNTF #3 #4 \__regex_compile_special:N ?
24550   {
24551     \tl_build_put_right:Nn \l__regex_build_tl
24552     { \if_false: { \fi: } { #1 } { #2 } \c_true_bool }
24553   }
24554   {
24555     \tl_build_put_right:Nn \l__regex_build_tl
24556     { \if_false: { \fi: } { #1 } { #2 } \c_false_bool }
24557     #3 #4
24558   }
24559 }

```

(End definition for `__regex_compile_quantifier_lazyness:nnNN`.)

`__regex_compile_quantifier?:w` For each “basic” quantifier, `?`, `*`, `+`, feed the correct arguments to `__regex_compile_quantifier_lazyness:nnNN`, `-1` means that there is no upper bound on the number of repetitions.

`__regex_compile_quantifier*:w`
`__regex_compile_quantifier+:w`

```

24560 \cs_new_protected:cpn { __regex_compile_quantifier?:w }
24561 { \__regex_compile_quantifier_lazyness:nnNN { 0 } { 1 } }
24562 \cs_new_protected:cpn { __regex_compile_quantifier*:w }
24563 { \__regex_compile_quantifier_lazyness:nnNN { 0 } { -1 } }
24564 \cs_new_protected:cpn { __regex_compile_quantifier+:w }
24565 { \__regex_compile_quantifier_lazyness:nnNN { 1 } { -1 } }

```

(End definition for `__regex_compile_quantifier?:w`, `__regex_compile_quantifier*:w`, and `__regex_compile_quantifier+:w`.)

`__regex_compile_quantifier{;w` Three possible syntaxes: `{<int>}`, `{<int>},` or `{<int>,<int>}`. Any other syntax causes us to abort and put whatever we collected back in the input stream, as `raw` characters, including the opening brace. Grab a number into `\l__regex_internal_a_int`. If the number is followed by a right brace, the range is `[a, a]`. If followed by a comma, grab one more number, and call the `_ii` or `_iii` auxiliary. Those auxiliaries check for a closing brace, leading to the range `[a, ∞]` or `[a, b]`, encoded as `{a}{-1}` and `{a}{b - a}`.

`__regex_compile_quantifier_braced_auxi:w`
`__regex_compile_quantifier_braced_auxii:w`
`__regex_compile_quantifier_braced_auxiii:w`

```

24566 \cs_new_protected:cpn { __regex_compile_quantifier_ \c_left_brace_str :w }
24567 {
24568   \__regex_get_digits:NTFw \l__regex_internal_a_int
24569   { \__regex_compile_quantifier_braced_auxi:w }
24570   { \__regex_compile_quantifier_abort:xNN { \c_left_brace_str } }
24571 }
24572 \cs_new_protected:Npn \__regex_compile_quantifier_braced_auxi:w #1#2
24573 {
24574   \str_case_e:nnF { #1 #2 }
24575   {
24576     { \__regex_compile_special:N \c_right_brace_str }
24577     {
24578       \exp_args:No \__regex_compile_quantifier_lazyness:nnNN
24579       { \int_use:N \l__regex_internal_a_int } { 0 }
24580     }

```

```

24581     { \_regex_compile_special:N , }
24582     {
24583         \_regex_get_digits:NTFw \l__regex_internal_b_int
24584         { \_regex_compile_quantifier_braced_auxiii:w }
24585         { \_regex_compile_quantifier_braced_auxii:w }
24586     }
24587 }
24588 {
24589     \_regex_compile_quantifier_abort:xNN
24590     { \c_left_brace_str \int_use:N \l__regex_internal_a_int }
24591     #1 #2
24592 }
24593 }
24594 \cs_new_protected:Npn \_regex_compile_quantifier_braced_auxii:w #1#2
24595 {
24596     \_regex_two_if_eq:NNNTF #1 #2 \_regex_compile_special:N \c_right_brace_str
24597     {
24598         \exp_args:No \_regex_compile_quantifier_lazyness:nnNN
24599         { \int_use:N \l__regex_internal_a_int } { -1 }
24600     }
24601     {
24602         \_regex_compile_quantifier_abort:xNN
24603         { \c_left_brace_str \int_use:N \l__regex_internal_a_int , }
24604         #1 #2
24605     }
24606 }
24607 \cs_new_protected:Npn \_regex_compile_quantifier_braced_auxiii:w #1#2
24608 {
24609     \_regex_two_if_eq:NNNTF #1 #2 \_regex_compile_special:N \c_right_brace_str
24610     {
24611         \if_int_compare:w \l__regex_internal_a_int >
24612             \l__regex_internal_b_int
24613             \_kernel_msg_error:nxxx { kernel } { backwards-quantifier }
24614             { \int_use:N \l__regex_internal_a_int }
24615             { \int_use:N \l__regex_internal_b_int }
24616             \int_zero:N \l__regex_internal_b_int
24617         \else:
24618             \int_sub:Nn \l__regex_internal_b_int \l__regex_internal_a_int
24619         \fi:
24620         \exp_args:Noo \_regex_compile_quantifier_lazyness:nnNN
24621         { \int_use:N \l__regex_internal_a_int }
24622         { \int_use:N \l__regex_internal_b_int }
24623     }
24624     {
24625         \_regex_compile_quantifier_abort:xNN
24626         {
24627             \c_left_brace_str
24628             \int_use:N \l__regex_internal_a_int ,
24629             \int_use:N \l__regex_internal_b_int
24630         }
24631         #1 #2
24632     }
24633 }

```

(End definition for _regex_compile_quantifier_{:w and others.)

40.3.6 Raw characters

`_regex_compile_raw_error:N` Within character classes, and following catcode tests, some escaped alphanumeric sequences such as `\b` do not have any meaning. They are replaced by a raw character, after spitting out an error.

```

24634 \cs_new_protected:Npn \_regex_compile_raw_error:N #1
24635 {
24636     \_kernel_msg_error:nnx { kernel } { bad-escape } {#1}
24637     \_regex_compile_raw:N #1
24638 }
```

(End definition for `_regex_compile_raw_error:N`.)

`_regex_compile_raw:N` If we are in a character class and the next character is an unescaped dash, this denotes a range. Otherwise, the current character `#1` matches itself.

```

24639 \cs_new_protected:Npn \_regex_compile_raw:N #1#2#3
24640 {
24641     \_regex_if_in_class:TF
24642     {
24643         \_regex_two_if_eq:NNNTF #2 #3 \_regex_compile_special:N -
24644         { \_regex_compile_range:Nw #1 }
24645         {
24646             \_regex_compile_one:n
24647             { \_regex_item_equal:n { \int_value:w '#1 } }
24648             #2 #3
24649         }
24650     }
24651     {
24652         \_regex_compile_one:n
24653         { \_regex_item_equal:n { \int_value:w '#1 } }
24654         #2 #3
24655     }
24656 }
```

(End definition for `_regex_compile_raw:N`.)

`_regex_compile_range:Nw` We have just read a raw character followed by a dash; this should be followed by an end-point for the range. Valid end-points are: any raw character; any special character, except a right bracket. In particular, escaped characters are forbidden.

`_regex_if_end_range:NNTF`

```

24657 \prg_new_protected_conditional:Npnn \_regex_if_end_range:NN #1#2 { TF }
24658 {
24659     \if_meaning:w \_regex_compile_raw:N #1
24660     \prg_return_true:
24661     \else:
24662         \if_meaning:w \_regex_compile_special:N #1
24663         \if_charcode:w ] #2
24664         \prg_return_false:
24665         \else:
24666             \prg_return_true:
24667         \fi:
24668     \else:
24669         \prg_return_false:
24670     \fi:
24671     \fi:
```

```

24672     }
24673 \cs_new_protected:Npn \__regex_compile_range:Nw #1#2#3
24674 {
24675     \__regex_if_end_range:NNTF #2 #3
24676     {
24677         \if_int_compare:w '#1 > '#3 \exp_stop_f:
24678         \__kernel_msg_error:nxxx { kernel } { range-backwards } {#1} {#3}
24679     \else:
24680         \tl_build_put_right:Nx \l__regex_build_tl
24681         {
24682             \if_int_compare:w '#1 = '#3 \exp_stop_f:
24683             \__regex_item_equal:n
24684             \else:
24685                 \__regex_item_range:nn { \int_value:w '#1 }
24686             \fi:
24687             { \int_value:w '#3 }
24688         }
24689     \fi:
24690 }
24691 {
24692     \__kernel_msg_warning:nxxx { kernel } { range-missing-end }
24693     {#1} { \c_backslash_str #3 }
24694     \tl_build_put_right:Nx \l__regex_build_tl
24695     {
24696         \__regex_item_equal:n { \int_value:w '#1 \exp_stop_f: }
24697         \__regex_item_equal:n { \int_value:w '- \exp_stop_f: }
24698     }
24699     #2#3
24700 }
24701 }

```

(End definition for __regex_compile_range:Nw and __regex_if_end_range:NNTF.)

40.3.7 Character properties

__regex_compile_.: In a class, the dot has no special meaning. Outside, insert __regex_prop_., which matches any character or control sequence, and refuses -2 (end-marker).

```

24702 \cs_new_protected:cpx { __regex_compile_.: }
24703 {
24704     \exp_not:N \__regex_if_in_class:TF
24705     { \__regex_compile_raw:N . }
24706     { \__regex_compile_one:n \exp_not:c { __regex_prop_.: } }
24707 }
24708 \cs_new_protected:cpn { __regex_prop_.: }
24709 {
24710     \if_int_compare:w \l__regex_curr_char_int > - 2 \exp_stop_f:
24711     \exp_after:wN \__regex_break_true:w
24712     \fi:
24713 }

```

(End definition for __regex_compile_.: and __regex_prop_.:)

__regex_compile_/d: The constants __regex_prop_d:, etc. hold a list of tests which match the corresponding character class, and jump to the __regex_break_point:TF marker. As for a normal character, we check for quantifiers.

```

\__regex_compile_/D:
\__regex_compile_/h:
\__regex_compile_/H:
\__regex_compile_/s:
\__regex_compile_/S:
\__regex_compile_/v:
\__regex_compile_/V:
\__regex_compile_/w:
\__regex_compile_/W:
\__regex_compile_/N:

```

```

24714 \cs_set_protected:Npn \__regex_tmp:w #1#2
24715 {
24716   \cs_new_protected:cpx { __regex_compile_/#1: }
24717   { \__regex_compile_one:n \exp_not:c { __regex_prop_#1: } }
24718   \cs_new_protected:cpx { __regex_compile_/#2: }
24719   {
24720     \__regex_compile_one:n
24721     { \__regex_item_reverse:n \exp_not:c { __regex_prop_#1: } }
24722   }
24723 }
24724 \__regex_tmp:w d D
24725 \__regex_tmp:w h H
24726 \__regex_tmp:w s S
24727 \__regex_tmp:w v V
24728 \__regex_tmp:w w W
24729 \cs_new_protected:cpn { __regex_compile_/N: }
24730 { \__regex_compile_one:n \__regex_prop_N: }

```

(End definition for __regex_compile_/d: and others.)

40.3.8 Anchoring and simple assertions

__regex_compile_anchor:NF In modes where assertions are allowed, anchor to the start of the query, the start of the match, or the end of the query, depending on the integer #1. In other modes, #2 treats the character as raw, with an error for escaped letters (\$ is valid in a class, but \A is definitely a mistake on the user's part).

```

\__regex_compile_anchor:NF
  \__regex_compile_#:
  \__regex_compile_/A:
  \__regex_compile_/G:
  \__regex_compile_/$:
  \__regex_compile_/Z:
  \__regex_compile_/z:
24731 \cs_new_protected:Npn \__regex_compile_anchor:NF #1#2
24732 {
24733   \__regex_if_in_class_or_catcode:TF {#2}
24734   {
24735     \tl_build_put_right:Nn \l__regex_build_tl
24736     { \__regex_assertion:Nn \c_true_bool { \__regex_anchor:N #1 } }
24737   }
24738 }
24739 \cs_set_protected:Npn \__regex_tmp:w #1#2
24740 {
24741   \cs_new_protected:cpn { __regex_compile_/#1: }
24742   { \__regex_compile_anchor:NF #2 { \__regex_compile_raw_error:N #1 } }
24743 }
24744 \__regex_tmp:w A \l__regex_min_pos_int
24745 \__regex_tmp:w G \l__regex_start_pos_int
24746 \__regex_tmp:w Z \l__regex_max_pos_int
24747 \__regex_tmp:w z \l__regex_max_pos_int
24748 \cs_set_protected:Npn \__regex_tmp:w #1#2
24749 {
24750   \cs_new_protected:cpn { __regex_compile_#1: }
24751   { \__regex_compile_anchor:NF #2 { \__regex_compile_raw:N #1 } }
24752 }
24753 \exp_args:Nx \__regex_tmp:w { \iow_char:N ^ } \l__regex_min_pos_int
24754 \exp_args:Nx \__regex_tmp:w { \iow_char:N $ } \l__regex_max_pos_int

```

(End definition for __regex_compile_anchor:NF and others.)

`__regex_compile_/b:` Contrarily to `^` and `$`, which could be implemented without really knowing what precedes in the token list, this requires more information, namely, the knowledge of the last character code.

`__regex_compile_/B:`

```

24755 \cs_new_protected:cpn { __regex_compile_/b: }
24756 {
24757   \__regex_if_in_class_or_catcode:TF
24758   { \__regex_compile_raw_error:N b }
24759   {
24760     \tl_build_put_right:Nn \l__regex_build_tl
24761     { \__regex_assertion:Nn \c_true_bool { \__regex_b_test: } }
24762   }
24763 }
24764 \cs_new_protected:cpn { __regex_compile_/B: }
24765 {
24766   \__regex_if_in_class_or_catcode:TF
24767   { \__regex_compile_raw_error:N B }
24768   {
24769     \tl_build_put_right:Nn \l__regex_build_tl
24770     { \__regex_assertion:Nn \c_false_bool { \__regex_b_test: } }
24771   }
24772 }

```

(End definition for `__regex_compile_/b:` and `__regex_compile_/B:.`)

40.3.9 Character classes

`__regex_compile_[:` Outside a class, right brackets have no meaning. In a class, change the mode ($m \rightarrow (m - 15)/13$, truncated) to reflect the fact that we are leaving the class. Look for quantifiers, unless we are still in a class after leaving one (the case of `[... \cL[...] ...]`). quantifiers.

```

24773 \cs_new_protected:cpn { __regex_compile_[: }
24774 {
24775   \__regex_if_in_class:TF
24776   {
24777     \if_int_compare:w \l__regex_mode_int >
24778     \c__regex_catcode_in_class_mode_int
24779     \tl_build_put_right:Nn \l__regex_build_tl { \if_false: { \fi: } }
24780     \fi:
24781     \tex_advance:D \l__regex_mode_int - 15 \exp_stop_f:
24782     \tex_divide:D \l__regex_mode_int 13 \exp_stop_f:
24783     \if_int_odd:w \l__regex_mode_int \else:
24784     \exp_after:wN \__regex_compile_quantifier:w
24785     \fi:
24786   }
24787   { \__regex_compile_raw:N ] }
24788 }

```

(End definition for `__regex_compile_[:.`)

`__regex_compile_[:` In a class, left brackets might introduce a POSIX character class, or mean nothing. Immediately following `\c<category>`, we must insert the appropriate catcode test, then parse the class; we pre-expand the catcode as an optimization. Otherwise (modes 0, -2 and -6) just parse the class. The mode is updated later.

```

24789 \cs_new_protected:cpn { __regex_compile_[: }

```

```

24790 {
24791     \__regex_if_in_class:TF
24792     { \__regex_compile_class_posix_test:w }
24793     {
24794         \__regex_if_within_catcode:TF
24795         {
24796             \exp_after:wN \__regex_compile_class_catcode:w
24797             \int_use:N \l__regex_catcodes_int ;
24798         }
24799         { \__regex_compile_class_normal:w }
24800     }
24801 }

```

(End definition for __regex_compile_[:.])

__regex_compile_class_normal:w In the “normal” case, we insert __regex_class:NnnnN *(boolean)* in the compiled code. The *(boolean)* is true for positive classes, and false for negative classes, characterized by a leading \sim . The auxiliary __regex_compile_class:TFNN also checks for a leading] which has a special meaning.

```

24802 \cs_new_protected:Npn \__regex_compile_class_normal:w
24803 {
24804     \__regex_compile_class:TFNN
24805     { \__regex_class:NnnnN \c_true_bool }
24806     { \__regex_class:NnnnN \c_false_bool }
24807 }

```

(End definition for __regex_compile_class_normal:w.)

__regex_compile_class_catcode:w This function is called for a left bracket in modes 2 or 6 (catcode test, and catcode test within a class). In mode 2 the whole construction needs to be put in a class (like single character). Then determine if the class is positive or negative, inserting __regex_item_catcode:nT or the reverse variant as appropriate, each with the current catcodes bitmap #1 as an argument, and reset the catcodes.

```

24808 \cs_new_protected:Npn \__regex_compile_class_catcode:w #1;
24809 {
24810     \if_int_compare:w \l__regex_mode_int = \c__regex_catcode_mode_int
24811     \tl_build_put_right:Nn \l__regex_build_tl
24812     { \__regex_class:NnnnN \c_true_bool { \if_false: } \fi: }
24813     \fi:
24814     \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
24815     \__regex_compile_class:TFNN
24816     { \__regex_item_catcode:nT {#1} }
24817     { \__regex_item_catcode_reverse:nT {#1} }
24818 }

```

(End definition for __regex_compile_class_catcode:w.)

__regex_compile_class:TFNN If the first character is \sim , then the class is negative (use #2), otherwise it is positive (use #1). If the next character is a right bracket, then it should be changed to a raw one.

```

24819 \cs_new_protected:Npn \__regex_compile_class:TFNN #1#2#3#4
24820 {
24821     \l__regex_mode_int = \int_value:w \l__regex_mode_int 3 \exp_stop_f:
24822     \__regex_two_if_eq:NNNTF #3 #4 \__regex_compile_special:N ^
24823     {

```

```

24824         \tl_build_put_right:Nn \l__regex_build_tl { #2 { \if_false: } \fi: }
24825         \__regex_compile_class:NN
24826     }
24827     {
24828         \tl_build_put_right:Nn \l__regex_build_tl { #1 { \if_false: } \fi: }
24829         \__regex_compile_class:NN #3 #4
24830     }
24831 }
24832 \cs_new_protected:Npn \__regex_compile_class:NN #1#2
24833 {
24834     \token_if_eq_charcode:NNTF #2 ]
24835     { \__regex_compile_raw:N #2 }
24836     { #1 #2 }
24837 }

```

(End definition for __regex_compile_class:TFNN and __regex_compile_class:NN.)

__regex_compile_class_posix_test:w Here we check for a syntax such as [:alpha:]. We also detect [= and [. which have a meaning in POSIX regular expressions, but are not implemented in l3regex. In case we see [:, grab raw characters until hopefully reaching :]. If that's missing, or the POSIX class is unknown, abort. If all is right, add the test to the current class, with an extra __regex_item_reverse:n for negative classes.

```

24838 \cs_new_protected:Npn \__regex_compile_class_posix_test:w #1#2
24839 {
24840     \token_if_eq_meaning:NNT \__regex_compile_special:N #1
24841     {
24842         \str_case:nn { #2 }
24843         {
24844             : { \__regex_compile_class_posix:NNNNw }
24845             = {
24846                 \__kernel_msg_warning:nxx { kernel }
24847                 { posix-unsupported } { = }
24848             }
24849             . {
24850                 \__kernel_msg_warning:nxx { kernel }
24851                 { posix-unsupported } { . }
24852             }
24853         }
24854     }
24855     \__regex_compile_raw:N [ #1 #2
24856 }
24857 \cs_new_protected:Npn \__regex_compile_class_posix:NNNNw #1#2#3#4#5#6
24858 {
24859     \__regex_two_if_eq:NNNTF #5 #6 \__regex_compile_special:N ^
24860     {
24861         \bool_set_false:N \l__regex_internal_bool
24862         \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
24863         \__regex_compile_class_posix_loop:w
24864     }
24865     {
24866         \bool_set_true:N \l__regex_internal_bool
24867         \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
24868         \__regex_compile_class_posix_loop:w #5 #6
24869     }

```

```

24870 }
24871 \cs_new:Npn \__regex_compile_class_posix_loop:w #1#2
24872 {
24873   \token_if_eq_meaning:NNTF \__regex_compile_raw:N #1
24874   { #2 \__regex_compile_class_posix_loop:w }
24875   { \if_false: { \fi: } \__regex_compile_class_posix_end:w #1 #2 }
24876 }
24877 \cs_new_protected:Npn \__regex_compile_class_posix_end:w #1#2#3#4
24878 {
24879   \__regex_two_if_eq:NNNTF #1 #2 \__regex_compile_special:N :
24880   { \__regex_two_if_eq:NNNTF #3 #4 \__regex_compile_special:N ] }
24881   { \use_ii:nn }
24882   {
24883     \cs_if_exist:cTF { __regex_posix_ \l__regex_internal_a_tl : }
24884     {
24885       \__regex_compile_one:n
24886       {
24887         \bool_if:NF \l__regex_internal_bool \__regex_item_reverse:n
24888         \exp_not:c { __regex_posix_ \l__regex_internal_a_tl : }
24889       }
24890     }
24891     {
24892       \__kernel_msg_warning:nxx { kernel } { posix-unknown }
24893       { \l__regex_internal_a_tl }
24894       \__regex_compile_abort_tokens:x
24895       {
24896         [: \bool_if:NF \l__regex_internal_bool { ^ }
24897         \l__regex_internal_a_tl :]
24898       }
24899     }
24900   }
24901   {
24902     \__kernel_msg_error:nxxx { kernel } { posix-missing-close }
24903     { [: \l__regex_internal_a_tl ] { #2 #4 }
24904     \__regex_compile_abort_tokens:x { [: \l__regex_internal_a_tl ]
24905     #1 #2 #3 #4
24906   }
24907 }

```

(End definition for __regex_compile_class_posix_test:w and others.)

40.3.10 Groups and alternations

`__regex_compile_group_begin:N` The contents of a regex group are turned into compiled code in `\l__regex_build_tl`, which ends up with items of the form `__regex_branch:n {⟨concatenation⟩}`. This construction is done using `\tl_build...` functions within a `TeX` group, which automatically makes sure that options (case-sensitivity and default catcode) are reset at the end of the group. The argument `#1` is `__regex_group:nnnN` or a variant thereof. A small subtlety to support `\cL(abc)` as a shorthand for `(\cLa\cLb\cLc)`: exit any pending catcode test, save the category code at the start of the group as the default catcode for that group, and make sure that the catcode is restored to the default outside the group.

```

24908 \cs_new_protected:Npn \__regex_compile_group_begin:N #1

```

```

24909 {
24910   \tl_build_put_right:Nn \l__regex_build_tl { #1 { \if_false: } \fi: }
24911   \__regex_mode_quit_c:
24912   \group_begin:
24913     \tl_build_begin:N \l__regex_build_tl
24914     \int_set_eq:NN \l__regex_default_catcodes_int \l__regex_catcodes_int
24915     \int_incr:N \l__regex_group_level_int
24916     \tl_build_put_right:Nn \l__regex_build_tl
24917       { \__regex_branch:n { \if_false: } \fi: }
24918   }
24919 \cs_new_protected:Npn \__regex_compile_group_end:
24920 {
24921   \if_int_compare:w \l__regex_group_level_int > 0 \exp_stop_f:
24922     \tl_build_put_right:Nn \l__regex_build_tl { \if_false: { \fi: } }
24923     \tl_build_end:N \l__regex_build_tl
24924     \exp_args:NNNx
24925     \group_end:
24926     \tl_build_put_right:Nn \l__regex_build_tl { \l__regex_build_tl }
24927     \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
24928     \exp_after:wN \__regex_compile_quantifier:w
24929   \else:
24930     \__kernel_msg_warning:nn { kernel } { extra-rparen }
24931     \exp_after:wN \__regex_compile_raw:N \exp_after:wN )
24932   \fi:
24933 }

```

(End definition for __regex_compile_group_begin:N and __regex_compile_group_end:.)

__regex_compile(: In a class, parentheses are not special. In a catcode test inside a class, a left parenthesis gives an error, to catch [a\cL(bcd)e]. Otherwise check for a ?, denoting special groups, and run the code for the corresponding special group.

```

24934 \cs_new_protected:cpn { __regex_compile(: }
24935 {
24936   \__regex_if_in_class:TF { \__regex_compile_raw:N ( }
24937   {
24938     \if_int_compare:w \l__regex_mode_int =
24939       \c__regex_catcode_in_class_mode_int
24940       \__kernel_msg_error:nn { kernel } { c-lparen-in-class }
24941       \exp_after:wN \__regex_compile_raw:N \exp_after:wN (
24942     \else:
24943       \exp_after:wN \__regex_compile_lparen:w
24944     \fi:
24945   }
24946 }
24947 \cs_new_protected:Npn \__regex_compile_lparen:w #1#2#3#4
24948 {
24949   \__regex_two_if_eq:NNNTF #1 #2 \__regex_compile_special:N ?
24950   {
24951     \cs_if_exist_use:cF
24952       { __regex_compile_special_group\_token_to_str:N #4 :w }
24953       {
24954         \__kernel_msg_warning:nnx { kernel } { special-group-unknown }
24955         { (? #4 }
24956         \__regex_compile_group_begin:N \__regex_group:nnnN

```

```

24957         \_regex_compile_raw:N ? #3 #4
24958     }
24959 }
24960 {
24961     \_regex_compile_group_begin:N \_regex_group:nnnN
24962     #1 #2 #3 #4
24963 }
24964 }

```

(End definition for _regex_compile(:))

_regex_compile_|: In a class, the pipe is not special. Otherwise, end the current branch and open another one.

```

24965 \cs_new_protected:cpn { \_regex_compile_|: }
24966 {
24967     \_regex_if_in_class:TF { \_regex_compile_raw:N | }
24968     {
24969         \tl_build_put_right:Nn \l__regex_build_tl
24970         { \if_false: { \fi: } \_regex_branch:n { \if_false: } \fi: }
24971     }
24972 }

```

(End definition for _regex_compile/(:))

_regex_compile_): Within a class, parentheses are not special. Outside, close a group.

```

24973 \cs_new_protected:cpn { \_regex_compile_): }
24974 {
24975     \_regex_if_in_class:TF { \_regex_compile_raw:N ) }
24976     { \_regex_compile_group_end: }
24977 }

```

(End definition for _regex_compile_(:))

_regex_compile_special_group::w Non-capturing, and resetting groups are easy to take care of during compilation; for those groups, the harder parts come when building.

```

24978 \cs_new_protected:cpn { \_regex_compile_special_group::w }
24979 { \_regex_compile_group_begin:N \_regex_group_no_capture:nnnN }
24980 \cs_new_protected:cpn { \_regex_compile_special_group_|:w }
24981 { \_regex_compile_group_begin:N \_regex_group_resetting:nnnN }

```

(End definition for _regex_compile_special_group::w and _regex_compile_special_group_|:w.)

_regex_compile_special_group_i:w The match can be made case-insensitive by setting the option with (?i); the original behaviour is restored by (?-i). This is the only supported option.

```

24982 \cs_new_protected:Npn \_regex_compile_special_group_i:w #1#2
24983 {
24984     \_regex_two_if_eq:NNNTF #1 #2 \_regex_compile_special:N )
24985     {
24986         \cs_set:Npn \_regex_item_equal:n
24987         { \_regex_item_caseless_equal:n }
24988         \cs_set:Npn \_regex_item_range:nn
24989         { \_regex_item_caseless_range:nn }
24990     }
24991     {
24992         \_kernel_msg_warning:nnx { kernel } { unknown-option } { (?i #2 }

```

```

24993     \_regex_compile_raw:N (
24994     \_regex_compile_raw:N ?
24995     \_regex_compile_raw:N i
24996     #1 #2
24997   }
24998 }
24999 \cs_new_protected:cpn { __regex_compile_special_group_-:w } #1#2#3#4
25000 {
25001   \_regex_two_if_eq:NNNTF #1 #2 \_regex_compile_raw:N i
25002   { \_regex_two_if_eq:NNNTF #3 #4 \_regex_compile_special:N ) }
25003   { \use_ii:nn }
25004   {
25005     \cs_set:Npn \_regex_item_equal:n
25006       { \_regex_item_caseful_equal:n }
25007     \cs_set:Npn \_regex_item_range:nn
25008       { \_regex_item_caseful_range:nn }
25009   }
25010   {
25011     \_kernel_msg_warning:nnx { kernel } { unknown-option } { (?-#2#4 }
25012     \_regex_compile_raw:N (
25013     \_regex_compile_raw:N ?
25014     \_regex_compile_raw:N -
25015     #1 #2 #3 #4
25016   }
25017 }

```

(End definition for _regex_compile_special_group_i:w and _regex_compile_special_group_-:w.)

40.3.11 Catcodes and csnames

```

\_regex_compile_/c:
\_regex_compile_c_test:NN

```

The \c escape sequence can be followed by a capital letter representing a character category, by a left bracket which starts a list of categories, or by a brace group holding a regular expression for a control sequence name. Otherwise, raise an error.

```

25018 \cs_new_protected:cpn { __regex_compile_/c: }
25019 { \_regex_chk_c_allowed:T { \_regex_compile_c_test:NN } }
25020 \cs_new_protected:Npn \_regex_compile_c_test:NN #1#2
25021 {
25022   \token_if_eq_meaning:NNTF #1 \_regex_compile_raw:N
25023   {
25024     \int_if_exist:cTF { c__regex_catcode_#2_int }
25025     {
25026       \int_set_eq:Nc \l__regex_catcodes_int
25027       { c__regex_catcode_#2_int }
25028       \l__regex_mode_int
25029       = \if_case:w \l__regex_mode_int
25030       \c__regex_catcode_mode_int
25031       \else:
25032       \c__regex_catcode_in_class_mode_int
25033       \fi:
25034       \token_if_eq_charcode:NNT C #2 { \_regex_compile_c_C:NN }
25035     }
25036   }
25037   { \cs_if_exist_use:cF { __regex_compile_c_#2:w } }
25038   {

```

```

25039         \_kernel_msg_error:nxx { kernel } { c-missing-category } {#2}
25040         #1 #2
25041     }
25042 }

```

(End definition for _regex_compile_/c: and _regex_compile_c_test:NN.)

_regex_compile_c_C:NN If \cC is not followed by . or (...) then complain because that construction cannot match anything, except in cases like \cC[\c{...}], where it has no effect.

```

25043 \cs_new_protected:Npn \_regex_compile_c_C:NN #1#2
25044 {
25045     \token_if_eq_meaning:NNTF #1 \_regex_compile_special:N
25046     {
25047         \token_if_eq_charcode:NNTF #2 .
25048         { \use_none:n }
25049         { \token_if_eq_charcode:NNTF #2 ( } % )
25050     }
25051     { \use:n }
25052     { \_kernel_msg_error:nnn { kernel } { c-C-invalid } {#2} }
25053     #1 #2
25054 }

```

(End definition for _regex_compile_c_C:NN.)

_regex_compile_c_[:w When encountering \c[, the task is to collect uppercase letters representing character categories. First check for ^ which negates the list of category codes.

```

\_regex_compile_c_lbrack_loop:NN
\_regex_compile_c_lbrack_add:N
\_regex_compile_c_lbrack_end:
25055 \cs_new_protected:cpn { \_regex_compile_c_[:w } #1#2
25056 {
25057     \l__regex_mode_int
25058     = \if_case:w \l__regex_mode_int
25059     \c__regex_catcode_mode_int
25060     \else:
25061     \c__regex_catcode_in_class_mode_int
25062     \fi:
25063     \int_zero:N \l__regex_catcodes_int
25064     \__regex_two_if_eq:NNNTF #1 #2 \_regex_compile_special:N ^
25065     {
25066         \bool_set_false:N \l__regex_catcodes_bool
25067         \_regex_compile_c_lbrack_loop:NN
25068     }
25069     {
25070         \bool_set_true:N \l__regex_catcodes_bool
25071         \_regex_compile_c_lbrack_loop:NN
25072         #1 #2
25073     }
25074 }
25075 \cs_new_protected:Npn \_regex_compile_c_lbrack_loop:NN #1#2
25076 {
25077     \token_if_eq_meaning:NNTF #1 \_regex_compile_raw:N
25078     {
25079         \int_if_exist:cTF { c__regex_catcode_#2_int }
25080         {
25081             \exp_args:Nc \_regex_compile_c_lbrack_add:N
25082             { c__regex_catcode_#2_int }

```



```

25083         \__regex_compile_c_lbrack_loop:NN
25084     }
25085 }
25086 {
25087     \token_if_eq_charcode:NNTF #2 ]
25088     { \__regex_compile_c_lbrack_end: }
25089 }
25090 {
25091     \__kernel_msg_error:nxx { kernel } { c-missing-rbrack } {#2}
25092     \__regex_compile_c_lbrack_end:
25093     #1 #2
25094 }
25095 }
25096 \cs_new_protected:Npn \__regex_compile_c_lbrack_add:N #1
25097 {
25098     \if_int_odd:w \int_eval:n { \l__regex_catcodes_int / #1 } \exp_stop_f:
25099     \else:
25100         \int_add:Nn \l__regex_catcodes_int {#1}
25101     \fi:
25102 }
25103 \cs_new_protected:Npn \__regex_compile_c_lbrack_end:
25104 {
25105     \if_meaning:w \c_false_bool \l__regex_catcodes_bool
25106         \int_set:Nn \l__regex_catcodes_int
25107         { \c__regex_all_catcodes_int - \l__regex_catcodes_int }
25108     \fi:
25109 }

```

(End definition for __regex_compile_c[:w and others.)

__regex_compile_c_{: The case of a left brace is easy, based on what we have done so far: in a group, compile the regular expression, after changing the mode to forbid nesting \c. Additionally, disable submatch tracking since groups don't escape the scope of \c{...}.

```

25110 \cs_new_protected:cpn { __regex_compile_c_ \c_left_brace_str :w }
25111 {
25112     \__regex_compile:w
25113     \__regex_disable_submatches:
25114     \l__regex_mode_int
25115     = \if_case:w \l__regex_mode_int
25116         \c__regex_cs_mode_int
25117     \else:
25118         \c__regex_cs_in_class_mode_int
25119     \fi:
25120 }

```

(End definition for __regex_compile_c_{:.)

__regex_compile_}: Non-escaped right braces are only special if they appear when compiling the regular expression for a csname, but not within a class: \c{[{}]} matches the control sequences \{ and \}. So, end compiling the inner regex (this closes any dangling class or group). __regex_compile_cs_aux:Nn Then insert the corresponding test in the outer regex. As an optimization, if the control sequence test simply consists of several explicit possibilities (branches) then use __-regex_item_exact_cs:n with an argument consisting of all possibilities separated by \scan_stop:.

```

25121 \flag_new:n { __regex_cs }
25122 \cs_new_protected:cpn { __regex_compile_ \c_right_brace_str : }
25123 {
25124   \__regex_if_in_cs:TF
25125   { \__regex_compile_end_cs: }
25126   { \exp_after:wN \__regex_compile_raw:N \c_right_brace_str }
25127 }
25128 \cs_new_protected:Npn \__regex_compile_end_cs:
25129 {
25130   \__regex_compile_end:
25131   \flag_clear:n { __regex_cs }
25132   \tl_set:Nx \l__regex_internal_a_tl
25133   {
25134     \exp_after:wN \__regex_compile_cs_aux:Nn \l__regex_internal_regex
25135     \q__regex_nil \q__regex_nil \q__regex_recursion_stop
25136   }
25137   \exp_args:Nx \__regex_compile_one:n
25138   {
25139     \flag_if_raised:nTF { __regex_cs }
25140     { \__regex_item_cs:n { \exp_not:o \l__regex_internal_regex } }
25141     {
25142       \__regex_item_exact_cs:n
25143       { \tl_tail:N \l__regex_internal_a_tl }
25144     }
25145   }
25146 }
25147 \cs_new:Npn \__regex_compile_cs_aux:Nn #1#2
25148 {
25149   \cs_if_eq:NNTF #1 \__regex_branch:n
25150   {
25151     \scan_stop:
25152     \__regex_compile_cs_aux:NNnnN #2
25153     \q__regex_nil \q__regex_nil \q__regex_nil
25154     \q__regex_nil \q__regex_nil \q__regex_nil \q__regex_recursion_stop
25155     \__regex_compile_cs_aux:Nn
25156   }
25157   {
25158     \__regex_quark_if_nil:NF #1 { \flag_raise_if_clear:n { __regex_cs } }
25159     \__regex_use_none_delimit_by_q_recursion_stop:w
25160   }
25161 }
25162 \cs_new:Npn \__regex_compile_cs_aux:NNnnN #1#2#3#4#5#6
25163 {
25164   \bool_lazy_all:nTF
25165   {
25166     { \cs_if_eq_p:NN #1 \__regex_class:NnnN }
25167     {#2}
25168     { \tl_if_head_eq_meaning_p:nN {#3} \__regex_item_caseful_equal:n }
25169     { \int_compare_p:nNn { \tl_count:n {#3} } = { 2 } }
25170     { \int_compare_p:nNn {#5} = { 0 } }
25171   }
25172   {
25173     \prg_replicate:nn {#4}
25174     { \char_generate:nn { \use_ii:nn #3 } {12} }

```

```

25175     \_regex_compile_cs_aux:NNnnnN
25176   }
25177   {
25178     \_regex_quark_if_nil:NF #1
25179     {
25180       \flag_raise_if_clear:n { \_regex_cs }
25181       \_regex_use_i_delimit_by_q_recursion_stop:nw
25182     }
25183     \_regex_use_none_delimit_by_q_recursion_stop:w
25184   }
25185 }

```

(End definition for _regex_compile_}: and others.)

40.3.12 Raw token lists with \u

_regex_compile_/u: The \u escape is invalid in classes and directly following a catcode test. Otherwise, it must be followed by a left brace. We then collect the characters for the argument of \u within an x-expanding assignment. In principle we could just wait to encounter a right brace, but this is unsafe: if the right brace was missing, then we would reach the end-markers of the regex, and continue, leading to obscure fatal errors. Instead, we only allow raw and special characters, and stop when encountering a special right brace, any escaped character, or the end-marker.

```

25186 \cs_new_protected:cpn { \_regex_compile_/u: } #1#2
25187 {
25188   \_regex_if_in_class_or_catcode:TF
25189   { \_regex_compile_raw_error:N u #1 #2 }
25190   {
25191     \_regex_two_if_eq:NNNTF #1 #2 \_regex_compile_special:N \c_left_brace_str
25192     {
25193       \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
25194       \_regex_compile_u_loop:NN
25195     }
25196     {
25197       \__kernel_msg_error:nn { kernel } { u-missing-lbrace }
25198       \_regex_compile_raw:N u #1 #2
25199     }
25200   }
25201 }
25202 \cs_new:Npn \_regex_compile_u_loop:NN #1#2
25203 {
25204   \token_if_eq_meaning:NNTF #1 \_regex_compile_raw:N
25205   { #2 \_regex_compile_u_loop:NN }
25206   {
25207     \token_if_eq_meaning:NNTF #1 \_regex_compile_special:N
25208     {
25209       \exp_after:wN \token_if_eq_charcode:NNTF \c_right_brace_str #2
25210       { \if_false: { \fi: } \_regex_compile_u_end: }
25211       { #2 \_regex_compile_u_loop:NN }
25212     }
25213     {
25214       \if_false: { \fi: }
25215       \__kernel_msg_error:nxx { kernel } { u-missing-rbrace } {#2}
25216       \_regex_compile_u_end:

```

```

25217         #1 #2
25218     }
25219 }
25220 }

```

(End definition for `_regex_compile/u:` and `_regex_compile_u_loop:NN`.)

`_regex_compile_u_end:` Once we have extracted the variable's name, we store the contents of that variable in `\l_regex_internal_a_tl`. The behaviour of `\u` then depends on whether we are within a `\c{...}` escape (in this case, the variable is turned to a string), or not.

```

25221 \cs_new_protected:Npn \_regex_compile_u_end:
25222 {
25223     \tl_set:Nv \l\_regex_internal_a_tl { \l\_regex_internal_a_tl }
25224     \if_int_compare:w \l\_regex_mode_int = \c\_regex_outer_mode_int
25225         \_regex_compile_u_not_cs:
25226     \else:
25227         \_regex_compile_u_in_cs:
25228     \fi:
25229 }

```

(End definition for `_regex_compile_u_end:`.)

`_regex_compile_u_in_cs:` When `\u` appears within a control sequence, we convert the variable to a string with escaped spaces. Then for each character insert a class matching exactly that character, once.

```

25230 \cs_new_protected:Npn \_regex_compile_u_in_cs:
25231 {
25232     \tl_gset:Nx \g\_regex_internal_tl
25233     {
25234         \exp_args:No \__kernel_str_to_other_fast:n
25235         { \l\_regex_internal_a_tl }
25236     }
25237     \tl_build_put_right:Nx \l\_regex_build_tl
25238     {
25239         \tl_map_function:NN \g\_regex_internal_tl
25240         \_regex_compile_u_in_cs_aux:n
25241     }
25242 }
25243 \cs_new:Npn \_regex_compile_u_in_cs_aux:n #1
25244 {
25245     \_regex_class:NnnN \c_true_bool
25246     { \_regex_item_caseful_equal:n { \int_value:w '#1 } }
25247     { 1 } { 0 } \c_false_bool
25248 }

```

(End definition for `_regex_compile_u_in_cs:`.)

`_regex_compile_u_not_cs:` In mode 0, the `\u` escape adds one state to the NFA for each token in `\l_regex_internal_a_tl`. If a given *<token>* is a control sequence, then insert a string comparison test, otherwise, `_regex_item_exact:nn` which compares catcode and character code.

```

25249 \cs_new_protected:Npn \_regex_compile_u_not_cs:
25250 {
25251     \tl_analysis_map_inline:Nn \l\_regex_internal_a_tl
25252     {

```

```

25253 \tl_build_put_right:Nx \l__regex_build_tl
25254 {
25255   \__regex_class:NnnN \c_true_bool
25256   {
25257     \if_int_compare:w "##3 = 0 \exp_stop_f:
25258       \__regex_item_exact_cs:n
25259       { \exp_after:wN \cs_to_str:N ##1 }
25260     \else:
25261       \__regex_item_exact:nn { \int_value:w "##3 } { ##2 }
25262     \fi:
25263   }
25264   { 1 } { 0 } \c_false_bool
25265 }
25266 }
25267 }

```

(End definition for __regex_compile_u_not_cs:.)

40.3.13 Other

__regex_compile_/K: The \K control sequence is currently the only “command”, which performs some action, rather than matching something. It is allowed in the same contexts as \b. At the compilation stage, we leave it as a single control sequence, defined later.

```

25268 \cs_new_protected:cpn { __regex_compile_/K: }
25269 {
25270   \int_compare:nNnTF \l__regex_mode_int = \c__regex_outer_mode_int
25271     { \tl_build_put_right:Nn \l__regex_build_tl { \__regex_command_K: } }
25272     { \__regex_compile_raw_error:N K }
25273 }

```

(End definition for __regex_compile_/K:.)

40.3.14 Showing regexes

__regex_show:N Within a group and within \tl_build_begin:N ... \tl_build_end:N we redefine all the function that can appear in a compiled regex, then run the regex. The result stored in \l__regex_internal_a_tl is then meant to be shown.

```

25274 \cs_new_protected:Npn \__regex_show:N #1
25275 {
25276   \group_begin:
25277   \tl_build_begin:N \l__regex_build_tl
25278   \cs_set_protected:Npn \__regex_branch:n
25279   {
25280     \seq_pop_right:NN \l__regex_show_prefix_seq
25281     \l__regex_internal_a_tl
25282     \__regex_show_one:n { +-branch }
25283     \seq_put_right:No \l__regex_show_prefix_seq
25284     \l__regex_internal_a_tl
25285     \use:n
25286   }
25287   \cs_set_protected:Npn \__regex_group:nnnN
25288   { \__regex_show_group_aux:nnnnN { } }
25289   \cs_set_protected:Npn \__regex_group_no_capture:nnnN
25290   { \__regex_show_group_aux:nnnnN { ~(no~capture) } }

```

```

25291 \cs_set_protected:Npn \__regex_group_resetting:nnnN
25292 { \__regex_show_group_aux:nnnnN { ~(resetting) } }
25293 \cs_set_eq:NN \__regex_class:NnnnN \__regex_show_class:NnnnN
25294 \cs_set_protected:Npn \__regex_command_K:
25295 { \__regex_show_one:n { reset~match~start~(\iow_char:N\K) } }
25296 \cs_set_protected:Npn \__regex_assertion:Nn ##1##2
25297 {
25298   \__regex_show_one:n
25299   { \bool_if:NF ##1 { negative~ } assertion:~##2 }
25300 }
25301 \cs_set:Npn \__regex_b_test: { word~boundary }
25302 \cs_set_eq:NN \__regex_anchor:N \__regex_show_anchor_to_str:N
25303 \cs_set_protected:Npn \__regex_item_caseful_equal:n ##1
25304 { \__regex_show_one:n { char~code~\int_eval:n{##1} } }
25305 \cs_set_protected:Npn \__regex_item_caseful_range:nn ##1##2
25306 {
25307   \__regex_show_one:n
25308   { range~[\int_eval:n{##1}, \int_eval:n{##2}] }
25309 }
25310 \cs_set_protected:Npn \__regex_item_caseless_equal:n ##1
25311 { \__regex_show_one:n { char~code~\int_eval:n{##1}~(caseless) } }
25312 \cs_set_protected:Npn \__regex_item_caseless_range:nn ##1##2
25313 {
25314   \__regex_show_one:n
25315   { Range~[\int_eval:n{##1}, \int_eval:n{##2}]~(caseless) }
25316 }
25317 \cs_set_protected:Npn \__regex_item_catcode:nT
25318 { \__regex_show_item_catcode:NnT \c_true_bool }
25319 \cs_set_protected:Npn \__regex_item_catcode_reverse:nT
25320 { \__regex_show_item_catcode:NnT \c_false_bool }
25321 \cs_set_protected:Npn \__regex_item_reverse:n
25322 { \__regex_show_scope:nn { Reversed~match } }
25323 \cs_set_protected:Npn \__regex_item_exact:nn ##1##2
25324 { \__regex_show_one:n { char~##2,~catcode~##1 } }
25325 \cs_set_eq:NN \__regex_item_exact_cs:n \__regex_show_item_exact_cs:n
25326 \cs_set_protected:Npn \__regex_item_cs:n
25327 { \__regex_show_scope:nn { control~sequence } }
25328 \cs_set:cpn { __regex_prop_.. } { \__regex_show_one:n { any~token } }
25329 \seq_clear:N \l__regex_show_prefix_seq
25330 \__regex_show_push:n { ~ }
25331 \cs_if_exist_use:N #1
25332 \tl_build_end:N \l__regex_build_tl
25333 \exp_args:NNNo
25334 \group_end:
25335 \tl_set:Nn \l__regex_internal_a_tl { \l__regex_build_tl }
25336 }

```

(End definition for __regex_show:N.)

__regex_show_one:n Every part of the final message go through this function, which adds one line to the output, with the appropriate prefix.

```

25337 \cs_new_protected:Npn \__regex_show_one:n #1
25338 {
25339   \int_incr:N \l__regex_show_lines_int

```

```

25340 \tl_build_put_right:Nx \l__regex_build_tl
25341 {
25342   \exp_not:N \iow_newline:
25343   \seq_map_function:NN \l__regex_show_prefix_seq \use:n
25344   #1
25345 }
25346 }

```

(End definition for __regex_show_one:n.)

__regex_show_push:n Enter and exit levels of nesting. The `scope` function prints its first argument as an “introduction”, then performs its second argument in a deeper level of nesting.

```

\__regex_show_pop:
\__regex_show_scope:nn
25347 \cs_new_protected:Npn \__regex_show_push:n #1
25348 { \seq_put_right:Nx \l__regex_show_prefix_seq { #1 ~ } }
25349 \cs_new_protected:Npn \__regex_show_pop:
25350 { \seq_pop_right:NN \l__regex_show_prefix_seq \l__regex_internal_a_tl }
25351 \cs_new_protected:Npn \__regex_show_scope:nn #1#2
25352 {
25353   \__regex_show_one:n {#1}
25354   \__regex_show_push:n { ~ }
25355   #2
25356   \__regex_show_pop:
25357 }

```

(End definition for __regex_show_push:n, __regex_show_pop:, and __regex_show_scope:nn.)

__regex_show_group_aux:nnnnN We display all groups in the same way, simply adding a message, (no capture) or (resetting), to special groups. The odd \use_ii:nn avoids printing a spurious +-branch for the first branch.

```

25358 \cs_new_protected:Npn \__regex_show_group_aux:nnnnN #1#2#3#4#5
25359 {
25360   \__regex_show_one:n { , -group~begin #1 }
25361   \__regex_show_push:n { | }
25362   \use_ii:nn #2
25363   \__regex_show_pop:
25364   \__regex_show_one:n
25365   { ‘-group~end \__regex_msg_repeated:nnN {#3} {#4} #5 }
25366 }

```

(End definition for __regex_show_group_aux:nnnnN.)

__regex_show_class:NnnnN I’m entirely unhappy about this function: I couldn’t find a way to test if a class is a single test. Instead, collect the representation of the tests in the class. If that had more than one line, write `Match` or `Don’t match` on its own line, with the repeating information if any. Then the various tests on lines of their own, and finally a line. Otherwise, we need to evaluate the representation of the tests again (since the prefix is incorrect). That’s clunky, but not too expensive, since it’s only one test.

```

25367 \cs_set:Npn \__regex_show_class:NnnnN #1#2#3#4#5
25368 {
25369   \group_begin:
25370   \tl_build_begin:N \l__regex_build_tl
25371   \int_zero:N \l__regex_show_lines_int
25372   \__regex_show_push:n {~}
25373   #2

```

```

25374 \int_compare:nTF { \l__regex_show_lines_int = 0 }
25375 {
25376   \group_end:
25377   \__regex_show_one:n { \bool_if:NTF #1 { Fail } { Pass } }
25378 }
25379 {
25380   \bool_if:nTF
25381   { #1 && \int_compare_p:n { \l__regex_show_lines_int = 1 } }
25382   {
25383     \group_end:
25384     #2
25385     \tl_build_put_right:Nn \l__regex_build_tl
25386     { \__regex_msg_repeated:nnN {#3} {#4} #5 }
25387   }
25388   {
25389     \tl_build_end:N \l__regex_build_tl
25390     \exp_args:NNNo
25391     \group_end:
25392     \tl_set:Nn \l__regex_internal_a_tl \l__regex_build_tl
25393     \__regex_show_one:n
25394     {
25395       \bool_if:NTF #1 { Match } { Don't-match }
25396       \__regex_msg_repeated:nnN {#3} {#4} #5
25397     }
25398     \tl_build_put_right:Nx \l__regex_build_tl
25399     { \exp_not:o \l__regex_internal_a_tl }
25400   }
25401 }
25402 }

```

(End definition for __regex_show_class:NnnnN.)

__regex_show_anchor_to_str:N The argument is an integer telling us where the anchor is. We convert that to the relevant info.

```

25403 \cs_new:Npn \__regex_show_anchor_to_str:N #1
25404 {
25405   anchor~at~
25406   \str_case:nnF { #1 }
25407   {
25408     { \l__regex_min_pos_int } { start~(\iow_char:N\A) }
25409     { \l__regex_start_pos_int } { start~of~match~(\iow_char:N\G) }
25410     { \l__regex_max_pos_int } { end~(\iow_char:N\Z) }
25411   }
25412   { <error:~'#1'~not~recognized> }
25413 }

```

(End definition for __regex_show_anchor_to_str:N.)

__regex_show_item_catcode:NnT Produce a sequence of categories which the catcode bitmap #2 contains, and show it, indenting the tests on which this catcode constraint applies.

```

25414 \cs_new_protected:Npn \__regex_show_item_catcode:NnT #1#2
25415 {
25416   \seq_set_split:Nnn \l__regex_internal_seq { } { CBEMTPUDSLOA }
25417   \seq_set_filter:Nnn \l__regex_internal_seq \l__regex_internal_seq

```



```

25418     { \int_if_odd_p:n { #2 / \int_use:c { c__regex_catcode_##1_int } } }
25419 \__regex_show_scope:nn
25420 {
25421     categories~
25422     \seq_map_function:NN \l__regex_internal_seq \use:n
25423     , ~
25424     \bool_if:NF #1 { negative~ } class
25425 }
25426 }

```

(End definition for `__regex_show_item_catcode:NnT`.)

`__regex_show_item_exact_cs:n`

```

25427 \cs_new_protected:Npn \__regex_show_item_exact_cs:n #1
25428 {
25429     \seq_set_split:Nnn \l__regex_internal_seq { \scan_stop: } {#1}
25430     \seq_set_map:NNn \l__regex_internal_seq
25431         \l__regex_internal_seq { \iow_char:N\##1 }
25432     \__regex_show_one:n
25433     { control~sequence~ \seq_use:Nn \l__regex_internal_seq { ~or~ } }
25434 }

```

(End definition for `__regex_show_item_exact_cs:n`.)

40.4 Building

40.4.1 Variables used while building

`\l__regex_min_state_int`
`\l__regex_max_state_int`

The last state that was allocated is `\l__regex_max_state_int - 1`, so that `\l__regex_max_state_int` always points to a free state. The `min_state` variable is 1 to begin with, but gets shifted in nested calls to the matching code, namely in `\c{...}` constructions.

```

25435 \int_new:N \l__regex_min_state_int
25436 \int_set:Nn \l__regex_min_state_int { 1 }
25437 \int_new:N \l__regex_max_state_int

```

(End definition for `\l__regex_min_state_int` and `\l__regex_max_state_int`.)

`\l__regex_left_state_int`
`\l__regex_right_state_int`
`\l__regex_left_state_seq`
`\l__regex_right_state_seq`

Alternatives are implemented by branching from a `left` state into the various choices, then merging those into a `right` state. We store information about those states in two sequences. Those states are also used to implement group quantifiers. Most often, the left and right pointers only differ by 1.

```

25438 \int_new:N \l__regex_left_state_int
25439 \int_new:N \l__regex_right_state_int
25440 \seq_new:N \l__regex_left_state_seq
25441 \seq_new:N \l__regex_right_state_seq

```

(End definition for `\l__regex_left_state_int` and others.)

`\l__regex_capturing_group_int`

`\l__regex_capturing_group_int` is the next ID number to be assigned to a capturing group. This starts at 0 for the group enclosing the full regular expression, and groups are counted in the order of their left parenthesis, except when encountering `resetting` groups.

```

25442 \int_new:N \l__regex_capturing_group_int

```

(End definition for `\l__regex_capturing_group_int`.)

40.4.2 Framework

This phase is about going from a compiled regex to an NFA. Each state of the NFA is stored in a `\toks`. The operations which can appear in the `\toks` are

- `__regex_action_start_wildcard`: inserted at the start of the regular expression to make it unanchored.
- `__regex_action_success`: marks the exit state of the NFA.
- `__regex_action_cost:n {\langle shift \rangle}` is a transition from the current $\langle state \rangle$ to $\langle state \rangle + \langle shift \rangle$, which consumes the current character: the target state is saved and will be considered again when matching at the next position.
- `__regex_action_free:n {\langle shift \rangle}`, and `__regex_action_free_group:n {\langle shift \rangle}` are free transitions, which immediately perform the actions for the state $\langle state \rangle + \langle shift \rangle$ of the NFA. They differ in how they detect and avoid infinite loops. For now, we just need to know that the `group` variant must be used for transitions back to the start of a group.
- `__regex_action_submatch:n {\langle key \rangle}` where the $\langle key \rangle$ is a group number followed by `<` or `>` for the beginning or end of group. This causes the current position in the query to be stored as the $\langle key \rangle$ submatch boundary.

We strive to preserve the following properties while building.

- The current capturing group is `capturing_group - 1`, and if a group opened now it would be labelled `capturing_group`.
- The last allocated state is `max_state - 1`, so `max_state` is a free state.
- The `left_state` points to a state to the left of the current group or of the last class.
- The `right_state` points to a newly created, empty state, with some transitions leading to it.
- The `left/right` sequences hold a list of the corresponding end-points of nested groups.

`__regex_build:n` The `n`-type function first compiles its argument. Reset some variables. Allocate two states, and put a wildcard in state 0 (transitions to state 1 and 0 state). Then build the regex within a (capturing) group numbered 0 (current value of `capturing_group`). Finally, if the match reaches the last state, it is successful.

```
\__regex_build:N
25443 \cs_new_protected:Npn \__regex_build:n #1
25444 {
25445   \__regex_compile:n {#1}
25446   \__regex_build:N \l__regex_internal_regex
25447 }
25448 \cs_new_protected:Npn \__regex_build:N #1
25449 {
25450   \__regex_standard_escapechar:
25451   \int_zero:N \l__regex_capturing_group_int
25452   \int_set_eq:NN \l__regex_max_state_int \l__regex_min_state_int
25453   \__regex_build_new_state:
```

```

25454     \__regex_build_new_state:
25455     \__regex_toks_put_right:Nn \l__regex_left_state_int
25456       { \__regex_action_start_wildcard: }
25457     \__regex_group:nnnN {#1} { 1 } { 0 } \c_false_bool
25458     \__regex_toks_put_right:Nn \l__regex_right_state_int
25459       { \__regex_action_success: }
25460   }

```

(End definition for __regex_build:n and __regex_build:N.)

__regex_build_for_cs:n The matching code relies on some global intarray variables, but only uses a range of their entries. Specifically,

- \g__regex_state_active_intarray from \l__regex_min_state_int to \l__regex_max_state_int;
- \g__regex_thread_state_intarray from \l__regex_min_active_int to \l__regex_max_active_int.

In fact, some data is stored in \toks registers (local) in the same ranges so these ranges mustn't overlap. This is done by setting \l__regex_min_active_int to \l__regex_max_state_int after building the NFA. Here, in this nested call to the matching code, we need the new versions of these ranges to involve completely new entries of the intarray variables, so we begin by setting (the new) \l__regex_min_state_int to (the old) \l__regex_max_active_int to use higher entries.

When using a regex to match a cs, we don't insert a wildcard, we anchor at the end, and since we ignore submatches, there is no need to surround the expression with a group. However, for branches to work properly at the outer level, we need to put the appropriate left and right states in their sequence.

```

25461 \cs_new_protected:Npn \__regex_build_for_cs:n #1
25462   {
25463     \int_set_eq:NN \l__regex_min_state_int \l__regex_max_active_int
25464     \int_set_eq:NN \l__regex_max_state_int \l__regex_min_state_int
25465     \__regex_build_new_state:
25466     \__regex_build_new_state:
25467     \__regex_push_lr_states:
25468     #1
25469     \__regex_pop_lr_states:
25470     \__regex_toks_put_right:Nn \l__regex_right_state_int
25471     {
25472       \if_int_compare:w \l__regex_curr_pos_int = \l__regex_max_pos_int
25473         \exp_after:wN \__regex_action_success:
25474       \fi:
25475     }
25476   }

```

(End definition for __regex_build_for_cs:n.)

40.4.3 Helpers for building an nfa

__regex_push_lr_states: When building the regular expression, we keep track of pointers to the left-end and right-end of each group without help from T_EX's grouping.

```

25477 \cs_new_protected:Npn \__regex_push_lr_states:
25478   {

```

```

25479     \seq_push:No \l__regex_left_state_seq
25480     { \int_use:N \l__regex_left_state_int }
25481     \seq_push:No \l__regex_right_state_seq
25482     { \int_use:N \l__regex_right_state_int }
25483   }
25484   \cs_new_protected:Npn \__regex_pop_lr_states:
25485   {
25486     \seq_pop:Nn \l__regex_left_state_seq \l__regex_internal_a_tl
25487     \int_set:Nn \l__regex_left_state_int \l__regex_internal_a_tl
25488     \seq_pop:Nn \l__regex_right_state_seq \l__regex_internal_a_tl
25489     \int_set:Nn \l__regex_right_state_int \l__regex_internal_a_tl
25490   }

```

(End definition for __regex_push_lr_states: and __regex_pop_lr_states:.)

__regex_build_transition_left:NNN Add a transition from #2 to #3 using the function #1. The left function is used for higher priority transitions, and the right function for lower priority transitions (which should be performed later). The signatures differ to reflect the differing usage later on. Both functions could be optimized.

```

25491   \cs_new_protected:Npn \__regex_build_transition_left:NNN #1#2#3
25492   { \__regex_toks_put_left:Nx #2 { #1 { \int_eval:n { #3 - #2 } } } }
25493   \cs_new_protected:Npn \__regex_build_transition_right:nNn #1#2#3
25494   { \__regex_toks_put_right:Nx #2 { #1 { \int_eval:n { #3 - #2 } } } }

```

(End definition for __regex_build_transition_left:NNN and __regex_build_transition_right:nNn.)

__regex_build_new_state: Add a new empty state to the NFA. Then update the left, right, and max states, so that the right state is the new empty state, and the left state points to the previously “current” state.

```

25495   \cs_new_protected:Npn \__regex_build_new_state:
25496   {
25497     \__regex_toks_clear:N \l__regex_max_state_int
25498     \int_set_eq:NN \l__regex_left_state_int \l__regex_right_state_int
25499     \int_set_eq:NN \l__regex_right_state_int \l__regex_max_state_int
25500     \int_incr:N \l__regex_max_state_int
25501   }

```

(End definition for __regex_build_new_state:.)

__regex_build_transitions_lazyness:NNNNN This function creates a new state, and puts two transitions starting from the old current state. The order of the transitions is controlled by #1, true for lazy quantifiers, and false for greedy quantifiers.

```

25502   \cs_new_protected:Npn \__regex_build_transitions_lazyness:NNNNN #1#2#3#4#5
25503   {
25504     \__regex_build_new_state:
25505     \__regex_toks_put_right:Nx \l__regex_left_state_int
25506     {
25507       \if_meaning:w \c_true_bool #1
25508       #2 { \int_eval:n { #3 - \l__regex_left_state_int } }
25509       #4 { \int_eval:n { #5 - \l__regex_left_state_int } }
25510     } \else:
25511       #4 { \int_eval:n { #5 - \l__regex_left_state_int } }
25512       #2 { \int_eval:n { #3 - \l__regex_left_state_int } }
25513     } \fi:

```

```

25514     }
25515 }

```

(End definition for `_regex_build_transitions_lazyness:NNNNN`.)

40.4.4 Building classes

```

\_regex_class:NnnnN
\_regex_tests_action_cost:n

```

The arguments are: $\langle \text{boolean} \rangle$ $\{\langle \text{tests} \rangle\}$ $\{\langle \text{min} \rangle\}$ $\{\langle \text{more} \rangle\}$ $\langle \text{lazyness} \rangle$. First store the tests with a trailing `_regex_action_cost:n`, in the true branch of `_regex_break_point:TF` for positive classes, or the false branch for negative classes. The integer $\langle \text{more} \rangle$ is 0 for fixed repetitions, -1 for unbounded repetitions, and $\langle \text{max} \rangle - \langle \text{min} \rangle$ for a range of repetitions.

```

25516 \cs_new_protected:Npn \_regex_class:NnnnN #1#2#3#4#5
25517 {
25518   \cs_set:Npx \_regex_tests_action_cost:n ##1
25519   {
25520     \exp_not:n { \exp_not:n {#2} }
25521     \bool_if:NTF #1
25522       { \_regex_break_point:TF { \_regex_action_cost:n {##1} } { } }
25523       { \_regex_break_point:TF { } { \_regex_action_cost:n {##1} } }
25524   }
25525   \if_case:w - #4 \exp_stop_f:
25526     \_regex_class_repeat:n {#3}
25527   \or: \_regex_class_repeat:nN {#3} #5
25528   \else: \_regex_class_repeat:nnN {#3} {#4} #5
25529   \fi:
25530 }
25531 \cs_new:Npn \_regex_tests_action_cost:n { \_regex_action_cost:n }

```

(End definition for `_regex_class:NnnnN` and `_regex_tests_action_cost:n`.)

```

\_regex_class_repeat:n

```

This is used for a fixed number of repetitions. Build one state for each repetition, with a transition controlled by the tests that we have collected. That works just fine for $\#1 = 0$ repetitions: nothing is built.

```

25532 \cs_new_protected:Npn \_regex_class_repeat:n #1
25533 {
25534   \prg_replicate:nn {#1}
25535   {
25536     \_regex_build_new_state:
25537     \_regex_build_transition_right:nNn \_regex_tests_action_cost:n
25538     \l__regex_left_state_int \l__regex_right_state_int
25539   }
25540 }

```

(End definition for `_regex_class_repeat:n`.)

```

\_regex_class_repeat:nN

```

This implements unbounded repetitions of a single class (e.g. the $*$ and $+$ quantifiers). If the minimum number $\#1$ of repetitions is 0, then build a transition from the current state to itself governed by the tests, and a free transition to a new state (hence skipping the tests). Otherwise, call `_regex_class_repeat:n` for the code to match $\#1$ repetitions, and add free transitions from the last state to the previous one, and to a new one. In both cases, the order of transitions is controlled by the lazyness boolean $\#2$.

```

25541 \cs_new_protected:Npn \_regex_class_repeat:nN #1#2
25542 {

```

```

25543 \if_int_compare:w #1 = 0 \exp_stop_f:
25544 \__regex_build_transitions_lazyness:NNNN #2
25545 \__regex_action_free:n \l__regex_right_state_int
25546 \__regex_tests_action_cost:n \l__regex_left_state_int
25547 \else:
25548 \__regex_class_repeat:n {#1}
25549 \int_set_eq:NN \l__regex_internal_a_int \l__regex_left_state_int
25550 \__regex_build_transitions_lazyness:NNNN #2
25551 \__regex_action_free:n \l__regex_right_state_int
25552 \__regex_action_free:n \l__regex_internal_a_int
25553 \fi:
25554 }

```

(End definition for __regex_class_repeat:nN.)

__regex_class_repeat:nnN We want to build the code to match from #1 to #1 + #2 repetitions. Match #1 repetitions (can be 0). Compute the final state of the next construction as a. Build #2 > 0 states, each with a transition to the next state governed by the tests, and a transition to the final state a. The computation of a is safe because states are allocated in order, starting from max_state.

```

25555 \cs_new_protected:Npn \__regex_class_repeat:nnN #1#2#3
25556 {
25557 \__regex_class_repeat:n {#1}
25558 \int_set:Nn \l__regex_internal_a_int
25559 { \l__regex_max_state_int + #2 - 1 }
25560 \prg_replicate:nn { #2 }
25561 {
25562 \__regex_build_transitions_lazyness:NNNN #3
25563 \__regex_action_free:n \l__regex_internal_a_int
25564 \__regex_tests_action_cost:n \l__regex_right_state_int
25565 }
25566 }

```

(End definition for __regex_class_repeat:nnN.)

40.4.5 Building groups

__regex_group_aux:nnnnN Arguments: {<label>} {<contents>} {<min>} {<more>} <lazyness>. If <min> is 0, we need to add a state before building the group, so that the thread which skips the group does not also set the start-point of the submatch. After adding one more state, the left_state is the left end of the group, from which all branches stem, and the right_state is the right end of the group, and all branches end their course in that state. We store those two integers to be queried for each branch, we build the NFA states for the contents #2 of the group, and we forget about the two integers. Once this is done, perform the repetition: either exactly #3 times, or #3 or more times, or between #3 and #3 + #4 times, with lazyness #5. The <label> #1 is used for submatch tracking. Each of the three auxiliaries expects left_state and right_state to be set properly.

```

25567 \cs_new_protected:Npn \__regex_group_aux:nnnnN #1#2#3#4#5
25568 {
25569 \if_int_compare:w #3 = 0 \exp_stop_f:
25570 \__regex_build_new_state:
25571 (assert)\assert_int:n { \l__regex_max_state_int = \l__regex_right_state_int + 1 }
25572 \__regex_build_transition_right:nNn \__regex_action_free_group:n

```

```

25573         \l__regex_left_state_int \l__regex_right_state_int
25574     \fi:
25575     \__regex_build_new_state:
25576     \__regex_push_lr_states:
25577     #2
25578     \__regex_pop_lr_states:
25579     \if_case:w - #4 \exp_stop_f:
25580         \__regex_group_repeat:nn {#1} {#3}
25581     \or: \__regex_group_repeat:nnN {#1} {#3} #5
25582     \else: \__regex_group_repeat:nnnN {#1} {#3} {#4} #5
25583     \fi:
25584 }

```

(End definition for __regex_group_aux:nnnnN.)

__regex_group:nnnN Hand to __regex_group_aux:nnnnN the label of that group (expanded), and the group itself, with some extra commands to perform.

__regex_group_no_capture:nnnN

```

25585 \cs_new_protected:Npn \__regex_group:nnnN #1
25586 {
25587     \exp_args:No \__regex_group_aux:nnnnN
25588     { \int_use:N \l__regex_capturing_group_int }
25589     {
25590         \int_incr:N \l__regex_capturing_group_int
25591         #1
25592     }
25593 }
25594 \cs_new_protected:Npn \__regex_group_no_capture:nnnN
25595 { \__regex_group_aux:nnnnN { -1 } }

```

(End definition for __regex_group:nnnN and __regex_group_no_capture:nnnN.)

__regex_group_resetting:nnnN
__regex_group_resetting_loop:nnNn

Again, hand the label -1 to __regex_group_aux:nnnnN, but this time we work a little bit harder to keep track of the maximum group label at the end of any branch, and to reset the group number at each branch. This relies on the fact that a compiled regex always is a sequence of items of the form __regex_branch:n {<branch>}.

```

25596 \cs_new_protected:Npn \__regex_group_resetting:nnnN #1
25597 {
25598     \__regex_group_aux:nnnnN { -1 }
25599     {
26000         \exp_args:Noo \__regex_group_resetting_loop:nnNn
26001         { \int_use:N \l__regex_capturing_group_int }
26002         { \int_use:N \l__regex_capturing_group_int }
26003         #1
26004         { ?? \prg_break:n } { }
26005         \prg_break_point:
26006     }
26007 }
26008 \cs_new_protected:Npn \__regex_group_resetting_loop:nnNn #1#2#3#4
26009 {
26010     \use_none:nn #3 { \int_set:Nn \l__regex_capturing_group_int {#1} }
26011     \int_set:Nn \l__regex_capturing_group_int {#2}
26012     #3 {#4}
26013     \exp_args:Nf \__regex_group_resetting_loop:nnNn
26014     { \int_max:nn {#1} { \l__regex_capturing_group_int } }

```

```

25615     {#2}
25616 }

```

(End definition for `_regex_group_resetting:nnnN` and `_regex_group_resetting_loop:nnNn`.)

`_regex_branch:n` Add a free transition from the left state of the current group to a brand new state, starting point of this branch. Once the branch is built, add a transition from its last state to the right state of the group. The left and right states of the group are extracted from the relevant sequences.

```

25617 \cs_new_protected:Npn \_regex_branch:n #1
25618 {
25619   \_regex_build_new_state:
25620   \seq_get:NN \l__regex_left_state_seq \l__regex_internal_a_tl
25621   \int_set:Nn \l__regex_left_state_int \l__regex_internal_a_tl
25622   \_regex_build_transition_right:nNn \_regex_action_free:n
25623     \l__regex_left_state_int \l__regex_right_state_int
25624   #1
25625   \seq_get:NN \l__regex_right_state_seq \l__regex_internal_a_tl
25626   \_regex_build_transition_right:nNn \_regex_action_free:n
25627     \l__regex_right_state_int \l__regex_internal_a_tl
25628 }

```

(End definition for `_regex_branch:n`.)

`_regex_group_repeat:nn` This function is called to repeat a group a fixed number of times `#2`; if this is 0 we remove the group altogether (but don't reset the `capturing_group` label). Otherwise, the auxiliary `_regex_group_repeat_aux:n` copies `#2` times the `\toks` for the group, and leaves `internal_a` pointing to the left end of the last repetition. We only record the submatch information at the last repetition. Finally, add a state at the end (the transition to it has been taken care of by the replicating auxiliary).

```

25629 \cs_new_protected:Npn \_regex_group_repeat:nn #1#2
25630 {
25631   \if_int_compare:w #2 = 0 \exp_stop_f:
25632     \int_set:Nn \l__regex_max_state_int
25633       { \l__regex_left_state_int - 1 }
25634     \_regex_build_new_state:
25635   \else:
25636     \_regex_group_repeat_aux:n {#2}
25637     \_regex_group_submatches:nnn {#1}
25638     \l__regex_internal_a_int \l__regex_right_state_int
25639     \_regex_build_new_state:
25640   \fi:
25641 }

```

(End definition for `_regex_group_repeat:nn`.)

`_regex_group_submatches:nnn` This inserts in states `#2` and `#3` the code for tracking submatches of the group `#1`, unless inhibited by a label of `-1`.

```

25642 \cs_new_protected:Npn \_regex_group_submatches:nnn #1#2#3
25643 {
25644   \if_int_compare:w #1 > - 1 \exp_stop_f:
25645     \_regex_toks_put_left:Nx #2 { \_regex_action_submatch:n { #1 < } }
25646     \_regex_toks_put_left:Nx #3 { \_regex_action_submatch:n { #1 > } }
25647   \fi:
25648 }

```


(End definition for `_regex_group_submatches:nnN`.)

`_regex_group_repeat_aux:n` Here we repeat `\toks` ranging from `left_state` to `max_state`, `#1 > 0` times. First add a transition so that the copies “chain” properly. Compute the shift `c` between the original copy and the last copy we want. Shift the `right_state` and `max_state` to their final values. We then want to perform `c` copy operations. At the end, `b` is equal to the `max_state`, and `a` points to the left of the last copy of the group.

```

25649 \cs_new_protected:Npn \_regex_group_repeat_aux:n #1
25650 {
25651   \_regex_build_transition_right:nNn \_regex_action_free:n
25652   \l__regex_right_state_int \l__regex_max_state_int
25653   \int_set_eq:NN \l__regex_internal_a_int \l__regex_left_state_int
25654   \int_set_eq:NN \l__regex_internal_b_int \l__regex_max_state_int
25655   \if_int_compare:w \int_eval:n {#1} > 1 \exp_stop_f:
25656     \int_set:Nn \l__regex_internal_c_int
25657     {
25658       ( #1 - 1 )
25659       * ( \l__regex_internal_b_int - \l__regex_internal_a_int )
25660     }
25661     \int_add:Nn \l__regex_right_state_int { \l__regex_internal_c_int }
25662     \int_add:Nn \l__regex_max_state_int { \l__regex_internal_c_int }
25663     \_regex_toks_memcpy:NNn
25664     \l__regex_internal_b_int
25665     \l__regex_internal_a_int
25666     \l__regex_internal_c_int
25667   \fi:
25668 }

```

(End definition for `_regex_group_repeat_aux:n`.)

`_regex_group_repeat:nnN` This function is called to repeat a group at least n times; the case $n = 0$ is very different from $n > 0$. Assume first that $n = 0$. Insert submatch tracking information at the start and end of the group, add a free transition from the right end to the “true” left state `a` (remember: in this case we had added an extra state before the left state). This forms the loop, which we break away from by adding a free transition from `a` to a new state.

Now consider the case $n > 0$. Repeat the group n times, chaining various copies with a free transition. Add submatch tracking only to the last copy, then add a free transition from the right end back to the left end of the last copy, either before or after the transition to move on towards the rest of the NFA. This transition can end up before submatch tracking, but that is irrelevant since it only does so when going again through the group, recording new matches. Finally, add a state; we already have a transition pointing to it from `_regex_group_repeat_aux:n`.

```

25669 \cs_new_protected:Npn \_regex_group_repeat:nnN #1#2#3
25670 {
25671   \if_int_compare:w #2 = 0 \exp_stop_f:
25672     \_regex_group_submatches:nnN {#1}
25673     \l__regex_left_state_int \l__regex_right_state_int
25674     \int_set:Nn \l__regex_internal_a_int
25675     { \l__regex_left_state_int - 1 }
25676     \_regex_build_transition_right:nNn \_regex_action_free:n
25677     \l__regex_right_state_int \l__regex_internal_a_int
25678     \_regex_build_new_state:
25679     \if_meaning:w \c_true_bool #3

```

```

25680     \__regex_build_transition_left:NNN \__regex_action_free:n
25681     \l__regex_internal_a_int \l__regex_right_state_int
25682 \else:
25683     \__regex_build_transition_right:nNn \__regex_action_free:n
25684     \l__regex_internal_a_int \l__regex_right_state_int
25685 \fi:
25686 \else:
25687     \__regex_group_repeat_aux:n {#2}
25688     \__regex_group_submatches:nNN {#1}
25689     \l__regex_internal_a_int \l__regex_right_state_int
25690 \if_meaning:w \c_true_bool #3
25691     \__regex_build_transition_right:nNn \__regex_action_free_group:n
25692     \l__regex_right_state_int \l__regex_internal_a_int
25693 \else:
25694     \__regex_build_transition_left:NNN \__regex_action_free_group:n
25695     \l__regex_right_state_int \l__regex_internal_a_int
25696 \fi:
25697 \__regex_build_new_state:
25698 \fi:
25699 }

```

(End definition for __regex_group_repeat:nnN.)

__regex_group_repeat:nnnN

We wish to repeat the group between #2 and #2 + #3 times, with a lazyness controlled by #4. We insert submatch tracking up front: in principle, we could avoid recording submatches for the first #2 copies of the group, but that forces us to treat specially the case #2 = 0. Repeat that group with submatch tracking #2 + #3 times (the maximum number of repetitions). Then our goal is to add #3 transitions from the end of the #2-th group, and each subsequent groups, to the end. For a lazy quantifier, we add those transitions to the left states, before submatch tracking. For the greedy case, we add the transitions to the right states, after submatch tracking and the transitions which go on with more repetitions. In the greedy case with #2 = 0, the transition which skips over all copies of the group must be added separately, because its starting state does not follow the normal pattern: we had to add it “by hand” earlier.

```

25700 \cs_new_protected:Npn \__regex_group_repeat:nnnN #1#2#3#4
25701 {
25702     \__regex_group_submatches:nNN {#1}
25703     \l__regex_left_state_int \l__regex_right_state_int
25704     \__regex_group_repeat_aux:n { #2 + #3 }
25705     \if_meaning:w \c_true_bool #4
25706     \int_set_eq:NN \l__regex_left_state_int \l__regex_max_state_int
25707     \prg_replicate:nn { #3 }
25708     {
25709         \int_sub:Nn \l__regex_left_state_int
25710         { \l__regex_internal_b_int - \l__regex_internal_a_int }
25711         \__regex_build_transition_left:NNN \__regex_action_free:n
25712         \l__regex_left_state_int \l__regex_max_state_int
25713     }
25714 \else:
25715     \prg_replicate:nn { #3 - 1 }
25716     {
25717         \int_sub:Nn \l__regex_right_state_int
25718         { \l__regex_internal_b_int - \l__regex_internal_a_int }

```

```

25719         \__regex_build_transition_right:nNn \__regex_action_free:n
25720         \l__regex_right_state_int \l__regex_max_state_int
25721     }
25722     \if_int_compare:w #2 = 0 \exp_stop_f:
25723         \int_set:Nn \l__regex_right_state_int
25724         { \l__regex_left_state_int - 1 }
25725     \else:
25726         \int_sub:Nn \l__regex_right_state_int
25727         { \l__regex_internal_b_int - \l__regex_internal_a_int }
25728     \fi:
25729     \__regex_build_transition_right:nNn \__regex_action_free:n
25730     \l__regex_right_state_int \l__regex_max_state_int
25731 \fi:
25732 \__regex_build_new_state:
25733 }

```

(End definition for __regex_group_repeat:nnnN.)

40.4.6 Others

__regex_assertion:Nn Usage: __regex_assertion:Nn *<boolean>* {*<test>*}, where the *<test>* is either of the two other functions. Add a free transition to a new state, conditionally to the assertion test.

__regex_b_test: The __regex_b_test: test is used by the \b and \B escape: check if the last character was a word character or not, and do the same to the current character. The boundary-markers of the string are non-word characters for this purpose. Anchors at the start or end of match use __regex_anchor:N, with a position controlled by the integer #1.

```

25734 \cs_new_protected:Npn \__regex_assertion:Nn #1#2
25735 {
25736     \__regex_build_new_state:
25737     \__regex_toks_put_right:Nx \l__regex_left_state_int
25738     {
25739         \exp_not:n {#2}
25740         \__regex_break_point:TF
25741         \bool_if:NF #1 { { } }
25742         {
25743             \__regex_action_free:n
25744             {
25745                 \int_eval:n
25746                 { \l__regex_right_state_int - \l__regex_left_state_int }
25747             }
25748         }
25749         \bool_if:NT #1 { { } }
25750     }
25751 }
25752 \cs_new_protected:Npn \__regex_anchor:N #1
25753 {
25754     \if_int_compare:w #1 = \l__regex_curr_pos_int
25755         \exp_after:wN \__regex_break_true:w
25756     \fi:
25757 }
25758 \cs_new_protected:Npn \__regex_b_test:
25759 {
25760     \group_begin:
25761     \int_set_eq:NN \l__regex_curr_char_int \l__regex_last_char_int

```

```

25762     \__regex_prop_w:
25763     \__regex_break_point:TF
25764     { \group_end: \__regex_item_reverse:n \__regex_prop_w: }
25765     { \group_end: \__regex_prop_w: }
25766 }

```

(End definition for __regex_assertion:Nn, __regex_b_test:, and __regex_anchor:N.)

__regex_command_K: Change the starting point of the 0-th submatch (full match), and transition to a new state, pretending that this is a fresh thread.

```

25767 \cs_new_protected:Npn \__regex_command_K:
25768 {
25769     \__regex_build_new_state:
25770     \__regex_toks_put_right:Nx \l__regex_left_state_int
25771     {
25772         \__regex_action_submatch:n { 0< }
25773         \bool_set_true:N \l__regex_fresh_thread_bool
25774         \__regex_action_free:n
25775         {
25776             \int_eval:n
25777             { \l__regex_right_state_int - \l__regex_left_state_int }
25778         }
25779         \bool_set_false:N \l__regex_fresh_thread_bool
25780     }
25781 }

```

(End definition for __regex_command_K:.)

40.5 Matching

We search for matches by running all the execution threads through the NFA in parallel, reading one token of the query at each step. The NFA contains “free” transitions to other states, and transitions which “consume” the current token. For free transitions, the instruction at the new state of the NFA is performed immediately. When a transition consumes a character, the new state is appended to a list of “active states”, stored in `\g__regex_thread_state_intarray`: this thread is made active again when the next token is read from the query. At every step (for each token in the query), we unpack that list of active states and the corresponding submatch props, and empty those.

If two paths through the NFA “collide” in the sense that they reach the same state after reading a given token, then they only differ in how they previously matched, and any future execution would be identical for both. (Note that this would be wrong in the presence of back-references.) Hence, we only need to keep one of the two threads: the thread with the highest priority. Our NFA is built in such a way that higher priority actions always come before lower priority actions, which makes things work.

The explanation in the previous paragraph may make us think that we simply need to keep track of which states were visited at a given step: after all, the loop generated when matching `(a?)*` against `a` is broken, isn’t it? No. The group first matches `a`, as it should, then repeats; it attempts to match `a` again but fails; it skips `a`, and finds out that this state has already been seen at this position in the query: the match stops. The capturing group is (wrongly) `a`. What went wrong is that a thread collided with itself, and the later version, which has gone through the group one more times with an empty match, should have a higher priority than not going through the group.

We solve this by distinguishing “normal” free transitions `__regex_action_free:n` from transitions `__regex_action_free_group:n` which go back to the start of the group. The former keeps threads unless they have been visited by a “completed” thread, while the latter kind of transition also prevents going back to a state visited by the current thread.

40.5.1 Variables used when matching

`\l__regex_min_pos_int` The tokens in the query are indexed from `min_pos` for the first to `max_pos - 1` for the last, and their information is stored in several arrays and `\toks` registers with those numbers.
`\l__regex_max_pos_int` We don’t start from 0 because the `\toks` registers with low numbers are used to hold the states of the NFA. We match without backtracking, keeping all threads in lockstep
`\l__regex_curr_pos_int` at the `current_pos` in the query. The starting point of the current match attempt is
`\l__regex_start_pos_int` `start_pos`, and `success_pos`, updated whenever a thread succeeds, is used as the next
`\l__regex_success_pos_int` starting position.

```
25782 \int_new:N \l__regex_min_pos_int
25783 \int_new:N \l__regex_max_pos_int
25784 \int_new:N \l__regex_curr_pos_int
25785 \int_new:N \l__regex_start_pos_int
25786 \int_new:N \l__regex_success_pos_int
```

(End definition for `\l__regex_min_pos_int` and others.)

`\l__regex_curr_char_int` The character and category codes of the token at the current position; the character code
`\l__regex_curr_catcode_int` of the token at the previous position; and the character code of the result of changing the
`\l__regex_last_char_int` case of the current token (`A-Z↔a-z`). This last integer is only computed when necessary,
`\l__regex_case_changed_char_int` and is otherwise `\c_max_int`. The `current_char` variable is also used in various other
phases to hold a character code.

```
25787 \int_new:N \l__regex_curr_char_int
25788 \int_new:N \l__regex_curr_catcode_int
25789 \int_new:N \l__regex_last_char_int
25790 \int_new:N \l__regex_case_changed_char_int
```

(End definition for `\l__regex_curr_char_int` and others.)

`\l__regex_curr_state_int` For every character in the token list, each of the active states is considered in turn. The variable `\l__regex_curr_state_int` holds the state of the NFA which is currently considered: transitions are then given as shifts relative to the current state.

```
25791 \int_new:N \l__regex_curr_state_int
```

(End definition for `\l__regex_curr_state_int`.)

`\l__regex_curr_submatches_prop` The submatches for the thread which is currently active are stored in the `current_submatches` property list variable. This property list is stored by `__regex_action_cost:n` into the `\toks` register for the target state of the transition, to be retrieved when matching at the next position. When a thread succeeds, this property list is copied to `\l__regex_success_submatches_prop`: only the last successful thread remains there.

```
25792 \prop_new:N \l__regex_curr_submatches_prop
25793 \prop_new:N \l__regex_success_submatches_prop
```

(End definition for `\l__regex_curr_submatches_prop` and `\l__regex_success_submatches_prop`.)

`\l__regex_step_int` This integer, always even, is increased every time a character in the query is read, and not reset when doing multiple matches. We store in `\g__regex_state_active_intarray` the last step in which each `<state>` in the NFA was encountered. This lets us break infinite loops by not visiting the same state twice in the same step. In fact, the step we store is equal to `step` when we have started performing the operations of `\toks<state>`, but not finished yet. However, once we finish, we store `step + 1` in `\g__regex_state_active_intarray`. This is needed to track submatches properly (see building phase). The `step` is also used to attach each set of submatch information to a given iteration (and automatically discard it when it corresponds to a past step).

```
25794 \int_new:N \l__regex_step_int
```

(End definition for `\l__regex_step_int`.)

`\l__regex_min_active_int` All the currently active threads are kept in order of precedence in `\g__regex_thread_state_intarray`, and the corresponding submatches in the `\toks`. For our purposes, those serve as an array, indexed from `min_active` (inclusive) to `max_active` (excluded).
`\l__regex_max_active_int` At the start of every step, the whole array is unpacked, so that the space can immediately be reused, and `max_active` is reset to `min_active`, effectively clearing the array.

```
25795 \int_new:N \l__regex_min_active_int
```

```
25796 \int_new:N \l__regex_max_active_int
```

(End definition for `\l__regex_min_active_int` and `\l__regex_max_active_int`.)

`\g__regex_state_active_intarray` `\g__regex_state_active_intarray` stores the last `<step>` in which each `<state>` was active.
`\g__regex_thread_state_intarray` `\g__regex_thread_state_intarray` stores threads to be considered in the next step, more precisely the states in which these threads are.

```
25797 \intarray_new:Nn \g__regex_state_active_intarray { 65536 }
```

```
25798 \intarray_new:Nn \g__regex_thread_state_intarray { 65536 }
```

(End definition for `\g__regex_state_active_intarray` and `\g__regex_thread_state_intarray`.)

`\l__regex_every_match_tl` Every time a match is found, this token list is used. For single matching, the token list is empty. For multiple matching, the token list is set to repeat the matching, after performing some operation which depends on the user function. See `__regex_single_match:` and `__regex_multi_match:n`.

```
25799 \tl_new:N \l__regex_every_match_tl
```

(End definition for `\l__regex_every_match_tl`.)

`\l__regex_fresh_thread_bool` When doing multiple matches, we need to avoid infinite loops where each iteration matches the same empty token list. When an empty token list is matched, the next successful match of the same empty token list is suppressed. We detect empty matches by setting `\l__regex_fresh_thread_bool` to `true` for threads which directly come from the start of the regex or from the `\K` command, and testing that boolean whenever a thread succeeds. The function `__regex_if_two_empty_matches:F` is redefined at every match attempt, depending on whether the previous match was empty or not: if it was, then the function must cancel a purported success if it is empty and at the same spot as the previous match; otherwise, we definitely don't have two identical empty matches, so the function is `\use:n`.

```
25800 \bool_new:N \l__regex_fresh_thread_bool
```

```
25801 \bool_new:N \l__regex_empty_success_bool
```

```
25802 \cs_new_eq:NN \__regex_if_two_empty_matches:F \use:n
```

(End definition for `\l__regex_fresh_thread_bool`, `\l__regex_empty_success_bool`, and `_regex_if_two_empty_matches:F`.)

`\g__regex_success_bool` The boolean `\l__regex_match_success_bool` is true if the current match attempt was successful, and `\g__regex_success_bool` is true if there was at least one successful match. This is the only global variable in this whole module, but we would need it to be local when matching a control sequence with `\c{...}`. This is done by saving the global variable into `\l__regex_saved_success_bool`, which is local, hence not affected by the changes due to inner regex functions.

```
25803 \bool_new:N \g__regex_success_bool
25804 \bool_new:N \l__regex_saved_success_bool
25805 \bool_new:N \l__regex_match_success_bool
```

(End definition for `\g__regex_success_bool`, `\l__regex_saved_success_bool`, and `\l__regex_match_success_bool`.)

40.5.2 Matching: framework

`__regex_match:n` First store the query into `\toks` registers and arrays (see `__regex_query_set:nnn`).
`__regex_match_cs:n` Then initialize the variables that should be set once for each user function (even for
`__regex_match_init:` multiple matches). Namely, the overall matching is not yet successful; none of the states should be marked as visited (`\g__regex_state_active_intarray`), and we start at step 0; we pretend that there was a previous match ending at the start of the query, which was not empty (to avoid smothering an empty match at the start). Once all this is set up, we are ready for the ride. Find the first match.

```
25806 \cs_new_protected:Npn \__regex_match:n #1
25807 {
25808   \int_zero:N \l__regex_balance_int
25809   \int_set:Nn \l__regex_curr_pos_int { 2 * \l__regex_max_state_int }
25810   \__regex_query_set:nnn { } { -1 } { -2 }
25811   \int_set_eq:NN \l__regex_min_pos_int \l__regex_curr_pos_int
25812   \tl_analysis_map_inline:nn {#1}
25813     { \__regex_query_set:nnn {##1} {"##3"} {##2} }
25814   \int_set_eq:NN \l__regex_max_pos_int \l__regex_curr_pos_int
25815   \__regex_query_set:nnn { } { -1 } { -2 }
25816   \__regex_match_init:
25817   \__regex_match_once:
25818 }
25819 \cs_new_protected:Npn \__regex_match_cs:n #1
25820 {
25821   \int_zero:N \l__regex_balance_int
25822   \int_set:Nn \l__regex_curr_pos_int
25823     {
25824       \int_max:nn { 2 * \l__regex_max_state_int - \l__regex_min_state_int }
25825       { \l__regex_max_pos_int }
25826       + 1
25827     }
25828   \__regex_query_set:nnn { } { -1 } { -2 }
25829   \int_set_eq:NN \l__regex_min_pos_int \l__regex_curr_pos_int
25830   \str_map_inline:nn {#1}
25831     {
25832       \__regex_query_set:nnn { \exp_not:n {##1} }
25833       { \tl_if_blank:nTF {##1} { 10 } { 12 } }
```

```

25834         { '##1' }
25835     }
25836     \int_set_eq:NN \l__regex_max_pos_int \l__regex_curr_pos_int
25837     \__regex_query_set:nnn { } { -1 } { -2 }
25838     \__regex_match_init:
25839     \__regex_match_once:
25840 }
25841 \cs_new_protected:Npn \__regex_match_init:
25842 {
25843     \bool_gset_false:N \g__regex_success_bool
25844     \int_step_inline:nnn
25845         \l__regex_min_state_int { \l__regex_max_state_int - 1 }
25846     {
25847         \__kernel_intarray_gset:Nnn
25848         \g__regex_state_active_intarray {##1} { 1 }
25849     }
25850     \int_set_eq:NN \l__regex_min_active_int \l__regex_max_state_int
25851     \int_zero:N \l__regex_step_int
25852     \int_set_eq:NN \l__regex_success_pos_int \l__regex_min_pos_int
25853     \int_set:Nn \l__regex_min_submatch_int
25854         { 2 * \l__regex_max_state_int }
25855     \int_set_eq:NN \l__regex_submatch_int \l__regex_min_submatch_int
25856     \bool_set_false:N \l__regex_empty_success_bool
25857 }

```

(End definition for `__regex_match:n`, `__regex_match_cs:n`, and `__regex_match_init:.`)

`__regex_match_once:` This function finds one match, then does some action defined by the `every_match` token list, which may recursively call `__regex_match_once:.` First initialize some variables: set the conditional which detects identical empty matches; this match attempt starts at the previous `success_pos`, is not yet successful, and has no submatches yet; clear the array of active threads, and put the starting state 0 in it. We are then almost ready to read our first token in the query, but we actually start one position earlier than the start, and `get` that token, to set `last_char` properly for word boundaries. Then call `__regex_match_loop:`, which runs through the query until the end or until a successful match breaks early.

```

25858 \cs_new_protected:Npn \__regex_match_once:
25859 {
25860     \if_meaning:w \c_true_bool \l__regex_empty_success_bool
25861     \cs_set:Npn \__regex_if_two_empty_matches:F
25862     {
25863         \int_compare:nNnF
25864             \l__regex_start_pos_int = \l__regex_curr_pos_int
25865     }
25866     \else:
25867     \cs_set_eq:NN \__regex_if_two_empty_matches:F \use:n
25868     \fi:
25869     \int_set_eq:NN \l__regex_start_pos_int \l__regex_success_pos_int
25870     \bool_set_false:N \l__regex_match_success_bool
25871     \prop_clear:N \l__regex_curr_submatches_prop
25872     \int_set_eq:NN \l__regex_max_active_int \l__regex_min_active_int
25873     \__regex_store_state:n { \l__regex_min_state_int }
25874     \int_set:Nn \l__regex_curr_pos_int
25875         { \l__regex_start_pos_int - 1 }

```



```

25876     \__regex_query_get:
25877     \__regex_match_loop:
25878     \l__regex_every_match_tl
25879 }

```

(End definition for __regex_match_once:.)

__regex_single_match: For a single match, the overall success is determined by whether the only match attempt is a success. When doing multiple matches, the overall matching is successful as soon as any match succeeds. Perform the action #1, then find the next match.

```

25880 \cs_new_protected:Npn \__regex_single_match:
25881 {
25882     \tl_set:Nn \l__regex_every_match_tl
25883     {
25884         \bool_gset_eq:NN
25885         \g__regex_success_bool
25886         \l__regex_match_success_bool
25887     }
25888 }
25889 \cs_new_protected:Npn \__regex_multi_match:n #1
25890 {
25891     \tl_set:Nn \l__regex_every_match_tl
25892     {
25893         \if_meaning:w \c_true_bool \l__regex_match_success_bool
25894         \bool_gset_true:N \g__regex_success_bool
25895         #1
25896         \exp_after:wN \__regex_match_once:
25897     \fi:
25898 }
25899 }

```

(End definition for __regex_single_match: and __regex_multi_match:n.)

__regex_match_loop: At each new position, set some variables and get the new character and category from the query. Then unpack the array of active threads, and clear it by resetting its length (max_active). This results in a sequence of __regex_use_state_and_submatches:nn {<state>} {<prop>}, and we consider those states one by one in order. As soon as a thread succeeds, exit the step, and, if there are threads to consider at the next position, and we have not reached the end of the string, repeat the loop. Otherwise, the last thread that succeeded is what __regex_match_once: matches. We explain the fresh_thread business when describing __regex_action_wildcard:.

```

25900 \cs_new_protected:Npn \__regex_match_loop:
25901 {
25902     \int_add:Nn \l__regex_step_int { 2 }
25903     \int_incr:N \l__regex_curr_pos_int
25904     \int_set_eq:NN \l__regex_last_char_int \l__regex_curr_char_int
25905     \int_set_eq:NN \l__regex_case_changed_char_int \c_max_int
25906     \__regex_query_get:
25907     \use:x
25908     {
25909         \int_set_eq:NN \l__regex_max_active_int \l__regex_min_active_int
25910         \int_step_function:nnN
25911         { \l__regex_min_active_int }
25912         { \l__regex_max_active_int - 1 }

```

```

25913         \_regex_match_one_active:n
25914     }
25915     \prg_break_point:
25916     \bool_set_false:N \l__regex_fresh_thread_bool
25917     \if_int_compare:w \l__regex_max_active_int > \l__regex_min_active_int
25918         \if_int_compare:w \l__regex_curr_pos_int < \l__regex_max_pos_int
25919             \exp_after:wN \exp_after:wN \exp_after:wN \_regex_match_loop:
25920         \fi:
25921     \fi:
25922 }
25923 \cs_new:Npn \_regex_match_one_active:n #1
25924 {
25925     \_regex_use_state_and_submatches:nn
25926     { \_kernel_intarray_item:Nn \g__regex_thread_state_intarray {#1} }
25927     { \_regex_toks_use:w #1 }
25928 }

```

(End definition for _regex_match_loop: and _regex_match_one_active:n.)

_regex_query_set:nnn The arguments are: tokens that o and x expand to one token of the query, the catcode, and the character code. Store those, and the current brace balance (used later to check for overall brace balance) in a \toks register and some arrays, then update the balance.

```

25929 \cs_new_protected:Npn \_regex_query_set:nnn #1#2#3
25930 {
25931     \_kernel_intarray_gset:Nnn \g__regex_charcode_intarray
25932     { \l__regex_curr_pos_int } {#3}
25933     \_kernel_intarray_gset:Nnn \g__regex_catcode_intarray
25934     { \l__regex_curr_pos_int } {#2}
25935     \_kernel_intarray_gset:Nnn \g__regex_balance_intarray
25936     { \l__regex_curr_pos_int } { \l__regex_balance_int }
25937     \_regex_toks_set:Nn \l__regex_curr_pos_int {#1}
25938     \int_incr:N \l__regex_curr_pos_int
25939     \if_case:w #2 \exp_stop_f:
25940     \or: \int_incr:N \l__regex_balance_int
25941     \or: \int_decr:N \l__regex_balance_int
25942     \fi:
25943 }

```

(End definition for _regex_query_set:nnn.)

_regex_query_get: Extract the current character and category codes at the current position from the appropriate arrays.

```

25944 \cs_new_protected:Npn \_regex_query_get:
25945 {
25946     \l__regex_curr_char_int
25947     = \_kernel_intarray_item:Nn \g__regex_charcode_intarray
25948     { \l__regex_curr_pos_int } \scan_stop:
25949     \l__regex_curr_catcode_int
25950     = \_kernel_intarray_item:Nn \g__regex_catcode_intarray
25951     { \l__regex_curr_pos_int } \scan_stop:
25952 }

```

(End definition for _regex_query_get:.)

40.5.3 Using states of the nfa

`__regex_use_state:` Use the current NFA instruction. The state is initially marked as belonging to the current **step**: this allows normal free transition to repeat, but group-repeating transitions won't. Once we are done exploring all the branches it spawned, the state is marked as **step + 1**: any thread hitting it at that point will be terminated.

```
25953 \cs_new_protected:Npn \__regex_use_state:
25954 {
25955   \__kernel_intarray_gset:Nnn \g__regex_state_active_intarray
25956     { \l__regex_curr_state_int } { \l__regex_step_int }
25957   \__regex_toks_use:w \l__regex_curr_state_int
25958   \__kernel_intarray_gset:Nnn \g__regex_state_active_intarray
25959     { \l__regex_curr_state_int }
25960     { \int_eval:n { \l__regex_step_int + 1 } }
25961 }
```

(End definition for `__regex_use_state:.`)

`__regex_use_state_and_submatches:nn` This function is called as one item in the array of active threads after that array has been unpacked for a new step. Update the `current_state` and `current_submatches` and use the state if it has not yet been encountered at this step.

```
25962 \cs_new_protected:Npn \__regex_use_state_and_submatches:nn #1 #2
25963 {
25964   \int_set:Nn \l__regex_curr_state_int {#1}
25965   \if_int_compare:w
25966     \__kernel_intarray_item:Nn \g__regex_state_active_intarray
25967       { \l__regex_curr_state_int }
25968     < \l__regex_step_int
25969     \tl_set:Nn \l__regex_curr_submatches_prop {#2}
25970     \exp_after:wN \__regex_use_state:
25971   \fi:
25972   \scan_stop:
25973 }
```

(End definition for `__regex_use_state_and_submatches:nn.`)

40.5.4 Actions when matching

`__regex_action_start_wildcard:` For an unanchored match, state 0 has a free transition to the next and a costly one to itself, to repeat at the next position. To catch repeated identical empty matches, we need to know if a successful thread corresponds to an empty match. The instruction resetting `\l__regex_fresh_thread_bool` may be skipped by a successful thread, hence we had to add it to `__regex_match_loop:` too.

```
25974 \cs_new_protected:Npn \__regex_action_start_wildcard:
25975 {
25976   \bool_set_true:N \l__regex_fresh_thread_bool
25977   \__regex_action_free:n {1}
25978   \bool_set_false:N \l__regex_fresh_thread_bool
25979   \__regex_action_cost:n {0}
25980 }
```

(End definition for `__regex_action_start_wildcard:.`)

`__regex_action_free:n` These functions copy a thread after checking that the NFA state has not already been used
`__regex_action_free_group:n` at this position. If not, store submatches in the new state, and insert the instructions for
`__regex_action_free_aux:nn` that state in the input stream. Then restore the old value of `\l__regex_curr_state_int`
and of the current submatches. The two types of free transitions differ by how they
test that the state has not been encountered yet: the `group` version is stricter, and will
not use a state if it was used earlier in the current thread, hence forcefully breaking the
loop, while the “normal” version will revisit a state even within the thread itself.

```

25981 \cs_new_protected:Npn __regex_action_free:n
25982 { __regex_action_free_aux:nn { > \l__regex_step_int \else: } }
25983 \cs_new_protected:Npn __regex_action_free_group:n
25984 { __regex_action_free_aux:nn { < \l__regex_step_int } }
25985 \cs_new_protected:Npn __regex_action_free_aux:nn #1#2
25986 {
25987   \use:x
25988   {
25989     \int_add:Nn \l__regex_curr_state_int {#2}
25990     \exp_not:n
25991     {
25992       \if_int_compare:w
25993         __kernel_intarray_item:Nn \g__regex_state_active_intarray
25994         { \l__regex_curr_state_int }
25995         #1
25996         \exp_after:wN __regex_use_state:
25997       \fi:
25998     }
25999     \int_set:Nn \l__regex_curr_state_int
26000     { \int_use:N \l__regex_curr_state_int }
26001     \tl_set:Nn \exp_not:N \l__regex_curr_submatches_prop
26002     { \exp_not:o \l__regex_curr_submatches_prop }
26003   }
26004 }

```

(End definition for `__regex_action_free:n`, `__regex_action_free_group:n`, and `__regex_action_free_aux:nn`.)

`__regex_action_cost:n` A transition which consumes the current character and shifts the state by #1. The
resulting state is stored in the appropriate array for use at the next position, and we also
store the current submatches.

```

26005 \cs_new_protected:Npn __regex_action_cost:n #1
26006 {
26007   \exp_args:Nx __regex_store_state:n
26008   { \int_eval:n { \l__regex_curr_state_int + #1 } }
26009 }

```

(End definition for `__regex_action_cost:n`.)

`__regex_store_state:n` Put the given state in `\g__regex_thread_state_intarray`, and increment the length of
`__regex_store_submatches:` the array. Also store the current submatch in the appropriate `\toks`.

```

26010 \cs_new_protected:Npn __regex_store_state:n #1
26011 {
26012   __regex_store_submatches:
26013   __kernel_intarray_gset:Nnn \g__regex_thread_state_intarray
26014   { \l__regex_max_active_int } {#1}
26015   \int_incr:N \l__regex_max_active_int

```

```

26016 }
26017 \cs_new_protected:Npn \__regex_store_submatches:
26018 {
26019     \__regex_toks_set:No \l__regex_max_active_int
26020     { \l__regex_curr_submatches_prop }
26021 }

```

(End definition for __regex_store_state:n and __regex_store_submatches:.)

__regex_disable_submatches: Some user functions don't require tracking submatches. We get a performance improvement by simply defining the relevant functions to remove their argument and do nothing with it.

```

26022 \cs_new_protected:Npn \__regex_disable_submatches:
26023 {
26024     \cs_set_protected:Npn \__regex_store_submatches: { }
26025     \cs_set_protected:Npn \__regex_action_submatch:n ##1 { }
26026 }

```

(End definition for __regex_disable_submatches:.)

__regex_action_submatch:n Update the current submatches with the information from the current position. Maybe a bottleneck.

```

26027 \cs_new_protected:Npn \__regex_action_submatch:n #1
26028 {
26029     \prop_put:Nno \l__regex_curr_submatches_prop {#1}
26030     { \int_use:N \l__regex_curr_pos_int }
26031 }

```

(End definition for __regex_action_submatch:n.)

__regex_action_success: There is a successful match when an execution path reaches the last state in the NFA, unless this marks a second identical empty match. Then mark that there was a successful match; it is empty if it is "fresh"; and we store the current position and submatches. The current step is then interrupted with \prg_break:, and only paths with higher precedence are pursued further. The values stored here may be overwritten by a later success of a path with higher precedence.

```

26032 \cs_new_protected:Npn \__regex_action_success:
26033 {
26034     \__regex_if_two_empty_matches:F
26035     {
26036         \bool_set_true:N \l__regex_match_success_bool
26037         \bool_set_eq:NN \l__regex_empty_success_bool
26038         \l__regex_fresh_thread_bool
26039         \int_set_eq:NN \l__regex_success_pos_int \l__regex_curr_pos_int
26040         \prop_set_eq:NN \l__regex_success_submatches_prop
26041         \l__regex_curr_submatches_prop
26042         \prg_break:
26043     }
26044 }

```

(End definition for __regex_action_success:.)

40.6 Replacement

40.6.1 Variables and helpers used in replacement

`\l_regex_replacement_csnames_int` The behaviour of closing braces inside a replacement text depends on whether a sequences `\c{` or `\u{` has been encountered. The number of “open” such sequences that should be closed by `}` is stored in `\l__regex_replacement_csnames_int`, and decreased by 1 by each `}`.

```
26045 \int_new:N \l__regex_replacement_csnames_int
```

(End definition for `\l__regex_replacement_csnames_int`.)

`\l_regex_replacement_category_tl` This sequence of letters is used to correctly restore categories in nested constructions such as `\cL(abc\cD(_)d)`.

`\l_regex_replacement_category_seq`

```
26046 \tl_new:N \l__regex_replacement_category_tl
```

```
26047 \seq_new:N \l__regex_replacement_category_seq
```

(End definition for `\l__regex_replacement_category_tl` and `\l__regex_replacement_category_seq`.)

`\l__regex_balance_tl` This token list holds the replacement text for `__regex_replacement_balance_one_match:n` while it is being built incrementally.

```
26048 \tl_new:N \l__regex_balance_tl
```

(End definition for `\l__regex_balance_tl`.)

`__regex_replacement_balance_one_match:n` This expects as an argument the first index of a set of entries in `\g__regex_submatch_begin_intarray` (and related arrays) which hold the submatch information for a given match. It can be used within an integer expression to obtain the brace balance incurred by performing the replacement on that match. This combines the braces lost by removing the match, braces added by all the submatches appearing in the replacement, and braces appearing explicitly in the replacement. Even though it is always redefined before use, we initialize it as for an empty replacement. An important property is that concatenating several calls to that function must result in a valid integer expression (hence a leading + in the actual definition).

```
26049 \cs_new:Npn \__regex_replacement_balance_one_match:n #1
```

```
26050 { - \__regex_submatch_balance:n {#1} }
```

(End definition for `__regex_replacement_balance_one_match:n`.)

`__regex_replacement_do_one_match:n` The input is the same as `__regex_replacement_balance_one_match:n`. This function is redefined to expand to the part of the token list from the end of the previous match to a given match, followed by the replacement text. Hence concatenating the result of this function with all possible arguments (one call for each match), as well as the range from the end of the last match to the end of the string, produces the fully replaced token list. The initialization does not matter, but (as an example) we set it as for an empty replacement.

```
26051 \cs_new:Npn \__regex_replacement_do_one_match:n #1
```

```
26052 {
```

```
26053   \__regex_query_range:nn
```

```
26054     { \__kernel_intarray_item:Nn \g__regex_submatch_prev_intarray {#1} }
```

```
26055     { \__kernel_intarray_item:Nn \g__regex_submatch_begin_intarray {#1} }
```

```
26056 }
```

(End definition for `__regex_replacement_do_one_match:n`.)

`_regex_replacement_exp_not:N` This function lets us navigate around the fact that the primitive `\exp_not:n` requires a braced argument. As far as I can tell, it is only needed if the user tries to include in the replacement text a control sequence set equal to a macro parameter character, such as `\c_parameter_token`. Indeed, within an x-expanding assignment, `\exp_not:N #` behaves as a single `#`, whereas `\exp_not:n {#}` behaves as a doubled `##`.

```
26057 \cs_new:Npn \_regex_replacement_exp_not:N #1 { \exp_not:n {#1} }
```

(End definition for `_regex_replacement_exp_not:N`.)

40.6.2 Query and brace balance

`_regex_query_range:nn` When it is time to extract submatches from the token list, the various tokens are stored in `\toks` registers numbered from `\l__regex_min_pos_int` inclusive to `\l__regex_max_pos_int` exclusive. The function `_regex_query_range:nn {<min>} {<max>}` unpacks registers from the position `<min>` to the position `<max> - 1` included. Once this is expanded, a second x-expansion results in the actual tokens from the query. That second expansion is only done by user functions at the very end of their operation, after checking (and correcting) the brace balance first.

```
26058 \cs_new:Npn \_regex_query_range:nn #1#2
26059 {
26060   \exp_after:wN \_regex_query_range_loop:ww
26061   \int_value:w \_regex_int_eval:w #1 \exp_after:wN ;
26062   \int_value:w \_regex_int_eval:w #2 ;
26063   \prg_break_point:
26064 }
26065 \cs_new:Npn \_regex_query_range_loop:ww #1 ; #2 ;
26066 {
26067   \if_int_compare:w #1 < #2 \exp_stop_f:
26068   \else:
26069     \exp_after:wN \prg_break:
26070   \fi:
26071   \_regex_toks_use:w #1 \exp_stop_f:
26072   \exp_after:wN \_regex_query_range_loop:ww
26073   \int_value:w \_regex_int_eval:w #1 + 1 ; #2 ;
26074 }
```

(End definition for `_regex_query_range:nn` and `_regex_query_range_loop:ww`.)

`_regex_query_submatch:n` Find the start and end positions for a given submatch (of a given match).

```
26075 \cs_new:Npn \_regex_query_submatch:n #1
26076 {
26077   \_regex_query_range:nn
26078   { \_kernel_intarray_item:Nn \g__regex_submatch_begin_intarray {#1} }
26079   { \_kernel_intarray_item:Nn \g__regex_submatch_end_intarray {#1} }
26080 }
```

(End definition for `_regex_query_submatch:n`.)

`_regex_submatch_balance:n` Every user function must result in a balanced token list (unbalanced token lists cannot be stored by TeX). When we unpacked the query, we kept track of the brace balance, hence the contribution from a given range is the difference between the brace balances at the `<max pos>` and `<min pos>`. These two positions are found in the corresponding “submatch” arrays.

```

26081 \cs_new_protected:Npn \__regex_submatch_balance:n #1
26082 {
26083   \int_eval:n
26084   {
26085     \int_compare:nNnTF
26086     {
26087       \__kernel_intarray_item:Nn
26088       \g__regex_submatch_end_intarray {#1}
26089     }
26090     = 0
26091     { 0 }
26092     {
26093       \__kernel_intarray_item:Nn \g__regex_balance_intarray
26094       {
26095         \__kernel_intarray_item:Nn
26096         \g__regex_submatch_end_intarray {#1}
26097       }
26098     }
26099   }
26100   \int_compare:nNnTF
26101   {
26102     \__kernel_intarray_item:Nn
26103     \g__regex_submatch_begin_intarray {#1}
26104   }
26105   = 0
26106   { 0 }
26107   {
26108     \__kernel_intarray_item:Nn \g__regex_balance_intarray
26109     {
26110       \__kernel_intarray_item:Nn
26111       \g__regex_submatch_begin_intarray {#1}
26112     }
26113   }
26114 }
26115 }

```

(End definition for __regex_submatch_balance:n.)

40.6.3 Framework

```

\__regex_replacement:n
\__regex_replacement_aux:n

```

The replacement text is built incrementally. We keep track in \l__regex_balance_int of the balance of explicit begin- and end-group tokens and we store in \l__regex_balance_tl some code to compute the brace balance from submatches (see its description). Detect unescaped right braces, and escaped characters, with trailing \prg_do_nothing: because some of the later function look-ahead. Once the whole replacement text has been parsed, make sure that there is no open csname. Finally, define the balance_one_match and do_one_match functions.

```

26116 \cs_new_protected:Npn \__regex_replacement:n #1
26117 {
26118   \group_begin:
26119   \tl_build_begin:N \l__regex_build_tl
26120   \int_zero:N \l__regex_balance_int
26121   \tl_clear:N \l__regex_balance_tl
26122   \__regex_escape_use:nnnn

```



```

26123     {
26124         \if_charcode:w \c_right_brace_str ##1
26125         \__regex_replacement_rbrace:N
26126         \else:
26127             \__regex_replacement_normal:n
26128         \fi:
26129         ##1
26130     }
26131     { \__regex_replacement_escaped:N ##1 }
26132     { \__regex_replacement_normal:n ##1 }
26133     {#1}
26134     \prg_do_nothing: \prg_do_nothing:
26135     \if_int_compare:w \l__regex_replacement_csnames_int > 0 \exp_stop_f:
26136         \__kernel_msg_error:nnx { kernel } { replacement-missing-rbrace }
26137         { \int_use:N \l__regex_replacement_csnames_int }
26138         \tl_build_put_right:Nx \l__regex_build_tl
26139         { \prg_replicate:nn \l__regex_replacement_csnames_int \cs_end: }
26140     \fi:
26141     \seq_if_empty:NF \l__regex_replacement_category_seq
26142     {
26143         \__kernel_msg_error:nnx { kernel } { replacement-missing-rparen }
26144         { \seq_count:N \l__regex_replacement_category_seq }
26145         \seq_clear:N \l__regex_replacement_category_seq
26146     }
26147     \cs_gset:Npx \__regex_replacement_balance_one_match:n ##1
26148     {
26149         + \int_use:N \l__regex_balance_int
26150         \l__regex_balance_tl
26151         - \__regex_submatch_balance:n {##1}
26152     }
26153     \tl_build_end:N \l__regex_build_tl
26154     \exp_args:NNo
26155     \group_end:
26156     \__regex_replacement_aux:n \l__regex_build_tl
26157 }
26158 \cs_new_protected:Npn \__regex_replacement_aux:n #1
26159 {
26160     \cs_set:Npn \__regex_replacement_do_one_match:n ##1
26161     {
26162         \__regex_query_range:nn
26163         {
26164             \__kernel_intarray_item:Nn
26165             \g__regex_submatch_prev_intarray {##1}
26166         }
26167         {
26168             \__kernel_intarray_item:Nn
26169             \g__regex_submatch_begin_intarray {##1}
26170         }
26171         #1
26172     }
26173 }

```

(End definition for __regex_replacement:n and __regex_replacement_aux:n.)

__regex_replacement_normal:n Most characters are simply sent to the output by \tl_build_put_right:Nn, unless a

particular category code has been requested: then `__regex_replacement_c_A:w` or a similar auxiliary is called. One exception is right parentheses, which restore the category code in place before the group started. Note that the sequence is non-empty there: it contains an empty entry corresponding to the initial value of `\l__regex_replacement_category_tl`.

```

26174 \cs_new_protected:Npn \__regex_replacement_normal:n #1
26175 {
26176   \tl_if_empty:NTF \l__regex_replacement_category_tl
26177   { \tl_build_put_right:Nn \l__regex_build_tl {#1} }
26178   { % (
26179     \token_if_eq_charcode:NNTF #1 )
26180     {
26181       \seq_pop:Nn \l__regex_replacement_category_seq
26182       \l__regex_replacement_category_tl
26183     }
26184     {
26185       \use:c
26186       {
26187         __regex_replacement_c_
26188         \l__regex_replacement_category_tl :w
26189       }
26190       \__regex_replacement_normal:n {#1}
26191     }
26192   }
26193 }
```

(End definition for `__regex_replacement_normal:n`.)

`__regex_replacement_escaped:N` As in parsing a regular expression, we use an auxiliary built from `#1` if defined. Otherwise, check for escaped digits (standing from submatches from 0 to 9): anything else is a raw character. We use `\token_to_str:N` to give spaces the right category code.

```

26194 \cs_new_protected:Npn \__regex_replacement_escaped:N #1
26195 {
26196   \cs_if_exist_use:cF { __regex_replacement_#1:w }
26197   {
26198     \if_int_compare:w 1 < 1#1 \exp_stop_f:
26199     \__regex_replacement_put_submatch:n {#1}
26200   \else:
26201     \exp_args:No \__regex_replacement_normal:n
26202     { \token_to_str:N #1 }
26203   \fi:
26204 }
26205 }
```

(End definition for `__regex_replacement_escaped:N`.)

40.6.4 Submatches

`__regex_replacement_put_submatch:n` Insert a submatch in the replacement text. This is dropped if the submatch number is larger than the number of capturing groups. Unless the submatch appears inside a `\c{...}` or `\u{...}` construction, it must be taken into account in the brace balance. Later on, `##1` will be replaced by a pointer to the 0-th submatch for a given match.

There is an `\exp_not:N` here as at the point-of-use of `\l__regex_balance_tl` there is an `x`-type expansion which is needed to get `##1` in correctly.

```

26206 \cs_new_protected:Npn \__regex_replacement_put_submatch:n #1
26207 {
26208   \if_int_compare:w #1 < \l__regex_capturing_group_int
26209     \tl_build_put_right:Nn \l__regex_build_tl
26210       { \__regex_query_submatch:n { \int_eval:n { #1 + ##1 } } }
26211     \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
26212     \tl_put_right:Nn \l__regex_balance_tl
26213       {
26214         + \__regex_submatch_balance:n
26215         { \exp_not:N \int_eval:n { #1 + ##1 } }
26216       }
26217   \fi:
26218 \fi:
26219 }

```

(End definition for `__regex_replacement_put_submatch:n`.)

`__regex_replacement_g:w` Grab digits for the `\g` escape sequence in a primitive assignment to the integer `\l__regex_internal_a_int`. At the end of the run of digits, check that it ends with a right brace.

```

26220 \cs_new_protected:Npn \__regex_replacement_g:w #1#2
26221 {
26222   \__regex_two_if_eq:NNNTF
26223     #1 #2 \__regex_replacement_normal:n \c_left_brace_str
26224     { \l__regex_internal_a_int = \__regex_replacement_g_digits:NN }
26225     { \__regex_replacement_error:NNN g #1 #2 }
26226 }
26227 \cs_new:Npn \__regex_replacement_g_digits:NN #1#2
26228 {
26229   \token_if_eq_meaning:NNTF #1 \__regex_replacement_normal:n
26230   {
26231     \if_int_compare:w 1 < 1#2 \exp_stop_f:
26232     #2
26233     \exp_after:wN \use_i:nnn
26234     \exp_after:wN \__regex_replacement_g_digits:NN
26235   \else:
26236     \exp_stop_f:
26237     \exp_after:wN \__regex_replacement_error:NNN
26238     \exp_after:wN g
26239   \fi:
26240 }
26241 {
26242   \exp_stop_f:
26243   \if_meaning:w \__regex_replacement_rbrace:N #1
26244     \exp_args:No \__regex_replacement_put_submatch:n
26245       { \int_use:N \l__regex_internal_a_int }
26246     \exp_after:wN \use_none:nn
26247   \else:
26248     \exp_after:wN \__regex_replacement_error:NNN
26249     \exp_after:wN g
26250   \fi:
26251 }

```

```

26252     #1 #2
26253 }

```

(End definition for `_regex_replacement_g:w` and `_regex_replacement_g_digits:NN`.)

40.6.5 Csnames in replacement

`_regex_replacement_c:w` `\c` may only be followed by an unescaped character. If followed by a left brace, start a control sequence by calling an auxiliary common with `\u`. Otherwise test whether the category is known; if it is not, complain.

```

26254 \cs_new_protected:Npn \_regex_replacement_c:w #1#2
26255 {
26256   \token_if_eq_meaning:NNTF #1 \_regex_replacement_normal:n
26257   {
26258     \exp_after:wN \token_if_eq_charcode:NNTF \c_left_brace_str #2
26259     { \_regex_replacement_cu_aux:Nw \_regex_replacement_exp_not:N }
26260     {
26261       \cs_if_exist:cTF { \_regex_replacement_c_#2:w }
26262       { \_regex_replacement_cat:NNN #2 }
26263       { \_regex_replacement_error:NNN c #1#2 }
26264     }
26265   }
26266   { \_regex_replacement_error:NNN c #1#2 }
26267 }

```

(End definition for `_regex_replacement_c:w`.)

`_regex_replacement_cu_aux:Nw` Start a control sequence with `\cs:w`, protected from expansion by `#1` (either `_regex_replacement_exp_not:N` or `\exp_not:V`), or turned to a string by `\tl_to_str:V` if inside another csname construction `\c` or `\u`. We use `\tl_to_str:V` rather than `\tl_to_str:N` to deal with integers and other registers.

```

26268 \cs_new_protected:Npn \_regex_replacement_cu_aux:Nw #1
26269 {
26270   \if_case:w \l__regex_replacement_csnames_int
26271   \tl_build_put_right:Nn \l__regex_build_tl
26272   { \exp_not:n { \exp_after:wN #1 \cs:w } }
26273   \else:
26274   \tl_build_put_right:Nn \l__regex_build_tl
26275   { \exp_not:n { \exp_after:wN \tl_to_str:V \cs:w } }
26276   \fi:
26277   \int_incr:N \l__regex_replacement_csnames_int
26278 }

```

(End definition for `_regex_replacement_cu_aux:Nw`.)

`_regex_replacement_u:w` Check that `\u` is followed by a left brace. If so, start a control sequence with `\cs:w`, which is then unpacked either with `\exp_not:V` or `\tl_to_str:V` depending on the current context.

```

26279 \cs_new_protected:Npn \_regex_replacement_u:w #1#2
26280 {
26281   \_regex_two_if_eq:NNNTF
26282   #1 #2 \_regex_replacement_normal:n \c_left_brace_str
26283   { \_regex_replacement_cu_aux:Nw \exp_not:V }
26284   { \_regex_replacement_error:NNN u #1#2 }
26285 }

```

(End definition for `_regex_replacement_u:w`.)

`_regex_replacement_rbrace:N` Within a `\c{...}` or `\u{...}` construction, end the control sequence, and decrease the brace count. Otherwise, this is a raw right brace.

```

26286 \cs_new_protected:Npn \_regex_replacement_rbrace:N #1
26287 {
26288   \if_int_compare:w \l__regex_replacement_csnames_int > 0 \exp_stop_f:
26289     \tl_build_put_right:Nn \l__regex_build_tl { \cs_end: }
26290     \int_decr:N \l__regex_replacement_csnames_int
26291   \else:
26292     \_regex_replacement_normal:n {#1}
26293   \fi:
26294 }
```

(End definition for `_regex_replacement_rbrace:N`.)

40.6.6 Characters in replacement

`_regex_replacement_cat:NNN` Here, `#1` is a letter among BEMTPUDSLOA and `#2#3` denote the next character. Complain if we reach the end of the replacement or if the construction appears inside `\c{...}` or `\u{...}`, and detect the case of a parenthesis. In that case, store the current category in a sequence and switch to a new one.

```

26295 \cs_new_protected:Npn \_regex_replacement_cat:NNN #1#2#3
26296 {
26297   \token_if_eq_meaning:NNTF \prg_do_nothing: #3
26298   { \_kernel_msg_error:nn { kernel } { replacement-catcode-end } }
26299   {
26300     \int_compare:nNnTF { \l__regex_replacement_csnames_int } > 0
26301     {
26302       \_kernel_msg_error:nnnn
26303       { kernel } { replacement-catcode-in-cs } {#1} {#3}
26304       #2 #3
26305     }
26306     {
26307       \_regex_two_if_eq:NNNTF #2 #3 \_regex_replacement_normal:n (
26308       {
26309         \seq_push:NV \l__regex_replacement_category_seq
26310         \l__regex_replacement_category_tl
26311         \tl_set:Nn \l__regex_replacement_category_tl {#1}
26312       }
26313       {
26314         \token_if_eq_meaning:NNT #2 \_regex_replacement_escaped:N
26315         {
26316           \_regex_char_if_alphanumeric:NTF #3
26317           {
26318             \_kernel_msg_error:nnnn
26319             { kernel } { replacement-catcode-escaped }
26320             {#1} {#3}
26321           }
26322           { }
26323         }
26324         \use:c { \_regex_replacement_c_#1:w } #2 #3
26325       }
26326     }
26327 }
```

```

26327     }
26328 }

```

(End definition for `_regex_replacement_cat:NNN`.)

We now need to change the category code of the null character many times, hence work in a group. The catcode-specific macros below are defined in alphabetical order; if you are trying to understand the code, start from the end of the alphabet as those categories are simpler than active or begin-group.

```

26329 \group_begin:

```

`_regex_replacement_char:nNN` The only way to produce an arbitrary character-catcode pair is to use the `\lowercase` or `\uppercase` primitives. This is a wrapper for our purposes. The first argument is the null character with various catcodes. The second and third arguments are grabbed from the input stream: `#3` is the character whose character code to reproduce. We could use `\char_generate:nn` but only for some catcodes (active characters and spaces are not supported).

```

26330 \cs_new_protected:Npn \_regex_replacement_char:nNN #1#2#3
26331 {
26332   \tex_lccode:D 0 = '#3 \scan_stop:
26333   \tex_lowercase:D { \tl_build_put_right:Nn \l__regex_build_tl {#1} }
26334 }

```

(End definition for `_regex_replacement_char:nNN`.)

`_regex_replacement_c_A:w` For an active character, expansion must be avoided, twice because we later do two `x`-expansions, to unpack `\toks` for the query, and to expand their contents to tokens of the query.

```

26335 \char_set_catcode_active:N \^^@
26336 \cs_new_protected:Npn \_regex_replacement_c_A:w
26337 { \_regex_replacement_char:nNN { \exp_not:n { \exp_not:N \^^@ } } }

```

(End definition for `_regex_replacement_c_A:w`.)

`_regex_replacement_c_B:w` An explicit begin-group token increases the balance, unless within a `\c{...}` or `\u{...}` construction. Add the desired begin-group character, using the standard `\if_false:` trick. We eventually `x`-expand twice. The first time must yield a balanced token list, and the second one gives the bare begin-group token. The `\exp_after:wN` is not strictly needed, but is more consistent with `l3tl`-analysis.

```

26338 \char_set_catcode_group_begin:N \^^@
26339 \cs_new_protected:Npn \_regex_replacement_c_B:w
26340 {
26341   \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
26342   \int_incr:N \l__regex_balance_int
26343   \fi:
26344   \_regex_replacement_char:nNN
26345   { \exp_not:n { \exp_after:wN \^^@ \if_false: } \fi: } }
26346 }

```

(End definition for `_regex_replacement_c_B:w`.)

`__regex_replacement_c_C:w` This is not quite catcode-related: when the user requests a character with category “control sequence”, the one-character control symbol is returned. As for the active character, we prepare for two x-expansions.

```

26347 \cs_new_protected:Npn \__regex_replacement_c_C:w #1#2
26348 {
26349     \tl_build_put_right:Nn \l__regex_build_tl
26350     { \exp_not:N \exp_not:N \exp_not:c {#2} }
26351 }

```

(End definition for __regex_replacement_c_C:w.)

`__regex_replacement_c_D:w` Subscripts fit the mould: `\lowercase` the null byte with the correct category.

```

26352 \char_set_catcode_math_subscript:N \^^@
26353 \cs_new_protected:Npn \__regex_replacement_c_D:w
26354 { \__regex_replacement_char:nNN { ^^@ } }

```

(End definition for __regex_replacement_c_D:w.)

`__regex_replacement_c_E:w` Similar to the begin-group case, the second x-expansion produces the bare end-group token.

```

26355 \char_set_catcode_group_end:N \^^@
26356 \cs_new_protected:Npn \__regex_replacement_c_E:w
26357 {
26358     \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
26359     \int_decr:N \l__regex_balance_int
26360     \fi:
26361     \__regex_replacement_char:nNN
26362     { \exp_not:n { \if_false: { \fi: ^^@ } } }
26363 }

```

(End definition for __regex_replacement_c_E:w.)

`__regex_replacement_c_L:w` Simply `\lowercase` a letter null byte to produce an arbitrary letter.

```

26364 \char_set_catcode_letter:N \^^@
26365 \cs_new_protected:Npn \__regex_replacement_c_L:w
26366 { \__regex_replacement_char:nNN { ^^@ } }

```

(End definition for __regex_replacement_c_L:w.)

`__regex_replacement_c_M:w` No surprise here, we lowercase the null math toggle.

```

26367 \char_set_catcode_math_toggle:N \^^@
26368 \cs_new_protected:Npn \__regex_replacement_c_M:w
26369 { \__regex_replacement_char:nNN { ^^@ } }

```

(End definition for __regex_replacement_c_M:w.)

`__regex_replacement_c_O:w` Lowercase an other null byte.

```

26370 \char_set_catcode_other:N \^^@
26371 \cs_new_protected:Npn \__regex_replacement_c_O:w
26372 { \__regex_replacement_char:nNN { ^^@ } }

```

(End definition for __regex_replacement_c_O:w.)

`__regex_replacement_c_P:w` For macro parameters, expansion is a tricky issue. We need to prepare for two x-expansions and passing through various macro definitions. Note that we cannot replace one `\exp_not:n` by doubling the macro parameter characters because this would misbehave if a mischievous user asks for `\c{\cP\#}`, since that macro parameter character would be doubled.

```

26373 \char_set_catcode_parameter:N \^^@
26374 \cs_new_protected:Npn \__regex_replacement_c_P:w
26375 {
26376   \__regex_replacement_char:nNN
26377   { \exp_not:n { \exp_not:n { ^^@^^@^^@^^@ } } }
26378 }

```

(End definition for __regex_replacement_c_P:w.)

`__regex_replacement_c_S:w` Spaces are normalized on input by T_EX to have character code 32. It is in fact impossible to get a token with character code 0 and category code 10. Hence we use 32 instead of 0 as our base character.

```

26379 \cs_new_protected:Npn \__regex_replacement_c_S:w #1#2
26380 {
26381   \if_int_compare:w '#2 = 0 \exp_stop_f:
26382   \__kernel_msg_error:nn { kernel } { replacement-null-space }
26383   \fi:
26384   \tex_lccode:D '\ = '#2 \scan_stop:
26385   \tex_lowercase:D { \tl_build_put_right:Nn \l__regex_build_tl {~} }
26386 }

```

(End definition for __regex_replacement_c_S:w.)

`__regex_replacement_c_T:w` No surprise for alignment tabs here. Those are surrounded by the appropriate braces whenever necessary, hence they don't cause trouble in alignment settings.

```

26387 \char_set_catcode_alignment:N \^^@
26388 \cs_new_protected:Npn \__regex_replacement_c_T:w
26389 { \__regex_replacement_char:nNN { ^^@ } }

```

(End definition for __regex_replacement_c_T:w.)

`__regex_replacement_c_U:w` Simple call to `__regex_replacement_char:nNN` which lowercases the math superscript `^^@`.

```

26390 \char_set_catcode_math_superscript:N \^^@
26391 \cs_new_protected:Npn \__regex_replacement_c_U:w
26392 { \__regex_replacement_char:nNN { ^^@ } }

```

(End definition for __regex_replacement_c_U:w.)

Restore the catcode of the null byte.

```

26393 \group_end:

```


40.6.7 An error

`_regex_replacement_error:NNN` Simple error reporting by calling one of the messages `replacement-c`, `replacement-g`, or `replacement-u`.

```
26394 \cs_new_protected:Npn \_regex_replacement_error:NNN #1#2#3
26395 {
26396     \__kernel_msg_error:nnx { kernel } { replacement-#1 } {#3}
26397     #2 #3
26398 }
```

(End definition for `_regex_replacement_error:NNN`.)

40.7 User functions

`\regex_new:N` Before being assigned a sensible value, a regex variable matches nothing.

```
26399 \cs_new_protected:Npn \regex_new:N #1
26400 { \cs_new_eq:NN #1 \c__regex_no_match_regex }
```

(End definition for `\regex_new:N`. This function is documented on page 229.)

`\l_tmpa_regex` The usual scratch space.

```
\l_tmpb_regex 26401 \regex_new:N \l_tmpa_regex
\g_tmpa_regex 26402 \regex_new:N \l_tmpb_regex
\g_tmpb_regex 26403 \regex_new:N \g_tmpa_regex
26404 \regex_new:N \g_tmpb_regex
```

(End definition for `\l_tmpa_regex` and others. These variables are documented on page 231.)

`\regex_set:Nn` Compile, then store the result in the user variable with the appropriate assignment function.

`\regex_gset:Nn`

`\regex_const:Nn`

```
26405 \cs_new_protected:Npn \regex_set:Nn #1#2
26406 {
26407     \__regex_compile:n {#2}
26408     \tl_set_eq:NN #1 \l__regex_internal_regex
26409 }
26410 \cs_new_protected:Npn \regex_gset:Nn #1#2
26411 {
26412     \__regex_compile:n {#2}
26413     \tl_gset_eq:NN #1 \l__regex_internal_regex
26414 }
26415 \cs_new_protected:Npn \regex_const:Nn #1#2
26416 {
26417     \__regex_compile:n {#2}
26418     \tl_const:Nx #1 { \exp_not:o \l__regex_internal_regex }
26419 }
```

(End definition for `\regex_set:Nn`, `\regex_gset:Nn`, and `\regex_const:Nn`. These functions are documented on page 229.)

`\regex_show:N` User functions: the `n` variant requires compilation first. Then show the variable with some appropriate text. The auxiliary is defined in a different section.

`\regex_show:n`

```
26420 \cs_new_protected:Npn \regex_show:n #1
26421 {
26422     \__regex_compile:n {#1}
26423     \__regex_show:N \l__regex_internal_regex
```

```

26424 \msg_show:nnxxxx { LaTeX / kernel } { show-regex }
26425 { \tl_to_str:n {#1} } { }
26426 { \l__regex_internal_a_tl } { }
26427 }
26428 \cs_new_protected:Npn \regex_show:N #1
26429 {
26430 \__kernel_chk_defined:NT #1
26431 {
26432 \__regex_show:N #1
26433 \msg_show:nnxxxx { LaTeX / kernel } { show-regex }
26434 { } { \token_to_str:N #1 }
26435 { \l__regex_internal_a_tl } { }
26436 }
26437 }

```

(End definition for `\regex_show:N` and `\regex_show:n`. These functions are documented on page 229.)

`\regex_match:nnTF` Those conditionals are based on a common auxiliary defined later. Its first argument
`\regex_match:NnTF` builds the NFA corresponding to the regex, and the second argument is the query token
list. Once we have performed the match, convert the resulting boolean to `\prg_return_`
`true:` or `false`.

```

26438 \prg_new_protected_conditional:Npnn \regex_match:nn #1#2 { T , F , TF }
26439 {
26440 \__regex_if_match:nn { \__regex_build:n {#1} } {#2}
26441 \__regex_return:
26442 }
26443 \prg_new_protected_conditional:Npnn \regex_match:Nn #1#2 { T , F , TF }
26444 {
26445 \__regex_if_match:nn { \__regex_build:N #1 } {#2}
26446 \__regex_return:
26447 }

```

(End definition for `\regex_match:nnTF` and `\regex_match:NnTF`. These functions are documented on page 229.)

`\regex_count:nnN` Again, use an auxiliary whose first argument builds the NFA.
`\regex_count:NnN`

```

26448 \cs_new_protected:Npn \regex_count:nnN #1
26449 { \__regex_count:nnN { \__regex_build:n {#1} } }
26450 \cs_new_protected:Npn \regex_count:NnN #1
26451 { \__regex_count:nnN { \__regex_build:N #1 } }

```

(End definition for `\regex_count:nnN` and `\regex_count:NnN`. These functions are documented on page 230.)

`\regex_extract_once:nnN` We define here 40 user functions, following a common pattern in terms of `:nnN` auxiliaries,
`\regex_extract_once:nnTF` defined in the coming subsections. The auxiliary is handed `__regex_build:n` or `__`
`\regex_extract_once:NnN` `regex_build:N` with the appropriate regex argument, then all other necessary arguments
`\regex_extract_once:NnTF` (replacement text, token list, *etc.* The conditionals call `__regex_return:` to return
`\regex_extract_all:nnN` either `true` or `false` once matching has been performed.

```

26452 \cs_set_protected:Npn \__regex_tmp:w #1#2#3
26453 {
26454 \cs_new_protected:Npn #2 ##1 { #1 { \__regex_build:n {##1} } }
26455 \cs_new_protected:Npn #3 ##1 { #1 { \__regex_build:N ##1 } }
26456 \prg_new_protected_conditional:Npnn #2 ##1##2##3 { T , F , TF }

```

```

\regex_replace_once:nnN
\regex_replace_once:NnN
\regex_replace_all:nnN
\regex_replace_all:NnN
\regex_replace_all:NnTF
\regex_split:nnN
\regex_split:nnTF
\regex_split:NnN
\regex_split:NnTF

```

```

26457     { #1 { \__regex_build:n {##1} } {##2} ##3 \__regex_return: }
26458 \prg_new_protected_conditional:Npnn #3 ##1##2##3 { T , F , TF }
26459     { #1 { \__regex_build:N ##1 } {##2} ##3 \__regex_return: }
26460 }
26461 \__regex_tmp:w \__regex_extract_once:nnN
26462 \regex_extract_once:nnN \regex_extract_once:NnN
26463 \__regex_tmp:w \__regex_extract_all:nnN
26464 \regex_extract_all:nnN \regex_extract_all:NnN
26465 \__regex_tmp:w \__regex_replace_once:nnN
26466 \regex_replace_once:nnN \regex_replace_once:NnN
26467 \__regex_tmp:w \__regex_replace_all:nnN
26468 \regex_replace_all:nnN \regex_replace_all:NnN
26469 \__regex_tmp:w \__regex_split:nnN \regex_split:nnN \regex_split:NnN

```

(End definition for `\regex_extract_once:nnNTF` and others. These functions are documented on page 230.)

40.7.1 Variables and helpers for user functions

`\l__regex_match_count_int` The number of matches found so far is stored in `\l__regex_match_count_int`. This is only used in the `\regex_count:nnN` functions.

```
26470 \int_new:N \l__regex_match_count_int
```

(End definition for `\l__regex_match_count_int`.)

`__regex_begin` `__regex_end` Those flags are raised to indicate extra begin-group or end-group tokens when extracting submatches.

```
26471 \flag_new:n { __regex_begin }
26472 \flag_new:n { __regex_end }
```

(End definition for `__regex_begin` and `__regex_end`.)

`\l__regex_min_submatch_int` `\l__regex_submatch_int` `\l__regex_zeroth_submatch_int` The end-points of each submatch are stored in two arrays whose index *submatch* ranges from `\l__regex_min_submatch_int` (inclusive) to `\l__regex_submatch_int` (exclusive). Each successful match comes with a 0-th submatch (the full match), and one match for each capturing group: submatches corresponding to the last successful match are labelled starting at `zeroth_submatch`. The entry `\l__regex_zeroth_submatch_int` in `\g__regex_submatch_prev_intarray` holds the position at which that match attempt started: this is used for splitting and replacements.

```
26473 \int_new:N \l__regex_min_submatch_int
26474 \int_new:N \l__regex_submatch_int
26475 \int_new:N \l__regex_zeroth_submatch_int
```

(End definition for `\l__regex_min_submatch_int`, `\l__regex_submatch_int`, and `\l__regex_zeroth_submatch_int`.)

`\g__regex_submatch_prev_intarray` Hold the place where the match attempt begun and the end-points of each submatch.

```

\g__regex_submatch_begin_intarray 26476 \intarray_new:Nn \g__regex_submatch_prev_intarray { 65536 }
\g__regex_submatch_end_intarray    26477 \intarray_new:Nn \g__regex_submatch_begin_intarray { 65536 }
26478 \intarray_new:Nn \g__regex_submatch_end_intarray { 65536 }
```

(End definition for `\g__regex_submatch_prev_intarray`, `\g__regex_submatch_begin_intarray`, and `\g__regex_submatch_end_intarray`.)

`__regex_return:` This function triggers either `\prg_return_false:` or `\prg_return_true:` as appropriate to whether a match was found or not. It is used by all user conditionals.

```

26479 \cs_new_protected:Npn \__regex_return:
26480 {
26481   \if_meaning:w \c_true_bool \g__regex_success_bool
26482     \prg_return_true:
26483   \else:
26484     \prg_return_false:
26485   \fi:
26486 }

```

(End definition for __regex_return:.)

40.7.2 Matching

`__regex_if_match:nn` We don't track submatches, and stop after a single match. Build the NFA with #1, and perform the match on the query #2.

```

26487 \cs_new_protected:Npn \__regex_if_match:nn #1#2
26488 {
26489   \group_begin:
26490     \__regex_disable_submatches:
26491     \__regex_single_match:
26492     #1
26493     \__regex_match:n {#2}
26494   \group_end:
26495 }

```

(End definition for __regex_if_match:nn.)

`__regex_count:nnN` Again, we don't care about submatches. Instead of aborting after the first “longest match” is found, we search for multiple matches, incrementing `\l__regex_match_count_int` every time to record the number of matches. Build the NFA and match. At the end, store the result in the user's variable.

```

26496 \cs_new_protected:Npn \__regex_count:nnN #1#2#3
26497 {
26498   \group_begin:
26499     \__regex_disable_submatches:
26500     \int_zero:N \l__regex_match_count_int
26501     \__regex_multi_match:n { \int_incr:N \l__regex_match_count_int }
26502     #1
26503     \__regex_match:n {#2}
26504     \exp_args:NNNo
26505   \group_end:
26506   \int_set:Nn #3 { \int_use:N \l__regex_match_count_int }
26507 }

```

(End definition for __regex_count:nnN.)

40.7.3 Extracting submatches

`__regex_extract_once:nnN` Match once or multiple times. After each match (or after the only match), extract the submatches using `__regex_extract:.` At the end, store the sequence containing all the submatches into the user variable #3 after closing the group.

```

26508 \cs_new_protected:Npn \__regex_extract_once:nnN #1#2#3
26509 {
26510   \group_begin:
26511   \__regex_single_match:
26512   #1
26513   \__regex_match:n {#2}
26514   \__regex_extract:
26515   \__regex_group_end_extract_seq:N #3
26516 }
26517 \cs_new_protected:Npn \__regex_extract_all:nnN #1#2#3
26518 {
26519   \group_begin:
26520   \__regex_multi_match:n { \__regex_extract: }
26521   #1
26522   \__regex_match:n {#2}
26523   \__regex_group_end_extract_seq:N #3
26524 }

```

(End definition for __regex_extract_once:nnN and __regex_extract_all:nnN.)

__regex_split:nnN Splitting at submatches is a bit more tricky. For each match, extract all submatches, and replace the zeroth submatch by the part of the query between the start of the match attempt and the start of the zeroth submatch. This is inhibited if the delimiter matched an empty token list at the start of this match attempt. After the last match, store the last part of the token list, which ranges from the start of the match attempt to the end of the query. This step is inhibited if the last match was empty and at the very end: decrement \l__regex_submatch_int, which controls which matches will be used.

```

26525 \cs_new_protected:Npn \__regex_split:nnN #1#2#3
26526 {
26527   \group_begin:
26528   \__regex_multi_match:n
26529   {
26530     \if_int_compare:w
26531     \l__regex_start_pos_int < \l__regex_success_pos_int
26532     \__regex_extract:
26533     \__kernel_intarray_gset:Nnn \g__regex_submatch_prev_intarray
26534     { \l__regex_zeroth_submatch_int } { 0 }
26535     \__kernel_intarray_gset:Nnn \g__regex_submatch_end_intarray
26536     { \l__regex_zeroth_submatch_int }
26537     {
26538       \__kernel_intarray_item:Nn \g__regex_submatch_begin_intarray
26539       { \l__regex_zeroth_submatch_int }
26540     }
26541     \__kernel_intarray_gset:Nnn \g__regex_submatch_begin_intarray
26542     { \l__regex_zeroth_submatch_int }
26543     { \l__regex_start_pos_int }
26544   \fi:
26545   }
26546   #1
26547   \__regex_match:n {#2}
26548   (assert)\assert_int:n { \l__regex_curr_pos_int = \l__regex_max_pos_int }
26549   \__kernel_intarray_gset:Nnn \g__regex_submatch_prev_intarray
26550   { \l__regex_submatch_int } { 0 }
26551   \__kernel_intarray_gset:Nnn \g__regex_submatch_end_intarray

```

```

26552     { \l__regex_submatch_int }
26553     { \l__regex_max_pos_int }
26554     \__kernel_intarray_gset:Nnn \g__regex_submatch_begin_intarray
26555     { \l__regex_submatch_int }
26556     { \l__regex_start_pos_int }
26557     \int_incr:N \l__regex_submatch_int
26558     \if_meaning:w \c_true_bool \l__regex_empty_success_bool
26559     \if_int_compare:w \l__regex_start_pos_int = \l__regex_max_pos_int
26560     \int_decr:N \l__regex_submatch_int
26561     \fi:
26562     \fi:
26563     \__regex_group_end_extract_seq:N #3
26564   }

```

(End definition for __regex_split:nnN.)

__regex_group_end_extract_seq:N The end-points of submatches are stored as entries of two arrays from \l__regex_min_submatch_int to \l__regex_submatch_int (exclusive). Extract the relevant ranges into \l__regex_internal_a_tl. We detect unbalanced results using the two flags __regex_begin and __regex_end, raised whenever we see too many begin-group or end-group tokens in a submatch.

```

26565 \cs_new_protected:Npn \__regex_group_end_extract_seq:N #1
26566 {
26567     \flag_clear:n { __regex_begin }
26568     \flag_clear:n { __regex_end }
26569     \seq_set_from_function:NnN \l__regex_internal_seq
26570     {
26571         \int_step_function:nnN { \l__regex_min_submatch_int }
26572         { \l__regex_submatch_int - 1 }
26573     }
26574     \__regex_extract_seq_aux:n
26575     \int_compare:nNnF
26576     {
26577         \flag_height:n { __regex_begin } +
26578         \flag_height:n { __regex_end }
26579     }
26580     = 0
26581     {
26582         \__kernel_msg_error:nnxxx { kernel } { result-unbalanced }
26583         { splitting~or~extracting~submatches }
26584         { \flag_height:n { __regex_end } }
26585         { \flag_height:n { __regex_begin } }
26586     }
26587     \seq_set_map:NnN \l__regex_internal_seq \l__regex_internal_seq {##1}
26588     \exp_args:NNNo
26589     \group_end:
26590     \tl_set:Nn #1 { \l__regex_internal_seq }
26591 }

```

(End definition for __regex_group_end_extract_seq:N.)

__regex_extract_seq_aux:n The :n auxiliary builds one item of the sequence of submatches. First compute the brace balance of the submatch, then extract the submatch from the query, adding the appropriate braces and raising a flag if the submatch is not balanced.

```

26592 \cs_new:Npn \__regex_extract_seq_aux:n #1
26593 {
26594   \exp_after:wN \__regex_extract_seq_aux:ww
26595   \int_value:w \__regex_submatch_balance:n {#1} ; #1;
26596 }
26597 \cs_new:Npn \__regex_extract_seq_aux:ww #1; #2;
26598 {
26599   \if_int_compare:w #1 < 0 \exp_stop_f:
26600     \flag_raise:n { __regex_end }
26601     \prg_replicate:nn {-#1} { \exp_not:n { { \if_false: } \fi: } }
26602   \fi:
26603   \__regex_query_submatch:n {#2}
26604   \if_int_compare:w #1 > 0 \exp_stop_f:
26605     \flag_raise:n { __regex_begin }
26606     \prg_replicate:nn {#1} { \exp_not:n { \if_false: { \fi: } } }
26607   \fi:
26608 }

```

(End definition for __regex_extract_seq_aux:n and __regex_extract_seq_aux:ww.)

__regex_extract: Our task here is to extract from the property list \l__regex_success_submatches_prop the list of end-points of submatches, and store them in appropriate array entries, from \l__regex_extract_b:wn the list of end-points of submatches, and store them in appropriate array entries, from \l__regex_extract_e:wn \l__regex_zeroth_submatch_int upwards. We begin by emptying those entries. This is somewhat a hack: the $\langle key \rangle$ is a non-negative integer followed by $<$ or $>$, which we use in a comparison to -1 . At the end, store the information about the position at which the match attempt started, in \g__regex_submatch_prev_intarray.

```

26609 \cs_new_protected:Npn \__regex_extract:
26610 {
26611   \if_meaning:w \c_true_bool \g__regex_success_bool
26612     \int_set_eq:NN \l__regex_zeroth_submatch_int \l__regex_submatch_int
26613     \prg_replicate:nn \l__regex_capturing_group_int
26614     {
26615       \__kernel_intarray_gset:Nnn \g__regex_submatch_begin_intarray
26616       { \l__regex_submatch_int } { 0 }
26617       \__kernel_intarray_gset:Nnn \g__regex_submatch_end_intarray
26618       { \l__regex_submatch_int } { 0 }
26619       \__kernel_intarray_gset:Nnn \g__regex_submatch_prev_intarray
26620       { \l__regex_submatch_int } { 0 }
26621       \int_incr:N \l__regex_submatch_int
26622     }
26623   \prop_map_inline:Nn \l__regex_success_submatches_prop
26624   {
26625     \if_int_compare:w ##1 - 1 \exp_stop_f:
26626       \exp_after:wN \__regex_extract_e:wn \int_value:w
26627     \else:
26628       \exp_after:wN \__regex_extract_b:wn \int_value:w
26629     \fi:
26630     \__regex_int_eval:w \l__regex_zeroth_submatch_int + ##1 {##2}
26631   }
26632   \__kernel_intarray_gset:Nnn \g__regex_submatch_prev_intarray
26633   { \l__regex_zeroth_submatch_int } { \l__regex_start_pos_int }
26634   \fi:
26635 }

```

```

26636 \cs_new_protected:Npn \__regex_extract_b:wn #1 < #2
26637 {
26638   \__kernel_intarray_gset:Nnn
26639   \g__regex_submatch_begin_intarray {#1} {#2}
26640 }
26641 \cs_new_protected:Npn \__regex_extract_e:wn #1 > #2
26642 { \__kernel_intarray_gset:Nnn \g__regex_submatch_end_intarray {#1} {#2} }

```

(End definition for __regex_extract:, __regex_extract_b:wn, and __regex_extract_e:wn.)

40.7.4 Replacement

__regex_replace_once:nnN Build the NFA and the replacement functions, then find a single match. If the match failed, simply exit the group. Otherwise, we do the replacement. Extract submatches. Compute the brace balance corresponding to replacing this match by the replacement (this depends on submatches). Prepare the replaced token list: the replacement function produces the tokens from the start of the query to the start of the match and the replacement text for this match; we need to add the tokens from the end of the match to the end of the query. Finally, store the result in the user's variable after closing the group: this step involves an additional x-expansion, and checks that braces are balanced in the final result.

```

26643 \cs_new_protected:Npn \__regex_replace_once:nnN #1#2#3
26644 {
26645   \group_begin:
26646   \__regex_single_match:
26647   #1
26648   \__regex_replacement:n {#2}
26649   \exp_args:No \__regex_match:n { #3 }
26650   \if_meaning:w \c_false_bool \g__regex_success_bool
26651   \group_end:
26652   \else:
26653     \__regex_extract:
26654     \int_set:Nn \l__regex_balance_int
26655     {
26656       \__regex_replacement_balance_one_match:n
26657       { \l__regex_zeroth_submatch_int }
26658     }
26659     \tl_set:Nx \l__regex_internal_a_tl
26660     {
26661       \__regex_replacement_do_one_match:n
26662       { \l__regex_zeroth_submatch_int }
26663       \__regex_query_range:nn
26664       {
26665         \__kernel_intarray_item:Nn \g__regex_submatch_end_intarray
26666         { \l__regex_zeroth_submatch_int }
26667       }
26668       { \l__regex_max_pos_int }
26669     }
26670     \__regex_group_end_replace:N #3
26671   \fi:
26672 }

```

(End definition for __regex_replace_once:nnN.)

`__regex_replace_all:nnN` Match multiple times, and for every match, extract submatches and additionally store the position at which the match attempt started. The entries from `\l__regex_min_submatch_int` to `\l__regex_submatch_int` hold information about submatches of every match in order; each match corresponds to `\l__regex_capturing_group_int` consecutive entries. Compute the brace balance corresponding to doing all the replacements: this is the sum of brace balances for replacing each match. Join together the replacement texts for each match (including the part of the query before the match), and the end of the query.

```

26673 \cs_new_protected:Npn \__regex_replace_all:nnN #1#2#3
26674 {
26675   \group_begin:
26676   \__regex_multi_match:n { \__regex_extract: }
26677   #1
26678   \__regex_replacement:n {#2}
26679   \exp_args:No \__regex_match:n {#3}
26680   \int_set:Nn \l__regex_balance_int
26681   {
26682     0
26683     \int_step_function:nnnN
26684     { \l__regex_min_submatch_int }
26685     \l__regex_capturing_group_int
26686     { \l__regex_submatch_int - 1 }
26687     \__regex_replacement_balance_one_match:n
26688   }
26689   \tl_set:Nx \l__regex_internal_a_tl
26690   {
26691     \int_step_function:nnnN
26692     { \l__regex_min_submatch_int }
26693     \l__regex_capturing_group_int
26694     { \l__regex_submatch_int - 1 }
26695     \__regex_replacement_do_one_match:n
26696     \__regex_query_range:nn
26697     \l__regex_start_pos_int \l__regex_max_pos_int
26698   }
26699   \__regex_group_end_replace:N #3
26700 }

```

(End definition for `__regex_replace_all:nnN`.)

`__regex_group_end_replace:N` If the brace balance is not 0, raise an error. Then set the user's variable `#1` to the x-expansion of `\l__regex_internal_a_tl`, adding the appropriate braces to produce a balanced result. And end the group.

```

26701 \cs_new_protected:Npn \__regex_group_end_replace:N #1
26702 {
26703   \if_int_compare:w \l__regex_balance_int = 0 \exp_stop_f:
26704   \else:
26705     \__kernel_msg_error:nnxxx { kernel } { result-unbalanced }
26706     { replacing }
26707     { \int_max:nn { - \l__regex_balance_int } { 0 } }
26708     { \int_max:nn { \l__regex_balance_int } { 0 } }
26709   \fi:
26710   \use:x
26711   {

```

```

26712     \group_end:
26713     \tl_set:Nn \exp_not:N #1
26714     {
26715         \if_int_compare:w \l__regex_balance_int < 0 \exp_stop_f:
26716         \prg_replicate:nn { - \l__regex_balance_int }
26717         { { \if_false: } \fi: }
26718         \fi:
26719         \l__regex_internal_a_tl
26720         \if_int_compare:w \l__regex_balance_int > 0 \exp_stop_f:
26721         \prg_replicate:nn { \l__regex_balance_int }
26722         { \if_false: { \fi: } }
26723         \fi:
26724     }
26725 }
26726 }

```

(End definition for `__regex_group_end_replace:N`.)

40.7.5 Storing and showing compiled patterns

40.8 Messages

Messages for the preparising phase.

```

26727 \use:x
26728 {
26729     \__kernel_msg_new:nnn { kernel } { trailing-backslash }
26730     { Trailing-escape-char~'\iow_char:N\\'~in-regex-or~replacement. }
26731     \__kernel_msg_new:nnn { kernel } { x-missing-rbrace }
26732     {
26733         Missing-brace~'\iow_char:N\}'~in-regex~
26734         '...\iow_char:N\x\iow_char:N\{...##1'.
26735     }
26736     \__kernel_msg_new:nnn { kernel } { x-overflow }
26737     {
26738         Character-code~##1~too~large~in~
26739         \iow_char:N\x\iow_char:N\{##2\iow_char:N\}~regex.
26740     }
26741 }

```

Invalid quantifier.

```

26742 \__kernel_msg_new:nnnn { kernel } { invalid-quantifier }
26743 { Braced-quantifier~'#1'~may~not~be~followed~by~'#2'. }
26744 {
26745     The~character~'#2'~is~invalid~in~the~braced~quantifier~'#1'.~
26746     The~only~valid~quantifiers~are~'*',~'?',~'+',~'{<int>}',~
26747     '{<min>}',~and~'{<min>,<max>}',~optionally~followed~by~'?''.
26748 }

```

Messages for missing or extra closing brackets and parentheses, with some fancy singular/plural handling for the case of parentheses.

```

26749 \__kernel_msg_new:nnnn { kernel } { missing-rbrack }
26750 { Missing~right~bracket~inserted~in~regular~expression. }
26751 {
26752     LaTeX~was~given~a~regular~expression~where~a~character~class~
26753     was~started~with~'[',~but~the~matching~']'~is~missing.

```

```

26754 }
26755 \__kernel_msg_new:nnnn { kernel } { missing-rparen }
26756 {
26757     Missing-right~
26758     \int_compare:nTF { #1 = 1 } { parenthesis } { parentheses } ~
26759     inserted-in-regular-expression.
26760 }
26761 {
26762     LaTeX-was-given-a-regular-expression-with-\int_eval:n {#1} ~
26763     more-left-parentheses-than-right-parentheses.
26764 }
26765 \__kernel_msg_new:nnnn { kernel } { extra-rparen }
26766 { Extra-right-parenthesis-ignored-in-regular-expression. }
26767 {
26768     LaTeX-came-across-a-closing-parenthesis-when-no-submatch-group-
26769     was-open.~The-parenthesis-will-be-ignored.
26770 }

```

Some escaped alphanumerics are not allowed everywhere.

```

26771 \__kernel_msg_new:nnnn { kernel } { bad-escape }
26772 {
26773     Invalid-escape~'\iow_char:N\\#1'~
26774     \__regex_if_in_cs:TF { within-a-control-sequence. }
26775     {
26776         \__regex_if_in_class:TF
26777         { in-a-character-class. }
26778         { following-a-category-test. }
26779     }
26780 }
26781 {
26782     The-escape-sequence~'\iow_char:N\\#1'~may-not-appear~
26783     \__regex_if_in_cs:TF
26784     {
26785         within-a-control-sequence-test-introduced-by~
26786         '\iow_char:N\\c\iow_char:N{\'.
26787     }
26788     {
26789         \__regex_if_in_class:TF
26790         { within-a-character-class~ }
26791         { following-a-category-test-such-as~'\iow_char:N\\cL'~ }
26792         because-it-does-not-match-exactly-one-character.
26793     }
26794 }

```

Range errors.

```

26795 \__kernel_msg_new:nnnn { kernel } { range-missing-end }
26796 { Invalid-end-point-for-range~'#1-#2'~in-character-class. }
26797 {
26798     The-end-point~'#2'~of-the-range~'#1-#2'~may-not-serve-as-an-
26799     end-point-for-a-range:~alphanumeric-characters-should-not-be-
26800     escaped,~and-non-alphanumeric-characters-should-be-escaped.
26801 }
26802 \__kernel_msg_new:nnnn { kernel } { range-backwards }
26803 { Range~'#1-#2'~out-of-order-in-character-class. }
26804 {

```

```

26805     In~ranges~of~characters~'[x-y]~'~appearing~in~character~classes,~
26806     the~first~character~code~must~not~be~larger~than~the~second.~
26807     Here,~'#1'~has~character~code~\int_eval:n~{'#1},~while~
26808     '#2'~has~character~code~\int_eval:n~{'#2}.
26809 }

```

Errors related to \c and \u.

```

26810 \__kernel_msg_new:nnnn { kernel } { c-bad-mode }
26811 { Invalid~nested~'\iow_char:N\\c'~escape~in~regular~expression. }
26812 {
26813     The~'\iow_char:N\\c'~escape~cannot~be~used~within~
26814     a~control~sequence~test~'\iow_char:N\\c{...}'~
26815     nor~another~category~test.~
26816     To~combine~several~category~tests,~use~'\iow_char:N\\c[...]'.
26817 }
26818 \__kernel_msg_new:nnnn { kernel } { c-C-invalid }
26819 { '\iow_char:N\\cC'~should~be~followed~by~'.~'~or~'(',~not~'#1'. }
26820 {
26821     The~'\iow_char:N\\cC'~construction~restricts~the~next~item~to~be~a~
26822     control~sequence~or~the~next~group~to~be~made~of~control~sequences.~
26823     It~only~makes~sense~to~follow~it~by~'.~'~or~by~a~group.
26824 }
26825 \__kernel_msg_new:nnnn { kernel } { c-lparen-in-class }
26826 { Catcode~test~cannot~apply~to~group~in~character~class }
26827 {
26828     Construction~such~as~'\iow_char:N\\cL(abc)'~are~not~allowed~inside~a~
26829     class~'[...]'~because~classes~do~not~match~multiple~characters~at~once.
26830 }
26831 \__kernel_msg_new:nnnn { kernel } { c-missing-rbrace }
26832 { Missing~right~brace~inserted~for~'\iow_char:N\\c'~escape. }
26833 {
26834     LaTeX~was~given~a~regular~expression~where~a~
26835     '\iow_char:N\\c\iow_char:N{...}'~construction~was~not~ended~
26836     with~a~closing~brace~'\iow_char:N}'.
26837 }
26838 \__kernel_msg_new:nnnn { kernel } { c-missing-rbrack }
26839 { Missing~right~bracket~inserted~for~'\iow_char:N\\c'~escape. }
26840 {
26841     A~construction~'\iow_char:N\\c[...]'~appears~in~a~
26842     regular~expression,~but~the~closing~']'~is~not~present.
26843 }
26844 \__kernel_msg_new:nnnn { kernel } { c-missing-category }
26845 { Invalid~character~'#1'~following~'\iow_char:N\\c'~escape. }
26846 {
26847     In~regular~expressions,~the~'\iow_char:N\\c'~escape~sequence~
26848     may~only~be~followed~by~a~left~brace,~a~left~bracket,~or~a~
26849     capital~letter~representing~a~character~category,~namely~
26850     one~of~'ABCDELMOPSTU'.
26851 }
26852 \__kernel_msg_new:nnnn { kernel } { c-trailing }
26853 { Trailing~category~code~escape~'\iow_char:N\\c'... }
26854 {
26855     A~regular~expression~ends~with~'\iow_char:N\\c'~followed~
26856     by~a~letter.~It~will~be~ignored.
26857 }

```

```

26858 \__kernel_msg_new:nnnn { kernel } { u-missing-lbrace }
26859 { Missing~left~brace~following~'\iow_char:N\\u'~escape. }
26860 {
26861   The~'\iow_char:N\\u'~escape~sequence~must~be~followed~by~
26862   a~brace~group~with~the~name~of~the~variable~to~use.
26863 }
26864 \__kernel_msg_new:nnnn { kernel } { u-missing-rbrace }
26865 { Missing~right~brace~inserted~for~'\iow_char:N\\u'~escape. }
26866 {
26867   LaTeX~
26868   \str_if_eq:eeTF { } {#2}
26869   { reached~the~end~of~the~string~ }
26870   { encountered~an~escaped~alphanumeric~character '\iow_char:N\\#2'~ }
26871   when~parsing~the~argument~of~an~
26872   '\iow_char:N\\u\iow_char:N{...}'~escape.
26873 }

```

Errors when encountering the POSIX syntax [:...:].

```

26874 \__kernel_msg_new:nnnn { kernel } { posix-unsupported }
26875 { POSIX~collating~element~'#1 ~ #1'~not~supported. }
26876 {
26877   The~' [.foo.] '~and~' [=bar=] '~syntaxes~have~a~special~meaning~
26878   in~POSIX~regular~expressions.~This~is~not~supported~by~LaTeX.~
26879   Maybe~you~forgot~to~escape~a~left~bracket~in~a~character~class?
26880 }
26881 \__kernel_msg_new:nnnn { kernel } { posix-unknown }
26882 { POSIX~class~'[:#1:]'~unknown. }
26883 {
26884   '[:#1:]'~is~not~among~the~known~POSIX~classes~
26885   '[:alnum:]',~'[:alpha:]',~'[:ascii:]',~'[:blank:]',~
26886   '[:cntrl:]',~'[:digit:]',~'[:graph:]',~'[:lower:]',~
26887   '[:print:]',~'[:punct:]',~'[:space:]',~'[:upper:]',~
26888   '[:word:]',~and~'[:xdigit:]'.
26889 }
26890 \__kernel_msg_new:nnnn { kernel } { posix-missing-close }
26891 { Missing~closing~':'~for~POSIX~class. }
26892 { The~POSIX~syntax~'#1'~must~be~followed~by~':'',~not~'#2'. }

```

In various cases, the result of a `l3regex` operation can leave us with an unbalanced token list, which we must re-balance by adding begin-group or end-group character tokens.

```

26893 \__kernel_msg_new:nnnn { kernel } { result-unbalanced }
26894 { Missing~brace~inserted~when~#1. }
26895 {
26896   LaTeX~was~asked~to~do~some~regular~expression~operation,~
26897   and~the~resulting~token~list~would~not~have~the~same~number~
26898   of~begin~group~and~end~group~tokens.~Braces~were~inserted:~
26899   #2~left,~#3~right.
26900 }

```

Error message for unknown options.

```

26901 \__kernel_msg_new:nnnn { kernel } { unknown-option }
26902 { Unknown~option~'#1'~for~regular~expressions. }
26903 {
26904   The~only~available~option~is~'case-insensitive',~toggled~by~

```

```

26905     '(?i)'~and~'(?-i)'.
26906   }
26907   \_kernel_msg_new:nnnn { kernel } { special-group-unknown }
26908   { Unknown~special~group~'#1~...'~in~a~regular~expression. }
26909   {
26910     The~only~valid~constructions~starting~with~'('?~are~
26911     '(:~...~)',~'(?|~...~)',~'(?i)',~and~'(?-i)'.
26912   }

```

Errors in the replacement text.

```

26913   \_kernel_msg_new:nnnn { kernel } { replacement-c }
26914   { Misused~'\iow_char:N\\c'~command~in~a~replacement~text. }
26915   {
26916     In~a~replacement~text,~the~'\iow_char:N\\c'~escape~sequence~
26917     can~be~followed~by~one~of~the~letters~'ABCDELMOPSTU'~
26918     or~a~brace~group,~not~by~'#1'.
26919   }
26920   \_kernel_msg_new:nnnn { kernel } { replacement-u }
26921   { Misused~'\iow_char:N\\u'~command~in~a~replacement~text. }
26922   {
26923     In~a~replacement~text,~the~'\iow_char:N\\u'~escape~sequence~
26924     must~be~followed~by~a~brace~group~holding~the~name~of~the~
26925     variable~to~use.
26926   }
26927   \_kernel_msg_new:nnnn { kernel } { replacement-g }
26928   {
26929     Missing~brace~for~the~'\iow_char:N\\g'~construction~
26930     in~a~replacement~text.
26931   }
26932   {
26933     In~the~replacement~text~for~a~regular~expression~search,~
26934     submatches~are~represented~either~as~'\iow_char:N \\g{dd..d}',~
26935     or~'\d',~where~'d'~are~single~digits.~Here,~a~brace~is~missing.
26936   }
26937   \_kernel_msg_new:nnnn { kernel } { replacement-catcode-end }
26938   {
26939     Missing~character~for~the~'\iow_char:N\\c<category><character>'~
26940     construction~in~a~replacement~text.
26941   }
26942   {
26943     In~a~replacement~text,~the~'\iow_char:N\\c'~escape~sequence~
26944     can~be~followed~by~one~of~the~letters~'ABCDELMOPSTU'~representing~
26945     the~character~category.~Then,~a~character~must~follow.~LaTeX~
26946     reached~the~end~of~the~replacement~when~looking~for~that.
26947   }
26948   \_kernel_msg_new:nnnn { kernel } { replacement-catcode-escaped }
26949   {
26950     Escaped~letter~or~digit~after~category~code~in~replacement~text.
26951   }
26952   {
26953     In~a~replacement~text,~the~'\iow_char:N\\c'~escape~sequence~
26954     can~be~followed~by~one~of~the~letters~'ABCDELMOPSTU'~representing~
26955     the~character~category.~Then,~a~character~must~follow,~not~
26956     '\iow_char:N\\#2'.
26957   }

```

```

26958 \__kernel_msg_new:nnnn { kernel } { replacement-catcode-in-cs }
26959 {
26960   Category-code~'\iow_char:N\c#1#3'~ignored-inside~
26961   '\iow_char:N\c\{...\}'~in~a~replacement~text.
26962 }
26963 {
26964   In~a~replacement~text,~the~category~codes~of~the~argument~of~
26965   '\iow_char:N\c\{...\}'~are~ignored~when~building~the~control~
26966   sequence~name.
26967 }
26968 \__kernel_msg_new:nnnn { kernel } { replacement-null-space }
26969 { TeX~cannot~build~a~space~token~with~character~code~0. }
26970 {
26971   You~asked~for~a~character~token~with~category~space,~
26972   and~character~code~0,~for~instance~through~
26973   '\iow_char:N\cS\iow_char:N\c00'.~
26974   This~specific~case~is~impossible~and~will~be~replaced~
26975   by~a~normal~space.
26976 }
26977 \__kernel_msg_new:nnnn { kernel } { replacement-missing-rbrace }
26978 { Missing~right~brace~inserted~in~replacement~text. }
26979 {
26980   There~ \int_compare:nTF { #1 = 1 } { was } { were } ~ #1~
26981   missing~right~\int_compare:nTF { #1 = 1 } { brace } { braces } .
26982 }
26983 \__kernel_msg_new:nnnn { kernel } { replacement-missing-rparen }
26984 { Missing~right~parenthesis~inserted~in~replacement~text. }
26985 {
26986   There~ \int_compare:nTF { #1 = 1 } { was } { were } ~ #1~
26987   missing~right~
26988   \int_compare:nTF { #1 = 1 } { parenthesis } { parentheses } .
26989 }

```

Used when showing a regex.

```

26990 \__kernel_msg_new:nnn { kernel } { show-regex }
26991 {
26992   >~Compiled~regex~
26993   \tl_if_empty:nTF {#1} { variable~ #2 } { {#1} } :
26994   #3
26995 }

```

`__regex_msg_repeated:nnN` This is not technically a message, but seems related enough to go there. The arguments are: #1 is the minimum number of repetitions; #2 is the number of allowed extra repetitions (−1 for infinite number), and #3 tells us about laziness.

```

26996 \cs_new:Npn \__regex_msg_repeated:nnN #1#2#3
26997 {
26998   \str_if_eq:eeF { #1 #2 } { 1 0 }
26999   {
27000     , ~ repeated ~
27001     \int_case:nnF {#2}
27002     {
27003       { -1 } { #1~or~more~times,~\bool_if:NTF #3 { lazy } { greedy } }
27004       { 0 } { #1~times }
27005     }

```

```

27006         {
27007             between~#1~and~\int_eval:n {#1+#2}~times,~
27008             \bool_if:NTF #3 { lazy } { greedy }
27009         }
27010     }
27011 }

```

(End definition for `__regex_msg_repeated:nnN`.)

40.9 Code for tracing

There is a more extensive implementation of tracing in the `l3trial` package `l3trace`. Function names are a bit different but could be merged.

`__regex_trace_push:nnN` Here `#1` is the module name (`regex`) and `#2` is typically 1. If the module's current tracing level is less than `#2` show nothing, otherwise write `#3` to the terminal.

```

\__regex_trace_pop:nnN
\__regex_trace:nnx
27012 \cs_new_protected:Npn \__regex_trace_push:nnN #1#2#3
27013 { \__regex_trace:nnx {#1} {#2} { entering~ \token_to_str:N #3 } }
27014 \cs_new_protected:Npn \__regex_trace_pop:nnN #1#2#3
27015 { \__regex_trace:nnx {#1} {#2} { leaving~ \token_to_str:N #3 } }
27016 \cs_new_protected:Npn \__regex_trace:nnx #1#2#3
27017 {
27018     \int_compare:nNnF
27019     { \int_use:c { g__regex_trace_#1_int } } < {#2}
27020     { \iow_term:x { Trace:~#3 } }
27021 }

```

(End definition for `__regex_trace_push:nnN`, `__regex_trace_pop:nnN`, and `__regex_trace:nnx`.)

`\g__regex_trace_regex_int` No tracing when that is zero.

```

27022 \int_new:N \g__regex_trace_regex_int

```

(End definition for `\g__regex_trace_regex_int`.)

`__regex_trace_states:n` This function lists the contents of all states of the NFA, stored in `\toks` from 0 to `\l__-regex_max_state_int` (excluded).

```

27023 \cs_new_protected:Npn \__regex_trace_states:n #1
27024 {
27025     \int_step_inline:nnn
27026     \l__regex_min_state_int
27027     { \l__regex_max_state_int - 1 }
27028     {
27029         \__regex_trace:nnx { regex } {#1}
27030         { \iow_char:N \toks ##1 = { \__regex_toks_use:w ##1 } }
27031     }
27032 }

```

(End definition for `__regex_trace_states:n`.)

```

27033 </initex | package>

```


41 l3box implementation

```
27034 \*initex | package)
```

```
27035 \@@=box)
```

41.1 Support code

`__box_dim_eval:w` Evaluating a dimension expression expandably. The only difference with `\dim_eval:n` is the lack of `\dim_use:N`, to produce an internal dimension rather than expand it into characters.

```
27036 \cs_new_eq:NN \__box_dim_eval:w \tex_dimexpr:D
```

```
27037 \cs_new:Npn \__box_dim_eval:n #1
```

```
27038 { \__box_dim_eval:w #1 \scan_stop: }
```

(End definition for `__box_dim_eval:w` and `__box_dim_eval:n`.)

41.2 Creating and initialising boxes

The following test files are used for this code: *m3box001.lvt*.

`\box_new:N` Defining a new `\box` register: remember that box 255 is not generally available.

```
\box_new:c 27039 \*package)
27040 \cs_new_protected:Npn \box_new:N #1
27041 {
27042     \__kernel_chk_if_free_cs:N #1
27043     \cs:w newbox \cs_end: #1
27044 }
27045 \package)
27046 \cs_generate_variant:Nn \box_new:N { c }
```

Clear a `\box` register.

```
27047 \cs_new_protected:Npn \box_clear:N #1
\box_clear:N 27048 { \box_set_eq:NN #1 \c_empty_box }
27049 \cs_new_protected:Npn \box_gclear:N #1
\box_gclear:N 27050 { \box_gset_eq:NN #1 \c_empty_box }
27051 \cs_generate_variant:Nn \box_clear:N { c }
27052 \cs_generate_variant:Nn \box_gclear:N { c }
```

Clear or new.

```
27053 \cs_new_protected:Npn \box_clear_new:N #1
\box_clear_new:N 27054 { \box_if_exist:NTF #1 { \box_clear:N #1 } { \box_new:N #1 } }
27055 \cs_new_protected:Npn \box_gclear_new:N #1
\box_gclear_new:N 27056 { \box_if_exist:NTF #1 { \box_gclear:N #1 } { \box_new:N #1 } }
27057 \cs_generate_variant:Nn \box_clear_new:N { c }
27058 \cs_generate_variant:Nn \box_gclear_new:N { c }
```

Assigning the contents of a box to be another box.

```
27059 \cs_new_protected:Npn \box_set_eq:NN #1#2
\box_set_eq:cN 27060 { \tex_setbox:D #1 \tex_copy:D #2 }
27061 \cs_new_protected:Npn \box_gset_eq:NN #1#2
\box_set_eq:Nc 27062 { \tex_global:D \tex_setbox:D #1 \tex_copy:D #2 }
27063 \cs_generate_variant:Nn \box_set_eq:NN { c , Nc , cc }
\box_gset_eq:NN 27064 \cs_generate_variant:Nn \box_gset_eq:NN { c , Nc , cc }
\box_gset_eq:cN
\box_gset_eq:Nc
\box_gset_eq:cc
```

Assigning the contents of a box to be another box, then drops the original box.

```

\box_set_eq_drop:NN 27065 \cs_new_protected:Npn \box_set_eq_drop:NN #1#2
{ \tex_setbox:D #1 \tex_box:D #2 }
\box_set_eq_drop:cN 27066
\box_set_eq_drop:Nc 27067 \cs_new_protected:Npn \box_gset_eq_drop:NN #1#2
{ \tex_global:D \tex_setbox:D #1 \tex_box:D #2 }
\box_set_eq_drop:cc 27068 \cs_generate_variant:Nn \box_set_eq_drop:NN { c , Nc , cc }
\box_gset_eq_drop:NN 27069 \cs_generate_variant:Nn \box_gset_eq_drop:NN { c , Nc , cc }
\box_gset_eq_drop:cN 27070
\box_gset_eq_drop:Nc 27071 \prg_new_eq_conditional:NNn \box_if_exist:N \cs_if_exist:N
\box_gset_eq_drop:cc 27072 { TF , T , F , p }
\box_if_exist_p:N 27073 \prg_new_eq_conditional:NNn \box_if_exist:c \cs_if_exist:c
\box_if_exist_p:c 27074 { TF , T , F , p }
\box_if_exist:NTF
\box_if_exist:cTF

```

Copies of the cs functions defined in l3basics.

41.3 Measuring and setting box dimensions

Accessing the height, depth, and width of a $\langle box \rangle$ register.

```

\box_ht:N 27075 \cs_new_eq:NN \box_ht:N \tex_ht:D
\box_dp:N 27076 \cs_new_eq:NN \box_dp:N \tex_dp:D
\box_wd:N 27077 \cs_new_eq:NN \box_wd:N \tex_wd:D
\box_ht:c 27078 \cs_generate_variant:Nn \box_ht:N { c }
\box_dp:c 27079 \cs_generate_variant:Nn \box_dp:N { c }
\box_wd:c 27080 \cs_generate_variant:Nn \box_wd:N { c }

\box_set_ht:Nn 27081 \cs_new_protected:Npn \box_set_dp:Nn #1#2
\box_set_ht:cn {
\box_gset_ht:Nn 27082 {
\box_gset_ht:cn 27083 \tex_setbox:D #1 = \tex_copy:D #1
\box_set_dp:Nn 27084 \box_dp:N #1 \__box_dim_eval:n {#2}
\box_set_dp:cn 27085 }
\box_gset_dp:Nn 27086 \cs_generate_variant:Nn \box_set_dp:Nn { c }
\box_gset_dp:cn 27087 \cs_new_protected:Npn \box_gset_dp:Nn #1#2
\box_set_wd:Nn 27088 { \box_dp:N #1 \__box_dim_eval:n {#2} }
\box_set_wd:cn 27089 \cs_generate_variant:Nn \box_gset_dp:Nn { c }
\box_gset_wd:Nn 27090 \cs_new_protected:Npn \box_set_ht:Nn #1#2
\box_gset_wd:cn 27091 {
\box_ht:N #1 \__box_dim_eval:n {#2}
\box_wd:N #1 \__box_dim_eval:n {#2}
\cs_generate_variant:Nn \box_set_ht:Nn { c }
\cs_new_protected:Npn \box_gset_ht:Nn #1#2
{ \box_ht:N #1 \__box_dim_eval:n {#2} }
\cs_generate_variant:Nn \box_gset_ht:Nn { c }
\cs_new_protected:Npn \box_set_wd:Nn #1#2
{
\tex_setbox:D #1 = \tex_copy:D #1
\box_wd:N #1 \__box_dim_eval:n {#2}
\cs_generate_variant:Nn \box_set_wd:Nn { c }
\cs_new_protected:Npn \box_gset_wd:Nn #1#2
{ \box_wd:N #1 \__box_dim_eval:n {#2} }
\cs_generate_variant:Nn \box_gset_wd:Nn { c }

```

Setting the size whilst respecting local scope requires copying; the same issue does not come up when working globally. When debugging, the dimension expression #2 is surrounded by parentheses to catch early termination.

41.4 Using boxes

Using a $\langle box \rangle$. These are just T_EX primitives with meaningful names.

```

\box_use_drop:N 27108 \cs_new_eq:NN \box_use_drop:N \tex_box:D
\box_use_drop:c 27109 \cs_new_eq:NN \box_use:N \tex_copy:D
\box_use:N       27110 \cs_generate_variant:Nn \box_use_drop:N { c }
\box_use:c       27111 \cs_generate_variant:Nn \box_use:N { c }

```

Move box material in different directions. When debugging, the dimension expression #1 is surrounded by parentheses to catch early termination.

```

\box_move_left:nn 27112 \cs_new_protected:Npn \box_move_left:nn #1#2
\box_move_right:nn 27113 { \tex_moveleft:D \_box_dim_eval:n {#1} #2 }
\box_move_up:nn   27114 \cs_new_protected:Npn \box_move_right:nn #1#2
\box_move_down:nn 27115 { \tex_moveright:D \_box_dim_eval:n {#1} #2 }
                  27116 \cs_new_protected:Npn \box_move_up:nn #1#2
                  27117 { \tex_raise:D \_box_dim_eval:n {#1} #2 }
                  27118 \cs_new_protected:Npn \box_move_down:nn #1#2
                  27119 { \tex_lower:D \_box_dim_eval:n {#1} #2 }

```

41.5 Box conditionals

The primitives for testing if a $\langle box \rangle$ is empty/void or which type of box it is.

```

\if_hbox:N 27120 \cs_new_eq:NN \if_hbox:N \tex_ifhbox:D
\if_vbox:N 27121 \cs_new_eq:NN \if_vbox:N \tex_ifvbox:D
\if_box_empty:N 27122 \cs_new_eq:NN \if_box_empty:N \tex_ifvoid:D

```

```

\box_if_horizontal_p:N 27123 \prg_new_conditional:Npnn \box_if_horizontal:N #1 { p , T , F , TF }
\box_if_horizontal_p:c 27124 { \if_hbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_horizontal:N $\underline{TF}$  27125 \prg_new_conditional:Npnn \box_if_vertical:N #1 { p , T , F , TF }
\box_if_horizontal:c $\underline{TF}$  27126 { \if_vbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_vertical_p:N 27127 \prg_generate_conditional_variant:Nnn \box_if_horizontal:N
\box_if_vertical_p:c 27128 { c } { p , T , F , TF }
\box_if_vertical:N $\underline{TF}$  27129 \prg_generate_conditional_variant:Nnn \box_if_vertical:N
\box_if_vertical:c $\underline{TF}$  27130 { c } { p , T , F , TF }

```

Testing if a $\langle box \rangle$ is empty/void.

```

\box_if_empty_p:N 27131 \prg_new_conditional:Npnn \box_if_empty:N #1 { p , T , F , TF }
\box_if_empty_p:c 27132 { \if_box_empty:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_empty:N $\underline{TF}$  27133 \prg_generate_conditional_variant:Nnn \box_if_empty:N
\box_if_empty:c $\underline{TF}$  27134 { c } { p , T , F , TF }

```

(End definition for $\backslash box_new:N$ and others. These functions are documented on page 235.)

41.6 The last box inserted

```

\box_set_to_last:N Set a box to the previous box.
\box_set_to_last:c 27135 \cs_new_protected:Npn \box_set_to_last:N #1
\box_gset_to_last:N 27136 { \tex_setbox:D #1 \tex_lastbox:D }
\box_gset_to_last:c 27137 \cs_new_protected:Npn \box_gset_to_last:N #1
                  27138 { \tex_global:D \tex_setbox:D #1 \tex_lastbox:D }
                  27139 \cs_generate_variant:Nn \box_set_to_last:N { c }
                  27140 \cs_generate_variant:Nn \box_gset_to_last:N { c }

```

(End definition for `\box_set_to_last:N` and `\box_gset_to_last:N`. These functions are documented on page 237.)

41.7 Constant boxes

`\c_empty_box` A box we never use.

```
27141 \box_new:N \c_empty_box
```

(End definition for `\c_empty_box`. This variable is documented on page 237.)

41.8 Scratch boxes

`\l_tmpa_box` Scratch boxes.

```
\l_tmpb_box 27142 \box_new:N \l_tmpa_box
```

```
\g_tmpa_box 27143 \box_new:N \l_tmpb_box
```

```
\g_tmpb_box 27144 \box_new:N \g_tmpa_box
```

```
27145 \box_new:N \g_tmpb_box
```

(End definition for `\l_tmpa_box` and others. These variables are documented on page 238.)

41.9 Viewing box contents

TeX's `\showbox` is not really that helpful in many cases, and it is also inconsistent with other L^AT_EX3 show functions as it does not actually shows material in the terminal. So we provide a richer set of functionality.

`\box_show:N` Essentially a wrapper around the internal function, but evaluating the breadth and depth arguments now outside the group.

`\box_show:c`

`\box_show:Nnn`

`\box_show:cnn`

```
27146 \cs_new_protected:Npn \box_show:N #1
```

```
{ \box_show:Nnn #1 \c_max_int \c_max_int }
```

```
27148 \cs_generate_variant:Nn \box_show:N { c }
```

```
27149 \cs_new_protected:Npn \box_show:Nnn #1#2#3
```

```
{ \__box_show:NNff 1 #1 { \int_eval:n {#2} } { \int_eval:n {#3} } }
```

```
27151 \cs_generate_variant:Nn \box_show:Nnn { c }
```

(End definition for `\box_show:N` and `\box_show:Nnn`. These functions are documented on page 238.)

`\box_log:N` Getting TeX to write to the log without interruption the run is done by altering the interaction mode. For that, the ϵ -TeX extensions are needed.

`\box_log:c`

`\box_log:Nnn`

`\box_log:cnn`

`__box_log:nNnn`

```
27152 \cs_new_protected:Npn \box_log:N #1
```

```
{ \box_log:Nnn #1 \c_max_int \c_max_int }
```

```
27154 \cs_generate_variant:Nn \box_log:N { c }
```

```
27155 \cs_new_protected:Npn \box_log:Nnn
```

```
{ \exp_args:No \__box_log:nNnn { \tex_the:D \tex_interactionmode:D } }
```

```
27157 \cs_new_protected:Npn \__box_log:nNnn #1#2#3#4
```

```
{
```

```
27159 \int_set:Nn \tex_interactionmode:D { 0 }
```

```
27160 \__box_show:NNff 0 #2 { \int_eval:n {#3} } { \int_eval:n {#4} }
```

```
27161 \int_set:Nn \tex_interactionmode:D {#1}
```

```
27162 }
```

```
27163 \cs_generate_variant:Nn \box_log:Nnn { c }
```

(End definition for `\box_log:N`, `\box_log:Nnn`, and `__box_log:nNnn`. These functions are documented on page 238.)

`__box_show:NNnn` The internal auxiliary to actually do the output uses a group to deal with breadth and
`__box_show:NNff` depth values. The `\use:n` here gives better output appearance. Setting `\tracingonline`
and `\errorcontextlines` is used to control what appears in the terminal.

```

27164 \cs_new_protected:Npn \__box_show:NNnn #1#2#3#4
27165 {
27166   \box_if_exist:NTF #2
27167   {
27168     \group_begin:
27169     \int_set:Nn \tex_showboxbreadth:D {#3}
27170     \int_set:Nn \tex_showboxdepth:D {#4}
27171     \int_set:Nn \tex_tracingonline:D {#1}
27172     \int_set:Nn \tex_errorcontextlines:D { -1 }
27173     \tex_showbox:D \use:n {#2}
27174   \group_end:
27175   }
27176   {
27177     \__kernel_msg_error:nxx { kernel } { variable-not-defined }
27178     { \token_to_str:N #2 }
27179   }
27180 }
27181 \cs_generate_variant:Nn \__box_show:NNnn { NNff }

```

(End definition for `__box_show:NNnn`.)

41.10 Horizontal mode boxes

`\hbox:n` (The test suite for this command, and others in this file, is `m3box002.lvt`.)
Put a horizontal box directly into the input stream.

```

27182 \cs_new_protected:Npn \hbox:n #1
27183 { \tex_hbox:D \scan_stop: { \color_group_begin: #1 \color_group_end: } }

```

(End definition for `\hbox:n`. This function is documented on page 238.)

```

\hbox_set:Nn
\hbox_set:cn
\hbox_gset:Nn
\hbox_gset:cn
27184 \cs_new_protected:Npn \hbox_set:Nn #1#2
27185 {
27186   \tex_setbox:D #1 \tex_hbox:D
27187   { \color_group_begin: #2 \color_group_end: }
27188 }
27189 \cs_new_protected:Npn \hbox_gset:Nn #1#2
27190 {
27191   \tex_global:D \tex_setbox:D #1 \tex_hbox:D
27192   { \color_group_begin: #2 \color_group_end: }
27193 }
27194 \cs_generate_variant:Nn \hbox_set:Nn { c }
27195 \cs_generate_variant:Nn \hbox_gset:Nn { c }

```

(End definition for `\hbox_set:Nn` and `\hbox_gset:Nn`. These functions are documented on page 239.)

`\hbox_set_to_wd:Nnn` Storing material in a horizontal box with a specified width. Again, put the dimension
`\hbox_set_to_wd:cn` expression in parentheses when debugging.

```

\hbox_gset_to_wd:Nnn
\hbox_gset_to_wd:cn
27196 \cs_new_protected:Npn \hbox_set_to_wd:Nnn #1#2#3
27197 {
27198   \tex_setbox:D #1 \tex_hbox:D to \__box_dim_eval:n {#2}

```

```

27199     { \color_group_begin: #3 \color_group_end: }
27200   }
27201 \cs_new_protected:Npn \hbox_gset_to_wd:Nnn #1#2#3
27202 {
27203   \tex_global:D \tex_setbox:D #1 \tex_hbox:D to \_box_dim_eval:n {#2}
27204   { \color_group_begin: #3 \color_group_end: }
27205 }
27206 \cs_generate_variant:Nn \hbox_set_to_wd:Nnn { c }
27207 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnn { c }

```

(End definition for `\hbox_set_to_wd:Nnn` and `\hbox_gset_to_wd:Nnn`. These functions are documented on page 239.)

`\hbox_set:Nw` Storing material in a horizontal box. This type is useful in environment definitions.

```

\hbox_set:cw 27208 \cs_new_protected:Npn \hbox_set:Nw #1
\hbox_gset:Nw 27209 {
\hbox_gset:cw 27210   \tex_setbox:D #1 \tex_hbox:D
\hbox_set_end: 27211   \c_group_begin_token
\hbox_gset_end: 27212   \color_group_begin:
27213 }
27214 \cs_new_protected:Npn \hbox_gset:Nw #1
27215 {
27216   \tex_global:D \tex_setbox:D #1 \tex_hbox:D
27217   \c_group_begin_token
27218   \color_group_begin:
27219 }
27220 \cs_generate_variant:Nn \hbox_set:Nw { c }
27221 \cs_generate_variant:Nn \hbox_gset:Nw { c }
27222 \cs_new_protected:Npn \hbox_set_end:
27223 {
27224   \color_group_end:
27225   \c_group_end_token
27226 }
27227 \cs_new_eq:NN \hbox_gset_end: \hbox_set_end:

```

(End definition for `\hbox_set:Nw` and others. These functions are documented on page 239.)

`\hbox_set_to_wd:Nnw` Combining the above ideas.

```

\hbox_set_to_wd:cnw 27228 \cs_new_protected:Npn \hbox_set_to_wd:Nnw #1#2
\hbox_gset_to_wd:Nnw 27229 {
\hbox_gset_to_wd:cnw 27230   \tex_setbox:D #1 \tex_hbox:D to \_box_dim_eval:n {#2}
27231   \c_group_begin_token
27232   \color_group_begin:
27233 }
27234 \cs_new_protected:Npn \hbox_gset_to_wd:Nnw #1#2
27235 {
27236   \tex_global:D \tex_setbox:D #1 \tex_hbox:D to \_box_dim_eval:n {#2}
27237   \c_group_begin_token
27238   \color_group_begin:
27239 }
27240 \cs_generate_variant:Nn \hbox_set_to_wd:Nnw { c }
27241 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnw { c }

```

(End definition for `\hbox_set_to_wd:Nnw` and `\hbox_gset_to_wd:Nnw`. These functions are documented on page 239.)

`\hbox_to_wd:nn` Put a horizontal box directly into the input stream.

`\hbox_to_zero:n`

```

27242 \cs_new_protected:Npn \hbox_to_wd:nn #1#2
27243 {
27244     \tex_hbox:D to \__box_dim_eval:n {#1}
27245     { \color_group_begin: #2 \color_group_end: }
27246 }
27247 \cs_new_protected:Npn \hbox_to_zero:n #1
27248 {
27249     \tex_hbox:D to \c_zero_dim
27250     { \color_group_begin: #1 \color_group_end: }
27251 }

```

(End definition for `\hbox_to_wd:nn` and `\hbox_to_zero:n`. These functions are documented on page 239.)

`\hbox_overlap_left:n` Put a zero-sized box with the contents pushed against one side (which makes it stick out on the other) directly into the input stream.

`\hbox_overlap_right:n`

```

27252 \cs_new_protected:Npn \hbox_overlap_left:n #1
27253 { \hbox_to_zero:n { \tex_hss:D #1 } }
27254 \cs_new_protected:Npn \hbox_overlap_right:n #1
27255 { \hbox_to_zero:n { #1 \tex_hss:D } }

```

(End definition for `\hbox_overlap_left:n` and `\hbox_overlap_right:n`. These functions are documented on page 239.)

`\hbox_unpack:N` Unpacking a box and if requested also clear it.

`\hbox_unpack:c`

`\hbox_unpack_drop:N`

`\hbox_unpack_drop:c`

```

27256 \cs_new_eq:NN \hbox_unpack:N \tex_unhcopy:D
27257 \cs_new_eq:NN \hbox_unpack_drop:N \tex_unhbox:D
27258 \cs_generate_variant:Nn \hbox_unpack:N { c }
27259 \cs_generate_variant:Nn \hbox_unpack_drop:N { c }

```

(End definition for `\hbox_unpack:N` and `\hbox_unpack_drop:N`. These functions are documented on page 239.)

41.11 Vertical mode boxes

TeX ends these boxes directly with the internal *end_graf* routine. This means that there is no `\par` at the end of vertical boxes unless we insert one. Thus all vertical boxes include a `\par` just before closing the color group.

`\vbox:n` The following test files are used for this code: *m3box003.lvt*.

The following test files are used for this code: *m3box003.lvt*.

`\vbox_top:n` Put a vertical box directly into the input stream.

```

27260 \cs_new_protected:Npn \vbox:n #1
27261 { \tex_vbox:D { \color_group_begin: #1 \par \color_group_end: } }
27262 \cs_new_protected:Npn \vbox_top:n #1
27263 { \tex_vtop:D { \color_group_begin: #1 \par \color_group_end: } }

```

(End definition for `\vbox:n` and `\vbox_top:n`. These functions are documented on page 240.)

\vbox_to_ht:nn Put a vertical box directly into the input stream.

```

\vbox_to_zero:n 27264 \cs_new_protected:Npn \vbox_to_ht:nn #1#2
\vbox_to_ht:nn 27265 {
\vbox_to_zero:n 27266 \tex_vbox:D to \__box_dim_eval:n {#1}
27267 { \color_group_begin: #2 \par \color_group_end: }
27268 }
27269 \cs_new_protected:Npn \vbox_to_zero:n #1
27270 {
27271 \tex_vbox:D to \c_zero_dim
27272 { \color_group_begin: #1 \par \color_group_end: }
27273 }

```

(End definition for \vbox_to_ht:nn and others. These functions are documented on page 240.)

\vbox_set:Nn Storing material in a vertical box with a natural height.

```

\vbox_set:cn 27274 \cs_new_protected:Npn \vbox_set:Nn #1#2
\vbox_gset:Nn 27275 {
\vbox_gset:cn 27276 \tex_setbox:D #1 \tex_vbox:D
27277 { \color_group_begin: #2 \par \color_group_end: }
27278 }
27279 \cs_new_protected:Npn \vbox_gset:Nn #1#2
27280 {
27281 \tex_global:D \tex_setbox:D #1 \tex_vbox:D
27282 { \color_group_begin: #2 \par \color_group_end: }
27283 }
27284 \cs_generate_variant:Nn \vbox_set:Nn { c }
27285 \cs_generate_variant:Nn \vbox_gset:Nn { c }

```

(End definition for \vbox_set:Nn and \vbox_gset:Nn. These functions are documented on page 240.)

\vbox_set_top:Nn Storing material in a vertical box with a natural height and reference point at the baseline of the first object in the box.

```

\vbox_set_top:cn 27286 \cs_new_protected:Npn \vbox_set_top:Nn #1#2
\vbox_gset_top:Nn 27287 {
\vbox_gset_top:cn 27288 \tex_setbox:D #1 \tex_vtop:D
27289 { \color_group_begin: #2 \par \color_group_end: }
27290 }
27291 \cs_new_protected:Npn \vbox_gset_top:Nn #1#2
27292 {
27293 \tex_global:D \tex_setbox:D #1 \tex_vtop:D
27294 { \color_group_begin: #2 \par \color_group_end: }
27295 }
27296 \cs_generate_variant:Nn \vbox_set_top:Nn { c }
27297 \cs_generate_variant:Nn \vbox_gset_top:Nn { c }

```

(End definition for \vbox_set_top:Nn and \vbox_gset_top:Nn. These functions are documented on page 240.)

\vbox_set_to_ht:Nnn Storing material in a vertical box with a specified height.

```

\vbox_set_to_ht:cnn 27298 \cs_new_protected:Npn \vbox_set_to_ht:Nnn #1#2#3
\vbox_gset_to_ht:Nnn 27299 {
\vbox_gset_to_ht:cnn 27300 \tex_setbox:D #1 \tex_vbox:D to \__box_dim_eval:n {#2}
27301 { \color_group_begin: #3 \par \color_group_end: }
27302 }

```



```

27303 \cs_new_protected:Npn \vbox_gset_to_ht:Nnn #1#2#3
27304 {
27305     \tex_global:D \tex_setbox:D #1 \tex_vbox:D to \_box_dim_eval:n {#2}
27306     { \color_group_begin: #3 \par \color_group_end: }
27307 }
27308 \cs_generate_variant:Nn \vbox_set_to_ht:Nnn { c }
27309 \cs_generate_variant:Nn \vbox_gset_to_ht:Nnn { c }

```

(End definition for `\vbox_set_to_ht:Nnn` and `\vbox_gset_to_ht:Nnn`. These functions are documented on page 240.)

`\vbox_set:Nw` Storing material in a vertical box. This type is useful in environment definitions.
`\vbox_set:cw`
`\vbox_gset:Nw`
`\vbox_gset:cw`
`\vbox_set_end:`
`\vbox_gset_end:`

```

27310 \cs_new_protected:Npn \vbox_set:Nw #1
27311 {
27312     \tex_setbox:D #1 \tex_vbox:D
27313     \c_group_begin_token
27314     \color_group_begin:
27315 }
27316 \cs_new_protected:Npn \vbox_gset:Nw #1
27317 {
27318     \tex_global:D \tex_setbox:D #1 \tex_vbox:D
27319     \c_group_begin_token
27320     \color_group_begin:
27321 }
27322 \cs_generate_variant:Nn \vbox_set:Nw { c }
27323 \cs_generate_variant:Nn \vbox_gset:Nw { c }
27324 \cs_new_protected:Npn \vbox_set_end:
27325 {
27326     \par
27327     \color_group_end:
27328     \c_group_end_token
27329 }
27330 \cs_new_eq:NN \vbox_gset_end: \vbox_set_end:

```

(End definition for `\vbox_set:Nw` and others. These functions are documented on page 241.)

`\vbox_set_to_ht:Nnw` A combination of the above ideas.

```

\vbox_set_to_ht:cnw 27331 \cs_new_protected:Npn \vbox_set_to_ht:Nnw #1#2
\vbox_gset_to_ht:Nnw 27332 {
\vbox_gset_to_ht:cnw 27333     \tex_setbox:D #1 \tex_vbox:D to \_box_dim_eval:n {#2}
27334     \c_group_begin_token
27335     \color_group_begin:
27336 }
27337 \cs_new_protected:Npn \vbox_gset_to_ht:Nnw #1#2
27338 {
27339     \tex_global:D \tex_setbox:D #1 \tex_vbox:D to \_box_dim_eval:n {#2}
27340     \c_group_begin_token
27341     \color_group_begin:
27342 }
27343 \cs_generate_variant:Nn \vbox_set_to_ht:Nnw { c }
27344 \cs_generate_variant:Nn \vbox_gset_to_ht:Nnw { c }

```

(End definition for `\vbox_set_to_ht:Nnw` and `\vbox_gset_to_ht:Nnw`. These functions are documented on page 241.)

`\vbox_unpack:N` Unpacking a box and if requested also clear it.

`\vbox_unpack:c` 27345 `\cs_new_eq:NN \vbox_unpack:N \tex_unvcopy:D`

`\vbox_unpack_drop:N` 27346 `\cs_new_eq:NN \vbox_unpack_drop:N \tex_unvbox:D`

`\vbox_unpack_drop:c` 27347 `\cs_generate_variant:Nn \vbox_unpack:N { c }`

27348 `\cs_generate_variant:Nn \vbox_unpack_drop:N { c }`

(End definition for `\vbox_unpack:N` and `\vbox_unpack_drop:N`. These functions are documented on page 241.)

`\vbox_set_split_to_ht:NNn` Splitting a vertical box in two.

`\vbox_set_split_to_ht:cNn` 27349 `\cs_new_protected:Npn \vbox_set_split_to_ht:NNn #1#2#3`

`\vbox_set_split_to_ht:Ncn` 27350 `{ \tex_setbox:D #1 \tex_vsplit:D #2 to _box_dim_eval:n {#3} }`

`\vbox_set_split_to_ht:ccn` 27351 `\cs_generate_variant:Nn \vbox_set_split_to_ht:NNn { c , Nc , cc }`

`\vbox_gset_split_to_ht:NNn` 27352 `\cs_new_protected:Npn \vbox_gset_split_to_ht:NNn #1#2#3`

`\vbox_gset_split_to_ht:cNn` 27353 `{`

`\vbox_gset_split_to_ht:Ncn` 27354 `\tex_global:D \tex_setbox:D #1`

`\vbox_gset_split_to_ht:ccn` 27355 `\tex_vsplit:D #2 to _box_dim_eval:n {#3}`

27356 `}`

27357 `\cs_generate_variant:Nn \vbox_gset_split_to_ht:NNn { c , Nc , cc }`

(End definition for `\vbox_set_split_to_ht:NNn` and `\vbox_gset_split_to_ht:NNn`. These functions are documented on page 241.)

41.12 Affine transformations

`\l__box_angle_fp` When rotating boxes, the angle itself may be needed by the engine-dependent code. This is done using the `fp` module so that the value is tidied up properly.

27358 `\fp_new:N \l__box_angle_fp`

(End definition for `\l__box_angle_fp`.)

`\l__box_cos_fp` These are used to hold the calculated sine and cosine values while carrying out a rotation.

`\l__box_sin_fp` 27359 `\fp_new:N \l__box_cos_fp`

27360 `\fp_new:N \l__box_sin_fp`

(End definition for `\l__box_cos_fp` and `\l__box_sin_fp`.)

`\l__box_top_dim` These are the positions of the four edges of a box before manipulation.

`\l__box_bottom_dim` 27361 `\dim_new:N \l__box_top_dim`

`\l__box_left_dim` 27362 `\dim_new:N \l__box_bottom_dim`

`\l__box_right_dim` 27363 `\dim_new:N \l__box_left_dim`

27364 `\dim_new:N \l__box_right_dim`

(End definition for `\l__box_top_dim` and others.)

`\l__box_top_new_dim` These are the positions of the four edges of a box after manipulation.

`\l__box_bottom_new_dim` 27365 `\dim_new:N \l__box_top_new_dim`

`\l__box_left_new_dim` 27366 `\dim_new:N \l__box_bottom_new_dim`

`\l__box_right_new_dim` 27367 `\dim_new:N \l__box_left_new_dim`

27368 `\dim_new:N \l__box_right_new_dim`

(End definition for `\l__box_top_new_dim` and others.)

`\l__box_internal_box` Scratch space, but also needed by some parts of the driver.

27369 `\box_new:N \l__box_internal_box`




Figure 1: Co-ordinates of a box prior to rotation.

(End definition for `\l_box_internal_box`.)

`\box_rotate:Nn` Rotation of a box starts with working out the relevant sine and cosine. The actual rotation is in an auxiliary to keep the flow slightly clearer

`\box_grotate:Nn`

`\box_grotate:cn`

`__box_rotate:NnN`

`__box_rotate:N`

`__box_rotate_xdir:nnN`

`__box_rotate_ydir:nnN`

`__box_rotate_quadrant_one:`

`__box_rotate_quadrant_two:`

`__box_rotate_quadrant_three:`

`__box_rotate_quadrant_four:`

```

27370 \cs_new_protected:Npn \box_rotate:Nn #1#2
27371 { \__box_rotate:NnN #1 {#2} \hbox_set:Nn }
27372 \cs_generate_variant:Nn \box_rotate:Nn { c }
27373 \cs_new_protected:Npn \box_grotate:Nn #1#2
27374 { \__box_rotate:NnN #1 {#2} \hbox_gset:Nn }
27375 \cs_generate_variant:Nn \box_grotate:Nn { c }
27376 \cs_new_protected:Npn \__box_rotate:NnN #1#2#3
27377 {
27378   #3 #1
27379   {
27380     \fp_set:Nn \l_box_angle_fp {#2}
27381     \fp_set:Nn \l_box_sin_fp { sind ( \l_box_angle_fp ) }
27382     \fp_set:Nn \l_box_cos_fp { cosd ( \l_box_angle_fp ) }
27383     \__box_rotate:N #1
27384   }
27385 }

```

The edges of the box are then recorded: the left edge is always at zero. Rotation of the four edges then takes place: this is most efficiently done on a quadrant by quadrant basis.

```

27386 \cs_new_protected:Npn \__box_rotate:N #1
27387 {
27388   \dim_set:Nn \l_box_top_dim { \box_ht:N #1 }
27389   \dim_set:Nn \l_box_bottom_dim { -\box_dp:N #1 }
27390   \dim_set:Nn \l_box_right_dim { \box_wd:N #1 }
27391   \dim_zero:N \l_box_left_dim

```

The next step is to work out the x and y coordinates of vertices of the rotated box in relation to its original coordinates. The box can be visualized with vertices B , C , D and E is illustrated (Figure 1). The vertex O is the reference point on the baseline, and in this implementation is also the centre of rotation. The formulae are, for a point P and angle α :

$$\begin{aligned}
 P'_x &= P_x - O_x \\
 P'_y &= P_y - O_y \\
 P''_x &= (P'_x \cos(\alpha)) - (P'_y \sin(\alpha)) \\
 P''_y &= (P'_x \sin(\alpha)) + (P'_y \cos(\alpha)) \\
 P'''_x &= P''_x + O_x + L_x \\
 P'''_y &= P''_y + O_y
 \end{aligned}$$

The “extra” horizontal translation L_x at the end is calculated so that the leftmost point of the resulting box has x -coordinate 0. This is desirable as \TeX boxes must have the reference point at the left edge of the box. (As O is always $(0,0)$, this part of the calculation is omitted here.)

```

27392 \fp_compare:nNnTF \l__box_sin_fp > \c_zero_fp
27393 {
27394     \fp_compare:nNnTF \l__box_cos_fp > \c_zero_fp
27395     { \__box_rotate_quadrant_one: }
27396     { \__box_rotate_quadrant_two: }
27397 }
27398 {
27399     \fp_compare:nNnTF \l__box_cos_fp < \c_zero_fp
27400     { \__box_rotate_quadrant_three: }
27401     { \__box_rotate_quadrant_four: }
27402 }

```

The position of the box edges are now known, but the box at this stage be misplaced relative to the current \TeX reference point. So the content of the box is moved such that the reference point of the rotated box is in the same place as the original.

```

27403 \hbox_set:Nn \l__box_internal_box { \box_use:N #1 }
27404 \hbox_set:Nn \l__box_internal_box
27405 {
27406     \tex_kern:D -\l__box_left_new_dim
27407     \hbox:n
27408     {
27409         \__box_backend_rotate:Nn
27410         \l__box_internal_box
27411         \l__box_angle_fp
27412     }
27413 }

```

Tidy up the size of the box so that the material is actually inside the bounding box. The result can then be used to reset the original box.

```

27414 \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
27415 \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
27416 \box_set_wd:Nn \l__box_internal_box
27417 { \l__box_right_new_dim - \l__box_left_new_dim }
27418 \box_use_drop:N \l__box_internal_box
27419 }

```

These functions take a general point $(\#1,\#2)$ and rotate its location about the origin, using the previously-set sine and cosine values. Each function gives only one component of the location of the updated point. This is because for rotation of a box each step needs only one value, and so performance is gained by avoiding working out both x' and y' at the same time. Contrast this with the equivalent function in the `l3coffins` module, where both parts are needed.

```

27420 \cs_new_protected:Npn \__box_rotate_xdir:nnN #1#2#3
27421 {
27422     \dim_set:Nn #3
27423     {
27424         \fp_to_dim:n
27425         {
27426             \l__box_cos_fp * \dim_to_fp:n {#1}
27427             - \l__box_sin_fp * \dim_to_fp:n {#2}

```

```

27428     }
27429   }
27430 }
27431 \cs_new_protected:Npn \__box_rotate_ydir:nnN #1#2#3
27432 {
27433   \dim_set:Nn #3
27434   {
27435     \fp_to_dim:n
27436     {
27437       \l__box_sin_fp * \dim_to_fp:n {#1}
27438       + \l__box_cos_fp * \dim_to_fp:n {#2}
27439     }
27440   }
27441 }

```

Rotation of the edges is done using a different formula for each quadrant. In every case, the top and bottom edges only need the resulting y -values, whereas the left and right edges need the x -values. Each case is a question of picking out which corner ends up at with the maximum top, bottom, left and right value. Doing this by hand means a lot less calculating and avoids lots of comparisons.

```

27442 \cs_new_protected:Npn \__box_rotate_quadrant_one:
27443 {
27444   \__box_rotate_ydir:nnN \l__box_right_dim \l__box_top_dim
27445   \l__box_top_new_dim
27446   \__box_rotate_ydir:nnN \l__box_left_dim \l__box_bottom_dim
27447   \l__box_bottom_new_dim
27448   \__box_rotate_xdir:nnN \l__box_left_dim \l__box_top_dim
27449   \l__box_left_new_dim
27450   \__box_rotate_xdir:nnN \l__box_right_dim \l__box_bottom_dim
27451   \l__box_right_new_dim
27452 }
27453 \cs_new_protected:Npn \__box_rotate_quadrant_two:
27454 {
27455   \__box_rotate_ydir:nnN \l__box_right_dim \l__box_bottom_dim
27456   \l__box_top_new_dim
27457   \__box_rotate_ydir:nnN \l__box_left_dim \l__box_top_dim
27458   \l__box_bottom_new_dim
27459   \__box_rotate_xdir:nnN \l__box_right_dim \l__box_top_dim
27460   \l__box_left_new_dim
27461   \__box_rotate_xdir:nnN \l__box_left_dim \l__box_bottom_dim
27462   \l__box_right_new_dim
27463 }
27464 \cs_new_protected:Npn \__box_rotate_quadrant_three:
27465 {
27466   \__box_rotate_ydir:nnN \l__box_left_dim \l__box_bottom_dim
27467   \l__box_top_new_dim
27468   \__box_rotate_ydir:nnN \l__box_right_dim \l__box_top_dim
27469   \l__box_bottom_new_dim
27470   \__box_rotate_xdir:nnN \l__box_right_dim \l__box_bottom_dim
27471   \l__box_left_new_dim
27472   \__box_rotate_xdir:nnN \l__box_left_dim \l__box_top_dim
27473   \l__box_right_new_dim
27474 }
27475 \cs_new_protected:Npn \__box_rotate_quadrant_four:

```

```

27476 {
27477   \__box_rotate_ydir:nnN \l__box_left_dim \l__box_top_dim
27478   \l__box_top_new_dim
27479   \__box_rotate_ydir:nnN \l__box_right_dim \l__box_bottom_dim
27480   \l__box_bottom_new_dim
27481   \__box_rotate_xdir:nnN \l__box_left_dim \l__box_bottom_dim
27482   \l__box_left_new_dim
27483   \__box_rotate_xdir:nnN \l__box_right_dim \l__box_top_dim
27484   \l__box_right_new_dim
27485 }

```

(End definition for `\box_rotate:Nn` and others. These functions are documented on page 245.)

`\l__box_scale_x_fp` Scaling is potentially-different in the two axes.
`\l__box_scale_y_fp`

```

27486 \fp_new:N \l__box_scale_x_fp
27487 \fp_new:N \l__box_scale_y_fp

```

(End definition for `\l__box_scale_x_fp` and `\l__box_scale_y_fp`.)

`\box_resize_to_wd_and_ht_plus_dp:Nnn` Resizing a box starts by working out the various dimensions of the existing box.

```

\box_resize_to_wd_and_ht_plus_dp:cmn
\box_gresize_to_wd_and_ht_plus_dp:Nnn
\box_gresize_to_wd_and_ht_plus_dp:cmn
\__box_resize_to_wd_and_ht_plus_dp:NnnN
\__box_resize_set_corners:N
  \__box_resize:N
  \__box_resize:NNN
27488 \cs_new_protected:Npn \box_resize_to_wd_and_ht_plus_dp:Nnn #1#2#3
27489 {
27490   \__box_resize_to_wd_and_ht_plus_dp:NnnN #1 {#2} {#3}
27491   \hbox_set:Nn
27492 }
27493 \cs_generate_variant:Nn \box_resize_to_wd_and_ht_plus_dp:Nnn { c }
27494 \cs_new_protected:Npn \box_gresize_to_wd_and_ht_plus_dp:Nnn #1#2#3
27495 {
27496   \__box_resize_to_wd_and_ht_plus_dp:NnnN #1 {#2} {#3}
27497   \hbox_gset:Nn
27498 }
27499 \cs_generate_variant:Nn \box_gresize_to_wd_and_ht_plus_dp:Nnn { c }
27500 \cs_new_protected:Npn \__box_resize_to_wd_and_ht_plus_dp:NnnN #1#2#3#4
27501 {
27502   #4 #1
27503   {
27504     \__box_resize_set_corners:N #1

```

The x -scaling and resulting box size is easy enough to work out: the dimension is that given as #2, and the scale is simply the new width divided by the old one.

```

27505   \fp_set:Nn \l__box_scale_x_fp
27506   { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }

```

The y -scaling needs both the height and the depth of the current box.

```

27507   \fp_set:Nn \l__box_scale_y_fp
27508   {
27509     \dim_to_fp:n {#3}
27510     / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim }
27511   }

```

Hand off to the auxiliary which does the rest of the work.

```

27512   \__box_resize:N #1
27513 }
27514 }
27515 \cs_new_protected:Npn \__box_resize_set_corners:N #1
27516 {

```

With at least one real scaling to do, the next phase is to find the new edge co-ordinates. In the x direction this is relatively easy: just scale the right edge. In the y direction, both dimensions have to be scaled, and this again needs the absolute scale value. Once that is all done, the common `resize/rescale` code can be employed.

(End definition for `\box_resize_to_wd_and_ht_plus_dp:Nnn` and others. These functions are documented on page 244.)

```

27537 \cs_new_protected:Npn \box_resize_to_ht:Nn #1#2
27538 { \__box_resize_to_ht:NnN #1 {#2} \hbox_set:Nn }
27539 \cs_generate_variant:Nn \box_resize_to_ht:Nn { c }
27540 \cs_new_protected:Npn \box_gresize_to_ht:Nn #1#2
27541 { \__box_resize_to_ht:NnN #1 {#2} \hbox_gset:Nn }
27542 \cs_generate_variant:Nn \box_gresize_to_ht:Nn { c }
27543 \cs_new_protected:Npn \__box_resize_to_ht:NnN #1#2#3
27544 {
27545     #3 #1
27546     {
27547         \__box_resize_set_corners:N #1
27548         \fp_set:Nn \l__box_scale_y_fp
27549         {
27550             \dim_to_fp:n {#2}
27551             / \dim_to_fp:n { \l__box_top_dim }
27552         }
27553         \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp
27554         \__box_resize:N #1
27555     }
27556 }
27557 \cs_new_protected:Npn \box_resize_to_ht_plus_dp:Nn #1#2

```

```

27558 { \_box_resize_to_ht_plus_dp:NnN #1 {#2} \hbox_set:Nn }
27559 \cs_generate_variant:Nn \box_resize_to_ht_plus_dp:Nn { c }
27560 \cs_new_protected:Npn \box_gresize_to_ht_plus_dp:Nn #1#2
27561 { \_box_resize_to_ht_plus_dp:NnN #1 {#2} \hbox_gset:Nn }
27562 \cs_generate_variant:Nn \box_gresize_to_ht_plus_dp:Nn { c }
27563 \cs_new_protected:Npn \_box_resize_to_ht_plus_dp:NnN #1#2#3
27564 {
27565   \hbox_set:Nn #1
27566   {
27567     \_box_resize_set_corners:N #1
27568     \fp_set:Nn \l__box_scale_y_fp
27569     {
27570       \dim_to_fp:n {#2}
27571       / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim }
27572     }
27573     \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp
27574     \_box_resize:N #1
27575   }
27576 }
27577 \cs_new_protected:Npn \box_resize_to_wd:Nn #1#2
27578 { \_box_resize_to_wd:NnN #1 {#2} \hbox_set:Nn }
27579 \cs_generate_variant:Nn \box_resize_to_wd:Nn { c }
27580 \cs_new_protected:Npn \box_gresize_to_wd:Nn #1#2
27581 { \_box_resize_to_wd:NnN #1 {#2} \hbox_gset:Nn }
27582 \cs_generate_variant:Nn \box_gresize_to_wd:Nn { c }
27583 \cs_new_protected:Npn \_box_resize_to_wd:NnN #1#2#3
27584 {
27585   #3 #1
27586   {
27587     \_box_resize_set_corners:N #1
27588     \fp_set:Nn \l__box_scale_x_fp
27589     { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
27590     \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp
27591     \_box_resize:N #1
27592   }
27593 }
27594 \cs_new_protected:Npn \box_resize_to_wd_and_ht:Nnn #1#2#3
27595 { \_box_resize_to_wd_and_ht:NnnN #1 {#2} {#3} \hbox_set:Nn }
27596 \cs_generate_variant:Nn \box_resize_to_wd_and_ht:Nnn { c }
27597 \cs_new_protected:Npn \box_gresize_to_wd_and_ht:Nnn #1#2#3
27598 { \_box_resize_to_wd_and_ht:NnnN #1 {#2} {#3} \hbox_gset:Nn }
27599 \cs_generate_variant:Nn \box_gresize_to_wd_and_ht:Nnn { c }
27600 \cs_new_protected:Npn \_box_resize_to_wd_and_ht:NnnN #1#2#3#4
27601 {
27602   #4 #1
27603   {
27604     \_box_resize_set_corners:N #1
27605     \fp_set:Nn \l__box_scale_x_fp
27606     { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
27607     \fp_set:Nn \l__box_scale_y_fp
27608     {
27609       \dim_to_fp:n {#3}
27610       / \dim_to_fp:n { \l__box_top_dim }
27611     }

```



```

27612         \_box_resize:N #1
27613     }
27614 }

```

(End definition for `\box_resize_to_ht:Nn` and others. These functions are documented on page 243.)

`\box_scale:Nnn` When scaling a box, setting the scaling itself is easy enough. The new dimensions are also relatively easy to find, allowing only for the need to keep them positive in all cases. `\box_scale:cnn` Once that is done then after a check for the trivial scaling a hand-off can be made to the common code. `\box_gscale:Nnn` The code here is split into two as this allows sharing with the auto-resizing functions. `\box_gscale:cnn`

```

\__box_scale:NnnN
\__box_scale:N
27615 \cs_new_protected:Npn \box_scale:Nnn #1#2#3
27616 { \__box_scale:NnnN #1 {#2} {#3} \hbox_set:Nn }
27617 \cs_generate_variant:Nn \box_scale:Nnn { c }
27618 \cs_new_protected:Npn \box_gscale:Nnn #1#2#3
27619 { \__box_scale:NnnN #1 {#2} {#3} \hbox_gset:Nn }
27620 \cs_generate_variant:Nn \box_gscale:Nnn { c }
27621 \cs_new_protected:Npn \__box_scale:NnnN #1#2#3#4
27622 {
27623     #4 #1
27624     {
27625         \fp_set:Nn \l__box_scale_x_fp {#2}
27626         \fp_set:Nn \l__box_scale_y_fp {#3}
27627         \__box_scale:N #1
27628     }
27629 }
27630 \cs_new_protected:Npn \__box_scale:N #1
27631 {
27632     \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
27633     \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
27634     \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
27635     \dim_zero:N \l__box_left_dim
27636     \dim_set:Nn \l__box_top_new_dim
27637     { \fp_abs:n { \l__box_scale_y_fp } \l__box_top_dim }
27638     \dim_set:Nn \l__box_bottom_new_dim
27639     { \fp_abs:n { \l__box_scale_y_fp } \l__box_bottom_dim }
27640     \dim_set:Nn \l__box_right_new_dim
27641     { \fp_abs:n { \l__box_scale_x_fp } \l__box_right_dim }
27642     \__box_resize_common:N #1
27643 }

```

(End definition for `\box_scale:Nnn` and others. These functions are documented on page 245.)

`\box_autosize_to_wd_and_ht:Nnn` Although autosizing a box uses dimensions, it has more in common in implementation with scaling. As such, most of the real work here is done elsewhere. `\box_autosize_to_wd_and_ht:cnn`

```

\box_gautosize_to_wd_and_ht:Nnn
\box_gautosize_to_wd_and_ht:cnn
27644 \cs_new_protected:Npn \box_autosize_to_wd_and_ht:Nnn #1#2#3
27645 { \__box_autosize:NnnN #1 {#2} {#3} { \box_ht:N #1 } \hbox_set:Nn }
27646 \cs_generate_variant:Nn \box_autosize_to_wd_and_ht:Nnn { c }
27647 \cs_new_protected:Npn \box_gautosize_to_wd_and_ht:Nnn #1#2#3
27648 { \__box_autosize:NnnN #1 {#2} {#3} { \box_ht:N #1 } \hbox_gset:Nn }
27649 \cs_generate_variant:Nn \box_gautosize_to_wd_and_ht:Nnn { c }
27650 \cs_new_protected:Npn \box_autosize_to_wd_and_ht_plus_dp:Nnn #1#2#3
27651 {
27652     \__box_autosize:NnnN #1 {#2} {#3} { \box_ht:N #1 + \box_dp:N #1 }

```

```

27653     \hbox_set:Nn
27654   }
27655   \cs_generate_variant:Nn \box_autosize_to_wd_and_ht_plus_dp:Nnn { c }
27656   \cs_new_protected:Npn \box_gautosize_to_wd_and_ht_plus_dp:Nnn #1#2#3
27657   {
27658     \__box_autosize:NnnN #1 {#2} {#3} { \box_ht:N #1 + \box_dp:N #1 }
27659     \hbox_gset:Nn
27660   }
27661   \cs_generate_variant:Nn \box_gautosize_to_wd_and_ht_plus_dp:Nnn { c }
27662   \cs_new_protected:Npn \__box_autosize:NnnN #1#2#3#4#5
27663   {
27664     #5 #1
27665     {
27666       \fp_set:Nn \l__box_scale_x_fp { ( #2 ) / \box_wd:N #1 }
27667       \fp_set:Nn \l__box_scale_y_fp { ( #3 ) / ( #4 ) }
27668       \fp_compare:nNnTF \l__box_scale_x_fp > \l__box_scale_y_fp
27669       { \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp }
27670       { \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp }
27671       \__box_scale:N #1
27672     }
27673   }

```

(End definition for `\box_autosize_to_wd_and_ht:Nnn` and others. These functions are documented on page 243.)

`__box_resize_common:N` The main resize function places its input into a box which start off with zero width, and includes the handles for engine rescaling.

```

27674   \cs_new_protected:Npn \__box_resize_common:N #1
27675   {
27676     \hbox_set:Nn \l__box_internal_box
27677     {
27678       \__box_backend_scale:Nnn
27679       #1
27680       \l__box_scale_x_fp
27681       \l__box_scale_y_fp
27682     }

```

The new height and depth can be applied directly.

```

27683     \fp_compare:nNnTF \l__box_scale_y_fp > \c_zero_fp
27684     {
27685       \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
27686       \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
27687     }
27688     {
27689       \box_set_dp:Nn \l__box_internal_box { \l__box_top_new_dim }
27690       \box_set_ht:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
27691     }

```

Things are not quite as obvious for the width, as the reference point needs to remain unchanged. For positive scaling factors resizing the box is all that is needed. However, for case of a negative scaling the material must be shifted such that the reference point ends up in the right place.

```

27692     \fp_compare:nNnTF \l__box_scale_x_fp < \c_zero_fp
27693     {
27694       \hbox_to_wd:nn { \l__box_right_new_dim }

```

```

27695         {
27696             \tex_kern:D \l__box_right_new_dim
27697             \box_use_drop:N \l__box_internal_box
27698             \tex_hss:D
27699         }
27700     }
27701     {
27702         \box_set_wd:Nn \l__box_internal_box { \l__box_right_new_dim }
27703         \hbox:n
27704         {
27705             \tex_kern:D \c_zero_dim
27706             \box_use_drop:N \l__box_internal_box
27707             \tex_hss:D
27708         }
27709     }
27710 }

```

(End definition for `__box_resize_common:N`.)

```
27711 \</initex | package>
```

42 l3coffins Implementation

```
27712 \<*initex | package>
```

```
27713 \<@@=coffin>
```

42.1 Coffins: data structures and general variables

`\l__coffin_internal_box` Scratch variables.

```

\l__coffin_internal_dim 27714 \box_new:N \l__coffin_internal_box
\l__coffin_internal_tl 27715 \dim_new:N \l__coffin_internal_dim
27716 \tl_new:N \l__coffin_internal_tl

```

(End definition for `\l__coffin_internal_box`, `\l__coffin_internal_dim`, and `\l__coffin_internal_tl`.)

`\c__coffin_corners_prop` The “corners”; of a coffin define the real content, as opposed to the \TeX bounding box. They all start off in the same place, of course.

```

27717 \prop_const_from_keyval:Nn \c__coffin_corners_prop
27718 {
27719     tl = { Opt } { Opt } ,
27720     tr = { Opt } { Opt } ,
27721     bl = { Opt } { Opt } ,
27722     br = { Opt } { Opt } ,
27723 }

```

(End definition for `\c__coffin_corners_prop`.)

`\c__coffin_poles_prop` Pole positions are given for horizontal, vertical and reference-point based values.

```

27724 \prop_const_from_keyval:Nn \c__coffin_poles_prop
27725 {
27726     l  = { Opt } { Opt } { Opt } { 1000pt } ,
27727     hc = { Opt } { Opt } { Opt } { 1000pt } ,
27728     r  = { Opt } { Opt } { Opt } { 1000pt } ,

```

```

27729      b = { Opt } { Opt } { 1000pt } { Opt } ,
27730      vc = { Opt } { Opt } { 1000pt } { Opt } ,
27731      t  = { Opt } { Opt } { 1000pt } { Opt } ,
27732      B  = { Opt } { Opt } { 1000pt } { Opt } ,
27733      H  = { Opt } { Opt } { 1000pt } { Opt } ,
27734      T  = { Opt } { Opt } { 1000pt } { Opt } ,
27735  }

```

(End definition for \c__coffin_poles_prop.)

\l__coffin_slope_A_fp Used for calculations of intersections.

```

\l__coffin_slope_B_fp
27736 \fp_new:N \l__coffin_slope_A_fp
27737 \fp_new:N \l__coffin_slope_B_fp

```

(End definition for \l__coffin_slope_A_fp and \l__coffin_slope_B_fp.)

\l__coffin_error_bool For propagating errors so that parts of the code can work around them.

```

27738 \bool_new:N \l__coffin_error_bool

```

(End definition for \l__coffin_error_bool.)

\l__coffin_offset_x_dim The offset between two sets of coffin handles when typesetting. These values are corrected from those requested in an alignment for the positions of the handles.

```

27739 \dim_new:N \l__coffin_offset_x_dim
27740 \dim_new:N \l__coffin_offset_y_dim

```

(End definition for \l__coffin_offset_x_dim and \l__coffin_offset_y_dim.)

\l__coffin_pole_a_tl Needed for finding the intersection of two poles.

```

\l__coffin_pole_b_tl
27741 \tl_new:N \l__coffin_pole_a_tl
27742 \tl_new:N \l__coffin_pole_b_tl

```

(End definition for \l__coffin_pole_a_tl and \l__coffin_pole_b_tl.)

\l__coffin_x_dim For calculating intersections and so forth.

```

\l__coffin_y_dim
27743 \dim_new:N \l__coffin_x_dim
\l__coffin_x_prime_dim
27744 \dim_new:N \l__coffin_y_dim
\l__coffin_y_prime_dim
27745 \dim_new:N \l__coffin_x_prime_dim
27746 \dim_new:N \l__coffin_y_prime_dim

```

(End definition for \l__coffin_x_dim and others.)

42.2 Basic coffin functions

There are a number of basic functions needed for creating coffins and placing material in them. This all relies on the following data structures.

__coffin_to_value:N Coffins are a two-part structure and we rely on the internal nature of box allocation to make everything work. As such, we need an interface to turn coffin identifiers into numbers. For the purposes here, the signature allowed is N despite the nature of the underlying primitive.

```

27747 \cs_new_eq:NN \__coffin_to_value:N \tex_number:D

```

(End definition for __coffin_to_value:N.)

`\coffin_if_exist_p:N` Several of the higher-level coffin functions would give multiple errors if the coffin does not exist. A cleaner way to handle this is provided here: both the box and the coffin structure are checked.

```

\coffin_if_exist_p:c
\coffin_if_exist:NTF
\coffin_if_exist:cTF
27748 \prg_new_conditional:Npnn \coffin_if_exist:N #1 { p , T , F , TF }
27749 {
27750   \cs_if_exist:NTF #1
27751   {
27752     \cs_if_exist:cTF { coffin ~ \__coffin_to_value:N #1 ~ poles }
27753     { \prg_return_true: }
27754     { \prg_return_false: }
27755   }
27756   { \prg_return_false: }
27757 }
27758 \prg_generate_conditional_variant:Nnn \coffin_if_exist:N
27759 { c } { p , T , F , TF }

```

(End definition for `\coffin_if_exist:NTF`. This function is documented on page 246.)

`__coffin_if_exist:NT` Several of the higher-level coffin functions would give multiple errors if the coffin does not exist. So a wrapper is provided to deal with this correctly, issuing an error on erroneous use.

```

27760 \cs_new_protected:Npn \__coffin_if_exist:NT #1#2
27761 {
27762   \coffin_if_exist:NTF #1
27763   { #2 }
27764   {
27765     \_kernel_msg_error:nxn { kernel } { unknown-coffin }
27766     { \token_to_str:N #1 }
27767   }
27768 }

```

(End definition for `__coffin_if_exist:NT`.)

`\coffin_clear:N` Clearing coffins means emptying the box and resetting all of the structures.

```

\coffin_clear:c
\coffin_gclear:N
\coffin_gclear:c
27769 \cs_new_protected:Npn \coffin_clear:N #1
27770 {
27771   \__coffin_if_exist:NT #1
27772   {
27773     \box_clear:N #1
27774     \__coffin_reset_structure:N #1
27775   }
27776 }
27777 \cs_generate_variant:Nn \coffin_clear:N { c }
27778 \cs_new_protected:Npn \coffin_gclear:N #1
27779 {
27780   \__coffin_if_exist:NT #1
27781   {
27782     \box_gclear:N #1
27783     \__coffin_greset_structure:N #1
27784   }
27785 }
27786 \cs_generate_variant:Nn \coffin_gclear:N { c }

```

(End definition for `\coffin_clear:N` and `\coffin_gclear:N`. These functions are documented on page 246.)

\coffin_new:N Creating a new coffin means making the underlying box and adding the data structures. The **\debug_suspend:** and **\debug_resume:** functions prevent **\prop_gclear_new:c** from writing useless information to the log file.

```

27787 \cs_new_protected:Npn \coffin_new:N #1
27788 {
27789   \box_new:N #1
27790   \debug_suspend:
27791   \prop_gclear_new:c { coffin ~ \__coffin_to_value:N #1 ~ corners }
27792   \prop_gclear_new:c { coffin ~ \__coffin_to_value:N #1 ~ poles }
27793   \prop_gset_eq:cN { coffin ~ \__coffin_to_value:N #1 ~ corners }
27794     \c__coffin_corners_prop
27795   \prop_gset_eq:cN { coffin ~ \__coffin_to_value:N #1 ~ poles }
27796     \c__coffin_poles_prop
27797   \debug_resume:
27798 }
27799 \cs_generate_variant:Nn \coffin_new:N { c }

```

(End definition for **\coffin_new:N**. This function is documented on page 246.)

\hcoffin_set:Nn Horizontal coffins are relatively easy: set the appropriate box, reset the structures then
\hcoffin_set:cn update the handle positions.

```

\hcoffin_gset:Nn 27800 \cs_new_protected:Npn \hcoffin_set:Nn #1#2
\hcoffin_gset:cn 27801 {
27802   \__coffin_if_exist:NT #1
27803   {
27804     \hbox_set:Nn #1
27805     {
27806       \color_ensure_current:
27807       #2
27808     }
27809     \__coffin_update:N #1
27810   }
27811 }
27812 \cs_generate_variant:Nn \hcoffin_set:Nn { c }
27813 \cs_new_protected:Npn \hcoffin_gset:Nn #1#2
27814 {
27815   \__coffin_if_exist:NT #1
27816   {
27817     \hbox_gset:Nn #1
27818     {
27819       \color_ensure_current:
27820       #2
27821     }
27822     \__coffin_gupdate:N #1
27823   }
27824 }
27825 \cs_generate_variant:Nn \hcoffin_gset:Nn { c }

```

(End definition for **\hcoffin_set:Nn** and **\hcoffin_gset:Nn**. These functions are documented on page 246.)

\vcoffin_set:Nnn Setting vertical coffins is more complex. First, the material is typeset with a given width.
\vcoffin_set:cnn The default handles and poles are set as for a horizontal coffin, before finding the top
\vcoffin_gset:Nnn baseline using a temporary box. No **\color_ensure_current:** here as that would add a
\vcoffin_gset:cnn

__coffin_set_vertical:NnnNN

whatsit to the start of the vertical box and mess up the location of the T pole (see *TEX by Topic* for discussion of the `\vtop` primitive, used to do the measuring).

```

27826 \cs_new_protected:Npn \vcoffin_set:Nnn #1#2#3
27827 {
27828   \__coffin_set_vertical:NnnNN #1 {#2} {#3}
27829   \vbox_set:Nn \__coffin_update:N
27830 }
27831 \cs_generate_variant:Nn \vcoffin_set:Nnn { c }
27832 \cs_new_protected:Npn \vcoffin_gset:Nnn #1#2#3
27833 {
27834   \__coffin_set_vertical:NnnNN #1 {#2} {#3}
27835   \vbox_gset:Nn \__coffin_gupdate:N
27836 }
27837 \cs_generate_variant:Nn \vcoffin_gset:Nnn { c }
27838 \cs_new_protected:Npn \__coffin_set_vertical:NnnNN #1#2#3#4#5
27839 {
27840   \__coffin_if_exist:NT #1
27841   {
27842     #4 #1
27843     {
27844       \dim_set:Nn \tex_hsize:D {#2}
27845       (*package)
27846       \dim_set_eq:NN \linewidth \tex_hsize:D
27847       \dim_set_eq:NN \columnwidth \tex_hsize:D
27848     }/package)
27849     #3
27850   }
27851   #5 #1
27852   \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
27853   \__coffin_set_pole:Nnx #1 { T }
27854   {
27855     { Opt }
27856     {
27857       \dim_eval:n
27858       { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
27859     }
27860     { 1000pt }
27861     { Opt }
27862   }
27863   \box_clear:N \l__coffin_internal_box
27864 }
27865 }

```

(End definition for `\vcoffin_set:Nnn`, `\vcoffin_gset:Nnn`, and `__coffin_set_vertical:NnnNN`. These functions are documented on page 247.)

`\hcoffin_set:Nw` These are the “begin”/“end” versions of the above: watch the grouping!

```

\hcoffin_set:cw 27866 \cs_new_protected:Npn \hcoffin_set:Nw #1
\hcoffin_gset:Nw 27867 {
\hcoffin_gset:cw 27868   \__coffin_if_exist:NT #1
\hcoffin_set_end: 27869   {
\hcoffin_gset_end: 27870     \hbox_set:Nw #1 \color_ensure_current:
27871     \cs_set_protected:Npn \hcoffin_set_end:
27872     {

```

```

27873         \hbox_set_end:
27874         \__coffin_update:N #1
27875     }
27876 }
27877 }
27878 \cs_generate_variant:Nn \hcoffin_set:Nw { c }
27879 \cs_new_protected:Npn \hcoffin_gset:Nw #1
27880 {
27881     \__coffin_if_exist:NT #1
27882     {
27883         \hbox_gset:Nw #1 \color_ensure_current:
27884         \cs_set_protected:Npn \hcoffin_gset_end:
27885         {
27886             \hbox_gset_end:
27887             \__coffin_gupdate:N #1
27888         }
27889     }
27890 }
27891 \cs_generate_variant:Nn \hcoffin_gset:Nw { c }
27892 \cs_new_protected:Npn \hcoffin_set_end: { }
27893 \cs_new_protected:Npn \hcoffin_gset_end: { }

```

(End definition for `\hcoffin_set:Nw` and others. These functions are documented on page 247.)

```

\vcoffin_set:Nnw The same for vertical coffins.
\vcoffin_set:cnw
\vcoffin_gset:Nnw
\vcoffin_gset:cnw
\__coffin_set_vertical:NnNNNNw
\vcoffin_set_end:
\vcoffin_gset_end:
27894 \cs_new_protected:Npn \vcoffin_set:Nnw #1#2
27895 {
27896     \__coffin_set_vertical:NnNNNNw #1 {#2} \vbox_set:Nw
27897     \vcoffin_set_end:
27898     \vbox_set_end: \__coffin_update:N
27899 }
27900 \cs_generate_variant:Nn \vcoffin_set:Nnw { c }
27901 \cs_new_protected:Npn \vcoffin_gset:Nnw #1#2
27902 {
27903     \__coffin_set_vertical:NnNNNNw #1 {#2} \vbox_gset:Nw
27904     \vcoffin_gset_end:
27905     \vbox_gset_end: \__coffin_gupdate:N
27906 }
27907 \cs_generate_variant:Nn \vcoffin_gset:Nnw { c }
27908 \cs_new_protected:Npn \__coffin_set_vertical:NnNNNNw #1#2#3#4#5#6
27909 {
27910     \__coffin_if_exist:NT #1
27911     {
27912         #3 #1
27913         \dim_set:Nn \tex_hsize:D {#2}
27914         \*package>
27915             \dim_set_eq:NN \linewidth \tex_hsize:D
27916             \dim_set_eq:NN \columnwidth \tex_hsize:D
27917         </package>
27918         \cs_set_protected:Npn #4
27919         {
27920             #5
27921             #6 #1
27922             \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }

```



```

27923         \__coffin_set_pole:Nnx #1 { T }
27924         {
27925             { Opt }
27926             {
27927                 \dim_eval:n
27928                 { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
27929             }
27930             { 1000pt }
27931             { Opt }
27932         }
27933         \box_clear:N \l__coffin_internal_box
27934     }
27935 }
27936 }
27937 \cs_new_protected:Npn \vcoffin_set_end: { }
27938 \cs_new_protected:Npn \vcoffin_gset_end: { }

```

(End definition for \vcoffin_set:Nnw and others. These functions are documented on page 247.)

```

\coffin_set_eq:NN Setting two coffins equal is just a wrapper around other functions.
\coffin_set_eq:Nc 27939 \cs_new_protected:Npn \coffin_set_eq:NN #1#2
\coffin_set_eq:cN 27940 {
\coffin_set_eq:cc 27941     \__coffin_if_exist:NT #1
\coffin_gset_eq:NN 27942     {
\coffin_gset_eq:Nc 27943         \box_set_eq:NN #1 #2
\coffin_gset_eq:cN 27944         \prop_set_eq:cc { coffin ~ \__coffin_to_value:N #1 ~ corners }
\coffin_gset_eq:cc 27945         { coffin ~ \__coffin_to_value:N #2 ~ corners }
27946         \prop_set_eq:cc { coffin ~ \__coffin_to_value:N #1 ~ poles }
27947         { coffin ~ \__coffin_to_value:N #2 ~ poles }
27948     }
27949 }
27950 \cs_generate_variant:Nn \coffin_set_eq:NN { c , Nc , cc }
27951 \cs_new_protected:Npn \coffin_gset_eq:NN #1#2
27952 {
27953     \__coffin_if_exist:NT #1
27954     {
27955         \box_gset_eq:NN #1 #2
27956         \prop_gset_eq:cc { coffin ~ \__coffin_to_value:N #1 ~ corners }
27957         { coffin ~ \__coffin_to_value:N #2 ~ corners }
27958         \prop_gset_eq:cc { coffin ~ \__coffin_to_value:N #1 ~ poles }
27959         { coffin ~ \__coffin_to_value:N #2 ~ poles }
27960     }
27961 }
27962 \cs_generate_variant:Nn \coffin_gset_eq:NN { c , Nc , cc }

```

(End definition for \coffin_set_eq:NN and \coffin_gset_eq:NN. These functions are documented on page 246.)

```

\c_empty_coffin Special coffins: these cannot be set up earlier as they need \coffin_new:N. The empty
\l__coffin_aligned_coffin coffin is set as a box as the full coffin-setting system needs some material which is not
\l__coffin_aligned_internal_coffin yet available. The empty coffin is created entirely by hand: not everything is in place yet.
27963 \coffin_new:N \c_empty_coffin
27964 \coffin_new:N \l__coffin_aligned_coffin
27965 \coffin_new:N \l__coffin_aligned_internal_coffin

```

(End definition for `\c_empty_coffin`, `\l__coffin_aligned_coffin`, and `\l__coffin_aligned_internal_coffin`. This variable is documented on page 250.)

```
\l_tmpa_coffin The usual scratch space.
\l_tmpb_coffin 27966 \coffin_new:N \l_tmpa_coffin
\g_tmpa_coffin 27967 \coffin_new:N \l_tmpb_coffin
\g_tmpb_coffin 27968 \coffin_new:N \g_tmpa_coffin
                27969 \coffin_new:N \g_tmpb_coffin
```

(End definition for `\l_tmpa_coffin` and others. These variables are documented on page 250.)

42.3 Measuring coffins

`\coffin_dp:N` Coffins are just boxes when it comes to measurement. However, semantically a separate set of functions are required.

```
\coffin_dp:c 27970 \cs_new_eq:NN \coffin_dp:N \box_dp:N
\coffin_ht:c 27971 \cs_new_eq:NN \coffin_dp:c \box_dp:c
\coffin_ht:N 27972 \cs_new_eq:NN \coffin_ht:N \box_ht:N
\coffin_wd:c 27973 \cs_new_eq:NN \coffin_ht:c \box_ht:c
\coffin_wd:N 27974 \cs_new_eq:NN \coffin_wd:N \box_wd:N
                27975 \cs_new_eq:NN \coffin_wd:c \box_wd:c
```

(End definition for `\coffin_dp:N`, `\coffin_ht:N`, and `\coffin_wd:N`. These functions are documented on page 249.)

42.4 Coffins: handle and pole management

`__coffin_get_pole:NnN` A simple wrapper around the recovery of a coffin pole, with some error checking and recovery built-in.

```
27976 \cs_new_protected:Npn \__coffin_get_pole:NnN #1#2#3
27977 {
27978   \prop_get:cnNF
27979   { coffin ~ \__coffin_to_value:N #1 ~ poles } {#2} #3
27980   {
27981     \__kernel_msg_error:nxxx { kernel } { unknown-coffin-pole }
27982     { \exp_not:n {#2} } { \token_to_str:N #1 }
27983     \tl_set:Nn #3 { { Opt } { Opt } { Opt } { Opt } }
27984   }
27985 }
```

(End definition for `__coffin_get_pole:NnN`.)

`__coffin_reset_structure:N` Resetting the structure is a simple copy job.

```
\__coffin_greset_structure:N 27986 \cs_new_protected:Npn \__coffin_reset_structure:N #1
                             27987 {
                             27988   \prop_set_eq:cN { coffin ~ \__coffin_to_value:N #1 ~ corners }
                             27989   \c__coffin_corners_prop
                             27990   \prop_set_eq:cN { coffin ~ \__coffin_to_value:N #1 ~ poles }
                             27991   \c__coffin_poles_prop
                             27992 }
                             27993 \cs_new_protected:Npn \__coffin_greset_structure:N #1
                             27994 {
                             27995   \prop_gset_eq:cN { coffin ~ \__coffin_to_value:N #1 ~ corners }
                             27996   \c__coffin_corners_prop
```

```

27997     \prop_gset_eq:cN { coffin ~ \_coffin_to_value:N #1 ~ poles }
27998     \c__coffin_poles_prop
27999 }

```

(End definition for _coffin_reset_structure:N and _coffin_greset_structure:N.)

`\coffin_set_horizontal_pole:Nnn` Setting the pole of a coffin at the user/designer level requires a bit more care. The idea here is to provide a reasonable interface to the system, then to do the setting with full expansion. The three-argument version is used internally to do a direct setting.

```

\coffin_set_horizontal_pole:cnn
\coffin_gset_horizontal_pole:Nnn
\coffin_gset_horizontal_pole:cnn
\_coffin_set_horizontal_pole:NnnN
\coffin_set_vertical_pole:Nnn
\coffin_set_vertical_pole:cnn
\coffin_gset_vertical_pole:Nnn
\coffin_gset_vertical_pole:cnn
\_coffin_set_vertical_pole:NnnN
\_coffin_set_pole:Nnn
\_coffin_set_pole:Nnx
28000 \cs_new_protected:Npn \coffin_set_horizontal_pole:Nnn #1#2#3
28001 { \_coffin_set_horizontal_pole:NnnN #1 {#2} {#3} \prop_put:cnx }
28002 \cs_generate_variant:Nn \coffin_set_horizontal_pole:Nnn { c }
28003 \cs_new_protected:Npn \coffin_gset_horizontal_pole:Nnn #1#2#3
28004 { \_coffin_set_horizontal_pole:NnnN #1 {#2} {#3} \prop_gput:cnx }
28005 \cs_generate_variant:Nn \coffin_gset_horizontal_pole:Nnn { c }
28006 \cs_new_protected:Npn \_coffin_set_horizontal_pole:NnnN #1#2#3#4
28007 {
28008   \_coffin_if_exist:NT #1
28009   {
28010     #4 { coffin ~ \_coffin_to_value:N #1 ~ poles }
28011     {#2}
28012     {
28013       { Opt } { \dim_eval:n {#3} }
28014       { 1000pt } { Opt }
28015     }
28016   }
28017 }
28018 \cs_new_protected:Npn \coffin_set_vertical_pole:Nnn #1#2#3
28019 { \_coffin_set_vertical_pole:NnnN #1 {#2} {#3} \prop_put:cnx }
28020 \cs_generate_variant:Nn \coffin_set_vertical_pole:Nnn { c }
28021 \cs_new_protected:Npn \coffin_gset_vertical_pole:Nnn #1#2#3
28022 { \_coffin_set_vertical_pole:NnnN #1 {#2} {#3} \prop_gput:cnx }
28023 \cs_generate_variant:Nn \coffin_gset_vertical_pole:Nnn { c }
28024 \cs_new_protected:Npn \_coffin_set_vertical_pole:NnnN #1#2#3#4
28025 {
28026   \_coffin_if_exist:NT #1
28027   {
28028     #4 { coffin ~ \_coffin_to_value:N #1 ~ poles }
28029     {#2}
28030     {
28031       { \dim_eval:n {#3} } { Opt }
28032       { Opt } { 1000pt }
28033     }
28034   }
28035 }
28036 \cs_new_protected:Npn \_coffin_set_pole:Nnn #1#2#3
28037 {
28038   \prop_put:cnx { coffin ~ \_coffin_to_value:N #1 ~ poles }
28039   {#2} {#3}
28040 }
28041 \cs_generate_variant:Nn \_coffin_set_pole:Nnn { Nnx }

```

(End definition for \coffin_set_horizontal_pole:Nnn and others. These functions are documented on page 247.)

```

\__coffin_update:N
\__coffin_gupdate:N
28042 \cs_new_protected:Npn \__coffin_update:N #1
28043 {
28044   \__coffin_reset_structure:N #1
28045   \__coffin_update_corners:N #1
28046   \__coffin_update_poles:N #1
28047 }
28048 \cs_new_protected:Npn \__coffin_gupdate:N #1
28049 {
28050   \__coffin_greset_structure:N #1
28051   \__coffin_gupdate_corners:N #1
28052   \__coffin_gupdate_poles:N #1
28053 }

```

Simple shortcuts.

(End definition for `__coffin_update:N` and `__coffin_gupdate:N`.)

```

\__coffin_update_corners:N
\__coffin_gupdate_corners:N
\__coffin_update_corners:NN
\__coffin_update_corners:NNN
28054 \cs_new_protected:Npn \__coffin_update_corners:N #1
28055 { \__coffin_update_corners:NN #1 \prop_put:Nnx }
28056 \cs_new_protected:Npn \__coffin_gupdate_corners:N #1
28057 { \__coffin_update_corners:NN #1 \prop_gput:Nnx }
28058 \cs_new_protected:Npn \__coffin_update_corners:NN #1#2
28059 {
28060   \exp_args:Nc \__coffin_update_corners:NNN
28061   { coffin ~ \__coffin_to_value:N #1 ~ corners }
28062   #1 #2
28063 }
28064 \cs_new_protected:Npn \__coffin_update_corners:NNN #1#2#3
28065 {
28066   #3 #1
28067   { tl }
28068   { { Opt } { \dim_eval:n { \box_ht:N #2 } } }
28069   #3 #1
28070   { tr }
28071   {
28072     { \dim_eval:n { \box_wd:N #2 } }
28073     { \dim_eval:n { \box_ht:N #2 } }
28074   }
28075   #3 #1
28076   { bl }
28077   { { Opt } { \dim_eval:n { -\box_dp:N #2 } } }
28078   #3 #1
28079   { br }
28080   {
28081     { \dim_eval:n { \box_wd:N #2 } }
28082     { \dim_eval:n { -\box_dp:N #2 } }
28083   }
28084 }

```

Updating the corners of a coffin is straight-forward as at this stage there can be no rotation. So the corners of the content are just those of the underlying `TeX` box.

(End definition for `__coffin_update_corners:N` and others.)

```

\__coffin_update_poles:N
\__coffin_gupdate_poles:N
\__coffin_update_poles:NN
\__coffin_update_poles:NNN

```

This function is called when a coffin is set, and updates the poles to reflect the nature of size of the box. Thus this function only alters poles where the default position is

dependent on the size of the box. It also does not set poles which are relevant only to vertical coffins.

```

28085 \cs_new_protected:Npn \__coffin_update_poles:N #1
28086 { \__coffin_update_poles:NN #1 \prop_put:Nnx }
28087 \cs_new_protected:Npn \__coffin_gupdate_poles:N #1
28088 { \__coffin_update_poles:NN #1 \prop_gput:Nnx }
28089 \cs_new_protected:Npn \__coffin_update_poles:NN #1#2
28090 {
28091   \exp_args:Nc \__coffin_update_poles:NNN
28092     { coffin ~ \__coffin_to_value:N #1 ~ poles }
28093     #1 #2
28094 }
28095 \cs_new_protected:Npn \__coffin_update_poles:NNN #1#2#3
28096 {
28097   #3 #1 { hc }
28098   {
28099     { \dim_eval:n { 0.5 \box_wd:N #2 } }
28100     { Opt } { Opt } { 1000pt }
28101   }
28102   #3 #1 { r }
28103   {
28104     { \dim_eval:n { \box_wd:N #2 } }
28105     { Opt } { Opt } { 1000pt }
28106   }
28107   #3 #1 { vc }
28108   {
28109     { Opt }
28110     { \dim_eval:n { ( \box_ht:N #2 - \box_dp:N #2 ) / 2 } }
28111     { 1000pt }
28112     { Opt }
28113   }
28114   #3 #1 { t }
28115   {
28116     { Opt }
28117     { \dim_eval:n { \box_ht:N #2 } }
28118     { 1000pt }
28119     { Opt }
28120   }
28121   #3 #1 { b }
28122   {
28123     { Opt }
28124     { \dim_eval:n { -\box_dp:N #2 } }
28125     { 1000pt }
28126     { Opt }
28127   }
28128 }

```

(End definition for `__coffin_update_poles:N` and others.)

42.5 Coffins: calculation of pole intersections

The lead off in finding intersections is to recover the two poles and then hand off to the auxiliary for the actual calculation. There may of course not be an intersection, for which an error trap is needed.

```

28129 \cs_new_protected:Npn \__coffin_calculate_intersection:Nnn #1#2#3
28130 {
28131   \__coffin_get_pole:NnN #1 {#2} \l__coffin_pole_a_tl
28132   \__coffin_get_pole:NnN #1 {#3} \l__coffin_pole_b_tl
28133   \bool_set_false:N \l__coffin_error_bool
28134   \exp_last_two_unbraced:Noo
28135     \__coffin_calculate_intersection:nnnnnnnn
28136     \l__coffin_pole_a_tl \l__coffin_pole_b_tl
28137   \bool_if:NT \l__coffin_error_bool
28138     {
28139       \__kernel_msg_error:nn { kernel } { no-pole-intersection }
28140       \dim_zero:N \l__coffin_x_dim
28141       \dim_zero:N \l__coffin_y_dim
28142     }
28143 }

```

The two poles passed here each have four values (as dimensions), (a, b, c, d) and (a', b', c', d') . These are arguments 1–4 and 5–8, respectively. In both cases a and b are the co-ordinates of a point on the pole and c and d define the direction of the pole. Finding the intersection depends on the directions of the poles, which are given by d/c and d'/c' . However, if one of the poles is either horizontal or vertical then one or more of c, d, c' and d' are zero and a special case is needed.

```

28144 \cs_new_protected:Npn \__coffin_calculate_intersection:nnnnnnnn
28145   #1#2#3#4#5#6#7#8
28146 {
28147   \dim_compare:nNnTF {#3} = \c_zero_dim

```

The case where the first pole is vertical. So the x -component of the interaction is at a . There is then a test on the second pole: if it is also vertical then there is an error.

```

28148   {
28149     \dim_set:Nn \l__coffin_x_dim {#1}
28150     \dim_compare:nNnTF {#7} = \c_zero_dim
28151     { \bool_set_true:N \l__coffin_error_bool }

```

The second pole may still be horizontal, in which case the y -component of the intersection is b' . If not,

$$y = \frac{d'}{c'} (a - a') + b'$$

with the x -component already known to be $\#1$.

```

28152   {
28153     \dim_set:Nn \l__coffin_y_dim
28154     {
28155       \dim_compare:nNnTF {#8} = \c_zero_dim
28156       {#6}
28157       {
28158         \fp_to_dim:n
28159         {
28160           ( \dim_to_fp:n {#8} / \dim_to_fp:n {#7} )
28161           * ( \dim_to_fp:n {#1} - \dim_to_fp:n {#5} )
28162           + \dim_to_fp:n {#6}
28163         }
28164       }
28165     }
28166   }
28167 }

```

If the first pole is not vertical then it may be horizontal. If so, then the procedure is essentially the same as that already done but with the x - and y -components interchanged.

```

28168     {
28169         \dim_compare:nNnTF {#4} = \c_zero_dim
28170     {
28171         \dim_set:Nn \l__coffin_y_dim {#2}
28172         \dim_compare:nNnTF {#8} = { \c_zero_dim }
28173         { \bool_set_true:N \l__coffin_error_bool }
28174     }

```

Now we deal with the case where the second pole may be vertical, or if not we have

$$x = \frac{c'}{d'}(b - b') + a'$$

which is again handled by the same auxiliary.

```

28175         \dim_set:Nn \l__coffin_x_dim
28176     {
28177         \dim_compare:nNnTF {#7} = \c_zero_dim
28178         {#5}
28179         {
28180             \fp_to_dim:n
28181             {
28182                 ( \dim_to_fp:n {#7} / \dim_to_fp:n {#8} )
28183                 * ( \dim_to_fp:n {#4} - \dim_to_fp:n {#6} )
28184                 + \dim_to_fp:n {#5}
28185             }
28186         }
28187     }
28188 }
28189 }

```

The first pole is neither horizontal nor vertical. To avoid even more complexity, we now work out both slopes and pass to an auxiliary.

```

28190     {
28191         \use:x
28192         {
28193             \__coffin_calculate_intersection:nnnnnn
28194             { \dim_to_fp:n {#4} / \dim_to_fp:n {#3} }
28195             { \dim_to_fp:n {#8} / \dim_to_fp:n {#7} }
28196         }
28197         {#1} {#2} {#5} {#6}
28198     }
28199 }
28200 }

```

Assuming the two poles are not parallel, then the intersection point is found in two steps. First we find the x -value with

$$x = \frac{sa - s'a' - b + b'}{s - s'}$$

and then finding the y -value with

$$y = s(x - a) + b$$

```

28201 \cs_set_protected:Npn \__coffin_calculate_intersection:nnnnnn #1#2#3#4#5#6
28202 {
28203   \fp_compare:nNnTF {#1} = {#2}
28204   { \bool_set_true:N \l__coffin_error_bool }
28205   {
28206     \dim_set:Nn \l__coffin_x_dim
28207     {
28208       \fp_to_dim:n
28209       {
28210         (
28211           #1 * \dim_to_fp:n {#3}
28212           - #2 * \dim_to_fp:n {#5}
28213           - \dim_to_fp:n {#4}
28214           + \dim_to_fp:n {#6}
28215         )
28216         /
28217         ( #1 - #2 )
28218       }
28219     }
28220     \dim_set:Nn \l__coffin_y_dim
28221     {
28222       \fp_to_dim:n
28223       {
28224         #1 * ( \l__coffin_x_dim - \dim_to_fp:n {#3} )
28225         + \dim_to_fp:n {#4}
28226       }
28227     }
28228   }
28229 }

```

(End definition for __coffin_calculate_intersection:Nnn, __coffin_calculate_intersection:nnnnnnnn, and __coffin_calculate_intersection:nnnnnn.)

42.6 Affine transformations

\l__coffin_sin_fp Used for rotations to get the sine and cosine values.
\l__coffin_cos_fp

```

28230 \fp_new:N \l__coffin_sin_fp
28231 \fp_new:N \l__coffin_cos_fp

```

(End definition for \l__coffin_sin_fp and \l__coffin_cos_fp.)

\l__coffin_bounding_prop A property list for the bounding box of a coffin. This is only needed during the rotation, so there is just the one.

```

28232 \prop_new:N \l__coffin_bounding_prop

```

(End definition for \l__coffin_bounding_prop.)

\l__coffin_corners_prop Used to avoid needing to track scope for intermediate steps.
\l__coffin_poles_prop

```

28233 \prop_new:N \l__coffin_corners_prop
28234 \prop_new:N \l__coffin_poles_prop

```

(End definition for \l__coffin_corners_prop and \l__coffin_poles_prop.)

\l__coffin_bounding_shift_dim The shift of the bounding box of a coffin from the real content.

```

28235 \dim_new:N \l__coffin_bounding_shift_dim

```


(End definition for \l__coffin_bounding_shift_dim.)

\l__coffin_left_corner_dim These are used to hold maxima for the various corner values: these thus define the
\l__coffin_right_corner_dim minimum size of the bounding box after rotation.
\l__coffin_bottom_corner_dim
\l__coffin_top_corner_dim

```
28236 \dim_new:N \l__coffin_left_corner_dim
28237 \dim_new:N \l__coffin_right_corner_dim
28238 \dim_new:N \l__coffin_bottom_corner_dim
28239 \dim_new:N \l__coffin_top_corner_dim
```

(End definition for \l__coffin_left_corner_dim and others.)

```
\coffin_rotate:Nn Rotating a coffin requires several steps which can be conveniently run together. The sine
\coffin_rotate:cn and cosine of the angle in degrees are computed. This is then used to set \l__coffin_
\coffin_grotate:Nn sin_fp and \l__coffin_cos_fp, which are carried through unchanged for the rest of
\coffin_grotate:cn the procedure.
\__coffin_rotate:NnNNN
28240 \cs_new_protected:Npn \coffin_rotate:Nn #1#2
28241 { \__coffin_rotate:NnNNN #1 {#2} \box_rotate:Nn \prop_set_eq:cn \hbox_set:Nn }
28242 \cs_generate_variant:Nn \coffin_rotate:Nn { c }
28243 \cs_new_protected:Npn \coffin_grotate:Nn #1#2
28244 { \__coffin_rotate:NnNNN #1 {#2} \box_grotate:Nn \prop_gset_eq:cn \hbox_gset:Nn }
28245 \cs_generate_variant:Nn \coffin_grotate:Nn { c }
28246 \cs_new_protected:Npn \__coffin_rotate:NnNNN #1#2#3#4#5
28247 {
28248   \fp_set:Nn \l__coffin_sin_fp { sind ( #2 ) }
28249   \fp_set:Nn \l__coffin_cos_fp { cosd ( #2 ) }
```

Use a local copy of the property lists to avoid needing to pass the name and scope around.

```
28250 \prop_set_eq:Nc \l__coffin_corners_prop
28251 { coffin ~ \__coffin_to_value:N #1 ~ corners }
28252 \prop_set_eq:Nc \l__coffin_poles_prop
28253 { coffin ~ \__coffin_to_value:N #1 ~ poles }
```

The corners and poles of the coffin can now be rotated around the origin. This is best achieved using mapping functions.

```
28254 \prop_map_inline:Nn \l__coffin_corners_prop
28255 { \__coffin_rotate_corner:Nnnn #1 {##1} ##2 }
28256 \prop_map_inline:Nn \l__coffin_poles_prop
28257 { \__coffin_rotate_pole:Nnnnnn #1 {##1} ##2 }
```

The bounding box of the coffin needs to be rotated, and to do this the corners have to be found first. They are then rotated in the same way as the corners of the coffin material itself.

```
28258 \__coffin_set_bounding:N #1
28259 \prop_map_inline:Nn \l__coffin_bounding_prop
28260 { \__coffin_rotate_bounding:nnn {##1} ##2 }
```

At this stage, there needs to be a calculation to find where the corners of the content and the box itself will end up.

```
28261 \__coffin_find_corner_maxima:N #1
28262 \__coffin_find_bounding_shift:
28263 #3 #1 {#2}
```

The correction of the box position itself takes place here. The idea is that the bounding box for a coffin is tight up to the content, and has the reference point at the bottom-left. The x -direction is handled by moving the content by the difference in the positions of the bounding box and the content left edge. The y -direction is dealt with by moving the box down by any depth it has acquired. The internal box is used here to allow for the next step.

```

28264 \hbox_set:Nn \l__coffin_internal_box
28265 {
28266   \tex_kern:D
28267   \dim_eval:n
28268     { \l__coffin_bounding_shift_dim - \l__coffin_left_corner_dim }
28269   \exp_stop_f:
28270   \box_move_down:nn { \l__coffin_bottom_corner_dim }
28271   { \box_use:N #1 }
28272 }

```

If there have been any previous rotations then the size of the bounding box will be bigger than the contents. This can be corrected easily by setting the size of the box to the height and width of the content. As this operation requires setting box dimensions and these transcend grouping, the safe way to do this is to use the internal box and to reset the result into the target box.

```

28273 \box_set_ht:Nn \l__coffin_internal_box
28274   { \l__coffin_top_corner_dim - \l__coffin_bottom_corner_dim }
28275 \box_set_dp:Nn \l__coffin_internal_box { 0pt }
28276 \box_set_wd:Nn \l__coffin_internal_box
28277   { \l__coffin_right_corner_dim - \l__coffin_left_corner_dim }
28278 #5 #1 { \box_use_drop:N \l__coffin_internal_box }

```

The final task is to move the poles and corners such that they are back in alignment with the box reference point.

```

28279 \prop_map_inline:Nn \l__coffin_corners_prop
28280   { \__coffin_shift_corner:Nnnn #1 {##1} ##2 }
28281 \prop_map_inline:Nn \l__coffin_poles_prop
28282   { \__coffin_shift_pole:Nnnnnn #1 {##1} ##2 }

```

Update the coffin data.

```

28283 #4 { coffin ~ \__coffin_to_value:N #1 ~ corners }
28284   \l__coffin_corners_prop
28285 #4 { coffin ~ \__coffin_to_value:N #1 ~ poles }
28286   \l__coffin_poles_prop
28287 }

```

(End definition for \coffin_rotate:Nn, \coffin_grotate:Nn, and __coffin_rotate:NnNNN. These functions are documented on page 248.)

`__coffin_set_bounding:N` The bounding box corners for a coffin are easy enough to find: this is the same code as for the corners of the material itself, but using a dedicated property list.

```

28288 \cs_new_protected:Npn \__coffin_set_bounding:N #1
28289 {
28290   \prop_put:Nnx \l__coffin_bounding_prop { tl }
28291     { { 0pt } { \dim_eval:n { \box_ht:N #1 } } }
28292   \prop_put:Nnx \l__coffin_bounding_prop { tr }
28293     {
28294       { \dim_eval:n { \box_wd:N #1 } }

```

```

28295     { \dim_eval:n { \box_ht:N #1 } }
28296   }
28297   \dim_set:Nn \l__coffin_internal_dim { -\box_dp:N #1 }
28298   \prop_put:Nnx \l__coffin_bounding_prop { bl }
28299   { { Opt } { \dim_use:N \l__coffin_internal_dim } }
28300   \prop_put:Nnx \l__coffin_bounding_prop { br }
28301   {
28302     { \dim_eval:n { \box_wd:N #1 } }
28303     { \dim_use:N \l__coffin_internal_dim }
28304   }
28305 }

```

(End definition for __coffin_set_bounding:N.)

__coffin_rotate_bounding:nnn Rotating the position of the corner of the coffin is just a case of treating this as a vector from the reference point. The same treatment is used for the corners of the material itself and the bounding box.

```

28306 \cs_new_protected:Npn \__coffin_rotate_bounding:nnn #1#2#3
28307 {
28308   \__coffin_rotate_vector:nnNN {#2} {#3} \l__coffin_x_dim \l__coffin_y_dim
28309   \prop_put:Nnx \l__coffin_bounding_prop {#1}
28310   { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
28311 }
28312 \cs_new_protected:Npn \__coffin_rotate_corner:Nnnn #1#2#3#4
28313 {
28314   \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
28315   \prop_put:Nnx \l__coffin_corners_prop {#2}
28316   { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
28317 }

```

(End definition for __coffin_rotate_bounding:nnn and __coffin_rotate_corner:Nnnn.)

__coffin_rotate_pole:Nnnnnn Rotating a single pole simply means shifting the co-ordinate of the pole and its direction. The rotation here is about the bottom-left corner of the coffin.

```

28318 \cs_new_protected:Npn \__coffin_rotate_pole:Nnnnnn #1#2#3#4#5#6
28319 {
28320   \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
28321   \__coffin_rotate_vector:nnNN {#5} {#6}
28322   \l__coffin_x_prime_dim \l__coffin_y_prime_dim
28323   \prop_put:Nnx \l__coffin_poles_prop {#2}
28324   {
28325     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
28326     { \dim_use:N \l__coffin_x_prime_dim }
28327     { \dim_use:N \l__coffin_y_prime_dim }
28328   }
28329 }

```

(End definition for __coffin_rotate_pole:Nnnnnn.)

__coffin_rotate_vector:nnNN A rotation function, which needs only an input vector (as dimensions) and an output space. The values \l__coffin_cos_fp and \l__coffin_sin_fp should previously have been set up correctly. Working this way means that the floating point work is kept to a minimum: for any given rotation the sin and cosine values do no change, after all.

```

28330 \cs_new_protected:Npn \__coffin_rotate_vector:nnNN #1#2#3#4

```

```

28331 {
28332   \dim_set:Nn #3
28333   {
28334     \fp_to_dim:n
28335     {
28336       \dim_to_fp:n {#1} * \l__coffin_cos_fp
28337       - \dim_to_fp:n {#2} * \l__coffin_sin_fp
28338     }
28339   }
28340   \dim_set:Nn #4
28341   {
28342     \fp_to_dim:n
28343     {
28344       \dim_to_fp:n {#1} * \l__coffin_sin_fp
28345       + \dim_to_fp:n {#2} * \l__coffin_cos_fp
28346     }
28347   }
28348 }

```

(End definition for __coffin_rotate_vector:nnNN.)

__coffin_find_corner_maxima:N
 __coffin_find_corner_maxima_aux:nn

The idea here is to find the extremities of the content of the coffin. This is done by looking for the smallest values for the bottom and left corners, and the largest values for the top and right corners. The values start at the maximum dimensions so that the case where all are positive or all are negative works out correctly.

```

28349 \cs_new_protected:Npn \__coffin_find_corner_maxima:N #1
28350 {
28351   \dim_set:Nn \l__coffin_top_corner_dim { -\c_max_dim }
28352   \dim_set:Nn \l__coffin_right_corner_dim { -\c_max_dim }
28353   \dim_set:Nn \l__coffin_bottom_corner_dim { \c_max_dim }
28354   \dim_set:Nn \l__coffin_left_corner_dim { \c_max_dim }
28355   \prop_map_inline:Nn \l__coffin_corners_prop
28356   { \__coffin_find_corner_maxima_aux:nn ##2 }
28357 }
28358 \cs_new_protected:Npn \__coffin_find_corner_maxima_aux:nn #1#2
28359 {
28360   \dim_set:Nn \l__coffin_left_corner_dim
28361   { \dim_min:nn { \l__coffin_left_corner_dim } {#1} }
28362   \dim_set:Nn \l__coffin_right_corner_dim
28363   { \dim_max:nn { \l__coffin_right_corner_dim } {#1} }
28364   \dim_set:Nn \l__coffin_bottom_corner_dim
28365   { \dim_min:nn { \l__coffin_bottom_corner_dim } {#2} }
28366   \dim_set:Nn \l__coffin_top_corner_dim
28367   { \dim_max:nn { \l__coffin_top_corner_dim } {#2} }
28368 }

```

(End definition for __coffin_find_corner_maxima:N and __coffin_find_corner_maxima_aux:nn.)

__coffin_find_bounding_shift:
 __coffin_find_bounding_shift_aux:nn

The approach to finding the shift for the bounding box is similar to that for the corners. However, there is only one value needed here and a fixed input property list, so things are a bit clearer.

```

28369 \cs_new_protected:Npn \__coffin_find_bounding_shift:
28370 {
28371   \dim_set:Nn \l__coffin_bounding_shift_dim { \c_max_dim }

```

```

28372     \prop_map_inline:Nn \l__coffin_bounding_prop
28373     { \__coffin_find_bounding_shift_aux:nn ##2 }
28374   }
28375   \cs_new_protected:Npn \__coffin_find_bounding_shift_aux:nn #1#2
28376   {
28377     \dim_set:Nn \l__coffin_bounding_shift_dim
28378     { \dim_min:nn { \l__coffin_bounding_shift_dim } {#1} }
28379   }

```

(End definition for `__coffin_find_bounding_shift:` and `__coffin_find_bounding_shift_aux:nn`.)

`__coffin_shift_corner:Nnnn` `__coffin_shift_pole:Nnnnnn` Shifting the corners and poles of a coffin means subtracting the appropriate values from the x - and y -components. For the poles, this means that the direction vector is unchanged.

```

28380   \cs_new_protected:Npn \__coffin_shift_corner:Nnnn #1#2#3#4
28381   {
28382     \prop_put:Nnx \l__coffin_corners_prop {#2}
28383     {
28384       { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
28385       { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
28386     }
28387   }
28388   \cs_new_protected:Npn \__coffin_shift_pole:Nnnnnn #1#2#3#4#5#6
28389   {
28390     \prop_put:Nnx \l__coffin_poles_prop {#2}
28391     {
28392       { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
28393       { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
28394       {#5} {#6}
28395     }
28396   }

```

(End definition for `__coffin_shift_corner:Nnnn` and `__coffin_shift_pole:Nnnnnn`.)

`\l__coffin_scale_x_fp` `\l__coffin_scale_y_fp` Storage for the scaling factors in x and y , respectively.

```

28397   \fp_new:N \l__coffin_scale_x_fp
28398   \fp_new:N \l__coffin_scale_y_fp

```

(End definition for `\l__coffin_scale_x_fp` and `\l__coffin_scale_y_fp`.)

`\l__coffin_scaled_total_height_dim` `\l__coffin_scaled_width_dim` When scaling, the values given have to be turned into absolute values.

```

28399   \dim_new:N \l__coffin_scaled_total_height_dim
28400   \dim_new:N \l__coffin_scaled_width_dim

```

(End definition for `\l__coffin_scaled_total_height_dim` and `\l__coffin_scaled_width_dim`.)

`\coffin_resize:Nnn` `\coffin_resize:cnn` `\coffin_gresize:Nnn` `\coffin_gresize:cnn` Resizing a coffin begins by setting up the user-friendly names for the dimensions of the coffin box. The new sizes are then turned into scale factor. This is the same operation as takes place for the underlying box, but that operation is grouped and so the same calculation is done here.

```

\__coffin_resize:NnnNN
28401   \cs_new_protected:Npn \coffin_resize:Nnn #1#2#3
28402   {
28403     \__coffin_resize:NnnNN #1 {#2} {#3}
28404     \box_resize_to_wd_and_ht_plus_dp:Nnn

```

```

28405     \prop_set_eq:cN
28406   }
28407   \cs_generate_variant:Nn \coffin_resize:Nnn { c }
28408   \cs_new_protected:Npn \coffin_gresize:Nnn #1#2#3
28409   {
28410     \__coffin_resize:NnnNN #1 {#2} {#3}
28411     \box_gresize_to_wd_and_ht_plus_dp:Nnn
28412     \prop_gset_eq:cN
28413   }
28414   \cs_generate_variant:Nn \coffin_gresize:Nnn { c }
28415   \cs_new_protected:Npn \__coffin_resize:NnnNN #1#2#3#4#5
28416   {
28417     \fp_set:Nn \l__coffin_scale_x_fp
28418     { \dim_to_fp:n {#2} / \dim_to_fp:n { \coffin_wd:N #1 } }
28419     \fp_set:Nn \l__coffin_scale_y_fp
28420     {
28421       \dim_to_fp:n {#3}
28422       / \dim_to_fp:n { \coffin_ht:N #1 + \coffin_dp:N #1 }
28423     }
28424     #4 #1 {#2} {#3}
28425     \__coffin_resize_common:NnnN #1 {#2} {#3} #5
28426   }

```

(End definition for `\coffin_resize:Nnn`, `\coffin_gresize:Nnn`, and `__coffin_resize:NnnNN`. These functions are documented on page 248.)

`__coffin_resize_common:NnnN` The poles and corners of the coffin are scaled to the appropriate places before actually resizing the underlying box.

```

28427   \cs_new_protected:Npn \__coffin_resize_common:NnnN #1#2#3#4
28428   {
28429     \prop_set_eq:Nc \l__coffin_corners_prop
28430     { coffin ~ \__coffin_to_value:N #1 ~ corners }
28431     \prop_set_eq:Nc \l__coffin_poles_prop
28432     { coffin ~ \__coffin_to_value:N #1 ~ poles }
28433     \prop_map_inline:Nn \l__coffin_corners_prop
28434     { \__coffin_scale_corner:Nnnn #1 {##1} ##2 }
28435     \prop_map_inline:Nn \l__coffin_poles_prop
28436     { \__coffin_scale_pole:Nnnnnn #1 {##1} ##2 }

```

Negative x -scaling values place the poles in the wrong location: this is corrected here.

```

28437     \fp_compare:nNnT \l__coffin_scale_x_fp < \c_zero_fp
28438     {
28439       \prop_map_inline:Nn \l__coffin_corners_prop
28440       { \__coffin_x_shift_corner:Nnnn #1 {##1} ##2 }
28441       \prop_map_inline:Nn \l__coffin_poles_prop
28442       { \__coffin_x_shift_pole:Nnnnnn #1 {##1} ##2 }
28443     }
28444     #4 { coffin ~ \__coffin_to_value:N #1 ~ corners }
28445     \l__coffin_corners_prop
28446     #4 { coffin ~ \__coffin_to_value:N #1 ~ poles }
28447     \l__coffin_poles_prop
28448   }

```

(End definition for `__coffin_resize_common:NnnN`.)

`\coffin_scale:Nnn` For scaling, the opposite calculation is done to find the new dimensions for the coffin.
`\coffin_scale:cnn` Only the total height is needed, as this is the shift required for corners and poles. The
`\coffin_gscale:Nnn` scaling is done the T_EX way as this works properly with floating point values without
`\coffin_gscale:cnn` needing to use the fp module.
`\coffin_scale:NnnNN`

```

28449 \cs_new_protected:Npn \coffin_scale:Nnn #1#2#3
28450 { \__coffin_scale:NnnNN #1 {#2} {#3} \box_scale:Nnn \prop_set_eq:cN }
28451 \cs_generate_variant:Nn \coffin_scale:Nnn { c }
28452 \cs_new_protected:Npn \coffin_gscale:Nnn #1#2#3
28453 { \__coffin_scale:NnnNN #1 {#2} {#3} \box_gscale:Nnn \prop_gset_eq:cN }
28454 \cs_generate_variant:Nn \coffin_gscale:Nnn { c }
28455 \cs_new_protected:Npn \__coffin_scale:NnnNN #1#2#3#4#5
28456 {
28457   \fp_set:Nn \l__coffin_scale_x_fp {#2}
28458   \fp_set:Nn \l__coffin_scale_y_fp {#3}
28459   #4 #1 { \l__coffin_scale_x_fp } { \l__coffin_scale_y_fp }
28460   \dim_set:Nn \l__coffin_internal_dim
28461     { \coffin_ht:N #1 + \coffin_dp:N #1 }
28462   \dim_set:Nn \l__coffin_scaled_total_height_dim
28463     { \fp_abs:n { \l__coffin_scale_y_fp } \l__coffin_internal_dim }
28464   \dim_set:Nn \l__coffin_scaled_width_dim
28465     { -\fp_abs:n { \l__coffin_scale_x_fp } \coffin_wd:N #1 }
28466   \__coffin_resize_common:NnnN #1
28467     { \l__coffin_scaled_width_dim } { \l__coffin_scaled_total_height_dim }
28468   #5
28469 }

```

(End definition for `\coffin_scale:Nnn`, `\coffin_gscale:Nnn`, and `\coffin_scale:NnnNN`. These functions are documented on page 248.)

`__coffin_scale_vector:nnNN` This functions scales a vector from the origin using the pre-set scale factors in x and y . This is a much less complex operation than rotation, and as a result the code is a lot clearer.

```

28470 \cs_new_protected:Npn \__coffin_scale_vector:nnNN #1#2#3#4
28471 {
28472   \dim_set:Nn #3
28473     { \fp_to_dim:n { \dim_to_fp:n {#1} * \l__coffin_scale_x_fp } }
28474   \dim_set:Nn #4
28475     { \fp_to_dim:n { \dim_to_fp:n {#2} * \l__coffin_scale_y_fp } }
28476 }

```

(End definition for `__coffin_scale_vector:nnNN`.)

`__coffin_scale_corner:Nnnn` Scaling both corners and poles is a simple calculation using the preceding vector scaling.
`__coffin_scale_pole:Nnnnnn`

```

28477 \cs_new_protected:Npn \__coffin_scale_corner:Nnnn #1#2#3#4
28478 {
28479   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
28480   \prop_put:Nnx \l__coffin_corners_prop {#2}
28481     { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
28482 }
28483 \cs_new_protected:Npn \__coffin_scale_pole:Nnnnnn #1#2#3#4#5#6
28484 {
28485   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
28486   \prop_put:Nnx \l__coffin_poles_prop {#2}
28487   {

```

```

28488         { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
28489         {#5} {#6}
28490     }
28491 }

```

(End definition for `__coffin_scale_corner:Nnnn` and `__coffin_scale_pole:Nnnnnn`.)

`__coffin_x_shift_corner:Nnnn`
`__coffin_x_shift_pole:Nnnnnn`

These functions correct for the x displacement that takes place with a negative horizontal scaling.

```

28492 \cs_new_protected:Npn \__coffin_x_shift_corner:Nnnn #1#2#3#4
28493 {
28494     \prop_put:Nnx \l__coffin_corners_prop {#2}
28495     {
28496         { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
28497     }
28498 }
28499 \cs_new_protected:Npn \__coffin_x_shift_pole:Nnnnnn #1#2#3#4#5#6
28500 {
28501     \prop_put:Nnx \l__coffin_poles_prop {#2}
28502     {
28503         { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
28504         {#5} {#6}
28505     }
28506 }

```

(End definition for `__coffin_x_shift_corner:Nnnn` and `__coffin_x_shift_pole:Nnnnnn`.)

42.7 Aligning and typesetting of coffins

`\coffin_join:NnnNnnnn`
`\coffin_join:cnnNnnnn`
`\coffin_join:Nnncnnnn`
`\coffin_join:cnncnnnn`

This command joins two coffins, using a horizontal and vertical pole from each coffin and making an offset between the two. The result is stored as the as a third coffin, which has all of its handles reset to standard values. First, the more basic alignment function is used to get things started.

```

\coffin_gjoin:NnnNnnnn
\coffin_gjoin:cnnNnnnn
\coffin_gjoin:Nnncnnnn
\coffin_gjoin:cnncnnnn
\__coffin_join:NnnNnnnnN
28507 \cs_new_protected:Npn \coffin_join:NnnNnnnn #1#2#3#4#5#6#7#8
28508 {
28509     \__coffin_join:NnnNnnnnN #1 {#2} {#3} #4 {#5} {#6} {#7} {#8}
28510     \coffin_set_eq:NN
28511 }
28512 \cs_generate_variant:Nn \coffin_join:NnnNnnnn { c , Nnnc , cnnc }
28513 \cs_new_protected:Npn \coffin_gjoin:NnnNnnnn #1#2#3#4#5#6#7#8
28514 {
28515     \__coffin_join:NnnNnnnnN #1 {#2} {#3} #4 {#5} {#6} {#7} {#8}
28516     \coffin_gset_eq:NN
28517 }
28518 \cs_generate_variant:Nn \coffin_gjoin:NnnNnnnn { c , Nnnc , cnnc }
28519 \cs_new_protected:Npn \__coffin_join:NnnNnnnnN #1#2#3#4#5#6#7#8#9
28520 {
28521     \__coffin_align:NnnNnnnnN
28522     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin

```

Correct the placement of the reference point. If the x -offset is negative then the reference point of the second box is to the left of that of the first, which is corrected using a kern. On the right side the first box might stick out, which would show up if it is wider than the sum of the x -offset and the width of the second box. So a second kern may be needed.


```

28523 \hbox_set:Nn \l__coffin_aligned_coffin
28524 {
28525   \dim_compare:nNnT { \l__coffin_offset_x_dim } < \c_zero_dim
28526   { \tex_kern:D -\l__coffin_offset_x_dim }
28527   \hbox_unpack:N \l__coffin_aligned_coffin
28528   \dim_set:Nn \l__coffin_internal_dim
28529   { \l__coffin_offset_x_dim - \box_wd:N #1 + \box_wd:N #4 }
28530   \dim_compare:nNnT \l__coffin_internal_dim < \c_zero_dim
28531   { \tex_kern:D -\l__coffin_internal_dim }
28532 }

```

The coffin structure is reset, and the corners are cleared: only those from the two parent coffins are needed.

```

28533 \__coffin_reset_structure:N \l__coffin_aligned_coffin
28534 \prop_clear:c
28535 {
28536   coffin ~ \__coffin_to_value:N \l__coffin_aligned_coffin
28537   \c_space_tl corners
28538 }
28539 \__coffin_update_poles:N \l__coffin_aligned_coffin

```

The structures of the parent coffins are now transferred to the new coffin, which requires that the appropriate offsets are applied. That then depends on whether any shift was needed.

```

28540 \dim_compare:nNnTF \l__coffin_offset_x_dim < \c_zero_dim
28541 {
28542   \__coffin_offset_poles:Nnn #1 { -\l__coffin_offset_x_dim } { Opt }
28543   \__coffin_offset_poles:Nnn #4 { Opt } { \l__coffin_offset_y_dim }
28544   \__coffin_offset_corners:Nnn #1 { -\l__coffin_offset_x_dim } { Opt }
28545   \__coffin_offset_corners:Nnn #4 { Opt } { \l__coffin_offset_y_dim }
28546 }
28547 {
28548   \__coffin_offset_poles:Nnn #1 { Opt } { Opt }
28549   \__coffin_offset_poles:Nnn #4
28550   { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
28551   \__coffin_offset_corners:Nnn #1 { Opt } { Opt }
28552   \__coffin_offset_corners:Nnn #4
28553   { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
28554 }
28555 \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
28556 #9 #1 \l__coffin_aligned_coffin
28557 }

```

(End definition for `\coffin_join:NnnNnnnn`, `\coffin_gjoin:NnnNnnnn`, and `__coffin_join:NnnNnnnnN`. These functions are documented on page 248.)

```

\coffin_attach:NnnNnnnn
\coffin_attach:cnnNnnnn
\coffin_attach:Nnnncnnnn
\coffin_attach:cnncnnnn
\coffin_gattach:NnnNnnnn
\coffin_gattach:cnnNnnnn
\coffin_gattach:Nnnncnnnn
\coffin_gattach:cnncnnnn
\__coffin_attach:NnnNnnnnN
  \__coffin_attach_mark:NnnNnnnn

```

A more simple version of the above, as it simply uses the size of the first coffin for the new one. This means that the work here is rather simplified compared to the above code. The function used when marking a position is hear also as it is similar but without the structure updates.

```

28558 \cs_new_protected:Npn \coffin_attach:NnnNnnnn #1#2#3#4#5#6#7#8
28559 {
28560   \__coffin_attach:NnnNnnnnN #1 {#2} {#3} #4 {#5} {#6} {#7} {#8}
28561   \coffin_set_eq:NN
28562 }

```

```

28563 \cs_generate_variant:Nn \coffin_attach:NnnNnnnn { c , Nnnc , cnnc }
28564 \cs_new_protected:Npn \coffin_gattach:NnnNnnnn #1#2#3#4#5#6#7#8
28565 {
28566   \__coffin_attach:NnnNnnnnN #1 {#2} {#3} #4 {#5} {#6} {#7} {#8}
28567   \coffin_gset_eq:NN
28568 }
28569 \cs_generate_variant:Nn \coffin_gattach:NnnNnnnn { c , Nnnc , cnnc }
28570 \cs_new_protected:Npn \__coffin_attach:NnnNnnnnN #1#2#3#4#5#6#7#8#9
28571 {
28572   \__coffin_align:NnnNnnnnN
28573   #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
28574   \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
28575   \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
28576   \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
28577   \__coffin_reset_structure:N \l__coffin_aligned_coffin
28578   \prop_set_eq:cc
28579   {
28580     coffin ~ \__coffin_to_value:N \l__coffin_aligned_coffin
28581     \c_space_tl corners
28582   }
28583   { coffin ~ \__coffin_to_value:N #1 ~ corners }
28584   \__coffin_update_poles:N \l__coffin_aligned_coffin
28585   \__coffin_offset_poles:Nnn #1 { Opt } { Opt }
28586   \__coffin_offset_poles:Nnn #4
28587   { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
28588   \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
28589   \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
28590 }
28591 \cs_new_protected:Npn \__coffin_attach_mark:NnnNnnnn #1#2#3#4#5#6#7#8
28592 {
28593   \__coffin_align:NnnNnnnnN
28594   #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
28595   \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
28596   \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
28597   \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
28598   \box_set_eq:NN #1 \l__coffin_aligned_coffin
28599 }

```

(End definition for \coffin_attach:NnnNnnnn and others. These functions are documented on page 248.)

`__coffin_align:NnnNnnnnN` The internal function aligns the two coffins into a third one, but performs no corrections on the resulting coffin poles. The process begins by finding the points of intersection for the poles for each of the input coffins. Those for the first coffin are worked out after those for the second coffin, as this allows the ‘primed’ storage area to be used for the second coffin. The ‘real’ box offsets are then calculated, before using these to re-box the input coffins. The default poles are then set up, but the final result depends on how the bounding box is being handled.

```

28600 \cs_new_protected:Npn \__coffin_align:NnnNnnnnN #1#2#3#4#5#6#7#8#9
28601 {
28602   \__coffin_calculate_intersection:Nnn #4 {#5} {#6}
28603   \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }
28604   \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
28605   \__coffin_calculate_intersection:Nnn #1 {#2} {#3}

```

```

28606 \dim_set:Nn \l__coffin_offset_x_dim
28607 { \l__coffin_x_dim - \l__coffin_x_prime_dim + #7 }
28608 \dim_set:Nn \l__coffin_offset_y_dim
28609 { \l__coffin_y_dim - \l__coffin_y_prime_dim + #8 }
28610 \hbox_set:Nn \l__coffin_aligned_internal_coffin
28611 {
28612   \box_use:N #1
28613   \tex_kern:D -\box_wd:N #1
28614   \tex_kern:D \l__coffin_offset_x_dim
28615   \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #4 }
28616 }
28617 \coffin_set_eq:NN #9 \l__coffin_aligned_internal_coffin
28618 }

```

(End definition for _coffin_align:NnnNnnnnN.)

_coffin_offset_poles:Nnn
_coffin_offset_pole:Nnnnnnn

Transferring structures from one coffin to another requires that the positions are updated by the offset between the two coffins. This is done by mapping to the property list of the source coffins, moving as appropriate and saving to the new coffin data structures. The test for a - means that the structures from the parent coffins are uniquely labelled and do not depend on the order of alignment. The pay off for this is that - should not be used in coffin pole or handle names, and that multiple alignments do not result in a whole set of values.

```

28619 \cs_new_protected:Npn \_coffin_offset_poles:Nnn #1#2#3
28620 {
28621   \prop_map_inline:cn { coffin ~ \_coffin_to_value:N #1 ~ poles }
28622   { \_coffin_offset_pole:Nnnnnnn #1 {##1} ##2 {#2} {#3} }
28623 }
28624 \cs_new_protected:Npn \_coffin_offset_pole:Nnnnnnn #1#2#3#4#5#6#7#8
28625 {
28626   \dim_set:Nn \l__coffin_x_dim { #3 + #7 }
28627   \dim_set:Nn \l__coffin_y_dim { #4 + #8 }
28628   \tl_if_in:nnTF {#2} { - }
28629   { \tl_set:Nn \l__coffin_internal_tl { {#2} } }
28630   { \tl_set:Nn \l__coffin_internal_tl { { #1 - #2 } } }
28631   \exp_last_unbraced:NNo \_coffin_set_pole:Nnx \l__coffin_aligned_coffin
28632   { \l__coffin_internal_tl }
28633   {
28634     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
28635     {#5} {#6}
28636   }
28637 }

```

(End definition for _coffin_offset_poles:Nnn and _coffin_offset_pole:Nnnnnnn.)

_coffin_offset_corners:Nnn
_coffin_offset_corner:Nnnnn

Saving the offset corners of a coffin is very similar, except that there is no need to worry about naming: every corner can be saved here as order is unimportant.

```

28638 \cs_new_protected:Npn \_coffin_offset_corners:Nnn #1#2#3
28639 {
28640   \prop_map_inline:cn { coffin ~ \_coffin_to_value:N #1 ~ corners }
28641   { \_coffin_offset_corner:Nnnnn #1 {##1} ##2 {#2} {#3} }
28642 }
28643 \cs_new_protected:Npn \_coffin_offset_corner:Nnnnn #1#2#3#4#5#6
28644 {

```

```

28645 \prop_put:cnx
28646 {
28647   coffin ~ \__coffin_to_value:N \l__coffin_aligned_coffin
28648   \c_space_tl corners
28649 }
28650 { #1 - #2 }
28651 {
28652   { \dim_eval:n { #3 + #5 } }
28653   { \dim_eval:n { #4 + #6 } }
28654 }
28655 }

```

(End definition for __coffin_offset_corners:Nnn and __coffin_offset_corner:Nnnnn.)

```

\__coffin_update_vertical_poles:NNN
\__coffin_update_T:nnnnnnnnN
\__coffin_update_B:nnnnnnnnN

```

The T and B poles need to be recalculated after alignment. These functions find the larger absolute value for the poles, but this is of course only logical when the poles are horizontal.

```

28656 \cs_new_protected:Npn \__coffin_update_vertical_poles:NNN #1#2#3
28657 {
28658   \__coffin_get_pole:NnN #3 { #1 -T } \l__coffin_pole_a_tl
28659   \__coffin_get_pole:NnN #3 { #2 -T } \l__coffin_pole_b_tl
28660   \exp_last_two_unbraced:Noo \__coffin_update_T:nnnnnnnnN
28661   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
28662   \__coffin_get_pole:NnN #3 { #1 -B } \l__coffin_pole_a_tl
28663   \__coffin_get_pole:NnN #3 { #2 -B } \l__coffin_pole_b_tl
28664   \exp_last_two_unbraced:Noo \__coffin_update_B:nnnnnnnnN
28665   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
28666 }
28667 \cs_new_protected:Npn \__coffin_update_T:nnnnnnnnN #1#2#3#4#5#6#7#8#9
28668 {
28669   \dim_compare:nNnTF {#2} < {#6}
28670   {
28671     \__coffin_set_pole:Nnx #9 { T }
28672     { { Opt } {#6} { 1000pt } { Opt } }
28673   }
28674   {
28675     \__coffin_set_pole:Nnx #9 { T }
28676     { { Opt } {#2} { 1000pt } { Opt } }
28677   }
28678 }
28679 \cs_new_protected:Npn \__coffin_update_B:nnnnnnnnN #1#2#3#4#5#6#7#8#9
28680 {
28681   \dim_compare:nNnTF {#2} < {#6}
28682   {
28683     \__coffin_set_pole:Nnx #9 { B }
28684     { { Opt } {#2} { 1000pt } { Opt } }
28685   }
28686   {
28687     \__coffin_set_pole:Nnx #9 { B }
28688     { { Opt } {#6} { 1000pt } { Opt } }
28689   }
28690 }

```

(End definition for __coffin_update_vertical_poles:NNN, __coffin_update_T:nnnnnnnnN, and __coffin_update_B:nnnnnnnnN.)

`\c__coffin_empty_coffin` An empty-but-horizontal coffin.

```

28691 \coffin_new:N \c__coffin_empty_coffin
28692 \tex_setbox:D \c__coffin_empty_coffin = \tex_hbox:D { }

(End definition for \c__coffin_empty_coffin.)

```

`\coffin_typeset:Nnnnn` Typesetting a coffin means aligning it with the current position, which is done using a coffin with no content at all. As well as aligning to the empty coffin, there is also a need to leave vertical mode, if necessary.

`\coffin_typeset:cnnnn`

```

28693 \cs_new_protected:Npn \coffin_typeset:Nnnnn #1#2#3#4#5
28694 {
28695     \mode_leave_vertical:
28696     \__coffin_align:NnnNnnnnN \c__coffin_empty_coffin { H } { 1 }
28697     #1 {#2} {#3} {#4} {#5} \l__coffin_aligned_coffin
28698     \box_use_drop:N \l__coffin_aligned_coffin
28699 }
28700 \cs_generate_variant:Nn \coffin_typeset:Nnnnn { c }

(End definition for \coffin_typeset:Nnnnn. This function is documented on page 249.)

```

42.8 Coffin diagnostics

`\l__coffin_display_coffin` Used for printing coffins with data structures attached.

```

\l__coffin_display_coord_coffin 28701 \coffin_new:N \l__coffin_display_coffin
\l__coffin_display_pole_coffin 28702 \coffin_new:N \l__coffin_display_coord_coffin
28703 \coffin_new:N \l__coffin_display_pole_coffin

```

(End definition for `\l__coffin_display_coffin`, `\l__coffin_display_coord_coffin`, and `\l__coffin_display_pole_coffin`.)

`\l__coffin_display_handles_prop` This property list is used to print coffin handles at suitable positions. The offsets are expressed as multiples of the basic offset value, which therefore acts as a scale-factor.

```

28704 \prop_new:N \l__coffin_display_handles_prop
28705 \prop_put:Nnn \l__coffin_display_handles_prop { tl }
28706 { { b } { r } { -1 } { 1 } }
28707 \prop_put:Nnn \l__coffin_display_handles_prop { thc }
28708 { { b } { hc } { 0 } { 1 } }
28709 \prop_put:Nnn \l__coffin_display_handles_prop { tr }
28710 { { b } { l } { 1 } { 1 } }
28711 \prop_put:Nnn \l__coffin_display_handles_prop { vcl }
28712 { { vc } { r } { -1 } { 0 } }
28713 \prop_put:Nnn \l__coffin_display_handles_prop { vhc }
28714 { { vc } { hc } { 0 } { 0 } }
28715 \prop_put:Nnn \l__coffin_display_handles_prop { vcr }
28716 { { vc } { l } { 1 } { 0 } }
28717 \prop_put:Nnn \l__coffin_display_handles_prop { bl }
28718 { { t } { r } { -1 } { -1 } }
28719 \prop_put:Nnn \l__coffin_display_handles_prop { bhc }
28720 { { t } { hc } { 0 } { -1 } }
28721 \prop_put:Nnn \l__coffin_display_handles_prop { br }
28722 { { t } { l } { 1 } { -1 } }
28723 \prop_put:Nnn \l__coffin_display_handles_prop { Tl }
28724 { { t } { r } { -1 } { -1 } }
28725 \prop_put:Nnn \l__coffin_display_handles_prop { Thc }

```

```

28726 { { t } { hc } { 0 } { -1 } }
28727 \prop_put:Nnn \l__coffin_display_handles_prop { Tr }
28728 { { t } { 1 } { 1 } { -1 } }
28729 \prop_put:Nnn \l__coffin_display_handles_prop { Hl }
28730 { { vc } { r } { -1 } { 1 } }
28731 \prop_put:Nnn \l__coffin_display_handles_prop { Hhc }
28732 { { vc } { hc } { 0 } { 1 } }
28733 \prop_put:Nnn \l__coffin_display_handles_prop { Hr }
28734 { { vc } { 1 } { 1 } { 1 } }
28735 \prop_put:Nnn \l__coffin_display_handles_prop { Bl }
28736 { { b } { r } { -1 } { -1 } }
28737 \prop_put:Nnn \l__coffin_display_handles_prop { Bhc }
28738 { { b } { hc } { 0 } { -1 } }
28739 \prop_put:Nnn \l__coffin_display_handles_prop { Br }
28740 { { b } { 1 } { 1 } { -1 } }

```

(End definition for \l__coffin_display_handles_prop.)

`\l__coffin_display_offset_dim` The standard offset for the label from the handle position when displaying handles.

```

28741 \dim_new:N \l__coffin_display_offset_dim
28742 \dim_set:Nn \l__coffin_display_offset_dim { 2pt }

```

(End definition for \l__coffin_display_offset_dim.)

`\l__coffin_display_x_dim` As the intersections of poles have to be calculated to find which ones to print, there is
`\l__coffin_display_y_dim` a need to avoid repetition. This is done by saving the intersection into two dedicated
values.

```

28743 \dim_new:N \l__coffin_display_x_dim
28744 \dim_new:N \l__coffin_display_y_dim

```

(End definition for \l__coffin_display_x_dim and \l__coffin_display_y_dim.)

`\l__coffin_display_poles_prop` A property list for printing poles: various things need to be deleted from this to get a
“nice” output.

```

28745 \prop_new:N \l__coffin_display_poles_prop

```

(End definition for \l__coffin_display_poles_prop.)

`\l__coffin_display_font_tl` Stores the settings used to print coffin data: this keeps things flexible.

```

28746 \tl_new:N \l__coffin_display_font_tl
28747 ⟨*initex⟩
28748 \tl_set:Nn \l__coffin_display_font_tl { } % TODO
28749 ⟨/initex⟩
28750 ⟨*package⟩
28751 \tl_set:Nn \l__coffin_display_font_tl { \sfamily \tiny }
28752 ⟨/package⟩

```

(End definition for \l__coffin_display_font_tl.)

`__coffin_color:n` Calls `\color`, and otherwise does nothing if `\color` is not defined.

```

28753 \cs_new_protected:Npn \__coffin_color:n #1
28754 { \cs_if_exist:NT \color { \color {#1} } }

```

(End definition for __coffin_color:n.)

`\coffin_mark_handle:Nnnn` Marking a single handle is relatively easy. The standard attachment function is used, meaning that there are two calculations for the location. However, this is likely to be okay given the load expected. Contrast with the more optimised version for showing all handles which comes next.

```

28755 \cs_new_protected:Npn \coffin_mark_handle:Nnnn #1#2#3#4
28756 {
28757   \hcoffin_set:Nn \l__coffin_display_pole_coffin
28758     {
28759     (*initex)
28760       \hbox:n { \tex_vrule:D width 1pt height 1pt \scan_stop: } % TODO
28761     }
28762     (*package)
28763       \__coffin_color:n {#4}
28764       \rule { 1pt } { 1pt }
28765     }
28766   }
28767   \__coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
28768   \l__coffin_display_pole_coffin { hc } { vc } { Opt } { Opt }
28769   \hcoffin_set:Nn \l__coffin_display_coord_coffin
28770     {
28771     (*initex)
28772       % TODO
28773     }
28774     (*package)
28775       \__coffin_color:n {#4}
28776     }
28777     \l__coffin_display_font_tl
28778     ( \tl_to_str:n { #2 , #3 } )
28779   }
28780   \prop_get:NnN \l__coffin_display_handles_prop
28781     { #2 #3 } \l__coffin_internal_tl
28782   \quark_if_no_value:NTF \l__coffin_internal_tl
28783     {
28784       \prop_get:NnN \l__coffin_display_handles_prop
28785         { #3 #2 } \l__coffin_internal_tl
28786       \quark_if_no_value:NTF \l__coffin_internal_tl
28787         {
28788           \__coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
28789           \l__coffin_display_coord_coffin { l } { vc }
28790             { 1pt } { Opt }
28791         }
28792         {
28793           \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
28794             \l__coffin_internal_tl #1 {#2} {#3}
28795         }
28796       }
28797     {
28798       \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
28799         \l__coffin_internal_tl #1 {#2} {#3}
28800     }
28801   }
28802 \cs_new_protected:Npn \__coffin_mark_handle_aux:nnnnNnn #1#2#3#4#5#6#7
28803 {
28804   \__coffin_attach_mark:NnnNnnnn #5 {#6} {#7}

```

```

28805 \l__coffin_display_coord_coffin {#1} {#2}
28806 { #3 \l__coffin_display_offset_dim }
28807 { #4 \l__coffin_display_offset_dim }
28808 }
28809 \cs_generate_variant:Nn \coffin_mark_handle:Nnnn { c }

```

(End definition for `\coffin_mark_handle:Nnnn` and `__coffin_mark_handle_aux:nnnnNnn`. This function is documented on page 249.)

`\coffin_display_handles:Nn`
`\coffin_display_handles:cn`
`__coffin_display_handles_aux:nnnnnn`
`__coffin_display_handles_aux:nnnn`
`__coffin_display_attach:Nnnnn`

Printing the poles starts by removing any duplicates, for which the H poles is used as the definitive version for the baseline and bottom. Two loops are then used to find the combinations of handles for all of these poles. This is done such that poles are removed during the loops to avoid duplication.

```

28810 \cs_new_protected:Npn \coffin_display_handles:Nn #1#2
28811 {
28812   \hcoffin_set:Nn \l__coffin_display_pole_coffin
28813   {
28814     \*initex
28815     \hbox:n { \tex_vrule:D width 1pt height 1pt \scan_stop: } % TODO
28816     \*initex
28817     \*package
28818     \__coffin_color:n {#2}
28819     \rule { 1pt } { 1pt }
28820   }
28821 }
28822 \prop_set_eq:Nc \l__coffin_display_poles_prop
28823 { coffin ~ \__coffin_to_value:N #1 ~ poles }
28824 \__coffin_get_pole:NnN #1 { H } \l__coffin_pole_a_tl
28825 \__coffin_get_pole:NnN #1 { T } \l__coffin_pole_b_tl
28826 \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
28827 { \prop_remove:Nn \l__coffin_display_poles_prop { T } }
28828 \__coffin_get_pole:NnN #1 { B } \l__coffin_pole_b_tl
28829 \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
28830 { \prop_remove:Nn \l__coffin_display_poles_prop { B } }
28831 \coffin_set_eq:NN \l__coffin_display_coffin #1
28832 \prop_map_inline:Nn \l__coffin_display_poles_prop
28833 {
28834   \prop_remove:Nn \l__coffin_display_poles_prop {##1}
28835   \__coffin_display_handles_aux:nnnnnn {##1} ##2 {#2}
28836 }
28837 \box_use_drop:N \l__coffin_display_coffin
28838 }

```

For each pole there is a check for an intersection, which here does not give an error if none is found. The successful values are stored and used to align the pole coffin with the main coffin for output. The positions are recovered from the preset list if available.

```

28839 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnnnn #1#2#3#4#5#6
28840 {
28841   \prop_map_inline:Nn \l__coffin_display_poles_prop
28842   {
28843     \bool_set_false:N \l__coffin_error_bool
28844     \__coffin_calculate_intersection:nnnnnnnn {#2} {#3} {#4} {#5} ##2
28845     \bool_if:NF \l__coffin_error_bool
28846     {

```



```

28847 \dim_set:Nn \l__coffin_display_x_dim { \l__coffin_x_dim }
28848 \dim_set:Nn \l__coffin_display_y_dim { \l__coffin_y_dim }
28849 \__coffin_display_attach:Nnnnn
28850 \l__coffin_display_pole_coffin { hc } { vc }
28851 { Opt } { Opt }
28852 \hcoffin_set:Nn \l__coffin_display_coord_coffin
28853 {
28854 \*initex
28855 % TODO
28856 \*initex
28857 \*package
28858 \__coffin_color:n {#6}
28859 \package
28860 \l__coffin_display_font_tl
28861 ( \tl_to_str:n { #1 , ##1 } )
28862 }
28863 \prop_get:NnN \l__coffin_display_handles_prop
28864 { #1 ##1 } \l__coffin_internal_tl
28865 \quark_if_no_value:NTF \l__coffin_internal_tl
28866 {
28867 \prop_get:NnN \l__coffin_display_handles_prop
28868 { ##1 #1 } \l__coffin_internal_tl
28869 \quark_if_no_value:NTF \l__coffin_internal_tl
28870 {
28871 \__coffin_display_attach:Nnnnn
28872 \l__coffin_display_coord_coffin { l } { vc }
28873 { 1pt } { Opt }
28874 }
28875 {
28876 \exp_last_unbraced:No
28877 \__coffin_display_handles_aux:nnnn
28878 \l__coffin_internal_tl
28879 }
28880 }
28881 {
28882 \exp_last_unbraced:No \__coffin_display_handles_aux:nnnn
28883 \l__coffin_internal_tl
28884 }
28885 }
28886 }
28887 }
28888 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnn #1#2#3#4
28889 {
28890 \__coffin_display_attach:Nnnnn
28891 \l__coffin_display_coord_coffin {#1} {#2}
28892 { #3 \l__coffin_display_offset_dim }
28893 { #4 \l__coffin_display_offset_dim }
28894 }
28895 \cs_generate_variant:Nn \coffin_display_handles:Nn { c }

```

This is a dedicated version of `\coffin_attach:NnnNnnnn` with a hard-wired first coffin. As the intersection is already known and stored for the display coffin the code simply uses it directly, with no calculation.

```

28896 \cs_new_protected:Npn \__coffin_display_attach:Nnnnn #1#2#3#4#5

```

```

28897 {
28898   \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
28899   \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }
28900   \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
28901   \dim_set:Nn \l__coffin_offset_x_dim
28902     { \l__coffin_display_x_dim - \l__coffin_x_prime_dim + #4 }
28903   \dim_set:Nn \l__coffin_offset_y_dim
28904     { \l__coffin_display_y_dim - \l__coffin_y_prime_dim + #5 }
28905   \hbox_set:Nn \l__coffin_aligned_coffin
28906     {
28907       \box_use:N \l__coffin_display_coffin
28908       \tex_kern:D -\box_wd:N \l__coffin_display_coffin
28909       \tex_kern:D \l__coffin_offset_x_dim
28910       \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #1 }
28911     }
28912   \box_set_ht:Nn \l__coffin_aligned_coffin
28913     { \box_ht:N \l__coffin_display_coffin }
28914   \box_set_dp:Nn \l__coffin_aligned_coffin
28915     { \box_dp:N \l__coffin_display_coffin }
28916   \box_set_wd:Nn \l__coffin_aligned_coffin
28917     { \box_wd:N \l__coffin_display_coffin }
28918   \box_set_eq:NN \l__coffin_display_coffin \l__coffin_aligned_coffin
28919 }

```

(End definition for `\coffin_display_handles:Nn` and others. This function is documented on page 249.)

```

\coffin_show_structure:N For showing the various internal structures attached to a coffin in a way that keeps things
\coffin_show_structure:c relatively readable. If there is no apparent structure then the code complains.
\coffin_log_structure:N
\coffin_log_structure:c
\__coffin_show_structure:NN
28920 \cs_new_protected:Npn \coffin_show_structure:N
28921   { \__coffin_show_structure:NN \msg_show:nnxxxx }
28922 \cs_generate_variant:Nn \coffin_show_structure:N { c }
28923 \cs_new_protected:Npn \coffin_log_structure:N
28924   { \__coffin_show_structure:NN \msg_log:nnxxxx }
28925 \cs_generate_variant:Nn \coffin_log_structure:N { c }
28926 \cs_new_protected:Npn \__coffin_show_structure:NN #1#2
28927   {
28928     \__coffin_if_exist:NT #2
28929     {
28930       #1 { LaTeX / kernel } { show-coffin }
28931       { \token_to_str:N #2 }
28932       {
28933         \iow_newline: >~ ht ~~~ \dim_eval:n { \coffin_ht:N #2 }
28934         \iow_newline: >~ dp ~~~ \dim_eval:n { \coffin_dp:N #2 }
28935         \iow_newline: >~ wd ~~~ \dim_eval:n { \coffin_wd:N #2 }
28936       }
28937       {
28938         \prop_map_function:cN
28939           { coffin ~ \__coffin_to_value:N #2 ~ poles }
28940         \msg_show_item_unbraced:nn
28941       }
28942     }
28943   }
28944 }

```

(End definition for `\coffin_show_structure:N`, `\coffin_log_structure:N`, and `_coffin_show_structure:NN`. These functions are documented on page 249.)

42.9 Messages

```

28945 \__kernel_msg_new:nnnn { kernel } { no-pole-intersection }
28946 { No~intersection~between~coffin~poles. }
28947 {
28948   LaTeX~was~asked~to~find~the~intersection~between~two~poles,~
28949   but~they~do~not~have~a~unique~meeting~point:~
28950   the~value~(0pt,~0pt)~will~be~used.
28951 }
28952 \__kernel_msg_new:nnnn { kernel } { unknown-coffin }
28953 { Unknown~coffin~'#1'. }
28954 { The~coffin~'#1'~was~never~defined. }
28955 \__kernel_msg_new:nnnn { kernel } { unknown-coffin-pole }
28956 { Pole~'#1'~unknown~for~coffin~'#2'. }
28957 {
28958   LaTeX~was~asked~to~find~a~typesetting~pole~for~a~coffin,~
28959   but~either~the~coffin~does~not~exist~or~the~pole~name~is~wrong.
28960 }
28961 \__kernel_msg_new:nnn { kernel } { show-coffin }
28962 {
28963   Size~of~coffin~#1 : #2 \\
28964   Poles~of~coffin~#1 : #3 .
28965 }
28966 </initex | package>

```

43 l3color-base Implementation

```

28967 <*initex | package>
28968 <@@=color>

```

`\l__color_current_tl` The color currently active for foreground (text, *etc.*) material. This is stored in the form of a color model followed by one or more values. There are four pre-defined models, three of which take numerical values in the range [0, 1]:

- **gray** `<gray>` Grayscale color with the `<gray>` value running from 0 (fully black) to 1 (fully white)
- **cmk** `<cyan>` `<magenta>` `<yellow>` `<black>`
- **rgb** `<red>` `<green>` `<blue>`

Notice that the value are separated by spaces. There is a fourth pre-defined model using a string value and a numerical one:

- **spot** `<name>` `<tint>` A pre-defined spot color, where the `<name>` should be a pre-defined string color name and the `<tint>` should be in the range [0, 1].

Additional models may be created to allow mixing of spot colors. The number of data entries these require will depend on the number of colors to be mixed.

T_EXhackers note: The content of `\l__color_current_tl` is space-separated as this allows it to be used directly in specials in many common cases. This internal representation is close to that used by the dvips program.

(End definition for \l__color_current_tl.)

\color_group_begin: Grouping for color is the same as using the basic `\group_begin:` and `\group_end:` functions. However, for semantic reasons, they are renamed here.

```
28969 \cs_new_eq:NN \color_group_begin: \group_begin:
28970 \cs_new_eq:NN \color_group_end: \group_end:
```

(End definition for \color_group_begin: and \color_group_end:. These functions are documented on page 251.)

\color_ensure_current: A driver-independent wrapper for setting the foreground color to the current color “now”.

```
28971 \cs_new_protected:Npn \color_ensure_current:
28972 {
28973   (*package)
28974   \__color_backend_pickup:N \l__color_current_tl
28975   </package>
28976   \__color_select:V \l__color_current_tl
28977 }
```

(End definition for \color_ensure_current:. This function is documented on page 251.)

\s__color_stop Internal scan marks.

```
28978 \scan_new:N \s__color_stop
```

(End definition for \s__color_stop.)

__color_select:n Take an internal color specification and pass it to the driver. This code is needed to ensure the current color but will also be used by the higher-level experimental material.

```
\__color_select:V
\__color_select:w
\__color_select_cmyk:w
\__color_select_gray:w
\__color_select_rgb:w
\__color_select_spot:w
28979 \cs_new_protected:Npn \__color_select:n #1
28980 { \__color_select:w #1 \s__color_stop }
28981 \cs_generate_variant:Nn \__color_select:n { V }
28982 \cs_new_protected:Npn \__color_select:w #1 ~ #2 \s__color_stop
28983 { \use:c { \__color_select_ #1 :w } #2 \s__color_stop }
28984 \cs_new_protected:Npn \__color_select_cmyk:w #1 ~ #2 ~ #3 ~ #4 \s__color_stop
28985 { \__color_backend_cmyk:nnnn {#1} {#2} {#3} {#4} }
28986 \cs_new_protected:Npn \__color_select_gray:w #1 \s__color_stop
28987 { \__color_backend_gray:n {#1} }
28988 \cs_new_protected:Npn \__color_select_rgb:w #1 ~ #2 ~ #3 \s__color_stop
28989 { \__color_backend_rgb:nnn {#1} {#2} {#3} }
28990 \cs_new_protected:Npn \__color_select_spot:w #1 ~ #2 \s__color_stop
28991 { \__color_backend_spot:nn {#1} {#2} }
```

(End definition for __color_select:n and others.)

\l__color_current_tl As the setting data is used only for specials, and those are always space-separated, it makes most sense to hold the internal information in that form.

```
28992 \tl_new:N \l__color_current_tl
28993 \tl_set:Nn \l__color_current_tl { gray~0 }
```

(End definition for \l__color_current_tl.)

```
28994 </initex | package>
```

44 l3luatex implementation

28995 $\langle *initex | package \rangle$

44.1 Breaking out to Lua

28996 $\langle *tex \rangle$

28997 $\langle @@=lua \rangle$

$\backslash_lua_escape:n$ Copies of primitives.
 $\backslash_lua_now:n$ 28998 $\backslash cs_new_eq:NN \backslash_lua_escape:n \backslash tex_luaescapestring:D$
 $\backslash_lua_shipout:n$ 28999 $\backslash cs_new_eq:NN \backslash_lua_now:n \backslash tex_directlua:D$
 29000 $\backslash cs_new_eq:NN \backslash_lua_shipout:n \backslash tex_latalua:D$

(End definition for $\backslash_lua_escape:n$, $\backslash_lua_now:n$, and $\backslash_lua_shipout:n$.)

These functions are set up in l3str for bootstrapping: we want to replace them with a “proper” version at this stage, so clean up.

29001 $\backslash cs_undefine:N \backslash lua_escape:e$

29002 $\backslash cs_undefine:N \backslash lua_now:e$

$\backslash lua_now:n$ Wrappers around the primitives. As with engines other than LuaTeX these have to be
 $\backslash lua_now:e$ macros, we give them the same status in all cases. When LuaTeX is not in use, simply
 $\backslash lua_shipout_e:n$ give an error message/
 $\backslash lua_shipout:n$
 $\backslash lua_escape:n$
 $\backslash lua_escape:e$

29003 $\backslash cs_new:Npn \backslash lua_now:e \#1 \{ \backslash_lua_now:n \{ \#1 \} \}$
 29004 $\backslash cs_new:Npn \backslash lua_now:n \#1 \{ \backslash lua_now:e \{ \exp_not:n \{ \#1 \} \} \}$
 29005 $\backslash cs_new_protected:Npn \backslash lua_shipout_e:n \#1 \{ \backslash_lua_shipout:n \{ \#1 \} \}$
 29006 $\backslash cs_new_protected:Npn \backslash lua_shipout:n \#1$
 29007 $\{ \backslash lua_shipout_e:n \{ \exp_not:n \{ \#1 \} \} \}$
 29008 $\backslash cs_new:Npn \backslash lua_escape:e \#1 \{ \backslash_lua_escape:n \{ \#1 \} \}$
 29009 $\backslash cs_new:Npn \backslash lua_escape:n \#1 \{ \backslash lua_escape:e \{ \exp_not:n \{ \#1 \} \} \}$
 29010 $\backslash sys_if_engine_luatex:F$
 29011 $\{$
 29012 $\backslash clist_map_inline:nn$
 29013 $\{$
 29014 $\backslash lua_escape:n , \backslash lua_escape:e ,$
 29015 $\backslash lua_now:n , \backslash lua_now:e$
 29016 $\}$
 29017 $\{$
 29018 $\backslash cs_set:Npn \#1 \##1$
 29019 $\{$
 29020 $\backslash_kernel_msg_expandable_error:nnn$
 29021 $\{ kernel \} \{ luatex-required \} \{ \#1 \}$
 29022 $\}$
 29023 $\}$
 29024 $\backslash clist_map_inline:nn$
 29025 $\{ \backslash lua_shipout_e:n , \backslash lua_shipout:n \}$
 29026 $\{$
 29027 $\backslash cs_set_protected:Npn \#1 \##1$
 29028 $\{$
 29029 $\backslash_kernel_msg_error:nnn$
 29030 $\{ kernel \} \{ luatex-required \} \{ \#1 \}$
 29031 $\}$
 29032 $\}$
 29033 $\}$

(End definition for $\backslash lua_now:n$ and others. These functions are documented on page 252.)

44.2 Messages

```
29034 \__kernel_msg_new:nnnn { kernel } { luatex-required }
29035 { LuaTeX~engine~not~in~use!~Ignoring~#1. }
29036 {
29037     The~feature~you~are~using~is~only~available~
29038     with~the~LuaTeX~engine.~LaTeX3~ignored~'~#1'.
29039 }
29040 </tex>
```

44.3 Lua functions for internal use

```
29041 <*lua>
```

Most of the emulation of pdfTeX here is based heavily on Heiko Oberdiek's pdfTeX-cmds package.

13kernel Create a table for the kernel's own use.

```
29042 13kernel = 13kernel or { }
```

(End definition for 13kernel. This function is documented on page 253.)

Local copies of global tables.

```
29043 local io      = io
29044 local kpse    = kpse
29045 local lfs     = lfs
29046 local math    = math
29047 local md5     = md5
29048 local os      = os
29049 local string  = string
29050 local tex     = tex
29051 local texio   = texio
29052 local tonumber = tonumber
29053 local unicode = unicode
```

Local copies of standard functions.

```
29054 local abs      = math.abs
29055 local byte     = string.byte
29056 local floor    = math.floor
29057 local format   = string.format
29058 local gsub     = string.gsub
29059 local lfs_attr = lfs.attributes
29060 local md5_sum  = md5.sum
29061 local open     = io.open
29062 local os_clock = os.clock
29063 local os_date  = os.date
29064 local os_exec  = os.execute
29065 local setcatcode = tex.setcatcode
29066 local sprint   = tex.sprint
29067 local cprint   = tex.cprint
29068 local write    = tex.write
29069 local write_nl = texio.write_nl
```

Newer ConTeXt releases replace the unicode library by utf and since Lua 5.3 we can even use the Lua standard utf8 library.

```
29070 local utf8_char = (utf8 and utf8.char) or (utf and utf.char) or unicode.utf8.char
```

Deal with ConT_EXt: doesn't use kpse library.

```
29071 local kpse_find = (resolvers and resolvers.findfile) or kpse.find_file
```

escapehex An internal auxiliary to convert a string to the matching hex escape. This works on a byte basis: extension to handled UTF-8 input is covered in pdf_{tex}cmds but is not currently required here.

```
29072 local function escapehex(str)
29073   write((gsub(str, ".",
29074     function (ch) return format("%02X", byte(ch)) end)))
29075 end
```

(End definition for escapehex.)

l3kernel.charcat Creating arbitrary chars using tex.cprint.

```
29076 local charcat
29077 function charcat(charcode, catcode)
29078   cprint(catcode, utf8_char(charcode))
29079 end
29080 l3kernel.charcat = charcat
```

(End definition for l3kernel.charcat. This function is documented on page 253.)

l3kernel.elapsedtime Simple timing set up: give the result from the system clock in scaled seconds.

l3kernel.resettimer

```
29081 local base_time = 0
29082 local function elapsedtime()
29083   local val = (os_clock() - base_time) * 65536 + 0.5
29084   if val > 2147483647 then
29085     val = 2147483647
29086   end
29087   write(format("%d", floor(val)))
29088 end
29089 l3kernel.elapsedtime = elapsedtime
29090 local function resettimer()
29091   base_time = os_clock()
29092 end
29093 l3kernel.resettimer = resettimer
```

(End definition for l3kernel.elapsedtime and l3kernel.resettimer. These functions are documented on page 253.)

l3kernel.filedump Similar comments here to the next function: read the file in binary mode to avoid any line-end weirdness.

```
29094 local function filedump(name, offset, length)
29095   local file = kpse_find(name, "tex", true)
29096   if file then
29097     local length = tonumber(length) or lfs_attr(file, "size")
29098     local offset = tonumber(offset) or 0
29099     local f = open(file, "rb")
29100     if f then
29101       if offset > 0 then
29102         f:seek("set", offset)
29103       end
29104       local data = f:read(length)
29105       escapehex(data)

```

```

29106         f:close()
29107     end
29108 end
29109 end
29110 l3kernel.filedump = filedump

```

(End definition for l3kernel.filedump. This function is documented on page 253.)

l3kernel.filemdfivesum Read an entire file and hash it: the hash function itself is a built-in. As Lua is byte-based there is no work needed here in terms of UTF-8 (see `pdfdoccmds` and how it handles strings that have passed through LuaTeX). The file is read in binary mode so that no line ending normalisation occurs.

```

29111 local function filemdfivesum(name)
29112     local file = kpse_find(name, "tex", true)
29113     if file then
29114         local f = open(file, "rb")
29115         if f then
29116             local data = f:read("*a")
29117             escapehex(md5_sum(data))
29118             f:close()
29119         end
29120     end
29121 end
29122 l3kernel.filemdfivesum = filemdfivesum

```

(End definition for l3kernel.filemdfivesum. This function is documented on page 253.)

l3kernel.filemoddate See procedure `makepdftime` in `utils.c` of pdfTeX.

```

29123 local function filemoddate(name)
29124     local file = kpse_find(name, "tex", true)
29125     if file then
29126         local date = lfs_attr(file, "modification")
29127         if date then
29128             local d = os_date("!*t", date)
29129             if d.sec >= 60 then
29130                 d.sec = 59
29131             end
29132             local u = os_date("!*t", date)
29133             local off = 60 * (d.hour - u.hour) + d.min - u.min
29134             if d.year ~= u.year then
29135                 if d.year > u.year then
29136                     off = off + 1440
29137                 else
29138                     off = off - 1440
29139                 end
29140             elseif d.yday ~= u.yday then
29141                 if d.yday > u.yday then
29142                     off = off + 1440
29143                 else
29144                     off = off - 1440
29145                 end
29146             end
29147             local timezone
29148             if off == 0 then

```



```

29149         timezone = "Z"
29150     else
29151         local hours = floor(off / 60)
29152         local mins  = abs(off - hours * 60)
29153         timezone = format("%+03d", hours)
29154         .. "" .. format("%02d", mins) .. ""
29155     end
29156     write("D:"
29157         .. format("%04d", d.year)
29158         .. format("%02d", d.month)
29159         .. format("%02d", d.day)
29160         .. format("%02d", d.hour)
29161         .. format("%02d", d.min)
29162         .. format("%02d", d.sec)
29163         .. timezone)
29164     end
29165 end
29166 end
29167 l3kernel.filemoddate = filemoddate

```

(End definition for l3kernel.filemoddate. This function is documented on page 253.)

l3kernel.filesize A simple disk lookup.

```

29168 local function filesize(name)
29169     local file = kpse_find(name, "tex", true)
29170     if file then
29171         local size = lfs_attr(file, "size")
29172         if size then
29173             write(size)
29174         end
29175     end
29176 end
29177 l3kernel.filesize = filesize

```

(End definition for l3kernel.filesize. This function is documented on page 253.)

l3kernel.strcmp String comparison which gives the same results as pdfTeX's `\pdfstrcmp`, although the ordering should likely not be relied upon!

```

29178 local function strcmp(A, B)
29179     if A == B then
29180         write("0")
29181     elseif A < B then
29182         write("-1")
29183     else
29184         write("1")
29185     end
29186 end
29187 l3kernel.strcmp = strcmp

```

(End definition for l3kernel.strcmp. This function is documented on page 253.)

l3kernel.shellescape Replicating the pdfTeX log interaction for shell escape.

```

29188 local function shellescape(cmd)
29189     local status,msg = os_exec(cmd)
29190     if status == nil then

```

```

29191     write_nl("log","runsystem(" .. cmd .. ")...(" .. msg .. ")\n")
29192     elseif status == 0 then
29193         write_nl("log","runsystem(" .. cmd .. ")...executed\n")
29194     else
29195         write_nl("log","runsystem(" .. cmd .. ")...failed " .. (msg or "") .. "\n")
29196     end
29197 end
29198 l3kernel.shellescape = shellescape

```

(End definition for `l3kernel.shellescape`. This function is documented on page 253.)

44.4 Generic Lua and font support

```

29199 <*initex>
29200 <@@=alloc>

```

A small amount of generic code is used by almost all LuaTeX material so needs to be loaded by the format.

```

29201 attribute_count_name = "g__alloc_attribute_int"
29202 bytecode_count_name  = "g__alloc_bytecode_int"
29203 chunkname_count_name = "g__alloc_chunkname_int"
29204 whatsit_count_name    = "g__alloc_whatsit_int"
29205 require("ltxlua")

```

With the above available the font loader code used by plain T_EX and L^AT_EX 2_ε when used with LuaTeX can be loaded here. This is thus being treated more-or-less as part of the engine itself.

```

29206 require("luaotfload-main")
29207 local _void = luaotfload.main()
29208 </initex>
29209 </lua>
29210 </initex | package>

```

45 l3unicode implementation

```

29211 <*initex | package>
29212 <@@=char>

```

Case changing both for strings and “text” requires data from the Unicode Consortium. Some of this is build in to the format (as `\lccode` and `\uccode` values) but this covers only the simple one-to-one situations and does not fully handle for example case folding.

As only the data needs to remain at the end of this process, everything is set up inside a group. The only thing that is outside is creating a stream: they are global anyway and it is best to force a stream for all engines. For performance reasons, some of the code here is very low-level: the material is read during loading `expl3` in package mode.

```

29213 \ior_new:N \g__char_data_ior
29214 \bool_lazy_or:nnTF { \sys_if_engine luatex_p: } { \sys_if_engine xetex_p: }
29215 {
29216     \group_begin:

```

Access the primitive but suppress further expansion: active chars are otherwise an issue.

```

29217     \cs_set:Npn \__char_generate_char:n #1

```

```
29218 { \tex_detokenize:D \tex_expandafter:D { \tex_Uchar:D " #1 } }
```

A fast local implementation for generating characters; the chars may be active, so we prevent further expansion.

```
29219 \cs_set:Npx \__char_generate:n #1
29220 {
29221   \exp_not:N \tex_unexpanded:D \exp_not:N \exp_after:wN
29222   {
29223     \sys_if_engine luatex:TF
29224     {
29225       \exp_not:N \tex_directlua:D
29226       {
29227         l3kernel.charcat
29228         (
29229           \exp_not:N \tex_number:D #1 ,
29230           \exp_not:N \tex_the:D \tex_catcode:D #1
29231         )
29232       }
29233     }
29234     {
29235       \exp_not:N \tex_Ucharcat:D
29236       #1 ~
29237       \tex_catcode:D #1 ~
29238     }
29239   }
29240 }
```

Parse the main Unicode data file for two things. First, we want the titlecase exceptions: the one-to-one lower- and uppercase mappings it contains are all be covered by the T_EX data. Second, we need normalization data: at present, just the canonical NFD mappings. Those all yield either one or two codepoints, so the split is relatively easy.

```
29241 \ior_open:Nn \g__char_data_ior { UnicodeData.txt }
29242 \cs_set_protected:Npn \__char_data_auxi:w
29243   #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 ; #8 ; #9 ;
29244   {
29245     \tl_if_blank:nF {#6}
29246     {
29247       \tl_if_head_eq_charcode:nNF {#6} < % >
29248       { \__char_data_auxii:w #1 ; #6 ~ \q_stop }
29249     }
29250     \__char_data_auxiii:w #1 ;
29251   }
29252 \cs_set_protected:Npn \__char_data_auxii:w #1 ; #2 ~ #3 \q_stop
29253 {
29254   \tl_const:cx
29255   { c__char_nfd_ \__char_generate_char:n {#1} _tl }
29256   {
29257     \__char_generate:n { "#2 }
29258     \tl_if_blank:nF {#3}
29259     { \__char_generate:n { "#3 } }
29260   }
29261 }
29262 \cs_set_protected:Npn \__char_data_auxiii:w
29263   #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 ~ \q_stop
29264   {
```

```

29265 \cs_set_nopar:Npn \l__char_tmpa_tl {#7}
29266 \reverse_if:N \if_meaning:w \l__char_tmpa_tl \c_empty_tl
29267 \cs_set_nopar:Npn \l__char_tmpb_tl {#5}
29268 \reverse_if:N \if_meaning:w \l__char_tmpa_tl \l__char_tmpb_tl
29269 \tl_const:cx
29270 { c__char_titlecase_ \__char_generate_char:n {#1} _tl }
29271 { \__char_generate:n { "#7" } }
29272 \fi:
29273 \fi:
29274 }
29275 \group_begin:
29276 \char_set_catcode_space:n { '\ }%
29277 \ior_map_variable:NNn \g__char_data_ior \l__char_tmpa_tl
29278 {%
29279 \if_meaning:w \l__char_tmpa_tl \c_space_tl
29280 \exp_after:wN \ior_map_break:
29281 \fi:
29282 \exp_after:wN \__char_data_auxi:w \l__char_tmpa_tl \q_stop
29283 }%
29284 \group_end:
29285 \ior_close:N \g__char_data_ior

```

The other data files all use C-style comments so we have to worry about # tokens (and reading as strings). The set up for case folding is in two parts. For the basic (core) mappings, folding is the same as lower casing in most positions so only store the differences. For the more complex foldings, always store the result, splitting up the two or three code points in the input as required.

```

29286 \ior_open:Nn \g__char_data_ior { CaseFolding.txt }
29287 \cs_set_protected:Npn \__char_data_auxi:w #1 ;~ #2 ;~ #3 ; #4 \q_stop
29288 {
29289 \if:w \tl_head:n { #2 ? } C
29290 \reverse_if:N \if_int_compare:w
29291 \char_value_lccode:n {"#1"} = "#3 ~
29292 \tl_const:cx
29293 { c__char_foldcase_ \__char_generate_char:n {#1} _tl }
29294 { \__char_generate:n { "#3" } }
29295 \fi:
29296 \else:
29297 \if:w \tl_head:n { #2 ? } F
29298 \__char_data_auxii:w #1 ~ #3 ~ \q_stop
29299 \fi:
29300 \fi:
29301 }
29302 \cs_set_protected:Npn \__char_data_auxii:w #1 ~ #2 ~ #3 ~ #4 \q_stop
29303 {
29304 \tl_const:cx { c__char_foldcase_ \__char_generate_char:n {#1} _tl }
29305 {
29306 \__char_generate:n { "#2" }
29307 \__char_generate:n { "#3" }
29308 \tl_if_blank:nF {#4}
29309 { \__char_generate:n { \int_value:w "#4" } }
29310 }
29311 }
29312 \ior_str_map_inline:Nn \g__char_data_ior

```

```

29313     {
29314         \reverse_if:N \if:w \c_hash_str \tl_head:w #1 \c_hash_str \q_stop
29315         \__char_data_auxi:w #1 \q_stop
29316         \fi:
29317     }
29318     \ior_close:N \g__char_data_ior

```

For upper- and lowercasing special situations, there is a bit more to do as we also have title casing to consider, plus we need to stop part-way through the file.

```

29319     \ior_open:Nn \g__char_data_ior { SpecialCasing.txt }
29320     \cs_set_protected:Npn \__char_data_auxi:w
29321     #1 ;~ #2 ;~ #3 ;~ #4 ; #5 \q_stop
29322     {
29323         \use:n { \__char_data_auxii:w #1 ~ lower ~ #2 ~ } ~ \q_stop
29324         \use:n { \__char_data_auxii:w #1 ~ upper ~ #4 ~ } ~ \q_stop
29325         \str_if_eq:nnF {#3} {#4}
29326         { \use:n { \__char_data_auxii:w #1 ~ title ~ #3 ~ } ~ \q_stop }
29327     }
29328     \cs_set_protected:Npn \__char_data_auxii:w
29329     #1 ~ #2 ~ #3 ~ #4 ~ #5 \q_stop
29330     {
29331         \tl_if_empty:nF {#4}
29332         {
29333             \tl_const:cx { c__char_ #2 case_ \__char_generate_char:n {#1} _tl }
29334             {
29335                 \__char_generate:n { "#3 }
29336                 \__char_generate:n { "#4 }
29337                 \tl_if_blank:nF {#5}
29338                 { \__char_generate:n { "#5 } }
29339             }
29340         }
29341     }
29342     \ior_str_map_inline:Nn \g__char_data_ior
29343     {
29344         \str_if_eq:eeTF
29345         { \tl_head:w #1 \c_hash_str \q_stop }
29346         { \c_hash_str }
29347         {
29348             \str_if_eq:eeT
29349             {#1}
29350             { \c_hash_str \c_space_tl Conditional-Mappings }
29351             { \ior_map_break: }
29352         }
29353         { \__char_data_auxi:w #1 \q_stop }
29354     }
29355     \ior_close:N \g__char_data_ior
29356     \group_end:
29357 }

```

For the 8-bit engines, the above is skipped but there is still some set up required. As case changing can only be applied to bytes, and they have to be in the ASCII range, we define a series of data stores to represent them, and the data are used such that only these are ever case-changed. We do open and close one file to force allocation of a read: this keeps all engines in line.

```

29358 {

```

```

29359 \group_begin:
29360 \cs_set_protected:Npn \__char_tmp:NN #1#2
29361 {
29362   \quark_if_recursion_tail_stop:N #2
29363   \tl_const:cn { c__char_uppercase_ #2 _tl } {#1}
29364   \tl_const:cn { c__char_lowercase_ #1 _tl } {#2}
29365   \tl_const:cn { c__char_foldcase_ #1 _tl } {#2}
29366   \__char_tmp:NN
29367 }
29368 \__char_tmp:NN
29369 AaBbCcDdEeFfGgHhIiJjKkLlMmNnOoPpQqRrSsTtUuVvWwXxYyZz
29370 ? \q_recursion_tail \q_recursion_stop
29371 \ior_open:Nn \g__char_data_ior { UnicodeData.txt }
29372 \ior_close:N \g__char_data_ior
29373 \group_end:
29374 }
29375 </initex | package>

```

46 l3text implementation

```

29376 <*initex | package>
29377 <@@=text>

```

46.1 Internal auxiliaries

\s__text_stop Internal scan marks.

```

29378 \scan_new:N \s__text_stop
(End definition for \s__text_stop.)

```

\q__text_nil Internal quarks.

```

29379 \quark_new:N \q__text_nil
(End definition for \q__text_nil.)

```

__text_quark_if_nil_p:n Branching quark conditional.

```

\__text_quark_if_nil:nTF
29380 \__kernel_quark_new_conditional:Nn \__text_quark_if_nil:n { TF }
(End definition for \__text_quark_if_nil:nTF.)

```

\q__text_recursion_tail Internal recursion quarks.

```

\q__text_recursion_stop
29381 \quark_new:N \q__text_recursion_tail
29382 \quark_new:N \q__text_recursion_stop
(End definition for \q__text_recursion_tail and \q__text_recursion_stop.)

```

__text_use_i_delimit_by_q_recursion_stop:nw Functions to gobble up to a quark.

```

29383 \cs_new:Npn \__text_use_i_delimit_by_q_recursion_stop:nw
29384 #1 #2 \q__text_recursion_stop {#1}
(End definition for \__text_use_i_delimit_by_q_recursion_stop:nw.)

```

__text_if_recursion_tail_stop_do:Nn Functions to query recursion quarks.

```

29385 \__kernel_quark_new_test:N \__text_if_recursion_tail_stop_do:Nn
(End definition for \__text_if_recursion_tail_stop_do:Nn.)

```

46.2 Utilities

The idea here is to take a token and ensure that if it's an implicit char, we output the explicit version. Otherwise, the token needs to be unchanged. First, we have to split between control sequences and everything else.

```

\__text_token_to_explicit:N
  \_text_token_to_explicit_char:N
  \_text_token_to_explicit_cs:N
  \_text_token_to_explicit_cs_aux:N
\__text_token_to_explicit:n
  \_text_token_to_explicit_auxi:w
  \_text_token_to_explicit_auxii:w
  \_text_token_to_explicit_auxiii:w
29386 \group_begin:
29387   \char_set_catcode_active:n { 0 }
29388   \cs_new:Npn \__text_token_to_explicit:N #1
29389     {
29390       \if_catcode:w \exp_not:N #1
29391         \if_catcode:w \scan_stop: \exp_not:N #1
29392           \scan_stop:
29393         \else:
29394           \exp_not:N ^^@
29395         \fi:
29396         \exp_after:wN \__text_token_to_explicit_cs:N
29397       \else:
29398         \exp_after:wN \__text_token_to_explicit_char:N
29399       \fi:
29400       #1
29401     }
29402 \group_end:

```

For control sequences, we can check for macros versus other cases using `\if_meaning:w`, then explicitly check for `\chardef` and `\mathchardef`.

```

29403 \cs_new:Npn \__text_token_to_explicit_cs:N #1
29404   {
29405     \exp_after:wN \if_meaning:w \exp_not:N #1 #1
29406     \exp_after:wN \use:nn \exp_after:wN
29407       \__text_token_to_explicit_cs_aux:N
29408   \else:
29409     \exp_after:wN \exp_not:n
29410   \fi:
29411   {#1}
29412 }
29413 \cs_new:Npn \__text_token_to_explicit_cs_aux:N #1
29414   {
29415     \bool_lazy_or:nnTF
29416       { \token_if_chardef_p:N #1 }
29417       { \token_if_mathchardef_p:N #1 }
29418     {
29419       \char_generate:nn {#1}
29420       { \char_value_catcode:n {#1} }
29421     }
29422     {#1}
29423   }

```

For character tokens, we need to filter out the implicit characters from those that are explicit. That's done here, then if necessary we work out the category code and generate the char. To avoid issues with alignment tabs, that one is done by elimination rather than looking up the code explicitly. The trick with finding the charcode is that the $\text{T}_{\text{E}}\text{X}$ messages are either the *⟨something⟩* character *⟨char⟩* or the *⟨type⟩* *⟨char⟩*.

```

29424 \cs_new:Npn \__text_token_to_explicit_char:N #1
29425   {

```

```

29426 \if:w
29427 \if_catcode:w ^ \exp_args:No \str_tail:n { \token_to_str:N #1 } ^
29428 \token_to_str:N #1 #1
29429 \else:
29430 AB
29431 \fi:
29432 \exp_after:wN \exp_not:n
29433 \else:
29434 \exp_after:wN \__text_token_to_explicit:n
29435 \fi:
29436 {#1}
29437 }
29438 \cs_new:Npn \__text_token_to_explicit:n #1
29439 {
29440 \exp_after:wN \__text_token_to_explicit_auxi:w
29441 \int_value:w
29442 \if_catcode:w \c_group_begin_token #1 1 \else:
29443 \if_catcode:w \c_group_end_token #1 2 \else:
29444 \if_catcode:w \c_math_toggle_token #1 3 \else:
29445 \if_catcode:w ## #1 6 \else:
29446 \if_catcode:w ^ #1 7 \else:
29447 \if_catcode:w \c_math_subscript_token #1 8 \else:
29448 \if_catcode:w \c_space_token #1 10 \else:
29449 \if_catcode:w A #1 11 \else:
29450 \if_catcode:w + #1 12 \else:
29451 4 \fi: \fi: \fi: \fi: \fi: \fi: \fi:
29452 \exp_after:wN ;
29453 \token_to_meaning:N #1 \s__text_stop
29454 }
29455 \cs_new:Npn \__text_token_to_explicit_auxi:w #1 ; #2 \s__text_stop
29456 {
29457 \char_generate:nn
29458 {
29459 \if_int_compare:w #1 < 9 \exp_stop_f:
29460 \exp_after:wN \__text_token_to_explicit_auxii:w
29461 \else:
29462 \exp_after:wN \__text_token_to_explicit_auxiii:w
29463 \fi:
29464 #2
29465 }
29466 {#1}
29467 }
29468 \exp_last_unbraced:NNNNo \cs_new:Npn \__text_token_to_explicit_auxii:w
29469 #1 { \tl_to_str:n { character ~ } } { ' }
29470 \cs_new:Npn \__text_token_to_explicit_auxiii:w #1 ~ #2 ~ { ' }

```

(End definition for `__text_token_to_explicit:N` and others.)

`__text_char_catcode:N` An idea from `l3char`: we need to get the category code of a specific token, not the general case.

```

29471 \cs_new:Npn \__text_char_catcode:N #1
29472 {
29473 \if_catcode:w \exp_not:N #1 \c_math_toggle_token
29474 3

```



```

29475 \else:
29476 \if_catcode:w \exp_not:N #1 \c_alignment_token
29477 4
29478 \else:
29479 \if_catcode:w \exp_not:N #1 \c_math_superscript_token
29480 7
29481 \else:
29482 \if_catcode:w \exp_not:N #1 \c_math_subscript_token
29483 8
29484 \else:
29485 \if_catcode:w \exp_not:N #1 \c_space_token
29486 10
29487 \else:
29488 \if_catcode:w \exp_not:N #1 \c_catcode_letter_token
29489 11
29490 \else:
29491 \if_catcode:w \exp_not:N #1 \c_catcode_other_token
29492 12
29493 \else:
29494 13
29495 \fi:
29496 \fi:
29497 \fi:
29498 \fi:
29499 \fi:
29500 \fi:
29501 \fi:
29502 }

```

(End definition for `_text_char_catcode:N`.)

`_text_if_expandable:NTF` Test for tokens that make sense to expand here: that is more restrictive than the engine view.

```

29503 \prg_new_conditional:Npnn \_text_if_expandable:N #1 { T , F , TF }
29504 {
29505   \token_if_expandable:NTF #1
29506   {
29507     \bool_lazy_any:nTF
29508     {
29509       { \token_if_protected_macro_p:N #1 }
29510       { \token_if_protected_long_macro_p:N #1 }
29511       { \token_if_eq_meaning_p:NN \q__text_recursion_tail #1 }
29512     }
29513     { \prg_return_false: }
29514     { \prg_return_true: }
29515   }
29516   { \prg_return_false: }
29517 }

```

(End definition for `_text_if_expandable:NTF`.)

46.3 Configuration variables

`\l_text_accents_tl` Special cases for accents and letter-like symbols, which in some cases will need to be converted further.
`\l_text_letterlike_tl`

```

29518 \tl_new:N \l_text_accents_tl
29519 \tl_set:Nn \l_text_accents_tl
29520 { \‘ \’ \^ \~ \= \u \. \” \r \H \v \d \c \k \b \t }
29521 \tl_new:N \l_text_letterlike_tl
29522 \tl_set:Nn \l_text_letterlike_tl
29523 {
29524   \AA \aa
29525   \AE \ae
29526   \DH \dh
29527   \DJ \dj
29528   \IJ \ij
29529   \L \l
29530   \NG \ng
29531   \O \o
29532   \OE \oe
29533   \SS \ss
29534   \TH \th
29535 }
29536 \tl_set:Nn \l_text_letterlike_tl {}
29537 \end{package}

```

(End definition for `\l_text_accents_tl` and `\l_text_letterlike_tl`. These variables are documented on page 258.)

`\l_text_case_exclude_arg_tl` Non-text arguments.

```

29538 \tl_new:N \l_text_case_exclude_arg_tl
29539 \tl_set:Nn \l_text_case_exclude_arg_tl { \begin \cite \end \label \ref }

```

(End definition for `\l_text_case_exclude_arg_tl`. This variable is documented on page 258.)

`\l_text_math_arg_tl` Math mode as arguments.

```

29540 \tl_new:N \l_text_math_arg_tl
29541 \tl_set:Nn \l_text_math_arg_tl { \ensuremath }

```

(End definition for `\l_text_math_arg_tl`. This variable is documented on page 258.)

`\l_text_math_delims_tl` Paired math mode delimiters.

```

29542 \tl_new:N \l_text_math_delims_tl
29543 \tl_set:Nn \l_text_math_delims_tl { $ $ \ ( \ ) }

```

(End definition for `\l_text_math_delims_tl`. This variable is documented on page 258.)

`\l_text_expand_exclude_tl` Commands which need not to expand.

```

29544 \tl_new:N \l_text_expand_exclude_tl
29545 \begin{package}
29546 \tl_set:Nn \l_text_expand_exclude_tl
29547 { \begin \cite \end \label \ref }
29548 \end{package}

```

(End definition for `\l_text_expand_exclude_tl`. This variable is documented on page 258.)

`\l__text_math_mode_tl` Used to control math mode output: internal as there is a dedicated setter.

```

29549 \tl_new:N \l__text_math_mode_tl

```

(End definition for `\l__text_math_mode_tl`.)

46.4 Expansion to formatted text

Markers for implicit char handling.

```
\c__text_chardef_space_token
\c__text_mathchardef_space_token
\c__text_chardef_group_begin_token
\c__text_mathchardef_group_begin_token
\c__text_chardef_group_end_token
\c__text_mathchardef_group_end_token
29550 \tex_chardef:D \c__text_chardef_space_token = '\ %
29551 \tex_mathchardef:D \c__text_mathchardef_space_token = '\ %
29552 \tex_chardef:D \c__text_chardef_group_begin_token = '\{ % '\}
29553 \tex_mathchardef:D \c__text_mathchardef_group_begin_token = '\{ % '\} '\{
29554 \tex_chardef:D \c__text_chardef_group_end_token = '\} % '\{
29555 \tex_mathchardef:D \c__text_mathchardef_group_end_token = '\} %
```

(End definition for `\c__text_chardef_space_token` and others.)

After precautions against & tokens, start a simple loop: that of course means that “text” cannot contain the two recursion quarks. The loop here must be f-type expandable; we have arbitrary user commands which might be protected *and* take arguments, and if the expansion code is used in a typesetting context, that will otherwise explode. (The same issue applies more clearly to case changing: see the example there.)

```
\text_expand:n
__text_expand:n
__text_expand_result:n
__text_expand_store:n
__text_expand_store:o
__text_expand_store:nw
__text_expand_end:w
__text_expand_loop:w
__text_expand_group:n
__text_expand_space:w
__text_expand_N_type:N
__text_expand_N_type_auxi:N
__text_expand_N_type_auxii:N
__text_expand_N_type_auxiii:N
__text_expand_math_search:NNN
__text_expand_math_loop:Nw
__text_expand_math_N_type:N
__text_expand_math_group:Nn
__text_expand_math_space:Nw
__text_expand_implicit:N
__text_expand_explicit:N
__text_expand_exclude:N
__text_expand_exclude:nN
__text_expand_exclude:NN
__text_expand_exclude:Nn
__text_expand_letterlike:N
__text_expand_letterlike:NN
__text_expand_cs:N
__text_expand_encoding:N
__text_expand_encoding_escape:N
__text_expand_protect:N
__text_expand_protect:nN
__text_expand_protect:Nw
__text_expand_replace:N
__text_expand_replace:n
__text_expand_cs_expand:N
__text_expand_noexpand:nn
29556 \cs_new:Npn \text_expand:n #1
29557 {
29558   __kernel_exp_not:w \exp_after:wN
29559   {
29560     \exp:w
29561     __text_expand:n {#1}
29562   }
29563 }
29564 \cs_new:Npn __text_expand:n #1
29565 {
29566   \group_align_safe_begin:
29567   __text_expand_loop:w #1
29568   \q__text_recursion_tail \q__text_recursion_stop
29569   __text_expand_result:n { }
29570 }
```

The approach to making the code f-type expandable is to use a marker result token and to shuffle the collected tokens

```
29571 \cs_new:Npn __text_expand_store:n #1
29572 { __text_expand_store:nw {#1} }
29573 \cs_generate_variant:Nn __text_expand_store:n { o }
29574 \cs_new:Npn __text_expand_store:nw #1#2 __text_expand_result:n #3
29575 { #2 __text_expand_result:n { #3 #1 } }
29576 \cs_new:Npn __text_expand_end:w #1 __text_expand_result:n #2
29577 {
29578   \group_align_safe_end:
29579   \exp_end:
29580   #2
29581 }
```

The main loop is a standard “tl action”; groups are handled recursively, while spaces are just passed through. Thus all of the action is in handling N-type tokens.

```
29582 \cs_new:Npn __text_expand_loop:w #1 \q__text_recursion_stop
29583 {
29584   \tl_if_head_is_N_type:nTF {#1}
29585   { __text_expand_N_type:N }
29586   {
29587     \tl_if_head_is_group:nTF {#1}
```

```

29588         { \__text_expand_group:n }
29589         { \__text_expand_space:w }
29590     }
29591     #1 \q__text_recursion_stop
29592 }
29593 \cs_new:Npn \__text_expand_group:n #1
29594 {
29595     \__text_expand_store:o
29596     {
29597         \exp_after:wN
29598         {
29599             \exp:w
29600             \__text_expand:n {#1}
29601         }
29602     }
29603     \__text_expand_loop:w
29604 }
29605 \exp_last_unbraced:NNo \cs_new:Npn \__text_expand_space:w \c_space_tl
29606 {
29607     \__text_expand_store:n { ~ }
29608     \__text_expand_loop:w
29609 }

```

Before we get into the real work, we have to watch out for problematic implicit characters: spaces and grouping tokens. Converting these to explicit characters later would lead to real issues as they are *not* N-type. A space is the easy case, so it's dealt with first: just insert the explicit token and continue the loop.

```

29610 \cs_new:Npx \__text_expand_N_type:N #1
29611 {
29612     \exp_not:N \__text_if_recursion_tail_stop_do:Nn #1
29613     { \exp_not:N \__text_expand_end:w }
29614     \exp_not:N \bool_lazy_any:nTF
29615     {
29616         { \exp_not:N \token_if_eq_meaning_p:NN #1 \c_space_token }
29617         {
29618             \exp_not:N \token_if_eq_meaning_p:NN #1
29619             \c__text_chardef_space_token
29620         }
29621         {
29622             \exp_not:N \token_if_eq_meaning_p:NN #1
29623             \c__text_mathchardef_space_token
29624         }
29625     }
29626     { \exp_not:N \__text_expand_space:w \c_space_tl }
29627     { \exp_not:N \__text_expand_N_type_auxi:N #1 }
29628 }

```

Implicit {/} offer two issues. First, the token could be an implicit brace character: we need to avoid turning that into a brace group, so filter out the cases manually. Then we handle the case where an implicit group is present. That is done in an “open-ended” way: there's the possibility the closing token is hidden somewhere.

```

29629 \cs_new:Npn \__text_expand_N_type_auxi:N #1
29630 {
29631     \bool_lazy_or:nnTF

```

```

29632 { \token_if_eq_meaning_p:NN #1 \c__text_chardef_group_begin_token }
29633 { \token_if_eq_meaning_p:NN #1 \c__text_mathchardef_group_begin_token }
29634 {
29635   \__text_expand_store:o \c_left_brace_str
29636   \__text_expand_loop:w
29637 }
29638 {
29639   \bool_lazy_or:nnTF
29640   { \token_if_eq_meaning_p:NN #1 \c__text_chardef_group_end_token }
29641   { \token_if_eq_meaning_p:NN #1 \c__text_mathchardef_group_end_token }
29642   {
29643     \__text_expand_store:o \c_right_brace_str
29644     \__text_expand_loop:w
29645   }
29646   { \__text_expand_N_type_auxii:N #1 }
29647 }
29648 }
29649 \cs_new:Npn \__text_expand_N_type_auxii:N #1
29650 {
29651   \token_if_eq_meaning:NNTF #1 \c_group_begin_token
29652   {
29653     { \if_false: } \fi:
29654     \__text_expand_loop:w
29655   }
29656   {
29657     \token_if_eq_meaning:NNTF #1 \c_group_end_token
29658     {
29659       \if_false: { \fi: }
29660       \__text_expand_loop:w
29661     }
29662     { \__text_expand_N_type_auxiii:N #1 }
29663   }
29664 }

```

The first step in dealing with N-type tokens is to look for math mode material: that needs to be left alone. The starting function has to be split into two as we need `\quark_if_recursion_tail_stop:N` first before we can trigger the search. We then look for matching pairs of delimiters, allowing for the case where math mode starts but does not end. Within math mode, we simply pass all the tokens through unchanged, just checking the N-type ones against the end marker.

```

29665 \cs_new:Npn \__text_expand_N_type_auxiii:N #1
29666 {
29667   \exp_after:wN \__text_expand_math_search:NNN
29668   \exp_after:wN #1 \l_text_math_delims_tl
29669   \q__text_recursion_tail \q__text_recursion_tail
29670   \q__text_recursion_stop
29671 }
29672 \cs_new:Npn \__text_expand_math_search:NNN #1#2#3
29673 {
29674   \__text_if_recursion_tail_stop_do:Nn #2
29675   { \__text_expand_explicit:N #1 }
29676   \token_if_eq_meaning:NNTF #1 #2
29677   {
29678     \__text_use_i_delimit_by_q_recursion_stop:nw

```

```

29679         {
29680             \_text_expand_store:n {#1}
29681             \_text_expand_math_loop:Nw #3
29682         }
29683     }
29684     { \_text_expand_math_search:NNN #1 }
29685 }
29686 \cs_new:Npn \_text_expand_math_loop:Nw #1#2 \q__text_recursion_stop
29687 {
29688     \tl_if_head_is_N_type:nTF {#2}
29689     { \_text_expand_math_N_type:NN }
29690     {
29691         \tl_if_head_is_group:nTF {#2}
29692         { \_text_expand_math_group:Nn }
29693         { \_text_expand_math_space:Nw }
29694     }
29695     #1#2 \q__text_recursion_stop
29696 }
29697 \cs_new:Npn \_text_expand_math_N_type:NN #1#2
29698 {
29699     \_text_if_recursion_tail_stop_do:Nn #2
29700     { \_text_expand_end:w }
29701     \_text_expand_store:n {#2}
29702     \token_if_eq_meaning:NNTF #2 #1
29703     { \_text_expand_loop:w }
29704     { \_text_expand_math_loop:Nw #1 }
29705 }
29706 \cs_new:Npn \_text_expand_math_group:Nn #1#2
29707 {
29708     \_text_expand_store:n { {#2} }
29709     \_text_expand_math_loop:Nw #1
29710 }
29711 \exp_after:wN \cs_new:Npn \exp_after:wN \_text_expand_math_space:Nw
29712 \exp_after:wN # \exp_after:wN 1 \c_space_tl
29713 {
29714     \_text_expand_store:n { ~ }
29715     \_text_expand_math_loop:Nw #1
29716 }

```

At this stage, either we have a control sequence or a simple character: split and handle.

```

29717 \cs_new:Npn \_text_expand_explicit:N #1
29718 {
29719     \token_if_cs:NNTF #1
29720     { \_text_expand_exclude:N #1 }
29721     {
29722         \_text_expand_store:n {#1}
29723         \_text_expand_loop:w
29724     }
29725 }
29726 % Next we exclude math commands: this is mainly as there \emph{might} be an
29727 % \cs{ensuremath}. We also handle accents, which are basically the same issue
29728 % but are kept separate for semantic reasons.
29729 % \begin{macrocode}
29730 \cs_new:Npn \_text_expand_exclude:N #1
29731 {

```

```

29732 \<initex>
29733   \exp_after:wN \_text_expand_exclude:NN
29734   \l_text_math_arg_tl
29735   #1
29736   \q__text_recursion_tail \q__text_recursion_stop
29737 \</initex>
29738 \<package>
29739   \exp_args:Ne \_text_expand_exclude:nN
29740   {
29741     \exp_not:V \l_text_math_arg_tl
29742     \exp_not:V \l_text_accents_tl
29743     \exp_not:V \l_text_expand_exclude_tl
29744   }
29745   #1
29746 \</package>
29747 }
29748 \<package>
29749 \cs_new:Npn \_text_expand_exclude:nN #1#2
29750 {
29751   \_text_expand_exclude:NN #2 #1
29752   \q__text_recursion_tail \q__text_recursion_stop
29753 }
29754 \</package>
29755 \cs_new:Npn \_text_expand_exclude:NN #1#2
29756 {
29757   \_text_if_recursion_tail_stop_do:Nn #2
29758 \<initex>
29759   { \_text_expand_cs:N #1 }
29760 \</initex>
29761 \<package>
29762   { \_text_expand_letterlike:N #1 }
29763 \</package>
29764 \cs_if_eq:NNTF #2 #1
29765 {
29766   \_text_use_i_delimit_by_q_recursion_stop:nw
29767   { \_text_expand_exclude:Nn #1 }
29768 }
29769 { \_text_expand_exclude:NN #1 }
29770 }
29771 \cs_new:Npn \_text_expand_exclude:Nn #1#2
29772 {
29773   \_text_expand_store:n { #1 {#2} }
29774   \_text_expand_loop:w
29775 }

```

Another list of exceptions: these ones take no arguments so are easier to handle.

```

29776 \<package>
29777 \cs_new:Npn \_text_expand_letterlike:N #1
29778 {
29779   \exp_after:wN \_text_expand_letterlike:NN \exp_after:wN
29780   #1 \l_text_letterlike_tl
29781   \q__text_recursion_tail \q__text_recursion_stop
29782 }
29783 \cs_new:Npn \_text_expand_letterlike:NN #1#2
29784 {

```

```

29785 \__text_if_recursion_tail_stop_do:Nn #2
29786 { \__text_expand_cs:N #1 }
29787 \cs_if_eq:NNTF #2 #1
29788 {
29789   \__text_use_i_delimit_by_q_recursion_stop:nw
29790   {
29791     \__text_expand_store:n {#1}
29792     \__text_expand_loop:w
29793   }
29794 }
29795 { \__text_expand_letterlike:NN #1 }
29796 }
29797 \endpackage

```

L^AT_EX 2_ε’s `\protect` makes life interesting. Where possible, we simply remove it and replace with the “parent” command; of course, the `\protect` might be explicit, in which case we need to leave it alone if it’s required.

```

29798 \cs_new:Npx \__text_expand_cs:N #1
29799 {
29800   \exp_not:N \str_if_eq:nnTF {#1} { \exp_not:N \protect }
29801   { \exp_not:N \__text_expand_protect:N }
29802   {
29803     \cs_if_exist:cTF { @current@cmd }
29804     { \exp_not:N \__text_expand_encoding:N #1 }
29805     { \exp_not:N \__text_expand_replace:N #1 }
29806   }
29807 }
29808 \cs_new:Npn \__text_expand_protect:N #1
29809 {
29810   \exp_args:Ne \__text_expand_protect:nN
29811   { \cs_to_str:N #1 } #1
29812 }
29813 \cs_new:Npn \__text_expand_protect:nN #1#2
29814 { \__text_expand_protect:Nw #2 #1 \q__text_nil #1 ~ \q__text_nil \q__text_nil \s__text_stop
29815 \cs_new:Npn \__text_expand_protect:Nw #1 #2 ~ \q__text_nil #3 \q__text_nil #4 \s__text_stop
29816 {
29817   \__text_quark_if_nil:nTF {#4}
29818   {
29819     \cs_if_exist:cTF {#2}
29820     { \exp_args:Ne \__text_expand_store:n { \exp_not:c {#2} } }
29821     { \__text_expand_store:n { \protect #1 } }
29822   }
29823   { \__text_expand_store:n { \protect #1 } }
29824   \__text_expand_loop:w
29825 }

```

Deal with encoding-specific commands

```

29826 \cs_new:Npn \__text_expand_encoding:N #1
29827 {
29828   \cs_if_eq:NNTF #1 \@current@cmd
29829   { \exp_after:wN \__text_expand_loop:w \__text_expand_encoding_escape:NN }
29830   {
29831     \cs_if_eq:NNTF #1 \@changed@cmd
29832     {
29833       \exp_after:wN \__text_expand_loop:w

```



```

29834         \_text_expand_encoding_escape:NN
29835     }
29836     { \_text_expand_replace:N #1 }
29837 }
29838 }
29839 \cs_new:Npn \_text_expand_encoding_escape:NN #1#2 { \exp_not:n {#1} }

```

See if there is a dedicated replacement, and if there is, insert it.

```

29840 \cs_new:Npn \_text_expand_replace:N #1
29841 {
29842     \bool_lazy_and:nnTF
29843     { \cs_if_exist_p:c { l\_text_expand\_token_to_str:N #1\_tl } }
29844     {
29845         \bool_lazy_or_p:nn
29846         { \token_if_cs_p:N #1 }
29847         { \token_if_active_p:N #1 }
29848     }
29849     {
29850         \exp_args:Nv \_text_expand_replace:n
29851         { l\_text_expand\_token_to_str:N #1\_tl }
29852     }
29853     { \_text_expand_cs_expand:N #1 }
29854 }
29855 \cs_new:Npn \_text_expand_replace:n #1 { \_text_expand_loop:w #1 }

```

Finally, expand any macros which can be: this then loops back around to deal with what they produce. The only issue is if the token is `\exp_not:n`, as that must apply to the following balanced text. There might be an `\exp_after:wN` there, so we check for it.

```

29856 \cs_new:Npn \_text_expand_cs_expand:N #1
29857 {
29858     \_text_if_expandable:NTF #1
29859     {
29860         \token_if_eq_meaning:NNTF #1 \exp_not:n
29861         { \_text_expand_noexpand:w }
29862         { \exp_after:wN \_text_expand_loop:w #1 }
29863     }
29864     {
29865         \_text_expand_store:n {#1}
29866         \_text_expand_loop:w
29867     }
29868 }
29869 \cs_new:Npn \_text_expand_noexpand:w #1#
29870 { \_text_expand_noexpand:nn {#1} }
29871 \cs_new:Npn \_text_expand_noexpand:nn #1#2
29872 {
29873     #1 \_text_expand_store:n #1 {#2}
29874     \_text_expand_loop:w
29875 }

```

(End definition for `\text_expand:n` and others. This function is documented on page 255.)

`\text_declare_expand_equivalent:Nn` Create equivalents to allow replacement.

```

\text_declare_expand_equivalent:cn 29876 \cs_new_protected:Npn \text_declare_expand_equivalent:Nn #1#2
29877 {
29878     \tl_clear_new:c { l\_text_expand\_token_to_str:N #1\_tl }

```

```

29879 \tl_set:cn { l__text_expand_ \token_to_str:N #1 _tl } {#2}
29880 }
29881 \cs_generate_variant:Nn \text_declare_expand_equivalent:Nn { c }

```

(End definition for `\text_declare_expand_equivalent:Nn`. This function is documented on page 255.)

```

29882 </initex | package>

```

47 l3text-case implementation

```

29883 (*initex | package)

```

```

29884 <@@=text>

```

47.1 Case changing

`\l_text_titlecase_check_letter_bool` Needed to determine the route used in titlecasing.

```

29885 \bool_new:N \l_text_titlecase_check_letter_bool
29886 \bool_set_true:N \l_text_titlecase_check_letter_bool

```

(End definition for `\l_text_titlecase_check_letter_bool`. This variable is documented on page 258.)

`\text_lowercase:n` `\text_uppercase:n` `\text_titlecase:n` The user level functions here are all wrappers around the internal functions for case changing.

```

\text_titlecase:n
\text_titlecase_first:n
\text_lowercase:nn
\text_uppercase:nn
\text_titlecase:nn
\text_titlecase_first:nn
29887 \cs_new:Npn \text_lowercase:n #1
29888 { \__text_change_case:nnn { lower } { } {#1} }
29889 \cs_new:Npn \text_uppercase:n #1
29890 { \__text_change_case:nnn { upper } { } {#1} }
29891 \cs_new:Npn \text_titlecase:n #1
29892 { \__text_change_case:nnn { title } { } {#1} }
29893 \cs_new:Npn \text_titlecase_first:n #1
29894 { \__text_change_case:nnn { titleonly } { } {#1} }
29895 \cs_new:Npn \text_lowercase:nn #1#2
29896 { \__text_change_case:nnn { lower } {#1} {#2} }
29897 \cs_new:Npn \text_uppercase:nn #1#2
29898 { \__text_change_case:nnn { upper } {#1} {#2} }
29899 \cs_new:Npn \text_titlecase:nn #1#2
29900 { \__text_change_case:nnn { title } {#1} {#2} }
29901 \cs_new:Npn \text_titlecase_first:nn #1#2
29902 { \__text_change_case:nnn { titleonly } {#1} {#2} }

```

(End definition for `\text_lowercase:n` and others. These functions are documented on page 257.)

```

\__text_change_case:nnn
\__text_change_case_aux:nnn
\__text_change_case_store:n
\__text_change_case_store:o
\__text_change_case_store:V
\__text_change_case_store:v
\__text_change_case_store:e
\__text_change_case_store:nw
\__text_change_case_result:n
\__text_change_case_end:w
\__text_change_case_loop:nnw
\__text_change_case_break:w
\__text_change_case_group_lower:nnn
\__text_change_case_group_upper:nnn
\__text_change_case_group_title:nnn
\__text_change_case_group_titleonly:nnn
\__text_change_case_space:nnw
\__text_change_case_N_type:nnN
\__text_change_case_N_type_aux:nnN
\__text_change_case_N_type:nnnN
\__text_change_case_math_search:nnNNN
\__text_change_case_math_loop:nnNw

```

As for the expansion code, the business end of case changing is the handling of N-type tokens. First, we expand the input fully (so the loops here don't need to worry about awkward look-aheads and the like). Then we split into the different paths.

The code here needs to be f-type expandable to deal with the situation where case changing is applied in running text. There, we might have case changing as a document command and the text containing other non-expandable document commands.

```

\cs_set_eq:NN \MakeLowercase \text_lowercase
...
\MakeLowercase{\enquote*{A} text}

```

If we use an e-type expansion and wrap each token in `\exp_not:n`, that would explode: the document command grabs `\exp_not:n` as an argument, and things go badly wrong. So we have to wrap the entire result in exactly one `\exp_not:n`, or rather in the kernel version.

```

29903 \cs_new:Npn \__text_change_case:nnn #1#2#3
29904 {
29905     \__kernel_exp_not:w \exp_after:wN
29906     {
29907         \exp:w
29908         \exp_args:Ne \__text_change_case_aux:nnn
29909         { \text_expand:n {#3} }
29910         {#1} {#2}
29911     }
29912 }
29913 \cs_new:Npn \__text_change_case_aux:nnn #1#2#3
29914 {
29915     \group_align_safe_begin:
29916     \__text_change_case_loop:nnw {#2} {#3} #1
29917     \q__text_recursion_tail \q__text_recursion_stop
29918     \__text_change_case_result:n { }
29919 }

```

As for expansion, collect up the tokens for future use.

```

29920 \cs_new:Npn \__text_change_case_store:n #1
29921 { \__text_change_case_store:nw {#1} }
29922 \cs_generate_variant:Nn \__text_change_case_store:n { o , e , V , v }
29923 \cs_new:Npn \__text_change_case_store:nw #1#2 \__text_change_case_result:n #3
29924 { #2 \__text_change_case_result:n { #3 #1 } }
29925 \cs_new:Npn \__text_change_case_end:w #1 \__text_change_case_result:n #2
29926 {
29927     \group_align_safe_end:
29928     \exp_end:
29929     #2
29930 }

```

The main loop is the standard `tl` action type.

```

29931 \cs_new:Npn \__text_change_case_loop:nnw #1#2#3 \q__text_recursion_stop
29932 {
29933     \tl_if_head_is_N_type:nTF {#3}
29934     { \__text_change_case_N_type:nnN }
29935     {
29936         \tl_if_head_is_group:nTF {#3}
29937         { \use:c { __text_change_case_group_ #1 :nnn } }
29938         { \__text_change_case_space:nnw }
29939     }
29940     {#1} {#2} #3 \q__text_recursion_stop
29941 }
29942 \cs_new:Npn \__text_change_case_break:w #1 \q__text_recursion_tail \q__text_recursion_stop
29943 {
29944     \__text_change_case_store:n {#1}
29945     \__text_change_case_end:w
29946 }

```

For a group, we *could* worry about whether this contains a character or not. However, that would make life very complex for little gain: exactly what a first character is is

rather weakly-defined anyway. So if there is a group, we simply assume that a character has been seen, and for title case we switch to the “rest of the tokens” situation. To avoid having too much testing, we use a two-step process here to allow the titlecase functions to be separate.

```

29947 \cs_new:Npn \__text_change_case_group_lower:nnn #1#2#3
29948 {
29949   \__text_change_case_store:o
29950   {
29951     \exp_after:wN
29952     {
29953       \exp:w
29954       \__text_change_case_aux:nnn {#3} {#1} {#2}
29955     }
29956   }
29957   \__text_change_case_loop:nnw {#1} {#2}
29958 }
29959 \cs_new_eq:NN \__text_change_case_group_upper:nnn
29960   \__text_change_case_group_lower:nnn
29961 \cs_new:Npn \__text_change_case_group_title:nnn #1#2#3
29962 {
29963   \__text_change_case_store:o
29964   {
29965     \exp_after:wN
29966     {
29967       \exp:w
29968       \__text_change_case_aux:nnn {#3} {#1} {#2}
29969     }
29970   }
29971   \__text_change_case_loop:nnw { lower } {#2}
29972 }
29973 \cs_new:Npn \__text_change_case_group_titleonly:nnn #1#2#3
29974 {
29975   \__text_change_case_store:o
29976   {
29977     \exp_after:wN
29978     {
29979       \exp:w
29980       \__text_change_case_aux:nnn {#3} {#1} {#2}
29981     }
29982   }
29983   \__text_change_case_break:w
29984 }
29985 \use:x
29986 {
29987   \cs_new:Npn \exp_not:N \__text_change_case_space:nnw ##1##2 \c_space_tl
29988 }
29989 {
29990   \__text_change_case_store:n { ~ }
29991   \__text_change_case_loop:nnw {#1} {#2}
29992 }

```

The first step of handling N-type tokens is to filter out the end-of-loop. That has to be done separately from the first real step as otherwise we pick up the wrong delimiter. The loop here is the same as the `expand` one, just passing the additional data long. If no

close-math token is found then the final clean-up is forced (i.e. there is no assumption of “well-behaved” input in terms of math mode).

```

29993 \cs_new:Npn \__text_change_case_N_type:nnN #1#2#3
29994 {
29995   \__text_if_recursion_tail_stop_do:Nn #3
29996   { \__text_change_case_end:w }
29997   \__text_change_case_N_type_aux:nnN {#1} {#2} #3
29998 }
29999 \cs_new:Npn \__text_change_case_N_type_aux:nnN #1#2#3
30000 {
30001   \exp_args:NV \__text_change_case_N_type:nnnN
30002   \l_text_math_delims_tl {#1} {#2} #3
30003 }
30004 \cs_new:Npn \__text_change_case_N_type:nnnN #1#2#3#4
30005 {
30006   \__text_change_case_math_search:nnNNN {#2} {#3} #4 #1
30007   \q__text_recursion_tail \q__text_recursion_tail
30008   \q__text_recursion_stop
30009 }
30010 \cs_new:Npn \__text_change_case_math_search:nnNNN #1#2#3#4#5
30011 {
30012   \__text_if_recursion_tail_stop_do:Nn #4
30013   { \__text_change_case_cs_check:nnN {#1} {#2} #3 }
30014   \token_if_eq_meaning:NNTF #3 #4
30015   {
30016     \__text_use_i_delimit_by_q_recursion_stop:nw
30017     {
30018       \__text_change_case_store:n {#3}
30019       \__text_change_case_math_loop:nnNw {#1} {#2} #5
30020     }
30021   }
30022   { \__text_change_case_math_search:nnNNN {#1} {#2} #3 }
30023 }
30024 \cs_new:Npn \__text_change_case_math_loop:nnNw #1#2#3#4 \q__text_recursion_stop
30025 {
30026   \tl_if_head_is_N_type:nTF {#4}
30027   { \__text_change_case_math_N_type:nnNN }
30028   {
30029     \tl_if_head_is_group:nTF {#4}
30030     { \__text_change_case_math_group:nnNn }
30031     { \__text_change_case_math_space:nnNw }
30032   }
30033   {#1} {#2} #3 #4 \q__text_recursion_stop
30034 }
30035 \cs_new:Npn \__text_change_case_math_N_type:nnNN #1#2#3#4
30036 {
30037   \__text_if_recursion_tail_stop_do:Nn #4
30038   { \__text_change_case_end:w }
30039   \__text_change_case_store:n {#4}
30040   \token_if_eq_meaning:NNTF #4 #3
30041   { \__text_change_case_loop:nnw {#1} {#2} }
30042   { \__text_change_case_math_loop:nnNw {#1} {#2} #3 }
30043 }
30044 \cs_new:Npn \__text_change_case_math_group:nnNn #1#2#3#4

```

```

30045 {
30046   \_text_change_case_store:n { {#4} }
30047   \_text_change_case_math_loop:nnNw {#1} {#2} #3
30048 }
30049 \use:x
30050 {
30051   \cs_new:Npn \exp_not:N \_text_change_case_math_space:nnNw ##1##2##3
30052     \c_space_tl
30053 }
30054 {
30055   \_text_change_case_store:n { ~ }
30056   \_text_change_case_math_loop:nnNw {#1} {#2} #3
30057 }

```

Once potential math-mode cases are filtered out the next stage is to test if the token grabbed is a control sequence: the two routes the code may take are then very different.

```

30058 \cs_new:Npn \_text_change_case_cs_check:nnN #1#2#3
30059 {
30060   \token_if_cs:NTF #3
30061   { \_text_change_case_exclude:nnN }
30062   { \use:c { \_text_change_case_char_ #1 :nnN } }
30063   {#1} {#2} #3
30064 }

```

To deal with a control sequence there is first a need to test if it is on the list which indicate that case changing should be skipped. That's done using a loop as for the other special cases. If a hit is found then the argument is grabbed and passed through as-is.

```

30065 \cs_new:Npn \_text_change_case_exclude:nnN #1#2#3
30066 {
30067   \exp_args:Ne \_text_change_case_exclude:nnnN
30068   {
30069     \exp_not:V \l_text_math_arg_tl
30070     \exp_not:V \l_text_case_exclude_arg_tl
30071   }
30072   {#1} {#2} #3
30073 }
30074 \cs_new:Npn \_text_change_case_exclude:nnnN #1#2#3#4
30075 {
30076   \_text_change_case_exclude:nnNN {#2} {#3} #4 #1
30077   \q__text_recursion_tail \q__text_recursion_stop
30078 }
30079 \cs_new:Npn \_text_change_case_exclude:nnNN #1#2#3#4
30080 {
30081   \_text_if_recursion_tail_stop_do:Nn #4
30082   { \use:c { \_text_change_case_letterlike_ #1 :nnN } {#1} {#2} #3 }
30083   \cs_if_eq:NNTF #3 #4
30084   {
30085     \_text_use_i_delimit_by_q_recursion_stop:nw
30086     { \_text_change_case_exclude:nnNn {#1} {#2} #3 }
30087   }
30088   { \_text_change_case_exclude:nnNN {#1} {#2} #3 }
30089 }
30090 \cs_new:Npn \_text_change_case_exclude:nnNn #1#2#3#4
30091 {
30092   \_text_change_case_store:n { #3 {#4} }

```

```

30093   \_text_change_case_loop:nnw {#1} {#2}
30094 }

```

Letter-like commands may still be present: they are set up using a simple lookup approach, so can easily be handled with no loop. If there is no hit, we are at the end of the process: we loop around. Letter-like chars are all available only in upper- and lowercase, so titlecasing maps to the uppercase version.

```

30095 \cs_new:Npn \_text_change_case_letterlike_lower:nnN #1#2#3
30096 { \_text_change_case_letterlike:nnnnN {#1} {#1} {#1} {#2} #3 }
30097 \cs_new_eq:NN \_text_change_case_letterlike_upper:nnN
30098   \_text_change_case_letterlike_lower:nnN
30099 \cs_new:Npn \_text_change_case_letterlike_title:nnN #1#2#3
30100 { \_text_change_case_letterlike:nnnnN { upper } { lower } {#1} {#2} #3 }
30101 \cs_new:Npn \_text_change_case_letterlike_titleonly:nnN #1#2#3
30102 { \_text_change_case_letterlike:nnnnN { upper } { end } {#1} {#2} #3 }
30103 \cs_new:Npn \_text_change_case_letterlike:nnnnN #1#2#3#4#5
30104 {
30105   \cs_if_exist:cTF { c__text_ #1 case_ \token_to_str:N #5 _t1 }
30106   {
30107     \_text_change_case_store:v
30108     { c__text_ #1 case_ \token_to_str:N #5 _t1 }
30109     \use:c { \_text_change_case_char_next_ #2 :nn } {#2} {#4}
30110   }
30111   {
30112     \_text_change_case_store:n {#5}
30113     \cs_if_exist:cTF
30114     {
30115       c__text_
30116       \str_if_eq:nnTF {#1} { lower } { upper } { lower }
30117       case_ \token_to_str:N #5 _t1
30118     }
30119     { \use:c { \_text_change_case_char_next_ #2 :nn } {#2} {#4} }
30120     { \_text_change_case_loop:nnw {#3} {#4} }
30121   }
30122 }

```

For upper- and lowercase changes, once we get to this stage there are only a couple of questions remaining: is there a language-specific mapping and is there the special case of a terminal sigma. If not, then we pass to a simple character mapping.

```

30123 \cs_new:Npn \_text_change_case_char_lower:nnN #1#2#3
30124 {
30125   \exp_not:N \cs_if_exist_use:cF { \_text_change_case_lower_ #2 :nnnN }
30126   {
30127     \bool_lazy_or:nnTF
30128     { \sys_if_engine luatex_p: }
30129     { \sys_if_engine xetex_p: }
30130     { \exp_not:N \_text_change_case_lower_sigma:nnnN }
30131     { \exp_not:N \_text_change_case_char:nnnN }
30132   }
30133   {#1} {#1} {#2} #3
30134 }
30135 \cs_new:Npn \_text_change_case_char_upper:nnN #1#2#3
30136 {
30137   \cs_if_exist_use:cF { \_text_change_case_upper_ #2 :nnnN }

```

```

30138     { \_text_change_case_char:nnnN }
30139     {#1} {#1} {#2} #3
30140   }

```

If the current character is an uppercase sigma, the a check is made on the next item in the input. If it is N-type and not a control sequence then there is a look-ahead phase: the logic here is simply based on letters. The one exception is Dutch: see below.

```

30141 \bool_lazy_or:nnT
30142 { \sys_if_engine luatex_p: }
30143 { \sys_if_engine xetex_p: }
30144 {
30145   \cs_new:Npn \_text_change_case_lower_sigma:nnnN #1#2#3#4
30146   {
30147     \int_compare:nNnTF { '#4 } = { "03A3 }
30148     { \_text_change_case_lower_sigma:nnNw {#2} {#3} #4 }
30149     { \_text_change_case_char:nnnN {#1} {#2} {#3} #4 }
30150   }
30151   \cs_new:Npn \_text_change_case_lower_sigma:nnNw #1#2#3#4 \q_text_recursion_stop
30152   {
30153     \tl_if_head_is_N_type:nTF {#4}
30154     { \_text_change_case_lower_sigma:NnnN #3 }
30155     {
30156       \_text_change_case_store:e
30157       { \char_generate:nn { "03C2 } { \_text_char_catcode:N #3 } }
30158       \_text_change_case_loop:nnw
30159     }
30160     {#1} {#2} #4 \q_text_recursion_stop
30161   }
30162   \cs_new:Npn \_text_change_case_lower_sigma:NnnN #1#2#3#4
30163   {
30164     \_text_change_case_store:e
30165     {
30166       \token_if_letter:NnTF #4
30167       { \char_generate:nn { "03C3 } { \_text_char_catcode:N #1 } }
30168       { \char_generate:nn { "03C2 } { \_text_char_catcode:N #1 } }
30169     }
30170     \_text_change_case_loop:nnw {#2} {#3} #4
30171   }
30172 }

```

For titlecasing, we need to fully expand the new character to see if it is a letter (or active) But that means looking ahead in the 8-bit case, so we have to grab the required tokens up-front. Life is a lot easier for Unicode T_EX's, where we just have one token to worry about. The one wrinkle here is that for look-ahead we'd get into trouble: luckily, only Dutch has that issue.

```

30173 \cs_new:Npx \_text_change_case_char_title:nnN #1#2#3
30174 {
30175   \exp_not:N \bool_if:NnTF \l_text_titlecase_check_letter_bool
30176   {
30177     \bool_lazy_or:nnTF
30178     { \sys_if_engine luatex_p: }
30179     { \sys_if_engine xetex_p: }
30180     { \exp_not:N \token_if_letter:NnTF #3 }
30181     {

```



```

30182         \exp_not:N \bool_lazy_or:nnTF
30183         { \exp_not:N \token_if_letter_p:N #3 }
30184         { \exp_not:N \token_if_active_p:N #3 }
30185     }
30186     { \exp_not:N \use:c { __text_change_case_char_ #1 :nN } }
30187     { \exp_not:N \__text_change_case_char_title:nnnN { title } {#1} }
30188 }
30189 { \exp_not:N \use:c { __text_change_case_char_ #1 :nN } }
30190 {#2} #3
30191 }
30192 \cs_new_eq:NN \__text_change_case_char_titleonly:nnN
30193 \__text_change_case_char_title:nnN
30194 \cs_new:Npn \__text_change_case_char_title:nN #1#2
30195 { \__text_change_case_char_title:nnnN { title } { lower } {#1} #2 }
30196 \cs_new:Npn \__text_change_case_char_titleonly:nN #1#2
30197 { \__text_change_case_char_title:nnnN { title } { end } {#1} #2 }
30198 \cs_new:Npn \__text_change_case_char_title:nnnN #1#2#3#4
30199 {
30200     \cs_if_exist_use:cF { __text_change_case_title_ #3 :nnnN }
30201     {
30202         \cs_if_exist_use:cF { __text_change_case_upper_ #3 :nnnN }
30203         { \__text_change_case_char:nnnN }
30204     }
30205     {#1} {#2} {#3} #4
30206 }

```

For Unicode engines we can handle all characters directly. However, for the 8-bit engines the aim is to deal with (a subset of) Unicode (UTF-8) input. They deal with that by making the upper half of the range active, so we look for that and if found work out how many UTF-8 octets there are to deal with. Those can then be grabbed to reconstruct the full Unicode character, which is then used in a lookup. (As will become obvious below, there is no intention here of covering all of Unicode.)

```

30207 \cs_new:Npn \__text_change_case_char:nnnN #1#2#3#4
30208 {
30209     \token_if_active:NTF #4
30210     { \__text_change_case_store:n {#4} }
30211     {
30212         \__text_change_case_store:e
30213         { \use:c { char_ #1 case :N } #4 }
30214     }
30215     \use:c { __text_change_case_char_next_ #2 :nn } {#2} {#3}
30216 }
30217 \bool_lazy_or:nnF
30218 { \sys_if_engine luatex_p: }
30219 { \sys_if_engine xetex_p: }
30220 {
30221     \cs_new_eq:NN \__text_change_case_char_aux:nnnN
30222     \__text_change_case_char:nnnN
30223     \cs_gset:Npn \__text_change_case_char:nnnN #1#2#3#4
30224     {
30225         \int_compare:nNnTF { '#4 } > { "80 }
30226         {
30227             \int_compare:nNnTF { '#4 } < { "E0 }
30228             { \__text_change_case_char_UTFviii:nnnNN }

```

```

30229         {
30230         \int_compare:nNnTF { '#4 } < { "F0 }
30231         { \__text_change_case_char_UTFviii:nnnNNN }
30232         { \__text_change_case_char_UTFviii:nnnNNNN }
30233     }
30234     {#1} {#2} {#3} #4
30235 }
30236 { \__text_change_case_char_aux:nnnN {#1} {#2} {#3} #4 }
30237 }
30238 \cs_new:Npn \__text_change_case_char_UTFviii:nnnNN #1#2#3#4#5
30239 { \__text_change_case_char_UTFviii:nnnn {#1} {#2} {#3} {#4#5} }
30240 \cs_new:Npn \__text_change_case_char_UTFviii:nnnNNN #1#2#3#4#5#6
30241 { \__text_change_case_char_UTFviii:nnnn {#1} {#2} {#3} {#4#5#6} }
30242 \cs_new:Npn \__text_change_case_char_UTFviii:nnnNNNN #1#2#3#4#5#6#7
30243 { \__text_change_case_char_UTFviii:nnnn {#1} {#2} {#3} {#4#5#6#7} }
30244 \cs_new:Npn \__text_change_case_char_UTFviii:nnnn #1#2#3#4
30245 {
30246     \cs_if_exist:cTF { c__text_ #1 case_ \tl_to_str:n {#4} _tl }
30247     {
30248         \__text_change_case_store:v
30249         { c__text_ #1 case_ \tl_to_str:n {#4} _tl }
30250     }
30251     { \__text_change_case_store:n {#4} }
30252     \use:c { __text_change_case_char_next_ #2 :nn } {#2} {#3}
30253 }
30254 }
30255 \cs_new:Npn \__text_change_case_char_next_lower:nn #1#2
30256 { \__text_change_case_loop:nnw {#1} {#2} }
30257 \cs_new_eq:NN \__text_change_case_char_next_upper:nn
30258 \__text_change_case_char_next_lower:nn
30259 \cs_new_eq:NN \__text_change_case_char_next_title:nn
30260 \__text_change_case_char_next_lower:nn
30261 \cs_new_eq:NN \__text_change_case_char_next_titleonly:nn
30262 \__text_change_case_char_next_lower:nn
30263 \cs_new:Npn \__text_change_case_char_next_end:nn #1#2
30264 { \__text_change_case_break:w }

```

(End definition for __text_change_case:nnn and others.)

__text_change_case_upper_de-alt:nnnN
__text_change_case_upper_de-alt:nnnNN

A simple alternative version for German.

```

30265 \bool_lazy_or:nnTF
30266 { \sys_if_engine luatex_p: }
30267 { \sys_if_engine xetex_p: }
30268 {
30269     \cs_new:cpn { __text_change_case_upper_de-alt:nnnN } #1#2#3#4
30270     {
30271         \int_compare:nNnTF { '#4 } = { "00DF }
30272         {
30273             \__text_change_case_store:e
30274             { \char_generate:nn { "1E9E } { \__text_char_catcode:N #4 } }
30275             \use:c { __text_change_case_char_next_ #2 :nn }
30276             {#2} {#3}
30277         }
30278         { \__text_change_case_char:nnnN {#1} {#2} {#3} #4 }

```

```

30279     }
30280   }
30281   {
30282     \cs_new:cpx { __text_change_case_upper_de-alt:nnnN } #1#2#3#4
30283     {
30284       \exp_not:N \int_compare:nNnTF { '#4 } = { "00C3 }
30285       {
30286         \exp_not:c { __text_change_case_upper_de-alt:nnnNN }
30287         {#1} {#2} {#3} #4
30288       }
30289       { \exp_not:N \__text_change_case_char:nnnN {#1} {#2} {#3} #4 }
30290     }
30291     \cs_new:cpn { __text_change_case_upper_de-alt:nnnNN } #1#2#3#4#5
30292     {
30293       \int_compare:nNnTF { '#5 } = { "009F }
30294       {
30295         \__text_change_case_store:V \c__text_grosses_Eszett_tl
30296         \use:c { __text_change_case_char_next_ #2 :nn } {#2} {#3}
30297       }
30298       { \__text_change_case_char:nnnN {#1} {#2} {#3} #4#5 }
30299     }
30300   }

```

(End definition for __text_change_case_upper_de-alt:nnnN and __text_change_case_upper_de-alt:nnnNN.)

```

\__text_change_case_upper_el:nnnN
\__text_change_case_upper_el:nnnn
\__text_change_case_upper_el_aux:nnnN
\__text_change_case_upper_el_loop:nnw
\__text_change_case_upper_el:nnN
\__text_change_case_if_greek:nTF

```

For Greek uppercasing, we need to know if characters *in the Greek range* have accents. That means doing a NFD conversion first, then starting a search. As described by the Unicode CLDR, Greek accents need to be found *after* any U+0308 (diaeresis) and are done in two groups to allow for the canonical ordering.

```

30301 \bool_lazy_or:nnT
30302 { \sys_if_engine_luatex_p: }
30303 { \sys_if_engine_xetex_p: }
30304 {
30305   \cs_new:Npn \__text_change_case_upper_el:nnnN #1#2#3#4
30306   {
30307     \__text_change_case_if_greek:nTF { '#4 }
30308     {
30309       \exp_args:Ne \__text_change_case_upper_el:nnnn
30310       { \char_to_nfd:N #4 } {#1} {#2} {#3}
30311     }
30312     { \__text_change_case_char:nnnN {#1} {#2} {#3} #4 }
30313   }
30314   \cs_new:Npn \__text_change_case_upper_el:nnnn #1#2#3#4
30315   { \__text_change_case_upper_el_aux:nnnN {#2} {#3} {#4} #1 }
30316   \cs_new:Npn \__text_change_case_upper_el_aux:nnnN #1#2#3#4
30317   {
30318     \__text_change_case_store:e { \use:c { char_ #1 case:N } #4 }
30319     \__text_change_case_upper_el_loop:nnw {#2} {#3}
30320   }
30321   \cs_new:Npn \__text_change_case_upper_el_loop:nnw
30322   #1#2#3 \q__text_recursion_stop
30323   {
30324     \tl_if_head_is_N_type:nTF {#3}
30325     { \__text_change_case_upper_el:nnN }

```

```

30326         { \__text_change_case_loop:nnw }
30327         {#1} {#2} #3 \q__text_recursion_stop
30328     }

```

In addition to the Greek accents, we list three cases here where an accent outside the Greek range has a nfd that would make it equivalent. That includes U+0344, which has to insert U+0308.

```

30329     \cs_new:Npn \__text_change_case_upper_el:nnN #1#2#3
30330     {
30331         \token_if_cs:NTF #3
30332         { \__text_change_case_loop:nnw {#1} {#2} #3 }
30333         {
30334             \int_compare:nNnTF { '#3 } = { "0308 }
30335             {
30336                 \__text_change_case_store:n {#3}
30337                 \__text_change_case_upper_el_loop:nnw {#1} {#2}
30338             }
30339             {
30340                 \bool_lazy_any:nTF
30341                 {
30342                     { \int_compare_p:nNn { '#3 } = { "0300 } }
30343                     { \int_compare_p:nNn { '#3 } = { "0301 } }
30344                     { \int_compare_p:nNn { '#3 } = { "0304 } }
30345                     { \int_compare_p:nNn { '#3 } = { "0306 } }
30346                     { \int_compare_p:nNn { '#3 } = { "0308 } }
30347                     { \int_compare_p:nNn { '#3 } = { "0313 } }
30348                     { \int_compare_p:nNn { '#3 } = { "0314 } }
30349                     { \int_compare_p:nNn { '#3 } = { "0342 } }
30350                     { \int_compare_p:nNn { '#3 } = { "0340 } }
30351                     { \int_compare_p:nNn { '#3 } = { "0341 } }
30352                     { \int_compare_p:nNn { '#3 } = { "0343 } }
30353                 }
30354                 { \__text_change_case_upper_el_loop:nnw {#1} {#2} }
30355                 {
30356                     \int_compare:nNnTF { '#3 } = { "0344 }
30357                     {
30358                         \__text_change_case_store:e
30359                         {
30360                             \char_generate:nn { "0308 }
30361                             { \__text_char_catcode:N #3 }
30362                         }
30363                         \__text_change_case_upper_el_loop:nnw {#1} {#2}
30364                     }
30365                     {
30366                         \int_compare:nNnTF { '#3 } = { "0345 }
30367                         { \__text_change_case_loop:nnw {#1} {#2} }
30368                         { \__text_change_case_loop:nnw {#1} {#2} #3 }
30369                     }
30370                 }
30371             }
30372         }
30373     }
30374     \prg_new_conditional:Npnn \__text_change_case_if_greek:n #1 { TF }
30375     {

```

```

30376 \if_int_compare:w #1 < "0370 \exp_stop_f:
30377 \prg_return_false:
30378 \else:
30379 \if_int_compare:w #1 > "03FF \exp_stop_f:
30380 \if_int_compare:w #1 < "1F00 \exp_stop_f:
30381 \prg_return_false:
30382 \else:
30383 \if_int_compare:w #1 > "1FFF \exp_stop_f:
30384 \prg_return_false:
30385 \else:
30386 \prg_return_true:
30387 \fi:
30388 \fi:
30389 \else:
30390 \prg_return_true:
30391 \fi:
30392 \fi:
30393 }
30394 }

```

(End definition for `_text_change_case_upper_el:nnnN` and others.)

`_text_change_case_title_el:nnnN` Titlecasing retains accents, but to prevent the uppercasing code from kicking in, there has to be an explicit function here.

```

30395 \bool_lazy_or:nnT
30396 { \sys_if_engine luatex_p: }
30397 { \sys_if_engine xetex_p: }
30398 {
30399 \cs_new:Npn \_text_change_case_title_el:nnnN #1#2#3#4
30400 { \_text_change_case_char:nnnN {#1} {#2} {#3} #4 }
30401 }

```

(End definition for `_text_change_case_title_el:nnnN`.)

`_text_change_cases_lower_lt:nnnN` For Lithuanian, the issue to be dealt with is dots over lower case letters: these should be present if there is another accent. The first step is a simple match attempt: look for the three uppercase accented letters which should gain a dot-above char in their lowercase form.

```

\_text_change_cases_lower_lt_auxi:nnnN
\_text_change_cases_lower_lt_auxii:nnnN
\_text_change_case_lower_lt:nnw
\_text_change_case_lower_lt:nnN
30402 \bool_lazy_or:nnT
30403 { \sys_if_engine luatex_p: }
30404 { \sys_if_engine xetex_p: }
30405 {
30406 \cs_new:Npn \_text_change_case_lower_lt:nnnN #1#2#3#4
30407 {
30408 \exp_args:Ne \_text_change_case_lower_lt_auxi:nnnN
30409 {
30410 \int_case:nn { '#4 }
30411 {
30412 { "00CC } { "0300 }
30413 { "00CD } { "0301 }
30414 { "0128 } { "0303 }
30415 }
30416 }
30417 {#2} {#3} #4
30418 }

```

If there was a hit, output the result with the dot-above and move on. Otherwise, look for one of the three letters that can take a combining accent: I, J and I-ogonek.

```

30419 \cs_new:Npn \__text_change_case_lower_lt_auxi:nnnN #1#2#3#4
30420 {
30421   \tl_if_blank:nTF {#1}
30422   {
30423     \exp_args:Ne \__text_change_case_lower_lt_auxii:nnnN
30424     {
30425       \int_case:nn { '#4 }
30426       {
30427         { "0049 } { "0069 }
30428         { "004A } { "006A }
30429         { "012E } { "012F }
30430       }
30431     }
30432     {#2} {#3} #4
30433   }
30434   {
30435     \__text_change_case_store:e
30436     {
30437       \char_generate:nn { "0069 } { \__text_char_catcode:N #4 }
30438       \char_generate:nn { "0307 } { \__text_char_catcode:N #4 }
30439       \char_generate:nn {#1} { \__text_char_catcode:N #4 }
30440     }
30441     \__text_change_case_loop:nnw {#2} {#3}
30442   }
30443 }

```

Again, branch depending on a hit. If there is one, we output the character then need to look for a combining accent: as usual, we need to be aware of the loop situation.

```

30444 \cs_new:Npn \__text_change_case_lower_lt_auxii:nnnN #1#2#3#4
30445 {
30446   \tl_if_blank:nTF {#1}
30447   { \__text_change_case_lower_sigma:nnnN {#2} {#2} {#3} #4 }
30448   {
30449     \__text_change_case_store:e
30450     { \char_generate:nn {#1} { \__text_char_catcode:N #4 } }
30451     \__text_change_case_lower_lt:nnw {#2} {#3}
30452   }
30453 }
30454 \cs_new:Npn \__text_change_case_lower_lt:nnw #1#2#3 \q__text_recursion_stop
30455 {
30456   \tl_if_head_is_N_type:nTF {#3}
30457   { \__text_change_case_lower_lt:nnN }
30458   { \__text_change_case_loop:nnw }
30459   {#1} {#2} #3 \q__text_recursion_stop
30460 }
30461 \cs_new:Npn \__text_change_case_lower_lt:nnN #1#2#3
30462 {
30463   \bool_lazy_and:nnT
30464   { ! \token_if_cs_p:N #3 }
30465   {
30466     \bool_lazy_any_p:n
30467     {

```

```

30468         { \int_compare_p:nNn { '#3 } = { "0300 } }
30469         { \int_compare_p:nNn { '#3 } = { "0301 } }
30470         { \int_compare_p:nNn { '#3 } = { "0303 } }
30471     }
30472 }
30473 {
30474     \__text_change_case_store:e
30475     { \char_generate:nn { "0307 } { \__text_char_catcode:N #3 } }
30476 }
30477 \__text_change_case_loop:nnw {#1} {#2} #3
30478 }
30479 }

```

(End definition for __text_change_cases_lower_lt:nnnN and others.)

_text_change_cases_upper_lt:nnnN The uppercasing version: first find i/j/i-ogonek, then look for the combining char: drop it if present.

```

\_text_change_cases_upper_lt:nnnN
\_text_change_cases_upper_lt_aux:nnnN
\_text_change_case_upper_lt:nnw
\_text_change_case_upper_lt:nnN
30480 \bool_lazy_or:nnT
30481 { \sys_if_engine luatex_p: }
30482 { \sys_if_engine xetex_p: }
30483 {
30484     \cs_new:Npn \__text_change_case_upper_lt:nnnN #1#2#3#4
30485     {
30486         \exp_args:Ne \__text_change_case_upper_lt_aux:nnnN
30487         {
30488             \int_case:nn { '#4 }
30489             {
30490                 { "0069 } { "0049 }
30491                 { "006A } { "004A }
30492                 { "012F } { "012E }
30493             }
30494         }
30495         {#2} {#3} #4
30496     }
30497     \cs_new:Npn \__text_change_case_upper_lt_aux:nnnN #1#2#3#4
30498     {
30499         \tl_if_blank:nTF {#1}
30500         { \__text_change_case_char:nnnN { upper } {#2} {#3} #4 }
30501         {
30502             \__text_change_case_store:e
30503             { \char_generate:nn {#1} { \__text_char_catcode:N #4 } }
30504             \__text_change_case_upper_lt:nnw {#2} {#3}
30505         }
30506     }
30507     \cs_new:Npn \__text_change_case_upper_lt:nnw #1#2#3 \q__text_recursion_stop
30508     {
30509         \tl_if_head_is_N_type:nTF {#3}
30510         { \__text_change_case_upper_lt:nnN }
30511         { \use:c { __text_change_case_char_next_ #1 :nn } }
30512         {#1} {#2} #3 \q__text_recursion_stop
30513     }
30514     \cs_new:Npn \__text_change_case_upper_lt:nnN #1#2#3
30515     {
30516         \bool_lazy_and:nnTF

```

```

30517         { ! \token_if_cs_p:N #3 }
30518         { \int_compare_p:nNn { '#3 } = { "0307 } }
30519         { \use:c { __text_change_case_char_next_ #1 :nn } {#1} {#2} }
30520         { \use:c { __text_change_case_char_next_ #1 :nn } {#1} {#2} #3 }
30521     }
30522 }

```

(End definition for `__text_change_cases_upper_lt:nnnN` and others.)

`__text_change_case_title_nl:nnnN`
`__text_change_case_title_nl:nnw`
`__text_change_case_title_nl:nnN`

For Dutch, there is a single look-ahead test for ij when title casing. If the appropriate letters are found, produce IJ and gobble the j/J.

```

30523 \cs_new:Npn \__text_change_case_title_nl:nnnN #1#2#3#4
30524 {
30525     \bool_lazy_or:nnTF
30526     { \int_compare_p:nNn { '#4 } = { "0049 } }
30527     { \int_compare_p:nNn { '#4 } = { "0069 } }
30528     {
30529         \__text_change_case_store:e
30530         { \char_generate:nn { "0049 } { \__text_char_catcode:N #4 } }
30531         \__text_change_case_title_nl:nnw {#2} {#3}
30532     }
30533     { \__text_change_case_char:nnnN {#1} {#2} {#3} #4 }
30534 }
30535 \cs_new:Npn \__text_change_case_title_nl:nnw #1#2#3 \q__text_recursion_stop
30536 {
30537     \tl_if_head_is_N_type:nnTF {#3}
30538     { \__text_change_case_title_nl:nnN }
30539     { \use:c { __text_change_case_char_next_ #1 :nn } }
30540     {#1} {#2} #3 \q__text_recursion_stop
30541 }
30542 \cs_new:Npn \__text_change_case_title_nl:nnN #1#2#3
30543 {
30544     \bool_lazy_and:nnTF
30545     { ! \token_if_cs_p:N #3 }
30546     {
30547         \bool_lazy_or_p:nn
30548         { \int_compare_p:nNn { '#3 } = { "004A } }
30549         { \int_compare_p:nNn { '#3 } = { "006A } }
30550     }
30551     {
30552         \__text_change_case_store:e
30553         { \char_generate:nn { "004A } { \__text_char_catcode:N #3 } }
30554         \use:c { __text_change_case_char_next_ #1 :nn } {#1} {#2}
30555     }
30556     { \use:c { __text_change_case_char_next_ #1 :nn } {#1} {#2} #3 }
30557 }

```

(End definition for `__text_change_case_title_nl:nnnN`, `__text_change_case_title_nl:nnw`, and `__text_change_case_title_nl:nnN`.)

`__text_change_case_lower_tr:nnnN`
`__text_change_case_lower_tr:nnNw`
`__text_change_case_lower_tr:NnnN`
`__text_change_case_lower_tr:nnnN`

The Turkic languages need special treatment for dotted-i and dotless-i. The lower casing rule can be expressed in terms of searching first for either a dotless-I or a dotted-I. In the latter case the mapping is easy, but in the former there is a second stage search.

```

30558 \bool_lazy_or:nnTF

```



```

30559 { \sys_if_engine luatex_p: }
30560 { \sys_if_engine xetex_p: }
30561 {
30562   \cs_new:Npn \__text_change_case_lower_tr:nnnN #1#2#3#4
30563   {
30564     \int_compare:nNnTF { '#4 } = { "0049 }
30565     { \__text_change_case_lower_tr:nnNw {#1} {#3} #4 }
30566     {
30567       \int_compare:nNnTF { '#4 } = { "0130 }
30568       {
30569         \__text_change_case_store:e
30570         { \char_generate:nn { "0069 } { \__text_char_catcode:N #4 } }
30571         \__text_change_case_loop:nnw {#1} {#3}
30572       }
30573       { \__text_change_case_lower_sigma:nnnN {#1} {#2} {#3} #4 }
30574     }
30575   }

```

After a dotless-I there may be a dot-above character. If there is then a dotted-i should be produced, otherwise output a dotless-i. When the combination is found both the dotless-I and the dot-above char have to be removed from the input.

```

30576   \cs_new:Npn \__text_change_case_lower_tr:nnNw #1#2#3#4 \q_text_recursion_stop
30577   {
30578     \tl_if_head_is_N_type:nTF {#4}
30579     { \__text_change_case_lower_tr:NnnN #3 }
30580     {
30581       \__text_change_case_store:e
30582       { \char_generate:nn { "0131 } { \__text_char_catcode:N #3 } }
30583       \__text_change_case_loop:nnw
30584     }
30585     {#1} {#2} #4 \q_text_recursion_stop
30586   }
30587   \cs_new:Npn \__text_change_case_lower_tr:NnnN #1#2#3#4
30588   {
30589     \bool_lazy_or:nnTF
30590     { \token_if_cs_p:N #4 }
30591     { ! \int_compare_p:nNn { '#4 } = { "0307 } }
30592     {
30593       \__text_change_case_store:e
30594       { \char_generate:nn { "0131 } { \__text_char_catcode:N #1 } }
30595       \__text_change_case_loop:nnw {#2} {#3} #4
30596     }
30597     {
30598       \__text_change_case_store:e
30599       { \char_generate:nn { "0069 } { \__text_char_catcode:N #1 } }
30600       \__text_change_case_loop:nnw {#2} {#3}
30601     }
30602   }
30603 }

```

For 8-bit engines, dot-above is not available so there is a simple test for an upper-case I. Then we can look for the UTF-8 representation of an upper case dotted-I without the combining char. If it's not there, preserve the UTF-8 sequence as-is. With 8bit engines, we cannot completely preserve category codes, so we have to make some assumptions:

output a “normal” i for the dotted case. As the original character here is catcode-13, we have to make a choice about handling of i: generate a “normal” one.

```

30604 {
30605   \cs_new:Npn \__text_change_case_lower_tr:nnnN #1#2#3#4
30606   {
30607     \int_compare:nNnTF { '#4 } = { "0049 }
30608     {
30609       \__text_change_case_store:V \c__text_dotless_i_tl
30610       \__text_change_case_loop:nnw {#1} {#3}
30611     }
30612     {
30613       \int_compare:nNnTF { '#4 } = { "00C4 }
30614       { \__text_change_case_lower_tr:nnnNN {#1} {#2} {#3} #4 }
30615       { \__text_change_case_char:nnnN {#1} {#2} {#3} #4 }
30616     }
30617   }
30618   \cs_new:Npn \__text_change_case_lower_tr:nnnNN #1#2#3#4#5
30619   {
30620     \int_compare:nNnTF { '#5 } = { "00B0 }
30621     {
30622       \__text_change_case_store:e
30623       {
30624         \char_generate:nn { "0069 }
30625         { \char_value_catcode:n { "0069 } }
30626       }
30627       \__text_change_case_loop:nnw {#1} {#3}
30628     }
30629     { \__text_change_case_char:nnnN {#1} {#2} {#3} #4#5 }
30630   }
30631 }

```

(End definition for __text_change_case_lower_tr:nnnN and others.)

__text_change_case_upper_tr:nnnN Uppercasing is easier: just one exception with no context.

```

30632 \cs_new:Npx \__text_change_case_upper_tr:nnnN #1#2#3#4
30633 {
30634   \exp_not:N \int_compare:nNnTF { '#4 } = { "0069 }
30635   {
30636     \bool_lazy_or:nnTF
30637     { \sys_if_engine luatex_p: }
30638     { \sys_if_engine xetex_p: }
30639     {
30640       \exp_not:N \__text_change_case_store:e
30641       {
30642         \exp_not:N \char_generate:nn { "0130 }
30643         { \exp_not:N \__text_char_catcode:N #4 }
30644       }
30645     }
30646     {
30647       \exp_not:N \__text_change_case_store:V
30648       \exp_not:N \c__text_dotted_I_tl
30649     }
30650   }
30651   \exp_not:N \use:c { __text_change_case_char_next_ #2 :nn } {#2} {#3}

```

```

30652     { \exp_not:N \__text_change_case_char:nnnN {#1} {#2} {#3} #4 }
30653   }

```

(End definition for __text_change_case_upper_tr:nnnN.)

```

\__text_change_case_lower_az:nnnN
\__text_change_case_upper_az:nnnN

```

Straight copies.

```

30654 \cs_new_eq:NN \__text_change_case_lower_az:nnnN
30655   \__text_change_case_lower_tr:nnnN
30656 \cs_new_eq:NN \__text_change_case_upper_az:nnnN
30657   \__text_change_case_upper_tr:nnnN

```

(End definition for __text_change_case_lower_az:nnnN and __text_change_case_upper_az:nnnN.)

47.2 Case changing data for 8-bit engines

```

\c__text_dotless_i_tl
\c__text_dotted_I_tl
\c__text_i_ogonek_tl
\c__text_I_ogonek_tl
\c__text_grosses_Eszett_tl

```

For cases where there is an 8-bit option in the T1 font set up, a variant is provided in both cases.

```

30658 \group_begin:
30659   \bool_lazy_or:nnF
30660     { \sys_if_engine_luatex_p: }
30661     { \sys_if_engine_xetex_p: }
30662     {
30663       \cs_set_protected:Npn \__text_tmp:w #1#2
30664       {
30665         \group_begin:
30666           \cs_set_protected:Npn \__text_tmp:w ##1##2##3##4
30667           {
30668             \tl_const:Nx #1
30669             {
30670               \exp_after:wN \exp_after:wN \exp_after:wN
30671               \exp_not:N \char_generate:nn {##1} { 13 }
30672               \exp_after:wN \exp_after:wN \exp_after:wN
30673               \exp_not:N \char_generate:nn {##2} { 13 }
30674               \tl_if_blank:nF {##3}
30675               {
30676                 \exp_after:wN \exp_after:wN \exp_after:wN
30677                 \exp_not:N \char_generate:nn {##3} { 13 }
30678               }
30679             }
30680           }
30681         \use:x
30682         { \__text_tmp:w \char_to_utfviii_bytes:n { "#2 } }
30683       \group_end:
30684     }
30685     \__text_tmp:w \c__text_dotless_i_tl      { 0131 }
30686     \__text_tmp:w \c__text_dotted_I_tl       { 0130 }
30687     \__text_tmp:w \c__text_i_ogonek_tl       { 012F }
30688     \__text_tmp:w \c__text_I_ogonek_tl       { 012E }
30689     \__text_tmp:w \c__text_grosses_Eszett_tl { 1E9E }
30690   }
30691 \group_end:

```

(End definition for \c__text_dotless_i_tl and others.)

For 8-bit engines we now need to define the case-change data for the multi-octet mappings. These need a list of what code points are doable in T1 so the list is hard coded

(there's no saving in loading the mappings dynamically). All of the straight-forward ones have two octets, so that is taken as read.

```

30692 \group_begin:
30693   \bool_lazy_or:nnF
30694     { \sys_if_engine luatex_p: }
30695     { \sys_if_engine xetex_p: }
30696   {
30697     \cs_set_protected:Npn \__text_loop:nn #1#2
30698     {
30699       \quark_if_recursion_tail_stop:n {#1}
30700       \use:x
30701       {
30702         \__text_tmp:w
30703         \char_to_utfviii_bytes:n { "#1 }
30704         \char_to_utfviii_bytes:n { "#2 }
30705       }
30706       \__text_loop:nn
30707     }
30708   \cs_set_protected:Npn \__text_tmp:nnnn #1#2#3#4#5
30709   {
30710     \tl_const:cx
30711     {
30712       c__text_ #1 case_
30713       \char_generate:nn {#2} { 12 }
30714       \char_generate:nn {#3} { 12 }
30715       _tl
30716     }
30717     {
30718       \exp_after:wN \exp_after:wN \exp_after:wN
30719       \exp_not:N \char_generate:nn {#4} { 13 }
30720       \exp_after:wN \exp_after:wN \exp_after:wN
30721       \exp_not:N \char_generate:nn {#5} { 13 }
30722     }
30723   }
30724   \cs_set_protected:Npn \__text_tmp:w #1#2#3#4#5#6#7#8
30725   {
30726     \tl_const:cx
30727     {
30728       c__text_lowercase_
30729       \char_generate:nn {#1} { 12 }
30730       \char_generate:nn {#2} { 12 }
30731       _tl
30732     }
30733     {
30734       \exp_after:wN \exp_after:wN \exp_after:wN
30735       \exp_not:N \char_generate:nn {#5} { 13 }
30736       \exp_after:wN \exp_after:wN \exp_after:wN
30737       \exp_not:N \char_generate:nn {#6} { 13 }
30738     }
30739     \__text_tmp:nnnn { upper } {#5} {#6} {#1} {#2}
30740     \__text_tmp:nnnn { title } {#5} {#6} {#1} {#2}
30741   }
30742   \__text_loop:nn
30743   { 00C0 } { 00E0 }

```

30744	{ 00C1 }	{ 00E1 }
30745	{ 00C2 }	{ 00E2 }
30746	{ 00C3 }	{ 00E3 }
30747	{ 00C4 }	{ 00E4 }
30748	{ 00C5 }	{ 00E5 }
30749	{ 00C6 }	{ 00E6 }
30750	{ 00C7 }	{ 00E7 }
30751	{ 00C8 }	{ 00E8 }
30752	{ 00C9 }	{ 00E9 }
30753	{ 00CA }	{ 00EA }
30754	{ 00CB }	{ 00EB }
30755	{ 00CC }	{ 00EC }
30756	{ 00CD }	{ 00ED }
30757	{ 00CE }	{ 00EE }
30758	{ 00CF }	{ 00EF }
30759	{ 00D0 }	{ 00F0 }
30760	{ 00D1 }	{ 00F1 }
30761	{ 00D2 }	{ 00F2 }
30762	{ 00D3 }	{ 00F3 }
30763	{ 00D4 }	{ 00F4 }
30764	{ 00D5 }	{ 00F5 }
30765	{ 00D6 }	{ 00F6 }
30766	{ 00D8 }	{ 00F8 }
30767	{ 00D9 }	{ 00F9 }
30768	{ 00DA }	{ 00FA }
30769	{ 00DB }	{ 00FB }
30770	{ 00DC }	{ 00FC }
30771	{ 00DD }	{ 00FD }
30772	{ 00DE }	{ 00FE }
30773	{ 0100 }	{ 0101 }
30774	{ 0102 }	{ 0103 }
30775	{ 0104 }	{ 0105 }
30776	{ 0106 }	{ 0107 }
30777	{ 0108 }	{ 0109 }
30778	{ 010A }	{ 010B }
30779	{ 010C }	{ 010D }
30780	{ 010E }	{ 010F }
30781	{ 0110 }	{ 0111 }
30782	{ 0112 }	{ 0113 }
30783	{ 0114 }	{ 0115 }
30784	{ 0116 }	{ 0117 }
30785	{ 0118 }	{ 0119 }
30786	{ 011A }	{ 011B }
30787	{ 011C }	{ 011D }
30788	{ 011E }	{ 011F }
30789	{ 0120 }	{ 0121 }
30790	{ 0122 }	{ 0123 }
30791	{ 0124 }	{ 0125 }
30792	{ 0128 }	{ 0129 }
30793	{ 012A }	{ 012B }
30794	{ 012C }	{ 012D }
30795	{ 012E }	{ 012F }
30796	{ 0132 }	{ 0133 }
30797	{ 0134 }	{ 0135 }

30798	{ 0136 }	{ 0137 }
30799	{ 0139 }	{ 013A }
30800	{ 013B }	{ 013C }
30801	{ 013E }	{ 013F }
30802	{ 0141 }	{ 0142 }
30803	{ 0143 }	{ 0144 }
30804	{ 0145 }	{ 0146 }
30805	{ 0147 }	{ 0148 }
30806	{ 014A }	{ 014B }
30807	{ 014C }	{ 014D }
30808	{ 014E }	{ 014F }
30809	{ 0150 }	{ 0151 }
30810	{ 0152 }	{ 0153 }
30811	{ 0154 }	{ 0155 }
30812	{ 0156 }	{ 0157 }
30813	{ 0158 }	{ 0159 }
30814	{ 015A }	{ 015B }
30815	{ 015C }	{ 015D }
30816	{ 015E }	{ 015F }
30817	{ 0160 }	{ 0161 }
30818	{ 0162 }	{ 0163 }
30819	{ 0164 }	{ 0165 }
30820	{ 0168 }	{ 0169 }
30821	{ 016A }	{ 016B }
30822	{ 016C }	{ 016D }
30823	{ 016E }	{ 016F }
30824	{ 0170 }	{ 0171 }
30825	{ 0172 }	{ 0173 }
30826	{ 0174 }	{ 0175 }
30827	{ 0176 }	{ 0177 }
30828	{ 0178 }	{ 00FF }
30829	{ 0179 }	{ 017A }
30830	{ 017B }	{ 017C }
30831	{ 017D }	{ 017E }
30832	{ 01CD }	{ 01CE }
30833	{ 01CF }	{ 01D0 }
30834	{ 01D1 }	{ 01D2 }
30835	{ 01D3 }	{ 01D4 }
30836	{ 01E2 }	{ 01E3 }
30837	{ 01E6 }	{ 01E7 }
30838	{ 01E8 }	{ 01E9 }
30839	{ 01EA }	{ 01EB }
30840	{ 01F4 }	{ 01F5 }
30841	{ 0218 }	{ 0219 }
30842	{ 021A }	{ 021B }

Add T2 (Cyrillic) as this is doable using a classical \MakeUppercase approach.

30843	{ 0400 }	{ 0450 }
30844	{ 0401 }	{ 0451 }
30845	{ 0402 }	{ 0452 }
30846	{ 0403 }	{ 0453 }
30847	{ 0404 }	{ 0454 }
30848	{ 0405 }	{ 0455 }
30849	{ 0406 }	{ 0456 }
30850	{ 0407 }	{ 0457 }

30851	{ 0408 }	{ 0458 }
30852	{ 0409 }	{ 0459 }
30853	{ 040A }	{ 045A }
30854	{ 040B }	{ 045B }
30855	{ 040C }	{ 045C }
30856	{ 040D }	{ 045D }
30857	{ 040E }	{ 045E }
30858	{ 040F }	{ 045F }
30859	{ 0410 }	{ 0430 }
30860	{ 0411 }	{ 0431 }
30861	{ 0412 }	{ 0432 }
30862	{ 0413 }	{ 0433 }
30863	{ 0414 }	{ 0434 }
30864	{ 0415 }	{ 0435 }
30865	{ 0416 }	{ 0436 }
30866	{ 0417 }	{ 0437 }
30867	{ 0418 }	{ 0438 }
30868	{ 0419 }	{ 0439 }
30869	{ 041A }	{ 043A }
30870	{ 041B }	{ 043B }
30871	{ 041C }	{ 043C }
30872	{ 041D }	{ 043D }
30873	{ 041E }	{ 043E }
30874	{ 041F }	{ 043F }
30875	{ 0420 }	{ 0440 }
30876	{ 0421 }	{ 0441 }
30877	{ 0422 }	{ 0442 }
30878	{ 0423 }	{ 0443 }
30879	{ 0424 }	{ 0444 }
30880	{ 0425 }	{ 0445 }
30881	{ 0426 }	{ 0446 }
30882	{ 0427 }	{ 0447 }
30883	{ 0428 }	{ 0448 }
30884	{ 0429 }	{ 0449 }
30885	{ 042A }	{ 044A }
30886	{ 042B }	{ 044B }
30887	{ 042C }	{ 044C }
30888	{ 042D }	{ 044D }
30889	{ 042E }	{ 044E }
30890	{ 042F }	{ 044F }

Core Greek support: there may need to be a little more work here to deal completely with accents.

30891	{ 0391 }	{ 03B1 }
30892	{ 0392 }	{ 03B2 }
30893	{ 0393 }	{ 03B3 }
30894	{ 0394 }	{ 03B4 }
30895	{ 0395 }	{ 03B5 }
30896	{ 0396 }	{ 03B6 }
30897	{ 0397 }	{ 03B7 }
30898	{ 0398 }	{ 03B8 }
30899	{ 0399 }	{ 03B9 }
30900	{ 039A }	{ 03BA }
30901	{ 039B }	{ 03BB }

```

30902     { 039C } { 03BC }
30903     { 039D } { 03BD }
30904     { 039E } { 03BE }
30905     { 039F } { 03BF }
30906     { 03A0 } { 03C0 }
30907     { 03A1 } { 03C1 }
30908     { 03A3 } { 03C3 }
30909     { 03A4 } { 03C4 }
30910     { 03A5 } { 03C5 }
30911     { 03A6 } { 03C6 }
30912     { 03A7 } { 03C7 }
30913     { 03A8 } { 03C8 }
30914     { 03A9 } { 03C9 }
30915     { 03D8 } { 03D9 }
30916     { 03DA } { 03DB }
30917     { 03DC } { 03DD }
30918     { 03DE } { 03DF }
30919     { 03E0 } { 03E1 }
30920     \q_recursion_tail ?
30921     \q_recursion_stop
30922     \cs_set_protected:Npn \__text_tmp:w #1#2#3
30923     {
30924         \group_begin:
30925         \cs_set_protected:Npn \__text_tmp:w ##1##2##3##4
30926         {
30927             \tl_const:cx
30928             {
30929                 c__text_ #3 case_
30930                 \char_generate:nn {##1} { 12 }
30931                 \char_generate:nn {##2} { 12 }
30932                 _tl
30933             }
30934             {#2}
30935         }
30936         \use:x
30937         { \__text_tmp:w \char_to_utfviii_bytes:n { "#1 } }
30938         \group_end:
30939     }
30940     \__text_tmp:w { 00DF } { SS } { upper }
30941     \__text_tmp:w { 00DF } { Ss } { title }
30942     \__text_tmp:w { 0131 } { I } { upper }
30943 }
30944 \group_end:

```

The (fixed) look-up mappings for letter-like control sequences.

```

30945 \group_begin:
30946     \cs_set_protected:Npn \__text_change_case_setup:NN #1#2
30947     {
30948         \quark_if_recursion_tail_stop:N #1
30949         \tl_const:cn { c__text_lowercase_ \token_to_str:N #1 _tl }
30950         { #2 }
30951         \tl_const:cn { c__text_uppercase_ \token_to_str:N #2 _tl }
30952         { #1 }
30953         \__text_change_case_setup:NN
30954     }

```



```

30955 \__text_change_case_setup:Nn
30956 \AA \aa
30957 \AE \ae
30958 \DH \dh
30959 \DJ \dj
30960 \IJ \ij
30961 \L \l
30962 \NG \ng
30963 \O \o
30964 \OE \oe
30965 \SS \ss
30966 \TH \th
30967 \q_recursion_tail ?
30968 \q_recursion_stop
30969 \tl_const:cn { c__text_uppercase_ \token_to_str:N \i _tl } { I }
30970 \tl_const:cn { c__text_uppercase_ \token_to_str:N \j _tl } { J }
30971 \group_end:

```

To deal with possible encoding-specific extensions to \@uclclist, we check at the end of the preamble. This will therefore only apply to L^AT_EX 2_ε package mode.

```

30972 \cs_if_exist:cT { @uclclist }
30973 {
30974   \AtBeginDocument
30975   {
30976     \group_begin:
30977     \cs_set_protected:Npn \__text_change_case_setup:Nn #1#2
30978     {
30979       \quark_if_recursion_tail_stop:N #1
30980       \tl_if_single_token:nT {#2}
30981       {
30982         \cs_if_exist:cF
30983         { c__text_uppercase_ \token_to_str:N #1 _tl }
30984         {
30985           \tl_const:cn
30986           { c__text_uppercase_ \token_to_str:N #1 _tl }
30987           { #2 }
30988         }
30989         \cs_if_exist:cF
30990         { c__text_lowercase_ \token_to_str:N #2 _tl }
30991         {
30992           \tl_const:cn
30993           { c__text_lowercase_ \token_to_str:N #2 _tl }
30994           { #1 }
30995         }
30996       }
30997       \__text_change_case_setup:Nn
30998     }
30999     \exp_after:wN \__text_change_case_setup:Nn \@uclclist
31000     \q_recursion_tail ?
31001     \q_recursion_stop
31002   \group_end:
31003 }
31004 }
31005 </initex | package>

```

48 l3text-purify implementation

```
31006 <*initex | package>
```

```
31007 <@@=text>
```

48.1 Purifying text

```
\_text_if_recursion_tail_stop:N
```

Functions to query recursion quarks.

```
31008 \_kernel_quark_new_test:N \_text_if_recursion_tail_stop:N
```

(End definition for `_text_if_recursion_tail_stop:N`.)

```
\text_purify:n
```

As in the other parts of the module, we start off with a standard “action” loop, with expansion applied up-front. Here, as there will be no text commands left in the output, there is no concern about using `\exp_not:n` and e-type expansion.

```
\_text_purify:n
```

```
\_text_purify_loop:w
```

```
\_text_purify_group:n
```

```
\_text_purify_space:w
```

```
\_text_purify_N_type:N
```

```
\_text_purify_N_type_aux:N
```

```
\_text_purify_math_search:NNN
```

```
\_text_purify_math_start:NNw
```

```
\_text_purify_math_store:n
```

```
\_text_purify_math_store:nw
```

```
\_text_purify_math_end:w
```

```
\_text_purify_math_loop:NNw
```

```
\_text_purify_math_N_type:NNN
```

```
\_text_purify_math_group:NNn
```

```
\_text_purify_math_space:NNw
```

```
\_text_purify_math_cmd:N
```

```
\_text_purify_math_cmd:NN
```

```
\_text_purify_math_cmd:Nn
```

```
\_text_purify_replace:N
```

```
\_text_purify_replace:n
```

```
\_text_purify_expand:N
```

```
\_text_purify_protect:N
```

```
31009 \cs_new:Npn \text_purify:n #1
```

```
31010 {
```

```
31011 \group_align_safe_begin:
```

```
31012 \exp_args:Ne \_text_purify:n
```

```
31013 { \text_expand:n {#1} }
```

```
31014 \group_align_safe_end:
```

```
31015 }
```

```
31016 \cs_new:Npn \_text_purify:n #1
```

```
31017 { \_text_purify_loop:w #1 \q__text_recursion_tail \q__text_recursion_stop }
```

The main loop is a standard “tl action”. Unlike the expansion or case changing, here any groups have to be run inline. Most of the business end is as before in the N-type token processing.

```
31018 \cs_new:Npn \_text_purify_loop:w #1 \q__text_recursion_stop
```

```
31019 {
```

```
31020 \tl_if_head_is_N_type:nTF {#1}
```

```
31021 { \_text_purify_N_type:N }
```

```
31022 {
```

```
31023 \tl_if_head_is_group:nTF {#1}
```

```
31024 { \_text_purify_group:n }
```

```
31025 { \_text_purify_space:w }
```

```
31026 }
```

```
31027 #1 \q__text_recursion_stop
```

```
31028 }
```

```
31029 \cs_new:Npn \_text_purify_group:n #1 { \_text_purify_loop:w #1 }
```

```
31030 \exp_last_unbraced:NNo \cs_new:Npn \_text_purify_space:w \c_space_tl
```

```
31031 {
```

```
31032 \c_space_tl
```

```
31033 \_text_purify_loop:w
```

```
31034 }
```

The first part of handling math mode is exactly the same as in the other functions: look for a start-of-math mode token and if found start a new loop tracking the closing token.

```
31035 \cs_new:Npn \_text_purify_N_type:N #1
```

```
31036 {
```

```
31037 \_text_if_recursion_tail_stop:N #1
```

```
31038 \_text_purify_N_type_aux:N #1
```

```
31039 }
```

```
31040 \cs_new:Npn \_text_purify_N_type_aux:N #1
```

```
31041 {
```

```

31042 \exp_after:wN \_text_purify_math_search:NNN
31043 \exp_after:wN #1 \l_text_math_delims_tl
31044 \q__text_recursion_tail ?
31045 \q__text_recursion_stop
31046 }
31047 \cs_new:Npn \_text_purify_math_search:NNN #1#2#3
31048 {
31049 \_text_if_recursion_tail_stop_do:Nn #2
31050 { \_text_purify_math_cmd:N #1 }
31051 \token_if_eq_meaning:NNTF #1 #2
31052 {
31053 \_text_use_i_delimit_by_q_recursion_stop:nw
31054 { \_text_purify_math_start:NNw #2 #3 }
31055 }
31056 { \_text_purify_math_search:NNN #1 }
31057 }
31058 \cs_new:Npn \_text_purify_math_start:NNw #1#2#3 \q__text_recursion_stop
31059 {
31060 \_text_purify_math_loop:NNw #1#2#3 \q__text_recursion_stop
31061 \_text_purify_math_result:n { }
31062 }
31063 \cs_new:Npn \_text_purify_math_store:n #1
31064 { \_text_purify_math_store:nw {#1} }
31065 \cs_new:Npn \_text_purify_math_store:nw #1#2 \_text_purify_math_result:n #3
31066 { #2 \_text_purify_math_result:n { #3 #1 } }
31067 \cs_new:Npn \_text_purify_math_end:w #1 \_text_purify_math_result:n #2
31068 {
31069 \exp_not:n { $ #2 $ }
31070 \_text_purify_loop:w #1
31071 }
31072 \cs_new:Npn \_text_purify_math_stop:Nw #1 \_text_purify_math_result:n #2
31073 { \exp_not:n {#1#2} }
31074 \cs_new:Npn \_text_purify_math_loop:NNw #1#2#3 \q__text_recursion_stop
31075 {
31076 \tl_if_head_is_N_type:nTF {#3}
31077 { \_text_purify_math_N_type:NNN }
31078 {
31079 \tl_if_head_is_group:nTF {#3}
31080 { \_text_purify_math_group:NNn }
31081 { \_text_purify_math_space:NNw }
31082 }
31083 #1#2#3 \q__text_recursion_stop
31084 }
31085 \cs_new:Npn \_text_purify_math_N_type:NNN #1#2#3
31086 {
31087 \_text_if_recursion_tail_stop_do:Nn #3
31088 { \_text_purify_math_stop:Nw #1 }
31089 \token_if_eq_meaning:NNTF #3 #2
31090 { \_text_purify_math_end:w }
31091 {
31092 \_text_purify_math_store:n {#3}
31093 \_text_purify_math_loop:NNw #1#2
31094 }
31095 }

```

```

31096 \cs_new:Npn \__text_purify_math_group:NNn #1#2#3
31097 {
31098   \__text_purify_math_store:n { {#3} }
31099   \__text_purify_math_loop:NNw #1#2
31100 }
31101 \exp_after:wN \cs_new:Npn \exp_after:wN \__text_purify_math_space:NNw
31102   \exp_after:wN # \exp_after:wN 1
31103   \exp_after:wN # \exp_after:wN 2 \c_space_tl
31104 {
31105   \__text_purify_math_store:n { ~ }
31106   \__text_purify_math_loop:NNw #1#2
31107 }

```

Then handle math mode as an argument: same outcomes, different input syntax.

```

31108 \cs_new:Npn \__text_purify_math_cmd:N #1
31109 {
31110   \exp_after:wN \__text_purify_math_cmd:NN \exp_after:wN #1
31111   \l_text_math_arg_tl \q_text_recursion_tail \q_text_recursion_stop
31112 }
31113 \cs_new:Npn \__text_purify_math_cmd:NN #1#2
31114 {
31115   \__text_if_recursion_tail_stop_do:Nn #2
31116   { \__text_purify_replace:N #1 }
31117   \cs_if_eq:NNTF #2 #1
31118   {
31119     \__text_use_i_delimit_by_q_recursion_stop:nw
31120     { \__text_purify_math_cmd:n }
31121   }
31122   { \__text_purify_math_cmd:NN #1 }
31123 }
31124 \cs_new:Npn \__text_purify_math_cmd:n #1
31125 { \__text_purify_math_end:w \__text_purify_math_result:n {#1} }

```

For N-type tokens, we first look for a string-context replacement before anything else: this can therefore cover anything. Assuming we don't find one, check to see if we can expand control sequences: if not, they have to be dropped. We also allow for L^AT_EX 2_ε `\protect`: there's an assumption that we don't have `\protect { \oops }` or similar, but that's also in the expansion code and seems like a reasonable balance.

```

31126 \cs_new:Npn \__text_purify_replace:N #1
31127 {
31128   \bool_lazy_and:nnTF
31129   { \cs_if_exist_p:c { l__text_purify_ \token_to_str:N #1 _tl } }
31130   {
31131     \bool_lazy_or_p:nn
31132     { \token_if_cs_p:N #1 }
31133     { \token_if_active_p:N #1 }
31134   }
31135   {
31136     \exp_args:Nv \__text_purify_replace:n
31137     { l__text_purify_ \token_to_str:N #1 _tl }
31138   }
31139   {
31140     \token_if_cs:NNTF #1
31141     { \__text_purify_expand:N #1 }
31142     {

```

```

31143         \text_token_to_explicit:N #1
31144         \text_purify_loop:w
31145     }
31146 }
31147 }
31148 \cs_new:Npn \text_purify_replace:n #1 { \text_purify_loop:w #1 }
31149 \cs_new:Npn \text_purify_expand:N #1
31150 {
31151     \str_if_eq:nnTF {#1} { \protect }
31152     { \text_purify_protect:N }
31153     {
31154         \text_if_expandable:NTF #1
31155         { \exp_after:wN \text_purify_loop:w #1 }
31156         { \text_purify_loop:w }
31157     }
31158 }
31159 \cs_new:Npn \text_purify_protect:N #1
31160 {
31161     \text_if_recursion_tail_stop:N #1
31162     \text_purify_loop:w
31163 }

```

(End definition for `\text_purify:n` and others. This function is documented on page 258.)

`\text_declare_purify_equivalent:Nn`
`\text_declare_purify_equivalent:Nx`

```

31164 \cs_new_protected:Npn \text_declare_purify_equivalent:Nn #1#2
31165 {
31166     \tl_clear_new:c { l_text_purify_token_to_str:N #1 _tl }
31167     \tl_set:cn { l_text_purify_token_to_str:N #1 _tl } {#2}
31168 }
31169 \cs_generate_variant:Nn \text_declare_purify_equivalent:Nn { Nx }

```

(End definition for `\text_declare_purify_equivalent:Nn`. This function is documented on page 258.)

Now pre-define a range of standard commands that need dedicated definitions in purified text. First handle font-related stuff: all of this needs to be disabled.

```

31170 \tl_map_inline:nn
31171 {
31172     \fontencoding
31173     \fontfamily
31174     \fontseries
31175     \fontshape
31176 }
31177 { \text_declare_purify_equivalent:Nn #1 { \use_none:n } }
31178 \text_declare_purify_equivalent:Nn \fontsize { \use_none:nn }
31179 \text_declare_purify_equivalent:Nn \selectfont { }
31180 \text_declare_purify_equivalent:Nn \usefont { \use_none:nnnn }
31181 \tl_map_inline:nn
31182 {
31183     \emph
31184     \text
31185     \textnormal
31186     \textrm
31187     \textsf
31188     \texttt

```

```

31189     \textbf
31190     \textmd
31191     \textit
31192     \textsl
31193     \textup
31194     \textsc
31195     \textulc
31196   }
31197   { \text_declare_purify_equivalent:Nn #1 { \use:n } }
31198 \tl_map_inline:nn
31199   {
31200     \normalfont
31201     \rmfamily
31202     \sffamily
31203     \ttfamily
31204     \bfseries
31205     \mdseries
31206     \itshape
31207     \scshape
31208     \slshape
31209     \upshape
31210     \em
31211     \Huge
31212     \LARGE
31213     \Large
31214     \footnotesize
31215     \huge
31216     \large
31217     \normalsize
31218     \scriptsize
31219     \small
31220     \tiny
31221   }
31222   { \text_declare_purify_equivalent:Nn #1 { } }

```

Environments have to be handled by pure expansion.

```

31223 \text_declare_purify_equivalent:Nn \begin { \use:c }
31224 \text_declare_purify_equivalent:Nn \end { \use:c }

```

Some common symbols and similar ideas.

```

31225 \text_declare_purify_equivalent:Nn \ { }
31226 \tl_map_inline:nn
31227   { \{ \} \# \$ \% \_ }
31228   { \text_declare_purify_equivalent:Nx #1 { \cs_to_str:N #1 } }

```

Cross-referencing.

```

31229 \text_declare_purify_equivalent:Nn \label { \use_none:n }

```

Spaces.

```

31230 \group_begin:
31231 \char_set_catcode_active:N \~
31232 \use:n
31233   {
31234     \group_end:
31235     \text_declare_purify_equivalent:Nx ~ { \c_space_tl }
31236   }

```

```

31237 \text_declare_purify_equivalent:Nn \nobreakspace { ~ }
31238 \text_declare_purify_equivalent:Nn \ { ~ }
31239 \text_declare_purify_equivalent:Nn \, { ~ }

```

48.2 Accent and letter-like data for purifying text

In contrast to case changing, both 8-bit and Unicode engines need information for text purification to handle accents and letter-like functions: these all need to be removed. However, the results are of course engine-dependent.

For the letter-like commands, life is relatively easy: they are all simply added as standard exceptions. The only oddity is `\SS`, which gets converted to two letters. (At some stage an alternative version can presumably be added to `babel` or similar.)

```

31240 \bool_lazy_or:nnTF
31241 { \sys_if_engine luatex_p: }
31242 { \sys_if_engine xetex_p: }
31243 {
31244   \cs_set_protected:Npn \__text_loop:Nn #1#2
31245   {
31246     \quark_if_recursion_tail_stop:N #1
31247     \text_declare_purify_equivalent:Nx #1
31248     {
31249       \char_generate:nn { "#2 }
31250       { \char_value_catcode:n { "#2 } }
31251     }
31252     \__text_loop:Nn
31253   }
31254 }
31255 {
31256   \cs_set_protected:Npn \__text_loop:Nn #1#2
31257   {
31258     \quark_if_recursion_tail_stop:N #1
31259     \text_declare_purify_equivalent:Nx #1
31260     {
31261       \exp_args:Ne \__text_tmp:n
31262       { \char_to_utfviii_bytes:n { "#2 } }
31263     }
31264     \__text_loop:Nn
31265   }
31266   \cs_set:Npn \__text_tmp:n #1 { \__text_tmp:nnnn #1 }
31267   \cs_set:Npn \__text_tmp:nnnn #1#2#3#4
31268   {
31269     \exp_after:wN \exp_after:wN \exp_after:wN
31270     \exp_not:N \char_generate:nn {#1} { 13 }
31271     \exp_after:wN \exp_after:wN \exp_after:wN
31272     \exp_not:N \char_generate:nn {#2} { 13 }
31273   }
31274 }
31275 \__text_loop:Nn
31276 \AA { 00C5 }
31277 \AE { 00C6 }
31278 \DH { 00D0 }
31279 \DJ { 0110 }
31280 \IJ { 0132 }

```

```

31281 \L { 0141 }
31282 \NG { 014A }
31283 \O { 00D8 }
31284 \OE { 0152 }
31285 \TH { 00DE }
31286 \aa { 00E5 }
31287 \ae { 00E6 }
31288 \dh { 00F0 }
31289 \dj { 0111 }
31290 \i { 0131 }
31291 \j { 0237 }
31292 \ij { 0132 }
31293 \l { 0142 }
31294 \ng { 014B }
31295 \o { 00F8 }
31296 \oe { 0153 }
31297 \ss { 00DF }
31298 \th { 00FE }
31299 \q_recursion_tail ?
31300 \q_recursion_stop
31301 \text_declare_purify_equivalent:Nn \SS { SS }

```

_text_purify_accent:NN Accent LICR handling is a little more complex. Accents may exist as pre-composed codepoints or as independent glyphs. The former are all saved as single token lists, whilst for the latter the combining accent needs to be re-ordered compared to the character it applies to.

```

31302 \cs_new:Npn \_text_purify_accent:NN #1#2
31303 {
31304   \cs_if_exist:cTF
31305     { c__text_purify_ \token_to_str:N #1 _ \token_to_str:N #2 _tl }
31306     {
31307       \exp_not:v
31308         { c__text_purify_ \token_to_str:N #1 _ \token_to_str:N #2 _tl }
31309     }
31310     {
31311       \exp_not:n {#2}
31312       \exp_not:v { c__text_purify_ \token_to_str:N #1 _tl }
31313     }
31314 }
31315 \tl_map_inline:Nn \l_text_accents_tl
31316 { \text_declare_purify_equivalent:Nn #1 { \_text_purify_accent:NN #1 } }

```

First set up the combining accents.

```

31317 \group_begin:
31318   \cs_set_protected:Npn \_text_loop:Nn #1#2
31319   {
31320     \quark_if_recursion_tail_stop:N #1
31321     \tl_const:cx { c__text_purify_ \token_to_str:N #1 _tl }
31322     { \_text_tmp:n {#2} }
31323     \_text_loop:Nn
31324   }
31325 \bool_lazy_or:nnTF
31326 { \sys_if_engine luatex_p: }
31327 { \sys_if_engine xetex_p: }

```



```

31328 {
31329   \cs_set:Npn \__text_tmp:n #1
31330   {
31331     \char_generate:nn { "#1 }
31332     { \char_value_catcode:n { "#1 } }
31333   }
31334 }
31335 {
31336   \cs_set:Npn \__text_tmp:n #1
31337   {
31338     \exp_args:Ne \__text_tmp_aux:n
31339     { \char_to_utfviii_bytes:n { "#1 } }
31340   }
31341   \cs_set:Npn \__text_tmp_aux:n #1 { \__text_tmp:nnnn #1 }
31342   \cs_set:Npn \__text_tmp:nnnn #1#2#3#4
31343   {
31344     \exp_after:wN \exp_after:wN \exp_after:wN
31345     \exp_not:N \char_generate:nn {#1} { 13 }
31346     \exp_after:wN \exp_after:wN \exp_after:wN
31347     \exp_not:N \char_generate:nn {#2} { 13 }
31348   }
31349 }
31350 \__text_loop:Nn
31351 \‘ { 0300 }
31352 \’ { 0301 }
31353 \^ { 0302 }
31354 \~ { 0303 }
31355 \= { 0304 }
31356 \u { 0306 }
31357 \. { 0307 }
31358 \" { 0308 }
31359 \r { 030A }
31360 \H { 030B }
31361 \v { 030C }
31362 \d { 0323 }
31363 \c { 0327 }
31364 \k { 0328 }
31365 \b { 0331 }
31366 \t { 0361 }
31367 \q_recursion_tail { }
31368 \q_recursion_stop

```

Now we handle the pre-composed accents: the list here is taken from `puenc.def`. All of the precomposed cases take a single letter as their second argument. We do not try to cover the case where an accent is added to a “real” dotless-i or -j, or a æ/Æ. Rather, we assume that if the UTF-8 character is used, it will have the real accent character too.

```

31369 \cs_set_protected:Npn \__text_loop:NNn #1#2#3
31370 {
31371   \quark_if_recursion_tail_stop:N #1
31372   \tl_const:cx
31373   { c__text_purify_ \token_to_str:N #1 _ \token_to_str:N #2 _tl }
31374   { \__text_tmp:n {#3} }
31375   \__text_loop:NNn
31376 }

```

```

31377 \__text_loop:NNn
31378 \‘ A { 00C0 }
31379 \’ A { 00C1 }
31380 \^ A { 00C2 }
31381 \~ A { 00C3 }
31382 \" A { 00C4 }
31383 \r A { 00C5 }
31384 \c C { 00C7 }
31385 \‘ E { 00C8 }
31386 \’ E { 00C9 }
31387 \^ E { 00CA }
31388 \" E { 00CB }
31389 \‘ I { 00CC }
31390 \’ I { 00CD }
31391 \^ I { 00CE }
31392 \" I { 00CF }
31393 \~ N { 00D1 }
31394 \‘ O { 00D2 }
31395 \’ O { 00D3 }
31396 \^ O { 00D4 }
31397 \~ O { 00D5 }
31398 \" O { 00D6 }
31399 \‘ U { 00D9 }
31400 \’ U { 00DA }
31401 \^ U { 00DB }
31402 \" U { 00DC }
31403 \’ Y { 00DD }
31404 \‘ a { 00E0 }
31405 \’ a { 00E1 }
31406 \^ a { 00E2 }
31407 \~ a { 00E3 }
31408 \" a { 00E4 }
31409 \r a { 00E5 }
31410 \c c { 00E7 }
31411 \‘ e { 00E8 }
31412 \’ e { 00E9 }
31413 \^ e { 00EA }
31414 \" e { 00EB }
31415 \‘ i { 00EC }
31416 \‘ \i { 00EC }
31417 \’ i { 00ED }
31418 \’ \i { 00ED }
31419 \^ i { 00EE }
31420 \^ \i { 00EE }
31421 \" i { 00EF }
31422 \" \i { 00EF }
31423 \~ n { 00F1 }
31424 \‘ o { 00F2 }
31425 \’ o { 00F3 }
31426 \^ o { 00F4 }
31427 \~ o { 00F5 }
31428 \" o { 00F6 }
31429 \‘ u { 00F9 }
31430 \’ u { 00FA }

```

31431	\^ u	{ 00FB }
31432	\" u	{ 00FC }
31433	\' y	{ 00FD }
31434	\" y	{ 00FF }
31435	\= A	{ 0100 }
31436	\= a	{ 0101 }
31437	\u A	{ 0102 }
31438	\u a	{ 0103 }
31439	\k A	{ 0104 }
31440	\k a	{ 0105 }
31441	\' C	{ 0106 }
31442	\' c	{ 0107 }
31443	\^ C	{ 0108 }
31444	\^ c	{ 0109 }
31445	\. C	{ 010A }
31446	\. c	{ 010B }
31447	\v C	{ 010C }
31448	\v c	{ 010D }
31449	\v D	{ 010E }
31450	\v d	{ 010F }
31451	\= E	{ 0112 }
31452	\= e	{ 0113 }
31453	\u E	{ 0114 }
31454	\u e	{ 0115 }
31455	\. E	{ 0116 }
31456	\. e	{ 0117 }
31457	\k E	{ 0118 }
31458	\k e	{ 0119 }
31459	\v E	{ 011A }
31460	\v e	{ 011B }
31461	\^ G	{ 011C }
31462	\^ g	{ 011D }
31463	\u G	{ 011E }
31464	\u g	{ 011F }
31465	\. G	{ 0120 }
31466	\. g	{ 0121 }
31467	\c G	{ 0122 }
31468	\c g	{ 0123 }
31469	\^ H	{ 0124 }
31470	\^ h	{ 0125 }
31471	\~ I	{ 0128 }
31472	\~ i	{ 0129 }
31473	\~ \i	{ 0129 }
31474	\= I	{ 012A }
31475	\= i	{ 012B }
31476	\= \i	{ 012B }
31477	\u I	{ 012C }
31478	\u i	{ 012D }
31479	\u \i	{ 012D }
31480	\k I	{ 012E }
31481	\k i	{ 012F }
31482	\k \i	{ 012F }
31483	\. I	{ 0130 }
31484	\^ J	{ 0134 }

31485	\^ j	{ 0135 }
31486	\^ \j	{ 0135 }
31487	\c K	{ 0136 }
31488	\c k	{ 0137 }
31489	\' L	{ 0139 }
31490	\' l	{ 013A }
31491	\c L	{ 013B }
31492	\c l	{ 013C }
31493	\v L	{ 013D }
31494	\v l	{ 013E }
31495	\. L	{ 013F }
31496	\. l	{ 0140 }
31497	\' N	{ 0143 }
31498	\' n	{ 0144 }
31499	\c N	{ 0145 }
31500	\c n	{ 0146 }
31501	\v N	{ 0147 }
31502	\v n	{ 0148 }
31503	\= O	{ 014C }
31504	\= o	{ 014D }
31505	\u O	{ 014E }
31506	\u o	{ 014F }
31507	\H O	{ 0150 }
31508	\H o	{ 0151 }
31509	\' R	{ 0154 }
31510	\' r	{ 0155 }
31511	\c R	{ 0156 }
31512	\c r	{ 0157 }
31513	\v R	{ 0158 }
31514	\v r	{ 0159 }
31515	\' S	{ 015A }
31516	\' s	{ 015B }
31517	\^ S	{ 015C }
31518	\^ s	{ 015D }
31519	\c S	{ 015E }
31520	\c s	{ 015F }
31521	\v S	{ 0160 }
31522	\v s	{ 0161 }
31523	\c T	{ 0162 }
31524	\c t	{ 0163 }
31525	\v T	{ 0164 }
31526	\v t	{ 0165 }
31527	\~ U	{ 0168 }
31528	\~ u	{ 0169 }
31529	\= U	{ 016A }
31530	\= u	{ 016B }
31531	\u U	{ 016C }
31532	\u u	{ 016D }
31533	\r U	{ 016E }
31534	\r u	{ 016F }
31535	\H U	{ 0170 }
31536	\H u	{ 0171 }
31537	\k U	{ 0172 }
31538	\k u	{ 0173 }

```

31539    \^ W    { 0174 }
31540    \^ w    { 0175 }
31541    \^ Y    { 0176 }
31542    \^ y    { 0177 }
31543    \" Y    { 0178 }
31544    \' Z    { 0179 }
31545    \' z    { 017A }
31546    \. Z    { 017B }
31547    \. z    { 017C }
31548    \v Z    { 017D }
31549    \v z    { 017E }
31550    \v A    { 01CD }
31551    \v a    { 01CE }
31552    \v I    { 01CF }
31553    \v \i   { 01D0 }
31554    \v i    { 01D0 }
31555    \v O    { 01D1 }
31556    \v o    { 01D2 }
31557    \v U    { 01D3 }
31558    \v u    { 01D4 }
31559    \v G    { 01E6 }
31560    \v g    { 01E7 }
31561    \v K    { 01E8 }
31562    \v k    { 01E9 }
31563    \k O    { 01EA }
31564    \k o    { 01EB }
31565    \v \j   { 01F0 }
31566    \v j    { 01F0 }
31567    \' G    { 01F4 }
31568    \' g    { 01F5 }
31569    \' N    { 01F8 }
31570    \' n    { 01F9 }
31571    \' \AE   { 01FC }
31572    \' \ae   { 01FD }
31573    \' \O    { 01FE }
31574    \' \o    { 01FF }
31575    \v H    { 021E }
31576    \v h    { 021F }
31577    \. A    { 0226 }
31578    \. a    { 0227 }
31579    \c E    { 0228 }
31580    \c e    { 0229 }
31581    \. O    { 022E }
31582    \. o    { 022F }
31583    \= Y    { 0232 }
31584    \= y    { 0233 }
31585    \q_recursion_tail ? { }
31586    \q_recursion_stop
31587    \group_end:

```

(End definition for _text_purify_accent:NN.)

```

31588    </initex | package>

```

49 l3legacy Implementation

```

31589 <*package>
31590 <@@=legacy>

\legacy_if_p:n A friendly wrapper.
\legacy_if:nTF
31591 \prg_new_conditional:Npnn \legacy_if:n #1 { p , T , F , TF }
31592 {
31593   \exp_args:Nc \if_meaning:w { if#1 } \iftrue
31594   \prg_return_true:
31595   \else:
31596   \prg_return_false:
31597   \fi:
31598 }

(End definition for \legacy_if:nTF. This function is documented on page 259.)

31599 </package>

```

50 l3candidates Implementation

```

31600 <*initex | package>

```

50.1 Additions to l3box

```

31601 <@@=box>

```

50.1.1 Viewing part of a box

```

\box_clip:N A wrapper around the driver-dependent code.
\box_clip:c
\box_gclip:N
\box_gclip:c
31602 \cs_new_protected:Npn \box_clip:N #1
31603 { \hbox_set:Nn #1 { \_box_backend_clip:N #1 } }
31604 \cs_generate_variant:Nn \box_clip:N { c }
31605 \cs_new_protected:Npn \box_gclip:N #1
31606 { \hbox_gset:Nn #1 { \_box_backend_clip:N #1 } }
31607 \cs_generate_variant:Nn \box_gclip:N { c }

```

(End definition for \box_clip:N and \box_gclip:N. These functions are documented on page 260.)

```

\box_set_trim:Nnnnn Trimming from the left- and right-hand edges of the box is easy: kern the appropriate
\box_set_trim:cnnnn parts off each side.
\box_gset_trim:Nnnnn
\box_gset_trim:cnnnn
\_box_set_trim:NnnnnN
31608 \cs_new_protected:Npn \box_set_trim:Nnnnn #1#2#3#4#5
31609 { \_box_set_trim:NnnnnN #1 {#2} {#3} {#4} {#5} \box_set_eq:NN }
31610 \cs_generate_variant:Nn \box_set_trim:Nnnnn { c }
31611 \cs_new_protected:Npn \box_gset_trim:Nnnnn #1#2#3#4#5
31612 { \_box_set_trim:NnnnnN #1 {#2} {#3} {#4} {#5} \box_gset_eq:NN }
31613 \cs_generate_variant:Nn \box_gset_trim:Nnnnn { c }
31614 \cs_new_protected:Npn \_box_set_trim:NnnnnN #1#2#3#4#5#6
31615 {
31616   \hbox_set:Nn \l\_box_internal_box
31617   {
31618     \tex_kern:D - \_box_dim_eval:n {#2}
31619     \box_use:N #1
31620     \tex_kern:D - \_box_dim_eval:n {#4}
31621   }

```

For the height and depth, there is a need to watch the baseline is respected. Material always has to stay on the correct side, so trimming has to check that there is enough material to trim. First, the bottom edge. If there is enough depth, simply set the depth, or if not move down so the result is zero depth. `\box_move_down:nn` is used in both cases so the resulting box always contains a `\lower` primitive. The internal box is used here as it allows safe use of `\box_set_dp:Nn`.

```

31622 \dim_compare:nNnTF { \box_dp:N #1 } > {#3}
31623 {
31624   \hbox_set:Nn \l__box_internal_box
31625   {
31626     \box_move_down:nn \c_zero_dim
31627     { \box_use_drop:N \l__box_internal_box }
31628   }
31629   \box_set_dp:Nn \l__box_internal_box { \box_dp:N #1 - (#3) }
31630 }
31631 {
31632   \hbox_set:Nn \l__box_internal_box
31633   {
31634     \box_move_down:nn { (#3) - \box_dp:N #1 }
31635     { \box_use_drop:N \l__box_internal_box }
31636   }
31637   \box_set_dp:Nn \l__box_internal_box \c_zero_dim
31638 }

```

Same thing, this time from the top of the box.

```

31639 \dim_compare:nNnTF { \box_ht:N \l__box_internal_box } > {#5}
31640 {
31641   \hbox_set:Nn \l__box_internal_box
31642   {
31643     \box_move_up:nn \c_zero_dim
31644     { \box_use_drop:N \l__box_internal_box }
31645   }
31646   \box_set_ht:Nn \l__box_internal_box
31647   { \box_ht:N \l__box_internal_box - (#5) }
31648 }
31649 {
31650   \hbox_set:Nn \l__box_internal_box
31651   {
31652     \box_move_up:nn { (#5) - \box_ht:N \l__box_internal_box }
31653     { \box_use_drop:N \l__box_internal_box }
31654   }
31655   \box_set_ht:Nn \l__box_internal_box \c_zero_dim
31656 }
31657 #6 #1 \l__box_internal_box
31658 }

```

(End definition for `\box_set_trim:Nnnnn`, `\box_gset_trim:Nnnnn`, and `__box_set_trim:NnnnnN`. These functions are documented on page 261.)

`\box_set_viewport:Nnnnn`
`\box_set_viewport:cnnnn`
`\box_gset_viewport:Nnnnn`
`\box_gset_viewport:cnnnn`
`__box_viewport:NnnnnN`

The same general logic as for the trim operation, but with absolute dimensions. As a result, there are some things to watch out for in the vertical direction.

```

31659 \cs_new_protected:Npn \box_set_viewport:Nnnnn #1#2#3#4#5
31660 { \__box_set_viewport:NnnnnN #1 {#2} {#3} {#4} {#5} \box_set_eq:NN }
31661 \cs_generate_variant:Nn \box_set_viewport:Nnnnn { c }

```

```

31662 \cs_new_protected:Npn \box_gset_viewport:Nnnnn #1#2#3#4#5
31663 { \__box_set_viewport:NnnnnN #1 {#2} {#3} {#4} {#5} \box_gset_eq:NN }
31664 \cs_generate_variant:Nn \box_gset_viewport:Nnnnn { c }
31665 \cs_new_protected:Npn \__box_set_viewport:NnnnnN #1#2#3#4#5#6
31666 {
31667   \hbox_set:Nn \l__box_internal_box
31668   {
31669     \tex_kern:D - \__box_dim_eval:n {#2}
31670     \box_use:N #1
31671     \tex_kern:D \__box_dim_eval:n { #4 - \box_wd:N #1 }
31672   }
31673   \dim_compare:nNnTF {#3} < \c_zero_dim
31674   {
31675     \hbox_set:Nn \l__box_internal_box
31676     {
31677       \box_move_down:nn \c_zero_dim
31678       { \box_use_drop:N \l__box_internal_box }
31679     }
31680     \box_set_dp:Nn \l__box_internal_box { - \__box_dim_eval:n {#3} }
31681   }
31682   {
31683     \hbox_set:Nn \l__box_internal_box
31684     { \box_move_down:nn {#3} { \box_use_drop:N \l__box_internal_box } }
31685     \box_set_dp:Nn \l__box_internal_box \c_zero_dim
31686   }
31687   \dim_compare:nNnTF {#5} > \c_zero_dim
31688   {
31689     \hbox_set:Nn \l__box_internal_box
31690     {
31691       \box_move_up:nn \c_zero_dim
31692       { \box_use_drop:N \l__box_internal_box }
31693     }
31694     \box_set_ht:Nn \l__box_internal_box
31695     {
31696       (#5)
31697       \dim_compare:nNnT {#3} > \c_zero_dim
31698       { - (#3) }
31699     }
31700   }
31701   {
31702     \hbox_set:Nn \l__box_internal_box
31703     {
31704       \box_move_up:nn { - \__box_dim_eval:n {#5} }
31705       { \box_use_drop:N \l__box_internal_box }
31706     }
31707     \box_set_ht:Nn \l__box_internal_box \c_zero_dim
31708   }
31709   #6 #1 \l__box_internal_box
31710 }

```

(End definition for `\box_set_viewport:Nnnnn`, `\box_gset_viewport:Nnnnn`, and `__box_viewport:NnnnnN`.
These functions are documented on page 261.)

50.2 Additions to l3flag

31711 <@@=flag>

`\flag_raise_if_clear:n` It might be faster to just call the “trap” function in all cases but conceptually the function name suggests we should only run it if the flag is zero in case the “trap” made customizable in the future.

```
31712 \cs_new:Npn \flag_raise_if_clear:n #1
31713 {
31714   \if_cs_exist:w flag~#1~0 \cs_end:
31715   \else:
31716     \cs:w flag~#1 \cs_end: 0 ;
31717   \fi:
31718 }
```

(End definition for `\flag_raise_if_clear:n`. This function is documented on page 262.)

50.3 Additions to l3msg

31719 <@@=msg>

Pass to an auxiliary the message to display and the module name

```
\msg_expandable_error:nnnnnn 31720 \cs_new:Npn \msg_expandable_error:nnnnnn #1#2#3#4#5#6
\msg_expandable_error:nnffff 31721 {
\msg_expandable_error:nnnnn 31722   \exp_args:Ne \_msg_expandable_error_module:nn
\msg_expandable_error:nnfff 31723   {
\msg_expandable_error:nnnn 31724     \exp_args:Nc \exp_args:Noooo
\msg_expandable_error:nnff 31725     { \c_msg_text_prefix_tl #1 / #2 }
\msg_expandable_error:nnn 31726     { \tl_to_str:n {#3} }
\msg_expandable_error:nnf 31727     { \tl_to_str:n {#4} }
\msg_expandable_error:nn 31728     { \tl_to_str:n {#5} }
\_msg_expandable_error_module:nn 31729     { \tl_to_str:n {#6} }
31730   }
31731   {#1}
31732 }
31733 \cs_new:Npn \msg_expandable_error:nnnnn #1#2#3#4#5
31734 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} {#5} { } }
31735 \cs_new:Npn \msg_expandable_error:nnnn #1#2#3#4
31736 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} { } { } }
31737 \cs_new:Npn \msg_expandable_error:nnn #1#2#3
31738 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} { } { } { } }
31739 \cs_new:Npn \msg_expandable_error:nn #1#2
31740 { \msg_expandable_error:nnnnnn {#1} {#2} { } { } { } { } }
31741 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnffff }
31742 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnfff }
31743 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnff }
31744 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnf }
31745 \cs_new:Npn \_msg_expandable_error_module:nn #1#2
31746 {
31747   \exp_after:wN \exp_after:wN
31748   \exp_after:wN \_msg_use_none_delimit_by_s_stop:w
31749   \use:n { \::error ! ~ #2 : ~ #1 } \s__msg_stop
31750 }
```

(End definition for `\msg_expandable_error:nnnnnn` and others. These functions are documented on page 263.)

`\msg_show_eval:Nn` A short-hand used for `\int_show:n` and similar functions that passes to `\tl_show:n` the result of applying `#1` (a function such as `\int_eval:n`) to the expression `#2`. The use of f-expansion ensures that `#1` is expanded in the scope in which the show command is called, rather than in the group created by `\iow_wrap:nnnN`. This is only important for expressions involving the `\currentgrouplevel` or `\currentgrouptype`. On the other hand we want the expression to be converted to a string with the usual escape character, hence within the wrapping code.

```

31751 \cs_new_protected:Npn \msg_show_eval:Nn #1#2
31752 { \exp_args:Nf \_msg_show_eval:nnN { #1 {#2} } {#2} \tl_show:n }
31753 \cs_new_protected:Npn \msg_log_eval:Nn #1#2
31754 { \exp_args:Nf \_msg_show_eval:nnN { #1 {#2} } {#2} \tl_log:n }
31755 \cs_new_protected:Npn \_msg_show_eval:nnN #1#2#3 { #3 { #2 = #1 } }

```

(End definition for `\msg_show_eval:Nn`, `\msg_log_eval:Nn`, and `_msg_show_eval:nnN`. These functions are documented on page 263.)

`\msg_show_item:n` Each item in the variable is formatted using one of the following functions. We cannot use `\` and so on because these short-hands cannot be used inside the arguments of messages, only when defining the messages.

```

31756 \cs_new:Npx \msg_show_item:n #1
31757 { \iow_newline: > ~ \c_space_tl \exp_not:N \tl_to_str:n { {#1} } }
31758 \cs_new:Npx \msg_show_item_unbraced:n #1
31759 { \iow_newline: > ~ \c_space_tl \exp_not:N \tl_to_str:n {#1} }
31760 \cs_new:Npx \msg_show_item:nn #1#2
31761 {
31762   \iow_newline: > \use:nn { ~ } { ~ }
31763   \exp_not:N \tl_to_str:n { {#1} }
31764   \use:nn { ~ } { ~ } => \use:nn { ~ } { ~ }
31765   \exp_not:N \tl_to_str:n { {#2} }
31766 }
31767 \cs_new:Npx \msg_show_item_unbraced:nn #1#2
31768 {
31769   \iow_newline: > \use:nn { ~ } { ~ }
31770   \exp_not:N \tl_to_str:n {#1}
31771   \use:nn { ~ } { ~ } => \use:nn { ~ } { ~ }
31772   \exp_not:N \tl_to_str:n {#2}
31773 }

```

(End definition for `\msg_show_item:n` and others. These functions are documented on page 264.)

50.4 Additions to l3prg

```

31774 <@@=bool>

```

`\bool_set_inverse:N` Set to false or true locally or globally.

```

31775 \cs_new_protected:Npn \bool_set_inverse:N #1
31776 { \bool_if:NTF #1 { \bool_set_false:N } { \bool_set_true:N } #1 }
31777 \cs_generate_variant:Nn \bool_set_inverse:N { c }
31778 \cs_new_protected:Npn \bool_gset_inverse:N #1
31779 { \bool_if:NTF #1 { \bool_gset_false:N } { \bool_gset_true:N } #1 }
31780 \cs_generate_variant:Nn \bool_gset_inverse:N { c }

```

(End definition for `\bool_set_inverse:N` and `\bool_gset_inverse:N`. These functions are documented on page 264.)

\s__bool_mark Internal scan marks.

\s__bool_stop 31781 \scan_new:N \s__bool_mark
31782 \scan_new:N \s__bool_stop

(End definition for \s__bool_mark and \s__bool_stop.)

\bool_case_true:n For boolean cases the overall idea is the same as for \tl_case:nn(TF) as described in l3tl.

\bool_case_true:nTF 31783 \cs_new:Npn \bool_case_true:nTF
31784 { \exp:w __bool_case:NnTF \c_true_bool }
\bool_case_false:nTF 31785 \cs_new:Npn \bool_case_true:nT #1#2
31786 { \exp:w __bool_case:NnTF \c_true_bool {#1} {#2} { } }
__bool_case:NnTF 31787 \cs_new:Npn \bool_case_true:nF #1
31788 { \exp:w __bool_case:NnTF \c_true_bool {#1} { } }
__bool_case_true:w 31789 \cs_new:Npn \bool_case_true:n #1
31790 { \exp:w __bool_case:NnTF \c_true_bool {#1} { } { } }
__bool_case_false:w 31791 \cs_new:Npn \bool_case_false:nTF
31792 { \exp:w __bool_case:NnTF \c_false_bool }
__bool_case_end:nw 31793 \cs_new:Npn \bool_case_false:nT #1#2
31794 { \exp:w __bool_case:NnTF \c_false_bool {#1} {#2} { } }
31795 \cs_new:Npn \bool_case_false:nF #1
31796 { \exp:w __bool_case:NnTF \c_false_bool {#1} { } }
31797 \cs_new:Npn \bool_case_false:n #1
31798 { \exp:w __bool_case:NnTF \c_false_bool {#1} { } { } }
31799 \cs_new:Npn __bool_case:NnTF #1#2#3#4
31800 {
31801 \bool_if:NTF #1 __bool_case_true:w __bool_case_false:w
31802 #2 #1 { } \s__bool_mark {#3} \s__bool_mark {#4} \s__bool_stop
31803 }
31804 \cs_new:Npn __bool_case_true:w #1#2
31805 {
31806 \bool_if:nTF {#1}
31807 { __bool_case_end:nw {#2} }
31808 { __bool_case_true:w }
31809 }
31810 \cs_new:Npn __bool_case_false:w #1#2
31811 {
31812 \bool_if:nTF {#1}
31813 { __bool_case_false:w }
31814 { __bool_case_end:nw {#2} }
31815 }
31816 \cs_new:Npn __bool_case_end:nw #1#2#3 \s__bool_mark #4#5 \s__bool_stop
31817 { \exp_end: #1 #4 }

(End definition for \bool_case_true:nTF and others. These functions are documented on page 264.)

50.5 Additions to l3prop

31818 <@@=prop>

__prop_use_i_delimit_by_s_stop:nw Functions to gobble up to a scan mark.

31819 \cs_new:Npn __prop_use_i_delimit_by_s_stop:nw #1 #2 \s__prop_stop {#1}

(End definition for __prop_use_i_delimit_by_s_stop:nw.)

`\prop_rand_key_value:N` Contrarily to `clist`, `seq` and `tl`, there is no function to get an item of a `prop` given an integer between 1 and the number of items, so we write the appropriate code. There is no bounds checking because `\int_rand:nn` is always within bounds. The initial `\int_value:w` is stopped by the first `\s__prop` in #1.

```

31820 \cs_new:Npn \prop_rand_key_value:N #1
31821 {
31822   \prop_if_empty:NF #1
31823   {
31824     \exp_after:wN \__prop_rand_item:w
31825     \int_value:w \int_rand:nn { 1 } { \prop_count:N #1 }
31826     #1 \s__prop_stop
31827   }
31828 }
31829 \cs_generate_variant:Nn \prop_rand_key_value:N { c }
31830 \cs_new:Npn \__prop_rand_item:w #1 \s__prop \__prop_pair:wn #2 \s__prop #3
31831 {
31832   \int_compare:nNnF {#1} > 1
31833   { \__prop_use_i_delimit_by_s_stop:nw { \exp_not:n { {#2} {#3} } } }
31834   \exp_after:wN \__prop_rand_item:w
31835   \int_value:w \int_eval:n { #1 - 1 } \s__prop
31836 }

```

(End definition for `\prop_rand_key_value:N` and `__prop_rand_item:w`. This function is documented on page 265.)

50.6 Additions to `l3seq`

```

31837 <@@=seq>

```

`\seq_mapthread_function:NNN` The idea is to first expand both sequences, adding the usual `{ ? \prg_break: } { }` to the end of each one. This is most conveniently done in two steps using an auxiliary function. The mapping then throws away the first tokens of #2 and #5, which for items in both sequences are `\s__seq __seq_item:n`. The function to be mapped are then be applied to the two entries. When the code hits the end of one of the sequences, the break material stops the entire loop and tidy up. This avoids needing to find the count of the two sequences, or worrying about which is longer.

```

31838 \cs_new:Npn \seq_mapthread_function:NNN #1#2#3
31839 { \exp_after:wN \__seq_mapthread_function:wNN #2 \s__seq_stop #1 #3 }
31840 \cs_new:Npn \__seq_mapthread_function:wNN \s__seq #1 \s__seq_stop #2#3
31841 {
31842   \exp_after:wN \__seq_mapthread_function:wNw #2 \s__seq_stop #3
31843   #1 { ? \prg_break: } { }
31844   \prg_break_point:
31845 }
31846 \cs_new:Npn \__seq_mapthread_function:wNw \s__seq #1 \s__seq_stop #2
31847 {
31848   \__seq_mapthread_function:Nnnwnn #2
31849   #1 { ? \prg_break: } { }
31850   \s__seq_stop
31851 }
31852 \cs_new:Npn \__seq_mapthread_function:Nnnwnn #1#2#3#4 \s__seq_stop #5#6
31853 {
31854   \use_none:n #2
31855   \use_none:n #5

```

```

31856     #1 {#3} {#6}
31857     \__seq_mapthread_function:Nnnwnn #1 #4 \s__seq_stop
31858   }
31859   \cs_generate_variant:Nn \seq_mapthread_function:NNN { Nc , c , cc }

```

(End definition for \seq_mapthread_function:NNN and others. This function is documented on page 265.)

\seq_set_filter:NNn Similar to \seq_map_inline:Nn, without a \prg_break_point: because the user's code is performed within the evaluation of a boolean expression, and skipping out of that would break horribly. The __seq_wrap_item:n function inserts the relevant __seq_item:n without expansion in the input stream, hence in the x-expanding assignment.

\seq_gset_filter:NNn
__seq_set_filter:NNNn

```

31860 \cs_new_protected:Npn \seq_set_filter:NNn
31861   { \__seq_set_filter:NNNn \tl_set:Nx }
31862 \cs_new_protected:Npn \seq_gset_filter:NNn
31863   { \__seq_set_filter:NNNn \tl_gset:Nx }
31864 \cs_new_protected:Npn \__seq_set_filter:NNNn #1#2#3#4
31865   {
31866     \__seq_push_item_def:n { \bool_if:nT {#4} { \__seq_wrap_item:n {##1} } }
31867     #1 #2 { #3 }
31868     \__seq_pop_item_def:
31869   }

```

(End definition for \seq_set_filter:NNn, \seq_gset_filter:NNn, and __seq_set_filter:NNNn. These functions are documented on page 265.)

\seq_set_map:NNn Very similar to \seq_set_filter:NNn. We could actually merge the two within a single function, but it would have weird semantics.

\seq_gset_map:NNn
__seq_set_map:NNNn

```

31870 \cs_new_protected:Npn \seq_set_map:NNn
31871   { \__seq_set_map:NNNn \tl_set:Nx }
31872 \cs_new_protected:Npn \seq_gset_map:NNn
31873   { \__seq_set_map:NNNn \tl_gset:Nx }
31874 \cs_new_protected:Npn \__seq_set_map:NNNn #1#2#3#4
31875   {
31876     \__seq_push_item_def:n { \exp_not:N \__seq_item:n {#4} }
31877     #1 #2 { #3 }
31878     \__seq_pop_item_def:
31879   }

```

(End definition for \seq_set_map:NNn, \seq_gset_map:NNn, and __seq_set_map:NNNn. These functions are documented on page 265.)

\seq_set_from_inline_x:Nnn Set __seq_item:n then map it using the loop code.

\seq_gset_from_inline_x:Nnn
__seq_set_from_inline_x:NNNn

```

31880 \cs_new_protected:Npn \seq_set_from_inline_x:Nnn
31881   { \__seq_set_from_inline_x:NNNn \tl_set:Nx }
31882 \cs_new_protected:Npn \seq_gset_from_inline_x:Nnn
31883   { \__seq_set_from_inline_x:NNNn \tl_gset:Nx }
31884 \cs_new_protected:Npn \__seq_set_from_inline_x:NNNn #1#2#3#4
31885   {
31886     \__seq_push_item_def:n { \exp_not:N \__seq_item:n {#4} }
31887     #1 #2 { \s__seq #3 \__seq_item:n }
31888     \__seq_pop_item_def:
31889   }

```

(End definition for \seq_set_from_inline_x:Nnn, \seq_gset_from_inline_x:Nnn, and __seq_set_from_inline_x:NNNn. These functions are documented on page 266.)

```

\seq_set_from_function:NnN Reuse \seq_set_from_inline_x:Nnn.
\seq_gset_from_function:NnN
31890 \cs_new_protected:Npn \seq_set_from_function:NnN #1#2#3
31891 { \seq_set_from_inline_x:Nnn #1 {#2} { #3 {##1} } }
31892 \cs_new_protected:Npn \seq_gset_from_function:NnN #1#2#3
31893 { \seq_gset_from_inline_x:Nnn #1 {#2} { #3 {##1} } }

(End definition for \seq_set_from_function:NnN and \seq_gset_from_function:NnN. These functions
are documented on page 266.)

```

```

\seq_indexed_map_function:NN Similar to \seq_map_function:NN but we keep track of the item index as a ;-delimited
\seq_indexed_map_inline:Nn argument of \__seq_indexed_map:Nw.
  \__seq_indexed_map:nNN
  \__seq_indexed_map:Nw
31894 \cs_new:Npn \seq_indexed_map_function:NN #1#2
31895 {
31896   \__seq_indexed_map:NN #1#2
31897   \prg_break_point:Nn \seq_map_break: { }
31898 }
31899 \cs_new_protected:Npn \seq_indexed_map_inline:Nn #1#2
31900 {
31901   \int_gincr:N \g__kernel_prg_map_int
31902   \cs_gset_protected:cpn
31903     { \__seq_map_ \int_use:N \g__kernel_prg_map_int :w } ##1##2 {#2}
31904   \exp_args:Nnc \__seq_indexed_map:NN #1
31905     { \__seq_map_ \int_use:N \g__kernel_prg_map_int :w }
31906   \prg_break_point:Nn \seq_map_break:
31907     { \int_gdecr:N \g__kernel_prg_map_int }
31908 }
31909 \cs_new:Npn \__seq_indexed_map:NN #1#2
31910 {
31911   \exp_after:wN \__seq_indexed_map:Nw
31912   \exp_after:wN #2
31913   \int_value:w 1
31914   \exp_after:wN \use_i:nn
31915   \exp_after:wN ;
31916   #1
31917   \prg_break: \__seq_item:n { } \prg_break_point:
31918 }
31919 \cs_new:Npn \__seq_indexed_map:Nw #1#2 ; #3 \__seq_item:n #4
31920 {
31921   #3
31922   #1 {#2} {#4}
31923   \exp_after:wN \__seq_indexed_map:Nw
31924   \exp_after:wN #1
31925   \int_value:w \int_eval:w 1 + #2 ;
31926 }

(End definition for \seq_indexed_map_function:NN and others. These functions are documented on
page 266.)

```

50.7 Additions to l3sys

```

31927 <@@=sys>
\c_sys_engine_version_str Various different engines, various different ways to extract the data!
31928 \str_const:Nx \c_sys_engine_version_str
31929 {

```

```

31930 \str_case:on \c_sys_engine_str
31931 {
31932   { pdftex }
31933   {
31934     \fp_eval:n { round(\int_use:N \tex_pdftexversion:D / 100 , 2) }
31935     .
31936     \tex_pdftexrevision:D
31937   }
31938   { ptex }
31939   {
31940     \cs_if_exist:NT \tex_ptexversion:D
31941     {
31942       p
31943       \int_use:N \tex_ptexversion:D
31944       .
31945       \int_use:N \tex_ptexminorversion:D
31946       \tex_ptexrevision:D
31947       -
31948       \int_use:N \tex_epTeXversion:D
31949     }
31950   }
31951   { luatex }
31952   {
31953     \fp_eval:n { round(\int_use:N \tex_luatexversion:D / 100, 2) }
31954     .
31955     \tex_luatexrevision:D
31956   }
31957   { uptex }
31958   {
31959     \cs_if_exist:NT \tex_ptexversion:D
31960     {
31961       p
31962       \int_use:N \tex_ptexversion:D
31963       .
31964       \int_use:N \tex_ptexminorversion:D
31965       \tex_ptexrevision:D
31966       -
31967       u
31968       \int_use:N \tex_uptexversion:D
31969       \tex_uptexrevision:D
31970       -
31971       \int_use:N \tex_epTeXversion:D
31972     }
31973   }
31974   { xetex }
31975   {
31976     \int_use:N \tex_XeTeXversion:D
31977     \tex_XeTeXrevision:D
31978   }
31979 }
31980 }

```

(End definition for `\c_sys_engine_version_str`. This variable is documented on page [267](#).)

50.8 Additions to l3file

31981 `<@@=ior>`

`\ior_shell_open:Nn` Actually much easier than either the standard open or input versions! When calling `__kernel_ior_open:Nn` the file the pipe is added to signal a shell command, but the quotes are not added yet—they are added later by `__kernel_file_name_quote:n`.

```
31982 \cs_new_protected:Npn \ior_shell_open:Nn #1#2
31983 {
31984   \sys_if_shell:TF
31985     { \exp_args:No \__ior_shell_open:nN { \tl_to_str:n {#2} } #1 }
31986     { \__kernel_msg_error:nn { kernel } { pipe-failed } }
31987 }
31988 \cs_new_protected:Npn \__ior_shell_open:nN #1#2
31989 {
31990   \tl_if_in:nnTF {#1} { " }
31991   {
31992     \__kernel_msg_error:nnx
31993       { kernel } { quote-in-shell } {#1}
31994   }
31995   { \__kernel_ior_open:Nn #2 { |#1 } }
31996 }
31997 \__kernel_msg_new:nnnn { kernel } { pipe-failed }
31998 { Cannot~run~piped~system~commands. }
31999 {
32000   LaTeX~tried~to~call~a~system~process~but~this~was~not~possible.\\
32001   Try~the~"---shell-escape"~(or~"---enable-pipes")~option.
32002 }
```

(End definition for `\ior_shell_open:Nn` and `__ior_shell_open:nN`. This function is documented on page 262.)

50.8.1 Building a token list

32003 `<@@=tl>`

Between `\tl_build_begin:N <tl var>` and `\tl_build_end:N <tl var>`, the `<tl var>` has the structure

```
\exp_end: ... \exp_end: \__tl_build_last:NNn <assignment> <next tl>
{<left>} <right>
```

where `<right>` is not braced. The “data” it represents is `<left>` followed by the “data” of `<next tl>` followed by `<right>`. The `<next tl>` is a token list variable whose name is that of `<tl var>` followed by `'`. There are between 0 and 4 `\exp_end:` to keep track of when `<left>` and `<right>` should be put into the `<next tl>`. The `<assignment>` is `\cs_set_nopar:Npx` if the variable is local, and `\cs_gset_nopar:Npx` if it is global.

`\tl_build_begin:N` First construct the `<next tl>`: using a prime here conflicts with the usual `expl3` convention
`\tl_build_gbegin:N` but we need a name that can be derived from `#1` without any external data such as a
`__tl_build_begin:NN` counter. Empty that `<next tl>` and setup the structure. The local and global versions
`__tl_build_begin:NNN` only differ by a single function `\cs_(g)set_nopar:Npx` used for all assignments: this is
important because only that function is stored in the `<tl var>` and `<next tl>` for subsequent
assignments. In principle `__tl_build_begin:NNN` could use `\tl_(g)clear_new:N` to
empty `#1` and make sure it is defined, but logging the definition does not seem useful so
we just do `#3 #1 {}` to clear it locally or globally as appropriate.


```

32004 \cs_new_protected:Npn \tl_build_begin:N #1
32005 { \__tl_build_begin:NN \cs_set_nopar:Npx #1 }
32006 \cs_new_protected:Npn \tl_build_gbegin:N #1
32007 { \__tl_build_begin:NN \cs_gset_nopar:Npx #1 }
32008 \cs_new_protected:Npn \__tl_build_begin:NN #1#2
32009 { \exp_args:Nc \__tl_build_begin:NNN { \cs_to_str:N #2 ' } #2 #1 }
32010 \cs_new_protected:Npn \__tl_build_begin:NNN #1#2#3
32011 {
32012     #3 #1 { }
32013     #3 #2
32014     {
32015         \exp_not:n { \exp_end: \exp_end: \exp_end: \exp_end: }
32016         \exp_not:n { \__tl_build_last:NNn #3 #1 { } }
32017     }
32018 }

```

(End definition for `\tl_build_begin:N` and others. These functions are documented on page 268.)

`\tl_build_clear:N` The `begin` and `gbegin` functions already clear enough to make the token list variable effectively empty. Eventually the `begin` and `gbegin` functions should check that `#1` is empty or undefined, while the `clear` and `gclear` functions ought to empty `#1`, `#1'` and so on, similar to `\tl_build_end:N`. This only affects memory usage.

```

32019 \cs_new_eq:NN \tl_build_clear:N \tl_build_begin:N
32020 \cs_new_eq:NN \tl_build_gclear:N \tl_build_gbegin:N

```

(End definition for `\tl_build_clear:N` and `\tl_build_gclear:N`. These functions are documented on page 268.)

`\tl_build_put_right:Nn` Similar to `\tl_put_right:Nn`, but apply `\exp:w` to `#1`. Most of the time this just removes one `\exp_end:`. When there are none left, `__tl_build_last:NNn` is expanded instead.

`\tl_build_put_right:Nx` It resets the definition of the `\tl var` by ending the `\exp_not:n` and the definition early.

`\tl_build_gput_right:Nn` Then it makes sure the `\next tl` (its argument `#1`) is set-up and starts a new definition.

`\tl_build_gput_right:Nx` Then `__tl_build_put:nn` and `__tl_build_put:nw` place the `\left` part of the original `\tl var` as appropriate for the definition of the `\next tl` (the `\right` part is left in the right place without ever becoming a macro argument). We use `\exp_after:wN` rather than some `\exp_args:No` to avoid reading arguments that are likely very long token lists. We use `\cs_(g)set_nopar:Npx` rather than `\tl_(g)set:Nx` partly for the same reason and partly because the assignments are interrupted by brace tricks, which implies that the assignment does not simply set the token list to an x-expansion of the second argument.

```

32021 \cs_new_protected:Npn \tl_build_put_right:Nn #1#2
32022 {
32023     \cs_set_nopar:Npx #1
32024     { \exp_after:wN \exp_not:n \exp_after:wN { \exp:w #1 #2 } }
32025 }
32026 \cs_new_protected:Npn \tl_build_put_right:Nx #1#2
32027 {
32028     \cs_set_nopar:Npx #1
32029     { \exp_after:wN \exp_not:n \exp_after:wN { \exp:w #1 } #2 }
32030 }
32031 \cs_new_protected:Npn \tl_build_gput_right:Nn #1#2
32032 {
32033     \cs_gset_nopar:Npx #1
32034     { \exp_after:wN \exp_not:n \exp_after:wN { \exp:w #1 #2 } }

```

```

32035 }
32036 \cs_new_protected:Npn \tl_build_gput_right:Nx #1#2
32037 {
32038   \cs_gset_nopar:Npx #1
32039   { \exp_after:wN \exp_not:n \exp_after:wN { \exp:w #1 } #2 }
32040 }
32041 \cs_new_protected:Npn \__tl_build_last:NNn #1#2
32042 {
32043   \if_false: { { \fi:
32044     \exp_end: \exp_end: \exp_end: \exp_end:
32045     \__tl_build_last:NNn #1 #2 { }
32046   }
32047 }
32048 \if_meaning:w \c_empty_tl #2
32049   \__tl_build_begin:NN #1 #2
32050 \fi:
32051 #1 #2
32052 {
32053   \exp_after:wN \exp_not:n \exp_after:wN
32054   {
32055     \exp:w \if_false: } } \fi:
32056   \exp_after:wN \__tl_build_put:nn \exp_after:wN {#2}
32057 }
32058 \cs_new_protected:Npn \__tl_build_put:nn #1#2 { \__tl_build_put:nw {#2} #1 }
32059 \cs_new_protected:Npn \__tl_build_put:nw #1#2 \__tl_build_last:NNn #3#4#5
32060 { #2 \tl_build_last:NNn #3 #4 { #1 #5 } }

```

`\tl_build_put_left:Nn` See `\tl_build_put_right:Nn` for all the machinery. We could easily provide `\tl_build_put_left:Nx` `\tl_build_put_left_right:Nnn`, by just add the `\right` material after the `\left` in the `\tl_build_gput_left:Nn` x-expanding assignment.

(End definition for `\tl_build_put_left:Nn`, `\tl_build_gput_left:Nn`, and `__tl_build_put_left:NNn`.
These functions are documented on page 269.)

the assignment as we go, which enables us to expand the $\langle next\ tl \rangle$ at the right place. The various $\langle right \rangle$ parts are eventually picked up in one last $\backslash exp_not:n$, with a brace trick to wrap all the $\langle right \rangle$ parts together.

```

32078 \cs_new_protected:Npn \tl_build_get:NN
32079 { \__tl_build_get:NNN \tl_set:Nx }
32080 \cs_new_protected:Npn \__tl_build_get:NNN #1#2#3
32081 { #1 #3 { \if_false: { \fi: \exp_after:wN \__tl_build_get:w #2 } } }
32082 \cs_new:Npn \__tl_build_get:w #1 \__tl_build_last:NNn #2#3#4
32083 {
32084   \exp_not:n {#4}
32085   \if_meaning:w \c_empty_tl #3
32086     \exp_after:wN \__tl_build_get_end:w
32087   \fi:
32088   \exp_after:wN \__tl_build_get:w #3
32089 }
32090 \cs_new:Npn \__tl_build_get_end:w #1#2#3
32091 { \exp_after:wN \exp_not:n \exp_after:wN { \if_false: } \fi: }

```

(End definition for $\backslash tl_build_get:NN$ and others. This function is documented on page 269.)

$\backslash tl_build_end:N$ Get the data then clear the $\langle next\ tl \rangle$ recursively until finding an empty one. It is perhaps
 $\backslash tl_build_gend:N$ wasteful to repeatedly use $\backslash cs_to_sr:N$. The local/global scope is checked by $\backslash tl_set:Nx$ or $\backslash tl_gset:Nx$.
 $\backslash _tl_build_end_loop:NN$

```

32092 \cs_new_protected:Npn \tl_build_end:N #1
32093 {
32094   \__tl_build_get:NNN \tl_set:Nx #1 #1
32095   \exp_args:Nc \__tl_build_end_loop:NN { \cs_to_str:N #1 ' } \tl_clear:N
32096 }
32097 \cs_new_protected:Npn \tl_build_gend:N #1
32098 {
32099   \__tl_build_get:NNN \tl_gset:Nx #1 #1
32100   \exp_args:Nc \__tl_build_end_loop:NN { \cs_to_str:N #1 ' } \tl_gclear:N
32101 }
32102 \cs_new_protected:Npn \__tl_build_end_loop:NN #1#2
32103 {
32104   \if_meaning:w \c_empty_tl #1
32105     \exp_after:wN \use_none:nnnnn
32106   \fi:
32107   #2 #1
32108   \exp_args:Nc \__tl_build_end_loop:NN { \cs_to_str:N #1 ' } #2
32109 }

```

(End definition for $\backslash tl_build_end:N$, $\backslash tl_build_gend:N$, and $\backslash _tl_build_end_loop:NN$. These functions are documented on page 269.)

50.8.2 Other additions to $\backslash l3tl$

$\backslash tl_range_braced:Nnn$ For the braced version $\backslash _tl_range_braced:w$ sets up $\backslash _tl_range_collect_braced:w$
 $\backslash tl_range_braced:cnn$ which stores items one by one in an argument after the semicolon. The unbraced version
 $\backslash tl_range_braced:nnn$ is almost identical. The version preserving braces and spaces starts by deleting spaces
 $\backslash tl_range_unbraced:Nnn$ before the argument to avoid collecting them, and sets up $\backslash _tl_range_collect:nn$
 $\backslash tl_range_unbraced:cnn$ with a first argument of the form $\{ \{ \langle collected \rangle \} \langle tokens \rangle \}$, whose head is the collected
 $\backslash tl_range_unbraced:nnn$
 $\backslash _tl_range_braced:w$
 $\backslash _tl_range_collect_braced:w$
 $\backslash _tl_range_unbraced:w$
 $\backslash _tl_range_collect_unbraced:w$

tokens and whose tail is what remains of the original token list. This form makes it easier to move tokens to the *collected* tokens.

```

32110 \cs_new:Npn \tl_range_braced:Nnn { \exp_args:No \tl_range_braced:nnn }
32111 \cs_generate_variant:Nn \tl_range_braced:Nnn { c }
32112 \cs_new:Npn \tl_range_braced:nnn { \__tl_range:Nnnn \__tl_range_braced:w }
32113 \cs_new:Npn \tl_range_unbraced:Nnn
32114   { \exp_args:No \tl_range_unbraced:nnn }
32115 \cs_generate_variant:Nn \tl_range_unbraced:Nnn { c }
32116 \cs_new:Npn \tl_range_unbraced:nnn
32117   { \__tl_range:Nnnn \__tl_range_unbraced:w }
32118 \cs_new:Npn \__tl_range_braced:w #1 ; #2
32119   { \__tl_range_collect_braced:w #1 ; { } #2 }
32120 \cs_new:Npn \__tl_range_unbraced:w #1 ; #2
32121   { \__tl_range_collect_unbraced:w #1 ; { } #2 }
32122 \cs_new:Npn \__tl_range_collect_braced:w #1 ; #2#3
32123   {
32124     \if_int_compare:w #1 > 1 \exp_stop_f:
32125       \exp_after:wN \__tl_range_collect_braced:w
32126       \int_value:w \int_eval:n { #1 - 1 } \exp_after:wN ;
32127     \fi:
32128     { #2 {#3} }
32129   }
32130 \cs_new:Npn \__tl_range_collect_unbraced:w #1 ; #2#3
32131   {
32132     \if_int_compare:w #1 > 1 \exp_stop_f:
32133       \exp_after:wN \__tl_range_collect_unbraced:w
32134       \int_value:w \int_eval:n { #1 - 1 } \exp_after:wN ;
32135     \fi:
32136     { #2 #3 }
32137   }

```

(End definition for `\tl_range_braced:Nnn` and others. These functions are documented on page 268.)

50.9 Additions to l3token

`\c_catcode_active_space_tl` While `\char_generate:nn` can produce active characters in some engines it cannot in general. It would be possible to simply change the catcode of space but then the code would need to avoid all spaces, making it quite unreadable. Instead we use the primitive `\tex_lowercase:D` trick.

```

32138 \group_begin:
32139   \char_set_catcode_active:N *
32140   \char_set_lccode:nn { '*' } { '\ }
32141   \tex_lowercase:D { \tl_const:Nn \c_catcode_active_space_tl { * } }
32142 \group_end:

```

(End definition for `\c_catcode_active_space_tl`. This variable is documented on page 269.)

```

32143 <@@=peek>

```

`\l_peek_collect_tl`

```

32144 \tl_new:N \l_peek_collect_tl

```

(End definition for `\l_peek_collect_tl`.)

```

\peek_catcode_collect_inline:Nn
\peek_charcode_collect_inline:Nn
\peek_meaning_collect_inline:Nn
  \__peek_collect:NNn
  \__peek_collect_true:w
\__peek_collect_remove:nw
  \__peek_collect:N

```

Most of the work is done by `__peek_execute_branches_...`, which calls either `__peek_true:w` or `__peek_false:w` according to whether the next token `\l_peek_token` matches the search token (stored in `\l_peek_search_token` and `\l_peek_search_tl`). Here, in the true case we run `__peek_collect_true:w`, which generally calls `__peek_collect:N` to store the peeked token into `\l_peek_collect_tl`, except in special non-N-type cases (begin-group, end-group, or space), where a frozen token is stored. The true branch calls `__peek_execute_branches_...` to fetch more matching tokens. Once there are no more, `__peek_false_aux:n` closes the safe-align group and runs the user's inline code.

```

32145 \cs_new_protected:Npn \peek_catcode_collect_inline:Nn
32146 { \__peek_collect:NNn \__peek_execute_branches_catcode: }
32147 \cs_new_protected:Npn \peek_charcode_collect_inline:Nn
32148 { \__peek_collect:NNn \__peek_execute_branches_charcode: }
32149 \cs_new_protected:Npn \peek_meaning_collect_inline:Nn
32150 { \__peek_collect:NNn \__peek_execute_branches_meaning: }
32151 \cs_new_protected:Npn \__peek_collect:NNn #1#2#3
32152 {
32153   \group_align_safe_begin:
32154   \cs_set_eq:NN \l_peek_search_token #2
32155   \tl_set:Nn \l_peek_search_tl {#2}
32156   \tl_clear:N \l_peek_collect_tl
32157   \cs_set:Npn \__peek_false:w
32158   { \exp_args:No \__peek_false_aux:n \l_peek_collect_tl }
32159   \cs_set:Npn \__peek_false_aux:n ##1
32160   {
32161     \group_align_safe_end:
32162     #3
32163   }
32164   \cs_set_eq:NN \__peek_true:w \__peek_collect_true:w
32165   \cs_set:Npn \__peek_true_aux:w { \peek_after:Nw #1 }
32166   \__peek_true_aux:w
32167 }
32168 \cs_new_protected:Npn \__peek_collect_true:w
32169 {
32170   \if_case:w
32171     \if_catcode:w \exp_not:N \l_peek_token { 1 \exp_stop_f: \fi:
32172     \if_catcode:w \exp_not:N \l_peek_token } 2 \exp_stop_f: \fi:
32173     \if_meaning:w \l_peek_token \c_space_token 3 \exp_stop_f: \fi:
32174     0 \exp_stop_f:
32175     \exp_after:wN \__peek_collect:N
32176   \or: \__peek_collect_remove:nw { \c_group_begin_token }
32177   \or: \__peek_collect_remove:nw { \c_group_end_token }
32178   \or: \__peek_collect_remove:nw { ~ }
32179   \fi:
32180 }
32181 \cs_new_protected:Npn \__peek_collect:N #1
32182 {
32183   \tl_put_right:Nn \l_peek_collect_tl {#1}
32184   \__peek_true_aux:w
32185 }
32186 \cs_new_protected:Npn \__peek_collect_remove:nw #1
32187 {
32188   \tl_put_right:Nn \l_peek_collect_tl {#1}

```

```

32189     \exp_after:wN \__peek_true_remove:w
32190   }

```

(End definition for \peek_catcode_collect_inline:Nn and others. These functions are documented on page 270.)

```

32191 \</initex | package>

```

51 l3deprecation implementation

```

32192 <*initex | package>
32193 <*kernel>
32194 <@@=deprecation>

```

51.1 Helpers and variables

\l_deprecation_grace_period_bool This is set to true when the deprecated command that is being defined is in its grace period, meaning between the time it becomes an error by default and the time 6 months later where even undo-recent-deprecations stops restoring it.

```

32195 \bool_new:N \l_deprecation_grace_period_bool

```

(End definition for \l_deprecation_grace_period_bool.)

\s_deprecation_mark Internal scan marks.

```

\s_deprecation_stop 32196 \scan_new:N \s_deprecation_mark
32197 \scan_new:N \s_deprecation_stop

```

(End definition for \s_deprecation_mark and \s_deprecation_stop.)

_deprecation_date_compare:nNnTF Expects #1 and #3 to be dates in the format YYYY-MM-DD (but accepts YYYY or YYYY-MM too, filling in zeros for the missing data). Compares them using #2 (one of <, =, >).

```

\_deprecation_date_compare_aux:w 32198 \cs_new:Npn \_deprecation_date_compare:nNnTF #1#2#3
32199 { \_deprecation_date_compare_aux:w #1 -0-0- \s_deprecation_mark #2 #3 -0-0- \s_depreca
32200 \cs_new:Npn \_deprecation_date_compare_aux:w
32201 #1 - #2 - #3 - #4 \s_deprecation_mark #5 #6 - #7 - #8 - #9 \s_deprecation_stop
32202 {
32203   \int_compare:nNnTF {#1} = {#6}
32204   {
32205     \int_compare:nNnTF {#2} = {#7}
32206     { \int_compare:nNnTF {#3} #5 {#8} }
32207     { \int_compare:nNnTF {#2} #5 {#7} }
32208   }
32209   { \int_compare:nNnTF {#1} #5 {#6} }
32210 }

```

(End definition for _deprecation_date_compare:nNnTF and _deprecation_date_compare_aux:w.)

\g_kernel_deprecation_undo_recent_bool

```

32211 \bool_new:N \g_kernel_deprecation_undo_recent_bool

```

(End definition for \g_kernel_deprecation_undo_recent_bool.)

```

\__deprecation_not_yet_deprecated:nTF
\__deprecation_minus_six_months:w
Receives a deprecation  $\langle date \rangle$  and runs the true (false) branch if the expl3 date is earlier
(later) than  $\langle date \rangle$ . If undo-recent-deprecations is used we subtract 6 months to the
expl3 date (equivalently add 6 months to the  $\langle date \rangle$ ). In addition, if the expl3 date is
between  $\langle date \rangle$  and  $\langle date \rangle$  plus 6 months, \l__deprecation_grace_period_bool is set
to true, otherwise false.

32212 \cs_new_protected:Npn \__deprecation_not_yet_deprecated:nTF #1
32213 {
32214   \bool_set_false:N \l__deprecation_grace_period_bool
32215   \exp_args:No \__deprecation_date_compare:nNnTF { \ExplLoaderFileDate } < {#1}
32216   { \use_i:nn }
32217   {
32218     \exp_args:Nf \__deprecation_date_compare:nNnTF
32219     {
32220       \exp_after:wN \__deprecation_minus_six_months:w
32221       \ExplLoaderFileDate -0-0- \s__deprecation_stop
32222     } < {#1}
32223     {
32224       \bool_set_true:N \l__deprecation_grace_period_bool
32225       \bool_if:NTF \g__kernel_deprecation_undo_recent_bool
32226     }
32227     { \use_ii:nn }
32228   }
32229 }
32230 \cs_new:Npn \__deprecation_minus_six_months:w #1 - #2 - #3 - #4 \s__deprecation_stop
32231 {
32232   \int_compare:nNnTF {#2} > 6
32233   { #1 - \int_eval:n { #2 - 6 } - #3 }
32234   { \int_eval:n { #1 - 1 } - \int_eval:n { #2 + 6 } - #3 }
32235 }

```

(End definition for **__deprecation_not_yet_deprecated:nTF** and **__deprecation_minus_six_months:w**.)

51.2 Patching definitions to deprecate

```

\__kernel_patch_deprecation:nnNnpn { $\langle date \rangle$ } { $\langle replacement \rangle$ } { $\langle definition \rangle$ }
{ $\langle function \rangle$ } { $\langle parameters \rangle$ } { $\langle code \rangle$ }

```

defines the $\langle function \rangle$ to produce a warning and run its $\langle code \rangle$, or to produce an error and not run any $\langle code \rangle$, depending on the expl3 date.

- If the expl3 date is less than the $\langle date \rangle$ (plus 6 months in case **undo-recent-deprecations** is used) then we define the $\langle function \rangle$ to produce a warning and run its code. The warning is actually suppressed in two cases:
 - if neither **undo-recent-deprecations** nor **enable-debug** are in effect we may be in an end-user's document so it is suppressed;
 - if the command is expandable then we cannot produce a warning.
- Otherwise, we define the $\langle function \rangle$ to produce an error.

In both cases we additionally make **\debug_on:n {deprecation}** turn the $\langle function \rangle$ into an **\outer** error, and **\debug_off:n {deprecation}** restore whatever the behaviour was without **\debug_on:n {deprecation}**.

In later sections we use the `\l3doc` key `deprecated` with a date equal to that $\langle date \rangle$ plus 6 months, so that `\l3doc` will complain if we forget to remove the stale $\langle parameters \rangle$ and $\{ \langle code \rangle \}$.

In the explanations below, $\langle definition \rangle$ $\langle function \rangle$ $\langle parameters \rangle$ $\{ \langle code \rangle \}$ or assignments that only differ in the scope of the $\langle definition \rangle$ will be called “the standard definition”.

```

\__kernel_patch_deprecation:nnNNpN (The parameter text is grabbed using #5#.) The arguments of \__kernel_deprecation_
\__deprecation_patch_aux:nnNNnn code:nn are run upon \debug_on:n {deprecation} and \debug_off:n {deprecation},
\__deprecation_warn_once:nnNnn respectively. In both scenarios we the  $\langle function \rangle$  may be \outer so we undefine it with
\__deprecation_patch_aux:Nn \tex_let:D before redefining it, with \__kernel_deprecation_error:Nnn or with some
\__deprecation_just_error:nnNN code added shortly.

```

Then check the date (taking into account `undo-recent-deprecations`) to see if the command should be deprecated right away (`false` branch of `__deprecation_not_yet_deprecated:nTF`), in which case `__deprecation_just_error:nnNN` makes $\langle function \rangle$ into an error (not `\outer`), ignoring its $\langle parameters \rangle$ and $\langle code \rangle$ completely.

Otherwise distinguish cases where we should give a warning from those where we shouldn't: warnings can only happen for protected commands, and we only want them if either `undo-recent-deprecations` or `enable-debug` is in force, not for standard users.

```

32236 \cs_new_protected:Npn \__kernel_patch_deprecation:nnNNpN #1#2#3#4#5#
32237 { \__deprecation_patch_aux:nnNNnn {#1} {#2} #3 #4 {#5} }
32238 \cs_new_protected:Npn \__deprecation_patch_aux:nnNNnn #1#2#3#4#5#6
32239 {
32240   \__kernel_deprecation_code:nn
32241   {
32242     \tex_let:D #4 \scan_stop:
32243     \__kernel_deprecation_error:Nnn #4 {#2} {#1}
32244   }
32245   { \tex_let:D #4 \scan_stop: }
32246   \__deprecation_not_yet_deprecated:nTF {#1}
32247   {
32248     \bool_if:nTF
32249     {
32250       \cs_if_eq_p:NN #3 \cs_gset_protected:Npn &&
32251       \__kernel_if_debug:TF
32252       { \c_true_bool } { \g__kernel_deprecation_undo_recent_bool }
32253     }
32254     { \__deprecation_warn_once:nnNNnn {#1} {#2} #4 {#5} {#6} }
32255     { \__deprecation_patch_aux:Nn #3 { #4 #5 {#6} } }
32256   }
32257   { \__deprecation_just_error:nnNN {#1} {#2} #3 #4 }
32258 }

```

In case we want a warning, the $\langle function \rangle$ is defined to produce such a warning without grabbing any argument, then redefine itself to the standard definition that the $\langle function \rangle$ should have, with arguments, and call that definition. The `x-type` expansion and `\exp_not:n` avoid needing to double the `#`, which we could not do anyways. We then deal with the code for `\debug_off:n {deprecation}`: presumably someone doing that does not need the warning so we simply do the standard definition.

```

32259 \cs_new_protected:Npn \__deprecation_warn_once:nnNNnn #1#2#3#4#5
32260 {
32261   \cs_gset_protected:Npx #3

```



```

32262     {
32263         \__kernel_if_debug:TF
32264         {
32265             \exp_not:N \__kernel_msg_warning:nnxxx
32266             { kernel } { deprecated-command }
32267             {#1}
32268             { \token_to_str:N #3 }
32269             { \tl_to_str:n {#2} }
32270         }
32271     { }
32272     \exp_not:n { \cs_gset_protected:Npn #3 #4 {#5} }
32273     \exp_not:N #3
32274 }
32275 \__kernel_deprecation_code:nn { }
32276 { \cs_set_protected:Npn #3 #4 {#5} }
32277 }

```

In case we want neither warning nor error, the $\langle function \rangle$ is given its standard definition. Here #1 is $\backslash\text{cs_new:Npn}$ or $\backslash\text{cs_new_protected:Npn}$ and #2 is $\langle function \rangle$ $\langle parameters \rangle$ $\{ \langle code \rangle \}$, so #1#2 performs the assignment. For $\backslash\text{debug_off:n} \{ \text{deprecation} \}$ we want to use the same assignment but with a different scope, hence the $\backslash\text{cs_if_eq:NNTF}$ test.

```

32278 \cs_new_protected:Npn \__deprecation_patch_aux:Nn #1#2
32279 {
32280     #1 #2
32281     \cs_if_eq:NNTF #1 \cs_gset_protected:Npn
32282     { \__kernel_deprecation_code:nn { } { \cs_set_protected:Npn #2 } }
32283     { \__kernel_deprecation_code:nn { } { \cs_set:Npn #2 } }
32284 }

```

Finally, if we want an error we reuse the same $\backslash\text{__deprecation_patch_aux:Nn}$ as the previous case. Indeed, we want $\backslash\text{debug_off:n} \{ \text{deprecation} \}$ to make the $\langle function \rangle$ into an error, just like it is by default. The error is expandable or not, and the last argument of the error message is empty or is **grace** to denote the case where we are in the 6 month grace period, in which case the error message is more detailed.

```

32285 \cs_new_protected:Npn \__deprecation_just_error:nnNN #1#2#3#4
32286 {
32287     \exp_args:NNx \__deprecation_patch_aux:Nn #3
32288     {
32289         \exp_not:N #4
32290         {
32291             \cs_if_eq:NNTF #3 \cs_gset_protected:Npn
32292             { \exp_not:N \__kernel_msg_error:nnnnnn }
32293             { \exp_not:N \__kernel_msg_expandable_error:nnnnnn }
32294             { kernel } { deprecated-command }
32295             {#1}
32296             { \token_to_str:N #4 }
32297             { \tl_to_str:n {#2} }
32298             { \bool_if:NT \l__deprecation_grace_period_bool { grace } }
32299         }
32300     }
32301 }

```

(End definition for $\backslash\text{__kernel_patch_deprecation:nnNNpn}$ and others.)

`_kernel_deprecation_error:Nnn` The `\outer` definition here ensures the command cannot appear in an argument. Use this auxiliary on all commands that have been removed since 2015.

```

32302 \cs_new_protected:Npn \_kernel_deprecation_error:Nnn #1#2#3
32303 {
32304   \tex_protected:D \tex_outer:D \tex_edef:D #1
32305   {
32306     \exp_not:N \_kernel_msg_expandable_error:nnnnn
32307     { kernel } { deprecated-command }
32308     { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
32309     \exp_not:N \_kernel_msg_error:nnxxx
32310     { kernel } { deprecated-command }
32311     { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
32312   }
32313 }

```

(End definition for `_kernel_deprecation_error:Nnn`.)

```

32314 \_kernel_msg_new:nnn { kernel } { deprecated-command }
32315 {
32316   \tl_if_blank:nF {#3} { Use~ \tl_trim_spaces:n {#3} ~not~ }
32317   #2~deprecated-on~#1.
32318   \str_if_eq:nnT {#4} { grace }
32319   {
32320     \c_space_tl
32321     For~6~months~after~that~date~one~can~restore~a~deprecated~
32322     command~by~loading~the~expl3~package~with~the~option~
32323     'undo-recent-deprecations'.
32324   }
32325 }

```

51.3 Removed functions

`_deprecation_old_protected:Nnn` Short-hands for old commands whose definition does not matter anymore, i.e., commands
`_deprecation_old:Nnn` past the grace period.

```

32326 \cs_new_protected:Npn \_deprecation_old_protected:Nnn #1#2#3
32327 {
32328   \_kernel_patch_deprecation:nnNNpn {#3} {#2}
32329   \cs_gset_protected:Npn #1 { }
32330 }
32331 \cs_new_protected:Npn \_deprecation_old:Nnn #1#2#3
32332 {
32333   \_kernel_patch_deprecation:nnNNpn {#3} {#2}
32334   \cs_gset:Npn #1 { }
32335 }
32336 \_deprecation_old:Nnn \box_resize:Nnn
32337 { \box_resize_to_wd_and_ht_plus_dp:Nnn } { 2019-01-01 }
32338 \_deprecation_old:Nnn \box_use_clear:N
32339 { \box_use_drop:N } { 2019-01-01 }
32340 \_deprecation_old:Nnn \c_job_name_tl
32341 { \c_sys_jobname_str } { 2017-01-01 }
32342 \_deprecation_old:Nnn \c_minus_one
32343 { -1 } { 2019-01-01 }
32344 \_deprecation_old:Nnn \dim_case:nnn
32345 { \dim_case:nnF } { 2015-07-14 }

```

```

32346 \__deprecation_old:Nnn \file_add_path:nN
32347 { \file_get_full_name:nN } { 2019-01-01 }
32348 \__deprecation_old_protected:Nnn \file_if_exist_input:nT
32349 { \file_if_exist:nT and~ \file_input:n } { 2018-03-05 }
32350 \__deprecation_old_protected:Nnn \file_if_exist_input:nTF
32351 { \file_if_exist:nT and~ \file_input:n } { 2018-03-05 }
32352 \__deprecation_old:Nnn \file_list:
32353 { \file_log_list: } { 2019-01-01 }
32354 \__deprecation_old:Nnn \file_path_include:n
32355 { \seq_put_right:Nn \l_file_search_path_seq } { 2019-01-01 }
32356 \__deprecation_old:Nnn \file_path_remove:n
32357 { \seq_remove_all:Nn \l_file_search_path_seq } { 2019-01-01 }
32358 \__deprecation_old:Nnn \g_file_current_name_tl
32359 { \g_file_curr_name_str } { 2019-01-01 }
32360 \__deprecation_old:Nnn \int_case:nnn
32361 { \int_case:nnF } { 2015-07-14 }
32362 \__deprecation_old:Nnn \int_from_binary:n
32363 { \int_from_bin:n } { 2016-01-05 }
32364 \__deprecation_old:Nnn \int_from_hexadecimal:n
32365 { \int_from_hex:n } { 2016-01-05 }
32366 \__deprecation_old:Nnn \int_from_octal:n
32367 { \int_from_oct:n } { 2016-01-05 }
32368 \__deprecation_old:Nnn \int_to_binary:n
32369 { \int_to_bin:n } { 2016-01-05 }
32370 \__deprecation_old:Nnn \int_to_hexadecimal:n
32371 { \int_to_hex:n } { 2016-01-05 }
32372 \__deprecation_old:Nnn \int_to_octal:n
32373 { \int_to_oct:n } { 2016-01-05 }
32374 \__deprecation_old_protected:Nnn \ior_get_str:NN
32375 { \ior_str_get:NN } { 2018-03-05 }
32376 \__deprecation_old:Nnn \ior_list_streams:
32377 { \ior_show_list: } { 2019-01-01 }
32378 \__deprecation_old:Nnn \ior_log_streams:
32379 { \ior_log_list: } { 2019-01-01 }
32380 \__deprecation_old:Nnn \iow_list_streams:
32381 { \iow_show_list: } { 2019-01-01 }
32382 \__deprecation_old:Nnn \iow_log_streams:
32383 { \iow_log_list: } { 2019-01-01 }
32384 \__deprecation_old:Nnn \luatex_if_engine_p:
32385 { \sys_if_engine luatex_p: } { 2017-01-01 }
32386 \__deprecation_old:Nnn \luatex_if_engine:F
32387 { \sys_if_engine luatex:F } { 2017-01-01 }
32388 \__deprecation_old:Nnn \luatex_if_engine:T
32389 { \sys_if_engine luatex:T } { 2017-01-01 }
32390 \__deprecation_old:Nnn \luatex_if_engine:TF
32391 { \sys_if_engine luatex:TF } { 2017-01-01 }
32392 \__deprecation_old:Nnn \pdftex_if_engine_p:
32393 { \sys_if_engine pdftex_p: } { 2017-01-01 }
32394 \__deprecation_old:Nnn \pdftex_if_engine:F
32395 { \sys_if_engine pdftex:F } { 2017-01-01 }
32396 \__deprecation_old:Nnn \pdftex_if_engine:T
32397 { \sys_if_engine pdftex:T } { 2017-01-01 }
32398 \__deprecation_old:Nnn \pdftex_if_engine:TF
32399 { \sys_if_engine pdftex:TF } { 2017-01-01 }

```

```

32400 \__deprecation_old:Nnn \prop_get:cn
32401   { \prop_item:cn } { 2016-01-05 }
32402 \__deprecation_old:Nnn \prop_get:Nn
32403   { \prop_item:Nn } { 2016-01-05 }
32404 \__deprecation_old:Nnn \quark_if_recursion_tail_break:N
32405   { } { 2015-07-14 }
32406 \__deprecation_old:Nnn \quark_if_recursion_tail_break:n
32407   { } { 2015-07-14 }
32408 \__deprecation_old:Nnn \scan_align_safe_stop:
32409   { protected-commands } { 2017-01-01 }
32410 \__deprecation_old:Nnn \sort_ordered:
32411   { \sort_return_same: } { 2019-01-01 }
32412 \__deprecation_old:Nnn \sort_reversed:
32413   { \sort_return_swapped: } { 2019-01-01 }
32414 \__deprecation_old:Nnn \str_case:nnn
32415   { \str_case:nnF } { 2015-07-14 }
32416 \__deprecation_old:Nnn \str_case:onnn
32417   { \str_case:onF } { 2015-07-14 }
32418 \__deprecation_old:Nnn \str_case_x:nnn
32419   { \str_case_e:nnF } { 2015-07-14 }
32420 \__deprecation_old:Nnn \tl_case:cn
32421   { \tl_case:cnF } { 2015-07-14 }
32422 \__deprecation_old:Nnn \tl_case:Nnn
32423   { \tl_case:NnF } { 2015-07-14 }
32424 \__deprecation_old_protected:Nnn \tl_to_lowercase:n
32425   { \tex_lowercase:D } { 2018-03-05 }
32426 \__deprecation_old_protected:Nnn \tl_to_uppercase:n
32427   { \tex_uppercase:D } { 2018-03-05 }
32428 \__deprecation_old:Nnn \token_new:Nn
32429   { \cs_new_eq:NN } { 2019-01-01 }
32430 \__deprecation_old:Nnn \xetex_if_engine_p:
32431   { \sys_if_engine_xetex_p: } { 2017-01-01 }
32432 \__deprecation_old:Nnn \xetex_if_engine:F
32433   { \sys_if_engine_xetex:F } { 2017-01-01 }
32434 \__deprecation_old:Nnn \xetex_if_engine:T
32435   { \sys_if_engine_xetex:T } { 2017-01-01 }
32436 \__deprecation_old:Nnn \xetex_if_engine:TF
32437   { \sys_if_engine_xetex:TF } { 2017-01-01 }

```

(End definition for __deprecation_old_protected:Nnn and __deprecation_old:Nnn.)

51.4 Deprecated primitives

\etex_beginL:D

__deprecation_primitive:NN

__deprecation_primitive:w

We renamed all primitives to \tex_...:D so all others are deprecated. In l3names, __kernel_primitives: is defined to contain __kernel_primitive:NN \beginL \etex_beginL:D and so on, one for each deprecated primitive. We apply \exp_not:N to the second argument of __kernel_primitive:NN because it may be outer (both when doing and undoing deprecation actually), then __deprecation_primitive:NN uses \tex_let:D to change the meaning of this potentially outer token. Then, either turn it into an error or make it equal to the primitive #1. To be more precise, #1 may not be defined, so try a \tex_...:D command as well.

```

32438 \cs_new_protected:Npn \__deprecation_primitive:NN #1#2 { }
32439 \exp_last_unbraced:NNNNo

```

```

32440 \cs_new:Npn \__deprecation_primitive:w #1 { \token_to_str:N _ } { }
32441 \__kernel_deprecation_code:nn
32442 {
32443   \cs_set_protected:Npn \__kernel_primitive:NN #1
32444   {
32445     \exp_after:wN \__deprecation_primitive:NN
32446     \exp_after:wN #1
32447     \exp_not:N
32448   }
32449   \cs_set_protected:Npn \__deprecation_primitive:NN #1#2
32450   {
32451     \tex_let:D #2 \scan_stop:
32452     \exp_args:NNx \__kernel_deprecation_error:Nnn #2
32453     {
32454       \iow_char:N \
32455       \cs_if_exist:NTF #1
32456       { \cs_to_str:N #1 }
32457       {
32458         tex_
32459         \exp_last_unbraced:Nf
32460         \__deprecation_primitive:w { \cs_to_str:N #2 }
32461       }
32462     }
32463     { 2020-01-01 }
32464   }
32465   \__kernel_primitives:
32466 }
32467 {
32468   \cs_set_protected:Npn \__kernel_primitive:NN #1
32469   {
32470     \exp_after:wN \__deprecation_primitive:NN
32471     \exp_after:wN #1
32472     \exp_not:N
32473   }
32474   \cs_set_protected:Npn \__deprecation_primitive:NN #1#2
32475   {
32476     \tex_let:D #2 #1
32477     \cs_if_exist:cT { tex_ \cs_to_str:N #1 :D }
32478     { \cs_set_eq:Nc #2 { tex_ \cs_to_str:N #1 :D } }
32479   }
32480   \__kernel_primitives:
32481 }

```

(End definition for `\etex_beginL:D`, `__deprecation_primitive:NN`, and `__deprecation_primitive:w`.)

51.5 Loading the patches

When loaded first, the patches are simply read here. Here the deprecation code is loaded with the lower-level `__kernel_...` macro because we don't want it to flip the `\g__sys_deprecation_bool` boolean, so that the deprecation code can be re-loaded later (when using `undo-recent-deprecations`).

```

32482 \group_begin:
32483 \cs_set_protected:Npn \ProvidesExplFile
32484 {

```

```

32485 \char_set_catcode_space:n { '\ }
32486 \ProvidesExplFileAux
32487 }
32488 \cs_set_protected:Npx \ProvidesExplFileAux #1#2#3#4
32489 {
32490 \group_end:
32491 \cs_if_exist:NTF \ProvidesFile
32492 { \exp_not:N \ProvidesFile {#1} [ #2~v#3~#4 ] }
32493 { \iow_log:x { File:~#1~#2~v#3~#4 } }
32494 }
32495 \cs_gset_protected:Npn \__kernel_sys_configuration_load:n #1
32496 { \file_input:n { #1 .def } }
32497 \__kernel_sys_configuration_load:n { l3deprecation }
32498 </kernel>
32499 <*patches>

Standard file identification.
32500 \ProvidesExplFile{l3deprecation.def}{2019-04-06}{L3 Deprecated functions}

```

51.6 Deprecated l3box functions

```

\box_set_eq_clear:NN
\box_set_eq_clear:cN
\box_set_eq_clear:Nc
\box_set_eq_clear:cc
\box_gset_eq_clear:NN
\box_gset_eq_clear:cN
\box_gset_eq_clear:Nc
\box_gset_eq_clear:cc
32501 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \box_set_eq_drop:N }
32502 \cs_gset_protected:Npn \box_set_eq_clear:NN #1#2
32503 { \tex_setbox:D #1 \tex_box:D #2 }
32504 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \box_gset_eq_drop:N }
32505 \cs_gset_protected:Npn \box_gset_eq_clear:NN #1#2
32506 { \tex_global:D \tex_setbox:D #1 \tex_box:D #2 }
32507 \cs_generate_variant:Nn \box_set_eq_clear:NN { c , Nc , cc }
32508 \cs_generate_variant:Nn \box_gset_eq_clear:NN { c , Nc , cc }

```

(End definition for \box_set_eq_clear:NN and \box_gset_eq_clear:NN.)

```

\hbox_unpack_clear:N
\hbox_unpack_clear:c
32509 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \hbox_unpack_drop:N }
32510 \cs_gset_protected:Npn \hbox_unpack_clear:N
32511 { \hbox_unpack_drop:N }
32512 \cs_generate_variant:Nn \hbox_unpack_clear:N { c }

```

(End definition for \hbox_unpack_clear:N.)

```

\vbox_unpack_clear:N
\vbox_unpack_clear:c
32513 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \vbox_unpack_drop:N }
32514 \cs_gset_protected:Npn \vbox_unpack_clear:N
32515 { \vbox_unpack_drop:N }
32516 \cs_generate_variant:Nn \vbox_unpack_clear:N { c }

```

(End definition for \vbox_unpack_clear:N.)

51.7 Deprecated l3int functions

32517 <@@=int>

\c_zero Constants that are now deprecated. By default define them with \int_const:Nn. To deprecate them call for instance __kernel_deprecation_error:Nnn \c_zero {0} {2020-01-01}. To redefine them (locally), use __int_constdef:Nw, with an \exp_not:N construction because the constants themselves are outer at that point.

```

32518 \cs_gset_protected:Npn \__int_deprecated_constants:nn #1#2
32519 {
32520   #1 \c_zero           { 0 } #2
32521   #1 \c_one           { 1 } #2
32522   #1 \c_two           { 2 } #2
32523   #1 \c_three         { 3 } #2
32524   #1 \c_four          { 4 } #2
32525   #1 \c_five          { 5 } #2
32526   #1 \c_six           { 6 } #2
32527   #1 \c_seven         { 7 } #2
32528   #1 \c_eight         { 8 } #2
32529   #1 \c_nine          { 9 } #2
32530   #1 \c_ten           { 10 } #2
32531   #1 \c_eleven        { 11 } #2
32532   #1 \c_twelve        { 12 } #2
32533   #1 \c_thirteen     { 13 } #2
32534   #1 \c_fourteen     { 14 } #2
32535   #1 \c_fifteen       { 15 } #2
32536   #1 \c_sixteen       { 16 } #2
32537   #1 \c_thirty_two    { 32 } #2
32538   #1 \c_one_hundred   { 100 } #2
32539   #1 \c_two_hundred_fifty_five { 255 } #2
32540   #1 \c_two_hundred_fifty_six { 256 } #2
32541   #1 \c_one_thousand  { 1000 } #2
32542   #1 \c_ten_thousand  { 10000 } #2
32543 }
32544 \cs_set_protected:Npn \__int_deprecated_constants:Nn #1#2
32545 {
32546   \cs_if_free:NT #1
32547   { \int_const:Nn #1 {#2} }
32548 }
32549 \__int_deprecated_constants:nn { \__int_deprecated_constants:Nn } { }
32550 \__kernel_deprecation_code:nn
32551 {
32552   \__int_deprecated_constants:nn
32553   { \exp_after:wN \__kernel_deprecation_error:Nnn \exp_not:N }
32554   { { 2020-01-01 } }
32555 }
32556 {
32557   \__int_deprecated_constants:nn
32558   {
32559     \exp_after:wN \use:nnn
32560     \exp_after:wN \__int_constdef:Nw \exp_not:N
32561   }
32562   { \exp_stop_f: }
32563 }
```

(End definition for \c_zero and others.)

__int_value:w Made public.

32564 \cs_gset_eq:NN __int_value:w \int_value:w

(End definition for __int_value:w.)

51.8 Deprecated l3luatex functions

32565 (@@=lua)

\lua_now_x:n

\lua_escape_x:n

\lua_shipout_x:n

32566 __kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \lua_now:e }

32567 \cs_gset:Npn \lua_now_x:n #1 { __lua_now:n {#1} }

32568 __kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \lua_escape:e }

32569 \cs_gset:Npn \lua_escape_x:n #1 { __lua_escape:n {#1} }

32570 __kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \lua_shipout:e:n }

32571 \cs_gset_protected:Npn \lua_shipout_x:n #1 { __lua_shipout:n {#1} }

(End definition for \lua_now_x:n, \lua_escape_x:n, and \lua_shipout_x:n.)

51.9 Deprecated l3msg functions

32572 (@@=msg)

\msg_log:n

\msg_term:n

32573 __kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \iow_log:n }

32574 \cs_gset_protected:Npn \msg_log:n #1

{

32575 \iow_log:n { }

32576 \iow_wrap:nnnN { . ~ #1 } { . ~ } { } \iow_log:n

32577 \iow_log:n { }

32578 }

32579 __kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \iow_term:n }

32580 \cs_gset_protected:Npn \msg_term:n #1

{

32581 \iow_term:n { ***** }

32582 \iow_wrap:nnnN { * ~ #1 } { * ~ } { } \iow_term:n

32583 \iow_term:n { ***** }

32584 }

(End definition for \msg_log:n and \msg_term:n.)

\msg_interrupt:nnn

32587 __kernel_patch_deprecation:nnNNpn { 2020-01-01 } { [Defined-error-message] }

32588 \cs_gset_protected:Npn \msg_interrupt:nnn #1#2#3

{

32589 \tl_if_empty:nTF {#3}

{

32590 __msg_old_interrupt_wrap:nn { \ \c__msg_no_info_text_tl }

32591 {#1 \ \ \ #2 \ \ \ \c__msg_continue_text_tl }

32592 }

32593 {

32594 __msg_old_interrupt_wrap:nn { \ \ #3 }

32595 {#1 \ \ \ \ #2 \ \ \ \c__msg_help_text_tl }

32596 }


```

32598     }
32599   }
32600   \cs_gset_protected:Npn \__msg_old_interrupt_wrap:nn #1#2
32601   {
32602     \iow_wrap:nnnN {#1} { | ~ } { } \__msg_old_interrupt_more_text:n
32603     \iow_wrap:nnnN {#2} { ! ~ } { } \__msg_old_interrupt_text:n
32604   }
32605   \cs_gset_protected:Npn \__msg_old_interrupt_more_text:n #1
32606   {
32607     \exp_args:Nx \tex_errhelp:D
32608     {
32609       |,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
32610       #1 \iow_newline:
32611       |.....
32612     }
32613   }
32614   \group_begin:
32615     \char_set_lccode:nn {'\{ } {'\ }
32616     \char_set_lccode:nn {'\} } {'\ }
32617     \char_set_lccode:nn {'\& } {'\! }
32618     \char_set_catcode_active:N \&
32619     \tex_lowercase:D
32620     {
32621       \group_end:
32622       \cs_gset_protected:Npn \__msg_old_interrupt_text:n #1
32623       {
32624         \iow_term:x
32625         {
32626           \iow_newline:
32627           !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
32628           \iow_newline:
32629           !
32630         }
32631         \__kernel_iow_with:Nnn \tex_newlinechar:D { '^~J }
32632         {
32633           \__kernel_iow_with:Nnn \tex_errorcontextlines:D { -1 }
32634           {
32635             \group_begin:
32636             \cs_set_protected:Npn &
32637             {
32638               \tex_errmessage:D
32639               {
32640                 #1
32641                 \use_none:n
32642                 { ..... }
32643               }
32644             }
32645             \exp_after:wN
32646             \group_end:
32647             &
32648           }
32649         }
32650       }
32651     }

```

(End definition for `\msg_interrupt:nnn`.)

51.10 Deprecated `l3prg` functions

32652 `<@@=prg>`

`__prg_break_point:Nn` Made public, but used by a few third-parties. It's not possible to perfectly support a mixture of `__prg_map_break:Nn` and `\prg_map_break:Nn` because they use different delimiters. The following code only breaks if someone tries to break from two “old-style” `__prg_break:` `__prg_map_break:Nn` ... `__prg_break_point:Nn` mappings in one go. Basically, the `__prg_map_break:Nn` converts a single `__prg_break_point:Nn` to `\prg_break_point:Nn`, and that delimiter had better be the right one. Then we call `\prg_map_break:Nn` which may end up breaking intermediate looks in the (unbraced) argument #1. It is essential to define the `break_point` functions before the corresponding `break` functions: otherwise `\debug_on:n {deprecation}` `\debug_off:n {deprecation}` would break when trying to restore the definitions because they would involve deprecated commands whose definition has not yet been restored.

```
32653 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \prg_break_point:Nn }
32654 \cs_gset:Npn \__prg_break_point:Nn { \prg_break_point:Nn }
32655 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \prg_break_point: }
32656 \cs_gset:Npn \__prg_break_point: { \prg_break_point: }
32657 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \prg_map_break:Nn }
32658 \cs_gset:Npn \__prg_map_break:Nn #1 \prg_break_point:Nn
32659 { \prg_map_break:Nn #1 \prg_break_point:Nn }
32660 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \prg_break: }
32661 \cs_gset:Npn \__prg_break: #1 \__prg_break_point: { }
32662 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \prg_break:n }
32663 \cs_gset:Npn \__prg_break:n #1#2 \__prg_break_point: { #1 }
```

(End definition for `__prg_break_point:Nn` and others.)

51.11 Deprecated `l3str` functions

```
\str_lower_case:n
\str_lower_case:f
\str_upper_case:n
\str_upper_case:f
\str_fold_case:n
\str_fold_case:V
32664 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \str_lowercase:n }
32665 \cs_gset:Npn \str_lower_case:n { \str_lowercase:n }
32666 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \str_lowercase:f }
32667 \cs_gset:Npn \str_lower_case:f { \str_lowercase:f }
32668 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \str_uppercase:n }
32669 \cs_gset:Npn \str_upper_case:n { \str_uppercase:n }
32670 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \str_uppercase:f }
32671 \cs_gset:Npn \str_upper_case:f { \str_uppercase:f }
32672 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \str_foldcase:n }
32673 \cs_gset:Npn \str_fold_case:n { \str_foldcase:n }
32674 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \str_foldcase:V }
32675 \cs_gset:Npn \str_fold_case:V { \str_foldcase:V }
```

(End definition for `\str_lower_case:n`, `\str_upper_case:n`, and `\str_fold_case:n`.)

```
\str_case_x:nn
\str_case_x:nnTF
\str_if_eq_x_p:nn
\str_if_eq_x:nnTF
32676 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \str_case_e:nn }
32677 \cs_gset:Npn \str_case_x:nn { \str_case_e:nn }
32678 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \str_case_e:nnT }
```

```

32679 \cs_gset:Npn \str_case_x:nnT { \str_case_e:nnT }
32680 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \str_case_e:nnF }
32681 \cs_gset:Npn \str_case_x:nnF { \str_case_e:nnF }
32682 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \str_case_e:nnTF }
32683 \cs_gset:Npn \str_case_x:nnTF { \str_case_e:nnTF }
32684 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \str_if_eq_p:ee }
32685 \cs_gset:Npn \str_if_eq_x_p:nn { \str_if_eq_p:ee }
32686 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \str_if_eq:eeT }
32687 \cs_gset:Npn \str_if_eq_x:nnT { \str_if_eq:eeT }
32688 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \str_if_eq:eeF }
32689 \cs_gset:Npn \str_if_eq_x:nnF { \str_if_eq:eeF }
32690 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \str_if_eq:eeTF }
32691 \cs_gset:Npn \str_if_eq_x:nnTF { \str_if_eq:eeTF }

```

(End definition for \str_case_x:nnTF and \str_if_eq_x:nnTF.)

51.11.1 Deprecated l3tl functions

```

32692 <@t=tl>

\tl_set_from_file:Nnn
\tl_set_from_file:cnn
\tl_gset_from_file:Nnn
\tl_gset_from_file:cnn
\tl_set_from_file_x:Nnn
\tl_set_from_file_x:cnn
\tl_gset_from_file_x:Nnn
\tl_gset_from_file_x:cnn
32693 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \file_get:nnN }
32694 \cs_gset_protected:Npn \tl_set_from_file:Nnn #1#2#3
32695 { \file_get:nnN {#3} {#2} #1 }
32696 \cs_generate_variant:Nn \tl_set_from_file:Nnn { c }
32697 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \file_get:nnN }
32698 \cs_gset_protected:Npn \tl_gset_from_file:Nnn #1#2#3
32699 {
32700   \group_begin:
32701     \file_get:nnN {#3} {#2} \l__tl_internal_a_tl
32702     \tl_gset_eq:NN #1 \l__tl_internal_a_tl
32703   \group_end:
32704 }
32705 \cs_generate_variant:Nn \tl_gset_from_file:Nnn { c }
32706 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \file_get:nnN }
32707 \cs_gset_protected:Npn \tl_set_from_file_x:Nnn #1#2#3
32708 {
32709   \group_begin:
32710     \file_get:nnN {#3} {#2} \l__tl_internal_a_tl
32711     #2 \scan_stop:
32712     \tl_set:Nx \l__tl_internal_a_tl { \l__tl_internal_a_tl }
32713     \exp_args:NNNo \group_end:
32714     \tl_set:Nn #1 \l__tl_internal_a_tl
32715   }
32716 \cs_generate_variant:Nn \tl_set_from_file_x:Nnn { c }
32717 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \file_get:nnN }
32718 \cs_gset_protected:Npn \tl_gset_from_file_x:Nnn #1#2#3
32719 {
32720   \group_begin:
32721     \file_get:nnN {#3} {#2} \l__tl_internal_a_tl
32722     #2 \scan_stop:
32723     \tl_gset:Nx #1 { \l__tl_internal_a_tl }
32724   \group_end:
32725 }
32726 \cs_generate_variant:Nn \tl_gset_from_file_x:Nnn { c }

```

(End definition for `\tl_set_from_file:Nnn` and others.)

```

\tl_lower_case:n
\tl_lower_case:nn 32727 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \text_lowercase:n }
\tl_upper_case:n 32728 \cs_gset:Npn \tl_lower_case:n #1
\tl_upper_case:nn 32729 { \text_lowercase:n {#1} }
\tl_mixed_case:n 32730 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \text_lowercase:nn }
\tl_mixed_case:nn 32731 \cs_gset:Npn \tl_lower_case:nn #1#2
32732 { \text_lowercase:nn {#1} {#2} }
32733 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \text_uppercase:n }
32734 \cs_gset:Npn \tl_upper_case:n #1
32735 { \text_uppercase:n {#1} }
32736 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \text_uppercase:nn }
32737 \cs_gset:Npn \tl_upper_case:nn #1#2
32738 { \text_uppercase:nn {#1} {#2} }
32739 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \text_titlecase:n }
32740 \cs_gset:Npn \tl_mixed_case:n #1
32741 { \text_titlecase:n {#1} }
32742 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \text_titlecase:nn }
32743 \cs_gset:Npn \tl_mixed_case:nn #1#2
32744 { \text_titlecase:nn {#1} {#2} }

```

(End definition for `\tl_lower_case:n` and others.)

51.12 Deprecated `l3tl-analysis` functions

```

\tl_show_analysis:N Simple renames.
\tl_show_analysis:n 32745 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \tl_analysis_show:N }
32746 \cs_gset_protected:Npn \tl_show_analysis:N { \tl_analysis_show:N }
32747 \__kernel_patch_deprecation:nnNNpn { 2020-01-01 } { \tl_analysis_show:n }
32748 \cs_gset_protected:Npn \tl_show_analysis:n { \tl_analysis_show:n }

```

(End definition for `\tl_show_analysis:N` and `\tl_show_analysis:n`.)

51.13 Deprecated `l3token` functions

```

\token_get_prefix_spec:N
\token_get_arg_spec:N 32749 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \cs_prefix_spec:N }
\token_get_replacement_spec:N 32750 \cs_gset:Npn \token_get_prefix_spec:N { \cs_prefix_spec:N }
32751 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \cs_argument_spec:N }
32752 \cs_gset:Npn \token_get_arg_spec:N { \cs_argument_spec:N }
32753 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { \cs_replacement_spec:N }
32754 \cs_gset:Npn \token_get_replacement_spec:N { \cs_replacement_spec:N }

(End definition for \token_get_prefix_spec:N, \token_get_arg_spec:N, and \token_get_replacement_spec:N.)

```

```

\char_lower_case:N
\char_upper_case:N 32755 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \char_lowercase:N }
\char_mixed_case:Nn 32756 \cs_gset:Npn \char_lower_case:N { \char_lowercase:N }
\char_fold_case:N 32757 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \char_uppercase:N }
\char_str_lower_case:N 32758 \cs_gset:Npn \char_upper_case:N { \char_uppercase:N }
\char_str_upper_case:N 32759 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \char_titlecase:N }
\char_str_mixed_case:Nn 32760 \cs_gset:Npn \char_mixed_case:N { \char_titlecase:N }
\char_str_fold_case:N

```

```

32761 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \char_foldcase:N }
32762 \cs_gset:Npn \char_fold_case:N { \char_foldcase:N }
32763 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \char_str_lowercase:N }
32764 \cs_gset:Npn \char_str_lower_case:N { \char_str_lowercase:N }
32765 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \char_str_uppercase:N }
32766 \cs_gset:Npn \char_str_upper_case:N { \char_str_uppercase:N }
32767 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \char_str_titlecase:N }
32768 \cs_gset:Npn \char_str_mixed_case:N { \char_str_titlecase:N }
32769 \__kernel_patch_deprecation:nnNNpn { 2022-01-01 } { \char_str_foldcase:N }
32770 \cs_gset:Npn \char_str_fold_case:N { \char_str_foldcase:N }

```

(End definition for \char_lower_case:N and others.)

51.14 Deprecated l3file functions

\c_term_ior

```

32771 \__kernel_patch_deprecation:nnNNpn { 2021-01-01 } { -1 }
32772 \cs_gset_protected:Npn \c_term_ior { -1 \scan_stop: }

```

(End definition for \c_term_ior.)

32773 </patches>

32774 </initex | package>

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
! 211
\! 32617
\" 10901, 10904, 29521, 31358, 31382, 31388, 31392, 31398, 31402, 31408, 31414, 31421, 31422, 31428, 31432, 31434, 31543
\# 6, 5907, 6214, 10901, 13460, 31227
\\$ 5906, 6212, 10901, 10904, 24754, 31227
\% 5908, 6222, 10901, 13462, 31227
\& 5899, 6213, 10901, 10904, 12235, 32617, 32618
&& 210
\' 29521, 31352, 31379, 31386, 31390, 31395, 31400, 31403, 31405, 31412, 31417, 31418, 31425, 31430, 31433, 31441, 31442, 31489, 31490, 31497, 31498, 31509, 31510, 31515, 31516, 31544, 31545, 31567, 31568, 31571, 31572, 31573, 31574
\(..... 13996, 14216, 14318, 29543
\) 29543
* 211
* 5592, 5615, 11295, 11297, 11301, 11309
** 211
+ 210, 211
\, 15214, 31239
- 210, 211
\- 286
\. 29521, 31357, 31445, 31446, 31455, 31456, 31465, 31466, 31483, 31495, 31496, 31546, 31547, 31577, 31578, 31581, 31582
/ 211
\/ 285
\: 5905
\:: 37, 348, 374, 2926, 2927, 2928, 2929, 2930, 2931, 2932, 2934, 2938, 2939, 2942, 2945, 2952, 2955, 2958, 2964, 3051, 3120, 3122, 3127, 3134, 3138, 3141, 3146, 3161, 3202, 3203, 3204, 3205, 3216
\::N 37, 2930, 3051, 3205
\::V 37, 2958
\::V_unbraced 37, 3119
\::c 37, 2932
\::e 37, 2936, 3051
\::e_unbraced 37, 3119, 3161
\::error 263, 31749
\::f 37, 2945, 3204
\::f_unbraced 37, 3119
\::n 37, 385, 2929, 3202, 3205
\::o 37, 2934, 3203
\::o_unbraced 37, 3119, 3202, 3203, 3204, 3205
\::p 37, 348, 2931
\::v 37, 2958
\::v_unbraced 37, 3119
\::x 37, 2952
\::x_unbraced 37, 3119, 3216
< 210
= 210
\= 15215, 29521, 31355, 31435, 31436, 31451, 31452, 31474, 31475, 31476, 31503, 31504, 31529, 31530, 31583, 31584
> 210
? 210
? commands:	
?: 210
\ \ 2865, 5901, 6209, 6449, 6450, 6453, 6775, 6778, 6779, 6780, 6781, 6786, 6792, 6797, 6804, 6961, 6964, 6965, 6966, 6968, 6974, 6979, 6984, 7135, 7142, 10901, 12138, 12156, 12158, 12163, 12164, 12188, 12198, 12205, 12220, 12664, 12672, 12679, 12691, 12692, 12717, 12718, 12725, 12746, 12748, 12749, 12781, 12794, 12795, 12808, 12875, 12921, 12937, 12941, 12946, 12953, 13465, 14519, 14525, 14532, 16288, 16300, 16306, 17103, 17106, 17107, 17108, 17115, 17118, 17119, 23341, 23344, 23345, 23370, 23371, 23378, 23379, 23826, 25295, 25408, 25409, 25410, 25431, 26730, 26734, 26739, 26773, 26782, 26786, 26791, 26811, 26813, 26814, 26816, 26819, 26821, 26828, 26832, 26835, 26839, 26841, 26845, 26847, 26853, 26855, 26859, 26861, 26865, 26870, 26872, 26914, 26916, 26921, 26923, 26929, 26934, 26935, 26939, 26943, 26953, 26956, 26960, 26961, 26965, 26973, 27030, 28963, 31225, 32000, 32454, 32592, 32593, 32596, 32597

- \backslash 4, 5902, 6210, 6454,
10901, 13459, 24080, 26734, 26739,
26786, 26835, 26872, 26961, 26965,
29552, 29553, 29554, 31227, 32615
 - \backslash 5, 5903, 6211,
6454, 10901, 13461, 26733, 26739,
26836, 26872, 26961, 26965, 29552,
29553, 29554, 29555, 31227, 32616
 - \backslash 7, 10, 104, 195, 196, 197, 198,
2553, 3246, 5904, 6215, 6568, 6569,
6902, 6903, 7084, 7085, 7086, 10901,
10904, 10906, 10912, 10964, 12242,
13377, 13413, 20986, 23425, 23498,
23501, 24026, 24031, 24032, 24033,
24034, 24037, 24048, 24085, 24139,
24141, 24143, 24145, 24147, 24149,
24753, 26335, 26338, 26352, 26355,
26364, 26367, 26370, 26373, 26387,
26390, 29521, 31353, 31380, 31387,
31391, 31396, 31401, 31406, 31413,
31419, 31420, 31426, 31431, 31443,
31444, 31461, 31462, 31469, 31470,
31484, 31485, 31486, 31517, 31518,
31539, 31540, 31541, 31542, 32631
 - \sim 211
 - \backslash 5910, 10901, 10904, 31227
 - \backslash 29521, 31351, 31378, 31385, 31389,
31394, 31399, 31404, 31411, 31415,
31416, 31424, 31429, 31569, 31570
 - \parallel 210
 - \backslash 4453, 5909, 6217,
10901, 10904, 13463, 24070, 24074,
24080, 29521, 31231, 31354, 31381,
31393, 31397, 31407, 31423, 31427,
31471, 31472, 31473, 31527, 31528
 - \backslash 284, 2457, 5592, 5615, 6216, 6454,
6778, 6779, 6780, 10901, 11287,
12719, 12738, 12845, 12994, 13466,
23542, 24025, 24030, 24074, 24084,
24259, 26384, 29276, 29550, 29551,
31238, 32140, 32485, 32615, 32616
- A**
- \backslash A 5593, 5616
 - \backslash AA 29525, 30956, 31276
 - \backslash aa 29525, 30956, 31286
 - \backslash above 287
 - \backslash abovedisplayshortskip 288
 - \backslash abovedisplayskip 289
 - \backslash abovewithdelims 290
 - abs 211
 - \backslash accent 291
 - acos 213
 - acosc 213
 - acot 214
 - acotd 214
 - acsc 213
 - acscd 213
 - \backslash adjdemerits 292
 - \backslash adjustspacing 1010, 1672
 - \backslash advance 169, 185, 293
 - \backslash AE 29526, 30957, 31277, 31571
 - \backslash ae 29526, 30957, 31287, 31572
 - \backslash afterassignment 294
 - \backslash aftergroup 295
 - \backslash alignmark 885, 1764
 - \backslash alignat 886, 1765
 - asec 213
 - asecd 213
 - asin 213
 - asind 213
 - assert commands:
 - \backslash assert_int:n 25571, 26548
 - atan 214
 - atand 214
 - \backslash AtBeginDocument 667, 14462, 30974
 - \backslash atop 296
 - \backslash atopwithdelims 297
 - \backslash attribute 887, 1766
 - \backslash attributedef 888, 1767
 - \backslash automaticdiscretionary 889, 1768
 - \backslash automatichyphenmode 891, 1770
 - \backslash automatichyphenpenalty 892, 1772
 - \backslash autospacing 1209, 2044
 - \backslash autoxspacing 1210, 2045
- B**
- \backslash b 29521, 31365
 - \backslash badness 298
 - \backslash baselineskip 299
 - \backslash batchmode 300
 - \backslash begin 222, 226, 19070, 23822,
23824, 29539, 29547, 29729, 31223
 - begin internal commands:
 - $___$ regex_begin 26471
 - \backslash begincsname 894, 1774
 - \backslash begingroup 13,
20, 38, 42, 48, 67, 143, 163, 274, 301
 - \backslash beginL 609, 1188, 1479
 - \backslash beginR 610, 1480
 - \backslash belowdisplayshortskip 302
 - \backslash belowdisplayskip 303
 - \backslash bfseries 31204
 - \backslash binoppenalty 304
 - \backslash bodydir 895, 1863
 - \backslash bodydirection 896

bool commands:

- \bool_case_false:n [264](#), [31783](#)
- \bool_case_false:nTF
..... [264](#), [31783](#), [31793](#), [31795](#)
- \bool_case_true:n [264](#), [31783](#)
- \bool_case_true:nTF
..... [264](#), [31783](#), [31785](#), [31787](#)
- \bool_const:Nn [107](#), [9573](#)
- \bool_do_until:Nn [110](#), [9770](#)
- \bool_do_until:nn [111](#), [9776](#)
- \bool_do_while:Nn [110](#), [9770](#)
- \bool_do_while:nn [111](#), [9776](#)
- .bool_gset:N [185](#), [15650](#)
- \bool_gset:Nn [107](#), [9595](#)
- \bool_gset_eq:NN
..... [107](#), [9591](#), [24016](#), [25884](#)
- \bool_gset_false:N
..... [107](#), [6093](#), [6102](#), [9579](#), [25843](#), [31779](#)
- .bool_gset_inverse:N [185](#), [15658](#)
- \bool_gset_inverse:N [264](#), [31775](#)
- \bool_gset_true:N [107](#),
[6083](#), [9579](#), [9965](#), [9971](#), [25894](#), [31779](#)
- \bool_if:NnTF [107](#),
[238](#), [2734](#), [6097](#), [6106](#), [9612](#), [9765](#),
[9767](#), [9771](#), [9773](#), [9963](#), [9969](#), [13680](#),
[13687](#), [15397](#), [15616](#), [15625](#), [15816](#),
[15818](#), [15820](#), [15866](#), [15868](#), [15870](#),
[15908](#), [15910](#), [15912](#), [15928](#), [15930](#),
[15932](#), [15973](#), [16001](#), [16020](#), [16022](#),
[16027](#), [16034](#), [16101](#), [16132](#), [16142](#),
[16170](#), [24887](#), [24896](#), [25299](#), [25377](#),
[25395](#), [25424](#), [25521](#), [25741](#), [25749](#),
[27003](#), [27008](#), [28137](#), [28845](#), [30175](#),
[31776](#), [31779](#), [31801](#), [32225](#), [32298](#)
- \bool_if:nTF
..... [107](#), [109](#), [111](#), [111](#), [111](#), [593](#),
[9626](#), [9644](#), [9715](#), [9722](#), [9741](#), [9748](#),
[9757](#), [9778](#), [9787](#), [9791](#), [9800](#), [9869](#),
[25380](#), [31806](#), [31812](#), [31866](#), [32248](#)
- \bool_if_exist:NnTF
..... [108](#), [9640](#), [15415](#), [15431](#)
- \bool_if_exist_p:N [108](#), [9640](#)
- \bool_if_p:N [107](#), [9612](#)
- \bool_if_p:n
..... [109](#), [537](#), [9576](#), [9598](#), [9603](#),
[9644](#), [9652](#), [9722](#), [9748](#), [9754](#), [9758](#)
- \bool_lazy_all:nTF
..... [109](#), [109](#), [109](#), [9702](#), [25164](#)
- \bool_lazy_all_p:n [109](#), [9702](#)
- \bool_lazy_and:nnTF ... [109](#), [109](#),
[109](#), [9719](#), [10063](#), [13259](#), [13793](#),
[29842](#), [30463](#), [30516](#), [30544](#), [31128](#)
- \bool_lazy_and_p:nn .. [109](#), [109](#), [9719](#)
- \bool_lazy_any:nTF
..... [109](#), [110](#), [110](#), [6225](#), [6249](#), [6271](#),
[6438](#), [9728](#), [14113](#), [29507](#), [29614](#), [30340](#)
- \bool_lazy_any_p:n
..... [109](#), [110](#), [9728](#), [13798](#), [30466](#)
- \bool_lazy_or:nnTF [109](#), [110](#),
[110](#), [9745](#), [11280](#), [13988](#), [14022](#),
[14070](#), [14206](#), [23431](#), [29214](#), [29415](#),
[29631](#), [29639](#), [30127](#), [30141](#), [30177](#),
[30182](#), [30217](#), [30265](#), [30301](#), [30395](#),
[30402](#), [30480](#), [30525](#), [30558](#), [30589](#),
[30636](#), [30659](#), [30693](#), [31240](#), [31325](#)
- \bool_lazy_or_p:nn
..... [110](#), [9745](#), [29845](#), [30547](#), [31131](#)
- \bool_log:N [107](#), [9627](#)
- \bool_log:n [108](#), [9621](#)
- \bool_new:N [106](#), [5948](#),
[9571](#), [9636](#), [9637](#), [9638](#), [9639](#), [9959](#),
[9960](#), [13408](#), [15296](#), [15297](#), [15304](#),
[15305](#), [15309](#), [15415](#), [15431](#), [23867](#),
[24294](#), [25800](#), [25801](#), [25803](#), [25804](#),
[25805](#), [27738](#), [29885](#), [32195](#), [32211](#)
- \bool_not_p:n [110](#), [9754](#), [13796](#)
- .bool_set:N [185](#), [15650](#)
- \bool_set:Nn [107](#), [530](#), [9595](#)
- \bool_set_eq:NN [107](#), [9591](#), [24010](#), [26037](#)
- \bool_set_false:N
..... [107](#), [253](#), [9579](#), [13514](#), [13656](#),
[13664](#), [13672](#), [13682](#), [13689](#), [15336](#),
[15810](#), [15811](#), [15812](#), [15862](#), [15863](#),
[15867](#), [15903](#), [15911](#), [15913](#), [15922](#),
[15923](#), [15933](#), [15954](#), [16008](#), [24861](#),
[25066](#), [25779](#), [25856](#), [25870](#), [25916](#),
[25978](#), [28133](#), [28843](#), [31776](#), [32214](#)
- .bool_set_inverse:N [185](#), [15658](#)
- \bool_set_inverse:N [264](#), [31775](#)
- \bool_set_true:N
..... [107](#), [267](#), [9579](#), [13642](#), [15331](#),
[15817](#), [15819](#), [15821](#), [15861](#), [15869](#),
[15871](#), [15904](#), [15905](#), [15909](#), [15924](#),
[15929](#), [15931](#), [15949](#), [16015](#), [24866](#),
[25070](#), [25773](#), [25976](#), [26036](#), [28151](#),
[28173](#), [28204](#), [29886](#), [31776](#), [32224](#)
- \bool_show:N [107](#), [9627](#)
- \bool_show:n [107](#), [9621](#)
- \bool_until_do:Nn [110](#), [9764](#)
- \bool_until_do:nn [111](#), [9776](#)
- \bool_while_do:Nn [110](#), [9764](#)
- \bool_while_do:nn [111](#), [9776](#)
- \bool_xor:nnTF [110](#), [9755](#)
- \bool_xor_p:nn [110](#), [9755](#)
- \c_false_bool .. [22](#), [106](#), [334](#), [367](#),
[531](#), [533](#), [534](#), [534](#), [534](#), [535](#), [2311](#),
[2363](#), [2364](#), [2395](#), [2414](#), [2419](#), [2451](#),

- 2470, 2671, 2678, 3579, 3853, 9571,
9582, 9586, 9693, 9716, 9722, 9740,
9880, 24538, 24556, 24770, 24806,
25105, 25247, 25264, 25320, 25457,
26650, 31792, 31794, 31796, 31798
\g_tmpa_bool 108, 9636
\l_tmpa_bool 108, 9636
\g_tmpb_bool 108, 9636
\l_tmpb_bool 108, 9636
\c_true_bool 22, 106, 334, 399, 531,
533, 534, 534, 534, 535, 2363, 2395,
2451, 2469, 2692, 9580, 9584, 9694,
9695, 9714, 9742, 9748, 9874, 23874,
24013, 24442, 24502, 24552, 24736,
24761, 24805, 24812, 25245, 25255,
25318, 25507, 25679, 25690, 25705,
25860, 25893, 26481, 26558, 26611,
31784, 31786, 31788, 31790, 32252
- bool internal commands:
__bool_!:Nw 9673
__bool_&_0: 9685
__bool_&_1: 9685
__bool_&_2: 9685
__bool_(!Nw 9678
__bool_)_0: 9685
__bool_)_1: 9685
__bool_)_2: 9685
__bool_case:NnTF 31783
__bool_case_end:nw 31783
__bool_case_false:w 31783
__bool_case_true:w 31783
__bool_choose:NNN .. 9680, 9684, 9685
__bool_get_next:NN
. 534, 534, 9660, 9663, 9675, 9681,
9696, 9697, 9698, 9699, 9700, 9701
__bool_if_p:n 9652
__bool_if_p_aux:w 533, 9652
__bool_if_recursion_tail_stop_-
do:nn 9611, 9714, 9740
__bool_lazy_all:n 9702
__bool_lazy_any:n 9728
__bool_p:Nw 9683
__bool_show:NN 9627
__bool_to_str:n 9621, 9634
__bool_use_i_delimit_by_q_-
recursion_stop:nw 9609, 9716, 9742
__bool_l_0: 9685
__bool_l_1: 9685
__bool_l_2: 9685
\botmark 305
\botmarks 611, 1481
\box 306
- box commands:
\box_autosize_to_wd_and_ht:Nnn ..
..... 243, 27644
\box_autosize_to_wd_and_ht_plus_-
dp:Nnn 243, 27644
\box_clear:N 235,
235, 27047, 27054, 27773, 27863, 27933
\box_clear_new:N 235, 27053
\box_clip:N 260, 261, 261, 31602
\box_dp:N 236, 17593, 27075,
27084, 27088, 27389, 27518, 27633,
27652, 27658, 27970, 27971, 28077,
28082, 28110, 28124, 28297, 28575,
28596, 28915, 31622, 31629, 31634
\box_gautosize_to_wd_and_ht:Nnn ..
..... 243, 27644
\box_gautosize_to_wd_and_ht_-
plus_dp:Nnn 243, 27644
\box_gclear:N 235, 27047, 27056, 27782
\box_gclear_new:N 235, 27053
\box_gclip:N 260, 31602
\box_gresize_to_ht:Nn ... 243, 27537
\box_gresize_to_ht_plus_dp:Nn ...
..... 244, 27537
\box_gresize_to_wd:Nn ... 244, 27537
\box_gresize_to_wd_and_ht:Nnn ...
..... 244, 27537
\box_gresize_to_wd_and_ht_plus_-
dp:Nnn 244, 27488, 28411
\box_grotate:Nn ... 245, 27370, 28244
\box_gscale:Nnn ... 245, 27615, 28453
\box_gset_dp:Nn 236, 27081
\box_gset_eq:NN
235, 27050, 27059, 27955, 31612, 31663
\box_gset_eq_clear:NN 32501
\box_gset_eq_drop:N 32504
\box_gset_eq_drop:NN 242, 27065
\box_gset_ht:Nn 236, 27081
\box_gset_to_last:N 237, 27135
\box_gset_trim:Nnnnn 261, 31608
\box_gset_viewport:Nnnnn .. 261, 31659
\box_gset_wd:Nn 237, 27081
\box_ht:N 236, 17592, 27075,
27093, 27097, 27388, 27517, 27632,
27645, 27648, 27652, 27658, 27858,
27928, 27972, 27973, 28068, 28073,
28110, 28117, 28291, 28295, 28574,
28595, 28913, 31639, 31647, 31652
\box_if_empty:NnTF 237, 27131
\box_if_empty_p:N 237, 27131
\box_if_exist:NnTF
..... 235, 27054, 27056, 27071, 27166
\box_if_exist_p:N 235, 27071
\box_if_horizontal:NnTF ... 237, 27123

- `\box_if_horizontal_p:N` . . . [237](#), [27123](#)
- `\box_if_vertical:NTF` [237](#), [27123](#)
- `\box_if_vertical_p:N` [237](#), [27123](#)
- `\box_log:N` [238](#), [27152](#)
- `\box_log:Nnn` [238](#), [27152](#)
- `\box_move_down:nn` [236](#), [1167](#), [27112](#),
[28270](#), [31626](#), [31634](#), [31677](#), [31684](#)
- `\box_move_left:nn` [236](#), [27112](#)
- `\box_move_right:nn` [236](#), [27112](#)
- `\box_move_up:nn` [236](#), [27112](#), [28615](#),
[28910](#), [31643](#), [31652](#), [31691](#), [31704](#)
- `\box_new:N` [235](#),
[235](#), [27039](#), [27141](#), [27142](#), [27143](#),
[27144](#), [27145](#), [27369](#), [27714](#), [27789](#)
- `\box_resize:Nnn` [32336](#)
- `\box_resize_to_ht:Nn` [243](#), [27537](#)
- `\box_resize_to_ht_plus_dp:Nn` . . .
. [244](#), [27537](#)
- `\box_resize_to_wd:Nn` [244](#), [27537](#)
- `\box_resize_to_wd_and_ht:Nnn` . . .
. [244](#), [27537](#)
- `\box_resize_to_wd_and_ht_plus_dp:Nnn` . . . [244](#), [27488](#), [28404](#), [32337](#)
- `\box_rotate:Nn` [245](#), [27370](#), [28241](#)
- `\box_scale:Nnn` [245](#), [27615](#), [28450](#)
- `\box_set_dp:Nn`
. [236](#), [1167](#), [27081](#), [27415](#),
[27686](#), [27689](#), [28275](#), [28575](#), [28596](#),
[28914](#), [31629](#), [31637](#), [31680](#), [31685](#)
- `\box_set_eq:NN` . [235](#), [27048](#), [27059](#),
[27943](#), [28598](#), [28918](#), [31609](#), [31660](#)
- `\box_set_eq_clear:NN` [32501](#)
- `\box_set_eq_drop:N` [32501](#)
- `\box_set_eq_drop:NN` [242](#), [27065](#)
- `\box_set_ht:Nn` . [236](#), [27081](#), [27414](#),
[27685](#), [27690](#), [28273](#), [28574](#), [28595](#),
[28912](#), [31646](#), [31655](#), [31694](#), [31707](#)
- `\box_set_to_last:N` [237](#), [27135](#)
- `\box_set_trim:Nnnnn` [261](#), [31608](#)
- `\box_set_viewport:Nnnnn` . . [261](#), [31659](#)
- `\box_set_wd:Nn` . [237](#), [27081](#), [27416](#),
[27702](#), [28276](#), [28576](#), [28597](#), [28916](#)
- `\box_show:N` [238](#), [242](#), [27146](#)
- `\box_show:Nnn` [238](#), [27146](#)
- `\box_use:N` [235](#), [236](#),
[236](#), [27108](#), [27403](#), [28271](#), [28612](#),
[28615](#), [28907](#), [28910](#), [31619](#), [31670](#)
- `\box_use_clear:N` [32338](#)
- `\box_use_drop:N` [242](#), [27108](#),
[27418](#), [27697](#), [27706](#), [28278](#), [28698](#),
[28837](#), [31627](#), [31635](#), [31644](#), [31653](#),
[31678](#), [31684](#), [31692](#), [31705](#), [32339](#)
- `\box_wd:N` [236](#),
[17591](#), [27075](#), [27102](#), [27106](#), [27390](#),
[27519](#), [27634](#), [27666](#), [27974](#), [27975](#),
[28072](#), [28081](#), [28099](#), [28104](#), [28294](#),
[28302](#), [28496](#), [28503](#), [28529](#), [28576](#),
[28597](#), [28613](#), [28908](#), [28917](#), [31671](#)
- `\c_empty_box`
. . . [235](#), [237](#), [237](#), [27048](#), [27050](#), [27141](#)
- `\g_tmpa_box` [238](#), [27142](#)
- `\l_tmpa_box` [238](#), [27142](#)
- `\g_tmpb_box` [238](#), [27142](#)
- `\l_tmpb_box` [238](#), [27142](#)
- box internal commands:
 - `\l__box_angle_fp`
. . . [27358](#), [27380](#), [27381](#), [27382](#), [27411](#)
 - `__box_autosize:NnnnN` [27644](#)
 - `__box_backend_clip:N` . [31603](#), [31606](#)
 - `__box_backend_rotate:Nn` [27409](#)
 - `__box_backend_scale:Nnn` [27678](#)
 - `\l__box_bottom_dim` [27361](#),
[27389](#), [27446](#), [27450](#), [27455](#), [27461](#),
[27466](#), [27470](#), [27479](#), [27481](#), [27510](#),
[27518](#), [27527](#), [27571](#), [27633](#), [27639](#)
 - `\l__box_bottom_new_dim`
[27365](#), [27415](#), [27447](#), [27458](#), [27469](#),
[27480](#), [27526](#), [27638](#), [27686](#), [27690](#)
 - `\l__box_cos_fp` [27359](#),
[27382](#), [27394](#), [27399](#), [27426](#), [27438](#)
 - `__box_dim_eval:n`
. [27036](#), [27084](#), [27088](#), [27093](#),
[27097](#), [27102](#), [27106](#), [27113](#), [27115](#),
[27117](#), [27119](#), [27198](#), [27203](#), [27230](#),
[27236](#), [27244](#), [27266](#), [27300](#), [27305](#),
[27333](#), [27339](#), [27350](#), [27355](#), [31618](#),
[31620](#), [31669](#), [31671](#), [31680](#), [31704](#)
 - `__box_dim_eval:w` [27036](#)
 - `\l__box_internal_box` [27369](#), [27403](#),
[27404](#), [27410](#), [27414](#), [27415](#), [27416](#),
[27418](#), [27676](#), [27685](#), [27686](#), [27689](#),
[27690](#), [27697](#), [27702](#), [27706](#), [31616](#),
[31624](#), [31627](#), [31629](#), [31632](#), [31635](#),
[31637](#), [31639](#), [31641](#), [31644](#), [31646](#),
[31647](#), [31650](#), [31652](#), [31653](#), [31655](#),
[31657](#), [31667](#), [31675](#), [31678](#), [31680](#),
[31683](#), [31684](#), [31685](#), [31689](#), [31692](#),
[31694](#), [31702](#), [31705](#), [31707](#), [31709](#)
 - `\l__box_left_dim` . . . [27361](#), [27391](#),
[27446](#), [27448](#), [27457](#), [27461](#), [27466](#),
[27472](#), [27477](#), [27481](#), [27520](#), [27635](#)
 - `\l__box_left_new_dim` [27365](#), [27406](#),
[27417](#), [27449](#), [27460](#), [27471](#), [27482](#)
 - `__box_log:nNnn` [27152](#)
 - `__box_resize:N`
. . . [27488](#), [27554](#), [27574](#), [27591](#), [27612](#)
 - `__box_resize:NNN` [27488](#)

- _box_resize_common:N [27530](#), [27642](#), [27674](#)
 - _box_resize_set_corners:N [27488](#), [27547](#), [27567](#), [27587](#), [27604](#)
 - _box_resize_to_ht:NnN [27537](#)
 - _box_resize_to_ht_plus_dp:NnN . [27537](#)
 - _box_resize_to_wd:NnN [27537](#)
 - _box_resize_to_wd_and_ht:NnnN . [27595](#), [27598](#), [27600](#)
 - _box_resize_to_wd_and_ht_plus_dp:NnnN [27488](#)
 - _box_resize_to_wd_ht:NnnN .. [27537](#)
 - \l_box_right_dim .. [27361](#), [27390](#), [27444](#), [27450](#), [27455](#), [27459](#), [27468](#), [27470](#), [27479](#), [27483](#), [27506](#), [27519](#), [27525](#), [27589](#), [27606](#), [27634](#), [27641](#)
 - \l_box_right_new_dim ... [27365](#), [27417](#), [27451](#), [27462](#), [27473](#), [27484](#), [27524](#), [27640](#), [27694](#), [27696](#), [27702](#)
 - _box_rotate:N [27370](#)
 - _box_rotate:NnN [27370](#)
 - _box_rotate_quadrant_four: ... [27370](#), [27475](#)
 - _box_rotate_quadrant_one: [27370](#), [27442](#)
 - _box_rotate_quadrant_three: ... [27370](#), [27464](#)
 - _box_rotate_quadrant_two: [27370](#), [27453](#)
 - _box_rotate_xdir:nnN [27370](#), [27420](#), [27448](#), [27450](#), [27459](#), [27461](#), [27470](#), [27472](#), [27481](#), [27483](#)
 - _box_rotate_ydir:nnN [27370](#), [27431](#), [27444](#), [27446](#), [27455](#), [27457](#), [27466](#), [27468](#), [27477](#), [27479](#)
 - _box_scale:N [27615](#), [27671](#)
 - _box_scale:NnnN [27615](#)
 - \l_box_scale_x_fp [27486](#), [27505](#), [27525](#), [27553](#), [27573](#), [27588](#), [27590](#), [27605](#), [27625](#), [27641](#), [27666](#), [27668](#), [27669](#), [27670](#), [27680](#), [27692](#)
 - \l_box_scale_y_fp [27486](#), [27507](#), [27527](#), [27529](#), [27548](#), [27553](#), [27568](#), [27573](#), [27590](#), [27607](#), [27626](#), [27637](#), [27639](#), [27667](#), [27668](#), [27669](#), [27670](#), [27681](#), [27683](#)
 - _box_set_trim:NnnnnN [31608](#)
 - _box_set_viewport:NnnnnN [31660](#), [31663](#), [31665](#)
 - _box_show:NnNn . [27150](#), [27160](#), [27164](#)
 - \l_box_sin_fp [27359](#), [27381](#), [27392](#), [27427](#), [27437](#)
 - \l_box_top_dim [27361](#), [27388](#), [27444](#), [27448](#), [27457](#), [27459](#), [27468](#), [27472](#), [27477](#), [27483](#), [27510](#), [27517](#), [27529](#), [27551](#), [27571](#), [27610](#), [27632](#), [27637](#)
 - \l_box_top_new_dim [27365](#), [27414](#), [27445](#), [27456](#), [27467](#), [27478](#), [27528](#), [27636](#), [27685](#), [27689](#)
 - _box_viewport:NnnnnN [31659](#)
 - \boxdir [897](#), [1864](#)
 - \boxdirection [898](#)
 - \boxmaxdepth [307](#)
 - bp [216](#)
 - \breakafterdirmode [899](#), [1775](#)
 - \brokenpenalty [308](#)
- C**
- \c .. [29521](#), [31363](#), [31384](#), [31410](#), [31467](#), [31468](#), [31487](#), [31488](#), [31491](#), [31492](#), [31499](#), [31500](#), [31511](#), [31512](#), [31519](#), [31520](#), [31523](#), [31524](#), [31579](#), [31580](#)
 - \catcode [4](#), [5](#), [6](#), [7](#), [10](#), [212](#), [213](#), [214](#), [215](#), [216](#), [217](#), [218](#), [219](#), [220](#), [225](#), [226](#), [227](#), [228](#), [229](#), [230](#), [231](#), [232](#), [233](#), [309](#)
 - catcode commands:
 - \c_catcode_active_space_tl [269](#), [32138](#)
 - \c_catcode_active_tl [133](#), [583](#), [11308](#), [11368](#)
 - \c_catcode_letter_token [133](#), [582](#), [11241](#), [11290](#), [11358](#), [23621](#), [29488](#)
 - \c_catcode_other_space_tl [129](#), [645](#), [11287](#), [13422](#), [13466](#), [13546](#), [13635](#), [13711](#)
 - \c_catcode_other_token [133](#), [583](#), [11244](#), [11290](#), [11363](#), [23619](#), [29491](#)
 - \catcodetable [900](#), [1776](#)
 - cc [216](#)
 - ceil [212](#)
 - \char [310](#), [11473](#)
 - char commands:
 - \l_char_active_seq .. [132](#), [156](#), [10899](#)
 - \char_fold_case:N [32755](#)
 - \char_foldcase:N [129](#), [11166](#), [32761](#), [32762](#)
 - \char_generate:nn [45](#), [129](#), [393](#), [446](#), [1038](#), [1180](#), [4434](#), [4450](#), [6007](#), [6280](#), [6296](#), [10926](#), [11159](#), [11163](#), [11194](#), [11223](#), [11278](#), [11287](#), [12994](#), [24164](#), [25174](#), [29419](#), [29457](#), [30157](#), [30167](#), [30168](#), [30274](#), [30360](#), [30437](#), [30438](#), [30439](#), [30450](#), [30475](#), [30503](#), [30530](#), [30553](#), [30570](#), [30582](#), [30594](#), [30599](#), [30624](#), [30642](#), [30671](#), [30673](#), [30677](#), [30713](#), [30714](#), [30719](#), [30721](#), [30729](#), [30730](#)

- 30735, 30737, 30930, 30931, 31249,
 31270, 31272, 31331, 31345, 31347
 \char_gset_active_eq:NN ... [128](#), [10905](#)
 \char_gset_active_eq:nN ... [128](#), [10905](#)
 \char_lower_case:N [32755](#)
 \char_lowercase:N
 [129](#), [11166](#), [32755](#), [32756](#)
 \char_mixed_case:N [32760](#)
 \char_mixed_case:Nn [32755](#)
 \char_set_active_eq:NN ... [128](#), [10905](#)
 \char_set_active_eq:nN ... [128](#), [10905](#)
 \char_set_catcode:nn
 [131](#), [242](#), [243](#), [244](#), [245](#), [246](#), [247](#),
[248](#), [249](#), [250](#), [10805](#), [10812](#), [10814](#),
[10816](#), [10818](#), [10820](#), [10822](#), [10824](#),
[10826](#), [10828](#), [10830](#), [10832](#), [10834](#),
[10836](#), [10838](#), [10840](#), [10842](#), [10844](#),
[10846](#), [10848](#), [10850](#), [10852](#), [10854](#),
[10856](#), [10858](#), [10860](#), [10862](#), [10864](#),
[10866](#), [10868](#), [10870](#), [10872](#), [10874](#)
 \char_set_catcode_active:N . [130](#),
[10811](#), [10906](#), [10964](#), [11309](#), [12235](#),
[23425](#), [26335](#), [31231](#), [32139](#), [32618](#)
 \char_set_catcode_active:n
 [130](#), [10843](#), [11027](#), [15214](#), [15215](#), [29387](#)
 \char_set_catcode_alignment:N ...
 [130](#), [6213](#), [10811](#), [11297](#), [26387](#)
 \char_set_catcode_alignment:n ...
 [130](#), [260](#), [10843](#), [11011](#)
 \char_set_catcode_comment:N
 [130](#), [6222](#), [10811](#)
 \char_set_catcode_comment:n
 [130](#), [10843](#)
 \char_set_catcode_end_line:N ...
 [130](#), [10811](#)
 \char_set_catcode_end_line:n ...
 [130](#), [10843](#)
 \char_set_catcode_escape:N
 [130](#), [6209](#), [10811](#)
 \char_set_catcode_escape:n [130](#), [10843](#)
 \char_set_catcode_group_begin:N .
 [130](#), [6210](#), [10811](#), [23498](#), [26338](#)
 \char_set_catcode_group_begin:n .
 [130](#), [10843](#), [11004](#)
 \char_set_catcode_group_end:N ...
 [130](#), [6211](#), [10811](#), [23501](#), [26355](#)
 \char_set_catcode_group_end:n ...
 [130](#), [10843](#), [11006](#)
 \char_set_catcode_ignore:N
 [130](#), [6216](#), [10811](#)
 \char_set_catcode_ignore:n
 [130](#), [257](#), [258](#), [10843](#)
 \char_set_catcode_invalid:N
 [130](#), [10811](#)
 \char_set_catcode_invalid:n
 [130](#), [10843](#)
 \char_set_catcode_letter:N
 [130](#), [6219](#), [10811](#), [19211](#), [19212](#), [26364](#)
 \char_set_catcode_letter:n
 [130](#), [261](#), [263](#), [10843](#), [11023](#)
 \char_set_catcode_math_subscript:N
 [130](#), [10811](#), [11301](#), [26352](#)
 \char_set_catcode_math_subscript:n
 [130](#), [10843](#), [11018](#)
 \char_set_catcode_math_superscript:N
 [130](#), [6215](#), [10811](#), [26390](#)
 \char_set_catcode_math_superscript:n
 [130](#), [262](#), [10843](#), [11016](#)
 \char_set_catcode_math_toggle:N .
 [130](#), [6212](#), [10811](#), [11295](#), [26367](#)
 \char_set_catcode_math_toggle:n .
 [130](#), [10843](#), [11009](#)
 \char_set_catcode_other:N
 [130](#), [6221](#), [6568](#), [6569](#), [6902](#), [6903](#),
[7084](#), [7085](#), [7086](#), [10811](#), [23658](#), [26370](#)
 \char_set_catcode_other:n
 .. [130](#), [259](#), [264](#), [10843](#), [10967](#), [11025](#)
 \char_set_catcode_parameter:N ...
 [130](#), [6214](#), [10811](#), [26373](#)
 \char_set_catcode_parameter:n ...
 [130](#), [10843](#), [11014](#)
 \char_set_catcode_space:N
 [130](#), [6217](#), [10811](#)
 \char_set_catcode_space:n .. [130](#),
[265](#), [10843](#), [11021](#), [14481](#), [29276](#), [32485](#)
 \char_set_lccode:nn
 [131](#), [10875](#), [10912](#),
[11031](#), [11032](#), [12231](#), [12232](#), [12233](#),
[12234](#), [32140](#), [32615](#), [32616](#), [32617](#)
 \char_set_mathcode:nn ... [132](#), [10875](#)
 \char_set_sfcode:nn [132](#), [10875](#)
 \char_set_uccode:nn [131](#), [10875](#)
 \char_show_value_catcode:n [131](#), [10805](#)
 \char_show_value_lccode:n [131](#), [10875](#)
 \char_show_value_mathcode:n
 [132](#), [10875](#)
 \char_show_value_sfcode:n [132](#), [10875](#)
 \char_show_value_uccode:n [132](#), [10875](#)
 \l_char_special_seq [132](#), [10899](#)
 \char_str_fold_case:N [32755](#)
 \char_str_foldcase:N
 [129](#), [11166](#), [32769](#), [32770](#)
 \char_str_lower_case:N [32755](#)
 \char_str_lowercase:N
 [129](#), [11166](#), [32763](#), [32764](#)
 \char_str_mixed_case:N [32768](#)
 \char_str_mixed_case:Nn [32755](#)

- \char_str_titlecase:N
..... [129](#), [11166](#), [32767](#), [32768](#)
- \char_str_upper_case:N [32755](#)
- \char_str_uppercase:N
..... [129](#), [11166](#), [32765](#), [32766](#)
- \char_titlecase:N
..... [129](#), [11166](#), [32759](#), [32760](#)
- \char_to_nfd:N [269](#), [11144](#), [30310](#)
- \char_to_utfviii_bytes:n
..... [269](#), [11066](#), [30682](#),
[30703](#), [30704](#), [30937](#), [31262](#), [31339](#)
- \char_upper_case:N [32755](#)
- \char_uppercase:N
..... [129](#), [11166](#), [32757](#), [32758](#)
- \char_value_catcode:n
[131](#), [242](#), [243](#), [244](#), [245](#), [246](#), [247](#),
[248](#), [249](#), [250](#), [4446](#), [4450](#), [10805](#),
[11163](#), [29420](#), [30625](#), [31250](#), [31332](#)
- \char_value_lccode:n . [131](#), [10875](#),
[11167](#), [11180](#), [11257](#), [11267](#), [29291](#)
- \char_value_mathcode:n ... [132](#), [10875](#)
- \char_value_sfcode:n [132](#), [10875](#)
- \char_value_uccode:n
..... [132](#), [10875](#), [11169](#), [11259](#)
- char internal commands:
- __char_change_case:NN [11166](#)
- __char_change_case:nN [11166](#)
- __char_change_case:NNN [11166](#)
- __char_change_case:nNN [11166](#)
- __char_change_case:NNNN [11166](#)
- __char_change_case_catcode:N ...
..... [11159](#), [11166](#)
- __char_change_case_multi:nN . [11166](#)
- __char_change_case_multi:NNNNw .
..... [11166](#)
- __char_data_auxi:w [29242](#),
[29282](#), [29287](#), [29315](#), [29320](#), [29353](#)
- __char_data_auxii:w
..... [29248](#), [29252](#), [29298](#),
[29302](#), [29323](#), [29324](#), [29326](#), [29328](#)
- __char_data_auxiii:w . [29250](#), [29262](#)
- \g__char_data_ior .. [29213](#), [29241](#),
[29277](#), [29285](#), [29286](#), [29312](#), [29318](#),
[29319](#), [29342](#), [29355](#), [29371](#), [29372](#)
- __char_generate:n [29219](#),
[29257](#), [29259](#), [29271](#), [29294](#), [29306](#),
[29307](#), [29309](#), [29335](#), [29336](#), [29338](#)
- __char_generate_aux:nn [10926](#)
- __char_generate_aux:nnw [10926](#)
- __char_generate_aux:w . [10928](#), [10932](#)
- __char_generate_auxii:nnw ... [10926](#)
- __char_generate_char:n .. [29217](#),
[29255](#), [29270](#), [29293](#), [29304](#), [29333](#)
- __char_generate_invalid_-
 catcode: [10926](#)
- __char_int_to_roman:w
..... [10925](#), [11036](#), [11060](#)
- __char_quark_if_no_value:NTF ...
..... [10804](#), [11201](#), [11203](#)
- __char_quark_if_no_value_p:N . [10804](#)
- __char_str_change_case:nN ... [11166](#)
- __char_str_change_case:nNN .. [11166](#)
- __char_tmp:n
.. [11029](#), [11041](#), [11044](#), [11046](#), [11049](#)
- __char_tmp:NN .. [29360](#), [29366](#), [29368](#)
- __char_tmp:nN .. [10907](#), [10918](#), [10919](#)
- \l__char_tmp_tl [10926](#)
- \l__char_tmpa_tl [29265](#),
[29266](#), [29268](#), [29277](#), [29279](#), [29282](#)
- \l__char_tmpb_tl [29267](#), [29268](#)
- __char_to_nfd:n [11144](#)
- __char_to_nfd:Nw [11144](#)
- __char_to_utfviii_bytes_auxi:n .
..... [11066](#)
- __char_to_utfviii_bytes_-
 auxii:Nnn [11066](#)
- __char_to_utfviii_bytes_-
 auxiii:n [11066](#)
- __char_to_utfviii_bytes_end: . [11066](#)
- __char_to_utfviii_bytes_-
 output:nnn [11066](#)
- __char_to_utfviii_bytes_-
 outputi:nw [11066](#)
- __char_to_utfviii_bytes_-
 outputii:nw [11066](#)
- __char_to_utfviii_bytes_-
 outputiii:nw [11066](#)
- __char_to_utfviii_bytes_-
 outputiv:nw [11066](#)
- \chardef [222](#), [235](#), [311](#)
- choice commands:
- .choice: [185](#), [15666](#)
- choices commands:
- .choices:nn [185](#), [15668](#)
- \cite [29539](#), [29547](#)
- \cleaders [312](#)
- \clearmarks [901](#), [1777](#)
- clist commands:
- \clist_clear:N [119](#),
[119](#), [10264](#), [10281](#), [10444](#), [15849](#), [15891](#)
- \clist_clear_new:N [119](#), [10268](#)
- \clist_concat:NNN
..... [119](#), [10307](#), [10333](#), [10346](#)
- \clist_const:Nn [119](#), [10261](#)
- \clist_count:N
[124](#), [126](#), [10644](#), [10673](#), [10705](#), [10771](#)
- \clist_count:n [124](#), [10644](#), [10736](#), [10762](#)

- \clist_gclear:N ... [119](#), [10264](#), [10283](#)
- \clist_gclear_new:N [119](#), [10268](#)
- \clist_gconcat:NNN
 - [119](#), [10307](#), [10335](#), [10348](#)
- \clist_get:NN [125](#), [10358](#)
- \clist_get:NNTF [125](#), [10395](#)
- \clist_gpop:NN [125](#), [10369](#)
- \clist_gpop:NNTF [126](#), [10395](#)
- \clist_gpush:Nn [126](#), [10420](#)
- \clist_gput_left:Nn
 - . [120](#), [10332](#), [10428](#), [10429](#), [10430](#),
 - [10431](#), [10432](#), [10433](#), [10434](#), [10435](#)
- \clist_gput_right:Nn [120](#), [10345](#)
- \clist_gremove_all:Nn ... [121](#), [10454](#)
- \clist_gremove_duplicates:N
 - [121](#), [10438](#)
- \clist_greverse:N [121](#), [10493](#)
- .clist_gset:N [185](#), [15678](#)
- \clist_gset:Nn [120](#), [6309](#), [10326](#)
- \clist_gset_eq:NN .. [119](#), [10272](#), [10441](#)
- \clist_gset_from_seq:NN
 - [119](#), [10280](#), [10457](#), [23106](#)
- \clist_gsort:Nn ... [121](#), [10511](#), [23091](#)
- \clist_if_empty:NNTF
 - [122](#), [10316](#), [10478](#), [10511](#),
 - [10568](#), [10598](#), [10618](#), [10770](#), [15525](#)
- \clist_if_empty:nTF [122](#), [10515](#)
- \clist_if_empty_p:N [122](#), [10511](#)
- \clist_if_empty_p:n [122](#), [10515](#)
- \clist_if_exist:NNTF
 - [119](#), [10322](#), [10671](#), [14357](#), [14446](#)
- \clist_if_exist_p:N [119](#), [10322](#)
- \clist_if_in:NnTF
 - [118](#), [122](#), [10447](#), [10529](#)
- \clist_if_in:nNTF .. [122](#), [10529](#), [16976](#)
- \clist_item:Nn
 - [126](#), [567](#), [567](#), [10702](#), [10771](#)
- \clist_item:nn [126](#), [567](#), [10733](#), [10766](#)
- \clist_log:N [127](#), [10774](#)
- \clist_log:n [127](#), [10788](#)
- \clist_map_break:.....
 - [123](#), [10572](#), [10577](#), [10586](#),
 - [10590](#), [10606](#), [10624](#), [10640](#), [16062](#)
- \clist_map_break:n ... [124](#), [10549](#),
- [10640](#), [16016](#), [16094](#), [23099](#), [23105](#)
- \clist_map_function:NN .. [38](#), [122](#),
- [8104](#), [8114](#), [10552](#), [10566](#), [10649](#), [10784](#)
- \clist_map_function:Nn [564](#)
- \clist_map_function:nN
 - [122](#), [266](#), [266](#), [564](#), [6312](#),
 - [8109](#), [8119](#), [8130](#), [10582](#), [10793](#), [16198](#)
- \clist_map_inline:Nn
 - [122](#), [123](#), [562](#), [10180](#), [10445](#), [10596](#),
 - [16011](#), [16053](#), [16083](#), [23099](#), [23105](#)
- \clist_map_inline:nn
 - [123](#), [3891](#), [10596](#), [14566](#),
 - [15484](#), [15578](#), [16445](#), [29012](#), [29024](#)
- \clist_map_variable:NNn .. [123](#), [10616](#)
- \clist_map_variable:nNn .. [123](#), [10616](#)
- \clist_new:N
 - [118](#), [119](#), [551](#), [10259](#), [10436](#),
 - [10795](#), [10796](#), [10797](#), [10798](#), [15292](#)
- \clist_pop:NN [125](#), [10369](#)
- \clist_pop:NNTF [125](#), [10395](#)
- \clist_push:Nn [126](#), [10420](#)
- \clist_put_left:Nn
 - . [120](#), [10332](#), [10420](#), [10421](#), [10422](#),
 - [10423](#), [10424](#), [10425](#), [10426](#), [10427](#)
- \clist_put_right:Nn
 - [120](#), [10345](#), [10448](#), [16129](#), [16139](#), [16167](#)
- \clist_rand_item:N [126](#), [10761](#)
- \clist_rand_item:n .. [115](#), [126](#), [10761](#)
- \clist_remove_all:Nn [121](#), [10195](#), [10454](#)
- \clist_remove_duplicates:N
 - [118](#), [121](#), [10438](#)
- \clist_reverse:N [121](#), [10493](#)
- \clist_reverse:n
 - [121](#), [560](#), [10494](#), [10496](#), [10499](#)
- .clist_set:N [185](#), [15678](#)
- \clist_set:Nn
 - . [120](#), [10326](#), [10333](#), [10335](#), [10346](#),
 - [10348](#), [10535](#), [10612](#), [10629](#), [15524](#)
- \clist_set_eq:NN
 - [119](#), [10272](#), [10439](#), [15996](#)
- \clist_set_from_seq:NN
 - [119](#), [10280](#), [10455](#), [23100](#)
- \clist_show:N [126](#), [127](#), [10774](#)
- \clist_show:n [127](#), [127](#), [10788](#)
- \clist_sort:Nn [121](#), [10511](#), [23091](#)
- \clist_use:Nn [125](#), [10669](#)
- \clist_use:Nnnn [124](#), [502](#), [10669](#)
- \c_empty_clist
 - [127](#), [10203](#), [10360](#), [10375](#), [10397](#), [10411](#)
- \l_foo_clist [220](#)
- \g_tmpa_clist [127](#), [10795](#)
- \l_tmpa_clist [127](#), [10795](#)
- \g_tmpb_clist [127](#), [10795](#)
- \l_tmpb_clist [127](#), [10795](#)
- clist internal commands:
 - __clist_concat:NNNN [10307](#)
 - __clist_count:n [10644](#)
 - __clist_count:w [10644](#)
 - __clist_get:wN [10358](#), [10400](#)
 - __clist_if_empty_n:w [10515](#)
 - __clist_if_empty_n:wNw [10515](#)
 - __clist_if_in_return:nnN [10529](#)
 - __clist_if_recursion_tail_-
break:nN [10211](#), [10577](#), [10590](#)

- __clist_if_recursion_tail_-
 - stop:n .. [10211](#), [10228](#), [10634](#), [10665](#)
- __clist_if_wrap:nTF
 - [552](#), [10233](#), [10258](#), [10299](#), [10460](#), [10541](#)
- __clist_if_wrap:w [552](#), [10233](#)
- \l__clist_internal_clist
 - [555](#), [10204](#), [10338](#), [10339](#), [10351](#), [10352](#), [10535](#), [10536](#), [10537](#), [10612](#), [10613](#), [10629](#), [10630](#)
- \l__clist_internal_remove_clist .
 - .. [10436](#), [10444](#), [10447](#), [10448](#), [10450](#)
- \l__clist_internal_remove_seq ...
 - [10436](#), [10462](#), [10463](#), [10464](#)
- __clist_item:nnnN [10702](#), [10735](#)
- __clist_item_n:nw [10733](#)
- __clist_item_n_end:n [10733](#)
- __clist_item_N_loop:nw [10702](#)
- __clist_item_n_loop:nw [10733](#)
- __clist_item_n_strip:n [10733](#)
- __clist_item_n_strip:w [10733](#)
- __clist_map_function:Nw
 - [562](#), [10566](#), [10603](#)
- __clist_map_function_n:Nn [563](#), [10582](#)
- __clist_map_unbrace:Nw .. [563](#), [10582](#)
- __clist_map_variable:Nnw [10616](#)
- __clist_pop:NNN [10369](#)
- __clist_pop:wN [10369](#)
- __clist_pop:wwNNN . [556](#), [10369](#), [10414](#)
- __clist_pop_TF:NNN [10395](#)
- __clist_put_left:NNNn [10332](#)
- __clist_put_right:NNNn [10345](#)
- __clist_rand_item:nn [10761](#)
- __clist_remove_all: [10454](#)
- __clist_remove_all:NNNn [10454](#)
- __clist_remove_all:w ... [559](#), [10454](#)
- __clist_remove_duplicates:NN . [10438](#)
- __clist_reverse:wwNww ... [560](#), [10499](#)
- __clist_reverse_end:ww .. [560](#), [10499](#)
- __clist_sanitize:n
 - [10220](#), [10262](#), [10327](#), [10329](#)
- __clist_sanitize:Nn [552](#), [10220](#)
- __clist_set_from_seq:n [10280](#)
- __clist_set_from_seq:NNNN ... [10280](#)
- __clist_show:NN [10774](#)
- __clist_show:Nn [10788](#)
- __clist_tmp:w . [559](#), [10213](#), [10467](#), [10489](#), [10543](#), [10552](#), [10556](#), [10558](#)
- __clist_trim_next:w [552](#), [563](#), [10214](#), [10223](#), [10231](#), [10585](#), [10593](#)
- __clist_use:nwn [10669](#)
- __clist_use:nwwwnwn ... [565](#), [10669](#)
- __clist_use:wn [10669](#)
- __clist_use_i_delimit_by_s_-
 - stop:nw [10207](#), [10729](#)
- __clist_use_none_delimit_by_s_-
 - stop:w [559](#), [10207](#), [10470](#), [10715](#), [10720](#)
- __clist_wrap_item:w [552](#), [10229](#), [10257](#)
- \closein [313](#)
- \closeout [314](#)
- \clubpenalties [612](#), [1482](#)
- \clubpenalty [315](#)
- cm [216](#)
- code commands:
 - .code:n [185](#), [15676](#)
- coffin commands:
 - \coffin_attach:NnnNnnnn
 - [248](#), [1105](#), [28558](#)
 - \coffin_clear:N [246](#), [27769](#)
 - \coffin_display_handles:Nn [249](#), [28810](#)
 - \coffin_dp:N
 - [249](#), [27970](#), [28422](#), [28461](#), [28934](#)
 - \coffin_gattach:NnnNnnnn . [248](#), [28558](#)
 - \coffin_gclear:N [246](#), [27769](#)
 - \coffin_gjoin:NnnNnnnn ... [248](#), [28507](#)
 - \coffin_gresize:Nnn [248](#), [28401](#)
 - \coffin_grotate:Nn [248](#), [28240](#)
 - \coffin_gscale:Nnn [248](#), [28449](#)
 - \coffin_gset_eq:NN
 - [246](#), [27939](#), [28516](#), [28567](#)
 - \coffin_gset_horizontal_pole:Nnn
 - [247](#), [28000](#)
 - \coffin_gset_vertical_pole:Nnn ..
 - [247](#), [28000](#)
 - \coffin_ht:N
 - [249](#), [27970](#), [28422](#), [28461](#), [28933](#)
 - \coffin_if_exist:NTF [246](#), [27748](#), [27762](#)
 - \coffin_if_exist_p:N [246](#), [27748](#)
 - \coffin_join:NnnNnnnn ... [248](#), [28507](#)
 - \coffin_log_structure:N .. [250](#), [28920](#)
 - \coffin_mark_handle:Nnnn . [249](#), [28755](#)
 - \coffin_new:N
 - [246](#), [1081](#), [27787](#), [27963](#), [27964](#), [27965](#), [27966](#), [27967](#), [27968](#), [27969](#), [28691](#), [28701](#), [28702](#), [28703](#)
 - \coffin_resize:Nnn [248](#), [28401](#)
 - \coffin_rotate:Nn [248](#), [28240](#)
 - \coffin_scale:Nnn [248](#), [28449](#)
 - \coffin_scale:NnnNN [28449](#)
 - \coffin_set_eq:NN [246](#), [27939](#), [28510](#), [28561](#), [28589](#), [28617](#), [28831](#)
 - \coffin_set_horizontal_pole:Nnn .
 - [247](#), [28000](#)
 - \coffin_set_vertical_pole:Nnn ...
 - [247](#), [28000](#)
 - \coffin_show_structure:N
 - [249](#), [250](#), [28920](#)
 - \coffin_typeset:Nnnnn ... [249](#), [28693](#)

- \coffin_wd:N
 [249](#), [27970](#), [28418](#), [28465](#), [28935](#)
- \c_empty_coffin [250](#), [27963](#)
- \g_tmpa_coffin [250](#), [27966](#)
- \l_tmpa_coffin [250](#), [27966](#)
- \g_tmpb_coffin [250](#), [27966](#)
- \l_tmpb_coffin [250](#), [27966](#)
- coffin internal commands:
- __coffin_align:NnnNnnnnN
 .. [28521](#), [28572](#), [28593](#), [28600](#), [28696](#)
- \l__coffin_aligned_coffin
 [27963](#), [28522](#),
 [28523](#), [28527](#), [28533](#), [28536](#), [28539](#),
 [28555](#), [28556](#), [28573](#), [28574](#), [28575](#),
 [28576](#), [28577](#), [28580](#), [28584](#), [28588](#),
 [28589](#), [28594](#), [28595](#), [28596](#), [28597](#),
 [28598](#), [28631](#), [28647](#), [28697](#), [28698](#),
 [28905](#), [28912](#), [28914](#), [28916](#), [28918](#)
- \l__coffin_aligned_internal_
 coffin [27963](#), [28610](#), [28617](#)
- __coffin_attach:NnnNnnnnN ... [28558](#)
- __coffin_attach_mark:NnnNnnnn ..
 [28558](#), [28767](#), [28788](#), [28804](#)
- \l__coffin_bottom_corner_dim ...
 [28236](#), [28270](#), [28274](#),
 [28353](#), [28364](#), [28365](#), [28385](#), [28393](#)
- \l__coffin_bounding_prop
 [28232](#), [28259](#), [28290](#),
 [28292](#), [28298](#), [28300](#), [28309](#), [28372](#)
- \l__coffin_bounding_shift_dim ...
 .. [28235](#), [28268](#), [28371](#), [28377](#), [28378](#)
- __coffin_calculate_intersection:Nnn
 [28129](#), [28602](#), [28605](#), [28898](#)
- __coffin_calculate_intersection:nnnnnn
 [28129](#)
- __coffin_calculate_intersection:nnnnnnnn
 [28129](#), [28844](#)
- __coffin_color:n
 .. [28753](#), [28763](#), [28775](#), [28818](#), [28858](#)
- \c__coffin_corners_prop
 [27717](#), [27794](#), [27989](#), [27996](#)
- \l__coffin_corners_prop
 [28233](#), [28250](#), [28254](#), [28279](#),
 [28284](#), [28315](#), [28355](#), [28382](#), [28429](#),
 [28433](#), [28439](#), [28445](#), [28480](#), [28494](#)
- \l__coffin_cos_fp
 [1089](#), [1091](#), [28230](#), [28249](#), [28336](#), [28345](#)
- __coffin_display_attach:Nnnnn [28810](#)
- \l__coffin_display_coffin
 [28701](#), [28831](#), [28837](#), [28907](#),
 [28908](#), [28913](#), [28915](#), [28917](#), [28918](#)
- \l__coffin_display_coord_coffin .
 [28701](#), [28769](#),
 [28789](#), [28805](#), [28852](#), [28872](#), [28891](#)
- \l__coffin_display_font_tl
 [28746](#), [28777](#), [28860](#)
- __coffin_display_handles_
 aux:nnnn [28810](#)
- __coffin_display_handles_
 aux:nnnnnn [28810](#)
- \l__coffin_display_handles_prop .
 .. [28704](#), [28780](#), [28784](#), [28863](#), [28867](#)
- \l__coffin_display_offset_dim ...
 .. [28741](#), [28806](#), [28807](#), [28892](#), [28893](#)
- \l__coffin_display_pole_coffin ...
 .. [28701](#), [28757](#), [28768](#), [28812](#), [28850](#)
- \l__coffin_display_poles_prop ...
 [28745](#), [28822](#),
 [28827](#), [28830](#), [28832](#), [28834](#), [28841](#)
- \l__coffin_display_x_dim
 [28743](#), [28847](#), [28902](#)
- \l__coffin_display_y_dim
 [28743](#), [28848](#), [28904](#)
- \c__coffin_empty_coffin [28691](#), [28696](#)
- \l__coffin_error_bool
 [27738](#), [28133](#), [28137](#),
 [28151](#), [28173](#), [28204](#), [28843](#), [28845](#)
- __coffin_find_bounding_shift: ..
 [28262](#), [28369](#)
- __coffin_find_bounding_shift_
 aux:nn [28369](#)
- __coffin_find_corner_maxima:N ..
 [28261](#), [28349](#)
- __coffin_find_corner_maxima_
 aux:nn [28349](#)
- __coffin_get_pole:NnN
 [27976](#), [28131](#), [28132](#), [28658](#), [28659](#),
 [28662](#), [28663](#), [28824](#), [28825](#), [28828](#)
- __coffin_greset_structure:N ...
 [27783](#), [27986](#), [28050](#)
- __coffin_gupdate:N
 .. [27822](#), [27835](#), [27887](#), [27905](#), [28042](#)
- __coffin_gupdate_corners:N
 [28051](#), [28054](#)
- __coffin_gupdate_poles:N
 [28052](#), [28085](#)
- __coffin_if_exist:NTF
 [27760](#), [27771](#), [27780](#), [27802](#),
 [27815](#), [27840](#), [27868](#), [27881](#), [27910](#),
 [27941](#), [27953](#), [28008](#), [28026](#), [28928](#)
- \l__coffin_internal_box
 [27714](#), [27852](#),
 [27858](#), [27863](#), [27922](#), [27928](#), [27933](#),
 [28264](#), [28273](#), [28275](#), [28276](#), [28278](#)
- \l__coffin_internal_dim
 [27714](#), [28297](#), [28299](#), [28303](#),
 [28460](#), [28463](#), [28528](#), [28530](#), [28531](#)

\l__coffin_internal_tl ... [27714](#),
 [28629](#), [28630](#), [28632](#), [28781](#), [28782](#),
 [28785](#), [28786](#), [28794](#), [28799](#), [28864](#),
 [28865](#), [28868](#), [28869](#), [28878](#), [28883](#)
 __coffin_join:NnnNnnnnN ... [28507](#)
 \l__coffin_left_corner_dim ...
 ... [28236](#), [28268](#), [28277](#),
 [28354](#), [28360](#), [28361](#), [28384](#), [28392](#)
 __coffin_mark_handle_aux:nnnnNnn
 ... [28755](#)
 __coffin_offset_corner:Nnnnn ... [28638](#)
 __coffin_offset_corners:Nnn ...
 ... [28544](#), [28545](#), [28551](#), [28552](#), [28638](#)
 __coffin_offset_pole:Nnnnnnn ... [28619](#)
 __coffin_offset_poles:Nnn ...
 ... [28542](#), [28543](#),
 [28548](#), [28549](#), [28585](#), [28586](#), [28619](#)
 \l__coffin_offset_x_dim ...
 ... [27739](#), [28525](#), [28526](#), [28529](#),
 [28540](#), [28542](#), [28544](#), [28550](#), [28553](#),
 [28587](#), [28606](#), [28614](#), [28901](#), [28909](#)
 \l__coffin_offset_y_dim ...
 ... [27739](#), [28543](#), [28545](#), [28550](#), [28553](#),
 [28587](#), [28608](#), [28615](#), [28903](#), [28910](#)
 \l__coffin_pole_a_tl ...
 ... [27741](#), [28131](#), [28136](#), [28658](#), [28661](#),
 [28662](#), [28665](#), [28824](#), [28826](#), [28829](#)
 \l__coffin_pole_b_tl ... [27741](#),
 [28132](#), [28136](#), [28659](#), [28661](#), [28663](#),
 [28665](#), [28825](#), [28826](#), [28828](#), [28829](#)
 \c__coffin_poles_prop ...
 ... [27724](#), [27796](#), [27991](#), [27998](#)
 \l__coffin_poles_prop ...
 ... [28233](#), [28252](#), [28256](#),
 [28281](#), [28286](#), [28323](#), [28390](#), [28431](#),
 [28435](#), [28441](#), [28447](#), [28486](#), [28501](#)
 __coffin_reset_structure:N ...
 ... [27774](#), [27986](#), [28044](#), [28533](#), [28577](#)
 __coffin_resize:NnnNN ... [28401](#)
 __coffin_resize_common:NnnN ...
 ... [28425](#), [28427](#), [28466](#)
 \l__coffin_right_corner_dim ...
 ... [28236](#), [28277](#), [28352](#), [28362](#), [28363](#)
 __coffin_rotate:NnNNN ... [28240](#)
 __coffin_rotate_bounding:nnn ...
 ... [28260](#), [28306](#)
 __coffin_rotate_corner:Nnnnn ...
 ... [28255](#), [28306](#)
 __coffin_rotate_pole:Nnnnnn ...
 ... [28257](#), [28318](#)
 __coffin_rotate_vector:nnNN ...
 ... [28308](#), [28314](#), [28320](#), [28321](#), [28330](#)
 __coffin_scale:NnnNN ...
 ... [28450](#), [28453](#), [28455](#)
 __coffin_scale_corner:Nnnn ...
 ... [28434](#), [28477](#)
 __coffin_scale_pole:Nnnnnn ...
 ... [28436](#), [28477](#)
 __coffin_scale_vector:nnNN ...
 ... [28470](#), [28479](#), [28485](#)
 \l__coffin_scale_x_fp [28397](#), [28417](#),
 [28437](#), [28457](#), [28459](#), [28465](#), [28473](#)
 \l__coffin_scale_y_fp ... [28397](#),
 [28419](#), [28458](#), [28459](#), [28463](#), [28475](#)
 \l__coffin_scaled_total_height_-
 dim ... [28399](#), [28462](#), [28467](#)
 \l__coffin_scaled_width_dim ...
 ... [28399](#), [28464](#), [28467](#)
 __coffin_set_bounding:N [28258](#), [28288](#)
 __coffin_set_horizontal_-
 pole:NnnN ... [28000](#)
 __coffin_set_pole:Nnn ...
 ... [27853](#), [27923](#), [28000](#),
 [28631](#), [28671](#), [28675](#), [28683](#), [28687](#)
 __coffin_set_vertical:NnnNN . [27826](#)
 __coffin_set_vertical:NnNNNNw [27894](#)
 __coffin_set_vertical_pole:NnnN
 ... [28000](#)
 __coffin_shift_corner:Nnnn ...
 ... [28280](#), [28380](#)
 __coffin_shift_pole:Nnnnnn ...
 ... [28282](#), [28380](#)
 __coffin_show_structure:NN ... [28920](#)
 \l__coffin_sin_fp ...
 ... [1089](#), [1091](#), [28230](#), [28248](#), [28337](#), [28344](#)
 \l__coffin_slope_A_fp ... [27736](#)
 \l__coffin_slope_B_fp ... [27736](#)
 __coffin_to_value:N ...
 ... [27747](#), [27752](#), [27791](#), [27792](#), [27793](#),
 [27795](#), [27944](#), [27945](#), [27946](#), [27947](#),
 [27956](#), [27957](#), [27958](#), [27959](#), [27979](#),
 [27988](#), [27990](#), [27995](#), [27997](#), [28010](#),
 [28028](#), [28038](#), [28061](#), [28092](#), [28251](#),
 [28253](#), [28283](#), [28285](#), [28430](#), [28432](#),
 [28444](#), [28446](#), [28536](#), [28580](#), [28583](#),
 [28621](#), [28640](#), [28647](#), [28823](#), [28939](#)
 \l__coffin_top_corner_dim ...
 ... [28236](#), [28274](#), [28351](#), [28366](#), [28367](#)
 __coffin_update:N ...
 ... [27809](#), [27829](#), [27874](#), [27898](#), [28042](#)
 __coffin_update_B:nnnnnnnnN . [28656](#)
 __coffin_update_corners:N ...
 ... [28045](#), [28054](#)
 __coffin_update_corners:NN . [28054](#)
 __coffin_update_corners:NNN . [28054](#)
 __coffin_update_poles:N ...
 ... [28046](#), [28085](#), [28539](#), [28584](#)
 __coffin_update_poles:NN ... [28085](#)

- `__coffin_update_poles:NNN` ... [28085](#)
- `__coffin_update_T:nnnnnnnnN` . [28656](#)
- `__coffin_update_vertical_-`
 - `poles:NNN` [28555](#), [28588](#), [28656](#)
- `\l__coffin_x_dim` ... [27743](#), [28140](#),
[28149](#), [28175](#), [28206](#), [28224](#), [28308](#),
[28310](#), [28314](#), [28316](#), [28320](#), [28325](#),
[28479](#), [28481](#), [28485](#), [28488](#), [28603](#),
[28607](#), [28626](#), [28634](#), [28847](#), [28899](#)
- `\l__coffin_x_prime_dim`
..... [27743](#), [28322](#),
[28326](#), [28603](#), [28607](#), [28899](#), [28902](#)
- `__coffin_x_shift_corner:Nnnn` ...
..... [28440](#), [28492](#)
- `__coffin_x_shift_pole:Nnnnnn` ...
..... [28442](#), [28492](#)
- `\l__coffin_y_dim` [27743](#),
[28141](#), [28153](#), [28171](#), [28220](#), [28308](#),
[28310](#), [28314](#), [28316](#), [28320](#), [28325](#),
[28479](#), [28481](#), [28485](#), [28488](#), [28604](#),
[28609](#), [28627](#), [28634](#), [28848](#), [28900](#)
- `\l__coffin_y_prime_dim`
..... [27743](#), [28322](#),
[28327](#), [28604](#), [28609](#), [28900](#), [28904](#)
- `\color` [28754](#)
- color commands:
 - `\color_ensure_current:` . [251](#), [1078](#),
[27806](#), [27819](#), [27870](#), [27883](#), [28971](#)
 - `\color_group_begin:`
..... [251](#), [251](#), [27183](#),
[27187](#), [27192](#), [27199](#), [27204](#), [27212](#),
[27218](#), [27232](#), [27238](#), [27245](#), [27250](#),
[27261](#), [27263](#), [27267](#), [27272](#), [27277](#),
[27282](#), [27289](#), [27294](#), [27301](#), [27306](#),
[27314](#), [27320](#), [27335](#), [27341](#), [28969](#)
 - `\color_group_end:` [251](#), [251](#),
[27183](#), [27187](#), [27192](#), [27199](#), [27204](#),
[27224](#), [27245](#), [27250](#), [27261](#), [27263](#),
[27267](#), [27272](#), [27277](#), [27282](#), [27289](#),
[27294](#), [27301](#), [27306](#), [27327](#), [28969](#)
- color internal commands:
 - `__color_backend_cmyk:nnnn` ... [28985](#)
 - `__color_backend_gray:n` [28987](#)
 - `__color_backend_pickup:N` [28974](#)
 - `__color_backend_rgb:nnn` [28989](#)
 - `__color_backend_spot:nn` [28991](#)
 - `\l__color_current_tl`
... [1108](#), [28969](#), [28974](#), [28976](#), [28992](#)
 - `__color_select:n` [28976](#), [28979](#)
 - `__color_select:w` [28979](#)
 - `__color_select_cmyk:w` [28979](#)
 - `__color_select_gray:w` [28979](#)
 - `__color_select_rgb:w` [28979](#)
 - `__color_select_spot:w` [28979](#)
- `\columnwidth` [27847](#), [27916](#)
- `\copy` [316](#)
- `\copyfont` [1011](#), [1673](#)
- `cos` [213](#)
- `cosd` [213](#)
- `cot` [213](#)
- `cotd` [213](#)
- `\count` [165](#), [167](#), [168](#), [169](#),
[173](#), [174](#), [176](#), [177](#), [180](#), [182](#), [183](#),
[184](#), [185](#), [189](#), [190](#), [192](#), [193](#), [317](#), [11481](#)
- `\countdef` [318](#)
- `\cr` [319](#)
- `\crampeddisplaystyle` [902](#), [1778](#)
- `\crampedscriptscriptstyle` [903](#), [1780](#)
- `\crampedscriptstyle` [905](#), [1782](#)
- `\crampedtextstyle` [906](#), [1783](#)
- `\crrcr` [320](#)
- `\creationdate` [875](#)
- `\cs` [19065](#), [29727](#)
- cs commands:
 - `\cs:w` [17](#),
[1036](#), [1036](#), [2115](#), [2137](#), [2139](#), [2192](#),
[2499](#), [2527](#), [2720](#), [2784](#), [2933](#), [2982](#),
[2991](#), [2993](#), [2997](#), [2998](#), [2999](#), [3061](#),
[3067](#), [3073](#), [3079](#), [3099](#), [3101](#), [3106](#),
[3113](#), [3114](#), [3179](#), [3183](#), [3222](#), [3840](#),
[6018](#), [6024](#), [8788](#), [8875](#), [9512](#), [9564](#),
[9811](#), [9813](#), [11150](#), [14584](#), [14882](#),
[14930](#), [14997](#), [15024](#), [16071](#), [16091](#),
[16107](#), [16120](#), [16738](#), [16757](#), [16824](#),
[17649](#), [17838](#), [17870](#), [18287](#), [18313](#),
[18326](#), [18362](#), [18406](#), [18910](#), [20615](#),
[21707](#), [26272](#), [26275](#), [27043](#), [31716](#)
 - `\cs_argument_spec:N`
..... [18](#), [2870](#), [32751](#), [32752](#)
 - `\cs_end:` [17](#),
[374](#), [2115](#), [2137](#), [2139](#), [2143](#), [2192](#),
[2493](#), [2499](#), [2521](#), [2527](#), [2647](#), [2720](#),
[2784](#), [2933](#), [2982](#), [2991](#), [2993](#), [2997](#),
[2998](#), [2999](#), [3061](#), [3067](#), [3073](#), [3079](#),
[3099](#), [3101](#), [3106](#), [3113](#), [3114](#), [3179](#),
[3183](#), [3222](#), [3840](#), [6024](#), [6027](#), [8788](#),
[8875](#), [9512](#), [9517](#), [9545](#), [9554](#), [9564](#),
[9808](#), [9814](#), [9816](#), [9818](#), [9820](#), [9822](#),
[9824](#), [9826](#), [9828](#), [9830](#), [9832](#), [9834](#),
[11150](#), [14584](#), [14882](#), [14930](#), [14997](#),
[15024](#), [15632](#), [16071](#), [16092](#), [16108](#),
[16120](#), [16741](#), [16757](#), [16832](#), [17652](#),
[17842](#), [17874](#), [18293](#), [18319](#), [18332](#),
[18365](#), [18409](#), [18916](#), [20615](#), [21710](#),
[26139](#), [26289](#), [27043](#), [31714](#), [31716](#)
 - `\cs_generate_from_arg_count:NNnn`
..... [14](#), [2700](#), [2742](#)

`\cs_generate_variant:Nn` 10, 25, 27, 28, 106,
 261, 368, 3539, 3882, 3884, 3886,
 3888, 4002, 4003, 4073, 4080, 4104,
 4265, 4276, 4277, 4282, 4283, 4288,
 4289, 4292, 4293, 4298, 4299, 4325,
 4326, 4327, 4328, 4329, 4330, 4347,
 4348, 4349, 4350, 4351, 4352, 4353,
 4354, 4371, 4372, 4373, 4374, 4375,
 4376, 4377, 4378, 4424, 4425, 4426,
 4427, 4491, 4492, 4493, 4494, 4556,
 4557, 4562, 4563, 4720, 4738, 4752,
 4761, 4783, 4788, 4790, 4799, 4811,
 4812, 4847, 4850, 4855, 4856, 4956,
 4967, 4968, 4990, 5001, 5138, 5145,
 5147, 5224, 5245, 5247, 5294, 5309,
 5310, 5313, 5314, 5325, 5347, 5348,
 5349, 5350, 5383, 5384, 5389, 5390,
 5479, 5537, 5555, 5581, 5632, 5693,
 5771, 5790, 5828, 5843, 5860, 5861,
 5862, 5875, 5917, 5920, 8080, 8083,
 8086, 8089, 8092, 8121, 8122, 8123,
 8124, 8125, 8126, 8132, 8168, 8169,
 8174, 8175, 8197, 8198, 8199, 8200,
 8205, 8206, 8207, 8208, 8225, 8226,
 8251, 8252, 8269, 8270, 8326, 8327,
 8377, 8390, 8391, 8409, 8435, 8436,
 8488, 8494, 8514, 8543, 8551, 8568,
 8569, 8593, 8616, 8630, 8664, 8666,
 8791, 8812, 8827, 8828, 8833, 8834,
 8836, 8838, 8851, 8852, 8853, 8854,
 8863, 8864, 8865, 8866, 8871, 8872,
 8874, 9481, 9485, 9572, 9578, 9587,
 9588, 9589, 9590, 9593, 9594, 9605,
 9606, 9628, 9630, 9768, 9769, 9774,
 9775, 10029, 10042, 10263, 10303,
 10304, 10305, 10306, 10320, 10321,
 10330, 10331, 10341, 10342, 10343,
 10344, 10354, 10355, 10356, 10357,
 10368, 10393, 10394, 10452, 10453,
 10491, 10492, 10497, 10498, 10581,
 10615, 10639, 10652, 10692, 10701,
 10725, 10732, 10773, 10775, 10777,
 10921, 10922, 10923, 10924, 11142,
 11198, 11746, 11752, 11755, 11758,
 11761, 11764, 11785, 11793, 11801,
 11860, 11861, 11862, 11863, 11870,
 11871, 11890, 11891, 11892, 11893,
 11906, 11916, 11952, 11954, 11956,
 11958, 11975, 11976, 12038, 12053,
 12067, 12073, 12075, 12604, 13029,
 13030, 13031, 13032, 13061, 13066,
 13107, 13128, 13298, 13324, 13332,
 13344, 13359, 13362, 13380, 13488,
 14010, 14019, 14020, 14021, 14368,
 14405, 14587, 14593, 14597, 14598,
 14603, 14604, 14613, 14614, 14617,
 14620, 14628, 14629, 14637, 14638,
 14881, 14911, 14933, 14939, 14942,
 14943, 14948, 14949, 14958, 14959,
 14961, 14963, 14968, 14969, 14974,
 14975, 14996, 15004, 15005, 15007,
 15027, 15033, 15038, 15039, 15044,
 15045, 15054, 15055, 15057, 15059,
 15064, 15065, 15070, 15071, 15075,
 15077, 15328, 15428, 15444, 15499,
 15506, 15575, 15643, 15649, 15826,
 15840, 15846, 15856, 15882, 15888,
 15898, 15938, 15978, 16201, 16347,
 16349, 16380, 16422, 16431, 16440,
 16449, 16457, 16476, 16478, 16492,
 16513, 16556, 17093, 17096, 18799,
 18806, 18807, 18808, 18811, 18812,
 18815, 18816, 18821, 18822, 18829,
 18830, 18831, 18832, 18834, 18836,
 19060, 19122, 22205, 22259, 22337,
 22382, 22397, 22451, 22790, 22810,
 22839, 22893, 22901, 22909, 23069,
 23071, 23093, 23096, 23102, 23108,
 23805, 24525, 27046, 27051, 27052,
 27057, 27058, 27063, 27064, 27069,
 27070, 27078, 27079, 27080, 27086,
 27089, 27095, 27098, 27104, 27107,
 27110, 27111, 27139, 27140, 27148,
 27151, 27154, 27163, 27181, 27194,
 27195, 27206, 27207, 27220, 27221,
 27240, 27241, 27258, 27259, 27284,
 27285, 27296, 27297, 27308, 27309,
 27322, 27323, 27343, 27344, 27347,
 27348, 27351, 27357, 27372, 27375,
 27493, 27499, 27539, 27542, 27559,
 27562, 27579, 27582, 27596, 27599,
 27617, 27620, 27646, 27649, 27655,
 27661, 27777, 27786, 27799, 27812,
 27825, 27831, 27837, 27878, 27891,
 27900, 27907, 27950, 27962, 28002,
 28005, 28020, 28023, 28041, 28242,
 28245, 28407, 28414, 28451, 28454,
 28512, 28518, 28563, 28569, 28700,
 28809, 28895, 28922, 28925, 28981,
 29573, 29881, 29922, 31169, 31604,
 31607, 31610, 31613, 31661, 31664,
 31741, 31742, 31743, 31744, 31777,
 31780, 31829, 31859, 32063, 32066,
 32111, 32115, 32507, 32508, 32512,
 32516, 32696, 32705, 32716, 32726
`\cs_gset:Nn` 14, 2715, 2779
`.cs_gset:Np` 185, 15686

- \cs_gset:Npn 10, 12, 2176, 2595, 2609, 2611, 4154, 4155, 4192, 4234, 8518, 10990, 12128, 12130, 12168, 13911, 13992, 14092, 14099, 14154, 14176, 15695, 15697, 17528, 30223, 32334, 32567, 32569, 32654, 32656, 32658, 32661, 32663, 32665, 32667, 32669, 32671, 32673, 32675, 32677, 32679, 32681, 32683, 32685, 32687, 32689, 32691, 32728, 32731, 32734, 32737, 32740, 32743, 32750, 32752, 32754, 32756, 32758, 32760, 32762, 32764, 32766, 32768, 32770
- \cs_gset:Npx 12, 2176, 2596, 2609, 2612, 8523, 26147
- \cs_gset_eq:NN 15, 2627, 2644, 2652, 4263, 4291, 6175, 6179, 8078, 8297, 8528, 8533, 9584, 9586, 10136, 10919, 11750, 12041, 12049, 13125, 13341, 32564
- \cs_gset_nopar:Nn 14, 2715, 2779
- \cs_gset_nopar:Npn 12, 2176, 2593, 2601, 2605, 3962
- \cs_gset_nopar:Npx 12, 1176, 2176, 2594, 2601, 2606, 4248, 4269, 4274, 4320, 4322, 4324, 4340, 4342, 4344, 4346, 4364, 4366, 4368, 4370, 32007, 32033, 32038, 32065
- \cs_gset_protected:Nn 14, 2715, 2779
- .cs_gset_protected:Np . . . 185, 15686
- \cs_gset_protected:Npn 12, 2176, 2599, 2621, 2623, 4742, 5541, 9099, 10601, 12044, 13223, 14839, 15699, 15701, 19127, 23009, 23017, 23030, 23435, 23703, 23708, 31902, 32250, 32272, 32281, 32291, 32329, 32495, 32502, 32505, 32510, 32514, 32518, 32571, 32574, 32581, 32588, 32600, 32605, 32622, 32694, 32698, 32707, 32718, 32746, 32748, 32772
- \cs_gset_protected:Npx 12, 2176, 2600, 2621, 2624, 9110, 14846, 19134, 32261
- \cs_gset_protected_nopar:Nn 14, 2715, 2779
- \cs_gset_protected_nopar:Npn 12, 2176, 2597, 2615, 2617
- \cs_gset_protected_nopar:Npx 12, 2176, 2598, 2615, 2618
- \cs_if_eq:NNTF 22, 1185, 2811, 2818, 2819, 2822, 2823, 2826, 2827, 10178, 12178, 15598, 17292, 17302, 17328, 17330, 17332, 17533, 25149, 29764, 29787, 29828, 29831, 30083, 31117, 32281, 32291
- \cs_if_eq_p:NN 22, 2811, 25166, 32250
- \cs_if_exist 233
- \cs_if_exist:N 22, 4300, 4301, 8176, 8178, 8839, 8841, 9640, 9642, 10322, 10324, 11977, 11979, 14605, 14607, 14950, 14952, 15046, 15048, 18861, 18862, 27071, 27073
- \cs_if_exist:NTF 16, 22, 313, 365, 443, 585, 616, 2479, 2536, 2538, 2540, 2542, 2544, 2546, 2548, 2550, 2831, 2936, 3006, 3042, 3132, 3156, 3224, 3255, 3506, 3772, 5400, 6146, 6155, 6159, 6173, 8281, 8814, 8815, 8816, 8817, 9493, 9494, 9540, 9885, 9886, 9887, 9889, 9893, 10061, 10176, 10987, 11146, 11446, 11465, 12099, 12928, 13049, 13053, 13081, 13144, 13282, 13286, 13737, 13931, 14034, 14311, 14460, 14564, 15342, 15451, 15542, 15994, 16036, 16044, 16056, 16068, 16075, 16086, 16104, 16118, 16193, 16237, 16245, 16390, 17526, 17701, 18788, 23007, 23025, 23028, 24883, 26261, 27750, 27752, 28754, 29803, 29819, 30105, 30113, 30246, 30972, 30982, 30989, 31304, 31940, 31959, 32455, 32477, 32491
- \cs_if_exist_p:N 22, 313, 2479, 9901, 11281, 11282, 13989, 14023, 14071, 14207, 29843, 31129
- \cs_if_exist_use:N 16, 336, 2535, 12484, 12502, 13457, 16070, 16090, 25331
- \cs_if_exist_use:NTF 16, 2535, 2537, 2539, 2545, 2547, 3802, 3871, 4107, 10151, 15547, 16974, 17659, 17661, 24117, 24124, 24488, 24493, 24530, 24951, 25037, 26196, 30125, 30137, 30200, 30202
- \cs_if_free:NTF 22, 104, 616, 2507, 2576, 3714, 3741, 12474, 32546
- \cs_if_free_p:N . . . 21, 22, 104, 2507
- \cs_log:N 16, 345, 2856
- \cs_meaning:N 15, 322, 2124, 2140, 2148, 2868, 10058
- \cs_new:Nn 12, 105, 2715, 2779
- \cs_new:Npn 10, 11, 14, 104, 104, 372, 943, 1185, 2266, 2283, 2585, 2609, 2613, 2686, 2688, 2690, 2698, 2750, 2816, 2817, 2818, 2819, 2820, 2821, 2822, 2823, 2824, 2825, 2826, 2827, 2872, 2876, 2885, 2894, 2903, 2906, 2915, 2916, 2926,

2927, 2928, 2929, 2930, 2931, 2932,
2934, 2938, 2942, 2945, 2958, 2964,
2970, 2981, 2983, 2990, 2992, 2994,
3001, 3002, 3004, 3008, 3012, 3018,
3020, 3025, 3030, 3036, 3044, 3051,
3052, 3058, 3064, 3070, 3076, 3082,
3089, 3096, 3103, 3110, 3119, 3120,
3122, 3127, 3134, 3138, 3141, 3151,
3152, 3154, 3158, 3161, 3162, 3164,
3166, 3172, 3178, 3180, 3186, 3188,
3195, 3202, 3203, 3204, 3205, 3206,
3208, 3217, 3219, 3222, 3223, 3226,
3230, 3233, 3235, 3240, 3250, 3253,
3257, 3275, 3276, 3278, 3284, 3289,
3291, 3297, 3317, 3319, 3321, 3334,
3341, 3356, 3362, 3368, 3373, 3374,
3397, 3427, 3434, 3440, 3468, 3474,
3479, 3485, 3534, 3535, 3536, 3537,
3606, 3627, 3649, 3652, 3660, 3673,
3688, 3699, 3731, 3836, 3838, 3972,
3978, 3986, 3993, 4000, 4004, 4010,
4043, 4053, 4056, 4160, 4169, 4202,
4207, 4209, 4218, 4224, 4229, 4256,
4419, 4480, 4595, 4660, 4663, 4664,
4665, 4666, 4677, 4692, 4697, 4702,
4707, 4712, 4714, 4723, 4725, 4731,
4733, 4753, 4759, 4762, 4784, 4786,
4789, 4791, 4800, 4805, 4810, 4813,
4825, 4826, 4827, 4829, 4836, 4843,
4845, 4848, 4859, 4871, 4879, 4885,
4891, 4897, 4904, 4915, 4924, 4926,
4933, 4939, 4941, 4943, 4957, 4959,
4961, 4969, 4974, 4979, 4991, 4992,
4993, 4994, 5002, 5048, 5057, 5088,
5109, 5116, 5124, 5130, 5137, 5139,
5144, 5146, 5148, 5149, 5157, 5169,
5178, 5187, 5192, 5198, 5221, 5222,
5223, 5225, 5267, 5282, 5283, 5399,
5415, 5457, 5462, 5467, 5472, 5477,
5482, 5488, 5493, 5498, 5503, 5508,
5510, 5516, 5518, 5526, 5528, 5530,
5556, 5582, 5584, 5586, 5597, 5606,
5609, 5620, 5629, 5631, 5633, 5641,
5643, 5650, 5671, 5681, 5686, 5691,
5692, 5694, 5702, 5704, 5712, 5718,
5724, 5743, 5745, 5754, 5760, 5767,
5769, 5772, 5782, 5789, 5791, 5799,
5804, 5809, 5820, 5827, 5829, 5835,
5837, 5842, 5844, 5850, 5851, 5856,
5857, 5858, 5859, 5863, 5868, 5873,
5876, 5878, 5886, 5891, 5964, 5971,
6012, 6014, 6020, 6026, 6028, 6033,
6038, 6054, 6070, 6084, 6181, 6187,
6231, 6237, 6269, 6279, 6290, 6316,
6323, 6370, 6403, 6417, 6488, 6498,
6535, 6597, 6638, 6640, 6657, 6663,
6686, 6716, 6737, 6746, 6823, 6843,
6863, 6886, 6893, 6920, 7023, 7037,
7064, 7073, 7075, 7096, 7101, 7107,
7112, 7180, 7203, 8066, 8160, 8166,
8196, 8209, 8264, 8345, 8375, 8403,
8408, 8430, 8465, 8467, 8475, 8481,
8489, 8495, 8497, 8499, 8508, 8544,
8552, 8570, 8588, 8592, 8594, 8617,
8618, 8619, 8626, 8628, 8691, 8696,
8698, 8699, 8705, 8713, 8719, 8737,
8745, 8753, 8766, 8768, 8775, 8777,
8875, 8882, 8896, 8901, 8907, 8918,
8923, 8930, 8932, 8934, 8936, 8938,
8940, 8942, 8952, 8957, 8962, 8967,
8972, 8974, 8980, 8998, 9006, 9014,
9020, 9026, 9034, 9042, 9048, 9054,
9061, 9077, 9087, 9089, 9125, 9139,
9145, 9177, 9209, 9211, 9213, 9219,
9225, 9237, 9245, 9257, 9265, 9298,
9331, 9333, 9335, 9337, 9339, 9344,
9349, 9354, 9359, 9360, 9361, 9362,
9363, 9364, 9365, 9366, 9367, 9368,
9369, 9370, 9371, 9372, 9373, 9374,
9375, 9384, 9385, 9394, 9400, 9402,
9411, 9418, 9424, 9426, 9428, 9444,
9455, 9478, 9511, 9551, 9552, 9561,
9562, 9609, 9625, 9652, 9653, 9662,
9663, 9673, 9678, 9683, 9685, 9693,
9694, 9695, 9696, 9697, 9698, 9699,
9700, 9701, 9702, 9712, 9728, 9738,
9754, 9764, 9766, 9770, 9772, 9776,
9784, 9789, 9797, 9803, 9810, 9812,
9814, 9815, 9817, 9819, 9821, 9823,
9825, 9827, 9829, 9831, 9833, 9835,
9840, 9841, 9842, 9843, 9844, 9845,
9846, 9847, 9848, 9849, 9859, 9861,
10088, 10090, 10207, 10208, 10214,
10220, 10226, 10256, 10257, 10296,
10392, 10488, 10490, 10499, 10506,
10509, 10522, 10528, 10566, 10575,
10582, 10588, 10595, 10640, 10642,
10644, 10662, 10669, 10693, 10694,
10697, 10699, 10702, 10710, 10726,
10733, 10741, 10743, 10757, 10759,
10760, 10761, 10763, 10768, 10807,
10877, 10883, 10889, 10895, 10926,
10932, 10973, 10981, 11051, 11066,
11071, 11115, 11117, 11119, 11122,
11125, 11131, 11137, 11143, 11144,
11156, 11166, 11168, 11170, 11179,
11181, 11190, 11196, 11199, 11209,
11215, 11222, 11224, 11256, 11258,

11260, 11266, 11268, 11274, 11395,
11425, 11500, 11512, 11513, 11521,
11530, 11539, 11552, 11553, 11554,
11555, 11558, 11614, 11622, 11624,
11626, 11636, 11646, 11737, 11847,
11894, 11900, 11907, 11915, 11995,
12001, 12023, 12032, 12054, 12061,
12068, 12070, 12094, 12167, 12202,
12266, 12271, 12276, 12278, 12280,
12282, 12288, 12297, 12308, 12314,
12453, 12455, 12472, 12605, 12982,
12991, 12997, 13009, 13014, 13019,
13024, 13207, 13209, 13295, 13385,
13393, 13431, 13448, 13503, 13554,
13563, 13582, 13583, 13591, 13597,
13605, 13615, 13620, 13626, 13632,
13705, 13707, 13709, 13768, 13779,
13790, 13825, 13830, 13836, 13845,
13847, 13856, 13858, 13859, 13861,
13917, 13922, 13942, 13944, 13955,
13956, 13957, 13959, 13977, 14074,
14076, 14078, 14080, 14085, 14101,
14104, 14111, 14125, 14135, 14145,
14167, 14169, 14242, 14256, 14270,
14304, 14458, 14579, 14639, 14644,
14646, 14654, 14662, 14670, 14672,
14684, 14690, 14703, 14705, 14707,
14709, 14711, 14719, 14724, 14729,
14734, 14739, 14741, 14747, 14749,
14757, 14765, 14771, 14777, 14785,
14793, 14799, 14805, 14812, 14826,
14860, 14862, 14868, 14882, 14883,
14890, 14898, 14900, 14902, 14990,
14993, 14997, 14999, 15002, 15072,
15100, 15102, 15109, 15111, 15113,
15124, 15131, 15135, 15143, 15152,
15156, 15164, 15166, 15174, 15178,
15185, 15192, 15199, 15208, 15218,
15224, 15230, 15231, 15232, 15233,
15234, 15246, 15258, 15266, 15271,
15277, 15411, 16116, 16182, 16191,
16197, 16199, 16202, 16213, 16218,
16224, 16348, 16350, 16352, 16366,
16423, 16425, 16432, 16438, 16456,
16458, 16466, 16563, 16564, 16565,
16566, 16567, 16568, 16569, 16570,
16571, 16572, 16582, 16606, 16608,
16610, 16619, 16621, 16628, 16640,
16641, 16643, 16653, 16663, 16673,
16683, 16691, 16693, 16700, 16702,
16703, 16708, 16715, 16729, 16731,
16747, 16748, 16756, 16758, 16767,
16769, 16781, 16786, 16790, 16795,
16797, 16799, 16801, 16803, 16810,
16812, 16820, 16822, 16834, 16836,
16838, 16840, 16864, 16866, 16868,
16869, 16870, 16872, 16874, 16876,
16878, 16896, 16911, 16912, 16918,
16935, 16948, 16954, 17080, 17081,
17082, 17083, 17084, 17085, 17086,
17091, 17094, 17140, 17142, 17144,
17146, 17152, 17156, 17158, 17167,
17168, 17177, 17190, 17203, 17210,
17224, 17240, 17252, 17263, 17273,
17279, 17290, 17300, 17326, 17337,
17354, 17365, 17370, 17390, 17392,
17403, 17408, 17421, 17444, 17445,
17449, 17466, 17467, 17491, 17499,
17517, 17548, 17574, 17578, 17581,
17583, 17589, 17601, 17613, 17620,
17626, 17634, 17657, 17672, 17691,
17699, 17714, 17729, 17740, 17750,
17760, 17765, 17774, 17791, 17804,
17809, 17815, 17817, 17824, 17854,
17882, 17898, 17909, 17914, 17932,
17950, 17961, 17976, 17981, 17991,
18001, 18011, 18027, 18075, 18080,
18087, 18095, 18101, 18106, 18110,
18127, 18135, 18167, 18184, 18198,
18217, 18225, 18234, 18243, 18254,
18256, 18270, 18280, 18281, 18298,
18305, 18310, 18323, 18336, 18341,
18371, 18385, 18415, 18416, 18420,
18437, 18459, 18461, 18472, 18504,
18508, 18523, 18540, 18564, 18566,
18568, 18570, 18580, 18585, 18596,
18608, 18619, 18632, 18652, 18670,
18672, 18684, 18690, 18698, 18712,
18719, 18730, 18737, 18751, 18857,
18859, 18876, 18898, 18903, 18920,
18947, 18948, 18949, 18950, 18966,
18977, 18985, 18997, 19003, 19009,
19017, 19025, 19031, 19037, 19045,
19053, 19071, 19084, 19106, 19154,
19160, 19171, 19195, 19197, 19199,
19201, 19209, 19213, 19220, 19227,
19228, 19229, 19230, 19231, 19232,
19235, 19237, 19266, 19274, 19285,
19287, 19289, 19291, 19298, 19322,
19324, 19334, 19349, 19358, 19372,
19380, 19388, 19395, 19402, 19410,
19420, 19434, 19445, 19446, 19452,
19469, 19476, 19478, 19485, 19490,
19507, 19508, 19509, 19528, 19534,
19544, 19556, 19563, 19577, 19585,
19623, 19632, 19653, 19655, 19657,
19666, 19677, 19689, 19704, 19717,
19730, 19738, 19756, 19774, 19781,

19789, 19799, 19800, 19809, 19810,
19819, 19829, 19843, 19853, 19864,
19872, 19874, 19885, 19891, 19926,
19947, 19949, 19951, 19953, 19960,
19969, 19974, 19981, 19988, 20008,
20013, 20030, 20041, 20046, 20056,
20058, 20068, 20075, 20077, 20083,
20085, 20087, 20091, 20110, 20111,
20116, 20124, 20125, 20148, 20161,
20168, 20176, 20177, 20178, 20179,
20180, 20181, 20189, 20195, 20197,
20199, 20221, 20226, 20236, 20246,
20257, 20270, 20281, 20286, 20293,
20302, 20304, 20313, 20322, 20336,
20338, 20340, 20353, 20363, 20368,
20377, 20385, 20392, 20398, 20407,
20409, 20421, 20426, 20434, 20439,
20449, 20455, 20461, 20468, 20475,
20477, 20482, 20484, 20489, 20491,
20505, 20515, 20527, 20532, 20539,
20549, 20551, 20553, 20564, 20578,
20592, 20612, 20625, 20627, 20632,
20645, 20650, 20658, 20663, 20673,
20685, 20715, 20716, 20717, 20719,
20721, 20723, 20737, 20743, 20752,
20771, 20777, 20787, 20806, 20814,
20847, 20853, 20862, 20864, 20878,
20937, 20945, 20963, 20980, 20981,
20986, 21011, 21034, 21063, 21079,
21089, 21100, 21121, 21136, 21141,
21146, 21148, 21162, 21168, 21183,
21191, 21201, 21211, 21224, 21242,
21248, 21262, 21277, 21315, 21317,
21319, 21321, 21323, 21338, 21353,
21368, 21383, 21398, 21413, 21421,
21435, 21437, 21443, 21455, 21463,
21470, 21696, 21703, 21740, 21748,
21749, 21760, 21767, 21769, 21775,
21786, 21796, 21803, 21810, 21825,
21864, 21877, 21908, 21914, 21921,
21941, 21943, 21960, 21975, 21988,
21995, 22000, 22002, 22011, 22024,
22027, 22048, 22061, 22076, 22094,
22109, 22119, 22128, 22141, 22157,
22174, 22187, 22193, 22195, 22200,
22201, 22202, 22203, 22206, 22211,
22217, 22222, 22224, 22247, 22255,
22257, 22260, 22265, 22271, 22276,
22278, 22301, 22326, 22335, 22336,
22338, 22343, 22345, 22350, 22352,
22362, 22370, 22378, 22380, 22383,
22388, 22393, 22395, 22396, 22398,
22403, 22408, 22410, 22415, 22422,
22436, 22441, 22443, 22453, 22455,
22457, 22459, 22461, 22472, 22482,
22484, 22490, 22497, 22503, 22513,
22518, 22520, 22528, 22529, 22543,
22550, 22556, 22557, 22570, 22585,
22591, 22613, 22628, 22638, 22659,
22668, 22691, 22709, 22720, 22725,
22736, 22753, 22758, 22805, 22811,
22825, 22894, 22902, 22910, 22916,
22923, 22928, 22934, 22946, 23083,
23238, 23251, 23256, 23262, 23263,
23270, 23277, 23284, 23291, 23298,
23299, 23301, 23308, 23314, 23393,
23398, 23399, 23407, 23413, 23590,
23595, 23602, 23639, 23644, 23659,
23682, 23687, 23735, 23741, 23759,
23764, 23779, 23781, 23783, 23790,
23827, 23856, 23861, 23886, 23888,
24115, 24121, 24132, 24137, 24150,
24155, 24167, 24179, 24189, 24198,
24218, 24329, 24347, 24355, 24367,
24379, 24871, 25147, 25162, 25202,
25243, 25403, 25531, 25923, 26049,
26051, 26057, 26058, 26065, 26075,
26227, 26592, 26597, 26996, 27037,
29003, 29004, 29008, 29009, 29383,
29388, 29403, 29413, 29424, 29438,
29455, 29468, 29470, 29471, 29556,
29564, 29571, 29574, 29576, 29582,
29593, 29605, 29629, 29649, 29665,
29672, 29686, 29697, 29706, 29711,
29717, 29730, 29749, 29755, 29771,
29777, 29783, 29808, 29813, 29815,
29826, 29839, 29840, 29855, 29856,
29869, 29871, 29887, 29889, 29891,
29893, 29895, 29897, 29899, 29901,
29903, 29913, 29920, 29923, 29925,
29931, 29942, 29947, 29961, 29973,
29987, 29993, 29999, 30004, 30010,
30024, 30035, 30044, 30051, 30058,
30065, 30074, 30079, 30090, 30095,
30099, 30101, 30103, 30135, 30145,
30151, 30162, 30194, 30196, 30198,
30207, 30238, 30240, 30242, 30244,
30255, 30263, 30269, 30291, 30305,
30314, 30316, 30321, 30329, 30399,
30406, 30419, 30444, 30454, 30461,
30484, 30497, 30507, 30514, 30523,
30535, 30542, 30562, 30576, 30587,
30605, 30618, 31009, 31016, 31018,
31029, 31030, 31035, 31040, 31047,
31058, 31063, 31065, 31067, 31072,
31074, 31085, 31096, 31101, 31108,
31113, 31124, 31126, 31148, 31149,
31159, 31302, 31712, 31720, 31733,

- 31735, 31737, 31739, 31745, 31783,
 31785, 31787, 31789, 31791, 31793,
 31795, 31797, 31799, 31804, 31810,
 31816, 31819, 31820, 31830, 31838,
 31840, 31846, 31852, 31894, 31909,
 31919, 32082, 32090, 32110, 32112,
 32113, 32116, 32118, 32120, 32122,
 32130, 32198, 32200, 32230, 32440
 \cs_new:Npx 11, 34, 34, 366,
 367, 2585, 2609, 2614, 3565, 10653,
 10663, 13430, 13442, 13812, 13820,
 13968, 16722, 17560, 18147, 19293,
 21302, 21308, 21920, 23615, 24138,
 24140, 24142, 24144, 24146, 24148,
 29610, 29798, 30123, 30173, 30282,
 30632, 31756, 31758, 31760, 31767
 \cs_new_eq:NN
 15, 105, 337, 339, 580, 2399,
 2627, 2905, 2914, 2951, 3221, 3515,
 3516, 3517, 3518, 3519, 3520, 3521,
 3522, 3523, 3524, 3525, 3526, 3527,
 3528, 3529, 3532, 3533, 3774, 3970,
 4244, 4247, 4550, 4551, 5293, 5307,
 5308, 5311, 5312, 5378, 5915, 5916,
 5918, 5919, 6248, 6264, 6266, 8073,
 8093, 8094, 8095, 8096, 8097, 8098,
 8099, 8100, 8324, 8631, 8632, 8633,
 8634, 8635, 8636, 8637, 8638, 8639,
 8640, 8641, 8642, 8643, 8644, 8645,
 8646, 8647, 8648, 8649, 8650, 8651,
 8652, 8653, 8654, 8655, 8656, 8684,
 8685, 8686, 8687, 8688, 8818, 8819,
 8822, 8873, 9124, 9480, 9484, 9569,
 9571, 9591, 9592, 9871, 9872, 9873,
 9874, 9877, 9878, 9879, 9880, 10052,
 10203, 10259, 10260, 10264, 10265,
 10266, 10267, 10268, 10269, 10270,
 10271, 10272, 10273, 10274, 10275,
 10276, 10277, 10278, 10279, 10420,
 10421, 10422, 10423, 10424, 10425,
 10426, 10427, 10428, 10429, 10430,
 10431, 10432, 10433, 10434, 10435,
 10925, 10989, 11296, 11298, 11299,
 11300, 11302, 11305, 11306, 11548,
 11549, 11550, 11765, 11766, 11767,
 11768, 11769, 11770, 11771, 11772,
 13060, 13083, 13141, 13297, 13386,
 13908, 14310, 14384, 14392, 14574,
 14575, 14576, 14880, 14910, 14914,
 14915, 14995, 14998, 15001, 15006,
 15010, 15011, 15074, 15076, 15080,
 15081, 16319, 16320, 16560, 16561,
 16562, 16766, 16947, 17223, 17251,
 17259, 17260, 17261, 17270, 17272,
 18074, 18193, 18194, 18195, 18798,
 18809, 18810, 22450, 22452, 22496,
 23386, 23387, 23818, 23830, 23959,
 23960, 24060, 24068, 24089, 24128,
 24129, 24130, 24131, 24308, 25802,
 26400, 27036, 27075, 27076, 27077,
 27108, 27109, 27120, 27121, 27122,
 27227, 27256, 27257, 27330, 27345,
 27346, 27747, 27970, 27971, 27972,
 27973, 27974, 27975, 28969, 28970,
 28998, 28999, 29000, 29959, 30097,
 30192, 30221, 30257, 30259, 30261,
 30654, 30656, 32019, 32020, 32429
 \cs_new_nopar:Nn 13, 2715, 2779
 \cs_new_nopar:Npn
 11, 337, 338, 2585, 2601, 2607
 \cs_new_nopar:Npx 11, 2585, 2601, 2608
 \cs_new_protected:Nn . 13, 2715, 2779
 \cs_new_protected:Npn . . 11, 372,
 1185, 2270, 2287, 2585, 2621, 2625,
 2627, 2628, 2629, 2630, 2631, 2632,
 2633, 2634, 2635, 2640, 2641, 2642,
 2643, 2645, 2700, 2710, 2712, 2723,
 2732, 2829, 2838, 2840, 2842, 2844,
 2846, 2854, 2856, 2857, 2859, 2860,
 2862, 2917, 2952, 3117, 3146, 3216,
 3247, 3539, 3552, 3570, 3574, 3577,
 3586, 3710, 3727, 3737, 3746, 3770,
 3778, 3790, 3798, 3809, 3811, 3813,
 3815, 3817, 3828, 3830, 3843, 3851,
 3862, 3881, 3883, 3885, 3887, 3889,
 3959, 4061, 4063, 4074, 4081, 4087,
 4105, 4114, 4119, 4124, 4129, 4134,
 4140, 4145, 4152, 4158, 4167, 4177,
 4179, 4181, 4183, 4185, 4190, 4235,
 4260, 4266, 4271, 4278, 4280, 4284,
 4286, 4290, 4291, 4294, 4296, 4313,
 4315, 4317, 4319, 4321, 4323, 4331,
 4333, 4335, 4337, 4339, 4341, 4343,
 4345, 4355, 4357, 4359, 4361, 4363,
 4365, 4367, 4369, 4387, 4393, 4395,
 4397, 4409, 4428, 4443, 4461, 4483,
 4485, 4487, 4489, 4495, 4517, 4523,
 4552, 4554, 4558, 4560, 4633, 4634,
 4635, 4739, 4750, 4768, 4774, 4776,
 4851, 4853, 4963, 4965, 5244, 5246,
 5248, 5253, 5255, 5268, 5339, 5341,
 5343, 5345, 5351, 5366, 5379, 5381,
 5385, 5387, 5538, 5553, 5562, 5572,
 5574, 5924, 6044, 6060, 6076, 6082,
 6086, 6088, 6108, 6126, 6134, 6144,
 6153, 6207, 6255, 6263, 6265, 6267,
 6277, 6283, 6307, 6318, 6324, 6327,
 6329, 6334, 6351, 6360, 6380, 6393,

6471, 6519, 6572, 6655, 6661, 6684,
6714, 6735, 6808, 6904, 6909, 6911,
6913, 6989, 6991, 6993, 6998, 7008,
7087, 7092, 7094, 7147, 7149, 7151,
7156, 7166, 8075, 8081, 8084, 8087,
8090, 8101, 8106, 8111, 8116, 8127,
8133, 8135, 8137, 8170, 8172, 8180,
8188, 8201, 8203, 8211, 8213, 8215,
8227, 8229, 8231, 8253, 8255, 8257,
8284, 8285, 8286, 8308, 8319, 8349,
8357, 8367, 8378, 8380, 8382, 8384,
8392, 8410, 8412, 8414, 8515, 8520,
8525, 8531, 8537, 8558, 8663, 8665,
8667, 8785, 8792, 8825, 8826, 8829,
8831, 8835, 8837, 8843, 8845, 8847,
8849, 8855, 8857, 8859, 8861, 8867,
8869, 8876, 9091, 9093, 9095, 9102,
9104, 9106, 9118, 9482, 9486, 9509,
9514, 9515, 9526, 9528, 9529, 9530,
9571, 9573, 9579, 9581, 9583, 9585,
9595, 9600, 9621, 9623, 9627, 9629,
9631, 9867, 9902, 9919, 9961, 9967,
9975, 9986, 10009, 10019, 10026,
10032, 10039, 10043, 10048, 10103,
10107, 10137, 10143, 10213, 10261,
10280, 10282, 10284, 10307, 10309,
10311, 10326, 10328, 10332, 10334,
10336, 10345, 10347, 10349, 10358,
10366, 10369, 10371, 10373, 10381,
10409, 10438, 10440, 10442, 10454,
10456, 10458, 10493, 10495, 10539,
10596, 10610, 10616, 10627, 10632,
10774, 10776, 10778, 10788, 10789,
10790, 10805, 10809, 10811, 10813,
10815, 10817, 10819, 10821, 10823,
10825, 10827, 10829, 10831, 10833,
10835, 10837, 10839, 10841, 10843,
10845, 10847, 10849, 10851, 10853,
10855, 10857, 10859, 10861, 10863,
10865, 10867, 10869, 10871, 10873,
10875, 10879, 10881, 10885, 10887,
10891, 10893, 10897, 10909, 11559,
11561, 11563, 11568, 11575, 11584,
11602, 11604, 11606, 11608, 11610,
11612, 11695, 11712, 11717, 11724,
11729, 11731, 11747, 11753, 11756,
11759, 11762, 11778, 11786, 11794,
11802, 11807, 11814, 11816, 11818,
11823, 11825, 11837, 11839, 11848,
11854, 11864, 11872, 11881, 11939,
11940, 11941, 11960, 11962, 11964,
12039, 12072, 12074, 12076, 12102,
12110, 12115, 12117, 12124, 12126,
12133, 12174, 12203, 12223, 12228,
12239, 12323, 12325, 12366, 12443,
12457, 12482, 12504, 12505, 12518,
12523, 12549, 12558, 12560, 12562,
12579, 12606, 12608, 12610, 12612,
12619, 13060, 13064, 13079, 13091,
13117, 13129, 13130, 13131, 13158,
13160, 13171, 13173, 13192, 13194,
13196, 13211, 13213, 13215, 13221,
13228, 13237, 13239, 13241, 13246,
13297, 13302, 13306, 13325, 13333,
13345, 13346, 13347, 13357, 13360,
13363, 13369, 13375, 13382, 13384,
13394, 13425, 13436, 13454, 13489,
13512, 13524, 13543, 13547, 13636,
13652, 13661, 13669, 13678, 13685,
13691, 13868, 13902, 14005, 14063,
14182, 14184, 14186, 14188, 14198,
14228, 14328, 14333, 14339, 14340,
14345, 14369, 14386, 14394, 14400,
14406, 14419, 14440, 14441, 14442,
14473, 14486, 14498, 14508, 14581,
14588, 14594, 14595, 14599, 14601,
14609, 14611, 14615, 14618, 14621,
14623, 14630, 14632, 14713, 14835,
14842, 14854, 14912, 14916, 14927,
14934, 14940, 14941, 14944, 14946,
14954, 14956, 14960, 14962, 14964,
14966, 14970, 14972, 15008, 15012,
15021, 15028, 15034, 15036, 15040,
15042, 15050, 15052, 15056, 15058,
15060, 15062, 15066, 15068, 15078,
15082, 15320, 15322, 15329, 15334,
15339, 15352, 15358, 15383, 15395,
15413, 15429, 15445, 15447, 15449,
15465, 15476, 15478, 15480, 15497,
15500, 15507, 15522, 15535, 15540,
15550, 15558, 15560, 15576, 15586,
15614, 15623, 15632, 15633, 15644,
15650, 15652, 15654, 15656, 15658,
15660, 15662, 15664, 15666, 15668,
15670, 15672, 15674, 15676, 15678,
15680, 15682, 15684, 15686, 15688,
15690, 15692, 15694, 15696, 15698,
15700, 15702, 15704, 15706, 15708,
15710, 15712, 15714, 15716, 15718,
15720, 15722, 15724, 15726, 15728,
15730, 15732, 15734, 15736, 15738,
15740, 15742, 15744, 15746, 15748,
15750, 15752, 15754, 15756, 15758,
15760, 15762, 15764, 15766, 15768,
15770, 15772, 15774, 15776, 15778,
15780, 15782, 15784, 15786, 15788,
15790, 15792, 15794, 15796, 15798,
15800, 15802, 15804, 15806, 15827,

15829, 15835, 15841, 15847, 15854,
15857, 15876, 15883, 15889, 15896,
15899, 15918, 15939, 15941, 15947,
15952, 15957, 15979, 15992, 16006,
16032, 16051, 16066, 16081, 16099,
16125, 16149, 16181, 16250, 16252,
16254, 16326, 16335, 16371, 16373,
16381, 16392, 16400, 16407, 16413,
16441, 16450, 16475, 16477, 16479,
16490, 16495, 16500, 16514, 16519,
16524, 16539, 16550, 16573, 16576,
16687, 16972, 16989, 16991, 16993,
16995, 17023, 17025, 17027, 17029,
17049, 17051, 17053, 17055, 17057,
17059, 17061, 17063, 17065, 18797,
18800, 18802, 18804, 18813, 18814,
18817, 18819, 18823, 18824, 18825,
18826, 18827, 18833, 18835, 18837,
18842, 18844, 19123, 19130, 19142,
21953, 22778, 22791, 22830, 22840,
22852, 22857, 22867, 22875, 22881,
22966, 22985, 22993, 23005, 23042,
23049, 23068, 23070, 23072, 23091,
23094, 23097, 23103, 23109, 23124,
23133, 23153, 23163, 23174, 23184,
23194, 23195, 23202, 23208, 23218,
23228, 23324, 23331, 23333, 23349,
23415, 23426, 23444, 23454, 23456,
23480, 23487, 23499, 23502, 23505,
23515, 23523, 23530, 23539, 23554,
23571, 23582, 23692, 23699, 23701,
23719, 23729, 23825, 23828, 23831,
23833, 23842, 23848, 23854, 23892,
23894, 23895, 23900, 23906, 23914,
23926, 23942, 23961, 23971, 23979,
23981, 23989, 24001, 24021, 24023,
24028, 24036, 24038, 24045, 24050,
24052, 24054, 24061, 24069, 24071,
24073, 24075, 24082, 24087, 24090,
24096, 24323, 24387, 24400, 24411,
24424, 24457, 24486, 24491, 24496,
24517, 24526, 24535, 24540, 24547,
24560, 24562, 24564, 24566, 24572,
24594, 24607, 24634, 24639, 24673,
24708, 24729, 24731, 24741, 24750,
24755, 24764, 24773, 24789, 24802,
24808, 24819, 24832, 24838, 24857,
24877, 24908, 24919, 24934, 24947,
24965, 24973, 24978, 24980, 24982,
24999, 25018, 25020, 25043, 25055,
25075, 25096, 25103, 25110, 25122,
25128, 25186, 25221, 25230, 25249,
25268, 25274, 25337, 25347, 25349,
25351, 25358, 25414, 25427, 25443,
25448, 25461, 25477, 25484, 25491,
25493, 25495, 25502, 25516, 25532,
25541, 25555, 25567, 25585, 25594,
25596, 25608, 25617, 25629, 25642,
25649, 25669, 25700, 25734, 25752,
25758, 25767, 25806, 25819, 25841,
25858, 25880, 25889, 25900, 25929,
25944, 25953, 25962, 25974, 25981,
25983, 25985, 26005, 26010, 26017,
26022, 26027, 26032, 26081, 26116,
26158, 26174, 26194, 26206, 26220,
26254, 26268, 26279, 26286, 26295,
26330, 26336, 26339, 26347, 26353,
26356, 26365, 26368, 26371, 26374,
26379, 26388, 26391, 26394, 26399,
26405, 26410, 26415, 26420, 26428,
26448, 26450, 26454, 26455, 26479,
26487, 26496, 26508, 26517, 26525,
26565, 26609, 26636, 26641, 26643,
26673, 26701, 27012, 27014, 27016,
27023, 27040, 27047, 27049, 27053,
27055, 27059, 27061, 27065, 27067,
27081, 27087, 27090, 27096, 27099,
27105, 27112, 27114, 27116, 27118,
27135, 27137, 27146, 27149, 27152,
27155, 27157, 27164, 27182, 27184,
27189, 27196, 27201, 27208, 27214,
27222, 27228, 27234, 27242, 27247,
27252, 27254, 27260, 27262, 27264,
27269, 27274, 27279, 27286, 27291,
27298, 27303, 27310, 27316, 27324,
27331, 27337, 27349, 27352, 27370,
27373, 27376, 27386, 27420, 27431,
27442, 27453, 27464, 27475, 27488,
27494, 27500, 27515, 27522, 27532,
27537, 27540, 27543, 27557, 27560,
27563, 27577, 27580, 27583, 27594,
27597, 27600, 27615, 27618, 27621,
27630, 27644, 27647, 27650, 27656,
27662, 27674, 27760, 27769, 27778,
27787, 27800, 27813, 27826, 27832,
27838, 27866, 27879, 27892, 27893,
27894, 27901, 27908, 27937, 27938,
27939, 27951, 27976, 27986, 27993,
28000, 28003, 28006, 28018, 28021,
28024, 28036, 28042, 28048, 28054,
28056, 28058, 28064, 28085, 28087,
28089, 28095, 28129, 28144, 28240,
28243, 28246, 28288, 28306, 28312,
28318, 28330, 28349, 28358, 28369,
28375, 28380, 28388, 28401, 28408,
28415, 28427, 28449, 28452, 28455,
28470, 28477, 28483, 28492, 28499,
28507, 28513, 28519, 28558, 28564,

- 28570, 28591, 28600, 28619, 28624,
 28638, 28643, 28656, 28667, 28679,
 28693, 28753, 28755, 28802, 28810,
 28839, 28888, 28896, 28920, 28923,
 28926, 28971, 28979, 28982, 28984,
 28986, 28988, 28990, 29005, 29006,
 29876, 31164, 31602, 31605, 31608,
 31611, 31614, 31659, 31662, 31665,
 31751, 31753, 31755, 31775, 31778,
 31860, 31862, 31864, 31870, 31872,
 31874, 31880, 31882, 31884, 31890,
 31892, 31899, 31982, 31988, 32004,
 32006, 32008, 32010, 32021, 32026,
 32031, 32036, 32041, 32058, 32059,
 32061, 32064, 32067, 32078, 32080,
 32092, 32097, 32102, 32145, 32147,
 32149, 32151, 32168, 32181, 32186,
 32212, 32236, 32238, 32259, 32278,
 32285, 32302, 32326, 32331, 32438
 \cs_new_protected:Npx
 . . . 11, 366, 367, 371, 2585, 2621,
 2626, 2717, 2781, 3554, 3558, 3563,
 3722, 3726, 5320, 10915, 11661,
 11676, 11681, 11686, 12334, 12336,
 12338, 12340, 12342, 12351, 12353,
 12355, 12628, 12630, 12632, 12634,
 12636, 12645, 12647, 12649, 13108,
 13884, 14351, 24702, 24716, 24718
 \cs_new_protected_nopar:Nn
 13, 2715, 2779
 \cs_new_protected_nopar:Npn
 11, 2585, 2602, 2615, 2619
 \cs_new_protected_nopar:Npx
 11, 2585, 2615, 2620
 \cs_prefix_spec:N
 18, 2870, 32749, 32750
 \cs_replacement_spec:N
 18, 2870, 16263, 32753, 32754
 \cs_set:Nn 13, 342, 2715, 2779
 .cs_set:Np 185, 15686
 \cs_set:Npn
 . . . 10, 11, 104, 104, 329, 338, 342,
 599, 2162, 2192, 2199, 2201, 2204,
 2205, 2206, 2207, 2208, 2209, 2210,
 2211, 2212, 2213, 2214, 2215, 2216,
 2217, 2218, 2219, 2220, 2221, 2222,
 2223, 2224, 2226, 2227, 2228, 2229,
 2230, 2231, 2232, 2233, 2234, 2257,
 2259, 2261, 2264, 2281, 2330, 2333,
 2395, 2443, 2445, 2447, 2449, 2454,
 2460, 2461, 2465, 2472, 2475, 2535,
 2537, 2539, 2541, 2543, 2545, 2547,
 2549, 2568, 2585, 2601, 2609, 2609,
 2715, 2779, 4200, 4222, 4469, 4526,
 4642, 4857, 5368, 5404, 7014, 7171,
 8721, 8729, 10056, 10467, 10556,
 10965, 11284, 11572, 11841, 12119,
 12121, 13401, 13724, 14245, 15687,
 15689, 16229, 16998, 17006, 17015,
 17032, 17040, 17068, 23064, 24100,
 24101, 24102, 24419, 24420, 24986,
 24988, 25005, 25007, 25301, 25328,
 25367, 25861, 26160, 29018, 29217,
 31266, 31267, 31329, 31336, 31341,
 31342, 32157, 32159, 32165, 32283
 \cs_set:Npx 11, 348, 701, 2162, 2609,
 2610, 4528, 10543, 11570, 11589,
 11595, 13459, 13460, 13461, 13462,
 13463, 23844, 23850, 25518, 29219
 \cs_set_eq:NN 15, 105, 339,
 531, 2397, 2627, 3558, 3576, 3726,
 4290, 5402, 5403, 6095, 6104, 6916,
 8259, 8260, 8262, 8416, 8417, 8428,
 9518, 9580, 9582, 10918, 11155,
 11333, 11566, 11587, 11594, 13465,
 13466, 13467, 13468, 13470, 13472,
 13473, 15511, 15527, 15531, 15581,
 15592, 15602, 23326, 23327, 23332,
 23483, 23526, 23551, 25293, 25302,
 25325, 25867, 32154, 32164, 32478
 \cs_set_nopar:Nn 13, 2715, 2779
 \cs_set_nopar:Npn 10, 11,
 133, 338, 2162, 2191, 2249, 2250,
 2601, 2603, 15467, 15538, 29265, 29267
 \cs_set_nopar:Npx 11,
 1176, 2162, 2195, 2601, 2604, 2954,
 3148, 4314, 4316, 4318, 4332, 4334,
 4336, 4338, 4356, 4358, 4360, 4362,
 15516, 32005, 32023, 32028, 32062
 \cs_set_protected:Nn . . . 13, 2715, 2779
 .cs_set_protected:Np 185, 15686
 \cs_set_protected:Npn
 10, 11, 254, 339,
 2162, 2178, 2180, 2182, 2184, 2186,
 2188, 2193, 2236, 2237, 2242, 2247,
 2248, 2251, 2263, 2265, 2267, 2268,
 2269, 2271, 2280, 2282, 2284, 2285,
 2286, 2288, 2297, 2309, 2335, 2352,
 2371, 2379, 2387, 2396, 2398, 2400,
 2412, 2426, 2463, 2551, 2564, 2566,
 2570, 2572, 2574, 2582, 2587, 2621,
 2621, 2655, 2676, 3744, 3905, 4649,
 5289, 5316, 6517, 6570, 8333, 10907,
 11029, 11421, 11439, 11693, 12247,
 12320, 12615, 12617, 12980, 13084,
 13381, 13383, 13522, 13603, 13703,
 13720, 14210, 14421, 14982, 15098,
 15244, 15498, 15691, 15693, 16155,

- 16953, 17447, 17524, 18108, 18182,
18196, 18418, 18435, 18470, 18506,
18521, 18538, 20089, 23328, 24714,
24739, 24748, 25278, 25287, 25289,
25291, 25294, 25296, 25303, 25305,
25310, 25312, 25317, 25319, 25321,
25323, 25326, 26024, 26025, 26452,
27871, 27884, 27918, 28201, 29027,
29242, 29252, 29262, 29287, 29302,
29320, 29328, 29360, 30663, 30666,
30697, 30708, 30724, 30922, 30925,
30946, 30977, 31244, 31256, 31318,
31369, 32276, 32282, 32443, 32449,
32468, 32474, 32483, 32544, 32636
- \cs_set_protected:Npx . . . 11, 240,
2162, 2621, 2622, 12490, 15502, 32488
- \cs_set_protected_nopar:Nn
. 14, 2715, 2779
- \cs_set_protected_nopar:Npn
. 12, 338, 2162, 2615, 2615
- \cs_set_protected_nopar:Npx
. 12, 2162, 2615, 2616
- \cs_show:N 16, 16, 22, 345, 2856
- \cs_split_function:N
. 17, 2276, 2293, 2405, 2406, 2463,
2687, 2728, 3545, 3848, 4077, 4098
- \cs_to_sr:N 1179
- \cs_to_str:N
. 4, 17, 51, 60, 333, 333, 334, 365,
434, 2454, 2469, 3343, 3509, 4205,
4227, 5899, 5900, 5901, 5902, 5903,
5904, 5905, 5906, 5907, 5908, 5909,
5910, 13386, 16951, 23858, 25259,
29811, 31228, 32009, 32095, 32100,
32108, 32456, 32460, 32477, 32478
- \cs_undefine:N
. 15, 528, 703, 2643, 12653, 12654,
12655, 13086, 22796, 29001, 29002
- cs internal commands:
- __cs_count_signature:N . . . 332, 2686
- __cs_count_signature:n 2686
- __cs_count_signature:nnN 2686
- __cs_generate_from_signature:n .
. 2737, 2750
- __cs_generate_from_signature:NNn
. 2719, 2723
- __cs_generate_from_signature:nnNNn
. 2727, 2732
- __cs_generate_internal_c:NN . 3811
- __cs_generate_internal_end:w . . .
. 3794, 3828
- __cs_generate_internal_long:nnnNNn
. 3832, 3836
- __cs_generate_internal_long:w . .
. 3795, 3830
- __cs_generate_internal_loop:nwnnw
. 3792,
3798, 3810, 3812, 3814, 3816, 3819
- __cs_generate_internal_N:NN . 3809
- __cs_generate_internal_n:NN . 3813
- __cs_generate_internal_one_-
go:NNn 372, 3767, 3790
- __cs_generate_internal_other:NN
. 3803, 3817
- __cs_generate_internal_test:Nw .
. 3752, 3774, 3778
- __cs_generate_internal_test_-
aux:w . . 3754, 3770, 3775, 3781, 3784
- __cs_generate_internal_variant:n
. 376, 3717, 3722, 3902, 3908
- __cs_generate_internal_variant:NNn
. 372, 3742, 3746
- __cs_generate_internal_variant:wNwNn
. 3724, 3737
- __cs_generate_internal_variant_-
loop:n 3722
- __cs_generate_internal_x:NN . 3815
- __cs_generate_variant:N . 3541, 3554
- __cs_generate_variant:n 3843
- __cs_generate_variant:nnNN
. 3544, 3577
- __cs_generate_variant:nnNnn . 3843
- __cs_generate_variant:Nnnw
. 3584, 3586
- __cs_generate_variant:w 3843
- __cs_generate_variant:ww 3554
- __cs_generate_variant:wwNN
. 368, 369, 3593, 3710
- __cs_generate_variant:wwNw . . 3554
- __cs_generate_variant_F_-
form:nnn 3843
- __cs_generate_variant_loop:nNwN
. 368, 369, 3594, 3606
- __cs_generate_variant_loop_-
base:N 3606
- __cs_generate_variant_loop_-
end:nwwwNNnn . 368, 369, 3596, 3606
- __cs_generate_variant_loop_-
invalid:NNwNNnn 369, 3606
- __cs_generate_variant_loop_-
long:wNNnn 369, 3599, 3606
- __cs_generate_variant_loop_-
same:w 369, 3606
- __cs_generate_variant_loop_-
special:NNwNNnn 3606, 3705
- __cs_generate_variant_p_-
form:nnn 3843

- __cs_generate_variant_same:N [369](#), [3651](#), [3699](#)
 - __cs_generate_variant_T_-
form:nnn [3843](#)
 - __cs_generate_variant_TF_-
form:nnn [3843](#)
 - __cs_get_function_name:N [332](#)
 - __cs_get_function_signature:N [332](#)
 - __cs_parm_from_arg_count_-
test:nnTF [2655](#)
 - __cs_split_function_auxi:w [2463](#)
 - __cs_split_function_auxii:w [2463](#)
 - __cs_tmp:w [333](#), [366](#),
[371](#), [372](#), [376](#), [2463](#), [2478](#), [2585](#),
[2601](#), [2603](#), [2604](#), [2605](#), [2606](#), [2607](#),
[2608](#), [2609](#), [2610](#), [2611](#), [2612](#), [2613](#),
[2614](#), [2615](#), [2616](#), [2617](#), [2618](#), [2619](#),
[2620](#), [2621](#), [2622](#), [2623](#), [2624](#), [2625](#),
[2626](#), [2715](#), [2755](#), [2756](#), [2757](#), [2758](#),
[2759](#), [2760](#), [2761](#), [2762](#), [2763](#), [2764](#),
[2765](#), [2766](#), [2767](#), [2768](#), [2769](#), [2770](#),
[2771](#), [2772](#), [2773](#), [2774](#), [2775](#), [2776](#),
[2777](#), [2778](#), [2779](#), [2787](#), [2788](#), [2789](#),
[2790](#), [2791](#), [2792](#), [2793](#), [2794](#), [2795](#),
[2796](#), [2797](#), [2798](#), [2799](#), [2800](#), [2801](#),
[2802](#), [2803](#), [2804](#), [2805](#), [2806](#), [2807](#),
[2808](#), [2809](#), [2810](#), [3558](#), [3576](#), [3718](#),
[3726](#), [3744](#), [3789](#), [3905](#), [3912](#), [3913](#),
[3914](#), [3915](#), [3916](#), [3917](#), [3918](#), [3919](#),
[3920](#), [3921](#), [3922](#), [3923](#), [3924](#), [3925](#),
[3926](#), [3927](#), [3928](#), [3929](#), [3930](#), [3931](#),
[3932](#), [3933](#), [3934](#), [3935](#), [3936](#), [3937](#),
[3938](#), [3939](#), [3940](#), [3941](#), [3942](#), [3943](#),
[3944](#), [3945](#), [3946](#), [3947](#), [3948](#), [3949](#),
[3950](#), [3951](#), [3952](#), [3953](#), [3954](#), [3955](#)
 - __cs_to_str:N [333](#), [2454](#)
 - __cs_to_str:w [333](#), [2454](#)
 - __cs_use_i_delimit_by_s_stop:nw
. [3535](#), [3856](#)
 - __cs_use_none_delimit_by_q_-
recursion_stop:w
. [3535](#), [3582](#), [3589](#), [3869](#)
 - __cs_use_none_delimit_by_s_-
stop:w [3535](#), [3860](#)
 - csc [213](#)
 - cscd [213](#)
 - \csname [14](#), [21](#), [39](#), [43](#), [49](#), [62](#), [84](#),
[86](#), [87](#), [88](#), [99](#), [124](#), [147](#), [151](#), [222](#), [321](#)
 - \csstring [907](#)
 - \currentcjktoken [1211](#), [1268](#)
 - \currentgrouplevel [613](#), [1483](#)
 - \currentgrouptype [614](#), [1484](#)
 - \currentifbranch [615](#), [1485](#)
 - \currentiflevel [616](#), [1486](#)
 - \currentiftype [617](#), [1487](#)
 - \currentspacingmode [1212](#)
 - \currentxspacingmode [1213](#)
- ## D
- \d [29521](#), [31362](#)
 - \day [322](#), [1411](#), [10080](#)
 - dd [216](#)
 - \deadcycles [323](#)
 - debug commands:
 - \debug_off: [314](#)
 - \debug_off:n [24](#), [1183](#),
[1184](#), [1184](#), [1185](#), [1185](#), [1194](#), [2237](#)
 - \debug_on: [314](#)
 - \debug_on:n
. [24](#), [301](#), [1183](#), [1184](#), [1194](#), [2237](#)
 - \debug_resume: [24](#), [1078](#), [2247](#), [27797](#)
 - \debug_suspend: [24](#), [1078](#), [2247](#), [27790](#)
 - debug internal commands:
 - \g__debug_deprecation_off_tl [2249](#)
 - \g__debug_deprecation_on_tl [2249](#)
 - \def [68](#),
[69](#), [70](#), [106](#), [123](#), [125](#), [126](#), [144](#), [145](#),
[148](#), [164](#), [179](#), [207](#), [211](#), [236](#), [275](#), [324](#)
 - default commands:
 - .default:n [186](#), [15702](#)
 - \defaultthyphenchar [325](#)
 - \defaultskewchar [326](#)
 - deg [215](#)
 - \delcode [327](#)
 - \delimiter [328](#)
 - \delimiterfactor [329](#)
 - \delimitershortfall [330](#)
 - deprecation internal commands:
 - __deprecation_date_compare:nNnTF
. [32198](#), [32215](#), [32218](#)
 - __deprecation_date_compare_-
aux:w [32198](#)
 - \l__deprecation_grace_period_-
bool [1183](#), [32195](#), [32214](#), [32224](#), [32298](#)
 - __deprecation_just_error:nNn
. [1184](#), [32236](#)
 - __deprecation_minus_six_-
months:w [32212](#)
 - __deprecation_not_yet_deprecated:nTF
. [1184](#), [32212](#), [32246](#)
 - __deprecation_old:Nnn [32326](#)
 - __deprecation_old_protected:Nnn
. [32326](#)
 - __deprecation_patch_aux:Nn
. [1185](#), [32236](#)
 - __deprecation_patch_aux:nNnNnn
. [32236](#)

```

\__deprecation_primitive:NN ....
    ..... 1188, 32438
\__deprecation_primitive:w ... 32438
\__deprecation_warn_once:nnNnn 32236
\detokenize ..... 62, 222, 618, 1488
\DH ..... 29527, 30958, 31278
\dh ..... 29527, 30958, 31288
dim commands:
\dim_abs:n ..... 169, 679, 14639
\dim_add:Nn ..... 169, 14621
\dim_case:nn ..... 172, 14719
\dim_case:nnn ..... 32344
\dim_case:nnTF .....
    ..... 172, 14719, 14724, 14729, 32345
\dim_compare:nNnTF .....
    ..... 170, 171, 172, 172, 172, 173, 202,
    ..... 14674, 14743, 14779, 14787, 14796,
    ..... 14802, 14814, 14817, 14828, 28147,
    ..... 28150, 28155, 28169, 28172, 28177,
    ..... 28525, 28530, 28540, 28669, 28681,
    ..... 31622, 31639, 31673, 31687, 31697
\dim_compare:nTF .....
    ..... 170, 171, 173, 173, 173,
    ..... 173, 14679, 14751, 14759, 14768, 14774
\dim_compare_p:n ..... 171, 14679
\dim_compare_p:nNn ..... 170, 14674
\dim_const:Nn ..... 168,
    ..... 672, 682, 14588, 14918, 14919, 16322
\dim_do_until:nn ..... 173, 14749
\dim_do_until:nNnn ..... 172, 14777
\dim_do_while:nn ..... 173, 14749
\dim_do_while:nNnn ..... 172, 14777
\dim_eval:n .....
    ..... 170, 171, 174, 174, 672, 1057,
    ..... 14591, 14722, 14727, 14732, 14737,
    ..... 14832, 14860, 14913, 14917, 27857,
    ..... 27927, 28013, 28031, 28068, 28072,
    ..... 28073, 28077, 28081, 28082, 28099,
    ..... 28104, 28110, 28117, 28124, 28267,
    ..... 28291, 28294, 28295, 28302, 28384,
    ..... 28385, 28392, 28393, 28496, 28503,
    ..... 28652, 28653, 28933, 28934, 28935
\dim_gadd:Nn ..... 169, 14621
\dim_gset:N ..... 186, 15710
\dim_gset:Nn ..... 169, 672, 14609
\dim_gset_eq:NN ..... 169, 14615
\dim_gsub:Nn ..... 169, 14621
\dim_gzero:N ..... 168, 14594, 14602
\dim_gzero_new:N ..... 168, 14599
\dim_if_exist:NTF .....
    ..... 168, 14600, 14602, 14605
\dim_if_exist_p:N ..... 168, 14605
\dim_log:N ..... 176, 14914
\dim_log:n ..... 176, 14914
\dim_max:nn .. 169, 14639, 28363, 28367
\dim_min:nn .....
    ..... 169, 14639, 28361, 28365, 28378
\dim_new:N .....
    .. 168, 168, 14580, 14590, 14600,
    ..... 14602, 14920, 14921, 14922, 14923,
    ..... 27361, 27362, 27363, 27364, 27365,
    ..... 27366, 27367, 27368, 27715, 27739,
    ..... 27740, 27743, 27744, 27745, 27746,
    ..... 28235, 28236, 28237, 28238, 28239,
    ..... 28399, 28400, 28741, 28743, 28744
\dim_ratio:nn . 170, 680, 14670, 14907
\dim_set:N ..... 186, 15710
\dim_set:Nn ..... 169, 14609,
    ..... 27388, 27389, 27390, 27422, 27433,
    ..... 27517, 27518, 27519, 27534, 27632,
    ..... 27633, 27634, 27636, 27638, 27640,
    ..... 27844, 27913, 28149, 28153, 28171,
    ..... 28175, 28206, 28220, 28297, 28332,
    ..... 28340, 28351, 28352, 28353, 28354,
    ..... 28360, 28362, 28364, 28366, 28371,
    ..... 28377, 28460, 28462, 28464, 28472,
    ..... 28474, 28528, 28603, 28604, 28606,
    ..... 28608, 28626, 28627, 28742, 28847,
    ..... 28848, 28899, 28900, 28901, 28903
\dim_set_eq:NN .....
    ..... 169, 14615, 27846, 27847, 27915, 27916
\dim_show:N ..... 175, 14910
\dim_show:n ..... 176, 681, 14912
\dim_sign:n ..... 174, 14862
\dim_step_function:nnnN .....
    ..... 173, 678, 14805, 14857
\dim_step_inline:nnnn ... 173, 14835
\dim_step_variable:nnnNn . 174, 14835
\dim_sub:Nn ..... 169, 14621
\dim_to_decimal:n .....
    ..... 174, 14883, 14899, 14904
\dim_to_decimal_in_bp:n .....
    ..... 175, 175, 14898
\dim_to_decimal_in_sp:n .... 175,
    ..... 175, 770, 14900, 17587, 17624, 18221
\dim_to_decimal_in_unit:nn 175, 14902
\dim_to_fp:n . 175, 770, 789, 14910,
    ..... 22415, 27426, 27427, 27437, 27438,
    ..... 27506, 27509, 27510, 27535, 27550,
    ..... 27551, 27570, 27571, 27589, 27606,
    ..... 27609, 27610, 28160, 28161, 28162,
    ..... 28182, 28183, 28184, 28194, 28195,
    ..... 28211, 28212, 28213, 28214, 28224,
    ..... 28225, 28336, 28337, 28344, 28345,
    ..... 28418, 28421, 28422, 28473, 28475
\dim_until_do:nn ..... 173, 14749
\dim_until_do:nNnn ..... 172, 14777

```

- `\dim_use:N` [174](#),
[174](#), [1057](#), [14642](#), [14648](#), [14649](#),
[14650](#), [14656](#), [14657](#), [14658](#), [14682](#),
[14701](#), [14861](#), [14865](#), [14880](#), [14886](#),
[28299](#), [28303](#), [28310](#), [28316](#), [28325](#),
[28326](#), [28327](#), [28481](#), [28488](#), [28634](#)
 - `\dim_while_do:nn` [173](#), [14749](#)
 - `\dim_while_do:nNnn` [173](#), [14777](#)
 - `\dim_zero:N` [168](#), [168](#), [14594](#), [14600](#),
[27391](#), [27520](#), [27635](#), [28140](#), [28141](#)
 - `\dim_zero_new:N` [168](#), [14599](#)
 - `\c_max_dim` [176](#), [179](#), [722](#),
[14918](#), [15015](#), [16351](#), [16394](#), [16402](#),
[28351](#), [28352](#), [28353](#), [28354](#), [28371](#)
 - `\g_tmpa_dim` [176](#), [14920](#)
 - `\l_tmpa_dim` [176](#), [14920](#)
 - `\g_tmpb_dim` [176](#), [14920](#)
 - `\l_tmpb_dim` [176](#), [14920](#)
 - `\c_zero_dim`
[176](#), [14814](#), [14817](#), [14870](#), [14918](#),
[15014](#), [16419](#), [27249](#), [27271](#), [27705](#),
[28147](#), [28150](#), [28155](#), [28169](#), [28172](#),
[28177](#), [28525](#), [28530](#), [28540](#), [31626](#),
[31637](#), [31643](#), [31655](#), [31673](#), [31677](#),
[31685](#), [31687](#), [31691](#), [31697](#), [31707](#)
 - dim internal commands:
 - `__dim_abs:N` [14639](#)
 - `__dim_case:nnTF` [14719](#)
 - `__dim_case:nw` [14719](#)
 - `__dim_case_end:nw` [14719](#)
 - `__dim_compare:w` [14679](#)
 - `__dim_compare:wNN` [674](#), [14679](#)
 - `__dim_compare_!:w` [14679](#)
 - `__dim_compare_<:w` [14679](#)
 - `__dim_compare_=:w` [14679](#)
 - `__dim_compare_>:w` [14679](#)
 - `__dim_compare_end:w` .. [14687](#), [14711](#)
 - `__dim_compare_error:` ... [674](#), [14679](#)
 - `__dim_eval:w` [680](#), [14574](#),
[14610](#), [14612](#), [14622](#), [14626](#), [14631](#),
[14635](#), [14642](#), [14648](#), [14649](#), [14650](#),
[14656](#), [14657](#), [14658](#), [14673](#), [14676](#),
[14682](#), [14701](#), [14706](#), [14808](#), [14809](#),
[14810](#), [14861](#), [14865](#), [14886](#), [14901](#)
 - `__dim_eval_end:` [14574](#),
[14610](#), [14612](#), [14622](#), [14626](#), [14631](#),
[14635](#), [14642](#), [14652](#), [14660](#), [14673](#),
[14676](#), [14861](#), [14865](#), [14886](#), [14901](#)
 - `__dim_maxmin:wwN` [14639](#)
 - `__dim_ratio:n` [14670](#)
 - `__dim_sign:Nw` [14862](#)
 - `__dim_step:NnnnN` [14805](#)
 - `__dim_step:NNnnnn` [14835](#)
 - `__dim_step:wwwN` [14805](#)
 - `__dim_tmp:w` [673](#)
 - `__dim_to_decimal:w` [14883](#)
 - `__dim_use_none_delimit_by_s-`
 stop:w [14579](#), [14697](#)
 - `\dimen` [331](#), [11480](#)
 - `\dimendef` [332](#)
 - `\dimexpr` [619](#), [1489](#)
 - `\directlua` [16](#), [23](#), [53](#), [55](#), [908](#), [1784](#)
 - `\disablecjktoken` [1269](#), [2084](#)
 - `\discretionary` [333](#)
 - `\disinhibitglue` [1214](#)
 - `\displayindent` [334](#)
 - `\displaylimits` [335](#)
 - `\displaystyle` [336](#)
 - `\displaywidowpenalties` [620](#), [1490](#)
 - `\displaywidowpenalty` [337](#)
 - `\displaywidth` [338](#)
 - `\divide` [339](#)
 - `\DJ` [29528](#), [30959](#), [31279](#)
 - `\dj` [29528](#), [30959](#), [31289](#)
 - `\do` [1316](#)
 - `\doublehyphendemerits` [340](#)
 - `\dp` [341](#)
 - `\draftmode` [1012](#), [1674](#)
 - `\dtou` [1215](#), [2046](#)
 - `\dump` [342](#)
 - `\dviextension` [909](#), [1785](#)
 - `\dvifedback` [910](#), [1786](#)
 - `\dvivariable` [911](#), [1787](#)
- E**
- `\edef` [107](#), [132](#), [209](#), [343](#)
 - `\efcode` [789](#), [1658](#)
 - `\elapsedtime` [876](#)
 - `\else` [15](#), [22](#), [44](#), [46](#), [85](#), [89](#),
[92](#), [95](#), [96](#), [100](#), [101](#), [162](#), [166](#), [181](#), [344](#)
 - else commands:
 - `\else:` [23](#),
[100](#), [100](#), [101](#), [105](#), [112](#), [112](#), [163](#),
[182](#), [245](#), [245](#), [245](#), [327](#), [328](#), [334](#),
[366](#), [398](#), [411](#), [412](#), [536](#), [814](#), [2100](#),
[2145](#), [2323](#), [2331](#), [2357](#), [2483](#), [2486](#),
[2495](#), [2501](#), [2511](#), [2514](#), [2523](#), [2529](#),
[2649](#), [2671](#), [2680](#), [2694](#), [2752](#), [2753](#),
[2814](#), [2976](#), [3249](#), [3401](#), [3429](#), [3444](#),
[3452](#), [3489](#), [3559](#), [3610](#), [3611](#), [3613](#),
[3617](#), [3629](#), [3630](#), [3631](#), [3632](#), [3633](#),
[3634](#), [3635](#), [3636](#), [3637](#), [3701](#), [3702](#),
[3704](#), [3753](#), [3783](#), [3870](#), [3982](#), [4020](#),
[4028](#), [4039](#), [4049](#), [4068](#), [4092](#), [4096](#),
[4138](#), [4197](#), [4214](#), [4568](#), [4578](#), [4589](#),
[4604](#), [4612](#), [4627](#), [4673](#), [4688](#), [4984](#),
[5014](#), [5035](#), [5053](#), [5061](#), [5071](#), [5084](#),
[5100](#), [5171](#), [5183](#), [5232](#), [5235](#), [5238](#),

- 5426, 5433, 5439, 5675, 5731, 5734,
5737, 5749, 5764, 5977, 5985, 5993,
6140, 6191, 6192, 6196, 6201, 6242,
6295, 6407, 6421, 6643, 6673, 6676,
6706, 6709, 6726, 6729, 6830, 6835,
6853, 6872, 6875, 6924, 6929, 6932,
7047, 7059, 7068, 7190, 7195, 8275,
8353, 8362, 8709, 8720, 8741, 8757,
8760, 8781, 8821, 8921, 8948, 8986,
8994, 9295, 9328, 9379, 9496, 9521,
9547, 9556, 9616, 9648, 9668, 9690,
9708, 9724, 9734, 9750, 9760, 9852,
9854, 9856, 9858, 10362, 10377,
10399, 10413, 10937, 10940, 10948,
10954, 10995, 11002, 11079, 11090,
11110, 11228, 11231, 11234, 11237,
11240, 11243, 11246, 11315, 11320,
11325, 11330, 11337, 11344, 11349,
11354, 11359, 11364, 11369, 11374,
11379, 11384, 11406, 11412, 11415,
11450, 11453, 11517, 11526, 11534,
11543, 11579, 11618, 11632, 11641,
11651, 11708, 12005, 13150, 14276,
14285, 14296, 14645, 14666, 14677,
14687, 14712, 14872, 14875, 16357,
16361, 16614, 16631, 16632, 16647,
16657, 16752, 16828, 16890, 16893,
16907, 16925, 16929, 17181, 17194,
17214, 17242, 17243, 17265, 17286,
17309, 17310, 17343, 17360, 17378,
17413, 17417, 17453, 17470, 17476,
17480, 17484, 17645, 17678, 17686,
17719, 17723, 17735, 17745, 17755,
17786, 17799, 17834, 17844, 17863,
17876, 17889, 17893, 17904, 17927,
17944, 17956, 17970, 17983, 17986,
17994, 17996, 18006, 18017, 18033,
18049, 18055, 18060, 18067, 18089,
18119, 18142, 18170, 18173, 18349,
18353, 18360, 18379, 18393, 18397,
18404, 18426, 18443, 18449, 18481,
18513, 18529, 18549, 18590, 18605,
18638, 18640, 18646, 18661, 18714,
18867, 18883, 18894, 18932, 18935,
18938, 18941, 18972, 18981, 18990,
18993, 19164, 19177, 19180, 19187,
19205, 19229, 19230, 19245, 19255,
19304, 19307, 19316, 19328, 19339,
19353, 19366, 19406, 19440, 19460,
19497, 19515, 19518, 19524, 19538,
19573, 19591, 19594, 19597, 19600,
19661, 19734, 19804, 19805, 19814,
19849, 19932, 19936, 19940, 20002,
20037, 20052, 20317, 20346, 20350,
20510, 20519, 20573, 20584, 20600,
20608, 20667, 20747, 20758, 20763,
20797, 20810, 20822, 20828, 20949,
20957, 20996, 21003, 21025, 21053,
21068, 21072, 21094, 21125, 21128,
21153, 21156, 21197, 21205, 21216,
21219, 21334, 21349, 21364, 21379,
21394, 21409, 21430, 21475, 21781,
21819, 21820, 21829, 21873, 21928,
21929, 21930, 22034, 22056, 22071,
22089, 22137, 22153, 22359, 22426,
22431, 22595, 22631, 22644, 22674,
22678, 22686, 22713, 22739, 22747,
22764, 22767, 22816, 22820, 22872,
22931, 22943, 22998, 22999, 23461,
23464, 23467, 23477, 23492, 23519,
23534, 23561, 23577, 23610, 23618,
23620, 23622, 23624, 23626, 23628,
23630, 23632, 23650, 23671, 23675,
23747, 23751, 23946, 23947, 23952,
23953, 23968, 23975, 24173, 24183,
24227, 24236, 24248, 24249, 24251,
24253, 24256, 24257, 24260, 24261,
24270, 24272, 24274, 24277, 24278,
24280, 24316, 24319, 24340, 24343,
24351, 24359, 24362, 24371, 24374,
24383, 24391, 24394, 24404, 24510,
24617, 24661, 24665, 24668, 24679,
24684, 24783, 24929, 24942, 25031,
25060, 25099, 25117, 25226, 25260,
25510, 25528, 25547, 25582, 25635,
25682, 25686, 25693, 25714, 25725,
25866, 25982, 26068, 26126, 26200,
26235, 26247, 26273, 26291, 26483,
26627, 26652, 26704, 27124, 27126,
27132, 29296, 29393, 29397, 29408,
29429, 29433, 29442, 29443, 29444,
29445, 29446, 29447, 29448, 29449,
29450, 29461, 29475, 29478, 29481,
29484, 29487, 29490, 29493, 30378,
30382, 30385, 30389, 31595, 31715
\em 31210
em 216
\emergencystretch 345
\emph 29726, 31183
\enablecjktoken 1270, 2085
\end 119, 301, 346, 19061,
23819, 23820, 29539, 29547, 31224
end internal commands:
__regex_end 26471
\endcsname .. 14, 21, 39, 43, 49, 62, 84,
86, 87, 88, 99, 124, 147, 151, 222, 347
\endgroup 13, 36,
38, 42, 48, 68, 118, 136, 155, 204, 348

- \endinput 137, 349
- \endL 621, 1492
- \endlinechar 221, 234, 350
- \endR 622, 1493
- \enquote 19063
- \ensuremath 29541
- \epTeXinputencoding 1216, 2047
- \epTeXversion 1217, 2048
- \eqno 351
- \errhelp 109, 128, 352
- \errmessage 117, 129, 353
- \ERROR 11043
- \errorcontextlines 354
- \errorstopmode 355
- \escapechar 356
- escapehex 29072
- \ETC 23807
- etex commands:
 - \etex_beginL:D 1188, 1479, 32438
 - \etex_beginR:D 1480
 - \etex_botmarks:D 1481
 - \etex_clubpenalties:D 1482
 - \etex_currentgrouplevel:D 1483
 - \etex_currentgrouptype:D 1484
 - \etex_currentifbranch:D 1485
 - \etex_currentiflevel:D 1486
 - \etex_currentiftype:D 1487
 - \etex_detokenize:D 1488
 - \etex_dimexpr:D 1489
 - \etex_displaywidowpenalties:D . 1491
 - \etex_endL:D 1492
 - \etex_endR:D 1493
 - \etex_eTeXrevision:D 1494
 - \etex_eTeXversion:D 1495
 - \etex_everyeof:D 1496
 - \etex_firstmarks:D 1497
 - \etex_fontchardp:D 1498
 - \etex_fontcharht:D 1499
 - \etex_fontcharic:D 1500
 - \etex_fontcharwd:D 1501
 - \etex_glueexpr:D 1502
 - \etex_glueshrink:D 1503
 - \etex_glueshrinkorder:D 1504
 - \etex_gluestretch:D 1505
 - \etex_gluestretchorder:D 1506
 - \etex_gluetomu:D 1507
 - \etex_ifcsname:D 1508
 - \etex_ifdefined:D 1509
 - \etex_iffontchar:D 1510
 - \etex_interactionmode:D 1511
 - \etex_interlinepenalties:D ... 1512
 - \etex_lastlinefit:D 1513
 - \etex_lastnodetype:D 1514
 - \etex_marks:D 1515
 - \etex_middle:D 1516
 - \etex_muexpr:D 1517
 - \etex_mutoglua:D 1518
 - \etex_numexpr:D 1519
 - \etex_pagediscards:D 1520
 - \etex_parshapedimen:D 1521
 - \etex_parshapeindent:D 1522
 - \etex_parshapelength:D 1523
 - \etex_predisplaydirection:D .. 1524
 - \etex_protected:D 1525
 - \etex_readline:D 1526
 - \etex_savinghyphcodes:D 1527
 - \etex_savingvdiscards:D 1528
 - \etex_scantokens:D 1529
 - \etex_showgroups:D 1530
 - \etex_showifs:D 1531
 - \etex_showtokens:D 1532
 - \etex_splitbotmarks:D 1533
 - \etex_splitdiscards:D 1534
 - \etex_splitfirstmarks:D 1535
 - \etex_TeXTeXtstate:D 1536
 - \etex_topmarks:D 1537
 - \etex_tracingassigns:D 1538
 - \etex_tracinggroups:D 1539
 - \etex_tracingifs:D 1540
 - \etex_tracingnesting:D 1541
 - \etex_tracingscantokens:D 1542
 - \etex_unexpanded:D 1543
 - \etex_unless:D 1544
 - \etex_widowpenalties:D 1545
 - \eTeXglueshrinkorder 912
 - \eTeXgluestretchorder 913
 - \eTeXrevision 623, 1494
 - \eTeXversion 624, 1495
 - \etoksapp 914, 1788
 - \etokspre 915, 1789
 - \euc 1218, 2049
 - \everycr 357
 - \everydisplay 358
 - \everyeof 625, 1496
 - \everyhbox 359
 - \everyjob 60, 61, 360
 - \everymath 361
 - \everypar 362
 - \everyvbox 363
 - ex 216
 - \exceptionpenalty 916
 - \exhyphenpenalty 364
 - exp 211
 - exp commands:
 - \exp:w 36, 36, 37, 327, 333, 349, 350, 351, 358, 359, 407, 408, 413, 428, 539, 552, 628, 646, 760, 762, 763, 766, 766, 785,

- 789, 790, 1177, 2122, 2258, 2260,
 2948, 2961, 2967, 3015, 3019, 3023,
 3028, 3034, 3040, 3056, 3068, 3074,
 3080, 3085, 3087, 3094, 3125, 3130,
 3139, 3144, 3153, 3155, 3163, 3170,
 3176, 3184, 3193, 3200, 3214, 3234,
 3238, 3243, 3245, 3282, 3464, 3823,
 4466, 4685, 4694, 4699, 4704, 4709,
 4947, 5106, 5176, 5459, 5464, 5469,
 5474, 5490, 5495, 5500, 5505, 5658,
 5667, 5722, 8954, 8959, 8964, 8969,
 9659, 9805, 10223, 10231, 10291,
 10585, 10593, 10928, 12984, 13568,
 14686, 14721, 14726, 14731, 14736,
 16660, 16775, 16779, 17157, 17283,
 17284, 17285, 17286, 17405, 17423,
 17452, 17496, 17508, 17513, 17521,
 17530, 17552, 17558, 17630, 17643,
 17644, 17653, 17666, 17684, 17685,
 17705, 17718, 17722, 17744, 17772,
 17785, 17798, 17822, 17833, 17843,
 17862, 17875, 17888, 17891, 17903,
 17926, 17955, 17969, 17985, 18005,
 18016, 18022, 18032, 18078, 18085,
 18116, 18131, 18139, 18156, 18172,
 18176, 18185, 18222, 18231, 18240,
 18245, 18247, 18258, 18260, 18275,
 18278, 18285, 18296, 18382, 18430,
 18448, 18451, 18465, 18478, 18528,
 18546, 18617, 18629, 18658, 18660,
 18664, 18666, 18724, 18734, 18744,
 18756, 18874, 18891, 18901, 19056,
 19057, 19058, 19249, 19252, 19260,
 19270, 19278, 20290, 20821, 20843,
 20998, 21175, 21451, 22194, 22209,
 22226, 22263, 22280, 22322, 22341,
 22354, 22386, 22401, 22412, 22534,
 22581, 22621, 22657, 22837, 22937,
 29560, 29599, 29907, 29953, 29967,
 29979, 31784, 31786, 31788, 31790,
 31792, 31794, 31796, 31798, 32024,
 32029, 32034, 32039, 32055, 32073
 \exp_after:wN
 33, 35, 36, 326, 330, 348,
 350, 413, 417, 521, 616, 737, 759,
 760, 762, 763, 827, 828, 889, 890,
 949, 971, 1038, 1129, 1177, 2119,
 2137, 2139, 2144, 2146, 2258, 2260,
 2314, 2338, 2356, 2358, 2377, 2385,
 2393, 2417, 2422, 2429, 2458, 2462,
 2467, 2478, 2494, 2496, 2499, 2522,
 2524, 2527, 2648, 2650, 2659, 2679,
 2681, 2720, 2784, 2880, 2889, 2898,
 2910, 2920, 2926, 2933, 2935, 2947,
 2948, 2960, 2961, 2966, 2967, 2972,
 2977, 2979, 2982, 2991, 2993, 2996,
 2997, 2998, 3001, 3003, 3005, 3009,
 3014, 3019, 3022, 3027, 3032, 3033,
 3034, 3038, 3039, 3040, 3046, 3047,
 3054, 3055, 3056, 3060, 3061, 3062,
 3066, 3067, 3068, 3072, 3073, 3074,
 3078, 3079, 3080, 3084, 3085, 3086,
 3087, 3091, 3092, 3093, 3094, 3098,
 3099, 3100, 3105, 3106, 3107, 3108,
 3112, 3113, 3114, 3115, 3121, 3124,
 3125, 3129, 3130, 3143, 3144, 3151,
 3153, 3155, 3159, 3163, 3165, 3168,
 3169, 3174, 3175, 3179, 3182, 3183,
 3187, 3190, 3191, 3192, 3197, 3198,
 3199, 3207, 3210, 3211, 3212, 3213,
 3218, 3220, 3222, 3223, 3234, 3237,
 3242, 3267, 3268, 3269, 3280, 3281,
 3293, 3294, 3295, 3300, 3308, 3309,
 3310, 3311, 3312, 3313, 3336, 3337,
 3338, 3339, 3399, 3400, 3402, 3424,
 3429, 3430, 3442, 3443, 3445, 3449,
 3450, 3451, 3454, 3456, 3459, 3463,
 3464, 3465, 3470, 3471, 3482, 3488,
 3490, 3494, 3495, 3498, 3499, 3509,
 3556, 3560, 3582, 3589, 3609, 3752,
 3754, 3781, 3782, 3784, 3821, 3823,
 3840, 3858, 3869, 3975, 3981, 3983,
 4007, 4058, 4059, 4138, 4172, 4213,
 4221, 4232, 4390, 4412, 4413, 4414,
 4415, 4474, 4475, 4476, 4537, 4538,
 4539, 4544, 4586, 4597, 4598, 4623,
 4669, 4671, 4789, 4918, 4945, 4976,
 4981, 4982, 4983, 4985, 4999, 5009,
 5026, 5050, 5060, 5063, 5080, 5081,
 5091, 5096, 5097, 5112, 5113, 5114,
 5172, 5174, 5175, 5176, 5181, 5182,
 5184, 5262, 5263, 5520, 5521, 5533,
 5588, 5611, 5645, 5646, 5657, 5658,
 5666, 5674, 5676, 5683, 5688, 5706,
 5707, 5708, 5720, 5721, 5748, 5750,
 5756, 5762, 5776, 5796, 5807, 5823,
 5831, 5839, 5846, 5853, 5865, 5953,
 5967, 5986, 5995, 6016, 6017, 6022,
 6023, 6048, 6049, 6064, 6065, 6113,
 6118, 6183, 6356, 6365, 6411, 6527,
 6563, 6565, 6580, 6586, 6750, 6752,
 6817, 6836, 6837, 6851, 6852, 6879,
 6880, 6995, 7017, 7030, 7031, 7058,
 7153, 7174, 7183, 8171, 8173, 8185,
 8193, 8337, 8371, 8383, 8396, 8397,
 8398, 8420, 8421, 8466, 8501, 8502,
 8503, 8574, 8575, 8601, 8602, 8605,
 8701, 8715, 8720, 8723, 8724, 8731,

8732, 8748, 8749, 8770, 8771, 8780,
8893, 8898, 8903, 8926, 8928, 9056,
9057, 9058, 9083, 9084, 9267, 9295,
9300, 9328, 9341, 9351, 9378, 9380,
9381, 9389, 9406, 9450, 9512, 9519,
9555, 9557, 9564, 9657, 9675, 9680,
9684, 9806, 10000, 10001, 10002,
10067, 10222, 10230, 10291, 10363,
10378, 10400, 10414, 10475, 10483,
10489, 10584, 10592, 10676, 10677,
10680, 10681, 10928, 10929, 10976,
10984, 11055, 11056, 11057, 11148,
11149, 11391, 11410, 11457, 11495,
11524, 11525, 11527, 11533, 11536,
11578, 11581, 11617, 11619, 11629,
11630, 11631, 11633, 11639, 11640,
11642, 11649, 11650, 11652, 11702,
11707, 11709, 11715, 11844, 12025,
12026, 12027, 12256, 12466, 12467,
12985, 12986, 12987, 12988, 13080,
13232, 13250, 13303, 13498, 13501,
13551, 13560, 13563, 13566, 13567,
13569, 13609, 13675, 13706, 13728,
13740, 13746, 13806, 13892, 13893,
13894, 14389, 14402, 14482, 14641,
14645, 14648, 14649, 14656, 14657,
14681, 14686, 14697, 14700, 14807,
14808, 14809, 14864, 14885, 14986,
15355, 15399, 15554, 15555, 15563,
15564, 15565, 15967, 15968, 15969,
16071, 16072, 16092, 16108, 16120,
16121, 16215, 16375, 16376, 16377,
16395, 16403, 16427, 16428, 16472,
16613, 16615, 16616, 16634, 16635,
16636, 16646, 16648, 16656, 16658,
16665, 16666, 16667, 16668, 16669,
16670, 16675, 16676, 16677, 16678,
16679, 16680, 16681, 16724, 16737,
16740, 16751, 16753, 16768, 16772,
16773, 16774, 16777, 16778, 16842,
16844, 16871, 16875, 16900, 16904,
16921, 16928, 16930, 17012, 17020,
17037, 17046, 17092, 17157, 17226,
17227, 17228, 17288, 17298, 17317,
17323, 17342, 17344, 17346, 17357,
17358, 17361, 17372, 17376, 17383,
17384, 17395, 17396, 17405, 17412,
17414, 17415, 17423, 17452, 17470,
17471, 17474, 17475, 17477, 17478,
17482, 17483, 17485, 17486, 17495,
17496, 17501, 17507, 17513, 17521,
17530, 17550, 17551, 17554, 17555,
17557, 17564, 17565, 17567, 17585,
17586, 17614, 17617, 17622, 17623,
17628, 17629, 17631, 17640, 17641,
17642, 17643, 17646, 17647, 17648,
17651, 17666, 17683, 17684, 17694,
17695, 17705, 17717, 17721, 17734,
17736, 17744, 17754, 17756, 17762,
17767, 17769, 17771, 17777, 17778,
17782, 17784, 17796, 17797, 17819,
17821, 17827, 17830, 17832, 17836,
17841, 17846, 17847, 17857, 17858,
17860, 17861, 17864, 17868, 17873,
17887, 17890, 17902, 17911, 17918,
17919, 17920, 17921, 17923, 17925,
17936, 17937, 17938, 17939, 17941,
17943, 17945, 17946, 17947, 17953,
17954, 17964, 17968, 17969, 17971,
17972, 17973, 17978, 17984, 17995,
17997, 18004, 18005, 18007, 18008,
18015, 18021, 18031, 18099, 18112,
18113, 18114, 18115, 18129, 18130,
18132, 18137, 18138, 18153, 18155,
18172, 18176, 18185, 18219, 18220,
18221, 18227, 18228, 18229, 18230,
18236, 18237, 18238, 18239, 18246,
18259, 18267, 18273, 18274, 18276,
18277, 18283, 18284, 18286, 18312,
18325, 18347, 18348, 18350, 18351,
18358, 18359, 18361, 18364, 18376,
18377, 18378, 18380, 18381, 18382,
18391, 18392, 18394, 18395, 18402,
18403, 18405, 18408, 18423, 18424,
18425, 18428, 18429, 18430, 18440,
18441, 18442, 18445, 18446, 18447,
18450, 18454, 18463, 18464, 18475,
18476, 18477, 18480, 18482, 18483,
18484, 18511, 18512, 18514, 18515,
18516, 18526, 18527, 18528, 18530,
18531, 18532, 18544, 18545, 18548,
18550, 18551, 18552, 18572, 18573,
18574, 18575, 18576, 18577, 18578,
18588, 18589, 18591, 18592, 18593,
18599, 18610, 18611, 18612, 18613,
18614, 18615, 18616, 18617, 18622,
18623, 18624, 18625, 18626, 18627,
18628, 18644, 18645, 18647, 18648,
18655, 18656, 18657, 18662, 18663,
18665, 18681, 18696, 18705, 18715,
18721, 18722, 18723, 18728, 18741,
18742, 18743, 18749, 18873, 18890,
18900, 18925, 18926, 18973, 19055,
19163, 19165, 19204, 19206, 19209,
19244, 19246, 19248, 19251, 19258,
19259, 19262, 19263, 19268, 19269,
19276, 19277, 19312, 19313, 19314,
19316, 19327, 19352, 19354, 19360,

19361, 19365, 19368, 19390, 19392,
19405, 19407, 19413, 19415, 19418,
19424, 19426, 19428, 19429, 19430,
19432, 19437, 19439, 19441, 19445,
19448, 19454, 19455, 19459, 19461,
19462, 19463, 19471, 19473, 19474,
19481, 19487, 19494, 19495, 19500,
19501, 19502, 19503, 19522, 19523,
19524, 19530, 19531, 19532, 19537,
19539, 19547, 19549, 19551, 19552,
19554, 19565, 19567, 19569, 19570,
19575, 19626, 19627, 19634, 19635,
19637, 19639, 19641, 19644, 19647,
19649, 19651, 19660, 19662, 19668,
19670, 19672, 19673, 19674, 19680,
19682, 19684, 19685, 19686, 19707,
19708, 19711, 19719, 19721, 19725,
19726, 19727, 19728, 19733, 19735,
19742, 19745, 19748, 19751, 19760,
19763, 19766, 19769, 19776, 19778,
19784, 19792, 19794, 19796, 19813,
19815, 19822, 19824, 19827, 19833,
19835, 19837, 19838, 19839, 19841,
19855, 19856, 19859, 19877, 19879,
19881, 19893, 19896, 19899, 19902,
19905, 19908, 19911, 19914, 19918,
19930, 19934, 19938, 19941, 19956,
19962, 19964, 19966, 19976, 20000,
20003, 20015, 20017, 20021, 20022,
20023, 20025, 20026, 20028, 20035,
20043, 20044, 20050, 20051, 20057,
20060, 20061, 20062, 20063, 20071,
20113, 20118, 20120, 20127, 20130,
20133, 20136, 20139, 20142, 20150,
20151, 20163, 20171, 20173, 20183,
20185, 20192, 20201, 20203, 20206,
20209, 20212, 20215, 20228, 20230,
20238, 20240, 20248, 20250, 20260,
20263, 20266, 20273, 20288, 20289,
20306, 20308, 20309, 20366, 20379,
20381, 20387, 20400, 20402, 20404,
20428, 20442, 20444, 20451, 20453,
20494, 20495, 20496, 20498, 20499,
20500, 20502, 20503, 20509, 20511,
20512, 20518, 20520, 20521, 20522,
20523, 20535, 20541, 20543, 20580,
20587, 20594, 20614, 20615, 20617,
20619, 20621, 20634, 20639, 20640,
20641, 20642, 20643, 20647, 20652,
20654, 20660, 20666, 20668, 20669,
20675, 20676, 20677, 20678, 20679,
20680, 20681, 20682, 20687, 20689,
20691, 20693, 20695, 20700, 20702,
20704, 20706, 20708, 20710, 20728,
20732, 20740, 20741, 20746, 20748,
20757, 20760, 20761, 20762, 20764,
20765, 20766, 20774, 20780, 20792,
20795, 20796, 20798, 20799, 20823,
20824, 20827, 20829, 20845, 20849,
20850, 20851, 20867, 20873, 20939,
20940, 20941, 20948, 20950, 20951,
20956, 20958, 20959, 20968, 20969,
20971, 20974, 20977, 20993, 20997,
20998, 21002, 21004, 21040, 21046,
21047, 21049, 21051, 21052, 21054,
21055, 21065, 21066, 21069, 21070,
21071, 21073, 21074, 21075, 21092,
21093, 21095, 21096, 21102, 21104,
21107, 21110, 21113, 21116, 21124,
21127, 21129, 21132, 21139, 21143,
21151, 21152, 21155, 21157, 21159,
21164, 21165, 21171, 21176, 21177,
21185, 21186, 21187, 21188, 21231,
21253, 21254, 21257, 21258, 21267,
21268, 21269, 21273, 21280, 21281,
21282, 21423, 21424, 21425, 21427,
21445, 21446, 21447, 21448, 21449,
21450, 21457, 21466, 21473, 21474,
21698, 21699, 21705, 21706, 21709,
21714, 21717, 21720, 21723, 21726,
21729, 21732, 21735, 21751, 21752,
21762, 21771, 21779, 21780, 21782,
21783, 21788, 21789, 21798, 21805,
21814, 21815, 21828, 21830, 21858,
21859, 21868, 21871, 21896, 21902,
21903, 21945, 21946, 21948, 21962,
21963, 21971, 21982, 22016, 22019,
22029, 22030, 22033, 22035, 22041,
22055, 22057, 22098, 22101, 22121,
22194, 22204, 22208, 22226, 22229,
22250, 22251, 22258, 22262, 22280,
22283, 22312, 22313, 22319, 22320,
22321, 22328, 22336, 22340, 22354,
22357, 22373, 22374, 22381, 22385,
22396, 22400, 22412, 22417, 22418,
22419, 22425, 22427, 22430, 22432,
22494, 22523, 22533, 22540, 22545,
22546, 22556, 22583, 22594, 22596,
22598, 22600, 22605, 22606, 22608,
22619, 22620, 22640, 22646, 22647,
22649, 22652, 22657, 22663, 22664,
22694, 22696, 22699, 22702, 22704,
22712, 22714, 22718, 22722, 22727,
22732, 22743, 22807, 22808, 22832,
22833, 22834, 22835, 22836, 22844,
22855, 22861, 22887, 22888, 22889,
22896, 22897, 22904, 22905, 22913,
22914, 22918, 22919, 22920, 22925,

- 22930, 22936, 22939, 22940, 22941,
 22942, 22943, 22989, 23087, 23088,
 23130, 23149, 23150, 23165, 23166,
 23167, 23395, 23401, 23403, 23414,
 23474, 23475, 23476, 23477, 23483,
 23484, 23500, 23518, 23520, 23526,
 23527, 23558, 23560, 23562, 23592,
 23607, 23609, 23611, 23636, 23646,
 23654, 23664, 23674, 23676, 23678,
 23713, 23737, 23746, 23749, 23750,
 23752, 23753, 23761, 23762, 23776,
 23832, 23845, 23846, 23851, 23852,
 23855, 23858, 23903, 23910, 23917,
 23923, 23930, 23938, 23974, 23976,
 23985, 24108, 24111, 24152, 24172,
 24174, 24175, 24182, 24185, 24186,
 24210, 24229, 24238, 24350, 24352,
 24358, 24361, 24363, 24370, 24373,
 24375, 24382, 24384, 24390, 24393,
 24396, 24711, 24784, 24796, 24928,
 24931, 24941, 24943, 25126, 25134,
 25209, 25259, 25473, 25755, 25896,
 25919, 25970, 25996, 26060, 26061,
 26069, 26072, 26233, 26234, 26237,
 26238, 26246, 26248, 26249, 26258,
 26272, 26275, 26345, 26594, 26626,
 26628, 29221, 29280, 29282, 29396,
 29398, 29405, 29406, 29409, 29432,
 29434, 29440, 29452, 29460, 29462,
 29558, 29597, 29667, 29668, 29711,
 29712, 29733, 29779, 29829, 29833,
 29862, 29905, 29951, 29965, 29977,
 30670, 30672, 30676, 30718, 30720,
 30734, 30736, 30999, 31042, 31043,
 31101, 31102, 31103, 31110, 31155,
 31269, 31271, 31344, 31346, 31747,
 31748, 31824, 31834, 31839, 31842,
 31911, 31912, 31914, 31915, 31923,
 31924, 32024, 32029, 32034, 32039,
 32053, 32056, 32071, 32073, 32074,
 32081, 32086, 32088, 32091, 32105,
 32125, 32126, 32133, 32134, 32175,
 32189, 32220, 32445, 32446, 32470,
 32471, 32553, 32559, 32560, 32645
 \exp_args:cc 29, 2136, 2990
 \exp_args:Nc
 ... 27, 29, 343, 2136, 2140, 2148,
 2362, 2375, 2383, 2391, 2583, 2602,
 2628, 2633, 2640, 2699, 2711, 2783,
 2816, 2817, 2818, 2819, 2841, 2845,
 2990, 3553, 4506, 4744, 5294, 9532,
 13001, 13218, 16263, 17306, 17546,
 18434, 18458, 18488, 18490, 18492,
 18494, 18496, 18498, 18500, 18502,
 18520, 18536, 18537, 18556, 18558,
 23696, 25081, 28060, 28091, 31593,
 31724, 32009, 32095, 32100, 32108
 \exp_args:Ncc
 . 31, 2630, 2634, 2642, 2824, 2825,
 2826, 2827, 2990, 4147, 4187, 6131
 \exp_args:Nccc 32, 2990
 \exp_args:Ncco 32, 3089
 \exp_args:Nccx 32, 3931
 \exp_args:Ncf 31, 3030
 \exp_args:NcNc 32, 3089
 \exp_args:NcNo 32, 3089
 \exp_args:Ncno 32, 3931
 \exp_args:NcnV 32, 3931
 \exp_args:Ncnx 32, 3931
 \exp_args:Nco 31, 353, 3030
 \exp_args:Ncoo 32, 3931
 \exp_args:NcV 31, 3030
 \exp_args:Ncv 31, 3030
 \exp_args:NcVV 32, 3931
 \exp_args:Ncx 31, 3905, 12993
 \exp_args:Ne 30, 349, 2201,
 2943, 3006, 3231, 11158, 11162,
 12999, 13770, 13772, 13851, 13919,
 13943, 14082, 14100, 14120, 14130,
 14140, 14168, 29739, 29810, 29820,
 29908, 30067, 30309, 30408, 30423,
 30486, 31012, 31261, 31338, 31722
 \exp_args:Nee 31, 3905, 14265
 \exp_args:Neee 32, 3931, 14106
 \exp_args:Nf 30,
 2687, 3018, 3277, 3343, 3378, 3392,
 4455, 5118, 5119, 5135, 5153, 5161,
 5165, 5189, 5195, 5205, 5635, 5637,
 5696, 5698, 5714, 6030, 6035, 6933,
 6934, 7098, 7109, 8469, 8470, 8486,
 8955, 8960, 8965, 8970, 9141, 9210,
 9212, 9230, 9239, 9250, 9259, 9397,
 9414, 9652, 10665, 10716, 10730,
 10751, 10762, 10810, 10880, 10886,
 10892, 10898, 11068, 11188, 11272,
 12284, 13601, 13659, 14722, 14727,
 14732, 14737, 16446, 19116, 22190,
 22756, 25613, 31752, 31754, 32218
 \exp_args:Nff .. 31, 3905, 5159, 16955
 \exp_args:Nffo 32, 3931
 \exp_args:Nfo 31, 3905
 \exp_args:NNc . 31, 322, 2629, 2632,
 2641, 2713, 2820, 2821, 2822, 2823,
 2858, 2861, 2990, 3823, 9098, 9109,
 13080, 13201, 13202, 13303, 14838,
 14845, 19126, 19133, 22784, 31904
 \exp_args:Nnc 31, 3905
 \exp_args:NNcf 32, 3931

- \exp_args:NNe [31](#), [3030](#)
- \exp_args:Nne [31](#), [3905](#)
- \exp_args:NNf [31](#),
[3030](#), [6398](#), [13079](#), [13302](#), [13485](#),
[14831](#), [16521](#), [16526](#), [21417](#), [21418](#)
- \exp_args:Nnf
..... [31](#), [3905](#), [4433](#), [11211](#), [16261](#)
- \exp_args:Nnff [32](#), [3931](#), [11217](#)
- \exp_args:Nnnc [32](#), [3931](#)
- \exp_args:Nnnf [32](#), [3931](#)
- \exp_args:NNNo .. [32](#), [3001](#), [24445](#),
[25333](#), [25390](#), [26504](#), [26588](#), [32713](#)
- \exp_args:NNno [32](#), [3931](#)
- \exp_args:Nnno [32](#), [3931](#)
- \exp_args:NNNV [32](#), [3089](#)
- \exp_args:NNnv [13204](#)
- \exp_args:NNnV [32](#), [3931](#)
- \exp_args:NNNx
..... [32](#), [933](#), [3931](#), [24453](#), [24924](#)
- \exp_args:NNnx [32](#), [3931](#)
- \exp_args:Nnnx [32](#), [3931](#)
- \exp_args:NNo
[25](#), [31](#), [3001](#), [3286](#), [9129](#), [11838](#), [26154](#)
- \exp_args:Nno [31](#), [3905](#), [4193](#),
[4418](#), [4479](#), [10008](#), [10620](#), [13175](#),
[13901](#), [14689](#), [16997](#), [17005](#), [17014](#),
[17031](#), [17039](#), [17067](#), [17573](#), [17577](#)
- \exp_args:NNoo [32](#), [3931](#)
- \exp_args:NNox [32](#), [3931](#)
- \exp_args:Nnox [32](#), [3931](#)
- \exp_args:NNV [31](#), [3030](#)
- \exp_args:NNv [31](#), [3030](#)
- \exp_args:NnV [31](#), [3905](#)
- \exp_args:Nnv [31](#), [3905](#)
- \exp_args:NNVV [32](#), [3931](#)
- \exp_args:NNx [31](#),
[2866](#), [3905](#), [14448](#), [14464](#), [32287](#), [32452](#)
- \exp_args:Nnx [31](#), [3905](#), [13267](#)
- \exp_args:No [27](#), [30](#),
[1177](#), [2850](#), [2855](#), [3001](#), [3286](#), [3290](#),
[3320](#), [3358](#), [3421](#), [3438](#), [3476](#), [3789](#),
[3812](#), [3819](#), [3891](#), [3908](#), [4406](#), [4411](#),
[4633](#), [4634](#), [4635](#), [4662](#), [4663](#), [4664](#),
[4665](#), [4666](#), [4732](#), [4751](#), [4760](#), [4775](#),
[4849](#), [4852](#), [4854](#), [4964](#), [4966](#), [4993](#),
[5002](#), [5137](#), [5144](#), [5146](#), [5203](#), [5212](#),
[5527](#), [5554](#), [5559](#), [5573](#), [5631](#), [5642](#),
[5692](#), [5703](#), [5770](#), [5789](#), [5827](#), [5842](#),
[6259](#), [6312](#), [6595](#), [8163](#), [9129](#), [9216](#),
[9222](#), [9983](#), [9998](#), [10482](#), [10494](#),
[10496](#), [10531](#), [10536](#), [10745](#), [10749](#),
[12460](#), [13234](#), [13367](#), [13397](#), [13493](#),
[13889](#), [13963](#), [14412](#), [14992](#), [15673](#),
[15707](#), [15735](#), [15757](#), [15828](#), [15837](#),
[15843](#), [15878](#), [15885](#), [15940](#), [16152](#),
[23700](#), [23723](#), [23780](#), [23782](#), [24521](#),
[24578](#), [24598](#), [25234](#), [25587](#), [26201](#),
[26244](#), [26649](#), [26679](#), [27156](#), [29427](#),
[31985](#), [32110](#), [32114](#), [32158](#), [32215](#)
- \exp_args:Noc [31](#), [3905](#)
- \exp_args:Nof [31](#), [3905](#), [4448](#)
- \exp_args:Noo . [31](#), [3905](#), [24620](#), [25600](#)
- \exp_args:Noof [32](#), [3931](#)
- \exp_args:Nooo [32](#), [3931](#)
- \exp_args:Noooo [13001](#), [31724](#)
- \exp_args:Noox [32](#), [3931](#)
- \exp_args:Nox [31](#), [3905](#)
- \exp_args:NV [30](#),
[3018](#), [13635](#), [13711](#), [13877](#), [15671](#),
[15705](#), [15733](#), [15755](#), [24012](#), [30001](#)
- \exp_args:Nv .. [30](#), [3018](#), [29850](#), [31136](#)
- \exp_args:NVo [31](#), [3905](#)
- \exp_args:NVV [31](#), [3030](#), [13546](#)
- \exp_args:Nx
.. [31](#), [2657](#), [3117](#), [3832](#), [5251](#), [6148](#),
[9534](#), [9634](#), [11033](#), [12229](#), [13403](#),
[15675](#), [15709](#), [15737](#), [15759](#), [18840](#),
[24753](#), [24754](#), [25137](#), [26007](#), [32607](#)
- \exp_args:Nxo [31](#), [3905](#)
- \exp_args:Nxx [31](#), [3905](#)
- \exp_args_generate:n [261](#), [3889](#), [12996](#)
- \exp_end: [36](#), [36](#), [327](#), [330](#), [333](#), [350](#),
[351](#), [358](#), [358](#), [405](#), [407](#), [408](#), [414](#),
[428](#), [429](#), [540](#), [628](#), [760](#), [789](#), [1176](#),
[1177](#), [2123](#), [2363](#), [2376](#), [2384](#), [2392](#),
[2979](#), [2988](#), [3245](#), [3275](#), [3465](#), [3823](#),
[4482](#), [4724](#), [4925](#), [5112](#), [5113](#), [5184](#),
[5517](#), [5691](#), [8981](#), [9837](#), [9840](#), [9841](#),
[9842](#), [9843](#), [9844](#), [9845](#), [9846](#), [9847](#),
[9848](#), [9850](#), [10218](#), [10959](#), [10973](#),
[10976](#), [10981](#), [10984](#), [10990](#), [10998](#),
[11051](#), [11056](#), [12988](#), [14748](#), [17288](#),
[18252](#), [20845](#), [22583](#), [22585](#), [22657](#),
[29579](#), [29928](#), [31817](#), [32015](#), [32044](#)
- \exp_end_continue_f:nw [37](#), [3245](#)
- \exp_end_continue_f:w
..... [36](#), [37](#), [349](#), [762](#),
[763](#), [2948](#), [3019](#), [3056](#), [3080](#), [3144](#),
[3163](#), [3176](#), [3200](#), [3214](#), [3234](#), [3245](#),
[4685](#), [9659](#), [10291](#), [12913](#), [13568](#),
[14686](#), [16660](#), [16775](#), [16779](#), [17405](#),
[17423](#), [17444](#), [17508](#), [17513](#), [17521](#),
[17530](#), [17552](#), [17630](#), [17666](#), [17674](#),
[17705](#), [18078](#), [18085](#), [18131](#), [18178](#),
[18185](#), [18222](#), [18266](#), [18272](#), [18275](#),
[18285](#), [18296](#), [18465](#), [18658](#), [18660](#),
[18664](#), [18666](#), [18724](#), [18734](#), [18744](#),
[18756](#), [18874](#), [18891](#), [18901](#), [19056](#),

- 19057, 19058, 19249, 19260, 19270,
 19278, 20290, 20998, 21175, 21451,
 22194, 22209, 22226, 22263, 22280,
 22322, 22341, 22354, 22386, 22401,
 22412, 22534, 22621, 22837, 22937
 \exp_last_two_unbraced:Nnn
 33, 3217, 28134, 28660, 28664
 \exp_last_unbraced:Nco 33, 3151, 10603
 \exp_last_unbraced:NcV 33, 3151
 \exp_last_unbraced:Ne 33, 3151, 22465
 \exp_last_unbraced:Nf 33,
 3151, 4076, 4097, 4204, 4226, 6479,
 6764, 6951, 7123, 9228, 9248, 16462,
 16950, 18865, 19342, 24163, 32459
 \exp_last_unbraced:Nfo 33, 3151, 22787
 \exp_last_unbraced:NNf 33, 3151
 \exp_last_unbraced:NNNf 33, 3151, 9597
 \exp_last_unbraced:NNNNf
 33, 3151, 9602
 \exp_last_unbraced:NNNNo 33,
 3151, 3569, 3573, 3736, 5885, 6596,
 15410, 16728, 16746, 29468, 32439
 \exp_last_unbraced:NNNo 33, 3151
 \exp_last_unbraced:NnNo 33, 3151
 \exp_last_unbraced:NNNV 33, 3151
 \exp_last_unbraced:NNo
 33, 3151, 4932, 10570,
 13400, 13819, 28631, 29605, 31030
 \exp_last_unbraced:Nno
 33, 3151, 8546, 12056
 \exp_last_unbraced:NNV 33, 3151
 \exp_last_unbraced:No
 . 33, 3151, 28793, 28798, 28876, 28882
 \exp_last_unbraced:Noo
 33, 3151, 11896, 11990
 \exp_last_unbraced:NV 33, 3151
 \exp_last_unbraced:Nv 33, 3151, 11059
 \exp_last_unbraced:Nx
 33, 3151, 6338, 6342, 6384
 \exp_not:N 34, 34, 88,
 162, 216, 350, 357, 362, 411, 412,
 584, 591, 767, 949, 958, 1031, 1035,
 1188, 1191, 2119, 2318, 2404, 2407,
 2719, 2720, 2783, 2784, 2926, 2972,
 3118, 3222, 3222, 3300, 3304, 3346,
 3399, 3419, 3429, 3442, 3546, 3548,
 3549, 3556, 3557, 3558, 3559, 3560,
 3561, 3567, 3593, 3602, 3657, 3658,
 3718, 3724, 3726, 3732, 3793, 3810,
 3812, 3840, 4530, 5006, 5009, 5023,
 5026, 5059, 5066, 5322, 5323, 5545,
 5546, 8162, 8164, 8562, 9114, 9377,
 10545, 10655, 10658, 10666, 10667,
 10916, 11003, 11007, 11036, 11226,
 11229, 11232, 11235, 11238, 11241,
 11244, 11310, 11314, 11319, 11324,
 11329, 11336, 11343, 11348, 11353,
 11358, 11363, 11368, 11378, 11383,
 11388, 11391, 11392, 11395, 11405,
 11410, 11425, 11443, 11448, 11449,
 11450, 11451, 11452, 11453, 11455,
 11457, 11458, 11459, 11463, 11464,
 11467, 11468, 11489, 11492, 11493,
 11495, 11496, 11500, 11503, 11504,
 11506, 11509, 11591, 11597, 11628,
 11631, 11638, 11639, 11648, 11649,
 11663, 11664, 11679, 11684, 11689,
 11698, 11699, 11945, 11968, 12335,
 12337, 12339, 12341, 12346, 12347,
 12352, 12354, 12356, 12629, 12631,
 12633, 12635, 12640, 12641, 12646,
 12648, 12650, 13110, 13111, 13115,
 13815, 13823, 13886, 13889, 13890,
 13892, 13893, 13894, 13895, 13898,
 13899, 13970, 13972, 14354, 14357,
 14358, 14359, 14361, 14362, 14365,
 14366, 14850, 14890, 15418, 15420,
 15434, 15436, 15490, 15491, 15503,
 15569, 15570, 15638, 15639, 15810,
 15811, 15812, 15813, 15814, 15817,
 15819, 15821, 15822, 15861, 15862,
 15863, 15864, 15867, 15869, 15871,
 15872, 15903, 15904, 15905, 15906,
 15909, 15911, 15913, 15914, 15922,
 15923, 15924, 15925, 15926, 15929,
 15931, 15933, 15934, 16724, 16725,
 17469, 17470, 17567, 17568, 17569,
 17570, 17676, 17716, 17720, 17742,
 17835, 17867, 17952, 17966, 17983,
 17993, 18003, 18040, 18043, 18149,
 18150, 18152, 18153, 18154, 18155,
 18156, 18157, 18160, 18162, 18164,
 18343, 18345, 18387, 18389, 18510,
 18525, 19138, 19295, 21304, 21305,
 21306, 21310, 21311, 21312, 23462,
 23465, 23617, 23618, 23619, 23620,
 23621, 23622, 23623, 23624, 23625,
 23626, 23627, 23628, 23629, 23630,
 23631, 23632, 23635, 23636, 23637,
 24139, 24141, 24143, 24145, 24147,
 24149, 24509, 24511, 24704, 24706,
 24717, 24721, 24888, 25342, 26001,
 26215, 26337, 26350, 26713, 29221,
 29225, 29229, 29230, 29235, 29390,
 29391, 29394, 29405, 29473, 29476,
 29479, 29482, 29485, 29488, 29491,
 29612, 29613, 29614, 29616, 29618,
 29622, 29626, 29627, 29800, 29801,

- 29804, 29805, 29820, 29987, 30051,
 30125, 30130, 30131, 30175, 30180,
 30182, 30183, 30184, 30186, 30187,
 30189, 30284, 30286, 30289, 30634,
 30640, 30642, 30643, 30647, 30648,
 30650, 30652, 30671, 30673, 30677,
 30719, 30721, 30735, 30737, 31270,
 31272, 31345, 31347, 31757, 31759,
 31763, 31765, 31770, 31772, 31876,
 31886, 32171, 32172, 32265, 32273,
 32289, 32292, 32293, 32306, 32309,
 32447, 32472, 32492, 32553, 32560
- `\exp_not:n`
 . 16, 29, 30, 34, 34, 34, 34, 34, 35,
 35, 35, 53, 54, 54, 56, 56, 57, 77,
 78, 82, 83, 88, 124, 125, 126, 126,
 145, 162, 195, 265, 268, 314, 389,
 396, 406, 415, 493, 497, 553, 554,
 557, 560, 600, 692, 944, 949, 954,
 958, 966, 971, 1031, 1036, 1036,
 1040, 1129, 1131, 1154, 1177, 1178,
 1179, 1184, 2119, 2319, 2325, 2327,
 2333, 2334, 2409, 2659, 2872, 2873,
 2926, 2939, 2955, 3135, 3148, 3222,
 3303, 3345, 3662, 3677, 3692, 3767,
 3814, 3837, 4250, 4269, 4295, 4297,
 4314, 4316, 4320, 4322, 4332, 4334,
 4336, 4338, 4340, 4342, 4344, 4346,
 4356, 4358, 4360, 4362, 4364, 4366,
 4368, 4370, 4527, 4531, 4532, 4533,
 4844, 4846, 5134, 5251, 5360, 5424,
 5566, 8184, 8185, 8192, 8193, 8209,
 8241, 8261, 8264, 8267, 8376, 8408,
 8432, 8485, 8563, 8617, 8627, 9115,
 10258, 10300, 10301, 10315, 10317,
 10387, 10482, 10490, 10510, 10546,
 10659, 10665, 10693, 10698, 10729,
 10760, 11037, 11153, 11462, 11570,
 11592, 11598, 11798, 11833, 11903,
 11946, 11949, 11950, 11969, 11973,
 12329, 12346, 12492, 12623, 12640,
 13361, 13378, 14851, 15222, 15228,
 15234, 15493, 15503, 15518, 15572,
 15640, 15815, 15823, 15851, 15864,
 15865, 15873, 15893, 15906, 15907,
 15915, 15927, 15935, 16131, 16133,
 16141, 16143, 16169, 16171, 17562,
 18801, 18803, 18805, 19139, 19296,
 22476, 23240, 23490, 23604, 23634,
 24509, 24511, 25140, 25399, 25520,
 25739, 25832, 25990, 26002, 26057,
 26272, 26275, 26283, 26337, 26345,
 26362, 26377, 26418, 26601, 26606,
 27982, 29004, 29007, 29009, 29409,
 29432, 29741, 29742, 29743, 29839,
 29860, 30069, 30070, 31069, 31073,
 31307, 31311, 31312, 31833, 32015,
 32016, 32024, 32029, 32034, 32039,
 32053, 32071, 32084, 32091, 32272
- `\exp_stop_f:` 35, 36,
 100, 349, 409, 493, 506, 646, 729,
 741, 807, 808, 896, 924, 944, 949,
 2945, 3406, 3409, 3424, 3432, 3487,
 5171, 5180, 5229, 5230, 5236, 5425,
 5432, 5439, 5673, 5689, 5728, 5729,
 5735, 5747, 5763, 5764, 5975, 5983,
 6190, 6191, 6192, 6197, 6198, 6240,
 6374, 6409, 6410, 6608, 6670, 6674,
 6704, 6707, 6723, 6727, 6748, 6826,
 6828, 6848, 6849, 6866, 6868, 6922,
 6925, 6926, 7045, 7050, 7186, 7191,
 8196, 8703, 8717, 8727, 8735, 8920,
 8925, 9079, 10104, 10806, 10808,
 10876, 10878, 10882, 10884, 10888,
 10890, 10894, 10896, 10934, 10935,
 10942, 10943, 10944, 10945, 10950,
 10951, 10970, 10985, 10993, 11059,
 11073, 11074, 11080, 11698, 11699,
 11700, 11701, 13080, 13303, 13556,
 13570, 13582, 14294, 14695, 14866,
 16354, 16358, 16530, 16534, 16563,
 16768, 16883, 16898, 16923, 17157,
 17161, 17165, 17167, 17171, 17175,
 17183, 17188, 17201, 17208, 17221,
 17232, 17233, 17244, 17245, 17254,
 17257, 17268, 17310, 17374, 17379,
 17451, 17481, 17639, 17682, 17733,
 17753, 17780, 17794, 17829, 17856,
 17865, 17884, 17900, 17916, 17934,
 17994, 18013, 18029, 18044, 18058,
 18267, 18346, 18357, 18390, 18401,
 18639, 18643, 18939, 18945, 18947,
 18962, 18971, 18979, 18987, 18988,
 19185, 19305, 19311, 19326, 19363,
 19436, 19458, 19512, 19513, 19521,
 19858, 19876, 19929, 19933, 19937,
 19955, 19990, 19991, 19992, 19993,
 19994, 20020, 20032, 20048, 20065,
 20343, 20344, 20441, 20534, 20569,
 20582, 20587, 20596, 20598, 20725,
 20754, 20759, 20789, 20826, 20866,
 20942, 20992, 21038, 21039, 21044,
 21050, 21068, 21091, 21123, 21126,
 21173, 21193, 21199, 21214, 21226,
 21264, 21285, 21325, 21340, 21355,
 21370, 21385, 21400, 21428, 21472,
 21738, 21748, 21778, 21930, 21932,
 21969, 21981, 22013, 22054, 22063,

- 22078, 22097, 22130, 22143, 22227,
 22281, 22329, 22332, 22355, 22564,
 22568, 22575, 22576, 22631, 22632,
 22633, 22642, 22652, 22670, 22739,
 22742, 22745, 22760, 22813, 22817,
 22859, 22931, 22938, 22988, 23259,
 23428, 23437, 23438, 23472, 23542,
 23550, 23573, 23575, 23576, 23580,
 23597, 23648, 23651, 23667, 23673,
 23745, 23748, 23945, 23946, 23947,
 23953, 23973, 24225, 24245, 24246,
 24250, 24254, 24255, 24258, 24259,
 24267, 24268, 24271, 24275, 24276,
 24279, 24338, 24433, 24677, 24682,
 24696, 24697, 24710, 24781, 24782,
 24821, 24921, 25098, 25257, 25525,
 25543, 25569, 25579, 25631, 25644,
 25655, 25671, 25722, 25939, 26067,
 26071, 26135, 26198, 26211, 26231,
 26236, 26242, 26288, 26341, 26358,
 26381, 26599, 26604, 26625, 26703,
 26715, 26720, 28269, 29459, 30376,
 30379, 30380, 30383, 32124, 32132,
 32171, 32172, 32173, 32174, 32562
- exp internal commands:
- __exp_arg_last_unbraced:nnn . . . 3119
 - __exp_arg_next:Nnn 2926, 2933
 - __exp_arg_next:nnn 350, 2926, 2935, 2943, 2947, 2960, 2966
 - __exp_e:N 3261, 3291
 - __exp_e:nn 352, 358, 3015, 3139, 3257, 3277, 3282, 3290, 3318, 3320, 3365, 3366, 3371, 3438, 3456
 - __exp_e:Nnn 360, 3291
 - __exp_e_end:nn 358, 3257, 3390
 - __exp_e_expandable:Nnn . . . 360, 3291
 - __exp_e_group:n 3264, 3278
 - __exp_e_if_toks_register:N . . . 3502
 - __exp_e_if_toks_register:NTF 3453, 3502
 - __exp_e_noexpand:Nnn 3311, 3346, 3368
 - __exp_e_primitive:Nnn . . . 3313, 3321
 - __exp_e_primitive_aux:NNnn . . . 3321
 - __exp_e_primitive_aux:NNw . . . 3321
 - __exp_e_primitive_other:NNnn . . 3321
 - __exp_e_primitive_other_aux:nNNnn 3321
 - __exp_e_protected:Nnn 360, 3291
 - __exp_e_put:nn 359, 361, 363, 3278, 3371, 3383, 3470
 - __exp_e_put:nnn 364, 3278, 3476
 - __exp_e_space:nn 3268, 3276
 - __exp_e_the:N 3434
 - __exp_e_the:Nnn 3312, 3347, 3434
 - __exp_e_the_errhelp: 3502
 - __exp_e_the_everycr: 3502
 - __exp_e_the_everydisplay: . . . 3502
 - __exp_e_the_everyeof: 3502
 - __exp_e_the_everyhbox: 3502
 - __exp_e_the_everyjob: 3502
 - __exp_e_the_everymath: 3502
 - __exp_e_the_everypar: 3502
 - __exp_e_the_everyvbox: 3502
 - __exp_e_the_output: 3502
 - __exp_e_the_pdfpageattr: 3502
 - __exp_e_the_pdfpageresources: 3502
 - __exp_e_the_pdfpagesattr: . . . 3502
 - __exp_e_the_pdfpkmode: 3502
 - __exp_e_the_toks:N 364, 3474
 - __exp_e_the_toks:n 364, 3450, 3474
 - __exp_e_the_toks:wnn 364, 3449, 3474
 - __exp_e_the_toks_reg:N 3434
 - __exp_e_the_XeTeXinterchartoks: 3502
 - __exp_e_unexpanded:N 3373
 - __exp_e_unexpanded:nN 362, 3373
 - __exp_e_unexpanded:nn 3373
 - __exp_e_unexpanded:Nnn 3310, 3345, 3373
 - __exp_eval_error_msg:w 2970
 - __exp_eval_register:N 2961, 2967, 2970, 3023, 3028, 3034, 3040, 3068, 3074, 3086, 3087, 3094, 3125, 3130, 3153, 3155, 3170, 3184, 3193, 3238, 3243
 - \l__exp_internal_tl 324, 2191, 2195, 2196, 2926, 2926, 2954, 2956, 3148, 3149
 - __exp_last_two_unbraced:nnN . 3217
 - \expandafter 13, 14, 21, 38, 39, 42, 43, 48, 49, 60, 61, 84, 86, 87, 88, 99, 124, 147, 155, 170, 186, 365
 - \expanded 324, 918, 1792
 - \expandglyphsinfont 1013, 1675
 - \ExplFileDate 7, 14476, 14491, 14505, 14509
 - \ExplFileDescription 7, 14475, 14488
 - \ExplFileExtension 14478, 14493, 14502
 - \ExplFileName 7, 14477, 14492, 14501
 - \ExplFileVersion 7, 14479, 14494, 14503
 - \explicitdiscretionary 919, 1793
 - \explicithyphenpenalty 917, 1790
 - \ExplLoaderFileDate 32215, 32221
 - \ExplSyntaxOff 4, 7, 7, 118, 207, 240, 254, 276, 277, 314
 - \ExplSyntaxOn 4, 7, 7, 118, 236, 276, 277, 314, 391, 571

F

- `fact` 211
- `false` 216
- `\fam` 366
- `\fi` 17, 35, 41, 51, 64,
65, 66, 91, 94, 96, 97, 98, 101, 102,
131, 140, 153, 154, 171, 187, 205, 367
- fi commands:
 - `\fi:` 23, 100, 100,
101, 105, 112, 112, 163, 182, 245,
245, 245, 327, 328, 330, 333, 334,
359, 391, 396, 398, 429, 430, 433,
512, 521, 541, 575, 655, 741, 766,
782, 813, 949, 2100, 2147, 2315,
2323, 2331, 2339, 2359, 2364, 2377,
2385, 2393, 2395, 2418, 2423, 2430,
2457, 2462, 2488, 2489, 2497, 2503,
2516, 2517, 2525, 2531, 2651, 2672,
2682, 2696, 2753, 2814, 2911, 2921,
2975, 2978, 2985, 2986, 3252, 3259,
3269, 3282, 3295, 3300, 3303, 3304,
3305, 3306, 3314, 3323, 3339, 3403,
3431, 3437, 3446, 3451, 3457, 3460,
3464, 3472, 3482, 3491, 3495, 3499,
3567, 3583, 3590, 3599, 3613, 3614,
3619, 3620, 3621, 3639, 3640, 3641,
3642, 3643, 3644, 3645, 3646, 3647,
3655, 3674, 3676, 3706, 3707, 3708,
3755, 3785, 3857, 3868, 3878, 3976,
3984, 4008, 4022, 4030, 4041, 4051,
4071, 4101, 4102, 4174, 4197, 4216,
4219, 4400, 4407, 4543, 4544, 4570,
4580, 4591, 4606, 4614, 4629, 4641,
4645, 4675, 4690, 4919, 4972, 4977,
4986, 4988, 5016, 5037, 5055, 5064,
5073, 5079, 5086, 5091, 5102, 5106,
5114, 5173, 5185, 5234, 5240, 5241,
5426, 5433, 5439, 5534, 5602, 5606,
5607, 5625, 5678, 5691, 5733, 5739,
5740, 5751, 5764, 5765, 5786, 5824,
5850, 5954, 5960, 5968, 5979, 5996,
5998, 6142, 6194, 6195, 6200, 6203,
6204, 6244, 6297, 6376, 6377, 6412,
6413, 6415, 6423, 6610, 6643, 6679,
6680, 6711, 6712, 6732, 6733, 6751,
6834, 6838, 6848, 6858, 6874, 6878,
6881, 6886, 6888, 6931, 6935, 6936,
7027, 7032, 7043, 7049, 7061, 7064,
7066, 7070, 7184, 7198, 7199, 8237,
8240, 8277, 8338, 8355, 8365, 8419,
8424, 8710, 8711, 8720, 8743, 8760,
8761, 8763, 8780, 8781, 8824, 8878,
8886, 8913, 8921, 8927, 8950, 8988,
8996, 9081, 9296, 9329, 9377, 9382,
9498, 9523, 9549, 9558, 9618, 9650,
9668, 9690, 9710, 9726, 9736, 9752,
9762, 9852, 9854, 9856, 9858, 9860,
9862, 9996, 10004, 10364, 10379,
10402, 10416, 10939, 10942, 10943,
10944, 10945, 10950, 10951, 10956,
10957, 10958, 10997, 11007, 11054,
11062, 11064, 11108, 11109, 11112,
11248, 11249, 11250, 11251, 11252,
11253, 11254, 11315, 11320, 11325,
11330, 11337, 11344, 11349, 11354,
11359, 11364, 11369, 11374, 11379,
11384, 11406, 11417, 11418, 11467,
11468, 11519, 11528, 11537, 11545,
11582, 11620, 11634, 11643, 11653,
11698, 11699, 11700, 11710, 11717,
11719, 12007, 13152, 13233, 13251,
13508, 13549, 13558, 13579, 13589,
13593, 13600, 13608, 13886, 13899,
14278, 14287, 14298, 14645, 14668,
14677, 14694, 14698, 14712, 14715,
14877, 14878, 16363, 16364, 16396,
16404, 16470, 16617, 16633, 16637,
16649, 16659, 16754, 16807, 16810,
16811, 16816, 16830, 16868, 16869,
16870, 16871, 16872, 16873, 16874,
16875, 16876, 16877, 16878, 16879,
16892, 16894, 16905, 16908, 16922,
16927, 16931, 17072, 17163, 17164,
17173, 17174, 17185, 17186, 17187,
17198, 17199, 17200, 17207, 17218,
17219, 17220, 17230, 17231, 17235,
17236, 17244, 17247, 17248, 17256,
17267, 17287, 17310, 17345, 17362,
17381, 17382, 17391, 17397, 17417,
17418, 17446, 17455, 17472, 17479,
17487, 17488, 17591, 17592, 17593,
17596, 17599, 17638, 17654, 17680,
17681, 17688, 17696, 17725, 17726,
17729, 17731, 17732, 17737, 17747,
17750, 17752, 17757, 17788, 17801,
17806, 17812, 17815, 17816, 17850,
17851, 17878, 17879, 17892, 17895,
17906, 17929, 17948, 17958, 17974,
17983, 17988, 17994, 17998, 18003,
18009, 18024, 18035, 18054, 18064,
18066, 18072, 18093, 18121, 18144,
18177, 18179, 18302, 18352, 18356,
18366, 18367, 18383, 18396, 18400,
18410, 18411, 18431, 18452, 18455,
18485, 18517, 18533, 18553, 18594,
18606, 18619, 18621, 18641, 18642,
18649, 18667, 18706, 18716, 18869,
18885, 18896, 18925, 18926, 18927,

- 18934, 18936, 18937, 18943, 18944,
 18947, 18974, 18982, 18983, 18991,
 18992, 18994, 18995, 19166, 19179,
 19189, 19190, 19195, 19196, 19197,
 19198, 19199, 19200, 19207, 19217,
 19224, 19235, 19236, 19247, 19264,
 19309, 19310, 19317, 19330, 19345,
 19355, 19369, 19399, 19408, 19442,
 19464, 19482, 19499, 19516, 19517,
 19519, 19520, 19525, 19540, 19573,
 19602, 19603, 19604, 19605, 19606,
 19619, 19663, 19736, 19803, 19805,
 19806, 19816, 19845, 19848, 19849,
 19860, 19880, 19943, 19944, 19945,
 19957, 19996, 19997, 19998, 19999,
 20005, 20008, 20010, 20020, 20038,
 20053, 20065, 20072, 20319, 20323,
 20325, 20329, 20336, 20337, 20347,
 20348, 20351, 20443, 20513, 20524,
 20536, 20568, 20575, 20586, 20602,
 20609, 20670, 20727, 20737, 20739,
 20749, 20767, 20768, 20800, 20803,
 20812, 20814, 20816, 20830, 20844,
 20868, 20952, 20960, 20991, 20999,
 21005, 21016, 21019, 21022, 21031,
 21041, 21043, 21049, 21056, 21059,
 21068, 21076, 21097, 21130, 21131,
 21158, 21160, 21178, 21179, 21198,
 21209, 21218, 21221, 21232, 21235,
 21238, 21256, 21266, 21277, 21279,
 21288, 21335, 21350, 21365, 21380,
 21395, 21410, 21413, 21415, 21432,
 21477, 21784, 21820, 21821, 21831,
 21872, 21873, 21897, 21924, 21925,
 21928, 21930, 21931, 21936, 21948,
 21967, 21972, 21980, 21983, 22015,
 22025, 22026, 22036, 22058, 22073,
 22091, 22099, 22102, 22130, 22138,
 22154, 22226, 22244, 22280, 22298,
 22331, 22354, 22360, 22433, 22434,
 22565, 22566, 22575, 22582, 22587,
 22597, 22607, 22632, 22635, 22648,
 22680, 22688, 22689, 22717, 22739,
 22740, 22741, 22744, 22749, 22769,
 22770, 22822, 22823, 22864, 22872,
 22925, 22931, 22944, 22990, 23002,
 23003, 23058, 23089, 23131, 23142,
 23151, 23160, 23215, 23225, 23235,
 23349, 23351, 23405, 23409, 23413,
 23440, 23451, 23469, 23470, 23471,
 23478, 23494, 23500, 23503, 23511,
 23521, 23536, 23544, 23552, 23563,
 23579, 23599, 23612, 23634, 23652,
 23660, 23662, 23665, 23672, 23677,
 23754, 23755, 23904, 23911, 23912,
 23918, 23921, 23924, 23931, 23932,
 23935, 23939, 23940, 23950, 23951,
 23956, 23957, 23969, 23977, 23986,
 23987, 24015, 24176, 24187, 24239,
 24241, 24248, 24251, 24252, 24256,
 24260, 24261, 24262, 24263, 24272,
 24273, 24277, 24280, 24281, 24282,
 24318, 24321, 24342, 24345, 24353,
 24364, 24365, 24376, 24377, 24385,
 24397, 24398, 24408, 24409, 24422,
 24441, 24442, 24450, 24451, 24502,
 24512, 24538, 24552, 24556, 24619,
 24667, 24670, 24671, 24686, 24689,
 24712, 24779, 24780, 24785, 24812,
 24813, 24824, 24828, 24862, 24867,
 24875, 24910, 24917, 24922, 24932,
 24944, 24970, 25033, 25062, 25101,
 25108, 25119, 25193, 25210, 25214,
 25228, 25262, 25474, 25513, 25529,
 25553, 25574, 25583, 25640, 25647,
 25667, 25685, 25696, 25698, 25728,
 25731, 25756, 25868, 25897, 25920,
 25921, 25942, 25971, 25997, 26070,
 26128, 26140, 26203, 26217, 26218,
 26239, 26250, 26276, 26293, 26343,
 26345, 26360, 26362, 26383, 26485,
 26544, 26561, 26562, 26601, 26602,
 26606, 26607, 26629, 26634, 26671,
 26709, 26717, 26718, 26722, 26723,
 27124, 27126, 27132, 29272, 29273,
 29281, 29295, 29299, 29300, 29316,
 29395, 29399, 29410, 29431, 29435,
 29451, 29463, 29495, 29496, 29497,
 29498, 29499, 29500, 29501, 29653,
 29659, 30387, 30388, 30391, 30392,
 31597, 31717, 32043, 32050, 32055,
 32081, 32087, 32091, 32106, 32127,
 32135, 32171, 32172, 32173, 32179
- file commands:
- \file_add_path:nN 32346
 - \file_compare_timestamp:nNn ... 166
 - \file_compare_timestamp:nNnTF ...
 166, 14262
 - \file_compare_timestamp_p:nNn ...
 166, 14262
 - \g_file_curr_dir_str
 163, 13714, 14373, 14379, 14396
 - \g_file_curr_ext_str
 163, 13714, 14375, 14381, 14398
 - \g_file_curr_name_str
 163, 10135, 12143, 13714,
 13749, 14374, 14380, 14397, 32359
 - \g_file_current_name_tl 32358

```

\file_full_name:n .....
    ..... 164, 13917, 14014, 14083,
    14100, 14107, 14168, 14266, 14267
\file_get:nnN .....
    . 164, 13868, 32693, 32695, 32697,
    32701, 32706, 32710, 32717, 32721
\file_get:nnNTF ... 164, 13868, 13870
\file_get_full_name:nN .....
    ..... 164, 315, 14005, 32347
\file_get_full_name:nNTF ... 164,
    13070, 13875, 14005, 14007, 14019,
    14020, 14324, 14330, 14335, 14347
\file_get_hex_dump:nN ... 165, 14182
\file_get_hex_dump:nnnN .. 165, 14228
\file_get_hex_dump:nnnNTF .....
    ..... 165, 14228, 14230
\file_get_hex_dump:nNTF .....
    ..... 165, 14182, 14183
\file_get_md5hash:nN .....
    ..... 165, 14184, 14192
\file_get_md5hash:nN\file_-
    get_size:nN ..... 14182
\file_get_md5hash:nN\file_-
    get_size:nNTF ..... 14182
\file_get_md5hash:nNTF 165, 14185
\file_get_size:nN ..... 166
\file_get_size:nNTF ..... 166, 14187
\file_get_timestamp:nN ... 166, 14182
\file_get_timestamp:nNTF .....
    ..... 166, 14182, 14189
\file_hex_dump:n .... 165, 165, 14104
\file_hex_dump:nnn .....
    ..... 165, 165, 14104, 14237
\file_if_exist:nTF .....
    . 164, 164, 164, 166, 6161, 14322,
    14554, 14556, 14560, 32349, 32351
\file_if_exist_input:n ... 167, 14328
\file_if_exist_input:nTF .....
    ..... 167, 14328, 32348, 32350
\file_input:n ..... 166, 167, 167,
    167, 6165, 14345, 32349, 32351, 32496
\file_input_stop: ..... 167, 14339
\file_list: ..... 32352
\file_log_list: ... 167, 14440, 32353
\file_md5hash:n . 165, 165, 14074
\file_parse_full_name:nnnn .....
    ..... 165, 14048, 14377, 14400
\file_path_include:n .... 167, 32354
\file_path_remove:n ..... 32356
\l_file_search_path_seq .....
    ..... 164, 164, 165, 165, 166,
    166, 13757, 13928, 14031, 32355, 32357
\file_show_list: ..... 167, 14440
\file_size:n ..... 166, 166, 14074

\file_timestamp:n ... 166, 166, 14074
file internal commands:
\l__file_base_name_tl .....
    ..... 13752, 14028, 14066
\__file_compare_timestamp:nnN . 14262
\__file_const:nn ..... 14568
\__file_details:nn ..... 14074
\__file_details_aux:nn . 14074, 14121
\l__file_dir_str .....
    ..... 13754, 14049, 14378, 14379
\__file_ext_check:n .....
    ..... 13939, 13950, 13957
\__file_ext_check:nn .. 13972, 13977
\__file_ext_check:nnw . 13963, 13968
\__file_ext_check:nw .....
    ..... 13958, 13959, 13966
\l__file_ext_str .....
    .. 13754, 14049, 14050, 14378, 14381
\__file_full_name:n ..... 13917
\__file_full_name_aux:n ..... 13917
\__file_full_name_aux:nn ..... 13917
\l__file_full_name_tl .....
    ..... 13752, 13875, 13878,
    14040, 14042, 14048, 14053, 14055,
    14058, 14065, 14067, 14324, 14330,
    14331, 14335, 14336, 14347, 14348
\__file_get_aux:nnN ..... 13868
\__file_get_details:nnN ..... 14182
\__file_get_do:Nw ..... 13868
\__file_get_full_name_search:nN .
    ..... 14005
\__file_hex_dump:n ..... 14104
\__file_hex_dump_auxi:nnn .... 14104
\__file_hex_dump_auxii:nnnn .. 14104
\__file_hex_dump_auxiii:nnnn .. 14104
\__file_hex_dump_auxiiv:nnn .. 14104
\__file_hex_dump_auxiv:nnn .....
    ..... 14138, 14140, 14145, 14154
\__file_id_info_auxi:w ..... 14473
\__file_id_info_auxii:w .. 669, 14473
\__file_id_info_auxiii:w ..... 14473
\__file_if_recursion_tail_-
    break:NN ..... 13766
\__file_if_recursion_tail_stop:N
    ..... 13766, 13792
\__file_if_recursion_tail_stop_-
    do:Nn ..... 13766
\__file_if_recursion_tail_stop_-
    do:nn ..... 13767, 13832
\__file_input:n . 14331, 14336, 14345
\__file_input_pop: ..... 14345
\__file_input_pop:nnn ..... 14345
\__file_input_push:n ..... 14345

```

- \g__file_internal_ior [14044](#), [14052](#),
[14054](#), [14057](#), [14067](#), [14068](#), [14070](#)
- \l__file_internal_tl
..... [13713](#), [14388](#), [14389](#)
- __file_list:N [14440](#)
- __file_list_aux:n [14440](#)
- \c__file_marker_tl
..... [655](#), [13867](#), [13890](#), [13903](#)
- __file_md5five_hash:n [14074](#)
- __file_name_cleanup:w [13917](#)
- __file_name_end: [13917](#)
- __file_name_ext_check:n [13917](#)
- __file_name_ext_check:nn [13917](#)
- __file_name_ext_check:nnw ... [13917](#)
- __file_name_ext_check:nw [13917](#)
- \l__file_name_str
..... [13754](#), [14049](#), [14378](#), [14380](#)
- __file_parse_full_name_auxi:w [14400](#)
- __file_parse_full_name_split:nNNNTF
..... [14400](#)
- __file_quark_if_nil:nTF
.. [13763](#), [13849](#), [13863](#), [13961](#), [13970](#)
- __file_quark_if_nil_p:n [13763](#)
- \g__file_record_seq
..... [665](#), [667](#), [668](#), [13744](#),
[14354](#), [14359](#), [14452](#), [14467](#), [14468](#)
- __file_size:n
.. [13908](#), [13926](#), [13946](#), [13979](#), [13983](#)
- \g__file_stack_seq
..... [665](#), [13717](#), [14371](#), [14388](#)
- __file_str_cmp:nn [14242](#), [14291](#)
- __file_str_escape:n [14242](#)
- __file_timestamp:n [14262](#)
- __file_tmp:w [13720](#), [13724](#), [13728](#),
[13734](#), [13740](#), [14421](#), [14436](#), [14438](#)
- \l__file_tmp_seq
..... [13758](#), [14444](#), [14448](#),
[14452](#), [14453](#), [14455](#), [14464](#), [14469](#)
- \filedump [877](#)
- \filemoddate [878](#)
- \filesize [879](#)
- \finalhyphendemerits [368](#)
- \firstmark [369](#)
- \firstmarks [626](#), [1497](#)
- \firstvalidlanguage [920](#), [1795](#)
- flag commands:
 - \flag_clear:n
..... [102](#), [102](#), [6257](#), [6285](#), [6346](#),
[6388](#), [6474](#), [6522](#), [6523](#), [6575](#), [6576](#),
[6810](#), [6811](#), [6812](#), [6813](#), [6814](#), [6915](#),
[7010](#), [7011](#), [7012](#), [7013](#), [7168](#), [7169](#),
[7170](#), [9514](#), [9527](#), [25131](#), [26567](#), [26568](#)
 - \flag_clear_new:n
.. [102](#), [459](#), [6757](#), [6758](#), [6759](#), [6760](#),
[6938](#), [6939](#), [6940](#), [7118](#), [7119](#), [9526](#)
 - \flag_height:n .. [103](#), [6085](#), [9535](#),
[9551](#), [9565](#), [26577](#), [26578](#), [26584](#), [26585](#)
 - \flag_if_exist:n [103](#)
 - \flag_if_exist:nTF .. [103](#), [9527](#), [9538](#)
 - \flag_if_exist_p:n [103](#), [9538](#)
 - \flag_if_raised:n [103](#)
 - \flag_if_raised:nTF [103](#), [6078](#), [6083](#),
[6085](#), [6784](#), [6790](#), [6795](#), [6802](#), [6972](#),
[6977](#), [6982](#), [7133](#), [7140](#), [9543](#), [25139](#)
 - \flag_if_raised_p:n [103](#), [9543](#)
 - \flag_log:n [102](#), [9528](#)
 - \flag_new:n [102](#), [102](#), [459](#), [528](#), [5949](#),
[5950](#), [9509](#), [9527](#), [16968](#), [16969](#),
[16970](#), [16971](#), [25121](#), [26471](#), [26472](#)
 - \flag_raise:n [103](#), [6243](#),
[6293](#), [6406](#), [6420](#), [6494](#), [6507](#), [6545](#),
[6550](#), [6631](#), [6831](#), [6832](#), [6855](#), [6856](#),
[6869](#), [6870](#), [6889](#), [6890](#), [6896](#), [6897](#),
[6927](#), [7077](#), [7078](#), [7187](#), [7188](#), [7192](#),
[7193](#), [7207](#), [7208](#), [9562](#), [26600](#), [26605](#)
 - \flag_raise_if_clear:n
.. [262](#), [17002](#), [17011](#), [17019](#), [17036](#),
[17045](#), [17076](#), [25158](#), [25180](#), [31712](#)
 - \flag_show:n [102](#), [9528](#)
- flag fp commands:
 - flag_fp_division_by_zero . [207](#), [16968](#)
 - flag_fp_invalid_operation [207](#), [16968](#)
 - flag_fp_overflow [207](#), [16968](#)
 - flag_fp_underflow [207](#), [16968](#)
- flag internal commands:
 - __flag_clear:wn [9514](#)
 - __flag_height_end:wn [9551](#)
 - __flag_height_loop:wn [9551](#)
 - __flag_show:Nn [9528](#)
- \floatingpenalty [370](#)
- \floor [212](#)
- \fmtname [146](#)
- \font [371](#)
- \fontchardp [627](#), [1498](#)
- \fontcharht [628](#), [1499](#)
- \fontcharic [629](#), [1500](#)
- \fontcharwd [630](#), [1501](#)
- \fontdimen [372](#)
- \fontencoding [31172](#)
- \fontfamily [31173](#)
- \fontid [921](#), [1796](#)
- \fontname [373](#)
- \fontseries [31174](#)
- \fontshape [31175](#)
- \fontsize [31178](#)
- \footnotesize [31214](#)

- \forcecjktoken 1271, 2086
- \formatname 922, 1797
- fp commands:
 - \c_e_fp 206, 208, 18846
 - \fp_abs:n 211, 216, 919, 22455, 27535, 27637, 27639, 27641, 28463, 28465
 - \fp_add:Nn 200, 919, 919, 18823
 - \fp_compare:nNnTF
 - 202, 203, 203, 203, 204, 204,
 - 18887, 19028, 19034, 19039, 19047,
 - 19108, 19114, 27392, 27394, 27399,
 - 27668, 27683, 27692, 28203, 28437
 - \fp_compare:nTF
 - 202, 203, 204, 204, 204, 204,
 - 210, 18871, 19000, 19006, 19011, 19019
 - \fp_compare_p:n 203, 18871
 - \fp_compare_p:nNn 202, 18887
 - \fp_const:Nn
 - 199, 18800, 18846, 18847, 18848, 18849
 - \fp_do_until:nn 204, 18997
 - \fp_do_until:nNnn 203, 19025
 - \fp_do_while:nn 204, 18997
 - \fp_do_while:nNnn 203, 19025
 - \fp_eval:n
 - 200, 201, 203, 210, 210, 210,
 - 210, 210, 211, 211, 211, 211, 211,
 - 211, 211, 212, 212, 212, 212, 213,
 - 213, 213, 213, 214, 214, 214, 215,
 - 215, 216, 216, 803, 22450, 31934, 31953
 - \fp_format:nn 217
 - \fp_gadd:Nn 200, 18823
 - .fp_gset:N 186, 15718
 - \fp_gset:Nn .. 200, 18800, 18824, 18826
 - \fp_gset_eq:NN 200, 18809, 18814
 - \fp_gsub:Nn 200, 18823
 - \fp_gzero:N 199, 18813, 18820
 - \fp_gzero_new:N 200, 18817
 - \fp_if_exist:NnTF
 - 202, 18818, 18820, 18861
 - \fp_if_exist_p:N 202, 18861
 - \fp_if_nan:n 261
 - \fp_if_nan:nTF 217, 261, 18863
 - \fp_if_nan_p:n 261, 18863
 - \fp_log:N 207, 18833
 - \fp_log:n 207, 18842
 - \fp_max:nn 216, 22457
 - \fp_min:nn 216, 22457
 - \fp_new:N
 - .. 199, 200, 18797, 18818, 18820,
 - 18850, 18851, 18852, 18853, 27358,
 - 27359, 27360, 27486, 27487, 27736,
 - 27737, 28230, 28231, 28397, 28398
 - .fp_set:N 186, 15718
 - \fp_set:Nn 200, 18800, 18823, 18825, 27380, 27381, 27382, 27505, 27507, 27548, 27568, 27588, 27605, 27607, 27625, 27626, 27666, 27667, 28248, 28249, 28417, 28419, 28457, 28458
 - \fp_set_eq:NN .. 200, 18809, 18813, 27553, 27573, 27590, 27669, 27670
 - \fp_show:N 207, 18833
 - \fp_show:n 207, 18842
 - \fp_sign:n 201, 22453
 - \fp_step_function:nnnN
 - 205, 19053, 19145
 - \fp_step_inline:nnnn 205, 19123
 - \fp_step_variable:nnnNn .. 205, 19123
 - \fp_sub:Nn 200, 18823
 - \fp_to_decimal:N
 - 201, 202, 16961, 22257, 22288, 22450
 - \fp_to_decimal:n
 - .. 200, 201, 201, 202, 202, 22257,
 - 22452, 22454, 22456, 22458, 22460
 - \fp_to_dim:N 201, 917, 22380
 - \fp_to_dim:n 201, 206, 22380, 27424, 27435, 27535, 28158, 28180, 28208, 28222, 28334, 28342, 28473, 28475
 - \fp_to_int:N 201, 22396
 - \fp_to_int:n 201, 22396
 - \fp_to_scientific:N
 - 201, 22203, 22234, 22241
 - \fp_to_scientific:n . 201, 202, 22203
 - \fp_to_tl:N
 - 202, 219, 16962, 18840, 22336
 - \fp_to_tl:n 202, 16574, 17001, 17010, 17035, 17044, 17073, 18679, 18694, 18843, 18845, 19080, 19081, 19100, 19111, 22336
 - \fp_trap:nn 207, 207, 746, 16972, 17087, 17088, 17089, 17090
 - \fp_until_do:nn 204, 18997
 - \fp_until_do:nNnn 204, 19025
 - \fp_use:N 202, 219, 22450
 - \fp_while_do:nn 204, 18997
 - \fp_while_do:nNnn 204, 19025
 - \fp_zero:N 199, 200, 18813, 18818
 - \fp_zero_new:N 200, 18817
 - \c_inf_fp 206, 215, 16588, 18187, 19616, 19698, 20036, 20796, 20819, 21021, 21024, 21028, 21052, 21254, 21417, 22942
 - \c_nan_fp 215, 749, 772, 16588, 17012, 17020, 17092, 17298, 17317, 17323, 17346, 17513, 17521, 17530, 17609, 17666, 17705, 18099, 18176, 18188, 18681, 18696, 19104, 20995, 22494, 22540, 22855, 22914, 22940

- \c_one_fp [205](#), [800](#),
[903](#), [18191](#), [18624](#), [18645](#), [18846](#),
[19204](#), [20057](#), [20790](#), [20990](#), [21042](#),
[21227](#), [21341](#), [21371](#), [21920](#), [22556](#)
- \c_pi_fp .. [206](#), [215](#), [782](#), [18189](#), [18848](#)
- \g_tmpa_fp [206](#), [18850](#)
- \l_tmpa_fp [206](#), [18850](#)
- \g_tmpb_fp [206](#), [18850](#)
- \l_tmpb_fp [206](#), [18850](#)
- \c_zero_fp [205](#), [803](#), [818](#), [930](#), [16588](#),
[16642](#), [18192](#), [18636](#), [18648](#), [18798](#),
[18813](#), [18814](#), [19206](#), [19209](#), [19445](#),
[19612](#), [20799](#), [20820](#), [21018](#), [21055](#),
[22135](#), [22241](#), [22425](#), [22939](#), [27392](#),
[27394](#), [27399](#), [27683](#), [27692](#), [28437](#)
- fp internal commands:
- __fp_&o:ww [805](#), [814](#), [19210](#)
- __fp_&tuple_o:ww [19210](#)
- __fp_*o:ww [19577](#)
- __fp_*tuple_o:ww [20083](#)
- __fp_+o:ww [816](#), [817](#), [845](#), [19298](#)
- __fp_-o:ww [816](#), [817](#), [19293](#)
- __fp_/o:ww [825](#), [867](#), [19689](#)
- __fp^o:ww [20986](#)
- __fp_acos_o:w [908](#), [910](#), [22076](#)
- __fp_acot_o:Nw . [21316](#), [21318](#), [21908](#)
- __fp_acotii_o:Nww [21918](#), [21921](#)
- __fp_acotii_o:ww [903](#)
- __fp_acsc_normal_o:NnwNnw
..... [910](#), [22134](#), [22149](#), [22157](#)
- __fp_acsc_o:w [22128](#)
- __fp_add:NNNn [18823](#)
- __fp_add_big_i:wNww [819](#)
- __fp_add_big_i_o:wNww
..... [816](#), [819](#), [19365](#), [19372](#)
- __fp_add_big_ii:wNww [819](#)
- __fp_add_big_ii_o:wNww [19368](#), [19372](#)
- __fp_add_inf_o:Nww ... [19314](#), [19334](#)
- __fp_add_normal_o:Nww
..... [818](#), [19313](#), [19349](#)
- __fp_add_npos_o:NnwNnw
..... [819](#), [19352](#), [19358](#)
- __fp_add_return_ii_o:Nww
..... [19316](#), [19322](#), [19327](#)
- __fp_add_significand_carry_-
o:wwwNN [820](#), [19405](#), [19420](#)
- __fp_add_significand_no_carry_-
o:wwwNN [820](#), [19407](#), [19410](#)
- __fp_add_significand_o:NnnwnnnnN
..... [819](#), [820](#), [19375](#), [19383](#), [19388](#)
- __fp_add_significand_pack:NNNNNNN
..... [19388](#)
- __fp_add_significand_test_o:N [19388](#)
- __fp_add_zeros_o:Nww . [19312](#), [19324](#)
- __fp_and_return:wNw [19210](#)
- __fp_array_bounds:NNnTF
..... [22811](#), [22842](#), [22912](#)
- __fp_array_bounds_error:NNn . [22811](#)
- __fp_array_count:n [16691](#),
[17282](#), [18954](#), [18955](#), [20096](#), [22176](#)
- __fp_array_gset:NNNNww [22830](#)
- __fp_array_gset:w [22830](#)
- __fp_array_gset_normal:w [22830](#)
- __fp_array_gset_recover:Nw .. [22830](#)
- __fp_array_gset_special:nnNNN ..
..... [22830](#), [22887](#)
- __fp_array_gzero:N [929](#)
- __fp_array_if_all_fp:nTF
..... [16703](#), [18674](#)
- __fp_array_if_all_fp_loop:w . [16703](#)
- \g__fp_array_int
..... [22776](#), [22783](#), [22785](#), [22797](#)
- __fp_array_item:N [22894](#)
- __fp_array_item:NNNnN [22894](#)
- __fp_array_item:NwN [22894](#)
- __fp_array_item:w [22894](#)
- __fp_array_item_normal:w [22894](#)
- __fp_array_item_special:w ... [22894](#)
- \l__fp_array_loop_int
..... [22777](#), [22883](#), [22886](#), [22889](#)
- __fp_array_new:nNNN [22778](#)
- __fp_array_new:nNNNN . [22787](#), [22791](#)
- __fp_array_to_clist:n
..... [17350](#), [22461](#), [22580](#)
- __fp_array_to_clist_loop:Nw . [22461](#)
- __fp_asec_o:w [22141](#)
- __fp_asin_auxi_o:NnNww
.. [908](#), [909](#), [910](#), [22106](#), [22109](#), [22168](#)
- __fp_asin_isqrt:wn [22109](#)
- __fp_asin_normal_o:NnwNnnnw ...
..... [22067](#), [22083](#), [22094](#)
- __fp_asin_o:w [22061](#)
- __fp_atan_auxi:ww . [905](#), [21986](#), [22000](#)
- __fp_atan_auxii:w [22000](#)
- __fp_atan_combine_aux:ww [22027](#)
- __fp_atan_combine_o:NwwwwwN ...
..... [904](#), [905](#), [21945](#), [21962](#), [22027](#)
- __fp_atan_default:w [800](#), [903](#), [21908](#)
- __fp_atan_div:wnwnw
..... [905](#), [21973](#), [21975](#)
- __fp_atan_inf_o:NNNw [903](#), [21933](#),
[21934](#), [21935](#), [21943](#), [22079](#), [22152](#)
- __fp_atan_near:wwn [21975](#)
- __fp_atan_near_aux:wn [21975](#)
- __fp_atan_normal_o:NnwNnw
..... [903](#), [21937](#), [21953](#)
- __fp_atan_o:Nw . [21320](#), [21322](#), [21908](#)
- __fp_atan_Taylor_break:w [22011](#)


```

\__fp_atan_Taylor_loop:www .....
..... 906, 22006, 22011
\__fp_atan_test_o:NwwNwwN .....
..... 909, 21956, 21960, 22116
\__fp_atanii_o:Nww ..... 21912, 21921
\__fp_basics_pack_high:NNNNw ...
.. 820, 837, 16801, 19413, 19565,
19668, 19680, 19822, 20015, 20541
\__fp_basics_pack_high_carry:w ..
..... 738, 16801
\__fp_basics_pack_low:NNNNw ...
..... 827, 837,
16801, 19415, 19567, 19670, 19682,
19824, 19964, 19966, 20017, 20543
\__fp_basics_pack_weird_high:NNNNNNw
..... 218, 16812, 19424, 19833
\__fp_basics_pack_weird_low:NNNNw
..... 218, 16812, 19426, 19835
\c__fp_big_leading_shift_int ...
.. 16787, 19894, 20229, 20239, 20249
\c__fp_big_middle_shift_int ....
.... 16787, 19897, 19900, 19903,
19906, 19909, 19912, 19916, 20231,
20241, 20251, 20261, 20264, 20267
\c__fp_big_trailing_shift_int ...
..... 16787, 19920, 20274
\c__fp_Bigg_leading_shift_int ...
..... 16792, 19743, 19761
\c__fp_Bigg_middle_shift_int ...
.. 16792, 19746, 19749, 19764, 19767
\c__fp_Bigg_trailing_shift_int ..
..... 16792, 19752, 19770
\__fp_binary_rev_type_o:Nww ....
..... 18310, 20086, 20088
\__fp_binary_type_o:Nww .....
..... 18310, 20084, 20097
\c__fp_block_int ..... 16593, 20493
\__fp_case_return:nw .....
. 741, 16869, 16899, 16902, 16907,
17411, 20755, 21251, 21933, 21934,
21935, 22228, 22282, 22356, 22358,
22359, 22425, 22860, 22862, 22863
\__fp_case_return_i_o:ww . 16876,
19315, 19329, 19338, 19610, 21924
\__fp_case_return_ii_o:ww .....
.. 16876, 19611, 21040, 21058, 21925
\__fp_case_return_o:Nw . 741, 742,
16870, 20036, 20790, 20795, 20798,
20990, 20995, 21018, 21021, 21024,
21227, 21341, 21371, 22135, 22137
\__fp_case_return_o:Nww .....
..... 16874, 19612, 19613,
19616, 19617, 21042, 21051, 21054
\__fp_case_return_same_o:w . 741,
742, 16872, 19845, 19849, 20037,
20049, 20052, 20574, 20802, 21015,
21231, 21234, 21326, 21334, 21349,
21364, 21379, 21386, 21394, 21409,
22064, 22072, 22090, 22136, 22153
\__fp_case_use:nw ..... 741,
16868, 19340, 19608, 19609, 19614,
19615, 19697, 19700, 19847, 20033,
20567, 20570, 21026, 21237, 21327,
21332, 21342, 21347, 21357, 21362,
21372, 21377, 21387, 21392, 21402,
21407, 22066, 22069, 22079, 22081,
22087, 22131, 22133, 22144, 22147,
22152, 22231, 22238, 22285, 22292
\__fp_change_func_type:NNN .....
.... 16731, 18103, 20079, 22213,
22267, 22344, 22390, 22405, 22844
\__fp_change_func_type_aux:w . 16731
\__fp_change_func_type_chk:NNN 16731
\__fp_chk:w ..... 728,
730, 782, 817, 818, 819, 821, 827,
829, 16575, 16588, 16589, 16590,
16591, 16592, 16602, 16607, 16609,
16610, 16638, 16641, 16643, 16653,
16666, 16685, 16880, 16896, 17068,
17073, 17300, 17354, 17363, 17365,
18201, 18921, 18922, 19084, 19100,
19104, 19168, 19169, 19172, 19183,
19184, 19192, 19193, 19201, 19213,
19216, 19220, 19223, 19299, 19319,
19320, 19322, 19323, 19324, 19332,
19335, 19346, 19347, 19349, 19358,
19434, 19586, 19620, 19621, 19624,
19705, 19843, 19851, 19853, 20030,
20039, 20041, 20046, 20054, 20056,
20058, 20062, 20564, 20576, 20578,
20787, 20804, 20806, 20987, 21006,
21008, 21009, 21012, 21029, 21032,
21035, 21060, 21061, 21063, 21079,
21168, 21181, 21183, 21187, 21191,
21224, 21240, 21323, 21336, 21338,
21351, 21353, 21366, 21368, 21381,
21383, 21396, 21398, 21411, 21421,
21922, 21938, 21939, 21943, 21954,
22061, 22074, 22076, 22092, 22095,
22105, 22128, 22139, 22141, 22155,
22157, 22162, 22224, 22245, 22248,
22278, 22299, 22302, 22352, 22368,
22371, 22446, 22447, 22557, 22559,
22591, 22857, 22865, 22868, 22947
\__fp_compare:wNNNNw ..... 18564
\__fp_compare_aux:wn ..... 18887
\__fp_compare_back:ww .....

```


- [924](#), [18903](#), [19182](#), [22575](#)
- _fp_compare_back_any:ww .. [806](#),
[806](#), [807](#), [18639](#), [18900](#), [18903](#), [18971](#)
- _fp_compare_back_tuple:ww .. [18948](#)
- _fp_compare_nan:w [806](#), [18903](#)
- _fp_compare_npos:nwnw [805](#),
[806](#), [808](#), [18931](#), [18977](#), [19436](#), [20343](#)
- _fp_compare_return:w [18871](#)
- _fp_compare_significand:nnnnnnnn
..... [18977](#)
- _fp_cos_o:w [21338](#)
- _fp_cot_o:w [888](#), [21398](#)
- _fp_cot_zero_o:Nnw
..... [887](#), [889](#), [21356](#), [21398](#)
- _fp_csc_o:w [21353](#)
- _fp_decimate:nNnnnn
..... [739](#), [743](#), [883](#), [16822](#),
[16887](#), [16914](#), [17367](#), [19374](#), [19382](#),
[19461](#), [20833](#), [20837](#), [21206](#), [22308](#)
- _fp_decimate_:Nnnnn [16834](#)
- _fp_decimate_auxi:Nnnnn [740](#), [16838](#)
- _fp_decimate_auxii:Nnnnn .. [16838](#)
- _fp_decimate_auxiii:Nnnnn .. [16838](#)
- _fp_decimate_auxiv:Nnnnn .. [16838](#)
- _fp_decimate_auxix:Nnnnn .. [16838](#)
- _fp_decimate_auxv:Nnnnn [16838](#)
- _fp_decimate_auxvi:Nnnnn .. [16838](#)
- _fp_decimate_auxvii:Nnnnn .. [16838](#)
- _fp_decimate_auxviii:Nnnnn .. [16838](#)
- _fp_decimate_auxx:Nnnnn [16838](#)
- _fp_decimate_auxxi:Nnnnn .. [16838](#)
- _fp_decimate_auxxii:Nnnnn .. [16838](#)
- _fp_decimate_auxxiii:Nnnnn .. [16838](#)
- _fp_decimate_auxxiv:Nnnnn .. [16838](#)
- _fp_decimate_auxxv:Nnnnn .. [16838](#)
- _fp_decimate_auxxvi:Nnnnn .. [16838](#)
- _fp_decimate_pack:nnnnnnnnnw .
..... [740](#), [16845](#), [16864](#)
- _fp_decimate_pack:nnnnnw
..... [16865](#), [16866](#)
- _fp_decimate_tiny:Nnnnn [16834](#)
- _fp_div_npos_o:Nww
..... [829](#), [829](#), [19694](#), [19704](#)
- _fp_div_significand_calc:wwnnnnnn
..... [832](#),
[833](#), [19721](#), [19730](#), [19778](#), [20647](#), [20654](#)
- _fp_div_significand_calc_-
i:wwnnnnnn [19730](#)
- _fp_div_significand_calc_-
ii:wwnnnnnn [19730](#)
- _fp_div_significand_i_o:wnnw ..
..... [829](#), [832](#), [19711](#), [19717](#)
- _fp_div_significand_ii:wnw ...
..... [834](#), [19725](#), [19726](#), [19727](#), [19774](#)
- _fp_div_significand_iii:wwnnnn
..... [835](#), [19728](#), [19781](#)
- _fp_div_significand_iv:wwnnnnnn
..... [835](#), [19784](#), [19789](#)
- _fp_div_significand_large_-
o:wwnnnnnw [837](#), [19815](#), [19829](#)
- _fp_div_significand_pack:NNN ..
..... [836](#),
[869](#), [19776](#), [19809](#), [20634](#), [20652](#), [20660](#)
- _fp_div_significand_small_-
o:wwnnnnnw [837](#), [19813](#), [19819](#)
- _fp_div_significand_test_o:w ..
..... [836](#), [836](#), [19719](#), [19810](#)
- _fp_div_significand_v:NN
..... [19794](#), [19796](#), [19799](#)
- _fp_div_significand_v:NNw .. [19789](#)
- _fp_div_significand_vi:Nw
..... [835](#), [19789](#)
- _fp_division_by_zero_o:Nnw ...
..... [746](#), [17032](#),
[17080](#), [20034](#), [20571](#), [21417](#), [21418](#)
- _fp_division_by_zero_o:NNww ...
[746](#), [17040](#), [17080](#), [19698](#), [19701](#), [21028](#)
- _c_fp_empty_tuple_fp
..... [16686](#), [17507](#), [18162](#), [18172](#)
- _fp_ep_compare:www .. [20338](#), [21969](#)
- _fp_ep_compare_aux:www [20338](#)
- _fp_ep_div:www
..... [901](#), [20368](#), [20479](#),
[21898](#), [21985](#), [21989](#), [21998](#), [22165](#)
- _fp_ep_div_eps_pack:NNNNw .. [20398](#)
- _fp_ep_div_epsilon:wnNNNN [859](#)
- _fp_ep_div_epsilon:wnNNNNnn
..... [20395](#), [20398](#)
- _fp_ep_div_epsilonii:wnNNNNnn .. [20398](#)
- _fp_ep_div_esti:www
..... [858](#), [20374](#), [20377](#)
- _fp_ep_div_estii:wwnnwn ... [20377](#)
- _fp_ep_div_estiii:NNNNwww [20377](#)
- _fp_ep_inv_to_float_o:wN [889](#)
..... [899](#), [20475](#), [20483](#), [21360](#), [21375](#)
- _fp_ep_isqrt:wnw [20421](#), [22126](#)
- _fp_ep_isqrt_aux:wn [20421](#)
- _fp_ep_isqrt_auxi:wnw [20424](#), [20426](#)
- _fp_ep_isqrt_auxii:wwnnwn .. [20421](#)
- _fp_ep_isqrt_epsilon:wN
..... [861](#), [20458](#), [20461](#)
- _fp_ep_isqrt_epsilonii:wnw [20461](#)
- _fp_ep_isqrt_esti:wwnnwn
..... [20436](#), [20439](#)
- _fp_ep_isqrt_estii:wwnnwn .. [20439](#)
- _fp_ep_isqrt_estiii:NNNNwww
..... [20439](#)

- __fp_ep_mul:wwwn [885](#), [20353](#), [21267](#),
[21280](#), [21855](#), [21885](#), [22113](#), [22124](#)
- __fp_ep_mul_raw:wwwn [20353](#), [21439](#), [21805](#)
- __fp_ep_to_ep:wwN . [20304](#), [20355](#),
[20358](#), [20370](#), [20373](#), [20423](#), [22114](#)
- __fp_ep_to_ep_end:www [20304](#)
- __fp_ep_to_ep_loop:N [898](#), [20304](#), [21806](#)
- __fp_ep_to_ep_zero:ww [20304](#)
- __fp_ep_to_fixed:wwn ... [20286](#),
[21436](#), [21992](#), [22001](#), [22111](#), [22600](#)
- __fp_ep_to_fixed_auxi:www ... [20286](#)
- __fp_ep_to_fixed_auxii:nnnnnnwn [20286](#)
- __fp_ep_to_float_o:wN [889](#)
- __fp_ep_to_float_o:wwN [887](#), [899](#), [20475](#),
[20487](#), [21291](#), [21330](#), [21345](#), [21904](#)
- __fp_error:nnnn [17001](#),
[17009](#), [17018](#), [17035](#), [17043](#), [17071](#),
[17094](#), [17293](#), [17295](#), [17316](#), [17321](#),
[18098](#), [18677](#), [18692](#), [19080](#), [19099](#),
[19110](#), [22219](#), [22273](#), [22347](#), [22854](#)
- __fp_exp_after?f:nw [736](#), [768](#), [17491](#)
- __fp_exp_after_any_f:Nnw [16756](#)
- __fp_exp_after_any_f:nw [736](#), [16756](#), [16782](#), [17493](#), [18267](#)
- __fp_exp_after_array_f:w [736](#), [16767](#),
[18152](#), [19250](#), [19261](#), [19271](#), [19279](#)
- __fp_exp_after_expr_mark_f:nw .. [768](#), [17491](#)
- __fp_exp_after_expr_stop_f:nw [16756](#)
- __fp_exp_after_f:nw [732](#), [768](#), [16643](#), [16761](#), [18200](#), [18338](#)
- __fp_exp_after_normal:nnNw [16646](#), [16656](#), [16673](#)
- __fp_exp_after_normal:Nwwww [16675](#), [16683](#)
- __fp_exp_after_o:w .. [732](#), [16643](#),
[16873](#), [16877](#), [16879](#), [17361](#), [17405](#),
[17423](#), [18659](#), [19200](#), [19218](#), [19227](#),
[19236](#), [19323](#), [20060](#), [21180](#), [21185](#)
- __fp_exp_after_special:nnNw ... [733](#), [16648](#), [16658](#), [16663](#)
- __fp_exp_after_tuple_f:nw [16767](#), [18466](#)
- __fp_exp_after_tuple_o:w [16767](#), [19225](#), [19228](#), [19231](#), [19233](#)
- \c__fp_exp_intarray [20880](#), [20966](#), [20973](#), [20976](#), [20978](#)
- __fp_exp_intarray:w [20937](#)
- __fp_exp_intarray_aux:w [20937](#)
- __fp_exp_large:NwN [876](#), [20937](#), [21164](#)
- __fp_exp_large_after:wwn [876](#), [20937](#)
- __fp_exp_normal_o:w .. [20792](#), [20806](#)
- __fp_exp_o:w [20550](#), [20787](#)
- __fp_exp_overflow:NN [20806](#)
- __fp_exp_pos_large:NnnNwn [20838](#), [20937](#)
- __fp_exp_pos_o:NNwnw [20809](#), [20811](#), [20814](#)
- __fp_exp_pos_o:Nwnnw [20806](#)
- __fp_exp_Taylor:Nnnwn [20834](#), [20853](#), [20983](#)
- __fp_exp_Taylor_break:Nnw ... [20853](#)
- __fp_exp_Taylor_ii:ww . [20859](#), [20862](#)
- __fp_exp_Taylor_loop:www [20853](#)
- __fp_expand:n [919](#)
- __fp_exponent:w [16610](#)
- __fp_facorial_int_o:n [884](#)
- __fp_fact_int_o:n [21245](#), [21248](#)
- __fp_fact_int_o:w [21242](#)
- __fp_fact_loop_o:w ... [21260](#), [21262](#)
- \c__fp_fact_max_arg_int [21223](#), [21250](#)
- __fp_fact_o:w [20554](#), [21224](#)
- __fp_fact_pos_o:w [21239](#), [21242](#)
- __fp_fact_small_o:w .. [21265](#), [21277](#)
- \c__fp_five_int [17155](#),
[17179](#), [17192](#), [17205](#), [17212](#), [17265](#)
- __fp_fixed(calculation):wwn .. [847](#)
- __fp_fixed_add:nnNnnwn [20179](#)
- __fp_fixed_add:Nnnnnwnn [20179](#)
- __fp_fixed_add:wwn [847](#),
[850](#), [20179](#), [20419](#), [20729](#), [20737](#),
[20748](#), [20766](#), [21997](#), [22057](#), [22615](#)
- __fp_fixed_add_after:NNNNwn . [20179](#)
- __fp_fixed_add_one:wN [848](#), [20111](#),
[20412](#), [20870](#), [20879](#), [22123](#), [22606](#)
- __fp_fixed_add_pack:NNNNwn . [20179](#)
- __fp_fixed_continue:wn [20110](#), [20356](#),
[20361](#), [20371](#), [20948](#), [21139](#), [21474](#),
[21843](#), [22115](#), [22124](#), [22598](#), [22610](#)
- __fp_fixed_div_int:wnN [20148](#)
- __fp_fixed_div_int:wwN [849](#), [20148](#), [20728](#), [20869](#), [22016](#)
- __fp_fixed_div_int_after:Nw ... [849](#), [20148](#)
- __fp_fixed_div_int_auxi:wnn . [20148](#)
- __fp_fixed_div_int_auxii:wnn ... [849](#), [20148](#)
- __fp_fixed_div_int_pack:Nw [849](#), [20148](#)
- __fp_fixed_div_myriad:wn [20116](#), [20416](#)

- __fp_fixed_inv_to_float_o:wN ...
..... [20482](#), [20811](#), [21075](#)
- __fp_fixed_mul:nnnnnnnw [20199](#)
- __fp_fixed_mul:wnn
.. [847](#), [848](#), [851](#), [897](#), [899](#), [20199](#),
[20365](#), [20396](#), [20411](#), [20413](#), [20417](#),
[20470](#), [20473](#), [20486](#), [20730](#), [20740](#),
[20780](#), [20871](#), [20969](#), [20984](#), [21085](#),
[21812](#), [21866](#), [22004](#), [22037](#), [22039](#)
- __fp_fixed_mul_add:nnnnwnnnn ...
..... [854](#), [20268](#), [20270](#)
- __fp_fixed_mul_add:nnnnwnnwN ...
..... [854](#), [20275](#), [20281](#)
- __fp_fixed_mul_add:Nwnnnwnnn ...
.... [853](#), [20232](#), [20242](#), [20253](#), [20257](#)
- __fp_fixed_mul_add:wwwn
..... [852](#), [20226](#), [22620](#)
- __fp_fixed_mul_after:wnn
..... [851](#), [20118](#), [20124](#), [20127](#),
[20201](#), [20228](#), [20238](#), [20248](#), [21102](#)
- __fp_fixed_mul_one_minus_-
mul:wnn [20226](#)
- __fp_fixed_mul_short:wnn
..... [848](#), [20125](#),
[20394](#), [20415](#), [20457](#), [20459](#), [22050](#)
- __fp_fixed_mul_sub_back:wwwn ...
..... [852](#), [20226](#),
[20471](#), [21833](#), [21835](#), [21836](#), [21837](#),
[21838](#), [21839](#), [21840](#), [21841](#), [21842](#),
[21846](#), [21848](#), [21849](#), [21850](#), [21851](#),
[21852](#), [21853](#), [21854](#), [21879](#), [21881](#),
[21882](#), [21883](#), [21884](#), [21887](#), [21889](#),
[21890](#), [21891](#), [21892](#), [22017](#), [22025](#)
- __fp_fixed_one_minus_mul:wnn ...
..... [852](#), [853](#), [20246](#)
- __fp_fixed_sub:wnn [20179](#), [20463](#),
[20746](#), [20762](#), [20774](#), [21478](#), [21998](#),
[22055](#), [22121](#), [22608](#), [22617](#), [22649](#)
- __fp_fixed_to_float_o:Nw
..... [20489](#), [20755](#)
- __fp_fixed_to_float_o:wN
..... [847](#), [863](#),
[907](#), [20476](#), [20489](#), [20775](#), [20785](#),
[20809](#), [21071](#), [22045](#), [22548](#), [22654](#)
- __fp_fixed_to_float_pack:ww ...
..... [20522](#), [20532](#)
- __fp_fixed_to_float_rad_o:wN ...
..... [20484](#), [22045](#)
- __fp_fixed_to_float_round_-
up:wnnnnw [20535](#), [20539](#)
- __fp_fixed_to_float_zero:w
..... [20518](#), [20527](#)
- __fp_fixed_to_loop:N
..... [20495](#), [20505](#), [20509](#)
- __fp_fixed_to_loop_end:w
..... [20511](#), [20515](#)
- __fp_from_dim:wNnnnnnnn [22415](#)
- __fp_from_dim:wnnnnwNn [22442](#), [22443](#)
- __fp_from_dim:wnnnnwNw [22415](#)
- __fp_from_dim:wNw [22415](#)
- __fp_from_dim_test:ww
.... [918](#), [17585](#), [17622](#), [18219](#), [22415](#)
- __fp_func_to_name:N
..... [16948](#), [18098](#), [18107](#)
- __fp_func_to_name_aux:w [16948](#)
- \c__fp_half_prec_int
..... [16593](#), [17826](#), [17858](#)
- __fp_if_type_fp:NTwFw . [734](#), [800](#),
[16623](#), [16702](#), [16710](#), [16717](#), [16733](#),
[16760](#), [18686](#), [18700](#), [18879](#), [18905](#),
[18906](#), [19073](#), [19074](#), [19075](#), [19241](#)
- __fp_inf_fp:N [16606](#), [17056](#)
- __fp_int:wTF [16880](#), [22559](#)
- __fp_int_eval:w
.... [737](#), [751](#), [753](#), [753](#), [767](#), [782](#),
[819](#), [827](#), [827](#), [830](#), [834](#), [863](#), [16560](#),
[16620](#), [16695](#), [16826](#), [16829](#), [17229](#),
[17233](#), [17245](#), [17246](#), [17282](#), [17373](#),
[17377](#), [17416](#), [17632](#), [17637](#), [17679](#),
[17768](#), [17779](#), [17828](#), [17859](#), [17865](#),
[17866](#), [17912](#), [17922](#), [17924](#), [17940](#),
[17942](#), [17965](#), [17967](#), [18133](#), [18355](#),
[18399](#), [18599](#), [18892](#), [19362](#), [19370](#),
[19391](#), [19393](#), [19414](#), [19416](#), [19425](#),
[19427](#), [19456](#), [19462](#), [19472](#), [19474](#),
[19548](#), [19550](#), [19566](#), [19568](#), [19572](#),
[19588](#), [19628](#), [19636](#), [19638](#), [19640](#),
[19642](#), [19645](#), [19648](#), [19650](#), [19669](#),
[19671](#), [19681](#), [19683](#), [19709](#), [19712](#),
[19720](#), [19722](#), [19743](#), [19746](#), [19749](#),
[19752](#), [19761](#), [19764](#), [19767](#), [19770](#),
[19777](#), [19779](#), [19785](#), [19793](#), [19795](#),
[19797](#), [19803](#), [19823](#), [19825](#), [19834](#),
[19836](#), [19857](#), [19878](#), [19882](#), [19894](#),
[19897](#), [19900](#), [19903](#), [19906](#), [19909](#),
[19912](#), [19915](#), [19919](#), [19931](#), [19935](#),
[19939](#), [19942](#), [19963](#), [19965](#), [19967](#),
[19977](#), [20016](#), [20018](#), [20027](#), [20114](#),
[20119](#), [20121](#), [20128](#), [20131](#), [20134](#),
[20137](#), [20140](#), [20143](#), [20152](#), [20164](#),
[20172](#), [20174](#), [20184](#), [20186](#), [20193](#),
[20202](#), [20204](#), [20207](#), [20210](#), [20213](#),
[20216](#), [20229](#), [20231](#), [20239](#), [20241](#),
[20249](#), [20251](#), [20261](#), [20264](#), [20267](#),
[20274](#), [20289](#), [20307](#), [20310](#), [20366](#),
[20380](#), [20382](#), [20388](#), [20401](#), [20403](#),
[20405](#), [20429](#), [20445](#), [20452](#), [20453](#),
[20476](#), [20493](#), [20497](#), [20542](#), [20544](#),

- 20588, 20599, 20618, 20620, 20622,
 20635, 20648, 20653, 20655, 20661,
 20678, 20679, 20680, 20681, 20682,
 20683, 20688, 20690, 20692, 20694,
 20696, 20701, 20703, 20705, 20707,
 20709, 20711, 20733, 20741, 20825,
 20874, 20951, 20959, 20967, 20973,
 20976, 21082, 21103, 21105, 21108,
 21111, 21114, 21117, 21133, 21159,
 21173, 21189, 21259, 21269, 21274,
 21426, 21458, 21467, 21699, 21713,
 21716, 21719, 21722, 21725, 21728,
 21731, 21734, 21737, 21753, 21763,
 21772, 21790, 21799, 21806, 21817,
 21827, 21860, 21870, 21895, 21904,
 21947, 21964, 21966, 21978, 21979,
 22020, 22031, 22042, 22100, 22252,
 22375, 22428, 22524, 22547, 22601,
 22653, 22675, 22677, 22679, 22684,
 22703, 22715, 22723, 22728, 22733
 __fp_int_eval_end:
 16560, 16620, 16698, 16817, 17282,
 17387, 17391, 18600, 18892, 19572,
 19607, 19799, 20174, 20310, 21133,
 21189, 21459, 21468, 21817, 21827,
 21870, 21895, 21979, 22682, 22684
 __fp_int_p:w 16880
 __fp_int_to_roman:w 16560,
 16829, 17840, 17872, 20615, 22785
 __fp_invalid_operation:nnw
 . 746, 16998, 17080, 17092, 22233,
 22240, 22287, 22294, 22394, 22409
 __fp_invalid_operation_o:nw ...
 . 746, 17091, 18107, 19847, 20073,
 20567, 21237, 21246, 21333, 21348,
 21363, 21378, 21393, 21408, 22070,
 22088, 22104, 22132, 22145, 22161
 __fp_invalid_operation_o:Nww ...
 746, 17006, 17080,
 18308, 19342, 19614, 19615, 21174
 __fp_invalid_operation_o:nww . 20098
 __fp_invalid_operation_tl_o:nn .
 746, 17015, 17080, 17348, 22579
 __fp_kind:w 16621, 17341, 18865
 \c__fp_leading_shift_int
 16783, 20119,
 20128, 20202, 21103, 21753, 21790
 __fp_ln_c:NwNw 870, 871, 20712, 20743
 __fp_ln_div_after:Nw
 869, 20614, 20663
 __fp_ln_div_i:w 20636, 20645
 __fp_ln_div_ii:wnn
 .. 20639, 20640, 20641, 20642, 20650
 __fp_ln_div_vi:wnn ... 20643, 20658
 __fp_ln_exponent:wn 872, 20590, 20752
 __fp_ln_exponent_one:ww 20757, 20771
 __fp_ln_exponent_small:NNww ...
 20760, 20764, 20777
 \c__fp_ln_i_fixed_tl 20555
 \c__fp_ln_ii_fixed_tl 20555
 \c__fp_ln_iii_fixed_tl 20555
 \c__fp_ln_iv_fixed_tl 20555
 \c__fp_ln_ix_fixed_tl 20555
 __fp_ln_npos_o:w
 864, 865, 20576, 20578
 __fp_ln_o:w .. 864, 880, 20552, 20564
 __fp_ln_significand:NNNNnnnN ...
 866, 20589, 20592, 21083
 __fp_ln_square_t_after:w
 20687, 20719
 __fp_ln_square_t_pack:NNNNnw ...
 .. 20689, 20691, 20693, 20695, 20717
 __fp_ln_t_large:NNw
 869, 20668, 20675, 20685
 __fp_ln_t_small:Nw ... 20666, 20673
 __fp_ln_t_small:w 869
 __fp_ln_Taylor:wwNw 870, 20720, 20721
 __fp_ln_Taylor_break:w 20726, 20737
 __fp_ln_Taylor_loop:www
 20722, 20723, 20732
 __fp_ln_twice_t_after:w 20700, 20716
 __fp_ln_twice_t_pack:Nw . 20702,
 20704, 20706, 20708, 20710, 20715
 \c__fp_ln_vi_fixed_tl 20555
 \c__fp_ln_vii_fixed_tl 20555
 \c__fp_ln_viii_fixed_tl 20555
 \c__fp_ln_x_fixed_tl
 20555, 20774, 20781
 __fp_ln_x_ii:wnnnn ... 20594, 20612
 __fp_ln_x_iii:NNNNNNw . 20621, 20625
 __fp_ln_x_iii_var:NNNNNw
 20619, 20627
 __fp_ln_x_iv:wnnnnnnnn
 868, 20617, 20632
 __fp_logb_aux_o:w 20030
 __fp_logb_o:w 19288, 20030
 \c__fp_max_exp_exponent_int
 16599, 20817
 \c__fp_max_exponent_int .. 16597,
 16603, 16631, 20327, 20529, 21138
 \c__fp_middle_shift_int
 16783, 20131,
 20134, 20137, 20140, 20204, 20207,
 20210, 20213, 21105, 21108, 21111,
 21114, 21756, 21763, 21793, 21799
 __fp_minmax_aux_o:Nw 19154
 __fp_minmax_auxi:ww
 19176, 19188, 19195

- _fp_minmax_auxii:ww [19178](#), [19186](#), [19195](#)
- _fp_minmax_break_o:w . [19169](#), [19199](#)
- _fp_minmax_loop:Nww [812](#), [19163](#), [19165](#), [19171](#)
- _fp_minmax_o:Nw [805](#), [18858](#), [18860](#), [19154](#)
- _c_fp_minus_min_exponent_int ... [16597](#), [16632](#)
- _fp_misused:n . [16573](#), [16577](#), [16688](#)
- _fp_mul_cases_o:NnNnw [829](#), [19579](#), [19585](#), [19691](#)
- _fp_mul_cases_o:nNnw [19585](#)
- _fp_mul_npos_o:Nww [825](#), [827](#), [829](#), [918](#), [19582](#), [19623](#), [22445](#)
- _fp_mul_significand_drop:NNNNw [827](#), [19632](#)
- _fp_mul_significand_keep:NNNNw [19632](#)
- _fp_mul_significand_large_-
f:NwwNNNN [19662](#), [19666](#)
- _fp_mul_significand_o:nnnnNnnnn [827](#), [827](#), [19630](#), [19632](#)
- _fp_mul_significand_small_-
f:NNwwN [19660](#), [19677](#)
- _fp_mul_significand_test_f:NNN [828](#), [19634](#), [19657](#)
- _c_fp_myriad_int [16596](#),
[20114](#), [20145](#), [20146](#), [20223](#), [20284](#)
- _fp_neg_sign:N [817](#), [16619](#), [19296](#), [19449](#)
- _fp_not_o:w [805](#), [18126](#), [19201](#)
- _c_fp_one_fixed_tl [20108](#),
[20728](#), [20941](#), [21139](#), [21166](#), [21949](#),
[22016](#), [22121](#), [22598](#), [22608](#), [22649](#)
- _fp_overflow:w [732](#),
[746](#), [748](#), [16634](#), [17080](#), [20819](#), [21253](#)
- _c_fp_overflowing_fp [16600](#), [22234](#), [22288](#)
- _fp_pack:NNNNw .. [16783](#), [20120](#),
[20130](#), [20133](#), [20136](#), [20139](#), [20142](#),
[20203](#), [20206](#), [20209](#), [20212](#), [20215](#),
[21104](#), [21107](#), [21110](#), [21113](#), [21116](#)
- _fp_pack_big:NNNNNw ... [16787](#),
[19896](#), [19899](#), [19902](#), [19905](#), [19908](#),
[19911](#), [19914](#), [19918](#), [20230](#), [20240](#),
[20250](#), [20260](#), [20263](#), [20266](#), [20273](#)
- _fp_pack_Bigg:NNNNNw [16792](#), [19745](#),
[19748](#), [19751](#), [19763](#), [19766](#), [19769](#)
- _fp_pack_eight:wNNNNNNNN [738](#), [823](#), [16799](#),
[19558](#), [19867](#), [20295](#), [21445](#), [21446](#)
- _fp_pack_twice_four:wNNNNNNNN .
..... [738](#), [16797](#), [17398](#), [17399](#),
[19500](#), [19501](#), [20296](#), [20297](#), [20298](#),
[20330](#), [20331](#), [20332](#), [20520](#), [20521](#),
[20856](#), [20857](#), [20858](#), [21447](#), [21448](#),
[21742](#), [21743](#), [21744](#), [21745](#), [22438](#)
- _fp_parse:n [758](#), [770](#),
[782](#), [789](#), [802](#), [803](#), [810](#), [919](#), [919](#),
[929](#), [17429](#), [17582](#), [18243](#), [18801](#),
[18803](#), [18805](#), [18828](#), [18865](#), [18874](#),
[18891](#), [18901](#), [19058](#), [19118](#), [20043](#),
[22209](#), [22263](#), [22341](#), [22386](#), [22401](#),
[22454](#), [22456](#), [22458](#), [22460](#), [22837](#)
- _fp_parse_after:ww [18243](#)
- _fp_parse_apply_binary:NwNwN ..
[762](#), [763](#), [766](#), [766](#), [794](#), [18281](#), [18476](#)
- _fp_parse_apply_binary_chk:NN .
..... [18281](#), [18312](#), [18325](#)
- _fp_parse_apply_binary_-
error:NNN [18281](#)
- _fp_parse_apply_comma:NwNwN ...
..... [794](#), [18435](#)
- _fp_parse_apply_compare:NwNNNNwN
..... [18623](#), [18632](#)
- _fp_parse_apply_compare_-
aux:NNwN [18644](#), [18647](#), [18652](#)
- _fp_parse_apply_function:NNNwN
..... [785](#), [18075](#), [18236](#)
- _fp_parse_apply_unary:NNNwN ...
..... [18080](#), [18112](#), [18227](#)
- _fp_parse_apply_unary_chk:nNNNw
..... [18091](#), [18092](#), [18095](#)
- _fp_parse_apply_unary_chk:nNNw
..... [18080](#)
- _fp_parse_apply_unary_chk:NwNw
..... [18080](#)
- _fp_parse_apply_unary_error:NNw
..... [18080](#), [20080](#)
- _fp_parse_apply_unary_type:NNN
..... [18080](#)
- _fp_parse_caseless_inf:N ... [18193](#)
- _fp_parse_caseless_infinity:N .
..... [18193](#)
- _fp_parse_caseless_nan:N ... [18193](#)
- _fp_parse_compare:NNNNNNN .. [18564](#)
- _fp_parse_compare_auxi:NNNNNNN
..... [18564](#)
- _fp_parse_compare_auxii:NNNNN .
..... [18564](#)
- _fp_parse_compare_end:NNNw . [18564](#)
- _fp_parse_continue:NwN
..... [762](#), [763](#), [790](#), [18270](#), [18283](#),
[18463](#), [18662](#), [19258](#), [19268](#), [19276](#)

__fp_parse_continue_compare:NNwNN
 18655, 18670
 __fp_parse_digits_:N 17447
 __fp_parse_digits_i:N 17447
 __fp_parse_digits_ii:N 17447
 __fp_parse_digits_iii:N 17447
 __fp_parse_digits_iv:N 17447
 __fp_parse_digits_v:N 17447
 __fp_parse_digits_vi:N
 17447, 17784, 17832
 __fp_parse_digits_vii:N
 775, 17447, 17771, 17821
 __fp_parse_excl_error: 18564
 __fp_parse_expand:w
 765, 766, 766, 766, 17444, 17446,
 17456, 17496, 17558, 17602, 17611,
 17614, 17618, 17655, 17689, 17727,
 17729, 17748, 17750, 17772, 17789,
 17802, 17822, 17852, 17880, 17896,
 17907, 17930, 17959, 17969, 17976,
 17989, 18005, 18025, 18036, 18122,
 18145, 18157, 18232, 18241, 18249,
 18262, 18382, 18430, 18454, 18480,
 18528, 18548, 18617, 18630, 19254
 __fp_parse_exponent:N
 780, 17557, 17763, 17912, 17979, 17981
 __fp_parse_exponent:Nw
 17787, 17800,
 17849, 17877, 17928, 17957, 17976
 __fp_parse_exponent_aux:N ... 17981
 __fp_parse_exponent_body:N
 18007, 18011
 __fp_parse_exponent_digits:N ...
 18015, 18027
 __fp_parse_exponent_keep:N .. 18038
 __fp_parse_exponent_keep:NTF ...
 18018, 18038
 __fp_parse_exponent_sign:N
 17997, 18001
 __fp_parse_function:NNN
 17141, 17143, 17145,
 17148, 18225, 18858, 18860, 21316,
 21318, 21320, 21322, 22483, 22485
 __fp_parse_function_all_fp_-
 o:nnw 17275, 18672, 19156
 __fp_parse_function_one_two:nnw
 903, 18684, 21910, 21916, 22552
 __fp_parse_function_one_two_-
 aux:nnw 18684
 __fp_parse_function_one_two_-
 auxii:nnw 18684
 __fp_parse_function_one_two_-
 error_o:w 18684
 __fp_parse_infix:NN
 768, 771, 788, 793,
 793, 17495, 17667, 17706, 18185,
 18200, 18222, 18338, 18341, 18428
 __fp_parse_infix_!:N 18564
 __fp_parse_infix_&:Nw 18521
 __fp_parse_infix(:N 18504
 __fp_parse_infix):N 18418
 __fp_parse_infix*:N 18506
 __fp_parse_infix+:N
 766, 17444, 18470
 __fp_parse_infix_,:N 18435
 __fp_parse_infix -:N 18470
 __fp_parse_infix/:N 18470
 __fp_parse_infix.:N . 18538, 19239
 __fp_parse_infix<:N 18564
 __fp_parse_infix=:N 18564
 __fp_parse_infix>:N 18564
 __fp_parse_infix?:N 18538
 __fp_parse_infix<operation>:N 766
 __fp_parse_infix^:N 18470
 __fp_parse_infix_after_operand:NwN
 771, 17550, 17628, 18129, 18336
 __fp_parse_infix_after_paren:NN
 18154, 18180, 18385
 __fp_parse_infix_and:N 18470, 18537
 __fp_parse_infix_check:NNN
 18361, 18371, 18405
 __fp_parse_infix_comma:w 794, 18435
 __fp_parse_infix_end:N
 789, 793, 18250, 18255, 18263, 18416
 __fp_parse_infix_juxt:N
 793, 18351, 18359, 18470
 __fp_parse_infix_mark:NNN
 18348, 18392, 18415
 __fp_parse_infix_mul:N
 793, 796, 18376,
 18395, 18403, 18470, 18505, 18514
 __fp_parse_infix_or:N . 18470, 18536
 __fp_parse_infix_|:Nw 18521
 __fp_parse_large:N 774, 17734, 17817
 __fp_parse_large_leading:wwNN ..
 777, 17819, 17824
 __fp_parse_large_round:NN
 778, 17860, 17932
 __fp_parse_large_round_aux:wNN .
 17932
 __fp_parse_large_round_test:NN .
 17932
 __fp_parse_large_trailing:wwNN .
 778, 17830, 17854
 __fp_parse_letters:N
 772, 772, 17643, 17657
 __fp_parse_lparen_after:NwN . 18135

- __fp_parse_o:n [758](#), [18243](#), [19056](#), [19057](#)
- __fp_parse_one:Nw [761–764](#), [766](#), [773](#), [788](#),
[790](#), [17444](#), [17467](#), [17711](#), [18074](#), [18276](#)
- __fp_parse_one_digit:NN [786](#), [17483](#), [17626](#)
- __fp_parse_one_fp:NN [767](#), [17475](#), [17491](#)
- __fp_parse_one_other:NN [17486](#), [17634](#)
- __fp_parse_one_register:NN [17478](#), [17548](#)
- __fp_parse_one_register_aux:Nw . [17548](#)
- __fp_parse_one_register_-auxii:wwwNw [17548](#)
- __fp_parse_one_register_dim:ww . [17548](#)
- __fp_parse_one_register_int:www [17548](#)
- __fp_parse_one_register_-math:NNw [17589](#)
- __fp_parse_one_register_mu:www . [17548](#)
- __fp_parse_one_register_-special:N [17553](#), [17589](#)
- __fp_parse_one_register_wd:Nw [17589](#)
- __fp_parse_one_register_wd:w . [17589](#)
- __fp_parse_operand:Nw [761–764](#), [766](#), [789](#), [794](#),
[17444](#), [18118](#), [18120](#), [18141](#), [18143](#),
[18232](#), [18241](#), [18248](#), [18261](#), [18270](#),
[18453](#), [18479](#), [18547](#), [18630](#), [19253](#)
- __fp_parse_pack_carry:w . [777](#), [17804](#)
- __fp_parse_pack_leading:NNNNww [17767](#), [17804](#), [17827](#)
- __fp_parse_pack_trailing:NNNNNww .. [17777](#), [17804](#), [17846](#), [17857](#), [17864](#)
- __fp_parse_prefix:NNN . [17646](#), [17691](#)
- __fp_parse_prefix_!:Nw [18108](#)
- __fp_parse_prefix(:Nw [18135](#)
- __fp_parse_prefix_):Nw [18167](#)
- __fp_parse_prefix+:Nw [18074](#)
- __fp_parse_prefix -:Nw [18108](#)
- __fp_parse_prefix.:Nw [18127](#)
- __fp_parse_prefix_unknown:NNN [17691](#)
- __fp_parse_return_semicolon:w .. [17445](#), [17454](#), [17687](#),
[17894](#), [17905](#), [17987](#), [18019](#), [18034](#)
- __fp_parse_round:Nw [17146](#)
- __fp_parse_round_after:wN [780](#), [17909](#), [17914](#), [17964](#)
- __fp_parse_round_loop:N ... [780](#),
[780](#), [780](#), [17882](#), [17925](#), [17943](#), [17968](#)
- __fp_parse_round_up:N [17882](#)
- __fp_parse_small:N [774](#), [17754](#), [17765](#)
- __fp_parse_small_leading:wwNN .. [775](#), [17769](#), [17774](#), [17836](#)
- __fp_parse_small_round:NN [17796](#), [17914](#), [17953](#)
- __fp_parse_small_trailing:wwNN . [776](#), [17782](#), [17791](#), [17868](#)
- __fp_parse_strim_end:w [17740](#)
- __fp_parse_strim_zeros:N [774](#), [786](#), [17721](#), [17740](#), [18133](#)
- __fp_parse_trim_end:w [17714](#)
- __fp_parse_trim_zeros:N [17632](#), [17714](#)
- __fp_parse_unary_function:NNN .. [18225](#), [19286](#), [19288](#), [19290](#), [19292](#),
[20550](#), [20552](#), [20554](#), [21304](#), [21310](#)
- __fp_parse_word:Nw [772](#), [17640](#), [17657](#)
- __fp_parse_word_abs:N [19285](#)
- __fp_parse_word_acos:N [21296](#)
- __fp_parse_word_acosd:N [21296](#)
- __fp_parse_word_acot:N [21315](#)
- __fp_parse_word_acotd:N [21315](#)
- __fp_parse_word_acsc:N [21296](#)
- __fp_parse_word_acscd:N [21296](#)
- __fp_parse_word_asec:N [21296](#)
- __fp_parse_word_asecd:N [21296](#)
- __fp_parse_word_asin:N [21296](#)
- __fp_parse_word_asind:N [21296](#)
- __fp_parse_word_atan:N [21315](#)
- __fp_parse_word_atand:N [21315](#)
- __fp_parse_word_bp:N [18196](#)
- __fp_parse_word_cc:N [18196](#)
- __fp_parse_word_ceil:N [17140](#)
- __fp_parse_word_cm:N [18196](#)
- __fp_parse_word_cos:N [21296](#)
- __fp_parse_word_cosd:N [21296](#)
- __fp_parse_word_cot:N [21296](#)
- __fp_parse_word_cotd:N [21296](#)
- __fp_parse_word_csc:N [21296](#)
- __fp_parse_word_cscd:N [21296](#)
- __fp_parse_word_dd:N [18196](#)
- __fp_parse_word_deg:N [18182](#)
- __fp_parse_word_em:N [18215](#)
- __fp_parse_word_ex:N [18215](#)
- __fp_parse_word_exp:N [20549](#)
- __fp_parse_word_fact:N [20549](#)
- __fp_parse_word_false:N [18182](#)
- __fp_parse_word_floor:N [17140](#)
- __fp_parse_word_in:N [18196](#)
- __fp_parse_word_inf:N [18182](#), [18193](#), [18194](#)
- __fp_parse_word_ln:N [20549](#)
- __fp_parse_word_logb:N [19285](#)
- __fp_parse_word_max:N [18857](#)

- __fp_parse_word_min:N [18857](#)
- __fp_parse_word_mm:N [18196](#)
- __fp_parse_word_nan:N . [18182](#), [18195](#)
- __fp_parse_word_nc:N [18196](#)
- __fp_parse_word_nd:N [18196](#)
- __fp_parse_word_pc:N [18196](#)
- __fp_parse_word_pi:N [18182](#)
- __fp_parse_word_pt:N [18196](#)
- __fp_parse_word_rand:N [22482](#)
- __fp_parse_word_randint:N ... [22482](#)
- __fp_parse_word_round:N [17146](#)
- __fp_parse_word_sec:N [21296](#)
- __fp_parse_word_secd:N [21296](#)
- __fp_parse_word_sign:N [19285](#)
- __fp_parse_word_sin:N [21296](#)
- __fp_parse_word_sind:N [21296](#)
- __fp_parse_word_sp:N [18196](#)
- __fp_parse_word_sqrt:N [19285](#)
- __fp_parse_word_tan:N [21296](#)
- __fp_parse_word_tand:N [21296](#)
- __fp_parse_word_true:N [18182](#)
- __fp_parse_word_trunc:N [17140](#)
- __fp_parse_zero:
..... [774](#), [17736](#), [17756](#), [17760](#)
- __fp_pow_B:wwN [21086](#), [21121](#)
- __fp_pow_C_neg:w [21124](#), [21141](#)
- __fp_pow_C_overflow:w
..... [21129](#), [21136](#), [21157](#)
- __fp_pow_C_pack:w [21143](#), [21151](#), [21162](#)
- __fp_pow_C_pos:w [21127](#), [21146](#)
- __fp_pow_C_pos_loop:wN
..... [21147](#), [21148](#), [21155](#)
- __fp_pow_exponent:Nwnnnnw
..... [21092](#), [21095](#), [21100](#)
- __fp_pow_exponent:wnN . [21084](#), [21089](#)
- __fp_pow_neg:www . [882](#), [20997](#), [21168](#)
- __fp_pow_neg_aux:wNN ... [882](#), [21168](#)
- __fp_pow_neg_case:w . [21170](#), [21191](#)
- __fp_pow_neg_case_aux:nnnnn . [21191](#)
- __fp_pow_neg_case_aux:Nnnw
..... [883](#), [21191](#)
- __fp_pow_normal_o:ww
..... [878](#), [21002](#), [21034](#)
- __fp_pow_npos_aux:NNnw
..... [21069](#), [21073](#), [21079](#)
- __fp_pow_npos_o:Nww [879](#), [21046](#), [21063](#)
- __fp_pow_zero_or_inf:ww
..... [878](#), [21004](#), [21011](#)
- \c__fp_prec_and_int ... [17429](#), [18501](#)
- \c__fp_prec_colon_int
..... [17429](#), [18559](#), [19253](#)
- \c__fp_prec_comma_int
..... [786](#), [17429](#), [17503](#),
[18141](#), [18169](#), [18439](#), [18444](#), [18453](#)
- \c__fp_prec_comp_int
..... [17429](#), [18587](#), [18630](#)
- \c__fp_prec_end_int [789](#),
[793](#), [17429](#), [17505](#), [18248](#), [18261](#), [18422](#)
- \c__fp_prec_func_int
..... [786](#), [17429](#), [18140](#), [18232](#), [18241](#)
- \c__fp_prec_hat_int ... [17429](#), [18489](#)
- \c__fp_prec_hatii_int . [17429](#), [18489](#)
- \c__fp_prec_int
[16593](#), [16826](#), [16887](#), [16914](#), [17367](#),
[20837](#), [21203](#), [21206](#), [22306](#), [22308](#),
[22314](#), [22365](#), [22563](#), [22602](#), [22653](#)
- \c__fp_prec_juxt_int .. [17429](#), [18491](#)
- \c__fp_prec_not_int
..... [786](#), [17429](#), [18125](#), [18126](#)
- \c__fp_prec_or_int [17429](#), [18503](#)
- \c__fp_prec_plus_int
..... [760](#), [17429](#), [18497](#), [18499](#)
- \c__fp_prec_quest_int
..... [17429](#), [18542](#), [18557](#)
- \c__fp_prec_times_int
..... [17429](#), [18493](#), [18495](#)
- \c__fp_prec_tuple_int
..... [786](#), [17429](#), [17504](#), [18143](#), [18171](#)
- __fp_rand_myriads:n
..... [923](#), [924](#), [22518](#), [22535](#), [22621](#)
- __fp_rand_myriads_get:w [22518](#)
- __fp_rand_myriads_loop:w [22518](#)
- __fp_rand_o:Nw
..... [22483](#), [22490](#), [22496](#), [22529](#)
- __fp_rand_o:w [22529](#)
- __fp_randinat_wide_aux:w [22691](#)
- __fp_randinat_wide_auxii:w .. [22691](#)
- __fp_randint:n [22753](#)
- __fp_randint:ww [22659](#), [22763](#)
- __fp_randint_auxi_o:ww [22550](#)
- __fp_randint_auxii:wn [22550](#)
- __fp_randint_auxiii_o:ww [22550](#)
- __fp_randint_auxiv_o:ww [22550](#)
- __fp_randint_auxv_o:w [22550](#)
- __fp_randint_badarg:w ... [924](#), [22550](#)
- __fp_randint_default:w [22550](#)
- __fp_randint_o:Nw [22485](#), [22496](#), [22550](#)
- __fp_randint_o:w [22550](#)
- __fp_randint_split_aux:w [22691](#)
- __fp_randint_split_o:Nw . [927](#), [22691](#)
- __fp_randint_wide_aux:w
..... [927](#), [22694](#), [22725](#)
- __fp_randint_wide_auxii:w
..... [22727](#), [22736](#)
- __fp_reverse_args:Nww
..... [909](#), [910](#), [16569](#),
[21896](#), [21971](#), [22084](#), [22150](#), [22647](#)

__fp_round:NNN [751](#), [751](#), [753](#), [828](#),
 [844](#), [17156](#), [17226](#), [19417](#), [19428](#),
 [19672](#), [19684](#), [19826](#), [19837](#), [20021](#)
 __fp_round:Nwn . [17284](#), [17337](#), [22413](#)
 __fp_round:Nww . [17285](#), [17306](#), [17337](#)
 __fp_round:Nwww [17286](#), [17300](#)
 __fp_round_aux_o:Nw [17273](#)
 __fp_round_digit:Nw .. [740](#), [753](#),
 [827](#), [828](#), [844](#), [16844](#), [17240](#), [19431](#),
 [19574](#), [19675](#), [19687](#), [19840](#), [20026](#)
 __fp_round_name_from_cs:N
 .. [17276](#), [17296](#), [17322](#), [17326](#), [17349](#)
 __fp_round_neg:NNN [751](#),
 [754](#), [824](#), [17251](#), [19536](#), [19551](#), [19569](#)
 __fp_round_no_arg_o:Nw [17283](#), [17290](#)
 __fp_round_normal:NnnwNnn .. [17337](#)
 __fp_round_normal:NNwNnn [17337](#)
 __fp_round_normal:NwNNnw [17337](#)
 __fp_round_normal_end:wwNnn . [17337](#)
 __fp_round_o:Nw
 .. [17141](#), [17143](#), [17145](#), [17149](#), [17273](#)
 __fp_round_pack:Nw [17337](#)
 __fp_round_return_one:
 [751](#), [17156](#), [17162](#),
 [17172](#), [17180](#), [17184](#), [17193](#), [17197](#),
 [17206](#), [17213](#), [17217](#), [17255](#), [17266](#)
 __fp_round_s:NNNw
 .. [751](#), [753](#), [780](#), [17224](#), [17918](#), [17936](#)
 __fp_round_special:NwwNnn .. [17337](#)
 __fp_round_special_aux:Nw [17337](#)
 __fp_round_to_nearest:NNN
 [754](#), [755](#), [17149](#), [17152](#),
 [17156](#), [17260](#), [17292](#), [17302](#), [22413](#)
 __fp_round_to_nearest_neg:NNN [17251](#)
 __fp_round_to_nearest_ninf:NNN .
 [755](#), [17156](#), [17271](#)
 __fp_round_to_nearest_ninf_-
 neg:NNN [17251](#)
 __fp_round_to_nearest_pinf:NNN .
 [755](#), [17156](#), [17262](#)
 __fp_round_to_nearest_pinf_-
 neg:NNN [17251](#)
 __fp_round_to_nearest_zero:NNN .
 [755](#), [17156](#)
 __fp_round_to_nearest_zero_-
 neg:NNN [17251](#)
 __fp_round_to_ninf:NNN
 [17143](#), [17156](#), [17259](#), [17330](#)
 __fp_round_to_ninf_neg:NNN .. [17251](#)
 __fp_round_to_pinf:NNN
 [17145](#), [17156](#), [17251](#), [17332](#)
 __fp_round_to_pinf_neg:NNN .. [17251](#)
 __fp_round_to_zero:NNN
 [17141](#), [17156](#), [17328](#)
 __fp_round_to_zero_neg:NNN .. [17251](#)
 __fp_rrot:www [16570](#), [22017](#)
 __fp_sanitize:Nw
 [819](#), [821](#), [827](#), [829](#), [838](#),
 [884](#), [900](#), [907](#), [924](#), [16628](#), [17406](#),
 [17424](#), [19360](#), [19454](#), [19626](#), [19707](#),
 [19855](#), [20580](#), [20823](#), [21065](#), [21257](#),
 [21858](#), [21902](#), [22029](#), [22545](#), [22640](#)
 __fp_sanitize:wN
 [771](#), [775](#), [16628](#), [17631](#), [18132](#)
 __fp_sanitize_zero:w [16628](#)
 __fp_sec_o:w [21368](#)
 __fp_set_sign_o:w
 .. [18125](#), [19286](#), [20057](#), [20058](#), [20079](#)
 __fp_show:NN [18833](#)
 __fp_sign_aux_o:w [20046](#)
 __fp_sign_o:w [19290](#), [20046](#)
 __fp_sin_o:w [744](#), [785](#), [785](#), [908](#), [21323](#)
 __fp_sin_series_aux_o:NNwww . [21810](#)
 __fp_sin_series_o:NNwww .. [887](#),
 [901](#), [21329](#), [21344](#), [21359](#), [21374](#), [21810](#)
 __fp_small_int:wTF
 [883](#), [16896](#), [17339](#), [21244](#)
 __fp_small_int_normal:NnwTF . [16896](#)
 __fp_small_int_test:NnnwNTF . [16896](#)
 __fp_small_int_test:NnnwNw
 [16915](#), [16918](#)
 __fp_small_int_true:wTF [16896](#)
 __fp_sqrt_auxi_o:NNNNwnnN
 [19877](#), [19885](#)
 __fp_sqrt_auxii_o:NnnnnnnnN ..
 [839](#), [841](#), [19887](#), [19891](#), [19971](#), [19983](#)
 __fp_sqrt_auxiii_o:wnnnnnnnn ..
 [19888](#), [19926](#), [19972](#)
 __fp_sqrt_auxiv_o:NNNNNw [19926](#)
 __fp_sqrt_auxix_o:wnwnw [19960](#)
 __fp_sqrt_auxv_o:NNNNNw [19926](#)
 __fp_sqrt_auxvi_o:NNNNNw [19926](#)
 __fp_sqrt_auxvii_o:NNNNNw ... [19926](#)
 __fp_sqrt_auxviii_o:nnnnnnnn ..
 .. [19948](#), [19950](#), [19952](#), [19958](#), [19960](#)
 __fp_sqrt_auxx_o:Nnnnnnnnn
 [19956](#), [19974](#)
 __fp_sqrt_auxxi_o:wnnnN [19974](#)
 __fp_sqrt_auxxii_o:nnnnnnnnnw ...
 [19984](#), [19988](#)
 __fp_sqrt_auxxiii_o:w [19988](#)
 __fp_sqrt_auxxiv_o:wnnnnnnnnN ...
 [20000](#), [20003](#), [20011](#), [20013](#)
 __fp_sqrt_Newton_o:wnw
 [839](#), [19862](#), [19873](#), [19874](#)
 __fp_sqrt_npos_auxi_o:wnnnN . [19853](#)
 __fp_sqrt_npos_auxii_o:wnnnnnnnn
 [19853](#)

- __fp_sqrt_npos_o:w ... [19850](#), [19853](#)
- __fp_sqrt_o:w [19292](#), [19843](#)
- __fp_step:NNnnnn [19123](#)
- __fp_step:NnnnnN [19053](#)
- __fp_step:wwwN [19053](#)
- __fp_step_fp:wwwN [19053](#)
- __fp_str_if_eq:nn [16933](#),
[18043](#), [18057](#), [18345](#), [18389](#), [21037](#)
- __fp_sub_back_far_o:NnnwnnnN ..
..... [823](#), [19463](#), [19509](#)
- __fp_sub_back_near_after:wNNNNw
..... [19469](#), [19547](#)
- __fp_sub_back_near_o:nnnnnnnnN .
..... [822](#), [19459](#), [19469](#)
- __fp_sub_back_near_pack:NNNNNNw
..... [19469](#), [19549](#)
- __fp_sub_back_not_far_o:wwwNN .
..... [19524](#), [19544](#)
- __fp_sub_back_quite_far_ii:NN [19528](#)
- __fp_sub_back_quite_far_o:wwNN .
..... [19522](#), [19528](#)
- __fp_sub_back_shift:wnnnn
..... [822](#), [19481](#), [19485](#)
- __fp_sub_back_shift_ii:ww ... [19485](#)
- __fp_sub_back_shift_iii:NNNNNNNw
..... [19485](#)
- __fp_sub_back_shift_iv:nnnnw . [19485](#)
- __fp_sub_back_very_far_ii_-
o:nnNwNN [19556](#)
- __fp_sub_back_very_far_o:wwwNN
..... [19523](#), [19556](#)
- __fp_sub_eq_o:Nnwnw [19434](#)
- __fp_sub_npos_i_o:Nnwnw
..... [821](#), [19439](#), [19448](#), [19452](#)
- __fp_sub_npos_ii_o:Nnwnw [19434](#)
- __fp_sub_npos_o:NnwNnw
..... [821](#), [19354](#), [19434](#)
- __fp_tan_o:w [21383](#)
- __fp_tan_series_aux_o:Nnwww . [21864](#)
- __fp_tan_series_o:NNwww
..... [888](#), [889](#), [21390](#), [21405](#), [21864](#)
- __fp_ternary:NwWN . [805](#), [18557](#), [19237](#)
- __fp_ternary_auxi:NwWN
..... [805](#), [815](#), [19237](#)
- __fp_ternary_auxii:NwWN
..... [805](#), [815](#), [18559](#), [19237](#)
- __fp_tmp:w [740](#), [795](#),
[16838](#), [16848](#), [16849](#), [16850](#), [16851](#),
[16852](#), [16853](#), [16854](#), [16855](#), [16856](#),
[16857](#), [16858](#), [16859](#), [16860](#), [16861](#),
[16862](#), [16863](#), [16953](#), [16955](#), [17447](#),
[17459](#), [17460](#), [17461](#), [17462](#), [17463](#),
[17464](#), [17465](#), [17524](#), [17546](#), [18108](#),
[18125](#), [18126](#), [18182](#), [18187](#), [18188](#),
[18189](#), [18190](#), [18191](#), [18192](#), [18196](#),
[18204](#), [18205](#), [18206](#), [18207](#), [18208](#),
[18209](#), [18210](#), [18211](#), [18212](#), [18213](#),
[18214](#), [18418](#), [18434](#), [18435](#), [18458](#),
[18470](#), [18488](#), [18490](#), [18492](#), [18494](#),
[18496](#), [18498](#), [18500](#), [18502](#), [18506](#),
[18520](#), [18521](#), [18536](#), [18537](#), [18538](#),
[18556](#), [18558](#), [20089](#), [20103](#), [20104](#)
- __fp_to_decimal:w
.. [22268](#), [22278](#), [22395](#), [22412](#), [22899](#)
- __fp_to_decimal_dispatch:w [913](#),
[916](#), [917](#), [19116](#), [22258](#), [22262](#), [22265](#)
- __fp_to_decimal_huge:wnnnn .. [22278](#)
- __fp_to_decimal_large:Nnnw .. [22278](#)
- __fp_to_decimal_normal:wnnnn ..
..... [22278](#), [22366](#)
- __fp_to_decimal_recover:w ... [22265](#)
- __fp_to_dim:w [22380](#)
- __fp_to_dim_dispatch:w .. [917](#), [22380](#)
- __fp_to_dim_recover:w [22380](#)
- __fp_to_int:w [917](#), [22405](#), [22410](#)
- __fp_to_int_dispatch:w [22396](#)
- __fp_to_int_recover:w [22396](#)
- __fp_to_scientific:w
..... [914](#), [22214](#), [22224](#)
- __fp_to_scientific_dispatch:w ..
..... [912](#), [916](#), [22204](#), [22208](#), [22211](#)
- __fp_to_scientific_normal:wnnnn
..... [22224](#)
- __fp_to_scientific_normal:wNw [22224](#)
- __fp_to_scientific_recover:w . [22211](#)
- __fp_to_tl:w ... [22344](#), [22352](#), [22907](#)
- __fp_to_tl_dispatch:w
..... [911](#), [915](#), [22336](#), [22340](#), [22343](#), [22476](#)
- __fp_to_tl_normal:nnnn [22352](#)
- __fp_to_tl_recover:w [22343](#)
- __fp_to_tl_scientific:wnnnn . [22352](#)
- __fp_to_tl_scientific:wNw ... [22352](#)
- \c__fp_trailing_shift_int
..... [16783](#), [20121](#),
[20143](#), [20216](#), [21117](#), [21756](#), [21793](#)
- __fp_trap_division_by_zero_-
set:N [17023](#)
- __fp_trap_division_by_zero_set_-
error: [17023](#)
- __fp_trap_division_by_zero_set_-
flag: [17023](#)
- __fp_trap_division_by_zero_set_-
none: [17023](#)
- __fp_trap_invalid_operation_-
set:N [16989](#)
- __fp_trap_invalid_operation_-
set_error: [16989](#)

- __fp_trap_invalid_operation_-set_flag: [16989](#)
- __fp_trap_invalid_operation_-set_none: [16989](#)
- __fp_trap_overflow_set:N [17049](#)
- __fp_trap_overflow_set:NnNn . [17049](#)
- __fp_trap_overflow_set_error: [17049](#)
- __fp_trap_overflow_set_flag: . [17049](#)
- __fp_trap_overflow_set_none: . [17049](#)
- __fp_trap_underflow_set:N ... [17049](#)
- __fp_trap_underflow_set_error: .
..... [17049](#)
- __fp_trap_underflow_set_flag: [17049](#)
- __fp_trap_underflow_set_none: [17049](#)
- __fp_trig:NNNNwn . [21329](#), [21344](#),
[21359](#), [21374](#), [21389](#), [21404](#), [21421](#)
- \c__fp_trig_intarray [896](#),
[21482](#), [21712](#), [21715](#), [21718](#), [21721](#),
[21724](#), [21727](#), [21730](#), [21733](#), [21736](#)
- __fp_trig_large:ww ... [21429](#), [21696](#)
- __fp_trig_large_auxi:w [21696](#)
- __fp_trig_large_auxii:w . [896](#), [21696](#)
- __fp_trig_large_auxiii:w [896](#), [21696](#)
- __fp_trig_large_auxix:Nw [21769](#)
- __fp_trig_large_auxv:www
..... [21746](#), [21749](#)
- __fp_trig_large_auxvi:wnnnnnnnn
..... [21749](#)
- __fp_trig_large_auxvii:w
..... [21752](#), [21769](#)
- __fp_trig_large_auxviii:w ... [21769](#)
- __fp_trig_large_auxviii:ww
..... [21771](#), [21775](#)
- __fp_trig_large_auxx:wnnnnn . [21769](#)
- __fp_trig_large_auxxi:w [21769](#)
- __fp_trig_large_pack:NNNNw ...
..... [21749](#), [21798](#)
- __fp_trig_small:ww
[890](#), [898](#), [21431](#), [21435](#), [21441](#), [21808](#)
- __fp_trigd_large:ww .. [21429](#), [21443](#)
- __fp_trigd_large_auxi:nnnnwnnnn
..... [21443](#)
- __fp_trigd_large_auxii:wNw .. [21443](#)
- __fp_trigd_large_auxiii:www . [21443](#)
- __fp_trigd_small:ww
..... [891](#), [21431](#), [21437](#), [21480](#)
- __fp_trim_zeros:w
..... [22195](#), [22319](#), [22328](#), [22379](#)
- __fp_trim_zeros_dot:w [22195](#)
- __fp_trim_zeros_end:w [22195](#)
- __fp_trim_zeros_loop:w [22195](#)
- __fp_tuple_ [19227](#), [19228](#), [19231](#), [19232](#)
- __fp_tuple_&o:ww [19210](#)
- __fp_tuple_&tuple_o:ww [19210](#)
- __fp_tuple_*o:ww [20083](#)
- __fp_tuple_+tuple_o:ww [20089](#)
- __fp_tuple_-tuple_o:ww [20089](#)
- __fp_tuple_/o:ww [20083](#)
- __fp_tuple_chk:w [734](#),
[16686](#), [16692](#), [16693](#), [16770](#), [16773](#),
[18467](#), [18679](#), [18694](#), [18719](#), [18722](#),
[18738](#), [18739](#), [18742](#), [18951](#), [18952](#),
[20092](#), [20093](#), [20099](#), [20100](#), [22174](#)
- __fp_tuple_compare_back:ww .. [18948](#)
- __fp_tuple_compare_back_loop:w .
..... [18948](#)
- __fp_tuple_compare_back_-
tuple:ww [18948](#)
- __fp_tuple_convert:Nw
..... [22174](#), [22223](#), [22277](#), [22351](#)
- __fp_tuple_convert_end:w [22174](#)
- __fp_tuple_convert_loop:nNw . [22174](#)
- __fp_tuple_count:w [16691](#)
- __fp_tuple_count_loop:Nw [16691](#)
- __fp_tuple_map_loop_o:nw [18719](#)
- __fp_tuple_map_o:nw
.. [18719](#), [20076](#), [20084](#), [20086](#), [20088](#)
- __fp_tuple_mapthread_loop_o:nw .
..... [18737](#)
- __fp_tuple_mapthread_o:nww
..... [18737](#), [20097](#)
- __fp_tuple_not_o:w [19201](#)
- __fp_tuple_set_sign_aux_o:Nnw [20068](#)
- __fp_tuple_set_sign_aux_o:w . [20068](#)
- __fp_tuple_set_sign_o:w [20068](#)
- __fp_tuple_to_decimal:w [22265](#)
- __fp_tuple_to_scientific:w .. [22211](#)
- __fp_tuple_to_tl:w [22343](#)
- __fp_tuple_|o:ww [19210](#)
- __fp_tuple_|tuple_o:ww [19210](#)
- __fp_type_from_scan:N
.. [735](#), [16715](#), [18289](#), [18291](#), [18315](#),
[18317](#), [18328](#), [18330](#), [18912](#), [18914](#)
- __fp_type_from_scan:w [16715](#)
- __fp_type_from_scan_other:N ...
..... [16715](#), [16739](#), [16757](#)
- __fp_underflow:w
.. [732](#), [746](#), [748](#), [16635](#), [17080](#), [20820](#)
- __fp_use_i:ww
..... [855](#), [909](#), [16571](#), [20333](#), [22103](#)
- __fp_use_i:www [16571](#)
- __fp_use_i_delimit_by_s_stop:nw
..... [16582](#), [18880](#), [19242](#)
- __fp_use_i_until_s:nw [898](#), [16566](#),
[16615](#), [16625](#), [16888](#), [21473](#), [21751](#),
[21757](#), [21788](#), [22563](#), [22634](#), [22845](#)
- __fp_use_ii_until_s:nnw
..... [16566](#), [16613](#), [16624](#)

- `__fp_use_none_stop_f:n`
..... [16563](#), [20498](#), [20499](#), [20500](#)
- `__fp_use_none_until_s:w`
.. [16566](#), [19879](#), [21177](#), [22098](#), [22101](#)
- `__fp_use_s:n` [16564](#)
- `__fp_use_s:nn` [16564](#)
- `__fp_zero_fp:N` . [16606](#), [17064](#), [17412](#)
- `__fp_|_o:ww` [805](#), [19210](#)
- `__fp_|_tuple_o:ww` [19210](#)
- `__fp_` [19213](#), [19220](#), [19229](#), [19230](#)
- fparray commands:
 - `\fparray_count:N` [219](#),
[219](#), [219](#), [22805](#), [22817](#), [22828](#), [22884](#)
 - `\fparray_gset:Nnn` ... [219](#), [930](#), [22830](#)
 - `\fparray_gzero:N` [219](#), [22881](#)
 - `\fparray_item:Nn` ... [219](#), [930](#), [22894](#)
 - `\fparray_item_to_tl:Nn` ... [219](#), [22894](#)
 - `\fparray_new:Nn` [219](#), [22778](#)
 - `\futurelet` [374](#)
- G**
- `\gdef` [375](#)
- `\GetIdInfo` [7](#), [14473](#)
- `\gleaders` [928](#), [1803](#)
- `\global` [167](#),
[168](#), [182](#), [183](#), [184](#), [195](#), [196](#), [197](#),
[198](#), [199](#), [200](#), [201](#), [202](#), [203](#), [272](#), [376](#)
- `\globaldefs` [377](#)
- `\glueexpr` [631](#), [1502](#)
- `\glueshrink` [632](#), [1503](#)
- `\glueshrinkorder` [633](#), [1504](#)
- `\gluestretch` [634](#), [1505](#)
- `\gluestretchorder` [635](#), [1506](#)
- `\gluetomu` [636](#), [1507](#)
- group commands:
 - `\group_align_safe_begin/end:` [541](#), [952](#)
 - `\group_align_safe_begin:`
..... [113](#), [396](#), [400](#), [533](#), [4525](#),
[4899](#), [9656](#), [9859](#), [11571](#), [11586](#),
[23418](#), [29566](#), [29915](#), [31011](#), [32153](#)
 - `\group_align_safe_end:`
..... [113](#), [396](#), [400](#), [4548](#), [4925](#),
[9658](#), [9859](#), [11580](#), [11591](#), [11597](#),
[23421](#), [29578](#), [29927](#), [31014](#), [32161](#)
 - `\group_begin:`
.. [9](#), [391](#), [1108](#), [2129](#), [2858](#), [2861](#),
[2864](#), [3245](#), [3716](#), [3907](#), [4303](#), [4399](#),
[4620](#), [5288](#), [5315](#), [5591](#), [5614](#), [6000](#),
[6110](#), [6163](#), [6336](#), [6382](#), [6473](#), [6521](#),
[6567](#), [6574](#), [6901](#), [7083](#), [8294](#), [8331](#),
[9995](#), [10055](#), [10905](#), [10911](#), [10962](#),
[11042](#), [11290](#), [11308](#), [11332](#), [11420](#),
[11438](#), [11692](#), [12206](#), [12230](#), [12246](#),
[12319](#), [12614](#), [12979](#), [13198](#), [13410](#),
[13456](#), [13719](#), [13887](#), [14480](#), [15097](#),
[15243](#), [19210](#), [23074](#), [23111](#), [23417](#),
[23424](#), [23497](#), [23657](#), [24005](#), [24098](#),
[24413](#), [24912](#), [25276](#), [25369](#), [25760](#),
[26118](#), [26329](#), [26489](#), [26498](#), [26510](#),
[26519](#), [26527](#), [26645](#), [26675](#), [27168](#),
[28969](#), [29216](#), [29275](#), [29359](#), [29386](#),
[30658](#), [30665](#), [30692](#), [30924](#), [30945](#),
[30976](#), [31230](#), [31317](#), [32138](#), [32482](#),
[32614](#), [32635](#), [32700](#), [32709](#), [32720](#)
 - `\c_group_begin_token`
.... [55](#), [133](#), [270](#), [411](#), [581](#), [5031](#),
[5068](#), [11290](#), [11314](#), [23462](#), [27211](#),
[27217](#), [27231](#), [27237](#), [27313](#), [27319](#),
[27334](#), [27340](#), [29442](#), [29651](#), [32176](#)
 - `\group_end:`
[9](#), [9](#), [495](#), [1108](#), [2129](#), [2858](#), [2861](#),
[2867](#), [3254](#), [3719](#), [3910](#), [4309](#), [4421](#),
[4471](#), [4624](#), [5306](#), [5338](#), [5596](#), [5619](#),
[6010](#), [6123](#), [6166](#), [6349](#), [6391](#), [6486](#),
[6533](#), [6592](#), [6654](#), [7082](#), [7214](#), [8303](#),
[8341](#), [8346](#), [10012](#), [10083](#), [10913](#),
[10920](#), [11045](#), [11065](#), [11307](#), [11311](#),
[11339](#), [11437](#), [11485](#), [11716](#), [12225](#),
[12238](#), [12257](#), [12471](#), [12659](#), [12995](#),
[13204](#), [13414](#), [13485](#), [13742](#), [13905](#),
[14483](#), [15217](#), [15281](#), [19234](#), [23078](#),
[23119](#), [23328](#), [23422](#), [23443](#), [23504](#),
[23681](#), [24018](#), [24112](#), [24446](#), [24454](#),
[24925](#), [25334](#), [25376](#), [25383](#), [25391](#),
[25764](#), [25765](#), [26155](#), [26393](#), [26494](#),
[26505](#), [26589](#), [26651](#), [26712](#), [27174](#),
[28970](#), [29284](#), [29356](#), [29373](#), [29402](#),
[30683](#), [30691](#), [30938](#), [30944](#), [30971](#),
[31002](#), [31234](#), [31587](#), [32142](#), [32490](#),
[32621](#), [32646](#), [32703](#), [32713](#), [32724](#)
 - `\c_group_end_token`
[133](#), [270](#), [581](#), [11290](#), [11319](#), [23465](#),
[27225](#), [27328](#), [29443](#), [29657](#), [32177](#)
 - `\group_insert_after:N` [9](#), [2135](#), [24014](#)
- groups commands:
 - `.groups:n` [186](#), [15726](#)
- H**
- `\H` [29521](#), [31360](#), [31507](#), [31508](#), [31535](#), [31536](#)
- `\halign` [378](#)
- `\hangafter` [379](#)
- `\hangindent` [380](#)
- `\hbadness` [381](#)
- `\hbox` [382](#)
- hbox commands:
 - `\hbox:n`
[238](#), [27182](#), [27407](#), [27703](#), [28760](#), [28815](#)

- \hbox_gset:Nn [239](#), [27184](#), [27374](#), [27497](#),
[27541](#), [27561](#), [27581](#), [27598](#), [27619](#),
[27648](#), [27659](#), [27817](#), [28244](#), [31606](#)
- \hbox_gset:Nw [239](#), [27208](#), [27883](#)
- \hbox_gset_end: ... [239](#), [27208](#), [27886](#)
- \hbox_gset_to_wd:Nnn [239](#), [27196](#)
- \hbox_gset_to_wd:Nnw [239](#), [27228](#)
- \hbox_overlap_left:n [239](#), [27252](#)
- \hbox_overlap_right:n ... [239](#), [27252](#)
- \hbox_set:Nn [239](#), [239](#), [27184](#),
[27371](#), [27403](#), [27404](#), [27491](#), [27538](#),
[27558](#), [27565](#), [27578](#), [27595](#), [27616](#),
[27645](#), [27653](#), [27676](#), [27804](#), [28241](#),
[28264](#), [28523](#), [28610](#), [28905](#), [31603](#),
[31616](#), [31624](#), [31632](#), [31641](#), [31650](#),
[31667](#), [31675](#), [31683](#), [31689](#), [31702](#)
- \hbox_set:Nw [239](#), [27208](#), [27870](#)
- \hbox_set_end: [239](#), [239](#), [27208](#), [27873](#)
- \hbox_set_to_wd:Nnn . [239](#), [239](#), [27196](#)
- \hbox_set_to_wd:Nnw [239](#), [27228](#)
- \hbox_to_wd:nn [239](#), [27242](#), [27694](#)
- \hbox_to_zero:n
..... [239](#), [27242](#), [27253](#), [27255](#)
- \hbox_unpack:N [239](#), [27256](#), [28527](#)
- \hbox_unpack_clear:N [32509](#)
- \hbox_unpack_drop:N
..... [242](#), [27256](#), [32509](#), [32511](#)
- hcoffin commands:
- \hcoffin_gset:Nn [246](#), [27800](#)
- \hcoffin_gset:Nw [247](#), [27866](#)
- \hcoffin_gset_end: [247](#), [27866](#)
- \hcoffin_set:Nn
..... [246](#), [27800](#), [28757](#), [28769](#), [28812](#), [28852](#)
- \hcoffin_set:Nw [247](#), [27866](#)
- \hcoffin_set_end: [247](#), [27866](#)
- \hfi [1219](#)
- \hfil [383](#)
- \hfill [384](#)
- \hfilneg [385](#)
- \hfuzz [386](#)
- \hjcode [923](#), [1798](#)
- \hoffset [387](#)
- \holdinginserts [388](#)
- \hpack [924](#), [1799](#)
- \hrule [389](#)
- \hsize [390](#)
- \hskip [391](#)
- \hss [392](#)
- \ht [393](#)
- \Huge [31211](#)
- \huge [31215](#)
- hundred commands:
- \c_one_hundred [32518](#)
- \hyphenation [394](#)
- \hyphenationbounds [925](#), [1800](#)
- \hyphenationmin [926](#), [1801](#)
- \hyphenchar [395](#)
- \hyphenpenalty [396](#)
- \hyphenpenaltymode [927](#), [1802](#)
- I**
- \I [196](#)
- \i [199](#), [30969](#),
[31290](#), [31416](#), [31418](#), [31420](#), [31422](#),
[31473](#), [31476](#), [31479](#), [31482](#), [31553](#)
- \if [397](#)
- if commands:
- \if:w
..... [23](#), [128](#), [332](#), [333](#), [369](#), [981](#), [2100](#),
[2457](#), [2752](#), [2753](#), [3608](#), [3611](#), [3612](#),
[3613](#), [3614](#), [3629](#), [3630](#), [3631](#), [3632](#),
[3633](#), [3634](#), [3635](#), [3636](#), [3637](#), [3701](#),
[3702](#), [3704](#), [9377](#), [11532](#), [17341](#),
[17716](#), [17720](#), [17742](#), [17835](#), [17867](#),
[17886](#), [17952](#), [17966](#), [17983](#), [18003](#),
[18510](#), [18525](#), [18865](#), [21068](#), [22575](#),
[24314](#), [29289](#), [29297](#), [29314](#), [29426](#)
- \if_bool:N
..... [112](#), [112](#), [530](#), [2110](#), [9569](#), [9614](#)
- \if_box_empty:N ... [245](#), [27120](#), [27132](#)
- \if_case:w . [100](#), [428](#), [429](#), [430](#), [466](#),
[521](#), [741](#), [829](#), [882](#), [924](#), [2660](#), [3299](#),
[5689](#), [5763](#), [5986](#), [7028](#), [8684](#), [9268](#),
[9301](#), [11058](#), [13570](#), [16630](#), [16883](#),
[16898](#), [17281](#), [17310](#), [18598](#), [18639](#),
[19301](#), [19436](#), [19511](#), [19536](#), [19588](#),
[20032](#), [20048](#), [20065](#), [20342](#), [20569](#),
[20596](#), [20754](#), [20789](#), [20947](#), [20992](#),
[21044](#), [21170](#), [21193](#), [21226](#), [21285](#),
[21325](#), [21340](#), [21355](#), [21370](#), [21385](#),
[21400](#), [21926](#), [21979](#), [22063](#), [22078](#),
[22130](#), [22143](#), [22227](#), [22281](#), [22355](#),
[22572](#), [22859](#), [22938](#), [23473](#), [23667](#),
[23964](#), [24228](#), [25029](#), [25058](#), [25115](#),
[25525](#), [25579](#), [25939](#), [26270](#), [32170](#)
- \if_catcode:w
..... [23](#), [401](#), [412](#), [413](#), [591](#), [2100](#),
[3748](#), [4669](#), [5022](#), [5066](#), [5078](#), [5095](#),
[11226](#), [11229](#), [11232](#), [11235](#), [11238](#),
[11241](#), [11244](#), [11314](#), [11319](#), [11324](#),
[11329](#), [11336](#), [11343](#), [11348](#), [11353](#),
[11358](#), [11363](#), [11368](#), [11378](#), [11405](#),
[11623](#), [11628](#), [11698](#), [11699](#), [17469](#),
[17676](#), [17993](#), [18040](#), [18343](#), [18387](#),
[23462](#), [23465](#), [23619](#), [23621](#), [23623](#),
[23625](#), [23627](#), [23629](#), [23631](#), [29390](#),
[29391](#), [29427](#), [29442](#), [29443](#), [29444](#),

- 29445, 29446, 29447, 29448, 29449,
29450, 29473, 29476, 29479, 29482,
29485, 29488, 29491, 32171, 32172
- `\if_charcode:w`
..... *23*, *128*, *411*, *412*, *433*, *591*,
957, *2100*, 5005, 5059, 5847, 5966,
6643, 11383, 11625, 14274, 14283,
16886, 18878, 19240, 23532, 23556,
23605, 24171, 24181, 24663, 26124
- `\if_cs_exist:N` *23*,
2115, 2484, 2512, 3248, 11413, 11541
- `\if_cs_exist:w` *23*, *2115*, 2143, 2493,
2521, 2647, 9517, 9545, 9554, 31714
- `\if_dim:w`
182, *14574*, 14664, 14676, 14699, 14870
- `\if_eof:w`
163, *635*, *13141*, 13148, 13231, 13249
- `\if_false:`
..... *23*, *106*, *359*, *391*, *396*, *400*,
409, *498*, *512*, *541*, *575*, *655*, *949*,
1038, *2100*, 3259, 3269, 3282, 3295,
3323, 3339, 3437, 3451, 3457, 3464,
3472, 3482, 3495, 3499, 4400, 4407,
4543, 4544, 4641, 4645, 4684, 4972,
4977, 4988, 5079, 5091, 5106, 5114,
8237, 8240, 8419, 8424, 8898, 9860,
9996, 10004, 11005, 11054, 13549,
13589, 13593, 13600, 13608, 13886,
13899, 14686, 23409, 23451, 23500,
23503, 24422, 24441, 24442, 24451,
24502, 24538, 24552, 24556, 24779,
24812, 24824, 24828, 24862, 24867,
24875, 24910, 24917, 24922, 24970,
25193, 25210, 25214, 26345, 26362,
26601, 26606, 26717, 26722, 29653,
29659, 32043, 32055, 32081, 32091
- `\if_hbox:N` *245*, *27120*, 27124
- `\if_int_compare:w`
..... *22*, *100*, *512*, *513*, *2133*,
3487, 5171, 5180, 5229, 5230, 5236,
5423, 5432, 5437, 5673, 5728, 5729,
5735, 5747, 5763, 5975, 5983, 6190,
6191, 6192, 6197, 6198, 6240, 6292,
6373, 6374, 6405, 6408, 6409, 6419,
6608, 6670, 6674, 6704, 6707, 6723,
6727, 6748, 6826, 6828, 6847, 6848,
6866, 6868, 6922, 6925, 6926, 7044,
7045, 7186, 7191, *8684*, 8739, 8780,
8781, 8878, 8931, 8933, 8935, 8937,
8939, 8941, 8943, 8946, 9079, 9860,
9862, 10934, 10935, 10942, 10943,
10944, 10945, 10950, 10951, 10993,
11073, 11074, 11080, 11523, 13556,
14290, 14715, 16354, 16358, 16402,
16468, 16631, 16632, 16826, 16923,
17161, 17171, 17179, 17192, 17205,
17212, 17233, 17245, 17254, 17265,
17374, 17379, 17451, 17481, 17636,
17638, 17675, 17680, 17733, 17753,
17780, 17794, 17829, 17856, 17884,
17900, 17916, 17934, 17993, 18013,
18029, 18042, 18056, 18117, 18140,
18169, 18171, 18344, 18354, 18356,
18388, 18398, 18400, 18422, 18439,
18444, 18474, 18542, 18587, 18889,
18936, 18939, 18970, 18979, 18982,
18987, 18988, 18991, 18994, 19181,
19305, 19326, 19363, 19458, 19512,
19513, 19516, 19519, 19589, 19598,
19803, 19876, 19929, 19933, 19937,
19955, 19990, 19991, 19992, 19993,
19994, 20020, 20344, 20347, 20441,
20534, 20582, 20598, 20725, 20759,
20817, 20826, 20866, 21037, 21039,
21050, 21068, 21091, 21123, 21126,
21173, 21203, 21250, 21264, 21428,
21472, 21930, 21968, 21977, 22013,
22097, 22100, 22329, 22562, 22630,
22631, 22632, 22642, 22670, 22675,
22676, 22739, 22740, 22741, 22745,
22760, 22765, 22813, 22817, 22987,
23056, 23085, 23126, 23137, 23140,
23158, 23213, 23223, 23233, 23437,
23509, 23542, 23550, 23573, 23597,
23648, 23663, 23745, 23748, 23902,
23908, 23909, 23916, 23919, 23922,
23928, 23929, 23933, 23936, 23937,
23945, 23946, 23947, 23953, 23983,
23984, 24225, 24245, 24246, 24247,
24250, 24254, 24255, 24258, 24259,
24267, 24268, 24271, 24275, 24276,
24279, 24338, 24360, 24372, 24381,
24389, 24392, 24402, 24405, 24433,
24506, 24611, 24677, 24682, 24710,
24777, 24810, 24921, 24938, 25224,
25257, 25472, 25543, 25569, 25631,
25644, 25655, 25671, 25722, 25754,
25917, 25918, 25965, 25992, 26067,
26135, 26198, 26208, 26211, 26231,
26288, 26341, 26358, 26381, 26530,
26559, 26599, 26604, 26625, 26703,
26715, 26720, 29290, 29459, 30376,
30379, 30380, 30383, 32124, 32132
- `\if_int_odd:w` *101*,
901, *8684*, 8813, 8984, 8992, 9492,
10941, 10949, 10968, 11697, 17183,
17230, 17242, 18635, 19572, 19858,
21214, 21778, 21817, 21827, 21870,

- 21894, 22054, 22738, 23673, 23973,
24349, 24357, 24369, 24783, 25098
- `\if_meaning:w`
 23, 381, 397, 398, 412, 813, 1119,
 2100, 2311, 2337, 2355, 2414, 2419,
 2428, 2481, 2499, 2509, 2527, 2678,
 2692, 2813, 2909, 2972, 2973, 3300,
 3303, 3304, 3305, 3306, 3399, 3429,
 3442, 3448, 3556, 3579, 3588, 3780,
 3853, 3865, 3866, 3974, 3980, 4006,
 4018, 4026, 4058, 4065, 4089, 4093,
 4171, 4196, 4211, 4576, 4586, 4597,
 4610, 4625, 4917, 4981, 5050, 5532,
 5600, 5623, 5784, 5822, 6136, 6876,
 7025, 7040, 7067, 7182, 8273, 8336,
 8351, 8359, 8707, 8710, 8720, 8755,
 8760, 8761, 8913, 9668, 9690, 10360,
 10375, 10397, 10411, 11373, 11410,
 11448, 11451, 11515, 11577, 11616,
 11700, 12003, 13506, 14645, 14692,
 14873, 16612, 16633, 16645, 16655,
 16750, 16805, 16814, 16905, 16920,
 16922, 17072, 17160, 17170, 17182,
 17195, 17196, 17215, 17216, 17230,
 17231, 17242, 17243, 17309, 17356,
 17391, 17394, 17410, 17417, 17470,
 17473, 17591, 17592, 17593, 17594,
 17597, 17693, 17806, 17812, 18041,
 18089, 18300, 18373, 18636, 18654,
 18704, 18714, 18925, 18926, 18927,
 18928, 18929, 18930, 19162, 19174,
 19175, 19203, 19215, 19222, 19239,
 19302, 19337, 19351, 19397, 19404,
 19480, 19492, 19592, 19595, 19606,
 19659, 19732, 19802, 19805, 19812,
 19845, 19846, 19849, 20070, 20315,
 20326, 20507, 20517, 20566, 20665,
 20745, 20794, 20808, 20955, 20989,
 21001, 21014, 21017, 21020, 21023,
 21049, 21150, 21154, 21213, 21230,
 21236, 21820, 21873, 21924, 21925,
 21927, 21928, 21948, 21965, 22032,
 22130, 22226, 22280, 22354, 22424,
 22429, 22561, 22593, 22604, 22711,
 22872, 22925, 22931, 22998, 22999,
 23459, 23489, 23517, 23617, 24013,
 24313, 24337, 24659, 24662, 25105,
 25507, 25679, 25690, 25705, 25860,
 25893, 26243, 26481, 26558, 26611,
 26650, 29266, 29268, 29279, 29405,
 31593, 32048, 32085, 32104, 32173
- `\if_mode_horizontal:` . 23, 2111, 9854
- `\if_mode_inner:` 23, 2111, 9856
- `\if_mode_math:` 23, 2111, 9858
- `\if_mode_vertical:` 23, 2111, 2919, 9852
- `\if_predicate:w` 104, 106, 112, 9569,
 9646, 9706, 9721, 9732, 9747, 9758
- `\if_true:` 23, 106, 398, 2100
- `\if_vbox:N` 245, 27120, 27126
- `\ifabsdim` 1014, 1676
- `\ifabsnum` 1015, 1677
- `\ifcase` 398
- `\ifcat` 399
- `\ifcondition` 929
- `\ifcsname` 637, 1508
- `\ifdbbox` 1220, 2050
- `\ifddir` 1221, 2051
- `\ifdefined` 159, 638, 1509
- `\ifdim` 400
- `\ifeof` 401
- `\iffalse` 402
- `\iffontchar` 639, 1510
- `\ifhbox` 403
- `\ifhmode` 404
- `\ifincsname` 790, 1659
- `\ifinner` 405
- `\ifjfont` 1222
- `\ifmbox` 1223
- `\ifmdir` 1224, 2052
- `\ifmmode` 406
- `\ifnum` ... 45, 54, 83, 96, 101, 165, 180, 407
- `\ifodd` 408
- `\ifpdfabsdim` 746, 1618
- `\ifpdfabsnum` 747, 1619
- `\ifpdfprimitive` 748, 1620
- `\ifprimitive` 881, 1669
- `\iftbox` 1225, 2053
- `\iftdir` 1227, 2054
- `\iftfont` 1226
- `\iftrue` 409, 31593
- `\ifvbox` 410
- `\ifvmode` 411
- `\ifvoid` 412
- `\ifx` 14, 21, 39, 43,
 49, 84, 86, 87, 88, 99, 124, 146, 147, 413
- `\ifybox` 1228, 2055
- `\ifydir` 1229, 2056
- `\ignoreligaturesinfont` 1016, 1678
- `\ignorespaces` 414
- `\IJ` 29529, 30960, 31280
- `\ij` 29529, 30960, 31292
- `\immediate` 415
- `\immediateassigned` 930
- `\immediateassignment` 931
- `in` 216
- `\indent` 416
- `inf` 215
- `\infty` 17594, 17595

- inherit commands:
- .inherit:n [186](#), [15728](#)
 - \inhibitglue [1230](#), [2057](#)
 - \inhibitxspcode [1231](#), [2058](#)
 - \initcatcodetable [932](#), [1804](#)
- initial commands:
- .initial:n [187](#), [15730](#)
 - \input [50](#), [160](#), [161](#), [417](#)
 - \inputlineno [418](#)
 - \insert [419](#)
 - \insertht [1017](#), [1680](#)
 - \insertpenalties [420](#)
- int commands:
- \c_eight [32518](#)
 - \c_eleven [32518](#)
 - \c_fifteen [32518](#)
 - \c_five [32518](#)
 - \l_foo_int [230](#)
 - \c_four [32518](#)
 - \c_fourteen [32518](#)
 - \int_abs:n [89](#), [506](#), [8713](#), [16402](#)
 - \int_add:Nn [90](#), [8843](#), [13665](#), [23954](#),
[25100](#), [25661](#), [25662](#), [25902](#), [25989](#)
 - \int_case:nn [93](#), [521](#),
[8952](#), [9131](#), [9137](#), [30410](#), [30425](#), [30488](#)
 - \int_case:nnn [32360](#)
 - \int_case:nnTF
..... [93](#), [8598](#), [8952](#), [8957](#), [8962](#),
[10673](#), [17501](#), [22176](#), [27001](#), [32361](#)
 - \int_compare:nNnTF [91](#), [91](#),
[92](#), [93](#), [93](#), [94](#), [94](#), [202](#), [4402](#), [4430](#),
[4445](#), [4453](#), [5126](#), [5133](#), [5200](#), [5652](#),
[5654](#), [5663](#), [8288](#), [8477](#), [8484](#), [8794](#),
[8800](#), [8944](#), [8976](#), [9028](#), [9036](#), [9045](#),
[9051](#), [9063](#), [9066](#), [9127](#), [9215](#), [9221](#),
[9227](#), [9247](#), [9401](#), [9420](#), [9422](#), [9464](#),
[10150](#), [10712](#), [10714](#), [10719](#), [10728](#),
[10748](#), [10765](#), [11192](#), [11276](#), [13273](#),
[13365](#), [13478](#), [13982](#), [14127](#), [14137](#),
[14894](#), [16339](#), [16344](#), [16351](#), [16460](#),
[16502](#), [16528](#), [18954](#), [20095](#), [22159](#),
[22304](#), [22306](#), [22793](#), [22974](#), [23792](#),
[23991](#), [24003](#), [24157](#), [24475](#), [24477](#),
[25270](#), [25863](#), [26085](#), [26100](#), [26300](#),
[26575](#), [27018](#), [30147](#), [30225](#), [30227](#),
[30230](#), [30271](#), [30284](#), [30293](#), [30334](#),
[30356](#), [30366](#), [30564](#), [30567](#), [30607](#),
[30613](#), [30620](#), [30634](#), [31832](#), [32203](#),
[32205](#), [32206](#), [32207](#), [32209](#), [32232](#)
 - \int_compare:nTF
..... [91](#), [92](#), [94](#), [94](#), [94](#), [94](#), [203](#),
[674](#), [8891](#), [9000](#), [9008](#), [9017](#), [9023](#),
[13119](#), [13146](#), [13335](#), [22364](#), [25374](#),
[26758](#), [26980](#), [26981](#), [26986](#), [26988](#)
 - \int_compare_p:n [92](#), [8891](#), [25381](#)
 - \int_compare_p:nNn [22](#), [91](#),
[8944](#), [10066](#), [10129](#), [10131](#), [10133](#),
[13261](#), [14116](#), [14117](#), [25169](#), [25170](#),
[30342](#), [30343](#), [30344](#), [30345](#), [30346](#),
[30347](#), [30348](#), [30349](#), [30350](#), [30351](#),
[30352](#), [30468](#), [30469](#), [30470](#), [30518](#),
[30526](#), [30527](#), [30548](#), [30549](#), [30591](#)
 - \int_const:Nn [90](#), [1191](#), [5928](#), [5929](#),
[8792](#), [9430](#), [9431](#), [9432](#), [9433](#), [9434](#),
[9435](#), [9436](#), [9437](#), [9438](#), [9439](#), [9440](#),
[9441](#), [9442](#), [9443](#), [9488](#), [9489](#), [9490](#),
[10016](#), [10076](#), [10078](#), [10080](#), [10081](#),
[10082](#), [10116](#), [13037](#), [13191](#), [13256](#),
[13257](#), [16593](#), [16594](#), [16595](#), [16596](#),
[16597](#), [16598](#), [16599](#), [16783](#), [16784](#),
[16785](#), [16787](#), [16788](#), [16789](#), [16792](#),
[16793](#), [16794](#), [17155](#), [17429](#), [17430](#),
[17431](#), [17432](#), [17433](#), [17434](#), [17435](#),
[17436](#), [17437](#), [17438](#), [17439](#), [17440](#),
[17441](#), [17442](#), [17443](#), [21223](#), [22512](#),
[23040](#), [23881](#), [23882](#), [23883](#), [23884](#),
[24286](#), [24287](#), [24288](#), [24289](#), [24290](#),
[24291](#), [24295](#), [24296](#), [24297](#), [24298](#),
[24299](#), [24300](#), [24301](#), [24302](#), [24303](#),
[24304](#), [24305](#), [24306](#), [24307](#), [32547](#)
 - \int_decr:N [90](#),
[8855](#), [23146](#), [23147](#), [23148](#), [23211](#),
[23212](#), [23221](#), [23222](#), [23231](#), [23232](#),
[23452](#), [25941](#), [26290](#), [26359](#), [26560](#)
 - \int_div_round:nn [89](#), [8745](#)
 - \int_div_truncate:nn [89](#), [89](#),
[6031](#), [6036](#), [6697](#), [6698](#), [6753](#), [6933](#),
[7099](#), [7110](#), [8745](#), [9142](#), [9240](#), [9260](#),
[10079](#), [11086](#), [11099](#), [11104](#), [11116](#)
 - \int_do_until:nn [94](#), [8998](#)
 - \int_do_until:nNnn [93](#), [9026](#)
 - \int_do_while:nn [94](#), [8998](#)
 - \int_do_while:nNnn [93](#), [9026](#)
 - \int_eval:n [14](#),
[28](#), [88](#), [89](#), [89](#), [89](#), [91](#), [91](#), [92](#), [93](#),
[100](#), [100](#), [263](#), [314](#), [340](#), [405](#), [508](#),
[524](#), [722](#), [724](#), [727](#), [759](#), [806](#), [830](#)–
[832](#), [965](#), [1170](#), [2660](#), [2689](#), [2705](#),
[4456](#), [4802](#), [4807](#), [4815](#), [5119](#), [5127](#),
[5135](#), [5162](#), [5166](#), [5175](#), [5182](#), [5217](#),
[5227](#), [5646](#), [5659](#), [5684](#), [5708](#), [5709](#),
[5721](#), [5726](#), [5757](#), [5774](#), [5811](#), [5986](#),
[6006](#), [6024](#), [6317](#), [6837](#), [6852](#), [6880](#),
[7029](#), [7034](#), [7052](#), [7196](#), [8470](#), [8478](#),
[8486](#), [8572](#), [8696](#), [8955](#), [8960](#), [8965](#),
[8970](#), [9124](#), [9210](#), [9212](#), [9342](#), [9352](#),
[9387](#), [9398](#), [9404](#), [9415](#), [9446](#), [9483](#),
[9487](#), [9807](#), [10104](#), [10646](#), [10655](#),

- 10706, 10716, 10730, 10737, 10752,
 10806, 10808, 10876, 10878, 10882,
 10884, 10888, 10890, 10894, 10896,
 10929, 10930, 11069, 11121, 11124,
 11129, 11135, 11909, 12843, 13102,
 13319, 13601, 13659, 14108, 14109,
 14131, 14141, 14148, 14149, 14161,
 14162, 16338, 16377, 16378, 16429,
 16446, 16498, 16522, 16531, 16535,
 16603, 22501, 22661, 22664, 22665,
 22755, 22756, 22788, 22836, 22898,
 22906, 23088, 23354, 23355, 23575,
 23651, 23655, 23678, 23973, 24229,
 25098, 25304, 25308, 25311, 25315,
 25492, 25494, 25508, 25509, 25511,
 25512, 25655, 25745, 25776, 25960,
 26008, 26083, 26210, 26215, 26762,
 26807, 26808, 27007, 27150, 27160,
 31835, 32126, 32134, 32233, 32234
 \int_eval:w 89, 314, 318,
 318, 5677, 6018, 8696, 9520, 9555,
 13552, 13561, 13586, 13598, 16473,
 20044, 23402, 23637, 23647, 31925
 \int_from_alph:n 97, 9385
 \int_from_base:nn
 98, 9402, 9425, 9427, 9429
 \int_from_bin:n 98, 9424, 32363
 \int_from_binary:n 32362
 \int_from_hex:n 98, 9424, 32365
 \int_from_hexadecimal:n 32364
 \int_from_oct:n 98, 9424, 32367
 \int_from_octal:n 32366
 \int_from_roman:n 98, 9444
 \int_gadd:Nn 90, 8843
 \int_gdecr:N 90, 4748, 5551,
 8535, 8855, 9122, 10607, 12048,
 13226, 14858, 19146, 23717, 31907
 \int_gincr:N 90, 4741,
 5540, 8527, 8855, 9097, 9108, 10600,
 12043, 13217, 14837, 14844, 16329,
 19125, 19132, 22783, 23695, 31901
 .int_gset:N 187, 15738
 \int_gset:Nn 91, 508, 8867, 12264
 \int_gset_eq:NN 90, 8835
 \int_gsub:Nn 91, 8843, 22797
 \int_gzero:N 90, 8825, 8832
 \int_gzero_new:N 90, 8829
 \int_if_even:nTF 93, 8982, 13838
 \int_if_even_p:n 93, 8982
 \int_if_exist:NTF 90, 8830,
 8832, 8839, 9458, 9462, 25024, 25079
 \int_if_exist_p:N 90, 8839
 \int_if_odd:nTF 93, 8982, 20430
 \int_if_odd_p:n 93, 8982, 25418
 \int_incr:N 90, 6357, 6367,
 6400, 8310, 8855, 15486, 16418,
 16452, 16544, 22886, 23060, 23156,
 23157, 23493, 23535, 23548, 23566,
 23838, 23839, 24915, 25339, 25500,
 25590, 25903, 25938, 25940, 26015,
 26277, 26342, 26501, 26557, 26621
 \int_log:N 99, 9484
 \int_log:n 99, 9486
 \int_max:nn .. 89, 919, 8713, 20291,
 21452, 25614, 25824, 26707, 26708
 \int_min:nn 89, 922, 8713
 \int_mod:nn .. 89, 6698, 6699, 6934,
 8745, 9132, 9231, 9251, 10077, 11118
 \int_new:N
 .. 89, 90, 5926, 8784, 8796, 8802,
 8830, 8832, 9500, 9501, 9502, 9503,
 9504, 9505, 9863, 13387, 13390,
 13392, 13405, 15290, 16321, 16323,
 22776, 22777, 22953, 22954, 22955,
 22956, 22957, 22958, 22959, 22960,
 22961, 22962, 22963, 23388, 23389,
 23390, 23391, 23864, 23865, 23866,
 23879, 24284, 24285, 24292, 24293,
 24310, 25435, 25437, 25438, 25439,
 25442, 25782, 25783, 25784, 25785,
 25786, 25787, 25788, 25789, 25790,
 25791, 25794, 25795, 25796, 26045,
 26470, 26473, 26474, 26475, 27022
 \int_rand:n
 . 98, 262, 16439, 22503, 22506, 22753
 \int_rand:nn 98, 115, 262, 921, 922,
 929, 1172, 5142, 8492, 9488, 10766,
 10771, 22497, 22500, 22659, 31825
 \int_range:nn 923
 .int_set:N 187, 15738
 \int_set:Nn 91, 314,
 2865, 4403, 4438, 6223, 6475, 6524,
 6577, 8311, 8867, 13177, 13179,
 13371, 13373, 13388, 13398, 13411,
 13458, 13464, 13476, 13481, 15491,
 22968, 22970, 22972, 22995, 22996,
 23011, 23019, 23020, 23032, 23033,
 23044, 23045, 23046, 23062, 23065,
 23447, 23510, 23826, 25106, 25436,
 25487, 25489, 25558, 25610, 25611,
 25621, 25632, 25656, 25674, 25723,
 25809, 25822, 25853, 25874, 25964,
 25999, 26506, 26654, 26680, 27159,
 27161, 27169, 27170, 27171, 27172
 \int_set_eq:NN ... 90, 4401, 4404,
 8835, 9997, 13888, 23012, 23053,
 23944, 24403, 24407, 24416, 24418,
 24461, 24514, 24814, 24914, 24927,

- 25026, 25452, 25463, 25464, 25498,
 25499, 25549, 25653, 25654, 25706,
 25761, 25811, 25814, 25829, 25836,
 25850, 25852, 25855, 25869, 25872,
 25904, 25905, 25909, 26039, 26612
 \int_show:N 99, 9480
 \int_show:n 99, 526, 1170, 9482
 \int_sign:n 89, 679, 8699
 \int_step_... 232
 \int_step_function:nN 95, 8301, 9054
 \int_step_function:nnN
 95, 9054, 11041, 11046,
 11049, 13270, 23115, 25910, 26571
 \int_step_function:nnnN . 95, 266,
 266, 517, 810, 9054, 9121, 26683, 26691
 \int_step_inline:nn
 95, 723, 9091, 16332
 \int_step_inline:nnn
 . 95, 9091, 13046, 13279, 25844, 27025
 \int_step_inline:nnnn . 95, 811, 9091
 \int_step_variable:nNn 95, 9091
 \int_step_variable:nnNn 95, 9091
 \int_step_variable:nnnNn ... 95, 9091
 \int_sub:Nn 91, 8843, 12207, 13673,
 23948, 24618, 25709, 25717, 25726
 \int_to_Alph:n 96, 97, 9145
 \int_to_alpha:n 96, 96, 97, 9145
 \int_to_arabic:n 96, 9124
 \int_to_Base:n 97
 \int_to_base:n 97
 \int_to_Base:nn ... 97, 98, 9209, 9336
 \int_to_base:nn
 97, 98, 9209, 9332, 9334, 9338
 \int_to_bin:n . 97, 97, 98, 9331, 32369
 \int_to_binary:n 32368
 \int_to_Hex:n 97, 98, 9331, 24160
 \int_to_hex:n 97, 98, 9331, 32371
 \int_to_hexadecimal:n 32370
 \int_to_oct:n 97, 98, 9331, 32373
 \int_to_octal:n 32372
 \int_to_Roman:n 97, 98, 9339
 \int_to_roman:n 97, 98, 9339
 \int_to_symbols:nnn
 96, 96, 9125, 9147, 9179
 \int_until_do:nn 94, 8998
 \int_until_do:nNnn 94, 9026
 \int_use:N 88, 91, 753, 758,
 4743, 4745, 5542, 5546, 6366, 6833,
 6857, 6871, 6891, 6898, 7080, 7189,
 7194, 7210, 8528, 8534, 8873, 9100,
 9111, 10602, 10604, 12042, 12050,
 12167, 12738, 12845, 13180, 13219,
 13367, 14840, 14847, 15492, 19128,
 19135, 23697, 24435, 24508, 24579,
 24590, 24599, 24603, 24614, 24615,
 24621, 24622, 24628, 24629, 24797,
 25418, 25480, 25482, 25588, 25601,
 25602, 26000, 26030, 26137, 26149,
 26245, 26506, 27019, 31903, 31905,
 31934, 31943, 31945, 31948, 31953,
 31962, 31964, 31968, 31971, 31976
 \int_value:w
 100, 318, 318, 364, 506, 512,
 535, 674, 722, 724, 732, 737, 741,
 753, 760, 767, 770, 775, 782, 807,
 808, 817, 825, 833, 896, 901, 914,
 949, 1172, 2462, 3449, 3451, 5175,
 5182, 5646, 5647, 5659, 5677, 5684,
 5707, 5708, 5709, 5721, 5757, 6270,
 6356, 6378, 6753, 6829, 6837, 6852,
 6880, 8684, 8697, 8698, 8701, 8702,
 8715, 8716, 8723, 8724, 8725, 8731,
 8732, 8733, 8747, 8749, 8750, 8767,
 8770, 8771, 8772, 8779, 8894, 8898,
 8928, 9057, 9058, 9059, 9085, 9295,
 9328, 9520, 9555, 9565, 9681, 9684,
 9807, 10092, 10929, 10930, 13552,
 13561, 14673, 14864, 14901, 16348,
 16351, 16377, 16378, 16424, 16429,
 16473, 16677, 16678, 16679, 16680,
 16681, 16695, 16843, 16904, 16922,
 17229, 17359, 17373, 17375, 17377,
 17380, 17416, 17556, 17586, 17587,
 17624, 17632, 17763, 17768, 17770,
 17779, 17783, 17820, 17828, 17831,
 17837, 17848, 17859, 17865, 17866,
 17869, 17912, 17922, 17924, 17940,
 17942, 17965, 17979, 18057, 18059,
 18133, 18221, 18924, 18957, 19312,
 19313, 19314, 19316, 19362, 19365,
 19368, 19391, 19393, 19414, 19416,
 19425, 19427, 19431, 19449, 19456,
 19462, 19472, 19474, 19488, 19496,
 19504, 19548, 19550, 19566, 19568,
 19571, 19574, 19628, 19636, 19638,
 19640, 19642, 19645, 19648, 19650,
 19669, 19671, 19675, 19681, 19683,
 19687, 19709, 19712, 19720, 19722,
 19725, 19726, 19727, 19728, 19743,
 19746, 19749, 19752, 19761, 19764,
 19767, 19770, 19777, 19779, 19785,
 19793, 19795, 19797, 19823, 19825,
 19834, 19836, 19840, 19857, 19878,
 19882, 19894, 19897, 19900, 19903,
 19906, 19909, 19912, 19915, 19919,
 19931, 19935, 19939, 19942, 19963,
 19965, 19967, 19977, 20001, 20004,
 20016, 20018, 20024, 20027, 20044,

- 20064, 20114, 20119, 20121, 20128,
20131, 20134, 20137, 20140, 20143,
20152, 20164, 20172, 20174, 20184,
20186, 20193, 20202, 20204, 20207,
20210, 20213, 20216, 20229, 20231,
20239, 20241, 20249, 20251, 20261,
20264, 20267, 20274, 20289, 20307,
20310, 20366, 20380, 20382, 20388,
20401, 20403, 20405, 20429, 20445,
20452, 20453, 20497, 20499, 20500,
20501, 20542, 20544, 20581, 20588,
20595, 20616, 20618, 20620, 20622,
20635, 20639, 20640, 20641, 20642,
20643, 20648, 20653, 20655, 20661,
20678, 20679, 20680, 20681, 20682,
20683, 20688, 20690, 20692, 20694,
20696, 20701, 20703, 20705, 20707,
20709, 20711, 20733, 20741, 20757,
20762, 20766, 20825, 20874, 20942,
20951, 20959, 20970, 20972, 20975,
20978, 21067, 21103, 21105, 21108,
21111, 21114, 21117, 21124, 21127,
21129, 21133, 21155, 21157, 21189,
21259, 21269, 21274, 21284, 21426,
21458, 21467, 21699, 21700, 21711,
21714, 21717, 21720, 21723, 21726,
21729, 21732, 21735, 21753, 21763,
21772, 21790, 21799, 21806, 21816,
21860, 21869, 21904, 21947, 21964,
22020, 22031, 22042, 22252, 22328,
22375, 22420, 22428, 22430, 22432,
22524, 22547, 22601, 22641, 22653,
22664, 22665, 22695, 22698, 22701,
22703, 22705, 22712, 22715, 22723,
22728, 22733, 22836, 22898, 22906,
22919, 22920, 22921, 22931, 23088,
23402, 23414, 23593, 23635, 23637,
23647, 23655, 23674, 23676, 23684,
24153, 24647, 24653, 24685, 24687,
24696, 24697, 24821, 25246, 25261,
26061, 26062, 26073, 26595, 26626,
26628, 29309, 29441, 31825, 31835,
31913, 31925, 32126, 32134, 32564
\int_while_do:nn 94, 8998
\int_while_do:nNnn 94, 9026
\int_zero:N 90,
 90, 6337, 6383, 8295, 8825, 8830,
 13518, 15483, 16415, 16444, 16541,
 22883, 23448, 23449, 23450, 23549,
 24415, 24616, 25063, 25371, 25451,
 25808, 25821, 25851, 26120, 26500
\int_zero_new:N 90, 8829
\c_max_int 99, 196,
 726, 922, 970, 1021, 9489, 22706,
 23919, 23933, 25905, 27147, 27153
\c_nine 32518
\c_one 32518
\c_one_int 99,
 8856, 8858, 8860, 8862, 9488, 16473
\c_seven 32518
\c_six 32518
\c_sixteen 32518
\c_ten 32518
\c_thirteen 32518
\c_three 32518
\g_tmpa_int 99, 9500
\l_tmpa_int 2, 99, 225, 9500
\g_tmpb_int 99, 9500
\l_tmpb_int 2, 99, 9500
\c_twelve 32518
\c_two 32518
\c_zero 1191, 32518
\c_zero_int 99, 322,
 333, 333, 405, 2152, 2460, 2462,
 4401, 8780, 8781, 8794, 8825, 8826,
 8878, 8886, 9063, 9066, 9488, 9860,
 9862, 9997, 10095, 13888, 14715,
 16333, 16460, 22547, 22676, 22740
int internal commands:
__int_abs:N 8713
__int_case:nnTF 8952
__int_case:nw 8952
__int_case_end:nw 8952
__int_compare:nnN 513, 8891
__int_compare:NNw ... 512, 513, 8891
__int_compare:Nw . 511, 512, 513, 8891
__int_compare:w 512, 8891
__int_compare_!=:NNw 8891
__int_compare_<:NNw 8891
__int_compare_<=:NNw 8891
__int_compare_=:NNw 8891
__int_compare_==:NNw 8891
__int_compare_>:NNw 8891
__int_compare_>=:NNw 8891
__int_compare_end=:NNw .. 513, 8891
__int_compare_error:
 511, 512, 8876, 8894, 8896
__int_compare_error:Nw
 511, 512, 513, 8876, 8916
__int_constdef:Nw . 1191, 8792, 32560
__int_deprecated_constants:Nn ..
 32544, 32549
__int_deprecated_constants:nn 32518
__int_div_truncate:NwNw 8745
__int_eval:w
 314, 506, 507, 512, 8684,
 8697, 8698, 8702, 8716, 8724, 8725,
 8732, 8733, 8747, 8749, 8750, 8767,

8770, 8771, 8772, 8779, 8810, 8844, 8846, 8848, 8850, 8868, 8870, 8894, 8928, 8946, 8984, 8992, 9057, 9058, 9059, 9085, 9268, 9295, 9301, 9328	
__int_eval_end:	
8684, 8697, 8702, 8716, 8751, 8767, 8773, 8782, 8810, 8844, 8846, 8848, 8850, 8868, 8870, 8946, 8984, 8992, 9268, 9295, 9301, 9328	
__int_from_alph:N	524, 9385
__int_from_alph:nN	524, 9385
__int_from_base:N	524, 9402
__int_from_base:nnN	524, 9402
__int_from_roman:NN	9444
\c__int_from_roman_C_int	9430
\c__int_from_roman_c_int	9430
\c__int_from_roman_D_int	9430
\c__int_from_roman_d_int	9430
__int_from_roman_error:w	9444
\c__int_from_roman_I_int	9430
\c__int_from_roman_i_int	9430
\c__int_from_roman_L_int	9430
\c__int_from_roman_l_int	9430
\c__int_from_roman_M_int	9430
\c__int_from_roman_m_int	9430
\c__int_from_roman_V_int	9430
\c__int_from_roman_v_int	9430
\c__int_from_roman_X_int	9430
\c__int_from_roman_x_int	9430
__int_if_recursion_tail_stop:N	8694, 9457
__int_if_recursion_tail_stop- do:Nn	8694, 9396, 9413, 9460
\l__int_internal_a_int	9504
\l__int_internal_b_int	9504
\c__int_max_constdef_int	8792
__int_maxmin:wwN	8713
__int_mod:ww	8745
__int_pass_signs:wn	
523, 9375, 9389, 9406	
__int_pass_signs_end:wn	9375
__int_show:nN	9480
__int_sign:Nw	8699
__int_step:NNnnnn	9091
__int_step:NwnnN	9054
__int_step:wwwN	9054
__int_to_Base:nn	9209
__int_to_base:nn	9209
__int_to_base:nnN	9209
__int_to_base:nnnN	9209
__int_to_base:nnnnN	9209
__int_to_Letter:n	9209
__int_to_letter:n	9209
__int_to_roman:N	9339
__int_to_roman:w	
512, 522, 2133, 8684, 8904, 9342, 9352	
__int_to_Roman_aux:N	9351, 9354, 9357
__int_to_roman_c:w	9339
__int_to_roman_c:w	9339
__int_to_Roman_d:w	9339
__int_to_roman_d:w	9339
__int_to_Roman_i:w	9339
__int_to_roman_i:w	9339
__int_to_Roman_l:w	9339
__int_to_roman_l:w	9339
__int_to_Roman_m:w	9339
__int_to_roman_m:w	9339
__int_to_Roman_Q:w	9339
__int_to_roman_Q:w	9339
__int_to_Roman_v:w	9339
__int_to_roman_v:w	9339
__int_to_Roman_x:w	9339
__int_to_roman_x:w	9339
__int_to_symbols:nnnn	9125
__int_use_none_delimit_by_s- stop:w	8691, 8926
__int_value:w	32564
intarray commands:	
\intarray_const_from_clist:Nn	
196, 16441, 20880, 21482	
\intarray_count:N	
196, 196, 197, 16339, 16342, 16344, 16345, 16348, 16358, 16369, 16416, 16439, 16460, 16485, 16542, 22808	
\intarray_gset:Nnn 196, 722, 724, 16371	
\intarray_gset_rand:Nn	262, 16490
\intarray_gset_rand:Nnn	262, 16490
\intarray_gzero:N	196, 16413
\intarray_item:Nn	
197, 722, 724, 16423, 16439	
\intarray_log:N	197, 16475
\intarray_new:Nn	
196, 721, 724, 16326, 22800, 22801, 22802, 23876, 23877, 23878, 25797, 25798, 26476, 26477, 26478	
\intarray_rand_item:N	197, 16438
\intarray_show:N	197, 725, 16475
\intarray_to_clist:N	262, 16456
intarray internal commands:	
__intarray_bounds:NNnTF	
16352, 16383, 16434	
__intarray_bounds_error:Nn	16352
__intarray_const_from_clist:nN	
16441	
__intarray_count:w	
16319, 16338, 16348, 16447, 16468	

- __intarray_entry:w 16319, 16372, 16419, 16424
- \g__intarray_font_int 16323, 16329, 16331
- __intarray_gset:Nnn 16371
- __intarray_gset:Nww .. 16375, 16381
- __intarray_gset_all_same:Nn . 16490
- __intarray_gset_overflow:Nnn . 16371
- __intarray_gset_overflow:NNnn .. 16395, 16403, 16407
- __intarray_gset_overflow_-
test:nw 724, 726, 16385,
16392, 16400, 16453, 16509, 16516
- __intarray_gset_rand:NNn 16490
- __intarray_gset_rand_auxi:NNnn . 16490
- __intarray_gset_rand_auxii:NNnn . 16490
- __intarray_gset_rand_auxiii:NNnn . 16490
- __intarray_item:Nn 16423
- __intarray_item:Nw ... 16427, 16432
- \l__intarray_loop_int ... 16321,
16415, 16418, 16419, 16444, 16447,
16452, 16454, 16541, 16544, 16545
- __intarray_new:N 16326, 16443
- __intarray_show:NN 16475, 16477, 16479
- __intarray_signed_max_dim:n ... 16350, 16410, 16411
- \c__intarray_sp_dim 16322, 16331, 16372
- __intarray_to_clist:Nn 16456, 16486
- __intarray_to_clist:w 16456
- \interactionmode 640, 1511
- \interlinepenalties 641, 1512
- \interlinepenalty 421
- ior commands:
 - \ior_close:N 156,
157, 157, 262, 13093, 13117, 14044,
14057, 29285, 29318, 29355, 29372
 - \ior_get:NN 157,
158, 158, 159, 159, 262, 13158, 13238
 - \ior_get:NNTF 158, 13158, 13159
 - \ior_get_str:NN 32374
 - \ior_get_term:nN 262, 13192
 - \ior_if_eof:N 635
 - \ior_if_eof:NNTF 160, 13142, 13164,
13184, 13224, 13243, 14054, 14068
 - \ior_if_eof_p:N 160, 13142
 - \ior_list_streams: 32376
 - \ior_log_list: 157, 13129, 32379
 - \ior_log_streams: 32378
 - \ior_map_break: 159, 13207, 13225,
13232, 13244, 13250, 29280, 29351
 - \ior_map_break:n 160, 13207
 - \ior_map_inline:Nn .. 159, 159, 13211
 - \ior_map_variable:NNn 159, 13237, 29277
 - \ior_new:N 156, 13060, 13062, 13063, 14073, 29213
 - \ior_open:Nn 156,
665, 13064, 29241, 29286, 29319, 29371
 - \ior_open:NnTF 157, 13065, 13068
 - \ior_shell_open:Nn 262, 31982
 - \ior_shell_open:nN 262
 - \ior_show_list: ... 157, 13129, 32377
 - \ior_str_get:NN 157, 158, 262, 13171, 13240, 32375
 - \ior_str_get:NNTF .. 158, 13171, 13172
 - \ior_str_get_term:nN 262, 13192
 - \ior_str_map_inline:Nn 159, 159, 13211, 29312, 29342
 - \ior_str_map_variable:NNn 159, 13237
 - \c_term_ior 32771
 - \g_tmpa_ior 163, 13062
 - \g_tmpb_ior 163, 13062
- ior internal commands:
 - \l__ior_file_name_tl 13067, 13070, 13072
 - __ior_get:NN ... 13158, 13193, 13212
 - __ior_get_term:NnN 13192
 - \l__ior_internal_tl 13036, 13230, 13234
 - __ior_list:N 13129
 - __ior_map_inline:NNn 13211
 - __ior_map_inline:NNNn 13211
 - __ior_map_inline_loop:NNN ... 13211
 - __ior_map_variable:NNNn 13237
 - __ior_map_variable_loop:NNNn . 13237
 - __ior_new:N 631, 13078, 13101
 - __ior_new_aux:N 13083, 13087
 - __ior_open_stream:Nn 13091
 - __ior_shell_open:nN 31982
 - __ior_str_get:NN 13171, 13195, 13214
 - \l__ior_stream_tl 13043, 13094, 13102, 13110
 - \g__ior_streams_prop 13044, 13111, 13122, 13136
 - \g__ior_streams_seq 13038, 13094, 13123, 13124
 - \c__ior_term_ior 13037,
13060, 13119, 13125, 13146, 13202
 - \c__ior_term_noprompt_ior 13191, 13201

iow commands:

\iow_allow_break:
 [162](#), [261](#), [13425](#), [13467](#), [13472](#)
 \iow_allow_break:n [642](#)
 \iow_char:N
 .. [161](#), [6453](#), [12746](#), [12748](#), [12749](#),
 [12781](#), [12875](#), [12921](#), [13386](#), [20986](#),
 [23341](#), [23344](#), [23345](#), [23370](#), [23371](#),
 [23378](#), [23379](#), [24139](#), [24141](#), [24143](#),
 [24145](#), [24147](#), [24149](#), [24753](#), [24754](#),
 [25295](#), [25408](#), [25409](#), [25410](#), [25431](#),
 [26730](#), [26733](#), [26734](#), [26739](#), [26773](#),
 [26782](#), [26786](#), [26791](#), [26811](#), [26813](#),
 [26814](#), [26816](#), [26819](#), [26821](#), [26828](#),
 [26832](#), [26835](#), [26836](#), [26839](#), [26841](#),
 [26845](#), [26847](#), [26853](#), [26855](#), [26859](#),
 [26861](#), [26865](#), [26870](#), [26872](#), [26914](#),
 [26916](#), [26921](#), [26923](#), [26929](#), [26934](#),
 [26939](#), [26943](#), [26953](#), [26956](#), [26960](#),
 [26961](#), [26965](#), [26973](#), [27030](#), [32454](#)
 \iow_close:N .. [157](#), [157](#), [13310](#), [13333](#)
 \iow_indent:n . [162](#), [162](#), [643](#), [644](#),
 [6451](#), [6776](#), [6962](#), [12692](#), [12795](#),
 [13436](#), [13468](#), [13473](#), [17104](#), [17116](#)
 \l_iow_line_count_int
 . [162](#), [162](#), [644](#), [963](#), [12207](#), [13387](#),
 [13477](#), [13482](#), [13520](#), [23794](#), [23798](#)
 \iow_list_streams: [32380](#)
 \iow_log:n [160](#), [2570](#), [5269](#),
 [12412](#), [12427](#), [12428](#), [12434](#), [13381](#),
 [32493](#), [32573](#), [32576](#), [32577](#), [32578](#)
 \iow_log_list: [157](#), [13345](#), [32383](#)
 \iow_log_streams: [32382](#)
 \iow_new:N ... [156](#), [13297](#), [13299](#), [13300](#)
 \iow_newline:
 [161](#), [161](#), [161](#), [162](#), [315](#),
 [417](#), [611](#), [640](#), [12229](#), [13385](#), [13465](#),
 [13474](#), [13480](#), [14458](#), [23744](#), [25342](#),
 [28933](#), [28934](#), [28935](#), [31757](#), [31759](#),
 [31762](#), [31769](#), [32610](#), [32626](#), [32628](#)
 \iow_now:Nn
 .. [160](#), [160](#), [160](#), [161](#), [161](#), [10027](#),
 [13375](#), [13381](#), [13382](#), [13383](#), [13384](#)
 \iow_open:Nn [157](#), [13306](#)
 \iow_shipout:Nn
 [161](#), [161](#), [161](#), [640](#), [10040](#), [13360](#)
 \iow_shipout_x:Nn
 [161](#), [161](#), [161](#), [640](#), [13357](#)
 \iow_show_list: ... [157](#), [13345](#), [32381](#)
 \iow_term:n
 ... [160](#), [262](#), [2570](#), [12241](#), [12390](#),
 [12405](#), [12406](#), [12460](#), [13381](#), [27020](#),
 [32580](#), [32583](#), [32584](#), [32585](#), [32624](#)

\iow_wrap:nnnN
 [161](#), [161](#), [162](#), [162](#), [162](#), [261](#),
 [417](#), [644](#), [1170](#), [5254](#), [5269](#), [12205](#),
 [12208](#), [12220](#), [12391](#), [12413](#), [12432](#),
 [12439](#), [13428](#), [13434](#), [13439](#), [13451](#),
 [13454](#), [32577](#), [32584](#), [32602](#), [32603](#)
 \c_log_iow
 [163](#), [636](#), [13256](#), [13335](#), [13381](#), [13382](#)
 \c_term_iow
 .. [163](#), [636](#), [13256](#), [13270](#), [13273](#),
 [13297](#), [13335](#), [13341](#), [13383](#), [13384](#)
 \g_tmpa_iow [163](#), [13299](#)
 \g_tmpb_iow [163](#), [13299](#)
 iow internal commands:
 __iow_allow_break: [642](#), [13425](#), [13467](#)
 __iow_allow_break_error:
 [642](#), [13425](#), [13472](#)
 \l__iow_file_name_tl
 [13305](#), [13308](#), [13312](#), [13320](#)
 __iow_indent:n ... [643](#), [13436](#), [13468](#)
 __iow_indent_error:n
 [643](#), [13436](#), [13473](#)
 \l__iow_indent_int [13404](#),
 [13518](#), [13536](#), [13648](#), [13665](#), [13673](#)
 \l__iow_indent_tl .. [13404](#), [13519](#),
 [13535](#), [13647](#), [13666](#), [13674](#), [13675](#)
 \l__iow_line_break_bool
 [13408](#), [13514](#), [13642](#), [13656](#), [13664](#),
 [13672](#), [13680](#), [13682](#), [13687](#), [13689](#)
 \l__iow_line_part_tl
 [646](#), [647](#), [648](#), [13406](#), [13516](#),
 [13528](#), [13549](#), [13607](#), [13610](#), [13641](#),
 [13655](#), [13657](#), [13663](#), [13671](#), [13694](#)
 \l__iow_line_target_int
 [649](#), [13390](#), [13476](#),
 [13478](#), [13481](#), [13643](#), [13648](#), [13683](#)
 \l__iow_line_tl [13406](#), [13515](#), [13532](#),
 [13622](#), [13638](#), [13654](#), [13655](#), [13663](#),
 [13671](#), [13693](#), [13694](#), [13699](#), [13701](#)
 __iow_list:N [13345](#)
 __iow_new:N [13301](#), [13318](#)
 \l__iow_newline_tl [13389](#),
 [13474](#), [13475](#), [13477](#), [13480](#), [13698](#)
 \l__iow_one_indent_int
 [13391](#), [13665](#), [13673](#)
 \l__iow_one_indent_tl
 [641](#), [13391](#), [13666](#)
 __iow_open_stream:Nn [13306](#)
 __iow_set_indent:n [641](#), [13391](#)
 \l__iow_stream_tl
 [13276](#), [13311](#), [13319](#), [13327](#)
 \g__iow_streams_prop
 [13277](#), [13328](#), [13338](#), [13352](#)

- \g__iow_streams_seq [13265](#), [13311](#), [13339](#), [13340](#)
 - __iow_tmp:w [647](#), [13522](#),
[13546](#), [13603](#), [13635](#), [13703](#), [13711](#)
 - __iow_unindent:w .. [641](#), [13391](#), [13675](#)
 - __iow_use_i_delimit_by_s_-
stop:nw [13295](#), [13507](#)
 - __iow_with:nNnn [13363](#)
 - __iow_wrap_allow_break:n [13652](#)
 - \c__iow_wrap_allow_break_marker_-
tl [13410](#), [13430](#)
 - __iow_wrap_break:w ... [13589](#), [13603](#)
 - __iow_wrap_break_end:w .. [647](#), [13603](#)
 - __iow_wrap_break_first:w [13603](#)
 - __iow_wrap_break_loop:w [13603](#)
 - __iow_wrap_break_none:w [13603](#)
 - __iow_wrap_chunk:nw [13520](#), [13522](#),
[13658](#), [13659](#), [13667](#), [13676](#), [13683](#)
 - __iow_wrap_do: [13484](#), [13489](#)
 - __iow_wrap_end:n [13678](#)
 - __iow_wrap_end_chunk:w
..... [645](#), [13540](#), [13547](#), [13639](#)
 - \c__iow_wrap_end_marker_tl
..... [13410](#), [13494](#)
 - __iow_wrap_fix_newline:w [13489](#)
 - __iow_wrap_indent:n [13661](#)
 - \c__iow_wrap_indent_marker_tl ...
..... [13410](#), [13444](#)
 - __iow_wrap_line:nw
[645](#), [648](#), [13534](#), [13538](#), [13547](#), [13646](#)
 - __iow_wrap_line_aux:Nw [13547](#)
 - __iow_wrap_line_end:NnnnnnnN [13547](#)
 - __iow_wrap_line_end:nw
.... [647](#), [13547](#), [13623](#), [13624](#), [13633](#)
 - __iow_wrap_line_loop:w [13547](#)
 - __iow_wrap_line_seven:nnnnnnn [13547](#)
 - \c__iow_wrap_marker_tl
..... [642](#), [645](#), [13410](#), [13546](#)
 - __iow_wrap_newline:n [13678](#)
 - \c__iow_wrap_newline_marker_tl ..
..... [644](#), [13410](#), [13509](#)
 - __iow_wrap_next:nw
..... [13522](#), [13601](#), [13643](#)
 - __iow_wrap_next_line:w [13595](#), [13636](#)
 - __iow_wrap_start:w [13489](#)
 - __iow_wrap_store_do:n
..... [13594](#), [13681](#), [13688](#), [13691](#)
 - \l__iow_wrap_tl
..... [644](#), [644](#), [649](#), [650](#), [13409](#),
[13471](#), [13486](#), [13491](#), [13493](#), [13496](#),
[13498](#), [13501](#), [13517](#), [13695](#), [13697](#)
 - __iow_wrap_trim:N
[650](#), [13624](#), [13655](#), [13681](#), [13688](#), [13703](#)
 - __iow_wrap_trim:w [13703](#)
 - __iow_wrap_trim_aux:w [13703](#)
 - __iow_wrap_unindent:n [13661](#)
 - \c__iow_wrap_unindent_marker_tl .
..... [13410](#), [13446](#)
 - \itshape [31206](#)
- ## J
- \J [198](#)
 - \j [30970](#), [31291](#), [31486](#), [31565](#)
 - \jcharwidowpenalty [1232](#), [2059](#)
 - \jfam [1233](#), [2060](#)
 - \jfont [1234](#), [2061](#)
 - \jis [1235](#), [2062](#)
 - job commands:
 - \c_job_name_tl [32340](#)
 - \jobname [422](#)
- ## K
- \k [29521](#), [31364](#), [31439](#),
[31440](#), [31457](#), [31458](#), [31480](#), [31481](#),
[31482](#), [31537](#), [31538](#), [31563](#), [31564](#)
 - \kanjiskip [1236](#), [2063](#)
 - \kansuji [1237](#), [2064](#)
 - \kansujichar [1238](#), [2065](#)
 - \kcatcode [1239](#), [2066](#)
 - \kchar [1272](#), [2087](#)
 - \kchardef [1273](#), [2088](#)
 - \kern [423](#)
 - kernel internal commands:
 - __kernel_backend_align_begin: . [320](#)
 - __kernel_backend_align_end: . . [320](#)
 - \g__kernel_backend_header_bool . [320](#)
 - __kernel_backend_literal:n . . [319](#)
 - __kernel_backend_literal_pdf:n [319](#)
 - __kernel_backend_literal_-
postscript:n [319](#)
 - __kernel_backend_literal_svg:n [319](#)
 - __kernel_backend_matrix:n [320](#)
 - __kernel_backend_postscript:n . [319](#)
 - __kernel_backend_scope_begin: . [320](#)
 - __kernel_backend_scope_end: . . [320](#)
 - __kernel_chk_cs_exist:N [313](#)
 - __kernel_chk_defined:NTF
..... [313](#), [568](#), [606](#),
[2829](#), [2848](#), [5250](#), [8669](#), [9532](#), [9633](#),
[10780](#), [12078](#), [16481](#), [18839](#), [26430](#)
 - __kernel_chk_expr:nNnN [314](#)
 - __kernel_chk_if_free_cs:N
. [580](#), [607](#), [2574](#), [2589](#), [2637](#), [3961](#),
[4262](#), [4268](#), [4273](#), [8077](#), [8787](#), [8806](#),
[9575](#), [11291](#), [11293](#), [11303](#), [11749](#),
[14583](#), [14929](#), [15023](#), [16328](#), [27042](#)
 - \l__kernel_color_stack_int [320](#)
 - __kernel_cs_parm_from_arg_-
count:nnTF . . [314](#), [2299](#), [2655](#), [2702](#)

- __kernel_deprecation_code:nn ...
 [314](#), [1184](#), [2249](#), [32240](#),
 [32275](#), [32282](#), [32283](#), [32441](#), [32550](#)
- __kernel_deprecation_error:Nnn .
 [1184](#), [1191](#), [32243](#), [32302](#), [32452](#), [32553](#)
- \g__kernel_deprecation_undo_-
 recent_bool ... [32211](#), [32225](#), [32252](#)
- __kernel_exp_not:w [314](#), [357](#), [3221](#),
 [3223](#), [3227](#), [3231](#), [3234](#), [3237](#), [3242](#),
 [4945](#), [4971](#), [4996](#), [8909](#), [29558](#), [29905](#)
- \l__kernel_expl_bool
 [235](#), [238](#), [253](#), [267](#), [2099](#)
- __kernel_file_input_pop: [314](#), [14345](#)
- __kernel_file_input_push:n
 [314](#), [14345](#)
- __kernel_file_missing:n
 [314](#), [13065](#), [14340](#), [14349](#)
- __kernel_file_name_expand_-
 group:nw [13768](#)
- __kernel_file_name_expand_-
 loop:w [13768](#)
- __kernel_file_name_expand_N_-
 type:Nw [13768](#)
- __kernel_file_name_expand_-
 space:w [13768](#)
- __kernel_file_name_quote:n [1176](#),
 [13115](#), [13330](#), [13859](#), [13898](#), [14365](#)
- __kernel_file_name_quote:nw . [13859](#)
- __kernel_file_name_sanitizе:n ..
 .. [13309](#), [13768](#), [13920](#), [14029](#), [14343](#)
- __kernel_file_name_sanitizе:nN .
 [314](#), [314](#)
- __kernel_file_name_strip_-
 quotes:n [13768](#)
- __kernel_file_name_strip_-
 quotes:nnn [13768](#)
- __kernel_file_name_strip_-
 quotes:nnnw [13768](#)
- __kernel_file_name_trim_-
 spaces:n [13768](#)
- __kernel_file_name_trim_-
 spaces:nw [13768](#)
- __kernel_file_name_trim_spaces_-
 aux:n [13768](#)
- __kernel_file_name_trim_spaces_-
 aux:w [13768](#)
- __kernel_if_debug:TF
 [2236](#), [32251](#), [32263](#)
- __kernel_int_add:nnn [314](#), [8777](#), [22706](#)
- __kernel_intarray_gset:Nnn [722](#),
 [16333](#), [16345](#), [16371](#), [16454](#), [16545](#),
 [22870](#), [22871](#), [22873](#), [22877](#), [22878](#),
 [22879](#), [25847](#), [25931](#), [25933](#), [25935](#),
 [25955](#), [25958](#), [26013](#), [26533](#), [26535](#),
 [26541](#), [26549](#), [26551](#), [26554](#), [26615](#),
 [26617](#), [26619](#), [26632](#), [26638](#), [26642](#)
- __kernel_intarray_item:Nn
 [724](#), [896](#), [16423](#), [16471](#),
 [20966](#), [20972](#), [20975](#), [20978](#), [21712](#),
 [21715](#), [21718](#), [21721](#), [21724](#), [21727](#),
 [21730](#), [21733](#), [21736](#), [22919](#), [22920](#),
 [22921](#), [25926](#), [25947](#), [25950](#), [25966](#),
 [25993](#), [26054](#), [26055](#), [26078](#), [26079](#),
 [26087](#), [26093](#), [26095](#), [26102](#), [26108](#),
 [26110](#), [26164](#), [26168](#), [26538](#), [26665](#)
- __kernel_ior_open:Nn . [315](#), [1176](#),
 [13072](#), [13091](#), [14052](#), [14067](#), [31995](#)
- __kernel_iow_with:Nnn
 [315](#), [417](#), [610](#), [640](#),
 [5258](#), [5260](#), [12242](#), [12244](#), [12462](#),
 [12464](#), [13363](#), [13377](#), [32631](#), [32633](#)
- __kernel_msg_error:nn
 [315](#), [2551](#), [9908](#), [12652](#),
 [24395](#), [24428](#), [24476](#), [24479](#), [24940](#),
 [25197](#), [26298](#), [26382](#), [28139](#), [31986](#)
- __kernel_msg_error:nnn
 [315](#), [2239](#), [2244](#), [2312](#), [2367](#), [2415](#),
 [2420](#), [2551](#), [2739](#), [2746](#), [2834](#), [3580](#),
 [3854](#), [4066](#), [4090](#), [4094](#), [4239](#), [4499](#),
 [5355](#), [6079](#), [6138](#), [8290](#), [8321](#), [9990](#),
 [10109](#), [11832](#), [12475](#), [12652](#), [14213](#),
 [14342](#), [15363](#), [15423](#), [15439](#), [15609](#),
 [15627](#), [16341](#), [16552](#), [16574](#), [16984](#),
 [22795](#), [23335](#), [24434](#), [24636](#), [25039](#),
 [25052](#), [25091](#), [25215](#), [26136](#), [26143](#),
 [26396](#), [27177](#), [27765](#), [29029](#), [31992](#)
- __kernel_msg_error:nnnn
 [315](#), [2303](#), [2343](#),
 [2434](#), [2551](#), [2578](#), [2704](#), [3665](#), [3874](#),
 [3897](#), [4109](#), [6170](#), [9929](#), [9939](#), [9952](#),
 [12106](#), [12501](#), [12652](#), [13427](#), [15347](#),
 [15403](#), [15458](#), [15472](#), [15618](#), [16111](#),
 [16163](#), [16980](#), [23197](#), [23204](#), [24613](#),
 [24678](#), [24902](#), [26302](#), [26318](#), [27981](#)
- __kernel_msg_error:nnnnn
 [315](#), [12652](#), [13438](#), [16383](#),
 [22842](#), [23352](#), [26582](#), [26705](#), [32309](#)
- __kernel_msg_error:nnnnnn
 . [315](#), [3680](#), [3694](#), [12652](#), [16409](#), [32292](#)
- __kernel_msg_expandable_-
 error:nn [316](#),
 [3251](#), [8068](#), [9838](#), [10936](#), [10938](#),
 [10946](#), [10952](#), [10994](#), [11738](#), [12996](#),
 [15189](#), [15196](#), [15236](#), [17512](#), [24134](#)
- __kernel_msg_expandable_-
 error:nnn [316](#),
 [2987](#), [3327](#), [3387](#), [3411](#), [4795](#), [8612](#),
 [8887](#), [9068](#), [10093](#), [10688](#), [12996](#)

- 13840, 13994, 14316, 14819, 17519,
- 17535, 17540, 17607, 17664, 17703,
- 17709, 18046, 18051, 18062, 18069,
- 18160, 18174, 18374, 18427, 19095,
- 22492, 22499, 22505, 24220, 29020
- __kernel_msg_expandable_-
- error:nnnn
 . [316](#), [12996](#), 13433, 16504, 18561,
 18582, 19256, 22671, 22761, 24159
- __kernel_msg_expandable_-
- error:nnnnn . [316](#), [12996](#), 13450,
 16434, 17095, 22538, 22912, 32306
- __kernel_msg_expandable_-
- error:nnnnnn ... [316](#), [12996](#), 32293
- __kernel_msg_fatal:nn
 [315](#), [12652](#), 13097, 13314
- __kernel_msg_fatal:nnn .. [315](#), [12652](#)
- __kernel_msg_fatal:nnnn . [315](#), [12652](#)
- __kernel_msg_fatal:nnnnn [315](#), [12652](#)
- __kernel_msg_fatal:nnnnnn [315](#), [12652](#)
- __kernel_msg_info:nn ... [316](#), [12657](#)
- __kernel_msg_info:nnn ... [316](#), [12657](#)
- __kernel_msg_info:nnnn .. [316](#), [12657](#)
- __kernel_msg_info:nnnnn . [316](#), [12657](#)
- __kernel_msg_info:nnnnnn [316](#), [12657](#)
- __kernel_msg_new:nnn
 ... [315](#), 6425, 6427, 6436, [12606](#),
 12702, 12704, 12706, 12708, 12710,
 12780, 12831, 12879, 12912, 12914,
 12916, 12918, 12920, 12922, 12924,
 12926, 12930, 12933, 12940, 12942,
 12949, 12956, 14516, 15239, 15241,
 16309, 16324, 17123, 17125, 17127,
 17129, 17131, 17133, 17135, 18759,
 18761, 18763, 18765, 18767, 18769,
 18771, 18773, 18775, 18777, 18779,
 18781, 18783, 18785, 18790, 19148,
 19150, 19152, 22488, 23808, 26729,
 26731, 26736, 26990, 28961, 32314
- __kernel_msg_new:nnnn
 [315](#), 6299, 6429, 6444, 6458,
 6464, 6511, 6556, 6646, 6761, 6941,
 6948, 7120, [12606](#), 12660, 12668,
 12676, 12683, 12694, 12712, 12721,
 12728, 12735, 12742, 12751, 12760,
 12767, 12773, 12782, 12789, 12798,
 12804, 12811, 12818, 12821, 12833,
 12840, 12848, 12855, 12863, 12871,
 12891, 12902, 12967, 12973, 13999,
 14510, 14522, 14529, 14536, 14541,
 16273, 16276, 16279, 16285, 16291,
 16297, 16303, 16957, 17097, 17112,
 23340, 23358, 23365, 23374, 26742,
 26749, 26755, 26765, 26771, 26795,
- 26802, 26810, 26818, 26825, 26831,
- 26838, 26844, 26852, 26858, 26864,
- 26874, 26881, 26890, 26893, 26901,
- 26907, 26913, 26920, 26927, 26937,
- 26948, 26958, 26968, 26977, 26983,
- 28945, 28952, 28955, 29034, 31997
- __kernel_msg_set:nnn ... [315](#), [12606](#)
- __kernel_msg_set:nnnn ... [315](#), [12606](#)
- __kernel_msg_warning:nn
 [316](#), [12657](#), 24930
- __kernel_msg_warning:nnn
 [316](#), [12657](#), 24846,
 24850, 24892, 24954, 24992, 25011
- __kernel_msg_warning:nnnn
 [316](#), [12657](#), 24543, 24692
- __kernel_msg_warning:nnnnn
 [316](#), [12657](#), 32265
- __kernel_msg_warning:nnnnnn ...
 [316](#), 12589, [12657](#)
- __kernel_patch_deprecation:nnNNpn
 [1183](#), [32236](#),
 32328, 32333, 32501, 32504, 32509,
 32513, 32566, 32568, 32570, 32573,
 32580, 32587, 32653, 32655, 32657,
 32660, 32662, 32664, 32666, 32668,
 32670, 32672, 32674, 32676, 32678,
 32680, 32682, 32684, 32686, 32688,
 32690, 32693, 32697, 32706, 32717,
 32727, 32730, 32733, 32736, 32739,
 32742, 32745, 32747, 32749, 32751,
 32753, 32755, 32757, 32759, 32761,
 32763, 32765, 32767, 32769, 32771
- __kernel_prefix_arg_replacement:wN
 [2870](#)
- \g__kernel_prg_map_int
 [316](#), [403](#), [517](#), [678](#),
 [960](#), 2099, 4741, 4743, 4745, 4748,
 5540, 5542, 5546, 5551, 8527, 8528,
 8534, 8535, 9097, 9100, 9108, 9111,
 9122, [9863](#), 10600, 10602, 10604,
 10607, 12042, 12043, 12048, 12050,
 13217, 13219, 13226, 14837, 14840,
 14844, 14847, 14858, 19125, 19128,
 19132, 19135, 19146, 23695, 23697,
 23717, 31901, 31903, 31905, 31907
- __kernel_primitive:NN
 [275](#), [278](#), 284, 285,
 286, 287, 288, 289, 290, 291, 292,
 293, 294, 295, 296, 297, 298, 299,
 300, 301, 302, 303, 304, 305, 306,
 307, 308, 309, 310, 311, 312, 313,
 314, 315, 316, 317, 318, 319, 320,
 321, 322, 323, 324, 325, 326, 327,
 328, 329, 330, 331, 332, 333, 334,

335, 336, 337, 338, 339, 340, 341,
342, 343, 344, 345, 346, 347, 348,
349, 350, 351, 352, 353, 354, 355,
356, 357, 358, 359, 360, 361, 362,
363, 364, 365, 366, 367, 368, 369,
370, 371, 372, 373, 374, 375, 376,
377, 378, 379, 380, 381, 382, 383,
384, 385, 386, 387, 388, 389, 390,
391, 392, 393, 394, 395, 396, 397,
398, 399, 400, 401, 402, 403, 404,
405, 406, 407, 408, 409, 410, 411,
412, 413, 414, 415, 416, 417, 418,
419, 420, 421, 422, 423, 424, 425,
426, 427, 428, 429, 430, 431, 432,
433, 434, 435, 436, 437, 438, 439,
440, 441, 442, 443, 444, 445, 446,
447, 448, 449, 450, 451, 452, 453,
454, 455, 456, 457, 458, 459, 460,
461, 462, 463, 464, 465, 466, 467,
468, 469, 470, 471, 472, 473, 474,
475, 476, 477, 478, 479, 480, 481,
482, 483, 484, 485, 486, 487, 488,
489, 490, 491, 492, 493, 494, 495,
496, 497, 498, 499, 500, 501, 502,
503, 504, 505, 506, 507, 508, 509,
510, 511, 512, 513, 514, 515, 516,
517, 518, 519, 520, 521, 522, 523,
524, 525, 526, 527, 528, 529, 530,
531, 532, 533, 534, 535, 536, 537,
538, 539, 540, 541, 542, 543, 544,
545, 546, 547, 548, 549, 550, 551,
552, 553, 554, 555, 556, 557, 558,
559, 560, 561, 562, 563, 564, 565,
566, 567, 568, 569, 570, 571, 572,
573, 574, 575, 576, 577, 578, 579,
580, 581, 582, 583, 584, 585, 586,
587, 588, 589, 590, 591, 592, 593,
594, 595, 596, 597, 598, 599, 600,
601, 602, 603, 604, 605, 606, 607,
608, 609, 610, 611, 612, 613, 614,
615, 616, 617, 618, 619, 620, 621,
622, 623, 624, 625, 626, 627, 628,
629, 630, 631, 632, 633, 634, 635,
636, 637, 638, 639, 640, 641, 642,
643, 644, 645, 646, 647, 648, 649,
650, 651, 652, 653, 654, 655, 656,
657, 658, 659, 660, 661, 662, 663,
664, 665, 666, 667, 668, 669, 670,
671, 672, 673, 674, 675, 676, 677,
678, 679, 680, 681, 682, 683, 684,
685, 686, 687, 688, 689, 690, 691,
692, 693, 694, 695, 696, 697, 698,
699, 701, 702, 703, 704, 705, 706,
707, 709, 710, 711, 712, 713, 714,
715, 716, 717, 718, 719, 720, 721,
722, 723, 724, 725, 726, 727, 728,
729, 730, 731, 732, 733, 734, 735,
736, 737, 738, 739, 740, 741, 742,
743, 744, 745, 746, 747, 748, 749,
750, 751, 752, 753, 754, 755, 756,
757, 758, 759, 760, 761, 762, 763,
764, 765, 766, 767, 768, 769, 770,
771, 772, 773, 774, 775, 776, 777,
778, 779, 780, 781, 782, 783, 784,
785, 786, 787, 788, 789, 790, 791,
792, 793, 794, 795, 796, 797, 798,
803, 815, 817, 818, 819, 820, 821,
822, 823, 824, 825, 826, 827, 829,
831, 833, 834, 835, 837, 838, 839,
840, 841, 842, 844, 846, 847, 849,
851, 852, 853, 854, 855, 856, 857,
858, 859, 860, 861, 862, 863, 864,
865, 866, 867, 868, 869, 870, 871,
872, 873, 874, 875, 876, 877, 878,
879, 880, 881, 882, 883, 884, 885,
886, 887, 888, 889, 891, 892, 894,
895, 896, 897, 898, 899, 900, 901,
902, 903, 905, 906, 907, 908, 909,
910, 911, 912, 913, 914, 915, 916,
917, 918, 919, 920, 921, 922, 923,
924, 925, 926, 927, 928, 929, 930,
931, 932, 933, 934, 935, 936, 937,
938, 939, 940, 941, 942, 943, 944,
945, 946, 947, 948, 949, 950, 951,
952, 953, 954, 955, 956, 957, 958,
959, 960, 961, 962, 963, 964, 965,
966, 967, 968, 969, 970, 971, 972,
973, 974, 975, 976, 977, 978, 979,
980, 981, 982, 983, 984, 985, 986,
987, 988, 989, 990, 991, 992, 993,
994, 995, 996, 997, 998, 999, 1000,
1001, 1002, 1004, 1005, 1006, 1007,
1008, 1009, 1010, 1011, 1012, 1013,
1014, 1015, 1016, 1017, 1018, 1020,
1022, 1024, 1025, 1026, 1027, 1028,
1029, 1030, 1031, 1032, 1033, 1034,
1035, 1036, 1037, 1038, 1039, 1040,
1041, 1042, 1043, 1044, 1045, 1046,
1047, 1048, 1049, 1050, 1051, 1052,
1053, 1054, 1055, 1056, 1057, 1058,
1059, 1060, 1061, 1062, 1063, 1064,
1065, 1066, 1067, 1069, 1071, 1072,
1073, 1074, 1076, 1077, 1078, 1079,
1081, 1082, 1084, 1086, 1087, 1088,
1089, 1090, 1092, 1094, 1095, 1096,
1097, 1099, 1100, 1101, 1102, 1103,
1104, 1105, 1106, 1107, 1108, 1109,
1110, 1111, 1112, 1113, 1114, 1115,

1116, 1117, 1118, 1119, 1120, 1121,
1122, 1123, 1124, 1125, 1126, 1127,
1128, 1129, 1130, 1131, 1132, 1133,
1134, 1135, 1136, 1138, 1140, 1141,
1143, 1145, 1146, 1147, 1148, 1150,
1151, 1152, 1154, 1156, 1158, 1159,
1160, 1161, 1162, 1163, 1164, 1165,
1166, 1167, 1168, 1169, 1171, 1173,
1174, 1175, 1176, 1177, 1178, 1179,
1180, 1181, 1182, 1183, 1184, 1185,
1186, 1187, 1188, 1188, 1189, 1191,
1193, 1194, 1195, 1196, 1197, 1198,
1199, 1200, 1201, 1202, 1203, 1204,
1205, 1206, 1207, 1208, 1209, 1210,
1211, 1212, 1213, 1214, 1215, 1216,
1217, 1218, 1219, 1220, 1221, 1222,
1223, 1224, 1225, 1226, 1227, 1228,
1229, 1230, 1231, 1232, 1233, 1234,
1235, 1236, 1237, 1238, 1239, 1240,
1241, 1242, 1243, 1244, 1245, 1246,
1247, 1248, 1249, 1250, 1251, 1252,
1254, 1256, 1257, 1258, 1259, 1260,
1262, 1263, 1264, 1265, 1266, 1267,
1268, 1269, 1270, 1271, 1272, 1273,
1274, 1275, 1276, 1277, 1278, 1279,
1280, 1281, 1282, 1283, 1284, 1468,
1479, 1480, 1481, 1482, 1483, 1484,
1485, 1486, 1487, 1488, 1489, 1490,
1492, 1493, 1494, 1495, 1496, 1497,
1498, 1499, 1500, 1501, 1502, 1503,
1504, 1505, 1506, 1507, 1508, 1509,
1510, 1511, 1512, 1513, 1514, 1515,
1516, 1517, 1518, 1519, 1520, 1521,
1522, 1523, 1524, 1525, 1526, 1527,
1528, 1529, 1530, 1531, 1532, 1533,
1534, 1535, 1536, 1537, 1538, 1539,
1540, 1541, 1542, 1543, 1544, 1545,
1546, 1547, 1548, 1549, 1550, 1551,
1552, 1553, 1554, 1555, 1556, 1557,
1558, 1559, 1560, 1561, 1562, 1563,
1564, 1565, 1566, 1567, 1568, 1569,
1571, 1573, 1574, 1575, 1576, 1577,
1578, 1579, 1581, 1582, 1583, 1584,
1585, 1586, 1587, 1589, 1590, 1591,
1592, 1593, 1594, 1595, 1596, 1597,
1598, 1599, 1600, 1601, 1602, 1603,
1604, 1605, 1607, 1608, 1609, 1610,
1611, 1612, 1613, 1614, 1615, 1616,
1617, 1618, 1619, 1620, 1621, 1622,
1623, 1624, 1625, 1626, 1627, 1628,
1629, 1630, 1631, 1632, 1633, 1634,
1635, 1636, 1637, 1638, 1639, 1640,
1641, 1642, 1643, 1644, 1645, 1646,
1647, 1648, 1649, 1650, 1651, 1652,
1653, 1654, 1655, 1656, 1657, 1658,
1659, 1660, 1661, 1662, 1663, 1664,
1665, 1666, 1667, 1668, 1669, 1670,
1671, 1672, 1673, 1674, 1675, 1676,
1677, 1678, 1680, 1681, 1683, 1685,
1687, 1688, 1689, 1690, 1691, 1692,
1693, 1694, 1695, 1696, 1697, 1698,
1699, 1700, 1701, 1702, 1703, 1704,
1706, 1707, 1708, 1709, 1710, 1711,
1712, 1713, 1714, 1715, 1716, 1718,
1720, 1722, 1723, 1724, 1726, 1727,
1728, 1729, 1730, 1731, 1733, 1735,
1736, 1738, 1740, 1741, 1742, 1743,
1744, 1745, 1746, 1747, 1748, 1749,
1750, 1751, 1752, 1753, 1754, 1755,
1756, 1757, 1758, 1759, 1760, 1761,
1762, 1763, 1764, 1765, 1766, 1767,
1768, 1770, 1772, 1774, 1775, 1776,
1777, 1778, 1780, 1782, 1783, 1784,
1785, 1786, 1787, 1788, 1789, 1790,
1792, 1793, 1795, 1796, 1797, 1798,
1799, 1800, 1801, 1802, 1803, 1804,
1805, 1806, 1807, 1808, 1809, 1810,
1811, 1812, 1813, 1814, 1816, 1817,
1818, 1819, 1820, 1821, 1822, 1823,
1824, 1825, 1826, 1827, 1828, 1829,
1830, 1831, 1832, 1833, 1834, 1835,
1836, 1837, 1838, 1839, 1840, 1841,
1842, 1844, 1845, 1846, 1847, 1848,
1849, 1850, 1851, 1853, 1854, 1856,
1857, 1859, 1860, 1861, 1862, 1863,
1864, 1865, 1866, 1867, 1868, 1870,
1871, 1872, 1873, 1874, 1875, 1876,
1877, 1878, 1879, 1880, 1881, 1882,
1883, 1884, 1885, 1886, 1887, 1888,
1889, 1890, 1891, 1892, 1893, 1894,
1895, 1896, 1897, 1898, 1899, 1900,
1901, 1902, 1903, 1905, 1907, 1908,
1909, 1910, 1912, 1913, 1914, 1915,
1917, 1918, 1920, 1922, 1923, 1924,
1925, 1926, 1928, 1930, 1931, 1932,
1933, 1935, 1936, 1937, 1938, 1939,
1940, 1941, 1942, 1943, 1944, 1945,
1946, 1947, 1948, 1949, 1950, 1951,
1952, 1953, 1954, 1955, 1956, 1957,
1958, 1959, 1960, 1961, 1962, 1963,
1964, 1965, 1966, 1967, 1968, 1969,
1970, 1971, 1972, 1974, 1976, 1977,
1979, 1981, 1982, 1983, 1984, 1985,
1986, 1987, 1989, 1991, 1993, 1994,
1995, 1996, 1997, 1998, 1999, 2000,
2001, 2002, 2003, 2004, 2006, 2008,
2009, 2010, 2011, 2012, 2013, 2014,
2015, 2016, 2017, 2018, 2019, 2020,

- 2021, 2022, 2023, 2024, 2026, 2028,
2029, 2030, 2031, 2032, 2033, 2034,
2035, 2036, 2037, 2038, 2039, 2040,
2041, 2042, 2043, 2044, 2045, 2046,
2047, 2048, 2049, 2050, 2051, 2052,
2053, 2054, 2055, 2056, 2057, 2058,
2059, 2060, 2061, 2062, 2063, 2064,
2065, 2066, 2067, 2068, 2069, 2070,
2071, 2072, 2073, 2074, 2075, 2076,
2077, 2078, 2079, 2080, 2081, 2082,
2083, 2084, 2085, 2086, 2087, 2088,
2089, 2090, 2091, 2092, 32443, 32468
 - __kernel_primitives:
 . 301, 1188, 1475, 2095, 32465, 32480
 - __kernel_quark_new_conditional:Nn
 318, 4061, 4385, 10804,
 13763, 15315, 15316, 23891, 29380
 - __kernel_quark_new_test:N
 317, 380, 381, 383,
 385, 4061, 4384, 5286, 5287, 8694,
 8695, 9611, 10211, 10212, 11745,
 13766, 13767, 15319, 29385, 31008
 - __kernel_randint:n
 318, 318, 318, 726, 923,
 926, 16535, 22513, 22525, 22683, 22768
 - __kernel_randint:nn
 318, 726, 16531, 22687, 22691, 22766
 - \c__kernel_randint_max_int
 926, 2099, 16528, 22512, 22681, 22765
 - __kernel_register_log:N
 318, 2838, 9484, 14914,
 14915, 15010, 15011, 15080, 15081
 - __kernel_register_show:N
 318, 318,
 417, 2838, 9480, 14910, 15006, 15076
 - __kernel_register_show_aux:NN 2838
 - __kernel_register_show_aux:nnN 2838
 - __kernel_show:NN 2856
 - __kernel_str_to_other:n ... 319,
 319, 425, 427, 431, 5586, 5638, 5699
 - __kernel_str_to_other_fast:n ...
 319, 5547, 5567,
 5609, 6112, 13397, 13493, 24105, 25234
 - __kernel_str_to_other_fast_
 loop:w 5609
 - __kernel_sys_configuration_
 load:n 9915, 9964, 9970, 32495, 32497
 - __kernel_tl_to_str:w
 319, 401, 2126, 4059, 4598,
 4670, 4789, 4982, 5418, 5522, 14259
- keys commands:
- \l_keys_choice_int
 185, 187, 189, 189,
 191, 15290, 15483, 15486, 15491, 15492
 - \l_keys_choice_tl
 185, 187, 189, 191, 15290, 15490
 - \keys_define:nn ... 184, 12793, 15320
 - \keys_if_choice_exist:nnnTF
 194, 16242
 - \keys_if_choice_exist_p:nnn
 194, 16242
 - \keys_if_exist:nnTF
 193, 719, 16235, 16259
 - \keys_if_exist_p:nn 193, 16235
 - \l_keys_key_str 191, 15293, 15424,
 15440, 15969, 15971, 16057, 16061,
 16087, 16090, 16091, 16131, 16188
 - \l_keys_key_tl 15293, 15971
 - \keys_log:nn 194, 16250
 - \l_keys_path_str 191,
 15298, 15348, 15368, 15377, 15380,
 15387, 15391, 15405, 15417, 15419,
 15421, 15433, 15435, 15437, 15452,
 15455, 15459, 15467, 15469, 15470,
 15473, 15488, 15502, 15512, 15517,
 15527, 15531, 15538, 15543, 15547,
 15552, 15559, 15566, 15567, 15582,
 15593, 15599, 15603, 15619, 15628,
 15636, 15677, 15959, 15970, 15994,
 15997, 16036, 16040, 16045, 16054,
 16068, 16070, 16071, 16076, 16084,
 16112, 16141, 16164, 16176, 16185
 - \l_keys_path_tl . 15298, 15380, 15459
 - \keys_set:nn 183,
 187, 191, 191, 192, 15554, 15559, 15806
 - \keys_set_filter:nnn 193, 15876
 - \keys_set_filter:nnnN ... 193, 15876
 - \keys_set_filter:nnnnN ... 193, 15876
 - \keys_set_groups:nnn 193, 15876
 - \keys_set_known:nn 192, 15835
 - \keys_set_known:nnN . 192, 711, 15835
 - \keys_set_known:nnnnN 192, 15835
 - \keys_show:nn 194, 194, 16250
 - \l_keys_value_tl
 191, 15308, 15619, 16039,
 16043, 16049, 16060, 16072, 16093,
 16108, 16121, 16133, 16143, 16171
- keys internal commands:
- __keys_bool_set:Nn
 .. 15413, 15651, 15653, 15655, 15657
 - __keys_bool_set_inverse:Nn
 .. 15429, 15659, 15661, 15663, 15665
 - __keys_check_groups: . 15998, 16006
 - __keys_choice_find:n . 15446, 16182
 - __keys_choice_find:nn 16182
 - __keys_choice_make:
 .. 15416, 15432, 15445, 15477, 15667
 - __keys_choice_make:N 15445

```

\__keys_choice_make_aux:N .... 15445
\__keys_choices_make:nn .....
.. 15476, 15669, 15671, 15673, 15675
\__keys_choices_make:Nnn ..... 15476
\__keys_cmd_set:nn .....
15417, 15419, 15421, 15433, 15435,
15437, 15469, 15470, 15487, 15497,
15552, 15559, 15567, 15636, 15677
\c_keys_code_root_str .....
..... 15283, 15498, 15502,
15547, 16068, 16071, 16087, 16091,
16105, 16107, 16118, 16120, 16193,
16194, 16195, 16238, 16246, 16265
\__keys_cs_set:NNpn .....
.... 15500, 15687, 15689, 15691,
15693, 15695, 15697, 15699, 15701
\__keys_default_inherit: .... 16032
\c_keys_default_root_str .....
..... 15283, 15512,
15517, 16036, 16040, 16057, 16061
\__keys_default_set:n 15426, 15442,
15507, 15703, 15705, 15707, 15709
\__keys_define:n ..... 15325, 15329
\__keys_define:nn ..... 15325, 15329
\__keys_define:nnn ..... 15320
\__keys_define_aux:nn ..... 15329
\__keys_define_code:n . 15343, 15395
\__keys_define_code:w ..... 15395
\__keys_execute: .....
.. 15975, 16002, 16024, 16028, 16066
\__keys_execute:nn ..... 16066
\__keys_execute_inherit: 15544, 16066
\__keys_execute_unknown: . 715, 16066
\l_keys_filtered_bool ... 15304,
15811, 15818, 15819, 15862, 15868,
15869, 15904, 15910, 15911, 15923,
15930, 15931, 16001, 16022, 16027
\__keys_find_key_module:NNw ....
..... 15563, 15947
\l_keys_groups_clist ... 15292,
15524, 15525, 15532, 15996, 16011
\c_keys_groups_root_str .....
.. 15283, 15527, 15531, 15994, 15997
\__keys_groups_set:n .. 15522, 15727
\__keys_if_recursion_tail_stop:n
..... 15319, 16231
\__keys_inherit:n ..... 15535, 15729
\c_keys_inherit_root_str .....
..... 15283, 15538,
15543, 16045, 16054, 16076, 16084
\l_keys_inherit_str .... 15300,
15546, 15966, 16089, 16184, 16188
\__keys_initialise:n .....
.. 15540, 15731, 15733, 15735, 15737

\__keys_meta_make:n ... 15550, 15747
\__keys_meta_make:nn .. 15550, 15749
\l_keys_module_str .....
.... 15295, 15321, 15324, 15326,
15370, 15371, 15377, 15555, 15828,
15831, 15833, 15950, 15955, 15965,
15968, 15976, 16105, 16107, 16112
\__keys_multichoice_find:n .....
..... 15448, 16182
\__keys_multichoice_make: .....
..... 15445, 15479, 15751
\__keys_multichoices_make:nn ...
.. 15476, 15753, 15755, 15757, 15759
\l_keys_no_value_bool .....
..... 15296, 15331,
15336, 15397, 15616, 15625, 15949,
15954, 16034, 16132, 16142, 16170
\l_keys_only_known_bool .....
.... 15297, 15810, 15816, 15817,
15861, 15866, 15867, 15903, 15908,
15909, 15922, 15928, 15929, 16101
\__keys_parent:n .....
.... 15452, 15455, 15459, 15543,
16045, 16054, 16076, 16084, 16199
\__keys_parent:w ..... 16199
\__keys_prop_put:Nn .....
.. 15560, 15769, 15771, 15773, 15775
\__keys_property_find:n 15341, 15352
\__keys_property_find:w ..... 15352
\__keys_property_search:w .....
..... 15378, 15383, 15392
\l_keys_property_str .....
..... 15303, 15342, 15345,
15348, 15354, 15355, 15362, 15374,
15388, 15400, 15401, 15404, 15408
\c_keys_props_root_str .....
..... 15289, 15342,
15401, 15408, 15650, 15652, 15654,
15656, 15658, 15660, 15662, 15664,
15666, 15668, 15670, 15672, 15674,
15676, 15678, 15680, 15682, 15684,
15686, 15688, 15690, 15692, 15694,
15696, 15698, 15700, 15702, 15704,
15706, 15708, 15710, 15712, 15714,
15716, 15718, 15720, 15722, 15724,
15726, 15728, 15730, 15732, 15734,
15736, 15738, 15740, 15742, 15744,
15746, 15748, 15750, 15752, 15754,
15756, 15758, 15760, 15762, 15764,
15766, 15768, 15770, 15772, 15774,
15776, 15778, 15780, 15782, 15784,
15786, 15788, 15790, 15792, 15794,
15796, 15798, 15800, 15802, 15804
\__keys_quark_if_nil:nTF 15315, 16220

```

__keys_quark_if_nil_p:n [15315](#)
 __keys_quark_if_no_value:N .. [15316](#)
 __keys_quark_if_no_value:NTF . [16127](#)
 \l_keys_relative_tl [15301](#),
 [15813](#), [15822](#), [15823](#), [15864](#), [15872](#),
 [15873](#), [15906](#), [15914](#), [15915](#), [15925](#),
 [15934](#), [15935](#), [16127](#), [16137](#), [16151](#),
 [16152](#), [16156](#), [16157](#), [16165](#), [16177](#)
 \l_keys_selective_bool
 [15304](#), [15812](#), [15820](#), [15821](#),
 [15863](#), [15870](#), [15871](#), [15905](#), [15912](#),
 [15913](#), [15924](#), [15932](#), [15933](#), [15973](#)
 \l_keys_selective_seq
 .. [15306](#), [15940](#), [15943](#), [15945](#), [16009](#)
 __keys_set:nn .. [15806](#), [15865](#), [15944](#)
 __keys_set:nnn [15806](#)
 __keys_set_filter:nnnn [15876](#)
 __keys_set_filter:nnnnN [15876](#)
 __keys_set_keyval:n .. [15832](#), [15947](#)
 __keys_set_keyval:nn . [15832](#), [15947](#)
 __keys_set_keyval:nnn [15947](#)
 __keys_set_known:nnn [15835](#)
 __keys_set_known:nnnn [15835](#)
 __keys_set_selective: [15947](#)
 __keys_set_selective:nnn [15876](#)
 __keys_set_selective:nnnn ... [15876](#)
 __keys_show:Nnn [16250](#)
 __keys_store_unused:
 [16003](#), [16023](#), [16029](#), [16066](#)
 __keys_store_unused:w
 [16155](#), [16176](#), [16181](#)
 __keys_store_unused_aux: [16066](#)
 \l_keys_tmp_bool
 [15309](#), [16008](#), [16015](#), [16020](#)
 \l_keys_tmpa_tl [15309](#), [15564](#)
 \l_keys_tmpb_tl . [15309](#), [15565](#), [15571](#)
 __keys_trim_spaces:n
 [15324](#), [15354](#), [15488](#),
 [15831](#), [15963](#), [16152](#), [16193](#), [16194](#),
 [16213](#), [16238](#), [16246](#), [16257](#), [16266](#)
 __keys_trim_spaces_auxi:w ... [16213](#)
 __keys_trim_spaces_auxii:w .. [16213](#)
 __keys_trim_spaces_auxiii:w . [16213](#)
 \c_keys_type_root_str
 [15283](#), [15452](#), [15455](#), [15467](#)
 __keys_undefine: [15537](#), [15576](#), [15801](#)
 \l_keys_unused_clist
 . [710](#), [15307](#), [15838](#), [15844](#), [15849](#),
 [15851](#), [15852](#), [15879](#), [15886](#), [15891](#),
 [15893](#), [15894](#), [16129](#), [16139](#), [16167](#)
 __keys_validate_cleanup:w ... [15586](#)
 __keys_validate_forbidden: .. [15586](#)
 __keys_validate_required: ... [15586](#)
 \c_keys_validate_root_str [15283](#),
 [15593](#), [15599](#), [15603](#), [16070](#), [16090](#)
 __keys_value_or_default:n
 [15972](#), [16032](#)
 __keys_value_requirement:nn ...
 .. [15519](#), [15586](#), [15647](#), [15803](#), [15805](#)
 __keys_variable_set:NnnN
 [15633](#), [15679](#), [15681](#),
 [15683](#), [15685](#), [15785](#), [15787](#), [15789](#),
 [15791](#), [15793](#), [15795](#), [15797](#), [15799](#)
 __keys_variable_set_required:NnnN
 [15633](#),
 [15711](#), [15713](#), [15715](#), [15717](#), [15719](#),
 [15721](#), [15723](#), [15725](#), [15739](#), [15741](#),
 [15743](#), [15745](#), [15761](#), [15763](#), [15765](#),
 [15767](#), [15777](#), [15779](#), [15781](#), [15783](#)
 keyval commands:
 \keyval_parse:NNn
 .. [195](#), [692](#), [693](#), [15100](#), [15325](#), [15832](#)
 keyval internal commands:
 __keyval_blank_key_error:w
 [15220](#), [15226](#), [15233](#)
 __keyval_blank_true:w . [15181](#), [15233](#)
 __keyval_cleanup_active:w
 [690](#), [15119](#), [15156](#), [15203](#)
 __keyval_cleanup_other:w
 [691](#), [15161](#), [15178](#)
 __keyval_end_loop_active:w
 [15105](#), [15199](#)
 __keyval_end_loop_other:w
 [15116](#), [15199](#)
 __keyval_if_blank:w
 [15181](#), [15220](#), [15226](#), [15230](#)
 __keyval_if_empty:w [15230](#)
 __keyval_if_recursion_tail:w ...
 [15104](#), [15115](#), [15230](#)
 __keyval_key:nNN .. [691](#), [15183](#), [15218](#)
 __keyval_loop_active:NNw
 [15101](#), [15102](#), [15211](#)
 __keyval_loop_other:NNw
 [15106](#), [15113](#), [15206](#), [15210](#)
 __keyval_misplaced_equal_after_
 active_error:w
 [689](#), [15127](#), [15132](#), [15185](#)
 __keyval_misplaced_equal_in_
 split_error:w ... [15138](#), [15144](#),
 [15148](#), [15153](#), [15169](#), [15175](#), [15185](#)
 __keyval_pair:nnNN
 [690](#), [691](#), [15155](#), [15177](#), [15218](#)
 __keyval_split_active:w
 [689](#), [689](#), [15109](#), [15117](#), [15137](#), [15201](#)
 __keyval_split_active_auxi:w ...
 [15118](#), [15124](#), [15157](#), [15202](#)

- `__keyval_split_active_auxii:w` .. [689](#), [689](#), [15124](#)
 - `__keyval_split_active_auxiii:w` . [689](#), [15124](#)
 - `__keyval_split_active_auxiv:w` .. [690](#), [15124](#)
 - `__keyval_split_active_auxv:w` . [15124](#)
 - `__keyval_split_other:w` [15109](#), [15126](#), [15147](#), [15159](#), [15168](#)
 - `__keyval_split_other_auxi:w` [690](#), [15160](#), [15164](#), [15179](#)
 - `__keyval_split_other_auxii:w` . [15164](#)
 - `__keyval_split_other_auxiii:w` .. [691](#), [15164](#)
 - `__keyval_tmp:n` [15244](#), [15280](#)
 - `__keyval_tmp:NN` ... [692](#), [15098](#), [15216](#)
 - `__keyval_trim:nN` [15134](#), [15155](#), [15165](#), [15177](#), [15183](#), [15243](#)
 - `__keyval_trim_auxi:w` [15243](#)
 - `__keyval_trim_auxii:w` [15243](#)
 - `__keyval_trim_auxiii:w` [15243](#)
 - `__keyval_trim_auxiv:w` [15243](#)
 - `\kuten` [1240](#), [1274](#), [2067](#), [2089](#)
- L**
- `\L` [29530](#), [30961](#), [31281](#)
 - `\l` [29530](#), [30961](#), [31293](#)
 - `l3kernel` [253](#), [29042](#)
 - `l3kernel.charcat` [253](#), [29076](#)
 - `l3kernel.elapsedtime` [253](#), [29081](#)
 - `l3kernel.filedump` [253](#), [29094](#)
 - `l3kernel.filemdfivesum` [253](#), [29111](#)
 - `l3kernel.filemoddate` [253](#), [29123](#)
 - `l3kernel.filesize` [253](#), [29168](#)
 - `l3kernel.resettimer` [253](#), [29081](#)
 - `l3kernel.shellescape` [253](#), [29188](#)
 - `l3kernel.strcmp` [253](#), [29178](#)
 - `\label` [29539](#), [29547](#), [31229](#)
 - `\language` [424](#)
 - `\LARGE` [31212](#)
 - `\Large` [31213](#)
 - `\large` [31216](#)
 - `\lastallocatedtoks` [23026](#)
 - `\lastbox` [425](#)
 - `\lastkern` [426](#)
 - `\lastlinefit` [642](#), [1513](#)
 - `\lastnamedcs` [933](#), [1805](#)
 - `\lastnodechar` [1241](#)
 - `\lastnodesubtype` [1242](#)
 - `\lastnodetype` [643](#), [1514](#)
 - `\lastpenalty` [427](#)
 - `\lastsavedboxresourceindex` .. [1018](#), [1681](#)
 - `\lastsavedimageresourceindex` [1020](#), [1683](#)
 - `\lastsavedimageresourcepages` [1022](#), [1685](#)
 - `\lastskip` [428](#)
 - `\lastxpos` [1024](#), [1687](#)
 - `\lastypos` [1025](#), [1688](#)
 - `\latelua` [934](#), [1806](#)
 - `\lateluafunction` [935](#)
 - LaTeX3 error commands:
 - `\LaTeX3_error:` [628](#)
 - `\lccode` [167](#), [182](#), [195](#), [197](#), [199](#), [201](#), [203](#), [429](#)
 - `\leaders` [430](#)
 - `\left` [431](#)
 - left commands:
 - `\c_left_brace_str` [71](#), [981](#), [5899](#), [13814](#), [24181](#), [24566](#), [24570](#), [24590](#), [24603](#), [24627](#), [25110](#), [25191](#), [26223](#), [26258](#), [26282](#), [29635](#)
 - `\leftghost` [936](#), [1865](#)
 - `\lefthyphenmin` [432](#)
 - `\leftmarginkern` [791](#), [1660](#)
 - `\leftskip` [433](#)
 - legacy commands:
 - `\legacy_if:nTF` [259](#), [31591](#)
 - `\legacy_if_p:n` [259](#), [31591](#)
 - `\legno` [434](#)
 - `\let` [2](#), [40](#), [272](#), [273](#), [435](#)
 - `\latcharcode` [937](#), [1807](#)
 - `\letterspacefont` [792](#), [1661](#)
 - `\limits` [436](#)
 - `\LineBreak` [74](#), [75](#), [76](#), [77](#), [78](#), [79](#), [80](#), [81](#), [106](#), [113](#), [114](#), [115](#), [123](#), [125](#)
 - `\linedir` [938](#), [1866](#)
 - `\linedirection` [939](#)
 - `\linepenalty` [437](#)
 - `\lineskip` [438](#)
 - `\lineskiplimit` [439](#)
 - `\linewidth` [27846](#), [27915](#)
 - `\ln` [21092](#), [21095](#)
 - `ln` [211](#)
 - `\localbrokenpenalty` [940](#), [1867](#)
 - `\localinterlinepenalty` [941](#), [1868](#)
 - `\localleftbox` [946](#), [1870](#)
 - `\localrightbox` [947](#), [1871](#)
 - `\loccount` [13053](#), [13286](#)
 - `\loctoks` [22998](#), [22999](#), [23025](#)
 - `logb` [212](#)
 - `\long` [275](#), [440](#), [11475](#), [11479](#)
 - `\LongText` [70](#), [111](#), [135](#)
 - `\looseness` [441](#)
 - `\lower` [442](#)
 - `\lowercase` [443](#)
 - `\lpcode` [793](#), [1662](#)
 - lua commands:
 - `\lua_escape:n` [252](#), [5402](#), [5417](#), [10022](#), [10035](#), [13914](#), [14095](#), [14160](#), [14179](#), [14258](#), [14307](#), [29001](#), [29003](#), [32568](#)

<code>\lua_escape_x:n</code>	32566	<code>\luatex_hjcode:D</code>	1798
<code>\lua_now:n</code>	252, 5403, 5406, 10021, 10977, 13913, 14094, 14156, 14178, 14247, 14306, 29002, 29003, 32566	<code>\luatex_hpack:D</code>	1799
<code>\lua_now_x:n</code>	32566	<code>\luatex_hyphenationbounds:D</code> . .	1800
<code>\lua_shipout:n</code>	252, 29003	<code>\luatex_hyphenationmin:D</code>	1801
<code>\lua_shipout_e:n</code>		<code>\luatex_hyphenpenalty:D</code> . .	1802
.	252, 10034, 29003, 32570	<code>\luatex_if_engine:TF</code>	
<code>\lua_shipout_x:n</code>	32566	32386, 32388, 32390
lua internal commands:		<code>\luatex_if_engine_p:</code>	32384
<code>__lua_escape:n</code>	28998, 29008, 32569	<code>\luatex_initcatcodetable:D</code> . . .	1804
<code>__lua_now:n</code>	28998, 29003, 32567	<code>\luatex_lastnamedcs:D</code>	1805
<code>__lua_shipout:n</code>	28998, 29005, 32571	<code>\luatex_latelua:D</code>	1806
<code>\luabytecode</code>	942	<code>\luatex_leftghost:D</code>	1865
<code>\luabytecodecall</code>	943	<code>\luatex_letcharcode:D</code>	1807
<code>\luacopyinputnodes</code>	944	<code>\luatex_linedir:D</code>	1866
<code>\luaedef</code>	945	<code>\luatex_localbrokenpenalty:D</code> .	1867
<code>\luaescapestring</code>	948, 1808	<code>\luatex_localinterlinepenalty:D</code>	1869
<code>\luafunction</code>	949, 1809	<code>\luatex_localleftbox:D</code>	1870
<code>\luafunctioncall</code>	950	<code>\luatex_localrightbox:D</code>	1871
luatex commands:		<code>\luatex_luaescapestring:D</code>	1808
<code>\luatex_alignmark:D</code>	1764	<code>\luatex_luafunction:D</code>	1809
<code>\luatex_aligntab:D</code>	1765	<code>\luatex luatexbanner:D</code>	1810
<code>\luatex_attribute:D</code>	1766	<code>\luatex luatexrevision:D</code>	1811
<code>\luatex_attributedef:D</code>	1767	<code>\luatex luatexversion:D</code>	1812
<code>\luatex_automaticdiscretionary:D</code>		<code>\luatex_mathdelimitersmode:D</code> .	1813
.	1769	<code>\luatex_mathdir:D</code>	1872
<code>\luatex_automaticallyhyphenmode:D</code> .	1771	<code>\luatex_mathdisplayskipmode:D</code> .	1815
<code>\luatex_automaticallyhyphenpenalty:D</code>		<code>\luatex_matheqnogapstep:D</code>	1816
.	1773	<code>\luatex_mathnolimitsmode:D</code> . . .	1817
<code>\luatex_begincsname:D</code>	1774	<code>\luatex_mathoption:D</code>	1818
<code>\luatex_bodydir:D</code>	1863	<code>\luatex_mathpenaltiesmode:D</code> . .	1819
<code>\luatex_boxdir:D</code>	1864	<code>\luatex_mathrulesfam:D</code>	1820
<code>\luatex_breakafterdirmode:D</code> . .	1775	<code>\luatex_mathscriptboxmode:D</code> . .	1822
<code>\luatex_catcodetable:D</code>	1776	<code>\luatex_mathscriptsmode:D</code>	1821
<code>\luatex_clearmarks:D</code>	1777	<code>\luatex_mathstyle:D</code>	1823
<code>\luatex_crampeddisplaystyle:D</code> .	1779	<code>\luatex_mathsurroundmode:D</code> . . .	1824
<code>\luatex_crampedscriptscriptstyle:D</code>		<code>\luatex_mathsurroundskip:D</code> . . .	1825
.	1781	<code>\luatex_nohrule:D</code>	1826
<code>\luatex_crampedscriptstyle:D</code> .	1782	<code>\luatex_nokerns:D</code>	1827
<code>\luatex_crampedtextstyle:D</code> . . .	1783	<code>\luatex_noligs:D</code>	1828
<code>\luatex_directlua:D</code>	1784	<code>\luatex_nospaces:D</code>	1829
<code>\luatex_dviextension:D</code>	1785	<code>\luatex_novrule:D</code>	1830
<code>\luatex_dvifeedback:D</code>	1786	<code>\luatex_outputbox:D</code>	1831
<code>\luatex_dvivariable:D</code>	1787	<code>\luatex_pagebottomoffset:D</code> . . .	1832
<code>\luatex_etoksapp:D</code>	1788	<code>\luatex_pagedir:D</code>	1873
<code>\luatex_etokspre:D</code>	1789	<code>\luatex_pageleftoffset:D</code>	1833
<code>\luatex_expanded:D</code>	1792	<code>\luatex_pagerightoffset:D</code>	1834
<code>\luatex_explicitdiscretionary:D</code>	1794	<code>\luatex_pagetopoffset:D</code>	1835
<code>\luatex_explicityhyphenpenalty:D</code>	1791	<code>\luatex_pardir:D</code>	1874
<code>\luatex_firstvalidlanguage:D</code> .	1795	<code>\luatex_pdfextension:D</code>	1836
<code>\luatex_fontid:D</code>	1796	<code>\luatex_pdffeedback:D</code>	1837
<code>\luatex_formatname:D</code>	1797	<code>\luatex_pdfvariable:D</code>	1838
<code>\luatex_gleaders:D</code>	1803	<code>\luatex_postexhyphenchar:D</code> . . .	1839
		<code>\luatex_posthyphenchar:D</code>	1840
		<code>\luatex_prebinoppenalty:D</code>	1841

<code>\luatex_predisplaysapfactor:D</code>	1843	<code>\luatexpagerightoffset</code>	1389
<code>\luatex_preexhyphenchar:D</code>	1844	<code>\luatexpagetopoffset</code>	1361
<code>\luatex_prehyphenchar:D</code>	1845	<code>\luatexpagewidth</code>	1390
<code>\luatex_prerelpenalty:D</code>	1846	<code>\luatexpardir</code>	1391
<code>\luatex_rightghost:D</code>	1875	<code>\luatexpostexhyphenchar</code>	1362
<code>\luatex_savecatcodetable:D</code>	1847	<code>\luatexposthyphenchar</code>	1363
<code>\luatex_scantextokens:D</code>	1848	<code>\luatexpreeexhyphenchar</code>	1364
<code>\luatex_setfontid:D</code>	1849	<code>\luatexprehyphenchar</code>	1365
<code>\luatex_shapemode:D</code>	1850	<code>\luatexrevision</code>	952, 1811
<code>\luatex_suppressifcsnameerror:D</code>	1852	<code>\luatexrightghost</code>	1392
<code>\luatex_suppresslongerror:D</code>	1853	<code>\luatexsavecatcodetable</code>	1366
<code>\luatex_suppressmathparerror:D</code>	1855	<code>\luatexscantextokens</code>	1367
<code>\luatex_suppressoutererror:D</code>	1856	<code>\luatexsuppressfontnotfounderror</code>	1337, 1376
<code>\luatex_suppressprimitiveerror:D</code>	1858	<code>\luatexsuppressifcsnameerror</code>	1369
<code>\luatex_textdir:D</code>	1876	<code>\luatexsuppresslongerror</code>	1370
<code>\luatex_toksapp:D</code>	1859	<code>\luatexsuppressmathparerror</code>	1372
<code>\luatex_tokspre:D</code>	1860	<code>\luatexsuppressoutererror</code>	1373
<code>\luatex_tpack:D</code>	1861	<code>\luatextextdir</code>	1393
<code>\luatex_vpack:D</code>	1862	<code>\luatexUchar</code>	1374
<code>\luatexalignmark</code>	1338	<code>\luatexversion</code>	45, 101, 953, 1812
<code>\luatexaligntab</code>	1339		
<code>\luatexattribute</code>	1340		
<code>\luatexattributedef</code>	1341		
<code>\luatexbanner</code>	951, 1810		
<code>\luatexbodydir</code>	1377		
<code>\luatexboxdir</code>	1378		
<code>\luatexcatcodetable</code>	1342		
<code>\luatexclearmarks</code>	1343		
<code>\luatexcrampeddisplaystyle</code>	1344		
<code>\luatexcrampedscriptscriptstyle</code>	1346		
<code>\luatexcrampedscriptstyle</code>	1347		
<code>\luatexcrampedtextstyle</code>	1348		
<code>\luatexfontid</code>	1349		
<code>\luatexformatname</code>	1350		
<code>\luatexgladers</code>	1351		
<code>\luatexinitcatcodetable</code>	1352		
<code>\luatexlatalua</code>	1353		
<code>\luatexleftghost</code>	1379		
<code>\luatexlocalbrokenpenalty</code>	1380		
<code>\luatexlocalinterlinepenalty</code>	1382		
<code>\luatexlcalleftbox</code>	1383		
<code>\luatexlocalrightbox</code>	1384		
<code>\luatexluaescapestring</code>	1354		
<code>\luatexluafunction</code>	1355		
<code>\luatexmathdir</code>	1385		
<code>\luatexmathstyle</code>	1356		
<code>\luatexnokerns</code>	1357		
<code>\luatexnoligs</code>	1358		
<code>\luatexoutputbox</code>	1359		
<code>\luatexpagebottomoffset</code>	1386		
<code>\luatexpagedir</code>	1387		
<code>\luatexpageheight</code>	1388		
<code>\luatexpageleftoffset</code>	1360		

- `\mathpunct` 457
- `\mathrel` 458
- `\mathrulesfam` 962, 1820
- `\mathscriptboxmode` 964, 1822
- `\mathscriptcharmode` 965
- `\mathscriptsmode` 963, 1821
- `\mathstyle` 966, 1823
- `\mathsurround` 459
- `\mathsurroundmode` 967, 1824
- `\mathsurroundskip` 968, 1825
- `max` 212
- max commands:
 - `\c_max_char_int` 99, 9490, 10951, 24157
 - `\c_max_register_int`
 - 99, 232, 935, 2153, 6405,
 - 8288, 8684, 12738, 12843, 12845,
 - 22970, 22996, 23033, 23041, 23045
- `\maxdeadcycles` 460
- `\maxdepth` 461
- `\mdfivesum` 880, 1668
- `\mdseries` 31205
- `\meaning` 462
- `\medmuskip` 463
- `\message` 464
- `\MessageBreak` 123
- meta commands:
 - `.meta:n` 187, 15746
 - `.meta:nn` 187, 15748
- `\middle` 645, 1516
- `min` 212
- minus commands:
 - `\c_minus_inf_fp`
 - 206, 215, 16588, 19617,
 - 19701, 20034, 20571, 21418, 22943
 - `\c_minus_zero_fp`
 - 205, 16588, 19613, 22137, 22941
- `\mkern` 465
- `mm` 216
- mode commands:
 - `\mode_if_horizontal:TF` 111, 9853
 - `\mode_if_horizontal_p:` 111, 9853
 - `\mode_if_inner:TF` 111, 9855
 - `\mode_if_inner_p:` 111, 9855
 - `\mode_if_math:TF` 111, 9857
 - `\mode_if_math_p:` 111, 9857
 - `\mode_if_vertical:TF` 112, 9851
 - `\mode_if_vertical_p:` 112, 9851
 - `\mode_leave_vertical:` 24, 2917, 28695
- `\month` 466, 1417, 10081
- `\moveleft` 467
- `\moveright` 468
- msg commands:
 - `\msg_critical:nn` 153, 167, 12371
 - `\msg_critical:nnn` 153, 12371
 - `\msg_critical:nnnn` 153, 12371
 - `\msg_critical:nnnnnn` 153, 12371
 - `\msg_critical_text:n` 151, 12266, 12374
 - `\msg_error:nn` 153, 12379
 - `\msg_error:nnn` 153, 12379
 - `\msg_error:nnnn` 153, 12379
 - `\msg_error:nnnnn` 153, 12379
 - `\msg_error:nnnnnn` ... 153, 263, 12379
 - `\msg_error_text:n` .. 151, 12266, 12382
 - `\msg_expandable_error:nn` . 263, 31720
 - `\msg_expandable_error:nnn` 263, 31720
 - `\msg_expandable_error:nnnn` 263, 31720
 - `\msg_expandable_error:nnnnn`
 - 263, 31720
 - `\msg_expandable_error:nnnnnn` ...
 - 263, 31720
 - `\msg_fatal:nn` 153, 12358
 - `\msg_fatal:nnn` 153, 12358
 - `\msg_fatal:nnnn` 153, 12358
 - `\msg_fatal:nnnnn` 153, 12358
 - `\msg_fatal:nnnnnn` 153, 12358
 - `\msg_fatal_text:n` .. 151, 12266, 12361
 - `\msg_gset:nnn` 150, 12110
 - `\msg_gset:nnnn` 150, 12110
 - `\msg_if_exist:nnTF`
 - 151, 12097, 12104, 12485
 - `\msg_if_exist_p:nn` 151, 12097
 - `\msg_info:nn` 154, 12408
 - `\msg_info:nnn` 154, 12408
 - `\msg_info:nnnn` 154, 12408
 - `\msg_info:nnnnn` 154, 12408
 - `\msg_info:nnnnnn` 154, 154, 12408, 12658
 - `\msg_info_text:n` ... 152, 12266, 12410
 - `\msg_interrupt:nnn` 32587
 - `\msg_line_context:`
 - . 151, 609, 2568, 12167, 15240, 15242
 - `\msg_line_number:` 151, 12167
 - `\msg_log:n` 32573
 - `\msg_log:nn` 154, 12430
 - `\msg_log:nnn` 154, 12430
 - `\msg_log:nnnn` 154, 12430
 - `\msg_log:nnnnn` 154, 12430
 - `\msg_log:nnnnnn` 154, 8665,
 - 10776, 10789, 12074, 12430, 13130,
 - 13346, 14441, 16253, 16477, 28924
 - `\msg_log_eval:Nn` . 263, 9487, 9624,
 - 14917, 15013, 15083, 18845, 31751
 - `\g_msg_module_documentation_prop` 152
 - `\msg_module_name:n`
 - 152, 12177, 12285, 12308, 12389, 12411
 - `\g_msg_module_name_prop`
 - 152, 152, 12293, 12310, 12311

- \msg_module_type:n
..... [151](#), [152](#), [152](#), [12284](#), [12297](#)
- \g_msg_module_type_prop
..... [152](#), [152](#), [12293](#), [12299](#), [12300](#)
- \msg_new:nnn [150](#), [12110](#), [12609](#)
- \msg_new:nnnn . [150](#), [607](#), [12110](#), [12607](#)
- \msg_none:nn [154](#), [12436](#)
- \msg_none:nnn [154](#), [12436](#)
- \msg_none:nnnn [154](#), [12436](#)
- \msg_none:nnnnn [154](#), [12436](#)
- \msg_redirect_class:nn ... [155](#), [12558](#)
- \msg_redirect_module:nnn . [155](#), [12558](#)
- \msg_redirect_name:nnn ... [155](#), [12549](#)
- \msg_see_documentation_text:n ...
..... [152](#), [12308](#)
- \msg_set:nnn [150](#), [12110](#), [12613](#)
- \msg_set:nnnn [150](#), [12110](#), [12611](#)
- \msg_show:nn [263](#), [12437](#)
- \msg_show:nnn [263](#), [12437](#)
- \msg_show:nnnn [263](#), [12437](#)
- \msg_show:nnnnn [263](#), [12437](#)
- \msg_show:nnnnnn
..... [263](#), [264](#), [504](#), [568](#), [606](#),
[8663](#), [10774](#), [10788](#), [12072](#), [12437](#),
[13129](#), [13345](#), [14440](#), [16251](#), [16475](#),
[23724](#), [23732](#), [26424](#), [26433](#), [28921](#)
- \msg_show_eval:Nn [263](#), [9483](#), [9622](#),
[14913](#), [15009](#), [15079](#), [18843](#), [31751](#)
- \msg_show_item:n
.. [263](#), [264](#), [8673](#), [10784](#), [10793](#), [31756](#)
- \msg_show_item:nn
..... [264](#), [606](#), [12082](#), [31756](#)
- \msg_show_item_unbraced:n [264](#), [31756](#)
- \msg_show_item_unbraced:nn . [264](#),
[633](#), [13137](#), [13353](#), [16261](#), [28940](#), [31756](#)
- \msg_term:n [32573](#)
- \msg_warning:nn [153](#), [12386](#)
- \msg_warning:nnn [153](#), [12386](#)
- \msg_warning:nnnn [153](#), [12386](#)
- \msg_warning:nnnnn [153](#), [12386](#)
- \msg_warning:nnnnnn [153](#), [12386](#), [12657](#)
- \msg_warning_text:n [151](#), [12266](#), [12388](#)
- msg internal commands:
- _msg_chk_free:nn [12102](#), [12112](#)
- _msg_chk_if_free:nn [12102](#)
- _msg_class_chk_exist:nTF
 .. [12472](#), [12487](#), [12554](#), [12564](#), [12569](#)
- \l_msg_class_loop_seq
 [620](#), [12481](#), [12573](#),
[12581](#), [12591](#), [12592](#), [12595](#), [12597](#)
- _msg_class_new:nn [616](#),
[621](#), [12319](#), [12358](#), [12371](#), [12379](#),
[12386](#), [12408](#), [12430](#), [12436](#), [12437](#)
- \l__msg_class_tl . [617](#), [620](#), [12477](#),
[12494](#), [12507](#), [12528](#), [12532](#), [12535](#),
[12543](#), [12582](#), [12584](#), [12586](#), [12600](#)
- \c__msg_coding_error_text_tl ...
 [12135](#),
[12663](#), [12671](#), [12697](#), [12715](#), [12724](#),
[12731](#), [12745](#), [12754](#), [12776](#), [12785](#),
[12792](#), [12801](#), [12807](#), [12814](#), [12824](#),
[12836](#), [12851](#), [12858](#), [12866](#), [12874](#)
- \c__msg_continue_text_tl
 [12135](#), [12184](#), [32593](#)
- \c__msg_critical_text_tl [12135](#), [12376](#)
- \l__msg_current_class_tl
 [619](#), [12477](#), [12489](#), [12527](#),
[12532](#), [12535](#), [12543](#), [12572](#), [12586](#)
- _msg_error_code:nnnnnn [12656](#)
- _msg_expandable_error:n
 [629](#), [12979](#), [12999](#)
- _msg_expandable_error:w [628](#), [12979](#)
- _msg_expandable_error_module:nn
 [31720](#)
- _msg_fatal_code:nnnnnn [12652](#)
- _msg_fatal_exit: [12358](#)
- \c__msg_fatal_text_tl . [12135](#), [12363](#)
- \c__msg_help_text_tl
 [12135](#), [12194](#), [32597](#)
- \l__msg_hierarchy_seq
 [618](#), [618](#), [12480](#), [12510](#), [12520](#), [12525](#)
- \l__msg_internal_tl [12089](#),
[12220](#), [12226](#), [12369](#), [12461](#), [12467](#)
- _msg_interrupt:n [12221](#), [12230](#)
- _msg_interrupt:Nnnn [12174](#)
- _msg_interrupt:NnnnN
 [12174](#), [12360](#), [12373](#), [12381](#)
- _msg_interrupt_more_text:n ...
 [610](#), [12203](#)
- _msg_interrupt_text:n [12203](#)
- _msg_interrupt_wrap:nnn
 [12182](#), [12192](#), [12203](#)
- _msg_kernel_class_new:nN
 [622](#), [12614](#), [12652](#), [12656](#), [12657](#), [12658](#)
- _msg_kernel_class_new_aux:nN [12614](#)
- \c__msg_more_text_prefix_tl ...
 .. [12095](#), [12121](#), [12130](#), [12179](#), [12196](#)
- \l__msg_name_str
 [12090](#), [12177](#), [12210](#), [12214](#), [12389](#),
[12397](#), [12401](#), [12411](#), [12419](#), [12423](#)
- \c__msg_no_info_text_tl
 [12135](#), [12186](#), [32592](#)
- _msg_no_more_text:nnnn [12174](#)
- _msg_old_interrupt_more_text:n
 [32602](#), [32605](#)
- _msg_old_interrupt_text:n
 [32603](#), [32622](#)

- _msg_old_interrupt_wrap:nn ...
..... 32592, 32596, 32600
 - \c_msg_on_line_text_tl 12135, 12170
 - _msg_redirect:nnn 12558
 - _msg_redirect_loop_chk:nnn ...
..... 12558, 12600
 - _msg_redirect_loop_list:n .. 12558
 - \l_msg_redirect_prop
..... 12479, 12507, 12552, 12555
 - \c_msg_return_text_tl
..... 12135, 12666, 12674, 12681
 - _msg_show:n 616, 12437
 - _msg_show:nn 12437
 - _msg_show:w 12437
 - _msg_show_dot:w 12437
 - _msg_show_eval:nnN 31751
 - _msg_text:n 12266
 - _msg_text:nn 12266
 - \c_msg_text_prefix_tl
..... 629, 12095, 12099,
12119, 12128, 12183, 12193, 12394,
12416, 12433, 12440, 13002, 31725
 - \l_msg_text_str
12090, 12176, 12208, 12213, 12388,
12393, 12400, 12410, 12415, 12422
 - _msg_tmp:w 12980, 12993
 - \c_msg_trouble_text_tl 12135
 - _msg_use:nnnnnn 12329, 12482
 - _msg_use_code: 617, 12482
 - _msg_use_hierarchy:nwN 12482
 - _msg_use_none_delimit_by_s-
stop:w 12094, 12513, 31748
 - _msg_use_redirect_module:n ...
..... 618, 12482
 - _msg_use_redirect_name:n ... 12482
 - \mskip 469
 - \muexpr 646, 1517
 - multichoice commands:
 .multichoice: 187, 15750
 - multichoices commands:
 .multichoices:nn 187, 15750
 - \multiply 470
 - \muskip 471, 11482
 - muskip commands:
 \c_max_muskip 182, 15084
 - \muskip_add:Nn 180, 15060
 - \muskip_const:Nn
 180, 15028, 15084, 15085
 - \muskip_eval:n
 181, 181, 15031, 15072, 15079, 15083
 - \muskip_gadd:Nn 180, 15060
 - .muskip_gset:N 187, 15760
 - \muskip_gset:Nn 181, 15050
 - \muskip_gset_eq:NN 181, 15056
 - \muskip_gsub:Nn 181, 15060
 - \muskip_gzero:N ... 180, 15034, 15043
 - \muskip_gzero_new:N 180, 15040
 - \muskip_if_exist:NTF
 180, 15041, 15043, 15046
 - \muskip_if_exist_p:N 180, 15046
 - \muskip_log:N 182, 15080
 - \muskip_log:n 182, 15080
 - \muskip_new:N
 .. 180, 180, 15020, 15030, 15041,
 15043, 15086, 15087, 15088, 15089
 - .muskip_set:N 187, 15760
 - \muskip_set:Nn 181, 15050
 - \muskip_set_eq:NN 181, 15056
 - \muskip_show:n 181, 15076
 - \muskip_show:N 182, 687, 15078
 - \muskip_sub:Nn 181, 15060
 - \muskip_use:N . 181, 181, 15073, 15074
 - \muskip_zero:N 180, 180, 15034, 15041
 - \muskip_zero_new:N 180, 15040
 - \g_tmpa_muskip 182, 15086
 - \l_tmpa_muskip 182, 15086
 - \g_tmpb_muskip 182, 15086
 - \l_tmpb_muskip 182, 15086
 - \c_zero_muskip 182, 15035, 15037, 15084
 - \muskipdef 472
 - \mutoglu 647, 1518
- N
- \n 29191, 29193, 29195
 - nan 215
 - nc 216
 - nd 216
 - \newbox 508
 - \newcount 508
 - \newdimen 508
 - \newlinechar 104, 473
 - \next 68, 107, 132, 141, 145, 148, 156
 - \NG 29531, 30962, 31282
 - \ng 29531, 30962, 31294
 - \noalign 474
 - \noautospace 1243, 2068
 - \noautoxspacing 1244, 2069
 - \noboundary 475
 - \nobreakspace 31237
 - \noexpand 119, 123, 134, 137, 476
 - \nohrule 969, 1826
 - \noindent 477
 - \nokerns 970, 1827
 - \noligs 971, 1828
 - \nolimits 478
 - \nonscript 479
 - \nonstopmode 480
 - \normaldeviate 1026, 1689

`\normalend` 1437, 1438, 13049, 13081, 13282
`\normaleveryjob` 1439
`\normalexpanded` 1448
`\normalfont` 31200
`\normalhoffset` 1451
`\normalinput` 1440
`\normalitaliccorrection` 1450, 1452
`\normallanguage` 1441
`\normalleft` 1458, 1459
`\normalmathop` 1442
`\normalmiddle` 1460
`\normalmonth` 1443
`\normalouter` 1444
`\normalover` 1445
`\normalright` 1461
`\normalshowtokens` 1454
`\normalsize` 31217
`\normalunexpanded` 1447
`\normalvcenter` 1446
`\normalvoffset` 1453
`\nospaces` 972, 1829
notexpanded commands:
`\notexpanded: <token>` 140
`\novrule` 973, 1830
`\nulldelimiterspace` 481
`\nullfont` 482
`\num` 199
`\number` 483
`\numexpr` 168, 182, 648, 1519

O

`\O` 29532, 30963, 31283, 31573
`\o` 29532, 30963, 31295, 31574
`\odelcode` 1278
`\odelimiter` 1279
`\OE` 29533, 30964, 31284
`\oe` 29533, 30964, 31296
`\omathaccent` 1280
`\omathchar` 1281
`\omathchardef` 1282
`\omathcode` 1283
`\omit` 484
one commands:
`\c_minus_one` 32342
`\c_one_degree_fp` 206, 215, 18190, 18848
`\openin` 485
`\openout` 486
`\or` 487
or commands:

`\or:` . 100, 428, 429, 430, 741, 2100,
2662, 2663, 2664, 2665, 2666, 2667,
2668, 2669, 2670, 3309, 3310, 3311,
3312, 3313, 5689, 5765, 5988, 5989,
5990, 5991, 5992, 7030, 7031, 8684,

9270, 9271, 9272, 9273, 9274, 9275,
9276, 9277, 9278, 9279, 9280, 9281,
9282, 9283, 9284, 9285, 9286, 9287,
9288, 9289, 9290, 9291, 9292, 9293,
9294, 9303, 9304, 9305, 9306, 9307,
9308, 9309, 9310, 9311, 9312, 9313,
9314, 9315, 9316, 9317, 9318, 9319,
9320, 9321, 9322, 9323, 9324, 9325,
9326, 9327, 11003, 11007, 11010,
11012, 11013, 11015, 11017, 11019,
11020, 11022, 11024, 11026, 11028,
11061, 13572, 13573, 13574, 13575,
13576, 13577, 13578, 16634, 16635,
16636, 16885, 16900, 16901, 17284,
17285, 17310, 18602, 18603, 18604,
18640, 19313, 19314, 19315, 19438,
19523, 19609, 19610, 19611, 19612,
19613, 19614, 19615, 19616, 19617,
19696, 19699, 20035, 20036, 20050,
20051, 20065, 20349, 20572, 20597,
20603, 20604, 20605, 20606, 20607,
20756, 20791, 20793, 20801, 20994,
21045, 21048, 21057, 21172, 21195,
21196, 21228, 21229, 21233, 21286,
21287, 21327, 21332, 21342, 21347,
21357, 21362, 21372, 21377, 21387,
21392, 21402, 21407, 21934, 21935,
21980, 22065, 22068, 22080, 22086,
22133, 22135, 22136, 22146, 22152,
22229, 22230, 22237, 22283, 22284,
22291, 22357, 22358, 22578, 22861,
22862, 22863, 22940, 22941, 22942,
23475, 23476, 23669, 23670, 23965,
23966, 23967, 23968, 24231, 24232,
24233, 24234, 24235, 25527, 25581,
25940, 25941, 32176, 32177, 32178

`\oradical` 1284
`\outer` 6, 488, 508
`\output` 489
`\outputbox` 974, 1831
`\outputmode` 1027, 1690
`\outputpenalty` 490
`\over` 491
`\overfullrule` 492
`\overline` 493
`\overwithdelims` 494

P

`\PackageError` 126, 134
`\pagebottomoffset` 975, 1832
`\pagedepth` 495
`\pagedir` 976, 1873
`\pagedirection` 977
`\pagediscards` 649, 1520

<code>\pagefilllstretch</code>	496	<code>\pdffontexpand</code>	759, 1629
<code>\pagefillstretch</code>	497	<code>\pdffontname</code>	687, 1558
<code>\pagefilstretch</code>	498	<code>\pdffontobjnum</code>	688, 1559
<code>\pagefistretch</code>	1245	<code>\pdffontsize</code>	760, 1630
<code>\pagegoal</code>	499	<code>\pdfgamma</code>	689, 1560
<code>\pageheight</code>	1028, 1691	<code>\pdfgentounicode</code>	692, 1563
<code>\pageleftoffset</code>	978, 1833	<code>\pdfglyphptounicode</code>	693, 1564
<code>\pagerightoffset</code>	979, 1834	<code>\pdfhorigin</code>	694, 1565
<code>\pageshrink</code>	500	<code>\pdfignoreddimen</code>	761, 1631
<code>\pagestretch</code>	501	<code>\pdfimageapplygamma</code>	690, 1561
<code>\pagetopoffset</code>	980, 1835	<code>\pdfimagegamma</code>	691, 1562
<code>\pagetotal</code>	502	<code>\pdfimagehicolor</code>	695, 1566
<code>\pagewidth</code>	1029, 1692	<code>\pdfimageresolution</code>	696, 1567
<code>\par</code>	10, 11, 11, 11, 12, 12, 12, 13, 13, 13, 14, 14, 14, 158, 339, 503, 1063, 27261, 27263, 27267, 27272, 27277, 27282, 27289, 27294, 27301, 27306, 27326	<code>\pdfincludechars</code>	697, 1568
<code>\pardir</code>	981, 1874	<code>\pdfinclusioncopyfonts</code>	698, 1569
<code>\pardirection</code>	982	<code>\pdfinclusionerrorlevel</code>	699, 1571
<code>\parfillskip</code>	504	<code>\pdfinfo</code>	701, 1573
<code>\parindent</code>	505	<code>\pdfinsertht</code>	762, 1632
<code>\parshape</code>	506	<code>\pdflastannot</code>	702, 1574
<code>\parshapedimen</code>	650, 1521	<code>\pdflastlinedepth</code>	763, 1633
<code>\parshapeindent</code>	651, 1522	<code>\pdflastlink</code>	703, 1575
<code>\parshapelength</code>	652, 1523	<code>\pdflastobj</code>	704, 1576
<code>\parskip</code>	507	<code>\pdflastxform</code>	705, 1577
<code>\patterns</code>	508	<code>\pdflastximage</code>	706, 1578
<code>\pausing</code>	509	<code>\pdflastximagecolordepth</code>	707, 1579
<code>pc</code>	216	<code>\pdflastximagepages</code>	709, 1581
<code>\pdfadjustspacing</code>	749, 1621	<code>\pdflastxpos</code>	764, 1634
<code>\pdfannot</code>	675, 1546	<code>\pdflastypos</code>	765, 1635
<code>\pdfcatalog</code>	676, 1547	<code>\pdflinkmargin</code>	710, 1582
<code>\pdfcolorstack</code>	678, 1549	<code>\pdfliteral</code>	711, 1583
<code>\pdfcolorstackinit</code>	679, 1550	<code>\pdfmajorversion</code>	712
<code>\pdfcompresslevel</code>	677, 1548	<code>\pdfmapfile</code>	766, 1636
<code>\pdfcopyfont</code>	750, 1622	<code>\pdfmapline</code>	767, 1637
<code>\pdfcreationdate</code>	680, 1551	<code>\pdfmdfivesum</code>	768, 1638
<code>\pdfdecimaldigits</code>	681, 1552	<code>\pdfminorversion</code>	713, 1584
<code>\pdfdest</code>	682, 1553	<code>\pdfnames</code>	714, 1585
<code>\pdfdestmargin</code>	683, 1554	<code>\pdfnoligatures</code>	769, 1639
<code>\pdfdraftmode</code>	751, 1623	<code>\pdfnormaldeviate</code>	770, 1640
<code>\pdfeachlinedepth</code>	752, 1624	<code>\pdfobj</code>	715, 1586
<code>\pdfeachlineheight</code>	753, 1625	<code>\pdfobjcompresslevel</code>	716, 1587
<code>\pdfelapsedtime</code>	754	<code>\pdfoutline</code>	717, 1589
<code>\pdfendlink</code>	684, 1555	<code>\pdfoutput</code>	718, 1590
<code>\pdfendthread</code>	685, 1556	<code>\pdfpageattr</code>	719, 1591
<code>\pdfextension</code>	983, 1836	<code>\pdfpagebox</code>	721, 1592
<code>\pdffeedback</code>	984, 1837	<code>\pdfpageheight</code>	771, 1641
<code>\pdffiledump</code>	755	<code>\pdfpageref</code>	722, 1593
<code>\pdffilemoddate</code>	756, 1626	<code>\pdfpageresources</code>	723, 1594
<code>\pdffilesizes</code>	757, 1627	<code>\pdfpagesattr</code>	720, 724, 1595
<code>\pdffirstlineheight</code>	758, 1628	<code>\pdfpagewidth</code>	772, 1642
<code>\pdffontattr</code>	686, 1557	<code>\pdfpkmode</code>	773, 1643
		<code>\pdfpkresolution</code>	774, 1644
		<code>\pdfprimitive</code>	775, 1645
		<code>\pdfprotrudechars</code>	776, 1646
		<code>\pdfpxdimen</code>	777, 1647

\pdfandomseed	778, 1648	\pdftex_pdfcolorstack:D	1549
\pdfrefobj	725, 1596	\pdftex_pdfcolorstackinit:D	1550
\pdfrefxform	726, 1597	\pdftex_pdfcompresslevel:D	1548
\pdfrefximage	727, 1598	\pdftex_pdfcreationdate:D	1551
\pdfresettimer	779	\pdftex_pdfdecimaldigits:D	1552
\pdfrestore	728, 1599	\pdftex_pdfdest:D	1553
\pdfretval	729, 1600	\pdftex_pdfdestmargin:D	1554
\pdfsave	730, 1601	\pdftex_pdfendlink:D	1555
\pdfsavepos	780, 1649	\pdftex_pdfendthread:D	1556
\pdfsetmatrix	731, 1602	\pdftex_pdffontattr:D	1557
\pdfsetrandomseed	782, 1651	\pdftex_pdffontname:D	1558
\pdfshellescape	783, 1652	\pdftex_pdffontobjnum:D	1559
\pdfstartlink	732, 1603	\pdftex_pdfgamma:D	1560
\pdfstartthread	733, 1604	\pdftex_pdfgentounicode:D	1563
\pdfstrcmp	40, 422, 781, 1650	\pdftex_pdfglyphtounicode:D	1564
\pdfsuppressptexinfo	734, 1605	\pdftex_pdfhorigin:D	1565
pdftex commands:		\pdftex_pdfimageapplygamma:D	1561
\pdftex_adjustspacing:D	1621, 1672	\pdftex_pdfimagegamma:D	1562
\pdftex_copyfont:D	1622, 1673	\pdftex_pdfimagehicolor:D	1566
\pdftex_draftmode:D	1623, 1674	\pdftex_pdfimageresolution:D	1567
\pdftex_eachlinedepth:D	1624	\pdftex_pdfincludechars:D	1568
\pdftex_eachlineheight:D	1625	\pdftex_pdfinclusioncopyfonts:D	1570
\pdftex_efcode:D	1658	\pdftex_pdfinclusionerrorlevel:D	1572
\pdftex_filemoddate:D	1626	1573
\pdftex_filesize:D	1627	\pdftex_pdfinfo:D	1573
\pdftex_firstlineheight:D	1628	\pdftex_pdflastannot:D	1574
\pdftex_fontexpand:D	1629, 1675	\pdftex_pdflastlink:D	1575
\pdftex_fontsize:D	1630	\pdftex_pdflastobj:D	1576
\pdftex_if_engine:TF	\pdftex_pdflastxform:D	1577, 1682
.....	32394, 32396, 32398	\pdftex_pdflastximage:D	1578, 1684
\pdftex_if_engine_p:	32392	\pdftex_pdflastximagecolordepth:D	1580
\pdftex_ifabsdim:D	1618, 1676	1581, 1686
\pdftex_ifabsnum:D	1619, 1677	\pdftex_pdflastximagepages:D	1582
\pdftex_ifincsname:D	1659	1583
\pdftex_ifprimitive:D	1620, 1669	\pdftex_pdflinkmargin:D	1584
\pdftex_ignoredimen:D	1631	\pdftex_pdfliteral:D	1585
\pdftex_ignoreligaturesinfont:D	1679	\pdftex_pdfminorversion:D	1586
\pdftex_insertht:D	1632, 1680	\pdftex_pdfnames:D	1588
\pdftex_lastlinedepth:D	1633	\pdftex_pdfobj:D	1589
\pdftex_lastxpos:D	1634, 1687	\pdftex_pdfobjcompresslevel:D	1590, 1690
\pdftex_lastypos:D	1635, 1688	\pdftex_pdfoutline:D	1591
\pdftex_leftmarginkern:D	1660	\pdftex_pdfpageattr:D	1592
\pdftex_letterspacefont:D	1661	\pdftex_pdfpagebox:D	1593
\pdftex_lpcode:D	1662	\pdftex_pdfpageref:D	1594
\pdftex_mapfile:D	1636	\pdftex_pdfpageresources:D	1595
\pdftex_mapline:D	1637	\pdftex_pdfpagesattr:D	1596
\pdftex_mdffivesum:D	1638, 1668	\pdftex_pdfrefobj:D	1597, 1696
\pdftex_noligatures:D	1639	\pdftex_pdfrefxform:D	1598, 1697
\pdftex_normaldeviate:D	1640, 1689	\pdftex_pdfrefximage:D	1599
\pdftex_pageheight:D	1641, 1691	\pdftex_pdfrestore:D	1600
\pdftex_pagewidth:D	1642	\pdftex_pdfretval:D	1601
\pdftex_pagewith:D	1692	\pdftex_pdfsave:D	1602
\pdftex_pdfannot:D	1546		
\pdftex_pdfcatalog:D	1547		

- \pdfutex_pdfstartlink:D 1603
- \pdfutex_pdfstartthread:D 1604
- \pdfutex_pdfsuppressptexinfo:D . 1606
- \pdfutex_pdftexbanner:D 1655
- \pdfutex_pdftexrevision:D 1656
- \pdfutex_pdftexversion:D 1657
- \pdfutex_pdfthread:D 1607
- \pdfutex_pdfthreadmargin:D 1608
- \pdfutex_pdftrailer:D 1609
- \pdfutex_pdfuniqueresname:D ... 1610
- \pdfutex_pdfvorigin:D 1611
- \pdfutex_pdfxform:D 1612, 1699
- \pdfutex_pdfxformattr:D 1613
- \pdfutex_pdfxformname:D 1614
- \pdfutex_pdfxformresources:D .. 1615
- \pdfutex_pdfximage:D 1616, 1700
- \pdfutex_pdfximagebbox:D 1617
- \pdfutex_pkmode:D 1643
- \pdfutex_pkresolution:D 1644
- \pdfutex_primitive:D 1645, 1670
- \pdfutex_protrudechars:D .. 1646, 1693
- \pdfutex_pxdimen:D 1647, 1694
- \pdfutex_quitvmode:D 1663
- \pdfutex_randomseed:D 1648, 1695
- \pdfutex_rightmarginkern:D 1664
- \pdfutex_rpcode:D 1665
- \pdfutex_savepos:D 1649, 1698
- \pdfutex_setrandomseed:D .. 1651, 1701
- \pdfutex_shellescape:D ... 1652, 1671
- \pdfutex_strcmp:D 1650
- \pdfutex_synctex:D 1666
- \pdfutex_tagcode:D 1667
- \pdfutex_tracingfonts:D ... 1653, 1702
- \pdfutex_uniformdeviate:D . 1654, 1703
- \pdfutextbanner 786, 1655
- \pdfutextrevision 787, 1656
- \pdfutextversion 96, 788, 1657
- \pdfutethread 735, 1607
- \pdfutethreadmargin 736, 1608
- \pdfutracingfonts .. 784, 1328, 1329, 1653
- \pdfutrailer 737, 1609
- \pdfuniformdeviate 785, 1654
- \pdfuniqueresname 738, 1610
- \pdfvariable 985, 1838
- \pdfvorigin 739, 1611
- \pdfxform 740, 1612
- \pdfxformattr 741, 1613
- \pdfxformname 742, 1614
- \pdfxformresources 743, 1615
- \pdfximage 744, 1616
- \pdfximagebbox 745, 1617
- peek commands:
 - \peek_after:Nw 113, 137, 137, 137, 11559, 11572, 11600, 32165
 - \peek_catcode:NTF 137, 11655
 - \peek_catcode_collect_inline:Nn 270, 32145
 - \peek_catcode_ignore_spaces:NTF 138, 11669
 - \peek_catcode_remove:NTF . 138, 11655
 - \peek_catcode_remove_ignore_spaces:NTF 138, 11669
 - \peek_charcode:NTF 138, 11655
 - \peek_charcode_collect_inline:Nn 270, 32145
 - \peek_charcode_ignore_spaces:NTF 138, 11669
 - \peek_charcode_remove:NTF 138, 11655
 - \peek_charcode_remove_ignore_spaces:NTF 139, 11669
 - \peek_gafter:Nw 137, 137, 11559
 - \peek_meaning:NTF 139, 11655
 - \peek_meaning_collect_inline:Nn 270, 32145
 - \peek_meaning_ignore_spaces:NTF 139, 11669
 - \peek_meaning_remove:NTF . 139, 11655
 - \peek_meaning_remove_ignore_spaces:NTF 139, 11669
 - \peek_N_type:TF 140, 11692, 11729, 11731
 - \peek_remove_spaces:n 270, 592, 11568, 11678, 11683, 11688
- peek internal commands:
 - __peek_collect:N 1181, 32145
 - __peek_collect:NNn 32145
 - __peek_collect_remove:nw 32145
 - \l_peek_collect_tl 1181, 32144, 32156, 32158, 32183, 32188
 - __peek_collect_true:w .. 1181, 32145
 - __peek_execute_branches_...: . 1181
 - __peek_execute_branches_catcode: 592, 11622, 32146
 - __peek_execute_branches_catcode_aux: 11622
 - __peek_execute_branches_catcode_auxii:N 11622
 - __peek_execute_branches_catcode_auxiii: 11622
 - __peek_execute_branches_charcode: 592, 11622, 32148
 - __peek_execute_branches_meaning: 592, 11614, 32150
 - __peek_execute_branches_N_type: 11692
 - __peek_false:w 593, 1181, 11552, 11570, 11581, 11595, 11619, 11642, 11652, 11709, 11722, 32157

- __peek_false_aux:n [1181](#), [32158](#), [32159](#)
- __peek_N_type:w [11692](#)
- __peek_N_type_aux:nw [11692](#)
- __peek_remove_spaces: [11568](#)
- \l_peek_search_tl [589](#), [591](#), [1181](#),
[11551](#), [11588](#), [11639](#), [11649](#), [32155](#)
- \l_peek_search_token
[589](#), [1181](#), [11550](#), [11587](#), [11616](#), [32154](#)
- __peek_tmp:w
..... [11552](#), [11566](#), [11693](#), [11715](#)
- __peek_token_generic:NNTF
..... [592](#), [593](#), [11602](#),
[11604](#), [11606](#), [11726](#), [11730](#), [11732](#)
- __peek_token_generic_aux:NNTF .
..... [11584](#), [11603](#), [11609](#)
- __peek_token_remove_generic:NNTF
..... [592](#), [11602](#), [11610](#), [11612](#)
- __peek_true:w [593](#),
[1181](#), [11552](#), [11594](#), [11617](#), [11640](#),
[11650](#), [11707](#), [11721](#), [11722](#), [32164](#)
- __peek_true_aux:w [590](#),
[590](#), [11552](#), [11565](#), [11572](#), [11573](#),
[11589](#), [11603](#), [32165](#), [32166](#), [32184](#)
- __peek_true_remove:w
[590](#), [590](#), [11563](#), [11578](#), [11609](#), [32189](#)
- __peek_use_none_delimit_by_s_-
stop:w [593](#), [11558](#), [11705](#)
- \penalty [510](#)
- \pi [17597](#), [17598](#)
- pi [215](#)
- \pm [19063](#), [19064](#)
- \postbreakpenalty [1246](#), [2070](#)
- \postdisplaypenalty [511](#)
- \postexhyphenchar [986](#), [1839](#)
- \posthyphenchar [987](#), [1840](#)
- \prebinoppenalty [988](#), [1841](#)
- \prebreakpenalty [1247](#), [2071](#)
- \predisplaydirection [653](#), [1524](#)
- \predisplaygapfactor [989](#), [1842](#)
- \predisplaypenalty [512](#)
- \predisplaysize [513](#)
- \preexhyphenchar [990](#), [1844](#)
- \prehyphenchar [991](#), [1845](#)
- \prerelpenalty [992](#), [1846](#)
- \pretolerance [514](#)
- \prevdepth [515](#)
- \prevgraf [516](#)
- prg commands:
- \prg_break:
..... [113](#), [461](#), [499](#), [500](#), [604](#), [605](#),
[1029](#), [2914](#), [5132](#), [6050](#), [6066](#), [6184](#),
[6234](#), [6340](#), [6344](#), [6386](#), [6481](#), [6528](#),
[6581](#), [6587](#), [6818](#), [6899](#), [7071](#), [7212](#),
[8472](#), [8505](#), [8548](#), [9070](#), [9864](#), [12008](#),
[12029](#), [12058](#), [14068](#), [16696](#), [16705](#),
[18726](#), [18746](#), [18747](#), [18959](#), [18960](#),
[18973](#), [19073](#), [19074](#), [19075](#), [22467](#),
[22519](#), [22743](#), [23253](#), [23328](#), [23664](#),
[23738](#), [23768](#), [23769](#), [23770](#), [23771](#),
[23772](#), [23773](#), [24131](#), [24135](#), [26042](#),
[26069](#), [31843](#), [31849](#), [31917](#), [32660](#)
- \prg_break:n
..... [113](#), [113](#), [2914](#), [5134](#), [5954](#),
[5960](#), [5972](#), [8346](#), [8485](#), [9080](#), [9864](#),
[11903](#), [16469](#), [16712](#), [25604](#), [32662](#)
- \prg_break_point: . . [113](#), [113](#), [658](#),
[937](#), [938](#), [944](#), [1173](#), [2914](#), [5122](#),
[5955](#), [5961](#), [6051](#), [6067](#), [6185](#), [6235](#),
[6341](#), [6345](#), [6387](#), [6482](#), [6529](#), [6582](#),
[6588](#), [6819](#), [7019](#), [7176](#), [8343](#), [8473](#),
[8505](#), [8548](#), [8585](#), [8592](#), [9075](#), [9864](#),
[11898](#), [11993](#), [12029](#), [12058](#), [14041](#),
[16463](#), [16697](#), [16706](#), [18727](#), [18748](#),
[18961](#), [19077](#), [22468](#), [22519](#), [22751](#),
[23081](#), [23122](#), [23246](#), [23253](#), [23587](#),
[23739](#), [23775](#), [24109](#), [25605](#), [25915](#),
[26063](#), [31844](#), [31917](#), [32655](#), [32656](#)
- \prg_break_point:Nn
. [40](#), [112](#), [112](#), [347](#), [500](#), [517](#), [678](#),
[1194](#), [2905](#), [4729](#), [4747](#), [4757](#), [4772](#),
[5524](#), [5550](#), [5570](#), [8506](#), [8541](#), [8549](#),
[8566](#), [9122](#), [9864](#), [10572](#), [10586](#),
[10606](#), [10624](#), [12030](#), [12046](#), [12059](#),
[13225](#), [13244](#), [14858](#), [19146](#), [23716](#),
[31897](#), [31906](#), [32653](#), [32654](#), [32659](#)
- \prg_do_nothing:
..... [9](#), [113](#), [391](#), [442](#), [490](#),
[552](#), [567](#), [597](#), [748](#), [918](#), [985](#), [1032](#),
[2903](#), [2914](#), [3231](#), [3623](#), [3650](#), [3749](#),
[3750](#), [3751](#), [4211](#), [4212](#), [4415](#), [5340](#),
[5342](#), [6116](#), [7069](#), [8147](#), [8154](#), [8438](#),
[8440](#), [10002](#), [10217](#), [10223](#), [10231](#),
[10386](#), [10585](#), [10593](#), [10742](#), [10746](#),
[10753](#), [11804](#), [11812](#), [11821](#), [13271](#),
[13571](#), [13894](#), [16990](#), [17024](#), [17050](#),
[17058](#), [18611](#), [22448](#), [23168](#), [23326](#),
[23327](#), [23558](#), [23607](#), [24430](#), [24473](#),
[24474](#), [24481](#), [24482](#), [26134](#), [26297](#)
- \prg_generate_conditional_-
variant:Nnn [106](#), [3843](#),
[4032](#), [4054](#), [4572](#), [4582](#), [4593](#), [4616](#),
[4636](#), [4647](#), [4721](#), [5018](#), [5039](#), [5428](#),
[5441](#), [5449](#), [5480](#), [8279](#), [8347](#), [8441](#),
[8443](#), [8457](#), [8459](#), [8461](#), [8463](#), [9620](#),
[10404](#), [10418](#), [10419](#), [10562](#), [10564](#),
[11937](#), [11938](#), [11986](#), [12010](#), [12021](#),
[13077](#), [27127](#), [27129](#), [27133](#), [27758](#)
- \prg_map_break:Nn

112, 112, 347, 404, 564, 606, 1194,
 2905, 4785, 4787, 5583, 5585, 8496,
 8498, 9864, 10641, 10643, 12069,
 12071, 13208, 13210, 32657, 32659
 \prg_new_conditional:Nnn
 104, 2280, 9570
 \prg_new_conditional:Npnn .. 104,
 104, 106, 318, 582, 592, 2263, 2811,
 3502, 4016, 4024, 4034, 4044, 4193,
 4564, 4574, 4584, 4600, 4608, 4651,
 4667, 4678, 5003, 5020, 5041, 5076,
 5093, 5104, 5421, 5430, 5435, 5951,
 5958, 5973, 5981, 6668, 6702, 6721,
 8271, 8891, 8944, 8982, 8990, 9538,
 9543, 9570, 9612, 9644, 9704, 9719,
 9730, 9745, 9755, 9851, 9853, 9855,
 9857, 10233, 10515, 11312, 11317,
 11322, 11327, 11334, 11340, 11346,
 11351, 11356, 11361, 11366, 11371,
 11376, 11381, 11388, 11403, 11408,
 11443, 11489, 11981, 11988, 12097,
 13142, 14262, 14674, 14679, 14976,
 14984, 16235, 16242, 16880, 18038,
 18863, 18871, 18887, 24223, 24243,
 24265, 24311, 24335, 27123, 27125,
 27131, 27748, 29503, 30374, 31591
 \prg_new_eq_conditional:NNn
 105, 2396, 4300, 4301,
 5391, 5393, 5395, 5397, 8176, 8178,
 8657, 8658, 8659, 8660, 8661, 8662,
 8839, 8841, 9570, 9640, 9642, 10322,
 10324, 10511, 10513, 11977, 11979,
 14605, 14607, 14950, 14952, 15046,
 15048, 18861, 18862, 27071, 27073
 \prg_new_protected_conditional:Nnn
 104, 2280, 9570
 \prg_new_protected_conditional:Npnn
 104, 2263, 4618, 4638,
 5443, 5451, 6090, 6099, 8328, 8437,
 8439, 8445, 8448, 8451, 8454, 9570,
 9980, 10395, 10405, 10407, 10529,
 10533, 11917, 11927, 12012, 13068,
 13162, 13182, 13873, 14011, 14190,
 14192, 14194, 14196, 14233, 14322,
 24657, 26438, 26443, 26456, 26458
 \prg_replicate:nn
 49, 81, 111, 539, 723,
 9803, 12211, 12398, 12420, 13403,
 16416, 16542, 20291, 21144, 21452,
 21708, 21754, 21791, 22314, 22322,
 22781, 22884, 23835, 24436, 25173,
 25534, 25560, 25707, 25715, 26139,
 26601, 26606, 26613, 26716, 26721
 \prg_return_false: . 105, 106, 328,
 411, 495, 512, 561, 561, 1044, 2257,
 2323, 2331, 2482, 2487, 2500, 2505,
 2513, 2530, 2814, 3512, 4021, 4029,
 4040, 4050, 4197, 4569, 4579, 4590,
 4605, 4613, 4628, 4644, 4658, 4674,
 4689, 5015, 5036, 5054, 5062, 5072,
 5085, 5099, 5113, 5426, 5433, 5439,
 5447, 5455, 5956, 5962, 5978, 5994,
 6097, 6106, 6672, 6675, 6678, 6705,
 6708, 6725, 6728, 6731, 8276, 8342,
 8361, 8889, 8921, 8926, 8949, 8987,
 8995, 9541, 9548, 9570, 9617, 9649,
 9709, 9725, 9735, 9751, 9761, 9852,
 9854, 9856, 9858, 9984, 9992, 10249,
 10252, 10398, 10412, 10518, 10553,
 10559, 11315, 11320, 11325, 11330,
 11337, 11344, 11349, 11354, 11359,
 11364, 11369, 11374, 11379, 11384,
 11401, 11406, 11411, 11416, 11449,
 11452, 11464, 11493, 11518, 11535,
 11544, 11925, 11935, 11984, 12004,
 12019, 12100, 13075, 13151, 13165,
 13185, 13882, 14016, 14045, 14203,
 14225, 14239, 14277, 14286, 14297,
 14319, 14326, 14677, 14696, 14711,
 14712, 14980, 14987, 16240, 16248,
 16891, 16893, 18053, 18065, 18868,
 18882, 18895, 24237, 24248, 24251,
 24256, 24260, 24261, 24269, 24272,
 24277, 24280, 24317, 24320, 24341,
 24344, 24664, 24669, 26484, 27124,
 27126, 27132, 27754, 27756, 29513,
 29516, 30377, 30381, 30384, 31596
 \prg_return_true: .. 105, 106, 328,
 398, 411, 412, 495, 601, 655, 1042,
 1044, 2257, 2323, 2331, 2485, 2502,
 2510, 2515, 2528, 2533, 2814, 3504,
 3512, 4019, 4027, 4038, 4048, 4197,
 4567, 4577, 4588, 4603, 4611, 4626,
 4644, 4657, 4672, 4687, 5013, 5034,
 5052, 5070, 5083, 5101, 5112, 5426,
 5433, 5439, 5447, 5455, 5972, 5976,
 5984, 5997, 6097, 6106, 6672, 6678,
 6710, 6725, 6731, 8274, 8346, 8364,
 8921, 8947, 8985, 8993, 9541, 9546,
 9570, 9615, 9647, 9707, 9723, 9733,
 9749, 9759, 9852, 9854, 9856, 9858,
 10005, 10245, 10248, 10254, 10401,
 10415, 10519, 10549, 10559, 11315,
 11320, 11325, 11330, 11337, 11344,
 11349, 11354, 11359, 11364, 11369,
 11374, 11379, 11384, 11400, 11406,
 11414, 11463, 11516, 11542, 11923,
 11933, 11984, 12006, 12017, 12100,

- 13073, 13149, 13154, 13156, 13168,
 13188, 13880, 14017, 14059, 14204,
 14240, 14275, 14284, 14295, 14325,
 14677, 14712, 14979, 14988, 16239,
 16247, 16884, 16889, 18048, 18071,
 18866, 18884, 18893, 24226, 24240,
 24248, 24251, 24256, 24260, 24272,
 24277, 24280, 24315, 24339, 24660,
 24666, 26482, 27124, 27126, 27132,
 27753, 29514, 30386, 30390, 31594
 \prg_set_conditional:Nnn
 104, 2280, 9570
 \prg_set_conditional:Npnn
 104, 105, 106, 2263,
 2479, 2491, 2507, 2519, 9570, 14313
 \prg_set_eq_conditional:NNn
 105, 2396, 9570
 \prg_set_protected_conditional:Nnn
 104, 2280, 9570
 \prg_set_protected_conditional:Npnn
 104, 2263, 9570, 14026
 prg internal commands:
 __prg_break: 32653
 __prg_break:n 32653
 __prg_break_point: 32653
 __prg_break_point:Nn 347, 1194, 32653
 __prg_generate_conditional:nnNNNnnn
 2275, 2300, 2309
 __prg_generate_conditional:NNnnnnNw
 2309
 __prg_generate_conditional_
 count:NNNnn 2280
 __prg_generate_conditional_
 count:nnNNNnn 2280
 __prg_generate_conditional_
 fast:nw 328, 329, 2309
 __prg_generate_conditional_
 parm:NNNpnn 2263
 __prg_generate_conditional_
 test:w 2309
 __prg_generate_F_form:wNNnnnnN 2352
 __prg_generate_p_form:wNNnnnnN .
 328, 2352
 __prg_generate_T_form:wNNnnnnN 2352
 __prg_generate_TF_form:wNNnnnnN
 2352
 __prg_map_break:Nn 1194, 32653
 __prg_p_true:w 330, 2352
 __prg_replicate:N 9803
 __prg_replicate 9803
 __prg_replicate_0:n 9803
 __prg_replicate_1:n 9803
 __prg_replicate_2:n 9803
 __prg_replicate_3:n 9803
 __prg_replicate_4:n 9803
 __prg_replicate_5:n 9803
 __prg_replicate_6:n 9803
 __prg_replicate_7:n 9803
 __prg_replicate_8:n 9803
 __prg_replicate_9:n 9803
 __prg_replicate_first:N 9803
 __prg_replicate_first-:n ... 9803
 __prg_replicate_first_0:n ... 9803
 __prg_replicate_first_1:n ... 9803
 __prg_replicate_first_2:n ... 9803
 __prg_replicate_first_3:n ... 9803
 __prg_replicate_first_4:n ... 9803
 __prg_replicate_first_5:n ... 9803
 __prg_replicate_first_6:n ... 9803
 __prg_replicate_first_7:n ... 9803
 __prg_replicate_first_8:n ... 9803
 __prg_replicate_first_9:n ... 9803
 __prg_set_eq_conditional:NNNn 2396
 __prg_set_eq_conditional:nnNNnNNw
 2404, 2412
 __prg_set_eq_conditional_F_
 form:nnn 2412
 __prg_set_eq_conditional_F_
 form:wNnnnn 2449
 __prg_set_eq_conditional_
 loop:nnnnNw 2412
 __prg_set_eq_conditional_p_
 form:nnn 2412
 __prg_set_eq_conditional_p_
 form:wNnnnn 2443
 __prg_set_eq_conditional_T_
 form:nnn 2412
 __prg_set_eq_conditional_T_
 form:wNnnnn 2447
 __prg_set_eq_conditional_TF_
 form:nnn 2412
 __prg_set_eq_conditional_TF_
 form:wNnnnn 2445
 __prg_use_none_delimit_by_q_
 recursion_stop:w
 2261, 2338, 2417, 2422, 2429
 \primitive 882, 1670
 prop commands:
 \c_empty_prop 149,
 596, 11740, 11750, 11754, 11757, 11983
 \prop_clear:N 143, 143,
 11753, 11760, 11780, 11783, 11788,
 11791, 11796, 11799, 25871, 28534
 \prop_clear_new:N 143, 11759
 \prop_const_from_keyval:Nn
 144, 11778, 27717, 27724
 \prop_count:N 145, 11907, 31825
 \prop_gc_clear:N 143, 11753, 11763

- \prop_gclear_new:N
..... [143](#), [1078](#), [11759](#), [27791](#), [27792](#)
- \prop_get:Nn [113](#), [32400](#), [32402](#)
- \prop_get:NnN [38](#), [39](#), [144](#),
[145](#), [11864](#), [28780](#), [28784](#), [28863](#), [28867](#)
- \prop_get:NnNTF [144](#), [146](#), [146](#), [6157](#),
[12012](#), [12507](#), [12527](#), [12582](#), [27978](#)
- \prop_gpop:NnN [145](#), [11872](#)
- \prop_gpop:NnNTF [145](#), [146](#), [11917](#)
- .prop_gput:N [187](#), [15768](#)
- \prop_gput:Nnn
..... [144](#), [5933](#), [5934](#), [5935](#), [5936](#),
[5937](#), [5938](#), [5939](#), [5940](#), [5941](#), [5942](#),
[5943](#), [5944](#), [5945](#), [5946](#), [5947](#), [11939](#),
[12294](#), [12296](#), [13057](#), [13111](#), [13290](#),
[13328](#), [28004](#), [28022](#), [28057](#), [28088](#)
- \prop_gput_if_new:Nnn ... [144](#), [11960](#)
- \prop_gremove:Nn
..... [145](#), [11848](#), [13122](#), [13338](#)
- \prop_gset_eq:NN [143](#), [11757](#), [11765](#),
[11790](#), [27793](#), [27795](#), [27956](#), [27958](#),
[27995](#), [27997](#), [28244](#), [28412](#), [28453](#)
- \prop_gset_from_keyval:Nn [143](#), [11778](#)
- \prop_if_empty:NTF . [145](#), [11981](#), [31822](#)
- \prop_if_empty_p:N [145](#), [11981](#)
- \prop_if_exist:NTF
..... [145](#), [11760](#), [11763](#), [11977](#), [15562](#)
- \prop_if_exist_p:N [145](#), [11977](#)
- \prop_if_in:NnNTF
..... [146](#), [11988](#), [12299](#), [12310](#)
- \prop_if_in_p:Nn [146](#), [11988](#)
- \prop_item:Nn [145](#),
[147](#), [11894](#), [12300](#), [12311](#), [32401](#), [32403](#)
- \prop_log:N [148](#), [12072](#)
- \prop_map_break:
..... [147](#), [605](#), [12030](#), [12046](#), [12059](#), [12068](#)
- \prop_map_break:n [148](#), [12068](#)
- \prop_map_function:NN
.. [147](#), [147](#), [264](#), [603](#), [605](#), [11912](#),
[12023](#), [12082](#), [13136](#), [13352](#), [28938](#)
- \prop_map_inline:Nn
..... [147](#), [12039](#), [26623](#),
[28254](#), [28256](#), [28259](#), [28279](#), [28281](#),
[28355](#), [28372](#), [28433](#), [28435](#), [28439](#),
[28441](#), [28621](#), [28640](#), [28832](#), [28841](#)
- \prop_map_tokens:Nn
..... [147](#), [147](#), [501](#), [12054](#)
- \prop_new:N
... [143](#), [143](#), [5932](#), [11747](#), [11760](#),
[11763](#), [11773](#), [11774](#), [11775](#), [11776](#),
[11777](#), [12293](#), [12295](#), [12322](#), [12479](#),
[13044](#), [13277](#), [15562](#), [25792](#), [25793](#),
[28232](#), [28233](#), [28234](#), [28704](#), [28745](#)
- \prop_pop:NnN [144](#), [11872](#)
- \prop_pop:NnNTF [144](#), [146](#), [11917](#)
- .prop_put:N [187](#), [15768](#)
- \prop_put:Nnn [144](#),
[368](#), [595](#), [595](#), [11830](#), [11939](#), [12555](#),
[12571](#), [12588](#), [26029](#), [28001](#), [28019](#),
[28038](#), [28055](#), [28086](#), [28290](#), [28292](#),
[28298](#), [28300](#), [28309](#), [28315](#), [28323](#),
[28382](#), [28390](#), [28480](#), [28486](#), [28494](#),
[28501](#), [28645](#), [28705](#), [28707](#), [28709](#),
[28711](#), [28713](#), [28715](#), [28717](#), [28719](#),
[28721](#), [28723](#), [28725](#), [28727](#), [28729](#),
[28731](#), [28733](#), [28735](#), [28737](#), [28739](#)
- \prop_put_if_new:Nnn [144](#), [11960](#)
- \prop_rand_key_value:N ... [265](#), [31820](#)
- \prop_remove:N [145](#), [11848](#),
[12552](#), [12567](#), [28827](#), [28830](#), [28834](#)
- \prop_set_eq:NN [143](#), [11754](#), [11765](#),
[11782](#), [26040](#), [27944](#), [27946](#), [27988](#),
[27990](#), [28241](#), [28250](#), [28252](#), [28405](#),
[28429](#), [28431](#), [28450](#), [28578](#), [28822](#)
- \prop_set_from_keyval:Nn
..... [143](#), [597](#), [11778](#)
- \prop_show:N [148](#), [12072](#)
- \g_tmpa_prop [148](#), [11773](#)
- \l_tmpa_prop [148](#), [11773](#)
- \g_tmpb_prop [148](#), [11773](#)
- \l_tmpb_prop [148](#), [11773](#)
- prop internal commands:
 __prop_count:nn [11907](#)
 __prop_from_keyval:n [11778](#)
 __prop_from_keyval_key:n [11778](#)
 __prop_from_keyval_key:w [597](#), [11778](#)
 __prop_from_keyval_loop:w ... [11778](#)
 __prop_from_keyval_split:Nw . [11778](#)
 __prop_from_keyval_value:n .. [11778](#)
 __prop_from_keyval_value:w
 [597](#), [11778](#)
 __prop_if_in:N [603](#), [11988](#)
 __prop_if_in:nwn [603](#), [11988](#)
 __prop_if_recursion_tail_stop:n
 [11745](#), [11809](#)
 \l__prop_internal_prop ... [11777](#),
 [11780](#), [11782](#), [11783](#), [11788](#), [11790](#),
 [11791](#), [11796](#), [11798](#), [11799](#), [11830](#)
 \l__prop_internal_tl
 [602](#), [11736](#), [11739](#),
 [11943](#), [11949](#), [11950](#), [11966](#), [11973](#)
 __prop_item:Nn:nwn [600](#)
 __prop_item:Nn:nwn [11894](#)
 __prop_map_function:Nwn [12023](#)
 __prop_map_tokens:nwn [12054](#)
 __prop_pair:wn
 [594](#), [594](#), [594](#), [599](#), [603](#),
 [604](#), [605](#), [605](#), [11736](#), [11737](#), [11842](#),

- 11845, 11897, 11900, 11945, 11968,
 11991, 11995, 12029, 12032, 12042,
 12044, 12049, 12058, 12061, 31830
 __prop_put:NNnn 11939
 __prop_put_if_new:NNnn 11960
 __prop_rand_item:w 31820
 __prop_show:NN . 12072, 12074, 12076
 __prop_split:NnTF
 595, 602, 602, 603, 11837,
 11850, 11856, 11866, 11874, 11883,
 11919, 11929, 11948, 11971, 12014
 __prop_split_aux:NnTF 11837
 __prop_split_aux:w 599, 11837
 __prop_use_i_delimit_by_s_-
 stop:nw 31819, 31833
 \protect 1128, 13470,
 17531, 29800, 29821, 29823, 31151
 \protected 207,
 209, 211, 236, 654, 1525, 11477, 11479
 \protrudechars 1030, 1693
 \ProvidesExplClass 7
 \ProvidesExplFile 7, 32483, 32500
 \ProvidesExplFileAux 32486, 32488
 \ProvidesExplPackage 7
 \ProvidesFile 32491, 32492
 pt 216
 ptex commands:
 \ptex_autospacing:D 2044
 \ptex_autoxspacing:D 2045
 \ptex_dtou:D 2046
 \ptex_epTeXversion:D 2048
 \ptex_euc:D 2049
 \ptex_ifdbbox:D 2050
 \ptex_ifddir:D 2051
 \ptex_ifmdir:D 2052
 \ptex_iftbody:D 2053
 \ptex_iftdir:D 2054
 \ptex_ifybox:D 2055
 \ptex_ifydir:D 2056
 \ptex_inhibitglue:D 2057
 \ptex_inhibitxspcode:D 2058
 \ptex_inputencoding:D 2047
 \ptex_jcharwidowpenalty:D 2059
 \ptex_jfam:D 2060
 \ptex_jfont:D 2061
 \ptex_jis:D 2062
 \ptex_kanjiskip:D 2063
 \ptex_kansuji:D 2064
 \ptex_kansujichar:D 2065
 \ptex_kcatcode:D 2066
 \ptex_kuten:D 2067
 \ptex_noautospacing:D 2068
 \ptex_noautoxspacing:D 2069
 \ptex_postbreakpenalty:D 2070
 \ptex_prebreakpenalty:D 2071
 \ptex_ptexminorversion:D 2072
 \ptex_ptexrevision:D 2073
 \ptex_ptexversion:D 2074
 \ptex_showmode:D 2075
 \ptex_sjis:D 2076
 \ptex_tate:D 2077
 \ptex_tbaselineshift:D 2078
 \ptex_tfont:D 2079
 \ptex_xkanjiskip:D 2080
 \ptex_xspcode:D 2081
 \ptex_ybaselineshift:D 2082
 \ptex_yoko:D 2083
 \ptexminorversion 1248, 2072
 \ptexrevision 1249, 2073
 \ptexversion 1250, 2074
 \pxdimen 1031, 1694
- Q
- quark commands:
- \q_mark 39, 949, 3964
 \q_nil 21,
 21, 39, 39, 39, 58, 325, 377, 380,
 381, 2219, 2222, 3964, 4018, 4037,
 4043, 4058, 4059, 4065, 4089, 4093
 \q_no_value 38, 39, 39, 39, 77, 77, 77,
 77, 77, 77, 83, 83, 83, 116, 125, 144,
 144, 145, 158, 158, 164, 164, 165,
 165, 166, 166, 377, 379, 496, 497,
 556, 600, 600, 3964, 4026, 4047,
 4053, 8352, 8360, 8372, 8398, 9978,
 10361, 10376, 11868, 11879, 11888,
 13159, 13172, 13871, 14008, 14040,
 14183, 14185, 14187, 14189, 14231
 \quark_if_nil:n 380
 \quark_if_nil:NnTF 39, 4016
 \quark_if_nil:NnTF .. 39, 378, 381, 4034
 \quark_if_nil_p:N 39, 4016
 \quark_if_nil_p:n 39, 4034
 \quark_if_no_value:NnTF .. 39, 4016,
 14042, 28782, 28786, 28865, 28869
 \quark_if_no_value:NnTF 39, 4034
 \quark_if_no_value_p:N 39, 4016
 \quark_if_no_value_p:n 39, 4034
 \quark_if_recursion_tail_break:N
 32404
 \quark_if_recursion_tail_break:n
 32406
 \quark_if_recursion_tail_-
 break:Nn 40, 381, 4004
 \quark_if_recursion_tail_-
 break:nN 40, 381, 4004
 \quark_if_recursion_tail_stop:N .
 40,

- [317](#), [381](#), [1125](#), [3972](#), [29362](#), [30948](#),
[30979](#), [31246](#), [31258](#), [31320](#), [31371](#)
`\quark_if_recursion_tail_stop:n` .
..... [40](#), [317](#), [379](#), [381](#), [3986](#), [30699](#)
`\quark_if_recursion_tail_stop-`
do:Nn [40](#), [317](#), [381](#), [3972](#)
`\quark_if_recursion_tail_stop-`
do:nn [40](#), [317](#), [381](#), [3986](#)
`\quark_new:N`
... [38](#), [317](#), [318](#), [383](#), [3959](#), [3964](#),
[3965](#), [3966](#), [3967](#), [3968](#), [3969](#), [3971](#),
[4379](#), [4380](#), [4381](#), [4382](#), [4383](#), [4895](#),
[4896](#), [5284](#), [5285](#), [5931](#), [8692](#), [8693](#),
[9607](#), [9608](#), [10209](#), [10210](#), [10803](#),
[11743](#), [11744](#), [13296](#), [13762](#), [13764](#),
[13765](#), [15313](#), [15314](#), [15317](#), [15318](#),
[23885](#), [23890](#), [29379](#), [29381](#), [29382](#)
`\q_recursion_stop` [21](#),
[21](#), [40](#), [40](#), [40](#), [40](#), [40](#), [41](#), [325](#), [378](#),
[2221](#), [2225](#), [3968](#), [29370](#), [30921](#),
[30968](#), [31001](#), [31300](#), [31368](#), [31586](#)
`\q_recursion_tail`
.. [39](#), [40](#), [40](#), [40](#), [40](#), [40](#), [41](#), [378](#),
[378](#), [3968](#), [3974](#), [3980](#), [3989](#), [3996](#),
[4001](#), [4006](#), [4013](#), [29370](#), [30920](#),
[30967](#), [31000](#), [31299](#), [31367](#), [31585](#)
`\q_stop` [21](#),
[21](#), [33](#), [38](#), [38](#), [39](#), [39](#), [54](#), [325](#),
[377](#), [2220](#), [2223](#), [3964](#), [4991](#), [29248](#),
[29252](#), [29263](#), [29282](#), [29287](#), [29298](#),
[29302](#), [29314](#), [29315](#), [29321](#), [29323](#),
[29324](#), [29326](#), [29329](#), [29345](#), [29353](#)
`\s_stop` [42](#), [42](#), [386](#), [4247](#), [4256](#)
quark internal commands:
`\s_bool_mark` ... [31781](#), [31802](#), [31816](#)
`\q_bool_recursion_stop`
..... [9607](#), [9610](#), [9703](#), [9729](#)
`\q_bool_recursion_tail`
..... [9607](#), [9703](#), [9729](#)
`\s_bool_stop` ... [31781](#), [31802](#), [31816](#)
`\q_char_no_value` [10803](#), [11197](#)
`\s_char_stop`
.. [10802](#), [11151](#), [11156](#), [11197](#), [11199](#)
`\q_clist_mark` [565](#)
`\s_clist_mark` [552](#), [557](#), [559](#), [560](#),
[561](#), [10205](#), [10238](#), [10239](#), [10256](#),
[10378](#), [10388](#), [10392](#), [10414](#), [10470](#),
[10476](#), [10490](#), [10502](#), [10503](#), [10504](#),
[10507](#), [10508](#), [10509](#), [10518](#), [10519](#),
[10528](#), [10682](#), [10683](#), [10695](#), [10696](#)
`\q_clist_recursion_stop`
.... [564](#), [10209](#), [10224](#), [10623](#), [10659](#)
`\q_clist_recursion_tail`
..... [562](#), [10209](#), [10224](#),
[10571](#), [10585](#), [10605](#), [10623](#), [10659](#)
`\q_clist_stop` [565](#)
`\s_clist_stop`
..... [560](#), [10205](#), [10207](#), [10208](#),
[10363](#), [10366](#), [10378](#), [10381](#), [10389](#),
[10392](#), [10400](#), [10414](#), [10476](#), [10504](#),
[10507](#), [10508](#), [10520](#), [10528](#), [10684](#),
[10695](#), [10696](#), [10697](#), [10723](#), [10757](#)
`\s_color_stop` [28978](#), [28980](#), [28982](#),
[28983](#), [28984](#), [28986](#), [28988](#), [28990](#)
`\s_cs_mark` [334](#),
[367](#), [368](#), [2469](#), [2470](#), [2473](#), [2474](#),
[2475](#), [3532](#), [3562](#), [3563](#), [3565](#), [3571](#),
[3575](#), [3597](#), [3606](#), [3625](#), [3653](#), [3656](#),
[3664](#), [3679](#), [3711](#), [3725](#), [3729](#), [3738](#),
[3757](#), [3766](#), [3771](#), [3860](#), [3863](#), [3879](#)
`\q_cs_nil` [3866](#)
`\q_cs_recursion_stop`
..... [3534](#), [3538](#), [3549](#), [3859](#)
`\s_cs_stop` [334](#), [368](#),
[2470](#), [2473](#), [2474](#), [2475](#), [3532](#), [3535](#),
[3536](#), [3566](#), [3575](#), [3601](#), [3653](#), [3656](#),
[3660](#), [3668](#), [3674](#), [3683](#), [3689](#), [3691](#),
[3711](#), [3733](#), [3738](#), [3768](#), [3771](#), [3860](#)
`\s_deprecation_mark`
..... [32196](#), [32199](#), [32201](#)
`\s_deprecation_stop`
.. [32196](#), [32199](#), [32201](#), [32221](#), [32230](#)
`\s_dim_mark` [14577](#), [14740](#), [14747](#)
`\s_dim_stop` [14577](#),
[14579](#), [14687](#), [14711](#), [14740](#), [14747](#)
`\q_file_nil`
.. [13762](#), [13846](#), [13860](#), [13958](#), [13964](#)
`\q_file_recursion_stop`
.. [13764](#), [13775](#), [13779](#), [13788](#), [13828](#)
`\q_file_recursion_tail`
..... [13764](#), [13775](#), [13828](#)
`\s_file_stop` [13724](#), [13729](#), [13761](#),
[13846](#), [13847](#), [13852](#), [13858](#), [13860](#),
[13861](#), [13958](#), [13959](#), [13964](#), [13966](#),
[13968](#), [14403](#), [14407](#), [14421](#), [14436](#),
[14438](#), [14496](#), [14499](#), [14506](#), [14508](#)
`\s_fp` [728](#), [730](#), [734](#), [735](#), [758](#), [764](#),
[765](#), [768](#), [782](#), [784](#), [785](#), [814](#), [817](#),
[818](#), [819](#), [821](#), [827](#), [829](#), [918](#), [16575](#),
[16588](#), [16589](#), [16590](#), [16591](#), [16592](#),
[16602](#), [16607](#), [16609](#), [16610](#), [16625](#),
[16638](#), [16641](#), [16643](#), [16653](#), [16665](#),
[16685](#), [16702](#), [16705](#), [16712](#), [16719](#),
[16735](#), [16762](#), [16868](#), [16870](#), [16872](#),
[16873](#), [16874](#), [16876](#), [16877](#), [16878](#),
[16880](#), [16896](#), [17068](#), [17073](#), [17300](#),
[17354](#), [17363](#), [17365](#), [18043](#), [18201](#),
[18687](#), [18702](#), [18726](#), [18746](#), [18747](#),

- 18881, 18906, 18907, 18921, 18922,
- 18959, 18960, 19073, 19074, 19075,
- 19084, 19100, 19104, 19168, 19169,
- 19172, 19183, 19184, 19192, 19193,
- 19195, 19196, 19197, 19199, 19200,
- 19201, 19213, 19216, 19220, 19223,
- 19243, 19293, 19296, 19299, 19319,
- 19320, 19322, 19323, 19324, 19332,
- 19335, 19346, 19347, 19349, 19358,
- 19434, 19586, 19620, 19621, 19624,
- 19705, 19843, 19851, 19853, 20030,
- 20039, 20041, 20046, 20054, 20056,
- 20058, 20061, 20564, 20576, 20578,
- 20787, 20804, 20806, 20987, 21006,
- 21008, 21009, 21012, 21029, 21032,
- 21035, 21060, 21061, 21063, 21079,
- 21168, 21181, 21183, 21186, 21191,
- 21224, 21240, 21323, 21336, 21338,
- 21351, 21353, 21366, 21368, 21381,
- 21383, 21396, 21398, 21411, 21421,
- 21922, 21938, 21939, 21943, 21954,
- 22061, 22074, 22076, 22092, 22095,
- 22105, 22128, 22139, 22141, 22155,
- 22157, 22162, 22224, 22245, 22248,
- 22278, 22299, 22302, 22352, 22368,
- 22371, 22446, 22447, 22557, 22559,
- 22591, 22857, 22865, 22868, 22947
- \s__fp<type> 758
- \s__fp_division 16583
- \s__fp_exact 16583, 16588,
- 16589, 16590, 16591, 16592, 19168
- \s__fp_expr_mark 764, 765, 768, 789,
- 793, 16578, 18250, 18263, 18345, 18389
- \s__fp_expr_stop 736,
- 16578, 16776, 18152, 18251, 18255,
- 18264, 19250, 19261, 19271, 19279
- \s__fp_invalid 16583
- \s__fp_mark 16580, 16725, 16726, 16730
- \s__fp_overflow 16583, 16609
- \s__fp_stop 734, 16580, 16582, 16626, 16702,
- 16713, 16720, 16726, 16730, 16744,
- 16763, 17571, 17575, 18082, 18087,
- 18687, 18709, 18880, 18881, 18906,
- 18907, 19073, 19074, 19075, 19242,
- 19243, 20863, 20878, 22198, 22202
- \s__fp_tuple 734,
- 16686, 16692, 16693, 16770, 16772,
- 18467, 18679, 18694, 18719, 18721,
- 18738, 18739, 18741, 18951, 18952,
- 20092, 20093, 20099, 20100, 22174
- \s__fp_underflow 16583, 16607
- \s__int_mark 8689, 8904, 8907, 8973, 8980
- \q__int_recursion_stop 8692, 9391, 9408, 9451, 9478
- \q__int_recursion_tail 8692, 9391, 9408, 9451
- \s__int_stop 512, 523,
- 8689, 8691, 8883, 8899, 8901, 8905,
- 8918, 8973, 8980, 9384, 9390, 9407
- \s__iow_mark . 13293, 13613, 13620,
- 13632, 13706, 13707, 13708, 13709
- \q__iow_nil 13296, 13499, 13506
- \s__iow_stop 13293, 13295, 13499, 13540,
- 13598, 13636, 13649, 13706, 13709
- \s__kernel_stop 2873, 2881, 2890, 2899
- \q__keys_nil 15313, 16216, 16224
- \q__keys_no_value 716, 15302, 15313, 15814,
- 15838, 15855, 15880, 15897, 15926
- \q__keys_recursion_stop 15317, 16227
- \q__keys_recursion_tail 15317, 16227
- \s__keys_stop 15312, 15356, 15358, 15378,
- 15383, 15392, 15400, 15411, 15566,
- 15970, 15979, 15989, 16158, 16178,
- 16200, 16202, 16210, 16216, 16218
- \s__keyval_mark 688, 688, 689, 689,
- 692, 15093, 15101, 15107, 15109,
- 15110, 15111, 15112, 15118, 15119,
- 15122, 15127, 15128, 15132, 15133,
- 15138, 15139, 15144, 15145, 15148,
- 15149, 15153, 15154, 15157, 15160,
- 15161, 15169, 15170, 15175, 15176,
- 15179, 15182, 15186, 15187, 15193,
- 15202, 15203, 15206, 15211, 15220,
- 15221, 15226, 15227, 15230, 15231,
- 15232, 15233, 15234, 15251, 15252,
- 15258, 15262, 15264, 15266, 15277
- \s__keyval_nil . 689, 15093, 15117,
- 15126, 15132, 15135, 15137, 15144,
- 15147, 15153, 15157, 15159, 15166,
- 15168, 15175, 15179, 15181, 15186,
- 15187, 15193, 15201, 15220, 15226,
- 15250, 15254, 15271, 15274, 15277
- \s__keyval_stop 15093, 15109, 15110,
- 15111, 15112, 15120, 15124, 15129,
- 15133, 15140, 15145, 15150, 15154,
- 15157, 15162, 15164, 15171, 15176,
- 15179, 15181, 15182, 15186, 15193,
- 15204, 15220, 15221, 15226, 15227,
- 15230, 15233, 15234, 15256, 15277
- \s__keyval_tail 688, 15093, 15101, 15105, 15106,
- 15116, 15200, 15209, 15210, 15232

- \s__msg_mark [12092](#),
[12447](#), [12512](#), [12513](#), [12518](#), [12521](#)
- \s__msg_stop ... [628](#), [12092](#), [12094](#),
[12449](#), [12453](#), [12455](#), [12514](#), [31749](#)
- \s__peek_mark
..... [11556](#), [11704](#), [11705](#), [11712](#)
- \s__peek_stop
.. [11556](#), [11558](#), [11693](#), [11706](#), [11715](#)
- \s__prg_mark [2321](#), [2323](#), [2331](#)
- \q__prg_recursion_stop
..... [331](#), [2262](#), [2327](#), [2409](#)
- \q__prg_recursion_tail
..... [331](#), [2327](#), [2337](#), [2409](#), [2428](#)
- \s__prg_stop [2348](#), [2353](#), [2372](#), [2380](#),
[2388](#), [2439](#), [2443](#), [2445](#), [2447](#), [2449](#)
- \s__prop .. [594](#), [594](#), [599](#), [605](#), [605](#),
[1172](#), [11736](#), [11736](#), [11737](#), [11740](#),
[11842](#), [11845](#), [11897](#), [11900](#), [11946](#),
[11969](#), [11991](#), [11995](#), [12029](#), [12032](#),
[12044](#), [12058](#), [12061](#), [31830](#), [31835](#)
- \s__prop_mark
.. [597](#), [599](#), [11741](#), [11817](#), [11818](#),
[11824](#), [11825](#), [11842](#), [11844](#), [11845](#)
- \q__prop_recursion_stop [11743](#), [11805](#)
- \q__prop_recursion_tail
.... [603](#), [11743](#), [11805](#), [11992](#), [12003](#)
- \s__prop_stop [597](#),
[599](#), [11741](#), [11811](#), [11818](#), [11821](#),
[11825](#), [11842](#), [11845](#), [31819](#), [31826](#)
- \s__quark [386](#), [3970](#), [4205](#), [4207](#), [4208](#),
[4219](#), [4222](#), [4227](#), [4230](#), [4232](#), [4253](#)
- __quark_if_empty_if:n ... [4034](#), [4195](#)
- __quark_if_nil:w [380](#), [4034](#)
- __quark_if_no_value:w [4034](#)
- __quark_if_recursion_tail:w ...
..... [378](#), [383](#), [3986](#), [4013](#)
- __quark_module_name:N
..... [384](#), [4062](#), [4085](#), [4200](#)
- __quark_module_name:w [4200](#)
- __quark_module_name_end:w ... [4200](#)
- __quark_module_name_loop:w .. [4200](#)
- __quark_new_conditional:Nnnn . [4061](#)
- __quark_new_conditional_aux_-
do:NNnnn [384](#), [4182](#), [4184](#), [4185](#)
- __quark_new_conditional_-
define:NNNNn [384](#), [4185](#)
- __quark_new_conditional_N:Nnnn [4181](#)
- __quark_new_conditional_n:Nnnn [4181](#)
- __quark_new_test:NNNn [4061](#)
- __quark_new_test_aux:Nn
..... [4062](#), [4063](#), [4073](#)
- __quark_new_test_aux:nnNNnnnn [4061](#)
- __quark_new_test_aux_do:nnNNnnnnNNn
..... [382](#), [383](#), [4116](#),
[4121](#), [4126](#), [4131](#), [4136](#), [4142](#), [4145](#)
- __quark_new_test_define_break_-
ifx:nnNNNNn [4143](#), [4158](#)
- __quark_new_test_define_break_-
tl:nnNNNNn [4127](#), [4158](#)
- __quark_new_test_define_-
ifx:nNnNNn [382](#), [383](#), [4132](#), [4137](#), [4158](#)
- __quark_new_test_define_-
tl:nNnNNn [382](#), [383](#), [4117](#), [4122](#), [4158](#)
- __quark_new_test_N:Nnnn [4114](#)
- __quark_new_test_n:Nnnn [4114](#)
- __quark_new_test_NN:Nnnn [4114](#)
- __quark_new_test_Nn:Nnnn [4114](#)
- __quark_new_test_nN:Nnnn [4124](#)
- __quark_new_test_nn:Nnnn [4114](#)
- \q__quark_nil [3971](#)
- __quark_quark_conditional_-
name:N [385](#), [4084](#), [4222](#)
- __quark_quark_conditional_-
name:w [385](#), [4222](#)
- __quark_test_define_aux:NNNNnnNNn
..... [383](#), [4145](#)
- __quark_tmp:w
..... [385](#), [4200](#), [4221](#), [4222](#), [4232](#)
- \q__regex_nil
..... [23890](#), [25135](#), [25153](#), [25154](#)
- \q__regex_recursion_stop
.. [23885](#), [23887](#), [23889](#), [25135](#), [25154](#)
- \s__seq
[487](#), [490](#), [491](#), [491](#), [497](#), [501](#), [502](#),
[1172](#), [8063](#), [8074](#), [8104](#), [8109](#), [8114](#),
[8119](#), [8130](#), [8158](#), [8184](#), [8192](#), [8196](#),
[8419](#), [8467](#), [8618](#), [31840](#), [31846](#), [31887](#)
- \s__seq_mark
..... [8064](#), [8606](#), [8607](#), [8621](#), [8624](#)
- \s__seq_stop [8064](#), [8372](#),
[8375](#), [8383](#), [8385](#), [8466](#), [8467](#), [8608](#),
[8621](#), [8624](#), [8626](#), [31839](#), [31840](#),
[31842](#), [31846](#), [31850](#), [31852](#), [31857](#)
- \s__skip_stop ... [14925](#), [14988](#), [14990](#)
- \s__sort_mark [940](#),
[944](#), [944](#), [946](#), [22964](#), [23171](#), [23175](#),
[23181](#), [23185](#), [23191](#), [23194](#), [23259](#),
[23260](#), [23262](#), [23299](#), [23301](#), [23304](#),
[23308](#), [23311](#), [23314](#), [23316](#), [23319](#)
- \s__sort_stop [943](#),
[944](#), [944](#), [946](#), [22964](#), [23247](#), [23256](#),
[23260](#), [23262](#), [23299](#), [23300](#), [23301](#),
[23306](#), [23308](#), [23312](#), [23314](#), [23322](#)
- \s__str [441](#),
[466](#), [469](#), [5930](#), [6066](#), [6070](#), [6270](#),
[6317](#), [6372](#), [6378](#), [6827](#), [6839](#), [6844](#),

- 6854, 6859, 6864, 6867, 6882, 6895,
6898, 7033, 7034, 7051, 7057, 7073,
7079, 7080, 7185, 7200, 7209, 7210
 - \s__str_mark
..... [420](#), [426](#), [433](#), [5280](#), 5478,
5509, 5516, 5589, 5606, 5854, 5856
 - \q__str_nil
... [467](#), [5931](#), 7018, 7025, 7040, 7067
 - \q__str_recursion_stop
..... [5284](#), 5870, 5878, 5883
 - \q__str_recursion_tail
[425](#), [5284](#), 5523, 5532, 5549, 5569, 5870
 - \s__str_stop [426](#), [430](#),
[465](#), [469](#), [470](#), [5280](#), 5282, 5283,
5375, 5478, 5509, 5516, 5589, 5598,
5604, 5606, 5612, 5629, 5648, 5710,
5767, 5779, 5817, 5833, 5840, 5848,
5850, 5854, 5856, 6066, 6072, 6114,
6119, 6127, 6340, 6344, 6353, 6362,
6386, 6395, 6744, 6746, 6754, 6840,
6876, 6990, 6992, 6996, 7008, 7148,
7150, 7154, 7166, 7175, 7182, 7203
 - \q__text_nil [29379](#), 29814, 29815
 - \q__text_recursion_stop
[29381](#), 29384, 29568, 29582, 29591,
29670, 29686, 29695, 29736, 29752,
29781, 29917, 29931, 29940, 29942,
30008, 30024, 30033, 30077, 30151,
30160, 30322, 30327, 30454, 30459,
30507, 30512, 30535, 30540, 30576,
30585, 31017, 31018, 31027, 31045,
31058, 31060, 31074, 31083, 31111
 - \q__text_recursion_tail
.... [29381](#), 29511, 29568, 29669,
29736, 29752, 29781, 29917, 29942,
30007, 30077, 31017, 31044, 31111
 - \s__text_stop
.. [29378](#), 29453, 29455, 29814, 29815
 - \s__tl [948](#), [949](#), [949](#), [950](#),
[951](#), [958](#), [958](#), [959](#), [23384](#), [23385](#),
23604, 23635, 23641, 23666, 23684,
23689, 23703, 23715, 23738, 23741
 - \q__tl_act_mark
..... [407](#), [407](#), [408](#), [4895](#), 4900, 4917
 - \q__tl_act_stop
.... [407](#), [4895](#), 4900, 4904, 4913,
4915, 4921, 4926, 4929, 4933, 4936
 - \q__tl_mark
... [395](#), [4379](#), 4484, 4486, 4488, 4490
 - \s__tl_mark [402](#),
[406](#), [406](#), 4713, 4723, 4832, 4833,
4836, 4839, 4840, 4846, 4849, 4864,
4865, 4871, 4875, 4877, 4880, [5270](#)
 - \q__tl_nil [395](#), [397](#), [398](#), [4379](#), 4510,
4586, 4587, 4597, 4598, 4981, 4982
 - \s__tl_nil
[406](#), 4863, 4867, 4885, 4888, 4891, [5270](#)
 - \q__tl_recursion_stop [4382](#)
 - \q__tl_recursion_tail
.. [4382](#), 4728, 4746, 4756, 4771, 5121
 - \q__tl_stop [395](#), [4379](#), 4509
 - \s__tl_stop
..... [393](#), [405](#), 4467, 4469, 4671,
4677, 4713, 4723, 4834, 4836, 4841,
4843, 4869, 4891, 4972, 4974, 4992,
5010, 5027, 5051, 5257, 5267, [5270](#)
 - \s__token_stop [585](#),
[587](#), [11289](#), 11393, 11396, 11426,
11460, 11497, 11501, 11507, 11530
 - \quitvmode 794, 1663
- ## R
- \r [29521](#), 31359, 31383, 31409, 31533, 31534
 - \radical 517
 - \raise 518
 - rand [215](#)
 - randint [215](#)
 - \randomseed [1032](#), 1695
 - \read 519
 - \readline [655](#), 1526
 - \readpapersizespecial [1251](#)
 - \ref [29539](#), 29547
 - regex commands:
 - \c_foo_regex [222](#)
 - \regex_(g)set:Nn [229](#)
 - \regex_const:Nn [222](#), [229](#), [26405](#)
 - \regex_count:NnN [230](#), [26448](#)
 - \regex_count:nnN [230](#), [1043](#), [26448](#)
 - \regex_extract_all:NnN ... [230](#), [26452](#)
 - \regex_extract_all:nnN
..... [223](#), [230](#), [965](#), [26452](#)
 - \regex_extract_all:NnNTF . [230](#), [26452](#)
 - \regex_extract_all:nnNTF . [230](#), [26452](#)
 - \regex_extract_once:NnN .. [230](#), [26452](#)
 - \regex_extract_once:nnN
..... [230](#), [230](#), [26452](#)
 - \regex_extract_once:NnNTF [230](#), [26452](#)
 - \regex_extract_once:nnNTF
..... [227](#), [230](#), [26452](#)
 - \regex_gset:Nn [229](#), [26405](#)
 - \regex_match:NnTF [229](#), [26438](#)
 - \regex_match:nnTF [229](#), [26438](#)
 - \regex_new:N [229](#),
[967](#), [26399](#), 26401, 26402, 26403, 26404
 - \regex_replace_all:NnN ... [231](#), [26452](#)
 - \regex_replace_all:nnN [223](#), [231](#), [26452](#)
 - \regex_replace_all:NnNTF . [231](#), [26452](#)

- \regex_replace_all:nnNTF . [231](#), [26452](#)
- \regex_replace_once:NnN . . . [231](#), [26452](#)
- \regex_replace_once:nnN
- [230](#), [231](#), [26452](#)
- \regex_replace_once:NnNTF [231](#), [26452](#)
- \regex_replace_once:nnNTF [231](#), [26452](#)
- \regex_set:Nn [229](#), [26405](#)
- \regex_show:N [229](#), [26420](#)
- \regex_show:n [222](#), [229](#), [26420](#)
- \regex_split:NnN [231](#), [26452](#)
- \regex_split:nnN [231](#), [26452](#)
- \regex_split:NnNTF [231](#), [26452](#)
- \regex_split:nnNTF [231](#), [26452](#)
- \g_tmpa_regex [231](#), [26401](#)
- \l_tmpa_regex [231](#), [26401](#)
- \g_tmpb_regex [231](#), [26401](#)
- \l_tmpb_regex [231](#), [26401](#)
- regex internal commands:
- __regex_action_cost:n
- [1010](#), [1013](#), [1021](#),
- [25522](#), [25523](#), [25531](#), [25979](#), [26005](#)
- __regex_action_free:n
- [1010](#), [1021](#), [25545](#), [25551](#),
- [25552](#), [25563](#), [25622](#), [25626](#), [25651](#),
- [25676](#), [25680](#), [25683](#), [25711](#), [25719](#),
- [25729](#), [25743](#), [25774](#), [25977](#), [25981](#)
- __regex_action_free_aux:nn . . [25981](#)
- __regex_action_free_group:n . . .
- [1010](#), [1021](#), [25572](#), [25691](#), [25694](#), [25981](#)
- __regex_action_start_wildcard: .
- [1010](#), [25456](#), [25974](#)
- __regex_action_submatch:n [1010](#),
- [25645](#), [25646](#), [25772](#), [26025](#), [26027](#)
- __regex_action_success:
- [1010](#), [25459](#), [25473](#), [26032](#)
- __regex_action_wildcard: [1025](#)
- \c_regex_all_catcodes_int
- [24295](#), [24417](#), [24507](#), [25107](#)
- __regex_anchor:N
- [979](#), [1019](#), [24736](#), [25302](#), [25734](#)
- \c_regex_ascii_lower_int
- [23884](#), [23949](#), [23955](#)
- \c_regex_ascii_max_control_int .
- [23881](#), [24065](#)
- \c_regex_ascii_max_int
- [23881](#), [24058](#), [24066](#), [24247](#)
- \c_regex_ascii_min_int
- [23881](#), [24057](#), [24064](#)
- __regex_assertion:Nn . [979](#), [1019](#),
- [24736](#), [24761](#), [24770](#), [25296](#), [25734](#)
- __regex_b_test:
- [979](#), [1019](#), [24761](#), [24770](#), [25301](#), [25734](#)
- \l_regex_balance_int [967](#),
- [1032](#), [23879](#), [25808](#), [25821](#), [25936](#),
- [25940](#), [25941](#), [26120](#), [26149](#), [26342](#),
- [26359](#), [26654](#), [26680](#), [26703](#), [26707](#),
- [26708](#), [26715](#), [26716](#), [26720](#), [26721](#)
- \g__regex_balance_intarray
- [965](#), [967](#), [23876](#), [25935](#), [26093](#), [26108](#)
- \l__regex_balance_tl
- [1032](#), [1035](#), [26048](#), [26121](#), [26150](#), [26212](#)
- __regex_branch:n
- . . . [979](#), [996](#), [1015](#), [23873](#), [24422](#),
- [24917](#), [24970](#), [25149](#), [25278](#), [25617](#)
- __regex_break_point:TF
- [968](#), [991](#), [1013](#), [23892](#),
- [23898](#), [25522](#), [25523](#), [25740](#), [25763](#)
- __regex_break_true:w
- . . [968](#), [969](#), [23892](#), [23898](#), [23903](#),
- [23910](#), [23917](#), [23923](#), [23930](#), [23938](#),
- [23985](#), [23997](#), [24014](#), [24711](#), [25755](#)
- __regex_build:N [1042](#),
- [25443](#), [26445](#), [26451](#), [26455](#), [26459](#)
- __regex_build:n [1042](#),
- [25443](#), [26440](#), [26449](#), [26454](#), [26457](#)
- __regex_build_for_cs:n [24009](#), [25461](#)
- __regex_build_new_state:
- [25453](#), [25454](#),
- [25465](#), [25466](#), [25495](#), [25504](#), [25536](#),
- [25570](#), [25575](#), [25619](#), [25634](#), [25639](#),
- [25678](#), [25697](#), [25732](#), [25736](#), [25769](#)
- \l__regex_build_tl [996](#),
- [23870](#), [24414](#), [24421](#), [24439](#), [24444](#),
- [24447](#), [24448](#), [24451](#), [24452](#), [24455](#),
- [24501](#), [24504](#), [24537](#), [24551](#), [24555](#),
- [24680](#), [24694](#), [24735](#), [24760](#), [24769](#),
- [24779](#), [24811](#), [24824](#), [24828](#), [24910](#),
- [24913](#), [24916](#), [24922](#), [24923](#), [24926](#),
- [24969](#), [25237](#), [25253](#), [25271](#), [25277](#),
- [25332](#), [25335](#), [25340](#), [25370](#), [25385](#),
- [25389](#), [25392](#), [25398](#), [26119](#), [26138](#),
- [26153](#), [26156](#), [26177](#), [26209](#), [26271](#),
- [26274](#), [26289](#), [26333](#), [26349](#), [26385](#)
- __regex_build_transition-
 left:NNN [25491](#), [25680](#), [25694](#), [25711](#)
- __regex_build_transition-
 right:nNn [25491](#),
- [25537](#), [25572](#), [25622](#), [25626](#), [25651](#),
- [25676](#), [25683](#), [25691](#), [25719](#), [25729](#)
- __regex_build_transitions-
 lazyness:NNNN
- [25502](#), [25544](#), [25550](#), [25562](#)
- \l__regex_capturing_group_int . . .
- [965](#),
- [1009](#), [1049](#), [25442](#), [25451](#), [25588](#),
- [25590](#), [25601](#), [25602](#), [25610](#), [25611](#),
- [25614](#), [26208](#), [26613](#), [26685](#), [26693](#)

```

\l_regex_case_changed_char_int .
    ..... 970,
    23919, 23922, 23933, 23936, 23937,
    23944, 23948, 23954, 25787, 25905
\c_regex_catcode_A_int ..... 24295
\c_regex_catcode_B_int ..... 24295
\c_regex_catcode_C_int ..... 24295
\c_regex_catcode_D_int ..... 24295
\c_regex_catcode_E_int ..... 24295
\c_regex_catcode_in_class_mode_
    int ..... 24285,
    24406, 24778, 24939, 25032, 25061
\g_regex_catcode_intarray ....
    ..... 965, 967, 23876, 25933, 25950
\c_regex_catcode_L_int ..... 24295
\c_regex_catcode_M_int ..... 24295
\c_regex_catcode_mode_int 24285,
    24402, 24475, 24810, 25030, 25059
\c_regex_catcode_O_int ..... 24295
\c_regex_catcode_P_int ..... 24295
\c_regex_catcode_S_int ..... 24295
\c_regex_catcode_T_int ..... 24295
\c_regex_catcode_U_int ..... 24295
\l_regex_catcodes_bool .....
    ..... 24292, 25066, 25070, 25105
\l_regex_catcodes_int ..... 980,
    24292, 24418, 24506, 24508, 24514,
    24797, 24814, 24914, 24927, 25026,
    25063, 25098, 25100, 25106, 25107
\__regex_char_if_alphanumeric:N .
    ..... 24265
\__regex_char_if_alphanumeric:NTF
    ..... 24243, 24468, 26316
\__regex_char_if_special:N ... 24243
\__regex_char_if_special:NTF ...
    ..... 24243, 24464
\g_regex_charcode_intarray ....
    ..... 965, 967, 23876, 25931, 25947
\__regex_chk_c_allowed:TF .....
    ..... 24387, 25019
\__regex_class:NnnnN .....
    ..... 979, 986, 988, 994,
    23874, 24502, 24805, 24806, 24812,
    25166, 25245, 25255, 25293, 25516
\c_regex_class_mode_int .....
    ..... 24285, 24392, 24407
\__regex_class_repeat:n .....
    ... 1013, 25526, 25532, 25548, 25557
\__regex_class_repeat:nN 25527, 25541
\__regex_class_repeat:nnN .....
    ..... 25528, 25555
\__regex_command_K: .....
    ..... 979, 25271, 25294, 25767
\__regex_compile:n ..... 24457,
    25445, 26407, 26412, 26417, 26422
\__regex_compile:w .....
    ..... 985, 24411, 24459, 25112
\__regex_compile$: ..... 24731
\__regex_compile(: ..... 24934
\__regex_compile): ..... 24973
\__regex_compile.: ..... 24702
\__regex_compile/A: ..... 24731
\__regex_compile/B: ..... 24755
\__regex_compile/b: ..... 24755
\__regex_compile/c: ..... 25018
\__regex_compile/D: ..... 24714
\__regex_compile/d: ..... 24714
\__regex_compile/G: ..... 24731
\__regex_compile/H: ..... 24714
\__regex_compile/h: ..... 24714
\__regex_compile/K: ..... 25268
\__regex_compile/N: ..... 24714
\__regex_compile/S: ..... 24714
\__regex_compile/s: ..... 24714
\__regex_compile/u: ..... 25186
\__regex_compile/V: ..... 24714
\__regex_compile/v: ..... 24714
\__regex_compile/W: ..... 24714
\__regex_compile/w: ..... 24714
\__regex_compile/Z: ..... 24731
\__regex_compile/z: ..... 24731
\__regex_compile[: ..... 24789
\__regex_compile]: ..... 24773
\__regex_compile^: ..... 24731
\__regex_compile_abort_tokens:n .
    ..... 24517, 24544, 24894, 24904
\__regex_compile_anchor:NTF .. 24731
\__regex_compile_c[:w ..... 25055
\__regex_compile_c_C:NN 25034, 25043
\__regex_compile_c_lbrack_add:N .
    ..... 25055
\__regex_compile_c_lbrack_end: 25055
\__regex_compile_c_lbrack_
    loop:NN ..... 25055
\__regex_compile_c_test:NN ... 25018
\__regex_compile_class:NN .... 24819
\__regex_compile_class:TFNN ....
    ..... 994, 24804, 24815, 24819
\__regex_compile_class_catcode:w
    ..... 24796, 24808
\__regex_compile_class_normal:w .
    ..... 24799, 24802
\__regex_compile_class_posix:NNNNw
    ..... 24838
\__regex_compile_class_posix_
    end:w ..... 24838

```

__regex_compile_class_posix_-
 loop:w [24838](#)
 __regex_compile_class_posix_-
 test:w [24792](#), [24838](#)
 __regex_compile_cs_aux:Nn ... [25121](#)
 __regex_compile_cs_aux:NNnnN [25121](#)
 __regex_compile_end:
 [985](#), [24411](#), [24484](#), [25130](#)
 __regex_compile_end_cs: [24480](#), [25121](#)
 __regex_compile_escaped:N
 [24469](#), [24486](#)
 __regex_compile_group_begin:N ..
 .. [24908](#), [24956](#), [24961](#), [24979](#), [24981](#)
 __regex_compile_group_end:
 [24908](#), [24976](#)
 __regex_compile_lparen:w
 [24943](#), [24947](#)
 __regex_compile_one:n
 [24496](#), [24646](#), [24652](#), [24706](#),
 [24717](#), [24720](#), [24730](#), [24885](#), [25137](#)
 __regex_compile_quantifier:w ...
 [24515](#), [24526](#), [24784](#), [24928](#)
 __regex_compile_quantifier*:w .
 [24560](#)
 __regex_compile_quantifier+:w .
 [24560](#)
 __regex_compile_quantifier?:w .
 [24560](#)
 __regex_compile_quantifier_-
 abort:nN
 .. [24535](#), [24570](#), [24589](#), [24602](#), [24625](#)
 __regex_compile_quantifier_-
 braced_auxi:w [24566](#)
 __regex_compile_quantifier_-
 braced_auxii:w [24566](#)
 __regex_compile_quantifier_-
 braced_auxiii:w [24566](#)
 __regex_compile_quantifier_-
 lazyness:nnN [988](#), [24547](#), [24561](#),
 [24563](#), [24565](#), [24578](#), [24598](#), [24620](#)
 __regex_compile_quantifier_-
 none: [24531](#), [24533](#), [24535](#)
 __regex_compile_range:Nw
 [24644](#), [24657](#)
 __regex_compile_raw:N
 [24337](#), [24465](#), [24469](#), [24471](#),
 [24489](#), [24494](#), [24522](#), [24637](#), [24639](#),
 [24659](#), [24705](#), [24751](#), [24787](#), [24835](#),
 [24855](#), [24873](#), [24931](#), [24936](#), [24941](#),
 [24957](#), [24967](#), [24975](#), [24993](#), [24994](#),
 [24995](#), [25001](#), [25012](#), [25013](#), [25014](#),
 [25022](#), [25077](#), [25126](#), [25198](#), [25204](#)
 __regex_compile_raw_error:N ...
 [24634](#),
 [24742](#), [24758](#), [24767](#), [25189](#), [25272](#)
 __regex_compile_special:N
 [981](#), [24465](#), [24486](#),
 [24528](#), [24549](#), [24576](#), [24581](#), [24596](#),
 [24609](#), [24643](#), [24662](#), [24822](#), [24840](#),
 [24859](#), [24879](#), [24880](#), [24949](#), [24984](#),
 [25002](#), [25045](#), [25064](#), [25191](#), [25207](#)
 __regex_compile_special_group_-
 -w [24982](#)
 __regex_compile_special_group_-
 :w [24978](#)
 __regex_compile_special_group_-
 i:w [24982](#)
 __regex_compile_special_group_-
 l:w [24978](#)
 __regex_compile_u_end:
 [25210](#), [25216](#), [25221](#)
 __regex_compile_u_in_cs:
 [25227](#), [25230](#)
 __regex_compile_u_in_cs_aux:n ..
 [25240](#), [25243](#)
 __regex_compile_u_loop:NN ... [25186](#)
 __regex_compile_u_not_cs:
 [25225](#), [25249](#)
 __regex_compile_|: [24965](#)
 __regex_compute_case_changed_-
 char: [23920](#), [23934](#), [23942](#)
 __regex_count:nnN [26449](#), [26451](#), [26496](#)
 \c_regex_cs_in_class_mode_int ..
 [24285](#), [25118](#)
 \c_regex_cs_mode_int . [24285](#), [25116](#)
 \l_regex_cs_name_tl
 [23880](#), [24006](#), [24012](#)
 \l_regex_curr_catcode_int [23964](#),
 [23983](#), [23991](#), [24003](#), [25787](#), [25949](#)
 \l_regex_curr_char_int
 [23902](#), [23908](#),
 [23909](#), [23916](#), [23928](#), [23929](#), [23944](#),
 [23945](#), [23946](#), [23947](#), [23953](#), [23984](#),
 [24710](#), [25761](#), [25787](#), [25904](#), [25946](#)
 __regex_curr_cs_to_str:
 [23856](#), [23994](#), [24006](#)
 \l_regex_curr_pos_int
 . [966](#), [23859](#), [25472](#), [25754](#), [25782](#),
 [25809](#), [25811](#), [25814](#), [25822](#), [25829](#),
 [25836](#), [25864](#), [25874](#), [25903](#), [25918](#),
 [25932](#), [25934](#), [25936](#), [25937](#), [25938](#),
 [25948](#), [25951](#), [26030](#), [26039](#), [26548](#)
 \l_regex_curr_state_int
 [1021](#), [1028](#), [25791](#),
 [25956](#), [25957](#), [25959](#), [25964](#), [25967](#),
 [25989](#), [25994](#), [25999](#), [26000](#), [26008](#)
 \l_regex_curr_submatches_prop ..
 [25792](#), [25871](#), [25969](#),

- 26001, 26002, 26020, 26029, 26041
- \l_regex_default_catcodes_int ..
 - 980, [24292](#), 24416,
 - 24418, 24514, 24814, 24914, 24927
- _regex_disable_submatches: ...
 - .. 24008, 25113, [26022](#), 26490, 26499
- \l_regex_empty_success_bool ...
 - .. [25800](#), 25856, 25860, 26037, 26558
- _regex_escape_␣:w [24131](#)
- _regex_escape_/a:w [24131](#)
- _regex_escape_/break:w [24131](#)
- _regex_escape_/e:w [24131](#)
- _regex_escape_/f:w [24131](#)
- _regex_escape_/n:w [24131](#)
- _regex_escape_/r:w [24131](#)
- _regex_escape_/t:w [24131](#)
- _regex_escape_/x:w [24150](#)
- _regex_escape_\:w [24115](#)
- _regex_escape_break:w [24131](#)
- _regex_escape_escaped:N
 - 24101, 24125, [24128](#)
- _regex_escape_loop:N
 - 974, 24108, [24115](#), 24150,
 - 24186, 24194, 24195, 24212, 24221
- _regex_escape_raw:N
 - .. 975, 24102, [24128](#), 24139, 24141,
 - 24143, 24145, 24147, 24149, 24163
- _regex_escape_unescaped:N
 - [24100](#), 24118, [24128](#)
- _regex_escape_use:nnnn
 - 974, 985, [24096](#), 24462, 26122
- _regex_escape_x:N 976, 24185, [24189](#)
- _regex_escape_x_end:w .. 975, [24150](#)
- _regex_escape_x_large:n [24150](#)
- _regex_escape_x_loop:N
 - 976, 24182, 24198
- _regex_escape_x_loop_error: . [24198](#)
- _regex_escape_x_loop_error:n ..
 - 24201, 24213, 24218
- _regex_escape_x_test:N
 - 975, 24153, [24167](#)
- _regex_escape_x_testii:N ... [24167](#)
- \l_regex_every_match_tl
 - [25799](#), 25878, 25882, 25891
- _regex_extract: ... [1044](#), 26514,
 - 26520, 26532, [26609](#), 26653, 26676
- _regex_extract_all:nnN [26463](#), [26508](#)
- _regex_extract_b:wn [26609](#)
- _regex_extract_e:wn [26609](#)
- _regex_extract_once:nnN
 - 26461, [26508](#)
- _regex_extract_seq_aux:n
 - [26574](#), [26592](#)
- _regex_extract_seq_aux:ww .. [26592](#)
- \l_regex_fresh_thread_bool
 - [1022](#), [1027](#), [25773](#), [25779](#),
 - [25800](#), 25916, 25976, 25978, 26038
- _regex_get_digits:NtFw
 - [24323](#), 24568, 24583
- _regex_get_digits_loop:nw
 - [24326](#), [24329](#), [24332](#)
- _regex_get_digits_loop:w ... [24323](#)
- _regex_group:nnnN 979,
 - 996, 24956, 24961, 25287, 25457, [25585](#)
- _regex_group_aux:nnnnN
 - ... [1015](#), [25567](#), 25587, 25595, 25598
- _regex_group_aux:nnnnnN [1015](#)
- _regex_group_end_extract_seq:N
 - [26515](#), [26523](#), [26563](#), [26565](#)
- _regex_group_end_replace:N ...
 - [26670](#), [26699](#), [26701](#)
- \l_regex_group_level_int
 - [24284](#), [24415](#),
 - [24433](#), 24435, 24437, 24915, 24921
- _regex_group_no_capture:nnnN ..
 - 979, 24979, 25289, [25585](#)
- _regex_group_repeat:nn [25580](#), [25629](#)
- _regex_group_repeat:nnN
 - [25581](#), [25669](#)
- _regex_group_repeat:nnnN
 - [25582](#), [25700](#)
- _regex_group_repeat_aux:n
 - [1016](#), [1017](#), [25636](#), [25649](#), 25687, 25704
- _regex_group_resetting:nnnN ...
 - 979, 24981, 25291, [25596](#)
- _regex_group_resetting_-
 - loop:nnNn [25596](#)
- _regex_group_submatches:nnN ...
 - .. [25637](#), [25642](#), 25672, 25688, 25702
- _regex_hexadecimal_use:N ... [24223](#)
- _regex_hexadecimal_use:NtF ...
 - [24184](#), 24193, 24203, [24223](#)
- _regex_if_end_range:NN [24657](#)
- _regex_if_end_range:NNTF ... [24657](#)
- _regex_if_in_class:TF
 - [24347](#), 24426, 24499,
 - 24515, 24641, 24704, 24775, 24791,
 - 24936, 24967, 24975, 26776, 26789
- _regex_if_in_class_or_catcode:TF
 - .. [24367](#), 24733, 24757, 24766, 25188
- _regex_if_in_cs:TF
 - [24355](#), 25124, 26774, 26783
- _regex_if_match:nn
 - 26440, 26445, [26487](#)
- _regex_if_raw_digit:NN [24335](#)
- _regex_if_raw_digit:NNTF
 - [24325](#), [24331](#), [24335](#)

```

\\_regex_if_two_empty_matches:TF
    ... 1022, 25800, 25861, 25867, 26034
\\_regex_if_within_catcode:TF ...
    ... 24379, 24794
\\_regex_int_eval:w ...
    ... 23818, 26061, 26062, 26073, 26630
\\l_regex_internal_a_int ...
    ... 988, 1035, 23862,
    24568, 24579, 24590, 24599, 24603,
    24611, 24614, 24618, 24621, 24628,
    25549, 25552, 25558, 25563, 25638,
    25653, 25659, 25665, 25674, 25677,
    25681, 25684, 25689, 25692, 25695,
    25710, 25718, 25727, 26224, 26245
\\l_regex_internal_a_tl ...
    ... 974, 1004, 1004, 1005, 1046,
    1049, 23862, 23993, 23996, 24099,
    24106, 24113, 24862, 24867, 24883,
    24888, 24893, 24897, 24903, 24904,
    25132, 25143, 25193, 25223, 25235,
    25251, 25281, 25284, 25335, 25350,
    25392, 25399, 25486, 25487, 25488,
    25489, 25620, 25621, 25625, 25627,
    26426, 26435, 26659, 26689, 26719
\\l_regex_internal_b_int ...
    ... 23862, 24583, 24612, 24615,
    24616, 24618, 24622, 24629, 25654,
    25659, 25664, 25710, 25718, 25727
\\l_regex_internal_b_tl ... 23862
\\l_regex_internal_bool ...
    ... 23862, 24861, 24866, 24887, 24896
\\l_regex_internal_c_int ...
    ... 23862, 25656, 25661, 25662, 25666
\\l_regex_internal_regex ...
    ... 984, 24308, 24455, 25134, 25140,
    25446, 26408, 26413, 26418, 26423
\\l_regex_internal_seq ... 23862,
    25416, 25417, 25422, 25429, 25430,
    25431, 25433, 26569, 26587, 26590
\\g_regex_internal_tl ...
    ... 23862, 24104, 24108, 25232, 25239
\\_regex_item_caseful_equal:n ...
    ... 979, 23900, 24025,
    24026, 24030, 24031, 24032, 24033,
    24034, 24043, 24048, 24066, 24084,
    24419, 25006, 25168, 25246, 25303
\\_regex_item_caseful_range:nn ...
    ... 979, 23900, 24022,
    24037, 24040, 24041, 24042, 24056,
    24063, 24070, 24072, 24074, 24077,
    24078, 24079, 24080, 24085, 24088,
    24093, 24094, 24420, 25008, 25305
\\_regex_item_caseless_equal:n ...
    ... 979, 23914, 24987, 25310
\\_regex_item_caseless_range:nn ...
    ... 979, 23914, 24989, 25312
\\_regex_item_catcode: ... 23961
\\_regex_item_catcode:nTF ...
    ... 979, 994, 23961, 24508, 24816, 25317
\\_regex_item_catcode_reverse:nTF
    ... 979, 23961, 24817, 25319
\\_regex_item_cs:n ...
    ... 967, 979, 24001, 25140, 25326
\\_regex_item_equal:n ...
    ... 23959, 24419, 24647, 24653,
    24683, 24696, 24697, 24986, 25005
\\_regex_item_exact:nn ...
    ... 979, 1004, 23981, 25261, 25323
\\_regex_item_exact_cs:n ...
    ... 979, 1001, 23981, 25142, 25258, 25325
\\_regex_item_range:nn ...
    ... 23959, 24420, 24685, 24988, 25007
\\_regex_item_reverse:n ...
    ... 979, 995, 23895, 23980,
    24047, 24721, 24887, 25321, 25764
\\l_regex_last_char_int ...
    ... 25761, 25787, 25904
\\l_regex_left_state_int ...
    ... 25438, 25455, 25480, 25487,
    25498, 25505, 25508, 25509, 25511,
    25512, 25538, 25546, 25549, 25573,
    25621, 25623, 25633, 25653, 25673,
    25675, 25703, 25706, 25709, 25712,
    25724, 25737, 25746, 25770, 25777
\\l_regex_left_state_seq ...
    ... 25438, 25479, 25486, 25620
\\_regex_match:n ...
    ... 25806, 26493, 26503,
    26513, 26522, 26547, 26649, 26679
\\l_regex_match_count_int ...
    ... 1043, 1044, 26470, 26500, 26501, 26506
\\_regex_match_cs:n ... 24012, 25806
\\_regex_match_init: ... 25806
\\_regex_match_loop: ...
    ... 1024, 1027, 25877, 25900
\\_regex_match_once: ...
    ... 1024, 1025, 25817, 25839, 25858, 25896
\\_regex_match_one_active:n ... 25900
\\l_regex_match_success_bool ...
    ... 1023,
    25803, 25870, 25886, 25893, 26036
\\l_regex_max_active_int ...
    ... 1011, 25463, 25795, 25872, 25909,
    25912, 25917, 26014, 26015, 26019
\\l_regex_max_pos_int ... 1031,
    24746, 24747, 24754, 25410, 25472,
    25782, 25814, 25825, 25836, 25918,
    26548, 26553, 26559, 26668, 26697

```

- \l_regex_max_state_int
 .. [1009](#), [1011](#), [1056](#), [25435](#), [25452](#),
 [25464](#), [25497](#), [25499](#), [25500](#), [25559](#),
 [25571](#), [25632](#), [25652](#), [25654](#), [25662](#),
 [25706](#), [25712](#), [25720](#), [25730](#), [25809](#),
 [25824](#), [25845](#), [25850](#), [25854](#), [27027](#)
- \l_regex_min_active_int
 [1011](#), [25795](#),
 [25850](#), [25872](#), [25909](#), [25911](#), [25917](#)
- \l_regex_min_pos_int
 [1031](#), [24744](#), [24753](#),
 [25408](#), [25782](#), [25811](#), [25829](#), [25852](#)
- \l_regex_min_state_int
 [1011](#), [25435](#), [25452](#), [25463](#),
 [25464](#), [25824](#), [25845](#), [25873](#), [27026](#)
- \l_regex_min_submatch_int
 [1043](#), [1046](#), [1049](#), [25853](#),
 [25855](#), [26473](#), [26571](#), [26684](#), [26692](#)
- \l_regex_mode_int [24285](#),
 [24349](#), [24357](#), [24360](#), [24369](#), [24372](#),
 [24381](#), [24389](#), [24392](#), [24402](#), [24403](#),
 [24405](#), [24407](#), [24461](#), [24475](#), [24477](#),
 [24777](#), [24781](#), [24782](#), [24783](#), [24810](#),
 [24821](#), [24938](#), [25028](#), [25029](#), [25057](#),
 [25058](#), [25114](#), [25115](#), [25224](#), [25270](#)
- _regex_mode_quit_c:
 [24400](#), [24498](#), [24911](#)
- _regex_msg_repeated:nnN
 [25365](#), [25386](#), [25396](#), [26996](#)
- _regex_multi_match:n [1022](#),
 [25880](#), [26501](#), [26520](#), [26528](#), [26676](#)
- \c_regex_no_match_regex
 [23871](#), [24308](#), [26400](#)
- \c_regex_outer_mode_int
 [24285](#), [24360](#), [24372](#), [24381](#), [24389](#),
 [24403](#), [24461](#), [24477](#), [25224](#), [25270](#)
- _regex_pop_lr_states:
 [25469](#), [25477](#), [25578](#)
- _regex_posix_alnum: [24050](#)
- _regex_posix_alpha: [24050](#)
- _regex_posix_ascii: [24050](#)
- _regex_posix_blank: [24050](#)
- _regex_posix_cntrl: [24050](#)
- _regex_posix_digit: [24050](#)
- _regex_posix_graph: [24050](#)
- _regex_posix_lower: [24050](#)
- _regex_posix_print: [24050](#)
- _regex_posix_punct: [24050](#)
- _regex_posix_space: [24050](#)
- _regex_posix_upper: [24050](#)
- _regex_posix_word: [24050](#)
- _regex_posix_xdigit: [24050](#)
- _regex_prop_: [991](#), [24702](#)
- _regex_prop_d: ... [991](#), [24021](#), [24068](#)
- _regex_prop_h: [24021](#), [24060](#)
- _regex_prop_N: [24021](#), [24730](#)
- _regex_prop_s: [24021](#)
- _regex_prop_v: [24021](#)
- _regex_prop_w:
 .. [24021](#), [24089](#), [25762](#), [25764](#), [25765](#)
- _regex_push_lr_states:
 [25467](#), [25477](#), [25576](#)
- _regex_quark_if_nil:N [23891](#)
- _regex_quark_if_nil:NTF
 [25158](#), [25178](#)
- _regex_quark_if_nil:nTF [23891](#)
- _regex_quark_if_nil_p:n [23891](#)
- _regex_query_get:
 [25876](#), [25906](#), [25944](#)
- _regex_query_range:nn
 [1031](#), [26053](#),
 [26058](#), [26077](#), [26162](#), [26663](#), [26696](#)
- _regex_query_range_loop:ww . [26058](#)
- _regex_query_set:nnn
 [1023](#), [25810](#), [25813](#),
 [25815](#), [25828](#), [25832](#), [25837](#), [25929](#)
- _regex_query_submatch:n
 [26075](#), [26210](#), [26603](#)
- _regex_replace_all:nnN [26467](#), [26673](#)
- _regex_replace_once:nnN
 [26465](#), [26643](#)
- _regex_replacement:n
 [26116](#), [26648](#), [26678](#)
- _regex_replacement_aux:n ... [26116](#)
- _regex_replacement_balance-
 one_match:n [1030](#),
 [1030](#), [26049](#), [26147](#), [26656](#), [26687](#)
- _regex_replacement_c:w [26254](#)
- _regex_replacement_c_A:w
 [1034](#), [26335](#)
- _regex_replacement_c_B:w ... [26338](#)
- _regex_replacement_c_C:w ... [26347](#)
- _regex_replacement_c_D:w ... [26352](#)
- _regex_replacement_c_E:w ... [26355](#)
- _regex_replacement_c_L:w ... [26364](#)
- _regex_replacement_c_M:w ... [26367](#)
- _regex_replacement_c_O:w ... [26370](#)
- _regex_replacement_c_P:w ... [26373](#)
- _regex_replacement_c_S:w ... [26379](#)
- _regex_replacement_c_T:w ... [26387](#)
- _regex_replacement_c_U:w ... [26390](#)
- _regex_replacement_cat:NNN ...
 [26262](#), [26295](#)
- \l_regex_replacement_category_-
 seq [26046](#),
 [26141](#), [26144](#), [26145](#), [26181](#), [26309](#)

- \l_regex_replacement_category_-
 tl [1034](#), [26046](#),
 [26176](#), [26182](#), [26188](#), [26310](#), [26311](#)
- _regex_replacement_char:nNN ...
 [1040](#), [26330](#),
 [26337](#), [26344](#), [26354](#), [26361](#), [26366](#),
 [26369](#), [26372](#), [26376](#), [26389](#), [26392](#)
- \l_regex_replacement_csnames_-
 int [1030](#), [26045](#), [26135](#),
 [26137](#), [26139](#), [26211](#), [26270](#), [26277](#),
 [26288](#), [26290](#), [26300](#), [26341](#), [26358](#)
- _regex_replacement_cu_aux:Nw ..
 [26259](#), [26268](#), [26283](#)
- _regex_replacement_do_one_-
 match:n . [26051](#), [26160](#), [26661](#), [26695](#)
- _regex_replacement_error:NNN ..
 [26225](#), [26237](#),
 [26248](#), [26263](#), [26266](#), [26284](#), [26394](#)
- _regex_replacement_escaped:N ..
 [26131](#), [26194](#), [26314](#)
- _regex_replacement_exp_not:N ..
 [1036](#), [26057](#), [26259](#)
- _regex_replacement_g:w [26220](#)
- _regex_replacement_g_digits:NN
 [26220](#)
- _regex_replacement_normal:n ...
 [26127](#), [26132](#), [26174](#), [26201](#), [26223](#),
 [26229](#), [26256](#), [26282](#), [26292](#), [26307](#)
- _regex_replacement_put_-
 submatch:n ... [26199](#), [26206](#), [26244](#)
- _regex_replacement_rbrace:N ...
 [26125](#), [26243](#), [26286](#)
- _regex_replacement_u:w [26279](#)
- _regex_return: [1042](#),
 [26441](#), [26446](#), [26457](#), [26459](#), [26479](#)
- \l_regex_right_state_int
 [25438](#), [25458](#), [25470](#),
 [25482](#), [25489](#), [25498](#), [25499](#), [25538](#),
 [25545](#), [25551](#), [25564](#), [25571](#), [25573](#),
 [25623](#), [25627](#), [25638](#), [25652](#), [25661](#),
 [25673](#), [25677](#), [25681](#), [25684](#), [25689](#),
 [25692](#), [25695](#), [25703](#), [25717](#), [25720](#),
 [25723](#), [25726](#), [25730](#), [25746](#), [25777](#)
- \l_regex_right_state_seq
 [25438](#), [25481](#), [25488](#), [25625](#)
- \l_regex_saved_success_bool ...
 [1023](#), [24010](#), [24017](#), [25803](#)
- _regex_show:N . [25274](#), [26423](#), [26432](#)
- _regex_show_anchor_to_str:N ...
 [25302](#), [25403](#)
- _regex_show_class:NnnnN
 [25293](#), [25367](#)
- _regex_show_group_aux:nnnnN ...
 [25288](#), [25290](#), [25292](#), [25358](#)
- _regex_show_item_catcode:NnTF .
 [25318](#), [25320](#), [25414](#)
- _regex_show_item_exact_cs:n ...
 [25325](#), [25427](#)
- \l_regex_show_lines_int
 .. [24310](#), [25339](#), [25371](#), [25374](#), [25381](#)
- _regex_show_one:n [25282](#),
 [25295](#), [25298](#), [25304](#), [25307](#), [25311](#),
 [25314](#), [25324](#), [25328](#), [25337](#), [25353](#),
 [25360](#), [25364](#), [25377](#), [25393](#), [25432](#)
- _regex_show_pop: [25347](#), [25363](#)
- \l_regex_show_prefix_seq
 [24309](#), [25280](#),
 [25283](#), [25329](#), [25343](#), [25348](#), [25350](#)
- _regex_show_push:n
 [25330](#), [25347](#), [25361](#), [25372](#)
- _regex_show_scope:nn
 [25322](#), [25327](#), [25347](#), [25419](#)
- _regex_single_match: [1022](#),
 [24007](#), [25880](#), [26491](#), [26511](#), [26646](#)
- _regex_split:nnN [26469](#), [26525](#)
- _regex_standard_escapechar: ...
 .. [23822](#), [23825](#), [24103](#), [24460](#), [25450](#)
- \l_regex_start_pos_int
 [24745](#), [25409](#),
 [25782](#), [25864](#), [25869](#), [25875](#), [26531](#),
 [26543](#), [26556](#), [26559](#), [26633](#), [26697](#)
- \g_regex_state_active_intarray .
 [964](#), [1011](#), [1022](#), [1022](#), [1023](#), [25797](#),
 [25848](#), [25955](#), [25958](#), [25966](#), [25993](#)
- \l_regex_step_int
 [964](#), [25794](#), [25851](#), [25902](#),
 [25956](#), [25960](#), [25968](#), [25982](#), [25984](#)
- _regex_store_state:n
 [25873](#), [26007](#), [26010](#)
- _regex_store_submatches:
 [26010](#), [26024](#)
- _regex_submatch_balance:n ...
 .. [26050](#), [26081](#), [26151](#), [26214](#), [26595](#)
- \g_regex_submatch_begin_-
 intarray [965](#), [1030](#), [26055](#),
 [26078](#), [26103](#), [26111](#), [26169](#), [26476](#),
 [26538](#), [26541](#), [26554](#), [26615](#), [26639](#)
- \g_regex_submatch_end_intarray .
 . [965](#), [26079](#), [26088](#), [26096](#), [26476](#),
 [26535](#), [26551](#), [26617](#), [26642](#), [26665](#)
- \l_regex_submatch_int
 [965](#), [1043](#), [1045](#), [1046](#), [1049](#),
 [25855](#), [26473](#), [26550](#), [26552](#), [26555](#),
 [26557](#), [26560](#), [26572](#), [26612](#), [26616](#),
 [26618](#), [26620](#), [26621](#), [26686](#), [26694](#)
- \g_regex_submatch_prev_intarray
 .. [965](#), [1043](#), [1047](#), [26054](#), [26165](#),
 [26476](#), [26533](#), [26549](#), [26619](#), [26632](#)

- \g__regex_success_bool 1023,
24011, 24013, 24016, 25803, 25843,
25885, 25894, 26481, 26611, 26650
 - \l__regex_success_pos_int
.. 25782, 25852, 25869, 26039, 26531
 - \l__regex_success_submatches_
prop 1021, 1047, 25792, 26040, 26623
 - __regex_tests_action_cost:n . . .
..... 25516, 25537, 25546, 25564
 - \g__regex_thread_state_intarray .
..... 965, 1011, 1020,
1022, 1022, 1028, 25797, 25926, 26013
 - __regex_tmp:w
23844, 23846, 23850, 23852, 23861,
24714, 24724, 24725, 24726, 24727,
24728, 24739, 24744, 24745, 24746,
24747, 24748, 24753, 24754, 26452,
26461, 26463, 26465, 26467, 26469
 - __regex_toks_clear:N . 23828, 25497
 - __regex_toks_memcpy:Nn 23833, 25663
 - __regex_toks_put_left:Nn
..... 23842, 25492, 25645, 25646
 - __regex_toks_put_right:Nn
..... 966, 23842, 25455, 25458,
25470, 25494, 25505, 25737, 25770
 - __regex_toks_set:Nn
..... 23828, 25937, 26019
 - __regex_toks_use:w
.. 23827, 25927, 25957, 26071, 27030
 - __regex_trace:nnn 27012, 27029
 - __regex_trace_pop:nnN 27012
 - __regex_trace_push:nnN 27012
 - \g__regex_trace_regex_int 27022
 - __regex_trace_states:n 27023
 - __regex_two_if_eq:NNNN 24311
 - __regex_two_if_eq:NNNTF
..... 24311, 24549, 24596,
24609, 24643, 24822, 24859, 24879,
24880, 24949, 24984, 25001, 25002,
25064, 25191, 26222, 26281, 26307
 - __regex_use_i_delimit_by_q_
recursion_stop:nw .. 23886, 25181
 - __regex_use_none_delimit_by_q_
recursion_stop:w
..... 23886, 25159, 25183
 - __regex_use_state:
..... 25953, 25970, 25996
 - __regex_use_state_and_submatches:nn
..... 1025, 25925, 25962
 - \l__regex_zeroth_submatch_int . . .
..... 1043, 1047, 26473,
26534, 26536, 26539, 26542, 26612,
26630, 26633, 26657, 26662, 26666
 - \relax 14, 21, 39, 43, 49, 84, 86,
87, 88, 99, 124, 147, 168, 182, 212,
213, 214, 215, 216, 217, 218, 219,
220, 221, 222, 225, 226, 227, 228,
229, 230, 231, 232, 233, 234, 235, 520
 - \relpenalty 521
 - \RequirePackage 150
 - \resettimer 883
 - reverse commands:
 \reverse_if:N
 23, 433, 512, 513, 767, 2100,
 5847, 8780, 8931, 8933, 8935, 8937,
 8992, 9757, 14699, 14704, 14708,
 14710, 17471, 21049, 21871, 21894,
 23908, 23909, 23928, 23929, 23936,
 23937, 29266, 29268, 29290, 29314
 - \right 522
 - right commands:
 \c_right_brace_str 71, 5899,
 13817, 24211, 24576, 24596, 24609,
 25122, 25126, 25209, 26124, 29643
 - \rightghost 993, 1875
 - \righthyphenmin 523
 - \rightmarginkern 795, 1664
 - \rightskip 524
 - \rmfamily 31201
 - \romannumeral 525
 - round 212
 - \rPCODE 796, 1665
 - \rule 28764, 28819
- S**
- s@ internal commands:
 \s@_ 951
 - \saveboxresource 1036, 1699
 - \savecatcodetable 994, 1847
 - \saveimageresource 1037, 1700
 - \savepos 1035, 1698
 - \savingsphcodes 656, 1527
 - \savingsdiscards 657, 1528
 - scan commands:
 \scan_align_safe_stop: 32408
 - \scan_new:N
 41, 386, 418, 4235, 5270, 5271,
 5272, 5280, 5281, 5930, 8063, 8064,
 8065, 8689, 8690, 10205, 10206,
 10802, 11289, 11556, 11557, 11736,
 11741, 11742, 12092, 12093, 13293,
 13294, 13761, 14577, 14578, 14925,
 15093, 15094, 15095, 15096, 15312,
 16575, 16578, 16579, 16580, 16581,
 16583, 16584, 16585, 16586, 16587,
 16686, 22964, 22965, 23385, 28978,
 29378, 31781, 31782, 32196, 32197

- \scan_stop:
 - [9](#), [17](#), [18](#), [18](#), [18](#), [41](#), [41](#), [89](#),
[252](#), [266](#), [314](#), [318](#), [318](#), [334](#), [335](#),
[337](#), [346](#), [350](#), [351](#), [362](#), [386](#), [388](#),
[391](#), [400](#), [404](#), [433](#), [512](#), [517](#), [531](#),
[584](#), [584](#), [591](#), [593](#), [594](#), [605](#), [628](#),
[672](#), [673](#), [673](#), [678](#), [764](#), [767](#), [768](#),
[769](#), [773](#), [979](#), [1001](#), [2129](#), [2481](#),
[2499](#), [2509](#), [2527](#), [2553](#), [2883](#), [2892](#),
[2901](#), [2973](#), [3408](#), [3532](#), [3533](#), [3548](#),
[3588](#), [3614](#), [3638](#), [3655](#), [3859](#), [3865](#),
[3970](#), [4244](#), [4247](#), [4405](#), [4640](#), [5848](#),
[6027](#), [6354](#), [6355](#), [6363](#), [6364](#), [6396](#),
[6397](#), [7029](#), [8417](#), [9122](#), [9999](#), [10003](#),
[10178](#), [11333](#), [11405](#), [11628](#), [11727](#),
[11730](#), [11732](#), [13110](#), [13115](#), [13199](#),
[13327](#), [13330](#), [13891](#), [13898](#), [14365](#),
[14591](#), [14610](#), [14612](#), [14616](#), [14619](#),
[14622](#), [14626](#), [14631](#), [14635](#), [14858](#),
[14937](#), [14955](#), [14957](#), [14965](#), [14967](#),
[14971](#), [14973](#), [14994](#), [15000](#), [15003](#),
[15031](#), [15051](#), [15053](#), [15061](#), [15063](#),
[15067](#), [15069](#), [15073](#), [16331](#), [16338](#),
[16561](#), [16750](#), [17469](#), [17473](#), [17676](#),
[17693](#), [17993](#), [18040](#), [18041](#), [18300](#),
[18343](#), [18373](#), [18387](#), [19146](#), [20959](#),
[20967](#), [21713](#), [21716](#), [21719](#), [21722](#),
[21725](#), [21728](#), [21731](#), [21734](#), [21737](#),
[22999](#), [23507](#), [23547](#), [23551](#), [23557](#),
[23559](#), [23606](#), [23608](#), [23994](#), [23995](#),
[24333](#), [25151](#), [25429](#), [25948](#), [25951](#),
[25972](#), [26332](#), [26384](#), [27038](#), [27183](#),
[28760](#), [28815](#), [29391](#), [29392](#), [32242](#),
[32245](#), [32451](#), [32711](#), [32722](#), [32772](#)
- scan internal commands:
 - \g__scan_marks_tl
 - ... [386](#), [4234](#), [4237](#), [4243](#), [4248](#), [4250](#)
 - \scantextokens [995](#), [1848](#)
 - \scantokens [658](#), [1529](#)
 - \scriptbaselineshiftfactor [1252](#)
 - \scriptfont [526](#)
 - \scriptscriptbaselineshiftfactor . [1254](#)
 - \scriptscriptfont [527](#)
 - \scriptscriptstyle [528](#)
 - \scriptsize [31218](#)
 - \scriptspace [529](#)
 - \scriptstyle [530](#)
 - \scrollmode [531](#)
 - \scshape [31207](#)
 - sec [213](#)
 - secd [213](#)
 - \selectfont [31179](#)
- seq commands:
 - \c_empty_seq [85](#), [488](#), [8074](#),
[8078](#), [8082](#), [8085](#), [8273](#), [8351](#), [8359](#)
 - \l_foo_seq [227](#)
 - \seq_clear:N
 - [75](#), [75](#), [85](#), [8081](#), [8088](#), [8217](#),
[12510](#), [12573](#), [14444](#), [25329](#), [26145](#)
 - \seq_clear_new:N [75](#), [8087](#)
 - \seq_concat:NNN .. [76](#), [85](#), [8170](#), [14452](#)
 - \seq_const_from_clist:Nn ... [76](#), [8127](#)
 - \seq_count:N [77](#), [82](#), [84](#), [196](#),
[8288](#), [8478](#), [8492](#), [8570](#), [8598](#), [26144](#)
 - \seq_elt:w [487](#)
 - \seq_elt_end: [487](#)
 - \seq_gclear:N
 - [75](#), [938](#), [8081](#), [8091](#), [8305](#), [23121](#)
 - \seq_gclear_new:N [75](#), [8087](#)
 - \seq_gconcat:NNN [76](#), [8170](#), [14466](#)
 - \seq_get:NN ... [83](#), [8651](#), [25620](#), [25625](#)
 - \seq_get:NNTF [83](#), [8657](#)
 - \seq_get_left:NN
 - [77](#), [8367](#), [8651](#), [8652](#), [8657](#), [8658](#)
 - \seq_get_left:NNTF [78](#), [8437](#)
 - \seq_get_right:NN [77](#), [8392](#)
 - \seq_get_right:NNTF [78](#), [8437](#)
 - \seq_gpop:NN [83](#), [8651](#), [14388](#)
 - \seq_gpop:NNTF [84](#), [8657](#), [13094](#), [13311](#)
 - \seq_gpop_left:NN
 - [77](#), [8378](#), [8655](#), [8656](#), [8661](#), [8662](#)
 - \seq_gpop_left:NNTF [78](#), [8445](#)
 - \seq_gpop_right:NN [77](#), [8410](#)
 - \seq_gpop_right:NNTF [79](#), [8445](#)
 - \seq_gpush:Nn
 - ... [25](#), [84](#), [8631](#), [13124](#), [13340](#), [14371](#)
 - \seq_gput_left:Nn
 - . [76](#), [8180](#), [8641](#), [8642](#), [8643](#), [8644](#),
[8645](#), [8646](#), [8647](#), [8648](#), [8649](#), [8650](#)
 - \seq_gput_right:Nn [76](#), [8201](#),
[13726](#), [13733](#), [13749](#), [14354](#), [14359](#)
 - \seq_gremove_all:Nn . [79](#), [8227](#), [13274](#)
 - \seq_gremove_duplicates:N .. [79](#), [8211](#)
 - \seq_greverse:N [79](#), [8253](#)
 - \seq_gset_eq:NN
 - ... [75](#), [8085](#), [8093](#), [8214](#), [8285](#), [23095](#)
 - \seq_gset_filter:NNn [265](#), [31860](#)
 - \seq_gset_from_clist:NN [75](#), [8101](#)
 - \seq_gset_from_clist:Nn [75](#), [8101](#)
 - \seq_gset_from_function:NnN
 - [266](#), [31890](#)
 - \seq_gset_from_inline_x:Nnn
 - [266](#), [8300](#), [23113](#), [31880](#), [31893](#)
 - \seq_gset_map:NNn [265](#), [31870](#)
 - \seq_gset_split:Nnn
 - [76](#), [8133](#), [13040](#), [13268](#)
 - \seq_gshuffle:N [80](#), [8281](#)
 - \seq_gsort:Nn [79](#), [8271](#), [23091](#)

- \seq_if_empty:NTF
..... [80](#), [8271](#), [8491](#), [10286](#), [26141](#)
- \seq_if_empty_p:N [80](#), [8271](#)
- \seq_if_exist:NTF
..... [76](#), [8088](#), [8091](#), [8176](#), [8596](#)
- \seq_if_exist_p:N [76](#), [8176](#)
- \seq_if_in:Nn [561](#)
- \seq_if_in:NnTF
..... [80](#), [84](#), [85](#), [8220](#), [8328](#), [13123](#), [13339](#)
- \seq_indexed_map_function:NN ...
..... [266](#), [31894](#)
- \seq_indexed_map_inline:Nn [266](#), [31894](#)
- \seq_item:Nn [77](#), [230](#),
[499](#), [8465](#), [8492](#), [12591](#), [12592](#), [12597](#)
- \seq_log:N [86](#), [8663](#)
- \seq_map_break:
..... [81](#), [265](#), [265](#), [8495](#), [8506](#),
[8541](#), [8549](#), [8566](#), [16016](#), [31897](#), [31906](#)
- \seq_map_break:n
..... [82](#), [500](#), [8495](#), [12530](#),
[12544](#), [13948](#), [14032](#), [23092](#), [23095](#)
- \seq_map_function:NN
..... [4](#), [80](#), [81](#), [264](#), [1174](#), [8499](#), [8673](#),
[10292](#), [12595](#), [14455](#), [25343](#), [25422](#)
- \seq_map_inline:Nn
..... [80](#), [80](#), [81](#), [85](#), [1173](#), [8218](#), [8537](#),
[12525](#), [14031](#), [16009](#), [23092](#), [23095](#)
- \seq_map_tokens:Nn [80](#), [81](#), [8544](#), [13928](#)
- \seq_map_variable:NNn [81](#), [8558](#)
- \seq_mapthread_function:NNN ...
..... [265](#), [31838](#)
- \seq_new:N [4](#), [75](#), [75](#), [8075](#),
[8088](#), [8091](#), [8210](#), [8283](#), [8677](#), [8678](#),
[8679](#), [8680](#), [10437](#), [10899](#), [10902](#),
[12480](#), [12481](#), [13038](#), [13265](#), [13717](#),
[13744](#), [13757](#), [13759](#), [15306](#), [22951](#),
[23868](#), [24309](#), [25440](#), [25441](#), [26047](#)
- \seq_pop:NN
..... [83](#), [8651](#), [25486](#), [25488](#), [26181](#)
- \seq_pop:NNTF [84](#), [8657](#)
- \seq_pop_left:NN
..... [77](#), [8378](#), [8653](#), [8654](#), [8659](#), [8660](#)
- \seq_pop_left:NNTF [78](#), [8445](#)
- \seq_pop_right:NN
..... [77](#), [8410](#), [25280](#), [25350](#)
- \seq_pop_right:NNTF [79](#), [8445](#)
- \seq_push:Nn
..... [84](#), [8631](#), [8638](#), [25479](#), [25481](#), [26309](#)
- \seq_put_left:Nn [76](#),
[8180](#), [8631](#), [8632](#), [8633](#), [8634](#), [8635](#),
[8636](#), [8637](#), [8638](#), [8639](#), [8640](#), [12520](#)
- \seq_put_right:Nn [76](#), [84](#), [85](#),
[8201](#), [8221](#), [12581](#), [25283](#), [25348](#), [32355](#)
- \seq_rand_item:N [78](#), [8489](#)
- \seq_remove_all:Nn
..... [76](#), [79](#), [84](#), [85](#), [8227](#), [10463](#), [32357](#)
- \seq_remove_duplicates:N
..... [79](#), [84](#), [85](#), [8211](#), [14453](#)
- \seq_reverse:N [79](#), [493](#), [8253](#)
- \seq_set_eq:NN
[75](#), [85](#), [8082](#), [8093](#), [8212](#), [8284](#), [23092](#)
- \seq_set_filter:NNn
..... [265](#), [1173](#), [25417](#), [31860](#)
- \seq_set_from_clist:NN [75](#), [8101](#), [10462](#)
- \seq_set_from_clist:Nn [75](#),
[118](#), [489](#), [8101](#), [14448](#), [14464](#), [15943](#)
- \seq_set_from_function:NnN
..... [266](#), [26569](#), [31890](#)
- \seq_set_from_inline_x:Nnn
..... [266](#), [1174](#), [31880](#), [31891](#)
- \seq_set_map:NNn
..... [265](#), [25430](#), [26587](#), [31870](#)
- \seq_set_split:Nnn
..... [76](#), [8133](#), [10900](#), [10903](#), [25416](#), [25429](#)
- \seq_show:N [86](#), [616](#), [8663](#)
- \seq_shuffle:N [80](#), [8281](#)
- \seq_sort:Nn [79](#), [220](#), [8271](#), [23091](#)
- \seq_use:Nn [83](#), [8594](#), [25433](#)
- \seq_use:Nnnn [82](#), [8594](#)
- \g_tmpa_seq [86](#), [8677](#)
- \l_tmpa_seq [86](#), [8677](#)
- \g_tmpb_seq [86](#), [8677](#)
- \l_tmpb_seq [86](#), [8677](#)
- seq internal commands:
 - __seq_count:w [502](#), [8570](#)
 - __seq_count_end:w [502](#), [8570](#)
 - __seq_get_left:wnw [8367](#)
 - __seq_get_right_end:NnN [8392](#)
 - __seq_get_right_loop:nw .. [497](#), [8392](#)
 - __seq_if_in: [8328](#)
 - __seq_indexed_map:NN
..... [31896](#), [31904](#), [31909](#)
 - __seq_indexed_map:nnn [31894](#)
 - __seq_indexed_map:Nw .. [1174](#), [31894](#)
 - \l_seq_internal_a_int
..... [8295](#), [8301](#), [8310](#), [8312](#), [8313](#)
 - \l_seq_internal_a_tl
..... [490](#), [8071](#), [8141](#), [8145](#), [8151](#),
[8156](#), [8158](#), [8242](#), [8247](#), [8332](#), [8336](#)
 - \l_seq_internal_b_int
..... [8311](#), [8314](#), [8315](#)
 - \l_seq_internal_b_tl
..... [8071](#), [8238](#), [8242](#), [8335](#), [8336](#)
 - \g__seq_internal_seq [8281](#)
 - __seq_item:n
..... [487](#), [487](#), [487](#), [487](#), [491](#), [495](#),
[496](#), [497](#), [499](#), [500](#), [500](#), [501](#), [502](#),
[502](#), [1172](#), [1173](#), [1173](#), [8066](#), [8184](#),

- 8192, 8202, 8204, 8209, 8259, 8260,
- 8262, 8267, 8297, 8333, 8372, 8375,
- 8385, 8400, 8403, 8416, 8417, 8428,
- 8472, 8481, 8505, 8508, 8518, 8523,
- 8529, 8533, 8548, 8552, 8577, 8578,
- 8579, 8580, 8581, 8582, 8583, 8584,
- 8589, 8590, 8605, 8620, 8623, 8626,
- 31876, 31886, 31887, 31917, 31919
- __seq_item:nN [8465](#)
- __seq_item:nwn [8465](#)
- __seq_item:wNn [8465](#)
- __seq_map_function:NNn [8499](#)
- __seq_map_function:Nw
..... [8502](#), [8508](#), [8512](#)
- __seq_map_tokens:nw [8544](#)
- __seq_mapthread_function:Nnnwnn
..... [31838](#)
- __seq_mapthread_function:wNN . [31838](#)
- __seq_mapthread_function:wNw . [31838](#)
- __seq_pop:NNNN
..... [8349](#), [8379](#), [8381](#), [8411](#), [8413](#)
- __seq_pop_item_def:
..... [487](#), [487](#), [8249](#), [8299](#),
[8515](#), [8541](#), [8566](#), [31868](#), [31878](#), [31888](#)
- __seq_pop_left:NNN . [8378](#), [8447](#), [8450](#)
- __seq_pop_left:wnwNNN [8378](#)
- __seq_pop_right:NNN
..... [492](#), [8410](#), [8453](#), [8456](#)
- __seq_pop_right_loop:nn [8410](#)
- __seq_pop_TF:NNNN [498](#), [8349](#),
[8438](#), [8440](#), [8447](#), [8450](#), [8453](#), [8456](#)
- __seq_push_item_def: ... [8296](#), [8515](#)
- __seq_push_item_def:n
..... [487](#), [487](#), [8233](#),
[8515](#), [8539](#), [8560](#), [31866](#), [31876](#), [31886](#)
- __seq_put_left_aux:w [491](#), [8180](#)
- __seq_remove_all_aux:NNn [8227](#)
- __seq_remove_duplicates:NN .. [8211](#)
- \l__seq_remove_seq
..... [8210](#), [8217](#), [8220](#), [8221](#), [8223](#)
- __seq_reverse:NN [8253](#)
- __seq_reverse_item:nw [493](#)
- __seq_reverse_item:nwn [8253](#)
- __seq_set_filter:NNNn [31860](#)
- __seq_set_from_inline_x:NNnn . [31880](#)
- __seq_set_map:NNNn [31870](#)
- __seq_set_split:NNnn [8133](#)
- __seq_set_split_auxi:w ... [490](#), [8133](#)
- __seq_set_split_auxii:w .. [490](#), [8133](#)
- __seq_set_split_end: [490](#), [8133](#)
- __seq_show:NN [8663](#)
- __seq_shuffle:NN [8281](#)
- __seq_shuffle_item:n [8281](#)
- __seq_tmp:w
..... [8073](#), [8259](#), [8262](#), [8416](#), [8428](#)
- __seq_use:NNnNnn [8594](#)
- __seq_use:nwn [8594](#)
- __seq_use:nwwwnwn [8594](#)
- __seq_use_setup:w [8594](#)
- __seq_wrap_item:n
[490](#), [1173](#), [8104](#), [8109](#), [8114](#), [8119](#),
[8130](#), [8142](#), [8167](#), [8209](#), [8245](#), [31866](#)
- \setbox [532](#)
- \setfontid [996](#), [1849](#)
- \setlanguage [533](#)
- \setrandomseed [1038](#), [1701](#)
- \sfcode [184](#), [534](#)
- \sffamily [28751](#), [31202](#)
- \shapemode [997](#), [1850](#)
- \shellescape [884](#), [1671](#)
- \Shipout [1314](#)
- \shipout [535](#), [1301](#), [1302](#)
- \ShortText [69](#), [117](#), [134](#)
- \show [536](#)
- \showbox [537](#)
- \showboxbreadth [538](#)
- \showboxdepth [539](#)
- \showgroups [659](#), [1530](#)
- \showifs [660](#), [1531](#)
- \showlists [540](#)
- \showmode [1256](#), [2075](#)
- \showthe [541](#)
- \ShowTokens [221](#)
- \showtokens [661](#), [1532](#)
- sign [212](#)
- sin [213](#)
- sind [213](#)
- \sjis [1257](#), [2076](#)
- \skewchar [542](#)
- \skip [543](#), [11483](#)
- skip commands:
 \c_max_skip [179](#), [15014](#)
 \skip_add:Nn [177](#), [14964](#)
 \skip_const:Nn
 [177](#), [685](#), [14934](#), [15014](#), [15015](#)
 \skip_eval:n [178](#), [178](#), [178](#),
 [178](#), [14937](#), [14978](#), [14993](#), [15009](#), [15013](#)
 \skip_gadd:Nn [177](#), [14964](#)
 .skip_gset:N [188](#), [15776](#)
 \skip_gset:Nn [177](#), [682](#), [14954](#)
 \skip_gset_eq:NN [177](#), [14960](#)
 \skip_gsub:Nn [177](#), [14964](#)
 \skip_gzero:N [177](#), [14940](#), [14947](#)
 \skip_gzero_new:N [177](#), [14944](#)
 \skip_horizontal:N [179](#), [14998](#)
 \skip_horizontal:n [179](#), [14998](#)
 \skip_if_eq:nnTF [178](#), [14976](#)

- \skip_if_eq_p:nn [178](#), [14976](#)
- \skip_if_exist:NTF
 - [177](#), [14945](#), [14947](#), [14950](#)
- \skip_if_exist_p:N [177](#), [14950](#)
- \skip_if_finite:nTF [178](#), [14982](#)
- \skip_if_finite_p:n [178](#), [14982](#)
- \skip_log:N [179](#), [15010](#)
- \skip_log:n [179](#), [15010](#)
- \skip_new:N
 - .. [176](#), [177](#), [14926](#), [14936](#), [14945](#),
 - [14947](#), [15016](#), [15017](#), [15018](#), [15019](#)
- .skip_set:N [188](#), [15776](#)
- \skip_set:Nn [177](#), [14954](#)
- \skip_set_eq:NN [177](#), [14960](#)
- \skip_show:N [178](#), [15006](#)
- \skip_show:n [178](#), [684](#), [15008](#)
- \skip_sub:Nn [177](#), [14964](#)
- \skip_use:N
 - [178](#), [178](#), [14987](#), [14994](#), [14995](#)
- \skip_vertical:N [180](#), [14998](#)
- \skip_vertical:n [180](#), [14998](#)
- \skip_zero:N [177](#), [177](#), [180](#), [14940](#), [14945](#)
- \skip_zero_new:N [177](#), [14944](#)
- \g_tmpa_skip [179](#), [15016](#)
- \l_tmpa_skip [179](#), [15016](#)
- \g_tmpb_skip [179](#), [15016](#)
- \l_tmpb_skip [179](#), [15016](#)
- \c_zero_skip [179](#),
- [672](#), [14594](#), [14596](#), [14940](#), [14941](#), [15014](#)
- skip internal commands:
 - __skip_if_finite:wwNw [14982](#)
 - __skip_tmp:w [14982](#), [14992](#)
- \skipdef [544](#)
- \slshape [31208](#)
- \small [31219](#)
- sort commands:
 - \sort_ordered: [32410](#)
 - \sort_return_same:
 - [220](#), [220](#), [940](#), [23174](#), [32411](#)
 - \sort_return_swapped:
 - [220](#), [220](#), [940](#), [23174](#), [32413](#)
 - \sort_reversed: [32412](#)
- sort internal commands:
 - __sort:nnNnn [942](#), [943](#)
 - \l_sort_A_int
 - . [940](#), [22961](#), [22968](#), [22975](#), [22978](#),
 - [22987](#), [23138](#), [23143](#), [23146](#), [23166](#),
 - [23198](#), [23205](#), [23220](#), [23222](#), [23223](#)
 - \l_sort_B_int
 - .. [940](#), [940](#), [22961](#), [23143](#), [23147](#),
 - [23155](#), [23157](#), [23158](#), [23210](#), [23211](#),
 - [23220](#), [23221](#), [23230](#), [23231](#), [23233](#)
 - \l_sort_begin_int
 - [934](#), [940](#), [22959](#), [23135](#), [23223](#), [23233](#)
 - \l_sort_block_int
 - [934](#), [935](#), [939](#), [22958](#), [22970](#),
 - [22975](#), [22979](#), [22982](#), [22987](#), [22988](#),
 - [23065](#), [23126](#), [23129](#), [23136](#), [23139](#)
 - \l_sort_C_int
 - .. [940](#), [940](#), [22961](#), [23144](#), [23148](#),
 - [23155](#), [23156](#), [23167](#), [23199](#), [23206](#),
 - [23210](#), [23212](#), [23213](#), [23230](#), [23232](#)
 - __sort_compare:nn
 - [937](#), [941](#), [23064](#), [23165](#)
 - __sort_compute_range:
 - [934](#), [935](#), [935](#), [22992](#), [23052](#)
 - __sort_copy_block: [939](#), [23145](#), [23153](#)
 - __sort_disable_toksdef: [23051](#), [23330](#)
 - __sort_disabled_toksdef:n ... [23330](#)
 - \l_sort_end_int [934](#), [939](#), [940](#), [940](#),
 - [22959](#), [23127](#), [23135](#), [23136](#), [23137](#),
 - [23138](#), [23139](#), [23140](#), [23141](#), [23158](#)
 - __sort_error: .. [23324](#), [23337](#), [23356](#)
 - __sort_i:nnnnNn [944](#)
 - \g_sort_internal_seq
 - [937](#), [938](#), [22951](#), [23113](#), [23120](#), [23121](#)
 - \g_sort_internal_tl
 - [22951](#), [23076](#), [23079](#), [23080](#)
 - \l_sort_length_int
 - [934](#), [934](#), [22953](#), [23062](#), [23126](#)
 - __sort_level:
 - [937](#), [947](#), [23066](#), [23124](#), [23328](#)
 - __sort_loop:wNn [943](#)
 - __sort_main:NNNn
 - [937](#), [938](#), [23049](#), [23075](#), [23112](#)
 - \l_sort_max_int
 - [934](#), [935](#), [22953](#), [22972](#), [23046](#), [23056](#)
 - \c_sort_max_length_int [22992](#)
 - __sort_merge_blocks:
 - [23128](#), [23133](#), [23327](#)
 - __sort_merge_blocks_aux:
 - [939](#), [23149](#), [23163](#), [23216](#), [23226](#), [23326](#)
 - __sort_merge_blocks_end:
 - [941](#), [23224](#), [23228](#)
 - \l_sort_min_int [934](#), [935](#), [937](#), [937](#),
 - [22953](#), [22969](#), [22977](#), [22995](#), [23011](#),
 - [23019](#), [23032](#), [23044](#), [23053](#), [23063](#),
 - [23077](#), [23116](#), [23127](#), [23354](#), [23355](#)
 - __sort_quick_cleanup:w [23238](#)
 - __sort_quick_end:nnTFNn
 - [945](#), [946](#), [23258](#), [23298](#)
 - __sort_quick_only_i:NnnnnNn . [23263](#)
 - __sort_quick_only_i_end:nnwnw .
 - [23274](#), [23298](#)
 - __sort_quick_only_ii:NnnnnNn . [23263](#)
 - __sort_quick_only_ii_end:nnwnw
 - [23281](#), [23298](#)
 - __sort_quick_prepare:Nnnn ... [23238](#)

- _sort_quick_prepare_end:NNnw [23238](#)
- _sort_quick_single_end:nnwnw [23267](#), [23298](#)
- _sort_quick_split:NnNn [944](#), [944](#), [23258](#), [23263](#), [23303](#), [23310](#), [23316](#), [23318](#)
- _sort_quick_split_end:nnwnw [23288](#), [23295](#), [23298](#)
- _sort_quick_split_i:NnnnnNn [943](#), [23263](#)
- _sort_quick_split_ii:NnnnnNn [23263](#)
- _sort_redefine_compute_range: [22992](#)
- _sort_return_mark:w [940](#), [23169](#), [23170](#), [23174](#)
- _sort_return_none_error: [940](#), [23172](#), [23174](#), [23208](#), [23218](#)
- _sort_return_same:w [940](#), [23182](#), [23200](#), [23208](#)
- _sort_return_swapped:w [23192](#), [23218](#)
- _sort_return_two_error: [940](#), [23174](#)
- _sort_seq:NNNNn [937](#), [23091](#)
- _sort_shrink_range: [935](#), [935](#), [22966](#), [22997](#), [23013](#), [23021](#), [23034](#)
- _sort_shrink_range_loop: [22966](#)
- _sort_tl:NnNn [937](#), [23068](#)
- _sort_tl_toks:w [937](#), [23068](#)
- _sort_too_long_error:NNw [23057](#), [23349](#)
- \l_sort_top_int [934](#), [937](#), [937](#), [940](#), [940](#), [22953](#), [23053](#), [23056](#), [23059](#), [23060](#), [23063](#), [23085](#), [23116](#), [23137](#), [23140](#), [23141](#), [23144](#), [23213](#), [23355](#)
- \l_sort_true_max_int [934](#), [935](#), [22953](#), [22969](#), [22982](#), [22996](#), [23012](#), [23020](#), [23033](#), [23045](#), [23354](#)
- sp [216](#)
- spac commands:
 - \spac_directions_normal_body_dir [1455](#)
 - \spac_directions_normal_page_dir [1456](#)
- \spacefactor [545](#)
- \spaceskip [546](#)
- \span [547](#)
- \special [548](#)
- \splitbotmark [549](#)
- \splitbotmarks [662](#), [1533](#)
- \splitdiscards [663](#), [1534](#)
- \splitfirstmark [550](#)
- \splitfirstmarks [664](#), [1535](#)
- \splitmaxdepth [551](#)
- \splittopskip [552](#)
- sqrt [214](#)
- \SS [29534](#), [30965](#), [31301](#)
- \ss [29534](#), [30965](#), [31297](#)
- str commands:
 - \c_ampersand_str [71](#), [5899](#)
 - \c_atsign_str [71](#), [5899](#)
 - \c_backslash_str [71](#), [5899](#), [6595](#), [6597](#), [6620](#), [6649](#), [6651](#), [6683](#), [6692](#), [6696](#), [24121](#), [24693](#)
 - \c_circumflex_str [71](#), [5899](#)
 - \c_colon_str [71](#), [5899](#), [11396](#), [11501](#), [11507](#), [15411](#)
 - \c_dollar_str [71](#), [5899](#)
 - \l_foo_str [72](#)
 - \c_hash_str [71](#), [5899](#), [6563](#), [6666](#), [29314](#), [29345](#), [29346](#), [29350](#)
 - \c_percent_str [71](#), [5899](#), [6565](#), [6719](#)
 - str_byte [5949](#)
 - \str_case:nn [64](#), [5457](#), [12959](#), [14217](#), [24842](#), [31930](#)
 - \str_case:nnn [32414](#), [32416](#)
 - \str_case:nnTF [64](#), [675](#), [5457](#), [5462](#), [5467](#), [9923](#), [9945](#), [10182](#), [12883](#), [15588](#), [25406](#), [32415](#), [32417](#)
 - \str_case_e:nn [64](#), [5457](#), [32676](#), [32677](#)
 - \str_case_e:nnTF [64](#), [3343](#), [5457](#), [5493](#), [5498](#), [6618](#), [24574](#), [32419](#), [32678](#), [32679](#), [32680](#), [32681](#), [32682](#), [32683](#)
 - \str_case_x:nn [32676](#)
 - \str_case_x:nnn [32418](#)
 - \str_case_x:nnTF [32676](#), [32679](#), [32681](#)
 - \str_clear:N [61](#), [61](#), [5288](#), [14416](#), [14428](#), [15362](#), [15546](#), [15965](#), [15966](#)
 - \str_clear_new:N [61](#), [5288](#)
 - \str_concat:NNN [61](#), [5288](#)
 - \str_const:Nn [60](#), [5315](#), [5899](#), [5900](#), [5901](#), [5902](#), [5903](#), [5904](#), [5905](#), [5906](#), [5907](#), [5908](#), [5909](#), [5910](#), [6659](#), [6660](#), [6682](#), [9883](#), [9914](#), [10148](#), [14550](#), [14557](#), [14561](#), [14565](#), [15283](#), [15284](#), [15285](#), [15286](#), [15287](#), [15288](#), [15289](#), [31928](#)
 - \str_count:N [66](#), [5789](#), [12213](#), [12214](#), [12400](#), [12401](#), [12422](#), [12423](#), [13399](#), [13477](#), [23799](#)
 - \str_count:n [66](#), [5789](#), [23793](#)
 - \str_count_ignore_spaces:n [66](#), [432](#), [5789](#), [23414](#)
 - \str_count_spaces:N [66](#), [5769](#)
 - \str_count_spaces:n [66](#), [432](#), [5769](#), [5795](#)
 - \str_declare_eight_bit_encoding:nnn [74](#), [448](#), [6324](#), [7217](#), [7224](#), [7288](#),

- 7330, 7387, 7488, 7575, 7661, 7735,
 7748, 7801, 7899, 7962, 8000, 8015
 str_end [7118](#)
 str_error [5949](#)
 \str_fold_case:n [32664](#)
 \str_foldcase:n
 [69](#), [70](#), [129](#), [257](#), [5857](#),
 [17662](#), [32672](#), [32673](#), [32674](#), [32675](#)
 \str_gclear:N [61](#), [5288](#)
 \str_gclear_new:N [5288](#)
 \str_gconcat:NNN [61](#), [5288](#)
 \str_gput_left:Nn [61](#), [5315](#)
 \str_gput_right:Nn [62](#), [5315](#)
 \str_gremove_all:Nn [62](#), [5385](#)
 \str_gremove_once:Nn [62](#), [5379](#)
 \str_greplace_all:Nnn [62](#), [5339](#), [5388](#)
 \str_greplace_once:Nnn [62](#), [5339](#), [5382](#)
 \str_gset:Nn
 [61](#), [5315](#), [14396](#), [14397](#), [14398](#)
 \str_gset_convert:Nnnn [72](#), [6086](#)
 \str_gset_convert:NnnnTF ... [74](#), [6086](#)
 \str_gset_eq:NN
 [61](#), [5288](#), [14379](#), [14380](#), [14381](#)
 \str_head:N [67](#), [432](#), [5827](#)
 \str_head:n
 .. [67](#), [411](#), [432](#), [433](#), [5012](#), [5059](#), [5827](#)
 \str_head_ignore_spaces:n .. [67](#), [5827](#)
 \str_if_empty:NTF [63](#), [5391](#), [14050](#),
 [14410](#), [15345](#), [15370](#), [15986](#), [16184](#)
 \str_if_empty_p:N [63](#), [5391](#)
 \str_if_eq:NN [423](#)
 \str_if_eq:nn [143](#), [595](#), [603](#)
 \str_if_eq:NNTF [63](#), [5435](#)
 \str_if_eq:nnTF [63](#),
 [64](#), [64](#), [146](#), [147](#), [492](#), [585](#), [2736](#),
 [3364](#), [4654](#), [5421](#), [5484](#), [5512](#), [7000](#),
 [7003](#), [7158](#), [7161](#), [8235](#), [9907](#), [9937](#),
 [10058](#), [11399](#), [11455](#), [11829](#), [11902](#),
 [11997](#), [12541](#), [12584](#), [14489](#), [14504](#),
 [14978](#), [15366](#), [15385](#), [15454](#), [16013](#),
 [17531](#), [17605](#), [24169](#), [24191](#), [24200](#),
 [26868](#), [26998](#), [29325](#), [29344](#), [29348](#),
 [29800](#), [30116](#), [31151](#), [32318](#), [32686](#),
 [32687](#), [32688](#), [32689](#), [32690](#), [32691](#)
 \str_if_eq_p:NN [63](#), [5435](#)
 \str_if_eq_p:nn .. [63](#), [5421](#), [9898](#),
 [10156](#), [10158](#), [14569](#), [32684](#), [32685](#)
 \str_if_eq_x:nnTF [32676](#), [32687](#), [32689](#)
 \str_if_eq_x_p:nn [32676](#)
 \str_if_exist:NTF [63](#), [5391](#), [9905](#)
 \str_if_exist_p:N [63](#), [5391](#)
 \str_if_in:NnTF [63](#), [5443](#)
 \str_if_in:nnTF [63](#), [3895](#), [5443](#)
 \str_item:Nn [67](#), [5631](#)
 \str_item:nn [67](#), [427](#), [432](#), [5631](#)
 \str_item_ignore_spaces:nn
 [67](#), [427](#), [5631](#)
 \str_log:N [70](#), [5915](#)
 \str_log:n [70](#), [5915](#)
 \str_lower_case:n [32664](#)
 \str_lowercase:n [69](#),
 [257](#), [5857](#), [32664](#), [32665](#), [32666](#), [32667](#)
 \str_map_break: [65](#), [5518](#)
 \str_map_break:n ... [65](#), [66](#), [3899](#), [5518](#)
 \str_map_function:NN
 [64](#), [64](#), [65](#), [65](#), [5518](#)
 \str_map_function:nN [64](#), [64](#), [425](#), [5518](#)
 \str_map_inline:Nn .. [65](#), [65](#), [65](#), [5518](#)
 \str_map_inline:nn
 [65](#), [3893](#), [5518](#), [25830](#)
 \str_map_variable:NNn [65](#), [5518](#)
 \str_map_variable:nNn [65](#), [5518](#)
 \str_new:N [60](#), [61](#), [5288](#), [5911](#), [5912](#),
 [5913](#), [5914](#), [12090](#), [12091](#), [13714](#),
 [13715](#), [13716](#), [13754](#), [13755](#), [13756](#),
 [15293](#), [15295](#), [15298](#), [15300](#), [15303](#)
 str_overflow [7118](#)
 \str_put_left:Nn [61](#), [5315](#), [14413](#)
 \str_put_right:Nn ... [62](#), [5315](#), [15984](#)
 \str_range:Nnn [68](#), [5692](#)
 \str_range:nnn [68](#), [165](#), [432](#), [5692](#), [23796](#)
 \str_range_ignore_spaces:nnn [68](#), [5692](#)
 \str_remove_all:Nn [62](#), [62](#), [5385](#)
 \str_remove_once:Nn [62](#), [5379](#)
 \str_replace_all:Nnn . [62](#), [5339](#), [5386](#)
 \str_replace_once:Nnn [62](#), [5339](#), [5380](#)
 \str_set:Nn [61](#), [62](#),
 [5315](#), [5577](#), [12176](#), [12177](#), [12388](#),
 [12389](#), [12410](#), [12411](#), [14410](#), [14425](#),
 [14432](#), [15324](#), [15326](#), [15354](#), [15368](#),
 [15374](#), [15377](#), [15387](#), [15388](#), [15391](#),
 [15831](#), [15833](#), [15976](#), [15982](#), [16089](#)
 \str_set_convert:Nnnn
 [72](#), [74](#), [74](#), [440](#), [450](#), [6086](#)
 \str_set_convert:NnnnTF [74](#), [440](#), [6086](#)
 \str_set_eq:NN [61](#), [5288](#), [14415](#)
 \str_show:N [70](#), [5915](#)
 \str_show:n [70](#), [5915](#)
 \str_tail:N [67](#), [5842](#)
 \str_tail:n [67](#), [953](#), [5842](#), [14432](#), [29427](#)
 \str_tail_ignore_spaces:n .. [67](#), [5842](#)
 \str_upper_case:n [32664](#)
 \str_uppercase:n [69](#),
 [257](#), [5857](#), [32668](#), [32669](#), [32670](#), [32671](#)
 \str_use:N [66](#), [5288](#)
 \c_tilde_str [71](#), [5899](#)
 \g_tmpa_str [71](#), [5911](#)
 \l_tmpa_str [62](#), [71](#), [5911](#)

- \g_tmpb_str [71](#), [5911](#)
- \l_tmpb_str [71](#), [5911](#)
- \c_underscore_str [71](#), [5899](#)
- str internal commands:
 - \g_str_alias_prop .. [443](#), [5932](#), [6157](#)
 - \c_str_byte_1_t1 [6000](#)
 - \c_str_byte_0_t1 [6000](#)
 - \c_str_byte_1_t1 [6000](#)
 - \c_str_byte_255_t1 [6000](#)
 - \c_str_byte_<number>_t1 [438](#)
 - _str_case:nnTF [5457](#)
 - _str_case:nw [5457](#)
 - _str_case_e:nnTF [5457](#)
 - _str_case_e:nw [5457](#)
 - _str_case_end:nw [5457](#)
 - _str_change_case:nn [5857](#)
 - _str_change_case_aux:nn [5857](#)
 - _str_change_case_char:nN ... [5857](#)
 - _str_change_case_end:nw [5857](#)
 - _str_change_case_end:wn [5876](#), [5894](#)
 - _str_change_case_loop:nw ... [5857](#)
 - _str_change_case_output:nw . [5857](#)
 - _str_change_case_result:n .. [5857](#)
 - _str_change_case_space:n ... [5857](#)
 - _str_collect_delimit_by_q-
stop:w [5720](#), [5743](#)
 - _str_collect_end:nnnnnnnw ...
..... [430](#), [5743](#)
 - _str_collect_end:wn [5743](#)
 - _str_collect_loop:wn [5743](#)
 - _str_collect_loop:wnNNNNNNN . [5743](#)
 - _str_convert:nnn
..... [442](#), [443](#), [6129](#), [6130](#), [6144](#)
 - _str_convert:nnnn [443](#), [6144](#)
 - _str_convert:NNnNN [6126](#)
 - _str_convert:nNNnnn [6086](#)
 - _str_convert:wwwn
..... [442](#), [6113](#), [6118](#), [6126](#)
 - _str_convert_decode_ : .. [6117](#), [6267](#)
 - _str_convert_decode_clist: . [6307](#)
 - _str_convert_decode_eight_
bit:n [6328](#), [6334](#)
 - _str_convert_decode_utf16: . [6989](#)
 - _str_convert_decode_utf16be: [6989](#)
 - _str_convert_decode_utf16le: [6989](#)
 - _str_convert_decode_utf32: . [7147](#)
 - _str_convert_decode_utf32be: [7147](#)
 - _str_convert_decode_utf32le: [7147](#)
 - _str_convert_decode_utf8: .. [6808](#)
 - _str_convert_encode_ : .. [6122](#), [6271](#)
 - _str_convert_encode_clist: . [6318](#)
 - _str_convert_encode_eight_
bit:n [6330](#), [6380](#)
 - _str_convert_encode_utf16: . [6904](#)
 - _str_convert_encode_utf16be: [6904](#)
 - _str_convert_encode_utf16le: [6904](#)
 - _str_convert_encode_utf32: . [7087](#)
 - _str_convert_encode_utf32be: [7087](#)
 - _str_convert_encode_utf32le: [7087](#)
 - _str_convert_encode_utf8: .. [6735](#)
 - _str_convert_escape_ : [6265](#)
 - _str_convert_escape_bytes: . [6265](#)
 - _str_convert_escape_hex: ... [6655](#)
 - _str_convert_escape_name: [457](#), [6659](#)
 - _str_convert_escape_string: . [6682](#)
 - _str_convert_escape_url: ... [6714](#)
 - _str_convert_gmap:N [6044](#),
[6268](#), [6347](#), [6656](#), [6662](#), [6685](#), [6715](#)
 - _str_convert_gmap_internal:N ..
..... [6060](#), [6278](#), [6286](#), [6320](#),
[6389](#), [6736](#), [6917](#), [7089](#), [7093](#), [7095](#)
 - _str_convert_gmap_internal_
loop:Nw [6060](#)
 - _str_convert_gmap_internal_
loop:Nww [6064](#), [6070](#), [6074](#)
 - _str_convert_gmap_loop:NN .. [6044](#)
 - _str_convert_lowercase_
alphanum:n [6149](#), [6181](#)
 - _str_convert_lowercase_
alphanum_loop:N [6181](#)
 - _str_convert_unescape_ : [6249](#)
 - _str_convert_unescape_bytes: [6249](#)
 - _str_convert_unescape_hex: . [6471](#)
 - _str_convert_unescape_name: ...
..... [452](#), [6517](#)
 - _str_convert_unescape_string: [6567](#)
 - _str_convert_unescape_url: . [6517](#)
 - _str_count:n . [432](#), [5647](#), [5707](#), [5789](#)
 - _str_count_aux:n [5789](#)
 - _str_count_loop:NNNNNNNNN .. [5789](#)
 - _str_count_spaces_loop:w ... [5769](#)
 - _str_decode_clist_char:n ... [6307](#)
 - _str_decode_eight_bit_char:N [6334](#)
 - _str_decode_eight_bit_load:nn [6334](#)
 - _str_decode_eight_bit_load_
missing:n [6334](#)
 - _str_decode_native_char:N .. [6267](#)
 - _str_decode_utf_viii_aux:wNnnwN
..... [6808](#)
 - _str_decode_utf_viii_continuation:wwN
..... [6808](#)
 - _str_decode_utf_viii_end: .. [6808](#)
 - _str_decode_utf_viii_overflow:w
..... [6808](#)
 - _str_decode_utf_viii_start:N [6808](#)
 - _str_decode_utf_xvi:Nw .. [465](#), [6989](#)
 - _str_decode_utf_xvi_bom:NN . [6989](#)
 - _str_decode_utf_xvi_error:nNN [7023](#)

- __str_decode_utf_xvi_extra:NNw [7023](#)
- __str_decode_utf_xvi_pair:NN ...
 ... [465](#), [466](#), [7017](#), [7023](#)
- __str_decode_utf_xvi_pair_-
 end:Nw ... [7023](#)
- __str_decode_utf_xvi_quad:NNwNN
 ... [7023](#)
- __str_decode_utf_xxii:Nw [469](#), [7147](#)
- __str_decode_utf_xxii_bom:NNNN
 ... [7147](#)
- __str_decode_utf_xxii_end:w . [7147](#)
- __str_decode_utf_xxii_loop:NNNN
 ... [7147](#)
- __str_encode_clist_char:n ... [6318](#)
- __str_encode_eight_bit_char:n [6380](#)
- __str_encode_eight_bit_char_-
 aux:n ... [6380](#)
- __str_encode_eight_bit_load:nn [6380](#)
- __str_encode_native_char:n . [6271](#)
- __str_encode_utf_vii_loop:wwnw [458](#)
- __str_encode_utf_viii_char:n . [6735](#)
- __str_encode_utf_viii_loop:wwnw
 ... [6735](#)
- __str_encode_utf_xvi_aux:N . [6904](#)
- __str_encode_utf_xvi_be:nn ... [463](#)
- __str_encode_utf_xvi_char:n . [6904](#)
- __str_encode_utf_xxii_be:n . [7087](#)
- __str_encode_utf_xxii_be_-
 aux:nn ... [7087](#)
- __str_encode_utf_xxii_le:n . [7087](#)
- __str_encode_utf_xxii_le_-
 aux:nn ... [7087](#)
- \l__str_end_flag ... [6938](#)
- \g__str_error_bool ...
 ... [5948](#), [6083](#), [6093](#), [6097](#), [6102](#), [6106](#)
- __str_escape:n ... [5399](#)
- __str_escape_hex_char:N ... [6655](#)
- __str_escape_name_char:N ... [6659](#)
- \c__str_escape_name_not_str [456](#), [6659](#)
- \c__str_escape_name_str ... [456](#), [6659](#)
- __str_escape_string_char:N . [6682](#)
- \c__str_escape_string_str ... [6682](#)
- __str_escape_url_char:N ... [6714](#)
- \l__str_extra_flag ... [6757](#), [6938](#)
- __str_filter_bytes:n ...
 ... [6225](#), [6259](#), [6537](#), [6599](#)
- __str_filter_bytes_aux:N ... [6225](#)
- __str_head:w ... [433](#), [5827](#)
- __str_hexadecimal_use:N ... [5981](#)
- __str_hexadecimal_use:Ntf ...
 ... [453](#), [5981](#), [6491](#), [6501](#), [6540](#), [6542](#)
- __str_if_contains_char:NN ... [5951](#)
- __str_if_contains_char:nN ... [5958](#)
- __str_if_contains_char:Ntf ...
 ... [5951](#), [6671](#), [6677](#), [6690](#)
- __str_if_contains_char:nNtf ...
 ... [437](#), [5951](#), [6724](#), [6730](#)
- __str_if_contains_char_aux:NN [5951](#)
- __str_if_contains_char_true: . [5951](#)
- __str_if_eq:nn [5399](#), [5424](#), [5432](#), [5438](#)
- __str_if_escape_name:N ... [6668](#)
- __str_if_escape_name:Ntf ... [6659](#)
- __str_if_escape_string:N ... [6702](#)
- __str_if_escape_string:Ntf . [6682](#)
- __str_if_escape_url:N ... [6721](#)
- __str_if_escape_url:Ntf ... [6714](#)
- __str_if_flag_error:nnn ...
 . [440](#), [441](#), [6076](#), [6095](#), [6104](#), [6260](#),
 [6287](#), [6348](#), [6390](#), [6485](#), [6531](#), [6532](#),
 [6590](#), [6591](#), [6821](#), [6918](#), [7021](#), [7178](#)
- __str_if_flag_no_error:nnn ...
 ... [440](#), [6076](#), [6095](#), [6104](#)
- __str_if_flag_times:Ntf ...
 ... [6084](#), [6766](#), [6767](#), [6768](#),
 [6769](#), [6953](#), [6954](#), [6955](#), [7125](#), [7126](#)
- __str_if_recursion_tail_-
 break:NN ... [5286](#), [5558](#), [5576](#)
- __str_if_recursion_tail_stop_-
 do:Nn ... [5286](#), [5893](#)
- \l__str_internal_int ...
 ... [5924](#), [6337](#), [6354](#), [6355](#), [6356](#),
 [6357](#), [6363](#), [6364](#), [6365](#), [6367](#), [6373](#),
 [6383](#), [6396](#), [6397](#), [6398](#), [6400](#), [6408](#)
- \l__str_internal_tl ... [443](#),
 [5924](#), [6001](#), [6002](#), [6004](#), [6157](#), [6158](#),
 [6159](#), [6161](#), [6165](#), [6169](#), [6176](#), [6326](#)
- __str_item:nn ... [427](#), [5631](#)
- __str_item:w ... [428](#), [5631](#)
- __str_load_catcodes: . [6164](#), [6207](#)
- __str_map_function:Nn ... [425](#), [5518](#)
- __str_map_function:w ... [425](#), [5518](#)
- __str_map_inline:NN ... [5518](#)
- __str_map_variable:NnN ... [5518](#)
- \c__str_max_byte_int [5929](#), [6292](#), [6419](#)
- \l__str_missing_flag ... [6757](#), [6938](#)
- __str_octal_use:N ... [5973](#)
- __str_octal_use:Ntf ...
 ... [437](#), [438](#), [5973](#), [6602](#), [6604](#), [6606](#)
- __str_output_byte:n ...
 ... [468](#), [6012](#), [6041](#), [6042](#), [6202](#),
 [6399](#), [6422](#), [6749](#), [6755](#), [7105](#), [7114](#)
- __str_output_byte:w ...
 ... [453](#), [6012](#), [6478](#), [6504](#), [6539](#), [6601](#)
- __str_output_byte_pair:nnN . [6028](#)
- __str_output_byte_pair_be:n ...
 ... [6028](#), [6906](#), [6910](#), [7104](#)

- __str_output_byte_pair_le:n . . .
 [6028](#), [6912](#), [7115](#)
- __str_output_end:
 [453](#), [6012](#), [6483](#), [6503](#), [6553](#), [6635](#), [6639](#)
- __str_output_hexadecimal:n
 [6012](#), [6658](#), [6666](#), [6719](#)
- \l__str_overflow_flag [6757](#)
- \l__str_overlong_flag [6757](#)
- __str_range:nnn [5692](#)
- __str_range:nnw [5692](#)
- __str_range:w [5692](#)
- __str_range_normalize:nn
 [5715](#), [5716](#), [5724](#)
- __str_replace:NNNnn [5339](#)
- __str_replace_aux:NNNnnn [5339](#)
- __str_replace_next:w [5339](#)
- \c__str_replacement_char_int . . .
 [5928](#), [6366](#), [6833](#), [6857](#), [6871](#), [6891](#),
 [6898](#), [6928](#), [7080](#), [7189](#), [7194](#), [7210](#)
- \g__str_result_tl
 [435](#), [439](#), [440](#), [441](#), [446](#), [447](#), [452](#),
 [465](#), [468](#), [469](#), [5927](#), [6046](#), [6050](#),
 [6062](#), [6066](#), [6112](#), [6124](#), [6258](#), [6259](#),
 [6309](#), [6310](#), [6313](#), [6321](#), [6476](#), [6480](#),
 [6525](#), [6527](#), [6578](#), [6581](#), [6584](#), [6587](#),
 [6815](#), [6817](#), [6907](#), [6990](#), [6992](#), [6996](#),
 [7015](#), [7090](#), [7148](#), [7150](#), [7153](#), [7172](#)
- __str_skip_end:NNNNNNNN
 [428](#), [429](#), [5671](#)
- __str_skip_end:w [5671](#)
- __str_skip_exp_end:w
 [429](#), [430](#), [5658](#), [5667](#), [5671](#), [5722](#)
- __str_skip_loop:wNNNNNNNN . . . [5671](#)
- __str_tail_auxi:w [5842](#)
- __str_tail_auxii:w [433](#), [5842](#)
- __str_tmp:n
 . . . [5289](#), [5295](#), [5298](#), [5316](#), [5326](#), [5329](#)
- __str_tmp:w [452](#), [463](#), [465](#),
 [469](#), [5924](#), [6517](#), [6563](#), [6565](#), [6570](#),
 [6595](#), [6916](#), [6923](#), [6928](#), [6930](#), [6933](#),
 [6934](#), [7014](#), [7029](#), [7034](#), [7045](#), [7048](#),
 [7054](#), [7055](#), [7171](#), [7186](#), [7191](#), [7197](#)
- __str_to_other_end:w [426](#), [5586](#)
- __str_to_other_fast_end:w . . . [5609](#)
- __str_to_other_fast_loop:w
 [5611](#), [5620](#), [5627](#)
- __str_to_other_loop:w [426](#), [5586](#)
- __str_unescape_hex_auxi:N . . . [6471](#)
- __str_unescape_hex_auxii:N . . . [6471](#)
- __str_unescape_name_loop:wNN . . [6517](#)
- __str_unescape_string_loop:wNNN
 [6567](#)
- __str_unescape_string_newlines:wN
 [6567](#)
- __str_unescape_string_repeat:NNNNNN
 [6567](#)
- __str_unescape_url_loop:wNN . . [6517](#)
- __str_use_i_delimit_by_s_-
 stop:nw [433](#),
 [5282](#), [5657](#), [5666](#), [5785](#), [5836](#), [5839](#)
- __str_use_none_delimit_by_s_-
 stop:w
 . . . [5282](#), [5373](#), [5655](#), [5664](#), [5823](#),
 [6072](#), [6353](#), [6362](#), [6395](#), [6750](#), [6840](#)
- \strcmp [40](#)
- \string [553](#)
- \suppressfontnotfounderror . . . [815](#), [1704](#)
- \suppressifcsnameerror [998](#), [1851](#)
- \suppresslongerror [999](#), [1853](#)
- \suppressmathparerror [1000](#), [1854](#)
- \suppressoutererror [1001](#), [1856](#)
- \suppressprimitiveerror [1002](#), [1857](#)
- \synctex [797](#), [1666](#)
- sys commands:
- \c_sys_backend_str [117](#), [9902](#)
- \c_sys_day_int [114](#), [10053](#)
- \c_sys_engine_str [114](#), [9883](#), [31930](#)
- \c_sys_engine_version_str . . . [267](#), [31928](#)
- \sys_everyjob: [10043](#), [10139](#)
- \sys_finalise: [117](#), [9904](#), [10137](#)
- \sys_get_shell:nnN [116](#), [9975](#)
- \sys_get_shell:nnN(TF) [262](#)
- \sys_get_shell:nnNTF [116](#), [9975](#), [9977](#)
- \sys_gset_rand_seed:n [115](#), [215](#), [10099](#)
- \c_sys_hour_int [114](#), [10053](#)
- \sys_if_engine luatex:TF
 [114](#), [252](#), [3350](#), [9883](#), [10015](#), [10017](#),
 [10030](#), [10118](#), [10969](#), [10971](#), [13113](#),
 [13896](#), [13909](#), [14090](#), [14152](#), [14174](#),
 [14243](#), [14302](#), [14363](#), [14548](#), [16933](#),
 [29010](#), [29223](#), [32387](#), [32389](#), [32391](#)
- \sys_if_engine luatex_p:
 [114](#), [6227](#), [6251](#),
 [6273](#), [6440](#), [9883](#), [13260](#), [13990](#),
 [14024](#), [14072](#), [14208](#), [29214](#), [30128](#),
 [30142](#), [30178](#), [30218](#), [30266](#), [30302](#),
 [30396](#), [30403](#), [30481](#), [30559](#), [30637](#),
 [30660](#), [30694](#), [31241](#), [31326](#), [32385](#)
- \sys_if_engine pdftex:TF
 [114](#), [9883](#), [32395](#), [32397](#), [32399](#)
- \sys_if_engine pdftex_p:
 [114](#), [9883](#), [32393](#)
- \sys_if_engine ptex:TF [114](#), [9883](#)
- \sys_if_engine ptex_p:
 [114](#), [9883](#), [23432](#)
- \sys_if_engine uptex:TF [114](#), [9883](#)
- \sys_if_engine uptex_p:
 [114](#), [9883](#), [23433](#)

- \sys_if_engine_xetex:TF
 5, 114, 3349, 9883, 9921,
 10165, 10970, 32433, 32435, 32437
 - \sys_if_engine_xetex_p:
 114, 6228, 6252, 6274,
 6441, 9883, 10064, 29214, 30129,
 30143, 30179, 30219, 30267, 30303,
 30397, 30404, 30482, 30560, 30638,
 30661, 30695, 31242, 31327, 32431
 - \sys_if_output_dvi:TF ... 115, 10146
 - \sys_if_output_dvi_p: ... 115, 10146
 - \sys_if_output_pdf:TF
 115, 9935, 10146, 10168
 - \sys_if_output_pdf_p: ... 115, 10146
 - \sys_if_platform_unix:TF
 115, 9902, 14566
 - \sys_if_platform_unix_p:
 115, 9902, 14566
 - \sys_if_platform_windows:TF
 115, 9902, 14566
 - \sys_if_platform_windows_p:
 115, 9902, 14566
 - \sys_if_rand_exist:TF
 267, 542, 9900,
 10087, 10101, 16493, 22486, 22510
 - \sys_if_rand_exist_p: 267, 9900
 - \sys_if_shell: 116
 - \sys_if_shell:TF
 116, 9982, 10126, 31984
 - \sys_if_shell_p: 116, 10126
 - \sys_if_shell_restricted:TF
 116, 10126
 - \sys_if_shell_restricted_p:
 116, 10126
 - \sys_if_shell_unrestricted:TF ...
 116, 10126
 - \sys_if_shell_unrestricted_p: ...
 116, 10126
 - \c_sys_jobname_str
 114, 163, 549, 10051, 32341
 - \sys_load_backend:n .. 117, 117, 9902
 - \sys_load_debug: 117, 9961
 - \sys_load_deprecation: 117, 9961
 - \c_sys_minute_int 114, 10053
 - \c_sys_month_int 114, 10053
 - \c_sys_output_str 115, 10146
 - \c_sys_platform_str
 115, 9902, 14548, 14569
 - \sys_rand_seed: .. 80, 115, 215, 10085
 - \c_sys_shell_escape_int
 116, 10114, 10129, 10131, 10133
 - \sys_shell_now:n 116, 10017
 - \sys_shell_shipout:n 116, 10030
 - \c_sys_year_int 114, 10053
- sys internal commands:
- \g_sys_backend_tl
 9912, 9913, 9914, 10160
 - __sys_const:nn . 9867, 9897, 9900,
 10128, 10130, 10132, 10155, 10157
 - \g_sys_debug_bool .. 9959, 9963, 9965
 - \g_sys_deprecation_bool
 1189, 9959, 9969, 9971
 - __sys_everyjob:n
 10043, 10051, 10053,
 10085, 10099, 10114, 10126, 10135
 - \g_sys_everyjob_tl 10043
 - __sys_finalise:n
 10137, 10146, 10161, 10174
 - \g_sys_finalise_tl 10137
 - __sys_get:nnN 9975
 - __sys_get_do:Nw 9975
 - \l_sys_internal_tl 9973
 - __sys_load_backend_check:N .. 9902
 - \c_sys_marker_tl .. 9974, 9998, 10010
 - \c_sys_shell_stream_int
 10015, 10027, 10040
 - __sys_tmp:w 10056,
 10077, 10079, 10080, 10081, 10082
- syst commands:
- \c_syst_last_allocated_toks .. 23026
- T
- \t 29521, 31366
 - \tabskip 554
 - \tagcode 798, 1667
 - \tan 213
 - \tand 213
 - \tate 1258, 2077
 - \tbaselineshift 1259, 2078
 - \temp . 164, 170, 175, 178, 179, 186, 191, 194
- TeX and L^AT_EX 2_ε commands:
- \@ 5900
 - \@@end 297, 1289, 1290
 - \@@hyph 1293
 - \@@input 1294
 - \@@italiccorr 1295
 - \@@shipout 1297, 1298
 - \@@tracingfonts 298, 1333
 - \@@underline 1296
 - \@addtofilelist 14358
 - \@changed@cmd 29831
 - \@classoptionslist 10176, 10178, 10180
 - \@current@cmd 29828
 - \@currnamestack
 650, 13737, 13739, 13740
 - \@filelist 167, 651, 665, 667,
 668, 14357, 14446, 14449, 14460, 14465
 - \@firstofone 19

- \@firstoftwo 19, 324
- \@gobbbbletwo 20
- \@gobble 20
- \@secondoftwo 19, 324
- \@tempa 144, 146, 1305, 1319, 1322
- \@tfor 298, 1305
- \@uclclist 1153, 30999
- \@unexpandable@protect 768
- \@unusedoptionlist 10195
- \AtBeginDocument 298
- \botmark 587
- \box 242
- \char 141
- \chardef 136, 136, 508, 531, 1119
- \color 1102
- \conditionally@traceoff
..... 643, 12484, 13457
- \conditionally@tracelon 12502
- \copy 235
- \count 141, 448, 935
- \cr 541
- \CROP@shipout 1306
- \csname 17
- \csstring 333
- \currentgrouplevel 345, 1170
- \currentgrouptype 345, 1170
- \def 141
- \detokenize 51
- \dimen 585
- \dimendef 585
- \directlua 252
- \dp 236, 769, 770
- \dup@shipout 1307
- \e@alloc@top 935, 23012
- \edef 1, 4, 387
- \end 614
- \endcsname 17
- \endinput 153
- \endlinechar 46, 46, 158, 391, 392, 587
- \endtemplate 113, 541
- \errhelp 609, 610
- \errmessage 609, 610, 610, 611
- \errorcontextlines 315, 417, 611, 1061
- \escapechar 51, 333, 345, 642
- \everyeof 393
- \everyjob 546
- \everypar 24, 347, 365
- \expandafter 33, 35
- \expanded 4, 20, 28,
30, 349, 352, 358, 360, 365, 372, 391
- \fi 140
- \firstmark 366, 587
- \font 140
- \fontdimen
... 197, 233, 721, 722, 723, 724, 724
- \frozen@everydisplay 1291
- \frozen@everymath 1292
- \futurelet
... 541, 589, 591, 949, 951, 953, 953
- \global 278
- \GPTorg@shipout 1308
- \halign 113, 347, 541, 575
- \hskip 179
- \ht 236, 769, 770
- \hyphen 587
- \hyphenchar 721
- \ifcase 100
- \ifdim 182
- \ifeof 163
- \iffalse 106
- \ifhbox 245
- \ifnum 100
- \ifodd 101, 593
- \iftrue 106
- \ifvbox 245
- \ifvoid 245
- \ifx 23, 274
- \indent 347
- \infty 208
- \input@path
164, 656, 13931, 13933, 14034, 14036
- \italiccorr 587
- \jobname 114, 546
- \lastnamedcs 336
- \lccode 274, 527, 952, 956, 1114
- \leavevmode 24
- \let 278
- \latcharcode 571
- \LL@shipout 1309
- \loctoks 935
- \long 3, 141, 142, 360
- \lower 1167
- \lowercase 1038, 1039, 1039
- \luaescapestring 252
- \makeatletter 7
- \MakeUppercase 1150
- \mathchar 141
- \mathchardef 136, 508, 1119
- \meaning
15, 133, 141, 585, 585, 591, 593, 951
- \mem@oldshipout 1310
- \message 28
- \newif 106, 259
- \newlinechar 46,
46, 315, 336, 391, 392, 417, 611, 640
- \newread 631
- \newtoks 220, 947, 964

- `\newwrite` 638
- `\noexpand` 34, 140, 359, 360, 360, 361, 362
- `\nullfont` 587
- `\number` 100, 822
- `\numexpr` 363
- `\opem@shipout` 1311
- `\or` 100
- `\outer` 141, 142, 274, 593, 631, 638, 1183, 1184, 1186
- `\parindent` 24
- `\pdfescapehex` 451
- `\pdfescapename` 73, 451
- `\pdfescapestring` 73, 451
- `\pdffilesize` 656
- `\pdfmapfile` 300
- `\pdfmapline` 300
- `\pdfstrcmp` xiii, 271, 272, 274, 288, 1113
- `\pdfuniformdeviate` 215
- `\pgfpages@originalshipout` 1312
- `\pi` 208
- `\pr@shipout` 1313
- `\primitive` 298, 359, 360, 360, 547
- `\protect` 644, 767, 768, 1156
- `\protected` 141, 142, 360
- `\ProvidesClass` 7
- `\ProvidesFile` 7
- `\ProvidesPackage` 7
- `\quitvmode` 347
- `\read` 158, 636
- `\readline` 158, 636
- `\relax` 22, 140, 274, 329, 334, 345, 528, 528, 728, 730, 753, 784
- `\RequirePackage` 7, 274, 650
- `\reserveinserts` 274
- `\romannumeral` 36, 727
- `\scantokens` 74, 391, 655
- `\sfcode` 275
- `\shipout` 298
- `\show` 16, 58, 345
- `\showbox` 1060
- `\showthe` 345, 526, 681, 684, 687
- `\showtokens` 58, 417, 616
- `\sin` 208
- `\skip` 956, 957
- `\space` 587
- `\splitbotmark` 587
- `\splitfirstmark` 587
- `\SS` 1159
- `\strcmp` 271, 288
- `\string` 133, 951, 953, 954
- `\tenrm` 140
- `\tex_lowercase:D` 574
- `\tex_unexpanded:D` 357
- `\the` 91, 140, 174, 178, 181, 350, 359, 360, 360, 363
- `\toks` xxi, 80, 100, 220, 363, 364, 365, 494, 934, 935, 935, 935, 937, 937, 938, 939, 940, 941, 941, 942, 947, 951, 952, 954, 956, 957, 959, 964, 965, 965, 966, 966, 966, 967, 971, 1010, 1011, 1016, 1017, 1021, 1021, 1022, 1022, 1023, 1026, 1028, 1031, 1038, 1056
- `\toks@` 365
- `\toksdef` 947
- `\topmark` 141, 587
- `\tracingfonts` 298
- `\tracingnesting` 391, 655
- `\tracingonline` 1061
- `\typeout` 644
- `\uccode` 1114
- `\Ucharcat` 574
- `\unexpanded` 34, 52, 52, 52, 56, 56, 57, 77, 78, 82, 83, 121, 124, 125, 126, 126, 145, 265, 268, 359, 360, 360, 362, 387, 409, 410, 512
- `\unhbox` 242
- `\unhcopy` 239
- `\uniformdeviate` 215
- `\unless` 23
- `\unvbox` 242
- `\unvcopy` 241
- `\uppercase` 1038
- `\usepackage` 650
- `\valign` 541
- `\verso@orig@shipout` 1315
- `\vskip` 180
- `\vtop` 1079
- `\wd` 236, 769, 770
- `\write` 161, 637, 640
- tex commands:
 - `\tex_above:D` 287
 - `\tex_abovedisplayshortskip:D` .. 288
 - `\tex_abovedisplayshortskip:D` 289
 - `\tex_abovewithdelims:D` 290
 - `\tex_accent:D` 291
 - `\tex_adjdemerits:D` 292
 - `\tex_adjustspacing:D` 749, 1010
 - `\tex_advance:D` .. 293, 8844, 8846, 8848, 8850, 8856, 8858, 8860, 8862, 14622, 14625, 14631, 14634, 14965, 14967, 14971, 14973, 15061, 15063, 15067, 15069, 23129, 23136, 23139, 23541, 23543, 23576, 23578, 24781
 - `\tex_afterassignment:D`
 - 294, 11565, 23482, 23525
 - `\tex_aftergroup:D` 295, 2135

- `\tex_alignmark:D` 885, 1338
- `\tex_aligntab:D` 886, 1339
- `\tex_atop:D` 296
- `\tex_atopwithdelims:D` 297
- `\tex_attribute:D` 887, 1340
- `\tex_attributedef:D` 888, 1341
- `\tex_automaticdiscretionary:D` .. 890
- `\tex_automatichyphenmode:D` 891
- `\tex_automatichyphenpenalty:D` .. 893
- `\tex_autospacing:D` 1209
- `\tex_autoxspacing:D` 1210
- `\tex_badness:D` 298
- `\tex_baselineskip:D` 299
- `\tex_batchmode:D` 300, 12368
- `\tex_beginsname:D` 894
- `\tex_begingroup:D`
..... 301, 1300, 1403, 1465, 2130
- `\tex_beginL:D` 609
- `\tex_beginR:D` 610
- `\tex_belowdisplayshortskip:D` .. 302
- `\tex_belowdisplayskip:D` 303
- `\tex_binoppenalty:D` 304
- `\tex_bodydir:D` 895, 1377, 1455
- `\tex_bodydirection:D` 896
- `\tex_botmark:D` 305
- `\tex_botmarks:D` 611
- `\tex_box:D`
..... 306, 27066, 27068, 27108, 32503, 32506
- `\tex_boxdir:D` 897, 1378
- `\tex_boxdirection:D` 898
- `\tex_boxmaxdepth:D` 307
- `\tex_breakafterdirmode:D` 899
- `\tex_brokenpenalty:D` 308
- `\tex_catcode:D`
..... 309, 3246, 10806, 10808, 29230, 29237
- `\tex_catcodetable:D` 900, 1342
- `\tex_char:D` 310
- `\tex_chardef:D`
..... 311, 322, 2123, 2152, 2154, 2451,
..... 2452, 8819, 9576, 9598, 9603, 11486,
..... 13110, 13327, 29550, 29552, 29554
- `\tex_cleaders:D` 312
- `\tex_clearmarks:D` 901, 1343
- `\tex_closein:D` 313, 13121
- `\tex_closeout:D` 314, 13337
- `\tex_clubpenalties:D` 612
- `\tex_clubpenalty:D` 315
- `\tex_copy:D` 316, 27060,
..... 27062, 27083, 27092, 27101, 27109
- `\tex_copyfont:D` 750, 1011
- `\tex_count:D`
..... 317, 13050, 13052, 13283,
..... 13285, 22995, 23011, 23019, 23020
- `\tex_countdef:D` 318
- `\tex_cr:D` 319
- `\tex_crampeddisplaystyle:D` 902, 1344
- `\tex_crampedscriptscriptstyle:D` .
..... 904, 1345
- `\tex_crampedscriptstyle:D` . 905, 1347
- `\tex_crampedtextstyle:D` ... 906, 1348
- `\tex_crcr:D` 320
- `\tex_creationdate:D` 875
- `\tex_csname:D` 321, 2117
- `\tex_csstring:D` 907
- `\tex_currentcjktoken:D` ... 1211, 1268
- `\tex_currentgrouplevel:D` 613
- `\tex_currentgrouptype:D` 614
- `\tex_currentifbranch:D` 615
- `\tex_currentiflevel:D` 616
- `\tex_currentiftype:D` 617
- `\tex_currentspacingmode:D` 1212
- `\tex_currentxspacingmode:D` ... 1213
- `\tex_day:D` 322, 1410, 1414
- `\tex_deadcycles:D` 323
- `\tex_def:D` 324, 801, 802,
..... 803, 1466, 1467, 1468, 2136, 2138,
..... 2140, 2141, 2162, 2164, 2165, 2166,
..... 2168, 2169, 2170, 2172, 2173, 2174
- `\tex_defaultthyphenchar:D` 325
- `\tex_defaultskewchar:D` 326
- `\tex_delcode:D` 327
- `\tex_delimiter:D` 328
- `\tex_delimiterfactor:D` 329
- `\tex_delimitershortfall:D` 330
- `\tex_detokenize:D`
..... 618, 2126, 2128, 29218
- `\tex_dimen:D` 331, 6354, 6363, 6373,
..... 6374, 6375, 6396, 6408, 6409, 6410
- `\tex_dimendef:D` 332
- `\tex_dimexpr:D` 619, 14575, 27036
- `\tex_directlua:D`
..... 908, 1331, 1332, 5403,
..... 10120, 14551, 16937, 28999, 29225
- `\tex_disablecjktoken:D` 1269
- `\tex_discretionary:D` 333
- `\tex_disinhibitglue:D` 1214
- `\tex_displayindent:D` 334
- `\tex_displaylimits:D` 335
- `\tex_displaystyle:D` 336
- `\tex_displaywidowpenalties:D` .. 620
- `\tex_displaywidowpenalty:D` 337
- `\tex_displaywidth:D` 338
- `\tex_divide:D` 339, 22988, 24782
- `\tex_doublehyphendemerits:D` ... 340
- `\tex_dp:D` 341, 27076
- `\tex_draftmode:D` 751, 1012
- `\tex_dtou:D` 1215
- `\tex_dump:D` 342

- `\tex_dviextension:D` 909
- `\tex_dvifeedback:D` 910
- `\tex_dvivariable:D` 911
- `\tex_eachlinedepth:D` 752
- `\tex_eachlineheight:D` 753
- `\tex_edef:D` 343,
1301, 1302, 1318, 1404, 1405, 1410,
1411, 1416, 1417, 1422, 1423, 2163,
2167, 2171, 2175, 13549, 13607, 32304
- `\tex_efcode:D` 789
- `\tex_elapsedtime:D` 754, 876
- `\tex_else:D`
.... 344, 1304, 1330, 1407, 1413,
1419, 1425, 2103, 2155, 2158, 2200
- `\tex_emergencystretch:D` 345
- `\tex_enablecjktoken:D` ... 1270, 9889
- `\tex_end:D` 346, 1290, 1438, 2562
- `\tex_endcsname:D` 347, 2118
- `\tex_endgroup:D`
... 348, 1287, 1326, 1428, 2096, 2131
- `\tex_endinput:D` ... 349, 12377, 14339
- `\tex_endL:D` 621
- `\tex_endlinechar:D`
.. 251, 252, 266, 350, 4402, 4403,
4404, 4438, 6223, 13177, 13179, 13180
- `\tex_endR:D` 622
- `\tex_epTeXinputencoding:D` 1216
- `\tex_epTeXversion:D` 1217, 31948, 31971
- `\tex_eqno:D` 351
- `\tex_errhelp:D` 352, 12229, 32607
- `\tex_errmessage:D`
..... 353, 2554, 12249, 32638
- `\tex_errorcontextlines:D` 354, 5260,
12244, 12264, 12464, 27172, 32633
- `\tex_errorstopmode:D` 355
- `\tex_escapechar:D` 356, 2865, 6475,
6524, 6577, 13199, 13411, 13458,
13464, 23447, 23509, 23510, 23826
- `\tex_eTeXglueshrinkorder:D` 912
- `\tex_eTeXgluestretchorder:D` ... 913
- `\tex_eTeXrevision:D` 623
- `\tex_eTeXversion:D` 624
- `\tex_etoksapp:D` 914
- `\tex_etokspre:D` 915
- `\tex_euc:D` 1218
- `\tex_everycr:D` 357
- `\tex_everydisplay:D` 358, 1291
- `\tex_everyeof:D`
..... 625, 4411, 4463, 9998, 13889
- `\tex_everyhbox:D` 359
- `\tex_everyjob:D` 360, 1439, 13746, 13748
- `\tex_everymath:D` 361, 1292
- `\tex_everypar:D` 362
- `\tex_everyvbox:D` 363
- `\tex_exceptionpenalty:D` 916
- `\tex_exhyphenpenalty:D` 364
- `\tex_expandafter:D` 365, 806, 1305,
1319, 1321, 1322, 1471, 2119, 29218
- `\tex_expanded:D`
..... 372, 918, 1448, 2199, 2200,
2936, 2939, 3006, 3009, 3042, 3048,
3132, 3135, 3156, 3159, 3224, 3227,
3255, 3732, 3772, 3780, 10987, 12928
- `\tex_explicitdiscretionary:D` .. 919
- `\tex_explicithyphenpenalty:D` .. 917
- `\tex_fam:D` 366
- `\tex_fi:D` 367,
807, 1299, 1323, 1325, 1334, 1335,
1336, 1394, 1396, 1397, 1401, 1409,
1415, 1421, 1427, 1434, 1449, 1457,
1462, 1472, 2104, 2160, 2161, 2202
- `\tex_filedump:D` 755, 877, 14147, 14172
- `\tex_filemoddate:D`
..... 756, 878, 14310, 14311
- `\tex_filesize:D`
..... 658, 658, 757, 879, 13908,
13989, 14023, 14071, 14172, 14207
- `\tex_finalhyphenemerits:D` 368
- `\tex_firstlineheight:D` 758
- `\tex_firstmark:D` 369
- `\tex_firstmarks:D` 626
- `\tex_firstvalidlanguage:D` 920
- `\tex_floatingpenalty:D` 370
- `\tex_font:D` 371, 16330
- `\tex_fontchardp:D` 627
- `\tex_fontcharht:D` 628
- `\tex_fontcharic:D` 629
- `\tex_fontcharwd:D` 630
- `\tex_fontdimen:D` 372, 16319
- `\tex_fontexpand:D` 759, 1013
- `\tex_fontid:D` 921, 1349
- `\tex_fontname:D` 373
- `\tex_fontsize:D` 760
- `\tex_forcecjktoken:D` 1271
- `\tex_formatname:D` 922, 1350
- `\tex_futurelet:D`
.... 374, 11560, 11562, 23455, 23513
- `\tex_gdef:D` 375, 2176, 2179, 2183, 2187
- `\tex_gleaders:D` 928, 1351
- `\tex_global:D` 272,
277, 279, 376, 673, 808, 810, 1321,
1408, 1414, 1420, 1426, 1473, 2631,
2638, 8797, 8803, 8807, 8826, 8837,
8848, 8850, 8860, 8862, 8870, 9576,
9603, 11292, 11294, 11304, 11562,
13110, 13327, 14591, 14596, 14612,
14619, 14625, 14634, 14937, 14941,
14957, 14962, 14967, 14973, 15031,

- 15037, 15053, 15058, 15063, 15069,
 16330, 27062, 27068, 27138, 27191,
 27203, 27216, 27236, 27281, 27293,
 27305, 27318, 27339, 27354, 32506
 \tex_globaldefs:D 377
 \tex_glueexpr:D 631, 14955,
 14957, 14965, 14967, 14971, 14973,
 14987, 14994, 15000, 15003, 22420
 \tex_glueshrink:D 632
 \tex_glueshrinkorder:D 633
 \tex_gluestretch:D . 634, 23667, 23673
 \tex_gluestretchorder:D 635
 \tex_gluetomu:D 636
 \tex_halign:D 378
 \tex_hangafter:D 379
 \tex_hangindent:D 380
 \tex_hbadness:D 381
 \tex_hbox:D 382, 27183, 27186,
 27191, 27198, 27203, 27210, 27216,
 27230, 27236, 27244, 27249, 28692
 \tex_hfi:D 1219
 \tex_hfil:D 383
 \tex_hfill:D 384
 \tex_hfilneg:D 385
 \tex_hfuzz:D 386
 \tex_hjcode:D 923
 \tex_hoffset:D 387, 1451
 \tex_holdinginserts:D 388
 \tex_hpack:D 924
 \tex_hruler:D 389
 \tex_hsize:D 390, 27844,
 27846, 27847, 27913, 27915, 27916
 \tex_hskip:D 391, 14998
 \tex_hss:D
 392, 27253, 27255, 27698, 27707
 \tex_ht:D 393, 27075
 \tex_hyphen:D 286, 1293
 \tex_hyphenation:D 394
 \tex_hyphenationbounds:D 925
 \tex_hyphenationmin:D 926
 \tex_hyphenchar:D 395, 16320
 \tex_hyphenpenalty:D 396
 \tex_hyphenpenaltymode:D 927
 \tex_if:D 128, 397, 2106, 2107
 \tex_ifabsdim:D 746, 1014
 \tex_ifabsnum:D 747, 1015, 16390, 16394
 \tex_ifcase:D 398, 8688
 \tex_ifcat:D 399, 2108
 \tex_ifcondition:D 929
 \tex_ifcscname:D 637, 2116
 \tex_ifdbbox:D 1220
 \tex_ifddir:D 1221
 \tex_ifdefined:D
 . 638, 805, 1289, 1297, 1328, 1331,
 1337, 1396, 1397, 1430, 1437, 1450,
 1458, 1470, 2115, 2153, 2156, 2200
 \tex_ifdim:D 400, 14574
 \tex_ifeof:D 401, 13141
 \tex_iffalse:D 402, 2101
 \tex_iffontchar:D 639
 \tex_ifhbox:D 403, 27120
 \tex_ifhmode:D 404, 2112
 \tex_ifincname:D 790
 \tex_ifinner:D 405, 2114
 \tex_ifjfont:D 1222
 \tex_ifmbox:D 1223
 \tex_ifmdir:D 1224
 \tex_ifmmode:D 406, 2111
 \tex_ifnum:D 407, 1395, 2133
 \tex_ifodd:D ... 408, 2110, 8687, 9569
 \tex_ifprimitive:D 748, 881
 \tex_iftbody:D 1225
 \tex_iftdir:D 1227
 \tex_iftfont:D 1226
 \tex_iftrue:D 409, 2100
 \tex_ifvbox:D 410, 27121
 \tex_ifvmode:D 411, 2113
 \tex_ifvoid:D 412, 27122
 \tex_ifx:D 413, 1303,
 1320, 1406, 1412, 1418, 1424, 2109
 \tex_ifybox:D 1228
 \tex_ifydir:D 1229
 \tex_ignoreddimen:D 761
 \tex_ignoreligaturesinfont:D . 1016
 \tex_ignorespaces:D 414
 \tex_immediate:D
 . 415, 2571, 2573, 13329, 13337, 13378
 \tex_immediateassigned:D 930
 \tex_immediateassignment:D 931
 \tex_indent:D 416, 2920
 \tex_inhibitglue:D 1230
 \tex_inhibitxspcode:D 1231
 \tex_initcatcodetable:D ... 932, 1352
 \tex_input:D
 . 417, 1294, 1440, 10003, 13895, 14362
 \tex_inputlineno:D .. 418, 2569, 12167
 \tex_insert:D 419
 \tex_inserttht:D 762, 1017
 \tex_insertpenalties:D 420
 \tex_interactionmode:D
 640, 27156, 27159, 27161
 \tex_interlinepenalties:D 641
 \tex_interlinepenalty:D 421
 \tex_italiccorrection:D
 285, 1295, 1452
 \tex_jcharwidowpenalty:D 1232
 \tex_jfam:D 1233
 \tex_jfont:D 1234

- `\tex_jis:D` 1235
- `\tex_jobname:D`
 - 422, 10052, 10136, 13728, 13729
- `\tex_kanjiskip:D` 1236, 9887
- `\tex_kansuji:D` 1237
- `\tex_kansujichar:D` 1238
- `\tex_kcatcode:D` 1239
- `\tex_kchar:D` 1272
- `\tex_kchardef:D` 1273
- `\tex_kern:D`
 - . 423, 27406, 27696, 27705, 28266,
 - 28526, 28531, 28613, 28614, 28908,
 - 28909, 31618, 31620, 31669, 31671
- `\tex_kuten:D` 1240, 1274
- `\tex_language:D` 424, 1441
- `\tex_lastbox:D` 425, 27136, 27138
- `\tex_lastkern:D` 426
- `\tex_lastlinedepth:D` 763
- `\tex_lastlinefit:D` 642
- `\tex_lastnamedcs:D` 933
- `\tex_lastnodechar:D` 1241
- `\tex_lastnodesubtype:D` 1242
- `\tex_lastnodetype:D` 643
- `\tex_lastpenalty:D` 427
- `\tex_lastskip:D` 428
- `\tex_lastxpos:D` 764, 1024
- `\tex_lastypos:D` 765, 1025
- `\tex_latelua:D` 934, 1353, 29000
- `\tex_lateluafunction:D` 935
- `\tex_lccode:D` 429, 4304,
 - 4305, 4306, 5592, 5593, 5615, 5616,
 - 10882, 10884, 23428, 23438, 23507,
 - 23509, 23512, 23542, 26332, 26384
- `\tex_leaders:D` 430
- `\tex_left:D` 431, 1459
- `\tex_leftghost:D` 936, 1379
- `\tex_lefthyphenmin:D` 432
- `\tex_leftmarginkern:D` 791
- `\tex_leftskip:D` 433
- `\tex_leqno:D` 434
- `\tex_let:D` 273,
 - 277, 279, 435, 808, 810, 1184, 1188,
 - 1290, 1291, 1292, 1293, 1294, 1295,
 - 1296, 1298, 1321, 1327, 1329, 1333,
 - 1338, 1339, 1340, 1341, 1342, 1343,
 - 1344, 1345, 1347, 1348, 1349, 1350,
 - 1351, 1352, 1353, 1354, 1355, 1356,
 - 1357, 1358, 1359, 1360, 1361, 1362,
 - 1363, 1364, 1365, 1366, 1367, 1368,
 - 1370, 1371, 1373, 1374, 1375, 1377,
 - 1378, 1379, 1380, 1381, 1383, 1384,
 - 1385, 1386, 1387, 1388, 1389, 1390,
 - 1391, 1392, 1393, 1399, 1400, 1408,
 - 1414, 1420, 1426, 1431, 1432, 1433,
 - 1438, 1439, 1440, 1441, 1442, 1443,
 - 1444, 1445, 1446, 1447, 1448, 1451,
 - 1452, 1453, 1454, 1455, 1456, 1459,
 - 1460, 1461, 1473, 2100, 2101, 2102,
 - 2103, 2104, 2105, 2106, 2107, 2108,
 - 2109, 2110, 2111, 2112, 2113, 2114,
 - 2115, 2116, 2117, 2118, 2119, 2120,
 - 2121, 2122, 2124, 2125, 2126, 2127,
 - 2128, 2129, 2130, 2131, 2133, 2134,
 - 2135, 2151, 2162, 2163, 2176, 2177,
 - 2627, 11292, 11294, 11304, 23429,
 - 23439, 32242, 32245, 32451, 32476
- `\tex_letcharcode:D` 937
- `\tex_letterspacefont:D` 792
- `\tex_limits:D` 436
- `\tex_linedir:D` 938
- `\tex_linedirection:D` 939
- `\tex_linepenalty:D` 437
- `\tex_lineskip:D` 438
- `\tex_lineskiplimit:D` 439
- `\tex_localbrokenpenalty:D` . 940, 1380
- `\tex_localinterlinepenalty:D` ...
 - 941, 1381
- `\tex_localleftbox:D` 946, 1383
- `\tex_localrightbox:D` 947, 1384
- `\tex_long:D`
 - .. 440, 801, 802, 803, 1466, 1467,
 - 1468, 2136, 2138, 2141, 2164, 2165,
 - 2166, 2167, 2168, 2170, 2172, 2173,
 - 2174, 2175, 2179, 2181, 2187, 2189
- `\tex_looseness:D` 441
- `\tex_lower:D` 442, 27119
- `\tex_lowercase:D`
 - 443, 1180, 4307, 5594, 5617, 10913,
 - 11033, 12236, 23429, 23439, 23508,
 - 26333, 26385, 32141, 32425, 32619
- `\tex_lpcode:D` 793
- `\tex_luabytecode:D` 942
- `\tex_luabytecodecall:D` 943
- `\tex_luacopyinputnodes:D` 944
- `\tex_luadef:D` 945
- `\tex_luaescapestring:D` 422,
 - 948, 1354, 5402, 16941, 16942, 28998
- `\tex_luafunction:D` 949, 1355
- `\tex_luafunctioncall:D` 950
- `\tex luatexbanner:D` 951
- `\tex luatexrevision:D` ... 952, 31955
- `\tex luatexversion:D`
 - 953, 1397, 1430, 2153, 5400,
 - 8814, 9493, 9885, 11281, 13261, 31953
- `\tex_mag:D` 444
- `\tex_mapfile:D` 766, 1399
- `\tex_mapline:D` 767, 1400
- `\tex_mark:D` 445

<code>\tex_marks:D</code>	644	<code>\tex_noautospaceing:D</code>	1243
<code>\tex_mathaccent:D</code>	446	<code>\tex_noautoxspacing:D</code>	1244
<code>\tex_mathbin:D</code>	447	<code>\tex_noboundary:D</code>	475
<code>\tex_mathchar:D</code>	448	<code>\tex_noexpand:D</code>	476, 2120
<code>\tex_mathchardef:D</code>	322, 449, 2159, 8822, 8823, 29551, 29553, 29555	<code>\tex_nohrule:D</code>	969
<code>\tex_mathchoice:D</code>	450	<code>\tex_noindent:D</code>	477
<code>\tex_mathclose:D</code>	451	<code>\tex_nokerns:D</code>	970, 1357
<code>\tex_mathcode:D</code> ...	452, 10876, 10878	<code>\tex_noligatures:D</code>	769
<code>\tex_mathdelimitersmode:D</code>	954	<code>\tex_noligs:D</code>	971, 1358
<code>\tex_mathdir:D</code>	955, 1385	<code>\tex_nolimits:D</code>	478
<code>\tex_mathdirection:D</code>	956	<code>\tex_nonscript:D</code>	479
<code>\tex_mathdisplayskipmode:D</code>	957	<code>\tex_nonstopmode:D</code>	480
<code>\tex_matheqnogapstep:D</code>	958	<code>\tex_normaldeviate:D</code>	770, 1026
<code>\tex_mathinner:D</code>	453	<code>\tex_nospaces:D</code>	972
<code>\tex_mathnolimitsmode:D</code>	959	<code>\tex_novrule:D</code>	973
<code>\tex_mathop:D</code>	454, 1442	<code>\tex_nulldelimiterspace:D</code>	481
<code>\tex_mathopen:D</code>	455	<code>\tex_nullfont:D</code>	482, 11515
<code>\tex_mathoption:D</code>	960	<code>\tex_number:D</code> .	483, 8684, 27747, 29229
<code>\tex_mathord:D</code>	456	<code>\tex_numexpr:D</code>	648, 8685, 16560, 23818
<code>\tex_mathpenaltiesmode:D</code>	961	<code>\tex_odelcode:D</code>	1278
<code>\tex_mathpunct:D</code>	457	<code>\tex_odelimiter:D</code>	1279
<code>\tex_mathrel:D</code>	458	<code>\tex_omathaccent:D</code>	1280
<code>\tex_mathrulesfam:D</code>	962	<code>\tex_omathchar:D</code>	1281
<code>\tex_mathscriptboxmode:D</code>	964	<code>\tex_omathchardef:D</code> 1282, 2156, 2157, 8815, 8817, 8818
<code>\tex_mathscriptcharmode:D</code>	965	<code>\tex_omathcode:D</code>	1283
<code>\tex_mathscriptsmode:D</code>	963	<code>\tex_omit:D</code>	484
<code>\tex_mathstyle:D</code>	966, 1356	<code>\tex_openin:D</code>	485, 13112
<code>\tex_mathsurround:D</code>	459	<code>\tex_openout:D</code>	486, 13329
<code>\tex_mathsurroundmode:D</code>	967	<code>\tex_or:D</code>	487, 2102
<code>\tex_mathsurroundskip:D</code>	968	<code>\tex_oradical:D</code>	1284
<code>\tex_maxdeadcycles:D</code>	460	<code>\tex_outer:D</code>	488, 1444, 32304
<code>\tex_maxdepth:D</code>	461	<code>\tex_output:D</code>	489
<code>\tex_mdffivesum:D</code>	768, 880, 14102	<code>\tex_outputbox:D</code>	974, 1359
<code>\tex_meaning:D</code> ..	462, 1302, 1319, 1404, 1410, 1416, 1422, 2124, 2125	<code>\tex_outputpenalty:D</code>	490
<code>\tex_medmuskip:D</code>	463	<code>\tex_over:D</code>	491, 1445
<code>\tex_message:D</code>	464	<code>\tex_overfullrule:D</code>	492
<code>\tex_middle:D</code>	645, 1460	<code>\tex_overline:D</code>	493
<code>\tex_mkern:D</code>	465	<code>\tex_overwithdelims:D</code>	494
<code>\tex_month:D</code> ...	466, 1416, 1420, 1443	<code>\tex_pagebottomoffset:D</code> ...	975, 1386
<code>\tex_moveleft:D</code>	467, 27113	<code>\tex_pagedepth:D</code>	495
<code>\tex_moveright:D</code>	468, 27115	<code>\tex_pagedir:D</code>	976, 1387, 1456
<code>\tex_mskip:D</code>	469	<code>\tex_pagedirection:D</code>	977
<code>\tex_muexpr:D</code> ..	646, 15051, 15053, 15061, 15063, 15067, 15069, 15073	<code>\tex_pagediscards:D</code>	649
<code>\tex_multiply:D</code>	470	<code>\tex_pagefilllstretch:D</code>	496
<code>\tex_muskip:D</code>	471	<code>\tex_pagefillstretch:D</code>	497
<code>\tex_muskipdef:D</code>	472	<code>\tex_pagefilstretch:D</code>	498
<code>\tex_mutoglue:D</code>	314, 647	<code>\tex_pagefistretch:D</code>	1245
<code>\tex_newlinechar:D</code> 473, 2553, 4404, 4430, 4434, 5258, 12242, 12462, 13377, 32631	<code>\tex_pagegoal:D</code>	499
<code>\tex_noalign:D</code>	474	<code>\tex_pageheight:D</code>	771, 1028, 1388
		<code>\tex_pageleftoffset:D</code>	978, 1360
		<code>\tex_pagerightoffset:D</code>	979, 1389
		<code>\tex_pageshrink:D</code>	500
		<code>\tex_pagestretch:D</code>	501

<code>\tex_pagetopoffset:D</code>	980, 1361	<code>\tex_pdfminorversion:D</code>	713
<code>\tex_pagetotal:D</code>	502	<code>\tex_pdfnames:D</code>	714
<code>\tex_pagewidth:D</code>	772, 1390	<code>\tex_pdfobj:D</code>	715
<code>\tex_pagewith:D</code>	1029	<code>\tex_pdfobjcompresslevel:D</code>	716
<code>\tex_par:D</code>	503	<code>\tex_pdfoutline:D</code>	717
<code>\tex_pardir:D</code>	981, 1391	<code>\tex_pdfoutput:D</code>	718, 1027, 10151
<code>\tex_pardirection:D</code>	982	<code>\tex_pdfpageattr:D</code>	719
<code>\tex_parfillskip:D</code>	504	<code>\tex_pdfpagebox:D</code>	721
<code>\tex_parindent:D</code>	505	<code>\tex_pdfpageref:D</code>	722
<code>\tex_parshape:D</code>	506	<code>\tex_pdfpageresources:D</code>	723
<code>\tex_parshapedimen:D</code>	650	<code>\tex_pdfpagesattr:D</code>	720, 724
<code>\tex_parshapeindent:D</code>	651	<code>\tex_pdfrefobj:D</code>	725
<code>\tex_parshapelength:D</code>	652	<code>\tex_pdfrefxform:D</code>	726, 1033
<code>\tex_parskip:D</code>	507	<code>\tex_pdfrefximage:D</code>	727, 1034
<code>\tex_patterns:D</code>	508	<code>\tex_pdfrestore:D</code>	728
<code>\tex_pausing:D</code>	509	<code>\tex_pdfretval:D</code>	729
<code>\tex_pdfannot:D</code>	675	<code>\tex_pdfsave:D</code>	730
<code>\tex_pdfcatalog:D</code>	676	<code>\tex_pdfsetmatrix:D</code>	731
<code>\tex_pdfcolorstack:D</code>	678	<code>\tex_pdfstartlink:D</code>	732
<code>\tex_pdfcolorstackinit:D</code>	679	<code>\tex_pdfstartthread:D</code>	733
<code>\tex_pdfcompresslevel:D</code>	677	<code>\tex_pdfsuppressptexinfo:D</code>	734
<code>\tex_pdfcreationdate:D</code>	680	<code>\tex_pdftexbanner:D</code>	786, 1431
<code>\tex_pdfdecimaldigits:D</code>	681	<code>\tex_pdftexrevision:D</code>	787, 1432, 31936
<code>\tex_pdfdest:D</code>	682	<code>\tex_pdftexversion:D</code>
<code>\tex_pdfdestmargin:D</code>	683		301, 788, 1396, 1433, 9886, 31934
<code>\tex_pdfendlink:D</code>	684	<code>\tex_pdfthread:D</code>	735
<code>\tex_pdfendthread:D</code>	685	<code>\tex_pdfthreadmargin:D</code>	736
<code>\tex_pdfextension:D</code>	983	<code>\tex_pdftrailer:D</code>	737
<code>\tex_pdffeedback:D</code>	984	<code>\tex_pdfuniquefilename:D</code>	738
<code>\tex_pdffontattr:D</code>	686	<code>\tex_pdfvariable:D</code>	985
<code>\tex_pdffontname:D</code>	687	<code>\tex_pdfvorigin:D</code>	739
<code>\tex_pdffontobjnum:D</code>	688	<code>\tex_pdfxform:D</code>	740, 1036
<code>\tex_pdfgamma:D</code>	689	<code>\tex_pdfxformattr:D</code>	741
<code>\tex_pdfgentounicode:D</code>	692	<code>\tex_pdfxformname:D</code>	742
<code>\tex_pdfglyptounicode:D</code>	693	<code>\tex_pdfxformresources:D</code>	743
<code>\tex_pdfhorigin:D</code>	694	<code>\tex_pdfximage:D</code>	744, 1037
<code>\tex_pdfimageapplygamma:D</code>	690	<code>\tex_pdfximagebbox:D</code>	745
<code>\tex_pdfimagegamma:D</code>	691	<code>\tex_penalty:D</code>	510
<code>\tex_pdfimagehicolor:D</code>	695	<code>\tex_pkmode:D</code>	773
<code>\tex_pdfimageresolution:D</code>	696	<code>\tex_pkresolution:D</code>	774
<code>\tex_pdfincludechars:D</code>	697	<code>\tex_postbreakpenalty:D</code>	1246
<code>\tex_pdfinclusioncopyfonts:D</code>	698	<code>\tex_postdisplaypenalty:D</code>	511
<code>\tex_pdfinclusionerrorlevel:D</code>	700	<code>\tex_posttexhyphenchar:D</code>	986, 1362
<code>\tex_pdfinfo:D</code>	701	<code>\tex_postthyphenchar:D</code>	987, 1363
<code>\tex_pdflastannot:D</code>	702	<code>\tex_prebinoppenalty:D</code>	988
<code>\tex_pdflastlink:D</code>	703	<code>\tex_prebreakpenalty:D</code>	1247
<code>\tex_pdflastobj:D</code>	704	<code>\tex_predisplaydirection:D</code>	653
<code>\tex_pdflastxform:D</code>	705, 1019	<code>\tex_predisplaygapfactor:D</code>	989
<code>\tex_pdflastximage:D</code>	706, 1021	<code>\tex_predisplaypenalty:D</code>	512
<code>\tex_pdflastximagecolordepth:D</code>	708	<code>\tex_predisplaysize:D</code>	513
<code>\tex_pdflastximagepages:D</code>	709, 1023	<code>\tex_preexhyphenchar:D</code>	990, 1364
<code>\tex_pdflinkmargin:D</code>	710	<code>\tex_prehyphenchar:D</code>	991, 1365
<code>\tex_pdfliteral:D</code>	711	<code>\tex_prerelpenalty:D</code>	992
<code>\tex_pdfmajorversion:D</code>	712	<code>\tex_pretolerance:D</code>	514

- `\tex_prevdepth:D` 515
- `\tex_prevgraf:D` 516
- `\tex_primitive:D`
 - ... 360, 775, 882, 3306, 10061, 10071
- `\tex_protected:D`
 - ... 654, 2164, 2166, 2168,
 - 2169, 2170, 2171, 2172, 2173, 2174,
 - 2175, 2183, 2185, 2187, 2189, 32304
- `\tex_protrudechars:D` 776, 1030
- `\tex_ptexminorversion:D`
 - ... 1248, 31945, 31964
- `\tex_ptexrevision:D` 1249, 31946, 31965
- `\tex_ptexversion:D`
 - ... 1250, 31940, 31943, 31959, 31962
- `\tex_pxdimen:D` 777, 1031
- `\tex_quitvmode:D` 794
- `\tex_radical:D` 517
- `\tex_raise:D` 518, 27117
- `\tex_randomseed:D` ... 778, 1032, 10088
- `\tex_read:D` 519, 12369, 13161
- `\tex_readline:D` 655, 13178
- `\tex_readpapersizespecial:D` .. 1251
- `\tex_relax:D`
 - ... 314, 520, 730, 2129, 8686, 14576
- `\tex_relpentalty:D` 521
- `\tex_resettimer:D` 779, 883
- `\tex_right:D` 522, 1461
- `\tex_rightghost:D` 993, 1392
- `\tex_rightthyphenmin:D` 523
- `\tex_rightmarginkern:D` 795
- `\tex_rightskip:D` 524
- `\tex_romannumeral:D` 333, 333, 358,
 - 525, 2122, 2134, 2456, 10925, 16562
- `\tex_rrcode:D` 796
- `\tex_savecatcodetable:D` ... 994, 1366
- `\tex_savepos:D` 780, 1035
- `\tex_savinghyphcodes:D` 656
- `\tex_savingvdiscards:D` 657
- `\tex_scantextokens:D` 995, 1367
- `\tex_scantokens:D` ... 658, 4416, 4477
- `\tex_scriptbaselineshiftfactor:D`
 - ... 1253
- `\tex_scriptfont:D` 526
- `\tex_scriptscriptbaselineshiftfactor:D`
 - ... 1255
- `\tex_scriptscriptfont:D` 527
- `\tex_scriptscriptstyle:D` 528
- `\tex_scriptspace:D` 529
- `\tex_scriptstyle:D` 530
- `\tex_scrollmode:D` 531
- `\tex_setbox:D` .. 532, 27060, 27062,
 - 27066, 27068, 27083, 27092, 27101,
 - 27136, 27138, 27186, 27191, 27198,
 - 27203, 27210, 27216, 27230, 27236,
 - 27276, 27281, 27288, 27293, 27300,
 - 27305, 27312, 27318, 27333, 27339,
 - 27350, 27354, 28692, 32503, 32506
- `\tex_setfontid:D` 996
- `\tex_setlanguage:D` 533
- `\tex_setrandomseed:D` 782, 1038, 10104
- `\tex_sfcode:D` 534, 10894, 10896
- `\tex_shapemode:D` 997
- `\tex_shellescape:D` ... 783, 884, 10123
- `\tex_shipout:D` 535, 1298, 1322
- `\tex_show:D` 536
- `\tex_showbox:D` 537, 27173
- `\tex_showboxbreadth:D` ... 538, 27169
- `\tex_showboxdepth:D` 539, 27170
- `\tex_showgroups:D` 659
- `\tex_showifs:D` 660
- `\tex_showlists:D` 540
- `\tex_showmode:D` 1256
- `\tex_showthe:D` 541
- `\tex_showtokens:D`
 - ... 417, 661, 1454, 5262, 12466
- `\tex_sjis:D` 1257
- `\tex_skewchar:D` 542
- `\tex_skip:D` 543,
 - 6355, 6364, 6374, 6397, 6409, 23545,
 - 23574, 23593, 23651, 23667, 23673
- `\tex_skipdef:D` 544
- `\tex_space:D` 284
- `\tex_spacefactor:D` 545
- `\tex_spaceskip:D` 546
- `\tex_span:D` 547
- `\tex_special:D` 548
- `\tex_splitbotmark:D` 549
- `\tex_splitbotmarks:D` 662
- `\tex_splitdiscards:D` 663
- `\tex_splitfirstmark:D` 550
- `\tex_splitfirstmarks:D` 664
- `\tex_splitmaxdepth:D` 551
- `\tex_splittopskip:D` 552
- `\tex_strcmp:D` . 781, 5399, 14242, 16947
- `\tex_string:D` 553, 1301,
 - 1305, 1405, 1411, 1417, 1423, 2127
- `\tex_suppressfontnotfounderror:D`
 - ... 816, 1375
- `\tex_suppressifcsnameerror:D` ...
 - ... 998, 1368
- `\tex_suppresslongerror:D` .. 999, 1370
- `\tex_suppressmathparerror:D`
 - ... 1000, 1371
- `\tex_suppressoutererror:D` 1001, 1373
- `\tex_suppressprimitiveerror:D` . 1003
- `\tex_synctex:D` 797
- `\tex_tabskip:D` 554
- `\tex_tagcode:D` 798

<code>\tex_tate:D</code>	1258	<code>\tex_tracingscantokens:D</code>	671
<code>\tex_tbaselineshift:D</code>	1259	<code>\tex_tracingstats:D</code>	574
<code>\tex_textbaselineshiftfactor:D</code>	1261	<code>\tex_uccode:D</code>	575, 10888, 10890
<code>\tex_textdir:D</code>	1004, 1393	<code>\tex_Uchar:D</code>	1041, 1374, 29218
<code>\tex_textdirection:D</code>	1005	<code>\tex_Ucharcat:D</code> ..	1042, 10985, 29235
<code>\tex_textfont:D</code>	555	<code>\tex_uchyph:D</code>	576
<code>\tex_textstyle:D</code>	556	<code>\tex_ucs:D</code>	1275
<code>\tex_TeXtstate:D</code>	665	<code>\tex_Udelcode:D</code>	1043
<code>\tex_tfont:D</code>	1262	<code>\tex_Udelcodenum:D</code>	1044
<code>\tex_the:D</code>	252, 314, 351, 557, 764, 769, 770, 2569, 2851, 2979, 2983, 3305, 3347, 3438, 3457, 3472, 3477, 6375, 6410, 8302, 8873, 8875, 10088, 10808, 10878, 10884, 10890, 10896, 13748, 14808, 14809, 14810, 14880, 14882, 14995, 14997, 15074, 17567, 18057, 23086, 23118, 23166, 23167, 23198, 23199, 23205, 23206, 23666, 23776, 23827, 23846, 23852, 23855, 23859, 27156, 29230	<code>\tex_Udelimiter:D</code>	1045
<code>\tex_thickmuskip:D</code>	558	<code>\tex_Udelimiterover:D</code>	1046
<code>\tex_thinmuskip:D</code>	559	<code>\tex_Udelimiterunder:D</code>	1047
<code>\tex_time:D</code>	560, 1404, 1408	<code>\tex_Uhextensible:D</code>	1048
<code>\tex_toks:D</code>	561, 3448, 3477, 6356, 6365, 6375, 6398, 6410, 8302, 8313, 8314, 8315, 23059, 23086, 23118, 23155, 23166, 23167, 23198, 23199, 23205, 23206, 23210, 23220, 23230, 23490, 23508, 23666, 23827, 23830, 23837, 23845, 23846, 23851, 23852, 23855, 23859	<code>\tex_Umathaccent:D</code>	1049
<code>\tex_toksapp:D</code>	1006	<code>\tex_Umathaxis:D</code>	1050
<code>\tex_toksdef:D</code>	562, 23338	<code>\tex_Umathbinbinspacing:D</code>	1051
<code>\tex_tokspre:D</code>	1007	<code>\tex_Umathbinclonespacing:D</code> ..	1052
<code>\tex_tolerance:D</code>	563	<code>\tex_Umathbininnerspacing:D</code> ..	1053
<code>\tex_topmark:D</code>	564	<code>\tex_Umathbinopenspacing:D</code>	1054
<code>\tex_topmarks:D</code>	666	<code>\tex_Umathbinopspacing:D</code>	1055
<code>\tex_topskip:D</code>	565	<code>\tex_Umathbinordspacing:D</code>	1056
<code>\tex_tpack:D</code>	1008	<code>\tex_Umathbinpunctspacing:D</code> ..	1057
<code>\tex_tracingassigns:D</code>	667	<code>\tex_Umathbinrelspacing:D</code>	1058
<code>\tex_tracingcommands:D</code>	566	<code>\tex_Umathchar:D</code>	1059
<code>\tex_tracingfonts:D</code>	784, 1039, 1327, 1329, 1333	<code>\tex_Umathcharclass:D</code>	1060
<code>\tex_tracinggroups:D</code>	668	<code>\tex_Umathchardef:D</code>	1061
<code>\tex_tracingifs:D</code>	669	<code>\tex_Umathcharfam:D</code>	1062
<code>\tex_tracinglostchars:D</code>	567	<code>\tex_Umathcharnum:D</code>	1063
<code>\tex_tracingmacros:D</code>	568	<code>\tex_Umathcharnumdef:D</code>	1064
<code>\tex_tracingnesting:D</code>	670, 4401, 9997, 13888	<code>\tex_Umathcharslot:D</code>	1065
<code>\tex_tracingonline:D</code>	569, 27171	<code>\tex_Umathclosebinspacing:D</code> ..	1066
<code>\tex_tracingoutput:D</code>	570	<code>\tex_Umathcloseclonespacing:D</code> ..	1068
<code>\tex_tracingpages:D</code>	571	<code>\tex_Umathcloseinnerspacing:D</code> ..	1070
<code>\tex_tracingparagraphs:D</code>	572	<code>\tex_Umathcloseopenspacing:D</code> ..	1071
<code>\tex_tracingrestores:D</code>	573	<code>\tex_Umathcloseopspacing:D</code>	1072
		<code>\tex_Umathcloseordspacing:D</code> ..	1073
		<code>\tex_Umathclosepunctspacing:D</code> ..	1075
		<code>\tex_Umathcloserelspacing:D</code> ..	1076
		<code>\tex_Umathcode:D</code>	1077
		<code>\tex_Umathcodenum:D</code>	1078
		<code>\tex_Umathconnectoroverlapmin:D</code>	1080
		<code>\tex_Umathfractiondelsize:D</code> ..	1081
		<code>\tex_Umathfractiondenomdown:D</code> ..	1083
		<code>\tex_Umathfractiondenomvgap:D</code> ..	1085
		<code>\tex_Umathfractionnumup:D</code>	1086
		<code>\tex_Umathfractionnumvgap:D</code> ..	1087
		<code>\tex_Umathfractionrule:D</code>	1088
		<code>\tex_Umathinnerbinspacing:D</code> ..	1089
		<code>\tex_Umathinnerclonespacing:D</code> ..	1091
		<code>\tex_Umathinnerinnerspacing:D</code> ..	1093
		<code>\tex_Umathinneropenspacing:D</code> ..	1094
		<code>\tex_Umathinneropspacing:D</code>	1095
		<code>\tex_Umathinnerordspacing:D</code> ..	1096
		<code>\tex_Umathinnerpunctspacing:D</code> ..	1098

<code>\tex_Umathinnerrelspacing:D</code> ..	1099	<code>\tex_Umathrelbinspacing:D</code>	1161
<code>\tex_Umathlimitabovebgap:D</code> ...	1100	<code>\tex_Umathrelclosespacing:D</code> ..	1162
<code>\tex_Umathlimitabovekern:D</code> ...	1101	<code>\tex_Umathrelinnerspacing:D</code> ..	1163
<code>\tex_Umathlimitabovevgap:D</code> ...	1102	<code>\tex_Umathrelopenspacing:D</code> ...	1164
<code>\tex_Umathlimitbelowbgap:D</code> ...	1103	<code>\tex_Umathrelopenspacing:D</code>	1165
<code>\tex_Umathlimitbelowkern:D</code> ...	1104	<code>\tex_Umathrelordspacing:D</code>	1166
<code>\tex_Umathlimitbelowvgap:D</code> ...	1105	<code>\tex_Umathrelpunctspacing:D</code> ..	1167
<code>\tex_Umathnolimitsubfactor:D</code> .	1106	<code>\tex_Umathrelrelspacing:D</code>	1168
<code>\tex_Umathnolimitsupfactor:D</code> .	1107	<code>\tex_Umathskewedfractionhgap:D</code>	1170
<code>\tex_Umathopbinspacing:D</code>	1108	<code>\tex_Umathskewedfractionvgap:D</code>	1172
<code>\tex_Umathopclosespacing:D</code> ...	1109	<code>\tex_Umathspaceafterscript:D</code> .	1173
<code>\tex_Umathopenbinspacing:D</code> ...	1110	<code>\tex_Umathstackdenomdown:D</code> ...	1174
<code>\tex_Umathopenclosespacing:D</code> .	1111	<code>\tex_Umathstacknumup:D</code>	1175
<code>\tex_Umathopeninnerspacing:D</code> .	1112	<code>\tex_Umathstackvgap:D</code>	1176
<code>\tex_Umathopenopenspacing:D</code> ..	1113	<code>\tex_Umathsubshiftdown:D</code>	1177
<code>\tex_Umathopenopspacing:D</code>	1114	<code>\tex_Umathsubshiftdrop:D</code>	1178
<code>\tex_Umathopenordspacing:D</code> ...	1115	<code>\tex_Umathsubsupshiftdown:D</code> ..	1179
<code>\tex_Umathopenpunctspacing:D</code> .	1116	<code>\tex_Umathsubsupvgap:D</code>	1180
<code>\tex_Umathopenrelspacing:D</code> ...	1117	<code>\tex_Umathsubtopmax:D</code>	1181
<code>\tex_Umathoperatorsize:D</code>	1118	<code>\tex_Umathsupbottommin:D</code>	1182
<code>\tex_Umathopinnerspacing:D</code> ...	1119	<code>\tex_Umathsupshiftdrop:D</code>	1183
<code>\tex_Umathopopenspacing:D</code>	1120	<code>\tex_Umathsupshiftup:D</code>	1184
<code>\tex_Umathopopspacing:D</code>	1121	<code>\tex_Umathsupsubbottommax:D</code> ..	1185
<code>\tex_Umathopordspacing:D</code>	1122	<code>\tex_Umathunderbarkern:D</code>	1186
<code>\tex_Umathoppunctspacing:D</code> ...	1123	<code>\tex_Umathunderbarrule:D</code>	1187
<code>\tex_Umathoprelspacing:D</code>	1124	<code>\tex_Umathunderbarvgap:D</code>	1188
<code>\tex_Umathordbinspacing:D</code>	1125	<code>\tex_Umathunderdelimitervgap:D</code>	1190
<code>\tex_Umathordclosespacing:D</code> ..	1126	<code>\tex_Umathunderdelimitervgap:D</code>	1192
<code>\tex_Umathordinnerspacing:D</code> ..	1127	<code>\tex_undefined:D</code> ... 279, 587, 810,	
<code>\tex_Umathordopenspacing:D</code> ...	1128	1327, 1399, 1400, 1408, 1414, 1420,	
<code>\tex_Umathordopspacing:D</code>	1129	1426, 1431, 1432, 1433, 2644, 2652,	
<code>\tex_Umathordordspacing:D</code>	1130	9518, 15513, 15528, 15583, 15604,	
<code>\tex_Umathordpunctspacing:D</code> ..	1131	22998, 23429, 23439, 23517, 23617	
<code>\tex_Umathordrelspacing:D</code>	1132	<code>\tex_underline:D</code>	577, 1296
<code>\tex_Umathoverbarkern:D</code>	1133	<code>\tex_unexpanded:D</code>	
<code>\tex_Umathoverbarrule:D</code>	1134	.. 672, 1447, 1477, 2121, 3221, 29221	
<code>\tex_Umathoverbarvgap:D</code>	1135	<code>\tex_unhbox:D</code>	578, 27257
<code>\tex_Umathoverdelimitervbgap:D</code> .	1137	<code>\tex_unhcopy:D</code>	579, 27256
<code>\tex_Umathoverdelimitervgap:D</code> .	1139	<code>\tex_uniformdeviate:D</code>	
<code>\tex_Umathpunctbinspacing:D</code> ..	1140	.. 494, 785, 921, 922, 1040, 8281,	
<code>\tex_Umathpunctclosespacing:D</code> .	1142	8312, 9901, 22515, 22516, 22697, 22700	
<code>\tex_Umathpunctinnerspacing:D</code> .	1144	<code>\tex_unkern:D</code>	580
<code>\tex_Umathpunctopenspacing:D</code> .	1145	<code>\tex_unless:D</code>	673, 2105
<code>\tex_Umathpunctopspacing:D</code> ...	1146	<code>\tex_Unosubscript:D</code>	1193
<code>\tex_Umathpunctordspacing:D</code> ..	1147	<code>\tex_Unosuperscript:D</code>	1194
<code>\tex_Umathpunctpunctspacing:D</code> .	1149	<code>\tex_unpenalty:D</code>	581
<code>\tex_Umathpunctrelspacing:D</code> ..	1150	<code>\tex_unskip:D</code>	582
<code>\tex_Umathquad:D</code>	1151	<code>\tex_unvbox:D</code>	583, 27346
<code>\tex_Umathradicaldegreeafter:D</code>	1153	<code>\tex_unvcopy:D</code>	584, 27345
<code>\tex_Umathradicaldegreebefore:D</code>	1155	<code>\tex_Uoverdelimiter:D</code>	1195
<code>\tex_Umathradicaldegreeraise:D</code>	1157	<code>\tex_uppercase:D</code>	585, 32427
<code>\tex_Umathradicalkern:D</code>	1158	<code>\tex_uptexrevision:D</code> ...	1276, 31969
<code>\tex_Umathradicalrule:D</code>	1159	<code>\tex_uptexversion:D</code> ...	1277, 31968
<code>\tex_Umathradicalvgap:D</code>	1160	<code>\tex_Uradical:D</code>	1196

<code>\tex_Uroot:D</code>	1197	<code>\tex_XeTeXgenerateactualtext:D</code> .	836
<code>\tex_Uskewed:D</code>	1198	<code>\tex_XeTeXglyph:D</code>	837
<code>\tex_Uskewedwithdelims:D</code>	1199	<code>\tex_XeTeXglyphbounds:D</code>	838
<code>\tex_Ustack:D</code>	1200	<code>\tex_XeTeXglyphindex:D</code>	839
<code>\tex_Ustartdisplaymath:D</code>	1201	<code>\tex_XeTeXglyphname:D</code>	840
<code>\tex_Ustartmath:D</code>	1202	<code>\tex_XeTeXinputencoding:D</code>	841
<code>\tex_Ustopdisplaymath:D</code>	1203	<code>\tex_XeTeXinputnormalization:D</code> .	843
<code>\tex_Ustopmath:D</code>	1204	<code>\tex_XeTeXinterchartokenstate:D</code> .	845
<code>\tex_Usubscript:D</code>	1205	<code>\tex_XeTeXinterchartoks:D</code>	846
<code>\tex_Usuperscript:D</code>	1206	<code>\tex_XeTeXisdefaultselector:D</code> ..	848
<code>\tex_Underdelimater:D</code>	1207	<code>\tex_XeTeXisexclusivefeature:D</code> .	850
<code>\tex_Uvextensible:D</code>	1208	<code>\tex_XeTeXlastfontchar:D</code>	851
<code>\tex_vadjust:D</code>	586	<code>\tex_XeTeXlinebreaklocale:D</code> ...	853
<code>\tex_valign:D</code>	587	<code>\tex_XeTeXlinebreakpenalty:D</code> ..	854
<code>\tex_vbadness:D</code>	588	<code>\tex_XeTeXlinebreakskip:D</code>	852
<code>\tex_vbox:D</code>	589, 27261, 27266, 27271, 27276, 27281, 27300, 27305, 27312, 27318, 27333, 27339	<code>\tex_XeTeXOTcountfeatures:D</code> ...	855
<code>\tex_vcenter:D</code>	590, 1446	<code>\tex_XeTeXOTcountlanguages:D</code> ..	856
<code>\tex_vfi:D</code>	1267	<code>\tex_XeTeXOTcountscripts:D</code>	857
<code>\tex_vfil:D</code>	591	<code>\tex_XeTeXOTfeaturetag:D</code>	858
<code>\tex_vfill:D</code>	592	<code>\tex_XeTeXOTlanguagetag:D</code>	859
<code>\tex_vfilneg:D</code>	593	<code>\tex_XeTeXOTscripttag:D</code>	860
<code>\tex_vfuzz:D</code>	594	<code>\tex_XeTeXpdffile:D</code>	861
<code>\tex_voffset:D</code>	595, 1453	<code>\tex_XeTeXpdfpagecount:D</code>	862
<code>\tex_vpack:D</code>	1009	<code>\tex_XeTeXpicfile:D</code>	863
<code>\tex_vrule:D</code>	596, 28760, 28815	<code>\tex_XeTeXrevision:D</code> 864, 10067, 31977	
<code>\tex_vsize:D</code>	597	<code>\tex_XeTeXselectorname:D</code>	865
<code>\tex_vskip:D</code>	598, 15001	<code>\tex_XeTeXtracingfonts:D</code>	866
<code>\tex_vsplit:D</code>	599, 27350, 27355	<code>\tex_XeTeXupwardsmode:D</code>	867
<code>\tex_vss:D</code>	600	<code>\tex_XeTeXuseglyphmetrics:D</code> ...	868
<code>\tex_vtop:D</code> ..	601, 27263, 27288, 27293	<code>\tex_XeTeXvariation:D</code>	869
<code>\tex_wd:D</code>	602, 27077	<code>\tex_XeTeXvariationdefault:D</code> ..	870
<code>\tex_widowpenalties:D</code>	674	<code>\tex_XeTeXvariationmax:D</code>	871
<code>\tex_widowpenalty:D</code>	603	<code>\tex_XeTeXvariationmin:D</code>	872
<code>\tex_write:D</code>		<code>\tex_XeTeXvariationname:D</code>	873
<code>\tex_xdef:D</code>	604, 2571, 2573, 13358, 13361, 13378	<code>\tex_XeTeXversion:D</code>	
<code>\tex_xdof:D</code>	605, 1475, 2177, 2181, 2185, 2189		874, 8816, 9494, 9893, 11282, 31976
<code>\tex_XeTeXcharclass:D</code>	817	<code>\tex_xkanjiskip:D</code>	1263
<code>\tex_XeTeXcharglyph:D</code>	818	<code>\tex_xleaders:D</code>	606
<code>\tex_XeTeXcountfeatures:D</code>	819	<code>\tex_xspaceskip:D</code>	607
<code>\tex_XeTeXcountglyphs:D</code>	820	<code>\tex_xspcode:D</code>	1264
<code>\tex_XeTeXcountselectors:D</code>	821	<code>\tex_ybaselineshift:D</code>	1265
<code>\tex_XeTeXcountvariations:D</code> ...	822	<code>\tex_year:D</code>	608, 1422, 1426
<code>\tex_XeTeXdashbreakstate:D</code>	824	<code>\tex_yoko:D</code>	1266
<code>\tex_XeTeXdefaultencoding:D</code> ...	823	<code>\text</code>	31184
<code>\tex_XeTeXfeaturecode:D</code>	825	text commands:	
<code>\tex_XeTeXfeaturename:D</code>	826	<code>\l_text_accents_tl</code>	
<code>\tex_XeTeXfindfeaturebyname:D</code> ..	828	255, 258, 29518, 29742, 31315
<code>\tex_XeTeXfindselectorbyname:D</code> .	830	<code>\l_text_case_exclude_arg_tl</code>	
<code>\tex_XeTeXfindvariationbyname:D</code> .	832	257, 258, 29538, 30070
<code>\tex_XeTeXfirstfontchar:D</code>	833	<code>\text_declare_expand_equivalent:Nn</code>	
<code>\tex_XeTeXfonttype:D</code>	834	255, 29876
		<code>\text_declare_purify_equivalent:Nn</code>	
		258, 258,
			31164, 31177, 31178, 31179, 31180,

- 31197, 31222, 31223, 31224, 31225,
- 31228, 31229, 31235, 31237, 31238,
- 31239, 31247, 31259, 31301, 31316
- \text_expand 257
- \text_expand:n
..... 255, 258, 29556, 29909, 31013
- \l_text_expand_exclude_tl
..... 255, 258, 29544, 29743
- \l_text_letterlike_tl
..... 255, 258, 29518, 29780
- \text_lowercase:n
... 69, 131, 257, 29887, 32727, 32729
- \text_lowercase:nn
..... 257, 29887, 32730, 32732
- \l_text_math_arg_tl ... 255, 258,
258, 29540, 29734, 29741, 30069, 31111
- \l_text_math_delims_tl . 255, 258,
258, 258, 29542, 29668, 30002, 31043
- \text_purify:n 258, 31009
- \text_titlecase:n
... 69, 129, 257, 29887, 32739, 32741
- \text_titlecase:nn
..... 257, 29887, 32742, 32744
- \l_text_titlecase_check_letter_-
bool 257, 258, 29885, 30175
- \text_titlecase_first:n .. 257, 29887
- \text_titlecase_first:nn . 257, 29887
- \text_uppercase:n
69, 129, 131, 257, 29887, 32733, 32735
- \text_uppercase:nn
..... 257, 29887, 32736, 32738
- text internal commands:
- __text_change_case:nnn
.... 29888, 29890, 29892, 29894,
29896, 29898, 29900, 29902, 29903
- __text_change_case_aux:nnn .. 29903
- __text_change_case_break:w .. 29903
- __text_change_case_char:nnnN ...
..... 29903,
30278, 30289, 30298, 30312, 30400,
30500, 30533, 30615, 30629, 30652
- __text_change_case_char_-
aux:nnnN 29903
- __text_change_case_char_-
lower:nnN 29903
- __text_change_case_char_next_-
end:nn 29903
- __text_change_case_char_next_-
lower:nn 29903
- __text_change_case_char_next_-
title:nn 29903
- __text_change_case_char_next_-
titleonly:nn 29903
- __text_change_case_char_next_-
upper:nn 29903
- __text_change_case_char_-
title:nN 29903
- __text_change_case_char_-
title:nnN 29903
- __text_change_case_char_-
title:nnnN 29903
- __text_change_case_char_-
titleonly:nN 29903
- __text_change_case_char_-
titleonly:nnN 29903
- __text_change_case_char_-
titleonly:nnnN 29903
- __text_change_case_char_-
UTFviii:nnnn 29903
- __text_change_case_char_-
UTFviii:nnnNN 29903
- __text_change_case_char_-
UTFviii:nnnNNN 29903
- __text_change_case_char_-
UTFviii:nnnNNNN 30232
- __text_change_case_char_-
UTFviii:nnnNNNNN 29903
- __text_change_case_cs_check:nnN
..... 29903
- __text_change_case_end:w 29903
- __text_change_case_exclude:nnN .
..... 29903
- __text_change_case_exclude:nnNN
..... 29903
- __text_change_case_exclude:nnNn
..... 29903
- __text_change_case_exclude:nnnnN
..... 29903
- __text_change_case_group_-
lower:nnn 29903
- __text_change_case_group_-
title:nnn 29903
- __text_change_case_group_-
titleonly:nnn 29903
- __text_change_case_group_-
upper:nnn 29903
- __text_change_case_if_greek:n 30374
- __text_change_case_if_greek:nTF
..... 30301
- __text_change_case_letterlike:nnnnN
..... 29903
- __text_change_case_letterlike_-
lower:nnN 29903
- __text_change_case_letterlike_-
title:nnN 29903
- __text_change_case_letterlike_-
titleonly:nnN 29903

_text_change_case_letterlike_-
 upper:nnN [29903](#)
 _text_change_case_loop:nnw ...
 [29903](#), [30326](#), [30332](#), [30367](#),
 [30368](#), [30441](#), [30458](#), [30477](#), [30571](#),
 [30583](#), [30595](#), [30600](#), [30610](#), [30627](#)
 _text_change_case_lower_-
 az:nnnN [30654](#)
 _text_change_case_lower_lt:nnN
 [30402](#)
 _text_change_case_lower_-
 lt:nnnN [30406](#)
 _text_change_case_lower_lt:nnw
 [30402](#)
 _text_change_case_lower_lt_-
 auxi:nnnN [30408](#), [30419](#)
 _text_change_case_lower_lt_-
 auxii:nnnN [30423](#), [30444](#)
 _text_change_case_lower_-
 sigma:NnnN [29903](#)
 _text_change_case_lower_-
 sigma:nnnN ... [29903](#), [30447](#), [30573](#)
 _text_change_case_lower_-
 sigma:nnNw [29903](#)
 _text_change_case_lower_-
 tr:NnnN [30558](#)
 _text_change_case_lower_-
 tr:nnnN [30558](#), [30655](#)
 _text_change_case_lower_-
 tr:nnnNN [30558](#)
 _text_change_case_lower_-
 tr:nnNw [30558](#)
 _text_change_case_math_-
 group:nnNn [29903](#)
 _text_change_case_math_-
 loop:nnNw [29903](#)
 _text_change_case_math_N_-
 type:nnNN [29903](#)
 _text_change_case_math_-
 search:nnNNN [29903](#)
 _text_change_case_math_-
 space:nnNw [29903](#)
 _text_change_case_N_type:nnN [29903](#)
 _text_change_case_N_type:nnnN .
 [29903](#)
 _text_change_case_N_type_-
 aux:nnN [29903](#)
 _text_change_case_result:n . [29903](#)
 _text_change_case_setup:NN ...
 [30946](#), [30953](#), [30955](#)
 _text_change_case_setup:Nn ...
 [30977](#), [30997](#), [30999](#)
 _text_change_case_space:nnw . [29903](#)
 _text_change_case_store:n
 [29903](#), [30273](#), [30295](#), [30318](#), [30336](#),
 [30358](#), [30435](#), [30449](#), [30474](#), [30502](#),
 [30529](#), [30552](#), [30569](#), [30581](#), [30593](#),
 [30598](#), [30609](#), [30622](#), [30640](#), [30647](#)
 _text_change_case_store:nw . [29903](#)
 _text_change_case_title_-
 el:nnnN [30395](#)
 _text_change_case_title_nl:nnN
 [30523](#)
 _text_change_case_title_-
 nl:nnnN [30523](#)
 _text_change_case_title_nl:nnw
 [30523](#)
 _text_change_case_upper_-
 az:nnnN [30654](#)
 _text_change_case_upper_-
 de-alt:nnnN [30265](#)
 _text_change_case_upper_-
 de-alt:nnnNN [30265](#)
 _text_change_case_upper_el:nnN
 [30301](#)
 _text_change_case_upper_-
 el:nnnN [30301](#)
 _text_change_case_upper_-
 el:nnnn [30301](#)
 _text_change_case_upper_el_-
 aux:nnnN [30301](#)
 _text_change_case_upper_el_-
 loop:nnw [30301](#)
 _text_change_case_upper_lt:nnN
 [30480](#)
 _text_change_case_upper_-
 lt:nnnN [30484](#)
 _text_change_case_upper_lt:nnw
 [30480](#)
 _text_change_case_upper_lt_-
 aux:nnnN [30486](#), [30497](#)
 _text_change_case_upper_-
 tr:nnnN [30632](#), [30657](#)
 _text_change_cases_lower_-
 lt:nnnN [30402](#)
 _text_change_cases_lower_lt_-
 auxi:nnnN [30402](#)
 _text_change_cases_lower_lt_-
 auxii:nnnN [30402](#)
 _text_change_cases_upper_-
 lt:nnnN [30480](#)
 _text_change_cases_upper_lt_-
 aux:nnnN [30480](#)
 _text_char_catcode:N
 [29471](#), [30157](#), [30167](#), [30168](#),
 [30274](#), [30361](#), [30437](#), [30438](#), [30439](#),

- 30450, 30475, 30503, 30530, 30553,
30570, 30582, 30594, 30599, 30643
- \c_text_chardef_group_begin_
token 29550, 29632
- \c_text_chardef_group_end_token
..... 29550, 29640
- \c_text_chardef_space_token ...
..... 29550, 29619
- \c_text_dotless_i_tl . 30609, 30658
- \c_text_dotted_I_tl .. 30648, 30658
- _text_expand:n 29556
- _text_expand_cs:N 29556
- _text_expand_cs_expand:N ... 29556
- _text_expand_encoding:N 29556
- _text_expand_encoding_escape:N
..... 29556
- _text_expand_encoding_escape:NN
..... 29829, 29834, 29839
- _text_expand_end:w 29556
- _text_expand_exclude:N 29556
- _text_expand_exclude:NN 29556
- _text_expand_exclude:Nn 29556
- _text_expand_exclude:nN 29556
- _text_expand_explicit:N 29556
- _text_expand_group:n 29556
- _text_expand_implicit:N 29556
- _text_expand_letterlike:N . 29556
- _text_expand_letterlike:NN . 29556
- _text_expand_loop:w 29556
- _text_expand_math_group:Nn . 29556
- _text_expand_math_loop:Nw . 29556
- _text_expand_math_N_type:NN . 29556
- _text_expand_math_search:NNN 29556
- _text_expand_math_space:Nw . 29556
- _text_expand_N_type:N 29556
- _text_expand_N_type_auxi:N . 29556
- _text_expand_N_type_auxii:N . 29556
- _text_expand_N_type_auxiii:N 29556
- _text_expand_noexpand:nn ... 29556
- _text_expand_noexpand:w
..... 29861, 29869
- _text_expand_protect:N 29556
- _text_expand_protect:nN 29556
- _text_expand_protect:Nw 29556
- _text_expand_replace:N 29556
- _text_expand_replace:n 29556
- _text_expand_result:n 29556
- _text_expand_space:w 29556
- _text_expand_store:n 29556
- _text_expand_store:nw 29556
- \c_text_grosses_Eszett_tl
..... 30295, 30658
- \c_text_I_ogonek_tl 30658
- \c_text_i_ogonek_tl 30658
- _text_if_expandable:NTF
..... 29503, 29858, 31154
- _text_if_recursion_tail_stop:N
..... 31008, 31037, 31161
- _text_if_recursion_tail_stop_
do:Nn 29385, 29612, 29674,
29699, 29757, 29785, 29995, 30012,
30037, 30081, 31049, 31087, 31115
- _text_loop:Nn 31244, 31252, 31256,
31264, 31275, 31318, 31323, 31350
- _text_loop:nn . 30697, 30706, 30742
- _text_loop:NNn . 31369, 31375, 31377
- \l_text_math_mode_tl 29549
- \c_text_mathchardef_group_
begin_token 29550, 29633
- \c_text_mathchardef_group_end_
token 29550, 29641
- \c_text_mathchardef_space_token
..... 29550, 29623
- _text_purify:n 31009
- _text_purify_accent:NN 31302
- _text_purify_expand:N 31009
- _text_purify_group:n 31009
- _text_purify_loop:w 31009
- _text_purify_math_cmd:N 31009
- _text_purify_math_cmd:n
..... 31120, 31124
- _text_purify_math_cmd:NN ... 31009
- _text_purify_math_cmd:Nn ... 31009
- _text_purify_math_end:w 31009
- _text_purify_math_group:NNn . 31009
- _text_purify_math_loop:NNw . 31009
- _text_purify_math_N_type:NNN 31009
- _text_purify_math_result:n ...
..... 31061,
31065, 31066, 31067, 31072, 31125
- _text_purify_math_search:NNN 31009
- _text_purify_math_space:NNw . 31009
- _text_purify_math_start:NNw . 31009
- _text_purify_math_stop:Nw
..... 31072, 31088
- _text_purify_math_store:n .. 31009
- _text_purify_math_store:nw . 31009
- _text_purify_N_type:N 31009
- _text_purify_N_type_aux:N .. 31009
- _text_purify_protect:N 31009
- _text_purify_replace:N 31009
- _text_purify_replace:n 31009
- _text_purify_space:w 31009
- _text_quark_if_nil:nTF 29380, 29817
- _text_quark_if_nil_p:n 29380
- _text_tmp:n 31261,
31266, 31322, 31329, 31336, 31374

- _text_tmp:nnnn ... 30708, 30739, 30740, 31266, 31267, 31341, 31342
- _text_tmp:w 30663, 30666, 30682, 30685, 30686, 30687, 30688, 30689, 30702, 30724, 30922, 30925, 30937, 30940, 30941, 30942
- _text_tmp_aux:n 31338, 31341
- _text_token_to_explicit:N 29386, 31143
- _text_token_to_explicit:n .. 29386
- _text_token_to_explicit_auxi:w 29386
- _text_token_to_explicit_auxii:w 29386
- _text_token_to_explicit_auxiii:w 29386
- _text_token_to_explicit_char:N 29386
- _text_token_to_explicit_cs:N 29386
- _text_token_to_explicit_cs_aux:N 29386
- _text_use_i_delimit_by_q_recursion_stop:nw 29383, 29678, 29766, 29789, 30016, 30085, 31053, 31119
- \textbaselineshiftfactor 1260
- \textbf 31189
- \textdir 1004, 1876
- \textdirection 1005
- \textfont 555
- \textit 31191
- \textmd 31190
- \textnormal 31185
- \textrm 31186
- \textsc 31194
- \textsf 31187
- \textsl 31192
- \textstyle 556
- \texttt 19064, 31188
- \textulc 31195
- \textup 31193
- \TeXeTstate 665, 1536
- \tfont 1262, 2079
- \TH 29535, 30966, 31285
- \th 29535, 30966, 31298
- \the 61, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 557
- \thickmuskip 558
- \thinmuskip 559
- thousand commands:
 - \c_one_thousand 32518
 - \c_ten_thousand 32518
- \time 560, 1405, 10077, 10079
- \tiny 28751, 31220
- tl commands:
 - \c_empty_tl 58, 520, 552, 3329, 4263, 4279, 4281, 4302, 4576, 9217, 9223, 10203, 10222, 12384, 29266, 32048, 32085, 32104
 - \l_my_tl 222, 228
 - \c_novalue_tl 47, 58, 4303, 4662
 - \c_space_tl 58, 4312, 4933, 5886, 10658, 10667, 12171, 13820, 13822, 28537, 28581, 28648, 29279, 29350, 29605, 29626, 29712, 29987, 30052, 31030, 31032, 31103, 31235, 31757, 31759, 32320
 - \tl_analysis_map_inline:Nn 221, 23692, 25251
 - \tl_analysis_map_inline:nn 221, 23692, 25812
 - \tl_analysis_show:N 221, 23719, 32745, 32746
 - \tl_analysis_show:n 221, 23719, 32747, 32748
 - \tl_build_begin:N 268, 269, 269, 269, 1005, 1176, 24414, 24913, 25277, 25370, 26119, 32004, 32019
 - \tl_build_clear:N 268, 32019
 - \tl_build_end:N 268, 269, 1005, 1176, 1177, 24444, 24452, 24923, 25332, 25389, 26153, 32092
 - \tl_build_gbegin:N 268, 269, 269, 269, 32004, 32020
 - \tl_build_gclear:N 268, 32019
 - \tl_build_gend:N 269, 32092
 - \tl_build_get:N 269
 - \tl_build_get:NN 269, 32078
 - \tl_build_gput_left:Nn ... 269, 32061
 - \tl_build_gput_right:Nn .. 269, 32021
 - \tl_build_put_left:Nn ... 269, 32061
 - \tl_build_put_right:Nn . 269, 1033, 1178, 24421, 24439, 24447, 24451, 24501, 24504, 24537, 24551, 24555, 24680, 24694, 24735, 24760, 24769, 24779, 24811, 24824, 24828, 24910, 24916, 24922, 24926, 24969, 25237, 25253, 25271, 25340, 25385, 25398, 26138, 26177, 26209, 26271, 26274, 26289, 26333, 26349, 26385, 32021
 - \tl_case:Nn 48, 4692
 - \tl_case:nn 423
 - \tl_case:nn(TF) 514, 1171
 - \tl_case:Nnn 32420, 32422
 - \tl_case:NnTF 48, 4692, 4697, 4702, 32421, 32423
 - \tl_clear:N 43, 44, 4278, 4285, 4390, 6169,

- 10264, 10265, 13515, 13516, 13519,
13528, 13638, 13641, 13701, 14212,
16043, 24099, 26121, 32095, 32156
\tl_clear_new:N 44,
4284, 10268, 10269, 14475, 14476,
14477, 14478, 14479, 29878, 31166
\tl_concat:NNN 44, 4294, 5311
\tl_const:Nn
..... 43, 530, 4266, 4302, 4310,
4312, 4386, 6006, 6011, 6331, 6332,
8074, 8129, 9974, 10262, 11035,
11287, 11310, 11740, 11798, 12095,
12096, 12135, 12140, 12142, 12144,
12146, 12148, 12153, 12154, 12161,
13412, 13418, 13867, 16588, 16589,
16590, 16591, 16592, 16600, 16689,
18805, 20108, 20555, 20556, 20557,
20558, 20559, 20560, 20561, 20562,
20563, 23806, 23871, 26418, 29254,
29269, 29292, 29304, 29333, 29363,
29364, 29365, 30668, 30710, 30726,
30927, 30949, 30951, 30969, 30970,
30985, 30992, 31321, 31372, 32141
\tl_count:N 27, 48, 51, 52, 4800
\tl_count:n 27, 48, 51, 52, 341, 431,
432, 507, 734, 2301, 2305, 2693,
2743, 4800, 5127, 5142, 5154, 25169
\tl_count_tokens:n 52, 4813
\tl_gclear:N
..... 43, 937, 4278, 4287, 10046,
10141, 10266, 10267, 23080, 32100
\tl_gclear_new:N 44, 4284, 10270, 10271
\tl_gconcat:NNN 44, 4294, 5312
\tl_gput_left:Nn . 44, 4331, 6907, 7090
\tl_gput_right:Nn . 44, 2253, 2254,
4243, 4355, 8204, 10049, 10144, 22784
\tl_gremove_all:Nn 45, 4558
\tl_gremove_once:Nn 45, 4552
\tl_greplace_all:Nnn . 45, 4483, 4561
\tl_greplace_once:Nnn 45, 4483, 4555
\tl_greverse:N 52, 4963
.tl_gset:N 188, 15784
\tl_gset:Nn 44, 76,
394, 1179, 4297, 4313, 4396, 4486,
4490, 4854, 4966, 5342, 5346, 6046,
6062, 6112, 6258, 6310, 6321, 6476,
6525, 6578, 6584, 6815, 7015, 7172,
8113, 8118, 8136, 8173, 8190, 8230,
8256, 8381, 8413, 8450, 8456, 9931,
9941, 9954, 10163, 10185, 10187,
10189, 10191, 10193, 10283, 10310,
10329, 10372, 10408, 10457, 10496,
11857, 11886, 11932, 11940, 11963,
18803, 23076, 23584, 24104, 25232,
31863, 31873, 31883, 32099, 32723
\tl_gset_eq:NN 44, 4281,
4290, 5308, 6089, 6105, 8097, 8098,
8099, 8100, 9592, 10276, 10277,
10278, 10279, 11769, 11770, 11771,
11772, 18810, 23070, 26413, 32702
\tl_gset_from_file:Nnn 32693
\tl_gset_from_file_x:Nnn 32693
\tl_gset_rescan:Nnn 46, 4387
.tl_gset_x:N 188, 15784
\tl_gsort:Nn 53, 4895, 23068
\tl_gtrim_spaces:N 53, 4845
\tl_head:N 54, 4969
\tl_head:n . . 54, 54, 359, 409, 410,
415, 3287, 4969, 5151, 29289, 29297
\tl_head:w
..... 54, 411, 412, 4969, 29314, 29345
\tl_if_blank:nTF
..... 46, 54, 54, 54, 4564,
4997, 5141, 5291, 5318, 9911, 10666,
10745, 11160, 12290, 13200, 13722,
13924, 13926, 13946, 13979, 14087,
14171, 14272, 14281, 15360, 15961,
15981, 16161, 16204, 16206, 23242,
25833, 29245, 29258, 29308, 29337,
30421, 30446, 30499, 30674, 32316
\tl_if_blank_p:n 46, 4564, 14115
\tl_if_empty:N 5395, 5397, 10511, 10513
\tl_if_empty:NNTF . 47, 4574, 12187,
12197, 13532, 13622, 13657, 13739,
14015, 14202, 14238, 16137, 26176
\tl_if_empty:nTF
..... 47, 398, 400, 401, 552, 561,
2341, 2432, 3266, 3385, 3988, 3995,
4012, 4162, 4497, 4584, 4595, 4643,
4683, 5090, 5111, 5353, 6137, 7205,
8139, 9655, 10216, 10235, 10244,
10247, 10524, 10557, 11503, 11722,
11827, 12459, 12551, 12566, 12686,
12690, 12764, 12826, 12935, 12936,
12945, 12952, 12958, 12965, 13526,
14423, 14426, 14546, 15412, 15509,
16312, 17304, 18162, 22463, 22531,
23810, 23811, 26993, 29331, 32590
\tl_if_empty_p:N 47, 4574
\tl_if_empty_p:n 47, 4584, 4595
\tl_if_eq:NN 423
\tl_if_eq:nn(TF) 121, 121
\tl_if_eq:NNTF
..... 38, 47, 48, 492, 4608, 4716, 8242,
11983, 12532, 12586, 28826, 28829
\tl_if_eq:nnTF
..... 47, 79, 79, 492, 4618, 10545

- \tl_if_eq_p:NN [47](#), [4608](#)
- \tl_if_exist:N [5391](#), [5393](#)
- \tl_if_exist:NTF
 - [44](#), [4285](#), [4287](#), [4300](#), [4793](#),
 - [11172](#), [11183](#), [11262](#), [11270](#), [23721](#)
- \tl_if_exist_p:N [44](#), [4300](#)
- \tl_if_head_eq_catcode:nN [411](#)
- \tl_if_head_eq_catcode:nNTF [55](#), [5003](#)
- \tl_if_head_eq_catcode_p:nN [55](#), [5003](#)
- \tl_if_head_eq_charcode:nN [411](#)
- \tl_if_head_eq_charcode:nNTF ...
 - [55](#), [5003](#), [29247](#)
- \tl_if_head_eq_charcode_p:nN [55](#), [5003](#)
- \tl_if_head_eq_meaning:nN [412](#)
- \tl_if_head_eq_meaning:nNTF [55](#), [5003](#)
- \tl_if_head_eq_meaning_p:nN
 - [55](#), [5003](#), [25168](#)
- \tl_if_head_is_group:nTF
 - [55](#), [3263](#), [3382](#), [4909](#), [5030](#),
 - [5067](#), [5093](#), [10242](#), [13784](#), [29587](#),
 - [29691](#), [29936](#), [30029](#), [31023](#), [31079](#)
- \tl_if_head_is_group_p:n ... [55](#), [5093](#)
- \tl_if_head_is_N_type:n [411](#)
- \tl_if_head_is_N_type:nTF ... [55](#),
 - [3260](#), [3324](#), [3370](#), [3376](#), [3421](#), [3436](#),
 - [3481](#), [4680](#), [4906](#), [5007](#), [5024](#), [5043](#),
 - [5076](#), [5212](#), [13781](#), [29584](#), [29688](#),
 - [29933](#), [30026](#), [30153](#), [30324](#), [30456](#),
 - [30509](#), [30537](#), [30578](#), [31020](#), [31076](#)
- \tl_if_head_is_N_type_p:n .. [55](#), [5076](#)
- \tl_if_head_is_space:nTF
 - [55](#), [5104](#), [5194](#), [5203](#), [5880](#)
- \tl_if_head_is_space_p:n ... [55](#), [5104](#)
- \tl_if_in:Nn [561](#)
- \tl_if_in:nn [400](#), [400](#)
- \tl_if_in:NnTF
 - [47](#), [4237](#), [4519](#), [4633](#), [4633](#), [4634](#)
- \tl_if_in:nnTF [47](#), [399](#),
 - [423](#), [4433](#), [4503](#), [4505](#), [4633](#), [4634](#),
 - [4635](#), [4638](#), [5446](#), [5454](#), [9988](#), [11720](#),
 - [12445](#), [12447](#), [23995](#), [28628](#), [31990](#)
- \tl_if_novalue:nTF [47](#), [4649](#)
- \tl_if_novalue_p:n [47](#), [4649](#)
- \tl_if_single:n [400](#)
- \tl_if_single:NTF [48](#), [4663](#), [4664](#), [4665](#)
- \tl_if_single:nTF
 - [48](#), [533](#), [4664](#), [4665](#), [4666](#), [4667](#)
- \tl_if_single_p:N [48](#), [4663](#)
- \tl_if_single_p:n [48](#), [4663](#), [4667](#)
- \tl_if_single_token:nTF
 - [48](#), [4678](#), [30980](#)
- \tl_if_single_token_p:n [48](#), [4678](#)
- \tl_item:Nn [56](#), [5116](#)
- \tl_item:nn [56](#), [414](#), [5116](#), [5142](#)
- \tl_log:N [58](#), [5244](#), [5919](#)
- \tl_log:n [58](#),
 - [345](#), [345](#), [804](#), [2843](#), [2859](#), [5246](#),
 - [5268](#), [5918](#), [9529](#), [9629](#), [18835](#), [31754](#)
- \tl_lower_case:n [32727](#)
- \tl_lower_case:nn [32727](#)
- \tl_map_break: [50](#),
 - [233](#), [960](#), [4729](#), [4735](#), [4747](#), [4757](#),
 - [4764](#), [4772](#), [4778](#), [4784](#), [23715](#), [23716](#)
- \tl_map_break:n
 - [50](#), [50](#), [4784](#), [14037](#), [23075](#)
- \tl_map_function:NN [48](#),
 - [49](#), [49](#), [49](#), [266](#), [266](#), [4725](#), [4808](#), [25239](#)
- \tl_map_function:nN
 - [48](#), [49](#), [49](#), [2737](#),
 - [4725](#), [4803](#), [6218](#), [6220](#), [8142](#), [24521](#)
- \tl_map_inline:Nn [49](#), [49](#), [49](#),
 - [4739](#), [6002](#), [6004](#), [14036](#), [23075](#), [31315](#)
- \tl_map_inline:nn [40](#),
 - [49](#), [49](#), [4739](#), [9895](#), [11655](#), [11657](#),
 - [11659](#), [11669](#), [13415](#), [18215](#), [21296](#),
 - [23026](#), [31170](#), [31181](#), [31198](#), [31226](#)
- \tl_map_tokens:Nn ... [49](#), [4753](#), [13933](#)
- \tl_map_tokens:nn [49](#), [4753](#)
- \tl_map_variable:NNn [49](#), [4768](#)
- \tl_map_variable:nNn .. [49](#), [404](#), [4768](#)
- \tl_mixed_case:n [32727](#)
- \tl_mixed_case:nn [32727](#)
- \tl_new:N [43](#), [44](#), [133](#), [388](#),
 - [4260](#), [4285](#), [4287](#), [4631](#), [4632](#), [5273](#),
 - [5274](#), [5275](#), [5276](#), [5925](#), [5927](#), [8071](#),
 - [8072](#), [9973](#), [10050](#), [10145](#), [10160](#),
 - [10204](#), [10259](#), [10260](#), [10961](#), [11551](#),
 - [11739](#), [12089](#), [12477](#), [12478](#), [13036](#),
 - [13043](#), [13067](#), [13276](#), [13305](#), [13389](#),
 - [13391](#), [13404](#), [13406](#), [13407](#), [13409](#),
 - [13713](#), [13752](#), [13753](#), [15291](#), [15294](#),
 - [15299](#), [15301](#), [15307](#), [15308](#), [15310](#),
 - [15311](#), [22780](#), [22952](#), [23392](#), [23862](#),
 - [23863](#), [23869](#), [23870](#), [23880](#), [25799](#),
 - [26046](#), [26048](#), [27716](#), [27741](#), [27742](#),
 - [28746](#), [28992](#), [29519](#), [29522](#), [29538](#),
 - [29540](#), [29542](#), [29544](#), [29549](#), [32144](#)
- \tl_put_left:Nn [44](#), [4331](#)
- \tl_put_right:Nn
 - [44](#), [1177](#), [4355](#), [8202](#), [11005](#),
 - [11007](#), [11010](#), [11012](#), [11013](#), [11015](#),
 - [11017](#), [11019](#), [11020](#), [11022](#), [11024](#),
 - [11026](#), [11028](#), [13663](#), [13666](#), [13671](#),
 - [14055](#), [24106](#), [26212](#), [32183](#), [32188](#)
- \tl_rand_item:N [56](#), [5139](#)
- \tl_rand_item:n [56](#), [5139](#)
- \tl_range:Nnn [57](#), [5146](#)
- \tl_range:nnn [57](#), [68](#), [268](#), [5146](#)

- \tl_range_braced:Nnn [268](#), [32110](#)
- \tl_range_braced:nnn . . . [57](#), [268](#), [32110](#)
- \tl_range_unbraced:Nnn . . . [268](#), [32110](#)
- \tl_range_unbraced:nnn [57](#), [268](#), [32110](#)
- \tl_remove_all:Nn [45](#), [45](#), [4558](#)
- \tl_remove_once:Nn [45](#), [4552](#)
- \tl_replace_all:Nnn
- [45](#), [490](#), [559](#), [4483](#), [4559](#), [8151](#)
- \tl_replace_once:Nnn
- [45](#), [4483](#), [4553](#), [11043](#)
- \tl_rescan:nn [46](#), [46](#), [391](#), [4387](#)
- \tl_reverse:N [52](#), [52](#), [4963](#)
- \tl_reverse:n
- [52](#), [52](#), [52](#), [4943](#), [4964](#), [4966](#)
- \tl_reverse_items:n . . . [52](#), [52](#), [52](#), [4829](#)
- .tl_set:N [188](#), [15784](#)
- \tl_set:Nn
- [44](#), [45](#), [46](#), [76](#), [188](#), [269](#), [269](#), [366](#),
- [389](#), [394](#), [617](#), [1179](#), [4295](#), [4313](#),
- [4394](#), [4484](#), [4488](#), [4621](#), [4622](#), [4779](#),
- [4852](#), [4964](#), [5257](#), [5340](#), [5344](#), [6001](#),
- [6158](#), [6326](#), [8103](#), [8108](#), [8134](#), [8141](#),
- [8145](#), [8156](#), [8171](#), [8182](#), [8228](#), [8238](#),
- [8247](#), [8254](#), [8332](#), [8335](#), [8352](#), [8360](#),
- [8369](#), [8379](#), [8388](#), [8394](#), [8411](#), [8425](#),
- [8447](#), [8453](#), [8562](#), [9114](#), [9912](#), [9978](#),
- [10013](#), [10281](#), [10308](#), [10327](#), [10361](#),
- [10367](#), [10370](#), [10376](#), [10383](#), [10406](#),
- [10455](#), [10494](#), [10635](#), [11003](#), [11008](#),
- [11588](#), [11851](#), [11867](#), [11868](#), [11876](#),
- [11877](#), [11879](#), [11885](#), [11888](#), [11921](#),
- [11922](#), [11931](#), [11939](#), [11943](#), [11961](#),
- [11966](#), [12016](#), [12226](#), [12461](#), [12489](#),
- [12572](#), [13102](#), [13159](#), [13172](#), [13205](#),
- [13308](#), [13319](#), [13396](#), [13471](#), [13474](#),
- [13475](#), [13480](#), [13491](#), [13496](#), [13517](#),
- [13654](#), [13674](#), [13693](#), [13695](#), [13871](#),
- [13906](#), [14008](#), [14013](#), [14028](#), [14040](#),
- [14065](#), [14183](#), [14185](#), [14187](#), [14189](#),
- [14200](#), [14231](#), [14236](#), [14488](#), [14491](#),
- [14492](#), [14493](#), [14494](#), [14501](#), [14502](#),
- [14503](#), [14505](#), [14509](#), [14850](#), [15302](#),
- [15490](#), [15813](#), [15822](#), [15851](#), [15852](#),
- [15864](#), [15872](#), [15893](#), [15894](#), [15906](#),
- [15914](#), [15925](#), [15934](#), [15945](#), [15959](#),
- [16049](#), [16151](#), [18801](#), [19138](#), [23993](#),
- [24006](#), [24455](#), [24862](#), [24867](#), [25132](#),
- [25193](#), [25223](#), [25335](#), [25392](#), [25882](#),
- [25891](#), [25969](#), [26001](#), [26311](#), [26590](#),
- [26659](#), [26689](#), [26713](#), [27983](#), [28629](#),
- [28630](#), [28748](#), [28751](#), [28993](#), [29520](#),
- [29523](#), [29539](#), [29541](#), [29543](#), [29546](#),
- [29879](#), [31167](#), [31861](#), [31871](#), [31881](#),
- [32079](#), [32094](#), [32155](#), [32712](#), [32714](#)
- \tl_set_eq:NN . [44](#), [531](#), [4279](#), [4290](#),
- [5307](#), [6087](#), [6096](#), [8093](#), [8094](#), [8095](#),
- [8096](#), [9591](#), [10272](#), [10273](#), [10274](#),
- [10275](#), [11765](#), [11766](#), [11767](#), [11768](#),
- [12535](#), [12543](#), [14058](#), [15380](#), [15971](#),
- [16038](#), [16059](#), [18809](#), [23068](#), [26408](#)
- \tl_set_from_file:Nnn [32693](#)
- \tl_set_from_file_x:Nnn [32693](#)
- \tl_set_rescan:Nnn
- [46](#), [46](#), [391](#), [655](#), [4387](#)
- .tl_set_x:N [188](#), [15784](#)
- \tl_show:N [58](#), [58](#), [961](#), [5244](#), [5916](#), [23727](#)
- \tl_show:n
- [58](#), [58](#), [263](#), [345](#), [345](#), [417](#), [418](#),
- [804](#), [1170](#), [2839](#), [2856](#), [5244](#), [5253](#),
- [5915](#), [9528](#), [9627](#), [10810](#), [10880](#),
- [10886](#), [10892](#), [10898](#), [18833](#), [31752](#)
- \tl_show_analysis:N [32745](#)
- \tl_show_analysis:n [32745](#)
- \tl_sort:Nn [53](#), [4895](#), [23068](#)
- \tl_sort:nN [53](#), [942](#), [944](#), [4895](#), [23238](#)
- \tl_tail:N [54](#), [447](#), [4969](#), [6321](#), [25143](#)
- \tl_tail:n [54](#), [4969](#)
- \tl_to_lowercase:n [32424](#)
- \tl_to_str:N
- [51](#), [60](#), [162](#), [420](#), [644](#), [1036](#),
- [4789](#), [5361](#), [5438](#), [5446](#), [6480](#), [11263](#),
- [11271](#), [13475](#), [13486](#), [14449](#), [14465](#)
- \tl_to_str:n [46](#),
- [46](#), [51](#), [51](#), [60](#), [69](#), [70](#), [116](#), [144](#),
- [144](#), [162](#), [184](#), [227](#), [228](#), [319](#), [328](#),
- [401](#), [420](#), [426](#), [432](#), [585](#), [602](#), [603](#),
- [1036](#), [1036](#), [2126](#), [2149](#), [2240](#), [2245](#),
- [2326](#), [2408](#), [2873](#), [3547](#), [3561](#), [3564](#),
- [3571](#), [3575](#), [3859](#), [3891](#), [3909](#), [4221](#),
- [4232](#), [4406](#), [4500](#), [4587](#), [4788](#), [5254](#),
- [5269](#), [5323](#), [5362](#), [5446](#), [5454](#), [5589](#),
- [5611](#), [5635](#), [5642](#), [5696](#), [5703](#), [5777](#),
- [5796](#), [5807](#), [5832](#), [5840](#), [5848](#), [5854](#),
- [5866](#), [5877](#), [6001](#), [6114](#), [6119](#), [6184](#),
- [9389](#), [9406](#), [9450](#), [9535](#), [9983](#), [10022](#),
- [10035](#), [11277](#), [11285](#), [11392](#), [11396](#),
- [11426](#), [11427](#), [11460](#), [11475](#), [11477](#),
- [11479](#), [11497](#), [11715](#), [11720](#), [11838](#),
- [11896](#), [11897](#), [11945](#), [11968](#), [11990](#),
- [11991](#), [12330](#), [12331](#), [12624](#), [12625](#),
- [13003](#), [13004](#), [13005](#), [13006](#), [13397](#),
- [13413](#), [13943](#), [13973](#), [14066](#), [14403](#),
- [14690](#), [14891](#), [14992](#), [16215](#), [16726](#),
- [16730](#), [16747](#), [16955](#), [16956](#), [17569](#),
- [17570](#), [17575](#), [17579](#), [22219](#), [22273](#),
- [22347](#), [22854](#), [24521](#), [26275](#), [26425](#),
- [28778](#), [28861](#), [29469](#), [30246](#), [30249](#),
- [31726](#), [31727](#), [31728](#), [31729](#), [31757](#),

- 31759, 31763, 31765, 31770, 31772,
- 31985, 32269, 32297, 32308, 32311
- \tl_to_uppercase:n 32426
- \tl_trim_spaces:N 53, 4845
- \tl_trim_spaces:n
 - ... 52, 4845, 8163, 13852, 13854,
 - 15372, 16221, 16226, 16232, 32316
- \tl_trim_spaces_apply:nN
 - .. 53, 693, 4845, 10218, 10758, 11815
- \tl_trim_spaces:n 406
- \tl_upper_case:n 32727
- \tl_upper_case:nn 32727
- \tl_use:N .. 51, 174, 178, 181, 4791,
- 6339, 6343, 6385, 10045, 10140, 15582
- \g_tmpa_tl 59, 5273
- \l_tmpa_tl 5, 45, 59,
- 1301, 1303, 1320, 1404, 1406, 1410,
- 1412, 1416, 1418, 1422, 1424, 5275
- \g_tmpb_tl 59, 5273
- \l_tmpb_tl 59, 1302,
- 1303, 1318, 1320, 1405, 1406, 1411,
- 1412, 1417, 1418, 1423, 1424, 5275
- tl internal commands:
- __tl_act:NNNnn
 - 407, 407, 409, 4817, 4897, 4948
- __tl_act_count_group:nn 4813
- __tl_act_count_normal:nN 4813
- __tl_act_count_space:n 4813
- __tl_act_end:w 4897
- __tl_act_end:wn 405, 4918, 4924
- __tl_act_group:nwnNNN 4897
- __tl_act_loop:w 4897
- __tl_act_normal:NwnNNN 4897
- __tl_act_output:n 408, 4897
- __tl_act_result:n
 - 408, 4902, 4924, 4939, 4940, 4941, 4942
- __tl_act_reverse 408
- __tl_act_reverse_output:n
 - 4897, 4958, 4960, 4962
- __tl_act_space:wnNNN 408, 4897
- __tl_analysis:n
 - 952, 961, 23415, 23694, 23723, 23731
- __tl_analysis_a:n 23419, 23444
- __tl_analysis_a_bgroup:w
 - 23475, 23497
- __tl_analysis_a_cs:ww 23554
- __tl_analysis_a_egroup:w
 - 23477, 23497
- __tl_analysis_a_group:nw 23497
- __tl_analysis_a_group_aux:w . 23497
- __tl_analysis_a_group_auxii:w 23497
- __tl_analysis_a_group_test:w . 23497
- __tl_analysis_a_loop:w .. 23451,
- 23454, 23495, 23537, 23551, 23569
- __tl_analysis_a_safe:N
 - 23476, 23518, 23554
- __tl_analysis_a_space:w 23474, 23480
- __tl_analysis_a_space_test:w ...
 - 954, 23480
- __tl_analysis_a_store:
 - 954, 23491, 23533, 23539
- __tl_analysis_a_type:w 23455, 23456
- __tl_analysis_b:n 23420, 23582
- __tl_analysis_b_char:Nww
 - 23609, 23615
- __tl_analysis_b_cs:Nww 23611, 23639
- __tl_analysis_b_cs_test:ww .. 23639
- __tl_analysis_b_loop:w
 - 960, 23582, 23685, 23690
- __tl_analysis_b_normal:wwN
 - 23595, 23660
- __tl_analysis_b_normals:ww
 - 958, 959, 23592, 23595, 23636, 23646
- __tl_analysis_b_special:w
 - 23598, 23657
- __tl_analysis_b_special_char:wN
 - 23657
- __tl_analysis_b_special_space:w
 - 23657
- \l__tl_analysis_char_token
 - 949, 954,
 - 955, 23386, 23484, 23489, 23527, 23532
- __tl_analysis_cs_space_count:NN
 - 23399, 23568, 23642
- __tl_analysis_cs_space_count:w
 - 23399
- __tl_analysis_cs_space_count_-end:w
 - 23399
- __tl_analysis_disable:n
 - 23424, 23446, 23512, 23565
- __tl_analysis_extract_charcode:
 - 23393, 23507
- __tl_analysis_extract_charcode_-aux:w
 - 23393
- \l__tl_analysis_index_int
 - 956, 957,
 - 23389, 23449, 23452, 23490, 23508,
 - 23545, 23548, 23574, 23576, 23663
- __tl_analysis_map_inline_aux:Nn
 - 23692
- __tl_analysis_map_inline_-aux:nnn
 - 23692
- \l__tl_analysis_nesting_int
 - 953, 23390, 23450, 23541, 23550
- \l__tl_analysis_normal_int
 - 23388, 23448, 23493, 23535,
 - 23546, 23549, 23566, 23575, 23580

\g__tl_analysis_result_tl
 ... [960](#), [23392](#), [23584](#), [23714](#), [23737](#)
 __tl_analysis_show:
 ... [23725](#), [23733](#), [23735](#)
 __tl_analysis_show_active:n ...
 ... [23750](#), [23779](#)
 __tl_analysis_show_cs:n [23746](#), [23779](#)
 \c__tl_analysis_show_etc_str ...
 ... [963](#), [23799](#), [23801](#), [23806](#)
 __tl_analysis_show_long:nn .. [23779](#)
 __tl_analysis_show_long_-
 aux:nnnn [23779](#), [23785](#)
 __tl_analysis_show_loop:wNw .. [23735](#)
 __tl_analysis_show_normal:n ...
 ... [23753](#), [23759](#)
 __tl_analysis_show_value:N
 ... [23764](#), [23788](#)
 \l__tl_analysis_token
 ... [949](#), [950](#), [953](#), [954](#),
 ... [955](#), [23386](#), [23396](#), [23455](#), [23459](#),
 ... [23462](#), [23465](#), [23513](#), [23517](#), [23532](#)
 \l__tl_analysis_type_int
 ... [953](#), [956](#), [23391](#),
 ... [23458](#), [23473](#), [23541](#), [23543](#), [23547](#)
 __tl_build_begin:NN .. [32004](#), [32049](#)
 __tl_build_begin:NNN .. [1176](#), [32004](#)
 __tl_build_end_loop:NN [32092](#)
 __tl_build_get:NNN
 ... [32078](#), [32094](#), [32099](#)
 __tl_build_get:w [32078](#)
 __tl_build_get_end:w [32078](#)
 __tl_build_last:NNn
 ... [1176](#), [1177](#), [32016](#), [32021](#), [32082](#)
 __tl_build_put:nn [1177](#), [32021](#), [32073](#)
 __tl_build_put:nw [1177](#), [32021](#)
 __tl_build_put_left:NNn [32061](#)
 __tl_case:NnTF
 ... [4695](#), [4700](#), [4705](#), [4710](#), [4712](#)
 __tl_case:nnTF [4692](#)
 __tl_case:Nw [4692](#)
 __tl_case_end:nw [4692](#)
 __tl_count:n [405](#), [4800](#)
 __tl_head_auxi:nw [4969](#)
 __tl_head_auxii:n [4969](#)
 __tl_if_blank_p:NNw [4564](#)
 __tl_if_empty_if:n
 ... [380](#), [397](#), [398](#), [4566](#), [4595](#), [4681](#), [4685](#)
 __tl_if_head_eq_meaning_-
 normal:nN [5044](#), [5048](#)
 __tl_if_head_eq_meaning_-
 special:nN [5045](#), [5057](#)
 __tl_if_head_is_N_type:w .. [413](#), [5076](#)
 __tl_if_head_is_space:w [5104](#)
 __tl_if_noalue:w [4649](#)
 __tl_if_recursion_tail_break:nN
 ... [414](#), [4384](#), [4735](#), [4764](#), [4778](#), [5132](#)
 __tl_if_recursion_tail_stop:nTF
 ... [4384](#)
 __tl_if_recursion_tail_stop_p:n
 ... [4384](#)
 __tl_if_single:nnw .. [401](#), [4669](#), [4677](#)
 __tl_if_single:nTF [4667](#)
 __tl_if_single_p:n [4667](#)
 \l__tl_internal_a_tl
 ... [417](#), [4389](#), [4390](#), [4391](#),
 ... [4618](#), [5257](#), [5263](#), [32701](#), [32702](#),
 ... [32710](#), [32712](#), [32714](#), [32721](#), [32723](#)
 \l__tl_internal_b_tl [4618](#)
 __tl_item:nn [5116](#)
 __tl_item_aux:nn [5116](#)
 __tl_map_function:Nn [403](#), [4725](#), [4744](#)
 __tl_map_tokens:nn [4753](#)
 __tl_map_variable:Nnn [4768](#)
 __tl_quark_if_nil:n [4385](#)
 __tl_quark_if_nil:nTF [4508](#)
 __tl_range:Nnnn .. [5146](#), [32112](#), [32117](#)
 __tl_range:nnNn [5146](#)
 __tl_range:nnnNn [5146](#)
 __tl_range:w [415](#), [5146](#)
 __tl_range_braced:w [415](#), [1179](#), [32110](#)
 __tl_range_collect:nn ... [1179](#), [5146](#)
 __tl_range_collect_braced:w ...
 ... [415](#), [1179](#), [32110](#)
 __tl_range_collect_group:nN .. [5146](#)
 __tl_range_collect_group:nn ...
 ... [5214](#), [5223](#)
 __tl_range_collect_N:nN [5146](#)
 __tl_range_collect_space:nw .. [5146](#)
 __tl_range_collect_unbraced:w [32110](#)
 __tl_range_items:nnNn [415](#)
 __tl_range_normalize:nn
 ... [5161](#), [5165](#), [5225](#)
 __tl_range_skip:w [415](#), [5146](#)
 __tl_range_skip_spaces:n [5146](#)
 __tl_range_unbraced:w [32110](#)
 __tl_replace:NnNNNnn
 ... [394](#), [395](#), [4484](#), [4486](#), [4488](#), [4490](#), [4495](#)
 __tl_replace_auxi:NnnNNNnn [395](#), [4495](#)
 __tl_replace_auxii:nNNNnn
 ... [394](#), [395](#), [396](#), [4495](#)
 __tl_replace_next:w
 ... [394](#), [396](#), [4488](#), [4490](#), [4495](#)
 __tl_replace_wrap:w
 ... [394](#), [396](#), [4484](#), [4486](#), [4495](#)
 __tl_rescan:NNw [391](#), [4387](#), [4469](#), [4474](#)
 \c__tl_rescan_marker_tl
 ... [393](#), [4386](#), [4411](#), [4419](#), [4449](#), [4481](#)
 __tl_reverse_group_preserve:nn [4943](#)

- _tl_reverse_items:nwNwn [4829](#)
- _tl_reverse_items:wn [4829](#)
- _tl_reverse_normal:nN [4943](#)
- _tl_reverse_space:n [4943](#)
- _tl_set_rescan:nNN
..... [391](#), [392](#), [4406](#), [4428](#)
- _tl_set_rescan:NNnn [391](#), [4387](#)
- _tl_set_rescan_multi:nNN
..... [391](#), [392](#), [393](#), [4387](#), [4436](#), [4458](#)
- _tl_set_rescan_single:nnNN ...
..... [392](#), [4428](#)
- _tl_set_rescan_single:NNww .. [393](#)
- _tl_set_rescan_single_aux:nnnNN
..... [4428](#)
- _tl_set_rescan_single_aux:w ...
..... [393](#), [4428](#)
- _tl_show:n [5253](#)
- _tl_show:NN [5244](#)
- _tl_show:w [5253](#)
- _tl_tl_head:w [4969](#), [5010](#), [5027](#), [5051](#)
- _tl_tmp:w [400](#),
[406](#), [4642](#), [4643](#), [4649](#), [4662](#), [4857](#), [4894](#)
- _tl_trim_spaces:nn
..... [693](#), [4846](#), [4849](#), [4857](#)
- _tl_trim_spaces_auxi:w .. [406](#), [4857](#)
- _tl_trim_spaces_auxii:w . [406](#), [4857](#)
- _tl_trim_spaces_auxiii:w [406](#), [4857](#)
- _tl_trim_spaces_auxiv:w . [406](#), [4857](#)
- \tn [23823](#)
- token commands:
- \c_alignment_token [133](#),
[581](#), [11229](#), [11290](#), [11329](#), [23625](#), [29476](#)
- \c_parameter_token
..... [133](#), [582](#), [1031](#), [11290](#), [11333](#), [11336](#)
- \g_peek_token . [137](#), [137](#), [11548](#), [11562](#)
- \l_peek_token [137](#), [137](#), [591](#),
[593](#), [1181](#), [11548](#), [11560](#), [11577](#),
[11616](#), [11628](#), [11648](#), [11698](#), [11699](#),
[11700](#), [11703](#), [32171](#), [32172](#), [32173](#)
- \c_space_token [34](#), [55](#), [58](#), [133](#), [140](#),
[270](#), [411](#), [582](#), [3405](#), [5032](#), [5069](#),
[11238](#), [11290](#), [11353](#), [11577](#), [11700](#),
[13587](#), [23459](#), [23489](#), [23631](#), [24171](#),
[24206](#), [29448](#), [29485](#), [29616](#), [32173](#)
- \token_get_arg_spec:N [32749](#)
- \token_get_prefix_spec:N [32749](#)
- \token_get_replacement_spec:N . [32749](#)
- \token_if_active:NTF [135](#), [11366](#), [30209](#)
- \token_if_active_p:N
..... [135](#), [11366](#), [13802](#), [29847](#), [30184](#), [31133](#)
- \token_if_alignment:NTF
..... [134](#), [134](#), [11327](#)
- \token_if_alignment_p:N .. [134](#), [11327](#)
- \token_if_chardef:NTF
..... [136](#), [11438](#), [23768](#)
- \token_if_chardef_p:N
..... [136](#), [11438](#), [29416](#)
- \token_if_cs:NTF
..... [135](#), [11403](#), [29719](#), [30060](#), [30331](#), [31140](#)
- \token_if_cs_p:N [135](#), [11403](#), [29846](#),
[30464](#), [30517](#), [30545](#), [30590](#), [31132](#)
- \token_if_dim_register:NTF
..... [136](#), [11438](#), [23770](#)
- \token_if_dim_register_p:N [136](#), [11438](#)
- \token_if_eq_catcode:NNTF .. [135](#),
[137](#), [138](#), [138](#), [138](#), [270](#), [3405](#), [11376](#)
- \token_if_eq_catcode_p:NN [135](#), [11376](#)
- \token_if_eq_charcode:NNTF
..... [135](#), [138](#), [138](#), [138](#), [139](#),
[270](#), [11381](#), [12885](#), [13587](#), [20818](#),
[24206](#), [24211](#), [24834](#), [25034](#), [25047](#),
[25049](#), [25087](#), [25209](#), [26179](#), [26258](#)
- \token_if_eq_charcode_p:NN [135](#), [11381](#)
- \token_if_eq_meaning:NNTF
..... [135](#), [139](#), [139](#), [139](#),
[139](#), [270](#), [3408](#), [3419](#), [11371](#), [13639](#),
[17074](#), [18090](#), [18149](#), [19086](#), [19088](#),
[19093](#), [19157](#), [19343](#), [21416](#), [24528](#),
[24840](#), [24873](#), [25022](#), [25045](#), [25077](#),
[25204](#), [25207](#), [26229](#), [26256](#), [26297](#),
[26314](#), [29651](#), [29657](#), [29676](#), [29702](#),
[29860](#), [30014](#), [30040](#), [31051](#), [31089](#)
- \token_if_eq_meaning_p:NN
..... [135](#), [11371](#), [29511](#), [29616](#), [29618](#),
[29622](#), [29632](#), [29633](#), [29640](#), [29641](#)
- \token_if_expandable:NTF
..... [135](#), [11408](#), [23766](#), [29505](#)
- \token_if_expandable_p:N
..... [135](#), [11408](#), [13794](#)
- \token_if_group_begin:NTF [134](#), [11312](#)
- \token_if_group_begin_p:N [134](#), [11312](#)
- \token_if_group_end:NTF .. [134](#), [11317](#)
- \token_if_group_end_p:N .. [134](#), [11317](#)
- \token_if_int_register:NTF
..... [136](#), [11438](#), [23771](#)
- \token_if_int_register_p:N [136](#), [11438](#)
- \token_if_letter:N [584](#)
- \token_if_letter:NTF
..... [135](#), [11356](#), [30166](#), [30180](#)
- \token_if_letter_p:N [135](#), [11356](#), [30183](#)
- \token_if_long_macro:NTF . [135](#), [11438](#)
- \token_if_long_macro_p:N . [135](#), [11438](#)
- \token_if_macro:NTF
..... [135](#), [2878](#), [2887](#), [2896](#), [11386](#), [11492](#)
- \token_if_macro_p:N [135](#), [11386](#)
- \token_if_math_subscript:NTF ...
..... [134](#), [11346](#)

- \token_if_math_subscript_p:N . . . 4240, 4386, 5081, 5097, 5251, 5559, 5975, 5983, 5986, 8291, 8672, 8912, 9634, 9689, 9974, 10058, 10783, 11146, 11150, 11172, 11175, 11183, 11186, 11262, 11263, 11270, 11271, 11290, 11473, 11474, 11479, 11480, 11481, 11482, 11483, 11484, 12081, 13459, 13460, 13461, 13462, 13463, 13470, 13808, 13867, 14000, 14216, 16369, 16410, 16484, 16725, 16740, 16961, 16962, 17451, 17452, 17481, 17650, 17701, 17733, 17753, 17768, 17780, 17781, 17794, 17795, 17820, 17829, 17831, 17856, 17859, 17884, 17886, 17900, 17916, 17934, 18003, 18013, 18014, 18029, 18030, 18363, 18407, 18599, 18840, 22828, 23336, 23353, 23404, 23485, 23528, 23558, 23607, 23618, 23620, 23622, 23632, 23668, 23679, 23725, 23761, 23786, 23807, 24117, 24124, 24225, 24229, 24952, 26202, 26434, 27013, 27015, 27178, 27766, 27982, 28931, 29427, 29428, 29843, 29851, 29878, 29879, 30105, 30108, 30117, 30949, 30951, 30969, 30970, 30983, 30986, 30990, 30993, 31129, 31137, 31166, 31167, 31305, 31308, 31312, 31321, 31373, 32268, 32296, 32308, 32311, 32440
- \token_if_math_superscript:NTF . . . 134, 11340
- \token_if_math_superscript_p:N . . . 134, 11340
- \token_if_math_toggle:NTF 134, 11322
- \token_if_math_toggle_p:N 134, 11322
- \token_if_mathchardef:NTF 136, 11438, 23769
- \token_if_mathchardef_p:N 136, 11438, 29417
- \token_if_muskip_register:NTF 136, 11438
- \token_if_muskip_register_p:N 136, 11438
- \token_if_other:NTF 135, 11361
- \token_if_other_p:N 135, 11361
- \token_if_parameter:NTF . . . 134, 11332
- \token_if_parameter_p:N . . . 134, 11332
- \token_if_primitive:NTF . . . 137, 11486
- \token_if_primitive_p:N . . . 137, 11486
- \token_if_protected_long_ -
macro:NTF 136, 3302, 11438
- \token_if_protected_long_macro_ -
p:N 136, 11438, 13801, 29510
- \token_if_protected_macro:NTF 135, 3301, 11438
- \token_if_protected_macro_p:N 135, 11438, 13800, 29509
- \token_if_skip_register:NTF 136, 11438, 23772
- \token_if_skip_register_p:N 136, 11438
- \token_if_space:NTF 134, 11351
- \token_if_space_p:N 134, 11351
- \token_if_toks_register:NTF 137, 365, 3504, 11438, 23773
- \token_if_toks_register_p:N 137, 11438
- \token_new:Nn 32428
- \token_to_meaning:N 15, 133, 583, 587, 2124, 2140, 2579, 2881, 2890, 2899, 3510, 3561, 11290, 11392, 11459, 11496, 11703, 23396, 23762, 23787, 29453
- \token_to_str:N . . . 5, 17, 60, 133, 162, 333, 413, 512, 585, 765, 767, 1034, 2126, 2140, 2140, 2304, 2313, 2345, 2368, 2416, 2421, 2436, 2457, 2458, 2478, 2579, 2705, 2740, 2747, 2835, 2855, 2868, 3487, 3581, 3666, 3681, 3696, 3703, 3729, 3738, 3789, 3855, 3876, 4067, 4091, 4095, 4110, 4240, 4386, 5081, 5097, 5251, 5559, 5975, 5983, 5986, 8291, 8672, 8912, 9634, 9689, 9974, 10058, 10783, 11146, 11150, 11172, 11175, 11183, 11186, 11262, 11263, 11270, 11271, 11290, 11473, 11474, 11479, 11480, 11481, 11482, 11483, 11484, 12081, 13459, 13460, 13461, 13462, 13463, 13470, 13808, 13867, 14000, 14216, 16369, 16410, 16484, 16725, 16740, 16961, 16962, 17451, 17452, 17481, 17650, 17701, 17733, 17753, 17768, 17780, 17781, 17794, 17795, 17820, 17829, 17831, 17856, 17859, 17884, 17886, 17900, 17916, 17934, 18003, 18013, 18014, 18029, 18030, 18363, 18407, 18599, 18840, 22828, 23336, 23353, 23404, 23485, 23528, 23558, 23607, 23618, 23620, 23622, 23632, 23668, 23679, 23725, 23761, 23786, 23807, 24117, 24124, 24225, 24229, 24952, 26202, 26434, 27013, 27015, 27178, 27766, 27982, 28931, 29427, 29428, 29843, 29851, 29878, 29879, 30105, 30108, 30117, 30949, 30951, 30969, 30970, 30983, 30986, 30990, 30993, 31129, 31137, 31166, 31167, 31305, 31308, 31312, 31321, 31373, 32268, 32296, 32308, 32311, 32440
- token internal commands:
 - \c_token_A_int 11486, 11523
 - __token_delimit_by_char:w . . 11420
 - __token_delimit_by_count:w . . 11420
 - __token_delimit_by_dimen:w . . 11420
 - __token_delimit_by_macro:w . . 11420
 - __token_delimit_by_muskip:w . 11420
 - __token_delimit_by_skip:w . . . 11420
 - __token_delimit_by_toks:w . . . 11420
 - __token_if_macro_p:w 11386
 - __token_if_primitive:NNw 11486
 - __token_if_primitive:Nw 11486
 - __token_if_primitive_loop:N . 11486
 - __token_if_primitive_nullfont:N 11486
 - __token_if_primitive_space:w . 11486
 - __token_if_primitive_undefined:N 11486
 - __token_tmp:w 585, 11421, 11430, 11431, 11432, 11433, 11434, 11435, 11436, 11439, 11473, 11474, 11475, 11476, 11478, 11480, 11481, 11482, 11483, 11484
- \toks 561, 11484
- \toksapp 1006, 1859

<code>\toksdef</code>	562, 23332	<code>\Umathbinpunctspacing</code>	1057, 1893
<code>\tokspre</code>	1007, 1860	<code>\Umathbinrelspacing</code>	1058, 1894
<code>\tolerance</code>	563	<code>\Umathchar</code>	1059, 1895
<code>\topmark</code>	564	<code>\Umathcharclass</code>	1060, 1896
<code>\topmarks</code>	666, 1537	<code>\Umathchardef</code>	1061, 1897
<code>\topskip</code>	565	<code>\Umathcharfam</code>	1062, 1898
<code>\tpack</code>	1008, 1861	<code>\Umathcharnum</code>	1063, 1899
<code>\tracingassigns</code>	667, 1538	<code>\Umathcharnumdef</code>	1064, 1900
<code>\tracingcommands</code>	566	<code>\Umathcharslot</code>	1065, 1901
<code>\tracingfonts</code>	1039, 1702	<code>\Umathclosebinspacing</code>	1066, 1902
<code>\tracinggroups</code>	668, 1539	<code>\Umathcloseclosespacing</code>	1067, 1903
<code>\tracingifs</code>	669, 1540	<code>\Umathcloseinnerspacing</code>	1069, 1905
<code>\tracinglostchars</code>	567	<code>\Umathcloseopenspacing</code>	1071, 1907
<code>\tracingmacros</code>	568	<code>\Umathcloseopspacing</code>	1072, 1908
<code>\tracingnesting</code>	670, 1541	<code>\Umathcloseordspacing</code>	1073, 1909
<code>\tracingonline</code>	569	<code>\Umathclosepunctspacing</code>	1074, 1910
<code>\tracingoutput</code>	570	<code>\Umathcloserelspacing</code>	1076, 1912
<code>\tracingpages</code>	571	<code>\Umathcode</code>	159, 1077, 1913
<code>\tracingparagraphs</code>	572	<code>\Umathcodenum</code>	1078, 1914
<code>\tracingrestores</code>	573	<code>\Umathconnectoroverlapmin</code> ...	1079, 1915
<code>\tracingscantokens</code>	671, 1542	<code>\Umathfractiondelsize</code>	1081, 1917
<code>\tracingstats</code>	574	<code>\Umathfractiondenomdown</code>	1082, 1918
<code>true</code>	216	<code>\Umathfractiondenomvgap</code>	1084, 1920
<code>trunc</code>	212	<code>\Umathfractionnumup</code>	1086, 1922
<code>\ttfamily</code>	31203	<code>\Umathfractionnumvgap</code>	1087, 1923
two commands:		<code>\Umathfractionrule</code>	1088, 1924
<code>\c_thirty_two</code>	32518	<code>\Umathinnerbinspacing</code>	1089, 1925
<code>\c_two_hundred_fifty_five</code>	32518	<code>\Umathinnerclosespacing</code>	1090, 1926
<code>\c_two_hundred_fifty_six</code>	32518	<code>\Umathinnerinnerspacing</code>	1092, 1928
		<code>\Umathinneropenspacing</code>	1094, 1930
		<code>\Umathinneropspacing</code>	1095, 1931
		<code>\Umathinnerordspacing</code>	1096, 1932
		<code>\Umathinnerpunctspacing</code>	1097, 1933
		<code>\Umathinnerrelspacing</code>	1099, 1935
		<code>\Umathlimitabovebgap</code>	1100, 1936
		<code>\Umathlimitabovekern</code>	1101, 1937
		<code>\Umathlimitabovevgap</code>	1102, 1938
		<code>\Umathlimitbelowbgap</code>	1103, 1939
		<code>\Umathlimitbelowkern</code>	1104, 1940
		<code>\Umathlimitbelowvgap</code>	1105, 1941
		<code>\Umathnolimitsubfactor</code>	1106, 1942
		<code>\Umathnolimitsupfactor</code>	1107, 1943
		<code>\Umathopbinspacing</code>	1108, 1944
		<code>\Umathopclosespacing</code>	1109, 1945
		<code>\Umathopenbinspacing</code>	1110, 1946
		<code>\Umathopenclosespacing</code>	1111, 1947
		<code>\Umathopeninnerspacing</code>	1112, 1948
		<code>\Umathopenopenspacing</code>	1113, 1949
		<code>\Umathopenopspacing</code>	1114, 1950
		<code>\Umathopenordspacing</code>	1115, 1951
		<code>\Umathopenpunctspacing</code>	1116, 1952
		<code>\Umathopenrelspacing</code>	1117, 1953
		<code>\Umathoperatorsize</code>	1118, 1954
		<code>\Umathopinnerspacing</code>	1119, 1955
U			
<code>\u</code>	xxii, 1003, 29521, 31356, 31437, 31438, 31453, 31454, 31463, 31464, 31477, 31478, 31479, 31505, 31506, 31531, 31532		
<code>\uccode</code> ..	168, 183, 196, 198, 200, 202, 575		
<code>\Uchar</code>	1041, 1877		
<code>\Ucharcat</code>	1042, 1878		
<code>\uchyph</code>	576		
<code>\ucs</code>	1275, 2090		
<code>\Udelcode</code>	1043, 1879		
<code>\Udelcodenum</code>	1044, 1880		
<code>\Udelimiter</code>	1045, 1881		
<code>\Udelimiterover</code>	1046, 1882		
<code>\Udelimiterunder</code>	1047, 1883		
<code>\Uhexensible</code>	1048, 1884		
<code>\Umathaccent</code>	1049, 1885		
<code>\Umathaxis</code>	1050, 1886		
<code>\Umathbinbinspacing</code>	1051, 1887		
<code>\Umathbinclosespacing</code>	1052, 1888		
<code>\Umathbininnerspacing</code>	1053, 1889		
<code>\Umathbinopenspacing</code>	1054, 1890		
<code>\Umathbinopspacing</code>	1055, 1891		
<code>\Umathbinordspacing</code>	1056, 1892		

- `\Umathopopenspacing` 1120, 1956
- `\Umathopopspacing` 1121, 1957
- `\Umathopordspacing` 1122, 1958
- `\Umathoppunctspacing` 1123, 1959
- `\Umathoprelspacing` 1124, 1960
- `\Umathordbinspacing` 1125, 1961
- `\Umathordclosespacing` 1126, 1962
- `\Umathordinnerspacing` 1127, 1963
- `\Umathordopenspacing` 1128, 1964
- `\Umathordopspacing` 1129, 1965
- `\Umathordordspacing` 1130, 1966
- `\Umathordpunctspacing` 1131, 1967
- `\Umathordreldspacing` 1132, 1968
- `\Umathoverbarkern` 1133, 1969
- `\Umathoverbarrule` 1134, 1970
- `\Umathoverbarvgap` 1135, 1971
- `\Umathoverdelimiterbgap` 1136, 1972
- `\Umathoverdelimitervgap` 1138, 1974
- `\Umathpunctbinspacing` 1140, 1976
- `\Umathpunctclosespacing` 1141, 1977
- `\Umathpunctinnerspacing` 1143, 1979
- `\Umathpunctopenspacing` 1145, 1981
- `\Umathpunctopspacing` 1146, 1982
- `\Umathpunctordspacing` 1147, 1983
- `\Umathpunctpunctspacing` 1148, 1984
- `\Umathpunctrelspacing` 1150, 1985
- `\Umathquad` 1151, 1986
- `\Umathradicaldegreeafter` 1152, 1987
- `\Umathradicaldegreebefore` ... 1154, 1989
- `\Umathradicaldegreeraise` 1156, 1991
- `\Umathradicalkern` 1158, 1993
- `\Umathradicalrule` 1159, 1994
- `\Umathradicalvgap` 1160, 1995
- `\Umathrelbinspacing` 1161, 1996
- `\Umathrelclosespacing` 1162, 1997
- `\Umathrelinnerspacing` 1163, 1998
- `\Umathrelopenspacing` 1164, 1999
- `\Umathrelopspacing` 1165, 2000
- `\Umathrelordspacing` 1166, 2001
- `\Umathrelpunctspacing` 1167, 2002
- `\Umathrelrelspacing` 1168, 2003
- `\Umathskewedfractionhgap` 1169, 2004
- `\Umathskewedfractionvgap` 1171, 2006
- `\Umathspaceafterscript` 1173, 2008
- `\Umathstackdenomdown` 1174, 2009
- `\Umathstacknumup` 1175, 2010
- `\Umathstackvgap` 1176, 2011
- `\Umathsubshiftdown` 1177, 2012
- `\Umathsubshiftdrop` 1178, 2013
- `\Umathsubsupshiftdown` 1179, 2014
- `\Umathsubsupvgap` 1180, 2015
- `\Umathsubtopmax` 1181, 2016
- `\Umathsupbottommin` 1182, 2017
- `\Umathsupshiftdrop` 1183, 2018
- `\Umathsupshiftup` 1184, 2019
- `\Umathsupsubbottommax` 1185, 2020
- `\Umathunderbarkern` 1186, 2021
- `\Umathunderbarrule` 1187, 2022
- `\Umathunderbarvgap` 1188, 2023
- `\Umathunderdelimiterbgap` 1189, 2024
- `\Umathunderdelimitervgap` 1191, 2026
- undefine commands:
 - `.undefine:` 188, 15800
- `\underline` 577
- `\unexpanded` 672, 1543, 3389, 3413
- `\unhbox` 578
- `\unhcopy` 579
- `\uniformdeviate` 1040, 1703
- `\unkern` 580
- `\unless` 673, 1544
- `\Unosubscript` 1193, 2028
- `\Unosuperscript` 1194, 2029
- `\unpenalty` 581
- `\unskip` 582
- `\unvbox` 583
- `\unvcopy` 584
- `\Uoverdelimiter` 1195, 2030
- `\uppercase` 585
- `\upshape` 31209
- uptex commands:
 - `\uptex_disablecjktoken:D` 2084
 - `\uptex_enablecjktoken:D` 2085
 - `\uptex_forcecjktoken:D` 2086
 - `\uptex_kchar:D` 2087
 - `\uptex_kchardef:D` 2088
 - `\uptex_kuten:D` 2089
 - `\uptex_ucs:D` 2090
 - `\uptex_uptexrevision:D` 2091
 - `\uptex_uptexversion:D` 2092
- `\uptexrevision` 1276, 2091
- `\uptexversion` 1277, 2092
- `\Uradical` 1196, 2031
- `\Uroot` 1197, 2032
- use commands:
 - `\use:N` 16, 102, 329, 2192, 2340, 2431, 2544, 2546, 2548, 2550, 5896, 8910, 9346, 9356, 9461, 9465, 9467, 9469, 9470, 9474, 9665, 9687, 12183, 12193, 12196, 12394, 12416, 12433, 12440, 12494, 13544, 14088, 14201, 14693, 15401, 15408, 15635, 16194, 16195, 24429, 26185, 26324, 28983, 29937, 30062, 30082, 30109, 30119, 30186, 30189, 30213, 30215, 30252, 30275, 30296, 30318, 30511, 30519, 30520, 30539, 30554, 30556, 30650, 31223, 31224

`\use:n` 19, 20, 20, 43, 140,
 323, 372, 391, 501, 564, 628, 765,
 933, 944, 1022, 1061, 2193, 2199,
 2201, 2204, 2273, 2290, 2316, 2376,
 2385, 2402, 2648, 2725, 2870, 3118,
 3542, 3591, 3728, 3759, 3845, 4193,
 4765, 4780, 5060, 5358, 5418, 5445,
 5453, 5543, 5564, 5578, 6248, 8555,
 9871, 9878, 10636, 11022, 11304,
 11386, 11423, 11441, 11487, 12064,
 12327, 12344, 12621, 12638, 12989,
 13175, 13267, 13366, 14030, 14259,
 14888, 15182, 15233, 15808, 15859,
 15901, 15920, 16153, 16174, 16997,
 17005, 17014, 17031, 17039, 17067,
 17533, 19078, 23776, 23974, 24390,
 24393, 24519, 25051, 25285, 25343,
 25422, 25802, 25867, 25907, 25987,
 26710, 26727, 27173, 28191, 29323,
 29324, 29326, 29985, 30049, 30681,
 30700, 30936, 31197, 31232, 31749
`\use:nn` 19,
 2204, 2951, 4418, 4479, 6031, 10008,
 10620, 11211, 13901, 14689, 17564,
 17573, 17577, 20998, 22873, 23744,
 29406, 31762, 31764, 31769, 31771
`\use:nnn` . 19, 2204, 2702, 11217, 32559
`\use:nnnn` 19, 2204
`\use_i:nn` . . . 19, 322, 327, 328, 329,
 384, 599, 605, 886, 889, 903, 907,
 908, 2144, 2208, 2258, 2334, 2356,
 2494, 2522, 2681, 3400, 3430, 3443,
 3488, 3762, 3833, 4182, 4482, 4983,
 6546, 6551, 6632, 6636, 8171, 8173,
 8547, 8574, 9873, 11844, 12057,
 14433, 16706, 17342, 17533, 18906,
 19242, 19537, 20025, 20308, 20827,
 20993, 21306, 21316, 21320, 21828,
 22033, 22594, 22619, 23159, 23214,
 23224, 23234, 23560, 24350, 24361,
 24370, 24373, 24382, 31914, 32216
`\use_i:nnn` 19, 453, 2210, 2881,
 3867, 6017, 6554, 7058, 8420, 9522,
 17501, 19494, 20968, 22807, 26233
`\use_i:nnnn` 19, 314, 534, 535, 2210,
 9660, 9662, 9676, 9681, 9697, 9699,
 19076, 19512, 19519, 19712, 22605
`\use_i_delimit_by_q_nil:nw` . 21, 2222
`\use_i_delimit_by_q_recursion_-`
`stop:nw` 21, 2222, 3981, 3997
`\use_i_delimit_by_q_recursion_-`
`stop:w` 40, 40
`\use_i_delimit_by_q_stop:nw` 21, 2222
`\use_i_ii:nnn` . 20, 328, 329, 2210,
 2325, 2977, 4211, 8396, 8501, 12025
`\use_ii:nn`
 . 19, 112, 322, 327, 384, 599, 801,
 806, 886, 889, 903, 907, 908, 919,
 1007, 1466, 1471, 2146, 2208, 2260,
 2358, 2377, 2393, 2496, 2524, 2679,
 2905, 3402, 3445, 3490, 4184, 4431,
 4985, 9879, 11845, 14429, 16907,
 16930, 17344, 18717, 18906, 18907,
 19539, 20829, 21312, 21318, 21322,
 21830, 22035, 22465, 22596, 23562,
 24352, 24358, 24363, 24375, 24384,
 24881, 25003, 25174, 25362, 32227
`\use_ii:nnn` . 19, 330, 2210, 2393, 2890
`\use_ii:nnnn` . 19, 534, 535, 2210, 9676
`\use_ii_i:nn` 20, 442, 2218, 6036, 6121
`\use_iii:nnn` 19, 2210, 2899, 2910, 16712
`\use_iii:nnnn` 19,
 534, 535, 2210, 9676, 9698, 9700, 9701
`\use_iv:nnnn`
 19, 534, 535, 2210, 9676, 9696, 18705
`\use_none:n` 20,
 385, 397, 406, 406, 461, 557, 560,
 610, 644, 762, 763, 766, 766, 802,
 808, 960, 1467, 1473, 2226, 2324,
 2376, 2377, 2650, 2706, 3290, 3421,
 3800, 3801, 3983, 3998, 4122, 4138,
 4208, 4465, 4544, 4566, 4681, 4892,
 4982, 4999, 5063, 5080, 5090, 5091,
 5096, 5111, 5114, 5203, 5212, 5972,
 5995, 6011, 6023, 6056, 6189, 6239,
 6490, 6500, 6538, 6600, 6764, 6846,
 6951, 7123, 8069, 8405, 9216, 9222,
 9512, 9872, 9877, 10067, 10247,
 10291, 10388, 10483, 10510, 10549,
 11536, 12252, 12460, 12686, 12690,
 13517, 13572, 13628, 13964, 15504,
 16094, 16207, 16462, 16701, 16850,
 16854, 16858, 16862, 18164, 18417,
 18424, 18441, 18460, 18483, 18551,
 18592, 18717, 18732, 18753, 18754,
 18968, 18969, 19513, 19516, 20496,
 22189, 22474, 23558, 23607, 23705,
 23743, 23976, 24238, 24396, 25048,
 31177, 31229, 31854, 31855, 32641
`\use_none:nn`
 20, 396, 401, 411, 411, 498, 2226,
 2306, 2314, 2385, 3899, 4527, 4671,
 4844, 5010, 5027, 6080, 6411, 8243,
 8427, 9655, 10216, 10524, 13573,
 13617, 16766, 16849, 16853, 16857,
 16861, 22184, 25610, 26246, 31178
`\use_none:nnn` . 20, 412, 2226, 3667,
 3682, 4111, 5051, 13574, 16848,

16852, 16856, 16860, 17501, 23774	\utex_delcode:D	1879
\use_none:nnnn	\utex_delcodenum:D	1880
..... 20, 2226, 13575, 14820, 31180	\utex_delimiter:D	1881
\use_none:nnnnn	\utex_delimiterover:D	1882
..... 20, 325, 646, 748, 2226, 13576, 13586, 16992, 17026, 17052, 17060, 19102	\utex_delimiterunder:D	1883
\use_none:nnnnnn	\utex_fractiondelsize:D	1917
..... 20, 2226, 2438, 13577, 32105	\utex_fractiondenomdown:D	1919
\use_none:nnnnnnn	\utex_fractiondenomvgap:D	1921
..... 20, 748, 2226, 16994, 17028, 17054, 17062, 17385, 19553	\utex_fractionnumup:D	1922
\use_none:nnnnnnnn	\utex_fractionnumvgap:D	1923
..... 20, 329, 2226, 2347, 3748	\utex_fractionrule:D	1924
\use_none:nnnnnnnnn	\utex_hextensible:D	1884
..... 20, 2226	\utex_innerbinspacing:D	1925
\use_none_delimit_by_q_nil:w	\utex_innerclosespacing:D	1927
21, 2219	\utex_innerinnerspacing:D	1929
\use_none_delimit_by_q_recursion_stop:w	\utex_inneropenspacing:D	1930
..... 21, 40, 40, 327, 2219, 3975, 3990	\utex_inneropspacing:D	1931
\use_none_delimit_by_q_stop:w	\utex_innerordspacing:D	1932
..... 21, 386, 461, 2219	\utex_innerpunctspacing:D	1934
\use_none_delimit_by_s_stop:w	\utex_innerrelspacing:D	1935
..... 42, 42, 4256	\utex_limitabovebgap:D	1936
\useboxresource	\utex_limitabovekern:D	1937
1033, 1696	\utex_limitabovevgap:D	1938
\usefont	\utex_limitbelowbgap:D	1939
31180	\utex_limitbelowkern:D	1940
\useimageresource	\utex_limitbelowvgap:D	1941
1034, 1697	\utex_mathaccent:D	1885
\Uskewed	\utex_mathaxis:D	1886
1198, 2033	\utex_mathchar:D	1895
\Uskewedwithdelims	\utex_mathcharclass:D	1896
1199, 2034	\utex_mathchardef:D	1897
\Ustack	\utex_mathcharfam:D	1898
1200, 2035	\utex_mathcharnum:D	1899
\Ustartdisplaymath	\utex_mathcharnumdef:D	1900
1201, 2036	\utex_mathcharslot:D	1901
\Ustartmath	\utex_mathcode:D	1913
1202, 2037	\utex_mathcodenum:D	1914
\Ustopdisplaymath	\utex_nolimitsubfactor:D	1942
1203, 2038	\utex_nolimitsupfactor:D	1943
\Ustopmath	\utex_nosubscript:D	2028
1204, 2039	\utex_nosuperscript:D	2029
\Usubscript	\utex_opbinspacing:D	1944
1205, 2040	\utex_opclosespacing:D	1945
\Usuperscript	\utex_openbinspacing:D	1946
1206, 2041	\utex_openclosespacing:D	1947
utex commands:	\utex_openinnerspacing:D	1948
\utex_binbinspacing:D	\utex_openopenspacing:D	1949
1887	\utex_openopspacing:D	1950
\utex_binclosespacing:D	\utex_openordspacing:D	1951
1888	\utex_openpunctspacing:D	1952
\utex_bininnerspacing:D	\utex_openrelspacing:D	1953
1889	\utex_operatorsize:D	1954
\utex_binopenspacing:D	\utex_opinnerspacing:D	1955
1890	\utex_opopenspacing:D	1956
\utex_binopspacing:D		
1891		
\utex_binordspacing:D		
1892		
\utex_binpunctspacing:D		
1893		
\utex_binrelspacing:D		
1894		
\utex_char:D		
1877		
\utex_charcat:D		
1878		
\utex_closebinspacing:D		
1902		
\utex_closeclosespacing:D		
1904		
\utex_closeinnerspacing:D		
1906		
\utex_closeopenspacing:D		
1907		
\utex_closeopspacing:D		
1908		
\utex_closeordspacing:D		
1909		
\utex_closepunctspacing:D		
1911		
\utex_closerelspacing:D		
1912		
\utex_connectoroverlapmin:D		
1916		

<code>\utext_opsopspacing:D</code>	1957	<code>\utext_stopdisplaymath:D</code>	2038
<code>\utext_opordspacing:D</code>	1958	<code>\utext_stopmath:D</code>	2039
<code>\utext_oppunctspacing:D</code>	1959	<code>\utext_subscript:D</code>	2040
<code>\utext_oprelspacing:D</code>	1960	<code>\utext_subshiftdown:D</code>	2012
<code>\utext_ordbinspacing:D</code>	1961	<code>\utext_subshiftdrop:D</code>	2013
<code>\utext_ordclosespacing:D</code>	1962	<code>\utext_subsupshiftdown:D</code>	2014
<code>\utext_ordinnerspacing:D</code>	1963	<code>\utext_subsupvgap:D</code>	2015
<code>\utext_ordopenspacing:D</code>	1964	<code>\utext_subtopmax:D</code>	2016
<code>\utext_ordopspacing:D</code>	1965	<code>\utext_supbottommin:D</code>	2017
<code>\utext_ordordspacing:D</code>	1966	<code>\utext_superscript:D</code>	2041
<code>\utext_ordpunctspacing:D</code>	1967	<code>\utext_supshiftdrop:D</code>	2018
<code>\utext_ordrelspacing:D</code>	1968	<code>\utext_supshiftup:D</code>	2019
<code>\utext_overbarkern:D</code>	1969	<code>\utext_supsubbottommax:D</code>	2020
<code>\utext_overbarrule:D</code>	1970	<code>\utext_underbarkern:D</code>	2021
<code>\utext_overbarvgap:D</code>	1971	<code>\utext_underbarrule:D</code>	2022
<code>\utext_overdelimter:D</code>	2030	<code>\utext_underbarvgap:D</code>	2023
<code>\utext_overdelimterbgap:D</code>	1973	<code>\utext_underdelimter:D</code>	2042
<code>\utext_overdelimtervlgap:D</code>	1975	<code>\utext_underdelimterbgap:D</code> ...	2025
<code>\utext_punctbinspacing:D</code>	1976	<code>\utext_underdelimtervlgap:D</code> ...	2027
<code>\utext_punctclosespacing:D</code>	1978	<code>\utext_vextensible:D</code>	2043
<code>\utext_punctinnerspacing:D</code>	1980	<code>\Uunderdelimter</code>	1207, 2042
<code>\utext_punctopenspacing:D</code>	1981	<code>\Uvextensible</code>	1208, 2043
<code>\utext_punctopspacing:D</code>	1982		
<code>\utext_punctordspacing:D</code>	1983		
<code>\utext_punctpunctspacing:D</code>	1984		
<code>\utext_punctrelspacing:D</code>	1985		
<code>\utext_quad:D</code>	1986		
<code>\utext_radical:D</code>	2031		
<code>\utext_radicaldegreeafter:D</code> ...	1988		
<code>\utext_radicaldegreebefore:D</code> ..	1990		
<code>\utext_radicaldegreeraise:D</code> ...	1992		
<code>\utext_radicalkern:D</code>	1993		
<code>\utext_radicalrule:D</code>	1994		
<code>\utext_radicalvgap:D</code>	1995		
<code>\utext_relbinspacing:D</code>	1996		
<code>\utext_relclosespacing:D</code>	1997		
<code>\utext_relinnerspacing:D</code>	1998		
<code>\utext_reloppspacing:D</code>	1999		
<code>\utext_relopspacing:D</code>	2000		
<code>\utext_relordspacing:D</code>	2001		
<code>\utext_relpunctspacing:D</code>	2002		
<code>\utext_relrelspacing:D</code>	2003		
<code>\utext_root:D</code>	2032		
<code>\utext_skewed:D</code>	2033		
<code>\utext_skewedfractionhgap:D</code> ...	2005		
<code>\utext_skewedfractionvgap:D</code> ...	2007		
<code>\utext_skewedwithdelims:D</code>	2034		
<code>\utext_spaceafterscript:D</code>	2008		
<code>\utext_stack:D</code>	2035		
<code>\utext_stackdenomdown:D</code>	2009		
<code>\utext_stacknumup:D</code>	2010		
<code>\utext_stackvgap:D</code>	2011		
<code>\utext_startdisplaymath:D</code>	2036		
<code>\utext_startmath:D</code>	2037		

- \vbox_set_top:Nn 240, 27286, 27852, 27922
- \vbox_to_ht:nn 240, 27264
- \vbox_to_zero:n 240, 27264
- \vbox_top:n 240, 27260
- \vbox_unpack:N 241, 27345, 27852, 27922
- \vbox_unpack_clear:N 32513
- \vbox_unpack_drop:N 242, 27345, 32513, 32515
- \vcenter 590
- vcoffin commands:
 - \vcoffin_gset:Nnn 247, 27826
 - \vcoffin_gset:Nnw 247, 27894
 - \vcoffin_gset_end: 247, 27894
 - \vcoffin_set:Nnn 247, 27826
 - \vcoffin_set:Nnw 247, 27894
 - \vcoffin_set_end: 247, 27894
- \vfi 1267
- \vfil 591
- \vfill 592
- \vfildneg 593
- \vfuzz 594
- \voffset 595
- \vpack 1009, 1862
- \vrule 596
- \vsize 597
- \vskip 598
- \vsplit 599
- \vss 600
- \vtop 601

- W**
- \wd 602
- \widowpenalties 674, 1545
- \widowpenalty 603
- \write 604

- X**
- \xdef 605
- xetex commands:
 - \xetex_charclass:D 1706
 - \xetex_charglyph:D 1707
 - \xetex_countfeatures:D 1708
 - \xetex_countglyphs:D 1709
 - \xetex_countselectors:D 1710
 - \xetex_countvariations:D 1711
 - \xetex_dashbreakstate:D 1713
 - \xetex_defaultencoding:D 1712
 - \xetex_featurecode:D 1714
 - \xetex_featurename:D 1715
 - \xetex_findfeaturebyname:D 1717
 - \xetex_findselectorbyname:D 1719
 - \xetex_findvariationbyname:D 1721
 - \xetex_firstfontchar:D 1722
 - \xetex_fonttype:D 1723
 - \xetex_generateactualtext:D 1725
 - \xetex_glyph:D 1726
 - \xetex_glyphbounds:D 1727
 - \xetex_glyphindex:D 1728
 - \xetex_glyphname:D 1729
 - \xetex_if_engine:TF 32432, 32434, 32436
 - \xetex_if_engine_p: 32430
 - \xetex_inputencoding:D 1730
 - \xetex_inputnormalization:D 1732
 - \xetex_interchartokenstate:D 1734
 - \xetex_interchartoks:D 1735
 - \xetex_isdefaultselector:D 1737
 - \xetex_isexclusivefeature:D 1739
 - \xetex_lastfontchar:D 1740
 - \xetex_linebreaklocale:D 1742
 - \xetex_linebreakpenalty:D 1743
 - \xetex_linebreakskip:D 1741
 - \xetex_OTcountfeatures:D 1744
 - \xetex_OTcountlanguages:D 1745
 - \xetex_OTcountscripts:D 1746
 - \xetex_OTfeaturetag:D 1747
 - \xetex_OTlanguagetag:D 1748
 - \xetex_OTscripttag:D 1749
 - \xetex_pdffile:D 1750
 - \xetex_pdfpagecount:D 1751
 - \xetex_picfile:D 1752
 - \xetex_selectorname:D 1753
 - \xetex_suppressfontnotfounderror:D 1705
 - \xetex_tracingfonts:D 1754
 - \xetex_upwardsmode:D 1755
 - \xetex_useglyphmetrics:D 1756
 - \xetex_variation:D 1757
 - \xetex_variationdefault:D 1758
 - \xetex_variationmax:D 1759
 - \xetex_variationmin:D 1760
 - \xetex_variationname:D 1761
 - \xetex_XeTeXrevision:D 1762
 - \xetex_XeTeXversion:D 1763
 - \XeTeXcharclass 817, 1706
 - \XeTeXcharglyph 818, 1707
 - \XeTeXcountfeatures 819, 1708
 - \XeTeXcountglyphs 820, 1709
 - \XeTeXcountselectors 821, 1710
 - \XeTeXcountvariations 822, 1711
 - \XeTeXdashbreakstate 824, 1713
 - \XeTeXdefaultencoding 823, 1712
 - \XeTeXfeaturecode 825, 1714
 - \XeTeXfeaturename 826, 1715
 - \XeTeXfindfeaturebyname 827, 1716
 - \XeTeXfindselectorbyname 829, 1718
 - \XeTeXfindvariationbyname 831, 1720

<code>\XeTeXfirstfontchar</code>	833, 1722	<code>\XeTeXpdffile</code>	861, 1750
<code>\XeTeXfonttype</code>	834, 1723	<code>\XeTeXpdfpagecount</code>	862, 1751
<code>\XeTeXgenerateactualtext</code>	835, 1724	<code>\XeTeXpicfile</code>	863, 1752
<code>\XeTeXglyph</code>	837, 1726	<code>\XeTeXrevision</code>	864, 1762
<code>\XeTeXglyphbounds</code>	838, 1727	<code>\XeTeXselectorname</code>	865, 1753
<code>\XeTeXglyphindex</code>	839, 1728	<code>\XeTeXtracingfonts</code>	866, 1754
<code>\XeTeXglyphname</code>	840, 1729	<code>\XeTeXupwardsmode</code>	867, 1755
<code>\XeTeXinputencoding</code>	841, 1730	<code>\XeTeXuseglyphmetrics</code>	868, 1756
<code>\XeTeXinputnormalization</code>	842, 1731	<code>\XeTeXvariation</code>	869, 1757
<code>\XeTeXinterchartokenstate</code>	844, 1733	<code>\XeTeXvariationdefault</code>	870, 1758
<code>\XeTeXinterchartoks</code>	846, 1735	<code>\XeTeXvariationmax</code>	871, 1759
<code>\XeTeXisdefaultselector</code>	847, 1736	<code>\XeTeXvariationmin</code>	872, 1760
<code>\XeTeXisexclusivefeature</code>	849, 1738	<code>\XeTeXvariationname</code>	873, 1761
<code>\XeTeXlastfontchar</code>	851, 1740	<code>\XeTeXversion</code>	874, 1763
<code>\XeTeXlinebreaklocale</code>	853, 1742	<code>\xkanjiskip</code>	1263, 2080
<code>\XeTeXlinebreakpenalty</code>	854, 1743	<code>\xleaders</code>	606
<code>\XeTeXlinebreakskip</code>	852, 1741	<code>\xspaceskip</code>	607
<code>\XeTeXOTcountfeatures</code>	855, 1744	<code>\xspcode</code>	1264, 2081
<code>\XeTeXOTcountlanguages</code>	856, 1745		
<code>\XeTeXOTcountscripts</code>	857, 1746		
		Y	
<code>\XeTeXOTfeaturetag</code>	858, 1747	<code>\ybaselineshift</code>	1265, 2082
<code>\XeTeXOTlanguagetag</code>	859, 1748	<code>\year</code>	608, 1423, 10082
<code>\XeTeXOTscripttag</code>	860, 1749	<code>\yoko</code>	1266, 2083