

Lwarp

L^AT_EX HTML⁵

The lwarp package

L^AT_EX to HTML

v0.905 — 2022/03/22

© 2016–2022 Brian Dunn
bd@BDTechConcepts.com

Abstract

The `lwarp` package converts L^AT_EX to HTML by using L^AT_EX to process the user's document and directly generate HTML tags. External utility programs are only used for the final conversion of text and images. Math may be represented by SVG images or MATHJAX. More than 500 L^AT_EX packages and classes are supported, of which more than 90 also support MATHJAX.

Documents may be produced by DVI or PDF L^AT_EX, LuaL^AT_EX, XeL^AT_EX; by several CJK engines, classes, and packages; or by customized systems such as `pertex` and `pythontex`. A `texlua` script automates compilation, index, glossary, and batch image processing, and also supports `latexmk`. Configuration is semi-automatic at the first manual compile. Support files are self-generated. Print and HTML versions of each document may coexist.

Assistance is provided for HTML import into EPUB conversion software and word processors.

Requirements include the commonly-available POPPLER utilities (included with M^IK^TE^X) and PERL. Detailed installation instructions are included for each of the major operating systems and T_EX distributions.

A quick-start tutorial is provided, as well as extensive documentation for special cases, a general index, and a troubleshooting index. Automatic error testing is provided for configuration files, package load order, and image generation.

SVG math and many other generated images include L^AT_EX expressions in the alt tags. MATHJAX may be used with advanced equation numbering under the direct control of `lwarp`.

Complicated tables are supported, which copy/paste well into LIBREOFFICE WRITER.

Supported classes and packages include `memoir` and `koma-script`, `cleveref`, `caption`, `mdframed`, `siunitx`, and many popular packages for tabulars, floats, graphics, theorems, the title page, bibliography, indexing, footnotes, and editorial work, as well as a number of CJK-related classes and packages.

T_EX is a self-modifying tokenized macro-expansion language. Since `lwarp` is written directly in L^AT_EX, it is able to interpret the document's meaning at a deeper level than external conversions which merely approximate T_EX. HTML5 and CSS3 are leveraged to provide advanced features such as `booktabs trim`, `multicolumns`, `side-by-side minipages`, and JAVASCRIPT-free navigation.

[For a quick-start tutorial, see section 5, Tutorial.](#)

[For a list of supported features, see table 2: Supported packages and features.](#)

[To update existing projects, see section 1: Updates.](#)

Lwarp is still in development. Changes are likely.

License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

Support T_EX development

T_EX and related projects:

- are mostly open-sourced and a volunteer effort;
- benefit students, academics, scientists, engineers, and businesses;
- help drive education, public and private research, and commercial activity;
- are used in the fields of mathematics, science, engineering, and humanities;
- are international in reach;
- span decades of development;
- are enduring — many older packages are still actively used and maintained;
- are largely backwards compatible;
- are portable across all the major computing platforms;
- are usable even on older computers and away from internet access;
- are continuing to maintain relevance with modern improvements;
- require no yearly subscription fees;
- and are supported by an active community of knowledgeable volunteers.

Please consider helping by joining and/or contributing to the T_EX Users Group, a United States 501(c)(3) tax-exempt charitable organization. Contributions are accepted by credit card, check, or Pay Pal, via the United Way, or by USA or European bank transfer. Membership in TUG supports the development of T_EXLive, the major T_EX distribution.

Donations may be directed towards individual projects:

TUG Bursary Fund: Assistance for attending annual TUG meetings.

CTAN: The Comprehensive T_EX Archive Network — Central storage for T_EX.

TeX Development Fund: Support for specific projects.

EduTeX: Teaching and using T_EX in schools and universities.

GUST e-foundry fonts: Enhanced for math and additional language groups.

LaTeX Project: Modernizing the L^AT_EX core.

Libre Font Fund: Fonts, tools (FontForge), and distribution (the Open Font Library).

LuaTeX: Combining the PDF T_EX engine and the Lua language.

MetaPost: Postscript graphics.

MacTeX: T_EX for Mac.

PDF Accessibility: Modern PDF standards.

Other: Additional projects may be specified.

To make a contribution: <https://www.tug.org/donate.html>

For country-specific T_EX users groups: <http://tug.org/usergroups.html>

For users of MiK_TE_X: <https://miktex.org/donations.html>

Contents

Support T_EX development	2
List of Figures	42
List of Tables	42
1 Updates	43
2 Introduction	63
2.1 Typesetting conventions	65
2.2 Supported packages and features	66
3 Alternatives	72
3.1 internet class	72
3.2 T _E X4HT	72
3.3 Translators	72
3.4 ASCIIDOC and ASCIIDOCTOR	73
3.4.1 ASCIIDOCTOR-L ^A T _E X	73
3.5 PANDOC	73
3.6 Word processors	73
3.7 Commercial systems	73
3.8 Comparisons	73
4 Installation	75
4.1 Installing the lwarp package	77
4.2 Installing the <i>lwarpmk</i> utility	78
4.2.1 Using a local copy of <i>lwarpmk</i>	79
4.3 Installing additional utilities	80
5 Tutorial	82
5.1 Starting a new project	82
5.2 Compiling the print version with <i>lwarpmk</i>	86
5.3 Compiling the HTML version with <i>lwarpmk</i>	87
5.4 Generating the SVG images	88
5.5 Using MATHJAX for math	89
5.6 Changing the CSS style	90
5.7 Customizing the HTML output	90

5.8	Using <i>latexmk</i>	91
5.9	Using X _Y L ^A T _E X or LuaL ^A T _E X.	92
5.10	Using DVI L ^A T _E X	92
5.11	Using a glossary	93
5.11.1	gloss package	93
5.11.2	glossaries package	93
5.12	Cleaning auxiliary files	94
5.13	Cleaning auxiliary and output files	94
5.14	Cleaning the images from the <project>-images directory	94
5.15	Converting PDF or EPS images to SVG	94
5.16	Creating HTML from an incomplete compile	94
5.17	Processing multiple projects in the same directory	94
5.18	Using the <i>make</i> utility	95
5.19	What next?	96
6	Converting an existing document	97
7	Additional details	98
7.1	Localization.	98
7.2	Accessibility.	98
7.3	Shell escape.	100
7.4	Font and UTF-8 support	100
7.4.1	Indexes, glossaries, and encoding	101
7.5	lwarp package loading and options.	102
7.6	Customizing the HTML output	107
7.6.1	Example HTML file naming	113
7.7	Customizing the CSS	113
7.8	Assigning CSS classes and styles	114
7.9	Selecting the operating system	115
7.10	Selecting actions for print, HTML, or MATHJAX output	115
7.11	Commands to be placed into the warpprint environment	116
7.12	Title page	117
7.13	HTML page meta descriptions	118

7.14	HTML homepage meta title	118
7.15	HTML page meta author	118
8	Special cases and limitations	119
8.1	Things to avoid	119
8.1.1	Invalid HTML	119
8.2	Formatting	120
8.2.1	Text formatting	120
8.2.2	Small caps	120
8.2.3	Horizontal and vertical space and rules	120
8.2.4	Text alignment	121
8.2.5	Accents.	121
8.2.6	textcomp package	121
8.2.7	Superscripts and other non-math uses of math mode	121
8.2.8	Empty \item followed by a new line of text or a nested list:	121
8.2.9	Filenames and URLs in lists or footnotes	121
8.2.10	resize package	122
8.3	Boxes and minipages	122
8.3.1	Marginpars	122
8.3.2	Save Boxes	122
8.3.3	Minipages.	122
8.3.4	Side-by-side minipages	123
8.3.5	Framed minipages and other environments	123
8.3.6	fancybox package	124
8.3.7	mdframed package	125
8.3.8	tcolorbox package	126
8.4	Section names	126
8.5	Cross-references	127
8.5.1	Page references	128
8.5.2	cleveref and varioref packages.	128
8.5.3	Hyperlinks, hyperref, and url	128
8.5.4	Footnotes, endnotes, and page notes	129

8.5.5	xr, xr-hyper, and xcite packages	130
8.6	Front and back matter	130
8.6.1	Custom classes with multiple authors and affiliations	130
8.6.2	Starred chapters and sections	130
8.6.3	abstract package	131
8.6.4	titling and authblk	131
8.6.5	tocloft package	131
8.6.6	appendix package	132
8.6.7	pagenote package	132
8.6.8	endnotes package	132
8.6.9	BibTeX	132
8.6.10	xcite package	132
8.6.11	gloss package	132
8.6.12	glossaries package	133
8.6.13	nomencl package	134
8.6.14	Indexing overview	134
8.6.15	Indexing with makeidx, makeindex, xindy, xindex, gindex	134
8.6.16	Indexing with index	136
8.6.17	Indexing with splitidx	136
8.6.18	Indexing with imakeidx	138
8.6.19	Indexes with memoir	141
8.6.20	Using a custom makeindex style file	143
8.6.21	Using a custom xindy style file	144
8.6.22	Using a custom xindex style file	145
8.6.23	Additional indexing limitations	146
8.6.24	Index positions, TOC, tocibind	146
8.7	Math	147
8.7.1	Math in section names	147
8.7.2	Rendering tradeoffs	147
8.7.3	svg option	148
8.7.4	MATHJAX option	148

8.7.5	MATHJAX rendering options	149
8.7.6	Customizing MATHJAX	149
8.7.7	MATHJAX limitations	150
8.7.8	Catcode changes	151
8.7.9	Complicated inline math objects	152
8.7.10	Complicated display math objects	152
8.7.11	Theorems	152
8.7.12	ntheorem package	153
8.7.13	mathtools package	153
8.7.14	siunitx package	153
8.7.15	units and nicefrac packages	155
8.7.16	physics package	155
8.8	Graphics	155
8.8.1	tikz package	157
8.8.2	grffile package	157
8.8.3	color package	158
8.8.4	xcolor package	158
8.8.5	epstopdf package	158
8.8.6	pstricks package	158
8.8.7	pdftricks package	158
8.8.8	psfrag package	159
8.8.9	pstool package	159
8.8.10	asymptote package	159
8.8.11	overpic package	159
8.8.12	Multimedia packages	160
8.9	Tabbing	160
8.10	Tabular	161
8.10.1	tabular environment	161
8.10.2	multirow package	163
8.10.3	longtable package	164
8.10.4	threeparttablex package	165

8.10.5	supertabular and xtab packages	165
8.10.6	colortbl package	165
8.10.7	ctable package	165
8.10.8	bigdelim package	166
8.11	Floats	166
8.11.1	Float contents alignment	166
8.11.2	float, trivfloat, and/or algorithmicx together	166
8.11.3	caption and subcaption packages.	166
8.11.4	subfig package	167
8.11.5	floatrow package	167
8.11.6	keyfloat package	168
8.12	KOMA-SCRIPT classes.	168
8.13	MEMOIR class	168
8.14	International languages.	170
8.15	Miscellaneous packages	170
8.15.1	verse and memoir	170
8.15.2	newclude package	170
8.15.3	babel package	171
8.15.4	polyglossia package	171
8.15.5	todonotes and luatodonotes packages	171
8.15.6	fixme	171
8.15.7	acro package	172
8.15.8	chemfig package	172
8.15.9	chemformula package	172
8.15.10	mhchem package	172
8.15.11	kotex package	172
9	Compiling using custom shell commands	173
9.1	Command options	173
9.2	Literal character macros	173
9.3	latexmk	174
9.4	perltex package	175

9.5	<code>pythontex</code> package	175
9.6	<code>sympytex</code> package	175
9.7	Other packages	176
9.8	<code>make</code> program	176
9.9	UTF-8 locale.	176
10	EPUB conversion	178
11	Word-processor conversion	180
11.1	Activating word-processor conversion	180
11.2	Additional modifications	181
11.3	Recommendations	183
11.4	Limitations	184
12	Modifying lwarp	185
12.1	Creating a development system	185
12.2	Modifying a package for <code>lwarp</code>	187
12.2.1	Adding a package to the <code>lwarp.dtx</code> file	187
12.3	Modifying a class for <code>lwarp</code>	188
12.4	Testing <code>lwarp</code>	188
12.5	Modifying <code>lwarpmk</code>	189
13	Troubleshooting	190
13.1	<code>lwarp</code> package error conditions and warnings	190
13.1.1	Configuration file <code>lwarpmk.conf</code>	190
13.1.2	Image generation with <code>lwarpmk</code> <code>limages</code>	190
13.1.3	Default bitmapped font	191
13.1.4	Packages	191
13.1.5	Compiling.	191
13.2	Using the <code>lwarp</code> package	192
13.2.1	Debug tracing output.	196
13.3	Compiling the <code>lwarp.dtx</code> file.	196
14	Trademarks	197
1	<code>lwarp.sty</code>	198
15	Implementation.	198

16	Section depths and HTML headings.	199
17	Source code	200
18	Detecting the T_EX engine — <i>pdf_latex, lua_latex, xel_latex</i>.	201
19	Early package requirements	201
20	Package load order	201
20.1	Tests of package load order	202
20.2	Error for disallowed packages and classes loaded before <i>lwarp</i>	205
20.3	Enforcing package loading after <i>lwarp</i> .	207
21	MD5 hashing.	217
22	PDF L_AT_EX T₁ and UTF-8 encoding	218
23	Unicode input characters	218
24	Avoid a bitmapped font	219
25	Upright quotes	219
26	Avoid bad font combinations	220
27	Miscellaneous tools	220
27.1	Variables	220
27.2	Lengths and units.	220
27.3	Counters	221
27.4	Patching macros	221
27.5	Copying macros	221
27.6	Chinese text isolation	222
27.7	Inserting vertical space	222
27.8	Argument selection	222
27.9	Inside boxes.	223
27.10	Global boxes	223
27.11	Converting a macro name to a cs name	224
27.12	Title case.	224
27.13	LetLtxMacros	224
27.14	Absorbing a star	224
28	Operating-System portability.	225
28.1	Literal characters	225

28.2	Common portability code	226
28.3	UNIX, LINUX, and MAC OS	226
28.4	MS-WINDOWS	226
29	Package options.	227
29.1	Additional options support	231
29.2	Conditional compilation	233
30	Required packages.	235
31	Loading packages	241
32	File handles	246
33	Include a file	247
34	Copying a file.	248
35	Debugging messages	248
36	Defining print and HTML versions of macros and environments	249
37	HTML-conversion output modifications	254
37.1	User-level controls	254
37.2	Heading adjustments	255
38	Remembering original formatting macros	257
39	Accents	258
40	Configuration files.	260
40.1	Decide whether to generate configuration files	260
40.2	<project>.html.tex	260
40.3	lwarpmk configuration files	261
40.3.1	Helper macros	261
40.3.2	lwarpmk.conf	266
40.3.3	<project>.lwarpmkconf.	267
40.4	lwarp.css	267
40.5	lwarp_sagebrush.css	297
40.6	lwarp_formal.css	301
40.7	sample_project.css	305
40.8	lwarp.ist	305
40.9	lwarp.xdy	306

40.10	<code>lwarp_one_limage.cmd</code>	306
40.11	<code>lwarp_mathjax.txt</code>	307
40.12	<code>lwarpmk.lua</code> — <code>lwarpmk</code> option	311
41	Stacks	328
41.1	Assigning depths	328
41.2	Closing actions.	329
41.3	Closing depths.	329
41.4	Pushing and popping the stack	330
42	Data arrays	331
43	Localizing catcodes	332
44	Localizing dynamic math	334
45	HTML entities.	334
46	HTML filename generation	336
47	Homepage link	339
48	Previous/next navigation links	340
49	<code>\LWRPrintStack</code> diagnostic tool	341
50	Closing stack levels	342
51	PDF pages and styles	343
52	HTML tags, spans, divs, elements.	344
52.1	Mapping L ^A T _E X sections to HTML sections	344
52.2	Hook while processing tags	344
52.3	Babel-French tag modifications	344
52.4	HTML output formatting	346
52.5	HTML tags	346
52.6	Block tags and comments	348
52.7	Div class and element class	349
52.8	Single-line elements	351
52.9	HTML5 semantic elements	351
52.10	High-level block and inline classes	351
52.11	Closing HTML tags	353

53	Paragraph handling	354
53.1	Paragraph Hooks	358
54	Paragraph start/stop handling	358
55	Indentfirst.	360
56	Page headers and footers	360
57	CSS	361
58	MATHJAX script	361
59	Title, HTML meta author, HTML meta description.	362
60	Footnotes	363
60.1	Regular page footnotes	364
60.2	Minipage footnotes	364
60.3	Titlepage thanks	364
60.4	Regular page footnote implementation	364
60.5	Minipage footnote implementation	367
60.6	Printing pending footnotes	368
61	Marginpars	369
62	Tracking internal cross references	370
63	Splitting HTML files	372
63.1	Sanitizing expressions for HTML	376
63.2	Customizing MATHJAX	379
64	Sectioning.	386
64.1	User-level starred section commands	386
64.2	Book class commands	387
64.3	Sectioning support macros	387
64.4	Pre- and post- sectioning names	395
64.5	\section and friends	395
65	Starting a new file	397
66	Starting HTML output.	401
67	Ending HTML output	404
68	Nullifying foreground/background hooks	406

69	Title page	406
69.1	Setting the title, etc.	407
69.2	<code>\if@titlepage</code> .	408
69.3	Changes for <code>\affiliation</code>	408
69.4	Printing the thanks	409
69.5	Printing the title, etc. in HTML	409
69.6	Printing the title, etc. in print form.	410
69.7	<code>\maketitle</code> for HTML output	411
69.8	<code>\published</code> and <code>\subtitle</code>	414
70	Abstract.	415
71	Quote and verse.	415
71.1	Attributions	415
71.2	Quotes, quotations	416
71.3	Verse	416
71.3.1	\LaTeX core verse environment.	417
71.3.2	verse and memoir	417
72	Verbatim and tabbing	418
73	Theorems	421
74	Lists	422
74.1	List environment	423
74.2	Itemize	426
74.3	Enumerate	427
74.4	Description	427
74.5	Patching the lists	428
75	Tabular	429
75.1	Limitations	429
75.2	Temporary package-related macros	431
75.2.1	<code>arydshln</code>	431
75.3	Token lookahead	432
75.4	Tabular variables	432
75.4.1	Multicolumn variables	436

75.4.2	Longtable variables	436
75.4.3	Midrule variables	436
75.5	Handling &, @, !, and bar	436
75.5.1	Handling &	438
75.6	Filling an unfinished row	439
75.7	Handling \\	440
75.8	Looking ahead in the column specifications	441
75.9	Parsing @, >, <, !, bar columns	442
75.10	Parsing common column types	447
75.11	Parsing 'w' columns	447
75.12	Parsing '*' columns	447
75.13	Expanding the star column specifications	447
75.14	Parsing the column specifications	448
75.15	colortbl and xcolor tabular color support.	454
75.16	Starting a new row	455
75.17	Printing vertical bar tags	456
75.18	Printing @ or ! tags	456
75.19	Cell opening tag	457
75.20	Midrules	459
75.21	Cell colors	464
75.22	Multicolumns	467
75.22.1	Parsing multicolumns	467
75.22.2	Multicolumn factored code.	470
75.22.3	Multicolumn	473
75.22.4	Longtable captions	474
75.22.5	Counting HTML tabular columns	476
75.23	Multirow if not loaded	477
75.24	Multicolumnrow	477
75.25	Utility macros inside a table	479
75.26	Special-case tabular markers	479
75.27	Checking for a new table cell	480

75.28	<code>\mrowcell</code>	483
75.29	<code>\mcolrowcell</code>	483
75.30	HTML tabular environment	483
76	Cross-references	490
76.1	Setup	490
76.2	New lwarp labels.	490
76.3	Labels	493
76.4	References	495
76.5	Hyper-references	499
77	Floats	503
77.1	Float environment	503
77.2	Float tracking	505
77.3	Caption inside a float environment	507
77.4	Caption and LOF linking and tracking	508
78	Table of Contents, LOF, LOT	511
78.1	Reading and printing the TOC	511
78.2	TOC commands	514
78.3	Side TOC	515
78.4	Low-level TOC line formatting	516
79	Index and glossary	519
80	Bibliography presentation	527
81	Restoring original formatting	528
82	Nullifying filename formatting	530
83	Math	533
83.1	Limitations	533
83.2	HTML alt tag names	533
83.3	Inline and display math	534
83.4	MATHJAX support	547
83.5	Equation environment	550
83.6	<code>\displaymathnormal</code> and <code>\displaymathother</code>	553

83.7	AMS Math environments	555
83.7.1	Support macros	555
83.7.2	Environment patches	555
84	Lateximages	558
84.1	Description	558
84.2	Support counters and macros	559
84.3	Font size	559
84.4	Equation numbers	560
84.5	HTML alt tags	561
84.6	lateximage environment	561
85	center, flushleft, flushright	568
86	Preloaded packages	569
87	siunitx	571
88	Graphics print-mode modifications	573
88.1	General limitations	573
88.2	Print-mode modifications	575
89	xcolor boxes	575
90	chemmacros environments.	578
91	cleveref	579
92	Preexisting label and reference definitions	579
93	picture environment.	580
94	Minipages and Boxes	580
94.1	Computed lengths	581
94.2	Virtual page size	581
94.3	Footnote handling	581
94.4	Minipage handling	582
94.5	\parbox, \mbox, \makebox, \framebox, \fbox, \raisebox	585
95	Direct formatting	591
96	Skips, spaces, font sizes	601
97	\phantomsection	608
98	\LaTeX and other logos	609

99	Starting and stopping lwarp	612
100	Loading array.	612
101	Loading everyshi patches	612
102	Loading textcomp patches	613
103	Loading amsmath, amsthm patches, centernot.	613
104	Loading KOMA-SCRIPT class patches	613
105	Loading MEMOIR class patches	614
106	ut* class patches	614
107	CT_EX patches.	615
108	kotexutf patches.	616
109	babel and polyglossia warnings	616
110	MATHJAX warnings.	617
2	lwarp-2in1.sty	621
3	lwarp-2up.sty	621
4	lwarp-a4.sty	621
5	lwarp-a4wide.sty	621
6	lwarp-a5comb.sty	622
7	lwarp-abstract.sty	622
8	lwarp-academicons.sty	624
9	lwarp-accents.sty	625
10	lwarp-accessibility.sty	626
11	lwarp-accsupp.sty	626
12	lwarp-acro.sty	627
13	lwarp-acronym.sty	629
14	lwarp-adjmulticol.sty	632
15	lwarp-addlines.sty	632
16	lwarp-afterpage.sty	633
17	lwarp-algorithm2e.sty	633
18	lwarp-algorithmicx.sty	637
19	lwarp-alltt.sty	637

20	lwarp-amscdx.sty	638
21	lwarp-amsmath.sty	639
22	lwarp-amsthm.sty	642
23	lwarp-anonchap.sty	647
24	lwarp-anysize.sty	647
25	lwarp-appendix.sty	648
26	lwarp-ar.sty	648
27	lwarp-arabicfront.sty	650
28	lwarp-array.sty	650
29	lwarp-arydshln.sty	651
30	lwarp-asymptote.sty	652
31	lwarp-atbegshi.sty	653
32	lwarp-attachfile.sty	654
33	lwarp-attachfile2.sty	655
34	lwarp-authblk.sty	657
35	lwarp-autobreak.sty	658
36	lwarp-autonum.sty	658
37	lwarp-awesomebox.sty	659
38	lwarp-axessibility.sty	660
39	lwarp-axodraw2.sty	661
40	lwarp-backnaur.sty	661
41	lwarp-backref.sty	662
42	lwarp-balance.sty	662
43	lwarp-bbding.sty	663
44	lwarp-beamerarticle.sty	667
45	lwarp-biblatex.sty	669
46	lwarp-bibunits.sty	673
47	lwarp-bigdelim.sty	673
48	lwarp-bigfoot.sty	675

49	lwarp-bigstrut.sty	675
50	lwarp-bitpattern.sty	676
51	lwarp-blowup.sty	676
52	lwarp-bm.sty	676
53	lwarp-booklet.sty	677
54	lwarp-bookmark.sty	677
55	lwarp-booktabs.sty	678
56	lwarp-bophook.sty	680
57	lwarp-bounddvi.sty	680
58	lwarp-boxedminipage.sty	680
59	lwarp-boxedminipage2e.sty	680
60	lwarp-braket.sty	681
61	lwarp-breakurl.sty	681
62	lwarp-breqn.sty	681
63	lwarp-bsheaders.sty	683
64	lwarp-bussproofs.sty	683
65	lwarp-bxpapersize.sty	684
66	lwarp-bytefield.sty	684
67	lwarp-cancel.sty	684
68	lwarp-canonicleayout.sty	685
69	lwarp-caption.sty	685
70	lwarp-caption3.sty	687
71	lwarp-cases.sty	690
72	lwarp-ccicons.sty	690
73	lwarp-centerlastline.sty	691
74	lwarp-centernot.sty	691
75	lwarp-changebar.sty	691
76	lwarp-changelayout.sty	692
77	lwarp-changepage.sty	692

78	lwarp-changes.sty	693
79	lwarp-chappg.sty	697
80	lwarp-chapterbib.sty	698
81	lwarp-chemfig.sty	698
82	lwarp-chemformula.sty	700
83	lwarp-chemgreek.sty	705
84	lwarp-chemmacros.sty	705
193	chemmacros	705
193.1	Changes to the user's document.	706
193.2	Code	706
193.3	Loading packages.	706
193.4	Loading modules	707
193.5	New environments	707
193.6	Acid-base	707
193.7	Charges	709
193.8	Nomenclature	709
193.9	Particles	711
193.10	Phases.	712
193.11	Mechanisms	712
193.12	Newman	714
193.13	Orbital	715
193.14	Reactions	715
193.15	Reactants	716
193.16	Redox	719
193.17	Scheme	719
193.18	Spectroscopy	720
193.19	Thermodynamics	723
85	lwarp-chemnum.sty	725
86	lwarp-chkfloat.sty	726
87	lwarp-chngpage.sty	726

88	lwarp-cite.sty	726
89	lwarp-citeref.sty	727
90	lwarp-CJK.sty	727
91	lwarp-CJKutf8.sty	728
92	lwarp-classicthesis.sty	728
93	lwarp-cleveref.sty	729
94	lwarp-clrdblpg.sty	732
95	lwarp-cmbright.sty	732
96	lwarp-cmdtrack.sty	733
97	lwarp-colonequals.sty	733
98	lwarp-color.sty	734
99	lwarp-colortbl.sty	734
100	lwarp-continue.sty	736
101	lwarp-copyrightbox.sty	736
102	lwarp-crop.sty	737
103	lwarp-ctable.sty	737
104	lwarp-cuted.sty	740
105	lwarp-cutwin.sty	740
106	lwarp-dblfloatfix.sty	741
107	lwarp-dblfnote.sty	741
108	lwarp-dcolumn.sty	741
109	lwarp-decimal.sty	742
110	lwarp-decorule.sty	742
111	lwarp-diagbox.sty	742
112	lwarp-dingbat.sty	744
113	lwarp-DotArrow.sty	745
114	lwarp-dotlessi.sty	745
115	lwarp-dprogress.sty	746
116	lwarp-draftcopy.sty	746

117	lwarp-draftfigure.sty	746
118	lwarp-draftwatermark.sty	747
119	lwarp-drftcite.sty	747
120	lwarp-easy-todo.sty	747
121	lwarp-ebook.sty	748
122	lwarp-econometrics.sty	749
123	lwarp-ed.sty	751
124	lwarp-ellipsis.sty	752
125	lwarp-embrac.sty	752
126	lwarp-emptypage.sty	753
127	lwarp-endfloat.sty	753
128	lwarp-endheads.sty	753
129	lwarp-endnotes.sty	754
130	lwarp-engtlc.sty	755
131	lwarp-enotez.sty	759
132	lwarp-enumerate.sty	761
133	lwarp-enumitem.sty	761
134	lwarp-epigraph.sty	762
135	lwarp-epsf.sty	763
136	lwarp-epsfig.sty	763
137	lwarp-epstopdf.sty	764
138	lwarp-epstopdf-base.sty	764
139	lwarp-eqlist.sty	765
140	lwarp-eqparbox.sty	765
141	lwarp-errata.sty	766
142	lwarp-eso-pic.sty	767
143	lwarp-esvect.sty	768
144	lwarp-etoc.sty	768
145	lwarp-eurosym.sty	771

146	lwarp-everypage.sty	771
147	lwarp-everyshi.sty	771
148	lwarp-extarrows.sty	772
149	lwarp-extramarks.sty	772
150	lwarp-fancybox.sty	773
151	lwarp-fancyhdr.sty	778
152	lwarp-fancypar.sty	779
153	lwarp-fancyref.sty	780
154	lwarp-fancytabs.sty	780
155	lwarp-fancyvrb.sty	781
156	lwarp-fbox.sty	787
157	lwarp-fewerfloatpages.sty	790
158	lwarp-figcaps.sty	790
159	lwarp-figsize.sty	790
160	lwarp-fitbox.sty	791
161	lwarp-fix2col.sty	791
162	lwarp-fixmath.sty	791
163	lwarp-fixme.sty	792
164	lwarp-fixmetodonotes.sty	793
165	lwarp-flafter.sty	794
166	lwarp-flippdf.sty	794
167	lwarp-float.sty	794
168	lwarp-floatflt.sty	796
169	lwarp-floatpag.sty	797
170	lwarp-floatrow.sty	797
171	lwarp-fltrace.sty	802
172	lwarp-flushend.sty	802
173	lwarp-fnbreak.sty	802
174	lwarp-fncychap.sty	803

175	lwarp-fnlineno.sty	803
176	lwarp-fnpara.sty	803
177	lwarp-fnpos.sty	804
178	lwarp-fontawesome.sty	804
179	lwarp-fontawesome5.sty	805
180	lwarp-fontaxes.sty	806
181	lwarp-fontenc.sty	806
182	lwarp-footmisc.sty	807
183	lwarp-footnote.sty	808
184	lwarp-footnotebackref.sty	809
185	lwarp-footnotehyper.sty	810
186	lwarp-footnoterange.sty	810
187	lwarp-footnpag.sty	810
188	lwarp-foreign.sty	810
189	lwarp-forest.sty	811
190	lwarp-fouridx.sty	811
191	lwarp-fourier.sty	812
192	lwarp-framed.sty	813
193	lwarp-froufrou.sty	815
194	lwarp-ftcap.sty	816
195	lwarp-ftnright.sty	816
196	lwarp-fullminipage.sty	817
197	lwarp-fullpage.sty	817
198	lwarp-fullwidth.sty	817
199	lwarp-fvextra.sty	817
200	lwarp-fwlw.sty	820
201	lwarp-gensymb.sty	821
202	lwarp-gentombow.sty	821
203	lwarp-geometry.sty	821

204	lwarp-ghsystem.sty	822
205	lwarp-gindex.sty	822
206	lwarp-gloss.sty	823
207	lwarp-glossaries.sty	824
208	lwarp-gmeometric.sty	826
209	lwarp-graphics.sty	826
318	graphics	826
318.1	Graphics extensions	826
318.2	Length conversions and graphics options	827
318.3	Printing HTML styles	830
318.4	<code>\includegraphics</code>	830
318.5	Boxes	835
210	lwarp-graphicx.sty	838
211	lwarp-grffile.sty	838
212	lwarp-grid.sty	839
213	lwarp-grid-system.sty	839
214	lwarp-gridset.sty	839
215	lwarp-hang.sty	840
216	lwarp-hanging.sty	841
217	lwarp-hepunits.sty	842
218	lwarp-hhline.sty	843
219	lwarp-hhtensor.sty	844
220	lwarp-hypbmsec.sty	844
221	lwarp-hypcap.sty	844
222	lwarp-hypdestopt.sty	845
223	lwarp-hypernat.sty	845
224	lwarp-hyperref.sty	845
225	lwarp-hyperxmp.sty	855
226	lwarp-hyphenat.sty	856

227	lwarp-idxlayout.sty	856
228	lwarp-ifoddpage.sty	857
229	lwarp-imateidx.sty	858
230	lwarp-impnatty.sty	862
231	lwarp-index.sty	862
232	lwarp-inputtrc.sty	863
233	lwarp-intopdf.sty	864
234	lwarp-isomath.sty	864
235	lwarp-isotope.sty	864
236	lwarp-jurabib.sty	866
237	lwarp-karnaugh-map.sty	867
238	lwarp-keyfloat.sty	870
239	lwarp-keystroke.sty	875
240	lwarp-kpfonts.sty	876
241	lwarp-kpfonts-otf.sty	878
242	lwarp-layaureo.sty	880
243	lwarp-layout.sty	880
244	lwarp-layouts.sty	880
245	lwarp-leading.sty	883
246	lwarp-leftidx.sty	883
247	lwarp-letterspace.sty	883
248	lwarp-lettrine.sty	883
249	lwarp-libertinustlmath.sty	884
250	lwarp-lineno.sty	890
251	lwarp-lips.sty	892
252	lwarp-lipsum.sty	893
253	lwarp-listings.sty	893
254	lwarp-listliketab.sty	899
255	lwarp-lltjext.sty	899

256	lwarp-lltjp-siunitx.sty	900
257	lwarp-lltjp-tascmac.sty	901
258	lwarp-longtable.sty	901
259	lwarp-lpic.sty	904
260	lwarp-lscape.sty	904
261	lwarp-ltablex.sty	904
262	lwarp-ltcaption.sty	905
263	lwarp-ltxgrid.sty	905
264	lwarp-ltxtable.sty	906
265	lwarp-lua-check-hyphen.sty	906
266	lwarp-lua-visual-debug.sty	906
267	lwarp-luacolor.sty	906
268	lwarp-luamplib.sty	907
269	lwarp-luatexko.sty	907
270	lwarp-luatodonotes.sty	909
271	lwarp-luavlna.sty	911
272	lwarp-lyluatex.sty	911
273	lwarp-magaz.sty	913
274	lwarp-makeidx.sty	914
275	lwarp-manyfoot.sty	914
276	lwarp-marginal.sty	916
277	lwarp-marginfit.sty	916
278	lwarp-marginfix.sty	916
279	lwarp-marginnote.sty	917
280	lwarp-marvosym.sty	917
281	lwarp-mathalpha.sty	918
282	lwarp-mathastext.sty	918
283	lwarp-mathcomp.sty	919
284	lwarp-mathdesign.sty	920

285	lwarp-mathdots.sty	921
286	lwarp-mathfixs.sty	922
287	lwarp-mathpazo.sty	922
288	lwarp-mathptmx.sty	923
289	lwarp-mathspec.sty	923
290	lwarp-mathtools.sty	925
291	lwarp-mattens.sty	928
292	lwarp-maybemath.sty	930
293	lwarp-mcaption.sty	931
294	lwarp-mdframed.sty	931
403	mdframed	931
403.1	Limitations	931
403.2	Package loading	932
403.3	Patches	932
403.4	Initial setup	932
403.5	Color and length HTML conversion	933
403.6	Environment encapsulation	933
403.7	Mdframed environment	934
403.8	Titles and subtitles	935
403.9	New environments	937
295	lwarp-mdwmath.sty	939
296	lwarp-media9.sty	940
297	lwarp-memhfixc.sty	942
298	lwarp-menukeys.sty	942
299	lwarp-metalogo.sty	943
300	lwarp-metalogox.sty	943
301	lwarp-mhchem.sty	944
302	lwarp-microtype.sty	946
303	lwarp-midfloat.sty	947

304	lwarp-midpage.sty	948
305	lwarp-minibox.sty	948
306	lwarp-minitoc.sty	949
307	lwarp-minted.sty	949
308	lwarp-mismath.sty	950
309	lwarp-mleftright.sty	953
310	lwarp-morefloats.sty	954
311	lwarp-moreverb.sty	954
312	lwarp-movie15.sty	955
313	lwarp-mparhack.sty	956
314	lwarp-multibib.sty	957
315	lwarp-multicap.sty	957
316	lwarp-multicol.sty	957
317	lwarp-multicolrule.sty	958
318	lwarp-multimedia.sty	959
319	lwarp-multiobjective.sty	960
320	lwarp-multirow.sty	960
321	lwarp-multitoc.sty	964
322	lwarp-musicography.sty	964
323	lwarp-mwe.sty	967
324	lwarp-nameauth.sty	968
325	lwarp-nameref.sty	969
326	lwarp-natbib.sty	969
327	lwarp-nccfancyhdr.sty	970
328	lwarp-nccfoots.sty	971
329	lwarp-nccmath.sty	971
330	lwarp-needspace.sty	973
331	lwarp-newpxmath.sty	973
332	lwarp-newtxmath.sty	974

333	lwarp-newtxsf.sty	975
334	lwarp-nextpage.sty	976
335	lwarp-nfssect-cfr.sty	976
336	lwarp-nicefrac.sty	982
337	lwarp-niceframe.sty	983
338	lwarp-nicematrix.sty	983
339	lwarp-noitcru.sty	986
340	lwarp-nolbreaks.sty	986
341	lwarp-nomencl.sty	986
342	lwarp-nonfloat.sty	987
343	lwarp-nonumonpart.sty	987
344	lwarp-nopageno.sty	987
345	lwarp-notes.sty	987
346	lwarp-notespages.sty	988
347	lwarp-nowidow.sty	988
348	lwarp-ntheorem.sty	989
457	ntheorem	989
457.1	Limitations	989
457.2	Options	989
457.3	Remembering the theorem style	990
457.4	HTML cross-referencing	993
457.5	<code>\newtheoremstyle</code>	993
457.6	Standard styles	994
457.7	Additional objects	995
457.8	Renewed standard configuration	995
457.9	<code>amsthm</code> option	996
457.10	Ending a theorem	998
457.11	<code>\NoEndMark</code>	999
457.12	List-of	999
457.13	Symbols	999

457.14	Cross-referencing	1000
349	lwarp-octave.sty	1000
350	lwarp-orcidlink.sty	1001
351	lwarp-overpic.sty	1002
352	lwarp-pagegrid.sty	1002
353	lwarp-pagenote.sty	1002
354	lwarp-pagesel.sty	1003
355	lwarp-paralist.sty	1003
356	lwarp-parallel.sty	1004
357	lwarp-parcolumns.sty	1005
358	lwarp-parnotes.sty	1007
359	lwarp-parskip.sty	1009
360	lwarp-pbalance.sty	1010
361	lwarp-pbox.sty	1010
362	lwarp-pdfcol.sty	1010
363	lwarp-pdfcolfoot.sty	1011
364	lwarp-pdfcolmk.sty	1011
365	lwarp-pdfcolparallel.sty	1011
366	lwarp-pdfcolparcolumns.sty	1012
367	lwarp-pdfcomment.sty	1012
368	lwarp-pdfcrypt.sty	1013
369	lwarp-pdflandscape.sty	1013
370	lwarp-pdfmarginpar.sty	1013
371	lwarp-pdfpages.sty	1014
372	lwarp-pdfprivacy.sty	1016
373	lwarp-pdfrender.sty	1016
374	lwarp-pdfsinc.sty	1016
375	lwarp-pdftricks.sty	1017
376	lwarp-pdfx.sty	1017

377	lwarp-perpage.sty	1018
378	lwarp-pfnote.sty	1019
379	lwarp-phfqit.sty	1019
380	lwarp-physics.sty	1020
381	lwarp-physunits.sty	1020
382	lwarp-picinpar.sty	1022
383	lwarp-pifont.sty	1023
384	lwarp-pinlabel.sty	1024
385	lwarp-placeins.sty	1024
386	lwarp-plarydshln.sty	1024
387	lwarp-plexst.sty	1024
388	lwarp-plexarydshln.sty	1025
389	lwarp-plexcolortbl.sty	1026
390	lwarp-plimsoll.sty	1026
391	lwarp-prelim2e.sty	1026
392	lwarp-prettyref.sty	1027
393	lwarp-preview.sty	1027
394	lwarp-psfrag.sty	1027
395	lwarp-psfragx.sty	1028
396	lwarp-pst-eps.sty	1028
397	lwarp-pstool.sty	1028
398	lwarp-pstricks.sty	1029
399	lwarp-pxatbegshi.sty	1030
400	lwarp-pxeveryshi.sty	1030
401	lwarp-pxfonts.sty	1030
402	lwarp-pxftnright.sty	1030
403	lwarp-pxjahyper.sty	1031
404	lwarp-quotchap.sty	1031
405	lwarp-quoting.sty	1032

406	lwarp-ragged2e.sty	1032
407	lwarp-realscripts.sty	1033
408	lwarp-refcheck.sty	1036
409	lwarp-register.sty	1036
410	lwarp-reysize.sty	1037
411	lwarp-repeatindex.sty	1038
412	lwarp-repltext.sty	1039
413	lwarp-resizegather.sty	1039
414	lwarp-returntograd.sty	1040
415	lwarp-rlepsz.sty	1040
416	lwarp-rmathbr.sty	1040
417	lwarp-rmpage.sty	1041
418	lwarp-romanbar.sty	1041
419	lwarp-romanbarpagenumber.sty	1041
420	lwarp-rotating.sty	1041
421	lwarp-rotfloat.sty	1042
422	lwarp-rviewport.sty	1043
423	lwarp-savetrees.sty	1043
424	lwarp-scalefont.sty	1043
425	lwarp-scalerel.sty	1044
426	lwarp-schemata.sty	1044
427	lwarp-scrextend.sty	1045
428	lwarp-scrhack.sty	1048
429	lwarp-scrlyer.sty	1049
430	lwarp-scrlyer-notecolumn.sty	1050
431	lwarp-scrlyer-scrpage.sty	1050
432	lwarp-scrpage2.sty	1052
433	lwarp-section.sty	1053
434	lwarp-sectionbreak.sty	1053

435	lwarp-sectsty.sty	1054
436	lwarp-selectp.sty	1054
437	lwarp-semantic-markup.sty	1055
438	lwarp-seqsplitt.sty	1056
439	lwarp-setspace.sty	1057
440	lwarp-shadethm.sty	1058
441	lwarp-shadow.sty	1058
442	lwarp-shapepar.sty	1058
443	lwarp-showidx.sty	1059
444	lwarp-showkeys.sty	1059
445	lwarp-showlabels.sty	1059
446	lwarp-showtags.sty	1060
447	lwarp-shuffle.sty	1060
448	lwarp-sidecap.sty	1061
449	lwarp-sidenotes.sty	1061
450	lwarp-simplebnf.sty	1063
451	lwarp-Slunits.sty	1064
452	lwarp-siunitx.sty	1072
453	lwarp-siunitx-v2.sty	1080
454	lwarp-common-mathjax-siunitx.sty	1091
455	lwarp-skmath.sty	1100
456	lwarp-slantsc.sty	1105
457	lwarp-slashed.sty	1105
458	lwarp-soul.sty	1106
459	lwarp-soulpos.sty	1107
460	lwarp-soulutf8.sty	1108
461	lwarp-splitbib.sty	1108
462	lwarp-splitidx.sty	1109
463	lwarp-srcltx.sty	1110

464	lwarp-srctex.sty	1111
465	lwarp-stabular.sty	1111
466	lwarp-stackengine.sty	1111
467	lwarp-stackrel.sty	1113
468	lwarp-statex2.sty	1114
469	lwarp-statistics.sty	1117
470	lwarp-statmath.sty	1123
471	lwarp-steinmetz.sty	1124
472	lwarp-stfloats.sty	1125
473	lwarp-struktex.sty	1125
474	lwarp-subcaption.sty	1126
475	lwarp-subfig.sty	1126
476	lwarp-subfigure.sty	1130
477	lwarp-subsupscripts.sty	1131
478	lwarp-supertabular.sty	1132
479	lwarp-svg.sty	1133
480	lwarp-swfigure.sty	1134
481	lwarp-sympytex.sty	1134
482	lwarp-syntonly.sty	1135
483	lwarp-tabfigures.sty	1135
484	lwarp-tablefootnote.sty	1135
485	lwarp-tables.sty	1136
486	lwarp-tabularx.sty	1136
487	lwarp-tabulary.sty	1136
488	lwarp-tagpdf.sty	1137
489	lwarp-tascmac.sty	1140
490	lwarp-tcolorbox.sty	1142
491	lwarp-tensor.sty	1147
492	lwarp-termcal.sty	1148

493	lwarp-textarea.sty	1149
494	lwarp-textcomp.sty	1149
495	lwarp-textfit.sty	1153
496	lwarp-textpos.sty	1153
497	lwarp-theorem.sty	1154
498	lwarp-thinsp.sty	1157
499	lwarp-thm-listof.sty	1158
500	lwarp-thm-restate.sty	1158
501	lwarp-thmbox.sty	1159
502	lwarp-thmtools.sty	1159
503	lwarp-threadcol.sty	1160
504	lwarp-threeparttable.sty	1160
505	lwarp-threeparttablex.sty	1161
506	lwarp-thumb.sty	1162
507	lwarp-thumbs.sty	1162
508	lwarp-tikz.sty	1162
509	lwarp-tikz-imagelabels.sty	1164
510	lwarp-titleps.sty	1164
511	lwarp-titleref.sty	1167
512	lwarp-titlesec.sty	1167
513	lwarp-titletoc.sty	1169
514	lwarp-titling.sty	1170
515	lwarp-tocbasic.sty	1175
516	lwarp-tocbibind.sty	1175
517	lwarp-tocdata.sty	1177
518	lwarp-tocenter.sty	1178
519	lwarp-tocloft.sty	1178
520	lwarp-tocstyle.sty	1184
521	lwarp-todo.sty	1184

522	lwarp-todonotes.sty	1185
523	lwarp-topcapt.sty	1187
524	lwarp-tram.sty	1187
525	lwarp-transparent.sty	1187
526	lwarp-trimclip.sty	1188
527	lwarp-trivfloat.sty	1188
528	lwarp-truncate.sty	1189
529	lwarp-turnthepage.sty	1190
530	lwarp-twoup.sty	1190
531	lwarp-txfonts.sty	1190
532	lwarp-txgreeks.sty	1190
533	lwarp-typearea.sty	1191
534	lwarp-typicons.sty	1192
535	lwarp-ulem.sty	1192
536	lwarp-umoline.sty	1194
537	lwarp-underscore.sty	1194
538	lwarp-unicode-math.sty	1195
539	lwarp-units.sty	1199
540	lwarp-unitsdef.sty	1200
541	lwarp-upgreek.sty	1200
542	lwarp-upref.sty	1201
543	lwarp-url.sty	1201
544	lwarp-ushort.sty	1201
545	lwarp-ospace.sty	1202
546	lwarp-varioref.sty	1202
547	lwarp-verse.sty	1202
548	lwarp-ersonotes.sty	1204
549	lwarp-vertbars.sty	1204
550	lwarp-vmargin.sty	1205

551	lwarp-vowel.sty	1205
552	lwarp-vpe.sty	1206
553	lwarp-vwcol.sty	1206
554	lwarp-wallpaper.sty	1208
555	lwarp-watermark.sty	1208
556	lwarp-widetable.sty	1209
557	lwarp-widows-and-orphans.sty	1209
558	lwarp-witharrows.sty	1209
559	lwarp-wrapfig.sty	1210
560	lwarp-wrapfig2.sty	1212
561	lwarp-xbmks.sty	1215
562	lwarp-xcolor.sty	1215
671	xcolor	1215
671.1	Limitations	1215
671.2	xcolor definitions: location and timing	1216
671.3	Package loading	1217
671.4	Remembering and restoring original definitions	1218
671.5	\normalcolor	1218
671.6	HTML color style	1218
671.7	HTML border	1219
671.8	High-level macros	1219
671.9	Row colors	1223
563	lwarp-xexchangebar.sty	1225
564	lwarp-xellipsis.sty	1225
565	lwarp-xetexko.sty	1226
566	lwarp-xevlna.sty	1226
567	lwarp-xfakebold.sty	1226
568	lwarp-xfrac.sty	1227
569	lwarp-xltabular.sty	1229

570	lwarp-xtextra.sty	1230
571	lwarp-xmpincl.sty	1230
572	lwarp-xpiano.sty	1230
573	lwarp-xpinyin.sty	1231
574	lwarp-xr.sty	1232
575	lwarp-xr-hyper.sty	1233
576	lwarp-xtab.sty	1233
577	lwarp-xunicode.sty	1235
578	lwarp-xurl.sty	1236
579	lwarp-xy.sty	1236
580	lwarp-zhlineskip.sty	1237
581	lwarp-zwpagelayout.sty	1237
582	lwarp-patch-komascript.sty	1238
583	lwarp-patch-memoir.sty	1240
692	patch-memoir	1240
692.1	Packages	1242
692.2	Label handling	1243
692.3	Page layout	1243
692.4	Text and fonts	1246
692.5	Titles	1246
692.6	Abstracts	1247
692.7	Document divisions	1247
692.8	Pagination and headers	1250
692.9	Paragraphs and lists	1251
692.10	Contents lists	1251
692.11	Floats and captions	1255
692.12	Footnotes and page notes	1258
692.13	Decorative text	1260
692.14	Poetry	1260
692.15	Boxes, verbatims and files	1261

692.16	Cross referencing	1261
692.17	Back matter	1262
692.18	Miscellaneous	1263
692.19	ccaption emulation	1264
692.20	Final patchwork	1267
584	lwarp-common-multimedia.sty	1267
585	lwarp-common-mathjax-letters.sty	1272
586	lwarp-common-mathjax-newpctxmath.sty	1278
587	lwarp-common-mathjax-nonunicode.sty	1285
588	lwarp-common-mathjax-overlaysymbols.sty	1288
	Change History	1290
698	Chg Hist	1290
	Index of Objects	1331
	General Index	1354
	Troubleshooting Index.	1359
	Index of Indexes	1366

List of Figures

1	tutorial.tex listing	83
---	--------------------------------	----

List of Tables

1	Typesetting conventions	65
2	L ^A T _E X lwarp package — Supported features	66
3	Required software programs	76
4	Configuration files created by print version	85
5	Localization settings	98
6	Accessibilty settings	99
7	Lwarp package options	103
8	HTML settings	108
9	\includegraphics and file names	155
10	Literal character macros	174
11	Section HTML headings for word-processor conversion	183
12	Section depths and HTML headings	199
13	Tabular baseline	448
14	Tabular HTML column conversions	449
15	HTML column type internal macros	450
16	Cross-referencing data structures	491
17	Float data structures	503
18	CSS related to the sideroc	515
19	amsthm package — css styling of theorems and proofs	643
20	Ntheorem package — css styling of theorems and proofs	989
21	Theorem package — css styling of theorems and proofs	1154

1 Updates

The following is a summary of updates to `lwarp`, highlighting new features and any special changes which must be made due to improvements or modifications in `lwarp` itself.

For a detailed list of the most recent changes, see the end of the Change History on page [1330](#).

v0.905: Bug fixes, internal improvements.

- Fixed conflict between `cleveref` and `splitidx`.
- Improved coexistence with `\AtEndDocument`.
- `acronym`: Updated to v1.47, added hyper links.

v0.904a: Fixed missing `lwarp-common-mathjax-siunitx` package.

v0.904: Added `siunitx` v3.

- Fixed HTML tags inside non-Latin text.
- `MATHJAX` now defaults to SVG rendering.
- Added `siunitx` v3. Updated `siunitx-v2`. See section [8.7.14](#) for limitations.
- Updated `caption`, `chemmacros`, `fbox`, `hyperref`, `multicol`, `wrapfig2`.

v0.903: Various updates and improvements.

`lwarpmk`

core

 New images

packages

- Error if `pdftotext` not available. Ensures that `POPPLER` programs are installed.
- `ps2pdf`: Allow transparency due to recent changes in `ps2pdf`.
- Due to changes in how automatically-generated SVG image file names are computed, after `lwarpmk html` use `lwarpmk cleanimages` a single time, and then `lwarpmk images` to generate the new images.
- Improved back refs.
- Fixed `verbatim*`.
- Various internal updates for recent `LATEX` release.
- `cuted`: Updated to v2.0.
- `flushend`: Updated to v4.0.
- `mathalpha`: Updated for v1.14+.
- `minted`: Updated to v2.6.
- `cases`: Updated to v3.2.
- `siunitx` with `MATHJAX`: Improved `\per`, `\numlist`, `\SIlist`, comma decimal points.
- Added `showlabels`, `wrapfig2`.

v0.902: `beamerarticle`, footnotes, paragraph tags.

core

packages

`MATHJAX`

- Fixed footnotes inside descriptions, `minipages`, `amsthm`, `\nameref`.
- Improved various paragraph tags.
- Improved `parnotes`, `sympytex`.
- Added `beamerarticle`.
- Updated `luatexko`, `xetexko`, `tagpdf`.
- Added missing standard international text symbols for `MATHJAX`.

v0.901: Tabular columns, float caption CSS, MATHJAX packages.

- core**
 - Added warpsvg to isolate SVG math, as opposed to warpMathJax.
 - Improved float caption CSS for newer browsers.
 - Improved emulation of `\newcolumnntype`.
 - Added `\HTMLnewcolumnntype`. See section 7.6,
 - `>\centering\arraybackslash`, etc. now sets HTML CSS `text-align`. Also detects `\itshape`, `\bfseries`, and `\bfseries\itshape`. See section 8.10.1.
- MATHJAX**
 - Now uses MATHJAX 3.2 packages for `centernot`, `colortbl`, `gensymb`, `mathtools`, `textcomp`, `upgreek`.
- packages**
 - `dcolumn`: Now works inside a `lateximage`.
 - Added `mwe`.
 - Added `ltpj-tascmac`, which fixed `ascmac`.

v0.900: Package updates.

- core**
 - Fix for detecting `\usepackage{lwarp}`.
- packages**
 - `amsmath`: Fixed `alignat` with MATHJAX.
 - `changes`: Updated to v4.2.1.
 - `froufrou`: Updated to v1.4.0.
 - `lipsum`: Updated to v2.3.

v0.899: Minor updates.

- core**
 - `lwarpmk`: Warns if `\usepackage{lwarp}` is not detected.
- packages**
 - `graphics`: Added support for `keepaspectratio`.
 - `keyfloat`: Fix: `lw` with `h`.
 - `multicol`: Improved CSS.

v0.898: Minor updates.

- Fewer underfull `\hbox` warnings.
- `wrapfig`: Improved integration with `keyfloat`.

v0.897: `siunitx` rollback.

- docs**
 - Added a table of file extensions to use with `\includegraphics`. See table 9.
- core**
 - Added tests for additional incompatible packages.
- packages**
 - `siunitx`: Supports rollback to v2. Does not yet support v3.
 - `fixme`: Improved to work if the user modifies layouts.
 - `float`: Improved integration with `newfloat`, `keyfloat`.
 - Added `centerlastline`, `decorule`, `fancypar`, `froufrou`, `pbalance`.
 - Verified works as-is with `fnpct`.

v0.896: Back references, accessibility.



MATHJAX
theorems
accessibility
packages

- **Due to changes in cross referencing, execute `lwarpmk clean` before recompiling.**
- Increased sectioning nesting stack depth. Error if overflow stack.
- Fixed footnotes at the end of the document, or inside a description label.
- Added an error if using braces inside `\usepackage` options.
- Fixed footnotes in bracket display math with MATHJAX.
- L^AT_EX theorems, amsthm, ntheorem, theorem: Print theorem footnotes following theorems.
- Added HTML `<main>` element to each page.
- Added ARIA math role to SVG math images, and note role to margin notes, footnotes, etc.
- Improved citation backreferences for various packages.
- chemfig: Updated to v1.6a.
- bigdelim: Updated to v2.8.
- xetexko: Updated to v3.1.
- hyperxmp: Fix: Accept and discard additional keys.
- hyperref: Fix: Added `*autorefname` macros.
- biblatex: Fix: Back references.
- tocloft: Fix: `\cftpagenumbersoff`, `\cftpagenumberson`.
- threeparttablex: Fix: `\TPTL@tnotex`.
- amsthm: Fix: Footnotes inside environment optional argument.
- listings: Fixed labels. Accepts but ignores escapes w/o error.
- pdfscape: Fix: Added landscape environment.
- Added ccicons, classicthesis, orcidlink.
- Added enotez.
- Verified support for doi, doipubmed.

v0.895: Vector packages, greatly improved MATHJAX for siunitx.

core
MATHJAX
packages

- Fixed quotes in HTML tags while using old font packages with X_EL^AT_EX and Lua^AT_EX.
- Added `\ifblank` and `\ifstrequal` to MATHJAX emulation.
- multirow: Allow `\par` per v2.7.
- acro: Updated to v3.5.
- fancyhdr: Updated to v4.0.
- changes: Updated to v4.0.1.
- epsfig, rotating: Now work inside `lateximage`.
- amscdx: Verified to work with SVG math. Warning added about use with MATHJAX.
- Added MATHJAX emulation for isomath, mattens, maybemath, skmath, tensor.
- Improved MATHJAX emulation for siunitx `\ang`, `\num`, `\SI`.
- Added epsf, imprnatty, isotope, lpic, luavlna, mdwmath, pinlabel, rlepsz, tikz-image, xevlna.
- Verified to work as-is: tensind.

v0.894: MATHJAX additions and improvements.

- MATHJAX**
 - Improved warning message for enabling SVG graphics for select math expressions while using MATHJAX.
 - Accept and ignore a star for `\hspace`.
 - Ignores `\arabic`, `\number`, `\noalign`.
- packages**
 - Added MATHJAX emulation for `backnaur`, `colortbl`, `nicematrix`.
 - `booktabs`: MATHJAX emulation now absorbs and discards `trim`.
 - `menukeys`: Updated to v1.6.1.

v0.893: Minor fixes, more packages.

- MATHJAX**
 - Added MATHJAX emulation for `\mathnormal`.
- packages**
 - Fixed `pstricks` `pspicture*`.
 - Fixed `tikz` font macros.
 - `braket`: Now uses the MATHJAX extension.
 - Added `esvect`, `fixmath`, `keystroke`, `mathastext`, `menukeys`, `picinpar`, `plimsoll`, `repltext`, `selectp`, `seqsplit`, `simplebnf`, `statistics`, `swfigure`.
 - Added MATHJAX emulation for `mathspec`.
 - Verified to work as-is for `apxproof`, `syntaxdi`, `venndiagram`.

v0.892: `minted`, `fvextra`, MATHJAX `\left/\right`.

- MATHJAX**
 - `fourier`, `libertinustlmath`, `newpxmath`, `newtxmath`, `newtxsf`, `unicode-math`: Added MATHJAX `\left/\right` support for additional delimiters.
- packages**
 - `textpos`: Updated to v1.10.
 - `xcolor`: Fixed optional args for `\fcolorbox` and related.
 - Added `fvextra`, `minted`.

v0.891: MATHJAX additions and improvements.

- core**
 - Now displays inline `\verb` text as `\texttt`.
 - Fixed `alltt` and `verbatim` with L^AT_EX lists.
 - Now generates an error if nested each of `warpHTML`, `warpprint`, `warpMathJax` inside itself.
- MATHJAX**
 - Added MATHJAX `textmacros` extension, allowing formatting inside `\text`.
- packages**
 - `biblatex`, `hyperref`: Added back page references.
 - `fancyvrb`: Fixed `BVerbatim` with a label.
 - `listings`: Fixed MATHJAX with captions, improved HTML sanitation.
 - `babel-french`: Fixed `\texorpdfstring` conflict.
 - Now honors Greek package options for `mathdesign`, `mathpazo`, `mathptmx`, `newpxmath`, `newtxmath`.
 - Improved MATHJAX for `colonequals`, `mathdesign`, `mathdots`, `mathfixs`, `mathtools`, `multiobjective`, `nicefrac`, `shuffle`, `units`.
 - `unicode-math`: Added Greek macros, as well as macros for the first several categories listed in `texdoc unimath-symbols`. Improved symbol shape macros with Greek. Improved documentation.
 - Added `bussproofs`, `cmbright`, `fourier`, `kpfonts`, `kpfonts-otf`, `libertinustlmath`, `scalarel`, `txgreek`.

v0.89: Additional MATHJAX support.

- core**
 - Adapted to upcoming L^AT_EX kernel changes.
 - Allows load of amsmath before lwarp.
- lwarpmk**
 - Also removes *.bbl when cleaning aux files.
- MATHJAX**
 - MATHJAX: Neutralized \protect, \mathcode and related, ligatures. Fixed nested environments.
- packages**
 - caption: Updated for v3.5, fix for label sep.
 - thmtools: Updated for v0.72. Fixed swapnumber, margin.
 - Improved MATHJAX for centernot, mathtools, mismath, Slunits, siunitx, statmath.
 - Added MATHJAX emulation for accents, hepunits, hhtensor, mathalpha, mathdesign, mathpazo, mathptmx, mleftright, newpxmath, newtxmath, newtxsf, pxfonts, shuffle, txfonts, upgreek, ushort.
 - Verified to work as-is: authoraftertitle.

v0.88: Indexing, boxing, theorems.

- **Now has programmed support for more than 500 packages and classes, of which more than 60 also support MATHJAX.**
- core**
 - Fixed: \ref*, and also added MATHJAX emulation.
 - If starting a new paragraph, \hrulefill creates a <div> with a thin horizontal line across the page. Use instead of \hrule.
 - Fixed: Use \chaptername where appropriate.
 - Fixed: Inline links causing extraneous paragraphs.
- lwarpmk**
 - Added **lwarpmk -v** to print the version number.
- indexing**
 - Added the IndexRef option to control the display of index entries. See section 7.5.
 - Added \IndexPageSeparator and \IndexRangeSeparator for custom index styles.
 - Added support for gindex, xindex.
 - Verified to work as-is with varindex.
- packages**
 - cleveref, varioref: Fix for starred macros.
 - varioref: Removed page-related text from HTML output.
 - xfakebold: Updated to v0.08, using pdfrender.
 - caption, scrextend: Fixed \caption*.
 - Added fbox, shadethm, tcolorbox, termcal, thmbox, thmtools.

v0.87: MATHJAX, bibliography packages.

- core**
 - Added boolean FixSmallCaps for fonts which render small caps as all caps.
 - Fixed \bibliography to use the HTML version's .bbl file. Previously the HTML bibliography relied on the print version's .bbl, thus would fail if the print document had not yet been created.
- MATHJAX**
 - Added \ifstar and \ifnextchar to MATHJAX, and removed \DeclareIfstar. See section 8.7.6.
- Removed**
\DeclareIfstar
 - physics: Now supports the MATHJAX v3 extension.

- **mathtools**: Improved `\underbracket`, `\overbracket` for MATHJAX.
- **nccmath**: Improved `\underrel` for MATHJAX.
- **mhchem**: Now supports the MATHJAX v3 extension for `\ce` inside math.
- **cancel**: Now supports the MATHJAX v3 extension.
- **embrac**: Neutralized kerning for improved HTML conversion.
- Added `citeref`, `drftcite`, `jurabib`, `multibib`, `splitbib`.
- Verified to work as-is with `bibtopic`, `collref`, `mciteplus`.

v0.86: MATHJAX major updates.

- core**
 - Fixed: Filename if named files with `*`, parens, period in section name.
 - Fixed: Labels in `eqnarray`, `lateximage`.
- MATHJAX**
 - Updated to MATHJAX v3. New repository.
 - Fixed forward references for MATHJAX.
 - Improved MATHJAX equation number formatting, now compatible with `amsmath \numberwithin` for chapters, sections, subsections, as well as `amsmath subequations`. See section 8.7.6.
 - Added `\DeclareIfstar` to define starred T_EX macros in MATHJAX. See section 8.7.6.
 - Generates an error if `\MathJaxFilename` file does not exist.
- packages**
 - **mathtools**, **nccmath**, **physics**: Added starred macros for MATHJAX.
 - **nccmath**: Fixed `\nr`, `\displaybreak` for MATHJAX.
 - **xcolor**: Fixed `\textcolor` with `babel-french`.

v0.85: fontspec

- packages**
 - **fontspec**: Fixed core font change macros for world languages.
-  **acro formats**
 - **acro**: Due to v3 changes, when defining acronym formats, use `\textbf` instead of `\bfseries`, etc.
 - Fixed `idxlayout`, `mathtools`, `titlesec`, `url`.

v0.84: Previous/next page links, numerous fixes.

- docs**
 - Added documentation of `BlockClass` and `\InlineClass` for `css <div>s` and `s`. See section 7.8.
 - Added `\LinkPrevious`, `\LinkNext` page links. See section 7.6.
 - Added `\FirstPageBottom`. Home page no longer shares `\PageBottom`. See section 7.6.
 - Improved coexistence with `comment`, support for nested environments.
-  **home page footer changed**
- core**
 - No longer requires but still supports the `caption` package.
 - Improved filenames and HTML titles when using special characters.
- 
 - **Change**: Append `-0` to section named `Index` previously `_index` to distinguish from `index.html`
 - Fixed style tags for `\multicolumn`, `\multirow`.
 - Fixed spacing in `tabbing`.
 - Fixed `lateximage` for: `quote`, `quotation`, `verse`, `center`, `flushleft`, `flushright`, `<par>` tags, `packages verbatim`, `alltt`, `epigraph`.

- Fixed `textcomp` due to integration into L^AT_EX kernel.
 - Fixed `\itshape`, etc. Adapted to L^AT_EX fontaxes integration.
 - Fixed `\@fnsymbol`.
 - Warns about section names with dollar-delimited math.
 - Warns about a `` containing a float, caption, section, `mdframed`, or other `<div>` object.
 - Only warn about X_YT_EX logo and `graphics` if actually used `\Xe`.
 - **lwarpmk clean** also removes `comment_*.cut`.
 - `scrextend`, `scrartcl`, `scrbook`: Added `\titlehead`, `\subject`, `\subtitle`, `\publishers`.
 - `titling`: Fixed `\printthanks`.
 - `memoir`, `abstract`: Fixed for updated memoir.
 - `memoir`: Fixed `\newcomment`, `pagenotes`, `crossreferences`. Fixed setting a recursive name.
 - Fixed or improved: `amsthm`, `backref`, `biblatex`, `fixme`, `nfssect-cfr`, `ntheorem`, `parcolumns`, `realscripts`, `rotfloat`, `titling`.
 - Added `boxedminipage`, renamed from `boxedminipage2e` per author.
 - Verified to work as-is with `mcite`.
- v0.83:** memoir fixes.
- packages
- `memoir`: Various fixes and updates.
 - `physunits`: Updated to v1.0.4.
- v0.82:** MATHJAX notes, xpinyin improvements, various updates.
- MATHJAX
- Improved footnotes with MATHJAX.
 - Added MATHJAX emulation for `endnotes`, `marginnote`, `nccfoots`, `pagenote`, `parnotes`, `sidenotes`.
- packages
- `xpinyin`: Added pinyin with modern HTML.
 - `luatexko`: Added `\dotemph`, `\ruby`, `\uline`, etc.
 - `soul`: Fixed `\<`.
 - `chemfig`: Updated to v1.5.
 - `draftwatermark`: Updated to v2.0.
 - `ulem`: Fixed: `\dashuline`.
 - `amsmath`: Fixed: `\intertext` with MATHJAX.
 - `endnotes`: Fixed: Marks in print mode.
 - `tocvsec2`, `tableof`: Verified to work as-is.
 - Added `etoc` (nullified).
- v0.81:** MATHJAX speedup and additional emulations.
- core
- Improved warning regarding SVG math sizing/baselines and `graphics/graphicsx`. See section 8.7.
- MATHJAX
- Improved MATHJAX emulation processing speed.
 - Added MATHJAX emulation for `accsupp`, `axessibilty`, `colonequals`, `decimal`, `dotlessi`, `econometrics`, `engtlc`, `multiobjective`, `physunits`, `Slunits`, `stackrel`, `statmath`.

- packages**
- **axessibility**: Updated to 2020/01/08 version.
 - **gridset**: Updated to v0.3.
 - **Slunits**: Fixed for math mode.
 - Added **DotArrow**, **nolbreaks**, **luamplib**, **returntogrid**, **statex2**, **tagpdf**.
 - Verified to work as-is with **icomma**, **mathpunctspace**, **textualicomma**.
- v0.80: MATHJAX, biblatex.**
- MATHJAX**
- Added docs and warning/info messages re: avoiding slow MATHJAX compilation. See section 8.7.6, **Customizing MATHJAX**.
 - Added MATHJAX emulation for **accessibility**, **autobreak**, **centernot**, **extrarrows**, **fouridx**, **gensymb**, **leftidx**, **mathcomp**, **mathdots**, **mathfixs**, **mismatch**, **nccmath**, **noitcrul**, **pdfcomment**, **relsize**, **rmathbr**, **subsupscripts**, **xfrac**.
 - Improved MATHJAX emulation for **unicode-math**.
- packages**
- **biblatex**, **url**: Now create hyperlinks.
 - **amsmath**: Fix to center starred environments.
 - **xcolor**, **graphics**: Made more macros robust.
 - **colortbl**: Fix: Rule color in a `lateximage`.
 - **chemmacros**: Updated to v5.10.
 - Added **fewerfloatpages**, **ghsystem**, **hline**, **mismatch**, **nccmath**.
- v0.79: MATHJAX, nested tabular.**
- MATHJAX**
- Added or improved MATHJAX emulation for **amsmath**, **ar**, **arydshln**, **bm**, **bigdelim**, **bigstrut**, **booktabs**, **braket**, **mathtools**, **multirow**, **physics**, **siunitx**, **slashed**, **unicode-math**, **xfakebold**.
 - Warn if using certain packages not supported by MATHJAX.
- core**
- **tabular**: Now may be nested.
 - **minipage**, **\parbox**, **fminipage**, **\makebox**, **\framebox**: Fix: Adjust for virtual page size.
 - Uses new **iftex**.
- packages**
- **graphicx**: Fix: Negative angles.
 - **caption**: Fix: `\captionlistentry` with `longtable`.
 - **multirow**: Fix: Centered vertical alignment.
 - **siunitx**: Fix: `\square`, `\cubed`.
 - **booktabs**: Fix: `memoir` with `lateximage`.
 - **babel** and **polyglossia**: Added troubleshooting warnings.
 - **fontawesome**, **fontawesome5**: Supports text color and size.
 - **transparent**: Fix: `lateximages`.
 - **epigraph**: Updated to v1.5e.
 - **xurl**: Updated to v0.08.
 - **subcaption**: Fixed with `memoir`.
 - **floatrow**: Fix: `\linewidth`. No longer require `float`, `graphics`.
 - **floatflt**, **wrapfig**, **niceframe**: Fix: Adjust for virtual page size.
 - Added **widetable**, **witharrows**, **steinmetz**.
 - Added **awesomebox**, **catoptions**.

- Added `svg`, supports `svg-extract`.
- Added `parcolumns`, `pdfcolparcolumns`,
- Added `parallel`, `pdfcolparallel`.
- Added `pdfcol`, `pdfcolfoot`, `pdfcolmk`.

v0.78: Fixes for support files, `alt` tags, hyperlinks, and the 2019/10 L^AT_EX release.

docs

- Docs: Improved documentation regarding package options. See section 8.1.
- Fix to overwrite existing support files using new `filecontents` environment.

packages

- `breqn`: Previously broken by the 2019/10 L^AT_EX update, but now working again.
- `graphics`: Fix for `\includegraphics alt` tags.
- `babel-french`: Fix for hyperlinks.
- `media9`, `movie15`, `multimedia`: Fix for the 2019/10 L^AT_EX update.
- `accessibility`: Added.

v0.77: Updates to fix recently-broken packages.

- `booktabs`: Updated to v1.6180339.
- `chemformula`: Updated to v4.15.

v0.76: MATHJAX, updates for L^AT_EX 2019/10 release.

docs

- Docs: Expanded documentation regarding the use of multiple projects in the same directory. See section 5.17.

MATHJAX

packages

- MATHJAX: Updated to v2.7.6.
- `xr`: Updated to v5.05.
- `xr-hyper`: Updated to v6.1.
- Verified works as-is with `xcite`.
- `acro`: Updated to v2.10.

⚠ broken

- Currently broken in print mode by the 2019/10 L^AT_EX update, and waiting for fixes: `breqn`, `grffile`, `multimedia`, `movie15`.

v0.75: `keyfloat`, `wrapfig`

packages

- `\minipage`: Fix for `\linewidth`.
- `keyfloat`: Improved color control.
- `wrapfig`: Fix for `\linewidth`.

v0.74: Docs, `svg math`, `lwarpmk`, HTML `alt` and `title text`, `lyluatex`

docs

- Added to the tutorial the section **What next?**. See section 5.19.
- Added documentation about localization options. See section 7.1.
- Added documentation about accessibility options. See section 7.2.
- Renamed and updated HTML `alt` text macros:

⚠ HTML `alt` text
changed names

Old	New
(hard coded as “image”)	<code>\ImageAltText</code>
<code>\mathimagename</code>	<code>\MathImageAltText</code>
<code>\packagediagramname</code>	<code>\PackageDiagramAltText</code>

- Added `\ImageAltText` for the default HTML alt text for an image. See section 7.6.
- Added `\ThisAltText`, which may be used to assign a one-time HTML alt tag to the very next image generated by `lwarp`, such as a `lateximage`, `picture`, `tikzpicture`, an image generated by various chemistry or engineering packages, or an SVG math image. This macro also adds a title tag to a reference or hyperlink. See section 7.6.
- svg math**
 - Adjusted `\LateximageFontScale` default from .75 to 1.
 - Fix: Font control for SVG math.
- misc**
 - Fix: Ignores negative `\hspace`.
 - Warning if `SideTOCDepth < FileDepth`.
- lwarpmk**
 - **lwarpmk: `lwarpmk clean`** removes additional files.
 - **lwarpmk: `lwarpmk epstopdf` and `lwarpmk pdftosvg`** now honor directories.
- packages**
 - **lyluatex:** Split images by system or per fullpage, improved margins and scaling.
 - Tested to work as-is with `mathspec`, `unicode-math`.

v0.73: `\include`, `memoir`, `koma-script`, `caption`, `xy`, `datatool`, music scores.

- Fix for `\include`.
- Warning for a `tabular` inside a ``.
- `\color:` Added HTML support for rules and frames, but not inline text. Use `\textcolor` if possible.
- Improved many HTML tags, reducing *tidy* warnings. See Change History.
- packages**
 - **memoir:** Fixes for `\frontmatter*` and `\mainmatter*`. Added `\book`.
 - **koma-script:** Fix for starred captions in the TOC.
 - **caption:** Fix for starred captions.
 - **datatool:** Added pie, bar, and plot charts.
 - **threeparttable:** Added `measuredfigure`.
 - **intopdf:** Updated to v0.2.1.
 - **tocdata:** Updated to v2.03.
 - **quotchap:** Updated to v1.2.
 - **versonotes:** Updated to v0.4.
 - **backnaur:** Now uses SVG images. Updated to v3.1.
 - **xy:** Fix for `\xybox`, improved `xy`, also now compatible with `qcircuit`.
 - **fancyvrb:** Fix for label HTML tags.
- Added `stackengine`.
- music**
 - Added `lyluatex`. (Music scores.)
 - **musicography:** Updated to 2019/05/28. Added support for `lateximages`.

v0.72: Font control, `\multicolumn`, `xr` and `xr-hyper`.

-  **images**
 - Due to internal changes, images for inline SVG math and `lateximages` will have new hash values, and will have to be regenerated using
 - Enter ⇒ **`lwarpmk cleanimages`**
 - and
 - Enter ⇒ **`lwarpmk images`**

packages

- Docs: Color-codes package names in the table of supported packages and features, table 2, according to each package's level of support by lwarp.
- `\multicolumn`: Fix for paragraph columns.
- `xr`, `xr-hyper`: Fixes for references, `\externaldocument`.
- `soulutf8`: Fix: Loads `soul` for emulation.
- `boxedminipage2e`: Added support for `lateximages`.
- `zhlineskip`: Updated to v1.0e.
- Added `fontaxes`, `slantsc`, `tabfigures`.
- Added `nfssect-cfr`, thus supporting `cfr-lm` and several other font packages.
- Added `backnaur`, `hypbmsec`, `minibox`, `pdfcrypt`, `shapepar`.

v0.71: Error handling, multimedia, tabular.

packages

- `tabular`: Added support for '*' columns. Fix for paragraph tags.
- `quotation`: Fix for HTML tag.
- Docs: Added a section about error conditions tested by lwarp. See section 13.1.
- `lwarpmk`: If file `lwarpmk.conf` is an older version, or the incorrect operating system, displays the print command to use to recompile.
- `chemfig`: Updated for v1.4.
- `endfloat`: Updated for v2.7.
- `textpos`: Updated for v1.9.1.
- Added `media9`, `movie15`, `multimedia`.

multimedia

v0.70: Error handling, MATHJAX, mathtools.

packages

- Error handling for "Label(s) changed." Refuses to `lwarpmk limages` until recompile first.
- Fix: If Computer Modern font is used, ensures `cm-super` or `lmodern` is used.
- Fixes for `\makebox`.
- Fixes for `\parbox` inside a ``.
- `MATHJAX`: Updated to v2.7.5. Loads the `autoload-all.js` extension. Added `\MathJaxFilename` to select custom scripts.
- `textcomp`, `xunicode`: Fix for `\textinterrobang`.
- `mhchem`: Works with `MATHJAX`. See section 410.
- `changes`: Updated to v3.1.2.
- Added `autonom`, `changelayout`, `inputtrc`, `mathtools`, `metalogox`.

v0.69: Error handling, many fixes, improved keyfloat / tocdata.

packages

- Fix for HTML corruption of `lateximage` displays.
- `\makebox`, `\framebox`: Fix for `(\langle width,height \rangle)` arguments.
- `fminipage`: Honors `\minipagefullwidth`.
- `array`, `longtable`: Fix for `\tabularnewline`.
- `tabularx`, `tabulary`: Fix to require the `array` package.

- supertabular, xtab: Fix to clear caption after use.
- graphics: Added a warning if used the `\includegraphics` scale option.
- multirow: Added an error if didn't use `\mrowcell` or `\mcolrowcell` when using `\multirow` or `\multicolumnrow`.
- keyfloat: Updated for v2.00, additional improvements.
- Added ctable, eqlist, eqparbox, ftcap, listliketab, minitoc, tocdata, topcapt.

v0.68: Error handling, tabulars, footnotes.

lwarpmk

- *lwarpmk*: Improved error handling for image generation if compile was incomplete.
- tabular: Fix for `\warpprintonly`.

packages

- longtable: Improved flexibility for `\endhead`, etc. Improved error reporting if `\endhead`, etc. incorrect for *lwarp*.
- threeparttable: Fix for caption type.
- hyperref: Fix for options with braces.
- morefloats: Fix to be loaded early for print output.
- listings: Updated for v1.7.
- Added bigfoot, fnpara, footnotebackref, manyfoot, tablefootnote, threeparttablex.
- Added layouts, niceframe, perpage, showtags.
- Prevented alg, algorithmic, pdfcpot, fncylab.

v0.67: Filename generation, symbol fonts.

docs

- Documentation fix for `<project>-images`, `<project>-images.txt`.
- Added discussion regarding section names. See section 8.4.

filenames

- Added `\FilenameNullify` and `\FilenameSimplify` for filename generation. See section 8.4.
- Core, textcomp, xunicode: Nullified additional symbols during filename generation.

packages

- color: Fix for version number warnings.
- Added academicons, bbding, dingbat, eurosym, fontawesome, fontawesome5, marvosym, pifont, typicons.
- Added changes, easyReview, fitbox, foreign, gloss, karnaugh-map, multicap, nomencl, notes, struktex, umoline, xfakebold.
- Tested to work as-is with askmaps, curves, euro, karnaughmap, tikz-karnaugh.

v0.66: xr, multiple projects, image names/directory, HTML formatting

⚠ Reset the configuration

- Due to changes in *lwarpmk*, **recompile any existing project a single time** using `pdflatex filename.tex` or similar, after which *lwarpmk* may then be used with the new configuration files.

lateximage

- Adds options `ImagesDirectory` and `ImagesName` to assign directory and name prefixes for *lateximage* images. The new defaults include the `jobname`, allowing the image directories for multiple projects to coexist.

⚠ existing projects

- To reuse existing *lateximage* directories, add *lwarp* options

```
\usepackage[
  ImagesDirectory={lateximages},
  ImagesName={lateximage-}
]{lwarp}
```

- If not reused, the existing `lateximages` directory and `lateximages.txt` file may be removed.
- filenames**
 - Added `\FilenameLimit` to control the maximum length of the file-names generated by `lwarp`.
 - Possible filename changes**
 - Improved filename generation when special characters or macros are used in section names.
 - WINDOWS**
 - Fix for `lwarpmk cleanimages` with `WINDOWS`.
 - floats**
 - Fixes for floats in the home page.
 - lists, table notes**
 - Improved css for definition lists, table notes.
 - tabular**
 - `tabular`: Fixes for `\par` in column specifier, `minipage` inside `tabular`.
 - indexing**
 - Indexing: Fix for a long line of multiple entries.
 - minipage**
 - `\minipagefullwidth`: Fix for global changes.
 - Added `\UseMinipageWidths` and `\IgnoreMinipageWidths`. See section 8.3.3.
 - colors**
 - Improved `\fbox`, `\fboxBlock`, `\fminipage` to use current text color.
 - HTML**
 - Improved HTML output formatting.
 - docs**
 - Added discussion regarding invalid HTML. See section 8.1.1.
 - Added discussion regarding math in section names, `\imagegraphics scale` option. See section 6.
 - Added discussion regarding international languages in section names. See section 8.14.
 - packages**
 - `caption`: Fix for options clash.
 - `xr`, `xr-hyper`: Now compatible.
 - `subcaption`: Improved horizontal spacing.
 - `multicol`: Fix for `minipage` inside `multicols`.
 - `multicolrule`: Updated for v1.2.
 - `tocbasic`: Minor update.
 - `acronym`: Fix for acronym in float caption.
 - `kotexutf`: Patch with `pdflatex` and new `lwarp` labels.
 - `extramarks`, `fancyhdr`: Updated for v3.10.
 - `memoir`: Added docs regarding version numbers. See section 8.13.
 - `zref`: No longer required.
 - Added `ar`, `ed`, `indentfirst`, `nameauth`, `truncate`.
 - Verified to work as-is with `changelog`.
 - Prevented `colortab`, `epsf`, `hyper`, `picinpar`, `picins`, `sistyle`, `ucs`.
- v0.65:** css layout, alt tags, Japanese.
- page layout**
 - Moved the `sideroc` to the left side, allowing improved css for margin notes.
 - Improved page layout css.
 - image alt tags**
 - `graphicx \includegraphics`: Added the alt key to assign an alt tag to an image. Default is "image", assigned to pass validation.
 - duplicate HTML files**
 - Detects and causes an error if duplicate HTML file names are generated, caused by identical or similar sectioning names.
 - fixes**
 - Fix for `tabular*`.

- Fix for tabular border colors.
 - Fixes `\quad`, `\enskip`, and figure captions to pass validation.
- Japanese packages
- Added `ltj*` classes, `bounddvi`, `gentombow`, `lltjext`, `plarydshln`, `plext`, `plextarydshln`, `plextcolortbl`, `pxatbegshi`, `pxeveryshi`, `pxftnright`, `pxjahyper`, `tascmac`.
 - Verified to work with `plarray`, `plautopatch`, `plextarray`, `plextdelarray`, `pxgentombow`, `plsiunitx`, `pxpdfpages`, `pxpgfrcs`, `pxpgfmark`.
- packages
- Added support for `fontspec \textsi` and `\sishape`.
 - Added `multicol's \docolaction`.
 - Added `embrace`, `footnoterange`, `multicolrule`, `versionotes`.
- v0.64:** Koma-Script, Japanese, Chinese.
- Japanese
- Added `utarticle` and related classes.
 - Improved `ujarticle` and related classes.
- Chinese
- Fix for `biblatex` with `CTEX` and other classes.
- Koma-Script packages
- Fixes for `scrlayer`, `scrlayer-scrpage`.
 - `addlines`: Updated to v0.3.
 - Added `bsheaders`, `gmeometric`, `marginal`, `mpage`, `scrpage2`.
- v0.63:** mdframed, Chinese, Japanese, Korean
- localization
- Added `\linkhomename`: A user-definable name for the **Home** link.
 - Documented `\sidetocname`: A user-definable name for the `sidetoc`.
- fixes
- Fix: `\LinkHome` for print output.
- optimizations
- Moved package load checks to the `lwarp` core to reduce the number of `lwarp-*` files.
- packages
- `mdframed`: Fix with `amsthm`, improved titles and font control. Improved rule widths.
- Chinese
- Fixes for `xeCJK`.
 - Added `xpinyin`, `zhlineskip`.
 - Verified to work with `ckjpunct`, `upzhkinsoku`, `zhspacing`.
- Japanese
- Verified to work with `zxjatype`, `luatexja`, `luatexja-fontspec`.
 - Added `bxjsarticle` and related classes.
 - Added `ltjsarticle` and related classes.
 - Added `plATEX`, `upLATEX`, `ujarticle` and related classes.
 - Prevented `utarticle` and related classes.
 - Prevented `bxckatype`.
- Korean
- Verified to work with `kotex`, `xetexko`, `luatexko`.
- v0.62:** MiKTeX docs, HTML title, CTeX, xeCJK, bitpattern.
- docs
- Docs: Setting a UTF-8 locale. See section 9.9.
- MiKTeX
- MiKTeX: Docs for *MiKTeX Console* and `miktex-poppler-bin`.
- HTML <title>
- HTML subpage titles: Added `\HTMLTitleBeforeSection` and `\HTMLTitleAfterSection` to select whether the `HTML <title>` displays the website name before or after the section name. See section 7.6.
- fixes
- Fix for package options handling.

- Fixes for horizontal white space between `fminipage`, `fcolorminipage`, `colorboxBlock`, `fcolorboxBlock`.
 - Logos: Fix for X_YTEX logo, improved css, made robust, improved search-engine optimization.
 - `\[$1]`: Additional HTML `
` if `$1 > 0 pt`.
 - Fixes for `\includgraphics` filename, and with `FormatWP`.
 - Fix: css for `\textup`.
 - Fix: Added `\slshape`.
 - Added `ctex` package and related classes, `xeCJK`.
 - Prevented `CJK`, `CJKutf8` unless `xeCJK`, `ctex` are used.
 - `chemfig`: Docs for new macro `\polymerdelim`.
 - `asymptote`: Docs for compilation.
 - `chngepage`: Fix to load `lwarp-changeagepage`.
 - `algorithm2e`: Fix with non-book classes.
 - `register`: Updated to v1.8.
 - `nicefrac`: Improved font control and css, honors `nice` and `ugly`.
 - `units`: Improved font control and css, honors `tight` and `loose`.
 - `xfrac`: Improved css.
 - `textcomp` and `xunicode`: Fix conflicts with `\textcircled`.
 - `ulem`: Improved compatibility with `CJKulem`, `lateximage`.
 - `MATHJAX` and `siunitx`: Removed inoperable extension.
 - Added `bitpattern`, `pdfcomment`, `pdfmarginpar`, `tram`, `unitsdef`, `xexchangebar`.
 - Added `musicography`, `octave`, `semantic-markup`.
 - Added `2in1`, `flippdf`, `notespages`, `rviewport`, `twoup`.
- v0.61:** Custom compilation, EPS-related packages, documentation, indexes.
- Split index into multiple indexes.
 - Improved documentation regarding font selection. See section 7.4.
 - Added documentation regarding debugging options. See section 35.
 - Added documentation regarding HTML entities inside program listings. See section 8.2.1.
- Added options to specify the shell commands to execute for `lwarpmk print` and `lwarpmk html`, allowing the use of `lwarp` with `perltex`, `pythontex`, etc. If not specified, these are set automatically depending on the L^AT_EX engine, `--shell-escape`, and `lwarp` options. See section 9.
- ⚠ **changed names**
- | Old | New |
|--------------------------------|--------------------------------|
| <code>\StartDynamicMath</code> | <code>\inlinemathother</code> |
| <code>\StopDynamicMath</code> | <code>\inlinemathnormal</code> |
- Fix: Paragraph tags in a tabular.
 - Fix: `supertabular` and `xtab` captions.
 - Fix: DVI L^AT_EX `\includegraphics` EPS images.
 - Fix: `newfloat` lists.
 - Fix: css footnotes text align, `minipage` tabular and footnote margins.

- packages
 - Added epsfig, psfrag, psfragx, pstool.
 - Added copyrightbox, pdfprivacy, thinsp, threadcol, uspace.
 - Added chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.
- v0.60: Fixes for longtable, listings.
 - fixes
 - longtable, etc.: Fixes for slowdown and memory management for very long tables.
 - listings: Fix for HTML entities, and also when used inside a list.
 - diagbox: Fix for incorrect HTML par tags.
 - packages
 - Added 2up, booklet.
 - Added bophook, draftfigure, fullminipage, grid-system, layaureo.
 - Added leading, widows-and-orphans.
 - Added fancytabs, thumb, thumbs.
- v0.59: DVI *latex*, MATHJAX, asymptote, pdftricks and pstricks, epstopdf, brqen.
 - ⚠ Reset the configuration
 - Due to changes in *lwarpmk*, **recompile any existing project a single time** using **pdflatex filename.tex** or similar, after which *lwarpmk* may then be used with the new configuration files.
 - lwarpmk
 - Added an error if *lwarpmk.conf*'s format has changed and the document must be recompiled.
 - Added a warning if the *lwarpmk.conf* configuration file appears to be for the wrong operating system, in case files are transferred between systems.
 - Added


```
lwarpmk epstopdf <list-of-EPS-files>
```

 to quickly convert a document's EPS images to PDF or SVG. See section 8.8.
 - dvi latex
 - Added support for DVI *latex*. See section 7.5.
 - latexmk
 - Fix for `--shell-escape` with *latexmk*.
 - math
 - Updated MATHJAX script to v2.7.4.
 - Fix: MATHJAX chapter number removed from non-numeric tagged equations.
 - Added MATHJAX support for nicefrac, units.
 - Fix for `\[` and `\]` with `\displaymathnormal`.
 - images
 - Fix for `\includegraphics` filename expansion.
 - `\includegraphics` now works with `.pdf` and `.eps` filename extensions.
 - packages
 - Moved amsmath out of the *lwarp* core.
 - Fix for chemformula `\NMR`.
 - Added asymptote, pdftricks, pstricks, pst-eps.
 - Added breqn, Slunits.
 - Added bxpapersize, canoniclayout, draftcopy, fbreak, nccfancyhdr.
 - Added accsupp, axessibility.
 - Added xunicode.
 - Improved and now supports epstopdf.
 - Tested to work as-is: eepic, sepfootnotes.
 - docs
 - Added information about setting up a development version of *lwarp*.

v0.58: Extensive improvements in indexing, glossaries. Adds PDF-inclusion packages.

△ Reset the configuration

lwarpmk
glossaries

index and glossary

misc. fixes

packages

- Due to changes in *lwarpmk*, **recompile any existing project a single time** using `pdflatex filename.tex` or similar, after which *lwarpmk* may then be used with the new configuration files.
- *lwarpmk*: Added the `-p` option to specify the project name.
- *lwarpmk*: Now uses *makeglossaries* for glossary generation, allowing the processing of multiple glossaries at once.
- Added *lwarp* option `GlossaryCmd` to specify the shell command used by `lwarpmk printglossary` and `lwarpmk htmlglossary`. Defaults to `makeglossaries`.
- Docs: Extra indexing options. See section 8.6.14.
- Added support for *makeindex*. (Previously supported only *xindy*.) Also added indexing packages listed below.
- Added *lwarp* options `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to specify shell commands used by `lwarpmk printindex`, `lwarpmk htmlindex`, and *latexmk*. May be preset with the `makeindex` or `xindy lwarp` options. See section 7.5.
- Added *lwarp* options `makeindex` and `xindy` to set `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to sensible values for a typical single index. See section 7.5.
- Added *lwarp* option `makeindexStyle` to tell *lwarpmk* to use a custom style instead of `lwarp.ist`. See section 8.6.20.
- Fix for index entries with `\see`, `\seealso`, `\emph`, `\textbf`, etc.
- Replaced each `\csuse` with `\@nameuse` for improved error detection.
- Additional internal print/HTML macro selection improvements.
- Fix: `\printindex` finishes pending `\index` writes first.
- Fixes for memoir: `makeidx`, `ccaption`, multiple indexes, `\specialindex`.
- Fixes for komascript: Indexing improvements.
- Added `imakeidx`, `index`, `repeatindex`, `splitidx`.
- Added `attachfile`, `attachfile2`, `intopdf`, `pdfpages`, `pdfx`.
- Added `cases`.
- Tested to work as-is: `notes2bib`, `hvinde`.

v0.57: *algorithm2e*, float styles, tabular packages, internal improvements.

MathJax
math macros

dynamic math

△ new name

- Added support for MATHJAX equations with `\footnote`, `\footnotemark`.
- Added `\StartDefiningMath` and `\StopDefiningMath` for use when defining macros in the preamble which contain `$`. See section 8.7.8.
- Added `\inlinemathother` and `\inlinemathnormal` to delimit math expressions which depend on a variable condition such as a counter. Such expressions will not be hashed for reuse, and will be converted to SVG math images even when MATHJAX is enabled. See section 8.7.9.
- Renamed `\EndDefiningTabulars` to `\StopDefiningTabulars`.

- lateximage alt tags**
- Improved localization for lateximage HTML alt tags. For SVG math images, the alt tag under some conditions will be set to `\MathImageAltText`, which defaults to `math image`. For packages, the alt tag is set using the package name followed by `\PackageDiagramAltText`, which defaults to `diagram`. Ex:
(-xy- diagram)
See section 7.6.
- misc. fixes**
- Fix: Improved print/HTML macro selection.
 - Fix: `\href` text catcodes.
 - Fix: `\subref` text.
 - Fixes: Colored `\rule` and `\boxframe`.
- packages**
- `float, rotfloat`: Adds support for float styles `ruled` and `boxed`.
 - `float`: Fix: Do not create `\l@<type>` until `\listof` is used.
 - `marginnote`: Fix: Long optional argument.
 - `ellipsis`: Adds `\midwordellipsis`.
 - `breakurl`: Fix for text catcodes.
 - Added `algorithm2e`, `register`, `ltablex`, `xltabular`, `xellipsis`, `trimclip`, `errata`, `vowel`, `xpiano`.
 - Prevents `glossary`.
 - Tested to work as-is with `gauss`, `phonrule`, `piano`, `Slunits`, `tikzcodeblocks`.
- v0.56: Shell escape, tabular packages.**
- lwarpmk**
- Added
`lwarpmk pdftosvg <list-of-PDF-files>`
to quickly convert a document's PDF images to SVG, for use with HTML.
See section 8.8.
 - Added support for `--shell-escape`. See section 7.3.
- tabular**
- Added support for `array w` and `W` columns.
 - Fix: `\multicolumn` parameter handling.
 - Added support for double `\hlines`, `\midrules`, and vertical rules.
 - Added support for `arydshln` dashed lines with HTML `tabular`, but reverts to plain rules for lateximage and SVG math array.
- misc. fixes**
- Fix: `\thinspace`.
 - Fix: `paralist` compact environments.
- packages**
- Added `parnotes`, `quoting`, `lua-check-hyphen`, `tocenter`, `underscore`.
 - Added `bibunits`.
 - Tested to work as-is with `babelbib`, `bodegraph`, `fast-diagram`, `nicematrix`, `structmech`.
- v0.55: Various fixes.**
- misc fixes**
- Fix: Extraneous space in file links, which also prevented *Calibre* EPUB conversions.
 - Fix: Float optional argument regression.
 - Fix: `\ForceHTMLTOC` with `\phantomsection`.
 - Fix: Overfull boxes in lateximages.
 - Fix: QED symbols in lateximage.
- packages**
- `koma-script`: Fix: Figure with `\centering`, etc.
 - Added `clrdblpg`.

v0.54: Float `\centering`, improved image checks.

⚠ Reset the configuration

lwarpmk

BibTeX
polyglossia

macros in section names

document encoding

⚠ New and revised
encoding options

- Due to changes in *lwarpmk*, **recompile any existing project a single time** using `pdflatex filename.tex` or similar, after which *lwarpmk* may then be used with the new configuration files.
- *lwarpmk* `limages` checks for the presence of the HTML version of the document and valid image references before attempting to create the `lateximages`.
- *lwarpmk*: Improved error message if configuration file does not exist.
- Added documentation for avoiding error with BibTeX and `\etalchar`. See section 8.6.9.
- Added documentation regarding `polyglossia`. See section 8.15.4.
- Added documentation regarding the use of macros in section names. See section 8.1.
- Renamed and added package options:

Old Package Option	New Package Option
<code>xdyFilename</code>	<code>xindyStyle</code>
<code>IndexLanguage</code>	<code>xindyLanguage</code>
–	<code>xindyCodepage</code>
–	<code>pdfotextEnc</code>

Use these options along with `inputenc` or `inputenx` to process documents in an encoding other than UTF-8. See section 7.4.

floats with `\centering`, etc.

- Floats now honor `\centering`, `\raggedright`, `\raggedleft`, and their `ragged2e` equivalents, when placed directly after:

```
\begin{floattype}
\centering
```

misc. fixes

- `tikz`: `\pgfpicture`, `fit`, `align`, `font`.
- `ragged2e`: `\centering` etc.
- `hyperref`: `\hypertarget` was creating duplicate of `\label`.
- `hyperref`: Active chars inside `\hyperref`, `\hyperlink`.
- `hyperref`: `\ref` inside `\hyperlink` caused a nested HTML link.
- `glossaries`: Fix when not using `babel` or `polyglossia`.
- `textcomp`: `\textperthousand`.
- L^AT_EX core verse environment: line spacing.
- Removed `\citetitle`, adjusted `\attribution`.
- `memoir`: Minor update for v3.7g.
- Added `inputenx`, `bibunits`, `chnpage`, `forest`, `magaz`, `gridset`.
- Prevents loading `ae`, `aecc`, `tlenc`, and `wasysym`.

⚠
packages

v0.53: Improved image checks.

lwarpmk

- *lwarpmk*: Added a warning about corrupted images due to the need to recompile the document one more time.
- *lwarpmk*: Added the `lwarpmk cleanlimages` command.
- Added documentation for `lwarpmk cleanlimages` and `lwarpmk pdftohtml`.

v0.52: Improved footnotes, svg math.

documentation

- Improved install instructions regarding `lwarp_baseline_marker.png`.
- Added documentation regarding footnotes in section headings, and footnotes with `\VerbatimFootnotes` from `fancybox`, `fancyvrb`. See section 8.5.4.
- Added documentation regarding font selection when using $\text{X}\text{E}\text{L}\text{A}\text{T}\text{E}\text{X}$ or $\text{L}\text{u}\text{a}\text{L}\text{A}\text{T}\text{E}\text{X}$ with `fontspec` and traditional font packages. See section 7.4.

SVG math

- Fix: Limit the number of background tasks when generating `lateximages`.
- Added user-adjustable svg math font scaling. See section 84.3.
- Added warnings if `lwarp_baseline_marker.png` is not present, or if `graphicx` or `graphics` is not loaded.
- Improved `\ensuremath` hashing expansion.
- Fix: `equation*` with `split`.
- `tabbing` now works inside a `lateximage`. Use for math in `tabbing`.

MathJax

- Fix: `MATHJAX` script was not executing in some conditions.
- Added `\CustomizeMathJax` to add custom functions. See section 8.7.

footnotes

- Fix: Footnote numbering when using `HTMLDebugComments`.
- Fix: Footnote paragraph tags.
- Fix: `FootnoteDepth` defaults to `\subsubsection`.

misc. fixes

- Fix: `\kill` in a `lateximage`.
- Fix: `\FileDepth`, misc. others, when input encoding is not `utf8`.
- Fix: `\texorpdfstring` in a section name.

packages

- `hyperref` emulation: Fix for `#`, `%`, `&`, `~`, `_` characters in URLs.
- `fancybox`, `fancyvrb`: Initial support for `\VerbatimFootnotes`.
- `nicefrac`: Added with fix for `\ensuremath`.
- `graphicx`: Fix for option defaults. Added `v1.1a/b` options.
- `endfloat`: Updated for `v2.6`.
- `url`: Fixes for active characters.

2 Introduction

The `lwarp` project aims to allow a rich \LaTeX document to be converted to a reasonable `HTML5` interpretation, with only minor intervention on the user's part. No attempt has been made to force \LaTeX to provide for every `HTML`-related possibility, and `HTML` cannot exactly render every possible \LaTeX concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the `HTML` conversion.

Several “modern” features of `HTML5`, `CSS3`, and `SVG` are employed to allow a fairly feature-rich document without relying on the use of `JAVASCRIPT`. Limited testing on older browsers shows that these new features degrade gracefully.

`lwarp` is a native \LaTeX package, and operates by either patching or emulating various functions. Source-level compatibility is a major goal, but occasional user intervention is required in certain cases.

As a package running directly in \LaTeX , `lwarp` has some advantages over other methods of `HTML` conversion. \TeX itself is still used, allowing a wider range of \TeX trickery to be understood. Lua expressions are still available with `LuaTeX`. Entire categories of \LaTeX packages work as-is when used with `lwarp`: definitions, file handling, utilities, internal data structures and calculations, specialized math-mode typesetting for various fields of science and engineering, and anything generating plain-text output. Blocks of `PDF` output may be automatically converted to `SVG` images while using the same font and spacing as the original print document, directly supporting `Tikz` and `picture`. Numerous packages are easily adapted for `HTML` versions, either by loading and patching the originals, or by creating nullified or emulated replacements, and all without resorting to external programming. As a result, several hundred packages have already been adapted (table 2), and an uncounted number more work as-is.

Packages have been selected according to several criteria: perceived importance, popularity lists, recent `CTAN` updates, `CTAN` topics, mention in other packages, support by other `HTML` conversion methods, and from sample documents taken from public archives. These include some “obsolete” packages as well.¹

Assistance is also provided for modifying the `HTML` output to suit the creation of `EPUB` documents, and for modifying the `HTML` output to ease import into a word processor.

`pdflatex`, `xelatex`, or `lualatex` may be used, allowing `lwarp` to process the usual image formats. While generating `HTML` output, `SVG` files are used in place of `PDF`. Other formats such as `PNG` and `JPG` are used as-is.

¹An amazing number of decades-old packages are still in use today.

svg images may be used for math, and are also used for `picture`, `Tikz`, and similar environments. The svg format has better browser and e-book support than MathML (as of this writing), while still allowing for high-quality display and printing of images (again, subject to potentially bug-ridden² browser support).

Furthermore, svg images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by `<alt>` tags holding the L^AT_EX source for the expression, allowing it to be copy/pasted into other documents.³ Custom L^AT_EX macros may be used as-is in math expressions, since the math is evaluated entirely inside L^AT_EX. An MD5 hash is used to combine multiple instances of the same inline math expression into a single image file, which then needs to be converted to svg only a single time.

The MATHJAX JavaScript display engine may be selected for math display instead of using svg images. Subject to browser support and Internet access, MATHJAX allows an HTML page to display math without relying on a large number of external image files.⁴ `lwarp` maintains L^AT_EX control for cross-referencing and equation numbering, and attempts to force MATHJAX to tag equations accordingly.

A *texlua* program called *lwarpmk* is used to process either the print or HTML version of the document. A few external utility programs are used to finish the conversion from a L^AT_EX-generated PDF file which happens to have HTML5 tags, to a number of HTML5 plain-text files and accompanying images.

`lwarp` automatically generates the extra files necessary for the HTML conversion, such as CSS and `.xdy` files, and configuration files for the utility *lwarpmk*. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects HTML output and then inputs the user's own source. This process allows both the printed and HTML versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during HTML conversion, `lwarp` first looks to see if it has its own modified version to use instead of the standard L^AT_EX version. These `lwarp-packagename.sty` files contain code used to emulate or replace functions for HTML output.

²FIREFOX has had an on-again/off-again bug for quite some time regarding printing svgs at high resolution.

³There seems to be some debate as to whether MathML is actually an improvement over L^AT_EX for sharing math. The author has no particular opinion on the matter, except to say that in this case L^AT_EX is much easier to implement!

⁴One svg image file per math expression, except that duplicate inline math expressions are combined into a single file according to the MD5 hash function of its contents. A common scientific paper can easily include several thousand files, and in one case the MD5 hash cut the number of files in half and the rendering time by 30%.

2.1 Typesetting conventions

Font weight, family, and style are used to indicate various objects:

Table 1: Typesetting conventions

<code>package</code>	L ^A T _E X package.
<i>program</i>	Program's executable name.
<code>option</code>	Program or package option.
<code>filename</code>	File name in the operating system.
<code>BRAND NAME</code>	Proper name for a program, operating system, etc.
commands	Commands to be entered by the user.
<code>code</code>	Program code.
<code>\macroname</code>	L ^A T _E X macro.
<code>environment</code>	L ^A T _E X environment.
<code>counter</code>	L ^A T _E X counter.
<code>boolean</code>	L ^A T _E X boolean.
<code><element></code>	HTML element.
<code>attribute</code>	HTML attribute.
User Interface	A user-interface item.
<code>ACRO</code>	Acronym.

subjects Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph. These are often the targets of index entries.

index entries

Black-colored tags in the left margin are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are command macros. Each of these also appears in the index as individual entries, and are also listed together under “files”, “packages”, “environments”, “booleans”, and “counters”.

 **warnings** Special warnings are marked with a warning icon.

2.2 Supported packages and features

Table 2 lists some of the various L^AT_EX features and packages which may be used.

Package names are colored according to their support level:

name: Supported as-is.

name: Modified to work with HTML output, and perhaps also as print output in SVG math or `lateximage` environments.

name: Emulated for HTML output.

name: Ignored for HTML output, but provides source-level compatibility.

MJ: Supported as-is for MATHJAX, subject to limitations.

MJ: Emulated for MATHJAX using custom macros, subject to limitations.

MJ: Ignored by MATHJAX, but may be used in the document source. May be converted to SVG images.

Table 2: L^AT_EX lwarp package — Supported features

Category	Status and supported features.
Engines:	DVI L ^A T _E X, PDF L ^A T _E X, X _Ǝ L ^A T _E X, LuaL ^A T _E X, upL ^A T _E X
L ^A T _E X compiling:	<i>latexmk</i> , <i>make</i> , etc.
External compiling:	<i>perltex</i> , <i>pythontex</i> , <i>symptex</i>
Classes:	article, book, report, scrartcl, scrbook, screprpt, memoir, CJK-related as listed below.
Koma-script:	scxextend , scrhack , scllayer . Others as listed below.
Memoir:	memhfixc
Beamer:	beamerarticle , but not the beamer class.
Languages:	babel , ckjpunct , imprnatypo , luavlina , polyglossia , xeCJK , xevlina .
Chinese:	CT _E X, ctex , upzhkinsoku , xpinyin , zhlineskip , zhspacing .
Japanese:	upL ^A T _E X, LuaT _E X-ja, gentombow , lltjext , plarray , plarydshln , plautopatch , plext , plextarray , plextarydshln , plextcolortbl , plextdelarray , pxatbegshi , pxeveryshi , pxftnright , pxgentombow , pxjahyper , pxpdfpages , pxpgfrcs , pxpgfmark , tascmac , zxjatype . bxjsarticle and related, ltjsarticle and related, luatexja , luatexja-fontspec , ujarticle and related, utarticle and related.
Korean:	kotex , luatexko , xetexko .

lwarp Supported Functions — continued

Category	Status
Page layout:	2in1, 2up, a4, a4wide, a5comb, addlines, anysize, atbegshi , balance, blowup, booklet, bophook, bounddvi, bxpapersize, canoniclayout, centerlastline, changelayout , changepage , chngpage, clrdblpg, continue, draftcopy, drafftfigure, draftwatermark, ebook, everyshi, fancyhdr , fancytabs, flippdf, fullminipage, fullpage, fwlw, geometry, gmeometric, grid, grid-system , gridset, layaureo, layout, layouts, leading, lscape, ltxgrid, nccfancyhdr, notespages, nowidow, pagegrid, pagesel, parallel , parcolumns , pbalance, pdfcolparallel, pdfcolparcolumns, pdfcrypt, pdfscape, pdfprivacy, preview, ragged2e , returntgrid, rmpage, scrlayer-scrpage , scrpage2 , setspace , selectp, textarea, threadcol, thumb, thumbs, titleps, tocenter, turnthepage, twoup, typearea, underlin, vmargin, watermark, widows-and-orphans, zwpagelayout.
Sectioning:	Adds FileDepth for splitting the HTML output. Files may be numbered sequentially or named according to section name. Common short words and punctuation are removed from the filenames. anonchap , bsheaders, decorule , fncychap, froufrou , hypbmsec , indentfirst , quotchap , section, sectionbreak , secdot , sectsty, titlesec, tocvsec2 .
Table of contents, figures, tables:	Supported, with hyperlinks. etoc , minitoc , multitoc , shorttoc , tableof , titletoc , tocbasic , tocbibind , tocdata , tocloft , tocstyle , tocvsec2 .
Title page:	<code>\maketitle</code> , <code>titlepage</code> , authblk , authaftertitle , titling .
Front & back matter:	abstract , appendix .
Indexing:	makeindex , xindy , and xindex are supported, with hyperlinks. gindex , hindex , idxlayout , imakeidx , index , makeidx , repeatindex , splitidx , varindex , xindex .
Glossary:	gloss , glossaries and xindy , nomencl .
Bibliography:	babelbib , bibtopic , backref , biblatex , bibunits , chapterbib , cite , citeref , collref , drftcite , hypernat , jurabib , mcite , mciteplus , multibib , natbib , notes2bib , splitbib , showtags .
Cross-references:	bookmark , breakurl , cleveref , fancyref , hypdestopt , hyperref , perpage , prettyref , titleref , url , varioref , xcite , xr , xr-hyper , xurl , zref .

lwarp Supported Functions — continued

Category	Status
Margin notes:	marginal, marginfit, marginfix, sclayer-notecolumn , versonotes .
Footnotes:	Adds FootnoteDepth to print footnotes at section breaks. MATHJAX emulation for \footnote, and also as marked in the following: bigfoot , dblfnote , endheads , endnotes^{MJ} , enotez^{MJ} , fixfoot , fnbreak , fnpara , fnpct , fnpos , footmisc , footnote , footnotebackref , footnoterange , footnpag , manyfoot , marginnote^{MJ} , nccfoots^{MJ} , pagenote^{MJ} , parnotes^{MJ} , pdfcolfoot , pfnote , sepfootnotes , sidenotes^{MJ} , tablefootnote .
Math:	Converted to SVG images with HTML <alt> tags containing the L ^A T _E X source for the math expression. MATHJAX supported as an alternative. amsmath^{MJ} : \mathcal{AMS} environments are supported. User-defined macros are available during conversion, due to native L ^A T _E X processing.
Theorems:	Native L ^A T _E X theorems, amsthm , apxproof , ntheorem , shadethm , theorem , thmbox , thmtools .
Additional math:	Math fonts via SVG images, accents^{MJ} , amscd^{MJ} , amscdx , autobreak^{MJ} , autonum , backnaur^{MJ} , bm^{MJ} , braket^{MJ} , breqn^{MJ} , bussproofs^{MJ} , cases^{MJ} , centernot^{MJ} , cmbright^{MJ} , colonequals^{MJ} , decimal^{MJ} , delarray , DotArrow^{MJ} , dotlessi^{MJ} , dotlessj^{MJ} , esvect^{MJ} , extrarrows^{MJ} , fixmath^{MJ} , fouridx^{MJ} , fourier^{MJ} , guass , hhtensor^{MJ} , icomma^{MJ} , isomath^{MJ} , jkmath , kpfonds^{MJ} , kpfonds-otf^{MJ} , leftidx^{MJ} , libertinust1math^{MJ} , mathalpha^{MJ} , mathastext^{MJ} , mathcomp^{MJ} , mathdesign^{MJ} , mathdots^{MJ} , mathfixs^{MJ} , mathpazo^{MJ} , mathptmx^{MJ} , mathpunctspace^{MJ} , mathspec^{MJ} , mathtools^{MJ} , mattens^{MJ} , maybemath^{MJ} , mdwmath^{MJ} , mismath^{MJ} , mlefttright^{MJ} , multiobjective^{MJ} , nccmath^{MJ} , nicematrix^{MJ} , noitcrl^{MJ} , newpxmath^{MJ} , newtxmath^{MJ} , newtxsf^{MJ} , pb-diagram , pxfonts^{MJ} , resizegather^{MJ} , rmathbr^{MJ} , scalere^{MJ} , shuffle^{MJ} , skmath^{MJ} , stackrel^{MJ} , statex2^{MJ} , statistics , statmath^{MJ} , subsupscripts^{MJ} , tensind , tensor^{MJ} , textualicomma^{MJ} , txfonts^{MJ} , txgreeks^{MJ} , unicode-math^{MJ} , upgreek^{MJ} , ushort^{MJ} , witharrows^{MJ} , xfakebold^{MJ} , xy . Many others work as-is.
Display math with \displaymathother:	Complicated math objects in display math, such as tikz-cd , etc.

lwarp Supported Functions — continued

Category	Status
Units and fractions:	<code>nicefrac^{MJ}</code> , <code>Slunits^{MJ}</code> , <code>siunitx^{MJ}</code> , <code>units^{MJ}</code> , <code>unitsdef</code> , <code>xfrac^{MJ}</code> .
Floats:	Appear where declared. <code>capt-of</code> , <code>caption</code> , <code>cutwin</code> , <code>dblfloatfix</code> , <code>endfloat</code> , <code>fewerfloatpages</code> , <code>fix2col</code> , <code>flafter</code> , <code>float</code> , <code>floatflt</code> , <code>floatrow</code> , <code>fltrace</code> , <code>ftcap</code> , <code>hypcap</code> , <code>keyfloat</code> , <code>morefloats</code> , <code>multicap</code> , <code>newfloat</code> , <code>nonfloat</code> , <code>picinpar</code> , <code>placeins</code> , <code>rotfloat</code> , <code>stfloats</code> , <code>subcaption</code> , <code>subfig</code> , <code>subfigure</code> , <code>subfloat</code> , <code>swfigure</code> , <code>topcapt</code> , <code>trivfloat</code> , <code>wrapfig</code> , <code>wrapfig2</code> .
Tabular:	<code>tabular</code> environment, <code>array^{MJ}</code> , <code>arydshln^{MJ}</code> , <code>bigdelim^{MJ}</code> , <code>bigstrut^{MJ}</code> , <code>booktabs^{MJ}</code> , <code>colortbl^{MJ}</code> , <code>ctable</code> , <code>dcolumn</code> , <code>diagbox</code> , <code>hhline^{MJ}</code> , <code>longtable</code> , <code>ltablex</code> , <code>ltxtable</code> , <code>multirow^{MJ}</code> , <code>supertabular</code> , <code>tabularx</code> , <code>tabulary</code> , <code>threeparttable</code> , <code>threeparttablex</code> , <code>widetable</code> , <code>xltabular</code> , <code>xtab</code> .
Graphics:	<code>graphics</code> and <code>graphicx</code> . <code>\includegraphics</code> supports width, height, origin, angle, and scale tags, and adds class. References to PDF files are changed to SVG, other image types are accepted as well. <code>\rotatebox</code> and <code>\scalebox</code> are supported as well as HTML can handle. <code>rotating</code> is emulated but all objects are unrotated in HTML. <code>picture</code> , <code>tikz</code> , and <code>xy</code> are converted to an SVG image. <code>asymptote</code> , <code>curves</code> , <code>datatool</code> , <code>eepic</code> , <code>epsf</code> , <code>epsfig</code> , <code>epstopdf</code> , <code>figsize</code> , <code>fitbox</code> , <code>grffile</code> , <code>lpic</code> , <code>luamplib</code> , <code>media9</code> , <code>movie15</code> , <code>multimedia</code> , <code>overpic</code> , <code>pict2e</code> , <code>pinlabel</code> , <code>psfrag</code> , <code>psfragx</code> , <code>pst-eps</code> , <code>pstool</code> , <code>pstricks</code> , <code>rlepsz</code> , <code>rviewport</code> , <code>svg</code> , <code>svg-extract</code> , <code>tikz</code> , <code>tikz-3dplot</code> , <code>tikz-image-labels</code> , <code>xy</code>
xcolor:	Full package color names, any color models, and mixing. <code>\textcolor</code> , <code>\colorbox</code> , <code>\fcolorbox</code> . Enhanced for HTML compatibility.
Lists:	Standard L ^A T _E X environments, <code>enumerate</code> , <code>enumitem</code> , <code>eqlist</code> , <code>hang</code> , <code>listliketab</code> , <code>paralist</code> .
Environments:	Standard L ^A T _E X environments.
Paragraphs, minipage, \parbox:	Some HTML5-imposed limitations. Nested minipages are supported. <code>eqparbox</code> , <code>fancypar</code> , <code>minibox</code> , <code>pbox</code> , <code>shapepar</code> .
Quotations:	<code>copyrightbox</code> , <code>csquotes</code> , <code>epigraph</code> , <code>quoting</code> , <code>verse</code> .
Verbatim:	<code>fancyvrb</code> , <code>fvextra</code> , <code>moreverb</code> , <code>shortvrb</code> , <code>verbatim</code> .
Frames:	<code>boxedminipage</code> , <code>boxedminipage2e</code> , <code>fancybox</code> , <code>fbox^{MJ}</code> , <code>framed</code> , <code>mdframed</code> , <code>niceframe</code> , <code>shadow</code> , <code>tcolorbox^{MJ}</code> , <code>vertbars</code> .

lwarp Supported Functions — continued

Category	Status
Multi-columns:	adjmulticol , multicol , multicolrule , vwcol .
Margins:	fullwidth , hanging , midpage .
Line numbering:	fnlineno , lineno .
Direct formatting:	<code>\emph</code> , <code>\textsuperscript</code> , <code>\textbf</code> , etc are supported. <code>\bfseries</code> , etc. are only supported in some cases. cancel^{MJ} , ellipsis , embrac , enparen , hyphenat , lettrine , lips , lua-check-hyphen , luacolor , magaz , moresize , nolbreaks , normalcolor , pdfcol , pdfcolmk , pdfrender , realscripts , resize^{MJ} , scalefnt , seqsplit^{MJ} , soul , soulpos , soulutf8 , stackengine , textfit , thinsp , trimclip , truncate , ulem , umoline , underscore , uspace , xellipsis .
Acronyms:	acro , acronym .
Ordinals:	engord , fmtcount , nth .
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for thin-unbreakable , unbreakable , \enskip , \quad , \qqquad , \hspace .
Rules:	<code>\rule</code> with width , height , raise , text color .
HTML reserved characters:	<code>\&</code> , <code>\textless</code> , and <code>\textgreater</code> are converted to HTML entities.
Fonts:	Used as-is. Appear in svg math expressions or embedded image environments . fontaxes , nfssect-cfr , slantsc , tabfigures . Tested to work as-is: Special font macros in cfr-lm and others which use nfssect-cfr . Also see the math section for math and MATHJAX support for math font packages .
Symbols:	Native \LaTeX diacriticals, academicons , amssymb^{MJ} , bbding , ccicons , chemgreek , dingbat , euro , eurosym , fontawesome , fontawesome5 , gensymb^{MJ} , latexsym^{MJ} , marvosym , metalogo , metalogox , pifont , textalpha , textcomp^{MJ} , textgreek , typicons , xunicode .
Files:	attachfile , attachfile2 , hyperxmp , inputtrc , intopdf , pdfpages , pdfx , xmpincl .

lwarp Supported Functions — continued

Category	Status
Science and engineering:	algorithm2e, algorithmicx, ar ^{MJ} , askmaps, axodraw2, bitpattern, blochsphere, bodegraph, bohr, bytefield, chemfig, chemformula, chemgreek, chemmacros, chemnum, circuitikz, econometrics ^{MJ} , elements, engtlc ^{MJ} , fast-diagram, ghsystem, hepnicensnames, heppennames, hepunits ^{MJ} , isotope ^{MJ} , karnaughmap, karnaugh-map, keystroke, listings, listingsutf8, linop, menukeys, mhchem ^{MJ} , minted, pgfgantt, phfqit, physics ^{MJ} , physunits ^{MJ} , plimsoll ^{MJ} , qcircuit, register, simplebnf, simpler-wick, slashed ^{MJ} , steinmetz ^{MJ} , structmech, struktex, syntaxdi, tikz-karnaugh, tikzcodeblocks, venndiagram
Arts and humanities:	foreign, forest, lyluatex, musicography, nameauth, octave, phonrule, piano, schemata, semantic-markup, tikz-dependency, vowel, xpiano
Academic:	academicons, classicthesis, doi, doipubmed, orcidlink ^{MJ} , termcal
Admonitions:	awesomebox, notes.
Editorial:	changebar, changelog, changes, easy-todo, easyReview, ed, errata, fixme, fixmetodonotes, pdfcomment ^{MJ} , pdfmarginpar, todo, todonotes, tram, xexchangebar.
Accessibility:	accessibility ^{MJ} , accsupp ^{MJ} , aaccessibility ^{MJ} , pdfcomment ^{MJ} , repltext ^{MJ} , tagpdf.
Package handling:	catoptions.
Debug:	chkfloat, cmdtrack, dprogress, lipsum, lua-visual-debug, mwe, refcheck, showlabels, showkeys, srcltx, srctex, vpe, xbmks.
Working as-is:	Various utility, calculation, file, and text-only packages, such as calc, fileerr, somedefs, trace, xspace. Also, most math-only packages, including specialized typesetting for various fields of science and engineering.

3 Alternatives

Summarized below are several other ways to convert a \LaTeX or other document to HTML . Where an existing \LaTeX document is to be converted to HTML , `lwarp` may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

3.1 internet class

Cls internet

The closest to `lwarp` in design principle is the `internet` class by Andrew Stacey—an interesting project which directly produces several versions of `markdown`, and also `HTML` and `EPUB`. <https://github.com/loopspace/latex-to-internet>

3.2 \TeX4HT

Prog TeX4ht

<http://tug.org/tex4ht/>

Prog htlatex

This system uses native \LaTeX processing to produce a `DVI` file containing special commands, and then uses additional post-processing for the `HTML` conversion by way of numerous configuration files. In some cases `lwarp` provides a better `HTML` conversion, and it supports a different set of packages. `TeX4ht` produces several other forms of output beyond `HTML`, including `ODT` and a direct path to `EPUB`, and is still being developed.

3.3 Translators

These systems use external programs to translate a subset of \LaTeX syntax into `HTML`. Search for each on `CTAN` (<http://ctan.org>).

Prog Hevea

H^Ev^Ea: <http://hevea.inria.fr/> (not on `CTAN`)

Prog TtH

T_TH: <http://hutchinson.belmont.ma.us/tth/>

Prog GELLMU

GELLMU: <http://www.albany.edu/~hammond/gellmu/>

Prog LaTeXML

\LaTeX XML: <http://dlmf.nist.gov/LaTeXML/>

Prog Plastex

PlasTeX: <https://github.com/tiarno/plastex>

Prog LaTeX2HTML

\LaTeX 2HTML: <http://www.latex2html.org/>
and <http://ctan.org/pkg/latex2html>.

Prog TeX2page

TeX2page: <http://ds26gte.github.io/tex2page/index.html>

Finally, `GladTeX` may be used to directly insert \LaTeX math into `HTML`:

Prog GladTeX

GladTeX: <http://humenda.github.io/GladTeX/>

3.4 ASCIIDOC and ASCIIDOCTOR

AsciiDoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes L^AT_EX and HTML.

Prog AsciiDoc

Asciidoctor: <http://asciidoctor.org/> (More active.)

Prog AsciiDoctor

AsciiDoc: <http://asciidoc.org/> (The original project.)

3.4.1 ASCIIDOCTOR-L^AT_EX

The Asciidoctor-LaTeX project is developing additional L^AT_EX-related features.

Asciidoctor-LateX:

<http://www.noteshare.io/book/asciidoctor-latex-manual>

<https://github.com/asciidoctor/asciidoctor-latex>

Prog Asciidoctor-LaTeX

3.5 PANDOC

Prog Pandoc

A markup system which also reads and writes L^AT_EX and HTML.

Pandoc: <http://pandoc.org/>

(Watch for improvements in cross-references to figures and tables.)

3.6 Word processors

Prog Word

Prog LibreOffice

Prog OpenOffice

It should be noted that the popular word processors have advanced through the years in their abilities to represent math with a L^AT_EX-ish input syntax, unicode math fonts, and high-quality output, and also generate HTML with varying success. See recent developments in MICROSOFT[®] *Word*[®] and LIBREOFFICE[™] *Writer*.

3.7 Commercial systems

Prog Adobe

Prog FrameMaker

Prog InDesign

Prog Flare

Prog Madcap

Likewise, several professional systems exist whose abilities have been advancing in the areas of typesetting, cross-referencing, and HTML generation. See ADOBE[®] *FrameMaker*[®], ADOBE *InDesign*[®], and MADCAP *Flare*[™].

3.8 Comparisons

AsciiDoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to require many combinations of special characters, resulting in a complicated mess of syntax. By contrast, L^AT_EX spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster

entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that L^AT_EX is comparably easy to learn, while L^AT_EX provides many more advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of L^AT_EX vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a L^AT_EX back end, yielding high-quality results especially when the L^AT_EX template is adjusted, but they lose the ability to use L^AT_EX macros and other L^AT_EX source-document features.

The effort required to customize the output of each markup system varies. For print output, L^AT_EX configuration files are usually used. For HTML output, a CSS file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of lwarp, CSS is used, and much HTML output is adjusted through the usual L^AT_EX optional macro parameters, but further customization may require patching L^AT_EX code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

4 Installation

Table 3 shows the tools which are used for the L^AT_EX to HTML conversion. In most cases, these will be available via the standard package-installation tools.

Detailed installation instructions follow.

Table 3: Required software programs

Provided by your L^AT_EX distribution:

From T_EXLive: <http://tug.org/texlive/>.

L^AT_EX: *pdflatex*, *xelatex*, or *lualatex*.

The lwarp package: This package.

The *lwarpmk* utility: Provided along with this package. This should be an operating-system executable in the same way that *pdflatex* or *latexmk* is. It is possible to have the *lwarp* package generate a local copy of *lwarpmk* called `lwarpmk.lua`. See table 4.

***luatex*:** Used by the *lwarpmk* program to simplify and automate document generation.

***xindy*:** The *xindy* program is used by *lwarp* to create indexes. On a M_IK_TE_X system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

***latexmk*:** Optionally used by *lwarpmk* to compile L^AT_EX code. On a M_IK_TE_X system, *Perl* may need to be installed first.

***pdfcrop*:** Used to pull images out of the L^AT_EX PDF.

POPPLER PDF utilities:

***pdftotext*:** Used to convert PDF to text.

***pdfseparate*:** Used to pull images out of the L^AT_EX PDF.

***pdftocairo*:** Used to convert images to SVG.

These might be provided by your operating-system package manager, and M_IK_TE_X provides `miktex-poppler-bin-*` packages.

From POPPLER: poppler.freedesktop.org.

For MACOS[®], see <https://brew.sh/>, install *Homebrew*, then

```
Enter ⇒ brew install poppler
```

For WINDOWS, see M_IK_TE_X `miktex-poppler-bin-*`, or:

<https://sourceforge.net/projects/poppler-win32/> and:
<http://blog.alivate.com.au/poppler-windows/>

Perl:

This may be provided by your operating-system package manager, and may be required for some of the POPPLER PDF utilities.

strawberryperl.com (recommended), perl.org

Automatically downloaded from the internet as required:

MATHJAX: Optionally used to display math. From: mathjax.org

4.1 Installing the lwarp package

There are several ways to install lwarp. These are listed here with the preferred methods listed first:

Pre-installed: Try entering into a command line:

```
Enter ⇒ kpsewhich lwarp.sty
```

If a path to lwarp.sty is shown, then lwarp is already installed and you may skip to the next section.

TeX Live: If using a TeX Live distribution, try installing via *tlmgr*:

```
Enter ⇒ tlmgr install lwarp
```

MiKTeX:

1. For newer versions of MiKTeX, install or update lwarp using the *MiKTeX Console* program.
2. For older versions of MiKTeX, to install lwarp the first time, use the *MiKTeX Package Manager (Admin)*. To update lwarp, use *MiKTeX Update (Admin)*.
3. Either way, also update the package miktex-misc, which will install and update the *lwarpmk* executable.

Operating-system package: The operating-system package manager may already have lwarp, perhaps as part of a set of TeX-related packages.

CTAN TDS archive: lwarp may be downloaded from the Comprehensive TeX Archive:

1. See <http://ctan.org/pkg/lwarp> for the lwarp package.
2. Download the TDS archive: lwarp.tds.zip
3. Find the TeX local directory:

TeX Live:

```
Enter ⇒ kpsewhich -var-value TEXMFLOCAL
```

MiKTeX:

In the **Settings** window, **Roots** tab, look for a local TDS root.

This should be something like:

```
/usr/local/texlive/texmf-local/
```

4. Unpack the archive in the TDS local directory.
5. Renew the cache:

```
Enter ⇒ mktexlsr
```

— OR —

```
Enter ⇒ texhash
```

Or, for WINDOWS MiKTeX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.

CTAN .dtx and .ins files: Another form of TeX package is .dtx and .ins source files. These files are used to create the documentation and .sty files.

1. See <http://ctan.org/pkg/lwarp> for the lwarp package.
2. Download the zip archive lwarp.zip into your own lwarp directory.
3. Unpack lwarp.zip.

4. Locate the contents `lwarp.dtx` and `lwarp.ins`

5. Create the `.sty` files:

```
Enter ⇒ pdflatex lwarp.ins
```

6. Create the documentation:

```
pdflatex lwarp.dtx (several times)
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
makeindex -s gind.ist lwarp.idx
pdflatex lwarp.dtx (several times)
```

7. Copy the `.sty` files somewhere such as the T_EX Live local tree found in the previous CTAN TDS section, under the subdirectory:

```
<texlocal>/tex/latex/local/lwarp
```

8. Copy `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` to the same place as the `.sty` files.

9. Copy the documentation `lwarp.pdf` to a source directory in the local tree, such as:

```
<texlocal>/doc/local/lwarp
```

10. Renew the cache:

```
Enter ⇒ mktexlsr
```

— or —

```
Enter ⇒ texhash
```

Or, for WINDOWS MiK_TE_X, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.

11. See section 4.2.1 to generate your local copy of *lwarpmk*.

12. Once the local version of `lwarpmk.lua` is installed, it may be made available system-wide as per section 4.2.

Project-local CTAN `.dtx` and `.ins` files: The `.dtx` and `.ins` files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant `*.sty` and `lwarpmk.lua` files may be used as-is, so long as they are in the same directory as the document source. The files `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` must also be copied as well. This approach is especially useful if you would like to temporarily test *lwarp* before deciding whether to permanently install it.

Just testing!

4.2 Installing the *lwarpmk* utility

(Note: If *lwarpmk* is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 4.2.1.)

After the *lwarp* package is installed, you may need to setup the *lwarpmk* utility:

1. At a command line, try executing **lwarpmk**. If the *lwarpmk* help message appears, then *lwarpmk* is already set up. If not, it is easiest to generate and use a local copy. See section 4.2.1.
2. For MiK_TE_X, try updating the `miktex-misc` package. This may install the *lwarpmk* executable for you.

Otherwise, continue with the following:

3. Locate the file `lwarpmk.lua`, which should be in the `scripts` directory of the TDS tree. On a T_EX Live or M_IKT_EX system you may use

Enter ⇒ **kpsewhich lwarpmk.lua**

(If the file is not found, you may also generate a local copy and use it instead. See section 4.2.1.)

4. Create *lwarpmk*:

Unix: Create a symbolic link and make it executable:

- (a) Locate the T_EX Live binaries:

Enter ⇒ **kpsewhich -var-value TEXMFROOT**

This will be something like:

`/usr/local/texlive/<year>`

The binaries are then located in the `bin/<arch>` directory under the root:

`/usr/local/texlive/<year>/bin/<architecture>/`

In this directory you will find programs such as *pdflatex* and *makeindex*.

- (b) In the binaries directory, create a new symbolic link from the binaries directory to `lwarpmk.lua`:

Enter ⇒ **ln -s <path to lwarpmk.lua> lwarpmk**

- (c) Make the link executable:

Enter ⇒ **chmod 0755 lwarpmk**

WINDOWS T_EX Live: Create a new `lwarpmk.exe` file:

- (a) Locate the T_EX Live binaries as shown above for UNIX.
- (b) In the binaries directory, make a *copy* of `runscript.exe` and call it `lwarpmk.exe`. This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

WINDOWS M_IKT_EX: Create a new `lwarpmk.bat` file:

- (a) Locate the M_IKT_EX binaries. These will be in a directory such as:

`C:\Program Files\MiKTeX 2.9\miktex\bin\x64`

In this directory you will find programs such as `pdflatex.exe` and `makeindex.exe`.

- (b) Create a new file named `lwarpmk.bat` containing:

`texlua "C:\Program Files\MiKTeX 2.9\scripts\lwarp\lwarp.texlua" %*`

This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

4.2.1 Using a local copy of *lwarpmk*

It is also possible to use a local version of *lwarpmk*:

1. When compiling the tutorial in section 5, use the `lwarpmk` option for the `lwarp` package:

```
\usepackage[lwarpmk]{lwarp}
```

2. When the tutorial is compiled with *pdflatex*, the file `lwarpmk.lua` will be generated along with the other configuration files.
3. `lwarpmk.lua` may be used for this project:

Unix:

(a) Make `lwarpmk.lua` executable:

Enter ⇒ `chmod 0755 lwarpmk.lua`

(b) Compile documents with

Enter ⇒ `./lwarpmk.lua html`

Enter ⇒ `./lwarpmk.lua print`

etc.

(c) It may be useful to rename or link to a version without the `.lua` suffix.

WINDOWS:

Compile documents with either of the following, depending on which command shell is being used:

Enter ⇒ `texlua lwarpmk.lua html`

Enter ⇒ `texlua lwarpmk.lua print`

etc.

Or:

Enter ⇒ `lwarpmk html`

Enter ⇒ `lwarpmk print`

etc.

4.3 Installing additional utilities

To test for the existence of the additional utilities:

Enter the following in a command line. If each program's version is displayed, then that utility is already installed. See table 3 on page 76.

Enter ⇒ `luatex --version`

Enter ⇒ `xindy --version`

Enter ⇒ `latexmk --version`

Enter ⇒ `perl --version`

Enter ⇒ `pdfcrop --version`

Enter ⇒ `pdftotext -v`

Enter ⇒ `pdfseparate --version`

Enter ⇒ `pdftocairo -v`

To install *xindy*, *latexmk*, and *pdfcrop*:

The TeX utilities *xindy*, *latexmk*, and *pdfcrop* may be installed in *TeXLive* with *tlmgr*, installed by *MiKTeX*, provided by your operating system's package manager, or downloaded from the CTAN archive:

<http://ctan.org/pkg/xindy>

<http://ctan.org/pkg/latexmk>

<http://ctan.org/pkg/pdfcrop>

To install the POPPLER utilities to a UNIX/LINUX system:

The tools from the POPPLER project should be provided by your operating system's package manager.

To install the POPPLER utilities to a MACOS machine:

1. Install *Homebrew* from <https://brew.sh/>:

`/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"`

Prog [requirement] pdftotext
 Prog [requirement] pdfseparate
 Prog [requirement] pdftocairo

2. Install the POPPLER utilities:

Enter ⇒ **brew install poppler**

To install the POPPLER utilities to a WINDOWS machine:

If using MikTEX, install a miktex-poppler-bin-* package. Otherwise:

1. See table 3 on page 76.
2. Download and extract the POPPLER utilities *pdftotext*, *pdfseparate*, and *pdfseparate* to a directory, such as Poppler.
3. In the **Start** window, type "Path" to search for results related to Path. Or, open the control panel and search for "Path".
4. Choose **Edit the system environment variables** in the control panel.
5. Choose the **Environment Variables** button.
6. Choose the **Path** variable, then the **Edit** button.
7. Choose the **New** button to make an additional entry.
8. Enter the bin directory of the POPPLER utilities, such as:
C:\Users\\Desktop\Poppler\poppler-0.5_x86\poppler-0.5\bin
Be sure to include \bin.
9. Click **Ok** when done.

Prog [requirement] perl

To install PERL to a WINDOWS machine:

1. Download and install a version of PERL, such as STRAWBERRY PERL, to a directory without a space in its name, such as C:\Strawberry.
2. Edit the **Path** as seen above for the POPPLER utilities.
3. Enter the bin directory of the *perl* utility, such as:
C:\Strawberry\perl\bin
Be sure to include \bin.
4. Click **Ok** when done.

Any utilities installed by hand must be added to the PATH.

5 Tutorial

This section shows an example of how to create an `lwarp` document.

Need help?

See the [General Index](#) for “how-to”, and the [Troubleshooting Index](#) if something doesn’t work. A [Troubleshooting](#) section is also available. The [Index of Objects](#) contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

5.1 Starting a new project

1. Create a new project directory called `tutorial`.
2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

Copy from the documentation PDF:

A listing is in [fig. 1](#), which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

Copy from the lwarp documentation directory:

Another copy may be found by entering into a command line:

Enter ⇒ `texdoc -l lwarp_tutorial.txt`

This should be in the `doc/latex/lwarp/` directory along with this PDF documentation. Copy `lwarp_tutorial.txt` directly into your `tutorial` directory, renamed as `tutorial.tex`.

When using Windows, use an editor other than Notepad, since Notepad does not accept the end-of-line from a Unix text file.

3. Compile the project:

Enter ⇒ `pdflatex tutorial.tex`

(several times)

(*xelatex* or *lualatex* may be used as well. `lwarp` also supports DVI *latex* for use with `.eps` images.)

4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in [table 4](#). These files are created by the `lwarp` package.

(Two of the new files are configuration files for the helper program *lwarpmk*. Whenever a print version of the document is created, the configuration files for *lwarpmk* are updated to record the operating system, L^AT_EX engine (*latex*, *pdflatex*, *xelatex*, or *lualatex*), the filenames of the source code and HTML output, and whether the additional helper program *latexmk* will be used to compile the document.)

File `tutorial.tex`

File `lwarp_tutorial.txt`

⚠ Note: `.txt` suffix!

⚠ Bad formatting!

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarp package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern}           % pdflatex or dvi latex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec}         % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
% HomeHTMLFilename=index,      % Filename of the homepage.
% HTMLFilename={node-},        % Filename prefix of other pages.
% IndexLanguage=english,      % Language for xindy index, glossary.
% latexmk,                     % Use latexmk to compile.
% OSWindows,                   % Force Windows. (Usually automatic.)
% mathjax,                      % Use MathJax to display math.
]{lwarp}
% \boolfalse{FileSectionNames} % If false, numbers the files.

% --- LOAD PDFLATEX MATH FONTS HERE ---

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor}   % (Demonstration purposes only.)
\usepackage{hyperref,cleveref} % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarp Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2} % Include subsections in the \TOC.
\setcounter{secnumdepth}{2} % Number down to subsections.
\setcounter{FileDepth}{1} % Split \HTML\ files at sections
\booltrue{CombineHigherDepths} % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1} % Include subsections in the side\TOC
\HTMLTitle{Webpage Title} % Overrides \title for the web page.
\HTMLAuthor{Some Author} % Sets the HTML meta author tag.
\HTMLLanguage{en-US} % Sets the HTML meta language.
\HTMLDescription{A description.} % Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSFilename{lwarp_sagebrush.css}

\begin{document}

\maketitle % Or titlepage/titlingpage environment.
```

```

% An article abstract would go here.

\tableofcontents           % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math:  $r = r_0 + vt - \frac{1}{2}at^2$ 
followed by display math:
\begin{equation}
a^2 + b^2 = c^2
\end{equation}

\begin{warpprint} % For print output ...
\cleardoublepage % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage % HTML index will be on its own page.
\ForceHTMLTOC % HTML index will have its own toc entry.
\printindex

\end{document}

```

Table 4: Configuration files created by print version

- tutorial.pdf:** The PDF output from L^AT_EX. The print version of the document.
- tutorial_html.tex:** A small .tex file used to create a parallel HTML version of the document, which co-exists with usual the PDF version, and which will have its own auxiliary files. In this way, both PDF and HTML documents may co-exist side-by-side.
- Auxiliary files:** The usual L^AT_EX files .aux, .log, .out, .toc, .lof, .idx. When an HTML version of the document is created, _html versions of the auxiliary files will also be generated.
- lwarpmk.conf:** A configuration file for *lwarpmk*, which is used to automate the compilation of PDF or HTML versions of the document.
- tutorial.lwarpmkconf:** Another configuration file used by *lwarpmk*, which is only useful if you wish to have several projects residing in the same directory.
- .css files:** *lwarp.css*, *lwarp_formal.css*, *lwarp_sagebrush.css* These files are standard for *lwarp*, and are not meant to be modified by the user.
- sample_project.css:** An example of a user-customized css file, which may be used for project-specific changes to the *lwarp* defaults.
- lwarp.ist:** Used by *lwarp* while creating an index using *makeindex*. This file should not be modified by the user. A custom file may be used instead, if necessary.
- lwarp.xdy:** Used by *lwarp* while creating an index using *xindy*. This file should not be modified by the user. A custom file may be used instead, if necessary.
- lwarp_one_limage.txt:** For WINDOWS only. Used to process SVG images in the background. Copied to *lwarp_one_limage.cmd* when images are generated.
- lwarp_mathjax.txt:** Inserted into the HTML files when MATHJAX is used to display math. Do not modify, see `\MathJaxFilename` instead.
- comment_*.cut:** Temporary files used by *lwarp* to conditionally process blocks of text. These files may be ignored.

When the *lwarpmk* option is given to the *lwarp* package:

lwarpmk.lua: A local copy of the *lwarpmk* utility.

On UNIX-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

5.2 Compiling the print version with *lwarpmk*

The *lwarpmk* utility program is used to compile either the printed or the HTML version of the document.

`lwarpmk print` is used to recompile a printed version of the document.

⚠ Enable *lwarpmk*

1. If you have not yet done so, add `\usepackage{lwarp}` to the document, then compile the project a single time using *pdflatex*, *lualatex*, or *xelatex*. This generates the file `lwarpmk.conf`, which then allows the *lwarpmk* program to be used.

2. Re-compile the print version:

Enter ⇒ **lwarpmk print**

lwarpmk prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then *lwarpmk* informs you of that fact and then exits.

3. Make a small change in the original document, such as adding a space character.

4. Recompile again.

Enter ⇒ **lwarpmk print**

The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

5. Force a recompile to occur.

Enter ⇒ **lwarpmk again**

Enter ⇒ **lwarpmk print**

`lwarpmk again` updates the date code for the file, triggering a recompile the next time the document is made.⁵

6. Process the index.^{6 7}

Enter ⇒ **lwarpmk printindex**

7. Recompile again to include the index.

Enter ⇒ **lwarpmk print**

8. To force a single recompile when needed, even if no changes were detected:

Enter ⇒ **lwarpmk print1**

Note that the HTML customization commands are ignored while making the print version.

⁵Although, when using the utility *latexmk* (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

⁶The command `lwarpmk printglossary` is also available to process a glossary produced with the glossaries package. See section 8.6.12.

⁷Also see section 8.6.15 for index options.

5.3 Compiling the HTML version with *lwarpmk*

`lwarpmk html` is used to recompile an HTML version of the document.

⚠ Enable *lwarpmk*

1. If you have not yet done so, add `\usepackage{lwarp}` to the document, then compile the project a single time using *pdflatex*, *lualatex*, or *xelatex*. This generates the file `lwarpmk.conf`, which then allows the *lwarpmk* program to be used.

2. Compile the HTML version:

```
Enter ⇒ lwarpmk html
```

- (a) *lwarpmk* uses L^AT_EX to process `tutorial_html.tex` to create `tutorial_html.pdf`.
- (b) *pdftotext* is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.
- (c) *lwarpmk* manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`⁸, `Some-math.html`, and the document's index in `_Index.html`.⁹

3. View the HTML page in a web browser.

Open the file `tutorial.html` in a web browser.

math images

Note that math images have not yet been generated, so math is still displayed as its `alt` tag, which is set to the plain-text L^AT_EX source for that expression. Math may be displayed as SVG images (section 5.4) or by a MATHJAX script (section 5.5).

4. Force a recompile:

```
Enter ⇒ lwarpmk again
```

```
Enter ⇒ lwarpmk html
```

```
Enter ⇒ lwarpmk print
```

5. Process the HTML index and recompile:¹⁰¹¹

```
Enter ⇒ lwarpmk htmlindex
```

```
Enter ⇒ lwarpmk html
```

`_Index.html` is updated for the new L^AT_EX index.

6. Reload the web page to see the added index.

7. To force a single recompile when needed, even if no changes were detected:

```
Enter ⇒ lwarpmk html1
```

⁸`First-chapter.html` also contains the first section, even though the second section is its own HTML page. This behavior is controlled by the boolean `CombineHigherDepths`.

⁹`index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

¹⁰The command `lwarpmk htmlglossary` is also available to process a glossary produced with the `glossaries` package. See section 8.6.12.

¹¹Also see section 8.6.15 for index options.

5.4 Generating the SVG images

math as SVG images By default `lwarp` represents math as SVG images, with the \LaTeX source included in `alt` attributes. In this way, the math is displayed as it was drawn by \LaTeX , and the \LaTeX source may be copied and pasted into other documents.

picture and Tikz `lwarp` uses the same mechanism for `picture` and `Tikz` environments.

1. Create the SVG images:

```
Enter ⇒ lwarpmk limages
```

```
Enter ⇒ lwarpmk html
```

2. Move to the tutorial's HTML math page and reload the document in the browser.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the \LaTeX source.

 **adding/removing** When a math expression, `picture`, or `Tikz` environment is added or removed, the SVG images must be re-created by entering **lwarpmk limages** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as `Tikz` may move to new image numbers when the document is changed.

recompile first Before attempting to create the SVG image files, `lwarpmk` verifies that the HTML version of the document exists and has correct internal image references.¹² If it is necessary to recompile the document's HTML version one more time, `lwarpmk` usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the \LaTeX recompile warnings.

 **HTML instead of images** If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

 **page counter** Incorrect SVG images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

Lots of files! Expressing math as SVG images has the advantage of representing the math exactly as \LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, `lwarp` uses an MD5 hash on its \LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and `Tikz` require one image file each. For a document with a large amount of math, see section 5.5 to use `MATHJAX` instead.

¹²This becomes important when dealing with a document containing thousands of images.

5.5 Using MATHJAX for math

[math with MATHJAX](#) Math may also be represented using the MATHJAX JAVASCRIPT project.

1. In the tutorial's source code, uncomment the `mathjax` package option for `lwarp`:

```
mathjax, % Use MathJax to display math.
```

2. Recompile

```
Enter ⇒ lwarpmk html
```

3. Reload the math page.

 **MATHJAX requirements** MATHJAX requires web access unless a local copy of MATHJAX is available, and it also requires that JAVASCRIPT is enabled for the web page. The math is rendered by MATHJAX. Right-click on math to see several options for rendering, and for copying the L^AT_EX source.

While using MATHJAX has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as L^AT_EX, and it may not support some math-related packages.

5.6 Changing the css style

For a formal css style, add to the preamble:

```
\usepackage{lwarp}  
...  
\CSSfilename{lwarp_formal.css}  
...  
\begin{document}
```

For a modern css style, `lwarp_sagebrush.css` is also provided:

```
\CSSfilename{lwarp_sagebrush.css}
```

See section 7.7 for more information about modifying the css styling of the document.

5.7 Customizing the HTML output

A number of settings may be made to control the HTML output, including filename generation, automatic compilation, math output, document splitting, meta data, and page headers and footers.

See section 7.6 for more information.

5.8 Using *latexmk*

latexmk is a L^AT_EX utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the *latexmk* option for the *lwarp* package:

```
latexmk, % Use latexmk to compile.
```

2. Recompile the printed version of the document.

```
Enter ⇒ lwarpmk print
```

lwarp updates its own configuration files (*lwarpmk.conf* and *tutorial.lwarpmkconf*) whenever the printed version of the document is compiled. These configuration files remember that *lwarpmk* should use *latexmk* to compile the document.

3. Recompile the document.

```
Enter ⇒ lwarpmk print
```

and/or

```
Enter ⇒ lwarpmk html
```

Changes are detected by comparing checksums rather than modification times, so *lwarpmk* again will not trigger a recompile, but *latexmk* has a much better awareness of changes than the *lwarpmk* utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source, and a single recompile may be forced with:

```
Enter ⇒ lwarpmk print1
```

and/or

```
Enter ⇒ lwarpmk html1
```

[forced single-pass recompile](#)

5.9 Using Xe_ΛTeX or Lua_ΛTeX

Xe_ΛTeX or Lua_ΛTeX may be used instead of L_ΛTeX.

1. Remove the auxiliary files for the project:

```
Enter ⇒ lwarpmk cleanall
```

2. Use *xelatex* or *lualatex* to compile the printed version a single time.

```
Enter ⇒ xelatex tutorial.tex
```

— *or* —

```
Enter ⇒ lualatex tutorial.tex
```

When the compile occurs, the configuration files for *lwarpmk* are modified to remember which T_EX engine was used. Xe_ΛTeX or Lua_ΛTeX will be used for future runs of *lwarpmk*.

3. To recompile the document:

```
Enter ⇒ lwarpmk print
```

-and-

```
Enter ⇒ lwarpmk html
```

4. Also remember to update the indexes and recompile again:

```
Enter ⇒ lwarpmk htmlindex
```

```
Enter ⇒ lwarpmk html
```

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk print
```

5.10 Using DVI L_ΛTeX

Traditional DVI L_ΛTeX may also be used along with .eps image files. An svg version of each image must also be provided. *lwarpmk* may be used to convert image formats.

To convert EPS files to PDF:

```
Enter ⇒ lwarpmk epstopdf *.eps (or a list of files)
```

To convert PDF files to SVG:

```
Enter ⇒ lwarpmk pdftosvg *.pdf (or a list of files)
```

 **bitmapped fonts** See section 7.4 regarding font selection to avoid the use of bitmapped fonts.

5.11 Using a glossary

lwarp supports the `gloss` and `glossaries` packages, although this tutorial does not supply an example.

5.11.1 `gloss` package

See section [8.6.11](#).

5.11.2 `glossaries` package

To process the glossary for the print version:

```
Enter ⇒ lwarpmk printglossary
```



(If `makeglossaries` is not found, see section [8.6.12](#).)

To process the glossary for the HTML version:

```
Enter ⇒ lwarpmk htmlglossary
```

In each case, the document will have to be recompiled afterwards:

```
Enter ⇒ lwarpmk html1
```

```
Enter ⇒ lwarpmk html
```

```
Enter ⇒ lwarpmk print1
```

```
Enter ⇒ lwarpmk print
```

See section [8.6.12](#) to set options for processing glossaries.

5.12 Cleaning auxiliary files

To remove the auxiliary files `.aux`, `.toc`, `.lof`, `.lot`, `.idx`, `.ind`, `.log`, and `.gl*`, and a few others:

```
Enter ⇒ lwarpmk clean
```

5.13 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the `.pdf` and `.html` files:

```
Enter ⇒ lwarpmk cleanall
```

5.14 Cleaning the images from the `<project>-images` directory

The `<project>-images` directory contains SVG images automatically generated for inline and display math, `tikz`, etc. To remove all the images from the `<project>-images` directory:

```
Enter ⇒ lwarpmk cleanimages
```

5.15 Converting PDF or EPS images to SVG

HTML cannot display PDF or EPS images, so any external PDF graphics images must be converted to SVG format. `pdftocairo` and `epstopdf` may be used one image at a time, but `lwarpmk` also provides a way to convert PDF or EPS images in bulk:

```
Enter ⇒ lwarpmk epstopdf *.eps (or a list of files)
```

```
Enter ⇒ lwarpmk pdftosvg *.pdf (or a list of files)
```

Be sure to always provide SVG files for HTML output.

5.16 Creating HTML from an incomplete compile

During testing it may be useful to finish the HTML conversion even when the document had errors and did not compile successfully. To attempt an HTML conversion of an incomplete document:

```
Enter ⇒ lwarpmk pdftohtml [-p project]
```

5.17 Processing multiple projects in the same directory

 `xr`, `xr-hyper`, `xcite`

It is possible to have several projects in the same directory. `lwarpmk` has an optional parameter which is the document to compile.

To create each project:

```
Enter ⇒ pdflatex project_a
```

```
Enter ⇒ pdflatex project_b
```

Each project is given its own configuration file:

```
project_a.lwarpmkconf, project_b.lwarpmkconf
```

To compile each project with `lwarpmk`:

```
Enter ⇒ lwarpmk print -p project_a
```

```
Enter ⇒ lwarpmk print -p project_b
```

```
Enter ⇒ lwarpmk html -p project_a
```

```
Enter ⇒ lwarpmk html -p project_b
```

To generate each project's images:

```
Enter ⇒ lwarpmk limages -p project_a
```

```
Enter ⇒ lwarpmk limages -p project_b
```

To clean each project's images:

```
Enter ⇒ lwarpmk cleanlimages -p project_a
```

```
Enter ⇒ lwarpmk cleanlimages -p project_b
```

To clean each project's auxiliary files:

```
Enter ⇒ lwarpmk cleanall -p project_a
```

```
Enter ⇒ lwarpmk cleanall -p project_b
```

If using *bibtex*, for example, the HTML version must also be processed:

```
Enter ⇒ bibtex project_a_html
```

5.18 Using the *make* utility

lwarpmk has an action which may be useful for integration with the common *make* utility:

```
lwarpmk pdftohtml [-p project]
```

make may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then *lwarpmk* may be used to convert each target to HTML files.

5.19 What next?

How do I do something? See the [General Index](#).

Something do not work! See the [Troubleshooting Index](#) or section [13: Troubleshooting](#).

Package options: See section [29, Package options](#).

HTML and filename settings: See section [7.6, Customizing the HTML output](#).

Footnote placement: See section [7.6, Customizing the HTML output](#).

Title page, indexing, glossaries: See section [8.6, Front and back matter](#).

Shell escape: See section [7.3, Shell escape](#).

css customization: See section [7.7, Customizing the css](#).

MATHJAX customization: See section [8.7.6, Customizing MATHJAX](#).

Localization: (languages) — See section [7.1, Localization](#).

Accessibility: (alt and title tags) — See section [7.2, Accessibility](#).

Converting an existing document: See section [6, Converting an existing document](#).

EPUB conversion: See section [10, EPUB conversion](#).

Word processor conversion: See section [11, Word-processor conversion](#).

6 Converting an existing document

To convert an existing document for use with lwarp:

1. Arrange the document in the following order:

- (a) Declare the `\documentclass`.
- (b) Load text fonts.
- (c) Load `inputenc` or `inputenx`, `fontenc`, or `fontspec`.
- (d) Load `lwarp`.
- (e) Load remaining packages.

2. Modify the document:

- (a) If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the toc entry without the math, or use `\texorpdfstring` from the `hyperref` package:

```
\section{Some math \texorpdfstring{$1+2=3$}{three}}
```

- (b) Avoid using the `\includegraphics scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

- (c) Possible changes to `tabular` environments include: `* columns`, `multirow`, `longtable`, `supertabular`, `xtable`, `bigdelim`. See section 8.10.1.

- (d) If using braces in package options, such as with `caption`, see section 8.1.

- (e) Possible option clashes with `memoir`. See section 8.13.

- (f) If using `indexes`, see section 8.6.15.

- (g) If using many `indexes`, `glossaries`, `.aux` files, etc., see section 8.6.15 regarding `morewrites`. If `morewrites` is already used, be sure to add the setup with `allocate=10`.

- (h) Other changes as per [Special cases and limitations](#), section 8.

3. Convert any PDF images to SVG. See section 8.8.

4. Manually compile the print version with `latex`, `pdflatex`, `lualatex`, or `xelatex`.

5. `lwarpmk print` to finish the print version.

6. `lwarpmk html` to create the HTML version.

7. `lwarpmk limages` to create the SVG images of any SVG math, `lateximage`, `Tikz`, etc.

See the [General Index](#) for “how-to”, and the [Troubleshooting Index](#) if something doesn’t work. A [Troubleshooting](#) section is also available. The [Index of Objects](#) contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

Need help?

⚠ math in section names

⚠ scale

⚠ tabular

⚠ package options

⚠ indexes

Table 5: Localization settings

Object names: L^AT_EX provides redefinable names for various objects, and lwarp adds a few more. Use `\renewcommand` to change these.

`\abstractname`: This macro is honored by lwarp.

`\linkhomename`: Displayed by the link to the homepage.

`\linkpreviousname`: Displayed by the link to the previous page

`\linknextname`: Displayed by the link to the next page.

`\sitetocname`: Displayed at the head of the sideroc.

HTML settings: See table 8 and section 7.6 for details.

`\HTMLLanguage`: The language to declare for each web page.

**`\ImageAltText`, `\MathImageAltText`, `\PackageDiagramAltText`,
`\AltTextOpen`, `\AltTextClose`:** The defaults used for HTML alt text for images. See section 7.2.

`\CSSFilename`: The name of the css file to use.

`\MathJaxFilename`: The name of the MATHJAX script to use.

Package options:

`ImagesName` and `ImagesDirectory`: These options control the filenames used by lwarp when it automatically generates images. See table 7 and section 7.5.

`xindyStyle`, `xindyLanguage`, `xindyCodepage`: When using *xindy*, these options may be set according to local use. See section 8.6.21.

`pdftotextEnc`: To adjust the encoding of *pdftotext*.

7 Additional details

7.1 Localization

Regional localization is supported by lwarp via the package options and macros shown in table 5.

7.2 Accessibility

lwarp provides several methods for improving access to the document using tools such as text-only browsers, copy/paste, text-to-speech readers, or Braille readers. lwarp can use the HTML alt text attribute for images, as describe below. lwarp can also use the HTML title attribute, which usually generates a pop-up text. lwarp can add this to a reference or hyperlink. lwarp also uses standard HTML5 elements which are pre-assigned ARIA roles for increased accessibility, and lwarp assigns the math role for SVG math images, and the note role for footnotes, end notes, margin paragraphs and notes, etc. MATHJAX also has provisions for improved accessibility as well. See table 6.

Table 6: Accessibility settings

\ImageAltText: The default HTML alt text for `\includegraphics` and `lateximages`. Set with `\renewcommand`.

\includegraphics alt key: For `\includegraphics`, `lwarp` adds the alt key/value. For example:

```
\includegraphics[alt={Some text.}]{filename}
```

svg math: For simple SVG math, `lwarp` places the L^AT_EX math expression in the alt text, so that the L^AT_EX expression may be copied and pasted to another document as plain text.

\MathImageAltText: For complicated SVG math, such as enclosed in `\InlineMathOther`/`\InlineMathNormal`, or `\DisplayMathOther`/`\DisplayMathNormal`, the HTML alt text will be set to `\MathImageAltText`. Set with `\renewcommand`.

MATHJAX: For MATHJAX, the accessibility tools provided by MATHJAX are enabled by default by `lwarp`'s MATHJAX scripts.

\PackageDiagramAltText: Various packages create diagrams which `lwarp` converts into SVG images. These are given alt text set to `\PackageDiagramAltText`. Set with `\renewcommand`.

\ThisAltText: The HTML alt text of the next image may be set with:

```
\ThisAltText{Custom text about the image.}
<SVG math, Tikz, picture, etc.>
```

The next single image will be generated with the given text, and the following images will revert to back to their defaults.

`\ThisAltText` may also be used to assign an HTML title to the next reference or hyperlink.

```
\ThisAltText{Custom text about the link.}
Text ... \ref{label_name} ... text.
```

See section 7.6.

\AltTextOpen and \AltTextClose: By default, HTML alt text is enclosed by parentheses. This may be changed by redefining `\AltTextOpen` and `\AltTextClose`. Set with `\renewcommand`.

7.3 Shell escape

Opt `--shell-escape`

Some documents require the use of an external program, which is allowed when using the `--shell-escape` command-line option. When the document is first compiled manually, and also whenever the print version is recompiled, `lwarp` detects and remembers whether shell escape is enabled. If so, it will also be enabled when the document is recompiled with `lwarpmk`.

7.4 Font and UTF-8 support

- ⚠ **type 3 bitmapped fonts** `lwarp` uses `pdftotext` to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which may prevent the use of older “type 3” bit-mapped fonts, and of older packages such as `ae`. The `lwarp` option `pdftotextEnc` may be useful in some situations. See section 7.5.
- vector fonts
Computer Modern
⚠ `pdflatex`
⚠ `DVI latex`
While using DVI `latex` or PDF `pdflatex`, if no font-related package is specified then the default COMPUTER MODERN font is used, which may be a “type 3” bit-mapped font which may not convert well to plain text. A “type 1” vector font is required.
- Pkg `cm-super`
To use the updated `cm-super`’s type 1 fonts instead of Computer Modern, install the `cm-super` font package.
- Pkg `lmodern`
To use Latin Modern instead, add

```
usepackage{lmodern}
```


to the preamble.
- Pkg `dejavu`
Another useful option is the Deja Vu series of fonts, which have an increased coverage of language and glyphs:

```
\usepackage{dejavu}
```
- `latex`, `pdflatex`, T1, UTF8
While using DVI `latex` or PDF `pdflatex`, `lwarp` automatically loads `fontenc` with T1 encoding. `fontenc` may be loaded with an additional encoding after `lwarp`. `inputenc` is automatically loaded with UTF8 encoding if it has not yet been loaded, but may also be specified with another encoding such as `latin1`. See the next section regarding index encoding.
- ⚠ `xelatex`, `lualatex`,
fontspec
X_YL^AT_EX and Lua^AT_EX users must use the `fontspec` package. Do NOT use `fontenc`! Place `fontspec` or `fontenc`, `xunicode`, and other font and UTF-8 related commands after the `\documentclass` command and before `\usepackage{lwarp}`.
- ⚠ **package conflicts**
In some cases, a package conflict may require that a font package be loaded after `lwarp`, which should work as well:
1. `documentclass{article/book/report}` comes first, followed by any of:
 2. Font and UTF-8 related commands:
 - For X_YL^AT_EX or Lua^AT_EX:
 - `fontspec` and font choices
- Pkg `fontspec`
ligatures
`lwarp` sets the following to turn off T_EX ligatures during the generation of HTML tags, and turn off common ligatures in regular text,

since older browsers may not display them correctly and newer browsers can automatically re-create them.

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
```

- For *pdf_latex*:

Pkg lmodern
 Pkg fontenc
 Pkg inputenc
 Pkg inputenx
 Pkg newunicodechar
 File glyphtounicode.tex

- (a) `\usepackage{lmodern}`, or other font-related packages
- (b) `\usepackage[T1]{fontenc}`
- (c) `\usepackage[utf8]{inputenc}`, or `latin1`, etc. Or use `inputenx`.
- (d) `\usepackage{newunicodechar}` along with related definitions.
- (e) To assist with the PDF-HTML conversion:
 - i. `\input glyphtounicode.tex`
 - ii. `\input glyphtounicode-cmr.tex`% from the pdfx package
 - iii. `\pdfgentounicode=1`

 **dotless j**

Pkg cmap
 Pkg mmap
 Pkg textcomp

- (f) Another option to assist with the PDF-HTML conversion, such as the dotless j (`\j`):
 - `\usepackage{cmap}` — or —
 - `\usepackage{mmap}` — or —
 - `\usepackage[noTeX]{mmap}`
- (g) `\usepackage{textcomp}`

3. `\usepackage{newtxmath}` or other math-related font packages. Many of these load `amsmath`, which may now be loaded before `lwarp`.

4. `\usepackage{lwarp}` (section 7.5) is placed after any of the above, followed by:

 **fontspec with monospaced fonts**

5. `\setmonofont{TeX Gyre Cursor}` or similar may be required if using X_YL^AT_EX or Lua^AT_EX and `fontspec` along with traditional font packages such as `txfonts`, `newtxtext`, etc. This is required to turn off the monospaced font's ligatures with `fontspec` after loading the traditional font packages. Monospaced output ligatures must be turned off to produce the correct HTML characters.

Any monospace font with built-in ligatures may require these ligatures to be disabled for HTML. In one example, JETBRAIN MONO, it is required to use

 **JETBRAIN MONO**
 **HTML corrupted**

```
\setmonofont{JetBrains Mono}[%
...
Contextuals=AlternateOff,
]
```

After `lwarp` is loaded, the ligature may be re-enabled for print mode by using `\setmonofont` again inside a `warpprint` environment.

6. ... the rest of the preamble and the main document.

 **UTF-8 locale** In some cases, an external program may require a UTF-8 “locale”. See section 9.9.

7.4.1 Indexes, glossaries, and encoding

`lwarp` supports `makeindex`, `xindy`, `xindex`, and `glossaries`, `gloss`, and `nomencl`.

See section 8.6.14 for indexing, and section 8.6.12 for the `glossaries` package.

7.5 lwarp package loading and options

lwarp supports book, report, and article classes, as well as the equivalent KOMA-script classes and memoir, and various CJK-related classes and packages.

Load the lwarp package immediately after the font and UTF-8 setup commands.

Package options may be set while loading lwarp, or later with

```
\lwarpsetup{<key=value, . . . >}
```

lwarp package options are as follows:

Pkg	lwarp	
Opt	mathsvg	mathsvg and mathjax : Selects SVG images or MATHJAX for math display. See section 8.7.
Opt	mathjax	
		Default: mathsvg
Opt	latexmk	latexmk : Tells <i>lwarpmk</i> to use <i>latexmk</i> to recompile the document several times if necessary. Otherwise, <i>lwarpmk</i> attempts to determine for itself whether to recompile. See section 7.6.
Opt	dvips	dvips : Tells <i>lwarpmk</i> to use <i>dvips</i> and <i>ps2pdf</i> to convert DVI output to PDF.
Opt	dvipdfm	dvipdfm : Tells <i>lwarpmk</i> to use <i>dvipdfm</i> to convert DVI output to PDF.
Opt	dvipdfmx	dvipdfmx : Tells <i>lwarpmk</i> to use <i>dvipdfmx</i> to convert DVI output to PDF.
Opt	HomeHTMLfilename	HomeHTMLfilename : Filename of the homepage, without the “.html” suffix. Defaults to the \BaseJobname. A common setting is: <code>HomeHTMLfilename=index</code> causing the homepage to be the file <code>index.html</code> . Underscores are allowed in HomeHTMLfilename and HTMLfilename options, but may need to be escaped elsewhere, such as when appearing in a list: <code>\item [\href{file_name.pdf}{text}] \</code> See section 7.6.1 for examples of naming and numbering HTML files.
	Default: \BaseJobname	
	filename underscores	
Opt	HTMLfilename	HTMLfilename : A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty. See section 7.6.1 for examples of naming and numbering HTML files.
	Default: <empty>	
Opt	ImagesName	ImagesName : The prefix for the images automatically generated by lwarp for objects such as svg math and lateximages.
	Default: image-	
Opt	ImagesDirectory	ImagesDirectory : The directory for the images automatically generated by lwarp for objects such as svg math and lateximages. By default, these images will appear in a directory named <jobname>-images, and the images will be named and numbered image-<nn>.
	Default: \jobname-images	

Table 7: Lwarp package options

Option	Description
<code>mathsvg</code>	Show math using <code>svg</code> images.
<code>mathjax</code>	Show math using <code>MATHJAX</code> .
<code>latexmk</code>	Use <code>latexmk</code> for compiling documents.
<code>dvips</code>	Use <code>dvips</code> and <code>ps2pdf</code> to convert <code>DVI</code> documents.
<code>dvipdfm</code>	Use <code>dvipdfm</code> to convert <code>DVI</code> documents.
<code>dvipdfmx</code>	Use <code>dvipdfmx</code> to convert <code>DVI</code> documents.
<code>HomeHTMLFilename</code>	The filename of the home page.
<code>HTMLFilename</code>	A prefix for the filenames of the remaining web pages.
<code>ImagesName</code>	A prefix for the filenames of generated images.
<code>ImagesDirectory</code>	The directory used to hold generated images.
<code>PrintLatexCmd</code>	The shell commands for <code>lwarpmk print</code> .
<code>HTMLLatexCmd</code>	The shell commands for <code>lwarpmk html</code> .
For indexing (section 8.6.15) and glossaries (section 8.6.12):	
<code>makeindex</code>	Use <code>makeindex</code> to generate indices.
<code>makeindexStyle</code>	Set a custom style for <code>makeindex</code> .
<code>xindy</code>	Use <code>xindy</code> to generate indices.
<code>xindyStyle</code>	Set a custom style for <code>xindy</code> .
<code>xindyLanguage</code>	The <code>xindy</code> language option used for index generation.
<code>xindyCodepage</code>	The <code>xindy</code> codepage option used for index generation.
<code>xindex</code>	Use <code>xindex</code> to generate indices.
<code>xindexConfig</code>	Set a custom configuration file for <code>xindex</code> .
<code>PrintIndexCmd</code>	Shell commands executed by <code>lwarpmk printindex</code> .
<code>HTMLIndexCmd</code>	Shell commands executed by <code>lwarpmk htmlindex</code> .
<code>LatexmkIndexCmd</code>	Shell commands executed by <code>latexmk</code> .
<code>IndexRef</code>	How to format index links.
<code>GlossaryCmd</code>	Shell command executed by <code>lwarpmk printglossary</code> and <code>lwarpmk htmlglossary</code> .
Seldom necessary:	
<code>OSWindows</code>	Force compatibility with MS-WINDOWS.
<code>pdftotextEnc</code>	Set the encoding for <code>pdftotext</code> .
<code>lwarpmk</code>	Generate a local copy of <code>lwarpmk.lua</code> .
Used internally by <code>lwarp</code> :	
<code>warpprint</code>	Generate print output, and also generate configuration files.
<code>warphTML</code>	Generate HTML output.
<code>BaseJobname</code>	The <code>\jobname</code> to use. Set to the <code>\jobname</code> of the printed version even while generating HTML.

Opt	PrintLatexCmd Default: <automatic>	PrintLatexCmd: Sets the shell commands executed by lwarpmk print . If not specified, will automatically be set according to the detected L ^A T _E X engine and the use of <code>--shell-escape</code> .
Opt	HTMLLatexCmd Default: <automatic>	HTMLLatexCmd: Sets the shell commands executed by lwarpmk html . If not specified, will automatically be set according to the detected L ^A T _E X engine and the use of <code>--shell-escape</code> .
Opt	makeindex Default: makeindex	makeindex: Sets PrintIndexCmd, HTMLIndexCmd, and LatexmkImageCmd to use <i>makeindex</i> when generating indexes with lwarpmk printindex , lwarpmk htmlindex , or <i>latexmk</i> . If neither <code>makeindex</code> nor <code>xindy</code> is used, <code>makeindex</code> is assumed.
Opt	makeindexStyle Default: lwarp.ist	makeindexStyle: If you wish to use a custom <code>.ist</code> file for index generation, see section 8.6.20.
Opt	xindy Default: makeindex	xindy: Sets PrintIndexCmd, HTMLIndexCmd, and LatexmkImageCmd to use <i>xindy</i> when generating indexes with lwarpmk printindex , lwarpmk htmlindex , or <i>latexmk</i> .
Opt	xindyStyle Default: lwarp.xdy	xindyStyle: If you wish to use a custom <code>.xdy</code> file for index generation, see section 8.6.21.
Opt	xindyLanguage Default: english	xindyLanguage: If using an index or glossary, see section 29.
Opt	xindyCodepage Default: utf8	xindyCodepage: If using an index, see section 29.
Opt	xindex Default: makeindex	xindex: Sets PrintIndexCmd, HTMLIndexCmd, and LatexmkImageCmd to use <i>xindex</i> when generating indexes with lwarpmk printindex , lwarpmk htmlindex , or <i>latexmk</i> .
Opt	xindexConfig Default: <empty>	xindexConfig: If you wish to use a custom <code>xindex-*.lua</code> file for index generation, see section 8.6.22.
Opt	PrintIndexCmd Default: <automatic>	PrintIndexCmd: Sets the shell commands executed by lwarpmk printindex . If not specified, will be set by the selection of <code>makeindex</code> or <code>xindy</code> . May be used to specify the creation of multiple indexes. See section 8.6.15.

Examples:

```
makeindex -s lwarp.ist projectname.idx (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname.idx (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `PrintIndexCmd` to sensible values for each of those programs while compiling a single index. `lwarp`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified.

⚠ xindy

If specifying `PrintIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C` *xindy* options, as the `lwarp` `xindyLanguage` and `xindyCodepage` options are not used for the `PrintIndexCmd` option when it is set manually.

This option is stored in the configuration files `lwarpmk.conf` and `*.lwarpmkconf`, and is then passed by the `lwarpmk printindex` command to the operating system to compile the print indexes. Since the command string is parsed by `TEX`, written to a file, read from the file by `LuaTEX`, and finally passed to the operating system, any attempt at quoting will be problematic. For complicated commands, it would be best to create a shell script, and simply refer to the script with the `lwarp PrintIndexCmd` option.

Opt HTMLIndexCmd

Default: `<automatic>`

⚠ filenames

HTMLIndexCmd: Sets the shell commands executed by `lwarpmk htmlindex`. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 8.6.15.

Example settings are similar to `PrintIndexCmd`, but append `_html` to the filenames:

```
makeindex -s lwarp.ist projectname_html.idx      (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname_html.idx
(xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `HTMLIndexCmd` to sensible values for each of those programs while compiling a single index. `lwarp`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified.

⚠ xindy

If specifying `HTMLIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C xindy` options, as the `lwarp xindyLanguage` and `xindyCodepage` options are not used for the `HTMLIndexCmd` option when it is set manually.

As with `PrintIndexCmd`, to generate complicated indexes it may be worthwhile to use a shell script, then refer to that script with `HTMLIndexCmd`.

Opt LatexmkIndexCmd

Default: `<automatic>`

LatexmkIndexCmd: Sets the shell commands executed by `latexmk`. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `LatexmkIndexCmd` does not include any filenames, which will be provided instead by `latexmk`. See section 8.6.15.

Example settings are similar to `PrintIndexCmd`, but without a filename:

```
makeindex -s lwarp.ist                          (makeindex)
xindy -M lwarp.xdy -L english -C utf8           (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `LatexmkIndexCmd` to either of the two settings show above. `lwarp`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `latexmk` uses either of the single-line settings of `LatexmkIndexCmd` shown above to compile each of multiple indexes if necessary.

⚠ xindy

If specifying `LatexmkIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C xindy` options, as the `lwarp xindyLanguage` and `xindyCodepage` options are not used for the `LatexmkIndexCmd` option when it is set manually.

Opt IndexRef

Default: `cref`

IndexRef: Describes how to display the index entries for HTML output. Possible values are `ref`, `nameref`, `refnameref`, `cref`, `crefnameref`, `autoref`, or a text string such as `(link)` or `(*)` for each index entry reference. (Adding parentheses around a single character makes the link larger and easier to click on.) The default is `cref`, which is available even if the print document does

not use `cleveref`, as the `lwarp` package relies on `cleveref` during HTML output. Option `autoref` gives the same results as `cref`.

`\ref` and `\cref` to starred or otherwise unknown links will display as (*) instead of ??.

⚠ ??

If using `cref` (the default), and if a reference appears as ?? with a non-functional link, use `cleveref`'s `\crefname` to give a name to that type of label.

In general, `crefnameref` gives the most information, but the index can become quite verbose. Using (*) or similar yields a very compact index.

Opt `GlossaryCmd`
 Default: `makeglossaries`
GlossaryCmd: Sets the shell command executed by `lwarpmk printglossary` and `lwarpmk htmlglossary`. The print or HTML glossary filename is appended to this command. See section 8.6.12.

Opt `OSWindows`
OSWindows: `lwarp` attempts to automatically sense WINDOWS, but it may be forced with this option. See section 7.9.

Opt `pdftotextEnc`
 Default: `UTF-8`
pdftotextEnc: Used to specify the encoding used by `pdftotext` during the PDF-HTML conversion. In most situations, the default is the correct choice.

Opt `lwarpmk`
lwarpmk: If you wish to have `lwarp` generate a local copy of `lwarpmk.lua` for archival or local-installation purposes, compile the print version with the `lwarpmk` option set. See section 29.

The following options are used internally by `lwarp`, and usually are not used in the user's document:

Opt `warpprint`
 Opt `warpHTML`
warpprint and **warpHTML:** Usually controlled by `lwarpmk`, and not set in the document. Select the `warpprint` option to generate print output (default), or the `warpHTML` option to generate HTML5 output. The default is print output, so the print version may be compiled with the usual `pdflatex`, etc. When `lwarp` is loaded in print mode, it creates `<project>_html.tex`, which sets the `warpHTML` option before calling the user's source code `<project>.tex`. In this way, `<project>.tex` can `\usepackage{lwarp}` without any options to create a printed version, while `<project>_html.tex` will create an HTML version.

Opt `BaseJobname`
 Default: `\jobname`
BaseJobname: Not intended for the user. Used internally by `lwarp` when creating the `*_html.tex` file used to compile the HTML version. See section 29.

7.6 Customizing the HTML output

 **Placement!** Table 8 shows several settings may be used to customize the HTML output. Watch for the correct placement of each!

 **Changes!** Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:

Enter ⇒ `lwarpmk clearall`

2. Recompile the print version in order to recreate the configuration files for *lwarpmk*:

Enter ⇒ `lwarpmk print`

3. Finally, recompile the HTML version with the new settings:

Enter ⇒ `lwarpmk html`

Placed in the preamble before `\begin{document}`:

<code>\HTMLFirstPageTop</code> Default: <code><empty></code>	\HTMLFirstPageTop: <code>{\langle contents \rangle}</code> A user-definable custom action applied to the top of the home page. Useful for logos, etc. <code>\LinkNext</code> may be used to link to the next web page. Defaults empty. Ignored in print output.
<code>\HTMLFirstPageBottom</code> Default: <code><empty></code>	\HTMLFirstPageBottom: <code>{\langle contents \rangle}</code> A user-definable custom action applied to the bottom of the home page. Useful for logos, etc. <code>\LinkNext</code> may be used to link to the next web page. Defaults empty. Ignored in print output.
<code>\linkhomename</code> Default: <code>Home</code>	\linkhomename: Name of the link to the home page. Paragraphs are allowed. Redefine with <code>\renewcommand</code> .
<code>\linkpreviousname</code> Default: <code>Previous</code>	\linkpreviousname: Name of the link to the previous page. Paragraphs are allowed. Redefine with <code>\renewcommand</code> .
<code>\linknextname</code> Default: <code>Next</code>	\linknextname: Name of the link to the next page. Paragraphs are allowed. Redefine with <code>\renewcommand</code> .
Ctr <code>tocdepth</code>	tocdepth: Sectioning depth of the table of contents. See section 16 for a list of L ^A T _E X stack depths.
Ctr <code>SideTOCDepth</code> Default: <code>1</code> <code>sideroc</code>	SideTOCDepth: Sectioning depth of the sideroc. Defaults to 1, causing the sideroc to show sections but not subsections. Each subpage of the website has its own small table of contents on the side (the “sideroc”). Its depth is set by <code>SideTOCDepth</code> . This sideroc is only shown if the browser display is wide enough. When using a narrow web browser window, “responsive web design” is used to show the sideroc at the top of the page, as well as a link back to Home at the top and bottom. It is recommended to set: <code>SideTOCDepth=FileDepth</code> or

Table 8: HTML settings

Macro/Cntr/Bool	Loc*	Description
<code>\linkhomename</code>	P	Name of the link to the homepage.
<code>\linkpreviousname</code>	P	Name of the link to the previous page.
<code>\linknextname</code>	P	Name of the link to the next page.
<code>SideTOCDepth</code>	P	Sectioning depth of the sideroc.
<code>\sidetocname</code>	P	Name of the sideroc.
<code>FileDepth</code>	P	Sectioning depth of the file splits.
<code>CombineHigherDepths</code>	P	Combine higher section levels.
<code>FileSectionNames</code>	P	Use section names for file names, else use numbers.
<code>\FilenameLimit</code>	P	Maximum length of the generated filenames.
<code>FootnoteDepth</code>	P	Sectioning depth of footnotes.
<code>\abstractname</code>	P	The name of the abstract.
<code>\ImageAltText</code>	PD	<code>\includegraphics</code> and other images' alt tag.
<code>\ThisAltText {<text>}</code>	PD	Assigns an alt / title tag for the next image or link.
<code>\MathImageAltText</code>	PD	The svg math image <code>lateximage</code> alt tag.
<code>\PackageDiagramAltText</code>	PD	The suffix for a package's <code>lateximage</code> alt tags.
<code>\AltTextOpen</code>	PD	Start an HTML alt tag.
<code>\AltTextClose</code>	PD	End an HTML alt tag.
<code>\CSSFilename</code>	PS	The css for the following files.
<code>\MathJaxFilename</code>	PS	The MATHJAX script for the following files.
<code>\HTMLLanguage</code>	PS	The HTML lang tag.
<code>\HTMLTitle</code>	PS	The homepage's <title>, overriding <code>\title</code> .
<code>\HTMLTitleBeforeSection</code>	PS	Set subpage <title>s to <code>\HTMLTitle - sectionname</code>
<code>\HTMLTitleAfterSection</code>	PS	Set subpage <title>s to <code>sectionname - \HTMLTitle</code>
<code>\HTMLAuthor</code>	PS	The HTML author meta tag, overriding <code>\author</code> .
<code>\HTMLDescription</code>	PS	The HTML description meta tag.
<code>\HTMLFirstPageTop</code>	P	Heading for the home page.
<code>\HTMLFirstPageBottom</code>	P	Footer for the home page.
<code>\HTMLPageTop</code>	PS	Heading for the other pages.
<code>\HTMLPageBottom</code>	PS	Footer for the other pages.
<code>\HTMLnewcolumntype</code>	D	<code>\newcolumntype</code> for HTML.
<code>\IndexPageSeparator</code>	P	Index page list separator.
<code>\IndexRangeSeparator</code>	P	Index page range separator.
<code>FixSmallCaps</code>	P	Set true if small caps rendered as all caps.
<code>HTMLDebugComments</code>	P	Boolean to generate HTML comments.

* **P:** Preamble, **D:** Anywhere in the document. **S:** Before a section.

SideTOCDepth = FileDepth + 1

 **inaccessible pages**

If SideTOCDepth < FileDepth, web pages will be inaccessible via the sidetoc.

\sidetocname
Default: Contents

\sidetocname: Name of the sidetoc. Paragraphs are allowed. Redefine with \renewcommand.

Ctrl FileDepth
Default: -5

FileDepth: Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.

- To place the entire file into one HTML page, use:
`\setcounter{FileDepth}{-5}`
- To split the HTML file at \section depth, use:
`\setcounter{FileDepth}{1}`
- To ensure that the HTML pages/files are accessible:
Place a \tableofcontents somewhere before the first section break (therefore in the “home page”), and set
`tocdepth >= FileDepth`



Bool CombineHigherDepths
Default: true

CombineHigherDepths: Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

 **Inaccessible pages!**

 **Lost in an old page!**

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (`lwarpmk cleanall`), change FileDepth and/or CombineHigherDepths, then finally recompile and navigate to the desired page using the new file structure.

Bool FileSectionNames
Default: true

FileSectionNames: If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the HTMLFilename option is used as a prefix. See section 7.6.1 for examples of naming and numbering HTML files. The user must ensure that filenames are unique after begin sanitized. For example, math in the section name is removed before creating the filename, so the rest of the filename must be sufficiently unique to avoid name collisions.

 **Unique filename!**

\FilenameLimit
Default: 80

\FilenameLimit: The maximum length of the filenames generated by lwarp. “.html” is added to this length. Redefine with \renewcommand.

Ctrl FootnoteDepth
Default: 3

FootnoteDepth: Determines where to place pending footnotes. 3 places footnotes before each break down to the \subsubsection level. 1 places footnotes before each \section break. Any pending footnotes are also placed at the bottom of each page before each file break.

Bool FixSmallCaps
Default: false

FixSmallCaps: Set true if SMALL CAPS are rendering in all caps (“SMALL

CAPS”). May be required for some fonts (erewhon, utopia, fbb, et al.), and packages such as embrac.

Bool HTMLDebugComments Default: false	HTMLDebugComments: Set true to generate HTML comments, such as which section or <div> is being opened or closed.
\abstractname Default: Abstract	\abstractname: The name of the abstract. This may also be over-written by the babel package. Defaults to “Abstract”. Redefine with \renewcommand.
\IndexPageSeparator Default: “, ”	\IndexPageSeparator: Index page list separator. Adjust to match index style file. If using gindex, this is set automatically to gindex’s \indexpagesep.
\IndexRangeSeparator Default: “--”	\IndexRangeSeparator: Index page range separator. Adjust to match index style file. If using gindex, this is set automatically to gindex’s \indexrangesep.

Placed before \begin{document}, or before any sectioning command which causes a file break:

\CSSFilename Default: lwarp.css	\CSSFilename: $\{\langle filename.css \rangle\}$ Sets the css file to use for the following files. May be changed before each each sectioning command which would cause a file split.
------------------------------------	--

The css styles of the web pages are set by the \CSSFilename command. If \CSSFilename is not used, a default plain style is used to mimic printed L^AT_EX output. lwarp_sagebrush.css is a semi-fancy colored style as shown in this tutorial. Change it to lwarp_formal.css for a more formal look, or comment out the \CSSFilename command to see the default. \CSSFilename may be used before each file break to set the css for individual pagess of the website.

\MathJaxFilename Default: lwarp_mathjax.txt	\MathJaxFilename: $\{\langle filename \rangle\}$ Sets the MATHJAX script file to use for the following files. May be changed before each each sectioning command which would cause a file split.
--	---

The MATHJAX script file is copied into the head of each HTML file. This may be used to point to a local repository, add extensions, or change the script somewhere in the middle of the document. \MathJaxFilename may be used before each file break to set the script file for individual pages of the website.

\HTMLLanguage Default: en-US	\HTMLLanguage: $\{\langle langauge \rangle\}$ The HTML file’s HTML lang meta tag. Defaults to en-US.
---------------------------------	---

\HTMLTitle Default: \thetitle	\HTMLTitle: $\{\langle title \rangle\}$ Overrides \title for the HTML header’s meta title. Defaults to \thetitle, which is set by \title, or empty otherwise. Unlike the author, \thetitle is set by \title even if not using the titling package.
----------------------------------	---

\HTMLTitleBeforeSection Default: \HTMLTitleBeforeSection	\HTMLTitleBeforeSection: Sets subpage <title> tags to show the website title followed by the section name.
---	---

\HTMLTitleAfterSection	\HTMLTitleAfterSection: Sets subpage <title> tags to show the section name followed by the website title.
------------------------	--

custom <title>

To customize subpage <title>s, redefine \theHTMLTitleSection, which defaults to:

```
\def\theHTMLTitleSection{%
  \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
}
```

<code>\HTMLAuthor</code> Default: <code>\theauthor</code>	\HTMLAuthor: $\{\langle author \rangle\}$ The HTML header's meta author. Defaults to <code>\theauthor</code> , which is set by <code>\author</code> if using the <code>titling</code> package, but is empty otherwise. There are several ways to represent the author and affiliations, especially if using the <code>authblk</code> package, most of which do not result in a sensible <code>\theauthor</code> , so <code>\HTMLAuthor</code> is useful to create a list of authors without their affiliations.
<code>\HTMLDescription</code> Default: <code><empty></code>	\HTMLDescription: $\{\langle description \rangle\}$ Sets the HTML description tag for the following files. May be changed before each sectioning command which would cause a file split.
<code>\HTMLPageTop</code> Default: <code><empty></code>	\HTMLPageTop: $\{\langle contents \rangle\}$ A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. <code>\LinkHome</code> may be used to place a link back to the homepage, as well as <code>\LinkPrevious</code> and <code>\LinkNext</code> . Ignored in print output.
<code>\HTMLPageBottom</code> Default: <code><empty></code>	\HTMLPageBottom: $\{\langle contents \rangle\}$ A user-definable custom action applied to the bottom of pages other than the home page. Useful for authors, copyright notices, contact information, etc. Defaults empty. <code>\LinkHome</code> may be used to place a link back to the homepage, as well as <code>\LinkPrevious</code> and <code>\LinkNext</code> . Ignored in print output.
<code>\LinkHome</code>	\LinkHome: Creates a link to the home page. Usually used in <code>\HTMLPageTop</code> and related.
<code>\LinkPrevious</code>	\LinkPrevious: Creates a link to the previous HTML page, unless already at the home page. Usually used in <code>\HTMLPageTop</code> and related.
<code>\LinkNext</code>	\LinkNext: Creates a link to the next HTML page, unless already at the end. Usually used in <code>\HTMLPageTop</code> and related.

Placed in the home page before the first sectioning command which causes a file break:

<code>\tableofcontents</code>  TOC on the homepage!	\tableofcontents: Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage. Links to each chapter/section are provided, as selected by <code>tocdepth</code> .
--	--

Placed in the document wherever necessary:

<code>\ImageAltText</code> Default: <code>image</code>	\ImageAltText: Redefine with <code>\renewcommand</code> . <code>\includegraphics</code> and other images are assigned an HTML alt tag according to <code>\ImageAltText</code> along with <code>\AltTextOpen</code> and <code>\AltTextClose</code> . This text is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “image”, and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following <code>\includegraphics</code> and other images.
<code>\ThisAltText</code>	\ThisAltText: $\{\langle text \rangle\}$ <code>\ThisAltText</code> can be used to assign an HTML alt text attribute to the next image generated by a <code>lateximage</code> , <code>picture</code> , <code>tikzpicture</code> , or any other similar environment which generates an image, or the next SVG math expression. This tag is cleared after use. The tag is also cleared after each MATHJAX expression, in case the user changes between SVG math and MATHJAX.

`\ThisAltText` also may be used to add an HTML title to a reference or hyperlink, such as a `\ref`, `\cref`, `\href`, `\url`, `\hyperref`, or `\hyperlink`. In each case, the alternative text is cleared after use.

`\MathImageAltText`

Default: `math image`

`\MathImageAltText`: Redefine with `\renewcommand`. When creating an svg math image, its HTML alt tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the alt tag is set to `\MathImageAltText`, along with `\AltTextOpen` and `\AltTextClose`, and the image is not reused.

This alt expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “math image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following svg math images.

`\PackageDiagramAltText`

Default: `diagram`

`\PackageDiagramAltText`: Redefine with `\renewcommand`. For many packages, the output is placed inside a `lateximage` with an HTML alt tag set to the package name followed by `\PackageDiagramAltText`. For example:

`(-xy- diagram)`

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “diagram”, and may it be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

`\AltTextOpen`

Default: `(`

`\AltTextOpen`: Redefine with `\renewcommand`.

`\AltTextClose`

Default: `)`

`\AltTextClose`: Redefine with `\renewcommand`. HTML alt text is enclosed by the macros `\AltTextOpen` and `\AltTextClose`, which default to an opening and closing parenthesis.

`\HTMLnewcolumntype`

`\HTMLnewcolumntype`: `\newcolumntype` may not always work with `lwarp` for HTML output, since it often involves `TEX` boxes and fills. To provide a simplified column type for HTML, add `\HTMLnewcolumntype` in addition.

Env `warpprint`

`warpprint`: An environment which is only used while generating print output. Place inside anything which does not apply to HTML and which may cause problems with `lwarp`. If `lwarp` knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won’t have to be placed inside a `warpprint` environment, but unknown packages may cause problems which may be isolated from `lwarp` using this environment.



Do not place anything else on the same line as `\end{warpprint}`. Also do not nest `warpprint` inside itself.

Env `warpHTML`

`warpHTML`: An environment which is only included while generating HTML output. This is useful for website logos and other items which have no purpose in printed output.



Do not place anything else on the same line as `\end{warpHTML}`. Also do not nest `warpHTML` inside itself.

`\warpprintonly`

`\warpprintonly`: `{<contents>}` A macro version of the `warpprint` environ-

ment.

\warpHTMLonly

\warpHTMLonly: `{<contents>}` A macro version of the warpHTML environment.

7.6.1 Example HTML file naming

Examples of ways to name or number HTML files:

Numbered HTML nodes:

Example: Homepage `index.html`, and `node-1`, `node-2`.¹³

```
\usepackage[
  HomeHTMLFilename=index,
  HTMLFilename={node-}
]{lwarp}
\boolfalse{FileSectionNames}
```

Named HTML sections, no prefix:

Example: `index.html`, and `About.html`, `Products.html`

```
\usepackage[
  HomeHTMLFilename=index,
  HTMLFilename={}
]{lwarp}
\booltrue{FileSectionNames}
```

Named HTML sections, with prefix:

Example: Homepage `mywebsite.html`, and additional pages such as `mywebsite-About.html`, `mywebsite-Products`, etc.

```
\usepackage[
  HomeHTMLFilename=mywebsite,
  HTMLFilename={mywebsite-}
]{lwarp}
\booltrue{FileSectionNames}
```

7.7 Customizing the css

\CSSFilename

Default: `lwarp.css`

`{<filename>}`

\CSSFilename may be used to choose which .css file is used to display each page of the web site. Use \CSSFilename before \begin{document} to assign the style of the home page. If different parts of the website should have different styles, call \CSSFilename again before each section heading which creates a new file. This may be changed numerous times throughout the file, resulting in different HTML pages having different css files assigned:

¹³See \SetHTMLFileNumber to number in groups by chapter, for example.

```

...
\CSSFilename{myCSS.css}
\chapter{Another Chapter}
...

```

The styles provided by `lwarp` include:

lwarp.css: A default style if `\CSSFilename` is not used. This style is comparable to a plain \LaTeX document. To set this style, you may use `\CSSFilename{lwarp.css}`, or no `\CSSFilename` call at all.

lwarp_formal.css: A formal style with a serif fonts and a traditional look.

lwarp_sagebrush.css: A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the `\CSSFilename` entry in the tutorial, `lwarpmk.html` again, and then reload the tutorial webpage.

Custom css A customized style may also be created. For each new project a file called `sample_project.css` is generated. This may be renamed to `<project>.css` then used by assigning `\CSSFilename{<project>.css}`.



Rename it!

Note that `sample_project.css` is overwritten whenever `lwarp` is loaded in print mode. It is therefore important to rename the file to something like `<project>.css` before using it, so that your own changes are not overwritten.

`<project>.css` has an entry which loads `lwarp.css`, and this entry may be changed to load `lwarp_formal.css` or `lwarp_sagebrush.css` if desired. Additional changes to the css may be made by making entries later in the `<project>.css` file.

It is best to make a local project-specific css file such as `project.css`, containing only things which are different from `lwarp.css`. The file `project.css` should refer to `lwarp.css` as follows:

```

File lwarp.css
File project.css
File sample_project.css

-----
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
-----

```

Finally use `\CSSFilename{<project>.css}` in the document to activate the custom css.

7.8 Assigning css classes and styles

HTML CSS classes and styles may be assigned to fragments of the document.

Env BlockClass

$$[\langle style \rangle] \{ \langle class \rangle \}$$

An entire block of text, including paragraphs, may be assigned a CSS class and optional CSS style using the BlockClass environment. The result is placed inside a `<div>`. A BlockClass may nest other BlockClasses or \InlineClasses.

\InlineClass

$$(\langle wp\ css\ style \rangle) [\langle web\ css\ style \rangle] \{ \langle css\ class \rangle \} \{ \langle text \rangle \}$$

A section of text without paragraphs may be assigned a CSS class and optional CSS style using the \InlineClass macro. The result is placed inside a ``. \InlineClass may be nested, but per the HTML standard it must not contain BlockClass, nor may it contain a paragraph, nor several other objects such as HTML figures. \InlineClass also accepts a second optional parameter, enclosed inside parentheses, which assigns the style while generating output for a word processor, while ignoring the web style.

Nullified versions of BlockClass and \InlineClass are provided for the print version, so they may be used in the document without placing them inside `warpHTML` or `\warpHTMLonly`.

7.9 Selecting the operating system

Prog Unix

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as “UNIX” in the configuration files), and MS-WINDOWS is supported as well.

Prog Mac OS

Prog Linux

Prog MS-Windows

If MS-WINDOWS is not correctly detected, use the lwarp option OSWindows.

Prog Windows

Opt OSWindows

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean `usingOSWindows` is set true. This boolean may be tested by the user for later use.

7.10 Selecting actions for print, HTML, or MATHJAX output

The following environments and macros are used to select actions which only apply to either traditional L^AT_EX print-formatted PDF generation, or to HTML generation, or to HTML with MATHJAX.

For most of built-in L^AT_EX and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which lwarp does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

Env warpHTML

Anything which is to be done only for HTML5 output is surrounded by a warpHTML environment:

```
\begin{warpHTML}
... something to be done only during \HTML\ generation
\end{warpHTML}
```

 `\end{warpHTML}` Do *not* place anything else on the same line as `\end{warpHTML}`. The exact phrase is used to mark the end of the environment. Do not nest `warpHTML` inside itself. `warpMathJax` may be used inside `warpHTML`.

 **nesting**

Env `warpprint` Anything which is to be done only for print output is surrounded by a `warpprint` environment:

```
\begin{warpprint}
... something to be done only during traditional \PDF\ generation
\end{warpprint}
```

 `\end{warpprint}` As above, do not place anything else on the line with `\end{warpprint}`. Do not nest `warpprint` inside itself.

 **nesting**

Env `warpall` Anything which is to be done for any output may be surrounded by a `warpall` environment. Doing so is optional.

```
\begin{warpall}
... something to be done during print \PDF\ or \HTML\ output
\end{warpall}
```

 `\end{warpall}` As above, do not place anything else on the line with `\end{warpall}`. Do not nest `warpall` inside itself.

 **nesting**

Macros are also provided for print-only or HTML-only code:

`\warpprintonly` `{\actions}`

Performs the given actions only when print output is being generated.

`\warpHTMLonly` `{\actions}`

Performs the given actions only when HTML output is being generated.

Env `warpMathJax` Anything which is to be done only while using HTML output with MATHJAXIS surrounded by a `warpMathJax` environment. Usually, this is `\CustomizeMathJax`, used to add emulation macros. `\end{warpMathJax}` must appear on its own line. Do not nest `warpMathJax` inside itself. `warpMathJax` may be used inside `warpHTML`.

 `\end{warpMathJax}`

 **nesting**

Env `warpsvg` Anything which is to be done only while using print output or HTML output with SVG math is surrounded by a `warpsvg` environment. `\end{warpsvg}` must appear on its own line. Do not nest `warpsvg` inside itself. `warpsvg` may be used inside `warpHTML`.

 `\end{warpsvg}`

 **nesting**

`\LWR@formatted` To define macros or environments which behave differently depending on print or HTML output, see section 36.

7.11 Commands to be placed into the `warpprint` environment

Certain print-related commands should always be placed inside a `warpprint` environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: `\parindent` `\parskip`
- Manual page positions such as the `textpos` package, which is emulated but only in a limited way.
- Anything changing the page counter. `lwarp` requires that the page counter not be adjusted during HTML output.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 13: [Troubleshooting](#).

7.12 Title page

In the preamble, place an additional block of code to set the following:

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
       Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

The title is used in the meta tags in the HTML files, unless overridden by `\HTMLTitle`, and the rest are used in `\maketitle`. To use a `\subtitle` or `\published` field, see section 69.8.

<code>\maketitle</code>	Use <code>\maketitle</code> just after the <code>\begin{document}</code> , as this will establish the title of the homepage. Optionally, use a <code>titlepage</code> environment instead.
Env <code>titlepage</code>	The <code>titlepage</code> environment may be used to hold a custom title page. The <code>titlepage</code> will be set in a <code><div></code> class <code>titlepage</code> , and <code>\printtitle</code> , etc. may be used inside this environment.
Env <code>titlingpage</code>	Another form of custom title page, where <code>\maketitle</code> is allowed, and additional information may be included as well.
<code>\title</code>	<code>{<title>}</code>
 HTML corrupted  newlines	Avoid newlines in the <code>\title</code> ; these will interfere with the file break and CSS detection. Use a <code>\subtitle</code> command instead (section 69.8). The title will appear in the document <code>\maketitle</code> as a heading <code><h1></code> . The HTML meta title tag will also have this title, unless <code>\HTMLTitle</code> is used to set the meta title to something else instead.
<code>\author</code>	<code>{<author>}</code>
	In <code>\author</code> , <code>\protect</code> may be needed before some formatting commands. In HTML, the author will appear in a <code><div></code> of class <code>author</code> in the <code>\maketitle</code> . If the <code>titling</code> package is used, the author will also appear in a HTML meta tag, but <code>\HTMLAuthor</code> may be necessary to create a plain list of names if <code>\author</code> had affiliations added. <code>\affiliation</code> is a new addition to <code>lwarp</code> .
<code>\date</code>	<code>{<date>}</code>

`\date` works as expected. In HTML, this will appear in a `<div>` class titled `date`.

`\thanks` `{\text}`

`\thanks` are allowed in the titlepage fields, and will be rendered as HTML notes at the bottom of the title page.

7.13 HTML page meta descriptions

`\HTMLDescription` `{\text}`

Default: (none)

limitations

Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character (").

placement

Use `\HTMLDescription` just before `\begin{document}` to set the description of the home page, and also just before each sectioning command such as `\chapter` or `\section` where a new file will be generated, depending on `FileDepth`. For example, if `FileDepth` is 1, use `\HTMLDescription` just before each `\section` command, and that description will be placed inside the HTML page for that `\section`. The same description will be used for all following HTML files as well, until reset by a new `\HTMLDescription`. It is best to use a unique description for each HTML file.

disabling

To disable the generation of HTML description meta tags, use:

```
\HTMLDescription{}
```

7.14 HTML homepage meta title

`\HTMLTitle` `{\text}`

Default: `\HTMLtitle{\thetitle}`

Sets the contents of the web page `<meta name="title">` element. May be set empty to cancel the meta title tag.

See section 7.6 for `\HTMLTitleBeforeSection` and `\HTMLTitleAfterSection`, used to set the title for HTML subpages.

7.15 HTML page meta author

`\HTMLAuthor` `{\text}`

Default: `\HTMLAuthor{\theauthor}`

Sets the contents of the web page `<meta name="author">` element. May be set empty to cancel the meta author tag.

`\author` may be used to create a list of authors and their affiliations, in several formats if using `authblk`, and these may not successfully parse properly into a sensible list for `\theauthor`. `\HTMLAuthor` may be used to set the meta tag to a simple list of names.

8 Special cases and limitations

Some commonly-used L^AT_EX expressions should be modified as follows to allow for a smooth conversion to both HTML and print-formatted outputs.

Need help?

See the [General Index](#) for “how-to”, and the [Troubleshooting Index](#) if something doesn’t work. A [Troubleshooting](#) section is also available. The [Index of Objects](#) contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

8.1 Things to avoid

In the document, avoid the following:

 **options with braces** **Package options:** Package options may cause problems with lwarp, especially if they include curly braces.

If selecting options with braces in `\usepackage` does not work:

```
\usepackage[font={it,small}]{caption}% does not work
```

... try instead selecting the package options before loading lwarp:

```
\PassOptionsToPackage{font={it,small}}{caption}
```

```
...
```

```
\usepackage{lwarp}
```

```
...
```

```
\usepackage{caption}
```

... or try setting package options after the package has been loaded:

```
\usepackage{caption}
```

```
\captionsetup{font={it,small}}
```

page counter: Do not adjust the page counter. If doing so is required for the print version, place the adjustment inside a `warpprint` environment.

Custom math environment macros: Do not use expressions such as `\beq` as a replacement for `\begin{equation}`.

Custom macros in section, figure, table names: Custom macros which appear in sectioning commands or float captions then appear in the `.toc`, `.lof`, and `.lot` lists, and should be made robust using `\newrobustcmd` or `\robustify` from `etoolbox`, `xparse`, etc.

When setting `FileSectionNames` to true to name the HTML files from the section names, the file names are created from sanitized versions of the chapter or section names, but the section names must be plain text or something which expands into plain text. Robust macros will not work at the sectioning level which is used for file names, but a robust macro or other complicated name may be used for the mandatory argument of `\chapter`, `\section`, etc., if a plain-text version is also included in the optional argument:

```
\chapter[Plain Name]{\ARobustMacro{Fancy Name}}
```

8.1.1 Invalid HTML

Additionally, some objects are valid L^AT_EX, but invalid HTML. An example is a tabular inside `\textbf`, since HTML does not allow a table inside a span. lwarp

will create the table, and the browser may support it, but the result is technically invalid.

8.2 Formatting

8.2.1 Text formatting

 **\bfseries, etc.** `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

 **HTML special chars** `&`, `<`, and `>` have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the `listings` package is supported, and its `literate` option is used to convert `&`, `<`, and `>` to proper HTML entities.

verbatim The various verbatim-related environments do not convert `&`, `<`, and `>`, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

8.2.2 Small caps

Bool `FixSmallCaps`

Some fonts, such as `erewhon`, `utopia`, or `fbf`, and some packages such as `embrac`, copy/paste “SMALL CAPS” as all caps (“SMALL CAPS”), which `lwarp` then reads as all caps, so the text is printed in all caps. If small caps are being rendered as all caps, set:

```
\booltrue{FixSmallCaps}
```

 **CJK fonts** Some CJK fonts may not work if `FixSmallCaps` is set true.

8.2.3 Horizontal and vertical space and rules

`\hspace` `\hspace` is converted to an inline HTML span of the given width, except that `0` width is ignored, a width of `.16667em` is converted to an HTML thin breakable space (U+2009), and a `\fill` is converted to a `\quad`.

`\vspace` `\vspace` is ignored for HTML.

`\,` `~` and `\,` are converted to HTML entities.

`\kern` `\hskip` `\kern` and `\hskip` are entered into the HTML PDF output as-is, then interpreted by *pdftotext*, and thus usually appear as a single space.

`\rule` `\rule` is converted to an HTML rule of the same dimensions, of the currently selected text color.

`\hrule` `\vrule` Both `\hrule` and `\vrule` are ignored for HTML. To create a horizontal dividing rule across the page, use `\hrulefill` in its own paragraph.

`\hrulefill` `\hrulefill` usually creates a one-inch rule, similar to a “fill in the blank”. If it

is used at the start of a new paragraph, it creates a `<div>` with a thin horizontal border across the page, as would often be done with `\hrule`.

8.2.4 Text alignment

Use the environments `center`, `flushright`, `flushleft` instead of the macros `\centering`, `\raggedright`, `\raggedleft`.

 **figure & table alignment** `\centering`, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

8.2.5 Accents

Native \LaTeX accents such as `\`` will work, but many more kinds of accents are available when using Unicode-aware \XeLaTeX and \LuaLaTeX . If using accents in section names which will become file names, it is recommended to use the \LaTeX accents such as `\`` and `\v` instead of Unicode accents. The \LaTeX accents will have the accents stripped when creating the filenames, whereas the Unicode accents will appear in the file names, which may cause issues with some operating systems.

8.2.6 textcomp package

Pkg `textcomp`

Some `textcomp` symbols do not have Unicode equivalents, and thus are not supported.

 **missing symbols** Many `textcomp` symbols are not supported by many system/browser fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

8.2.7 Superscripts and other non-math uses of math mode

Use `x` instead of `^{x}`

8.2.8 Empty `\item` followed by a new line of text or a nested list:

[lists](#) Use a trailing backslash: `\item[label] \`

8.2.9 Filenames and URLs in lists or footnotes

[filename underscore](#) Escape underscores in the filenames:

```
\item[\href{file\_name.pdf}]{text}]
```

8.2.10 relsize package

Pkg relsize

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified font-size.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarily restored, and so should work as expected.

 **not small** The HTML browser's setting for minimum font size may limit how small the output will be displayed.

8.3 Boxes and minipages

8.3.1 Marginpars

`\marginpar`

`[\left] \{right\}` `\marginpar` may contain paragraphs, but in order to remain inline with the surrounding text `lwarp` nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `
` tags.

`\marginparBlock`

`[\left] \{right\}` To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a ``. A line break will occur in the text where the `\marginBlock` occurs.

8.3.2 Save Boxes

 **HTML corrupted**

 **boxes**

TeX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. `lwarp` uses methods which help avoid this problem.

 **minipage, \parbox** `\savebox` and related do not (yet) support `minipage` or `\parbox`.

8.3.3 Minipages

 **inline** A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made inline-block.

placement `minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side Side-by-side `minipages` may be separated by `\quad`, `\qqquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a center environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

 **minipage in a span** There is limited support for `minipages` inside an HTML ``. An HTML `<div>` cannot appear inside a ``. While in a ``, `minipages`, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an "inline" format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

⚠ **minipage size** When using `minipage`, `\parbox`, and `fminipage`, a virtual 6×9 inch text area is used for `\linewidth`, `\textwidth`, and `\textheight`, both for sizing the minipage, and also for its contents.

if width is `\linewidth` If a minipage or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML A new macro `\minipagefullwidth` requests that, during HTML output, the next single minipage or `\parbox` be generated without an HTML width attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ **tabular, multicols** Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every minipage or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell lwarp to honor the specified widths of all following minipages and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell lwarp to ignore the specified widths.

`\UseMinipageWidths`
`\IgnoreMinipageWidths`

⚠ **multicol** Inside a `multicols`, `\linewidth` is divided by the specified number of columns.

⚠ **text alignment** Nested minipages adopt their parent's text alignment in HTML, whereas in regular L^AT_EX PDF output they do not. Use a `flushleft` or similar environment in the child minipage to force a text alignment.

8.3.4 Side-by-side minipages

Place side-by-side minipages inside a `center` environment, with horizontal space between them, such as `\quad`, `\qqquad`, `\hspace`, or `\hfill`. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

8.3.5 Framed minipages and other environments

`\fbox` can only be used around inline `` items during HTML output, but HTML cannot place a block element such as a `<div>` for a minipage or a list inside of a ``. Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

`\fbox`
`\fboxBlock`
Env `fminipage`

For a framed object, options include:

To remove the frame in HTML output: Place the `\fbox` command and its closing brace inside `warpprint` environments. This will nullify the frame for HTML output.

For inline text:

To frame the contents inline with some formatting losses in HTML: This is the default action of `\fbox` when enclosing a minipage. During HTML output, `\fbox` nullifies the HTML tags for `minipage`, `\parbox`, and lists. The contents are included as inline text inside the `\fbox`'s `` of class `framebox`. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.

For inline minipage and lists:

To frame the contents on their own line with improved formatting in HTML: A new command `\fboxBlock` is included, intended to be a direct replacement

for `\fbox` for cases where the `\fbox` surrounds a minipage, table, or list. For print output, this behaves as `\fbox`. For HTML output, the contents are placed inside an HTML `<div>` with the class `framed`, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and minipages look nicer, and valid HTML is created for a `tabular`. While an `\fbox` containing a `tabular` is valid L^AT_EX code, the result in HTML is problematic since a table is a `<div>` not a ``, so use `\fboxBlock` around a `tabular`, or else place the `tabular` inside a minipage, or use `fminipage`, described next. Also see below regarding the “Misplaced alignment tab character &.” error.

For display `tabular`,
minipages, and lists:

To create a framed minipage in both print and HTML: A new environment `fminipage` is included. For print output, this is identical to `minipage`, except that it is also framed. For HTML output, this forms a `<div>` of class `framed`, the contents preserve their HTML formatting, and valid HTML is created for a `tabular`. Also see section 89 for a new environment `fcolorminipage`. Also see below regarding the “Misplaced alignment tab character &.” error.

colored boxes and frames:

To create colored frames and boxes: See section 671 for `xcolor`’s `\colorbox` and `\fcolorbox`, and `lwarp`’s additional `\colorboxBlock` and `\fcolorboxBlock`.

⚠ Misplaced alignment
tab character &

To frame tables or verbatim environments: Place the contents inside a `fminipage`, or perhaps a `\fboxBlock` for a `tabular`. Also, if using `\fboxblock` with `tabular`, you will have to use `\StartDefiningTabulars` before the start of the macro which uses `\fboxBlock` and the `tabular`, and `\StopDefiningTabulars` afterwards. Also see the `lwarp` documentation for the `fancybox` package.

To frame equations: See section 259 for the `fancybox` package.

For fancy framed minipages: See packages `boxedminipage`, `shadow`, `fancybox`, `framed`, `mdframed`.

Custom environments: Use a custom environment to create a sidebar, containing a `BlockClass` environment with custom CSS formatting, and `\warpprintonly{\hrule}` command:

```
\begin{BlockClass}{frameminipage}% ignored in print output
  % use \CSS\ to format div class framedminipage
\warpprintonly{\hrule} % only appears in print output
Contents
\warpprintonly{\hrule} % only appears in print output
\end{BlockClass}
```

8.3.6 fancybox package

Pkg fancybox

framed equation example

`fancybox`’s documentation has an example `FramedEqn` environment which combines `math`, `\Sbox`, a `minipage`, and an `\fbox`. This combination requires that the entire environment be enclosed inside a `lateximage`, which is done by adding `\lateximage` at the very start of `FramedEqn`’s beginning code, and `\endlateximage` at the very end of the ending code. Unfortunately, the HTML `alt` attribute is not used here.

```

\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
... }{...
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}

```

framing alternatives `\fbox` works with `fancybox`. Also see `lwarp`'s `\fboxBlock` macro and `fminipage` environment for alternatives to `\fbox` for framing environments.

framed table example The `fancybox` documentation's example of a framed table using an `\fbox` containing a `tabular` does not work with `lwarp`, but the `FramedTable` environment does work if `\fbox` is replaced by `\fboxBlock`. This method does lose some HTML formatting. A better method is to enclose the table's contents inside a `fminipage` environment. The caption may be placed either inside or outside the `fminipage`:

```

\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
...
\end{tabular}
\end{fminipage}
\end{table}

```

⚠ framed verbatim `lwarp` does not support the `verbatim` environment inside a `span`, `box`, or `fancybox`'s `\Sbox`, but a `verbatim` may be placed inside a `fminipage`. The `fancybox` documentation's example `FramedVerb` may be defined as:

```

\newenvironment{FramedVerb}[1] % width
{
\VerbatimEnvironment
\fminipage{#1}
\beginVerbatim
}{
\endVerbatim
\endfminipage
}

```

framed \VerbBox `fancybox`'s `\VerbBox` may be used inside `\fbox`.

indented alignment `LVerbatim`, `\LVerbatimInput`, and `\LUseVerbatim` indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

8.3.7 mdframed package

Pkg mdframed

support Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for `mdframed` environments and frame titles.

⚠ loading When used, `lwarp` loads `mdframed` in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the `mdframed` source). Since `lwarp` does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont `theoremtitlefont` is not supported, since the following text is not in braces in the `mdframed` source.

ignored options `userdefinedwidth` and `align` are currently ignored.

css classes Environments created or encapsulated by `mdframed` are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class `|mdframedtitle|`. Subtitles are in a `<div>` of class `|mdframedsubtitle|`, and likewise for subsubtitles.

8.3.8 tcolorbox package

Pkg `tcolorbox`

`tcolorbox` is emulated for `HTML` and `MATHJAX`, and supported as-is inside a `lateximage` or `SVG math`.

What has been tested to work (at least partly) includes:

- `tcolorbox`, `\tcbox`.
- Title, subtitle.
- Upper, lower parts.
- Colors and title fonts.
- Floating objects.
- Some layered box features.
- Counters, labels, references.
- `listings`, `listingsutf8`.
- theorems: Theorems are supported. `math`, `ams equation`, etc. are not supported. Use a `tcolorbox` with regular `math` inside it. `\tcboxmath` and `\tcbhighmath` are supported in `SVG math`, and emulated in `MATHJAX`.
- Fitting features: `\tcboxfit` becomes `\tcbox` in `HTML`.
- Footnote numbering does not match the printed output.
- `MATHJAX` emulation is provided for common macros.

 **math**

 **footnotes**

 **undefined references** If using `cleveref`, it may be necessary to name theorems such as:

```
\crefname{tcb@cnt@mytheo}{my theorem}{my theorems}
```

8.4 Section names

If using named `HTML` files, by selecting `\booltrue{FileSectionNames}`, the generated filenames may be simplified by using `\FilenameSimplify` and `\FilenameNullify`:

`\FilenameSimplify`

```
{<text>}
```

To remove common short words from the automatically-generated filenames, replacing each with a single hyphen “-”, use `\FilenameSimplify`:

```
\FilenameSimplify*{-in-}
\FilenameSimplify*{A-}
```

The first example removes the word “in” in the middle of a filename, and the second example removes “A” at the start of the filename. The star forces the arguments to be detokenized, which is required for a plain-text comparison. (The unstarred form is used for a token-sensitive comparison, which is seldom required by the user.) After simplification, repeated hyphen characters will be further simplified to a single hyphen “-”. Finally, single hyphens at the start or end of the filename are removed.

`\FilenameNullify` `{\<macros>}`

 **macros in section names** Macro names may appear in the automatically-generated file names. To remove these, create *non-robust* nullified versions of the macros, ensuring that each line ends with a percent character % as shown below. These are placed inside `\FilenameNullify`, which adds them to the list of macros which are nullified during filename generation. Low-level macros such as `\begingroup` will cause problems when nullified. Many macros such as `\textbf` are already nullified. `lwarp` also already nullifies built-in symbol and `textcomp` macros, including if defined by `xunicode`, but not all `xunicode` macros. See the definition of `\LWR@nullfonts` for a complete list.

```
\FilenameNullify{%
  \renewcommand*{\macroname}[1]{#1}%
  \renewcommand*{\anothermacro}{}%
}
```

 **duplicate filename** Avoid duplicate file names. Section names at levels which result in HTML file splits must be unique. `lwarp` will generate an error if a duplicate HTML filename is generated. Use the optional TOC caption entry parameter for formatting. Remember to `\protect` L^AT_EX commands which appear in section names and TOC captions.

 **math in section names** If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring` from the `hyperref` package:

```
\section{Some math \texorpdfstring{$1+2=3$}{three}}
```

8.5 Cross-references

 **label characters** labels Labels with special characters may be a problem. It is best to stick with alphanumeric, hyphen, underscore, and perhaps the colon (if not French).

 **empty link** \nameref `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

8.5.1 Page references

 **L^AT_EX page numbers** The printed page does not translate to the HTML page, so `\pageref` references are converted to parentheses containing `\pagerefPageFor`, which defaults to “see”, followed by a hyperlink to the appropriate object.

Ex:

```
\ref{sec:name} on page \pageref{sec:name}
in HTML becomes:
“Sec. 1.23 on page (see sec. 1.23)”.
```

`\pagerefPageFor` may be redefined to “page for”, empty, etc. See page 498.

8.5.2 `cleveref` and `varioref` packages

Pkg `cleveref`

Pkg `varioref`

`cleveref` and `varioref` are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

 **cleveref page numbers**

Ex:

```
\cpageref{tab:first,tab:second}
in html becomes:
“pages for table 4.1 and for table 4.2”
```

See `\cpagerefFor` at page 730 to redefine the message which is printed for page number references.

 **varioref types** `cleveref` changes the behavior of `varioref` in that the reference type is automatically printed if `cleveref` is loaded. `Lwarp` requires `cleveref`, so the HTML version will always automatically print the reference types even if the print mode does not. The simplest way to make them match is to require the `cleveref` package for the document.

8.5.3 Hyperlinks, `hyperref`, and `url`

Pkg `hyperref`

Pkg `url`

`lwarp` emulates `hyperref`, including the creation of active hyperlinks, but does not require that `hyperref` be loaded by the document.

 **comments between arguments** Do not place a comment with a % character between arguments for `\hyperref`, etc., as it is neutralized for inclusion in HTML URLs.

`lwarp` can also load `url`, but `url` should not be used at the same time as `hyperref`, since they both define the `\url` command. `lwarp` does not (yet) attempt to convert `url` links into hyperlinks during HTML output, nor does the print version of `url` create hyperlinks.

 **backref** When generating HTML, `lwarp`'s emulation of `hyperref` does not automatically load `backref`, so `backref` must be loaded explicitly.

8.5.4 Footnotes, endnotes, and page notes

lwarp uses native L^AT_EX footnote code, although with its own `\box` to avoid the L^AT_EX output routine. The usual functions mostly work as-is.

footnote numbering To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For `bigfoot`, `manyfoot`, or `perpage`:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

MATHJAX Also for MATHJAX, `\footnotename` is used for a `\footnotemark` if the actual footnote number is not known. To redefine it, provide it before loading `lwarp`:

```
\providecommand{\footnotename}{something}
\usepackage{lwarp}
```

Similar for sidenotes. For endnotes:

```
\def\endnotename{something}% \def allows name to start with
"end"
```

For the `pagenote` package, there is no `\pagenotename` to define, since there is no `\pagenotemark` command.

footmisc The `footmisc stable` option is emulated by `lwarp`.

 **sectioning commands** When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the `footmisc` package with the `stable` option, provide a short TOC entry, and `\protect` the `\footnote`:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
{Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc If using `memoir` class, with which `lwarp` preloads `footmisc`, the `stable` option must be declared before `lwarp` is loaded:

 **memoir**

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

fancybox, fancyvrb

 **\VerbatimFootnotes** If using `fancybox` or `fancyvrb` with `\VerbatimFootnotes`, and using footnotes in a

 **sectioning or displaymath**

```
\subsection[Subsection Name]
{Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbatim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

[pfnote](#)
 ⚠ [pfnote numbers](#)

While emulating `pfnote`, `lwarp` is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. `lwarp` therefore uses continuous footnote numbering even for `pfnote`.

[bigfoot, manyfoot](#)
 ⚠ [verbatim](#)

Verbatim footnotes are not yet supported.

If using the `bigfoot` package, and possibly also `manyfoot`, problems may occur with counter allocation because `lwarp` uses many counters, and there is a difference in how counters numbered 256 and up are handled in PDF L^AT_EX. With `bigfoot` this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining `bigfoot` or `manyfoot` footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use X_EL^AT_EX or LuaL^AT_EX instead of PDF L^AT_EX.

8.5.5 `xr`, `xr-hyper`, and `xcite` packages

See section [5.17](#).

8.6 Front and back matter

8.6.1 Custom classes with multiple authors and affiliations

Some classes allow multiple authors and affiliations. Often it is possible to emulate these using a standard class along with `authblk`:

```
%\documentclass{customclass} % for print document
\documentclass{article} % for html document

\usepackage{lwarp}
\begin{warpHTML}
\usepackage{authblk}
\let\affiliation\affil % maybe required
\end{warpHTML}
```

8.6.2 Starred chapters and sections

[HTML page and TOC](#)

The following describes `\ForceHTMLPage` and `\ForceHTMLTOC`, which may be used for endnotes, glossaries, `tocbibind`, bibliographies, and the index. See the following sections where applicable. Continue here if interested in the reason for adding these commands to `lwarp`.

Some packages use `\chapter*` or `\section*` to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own HTML pages, and they are not given TOC entries.

lwarp provides a method to cause a starred section to be on its own HTML page, subject to `FileDepth`, and also a method to cause the starred section to have its own TOC entry during HTML output.

`\ForceHTMLPage`

To place a starred section on its own HTML page, use `\ForceHTMLPage` just before the `\chapter*` or `\section*`. lwarp will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using `\phantomsection` and `\addcontentsline` works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created, or when creating an EPUB where the TOC entry will point to the page before the starred section. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is created.

⚠ inaccessible HTML page

`\ForceHTMLTOC`

To automatically force the HTML version of the document to have a TOC entry for a starred section, use `\ForceHTMLTOC` just before the `\chapter*` or `\section*`, and place `\phantomsection` and `\addcontentsline` inside a `warpprint` environment.

For print output, `\ForceHTMLTOC` and `\ForceHTMLPage` have no effect.

8.6.3 abstract package

Pkg abstract

⚠ missing TOC

If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

8.6.4 titling and authblk

Pkg titling

Pkg authblk

package support

⚠ load order
`\published` and `\subtitle`

lwarp supports the native L^AT_EX titling commands, and also supports the packages `authblk` and `titling`. If both are used, `authblk` should be loaded before `titling`.

If using the `titling` package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 69.8.

8.6.5 tocloft package

Opt [tocloft] titles

Pkg tocloft

Pkg tocloft

⚠ tocloft & other packages

If using `tocloft` with `tocbibind`, `anonchp`, `fncychap`, or other packages which change chapter title formatting, load `tocloft` with its `titles` option, which tells `tocloft` to use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

8.6.6 appendix package

Pkg appendix During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and `also page` at the same time.

 **incorrect TOC link**

8.6.7 pagenote package

Pkg pagenote `pagenote` works as-is, but the `page` option is disabled.

 **labels** Note that labels in page notes do not appear as expected, even in the print version.

8.6.8 endnotes package

Pkg endnotes To place the endnotes in the TOC, use:

[table of contents](#)

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

[HTML page](#) To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

 **\endnotemark numbering** If using `MATHJAX`, see section 8.5.4 regarding the use of `\endnotemark` and `\endnotetext`.

8.6.9 BibTeX

`\etalchar` Displays a superscript “+” to indicate “and others”.

 **Modify *.bib** When enough authors are cited for a source, `BIBTEX` may use the `\etalchar` command to display a math superscript with a + character to indicate “and others”. Without modification, this will result in an “Improper `\prevdepth`” error. At present, `lwarp` requires that `\etalchar` be replaced by a text superscript. To do so, add to the start of the `.bib` file the following:

```
@PREAMBLE{"\let\etalchar\relax \newcommand{\etalchar}[1]{\textsuperscript{#1}}}
```

8.6.10 xcite package

See section 5.17.

8.6.11 gloss package

Pkg gloss To process the HTML glossary:

 **compiling** `bibtex <projectname>_html.gls`

8.6.12 glossaries package

Pkg glossaries

[processing glossaries](#)

Opt GlossaryCmd

Default: `makeglossaries`

Opt [lwarpmk] `printglossary`

Opt [lwarpmk] `htmlglossary`

lwarpmk has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the `glossaries` package using that package's *makeglossaries* program.

The shell command to execute is set by the `lwarp` option `GlossaryCmd`, which defaults to `makeglossaries`. The print or HTML glossary filename is appended to this command.

⚠ ***makeglossaries* not found**

In some situations it may be required to modify the default command, such as to add the `perl` command in front:

```
\usepackage[
  GlossaryCmd={perl makeglossaries},
] {lwarp}
```

[xindy language](#)

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
  GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

[placement and toc options](#)

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection= nolabel]{glossaries}
...
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
...
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries
```

⚠ ***glossary style***

The default `style=item` option for `glossaries` conflicts with `lwarp`, so the style is forced to `index` instead.

⚠ ***number list***

The page number list in the printed form would become `\namer{efs}` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

[print/HTML versions](#)

The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

8.6.13 nomencl package

Pkg nomencl

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o
<project>_html.nls
```

8.6.14 Indexing overview

There are many ways to process indexes for a L^AT_EX document, including native L^AT_EX capabilities, a number of packages and classes, the possible availability of shell escape and *latexmk*, and the need to process print and HTML versions. *lwarp* attempts to provide easy recompilation of indexes along with the rest of the document, but the various indexing options must be set correctly. Numerous examples are given below. Some differ in minor details, so the important parts are highlighted in red, and options are in green.

Once set up properly, the entire document may be recompiled with **lwarpmk print** and **lwarpmk html**. In some cases, it will also be necessary to compile the indexes with **lwarpmk printindex** and **lwarpmk htmlindex**. A recompile may then be forced with **lwarpmk print1** and **lwarpmk html1**.

- [manual processing](#) The user may continue to process indexes manually or by shell script without the use of *lwarpmk*, but adjustments will be required to process HTML indexes as well. In general, *.idx and *.ind files will be accompanied by *_html.idx and *_html.ind files.
- [custom index style](#) If using a custom indexing style file, see sections 8.6.20 to 8.6.22.
- [link appearance](#) To control how the index links appear in the HTML output, see the IndexRef option in section 7.5, page 105.
- [source code](#) See section 79 for *lwarp*'s core index and glossary code, section 340 for index, section 571 for splitidx, section 338 for imakeidx, section 625 for tocbibind, and section 692.17 for memoir's indexing patches.

8.6.15 Indexing with makeidx, makeindex, xindy, xindex, gindex

- [lwarpmk processing](#) The following allow the user to process indexes automatically, or using *lwarpmk*'s commands:

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

Prog makeindex

For a single index using *makeindex*:

```
\usepackage[makeindex,latexmk]{lwarp}
```

The usual .idx and .ind files will be used, along with the new lwarp.ist style file. When creating the HTML index, “_html” is automatically appended to each of the names.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

```
Enter ⇒ lwarpmk printindex
```

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

To use a custom configuration file, see section 8.6.20.

Prog xindy

For a single index using *xindy*:

```
\usepackage[
  xindy,
  xindyLanguage=english,
  xindyCodepage=utf8,
  latexmk
]{lwarp}
<optional>
<optional>
<optional>
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

To use a custom configuration file, see section 8.6.21.

Prog xindex

For a single index using *xindex*:

```
\usepackage[
  xindex,
  latexmk
]{lwarp}
<optional>
```

The usual `.idx` and `.ind` files will be used.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

To use a custom configuration file, see section 8.6.22.

Pkg gindex

For a single index using *gindex*:

```
\usepackage[
  makeindex,
  makeindexStyle=gindex.ist,
  ... or ...
  makeindexStyle=gindexh.ist,
  latexmk
]{lwarp}
<optional>
```

The usual `.idx` and `.ind` files will be used.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

To use a custom configuration file, copy `gindex.ist` to a new file, modify, then specify it with `MakeindexStyle` as above. *lwarp* will automatically adapt to *gindex*'s `\indexpagesep` and `\indexrangesep` settings.

8.6.16 Indexing with index

Prog index

lwarp is told how to use *makeindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

For multiple indexes using *makeindex* and *index*:

(Assuming that the second index has file extensions `.sist` and `.sind`)

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist
      -o <projectname>.sind <projectname>.sidx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist
      -o <projectname>_html.sind <projectname>_html.sidx
  }
]{lwarp}
\usepackage{index}
...
\makeindex
\newindex{secondname}{sidx}{sind}{Second Index}
```

⚠ WINDOWS

For Windows, replace the two “;” characters with “&”.

When creating the HTML index, “_html” is automatically appended to the index filenames.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

If the `latexmk` option is selected for `lwarp`, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

8.6.17 Indexing with splitidx

Prog splitidx

lwarp is told how to use *splitindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

If the `latexmk` option is selected for `lwarp`, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

⚠ \thepage When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer

to `\thepage` during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the `\index`-like action occurs, and then refer to `\arabic{LWR@autoindex}` instead of `\thepage` where the reference should occur.

See section 692.17 in the `lwarp-patch-memoir` package for the `\@@wrspindexhyp` macro as an example.

For multiple indexes using *makeindex* and *splitidx*:

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    splitindex <projectname> -- -s lwarp.ist
  },
  HTMLIndexCmd={
    splitindex <projectname>_html -- -s lwarp.ist
  }
]{lwarp}
\usepackage{splitidx}
...
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, “_html” is automatically appended to each of the names.

Use

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

For multiple indexes using *xindy* and *splitidx*:

```
\usepackage[
  xindy, latexmk,
  PrintIndexCmd={
    splitindex -m xindy <projectname> -- -M lwarp.xdy
    -L english -C utf8 <optional>
  },
  HTMLIndexCmd={
    splitindex -m xindy <projectname>_html -- -M
    lwarp.xdy
    -L english -C utf8 <optional>
  }
]{lwarp}
\usepackage{splitidx}
...
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, “_html” is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

8.6.18 Indexing with imakeidx

Prog imakeidx

Due to the number of methods which may be used to process multiple indexes, the options for style file and *xindy* language and codepage must be specified in one of several different ways. These are described in detail later in this section, but are summarized here.

If shell escape is used, *imakeidx* will automatically compile the indexes by itself. Options specifying a custom style file and *xindy* language and codepage must be specified for each `\makeindex` command using its `options=` option, which must include *lwarp*'s special `lwarp.ist` or `lwarp.xdy` file, or a file based on them. If using a custom indexing style file, see sections 8.6.20 to 8.6.22.

The `splitindex` option is also available if shell escape is used, in which case the `splitidx` package and *splitindex* program will also be used.

If shell escape is not possible, *latexmk* may be used to automatically compile the indexes. The style, language, and codepage options are specified with *lwarp*'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options. These are passed to *latexmk* by *lwarpmk*'s **lwarpmk printindex** and **lwarpmk htmlindex** commands.

Where shell escape and *latexmk* are not possible, *lwarpmk* may be used to manually compile the indexes. *lwarp*'s `PrintIndexCmd` and `HTMLIndexCmd` options are used.

For a single or multiple indexes using *makeindex* and *imakeidx*:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

imakeidx will automatically compile the indexes. Shell escape is not required while using *makeindex*. *latexmk* may be specified, and if so it will be used for **lwarpmk print** and **lwarpmk html**, but *imakeidx* will actually create the indexes.

For a single or multiple indexes using *makeindex* and *splitindex* with *imakeidx*:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```

\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]

```

 enable shell escape

Shell escape is required while using *splitindex*. For the first compile, use

```
Enter ⇒ pdflatex --shell-escape projectname.tex
```

```
Enter ⇒ pdflatex --enable-write18 projectname.tex (MiKTeX)
```

or similar with *xelatex* or *lualatex*. *lwarp* will remember that shell escape was used.

imakeidx will automatically execute *splitindex*, and will also use *makeindex* to compile the indexes.

latexmk may be specified, and if so it will be used for **lwarpmk print** and **lwarpmk html**, but *imakeidx* will actually create the indexes.

For multiple indexes using *xindy* and *imakeidx*, using shell escape:

Options may be given to *imakeidx*'s `\makeindex` command. The style file `lwarp.xdy` is automatically used for HTML output, and is not necessary for print output since the output will be similar. If language or codepage must be set, they should be specified as options for `\makeindex`, since *imakeidx* will process the indexes.

```

\usepackage[xindy,latexmk] {lwarp}
\usepackage[xindy,splitindex]{imakeidx}
. . .
\makeindex[
  options={ -M lwarp.xdy -L english -c utf8 }
]
\makeindex[
  name=secondname,
  options={ -M lwarp.xdy -L english -c utf8 }
]

```

 enable shell escape

For the first compile, use

```
Enter ⇒ pdflatex --shell-escape projectname.tex
```

```
Enter ⇒ pdflatex --enable-write18 projectname.tex (MiKTeX)
```

or similar with *xelatex* or *lualatex*. *lwarp* will remember that shell escape was used.

imakeidx will automatically execute *splitindex* if selected, and will also use *xindy* to compile the indexes.

If selected, *latexmk* will automatically recompile the entire document as necessary.

For indexes using *xindy* and *imakeidx*, without shell escape, but *with latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\usepackage[
  xindy,
  xindyLanguage=english,           <optional>
  xindyCodepage=utf8,             <optional>
  latexmk,
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

latexmk will create the indexes automatically when **lwarpmk print** and **lwarpmk html** are executed.

For indexes using *xindy* and *imakeidx*, without shell escape, and *without latexmk*:

lwarpmk must be told how to create the indexes:

```
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
    <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
    secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
    <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
    secondname_html.idx
  }
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

⚠ WINDOWS

For Windows, replace the two “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name_html.idx.

Use

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

For multiple indexes using *xindex* and *imakeidx*, using shell escape:

xindex, *makeindex*, *imakeidx*, and *splitindex* can all work together:

```

\usepackage[%
  xindex,
  xindexConfig=-imakeidx,
  latexmk
] {lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
. . .
\makeindex[%
  options={ -s lwarp.ist} }
]
\makeindex[
  name=secondname,
  options={ -s lwarp.ist} }
]

```

⚠ enable shell escape

For the first compile, use:

```
Enter ⇒ pdflatex --shell-escape projectname.tex
```

```
Enter ⇒ pdflatex --enable-write18 projectname.tex (MiKTeX)
```

or similar with *xelatex* or *lualatex*. *lwarp* will remember if shell escape was used.

xindex will use *imakeidx*, and *imakeidx* will automatically execute *splitindex* if selected.

If selected, *latexmk* will automatically recompile the entire document as necessary.

8.6.19 Indexes with memoir

For a single index with memoir and *makeindex*:

```

\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex

```

The usual *.idx* and *.ind* files will be used, along with the *lwarp.ist* style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

For multiple indexes with memoir and *makeindex*, using *latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```

\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
\makeindex[secondname]

```

lwarpmk will use *latexmk* to create the indexes automatically when the user executes *lwarpmk print* and *lwarpmk html*.

For multiple indexes with memoir and *makeindex*, without latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  makeindex,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist secondname.idx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist secondname_html.idx
  }
]{lwarp}
...
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS

For Windows, replace the two “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name_html.idx.

Use

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

For a single index with memoir and *xindy*:

```
\documentclass{memoir}
\usepackage[
  xindy,
  xindyLanguage=english,           <optional>
  xindyCodepage=utf8,             <optional>
  latexmk                          <optional>
]{lwarp}
...
\xindyindex
\makeindex
```

The usual .idx and .ind files will be used, along with the lwarp.xdy style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

For multiple indexes with memoir and *xindy*, using latexmk:

lwarp's options are used, and are passed to *latexmk*.

```

\documentclass{memoir}
\usepackage[
  xindy,
  xindyLanguage=english,           <optional>
  xindyCodepage=utf8,             <optional>
  latexmk
]{lwarp}
. . .
\xindyindex
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically.

For multiple indexes with memoir and *xindy*, without latexmk:

lwarpmk must be told how to create the indexes:

```

\documentclass{memoir}
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
    <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
    secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
    <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
    secondname_html.idx
  }
]{lwarp}
. . .
\xindyindex
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS

For Windows, replace the four “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name_html.idx.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

8.6.20 Using a custom *makeindex* style file

When using *makeindex*, *lwarpmk* uses the file `lwarp.ist` to process the index. This file is over-written by *lwarp* whenever a print version of the document is processed.

To use a custom *makeindex* style file:

Prog makeindex
File lwarp.ist

1. Copy `lwarp.ist` to a new filename such as `projectname.ist`
2. Make changes to `projectname.ist`. Keep the lines which refer to `\hyperindexref`. These lines creates the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

3. If changing

```
delim_n -and- delim_r
```

in `projectname.ist`, then in the document preamble redefine

```
\IndexPageSeparator -and- \IndexRangeSeparator
```

to match.

Opt `makeindexStyle`

4. In the document source use the `makeindexStyle` option for `lwarp`:

```
\usepackage[
  . . . other options . . .
  makeindex,
  makeindexStyle=projectname.ist,
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

5. Recompile the print version, which causes `lwarp` to rewrite the `lwarpmk.conf` configuration file. This tells `lwarpmk` to use the custom `projectname.ist` file instead of `lwarp.ist`.

8.6.21 Using a custom *xindy* style file

Prog `xindy`

File `lwarp.xdy`

When using *xindy*, `lwarpmk` uses the file `lwarp.xdy` to process the index. This file is over-written by `lwarp` whenever a print version of the document is processed.

To use a custom *xindy* style file:

1. Copy `lwarp.xdy` to a new filename such as `projectname.xdy`
2. Make changes to `projectname.xdy`.

Keep the lines which refer to `\hyperindexref`:

```
(define-attributes (("hyperindexref"))
(markup-locref :open "\hyperindexref{" :close "}")
. . .
(markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
```

These lines create the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

To create custom styles, refer to the lines for `\textbf` and `\textit`.

3. If changing any of

```
markup-locref-list :sep
markup-locclass-list :open
markup-locclass-list :sep
markup-crossref-layer-list :sep
markup-range :sep
```

in `projectname.xdy`, then in the document preamble redefine

```
\IndexPageSeparator -and- \IndexRangeSeparator
```

to match.

Opt `xindyStyle`

4. In the document source use the `xindyStyle` option for `lwarp`:

```
\usepackage[
  ... other options ...
  xindy,
  xindyStyle=projectname.xdy,
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

5. Recompile the print version, which causes `lwarp` to rewrite the `lwarpmk.conf` configuration file. This tells `lwarpmk` to use the custom `projectname.xdy` file instead of `lwarp.xdy`.

8.6.22 Using a custom *xindex* style file

Prog `xindex`

To use a custom *xindex* style file:

 **filename**

1. Copy `xindex-cfg.lua` to a new filename such as `xindex-projectname.lua`. The filename must start with `xindex-` and end with `.lua`.
2. Make changes to `xindex-projectname.lua`.
3. If changing

```
itemPageDelimiter -and- rangeSymbol
```

in `xindex-projectname.lua`, then in the document preamble redefine

```
\IndexPageSeparator -and- \IndexRangeSeparator
```

to match.

Opt `xindexConfig`

4. In the document source use the `xindexConfig` option for `lwarp`:

```
\usepackage[
  ... other options ...
  xindex,
  xindexConfig=projectname, % (without xindex- or .lua)
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

5. Recompile the print version, which causes `lwarp` to rewrite the `lwarpmk.conf` configuration file. This tells `lwarpmk` to use the custom `xindex-projectname.lua` file instead of the default `xindex-cfg.lua`.

8.6.23 Additional indexing limitations

 **xindy with hyperref** *xindy* and *hyperref* may not work well together for print output with “see”, “see also”, reference ranges, or stylized index references. It may be necessary to turn off hyper-referencing for indexes:

```
\usepackage[hyperindex=false]{hyperref}
```

 **empty index** If an HTML index is empty, it may be necessary to add the following before *lwarp* is loaded:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
. . .
\usepackage{lwarp}
```

makeindex custom display styles When using *makeindex*, custom display styles are possible:

```
\begin{warpprint}
\newcommand{\notesstyle}[1]{#1nn}
\end{warpprint}

\begin{warpHTML}
\makeatletter
\newcommand{\notesstyle}[1]{\LWR@doindexentry{#1} notes }
\makeatother
\end{warpHTML}
. . .
A sentence.\index{key|notesstyle}
```

xindy custom display styles For custom styles with *xindy*, see *lwarp.xdy* for `\textbf` and `\textit` as examples.

8.6.24 Index positions, toc, tocbibind

placement and toc options An index may be placed inline with other HTML text, or on its own HTML page:

Pkg `makeidx`

Inline, with a manual toc entry:

A commonly-used method to introduce an index in a L^AT_EX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg `makeidx`

On its own HTML page, with a manual toc entry:

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg `tocbibind`

Inline, with an automatic toc entry:

The `tocbibind` package may be used to automatically place an entry in the TOC.

```

\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex

```

Pkg tocbibind

On its own HTML page, with an automatic TOC entry:

```

\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex

```

Opt [tocbibind] numindex

numbered index section

Use the `tocbibind numindex` option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as `imakeidx`, may also have options for including the index in the Table of Contents.

Pkg tocloft

tocloft & other packages

If using `tocloft` with `tocbibind`, `anonchp`, `fncychap`, or other packages which change chapter title formatting, load `tocloft` with its `titles` option, which tells `tocloft` to use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

8.7 Math

8.7.1 Math in section names

math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring` from the `hyperref` package:

```

\section{Some math \texorpdfstring{$1+2=3$}{three}}

```

8.7.2 Rendering tradeoffs

Math rendering Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.

SVG files Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline The SVG images are currently stored separately, but they could be encoded inline directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files Others L^AT_EX-to-HTML converters have used PNG files, sometimes pre-scaled for

print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML. Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 10 regarding EPUB output with MATHJAX.

8.7.3 SVG option

SVG math option For SVG math, math is rendered as usual by L^AT_EX into the initial PDF file using the current font¹⁴, then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by L^AT_EX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML alt attribute carries the L^AT_EX code which generated the math, allowing copy/paste of the L^AT_EX math expression into other documents.

SVG image font size For the lateximage environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

SVG math copy/paste For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the L^AT_EX code for the math expression. For $\mathcal{A}\mathcal{M}\mathcal{S}$ environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred $\mathcal{A}\mathcal{M}\mathcal{S}$ environment, although the `\tag` macro will still appear inside the L^AT_EX math expression.

SVG math size, baseline SVG math sizing and baselines are improved if the `graphics` or `graphicx` package is loaded. An almost-invisible marker is placed at either end of the image to assist in cropping and computing the baseline. A warning is issued at the end of the compile if `graphics` or `graphicx` are not used.

SVG math in T_EX boxes SVG math does not work inside T_EX boxes, since a `\newpage` is required before and after each image.

8.7.4 MATHJAX option

MATHJAX math option The MATHJAX (mathjax.org) L^AT_EX-math to HTML converter may be used to display math.

Prog MathJax

When MATHJAX is enabled, math is rendered twice:

¹⁴See section 677 regarding fonts and fractions.

1. As regular L^AT_EX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of L^AT_EX, and
2. As detokenized printed L^AT_EX commands placed directly into the HTML output for interpretation by the MATHJAX display scripts. An additional script is used to pre-set the equation number format and value according to the current L^AT_EX values, and the MATHJAX equation numbering system is ignored in favor of the L^AT_EX internal system, seamlessly integrating with the rest of the HTML output, including any math appearing in non-MATHJAX SVG output.

⚠ fonts

8.7.5 MATHJAX rendering options

MATHJAX v3 may render using CHTML or SVG. SVG display renders italic characters correctly. To select SVG rendering, right-click on some math, and select

Math Settings → **Math Renderer** → **SVG**

Wait a moment for the math to re-render.

8.7.6 Customizing MATHJAX

equation numbering

lwarp detects and adjusts MATHJAX equation numbering format for article and book style equations as well as `amsmath \numberwithin` for chapters, sections, and subsections. Custom equation number formats may be set as follows, for example:

```
\renewcommand*\theequation{\Alph{section}.\arabic{equation}}
\AtBeginDocument{
  \renewcommand*\theMathJaxsection{\Alph{section}.}
}
```

⚠ subequation

The `amsmath` `subequations` environment is supported, but only with `\alpha` subequation numbering.

global customizations

MATHJAX does not have preexisting support every possible math function. Additional MATHJAX function definitions may be defined in the preamble. These will be declared at the start of each HTML page, and thus will have a global effect across all HTML pages.

Examples:

```
\begin{warpMathJax}
\CustomizeMathJax{
  \newcommand{\expval}[1]{\langle#1\rangle}
  \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arcsinh}{\text{arcsinh}}}
\CustomizeMathJax{\newcommand{\arccosh}{\text{arccosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
\end{warpMathJax}
```

⚠ slow compilation

To avoid a slowdown in compile speed, use the `warpMathJax` environment to prevent its contents from being processed in print or SVG math output. Also, place

each new definition inside its own `\CustomizeMathJax`. A warning to this effect is issued if an overly-long definition is attempted.

lwarp already provides MATHJAX customizations for some packages.

siunitx When using `siunitx`, a similar process may be used to add custom units:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\myunit}{\mathrm{WXYZ}}}
\CustomizeMathJax{\newcommand{\umyunit}{\mathrm{\micro\myunit}}}
\end{warpMathJax}
```

advanced control For more advanced control over dynamically creating custom definitions, see as an example the lwarp definition for `\DeclarePairedDelimiterX`, in section 399, [mathtools](#).

local customizations For customizations local to the current HTML page only, macros may be defined as follows:

```
\begin{warpMathJax}
\(\newcommand{\macroname}{. . .} \)
\(\newcommand{\anothername}{. . .} \)
\end{warpMathJax}
```

To maintain compile speed, use the `warpMathJax` environment, and use a separate math environment for each definition.

`\ifstar` For MATHJAX, use `\ifstar` instead of `\@ifstar`:

```
\CustomizeMathJax{
\def\myname{
\ifstar\starredaction\unstarredaction
% (Do not place anything after!)
} }
```

`\ifnextchar` For MATHJAX, use `\ifnextchar` instead of `\@ifnextchar`:

```
\CustomizeMathJax{\def\myname{\ifnextchar X \found\notfound}}
```

“X” may be a single ASCII character, or a hex number inside braces, ex:

```
\CustomizeMathJax{\def\myname{\ifnextchar{0x7B}\found\notfound}}
```

Use “(” or “{0x28}” for a left parenthesis, “{0x7B}” for a left brace, “{0x7D}” for a right brace, or “{0x5C}” for a backslash.

8.7.7 MATHJAX limitations

MATHJAX limitations Limitations when using MATHJAX include:

Prog MathJax



`\multicolumn`, `\multirow`

- MATHJAX does not support `\multicolumn` or `\multirow`. These may be used in text tabulars or SVG math, but in MATHJAX math arrays they are emulated. `\multicolumn` only fills a single cell, resulting in a short row. `\multirow` simply prints its text on the first line.



`footnotes`

- Footnotes are emulated when used inside a MATHJAX expression. For an equation with a single footnote, the correct footnote number is used. For non-equations, `\footnotename` is used instead, since the actual number

cannot be tracked. See section 8.5.4 regarding the use of footnotes with MATHJAX.

- ⚠ **references**
 - Inside a MATHJAX expression, references to equations work within the same HTML web page, but do not work when referring to an equation in a different HTML web page. Outside of a MATHJAX expression, in the text body, references work as expected.

- lateximage
 - Math appearing inside a lateximage, and therefore also inside a Tikz or picture environment, is rendered as SVG math even if MATHJAX is used in the rest of the document.

- siunitx
 - For siunitx, see [siunitx package](#), section 8.7.14.

- physics
 - For physics, see [physics package](#), section 8.7.16.

- tabbing
 - A tabbing environment is emulated using an HTML `<pre>`. While MATHJAX is enabled inside tabbing, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

- \text
 - MATHJAX includes the *textmacros* extension, which supports various macros which are commonly used inside `\text`, such as `\textbf` and text accents. Lwarp supports this extension.

- ⚠ **Unicode**
 - If using DVI L^AT_EX or PDF L^AT_EX, unicode input may not appear correctly in MATHJAX. Either use X_YL^AT_EX or LuaL^AT_EX, or replace Unicode special characters such as


```
\text{special character æ}
```

 with their special macros, such as


```
\text{special character \ae}
```

- ⚠ **other macros and packages**
 - Many other math-related macros and packages are not directly supported by MATHJAX, including `\ensuremath` and occasionally-used macros such as `\relax`. While using MATHJAX, lwarp provides emulation for many of these macros, as well as for footnotes and emulation for dozens of packages (see table 2). In many cases these emulations simply ignore the package in a source-compatible way. Others produce a result which represents the meaning, even if they don't look exact. Look up each package in this document for a description of the limitations of each.

8.7.8 Catcode changes

preamble macros with math

The math shift character `$` is not set for HTML output until after the preamble. Macros defined in the preamble which contain `$` must be enclosed between `\StartDefiningMath` and `\StopDefiningMath` to temporarily change to the HTML meaning of `$`:

```
\StartDefiningMath
\newcommand{. . .}
\StopDefiningMath
```

As an alternative, use `\(` and `\)` instead of `$`, in which case `\StartDefiningMath` and `\StopDefiningMath` are not necessary.

If a package defines macros using `$`, it may be necessary to use `\StartDefiningMath` and `\StopDefiningMath` before and after loading the package.

8.7.9 Complicated inline math objects

`\inlinemathnormal`
`\inlinemathother`

[changing contents](#)
[complicated alt tag](#)

[MATHJAX limitations](#)

An inline math expression is usually converted to a reusable hashed SVG math image, or a MATHJAX expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as $x+1$, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an `alt` tag. Yet another problem is math packages which are only partially emulated in MATHJAX. The macro `\inlinemathother` may be used before a sequence of dynamic or complicated math expressions, and `\inlinemathnormal` after. Doing so tells `lwarp` to use unhashed SVG math images for those particular expressions, even if MATHJAX is otherwise in use. See section 44.

8.7.10 Complicated display math objects

`\displaymathnormal`

By default, or when selecting `\displaymathnormal`, MATHJAX math display environments print their contents as text into HTML for MATHJAX to interpret, and SVG display math environments render their contents as SVG images and use their contents as the `alt` tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Tikz pictures, compilation will fail.

`\displaymathother`

[MATHJAX unsupported](#)
[complicated alt tag](#)

When selecting `\displaymathother`, it is assumed that the contents are more complicated than “pure” math. An example is an elaborate Tikz picture, which will not render in MATHJAX and will not make sense as an HTML `alt` tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML `alt` tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Tikz pictures are more likely to compile successfully.

8.7.11 Theorems

 [cref reference format](#)
[undefined](#)

If the print version does not use `cleveref`, place all `\theoremstyle` and `\newtheorem` declarations in the preamble inside `\AtEndPreamble`.¹⁵ For some theorems, it may also be required to add inside `\AtEndPreamble` something such as:

```
\usepackage{etoolbox} % for \ifdef, \AtEndPreamble
\AtEndPreamble{ % if not using cleveref package
  \theoremstyle{definition}
  \newtheorem{dtheorem}{Definition}
  . . .
  \ifdef{\cref}{
    \crefname{Proof}{Proof}{Proofs}
  }{}
```

¹⁵`lwarp` uses `cleveref` for the HTML conversion, and loads `cleveref \AtEndPreamble`, just before `\AtBeginDocument`. This is also before the `.aux` file is read.

8.7.12 ntheorem package

Pkg ntheorem

This conversion is not total. Font control is via css, and the custom L^AT_EX font settings are ignored.

⚠ Font control

⚠ Equation numbering

ntheorem has a bug with equation numbering in $\mathcal{A}\mathcal{M}\mathcal{S}$ environments when the option thref is used. lwarp does not share this bug, so equations with \split, etc. are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's thref option.

8.7.13 mathtools package

Pkg mathtools

showonlyrefs is disabled, as it conflicts with cleveref, which is used by lwarp. Equation numbers may not match the print version.

⚠ equation numbering

⚠ italic correction

mathic is not emulated for HTML.

⚠ MATHJAX

If using MATHJAX:

- mathtools disallowspaces does not work for MATHJAX. Protect brackets which are not optional arguments, such as:

```
\begin{gathered}{}
[p]=1 . . .
\end{gathered}
```

- showonlyrefs does not work in MATHJAX, and will result in a difference in equation numbering compared to the print version.
- alignat in MATHJAX requires math mode, but in L^AT_EX it doesn't. It may be required to use warpHTML and warpprint to isolate a version for each mode.
- \DeclarePairedDelimiter and related must be in the preamble before \begin{document}.

8.7.14 siunitx package

Pkg siunitx

siunitx is well supported by lwarp.

Limitations Some general limitations:

fractions Due to *pdftotext* limitations, fraction output is replaced by symbol output for per-mode and quotient-mode.

\cancel is not currently supported for siunitx v3.

Negative values are not automatically colored.

⚠ tabular

Tabular S and s columns are rendered as simple c columns, although key settings will be set. If using scientific notation, table-format, table-align-uncertainty, drop-exponent, etc.. use \tablenum for each cell. This is especially required for drop-exponent, without which the value will be shown incorrectly.

⚠ drop-exponent

⚠ table-auto-round

table-auto-round is ignored.

Math rendering Math may be rendered in several ways in the same document:

For math mode with `svg display`: The original siunitx code is used while generating the SVG image.

For HTML text mode: lwarp uses siunitx code patched for HTML, and simplified units.

For math expressions while using `MATHJAX`: A limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. The result usually looks fine, and otherwise is enough to get the meaning across.

Custom units siunitx allows customized units:

`\DeclareSIUnit`

```
{\langle name \rangle} {\langle definition \rangle}
```

`\DeclareSIUnit` declares a version of the unit for the print version. This is also used when the unit is printed in `svg math` or a `lateximage`. It is also used for HTML if an HTML-specific version is not defined with `\HTMLDeclareSIUnit`.

```
\DeclareSIUnit\myunit{\ensuremath{\text{m}_y}}
```

`\HTMLDeclareSIUnit`

```
{\langle name \rangle} {\langle definition \rangle}
```

 **v3 only!** Use this after the print unit has been defined. For siunitx v3, `\HTMLDeclareSIUnit` declares a simplified version of the unit for HTML, for example if the print-mode unit uses `TeX boxes` or `\ensuremath`:

```
\HTMLDeclareSIUnit\myunit{\text{m}\textsubscript{\textit{y}}}
```

It is also possible to provide a custom unit for `MATHJAX`:

```
\CustomizeMathJax{\newcommand{\myunit}{\text{m}_y}}
```

Predefined units Most units work as-is with HTML. For the following units, lwarp has already set `\HTMLDeclareSIUnit`: `\celsius`, `\arcminute`, `\arcsecond`, `\elementarycharge`, `\clight`, `\bohr`, `\electronmass`, `\hartree`, `\planckbar`.

 **MathJax**

Document modifications required for `MATHJAX`

 **`\sisetup`**

- Place `\sisetup` in the preamble before `\begin{document}`. Changes made later may be ignored, especially with `MATHJAX`. The `MATHJAX` emulation also ignores most macro options.

 **complex numbers**

- Complex numbers are displayed as entered, ignoring `output-complex-root`.

custom units

- Custom units may be added with `\CustomizeMathJax`. For example, from `lwarp-common-mathjax-siunitx`:

```
\CustomizeMathJax{\newcommand{\hartree}{\mathit{E}_{\mathrm{h}}}}
\CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\unicode{x212B}}}}
```

 **unit spacing**

- Units work better using `~` between units instead of using periods.

Table 9: `\includegraphics` and file names

Print image file	HTML image file	Command to use
image.pdf ^a	image.svg ^a	<code>\includegraphics{image}</code>
image.eps ^a	image.svg ^a	<code>\includegraphics{image}</code>
image.jpg	— ^b	<code>\includegraphics{image}</code>
image.png	— ^b	<code>\includegraphics{image}</code>
image.JPG	— ^b	<code>\includegraphics{image.JPG}</code> ^c
image.PNG	— ^b	<code>\includegraphics{image.PNG}</code> ^c
image.jpg	image.gif	<code>\includegraphics{image}</code>

^a: Must be a lowercase file extension.

^b: The same file is used for print and HTML.

^c: The uppercase extension must be specified.

⚠ `\square`, `\cubic`

- To square or cube compound units, enclose the following compound units in braces:

`\cubic{\centi\meter}`

Single units do not require braces.

- For `\numlist`, the argument is printed as text as-is, so use space between semicolons for improved readability.

⚠ Missing \$ inserted

- If using `parse-numbers = false`, also use `\num` or `\qty`. `siunitx=siunitx>Missing $ inserted`.

Also see [MATHJAX option](#), section 8.7.4.

8.7.15 units and nicefrac packages

Pkg units
Pkg nicefrac

`units` and `nicefrac` work with `lwarp`, but `MATHJAX` does not have an extension for `units` or `nicefrac`. These packages do work with `lwarp`'s option `svgmath`.

8.7.16 physics package

Pkg physics

`physics` works as-is for HTML with SVG math.

For `MATHJAX`, the `MATHJAX v3 physics` extension is used.

8.8 Graphics

Pkg graphics
Pkg graphicx

[file extensions](#)

Per table 9, image filenames may be specified either with or without an extension. If an extension is given it will be used as-is, for either print or HTML output. If no extension is given, a list of possible extensions is tried, which depends on whether print or HTML is being generated. This allows a PDF file for print and a

⚠ case sensitive

SVG file for HTML, for example. If no extension is given, the automatic search will only return lowercase extensions, even if the filename actually has an uppercase extension, and `lwarp` cannot get around this problem, so image file extensions must be lowercase to be seen by the HTML browser with `lwarp`. For example, name the image file `image.pdf` instead of `image.PDF`, but refer to it in the source as `image`, without an extension. For images which may be used as-is with either print or HTML, such as JPG or PNG, you may use a capitalized extension if it is specified in the source, such as `image.JPG`.

\includegraphics file formats

For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps` image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, `lwarp` will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a `.pdf` or `.eps` image is referred to with its file extension, the extension will be changed to `.svg` for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog `pdftocairo`

PDF to SVG

To convert a PDF image to SVG, use the utility `pdftocairo`:

```
Enter ⇒ pdftocairo -svg filename.pdf
```

Prog `lwarpmk pdftosvg`

For a large number of images, use `lwarpmk`:

```
Enter ⇒ lwarpmk pdftosvg *.pdf (or a list of filenames)
```

Prog `lwarpmk epstopdf`

For EPS images converted to PDF using the package `epstopdf`, use

Prog `epstopdf`

epstopdf package

```
Enter ⇒ lwarpmk pdftosvg *.PDF
```

to convert to SVG images.

DVI L^AT_EX

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

```
Enter ⇒ lwarpmk epstopdf *.eps (or a list of filenames)
```

```
Enter ⇒ lwarpmk pdftosvg *.pdf (or a list of filenames)
```

PNG and JPG

For PNG or JPG while using `pdflatex`, `lualatex`, or `xelatex`, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF

GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities

If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

duplicate files**⚠ image not displayed**

A complication occurs if a file of the same name exists elsewhere in the T_EX tree, such as a test image from some L^AT_EX package. T_EX looks in the local document directory before considering the directories specified by `\graphicspath`, but the T_EX tree is found as "local", so any file in the tree is found before the directories

in `\graphicspath`. To use such an image, it must be copied to the document's directory to be used for HTML, and furthermore must be in the document's base directory instead of an images subdirectory.

- ⚠ **graphics vs. graphicx** If using the older `graphics` syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer `graphicx` syntax. Note that
- ⚠ **viewport** viewports are not supported by `lwarp`—the entire image will be shown.

units For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys. (`alt` has recently been incorporated into `graphicx` itself.)

HTML class With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML alt tags Likewise, the `\includegraphics alt` key adds an HTML `alt` tag to an image, and is ignored for print output. If not assigned, each image is given an `alt` tag according to `\ImageAltText`.

- ⚠ **scale** Avoid using the `\includegraphics scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

\rotatebox `\rotatebox` accepts the optional `origin` key.

- ⚠ **browser support** `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike L^AT_EX, so expect some ugly results for scaling and rotating.

8.8.1 tikz package

Pkg `tikz` If using `display math` with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

- ⚠ **displaymath and matrices**

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the `tikz` expression must be replaced with `\&`.

8.8.2 grffile package

Pkg `grffile` `grffile` is supported as-is. File types known to the browser are displayed, and

 **matching PDF and SVG**

unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

8.8.3 color package

Pkg color

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

8.8.4 xcolor package

Pkg xcolor

\colorboxBlock and \fcolorboxBlock

\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a <div> instead of a . These <div>s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none

\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes required.

colored tables

\rowcolors is supported, except that the optional argument is ignored so far.

colored text and boxes

\textcolor, \colorbox, and \fcolorbox are supported.

\color and \pagecolor

\color and \pagecolor are ignored. Use css or \textcolor where possible.

8.8.5 epstopdf package

Pkg epstopdf

 **convert to .svg**

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

```
Enter => lwarpmk pdftosvg <listofPDFfiles>
```

to generate .svg versions.

8.8.6 pstricks package

Pkg pstricks

 **use pspicture**

All pstricks Pkg content should be contained inside a pspicture environment.

8.8.7 pdftricks package

Pkg pdftricks

 **convert image files**

The pdftricks image files <jobname>-fig*.pdf must be converted to .svg, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

```
Enter => lwarpmk pdftosvg <jobname>-fig*.pdf
```

8.8.8 psfrag package

Pkg psfrag

 use psfrags

The psfrags environment is modified to use `lateximage` to encapsulate the image. Always use a psfrags environment to contain any local `\psfrag` macros and the associated `\includegraphics` or `\epsfig` calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.



Tip: Use a mono-spaced font for the tags in the EPS file.

8.8.9 pstool package

Pkg pstool

 path and filename

`\graphicspath` is ignored, and the file directory must be stated.

The filename must not have a file extension.

Use

```
Enter => lwarpmk html
```

followed by

```
Enter => lwarpmk limages
```

.

8.8.10 asymptote package

Pkg asymptote

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex
```

```
lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1
```

```
lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

8.8.11 overpic package

Pkg overpic

 scaling

The macros `\overpicfontsize` and `\overpicfontskip` are used during HTML generation. These are sent to `\fontsize` to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the `overpic` and `Overpic` environments.

8.8.12 Multimedia packages

Pkg multimedia
Pkg movie15
Pkg media9

The packages `multimedia`, `movie15`, and `media9` are supported.

HTML5 `<audio>` and `<video>` objects are created for `.mp3` and `.mp4` files.

HTML5 `<embed>` objects are created for `http` and `ftp` links.

`\href` links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For `media9`, a multimedia object is inserted for each `addressource=`, as well as each `flashvars source=` and `src=`. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside `\warpprintonly` or the `warpprint` environment.

Each HTML multimedia object includes the poster text, except for `<embed>` objects. For `movie15`, the `text` option is supported to specify the poster text.

The `width`, `height`, and `totalheight` options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

`media9 \addmediapath` is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each `<audio>` and `<video>` object.

`media9` slideshows are not supported.

`\hyperlinkmovie`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YOUTUBE™ video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

8.9 Tabbing

The tabbing environment works, except that `svg math` and `lateximages` do not yet work inside the environment.

 **math in tabbing** If `math` is used inside tabbing, place tabbing inside a `lateximage` environment, which will render the entire environment as a single `svg` image.

8.10 Tabular

8.10.1 tabular environment

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

- When defining environments or macros which include tabular and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are ignored in print mode.

```
\StartDefiningTabulars
```

```
<define macros or environments using tabular and & here>
```

```
\StopDefiningTabulars
```

This includes before and after defining any macro which used \ttabbox from floatrow.

- When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % (& is used in a definition)
```

```
\newenvironment{outerenvironment}
```

```
{
  \tabular{cc}
  left & right \\
}
```

```
{
  \TabularMacro\ResumeTabular
  left & right \\
  \endtabular
}
```

```
\StopDefiningTabulars
```

For developers:

- To automate the use of \StartDefiningTabulars and \EndDefiningTabulars, these macros may be embedded inside an HTML environment definition to automatically change the catcode of & before absorbing the arguments. Another environment may be embedded as well.

⚠ Misplaced alignment
tab character &

⚠ floatrow

⚠ tabular inside another
environment

```

% Does the work after the catcode has been changed:
\newcommand*{\LWR@HTML@subsomename}[2]{%
  . . .
  \otherenvironmentname [<args>] {<args>} % for
example
}
% Change catcode before absorbing arguments:
\newcommand*{\LWR@HTML@somename{%
  \StartDefiningTabulars
  \LWR@HTML@subsomename
}
% Change catcode again at the end:
\newcommand*{\LWR@HTML@endsomename}{%
  . . .
  \endotherenvironmentname % for example
  \StopDefiningTabulars
}
% Combine with the existing print definition:
\LWR@formattedenv{somename}

```

Cell contents:**⚠ macro in a table**

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use `\TabularMacro` just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \
```

Column specifiers:**⚠ math**

- Due to the way math is gathered for processing, column specifiers such as `>{$}c<{$}` do not work with `lwarp`. Instead, each cell must specify math mode individually.

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In `\multirow` cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the `\multirow` which do not appear in the HTML version.

⚠ \newcolumntype

- If `\newcolumntype` does not work for HTML, add a simplified column type using `\HTMLnewcolumntype`.

font and alignment

- `lwarp` detects each of the following, and sets HTML CSS appropriately:
 - `>{\centering\arraybackslash}`
 - `>{\raggedright\arraybackslash}`
 - `>{\raggedleft\arraybackslash}`
 - `>{\itshape}`
 - `>{\bfseries}`
 - `>{\bfseries\itshape}`

These may be used with `\newcolumntype`, such as:

```
\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}
```

Rules:**vertical rules**

- Doubled `\hlines`, `\midrules`, and vertical rules are supported.
- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:

```
\cmidrule{2-3} \[-2ex]
\bottomrule
```

The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

- For `\toprule` and `\bottomrule`, when combined with a `warpprint` or `warppHTML` environment, if a “Misplaced `\noalign`” error occurs, change

```
This & That \endhead
```

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevant to HTML output.

⚠ `\warpprintonly`

⚠ Misplaced `\noalign`

Other:

- `tabularx` ignores the width, but X columns do produce paragraph columns or multicolumns.

longtable headings

- For `longtable`, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.

⚠ S columns

- For S columns (from the `siunitx` package), while producing print output, anything non-numeric must be placed inside `{ }` braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by `lwarp`'s tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
```

```
\warppHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

- In \LaTeX , a `tabular` may be placed inside a `minipage`, but in HTML a `<table>` may not be inside a ``. If this situation is detected, a warning is printed instructing the user to isolate the `` using `\warpprintonly` or the `warpprint` environment.

8.10.2 multirow package

vposn

- Note that recent versions of `multirow` include a new optional `vposn` argument.

multirow cells

- For `multirow`, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
... & \multirow{2}{.5in}{text} & ...
```

```
... & \mrowcell & ...
```

⚠ `tabular` inside a ``

colored cells

- The `multirow` documentation regarding colored cells recommends using a negative number of rows. This will not work with `lwrap`, so `\warpprintonly` and `\warpHTMLonly` must be used to make versions for print and HTML.

with `\multicolumn`

⚠ `\multicolumn & \multirow`

- See section 429.2 for `\multicolumnrow`.

`lwrap` does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

⚠ skipped cells

As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines, `\mcolrowcell` must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

⚠ empty cells

```
... & \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text} & ...
... & \mcolrowcell & \mcolrowcell & ...
... & \mcolrowcell & \mcolrowcell & ...
```

⚠ `MathJax`

- `MATHJAX` does not support `multirow`, so it is emulated to only print its text on the first row. `\multirow` works as expected in text tabulars or SVG math.

8.10.3 longtable package

Pkg `longtable`

Use one of either `\endhead` or `\endfirsthead` for both print and HTML, and use a `\warpprintonly` macro to disable the other head phrase, and also the `\endfoot` and `\endfirstfoot` phrases. (See section 8.10.4 if using `threeparttablex`.)

```
\begin{longtable}[ column specifiers ]
[ ... ] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[ ... ] \endhead % or \endfirsthead
[ ... ] \endfoot
[ <lastfoot macros> ] \endlastfoot
}
... table contents ...
\warpHTMLonly{
[ <lastfoot macros> ] % HTML last footer, without \endfoot
% or \endlastfoot.
}
\end{longtable}
```

- ⚠ `Misplaced \noalign` Use the `\warpprintonly` macro instead of the `warpprint` environment. Doing so helps avoid “Misplaced `\noalign`.” when using `\begin{warpprint}`.

- ⚠ `\kill` `\kill` is ignored, place a `\kill` line inside

```
\begin{warpprint} ... \end{warpprint}
```

or place it inside `\warpprintonly`.

- ⚠ `lateximage` `longtable` is not supported inside a `lateximage`.

8.10.4 threeparttablex package

Pkg threeparttablex

threeparttablex is used with longtable and booktabs as follows:

```

\begin{longtable}[column specifiers] }
[ . . . ] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[ . . . ] \endhead % or \endfirsthead
[ . . . ] \endfoot
\bottomrule \insertTableNotes \endlastfoot
}
. . . table contents . . .
\warppHTMLonly{ % HTML last footer
\bottomrule
\UseMinipageWidths % optional
\insertTableNotes
\endlastfoot
}
\end{longtable}

```

table width The table notes are created using a `\multicolumn`. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, `lwarp` guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use `\UseMinipageWidths` before `\insertTableNotes`. The width is then specified, and in many cases the result is an improvement in overall table layout.

8.10.5 supertabular and xtab packages

Pkg supertabular

For `\tablefirsthead`, etc., enclose them as follows:

Pkg xtab

```

\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars

```

 **Misplaced alignment tab character &**

See section 8.10.1.

 **lateximage** `supertabular` and `xtab` are not supported inside a `lateximage`.

8.10.6 colortbl package

Pkg colortbl

Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.

 **row/cell color**

`colortbl` ignores the overhang arguments.

8.10.7 ctable package

 **Misplaced alignment tab character &**

Use `\StartDefiningTabulars` before one or more `\ctables`, and `\StopDefiningTabulars` after. These change the meaning of the ampersand `&` character.

8.10.8 bigdelim package

Pkg bigdelim

⚠ use `\mrowcell`

`\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

```

\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}

```

$$\begin{array}{cc}
 \leftarrow & a \quad b \\
 & \left\{ \begin{array}{l} c \quad d \\ e \quad f \\ g \quad h \end{array} \right. \\
 \leftarrow & i \quad j
 \end{array}$$

For MATHJAX, limited emulation is provided which merely prints the delimiter and optional text in the first row.

8.11 Floats

8.11.1 Float contents alignment

⚠ figure & table alignment

`\centering`, etc. are honored in a figure or table if they are the first command inside the float:

```

\begin{table*}
\centering
\caption{A Table}
...

```

8.11.2 float, trivfloat, and/or algorithmicx together

Pkg float

If using `\newfloat`, `trivfloat`, and/or `algorithmicx` together, see section 636.1.

Pkg trivfloat

Pkg algorithmicx

⚠ package conflicts

8.11.3 caption and subcaption packages

Pkg caption

Package options may cause problems with `lwarp`, especially if they include curly braces.

Pkg subcaption

If selecting options with braces in `\usepackage` does not work:

```
\usepackage[font={it,small}]{caption}% does not work
```

... try instead selecting the package options before loading `lwarp`:

```

\PassOptionsToPackage{font={it,small}}{caption}
...
\usepackage{lwarp}
...
\usepackage{caption}

```

... or try setting package options after the package has been loaded:

```

\usepackage{caption}
\captionsetup{font={it,small}}

```

⚠ **numbering** To ensure proper float numbering, set caption positions such as:

```

\captionsetup[figure]{position=bottom}
\captionsetup[subfigure]{position=bottom}
\captionsetup[table]{position=top}
\captionsetup[subtable]{position=top}

```

Similarly for `longtable`. These positions depend on where the user places the `\caption` command inside each float.

8.11.4 subfig package

Pkg subfig

⚠ **table numbering** To have correct sub table numbers:

```

\usepackage{caption}
\captionsetup[table]{position=top}

```

⚠ **lof/lotdepth** At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

⚠ **horizontal spacing** In the document source, use `\hfill` and `\hspace*` between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

8.11.5 floatrow package

Pkg floatrow

⚠ **Misplaced alignment
tab character &
subfig package**

Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 8.10.1.

When combined with the `subfig` package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ **\FBwidth, \FBheight**

The emulation of `floatrow` does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. `lwarp` will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally after-

wards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

8.11.6 keyfloat package

Pkg keyfloat

 **keywrap**

If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a `minipage`, which internally adjusts for a virtual 6-inch wide `minipage`, which then corrupts the `lw` option.)

For wrapped figures, overhang and number of lines are ignored.

8.12 KOMA-SCRIPT classes

Cls komascript

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

`\captionformat`, `\figureformat`, and `\tableformat` are not yet emulated.

 **Not fully tested!** [Please send bug reports!](#)

Some features have not yet been tested. Please contact the author with any bug reports.

8.13 MEMOIR class

Cls memoir

 **captions**

`lwarp` uses `caption`, which causes a warning from `memoir`. This is normal. Adjust captions via `caption`, instead of `memoir`.

 **options clash**

While emulating `memoir`, `lwarp` pre-loads a number of packages (section 692.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading `lwarp`:

```
\documentclass{memoir}
...
\PassOptionsToPackage{options_list}{package_name}
...
\usepackage{lwarp}
...
\usepackage{package_name}
```

 **version numbers**

`memoir` emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since `lwarp` is intended to support the freestanding packages, which are often newer than the date declared by `memoir`, it is hoped that `memoir` will update and change its emulated version numbers to match.

`\label(bookmark){tag}` `\label` accepts an optional (bookmark) argument, but this is ignored in HTML.

 **comment** The `comment` environment is from the `comment` package, and thus requires that

the `\begin` and `\end` each be on its own line:

```
\begin{comment}
This is a comment.
\end{comment}
```

`\newcomment` Comments defined with `\newcomment` use memoir's definitions, and behave as expected, where the `\begin` and `\end` do have to each be on its own line.

⚠ `verbatim footnotes` `\verbfootnote` is not supported.

⚠ `\newfootnoteseries` `\newfootnoteseries`, etc. are not supported.

⚠ `page notes` `lwarp` loads `pagenote` to perform memoir's `pagenote` functions, but there are minor differences in `\pagenotesubhead` and related macros.

`page notes with cleveref` To add support for pagenotes with `cleveref`, add:

```
\crefname{pagenote}{page note}{page notes}
\Crefname{pagenote}{Page note}{Page notes}
```

`page note \nameref` Note that for print mode, `\nameref` print the section name where the page notes are declared in the text, but for HTML it prints the name where the page notes are printed.

⚠ `poems` Poem numbering is not supported.

⚠ `verbatim` The `verbatim` environment does not yet support the memoir enhancements. It is currently recommended to load and use `fancyvrb` instead.

⚠ `glossaries` The memoir glossary system is not yet supported by `lwarpmk`. The `glossaries` package may be used instead, but does require the glossary entries be changed from the memoir syntax to the `glossaries` syntax.

⚠ `framewithtitle, titledframe` The custom frame commands in the memoir manual may be emulated by placing the original definitions in the preamble inside `warpprint` environments, and then providing an HTML equivalent:

```
\begin{warpHTML}
\newcommand{\FrameTitle}[2]{%
  \textbf{#2}
}

\newenvironment{framewithtitle}[2][\FrameFirst@Lab\ (cont.)]{%
  \begin{fminipage}{\linewidth}
  \textbf{#2}
  \begin{minipage}{\linewidth}
}
{\end{minipage}\end{fminipage}}

\newcommand{\TitleFrame}[2]{%
  \par
  \textbf{#1}\par
  \fboxBlock{#2}
}

\newenvironment{titledframe}[2][\FrameFirst@Lab\ (cont.)]{%
  \par
  \textbf{#2}
```

```

\begin{fminipage}{\linewidth}
}
{\end{fminipage}}
\end{warpHTML}

```

8.14 International languages

 **section and file names** If using *pdflatex* with the setting `\booltrue{FileSectionNames}`, non-ASCII text in section names can result in corrupted HTML file names. *pdflatex* may be used if setting `\boolfalse{FileSectionNames}`, in which case HTML file numbers will be generated.

For correct HTML file names, use *xelatex*, *lualatex*, or dedicated document classes/engines.

(As of this writing, this warning is only relevant to the *kotex* package.)

8.15 Miscellaneous packages

8.15.1 verse and memoir

Pkg verse
Cls memoir
\attrib

When using *verse* or *memoir*, always place a `\\` after each line.

The documentation for the *verse* and *memoir* packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. *lwarp* provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```

\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}

```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by *verse* and *memoir* to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any *verse* environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

 **spacing** Horizontal spacing relies on *pdftotext*'s ability to discern the layout (`-layout` option) of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which

 **verse margin** case a label may be shifted by one space. During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused *pdftotext* to shift everything over.

8.15.2 newclude package

Pkg newclude

newclude modifies `\label` in a non-adaptive way, so *newclude* must be loaded

 **loading** before `lwarp` is loaded:

```
\documentclass{article}
... <font setup>
\usepackage{newclude}
\usepackage[warppHTML]{lwarp}
...
```

8.15.3 babel package

Pkg babel When French is used, the caption separator is changed to a dash. To restore it to a colon, the following may be placed before `lwarp` is loaded:

 `\CaptionSeparator`

```
\renewcommand*{\CaptionSeparator}{:~}
```

punctuation spaces Also when French is used, `lwarp` creates fixed-width space around punctuation by patching `\FBcolonspace`, `\FBthinspace`, `\FBguillemet`, `\FBmedkern`, `\FBthickkern`, `\FBtextellipsis`, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a `warpprint` environment so that the user's changes do not affect the HTML output.

 **customized spacing**

8.15.4 polyglossia package

Pkg polyglossia `lwarp` uses `cleveref`, which has some limitations when using `polyglossia`, possibly resulting in the error

```
! Undefined control sequence. . . . \__hook begindocument
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by `cleveref`, then select other languages using `\setotherlanguages`.

Once the print version works with `cleveref` and `polyglossia`, the HTML version should work as well using `lwarp`.

8.15.5 todonotes and luatodonotes packages

Pkg todonotes The documentation for `todonotes` and `luatodonotes` have an example with a `todo` inside a caption. If this example does not work it will be necessary to move the `todo` outside of the caption.

Pkg luatodonotes

8.15.6 fixme

Pkg fixme External layouts (`\fxloadlayouts`) are not supported.

 **external layouts**

Customized layouts are overwritten by `lwarp`'s versions `\AtBeginDocument` in order to provide the HTML conversion. If creating a new layout, see `lwarp`'s changes to provide similar for the new layout, inside a `warpHTML` environment.

User control is provided for setting the HTML styling of the “faces”. The defaults are as follows, and may be changed in the preamble after `fixme` is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

8.15.7 acro package

 **formats** Define acronym formats using `\textbf` instead of `\bfseries` etc.

8.15.8 chemfig package

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```
\begin{lateximage}[-chemfig-~\PackageDiagramAltText]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

8.15.9 chemformula package

 **chemformula with MATHJAX** `chemformula` works best without `MATHJAX`. If `MATHJAX` is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The `chemformula` package adapts to `array`, but does not know about `MATHJAX`, and `MATHJAX` does not know about `chemformula`.)

While using `MATHJAX`, `\displaymathother` may also be used for other forms of display and inline math which contain `chemformula` expressions.

8.15.10 mhchem package

See section 410.

8.15.11 kotex package

See section 8.14 regarding `pdf \LaTeX` and Korean section names.

 **Korean section names**

9 Compiling using custom shell commands

`lwarp` and `lwarpmk` try to make it easy to process print and HTML compilation tasks in most situations. Depending on the operating system, command-line options, T_EX engine, and `lwarp` options, the commands `lwarpmk print` and `lwarpmk html` are automatically set up to correctly recompile the project. These actions may be overridden using `lwarp` options, thus allowing the use of packages such as `perltex` and `pythontex`.

9.1 Command options

Opt `PrintLatexCmd`
Opt `HTMLLatexCmd`

The `lwarp` options `PrintLatexCmd` and `HTMLLatexCmd` are used to set customized commands to be executed by `lwarpmk print` and `lwarpmk html`.

`PrintLatexCmd` should be set to shell commands which take `project.tex` and generate `project.pdf`.

`HTMLLatexCmd` should be set to take `project_html.tex` and generate `project_html.pdf`. `lwarpmk` will then take `project_html.pdf` and automatically convert it and generate `project.html`.

9.2 Literal character macros

The `lwarp` package options are parsed by T_EX, and so some characters require the use of a special macro to represent them. See table 10. `\LWRopquote` and `\LWRopseq` may be used to increase operating-system portability. `\jobname` must have `_html` appended for processing HTML. `\space` may be necessary between other macros.

 **macro not found** To use these macros, either `kvoptions-patch` must be loaded before `lwarp`:

```
\usepackage{kvoptions-patch}
\usepackage[
  PrintLatexCmd={... } ,
  HTMLLatexCmd={ ... }
]{lwarp}
```

Table 10: Literal character macros

Character	Macro	Comment
%	\LWRpercent	
\$	\LWRdollar	
&	\LWRamp	
%	\LWRhash	
\	\LWRbackslash	
' or "	\LWRopquote	Depends on the operating system.
& or &&	\LWRopseq	Depends on the operating system.
(space)	\space	Forces an extra space.
(jobname)	\jobname	Without file extension.

or `\lwarpsetup` must be used to set `PrintLatexCmd` and `HTMLLatexCmd`:

```

\usepackage[...]{lwarp}
\lwarpsetup{
  PrintLatexCmd=
  {
    latex tm \LWRopseq
    dvips -o tm-pics.ps tm.dvi \LWRopseq
    ps2pdf -dALLOWPSTRANSPARENCY tm-pics.ps \LWRopseq
    pdflatex tm.tex
  } ,
  HTMLLatexCmd=
  {
    latex tm_html \LWRopseq
    dvips -o tm_html-pics.ps tm_html.dvi \LWRopseq
    ps2pdf -dALLOWPSTRANSPARENCY tm_html-pics.ps \LWRopseq
    pdflatex tm_html.tex
  }
}

```

9.3 *latexmk*

Prog `latexmk`

If *latexmk* is used for a project, it may be easiest to continue using it.

`latexmk project.tex` would create `project.pdf` as normal.

`latexmk project_html.tex` would create `project_html.pdf`, then

`lwarpmk pdftohtml project_html.pdf` would take `project_html.pdf` and convert it to `project.html`.

Pkg `sagetex`

latexmk may simplify the use of packages such as `sagetex`.

9.4 perltex package

Pkg perltex

The lwarp package option settings to use perltex would be similar to:

```
\usepackage[
  . . .
  PrintLatexCmd={perltex -latex=pdflatex project.tex} ,
  HTMLLatexCmd={perltex -latex=pdflatex project_html.tex} ,
  . . .
]{lwarp}
```

 **“impure” math** Place **perltex** math expressions between `\displaymathother` and `\displaymathnormal`, or `\inlinemathother` and `\inlinemathnormal`. See section 8.7.10.

9.5 pythontex package

Pkg pythontex

An example using pythontex:

```
\usepackage[
  . . .
  PrintLatexCmd={
    pdflatex project.tex \LWRopseq
    pythontex project \LWRopseq
    pdflatex project.tex
  } ,
  HTMLLatexCmd={
    pdflatex project_html.tex \LWRopseq
    pythontex project_html \LWRopseq
    pdflatex project_html.tex
  } ,
  . . .
]{lwarp}
```

Another possibility is to use *latexmk*, placing the `latexmk . . .` commands in the `PrintLatexCmd` and `HTMLLatexCmd` options. While using these options, the lwarp option `latexmk` would not be used.

 **“impure” math** No attempt has yet been made to make **pythontex** robust with HTML output. Some math objects must be surrounded by `\displaymathother ... \displaymathnormal`, or `\inlinemathother ... \inlinemathnormal`. Displays of code may have to be

 **HTML look-alike** enclosed inside a `lateximage` environment to prevent `<`, `>` and similar from being interpreted by the browser as HTML entities.

9.6 sympytex package

Pkg sympytex

For sympytex:

```

\usepackage[
  . . .
  PrintLatexCmd={
    pdflatex project.tex \LWRopseq
    python project.sympy \LWRopseq
    pdflatex project.tex
  } ,
  HTMLLatexCmd={
    pdflatex project_html.tex \LWRopseq
    python project_html.sympy \LWRopseq
    pdflatex project_html.tex
  } ,
  . . .
]{lwarp}

```

Also see the warnings for `pythontex`, above.

9.7 Other packages

Pkg rterface

Other packages such as `rterface` would be set up similar to `pythontex`, and the same warnings would apply.

9.8 *make* program

Prog make

To use `lwarp` with the *make* program, have the makefile take `project.tex` and generate the print version `project.pdf`, as normal. `\usepackage{lwarp}` must be used, and it generates `lwarpmk.conf` when the print version is created.

To generate HTML, first have `project_html.tex` be compiled to generate `project_html.pdf`. This must be in PDF format. Finally, have `project_html.pdf` be converted to HTML using `lwarpmk pdftohtml project_html.pdf`, and convert SVG math with `lwarpmk limages`.

9.9 UTF-8 locale

 **UTF-8 locale** *lwarpmk* uses the *texlua* program, which sets the “locale” to “C”, including for external operating-system calls such as when executing `lwarpmk html`. In some cases, an external program called from the user’s document may require the use of a UTF-8 “locale”. For UNIX-related operating systems, it may be required to use `lwarp`’s custom compilation options to add a locale change:

```

\usepackage[lwarp][
  PrintLatexCmd={
    env LC_CTYPE=en_US.UTF-8
    xelatex -shell-escape project.tex
  }
  HTMLLatexCmd={
    env LC_CTYPE=en_US.UTF-8
    xelatex -shell-escape project_html.tex
  }
]

```

Pkg ditaa

The only example seen so far where this is required is the `ditaa` package, where the locale change allows the use of UTF-8 with Xe \LaTeX and `ditaa`. To use Lua \LaTeX instead, the locale change would have to be made inside the `ditaa` package where its calls the *ditaa* program.

10 EPUB conversion

lwarp does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

<meta> author To assign the author's name for regular lwarp HTML files, and also for the EPUB, use `\HTMLAuthor {<name>}`. This assigns the name to the `<meta>` author element. It may be set empty, and it defaults to `\theauthor`.

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

FormatEPUB

Bool FormatEPUB

Default: false

FormatEPUB changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

To help convert lwarp HTML output to EPUB, add

```
\booltrue{FormatEPUB}
```

to the project's source preamble after `\usepackage{lwarp}`. The EPUB version of the document cannot co-exist with the regular HTML version, so

```
Enter ⇒ lwarpmk cleanall
```

```
Enter ⇒ lwarpmk html
```

```
Enter ⇒ lwarpmk images
```

to recompile with the FormatEPUB boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.

The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program *Calibre* (<https://calibre-ebook.com/>).

 **search order**

The EPUB conversion program must know what order the files are included. For lwarp projects, set the EPUB conversion software to do a breadth-first search of the files. For *Calibre*, this option is found in

Preferences → Plugins → File type plugins → HTML to Zip

 **encoding**

Check the box **Add linked files in breadth first order**. Set the document encoding as `utf-8`, which is what lwarp generates for HTML, even if the original printed document uses some other encoding.

 **section breaks**

The EPUB-conversion program must also know where the section breaks are located. For a list of lwarp's section headings, see table 12. For example, an article class document would break at `\section`, which is mapped to HTML heading level

<h4>, whereas a book class document would break at `\chapter`, which is HTML heading level <h3>. For *Calibre*, this option is found in

Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)

Select the “magic wand” to the right of this entry box, and set the first entry

Match HTML tags with tag name:

to “h4”. (Or “h3” for document classes with `\chapters`.) The Detect chapters at field should then show

//h:h4 — or — **//h:h3**

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the *lwarp*-generated HTML files may be loaded by *Calibre*, and then converted to an EPUB.

MathJax support

MATHJAX may be used in EPUB documents. Some e-readers include MATHJAX, but any given reader may or may not have a recent version, and may or may not include extensions such as support for `siunitx`.

lwarp adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader’s version of MATHJAX, so *lwarp* requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn’t work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MATHJAX, especially for equations numbered by chapter, or where `siunitx` support is important.

11 Word-processor conversion

lwarp may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LIBREOFFICE works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. lwarp provides some assistance in locating these frame boundaries, as shown below.

11.1 Activating word-processor conversion

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

FormatWP

Bool FormatWP

Default: false

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Additionally, honors the booleans WPMarkFloats, WPMarkMinipages, WPMarkTOC, and WPMarkLOFT.

To help modify lwarp HTML output for easier import to a word processor, add

```
\booltrue{FormatWP}
```

formatting adjustments

to the project's source preamble after lwarp is loaded. The following changes are then made to the HTML output:

- If using a class without chapters, \section and lower are shifted up in level for the HTML heading tags. The CSS has not been changed, so the section heading formats will not match the normal HTML output, but when imported to *LibreOffice Writer* the higher section headings will import as **Heading 1** for the title, **Heading 2** for \section, etc.
- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and <div>s, but they are no longer useful when the document has been imported into a word processor.
- An additional <div> with an id encapsulates each float and minipage, which on import into *LibreOffice Writer* causes a thin frame to appear around the text block for each.
- Float captions are given an explicit italic formatting.
- Tabular rule borders are made explicit for *LibreOffice Writer*. LIBREOFFICE displays a light border around each cell while editing, even those which have

no border when printed, and `lwarp` also uses a light border for thin rules, so it will be best to judge the results using the print preview instead of while editing in `LIBREOFFICE`.

- `\includegraphics` and `svg` math width and height are made explicit for `LIBREOFFICE`.
- `\hspace` is approximated by a number of `\quads`, and rules are approximated by a number of underscores.
- Explicit `HTML` styles are given to:
 - `\textsc`, etc.
 - `\underline`, `soul` and `ulem` markup.
 - `center`, `flushleft`, `flushright`.
 - `\marginpar`, `keyfloat`, `sidenotes`, `floatflt`, and `wrapfig`.
 - `fancybox` `\shadowbox`, etc.
 - The `LATEX` and `TEX` logos.

- Honors several booleans:

WPMarkFloats: Marks the begin and end of floats.

WPMarkMinipages: Marks the begin and end of minipages.

WPMarkTOC: Marks the location of the Table of Contents.

WPMarkLOFT: Marks the locations of the List of Figures/Tables.

WPMarkMath: Prints `LATEX` math instead of using images.

WPTitleHeading: Adjusts title and section headings.

Several of these may be used to add markers to the `HTML` text which help determine where to adjust the word processor document after import.

11.2 Additional modifications

WPMarkFloats

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.

WPMarkMinipages

Adds

Bool WPMarkFloats

Default: false

Bool WPMarkMinipages

Default: false

```

=== begin minipage ===
. . .
=== end minipage ===

```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

WPMarkTOC

Bool WPMarkTOC

Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual toc.

If set false, the actual toc is printed instead.

WPMarkLOFT

Bool WPMarkLOFT

Default: false

While formatting for word processors, adds

```

=== list of figures === and/or
=== list of tables ===

```

where each of these lists would have been. This helps identify where to insert the actual lists.

If set false, the actual lists are printed instead.

WPMarkMath

Bool WPMarkMath

[siunitx](#)

Default: false

Prog TeXMaths

While formatting for word processors, prints math as L^AT_EX code instead of creating svg images or MATHJAX. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

When using the *siunitx* package, enter

```
\usepackage{siunitx}
```

in the *TeXMaths* preamble. Equation numbering is problematic for $\mathcal{A}\mathcal{M}\mathcal{S}$ math environments.

WPTitleHeading

Bool WPTitleHeading

Default: false
[section headings](#)

While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LIBREOFFICE. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

Table 11: Section HTML headings for word-processor conversion

Section	HTML headings*			
	With \chapter		Without \chapter	
	WPTitleHeading true	WPTitleHeading false	WPTitleHeading true	WPTitleHeading false
Title	<h1>	plain	<h1>	plain
\book	<div>	<div>	<div>	<div>
\part	<h2>	<h1>	<h2>	<h1>
\chapter	<h3>	<h2>	—	—
\section	<h4>	<h3>	<h3>	<h2>
\subsection	<h5>	<h4>	<h4>	<h3>
\paragraph	<h6>	<h5>	<h5>	<h4>
\subparagraph		<h6>	<h6>	<h5>

* For default depths when not FormatWP, see table 12 on page 199.

See table 11 on page 183.

11.3 Recommendations

TOC, LOF, LOT For use with *LibreOffice Writer*, it is recommended to:

1. Set `\booltrue{FormatWP}`
2. Set `\booltrue{WPMarkTOC}` and `\boolfalse{WPMarkLOFT}`
3. Use `lwarp` to generate the HTML document.
4. Copy/paste from the HTML document into an empty *LibreOffice Writer* document.
5. Manually insert a LIBREOFFICE TOC in the LIBREOFFICE document.
6. Manually add frames around each float, adding a caption which is cut/pasted from each float's simulated caption.
7. Manually create cross references.

This process yields a document with an actual LIBREOFFICE Table of Contents, but a simulated List of Figures and List of Tables.

siunitx For `siunitx`, remember to adjust the preamble as mentioned above.

LO view border options LIBREOFFICE has options in the **View** menu to turn on/off the display of thin borders around table cells and text objects.

11.4 Limitations

Floats and captions are not explicitly converted to LIBREOFFICE floats with their own captions. Floats are surrounded by a thin frame in the LIBREOFFICE editor, and may be marked with `WPMarkFloats`, but are not given a proper LIBREOFFICE object frame. Captions are given an explicit italic formatting, but not a proper LIBREOFFICE paragraph style.

Cross references are not actual LIBREOFFICE linked cross references.

The List of Figures and List of Tables are not linked. The pasted pseudo LOF and LOT match the numbering of the L^AT_EX and HTML versions.

Equation numbering is not automatic, but the equation numbers in SVG math will match the L^AT_EX and HTML output. SVG math is recommended when using the $\mathcal{A}\mathcal{M}\mathcal{S}$ environments, which may have multiple numbered equations per object.

As of when last checked, LIBREOFFICE ignores the following:

- Minipage alignment.
- Tabular cell vertical alignment.
- Image rotation and scaling.
- Rounded border corners, which are also used by:
 - `\textcircled`
 - `booktabs trim`
- `\hspace` and rules, also used by `algorithmic`.
- Coloring of text decorations, used by `soul` and `ulem`.
- Overline text decoration, used by `romanbar`.

LIBREOFFICE also has limitations with frames and backgrounds:

- Multiple lines in an object are framed individually instead of as a whole.
- Nested frames are not handled correctly.
- Images inside boxes are not framed correctly.
- Spans with background colors and frames are not displayed correctly.

12 Modifying lwarp

- locating something** To quickly find the source for a package in `lwarp.dtx`, search for `*packagename`, such as `*siunitx`.
- Likewise, to quickly find the source for a file in `lwarp.dtx`, search for `*filename`, such as `*lwarp.css`.
- Purely text-based packages probably will work as-is when generating HTML.
- Look to existing code for ideas on how to expand into new code.
- image of TeX output** An environment may be converted to a `lateximage` then displayed with an image of the resulting L^AT_EX output. See section 93 for an example of the `picture` environment.
- css classes** To create a custom HTML block or inline CSS class, see section 52.10.
- print/HTML macros** To create print and HTML versions of the same macro or environment, see section 36.
-  **TeX boxes** Any TeX boxes must be undone, as `svg math` or `lateximages` require `\newpage`, which will not work in a TeX box.

12.1 Creating a development system

The following creates a local development system for `lwarp` on a TeXLive system in a UNIX-like environment. Doing so allows anything requesting `lwarp` to use the development version instead of whichever version is installed in TeXLive.

Create a development directory:

Place into this directory `lwarp.dtx` and `lwarp.ins`.

To create `lwarp.sty`, execute

```
Enter ⇒ pdflatex lwarp.ins
```

which creates `lwarp.sty` and several hundred additional `lwarp-*.sty` files for the various packages which are supported.

To create the initial documentation `lwarp.pdf`, execute

```
Enter ⇒ pdflatex lwarp.dtx
```

To make the development files visible to other projects:

Create the directory

```
/usr/local/texlive/texmf-local/tex/latex/local/lwarp
```

Inside this directory, create the file `update`, containing:

```
rm lwarp-*.sty
ln -s /path_to_dev_directory/lwarp*.sty .
ln -s /path_to_dev_directory/lwarp_baseline_marker.png .
ln -s /path_to_dev_directory/lwarp_baseline_marker.eps .
mktexlsr
```

Run `./update` now, and whenever a new `lwarp-*` package is added.

To make the development version of *lwarpmk* visible to other projects:

```
cd /opt
ln -s /usr/local/texlive/texmf-local/bin/x86_64-linux texbin_local
cd texbin_local
ln -s ../../scripts/lwarp/lwarpmk.lua lwarpmk
cd /usr/local/texlive/texmf-local/scripts/
mkdir lwarp
cd lwarp
ln -s /path_to_dev_directory/lwarpmk.lua lwarpmk
```

Verify that the correct version is found with

```
Enter ⇒ which lwarpmk
```

To make the local versions visible to the shell:

Paths must be set by the shell startup, such as in `.bashrc` and `.cshrc`:

In `.bashrc`:

```
PATH=/opt/texbin_local:/opt/texbin:$PATH
```

In `.cshrc`:

```
setenv PATH ${HOME}/bin:/opt/texbin_local:/opt/texbin:${PATH}
```

To fully compile the *lwarp* documentation and indexes:

```
pdflatex lwarp.ins
pdflatex lwarp.dtx
pdflatex lwarp.dtx <if necessary>
makeindex -s gglo.ist -o lwarp.gls lwarp.glo <indexes>
splitindex lwarp.idx -s gind.ist
pdflatex lwarp.dtx
pdflatex lwarp.dtx <if necessary>
makeindex -s gglo.ist -o lwarp.gls lwarp.glo <indexes>
splitindex lwarp.idx -s gind.ist <again>
pdflatex lwarp.dtx
pdflatex lwarp.dtx <if necessary>
```

(The second round of index processing is required to fully resolve the final Index of Indexes.)

To make it easier to update the documentation after a minor change, it is useful to create a command script called `make_index`, containing:

```
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
splitindex lwarp.idx -- -s gind.ist
```

 **references**

Note that Index of Indexes and the cross-references to the indexes may not be correct until the above has been accomplished.

12.2 Modifying a package for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic L^AT_EX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

When creating HTML, lwarp redefines the `\usepackage` and `\RequirePackage` macros such that it first looks to see if a `lwarp-<packagename>.sty` version exists. If so, the lwarp version is used instead. This modular system allows users to create their own versions of packages for lwarp to use for HTML, simply by creating a new package with a `lwarp-` prefix. If placed in the local directory along with the source code, it will be seen by that project alone. If placed alongside the other lwarp-packages where T_EX can see it, then the user's new package will be seen by any documents using lwarp. (Remember `mktexlsr` or `texhash`.)

An `lwarp-<packagename>.sty` package is only used during HTML generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful HTML conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing `lwarp-` packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new `lwarp-` package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a “local” prefix according to the package name, and `@` characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for HTML output. Only the “user-facing” macros need to be nullified or emulated.

Each `lwarp-*` package should first call either of:

```
\LWR@ProvidesPackageDrop
— or —
\LWR@ProvidesPackagePass
```

If “Drop”ped, the original print-version package is ignored, and only the `lwarp-` version is used. Use this where the original print version is useless for HTML. If “Pass”ed, the original package is loaded first, with the user-supplied options, then the `lwarp-` version continues loading as well. See section 457 ([ntheorem](#)) for an example of selectively disabling user options for a package. Use this when HTML output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a `lwarp-` version.

12.2.1 Adding a package to the `lwarp.dtx` file

When adding a package to `lwarp.dtx` for permanent including in lwarp, provide the `lwarp-<packagename>` code in `lwarp.dtx`, add its entry into `lwarp.ins`, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to `lwarp.dtx` in section 20.1. This causes `lwarp` to stop with an error if `packagename` is loaded before `lwarp`. Finally, add an entry in table 2, **Supported packages and features**, and also the Updates section.

12.3 Modifying a class for lwarp

If a class loads additional packages, it will be required to modify the class for `lwarp`, since `lwarp` must be loaded before most other packages.

To work with `lwarp`, a class must first set up anything which replicates the functions of the basic L^AT_EX classes, load any required fonts, then load `lwarp`, then finally load and adjust any other required packages.

12.4 Testing lwarp

Compiling `lwarp.ins` generates all the `*.sty` files for `lwarp`. It can be useful to create additional `*.ins` files to be able to recompile only the pieces which have changed.

compiling individual packages

For example, to be able to recompile the `lwarp` core alone, copy `lwarp.ins` to `core.ins`, then modify `core.ins` to only compile:

File `core.ins`

```
\generate{
\file{lwarp.sty}{\from{lwarp.dtx}{package}}
}
```

For individual packages, create `packagename.ins`, set to compile only:

```
\generate{
\file{lwarp-packagename.sty}{\from{lwarp.dtx}{packagename}}
}
```

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

compiling css and other generated files

Remember that the configuration files are only rewritten when compiling the printed version of the document.

When changing the source to *lwarpmk* or a css file in `lwarp.dtx`:

1. Change the source in `lwarp.dtx`.
2. `pdflatex lwarp.ins -or- pdflatex core.ins`
3. `pdflatex lwarp.dtx`
4. If modifying *lwarpmk* the new version should now be active.
5. If modifying css files or other files generated by `lwarp`:
 - (a) For the document, `lwarpmk print` to update the css files in the project.
 - (b) Reload the HTML document to see the effect of the new css files.

Sometimes it is worth checking the `<project>_html.pdf` file, which is the PDF containing HTML tags. Also, `<project>_html.html` has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and CSS code.

12.5 Modifying *lwarpmk*

Prog `lwarpmk`
File `lwarpmk.lua`

In most installations, `lwarpmk.lua` is an executable file located somewhere the operating system knows about, and it is called by typing **lwarpmk** into a terminal.

A project-local copy of `lwarpmk.lua` may be generated, modified, and then used to compile documents:

1. Add the `lwarpmk` option to the `lwarp` package.
2. Recompile the printed version of the document. The `lwarpmk` option causes `lwarp` to create a local copy of `lwarpmk.lua`
3. The `lwarpmk` option may now be removed from the `lwarp` package.
4. Copy and rename `lwarpmk.lua` to a new file such as `mymake.lua`.
5. Modify `mymake.lua` as desired.
6. If necessary, make `mymake.lua` executable.
7. Use `mymake.lua` instead of `lwarpmk.lua`.

13 Troubleshooting

13.1 lwarp package error conditions and warnings

lwarp tests for a number of error conditions and prints appropriate warnings. The following is a summary of these conditions.

13.1.1 Configuration file `lwarpmk.conf`

File does not exist: The configuration file must exist for `lwarpmk`.

Incorrect Unix /Windows selection: The operating system which was detected by `lwarp`. So far only Unix and Windows are supported.

Incorrect delimiter characters. Older versions of `lwarpmk` used a different delimiter.

Source name is set to `lwarp`: `lwarp` has recently been recompiled in this directory, which overwrote the project's configuration files. This also occurs if `lwarpmk` is executed in `lwarp`'s source directory.

Incorrect operating system: The configuration file was set for a different operating system, perhaps due to sharing in a collaborative project.

Outdated configuration files: `lwarp` has been updated since this project was last compiled. If there appears to be a valid print command in the file, `lwarpmk` displays this to instruct the user how to recompile the print version, which then updates the configuration files.

The designated source file does not exist: For whatever reason...

Unknown engine: `lwarp` cannot determine which engine is being used. Supported are DVI L^AT_EX, PDF L^AT_EX, X_YL^AT_EX, LuaL^AT_EX, and upL^AT_EX.

13.1.2 Image generation with `lwarpmk limages`

“Wait a moment for the images to complete before reloading page.”:

Images are generated by background tasks. If the document is reloaded before these tasks are complete, some images may not yet be generated. `lwarpmk` tries to wait for background tasks to complete before exiting.

HTML version does not exist: Images are extracted from the HTML version, which must be compiled before images are generated.

***-images.txt does not exist:** This file tells which images to extract from the HTML file. If the file does not exist, it may be that no SVG math or `lateximages` were used. If so, `lwarpmk limages` is not necessary.

Cross references are not correct: The document must have up-to-date cross references to locate the images to extract. A number of conditions may cause incorrect cross references.

“WARNING: Images will be incorrect.”: An image reference was not found. Re-compile.

`lwarpmk epstopdf *` or `lwarpmk pdftosvg *`: Errors if filenames are not found.

13.1.3 Default bitmapped font

lwarp requires the use of a vector font. If lwarp detects that the document uses the default COMPUTER MODERN font, and the cm-super package is not installed, it is assumed that the font is bitmapped. An error is generated, along with the recommendation to install cm-super or use lmodern.

13.1.4 Packages

Loaded before lwarp: Some packages and classes must be loaded before lwarp. These include input and font encoding, morewrites and newclude, and a number of CJK-related packages and classes.

Loaded after lwarp: Most packages which are modified by lwarp must be loaded after lwarp.

Loaded never: Some packages do not work with lwarp. An error is generated, along with a list of alternatives to consider.

Specific packages: Some packages enforce a specific load order vs. certain other packages.

Patching error: lwarp tries to patch some packages using xpatch. If the original package has been updated more recently than lwarp, a patch may not work. It may be necessary to use an older version of the package until lwarp is updated.

longtable: lwarp's longtable package issues detailed error messages regarding the use of the table headers and footers.

polyglossia: If used, an informative message is printed to instruct the user to be sure to set a language, without which an error will occur.

babel or polyglossia: An informative message is printed to note that not all languages are supported by cleveref.

13.1.5 Compiling

SideTOCDepth < FileDepth: A warning is displayed if these counters are set such that the sideroc will not be able to access all pages of the website.

Filenames: lwarp may generate file names from section names. While doing so, the filenames are simplified, and special characters and math are removed. If this process generates a duplicate filename, and error is generated, describing the filename and which section name generated it. A warning is issued if dollar-delimited math is used. Parenthesis-delimited math is recommended instead.

 **HTML corrupted** **Multirow:** When \multirow or \multicolrow are used, \mrowcell or \mcolrowcell must be placed in the appropriate cells to avoid corrupted HTML output.

(width,height) missing a comma: \makebox and \framebox can accept a parenthesis-delimited width and height, which must be separated by a comma.

“Load graphicx or graphics for improved svg math baselines.”: svg math sizing and baselines are improved if either of these packages are used.

“Load graphicx or graphics for improved XeTeX logo.”: If these packages are loaded, the Xe_{La}TeX logo can use the reversed “E”.

“It is recommended to use [width=xx\linewidth] instead of [scale=yy] ”: Browser support of scale does not have the same effect as in L^AT_EX.

13.2 Using the lwarp package

The following address problems which may occur, and possible solutions to each.

Also see:

Section 7.11: [Commands to be placed into the warpprint environment](#)

Section 8: [Special cases and limitations](#)

△ **HTML corrupted** **Text is not converting correctly / corrupted HTML tags:**

- Font-related UTF-8 information must be embedded in the PDF file. See section 7.4 regarding bitmapped vs. vector fonts.
- See section 8.2.1 regarding HTML entities and the characters &, <, and >.

△ **dotlessj** **Dotless j (\j):** See section 7.4 regarding cmap, mmap.

Undefined HTML settings:

- See the warning regarding the placement of the HTML settings at section 7.6.

Tabular problems: See section 8.10.1.

Obscure error messages:

Print first: Be sure that a print version of the document compiles and that your document’s L^AT_EX code is correct, before attempting to generate an HTML version.

`\end{warpHTML}, \end{warpprint}, \end{warpall}, \end{warpMathJax}:`

Each of these must be without any other characters on the same line.

“Runaway argument? File ended while scanning use of \next:

Don’t use warpHTML, warpprint, warpall, or warpMathJax inside itself.

Options clash: If using memoir, see section 8.13.

“Missing \begin{document}.”: Some packages require that their options be specified before lwarp is loaded, or via the package’s setup macro, especially if these options include the use of braces. See section 8.1.

“No room for a new \write.”: Before `\usepackage{lwarp}`, add:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
```

“! TeX capacity exceeded, sorry [text input levels=15].”: Packages were nested too many levels deep. Locate the file `texmf.cnf` for your distribution, and add the line

```
max_in_open = 30
```

“Missing \$ inserted.”: If using a filename or URL in a footnote or `\item`, escape underscores with `_.`

△ [warpHTML](#), [warpprint](#),
[warpMathJax](#), [warpall](#)

“Label(s) may have changed. Rerun to get cross-references right.”:

This warning may repeat endlessly if a math expression is used in a caption. Simple math expressions such as $X=1$ may be replaced with

```
\textit{X}\,=\,1
```

“Temporary page! LaTeX was unable to guess the total number of pages ...”:

Harmless. Recompile the document one more time.

“Leaders not followed by proper glue”:

This can be caused by a missing `\l@<floastype>` or `\l@<sectiontype>` definition. See `lwarp`'s definitions for examples.

“Improper \prevdepth”: `lateximages` and `svg` math require `\newpage`, which cannot work inside `TEX` boxes or `\ensuremath`. Anything using `\newsavebox`, `\newbox`, `Lrbox`, `\savebox`, `\hbox`, `\vbox`, `\usebox`, `\sbox`, etc., must be modified to work without box commands.

If you find something using `\ensuremath`, have it temporarily set:

```
\LetLtxMacro\@ensuredmath\LWR@origensuredmath
```

inside a group first.

`LWR@texboxdepth`

As a stop-gap measure, you may wish to try incrementing the counter `LWR@texboxdepth` before the problematic macro, and then decrementing it after. Doing so tells `lwarp` to avoid using a `\newpage` inside the macro, which may avoid this error.

Also, custom macros which appear inside a section, figure, or table name should be made robust since they appear inside the `.toc`, `.lof`, or `.lot` files. Use `\newrobustcmd` or `\robustify` from `etoolbox`, `xparse`, etc.

If using BibTeX, see section 8.6.9.

“! Undefined control sequence. . . . __hook begindocument”:

See section 8.15.4 if using `polyglossia`.

“\begin{equation} ended by \end{document}”: Do not use custom macros such as `\beq` and `\eeq` to replace

```
\begin{equation}
. . .
\end{equation}
```

“Misplaced \omit”: If using `\LWR@formatted` to define new macros for print and HTML modes, see section 36 regarding `\LWR@expandableformatted`.**“Token not allowed in a PDF string”:** This `hyperref` warning appears while creating the print-mode document, not HTML. A low-level macro is being used in a section name which appears in the PDF bookmarks. `hyperref` removes this macro from the bookmark, and warns of doing so. To avoid this warning, use `\pdfstringdefDisableCommands` in the preamble to define simplified replacement macros for each, or use `\texorpdfstring` in the `\section` or related macro to declare what to use for the `TEX` text, v.s. the PDF bookmark. See the `hyperref` manual.**“Command \textquoteright invalid in math mode”:** This can occur when the document source has math containing the slanted quote ' character, instead of using the upright quote ’ character.**“Complicated objects inside math”:** Some objects, such as `Tikz`, may not compile in `lwarp`'s normal math emulation. Insert

⚠ macros in section, table, figure names

⚠ BibTeX

⚠ `polyglossia`

⚠ custom macros for environments

⚠ `\LWR@formatted`

⚠ quote character

⚠ “impure” math objects

`\displaymathother` — *or* — `\inlinemathother`
 before the math, and then
`\displaymathnormal` — *or* — `\inlinemathnormal`
 when displaying “normal” math. See section 8.7.10.

Slow compilation of math objects: Complicated math objects can also cause problems with alt tags, resulting in very slow compilation, large alt tags, and possible crashes. Use `\inlinemathother ... \inlinemathnormal` or `\displaymathother ... \displaymathnormal` around the math expression.

⚠ **MATHJAX** **Incorrect MATHJAX:** Some objects do not convert to MATHJAX. Use `\displaymathother` before these objects, then `\displaymathnormal` to return to “normal” display math. See section 8.7.10.

Missing sections: See section 7.6 regarding the `FileDepth` and `SideTOCDepth` counters, and the use of `\tableofcontents` in the home page.

Misnumbered footnotes from section headings: See section 8.5.4.

Missing HTML files:

- See the warning regarding changes to the HTML settings at section 7.6.
- Ensure that the filenames are unique after math and short words are removed. See `FileSectionNames` at section 7.6.

Missing / incorrect cross-references:

- Use `lwarpmk` again followed by `lwarpmk html` or `lwarpmk print` to compile the document one more time.
- Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).
`\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.
- `cleveref` and `varioref` are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

Ex:

```
\cpageref{tab:first,tab:second}
```

in html becomes:

“pages **for** table 4.1 and **for** table 4.2”

See `\cpagerefFor` at page 730 to redefine the message which is printed for page number references.

BibTeX errors with `\eta\char`: See section 8.6.9.

Malformed URLs: Do not use the % character between arguments of `\hyperref`, etc., as this character is among those which is neutralized for inclusion in HTML URLs.

Em-dashes or En-dashes in listing captions and titles:

Use `XYLATEX` or `LuaATEX`.

labels

⚠ label characters

`\nameref`

⚠ empty link

⚠ cleveref page numbers

Floats out of sequence:

Mixed “Here” and floating: Floats [H]ere and regular floats may become out of order. `\clearpage` if necessary.

Caption setup: With `\captionsetup` set the positions for the captions above or below to match their use in the source code.

Images are appearing in strange places:

- When images are added or removed, Enter `lwarpmk limages` to refresh the `lateximage` images.

svg images:

⚠ adding/removing

When a math expression, `picture`, or `Tikz` environment is added or removed, the `svg` images must be re-created by entering `lwarpmk limages` to maintain the proper image-file associations. Inline `svg` math may be hashed and thus not need to be recreated, but display math and objects such as `Tikz` may move to new image numbers when the document is changed.

recompile first

Before attempting to create the `svg` image files, `lwarpmk` verifies that the `HTML` version of the document exists and has correct internal image references.¹⁶ If it is necessary to recompile the document’s `HTML` version one more time, `lwarpmk` usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the `LATEX` recompile warnings.

⚠ HTML instead of images

If `HTML` appears where an `svg` image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect `svg` images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

⚠ Lots of files!

Expressing math as `svg` images has the advantage of representing the math exactly as `LATEX` would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, `lwarp` uses an MD5 hash on its `LATEX` source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and `Tikz` require one image file each. For a document with a large amount of math, see section 5.5 to use `MATHJAX` instead.

Plain-looking document:

- The document’s `css` stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFILENAME` statements point to a valid `css` file.

⚠ HTML corrupted

Broken fragments of HTML:

- Check the `PDF` file used to create `HTML` to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

Changes do not seem to be taking effect:

¹⁶This becomes important when dealing with a document containing thousands of images.

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the HTML settings at section 7.6.
- Verify that the proper CSS is actually being used.
- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

Un-matched conditional compiles:

- Verify the proper begin/end of `warpprint`, `warpHTML`, and `warpall` environments.

13.2.1 Debug tracing output

`\tracinglwarp`

When `\tracinglwarp` is used, `lwarp` will add extra tracing messages to the `.log` file. The last several messages may help track down errors.

Place `\tracinglwarp` just after `\usepackage{lwarp}` to activate tracing.

13.3 Compiling the `lwarp.dtx` file

lwarp_tutorial.tex: Copy or link `lwarp_tutorial.txt` from the TDS doc directory to the source directory, or wherever you wish to compile the documentation. This file is included verbatim in the documentation, but is in the doc directory so that it may be found by *texdoc* and copied by the user.

Illogical error messages caused by an out-of-sync `lwarp.sty` file:

1. Delete the `lwarp.sty` file.
2. Enter `pdflatex lwarp.ins` to generate a new `lwarp.sty` file.
3. Enter `pdflatex lwarp.dtx` to recompile the `lwarp.pdf` documentation.

Un-nested environments:

Be sure to properly nest:

- `\begin{macrocode}` and `\end{macrocode}`
- `\begin{macro}` and `\end{macro}`
- `\begin{environment}` and `\end{environment}`

14 Trademarks

- T_EX is a trademark of American Mathematical Society.
- ADOBE® and ADOBE *Framemaker*® are either registered trademarks or trademarks of ADOBE SYSTEMS INCORPORATED in the United States and/or other countries.
- LINUX® is the registered trademark of Linus Torvalds in the U.S. and other countries.
- MAC OS® is a trademark of APPLE INC.
- MADCAP FLARE™ is the property of MADCAP SOFTWARE, INC.
- MATHJAX is copyright 2009 and later. The MATHJAX CONSORTIUM is a joint venture of the AMERICAN MATHEMATICAL SOCIETY (AMS) and the SOCIETY FOR INDUSTRIAL AND APPLIED MATHEMATICS (SIAM) to advance mathematical and scientific content on the web.
- MICROSOFT®, ENCARTA, MSN, and WINDOWS® are either registered trademarks or trademarks of MICROSOFT CORPORATION in the United States and/or other countries.
- UNIX® is a registered trademark of THE OPEN GROUP.
- YOUTUBE™ is trademark of GOOGLE LLC.

File 1 **lwarp.sty**

15 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of ~~erude~~ ~~haeks~~ clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include `xcolor` with its color models and conversion to HTML color output, and `siunitx` which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by *pdftotext*.

Packages were emulated where their primary purpose was visual formatting which is not relevant to HTML output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in HTML output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a `lateximage` environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

Table 12: Section depths and HTML headings

Section	L ^A T _E X depth	HTML headings *
Title of the entire website		<h1>
(none)	-5	new for this package
book	-2	<div class = "book">
part	-1	<h2>
chapter	0	<h3>
section	1	<h4>
subsection	2	<h5>
subsubsection	3	<h6>
paragraph	4	
subparagraph	5	
listitem	7	new for this package, used for list items

* If FormatWP is true, section headings may be adjusted, depending on WPTitleHeading. See table 11 on page 183.

16 Section depths and HTML headings

Stacks are created to track depth inside the L^AT_EX document structure. This depth is translated to HTML headings as shown in table 12. “Depth” here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the L^AT_EX document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Support for the memoir package will require the addition of a book level, which may push the HTML headings down a step, and also cause subsubsection to become a <div> due to a limit of six HTML headings.

It is possible to use HTML5 <section> and <h1> for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the CSS to remain fixed as well.

17 Source code

This is where the documented source code for `lwarp` begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the `lwarp` package.

line numbers The small numbers at the left end of a line refer to line numbers in the `lwarp.sty` file.

subjects Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph. These are often the targets of index entries.

index entries Black-colored tags in the left margin are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are command macros. Each of these also appears in the index as individual entries, and are also listed together under “files”, “packages”, “environments”, “booleans”, and “counters”.

 **warnings** Special warnings are marked with a warning icon.

for HTML output:
for PRINT output:
for HTML & PRINT: Green-colored tags in the left margin show which sections of source code apply to the generation of HTML, print, or both forms of output.

18 Detecting the T_EX engine — *pdf_latex*, *lua_latex*, *xelatex*

See: <http://tex.stackexchange.com/a/47579>.

Detects X_YT_EX and Lua^AT_EX:

```

1 \RequirePackage{iftex}[2019/11/07]
2 \RequirePackage{ifpdf}
3 \RequirePackage{ifptex}
4
5 \newif\ifxetexorluatex
6
7 \ifXeTeX
8   \xetexorluatextrue
9 \else
10  \ifLuaTeX
11    \xetexorluatextrue
12  \else
13    \xetexorluatexfalse
14  \fi
15 \fi

```

19 Early package requirements

Pkg etoolbox

Provides `\ifbool` and other functions.

```
16 \RequirePackage{etoolbox}[2011/01/03]% v2.6 for \BeforeBeginEnvironment, etc.
```

Patch to fix copy of environment with a `\par`:

<https://github.com/josephwright/etoolbox/issues/35>

```
17 \long\def\etb@carsquare#1#2#3\@nil{#1#2}
```

Pkg xpatch

Patches macros with optional arguments.

```
18 \RequirePackage{xpatch}
```

Pkg ifplatform

Provides `\ifwindows` to try to automatically detect WINDOWS OS.

```
19 \RequirePackage{ifplatform}% sense op-system platform
```

Pkg letltxmacro

```
20 \RequirePackage{letltxmacro}
```

20 Package load order

Several packages must never be used with `lwarp`, others should only be loaded before `lwarp`, and others should only be loaded after. The `lwarp` core checks most

of these cases. In some `lwarp-*` packages, `\LWR@loadbefore` is used to trigger an error if they are loaded after `lwarp`, while additional code provides necessary patches for when they are loaded before.

Packages which must be loaded after `lwarp` are enforced by a large number of `\LWR@loadafter` statements, below. Some packages are emulated by `memoir`, and so these are tested by `\LWR@notmemoirloadafter`, which does not cause an error if `memoir` is used.

`\LWR@checkloadfilename` is used to check each filename to see if it must never be loaded, or must always be loaded before `lwarp`.

20.1 Tests of package load order

`\LWR@loadafter` $\{\langle packagename \rangle\}$ Error if this package was loaded before `lwarp`.

```

21 \newcommand*\LWR@loadafter}[1]{%
22 \IfPackageLoadedTF{#1}
23 {
24   \PackageError{lwarp}
25     {%
26       Package #1,\MessageBreak
27       or one which uses #1,\MessageBreak
28       must be loaded after Lwarp.\MessageBreak
29       Enter 'H' for possible solutions%
30     }
31     {%
32       Move ‘‘\protect\usepackage{#1}’’ after
33       ‘‘\protect\usepackage{lwarp}’’.\MessageBreak
34       Package #1 may also be loaded by something else,\MessageBreak
35       which must also be moved after Lwarp.%
36     }
37 }
38 {\relax}
39 }

```

`\LWR@notmemoirloadafter` $\{\langle packagename \rangle\}$ Error if not `memoir` class and this package was loaded before `lwarp`.

`memoir` emulates many packages, and pretends that they have already been loaded.

```

40 \IfClassLoadedTF{memoir}
41 {\newcommand*\LWR@notmemoirloadafter}[1]{}
42 {\LetLtxMacro\LWR@notmemoirloadafter\LWR@loadafter}

```

`\LWR@notltjloadafter` $\{\langle packagename \rangle\}$ Error if not a `ltjs*` class and this package was loaded before `lwarp`.

```

43 \LetLtxMacro\LWR@notltjloadafter\LWR@loadafter
44
45 \IfClassLoadedTF{ltjarticle}{\renewcommand*\LWR@notltjloadafter}[1]{}{}
46 \IfClassLoadedTF{ltjbook}{\renewcommand*\LWR@notltjloadafter}[1]{}{}
47 \IfClassLoadedTF{ltjreport}{\renewcommand*\LWR@notltjloadafter}[1]{}{}
48 \IfClassLoadedTF{ltjsarticle}{\renewcommand*\LWR@notltjloadafter}[1]{}{}

```

```

49 \IfClassLoadedTF{tjtsbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}}
50 \IfClassLoadedTF{tjtsreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}}
51 \IfClassLoadedTF{tjtspf}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}}
52 \IfClassLoadedTF{tjtskiyou}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}}
53 \IfClassLoadedTF{tjtarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}}
54 \IfClassLoadedTF{tjtbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}}
55 \IfClassLoadedTF{tjtreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}}

```

`\LWR@loadbefore` $\{\langle package name \rangle\}$ Error if this package is loaded after `lwarp`.

```

56 \newcommand*{\LWR@loadbefore}[1]{%
57 \IfPackageLoadedTF{#1}
58 {\relax}
59 {
60   \PackageError{lwarp}
61   {%
62     Package #1 must be loaded before lwarp.\MessageBreak
63     Enter 'H' for possible solutions%
64   }
65   {Move ‘‘\protect\usepackage{#1}’’ before ‘‘\protect\usepackage{lwarp}’’..}
66 }
67 }

```

`\LWR@checkloadbefore` $\{\langle package name \rangle\}$

Given `\LWR@tempone` is the package name to compare to, if package names match, error if it is loaded after `lwarp`.

```

68 \newcommand*{\LWR@checkloadbefore}[1]{%
69   \ifdefstring{\LWR@tempone}{#1}{%
70     \LWR@loadbefore{#1}%
71   }{ }%
72 }

```

`\LWR@loadnever` $\{\langle bad package name \rangle\} \{\langle replacement pkg names \rangle\}$

The first packages is not supported, so tell the user to use the second instead. Factored from `\LWR@checkloadnever` and `\LWR@earlyloadnever`.

```

73 \newcommand*{\LWR@loadnever}[2]{%
74 \PackageError{lwarp}
75 {%
76   Package #1 is not yet supported\MessageBreak
77   by lwarp's HTML conversion%
78   \ifblank{#2}{}{
79     .\MessageBreak
80     Package(s)\MessageBreak
81     \space\space#2\MessageBreak
82     may be useful instead%
83   }%
84 }
85 {%
86   Package #1 might conflict with lwarp in some way,\MessageBreak
87   or is superceded by another package.%
88   \ifblank{#2}{}{
89     \MessageBreak
90     For possible alternatives, see package(s) #2.%

```

```

91    }%
92 }
93 }

```

`\LWR@afterloadnever` $\{\langle badpackagename \rangle\} \{\langle replacementpkgnames \rangle\}$

Given: `\LWR@tempone` is set to the package name being tested against, if this package name is the bad packagename, suggest the replacements instead. This is used when loading packages after `lwarp`.

```

94 \newcommand*\LWR@afterloadnever[2]{%
95   \ifdefstring{\LWR@tempone}{#1}{%
96     \LWR@loadnever{#1}{#2}%
97   }{ }%
98 }

```

`\LWR@earlyloadnever` $\{\langle badpackagename \rangle\} \{\langle replacementpkgnames \rangle\}$

The first package is not supported, so tell the user to use the second instead. This version checks immediately for packages which may have been loaded before `lwarp`.

```

99 \newcommand*\LWR@earlyloadnever[2]{%
100   \IfPackageLoadedTF{#1}{%
101     \LWR@loadnever{#1}{#2}%
102   }{ }%
103 }

```

`\LWR@earlyclassloadnever` $\{\langle badclassname \rangle\} \{\langle replacementclassname \rangle\}$

The first class is not supported, so tell the user to use the second instead. This version checks immediately for classes which may have been loaded before `lwarp`.

```

104 \newcommand*\LWR@earlyclassloadnever[2]{%
105   \IfClassLoadedTF{#1}{%
106     \PackageError{lwarp}
107     {%
108       Class #1 is not supported\MessageBreak
109       by lwarp's HTML conversion%
110       \ifblank{#2}{ }{%
111         .\MessageBreak
112         #2 may be useful instead%
113       }%
114     }
115     {%
116       Class #1 might conflict with lwarp in some way,\MessageBreak
117       or is superceded by another class.%
118       \ifblank{#2}{ }{%
119         \MessageBreak
120         For a possible alternative, see #2.%
121       }%
122     }
123   }{\relax}%
124 }

```

20.2 Error for disallowed packages and classes loaded before lwarp

`\LWR@checkloadnevers` Checks against a list of incompatible packages.

```
125 \newcommand*{\LWR@checkloadnevers}{
126 \LWR@checkloadnever{ae}{cm-super, lmodern}
127 \LWR@checkloadnever{aeopl}{cm-super, lmodern}
128 \LWR@checkloadnever{aecc}{cm-super, lmodern}
129 \LWR@checkloadnever{alg}{algorithm2e, algorithmicx}
130 \LWR@checkloadnever{algorithmic}{algorithm2e, algorithmicx}
131 \LWR@checkloadnever{bitfield}{bytefield}
```

`bxckatype` is based on CJK:

```
132 \LWR@checkloadnever{bxckatype}{upLaTeX, bxjsarticle, uarticle, utarticle}

133 \LWR@checkloadnever{caption2}{caption}
134 % \LWR@checkloadnever{ccaption}{caption}% might be preloaded by memoir
135 \LWR@checkloadnever{colortab}{colortbl}
136 \LWR@checkloadnever{csvtools}{datatool}
137 \LWR@checkloadnever{doublespace}{setspace}
138 \LWR@checkloadnever{fancyheadings}{fancyhdr}
139 \LWR@checkloadnever{fncylab}{cleveref}
140 \LWR@checkloadnever{formula}{siunitx}
141 \LWR@checkloadnever{glossary}{glossaries}
```

`hangul` is not in TeXLive, and is not tested:

```
142 \LWR@checkloadnever{hangul}{kotex, xetexko, luatexko}

143 \LWR@checkloadnever{hyper}{hyperref}
144 \LWR@checkloadnever{libgreek}{libertinust1math, newtx}
145 \LWR@checkloadnever{newthm}{ntheorem}
146 \LWR@checkloadnever{pdfcprot}{microtype}
147 \LWR@checkloadnever{picins}{floatflt, wrapfig, wrapfig2}
148 \LWR@checkloadnever{rplain}{fancyhdr}
149 \LWR@checkloadnever{si}{siunitx}
150 \LWR@checkloadnever{sistyle}{siunitx}
151 \LWR@checkloadnever{slashbox}{diagbox}
152 \LWR@checkloadnever{statex}{statex2}
153 \LWR@checkloadnever{t1enc}{fontenc, inputenc, inputenx}
154 \LWR@checkloadnever{ucs}{inputenc, inputencx}
155 \LWR@checkloadnever{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

The following may one day be supported by lwarp:

```
156 % \LWR@checkloadnever{adjustbox}{}% req'd for menukeys
157 \LWR@checkloadnever{animate}{}
158 \LWR@checkloadnever{auto-pst-pdf}{}
159 \LWR@checkloadnever{auto-pst-pdf-lua}{}
160 \LWR@checkloadnever{algorithms}{}
161 \LWR@checkloadnever{arraycols}{}
162 \LWR@checkloadnever{bidi}{}
163 \LWR@checkloadnever{cals}{}

164 \LWR@checkloadnever{cellspace}{tbls}
```

```
165 \LWR@checkloadnever{cgloss4e}{}  
166 \LWR@checkloadnever{collcell}{}  
167 \LWR@checkloadnever{colophon}{}  
168 \LWR@checkloadnever{cooltooltips}{}  
169 \LWR@checkloadnever{covington}{}  
170 \LWR@checkloadnever{crbox}{}  
171 \LWR@checkloadnever{decision-table}{}  
172 \LWR@checkloadnever{dvgloss}{}  
173 \LWR@checkloadnever{ednotes}{}  
174 \LWR@checkloadnever{edfnotes}{}  
175 \LWR@checkloadnever{eledform}{}  
176 \LWR@checkloadnever{eledmac}{}  
177 \LWR@checkloadnever{embedfile}{}  
178 \LWR@checkloadnever{endnotes-hy}{endnotes}  
179 \LWR@checkloadnever{expex}{}  
180 \LWR@checkloadnever{fancytooltips}{}  
181 \LWR@checkloadnever{fixocgx}{}  
182 \LWR@checkloadnever{flowfram}{}  
183 \LWR@checkloadnever{gb4e}{}  
184 \LWR@checkloadnever{gmverse}{}  
185 \LWR@checkloadnever{graphbox}{}  
186 \LWR@checkloadnever{graphicxbox}{}  
187 \LWR@checkloadnever{hvfloat}{}  
188 \LWR@checkloadnever{inline-images}{}  
189 \LWR@checkloadnever{isorot}{rotating}  
190 \LWR@checkloadnever{ledmac}{}  
191 \LWR@checkloadnever{linguex}{}  
192 \LWR@checkloadnever{longdiv}{}  
193 \LWR@checkloadnever{longfigure}{}  
194 \LWR@checkloadnever{longtabu}{}  
195 \LWR@checkloadnever{mdwenv}{}  
196 \LWR@checkloadnever{mdwlist}{}  
197 \LWR@checkloadnever{mdwtab}{}  
198 \LWR@checkloadnever{navigator}{}  
199 \LWR@checkloadnever{nccpic}{}  
200 \LWR@checkloadnever{nccsect}{}  
201 \LWR@checkloadnever{newvbtm}{}  
202 \LWR@checkloadnever{ocg-p}{}  
203 \LWR@checkloadnever{ocgtools}{}  
204 \LWR@checkloadnever{ocgx}{}  
205 \LWR@checkloadnever{ocgx2}{}  
206 \LWR@checkloadnever{parrun}{}  
207 \LWR@checkloadnever{poemscol}{}  
208 \LWR@checkloadnever{poetry}{}  
209 \LWR@checkloadnever{program}{}  
210 \LWR@checkloadnever{proofread}{}  
211 \LWR@checkloadnever{pst-pdf}{}  
212 \LWR@checkloadnever{refstyle}{}  
213 \LWR@checkloadnever{robustindex}{}  
214 \LWR@checkloadnever{robustglossary}{}  
215 \LWR@checkloadnever{semioneseid}{}  
216 \LWR@checkloadnever{slemph}{}  
217 \LWR@checkloadnever{snotez}{sidenotes}  
218 \LWR@checkloadnever{spacingtricks}{}  
219 \LWR@checkloadnever{sverb}{verbatim, fancyvrb}  
220 \LWR@checkloadnever{syntax}{}  
221 \LWR@checkloadnever{tablists}{}  
222 \LWR@checkloadnever{tabto}{}  
223 \LWR@checkloadnever{tabu}{}  
224 \LWR@checkloadnever{tabularht}{}
```

```

225 \LWR@checkloadnever{tabularkv}{}
226 \LWR@checkloadnever{thumby}{}
227 \LWR@checkloadnever{titles}{}
228 \LWR@checkloadnever{typehtml}{}
229 \LWR@checkloadnever{unicode-bidi}{}
230 \LWR@checkloadnever{vcell}{}
231 \LWR@checkloadnever{xhfill}{}
232 }

```

`\LWR@checkloadnever` $\{\langle badpackage \rangle\} \{\langle replacementpkgname \rangle\}$

The first package is not supported, so tell the user to use the second instead.

When `lwarp` is first loaded, this is set to `\LWR@earlyloadnever` to check for incompatible packages which were loaded before `lwarp`. After `lwarp` is loaded, this is changed to `\LWR@afterloadnever` to check for incompatible packages during `\usepackage`.

```
233 \LetLtxMacro\LWR@checkloadnever\LWR@earlyloadnever
```

Now check for incompatible packages which have been loaded before `lwarp`:

```
234 \LWR@checkloadnevers
```

The older `CJK` and `CJKutf8` only work with `xeCJK`:

```

235 \IfPackageLoadedTF{xeCJK}{}{
236   \LWR@checkloadnever{CJK}{ctex, xeCJK}
237   \LWR@checkloadnever{CJKutf8}{ctex, xeCJK}
238 }

```

Some classes do not work with `lwarp`:

```

239 \LWR@earlyclassloadnever{beamer}{beamerarticle}
240 \LWR@earlyclassloadnever{jarticle}{ujarticle}
241 \LWR@earlyclassloadnever{jbook}{ujbook}
242 \LWR@earlyclassloadnever{jreport}{ujreport}
243 \LWR@earlyclassloadnever{tarticle}{utarticle}
244 \LWR@earlyclassloadnever{tbook}{utbook}
245 \LWR@earlyclassloadnever{treport}{utreport}
246 \LWR@earlyclassloadnever{novel}{}
247 \LWR@earlyclassloadnever{powerdot}{}

```

20.3 Enforcing package loading after `lwarp`

Packages which should only be loaded after `lwarp` are tested here to trip an error if they have already been loaded.

The following packages must be loaded after `lwarp`:

```

248 \LWR@loadafter{2in1}
249 \LWR@loadafter{2up}
250 \LWR@loadafter{a4}
251 \LWR@loadafter{a4wide}
252 \LWR@loadafter{a5comb}
253 \LWR@notmemoirlloadafter{abstract}

```

```
254 \LWR@loadafter{academicons}
255 \LWR@loadafter{accents}
256 \LWR@loadafter{accessibility}
257 \LWR@loadafter{accsupp}
258 \LWR@loadafter{acro}
259 \LWR@loadafter{acronym}
260 \LWR@loadafter{adjmulticol}
261 \LWR@loadafter{addlines}
262 \LWR@loadafter{afterpage}
263 \LWR@loadafter{algorithm2e}
264 \LWR@loadafter{algorithmicx}
265 \LWR@loadafter{alltt}
266 \LWR@loadafter{amscdx}
267 % \LWR@loadafter{amsmath}% may be preloaded
268 % \LWR@loadafter{amsthm}% may be preloaded
269 \LWR@loadafter{anonchop}
270 \LWR@loadafter{anysize}
271 \LWR@notmemoirloadafter{appendix}
272 \LWR@loadafter{ar}
273 \LWR@loadafter{arabicfront}
274 \LWR@notmemoirloadafter{array}
275 \LWR@loadafter{arydshln}
276 \LWR@loadafter{asymptote}
277 % \LWR@loadafter{atbegshi}% now in LaTeX core, also used by morewrites
278 \LWR@loadafter{attachfile}
279 \LWR@loadafter{attachfile2}
280 \LWR@loadafter{authblk}
281 \LWR@loadafter{authoraftertitle}% Supported as-is, but must be loaded after.
282 \LWR@loadafter{autobreak}
283 \LWR@loadafter{autonum}
284 \LWR@loadafter{awesomebox}
285 \LWR@loadafter{axessibility}
286 \LWR@loadafter{axodraw2}
287 \LWR@loadafter{backnaur}
288 \LWR@loadafter{backref}
289 \LWR@loadafter{balance}
290 \LWR@loadafter{bbding}
291 \LWR@loadafter{beamerarticle}
292 \LWR@loadafter{bigdelim}
293 \LWR@loadafter{bigfoot}
294 \LWR@loadafter{bigstrut}
295 \LWR@loadafter{bitpattern}
296 \LWR@loadafter{blowup}
297 \LWR@loadafter{bm}
298 \LWR@loadafter{booklet}
299 \LWR@loadafter{bookmark}
300 \LWR@notmemoirloadafter{booktabs}
301 \LWR@loadafter{bophook}
302 \LWR@loadafter{bounddvi}
303 \LWR@loadafter{boxedminipage}
304 \LWR@loadafter{boxedminipage2e}
305 \LWR@loadafter{braket}
306 \LWR@loadafter{breakurl}
307 \LWR@loadafter{breqn}
308 \LWR@loadafter{bsheaders}
309 \LWR@loadafter{bussproofs}
310 \LWR@loadafter{bypapersize}
311 \LWR@loadafter{bytefield}
312 \LWR@loadafter{ccicons}
313 \LWR@loadafter{cancel}
```

314 \LWR@loadafter{canoniclayout}
315 \LWR@loadafter{caption}
316 \LWR@loadafter{caption2}
317 \LWR@loadafter{caption3}
318 \LWR@loadafter{cases}
319 % catoptions is supported by the lwarp core
320 % \LWR@loadafter{ccaption}% may be preloaded by memoir
321 \LWR@loadafter{centerlastline}
322 % \LWR@loadafter{centernot}% may be preloaded by newtx
323 \LWR@loadafter{changebar}
324 \LWR@loadafter{changelayout}
325 \LWR@notmemoirloadafter{changepage}
326 \LWR@loadafter{changes}
327 \LWR@loadafter{chappg}
328 \LWR@loadafter{chapterbib}
329 \LWR@loadafter{chemfig}
330 \LWR@loadafter{chemformula}
331 \LWR@loadafter{chemgreek}
332 \LWR@loadafter{chemmacros}
333 \LWR@loadafter{chemnum}
334 \LWR@loadafter{chkfloat}
335 \LWR@notmemoirloadafter{chnpage}
336 \LWR@loadafter{cite}
337 \LWR@loadafter{citeref}
338 \LWR@loadafter{classicthesis}
339 \LWR@loadafter{cleveref}
340 % cmbright may be preloaded
341 \LWR@loadafter{cmdtrack}
342 \LWR@loadafter{colonequals}
343 \LWR@loadafter{color}
344 \LWR@loadafter{colortbl}
345 \LWR@loadafter{continue}
346 \LWR@loadafter{copyrightbox}
347 \LWR@notmemoirloadafter{crop}
348 % ctex must be loaded before lwarp
349 \LWR@loadafter{ctable}
350 \LWR@loadafter{cuted}
351 \LWR@loadafter{cutwin}
352 \LWR@loadafter{dblfloatfix}
353 \LWR@loadafter{dblfnote}
354 \LWR@notmemoirloadafter{dcolumn}
355 \LWR@loadafter{decimal}
356 \LWR@loadafter{decorule}
357 \LWR@loadafter{diagbox}
358 \LWR@loadafter{dingbat}
359 \LWR@loadafter{DotArrow}
360 \LWR@loadafter{dotlessi}
361 \LWR@loadafter{dprogress}
362 \LWR@loadafter{draftcopy}
363 \LWR@loadafter{draftfigure}
364 \LWR@loadafter{draftwatermark}
365 \LWR@loadafter{drftcite}
366 \LWR@loadafter{easy-todo}
367 \LWR@loadafter{ebook}
368 \LWR@loadafter{econometrics}
369 \LWR@loadafter{ed}
370 \LWR@loadafter{ellipsis}
371 \LWR@loadafter{embrac}
372 \LWR@loadafter{emptypage}
373 \LWR@loadafter{endfloat}

```
374 \LWR@loadafter{endheads}
375 \LWR@loadafter{endnotes}
376 \LWR@loadafter{engtlc}
377 \LWR@loadafter{enotez}
378 \LWR@notmemoirloadafter{enumerate}
379 \LWR@loadafter{enumitem}
380 \LWR@notmemoirloadafter{epigraph}
381 \LWR@loadafter{epsf}
382 \LWR@loadafter{epsfig}
383 \LWR@loadafter{epstopdf}
384 \LWR@loadafter{epstopdf-base}
385 \LWR@loadafter{eqlist}
386 \LWR@loadafter{eqparbox}
387 \LWR@loadafter{errata}
388 \LWR@loadafter{eso-pic}
389 \LWR@loadafter{esvect}
390 \LWR@loadafter{etoc}
391 \LWR@loadafter{eurosym}
392 \LWR@loadafter{everypage}
393 % \LWR@loadafter{everyshi}% now in LaTeX core
394 \LWR@loadafter{extrarrows}
395 \LWR@loadafter{extramarks}
396 \LWR@loadafter{fancybox}
397 \LWR@loadafter{fancyhdr}
398 \LWR@loadafter{fancypar}
399 \LWR@loadafter{fancyref}
400 \LWR@loadafter{fancytabs}
401 \LWR@loadafter{fancyvrb}
402 \LWR@loadafter{fbox}
403 \LWR@loadafter{fewerfloatpages}
404 \LWR@loadafter{figcaps}
405 \LWR@loadafter{figsize}
406 \LWR@loadafter{fitbox}
407 \LWR@loadafter{fix2col}
408 \LWR@loadafter{fixmath}
409 \LWR@loadafter{fixme}
410 \LWR@loadafter{fixmetodonotes}
411 \LWR@loadafter{flafter}
412 \LWR@loadafter{flippdf}
413 \LWR@loadafter{float}
414 \LWR@loadafter{floatflt}
415 \LWR@loadafter{floatpag}
416 \LWR@loadafter{floatrow}
417 \LWR@loadafter{fltrace}
418 \LWR@loadafter{flushend}
419 \LWR@loadafter{fnbreak}
420 \LWR@loadafter{fncychap}
421 \LWR@loadafter{fnlineno}
422 \LWR@loadafter{fnpara}
423 \LWR@loadafter{fnpos}
424 \LWR@loadafter{fontawesome}
425 \LWR@loadafter{fontawesome5}
426 % fontenc must be loaded before lwarp
427 % fontspec must be loaded before lwarp
428 \LWR@loadafter{footmisc}
429 \LWR@loadafter{footnote}
430 \LWR@loadafter{footnotebackref}
431 \LWR@loadafter{footnotehyper}
432 \LWR@loadafter{footnoterange}
433 \LWR@loadafter{footnpag}
```

```
434 \LWR@loadafter{foreign}
435 \LWR@loadafter{forest}
436 \LWR@loadafter{fouridx}
437 % fourier may be loaded before lwarp
438 \LWR@loadafter{framed}
439 \LWR@loadafter{froufrou}
440 \LWR@loadafter{ftcap}
441 \LWR@loadafter{ftnright}
442 \LWR@loadafter{fullminipage}
443 \LWR@loadafter{fullpage}
444 \LWR@loadafter{fullwidth}
445 \LWR@loadafter{fvextra}
446 \LWR@loadafter{fwlw}
447 \LWR@loadafter{gensymb}
448 \LWR@loadafter{gentombow}
449 % geometry is always loaded by lwarp, and lwarp-geometry is AtBeginDocument
450 \LWR@loadafter{ghsystem}
451 \LWR@loadafter{gindex}
452 \LWR@loadafter{glossaries}
453 \LWR@loadafter{gmeometric}
454 % \LWR@loadafter{graphics}% pre-loaded by xunicode
455 % \LWR@loadafter{graphicx}% pre-loaded by xunicode
456 \LWR@loadafter{gloss}
457 \LWR@loadafter{glossary}
458 \LWR@loadafter{grffile}
459 \LWR@loadafter{grid}
460 \LWR@loadafter{grid-system}
461 \LWR@loadafter{gridset}
462 \LWR@loadafter{hang}
463 \LWR@loadafter{hanging}
464 \LWR@loadafter{hepunits}
465 \LWR@loadafter{hhline}
466 \LWR@loadafter{hhtensor}
467 \LWR@loadafter{hypbmsec}
468 \LWR@loadafter{hypcap}
469 \LWR@loadafter{hypdestopt}
470 \LWR@loadafter{hypernat}
471 \LWR@loadafter{hyperref}
472 \LWR@loadafter{hyperxmp}
473 \LWR@loadafter{hyphenat}
474 \LWR@loadafter{idxlayout}
475 \LWR@loadafter{ifoddpages}
476 \LWR@loadafter{imakeidx}
477 \LWR@loadafter{impnatty}
478 \LWR@notmemoirloadafter{index}
479 % inputenc must be loaded before lwarp
480 % inputenx must be loaded before lwarp
481 % inputtrc may be loaded before lwarp
482 \LWR@loadafter{intopdf}
483 \LWR@loadafter{isomath}
484 \LWR@loadafter{isotope}
485 \LWR@loadafter{jurabib}
486 \LWR@loadafter{karnaugh-map}
487 \LWR@loadafter{keyfloat}
488 \LWR@loadafter{keystroke}
489 % kpfonts may be loaded before lwarp
490 % kpfonts-otf may be loaded before lwarp
491 \LWR@loadafter{layaureo}
492 \LWR@loadafter{layout}
493 \LWR@loadafter{layouts}
```

```
494 \LWR@loadafter{leading}
495 \LWR@loadafter{leftidx}
496 \LWR@loadafter{letterspace}
497 \LWR@loadafter{letrrine}
498 % libertinust1math may be loaded before lwarp
499 \LWR@loadafter{lineno}
500 \LWR@loadafter{lips}
501 \LWR@loadafter{listings}
502 \LWR@loadafter{listliketab}
503 \LWR@loadafter{lltjp-siunitx}
504 \LWR@loadafter{lltjp-tascmac}
505 \LWR@loadafter{longtable}
506 \LWR@loadafter{lpic}
507 \LWR@loadafter{lscapex}
508 \LWR@loadafter{ltablex}
509 \LWR@loadafter{ltcaption}
510 \LWR@loadafter{ltxgrid}
511 \LWR@loadafter{ltxtable}
512 \LWR@loadafter{lua-check-hyphen}
513 \LWR@loadafter{lua-visual-debug}
514 \LWR@loadafter{luacolor}
515 \LWR@loadafter{luamplib}
516 \LWR@loadafter{luatodonotes}
517 \LWR@loadafter{luavlna}
518 \LWR@loadafter{lyluatex}
519 \LWR@loadafter{magaz}
520 \LWR@notmemoirloadafter{makeidx}
521 \LWR@loadafter{manyfoot}
522 \LWR@loadafter{marginfit}
523 \LWR@loadafter{marginfix}
524 \LWR@loadafter{marginnote}
525 \LWR@loadafter{marvosym}
526 % mathalpha may be loaded before lwarp
527 \LWR@loadafter{mathastext}
528 \LWR@loadafter{mathcomp}
529 \LWR@loadafter{mathdesign}
530 \LWR@loadafter{mathdots}
531 \LWR@loadafter{mathfixs}
532 \LWR@loadafter{mathpazo}
533 \LWR@loadafter{mathptmx}
534 \LWR@loadafter{mathspec}
535 \LWR@loadafter{mathtools}
536 \LWR@loadafter{mattens}
537 \LWR@loadafter{maybemath}
538 \LWR@loadafter{mcaption}
539 \LWR@loadafter{mdframed}
540 \LWR@loadafter{mdwmath}
541 \LWR@loadafter{media9}
542 \LWR@loadafter{memhfixc}
543 \LWR@loadafter{menukeys}
544 \LWR@loadafter{metalogo}
545 \LWR@loadafter{metalogoX}
546 \LWR@loadafter{mhchem}
547 \LWR@loadafter{microtype}
548 \LWR@loadafter{midfloat}
549 \LWR@loadafter{midpage}
550 \LWR@loadafter{minibox}
551 \LWR@loadafter{minitoc}
552 \LWR@loadafter{minted}
553 \LWR@loadafter{mismath}
```

```
554 \LWR@loadafter{mleftright}
555 % morefloats must be allowed early for print mode
556 \LWR@notmemoirloadafter{moreverb}
557 % morewrites must be loaded before lwarp
558 \LWR@notmemoirloadafter{movie15}
559 \LWR@notmemoirloadafter{mparhack}
560 \LWR@loadafter{multibib}
561 \LWR@loadafter{multicap}
562 %\LWR@loadafter{multicol}% loaded by ltxdoc
563 \LWR@loadafter{multicolrule}
564 \LWR@loadafter{multimedia}
565 \LWR@loadafter{multiobjective}
566 \LWR@loadafter{multirow}
567 \LWR@loadafter{multitoc}
568 \LWR@loadafter{musicography}
569 \LWR@loadafter{mwe}
570 \LWR@loadafter{nameauth}
571 \LWR@loadafter{nameref}
572 \LWR@loadafter{natbib}
573 \LWR@notmemoirloadafter{nccfancyhdr}
574 \LWR@loadafter{nccfoots}
575 \LWR@loadafter{nccmath}
576 \LWR@notmemoirloadafter{needspace}
577 % newclude must be loaded before lwarp
578 % newpxmath may be preloaded
579 % newtxmath may be loaded before lwarp
580 % newtxsf may be loaded before lwarp
581 % newunicodechar must be loaded before lwarp
582 \LWR@notmemoirloadafter{nextpage}
583 \LWR@loadafter{nicefrac}
584 \LWR@loadafter{niceframe}
585 \LWR@loadafter{nicematrix}
586 \LWR@loadafter{noitcru1}
587 \LWR@loadafter{nolbreaks}
588 \LWR@loadafter{nomencl}
589 \LWR@loadafter{nonfloat}
590 \LWR@loadafter{nonumonpart}
591 \LWR@loadafter{nopageno}
592 \LWR@loadafter{notes}
593 \LWR@loadafter{notespages}
594 \LWR@loadafter{nowidow}
595 \LWR@loadafter{ntheorem}
596 \LWR@loadafter{octave}
597 \LWR@loadafter{orcidlink}
598 \LWR@loadafter{overpic}
599 \LWR@loadafter{pagegrid}
600 \LWR@notmemoirloadafter{pagenote}
601 \LWR@loadafter{pagesel}
602 \LWR@loadafter{paralist}
603 \LWR@loadafter{parallel}
604 \LWR@loadafter{parcolumns}
605 \LWR@loadafter{parnotes}
606 \LWR@notmemoirloadafter{parskip}
607 \LWR@loadafter{pbalance}
608 \LWR@loadafter{pbox}
609 \LWR@loadafter{pdfcol}
610 \LWR@loadafter{pdfcolfoot}
611 \LWR@loadafter{pdfcolmk}
612 \LWR@loadafter{pdfcolparallel}
613 \LWR@loadafter{pdfcolparcolumns}
```

```
614 \LWR@loadafter{pdfcomment}
615 \LWR@loadafter{pdfcrypt}
616 \LWR@loadafter{pdflandscape}
617 \LWR@loadafter{pdfmarginpar}
618 \LWR@loadafter{pdfpages}
619 \LWR@loadafter{pdfprivacy}
620 \LWR@loadafter{pdfrender}
621 \LWR@loadafter{pdfsync}
622 \LWR@loadafter{pdftricks}
623 \LWR@loadafter{pdfx}
624 \LWR@loadafter{perpage}
625 \LWR@loadafter{pfnote}
626 \LWR@loadafter{phfqit}
627 \LWR@loadafter{physics}
628 \LWR@loadafter{physunits}
629 \LWR@loadafter{picinpar}
630 \LWR@loadafter{pifont}
631 \LWR@loadafter{pinlabel}
632 \LWR@loadafter{placeins}
633 \LWR@loadafter{plarray}
634 \LWR@loadafter{plarydshln}
635 \LWR@loadafter{plextarray}
636 \LWR@loadafter{plextarydshln}
637 \LWR@loadafter{plcolortbl}
638 \LWR@loadafter{plextdelarray}
639 \LWR@loadafter{plimsoll}
640 \LWR@loadafter{prelim2e}
641 \LWR@loadafter{prettyref}
642 \LWR@loadafter{preview}
643 \LWR@loadafter{psfrag}
644 \LWR@loadafter{psfragx}
645 \LWR@loadafter{pst-eps}
646 \LWR@loadafter{pstool}
647 \LWR@loadafter{pstricks}
648 % \LWR@loadafter{pxatbegshi}% may be used by morewrites
649 \LWR@loadafter{pxeveryshi}
650 % \LWR@loadafter{pxfonts}% may be loaded before lwarp
651 \LWR@loadafter{pxftnright}
652 \LWR@loadafter{pxjahyper}
653 \LWR@loadafter{quotchap}
654 \LWR@loadafter{quoting}
655 \LWR@loadafter{ragged2e}
656 \LWR@loadafter{realscripts}
657 \LWR@loadafter{refcheck}
658 \LWR@loadafter{register}
659 \LWR@loadafter{relsize}
660 \LWR@loadafter{repeatindex}
661 \LWR@loadafter{resizgather}
662 \LWR@loadafter{returntograd}
663 \LWR@loadafter{rlepsz}
664 \LWR@loadafter{rmathbr}
665 \LWR@loadafter{rmpage}
666 \LWR@loadafter{romanbar}
667 \LWR@loadafter{romanbarpagenumber}
668 \LWR@loadafter{rotating}
669 \LWR@loadafter{rotfloat}
670 \LWR@loadafter{rviewport}
671 \LWR@loadafter{savetrees}
672 % scalefnt is loaded by babel-french
673 \LWR@loadafter{scalerel}
```

674 \LWR@loadafter{schemata}
675 \LWR@loadafter{scrextend}
676 \LWR@loadafter{scrhack}
677 \LWR@loadafter{scrLayer}
678 \LWR@loadafter{scrLayer-notecolumn}
679 \LWR@loadafter{scrLayer-scrpage}
680 \LWR@loadafter{scrpage2}
681 \LWR@loadafter{section}
682 \LWR@loadafter{sectionbreak}
683 \LWR@loadafter{sectsty}
684 \LWR@loadafter{selectp}
685 \LWR@loadafter{semantic-markup}
686 \LWR@notmemoirloadafter{setspace}
687 \LWR@loadafter{shadow}
688 \LWR@loadafter{shapepar}
689 \LWR@notmemoirloadafter{showidx}
690 \LWR@loadafter{showLabels}
691 \LWR@loadafter{showkeys}
692 \LWR@loadafter{showtags}
693 \LWR@loadafter{shuffle}
694 \LWR@loadafter{sidecap}
695 \LWR@loadafter{sidenotes}
696 \LWR@loadafter{simplebnf}
697 \LWR@loadafter{SIunits}
698 \LWR@loadafter{siunitx}
699 \LWR@loadafter{siunitx-v2}
700 \LWR@loadafter{skmath}
701 \LWR@loadafter{slantsc}
702 \LWR@loadafter{slashed}
703 \LWR@loadafter{soul}
704 \LWR@loadafter{soulpos}
705 \LWR@loadafter{soulutf8}
706 \LWR@loadafter{splitbib}
707 \LWR@loadafter{splitidx}
708 \LWR@loadafter{srcltx}
709 \LWR@loadafter{srctex}
710 \LWR@loadafter{stabular}
711 \LWR@loadafter{stackengine}
712 \LWR@loadafter{stackrel}
713 \LWR@loadafter{statex2}
714 \LWR@loadafter{statistics}
715 \LWR@loadafter{statmath}
716 \LWR@loadafter{steinmetz}
717 \LWR@notltjloadafter{stfloats}
718 \LWR@loadafter{struktex}
719 \LWR@loadafter{subcaption}
720 \LWR@loadafter{subfig}
721 \LWR@loadafter{subfigure}
722 \LWR@loadafter{subsupscripts}
723 \LWR@loadafter{supertabular}
724 \LWR@loadafter{svg}
725 \LWR@loadafter{swfigure}
726 \LWR@loadafter{sympytex}
727 \LWR@loadafter{syntonly}
728 \LWR@loadafter{t1inc}
729 \LWR@loadafter{tabfigures}
730 \LWR@loadafter{tbls}
731 \LWR@loadafter{tablefootnote}
732 \LWR@notmemoirloadafter{tabularx}
733 \LWR@loadafter{tabulary}

```
734 \LWR@loadafter{tagpdf}
735 \LWR@loadafter{tascmac}
736 \LWR@loadafter{tcolorbox}
737 \LWR@loadafter{tensor}
738 \LWR@loadafter{termcal}
739 \LWR@loadafter{textarea}
740 % \LWR@loadafter{textcomp}% maybe before lwarp with font packages
741 \LWR@loadafter{textfit}
742 \LWR@loadafter{textpos}
743 \LWR@loadafter{theorem}
744 \LWR@loadafter{thinsp}
745 \LWR@loadafter{thm-listof}
746 \LWR@loadafter{thm-restate}
747 \LWR@loadafter{thmbox}
748 \LWR@loadafter{thmtools}
749 \LWR@loadafter{threadcol}
750 \LWR@loadafter{threeparttable}
751 \LWR@loadafter{threeparttablex}
752 \LWR@loadafter{thumb}
753 \LWR@loadafter{thumbs}
754 \LWR@loadafter{tikz}
755 \LWR@loadafter{tikz-imagelabels}
756 \LWR@loadafter{titleps}
757 \LWR@loadafter{titlesec}
758 \LWR@loadafter{titletoc}
759 \LWR@notmemoirloadafter{titling}
760 % \LWR@loadafter{tocbasic}% preloaded by koma-script classes
761 \LWR@notmemoirloadafter{tocbibind}
762 \LWR@loadafter{tocdata}
763 \LWR@loadafter{tocenter}
764 \LWR@notmemoirloadafter{tocloft}
765 \LWR@loadafter{tocstyle}
766 \LWR@loadafter{todo}
767 \LWR@loadafter{todonotes}
768 \LWR@loadafter{topcapt}
769 \LWR@loadafter{tram}
770 \LWR@loadafter{transparent}
771 \LWR@loadafter{trimclip}
772 \LWR@loadafter{trivfloat}
773 \LWR@loadafter{truncate}
774 \LWR@loadafter{turnthepage}
775 \LWR@loadafter{twoup}
776 % \LWR@loadafter{txfonts}% may be loaded before lwarp
777 % txgreek may be loaded before lwarp

778 % \LWR@loadafter{typearea}% preloaded by koma-script classes
779 \LWR@loadafter{typicons}
780 % \LWR@loadafter{ulem}% preloaded by ctexart and related classes
781 \LWR@loadafter{umoline}
782 \LWR@loadafter{underscore}
783 % unicode-math may be loaded before lwarp
784 \LWR@loadafter{units}
785 \LWR@loadafter{unitsdef}
786 \LWR@loadafter{upgreek}
787 \LWR@loadafter{upref}
788 \LWR@loadafter{url}
789 \LWR@loadafter{ushort}
790 \LWR@loadafter{uspace}
791 \LWR@loadafter{varioref}
792 \LWR@notmemoirloadafter{verse}
```

```

793 \LWR@loadafter{versonotes}
794 \LWR@loadafter{vertbars}
795 \LWR@loadafter{vmargin}
796 \LWR@loadafter{vowel}
797 \LWR@loadafter{vpe}
798 \LWR@loadafter{vwcol}
799 \LWR@loadafter{wallpaper}
800 \LWR@loadafter{watermark}
801 \LWR@loadafter{widetable}
802 \LWR@loadafter{widows-and-orphans}
803 \LWR@loadafter{witharrows}
804 \LWR@loadafter{wrapfig}
805 \LWR@loadafter{wrapfig2}
806 \LWR@loadafter{xbmks}
807 \LWR@loadafter{xcolor}
808 \LWR@loadafter{xexchangebar}
809 \LWR@loadafter{xellipsis}
810 % xetexko must be loaded before lwarp
811 \LWR@loadafter{xevlna}
812 \LWR@loadafter{xfakebold}
813 \LWR@loadafter{xfrac}
814 \LWR@loadafter{xltabular}
815 \LWR@loadafter{xltextra}
816 \LWR@loadafter{xmpincl}
817 \LWR@loadafter{xpiano}
818 \LWR@loadafter{xpinyin}
819 \LWR@loadafter{xr}
820 \LWR@loadafter{xr-hyper}
821 \LWR@loadafter{xtab}
822 % xunicode must be loaded before lwarp
823 \LWR@loadafter{xurl}
824 \LWR@loadafter{xy}
825 \LWR@loadafter{zwpagelayout}

```

21 MD5 hashing

The MD5 hash is used for lateximage filenames for svg math.

```

826 \newcommand{\LWR@mdfive}[1]{%
827   \PackageError{lwarp}
828     {No MD5 macro was found}
829     {%
830       Lwarp must find the macros \protect\pdfmdfivesum\space
831       or \protect\mdfivesum.%
832     }
833 }

```

The default for PDF^LATEX, DVI^LATEX, up^LATEX, etc:

```
834 \let\LWR@mdfive\pdfmdfivesum
```

For Lua^LATEX:

```

835 \ifLuaTeX
836 \RequirePackage{pdftexcmds}
837 \let\LWR@mdfive\pdf@mdfivesum
838 \fi

```

For X_YL^AT_EX:

```
839 \ifXeTeX
840 \@ifundefined{pdfmfivesum}{}
841     {\let\LWR@mdfive\pdfmfivesum}
842 \@ifundefined{mdfivesum}{}
843     {\let\LWR@mdfive\mdfivesum}
844 \fi
```

22 PDF L^AT_EX T1 and UTF-8 encoding

When using PDF L^AT_EX, lwarp requires T1 font encoding, and recommends UTF-8 input encoding.

If some other input encoding is already defined, lwarp will try to use it instead, and hope for the best.

X_YL^AT_EX and LuaL^AT_EX are both UTF-8 by nature.

`\LWR@pdfencoding` Sets T1, and also utf8 if not already set.

```
845 \newcommand*\LWR@pdfencoding{%
846     \RequirePackage[T1]{fontenc}
847
848     \IfPackageLoadedTF{inputenc}{}{
849         \IfPackageLoadedTF{inputenx}{}{
850             \RequirePackage[utf8]{inputenc}
851         }
852     }
853 }

854 \ifPDFTeX% pdflatex or dvi latex
855     \LWR@pdfencoding
856 \fi
857
858 \ifpTeX
859     \LWR@pdfencoding
860 \fi
```

23 Unicode input characters

for HTML & PRINT: If using *pdflatex*, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be `\texttimes`.

The first arguments of `\newunicodechar` below are text ligatures in the source code, even though they are not printed in the following listing.

```
861 \ifpTeX
862 \else
863 \RequirePackage{newunicodechar}
864
```

```

865 \newunicodechar{x}{\texttimes}
866
867 \ifPDFTeX% pdflatex or dvi latex
868 \newunicodechar{ff}{ff}% Here, the first arguments are ligatures.
869 \newunicodechar{fi}{fi}
870 \newunicodechar{fl}{fl}
871 \newunicodechar{ffi}{ffi}
872 \newunicodechar{ffl}{ffl}
873 \newunicodechar{-}{---}
874 \newunicodechar{-}{--}
875 \fi
876
877 \fi

```

24 Avoid a bitmapped font

If DVI or PDF L^AT_EX, and if the default Computer Modern is the selected font family, ensure that cm-super or lmodern is used to provide a vector font.

```

878 \ifxetexorluatex
879 \else
880   \ifdefstring{\f@family}{cmr}{
881     \IfFileExists{typelec.sty}% found in cm-super
882     {}
883     {% cm-super not installed
884       \IfFileExists{lmodern.sty}{
885         \PackageInfo{lwarp}{cm-super not installed, loading lmodern}
886         \RequirePackage{lmodern}
887       }{
888         \PackageError{lwarp}
889         {%
890           Lwarp requires a vector font.\MessageBreak
891           Install and load cm-super, lmodern, or another\MessageBreak
892           Type-1 vector font before loading lwarp.\MessageBreak
893           Enter 'H' for possible solutions%
894         }
895         {%
896           Install cm-super or lmodern.\MessageBreak
897           If lmodern, load it before lwarp:\MessageBreak
898           \space\space\protect\usepackage{lmodern}\MessageBreak
899           \space\space\protect\usepackage{lwarp}%
900         }
901       }
902     }% cm-super not installed
903   }{% f@family
904 \fi

```

25 Upright quotes

In PDF T_EX, preserve upright quotes in verbatim text. upquote also loads textcomp.

```

905 \ifPDFTeX
906 \RequirePackage{upquote}
907 \fi

```

```

908
909 \ifpTeX
910   \RequirePackage{upquote}
911 \fi

```

26 Avoid bad font combinations

For Xe_LA_TE_X and Lua_LA_TE_X, certain font combinations cause problems with `lwarp`.

`libertinus-otf` has special handling for `\textquotedbl`. Search for `\LWR@orig@textquotedbl`.

```

912 \ifxetexorluatex
913   \AtBeginDocument{
914     \IfPackageLoadedTF{kpfonts}{
915       \PackageError{lwarp}
916         {%
917           When using XeLaTeX or LuaLaTeX, \MessageBreak
918           use kpfonts-otf instead of kpfonts%
919         }
920       {%
921         Replace: \protect\usepackage{kpfonts}\MessageBreak
922         with: \protect\usepackage{kpfonts-otf}
923       }
924     }{}
925   }
926 \fi

```

27 Miscellaneous tools

27.1 Variables

```

927 \newlength{\LWR@templengthone}
928 \newlength{\LWR@templengthtwo}
929 \newlength{\LWR@templengththree}
930 \newcounter{LWR@tempcountone}

```

27.2 Lengths and units

`\LWR@providelength` `{\langle lengthname \rangle}` Provides the length if it isn't defined yet.

Used to provide source compatibility for lengths which will be ignored, but might or might not be already provided by other packages.

```

931 \newcommand*\LWR@providelength[1]{%
932   \ifdeflength{#1}{\newlength{#1}}%
933 }

```

`\LWR@convertto` `{\langle dest unit \rangle}{\langle length \rangle}`

Prints a length in the given units, without printing the unit itself.

```

934 \newcommand*\LWR@convertto[2]{\strip@pt\dimexpr #2*65536/\number\dimexpr 1#1}

```

`\LWR@printpercentlength` $\{\langle smaller \rangle\} \{\langle larger \rangle\}$

Prints a percent ratio of the two lengths.

```
935 \newcommand*\LWR@printpercentlength[2]{%
936   \setcounter{LWR@tempcountone}{100*\ratio{#1}{#2}}%
937   \arabic{LWR@tempcountone}%
938 }
```

27.3 Counters

`\defaddtcounter` $\{\langle name \rangle\} \{\langle value \rangle\}$

Locally add to a counter.

```
939 \providecommand*\defaddtcounter[2]{%
940   \defcounter{#1}{\value{#1}+#2}%
941 }
```

27.4 Patching macros

`\LWR@patcherror` $\{\langle packagename \rangle\} \{\langle macroname \rangle\}$

Prints an error if could not patch a macro.

```
942 \newcommand*\LWR@patcherror[2]{%
943   \PackageError{Lwarp}%
944   {%
945     Unable to patch package #1,\MessageBreak
946     macro \LWRbackslash #2.\MessageBreak
947     Lwarp or #1 may need to be updated%
948   }%
949   {Please contact the maintainer of the Lwarp package.}%
950 }
```

27.5 Copying macros

`\csNewCommandCopycs` $\{\langle dest csname \rangle\} \{\langle source csname \rangle\}$

Given a cs-name for each, copies a macro to a new definition.

```
951 \providecommand*\csNewCommandCopycs[2]{%
952   \expandafter\NewCommandCopy\csname#1\expandafter\endcsname%
953   \csname#2\endcsname%
954 }
```

`\NewEnvironmentCopy` $\{\langle dest \rangle\} \{\langle source \rangle\}$

Copies an environment to a new definition.

```
955 \providecommand*\NewEnvironmentCopy[2]{%
956   \csNewCommandCopycs{#1}{#2}%
957   \csNewCommandCopycs{end#1}{end#2}%
958 }
```

27.6 Chinese text isolation

`\LWR@isolate` $\langle text \rangle$ Isolates Chinese characters from the surrounding text. This is required to avoid extra spaces on either side of the Chinese characters, especially when written to a file.

```
959 \newcommand{\LWR@isolate}[1]{#1}%
960
961 \IfPackageLoadedTF{ctexpatch}{
962   \renewcommand{\LWR@isolate}[1]{\null#1\null}%
963 }{}
964
965 \IfPackageLoadedTF{xCJK}{
966   \renewcommand{\LWR@isolate}[1]{\null#1\null}%
967 }{}
```

`\LWR@disablepinyin` Disable xpinyin during file, sideTOC, and footnote generation. Set by xpinyin.

```
968 \newcommand*\LWR@disablepinyin{}
```

27.7 Inserting vertical space

`\LWR@forceemptyline` Extra vertical space in the HTML output. Use after `\LWR@stoppars`.

```
969 \newcommand*\LWR@forceemptyline}{%
970   \LWR@origrule{0pt}{1\baselineskip}%
971   \LWR@orignewline%
972 }
```

27.8 Argument selection

`\LWR@thirdofthree` $\langle first \rangle \langle second \rangle \langle third \rangle$

`\LWR@fourthoffour` $\langle first \rangle \langle second \rangle \langle third \rangle \langle fourth \rangle$

`\LWR@firstoffive` $\langle first \rangle \langle second \rangle \langle third \rangle \langle fourth \rangle \langle fifth \rangle$

`\LWR@secondoffive` $\langle first \rangle \langle second \rangle \langle third \rangle \langle fourth \rangle \langle fifth \rangle$

`\LWR@thirdoffive` $\langle first \rangle \langle second \rangle \langle third \rangle \langle fourth \rangle \langle fifth \rangle$

`\LWR@fourthoffive` $\langle first \rangle \langle second \rangle \langle third \rangle \langle fourth \rangle \langle fifth \rangle$

`\LWR@fifthoffive` $\langle first \rangle \langle second \rangle \langle third \rangle \langle fourth \rangle \langle fifth \rangle$

Expands to the *n*th of the five arguments. Used for extra cross referencing.

```
973 \long\def\LWR@thirdofthree#1#2#3{#3}%
974 \long\def\LWR@fourthoffour#1#2#3#4{#4}%
975
```

```

976 \long\def\LWR@firstoffive#1#2#3#4#5{#1}
977 \long\def\LWR@secondoffive#1#2#3#4#5{#2}
978 \long\def\LWR@thirdoffive#1#2#3#4#5{#3}
979 \long\def\LWR@fourthoffive#1#2#3#4#5{#4}
980 \long\def\LWR@fifthoffive#1#2#3#4#5{#5}

```

27.9 Inside boxes

Greater than zero if currently inside a T_EX box, thus should not use `\LWR@orignewpage`. See section 13.2.

```

981 \newcounter{LWR@textboxdepth}
982 \setcounter{LWR@textboxdepth}{0}

```

`\LWR@maybe@orignewpage` Only do `\LWR@orignewpage` if not inside a T_EX box.

```

983 \newcommand*{\LWR@maybe@orignewpage}{%
984   \LWR@traceinfo{LWR@maybe@orignewpage}%
985   \ifnumgreater{\value{LWR@textboxdepth}}{0}%
986     {}%
987     {\LWR@orignewpage}%
988   \LWR@traceinfo{LWR@maybe@orignewpage done}%
989 }

```

27.10 Global boxes

`\LWR@gsavebox` `{\langle macroname \rangle}{\langle contents \rangle}`

From <https://tex.stackexchange.com/questions/288702/savebox-forgets-its-content-across-columns-inside-align>

```

990 \DeclareRobustCommand\LWR@gsavebox[1]{%
991   \ifnextchar(%
992     {\LWR@gsavepicbox#1}{\ifnextchar[{\LWR@gsavebox#1}{\LWR@gsbox#1}}}%
993 \long\def\LWR@gsbox#1#2{\global\setbox#1\hbox{%
994   \color@setgroup#2\color@endgroup}}
995 \def\LWR@gsavebox#1[#2]{%
996   \ifnextchar [{{\LWR@igsavebox#1[#2]}{\LWR@igsavebox#1[#2][c]}}
997 \long\def\LWR@igsavebox#1[#2][#3]#4{%
998   \LWR@gsbox#1{\@makebox[#2][#3]{#4}}
999 \def\LWR@gsavepicbox#1(#2,#3){%
1000   \ifnextchar[%
1001     {\LWR@igsavepicbox#1(#2,#3)}{\LWR@igsavepicbox#1(#2,#3)[]}}
1002 \long\def\LWR@igsavepicbox#1(#2,#3)[#4]#5{%
1003   \LWR@gsbox#1{\@makepicbox(#2,#3)[#4]{#5}}

```

Env `LWR@glrbox` `{\langle macroname \rangle}`

```

1004 \def\LWR@glrbox#1{%
1005   \edef\reserved@a{%
1006     \endgroup
1007     \global\setbox#1\hbox{%
1008       \begingroup\aftergroup%
1009       \def\noexpand\@currenvir{\@currenvir}%

```

```

1010     \def\noexpand\@currentline{\on@line}}%
1011 \reserved@a
1012 \endpefalse
1013 \color@setgroup
1014 \ignorespaces}
1015 \let\LWR@endglrbox\LWR@endlrbox

```

27.11 Converting a macro name to a cs name

`\macrotoocsname` {<*macro name with backslash*>}

Results in the macro name without the leading backslash.

Ref: <https://tex.stackexchange.com/questions/42318/removing-a-backslash-from-a-character-sequence>

```

1016 \newcommand*\macrotoocsname[1]{%
1017 \ifcat\relax\noexpand#1%
1018 \expandafter\expandafter\expandafter\@gobble\expandafter\string
1019 \fi
1020 #1%
1021 }

```

27.12 Title case

`\LWRtexttitlecase`

```

1022 \ExplSyntaxOn
1023 \newcommand*\LWRtexttitlecase[1]{%
1024 \text_titlecase:n{#1}%
1025 }
1026 \ExplSyntaxOff

```

27.13 LetLtxMacros

`\LWR@LetLtxMacros` {<*newcsname*>} {<*oldcsname*>}

`\LetLtxMacro` with cs names.

```

1027 \newcommand*\LWR@LetLtxMacros[2]{%
1028 \expandafter\LetLtxMacro\csname #1\expandafter\endcsname%
1029 \csname#2\endcsname%
1030 }

```

27.14 Absorbing a star

`\LWR@absorbstar` {<*csname*>}

Modifies a macro to absorb a star. Used for `cleveref`, since `hyperref` is emulated, so the starred macros are not created by `cleveref`.

```

1031 \newcommand*\LWR@absorbstar}[1]{%
1032   \LWR@LetLtxMacros{LWR@origins@#1}{#1}%
1033   \csdef{#1}{\@ifstar{\csuse{LWR@origins@#1}}{\csuse{LWR@origins@#1}}}
1034   \expandafter\robustify\csname #1\endcsname
1035 }

```

28 Operating-System portability

Prog Unix
 Prog Mac OS
 Prog Linux
 Prog MS-Windows
 Prog Windows
 Opt OSWindows

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as “UNIX” in the configuration files), and MS-WINDOWS is supported as well.

If MS-WINDOWS is not correctly detected, use the lwarp option OSWindows.

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean usingOSWindows is set true. This boolean may be tested by the user for later use.

28.1 Literal characters

Literal characters to be used in PrintLatexCmd and HTMLLatexCmd. These are defined without @ to easily allow their inclusion in the user’s document.

The literal % character:

```
1036 \let\LWRpercent\@percentchar
```

The literal \$ character:

```

1037 \catcode'\$=12
1038 \def\LWRdollar{$}
1039 \catcode'\$=3

```

The literal & character:

```

1040 \catcode'\&=12
1041 \def\LWRamp{&}
1042 \catcode'\&=4

```

The literal \ character. The ampersand is temporarily set to the escape character during the definition of the backslash macro.

```

1043 \catcode'\&=0
1044 &catcode'\&=12
1045 \def&LWRbackslash{\}
1046 &catcode'\&=0
1047 \catcode'\&=4

```

The literal { character. The ampersand is temporarily set to the begin group character during the definition of the leftbrace macro.

```

1048 \catcode'\&=1
1049 \catcode'\{=12
1050 \def\LWRleftbrace&{ }

```

```
1051 \catcode'\{=1
1052 \catcode'\&=4
```

The literal } character. The ampersand is temporarily set to the end group character during the definition of the leftbrace macro.

```
1053 \catcode'\&=2
1054 \catcode'\}=12
1055 \def\LWRrightbrace{ }&
1056 \catcode'\}=2
1057 \catcode'\&=4
```

The literal # character:

```
1058 \catcode'\#=12
1059 \def\LWRhash{#}
1060 \catcode'\#=6
```

`\LWRopquote` The operating system's quote mark, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
1061 \def\LWRopquote{' }
```

`\LWRopseq` The operating system's sequential execution command, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
1062 \def\LWRopseq{ \space\LWRamp\LWRamp\space\space }
```

28.2 Common portability code

Bool `usingOSWindows`

Set if the `OSWindows` option is used, or if `WINDOWS` is automatically detected.

```
1063 \newbool{usingOSWindows}
1064 \boolfalse{usingOSWindows}
```

28.3 UNIX, LINUX, and MAC OS

`\OSPathSymbol` Symbol used to separate directories in a path.

```
1065 \newcommand*{\OSPathSymbol}{/}
```

28.4 MS-WINDOWS

For MS-WINDOWS:

`\LWR@setOSWindows` Set defaults for the MS-WINDOWS operating system. `lwarp` attempts to auto-detect the operating system, and the `OSWindows` option may also be used to force MS-WINDOWS compatibility.

```
1066 \newcommand*{\LWR@setOSWindows}
```

```

1067 {
1068 \booltrue{usingOSWindows}
1069 \renewcommand*{\OSPathSymbol}{\@backslashchar}
1070 \def\LWRopquote{"}
1071 \def\LWRopseq{\space\LWRamp\space\space}
1072 }

```

Test for windows during compile. The user may also specify OSWindows package option in case this test fails.

```

1073 \ifwindows
1074 \LWR@setOSWindows
1075 \fi

```

29 Package options

Pkg kvoptions

Allows key/value package options.

```

1076 \RequirePackage{kvoptions}
1077 \SetupKeyvalOptions{family=LWR,prefix=LWR@}

```

`\lwarpsetup` A user interface to set the keys:

```

1078 \newcommand{\lwarpsetup}[1]{\setkeys{LWR}{#1}}

```

Bool warpingprint

Bool warpingHTML

Bool mathjax

Bool LWR@origmathjax

Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax.

LWR@origmathjax remembers the original setting to be restored by `\displaymathnormal`.

```

1079 \newbool{warpingprint}
1080 \newbool{warpingHTML}
1081 \newbool{mathjax}
1082 \newbool{LWR@origmathjax}

```

defaults The default is print output, and SVG math if the user chose HTML output.

```

1083 \booltrue{warpingprint}%
1084 \boolfalse{warpingHTML}%
1085 \boolfalse{mathjax}%

```

Opt warpprint

If the warpprint option is given, boolean warpingprint is true and boolean warpingHTML is false, and may be used for `\ifbool` tests.

```

1086 \DeclareVoidOption{warpprint}{%
1087   \PackageInfo{lwarp}{Using option 'warpprint'}
1088   \booltrue{warpingprint}%
1089   \boolfalse{warpingHTML}%
1090 }

```

Opt warpHTML

Anything in the warpHTML environment will be generated for HTML output only.

Opt `warpHTML` If the `warpHTML` option is given, boolean `warpingHTML` is true and boolean `warpingprint` is false, and may be used for `\ifbool` tests.

```
1091 \DeclareVoidOption{warpHTML}{%
1092   \PackageInfo{lwarp}{Using option 'warpHTML'}%
1093   \booltrue{warpingHTML}%
1094   \boolfalse{warpingprint}%
1095 }
```

Opt `mathsvg` Option `mathsvg` selects SVG math display: If the `mathsvg` option is given, boolean `mathjax` is false, and may be used for `\ifbool` tests.

```
1096 \DeclareVoidOption{mathsvg}{%
1097   \PackageInfo{lwarp}{Using option 'mathsvg'}
1098   \boolfalse{mathjax}%
1099   \boolfalse{LWR@origmathjax}%
1100 }
```

Opt `mathjax` Option `mathjax` selects MATHJAX math display: If the `mathjax` option is given, boolean `mathjax` is true, may be used for `\ifbool` tests.

```
1101 \DeclareVoidOption{mathjax}{%
1102   \PackageInfo{lwarp}{Using option 'mathjax'}
1103   \booltrue{mathjax}%
1104   \booltrue{LWR@origmathjax}%
1105 }
```

Opt `BaseJobname` Option `BaseJobname` sets the `\BaseJobname` for this document.

Default: `\jobname`

This is the `\jobname` of the printed version, even if currently compiling the HTML version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLFilename` if the user did not provide one.

```
1106 \DeclareStringOption[\jobname]{BaseJobname}
```

Opt `ImagesDirectory` Option `ImagesDirectory` sets the name of the directory to use for the `lateximage` images.

Default: `\jobname-images`

```
1107 \DeclareStringOption[\BaseJobname-images]{ImagesDirectory}
```

Opt `ImagesName` Option `ImagesName` sets the prefix to use for the `lateximage` images.

Default: `image-`

```
1108 \DeclareStringOption[image-]{ImagesName}
```

Opt `makeindexStyle` Selects a custom `.ist` file. A customized file should be based on `lwarp.ist`. See section 8.6.20.

Default: `lwarp.ist`

```
1109 \DeclareStringOption[lwarp.ist]{makeindexStyle}
```

Opt `xindyStyle` Selects a custom `.xdy` file. A customized file should be based on `lwarp.xdy`. See section 8.6.21.

Default: `lwarp.xdy`

```
1110 \DeclareStringOption[lwarp.xdy]{xindyStyle}
```

- Opt `xindyLanguage`
 Default: `english`
 Sets the *xindy* language to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index and glossary.
- ```
1111 \DeclareStringOption[english]{xindyLanguage}
```
- Opt `xindyCodepage`  
 Default: `utf8`  
 Sets the *xindy* codepage to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index.
- ```
1112 \DeclareStringOption[utf8]{xindyCodepage}
```
- Opt `xindexConfig`
 Default: `<empty>`
 Selects a custom `xindex-*.lua` file. A customized file should be based on `xindex-cfg.lua`. See section 8.6.22.
- ```
1113 \DeclareStringOption[]{}{xindexConfig}
```
- Opt `pdftotextEnc`  
 Default: `UTF-8`  
 The option `pdftotextEnc` sets the encoding used by *pdftotext*. This is passed to *pdftotext* using its `-enc` option, and is used when converting L<sup>A</sup>T<sub>E</sub>X PDF output with HTML tags into a plain-text file with HTML tags.
- ```
1114 \DeclareStringOption[UTF-8]{pdftotextEnc}
```
- Opt `lwarpmk`
 Tells *lwarp* to generate a local copy of *lwarpmk* called `lwarpmk.lua`. Useful for archiving for future use. This file may be made executable and acts just like *lwarpmk*.
- If `lwarpmk` option, creates a local copy of `lwarpmk.lua`:
- ```
1115 \newbool{LWR@creatinglwarpmk}
1116 \boolfalse{LWR@creatinglwarpmk}
1117
1118 \DeclareVoidOption{lwarpmk}{
1119 \PackageInfo{lwarp}{Using option 'lwarpmk'}
1120 \booltrue{LWR@creatinglwarpmk}
1121 }
```
- Opt `OSWindows`  
 Tells *lwarp* to use MS-WINDOWS compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated `lwarpmk.conf` file to find out whether the operating system was detected correctly.
- ```
1122 \DeclareVoidOption{OSWindows}{
1123   \PackageInfo{lwarp}{Using option 'OSWindows'}
1124   \LWR@setOSWindows
1125 }
```
- Opt `HomeHTMLFilename`
 Default: `\BaseJobname`
 The filename of the homepage. The default is the jobname. This option is stored into `\LWR@HomeHTMLFilename`, and later transferred into `\HomeHTMLFilename` for internal use.
- ```
1126 \DeclareStringOption[]{}{HomeHTMLFilename}
```
- Opt `HTMLFilename`  
 Default: `<empty>`  
 The filename prefix of web pages after the homepage. The default is empty, no prefix. This option is stored into `\LWR@HTMLFilename`, and later transferred into `\HTMLFilename` for internal use.
- ```
1127 \DeclareStringOption[]{}{HTMLFilename}
```

- Opt `PrintLatexCmd` The shell commands to use to compile the print document.
 Default: `<automatic>`
 1128 `\DeclareStringOption[]{\PrintLatexCmd}`
- Opt `HTMLLatexCmd` The shell commands to use to compile the HTML document.
 Default: `<automatic>`
 1129 `\DeclareStringOption[]{\HTMLLatexCmd}`
- Opt `PrintIndexCmd` The shell commands to use to compile the print indexes.
 Default: `<empty>`
 1130 `\DeclareStringOption[]{\PrintIndexCmd}`
- Opt `HTMLIndexCmd` The shell commands to use to compile the HTML indexes.
 Default: `<empty>`
 1131 `\DeclareStringOption[]{\HTMLIndexCmd}`
- Opt `LatexmkIndexCmd` The shell commands to be used by *latexmk* to compile the print indexes. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `LatexmkIndexCmd` does not include the filename, which will be provided by *latexmk*.
 Default: `<empty>`
 1132 `\DeclareStringOption[]{\LatexmkIndexCmd}`
- Opt `makeindex` Tells *lwarp* to use *makeindex* for index generation. When `lwarpmk.conf` and `*.lwarpmkconf` are generated, `PrintIndexCmd` and `HTMLIndexCmd` will be set for *makeindex* with a single index file.
 1133 `\DeclareBoolOption[false]{makeindex}`
- Opt `xindy` Tells *lwarp* to use *xindy* for index generation. When `lwarpmk.conf` and `*.lwarpmkconf` are generated, `PrintIndexCmd` and `HTMLIndexCmd` will be set for *xindy* with a single index file.
 1134 `\DeclareBoolOption[false]{xindy}`
- Opt `xindex` Tells *lwarp* to use *xindex* for index generation. When `lwarpmk.conf` and `*.lwarpmkconf` are generated, `PrintIndexCmd` and `HTMLIndexCmd` will be set for *xindex* with a single index file.
 1135 `\DeclareBoolOption[false]{xindex}`
- Opt `IndexRef` Tells *lwarp* how to display the index entries in HTML output. See section 7.5.
 Default: `cref`
 1136 `\DeclareStringOption[cref]{IndexRef}`
- Opt `GlossaryCmd` The shell command to use to compile the glossary. The print or HTML version of the glossary filename will be appended to this command.
 Default: `makeglossaries`
 1137 `\DeclareStringOption[makeglossaries]{GlossaryCmd}`
- Opt `latexmk` Option `latexmk` tells *lwarpmk* to use *latexmk* when compiling documents.
 1138 `\DeclareBoolOption[false]{latexmk}`

- Opt dvips Option dvips tells *lwarpmk* to use *dvips* when compiling DVI *latex* documents.
- ```
1139 \DeclareBoolOption[false]{dvips}
```
- Opt dvipdfm        Option dvipdfm tells *lwarpmk* to use *dvipdfm* when compiling DVI *latex* documents.
- ```
1140 \DeclareBoolOption[false]{dvipdfm}
```
- Opt dvipdfmx Option dvipdfmx tells *lwarpmk* to use *dvipdfmx* when compiling DVI *latex* documents.
- ```
1141 \DeclareBoolOption[false]{dvipdfmx}
```

[Execute options](#)   Execute the package options, with the defaults which have been set just above:

```
1142 \ProcessKeyvalOptions*\relax
```

## 29.1 Additional options support

Assign the `\BaseJobname` if the user hasn't provided one:

```
1143 \providecommand*\BaseJobname{\LWR@BaseJobname}
```

Defaults unless already over-ridden by the user:

```
1144 \ifcseempty{\LWR@HomeHTMLFilename}{
1145 \newcommand*\HomeHTMLFilename{\BaseJobname}
1146 }{
1147 \csedef{HomeHTMLFilename}{\LWR@HomeHTMLFilename}
1148 }
1149
1150 \csedef{HTMLFilename}{\LWR@HTMLFilename}
```

Special handling for underscores in labels and filenames.

`\LWR@sanitized`   The sanitized version of what was given to `\LWR@sanitize`. Characters are set to their detokenized versions. Required for underscores in labels and filenames.

```
1151 \newcommand*\LWR@sanitized{}
```

`\LWR@sanitize`    `{\langle text \rangle}`

Sanitizes the text and returns the result in `\LWR@sanitized`.

```
1152 \newcommand*\LWR@sanitize[1]{%
1153 \edef\LWR@sanitized{#1}%
1154 \edef\LWR@sanitized{\detokenize\expandafter{\LWR@sanitized}}%
1155 }
```

Sanitize some string options to neutralize underscores.

```
1156 \LWR@sanitize{\LWR@BaseJobname}
1157 \edef\LWR@BaseJobname{\LWR@sanitized}
```

```

1158
1159 \LWR@sanitize{\LWR@ImagesDirectory}
1160 \edef\LWR@ImagesDirectory{\LWR@sanitized}
1161
1162 \LWR@sanitize{\LWR@ImagesName}
1163 \edef\LWR@ImagesName{\LWR@sanitized}

```

\LWR@PrintIndexCmd and \LWR@HTMLIndexCmd are tested to see if they are empty. If so, they are set to a reasonable defaults for a single index using *makeindex*, then possibly set to defaults for *xindy* if the *lwarp xindy* option was selected, then likewise for *xindex* if the *xindex* option was selected.

```

1164 \ifdefempty{\LWR@PrintIndexCmd}{
1165 \renewcommand{\LWR@PrintIndexCmd}{%
1166 makeindex -s \LWR@makeindexStyle \space \jobname.idx%
1167 }
1168 \ifbool{LWR@xindy}{
1169 \renewcommand{\LWR@PrintIndexCmd}{%
1170 xindy
1171 -M \LWR@xindyStyle \space
1172 -L \LWR@xindyLanguage \space
1173 -C \LWR@xindyCodepage \space
1174 \jobname.idx%
1175 }
1176 }{}
1177 \ifbool{LWR@xindex}{
1178 \ifdefvoid{\LWR@xindexConfig}{
1179 \renewcommand{\LWR@PrintIndexCmd}{%
1180 xindex
1181 \jobname.idx%
1182 }
1183 }{
1184 \renewcommand{\LWR@PrintIndexCmd}{%
1185 xindex
1186 -c \LWR@xindexConfig \space
1187 \jobname.idx%
1188 }
1189 }
1190 }{}
1191 }{}
1192
1193 \ifdefempty{\LWR@HTMLIndexCmd}{
1194 \renewcommand{\LWR@HTMLIndexCmd}{%
1195 makeindex -s \LWR@makeindexStyle \space \jobname_html.idx%
1196 }
1197 \ifbool{LWR@xindy}{
1198 \renewcommand{\LWR@HTMLIndexCmd}{%
1199 xindy
1200 -M \LWR@xindyStyle \space
1201 -L \LWR@xindyLanguage \space
1202 -C \LWR@xindyCodepage \space
1203 \jobname_html.idx%
1204 }
1205 }{}
1206 \ifbool{LWR@xindex}{
1207 \ifdefvoid{\LWR@xindexConfig}{
1208 \renewcommand{\LWR@HTMLIndexCmd}{%
1209 xindex
1210 \jobname_html.idx%

```

```

1211 }
1212 }{
1213 \renewcommand{\LWR@HTMLIndexCmd}{%
1214 xindex
1215 -c \LWR@indexConfig \space
1216 \jobname_html.idx%
1217 }
1218 }
1219 }{}
1220 }{}
1221
1222 \ifdefempty{\LWR@LatexmkIndexCmd}{
1223 \renewcommand{\LWR@LatexmkIndexCmd}{%
1224 makeindex -s \LWR@makeindexStyle%
1225 }
1226 \ifbool{\LWR@xindy}{
1227 \renewcommand{\LWR@LatexmkIndexCmd}{%
1228 xindy
1229 -M \LWR@xindyStyle \space
1230 -L \LWR@xindyLanguage \space
1231 -C \LWR@xindyCodepage%
1232 }
1233 }{}
1234 \ifbool{\LWR@index}{
1235 \ifdefvoid{\LWR@indexConfig}{
1236 \renewcommand{\LWR@LatexmkIndexCmd}{%
1237 xindex
1238 }
1239 }{
1240 \renewcommand{\LWR@LatexmkIndexCmd}{%
1241 xindex
1242 -c \LWR@indexConfig
1243 }
1244 }
1245 }{}
1246 }{}

```

## 29.2 Conditional compilation

`\warpprintonly` {<*contents*>}

Only process the contents if producing printed output.

```
1247 \newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{}}
```

`\warpHTMLonly` {<*contents*>}

Only process the contents if producing HTML output.

```
1248 \newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{}}
```

Pkg comment

Provides conditional code blocks.

Attempts to use `versions` or `verbatim` fail in some cases, and do not provide much of a speed benefit even when they do work.

```
1249 \RequirePackage{comment}
```

`\LWR@includecomment` {<env name>} {<partial filename>}

`\LWR@excludecomment` {<env name>} {<partial filename>}

Use many comment cut files to avoid collision in case the user uses the comment package. Each filename is “comment\_#2.cut”. Based on the comment package.

```

1250 \def\LWR@includecomment
1251 #1#2{\message{Lwarp: Including comment '#1'}%
1252 \csarg\def{After#1Comment}{%
1253 \CloseAndInputCutFile%
1254 \csundef{LWR@#1commentused}%
1255 }
1256 \csarg\def{#1}{%
1257 \endgroup
1258 \ifcsdef{LWR@#1commentused}{
1259 \PackageError{Lwarp}%
1260 {Nested #1 environment}%
1261 {%
1262 Environment #1 cannot be nested.\MessageBreak
1263 This can happen when a package is loaded
1264 from inside a\MessageBreak
1265 #1 environment.%
1266 }%
1267 }{\relax}
1268 \csdef{LWR@#1commentused}{%
1269 \message{Including '#1' comment.}%
1270 \def\CommentCutFile{comment_#2.cut}
1271 \SetUpCutFile
1272 \ProcessComment{#1}
1273 }%
1274 \CommentEndDef{#1}
1275 }
1276
1277 \def\LWR@excludecomment
1278 #1#2{\message{Lwarp: Excluding comment '#1'}%
1279 \csarg\def{#1}{
1280 \endgroup
1281 \message{Excluding '#1' comment.}%
1282 \beginingroup
1283 \def\CommentCutFile{comment_#2.cut}
1284 \def\ProcessCutFile{}%
1285 \def\ThisComment####1{}%
1286 \ProcessComment{#1}
1287 }%
1288 \csarg\def{After#1Comment}{\CloseAndInputCutFile \endgroup}
1289 \CommentEndDef{#1}}

```

Env `warpall` Anything in the `warpall` environment will be generated for print or HTML outputs.

```
1290 \LWR@includecomment{warpall}{all}
```

Env `warpHTML` For HTML output:

```

1291 \ifbool{warpingHTML}
1292 {\LWR@includecomment{warpHTML}{html}}
1293 {\LWR@excludecomment{warpHTML}{html}}

```

Env `warpprint` Anything in the `warpprint` environment will be generated for print output only.

```
1294 \ifbool{warpingprint}
1295 {\LWR@includecomment{warpprint}{print}}
1296 {\LWR@excludecomment{warpprint}{print}}
```

Env `warpMathJax` Only if `MATHJAX` is being used along with `HTML`.

```
1297 \begin{warpprint}
1298 \LWR@excludecomment{warpMathJax}{mathjax}
1299 \end{warpprint}
1300
1301 \begin{warpHTML}
1302 \ifbool{mathjax}
1303 {\LWR@includecomment{warpMathJax}{mathjax}}
1304 {\LWR@excludecomment{warpMathJax}{mathjax}}
1305 \end{warpHTML}
```

Env `warpsvg` Only if `SVG` math is being used along with `HTML`, or in print mode.

```
1306 \begin{warpprint}
1307 \LWR@includecomment{warpsvg}{mathsvg}
1308 \end{warpprint}
1309
1310 \begin{warpHTML}
1311 \ifbool{mathjax}
1312 {\LWR@excludecomment{warpsvg}{mathsvg}}
1313 {\LWR@includecomment{warpsvg}{mathsvg}}
1314 \end{warpHTML}
```

Env `LWRcreateLwarpmk` Optionally generate a local copy of `lwarpmk`. Default to `no`.

```
1315 \ifbool{LWR@creatinglwarpmk}
1316 {\LWR@includecomment{LWRcreateLwarpmk}{lwarpmk}}
1317 {\LWR@excludecomment{LWRcreateLwarpmk}{lwarpmk}}
```

## 30 Required packages

These packages are automatically loaded by `lwarp` when generating `HTML` output. Some of them are also automatically loaded when generating print output, but some are not.

**for HTML output:** 1318 `\begin{warpHTML}`

Pkg `fontspec`

Load `fontspec` if necessary:

```
1319 \ifxetexorluatex
1320 \IfPackageLoadedTF{fontspec}{}{
1321 \usepackage[no-math]{fontspec}
1322 }
```

The monospaced font is used for `HTML` tags, so turn off its TeX ligatures and common ligatures:

```

1323 \defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
1324 \defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
1325 \defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
1326 \else

```

*pdf<sub>l</sub>atex* only: **Only pre-loaded if *pdf<sub>l</sub>atex* is being used.**

Pkg microtype

**ligatures** Older browsers don't display ligatures. Turn off letter ligatures, keeping L<sup>A</sup>T<sub>E</sub>X dash and quote ligatures, which may fail on older browsers but at least won't corrupt written words.

```

1327 \RequirePackage{microtype}
1328
1329 \microtypesetup{
1330 protrusion=false,
1331 expansion=false,
1332 tracking=false,
1333 kerning=false,
1334 spacing=false}
1335 % \begin{macrocode}
1336 %
1337 % Disable ligatures for typewriter fonts.
1338 % The comma was causing issues with \MathJax\ and \cs{,} followed by a comma.
1339 % Ligatures for f, q, t, etc used to be disabled for non-typewriter fonts, but
1340 % are now allowed.
1341 % \changes{v0.89}{2020/08/01}{Disable typewriter ligatures.}
1342 % ^^A \DisableLigatures[,{,},f,q,t,T,Q]{encoding = *,family = *}% previous
1343 % \begin{macrocode}
1344 \DisableLigatures{encoding = *,family = tt*}

1345 \fi

1346 \end{warpHTML}

```

Pkg geometry

Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

**for HTML output:** 1347 \begin{warpHTML}

If **geometry** has not yet been loaded, use the preexisting page and text sizes to be preserved for later reuse. These will be replaced by **lwarp** \AtBeginDocument with a very large page size to reduce HTML tag overflow off the page.

```

1348 \IfPackageLoadedTF{geometry}
1349 {}{
1350 \RequirePackage[

```

```

1351 reset,
1352 paperwidth=\paperwidth,
1353 paperheight=\paperheight,
1354 textwidth=\textwidth,
1355 textheight=\textheight,
1356 left=\oddsidemargin,
1357 top=\topmargin,
1358 marginparsep=\marginparsep,
1359 marginparwidth=\marginparwidth,
1360]{geometry}
1361 }

```

Remember the original definitions for later reuse. If the `geometry` package is loaded by the user, `lwarp-geometry` will nullify the user-level originals.

```

1362 \LetLtxMacro\LWR@origgeometry\geometry
1363 \LetLtxMacro\LWR@orignewgeometry\newgeometry
1364 \LetLtxMacro\LWR@origrestoregeometry\restoregeometry
1365 \LetLtxMacro\LWR@origsavegeometry\savegeometry
1366 \LetLtxMacro\LWR@origloadgeometry\loadgeometry

```

Bool  
LWR@allowanothergeometry

`geometry` may be loaded by the user before `lwarp`, after `lwarp`, or not at all. If before `lwarp`, it will have already been loaded by now and its page layout has already been saved. If `geometry` is loaded after `lwarp`, its layout will be set at that time and the user macros nullified. `\AtEndPreamble` this layout will be saved. If the user never loads `geometry`, `lwarp-geometry` will be loaded `\AtBeginDocument`, but it should not change the page layout set here. This is controlled by the boolean `LWR@allowanothergeometry`. Geometry may be adjusted throughout the preamble until `\AtEndPreamble`, when this boolean is set false.

```

1367 \newbool{LWR@allowanothergeometry}
1368 \booltrue{LWR@allowanothergeometry}

```

Use `\AtEndPreamble` to avoid class and option conflict by changing settings after other packages load, instead of using `geometry` package options:

```
1369 \AtEndPreamble{
```

Whatever `geometry` choices the user has made in the preamble, either before or after `lwarp` was loaded, are now saved for possible temporary reuse, such as by `lyluatex`.

See the `lwarp-geometry` section for what happens if `geometry` is loaded after `lwarp`.

```
1370 \LWR@origsavegeometry{LWR@usergeometry}
```

The user's paper size is saved for later reuse, such as by the `pdfpages` or `parallel` packages.

```

1371 \newlength{\LWR@userspaperwidth}
1372 \setlength{\LWR@userspaperwidth}{\paperwidth}
1373
1374 \newlength{\LWR@userspaperheight}
1375 \setlength{\LWR@userspaperheight}{\paperheight}
1376
1377 \newlength{\LWR@usersmarginparwidth}
1378 \setlength{\LWR@usersmarginparwidth}{\marginparwidth}
1379

```

```

1380 \newlength{\LWR@userstextwidth}
1381 \setlength{\LWR@userstextwidth}{\textwidth}
1382
1383 \newlength{\LWR@userstextheight}
1384 \setlength{\LWR@userstextwidth}{\textheight}

```

For `lwarp`, use a very large page and margins to help avoid letting HTML tags run off the edge:

```

1385 \LWR@origgeometry{
1386 reset,
1387 paperheight=190in,
1388 paperwidth=20in,
1389 left=2in,
1390 right=6in,
1391 top=1in,
1392 bottom=1in,
1393 heightrounded,%
1394 }

```

The `lwarp` page geometry is saved for future restore:

```

1395 \LWR@origsavegeometry{\LWR@lwarpgeometry}

```

No longer adjust the page layout when `lwarp-geometry` is loaded `\AtBeginDocument`:

```

1396 \boolfalse{\LWR@allowanothergeometry}%

```

`ltjsbook` and other classes can print vertically, and require these to be reset by `lwarp`:

```

1397 \setlength{\textheight}{0.8\paperheight}
1398 \setlength{\textwidth}{0.7\paperwidth}
1399
1400 \@twosidefalse
1401 \@mparswitchfalse
1402 }% \AtEndPreamble
1403
1404 \end{warpHTML}

```

**for HTML & PRINT:** 1405 \begin{warpall}

Pkg xparse

$\LaTeX$ 3 command argument parsing

```

1406 \RequirePackage{xparse}

```

Pkg calc

```

1407 \RequirePackage{calc}

```

```

1408 \end{warpall}

```

**for HTML output:** 1409 \begin{warpHTML}

Pkg expl3

L<sup>A</sup>T<sub>E</sub>X3 programming

```
1410 \RequirePackage{expl3}
```

Pkg gettitlestring

Used to emulate `\nameref`.

```
1411 \RequirePackage{gettitlestring}
```

```
1412
```

```
1413
```

```
1414 \end{warpHTML}
```

**for HTML & PRINT:** `1415 \begin{warpall}`

Pkg filecontents

Used to write helper files while creating the print version.

Recent versions of L<sup>A</sup>T<sub>E</sub>X (as of Fall 2019) now include the functionality of the `filecontents` package, but with a new optional argument used to specify whether to force the overwriting of an existing file. If an older L<sup>A</sup>T<sub>E</sub>X kernel is used, the original `filecontents` package is used, but it is patched to throw away the new optional argument.

```
1416 \@ifundefined{filec@ntents@opt}{% older kernel, discard optional args
```

```
1417
```

```
1418 \RequirePackage{filecontents}
```

```
1419
```

```
1420 \LetLtxMacro\LWR@orig@filec@ntents\filec@ntents
```

```
1421
```

```
1422 \IfPackageAtLeastTF{filecontents}{2011/10/08}
```

```
1423 {
```

For a newer version of the `filecontents` package, simply discard the optional argument.

```
1424 \renewcommand*{\filec@ntents}[1][\LWR@orig@filec@ntents]
```

```
1425 }
```

```
1426 {% patch older package for morewrites
```

For an older version of `filecontents`, discard the optional argument, and also patch to work with `morewrites`, per <https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910>

```
1427 \newwrite\fcwrite
```

```
1428 \renewcommand*{\filec@ntents}[1][\LWR@orig@filec@ntents]{%
```

```
1429 \def\chardef##1\write{\let\reserved@cfwrite}%
```

```
1430 \LWR@orig@filec@ntents%
```

```
1431 }
```

```
1432 }
```

```
1433
```

```
1434 }% older kernel
```

```
1435 {% newer kernel
```

For a newer kernel with a filecontents environment which accepts the optional overwrite argument, use the environment as-is.

```
1436 }% newer kernel, filecontents env accepts optional args, do not load package
```

```
1437 \end{warpall}
```

**for HTML output:** 1438 \begin{warpHTML}

Pkg xifthen

```
1439 \RequirePackage{xifthen}
```

Pkg verbatim

```
1440 \RequirePackage{verbatim}
```

Pkg refcount

Provides \setcounterref, \setcounterpageref, etc.

```
1441 \RequirePackage{refcount}
```

Pkg newfloat

```
1442 \RequirePackage{newfloat}
```

```
1443 \end{warpHTML}
```

**for HTML & PRINT:** 1444 \begin{warpall}

Pkg xstring

 [index](#)

There was a short-term bug in xstring regarding \IfInteger which affected lwarp's index generation. The updated version is requested here.

```
1445 \RequirePackage{xstring}[2019/02/01]
```

Pkg environ

Used to encapsulate math environments for re-use in HTML <alt> text.

```
1446 \RequirePackage{environ}
```

```
1447 \end{warpall}
```

**for HTML output:** 1448 \begin{warpHTML}

Pkg printlen

Used to convert lengths for image width/height options.

```
1449 \RequirePackage{printlen}
```

\LWR@printlength {<length>}

Prints a length using a locally-controlled unit and space. Rounding is used unless the length is small.

```
1450 \newrobustcmd*\LWR@printlength}[1]{%
```

```
1451 \beginingroup%
```

```

1452 \uselengthunit{PT}%
1453 \renewcommand*\unitspace{}%
1454 \ifdimless{#1}{10pt}{%
1455 \printlength{#1}%
1456 }{%
1457 \rndprintlength{#1}%
1458 }%
1459 \endgroup%
1460 }

1461 \end{warpHTML}

```

### 31 Loading packages

`\RequirePackage` and `\usepackage` are modified to error-check for certain packages, and for HTML they load the `lwarp-` version if it exists.

**for HTML & PRINT:** 1462 `\begin{warpall}`

Remember the original `\RequirePackage`:

```

1463 \LetLtxMacro\LWR@origRequirePackage\RequirePackage
1464 \LetLtxMacro\LWR@origRequirePackageWithOptions\RequirePackageWithOptions

```

`\LWR@requirepackagenames` Stores the list of required package names.

```
1465 \newcommand*\LWR@requirepackagenames{}
```

`\LWR@parsedrequirepackagenames` Stores the parsed list of required package names after spaces are removed and `lwarp-` is prepended.

```
1466 \newcommand*\LWR@parsedrequirepackagenames{}
```

`\LWR@nullifycomment` Remove the preexisting comment environment. Certain packages define it for their own use.

```

1467 \newcommand*\LWR@nullifycomment{%
1468 \PackageInfo{lwarp}%
1469 {Nullifying the comment environment before loading \LWR@strresulttwo,}%
1470 \let\comment\relax%
1471 \let\endcomment\relax%
1472 }

```

`\LWR@findword` [*1: separator*] [*2: list*] [*3: index*] [*4: destination*]

Note that argument 4 is passed directly to `\StrBetween`.

```

1473 \newcommand*\LWR@findword[3][,]{%
1474 \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}{#1}%
1475 }

```

`\LWR@checkloadnever` {*bad package name*} {*replacement package names*}

From now on, check for incompatible packages loaded via `\usepackage`, instead of packages loaded before `lwarp`:

```
1476 \LetLtxMacro\LWR@checkloadnever\LWR@afterloadnever
```

`\LWR@checkloadfilename`  $\{\langle filename \rangle\}$  Checks if this filename should be loaded after `lwarp`, or never at all.

```
1477 \newcommand*{\LWR@checkloadfilename}[1]{%
```

Remember the package name to compare with, to be used by `\LWR@checkloadnever` and `\LWR@checkloadbefore`.

```
1478 \edef\LWR@tempone{#1}%
```

Check against the list of packages which should never be loaded:

```
1479 \LWR@checkloadnevers
```

The following should only be loaded before `lwarp`:

```
1480 \LWR@checkloadbefore{ctex}
1481 \LWR@checkloadbefore{fontspec}
1482 \LWR@checkloadbefore{inputenc}
1483 \LWR@checkloadbefore{inputenx}
1484 \LWR@checkloadbefore{nfssect-cfr}
1485 \LWR@checkloadbefore{fontaxes}
1486 \LWR@checkloadbefore{kotex}
1487 \LWR@checkloadbefore{kpfonts}% textcomp option clash
1488 \LWR@checkloadbefore{luatexja}
1489 \LWR@checkloadbefore{luatexja-fontspec}
1490 \LWR@checkloadbefore{luatexko}
1491 \LWR@checkloadbefore{morewrites}
1492 \LWR@checkloadbefore{newclude}
1493 \LWR@checkloadbefore{newunicodechar}
1494 \LWR@checkloadbefore{pnext}
1495 \LWR@checkloadbefore{xeCJK}
1496 \LWR@checkloadbefore{xetexko}
1497 \LWR@checkloadbefore{zxjatype}
1498 }
```

`\LWR@lookforpackagename`  $\{\langle index \rangle\}$

If HTML, and if this is an `lwarp`-supported package name, re-direct it to the `lwarp` version by renaming it `lwarp-` followed by the original name.

Looks `index` deep into the list of package names, `\LWR@requirepackagenames`, and builds `\LWR@parsedrequirepackagenames` which is the modified list of names.

```
1499 \newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the `index`'th package name from the list:

```
1500 \LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in `LWR@strresult` and the final name with no blanks goes into `LWR@strresulttwo`.

```
1501 \StrSubstitute[100]{\LWR@strresult}{ }{ }\LWR@strresulttwo]%
```

See if the package name was found:

```
1502 \IfStrEq{\LWR@strresulttwo}{}%
1503 {}% no filename
1504 {% yes filename was found
```

Possible adjustments before loading the package. Maybe nullify the comment environment if the new package will be redefining it for a new purpose.

```
1505 \ifdefstring{\LWR@strresulttwo}{easyReview}{\LWR@nullifycomment}{}%
1506 \ifdefstring{\LWR@strresulttwo}{changes}{\LWR@nullifycomment}{}%
```

If HTML, check if the package should be loaded before `lwarp`, or never at all:

```
1507 \ifbool{warpingHTML}{\LWR@checkloadfilename{\LWR@strresulttwo}}{%}
```

If HTML, and if found, and if an `lwarp`-equivalent name exists, use `lwarp-*` instead.

```
1508 \ifboolexpr{
1509 bool{warpingHTML} and
1510 test{\IfFileExists{lwarp-\LWR@strresulttwo.sty}}
1511 }%
1512 {% lwarp-* file found
1513 \ifdefvoid{\LWR@parsedrequirepackagenames}{%
1514 \edef\LWR@parsedrequirepackagenames{lwarp-\LWR@strresulttwo}%
1515 }{%
1516 \edef\LWR@parsedrequirepackagenames{%
1517 \LWR@parsedrequirepackagenames,lwarp-\LWR@strresulttwo%
1518 }%
1519 }%
1520 }%
1521 {%
```

Otherwise, use the current package name.

```
1522 \ifdefvoid{\LWR@parsedrequirepackagenames}{%
1523 \edef\LWR@parsedrequirepackagenames{\LWR@strresulttwo}%
1524 }{%
1525 \edef\LWR@parsedrequirepackagenames{%
1526 \LWR@parsedrequirepackagenames,\LWR@strresulttwo%
1527 }%
1528 }%
1529 }% no lwarp-* file
1530 }% yes filename
1531 }
```

`\RequirePackage` [*1: options*] [*2: package names*] [*3: version*]

For each of many package names in a comma-separated list, if an `lwarp` version of a package exists, select it instead of the L<sup>A</sup>T<sub>E</sub>X version.

```
1532 \RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to twenty names:<sup>17</sup>

<sup>17</sup>This was originally nine names, but then I came across a package which used twelve...

```

1533 \renewcommand*{\LWR@requirepackagenames}{#2}%
1534 \renewcommand*{\LWR@parsedrequirepackagenames}{}%
1535 \LWR@lookforpackagename{1}%
1536 \LWR@lookforpackagename{2}%
1537 \LWR@lookforpackagename{3}%
1538 \LWR@lookforpackagename{4}%
1539 \LWR@lookforpackagename{5}%
1540 \LWR@lookforpackagename{6}%
1541 \LWR@lookforpackagename{7}%
1542 \LWR@lookforpackagename{8}%
1543 \LWR@lookforpackagename{9}%
1544 \LWR@lookforpackagename{10}%
1545 \LWR@lookforpackagename{11}%
1546 \LWR@lookforpackagename{12}%
1547 \LWR@lookforpackagename{13}%
1548 \LWR@lookforpackagename{14}%
1549 \LWR@lookforpackagename{15}%
1550 \LWR@lookforpackagename{16}%
1551 \LWR@lookforpackagename{17}%
1552 \LWR@lookforpackagename{18}%
1553 \LWR@lookforpackagename{19}%
1554 \LWR@lookforpackagename{20}%

```

Error if braces are used in optional argument. This can cause an error, so tell how to avoid.

```

1555 \IfSubStr{\detokenize\expandafter{#1}}{\LWRleftbrace}%
1556 {%
1557 \PackageError{lwarp}{%
1558 You used:\MessageBreak
1559 \protect\usepackage[#1]{#2}\MessageBreak
1560 Braces in the package options will fail with Lwarp.\MessageBreak
1561 Instead, use:\MessageBreak
1562 \protect\PassOptionsToPackage{#1}{#2}\MessageBreak
1563 \protect\usepackage{#2}\MessageBreak
1564 near the line number given below.\MessageBreak
1565 Enter 'h' for more info%
1566 }%
1567 {%
1568 See the Lwarp manual troubleshooting index entry for\MessageBreak
1569 ‘package, options with braces’%
1570 }%
1571 }%
1572 {}% no brace

```

\RequirePackage depending on the options and version:

```

1573 \IfValueTF{#1}%
1574 {% options given
1575 \IfValueTF{#3}% version given?
1576 {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}[#3]}%
1577 {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}}%
1578 }%
1579 {% no options given
1580 \IfValueTF{#3}% version given?
1581 {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}[#3]}%
1582 {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}}%
1583 }%
1584 }
1585 \LetLtxMacro\usepackage\RequirePackage

```

```
1586 \@onlypreamble\RequirePackage
1587 \@onlypreamble\usepackage
```

```
1588 \end{warppall}
```

**for HTML output:** 1589 \begin{warppHTML}

```
\LWR@ProvidesPackagePass {<pkgname>} [<version>]
```

Uses the original package, including options.

```
1590 \NewDocumentCommand{\LWR@ProvidesPackagePass}{m o}{
1591 \PackageInfo{lwarp}{%
1592 Using package ‘#1’,\MessageBreak
1593 and adding lwarp modifications, including options,\MessageBreak%
1594 }%
1595 \IfValueTF{#2}%
1596 {\ProvidesPackage{lwarp-#1}[#2]}%
1597 {\ProvidesPackage{lwarp-#1}}%
1598 \DeclareOption*{%
1599 \PassOptionsToPackage{CurrentOption}{#1}%
1600 }%
1601 \ProcessOptions\relax%
```

If using `catoptions`, an error occurs if a package is loaded with an option then loaded again with no options. `lwarp` does this if a package is preloaded then later patched. To avoid an error while using `catoptions`, if a package has already been loaded, it is loaded again with its original options.

```
1602 \IfPackageLoadedTF{#1}{%
1603 \edef\LWR@tempone{\csuse{opt@#1.sty}}%
1604 \IfValueTF{#2}%
1605 {%
1606 \expandafter\LWR@origRequirePackage%
1607 \expandafter[\LWR@tempone]{#1}[#2]%
1608 }%
1609 {%
1610 \expandafter\LWR@origRequirePackage%
1611 \expandafter[\LWR@tempone]{#1}%
1612 }%
1613 }{%
1614 \IfValueTF{#2}%
1615 {\LWR@origRequirePackage{#1}[#2]}%
1616 {\LWR@origRequirePackage{#1}}%
1617 }%
```

In some cases, the following seems to be required to avoid an “unknown option” error, such as when loading `xcolor` with options.

```
1618 \DeclareOption*{%
1619 \ProcessOptions\relax%
1620 }
```

```
\LWR@ProvidesPackageDropA {<name>} {<date or -NoValue->}
```

Declares the package. Factored for reuse.

```

1621 \newcommand*\LWR@ProvidesPackageDropA}[2]{%
1622 \PackageInfo{lwarp}{%
1623 Replacing package ‘#1’ with the lwarp version,\MessageBreak
1624 and discarding options,%
1625 }%
1626 \IfValueTF{#2}
1627 {\ProvidesPackage{lwarp-#1}[#2]}
1628 {\ProvidesPackage{lwarp-#1}}
1629 }

```

`\LWR@ProvidesPackageDropB` Nullifies then processes the options.

Seems to be required when options contain curly braces, which were causing “Missing `\begin{document}`”.

```

1630 \newcommand*\LWR@ProvidesPackageDropB}{%
1631 % \ProcessOptions\relax% original LaTeX code
1632 \let\ds@\empty% from the original \ProcessOptions
1633 \edef\@curroptions{}% lwarp modification to \ProcessOptions
1634 \@processoptions\relax% from the original \ProcessOptions
1635 }

```

`\LWR@ProvidesPackageDrop` `{\langle pkgname \rangle} [\langle version \rangle]`

Ignores the original package and uses lwarp’s version instead. Drops/discards all options.

```

1636 \NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o}{

```

Declare the package:

```

1637 \LWR@ProvidesPackageDropA{#1}{#2}

```

Ignore all options:

```

1638 \DeclareOption*{}

```

Process the options:

```

1639 \LWR@ProvidesPackageDropB
1640 }

```

```

1641 \end{warpHTML}

```

## 32 File handles

Defines file handles for writes.

**for HTML & PRINT:** `1642 \begin{warpall}`

`\LWR@quickfile` For quick temporary use only. This is reused in several places.

```

1643 \newwrite\LWR@quickfile%

```

```
1644 \end{warpall}
```

**for HTML output:** 1645 \begin{warpHTML}

\LWR@lateximagesfile For <project>-images.txt:

```
1646 \newwrite\LWR@lateximagesfile
```

```
1647 \end{warpHTML}
```

### 33 Include a file

During HTML output, `\include{<filename>}` causes the following to occur:

1. `lwarp` creates `<filename>_html_inc.tex` whose contents are:
 

```
\input <filename>.tex
```
2. `<filename>_html_inc.tex` is then `\included` instead of `<filename>.tex`.
3. `<filename>_html_inc.aux` is automatically generated and used by L<sup>A</sup>T<sub>E</sub>X.

**for HTML output:** 1648 \begin{warpHTML}

\@include {<filename>} Modified to load \_html\_inc files.

(Below, `\clearpage` caused missing text, and was changed to `\newpage`.)

```
1649 \def\@include#1 {%
1650 \immediate\openout\LWR@quickfile #1_html_inc.tex% lwarp
1651 \immediate\write\LWR@quickfile{\string\input{#1.tex}}% lwarp
1652 \immediate\closeout\LWR@quickfile% lwarp
1653 \LWR@maybe@orignewpage% changed from clearpage
1654 \if@filesw
1655 \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
1656 \fi
1657 \@tempswatruw
1658 \if@partsw
1659 \@tempswafalse
1660 \edef\reserved@a{#1}%
1661 \@for\reserved@a:=\@partlist\do
1662 {\ifx\reserved@a\reserved@b\@tempswatruw\fi}%
1663 \fi
1664 \if@tempswa
1665 \let\@auxout\@partaux
1666 \if@filesw
1667 \immediate\openout\@partaux #1_html_inc.aux % changed
1668 \immediate\write\@partaux{\relax}%
1669 \fi
1670 \input{#1_html_inc.tex}% changed
1671 \LWR@maybe@orignewpage% changed from clearpage
1672 \writeckpt{#1}%
1673 \if@filesw
1674 \immediate\closeout\@partaux
```

```

1675 \fi
1676 \else
1677 \deadcycles\z@
1678 \@nameuse{cp@#1}%
1679 \fi
1680 \let\@auxout\@mainaux%
1681 }

1682 \end{warpHTML}

```

## 34 Copying a file

**for HTML output:** 1683 \begin{warpHTML}

`\LWR@copyfile {<source filename>} {<destination filename>}`

Used to copy the .toc file to .sidetoc to re-print the TOC in the sideroc navigation pane.

```

1684 \newwrite\LWR@copyoutfile % open the file to write to
1685 \newread\LWR@copyinfile % open the file to read from
1686
1687 \newcommand*{\LWR@copyfile}[2]{%
1688 \LWR@traceinfo{LWR@copyfile: copying #1 to #2}
1689
1690 \immediate\openout\LWR@copyoutfile=#2
1691 \openin\LWR@copyinfile=#1
1692 \begingroup\endlinechar=-1
1693 \makeatletter
1694
1695 \LWR@traceinfo{LWR@copyfile: about to loop}
1696
1697 \loop\unless\ifeof\LWR@copyinfile
1698 \LWR@traceinfo{LWR@copyfile: one line}
1699 \read\LWR@copyinfile to\LWR@fileline % Read one line and store it into \LWR@fileline
1700 % \LWR@fileline\par % print the content into the pdf
1701 % print the content:
1702 \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
1703 \repeat
1704 \immediate\closeout\LWR@copyoutfile
1705 \LWR@traceinfo{LWR@copyfile: done}
1706 \endgroup
1707 }

1708 \end{warpHTML}

```

## 35 Debugging messages

**HTML comments** To have the HTML output include additional HTML comments, such as which <div> is closing, use

```
\booltrue{HTMLDebugComments}
```

**debugging information** To have debug information written to the log, use

```
\tracinglwarp
```

**for HTML & PRINT:** 1709 \begin{warpall}

Bool LWR@tracinglwarp True if tracing is turned on.

```
1710 \newbool{LWR@tracinglwarp}
```

\tracinglwarp Turns on the debug tracing messages.

```
1711 \newcommand{\tracinglwarp}{\booltrue{LWR@tracinglwarp}}
```

\LWR@traceinfo {<text>} If tracing is turned on, writes the text to the .log file.

```
1712 \newcommand{\LWR@traceinfo}[1]{%
1713 \ifbool{LWR@tracinglwarp}%
1714 {%
1715 \typeout{*** lwarp: #1}%
1716 }%
1717 {}%
1718 }
```

Bool HTMLDebugComments Add comments in HTML about closing <div>s, sections, etc.

Default: false

```
1719 \newbool{HTMLDebugComments}
1720 \boolfalse{HTMLDebugComments}
```

If \tracinglwarp, show where preamble hooks occur:

```
1721 \AfterEndPreamble{
1722 \LWR@traceinfo{AfterEndPreamble}
1723 }
1724
1725 \AtBeginDocument{
1726 \LWR@traceinfo{AtBeginDocument}
1727 }
1728 \end{warpall}
```

## 36 Defining print and HTML versions of macros and environments

The following refers to defining objects inside `lwarp`, and may also be of some use for package authors to adapt their packages for `lwarp`. The following is not for the user's document.

Many macros and environments must be provided as both print and HTML versions.

While generating the print version of a document, the original macros as defined by `LATEX` and its packages are used as-is.

While generating the HTML version of a document, the original macro or environment is redefined to call a new HTML version or a copy of the original print

version. The new HTML versions of macros and environments are used most of the time. Copies of the print versions are used inside a `lateximage` environment, which draws and remembers an image of the printed output, and also several other places.

The general structure for providing print and HTML versions of a macro or environment is as follows:

**For a preexisting macro:** An HTML version is provided with a special name, inside a `warpHTML` environment, then `\LWR@formatted` is used to redefine and patch various macros:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}

\LWR@formatted{name}
\end{warpHTML}
```

`\LWR@formatted{name}` copies the original print version to a new name `\LWR@print@<name>`, then redefines `\name` to use either the print or HTML version depending on which mode `lwarp` is using.

**For a preexisting environment:** The process is similar. Note the use of `\LWR@formattedenv` instead of `\LWR@formatted`.

```
\begin{warpHTML}
\newenvironment{\LWR@HTML@name}{...}{...}

\LWR@formattedenv{name}
\end{warpHTML}
```

**For a new macro or environment:** The print version is defined inside `warpall`, so that it can also be seen and modified by during HTML output.

```
\begin{warpall}
\newcommand{\name}{...}% The print version.
\end{warpall}

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment, using `\formattedenv`.

In general, `\LWR@formatted` or `\LWR@formattedenv` are placed inside a `warpHTML` environment, and while producing an HTML document they do the following:

- Macros are modified:
  1. The pre-existing print version `\name` is saved as `\LWR@print@<name>`, unless `\LWR@print@<name>` is already defined.
  2. The original `\name` is redefined to call either the print or HTML version depending on which format is in use at the moment, as set by `\LWR@formatting`, which is defined as either “print” or “HTML”.

- When `lwarp` is producing a print document, the original definitions are used, as well as any new definitions defined in `warpall` above.
- When `lwarp` is generating HTML output, `\LWR@formatting` is set to “HTML”, and `\name` is directed to `\LWR@HTML@<name>`. For an environment, `\endname` is directed to `\endLWR@HTML@<name>`.
- When `lwarp` is generating HTML output but enters a `lateximage` environment, or for some other reason needs to draw images using the original print definitions, `\LWR@formatting` is changed to “print” and `\name` is then redirected to `\LWR@print@<name>`, which was the original `\name`.
- Since the new `\name` does not process any arguments, they are processed by `\LWR@print@name` or `\LWR@HTML@name`.

Expandable versions are also provided as well. These usually are necessary for anything which could appear inside a `tabular`, without which a “Misplaced `\omit`” error may occur.

⚠ Misplaced `\omit` error

```
\LWR@expandableformatted
\LWR@expandableformattedenv
```

(Older versions of `lwarp` used `\LetLtxMacro` for everything, but this could fail when using macros defined by `xparse`. This older system is still in use for many definitions.)

**for HTML output:** 1729 `\begin{warpHTML}`

`\LWR@formatting` Remembers if selected print/HTML formatting.

Used while `\LWR@restoreorigformatting`, such as in an `lateximage`. May be set to either “print” or “HTML”.

```
1730 \newcommand*{\LWR@formatting}{HTML}
```

`\LWR@formatted@checkname` `{<name>}`

```
1731 \newcommand*{\LWR@formatted@checkname}[1]{%
1732 \ifcsundef{#1}{%
1733 \ifcsundef{LWR@print@#1}{%
1734 \PackageError{lwarp}
1735 {%
1736 \LWRbackslash#1 or \protect\LWR@print@#1\MessageBreak
1737 must be defined before using \protect\LWR@formatted, etc%
1738 }
1739 {Perhaps #1 is misspelled.}
1740 }{\relax}%
1741 }{\relax}%
1742 \ifcsundef{LWR@HTML@#1}{%
1743 \PackageError{lwarp}
1744 {%
1745 \protect\LWR@HTML@#1 must be defined
1746 before using \protect\LWR@formatted, etc%
1747 }
1748 {Perhaps #1 is misspelled.}
1749 }{\relax}%
1750 }
```

`\LWR@formatted@checkendname` {<*name*>}

```

1751 \newcommand*{\LWR@formatted@checkendname}[1]{%
1752 \ifcsundef{end#1}{%
1753 \ifcsundef{endLWR@print@#1}{%
1754 \PackageError{lwarp}
1755 {%
1756 \protect\end#1 or \protect\endLWR@print@#1\MessageBreak
1757 must be defined before using \protect\LWR@formatted, etc%
1758 }
1759 {Perhaps #1 is misspelled.}
1760 }\relax}%
1761 }\relax}%
1762 \ifcsundef{endLWR@HTML@#1}{%
1763 \PackageError{lwarp}
1764 {%
1765 \protect\endLWR@HTML@#1 must be defined
1766 before using \protect\LWR@formatted, etc%
1767 }
1768 {Perhaps #1 is misspelled.}
1769 }\relax}%
1770 }
```

`\LWR@formatted` {<*macroname*>} No backslash in the macro name.

If not yet defined, defines `\LWR@print@<name>` as the original print-mode `\<name>`. Also redefines `\<name>` to use `\LWR@<format>@<name>`, where `<format>` is set by `\LWR@formatting`, and is `print` or `HTML`.

```

1771 \newcommand*{\LWR@formatted}[1]{%
1772 \LWR@formatted@checkname{#1}%
1773 \ifcsundef{LWR@print@#1}{%
1774 \csNewCommandCopycs{LWR@print@#1}{#1}%
1775 }{%
1776 \ifcsundef{#1}{%
1777 \expandafter\newrobustcmd\csname #1\endcsname{%
1778 \@nameuse{LWR@\LWR@formatting @#1}%
1779 }%
1780 }{%
1781 \expandafter\renewrobustcmd\csname #1\endcsname{%
1782 \@nameuse{LWR@\LWR@formatting @#1}%
1783 }%
1784 }%
1785 }
```

`\LWR@expandableformatted` {<*macroname*>} No backslash in the macro name.

An expandable version of `\LWR@formatted`.

```

1786 \newcommand*{\LWR@expandableformatted}[1]{%
1787 \LWR@formatted@checkname{#1}%
1788 \ifcsundef{LWR@print@#1}{%
1789 \csNewCommandCopycs{LWR@print@#1}{#1}%
1790 }{%
1791 \ifcsundef{#1}{%
1792 \expandafter\newcommand\csname #1\endcsname{%
1793 \@nameuse{LWR@\LWR@formatting @#1}%
1794 }%
1795 }
```

```

1795 }{%
1796 \expandafter\renewcommand\csname #1\endcsname{%
1797 \@nameuse{LWR@LWR@formatting @#1}%
1798 }%
1799 }%
1800 }

```

`\LWR@formattedenv` {*<environmentname>*}

If not yet defined, defines the environment `LWR@print@<name>` as the original print-mode `<name>`. Also redefines the environment `<name>` to use environment `LWR@<format>@<name>`, where `<format>` is set by `\LWR@formatting`, and is print or HTML.

```

1801 \newcommand*{\LWR@formattedenv}[1]{%
1802 \LWR@formatted@checkname{#1}%
1803 \LWR@formatted@checkendname{#1}%
1804 \ifcsundef{LWR@print@#1}{%
1805 \NewEnvironmentCopy{LWR@print@#1}{#1}%
1806 }{%
1807 \DeclareDocumentEnvironment{#1}{}%
1808 {%
1809 \@nameuse{LWR@LWR@formatting @#1}%
1810 }%
1811 {%
1812 \@nameuse{endLWR@LWR@formatting @#1}%
1813 }%
1814 }

```

`\LWR@expandableformattedenv` {*<environmentname>*}

An expandable version of `LWR@formattedenv`.

```

1815 \newcommand*{\LWR@expandableformattedenv}[1]{%
1816 \LWR@formatted@checkname{#1}%
1817 \LWR@formatted@checkendname{#1}%
1818 \ifcsundef{LWR@print@#1}{%
1819 \NewEnvironmentCopy{LWR@print@#1}{#1}%
1820 }{%
1821 \DeclareExpandableDocumentEnvironment{#1}{}%
1822 {%
1823 \@nameuse{LWR@LWR@formatting @#1}%
1824 }%
1825 {%
1826 \@nameuse{endLWR@LWR@formatting @#1}%
1827 }%
1828 }

```

```
1829 \end{warpHTML}
```

Print versions.

**for PRINT output:** 1830 `\begin{warpprint}`

```

1831 \newcommand*{\LWR@formatted}[1]{}
1832 \newcommand*{\LWR@expandableformatted}[1]{}
1833 \newcommand*{\LWR@formattedenv}[1]{}
1834 \newcommand*{\LWR@expandableformattedenv}[1]{}

```

```
1835 \end{warpprint}
```

## 37 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

**for HTML & PRINT:** 1836 \begin{warppall}

### 37.1 User-level controls

Bool `FormatEPUB` Changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

Default: false

```
1837 \newbool{FormatEPUB}
1838 \boolfalse{FormatEPUB}
```

Bool `FormatWP` Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.

Default: false

```
1839 \newbool{FormatWP}
1840 \boolfalse{FormatWP}
```

Bool `WPMarkFloats` Adds

Default: false

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.<sup>18</sup>

```
1841 \newbool{WPMarkFloats}
1842 \boolfalse{WPMarkFloats}
```

Bool `WPMarkMinipages` Adds

Default: false

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

```
1843 \newbool{WPMarkMinipages}
1844 \boolfalse{WPMarkMinipages}
```

<sup>18</sup>Perhaps some day word processors will have HTML import options for identifying <figure> and caption tags for figures and tables.

|      |                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Bool | WPMarkTOC      | <p>While formatting for word processors, adds</p> <p><i>Default: true</i></p> <pre>=== table of contents ===</pre> <p>where the Table of Contents would have been. This helps identify where to insert the actual toc.</p> <p><i>If set false, the actual toc is printed instead.</i></p> <pre>1845 \newbool{WPMarkTOC} 1846 \booltrue{WPMarkTOC}</pre>                                                                                                                                       |
| Bool | WPMarkLOFT     | <p>While formatting for word processors, adds</p> <p><i>Default: false</i></p> <pre>=== list of figures === and/or === list of tables ===</pre> <p>where each of these lists would have been. This helps identify where to insert the actual lists.</p> <p><i>If set false, the actual lists are printed instead.</i></p> <pre>1847 \newbool{WPMarkLOFT} 1848 \boolfalse{WPMarkLOFT}</pre>                                                                                                    |
| Bool | WPMarkMath     | <p>While formatting for word processors, prints math as L<sup>A</sup>T<sub>E</sub>X code instead of creating SVG images or MATHJAX. This is useful for cut/paste into the <i>LibreOffice Writer TeXMaths</i> extension.</p> <p><i>Default: false</i></p> <pre>1849 \newbool{WPMarkMath} 1850 \boolfalse{WPMarkMath}</pre>                                                                                                                                                                     |
| Bool | WPTitleHeading | <p>While formatting for word processors, true sets the document title to &lt;h1&gt;, which is expected for HTML documents, but also causes the lower-level section headings to start at <b>Heading 2</b> when imported into LIBREOFFICE. Set to false to cause the title to be plain text, and the section headings to begin at <b>Heading 1</b>.</p> <p>See table 11 on page 183.</p> <pre>1851 \newbool{WPTitleHeading} 1852 \boolfalse{WPTitleHeading}</pre> <pre>1853 \end{warpall}</pre> |

## 37.2 Heading adjustments

If formatting the HTML for a word processor, adjust heading levels.

If WPTitleHeading is true, adjust so that part is **Heading 1**.

If WPTitleHeading is false, use <h1> for the title, and set part to **Heading 2**.

**for HTML output:**

```
1854 \begin{warpHTML}
```

```
1855 \AtBeginDocument{
```

```
1856 \ifbool{FormatWP}{
1857 \@ifundefined{chapter}{
1858 \ifbool{WPTitleHeading}{% part and section starting at h2
1859 \renewcommand*\LWR@tagtitle}{h1}
1860 \renewcommand*\LWR@tagtitleend}{/h1}
1861 \renewcommand*\LWR@tagpart}{h2}
1862 \renewcommand*\LWR@tagpartend}{/h2}
1863 \renewcommand*\LWR@tagsection}{h3}
1864 \renewcommand*\LWR@tagsectionend}{/h3}
1865 \renewcommand*\LWR@tagsubsection}{h4}
1866 \renewcommand*\LWR@tagsubsectionend}{/h4}
1867 \renewcommand*\LWR@tagsubsubsection}{h5}
1868 \renewcommand*\LWR@tagsubsubsectionend}{/h5}
1869 \renewcommand*\LWR@tagparagraph}{h6}
1870 \renewcommand*\LWR@tagparagraphend}{/h6}
1871 \renewcommand*\LWR@tagsubparagraph}{span class=\textquotedbl{}subparagraph\textquotedbl}
1872 \renewcommand*\LWR@tagsubparagraphend}{/span}
1873 }% WPTitleHeading
1874 {% not WPTitleHeading, part and section starting at h1
1875 \renewcommand*\LWR@tagtitle}{div class=\textquotedbl{}title\textquotedbl}
1876 \renewcommand*\LWR@tagtitleend}{/div}
1877 \renewcommand*\LWR@tagpart}{h1}
1878 \renewcommand*\LWR@tagpartend}{/h1}
1879 \renewcommand*\LWR@tagsection}{h2}
1880 \renewcommand*\LWR@tagsectionend}{/h2}
1881 \renewcommand*\LWR@tagsubsection}{h3}
1882 \renewcommand*\LWR@tagsubsectionend}{/h3}
1883 \renewcommand*\LWR@tagsubsubsection}{h4}
1884 \renewcommand*\LWR@tagsubsubsectionend}{/h4}
1885 \renewcommand*\LWR@tagparagraph}{h5}
1886 \renewcommand*\LWR@tagparagraphend}{/h5}
1887 \renewcommand*\LWR@tagsubparagraph}{h6}
1888 \renewcommand*\LWR@tagsubparagraphend}{/h6}
1889 }% not WPTitleHeading
1890 }% chapter undefined
1891 {% chapter defined
1892 \ifbool{WPTitleHeading}{}
1893 {% not WPTitleHeading, part and chapter starting at h1
1894 \renewcommand*\LWR@tagtitle}{div class=\textquotedbl{}title\textquotedbl}
1895 \renewcommand*\LWR@tagtitleend}{/div}
1896 \renewcommand*\LWR@tagpart}{h1}
1897 \renewcommand*\LWR@tagpartend}{/h1}
1898 \renewcommand*\LWR@tagchapter}{h2}
1899 \renewcommand*\LWR@tagchapterend}{/h2}
1900 \renewcommand*\LWR@tagsection}{h3}
1901 \renewcommand*\LWR@tagsectionend}{/h3}
1902 \renewcommand*\LWR@tagsubsection}{h4}
1903 \renewcommand*\LWR@tagsubsectionend}{/h4}
1904 \renewcommand*\LWR@tagsubsubsection}{h5}
1905 \renewcommand*\LWR@tagsubsubsectionend}{/h5}
1906 \renewcommand*\LWR@tagparagraph}{h6}
1907 \renewcommand*\LWR@tagparagraphend}{/h6}
1908 \renewcommand*\LWR@tagsubparagraph}{span class=\textquotedbl{}subparagraph\textquotedbl}
1909 \renewcommand*\LWR@tagsubparagraphend}{/span}
1910 }% not WPTitleHeading
1911 }% chapter defined
1912 }{}% FormatWP
1913 }% AtBeginDocument

1914 \end{warpHTML}
```

## 38 Remembering original formatting macros

for HTML output: 1915 \begin{warpHTML}

Remember original definitions of formatting commands. Will be changed to HTML commands for most uses. Will be temporarily restored to original meaning inside any lateximage environment. Also nullify unused commands.

Some packages redefine \#, which is used to generate HTML, so the original must be remembered here.

```
1916 \chardef\LWR@origpound='#
1917 \let\LWR@origcomma\,
1918 \let\LWR@origthinspace\thinspace
1919 \let\LWR@orignegthinspace\negthinspace
1920 \let\LWR@origtilde~
1921 \let\LWR@origenskip\enskip
1922 \let\LWR@origquad\quad
1923 \let\LWR@origqqquad\qqquad
1924 \let\LWR@origfil\hfil
1925 \let\LWR@orighss\hss
1926 \let\LWR@origllap\llap
1927 \let\LWR@origrlap\rlap
1928 \let\LWR@origfilneg\hfilneg
1929 \let\LWR@origspace\hspace
1930
1931 \let\LWR@origrule\rule
1932
1933 \let\LWR@origmedskip\medskip
1934 \let\LWR@origbigskip\bigskip
1935
1936 \let\LWR@origtextellipsis\textellipsis

1937 \let\LWR@origdots\vdots
```

**libertinus-otf** has too much kerning for \textquotedbl, causing an extra space.

```
1938 \LetLtxMacro\LWR@orig@@textquotedbl\textquotedbl
1939 \LetLtxMacro\LWR@orig@textquotedbl\LWR@orig@@textquotedbl
1940
1941 \AtEndPreamble{
1942 \IfPackageLoadedTF{libertinus-otf}{
1943 \renewcommand{\LWR@orig@textquotedbl}{\LWR@orig@@textquotedbl\kern-.15em}
1944 \LetLtxMacro\textquotedbl\LWR@orig@textquotedbl
1945 }{ }
1946 }

1947 \LetLtxMacro\LWR@origttfamily\ttfamily
1948
1949 \LetLtxMacro\LWR@origem\em
1950
1951 \LetLtxMacro\LWR@orignormalfont\normalfont
1952
1953 \let\LWR@origonecolumn\onecolumn
1954
1955 \let\LWR@origsp\sp
```

```

1956 \let\LWR@origsb\sb
1957
1958 \LetLtxMacro\LWR@origunderline\underline

1959 \let\LWR@orignewpage\newpage
1960
1961 \let\LWR@origpagestyle\pagestyle
1962 \let\LWR@origthispagestyle\thispagestyle
1963 \LetLtxMacro\LWR@origpagenumbering\pagenumbering
1964
1965 \let\LWR@orignewline\newline
1966
1967 \AtBeginDocument{% in case packages change definition
1968 \let\LWR@orig@trivlist\@trivlist
1969 \let\LWR@origtrivlist\trivlist
1970 \let\LWR@origendtrivlist\endtrivlist
1971 \LetLtxMacro\LWR@origitem\item
1972 \LetLtxMacro\LWR@origitemize\itemize
1973 \LetLtxMacro\LWR@endorigitemize\enditemize
1974 \LetLtxMacro\LWR@origenumerate\enumerate
1975 \LetLtxMacro\LWR@endorigenumerate\endenumerate
1976 \LetLtxMacro\LWR@origdescription\description
1977 \LetLtxMacro\LWR@endorigdescription\enddescription
1978 \let\LWR@orig@mklab@mklab
1979 \let\LWR@origmakelabel\makelabel
1980 \let\LWR@orig@donoparitem\@donoparitem
1981 \LetLtxMacro\LWR@orig@item\@item
1982 \let\LWR@orig@nbitem\@nbitem
1983 }
1984
1985 \let\LWR@origpar\par
1986
1987 \LetLtxMacro\LWR@origfootnote\footnote
1988 \let\LWR@orig@mpfootnotetext\@mpfootnotetext
1989
1990
1991 \AtBeginDocument{% in case packages change definition
1992 \LetLtxMacro\LWR@origline\hline%
1993 \LetLtxMacro\LWR@origcline\cline%
1994 }

1995 \end{warpHTML}

```

## 39 Accents

Native L<sup>A</sup>T<sub>E</sub>X accents such as `\` will work, but many more kinds of accents are available when using Unicode-aware X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X and LuaL<sup>A</sup>T<sub>E</sub>X. If using accents in section names which will become file names, it is recommended to use the L<sup>A</sup>T<sub>E</sub>X accents such as `\` and `\v` instead of Unicode accents. The L<sup>A</sup>T<sub>E</sub>X accents will have the accents stripped when creating the filenames, whereas the Unicode accents will appear in the file names, which may cause issues with some operating systems.

**for HTML output:** 1996 \begin{warpHTML}

Without `\AtBeginDocument`, `\t` was being re-defined somewhere.

```
1997 \AtBeginDocument{
```

The following are restored for print when inside a lateximage.

For Unicode engines, only `\t` needs to be redefined:

```
1998 \LetLtxMacro\LWR@origtie\t
```

For PDF L<sup>A</sup>T<sub>E</sub>X, additional work is required:

```
1999 \ifPDFTeX% pdflatex or dvi latex
2000 \LetLtxMacro\LWR@origgraveaccent\'
2001 \LetLtxMacro\LWR@origacuteaccent\'
2002 \LetLtxMacro\LWR@origcircumflexaccent\^
2003 \LetLtxMacro\LWR@origtildeaccent\~
2004 \LetLtxMacro\LWR@origmacronaccent\=
2005 \LetLtxMacro\LWR@origbreve\u
2006 \LetLtxMacro\LWR@origdotaccent\.
2007 \LetLtxMacro\LWR@origdiaeresisaccent\"
2008 \LetLtxMacro\LWR@origdoubleacuteaccent\H
2009 \LetLtxMacro\LWR@origcaronaccent\v
2010 \LetLtxMacro\LWR@origdotbelowaccent\d
2011 \LetLtxMacro\LWR@origcedillaaccent\c
2012 \LetLtxMacro\LWR@origmacronbelowaccent\b
```

The HTML redefinitions follow.

For PDF L<sup>A</sup>T<sub>E</sub>X, Unicode diacritical marks are used:

```
2013 \renewcommand*{\'}[1]{#1\HTMLUnicode{0300}}
2014 \renewcommand*{\'}[1]{#1\HTMLUnicode{0301}}
2015 \renewcommand*{\^}[1]{#1\HTMLUnicode{0302}}
2016 \renewcommand*{\~}[1]{#1\HTMLUnicode{0303}}
2017 \renewcommand*{\=}[1]{#1\HTMLUnicode{0304}}
2018 \renewcommand*{\u}[1]{#1\HTMLUnicode{0306}}
2019 \renewcommand*{\.}[1]{#1\HTMLUnicode{0307}}
2020 \renewcommand*{\"}[1]{#1\HTMLUnicode{0308}}
2021 \renewcommand*{\H}[1]{#1\HTMLUnicode{030B}}
2022 \renewcommand*{\v}[1]{#1\HTMLUnicode{030C}}
2023 \renewcommand*{\d}[1]{#1\HTMLUnicode{0323}}
2024 \renewcommand*{\c}[1]{#1\HTMLUnicode{0327}}
2025 \renewcommand*{\b}[1]{#1\HTMLUnicode{0331}}
2026 \fi
```

For all engines, a Unicode diacritical tie is used:

```
2027 \def\LWR@t#1#2{#1\HTMLUnicode{0361}#2}
2028 \renewcommand*{\t}[1]{\LWR@t#1}
```

`\LWR@restoreorigaccents` Called from `\restoreoriginalformatting` when a lateximage is begun.

```
2029 \ifPDFTeX% pdflatex or dvi latex
2030 \newcommand*{\LWR@restoreorigaccents}{%
2031 \LetLtxMacro\'\LWR@origgraveaccent%
2032 \LetLtxMacro\''\LWR@origacuteaccent%
2033 \LetLtxMacro\^\LWR@origcircumflexaccent%
2034 \LetLtxMacro\~\LWR@origtildeaccent%
2035 \LetLtxMacro\=\LWR@origmacronaccent%
2036 \LetLtxMacro\u\LWR@origbreve%
2037 \LetLtxMacro\.\LWR@origdotaccent%
2038 \LetLtxMacro\\"\LWR@origdiaeresisaccent%
```

```

2039 \LetLtxMacro\H\LWR@origdoubleacuteaccent%
2040 \LetLtxMacro\v\LWR@origcaronaccent%
2041 \LetLtxMacro\t\LWR@origtie%
2042 \LetLtxMacro\d\LWR@origdotbelowaccent%
2043 \LetLtxMacro\c\LWR@origcedillaaccent%
2044 \LetLtxMacro\b\LWR@origmacronbelowaccent%
2045 }%
2046 \else% XeLaTeX, LuaLaTeX:
2047 \newcommand*{\LWR@restoreorigaccents}{%
2048 \LetLtxMacro\t\LWR@origtie%
2049 }%
2050 \fi%
2051 }% AtBeginDocument

2052 \end{warpHTML}

```

## 40 Configuration files

### 40.1 Decide whether to generate configuration files

Configuration files are only written if processing the print version of the document, and not processing a pstool image. pstool uses an additional compile for each image using the original document's preamble, which includes lwarp, so the lwarp configuration files are turned off if -pstool is part of the \jobname.

Default to no configuration files:

```
2053 \LWR@excludecomment{\LWRwriteconf}{writeconf}
```

Generate configuration files if print mode and not -pstool:

**for PRINT output:**

```

2054 \begin{warpprint}
2055 \fullexpandarg%
2056 \IfSubStr*{\jobname}{-pstool}
2057 {
2058 \PackageInfo{lwarp}{%
2059 Jobname with -pstool is found.\MessageBreak
2060 Not generating lwarp configuration files,%
2061 }
2062 }
2063 {
2064 \PackageInfo{lwarp}{Generating lwarp configuration files,}%
2065 \LWR@includecomment{\LWRwriteconf}{writeconf}
2066 }
2067 \end{warpprint}

```

### 40.2 <project>\_html.tex

Used to allow an HTML version of the document to exist alongside the print version.

**Config file:**

```

2068 \begin{LWRwriteconf}
2069 \immediate\openout\LWR@quickfile=\jobname_html.tex
2070 \immediate\write\LWR@quickfile{%
2071 \detokenize{\PassOptionsToPackage}%

```

```

2072 {warpHTML,BaseJobname=\jobname}{lwarp}%
2073 }
2074 \immediate\write\LWR@quickfile{%
2075 \detokenize{\input}\string{\jobname.tex\string }%
2076 }
2077 \immediate\closeout\LWR@quickfile
2078 \end{LWRwriteconf}

```

### 40.3 *lwarpmk* configuration files

**Config file:** 2079 \begin{LWRwriteconf}

`\LWR@lwarpcnfversion` The version number of the configuration file, allowing *lwarpmk* to detect an obsolete configuration file format. Incremented by one each time the configuration file format changes. (This is NOT the same as the *lwarp* version number.)

```
2080 \newcommand*{\LWR@lwarpcnfversion}{2}% also in lwarpmk.lua
```

#### 40.3.1 Helper macros

`\LWR@shellescapecmd` The LaTeX compile option for shell escape, if used.

```

2081 \ifshellescape
2082 \def\LWR@shellescapecmd{--shell-escape }
2083 \else
2084 \def\LWR@shellescapecmd{}
2085 \fi

```

`\LWR@compilecmd`  $\{\langle engine \rangle\} \{\langle suffix \rangle\}$

Used to form the basic compilation command for a document, adding the optional shell escape.

Engine is *pdf $\textit{latex}$* , etc. Suffix is empty or `_html`

```

2086 \newcommand*{\LWR@compilecmd}[2]{%
2087 #1 \LWR@shellescapecmd \jobname#2%
2088 }

```

`\LWR@addcompilecmd`  $\{\langle cmd \rangle\} \{\langle suffix \rangle\}$

Adds to the compilation command.

Cmd is *dvipdfmx*, etc. Suffix is empty or `_html`

```

2089 \newcommand*{\LWR@addcompilecmd}[2]{%
2090 \LWRopseq
2091 #1 \jobname#2%
2092 }

```

`\LWR@unknownengine` Error message if not sure which L<sup>A</sup>T<sub>E</sub>X engine is being used.

```
2093 \newcommand*{\LWR@unknownengine}{%
```

```

2094 \PackageError{lwarp}%
2095 {Unknown LaTeX engine}%
2096 {%
2097 Lwarp only knows about pdflatex, DVI latex,
2098 xelatex, lualatex, and upLATEX.%
2099 }%
2100 }

```

`\LWR@latexmkvar`  $\{\langle varname \rangle\} \{\langle value \rangle\}$

Adds a *latexmk* variable assignment.

```

2101 \newcommand*\LWR@latexmkvar}[2]{%
2102 -e
2103 \LWRopquote%
2104 \LWRdollar #1=q/#2/%
2105 \LWRopquote
2106 }

```

`\LWR@latexmkcmd`  $\{\langle latexmk options \rangle\}$

Sets a call to *latexmk* with the given options, possibly adding `--shell-escape`, and also adding the indexing program.

```

2107 \newcommand*\LWR@latexmkcmd}[1]{%
2108 latexmk \space \LWR@shellescapecmd \space #1 \space
2109 -recorder \space
2110 \LWR@latexmkvar{makeindex}\LWR@LatexmkIndexCmd}%
2111 }

```

`\LWR@latexmkdvipdfm`  $\{\langle dvipdfm \text{ or } dvipdfmx \rangle\}$

Adds the options settings for *dvipdfm* or *dvipdfmx*.

```

2112 \newcommand*\LWR@latexmkdvipdfm}[1]{%
2113 -pdfdvi \space
2114 \LWR@latexmkvar{dvipdf}{%
2115 #1
2116 \@percentchar 0
2117 -o \@percentchar D
2118 \@percentchar S%
2119 }
2120 }

```

`\LWR@compileuplatex` Sets compile options for up<sup>L</sup>A<sub>T</sub>E<sub>X</sub> with *ujarticle* or related classes.

```

2121 \newcommand*\LWR@compileuplatex){
2122 \def\LWR@tempprintlatexcmd{%
2123 \LWR@compilecmd{uplatex}{}
2124 \LWR@addcompilecmd{dvipdfmx}{}
2125 }
2126 \def\LWR@tempHTMLlatexcmd{%
2127 \LWR@compilecmd{uplatex}{_html}
2128 \LWR@addcompilecmd{dvipdfmx}{_html}
2129 }
2130 }

```

\LWR@PrintLatexCmd If not set by the user, the following sets the command to use to compile the source  
 \LWR@HTMLLatexCmd to PDF form.

If using *latexmk*, a complicated string is created, eventually resulting in something such as:

For *xelatex* with `--shell-escape`:

---

```
[[latexmk -xelatex --shell-escape -recorder
 -e '$makeindex = q/makeindex -s lwarp.ist/' <jobname>_html]]
```

---

For *dvipdfmx*:

---

```
[[latexmk -pdfdvi -e '$dvi-pdf=q/dvipdfmx %0 -o %D %S/'
 -recorder
 -e '$makeindex=q/makeindex -s lwarp.ist/' <jobname>_html]]
```

---

For the following, temporary values are computed, but the permanent values are only set if the originals were not assigned by the user.

```
2131 \ifbool{LWR@latexmk}{
```

For *latexmk* with *pdflatex* or *lualatex*:

```
2132 \ifpdf
```

For *latexmk* with *pdflatex*:

```
2133 \ifPDFTeX
2134 \def\LWR@latexcmd{\LWR@latexmkcmd{-pdf -dvi- -ps-}}
2135 \else
```

For *latexmk* with *lualatex*:

```
2136 \ifLuaTeX
2137 \def\LWR@latexcmd{\LWR@latexmkcmd{-lualatex}}
2138 \else
2139 \LWR@unknownengine
2140 \fi
2141 \fi
2142 \else% \ifpdf
```

For *latexmk* with *xelatex* or DVI *latex*:

```
2143 \ifXeTeX
```

For *latexmk* with *xelatex*:

```
2144 \def\LWR@latexcmd{\LWR@latexmkcmd{-xelatex}}
2145 \else% \ifXeTeX
```

For *latexmk* with DVI *latex*:

```

2146 \ifbool{LWR@dvi pdfm}{
2147 \def\LWR@latexcmd{%
2148 \LWR@latexmkcmd{%
2149 \LWR@latexmkdvipdfm{dvi pdfm}%
2150 }
2151 }
2152 }{
2153 \ifbool{LWR@dvi pdfmx}{
2154 \def\LWR@latexcmd{%
2155 \LWR@latexmkcmd{%
2156 \LWR@latexmkdvipdfm{dvi pdfmx}%
2157 }
2158 }
2159 }{
2160 \def\LWR@latexcmd{\LWR@latexmkcmd{-pdfps}}
2161 }
2162 }
2163 \fi
2164 \fi% \ifpdf

```

The final assignment if *latexmk*:

```

2165 \def\LWR@tempprintlatexcmd{\LWR@latexcmd \space \jobname}
2166 \def\LWR@tempHTMLlatexcmd{\LWR@latexcmd \space \jobname_html}
2167 }% latexmk

```

Without *latexmk*, the compiling command is simply the compiler name and the optional shell escape:

```

2168 {% not latexmk
2169 \ifpdf

```

For *pdflatex* or *lualatex*:

```

2170 \ifPDFTeX

```

For *pdflatex*:

```

2171 \def\LWR@tempprintlatexcmd{\LWR@compilecmd{pdf latex}}
2172 \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{pdf latex}_{_html}}
2173 \else
2174 \ifLuaTeX

```

For *lualatex*:

```

2175 \def\LWR@tempprintlatexcmd{\LWR@compilecmd{lualatex}}
2176 \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{lualatex}_{_html}}
2177 \else
2178 \LWR@unknownengine
2179 \fi
2180 \fi
2181 \else% \ifpdf

```

For DVI *latex* or *xelatex*:

```

2182 \ifXeTeX

```

For *xelatex*:

```

2183 \def\LWR@tempprintlatexcmd{\LWR@compilecmd{xelatex}{}}
2184 \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{xelatex}{_html}}
2185 \else

```

For DVI *latex*. Default to *dvips*, unless told to use *dvipdfm* or *dvipdfmx*:

```

2186 \ifbool{LWR@dvipdfm}{

```

For DVI *latex* with *dvipdfm*:

```

2187 \def\LWR@tempprintlatexcmd{%
2188 \LWR@compilecmd{latex}{}
2189 \LWR@addcompilecmd{dvipdfm}{}
2190 }
2191 \def\LWR@tempHTMLlatexcmd{%
2192 \LWR@compilecmd{latex}{_html}
2193 \LWR@addcompilecmd{dvipdfm}{_html}
2194 }
2195 }{
2196 \ifbool{LWR@dvipdfmx}{

```

For DVI *latex* with *dvipdfmx*:

```

2197 \def\LWR@tempprintlatexcmd{%
2198 \LWR@compilecmd{latex}{}
2199 \LWR@addcompilecmd{dvipdfmx}{}
2200 }
2201 \def\LWR@tempHTMLlatexcmd{%
2202 \LWR@compilecmd{latex}{_html}
2203 \LWR@addcompilecmd{dvipdfmx}{_html}
2204 }
2205 }{% dvips

```

For DVI *latex* with *dvips* and *ps2pdf*:

```

2206 \def\LWR@tempprintlatexcmd{%
2207 \LWR@compilecmd{latex}{}
2208 \LWR@addcompilecmd{dvips}{}
2209 \LWR@addcompilecmd{ps2pdf -dALLOWPSTRANSARENCY}{} .ps
2210 }
2211 \def\LWR@tempHTMLlatexcmd{%
2212 \LWR@compilecmd{latex}{_html}
2213 \LWR@addcompilecmd{dvips}{_html}
2214 \LWR@addcompilecmd{ps2pdf -dALLOWPSTRANSARENCY}{_html} .ps
2215 }
2216 }
2217 }
2218 \fi% \ifXeTeX
2219 \fi% \ifpdf
2220}% latexmk

```

For *ujarticle*, *utarticle*, and related, using upL<sup>A</sup>T<sub>E</sub>X and *dvipdfmx*:

```

2221 \IfClassLoadedTF{ujarticle}{\LWR@compileuplatex}{}
2222 \IfClassLoadedTF{ujbook}{\LWR@compileuplatex}{}
2223 \IfClassLoadedTF{ujreport}{\LWR@compileuplatex}{}
2224 \IfClassLoadedTF{utarticle}{\LWR@compileuplatex}{}
2225 \IfClassLoadedTF{utbook}{\LWR@compileuplatex}{}
2226 \IfClassLoadedTF{utreport}{\LWR@compileuplatex}{}

```

Only make the setting permanent if the original was empty:

```
2227 \ifdefempty{\LWR@PrintLatexCmd}{
2228 \def\LWR@PrintLatexCmd{\LWR@tempprintlatexcmd}
2229 }{}
2230 \ifdefempty{\LWR@HTMLLatexCmd}{
2231 \def\LWR@HTMLLatexCmd{\LWR@tempHTMLlatexcmd}
2232 }{}
```

`\LWR@writeconf {<filename>}`

Common code for each of `lwarpmk.conf` and `<project>.lwarpmkconf`. Each entry is a variable name, the equal sign, and a quoted string inside `[[ and ]]`, which are *lua*'s long quote characters, allowing the use of single and double quotes inside.

```
2233 \newcommand{\LWR@writeconf}[1]{
2234 \ifcsdef{\LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
2235 \immediate\openout\LWR@quickfile=#1
2236 \immediate\write\LWR@quickfile{confversion = [[\LWR@lwarpcnfversion]]}
2237 \ifbool{usingOSWindows}{
2238 \immediate\write\LWR@quickfile{opsystem = [[Windows]]}
2239 }{
2240 \immediate\write\LWR@quickfile{opsystem = [[Unix]]}
2241 }
2242 \immediate\write\LWR@quickfile{sourcename = [[\jobname]]}
2243 \immediate\write\LWR@quickfile{homehtmlfilename = [[\HomeHTMLFilename]]}
2244 \immediate\write\LWR@quickfile{htmlfilename = [[\HTMLFilename]]}
2245 \immediate\write\LWR@quickfile{imagesdirectory = [[\LWR@ImagesDirectory]]}
2246 \immediate\write\LWR@quickfile{imagesname = [[\LWR@ImagesName]]}
2247 \immediate\write\LWR@quickfile{latexmk = [[\ifbool{\LWR@latexmk}{true}{false}]]}
2248 \immediate\write\LWR@quickfile{printlatexcmd = [[\LWR@PrintLatexCmd]]}
2249 \immediate\write\LWR@quickfile{HTMLlatexcmd = [[\LWR@HTMLLatexCmd]]}
2250 \immediate\write\LWR@quickfile{printindexcmd = [[\LWR@PrintIndexCmd]]}
2251 \immediate\write\LWR@quickfile{HTMLindexcmd = [[\LWR@HTMLIndexCmd]]}
2252 \immediate\write\LWR@quickfile{latexmkindexcmd = [[\LWR@LatexmkIndexCmd]]}
2253 \immediate\write\LWR@quickfile{glossarycmd = [[\LWR@GlossaryCmd]]}
2254 \immediate\write\LWR@quickfile{pdftotextenc = [[\LWR@pdftotextEnc]]}
2255 \immediate\closeout\LWR@quickfile
2256 }
2257

2258 \end{\LWR@writeconf}
```

### 40.3.2 lwarpmk.conf

File `lwarpmk.conf`

`lwarpmk.conf` is automatically (re-)created by the `lwarp` package when executing `pdflatex <project.tex>`, or similar for `xelatex` or `lualatex`, in print-document generation mode, which is the default unless the `warpHTML` option is given. `lwarpmk.conf` is then used by the utility `lwarpmk`.

**Config file:**

```
2259 \begin{\LWR@writeconf}
2260
2261 \AtBeginDocument{\LWR@writeconf{lwarpmk.conf}}
2262
2263 \end{\LWR@writeconf}
```

### 40.3.3 <project>.lwarpmkconf

File project.lwarpmkconf

A project-specific configuration file for *lwarpmk*.

The `makeindex` and `xindy` options have already been handled for `lwarp.conf`.

**Config file:**

```
2264 \begin{LWRwriteconf}
2265
2266 \AtBeginDocument{\LWRwriteconf{\jobname.lwarpmkconf}}
2267
2268 \end{LWRwriteconf}
```

## 40.4 lwarp.css

File lwarp.css

This is the base CSS layer used by *lwarp*.

This must be present both when compiling the project and also when distributing the HTML files.

**Config file:**

```
2269 \begin{LWRwriteconf}
2270 \begin{filecontents*}[overwrite]{lwarp.css}
2271 /*
2272 CSS stylesheet for the LaTeX Lwarp package
2273 Copyright 2016-2022 Brian Dunn – BD Tech Concepts LLC
2274 */
2275
2276
2277 /* a fix for older browsers: */
2278 header, section, footer, aside, nav, main,
2279 article, figure { display: block; }
2280
2281
2282 A:link {color:#000080 ; text-decoration: none ; }
2283 A:visited {color:#800000 ; }
2284 A:hover {color:#000080 ; text-decoration: underline ;}
2285 A:active {color:#800000 ; }
2286
2287 a.tocbook {display: inline-block ; margin-left: 0em ;
2288 font-weight: bold ; margin-top: 1ex ; margin-bottom: 1ex ; }
2289 a.tocpart {display: inline-block ; margin-left: 0em ;
2290 font-weight: bold ;}
2291 a.tocchapter {display: inline-block ; margin-left: 0em ;
2292 font-weight: bold ;}
2293 a.tocsection {display: inline-block ; margin-left: 1em ;
2294 text-indent: -.5em ; font-weight: bold ; }
2295 a.tocsubsection {display: inline-block ; margin-left: 2em ;
2296 text-indent: -.5em ; }
2297 a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
2298 text-indent: -.5em ; }
2299 a.tocparagraph {display: inline-block ; margin-left: 4em ;
2300 text-indent: -.5em ; }
2301 a.tocsubparagraph {display: inline-block ; margin-left: 5em ;
2302 text-indent: -.5em ; }
2303 a.tocfigure {margin-left: 0em}
2304 a.tocsubfigure {margin-left: 2em}
2305 a.tocatable {margin-left: 0em}
2306 a.tocsubtable {margin-left: 2em}
2307 a.toctheorem {margin-left: 0em}
```

```
2308 a.toclstlisting {margin-left: 0em}
2309
2310 body {
2311 font-family: "DejaVu Serif", "Bitstream Vera Serif",
2312 "Lucida Bright", Georgia, serif;
2313 background: #FAF7F4 ;
2314 color: black ;
2315 margin:0em ;
2316 padding:0em ;
2317 font-size: 100% ;
2318 line-height: 1.2 ;
2319 }
2320
2321 p {margin: 1.5ex 0em 1.5ex 0em ;}
2322 table p {margin: .5ex 0em .5ex 0em ;}
2323
2324 /* Holds a section number */
2325 span.sectionnumber { margin-right: 0em }
2326
2327 /* Inserted in front of index lines */
2328 span.indexitem {margin-left: 0em}
2329 span.indexsubitem {margin-left: 2em}
2330 span.indexsubsubitem {margin-left: 4em}
2331 div.indexheading {margin-top: 2ex ; font-weight: bold}
2332
2333 div.hidden, span.hidden { display: none ; }
2334
2335 kbd, span.texttt, p span.texttt {
2336 font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2337 "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2338 "Courier New", monospace;
2339 font-size: 100% ;
2340 }
2341
2342 pre { padding: 3pt ; }
2343
2344 span.strong, span.textbf, div.strong, div.textbf, table td.tdbfseries { font-weight: bold; }
2345
2346 span.textit, div.textit, table td.tditshape { font-style: italic; }
2347
2348 table td.tdbfit { font-weight: bold ; font-style:italic }
2349
2350 span.textnormal, div.textnormal {
2351 font-weight: normal;
2352 font-style: normal;
2353 font-variant: normal;
2354 font-variant-numeric: normal ;
2355 font-family: "DejaVu Serif", "Bitstream Vera Serif",
2356 "Lucida Bright", Georgia, serif;
2357 }
2358
2359 span.textmd, div.textmd { font-weight: normal; }
2360
2361 span.textup, div.textup {
2362 font-style: normal;
2363 font-variant: normal;
2364 font-variant-numeric: normal ;
2365 }
2366
2367 span.textsc, div.textsc {
```

```
2368 font-variant: small-caps;
2369 font-variant-numeric: oldstyle-nums ;
2370 }
2371
2372 span.textulc, div.textulc {
2373 font-variant: normal ;
2374 font-variant-numeric: normal ;
2375 }
2376
2377 span.textsl, div.textsl { font-style: oblique; }
2378
2379 span.textrm, div.textrm {
2380 font-family: "DejaVu Serif", "Bitstream Vera Serif",
2381 "Lucida Bright", Georgia, serif;
2382 }
2383
2384 span.textsf, div.textsf {
2385 font-family: "DejaVu Sans", "Bitstream Vera Sans",
2386 Geneva, Verdana, sans-serif ;
2387 }
2388
2389 /* nfssect-cfr lining figures */
2390 span.textln, div.textln {
2391 font-variant-numeric: lining-nums ;
2392 }
2393
2394 /* nfssect-cfr proportional figures */
2395 span.textp, div.textp {
2396 font-variant-numeric: proportional-nums ;
2397 }
2398
2399 /* nfssect-cfr tabular figures */
2400 span.textt, div.textt {
2401 font-variant-numeric: tabular-nums ;
2402 }
2403
2404 /* nfssect-cfr font weights */
2405 span.textdb, div.textdb {
2406 font-weight: 500 ;
2407 }
2408
2409 span.textsb, div.textsb {
2410 font-weight: 600 ;
2411 }
2412
2413 span.texteb, div.texteb {
2414 font-weight: 800 ;
2415 }
2416
2417 span.textub, div.textub {
2418 font-weight: 900 ;
2419 }
2420
2421 span.textlg, div.textlg {
2422 font-weight: 300 ;
2423 }
2424
2425 span.textel, div.textel {
2426 font-weight: 200 ;
2427 }
```

```
2428
2429 span.textul, div.textul {
2430 font-weight: 100 ;
2431 }
2432
2433
2434
2435 span.textcircled { border: 1px solid black ; border-radius: 1ex ; }
2436
2437 span.underline {
2438 text-decoration: underline ;
2439 text-decoration-skip: auto ;
2440 }
2441
2442 span.overline {
2443 text-decoration: overline ;
2444 text-decoration-skip: auto ;
2445 }
2446
2447 div.hrule { border-top: 1px solid silver }
2448
2449
2450 /* for vertical text: */
2451 div.verticalrl { writing-mode: vertical-rl }
2452 div.horizontaltb { writing-mode: horizontal-tb }
2453
2454
2455 /* for diagbox */
2456 div.diagboxtitleN { border-bottom: 1px solid gray }
2457 div.diagboxtitleS { border-top: 1px solid gray }
2458
2459 div.diagboxE {
2460 padding-left: 2em ;
2461 text-align: right ;
2462 }
2463
2464 div.diagboxW {
2465 padding-right: 2em ;
2466 text-align: left ;
2467 }
2468
2469
2470
2471 /* For realscripts */
2472 .supsubscript {
2473 display: inline-block;
2474 text-align:left ;
2475 }
2476
2477 .supsubscript sup,
2478 .supsubscript sub {
2479 position: relative;
2480 display: block;
2481 font-size: .7em;
2482 line-height: 1;
2483 }
2484
2485 .supsubscript sup {
2486 top: .3em;
2487 }
```

```
2488
2489 .supsubscript sub {
2490 top: .3em;
2491 }
2492
2493 div.attribution p {
2494 text-align: right ;
2495 font-size: 80%
2496 }
2497
2498 span.poemtitle {
2499 font-size: 120% ; font-weight: bold;
2500 }
2501
2502 pre.tabbing {
2503 font-family: "Linux Libertine Mono O", "Lucida Console",
2504 "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
2505 "Liberation Mono", "FreeMono", "Andale Mono",
2506 "Nimbus Mono L", "Courier New", monospace;
2507 }
2508
2509 blockquote {
2510 display: block ;
2511 margin-left: 2em ;
2512 margin-right: 2em ;
2513 }
2514
2515 /* quotchap is for the quotchap package */
2516 div.quotchap {
2517 display: block ;
2518 font-style: oblique ;
2519 overflow-x: auto ;
2520 margin-left: 2em ;
2521 margin-right: 2em ;
2522 }
2523
2524 blockquote p, div.quotchap p {
2525 line-height: 1.5;
2526 text-align: left ;
2527 font-size: .85em ;
2528 }
2529
2530 /* qauthor is for the quotchap package */
2531 div.qauthor {
2532 display: block ;
2533 text-align: right ;
2534 margin-left: auto ;
2535 margin-right: 2em ;
2536 font-size: 80% ;
2537 font-variant: small-caps;
2538 }
2539
2540 div.qauthor p {
2541 text-align: right ;
2542 }
2543
2544 div.epigraph, div.dictum {
2545 line-height: 1.2;
2546 text-align: left ;
2547 padding: 3ex 1em 0ex 1em ;
```

```
2548 /* margin: 3ex auto 3ex auto ; */ /* Epigraph centered */
2549 margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
2550 /* margin: 3ex 1em 3ex 1em ; */ /* Epigraph to the left */
2551 font-size: .85em ;
2552 max-width: 27em ;
2553 }
2554
2555 div.epigraphsource, div.dictumauthor {
2556 text-align:right ;
2557 margin-left:auto ;
2558 /* max-width: 50% ; */
2559 border-top: 1px solid #A0A0A0 ;
2560 padding-bottom: 3ex ;
2561 line-height: 1.2;
2562 }
2563
2564 div.epigraph p, div.dictum p { padding: .5ex ; margin: 0ex ;}
2565 div.epigraphsource p, div.dictumauthor p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
2566 div.dictumauthor { font-style:italic }
2567
2568
2569 /* copyrightbox package: */
2570 div.copyrightbox { margin: .5ex .5em }
2571 div.copyrightbox p {margin: 0px .5em ; padding: 0px}
2572 div.copyrightboxnote {text-align: left ; font-size: 60%}
2573
2574
2575 /* lettrine package: */
2576 span.lettrine { font-size: 4ex ; float: left ; }
2577 span.lettrinetext { font-variant: small-caps ; }
2578
2579 /* ulem, soul, umoline packages: */
2580 span.uline {
2581 text-decoration: underline ;
2582 text-decoration-skip: auto ;
2583 }
2584
2585 span.uuline {
2586 text-decoration: underline ;
2587 text-decoration-skip: auto ;
2588 text-decoration-style: double ;
2589 }
2590
2591 span.uwave {
2592 text-decoration: underline ;
2593 text-decoration-skip: auto ;
2594 text-decoration-style: wavy ;
2595 }
2596
2597 span.sout {
2598 text-decoration: line-through ;
2599 }
2600
2601 span.oline {
2602 text-decoration: overline ;
2603 text-decoration-skip: auto ;
2604 }
2605
2606 span.xout {
2607 text-decoration: line-through ;
```

```
2608 }
2609
2610 span.dashuline {
2611 text-decoration: underline ;
2612 text-decoration-skip: auto ;
2613 text-decoration-style: dashed ;
2614 }
2615
2616 span.dotuline {
2617 text-decoration: underline ;
2618 text-decoration-skip: auto ;
2619 text-decoration-style: dotted ;
2620 }
2621
2622 span.letterspacing { letter-spacing: .2ex ; }
2623
2624 span.capsspacing {
2625 font-variant: small-caps ;
2626 letter-spacing: .1ex ;
2627 }
2628
2629 span.highlight { background: #F8E800 ; }
2630
2631
2632 /* keystroke package: */
2633 span.keystroke {
2634 border-style: outset ;
2635 padding: 0pt .5em 0pt .5em ;
2636 }
2637
2638
2639 html body {
2640 margin: 0 ;
2641 line-height: 1.2;
2642 }
2643
2644
2645 body div {
2646 margin: 0ex;
2647 }
2648
2649
2650 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
2651 {
2652 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2653 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2654 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2655 "Times New Roman", serif;
2656 font-style: normal ;
2657 font-weight: bold ;
2658 text-align: left ;
2659 }
2660
2661 h1 { /* title of the entire website, used on each page */
2662 text-align: center ;
2663 font-size: 2.5em ;
2664 padding: .4ex 0em 0ex 0em ;
2665 }
2666
2667 div.book {
```

```
2668 text-align: center ;
2669 font-size: 2.325em ;
2670 padding: .4ex 0em 0ex 0em ;
2671 }
2672
2673 h2 { font-size: 2.25em }
2674 h3 { font-size: 2em }
2675 h4 { font-size: 1.75em }
2676 h5 { font-size: 1.5em }
2677 h6 { font-size: 1.25em }
2678 span.paragraph {font-size: 1em ; font-variant: normal ;
2679 margin-right: 1em ; }
2680 span.subparagraph {font-size: 1em ; font-variant: normal ;
2681 margin-right: 1em ; }
2682
2683 div.minisec {
2684 font-family: "DejaVu Sans", "Bitstream Vera Sans",
2685 Geneva, Verdana, sans-serif ;
2686 font-style: normal ;
2687 font-weight: bold ;
2688 text-align: left ;
2689 }
2690
2691 h1 {
2692 margin: 0ex 0em 0ex 0em ;
2693 line-height: 1.3;
2694 text-align: center ;
2695 }
2696
2697 h2 {
2698 margin: 1ex 0em 1ex 0em ;
2699 line-height: 1.3;
2700 text-align: center ;
2701 }
2702
2703 h3 {
2704 margin: 3ex 0em 1ex 0em ;
2705 line-height: 1.3;
2706 }
2707
2708 h4 {
2709 margin: 3ex 0em 1ex 0em ;
2710 line-height: 1.3;
2711 }
2712
2713 h5 {
2714 margin: 3ex 0em 1ex 0em ;
2715 line-height: 1.3;
2716 }
2717
2718 h6 {
2719 margin: 3ex 0em 1ex 0em ;
2720 line-height: 1.3;
2721 }
2722
2723
2724 div.titlepage {
2725 text-align: center ;
2726 }
2727
```

```
2728 .footnotes {
2729 text-align: left ;
2730 font-size: .85em ;
2731 margin: 3ex 2em 0ex 2em ;
2732 border-top: 1px solid silver ;
2733 }
2734
2735 .marginpar, .marginparblock {
2736 max-width: 50%;
2737 float: right ;
2738 clear: both ;
2739 text-align: left ;
2740 margin: 1ex 0.5em 1ex 1em ;
2741 padding: 1ex 0.5em 1ex 0.5em ;
2742 font-size: 85% ;
2743 border-top: 1px solid silver ;
2744 border-bottom: 1px solid silver ;
2745 overflow-x: auto ;
2746 }
2747
2748 .marginpar br { margin-bottom: 2ex ; }
2749
2750 div.marginblock, div.marginparblock {
2751 max-width:50%;
2752 min-width: 10em; /* room for caption */
2753 float:right;
2754 text-align:left;
2755 margin: 1ex 0.5em 1ex 1em ;
2756 padding: 1ex 0.5em 1ex 0.5em ;
2757 overflow-x: auto;
2758 }
2759
2760 div.marginblock div.minipage,
2761 div.marginparblock div.minipage {
2762 display: inline-block ;
2763 margin: 0pt auto 0pt auto ;
2764 }
2765
2766 div.marginblock div.minipage p ,
2767 div.marginparblock div.minipage p
2768 { font-size: 85%}
2769
2770 div.marginblock br ,
2771 div.marginparblock br
2772 { margin-bottom: 2ex ; }
2773
2774 main.bodycontainer {
2775 float: left ;
2776 width: 80% ;
2777 }
2778
2779 div.bodywithoutsidetoc main.bodycontainer {
2780 float: none ;
2781 width: 100% ;
2782 }
2783
2784 section.textbody div.footnotes{
2785 margin: 1ex 2em 2ex 2em ;
2786 border-bottom: 2px solid silver ;
2787 }
```

```
2788
2789 .footnoteheader {
2790 border-top: 2px solid silver ;
2791 margin-top: 3ex ;
2792 padding-top: 1ex ;
2793 font-weight: bold ;
2794 }
2795
2796 .mpfootnotes {
2797 text-align: left ;
2798 font-size: .85em ;
2799 margin-left: 1em ;
2800 border-top: 1px solid silver ;
2801 }
2802
2803 /* Remove footnote top border in the title page. */
2804 div.titlepage div.mpfootnotes {
2805 border-top: none ;
2806 }
2807
2808
2809
2810 ul, ol {
2811 margin: 1ex 1em 1ex 0em;
2812 line-height: 1.2;
2813 }
2814
2815 body dir, body menu {
2816 margin: 3ex 1em 3ex 0em;
2817 line-height: 1.2;
2818 }
2819
2820 li { margin: 0ex 0em 1ex 0em; }
2821
2822 li.p { display: inline ; }
2823
2824 html {
2825 margin: 0;
2826 padding: 0;
2827 }
2828
2829 .programlisting {
2830 font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2831 "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2832 "Courier New", monospace;
2833 margin: 1ex 0ex 1ex 0ex ;
2834 padding: .5ex 0pt .5ex 0pt ;
2835 overflow-x: auto;
2836 }
2837
2838 section.textbody>pre.programlisting {
2839 border-top: 1px solid silver ;
2840 border-bottom: 1px solid silver ;
2841 }
2842
2843
2844 div.displaymath {
2845 text-align: center ;
2846 }
2847
```

```
2848 div.displaymathnumbered {
2849 text-align: right ;
2850 margin-left: 5% ;
2851 margin-right: 5% ;
2852 min-width: 2.5in ;
2853 }
2854
2855 @media all and (min-width: 400px) {
2856 div.displaymathnumbered {
2857 margin-left: 10% ;
2858 margin-right: 10% ;
2859 }
2860 }
2861
2862 @media all and (min-width: 800px) {
2863 div.displaymathnumbered {
2864 margin-right: 20% ;
2865 }
2866 }
2867
2868 @media all and (min-width: 1200px) {
2869 div.displaymathnumbered {
2870 margin-right: 30% ;
2871 }
2872 }
2873
2874
2875 .inlineprogramlisting {
2876 font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2877 "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2878 "Courier New", monospace;
2879 overflow-x: auto;
2880 }
2881
2882 span.listinglabel {
2883 display: inline-block ;
2884 font-size: 70% ;
2885 width: 4em ;
2886 text-align: right ;
2887 margin-right: 2em ;
2888 }
2889
2890 div.abstract {
2891 margin: 2em 5% 2em 5% ;
2892 padding: 1ex 1em 1ex 1em ;
2893 /* font-weight: bold ; */
2894 font-size: 90% ;
2895 text-align: left ;
2896 }
2897
2898 div.abstract dl {line-height:1.5;}
2899 div.abstract dt {color:#304070;}
2900
2901 div.abstracttitle{
2902 font-family: "URW Classico", Optima, "Linux Biolinum O",
2903 "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2904 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2905 font-weight:bold;
2906 font-size:1.25em;
2907 text-align: center ;
```

```
2908 }
2909
2910 span.abstractrunintitle{
2911 font-family: "URW Classico", Optima, "Linux Biolinum O",
2912 "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2913 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2914 font-weight:bold;
2915 }
2916
2917
2918 .verbatim {
2919 overflow-x: auto ;
2920 }
2921
2922 .alltt {
2923 overflow-x: auto ;
2924 }
2925
2926
2927 .bverbatim {
2928 margin: 1ex 0pt 1ex 0pt ;
2929 padding: .5ex 0pt .5ex 0pt ;
2930 overflow-x: auto ;
2931 }
2932
2933 .lverbatim {
2934 margin: 1ex 0pt 1ex 0pt ;
2935 padding: .5ex 0pt .5ex 0pt ;
2936 overflow-x: auto ;
2937 }
2938
2939 .fancyvrb {
2940 font-size:.85em ;
2941 margin: 3ex 0pt 3ex 0pt
2942 }
2943
2944 .fancyvrblabel {
2945 font-size: .85em ;
2946 text-align: center ;
2947 font-weight: bold ;
2948 margin-top: 1ex ;
2949 margin-bottom: 1ex ;
2950 }
2951
2952
2953 .verse {
2954 font-family: "Linux Libertine Mono O", "Lucida Console",
2955 "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
2956 "Liberation Mono", "FreeMono", "Andale Mono",
2957 "Nimbus Mono L", "Courier New", monospace;
2958 margin-left: 1em ;
2959 }
2960
2961
2962 div.singlespace { line-height: 1.2 ; }
2963 div.onehalfspace { line-height: 1.5 ; }
2964 div.doublespace { line-height: 2 ; }
2965
2966
2967 /* Word processor format output: */
```

```
2968 div.wpfigure { border: 1px solid red ; margin: .5ex ; padding: .5ex ; }
2969 div.wptable { border: 1px solid blue ; margin: .5ex ; padding: .5ex ; }
2970 div.wpminipage { border: 1px solid green ; margin: .5ex ; padding: .5ex ;}
2971
2972
2973
2974
2975 /* Minipage environments, vertically aligned to top, center, bottom: */
2976 .minipage, .fminipage, .fcolorminipage {
2977 /* display: inline-block ; */
2978 /* Mini pages which follow each other will be tiled. */
2979 text-align:left;
2980 margin: .25em .25em .25em .25em;
2981 padding: .25em .25em .25em .25em;
2982 display: inline-flex;
2983 flex-direction: column ;
2984 overflow: auto;
2985 }
2986
2987 .inlineminipage {
2988 display: inline-block ;
2989 text-align: left
2990 }
2991
2992 /* Paragraphs in the flexbox did not collapse their margins. */
2993 /* Have not yet researched this. */
2994 .minipage p {margin: .75ex 0em .75ex 0em ;}
2995
2996 .fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
2997 .fcolorbox .minipage, .fcolorboxBlock .minipage
2998 {border: none ; background: none;}
2999
3000 .fbox, .fboxBlock { border: 1px solid black ; padding: 4pt }
3001
3002 .fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
3003 .fminipage, .fcolorminipage
3004 {display: inline-block}
3005
3006 .shadowbox, .shabox {
3007 border: 1px solid black;
3008 box-shadow: 3px 3px 3px #808080 ;
3009 border-radius: 0px ;
3010 padding: .4ex .3em .4ex .3em ;
3011 margin: 0pt .3ex 0pt .3ex ;
3012 display: inline-block ;
3013 }
3014
3015 .doublebox {
3016 border: 3px double black;
3017 border-radius: 0px ;
3018 padding: .4ex .3em .4ex .3em ;
3019 margin: 0pt .3ex 0pt .3ex ;
3020 display: inline-block ;
3021 }
3022
3023 .ovalbox, .Ovalbox {
3024 border: 1px solid black;
3025 border-radius: 1ex ;
3026 padding: .4ex .3em .4ex .3em ;
3027 margin: 0pt .3ex 0pt .3ex ;
```

```
3028 display: inline-block ;
3029 }
3030
3031 .Ovalbox { border-width: 2px ; }
3032
3033 .framebox {
3034 border: 1px solid black;
3035 border-radius: 0px ;
3036 padding: .3ex .2em 0ex .2em ;
3037 margin: 0pt .1ex 0pt .1ex ;
3038 display: inline-block ;
3039 }
3040
3041
3042 /* mdframed, tcolorbox, shadebox packages */
3043 .mdframed, .tcolorbox, .shadebox {
3044 padding: 0ex ;
3045 margin: 2ex 0em 2ex 0em ;
3046 border: 1px solid black ;
3047 }
3048
3049 .tcolorbox {
3050 border-radius: 10pt ;
3051 margin: 2ex 1em 2ex 1em ;
3052 }
3053
3054 .mdframed p, .tcolorbox p { padding: 0ex .5em 0ex .5em ; }
3055
3056 .mdframed dl, .tcolorbox dl { padding: 1ex .5em 0ex .5em ; }
3057
3058 .mdframedtitle, .tcolorboxtitle {
3059 padding: .5ex 0pt 0pt 0pt ;
3060 border-radius: 10pt 10pt 0pt 0pt ;
3061 display: block ;
3062 margin-bottom: 1ex ;
3063 border-bottom: 1px solid silver ;
3064 }
3065
3066 .tcolorboxsubtitle .tcolorbox {
3067 margin: 2ex 0em 2ex 0em ;
3068 border-radius: 0pt ;
3069 }
3070
3071 .mdframedsubtitle {
3072 display: block ;
3073 }
3074
3075 .mdframedsubsubtitle {
3076 display: block ;
3077 }
3078
3079 .mdtheorem {
3080 padding: 0ex .5em 0ex .5em ;
3081 margin: 3ex 5% 3ex 5% ;
3082 }
3083
3084
3085 /* framed package */
3086 .framed, pre.boxedverbatim, fcolorbox {
3087 margin: 3ex 0em 3ex 0em ;
```

```
3088 border: 1px solid black;
3089 border-radius: 0px ;
3090 padding: .3ex 1em 0ex 1em ;
3091 display: block ;
3092 }
3093
3094 .shaded {
3095 margin: 3ex 0em 3ex 0em ;
3096 padding: .3ex 1em .3ex 1em ;
3097 display: block ;
3098 }
3099
3100 .snugframed {
3101 margin: 3ex 0em 3ex 0em ;
3102 border: 1px solid black;
3103 border-radius: 0px ;
3104 display: block ;
3105 }
3106
3107 .framedleftbar {
3108 margin: 3ex 0em 3ex 0em ;
3109 border-left: 3pt solid black;
3110 border-radius: 0px ;
3111 padding: .3ex .2em .3ex 1em ;
3112 display: block ;
3113 }
3114
3115 .framedtitle {
3116 margin: 0em ;
3117 padding: 0em ;
3118 font-size: 130%
3119 }
3120
3121 .framedtitle p { padding: .3em }
3122
3123
3124 /* For the niceframe package: */
3125
3126 div.niceframe, div.curlyframe, div.artdecoframe, div.generalframe {
3127 padding: 1ex ;
3128 margin: 2ex auto ;
3129 border-radius: 2ex ;
3130 }
3131
3132 div.niceframe {
3133 border: 6px groove black ;
3134 }
3135
3136 div.curlyframe {
3137 border-left: 3px dotted black ;
3138 border-right: 3px dotted black ;
3139 border-radius: 6ex ;
3140 }
3141
3142 div.artdecoframe {
3143 border-left: 10px double black ;
3144 border-right: 10px double black ;
3145 border-radius: 6ex ;
3146 }
3147
```

```
3148 div.generalframe {
3149 border: 6px groove black ;
3150 }
3151
3152
3153 /* For beamerarticle: */
3154 div.beamerframe {
3155 margin: 3ex 1em 3ex 1em ;
3156 border: 1px solid gray;
3157 border-radius: 0px ;
3158 padding: .3ex 1em 0ex 1em ;
3159 display: block ;
3160 }
3161
3162
3163 dl {
3164 margin: 1ex 2em 1ex 0em;
3165 line-height: 1.3;
3166 }
3167
3168 dl dt {
3169 display: block ;
3170 float:left ;
3171 font-weight: bold;
3172 padding-right: 1em ;
3173 }
3174
3175 dl dd { display: block ; }
3176
3177 dl dd:after { content: "" ; display: block ; clear: both }
3178
3179 dl dd p { margin-top: 0em; }
3180
3181 dd ul, dd ol, dd dl {
3182 clear: both ;
3183 /* padding-top: 1ex ; */
3184 }
3185
3186
3187 nav {
3188 font-family: "URW Classico", Optima, "Linux Biolinum O",
3189 "DejaVu Sans", "Bitstream Vera Sans",
3190 Geneva, Verdana, sans-serif ;
3191 margin-bottom: 4ex ;
3192 }
3193
3194 nav p {
3195 line-height: 1.2 ;
3196 margin-top:.5ex ;
3197 margin-bottom:.5ex;
3198 font-size: .9em ;
3199 }
3200
3201
3202
3203 img, img.hyperimage, img.borderimage {
3204 max-width: 600px;
3205 border: 1px solid silver;
3206 box-shadow: 3px 3px 3px #808080 ;
3207 padding: .5% ;
```

```
3208 margin: .5% ;
3209 background: none ;
3210 }
3211
3212 img.inlineimage{
3213 padding: 0px ;
3214 box-shadow: none ;
3215 border: none ;
3216 background: none ;
3217 margin: 0px ;
3218 display: inline-block ;
3219 border-radius: 0px ;
3220 }
3221
3222 img.logoimage{
3223 max-width: 300px ;
3224 box-shadow: 3px 3px 3px #808080 ;
3225 border: 1px solid black ;
3226 background:none ;
3227 padding:0 ;
3228 margin:.5ex ;
3229 border-radius: 10px ;
3230 }
3231
3232
3233 .section {
3234 /*
3235 To have each section float relative to each other:
3236 */
3237 /*
3238 display: block ;
3239 float: left ;
3240 position: relative ;
3241 background: white ;
3242 border: 1px solid silver ;
3243 padding: .5em ;
3244 */
3245 margin: 0ex .5em 0ex .5em ;
3246 padding: 0 ;
3247 }
3248
3249
3250 figure {
3251 margin: 5ex auto 5ex auto ;
3252 padding: 1ex 1em 1ex 1em ;
3253 overflow-x: auto ;
3254 }
3255
3256
3257 /* To automatically center images in figures: */
3258 /*
3259 figure img.inlineimage {
3260 margin: 0ex auto 0ex auto ;
3261 display: block ;
3262 }
3263 */
3264
3265 /* To automatically center minipages in figures: */
3266 /*
3267 figure div.minipage, figure div.minipage div.minipage {
```

```
3268 margin: 1ex auto 1ex auto ;
3269 display: block ;
3270 }
3271 */
3272
3273 figure figure { margin: 0pt }
3274
3275 figure div.minipage p { font-size: 85% ; }
3276
3277 figure.subfigure, figure.subtable {
3278 display: inline-block ; margin: 3ex 1em 3ex 1em ;
3279 }
3280
3281 div.figurecaption .minipage { margin:0 ; padding: 0 }
3282
3283 /* for subcaptions: */
3284 figure div.minipage div.figurecaption {
3285 max-width: 100% ; /* fallback if min() does not work */
3286 max-width: min(30em,100%)
3287 }
3288
3289 div.minipage figure { border: none ; box-shadow: none ; }
3290 div.minipage figure.table { margin: 0ex }
3291 div.minipage div.footnotes { margin: 1ex 2em 0ex 2em }
3292
3293 div.floatrow { text-align: center ; }
3294
3295 div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }
3296
3297 div.floatfoot { font-size: .85em ;
3298 border-top: 1px solid silver ; line-height: 1.2 ; }
3299
3300 /* Center if only one line, "start" align if more than one line: */
3301 div.figurecaption , .lstlistingtitle {
3302 font-size: .85em ;
3303 font-weight: bold ;
3304 text-align: start ;
3305 margin: 1ex auto ;
3306 width: max-content ;
3307 max-width: 100% ;
3308 }
3309
3310 /* A marginblock is small, so always center and don't mess with the width. */
3311 div.marginblock div.figurecaption {
3312 width: 100% ;
3313 text-align: center ;
3314 }
3315
3316 figure.subfigure div.figurecaption, figure.subtable div.figurecaption {
3317 border-bottom: none ; background: none ;
3318 }
3319
3320 div.nonfloatcaption {
3321 margin: 1ex auto 1ex auto ;
3322 font-size: .85em ;
3323 text-align: center ;
3324 font-weight: bold ;
3325 }
3326
3327 /* For a \RawCaption inside a minipage inside a figure's floatrow: */
```

```
3328 figure div.floatrow div.minipage div.figurecaption {
3329 border: none ;
3330 background: none ;
3331 }
3332
3333
3334 /* For packages such as float, rotfloat, and algorithm2e: */
3335
3336 figure.boxed, figure.boxruled {
3337 border: 1px solid black ;
3338 }
3339
3340 figure.ruled {
3341 border-top: 1px solid black ;
3342 border-bottom: 1px solid black ;
3343 border-left: 0px ;
3344 border-right: 0px ;
3345 border-radius: 0px ;
3346 background: none ;
3347 box-shadow: none ;
3348 }
3349
3350 figure.ruled div.figurecaption, figure.boxruled div.figurecaption {
3351 border-top: 1px solid silver ;
3352 border-bottom: 1px solid silver ;
3353 }
3354
3355
3356 table {
3357 margin: 1ex auto 1ex auto ;
3358 border-collapse: separate ;
3359 border-spacing: 0px ;
3360 line-height: 1.3 ;
3361 }
3362
3363 table > tbody > tr.hline > td {border-top: 1px solid #808080 ; margin-top: 0ex ;
3364 margin-bottom: 0ex ; } /* for \hline */
3365
3366 tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;
3367 margin-bottom: 0ex ; } /* for \toprule, \bottomrule */
3368
3369 td {padding: .5ex .5em .5ex .5em ;}
3370
3371 table td.tdl { text-align: left ; vertical-align: middle ; }
3372 table td.tdc { text-align: center ; vertical-align: middle ; }
3373 table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }
3374 table td.tdbang { text-align: center ; vertical-align: middle ; }
3375 table td.tdr { text-align: right ; vertical-align: middle ; }
3376 table td.tdp { text-align: left ; vertical-align: bottom ; }
3377 table td.tdm { text-align: left ; vertical-align: middle ; }
3378 table td.tdb { text-align: left ; vertical-align: top ; }
3379
3380 table td.tvertbarl { border-left: 1px solid black }
3381 table td.tvertbardouble { border-left: 4px double black }
3382 table td.tvertbarr { border-right: 1px solid black }
3383 table td.tvertbarrdouble { border-right: 4px double black }
3384
3385 table td.tvertbardash { border-left: 1px dashed black }
3386 table td.tvertbardoubledash { border-left: 2px dashed black }
3387 table td.tvertbarrdash { border-right: 1px dashed black }
```

```
3388 table td.tvertbarrdoubledash { border-right: 2px dashed black }
3389
3390 table td.tdcenter { text-align: center}
3391 table td.tdleft { text-align: left}
3392 table td.tdright { text-align: right}
3393
3394
3395 /* for cmidrules: */
3396 table td.tdrule {
3397 border-top: 1px solid #A0A0A0 ;
3398 }
3399
3400 table td.tdrulel {
3401 border-top-left-radius:.5em ;
3402 border-top: 1px solid #A0A0A0 ;
3403 }
3404
3405 table td.tdruler {
3406 border-top-right-radius:.5em ;
3407 border-top: 1px solid #A0A0A0 ;
3408 }
3409
3410 table td.tdrulelr {
3411 border-top-left-radius:.5em ;
3412 border-top-right-radius:.5em ;
3413 border-top: 1px solid #A0A0A0 ;
3414 }
3415
3416
3417 /* Margins of paragraphs inside table cells: */
3418 td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
3419 padding-bottom: 1ex ; margin: 0ex ; }
3420 td.tdm p , td.tdmrule p , td.tdM p , td.tdMrule p { padding-top: 1ex ;
3421 padding-bottom: 1ex ; margin: 0ex ; }
3422 td.tdb p , td.tdbrule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
3423 padding-bottom: 1ex ; margin: 0ex ; }
3424
3425 td.tdp , td.tdprule , td.tdP , td.tdPrule
3426 { padding: 0ex .5em 0ex .5em ; }
3427 td.tdm , td.tdmrule , td.tdM , td.tdMrule
3428 { padding: 0ex .5em 0ex .5em ; }
3429 td.tdb , td.tdbrule , td.tdB , td.tdBrule
3430 { padding: 0ex .5em 0ex .5em ; }
3431
3432
3433 /* table notes: */
3434 .tnotes {
3435 margin: 0ex 5% 1ex 5% ;
3436 padding: 0.5ex 1em 0.5ex 1em;
3437 font-size:.80em;
3438 text-align: left ;
3439 }
3440
3441 .minipage .tnotes {
3442 margin: 0pt ;
3443 padding: 0pt ;
3444 }
3445
3446 .tnotes dl dt p {margin-bottom:0px;}
3447
```

```
3448 .tnoteitemheader {margin-right: 1em;}
3449
3450
3451 /* for colortbl and cell color */
3452 div.cellcolor {
3453 width: 100% ;
3454 padding: .5ex .5em .5ex .5em ;
3455 margin: -.5ex -.5em -.5ex -.5em ;
3456 }
3457
3458
3459 /* for lyluatex */
3460 span.lyluatex {
3461 display: inline-block ;
3462 }
3463
3464 div.lyluatex p span.lateximagesource img {
3465 display: block ;
3466 margin-top: 3ex ;
3467 margin-bottom: 3ex ;
3468 }
3469
3470
3471 /* for bigdelim */
3472 .ldelim, .rdelim { font-size: 200% }
3473
3474
3475 /* center, flushleft, flushright environments */
3476 div.center{text-align:center;}
3477 div.center table {margin-left:auto;margin-right:auto;}
3478 div.flushleft{text-align:left;}
3479 div.flushleft table {margin-left:0em ; margin-right:auto;}
3480 div.flushright{text-align:right;}
3481 div.flushright table {margin-left:auto ; margin-right: 0em ;}
3482
3483
3484 /* Fancybox */
3485 div.Btrivlist table tr td {
3486 padding: .2ex 0em ;
3487 }
3488
3489
3490 /* program listing callouts: */
3491 span.callout {
3492 font-family: "DejaVu Sans", "Bitstream Vera Sans",
3493 Geneva, Verdana, sans-serif ;
3494 border-radius: .5em;
3495 background-color:black;
3496 color:white;
3497 padding:0px .25em 0px .25em;
3498 margin: 0 ;
3499 font-weight: bold;
3500 font-size:.72em ;
3501 }
3502
3503 div.programlisting pre.verbatim span.callout{
3504 font-size: .85em ;
3505 }
3506
3507 span.verbatim {
```

```
3508 font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
3509 "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
3510 "Courier New", monospace;
3511 }
3512
3513
3514
3515 div.titlehead
3516 {
3517 text-align: left ;
3518 font-style: normal ;
3519 font-weight: normal ;
3520 font-style: normal ;
3521 font-size: .8em ;
3522 margin: 1ex 0em 1ex 0em ;
3523 }
3524
3525 div.subject
3526 {
3527 text-align: center ;
3528 font-style: normal ;
3529 font-weight: bold ;
3530 font-style: normal ;
3531 font-size: .8em ;
3532 margin: 1ex 0em 1ex 0em ;
3533 }
3534
3535 div.published
3536 {
3537 text-align: center ;
3538 font-variant: normal ;
3539 font-style: italic ;
3540 font-size: 1em ;
3541 margin: 1ex 0em 1ex 0em ;
3542 }
3543
3544 div.subtitle
3545 {
3546 text-align: center ;
3547 font-variant: normal ;
3548 font-style: italic ;
3549 font-size: 1.25em ;
3550 margin: 1ex 0em 1ex 0em ;
3551 }
3552
3553 div.subtitle p { margin: 1ex ; }
3554
3555 div.author
3556 {
3557 text-align: center ;
3558 font-variant: normal ;
3559 font-style: normal ;
3560 font-size: 1em ;
3561 margin: 1ex 0em 1ex 0em ;
3562 }
3563
3564 div.oneauthor {
3565 display: inline-block ;
3566 margin: 0ex 1em 0ex 1em ;
3567 }
```

```
3568
3569 /*
3570 div.author table {
3571 margin: 1ex auto 0ex auto ;
3572 background: none ;
3573 }
3574
3575 div.author table tbody tr td { padding: .25ex ; }
3576 */
3577
3578 span.affiliation {font-size: .85em ; font-variant: small-caps; }
3579
3580 div.titledate {
3581 text-align: center ;
3582 font-size: .85em ;
3583 font-style: italic;
3584 margin: 1ex 0em 1ex 0em ;
3585 }
3586
3587
3588 nav.topnavigation{
3589 text-align: left ;
3590 padding: 0.5ex 1em 0.5ex 1em ;
3591 /* margin: 2ex 0em 3ex 0em ; */
3592 margin: 0 ;
3593 border-bottom: 1px solid silver ;
3594 border-top: 1px solid silver ;
3595 clear:both ;
3596 }
3597
3598 nav.botnavigation{
3599 text-align: left ;
3600 padding: 0.5ex 1em 0.5ex 1em ;
3601 /* margin: 3ex 0em 2ex 0em ; */
3602 margin: 0 ;
3603 border-top: 1px solid silver ;
3604 border-bottom: 1px solid silver ;
3605 clear:both ;
3606 }
3607
3608
3609 header {
3610 line-height: 1.2 ;
3611 font-size: 1em ;
3612 border-bottom: 1px solid silver ;
3613 margin: 0px ;
3614 padding: 2ex 1em 2ex 1em ;
3615 text-align:left ;
3616 }
3617
3618
3619 footer {
3620 font-size: .85em ;
3621 line-height: 1.2 ;
3622 margin-top: 1ex ;
3623 border-top: 1px solid silver ;
3624 padding: 2ex 1em 2ex 1em ;
3625 clear:both ;
3626 text-align:left ;
3627 }
```

```
3628
3629
3630 /* for \LinkHome, \LinkPrevious, and \LinkNext: */
3631 a.linkhome { font-weight:bold ; font-size: 1em ;}
3632
3633
3634 div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }
3635
3636 img.lateximage{
3637 padding: 0pt ;
3638 margin: 0pt ;
3639 box-shadow: none ;
3640 border: none ;
3641 background: none ;
3642 max-width: 100% ;
3643 border-radius: 0ex ;
3644 border: none ;
3645 }
3646
3647
3648 div.sidetoccontainer {
3649 font-family: "DejaVu Serif", "Bitstream Vera Serif",
3650 "Lucida Bright", Georgia, serif;
3651 float: left ;
3652 width: 19%; /* room for border-right next to 80% main */
3653 margin: 0pt 0em 3ex 0pt ;
3654 border-right: 1px solid silver;
3655 border-bottom: 1px solid silver;
3656 background: #FAF7F4 ;
3657 font-size:.9em ;
3658 border-radius: 0px 0px 20px 0px ;
3659 }
3660
3661 div.sidetoccontents {
3662 overflow-y: auto ;
3663 width: 100% ;
3664 text-align: left ;
3665 }
3666
3667
3668 nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;
3669 text-indent: 0 ; }
3670
3671 nav.sidetoc p a {color:black ; font-size: .7em ;}
3672
3673 div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;
3674 border-bottom: 1px solid silver ; }
3675
3676 nav.sidetoc a:hover {text-decoration: underline ; }
3677
3678
3679
3680 section.textbody { margin: 0ex 1em 0ex 1em ;}
3681
3682
3683 div.multicolshheading { -webkit-column-span: all;
3684 -moz-column-span: all; column-span: all; }
3685 div.multicols {
3686 -webkit-columns: 3 auto ;
3687 -moz-columns: 3 auto ;
```

```
3688 columns: 3 auto ;
3689 }
3690 div.multicols p {margin-top: 0ex}
3691
3692
3693 /* Used for xfrac and nicefrac: */
3694 span.numerator {
3695 font-size: 60% ;
3696 vertical-align: .4em ;
3697 }
3698
3699 span.denominator {
3700 font-size: 60%
3701 }
3702
3703
3704 /* Used for algorithm2e: */
3705 div.alg2evline{
3706 margin-left: 1em ;
3707 padding-left: 1em ;
3708 border-left: 1px solid black ;
3709 border-radius: 0px 0px 0px 1ex ;
3710 }
3711
3712 div.alg2evsline{
3713 margin-left: 1em ;
3714 padding-left: 1em ;
3715 border-left: 1px solid black ;
3716 }
3717
3718 div.alg2enoline{
3719 margin-left: 1em ;
3720 padding-left: 1em ;
3721 }
3722
3723 span.alg2elinenumber{
3724 margin-right: .5em ;
3725 font-size: 60% ;
3726 color: red ;
3727 }
3728
3729
3730 /* Used for algorithmicx: */
3731 span.floatright { float: right ; }
3732
3733
3734 /* keyfloat and tocdata: */
3735 .floatnotes {
3736 margin: 0ex 5% 0ex 5% ;
3737 padding: 0ex 1em 0ex 1em ;
3738 font-size: .80em ;
3739 text-align: left ;
3740 }
3741
3742 .authorartist{
3743 display:block ;
3744 font-size:.70em ;
3745 font-style: italic;
3746 }
3747
```

```
3748 nav .authorartist{ display:inline; }
3749
3750
3751
3752 /* Native LaTeX theorems: */
3753
3754 .theoremcontents {
3755 font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ;
3756 }
3757
3758 .theoremlabel {
3759 font-style: normal; font-weight: bold ; margin-right: .5em ;
3760 }
3761
3762
3763
3764 /* theorem, amsthm, and ntheorem packages */
3765
3766 span.theoremheader,
3767 span.theoremheaderplain,
3768 span.theoremheaderdefinition,
3769 span.theoremheaderbreak,
3770 span.theoremheadermarginbreak,
3771 span.theoremheaderchangebreak,
3772 span.theoremheaderchange,
3773 span.theoremheadermargin
3774 {
3775 font-style:normal ; font-weight: bold ; margin-right: 1em ;
3776 }
3777
3778 span.amsthmnameplain,
3779 span.amsthmnamedefinition,
3780 span.amsthmnumberplain,
3781 span.amsthmnumberdefinition
3782 {
3783 font-style:normal ; font-weight: bold ;
3784 }
3785
3786
3787 span.amsthmnameremark,
3788 span.amsthmnumberremark
3789 {font-style:italic ; font-weight: normal ; }
3790
3791
3792 span.amsthmnoteplain,
3793 span.amsthmnotedefinition
3794 {font-style:normal ;}
3795
3796
3797 span.theoremheaderremark,
3798 span.theoremheaderproof,
3799 span.amsthmproofname
3800 {font-style:italic ; font-weight: normal ; margin-right: 1em ; }
3801
3802 span.theoremheadersc
3803 {
3804 font-style:normal ;
3805 font-variant: small-caps ;
3806 font-weight: normal ;
3807 margin-right: 1em ;
```

```
3808 }
3809
3810 .theoremdemark {float:right}
3811
3812 div.amsthbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
3813 div.theorembodybreak, div.theorembodynonumberbreak,
3814 div.theorembodymarginbreak,
3815 div.theorembodychangebreak,
3816 div.theorembodychange,
3817 div.theorembodymargin
3818 {
3819 font-style:italic;
3820 margin-top: 3ex ; margin-bottom: 3ex ;
3821 }
3822
3823 div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
3824 div.theorembodyplainupright, nonumberplainuprightsc,
3825 div.amsthbodydefinition, div.amsthbodyremark,
3826 div.amsthproof
3827 {
3828 font-style: normal ;
3829 margin-top: 3ex ; margin-bottom: 3ex ;
3830 }
3831
3832 span.amsthmnoteremark {}
3833
3834
3835 /* thmbox */
3836
3837 .thmbox {
3838 font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ;
3839 border: 1px solid gray ;
3840 padding: 1ex ;
3841 }
3842
3843 .thmboxtitle {
3844 font-style: normal; font-weight: bold ; margin-right: .5em ;
3845 border-bottom: 1px solid gray ;
3846 }
3847
3848 span.thmboxproofname, span.thmboxexemplename {
3849 font-weight: bold ;
3850 }
3851
3852 div.thmboxproof, div.thmboxexample {
3853 font-size: 0.85em ;
3854 margin: 2ex ;
3855 }
3856
3857 div.thmboxleftbar {
3858 border-left: 2px solid black ;
3859 padding-left: 1em ;
3860 }
3861
3862
3863
3864 /* For the backnaur package: */
3865 div.backnaur {
3866 display: block ;
3867 margin: 2ex 2em 2ex 2em ;
```

```
3868 }
3869
3870 div.backnaur p {
3871 margin: .25ex 0ex .25ex 0ex ;
3872 }
3873
3874 div.backnaurprod {
3875 display: inline-block ;
3876 min-width: 8em ;
3877 text-align:right ;
3878 }
3879
3880 div.backnaurdsc {
3881 display: inline-block ;
3882 }
3883
3884
3885 /* For the notes package: */
3886 div.notesimportantnote, div.noteswarningnote, div.notesinformationnote {
3887 clear: both ;
3888 margin: 2ex 2em 2ex 2em ;
3889 border: 1px solid silver ;
3890 }
3891
3892 div.notesicon {
3893 float:left ;
3894 display: inline-block ;
3895 background: gold ;
3896 padding: 0ex 1em 0ex 1em ;
3897 margin-right: 1em ;
3898 font-weight: bold ;
3899 }
3900
3901 div.notescontents { font-style: italic }
3902
3903
3904 /* nolbreaks package: */
3905 span.nolbreaks { white-space: nowrap ; }
3906
3907
3908 /*
3909 For CSS LaTeX and related logos:
3910 Based on spacing demonstrated by the metafont package.
3911
3912 The subscripts are shrunk instead of lowered below the baseline,
3913 to avoid browser rendering errors with the line height in lists, etc.
3914 */
3915
3916 .latexlogofont {
3917 font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3918 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3919 font-variant: normal ;
3920 }
3921
3922 .latexlogo {
3923 font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3924 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3925 }
3926
3927 .latexlogosup {
```

```
3928 text-transform: uppercase;
3929 letter-spacing: .03em ;
3930 font-size: 0.7em;
3931 vertical-align: 0.25em;
3932 margin-left: -0.4em;
3933 margin-right: -0.15em;
3934 }
3935
3936 .latexlogosub {
3937 text-transform: uppercase;
3938 /* vertical-align: -0.27ex; */
3939 margin-left: -0.08em;
3940 margin-right: -0.07em;
3941 /* font-size: 1em; */
3942 font-size: .7em ;
3943 }
3944
3945 .latexlogotwoe {
3946 text-transform: none ;
3947 font-variant-numeric: oldstyle-nums ;
3948 }
3949
3950 .latexlogotwoesub {
3951 font-style:italic ;
3952 /* vertical-align: -0.27ex; */
3953 margin-left: -0.11em;
3954 margin-right: -0.1em;
3955 /* font-size: 1em; */
3956 font-size: .7em ;
3957 }
3958
3959 .xelatexlogo {
3960 font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3961 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3962 letter-spacing: .03em ;
3963 }
3964
3965 .xelatexlogosub {
3966 /* vertical-align: -0.27ex; */
3967 margin-left: -0.0667em;
3968 margin-right: -.05em;
3969 /* font-size: 1em; */
3970 font-size: .7em ;
3971 letter-spacing: .03em ;
3972 }
3973
3974 .amslogo {
3975 font-family: "TeXGyreChorus", "URW Chancery L",
3976 "Apple Chancery", "ITC Zapf Chancery", "Monotype Corsiva",
3977 "Linux Libertine O", "Nimbus Roman No 9 L", "FreeSerif",
3978 "Hoefler Text", Times, "Times New Roman", serif ;
3979 font-style: italic ;
3980 }
3981
3982 .lyxlogo {
3983 font-family: "URW Classico", Optima, "Linux Biolinum O",
3984 "DejaVu Sans", "Bitstream Vera Sans", Geneva,
3985 Verdana, sans-serif ;
3986 }
3987
```

```
3988
3989 /* Only display top and bottom navigation if a small screen: */
3990 /* Hide the sidetoc if a small screen: */
3991 nav.topnavigation { display:none; }
3992 nav.botnavigation { display:none; }
3993
3994 /* Only display the sidetoc's webpage title if a small screen */
3995 span.sidetocthetitle { display: none }
3996
3997 @media screen and (max-width: 100em) {
3998 div.multicols {
3999 -webkit-columns: 2 auto ;
4000 -moz-columns: 2 auto ;
4001 columns: 2 auto ;
4002 }
4003 }
4004
4005 @media screen and (max-width: 50em) {
4006 div.sidetoccontainer {
4007 float: none ;
4008 width: 100% ;
4009 padding: 0 ;
4010 border-radius: 0 ;
4011 border-bottom: 1px solid black ;
4012 border-top: 1px solid black ;
4013 box-shadow: none ;
4014 }
4015 span.sidetocthetitle { display: inline }
4016 nav.topnavigation { display:block }
4017 nav.botnavigation { display:block }
4018 main.bodycontainer { width: 100% }
4019 .marginpar {
4020 max-width: 100%;
4021 float: none;
4022 display:block ;
4023 margin: 1ex 1em 1ex 1em ;
4024 }
4025 div.multicols {
4026 -webkit-columns: 1 auto ;
4027 -moz-columns: 1 auto ;
4028 columns: 1 auto ;
4029 }
4030 }
4031
4032 @media print {
4033 body {
4034 font-family: "Linux Libertine O",
4035 "DejaVu Serif", "Bitstream Vera Serif",
4036 "Liberation Serif", "Nimbus Roman No 9 L",
4037 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
4038 }
4039 div.sidetoccontainer { display:none; }
4040 nav.topnavigation { display: none; }
4041 nav.botnavigation { display: none; }
4042 main.bodycontainer { width: 100% }
4043 }
4044
4045 @media handheld {
4046 div.sidetoccontainer { display:none; }
4047 nav.topnavigation { display:block }
```

```

4048 nav.botnavigation { display:block }
4049 main.bodycontainer { width: 100% }
4050 }
4051
4052 @media projection {
4053 div.sidetoccontainer { display:none; }
4054 nav.topnavigation { display:block }
4055 nav.botnavigation { display:block }
4056 main.bodycontainer { width: 100% }
4057 }
4058 \end{filecontents*}
4059 % \end{Verbatim}% for syntax highlighting
4060 \end{LWRwriteconf}

```

## 40.5 lwarp\_sagebrush.css

File lwarp\_sagebrush.css

An optional CSS which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

```

Config file: 4061 \begin{LWRwriteconf}
4062 \begin{filecontents*}[overwrite]{lwarp_sagebrush.css}
4063 @import url("lwarp.css") ;
4064
4065
4066 A:link {color:#105030 ; text-decoration: none ; }
4067 A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}
4068 A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}
4069 A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}
4070
4071
4072
4073 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
4074 {
4075 font-family: "URW Classico", Optima, "Linux Biolinum 0",
4076 "Linux Libertine 0", "Liberation Serif",
4077 "Nimbus Roman No 9 L", "FreeSerif",
4078 "Hoefler Text", Times, "Times New Roman", serif;
4079 font-variant: small-caps ;
4080 font-weight: normal ;
4081 color: #304070 ;
4082 text-shadow: 2px 2px 3px #808080;
4083 }
4084
4085 h1 { /* title of the entire website, used on each page */
4086 font-variant: small-caps ;
4087 color: #304070 ;
4088 text-shadow: 2px 2px 3px #808080;
4089 background-color: #F7F7F0 ;
4090 background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);
4091 }
4092
4093 h1 {
4094 border-bottom: 1px solid #304070;
4095 /* border-top: 2px solid #304070; */
4096 }
4097

```

```
4098 h2 {
4099 border-bottom: 1px solid #304070;
4100 /* border-top: 2px solid #304070; */
4101 background-color: #F7F7F0 ;
4102 background-image: linear-gradient(to bottom, #F7F7F0, #DAD0C0);
4103 }
4104
4105
4106
4107 div.abstract {
4108 background: #f5f5eb ;
4109 background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
4110
4111 border: 1px solid silver;
4112 border-radius: 1em ;
4113 }
4114
4115 div.abstract dl {line-height:1.5;}
4116 div.abstract dt {color:#304070;}
4117
4118 div.abstracttitle{
4119 font-family: "URW Classico", Optima, "Linux Biolinum O",
4120 "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
4121 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
4122 font-weight:bold;
4123 font-variant: small-caps ;
4124 font-size:1.5em;
4125 border-bottom: 1px solid silver ;
4126 color: #304070 ;
4127 text-align: center ;
4128 text-shadow: 1px 1px 2px #808080;
4129 }
4130
4131 span.abstracrunintitle{
4132 font-family: "URW Classico", Optima, "Linux Biolinum O",
4133 "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
4134 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
4135 font-weight:bold;
4136 }
4137
4138
4139 div.epigraph, div.dictum {
4140 background: #f5f5eb ;
4141 background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
4142
4143 border: 1px solid silver ;
4144 border-radius: 1ex ;
4145 box-shadow: 3px 3px 3px #808080 ;
4146 }
4147
4148
4149 .example {
4150 background-color: #f5f5eb ;
4151 background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
4152
4153 }
4154
4155 div.exampletitle{
4156 font-family: "URW Classico", Optima, "Linux Biolinum O",
4157 "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
```

```
4158 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
4159 font-weight:bold;
4160 font-variant: small-caps ;
4161 border-bottom: 1px solid silver ;
4162 color: #304070 ;
4163 text-align: center ;
4164 text-shadow: 1px 1px 2px #808080;
4165 }
4166
4167
4168 .sidebar {
4169 background-color: #f5f5eb ;
4170 background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
4171
4172 }
4173
4174 div.sidebar{
4175 font-family: "URW Classico", Optima, "Linux Biolinum O",
4176 "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
4177 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
4178 font-weight:bold;
4179 font-variant: small-caps ;
4180 border-bottom: 1px solid silver ;
4181 color: #304070 ;
4182 text-align: center ;
4183 text-shadow: 1px 1px 2px #808080;
4184 }
4185
4186
4187 .fancyvrblabel {
4188 font-family: "URW Classico", Optima, "Linux Biolinum O",
4189 "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
4190 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
4191 font-weight:bold;
4192 font-variant: small-caps ;
4193 font-size: 1.5em ;
4194 color: #304070 ;
4195 text-align: center ;
4196 text-shadow: 1px 1px 2px #808080;
4197 }
4198
4199 div.minipage {
4200 background-color: #eeeeee7 ;
4201 border: 1px solid silver ;
4202 border-radius: 1ex ;
4203 }
4204
4205 table div.minipage { background: none ; border: none ; }
4206
4207 div.framebox div.minipage {border:none ; background:none}
4208
4209 section.textbody > div.minipage {
4210 box-shadow: 3px 3px 3px #808080 ;
4211 }
4212
4213 div.fboxBlock div.minipage { box-shadow: none ; }
4214
4215 .framed .minipage , .framedleftbar .minipage {
4216 border: none ;
4217 background: none ;
```

```
4218 padding: 0ex ;
4219 margin: 0ex ;
4220 }
4221
4222 figure.figure .minipage, div.figurecaption .minipage { border: none; }
4223
4224 div.marginblock div.minipage ,
4225 div.marginparblock div.minipage
4226 { border: none; }
4227
4228 figure , div.marginblock {
4229 background-color: #eeeeee7 ;
4230 border: 1px solid silver ;
4231 border-radius: 1ex ;
4232 box-shadow: 3px 3px 3px #808080 ;
4233 }
4234
4235 figure figure {
4236 border: 1px solid silver ;
4237 margin: 0em ;
4238 box-shadow: none ;
4239 }
4240
4241 /*
4242 div.figurecaption {
4243 border-top: 1px solid silver ;
4244 border-bottom: 1px solid silver ;
4245 background-color: #e8e8e8 ;
4246 }
4247 */
4248
4249
4250 div.table {
4251 box-shadow: 3px 3px 3px #808080 ;
4252 }
4253
4254 /*
4255 .tnotes {
4256 background: #e8e8e8;
4257 border: 1px solid silver;
4258 }
4259 */
4260
4261
4262 nav.topnavigation{
4263 background-color: #b0b8b0 ;
4264 background-image: linear-gradient(to bottom,#e0e0e0,#b0b8b0) ;
4265 }
4266
4267 nav.botnavigation{
4268 background-color: #b0b8b0 ;
4269 background-image: linear-gradient(to top,#e0e0e0,#b0b8b0) ;
4270 }
4271
4272
4273
4274 header{
4275 background-color: #F7F7F0 ;
4276 background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
4277 }
```

```

4278
4279 footer{
4280 background-color: #F7F7F0 ;
4281 background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
4282 }
4283
4284
4285
4286 div.sidetoccontainer {
4287 background-color: #F7F7F0 ;
4288 background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
4289 box-shadow: 3px 3px 3px #808080 ;
4290 }
4291
4292 div.sidetocitle {color: #304070 ; }
4293
4294 nav.sidetoc a:hover {
4295 color:#006000 ;
4296 text-decoration: none ;
4297 text-shadow:0px 0px 2px #a0a0a0;
4298 }
4299
4300
4301 @media screen and (max-width: 45em) {
4302 div.sidetoccontainer { border-radius: 0 ; }
4303 }
4304
4305
4306 \end{filecontents*}
4307 % \end{Verbatim}% for syntax highlighting
4308 \end{LWRwriteconf}

```

## 40.6 lwarp\_formal.css

File lwarp\_formal.css

An optional css which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

**Config file:**

```

4309 \begin{LWRwriteconf}
4310 \begin{filecontents*}[overwrite]{lwarp_formal.css}
4311 @import url("lwarp.css") ;
4312
4313
4314
4315 A:link {color:#802020 ; text-decoration:none; }
4316 A:visited {color:#802020 ; text-shadow:none ;}
4317 A:hover {color:#400000 ; text-shadow:none ;}
4318 A:active {color:#C00000 ; text-shadow:none ;}
4319
4320
4321 body {
4322 font-family: "Linux Libertine 0", "Hoefler Text", "Garamond",
4323 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4324 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4325 "Times New Roman", serif;
4326 background: #fffcf5;
4327 }

```

```
4328
4329 span.textrm {
4330 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4331 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4332 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4333 "Times New Roman", serif;
4334 }
4335
4336 span.textsf {
4337 font-family: "DejaVu Sans", "Bitstream Vera Sans",
4338 Geneva, Verdana, sans-serif ;
4339 }
4340
4341
4342
4343 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
4344 {
4345 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4346 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4347 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4348 "Times New Roman", serif;
4349 color: #800000 ;
4350 text-shadow: none ;
4351 }
4352
4353 h1, h2 {
4354 background-color: #fffcf5 ;
4355 background-image: none ;
4356 border-bottom: 1px solid #808080;
4357 /* border-top: 2px solid #808080; */
4358 }
4359
4360 div.abstracttitle {
4361 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4362 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4363 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4364 "Times New Roman", serif;
4365 color: black ;
4366 text-shadow: none ;
4367 }
4368
4369 span.abstracrunintitle {
4370 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4371 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4372 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4373 "Times New Roman", serif;
4374 color: black ;
4375 text-shadow: none ;
4376 }
4377
4378 div.abstract { font-size: 100% }
4379
4380 .sidebar {
4381 background: #fffcf5;
4382 background-image: none ;
4383 margin: 2em 5% 2em 5%;
4384 padding: 0.5em 1em;
4385 border: none ;
4386 border-top : 1px solid silver;
4387 border-bottom : 1px solid silver;
```

```
4388 font-size: 90% ;
4389 }
4390
4391 div.sidebartitle{
4392 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4393 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4394 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4395 "Times New Roman", serif;
4396 color: #800000 ;
4397 text-shadow: none ;
4398 border: none ;
4399 }
4400
4401 .example {
4402 background: #fffcf5;
4403 background-image: none ;
4404 margin: 2em 5% 2em 5%;
4405 padding: 0.5em 1em;
4406 border: none ;
4407 border-top : 1px solid silver;
4408 border-bottom : 1px solid silver;
4409 }
4410
4411 div.exampletitle{
4412 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4413 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4414 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4415 "Times New Roman", serif;
4416 color: #800000 ;
4417 text-shadow: none ;
4418 border: none ;
4419 }
4420
4421 div.fancyvrblabel{
4422 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4423 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4424 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4425 "Times New Roman", serif;
4426 color: #800000 ;
4427 text-shadow: none ;
4428 border: none ;
4429 }
4430
4431
4432
4433 figure {
4434 margin: 5ex 5% 5ex 5% ;
4435 padding: 1ex 1em 1ex 1em ;
4436 background-color: #fffcf5 ;
4437 overflow-x: auto ;
4438 border: none ;
4439 /* border-top: 1px solid silver; */
4440 /* border-bottom: 1px solid silver; */
4441 }
4442
4443
4444 div.figurecaption , .lstlisting {
4445 border: none ;
4446 /* border-top: 1px solid silver ; */
4447 /* border-bottom: 1px solid silver ; */
```

```
4448 background-color: #fffcf5 ;
4449 }
4450
4451 .tnotes {
4452 background: #fffcf5 ;
4453 border-top: 1px solid silver ;
4454 border-bottom: 1px solid silver ;
4455 }
4456
4457 .theorem {
4458 background: none ;
4459 }
4460
4461 .minipage {
4462 background-color: #fffcf5 ;
4463 border: none ;
4464 }
4465
4466 div.floatrow figure { border: none ; }
4467
4468 figure figure { border: none ; }
4469
4470
4471 nav.toc, nav.lof, nav.lot, nav.lol {
4472 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4473 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4474 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4475 "Times New Roman", serif;
4476 }
4477
4478 div.sidetoccontainer {
4479 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4480 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4481 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4482 "Times New Roman", serif;
4483 background-image: linear-gradient(to bottom, #fffcf5, #C0C0C0);
4484 }
4485
4486 div.sidetocctitle{
4487 color: #800000 ;
4488 }
4489
4490 header{
4491 background-color: #e0e0e0 ;
4492 background-image: linear-gradient(to top, #fffcf5, #b0b0b0);
4493 text-align:center ;
4494 }
4495
4496 footer{
4497 background-color: #e0e0e0 ;
4498 background-image: linear-gradient(to bottom, #fffcf5, #b0b0b0);
4499 padding: 2ex 1em 2ex 1em ;
4500 text-align:left ;
4501 }
4502
4503 nav.botnavigation {
4504 background: #dedcd5 ;
4505 border-top: 1px solid black ;
4506 }
4507 \end{filecontents*}
```

```
4508 % \end{Verbatim}% for syntax highlighting
4509 \end{LWRwriteconf}
```

## 40.7 sample\_project.css

File sample\_project.css

The project-specific CSS file. Use with \CSSFilename.

If used, this must be present both when compiling the project and also when distributing the HTML files.

**Config file:**

```
4510 \begin{LWRwriteconf}
4511 \begin{filecontents*}[overwrite]{sample_project.css}
4512 /* (--- Start of project.css ---) */
4513 /* (--- A sample project-specific CSS file for lwarp ---) */
4514
4515 /* Uncomment one of the following: */
4516 @import url("lwarp.css") ;
4517 /* @import url("lwarp_formal.css") ; */
4518 /* @import url("lwarp_sagebrush.css") ; */
4519
4520 /* Project-specific CSS setting follow here. */
4521 /* . . . */
4522
4523 /* (--- End of project.css ---) */
4524 \end{filecontents*}
4525 % \end{Verbatim}% for syntax highlighting
4526 \end{LWRwriteconf}
```

## 40.8 lwarp.ist

File lwarp.ist

Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The page compositor line is for memoir's \specialindex.

**Config file:**

```
4527 \begin{LWRwriteconf}
4528 \begin{filecontents*}[overwrite]{lwarp.ist}
4529 preamble
4530 "\begin{theindex}
4531 \providecommand*\lettergroupDefault[1]{}
4532 \providecommand*\lettergroup[1]{%
4533 \par\textbf{#1}\par
4534 \nopagebreak
4535 }
4536 "
4537 headings_flag 1
4538 heading_prefix "
4539 \lettergroup{"
4540 heading_suffix "}"
4541 delim_0 ", \hyperindexref{"
4542 delim_1 ", \hyperindexref{"
4543 delim_2 ", \hyperindexref{"
4544 delim_n "}, \hyperindexref{"
4545 delim_r "} -- \hyperindexref{"
4546 delim_t "}"
```

```

4547 page_compositor ". "
4548 \end{filecontents*}
4549 % \end{Verbatim}% for syntax highlighting
4550 \end{LWRwriteconf}

```

## 40.9 lwarp.xdy

File lwarp.xdy

Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

See:

<https://tex.stackexchange.com/questions/80300/how-can-i-convince-hyperref-and-xindy-to-play-together-nicely>

**Config file:**

```

4551 \begin{LWRwriteconf}
4552 \begin{filecontents*}[overwrite]{lwarp.xdy}
4553 (require "tex/inputenc/latin.xdy")
4554 (merge-rule "\\PS *" "Postscript")
4555 (require "texindy.xdy")
4556 (require "page-ranges.xdy")
4557 (require "book-order.xdy")
4558 (define-location-class "arabic-page-numbers"
4559 ("arabic-numbers") :min-range-length 1)
4560 (require "makeindex.xdy")
4561 (define-attributes (("hyperindexref")))
4562 (markup-locref :open "\hyperindexref{" :close "}")
4563 (markup-locref :open "\hyperindexref{" :close "}" :attr "hyperpage")
4564 (markup-locref :open "\textbf{\hyperindexref{" :close "}" :attr "textbf")
4565 (markup-locref :open "\textit{\hyperindexref{" :close "}" :attr "textit")
4566 (define-location-class-order ("roman-page-numbers"
4567 "arabic-page-numbers"
4568 "alpha-page-numbers"
4569 "Roman-page-numbers"
4570 "Alpha-page-numbers"
4571 "see"
4572 "seealso"))
4573 \end{filecontents*}
4574 % \end{Verbatim}% for syntax highlighting
4575 \end{LWRwriteconf}

```

## 40.10 lwarp\_one\_limage.cmd

File lwarp\_one\_limage.cmd

Used by lwarp to help make lateximages when using WINDOWS.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The arguments are each of the three fields from <project>-images.txt, and also the base name of the source file.

*MiKTeX* does not allow file lwarp\_one\_limage.cmd to be created directly by *lwarpmk*, so lwarp\_one\_limage.txt is created instead, then copied to lwarp\_one\_limage.cmd by *lwarpmk*. This occurs each time *lwarpmk* used to create lateximages.

```

Config file: 4576 \begin{LWRwriteconf}
4577 \immediate\openout\LWR@quickfile=lwarp_one_limage.txt
4578 \immediate\write\LWR@quickfile{%
4579 pdfseparate -f \LWRpercent 1 -l \LWRpercent 1 \LWRpercent 4_html.pdf %
4580 \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent\LWRpercent d.pdf%
4581 }
4582 \immediate\write\LWR@quickfile{%
4583 pdfcrop --hires \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf %
4584 \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
4585 }
4586 \immediate\write\LWR@quickfile{%
4587 pdftocairo -svg -noshrink \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf %
4588 \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.svg%
4589 }
4590 \immediate\write\LWR@quickfile{%
4591 del \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
4592 }
4593 \immediate\write\LWR@quickfile{%
4594 del \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf%
4595 }
4596 \immediate\write\LWR@quickfile{exit}
4597 \immediate\closeout\LWR@quickfile
4598 \end{LWRwriteconf}

```

## 40.11 lwarp\_mathjax.txt

*(Emulates or patches code by DAVIDE P. CERVONE.)*

File lwarp\_mathjax.txt

The default MATHJAX script used by lwarp when using MATHJAX. A recent version of MATHJAX is used, as served by the recommended repository. Adjustments are made to allow L<sup>A</sup>T<sub>E</sub>X to control the equation tags and provide for starred macros.

\MathJaxFilename determines which script file is copied into the HTML pages, and defaults to lwarp\_mathjax.txt. The script files must be present when compiling the project, but do not need to be present when distributing the resulting HTML files.

**custom script** To generate a custom script, such as to use a local repository, copy lwarp\_mathjax.txt to a new file, make changes while keeping lwarp's adjustments for equation numbering and starred macros, and use \MathJaxFilename to select the new filename.

```

Config file: 4599 \begin{LWRwriteconf}
4600 \begin{filecontents*}[overwrite]{lwarp_mathjax.txt}
4601 <script>
4602 // Lwarp MathJax emulation code
4603 //
4604 // Based on code by Davide P. Cervone.
4605 // Equation numbering: https://github.com/mathjax/MathJax/issues/2427
4606 // Starred and ifnextchar macros: https://github.com/mathjax/MathJax/issues/2428
4607 // \left, \right delimiters: https://github.com/mathjax/MathJax/issues/2535
4608 //
4609 // Modified by Brian Dunn to adjust equation numbering and add subequations.
4610 //
4611 // LaTeX can use \seteqnumber{subequations?}{section}{number} before each equation.
4612 // subequations? is 0 usually, 1 if inside subequations.
4613 // section is a string printed as-is, or empty.
4614 // number is auto-incremented by MathJax between equations.
4615 //

```

```
4616 MathJax = {
4617 subequations: "0",
4618 section: "",
4619 loader: {
4620 load: ['[tex]/tagformat', '[tex]/textmacros'],
4621 },
4622 startup: {
4623 ready() {
4624 // These would be replaced by import commands if you wanted to make
4625 // a proper extension.
4626 const Configuration = MathJax._.input.tex.Configuration.Configuration;
4627 const CommandMap = MathJax._.input.tex.SymbolMap.CommandMap;
4628 const Macro = MathJax._.input.tex.Symbol.Macro;
4629 const TexError = MathJax._.input.tex.TexError.default;
4630 const ParseUtil = MathJax._.input.tex.ParseUtil.default;
4631 const expandable = MathJax._.util.Options.expandable;
4632
4633 // Insert the replacement string into the TeX string, and check
4634 // that there haven't been too many macro substitutions (prevents
4635 // infinite loops).
4636 const useArgument = (parser, text) => {
4637 parser.string = ParseUtil.addArgs(parser, text, parser.string.slice(parser.i));
4638 parser.i = 0;
4639 if (++parser.macroCount > parser.configuration.options.maxMacros) {
4640 throw new TexError('MaxMacroSub1',
4641 'MathJax maximum macro substitution count exceeded; ' +
4642 'is there a recursive macro call?');
4643 }
4644 }
4645
4646 // Create the command map for:
4647 // \ifstar, \ifnextchar, \ifblank, \ifstrequal, \gsub, \seteqnumber
4648 new CommandMap('Lwarp-macros', {
4649 ifstar: 'IfstarFunction',
4650 ifnextchar: 'IfnextcharFunction',
4651 ifblank: 'IfblankFunction',
4652 ifstrequal: 'IfstrequalFunction',
4653 gsubstitute: 'GsubstituteFunction',
4654 seteqnumber: 'SeteqnumberFunction'
4655 }, {
4656 // This function implements an ifstar macro.
4657 IfstarFunction(parser, name) {
4658 const resultstar = parser.GetArgument(name);
4659 const resultnostar = parser.GetArgument(name);
4660 const star = parser.GetStar(); // true if there is a *
4661 useArgument(parser, star ? resultstar : resultnostar);
4662 },
4663
4664 // This function implements an ifnextchar macro.
4665 IfnextcharFunction(parser, name) {
4666 let whichchar = parser.GetArgument(name);
4667 if (whichchar.match(/^(?:0x[0-9A-F]+|[0-9]+)$/i)) {
4668 // $ syntax highlighting
4669 whichchar = String.fromCharCode(parseInt(whichchar));
4670 }
4671 const resultnextchar = parser.GetArgument(name);
4672 const resultnotnextchar = parser.GetArgument(name);
4673 const gotchar = (parser.GetNext() === whichchar);
4674 useArgument(parser, gotchar ? resultnextchar : resultnotnextchar);
4675 },

```

```
4676
4677 // This function implements an ifblank macro.
4678 IfblankFunction(parser, name) {
4679 const blankarg = parser.GetArgument(name);
4680 const resultblank = parser.GetArgument(name);
4681 const resultnotblank = parser.GetArgument(name);
4682 const isblank = (blankarg.trim() == "");
4683 useArgument(parser, isblank ? resultblank : resultnotblank);
4684 },
4685
4686 // This function implements an ifstrequal macro.
4687 IfstrequalFunction(parser, name) {
4688 const strequalfirst = parser.GetArgument(name);
4689 const strequalsecond = parser.GetArgument(name);
4690 const resultequal = parser.GetArgument(name);
4691 const resultnotequal = parser.GetArgument(name);
4692 const isequal = (strequalfirst == strequalsecond);
4693 useArgument(parser, isequal ? resultequal : resultnotequal);
4694 },
4695
4696 // This function implements a gsub macro.
4697 GsubstituteFunction(parser, name) {
4698 const gsubfirst = parser.GetArgument(name);
4699 const gsubsecond = parser.GetArgument(name);
4700 const gsubthird = parser.GetArgument(name);
4701 let gsubresult=gsubfirst.replace(gsubsecond, gsubthird);
4702 useArgument(parser, gsubresult);
4703 },
4704
4705 // This function modifies the equation numbers.
4706 SeteqnumberFunction(parser, name) {
4707 // Get the macro parameters
4708 const star = parser.GetStar(); // true if there is a *
4709 const optBrackets = parser.GetBrackets(name); // contents of optional brackets
4710 const newsubequations = parser.GetArgument(name); // the subequations argument
4711 const neweqsection = parser.GetArgument(name); // the eq section argument
4712 const neweqnumber = parser.GetArgument(name); // the eq number argument
4713 MathJax.config.subequations=newsubequations; // a string with boolean meaning
4714 MathJax.config.section=neweqsection; // a string with numeric meaning
4715 parser.tags.counter = parser.tags.allCounter = neweqnumber;
4716 }
4717
4718 });
4719
4720 // Create the Lwarp-macros package
4721 Configuration.create('Lwarp-macros', {
4722 handler: {macro: ['Lwarp-macros']}
4723 });
4724
4725 MathJax.startup.defaultReady();
4726
4727 // For forward references:
4728 MathJax.startup.input[0].preFilters.add(({math}) => {
4729 if (math.inputData.recompile){
4730 MathJax.config.subequations = math.inputData.recompile.subequations;
4731 MathJax.config.section = math.inputData.recompile.section;
4732 }
4733 });
4734 MathJax.startup.input[0].postFilters.add(({math}) => {
4735 if (math.inputData.recompile){
```

```

4736 math.inputData.recompile.subequations = MathJax.config.subequations;
4737 math.inputData.recompile.section = MathJax.config.section;
4738 }
4739 });
4740
4741 // For \left, \right with unicode-math:
4742 const {DelimiterMap} = MathJax._.input.tex.SymbolMap;
4743 const {Symbol} = MathJax._.input.tex.Symbol;
4744 const {MapHandler} = MathJax._.input.tex.MapHandler;
4745 const delimiter = MapHandler.getMap('delimiter');
4746 delimiter.add('\lBrack', new Symbol('\lBrack', '\u27E6'));
4747 delimiter.add('\rBrack', new Symbol('\rBrack', '\u27E7'));
4748 delimiter.add('\lAngle', new Symbol('\lAngle', '\u27EA'));
4749 delimiter.add('\rAngle', new Symbol('\rAngle', '\u27EB'));
4750 delimiter.add('\lbrbrak', new Symbol('\lbrbrak', '\u2772'));
4751 delimiter.add('\rbrbrak', new Symbol('\rbrbrak', '\u2773'));
4752 delimiter.add('\lbag', new Symbol('\lbag', '\u27C5'));
4753 delimiter.add('\rbag', new Symbol('\rbag', '\u27C6'));
4754 delimiter.add('\llparenthesis', new Symbol('\llparenthesis', '\u2987'));
4755 delimiter.add('\rrparenthesis', new Symbol('\rrparenthesis', '\u2988'));
4756 delimiter.add('\llLangle', new Symbol('\llLangle', '\u2989'));
4757 delimiter.add('\llRangle', new Symbol('\llRangle', '\u298A'));
4758 delimiter.add('\lLbrbrak', new Symbol('\lLbrbrak', '\u27EC'));
4759 delimiter.add('\lRbrbrak', new Symbol('\lRbrbrak', '\u27ED'));
4760 delimiter.add('\lBrace', new Symbol('\lBrace', '\u2983'));
4761 delimiter.add('\rBrace', new Symbol('\rBrace', '\u2984'));
4762 delimiter.add('\lLParen', new Symbol('\lLParen', '\u2985'));
4763 delimiter.add('\rLParen', new Symbol('\rLParen', '\u2986'));
4764 delimiter.add('\llbrackubar', new Symbol('\llbrackubar', '\u298B'));
4765 delimiter.add('\lbrackubar', new Symbol('\lbrackubar', '\u298C'));
4766 delimiter.add('\llbrackultick', new Symbol('\llbrackultick', '\u298D'));
4767 delimiter.add('\lbracklrtick', new Symbol('\lbracklrtick', '\u298E'));
4768 delimiter.add('\llbracklltick', new Symbol('\llbracklltick', '\u298F'));
4769 delimiter.add('\lbrackurtick', new Symbol('\lbrackurtick', '\u2990'));
4770 delimiter.add('\llangledot', new Symbol('\llangledot', '\u2991'));
4771 delimiter.add('\lrangledot', new Symbol('\lrangledot', '\u2992'));
4772 delimiter.add('\llparenless', new Symbol('\llparenless', '\u2993'));
4773 delimiter.add('\lparenltr', new Symbol('\lparenltr', '\u2994'));
4774 delimiter.add('\lLparenltr', new Symbol('\lLparenltr', '\u2995'));
4775 delimiter.add('\lRparenless', new Symbol('\lRparenless', '\u2996'));
4776 delimiter.add('\llblbrbrak', new Symbol('\llblbrbrak', '\u2997'));
4777 delimiter.add('\lrbkbrbrak', new Symbol('\lrbkbrbrak', '\u2998'));
4778 delimiter.add('\llvzigzag', new Symbol('\llvzigzag', '\u29D8'));
4779 delimiter.add('\lrvzigzag', new Symbol('\lrvzigzag', '\u29D9'));
4780 delimiter.add('\lLvzigzag', new Symbol('\lLvzigzag', '\u29DA'));
4781 delimiter.add('\lRvzigzag', new Symbol('\lRvzigzag', '\u29DB'));
4782 delimiter.add('\llcurvyangle', new Symbol('\llcurvyangle', '\u29FC'));
4783 delimiter.add('\lrcurvyangle', new Symbol('\lrcurvyangle', '\u29FD'));
4784 delimiter.add('\lVvert', new Symbol('\lVvert', '\u2980'));
4785 } // ready
4786 }, // startup
4787
4788 tex: {
4789 packages: {'[+]': ['tagformat', 'Lwarp-macros', 'textmacros']},
4790 tags: "ams",
4791 tagformat: {
4792 number: function (n) {
4793 if(MathJax.config.subequations==0)
4794 return(MathJax.config.section + n);
4795 else

```

```

4796 return(MathJax.config.section + String.fromCharCode(96+n));
4797 },
4798 },
4799 }
4800 }
4801 </script>
4802
4803 <script
4804 id="MathJax-script"
4805 src="https://cdn.jsdelivr.net/npm/mathjax@3/es5/tex-svg.js"
4806 ></script>
4807 \end{filecontents*}
4808 % \end{Verbatim}% for syntax highlighting
4809 \end{LWRwriteconf}

```

## 40.12 lwarpmk.lua — lwarpmk option

Opt lwarpmk

Creates a local copy of *lwarpmk*.

Prog lwarpmk

Command-line utility to process lwarp files and images.

[parallel processing](#) lateximages and SVG math images are generated using multiple processes in parallel. For UNIX and LINUX, every 32 images the wait command is issued to wait for the previous batch of images to finish processing before starting a new batch. For WINDOWS, every 32 images one task is dispatched with

```
START /B /WAIT /BELOWNORMAL
```

which causes the operating system to wait until this lesser-priority tasks finishes, hopefully also waiting for the normal priority tasks which were already in progress to also complete. Afterwards, the next batch of images is started.

The following is only generated if the lwarpmk option was given to lwarp.

```

4810 \begin{LWRcreatelwarpmk}

4811 \begin{filecontents*}[overwrite]{lwarpmk.lua}
4812 #!/usr/bin/env texlua
4813
4814 -- Copyright 2016-2022 Brian Dunn
4815
4816
4817 printversion = "v0.905"
4818 requiredconfversion = "2" -- also at *lwarpmk.conf
4819
4820 function printhelp ()
4821 print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help.");
4822 end
4823
4824
4825 function printusage ()
4826 --
4827 -- Print the usage of the lwarpmk command:
4828 --
4829 print ([[
4830
4831 lwarpmk print [-p project]: Compile the print version if necessary.
4832 lwarpmk print1 [-p project]: Forced single compile of the print version.

```

```

4833 lwarpmk printindex [-p project]: Process print indexes.
4834 lwarpmk printglossary [-p project]: Process the glossary for the print version.
4835 lwarpmk html [-p project]: Compile the HTML version if necessary.
4836 lwarpmk html1 [-p project]: Forced single compile of the HTML version.
4837 lwarpmk htmlindex [-p project]: Process HTML indexes.
4838 lwarpmk htmlglossary [-p project]: Process the glossary for the html version.
4839 lwarpmk again [-p project]: Touch the source code to trigger recompiles.
4840 lwarpmk limages [-p project]: Process the "lateximages" created by lwarp.sty.
4841 lwarpmk pdftohtml [-p project]:
4842 For use with latexmk or a Makefile:
4843 Converts project_html.pdf to project_html.html and individual HTML files.
4844 Finishes the HTML conversion even if there was a compile error.
4845 lwarpmk pdftosvg <list of file names>: Converts each PDF file to SVG.
4846 lwarpmk epstopdf <list of file names>: Converts each EPS file to PDF.
4847 lwarpmk clean [-p project]: Remove *.aux, *.toc, *.lof/t,
4848 *.idx, *.ind, *.bbl, *.log, *_html_inc.*, .gl*,
4849 *_html.pdf, *_html.html, *_html.sidetoc
4850 lwarpmk cleanall [-p project]: Remove auxiliary files, project.pdf, *.html
4851 lwarpmk cleanimages: Removes all images from the "lateximages" directory.
4852 lwarpmk -v: Print the version number.
4853 lwarpmk -h: Print this help message.
4854 lwarpmk --help: Print this help message.
4855
4856]])
4857 -- printconf ()
4858 end
4859
4860
4861 function splitfilename (pathandfilename)
4862 --
4863 -- Separates out the path and extension from a filename.
4864 -- Returns path, filename with extension, and extension.
4865 -- Ex: thispath, thisfilename, thisextension = splitfilename ("path/to/filename.ext")
4866 --
4867 -- https://www.fhug.org.uk/wiki/wiki/doku.php?id=plugins:code_snippets:
4868 -- split_filename_in_to_path_filename_and_extension
4869 --
4870 if lfs.attributes(pathandfilename,"mode") == "directory" then
4871 local strPath = pathandfilename:gsub("[\\/]$", "") -- $(syntax highlighting)
4872 return strPath.."\\", "", ""
4873 end
4874 pathandfilename = pathandfilename.."."
4875 return pathandfilename:match("^(-)([^\\"/]-)%.(^[^\\"/]-)%.%?$")
4876 end
4877
4878
4879 function splitfile (destfile,sourcefile)
4880 --
4881 -- Split one large sourcefile into a number of files,
4882 -- starting with destfile.
4883 -- The file is split at each occurrence of <!--|Start file|newfilename|*
4884 -- If lwarp is in use, sets usinglwarp.
4885 --
4886 usinglwarp = false ;
4887 print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
4888 local sfile = io.open(sourcefile)
4889 io.output(destfile)
4890 for line in sfile:lines() do
4891 i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*)|") ;
4892 if (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then

```

```
4893 -- split the file
4894 io.output(newfilename) ;
4895 else
4896 if ((i~= nil) and (copen == "<!--") and (cstart == "Using lwarp")) then
4897 -- verified the use of \usepackage{lwarp}
4898 usinglwarp = true ;
4899 else
4900 -- not a splitpoint
4901 io.write (line .. "\n") ;
4902 end end
4903 end -- do
4904 io.close(sfile)
4905 if (usinglwarp == false) then
4906 print ("lwarpmk: ===")
4907 print ("lwarpmk: \\usepackage{lwarp} was not detected.")
4908 print ("lwarpmk: The HTML output will not be correct.")
4909 print ("lwarpmk: Ensured that \\usepackage{lwarp} is enabled,")
4910 print ("lwarpmk: then lwarpmk print and lwarpmk html again.")
4911 print ("lwarpmk: ===")
4912 end
4913 end -- function
4914
4915
4916 function cvalueerror (line, linenum , cvalue)
4917 --
4918 -- Incorrect value, so print an error and exit.
4919 --
4920 print ("lwarpmk: ===")
4921 print ("lwarpmk: " .. linenum .. " : " .. line) ;
4922 print (
4923 "lwarpmk: incorrect variable value \"" .. cvalue ..
4924 "\"" in lwarpmk.conf.\n"
4925) ;
4926 print ("lwarpmk: ===")
4927 -- printconf () ;
4928 os.exit(1) ;
4929 end
4930
4931
4932 function printhowtorecompile ()
4933 -- Tells the user how to recompile to regenerate the configuration files.
4934 print ("lwarpmk: The configuration files lwarpmk.conf and "..sourcename.."lwarpmkconf")
4935 print ("lwarpmk: must be updated. To do so, recompile")
4936 print ("lwarpmk: " , sourcename.."tex")
4937 if (printlatexcmd == "") then
4938 print ("lwarpmk: using xe/luatex/pdflatex,")
4939 else
4940 print ("lwarpmk: using the command:")
4941 print ("lwarpmk: " , printlatexcmd)
4942 end
4943 print ("lwarpmk: then use lwarpmk again.")
4944 end -- printhowtorecompile
4945
4946
4947 function ignoreconf ()
4948 -- Global argument index
4949 argindex = 2
4950 end
4951
4952 function loadconf ()
```

```
4953 --
4954 -- Load settings from the project's "lwarpmk.conf" file:
4955 --
4956 -- Default configuration filename:
4957 local conffile = "lwarpmk.conf"
4958 local confroot = "lwarpmk"
4959 -- Global argument index
4960 argindex = 2
4961 -- Optional configuration filename:
4962 if (arg[argindex] == "-p") then
4963 argindex = argindex + 1
4964 confroot = arg[argindex]
4965 conffile = confroot.."lwarpmk.conf"
4966 argindex = argindex + 1
4967 end
4968 -- Additional defaults:
4969 confversion = "0"
4970 opsystem = "Unix"
4971 imagesdirectory = "lateximages"
4972 imagesname = "image-"
4973 latexmk = "false"
4974 printlatexcmd = ""
4975 HTMLlatexcmd = ""
4976 printindexcmd = ""
4977 HTMLindexcmd = ""
4978 latexmkindexcmd = ""
4979 -- to be removed:
4980 -- indexprog = "makeindex"
4981 -- makeindexstyle = "lwarp.ist"
4982 -- xindylanguage = "english"
4983 -- xindycodepage = "utf8"
4984 -- xindystyle = "lwarp.xdy"
4985 -- pdftotextenc = "UTF-8"
4986 glossarycmd = "makeglossaries"
4987 -- Verify the file exists:
4988 if (lfs.attributes(conffile,"mode")==nil) then
4989 -- file not exists
4990 print ("lwarpmk: ===")
4991 print ("lwarpmk: File \" .. conffile ..\" does not exist.")
4992 print ("lwarpmk: Move to the project's source directory,")
4993 print ("lwarpmk: recompile using pdflatex, xelatex, or luatex,")
4994 print ("lwarpmk: then try using lwarpmk again.")
4995 if (arg[argindex] ~= nil) then
4996 print (
4997 "lwarpmk: (\" .. confroot ..
4998 "\" does not appear to be a project name.)"
4999)
5000 end
5001 print ("lwarpmk: ===")
5002 printhelp () ;
5003 os.exit(1) -- exit the entire lwarpmk script
5004 else -- file exists
5005 -- Read the file:
5006 print ("lwarpmk: Reading " .. conffile ..".")
5007 local cfile = io.open(conffile)
5008 -- Scan each line, parsing each line as: name = [[string]]
5009 local linenum = 0
5010 for line in cfile:lines() do -- scan lines
5011 linenum = linenum + 1
5012 i,j,cvarname,cvalue = string.find (line,"([%w-]*)%s*=%s*%[[^%]]*]");
```

```
5013-- Error if incorrect enclosing characters:
5014 if (i == nil) then
5015 print ("lwarpmk: ===")
5016 print ("lwarpmk: " .. linenum .. " : " .. line) ;
5017 print ("lwarpmk: Incorrect entry in " .. conffile .. ".\n") ;
5018 print ("lwarpmk: ===")
5019 -- printconf () ;
5020 os.exit(1) ;
5021 end -- nil
5022 if (cvarname == "confversion") then
5023 confversion = cvalue
5024 elseif (cvarname == "opssystem") then
5025 -- Verify choice of opssystem:
5026 if ((cvalue == "Unix") or (cvalue == "Windows")) then
5027 opssystem = cvalue
5028 else
5029 cvalueerror (line, linenum , cvalue)
5030 end
5031 elseif (cvarname == "sourcename") then sourcename = cvalue
5032 elseif (cvarname == "homehtmlfilename") then homehtmlfilename = cvalue
5033 elseif (cvarname == "htmlfilename") then htmlfilename = cvalue
5034 elseif (cvarname == "imagesdirectory") then imagesdirectory = cvalue
5035 elseif (cvarname == "imagesname") then imagesname = cvalue
5036 elseif (cvarname == "latexmk") then latexmk = cvalue
5037 elseif (cvarname == "printlatexcmd") then printlatexcmd = cvalue
5038 elseif (cvarname == "HTMLlatexcmd") then HTMLlatexcmd = cvalue
5039 elseif (cvarname == "printindexcmd") then printindexcmd = cvalue
5040 elseif (cvarname == "HTMLindexcmd") then HTMLindexcmd = cvalue
5041 elseif (cvarname == "latexmkindexcmd") then latexmkindexcmd = cvalue
5042 elseif (cvarname == "glossarycmd") then glossarycmd = cvalue
5043 elseif (cvarname == "pdftotextenc") then pdftotextenc = cvalue
5044 else
5045 print ("lwarpmk: ===")
5046 print ("lwarpmk: " .. linenum .. " : " .. line) ;
5047 print (
5048 "lwarpmk: Incorrect variable name \" .. cvarname .. "\" in " ..
5049 conffile .. ".\n"
5050) ;
5051 print ("lwarpmk: ===")
5052 -- printconf () ;
5053 os.exit(1) ;
5054 end -- cvarname
5055 end -- do scan lines
5056 io.close(cfile)
5057 end -- file exists
5058 -- Error if sourcename is "lwarp".
5059 -- This could happen if a local copy of lwarp has recently been recompiled.
5060 if sourcename=="lwarp" then
5061 print ("lwarpmk: ===")
5062 print ("lwarpmk: lwarp.sty has recently been recompiled in this directory,")
5063 print ("lwarpmk: and \"lwarpmk.conf\" is no longer set for your own project.")
5064 print ("lwarpmk: (Perhaps you are not in your project's directory?)")
5065 print ("lwarpmk: In your project directory, recompile your project")
5066 print ("lwarpmk: using pdf/luaxelatex <projectname>.")
5067 print ("lwarpmk: After a recompile, \"lwarpmk.conf\" will be set for your project,")
5068 print ("lwarpmk: and you may again use lwarpmk.")
5069 print ("lwarpmk: ===")
5070 os.exit(1)
5071 end -- sourcename of "lwarp"
5072 -- Select some operating-system commands:
```

```
5073 if opsystem=="Unix" then -- For Unix / Linux / Mac OS:
5074 rmname = "rm"
5075 mvname = "mv"
5076 cpname = "cp"
5077 touchnamepre = "touch"
5078 touchnamepost = ""
5079 newtouchname = "touch"
5080 dirslash = "/"
5081 opquote= "\'"
5082 cmdgroupopenname = " ("
5083 cmdgroupclosename = ") "
5084 seqname = " && "
5085 bname = " &"
5086 elseif opsystem=="Windows" then -- For Windows
5087 rmname = "DEL"
5088 mvname = "MOVE"
5089 cpname = "COPY"
5090 touchnamepre = "COPY /b"
5091 touchnamepost = "+,,"
5092 newtouchname = "echo empty >"
5093 dirslash = "\\"
5094 opquote= "\""
5095 cmdgroupopenname = ""
5096 cmdgroupclosename = ""
5097 seqname = " & "
5098 bname = ""
5099 else
5100 print ("lwarpmk: ===")
5101 print ("lwarpmk: Select Unix or Windows for opsystem.")
5102 print ("lwarpmk: ===")
5103 os.exit(1)
5104 end --- for Windows
5105 -- Warning if the operating system does not appear to be correct,
5106 -- in case files were transferred to another system.
5107 if ((package.config:sub(1,1)) ~= dirslash) then
5108 print ("lwarpmk: ===")
5109 print ("lwarpmk: It appears that lwarpmk.conf is for a different operating system.")
5110 printhowtorecompile ()
5111 print ("lwarpmk: ===")
5112 os.exit(1)
5113 end
5114 -- Error if the configuration file's version is not current:
5115 if (confversion ~= requiredconfversion) then
5116 print ("lwarpmk: ===")
5117 printhowtorecompile ()
5118 print ("lwarpmk: ===")
5119 os.exit(1)
5120 end
5121 end -- loadconf
5122
5123
5124 function executecheckerror (executecommands , errormessage)
5125 --
5126 -- Execute an operating system call,
5127 -- and maybe exit with an error message.
5128 --
5129 local err
5130 err = os.execute (executecommands)
5131 if (err ~= 0) then
5132 print ("lwarpmk: ===")
```

```
5133 print ("lwarpmk: " .. errormessage)
5134 print ("lwarpmk: ===")
5135 os.exit(1)
5136 end
5137 end -- executecheckerror
5138
5139
5140 function refreshdate ()
5141 os.execute(touchnamepre .. " " .. sourcename .. ".tex " .. touchnamepost)
5142 end
5143
5144
5145
5146 function reruntoget (filesorce)
5147 --
5148 -- Scan the LaTeX log file for the phrase "Rerun to get",
5149 -- indicating that the file should be compiled again.
5150 -- Return true if found.
5151 --
5152 local fsource = io.open(filesorce)
5153 for line in fsource:lines() do
5154 if (string.find(line,"Rerun to get") ~= nil) then
5155 io.close(fsource)
5156 return true
5157 end -- if
5158 end -- do
5159 io.close(fsource)
5160 return false
5161 end
5162
5163
5164
5165 function onetime (latexcmd, fsuffix)
5166 --
5167 -- Compile one time, return true if should compile again.
5168 -- fsuffix is "" for print, "_html" for HTML output.
5169 --
5170 print("lwarpmk: Compiling with: " .. latexcmd)
5171 executecheckerror (
5172 latexcmd ,
5173 "Compile error."
5174)
5175 return (reruntoget(sourcename .. fsuffix .. ".log")) ;
5176 end
5177
5178
5179 function manytimes (latexcmd, fsuffix)
5180 --
5181 -- Compile up to five times.
5182 -- fsuffix is "" for print, "_html" for HTML output
5183 --
5184 if onetime(latexcmd, fsuffix) == true then
5185 if onetime(latexcmd, fsuffix) == true then
5186 if onetime(latexcmd, fsuffix) == true then
5187 if onetime(latexcmd, fsuffix) == true then
5188 if onetime(latexcmd, fsuffix) == true then
5189 end end end end end
5190 end
5191
5192
```

```
5193 function verifyfileexists (filename)
5194 --
5195 -- Exit if the given file does not exist.
5196 --
5197 if (lfs.attributes (filename , "modification") == nil) then
5198 print ("lwarpmk: ===")
5199 print ("lwarpmk: " .. filename .. " not found.") ;
5200 print ("lwarpmk: ===")
5201 os.exit (1) ;
5202 end
5203 end
5204
5205
5206
5207 function pdftohtml ()
5208 --
5209 -- Convert <project>_html.pdf into HTML files:
5210 --
5211 -- Convert to text:
5212 print ("lwarpmk: Converting " .. sourcename
5213 .. "_html.pdf to " .. sourcename .. "_html.html")
5214 err = os.execute("pdftotext -enc " .. pdftotextenc .. " -nopgbrk -layout "
5215 .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
5216 if (err ~= 0) then
5217 print ("lwarpmk: ===")
5218 print ("lwarpmk: Ensure that the Poppler utilities are installed.")
5219 print ("lwarpmk: See the Lwarp manual: 'Installing additional utilities'.")
5220 print ("lwarpmk: ===")
5221 os.exit(1)
5222 end
5223 -- Split the result into individual HTML files:
5224 splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
5225 end
5226
5227
5228 function removeaux ()
5229 --
5230 -- Remove auxiliary files:
5231 -- All .aux files are removed since there may be many bbl*.aux files.
5232 -- Also removes sourcename_html.pdf, sourcename_html.html,
5233 -- and sourcename_html.sidetoc, plus comment_*.cut.
5234 --
5235 os.execute (rmname .. " *.aux " ..
5236 sourcename .. ".toc " .. sourcename .. "_html.toc " ..
5237 sourcename .. ".lof " .. sourcename .. "_html.lof " ..
5238 sourcename .. ".lot " .. sourcename .. "_html.lot " ..
5239 sourcename .. ".bbl " .. sourcename .. "_html.bbl " ..
5240 " *.idx " ..
5241 " *.ind " ..
5242 sourcename .. ".ps " .. sourcename .. "_html.ps " ..
5243 sourcename .. ".log " .. sourcename .. "_html.log " ..
5244 sourcename .. ".gl*" .. sourcename .. "_html.gl*" ..
5245 sourcename .. "_html.pdf " ..
5246 sourcename .. "_html.html " ..
5247 sourcename .. "_html.sidetoc " ..
5248 " *_html_inc.* " ..
5249 " comment_*.cut"
5250)
5251 end
5252
```

```
5253 function checkhtmlpdfexists ()
5254 --
5255 -- Error if the HTML document does not exist.
5256 -- The lateximages are drawn from the HTML PDF version of the document,
5257 -- so "lwarpmk html" must be done before "lwarpmk limages".
5258 --
5259 local htmlpdffile = io.open(sourcename .. "_html.pdf", "r")
5260 if (htmlpdffile == nil) then
5261 print ("")
5262 print ("lwarpmk: ===")
5263 print ("lwarpmk: The HTML version of the document does not exist.")
5264 print ("lwarpmk: Enter \"lwarpmk html\" to compile the HTML version.")
5265 print ("lwarpmk: ===")
5266 os.exit(1)
5267 end
5268 io.close (htmlpdffile)
5269 end -- checkhtmlpdfexists
5270
5271
5272 function warnlimages ()
5273 --
5274 -- Warning of a missing <sourcename>-images.txt file:
5275 print ("lwarpmk: ===")
5276 print ("lwarpmk: \"\" .. sourcename .. "-images.txt\" does not exist.")
5277 print ("lwarpmk: Your project does not use SVG math or other lateximages,")
5278 print ("lwarpmk: or the file has been deleted somehow.")
5279 print ("lwarpmk: Use \"lwarpmk html1\" to recompile your project")
5280 print ("lwarpmk: and recreate \"\" .. sourcename .. "-images.txt\".")
5281 print ("lwarpmk: If your project does not use SVG math or other lateximages,")
5282 print ("lwarpmk: then \"\" .. sourcename .. "-images.txt\" will never exist, and")
5283 print ("lwarpmk: \"lwarpmk limages\" will not be necessary.")
5284 print ("lwarpmk: ===")
5285 end -- warnlimages
5286
5287
5288 function warnlimagesrecompile ()
5289 -- Warning if must recompile before creating limages:
5290 print ("")
5291 print ("lwarpmk: ===")
5292 print ("lwarpmk: Cross-references are not yet correct.")
5293 print ("lwarpmk: The document must be recompiled before creating the lateximages.")
5294 print ("lwarpmk: Enter \"lwarpmk html1\" again, then try \"lwarpmk limages\" again.")
5295 print ("lwarpmk: ===")
5296 end --warnlimagesrecompile
5297
5298
5299 function checklimages ()
5300 --
5301 -- Check <sourcename>.txt to see if need to recompile first.
5302 -- If any entry has a page number of zero, then there were incorrect images.
5303 --
5304 print ("lwarpmk: Checking for a valid \" .. sourcename .. "-images.txt file.")
5305 local limagesfile = io.open(sourcename .. "-images.txt", "r")
5306 if (limagesfile == nil) then
5307 warnlimages ()
5308 os.exit(1)
5309 end
5310 -- Track warning to recompile if find a page 0
5311 local pagezerowarning = false
5312 -- Scan <sourcename>.txt
```

```

5313 for line in limagesfile:lines() do
5314 -- lwimgpage is the page number in the PDF which has the image
5315 -- lwimghash is true if this filename is a hash
5316 -- lwimgname is the lateximage filename root to assign for the image
5317 i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
5318 -- For each entry:
5319 if ((i~=nil)) then
5320 -- If the page number is 0, image references are incorrect
5321 -- and must recompile the source document:
5322 if (lwimgpage == "0") then
5323 pagezerowarning = true
5324 end
5325 end -- if i~=nil
5326 end -- do
5327 -- The last line should be |end|end|end|.
5328 -- If not, the compile must have aborted, and the images are incomplete.
5329 if (lwimgpage ~= "end") then
5330 warnlimagesrecompile()
5331 os.exit(1) ;
5332 end
5333 if (pagezerowarning) then
5334 warnlimagesrecompile()
5335 os.exit(1) ;
5336 end -- pagezerowarning
5337 end -- checklimages
5338
5339
5340 function createuniximage (lwimgfullname)
5341 --
5342 -- Create one lateximage for Unix / Linux / Mac OS.
5343 --
5344 executecheckerror (
5345 cmdgroupopenname ..
5346 "pdfseparate -f " .. lwimgpage .. " -l " .. lwimgpage .. " " ..
5347 sourcename .. "_html.pdf " ..
5348 imagesdirectory .. dirslash .. "lateximagetemp-%d" .. ".pdf" ..
5349 seqname ..
5350 -- Crop the image:
5351 "pdfcrop --hires " .. imagesdirectory .. dirslash .. "lateximagetemp-" ..
5352 lwimgpage .. ".pdf " ..
5353 imagesdirectory .. dirslash .. lwimgname .. ".pdf" ..
5354 seqname ..
5355 -- Convert the image to svg:
5356 "pdftocairo -svg -noshrink " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf" ..
5357 imagesdirectory .. dirslash .. lwimgname .. ".svg" ..
5358 seqname ..
5359 -- Remove the temporary files:
5360 rmname .. " " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf" .. seqname ..
5361 rmname .. " " .. imagesdirectory .. dirslash .. "lateximagetemp-" .. lwimgpage .. ".pdf" ..
5362 cmdgroupclosename .. " >/dev/null " .. bgnname
5363 ,
5364 "File error trying to convert " .. lwimgfullname
5365)
5366 -- Every 32 images, wait for completion at below normal priority,
5367 -- allowing other image tasks to catch up.
5368 numimageprocesses = numimageprocesses + 1
5369 if (numimageprocesses > 32) then
5370 numimageprocesses = 0
5371 print ("lwarpmk: waiting")
5372 executecheckerror ("wait" , "File error trying to wait.")

```

```
5373 end
5374 end -- createuniximage
5375
5376
5377 function createwindowsimage (lwimgfullname)
5378 --
5379 -- Create one lateximage for Windows.
5380 --
5381 -- Every 32 images, wait for completion at below normal priority,
5382 -- allowing other image tasks to catch up.
5383 numimageprocesses = numimageprocesses + 1
5384 if (numimageprocesses > 32) then
5385 numimageprocesses = 0
5386 thiswaitcommand = "/WAIT /BELOWNORMAL"
5387 print ("lwarpmk: waiting")
5388 else
5389 thiswaitcommand = ""
5390 end
5391 -- Execute the image generation command
5392 executecheckerror (
5393 "start /B " .. thiswaitcommand .. " \"\" lwarp_one_limage " ..
5394 lwimgpage .. " " ..
5395 lwimghash .. " " ..
5396 lwimgname .. " " ..
5397 sourcename .. " <nul >nul"
5398 ,
5399 "File error trying to create image."
5400)
5401 end -- createwindowsimage
5402
5403
5404 function createonelateximage (line)
5405 --
5406 -- Given the next line of <sourcename>.txt, convert a single image.
5407 --
5408 -- lwimgpage is the page number in the PDF which has the image
5409 -- lwimghash is true if this filename is a hash
5410 -- lwimgname is the lateximage filename root to assign for the image
5411 i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
5412 -- For each entry:
5413 if ((i~=nil)) then
5414 -- Skip if the page number is 0:
5415 if (lwimgpage == "0") then
5416 pagezerowarning = true
5417 -- Skip if the page number is "end":
5418 else if (lwimgpage == "end") then
5419 else
5420 -- Skip is this image is hashed and already exists:
5421 local lwimgfullname = imagesdirectory .. dirslash .. lwimgname .. ".svg"
5422 if (
5423 (lwimghash ~= "true") or
5424 (lfs.attributes(lwimgfullname,"mode")==nil) -- file not exists
5425)
5426 then -- not hashed or not exists:
5427 -- Print the name of the file being generated:
5428 print ("lwarpmk: " .. lwimgname)
5429 -- Touch/create the dest so that only once instance tries to build it:
5430 executecheckerror (
5431 newtouchname .. " " .. lwimgfullname ,
5432 "File error trying to touch " .. lwimgfullname
```

```
5433)
5434 -- Separate out the image into its own single-page pdf:
5435 if opsystem=="Unix" then
5436 createuniximage (lwimgfullname)
5437 elseif opsystem=="Windows" then
5438 createwindowsimage (lwimgfullname)
5439 end
5440 end -- not hashed or not exists
5441 end -- not page "end"
5442 end -- not page 0
5443 end -- not nil
5444 end -- createonelateximage
5445
5446
5447 function createlateximages ()
5448 --
5449 -- Create lateximages based on <sourcename>-images.txt:
5450 --
5451 -- See if the document must be recompiled first:
5452 checklimages ()
5453 -- See if the HTML version exists:
5454 checkhtmlpdfexists ()
5455 -- Attempt to create the lateximages:
5456 print ("lwarpmk: Creating lateximages.")
5457 local limagesfile = io.open(sourcename .. "-images.txt", "r")
5458 if (limagesfile == nil) then
5459 warnlimages ()
5460 os.exit(1)
5461 end
5462 -- Create the lateximages directory, ignore error if already exists
5463 err = os.execute("mkdir " .. imagesdirectory)
5464 -- For Windows, create lwarp_one_limage.cmd from lwarp_one_limage.txt:
5465 if opsystem=="Windows" then
5466 executecheckerror (
5467 cpname .. " lwarp_one_limage.txt lwarp_one_limage.cmd" ,
5468 "File error trying to copy lwarp_one_limage.txt to lwarp_one_limage.cmd"
5469)
5470 end -- create lwarp_one_limage.cmd
5471 -- Track the number of parallel processes
5472 numimageprocesses = 0
5473 -- Track warning to recompile if find a page 0
5474 pagezerowarning = false
5475 -- Scan <sourcename>.txt
5476 for line in limagesfile:lines() do
5477 createonelateximage (line)
5478 end -- do
5479 io.close(limagesfile)
5480 print ("lwarpmk limages: ===")
5481 print ("lwarpmk limages: Wait a moment for the images to complete")
5482 print ("lwarpmk limages: before reloading the page.")
5483 print ("lwarpmk limages: ===")
5484 print ("lwarpmk limages: Done.")
5485 if (pagezerowarning == true) then
5486 print ("lwarpmk limages: WARNING: Images will be incorrect.")
5487 print ("lwarpmk limages: Enter \"lwarpmk cleanlimages\", then")
5488 print ("lwarpmk limages: recompile the document one more time, then")
5489 print ("lwarpmk limages: repeat \"lwarpmk images\" again.")
5490 end -- pagezerowarning
5491 end -- function
5492
```

```
5493
5494 function convertepstopdf ()
5495 --
5496 -- Converts EPS files to PDF files.
5497 -- The filenames are arg[argindex] and up.
5498 -- arg[1] is the command "epstopdf".
5499 --
5500 ignoreconf ()
5501 for i = argindex , #arg do
5502 if (lfs.attributes(arg[i],"mode")==nil) then
5503 print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
5504 else
5505 print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
5506 thispath, thisfilename, thisextension = splitfilename(arg[i])
5507 if (thispath == nil) then
5508 os.execute ("epstopdf " .. arg[i])
5509 else
5510 os.execute (
5511 "epstopdf " ..
5512 thispath .. thisfilename .. "." .. thisextension .. " " ..
5513 thispath .. thisfilename .. ".pdf"
5514)
5515 end
5516 end -- if
5517 end -- do
5518 end --function
5519
5520
5521 function convertpdfptosvg ()
5522 --
5523 -- Converts PDF files to SVG files.
5524 -- The filenames are arg[argindex] and up.
5525 -- arg[1] is the command "pdftosvg".
5526 --
5527 ignoreconf ()
5528 for i = argindex , #arg do
5529 if (lfs.attributes(arg[i],"mode")==nil) then
5530 print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
5531 else
5532 print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
5533 thispath, thisfilename, thisextension = splitfilename(arg[i])
5534 if (thispath == nil) then
5535 os.execute ("pdftocairo -svg " .. arg[i])
5536 else
5537 os.execute (
5538 "pdftocairo -svg " ..
5539 thispath .. thisfilename .. "." .. thisextension .. " " ..
5540 thispath .. thisfilename .. ".svg"
5541)
5542 end
5543 end -- if
5544 end -- do
5545 end --function
5546
5547
5548 -- Force an update and conclude processing:
5549 function updateanddone ()
5550 print ("lwarpmk: Forcing an update of " .. sourcename .. ".tex.")
5551 refreshdate ()
5552 print ("lwarpmk: " .. sourcename .. ".tex is ready to be recompiled.")
```

```
5553 print ("lwarpmk: Done.")
5554 end -- function
5555
5556
5557 -- Start of the main code: --
5558
5559
5560 -- lwarpmk --version :
5561
5562 if (arg[1] == "--version") then
5563 print ("lwarpmk: " .. printversion)
5564
5565 else -- not --version
5566
5567
5568 -- print intro:
5569
5570 print ("lwarpmk: " .. printversion .. " Automated make for the LaTeX Lwarp package.")
5571
5572
5573 -- lwarpmk print:
5574
5575 if arg[1] == "print" then
5576 loadconf ()
5577 if (latexmk == "true") then
5578 print ("lwarpmk: Compiling with: " .. printlatexcmd)
5579 executecheckerror (
5580 printlatexcmd ,
5581 "Compile error."
5582)
5583 print ("lwarpmk: Done.")
5584 else -- not latexmk
5585 verifyfileexists (sourcename .. ".tex") ;
5586 -- See if up to date:
5587 if (
5588 (lfs.attributes (sourcename .. ".pdf" , "modification") == nil) or
5589 (
5590 lfs.attributes (sourcename .. ".tex" , "modification") >
5591 lfs.attributes (sourcename .. ".pdf" , "modification")
5592)
5593) then
5594 -- Recompile if not yet up to date:
5595 manytimes(printlatexcmd, "")
5596 print ("lwarpmk: Done.") ;
5597 else
5598 print ("lwarpmk: " .. sourcename .. ".pdf is up to date.") ;
5599 end
5600 end -- not latexmk
5601
5602
5603 -- lwarpmk print1:
5604
5605 elseif arg[1] == "print1" then
5606 loadconf ()
5607 verifyfileexists (sourcename .. ".tex") ;
5608 onetime(printlatexcmd, "")
5609 print ("lwarpmk: Done.") ;
5610
5611
5612 -- lwarpmk printindex:
```

```
5613-- Compile the index then touch the source
5614-- to trigger a recompile of the document:
5615
5616elseif arg[1] == "printindex" then
5617loadconf ()
5618os.execute (printindexcmd)
5619print ("lwarpmk: -----")
5620updateanddone ()
5621
5622
5623-- lwarpmk printglossary:
5624-- Compile the glossary then touch the source
5625-- to trigger a recompile of the document:
5626
5627elseif arg[1] == "printglossary" then
5628loadconf ()
5629print ("lwarpmk: Processing the glossary.")
5630
5631os.execute(glossarycmd .. " " .. sourcename)
5632updateanddone ()
5633
5634
5635-- lwarpmk html:
5636
5637elseif arg[1] == "html" then
5638loadconf ()
5639if (latexmk == "true") then
5640 print ("lwarpmk: Compiling with: " .. HTMLlatexcmd)
5641 executecheckerror (
5642 HTMLlatexcmd ,
5643 "Compile error."
5644)
5645 pdftohtml ()
5646 print ("lwarpmk: Done.")
5647else -- not latexmk
5648 verifyfileexists (sourcename .. ".tex") ;
5649 -- See if exists and is up to date:
5650 if (
5651 (lfs.attributes (homehtmlfilename .. ".html" , "modification") == nil) or
5652 (
5653 lfs.attributes (sourcename .. ".tex" , "modification") >
5654 lfs.attributes (homehtmlfilename .. ".html" , "modification")
5655)
5656) then
5657 -- Recompile if not yet up to date:
5658 manytimes(HTMLlatexcmd, "_html")
5659 pdftohtml ()
5660 print ("lwarpmk: Done.")
5661 else
5662 print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
5663 end
5664end -- not latexmk
5665
5666
5667-- lwarpmk html1:
5668
5669elseif arg[1] == "html1" then
5670 loadconf ()
5671 verifyfileexists (sourcename .. ".tex") ;
5672 onetime(HTMLlatexcmd, "_html")
```

```
5673 pdftohtml ()
5674 print ("lwarpmk: Done.")
5675
5676
5677 -- lwarpmk pdftohtml:
5678 elseif arg[1] == "pdftohtml" then
5679 loadconf ()
5680 pdftohtml ()
5681
5682
5683 -- lwarpmk htmlindex:
5684 -- Compile the index then touch the source
5685 -- to trigger a recompile of the document:
5686
5687 elseif arg[1] == "htmlindex" then
5688 loadconf ()
5689 os.execute (HTMLindexcmd)
5690 print ("lwarpmk: -----")
5691 updateanddone ()
5692
5693
5694 -- lwarpmk htmlglossary:
5695 -- Compile the glossary then touch the source
5696 -- to trigger a recompile of the document.
5697 -- The <sourcename>.xdy file is created by the glossaries package.
5698
5699 elseif arg[1] == "htmlglossary" then
5700 loadconf ()
5701 print ("lwarpmk: Processing the glossary.")
5702 os.execute(glossarycmd .. " " .. sourcename .. "_html")
5703 updateanddone ()
5704
5705
5706 -- lwarpmk limages:
5707 -- Scan the <sourcename>.txt file to create lateximages.
5708
5709 elseif arg[1] == "limages" then
5710 loadconf ()
5711 print ("lwarpmk: Processing images.")
5712 createlateximages ()
5713 print ("lwarpmk: Done.")
5714
5715
5716 -- lwarpmk again:
5717 -- Touch the source to trigger a recompile.
5718
5719 elseif arg[1] == "again" then
5720 loadconf ()
5721 updateanddone ()
5722
5723
5724 -- lwarpmk clean:
5725 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
5726
5727 elseif arg[1] == "clean" then
5728 loadconf ()
5729 removeaux ()
5730 print ("lwarpmk: Done.")
5731
5732
```

```
5733 -- lwarpmk cleanall
5734 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
5735 -- and also project.pdf, project.dvi, *.html
5736
5737 elseif arg[1] == "cleanall" then
5738 loadconf ()
5739 removeaux ()
5740 os.execute (rmname .. " " ..
5741 sourcename .. ".pdf " .. sourcename .. "_html.pdf " ..
5742 sourcename .. ".dvi " .. sourcename .. "_html.dvi " ..
5743 "*.html"
5744)
5745 print ("lwarpmk: Done.")
5746
5747
5748 -- lwarpmk cleanimages
5749 -- Remove images from the imagesdirectory.
5750
5751 elseif arg[1] == "cleanimages" then
5752 loadconf ()
5753 os.execute (rmname .. " " .. imagesdirectory .. dirslash .. "*")
5754 print ("lwarpmk: Done.")
5755
5756 -- lwarpmk epstopdf <list of file names>
5757 -- Convert EPS files to PDF using epstopdf
5758 elseif arg[1] == "epstopdf" then
5759 convertepstopdf ()
5760 print ("lwarpmk: Done.")
5761
5762
5763 -- lwarpmk pdftosvg <list of file names>
5764 -- Convert PDF files to SVG using pdftocairo
5765 elseif arg[1] == "pdftosvg" then
5766 convertpdftosvg ()
5767 print ("lwarpmk: Done.")
5768
5769
5770 -- lwarpmk with no argument :
5771
5772 elseif (arg[1] == nil) then
5773 printhelp ()
5774
5775
5776 -- lwarpmk -v:
5777
5778 elseif (arg[1] == "-v") then
5779 -- The version number has already been printed
5780 -- by the lwarpmk intro.
5781
5782 -- lwarpmk -h or lwarpmk --help :
5783
5784 elseif (arg[1] == "-h") or (arg[1] == "--help") then
5785 printusage ()
5786
5787
5788 -- Unknown command:
5789
5790 else
5791 printhelp ()
5792 print ("\nlwarpmk: ***** Unknown command \"\"..arg[1]..\"\". *****\n")
```

```

5793 end
5794
5795 end -- not --version
5796 \end{filecontents*}
5797 % \end{Verbatim}% for syntax highlighting

5798 \end{LWRcreateLwarpmk}

```

## 41 Stacks

**for HTML output:** 5799 \begin{warpHTML}



Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (un-nested) in proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new `\section` would close any currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an `\enumerate`, for example. Depths to be recorded in `\LWR@closedepthone`, etc.

### 41.1 Assigning depths

initial depths for empty stack entries:

```
5800 \newcommand*\LWR@depthnone}{-5}
```

All sectioning depths are deeper than `LWR@depthfinished`:

```

5801 \newcommand*\LWR@depthfinished}{-4}
5802 \newcommand*\LWR@depthbook}{-2}
5803 \newcommand*\LWR@depthpart}{-1}
5804 \newcommand*\LWR@depthchapter}{0}
5805 \newcommand*\LWR@depthsection}{1}
5806 \newcommand*\LWR@depthsubsection}{2}
5807 \newcommand*\LWR@depthsubsubsection}{3}
5808 \newcommand*\LWR@depthparagraph}{4}
5809 \newcommand*\LWR@depthsubparagraph}{5}

```

Used by `\itemize`, `\enumerate`, `\description`:

```
5810 \newcommand*\LWR@depthlist}{6}
```

Used by `\item`:

```

5811 \newcommand*\LWR@depthlistitem}{7}
5812 \let\LWR@depthdescitem\LWR@depthlistitem

```

## 41.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to `\pushclose` and `\popclose` as well.

```

5813 \newcommand*\LWR@closeone{}% top of the stack
5814 \newcommand*\LWR@closetwo{}
5815 \newcommand*\LWR@closethree{}
5816 \newcommand*\LWR@closefour{}
5817 \newcommand*\LWR@closefive{}
5818 \newcommand*\LWR@closesix{}
5819 \newcommand*\LWR@closeseven{}
5820 \newcommand*\LWR@closeeight{}
5821 \newcommand*\LWR@closenine{}
5822 \newcommand*\LWR@closeten{}
5823 \newcommand*\LWR@closeeleven{}
5824 \newcommand*\LWR@closetwelve{}
5825 \newcommand*\LWR@closethirteen{}
5826 \newcommand*\LWR@closefourteen{}
5827 \newcommand*\LWR@closefifteen{}
5828 \newcommand*\LWR@closesixteen{}
5829 \newcommand*\LWR@closeseventeen{}
5830 \newcommand*\LWR@closeeighteen{}
5831 \newcommand*\LWR@closeineteen{}

```

## 41.3 Closing depths

A stack to record the depth of each level:



Note that nested L<sup>A</sup>T<sub>E</sub>X structures may push depths which are non-sequential.

*Ex:*

---

```

\begin{itemize}
 \item{A}
 \begin{description}
 \item{B}
 \end{description}
\end{itemize}

```

---

```

5832 \newcommand*\LWR@closedepthone{\LWR@depthnone}% top of the stack
5833 \newcommand*\LWR@closedepthtwo{\LWR@depthnone}
5834 \newcommand*\LWR@closedepththree{\LWR@depthnone}
5835 \newcommand*\LWR@closedepthfour{\LWR@depthnone}
5836 \newcommand*\LWR@closedepthfive{\LWR@depthnone}
5837 \newcommand*\LWR@closedepthsix{\LWR@depthnone}
5838 \newcommand*\LWR@closedepthseven{\LWR@depthnone}
5839 \newcommand*\LWR@closedeptheight{\LWR@depthnone}
5840 \newcommand*\LWR@closedepthnine{\LWR@depthnone}
5841 \newcommand*\LWR@closedepthten{\LWR@depthnone}
5842 \newcommand*\LWR@closedepthleven{\LWR@depthnone}
5843 \newcommand*\LWR@closedepthtwelve{\LWR@depthnone}
5844 \newcommand*\LWR@closedepththirteen{\LWR@depthnone}
5845 \newcommand*\LWR@closedepthfourteen{\LWR@depthnone}

```

```

5846 \newcommand*\LWR@closedepthfifteen{\LWR@depthnone}
5847 \newcommand*\LWR@closedepthsixteen{\LWR@depthnone}
5848 \newcommand*\LWR@closedepthseventeen{\LWR@depthnone}
5849 \newcommand*\LWR@closedeptheighteen{\LWR@depthnone}
5850 \newcommand*\LWR@closedepthnineteen{\LWR@depthnone}

```

## 41.4 Pushing and popping the stack

`\LWR@pushclose` {<*sectiontype*>}

Pushes one return action and its L<sup>A</sup>T<sub>E</sub>X depth onto the stacks.

```

5851 \NewDocumentCommand{\LWR@pushclose}{m}
5852 {%
5853 \global\let\LWR@closeynineteen\LWR@closeeighteen%
5854 \global\let\LWR@closeeighteen\LWR@closeeseventeen%
5855 \global\let\LWR@closeeseventeen\LWR@closesixteen%
5856 \global\let\LWR@closesixteen\LWR@closefifteen%
5857 \global\let\LWR@closefifteen\LWR@closefourteen%
5858 \global\let\LWR@closefourteen\LWR@closethirteen%
5859 \global\let\LWR@closethirteen\LWR@closetwelve%
5860 \global\let\LWR@closetwelve\LWR@closeeleven%
5861 \global\let\LWR@closeeleven\LWR@closeten%
5862 \global\let\LWR@closeten\LWR@closeynine%
5863 \global\let\LWR@closeynine\LWR@closeeight%
5864 \global\let\LWR@closeeight\LWR@closeseven%
5865 \global\let\LWR@closeseven\LWR@closesix%
5866 \global\let\LWR@closesix\LWR@closefive%
5867 \global\let\LWR@closefive\LWR@closefour%
5868 \global\let\LWR@closefour\LWR@closethree%
5869 \global\let\LWR@closethree\LWR@closetwo%
5870 \global\let\LWR@closetwo\LWR@closeone%
5871 \global\csletcs{LWR@closeone}{LWR@printclose#1}%
5872 \global\let\LWR@closedepthnineteen\LWR@closedeptheighteen%
5873 \global\let\LWR@closedeptheighteen\LWR@closedepthseventeen%
5874 \global\let\LWR@closedepthseventeen\LWR@closedepthsixteen%
5875 \global\let\LWR@closedepthsixteen\LWR@closedepthfifteen%
5876 \global\let\LWR@closedepthfifteen\LWR@closedepthfourteen%
5877 \global\let\LWR@closedepthfourteen\LWR@closedepththirteen%
5878 \global\let\LWR@closedepththirteen\LWR@closedepthtwelve%
5879 \global\let\LWR@closedepthtwelve\LWR@closedeptheleven%
5880 \global\let\LWR@closedeptheleven\LWR@closedepthten%
5881 \global\let\LWR@closedepthten\LWR@closedepthnine%
5882 \global\let\LWR@closedepthnine\LWR@closedeptheight%
5883 \global\let\LWR@closedeptheight\LWR@closedepthseven%
5884 \global\let\LWR@closedepthseven\LWR@closedepthsix%
5885 \global\let\LWR@closedepthsix\LWR@closedepthfive%
5886 \global\let\LWR@closedepthfive\LWR@closedepthfour%
5887 \global\let\LWR@closedepthfour\LWR@closedepththree%
5888 \global\let\LWR@closedepththree\LWR@closedepthtwo%
5889 \global\let\LWR@closedepthtwo\LWR@closedepthone%
5890 \global\csletcs{LWR@closedepthone}{LWR@depth#1}%

```

Error if the deepest depth is no longer `\LWR@depthnone`, which means that it somehow has been nested too deeply, or things are not being unnested correctly.

```

5891 \ifdefstring{\LWR@closedepthnineteen}{\LWR@depthnone}%
5892 {%

```

```

5893 {%
5894 \PackageError{lwarp}%
5895 {The document is nested too deeply for Lwarp}%
5896 {PLEASE inform the Lwarp maintainer!}%
5897 }%
5898 }

```

`\LWR@popclose` Pops one action and its depth off the stacks.

```

5899 \newcommand*{\LWR@popclose}
5900 {%
5901 \global\let\LWR@closeone\LWR@closestwo%
5902 \global\let\LWR@closestwo\LWR@closesthree%
5903 \global\let\LWR@closesthree\LWR@closefour%
5904 \global\let\LWR@closefour\LWR@closefive%
5905 \global\let\LWR@closefive\LWR@closesix%
5906 \global\let\LWR@closesix\LWR@closeseven%
5907 \global\let\LWR@closeseven\LWR@closeeight%
5908 \global\let\LWR@closeeight\LWR@closeenine%
5909 \global\let\LWR@closeenine\LWR@closeeten%
5910 \global\let\LWR@closeeten\LWR@closeeleven%
5911 \global\let\LWR@closeeleven\LWR@closeetwelve%
5912 \global\let\LWR@closeetwelve\LWR@closeethirteen%
5913 \global\let\LWR@closeethirteen\LWR@closefourteen%
5914 \global\let\LWR@closefourteen\LWR@closefifteen%
5915 \global\let\LWR@closefifteen\LWR@closesixteen%
5916 \global\let\LWR@closesixteen\LWR@closeseventeen%
5917 \global\let\LWR@closeseventeen\LWR@closeeighteen%
5918 \global\let\LWR@closeeighteen\LWR@closeenineteen%
5919 \global\let\LWR@closedepthone\LWR@closedepthtwo%
5920 \global\let\LWR@closedepthtwo\LWR@closedepththree%
5921 \global\let\LWR@closedepththree\LWR@closedepthfour%
5922 \global\let\LWR@closedepthfour\LWR@closedepthfive%
5923 \global\let\LWR@closedepthfive\LWR@closedepthsix%
5924 \global\let\LWR@closedepthsix\LWR@closedepthseven%
5925 \global\let\LWR@closedepthseven\LWR@closedeptheight%
5926 \global\let\LWR@closedeptheight\LWR@closedepthnine%
5927 \global\let\LWR@closedepthnine\LWR@closedephten%
5928 \global\let\LWR@closedephten\LWR@closedeptheleven%
5929 \global\let\LWR@closedeptheleven\LWR@closedephtwelve%
5930 \global\let\LWR@closedephtwelve\LWR@closedepththirteen%
5931 \global\let\LWR@closedepththirteen\LWR@closedepthfourteen%
5932 \global\let\LWR@closedepthfourteen\LWR@closedepthfifteen%
5933 \global\let\LWR@closedepthfifteen\LWR@closedepthsixteen%
5934 \global\let\LWR@closedepthsixteen\LWR@closedepthseventeen%
5935 \global\let\LWR@closedepthseventeen\LWR@closedeptheighteen%
5936 \global\let\LWR@closedeptheighteen\LWR@closedepthnineteen%
5937 }

5938 \end{warpHTML}

```

## 42 Data arrays

These macros are similar to the `arrayjobx` package, except that `\LWR@setexparray`'s argument is expanded only once when assigned.

name has no backslash, index can be a number or a text name, and an empty value must be `\relax` instead of empty.

To assign an empty value:

```
\LWR@setexparray{name}{index}{}
```

**for HTML output:** 5939 `\begin{warpHTML}`

```
\LWR@setexparray {<name>} {<index>} {<contents>}
```

```
5940 \newbool{LWR@setexparray@doingparhooks}
5941
5942 \NewDocumentCommand{\LWR@setexparray}{m m m}{%
```

Temporarily disable paragraph handling during the assignment. This is not done in a group with global assignments because a table may be nested.

```
5943 \let\ifLWR@setexparray@doingparhooks\ifLWR@doingparhooks%
5944 \setbool{LWR@doingparhooks}{false}%
5945 \let\LWR@setexparray@par\par%
5946 \let\par\relax%
```

The name of the control sequence is the given name with the index appended.

```
5947 \xdef\LWR@thisexparrayname{#1#2}%
```

Locally assign the value to the control sequence:

```
5948 \ifstrempy{#3}%
5949 {\csdef{\LWR@thisexparrayname}{}}%
5950 {\csdef{\LWR@thisexparrayname}{#3}}%
```

Restore the paragraph handling:

```
5951 \let\ifLWR@doingparhooks\ifLWR@setexparray@doingparhooks%
5952 \let\par\LWR@setexparray@par%
5953 }
```

```
\LWR@getexparray {<name>} {<index>}
```

```
5954 \newcommand*{\LWR@getexparray}[2]{%
5955 \@nameuse{#1#2}%
5956 }
```

```
5957 \end{warpHTML}
```

## 43 Localizing catcodes

**for HTML & PRINT:** 5958 `\begin{warpall}`

 **Misplaced alignment tab character &** Place `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error  
 Misplaced alignment tab character &.

`\StartDefiningTabulars` Place before defining something with & in it.

```
5959 \newcommand{\StartDefiningTabulars}{%
5960 \LWR@traceinfo{StartDefiningTabulars}%
5961 \warpHTMLonly{\catcode'\&=\active}%
5962 }
```

`\StopDefiningTabulars` Place after defining something with & in it.

```
5963 \newcommand{\StopDefiningTabulars}{%
5964 \LWR@traceinfo{StopDefiningTabulars}%
5965 \warpHTMLonly{\catcode'\&=4}%
5966 }
```

Bool `LWR@mathmacro`

True if currently defining math macros. Used to disable SVG math hashing and MATHJAX math contents while defining a macro using inline math. Begin a macro, it is not guaranteed that the contents are static, and so the image must be unique. The contents also almost certainly will not be parsed correctly by MATHJAX.

```
5967 \newbool{LWR@mathmacro}
5968 \boolfalse{LWR@mathmacro}
```

`\StartDefiningMath` Place before defining something with \$ in it.

```
5969 \newcommand{\StartDefiningMath}{%
5970 \LWR@traceinfo{StartDefiningMath}%
5971 \warpHTMLonly{\catcode'\$=\active}%
5972 }
```

`\StopDefiningMath` Place after defining something with \$ in it.

```
5973 \newcommand{\StopDefiningMath}{%
5974 \LWR@traceinfo{StopDefiningMath}%
5975 \warpHTMLonly{\catcode'\$=3}% math shift
5976 }
```

```
5977 \end{warpall}
```

**for HTML output:** 5978 `\begin{warpHTML}`

A definition for & in case it is referred to after `\StartDefiningTabulars` but outside a tabular.

```
5979 \StartDefiningTabulars
5980 \protected\def&{%
5981 \PackageWarning{lwarp}{%
5982 An ampersand is being used inside a tabular\MessageBreak
5983 }%
5984 }%
5985 \StopDefiningTabulars
```

```
5986 \end{warpHTML}
```

## 44 Localizing dynamic math

Inline SVG math usually uses a hash of its contents to generate `lateximages` which are reusable for multiple instances with the same contents. If the contents may change for each use, such as depending on the current value of a counter, then `\inlinemathother` must be used before the inline math expression, and `\inlinemathnormal` must be used after.

For `MATHJAX`, the inline math expression is usually printed for `MATHJAX` to interpret. When marked as dynamic math, the following inline math expression will be displayed as an unhashed inline SVG image instead.

For existing code and packages, it may be possible to patch macros after they have been defined, using the `xpatch` package, which is pre-loaded by `lwarp`:

---

```
\xpatchcmd{\macroname}
 {$math expression$}
 {\inlinemathother$math expression$\inlinemathnormal}
 {}
 {\typeout{Error patching macroname.}}
```

---

**for HTML & PRINT:** 5987 \begin{warpall}

Bool `LWR@dynamicmath` True to mark inline math which is dynamic in nature, thus should not be hashed for reuse.  
 Default: `false`

```
5988 \newbool{LWR@dynamicmath}
5989 \boolfalse{LWR@dynamicmath}
```

`\inlinemathother` Place before using `$ ... $` or `\( ... \)` if the contents of the math are not static, depending on counters or dynamic macros.

```
5990 \newcommand{\inlinemathother}{%
5991 \LWR@traceinfo{inlinemathother}%
5992 \booltrue{LWR@dynamicmath}%
5993 }
```

`\inlinemathnormal` Place after using `$ ... $` or `\( ... \)` with dynamic contents.

```
5994 \newcommand{\inlinemathnormal}{%
5995 \LWR@traceinfo{inlinemathnormal}%
5996 \boolfalse{LWR@dynamicmath}%
5997 }
```

```
5998 \end{warpall}
```

## 45 HTML entities

**for HTML output:** 5999 \begin{warpHTML}

HTML Unicode entities:

```
6000 \let\LWR@origampersand\&
```

```
\LWR@fontfortags {<macro name>} {<argument>}
```

Forces roman TT font for HTML tags.

```
6001 \newrobustcmd*{\LWR@fontfortags}[2]{%
6002 \ifmmode%
6003 \PackageError{lwarp}%
6004 {%
6005 An HTML tag was generated inside math.\MessageBreak
6006 This should never occur.\MessageBreak
6007 Something is broken in Lwarp.\MessageBreak
6008 Enter 'h' for details%
6009 }%
6010 {(Using #1{#2}.)}%
6011 \else%
```

Used by ljtbook, platex, and related.

```
6012 \ifdef{\romanencoding}%
6013 {%
6014 \romanencoding{\encodingdefault}%
6015 }%
6016 {%
```

Used by babel:

```
6017 \ifdef{\latintext}
6018 {\latintext}
6019 {\fontencoding\encodingdefault}%
6020 }%
6021 \LWR@print@normalfont%
6022 \LWR@origttfamily%
6023 \fi%
6024 }
```

```
\HTMLentity {<entitytag>}
```

\protect is in case the tag appears in TOC, LOF, LOT.

```
6025 \newcommand*{\HTMLentity}[1]{%
6026 % \LWR@traceinfo{HTMLentity \detokenize{#1}}%
6027 \begingroup%
6028 \LWR@hook@processingtags%
6029 \LWR@fontfortags{HTMLentity}{\detokenize{#1}}%
6030 \protect\LWR@origampersand\LWR@isoLate{#1};%
6031 \endgroup%
6032 % \LWR@traceinfo{HTMLentity done}%
6033 }
```

```
\HTMLUnicode {<hex_unicode>}
```

```
6034 \newcommand*{\HTMLUnicode}[1]{\HTMLentity{\LWR@origpound{x#1}}
```

```
6035 \renewrobustcmd*{\&}{\HTMLentity{amp}}
```

`\textless`

```
6036 \let\LWR@origtextless\textless
6037 \renewrobustcmd*{\textless}{\HTMLentity{lt}}
```

`\textgreater`

```
6038 \let\LWR@origtextgreater\textgreater
6039 \renewrobustcmd*{\textgreater}{\HTMLentity{gt}}
```

```
6040 \end{warpHTML}
```

## 46 HTML filename generation

The filename of the homepage is set to `\HomeHTMLFilename.html`. The filenames of additional sections start with `\HTMLFilename`, to which is appended a section number or a simplified section name, depending on `FileSectionNames`.

**for HTML & PRINT:** 6041 `\begin{warpall}`

`\BaseJobname` The `\jobname` of the printed version, even if currently compiling the HTML version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLFilename` if the user did not provide one.

```
6042 \providecommand*{\BaseJobname}{\jobname}
```

`\HTMLFilename` The prefix for all generated HTML files other than the home page, defaulting to empty. See section 7.6.1.

```
6043 \providecommand*{\HTMLFilename}{}
```

`\HomeHTMLFilename` The filename of the home page, defaulting to the `\BaseJobname`. See section 7.6.1.

```
6044 \providecommand*{\HomeHTMLFilename}{\BaseJobname}
```

`\SetHTMLFileNumber` `{\langle number \rangle}`

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
6045 \newcommand*{\SetHTMLFileNumber}[1]{%
6046 \setcounter{LWR@htmlfilenumber}{#1}%
6047 }
```

|      |                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Bool | FileSectionNames                      | <p>Selects how to create HTML file names.</p> <p>Defaults to use section names in the filenames.</p> <pre>6048 \newbool{FileSectionNames} 6049 \booltrue{FileSectionNames}</pre> <pre>6050 \end{warpall}</pre> <p><b>for HTML output:</b> <pre>6051 \begin{warpHTML}</pre></p> <p>Updated each time a new HTML file is begun. Used to provide HTML previous/next web page links.</p> <pre>6052 \newcounter{LWR@HTMLpagenum} 6053 \setcounter{LWR@HTMLpagenum}{0}</pre>                                                                                    |
| Ctr  | LWR@htmlseqfilenumber                 | <p>A sequential count of the number of each HTML file as it is being created. Number 0 is the home page. Unlike <code>\LWR@htmlfilenumber</code>, this one is known to increment by one for each file. This is used to generate previous /next links for each web page, via labels called <code>\BaseJobname-autofile-*</code>, and the last page is also labelled <code>\BaseJobname-autofile-last</code>.</p> <pre>6054 \newcounter{LWR@htmlseqfilenumber} 6055 \setcounter{LWR@htmlseqfilenumber}{0}</pre>                                             |
| Bool | LWR@setseqfilelabel                   | <p>At each new HTML file, this is false until a sectional unit is used, at which point this is set true and a label is placed. In this way, the previous/next labels will point to a named section.</p> <pre>6056 \newbool{LWR@setseqfilelabel} 6057 \setbool{LWR@setseqfilelabel}{false}</pre>                                                                                                                                                                                                                                                           |
| Ctr  | LWR@htmlfilenumber                    | <p>Records the number of each HTML file as it is being created. Number 0 is the home page. This might not be sequential, as the user may use <code>\SetHTMLFileNumber</code> to create groups of numbered nodes.</p> <pre>6058 \newcounter{LWR@htmlfilenumber} 6059 \setcounter{LWR@htmlfilenumber}{0}</pre>                                                                                                                                                                                                                                              |
|      | <code>\LWR@htmlsectionfilename</code> | <p><code>{\htmlfilenumber or name}</code></p> <p>Prints the filename for a given section: <code>\HTMLFilename{}filenumber/name.html</code></p> <pre>6060 \newcommand*{\LWR@htmlsectionfilename}[1]{% 6061 \LWR@traceinfo{LWR@htmlsectionfilename A !\detokenize{#1}}% 6062 \begingroup%</pre> <p>Disable CJK xpinyin while generating file names.</p> <pre>6063 \LWR@disablepinyin%</pre> <p>Section 0 or empty is given the home filename. The filename must be detokenized for underscores.</p> <pre>6064 % \LWR@traceinfo{about to assign temp}%</pre> |

```

6065 \LWR@sanitize{#1}%
6066 \LWR@traceinfo{about to compare with ??}%
6067 \ifdefstring{\LWR@sanitized}{??}
6068 {\LWR@traceinfo{found ??}}%
6069 {\LWR@traceinfo{not found ??}}%
6070 \LWR@traceinfo{about to compare with zero or empty}%
6071 \ifboolexpr{
6072 test {\ifdefstring{\LWR@sanitized}{0}} or
6073 test {\ifdefstring{\LWR@sanitized}{}} or
6074 test {\ifdefstring{\LWR@sanitized}{??}}
6075 }
6076 {%
6077 \LWR@traceinfo{LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
6078 \HomeHTMLFilename.html%
6079 }%

```

For a  $\LaTeX$  section named “Index” or “index” without a prefix, create a filename with a trailing `-0` to avoid colliding with the HTML filename `index.html`:

```

6080 {%
6081 \LWR@traceinfo{LWR@htmlsectionfilename C \LWR@sanitized}%
6082 \ifboolexpr{
6083 test{\ifdefvoid{\HTMLFilename}} and
6084 (
6085 test{\ifdefstring{\LWR@sanitized}{Index}} or
6086 test{\ifdefstring{\LWR@sanitized}{index}}
6087)
6088 }%
6089 {%
6090 \LWR@traceinfo{Adding a zero to the index filename.}%
6091 \LWR@sanitized-0.html%
6092 }%

```

Otherwise, create a filename with the chosen prefix:

```

6093 {%
6094 \HTMLFilename\LWR@isolate{\LWR@sanitized}.html%
6095 }%
6096 }%
6097 \LWR@traceinfo{LWR@htmlsectionfilename Z}%
6098 \endgroup%
6099 }

```

`\LWR@htmlrefsectionfilename`  $\{\langle label \rangle\}$

Prints the filename for the given label

```

6100 \newcommand*{\LWR@htmlrefsectionfilename}[1]{%
6101 \LWR@traceinfo{LWR@htmlrefsectionfilename: !\detokenize{#1}!}%

```

`\LWR@nullfonts` to allow math in a section name.

```

6102 \begingroup%
6103 \LWR@nullfonts%
6104 \LWR@htmlsectionfilename{\LWR@htmlfileref{#1}}%
6105 \endgroup%
6106 \LWR@traceinfo{LWR@htmlrefsectionfilename: done}%
6107 }

```

```
6108 \end{warpHTML}
```

## 47 Homepage link

**for HTML & PRINT:** 6109 \begin{warpall}

`\linkhomename` Holds the default name for the home link.

```
6110 \newcommand{\linkhomename}{Home}
```

```
6111 \end{warpall}
```

**for HTML output:** 6112 \begin{warpHTML}

`\LinkHome` May be used wherever you wish to place a link back to the homepage. The filename must be detokenized for underscores.

```
6113 \newcommand*\LinkHome{%
```

```
6114 \LWR@subhyperrefclass{\HomeHTMLfilename.html}{\linkhomename}{linkhome}%
```

```
6115 }
```

```
6116 \end{warpHTML}
```

**for PRINT output:** 6117 \begin{warpprint}

`\LinkHome` May be used wherever you wish to place a link back to the homepage. For print output, if `hyperref` is available a hyperlink to the first page is used, named by `\linkhomename`. If `hyperref` is not available, a `pageref` is used instead.

`\BaseJobname` is included in the link label in case multiple documents are cross-referenced.

```
6118 \AtBeginDocument{
```

```
6119 \@ifundefined{hyperref}{
```

```
6120 \newcommand*\LinkHome{%
```

```
6121 \linkhomename\ --- page \pageref{\BaseJobname-page-LWRfirstpage}%
```

```
6122 }
```

```
6123 }{
```

```
6124 \newcommand*\LinkHome{%
```

```
6125 \hyperref[\BaseJobname-page-LWRfirstpage]{\linkhomename}%
```

```
6126 }
```

```
6127 }
```

```
6128 }
```

```
6129 }
```

```
6130 \AfterEndPreamble{\label{\BaseJobname-page-LWRfirstpage}}
```

```
6131 \end{warpprint}
```

**for HTML output:** 6132 \begin{warpHTML}

`\LWR@topnavigation` Creates a link to the homepage at the top of the page for use when the window is too narrow for the sideroc.

```

6133 \newcommand*\LWR@topnavigation}{%
6134 \LWR@html@elementclassline{nav}{topnavigation}{\LinkHome}
6135 }

```

`\LWR@botnavigation` Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sideroc.

```

6136 \newcommand*\LWR@botnavigation}{%
6137 \LWR@html@elementclassline{nav}{botnavigation}{\LinkHome}
6138 }

```

```
6139 \end{warpHTML}
```

## 48 Previous/next navigation links

**for HTML & PRINT:** 6140 `\begin{warpall}`

`\Linkpreviousname` What to call the link to the previous web page.

```
6141 \newcommand*\Linkpreviousname}{Previous}
```

`\Linknextname` What to call the link to the next web page.

```
6142 \newcommand*\Linknextname}{Next}
```

```
6143 \end{warpall}
```

**for PRINT output:** 6144 `\begin{warpprint}`

`\LinkPrevious` Creates a link to the previous web page if there is one.

```
6145 \newcommand*\LinkPrevious}{}
```

`\LinkNext` Creates a link to the next web page if there is one.

```
6146 \newcommand*\LinkNext}{}
```

```
6147 \end{warpprint}
```

**for HTML output:** 6148 `\begin{warpHTML}`

`\LinkPrevious` Creates a link to the previous web page if there is one.

The links refer to the L<sup>A</sup>T<sub>E</sub>X labels `\Basejobname-autofile-*`

```

6149 \newcommand*\LinkPrevious}{%
6150 \ifnumless{\value{LWR@htmlseqfilenumber}}{1}}{1}}{%
6151 \setcounter{LWR@tempcountone}{\value{LWR@htmlseqfilenumber}-1}%
6152 \LWR@subhyperrefclass{%
6153 \LWR@htmlrefsectionfilename{%
6154 \Basejobname-autofile-\arabic{LWR@tempcountone}%

```

```

6155 }%
6156 }{\linkpreviousname}{linkhome}%
6157 }%
6158 }

```

`\LinkNext` Creates a link to the next web page if there is one.

The links refer to the L<sup>A</sup>T<sub>E</sub>X labels `\Basejobname-autofile-*` and the last is the label `\Basejobname-autofile-last`

```

6159 \newcommand*{\LinkNext}{%
6160 \ifcsdef{r@\BaseJobname-autofile-last@lwarp}{%
6161 \edef\LWR@tempone{%
6162 \LWR@htmlfileref{\BaseJobname-autofile-\arabic{LWR@htmlseqfilenumber}}}%
6163 }%
6164 \edef\LWR@temptwo{%
6165 \LWR@htmlfileref{\BaseJobname-autofile-last}%
6166 }%
6167 \ifdefequal{\LWR@tempone}{\LWR@temptwo}{}{%
6168 \setcounter{LWR@tempcountone}{\value{LWR@htmlseqfilenumber}+1}%
6169 \LWR@subhyperrefclass{%
6170 \LWR@htmlrefsectionfilename{%
6171 \BaseJobname-autofile-\arabic{LWR@tempcountone}}%
6172 }%
6173 }{\linknextname}{linkhome}%
6174 }%
6175 }{}%
6176 }

6177 \end{warpHTML}

```

## 49 \LWRPrintStack diagnostic tool



Diagnostics tool: Prints the L<sup>A</sup>T<sub>E</sub>X nesting depth values for the stack levels. `\LWR@startpars` is used before printing the stack, so that `\LWRPrintStack` may be called from anywhere in the normal text flow.

**for HTML output:** `6178 \begin{warpHTML}`

`\LWRPrintStack` Prints the closedepth stack.

```

6179 \newcommand*{\LWR@subprintstack}{
6180 \LWR@closedepthone\ \LWR@closedepthtwo\ \LWR@closedepththree\
6181 \LWR@closedepthfour\ \LWR@closedepthfive\ \LWR@closedepthsix\
6182 \LWR@closedepthseven\ \LWR@closedeptheight\ \LWR@closedepthnine\
6183 \LWR@closedephten\ \LWR@closedeptheleven\ \LWR@closedephtwelve\
6184 \LWR@closedepththirteen\ \LWR@closedepthfourteen\ \LWR@closedepthfifteen\
6185 \LWR@closedepthsixteen\ \LWR@closedepthseventeen\ \LWR@closedeptheighteen\
6186 \LWR@closedepthnineteen\
6187 }
6188
6189 \newcommand*{\LWRPrintStack}{
6190 \LWR@startpars
6191 \LWR@subprintstack
6192 }

```

```
6193 \end{warpHTML}
```

**for PRINT output:** 6194 \begin{warpprint}

```
6195 \newcommand*\LWRPrintStack{}
```

```
6196 \end{warpprint}
```

## 50 Closing stack levels

**for HTML output:** 6197 \begin{warpHTML}

Close one nested level:

```
6198 \newcommand*\LWR@closeoneprevious}{%
6199
6200 \LWR@closeone
6201
6202 \LWR@popclose
6203 }
```

`\LWR@closeprevious` `{\sectintype}` Close everything up to the given depth:

```
6204 \newcommand*\LWR@closeprevious}[1]{%
6205 \LWR@traceinfo{%
6206 \LWR@closeprevious to depth \csuse{\LWR@depth#1}, %
6207 depths are \LWR@subprintstack%
6208 }%
```

Close any pending paragraph:

```
6209 \LWR@stoppars%
```

Close anything nested deeper than the desired depth. First close anything deeper, then at most one of the same level.

```
6210 \whileboolexpr{test{\ifnumcomp{\LWR@closedepthone}{>}{\csuse{\LWR@depth#1}}}}%
6211 {%
6212 \LWR@traceinfo{\LWR@closeprevious: closing out depth \LWR@closedepthone}%
6213 \LWR@closeoneprevious%
6214 }%
6215 \ifboolexpr{test{\ifnumcomp{\LWR@closedepthone}{=}{\csuse{\LWR@depth#1}}}}%
6216 {%
6217 \LWR@traceinfo{\LWR@closeprevious: closing out depth \LWR@closedepthone}%
6218 \LWR@closeoneprevious%
6219 }{ }%
6220 \LWR@traceinfo{\LWR@closeprevious: done, depths are \LWR@subprintstack}%
6221 }
```

```
6222 \end{warpHTML}
```

## 51 PDF pages and styles

**for HTML output:** 6223 \begin{warpHTML}

\LWR@forcenewpage New PDF page a before major environment.

This is used just before major environments, such as verse. Reduces the chance of an environment overflowing the HTML PDF output page.

```
6224 \newcommand{\LWR@forcenewpage}{%
6225 \LWR@traceinfo{\LWR@forcenewpage}%
6226 \ifinner\else%
6227 \LWR@traceinfo{\LWR@forcenewpage A}%
6228 \LWR@stoppars%
6229 \LWR@traceinfo{\LWR@forcenewpage B}%
6230 \LWR@maybe@orignewpage%
6231 \LWR@traceinfo{\LWR@forcenewpage C}%
6232 \LWR@startpars%
6233 \fi%
6234 \LWR@traceinfo{\LWR@forcenewpage done}%
6235 }
```

\pagestyle, etc. are nullified for HTML output.

\pagestyle {<style>}

```
6236 \renewcommand*\pagestyle[1]{}
```

\thispagestyle {<style>}

```
6237 \renewcommand*\thispagestyle[1]{}
```

\markboth {<left>} {<right>}

```
6238 \renewcommand*\markboth[2]{}
```

\markright {<right>}

```
6239 \renewcommand*\markright[1]{}
```

\raggedbottom

```
6240 \renewcommand*\raggedbottom{}
```

\flushbottom

```
6241 \renewcommand*\flushbottom{}
```

\sloppy

```
6242 \renewcommand*\sloppy{}
```

\fussy

```
6243 \renewcommand*{\fussy}{}
```

\pagenumbering \* {<commands>}

```
6244 \RenewDocumentCommand{\pagenumbering}{s m}{}

6245 \end{warpHTML}
```

## 52 HTML tags, spans, divs, elements

for HTML output: 6246 \begin{warpHTML}

### 52.1 Mapping L<sup>A</sup>T<sub>E</sub>X sections to HTML sections

```
6247 \newcommand*{\LWR@tagtitle}{h1}
6248 \newcommand*{\LWR@tagtitleend}{/h1}
6249 \newcommand*{\LWR@tagbook}{div class=\textquotedbl{}book\textquotedbl}
6250 \newcommand*{\LWR@tagbookend}{/div}
6251 \newcommand*{\LWR@tagpart}{h2}
6252 \newcommand*{\LWR@tagpartend}{/h2}
6253 \newcommand*{\LWR@tagchapter}{h3}
6254 \newcommand*{\LWR@tagchapterend}{/h3}
6255 \newcommand*{\LWR@tagsection}{h4}
6256 \newcommand*{\LWR@tagsectionend}{/h4}
6257 \newcommand*{\LWR@tagsubsection}{h5}
6258 \newcommand*{\LWR@tagsubsectionend}{/h5}
6259 \newcommand*{\LWR@tagsubsubsection}{h6}
6260 \newcommand*{\LWR@tagsubsubsectionend}{/h6}
6261 \newcommand*{\LWR@tagparagraph}{span class=\textquotedbl{}paragraph\textquotedbl}
6262 \newcommand*{\LWR@tagparagraphend}{/span}
6263 \newcommand*{\LWR@tagsubparagraph}{span class=\textquotedbl{}subparagraph\textquotedbl}
6264 \newcommand*{\LWR@tagsubparagraphend}{/span}
6265
6266 \newcommand*{\LWR@tagregularparagraph}{p}
```

### 52.2 Hook while processing tags

Hook [lwarp] This is used to disable special text processing while processing HTML tags. Special processing includes that done by babel-french, luavina, xeVna.

\LWR@hook@processingtags

\LWR@hook@processingtags Disable special text processing while generating tags. Replaces \LWR@FBcancel in most places.

```
6267 \newcommand*{\LWR@hook@processingtags}{}

6268 \end{warpHTML}
```

### 52.3 Babel-French tag modifications

Adjust babel-french for HTML spaces. So far, this only works for *pdf<sub>l</sub>atex* and *xelatex*.

*(Emulates or patches code by DANIEL FLIPO.)*

```
6268 \providecommand*\LWR@FBcancel{}{}
6269
6270 \AtBeginDocument{%
```

In some circumstances, `\NoAutoSpacing` may be defined when `\frenchbsetup` is not.

```
6271 \@ifundefined{NoAutoSpacing}%
6272 {}%
6273 {%
6274 \LetLtxMacro\LWR@FBcancel\NoAutoSpacing%
6275 \appto{\LWR@hook@processingtags}{\LWR@FBcancel}%
6276 }%
6277
6278 \@ifundefined{frenchbsetup}%
6279 {}%
6280 {%
6281 \frenchbsetup{FrenchFootnotes=false}%

6282 %
6283 \renewrobustcmd*\FBcolonspace{%
6284 \begingroup%
6285 \LWR@hook@processingtags%
6286 \LWR@origampersand{} \, %
6287 \endgroup%
6288 }%
6289 \renewrobustcmd*\FBthinspace{%
6290 \begingroup%
6291 \LWR@hook@processingtags%
6292 \LWR@origampersand\LWR@origpound{x202f;% \,
6293 \endgroup%
6294 }%
6295 \renewrobustcmd*\FBguillspace{%
6296 \begingroup%
6297 \LWR@hook@processingtags%
6298 \LWR@origampersand{} \, for \og xyz \fg{}
6299 \endgroup%
6300 }%
6301 \DeclareDocumentCommand{\FBmedkern}{}{}%
6302 \begingroup%
6303 \LWR@hook@processingtags%
6304 \LWR@origampersand\LWR@origpound{x202f;% \,
6305 \endgroup%
6306 }%
6307 \DeclareDocumentCommand{\FBthickkern}{}{}%
6308 \begingroup%
6309 \LWR@hook@processingtags%
6310 \LWR@origampersand{} \, ~
6311 \endgroup%
6312 }%
6313 \renewrobustcmd*{~}{\HTMLentity{nbsp}}% was overwritten by babel-french
6314 \ifFBunicode%
6315 \else%
6316 \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
6317 \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
6318 \fi%
6319 }%
```

6320 }

## 52.4 HTML output formatting

Helps format the output HTML code for human readability.

`\LWR@indentHTML` Newline and indent the output HTML code.

```
6321 \newcommand*{\LWR@indentHTML}{%
6322 \LWR@orignewline\LWR@origrule{2em}{0pt}%
6323 }
```

`\LWR@indentHTMLtwo` Newline and indent the output HTML code.

```
6324 \newcommand*{\LWR@indentHTMLtwo}{%
6325 \LWR@orignewline\LWR@origrule{4em}{0pt}%
6326 }
```

## 52.5 HTML tags

`\LWR@htmltagc` `{\tag}` Break ligatures and use upright apostrophes in HTML tags.

`\protect` is in case the tag appears in TOC, LOF, LOT.

```
6327 \newcommand*{\LWR@htmltagc}[1]{%
6328 \LWR@traceinfo{\LWR@htmltagc !\detokenize{#1}!}%
6329 \begingroup%
6330 \LWR@hook@processingtags%
6331 \LWR@fontfortags{\LWR@htmltagc}{\detokenize{#1}}%
6332 \protect\LWR@origtextless%
6333 \LWR@isolate{#1}%
6334 \protect\LWR@origtextgreater%
6335 \endgroup%
6336 }
```

`\LWR@spanwarnformat` `{\object}`

Warns if the given object is used inside a span.

```
6337 \newcommand*{\LWR@spanwarnformat}[1]{%
6338 \ifnumcomp{\value{\LWR@spandepth}}{>}{0}{%
6339 \PackageWarning{lwarp}{%
6340 A #1 is being used inside a span.\MessageBreak
6341 Formatting may be lost,%
6342 }%
6343 }{%
6344 }
```

`\LWR@spanwarninvalid` `{\object}`

Warns if the given object is used inside a span.

```
6345 \newcommand*{\LWR@spanwarninvalid}[1]{%
```

```

6346 \ifnumcomp{\value{LWR@spandepth}}{>}{0}{%
6347 \PackageWarning{lwarp}{%
6348 A #1 is being used inside a span.\MessageBreak
6349 This generates invalid HTML,%
6350 }%
6351 }{%
6352 }

```

Env LWR@nestspan Disable minipage, \parbox, and HTML <div>s inside a <span>.

- ⚠ \begin{LWR@nestspan} must follow the opening <span> tag to allow a paragraph to start if the span is at the beginning of a new paragraph.
- ⚠ \end{LWR@nestspan} must follow the </span> or a <p> may appear inside the span.

```

6353 \newcommand*\LWR@nestspanitem}{%
6354 \if@newlist\else{
6355 \LWR@htmltagc{br /}%
6356 \LWR@orignewline%
6357 }\fi%
6358 \LWR@origitem%
6359 }
6360
6361 \newenvironment*LWR@nestspan}
6362 {%
6363 \LWR@traceinfo{LWR@nestspan starting}%
6364 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}{%
6365 {%
6366 \LWR@traceinfo{LWR@nestspan: inside a lateximage}%
6367 }%
6368 {% not in a lateximage
6369 \LWR@traceinfo{LWR@nestspan: NOT inside a lateximage}%
6370 \addtocounter{LWR@spandepth}{1}%

```

Nullify several objects inside the span:

```

6371 \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}%
6372 {\LWR@spanwarnformat{minipage or \protect\parbox}}%
6373 {}%
6374 \RenewDocumentEnvironment{BlockClass}{o m}%
6375 {\LWR@spanwarnformat{multi-paragraph object}}%
6376 {}%
6377 \RenewDocumentEnvironment{LWR@BlockClassWP}{m m D(){} m}%
6378 {\LWR@spanwarnformat{multi-paragraph object}}%
6379 {}%
6380 \renewcommand{\BlockClassSingle}[2]{%
6381 {\LWR@spanwarnformat{multi-paragraph object}}%
6382 ##2%
6383 }%
6384 \renewcommand{\LWR@forcenewpage}{}%
6385 \renewcommand{\LWR@liststart}{\LetLtxMacro\item\LWR@nestspanitem}%
6386 \renewcommand{\LWR@listend}{\leavevmode}%
6387 \renewenvironment{quote}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
6388 \renewenvironment{quotation}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
6389 }% not in a lateximage
6390 \LWR@traceinfo{LWR@nestspan starting: done}%
6391 }% starting env
6392 {% ending env

```

```

6393 \LWR@traceinfo{LWR@nestspan ending}%
6394 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
6395 }%
6396 {\addtocounter{LWR@spandepth}{-1}}%
6397 \LWR@traceinfo{LWR@nestspan ending: done}%
6398 }

```

`\LWR@htmlspan` {<tag>} {<text>}



`\LWR@spandepth` is used to ensure that paragraph tags are not generated inside a span. The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```

6399 \NewDocumentCommand{\LWR@htmlspan}{m +m}{%
6400 \LWR@ensuredoingapar%
6401 \LWR@htmltagc{#1}%
6402 \begin{LWR@nestspan}%
6403 #2%
6404 \LWR@htmltagc{/#1}%
6405 \end{LWR@nestspan}%
6406 }

```

`\LWR@htmlspanclass` [*style*] (<aria role>) {<class>} {<text>}

```

6407 \NewDocumentCommand{\LWR@htmlspanclass}{o D(){} m +m}{%
6408 \LWR@traceinfo{LWR@htmlspanclass |#1|#2|#3|}%
6409 \LWR@ensuredoingapar%
6410 \ifblank{#2}%
6411 {\LWR@subhtmlclass{span}[#1]{#3}}%
6412 {\LWR@subhtmlclass{span}[#1](#2){#3}}%
6413 \begin{LWR@nestspan}%
6414 #4%
6415 \LWR@htmltagc{/span}%
6416 \LWR@traceinfo{LWR@htmlspanclass done}%
6417 \end{LWR@nestspan}%
6418 }

```

`\LWR@htmltag` {<tag>}

Print an HTML tag: <tag>

```

6419 \newcommand*{\LWR@htmltag}[1]{%
6420 \LWR@htmltagc{#1}%
6421 }

```

## 52.6 Block tags and comments

In the following, `\origttfamily` breaks ligatures, which may not be used for HTML codes:

`\LWR@htmlopencomment`  
`\LWR@htmlclosecomment`

```

6422 \newcommand*{\LWR@htmlopencomment}{%
6423 % \LWR@traceinfo{LWR@htmlopencomment}%
6424 \begingroup%

```

```

6425 \LWR@hook@processingtags%
6426 \LWR@fontfortags{\LWR@htmlcomment}{}%
6427 \LWR@print@embox{\LWR@origtextless{!-\/-}%
6428 \endgroup%
6429 }
6430
6431 \newcommand*\LWR@htmlclosecomment}{%
6432 % \LWR@traceinfo{\LWR@htmlclosecomment}%
6433 \begingroup%
6434 \LWR@hook@processingtags%
6435 \LWR@fontfortags{\LWR@htmlclosecomment}{}%
6436 \LWR@print@embox{-\/-\LWR@origtextgreater}%
6437 \endgroup%
6438 }

```

`\LWR@htmlcomment` {<*comment*>}

```

6439 \newcommand{\LWR@htmlcomment}[1]{%
6440 \ifmode%
6441 \else%
6442 \LWR@htmlcomment{}%
6443 {%
6444 \LWR@print@normalfont%
6445 \LWR@origttfamily% break ligatures
6446 #1%
6447 }%
6448 \LWR@htmlclosecomment{}%
6449 \fi%
6450 }

```

`\LWR@htmlblockcomment` {<*comment*>}

```

6451 \newcommand{\LWR@htmlblockcomment}[1]
6452 {\LWR@stoppars\LWR@htmlcomment{#1}\LWR@startpars}

```

`\LWR@htmlblocktag` {<*tag*>} print a stand-alone HTML tag

```

6453 \newcommand*\LWR@htmlblocktag}[1]{%
6454 \LWR@stoppars%
6455 \LWR@htmltag{#1}%
6456 \LWR@startpars%
6457 }

```

## 52.7 Div class and element class

`\LWR@subhtmlElementclass` {<*element*>} [<*style*>] (<*aria role*>) {<*class*>}

Factored and reused in several places.

The trailing spaces allow more places for a line break.

The use of `\textquotedbl` instead of `"` provides improved compatibility with XeCJK.

```

6458 \NewDocumentCommand{\LWR@subhtmlElementclass}{m O{} D(){} m}{%

```

```

6459 \LWR@traceinfo{LWR@subhtmlElementclass !#1!#2!#3!#4!}%
6460 \ifblank{#2}%
6461 {% empty style
6462 \LWR@htmltag{%
6463 #1%
6464 \ifblank{#3}{ role=\textquotedbl#3\textquotedbl}% spaces
6465 \ifblank{#4}{ class=\textquotedbl#4\textquotedbl}% spaces
6466 }%
6467 }%
6468 {% non-empty style
6469 \LWR@htmltag{%
6470 #1\LWR@indentHTML%
6471 \ifblank{#3}{role=\textquotedbl#3\textquotedbl\LWR@indentHTML}%
6472 \ifblank{#4}{class=\textquotedbl#4\textquotedbl\LWR@indentHTML}%
6473 style=\textquotedbl#2\textquotedbl\LWR@orignewLine%
6474 }%
6475 }%
6476 \LWR@traceinfo{LWR@subhtmlElementclass done}%
6477 }

```

`\LWR@htmlElementclass` {<element>} [<style>] {<class>}

```

6478 \NewDocumentCommand{\LWR@htmlElementclass}{m o D(){} m}{%
6479 \LWR@stoppars%
6480 \LWR@forceemptyline%
6481 \ifblank{#3}%
6482 {\LWR@subhtmlElementclass{#1}[#2][#4]}%
6483 {\LWR@subhtmlElementclass{#1}[#2](#3){#4}}%
6484 \LWR@startpars%
6485 }

```

`\LWR@htmlElementclassend` {<element>} {<class>}

```

6486 \newcommand*{\LWR@htmlElementclassend}[2]{%
6487 \LWR@stoppars%
6488 \LWR@htmltag{/#1}%
6489 \ifbool{HTMLDebugComments}{%
6490 \LWR@htmlcomment{End of #1 ‘#2’}%
6491 }{}%
6492 \LWR@startpars%
6493 }

```

`\LWR@htmlDivclass` [<style>] (<aria role>) {<class>}

```

6494 \NewDocumentCommand{\LWR@htmlDivclass}{o D(){} m}{%
6495 \ifblank{#2}
6496 {\LWR@htmlElementclass{div}[#1][#3]}%
6497 {\LWR@htmlElementclass{div}[#1](#2)[#3]}%
6498 }

```

`\LWR@htmlDivclassend` {<class>}

```

6499 \newcommand*{\LWR@htmlDivclassend}[1]{%
6500 \LWR@htmlElementclassend{div}{#1}%
6501 }

```

## 52.8 Single-line elements

A single-line element, without a paragraph tag for the line of text:

```
\LWR@htmlElementclassline {<element>} [<style>] {<class>} {<text>}
```

```
6502 \NewDocumentCommand{\LWR@htmlElementclassline}{m o m +m}{%
6503 \LWR@stoppars
6504 \LWR@forceemptyline%
6505 \LWR@subhtmlElementclass{#1}[#2][#3]%
6506 #4%
6507 \LWR@htmltag{/#1}
6508 \LWR@startpars
6509 }
```

## 52.9 HTML5 semantic elements

```
\LWR@htmlElement {<element>}
```

```
6510 \newcommand*{\LWR@htmlElement}[1]{%
6511 \LWR@htmlblocktag{#1}
6512 }
```

```
\LWR@htmlElementend {<element>}
```

```
6513 \newcommand*{\LWR@htmlElementend}[1]{%
6514 \LWR@stoppars
6515 \LWR@htmltag{/#1}
6516 \LWR@startpars
6517 }
6518
6519 \end{warpHTML}
```

## 52.10 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with CSS.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section 95.

```
Env BlockClass [<style>] (<aria role>) {<class>} High-level interface for <div> classes.
```

```
Ex: \begin{BlockClass}{class} text \end{BlockClass}
```

```
for HTML & PRINT: 6520 \begin{warpall}
6521 \NewDocumentEnvironment{BlockClass}{o D(){} m}{}{}
6522 \end{warpall}
```

```
for HTML output: 6523 \begin{warpHTML}
6524
6525 \NewDocumentEnvironment{LWR@HTML@BlockClass}{o D(){} m}
```

```

6526 {\LWR@htmldivclass[#1](#2){#3}}%
6527 {\LWR@htmldivclassend{#3}}
6528
6529 \LWR@formattedenv{BlockClass}
6530 \end{warpHTML}

```

`\BlockClassSingle` `{\langle class \rangle}{\langle text \rangle}` A single-line `<div>`, without a paragraph tag for the line of text.

**for HTML & PRINT:**

```

6531 \begin{warpall}
6532 \newcommand{\BlockClassSingle}[2]{#2}
6533 \end{warpall}

```

**for HTML output:**

```

6534 \begin{warpHTML}
6535 \newcommand{\LWR@HTML@BlockClassSingle}[2]{%
6536 \LWR@html@element@class@line{div}{#1}{#2}%
6537 }
6538
6539 \LWR@formatted{BlockClassSingle}
6540 \end{warpHTML}

```

`\InlineClass` `(\langle WP style \rangle) [\langle style \rangle]{\langle class \rangle}{\langle text \rangle}`

High-level interface for inline span classes.

`(\langle WP style \rangle)` is css styling to add when formatting for a word processor import.

`[\langle style \rangle]` is the css styling to add when not formatting for a word processor.

**for HTML & PRINT:**

```

6541 \begin{warpall}
6542 \NewDocumentCommand{\InlineClass}{D{({})}{ } o m +m}{#4}%
6543 \end{warpall}

```

**for HTML output:**

```

6544 \begin{warpHTML}
6545 \NewDocumentCommand{\LWR@HTML@InlineClass}{D{({})}{ } o m +m}{%
6546 \LWR@traceinfo{LWR@HTML@InlineClass #3}%
6547 \ifbool{FormatWP}{%
6548 \LWR@traceinfo{LWR@HTML@InlineClass: FormatWP}%
6549 \LWR@htmlspanclass[#1]{#3}{#4}%
6550 }{%
6551 \LWR@traceinfo{LWR@HTML@InlineClass: not FormatWP}%
6552 \LWR@htmlspanclass[#2]{#3}{#4}%
6553 }%
6554 \LWR@traceinfo{LWR@HTML@InlineClass: done}%
6555 }
6556
6557 \LWR@formatted{InlineClass}
6558 \end{warpHTML}

```

Env `LWR@BlockClassWP` `{\langle WP style \rangle}{\langle HTML style \rangle} (\langle aria role \rangle) {\langle class \rangle}` Low-level interface for `<div>` classes with an automatic float ID. These are often used when `\ifbool{FormatWP}`.

The use of `\textquotedbl` instead of `"` provides improved compatibility with `xeCJK`.

**for HTML & PRINT:**

```

6559 \begin{warpall}
6560 \NewDocumentEnvironment{LWR@BlockClassWP}{m m D({}){ } m}{ }{ }
6561 \end{warpall}

```

```

for HTML output: 6562 \begin{warpHTML}
6563 \NewDocumentEnvironment{LWR@HTML@LWR@BlockClassWP}{m m D(){} m}%
6564 {%
6565 \LWR@stoppars%
6566 \ifbool{FormatWP}%
6567 {%
6568 \addtocounter{LWR@thisautoidWP}{1}%

6569 \LWR@htmltag{%
6570 div class=\textquotedbl#4\textquotedbl\ % space
6571 id=\textquotedbl%
6572 \LWR@print@box{autoidWP-\arabic{LWR@thisautoidWP}}%
6573 \textquotedbl%
6574 \ifblank{#3}{}{ role=\textquotedbl#3\textquotedbl}%
6575 \ifblank{#1}{}{ style=\textquotedbl#1\textquotedbl}%
6576 }%
6577 }% FormatWP
6578 {% not FormatWP
6579 \LWR@htmltag{%
6580 div class=\textquotedbl#4\textquotedbl%
6581 \ifblank{#3}{}{ role=\textquotedbl#3\textquotedbl}%
6582 \ifblank{#2}{}{ style=\textquotedbl#2\textquotedbl}%
6583 }%
6584 }% not FormatWP
6585 \LWR@startpars%
6586 }
6587 {\LWR@htmldivclassend{#4}}
6588
6589 \LWR@formattedenv{LWR@BlockClassWP}
6590 \end{warpHTML}

```

## 52.11 Closing HTML tags

```
for HTML output: 6591 \begin{warpHTML}
```

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```

6592 \newcommand*{\LWR@printclosebook}
6593 {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing book}}{}}
6594 \newcommand*{\LWR@printclosepart}
6595 {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
6596 \newcommand*{\LWR@printclosechapter}
6597 {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
6598 \newcommand*{\LWR@printclosesection}
6599 {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
6600 \newcommand*{\LWR@printclosesubsection}
6601 {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
6602 \newcommand*{\LWR@printclosesubsection}
6603 {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
6604 \newcommand*{\LWR@printcloseparagraph}
6605 {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
6606 \newcommand*{\LWR@printclose subparagraph}
6607 {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}

```

Lists require closing HTML tags:

```

6608 \newcommand*{\LWR@printcloselistitem}
6609 {\LWR@htmltag{/li}}
6610 \newcommand*{\LWR@printclosedescitem}
6611 {\LWR@htmltag{/dd}}
6612 \newcommand*{\LWR@printcloseitemize}
6613 {\LWR@htmltag{/ul}}
6614 \newcommand*{\LWR@printcloseenumerate}
6615 {\LWR@htmltag{/ol}}
6616 \newcommand*{\LWR@printclosedescription}
6617 {\LWR@htmltag{/dl}}

6618 \end{warpHTML}

```

## 53 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 54 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (`LWR@doingstartpars`), tags are not generated until a  $\LaTeX$  paragraph is being used (`LWR@doingapar`). `LWR@lateximagedepth` is used to prevent nesting tags inside a `lateximage`. `LWR@spandepth` is used to prevent nesting paragraph tags inside a paragraph, which became important inside `\fbox` commands and other spans.

The  $\LaTeX$  paragraph hooks are used to manage tag creation.

**for HTML output:** `6619 \begin{warpHTML}`

|      |                                                                                                          |                                                                                             |
|------|----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Ctrl | <code>LWR@spandepth</code>                                                                               | Do not create paragraph tags inside of an HTML span.                                        |
|      | <code>6620 \newcounter{LWR@spandepth}</code><br><code>6621 \setcounter{LWR@spandepth}{0}</code>          |                                                                                             |
| Bool | <code>LWR@doingparhooks</code>                                                                           | Tells whether the <code>lwarp</code> paragraph hooks are to be active.                      |
|      | <code>6622 \newbool{LWR@doingparhooks}</code><br><code>6623 \boolfalse{LWR@doingparhooks}</code>         |                                                                                             |
| Bool | <code>LWR@in@multirow@par</code>                                                                         | Tells whether to generate break instead of paragraph tags inside a <code>\multirow</code> . |
|      | <code>6624 \newbool{LWR@in@multirow@par}</code><br><code>6625 \boolfalse{LWR@in@multirow@par}</code>     |                                                                                             |
| Bool | <code>LWR@starting@fancybox</code>                                                                       | Suppresses <code>&lt;br&gt;</code> if beginning a <code>fancybox</code> environment.        |
|      | <code>6626 \newbool{LWR@starting@fancybox}</code><br><code>6627 \boolfalse{LWR@starting@fancybox}</code> |                                                                                             |
| Bool | <code>LWR@doingstartpars</code>                                                                          | Tells whether paragraphs may be generated.                                                  |
|      | <code>6628 \newbool{LWR@doingstartpars}</code><br><code>6629 \boolfalse{LWR@doingstartpars}</code>       |                                                                                             |
| Bool | <code>LWR@doingapar</code>                                                                               | Tells whether have actually generated and are currently processing paragraph text.          |

```
6630 \newbool{LWR@doingapar}
6631 \global\boolfalse{LWR@doingapar}
```

Bool LWR@algocf@dopars

Tells whether `algorithm2e` has patched paragraph handling using `\everypar`. If so, the open paragraph tags are generated by `algorithm2e`'s `\algocf@everypar` instead of `\LWR@openparagraph`.

```
6632 \newbool{LWR@algocf@dopars}
6633 \boolfalse{LWR@algocf@dopars}
```

`\PN@parnotes@auto` Redefined by `parnotes` to print paragraph notes at the end of each paragraph.

```
6634 \def\PN@parnotes@auto{}
```

`\LWR@ensuredoingapar` `\LWR@openparagraph` These were different in older versions of `lwarp`, but are now the same thing.

```
6635 \newcommand*{\LWR@openparagraph}
6636 {}
```

See if paragraph handling is enabled:

```
6637 \ifbool{LWR@doingapar}{
6638 \bool{LWR@doingparhooks} and
6639 \bool{LWR@doingstartpars}
6640 }{
6641 \% handling pars
```

See if have already started a `lateximage` or a `<span>`. If so, do not generate nested paragraph tags.

```
6642 \ifbool{LWR@doingapar}{
6643 test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
6644 test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
6645 }{ \% nested par tags?
```

If so: Do nothing if already started a `lateximage` page. Cannot nest a `lateximage`. Also do nothing if already inside a `<span>`. Do not nest paragraph tags inside a `<span>`.

```
6646 }{ \% no nested par tags
```

Else: No `lateximage` or `<span>` has been started yet, so it's OK to generate paragraph tags.

```
6647 }{ \% yes nest par tags
6648 \ifbool{LWR@doingapar}{}
```

If `parnotes` is used, paragraph notes are inserted before starting the next paragraph:

```
6649 \PN@parnotes@auto%
```

Set flag before creating the tag, so that the tag itself does not trigger a new paragraph:

```
6650 \global\booltrue{LWR@doingapar}
```

The opening paragraph tag. Do not create tag if doing algorithm2e handling instead:

```

6651 \ifbool{LWR@algocf@dopars}{}{%
6652 \ifbool{LWR@in@multirow@par}%
6653 {}%
6654 {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@originewline}%
6655 }%
6656 }%
6657 }% end of yes nest par tags
6658 }% end of handling pars
6659 {}% not handling pars
6660 }
6661
6662 \let\LWR@ensuredoingapar\LWR@openparagraph

```

`\LWR@closeparagraph@br` Add an HTML break if in a span, and not in a lateximage, and not in tabular metadata. Factored from `\LWR@closeparagraph`.

```

6663 \newcommand*{\LWR@closeparagraph@br}
6664 {%
6665 \ifboolexpr{
6666 test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}} and
6667 test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}} and
6668 not bool {LWR@starting@fancybox} and
6669 not bool {LWR@intabularmetadata} or
6670 bool {LWR@in@multirow@par}
6671 }%
6672 {\unskip\LWR@htmltagc{br /}}%
6673 }%
6674 }

```

`\LWR@closeparagraph`

```

6675 \newcommand*{\LWR@closeparagraph}
6676 {%
6677 % \LWR@traceinfo{LWR@closeparagraph}%

```

See if paragraph handling is enabled:

```

6678 \ifbool{LWR@doingparhooks}{%
6679 \ifbool{LWR@doingapar}%

```

If currently in paragraph mode:

```

6680 {% handling pars

```

See if already started a lateximage or a `<span>`:

```

6681 \ifboolexpr{
6682 test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
6683 test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}} or
6684 bool{LWR@in@multirow@par}
6685 }%

```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```

6686 {% no nested par tags
6687 \LWR@closeparagraph@br%
6688 }% no nested par tags

```

If have not already started a lateximage or a <span>:

```

6689 {% yes nest par tags

```

Print a closing tag.

(The fill seems to be required to force the caption package to create flush left caption text in the HTML.)

```

6690 \@hspacer{\fill}% \hspace*{\fill}
6691 \leavevmode\LWR@originewline%
6692 \LWR@htmltagc{/\LWR@tagregularparagraph}%

```

No longer doing a paragraph:

```

6693 \global\boolfalse{LWR@doingapar}%

```

Disable the special minipage & \hspace interaction until a new minipage is found:

```

6694 \global\boolfalse{LWR@minipagethispar}%

```

If parnotes is used, paragraph notes are inserted after ending the previous paragraph:

```

6695 \PN@parnotes@auto%

6696 }% end of yes nest par tags
6697 }% LWR@doingapar: end of handling pars

```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```

6698 {% not LWR@doingapar: not handling pars
6699 \LWR@closeparagraph@br%
6700 }% not handling pars

```

In most cases, finish with a L<sup>A</sup>T<sub>E</sub>X \par, but in the case of paragraphs between lines in a tabular fetch the next token instead. Required for \multicolumn.

```

6701 \ifboolexpr{%
6702 not bool {LWR@doingapar} and
6703 test {\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}} and
6704 test {
6705 \ifnumcomp{\value{LWR@tabulardepth}}{=}{\value{LWR@tabularpardepth}}
6706 } and
6707 bool {LWR@intabularmetadata} and
6708 not bool {LWR@tableparcell} and
6709 test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
6710 }%
6711 {\LWR@getmynexttoken}%
6712 }%
6713 }% LWR@doingparhooks
6714 }% not LWR@doingparhooks
6715 Do not place anything here, due to the above \LWR@getmynexttoken.
6716 }

```

## 53.1 Paragraph Hooks

Hook [LaTeX] para/begin

```
6717 \AddToHook{para/begin}[lwarp]{\LWR@openparagraph}
```

Hook [LaTeX] para/end

```
6718 \AddToHook{para/end}[lwarp]{\LWR@closeparagraph}
```

```
6719 \end{warpHTML}
```

## 54 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 53 has the commands which actually generate the tags.

The L<sup>A</sup>T<sub>E</sub>X paragraph hooks are used to generate the opening and closing paragraph tags.

**for HTML output:** 6720 \begin{warpHTML}

\LWR@startpars Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```
6721 \newcommand*{\LWR@startpars}%
6722 {%
```

Ignore if inside a lateximage or <span>:

```
6723 \ifboolexpr{
6724 test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
6725 test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
6726 }%
6727 {}% nesting
6728 {% not nesting
```

The L<sup>A</sup>T<sub>E</sub>X paragraph hook controls tag generation for the start and end of paragraphs.

See if currently handling HTML paragraphs:

```
6729 \ifboolexpr {bool{LWR@doingparhooks} and bool{LWR@doingstartpars}}%
```

If already in paragraph mode, do nothing.

```
6730 {}%
```

If not currently in paragraph mode:

```
6731 {\par}%
```

Are now handling paragraphs, but have not yet actually started one:

```
6732 \global\booltrue{LWR@doingstartpars}%
```

No <par> tag yet to undo:

```
6733 \global\boolfalse{LWR@doingapar}%
6734 }% not nesting
6735 }
```

`\LWR@stoppars` Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```
6736 \newcommand*{\LWR@stoppars}%
6737 {%
```

Ignore if inside a `lateximage` or `<span>`:

```
6738 \ifboolexpr{
6739 test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
6740 test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
6741 }%
6742 {}% nesting
6743 {% not nesting
```

See if currently handling HTML paragraphs:

```
6744 \ifboolexpr{bool{LWR@doingparhooks} and bool{LWR@doingapar}}%
```

if currently in an HTML paragraph:

```
6745 {%
```

Print a closing tag:

```
6746 \leavevmode\LWR@orignewline%
6747 \LWR@htmltagc{/\LWR@tagregularparagraph}%
6748 \LWR@orignewline%
```

No longer have an open HTML paragraph:

```
6749 \global\boolfalse{LWR@doingapar}%
```

Disable the special `minipage` & `\hspace` interaction until a new `minipage` is found:

```
6750 \global\boolfalse{LWR@minipagethispar}%
6751 }
```

If was not in an HTML paragraph:

```
6752 }%
```

No longer in paragraph mode:

```
6753 \global\setbool{LWR@doingstartpars}{false}%
```

No <p> tag to undo:

```
6754 \global\boolfalse{LWR@doingapar}%
6755 }% not nesting
6756 }

6757 \end{warpHTML}
```

## 55 Indentfirst

Pkg indentfirst

indentfirst redefines \@afterindentfalse to be \@afterindenttrue. This is reversed \AtBeginDocument here.

**for HTML output:**

```
6758 \begin{warpHTML}

6759 \AtBeginDocument{
6760 \def\@afterindentfalse{\let\if@afterindent\iffalse}
6761 \@afterindentfalse
6762 }
6763 \let\LWR@afterindent@syntaxhighlight\fi% syntax highlighting

6764 \end{warpHTML}
```

## 56 Page headers and footers

**for HTML & PRINT:**

```
6765 \begin{warpall}
```

In the following, catcode is manually changed back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
6766 \newcommand{\LWR@firstpagetop}{} % for the home page alone
6767 \newcommand{\LWR@firstpagebottom}{} % for the home page alone
6768 \newcommand{\LWR@pagetop}{} % for all other pages
6769 \newcommand{\LWR@pagebottom}{}%
```

\HTMLFirstPageTop {<*text and logos*>}

```
6770 \newcommand{\HTMLFirstPageTop}[1]{%
6771 \renewcommand{\LWR@firstpagetop}{#1}%
6772 }
```

\HTMLFirstPageBottom {<*text and logos*>}

```
6773 \newcommand{\HTMLFirstPageBottom}[1]{%
6774 \renewcommand{\LWR@firstpagebottom}{#1}%
6775 }
```

\HTMLPageTop {<*text and logos*>}

```
6776 \newcommand{\HTMLPageTop}[1]{%
6777 \renewcommand{\LWR@pagetop}{#1}%
6778 }
```

`\HTMLPageBottom`  $\{\langle text\ and\ logos\rangle\}$

```
6779 \newcommand{\HTMLPageBottom}[1]{%
6780 \renewcommand{\LWR@pagebottom}{#1}%
6781 }

6782 \end{warpall}
```

## 57 CSS

**for HTML output:** 6783 `\begin{warpHTML}`

`\LWR@currentcss` The CSS filename to use. This may be changed mid-document using `\CSSFilename`, allowing different CSS files to be used for different sections of the document.

```
6784 \newcommand*\LWR@currentcss{lwarp.css}
```

`\CSSFilename`  $\{\langle new-css-filename.css\rangle\}$  Assigns the CSS file to be used by the following HTML pages.

```
6785 \newcommand*\CSSFilename[1]{%
6786 \renewcommand*\LWR@currentcss{#1}%
6787 \@onelevel@sanitize\LWR@currentcss%
6788 }
6789
6790 \end{warpHTML}
```

**for PRINT output:** 6791 `\begin{warpprint}`  
6792 `\newcommand*\CSSFilename[1]{}`  
6793 `\end{warpprint}`

## 58 MATHJAX script

**for HTML output:** 6794 `\begin{warpHTML}`  
Default: `lwarp_mathjax.txt`

`\LWR@mathjaxfilename` The MATHJAX script filename to use. This file is copied into the head of each HTML page. This may be changed mid-document using `\MathJaxFilename`, allowing the use of a custom MATHJAX script, such as for a local repository, or different MATHJAX script files to be used for different sections of the document.

```
6795 \newcommand*\LWR@mathjaxfilename{lwarp_mathjax.txt}
```

`\MathJaxFilename`  $\{\langle filename\rangle\}$  Assigns the MATHJAX script file to be used by the following HTML pages.

```
6796 \newcommand*\MathJaxFilename[1]{%
6797 \renewcommand*\LWR@mathjaxfilename{#1}%
6798 \@onelevel@sanitize\LWR@mathjaxfilename%
6799 }
6800
6801 \end{warpHTML}
```

**for PRINT output:** 6802 `\begin{warpprint}`  
 6803 `\newcommand*{\MathJaxFilename}[1]{}`  
 6804 `\end{warpprint}`

## 59 Title, HTML meta author, HTML meta description

**for HTML output:** 6805 `\begin{warpHTML}`

`\title`  $\langle\textit{title}\rangle$  Modified to remember `\thetitle`, which is used to set the HTML page titles.

```
6806 \let\LWR@origtitle\title
6807
6808 \renewcommand*{\title}[1]{%
6809 \LWR@origtitle{#1}%
6810 \begingroup%
6811 \renewcommand{\thanks}[1]{%
6812 \protected@xdef\thetitle{#1}%
6813 \endgroup%
6814 }

6815 \end{warpHTML}
```

**for HTML & PRINT:** 6816 `\begin{warpall}`

`\HTMLTitle`  $\langle\textit{Titlename}\rangle$  The Title to place into an HTML meta tag. The default is to use the document `\title`'s setting.

```
6817 \providecommand{\thetitle}{\BaseJobname}
6818
6819 \newcommand{\theHTMLTitle}{\thetitle}
6820
6821 \newcommand{\HTMLTitle}[1]{\renewcommand{\theHTMLTitle}{#1}}
```

`\HTMLAuthor`  $\langle\textit{authorname}\rangle$  The author to place into an HTML meta tag. If none given, the default is `\theauthor`, which is empty unless the titling package is used.

```
6822 \providecommand{\theauthor}{}
6823
6824 \newcommand{\theHTMLAuthor}{\theauthor}
6825
6826 \newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}
```

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using `\HTMLDescription`, allowing different HTML descriptions to be used for different sections of the document.

 **HTML author** Do not use double quotes, and do not exceed 150 characters.

`\HTMLDescription`  $\langle\textit{New html meta description.}\rangle$  Assigns the HTML file's description meta tag.

```
6827 \newcommand{\LWR@currentHTMLDescription}{}

```

```

6828
6829 \newcommand{\HTMLDescription}[1]{%
6830 \renewcommand{\LWR@currentHTMLDescription}{#1}
6831 }
6832
6833 \end{warpa11}

```

## 60 Footnotes

lwarp uses native L<sup>A</sup>T<sub>E</sub>X footnote code, although with its own `\box` to avoid the L<sup>A</sup>T<sub>E</sub>X output routine. The usual functions mostly work as-is.

**footnote numbering** To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For `bigfoot`, `manyfoot`, or `perpage`:

```

\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}

```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

**MATHJAX** Also for MATHJAX, `\footnotename` is used for a `\footnotemark` if the actual footnote number is not known. To redefine it, provide it before loading `lwarp`:

```

\providecommand{\footnotename}{something}
\usepackage{lwarp}

```

Similar for sidenotes. For endnotes:

```
\def\endnotename{something}% \def allows name to start with "end"
```

For the `pagenote` package, there is no `\pagenotename` to define, since there is no `\pagenotemark` command.

**footmisc** The `footmisc` stable option is emulated by `lwarp`.

 **sectioning commands** When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the `footmisc` package with the `stable` option, provide a short toc entry, and `\protect` the `\footnote`:

```

\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
{Subsection Name\protect\footnote{A footnote.}}

```

**memoir with footmisc** If using `memoir` class, with which `lwarp` preloads `footmisc`, the `stable` option must be declared before `lwarp` is loaded:



**memoir**

```

\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .

```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handle differently.

## 60.1 Regular page footnotes

In HTML documents, footnotes are placed at the bottom of the web page or the section, depending on `FootnoteDepth`, using the L<sup>A</sup>T<sub>E</sub>X box `\LWR@footnotebox`. Using this instead of the original `\footins` box avoids having footnotes be printed by the output routine, since footnotes should be printed per HTML page instead of per PDF page.

See section 60.4 for the implementation.

## 60.2 Minipage footnotes

See section 60.5 for how minipage footnotes are gathered. See section 94.4 for how minipage footnotes are placed into the document.

## 60.3 Titlepage thanks

See section 69.7 for titlepage footnotes.

## 60.4 Regular page footnote implementation

**for HTML & PRINT:** 6834 `\begin{warpall}`

Ctrl `FootnoteDepth` Determines how deeply to place footnotes in the HTML files, similar to `tocdepth`.  
 Default: 3 The default of 3 places footnotes before each `\subsubsection` or higher. See table 12 for a table of L<sup>A</sup>T<sub>E</sub>X section headings.

```
6835 \newcounter{FootnoteDepth}
6836 \setcounter{FootnoteDepth}{3}
```

Ctrl `footnoteReset` If non-zero, the footnote counter is reset to this value each time the footnotes are printed, as controlled by `FootnoteDepth`. For the `manyfoot` and `bigfoot` packages, additional counters such as `footnote<suffix>Reset` will be defined as well. These counters may be set non-zero by the user, and are also set if the `perpage`'s `\MakePerPage` or `\MakeSortedPerPage` macros are used for the `footnote` or `footnote<suffix>` counters.

(The name is not capitalized because it is made from the counter's name with "Reset" appended.)

```
6837 \newcounter{footnoteReset}
6838 \setcounter{footnoteReset}{0}
```

```
6839 \end{warpall}
```

**for HTML output:** 6840 `\begin{warpHTML}`

Required for footnotes inside description or amsththeorem square braces:

```
6841 \AtBeginDocument{
6842 \robustify{\footnote}
6843 \robustify{\footnotemark}
6844 }
```

`\LWR@footnotebox` Patch L<sup>A</sup>T<sub>E</sub>X footnotes to use a new `\box` instead of an insert for `lwarp` footnotes. This avoids having the original `\footins` appear at the bottom of a `lateximage`, which is on its own new page.

```
6845 \newbox\LWR@footnotebox
```

`Bool LWR@spewingnotes` Used with the `footnote` package to suppress paragraph tags before and after `\spewnotes`.

```
6846 \newbool{LWR@spewingnotes}% For the footnote package.
```

Much of the following has unneeded print-mode formatting removed.

`\@makefntext` `{\langle text \rangle}`

```
6847 \long\def\@makefntext#1{\@thefnmark~{#1}}
```

`\@makefnmark`

```
6848 \def\@makefnmark{%
6849 \@thefnmark%
6850 }
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or `lateximage`, in which case paragraph tags must be added manually.

In a `lateximage` during HTML output, the `lateximage` is placed inside a print-mode `minipage`, but the footnotes are broken out by:

```
\def\@mpfn{footnote}
\def\@thempfn{\thefootnote}
\let\@footnotetext\LWR@footnotetext
```

`\LWR@@footnotetext` `{\langle text \rangle} {\langle footnote box name \rangle}`

Factored to allow multiple footnote boxes for `manyfoot`.

```
6851 \long\def\LWR@@footnotetext#1#2{%
6852 \LWR@traceinfo{LWR@footnotetext}%
```

Perhaps generate an `autopage` in the text to link a citation backreference closer to its usage.

```
6853 \LWR@newautopagelabel{page}%
6854 \LWR@ensuredoingapar%
```

Locally disable auto page labels inside the footnote text. Footnotes are accumulated in the current page before finally being placed in a potentially later page, so the autpages would be incorrect.

```
6855 \begingroup%
6856 \let\LWR@newautopagelabel\LWR@null@newautopagelabel%
```

Take the existing footnote box and add the new content:

```
6857 \global\setbox\csname #2\endcsname=\vbox{%
6858 \unvbox\csname #2\endcsname%
```

Remember the footnote number for \ref:

```
6859 \protected@edef\@currentlabel{%
6860 \csname p@footnote\endcsname\@thefnmark%
6861 }% @currentlabel
```

Open a group:

```
6862 \color@begingroup%
```

Disable CJK xpinyin while generating footnotes.

```
6863 \LWR@disablepinyin%
```

Use HTML superscripts in the footnote even when the main text is inside a lateximage, because the footnote will be in HTML:

```
6864 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
6865 \ifbool{LWR@spewingnotes}{}{%
6866 \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%
6867 }%
```

Append the footnote to the list:

```
6868 \@makefntext{#1}%
```

Closing paragraph tag:

```
6869 \ifbool{LWR@spewingnotes}{}{%
6870 \LWR@origtilde\LWR@orignewline%
6871 \LWR@htmltagc{/\LWR@tagregularparagraph}%
6872 \LWR@orignewline%
6873 }%
```

Close the group:

```
6874 \color@endgroup%
6875 }% vbox
6876 \endgroup%
6877 }%
```

```
\LWR@footnotetext {<text>}
```

```
6878 \long\def\LWR@footnotetext#1{\LWR@footnotetext{#1}{LWR@footnotebox}}%
```

```
\@footnotetext {<text>}
```

```
6879 \let\ltxMacro\@footnotetext\LWR@footnotetext
```

## 60.5 Minipage footnote implementation

Patch L<sup>A</sup>T<sub>E</sub>X minipage footnotes to use a new `\box` instead of an insert for `lwarp` minipage footnotes. This avoids having the original `\@mpfootins` appear at the bottom of a `lateximage`, which is on its own new page.

```
6880 \newbox\LWR@mpfootnotes
```

```
\@mpfootnotetext {<text>}
```

```
6881 \long\def\@mpfootnotetext#1{%
6882 \LWR@traceinfo{\@mpfootnotetext}%
6883 \LWR@ensuredoingapar%
6884 \global\setbox\LWR@mpfootnotes\box{%
6885 \unvbox\LWR@mpfootnotes%
6886 \reset@font\footnotesize%
6887 \hsize\columnwidth%
6888 \@parboxrestore%
6889 \protected@edef\@currentlabel%
6890 {\csname p@mpfootnote\endcsname\@thefnmark}%
6891 \color@begingroup%
```

Add paragraph tag:

```
6892 \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%
6893 \@makefntext{%
6894 \ignorespaces#1%
6895 }%
```

Add the closing paragraph tag:

```
6896 \leavevmode\LWR@orignewline%
6897 \LWR@htmltagc{/\LWR@tagregularparagraph}%
6898 \color@endgroup%
6899 }% vbox
```

Paragraph handling:

```
6900 \LWR@ensuredoingapar%
6901 \LWR@traceinfo{\@mpfootnotetext: done}%
6902 }
```

`\thempfootnote` Redefined to remove the `\itshape`, which caused an obscure compiling error in some situations.

```
6903 \AtBeginDocument{
6904 \def\thempfootnote{\@alph\c@mpfootnote}
6905 }
```

## 60.6 Printing pending footnotes

`\LWR@printpendingfootnotes`  $\{ \langle footnote\ counter\ name \rangle \}$

```
6906 \newcommand*\LWR@printpendingfootnotes}[1]{%
6907 \expandafter\ifvoid\csname LWR@#1box\endcsname\else
6908 \LWR@forcenewpage
6909 \begin{BlockClass}(note){footnotes}%
```

Create a new autpage in case citation back references occur inside the footnotes:

```
6910 \LWR@newautopagelabel{page}%

6911 \null
6912 \unvbox\csuse{LWR@#1box}
6913 \setbox\csuse{LWR@#1box}=\vbox{}
6914 \end{BlockClass}
6915 \ifltxcounter{#1Reset}{%
6916 \ifnumgreater{\value{#1Reset}}{0}{%
6917 \setcounter{#1}{\value{#1Reset}}%
6918 \addtocounter{#1}{-1}%
6919 }{}%
6920 }{}%
6921 \fi
6922 }
```

`\LWR@printpendingfootnotes` Enclose the footnotes in a class, print, then clear. For `manynotes`, new footnotes may be added via `\appto`.

```
6923 \newcommand*\LWR@printpendingfootnotes}{%
6924 \LWR@printpendingfootnotes{footnote}%
6925 }
```

`\LWR@maybeprintpendingfootnotes`  $\{ \langle depth \rangle \}$  Used to print footnotes before sections only if formatting for an EPUB or word processor:

```
6926 \newcommand*\LWR@maybeprintpendingfootnotes}[1]{%
6927 \ifboolexpr{
6928 not test{\ifnumcomp{#1}{>}{\value{FootnoteDepth}}} or
6929 bool{FormatEPUB} or
6930 bool{FormatWP}
6931 }%
6932 {\LWR@printpendingfootnotes}%
6933 }{}%
6934 }
```

`\LWR@printpendingmpfootnotes` Enclose the minipage footnotes in a class, print, then clear.

```
6935 \newcommand*\LWR@printpendingmpfootnotes}{%
6936 \ifvoid\LWR@mpfootnotes\else
6937 \LWR@forcenewpage
6938 \begin{BlockClass}(note){footnotes}%
6939 \null
6940 \unvbox\LWR@mpfootnotes
6941 \setbox\LWR@mpfootnotes=\vbox{}
6942 \end{BlockClass}
```

```
6943 \fi
6944 }
```

`\LWR@nullifyfootnotes` Cancels footnotes, such as inside an HTML comment or a `\nameref`.

```
6945 \newcommand*\LWR@nullifyfootnotes{%
6946 \renewcommand{\footnote}[2][{}]{%
6947 \renewcommand{\footnotemark}[1][{}]{%
6948 }

6949 \end{warpHTML}
```

## 61 Marginpars

`\marginpar` [*<left>*] [*<right>*] `\marginpar` may contains paragraphs, but in order to remain inline with the surrounding text `lwarp` nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `<br />` tags.

`\marginparBlock` [*<left>*] [*<right>*] To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a `<span>`. A line break will occur in the text where the `\marginBlock` occurs.

**for HTML output:** `6950 \begin{warpHTML}`

`\marginpar` [*<left>*] [*<right>*]

```
6951 \renewcommand{\marginpar}[2][{}]{%
6952 \ifbool{FormatWP}%
6953 {%
6954 \begin{LWR@BlockClassWP}%
6955 {width:2in; float:right; margin:10pt}{(note){marginblock}%
6956 #2
6957 \end{LWR@BlockClassWP}%
6958 }%
6959 {%
6960 \LWR@htmlspanclass(note){marginpar}{#2}%
6961 }%
6962 }
```

`\marginparBlock` [*<left>*] [*<right>*]

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

HTML version.

```
6963 \newcommand{\marginparBlock}[2][{}]{%
6964 \LWR@stoppars%
6965 \ifbool{FormatWP}%
6966 {%
6967 \begin{LWR@BlockClassWP}%
6968 {width:2in; float:right; margin:10pt}{%
6969 (note){marginblock}%
6970 #2
```

```

6971 \end{LWR@BlockClassWP}
6972 }%
6973 {%
6974 \begin{BlockClass}[width:2in; float:right; margin:10pt]%
6975 (note){marginparblock}%
6976 #2
6977 \end{BlockClass}
6978 }%
6979 \LWR@startpars%
6980 }

```

`\reversemarginpar`

```
6981 \renewcommand*{\reversemarginpar}{}

```

`\normalmarginpar`

```
6982 \renewcommand*{\normalmarginpar}{}

```

```
6983 \end{warpprint}

```

**for PRINT output:** `6984 \begin{warpprint}`

`\marginparBlock` [*left*] [*right*]

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

Print version.

```
6985 \LetLtxMacro\marginparBlock\marginpar

```

```
6986 \end{warpprint}

```

## 62 Tracking internal cross references

Cross references are generated using the PDF file's page number during L<sup>A</sup>T<sub>E</sub>X compilation. Internal labels are generated which include these page numbers in the label.

File `*_html.aux`

A new entry in the `*_html.aux` file is used to help cross-references:

```
\newlabel{autopage-<nnn>}{<x>}{<y>}
```

Ctrl `LWR@currentautosecpage`

Records the page number when the section was created. (If a math expression is included in the section name, and `svg math` is used, the corresponding `lateximage` will cause the page number to change by the time the following autosec label is created, thus the initial page number is recorded here.) `LWR@currentautosecfloatpage` is updated more often than `LWR@currentautosecpage`.

```
6987 \newcounter{LWR@currentautosecpage}

```

```
6988 \setcounter{LWR@currentautosecpage}{1}

```

Ctrl  
LWR@currentautosecfloatpage

The HTML output's PDF page number at the start of a new HTML file, section, or float. Updated more often than LWR@currentautosecpage, such as when a new float occurs. Used only for table of contents, list of figures, list of tables, but not for general cross references such as \label, citation backlinks, etc.

\LWRsetnextfloat is written with this and the autoid by the modified \addcontentsline just before each float's entry.

```
6989 \newcounter{LWR@currentautosecfloatpage}
6990 \setcounter{LWR@currentautosecfloatpage}{1}
```

Ctrl  
LWR@previousautopagelabel

Remembers which autopage label was most recently generated. Used to avoid duplicates.

```
6991 \newcounter{LWR@previousautopagelabel}
6992 \setcounter{LWR@previousautopagelabel}{-1}
```

\LWR@newautopagelabel {<pagenumber counter>}

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
6993 \newcommand*{\LWR@newautopagelabel}[1]{%
```

No action if this autopage label has already been defined:

```
6994 \ifnumequal{\value{LWR@previousautopagelabel}}{\value{page}}%
6995 {}%
```

If the PDF page has changed, create a label using the desired counter.

If the counter is LWR@currentautosecpage, that was the page number when the section generation began, but the current PDF page may be different by now if the section name had an SVG image, such as svg math. To allow the cross-reference to point just after the section heading, the label must be made after the section heading is complete, which may have generated a new PDF page. Thus, the label is made with the given counter, which may be the PDF page number where the section heading began, then if the PDF page number has changed, another label is made for the current page number.

```
6996 {%
6997 \label{\BaseJobname-autopage-\csuse{the#1}}%
```

If there are intervening pages, such as an SVG image, define another label for the new page:

```
6998 \ifnumequal{\value{#1}}{\value{page}}%
6999 {}%
7000 {\label{\BaseJobname-autopage-\csuse{thepage}}}%
```

Remember the latest autopage label:

```
7001 \setcounter{LWR@previousautopagelabel}{\value{page}}%
7002 }%
7003 }
```

\LWR@null@newautopagelabel {<pagenumber counter>}

Inside a footnote, the page numbers will be incorrect, so this is nullified.

```
7004 \newcommand*{\LWR@null@newautopagelabel}[1]{}
```

## 63 Splitting HTML files

- Files are split according to `FileDepth` and `CombineHigherDepths`.
- Filenames are sanitized by `\LWR@filenamoblanks`.
- `\LWR@newhtmlfile` finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

**for HTML & PRINT:** 7005 \begin{warpall}

Ctrl `FileDepth`      `{\langle section depth \rangle}` determines how deeply to break into new HTML files, similar to `tocdepth`. The default of `-5` produces one large HTML file.

```
7006 \newcounter{FileDepth}
7007 \setcounter{FileDepth}{-5}
```

Bool `CombineHigherDepths`      Combine higher-level sections together into one file?

```
7008 \newbool{CombineHigherDepths}
7009 \booltrue{CombineHigherDepths}
```

`\FilenameLimit`      Maximum length of the generated filenames.

```
7010 \newcommand*{\FilenameLimit}{80}
7011 \end{warpall}
```

**for HTML output:** 7012 \begin{warpHTML}

`\LWR@thisfilename`      The currently-active filename or number. At first, this is the homepage.

```
7013 \AtBeginDocument{
7014 \ifbool{FileSectionNames}%
7015 {\newcommand*{\LWR@thisfilename}{\HomeHTMLFilename}}
7016 {\newcommand*{\LWR@thisfilename}{0}}
7017 }
```

`\LWR@thisnewfilename`      The filename being sanitized.

```
7018 \newcommand*{\LWR@thisnewfilename}{}
```

`\LWR@simplifiname`      \* `{\langle expression \rangle}`      Simplify `\LWR@thisnewfilename`.

If starred, detokenizes the input expression. If found, changes the expression to a single detokenized dash.

```
7019 \NewDocumentCommand{\LWR@simplifiname}{s m}{%
```

```

7020 \IfBooleanTF{#1}{%
7021 \StrSubstitute{\LWR@thisnewfilename}%
7022 {\detokenize{#2}}%
7023 {\detokenize{-}}[\LWR@thisnewfilename]%
7024 }{%
7025 \StrSubstitute{\LWR@thisnewfilename}%
7026 {#2}%
7027 {\detokenize{-}}[\LWR@thisnewfilename]%
7028 }
7029 }

```

`\LWR@simplifycustom` User-defined filename simplifications. Redefine with `\newcommand`.

```
7030 \newcommand*\LWR@simplifycustom{}
```

`\FilenameSimplify` \* `{⟨phrase⟩}` Assign a user-defined filename simplification. Appends to `\LWR@simplifycustom`.

```

7031 \NewDocumentCommand{\FilenameSimplify}{s m}{%
7032 \IfBooleanTF{#1}{%
7033 \appto{\LWR@simplifycustom}{%
7034 \LWR@simplifyname*{#2}%
7035 }%
7036 }{%
7037 \appto{\LWR@simplifycustom}{%
7038 \LWR@simplifyname{#2}%
7039 }%
7040 }%
7041 }

```

`\LWR@avoiddupfilenames` Instructions for how to avoid duplicate filenames. This is used in a warning in `\LWR@filenamenoblanks`, and in an error in `\LWR@newhtmlfile`.

```

7042 \newcommand*\LWR@avoiddupfilenames{%
7043 To avoid duplicate filenames, use the optional\MessageBreak
7044 short Table of Contents entry:\MessageBreak
7045 \space\space\protect\section[Unique name, no math]{Name with math}%
7046 \MessageBreak
7047 or use \protect\texorpdfstring, from the hyperref package:\MessageBreak
7048 \space\space%
7049 \protect\section{\MessageBreak
7050 \space\space\space\space\protect\texorpdfstring\MessageBreak
7051 \space\space\space\space\space\space%
7052 {Name with math}{Unique name, no math}\MessageBreak
7053 \space\space}
7054 }

```

`\LWR@filenamenoblanks` `{⟨filename⟩}`

Convert blanks into dashes, removes short words, store result in `\LWR@thisfilename`.

Also see `\LWR@nullfonts` for nullified macros.

```

7055 \newcommand*\LWR@filenamenoblanks}[1]{%
7056 \begingroup

```

Locally temporarily disable direct-formatting commands, not used in filenames:

```
7057 \LWR@nullfonts%
7058 \renewcommand*{\LWR@htmltagc}[1]{}%

7059 \edef\LWR@thisnewfilename{#1}%
```

Replaces common macros with hyphens. (& is done by \LWR@nullfonts.)

```
7060 \RenewDocumentCommand{\LWR@subsingledollar}{s m m}{}%
7061 \LWR@simplifiname{_}
7062 \LWR@simplifiname{\#}
7063 \LWR@simplifiname{\textbackslash}
7064 \LWR@simplifiname{\protect}
7065 \LWR@simplifiname{\ }
7066 \LWR@simplifiname{\textless}
7067 \LWR@simplifiname{\textgreater}

7068 \edef\LWR@thisnewfilename{\detokenize\expandafter{\LWR@thisnewfilename}}%
```

Warn if there is dollar math in the section name:

```
7069 \ifbool{FileSectionNames}{%
7070 \IfSubStr{\LWR@thisnewfilename}{\LWRdollar}{%
7071 \PackageWarning{lwarp}
7072 {%
7073 This section name:\MessageBreak
7074 \space\space‘\detokenize\expandafter{#1}’\MessageBreak
7075 at the line number listed below,\MessageBreak
7076 is using $dollar-delimited math$,
7077 which generates\MessageBreak
7078 complicated file names. It is better to use\MessageBreak
7079 \space\space%
7080 \protect\section{Name with \protect\(\parenthesis math\protect\)}%
7081 \MessageBreak
7082 The math then will be removed from the file name.\MessageBreak
7083 \MessageBreak
7084 \LWR@avoiddupfilenames%
7085 \MessageBreak
7086 This section is found before or%
7087 }
7088 }{%
7089 }}%
```

```
7090 \LWR@traceinfo{\LWR@filenamenooblanks edef: !\LWR@thisnewfilename!}%
7091 \fullexpandarg%
```

Convert spaces into hyphens:

```
7092 \LWR@simplifiname*{ }
```

Convert punctutation into hyphens:

```
7093 \LWR@simplifiname*{*}
7094 \LWR@simplifiname*{(}
7095 \LWR@simplifiname*{)}
7096 \LWR@simplifiname*{.}
```

```

7097 \LWR@simplifiname*{!}
7098 \LWR@simplifiname*{,}
7099 \LWR@simplifiname*{'}
7100 \LWR@simplifiname*{+}
7101 \LWR@simplifiname*{/}
7102 \LWR@simplifiname*{:}
7103 \LWR@simplifiname*{;}
7104 \LWR@simplifiname*{=}
7105 \LWR@simplifiname*{?}
7106 \LWR@simplifiname*{@}
7107 \LWR@simplifiname*{^}
7108 \LWR@simplifiname*{&}
7109 \LWR@simplifiname*{"}
7110 \LWR@simplifiname*{<}
7111 \LWR@simplifiname*{>}

```

```
7112 \LWR@simplifiname{\LWRbackslash}
```

Braces are removed entirely to avoid extra dashes in the result.

```

7113 \StrSubstitute{\LWR@thisnewfilename}%
7114 {\LWRleftbrace}{}\[\LWR@thisnewfilename]%
7115 \StrSubstitute{\LWR@thisnewfilename}%
7116 {\LWRrightbrace}{}\[\LWR@thisnewfilename]%

```

```

7117 \LWR@simplifiname{\LWRpercent}
7118 \LWR@simplifiname{\LWRdollar}

```

```

7119 \LWR@simplifiname*{|}
7120 \LWR@simplifiname*{^}
7121 \LWR@simplifiname*{~}
7122 \LWR@simplifiname*{[]}
7123 \LWR@simplifiname*{[]}]
7124 \LWR@simplifiname*{'}

```

Convert short words:

```

7125 \LWR@simplifiname*{-s-}
7126 \LWR@simplifiname*{-S-}
7127 \LWR@simplifiname*{-a-}
7128 \LWR@simplifiname*{-A-}
7129 \LWR@simplifiname*{-an-}
7130 \LWR@simplifiname*{-AN-}
7131 \LWR@simplifiname*{-to-}
7132 \LWR@simplifiname*{-TO-}
7133 \LWR@simplifiname*{-by-}
7134 \LWR@simplifiname*{-BY-}
7135 \LWR@simplifiname*{-of-}
7136 \LWR@simplifiname*{-OF-}
7137 \LWR@simplifiname*{-and-}
7138 \LWR@simplifiname*{-AND-}
7139 \LWR@simplifiname*{-for-}
7140 \LWR@simplifiname*{-FOR-}
7141 \LWR@simplifiname*{-the-}
7142 \LWR@simplifiname*{-THE-}

```

Convert custom words:

```
7143 \LWR@simplifycustom%
```

If PDF L<sup>A</sup>T<sub>E</sub>X and not utf8 encoding, don't try to convert emdash, endash:

```
7144 \ifPDFTeX% pdflatex or dvi latex
7145 \ifdefstring{\inputencodingname}{utf8}{%
7146 \LWR@simplifyname*{-}
7147 % emdash
7148 \LWR@simplifyname*{-}
7149 % endash
7150 }{%
7151 \else% not PDFTeX
7152 \LWR@simplifyname*{-}
7153 \LWR@simplifyname*{-}
7154 \fi%
```

Convert multiple hyphens:

```
7155 \LWR@simplifyname*{-----}
7156 \LWR@simplifyname*{----}
7157 \LWR@simplifyname*{---}
7158 \LWR@simplifyname*{--}
```

If starts with a dash, remove the leading dash:

```
7159 \IfBeginWith{\LWR@thisnewfilename}{\detokenize{-}}{%
7160 \StrGobbleLeft{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
7161 }{%}
```

If ends with a dash, remove the trailing dash:

```
7162 \IfEndWith{\LWR@thisnewfilename}{\detokenize{-}}{%
7163 \StrGobbleRight{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
7164 }{%}
```

Limits the length of the filename:

```
7165 \StrLeft{\LWR@thisnewfilename}{\FilenameLimit}[\LWR@thisnewfilename]%
```

Return the global result:

```
7166 \global\let\LWR@thisfilename\LWR@thisnewfilename%
7167 \endgroup%
7168 \LWR@traceinfo{LWR@filenameno blanks: result is \LWR@thisfilename}%
7169 }
```

### 63.1 Sanitizing expressions for HTML

Math expressions are converted to lateximages, and some math environments may contain &, <, or >, which should not be allowed inside an HTML <alt> tag, so must convert them to HTML entities.

```
\LWR@replacestrings {<search>} {<replace>}
```

Replaces strings inside \tmpb.

Modified from the original, by PETR OLSAK, from the opmac package.

```

7170 \bgroup
7171 \catcode'\!=3 \catcode'\?=3
7172
7173 \long\gdef\LWR@replacestrings@addto#1#2{%
7174 \expandafter\def\expandafter#1\expandafter{#1#2}%
7175 }
7176
7177 \gdef\LWR@replacestrings#1#2{%
7178 \long\def\LWR@replacestringsA##1#1{\def\tmpb{##1}\LWR@replacestringsB}%
7179 \long\def\LWR@replacestringsB##1#1{%
7180 \ifx!##1\relax \else\LWR@replacestrings@addto\tmpb{#2##1}%
7181 \expandafter\LWR@replacestringsB\fi%
7182 }%
7183 \expandafter\LWR@replacestringsA\tmpb?#1!#1% from pysyntax.tex by Petr Krajnik
7184 \long\def\LWR@replacestringsA##1?#1?{%
7185 \def\tmpb{##1}%
7186 }\expandafter\LWR@replacestringsA\tmpb%
7187 }
7188 \egroup

```

Bool  
LWR@MathJax@silentquotes

If true, double quotes (\ " and ") are removed (used for mathspec). This unfortunately includes double quotes used inside \text with MATHJAX. If false, double quotes are escaped.

```

7189 \newbool{LWR@MathJax@silentquotes}
7190 \boolfalse{LWR@MathJax@silentquotes}

```

\LWR@subHTMLsanitize \LWR@strresult must first be set by \LWR@HTMLsanitize, \LWR@HTMLsanitizeexpand, or \CustomizeMathJax.

```

7191 \catcode'\#=12
7192 \catcode'\&=12
7193 \newcommand{\LWR@subHTMLsanitize}{%

```

The &, <, and > may be interpreted by the browser:

```

7194 \edef\tmpb{\detokenize\expandafter{\LWR@strresult}}%
7195 \LWR@replacestrings{&}{&};%
7196 \LWR@replacestrings{<}{<};%
7197 \LWR@replacestrings{>}{>};%

```

The quotes occasionally causes problems. For mathspec, also allow neutralization of \ " and the " character.

```

7198 \ifbool{LWR@MathJax@silentquotes}
7199 {%
7200 \expandafter\LWR@replacestrings\expandafter{\LWRbackslash"}{}}%
7201 \LWR@replacestrings{"}{}}%
7202 }%
7203 {\LWR@replacestrings"}{"};}%
7204 \LWR@replacestrings'}{'};}%
7205 \LWR@replacestrings`}{`};}%

```

MATHJAX allows expressions to be defined with \newcommand. These expressions would appear with ## for each argument, and each must be changed to a single

#. This must be done after all the above changes. Attempting another conversion after this causes an error upon further expansion.

```
7206 \LWR@replacestrings{##}{#}%
7207 \edef\LWR@strresult{\detokenize\expandafter{\tmpb}}%
7208 }
7209 \catcode'\#=6
7210 \catcode'\&=4
```

`\LWR@HTMLsanitizedetokenized`  $\{\langle \textit{detokenized text} \rangle\}$

Prints the sanitized text, already detokenized.

```
7211 \newrobustcmd{\LWR@HTMLsanitizedetokenized}[1]{%
7212 \LWR@traceinfo{\LWR@HTMLsanitizedetokenized !#1!}%
```

Cancel French `babel` character handling, and fully expand the strings:

```
7213 \begingroup%
7214 \LWR@hook@processingtags%
7215 \edef\LWR@strresult{#1}%
7216 \LWR@subHTMLsanitize%
7217 \LWR@strresult%
7218 \endgroup%
7219 \LWR@traceinfo{\LWR@HTMLsanitize done}%
7220 }
```

`\LWR@HTMLsanitizexpanded`  $\{\langle \textit{text} \rangle\}$

This version must be given the detokenized and expanded text. This is only used for adding math to `MATHJAX` expressions or `lateximage alt` tags.

```
7221 \edef\LWR@beginspaceleftbrace{begin \LWRleftbrace}
7222 \edef\LWR@beginspaceleftbrace{\detokenize\expandafter{\LWR@beginspaceleftbrace}}
7223 \edef\LWR@beginleftbrace{begin\LWRleftbrace}
7224 \edef\LWR@beginleftbrace{\detokenize\expandafter{\LWR@beginleftbrace}}
7225
7226 \edef\LWR@endspacerightbrace{end \LWRrightbrace}
7227 \edef\LWR@endspacerightbrace{\detokenize\expandafter{\LWR@endspacerightbrace}}
7228 \edef\LWR@endrightbrace{end\LWRrightbrace}
7229 \edef\LWR@endrightbrace{\detokenize\expandafter{\LWR@endrightbrace}}
7230
7231 \newrobustcmd{\LWR@HTMLsanitizexpanded}[1]{%
```

Cancel French `babel` character handling, and fully expand the strings:

```
7232 \begingroup%
7233 \LWR@hook@processingtags%

7234 \edef\LWR@strresult{#1}%
```

The math expression may includes spaces between tokens, but `MATHJAX` does not want a space between `\begin` or `\end` and the following brace. This space is removed here.

```
7235 \protect\StrSubstitute{\LWR@strresult}%
```

```

7236 {\LWR@beginspaceleftbrace}{\LWR@beginleftbrace}[\LWR@strresult]%
7237 \protect\StrSubstitute{\LWR@strresult}%
7238 {\LWR@endspacerightbrace}{\LWR@endrightbrace}[\LWR@strresult]%

7239 \LWR@subHTMLsanitize%
7240 \LWR@strresult%
7241 \endgroup%
7242 }

```

## 63.2 Customizing MATHJAX

`\LWR@customizedMathJax` Additional MATHJAX definitions to be added to the start of each HTML page.

```
7243 \newcommand*{\LWR@customizedMathJax}{}

```

Bool

Used to issue only one warning about using a `\CustomizeMathJax` per macro.

`\LWR@warnedcustomizemathjax`

```

7244 \newbool{\LWR@warnedcustomizemathjax}
7245 \boolfalse{\LWR@warnedcustomizemathjax}

```

`\LWR@subcustomizedmathjax` *{<macro definition>}*

```

7246 \newcommand*{\LWR@subcustomizedmathjax}[1]{%
7247 \begingroup%
7248 \LWR@hook@processingtags%
7249 \edef\LWR@strresult{\detokenize{#1}}%
7250 \LWR@subHTMLsanitize%
7251 \xdef\LWR@customizedMathJax{%
7252 \LWR@customizedMathJax%
7253 \LWR@strresult%
7254 }%
7255 \endgroup%
7256 }
7257 \@onlypreamble\LWR@subcustomizedmathjax

```

`\CustomizeMathJax` *{<macro definition>}*

A warning is issued if a very long argument is given.

```

7258 \newcommand*{\CustomizeMathJax}[1]{%
7259 \ifbool{\LWR@warnedcustomizemathjax}{}{%
7260 \StrLen{\detokenize{#1}}[\LWR@tempone]%
7261 \ifnumgreater{\LWR@tempone}{350}{%
7262 \AtEndDocument{%
7263 \PackageNoteNoLine{lwarp}{%
7264 To ensure faster MathJax compilation, place each\MessageBreak
7265 custom macro in its own \protect\CustomizeMathJax.\MessageBreak
7266 See the Lwarp documentation regarding customizing\MessageBreak
7267 MathJax%
7268 }%
7269 }%
7270 \booltrue{\LWR@warnedcustomizemathjax}%
7271 }{}%
7272 }%
7273 \appto\LWR@customizedMathJax{\LWRbackslash}%

```

```

7274 \LWR@subcustomizedmathjax{#1}%
7275 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
7276 }
7277 \@onlypreamble\CustomizeMathJax

```

`\LWR@infoprocessingmathjax`  $\{ \langle package\ name \rangle \}$

```

7278 \newcommand*{\LWR@infoprocessingmathjax}[1]{%
7279 \typeout{---}
7280 \typeout{Package lwarp: Processing MathJax customizations for #1.}
7281 \typeout{\space\space This may take a moment.}
7282 \typeout{---}
7283 }

```

#### defaults Default customizations:

In the MATHJAX code, footnotes are only referenced. For equations, they are also generated in the HTML when the L<sup>A</sup>T<sub>E</sub>X math is generated inside the HTML comment. For other math environments, the `\footnotemark/\footnotetext` method must be used. See section 8.5.4 regarding `\footnotemark`.



`\footnotemark`

For footnotes, `\footnotename` is used in most cases, however for equation the footnote is picked up from L<sup>A</sup>T<sub>E</sub>X in `\LWR@doendequation`.

First, `\footnotename` for MATHJAX is copied from L<sup>A</sup>T<sub>E</sub>X.

```

7284 \providecommand{\footnotename}{footnote}
7285
7286 % due to warpMathJax:
7287 \end{warpHTML}
7288
7289 \begin{warpMathJax}
7290 \xdef\LWR@customizedMathJax{\LWR@customizedMathJax%
7291 \LWRbackslash(%
7292 \LWRbackslash}newcommand%
7293 \{\LWRbackslash}footnotename\}%
7294 \{\footnotename}\}%
7295 \LWRbackslash)\par%
7296 }
7297 \end{warpMathJax}

```

`\LWRfootnote` is set per equation if a footnote is detected in the equation's math expression, otherwise it defaults to `\footnotename`.

```

7298 \begin{warpMathJax}
7299 \CustomizeMathJax{\def\LWRfootnote{1}}
7300 \CustomizeMathJax{\newcommand{\footnote}[2][\LWRfootnote]{\^{\mathrm{#1}}}}
7301 \CustomizeMathJax{\newcommand{\footnotemark}[1][\LWRfootnote]{\^{\mathrm{#1}}}}

```

`\hspace` is modified to accept and ignore a star:

```

7302 \CustomizeMathJax{\let\LWRorighspace\hspace}
7303 \CustomizeMathJax{\renewcommand{\hspace}{\ifstar\LWRorighspace\LWRorighspace}}

```

Various other customizations:

```

7304 \CustomizeMathJax{\newcommand{\mathnormal}[1]{#1}}
7305 \CustomizeMathJax{\newcommand\ensuremath[1]{#1}}

```

```

7306 \CustomizeMathJax{% absorb two optional arguments
7307 \newcommand{\LWRframebox}[2][\fbox{#2}]
7308 \newcommand{\framebox}[1][\LWRframebox]
7309 }
7310 \CustomizeMathJax{\newcommand{\setlength}[2]{}
7311 \CustomizeMathJax{\newcommand{\addtolength}[2]{}
7312 \CustomizeMathJax{\newcommand{\setcounter}[2]{}
7313 \CustomizeMathJax{\newcommand{\addtocounter}[2]{}
7314 \CustomizeMathJax{\newcommand{\arabic}[1]{}
7315 \CustomizeMathJax{\newcommand{\number}[1]{}
7316 \CustomizeMathJax{\newcommand{\noalign}[1]{\text{#1}\notag \\\}}
7317 \CustomizeMathJax{\newcommand{\cline}[1]{}
7318 \CustomizeMathJax{\newcommand{\directlua}[1]{\text{(directlua)}}}
7319 \CustomizeMathJax{\newcommand{\luatexdirectlua}[1]{\text{(directlua)}}}

```

`\protect`, `\mathchar`, and `\delimiter` are silently discarded; and `\mathcode` and `\delcode` are ignored.

```

7320 \CustomizeMathJax{\newcommand{\protect}{}
7321 \CustomizeMathJax{\def\LWRabsorbnumber#1 {}}
7322 \CustomizeMathJax{\def\LWRabsorbquotenumber"#1 {}}
7323 \CustomizeMathJax{\newcommand{\LWRabsorboption}[1]{}
7324 \CustomizeMathJax{\newcommand{\LWRabsorbtwooptions}[1][\LWRabsorboption]}
7325 \CustomizeMathJax{\def\mathchar{\ifnextchar"\LWRabsorbquotenumber\LWRabsorbnumber}}
7326 \CustomizeMathJax{\def\mathcode#1={\mathchar}}
7327 \CustomizeMathJax{\let\delcode\mathcode}
7328 \CustomizeMathJax{\let\delimiter\mathchar}

```

Some text symbols missing from MATHJAX:

```

7329 \CustomizeMathJax{\def\oe{\unicode{x0153}}}
7330 \CustomizeMathJax{\def\OE{\unicode{x0152}}}
7331 \CustomizeMathJax{\def\ae{\unicode{x00E6}}}
7332 \CustomizeMathJax{\def\AE{\unicode{x00C6}}}
7333 \CustomizeMathJax{\def\aa{\unicode{x00E5}}}
7334 \CustomizeMathJax{\def\AA{\unicode{x00C5}}}
7335 \CustomizeMathJax{\def\o{\unicode{x00F8}}}
7336 \CustomizeMathJax{\def\O{\unicode{x00D8}}}
7337 \CustomizeMathJax{\def\l{\unicode{x0142}}}
7338 \CustomizeMathJax{\def\L{\unicode{x0141}}}
7339 \CustomizeMathJax{\def\ss{\unicode{x00DF}}}
7340 \CustomizeMathJax{\def\SS{\unicode{x1E9E}}}
7341 \CustomizeMathJax{\def\dag{\unicode{x2020}}}
7342 \CustomizeMathJax{\def\ddag{\unicode{x2021}}}
7343 \CustomizeMathJax{\def\P{\unicode{x00B6}}}
7344 \CustomizeMathJax{\def\copyright{\unicode{x00A9}}}
7345 \CustomizeMathJax{\def\pounds{\unicode{x00A3}}}
7346 \end{warpMathJax}
7347
7348
7349 \begin{warpHTML}% due to warpMathJax

```

`\LWR@customizeMathJax` Prints MATHJAX commands to the HTML output.

```

7350 \newcommand{\LWR@customizeMathJax}{%
7351 \ifbool{mathjax}{

7352 \LWR@stoppars

```

```

7353 \LWR@htmlcomment{MathJax customizations:}
7354
7355 \begin{BlockClass}{hidden}
7356 \LWR@stoppars

```

Avoid ligatures while printing MATHJAX customizations:

```

7357 {
7358 \LWR@print@ttfamily
7359 \LWR@customizedMathJax
7360 }
7361 \LWR@startpars
7362 \end{BlockClass}
7363
7364 \LWR@startpars
7365 }{}
7366 }

```

```
7367 \end{warpHTML}
```

**for PRINT output:** 7368 \begin{warpprint}

\CustomizeMathJax The print-mode version:

```
7369 \newcommand*{\CustomizeMathJax}[1]{}

```

\FilenameSimplify \* {*expression*}

```
7370 \NewDocumentCommand{\FilenameSimplify}{s m}{}

```

```
7371 \end{warpprint}
```

**for HTML output:** 7372 \begin{warpHTML}

\LWR@createfooter If specified, create the first or later web page footer.

```

7373 \newcommand*{\LWR@createfooter}{%
7374 \ifnumLess{\value{LWR@htmlseqfilenumber}}{1}{%
7375 \ifdefempty{\LWR@firstpagebottom}{}%
7376 \LWR@htmlElement{footer}
7377
7378 \LWR@firstpagebottom
7379
7380 \LWR@htmlElementend{footer}
7381 }%
7382 }{%
7383 \ifdefempty{\LWR@pagebottom}{}%
7384 \LWR@htmlElement{footer}
7385
7386 \LWR@pagebottom
7387
7388 \LWR@htmlElementend{footer}
7389 }%
7390 }%
7391 }

```

`\LWR@newhtmlfile` {<section name>}

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and CSS are, then adds navigation, side TOC, header, and starts the text body.

```
7392 \newcommand*{\LWR@newhtmlfile}[1]{
7393 \LWR@traceinfo{\LWR@newhtmlfile}
```

At the bottom of the ending file:

```
7394 \LWR@htmlclassend{section}{tbody}
7395 \LWR@htmlclassend{main}{bodycontainer}
7396 \LWR@htmlclassend{div}{bodyandsidetoc}
7397
7398 \LWR@printpendingfootnotes
7399
```

No footer between files if EPUB:

```
7400 \ifbool{FormatEPUB}{\LWR@createfooter}
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
7401 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
7402 {}
7403 {\ifnumcomp{\value{\LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}}
```

End of this HTML file:

```
7404 \LWR@stoppars
7405 \LWR@htmltag{/body}\LWR@orignewline
7406 \LWR@htmltag{/html}\LWR@orignewline
7407 \LWR@traceinfo{\LWR@newhtmlfile: about to LWR@orignewpage}
7408 \LWR@maybe@orignewpage
```

```
7409 \addtocounter{\LWR@htmlfilenumber}{1}%
7410 \addtocounter{\LWR@htmlseqfilenumber}{1}%
```

If using a filename based on section name, create a version without blanks. The filename without blanks will be placed into `\LWR@thisfilename`. Duplicates will be detected using MD5 hashes.

If not using a filename, the file number will be used instead.

```
7411 \ifbool{FileSectionNames}%
7412 {%
```

Convert the section name to a filename with blanks and common words removed. The resulting filename is in `\LWR@thisfilename`.

```
7413 \LWR@filenamenoblanks{#1}%
```

Create a macro name from the MD5 hash of the file name, to detect duplicates:

```
7414 \edef\LWR@hashedname{\LWR@mdfive{\LWR@thisfilename}}%
```

If the macro name is not yet defined, this filename is unique.

```
7415 \ifcsundef{LWR@filename\LWR@hashedname}{%
```

If the filename is unique, create a macro using the hashed name, to be used to test for additional duplicates in the future.

```
7416 \csdef{LWR@filename\LWR@hashedname}{}%
7417 }{%
```

If the filename is not unique, create an error.

```
7418 \PackageError{lwarp}%
7419 {%
7420 The section name:\MessageBreak
7421 ‘#1’,\MessageBreak
7422 at the line number listed below,\MessageBreak
7423 generates the filename\MessageBreak
7424 ‘\LWR@thisfilename’,\MessageBreak
7425 which appears to be a duplicate. There is a\MessageBreak
7426 previous section with an identical or similar name.\MessageBreak
7427 While generating file names, Lwarp sanitizes math,\MessageBreak
7428 most symbols, and a few common short words,\MessageBreak
7429 and this may cause a conflict.\MessageBreak
7430 Enter ‘H’ for possible solutions%
7431 }%
7432 {%
7433 \LWR@avoiddupfilenames%
7434 }%
7435 }%
7436 }%
```

If using file numbers instead of names, the name is set to the next file number.

```
7437 {\renewcommand*{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}
```

Include an HTML comment to instruct lwarpmk where to split the files apart. Uses pipe-separated fields for `split_html.gawk`. Uses monospaced font with ligatures disabled for everything except the title.

```
7438 \LWR@traceinfo{LWR@newhtmlfile: about to print start file}%
```

`\LWR@nullfonts` to allow math in a section name.

```
7439 \begingroup%
7440 \LWR@nullfonts%
7441 \LWR@htmlblockcomment{%
7442 |Start file|}%
7443 \LWR@htmlsectionfilename{\LWR@thisfilename}|%
7444 }
7445 \endgroup%
```

At the top of the starting file:

```
7446 \LWR@stoppars
7447
```

Start a new file with the given section name:

```
7448 \LWR@filestart[#1]
7449
```

Track the PDF page numbers of the HTML output. This is updated more frequently than LWR@currentautosecpage.

```
7450 \setcounter{LWR@currentautosecfloatpage}{\value{page}}%
7451 \LWR@newautopagelabel{LWR@currentautosecfloatpage}%
```

No navigation between files if formatting for an EPUB or word processor:

```
7452 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
7453 {}
7454 {\LWR@topnavigation}
7455
```

No header if between files if formatting for an EPUB or word processor:

```
7456 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
7457 {}
7458 {
7459 \ifdefempty{\LWR@pagetop}{}{
7460 \LWR@htmlElement{header}
7461 }
7462 \LWR@pagetop
7463 \LWR@htmlElementend{header}
7464 }
7465 }
7466 }
7467
```

The container for the sidetoc and text body:

```
7468 \LWR@htmlElementclass{div}{bodyandsidetoc}
```

No sideroc if formatting for an EPUB or word processor:

```
7469 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
7470 {}
7471 {\LWR@sidetoc}
7472
```

Start of the <textbody>:

```
7473 \LWR@htmlElementclass{main}{bodycontainer}
7474 \LWR@htmlElementclass{section}{textbody}
```

Not yet found a new section in this file. Once one is found, a label will be placed for previous/next links.

```
7475 \boolfalse{LWR@setseqfilelabel}
```

Print title only if there is one. Skip if formatting for an EPUB or word processor:

```

7476 \ifthenelse{\boolean{FormatEpub}\OR\boolean{FormatWP}}%
7477 {}%
7478 {%
7479 \ifcvoid{thetitle}{}{%
7480 \LWR@printthetitle%
7481 }%
7482 }%

```

Keep paragraph tags disabled for now:

```

7483 \LWR@stoppars
7484

```

If using MATHJAX, print the customizations here.

```

7485 \LWR@customizeMathJax

7486 \LWR@traceinfo{LWR@newhtmlfile: done}
7487 }

7488 \end{warpHTML}

```

## 64 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing L<sup>A</sup>T<sub>E</sub>X code and packages. Formatting is handled by CSS, so the emulated code has much less work to do than the print versions.

**Unicode** Section names and the resulting filenames with accented characters are partially supported, depending on the ability of *pdf<sub>l</sub>atex* to generate characters and *pdf<sub>t</sub>otext* to read them. If extra symbols appear in the text, it may be that *pdf<sub>l</sub>atex* is actually producing a symbol over or under a character, resulting in *pdf<sub>t</sub>otext* picking up the accent symbol separately.

⚠ accents in filenames

X<sub>E</sub>L<sup>A</sup>T<sub>E</sub>X and LuaL<sup>A</sup>T<sub>E</sub>X directly support accented section and file names, but it may be necessary to use L<sup>A</sup>T<sub>E</sub>X accents instead of native Unicode accents. L<sup>A</sup>T<sub>E</sub>X accents will have the accents stripped when creating file names, whereas using Unicode accents will create filenames which include accents, which may cause issues with some operating systems.

**for HTML output:** 7489 \begin{warpHTML}

### 64.1 User-level starred section commands

`\ForceHTMLPage` For HTML output, forces the next section to be on its own HTML page, if `FileDepth` allows, even if starred. For use with `\printindex` and others which generate a starred section which should be on its own HTML page. Also see `\ForceHTMLTOC`.

For print output, no effect.

```

7490 \newbool{LWR@forcinghtmlpage}
7491 \boolfalse{LWR@forcinghtmlpage}
7492

```

```

7493 \newcommand*\ForceHTMLPage}{%
7494 \global\booltrue{LWR@forcinghtmlpage}%
7495 }

```

`\ForceHTMLTOC` For HTML output, forces the next section to have a TOC entry, even if starred. For use with `\printindex` and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with `tocbibind`. Also see `\ForceHTMLPage`.

For print output, no effect.

```

7496 \newbool{LWR@forcinghtmltoc}
7497 \boolfalse{LWR@forcinghtmltoc}
7498
7499 \newcommand*\ForceHTMLTOC}{%
7500 \global\booltrue{LWR@forcinghtmltoc}%
7501 }

```

```
7502 \end{warpHTML}
```

**for PRINT output:**

```

7503 \begin{warpprint}
7504 \newcommand*\ForceHTMLPage}{}
7505 \newcommand*\ForceHTMLTOC}{}
7506 \end{warpprint}

```

**for HTML output:**

```
7507 \begin{warpHTML}
```

## 64.2 Book class commands

`\mainmatter`  Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```

7508 \newbool{LWR@mainmatter}
7509 \DeclareDocumentCommand{\mainmatter}{}{}%
7510 \booltrue{LWR@mainmatter}%
7511 }

```

`\frontmatter` Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```

7512 \DeclareDocumentCommand{\frontmatter}{}{}%
7513 \boolfalse{LWR@mainmatter}%
7514 }

```

`\backmatter` Declare the back matter section of the document. Does not reset the page number.

```

7515 \DeclareDocumentCommand{\backmatter}{}{}%
7516 \boolfalse{LWR@mainmatter}
7517 }

```

## 64.3 Sectioning support macros

`\LWR@sectionnumber`  $\langle section\ type \rangle$

Typeset a section number and its trailing space with CSS formatting:

```
7518 \newcommand*\LWR@sectionnumber}[1]{%
7519 \InlineClass{sectionnumber}{#1}%
7520 }
```

`autosec` A tag used by the TOC and index.

`\LWR@createautosec`  $\langle section\ type \rangle$

Create an autosection tag.

The use of `\textquotedbl` instead of " provides improved compatibility with XeCJK.

```
7521 \newcommand*\LWR@createautosec}[1]{%
7522 \LWR@htmltag{%
7523 #1 % space
7524 id=\textquotedbl\LWR@print@box{autosec-\arabic{page}}\textquotedbl%
7525 }%
7526 }
```

`\LWR@pushoneclose`  $\langle section\ type \rangle$  Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

 `\LWR@stoppars` must be executed first.

```
7527 \NewDocumentCommand{\LWR@pushoneclose}{m}{%
7528 \LWR@traceinfo{\LWR@pushoneclose #1}%
7529 \LWR@pushclose{#1}%
7530 }
```

`\LWR@startnewdepth`  $\langle section\ type \rangle$

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

 `\LWR@stoppars` must be executed first.

```
7531 \NewDocumentCommand{\LWR@startnewdepth}{m}{%
```

Close any stacked sections up to this new one.

```
7532 \LWR@closeprevious{#1}%
```

Push a new section depth:

```
7533 \LWR@pushoneclose{#1}%
7534 }
```

Ctrl `LWR@prevFileDepth` Remembers the previous `LWR@FileDepth`.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
7535 \newcounter{LWR@prevFileDepth}
7536 \setcounter{LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

`\@secntformat`  $\{\langle sectiontype \rangle\}$

```
7537 \def\@secntformat#1{\csname the#1\endcsname\quad}
```

`\simplechapterdelim` Used by `tocbibind` and `anonchap`.

```
7538 \newcommand*\simplechapterdelim{}
```

`\@chapcntformat`  $\{\langle sectiontype \rangle\}$

`\let` to `\@secntformat` by default, but may be redefined by `\simplechapter` and `\restorechapter` from `tocbibind` or `anonchap`.

```
7539 \let\@chapcntformat\@secntformat
```

`\@partcntformat`  $\{\langle sectiontype \rangle\}$

`\let` to `\@secntformat` by default, but may be redefined by `ctex`.

```
7540 \let\@partcntformat\@secntformat
```

`\@partnameformat` Prints “Part” for part sections.

Nullified by `ctex`.

```
7541 \newcommand*\@partnameformat{\LWR@isolate{\partname}~}%
```

`\LWR@printchaptername` Print `\chaptername` in most cases, but this is nullified for `ctexbook`, `komascript`, `ujt`\* classes.

```
7542 \newcommand*\LWR@printchaptername{%
7543 \ifdefined\chaptername{\chaptername~}%
7544 }
```

`\LWR@section` \*  $[\langle TOC name \rangle] \{\langle name \rangle\} \{\langle sectiontype \rangle\}$

The common actions for the high-level sectioning commands.

```
7545 \DeclareDocumentCommand{\LWR@section}{m m m m}{%
7546 \IfValueTF{#2}%
7547 {\LWR@traceinfo{\LWR@section: starting #4 #2}}%
7548 {\LWR@traceinfo{\LWR@section: starting #4 #3}}%
```

Warn if starting a section inside a `<span>`:

```
7549 \LWR@spanwarninvalid{section}%
```

```
7550 \LWR@maybeprintpendingfootnotes{\csuse{\LWR@depth#4}}%
7551 \LWR@stoppars%
7552 \LWR@startnewdepth{#4}%
```

Cancel special minipage horizontal space interaction:

```
7553 \global\boolfalse{\LWR@minipagethispar}%
```

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for `\part*`, for appendix.

Generate a new L<sup>A</sup>T<sub>E</sub>X page so that toc and index page number points to the section:

```

7554 \LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%
7555 \IfBooleanT{#1}{\LWR@traceinfo{LWR@section: starred}}%
7556 \ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}}{}%
7557 \ifthenelse{%
7558 \(%
7559 \(\NOT\equal{#1}{\BooleanTrue})\OR%
7560 \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart})\OR%
7561 \(\boolean{LWR@forcinghtmlpage})\)%
7562 \)%
7563 \AND%
7564 \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{FileDepth}}%
7565 \AND%
7566 \(%
7567 \NOT\boolean{CombineHigherDepths}\OR%
7568 \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}%
7569 \)%
7570 \AND%

7571 \(% phantomsection
7572 \NOT\isempty{#3}%
7573 \OR%
7574 \(\NOT\equal{#1}{\BooleanTrue})\)%
7575 \)%
7576 }%

```

If so: start a new HTML file:

```

7577 {% new file
7578 \LWR@traceinfo{LWR@section: new HTML file}%

```

See if there was an optional toc name entry:

```

7579 \IfNoValueTF{#2}%

```

If no optional entry

```

7580 {\LWR@newhtmlfile{#3}}%

```

If yes an optional entry

```

7581 {\LWR@newhtmlfile{#2}}%
7582 }% new file

```

Else: No new HTML file:

```

7583 {% not new file

```

Generate a new L<sup>A</sup>T<sub>E</sub>X page so that toc and index page number points to the section:

```

7584 \LWR@traceinfo{LWR@section: not a new HTML file, about to LWR@orignewpage}%

```

```

7585 \LWR@maybe@orignewpage%
7586 }% not new file
7587

```

Remember this section's name for \nameref:

```

7588 \IfValueT{#3}{%
7589 \LWR@traceinfo{LWR@section: about to LWR@setlatestname}%
7590 \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
7591 }%

```

Print an opening comment with the level and the name; ex: “section” “Introduction”  
Footnotes may be used in section names, which would also appear in the HTML  
section opening comments, so the short toc entry is used if possible, and a limited  
opening comment is made if the sectional unit is starred.

```

7592 \begingroup%
7593 \LWR@nullfont%
7594 \LWR@nullifyfootnotes%
7595 \LWR@htmlcomment{.....}%
7596 \LWR@orignewline%
7597 \ifbool{HTMLDebugComments}%
7598 {%
7599 \IfBooleanTF{#1}% starred
7600 {%
7601 \IfNoValueTF{#2}% short TOC
7602 {\LWR@htmlcomment{Opening #4* ‘‘#3’’}}%
7603 {\LWR@htmlcomment{Opening #4* ‘‘#2’’}}%
7604 }%
7605 {%
7606 \IfNoValueTF{#2}% short TOC
7607 {\LWR@htmlcomment{Opening #4 ‘‘#3’’}}%
7608 {\LWR@htmlcomment{Opening #4 ‘‘#2’’}}%
7609 }%
7610 \LWR@orignewline%
7611 }%
7612 {}%
7613 \endgroup%

```

For inline sections paragraph and subparagraph, start a new paragraph now:

```

7614 \ifthenelse{%
7615 \cnttest{\@nameuse{LWR@depth#4}}{>=}{\LWR@depthparagraph}%
7616 }%
7617 {\LWR@startpars}%
7618 {}%

```

Create the opening tag with an autosec:

```

7619 \LWR@traceinfo{LWR@section: about to LWR@createautosec}%
7620 \LWR@createautosec{\@nameuse{LWR@tag#4}}%
7621 \setcounter{LWR@currentautosecpage}{\value{page}}%

```

Check if starred:

```

7622 \IfBooleanTF{#1}%
7623 {%

```

```
7624 \LWR@traceinfo{LWR@section: starred}%
```

Starred, but also forcing a TOC entry, so add unnumbered TOC name or regular name:

```
7625 \ifbool{LWR@forcinghtmltoc}%
7626 {%
7627 \addcontentsline{toc}{#4}{%
7628 \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
7629 }%
7630 }%
7631 }%
7632 }% starred
```

Not starred, so step counter and add to TOC:

```
7633 {% not starred
```

Only add a numbered TOC entry if section number is not too deep:

```
7634 \ifthenelse{%
7635 \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
7636 }%
7637 {% if secnumdepth
```

If in the main matter, step the counter and add the TOC entry. For article class, `lwarp` assumes that all is mainmatter.

```
7638 \LWR@traceinfo{LWR@section: about to test main matter}%
7639 \ifbool{LWR@mainmatter}%
7640 {%
7641 \LWR@traceinfo{LWR@section: yes mainmatter}%
7642 \refstepcounter{#4}%
```

Add main matter numbered TOC entry with the TOC name or the regular name:

```
7643 \LWR@traceinfo{LWR@section: about to addcontentsline}%
7644 \addcontentsline{toc}{#4}%
7645 {%
7646 \protect\numberline{%
7647 \@nameuse{pre#4name}%
7648 \@nameuse{the#4}%
7649 \@nameuse{post#4name}%
7650 }%
7651 {%
7652 \ignorespaces%
7653 \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
7654 }%
7655 }%
7656 \LWR@traceinfo{LWR@section: finished addcontentsline}%
7657 }% end of if main matter
```

If not main matter, add unnumbered TOC name or regular name:

```
7658 {% not main matter
7659 \LWR@traceinfo{LWR@section: no main matter}%
7660 \addcontentsline{toc}{#4}{%
7661 \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%

```

```

7662 }%
7663 }% end of not main matter
7664 }% end of secnumdepth

```

Deeper than secnumdepth, so add an unnumbered toc entry:

```

7665 {%
7666 \addcontentsline{toc}{#4}{%
7667 \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
7668 }%
7669 }%

```

For part, print “Part”:

```

7670 \ifbool{LWR@mainmatter}%
7671 {%
7672 \ifthenelse{%
7673 \(\cnttest{\@nameuse{LWR@depth#4}}{<=}%
7674 {\value{secnumdepth}}\)\ \AND%
7675 \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)%
7676 }%
7677 {\@partnameformat}%
7678 }%

```

Print the section number:

```

7679 \LWR@traceinfo{LWR@section: about to print section number}%
7680 \ifthenelse{%
7681 \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
7682 }%
7683 {%
7684 \ifstrequal{#4}{part}%
7685 {\protect\LWR@sectionnumber{\@partcntformat{#4}}}%
7686 {%
7687 \ifstrequal{#4}{chapter}%
7688 {%
7689 \LWR@printchaptername%
7690 \protect\LWR@sectionnumber{\@chappcntformat{#4}}%
7691 }%
7692 {\protect\LWR@sectionnumber{\@secCNTformat{#4}}}%
7693 }%
7694 }%
7695 }%
7696 \LWR@traceinfo{LWR@section: finished print section number}%
7697 }{%}%
7698 }% not starred

```

Print the section name:

```

7699 \LWR@traceinfo{LWR@section: about to print the section name}%
7700 \LWR@isolate{#3}%

```

Close the heading tag, such as /H2:

```

7701 \LWR@traceinfo{LWR@section: about to close the heading tag}%
7702 \LWR@htmltag{\@nameuse{LWR@tag#4end}}%
7703 \LWR@orignewline%

```

Generate a L<sup>A</sup>T<sub>E</sub>X label.

Track the PDF page numbers of the HTML output. A new autopage label may be generated for LWR@currentautosecpage for the start of the section, and also for the current page if it is different due to an SVG image in the section name. Also, the final page after the section has been created is updated in LWR@currentautosecfloatpage.

```
7704 \LWR@traceinfo{LWR@section: about to create the LaTeX label}%
7705 \setcounter{LWR@currentautosecfloatpage}{\value{page}}%
7706 \LWR@newautopagelabel{LWR@currentautosecpage}\LWR@orignewline%
```

If this is the first section found in this file, create a label for previous/next links:

```
7707 \ifbool{LWR@setseqfilelabel}{}{%
7708 \Label{\BaseJobname-autofile-\arabic{LWR@htmlseqfilenumber}}%
7709 \booltrue{LWR@setseqfilelabel}%
7710 }%
```

Start paragraph handing unless is an inline paragraph or subparagraph:

```
7711 \ifthenelse{%
7712 \cnttest{\@nameuse{LWR@depth#4}}{<}{\LWR@depthparagraph}%
7713 }%
7714 {\LWR@startpars}%
7715 {}%
```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a \part\* to start a new HTML page. This is used by appendix.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a \listoftables was tested in the middle of the document. The \chapter\* for the list was not allowing a new HTML page for the section following it while CombineHigherDepths was true.

```
7716 \ifthenelse{%
7717 \NOT\equal{#1}{\BooleanTrue}\OR%
7718 \cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}%
7719 }%
7720 {% not starred
7721 \setcounter{LWR@prevFileDepth}{\@nameuse{LWR@depth#4}}%
7722 }% not starred
7723 {}%
```

Reset to defaults if not a phantomsection:

```
7724 \ifstrempy{#3}%
7725 {}%
7726 {%
7727 \global\boolfalse{LWR@forcinghtmlpage}%
7728 \global\boolfalse{LWR@forcinghtmltoc}%
7729 }%
7730 %
7731 \LWR@traceinfo{LWR@section: done}%
7732 }
```

## 64.4 Pre- and post- sectioning names

|                               |                                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------|
| <code>\prebookname</code>     | Usually null, but is used by <code>uj*</code> and <code>ut*</code> Japanese classes.     |
| <code>\postbookname</code>    |                                                                                          |
|                               | 7733 <code>\providecommand*\prebookname{}</code>                                         |
|                               | 7734 <code>\providecommand*\postbookname{}</code>                                        |
| <code>\prepartname</code>     | Usually null, but is used by <code>uj*</code> and <code>ut*</code> Japanese classes.     |
| <code>\postpartname</code>    |                                                                                          |
|                               | 7735 <code>\providecommand*\prepartname{}</code>                                         |
|                               | 7736 <code>\providecommand*\postpartname{}</code>                                        |
| <code>\prechaptername</code>  | Usually null, but is used by <code>uj*</code> and <code>ut*</code> Japanese classes.     |
| <code>\postchaptername</code> |                                                                                          |
|                               | 7737 <code>\providecommand*\prechaptername{}</code>                                      |
|                               | 7738 <code>\providecommand*\postchaptername{}</code>                                     |
| <code>\presectionname</code>  | Always null, but provided here for algorithmic simplicity in <code>\LWR@section</code> . |
| <code>\postsectionname</code> |                                                                                          |
|                               | 7739 <code>\providecommand*\presectionname{}</code>                                      |
|                               | 7740 <code>\let\postsectionname\presectionname</code>                                    |
|                               | 7741                                                                                     |
|                               | 7742 <code>\let\presubsectionname\presectionname</code>                                  |
|                               | 7743 <code>\let\postsubsubsectionname\postsectionname</code>                             |
|                               | 7744                                                                                     |
|                               | 7745 <code>\let\presubsubsectionname\presectionname</code>                               |
|                               | 7746 <code>\let\postsubsubsectionname\postsectionname</code>                             |
|                               | 7747                                                                                     |
|                               | 7748 <code>\let\preparagraphname\presectionname</code>                                   |
|                               | 7749 <code>\let\postparagraphname\postsectionname</code>                                 |
|                               | 7750                                                                                     |
|                               | 7751 <code>\let\presubparagraphname\presectionname</code>                                |
|                               | 7752 <code>\let\postsubparagraphname\postsectionname</code>                              |

## 64.5 `\section` and friends

For `memoir`, a second optional argument is allowed.

For `hypbmsec`, a second optional argument or either parenthesis argument is allowed.

Each of these additional arguments are for headers or PDF bookmarks, and are ignored for HTML output.

```

\part * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {<6:name>}

7753 \newcommand{\part@preamble}{}% for koma-script
7754
7755 \DeclareDocumentCommand{\part}{s d() o o d() m}{%
7756 \LWR@section{#1}{#3}{#6}{part}%
7757
7758 \part@preamble% for koma-script
7759 \renewcommand{\part@preamble}{}%
7760 }

```

`\chapter * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {\<6:name>}`

```

7761 \let\@printcites\relax% for quotchap package
7762
7763 \newcommand{\chapter@preamble}{}% for koma-script
7764
7765 \ifundefined{chapter}
7766 {}
7767 {%
7768 \DeclareDocumentCommand{\chapter}{s d() o o d() m}{%
7769 \LWR@section{#1}{#3}{#6}{chapter}%
7770
7771 \@printcites% for quotchap package
7772
7773 \chapter@preamble% for koma-script
7774 \renewcommand{\chapter@preamble}{}%
7775 }
7776 }

```

`\section * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {\<6:name>}`

```

7777 \DeclareDocumentCommand{\section}{s d() o o d() m}{%
7778 \LWR@section{#1}{#3}{#6}{section}%
7779 }

```

`\subsection * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {\<6:name>}`

```

7780 \DeclareDocumentCommand{\subsection}{s d() o o d() m}{%
7781 \LWR@section{#1}{#3}{#6}{subsection}%
7782 }

```

`\subsubsection * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {\<6:name>}`

```

7783 \DeclareDocumentCommand{\subsubsection}{s d() o o d() m}{%
7784 \LWR@section{#1}{#3}{#6}{subsubsection}%
7785 }

```

`\paragraph * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {\<6:name>}`

```

7786 \DeclareDocumentCommand{\paragraph}{s d() o o d() m}{%
7787 \LWR@section{#1}{#3}{#6}{paragraph}%
7788 }

```

`\subparagraph * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {\<6:name>}`

```

7789 \DeclareDocumentCommand{\subparagraph}{s d() o o d() m}{%
7790 \LWR@section{#1}{#3}{#6}{subparagraph}%
7791 }

```

```

7792 \end{warpHTML}

```

## 65 Starting a new file

**for HTML & PRINT:** 7793 `\begin{warpall}`

`\HTMLLanguage` Default language for the HTML lang tag.

```
7794 \newcommand*\LWR@currentHTMLLanguage}{en-US}
7795
7796 \newcommand*\HTMLLanguage}[1]{%
7797 \renewcommand*\LWR@currentHTMLLanguage}{#1}%
7798 }
```

`\theHTMLTitleSeparator` May be used inside `\theHTMLTitleSection` to separate the website's overall HTML title and the particular page's section name.

```
7799 \ifPDFTeX% pdflatex or dvi latex
7800 \ifdefstring{\inputencodingname}{utf8}{%
7801 \newcommand*\theHTMLTitleSeparator}{ -\ }% EMDash
7802 }{%
7803 \newcommand*\theHTMLTitleSeparator}{ -\ }% hyphen
7804 }%
7805 \else%
7806 \ifpTeX
7807 \newcommand*\theHTMLTitleSeparator}{ -\ }% hyphen
7808 \else
7809 \newcommand*\theHTMLTitleSeparator}{ -\ }% EMDash
7810 \fi%
7811 \fi%
```

`\HTMLTitleBeforeSection` Sets the HTML page's meta title tag to show the website title before the section name.

```
7812 \newcommand*\HTMLTitleBeforeSection}{%
7813 \def\theHTMLTitleSection{%
7814 \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
7815 }%
7816 }
```

`\HTMLTitleAfterSection` Sets the HTML page's meta title tag to show the section name before the website title.

```
7817 \newcommand*\HTMLTitleAfterSection}{%
7818 \def\theHTMLTitleSection{%
7819 \theHTMLSection\theHTMLTitleSeparator\theHTMLTitle%
7820 }%
7821 }
```

`\theHTMLTitleSection` Forms the HTML page's meta title tag. The default is to show the website title before the section name.

```
7822 \HTMLTitleBeforeSection
```

`\theHTMLSection` The section name is passed to `\LWR@filestart`, which then sets `\theHTMLSection` for use inside `\theHTMLTitleSection` to create an HTML meta title tag.

```
7823 \newcommand*{\theHTMLSection}{}
```

```
7824 \end{warpall}
```

**for HTML output:** 7825 \begin{warpHTML}

\LWR@filestart [*<section name>*] Creates the opening HTML tags.

```
7826 \newcommand*{\LWR@filestart}[1][\%
7827 \LWR@traceinfo{\LWR@filestart !#1!}%
```

Locally temporarily disable direct-formatting commands:

```
7828 \begingroup%
7829 \LWR@nullfonts%
```

Save the section name for use while creating the HTML meta title tag:

```
7830 \edef\theHTMLSection{#1}%
```

Remove extra material:

```
7831 \StrSubstitute{\theHTMLSection}{\protect}{\detokenize{-}}[\theHTMLSection]%
7832 \StrSubstitute{\theHTMLSection}%
7833 {\detokenize{-----}}{\detokenize{-}}[\theHTMLSection]%
7834 \StrSubstitute{\theHTMLSection}%
7835 {\detokenize{----}}{\detokenize{-}}[\theHTMLSection]%
7836 \StrSubstitute{\theHTMLSection}%
7837 {\detokenize{---}}{\detokenize{-}}[\theHTMLSection]%
7838 \StrSubstitute{\theHTMLSection}%
7839 {\detokenize{--}}{\detokenize{-}}[\theHTMLSection]%
```

If starts with a dash, remove the leading dash:

```
7840 \IfBeginWith{\theHTMLSection}{\detokenize{-}}{%
7841 \StrGobbleLeft{\theHTMLSection}{1}[\theHTMLSection]%
7842 }{%}
```

Create the page's HTML header:

```
7843 \LWR@htmltag{!DOCTYPE html}\LWR@orignewline
```

The language is user-adjustable:

NOTE: \LWR@orig@textquotedbl is used here because \textquotedbl is nullified by \LWR@nullfonts while starting the new file.

```
7844 \LWR@htmltag{%
7845 html lang=\LWR@orig@textquotedbl\LWR@currentHTMLLanguage\LWR@orig@textquotedbl%
7846 }\LWR@orignewline
```

Start of the meta data:

```
7847 \LWR@htmltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
7848 \LWR@htmltag{%
7849 meta charset=\LWR@orig@textquotedbl{}UTF-8\LWR@orig@textquotedbl\ /%
7850 }\LWR@orignewline
```

Author:

```
7851 \ifthenelse{\equal{\theHTMLAuthor}{}}%
7852 {}%
7853 {%
7854 \LWR@htmltag{%
7855 meta name=\LWR@orig@textquotedbl{}author\LWR@orig@textquotedbl\ % space
7856 content=\LWR@orig@textquotedbl{}theHTMLAuthor\LWR@orig@textquotedbl\ /%
7857 }\LWR@orignewline%
7858 }%
```

lwarp is the generator:

```
7859 \LWR@htmltag{%
7860 meta % space
7861 name=\LWR@orig@textquotedbl{}generator\LWR@orig@textquotedbl\ % space
7862 content=\LWR@orig@textquotedbl{}LaTeX Lwarp package\LWR@orig@textquotedbl\ /%
7863 }\LWR@orignewline%
```

If there is a description, add it now:

```
7864 \ifdefempty{\LWR@currentHTMLDescription}{}{%
7865 \LWR@htmltag{%
7866 meta name=\LWR@orig@textquotedbl{}description\LWR@orig@textquotedbl\ % space
7867 content=\LWR@orig@textquotedbl{}LWR@currentHTMLDescription\LWR@orig@textquotedbl\ /%
7868 }\LWR@orignewline
7869 }%
```

Mobile-friendly viewport:

```
7870 \LWR@htmltag{%
7871 meta % space
7872 name=\LWR@orig@textquotedbl{}viewport\LWR@orig@textquotedbl\ % space
7873 content=\LWR@orig@textquotedbl{}width=device-width, initial-scale=1.0\LWR@orig@textquotedbl\ /%
7874 }\LWR@orignewline
```

IE patch:

```
7875 \LWR@htmltag{!-\/-[if lt IE 9]}\LWR@orignewline
7876 \LWR@htmltag{%
7877 script % space
7878 src=\LWR@orig@textquotedbl{}%
7879 http://html5shiv.googlecode.com/svn/trunk/html5.js%
7880 \LWR@orig@textquotedbl%
7881 }%
7882 \LWR@htmltag{/script}\LWR@orignewline
7883 \LWR@htmltag{![endif]-\/-}\LWR@orignewline
```

The page's title, if there is one. A section name is also added if given.

```
7884 \ifthenelse{\equal{\theHTMLTitle}{}}%
7885 {}%
```

```

7886 {%
7887 \LWR@htmltag{title}%
7888 \ifdefempty{\theHTMLSection}%
7889 {\theHTMLTitle}%
7890 {\theHTMLTitleSection}%
7891 \LWR@htmltag{/title}\LWR@orignewline%
7892 }%

```

The page's stylesheet:

```

7893 \LWR@htmltag{%
7894 link % space
7895 rel=\LWR@orig@textquotedbl{}stylesheet\LWR@orig@textquotedbl\ % space
7896 type=\LWR@orig@textquotedbl{}text/css\LWR@orig@textquotedbl\ % space
7897 href=\LWR@orig@textquotedbl\LWR@currentcss\LWR@orig@textquotedbl\ /%
7898 }%
7899 \LWR@orignewline

```

Optional MATHJAX support. The HTML tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```

7900 \ifbool{mathjax}%
7901 {%
7902 \begingroup%
7903 \LWR@restoreoriglists%
7904 \boolfalse{LWR@verbtags}%

7905 \IfFileExists{\LWR@mathjaxfilename}%
7906 {\verbatiminput{\LWR@mathjaxfilename}}%
7907 {%
7908 \PackageError{lwarp}%
7909 {%
7910 \protect\MathJaxFilename\space specified the file\MessageBreak
7911 \space\space\LWR@mathjaxfilename\MessageBreak
7912 which does not exist%
7913 }%
7914 {Specify an existing file, or remove \protect\MathJaxFilename.}%
7915 }%

7916 \booltrue{LWR@verbtags}%
7917 \endgroup%
7918 \LWR@stoppars%
7919 }% end of mathjax
7920 {}%

```

End of the header:

```
7921 \LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```

7922 \LWR@htmltag{body}\LWR@orignewline

7923 \endgroup%
7924 \LWR@traceinfo{LWR@filestart: done}%
7925 }

```

```
7926 \end{warpHTML}
```

## 66 Starting HTML output

**for HTML output:** 7927 \begin{warpHTML}

\LWR@LwarpStart Executed at the beginning of the entire document.

The use of \textquotedbl instead of " improves compatibility with xeCJK.

```
7928 \catcode'\$=\active
7929 \newcommand*\LWR@LwarpStart{
7930 {%
7931 \LWR@traceinfo{LWR@lwarpStart}
```

If formatting for a word processor, force filedepth to single-file only, force HTML debug comments off.

```
7932 \ifbool{FormatWP}{%
7933 \setcounter{FileDepth}{-5}%
7934 \boolfalse{HTMLDebugComments}%
7935 }{}
```

Expand and detokenize \HomeHTMLFilename and \HTMLFilename:

```
7936 \edef\LWR@strresult{\HomeHTMLFilename}
7937 \edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
7938 \edef\LWR@strresult{\HTMLFilename}
7939 \edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}
```

Force onecolumn and empty page style:

```
7940 \LWR@origonecolumn%
7941 \LWR@origpagestyle{empty}%
```

No black box for overfull lines:

```
7942 \overfullrule=0pt
```

Reduce chance of line overflow when HTML tags are added:

```
7943 \LWR@print@footnotesize%
```

In PDF output, don't allow line breaks to interfere with HTML tags:

```
7944 \LWR@print@raggedright%
7945 \LetLtxMacro{\}\LWR@endofline%
```

Spread the lines for *pdftotext* to read them well:

```
7946 \linespread{1.3}%
```

For *pdftotext* to reliably identify paragraph splits:

```
7947 \setlength{\parindent}{0pt}
7948 \setlength{\parskip}{2ex}
```

For the lateximage record file:

```
7949 \immediate\openout\LWR@lateximagesfile=\BaseJobname-images.txt
```

Removes space around the caption in the HTML:

```
7950 \setlength{\belowcaptionskip}{0ex}
7951 \setlength{\abovecaptionskip}{0ex}
```

Redefine the plain page style to be empty when used by index pages:

```
7952 \renewcommand{\ps@plain}{}
```

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Float captions:

```
7953 \let\LWR@origcaption\caption
```

Not yet started any paragraph handling:

```
7954 \global\booltrue{LWR@doingparhooks}
7955 \global\boolfalse{LWR@doingapar}
7956 \global\boolfalse{LWR@doingstartpars}
```

`\color@endgroup's \endgraf` was conflicting with `lwarp's` paragraph handling.

```
7957 \let\color@endgroup\endgroup
```

Document and page settings:

```
7958 \mainmatter
7959 \LWR@origpagenumbering{arabic}
```

Start a new HTML file and a header:

```
7960 \LWR@traceinfo{LWR@lwarpStart: Starting new file.}
7961 \LWR@filestart%
```

Tell *lwarpmk* that the *lwarp* package is in use. This allows *lwarpmk* to warn if `usepackage{lwarp}` was somehow disabled.

```
7962 \begingroup%
7963 \LWR@nullfonts%
7964 \LWR@htmlblockcomment{%
7965 |Using lwarp|}%
7966 \LWR@htmlsectionfilename{\LWR@thisfilename}|}%
7967 }
7968 \endgroup%
```

```
7969 \LWR@traceinfo{LWR@lwarpStart: Generating first header.}
7970 \ifdefempty{\LWR@firstpagetop}{}{%
7971 \LWR@htmltag{header}\LWR@originewline
7972 \LWR@startpars
7973 \LWR@firstpagetop
7974 \LWR@stoppars
```

```
7975 \LWR@htmltag{/header}\LWR@orignewline
7976 }%
```

```
7977 \LWR@htmlclass{div}{bodywithoutsidetoc}
7978 \LWR@htmlclass{main}{bodycontainer}
7979 \LWR@traceinfo{LWR@lwarpStart: Generating textbody.}
7980 \LWR@htmlclass{section}{textbody}
```

Create a label for previous/next links, and remember it has been done:

```
7981 \booltrue{LWR@setseqfilelabel}%
7982 \label{\BaseJobname-autofile-\arabic{LWR@htmlseqfilenumber}}
```

Patch the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native L<sup>A</sup>T<sub>E</sub>X environments, as well as those provided by `enumitem`, `enumerate`, and `paralist`.

```
7983 \LWR@patchlists
```

Ensure that math mode is active to call `lwarp`'s patches:

```
7984 \catcode'\$=\active
```

Required for `\nameref` to work with SVG math:

```
7985 \immediate\write\@mainaux{\catcode'\string\$\active}%
7986 \let\ltxMacro\LWR@syntaxhighlightone balance for editor syntax highlighting
```

Allow HTML paragraphs to begin:

```
7987 \LWR@startpars
```

If using `MATHJAX`, disable `\ensuremath` by printing a nullified definition at the start of each file, and add further customizations:

```
7988 \ifbool{mathjax}{
7989 \typeout{---}
7990 \typeout{Package lwarp:}
7991 \typeout{Processing MathJax customizations for the first HTML page.}
7992 \typeout{Later HTML pages will take the same amount of time.}
7993 \typeout{If this takes too long, see the Lwarp manual regarding customizing MathJax.}
7994 }{}
7995
7996 \LWR@customizeMathJax
7997
7998 \ifbool{mathjax}{
7999 \typeout{Done.}
8000 \typeout{---}
8001 }{}
```

First autpage label in case a figure occurs early before the first section: A new autpage label may be generated for `LWR@currentautosecpage` for the start of the section, and also for the current page if it is different due to an SVG image in the section name. Also, the final page after the section has been created is updated in `LWR@currentautosecfloatpage`.

```
8002 \setcounter{LWR@currentautosecfloatpage}{\value{page}}%
8003 \LWR@newautopagelabel{LWR@currentautosecpage}%
```

```

8004 \LWR@traceinfo{LWR@lwarpStart: done}
8005 }
8006 \catcode'\$=3% math shift until lwarp starts

8007 \end{warpHTML}

```

## 67 Ending HTML output

**for HTML output:** 8008 \begin{warpHTML}

`\LWR@requesttoc`  $\{\langle boolean \rangle\} \{\langle suffix \rangle\}$  Requests that a TOC, LOF, or LOT be generated.

```

8009 \newcommand*\LWR@requesttoc[2]{%
8010 \ifbool{#1}
8011 {
8012 \expandafter\newwrite\@nameuse{tf@#2}
8013 \immediate\openout \@nameuse{tf@#2} \jobname.#2\relax
8014 }{}
8015 }

```

`\LWR@LwarpEnd` Final stop of all HTML output:

```

8016 \newcommand*\LWR@LwarpEnd}
8017 {
8018 \LWR@stoppars
8019 \LWR@closeprevious{finished}

```

At the bottom of the ending file:

Print any pending footnotes:

```
8020 \LWR@printpendingfootnotes
```

Close the textbody.

(The `\LWR@origtilde` is in case no autopage is required for the label, which would not print anything, and something must be printed before the newline.)

```
8021 \label{\BaseJobname-autofile-last}\LWR@origtilde\LWR@orignewline
```

```

8022 \LWR@htmlElementclassend{section}{textbody}
8023 \LWR@htmlElementclassend{main}{bodycontainer}
8024 \LWR@htmlElementclassend{div}{bodyandsidetoc}

```

Create the footer if not EPUB

```
8025 \ifbool{FormatEPUB}{\LWR@createfooter}
```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```

8026 \ifthenelse{\boolean{FormatEpub}\OR\boolean{FormatWP}}
8027 {}
8028 {
8029 \ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{
8030 }

```

8031 \LWR@stoppars% final stop of all paragraphs

Finish the HTML file:

```

8032 \LWR@htmltag{/body}\LWR@orignewline
8033 \LWR@htmltag{/html}\LWR@orignewline

```

Seems to be required sometimes:

```

8034 \LWR@maybe@orignewpage
8035 }

```

Hook [LaTeX] `enddocument/info` Used to close the `*-images.txt` file.

`\enddocument` If labels have not changed, mark successful completion of the `lateximages.txt` file. Executed as everything is being shut down.

For the newer kernel hooks, see `texdoc lthooks-doc` and `texdoc ltshipout-doc`.

```

8036 \ifdef{\AddToHook}{% newer kernel
8037 \AddToHook{enddocument/info}{%
8038 \if@filesw
8039 \ifx \@multiplelabels \relax
8040 \if@tempswa

```

This is where warnings of duplicate labels would appear.

```
8041 \else
```

No duplicate labels, so safe to create images.

```

8042 \immediate\write\LWR@lateximagesfile{%
8043 |end|end|end|
8044 }%
8045 \fi
8046 \fi\fi
8047 }
8048 }% newer kernel
8049 {% older kernel
8050 \xpatchcmd{\enddocument}
8051 {%
8052 \if@tempswa
8053 \@latex@warning@no@line{Label(s) may have changed.
8054 Rerun to get cross-references right}%
8055 \fi
8056 }
8057 {%
8058 \if@tempswa
8059 \@latex@warning@no@line{Label(s) may have changed.
8060 Rerun to get cross-references right}%
8061 \else

```

No duplicate labels, so safe to create images.

```

8062 \immediate\write\LWR@lateximagesfile{%
8063 |end|end|end|%
8064 }%
8065 \fi
8066 }
8067 {}
8068 {
8069 \AtEndDocument{
8070 \PackageWarningNoLine{lwarp}
8071 {%
8072 Could not patch \protect\enddocument.\MessageBreak
8073 If labels have changed, be sure to recompile before\MessageBreak
8074 creating lateximages with\MessageBreak
8075 \space\space lwarpmk limages,\MessageBreak
8076 or the images may be corrupt%
8077 }
8078 }
8079 }
8080 }% older kernel

```

## 68 Nullifying foreground/background hooks

See `texdoc lthooks-doc` and `texdoc ltshipout-doc`.

Hook  
shipout/background

[LaTeX] Nullified.

Hook  
shipout/foreground

[LaTeX] Nullified.

```

8081 \ifdef{\RemoveFromHook}{
8082 \AfterEndPreamble{
8083 \IfHookEmptyTF{shipout/background}{}{
8084 \PackageInfo{lwarp}{Removing background hook}
8085 \RemoveFromHook{shipout/background}[*]
8086 }
8087 \IfHookEmptyTF{shipout/foreground}{}{
8088 \PackageInfo{lwarp}{Removing foreground hook}
8089 \RemoveFromHook{shipout/foreground}[*]
8090 }
8091 }
8092 }{}

8093 \end{warpHTML}

```

## 69 Title page

[package support](#) lwarp supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages `authblk` and `titling`. If both are used, `authblk` should be loaded before `titling`.



[load order](#)

[\published and \subtitle](#) If using the `titling` package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 69.8.

[affiliation](#) lwarp provides for the `\author` macro an additional `\affiliation` macro to pro-

vide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using `titlingpage's \theauthor` in the main text.

|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">reusing titlepage information</a>    | The titling package maintains the definitions of <code>\thetitle</code> , <code>\theauthor</code> , etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the <code>\thanks</code> and <code>\affiliation</code> removed, and for <code>\author</code> the <code>\and</code> is replaced to generate a simple inline list of authors separated by commas. Note: <code>\theauthor</code> does not work well with <code>authblk</code> unless the traditional L <sup>A</sup> T <sub>E</sub> X syntax is used. |
| ⚠ <code>\theauthor</code> , <code>authblk</code> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <a href="#">custom titlepages</a>                | <code>\printtitle</code> , <code>\printauthor</code> , etc., are provided for use inside a custom titlepage or <code>titlingpage</code> environment, and these retain the <code>\thanks</code> and <code>\affiliation</code> .                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>\printthanks</code>                        | <code>\printthanks</code> has been added to force the printing of thanks inside a <code>titlingpage</code> environment when <code>\maketitle</code> is not used.                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| ⚠ <code>\thanks</code>                           | Inside a <code>\titlepage</code> or <code>\titlingpage</code> environment, use <code>\thanks</code> instead of <code>\footnote</code> for acknowledgements, etc.                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

## 69.1 Setting the title, etc.

The following provide setting commands for both HTML and print outputs.

|                                           |                                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\author</code><br><code>\and</code> | <code>{\author}</code> While using <code>\maketitle</code> and print mode, the author is treated as a single-column tabular and the <code>\and</code> feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

```
\author{Name \ Affiliation \and Second Name \ Second Affiliation}
```

For HTML, the entire author block is placed inside a `<div>` of class `author`, and each individual author is inside a `<div>` of class `oneauthor`.

|                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\@title</code><br><code>\@author</code><br><code>\@date</code> | <code>\@title</code> , <code>\@author</code> , and <code>\@date</code> store the values as originally assigned, including any <code>\thanks</code> , <code>\and</code> , or <code>\affiliation</code> . These are low-level macros intended to be used by other macros only inside a titlepage or <code>titlingpage</code> , and are used by <code>\maketitle</code> . The author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For HTML, these tabulars become side-by-side <code>&lt;div&gt;</code> s of class <code>oneauthor</code> , all of which are combined into one <code>&lt;div&gt;</code> of class <code>author</code> . |
|----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                                                                  |                                                                                                                                                                                                                                                                                                 |
|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\printtitle</code><br><code>\printauthor</code><br><code>\printdate</code> | <code>\printtitle</code> , etc. are user-level macros intended to be used in custom titlepage or <code>titlingpage</code> environments in cases where <code>\maketitle</code> is not desired. These commands preserve the <code>\thanks</code> , etc., and should not be used in the main text. |
|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\thetitle</code><br><code>\theauthor</code><br><code>\thedata</code><br><code>\HTMLPageBottom</code> | <code>\thetitle</code> , <code>\theauthor</code> , and <code>\thedata</code> are available if <code>titling</code> has been loaded, and are sanitized user-level versions from which have been removed the <code>\thanks</code> and <code>\affiliation</code> , and <code>\and</code> is changed for inline text usage. The author is printed inline without <code>\affiliation</code> or <code>\thanks</code> , with <code>\and</code> placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each HTML page, such as: |
|------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

```
\HTMLPageBottom{
 \begin{center}\textcopyright~20xx \theauthor\end{center}
```

```
}

```

△ `\theauthor, authblk` `\theauthor` does not work well if `authblk` is used. If `\theauthor` is important, it is recommended to use the standard L<sup>A</sup>T<sub>E</sub>X syntax for `\author`, optionally with `lwarp`'s `\affiliation` macro as well.

△ `affiliations` After `\maketitle` has completed, `\theauthor` retains the definition of the author, but `\and` is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

`\affiliation` A solution, provide here, is to define a macro `\affiliation` which, during `\maketitle`, starts a new row and adds the affiliation, but after `\maketitle` is finished `\affiliation` is re-defined to discard its argument, thus printing only the author names when `\author` is later used inline.

## 69.2 `\if@titlepage`

**for HTML & PRINT:** 8094 `\begin{warpall}`

`\if@titlepage` Some classes do not provide `\if@titlepage`. In this case, provide it and force it false.

```
8095 \ifcvoid{@titlepagefalse}{
8096 \newif\if@titlepage
8097 \@titlepagefalse
8098 }{}

8099 \end{warpall}
```

## 69.3 Changes for `\affiliation`

`\affiliation` `{⟨text⟩}`

Adds the affiliation to the author for use in `\maketitle`.

Inside `titlepage`, this macro prints its argument. Outside, it is null.

**for HTML & PRINT:** 8100 `\begin{warpall}`  
8101 `\providerobustcmd{\affiliation}[1]{}{}`  
8102 `\end{warpall}`

**for PRINT output:** 8103 `\begin{warpprint}`

```
8104 \AtBeginEnvironment{titlepage}{
8105 \renewrobustcmd{\affiliation}[1]{\ \textsc{\small#1}}
8106 }
8107
8108 \AtBeginDocument{
8109 \IfPackageLoadedTF{titling}{
8110 \AtBeginEnvironment{titlingpage}{
8111 \renewrobustcmd{\affiliation}[1]{\ \textsc{\small#1}}
8112 }
```

```
8113 }{}% titling loaded
8114 }% AtBeginDocument
```

```
8115 \end{warpprint}
```

**for HTML output:** 8116 \begin{warpHTML}

Env `titlepage` Sets up a <div> of class `titlepage`. Provided even for memoir class, since it is used by `\maketitle`.

```
8117 \DeclareDocumentEnvironment{titlepage}{}
8118 {%
8119 \renewrobustcmd{\affiliation}[1]{\ \ \ \InlineClass{affiliation}{##1}}%
8120 \LWR@printpendingfootnotes
8121 \LWR@forcenewpage
8122 \BlockClass{titlepage}
8123 }
8124 {
8125 \endBlockClass
8126 \LWR@printpendingfootnotes
8127 }

8128 \end{warpHTML}
```

## 69.4 Printing the thanks

`\printthanks` Forces the `\thanks` to be printed. This is necessary in a `titlingpage` environment when `\maketitle` was not used.

**for PRINT output:** 8129 \begin{warpprint}  
8130 \newcommand\*{\printthanks}{\@thanks}  
8131 \end{warpprint}

**for HTML output:** 8132 \begin{warpHTML}  
8133 \newcommand\*{\printthanks}{\LWR@stoppars\@thanks\LWR@startpars}  
8134 \end{warpHTML}

## 69.5 Printing the title, etc. in HTML

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in HTML:

**for HTML output:** 8135 \begin{warpHTML}

`\printtitle`

```
8136 \newcommand*{\printtitle}
8137 {%
8138 \LWR@stoppars%
8139 \LWR@htmltag{\LWR@tagtitle}%
8140 \@title%
8141 \LWR@htmltag{\LWR@tagtitleend}%
8142 \LWR@startpars%
8143 }
```

`\LWR@printthetitle` A private version which prints the title without footnotes, used to title each HTML page.

```
8144 \newcommand*\LWR@printthetitle}
8145 {%
8146 \LWR@stoppars%
8147 \LWR@htmltag{\LWR@tagtitle}%
8148 \thetitle%
8149 \LWR@htmltag{\LWR@tagtitleend}%
8150 \LWR@startpars%
8151 }
```

`\printauthor` HTML version.

```
8152 \newcommand*\printauthor}{
```

The entire author block is contained in a <div> named author:

```
8153 \begin{BlockClass}{author}
```

\and finishes one author and starts the next:

```
8154 \renewcommand{\and}{%
8155 \end{BlockClass}
8156 \begin{BlockClass}{oneauthor}
8157 }
```

Individual authors are contained in a <div> named oneauthor:

```
8158 \begin{BlockClass}{oneauthor}
8159 \@author
8160 \end{BlockClass}
8161 \end{BlockClass}
8162 }
```

`\printdate`

```
8163 \newcommand*\printdate}{%
8164 \begin{BlockClass}{titledate}
8165 \@date
8166 \end{BlockClass}
8167 }
```

```
8168 \end{warpHTML}
```

## 69.6 Printing the title, etc. in print form

The following are for printing the title, etc. in a titlepage or a titlingpage in print form:

**for PRINT output:** `8169 \begin{warpprint}`

`\printtitle`

```
8170 \newcommand*\printtitle>{{\Huge\@title}}
```

`\printauthor` Print mode.

```
8171 \newcommand*\printauthor{
8172 {\large\begin{tabular}[t]{c}\@author\end{tabular}}}
```

`\printdate`

```
8173 \newcommand*\printdate{{\small\textit{\@date}}}
8174 \end{warpprint}
```

## 69.7 `\maketitle` for HTML output

An HTML `<div>` of class `titlepage` is used.

`\thanks` are a form of footnotes used in the title page. See section 60 for other kinds of footnotes.

See `\thanksmarkseries{series}`, below, to set the style of the footnote marks.

**for HTML output:** 8175 `\begin{warppHTML}`

```
8176 \IfClassLoadedTF{memoir}
8177 {
8178 \newcommand{\LWR@setfootnoteseries}{%
8179 \renewcommand\thefootnote{\@arabic\c@footnote}%
8180 }
8181 }{% not memoir
8182 \if@titlepage
8183 \newcommand{\LWR@setfootnoteseries}{%
8184 \renewcommand\thefootnote{\@arabic\c@footnote}%
8185 }
8186 \else
8187 \newcommand{\LWR@setfootnoteseries}{%
8188 \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
8189 }
8190 \fi
8191 }{% not memoir
```

`\LWR@maketitlesetup` Patches `\thanks` macros.

```
8192 \newcommand*\LWR@maketitlesetup{%
```

Redefine the footnote mark:

```
8193 \LWR@setfootnoteseries%
8194 \def\@makefnmark{%
8195 \thefootnote%
8196 }
```

```
\thefootnote ⇒ \nameuse{arabic}{footnote}, or
\thefootnote ⇒ \nameuse{fnsymbol}{footnote}
```

Redefine the footnote text:

```
8197 \long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
8198 \@thefnmark~%
```

```
\makethanksmark ⇒ \thanksfootmark ⇒ \tmark ⇒
\@thefnmark ⇒ \itshape a (or similar)
```

Print the text:

```
8199 {##1}%
8200 }%
8201 }
```

```
\@fnsymbol {⟨counter⟩}
```

Re-defined to use an HTML entity for the double vertical bar symbol. The original definition used `\|` which was not being seen by *pdftotext*.

```
8202 \def\LWR@HTML@fnsymbol#1{%
8203 \ifcase#1\or * \or
8204 \HTMLentity{dagger} \or
8205 \HTMLentity{Dagger} \or
8206 \HTMLentity{sect} \or
8207 \HTMLentity{para} \or
8208 \HTMLunicode{2016} \or
8209 ** \or
8210 \HTMLentity{dagger} \HTMLentity{dagger} \or
8211 \HTMLentity{Dagger} \HTMLentity{Dagger} \else
8212 \@ctrerr \fi%
8213 }
8214 \LWR@formatted{@fnsymbol}
```

```
\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.
```

Code from the titling package is adapted, simplified, and modified for HTML output.

The name `\LWR@maketitle` is used to preserve its definition in case a later package overwrites `\maketitle`.

```
8215 \newcommand*{\LWR@maketitle}{%
```

An HTML titlepage `<div>` is used for all classes.

```
8216 \begin{titlepage}
```

Set up special patches:

```
8217 \LWR@maketitlesetup
```

Typeset the title, etc:

```
8218 \@maketitle
```

Immediately generate any `\thanks` footnotes:

```
8219 \LWR@stoppars \@thanks \LWR@startpars
```

Close the HTML titlepage div and cleanup:

```

8220 \end{titlepage}
8221 \setcounter{footnote}{0}%
8222 \global\let\thanks\relax
8223 \global\let\maketitle\relax
8224 \global\let\@maketitle\relax
8225 \global\let\@thanks\@empty
8226 \global\let\@author\@empty
8227 \global\let\@date\@empty
8228 \global\let\@title\@empty
8229 \global\let\title\relax
8230 \global\let\author\relax
8231 \global\let\date\relax
8232 \global\let\and\relax
8233 }
8234
8235 \LetLtxMacro\maketitle\LWR@maketitle

```

`\@maketitle` HTML mode. Typesets the title, etc.:

```

8236 \providecommand*\@maketitle{}
8237 \renewrobustcmd*\@maketitle{%
8238 \LWR@stoppars%
8239 \LWR@htmltag{\LWR@tagtitle}%
8240 \@title%
8241 \LWR@htmltag{\LWR@tagtitleend}%
8242 \LWR@startpars%
8243 \begin{BlockClass}{author}%

```

For IEEEtran class:

```

8244 \renewcommand*\cr{}%
8245 \renewcommand*\rcr{}%
8246 \renewcommand*\noalign{}%

8247 \renewcommand{\and}{%
8248 \end{BlockClass}%
8249 \begin{BlockClass}{oneauthor}%
8250 }%
8251 \begin{BlockClass}{oneauthor}%
8252 \@author%
8253 \end{BlockClass}%
8254 \end{BlockClass}%
8255 \begin{BlockClass}{titledate}%
8256 \@date%
8257 \end{BlockClass}%
8258 }

```

`\LWR@titlingmaketitle` `\maketitle` for use inside an HTML titlingpage environment.

```

8259 \newcommand*\LWR@titlingmaketitle{%

```

Keep pending footnotes out of the title block:

```

8260 \LWR@stoppars\@thanks\LWR@startpars

```

Set up special patches:

```
8261 \LWR@maketitlesetup
```

Typeset the title, etc:

```
8262 \@maketitle
```

Immediately generate any \thanks footnotes:

```
8263 \LWR@stoppars\@thanks\LWR@startpars
8264 }
```

```
8265 \end{warpHTML}
```

## 69.8 \published and \subtitle

`\subtitle` and `\published` To add `\subtitle` and `\published` to the titlepage, load the titling package and use `\AddSubtitlePublished` in the preamble.

The default `lwarp.css` has definitions for the `published` and `subtitle` classes.

If `titling` is loaded, `\AddSubtitlePublished` creates a number of additional macros, and also assigns some of the `titling` hooks. If `titling` is not loaded, `\AddSubtitlePublished` creates null macros.

 **titling hooks** Do not use `\AddSubtitlePublished` if the user has patched the `titling` hooks for some other reason. Portions are marked `\warpprintonly` to reduce extra tags in HTML. Similarly, `BlockClass` has no effect in print mode. Thus, the following may be marked `warpall`.

**for HTML & PRINT:** `8266 \begin{warpall}`

`\AddSubtitlePublished` Adds `\published` and `\subtitle`, and related.

```
8267 \newcommand*\AddSubtitlePublished{%
8268 \IfPackageLoadedTF{titling}{% yes titling package
8269 \newcommand{\@published}{}%
8270 \newcommand{\published}[1]{\gdef\@published{##1}}%
8271 \renewcommand*\maketitlehooka{\printpublished}%
8272 \newcommand*\printpublished{%
8273 \warpprintonly{\begin{center}\unskip}%
8274 \begin{BlockClass}{published}%
8275 \warpprintonly{\large\itshape}%
8276 \@published%
8277 \end{BlockClass}%
8278 \warpprintonly{\end{center}}%
8279 }%
8280 \newcommand{\@subtitle}{}%
8281 \newcommand{\subtitle}[1]{\gdef\@subtitle{##1}}%
8282 \renewcommand*\maketitlehookb{\printsubtitle}%
8283 \newcommand*\printsubtitle{%
8284 \warpprintonly{\begin{center}\unskip}%
8285 \begin{BlockClass}{subtitle}%
8286 \warpprintonly{\Large\itshape}%
8287 \@subtitle%
```

```

8288 \end{BlockClass}%
8289 \warpprintonly{\end{center}}%
8290 }%
8291 }% yes titling package
8292 {% no titling package

8293 \def\@published{}%
8294 \DeclareDocumentCommand{\published}{m}{\gdef\@published{##1}}%
8295 \DeclareDocumentCommand{\printpublished}{}{}%
8296 \def\@subtitle{}%
8297 \DeclareDocumentCommand{\subtitle}{m}{\gdef\@subtitle{##1}}%
8298 \DeclareDocumentCommand{\printsubtitle}{}{}%
8299 }% no titling package
8300 }% \AddSubtitlePublished

8301 \end{warpall}

```

## 70 Abstract

The following code replaces the L<sup>A</sup>T<sub>E</sub>X default, and will itself be replaced later if the abstract package is loaded.

**for HTML output:** 8302 \begin{warpHTML}

\abstractname User-redefinable title for the abstract.

Also over-written by the babel package.

```
8303 \providecommand*{\abstractname}{Abstract}
```

Some classes allow an optional name, so it is allowed here.

Env abstract

```

8304 \DeclareDocumentEnvironment{abstract}{0{\abstractname}}
8305 {
8306 \LWR@forcenewpage
8307 \BlockClass{abstract}
8308 \BlockClassSingle{abstracttitle}{#1}
8309 }
8310 {
8311 \endBlockClass
8312 }

8313 \end{warpHTML}

```

## 71 Quote and verse

### 71.1 Attributions

\attribution {<name>}

For use with quote, quotation, verse:

Ex: "A quotation." \attribution{\textsc{Author Name}\textsl{Book Title}}

**for HTML & PRINT:** 8314 \begin{warpall}  
 8315 \newcommand{\attribution}[1]{  
 8316 \begin{flushright}  
 8317 \unskip  
 8318 #1  
 8319 \end{flushright}}%  
 8320 }  
 8321 \end{warpall}

**for HTML output:** 8322 \begin{warpHTML}  
 8323 \newcommand{\LWR@HTML@attribution}[1]{%  
 8324 \LWR@stoppars%  
 8325 \begin{BlockClass}{attribution}  
 8326 #1  
 8327 \end{BlockClass}  
 8328 \LWR@startpars%  
 8329 }  
 8330 \LWR@formatted{attribution}  
 8331 \end{warpHTML}

## 71.2 Quotes, quotations

**for HTML output:** 8332 \begin{warpHTML}

Env quote

```
8333 \newenvironment*{\LWR@HTML@quote}
8334 {
8335 \LWR@forcenewpage
8336 \LWR@htmlblocktag{blockquote}
8337 }
8338 {\LWR@htmlblocktag{/blockquote}}
8339
8340 \LWR@formattedenv{quote}
```

Env quotation

```
8341 \newenvironment*{\LWR@HTML@quotation}
8342 {
8343 \LWR@forcenewpage
8344 \LWR@htmlblocktag{blockquote}
8345 }
8346 {\LWR@htmlblocktag{/blockquote}}
8347
8348 \LWR@formattedenv{quotation}

8349 \end{warpHTML}
```

## 71.3 Verse

When using verse or memoir, always place a \\ after each line.

|                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\attrib</code>                                                                                  | The documentation for the <code>verse</code> and <code>memoir</code> packages suggest defining an <code>\attrib</code> command, which may already exist in current documents, but it will only work for print output. <code>lwarp</code> provides <code>\attribution</code> , which works for both print and HTML output. To combine the two so that <code>\attrib</code> is used for print and <code>\attribution</code> is used for HTML:                                                                                                                                                                                                                                                                                             |
|                                                                                                       | <pre> \begin{warpHTML}   \let\attrib\attribution \end{warpHTML} </pre>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Len <code>\vleftskip</code>                                                                           | These lengths are used by <code>verse</code> and <code>memoir</code> to control the left margin, and they may already be set by the user for print output. New lengths <code>\HTMLvleftskip</code> and <code>\HTMLleftmargini</code> are provided to control the margins in HTML output. These new lengths may be set by the user before any <code>verse</code> environment, and persist until they are manually changed again. One reason to change <code>\HTMLleftmargini</code> is if there is a wide <code>\flagverse</code> in use, such as the word “Chorus”, in which case the value of <code>\HTMLleftmargini</code> should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number. |
| Len <code>\vleftmargini</code>                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Len <code>\HTMLvleftskip</code>                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Len <code>\HTMLleftmargini</code>                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|  <b>spacing</b>      | Horizontal spacing relies on <i>pdftotext</i> 's ability to discern the layout ( <code>-layout</code> option) of the text in the HTML-tagged PDF output. For some settings of <code>\HTMLleftmargini</code> or <code>\HTMLleftskip</code> the horizontal alignment may not work out exactly, in which case a label may be shifted by one space. During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused <i>pdftotext</i> to shift everything over.                                                                                                                                                                                                                                      |
|  <b>verse margin</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

### 71.3.1 L<sup>A</sup>T<sub>E</sub>X core verse environment

**for HTML output:** 8350 `\begin{warpHTML}`

Env `verse`

```

8351 \newenvironment{LWR@HTML@verse}
8352 {\let\\newLine% lwarp
8353 \list{}{\itemsep \z@
8354 \itemindent -1.5em%
8355 \listparindent\itemindent
8356 \rightmargin \leftmargin
8357 \advance\leftmargin 1.5em}%
8358 \item\relax}
8359 {\endlist}
8360
8361 \LWR@formattedenv{verse}

8362 \end{warpHTML}

```

**for HTML & PRINT:** 8363 `\begin{warpall}`

### 71.3.2 verse and memoir

The following lengths are used by `verse` and `memoir`. They may be set in either print or HTML output, but are only used in HTML. This allows the user to set `\vleftskip` and `\vleftmargini` for print output, and optionally select different values for HTML.

Len `\HTMLvleftskip` Sets `\vleftskip` inside a verse environment in HTML.

```
8364 \newlength{\HTMLvleftskip}
8365 \setlength{\HTMLvleftskip}{1em}
```

Len `\HTMLleftmargini` Sets `\leftmargini` inside a verse environment in HTML.

```
8366 \newlength{\HTMLleftmargini}
8367 \setlength{\HTMLleftmargini}{4.5em}
```

```
8368 \end{warpall}
```

## 72 Verbatim and tabbing

**for HTML & PRINT:** 8369 `\begin{warpall}`

Len `\VerbatimHTMLWidth` Width to use in HTML Verbatim environment.

This width is used when placing line numbers to the right. Ignored during print output.

```
8370 \newlength{\VerbatimHTMLWidth}
8371 \setlength{\VerbatimHTMLWidth}{4in}
8372 \end{warpall}
```

**for HTML output:** 8373 `\begin{warpHTML}`

Bool `LWR@verbtags` Used to temporarily turn off verbatim tags while doing `\verbatiminput` in the HTML head.

```
8374 \newbool{LWR@verbtags}
8375 \booltrue{LWR@verbtags}
```

`\verb` Patched to encapsulate the verbatim text inside span with a class of `texttt`.

```
8376 \LetLtxMacro\LWR@orig@verb@egroup\verb@egroup
8377
8378 \def\LWR@verb@egroup@endspan{%
8379 \LWR@orig@verb@egroup%
8380 \LWR@htmltag{/span}%
8381 \endgroup%
8382 }

8383 \xpretocmd{\verb}
8384 {%
8385 \begingroup%
8386 \LWR@htmltag{span class=\textquotedbl{}texttt\textquotedbl}%
8387 \let\verb@egroup\LWR@verb@egroup@endspan%
8388 }
8389 {}
8390 {\LWR@patcherror{LaTeX}{verb}}
```

`\LWR@atbeginverbatim` [*1: style*] {*2: class*}

Encloses a verbatim environment with the given css class.

The use of `\textquotedbl` instead of `"` improves compatibility with `xeCJK`.

```
8391 \newcommand*{\LWR@atbeginverbatim}[2][[]
8392 {%
```

Stop generating HTML paragraph tags:

```
8393 \LWR@stoppars%
```

Avoid excessive space between lines:

```
8394 \setlength{\parskip}{0ex}%
8395 \setlength{\topsep}{0pt}%
8396 \setlength{\partopsep}{0pt}%
```

Inside the verbatim, temporarily prevent underfull `\hbox` warnings.

```
8397 \hbadness=10000\relax%
```

Create a new `pre` of the given class. The tags may temporarily be turned off for internal use, such as loading the `MATHJAX` script.

```
8398 \ifbool{LWR@verbtags}{%
8399 \LWR@htmltag{pre class=\textquotedbl#2\textquotedbl%
8400 \ifthenelse{\equal{#1}{}}{ style=\textquotedbl#1\textquotedbl}%
8401 }%
8402 \par%
8403 }{%}
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the css for the `verse` class.

```
8404 \begingroup%
```

```
8405 \LWR@print@normalfont%
8406 \LWR@origttfamily%
8407 \LWR@print@scriptsize%
```

Since inside a `<pre>`, restore the original list processing:

```
8408 \LWR@restoreoriglists%
```

Turn off `babel-french` extra space before punctuation:

```
8409 \LWR@hook@processingtags%
```

Do not produce HTML tags for `\hspace` inside a `verse` par. Restore plain `LATEX` `\hspace` functionality:

```
8410 \LWR@select@print@hspace%
8411 }
```

`\LWR@afterendverbatim` Finishes enclosing a verbatim environment.

```

8412 \newcommand*\LWR@afterendverbatim}{%
8413 \endgroup%
8414 \par%

```

At the end of the environment, close the pre:

```

8415 \ifbool{LWR@verbtags}{%
8416 \noindent\LWR@htmltag{/pre}\par% pre
8417 }{}%

```

Resume regular paragraph handling:

```

8418 \LWR@startpars%
8419 }

```

`\verbatiminput` {*{filename}*}

Patch `\verbatiminput` to add HTML tags:

```

8420 \newcommand{\LWR@HTML@verbatim@input}[2]{%
8421 \ifbool{LWR@verbtags}{\LWR@forcenewpage}{}%
8422 \LWR@atbeginverbatim{Verbatim}%
8423 \LWR@print@verbatim@input{#1}{#2}%
8424 \LWR@afterendverbatim%
8425 }
8426
8427 \LWR@formatted{verbatim@input}

```

Env `verbatim`

```

8428 \AfterEndPreamble{
8429 \LWR@traceinfo{Patching verbatim.}
8430 \AtBeginEnvironment{verbatim}{%
8431 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
8432 }{%
8433 }%
8434 \LWR@forcenewpage%
8435 \LWR@atbeginverbatim{verbatim}%
8436 }%
8437 }
8438 \AfterEndEnvironment{verbatim}{%
8439 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
8440 }{%
8441 }%
8442 \LWR@afterendverbatim%
8443 }%
8444 }
8445 %
8446 \AtBeginEnvironment{verbatim*}{%
8447 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
8448 }{%
8449 }%
8450 \LWR@forcenewpage%
8451 \LWR@atbeginverbatim{verbatim}%
8452 }%
8453 }
8454 \AfterEndEnvironment{verbatim*}{%
8455 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%

```

```

8456 {}%
8457 {%
8458 \LWR@afterendverbatim%
8459 }%
8460 }
8461 }

```

Env `tabbing` The `tabbing` environment works, except that `svg math` and `lateximages` do not yet work inside the environment.

 **math in tabbing** If math is used inside `tabbing`, place `tabbing` inside a `lateximage` environment, which will render the entire environment as a single `svg` image.

```

8462 \newenvironment*{LWR@HTML@tabbing}
8463 {%
8464 \LWR@forcenewpage%
8465 \LWR@atbeginverbatim{tabbing}%
8466 \let\enskip\LWR@origenskip%
8467 \let\quad\LWR@origquad%
8468 \let\qquad\LWR@origqquad%
8469 \let~\LWR@origtilde%
8470 \let\,\LWR@origcomma%
8471 \let\thinspace\LWR@origthinspace%
8472 \let\negthinspace\LWR@orignegthinspace%
8473 \LWR@print@tabbing%
8474 }
8475 {%
8476 \endLWR@print@tabbing%
8477 \LWR@afterendverbatim%
8478 }
8479
8480 \LWR@formattedenv{tabbing}

8481 \end{warpHTML}

```

## 73 Theorems

`\newtheorem`  $\{\langle text \rangle\} [\langle counter \rangle] \text{--- or ---} [\langle oldname \rangle] \{\langle text \rangle\}$

A few minor changes are made to supply HTML tags.

- The entire theorem is placed into a `<div>` of class `theoremcontents`.
- The label for each theorem is placed inside a `<span>` of class `theoremlabel`.
- The contents are placed inside a `<div>` of class `theoremcontents`.

**for HTML output:** `8482 \begin{warpHTML}`

`\@begintheorem`  $\{\langle name \rangle\} \{\langle number \rangle\}$

```

8483 \renewcommand{\@begintheorem}[2]{%
8484 \LWR@forcenewpage

```

```

8485 \LWR@printpendingfootnotes% lwarp

8486 \BlockClass{theoremcontents}
8487 \trivlist
8488 \item[\InlineClass{theoremLabel}{#1\ #2\ }]\itshape
8489 }

```

`\@opargbegintheorem`  $\langle name \rangle$   $\langle number \rangle$   $\langle oparg \rangle$

L<sup>A</sup>T<sub>E</sub>X defines this, but amsthm relaxes it, so it will not be defined if amsthm is loaded before lwarp.

```

8490 \ifundef{\@opargbegintheorem}{}{
8491 \renewcommand{\@opargbegintheorem}[3]{%
8492 \LWR@forcenewpage
8493 \BlockClass{theoremcontents}
8494 \trivlist
8495 \item[\InlineClass{theoremLabel}{#1\ #2\ (#3)\ }]\itshape
8496 }
8497 }

```

`\@endtheorem`

```

8498 \renewcommand*\@endtheorem}{%
8499 \endtrivlist

8500 \LWR@printpendingfootnotes% lwarp

8501 \endBlockClass% theoremcontents
8502 }

8503 \end{warpHTML}

```

## 74 Lists

The environments `itemize`, `enumerate`, and `description` are patched when `lwarp` is started. These patches support the standard L<sup>A</sup>T<sub>E</sub>X environments, as well as those of `enumerate`, `enumitem`, and `paralist`, and at least the French version of `babel`. Additional patches are done on a package-specific basis.

The L<sup>A</sup>T<sub>E</sub>X source for `itemize` and `enumerate` are found in `source2e`, but the source for `description` is found in `article.cls`, etc.

**empty item** To have an empty item, use `\mbox{}` or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

---

```

begin{itemize}
item \mbox{}
\begin{itemize}
...
\end{itemize}
item \

```

```

\begin{itemize}
...
\end{itemize}

```

`\makeLabel`

While inside a list environment, `lwarp` nullifies a number of TeX horizontal skip and fill commands, allowing the user to define `\makeLabel` for print mode while HTML mode ignores those commands.

 **label font** When defining `\makeLabel` in a list environment, use `\textbf` etc. instead of `\bfseries`.

## 74.1 List environment

**for HTML output:** 8504 `\begin{warpHTML}`

`\LWR@printcloseList` May be locally redefined by `enumerate` or `description`.

```
8505 \newcommand*\LWR@printcloseList{\LWR@printcloseitemize}
```

`\LWR@printopenList` May be locally redefined by `enumerate` or `description`.

```
8506 \newcommand*\LWR@printopenList{%
8507 ul style=\textquotedbl\LWR@print@mbbox{list-style-type:none}\textquotedbl}%
8508 }
```

`\@mklab` Removes PDF spacing.

```
8509 \AtBeginDocument{
8510 \def\@mklab#1{%
8511 % \hfil %
8512 #1}
8513 \let\makeLabel\@mklab
8514 }
```

`\@donoparitem` Modified for HTML output by replacing TeX boxes with plain text. Also removes PDF spacing.

```
8515 \def\@donoparitem{%
8516 \@noparitemfalse
8517 % \global\setbox\@labels\hbox{\hskip -\leftmargin
8518 % \unhbox\@labels
8519 % \hskip \leftmargin}%
8520 % \if@minipage\else
8521 % \@tempkipa\lastskip
8522 % \vskip -\lastskip
8523 % \advance\@tempkipa\outerparskip
8524 % \advance\@tempkipa -\parskip
8525 % \vskip\@tempkipa
8526 % \fi
8527 }
```

`\@item` Modified for HTML output by replacing TeX boxes with plain text. Also removes PDF spacing.

```
8528 \def\LWR@HTML@item[#1]{%
8529 \LWR@traceinfo{@item}%
8530 \if@noperitem
8531 \@donoperitem
8532 \else
8533 % \if@inlabel
8534 % \indent
8535 % \fi
8536 \ifhmode
8537 % \unskip\unskip
8538 \fi
8539 \if@newlist
8540 \if@nobreak
8541 \@nbitem
8542 \else
8543 % \addpenalty\@beginparpenalty
8544 % \addvspace\@topsep
8545 % \addvspace{-\parskip}%
8546 \fi
8547 \else
8548 % \addpenalty\@itempenalty
8549 % \addvspace\itemsep
8550 \fi
8551 \global\@inlabeltrue
8552 \fi
8553 % \everypar{%
8554 \@minipagefalse
8555 \global\@newlistfalse

8556 % \if@inlabel
8557 % \global\@inlabelfalse

8558 % {\setbox\z@\lastbox
8559 % \ifvoid\z@
8560 % \kern-\itemindent
8561 % \fi}%

8562 % \box\@labels
8563 % \penalty\z@
8564 % \fi

8565 % \if@nobreak
8566 % \@nobreakfalse
8567 % \clubpenalty \@M
8568 % \else
8569 % \clubpenalty \@clubpenalty
8570 % \everypar{%
8571 % \fi}%

8572 \if@noitemarg
8573 \@noitemargfalse
8574 \if@nمبرlist

8575 \refstepcounter\@listctr
8576 \fi
8577 \fi

8578 \makelabel{#1} % extra space
```

```

8579 % \sbox\@tempboxa{\makelabel{#1}}%
8580 % \global\setbox\@labels\hbox{%
8581 % \unhbox\@labels
8582 % \hskip \itemindent
8583 % \hskip -\labelwidth
8584 % \hskip -\labelsep
8585 % \ifdim \wd\@tempboxa >\labelwidth
8586 % \box\@tempboxa

8587 % \else
8588 % \hbox to\labelwidth {\unhbox\@tempboxa}%
8589 % \fi
8590 % \hskip \labelsep}%
8591 \ignorespaces%
8592 }

```

`\@nbitem`

```

8593 \def\@nbitem{%
8594 % \@tempskipa\@outerparskip
8595 % \advance\@tempskipa -\parskip
8596 % \addvspace\@tempskipa
8597 }

```

`\LWR@listitem` [*⟨label⟩*]

Handles `\item` inside a list, `itemize`, or `enumerate`.

See `\LWR@openparagraph` where extra `\hspace` is used to leave room for the label while inside a list during paragraph construction.

```

8598 \newcommand*\LWR@listitem{%
8599 \LWR@stoppars%
8600 \LWR@startnewdepth{listitem}%
8601 \LWR@htmltag{li}%
8602 \LWR@orignewline%
8603 \LWR@startpars%
8604 \LWR@ensuredoingapar%
8605 \LWR@origitem%
8606 }

```

`\LWR@nulllistfills` Nullifies various TeX fill commands, in case they are used inside `\makelabel`. Problems are caused when these are nullified all the time.

```

8607 \newcommand*\LWR@nulllistfills{%
8608 \renewcommand*\hss{}%
8609 \renewcommand*\llap[1]{##1}%
8610 \renewcommand*\rlap[1]{##1}%
8611 \renewcommand*\hfil{}%
8612 \renewcommand*\hfilneg{}%
8613 \renewcommand*\hfill{}%
8614 }

```

Env `list` {*⟨label⟩*} {*⟨commands⟩*}

```

8615 \newcommand*\LWR@liststart{%
8616 \LWR@traceinfo{LWR@liststart}%

```

```

8617 \LWR@stoppars%
8618 \LWR@pushoneclose{list}%
8619 \LWR@htmltag{\LWR@printopenlist}\LWR@orignewline%
8620 \LWR@startpars%
8621 \setlength{\topsep}{0pt}%
8622 \setlength{\partopsep}{0pt}%
8623 \setlength{\itemsep}{0pt}%
8624 \setlength{\parsep}{0pt}%
8625 \setlength{\leftmargin}{0pt}%
8626 \setlength{\rightmargin}{0pt}%
8627 \setlength{\listparindent}{0pt}%
8628 \setlength{\itemindent}{0pt}%
8629 \setlength{\labelsep}{1em}%
8630 \LWR@nulllistfills%
8631 }

8632 \newcommand*\LWR@listend}{%
8633 \LWR@traceinfo{LWR@listend}%
8634 \LWR@stoppars%
8635 \LWR@closeprevious{list}%
8636 \LWR@startpars%
8637 }

```

## 74.2 Itemize

`\LWR@itemizeitem` [*<label>*]

Handles `\item` inside an `itemize` or `enumerate`.

The optional argument is passed to `\LWR@origitem`.

See `\LWR@openparagraph` where extra `\hspace` is used to leave room for the label while inside a list during paragraph construction.

```

8638 \newcommand*\LWR@itemizeitem}{%
8639 \LWR@stoppars%
8640 \LWR@startnewdepth{listitem}%
8641 \LWR@htmltag{li}%
8642 \LWR@orignewline%
8643 \LWR@startpars%
8644 \LWR@ensuredoingapar%
8645 \LWR@origitem%
8646 }

```

Env `itemize` [*<options>*]

```

8647 \newcommand*\LWR@itemizestart}{%
8648 \renewcommand*\LWR@printcloselist}{\LWR@printcloseitemize}%
8649 \renewcommand*\LWR@printopenlist}{%
8650 ul style=\textquotedbl\LWR@print@mbbox{list-style-type:none}\textquotedbl}%
8651 }%
8652 \LetLtxMacro\item\LWR@itemizeitem%
8653 \LWR@nulllistfills%
8654 }

```

### 74.3 Enumerate

An HTML unordered list is used with customized L<sup>A</sup>T<sub>E</sub>X-generated labels.

Env `enumerate` [`<options>`]

```

8655 \newcommand*\LWR@enumerateliststart}{%
8656 \renewcommand*\LWR@printcloseitemize}{\LWR@printcloseitemize}%
8657 \renewcommand*\LWR@printopenitemize}{%
8658 ul style=\textquotedbl\LWR@print@mbbox{list-style-type:none}\textquotedbl}%
8659 }%
8660 \LetLtxMacro\item\LWR@itemizeitem%
8661 \LWR@nulllistfills%
8662 }
```

### 74.4 Description

`\LWR@descitem` [`<label>`] Handles an `\item` inside a description.

```

8663 \newcommand*\LWR@descitem}[1]{}%
8664 \LWR@stoppars%
8665 \LWR@setlatestname{#1}%
8666 \LWR@startnewdepth{descitem}%

```

While creating the label, encase it inside tags and disable `\hspace`, which is used by the standard classes to add space to the labels.

```

8667 \begingroup%
8668 \let\LWR@orig@desc@make@label\make@label
8669 \renewcommand*\make@label}[1]{}%
8670 \LWR@htmltag{dt}%
8671 \LWR@orig@desc@make@label{#1}%
8672 \LWR@htmltag{/dt}%
8673 }
8674 \LWR@select@html@no@space%
8675 \LWR@origitem[#1]%
8676 \endgroup%
8677 \LWR@orignewline%
8678 \LWR@htmltag{dd}%
8679 \LWR@startpars%
8680 }
```

Env `description` [`<options>`]

Footnotes are modified to correctly parse optional arguments.

```

8681 \newcommand*\LWR@descriptionstart}{%
8682 \renewcommand*\LWR@printcloseitemize}{\LWR@printclosedescription}
8683 \renewcommand*\LWR@printopenitemize}{dl}
8684 \LetLtxMacro\item\LWR@descitem%
8685 \LWR@nulllistfills%
8686 }
```

## 74.5 Patching the lists

`\LWR@patchlists` Patches list environments.

`\LWR@patchlists` remembers `\item` as defined by whatever packages have been loaded, then patches the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native L<sup>A</sup>T<sub>E</sub>X environments, as well as those provided by `enumitem`, `enumerate`, and `paralist`.

```

8687 \newcommand*\LWR@patchlists{%
8688 \LetLtxMacro\item\LWR@listitem%
8689 \LetLtxMacro\@item\LWR@HTML@item%
8690 \renewcommand*\@trivlist{%
8691 \LWR@traceinfo{@trivlist start}%
8692 \LWR@liststart%
8693 \LWR@orig@trivlist%
8694 \LWR@traceinfo{@trivlist done}%
8695 }%
8696 \renewcommand*\@trivlist{%
8697 \LWR@traceinfo{trivlist}%
8698 \LWR@origtrivlist%
8699 }%
8700 \renewcommand*\endtrivlist{%
8701 \LWR@traceinfo{endtrivlist start}%
8702 \LWR@origendtrivlist\LWR@listend%
8703 \LWR@traceinfo{endtrivlist done}%
8704 }%
8705 \renewcommand*\itemize{%
8706 \LWR@itemizestart\LWR@origitemize%
8707 }%
8708 \renewcommand*\enumerate{%
8709 \LWR@enumeratestart\LWR@origenumerate%
8710 }%
8711 \renewcommand*\description{%
8712 \LWR@descriptionstart\LWR@origdescription%
8713 }%
8714 }

```

`\LWR@restoreoriglists` Restores the original `trivlist` environment.

```

8715 \newcommand*\LWR@restoreoriglists{%
8716 \LWR@traceinfo{LWR@restoreoriglists}%
8717 \LetLtxMacro\item\LWR@origitem%
8718 \LetLtxMacro\@item\LWR@orig@item%
8719 \let\@trivlist\LWR@orig@trivlist%
8720 \let\trivlist\LWR@origtrivlist%
8721 \let\endtrivlist\LWR@origendtrivlist%
8722 \LetLtxMacro\itemize\LWR@origitemize%
8723 \LetLtxMacro\enditemize\LWR@endorigitemize%
8724 \LetLtxMacro\enumerate\LWR@origenumerate%
8725 \LetLtxMacro\endenumerate\LWR@endorigenumerate%
8726 \LetLtxMacro\description\LWR@origdescription%
8727 \LetLtxMacro\enddescription\LWR@endorigdescription%
8728 \let\@mklab\LWR@orig@mklab%
8729 \let\makeLabel\LWR@origmakeLabel%
8730 \let\@donoparitem\LWR@orig@donoparitem%
8731 \let\@nbitem\LWR@orig@nbitem%
8732 }

```

8733 \end{warpHTML}

## 75 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax of the L<sup>A</sup>T<sub>E</sub>X core and the various tabular-related packages.

### 75.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

#### Defining macros and environments:

- When defining environments or macros which include tabular and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and &
here>
\StopDefiningTabulars
```

This includes before and after defining any macro which used \ttabbox from floatrow.

- When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % (& is used in a
definition)
\newenvironment{outerenvironment}
{
 \tabular{cc}
 left & right \\
}
{
 \TabularMacro\ResumeTabular
 left & right \\
 \endtabular
}
\StopDefiningTabulars
```

#### For developers:

- To automate the use of \StartDefiningTabulars and \EndDefiningTabulars, these macros may be embedded inside an HTML environment definition to automatically change the catcode of & before absorbing the arguments. Another environment may be embedded as well.

⚠ Misplaced alignment  
tab character &

⚠ floatrow

⚠ tabular inside another  
environment

```

% Does the work after the catcode has been changed:
\newcommand*{\LWR@HTML@subsomename}[2]{%
 . . .
 \otherenvironmentname [<args>] {<args>} % for
 example
}
% Change catcode before absorbing arguments:
\newcommand*{\LWR@HTML@somename{%
 \StartDefiningTabulars
 \LWR@HTML@subsomename
}
% Change catcode again at the end:
\newcommand*{\LWR@HTML@endsomename}{%
 . . .
 \endotherenvironmentname % for example
 \StopDefiningTabulars
}
% Combine with the existing print definition:
\LWR@formattedenv{somename}

```

**Cell contents:****⚠ macro in a table**

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use `\TabularMacro` just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \
```

**Column specifiers:****⚠ math**

- Due to the way math is gathered for processing, column specifiers such as `>{$}c<{$}` do not work with `lwarp`. Instead, each cell must specify math mode individually.

**@ and !**

- Only one each of @ and ! is used at each column, and they are used in that order.

**\multirow**

- In `\multirow` cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the `\multirow` which do not appear in the HTML version.

**⚠ \newcolumntype**

- If `\newcolumntype` does not work for HTML, add a simplified column type using `\HTMLnewcolumntype`.

**font and alignment**

- `lwarp` detects each of the following, and sets HTML CSS appropriately:
  - `>{\centering\arraybackslash}`
  - `>{\raggedright\arraybackslash}`
  - `>{\raggedleft\arraybackslash}`
  - `>{\itshape}`
  - `>{\bfseries}`
  - `>{\bfseries\itshape}`

These may be used with `\newcolumntype`, such as:

```
\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}
```

**Rules:****vertical rules**

- Doubled `\hlines`, `\midrules`, and vertical rules are supported.
- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

**width and trim**

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

**combined rules**

- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:

```
\cmidrule{2-3} \[-2ex]
\bottomrule
```

The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

- For `\toprule` and `\bottomrule`, when combined with a `warpprint` or `warppHTML` environment, if a “Misplaced `\noalign`” error occurs, change

```
This & That \endhead
```

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevant to HTML output.

⚠ `\warpprintonly`

⚠ Misplaced `\noalign`

**Other:**

- `tabularx` ignores the width, but X columns do produce paragraph columns or multicolumns.

**longtable headings**

- For `longtable`, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.

⚠ S columns

- For S columns (from the `siunitx` package), while producing print output, anything non-numeric must be placed inside `{}` braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by `lwarp`'s tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
```

```
\warppHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

- In  $\LaTeX$ , a `tabular` may be placed inside a `minipage`, but in HTML a `<table>` may not be inside a `<span>`. If this situation is detected, a warning is printed instructing the user to isolate the `<span>` using `\warpprintonly` or the `warpprint` environment.

for HTML output: `8734 \begin{warppHTML}`

## 75.2 Temporary package-related macros

These macros are temporary placeholders for macros defined by various packages. If the relevant package is not loaded, these placeholders are used instead.

### 75.2.1 `arydshln`

Emulated by the original  $\LaTeX$  non-dashed versions.

⚠ `tabular` inside a `<span>`

```

8735 \LetLtxMacro\hdashline\hline
8736 \LetLtxMacro\cdashline\cline
8737 \LetLtxMacro\firsthdashline\hline
8738 \LetLtxMacro\lasthdashline\hline

```

### 75.3 Token lookahead

Used by `\LWR@futurenonpacelet` to look at the next token.

`\LWR@mynexttoken`

```
8739 \newcommand\LWR@mynexttoken\relax
```

`\LWR@futurenonpacelet` `\futurelet` copies the next token then executes a function to analyze it.

`\LWR@futurenonpacelet` does the same, but ignores intervening spaces and paragraphs.

Based on the `booktabs` style:

```

8740 \def\LWR@futurenonpacelet#1{\def\LWR@cs{#1}%
8741 \afterassignment\LWR@fnslone\let\nexttoken= }
8742
8743 \def\LWR@fnslone{\expandafter\futurelet\LWR@cs\LWR@fnsltwo}
8744
8745 \def\LWR@fnsltwo{%
8746 \expandafter\ifx\LWR@cs\sptoken%
8747 \let\next=\LWR@fnslthree%
8748 \else%
8749 \expandafter\ifx\LWR@cs\par%
8750 \let\next=\LWR@fnslthree%
8751 \else%
8752 \let\next=\nexttoken%
8753 \fi%
8754 \fi\next}
8755
8756 \def\LWR@fnslthree{\afterassignment\LWR@fnslone\let\next= }

```

`\LWR@getmynexttoken` Looks ahead and copies the next token into `\LWR@mynexttoken`.

```

8757 \newcommand*\LWR@getmynexttoken}{%
8758 \LWR@traceinfo{\LWR@getmynexttoken}%

```



Nothing must follow this next line:

```

8759 \LWR@futurenonpacelet\LWR@mynexttoken\LWR@tabledatacolumnstag
8760 }

```

### 75.4 Tabular variables

In order to support nested tabulars, each of these is used locally. For local counters, `etoolbox`'s `\defcounter` and `lwarp`'s new `\defaddtocounter` are used.

Bool `\LWR@startedrow`

True if should print a row tag before this column.

8761 \newbool{LWR@startedrow}  
 8762 \boolfalse{LWR@startedrow}

Bool LWR@tabularcelladded True if have added a data cell for this position.

8763 \newbool{LWR@tabularcelladded}  
 8764 \boolfalse{LWR@tabularcelladded}

Ctrl LWR@hlines Number of \hlines or \midrules above the next row.

8765 \newcounter{LWR@hlines}

Ctrl LWR@hdashedlines Number of \arydshln dashed lines above the next row.

8766 \newcounter{LWR@hdashedlines}

Bool LWR@doingtbrule True if the next row will have a top/bottom rule above it.

8767 \newbool{LWR@doingtbrule}  
 8768 \boolfalse{LWR@doingtbrule}

Bool LWR@doingcmidrule True if the next row will have a cmidrule above it.

This is used by \LWR@tabularfinishrow to force a final empty row to create the border for the \cmidrule.

8769 \newbool{LWR@doingcmidrule}  
 8770 \boolfalse{LWR@doingcmidrule}

Bool LWR@tableparcell True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

8771 \newbool{LWR@tableparcell}

Bool LWR@skippingmrowcell True if are doing an empty \multirow cell, and thus there is no data tag to close.

8772 \newbool{LWR@skippingmrowcell}

Bool LWR@skippingmcolrowcell True if are doing an empty \multicolumnrow cell, and thus there is no data tag to close, and do not print @ and ! columns.

8773 \newbool{LWR@skippingmcolrowcell}

Bool LWR@usedmultirow Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

8774 \newbool{LWR@usedmultirow}

Bool LWR@foundmrowcell Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

8775 \newbool{LWR@foundmrowcell}

Bool LWR@skipatbang True if just finished a \multicolumn so should not create the trailing @ or ! columns table data cells.

8776 \newbool{LWR@skipatbang}

- Bool LWR@emptyatbang True if finishing a row and should print empty @ or ! column table data cells.
- 8777 \newbool{LWR@emptyatbang}
- Bool LWR@intabularmetadata True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.
- 8778 \newbool{LWR@intabularmetadata}  
8779 \boolfalse{LWR@intabularmetadata}
- Bool LWR@exitingtabular When \end is found, turns off the next opening data tag.
- 8780 \newbool{LWR@exitingtabular}
- Bool LWR@tabularmutemods Mutes HTML output for @, !, < and >.
- This is used while printing the final row to generate \bottomrules.
- 8781 \newbool{LWR@tabularmutemods}
- Bool LWR@validtablecol True if found a valid table column type.
- 8782 \newbool{LWR@validtablecol}
- Bool LWR@opttablecol True if found a table column optional argument.
- 8783 \newbool{LWR@opttablecol}
- Used to add a style to a table data cell:
- 8784 \newbool{LWR@tdhavecellstyle}
- Ctr LWR@tabularDepth Tracks whether & is being used inside a tabular.
- 8785 \newcounter{LWR@tabulardepth}  
8786 \setcounter{LWR@tabulardepth}{0}
- Ctr LWR@tabularpardepth Tracks whether should look ahead at the next token when encountering a \par while processing tabular contents.
- When LWR@tabularpardepth is deeper than LWR@tabulardepth then lwarp has started looking at the contents of the tabular, and thus any \pars encountered must be followed by another token lookahead.
- 8787 \newcounter{LWR@tabularpardepth}  
8788 \setcounter{LWR@tabularpardepth}{0}
- 8789 \newcommand\*{\LWR@colresult}{}%temp storage for column format results  
8790 \newcommand\*{\LWR@pposition}{}  
8791 \newcommand\*{\LWR@pleft}{}  
8792 \newcommand\*{\LWR@pright}{}
- LWR@tablecolspec Holds the parsed column specification, of total width LWR@tabletotalLaTeXcols, not counting @ and ! columns.
- Will contain a string such as llrrccpc, exactly one letter per L<sup>A</sup>T<sub>E</sub>X table column, without @, !, >, <, or the vertical bar.

`\LWR@strresult` Holds the result of `Str` functions.

```
8793 \providecommand*\LWR@strresult{}
8794 \providecommand*\LWR@strresulttwo{}
```

`\LWR@origcolspec` Holds the original column specs given to `tabular`.

```
8795 \newcommand*\LWR@origcolspec{}
```

Ctrl `LWR@tablecolspecwidth` Holds the number of tokens in the table columns specification.

This includes one for each `@`, `!`, `<`, `>` column, and also one for each of the parameters of `p`, `@`, `!`, `<`, `>` columns, and three for each `D` column.

(This is not the total # of `LATEX` columns in the table.)

```
8796 \newcounter{LWR@tablecolspecwidth}
```

Ctrl `LWR@tablecolspecindex` While parsing the `LATEX` table column specification, starts at 1 and is incremented per token of the specification.

```
8797 \newcounter{LWR@tablecolspecindex}
```

Ctrl `LWR@tableLaTeXcolindex` While producing the table, resets to 1 at the start of the table and also at each end of line, and is incremented by 1 by each ampersand.

```
8798 \newcounter{LWR@tableLaTeXcolindex}
```

Ctrl `LWR@tabletotalLaTeXcols` While parsing a table column specification, begins at 0 and increments by 1 per `LATEX` table column. Eventually holds the final number of `LATEX` table columns in each row, not counting `@` and `!` columns. (In `HTML`, `@` and `!` cells become their own columns, but are not included in `LWR@tabletotalLaTeXcols`.)

```
8799 \newcounter{LWR@tabletotalLaTeXcols}
```

Ctrl `LWR@tabletotalLaTeXcolsnext` Holds the next `LATEX` table column index while parsing, equal to one more than `LWR@tabletotalLaTeXcols`.

```
8800 \newcounter{LWR@tabletotalLaTeXcolsnext}
```

`LWR@colatspec` A data array of specifications for `@` columns. The leftmost's index is `leftedge`, the others are counter values. See section 42.

`LWR@colbangspec` A data array of specifications for `!` columns. The leftmost's index is `leftedge`, the others are counter values. See section 42.

`LWR@colbeforespec` A data array of specifications for `>` columns.

`LWR@colafterspec` A data array of specifications for `<` columns.

`LWR@colbarspec` A data array of specifications for vertical rules.

`LWR@coladdclass` A data array of extra `css` class, as set by `>`.

Ctrl `LWR@cellcolordepth` Counts how many cell color `<div>`s were added to the current tabular data cell.

```
8801 \newcounter{LWR@cellcolordepth}
```

### 75.4.1 Multicolumn variables

```
8802 \newcounter{LWR@tablemulticolwidth}
```

Indexes into the multicolumn specification:

```
8803 \newcounter{LWR@tablemulticolspos}
```

Remembers multicolumn vertical rules if found in the column spec.

```
8804 \newcounter{LWR@mcolvertbarsl}
8805 \newcounter{LWR@mcolvertbarsr}
8806 \newcounter{LWR@mcolvertbarsldash}
8807 \newcounter{LWR@mcolvertbarsrdash}
8808 \newbool{LWR@mcolvertbaronleft}
```

### 75.4.2 Longtable variables

Bool LWR@starredlongtable Per the caption package, step the counter if longtable\*.

```
8809 \newbool{LWR@starredlongtable}
8810 \boolfalse{LWR@starredlongtable}
```

### 75.4.3 Midrule variables

Ctrl LWR@midrulecounter Indexes across the LWR@midrules and LWR@trim<l/r>rules data arrays.

```
8811 \newcounter{LWR@midrulecounter}
```

## 75.5 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:

[http://tex.stackexchange.com/questions/11638/  
where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860](http://tex.stackexchange.com/questions/11638/where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860)

\LWR@instertatbangcols

```
8812 \newcommand*{\LWR@insertatbangcols}{%
8813 \ifbool{LWR@skipatbang}%
8814 {}%
8815 {%
8816 \LWR@printatbang{at}{\arabic{LWR@tableLaTeXcolindex}}%
8817 \LWR@printatbang{bang}{\arabic{LWR@tableLaTeXcolindex}}%
8818 }%
8819 }
```

\LWR@closetabledatacell If LWR@skippingmrowcell or LWR@skippingmcolrowcell then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
8820 \newcommand*{\LWR@closetabledatacell}{%
8821 \booltrue{LWR@intabularmetadata}%
8822 \ifbool{LWR@exitingtabular}%
8823 {%
```

```

8824 \LWR@stoppars%
8825 }%
8826 {% not exiting tabular
8827 \ifboolexpr{bool{LWR@skippingmrowcell} or bool{LWR@skippingmcolrowcell}}%
8828 {%

```

```

8829 \LWR@stoppars%

```

If not skipping a `\multicolumnrow` cell, insert the @ and ! columns after this non-existent column.

```

8830 \ifbool{LWR@skippingmcolrowcell}%
8831 {}%
8832 {\LWR@insertatbangcols}%
8833 }%
8834 {% not skippingmrowcell

```

Insert any < then any @ and ! column contents, unless muted for the `\bottomrule` or a `\multicolumn`:

```

8835 \unskip%
8836 \ifboolexpr{%
8837 bool{LWR@tabularmutemods} or
8838 bool{LWR@skipatbang} or
8839 bool{LWR@emptyatbang}
8840 }%
8841 {}%
8842 {%
8843 \LWR@getexparray{LWR@colafterspec}%
8844 {\arabic{LWR@tableLaTeXcolindex}}%
8845 }%

```

Close paragraphs:

```

8846 \LWR@stoppars%
8847 \boolfalse{LWR@tableparcell}%

```

Close the table data cell.

Close any color <div>s.

```

8848 \whileboolexpr{test {\ifnumcomp{\value{LWR@cellcolordepth}}{>}{0}}}{%
8849 \LWR@htmltag{/div}\LWR@orignewline%
8850 \defaddtocounter{LWR@cellcolordepth}{-1}%
8851 }%

```

Skip the @ and ! cells if are closing a multicolumn cell.

```

8852 \leavevmode\unskip\LWR@htmltag{/td}\LWR@orignewline%
8853 \global\booltrue{LWR@tabularcelladded}%
8854 \LWR@insertatbangcols%
8855 }% not skipping mrowcell
8856 }% not exiting tabular
8857 \boolfalse{LWR@skippingmrowcell}%
8858 \boolfalse{LWR@skippingmcolrowcell}%
8859 \boolfalse{LWR@skipatbang}%

```

Color control. Column is set by >{} for each cell, so it must be cleared here.

```
8860 \def\LWR@cellHTMLcolor{}%
8861 \def\LWR@columnHTMLcolor{}%
8862 \defcounter{LWR@cellcolordepth}{0}%
8863 }
```

When not used inside a tabular, & performs its original function as recorded here ( with catcode 4 ).

```
8864 \let\LWR@origampmacro&
8865 \end{warpHTML}
```

### 75.5.1 Handling &

**for HTML output:** 8866 \begin{warpHTML}

& Will behave depending on whether it is being used inside tabular.

& is redefined to test whether it is inside a tabular environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```
8867 \newcommand*\LWR@tabularampersand{}%
8868 \LWR@traceinfo{LWR@tabularampersand}%
8869 \ifnumcomp{\value{LWR@tabulardepth}}{>}{0}%
8870 {%
```

If not skipping a multirow cell, close the current data cell.

```
8871 \unskip%
8872 \LWR@closetabledatacell%
```

Move to the next column.

```
8873 \defadddtcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
8874 \global\boolfalse{LWR@tabularcelladded}%
```

Look at the next token to decide multi or single column data tag.

```
8875 \LWR@getmynexttoken%
8876 }%
```

If not inside a tabular, performs the original action:

```
8877 {%
8878 \LWR@origampmacro%
8879 }%
8880 }
```

& is left with its original catcode for now.

tikz package seems to require & be left alone until after tikz has been loaded. Also, cleveref uses the ampersand in one of its options.

& is made active inside a tabular.

& is left alone when in math alignments.

## 75.6 Filling an unfinished row

`\LWR@tabularfinishrow` Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
8881 \newcommand*\LWR@tabularfinishrow{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
8882 \ifboolexpr{%
8883 not bool {LWR@exitingtabular} or%
8884 bool{LWR@doingtbrule} or%
8885 bool{LWR@doingcmidrule} or%
8886 test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
8887 test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
8888 bool{LWR@startedrow}%
8889 }{%
```

To temporarily turn off `LWR@exitingtabular` so that table data tags will still be generated:

If generating a final row for the `\bottomrule` borders, turn off the @, !, <, and > column output:

```
8890 \ifbool{LWR@exitingtabular}{%
8891 \booltrue{LWR@tabularmutemods}%
8892 }{%
8893 \boolfalse{LWR@tabularmutemods}%
8894 }%
```

Locally reenable the table data tags until finished with the final row:

```
8895 \boolfalse{LWR@exitingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
8896 \whileboolexpr{%
8897 test {
8898 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
8899 {\value{LWR@tabletotalLaTeXcols}}
8900 } or %
8901 (%
8902 bool{LWR@intabularmetadata} and%
8903 not bool{LWR@tabularcelladded} and%
```

```

8904 test {
8905 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}
8906 {\value{LWR@tabletotalLaTeXcols}}
8907 }%
8908)%
8909 }%
8910 {%
8911 \LWR@tabledatasinglecolumnntag%

```

The following is essentially `\LWR@tabularampersand` with `LWR@emptyatbang` added to empty the following cells:

```

8912 \LWR@closetabledatacell%
8913 \defaddtocounter{LWR@tableLaTeXcolindex}{1}%
8914 \global\boolfalse{LWR@tabularcellladded}%
8915 \booltrue{LWR@emptyatbang}%

```

Starts the next cell:

```

8916 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
8917 {\value{LWR@tabletotalLaTeXcols}}%
8918 {\LWR@getmynexttoken}%
8919 }%
8920 }%

```

Reenable the original `LWR@exitingtabular` to close the entire table:

```

8921 \ifbool{LWR@tabularmutemods}{%
8922 \booltrue{LWR@exitingtabular}%
8923 }{%
8924 \boolfalse{LWR@exitingtabular}%
8925 }%
8926 \boolfalse{LWR@tabularmutemods}%

8927 \boolfalse{LWR@emptyatbang}%
8928 }{% ifboolexpr
8929 }

```

## 75.7 Handling `\\`

Inside `tabular`, `\\` is redefined to `\LWR@tabularendofline`

Throws away options `\\[dim]` or `\\*`

`\LWR@tabularendofline`

```

8930 \NewDocumentCommand{\LWR@tabularendofline}{s o}{%

```

Finish the row:

```

8931 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
8932 {\value{LWR@tabletotalLaTeXcols}}%
8933 {\LWR@tabularfinishrow}%
8934 {\LWR@closetabledatacell}%
8935 \LWR@htmltag{/tr}\LWR@originewline%

```

xcolor row color support:

8936 \@rowcolor%

No longer inside a data cell:

8937 \booltrue{LWR@intabularmetadata}%

Not yet started a table row:

8938 \boolfalse{LWR@startedrow}%

Additional setup:

8939 \defcounter{LWR@hlines}{0}%  
 8940 \defcounter{LWR@hdashedlines}{0}%  
 8941 \boolfalse{LWR@doingtbrule}%  
 8942 \boolfalse{LWR@doingcmidrule}%  
 8943 \LWR@clearmidrules%

8944 \def\LWR@rowHTMLcolor{}

Start at first column:

8945 \defcounter{LWR@tableLaTeXcolindex}{1}%

Have not yet added data in this column:

8946 \global\boolfalse{LWR@tabularcelladded}%

Allow TeX to flush the pending paragraph. Not doing so causes a slowdown for very large tables.

8947 \LWR@stoppars%  
 8948 \LWR@origpar%

Look at the next token to decide between single column data tag or a special case:

8949 \LWR@getmynexttoken%  
 8950 }

## 75.8 Looking ahead in the column specifications

\LWR@columnspeclookahead {<offset>}

Looks offset tokens ahead in the column specification, setting \LWR@strresulttwo.

The w column alignment will be seen as a single unit such as {c}.

8951 \newcommand\*\LWR@columnspeclookahead[1]{%  
 8952 \setcounter{LWR@tempcountone}{\value{LWR@tablecolspecindex}}%  
 8953 \addtocounter{LWR@tempcountone}{#1}%  
 8954 \fullexpandarg%  
 8955 \StrChar{\LWR@origcolspec}{\arabic{LWR@tempcountone}}[\LWR@strresulttwo]%

Get the contents of the first group in `\LWR@strresulttwo`:

```
8956 \exploregroups%
8957 \StrChar{\LWR@strresulttwo}{1}[\LWR@strresulttwo]%
8958 \noexploregroups%
8959 }
```

## 75.9 Parsing @, >, <, !, bar columns

Holds the parsed argument for @, >, <, or ! columns:

```
8960 \newcommand*{\LWR@colparameter}{}
```

```
\LWR@parseatcolumn {{this column type}}
```

Handles `@{text}` columns.

The argument is ignored, but provided for compatibility with `\LWR@parsenormalcolumn`.

```
8961 \newcommand*{\LWR@parseatcolumn}[1]{%
```

Move to the next token after the '@':

```
8962 \LWR@traceinfo{at column}%
8963 \defaddtocounter{\LWR@tablecolspecindex}{1}%
```

Read the next token into `\LWR@colparameter`, expanding once:

```
8964 \LWR@traceinfo{about to read the next token:}%
8965 \expandarg%
8966 \StrChar{\LWR@origcolspec}%
8967 {\arabic{\LWR@tablecolspecindex}}[\LWR@colparameter]%
8968 \fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
8969 \LWR@traceinfo{have now read the next token}%
8970 \ifnumcomp{\value{\LWR@tabletotalLaTeXcols}}{=}{0}%
8971 {% left edge of the table:
8972 \LWR@traceinfo{at the left edge}%
8973 \LWR@setexparray{\LWR@colatspec}%
8974 {leftedge}%
8975 {\expandafter\@firstofone\LWR@colparameter}%
8976 \LWR@traceinfo{at the left edge: %
8977 \LWR@getexparray{\LWR@colatspec}{leftedge}}%
8978 }%
8979 {% not at the left edge:
8980 \LWR@traceinfo{not at the left edge}%
8981 \LWR@setexparray{\LWR@colatspec}%
8982 {\arabic{\LWR@tabletotalLaTeXcols}}%
8983 {\expandafter\@firstofone\LWR@colparameter}%
8984 \LWR@traceinfo{at \arabic{\LWR@tabletotalLaTeXcols}%
8985 : % space
8986 \LWR@getexparray{\LWR@colatspec}{\arabic{\LWR@tabletotalLaTeXcols}}}%
8987 }%
8988 \let\LWR@colparameter\relax%
```

```
8989 \booltrue{LWR@validtablecol}%
8990 }
```

`\LWR@parsebangcolumn`  $\{ \langle \textit{this column type} \rangle \}$  Handles  $\{ \langle \textit{text} \rangle \}$  columns.

The argument is ignored, but provided for compatibility with `\LWR@parsenormalcolumn`.

```
8991 \newcommand*{\LWR@parsebangcolumn}[1]{%
```

Move to the next token after the '!':

```
8992 \LWR@traceinfo{bang column}%
8993 \defaddtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into `\LWR@colparameter`, expanding once:

```
8994 \LWR@traceinfo{about to read the next token:}%
8995 \expandarg%
8996 \StrChar{\LWR@origcolspec}%
8997 {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
8998 \fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
8999 \LWR@traceinfo{have now read the next token}%
9000 \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
9001 {% left edge of the table:
9002 \LWR@traceinfo{at the left edge}%
9003 \LWR@setexparray{LWR@colbangspec}%
9004 {leftedge}%
9005 {\expandafter\@firstofone\LWR@colparameter}%
9006 }%
9007 {% not at the left edge:
9008 \LWR@traceinfo{not at the left edge}%
9009 \LWR@setexparray{LWR@colbangspec}%
9010 {\arabic{LWR@tabletotalLaTeXcols}}%
9011 {\expandafter\@firstofone\LWR@colparameter}%
9012 \LWR@traceinfo{bang \arabic{LWR@tabletotalLaTeXcols}: \LWR@colparameter!}%
9013 }%
9014 \let\LWR@colparameter\relax%
9015 \booltrue{LWR@validtablecol}%
9016 }
```

`\LWR@checkbeforeaddclass`  $\{ \langle \textit{compared csname} \rangle \} \{ \langle \textit{css class to add} \rangle \}$

```
9017 \newcommand*{\LWR@checkbeforeaddclass}[2]{%
9018 \ifcsstrequal{LWR@tempone}{#1}%
9019 {%
9020 \LWR@setexparray{LWR@coladdclass}%
9021 {\arabic{LWR@tabletotalLaTeXcolsnext}}%
9022 { #2}% space is intentional
9023 }{%
9024 }
```

`\LWR@checkmathcolpar` Error if using math in column parameters.

```
9025 \newcommand*{\LWR@checkmathcolpar}{%
```

```

9026 \IfSubStr{\detokenize\expandafter{\LWR@colparameter}}{\LWRdollar}%
9027 {%
9028 \PackageError{lwarp}%
9029 {%
9030 Lwarp does not support '$' in column specifiers.\MessageBreak
9031 Specify '$' math for each cell in the column.\MessageBreak
9032 Enter 'h' for more info%
9033 }%
9034 {%
9035 For example, replace '>{<}c<{<}' with 'c', and then\MessageBreak
9036 use '$cell contents$' for each cell in the column.%
9037 }%
9038 }{%
9039 }

```

`\LWR@parsebeforecolumn` *{<this column type>}*

Handles `>{text}` columns.

The argument is ignored, but provided for compatibility with `\LWR@parsenormalcolumn`.

```
9040 \newcommand*{\LWR@parsebeforecolumn}[1]{%
```

Move to the next token after the '>':

```
9041 \defaddtocomputer{\LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into `\LWR@colparameter`:

```

9042 \expandarg%
9043 \StrChar{\LWR@origcolspec}%
9044 {\arabic{\LWR@tablecolspecindex}}[\LWR@colparameter]%
9045 \fullexpandarg%

```

Error if using `>{<}`, which is not supported by `lwarp`.

```
9046 \LWR@checkmathcolpar%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```

9047 \LWR@setexparray{\LWR@colbeforespec}%
9048 {\arabic{\LWR@tabletotalLaTeXcolsnext}}%
9049 {\expandafter\@firstofone\LWR@colparameter}%
9050 %
9051 \edef\LWR@tempone{\expandafter\@firstofone\LWR@colparameter}%

```

If detect `>\centering\arraybackslash` or related, add a CSS class.

```

9052 \LWR@checkbeforeaddclass{\LWR@detect@centeringarraybackslash}{tdcenter}
9053 \LWR@checkbeforeaddclass{\LWR@detect@raggedrightarraybackslash}{tdleft}
9054 \LWR@checkbeforeaddclass{\LWR@detect@raggedleftarraybackslash}{tdright}
9055 \LWR@checkbeforeaddclass{\LWR@detect@itshape}{tditshape}
9056 \LWR@checkbeforeaddclass{\LWR@detect@bfseries}{tdbfseries}
9057 \LWR@checkbeforeaddclass{\LWR@detect@bfit}{tdbfit}

9058 \let\LWR@colparameter\relax%
9059 \booltrue{\LWR@validtablecol}%
9060 }

```

`\LWR@parseaftercolumn` *{<this column type>}*

Handles `<{text}>` columns.

The argument is ignored, but provided for compatibility with `\LWR@parsenormalcolumn`.

```
9061 \newcommand*{\LWR@parseaftercolumn}[1]{%
```

Move to the next token after the '<':

```
9062 \defaddtocounter{\LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into `\LWR@colparameter`:

```
9063 \expandarg%
9064 \StrChar{\LWR@origcolspec}%
9065 {\arabic{\LWR@tablecolspecindex}}[\LWR@colparameter]%
9066 \fullexpandarg%
```

Error if using `>{<}`, which is not supported by `lwarp`.

```
9067 \LWR@checkmathcolpar%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
9068 \LWR@setexparray{\LWR@colafterspec}%
9069 {\arabic{\LWR@tabletotalLaTeXcols}}%
9070 {\expandafter\@firstofone\LWR@colparameter}%
9071 \let\LWR@colparameter\relax%
9072 \booltrue{\LWR@validtablecol}%
9073 }
```

`\LWR@parsebarcolumn` *{<this column type>}*

Handles vertical rules.

The argument is ignored, but provided for compatibility with `\LWR@parsenormalcolumn`.

```
9074 \newcommand*{\LWR@parsebarcolumn}[1]{%
9075 \LWR@traceinfo{\LWR@parsebarcolumn}%
```

Remember the bar at this position:

```
9076 \ifnumcomp{\value{\LWR@tabletotalLaTeXcols}}{=}{0}%
9077 {% left edge of the table:
9078 \edef\LWR@tempone{\LWR@getexparray{\LWR@colbarspec}{leftedge}}%
9079 \ifdefstring{\LWR@tempone}{tvertbarl}%
9080 {\LWR@setexparray{\LWR@colbarspec}{leftedge}{tvertbarldouble}}%
9081 {\LWR@setexparray{\LWR@colbarspec}{leftedge}{tvertbarl}}%
9082 }%
9083 {% not at the left edge:
9084 \edef\LWR@tempone{%
9085 \LWR@getexparray{\LWR@colbarspec}{\arabic{\LWR@tabletotalLaTeXcols}}%
9086 }%
9087 \ifdefstring{\LWR@tempone}{tvertbarr}%
9088 {%
9089 \LWR@setexparray{\LWR@colbarspec}%
9090 {\arabic{\LWR@tabletotalLaTeXcols}}{tvertbarrdouble}}%
```

```

9091 }%
9092 {%
9093 \LWR@setexparray{LWR@colbarspec}%
9094 {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarr}%
9095 }%
9096 }%
9097 \booltrue{LWR@validtablecol}%
9098 }

```

`\LWR@parsecoloncolumn` {<*this column type*>}

Handles vertical rules.

The argument is ignored, but provided for compatibility with `\LWR@parsenormalcolumn`.

```

9099 \newcommand*{\LWR@parsecoloncolumn}[1]{%
9100 \LWR@traceinfo{LWR@parsecoloncolumn}%

```

Remember the bar at this position:

```

9101 \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
9102 {% left edge of the table:
9103 \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
9104 \ifdefstring{\LWR@tempone}{tvertbarldash}%
9105 {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldoubledash}}%
9106 {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldash}}%
9107 }%
9108 {% not at the left edge:
9109 \edef\LWR@tempone{%
9110 \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
9111 }%
9112 \ifdefstring{\LWR@tempone}{tvertbarrdash}%
9113 {\LWR@setexparray{LWR@colbarspec}%
9114 {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdoubledash}}%
9115 {\LWR@setexparray{LWR@colbarspec}%
9116 {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdash}}%
9117 }%
9118 \booltrue{LWR@validtablecol}%
9119 }

```

`\LWR@parsesemicoloncolumn` {<*this column type*>}

Handles vertical rules.

The argument is ignored, but provided for compatibility with `\LWR@parsenormalcolumn`.

The arguments to the column type are absorbed by `\LWR@columnntype@<char>`, defined by `\LWR@modifycolumnntype`.

```

9120 \newcommand*{\LWR@parsesemicoloncolumn}[1]{%

```

Treat ; as a : column:

```

9121 \LWR@parsecoloncolumn{%
9122 }

```

## 75.10 Parsing common column types

`\LWR@parsenormalcolumn`  $\{\langle this\ column\ type\rangle\}$

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

`\newcolumn` type definitions use `\LWR@parsenormalcolumn`, so an HTML and print version are given so that they may work inside a lateximage.

The arguments to the column type are absorbed by `\LWR@column` $\text{type}\langle\text{char}\rangle$ , defined by `\LWR@modifycolumn` $\text{type}$ .

```

9123 \newcommand*{\LWR@HTML\LWR@parsenormalcolumn}[1]{%
9124 \defaddtocounter{LWR@tabletotalLaTeXcols}{1}%
9125 \defaddtocounter{LWR@tabletotalLaTeXcolsnext}{1}%

9126 \LWR@setexparray{LWR@tablecolspec}{\arabic{LWR@tabletotalLaTeXcols}}{#1}%

9127 \LWR@traceinfo{normal column \arabic{LWR@tabletotalLaTeXcols}: #1}%
9128 \LWR@setexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
9129 \LWR@setexparray{LWR@colbangspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
9130 \LWR@setexparray{LWR@colbeforespec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
9131 \LWR@setexparray{LWR@colafterspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
9132 \LWR@setexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
9133 \LWR@setexparray{LWR@coladdclass}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
9134 \booltrue{LWR@validtablecol}%
9135 }
9136
9137 \newcommand*{\LWR@print\LWR@parsenormalcolumn}[1]{%
9138
9139 \LWR@formatted{LWR@parsenormalcolumn}

```

## 75.11 Parsing ‘w’ columns

W and w columns are handled via array with `\HTMLnewcolumn` $\text{type}$ .

## 75.12 Parsing ‘\*’ columns

`\LWR@parsestarcolumn`  $\{\langle this\ column\ type\rangle\}$  Star columns should already have been expanded, so this should never be used.

The arguments to the column type are absorbed by `\LWR@column` $\text{type}\langle\text{char}\rangle$ , defined by `\LWR@modifycolumn` $\text{type}$ .

The argument is ignored, but provided for compatibility with `\LWR@parsenormalcolumn`.

```

9140 \newcommand*{\LWR@parsestarcolumn}[1]{%

```

## 75.13 Expanding the star column specifications

`\LWR@expandpreamble`  $\{\langle tabular\ preamble\rangle\}$

Table 13: Tabular baseline

|   |     |     |     |   |
|---|-----|-----|-----|---|
| l | p   | m   | b   | r |
|   |     |     | bot |   |
|   |     | mid | bot |   |
| l | par | mid | bot | r |
|   | par | mid |     |   |
|   | par |     |     |   |

From array `\@mkpream`.

The resulting expanded preamble is stored in `\the\@temptokena`. Assign as:

```

\edef\destination{\the\@temptokena}

9141 \newcommand*\LWR@expandpreamble[1]{%
9142 \edef\@tempa{\@temptokena=#1}%
9143 \@tempa%
9144 \@tempswatruer%
9145 \@whilesw\if@tempswa\fi{%
9146 \@tempswafalse\the\NC@list%
9147 }%
9148 }
```

## 75.14 Parsing the column specifications

### △ tabular baselines

HTML CSS cannot exactly match the L<sup>A</sup>T<sub>E</sub>X concept of a baseline for a table row. Table 13 shows the L<sup>A</sup>T<sub>E</sub>X results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the `p` column specification in table 14 for details.

Table 14 describes how each kind of column is converted to HTML.

Table 15 shows the various internal macros generated for each column type.

```

\LWR@modifycolumnntype {<1: column type letter>} {<2: number args to ignore>} {<3: csname of the cell
action>} {<4: csname of the multicolumn print type action>} {<5: csname of the
multicolumn print data action>}
```

Add HTML functionality to an existing print version column type.

```

9149 \newcommand*\LWR@modifycolumnntype[5]{%
9150 \LWR@traceinfo{\LWR@modifycolumnntype !#1!#2!#3!#4!#5!}%
9151 \LWR@traceinfo{\LWR@modifycolumnntype #1}%
9152 \edef\@tempa{%
9153 \noexpand\csdef{\LWR@columnntype@#1}{%
9154 \noexpand\@nameuse{#3}{#1}%
9155 \noexpand\defaddtocounter{\LWR@tablecolspecindex}{#2}%
9156 }%
9157 \noexpand\csdef{\LWR@columnntype@mctype@#1}{%
9158 \noexpand\@nameuse{#4}{#1}%
9159 }%
9160 \noexpand\csdef{\LWR@columnntype@mcddata@#1}{%
```

Table 14: Tabular HTML column conversions

Each cell is given a css class of `td<columntype>`.

---

- l, r, c:** Converted to table cells without paragraph tags.  
 Uses css `vertical-align:middle` so that top or bottom-aligned cells may go above or below this cell.
- p:** Converted to table cells with paragraph tags. Ref: Table 13,  $\LaTeX$  places the top line of a parbox aligned with the rest of the text line, so css `vertical-align:bottom` is used to have the HTML result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the HTML conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the css may be desired, changing `td.tdp`, `td.tdP`, `td.tdprule`, and `td.tdPrule` to `vertical-align: middle`. Another possibility is to change L,R,C, and P to `vertical-align: top` and not worry about the alignment of B and M cells or trying to approximate  $\LaTeX$  baselines.
- m:** With paragraph tags, css `vertical-align:middle`.
- b:** With paragraph tags, css `vertical-align: top` so that the bottom of the text is closest to the middle of the text line.
- w and W:** Converted to `l`, `c`, or `r`. No paragraph tags.
- P, M, B:** Horizontally-centered versions.
- S:** Treated as 'c'. Ignores optional argument. From the `siunitx` package.
- D:** Treated as 'c'. From the `dcolumn` package.
- @, !, >, <:** One each, in that order.
- |:** Vertical rule.
- Unknown:** Converted to 'l'.
- \newcolumntype:** Expands to its replacement text.
- \HTMLnewcolumntype:** Provides simplified replacement text for HTML.
-

Table 15: HTML column type internal macros

---

**<coltype>**: The single-letter column type, such as c or X.

**Created by \LWR@modifycolumn****type**: Used by lwarp to add HTML functionality to each built-in column type.

**\LWR@column****type@<coltype>**: Handles tabular columns depending on the type. Calls \LWR@parsenormalcolumn or related, then advances \LWR@tablecolspecindex.

**\LWR@column****type@mctype@<coltype>**: Generates the \multicolumn HTML cell css class. Calls \LWR@printmccoltype@normal or related.

**\LWR@column****type@mcdata@<coltype>**: Generates the \multicolumn HTML cell data. Calls \LWR@printmccoldata@normal or related.

**Created by \newcolumn****type**: From array.

**\NC@find@<coltype>**: Internally used to parse the column specifier.

**\NC@rewrite@<coltype>**: Stores the print-mode replacement text.

**Created by \HTMLnewcolumn****type**: From lwarp.

**\LWR@print@NC@rewrite@<coltype>**: Copied from \NC@rewrite@<type>.

**\LWR@HTML@NC@rewrite@<coltype>**: Stores the HTML-mode replacement text.

**\NC@rewrite@<coltype>**: Redefined to use the print or HTML version.

---

```

9161 \noexpand\@nameuse{#5}{#2}%
9162 }%
9163 }%
9164 \@tempa%
9165 \LWR@traceinfo{LWR@modifycolumn type done}%
9166 }

9167 \LWR@modifycolumn type{l}{0}{LWR@parsenormalcolumn}
9168 {LWR@printmccoltype@normal}{LWR@printmccoldata@normal}
9169
9170 \LWR@modifycolumn type{c}{0}{LWR@parsenormalcolumn}
9171 {LWR@printmccoltype@normal}{LWR@printmccoldata@normal}
9172
9173 \LWR@modifycolumn type{r}{0}{LWR@parsenormalcolumn}
9174 {LWR@printmccoltype@normal}{LWR@printmccoldata@normal}

9175 \LWR@modifycolumn type{@}{0}{LWR@parseatcolumn}
9176 {LWR@printmccoltype@ignore}{LWR@printmccoldata@other}
9177
9178 \LWR@modifycolumn type{!}{0}{LWR@parsebangcolumn}
9179 {LWR@printmccoltype@ignore}{LWR@printmccoldata@other}
9180
9181 \LWR@modifycolumn type{>}{0}{LWR@parsebeforecolumn}
9182 {LWR@printmccoltype@ignore}{LWR@printmccoldata@other}
9183
9184 \LWR@modifycolumn type{<}{0}{LWR@parseaftercolumn}
9185 {LWR@printmccoltype@ignore}{LWR@printmccoldata@other}
9186

```

```

9187 \LWR@modifycolumnntype{|}{0}{LWR@parsebarcolumn}
9188 {LWR@printmccoltype@vertbar}{LWR@printmccoldata@skip}
9189
9190 \LWR@modifycolumnntype{:}{0}{LWR@parsecoloncolumn}
9191 {LWR@printmccoltype@colon}{LWR@printmccoldata@skip}
9192
9193 \LWR@modifycolumnntype{;}{1}{LWR@parsesemicoloncolumn}
9194 {LWR@printmccoltype@semicolon}{LWR@printmccoldata@skip}

9195 \LWR@modifycolumnntype{p}{1}{LWR@parsenormalcolumn}
9196 {LWR@printmccoltype@normal}{LWR@printmccoldata@paragraph}
9197
9198 \LWR@modifycolumnntype{m}{1}{LWR@parsenormalcolumn}
9199 {LWR@printmccoltype@normal}{LWR@printmccoldata@paragraph}
9200
9201 \LWR@modifycolumnntype{b}{1}{LWR@parsenormalcolumn}
9202 {LWR@printmccoltype@normal}{LWR@printmccoldata@paragraph}

```

A star column:

```

9203 \LWR@modifycolumnntype{*}{2}{LWR@parsestarcolumn}
9204 {LWR@printmccoltype@ignore}{LWR@printmccoldata@skip}

```

`\HTMLnewcolumnntype` {<col type>} [<num args>] [<optional arg>] {<replacement text>}

A user-level macro to creates an HTML version of the replacement text for the column type.

This is the equivalent to:

```

\newcommand*{\LWR@HTML@NC@rewrite@<columnntype>}[<num args>]
 {\NC@find <replacement text>}
\LWR@formatted{NC@rewrite@<columnntype>}

```

```

9205 \NewDocumentCommand{\HTMLnewcolumnntype}{m O{0} o m}{%
9206 \IfValueTF{#3}
9207 {
9208 \expandafter\newcommand\expandafter*%
9209 \csname LWR@HTML@NC@rewrite@#1\endcsname[#2][#3]{\NC@find #4}%
9210 \LWR@formatted{NC@rewrite@#1}%
9211 }
9212 {
9213 \expandafter\newcommand\expandafter*%
9214 \csname LWR@HTML@NC@rewrite@#1\endcsname[#2]{\NC@find #4}%
9215 \LWR@formatted{NC@rewrite@#1}%
9216 }
9217 }

```

```
9218 \end{warphTML}
```

**for PRINT output:** 9219 \begin{warpprint}

```
9220 \NewDocumentCommand{\HTMLnewcolumnntype}{m O{0} o m}{}
```

```
9221 \end{warpprint}
```

**for HTML output:** 9222 \begin{warphTML}

`\LWR@parsetablecols`  $\{\langle colspecs \rangle\}$

Scans the column specification left to right.

Builds `\LWR@tablecolspec` with the final specification, one  $\LaTeX$  column per entry. The final number of  $\LaTeX$  columns in each row is stored in `\LWR@tabletotalLaTeXcols`, which is the number of `&` and `\` in each line, but which does not include `@`, `!`, `<`, `>` specifications in the count.

```
9223 \newcommand*\LWR@parsetablecols[1]{%
9224 \LWR@traceinfo{\LWR@parsetablecols}%
```

Remember the original supplied column spec:

```
9225 \renewcommand*\LWR@origcolspec{#1}%
```

Remove spaces:

```
9226 \expandarg%
9227 \StrSubstitute{\LWR@origcolspec}{ }{ }[\LWR@origcolspec]%
```

Expand any star columns:

```
9228 \LWR@expandpreamble{\LWR@origcolspec}%
9229 \edef\LWR@origcolspec{\the\@temptokena}%
```

The parsed column spec data array, `\LWR@tablecolspec`, will be overwritten with new values.

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```
9230 \defcounter{\LWR@tabletotalLaTeXcols}{0}%
9231 \defcounter{\LWR@tabletotalLaTeXcolsnext}{1}%
9232 \LWR@setexparray{\LWR@colatspec}{leftedge}{1}%
9233 \LWR@setexparray{\LWR@colatspec}{1}{1}%
9234 \LWR@setexparray{\LWR@colatspec}{2}{1}%
9235 \LWR@setexparray{\LWR@colatspec}{3}{1}%
9236 \LWR@setexparray{\LWR@colbangspec}{leftedge}{1}%
9237 \LWR@setexparray{\LWR@colbangspec}{1}{1}%
9238 \LWR@setexparray{\LWR@colbangspec}{2}{1}%
9239 \LWR@setexparray{\LWR@colbangspec}{3}{1}%
9240 \LWR@setexparray{\LWR@colbeforespec}{1}{1}%
9241 \LWR@setexparray{\LWR@colbeforespec}{2}{1}%
9242 \LWR@setexparray{\LWR@colbeforespec}{3}{1}%
9243 \LWR@setexparray{\LWR@colafterspec}{1}{1}%
9244 \LWR@setexparray{\LWR@colafterspec}{2}{1}%
9245 \LWR@setexparray{\LWR@colafterspec}{3}{1}%
9246 \LWR@setexparray{\LWR@colbarspec}{leftedge}{1}%
9247 \LWR@setexparray{\LWR@colbarspec}{1}{1}%
9248 \LWR@setexparray{\LWR@colbarspec}{2}{1}%
9249 \LWR@setexparray{\LWR@colbarspec}{3}{1}%
9250 \LWR@setexparray{\LWR@coladdclass}{1}{1}%
9251 \LWR@setexparray{\LWR@coladdclass}{2}{1}%
9252 \LWR@setexparray{\LWR@coladdclass}{3}{1}%
```

Starting at the first column specification:

```
9253 \defcounter{\LWR@tablecolspecindex}{1}%
```

Place the colspecs string length into `\LWR@strresult`, and remember the number of characters in the column specification:

```
9254 \expandarg%
9255 \StrLen{\LWR@origcolspec}[\LWR@strresult]%
9256 \fullexpandarg%
9257 \LWR@traceinfo{original column spec length: \LWR@strresult}%
9258 \defcounter{\LWR@tablecolspecwidth}{\LWR@strresult}%
```

Haven't seen any optional arguments so far

```
9259 \boolfalse{\LWR@opttablecol}%
```

Scan through the column specifications:

```
9260 \whileboolexpr{%
9261 not test{%
9262 \ifnumcomp{\value{\LWR@tablecolspecindex}}{>}%
9263 {\value{\LWR@tablecolspecwidth}}%
9264 }%
9265 }%
9266 {%
```

Place the next single-character column type into `\LWR@strresult`:

```
9267 \expandarg%
9268 \StrChar{\LWR@origcolspec}{\arabic{\LWR@tablecolspecindex}}[\LWR@strresult]%
9269 \LWR@traceinfo{position \arabic{\LWR@tablecolspecindex}: \LWR@strresult}%
9270 \fullexpandarg%
```

Not yet found a valid column type:

```
9271 \boolfalse{\LWR@validtablecol}%
```

Skip over any optional arguments, such as `siunitx S` column:

```
9272 \IfStrEq{\LWR@strresult}{[]}{\booltrue{\LWR@opttablecol}}{%}
```

Throw away anything found inside the optional argument:

```
9273 \ifbool{\LWR@opttablecol}%
9274 {}% inside an optional argument
9275 {% not an optional tabular argument
```

Not inside an optional argument, so consider the column type:

```
9276 \ifcsdef{\LWR@columnntype@\LWR@strresult}%
9277 {\csuse{\LWR@columnntype@\LWR@strresult}}%
9278 {}%
```

If an unknown column type, use `l`:

```
9279 \ifbool{\LWR@validtablecol}{}%
9280 \LWR@traceinfo{invalid column type: \LWR@strresult}%
9281 \LWR@parsenormalcolumn{l}%
9282 }%
9283 }% not an optional column argument
```

If read the closing bracket, no longer inside the optional argument:

```
9284 \IfStrEq{\LWR@strresult}{\boolfalse{LWR@opttablecol}}{}
```

Move to the next character:

```
9285 \defaddtocounter{LWR@tablecolspecindex}{1}%
9286 }% whiledo
9287 }%
```

## 75.15 colortbl and xcolor tabular color support

These macros provide a minimal emulation of some `colortbl` macros which might appear between table cells. If `colortbl` is loaded, these macros will be replaced with functional versions.

For each of the HTML colors below, the text for the HTML color is set if requested, but the macro is empty if none has been set.

`\rownum` Reserve a counter register.

```
9288 \ifundefined{rownum}{\newcount\rownum}{}
```

`\@rowcolors` Emulated in case `xcolor` is not used.

```
9289 \newcommand*\@rowcolors{}
```

`\@rowc@lors` Emulated in case `xcolor` is not used.

```
9290 \newcommand*\@rowc@lors{}
```

`\LWR@xcolorrowHTMLcolor` Emulated `xcolor` row color.

```
9291 \newcommand*\LWR@xcolorrowHTMLcolor{}
```

`\LWR@columnHTMLcolor` HTMLstyle code for the column color.

```
9292 \def\LWR@columnHTMLcolor{}
```

`\LWR@rowHTMLcolor` HTMLstyle code for the row color.

```
9293 \def\LWR@rowHTMLcolor{}
```

`\LWR@cellHTMLcolor` HTMLstyle code for the cell color.

```
9294 \def\LWR@cellHTMLcolor{}
```

`\LWR@ruleHTMLcolor` HTMLstyle code for the rule color.

```
9295 \newcommand*\LWR@ruleHTMLcolor{}
```

`\rowcolor` [*model*] {*color*} [*left overhang*] [*right overhang*] Print version. The HTML version is in `lwarp-colortbl`. Used before starting a tabular data cell, thus `\LWR@getmynexttoken`.

```
9296 \newcommand*{\rowcolor}{\LWR@getmynexttoken}%
```

`\arrayrulecolor` [*model*] {*color*}

`\arrayrulecolornexttoken` [*model*] {*color*}

Print versions for use outside and inside a tabular:

```
9297 \newcommand{\arrayrulecolor}[2][named]{}
```

```
9298 \newcommand{\arrayrulecolornexttoken}[2][named]{\LWR@getmynexttoken}
```

`\doublerulesepcolor` [*model*] {*color*}

`\doublerulesepcolornexttoken` [*model*] {*color*}

Print versions for use inside and outside a tabular:

```
9299 \newcommand{\doublerulesepcolor}[2][named]{}
```

```
9300 \newcommand{\doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}
```

## 75.16 Starting a new row

`\LWR@maybenewtablerow` If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for `hline` or `tbrule` if necessary.

```
9301 \newcommand*{\LWR@maybenewtablerow}
```

```
9302 {%
```

```
9303 \ifbool{\LWR@startedrow}%
```

```
9304 }% started the row
```

```
9305 }% not started the row
```

Remember that now have started the row:

```
9306 \booltrue{\LWR@startedrow}%
```

Create the row tag, with a class if necessary.

```
9307 \booltrue{\LWR@intabularmetadata}%
```

```
9308 \ifbool{expr{%
```

```
9309 test{\ifnumcomp{\value{\LWR@hlines}}{>}{0}} or%
```

```
9310 test{\ifnumcomp{\value{\LWR@hdashedlines}}{>}{0}}%
```

```
9311 }%
```

```
9312 {%
```

```
9313 \LWR@htmltag{tr class=\textquotedbl{}hline\textquotedbl }%
```

```
9314 \LWR@orignewline%
```

```
9315 }%
```

```
9316 {% not doing hline
```

```
9317 \ifbool{\LWR@doingtbrule}%
```

```
9318 {%
```

```
9319 \ifdefvoid{\LWR@ruleHTMLcolor}{%
```

```
9320 \LWR@htmltag{tr class=\textquotedbl{}tbrule\textquotedbl}%
```

```

9321 }{%
9322 \LWR@htmltag{%
9323 tr class=\textquotedbl{}tbrule\textquotedbl\ % space
9324 style=\textquotedbl{}border-top: 1px solid % space
9325 \LWR@origpound\LWR@ruleHTMLcolor \textquotedbl{}%
9326 }%
9327 }%
9328 \LWR@orignewline%
9329 }%
9330 {\LWR@htmltag{tr}\LWR@orignewline}%
9331 }% end of not doing hline
9332 }% end of not started the row
9333 }

```

## 75.17 Printing vertical bar tags

`\LWR@printbartag`  $\{\langle index \rangle\}$

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```

9334 \newcommand*{\LWR@printbartag}[1]{%
9335 \LWR@traceinfo{\LWR@printbartag !#1!}%
9336 \ifboolexpr{bool{\LWR@tabularmutemods} or bool{\LWR@emptyatbang}}%
9337 {}% muting or empty
9338 {% not muting
9339 \edef\LWR@tempone{\LWR@getexpparray{\LWR@colbarspec}{#1}}%
9340 \ifdefempty{\LWR@tempone}{\LWR@tempone}%
9341 }% not muting
9342 \LWR@traceinfo{\LWR@printbartag done}%
9343 }

```

## 75.18 Printing @ or ! tags

`\LWR@printatbang`  $\{\langle at \text{ — } or \text{ — } bang \rangle\} \{\langle index \rangle\}$

```

9344 \newcommand*{\LWR@printatbang}[2]{%

```

Fetch the column at or bang spec:

```

9345 \xdef\LWR@atbangspec{\LWR@getexpparray{\LWR@col#1spec}{#2}}%
9346 \LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}%

```

Only generate if is not empty;

```

9347 \ifdefempty{\LWR@atbangspec}%
9348 {}%
9349 {% not empty
9350 \LWR@htmltag{%
9351 td class=\textquotedbl{}td#1%
9352 \LWR@subaddcmidruletrim{}{}%
9353 \LWR@printbartag{#2}%
9354 \textquotedbl{}%
9355 \LWR@tdstartstyles%
9356 \LWR@addcmidrulewidth%
9357 \LWR@addcdashline%

```

```

9358 \LWR@addtabularrulecolors%
9359 \LWR@tdendstyles%
9360 }%

```

Create an empty cell if muting for the `\bottomrule`:

```

9361 \ifbool{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
9362 {}%
9363 {\LWR@atbangspec}%
9364 %
9365 \LWR@htmltag{/td}\LWR@orignewline%
9366 \global\booltrue{LWR@tabularcelladded}%
9367 }% not empty
9368 }%

```

`\LWR@addleftmostbartag`

```

9369 \newcommand*\LWR@addleftmostbartag{%
9370 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}{%
9371 \LWR@printbartag{leftedge}%
9372 }{%
9373 }

```

`\LWR@tabularleftedge`

```

9374 \newcommand*\LWR@tabularleftedge{%
9375 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}%
9376 {%
9377 \LWR@printatbang{at}{leftedge}%
9378 \LWR@printatbang{bang}{leftedge}%
9379 }% left edge
9380 {}% not left edge
9381 }

```

## 75.19 Cell opening tag

`\LWR@thiscolspec` Temporary storage.

```

9382 \newcommand*\LWR@thiscolspec{}

```

`\LWR@tabledatasinglecolumnntag` Print a table data opening tag with style for alignment and color.

```

9383 \newcommand*\LWR@tabledatasinglecolumnntag%
9384 {%
9385 \LWR@traceinfo{LWR@tabledatasinglecolumnntag}%
9386 \LWR@maybenewtablerow%

```

Don't start a new paragraph tag if have already started one:

```

9387 \ifbool{LWR@intabularmetadata}%
9388 {%

```

If have found the end of tabular command, do not create the next data cell:

```

9389 \ifbool{LWR@exitingtabular}{}%
9390 {% not exiting tabular

```

Print the @ and ! contents before first column:

```
9391 \LWR@tabularleftedge%
```

Fetch the current column's alignment character into \LWR@strresult:

```
9392 \xdef\LWR@strresult{%
9393 \LWR@getexparray{\LWR@tablecolspec}{\arabic{\LWR@tableLaTeXcolindex}}%
9394 }%
```

Print the start of a new table data cell:

```
9395 \LWR@traceinfo{\LWR@tabledatasinglecolumnntag: about to print td tag}%
9396 \LWR@htmltag{%
9397 td class=\textquotedbl{}td%
```

Append this column's spec:

```
9398 \LWR@strresult%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add vertical bar tags.

```
9399 \LWR@addcmidruletrim%
9400 \LWR@addleftmostbartag%
9401 \LWR@printbartag{\arabic{\LWR@tableLaTeXcolindex}}%
```

Add any tabular > column text alignment or font control css:

```
9402 \LWR@getexparray{\LWR@coladdclass}%
9403 {\arabic{\LWR@tableLaTeXcolindex}}%
```

Close the class description:

```
9404 \textquotedbl{}%
```

Add styles for rules, alignment:

```
9405 \LWR@tdstartstyles%
9406 \LWR@addcmidrulewidth%
9407 \LWR@addcdashline%

9408 \xdef\LWR@thiscolspec{%
9409 \LWR@getexparray{\LWR@tablecolspec}%
9410 {\arabic{\LWR@tableLaTeXcolindex}}%
9411 }%
9412 \LWR@addformatwpaignment{\LWR@thiscolspec}%
```

Add styles for cell and rule colors:

```
9413 \LWR@addtabulararrowcolor%
9414 \LWR@addtabularrulecolors%

9415 \LWR@tdendstyles%
9416 }% HTML td
9417 \LWR@traceinfo{\LWR@tabledatasinglecolumnntag: done printing td tag}%
```

If this is a p, m, b, or X column, allow paragraphs:

```

9418 \ifboolexpr{%
9419 test{ \ifdefstring{\LWR@strresult}{p} } or
9420 test{ \ifdefstring{\LWR@strresult}{m} } or
9421 test{ \ifdefstring{\LWR@strresult}{b} }
9422 }%
9423 {% allow pars
9424 \LWR@traceinfo{\LWR@tabledatasinglecolumn: about to LWR@startpars}%
9425 \booltrue{\LWR@tableparcell}%
9426 \LWR@startpars%
9427 \LWR@traceinfo{\LWR@tabledatasinglecolumn: done with LWR@startpars}%
9428 }% allow pars
9429 }% no pars

```

Print the > contents unless muted for the \bottomrule:

```

9430 \ifboolexpr{\bool{\LWR@tabularmutemods} or \bool{\LWR@emptyatbang}}%
9431 }%
9432 {%
9433 \LWR@gettexpparray{\LWR@colbeforespec}{\arabic{\LWR@tableLaTeXcolindex}}%
9434 }%
9435 \boolfalse{\LWR@intabularmetadata}%
9436 }% not exiting tabular
9437 }{}% in tabular metadata
9438 \LWR@traceinfo{\LWR@tabledatasinglecolumn: done}%
9439 }%

```

## 75.20 Midrules

`LWR@midrules` `LWR@midrules` is a data array (section 42) of columns each containing a non-zero width if a midrule should be created for this column.

`LWR@trimlrules` `LWR@trimlrules` is a data array (section 42) of columns containing `l` if a midrule should be left trimmed for each column.

`LWR@trimrrules` `LWR@trimrrules` is a data array (section 42) of columns containing `r` if a midrule should be right trimmed for each column.

`LWR@cdashlines` `LWR@cdashlines` is a data array (section 42) of columns each containing a `Y` if an `arydshln` package "cdashed line" should be created for this column.

Len `\LWR@heavyrulewidth` The default width of the rule.

```

9440 \newlength{\LWR@heavyrulewidth}
9441 \setlength{\LWR@heavyrulewidth}{.08em}

```

Len `\LWR@lightrulewidth` The default width of the rule.

```

9442 \newlength{\LWR@lightrulewidth}
9443 \setlength{\LWR@lightrulewidth}{.05em}

```

Len `\LWR@cmidrulewidth` The default width of the rule.

```

9444 \newlength{\LWR@cmidrulewidth}
9445 \setlength{\LWR@cmidrulewidth}{.03em}

```

Len `\LWR@thiscmidrulewidth` The width of the next rule, defaulting to `\LWR@cmidrulewidth`.

If not `\LWR@cmidrulewidth`, a style will be used to generate the custom width.

Assigned from the `LWR@midrules` array.

```
9446 \newlength{\LWR@thiscmidrulewidth}
9447 \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}
```

`\LWR@clearmidrules` Start new midrules. Called at beginning of tabular and also at `\`.

Clears all `LWR@midrules` and `LWR@trimrules` markers for this line.

```
9448 \newcommand*{\LWR@clearmidrules}
9449 {%
9450 \defcounter{LWR@midrulecounter}{1}%
9451 \whileboolexpr{%
9452 not test{%
9453 \ifnumcomp{\value{LWR@midrulecounter}}{>}%
9454 {\value{LWR@tabletotalLaTeXcols}}%
9455 }%
9456 }%
9457 {%
9458 \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{0pt}%
9459 \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
9460 \LWR@setexparray{LWR@trimrules}{\arabic{LWR@midrulecounter}}{}%
9461 \LWR@setexparray{LWR@trimrrules}{\arabic{LWR@midrulecounter}}{}%
9462 \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{N}%
9463 \defaddtocounter{LWR@midrulecounter}{1}%
9464 }%
9465 }
```

`\LWR@subcmidrule` `{<width>}{<trim>}{<leftcolumn>}{<rightcolumn>}`

Marks `LWR@midrules` data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

`LWR@doingcmidrule` is set to force an empty row at the end of the tabular to create the rule.

```
9466 \newcommand*{\LWR@subcmidrule}[4]{%
9467 \defcounter{LWR@midrulecounter}{#3}%
9468 \whileboolexpr{%
9469 not test {%
9470 \ifnumcomp{\value{LWR@midrulecounter}}{>}{#4}%
9471 }%
9472 }%
9473 {%
9474 \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{#1}%
9475 \defaddtocounter{LWR@midrulecounter}{1}%
9476 }%
9477 \IfSubStr{#2}{l}{\LWR@setexparray{LWR@trimrules}{#3}{l}}{}%
9478 \IfSubStr{#2}{r}{\LWR@setexparray{LWR@trimrrules}{#4}{r}}{}%
9479 \booltrue{LWR@doingcmidrule}%
9480 }
```

`\LWR@docmidrule` `[<width>] (<trim>) {<leftcolumn-rightcolumn>}`

Marks LWR@midrules array elements to be a non-zero width from left to right columns. Also marks trimming for the L and/or R columns.

```
9481 \NewDocumentCommand{\LWR@docmidrule}
9482 {O{\LWR@cmidrulewidth} D()} >{\SplitArgument{1}{-}}m}
9483 {\LWR@subcmidrule{#1}{#2}#3}
```

`\LWR@subcdashline`  $\{\langle leftcolumn \rangle\} \{\langle rightcolumn \rangle\}$

Marks LWR@cdashlines data array elements to be Y from left to right columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
9484 \newcommand*{\LWR@subcdashline}[2]{%
9485 \defcounter{LWR@midrulecounter}{#1}%
9486 \whileboolexpr{%
9487 not test {%
9488 \ifnumcomp{\value{LWR@midrulecounter}}{>}{#2}%
9489 }%
9490 }%
9491 {%
9492 \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{Y}%
9493 \defaddtocounter{LWR@midrulecounter}{1}%
9494 }% whiledo
9495 \booltrue{LWR@doingcmidrule}%
9496 }
```

`\LWR@docdashline`  $\{\langle leftcolumn-rightcolumn \rangle\}$

Marks LWR@cdashlines data array elements to be Y from left to right columns.

```
9497 \NewDocumentCommand{\LWR@docdashline}{>{\SplitArgument{1}{-}}m}%
9498 {%
9499 \LWR@subcdashline#1%
9500 }
```

`\LWR@tdstartstyles` Begins possibly adding a table data cell style.

```
9501 \newcommand*{\LWR@tdstartstyles}{\boolfalse{LWR@tdhavecellstyle}}
```

`\LWR@tdaddstyle` Starts adding a table data cell style.

```
9502 \newcommand*{\LWR@tdaddstyle}{%
9503 \ifbool{LWR@tdhavecellstyle}%
9504 {; }%
9505 { style=\textquotedbl}%
9506 \booltrue{LWR@tdhavecellstyle}%
9507 }
```

`\LWR@tdendstyles` Finishes possibly adding a table data cell style. Prints the closing quote.

```
9508 \newcommand*{\LWR@tdendstyles}{%
9509 \ifbool{LWR@tdhavecellstyle}%
9510 {%
9511 \textquotedbl%
```

```

9512 \boolfalse{LWR@tdhavecellstyle}%
9513 }{}%
9514 }

```

`\LWR@subaddcmidruletrim` `{\langlelefttrim\rangle}{\langlerighttrim\rangle}` Adds a `\cmidrule` with optional trim.

```

9515 \newcommand*{\LWR@subaddcmidruletrim}[2]{%
9516 \setlength{\LWR@templengthone}{%
9517 \LWR@getexparray{LWR@midrules}{\arabic{LWR@tableLaTeXcolindex}}%
9518 }%
9519 \ifdimcomp{\LWR@templengthone}{>}{\0pt}%
9520 {%

```

Print the class with left and right trim letters appended:

```

9521 \LWR@origtilde tdrule#1#2%

```

Remember the width of the rule:

```

9522 \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
9523 }%
9524 {%
9525 \setlength{\LWR@thiscmidrulewidth}{\0pt}%
9526 }%
9527 }

```

`\LWR@addcmidruletrim` Adds left or right trim to a `\cmidrule`.

```

9528 \newcommand*{\LWR@addcmidruletrim}{%
9529 \LWR@subaddcmidruletrim%
9530 {\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
9531 {\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@tableLaTeXcolindex}}}%
9532 }

```

`\LWR@addrulewidth` `{\langlethiswidth\rangle}{\langledefaultwidth\rangle}`

If not default width, add a custom style with width and color depending on `thiswidth`.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```

9533 \newcommand{\LWR@addrulewidth}[2]{%

```

Only add a custom width if `thiswidth` is different than the `defaultwidth`, or if a color is being used:

```

9534 \ifboolexpr{%
9535 test{\ifdimcomp{#1}{=}{\0pt}} or
9536 (
9537 (test{\ifdimcomp{#1}{=}{#2}} and not bool{FormatWP})
9538 and (test {\ifdefvoid{\LWR@ruleHTMLcolor}})
9539)
9540 }%
9541 {}% default width and color
9542 {% custom width and/or color

```

Ensure that the width is wide enough to display in the browser:

```
9543 \LWR@forceminwidth{#1}%
```

Begin adding another style:

```
9544 \LWR@tdaddstyle%
```

The style itself:

```
9545 border-top:\LWR@printlength{\LWR@atleastonept} solid % space
```

If default gray, the darkness of the color depends on the thickness of the rule:

```
9546 \ifdefvoid{\LWR@ruleHTMLcolor}{%
9547 \ifdimcomp{#1}{<}{\LWR@lightrulewidth}%
9548 {\LWR@origpound{A0A0A0}}%
9549 {% lightrule or heavier
9550 \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}%
9551 {\LWR@origpound{808080}}%
9552 {black}}%
9553 {% lightrule or heavier
9554 }{%
9555 \LWR@origpound\LWR@ruleHTMLcolor%
9556 }%
9557 }% custom width and/or color
9558 }
```

`\LWR@addcmidrulewidth` Adds a style for the rule width.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
9559 \newcommand{\LWR@addcmidrulewidth}{%
9560 \LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
9561 }
```

`\LWR@addcdashline` Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
9562 \newcommand{\LWR@addcdashline}{%
9563 \edef\LWR@tempone{%
9564 \LWR@getexparray{\LWR@cdashlines}{\arabic{\LWR@tableLaTeXcolindex}}%
9565 }%
9566 \ifdefstring{\LWR@tempone}{Y}{%
9567 \LWR@tdaddstyle%
9568 border-top: 1pt dashed %
9569 \ifdefvoid{\LWR@ruleHTMLcolor}%
9570 {black}%
9571 {\LWR@origpound\LWR@ruleHTMLcolor}%
9572 }{%
9573 }
```

`\LWR@WPcell` `{<text-align>}{<vertical-align>}`

```
9574 \newcommand*{\LWR@WPcell}[2]{%
9575 \LWR@tdaddstyle%
9576 \LWR@print@embox{text-align:#1}; \LWR@print@embox{vertical-align:#2}%
9577 }
```

`\LWR@addformatwpalignment`  $\langle\textit{colspec}\rangle$

If `FormatWP`, adds a style for the alignment.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```

9578 \newcommand*{\LWR@addformatwpalignment}[1]{%
9579 \ifbool{FormatWP}{%
9580 \IfSubStr{#1}{l}{\LWR@WPcell{left}{middle}}{%
9581 \IfSubStr{#1}{c}{\LWR@WPcell{center}{middle}}{%
9582 \IfSubStr{#1}{r}{\LWR@WPcell{right}{middle}}{%
9583 \IfSubStr{#1}{p}{\LWR@WPcell{left}{bottom}}{%
9584 \IfSubStr{#1}{m}{\LWR@WPcell{left}{middle}}{%
9585 \IfSubStr{#1}{b}{\LWR@WPcell{left}{top}}{%
9586 }{%
9587 }

```

## 75.21 Cell colors

`\LWR@addtabularrowcolor` Adds a cell's row color style, if needed.

No color is added for the final row of empty cells which finishes each `tabular`.

```

9588 \newcommand*{\LWR@addtabularrowcolor}{%
9589 \ifbool{LWR@tabularmutemods}{}%
9590 \ifdefvoid{\LWR@rowHTMLcolor}{%
9591 \ifdefvoid{\LWR@xcolorrowHTMLcolor}{%
9592 {% xcolor row color
9593 \LWR@tdaddstyle%
9594 background:\LWR@origpound\LWR@xcolorrowHTMLcolor%
9595 }%
9596 }%
9597 {% explicit row color
9598 \LWR@tdaddstyle%
9599 background:\LWR@origpound\LWR@rowHTMLcolor%
9600 }%
9601 }%
9602 }

```

`\LWR@addtabularhrulecolor` Adds a cell's horizontal rule color style, if needed.

```

9603 \newcommand*{\LWR@addtabularhrulecolor}{%

```

If either form of horizontal rule is requested:

```

9604 \ifboolexpr{%
9605 test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
9606 test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
9607 bool{LWR@doingtbrule}%
9608 }{%

```

If there is a no custom color:

```

9609 \ifdefvoid{\LWR@ruleHTMLcolor}%
9610 {%
9611 \ifnumcomp{\value{LWR@hlines}}{>}{1}%

```

```

9612 {%
9613 \LWR@tdaddstyle%
9614 border-top: 4px double%
9615 }{% else
9616 \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
9617 {%
9618 \LWR@tdaddstyle%
9619 border-top: 2px dashed%
9620 }{% else
9621 \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
9622 {%
9623 \LWR@tdaddstyle%
9624 border-top: 1px dashed%
9625 }{}}%

```

If no color and not doubled or dashed, then add nothing, since a simpler rule is the default.

```

9626 }%

```

If there is a custom color:

```

9627 {%
9628 \ifnumcomp{\value{LWR@hlines}}{>}{1}%
9629 {%
9630 \LWR@tdaddstyle%
9631 border-top: 4px double \LWR@origpound\LWR@ruleHTMLcolor%
9632 }{% else
9633 \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
9634 {%
9635 \LWR@tdaddstyle%
9636 border-top: 2px dashed \LWR@origpound\LWR@ruleHTMLcolor%
9637 }{% else
9638 \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
9639 {%
9640 \LWR@tdaddstyle%
9641 border-top: 1px dashed \LWR@origpound\LWR@ruleHTMLcolor%
9642 }{% else
9643 \LWR@tdaddstyle%
9644 border-top: 1px solid \LWR@origpound\LWR@ruleHTMLcolor%
9645 }}}}%
9646 }%
9647 }{}%
9648 }

```

`\LWR@addtabularrulecolors` Adds a cell's rule color styles, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```

9649 \newcommand*{\LWR@addtabularrulecolors}{%

```

Custom horizontal rule color:

```

9650 \LWR@addtabularhrulecolor%

```

No vertical rules if finishing the tabular with a row of empty cells:

```

9651 \ifbool{LWR@tabularmutemods}{}%

```

If at the leftmost cell, possibly add a leftmost vertical rule:

```
9652 \ifnumequal{\value{LWR@tableLaTeXcolindex}}{1}{%
```

Fetch the left edge's vertical bar specification:

```
9653 \edef\LWR@tempone{\LWR@getexpparray{LWR@colbarspec}{leftedge}}%
```

Add a custom style if a vertical bar was requested:

```
9654 \ifdefstring{\LWR@tempone}{tvertbarl}{%
9655 \LWR@tdaddstyle%
9656 border-left: 1px solid % space
9657 \LWR@vertruleHTMLcolor%
9658 }{}%
9659 \ifdefstring{\LWR@tempone}{tvertbarldouble}{%
9660 \LWR@tdaddstyle%
9661 border-left: 4px double % space
9662 \LWR@vertruleHTMLcolor%
9663 }{}%
9664 \ifdefstring{\LWR@tempone}{tvertbarldash}{%
9665 \LWR@tdaddstyle%
9666 border-left: 1px dashed % space
9667 \LWR@vertruleHTMLcolor%
9668 }{}%
9669 \ifdefstring{\LWR@tempone}{tvertbarldoubledash}{%
9670 \LWR@tdaddstyle%
9671 border-left: 2px dashed % space
9672 \LWR@vertruleHTMLcolor%
9673 }{}%
9674 }{}%
```

Possibly add a right vertical rule for this cell:

```
9675 \edef\LWR@tempone{%
9676 \LWR@getexpparray{LWR@colbarspec}{\arabic{LWR@tableLaTeXcolindex}}%
9677 }%
9678 \ifdefstring{\LWR@tempone}{tvertbarr}{%
```

Add a custom style if a vertical bar was requested:

```
9679 \LWR@tdaddstyle%
9680 border-right: 1px solid \LWR@vertruleHTMLcolor%
9681 }{}%
9682 \ifdefstring{\LWR@tempone}{tvertbarrdouble}{%
9683 \LWR@tdaddstyle%
9684 border-right: 4px double \LWR@vertruleHTMLcolor%
9685 }{}%
9686 \ifdefstring{\LWR@tempone}{tvertbarrdash}{%
9687 \LWR@tdaddstyle%
9688 border-right: 1px dashed \LWR@vertruleHTMLcolor%
9689 }{}%
9690 \ifdefstring{\LWR@tempone}{tvertbarrdoubledash}{%
9691 \LWR@tdaddstyle%
9692 border-right: 2px dashed \LWR@vertruleHTMLcolor%
9693 }{}%
9694 }%
9695 }
```

`\LWR@subaddtabularcellcolor` {<*html color*>}

```

9696 \newcommand*{\LWR@subaddtabularcellcolor}[1]{%
9697 \LWR@htmltag{div class=\textquotedbl{}cellcolor\textquotedbl\ % space
9698 style=\textquotedbl{}%
9699 background:\LWR@origpound{}}{#1 %
9700 \textquotedbl\ %
9701 }% space
9702 \defaddtocounter{LWR@cellcolordepth}{1}%
9703 }

```

`\LWR@addtabularcellcolor` Adds a cell color style, if needed.

```

9704 \newcommand*{\LWR@addtabularcellcolor}{%
9705 \ifdefvoid{\LWR@cellHTMLcolor}%
9706 {%
9707 \ifdefvoid{\LWR@rowHTMLcolor}%
9708 {%
9709 \ifdefvoid{\LWR@xcolorrowHTMLcolor}%
9710 {%
9711 \ifdefvoid{\LWR@columnHTMLcolor}%
9712 {}%
9713 {\LWR@subaddtabularcellcolor{\LWR@columnHTMLcolor}}%
9714 }%
9715 {\LWR@subaddtabularcellcolor{\LWR@xcolorrowHTMLcolor}}%
9716 }%
9717 {\LWR@subaddtabularcellcolor{\LWR@rowHTMLcolor}}%
9718 }%
9719 {\LWR@subaddtabularcellcolor{\LWR@cellHTMLcolor}}%
9720 }

```

## 75.22 Multicolumns

### 75.22.1 Parsing multicolumns

`\LWR@printmccoltype@normal` {<*col type*>}

Prints the column type, and remembers that any vertical bars are no longer on the left edge.

```

9721 \newcommand*{\LWR@printmccoltype@normal}[1]{%
9722 #1%
9723 \boolfalse{LWR@mcolvertbaronleft}%
9724 }

```

`\LWR@printmccoltype@ignore` {<*col type*>}

This type does not print a multi-column data cell.

```

9725 \newcommand*{\LWR@printmccoltype@ignore}[1]{%

```

`\LWR@printmccoltype@vertbar` {<*col type*>}

Adds a left or right vertical bar.

```

9726 \newcommand*{\LWR@printmccoltype@vertbar}[1]{%
9727 \ifbool{\LWR@mcolvertbaronleft}%
9728 {\defaddtocounter{\LWR@mcolvertbarsl}{1}}% left edge
9729 {\defaddtocounter{\LWR@mcolvertbarsr}{1}}% not left edge
9730 }

```

`\LWR@printmccoltype@colon` {<*col type*>}

Adds a left or right vertical bar.

```

9731 \newcommand*{\LWR@printmccoltype@colon}[1]{%
9732 \ifbool{\LWR@mcolvertbaronleft}%
9733 {\defaddtocounter{\LWR@mcolvertbarsldash}{1}}% left edge
9734 {\defaddtocounter{\LWR@mcolvertbarsrdash}{1}}% not left edge
9735 }

```

`\LWR@printmccoltype@semicolon` {<*col type*>}

Adds a left or right vertical bar.

```

9736 \let\LWR@printmccoltype@semicolon\LWR@printmccoltype@colon

```

`\LWR@printmccoltype` {<*colspec*>} Print any valid column type found. Does not print @, !, >, or < columns or their associated tokens.

This is printed as part of the table data tag's class.

`\LWR@columntype@mctype@<type>` is defined by `\LWR@modifycolumnntype`.

```

9737 \newcommand*{\LWR@printmccoltype}[1]{%
9738 \LWR@traceinfo{\lwr@printmccoltype -#1-}%

```

Get one token of the column spec:

```

9739 \StrChar{#1}{\arabic{\LWR@tablemulticolspos}}[\LWR@strresult]%

```

Detokenize to avoid problems with special characters:

```

9740 \edef\LWR@strresult{\detokenize\expandafter{\LWR@strresult}}%

```

Add to the HTML tag depending on which column type is found:

```

9741 \ifcsdef{\LWR@columntype@mctype@\LWR@strresult}%
9742 {\csuse{\LWR@columntype@mctype@\LWR@strresult}}%
9743 {\boolfalse{\LWR@mcolvertbaronleft}}%
9744 \LWR@traceinfo{\lwr@printmccoltype done}%
9745 }

```

`\LWR@printmccoldata@other` {<*num args to skip*>} {<*entire colspec*>}

For @, !, >, <, print the next token without paragraph tags:

```

9746 \newcommand*{\LWR@printmccoldata@other}[2]{%
9747 \defaddtocounter{\LWR@tablemulticolspos}{1}%
9748 \StrChar{#2}{\arabic{\LWR@tablemulticolspos}}[\LWR@strresult]%
9749 \LWR@strresult%

```

A valid column data type was found:

```
9750 \booltrue{LWR@validtablecol}%
9751 }
```

`\LWR@printmccoldata@skip` {*<num args to skip>*} {*<entire colspec>*}

Nothing to print for this column type.

```
9752 \newcommand*{\LWR@printmccoldata@skip}[2]{%
9753 \defaddtocounter{LWR@tablemulticolspos}{#1}%
```

A valid column data type was found:

```
9754 \booltrue{LWR@validtablecol}%
9755 }
```

For `\LWR@printmccoldata@. . .>`, {*<num args to skip>*} is provided by `\LWR@column@type@mccoldata@<coltype>` when it was defined by `\LWR@modify@column@type`. `\entire colspec` is provided by `\LWR@printmccoldata` when it uses `\LWR@column@type@mccoldata@<coltype>`.

`\LWR@printmccoldata@normal` {*<num args to skip>*} {*<entire colspec>*}

```
9756 \newcommand*{\LWR@printmccoldata@normal}[2]{%
9757 \LWR@multicoltext%
9758 \defaddtocounter{LWR@tablemulticolspos}{#1}%
9759 }
```

`\LWR@printmccoldata@paragraph` {*<num args to skip>*} {*<entire colspec>*}

```
9760 \newcommand*{\LWR@printmccoldata@paragraph}[2]{%
9761 \LWR@startpars%
9762 \LWR@multicoltext%
9763 \defaddtocounter{LWR@tablemulticolspos}{#1}%
9764 \LWR@stoppars%
9765 }
```

`\LWR@printmccoldata` {*<entire colspec>*}

Print the data for any valid column type found.

```
9766 \newcommand*{\LWR@printmccoldata}[1]{%
9767 \LWR@traceinfo{LWR@printmccoldata -#1}%
```

Not yet found a valid column type:

```
9768 \boolfalse{LWR@validtablecol}%
```

Get one token of the column spec, into a local copy in case nested.

```
9769 \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
9770 \def\LWR@printmccoldata@token{\LWR@strresult}%
```

Print the text depending on which column type is found. Also handles @, >, < as it comes to them.

```

9771 \ifcsdef{LWR@columnntype@mcdata@\LWR@printmccoldata token}%
9772 {\csuse{LWR@columnntype@mcdata@\LWR@printmccoldata token}{#1}}%
9773 }%

```

If an unknown column type, print the text:

```

9774 \ifbool{LWR@validtablecol}{ }\LWR@multicoltext{}%

```

Tracing:

```

9775 \LWR@traceinfo{lwr@printmccoldata done}%
9776 }

```

```

\parsemulticolumnalignment {<1: colspec>} {<2: printresults csname>}

```

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a p{spec} column, or @, >, <, is a token list which will NOT match l, c, r, or p.

```

9777 \newcommand*{\LWR@parsemulticolumnalignment}[2]{%
9778 \defcounter{LWR@tablemulticolspos}{1}%
9779 \StrLen{#1}[\LWR@strresult]%
9780 \defcounter{LWR@tablemulticolwidth}{\LWR@strresult}%

```

Scan across the tokens in the column spec:

```

9781 \whileboolexpr{%
9782 not test {%
9783 \ifnumcomp{\value{LWR@tablemulticolspos}}{>}%
9784 {\value{LWR@tablemulticolwidth}}%
9785 }%
9786 }%
9787 {%

```

Execute the assigned print function for each token in the column spec:

```

9788 \csuse{#2}{#1}%

```

Move to the next token in the column spec:

```

9789 \defaddtocounter{LWR@tablemulticolspos}{1}%
9790 }%
9791 }

```

### 75.22.2 Multicolumn factored code

```

\LWR@addmulticolvertrulecolor

```

```

9792 \newcommand*{\LWR@addmulticolvertrulecolor}{%

```

No vertical rules if finishing the tabular with a row of empty cells:

```

9793 \ifbool{LWR@tabularmutemods}{ }%

```

Left side:

```

9794 \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{%
9795 \LWR@tdaddstyle%
9796 border-left: 1px solid \LWR@vertruleHTMLcolor%
9797 }{%
9798 \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{%
9799 \LWR@tdaddstyle%
9800 border-left: 4px double \LWR@vertruleHTMLcolor%
9801 }{%
9802 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{%
9803 \LWR@tdaddstyle%
9804 border-left: 1px dashed \LWR@vertruleHTMLcolor%
9805 }{%
9806 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
9807 \LWR@tdaddstyle%
9808 border-left: 2px dashed \LWR@vertruleHTMLcolor%
9809 }{%

```

Right side:

```

9810 \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{%
9811 \LWR@tdaddstyle%
9812 border-right: 1px solid \LWR@vertruleHTMLcolor%
9813 }{%
9814 \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{%
9815 \LWR@tdaddstyle%
9816 border-right: 4px double \LWR@vertruleHTMLcolor%
9817 }{%
9818 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{%
9819 \LWR@tdaddstyle%
9820 border-right: 1px dashed \LWR@vertruleHTMLcolor%
9821 }{%
9822 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
9823 \LWR@tdaddstyle%
9824 border-right: 2px dashed \LWR@vertruleHTMLcolor%
9825 }{%
9826 }%
9827 }

```

```
9828 \newcommand{\LWR@multicoltext}{}

```

To find multicolumn right trim:

```
9829 \newcounter{LWR@lastmulticolumn}

```

```
\LWR@domulticolumn [1: vpos] [2: #rows] [3: numLaTeXcols] [4: numHTMLcols] [5: colspec]
{6: text}
```

```

9830 \NewDocumentCommand{\LWR@domulticolumn}{o o m m +m}{%
9831 \LWR@traceinfo{\LWR@domulticolumn -#1- -#2- -#4- -#5-}%

```

Remember the text to be inserted, and when used remember that a valid column type was found:

```

9832 \renewcommand{\LWR@multicoltext}{%
9833 #6%
9834 \booltrue{LWR@validtablecol}%

```

9835 }%

Expand the preamble and save it.

```
9836 \LWR@expandpreamble{#5}%
9837 \edef\LWR@origmccolspec{\the\@temptokena}%
```

Compute the rightmost column to be included. This is used to create the right trim.

```
9838 \defcounter{LWR@lastmulticolumn}{\value{LWR@tableLaTeXcolindex}}%
9839 \defaddtocounter{LWR@lastmulticolumn}{#3}%
9840 \defaddtocounter{LWR@lastmulticolumn}{-1}%
```

Row processing:

```
9841 \LWR@maybenewtablerow%
```

Begin the opening table data tag:

```
9842 \LWR@htmltag{%
9843 td colspan=\textquotedbl#4\textquotedbl\ %

9844 \IfValueT{#2}{ % rows?
9845 rowspan=\textquotedbl#2\textquotedbl\ %
9846 }%

9847 class=\textquotedbl{}td%
```

Print the column type and vertical bars:

```
9848 \defcounter{LWR@mcolvertbarsl}{0}%
9849 \defcounter{LWR@mcolvertbarsr}{0}%
9850 \defcounter{LWR@mcolvertbarsldash}{0}%
9851 \defcounter{LWR@mcolvertbarsrdash}{0}%
9852 \booltrue{LWR@mcolvertbaronleft}%
9853 \LWR@parsemulticolumnalignment{\LWR@origmccolspec}{LWR@printmcoltype}%
```

If this column has a `cmidrule`, add “rule” to the end of the HTML class tag.

If this position had a “Y” then add “rule” for a horizontal rule:

```
9854 \LWR@subaddcmidruletrim%
9855 {%
9856 \LWR@getexparray{LWR@trimlrules}%
9857 {\arabic{LWR@tableLaTeXcolindex}}%
9858 }%
9859 {%
9860 \LWR@getexparray{LWR@trimrrules}%
9861 {\arabic{LWR@lastmulticolumn}}%
9862 }%
```

Also add vertical bar class.

```
9863 \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{ tvertbarl}{}%
9864 \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{ tvertbarldouble}{}%
9865 \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{ tvertbarr}{}%
```

```

9866 \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{ tvertbarrdouble}{}%
9867 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{ tvertbarldash}{}%
9868 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}%
9869 { tvertbarldoubledash}{}%
9870 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{ tvertbarrdash}{}%
9871 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}%
9872 { tvertbarrdoubledash}{}%

```

Close the class tag's opening quote:

```

9873 \textquotedbl{}%

9874 \LWR@tdstartstyles%

```

Style for vertical position:

```

9875 \IfValueT{#1}{% vpos?
9876 \ifstrequal{#1}{b}%
9877 {%
9878 \LWR@tdaddstyle%
9879 \LWR@print@ebox{vertical-align:bottom}%
9880 }{%
9881 \ifstrequal{#1}{t}%
9882 {%
9883 \LWR@tdaddstyle%
9884 \LWR@print@ebox{vertical-align:top}%
9885 }{%
9886 }% vpos?

```

Style for row colors:

```

9887 \LWR@addtabularrowcolor%

```

Other styles:

```

9888 \LWR@addcmidrulewidth%
9889 \LWR@addcdashline%
9890 \LWR@addtabularhrulecolor%
9891 \LWR@addmulticolvertrulecolor%
9892 \LWR@addformatwpaignment{\LWR@origmccolspec}%
9893 \LWR@tdendstyles%
9894 }% end of the opening table data tag
9895 \boolfalse{LWR@intabularmetadata}%
9896 \LWR@parsemulticolumnalignment{\LWR@origmccolspec}{LWR@printmccoldata}%
9897 }

```

### 75.22.3 Multicolumn

```
\LWR@htmlmulticolumn {<numcols>}{<alignment>}{<text>}
```

```

9898 \NewDocumentCommand{\LWR@htmlmulticolumn}{m m +m}%
9899 {%

```

Figure out how many extra HTML columns to add for @ and ! columns:

```

9900 \LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}%

```

Create the multicolumn tag:

```
9901 \LWR@domulticolumn{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#3}%
```

Move to the next L<sup>A</sup>T<sub>E</sub>X column:

```
9902 \defaddtocounter{LWR@tableLaTeXcolindex}{#1}%
9903 \defaddtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
9904 \booltrue{LWR@skipatbang}%
9905 }
```

#### 75.22.4 Longtable captions

longtable captions use \multicolumn.

Per the caption package. User-redefinable float type.

```
9906 \providecommand*{\LTcapttype}{table}
```

```
\LWR@longtabledatacaptiontag * [⟨toc entry⟩] {⟨caption⟩}
```

```
9907 \NewDocumentCommand{\LWR@longtabledatacaptiontag}{s o +m}
9908 {%
```

Remember the latest name for \nameref:

```
9909 \IfValueTF{#2}{% optional given?
9910 \ifblank{#2}% optional empty?
9911 {\LWR@setlatestname{#3}}% empty
9912 {\LWR@setlatestname{#2}}% given and non-empty
9913 }% optional given
9914 {\LWR@setlatestname{#3}}% no optional
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for @ and ! columns found between the first and the last column:

```
9915 \LWR@tabularhtmlcolumns{1}{\arabic{LWR@tabletotalLaTeXcols}}%
```

Create the multicolumn tag. The caption will be centered by the css caption class.

```
9916 \LWR@domulticolumn{\arabic{LWR@tabletotalLaTeXcols}}%
9917 {\arabic{LWR@tabhtmlcoltotal}}%
9918 {p}%
9919 {% \LWR@domulticolumn
9920 \IfBooleanTF{#1}% star?
```

Star version, show a caption but do not make a LOT entry:

```
9921 {% yes star
9922 \LWR@figcaption%
```

```

9923 \LWR@isolate{#3}%
9924 \endLWR@figcaption%
9925 }%
9926 {% No star:

```

Not the star version:

Don't step the counter if \caption[] {A caption.}

```

9927 \ifbool{LWR@starredlongtable}%
9928 {%
9929 \ifblank{#2}% TOC entry
9930 {}%
9931 {%
9932 \refstepcounter{\LTcapttype}%
9933 \protected@edef\@currentlabel{%
9934 \@nameuse{p@\LTcapttype}\@nameuse{the\LTcapttype}%
9935 }%
9936 }%
9937 }{}%

```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```

9938 \LWR@figcaption%
9939 \LWR@isolate{\@nameuse{fnum@\LTcapttype}}%
9940 \CaptionSeparator%
9941 \LWR@isolate{#3}%
9942 \endLWR@figcaption%

```

See if an optional caption was given:

```

9943 \ifblank{#2}% TOC entry empty

```

if the optional caption was given, but empty, do not form a TOC entry

```

9944 {}%

```

If the optional caption was given, but might only be []:

```

9945 {% TOC entry not empty
9946 \IfNoValueTF{#2}% No TOC entry?

```

The optional caption is []:

```

9947 {% No TOC entry
9948 \addcontentsline%
9949 {\@nameuse{ext@\LTcapttype}}%
9950 {\LTcapttype}%
9951 {%
9952 \protect\numberline%
9953 {\LWR@isolate{\@nameuse{p@\LTcapttype}}\@nameuse{the\LTcapttype}}%
9954 {\ignorespaces \LWR@isolate{#3}\protect\relax}%
9955 }%
9956 }% end of No TOC entry

```

The optional caption has text enclosed:

```

9957 {% yes TOC entry

```

```

9958 \addcontentsline%
9959 {\@nameuse{ext@LTcapttype}}%
9960 {\LTcapttype}%
9961 {%
9962 \protect\numberline%
9963 {\LWR@isolate{\@nameuse{p@LTcapttype}}\@nameuse{theLTcapttype}}%
9964 {\ignorespaces \LWR@isolate{#2}\protect\relax}%
9965 }%
9966 }% end of yes TOC entry
9967 }% end of TOC entry not empty
9968 }% end of no star

```

Skip any trailing @ or ! columns for this cell:

```

9969 \booltrue{LWR@skipatbang}%
9970 }% end of \LWR@domulticolumn
9971 \defaddtocounter{LWR@tableLaTeXcolindex}{\value{LWR@tabletotalLaTeXcols}}%
9972 \defaddtocounter{LWR@tableLaTeXcolindex}{-1}
9973
9974 }

```

### 75.22.5 Counting HTML tabular columns

The L<sup>A</sup>T<sub>E</sub>X specification for a table includes a number of columns separated by the & character. These columns differ in content from line to line. Additional virtual columns may be specified by the special @ and ! columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, @ and ! columns are placed into their own tabular columns. Thus, a L<sup>A</sup>T<sub>E</sub>X \multicolumn command may span several additional @ and ! columns in HTML output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```

9975 \newcounter{LWR@tabhtmlcolindex}
9976 \newcounter{LWR@tabhtmlcolend}
9977 \newcounter{LWR@tabhtmlcoltotal}

```

\LWR@subtabularhtmlcolumns {<index>}

Factored from \LWR@tabularhtmlcolumns, which follows.

```

9978 \newcommand*\LWR@subtabularhtmlcolumns}[1]{%

```

Temporarily define a macro equal to the @ specification for this column:

```

9979 \edef\LWR@atbangspec{\LWR@getexparray{LWR@colatspec}{#1}}%

```

If the @ specification is not empty, add to the count:

```

9980 \ifdefempty{\LWR@atbangspec}%
9981 {%
9982 \defaddtocounter{LWR@tabhtmlcoltotal}{1}}%

```

Likewise for the ! columns:

```

9983 \edef\LWR@atbangspec{\LWR@getexparray{LWR@colbangspec}{#1}}%

```

```

9984 \ifdefempty{\LWR@atbangspec}%
9985 {}%
9986 {\defaddtocounter{LWR@tabhtmlcoltotal}{1}}%
9987 }

```

`\LWR@tabularhtmlcolumns`  $\{\langle starting \textit{L}^{\textit{A}}\textit{T}^{\textit{E}}\textit{X} \textit{c}^{\textit{o}}\textit{l}^{\textit{u}}\textit{m}^{\textit{n}}\rangle\} \{\langle number \textit{L}^{\textit{A}}\textit{T}^{\textit{E}}\textit{X} \textit{c}^{\textit{o}}\textit{l}^{\textit{u}}\textit{m}^{\textit{n}}\rangle\}$

Compute the total number of HTML columns being spanned, considering the starting  $\textit{L}^{\textit{A}}\textit{T}^{\textit{E}}\textit{X}$  table column and the number of  $\textit{L}^{\textit{A}}\textit{T}^{\textit{E}}\textit{X}$  tabular columns being spanned. Any @ and ! columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter `LWR@tabhtmlcoltotal`.

```

9988 \newcommand*{\LWR@tabularhtmlcolumns}[2]{%

```

Count the starting index, compute ending index, and begin with the count being the  $\textit{L}^{\textit{A}}\textit{T}^{\textit{E}}\textit{X}$  span, to which additional @ and ! columns may be added:

```

9989 \defcounter{LWR@tabhtmlcolindex}{#1}%
9990 \defcounter{LWR@tabhtmlcoltotal}{#2}%
9991 \defcounter{LWR@tabhtmlcolend}{#1}%
9992 \defaddtocounter{LWR@tabhtmlcolend}{#2}%

```

If at the left edge, add the at/bang columns for the left edge:

```

9993 \ifnumcomp{\value{LWR@tabhtmlcolindex}}{=}{1}{%
9994 \LWR@subtabularhtmlcolumns{leftedge}%
9995 }{%

```

Walk across the  $\textit{L}^{\textit{A}}\textit{T}^{\textit{E}}\textit{X}$  columns looking for @ and ! columns:

```

9996 \whileboolexpr{%
9997 test {%
9998 \ifnumcomp{\value{LWR@tabhtmlcolindex}}{<}{\value{LWR@tabhtmlcolend}}%
9999 }%
10000 }%
10001 {%
10002 \LWR@subtabularhtmlcolumns{\arabic{LWR@tabhtmlcolindex}}%
10003 \defaddtocounter{LWR@tabhtmlcolindex}{1}%
10004 }% whiledo
10005 }

10006 \end{warpHTML}

```

### 75.23 Multirow if not loaded

A default definition in case `multirow` is not loaded. This is used during table parsing.

```

10007 \begin{warpHTML}
10008 \newcommand{\multirow}[2][c]{}
10009 \end{warpHTML}

```

### 75.24 Multicolumnrow

A print-mode version is defined here, and is also used during HTML output while inside a `lateximage`.

See section 429 for the HTML versions.

**for HTML & PRINT:** 10010 \begin{warpall}

```
\multicolumnrow {<1:cols>} {<2:halign>} [<3:vpos>] {<4:numrows>} [<5:bigstruts>] {<6:width>} [<7:fixup>]
{<8:text>}
```

For discussion of the use of \DeclareExpandableDocumentCommand, see:

<https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex>

\AtBeginDocument to adjust after the user may have loaded multirow, which requires several tests to determine which version is loaded and thus which options are available.

```
10011 \AtBeginDocument{
```

\ifundefined{@xmultirow} determines if multirow was never loaded.

Null action if not loaded:

```
10012 \ifundefined{@xmultirow}
10013 {
10014 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
10015 {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
10016 {}%
10017 }% no version of multirow was loaded
10018 {% \xmultirow defined, so some version of multirow was loaded
```

\IfPackageLoadedTF{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The print version:

```
10019 \IfPackageLoadedTF{multirow}{% v2.0 or newer
10020 \IfPackageAtLeastTF{multirow}{2016/09/01}% 2016/09/27 for v2.0
10021 {% v2.0+:
10022 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
10023 {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
10024 {\multicolumn{#1}{#2}{\xmultirow[#3][#4][#5][#6][#7][#8]}}%
10025 }
10026 {% loaded but older, probably not executed:
10027 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
10028 {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
10029 {\multicolumn{#1}{#2}{\xmultirow[#4][#5][#6][#7][#8]}}%
10030 }
10031 }% packagedloaded{multirow}
```

If not \IfPackageLoadedTF{multirow} but \xmultirow is defined, then this must be v1.6 or earlier, which did not \ProvidesPackage{multirow}, and did not have the vposn option.

```
10032 {% v1.6 or older did not \ProvidePackage
10033 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
10034 {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
10035 {\multicolumn{#1}{#2}{\xmultirow[#4][#5][#6][#7][#8]}}%
10036 }
10037
```

```

10038 }% \ifundefined{@xmultirow}
10039
10040 \providecommand*\multicolumnrow{\LWR@print@multicolumnrow}
10041
10042 }% AtBeginDocument

10043 \end{warpall}

```

## 75.25 Utility macros inside a table

**for HTML output:** 10044 \begin{warpHTML}

Used to prevent opening a tabular data cell if the following token is one which does not create tabular data:

```
10045 \newcommand*\LWR@doanything{}
```

In case array is not loaded:

```

10046 \let\firsthline\relax
10047 \let\lasthline\relax
10048 \newcommand*\firsthline{}
10049 \newcommand*\lasthline{}

```

In case bigdelim is not loaded:

```

10050 \newcommand*\ldelim{}
10051 \newcommand*\rdelim{}

```

```
10052 \end{warpHTML}
```

## 75.26 Special-case tabular markers

**for HTML & PRINT:** 10053 \begin{warpall}

`\TabularMacro` Place this just before inserting a custom macro in a table data cell. Doing so tells **lwarp** not to automatically start a new HTML table data cell yet. See section [8.10.1](#).

```
10054 \newcommand*\TabularMacro{}
```

```
10055 \end{warpall}
```

`\ResumeTabular` Used to resume tabular entries after resuming an environment.

 **tabular inside another environment** When creating a new environment which contains a tabular environment, **lwarp**'s emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```

\StartDefiningTabulars % (& is used in a definition)
\newenvironment{outerenvironment}
{
 \tabular{cc}
 left & right \\
}
{
 \TabularMacro\ResumeTabular
 left & right \\
 \endtabular
}
\StopDefiningTabulars

```

**for HTML output:** 10056 \begin{warpHTML}

```

10057 \newcommand*\ResumeTabular{%
10058 \boolfalse{LWR@exitingtabular}%
10059 \boolfalse{LWR@tabularmutemods}%
10060 \LWR@getmynexttoken%
10061 }

```

```
10062 \end{warpHTML}
```

**for PRINT output:** 10063 \begin{warpprint}

```
10064 \newcommand*\ResumeTabular{}
```

```
10065 \end{warpprint}
```

## 75.27 Checking for a new table cell

**for HTML output:** 10066 \begin{warpHTML}

`\LWR@tabledatacolumnstag` Open a new HTML table cell unless the next token is for a macro which does not create data, such as `\hline`, `\toprule`, etc:

```

10067 \newcommand*\LWR@tabledatacolumnstag%
10068 {%
10069 \LWR@traceinfo{LWR@tabledatacolumnstag}%

```

`\show\LWR@mynexttoken` to see what tokens to look for

If not any of the below, start a new table cell:

```
10070 \global\let\LWR@mynextaction\LWR@tabledatasinglecolumnstag%
```

If exiting the tabular:

```

10071 \ifdefequal{\LWR@mynexttoken}{\end}%
10072 {\booltrue{LWR@exitingtabular}}{}%

```

longtable can have a caption in a cell

```
10073 \ifdefequal{\LWR@mynexttoken}{\caption}%
10074 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

Look for other things which would not start a table cell:

```
10075 \ifdefequal{\LWR@mynexttoken}{\multicolumn}%
10076 {\global\let\LWR@mynextaction\LWR@donothing}}%
10077 \ifdefequal{\LWR@mynexttoken}{\multirow}%
10078 {\global\let\LWR@mynextaction\LWR@donothing}}%
10079 \ifdefequal{\LWR@mynexttoken}{\multicolumnrow}%
10080 {\global\let\LWR@mynextaction\LWR@donothing}}%
10081 \ifdefequal{\LWR@mynexttoken}{\noalign}%
10082 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

If an `\mrowcell`, this is a cell to be skipped over:

```
10083 \ifdefequal{\LWR@mynexttoken}{\mrowcell}%
10084 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

If an `\mcolrowcell`, this is a cell to be skipped over:

```
10085 \ifdefequal{\LWR@mynexttoken}{\mcolrowcell}%
10086 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10087 \ifdefequal{\LWR@mynexttoken}{\TabularMacro}%
10088 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10089 \ifdefequal{\LWR@mynexttoken}{\hline}%
10090 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10091 \ifdefequal{\LWR@mynexttoken}{\firsthline}%
10092 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10093 \ifdefequal{\LWR@mynexttoken}{\lasthline}%
10094 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10095 \ifdefequal{\LWR@mynexttoken}{\toprule}%
10096 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10097 \ifdefequal{\LWR@mynexttoken}{\midrule}%
10098 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10099 \ifdefequal{\LWR@mynexttoken}{\cmidrule}%
10100 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10101 \ifdefequal{\LWR@mynexttoken}{\morecmidrules}%
10102 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10103 \ifdefequal{\LWR@mynexttoken}{\specialrule}%
10104 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```
10105 \ifdefequal{\LWR@mynexttoken}{\cline}%
10106 {\global\let\LWR@mynextaction\LWR@donothing}}%
```

```

10107 \ifdefequal{\LWR@mynexttoken}{\bottomrule}%
10108 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10109 \ifdefequal{\LWR@mynexttoken}{\hhline}%
10110 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10111 \ifdefequal{\LWR@mynexttoken}{\rowcolor}%
10112 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10113 \ifdefequal{\LWR@mynexttoken}{\arrayrulecolor}%
10114 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10115 \ifdefequal{\LWR@mynexttoken}{\doublerulesepcolor}%
10116 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10117 \ifdefequal{\LWR@mynexttoken}{\warpprintonly}%
10118 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10119 \ifdefequal{\LWR@mynexttoken}{\warpHTMLonly}%
10120 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10121 \ifdefequal{\LWR@mynexttoken}{\ldelim}%
10122 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10123 \ifdefequal{\LWR@mynexttoken}{\rdelim}%
10124 {\global\let\LWR@mynextaction\LWR@donothing}}}%

```

For arydashln:

```

10125 \ifdefequal{\LWR@mynexttoken}{\hdashline}%
10126 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10127 \ifdefequal{\LWR@mynexttoken}{\cdashline}%
10128 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10129 \ifdefequal{\LWR@mynexttoken}{\firstdashline}%
10130 {\global\let\LWR@mynextaction\LWR@donothing}}}%

10131 \ifdefequal{\LWR@mynexttoken}{\lastdashline}%
10132 {\global\let\LWR@mynextaction\LWR@donothing}}}%

```

Ignore an empty line between rows:

```

10133 \ifdefequal{\LWR@mynexttoken}{\par}%
10134 {%
10135 \global\let\LWR@mynextaction\LWR@donothing%
10136 }}%

```

No action for an \end token.

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```

10137 \LWR@traceinfo{\LWR@tabledatacolumnntag: done, about to do \LWR@mynextaction}%
10138 \LWR@mynextaction%
10139 }

```

```
10140 \end{warpHTML}
```

## 75.28 \mrowcell

**for HTML & PRINT:** 10141 \begin{warpall}

 **multirow cells** `\mrowcell` The user must insert `\mrowcell` into any `\multirow` cells which must be skipped. This command has no action during print output.

```
10142 \newcommand*\mrowcell{}
```

```
10143 \end{warpall}
```

## 75.29 \mcolrowcell

**for HTML & PRINT:** 10144 \begin{warpall}

 **multirow cells** `\mcolrowcell` The user must insert `\mcolrowcell` into any `\multicolumnrow` cells which must be skipped. This command has no action during print output.

```
10145 \newcommand*\mcolrowcell{}
```

```
10146 \end{warpall}
```

## 75.30 HTML tabular environment

**for HTML output:** 10147 \begin{warpHTML}

These are default definitions in case `booktabs` is not loaded, and are not expected to be used, but must exist as placeholders. `memoir` may have already loaded `booktabs`.

```
10148 \providecommand*\toprule[1][\hline]
10149 \providecommand*\midrule[1][\hline]
10150 \providecommand*\cmidrule{\cline}
10151 \providecommand*\bottomrule[1][\hline]
10152 \providecommand*\addlinespace[1][\hline]
10153 \providecommand*\morecmidrules{}
10154 \providecommand*\specialrule[3][\hline]
```

`\noalign`  $\langle text \rangle$  Redefined for use inside `tabular`.

```
10155 \LetLtxMacro\LWR@orignoalign\noalign
10156
10157 \newcommand{\LWR@tabularnoalign}[1]{%
10158 \advance\rownum\m@ne%
10159 \LetLtxMacro\LWR@save@xcolorrowHTMLcolor\LWR@xcolorrowHTMLcolor%
10160 \renewcommand*\LWR@xcolorrowHTMLcolor{}%
10161 \multicolumn{\value{\LWR@tabletotalLaTeXcols}}{L}{#1} \\\
10162 \LetLtxMacro\LWR@xcolorrowHTMLcolor\LWR@save@xcolorrowHTMLcolor%
10163 % \@rowcol@ors%
10164 \LWR@getmynexttoken%
10165 }
```

`\LWR@HTMLhline` The definition of `\hline` depends on whether `tabls` has been loaded. If so, optional space below the line may be specified, but will be ignored.

```

10166 \AtBeginDocument{
10167
10168 \IfPackageLoadedTF{lwarp-tabls}
10169 {
10170 \newcommand*\LWR@HTMLhline}[1][{}]{%
10171 \ifbool{FormatWP}%
10172 {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
10173 {\defaddtocounter{LWR@hlines}{1}}}%
10174 \LWR@getmynexttoken}%
10175 }
10176 {
10177 \newcommand*\LWR@HTMLhline}{%
10178 \ifbool{FormatWP}%
10179 {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
10180 {\defaddtocounter{LWR@hlines}{1}}}%
10181 \LWR@getmynexttoken}%
10182 }
10183
10184 }% AtBeginDocument

```

`\LWR@HTMLcline` `{\langle columns \rangle}`

```

10185 \NewDocumentCommand{\LWR@HTMLcline}{m}%
10186 {\LWR@docmidrule{#1}\LWR@getmynexttoken}%

```

`\LWR@tabular@warpprintonly` `{\langle contents \rangle}`

Only process the contents if producing printed output. Modified inside a `tabular` to grab the next token.

```

10187 \newcommand{\LWR@tabular@warpprintonly}[1]{%
10188 \ifbool{warpingprint}{#1}{}%
10189 \LWR@getmynexttoken%
10190 }

```

`\LWR@nullifyNoAutoSpacing` For `babel-french`, turn off auto spacing at the start of the `tabular`, then nullify the autospacing commands inside the `tabular`, since they were not compatible with the `tabular` parsing code for each cell, which uses `xstring`.

```

10191 \AtBeginDocument{
10192 \ifundefined{NoAutoSpacing}%
10193 {% no babel-french
10194 \newcommand*\LWR@nullifyNoAutoSpacing}{%
10195 }% no babel-french
10196 {% yes babel-french
10197 \newcommand*\LWR@nullifyNoAutoSpacing}{%
10198 \NoAutoSpacing%
10199 \renewcommand*\NoAutoSpacing}{}%
10200 \renewcommand*\LWR@FBcancel}{}%
10201 }
10202 }% yes babel-french
10203 }% AtBeginDocument

```

Env `tabular` `<direction> [\langle vertposition \rangle] {\langle colspecs \rangle}`

The `<direction>` is from `plext` for Japanese documents, and is ignored.

```
10204 \StartDefiningTabulars
10205
10206 \NewDocumentCommand{\LWR@HTML@tabular}{d<> o m}
10207 {%
10208 \LWR@traceinfo{\LWR@HTML@tabular started}%
```

 **<table> inside <span>** In L<sup>A</sup>T<sub>E</sub>X, a `tabular` may be placed inside a `minipage`, but in HTML a `<table>` may not be inside a `<span>`. Since there may be several nested `<span>`s, with an unknown number of other objects between, it is hard to undo all these `<span>`s before the `<table>` then redo them after. The browser probably compensates for this situation, but formatting may be lost inside the `<table>` because several things are neutralized inside a `<span>`. Furthermore, in the HTML output, the entire `<table>` is placed on a single line of HTML code, since the line breaking commands are neutralized inside a `<span>`. Since this is such a sloppy situation, a warning is issued here instructing the user to please isolate the `<span>` to print-only.

```
10209 \LWR@spanwarnformat{tabular}%
10210 \addtocounter{\LWR@tabulardepth}{1}%
```

Not yet started a table row:

```
10211 \boolfalse{\LWR@startedrow}%
```

Not yet doing any rules:

```
10212 \defcounter{\LWR@hlines}{0}%
10213 \defcounter{\LWR@hdashedlines}{0}%
10214 \boolfalse{\LWR@doingtbrule}%
10215 \boolfalse{\LWR@doingcmidrule}%
```

For `babel-french`, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the `tabular` parsing code.

```
10216 \LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of `tabular` command. Unmute the `@` and `!` columns.

```
10217 \boolfalse{\LWR@exitingtabular}%
10218 \boolfalse{\LWR@tabularmutemods}%
```

Error if failed to use `\mrowcell` or `\mcolrowcell` when needed.

```
10219 \boolfalse{\LWR@usedmultirow}%
10220 \boolfalse{\LWR@foundmrowcell}%
```

In case of nesting:

```
10221 \renewcommand*{\LWR@multicoltext}{}%
10222 \booltrue{\LWR@intabularmetadata}%
```

New PDF page, unless in a `\multirow`:

```
10223 \ifbool{\LWR@in@multirow@par}%
10224 {\leavevmode\LWR@orignewline}%
10225 {\LWR@forcenewpage}%
```

In case of nesting, locally no longer in a `\multirow`:

```
10226 \boolfalse{LWR@in@multirow@par}%
```

Create the table tag:

```
10227 \LWR@htmlblocktag{table}%
```

Parse the table columns:

```
10228 \LWR@parsetablecols{#3}%
```

Table col spec is: `\LWR@tablecolspec` which is a string of `llccrr`, etc.

Do not place the table inside a paragraph:

```
10229 \LWR@stoppars%
```

Track column #:

```
10230 \defcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
10231 \global\boolfalse{LWR@tabularcelladded}%
```

Start looking for midrules:

```
10232 \LWR@clearmidrules%
```

`\` becomes a macro to end the table row:

```
10233 \LetLtxMacro{\}{\LWR@tabularendoffline}%
```

`\warpprintonly` inside a tabular must grab the next token.

```
10234 \LetLtxMacro\warpprintonly\LWR@tabular@warpprintonly%
```

The following adjust for `colortbl`.

```
10235 \LetLtxMacro\arrayrulecolor\arrayrulecolornexttoken%
10236 \LetLtxMacro\doublerulesepcolor\doublerulesepcolornexttoken%
10237 \def\LWR@columnHTMLcolor{}%
10238 \def\LWR@rowHTMLcolor{}%
10239 \def\LWR@cellHTMLcolor{}%
10240 \@rowcolors%
```

The vertical rules are set to the color active at the start of the tabular. `\arrayrulecolor` will then affect horizontal rules inside the tabular, but not the vertical rules.

```
10241 \ifdefvoid{\LWR@ruleHTMLcolor}%
10242 {\edef\LWR@vertruleHTMLcolor{black}}%
10243 {\edef\LWR@vertruleHTMLcolor{\LWR@origpound\LWR@ruleHTMLcolor}}%
```

Tracking the depth of cell color `<div>`:

```
10244 \defcounter{LWR@cellcolordepth}{0}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with `\LWR@getmynexttoken` to see if the next token might create a new data cell:

The optional parameter for `\hline` supports the `tabls` package.

```

10245 \LWR@traceinfo{\LWR@HTML@tabular: redefining macros}%
10246 \LetLtxMacro\noalign\LWR@tabularnoalign%
10247 \LetLtxMacro\hline\LWR@HTMLhline%
10248 \LetLtxMacro\cline\LWR@HTMLcline%

10249 \DeclareDocumentCommand{\hdashline}{o}{%
10250 \ifbool{FormatWP}%
10251 {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
10252 {\defaddtocounter{LWR@hdashedlines}{1}}%
10253 \LWR@getmynexttoken%
10254 }%

10255 \DeclareDocumentCommand{\cdashline}{m}{%
10256 \LWR@docdashline{##1}\LWR@getmynexttoken%
10257 }%

10258 \DeclareDocumentCommand{\firsthdashline}{o}{%
10259 \ifbool{FormatWP}%
10260 {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
10261 {\defaddtocounter{LWR@hdashedlines}{1}}%
10262 \LWR@getmynexttoken%
10263 }%

10264 \DeclareDocumentCommand{\lasthdashline}{o}{%
10265 \ifbool{FormatWP}%
10266 {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
10267 {\defaddtocounter{LWR@hdashedlines}{1}}%
10268 \LWR@getmynexttoken%
10269 }%

```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use `\LWR@getmynexttoken`.

```

10270 \renewcommand{\multicolumn}{\LWR@htmlmulticolumn}%
10271 \renewcommand*\mrowcell{%
10272 \LWR@maybenewtablerow%
10273 \LWR@tabularleftedge%
10274 \booltrue{LWR@skippingmrowcell}%
10275 \booltrue{LWR@foundmrowcell}%
10276 }%
10277 \renewcommand*\mcolrowcell{%
10278 \LWR@maybenewtablerow%
10279 \booltrue{LWR@skippingmcolrowcell}%
10280 \booltrue{LWR@foundmrowcell}%
10281 }%
10282 \LetLtxMacro\caption\LWR@longtabledatacaptiontag%

```

Reset for new processing:

```

10283 \boolfalse{LWR@tableparcel}%
10284 \boolfalse{LWR@skippingmrowcell}%

```

```

10285 \boolfalse{LWR@skippingmcolrowcell}%
10286 \boolfalse{LWR@skipatbang}%
10287 \boolfalse{LWR@emptyatbang}%

```

Set & for its special meaning inside the tabular:

```

10288 \StartDefiningTabulars%
10289 \protected\gdef&{\LWR@tabularampersand}%

```

Locally force any minipages to be fullwidth, until the end of the tabular:

```

10290 \booltrue{LWR@forceminipagefullwidth}%

```

Nest one level deeper of tabular paragraph handling:

```

10291 \addtocounter{LWR@tabularpardepth}{1}%

```

Look ahead for a possible table data cell:

```

10292 \LWR@traceinfo{LWR@HTML@tabular: about to LWR@getmynexttoken}%
10293 \LWR@getmynexttoken%
10294 }%

```

Ending the environment:

```

10295 \newcommand*{\LWR@HTML@endtabular}
10296 {%
10297 \LWR@traceinfo{LWR@HTML@endtabular}%

```

Unnest one level of tabular paragraph handling:

```

10298 \addtocounter{LWR@tabularpardepth}{-1}%
10299 \ifboolexpr{%
10300 test {%
10301 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}%
10302 {\value{LWR@tabletotalLaTeXcols}}
10303 } or %
10304 (%
10305 bool{LWR@intabularmetadata} and%
10306 not bool{LWR@tabularcelladded} and%
10307 test {%
10308 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}%
10309 {\value{LWR@tabletotalLaTeXcols}}%
10310 }%
10311)%
10312 }%
10313 {%
10314 \LWR@tabularfinishrow%
10315 }%
10316 {%
10317 \LWR@closetabledatacell%
10318 }%
10319 \LWR@htmlblocktag{/tr}%

```

xcolor row color support:

```

10320 \@rowc@lors%

```

```
10321 \LWR@htmlblocktag{/table}%
10322 \boolfalse{LWR@intabularmetadata}%
```

Unnest one level of tabular:

```
10323 \addtocounter{LWR@tabulardepth}{-1}%
```

Restore & to its usual meaning:

```
10324 \ifnumequal{\value{LWR@tabulardepth}}{0}{%
10325 \protected\gdef&{\LWR@origampmacro}%
10326 \StopDefiningTabulars%
10327 }{%}
```

Error if used `\multirow` or `\multicolumnrow` without using `\mrowcell` or `\mcolrowcell`.

```
10328 \ifbool{LWR@usedmultirow}{%
10329 \ifbool{LWR@foundmrowcell}%
10330 {\relax}%
10331 {%
10332 \PackageError{lwarp}%
10333 {%
10334 When using \protect\multirow, \protect\multicolumnrow, \MessageBreak
10335 or the bigdelim package, \MessageBreak
10336 place \protect\mrowcell\space or \protect\mcolrowcell\MessageBreak
10337 in empty cells which are to be skipped.\MessageBreak
10338 See the Lwarp package documentation:\MessageBreak
10339 "Special cases and limitations" -> "Tabular"
10340 }%
10341 {%
10342 See the Lwarp package documentation:\MessageBreak
10343 "Special cases and limitations" -> "Tabular".
10344 }%
10345 }%
10346 }{%}
```

```
10347 \LWR@traceinfo{LWR@HTML@endtabular finished}%
10348 }
10349
10350 \csletcs{LWR@HTML@endtabular*}{LWR@HTML@endtabular}
10351
10352 \StopDefiningTabulars
```

siunitx may redefine tabular, so set the following later:

```
10353 \AtBeginDocument{
10354 \LetLtxMacro\LWR@origendtabular\endtabular
10355 \csletcs{LWR@origendtabular*}{endtabular*}
10356 \LWR@formatted{@tabular}
10357 \LWR@formatted{endtabular}
10358 \LWR@formatted{endtabular*}
10359 }

10360 \end{warpHTML}
```

## 76 Cross-references

Sectioning commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

A new entry in `*_html.aux` is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{<section name>}{<filename>
 {<limagedepth>}{<limagenumber>}}
```

Table 16 shows the data structures related to cross-referencing.

**for HTML output:** 10361 \begin{warpHTML}

### 76.1 Setup

`\@currentlabelname` To remember the most recently defined section name, description, or caption, for `\nameref`.

```
10362 \def\@currentlabelname{\linkhomename}%
```

`\LWR@stripperperiod` `{<text>}` [`<.>`]

Removes a trailing period.

```
10363 \def\LWR@stripperperiod#1.\ltx@empty#2\@nil{#1}%
```

`\LWR@setlatestname` `{<object name>}`

Removes `\label`, strips any final period, and remembers the result.

```
10364 \newcommand*\LWR@setlatestname}[1]{%
```

Remove `\label` and other commands from the name, the strip any final period. See `getttitlestring`.

```
10365 \GetTitleStringExpand{#1}%
10366 \edef\@currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
10367 \edef\@currentlabelname{%
10368 \expandafter\LWR@stripperperiod\@currentlabelname%
10369 \ltx@empty.\ltx@empty\@nil%
10370 }%
10371 }
```

### 76.2 New lwarp labels.

A new entry in `*_html.aux` is used to remember section name, file, and lateximage depth and number for each label:

Table 16: Cross-referencing data structures

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <b>Original L<sup>A</sup>T<sub>E</sub>X:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | (print and HTML) |
| <p><b>\refstepcounter:</b> Steps the counter and sets \@currentlabel.</p> <p><b>\@currentlabel:</b> \p@&lt;ctr&gt;\the&lt;ctr&gt; Updated by \refstepcounter.</p> <p><b>\label:</b> Writes to the .aux file:<br/> <code>\newlabel{&lt;label&gt;}{\@currentlabel}{\thepage}}</code></p> <p><b>\newlabel:</b> When the .aux file is read, sets \r@&lt;label&gt;.</p> <p><b>\r@&lt;label&gt;:</b> Set to: <code>{\@currentlabel}{\thepage}</code></p> <p><b>\ref:</b> Returns the first part of \r@&lt;label&gt;.</p> <p><b>\pageref:</b> Returns the second part of \r@&lt;label&gt;.</p>                                                                                                                                                                                                                                                                                                                              |                  |
| <b>Added by lwarp:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | (HTML only)      |
| <p><b>\label:</b> Adds HTML tags (section 76.3), and another .aux entry (section 76.2). If memoir is used, its \@mem@old@label points to lwarp's version, and cleveref patches.</p> <p><b>\newlabel:</b> Unchanged. When the .aux file is read, sets \r@&lt;label&gt;@lwarp.</p> <p><b>\r@&lt;label&gt;@lwarp:</b> Set to <code>{\section_name}{file_name}{depth}{number}</code>:</p> <p><b>\LWR@nameref:</b> The section or object name for this label.</p> <p><b>\LWR@currentautosecpage:</b> The LWR@currentautosecpage for this label.</p> <p><b>\LWR@htmlfileref:</b> The filename or name for this label.</p> <p><b>\LWR@lateximagedepth:</b> The lateximagedepth for this label.</p> <p><b>\LWR@lateximagenumber:</b> The lateximagenumber for this label.</p> <p><b>\nameref:</b> Emulated from hyperref for lwarp. See section 76.4.</p> <p><b>\ref and \nameref:</b> Adds HTML tags. See section 76.4.</p> |                  |
| <b>Added by amsmath:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | (print and HTML) |
| <p><b>\label:</b> Execution is delayed until the math environment is completed.</p> <p><b>\ltx@label:</b> L<sup>A</sup>T<sub>E</sub>X \label, (HTML: patched by lwarp,) later patched by cleveref.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                  |
| <b>Added by cleveref:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (print and HTML) |
| <p><b>\refstepcounter:</b> Added: sets \cref@currentlabel.</p> <p><b>\cref@currentlabel:</b> (&lt;type&gt;=&lt;ctr&gt; unless an alias is used):<br/> <code>[&lt;type&gt;][\arabic{&lt;ctr&gt;}][&lt;parent ctrs&gt;]{\p@&lt;ctr&gt;\the&lt;ctr&gt;}</code> Also see section 60.4 for use with footnotes.</p> <p><b>\label:</b> Writes to the .aux file:<br/> <code>\newlabel{&lt;label&gt;@cref}{\cref@currentlabel}{\thepage}}</code></p> <p><b>\newlabel:</b> Unchanged. When the .aux file is read, sets \r@&lt;label&gt;@cref.</p> <p><b>\r@&lt;label&gt;@cref:</b> Set to: <code>{\cref@currentlabel}{\thepage}</code></p> <p><b>Utility functions:</b> See \cref@getlabel, \cref@gettype, \cref@getcounter, \cref@getprefix.</p> <p><b>Cross-referencing names:</b> \crefname and \Crefname assign human-readable names for references to this counter type.</p>                                              |                  |
| <b>Additionally patched by lwarp:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | (HTML only)      |
| <p><b>\cref, etc.:</b> Modified for lwarp. See section 202.</p> <p><b>\label inside math:</b> See section 83.7.1.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                  |
| <b>Footnotes:</b> See \noteentry in section 60.4.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                  |

```
\newlabel{<labelname>@lwarp}{<section name>}{<filename>}
 {<limagedepth>}{<limagenumber>}}
```

See:

<http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference>

`\LWR@setref` {<args list>} {<selector>} {<label>}

`\@setref` without the `\null` (`\hbox`), and without the warning messages. Each caused problems with `lwarp` references. The regular reference will cause the warning.

```
10372 \def\LWR@setref#1#2#3{%
10373 \ifx#1\relax%
10374 ??%
10375 \else%
10376 \expandafter#2#1%
10377 \fi}
```

`\LWR@nameref` {<label>} Returns the section name for this label:

```
10378 \newcommand*\LWR@nameref}[1]{%
10379 \begingroup%
10380 \LWR@nullifyfootnotes%
10381 \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@firstoffive{#1}%
10382 \endgroup%
10383 }
```

`\LWR@currentautosecpageref` {<label>} Returns the `LWR@currentautosecpage` for this label:

```
10384 \newcommand*\LWR@currentautosecpageref}[1]{%
10385 \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@secondoffive{#1}%
10386 }
```

`\LWR@htmlfileref` {<label>} Returns the file number or name for this label:

```
10387 \newcommand*\LWR@htmlfileref}[1]{%
10388 \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@thirdoffive{#1}%
10389 }
```

`\LWR@lateximagedepthref` {<label>} Returns the `lateximagedepth` for this label:

```
10390 \newcommand*\LWR@lateximagedepthref}[1]{%
10391 \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@fourthoffive{#1}%
10392 }
```

`\LWR@lateximagenumberref` {<label>} Returns the `lateximagenumber` for this label:

```
10393 \newcommand*\LWR@lateximagenumberref}[1]{%
10394 \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@fifthoffive{#1}%
10395 }
```

`\LWR@write@lwarplabel`  $\{\langle label \rangle\}$  Sanitize the name and then creates the label:

```

10396 \newcommand*{\LWR@write@lwarplabel}[1]{%
10397 \LWR@traceinfo{\LWR@write@lwarplabel !#1!}%
10398 \LWR@setlatestname{\@currentlabelname}%
10399 \@bsphack%
10400 \protected@write\@auxout{%
10401 {%
10402 \string\newlabel{#1@lwarp}{%
10403 {\@currentlabelname}%
10404 {\theLWR@currentautosecpage}%
10405 {%
10406 \ifbool{FileSectionNames}%
10407 {\LWR@thisfilename}%
10408 {\arabic{LWR@htmlfilenumber}}}%
10409 }%
10410 {\arabic{LWR@lateximagedepth}}}%
10411 {\arabic{LWR@lateximagenumber}}}%
10412 }%
10413 }%
10414 \@esphack%
10415 }

```

### 76.3 Labels

`\LWR@label@subcreatetag` Creates the tag from `\LWR@sanitized`.

```

10416 \newcommand*{\LWR@label@subcreatetag}{%
10417 \LWR@htmltag{a \LWR@print@mbox{id=\textquotedbl\LWR@sanitized\textquotedbl}}%
10418 \LWR@htmltag{/a}%
10419 }

```

`\LWR@label@inmathcomment`

```

10420 \newcommand*{\LWR@label@inmathcomment}{%
10421 \ifboolexpr{bool{mathjax} or (bool{FormatWP} and bool{WPMarkMath}) }%
10422 {%

```

The combined L<sup>A</sup>T<sub>E</sub>X & HTML label is printed in a `\mbox` field:

```

10423 \mbox{%

```

Shift the label over to the right side of the environment to avoid over-printing the math:

```

10424 \ifdef{\totwidth@}{\ifbool{LWR@amsmultline}{\hspace*{\totwidth@}}}{}%

```

Temporarily end the HTML comment, insert the L<sup>A</sup>T<sub>E</sub>X & HTML label, then resume the HTML comment. `\@firstofone` is required to remove extra braces introduced by the `amsmath` package.)

```

10425 \LWR@htmlclosecomment%
10426 \LWR@label@subcreatetag%
10427 \LWR@htmlopencomment%
10428 }% mbox
10429 }% mathjax

```

```

10430 {%
10431 \LWR@label@subcreatetag%
10432 }%
10433 }

```

`\LWR@label@createtag`  $\{\langle label \rangle\}$  Creates an HTML id tag.

Used by `\LWR@new@label` and `\hyperdef`.

`\detokenize` is used to allow underscores in the labels.

```

10434 \newcommand*{\LWR@label@createtag}[1]{%
10435 \LWR@traceinfo{\LWR@label@createtag !#1!}%

```

Create an HTML id tag unless are inside a `lateximage`, since it would appear in the image:

```

10436 \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}%
10437 }%
10438 {% not lateximage

```

If not doing a `lateximage`, create an HTML ID tag.

```

10439 \LWR@sanitize{#1}%
10440 \ifbool{\LWR@insidemathcomment}%
10441 {% inside HTML math comment
10442 \LWR@label@inmathcomment%
10443 }% inside HTML math comment
10444 {% not inside HTML math comment
10445 \ifbool{\LWR@doingstartpars}%
10446 {% pars allowed
10447 \ifbool{\LWR@doingapar}%
10448 {% par started
10449 \LWR@label@subcreatetag%
10450 }% par started
10451 {% par not started
10452 \LWR@stoppars%
10453 \LWR@label@subcreatetag%
10454 \LWR@startpars%
10455 }% par not started
10456 }% pars allowed
10457 {% pars not allowed
10458 \LWR@label@subcreatetag%
10459 }% pars not allowed
10460 }% not inside HTML math comment
10461 }% not lateximage
10462 }

```

`\LWR@new@label`  $\{\langle label \rangle\}$

`\label` during HTML output when not in `svg` math mode, removing extra spaces around the label, as done by a regular  $\text{\LaTeX}$  `\label`.

The is also used during a `lateximage`, including `svg` math, since the special label handling is required, but `\LWR@label@createtag` does not generate HTML tags inside a `lateximage`.

If `memoir` is used, it's `\@mem@old@label` is pointed here.

`cleveref` later encases this to add its own cross-referencing, and also patches `memoir`.

```
10463 \newcommand*{\LWR@new@label}[1]{%
10464 \LWR@traceinfo{LWR@new@label: starting}%
10465 \LWR@traceinfo{LWR@new@label: !#1!}%
10466 % \@bsphack%
```

Create a traditional L<sup>A</sup>T<sub>E</sub>X label, as modified by `cleveref`:

```
10467 \LWR@orig@label{#1}%
```

Create a special label which holds the section number, section name, `LWR@htmlfilenumber`, `LWR@lateximagedepth`, and `LWR@lateximagenumber`:

```
10468 \LWR@traceinfo{%
10469 LWR@new@label: filesectionnames is %
10470 \ifbool{FileSectionNames}{true}{false}%
10471 }%
10472 \LWR@traceinfo{%
10473 LWR@new@label: LWR@thisfilename is !\LWR@thisfilename!%
10474 }%
10475 \LWR@traceinfo{%
10476 LWR@new@label: LWR@htmlfilenumber is \arabic{LWR@htmlfilenumber}%
10477 }%
10478 \LWR@write@lwarplabel{#1}%
10479 \LWR@label@createtag{#1}%
10480 % \@esphack%
10481 \LWR@traceinfo{LWR@new@label: done}%
10482 }
```

## 76.4 References

`\LWR@addlinktitle`

```
10483 \newcommand*{\LWR@addlinktitle}{%
10484 \ifdefvoid{\LWR@ThisAltText}{ }{ % space
10485 title=\textquotedbl\LWR@ThisAltText\textquotedbl\ % space
10486 \gdef\LWR@ThisAltText{}%
10487 }%
10488 }
```

`\LWR@startref` `{\label}` (Common code for `\ref` and `\nameref`.)

Open an HTML tag reference to a filename, # character, and a label.

```
10489 \newcommand*{\LWR@startref}[1]
10490 {%
10491 \LWR@sanitize{#1}%
10492 \LWR@traceinfo{LWR@startref A: !#1!}%
```

Create the filename part of the link:

```
10493 \LWR@htmltag{a href=\textquotedbl%
10494 \LWR@traceinfo{LWR@startref B}%
```

```

10495 \LWR@print@mbbox{\LWR@htmlrefsectionfilename{#1}}%
10496 \LWR@traceinfo{\LWR@startref C}%
10497 \LWR@origpound%

```

Create the destination id:

See if `LWR@lateximagedepth` is unknown:

```

10498 \LWR@traceinfo{\LWR@startref D: !#1!}%
10499 \ifcsundef{r@#1@lwarp}%

```

“??” if `LWR@lateximagedepth` is unknown, so create a link with an unknown destination:

```

10500 {%
10501 \LWR@traceinfo{\LWR@startref D0: ??}%
10502 ??%
10503 }%

```

If `LWR@lateximagedepth` is known. Use a `lateximage` if the depth is greater than zero, or a regular link otherwise:

```

10504 {%
10505 \ifthenelse{\cnttest{\LWR@lateximagedepthref{#1}}{>}{0}}%
10506 {%
10507 lateximage-\BaseJobname-\LWR@lateximagenumberref{#1}%
10508 }%
10509 {%
10510 \LWR@traceinfo{\LWR@startref D3}%

```

`\detokenize` is used to allow underscores in the labels:

```

10511 \LWR@print@mbbox{\LWR@sanitized}%
10512 }%
10513 }%
10514 \LWR@traceinfo{\LWR@startref E}%

```

Closing quote:

```

10515 \textquotedbl%

```

Maybe add a title:

```

10516 \LWR@addlinktitle%
10517 }%
10518 \LWR@traceinfo{\LWR@startref F}%
10519 }

```

`\LWR@subnewref`  $\{\langle label \rangle\} \{\langle label \text{ or } sub@label \rangle\}$

Factored for the `subfig` package. Uses the original label for the hyper-reference, but prints its own text, such as “1 (b)”.

```

10520 \NewDocumentCommand{\LWR@subnewref}{m m}{%
10521 \LWR@traceinfo{\LWR@subnewref #1 #2}%
10522 \LWR@startref{#1}%

```

```

10523 \LWR@print@ref{#2}%
10524 \LWR@htmltag{/a}%
10525 }

```

`\ref * {<label>}`

`\ref` is redefined to `\LWR@HTML@ref`, except inside the text part of a `\hyperref`, where it is redefined to `\LWR@ref@ignorestar`.

`\LWR@HTML@ref * {<label>}` Create an internal document reference link, or without a link if starred per `hyperref`.

`hyperref` defines a starred version. Since `hyperref` is only emulated, the starred version is defined here for print mode, in case `\ref` is used inside `svg math`:

```
10526 \LWR@absorbstar{ref}%
```

The HTML version:

```

10527 \NewDocumentCommand{\LWR@HTML@ref}{s m}{%
10528 \LWR@traceinfo{\LWR@HTML@ref !#2!}%
10529 \IfBooleanTF{#1}%
10530 {\LWR@print@ref{#2}}%
10531 {\LWR@subnewref{#2}{#2}}%
10532 }
10533
10534 \LWR@formatted{ref}

```

`\LWR@refwithsection * {<label>}`

Creates a reference, using the section number as the text. Used for back references.

```

10535 \NewDocumentCommand{\LWR@refwithsection}{s m}{%
10536 \LWR@traceinfo{\LWR@refwithsection !#2!}%

```

If starred, just use the text without a hyperlink:

```

10537 \IfBooleanTF{#1}%
10538 {\LWR@print@ref{\BaseJobname-autopage-\LWR@currentautosecpageref{#2}}}%
10539 {%

```

Open the reference:

```
10540 \LWR@startref{#2}%
```

Add the text of the link.

Check for and handle an undefined reference:

```

10541 \edef\@tempa{\LWR@currentautosecpageref{#2}}%
10542 \ifdefstring{\@tempa}{??}%
10543 {??}%

```

For a defined reference:

```
10544 {%
```

Set `\@tempa` to `\r@<label>`, which is `{section number}{page number}`.

```
10545 \edef\@tempa{%
10546 \csname
10547 r@\BaseJobname-autopage-\LWR@currentautosecpageref{#2}%
10548 \endcsname%
10549 }%
```

Check the section number alone:

```
10550 \edef\@tempa{\expandafter\@firstoftwo\@tempa}%
```

If the reference has no section number print an asterisk:

```
10551 \expandafter\ifblank\expandafter{\@tempa}%
10552 {*}
```

If there is a section number, print it:

```
10553 {%
10554 \LWR@print@ref{%
10555 \BaseJobname-autopage-\LWR@currentautosecpageref{#2}%
10556 }%
10557 }%
10558 }%
```

Close the reference:

```
10559 \LWR@htmltag{/a}%
10560 }%
10561 }
```

For MATHJAX:

```
10562 \CustomizeMathJax{\let\LWRref\ref}
10563 \CustomizeMathJax{\renewcommand{\ref}{\ifstar\LWRref\LWRref}}
```

`\pagerefPageFor` Text for page references.

```
10564 \newcommand*{\pagerefPageFor}{see }
```

`\pageref * {<label>}` Create an internal document reference, or just the unlinked number if starred, per `hyperref`.

```
10565 \NewDocumentCommand{\LWR@new@pageref}{s m}{%
10566 \IfBooleanTF{#1}%
10567 {\pagerefPageFor\LWR@print@ref{#2}}%
10568 {\cpageref{#2}}%
10569 }
```

`\nameref {<label>}`

```
10570 \newrobustcmd*{\nameref}[1]{%
10571 \LWR@traceinfo{nameref}%
```

```

10572 \LWR@startref{#1}%
10573 \LWR@traceinfo{nameref B}%
10574 \LWR@nameref{#1}%
10575 \LWR@traceinfo{nameref C}%
10576 \LWR@htmltag{/a}%
10577 \LWR@traceinfo{nameref: done}%
10578 }

```

`\Nameref`  $\{\langle label \rangle\}$  In print, adds the page number. In HTML, does not.

```
10579 \LetLtxMacro\Nameref\nameref
```

## 76.5 Hyper-references



Note that the code currently only sanitizes the underscore character. Additional characters should be rendered inert as well. See the `hyperref.sty` definition of `\gdef\hyper@normalise` for an example.

Pkg hyperref



Do not tell other packages that `hyperref` is emulated. Some packages patch various commands if `hyperref` is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

```

10580 % DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:
10581 % \EmulatesPackage{hyperref}[2015/08/01]% Disabled. Do not do this.

```

Emulates `hyperref`:

`@currentHref` Added to support `backref`.

```

10582 \AtBeginDocument{
10583 \def\@currentHref{\BaseJobname-autopage-\theLWR@previousautopageLabel}%
10584 }

```

`\LWR@linkcatcodes` Sets catcodes before processing macros which have hyperlinks as arguments.

```

10585 \newcommand*\LWR@linkcatcodes}{%
10586 \catcode'\#=12%
10587 \catcode'\%=12%
10588 \catcode'\&=12%
10589 \catcode'\~=12%
10590 \catcode'_ =12%

```

For `babel-french`:

```

10591 \LWR@hook@processingtags%
10592 }

```

`\LWR@linkmediacatcodes` Sets catcodes before processing macros which have hyperlinks as arguments. Modified for multimedia links.

```

10593 \newcommand*\LWR@linkmediacatcodes}{%
10594 \catcode'\#=12%

```

```

10595 \catcode'\%=12%
10596 % \catcode'\&=12% left alone for splitting flash variables
10597 \catcode'\~=12%
10598 \catcode'_ =12%

```

For babel-french:

```

10599 \LWR@hook@processingtags%
10600 }

```

`\LWR@subhyperref` {<*URL*>}

Starts a link for `\LWR@hrefb`. A group must have been opened first, with nullified catcodes. The text name is printed afterwards, after the group is closed and catcodes restored.

```

10601 \NewDocumentCommand{\LWR@subhyperref}{m}{%
10602 \LWR@traceinfo{\LWR@subhyperref !#1!}%
10603 \LWR@sanitize{#1}%
10604 \LWR@htmltag{%
10605 a href=\textquotedbl\LWR@sanitized\textquotedbl\ % space
10606 \LWR@addlinktitle % space
10607 target=\textquotedbl_{ }blank\textquotedbl\ % space
10608 }%
10609 }

```

`\LWR@subhyperreftext` {<*text*>}

Finishes the hyperref for `\LWR@hrefb`. Catcodes must have been restored already. To be used after `\LWR@subhyperref`, and after its group has been closed.

```

10610 \newcommand{\LWR@subhyperreftext}[1]{%
10611 #1%
10612 \LWR@htmltag{/a}%
10613 \LWR@ensuredoingapar%
10614 }

```

`\LWR@subhyperrefclass` {<*URL*>}{<*text*>}{<*htmlclass*>}

```

10615 \NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
10616 \LWR@htmltag{%
10617 a % space
10618 href=\textquotedbl\begin\group\@sanitize#1\end\group\textquotedbl\ % space
10619 class=\textquotedbl#3\textquotedbl\ % space
10620 \LWR@addlinktitle % space
10621 }\LWR@orignewline%
10622 #2%
10623 \LWR@htmltag{/a}%
10624 \LWR@ensuredoingapar%
10625 }

```

`\LWR@href` [*options*] {<*URL*>}{<*text*>}

Create a link with accompanying text:

```

10626 \DeclareDocumentCommand{\LWR@hrefb}{O{} m}{%

```

```

10627 \LWR@ensuredoingapar%
10628 \LWR@subhyperref{#2}%
10629 \endgroup% restore catcodes
10630 \LWR@subhyperref{#2}%
10631 }
10632
10633 \newrobustcmd*{\LWR@href}{%
10634 \begingroup%
10635 \LWR@linkcatcodes%
10636 \LWR@hrefb%
10637 }

```

`\LWR@nolinkurl`  $\{\langle URL \rangle\}$

Print the name of the link without creating the link:

```

10638 \newcommand*{\LWR@nolinkurlb}[1]{%
10639 \LWR@ensuredoingapar%
10640 \def\LWR@templink{#1}%
10641 \@onelevel@sanitize\LWR@templink%
10642 \LWR@templink%
10643 \endgroup%
10644 }
10645
10646 \newrobustcmd*{\LWR@nolinkurl}{%
10647 \begingroup%
10648 \LWR@linkcatcodes%
10649 \LWR@nolinkurlb%
10650 }

```

`\LWR@url`  $\{\langle URL \rangle\}$

Create a link whose text name is the address of the link.

The `url` package may redefine `\url`, so it is `\let` to `\LWR@url` here and also redefined by `lwarp-url`.

```

10651 \DeclareDocumentCommand{\LWR@urlb}{m}{%
10652 \LWR@ensuredoingapar%
10653 \def\LWR@templink{#1}%
10654 \@onelevel@sanitize\LWR@templink%
10655 \LWR@href{\LWR@templink}{\LWR@templink}%
10656 \endgroup%
10657 }
10658
10659 \newrobustcmd*{\LWR@url}{%
10660 \begingroup%
10661 \LWR@linkcatcodes%
10662 \LWR@urlb%
10663 }

```

`\LWR@subinlineimage`  $\{\langle 1: \langle \text{alt} \rangle \text{ tag} \rangle\} \{\langle 2: \text{class} \rangle\} \{\langle 3: \text{filename} \rangle\} \{\langle 4: \text{extension} \rangle\} \{\langle 5: \text{css style} \rangle\} \{\langle 6: \text{aria role} \rangle\}$

Factored from `lateximage`.

```

10664 \newcommand*{\LWR@subinlineimage}[6]{%
10665 \ifblank{#6}%

```

```
10666 {\renewcommand*{\LWR@tempone}{}}%
10667 {\renewcommand*{\LWR@tempone}{role="#6"\LWR@indentHTML}}%
10668 \ifblank{#1}%
10669 {%
10670 \LWR@htmltag{img \LWR@indentHTML
10671 src=\textquotedbl#3.#4\textquotedbl \LWR@indentHTML
10672 alt=\textquotedbl#3\textquotedbl \LWR@indentHTML
10673 \LWR@tempone
10674 style=\textquotedbl#5\textquotedbl \LWR@indentHTML
10675 class=\textquotedbl#2\textquotedbl \LWR@orignewline
10676 }%
10677 }%
10678 {%
10679 \LWR@htmltag{img \LWR@indentHTML
10680 src=\textquotedbl#3.#4\textquotedbl \LWR@indentHTML
10681 alt=\textquotedbl#1\textquotedbl \LWR@indentHTML
10682 \LWR@tempone
10683 style=\textquotedbl#5\textquotedbl \LWR@indentHTML
10684 class=\textquotedbl#2\textquotedbl \LWR@orignewline
10685 }%
10686 }%
10687 }

10688 \end{warpHTML}
```

Table 17: Float data structures

---

For each `<type>` of float (figure, table, etc.) there exists the following:

- counter `<type>`:** A counter called `<type>`, such as figure, table.
  - `\<type>name`:** Name. `\figurename` prints “Figure”, etc.
  - `\ext@<type>`:** File extension. `\ext@figure` prints “lof”, etc.
  - `\fps@<type>`:** Placement.
  - `\the<type>`:** Number. `\thetable` prints the number of the table, etc.
  - `\p@<type>`:** Parent’s number. Prints the number of the [within] figure, etc.
  - `\fnum@<type>`:** Prints the figure number for the caption.  
`\<type>name \the<type>`, “Figure 123”.
  - `\<type>`:** Starts the float environment. `\figure` or `\begin{figure}`
  - `\end<type>`:** Ends the float environment. `\endfigure` or `\end{figure}`
  - `\tf@<ext>`:** The L<sup>A</sup>T<sub>E</sub>X file identifier for the output file.
  - `LWR@have<type>`:** A boolean remembering whether a `\listof` was requested for a float of this type.
  - File with extension `lo<f, t, a-z>`:** An output file containing the commands to build the `\listof<type>` “table-of-contents” structure.
  - Cross-referencing names:** For `cleveref`’s `\cref` and related, `\crefname` and `\Crefname` assign human-readable names for references to this float type.
- 

## 77 Floats

Floats are supported, although partially through emulation.

Table 17 shows the data structure associated with each `<type>` of float.

### 77.1 Float environment

**for HTML output:** 10689 `\begin{warpHTML}`

`\LWR@floatbegin` `{\<type>}` `[\<placement>]` Begins a `\newfloat` environment.

```
10690 \NewDocumentCommand{\LWR@floatbegin}{m o}{%
```

Warn if starting a float inside a `<span>`:

```
10691 \LWR@spanwarninvalid{float}%
```

```
10692 \ifbool{FormatWP}{\newline}{}%
```

```
10693 \LWR@stoppars%
```

There is a new float, so increment the unique float counter:

```
10694 \addtocounter{LWR@thisautoid}{1}%
10695 \booltrue{LWR@freezethisautoid}%

10696 \begingroup%
```

Settings while inside the environment:

```
10697 \LWR@print@raggedright%
```

Open an HTML figure tag. The figure is assigned a class equal to its type, and another class according to the float package style, if used. Note that `\csuse` returns an empty string if `\LWR@floatstyle@<type>` is not defined.

```
10698 \LWR@htmltag{%
10699 figure id=\textquotedbl%
10700 \LWR@print@embox{autoid-\arabic{LWR@thisautoid}}%
10701 \textquotedbl\ % space
10702 class=\textquotedbl#1 \@nameuse{LWR@floatstyle@#1}\textquotedbl%
10703 }%
10704 \ifbool{FormatWP}{%
10705 \LWR@originewline%
10706 \LWR@BlockClassWP{}}{wp#1}%
10707 }{}}%
```

Update the caption type:

```
10708 \renewcommand*{\@capttype}{#1}%
```

Mark the float for a word processor conversion:

```
10709 \LWR@startpars%
10710 \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%
10711
10712 === begin #1 ===
10713
10714 }{}}%
```

After each `\LWR@floatbegin`, look for `\centering`, etc next, using `\LWR@floatalignment`.

```
10715 }
```

For koma-script. The following does not work for tables.

```
10716 \AtBeginDocument{
10717
10718 \IfPackageLoadedTF{tocbasic}{
10719
10720 \appto\figure@atbegin{%
10721 \LWR@futurenonspacel\@mynexttoken\LWR@floatalignment%
10722 }
10723
10724 }{}}% tocbasic
10725
10726 }% AtBeginDocument
```

`\@xfloat` Support packages which create floats directly.  
`\@xdbfloat` Look for `\centering`, etc using `\LWR@floatalignment`.

```
10727 \AtBeginDocument{
10728 \def\@xfloat #1[#2]{%
10729 \LWR@floatbegin{#1}[#2]
10730 \LWR@futurenonspacel\@LWR@mynexttoken\LWR@floatalignment%
10731 }
10732 \def\@xdbfloat #1[#2]{%
10733 \LWR@floatbegin{#1}[#2]
10734 \LWR@futurenonspacel\@LWR@mynexttoken\LWR@floatalignment%
10735 }
10736 }
```

`\LWR@floatend` Ends a `\newfloat` environment.

```
10737 \newcommand*{\LWR@floatend}{%
```

If saw a `\centering`, finish the center environment:

```
10738 \LWR@endfloatalignment%
```

Mark the float end for a word processor conversion:

```
10739 \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%
10740 === end ===
10741 }{%
10742 }{%
10743 }{%
10744 \LWR@stoppars%
```

Close an HTML figure tag:

```
10745 \ifbool{FormatWP}{\endLWR@BlockClassWP}{}%
10746 \LWR@htmlElementend{figure}%
10747 \endgroup%
10748 \boolfalse{LWR@freezethisautoid}%
10749 \LWR@startpars%
10750 \ifbool{FormatWP}{\newline}{}%
10751 }
```

`\end@float` Support packages which create floats directly.  
`\end@dbfloat`

```
10752 \AtBeginDocument{
10753 \let\end@float\LWR@floatend
10754 \let\end@dbfloat\LWR@floatend
10755 }
```

## 77.2 Float tracking

Ctrl `LWR@thisautoid`

A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
10756 \newcounter{LWR@thisautoid}
```

- Ctrl LWR@thisautoidWP      A sequential counter for all word processor conversion <div>s. This is used to convince LIBREOFFICE to form a frame around this element.
- ```
10757 \newcounter{LWR@thisautoidWP}
```
- Bool LWR@freezethisautoid Prevents multiple increments of \LWR@thisautoid inside a float.
- ```
10758 \newbool{LWR@freezethisautoid}
10759 \boolfalse{LWR@freezethisautoid}
```
- \LWR@forcenewautoidanchor      Adds a new <autoid> anchor.
- ```
10760 \newcommand*{\LWR@forcenewautoidanchor}{%
10761     \addtocounter{LWR@thisautoid}{1}%
10762     \ifbool{LWR@doingapar}%
10763     {%
10764         \LWR@htmltag{a id=\textquotedbl%
10765             \LWR@print@box{autoid-\arabic{LWR@thisautoid}}%
10766             \textquotedbl\ }% space
10767         \LWR@htmltag{/a }%
10768     }%
10769     {%
10770         \LWR@stoppars%
10771         \LWR@htmltag{a id=\textquotedbl%
10772             \LWR@print@box{autoid-\arabic{LWR@thisautoid}}%
10773             \textquotedbl\ }% space
10774         \LWR@htmltag{/a }%
10775         \LWR@startpars%
10776     }%
10777 }
```
- \LWR@newautoidanchor Sometimes adds a new <autoid> anchor.
- ```
10778 \newcommand*{\LWR@newautoidanchor}{%
10779 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
10780 }%
10781 {\ifbool{LWR@freezethisautoid}}{\LWR@forcenewautoidanchor}}%
10782 }
```
- \@capttype      Remembers which float type is in use.
- ```
10783 \newcommand*{\@capttype}{}
```
- \LWR@floatalignmentname Set to center, flushleft, or flushright if saw \centering, \raggedright, or \raggedleft.
- ```
10784 \newcommand*{\LWR@floatalignmentname}{}
```
- \LWR@floatalignment      If sees a \centering, \raggedleft, or \raggedright, creates a center, flushright, or flushleft environment.
- ```
10785 \newcommand*{\LWR@floatalignment}{%
10786     \ifdefstrequal{\LWR@mynexttoken}{\centering}{%
10787         \center%
10788         \renewcommand*{\LWR@floatalignmentname}{center}%
10789     }{}
```

```

10790 \ifdefstrequal{\LWR@mynexttoken}{\raggedright}{%
10791     \flushleft%
10792     \renewcommand*\LWR@floatalignmentname}{flushleft}%
10793 }{%
10794 \ifdefstrequal{\LWR@mynexttoken}{\raggedleft}{%
10795     \flushright%
10796     \renewcommand*\LWR@floatalignmentname}{flushright}%
10797 }{%
10798 }

```

`\LWR@endfloatalignment` Closes an environment from `\LWR@floatalignment`.

```

10799 \newcommand*\LWR@endfloatalignment{%
10800     \ifdefvoid{\LWR@floatalignmentname}%
10801     {}%
10802     {\@nameuse{end\LWR@floatalignmentname}}%
10803     \renewcommand*\LWR@floatalignmentname}{}%
10804 }

```

77.3 Caption inside a float environment

`\CaptionSeparator` How to separate the float number and the caption text, if not defined by the user. In most cases, `caption`'s settings are used instead.

```

10805 \AtBeginDocument{\providecommand*\CaptionSeparator}{:~}}

```

`\@caption` $\langle posn \rangle$ [$\langle name \rangle$] [$\langle long name \rangle$]

`\@makecaption` [$\langle name and num \rangle$] [$\langle text \rangle$]

Prints the float type and number, the caption separator, and the caption text.

`\@caption` is provided here in case `caption` is not loaded, and is based on the `nameref` package.

```

10806 \AtBeginDocument{
10807     \IfPackageLoadedTF{caption}{}{
10808         \let\LWR@orig@caption\@caption%
10809         \long\def\@caption#1[#2]{%

```

Warn if using a caption inside a ``:

```

10810         \LWR@spanwarnformat{caption}%

10811         \LWR@setlatestname{#2}%
10812         \LWR@orig@caption{#1}[#2]% also takes third argument
10813     }%
10814
10815     \renewcommand{\@makecaption}[2]{%
10816         \LWR@traceinfo{\@makecaption}%
10817         \caption@begin{\@capttype}%
10818         \LWR@isolate{#1}%
10819         \edef\LWR@tempone{#1}%
10820         \ifdefvoid{\LWR@tempone}{\CaptionSeparator}%
10821         \LWR@isolate{#2}%

```

```

10822         \caption@end%
10823         \LWR@traceinfo{@makecaption: done}%
10824     }%
10825 }
10826 }

```

77.4 Caption and LOF linking and tracking

When a new HTML file is marked in the L^AT_EX PDF file, or at the start of a new section, the L^AT_EX PDF page number at that point is stored in LWR@currentautosecfloatpage, (and the associated filename is remembered by the special L^AT_EX labels). This page number is used to generate an autopage HTML <id> in the HTML output at the start of the new HTML file or section. Meanwhile, there is a float counter used to generate an HTML autoid <id> at the start of the float itself in the HTML file. The autopage and autoid values to use for each float are written to the .lof, etc. files just before each float's entry. These values are used by \l@figure, etc. to create the HTML links in the List of Figures, etc.

Ctrl LWR@nextautoid Tracks autoid for floats. Tracks autopage for floats.

Ctrl LWR@nextautopage These are updated per float as the .lof, .lot file is read.

```

10827 \newcounter{LWR@nextautoid}
10828 \newcounter{LWR@nextautopage}

```

```
\LWRsetnextfloat {<autopage>} {<float autoid>}
```

File *_html.lof This is written to the *_html.lof or *_html.lot file just before each float's usual entry. The autopage and the float's autoid are remembered for \l@figure to use when creating the HTML links.

File *_html.lot

```

10829 \newcommand*\LWRsetnextfloat}[2]{%
10830     \setcounter{LWR@nextautopage}{#1}%
10831     \setcounter{LWR@nextautoid}{#2}%
10832 }

```

Env LWR@figcaption An HTML <figcaption> is not allowed in places where L^AT_EX does allow a figure caption, such as inside a longtable where the tabular has already started, or inside a center environment. Therefore, a <div> of class figurecaption is used instead.

```

10833 \newenvironment*LWR@figcaption}
10834     {%
10835         \ifbool{FormatWP}{%
10836             \BlockClass[font-style:italic]{figurecaption}%
10837         }{%
10838             \BlockClass{figurecaption}%
10839         }%

```

Inside the caption, temporarily prevent underfull \hbox warnings, such as when the caption contains a math SVG image.

```

10840         \hbadness=10000\relax%
10841     }%
10842     {\endBlockClass}

```

`\LWR@HTML@caption@begin` $\{\langle type \rangle\}$

Low-level code to create HTML tags for captions.

The print versions are from the `caption` package, if loaded.

```
10843 \newcommand*{\LWR@HTML@caption@begin}[1]
10844 {%
10845   \LWR@traceinfo{\LWR@HTML@caption@begin}%
```

Keep `par` and `minipage` changes local:

```
10846   \begingroup%
```

No need for a `minipage` or `\parbox` inside the caption:

```
10847   \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{\}{}%
10848   \RenewDocumentCommand{\parbox}{O{t} O{} O{t} m +m}{##5}%
```

Enclose the original caption code inside an HTML tag:

```
10849   \LWR@figcaption%
10850   \LWR@traceinfo{\LWR@HTML@caption@begin: about to LWR@origcaption@begin}%
10851   \LWR@print@caption@begin{#1}%
10852   \LWR@traceinfo{\LWR@HTML@caption@begin: done}%
10853 }
```

`\LWR@HTML@caption@end` Low-level patches to create HTML tags for captions.

```
10854 \newcommand*{\LWR@HTML@caption@end}
10855 {%
10856   \LWR@traceinfo{\LWR@HTML@caption@end}%
10857   \LWR@print@caption@end%
```

Closing tag:

```
10858   \endLWR@figcaption%
10859   \endgroup%
10860   % \leavevmode% avoid bad space factor (0) error
10861   \LWR@traceinfo{\LWR@HTML@caption@end: done}%
10862 }
```

`\caption@begin` Low-level patches to create HTML tags for captions. These are assigned `\AtBeginDocument`
`\caption@end` so that other packages which modify captions will have already been loaded before saving the print-mode version.

Print versions are provided here in case `caption` is not loaded.

```
10863 \AtBeginDocument{
10864   \providecommand{\caption@begin}[1]{}
10865   \LWR@formatted{caption@begin}
10866
10867   \providecommand{\caption@end}{}
10868   \LWR@formatted{caption@end}
10869 }
```

`\captionlistentry` Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```

10870 \AtBeginDocument{%
10871 \IfPackageLoadedTF{caption}{
10872   \let\LWR@origcaptionlistentry\captionlistentry
10873
10874   \renewcommand*\captionlistentry{%
10875     \LWR@ensuredoingapar%
10876     \LWR@origcaptionlistentry%
10877   }

10878   \def\LWR@LTcaptionlistentry{%
10879     \LWR@ensuredoingapar%
10880     \LWR@forcenewautoidanchor%
10881     \bgroup%
10882     \ifstar{\egroup\LWR@LT@captionlistentry}% gobble *
10883     {\egroup\LWR@LT@captionlistentry}%
10884   }%
10885
10886   \def\LWR@LT@captionlistentry#1{%
10887     \caption@listentry\@firstoftwo[\LTcapttype]{#1}%
10888   }%
10889 }% caption loaded
10890 {% caption not loaded
10891   \newcommand{\captionlistentry}[2][{}]{%
10892     \newcommand{\LWR@LT@captionlistentry}[2][{}]{%
10893   }
10894 }% AtBeginDocument

```

`\addcontentsline` Patched to write the autopage and autoid before each float's entry. No changes if writing .toc For a theorem, automatically defines `\ext@<type>` as needed, to mimic and reuse the float mechanism.

f

```

10895 \let\LWR@origaddcontentsline\addcontentsline
10896
10897 \renewcommand*\addcontentsline}[3]{%
10898   \ifstrequal{#1}{toc}{% not TOC

10899     \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
10900     }%
10901     {\LWR@newautoidanchor}%

10902     \ifcvoid{ext@#2}{\csdef{ext@#2}{#1}}{%

10903       \addtocontents{\@nameuse{ext@#2}}{%
10904         \protect\LWRsetnextfloat%
10905         {\arabic{LWR@currentautosecfloatpage}}%
10906         {\arabic{LWR@thisautoid}}%
10907       }%
10908     }% not TOC
10909     \LWR@origaddcontentsline{#1}{#2}{#3}%
10910 }

```

Pkg `capt-of`
Pkg `caption`

Either package provides `\captionof`, which is later patched at the beginning of

the document.

`\captionof` Patched to handle paragraph tags.

```

10911 \RequirePackage{capt-of}
10912
10913 \AtBeginDocument{
10914     \let\LWR@origcaptionof\captionof
10915
10916     \renewcommand*{\captionof}{%
10917         \LWR@stoppars%
10918         \LWR@origcaptionof%
10919     }
10920 }% AtBeginDocument

10921 \end{warpHTML}

```

78 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The `.toc`, `.lof`, and `.lot` files are named by the source code `\jobname`.

In HTML, the printed tables are placed inside a `<div>` of class `toc`, `lof`, or `lot`.

A “`sidetoc`” is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular L^AT_EX infrastructure is used for TOC, along with some patches to generate HTML output.

for HTML output: `10922 \begin{warpHTML}`

78.1 Reading and printing the toc

`\LWR@myshorttoc` `{\<toc/lof/lot/sidetoc)}`

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the @ character into a normal letter to allow formatting commands in the section names.

Unlike in regular L^AT_EX, the file is not reset after being read, since the `sidetoc` may be referred to again in each HTML page.

```

10923 \newcommand*{\LWR@myshorttoc}[1]{%
10924     \LWR@traceinfo{\LWR@myshorttoc: #1}%

```

Only if the file exists:

```

10925     \IfFileExists{\jobname.#1}{%
10926         \LWR@traceinfo{\LWR@myshorttoc: loading}%

```



Many of the commands in the file will have @ characters in them, so @ must be

made a regular letter.

```
10927      \begingroup%
10928      \makeatletter%
```

Disable \ref to avoid nested HTML references.

```
10929      \LetLtxMacro\ref\LWR@print@ref%
10930      \LWR@disablepinyin%
```

Read in the toc file:

```
10931      \@input{\jobname.#1}%
10932      \endgroup%
10933      }%
10934      {%
10935      \LWR@traceinfo{LWR@myshorttoc: done}%
10936      }
```

```
\LWR@subtableofcontents {<toc/lof/lot>} {<sectionstarname>}
```

Places a TOC/LOF/LOT at the current position.

```
10937 \NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
10938      \@ifundefined{chapter}%
10939      {\LWR@closeprevious{section}}%
10940      {\LWR@closeprevious{chapter}}%
```

Prints any pending footnotes so that they appear above the potentially large toc:

```
10941      \LWR@printpendingfootnotes%
```

Place the list into its own chapter (if defined) or section:

```
10942      \@ifundefined{chapter}{\section*{#2}}{\chapter*{#2}}%
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
10943      \LWR@htmlElementclass{nav}{#1}%
```

Create the actual list:

```
10944      \LWR@myshorttoc{#1}%
```

Close the nav:

```
10945      \LWR@htmlElementclassend{nav}{#1}%
10946      }
```

```
\@starttoc {<ext>}
```

Patch \@starttoc to encapsulate the TOC inside HTML tags:

```

10947 \let\LWR@orig@starttoc \@starttoc
10948
10949 \renewcommand{\@starttoc}[1]{
10950   \LWR@htmlElementclass{nav}{#1}%
10951   \LWR@orig@starttoc{#1}%
10952   \LWR@htmlElementclassend{nav}{#1}%
10953 }

```

Bool LWR@copiedsidetoc

Used to only copy the toc file to the sidetoc a single time.

(listings and perhaps other packages would re-use \tableofcontents for their own purposes, causing the sidetoc to be copied more than once, and thus end up empty.)

```

10954 \newbool{LWR@copiedsidetoc}
10955 \boolfalse{LWR@copiedsidetoc}

```

\tableofcontents Patch \tableofcontents, etc. to print footnotes first. newfloat uses \listoffigures for all future float types.

```

10956 \AtBeginDocument{
10957
10958 \LetLtxMacro\LWR@origtableofcontents\tableofcontents
10959
10960 \renewcommand*{\tableofcontents}{%

```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```

10961   \ifboolexpr{bool{FormatWP} and bool{WPMarkTOC}}{
10962
10963     === table of contents ===
10964
10965   }
10966   {

```

Copy the .toc file to .sidetoc for printing the sideroc. The original .toc file is renewed when \tableofcontents is finished.

```

10967     \ifbool{LWR@copiedsidetoc}{}{%
10968       \LWR@copyfile{\jobname.toc}{\jobname.sidetoc}%
10969       \booltrue{LWR@copiedsidetoc}%
10970     }%
10971     \LWR@printpendingfootnotes

```

Disable \ref to avoid nested HTML references.

```

10972     \begingroup%
10973     \LetLtxMacro\ref\LWR@print@ref%
10974     \LWR@disablepinyin%
10975     \LWR@origtableofcontents%
10976     \endgroup%
10977   }
10978 }% \tableofcontents
10979
10980 }% AtBeginDocument

```

`\listoffigures`

```

10981 \let\LWR@origlistoffigures\listoffigures
10982
10983 \renewcommand*\listoffigures{
10984   \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{
10985
10986     === list of figures ===
10987
10988   }
10989   {
10990     \LWR@printpendingfootnotes

```

Disable `\ref` to avoid nested HTML references.

```

10991   \begingroup%
10992   \LetLtxMacro\ref\LWR@print@ref%
10993   \LWR@disablepinyin%
10994   \LWR@origlistoffigures%
10995   \endgroup%
10996 }
10997 }

```

`\listoftables`

```

10998 \let\LWR@origlistoftables\listoftables
10999
11000 \renewcommand*\listoftables{
11001   \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{
11002
11003     === list of tables ===
11004
11005   }
11006   {
11007     \LWR@printpendingfootnotes

```

Disable `\ref` to avoid nested HTML references.

```

11008   \begingroup%
11009   \LetLtxMacro\ref\LWR@print@ref%
11010   \LWR@disablepinyin%
11011   \LWR@origlistoftables%
11012   \endgroup%
11013 }
11014 }

```

78.2 toc commands

`\LWR@listof` $\langle\{type\}\rangle$ $\langle\{title\}\rangle$

Emulate the `\listof` command from the `float` package (section 276). Used to create lists of custom float types. Also used to redefine the standard L^AT_EX `\listoffigures` and `\listoftables` commands, and in `tocloft` and `memoir`.

```

11015 \NewDocumentCommand{\LWR@listof}{m +m}{%
11016   \@ifundefined{L@#1}{%

```

```

11017     \csdef{l@#1}##1##2{\hypertocfloat{1}{#1}{\@nameuse{ext@#1}}{##1}{##2}}%
11018     }{ }%
11019     \LWR@subtableofcontents{\@nameuse{ext@#1}}{#2}%
11020     \expandafter\newwrite\csname tf@\csname ext@#1\endcsname\endcsname%
11021     \immediate\openout \csname tf@\csname ext@#1\endcsname\endcsname%
11022         \jobname.\@nameuse{ext@#1}\relax%
11023 }

```

78.3 Side toc

The “side toc” is a table-of-contents positioned to the side.

It may be renamed by redefining `\sitetocname`, and may contain paragraphs.

Per table 18, `css` may be used to format the sideroc.

Table 18: CSS related to the sideroc

div.sidetoccontainer: The entire sideroc.

div.sidetoctitle: The title.

div.sidetoccontents: The table of contents.

```
11024 \end{warpHTML}
```

for HTML & PRINT: 11025 \begin{warpall}

Ctrl SideTOCDepth

Controls how deep the side-TOC gets. Use a standard \LaTeX section level similar to `tocdepth`. Warn if parts of the website may be inaccessible.

```

11026 \newcounter{SideTOCDepth}
11027 \setcounter{SideTOCDepth}{1}
11028
11029 \AtEndDocument{%
11030     \ifnumcomp{\value{SideTOCDepth}}{<}{\value{FileDepth}}{
11031         \PackageWarningNoLine{lwarp}
11032         {%
11033             SideTOCDepth is less than FileDepth,\MessageBreak
11034             so some website pages may be inaccessible%
11035         }
11036     }{ }
11037 }

```

`\sitetocname` Holds the default name for the sideroc.

```
11038 \newcommand{\sitetocname}{Contents}
```

```
11039 \end{warpall}
```

for HTML output: 11040 \begin{warpHTML}

`\LWR@sitetoc` Creates the actual side-TOC.

```
11041 \newcommand*{\LWR@sitetoc}{%
```

```

11042 \LWR@forcenewpage
11043 \LWR@stoppars
11044

```

The entire sidetoc is placed into a nav of class sidetoc.

```

11045 \LWR@htmlElementclass{div}{sidetoccontainer}
11046 \LWR@htmlElementclass{nav}{sidetoc}
11047
11048 \setcounter{tocdepth}{\value{SideTOCDepth}}
11049

```

The title is placed into a <div> of class sidetoc title, and may contain paragraphs.

```

11050 \begin{BlockClass}{sidetoc title}
11051 \ifcsvoid{thetitle}{\InlineClass{sidetoc thetitle}{\thetitle}\par}
11052 \sidetocname
11053 \end{BlockClass}

```

The table of contents is placed into a <div> of class sidetoc contents.

```

11054 \begin{BlockClass}{sidetoc contents}
11055 \LinkHome
11056
11057 \LWR@myshorttoc{sidetoc}
11058 \end{BlockClass}
11059 \LWR@htmlElementclassend{nav}{sidetoc}
11060 \LWR@htmlElementclassend{div}{sidetoc container}
11061 }

```

78.4 Low-level toc line formatting

`\numberline` {<number>}

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```

11062 \newcommand*\LWR@numberline[1]{%
11063 \LWR@sectionnumber{#1}\quad%
11064 }
11065
11066 \LetLtxMacro\numberline\LWR@numberline

```

`\LWR@maybetocdata` Replaced by `tocdata`. Adds author name.

```

11067 \newcommand*\LWR@maybetocdata{}

```

`\hypertoc` {<1: depth>} {<2: type>} {<3: name>} {<4: page>}

Called by `\l@section`, etc. to create a hyperlink to a section.

The autopage label is always created just after the section opens.

#1 is depth

#2 is section, subsection, etc.

#3 the text of the caption

#4 page number

```
11068 \NewDocumentCommand{\hypertoc}{m m +m m}{%
11069   \LWR@traceinfo{hypertoc !#1!#2!#3!#4!}%
```

Respond to tocdepth:

```
11070   \ifnumcomp{#1}{>}{\value{tocdepth}}%
11071     {}%
11072     {%
11073     \LWR@startpars%
```

Create an HTML link to <filename>#autosec-(page), with the name, of the given HTML class.

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
11074   \LWR@subhyperrefclass{%
11075     \LWR@htmlrefsectionfilename{\BaseJobname-autopage-#4}%
11076     \LWR@origpound\LWR@print@mbbox{autosec-#4}%
11077     }{#3}{toc#2}%

11078   \LWR@maybetocdata%

11079   \LWR@stoppars%
11080   }%
11081   \LWR@traceinfo{hypertoc done}%
11082 }
```

Ctrl lofdepth

TOC depth for figures.

```
11083 \IfClassLoadedTF{memoir}{}{
11084   \newcounter{lofdepth}
11085   \setcounter{lofdepth}{1}
11086 }
```

Ctrl lotdepth

TOC depth for tables.

```
11087 \IfClassLoadedTF{memoir}{}{
11088   \newcounter{lotdepth}
11089   \setcounter{lotdepth}{1}
11090 }
```

\hypertocfloat {<1: depth>} {<2: type>} {<3: ext of parent>} {<4: caption>} {<5: page>}

#1 is depth

#2 is figure, table, etc.

#3 is lof, lot, of the parent.

#4 the text of the caption

#5 page number

```
11091 \newcommand{\hypertocfloat}[5]{%
```

If some float-creation package has not yet defined the float type's `lofdepth` counter, etc, define it here:

```
11092   \@ifundefined{c@#3depth}{%
11093     \newcounter{#3depth}%
11094     \setcounter{#3depth}{1}%
11095   }{}
```

Respond to `lofdepth`, etc.:

```
11096   \LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%
11097   \ifthenelse{\cnttest{#1}{<=}{\arabic{#3depth}}}%
11098     {%
11099       \LWR@startpars%
```

Create an HTML link to `filename#autoid-(float number)`, with text of the caption, of the given HTML class.

`\BaseJobname` is added to the label in case `xr` or `xr-hyper` are used.

```
11100       \LWR@subhyperrefclass{%
11101       \LWR@htmlrefsectionfilename{%
11102         \BaseJobname-autopage-\arabic{LWR@nextautopage}%
11103       }%
11104       \LWR@origpound\LWR@print@mbbox{autoid-\arabic{LWR@nextautoid}}}%
11105       {#4}{toc#2}%

11106       \LWR@maybetocdata%

11107       \LWR@stoppars%
11108     }%
11109   }%
11110 }
```

Automatically called by `\contentsline`:

```
\l@book {<name>} {<page>}
```

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\book`.

```
11111 \DeclareDocumentCommand{\l@book}{m m}{\hypertoc{-2}{book}{#1}{#2}}
```

```
\l@part {<name>} {<page>}
```

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\part`.

```
11112 \DeclareDocumentCommand{\l@part}{m m}{\hypertoc{-1}{part}{#1}{#2}}
```

`\l@chapter` $\{\langle name \rangle\} \{\langle page \rangle\}$

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\chapter`.

```
11113 \@ifundefined{chapter}
11114 {}
11115 {
11116 \DeclareDocumentCommand{\l@chapter}{m m}
11117   {\hypertoc{0}{chapter}{#1}{#2}}
11118 }
```

`\l@section` $\{\langle name \rangle\} \{\langle page \rangle\}$

```
11119 \renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
```

`\l@subsection` $\{\langle name \rangle\} \{\langle page \rangle\}$

```
11120 \renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
```

`\l@subsubsection` $\{\langle name \rangle\} \{\langle page \rangle\}$

```
11121 \renewcommand{\l@subsubsection}[2]{\hypertoc{3}{subsubsection}{#1}{#2}}
```

`\l@paragraph` $\{\langle name \rangle\} \{\langle page \rangle\}$

```
11122 \renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}
```

`\l@subparagraph` $\{\langle name \rangle\} \{\langle page \rangle\}$

```
11123 \renewcommand{\l@subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}
```

`\l@figure` $\{\langle name \rangle\} \{\langle page \rangle\}$

```
11124 \renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}
```

`\l@table` $\{\langle name \rangle\} \{\langle page \rangle\}$

```
11125 \renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}
```

```
11126 \end{warpHTML}
```

79 Index and glossary

See:

<http://tex.stackexchange.com/questions/187038/>

[how-to-mention-section-number-in-index-created-by-imakeidx](#)

Index links are tracked by the counter `LWR@autoindex`. This counter is used to create a label for each index entry, and a reference to this label for each entry in

the index listing. This method allows each index entry to link directly to its exact position in the document.

for HTML output: 11127 \begin{warpHTML}

```
11128 \newcounter{LWR@autoindex}
11129 \setcounter{LWR@autoindex}{0}
11130
11131 \newcounter{LWR@autoglossary}
11132 \setcounter{LWR@autoglossary}{0}
```

\IndexPageSeparator User-adjustable delimiters for page and range separators in the *.ind files.
 \IndexRangeSeparator

```
11133 \newcommand*\IndexPageSeparator}{, }
11134 \newcommand*\IndexRangeSeparator}{--}
```

Env theindex

```
11135 \@ifundefined{chapter}
11136    {\newcommand*\LWR@indexsection}[1]{\section*{#1}}
11137    {\newcommand*\LWR@indexsection}[1]{\chapter*{#1}}
11138
11139
11140 \AtBeginDocument{
11141
11142 \renewenvironment*{theindex}{%
11143    \LWR@indexsection{\indexname}%
11144    \LetLtxMacro\item\LWR@indexitem%
11145    \LetLtxMacro\subitem\LWR@indexsubitem%
11146    \LetLtxMacro\subsubitem\LWR@indexsubsubitem%
11147 }{}
11148
11149 }% AtBeginDocument
```

\LWR@indexitem [*<index key>*] The optional argument is added to support repeatindex.

```
11150 \newcommand{\LWR@indexitem}[1][\@empty]{
11151
11152    \InlineClass{indexitem}{\LWR@htmlcomment{}}#1%
11153 }
```

\LWR@indexsubitem

```
11154 \newcommand{\LWR@indexsubitem}{
11155
11156    \InlineClass{indexsubitem}{\LWR@htmlcomment{}}%
11157 }
```

\LWR@indexsubsubitem

```
11158 \newcommand{\LWR@indexsubsubitem}{
11159
11160    \InlineClass{indexsubsubitem}{\LWR@htmlcomment{}}%
11161 }
```

`\LWR@index@modifyentry` $\{\langle indexing\ term\rangle\}$

If using *xindex*, modifies the pipe character to become `\hyperindexformat`. The indexing term is split into two argument at the pipe, then fed to `\LWR@index@modifyentrysub`.

```
11162 \NewDocumentCommand{\LWR@index@modifyentry}{>\SplitArgument{1}{|}m}
11163   {\LWR@index@modifyentrysub#1}
```

Handle left and right parenthesis range argument, or add a `\hyperindexformat` clause.

```
11164 \newcommand*{\LWR@index@modifyentrysub}[2]{%
11165   \edef\LWR@tempone{#1}%
11166   \edef\LWR@temptwo{#2}%
11167   \IfValueTF{#2}{%
11168     \ifx#2(%
11169       \appto\LWR@tempone{|}%
11170     \else%
11171       \ifx#2)%
11172         \appto\LWR@tempone{|}%
11173       \else%
11174         \appto\LWR@tempone{%
11175           |hyperindexformat\LWRleftbrace%
11176           \LWRbackslash#2%
11177           \LWRrightbrace%
11178         }%
11179       \fi%
11180     \fi%
11181   }%
11182   {}%
11183 }
```

Bool `LWR@index@tricked` Used to track *xindex* creation. See next.

```
11184 \newbool{LWR@index@tricked}
11185 \boolfalse{LWR@index@tricked}
```

`\@wrindex` $\{\langle indexing\ term\rangle\}$ Redefined to write the `LWR@autoindex` counter instead of page.

If using *xindex*, the first line is a comment including a special phrase which tricks *xindex* into thinking that `\hyperref` was used.

```
11186 \def\LWR@wrindex#1{%
11187   \ifbool{LWR@index}{%
11188     \ifbool{LWR@index@tricked}{%}%
11189     \protected@write\@indexfile{%
11190       {%
11191         \LWRpercent\space hyperpage\LWRrightbrace%
11192         \LWRpercent\space trick xindex to assume hyperref%
11193       }%
11194       \global\booltrue{LWR@index@tricked}%
11195     }%
11196     \LWR@index@modifyentry{#1}%
11197   }{%
11198     \def\LWR@tempone{#1}%
11199   }%
11200   \addtocounter{LWR@autoindex}{1}%
}
```

```
11201 \protected@write\@indexfile{}%
11202 {\string\indexentry{\LWR@tempone}{\arabic{LWR@autoindex}}}%
```

The label is assigned after the file write to avoid conflict with `cleveref`.

```
11203 \label{LWRindex-\arabic{LWR@autoindex}}%
11204 \endgroup%
11205 \@esphack%
11206 }
11207
11208 \AtBeginDocument{
11209 \let\@wrindex\LWR@wrindex
11210 }
```

`\@wrglossary {<term>}` Redefined to write the `LWR@autoglossary` counter instead of page.

```
11211 \def\@wrglossary#1{%
11212 \addtocounter{LWR@autoglossary}{1}%
11213 \LWR@new@label{LWRglossary-\theLWR@autoglossary}%
11214 \protected@write\@glossaryfile{}%
11215 {\string\glossaryentry{#1}{\theLWR@autoglossary}}%
11216 \endgroup%
11217 \@esphack%
11218 }
```

`\LWR@indexnameref@anonref {<LWR@autoindex>}`

Displays a reference link where there no `\ref` available.

```
11219 \newcommand*\LWR@indexnameref@anonref[1]{%
11220 \LWR@startref{LWRindex-#1}%
11221 (*)%
11222 \LWR@htmltag{/a}%
11223 }
```

`\LWR@indexnameref@ref {<LWR@autoindex>}`

Creates `\ref`-style index references. To avoid an unwanted space if there is nothing to reference, the reference is checked first.

```
11224 \newcommand*\LWR@indexnameref@ref[1]{%
11225 \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
11226 \ifdefvoid{\LWR@thisref}{}%
11227 \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
11228 \ifdefvoid{\LWR@thisref}%
11229 {\LWR@indexnameref@anonref{#1}}%
11230 {\ref{LWRindex-#1}}%
11231 }%
11232 }
```

`\LWR@indexnameref@refnameref {<LWR@autoindex>}`

Creates `\ref`-style index references. To avoid an unwanted space if there is nothing to reference, the reference is checked first. For links to starred or `??` objects, only the name is used.

```
11233 \newcommand*\LWR@indexnameref@refnameref[1]{%
```

```

11234 \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
11235 \ifdefvoid{\LWR@thisref}{}{%
11236     \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
11237     \ifdefvoid{\LWR@thisref}{}{%
11238         \ifdefstring{\LWR@thisref}{(*)}%
11239         {}%
11240         {\ref{LWRindex-#1} }% space
11241     }%
11242 }%
11243 \nameref{LWRindex-#1}%
11244 }

```

`\LWR@indexnameref@cref` $\langle LWR@autoindex \rangle$

Creates `\cref`-style index references. If no numbered reference is available, a `\nameref` is used instead. If the reference is `??`, which will be changed by `\LWR@indexnameref` to become `(*)`, then the link is changed to show `(*)`.

```

11245 \newcommand*{\LWR@indexnameref@cref}[1]{%
11246     \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
11247     \ifdefvoid{\LWR@thisref}{}%
11248     \nameref{LWRindex-#1}%
11249 }{%
11250     \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
11251     \ifdefvoid{\LWR@thisref}{}%
11252     \nameref{LWRindex-#1}%
11253 }{%
11254     \ifdefstring{\LWR@thisref}{(*)}{%
11255         \LWR@indexnameref@anonref{#1}%
11256     }{%
11257         \cref{LWRindex-#1}%
11258     }%
11259 }%
11260 }%
11261 }

```

`\LWR@indexnameref@crefnameref` $\langle LWR@autoindex \rangle$

Creates `\cref`-style index references. If no numbered reference is available, a `\nameref` is used instead. If the reference is `??`, which will be changed by `\LWR@indexnameref` to become `(*)`, then the link is changed to show only the name.

```

11262 \newcommand*{\LWR@indexnameref@crefnameref}[1]{%
11263     \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
11264     \ifdefvoid{\LWR@thisref}%
11265     {}%
11266     {%
11267         \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
11268         \ifdefvoid{\LWR@thisref}%
11269         {}%
11270         {%
11271             \ifdefstring{\LWR@thisref}{(*)}%
11272             {}%
11273             {\cref{LWRindex-#1} }% space
11274         }%
11275     }%
11276     \nameref{LWRindex-#1}%
11277 }

```

`\LWR@indexnameref` $\{\langle LWR@autoindex \rangle\}$

Creates a hyperlink based on the given entry's autoindex.

```
11278 \newcommand*\LWR@indexnameref[1]{%
11279   {% group
```

Temporarily redefine `\caption@xref` because it was printing ?? in the indexes, and also causing error on expansion:

```
11280     \ifdef{\caption@xref}{%
11281       \renewcommand*\caption@xref[2]{(*)}%
11282     }{%

11283     \ifdefstring{\LWR@IndexRef}{ref}{%
11284       \LWR@indexnameref@ref{#1}%
11285     }{%
11286     \ifdefstring{\LWR@IndexRef}{nameref}{%
11287       \nameref{LWRindex-#1}%
11288     }{%
11289     \ifdefstring{\LWR@IndexRef}{refnameref}{%
11290       \LWR@indexnameref@refnameref{#1}%
11291     }{%
11292     \ifdefstring{\LWR@IndexRef}{cref}{%
11293       \LWR@indexnameref@cref{#1}%
11294     }{%
11295     \ifdefstring{\LWR@IndexRef}{crefnameref}{%
11296       \LWR@indexnameref@crefnameref{#1}%
11297     }{%
11298     \ifdefstring{\LWR@IndexRef}{autoref}{%
11299       \LWR@indexnameref@cref{#1}%
11300     }{% text string
11301       \LWR@startref{LWRindex-#1}%
11302       \LWR@IndexRef%
11303       \LWR@htmltag{/a}%
11304     }}}}]}%
11305   }% group
11306 }
```

`\LWR@doindexentrysubsub` $\{\langle range\ start: LWR@autoindex, or\ macros. \rangle\} \{\langle range\ end\ or\ blank \rangle\}$

Creates a hyperlink, or handles `\see`, `\textbf`, etc.

```
11307 \newrobustcmd*\LWR@doindexentrysubsub[2]{%
11308   \IfInteger{#1}%
11309     {\LWR@indexnameref{#1}}%
11310     {#1}%
11311   \IfValueT{#2}{%
11312     \IndexRangeSeparator%
11313     \IfInteger{#2}%
11314       {\LWR@indexnameref{#2}}%
11315       {#2}%
11316   }%
11317 }
```

`\LWR@doindexentrysub` $\{\langle range\ delimiter \rangle\} \{\langle LWR@autoindex\ or\ macros, possible\ a\ range \rangle\}$

```
11318 \NewDocumentCommand{\LWR@doindexentrysub}{m >\SplitArgument{1}{#1}}m}
```

```
11319   {\LWR@doindexentrysubsub#2}
```

`\LWR@doindexentry` $\{\langle LWR@autoindex \text{ or macros, possible a range} \rangle\}$

```
11320 \newcommand*{\LWR@doindexentry}[1]{%
11321   \relax% required
11322   \expandafter\LWR@doindexentrysub\expandafter{\IndexRangeSeparator}{#1}%
11323 }
```

`\LWR@hyperindexrefnullified` Handles macros commonly seen inside an `\index` entry. Each macro is redefined to create and format a link to its entry.

 **index formatting** To handle additional macros:

```
\appto\LWR@hyperindexrefnullified{. . . }
```

```
11324 \newcommand{\LWR@hyperindexrefnullified}{%
11325   \renewrobustcmd{\emph}[1]{\LWR@HTML@emph{\LWR@doindexentry{##1}}}%
11326   \renewrobustcmd{\textbf}[1]{\LWR@HTML@textbf{\LWR@doindexentry{##1}}}%
11327   \renewrobustcmd{\texteb}[1]{\LWR@HTML@texteb{\LWR@doindexentry{##1}}}%
11328   \renewrobustcmd{\textlg}[1]{\LWR@HTML@textlg{\LWR@doindexentry{##1}}}%
11329   \renewrobustcmd{\textrm}[1]{\LWR@HTML@textrm{\LWR@doindexentry{##1}}}%
11330   \renewrobustcmd{\textsf}[1]{\LWR@HTML@textsf{\LWR@doindexentry{##1}}}%
11331   \renewrobustcmd{\texttt}[1]{\LWR@HTML@texttt{\LWR@doindexentry{##1}}}%
11332   \renewrobustcmd{\textup}[1]{\LWR@HTML@textup{\LWR@doindexentry{##1}}}%
11333   \renewrobustcmd{\textsc}[1]{\LWR@HTML@textsc{\LWR@doindexentry{##1}}}%
11334   \renewrobustcmd{\textulc}[1]{\LWR@HTML@textulc{\LWR@doindexentry{##1}}}%
11335   \renewrobustcmd{\textsi}[1]{\LWR@HTML@textsi{\LWR@doindexentry{##1}}}%
11336   \renewrobustcmd{\textit}[1]{\LWR@HTML@textit{\LWR@doindexentry{##1}}}%
11337   \renewrobustcmd{\textsl}[1]{\LWR@HTML@textsl{\LWR@doindexentry{##1}}}%
11338 }
```

`\hyperindexref` $\{\langle list \text{ of } LWR@autoindex, \text{ commas, and ranges} \rangle\}$

`\hyperindexref{LWR@autoindex}` is inserted into `*.ind` by the *makeindex* style file `lwarp.ist` or the *xindy* style file `lwarp.xdy`. For *xindex*, `\hyperpage` is inserted, which is `\let` to `\hyperindexref`. For *gindex*, `\addindexitem` and related are inserted, which are defined to use `\hyperindexref`.

The argument is split at commas, and also for ranges, then passed to `\LWR@hyperindexrefsub`.

```
11339 \newcommand*{\hyperindexref}[1]{%
11340   \relax% required
11341   \expandafter\LWR@hyperindexref@comma\expandafter{\IndexPageSeparator}{#1}%
11342 }
```

`\LWR@hyperindexref@comma` $\{\langle separator \rangle\} \{\langle list \text{ of args} \rangle\}$

The list is split at commas, and passed to `\LWR@hyperindexref@@comma`.

```
11343 \NewDocumentCommand{\LWR@hyperindexref@comma}
11344   {m >\SplitList{#1}} m}
11345   {%
```

Used to place the separator between each entry, but not before the first.

```
11346 \def\LWR@hyperindexref@thiscomma{}%
11347 \def\LWR@hyperindexref@nextcomma{#1}%
```

Each comma-delimited entry is now passed individually to \LWR@hyperindexref@@comma.

```
11348 \ProcessList{#2}\LWR@hyperindexref@@comma%
11349 }
```

\LWR@hyperindexref@@comma {⟨*arg, perhaps with a range*⟩}

A comma separator is placed if not the first item, then the range is parsed.

```
11350 \newcommand*{\LWR@hyperindexref@@comma}[1]{%
11351 \LWR@hyperindexref@thiscomma%
11352 \renewcommand{\LWR@hyperindexref@thiscomma}{\LWR@hyperindexref@nextcomma}%
11353 \expandafter\LWR@hyperindexref@range\expandafter{\IndexRangeSeparator}{#1}%
11354 }
```

\LWR@hyperindexref@range {⟨*range delimiter*⟩} {⟨*arg*⟩}

```
11355 \NewDocumentCommand{\LWR@hyperindexref@range}
11356 {m >{\SplitArgument{1}{#1}} m}
11357 {\LWR@hyperindexrefsub#2}
```

\LWR@hyperindexrefsub {⟨*range start: LWR@autoindex*⟩} {⟨*range end, or -NoValue-*⟩}

Handles the start and end of a range, if applicable.

```
11358 \newcommand*{\LWR@hyperindexrefsub}[2]{%
11359 \LWR@hyperindexrefsubtwo{#1}%
11360 \IfValueT{#2}{%
11361 \IndexRangeSeparator%
11362 \LWR@hyperindexrefsubtwo{#2}%
11363 }%
11364 }
```

\LWR@hyperindexrefsubtwo {⟨*LWR@autoindex*⟩}

```
11365 \newcommand*{\LWR@hyperindexrefsubtwo}[1]{%
```

In long index lines with numerous entries, *makeindex* can insert a newline before the page number, resulting in an extra space before the first digit. If the first character is a space, remove it first.

```
11366 \edef\LWR@tempone{#1}%
11367 \IfBeginWith{\LWR@tempone}{ }{%
11368 \StrGobbleLeft{\LWR@tempone}{1}[\LWR@tempone]%
11369 }{ }%
```

If a numeric entry, create a link. If not numeric, such as \see, use the entry as-is. \emph, \textit, etc. have been redefined above to create and format the entry.

```
11370 \IfInteger{\LWR@tempone}%
11371 {\LWR@indexnameref{\LWR@tempone}}%
11372 {%
11373 \begingroup%
```

```

11374         \LWR@hyperindexrefnullified%
11375         #1%
11376         \endgroup%
11377     }%
11378 }

```

`\hyperpage` Emulate `hyperref`.

```
11379 \LetLtxMacro\hyperpage\hyperindexref
```

`\nohyperpage` Emulate `hyperref`.

```
11380 \def\nohyperpage#1{}
```

`\hyperindexformat` Emulate `hyperref`.

```

11381 \def\hyperindexformat#1#2{%
11382     #1{\hyperpage{#2}}%
11383 }%

```

```
11384 \end{warpHTML}
```

for PRINT output: A null command for print mode, in case `hyperref` was not used:

```

11385 \begin{warpprint}
11386 \newcommand{\hyperindexref}[1]{#1}
11387 \end{warpprint}

```

for HTML & PRINT: For the `glossaries` package, try to prevent an error where `\glo@name` was not found:

```

11388 \begin{warpall}
11389 \providecommand{\glo@name}{}
11390 \end{warpall}

```

80 Bibliography presentation

for HTML output: 11391 `\begin{warpHTML}`

`\bibliography` `{\filenames}` At one time this was modified to read `\BaseJobname.bbl`, which meant the HTML version could not resolve until the print version was also present. This also confused `multibib`. It has been reverted to the original to use `\jobname.bbl`.

`\@biblabel` `{\text-refnumber}`

```
11392 \renewcommand{\@biblabel}[1][[#1]\quad}
```

Env `thebibliography` To emphasize document titles in the bibliography, the following redefines `\em` inside `thebibliography` to gather everything until the next closing brace, then display these tokens with `\textit`.

Adapted from `embracedef.sty`, which is by TAKAYUKI YATO:
<https://gist.github.com/zr-tex8r/b72555e3e7ad2f0a37f1>

```

11393 \AtBeginDocument{
11394
11395 \AtBeginEnvironment{thebibliography}{
11396
11397 \providecommand*\LWR@newem}[1]{\textit{#1}}
11398
11399 \renewrobustcmd{\em}{%
11400   \begingroup
11401     \gdef\LWR@em@after{\LWR@em@finish\LWR@newem}%
11402     \afterassignment\LWR@em@after
11403     \toks@\bgroup
11404 }
11405
11406 \def\LWR@em@finish#1{%
11407   \xdef\LWR@em@after{\noexpand#1{\the\toks@}}%
11408   \endgroup
11409   \LWR@em@after\egroup
11410 }
11411
11412 }% \AtBeginEnvironment{thebibliography}
11413
11414 }% \AtBeginDocument

11415 \end{warpHTML}

```

81 Restoring original formatting

for HTML output: 11416 \begin{warpHTML}

`\LWR@restoreMathJaxformatting` A few macros (ref: `tcolorbox`) must be treated separately while printing the HTML comment for a MATHJAX expression. These are set here, to which other functions may be appended.

```
11417 \newcommand*\LWR@restoreMathJaxformatting{}
```

`\LWR@restoreorigformatting` Used to temporarily restore the print-mode meaning of a number of formatting, graphics, and symbols-related macros while generating SVG math or a `lateximage`.

Must be used inside a group.

Sets `\LWR@formatting` to print until the end of the group.

A number of packages will `\appto` additional actions to this macro.

Various packages add to this macro using `\appto`.

```

11418 \newcommand*\LWR@restoreorigformatting}{%
11419   \LWR@traceinfo{LWR@restoreorigformatting}%

```

Numerous macros change their print/HTML meaning depending on `\LWR@formatting`:

```

11420   \renewcommand*\LWR@formatting}{print}%
11421   \linespread{1}%

```

```

11422 \setbool{LWR@doingparhooks}{false}%
11423 \LWR@select@print@hspace%

11424 \def\color@endgroup{\endgraf\endgroup}%

11425 \LetLtxMacro\hfil\LWR@orighfil%
11426 \let\hss\LWR@orighss%
11427 \let\llap\LWR@origllap%
11428 \let\rlap\LWR@origrlap%
11429 \let\hfilneg\LWR@orighfilneg%

11430 \let\,\LWR@origcomma% disable HTML short unbreakable space
11431 \let\thinspace\LWR@origthinspace% disable HTML short unbreakable space
11432 \let\negthinspace\LWR@orignegthinspace% disable HTML negative short unbreakable space
11433 \let\textellipsis\LWR@origtextellipsis%

11434 \let\vdots\LWR@origvdots%

11435 \let\textless\LWR@origtextless%
11436 \let\textgreater\LWR@origtextgreater%

11437 \let&\LWR@origampersand%

11438 \LetLtxMacro\em\LWR@origem%
11439 \LetLtxMacro\normalfont\LWR@orignormalfont%
11440 \let\sp\LWR@origsp%
11441 \let\sb\LWR@origsb%
11442 \LetLtxMacro\underline\LWR@origunderline%
11443 \let~\LWR@origtilde%
11444 \let\enskip\LWR@origenskip%
11445 \let\quad\LWR@origquad%
11446 \let\qqquad\LWR@origqqquad%

\endtabular must be restored to its original, instead of relying on lwarp's \LWR@formatted
mechanism:

11447 \LetLtxMacro\endtabular\LWR@origendtabular%
11448 \csletcs{endtabular*}{LWR@origendtabular*}%

11449 \LetLtxMacro\noalign\LWR@orignoalign%
11450 \LetLtxMacro\hline\LWR@orighline%

11451 \let\newline\LWR@orignewline%
11452 \LetLtxMacro\includegraphics\LWR@origincludegraphics%

11453 \LetLtxMacro\@ensuredmath\LWR@origensuredmath%

11454 \let\math\LWR@orig@math%
11455 \let\endmath\LWR@orig@endmath%
11456 \let\displaymath\LWR@orig@displaymath%
11457 \let\enddisplaymath\LWR@orig@enddisplaymath%
11458 %
11459 \LWR@restoreorigaccents%
11460 \LWR@restoreoriglists%

```

```
11461 \let\empfootnotetext\LWR@orig@mpfootnotetext%
11462 \LWR@hook@processingtags%
```

To enable MATHJAX-specific nullification, used for tcolorbox:

```
11463 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
11464   {\LWR@restoreMathJaxformatting}%
11465   }%
11466 }

11467 \end{warpHTML}
```

82 Nullifying filename formatting

The following are used to nullify certain macros and environments while converting section names to file names.

for HTML output: 11468 \begin{warpHTML}

Also commonly used are \@empty, \@gobble, and \@firstofone.

```
11469 \newcommand*\LWR@dash}{-}
```

\LWR@nullfonts Removes formatting during filename operations, file references, and HTML comments.



Use only inside a group.

The following are *not* made robust, since they must be expanded to their nullified versions.

```
11470 \catcode'\$=\active% redefining $ below
11471 \catcode'\_ =12% redefining \_ below
11472 \newcommand*\LWR@nullfonts}{%
```

Various built-in symbols.

```
11473 \renewcommand*\${-}%
11474 \renewcommand*\%{-}%
11475 \renewcommand*\_{-}%
11476 \renewcommand*\}{-}%
11477 \renewcommand*\{-}%
11478 \renewcommand*\&{-}% used to be 'and'
11479 \renewcommand*\#{-}%
11480 \renewcommand*\,{-}%
11481 \renewcommand*\~{-}%
11482 %
11483 % accents:
11484 \renewcommand*\`[1]{##1}%
11485 \renewcommand*\'[1]{##1}%
11486 \renewcommand*\^[1]{##1}%
11487 \renewcommand*\~[1]{##1}%
11488 \renewcommand*\=[1]{##1}%
```

```

11489 \renewcommand*{\u}[1]{##1}%
11490 \renewcommand*{\.}[1]{##1}%
11491 \renewcommand*{\"}[1]{##1}%
11492 \renewcommand*{\H}[1]{##1}%
11493 \renewcommand*{\v}[1]{##1}%
11494 \renewcommand*{\d}[1]{##1}%
11495 \renewcommand*{\c}[1]{##1}%
11496 \renewcommand*{\b}[1]{##1}%
11497 \renewcommand*{\t}[1]{##1}%
11498 %
11499 \let\newline\LWR@dash%
11500 \let\textasciicircum\LWR@dash%
11501 \let\textasciitilde\LWR@dash%
11502 \let\textasteriskcentered\LWR@dash%
11503 \let\textbackslash\LWR@dash%
11504 \let\textbar\LWR@dash%
11505 \let\textbardbl\LWR@dash%
11506 \let\textbigcircle\LWR@dash%
11507 \let\textbraceleft\LWR@dash%
11508 \let\textbraceright\LWR@dash%
11509 \let\textbullet\LWR@dash%
11510 \let\textcopyright\LWR@dash%
11511 \let\textdagger\LWR@dash%
11512 \let\textdaggerdbl\LWR@dash%
11513 \let\textdollar\LWR@dash%
11514 \let\textellipsis\LWR@dash%
11515 \let\textemdash\LWR@dash%
11516 \let\textendash\LWR@dash%
11517 \let\textexclamdown\LWR@dash%
11518 \let\textgreater\LWR@dash%
11519 \let\textless\LWR@dash%
11520 \let\textordfeminine\LWR@dash%
11521 \let\textordmasculine\LWR@dash%
11522 \let\textparagraph\LWR@dash%
11523 \let\textperiodcentered\LWR@dash%
11524 \let\textpertenthousand\LWR@dash%
11525 \let\textperthousand\LWR@dash%
11526 \let\textquestiondown\LWR@dash%
11527 \let\textquotedblleft\LWR@dash%
11528 \let\textquotedblright\LWR@dash%
11529 \let\textquoteleft\LWR@dash%
11530 \let\textquoteright\LWR@dash%
11531 \let\textregistered\LWR@dash%
11532 \let\textsection\LWR@dash%
11533 \let\textsterling\LWR@dash%
11534 \let\texttrademark\LWR@dash%
11535 \let\textunderscore\LWR@dash%
11536 \let\textvisiblespace\LWR@dash%
11537 \let\copyright\LWR@dash%
11538 \let\dag\LWR@dash%
11539 \let\ddag\LWR@dash%
11540 \let\dots\LWR@dash%
11541 \let\P\LWR@dash%
11542 \let\pounds\LWR@dash%
11543 \let\S\LWR@dash%
11544 %
11545 \renewcommand*{\aa}{a}%
11546 \renewcommand*{\AA}{A}%
11547 \renewcommand*{\AE}{AE}%
11548 \renewcommand*{\ae}{ae}%

```

```

11549 \renewcommand*\dh}{d}%
11550 \renewcommand*\DH}{D}%
11551 \renewcommand*\DJ}{D}%
11552 \renewcommand*\dj}{d}%
11553 \renewcommand*\IJ}{IJ}%
11554 \renewcommand*\ij}{ij}%
11555 \renewcommand*\L}{L}%
11556 \renewcommand*\l}{l}%
11557 \renewcommand*\NG}{NG}%
11558 \renewcommand*\ng}{ng}%
11559 \renewcommand*\O}{O}%
11560 \renewcommand*\o}{o}%
11561 \renewcommand*\oe}{oe}%
11562 \renewcommand*\OE}{OE}%
11563 \renewcommand*\ss}{ss}%
11564 \renewcommand*\SS}{SS}%
11565 \renewcommand*\th}{th}%
11566 \renewcommand*\TH}{TH}%
11567 %
11568 \let\guillemotleft\@empty%
11569 \let\guilsinglleft\@empty%
11570 \let\quotedblbase\@empty%
11571 \let\textquotedbl\@empty%
11572 \let\guillemotright\@empty%
11573 \let\guilsinglright\@empty%
11574 \let\quotesinglbase\@empty%

11575 \renewcommand*\HTMLunicode}[1]{}%
11576 \renewcommand*\HTMLentity}[1]{}%

11577 \renewcommand{\textsuperscript}[1]{##1}%
11578 \renewcommand{\textsubscript}[1]{##1}%

11579 \renewcommand{\underline}[1]{##1}%

11580 \RenewDocumentCommand{\hspace}{s m}{}%

11581 \RenewDocumentCommand{\LWRhtmlspanclass}{o D(){} m +m}{##4}%
11582 \DeclareExpandableDocumentCommand{\InlineClass}{D{()}{ } o m +m}{##4}%

```

Nullify math macros.

```

11583 \def\{##1\}{}%
11584 \def\[##1\]{}%
11585 \RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%

```

Nullify logos:

```

11586 \renewcommand*\TeX}{TeX}%
11587 \renewcommand*\LaTeX}{LaTeX}%
11588 \renewcommand*\LaTeXe}{LaTeX2e}%
11589 \renewcommand*\LuaTeX}{LuaTeX}%
11590 \renewcommand*\LuaLaTeX}{LuaLaTeX}%
11591 \renewcommand*\XeTeX}{XeTeX}%
11592 \renewcommand*\XeLaTeX}{XeLaTeX}%
11593 \renewcommand*\ConTeXt}{ConTeXt}%
11594 \renewcommand*\BibTeX}{BibTeX}%

```

```

11595 \renewcommand*\MakeIndex}{MakeIndex}%
11596 \renewcommand*\AmS}{AmS}%
11597 \renewcommand*\MiKTeX}{MiKTeX}%
11598 \renewcommand*\LyX}{LyX}%

```

Use the simpler form with `\texorpdfstring`:

```

11599 \def\texorpdfstring{\expandafter\@secondoftwo}%
11600 }
11601 \catcode'\$=3%
11602 \catcode'\_ =8%

```

`\FilenameNullify` {<*redefinitions*>}

Adds more nullifying definitions for filename generation.

```

11603 \newcommand*\FilenameNullify[1]{%
11604 \appto{\LWR@nullfonts}{#1}%
11605 }

11606 \end{warpHTML}

```

83 Math

83.1 Limitations

See [Math](#), section 8.7.

83.2 HTML alt tag names

Redefinable names for the HTML alt tags, for translation according to the reader's native language.

for HTML & PRINT: 11607 `\begin{warpall}`

`\AltTextOpen` The opening part of HTML alt tag for an image. The default is a left parenthesis.
Default: (

```
11608 \newcommand*\AltTextOpen}{(}
```

`\AltTextClose` The closing part of HTML alt tag for an image. The default is a right parenthesis.
Default:)

```
11609 \newcommand*\AltTextClose}{)}
```

`\ImageAltText` The HTML alt tag for an image.
Default: image

```
11610 \newcommand*\ImageAltText}{image}
```

`\MathImageAltText` The HTML alt tag for an SVG math image.

Default: “math image”

```
11611 \newcommand*\MathImageAltText}{math image}
```

`\LWR@ThisAltText` The HTML alt tag for the next image. Cleared after use, and also after each `lateximage`, `\LWR@subsingledollar`, and each use of `MATHJAX`.

```
11612 \newcommand*\LWR@ThisAltText}{}
```

`\ThisAltText` $\langle text \rangle$

Assigns the HTML alt tag for the next image generated by `lwarp`, such as a `lateximage`, `picture`, or SVG math.

```
11613 \newcommand*\ThisAltText}[1]{%
11614   \renewcommand{\LWR@ThisAltText}{#1}%
11615 }
```

`\PackageDiagramAltText` Appended to the `lateximage` HTML alt tag for the images generated by many packages.

Default: “diagram”

```
11616 \newcommand*\PackageDiagramAltText}{diagram}
```

```
11617 \end{warpall}
```

83.3 Inline and display math

for HTML output: 11618 `\begin{warpHTML}`

Ctrl `LWR@externalfilecnt` Counter for the external files which are generated and then referenced from the HTML:

```
11619 \newcounter{LWR@externalfilecnt}
```

Bool `LWR@indisplaymathimage` True if processing display math for SVG output. Inside a `lateximage`, display math is only set to print-mode output if `LWR@indisplaymathimage` is false. Used to avoid nullifying display math before it has been completed.

```
11620 \newbool{LWR@indisplaymathimage}
```

Bool `LWR@insidemathcomment` True while inside an HTML comment which is displaying a math environment. Used to undo the comment for a moment while creating a `\label`, so that the label’s HTML tags will be seen by HTML.

```
11621 \newbool{LWR@insidemathcomment}
11622 \boolfalse{LWR@insidemathcomment}
```

Bool `LWR@xfakebold` True if `xfakebold \setBold` is in use.

```
11623 \newbool{LWR@xfakebold}
11624 \boolfalse{LWR@xfakebold}
```

`\LWR@orig@setBold` Redefined by `lwarp-xfakebold`.

```
11625 \newcommand*\LWR@orig@setBold{}
```

`\LWR@orig@unsetBold` Redefined by `lwarp-xfakebold`.

```
11626 \newcommand*\LWR@orig@unsetBold{}
```

`\LWR@applyxfakebold` Redefined by `lwarp-xfakebold`.

```
11627 \newcommand*\LWR@applyxfakebold{}
```

`\LWR@setcurrentfont` Sets the actual L^AT_EX font to that which was selected for HTML output. Ex: In HTML mode, `\bfseries` sets `\LWR@f@series` to “bf”. This sets the PDF output here for use inside a `lateximage`.

```
11628 \newcommand*\LWR@setcurrentfont}{%
11629   \LWR@traceinfo{Using font family \LWR@f@family}%
11630   \@nameuse{\LWR@print@\LWR@f@family family}%
11631   \LWR@traceinfo{Using font series \LWR@f@series}%
11632   \@nameuse{\LWR@print@\LWR@f@series series}%
11633   \LWR@traceinfo{Using font shape \LWR@f@shape}%
11634   \@nameuse{\LWR@print@\LWR@f@shape shape}%
11635   \LWR@traceinfo{Using font caps shape \LWR@f@shapecaps}%
11636   \@nameuse{\LWR@print@\LWR@f@shapecaps shape}%
11637 }
```

`\$`

Plain dollar signs appearing in the HTML output may be interpreted by MATHJAX to be math shifts. For a plain text dollar `\$`, use an HTML entity to avoid it being interpreted by MATHJAX, unless are inside a `lateximage`, in which case it will not be seen by MATHJAX.

```
11638 \let\LWR@origtextdollar\$
11639
11640 \renewcommand*\{\$}{%
11641   \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}%
11642     {\LWR@origtextdollar}%
11643     {\HTMLUnicode{00024}}%
11644 }
```

File

`lwarp_baseline_marker.png`

File

`lwarp_baseline_marker.eps`

A marker to be used to help *pdfcrop* identify the inline math baseline and width. If either `graphicx` or `graphics` is loaded, this marker is placed at the lower left and lower right corners of the inline math. *pdfcrop* is then able to identify the width of the image, and also the height of an image such as a horizontal dash which does not otherwise touch the baseline.

A marker with alpha or opacity of 0% is not registered by *pdfcrop*, so the marker is a small square block of 1% alpha, which seems to work while still being effectively invisible in the final svg image.

If `graphicx` is loaded, this marker is sized as a tiny 1 sp square. If `graphics` is loaded, this marker is used at its default size of around .25 pt. If neither `graphics` package is loaded, the marker is replaced by a 10 sp horizontal space, and there is no assistance for determining baseline or width of the inline math image. The best results are obtained when using `graphicx`.

`\LWR@addbaselinemarker` Places a small marker in an SVG inline image. If `graphics` or `graphicx` are loaded, the marker is a mostly transparent image. If neither is loaded, no marker is used.

```

11645 \AtBeginDocument{
11646
11647 \ifpdf
11648   \newcommand*\LWR@baselinename{\lwarp_baseline_marker.png}
11649 \else
11650   \ifXeTeX
11651     \newcommand*\LWR@baselinename{\lwarp_baseline_marker.png}
11652   \else
11653     \newcommand*\LWR@baselinename{\lwarp_baseline_marker.eps}
11654   \fi
11655 \fi
11656
11657 \IfFileExists{\LWR@baselinename}%
11658 {
11659   \IfPackageLoadedTF{graphicx}{
11660     \newcommand*\LWR@addbaselinemarker}{%
11661       \LWR@originincludegraphics{\LWR@baselinename}%
11662     }
11663   }{
11664     \IfPackageLoadedTF{graphics}{
11665       \newcommand*\LWR@addbaselinemarker}{%
11666         \LWR@originincludegraphics{\LWR@baselinename}%
11667       }
11668     }{
11669       \newcommand*\LWR@addbaselinemarker}{%
11670         \global\booltrue{\LWR@warnbaselinemarker}%
11671       }
11672     \AtEndDocument{
11673       \ifbool{\LWR@warnbaselinemarker}{
11674         \PackageNoteNoLine{\lwarp}{%
11675           Load graphicx or graphics for improved\MessageBreak
11676           SVG math sizing and baselines%
11677         }
11678       }{}
11679     }
11680   }
11681 }
11682 }{% lwarp_baseline_marker.png or .eps is not present
11683   \newcommand*\LWR@addbaselinemarker}{%
11684     \global\booltrue{\LWR@warnbaselinemarker}%
11685   }
11686 \AtEndDocument{
11687   \ifbool{\LWR@warnbaselinemarker}{
11688     \PackageWarningNoLine{\lwarp}{%
11689       File \LWR@baselinename\space is not installed\MessageBreak
11690       alongside the lwarp-*.sty files, so\MessageBreak
11691       SVG math sizing and baselines may not be accurate}
11692   }{}
11693 }
11694 }
11695
11696 }% AtBeginDocument

```

Bool `LWR@warnbaselinemarker` True if the math baseline marker was ever called for, but `graphics` or `graphicx` were

not loaded.

```
11697 \newbool{LWR@warnbaselinemarker}
11698 \boolfalse{LWR@warnbaselinemarker}
```

Bool LWR@unknownmathsize If Tikz or other objects are used inside math mode, the resulting image may exceed the TEX box, resulting in an incorrect measurement of the size of the resulting image. If this is so, the HTML styles for image size and depth will be neutralized.

```
11699 \newbool{LWR@unknownmathsize}
```

\LWR@singledollarmeasure $\langle \mathit{expression} \rangle$

Measures the size of the image of the math expression.

(In some circumstances SVG math is used even if MATHJAX is preferred.)

SVG math: \LWR@origensuredmath is part of argument #4.

SVG math \ensuremath: \LWR@origensuredmath is part of argument #4.

SVG dynamic math: \LWR@origensuredmath is part of argument #4.

MATHJAX: Argument #4 is the contents of the math expression without \LWR@origensuredmath. This case is handled above.

MATHJAX \ensuremath: \LWR@origensuredmath is part of argument #4.

MATHJAX dynamic math: Argument #4 is the contents of the math expression without \LWR@origensuredmath, so \LWR@origensuredmath is added below.

\ifmmode: Included “just in case”.

Factored from \LWR@subsingledollarsvg.

```
11700 \newcommand*{\LWR@singledollarmeasure}[1]{%
11701   \begingroup%
```

Temporarily disable formatting while measuring the image parameters:

```
11702   \LWR@restoreorigformatting%
11703   \RenewDocumentEnvironment{lateximage}{s o s o o d()}{}{}% inside group
11704   \LWR@print@normalsize%
```

Temporarily set font for the HTML PDF output:

```
11705   \LWR@setcurrentfont%
```

lateximagedepth must be nested to avoid generating paragraph tags. $\mathcal{M}\mathcal{S}$ math modifies the \text macro such that \addtocounter does not always occur as expected. Lower-level code is used instead.

```
11706   \global\advance\c@LWR@lateximagedepth 1\relax%
```

Typeset the math in a box. While doing so, some macros or environments may set LWR@unknownmathsize, in which case this will be used to cancel the HTML styles being generated here.

```

11707 \boolfalse{LWR@unknownmathsize}%
11708 \ifmode%
11709   \global\abox{\LWR@singledollarbox}{#1}%
11710 \else%
11711   \ifbool{LWR@dynamicmath}{%
11712     \ifbool{mathjax}{%
11713       \global\abox{\LWR@singledollarbox}%
11714         {\LWR@origensuredmath{#1}}%
11715     }{%
11716       \global\abox{\LWR@singledollarbox}{#1}%
11717     }%
11718   }{%
11719     \global\abox{\LWR@singledollarbox}{#1}%
11720   }%
11721 \fi%

```

Add a small and almost transparent marker at the depth of the image.

A math minus sign has the same depth as a plus, even though it does not draw anything below the baseline. This means that *pdfcrop* would crop the image without depth. The marker below the baseline is seen by *pdfcrop* and preserves the depth.

```

11722 \global\abox{\LWR@singledollarbox}{%
11723   \usebox{\LWR@singledollarbox}%
11724   \raisebox{-\dp\LWR@singledollarbox}{%
11725     \LWR@addbaselinemarker%
11726   }%
11727 }%

```

More low-level code to undo the counter change.

```

11728 \global\advance\c@LWR@lateximagedepth -1\relax% Due to AmS \text macro.

```

Measure the depth:

```

11729 \setlength{\LWR@singledollardepth}{%
11730   \LateximageFontScale\dp\LWR@singledollarbox%
11731 }%

```

Make the length a global change:

```

11732 \global\LWR@singledollardepth=\LWR@singledollardepth%

```

Likewise for width:

```

11733 \setlength{\LWR@singledollarwidth}{%
11734   \LateximageFontScale\wd\LWR@singledollarbox%
11735 }%
11736 \global\LWR@singledollarwidth=\LWR@singledollarwidth%

```

Likewise for total height:

```

11737 \setlength{\LWR@singledollarheight}{%
11738   \LateximageFontScale\ht\LWR@singledollarbox%
11739 }%
11740 \addtolength{\LWR@singledollarheight}{%
11741   \LateximageFontScale\dp\LWR@singledollarbox%

```

```

11742 }%
11743 \global\LWR@singledollarheight=\LWR@singledollarheight%

11744 \endgroup%
11745 }

```

`\LWR@subsingledollarsvg` * $\langle 2: \textit{alt text} \rangle \langle 3: \textit{add'l hashing} \rangle \langle 4: \textit{math expression} \rangle$

For inline math. Uses svg math. The image is measured and adjusted to the baseline of the HTML output, and placed inside a `lateximage`.

(In some circumstances SVG math is used even if `MATHJAX` is preferred.)

Factored from `\LWR@subsingledollar`.

```

11746 \newcommand*\LWR@subsingledollarsvg[4]{%
11747   \LWR@traceinfo{\LWR@subsingledollarsvg}%

```

Measure the depth, width, and height of the math image:

```

11748   \LWR@singledollarmeasure{#4}%

```

Set a style for the the height or width. The em unit is used so that the math scales according to the user's selected font size.

Start with the greater of the width or the height, biased towards the width:

```

11749   \ifdimgreater{\LWR@singledollarwidth}{.7\LWR@singledollarheight}{%
11750     \def\LWR@singledollarstyle{%
11751       width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
11752     }%
11753   }{%
11754     \def\LWR@singledollarstyle{%
11755       height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
11756     }%
11757   }%

```

If a very narrow width, use the height.

```

11758   \ifdimless{\LWR@singledollarwidth}{.2em}%
11759   {%
11760     \def\LWR@singledollarstyle{%
11761       height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
11762     }%
11763   }%
11764   {}%

```

If very wide and short, use the width:

```

11765   \ifdimless{\LWR@singledollarheight}{.2em}%
11766   {%
11767     \def\LWR@singledollarstyle{%
11768       width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
11769     }%
11770   }%
11771   {}%

```

If there is significant text depth, add the depth to the style.

```

11772 \ifdimgreater{\LWR@singledollardepth}{0.05ex}{%
11773   \def\LWR@singledollardepthstyle{%
11774     \ ; % extra space
11775     \LWR@print@embox{%
11776       vertical-align:-\LWR@convertto{em}{\the\LWR@singledollardepth} em%
11777     } % extra space
11778   }%
11779 }{%
11780 \def\LWR@singledollardepthstyle{}%
11781 }%

```

If using certain Tikz actions inside math, the resulting image may exceed the T_EX boundaries, so the HTML size styles may be incorrect, and must be neutralized.

```

11782 \ifbool{\LWR@unknownmathsize}{%
11783   \def\LWR@singledollarstyle{}%
11784   \def\LWR@singledollardepthstyle{}%
11785 }{%

```

Create the lateximage using the alternate tag and the computed size and depth. The star causes lateximage to use an MD5 hash as the filename. When hashing, also include the current font and color in the hash.

```

11786 \ifbool{\LWR@dynamicmath}{%
11787   \LWR@traceinfo{subsingledollarsvg: dynamic}%
11788   \begin{lateximage}% no hashing
11789     [\MathImageAltText]% alt tag
11790     []% no add'l hashing
11791     [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
11792     (math)% ARIA
11793   }{% not dynamic math
11794     \LWR@traceinfo{subsingledollarsvg: static}%
11795     \IfValueTF{#1}{% #1 True
11796       \LWR@findcurrenttextcolor% sets \LWR@tempcolor

```

Support for xfakebold:

```

11797 \ifbool{\LWR@xfakebold}%
11798   {\def\LWR@tempone{Y}}%
11799   {\def\LWR@tempone{N}}%

11800 \LWR@traceinfo{subsingledollarsvg about to lateximage}%
11801 \begin{lateximage}*% use hashing
11802   [#2]% alt
11803   *% do not add open/closing braces
11804   [% addl' hashing
11805     #3%
11806     FM\LWR@family%
11807     SR\LWR@series%
11808     SH\LWR@shape%
11809     SHC\LWR@shapecaps%
11810     CL\LWR@tempcolor%
11811     FB\LWR@tempone% xfakebold
11812   ]%
11813   [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
11814   (math)% ARIA
11815   \LWR@traceinfo{subsingledollar did lateximage}%
11816 }{% #1 False
11817   \begin{lateximage}% no hashing

```

```

11818             [#2]% alt
11819             []% no add'l hashing
11820             [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
11821             (math)% ARIA
11822             }%
11823             }% not dynamic math

```

Place small and almost transparent markers on the baseline at the left and right edges of the image. These markers are seen by *pdfcrop*, and force vertically-centered objects such as a dash to be raised off the baseline in the cropped image, and also force the total width and left/right margins to be correct. (Except that in some fonts a character may exceed the bounding box, and thus may appear wider than expected when converted to an image.)

```
11824 \LWR@addbaselinemarker%
```

Support for `xfakebold`:

```
11825 \LWR@applyxfakebold%
```

Typeset the contents:

```
11826 \usebox{\LWR@singledollarbox}%
```

The closing baseline marker:

```
11827 \LWR@addbaselinemarker%
```

```
11828 \end{lateximage}%
```

```
11829 %
```

```
11830 }
```

```
\LWR@subsingledollar *{\langle 2: alt text \rangle}{\langle 3: add'l hashing \rangle}{\langle 4: math expression \rangle}
```

For inline math. Uses `MATHJAX`, or for `SVG` math the image is measured and adjusted to the baseline of the `HTML` output, and placed inside a `lateximage`.

SVG math: `\LWR@origensuredmath` is part of argument #4.

SVG math \ensuremath: `\LWR@origensuredmath` is part of argument #4.

SVG dynamic math: `\LWR@origensuredmath` is part of argument #4.

MATHJAX: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`. This case is handled above.

MATHJAX \ensuremath: `\LWR@origensuredmath` is part of argument #4.

MATHJAX dynamic math: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`, so `\LWR@origensuredmath` is added below.

[image filename hashing](#) If starred, a hashed filename is used. If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated T_EX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is used in the additional hashing argument to ensure a unique image.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple alt tag is still the same.

```

11831 \newlength{\LWR@singledollarwidth}
11832 \newlength{\LWR@singledollarheight}
11833 \newlength{\LWR@singledollardepth}
11834
11835 \newsavebox{\LWR@singledollarbox}
11836
11837 \NewDocumentCommand{\LWR@subsingledollar}{s m m m}{%
11838   \LWR@traceinfo{LWR@subsingledollar !#2!}%

11839   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
11840   {%
11841     \LWR@traceinfo{LWR@subsingledollar: already in a lateximage}%
11842     #4% contents
11843   }%
11844   {% not in a lateximage
11845     \begingroup%
```

Support for xfakebold:

```

11846   \LWR@applyxfakebold%
```

MATHJAX cannot parse the often complicated T_EX expressions which appear in the various uses of `\ensuredmath`. `\ensuremath` forces the alt tag to “(math image)”, as translated according to `\MathImageAltText`. If this is the case, force the use of a `lateximage` even if MATHJAX. Likewise for `siunitx` if `parse-numbers=false`.

If MATHJAX, or if formatting math for a word processor, and not `\ensuredmath`, and not a dynamic math expression, print the math expression:

```

11847   \ifboolexpr{%
11848     (
11849       bool{mathjax} or
11850       ( bool{FormatWP} and bool{WPMarkMath} )
11851     ) and
11852     ( not test {
11853       \ifstrequal {#2}% from \ensuredmath
11854       {\AltTextOpen\MathImageAltText\AltTextClose}
11855     }
11856     ) and
11857     ( not bool{LWR@dynamicmath} )
11858   }%
```

For MATHJAX, print the math between `\(` and `\)`:

```

11859   {%
11860     \LWR@traceinfo{LWR@subsingledollar: Mathjax}%
11861   {%
11862     \textbackslash(%
11863     {%
```

`\ifmmode` to avoid error about `\ttfamily` inside math mode in the case of nested math, ex. equation with `tcolorbox` with math.

```

11864             \ifmmode\else\LWR@print@ttfamily\fi%
11865             \LWR@HTMLsanitizedetokenized{\detokenize{#4}}%
11866             }%
11867             \textbackslash}%
11868             }%
11869     }% mathjax

```

For svg, print the math inside a `lateximage`, with an `<alt>` tag of the \LaTeX code, and a css style to control the baseline adjustment.

```

11870     {% not mathjax
11871         \LWR@traceinfo{%
11872             LWR@subsingledollar: NOT mathjax, or is ensuremath, or is dynamic%
11873         }%
11874         \LWR@subsingledollarsvg{#1}{#2}{#3}{#4}%
11875     }% not mathjax
11876     \endgroup%
11877 }% not in a lateximage

```

Clear the single-use alt text:

```

11878 \gdef\LWR@ThisAltText{%
11879     \LWR@traceinfo{LWR@subsingledollar: done}%
11880 }

```

```

11881 \LetLtxMacro\LWR@origdollar$
11882 \LetLtxMacro\LWR@secondorigdollar$% balance for editor syntax highlighting

```

```

11883 \LetLtxMacro\LWR@origopenparen\
11884 \LetLtxMacro\LWR@origcloseparen\
11885 \LetLtxMacro\LWR@origopenbracket\[
11886 \LetLtxMacro\LWR@origclosebracket\

```

\$ Redefine the dollar sign to place math inside a `lateximage`, or use `MATHJAX`:
\$\$

```

11887 \begingroup
11888 \catcode'\$=\active%
11889 \protected\gdef$\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%

```

Used by `chemformula` to escape single-dollar math:

```

11890 \protected\gdef\LWR@newsingledollar{\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%

```

`\LWR@doubledollar` Redefine the double dollar sign to place math inside a `lateximage`, or use `MATHJAX`:

```

11891 \protected\gdef\LWR@doubledollar$#1$${%

```

If `MATHJAX` or formatting for a word processor, print the \LaTeX expression:

```

11892     \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%

```

For `MATHJAX`, print the math between `\[` and `\]`. If there is a footnote, endnote, or other kind of note ('note' is present), sync the note numbers.

```

11893   {% intentional blank line:
11894
11895       \IfSubStr{\detokenize\expandafter{#1}}{\detokenize{note}}{%

```

The equation is printed to the PDF output inside HTML comment tags. This allows labels and footnotes to be accepted and processed. The math environment is selected here, and `\LWR@hidelatexequation` will use the original print-mode meaning of math.

```

11896       \LWR@hidelatexequation{math}{#1}%

11897       \InlineClass{hidden}{\LWR@syncnotenumbers}%
11898       \textbackslashash[%
11899       {%
11900           \LWR@print@ttfamily%
11901           \LWR@HTMLsanitizedetokenized{\detokenize{#1}}%
11902       }%
11903       \textbackslashash]
11904       \InlineClass{hidden}{\LWR@syncnotenames}%
11905   }{%
11906       \textbackslashash[%
11907       {%
11908           \LWR@print@ttfamily%
11909           \LWR@HTMLsanitizedetokenized{\detokenize{#1}}%
11910       }%
11911       \textbackslashash]
11912   }%
11913
11914   }% mathjax

```

For svg, print the math inside a `lateximage`, with an `<alt>` tag of the L^AT_EX code:

```

11915   {% not mathjax
11916       \begin{BlockClass}{displaymath}%
11917       \LWR@newautoidanchor%
11918       \booltrue{\LWR@indisplaymathimage}%
11919       \begin{lateximage}%
11920       [%
11921           \textbackslashash{[] % extra space
11922           \LWR@HTMLsanitizedetokenized{\detokenize{#1}} % extra space
11923           \textbackslashash{]}}%
11924       ]%
11925       *% do not add open/closing braces
11926       (math)% ARIA

```

Support for `xfakebold`:

```

11927       \LWR@applyxfakebold%

11928       \LWR@origdollar\LWR@origdollar#1\LWR@origdollar\LWR@origdollar%
11929       \end{lateximage}%
11930       \end{BlockClass}%
11931   }% not mathjax

```

Clear the single-use alt text:

```
11932 \gdef\LWR@ThisAltText{%
11933 }%
```

`\LWR@singledollar` $\langle\mathit{expression}\rangle$

```
11934 \protected\gdef\LWR@singledollar#1${%
11935   \LWR@traceinfo{LWR@singledollar}%
11936   \ifbool{mathjax}{%
11937     \LWR@subsingledollar*%
11938     {% alt tag
11939       \textbackslash( %
11940       \LWR@HTMLsanitizedetokenized{\detokenize{#1}} % extra space
11941       \textbackslash)%
11942     }%
11943     {singledollar}% add'l hashing
11944     {#1}% contents
11945   }{% not mathjax
11946     \LWR@subsingledollar*%
11947     {% alt tag
11948       \textbackslash( %
11949       \LWR@HTMLsanitizedetokenized{\detokenize{#1}} % extra space
11950       \textbackslash)%
11951     }%
11952     {singledollar}% add'l hashing
11953     {\LWR@origensuredmath{#1}}% contents
11954   }% not mathjax
```

Clear the single-use alt text:

```
11955 \gdef\LWR@ThisAltText{%
11956 }
```

`\(` Redefine to the above dollar macros.

```
\[
11957 \AtBeginDocument{
11958   \protected\gdef\(#1\){$#1$}
11959   \protected\gdef\[#1\]{$$#1$$}
11960 }
11961
11962 \endgroup% active $
```

```
11963 \AtBeginDocument{
11964 \LetLtxMacro\LWR@openbracketnormal\[
11965 \LetLtxMacro\LWR@closebracketnormal\]
11966 }
```

`\@ensuredmath` $\langle\mathit{expression}\rangle$

If MATHJAX, a `lateximage` is used, since `\ensuremath` is often used for complex TEX expressions which MATHJAX may not render. If `svg math`, a hashed file is used with a simple alt tag, but additional hashing provided by the contents.

```
11967 \LetLtxMacro\LWR@origensuredmath\@ensuredmath
11968
11969 \renewcommand{\@ensuredmath}[1]{%
11970   \ifbool{mathjax}{%
11971     \LWR@subsingledollar*\AltTextOpen\MathImageAltText\AltTextClose}%
```

```

11972      {%
11973      \protect\LWR@HTMLsanitizedetokenized{\detokenize\expandafter{#1}}%
11974      }%
11975      {%
11976          \relax%
11977          \LWR@origensuredmath{#1}%
11978      }%
11979  }{% SVG math

```

If already inside a `lateximage` in math mode, continue as-is.

```

11980      \ifmmode%
11981          \LWR@origensuredmath{#1}%
11982      \else%

```

Create an inline math `lateximage` with a simple `alt` tag and additional hashing according to the contents.

```

11983          \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
11984              {\LWR@origensuredmath{#1}}%
11985          {%
11986              \LWR@subsingledollar*%
11987              {\AltTextOpen\MathImageAltText\AltTextClose}%
11988          {%
11989              \protect\LWR@HTMLsanitizedetokenized{%
11990                  \detokenize\expandafter{#1}%
11991              }%
11992          }%
11993          {\LWR@origensuredmath{#1}}%
11994      }%
11995  \fi%
11996  }%

```

Clear the single-use `alt` text:

```

11997      \gdef\LWR@ThisAltText{}%
11998  }

```

Remember then remove the old `math` and `displaymath` environments:

```

11999 \let\LWR@orig@math\math
12000 \let\LWR@orig@endmath\endmath
12001
12002 \let\LWR@orig@displaymath\displaymath
12003 \let\LWR@orig@enddisplaymath\enddisplaymath
12004
12005 \let\math\relax
12006 \let\endmath\relax
12007
12008 \let\displaymath\relax
12009 \let\enddisplaymath\relax

```

Env `math` Set math mode then typeset the body of what was between the `begin/end`. See the `environ` package for `\BODY`.

```

12010 \NewEnviron{math}{\expandafter\(\BODY\)}

```

Env LWR@displaymathnormal Set math mode then typeset the body of what was between the begin/end. See the `environ` package for `\BODY`.

```
12011 \NewEnviron{LWR@displaymathnormal}{\expandafter\[\BODY\]\@ignoretrue}
```

Set the default `displaymath` to the normal version:

```
12012 \LetLtxMacro\displaymath\LWR@displaymathnormal%
12013 \LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
```

Env LWR@displaymathother A version of `displaymath` which can handle complicated objects, but does not supply `MATHJAX` or `HTML alt` tags.

```
12014 \newenvironment{LWR@displaymathother}
12015 {%
12016   \begin{BlockClass}{displaymath}%
12017   \LWR@newautoidanchor%
12018   \booltrue{LWR@indisplaymathimage}%
12019   \begin{lateximage}[\MathImageAltText](math)% [alt](ARIA)
12020   \LWR@origdollar\LWR@origdollar%
12021 }
12022 {%
12023   \LWR@origdollar\LWR@origdollar%
12024   \end{lateximage}%
12025   \end{BlockClass}%
12026 }
```

Env LWR@equationother A version of `displaymath` which can handle complicated objects, but does not supply `MATHJAX` or `HTML alt` tags.

```
12027 \newenvironment{LWR@equationother}
12028 {%
12029   \begin{BlockClass}{displaymathnumbered}%
12030   \LWR@newautoidanchor%
12031   \booltrue{LWR@indisplaymathimage}%
12032   \begin{lateximage}[\MathImageAltText](math)% [alt](ARIA)
12033   \LWR@orig@equation%
12034 }
12035 {%
12036   \LWR@orig@endequation%
12037   \end{lateximage}%
12038   \end{BlockClass}%
12039 }
```

83.4 MATHJAX support

Ctrl LWR@nextequation Used to add one to compute the next equation number.

```
12040 \newcounter{LWR@nextequation}
```

Determining how to set `MATHJAX` section and equation numbers. Adjusts for various kinds of `\theequation` to determine `\theMathJaxsection` and `\theMathJaxequation`.

```
12041 \newcommand\LWR@article@theequation{\@arabic\c@equation}
12042
```

```

12043 \newcommand\LWR@book@theequation
12044 {\ifnum \c@chapter>\z@ \thechapter.\fi \@arabic\c@equation}
12045
12046
12047 \newcommand\LWR@chapter@theequation{\thechapter.\arabic{equation}}
12048 \newcommand\LWR@section@theequation{\thesection.\arabic{equation}}
12049 \newcommand\LWR@subsection@theequation{\thesubsection.\arabic{equation}}
12050
12051 \AtBeginDocument{
12052   % default per article class:
12053   \newcommand*\theMathJaxsubequations{}{0}
12054   \newcommand*\theMathJaxsection{}{}
12055   \newcommand*\theMathJaxequation{\arabic{equation}}
12056
12057   \ifdefstrequal{\theequation}{\LWR@article@theequation}
12058   {}{
12059     \ifdefstrequal{\theequation}{\LWR@book@theequation}{
12060       \renewcommand*\theMathJaxsection{\ifnum \c@chapter>\z@ \thechapter.\fi}
12061     }{
12062       \ifdefstrequal{\theequation}{\LWR@subsection@theequation}{
12063         \renewcommand*\theMathJaxsection{\thesubsection}{.}
12064       }{
12065         \ifdefstrequal{\theequation}{\LWR@section@theequation}{
12066           \renewcommand*\theMathJaxsection{\thesection}{.}
12067         }{
12068           \ifdefstrequal{\theequation}{\LWR@chapter@theequation}{
12069             \renewcommand*\theMathJaxsection{\thechapter}{.}
12070           }{% unknown format
12071             \PackageWarningNoLine{lwarp}
12072             {%
12073               Unknown equation tag format for \protect\theequation.\MessageBreak
12074               Article-style equation numbering will be used%
12075             }
12076           }}}}
12077 }

```

`\LWR@synchronmathjax` Sets the MATHJAX equation format and number for the following equations.

These MATHJAX commands are printed inside “\(" and “\)” characters. They are printed to HTML output, not interpreted by L^AT_EX.

```
12078 \newcommand*\LWR@synchronmathjax}{%
```

Tell MATHJAX that the next equation number is the current L^AT_EX equation number.

Before each equation, lwarp inserts into the HTML code:

```
\setequationnumber{subequations?}{section}{number}
```

subequations? is 0 usually, 1 if inside amsmath subequations.

section is a string printed as-is, or empty.

number is auto-incremented by MATHJAX between equations.

Place the MATHJAX command inside “\(" and “\)” characters, to be printed to HTML, not interpreted by L^AT_EX.

```

12079     \LWR@stoppars%
12080     \InlineClass{hidden}{
12081         \textbackslash{
12082         \textbackslash{seteqnumber%
12083         \{\theMathJaxsubequations\}%
12084         \{\theMathJaxsection\}%
12085         \{\theMathJaxequation\}%
12086         \textbackslash}%
12087     }
12088     \LWR@startpars%
12089 }

```

`\LWR@hidelatexequation` $\langle environment \rangle$ $\langle contents \rangle$

Creates the L^AT_EX version of the equation inside an HTML comment.

```
12090 \NewDocumentCommand{\LWR@hidelatexequation}{m +m}{%
```

Stop HTML paragraph handling and open an HTML comment:

```

12091     \LWR@stoppars
12092     \LWR@htmlopencomment
12093

```

Start the L^AT_EX math environment inside the HTML comment:

```

12094     \begingroup
12095     \@nameuse{LWR@orig@#1}

```

While in the math environment, restore various commands to their L^AT_EX meanings.

```

12096     \LWR@restoreorigformatting
12097     \booltrue{LWR@insidemathcomment}

```

Temporarily prevent underfull `\hbox` warnings.

```
12098     \hbadness=10000\relax%
```

See `\LWR@htmlmathlabel` in section [83.7.1](#).

Print the contents of the equation:

```
12099     #2
```

End the L^AT_EX math environment inside the HTML comment:

```

12100     \@nameuse{LWR@orig@end#1}
12101     \endgroup
12102

```

Close the HTML comment and resume HTML paragraph handling:

```

12103     \LWR@htmlclosecomment
12104     \boolfalse{LWR@insidemathcomment}
12105     \LWR@startpars
12106 }

```

```
\LWR@addmathjax {<environment name>} {<contents>}
```

Given the name of a math environment and its contents, create a MATHJAX instance. The contents are printed to HTML output, not interpreted by L^AT_EX.

```
12107 \NewDocumentCommand{\LWR@addmathjax}{m +m}{%
```

```
12108   \LWR@origtilde\LWR@orignewline
```

Enclose the MATHJAX environment inside printed “\(" and “\)” characters. Print the environment name and contents, sanitizing for HTML special characters.

```
12109   {%
12110     \LWR@print@ttfamily%
12111     \textbackslash{}begin\{#1\}
```

The alignat environment takes a mandatory argument, which must be replicated here.

```
12112     \ifboolexpr{
12113       test {\ifstrequal{#1}{alignat}} or
12114       test {\ifstrequal{#1}{alignat*}} or
12115       test {\ifstrequal{#1}{alignat+}}
12116     }%
12117     {\{\arabic{LWR@maxfields@}\}}%
12118     {}%
```

The environment contents and \end:

```
12119     \LWR@orignewline%
12120     \LWR@HTMLsanitizeexpanded{\detokenize\expandafter{#2}}%
12121     \LWR@orignewline%
12122     \textbackslash{}end\{#1\}
12123   }%

12124   \LWR@orignewline
12125 }
```

83.5 Equation environment

Remember existing equation environment, after redefined by amsmath, if loaded.

```
12126 \AtBeginDocument{
12127   \let\LWR@orig@equation\equation
12128   \let\LWR@orig@endequation\endequation
12129   \csletcs{LWR@orig@equation*}{equation*}
12130   \csletcs{LWR@orig@endequation*}{endequation*}
12131 }
```

```
\LWR@doequation {<env contents>} {<env name>}
```

For SVG math output, the contents are typeset using the original equation inside a lateximage, along with an <alt> tag containing a detokenized copy of the L^AT_EX source for the math.

For MATHJAX output, the contents are typeset in an original equation environment placed inside a HTML comment, with special processing for \labels. The contents are also printed to the HTML output for processing by the MATHJAX script.

```
12132 \newcommand*{\LWR@doequation}[2]{%
12133
```

If mathjax or FormatWP, print the L^AT_EX expression:

```
12134 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

MATHJAX output:

```
12135 {
```

Print commands to synchronize MATHJAX's equation number and format to the current L^AT_EX chapter/section and equation number:

```
12136 \LWR@syncmathjax%
```

Print the L^AT_EX math inside an HTML comment:

```
12137 \LWR@hidelatexequation{#2}{#1}
12138 }
```

SVG output: Create the lateximage along with an HTML <alt> tag having an equation number, the L^AT_EX equation environment commands, and the contents of the environment's \BODY.

```
12139 {% not mathjax
```

Begin the lateximage with an <alt> tag containing the math source:

```
12140 \ifstrequal{#2}{equation*}{%
12141 \begin{BlockClass}{displaymath}%
12142 }{%
12143 \begin{BlockClass}{displaymathnumbered}%
12144 }%
12145 \LWR@newautoidanchor%
12146 \booltrue{\LWR@indisplaymathimage}%
12147 \begin{lateximage}[%
12148 \ifstrequal{#2}{equation*}{%
12149 \ifdefequal{\LWR@equationtag}{\theequation}{%
12150 % no tag was given
12151 }{%
12152 (\LWR@equationtag) % tag was given
12153 }%
12154 }{%
12155 (\LWR@equationtag) % automatic numbering
12156 }%
12157 \textbackslash{begin\{#2\}} % extra space
12158 \LWR@HTMLsanitizeexpanded{\detokenize\expandafter{#1}} % extra space
12159 \textbackslash{end\{#2\}}%
12160 ]*(math)% alt tag, ARIA
```

Support for xfakebold:

```
12161 \LWR@applyxfakebold%
```

Create the actual L^AT_EX-formatted equation inside the lateximage using the contents of the environment.

```

12162     \@nameuse{LWR@orig#2}%
12163     #1% contents collected by \collect@body
12164     \@nameuse{LWR@orig@end#2}%
12165     \end{lateximage}%
12166     \end{BlockClass}%
12167 }% not mathjax

```

Clear the single-use alt text:

```

12168 \gdef\LWR@ThisAltText{}%
12169 }

```

After the environment, if MATHJAX, print the math to the HTML output for MATHJAX processing. If a footnote is used, sync the footnote counter before, then unsync after for non-equation environments, as defined next.

```

12170 \newcommand*\LWR@doendequation}[1]{%
12171 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
12172   {%
12173     \IfSubStr{\detokenize\expandafter{\BODY}}{\detokenize{note}}{%
12174       \InlineClass{hidden}{\LWR@syncnotenumbers}%
12175       \LWR@addmathjax{#1}{\BODY}%
12176       \InlineClass{hidden}{\LWR@syncnotenames}%
12177     }{%
12178       \LWR@addmathjax{#1}{\BODY}%
12179     }%
12180   }{%
12181

```

Clear the single-use alt text:

```

12182 \gdef\LWR@ThisAltText{}%
12183 }

```

The following are used to synchronize footnote marks and related to MATHJAX if *note* is used inside the MATHJAX expression. The counter is read from L^AT_EX then defined into MATHJAX for use during the following equation. After the equation, the MATHJAX value is returned to the text from \footnotename. Other notes may be added by appending to \LWR@syncnotenumbers and \LWR@syncnotenames.

`\LWR@synconenotenum` {<MathJax variable>} {<mark>}

```

12184 \newcommand*\LWR@synconenotenum}[2]{%
12185 \textbackslash(
12186 \textbackslash)}def\textbackslash{#1\{#2\}
12187 \textbackslash)
12188 }

```

`\LWR@syncnotenumbers` Assignments to make.

```

12189 \newcommand*\LWR@syncnotenumbers{\LWR@synconenotenum[LWRfootnote]{\thefootnote}}

```

`\LWR@synconenotename` {<MathJax variable>} {<text>}

```

12190 \newcommand*\LWR@synconenotename}[2]{%
12191   \textbackslash(
12192   \textbackslash{def\textbackslash{#1name\{#2\}
12193   \textbackslash)
12194 }

```

`\LWR@syncnotenames` Assignments to make.

```

12195 \newcommand*\LWR@syncnotenames{\LWR@synconenotename{LWRfootnote}{\footnotename}}

```

Remove existing equation environment:

```

12196 \AtBeginDocument{
12197   \let\equation\relax
12198   \let\endequation\relax
12199   \csletcs{equation*}{relax}
12200   \csletcs{endequation*}{relax}
12201 }

```

Env `equation` The new equation environment is created with `\NewEnviron` (from the `environ` package), which stores the contents of its environment in a macro called `\BODY`.

```

12202 \AtBeginDocument{
12203   \NewEnviron{equation}%
12204     {\LWR@doequation{\BODY}{equation}}%
12205     [\LWR@doendequation{equation}]
12206
12207   \LetLtxMacro\LWR@equationnormal\equation
12208   \LetLtxMacro\endLWR@equationnormal\endequation
12209 }% AtBeginDocument

```

Env `equation*`

```

12210 \AtBeginDocument{
12211   \NewEnviron{equation*}%
12212     {\LWR@doequation{\BODY}{equation*}}%
12213     [\LWR@doendequation{equation*}]
12214
12215   \csletcs{LWR@equationnormalstar}{equation*}
12216   \csletcs{LWR@endequationnormalstar}{endequation*}
12217 }% AtBeginDocument

```

Remember the “less” version of `equation`, which uses `MATHJAX` and `alt` tags, but does not support complicated contents such as some `Tikz` expressions.

```

12218 \AtBeginDocument{
12219   \LetLtxMacro\LWR@equationless\equation
12220   \LetLtxMacro\endLWR@equationless\endequation
12221   \csletcs{LWR@equationlessstar}{equation*}
12222   \csletcs{LWR@endequationlessstar}{endequation*}
12223 }

```

83.6 `\displaymathnormal` and `\displaymathother`

`\displaymathnormal`

By default, or when selecting `\displaymathnormal`, `MATHJAX` math display envi-

ronments print their contents as text into HTML for MATHJAX to interpret, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Tikz pictures, compilation will fail.

`\displaymathother` When selecting `\displaymathother`, it is assumed that the contents are more complicated than “pure” math. An example is an elaborate Tikz picture, which will not render in MATHJAX and will not make sense as an HTML alt tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Tikz pictures are more likely to compile successfully.

MATHJAX unsupported complicated alt tag

`\displaymathnormal` Use when display math environments have simple math which is to sent to MATHJAX or included in HTML alt tags.

simple math objects

```
12224 \newcommand*{\displaymathnormal}{%
12225   \ifbool{LWR@origmathjax}{\booltrue{mathjax}}{\boolfalse{mathjax}}%
12226   \LetLtxMacro\[\LWR@openbracketnormal%
12227   \LetLtxMacro\]\LWR@closebracketnormal%
12228   \LetLtxMacro\displaymath\LWR@displaymathnormal%
12229   \LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
12230   \LetLtxMacro\equation\LWR@equationnormal%
12231   \LetLtxMacro\endequation\endLWR@equationnormal%
12232   \csletcs{equation*}{LWR@equationnormalstar}%
12233   \csletcs{endequation*}{LWR@endequationnormalstar}%
12234 }
```

`\displaymathother` Use when display math environments have complicated objects which will not work with MATHJAX or should not be included in HTML alt tags. Complicated contents are more likely to compile correctly.

complicated math objects

```
12235 \newcommand*{\displaymathother}{%
12236   \boolfalse{mathjax}%
12237   \LetLtxMacro\displaymath\LWR@displaymathother%
12238   \LetLtxMacro\enddisplaymath\endLWR@displaymathother%
12239   \LetLtxMacro\[\LWR@displaymathother%
12240   \LetLtxMacro\]\endLWR@displaymathother%
12241   \LetLtxMacro\equation\LWR@equationother%
12242   \LetLtxMacro\endequation\endLWR@equationother%
12243   \csletcs{equation*}{displaymath}%
12244   \csletcs{endequation*}{enddisplaymath}%
12245 }
```

```
12246 \end{warpHTML}
```

for PRINT output: 12247 `\begin{warpprint}`

Print-mode versions:

```
12248 \newcommand*{\displaymathnormal}{}
12249 \newcommand*{\displaymathother}{}

12250 \end{warpprint}
```

for HTML output: 12251 `\begin{warpHTML}`

83.7 AMS Math environments

83.7.1 Support macros

Bool LWR@amsmultline

True if processing a multiline environment.

To compensate for multiline-specific code, LWR@amsmultline is used to add extra horizontal space in `\LWR@htmlmathlabel` if is used in an `amsmath` environment which is not a multiline environment and not an equation.

```
12252 \newbool{LWR@amsmultline}
12253 \boolfalse{LWR@amsmultline}
```

`\LWR@beginhideamsmath` Starts hiding L^AT_EX math inside an HTML comment.

```
12254 \newcommand*{\LWR@beginhideamsmath}{
12255   \LWR@stoppars
12256   \LWR@origtilde\LWR@orignewline
12257   \LWR@htmlopencomment
12258
12259   \begingroup
12260   \LWR@restoreorigformatting
```

Temporarily prevent underfull `\hbox` warnings.

```
12261   \hbadness=10000\relax%
12262   \booltrue{LWR@insidemathcomment}
12263 }
```

`\LWR@endhideamsmath` Ends hiding L^AT_EX math inside an HTML comment.

```
12264 \newcommand*{\LWR@endhideamsmath}{
12265   \endgroup
12266
12267   \LWR@htmlclosecomment
12268   \boolfalse{LWR@insidemathcomment}
12269   \LWR@orignewline
12270   \LWR@startpars
12271 }
```

83.7.2 Environment patches

The `amsmath` environments already collect their contents in `\@envbody` for further processing. `eqnarray` is not an $\mathcal{A}\mathcal{M}\mathcal{S}$ package, and thus requires special handling.

For `svg math`: Each environment is encapsulated inside a `lateximage` environment, along with a special optional argument of `\LWR@amsmathbody` or `\LWR@amsmathbodynumbered` telling `lateximage` to use as the HTML `<alt>` tag the environment's contents which were automatically captured by the $\mathcal{A}\mathcal{M}\mathcal{S}$ environment.

For `MATHJAX`: Each environment is synched with L^AT_EX's equation numbers, typeset with L^AT_EX inside an HTML comment, then printed to HTML output for `MATHJAX` to process.

Env eqnarray This environment is not an \mathcal{AMS} environment and thus its body is not automatically captured, so the `environ` package is used to capture the environment into `\BODY`.

```
12272 \let\LWR@origeqnarray\eqnarray
12273 \let\LWR@origendeqnarray\endeqnarray
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
12274 \newbool{LWR@numbereqnarray}
12275 \booltrue{LWR@numbereqnarray}
```

Common code used by `eqnarray` and `Beqnarray` (from `fancybox`):

```
12276 \newcommand{\LWR@eqnarrayfactor}{%
```

If `mathjax` or `FormatWP`, print the \LaTeX expression:

```
12277 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
12278 {%
```

If `MATHJAX`, the environment contents (the `\BODY`) are executed in a `HTML` comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for `MATHJAX` to interpret:

```
12279 \LWR@syncmathjax%
12280 \boolfalse{LWR@amsmultline}%
12281 \ifbool{LWR@numbereqnarray}%
12282 {%
```

If numbering the equations, execute a copy inside an `HTML` comment block:

```
12283 \LWR@beginhideamsmath%
12284 \LWR@origeqnarray%
12285 \BODY%
12286 \LWR@origendeqnarray%
12287 \LWR@endhideamsmath%
```

Then print the (sanitized) contents to the output for `MATHJAX` to interpret:

```
12288 \LWR@addmathjax{eqnarray}{\BODY}%
12289 }%
12290 {% not LWR@numbereqnarray
```

If not numbering equations, just create the contents for `MATHJAX`:

```
12291 \LWR@addmathjax{eqnarray*}{\BODY}%
12292 }% LWR@numbereqnarray
12293 }% mathjax
12294 {% not mathjax
12295 \ifbool{LWR@numbereqnarray}%
12296 {%
```

For numbered `svg` equations, first create a `lateximage` with an `alt` attribute containing sanitized copy of the source code:

```

12297         \begin{BlockClass}{displaymathnumbered}%
12298         \LWR@newautoidanchor%
12299         \booltrue{LWR@indisplaymathimage}%
12300         \begin{lateximage}[(\LWR@startingequationtag\textendash\LWR@equationtag)%
12301         \LWR@addmathjax{eqnarray}{\BODY}]*(\math)%

```

Support for xfakebold:

```

12302         \LWR@applyxfakebold%

```

Create the image contents using an actual eqnarray:

```

12303         \LWR@origeqnarray%
12304         \BODY%
12305         \LWR@origendeqnarray%
12306         \end{lateximage}%
12307         \end{BlockClass}%
12308     }%
12309     {% not LWR@numbreqnarray

```

If not numbered, do the same, but an extra \nonumber seems to be required:

```

12310         \begin{BlockClass}{displaymath}%
12311         \LWR@newautoidanchor%
12312         \booltrue{LWR@indisplaymathimage}%
12313         \begin{lateximage}[(\LWR@addmathjax{eqnarray*}{\BODY})*(\math)%

```

Support for xfakebold:

```

12314         \LWR@applyxfakebold%

12315         \def\@eqnrc{\nonumber\@seqnrc}
12316         \csuse{LWR@origeqnarray}%
12317         \BODY%
12318         \nonumber\csuse{LWR@origendeqnarray}%
12319         \end{lateximage}%
12320         \end{BlockClass}%
12321     }% LWR@numbreqnarray
12322 }% not mathjax

```

Default to number equations in the future:

```

12323     \booltrue{LWR@numbreqnarray}%

```

Clear the single-use alt text:

```

12324     \gdef\LWR@ThisAltText{}%
12325 }

```

eqnarray itself is made with a blank line before and after to force it to be on its own line:

```

12326 \RenewEnvron{eqnarray}
12327 {%
12328
12329 \LWR@eqnarrayfactor
12330
12331 }

```

The starred version is patched to turn off the numbering:

```
12332 \csgpreto{eqnarray*}{\boolfalse{LWR@numbereqnarray}}
```

```
12333 \end{warpHTML}
```

84 Lateximages

84.1 Description

Env lateximage

A `lateximage` is a piece of the document which is typeset in L^AT_EX then included in the HTML output as an image. This is used for math if `svg math` is chosen, and also for the `picture`, `tikzpicture`, and other environments.

Before typesetting the `lateximage` a large number of formatting, graphics, and symbols-related macros are temporarily restored to their print-mode meaning by `\LWR@restoreorigformatting`. (See section 81.)

A `lateximage` is typeset on its own PDF page inside an HTML comment which starts on the preceding page and ends on following page, and instructions are written to `lateximage.txt` for `lwarpmk` to extract the `lateximage` from the page of the PDF file then generate an accompanying `.svg` file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML `` is created to hold both the HTML comment, which will have the `pdftotext` conversion, and also the link to the final `.svg` image.

A L^AT_EX label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

HTML alt tag The HTML `alt` tag is set to the L^AT_EX source for `svg math`, some chemistry expressions, and perhaps some other expressions which make sense for text copy/paste. In some other cases, the `alt` tag is set according to the package name.

When creating an `svg math` image, its HTML `alt` tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the `alt` tag is set to `\MathImageAltText`, along with `\AltTextOpen` and `\AltTextClose`, and the image is not reused.

This `alt` expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “math image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `svg math` images.

For many packages, the output is placed inside a `lateximage` with an HTML `alt` tag set to the package name followed by `\PackageDiagramAltText`. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “diagram”, and may it be changed ac-

ording to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

svg image font size For the `lateximage` environment, the size of the math and text used in the `svg` image may be adjusted by setting `\LateximageFontSizeName` to a font size name—*without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline `svg` math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

84.2 Support counters and macros

for HTML output: 12334 `\begin{warpHTML}`

Ctrl LWR@lateximagenumber Sequence the images.

```
12335 \newcounter{LWR@lateximagenumber}
12336 \setcounter{LWR@lateximagenumber}{0}
```

Ctrl LWR@lateximagedepth Do not create `\lateximage` inside of `\lateximage`.

```
12337 \newcounter{LWR@lateximagedepth}
12338 \setcounter{LWR@lateximagedepth}{0}
```

A few utility macros to write special characters:

```
12339 \edef\LWR@hashmark{\string#} % for use in \write
12340 \edef\LWR@percent{\@percentchar} % for use in \write
```

Ctrl LWR@LIpage Used to reference the PDF page number of a `lateximage` to be written into `<project>-images.txt`.

```
12341 \newcounter{LWR@LIpage}
```

```
12342 \end{warpHTML}
```

84.3 Font size

for HTML & PRINT: 12343 `\begin{warpall}`

`\LateximageFontSizeName` Declares how large to write text in `\lateximages`. The `.svg` file text size should blend well with the surrounding HTML text size.

 **no backslash** Do not include the leading backslash in the name.

```
12344 \newcommand*{\LateximageFontSizeName}{normalsize}
```

`\LateximageFontScale` Declares how large to scale inline svg math images. The .svg file text size should blend well with the surrounding HTML text size. The default is 1, but it may be redefined as needed depending on the HTML font.

```
12345 \newcommand*\LateximageFontScale{1}
12346 \end{warpall}
```

84.4 Equation numbers

for HTML output: 12347 `\begin{warpHTML}`

Ctrl `LWR@startingequation` For use with `lateximage` and multi-line numbered equations. Remembers the next equation number so that it may be printed in the alt tag.

```
12348 \newcounter{LWR@startingequation}
12349
12350 \ifundefined{chapter}
12351 {
12352 \renewcommand{\theLWR@startingequation}{%
12353   \arabic{LWR@startingequation}%
12354 }
12355 }
12356 {% chapter defined
12357 \renewcommand{\theLWR@startingequation}{%
12358   \ifnumcomp{\value{chapter}}{>}{0}{\arabic{chapter}.}}{%
12359   \arabic{LWR@startingequation}%
12360 }
12361 }
```

Bool `LWR@isstartingequation` True for the first equation tag, false for later tags in the same environment.

```
12362 \newbool{LWR@isstartingequation}
```

`\LWR@startingequationtag` Prints the starting equation number or tag.

```
12363 \let\LWR@startingequationtag\theLWR@startingequation
```

`\LWR@equationtag` Prints the ending equation number or tag.

This is reset by `lateximage`, may be temporarily overwritten by `\tag` calling `\LWR@remembertag`.

```
12364 \newcommand*\LWR@equationtag{}
```

Only if `svg math`, patch `\tag` after packages have loaded, in case someone else modified `\tag`.

```
12365 \AtBeginDocument{
12366
12367 \ifbool{mathjax}{}{% not mathjax
```

`\LWR@remembertag` `{\tag}`

For use inside the math environments while using svg math. Sets `\theLWR@startingequation` and `\theequation` to the given tag.

```

12368 \NewDocumentCommand{\LWR@remembertag}{m}{%
12369   \ifbool{LWR@isstartingequation}%
12370   {%
12371     \global\boolfalse{LWR@isstartingequation}%
12372     \xdef\LWR@startingequationtag{#1}%
12373   }{%
12374     \xdef\LWR@equationtag{#1}%
12375 }%

12376 }% not mathjax
12377 }% AtBeginDocument

```

84.5 HTML alt tags

`\LWR@amsmathbody` `{\langle envname \rangle}` For use inside the optional argument to a `lateximage` to add the contents of a AMS math environment to the `<alt>` tag.

```

12378 \newcommand*{\LWR@amsmathbody}[1]
12379 {%
12380   \textbackslashash{\begin\}\{#1\} % extra space
12381   \LWR@HTMLsanitizeexpanded{\detokenize\expandafter{\the\@envbody}}%
12382   \textbackslashash{\end\}\{#1\}%
12383 }

```

`\LWR@amsmathbodynumbered` `{\langle envname \rangle}` For use inside the optional argument to a `lateximage` to add the contents of a AMS math environment to the `alt` tag, prefixed by the equation numbers.

```

12384 \newcommand*{\LWR@amsmathbodynumbered}[1]
12385 {%
12386   \ifnumcomp{\value{LWR@startingequation}}{=}{\value{equation}}%
12387   {(\LWR@equationtag)}%
12388   {(\LWR@startingequationtag\textendash\LWR@equationtag)} % extra space
12389   \LWR@amsmathbody{#1} % extra space
12390 }

```

84.6 lateximage environment

`\LWR@lateximage@oneimageb` `{\langle 1: alt text \rangle}{\langle 2: filename \rangle}{\langle 3: css style \rangle}{\langle 4: aria role \rangle}` Creates the image for the `lateximage`.

```

12391 \newcommand{\LWR@lateximage@oneimageb}[4]{%
12392   \LWR@subinlineimage{#1}{lateximage}%
12393   {%
12394     \LWR@print@embox{%
12395       \LWR@ImagesDirectory\OSPathSymbol%
12396       #2%
12397     }%
12398   }{svg}{#3}{#4}%
12399 }

```

```
\LWR@lateximage@oneimage {<1: alt text>} {<2: filename>} {<3: css style>} {<4: delimit?>} {<5: aria role>}
```

Creates an image for the `lateximage`, whose alt text depends on the circumstances.

```
12400 \newcommand{\LWR@lateximage@oneimage}[5]{%
12401   \LWR@traceinfo{\LWR@lateximage@oneimage !#1!#2!#3!#4!#5!}%
12402   \ifdefvoid{\LWR@ThisAltText}{%
12403     \IfBooleanTF{#4}{%
12404       \LWR@lateximage@oneimageb{#1}{#2}{#3}{#5}%
12405     }{%
12406       \LWR@lateximage@oneimageb%
12407         {\AltTextOpen#1\AltTextClose}%
12408         {#2}{#3}{#5}%
12409     }%
12410   }{%
12411     \LWR@lateximage@oneimageb%
12412       {\AltTextOpen\LWR@ThisAltText\AltTextClose}%
12413       {#2}{#3}{#5}%
12414   }%
12415 }
```

```
Env lateximage * [<2: <alt> tag>] * [<4: add'l hashing>] [<5: css style>] (<6: aria role>)
```

Typesets the contents and then renders the result as an SVG file. Star #1 causes the image to be hashed for reuse. Star #3 causes the alt tag to not include `\AltTextOpen` and `\AltTextClose`, for use with math expressions.

The optional `<alt>` tag is included in the HTML code for use with copy/paste.

[image filename hashing](#) If starred, a hashed filename is used. If so, the hash is based on the alt tag and also the additional hashing argument.

This may be used to provide an expression with a simple alt tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated T_EX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is used in the additional hashing argument to ensure a unique image.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple alt tag is still the same.

File *_html.aux

A new label is placed into the file *_html.aux:

```
\newlabel{\LWR@lateximage-<BaseJobname>-<number>}{{<x>}{<y>}}
```

This is used to find the image in the PDF file, according to its name.

File *-images.txt

A list of images to generate is created in `<jobname>-images.txt`. Each line has three pipe-delimited fields, containing the PDF page number from `<jobname>-html.pdf`, where the image is located, a boolean indicating whether the image is hashed, and the filename of the image. The last line has “end” in each field, and is used to detect an incomplete compile.

```
12416 \catcode'\$=\active%
```

```

12417
12418 \NewDocumentEnvironment{lateximage}{s O{\ImageAltText} s O{} O{} D(){}%
12419 {%
12420 \LWR@traceinfo{lateximage !#1!#2!#3!#4!#5!#6!}%
12421 \LWR@traceinfo{lateximage: starting on \jobname.pdf page \arabic{page}}%
12422 \LWR@traceinfo{lateximage: entering depth is \arabic{LWR@lateximagedepth}}%

```

Nested lateximages remain one large lateximage:

```
12423 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
```

If nesting inside an already-existing lateximage, simply record one more level. $\mathcal{A}\mathcal{M}\mathcal{S}$ packages redefine `\addtocounter` to do nothing if inside a `\text`, so lower-level \TeX macros are used for tracking nested lateximages.

```

12424 {%
12425     \addtocounter{LWR@lateximagedepth}{1}%
12426     \global\advance\c@LWR@Lateximagedepth 1\relax% Due to AmS \text macro.
12427 }%

```

Otherwise, this is the outer-most lateximage:

```
12428 {% start of outer-most lateximage
```

Remember the next equation number to be allocated, in case it must be printed in a multi-equation environment:

```

12429     \LWR@traceinfo{lateximage: starting outer-most lateximage}%
12430     \setcounter{LWR@startingequation}{\value{equation}}%
12431     \addtocounter{LWR@startingequation}{1}%
12432     \booltrue{LWR@isstartingequation}%
12433     \let\LWR@startingequationtag\theLWR@startingequation%

```

The default equation tag, unless overwritten by `\tag`:

```
12434     \let\LWR@equationtag\theequation%
```

Starting a new lateximage:

```

12435     \addtocounter{LWR@lateximagenumber}{1}%
12436     \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{LWR@lateximagenumber}}%

```

While inside a lateximage, locally do not use mathjax:

```
12437     \boolfalse{mathjax}%
```

Be sure that are doing a paragraph:

```
12438     \LWR@ensuredoingapar%
```

Inside the lateximage, temporarily prevent underfull `\hbox` warnings.

```
12439     \hbadness=10000\relax%
```

Next file:

```

12440     \addtocounter{LWR@externalfilecnt}{1}%
12441     \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{LWR@externalfilecnt}}%

```

Figure out what the next page number will be. `\setcounterpageref` assigns `LWR@Lpage` to the page number for the reference `LWR\lateximage-BaseJobname-XXX`:

```
12442 \setcounterpageref{LWR@Lpage}{%
12443     LWR\lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}%
12444 }%
12445 \LWR@traceinfo{lateximage: LWR@Lpage is \arabic{LWR@Lpage}}%
```

Create an HTML span which will hold the comment which contains the *pdftotext* translation of the image's page, and also will hold the link to the .svg file:

```
12446 \LWR@htmltag{span\LWR@indentHTML%
12447     id=\textquotedbl{}%
12448     lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}%
12449     \textquotedbl\LWR@indentHTML
12450     class=\textquotedbl{}lateximagesource\textquotedbl\LWR@originewline
12451 }%
```

Write instructions to the `<ImagesDirectory>.txt` file:

```
12452 \LWR@traceinfo{lateximage: about to write to \BaseJobname-images.txt}%
12453 \IfBooleanTF{#1}% starred
12454 {% hash
```

Compute and save the hashed file name for later use:

```
12455 \ifdefvoid{\LWR@ThisAltText}{%
12456     \IfBooleanTF{#3}{%
12457         \edef\LWR@hashedname{%
12458             \LWR@mdfive{\detokenize\expandafter{#2}-!-#4}%
12459         }%
12460     }{%
12461         \edef\LWR@hashedname{%
12462             \LWR@mdfive{\detokenize\expandafter{\AltTextOpen#2\AltTextClose}-!-#4}%
12463         }%
12464     }%
12465 }{%
12466     \edef\LWR@hashedname{%
12467         \LWR@mdfive{\detokenize\expandafter{\AltTextOpen\LWR@ThisAltText\AltTextClose}-!-#4}%
12468     }%
12469 }%
12470 \LWR@traceinfo{lateximage: hash is \LWR@hashedname}%
```

Write the page, hashing, and hashed name:

```
12471 \immediate\write\LWR@lateximagesfile{%
12472     |\arabic{LWR@Lpage}|true|\LWR@hashedname|%
12473 }%
12474 }% hash
12475 {% no hash
```

No hash, so write the page, no hashing, and the image number:

```
12476 \LWR@traceinfo{lateximage: hash false}%
12477 \immediate\write\LWR@lateximagesfile{%
12478     |\arabic{LWR@Lpage}|false|\LWR@ImagesName\arabic{LWR@externalfilecnt}|%
12479 }%
12480 }% no hash
```

Place an open comment tag. This will hide any traces of the lateximage PDF page which were picked up by *pdftotext*.

```
12481 \LWR@traceinfo{lateximage: about to create open comment}%
12482 \LWR@htmlopencomment%
```

One level deeper. At this outer-most lateximage, it is known that this is not being used inside an \mathcal{AMS} \text, since the outer-most level will never be in math mode.

```
12483 \addtocounter{LWR@lateximagedepth}{1}%
```

Start the new PDF page:

```
12484 \LWR@traceinfo{lateximage: about to create a new page}%
12485 \LWR@maybeoriginnewpage%
```

If the current page is larger, typeset the image in a “standard” width page and font size:

```
12486 \LWR@traceinfo{lateximage: about to create minipage}%
12487 \setcounter{LWR@mpfootnote@store}{\value{mpfootnote}}
12488 \ifdimless{\linewidth}{6in}{%
12489     \LWR@print@minipage{\linewidth}%
12490 }{%
12491     \LWR@print@minipage{6in}%
12492 }%

12493 \ifnumgreater{\value{LWR@minipage@depth}}{0}%
12494     {\setcounter{mpfootnote}{\value{LWR@mpfootnote@store}}}%
12495     {}%
12496 \@nameuse{LWR@print@LateximageFontSizeName}%
```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for \hspace, etc. inside a lateximage.

```
12497 \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
12498 \LWR@restoreorigformatting%
```

If not inside a minipage, use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```
12499 \ifnumgreater{\value{LWR@minipage@depth}}{0}%
12500     {}%
12501     {%
12502         \def\@mpfn{footnote}%
12503         \def\thempfn{\thefootnote}%
12504         \LetLtxMacro\@footnotetext\LWR@footnotetext%
12505     }%
```

Create the LWRlateximage<number> label:

```
12506 \LWR@traceinfo{lateximage: about to create label}%
12507 \LWR@orig@label{LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}}%
12508 \LWR@traceinfo{lateximage: finished creating the label}%
```

Adjust the rule color to match HTML:

```

12509 \ifdefvoid{\LWR@ruleHTMLcolor}{}{%
12510     \LWR@print@arrayrulecolor[HTML]{\LWR@ruleHTMLcolor}%
12511 }%

```

Enable print-mode math functions:

```

12512 \LetLtxMacro$\LWR@origdollar%
12513 \catcode'\$=3% math shift
12514 \LetLtxMacro\(\LWR@origopenparen%
12515 \LetLtxMacro\)\LWR@origcloseparen%

```

Only enable print-mode display math if are not already inside display math:

```

12516 \ifbool{\LWR@indisplaymathimage}{}{% not in display math
12517     \LetLtxMacro\[\LWR@origopenbracket%
12518     \LetLtxMacro\]\LWR@origclosebracket%
12519     \let\equation\LWR@orig@equation%
12520     \let\endequation\LWR@orig@endequation%
12521     \csletcs{equation*}{LWR@orig@equation*}%
12522     \csletcs{endequation*}{LWR@orig@endequation*}%
12523 }% not in display math

```

For chemformula:

```

12524 \LetLtxMacro\LWR@newsingledollar$%
12525 \LetLtxMacro\LWR@newsingledollar$% syntax highlighting

12526 }% end of outer-most lateximage
12527 \LWR@traceinfo{lateximage: finished start of environment}%
12528 }% end of \begin{lateximage}

```

`\endlateximage` When the lateximage environment closes:

```

12529 {% start of \end{lateximage}
12530 \LWR@traceinfo{lateximage: starting end of lateximage}%

```

Nested more than one deep?

```

12531 \LWR@traceinfo{lateximage: internal depth was \arabic{\LWR@lateximagedepth}}%
12532 \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{1}%

```

If nesting inside an already existing lateximage, simply record one less level. Uses a lower-level TeX macro due to $\mathcal{A}\mathcal{M}\mathcal{S}$ `\text` change of `\addtocounter`.

```

12533 {%
12534     \LWR@traceinfo{lateximage: unnesting}%
12535     \global\advance\c@LWR@lateximagedepth -1\relax%
12536 }%

```

If this is the outer-most lateximage:

```

12537 {% end of outer-most lateximage

```

Finish the lateximage minipage and start a new PDF page:

```

12538 \LWR@traceinfo{lateximage: ending outer-most lateximage}%
12539     \endLWR@print@minipage%
12540     \LWR@maybe@orignewpage%

```

Close the HTML comment which encapsulated any traces of the lateximage picked up by *pdftotext*:

```
12541 \LWR@print@vspace*{.5\baselineskip}%
12542 \LWR@htmlclosecomment%
12543 \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%
```

Create a link to the lateximage, allowing its natural height:

```
12544 \LWR@traceinfo{about to LWR@lateximage@oneimage !#2!}%
12545 \IfBooleanTF{#1}% starred
12546 {% hash
12547   \LWR@lateximage@oneimage{#2}{\LWR@hashedname}{#5}{#3}{#6}%
12548 }% hash
12549 {% no hash
12550   \LWR@lateximage@oneimage{#2}{\LWR@ImagesName\theLWR@externalfilecnt}{#5}{#3}{#6}%
12551 }% no hash
```

Be sure that are doing a paragraph:

```
12552 \LWR@ensuredoingapar%
```

Close the HTML span which has the *pdftotext* comment and also the link to the .svg image:

```
12553 \LWR@htmltag{/span}%
12554 \ifbool{HTMLDebugComments}{%
12555   \LWR@htmlcomment{End of lateximage}%
12556 }{ }%
```

Undo one lateximage level. This is not inside an \mathcal{AMS} text, so regular `\addtocounter` may be used here.

```
12557 \addtocounter{LWR@lateximagedepth}{-1}%
```

Clear the single-use alt text:

```
12558 \gdef\LWR@ThisAltText{}%
12559 }% end of outer-most lateximage
12560 \LWR@traceinfo{lateximage: exiting depth is \arabic{LWR@lateximagedepth}}%
12561 \LWR@traceinfo{lateximage: done}%
12562 }%
12563 \catcode'\$=3% math shift
12564 \end{warppHTML}
```

for PRINT output: 12565 \begin{warpprint}

```
Env lateximage * [<alt> tag] * [<add'l hashing>] [<css style>]
```

Ignored in print mode.

```
12566 \NewDocumentEnvironment{lateximage}{s o s o d()}
12567 {}{ }
```

```
12568 \end{warpprint}
```

85 center, flushleft, flushright

for HTML output: 12569 \begin{warpHTML}

Env center Replace center functionality with css tags. In a , these macros are nullified, but extra % are used to remove spurious spaces here as well.

```

12570 \newenvironment*{LWR@HTML@center}
12571 {%
12572   \LWR@forcenewpage%
12573   \ifbool{FormatWP}%
12574     {\BlockClass[\LWR@print@mbox{text-align:center}]{center}}%
12575     {\BlockClass{center}}%
12576 }
12577 {\endBlockClass}
12578
12579 \LWR@formattedenv{center}

```

Env flushright

```

12580 \newenvironment*{LWR@HTML@flushright}
12581 {%
12582   \LWR@forcenewpage%
12583   \ifbool{FormatWP}%
12584     {\BlockClass[\LWR@print@mbox{text-align:right}]{flushright}}%
12585     {\BlockClass{flushright}}%
12586 }
12587 {\endBlockClass}
12588
12589 \LWR@formattedenv{flushright}

```

Env flushleft

```

12590 \newenvironment*{LWR@HTML@flushleft}
12591 {%
12592   \LWR@forcenewpage%
12593   \ifbool{FormatWP}%
12594     {\BlockClass[\LWR@print@mbox{text-align:left}]{flushleft}}%
12595     {\BlockClass{flushleft}}%
12596 }
12597 {\endBlockClass}
12598
12599 \LWR@formattedenv{flushleft}

```

\centering, \raggedleft, and \raggedright usually have no effect on the HTML output, but they may be used to compare with the next token to identify their use at the start of a float. See \LWR@floatalignment.

\centering

```

12600 \newcommand*{\LWR@HTML@centering}{%
12601   \ifbool{HTMLDebugComments}{%
12602     \LWR@htmlcomment{centering}%
12603   }{%
12604 }
12605 \LWR@formatted{centering}

```

`\raggedleft`

```
12606 \newcommand*{\LWR@HTML@raggedleft}{%
12607     \ifbool{HTMLDebugComments}{%
12608         \LWR@htmlcomment{raggedleft}%
12609     }{}%
12610 }
12611 \LWR@formatted{raggedleft}
```

`\raggedright`

```
12612 \newcommand*{\LWR@HTML@raggedright}{%
12613     \ifbool{HTMLDebugComments}{%
12614         \LWR@htmlcomment{raggedright}%
12615     }{}%
12616 }
12617 \LWR@formatted{raggedright}
```

`\leftline {<text>}`

```
12618 \renewcommand{\leftline}[1]{\begin{flushleft}#1\end{flushleft}}
```

`\centerline {<text>}`

```
12619 \renewcommand{\centerline}[1]{\begin{center}#1\end{center}}
```

`\rightline {<text>}`

```
12620 \renewcommand{\rightline}[1]{\begin{flushright}#1\end{flushright}}
```

```
12621 \end{warpHTML}
```

86 Preloaded packages

for HTML output: 12622 `\begin{warpHTML}`

If the given package was loaded before or by `lwarp`, load the `lwarp` version as well.

`\LWR@PreloadedPackage {<packagename>}`

```
12623 \newcommand*{\LWR@PreloadedPackage}[1]{%
12624     \IfPackageLoadedTF{#1}%
12625     {%
12626         \AtBeginDocument{
12627             \LWR@origRequirePackage{lwarp-#1}%
12628         }
12629     }%
12630     {}%
12631 }
```

If `inputtrc` was loaded before `lwarp`, as is usually done, explicitly load the `lwarp` patches now:

```
12632 \LWR@PreloadedPackage{inputtrc}
```

If `textcomp` was loaded before `lwarp`, perhaps as part of the font-related packages, explicitly load the `lwarp` patches now:

```
12633 \LWR@PreloadedPackage{textcomp}
```

If `xunicode` was loaded before `lwarp`, perhaps as part of the font-related packages, explicitly load the `lwarp` patches now:

```
12634 \LWR@PreloadedPackage{xunicode}
```

If `graphics` or `graphicx` were loaded before `lwarp`, perhaps by `xunicode`, explicitly load the `lwarp` patches now:

```
12635 \LWR@PreloadedPackage{graphics}
```

```
12636 \LWR@PreloadedPackage{graphicx}
```

`scalegnt` may have been preloaded by `babel`

```
12637 \LWR@PreloadedPackage{scalegnt}
```

`fontaxes` must be preloaded so that `lwarp` may patch it for `HTML`.

```
12638 \LWR@PreloadedPackage{fontaxes}
```

Various font packages which may be loaded before `lwarp`:

```
12639 \LWR@PreloadedPackage{cmbright}
```

```
12640 \LWR@PreloadedPackage{fourier}
```

```
12641 \LWR@PreloadedPackage{kpfonts}
```

```
12642 \LWR@PreloadedPackage{kpfonts-otf}
```

```
12643 \LWR@PreloadedPackage{libertinust1math}
```

```
12644 \LWR@PreloadedPackage{pxfonts}
```

```
12645 \LWR@PreloadedPackage{txfonts}
```

```
12646 \LWR@PreloadedPackage{txgreek}
```

```
12647 \LWR@PreloadedPackage{newpxmath}
```

```
12648 \LWR@PreloadedPackage{newtxmath}
```

```
12649 \LWR@PreloadedPackage{newtxsf}
```

```
12650 \LWR@PreloadedPackage{mathalpha}
```

```
12651 \LWR@PreloadedPackage{unicode-math}
```

`nfssect-cfr` may be preloaded by `cfm-lm` or related font packages.

```
12652 \LWR@PreloadedPackage{nfssect-cfr}
```

`ulem` may be preloaded by `ctex`, `ctexart`, and related classes.

```
12653 \LWR@PreloadedPackage{ulem}
```

```
12654 \LWR@PreloadedPackage{xetexko}
```

`geometry` is preloaded by `lwarp`, and perhaps by various classes.

```
12655 \LWR@PreloadedPackage{geometry}
```

`plext` is preloaded by some CJK classes.

```
12656 \LWR@PreloadedPackage{plext}
```

stfloats is preloaded by ltj* classes.

```
12657 \LWR@PreloadedPackage{stfloats}
```

lltjext is preloaded by ltj* classes.

```
12658 \LWR@PreloadedPackage{lltjext}
```

luatexko must be loaded before lwarp.

```
12659 \LWR@PreloadedPackage{luatexko}
```

```
12660 \end{warpHTML}
```

87 siunitx

Pkg siunitx

A few HTML unit equivalents are defined here.

siunitx is well supported by lwarp.

Limitations Some general limitations:

fractions Due to *pdftotext* limitations, fraction output is replaced by symbol output for per-mode and quotient-mode.

\cancel is not currently supported for siunitx v3.

Negative values are not automatically colored.

tabular Tabular S and s columns are rendered as simple c columns, although key settings will be set. If using scientific notation, table-format, table-align-uncertainty, drop-exponent, etc.. use \tablenum for each cell. This is especially required for

drop-exponent drop-exponent, without which the value will be shown incorrectly.

table-auto-round table-auto-round is ignored.

Math rendering Math may be rendered in several ways in the same document:

For math mode with svg display: The original siunitx code is used while generating the svg image.

For HTML text mode: lwarp uses siunitx code patched for HTML, and simplified units.

For math expressions while using MATHJAX: A limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. The result usually looks fine, and otherwise is enough to get the meaning across.

Custom units siunitx allows customized units:

`\DeclareSIUnit` $\{\langle name \rangle\} \{\langle definition \rangle\}$

`\DeclareSIUnit` declares a version of the unit for the print version. This is also used when the unit is printed in `svg math` or a `lateximage`. It is also used for HTML if an HTML-specific version is not defined with `\HTMLDeclareSIUnit`.

```
\DeclareSIUnit\myunit{\ensuremath{\text{m}_y}}
```

`\HTMLDeclareSIUnit` $\{\langle name \rangle\} \{\langle definition \rangle\}$

 **v3 only!** Use this after the print unit has been defined. For siunitx v3, `\HTMLDeclareSIUnit` declares a simplified version of the unit for HTML, for example if the print-mode unit uses `TeX` boxes or `\ensuremath`:

```
\HTMLDeclareSIUnit\myunit{\text{m}\textsubscript{\textit{y}}}
```

It is also possible to provide a custom unit for MATHJAX:

```
\CustomizeMathJax{\newcommand{\myunit}{\text{m}_y}}
```

Predefined units Most units work as-is with HTML. For the following units, `lwarp` has already set `\HTMLDeclareSIUnit`: `\celsius`, `\arcminute`, `\arcsecond`, `\elementarycharge`, `\clight`, `\bohr`, `\electronmass`, `\hartree`, `\planckbar`.

 **MathJax**

Document modifications required for MATHJAX

 `\sisetup`

- Place `\sisetup` in the preamble before `\begin{document}`. Changes made later may be ignored, especially with MATHJAX. The MATHJAX emulation also ignores most macro options.

 **complex numbers**

- Complex numbers are displayed as entered, ignoring `output-complex-root`.

custom units

- Custom units may be added with `\CustomizeMathJax`. For example, from `lwarp-common-mathjax-siunitx`:

```
\CustomizeMathJax{\newcommand{\hartree}{\mathit{E}_{\mathrm{h}}}}
\CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\unicode{x212B}}}}
```

 **unit spacing**

- Units work better using `~` between units instead of using periods.

 `\square`, `\cubic`

- To square or cube compound units, enclose the following compound units in braces:

```
\cubic{\centimeter}
```

Single units do not require braces.

- For `\numlist`, the argument is printed as text as-is, so use space between semicolons for improved readability.

 **Missing \$ inserted**

- If using `parse-numbers = false`, also use `\num` or `\qty`. `siunitx=siunitx>Missing $ inserted`.

Also see **MATHJAX option**, section 8.7.4.

for HTML output: `12661 \begin{warpHTML}`

Options for siunitx:

```

12662 \newrobustcmd{\LWR@siunitx@textcelsius}{\HTMLentity{deg}C}
12663 \newrobustcmd{\LWR@siunitx@textdegree}{\HTMLentity{deg}}
12664 \newrobustcmd{\LWR@siunitx@textprime}{\HTMLUnicode{2032}}
12665 \newrobustcmd{\LWR@siunitx@textdblprime}{\HTMLUnicode{2033}}
12666 \newrobustcmd{\LWR@siunitx@textplanckbar}{\text{\textit{\HTMLUnicode{210F}}}}
12667
12668 \appto\LWR@restoreorigformatting{%
12669 \renewrobustcmd{\LWR@siunitx@textcelsius}{\text{\ensuremath{^\circ}C}}%
12670 \renewrobustcmd{\LWR@siunitx@textdegree}{\text{\ensuremath{^\circ}}}%
12671 \renewrobustcmd{\LWR@siunitx@textprime}{\text{\ensuremath{^\prime}}}%
12672 \renewrobustcmd{\LWR@siunitx@textdblprime}{\text{\ensuremath{^\prime\prime}}}%
12673 \renewrobustcmd{\LWR@siunitx@textplanckbar}{\text{\ensuremath{\hbar}}}%
12674 }

12675 \end{warpHTML}

```

for PRINT output: The print version of `\HTMLDeclareSIUnit`.

```

12676 \begin{warpprint}
12677 \NewDocumentCommand{\HTMLDeclareSIUnit}{o +m m}{}
12678 \end{warpprint}

```

88 Graphics print-mode modifications

88.1 General limitations

Per table 9, image filenames may be specified either with or without an extension. If an extension is given it will be used as-is, for either print or HTML output. If no extension is given, a list of possible extensions is tried, which depends on whether print or HTML is being generated. This allows a PDF file for print and a SVG file for HTML, for example. If no extension is given, the automatic search will only return lowercase extensions, even if the filename actually has an uppercase extension, and `lwarp` cannot get around this problem, so image file extensions must be lowercase to be seen by the HTML browser with `lwarp`. For example, name the image file `image.pdf` instead of `image.PDF`, but refer to it in the source as `image`, without an extension. For images which may be used as-is with either print or HTML, such as `JPG` or `PNG`, you may use a capitalized extension if it is specified in the source, such as `image.JPG`.

file extensions

⚠ case sensitive

`\includegraphics` file formats For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps` image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, `lwarp` will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a `.pdf` or `.eps` image is referred to with its file extension, the extension will be changed to `.svg` for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo To convert a PDF image to SVG, use the utility *pdftocairo*:

PDF to SVG

Enter ⇒ **pdftocairo -svg filename.pdf**

Prog lwarpmk pdftosvg For a large number of images, use *lwarpmk*:

Enter ⇒ **lwarpmk pdftosvg *.pdf (or a list of filenames)**

Prog lwarpmk epstopdf For EPS images converted to PDF using the package *epstopdf*, use

Prog epstopdf
epstopdf package

Enter ⇒ **lwarpmk pdftosvg *.PDF**

to convert to SVG images.

DVI L^AT_EX When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **lwarpmk epstopdf *.eps (or a list of filenames)**

Enter ⇒ **lwarpmk pdftosvg *.pdf (or a list of filenames)**

PNG and JPG For PNG or JPG while using *pdf_latex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

duplicate files A complication occurs if a file of the same name exists elsewhere in the T_EX tree, such as a test image from some L^AT_EX package. T_EX looks in the local document

△ image not displayed directory before considering the directories specified by `\graphicspath`, but the T_EX tree is found as “local”, so any file in the tree is found before the directories in `\graphicspath`. To use such an image, it must be copied to the document’s directory to be used for HTML, and furthermore must be in the document’s base directory instead of an images subdirectory.

△ graphics vs. graphicx If using the older `graphics` syntax, use both optional arguments for `\includegraphics`.

△ viewport A single optional parameter is interpreted as the newer `graphicx` syntax. Note that viewports are not supported by *lwarp*—the entire image will be shown.

units For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys. (`alt` has recently been incorporated into `graphicx` itself.)

HTML class With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML alt tags Likewise, the `\includegraphics alt` key adds an HTML alt tag to an image, and is ignored for print output. If not assigned, each image is given an alt tag according to `\ImageAltText`.

 **scale** Avoid using the `\includegraphics scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

`\rotatebox` `\rotatebox` accepts the optional origin key.

 **browser support** `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike L^AT_EX, so expect some ugly results for scaling and rotating.

88.2 Print-mode modifications

for PRINT output: For print output, accept and then discard the new `class` key:

```
12679 \begin{warpprint}
12680 \define@key{Gin}{class}{}

```

Print-mode additions for the `overpic` package. See section 460 for the HTML version.

```
12681 \AtBeginDocument{
12682 \IfPackageLoadedTF{overpic}{
12683 \newcommand*{\overpicfontsize}{12}
12684 \newcommand*{\overpicfontskip}{14}
12685 }{}
12686 }
12687 \end{warpprint}

```

89 xcolor boxes

Pkg `xcolor`

A few new definitions are provided for enhanced HTML colored boxes, and `\fcolorbox` is slightly modified. Print-mode version are also provided.

Print-mode versions of new `xcolor` definitions. These are defined inside `warppall` because they are also used for HTML while inside a `lateximage`. They are defined `\AtBeginDocument` so that the `xcolor` originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of none, in which case only the frame is drawn, allowing the background page color to show.

for HTML & PRINT: `12688 \begin{warppall}`

After `xparse` may have been loaded ...

```
12689 \AtBeginDocument{
```

... and *only* if xcolor was loaded:

```
12690 \IfPackageLoadedTF{xcolor}{
12691 \LWR@traceinfo{patching xcolor}
```

The print version:

`\colorboxBlock` `\colorboxBlock` is the same as `\colorbox`:

```
12692 \LetLtxMacro\colorboxBlock\colorbox
```

The original definition is reused by the new versions:

```
12693 \LetLtxMacro\LWR@orig@print@fcolorbox\fcolorbox
```

```
\fcolorbox [<framemodel>] [<framecolor>] [<boxmodel>] [<boxcolor>] [<text>]
```

In print mode, `\fcolorbox` is modified to accept a background color of none.

(`\fcolorbox` is particular about its optional arguments, thus the elaborate combinations of `\ifthenelse`.)

```
12694 \newsavebox{\LWR@colorminipagebox}
12695
12696 \NewDocumentCommand{\LWR@print@fcolorbox}{o m o m +m}{%
12697   \LWR@traceinfo[LWR@print@fcolorbox #2 #4]%
```

Pre-load the contents into an LR box so that they can be used inside a `\fcolorbox`:

```
12698   \begin{lrbox}{\LWR@colorminipagebox}%
12699   #5%
12700   \end{lrbox}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a `\fcolorbox`.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
12701   \ifstrequal{#4}{none}%
12702   {% #4 none
12703     \LWR@traceinfo{background is none}%
12704     {% scope the \colorlet
12705       \colorlet{LWR@currentcolor}{.}%
12706       \color{#2}%
12707       \fbox{%
12708         \color{LWR@currentcolor}%
12709         \usebox{\LWR@colorminipagebox}%
12710       }% fbox
12711     }% colorlet
12712   }% #4 none
12713   {% #4 not none
12714     \LWR@traceinfo{background not none}%
12715     \IfValueTF{#1}%
12716     {%
12717       \IfValueTF{#3}%
12718       {\LWR@orig@print@fcolorbox[#1][#2][#3][#4]{\usebox{\LWR@colorminipagebox}}}%
```

```

12719   {\LWR@orig@print@fcolorbox[#1]{#2}{#4}\usebox{\LWR@colorminipagebox}}}%
12720   }%
12721   {% no value #1
12722     \IfValueTF{#3}%
12723     {\LWR@orig@print@fcolorbox[#2][#3]{#4}\usebox{\LWR@colorminipagebox}}}%
12724     {\LWR@orig@print@fcolorbox[#2]{#4}\usebox{\LWR@colorminipagebox}}}%
12725   }% no value #1
12726   }% #4 not none
12727   \LWR@traceinfo{LWR@print@fcolorbox done}%
12728 }

```

```
12729 \renewrobustcmd*{\fcolorbox}{\LWR@print@fcolorbox}%
```

```
\fcolorboxBlock [framemodel] {framecolor} [boxmodel] {boxcolor} {text}
```

In print mode, `\fcolorboxBlock` is the same as `\fcolorbox`.

```
12730 \newcommand*{\LWR@print@fcolorboxBlock}{\LWR@print@fcolorbox}
```

```
12731 \newrobustcmd*{\fcolorboxBlock}{\LWR@print@fcolorboxBlock}
```

```
Env fcolorminipage [1:framemodel] {2:framecolor} [3:boxmodel] {4:boxcolor} [5:align]
[6:height] [7:inner-align] {8:width}
```

In print mode, becomes a `\fcolorbox` containing a minipage:

```

12732 \NewDocumentEnvironment{fcolorminipage}{o m o m O{c} O{ } o m}
12733 {%
12734   \LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%

```

Pre-load the contents into an LR box so that they can be used inside a `\fcolorbox`:

```
12735   \begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```

12736   \IfValueTF{#7}%
12737   {\begin{minipage}[#5][#6][#7]{#8}}%
12738   {\begin{minipage}[#5][#6][#5]{#8}}%
12739 }%
12740 {%
12741   \end{minipage}%
12742   \end{lrbox}%
12743   \LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}%

```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a `\fcolorbox`.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```

12744   \ifstrequal{#4}{none}%
12745   {% #4 none
12746     {% scope the \colorlet
12747       \colorlet{\LWR@currentcolor}{.}%
12748       \color{#2}%
12749       \fbox{%

```

```

12750             \color{LWR@currentcolor}%
12751             \usebox{\LWR@colorminipagebox}%
12752             }% fbox
12753             }% colorlet
12754             }% #4 none
12755             {% #4 not none
12756             \IfValueTF{#1}%
12757             {%
12758             \IfValueTF{#3}%
12759             {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
12760             {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
12761             }%
12762             {% no value #1
12763             \IfValueTF{#3}%
12764             {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
12765             {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
12766             }% no value #1
12767             }% #4 not none
12768             \LWR@traceinfo{*** finished end fcolorminipage}%
12769 }

```

xcolor is known to have been loaded, and provided HTML versions of the following, and the print versions are provide above, so now they may be \LW@formatted.

```

12770 \LWR@formatted{colorbox}
12771 \LWR@formatted{colorboxBlock}
12772 \LWR@formatted{fcolorbox}
12773 \LWR@formatted{fcolorboxBlock}
12774 \LWR@formattedenv{fcolorminipage}

12775 \LWR@traceinfo{xcolor patches done}
12776 }{% xcolor loaded
12777 }% AtBeginDocument

12778 \end{warpall}

```

90 chemmacros environments

\makepolymerdelims and redox reactions must be enclosed in a lateximage during HTML output. These environments are provided here in print mode, and in the chemmacros code in HTML mode, as a high-level semantic syntax which automatically embeds the contents in a lateximage with an appropriate alt tag.

for PRINT output: 12779 \begin{warpprint}

```

12780 \AtBeginDocument{
12781 \IfPackageLoadedTF{chemmacros}{

12782 \DeclareDocumentEnvironment{polymerdelims}{}
12783 {}{}

```

Env polymerdelims

Env redoxreaction

```
{\langle space above \rangle} {\langle space below \rangle}
```

For print output, extra space is include above and below the image, and a `lateximage` is not necessary. This extra space must be enforced, even inside a float, so zero-width rules are used.

For the HTML version, see section 193.5.

```
12784 \DeclareDocumentEnvironment{redoxreaction}{m m}
12785   {\rule{0pt}{#1}}{\rule[-#2]{0pt}{#2}}

12786 }{}% chemmacros
12787 }% AtBeginDocument

12788 \end{warpprint}
```

91 cleveref

loading order `cleveref` and `lwarp-cleveref` with its associated macro patches are automatically preloaded at the end of the preamble via `\AtEndPreamble` and `\AfterEndPreamble`. This is done because the HTML conversion requires `cleveref`. The user's document may not require `cleveref`, thus the user may never explicitly load it, so during HTML output `lwarp` loads it last. If the user's document preamble uses `cleveref` options, or functions such as `\crefname`, then `cleveref` may be loaded in the user's preamble near the end, and `lwarp`'s additional loading of `cleveref` will have no effect.

`\AtEndPreamble` forces `cleveref` to be loaded last, if it has not yet been loaded by the user.

for HTML output:

```
12789 \begin{warppHTML}
12790
12791 \AtEndPreamble{
12792   \RequirePackage{cleveref}
12793 }
12794
12795 \end{warppHTML}
```

92 Preexisting label and reference definitions

Remember and patch some label-related definitions. These will be further encased and patched by other packages later.

`\label` and `\pageref` do NOT change their behavior according to print or HTML output, and thus do not use the `\LWR@formatted` system.

for HTML output:

```
12796 \begin{warppHTML}
12797
12798 \LetLtxMacro\LWR@orig@label\label% includes memoir, before cleveref
12799 \LetLtxMacro\label\LWR@new@label
12800
12801 \LetLtxMacro\LWR@orig@pageref\pageref
12802 \LetLtxMacro\pageref\LWR@new@pageref
12803
12804 \end{warppHTML}
```

93 picture environment

Env `picture`

The `picture` environment is enclosed inside a `\lateximage`.

for HTML output: `12805 \begin{warpHTML}`

Env `picture`

```
12806 \BeforeBeginEnvironment{picture}{\begin{lateximage}[picture]}
12807
12808 \AfterEndEnvironment{picture}{\end{lateximage}}

12809 \end{warpHTML}
```

94 Minipages and Boxes

A CSS flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

 **inline** A line of text with an inline minipage or `\parbox` will have the minipage or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made inline-block.

placement minipages and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side Side-by-side minipages may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a center environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.

 **minipage in a span** There is limited support for minipages inside an HTML ``. An HTML `<div>` cannot appear inside a ``. While in a ``, minipages, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an “inline” format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

 **minipage size** When using minipage, `\parbox`, and `fminipage`, a virtual 6 × 9 inch text area is used for `\linewidth`, `\textwidth`, and `\textheight`, both for sizing the minipage, and also for its contents.

if width is `\linewidth` If a minipage or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML A new macro `\minipagefullwidth` requests that, during HTML output, the next single minipage or `\parbox` be generated without an HTML width attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version’s width makes no sense in HTML.

 **tabular, multicols** Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every minipage or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell lwrap to honor the specified widths of all following minipages and `\parboxes`

`\UseMinipageWidths`
`\IgnoreMinipageWidths`

until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell `lwrap` to ignore the specified widths.

 **multicol** Inside a `multicols`, `\linewidth` is divided by the specified number of columns.

 **text alignment** Nested minipages adopt their parent's text alignment in HTML, whereas in regular L^AT_EX PDF output they do not. Use a `flushleft` or similar environment in the child minipage to force a text alignment.

for HTML output: `12810 \begin{warpHTML}`

94.1 Computed lengths

Len `\LWR@minipagewidth` Used to convert the width into printable units.

```
12811 \newlength{\LWR@minipagewidth}
```

Len `\LWR@minipageheight` Used to convert the height into printable units.

```
12812 \newlength{\LWR@minipageheight}
```

94.2 Virtual page size

Ctr `LWR@virtualpagedePTH` Used to only reset the line width at the outermost minipage.

```
12813 \newcounter{LWR@virtualpagedePTH}
12814 \setcounter{LWR@virtualpagedePTH}{0}
```

Env `LWR@setvirtualpage` * [`<columns>`]

If not nesting a minipage, adjust `\linewidth`, `\textwidth`, and `\textheight` for a virtual 6×9 page, and start on a new PDF page to help prevent page overflows.

If starred, force a new page in the PDF before generating more HTML. This may be done to reduce the chance of page overflow when starting a new minipage.

The optional number of columns defaults to 1.

```
12815 \NewDocumentEnvironment{LWR@setvirtualpage}{s 0{1}}{%
12816   \ifnumequal{\value{LWR@virtualpagedePTH}}{0}{%
12817     \IfBooleanT{#1}{\LWR@maybe@orignewpage}%
12818     \setlength{\linewidth}{6in/#2}%
12819     \setlength{\textwidth}{6in}%
12820     \setlength{\textheight}{9in}%
12821   }{%
12822     \addtocounter{LWR@virtualpagedePTH}{1}%
12823   }
12824 {\addtocounter{LWR@virtualpagedePTH}{-1}}
```

94.3 Footnote handling

Also see section 60 for other forms of footnotes. Minipage footnotes are gathered in section 60.5, and then placed into the document in section 94.4.

94.4 Minipage handling

- Bool** LWR@minipagefullwidth Should the next minipage have no HTML width?
- ```
12825 \newbool{LWR@minipagefullwidth}
12826 \boolfalse{LWR@minipagefullwidth}
```
- Bool** LWR@forceminipagefullwidth    Should the next minipage have no HTML width? Used to force full width for all minipages in an environment such as tabular or multicols, where the actual width depends on the browser width. Controlled by \useminipagewidths and \ignoreminipagewidths.
- ```
12827 \newbool{LWR@forceminipagefullwidth}
12828 \boolfalse{LWR@forceminipagefullwidth}
```
- \minipagefullwidth** Requests that the next minipage have no width tag in HTML:
- for HTML output:** 12829 \newcommand*{\minipagefullwidth}{\global\booltrue{LWR@minipagefullwidth}}
- \UseMinipageWidths** Locally requests that minipage widths be honored.
- ```
12830 \newcommand*{\UseMinipageWidths}{\boolfalse{LWR@forceminipagefullwidth}}
```
- \IgnoreMinipageWidths**    Locally requests that minipage widths be ignored.
- ```
12831 \newcommand*{\IgnoreMinipageWidths}{\booltrue{LWR@forceminipagefullwidth}}
12832 \end{warpHTML}
```
- for PRINT output:** 12833 \begin{warpprint}
- ```
12834 \newcommand*{\minipagefullwidth}{}
12835 \newcommand*{\UseMinipageWidths}{}
12836 \newcommand*{\IgnoreMinipageWidths}{}
12837 \end{warpprint}
```
- for HTML output:** 12838 \begin{warpHTML}
- Bool** LWR@minipagethispar    Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.
- ```
12839 \newbool{LWR@minipagethispar}
12840 \boolfalse{LWR@minipagethispar}
```
- Ctr** LWR@minipage@depth Used to track whether to change footnote styles in a lateximage inside an HTML minipage.
- ```
12841 \newcounter{LWR@minipage@depth}
12842 \setcounter{LWR@minipage@depth}{0}
```
- Ctr** LWR@mpfootnote@store    Used to maintain minipage footnote number while nesting inside a lateximage.
- ```
12843 \newcounter{LWR@mpfootnote@store}
```
- Env** minipage [*⟨vert position⟩*] [*⟨height⟩*] [*⟨inner vert position⟩*] {*⟨width⟩*}

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using `\linewidth`, `\textwidth`, or `\textheight`, these are scaled proportionally to a 6×9 inch text area.

```
12844 \NewDocumentEnvironment{LWR@HTML@sub@minipage}{m m m m}
12845 {%
12846 \LWR@traceinfo{minipage}%
```

Start an environment, in which width and height is computed based on a virtual page size instead of the extra-large PDF page used during HTML tag generation.

```
12847 \begin{LWR@setvirtualpage}*%
```

Save the requested width now that `\linewidth`, etc. are adjusted to virtual size.

```
12848 \setlength{\LWR@minipagewidth}{#4}%
12849 \ifnumequal{\value{LWR@virtualpagedepth}}{1}{%
12850   \addtolength{\LWR@minipagewidth}{3em}% room for frames
12851 }{%
12852 \LWR@traceinfo{computed width is \LWR@printlength{\LWR@minipagewidth}}%
```

Compute height:

```
12853 \setlength{\LWR@minipageheight}{\textheight}% default unless specified
12854 \ifblank{#2}{\setlength{\LWR@minipageheight}{#2}}%
```

L^AT_EX wants to start a paragraph for the virtual minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

```
12855 \ifbool{FormatWP}{\newline}{}%
12856 \LWR@stoppars%
```

If FormatWP, add a text frame:

```
12857 \ifbool{FormatWP}{%
12858
12859 \addtocounter{LWR@thisautoidWP}{1}%
12860 \LWR@htmltag{%
12861   div id=\textquotedbl%
12862     \LWR@print@mbbox{autoidWP-\arabic{LWR@thisautoidWP}}%
12863   \textquotedbl\ % space
12864   class=\textquotedbl{}wminipage\textquotedbl%
12865 }%
12866
12867 }{%
```

Create the `<div>` tag with optional alignment style:

```
12868 \LWR@traceinfo{minipage: creating div class}%
12869 \LWR@htmltag{div class=\textquotedbl{}minipage\textquotedbl\ style=\textquotedbl%
12870 \ifthenelse{\equal{#1}{t}}{\LWR@print@mbbox{vertical-align:bottom} ; }{%
12871 \ifthenelse{\equal{#1}{c}}{\LWR@print@mbbox{vertical-align:middle} ; }{%
12872 \ifthenelse{\equal{#1}{b}}{\LWR@print@mbbox{vertical-align:top} ; }{%
12873 \ifthenelse{\equal{#3}{t}}{\LWR@print@mbbox{justify-content:flex-start} ; }{%
12874 \ifthenelse{\equal{#3}{c}}{\LWR@print@mbbox{justify-content:center} ; }{%
```

```
12875 \ifthenelse{\equal{#3}{b}}{\LWR@print@mbbox[justify-content:flex-end] ; }{}%
12876 \ifthenelse{\equal{#3}{s}}{\LWR@print@mbbox[justify-content:space-between] ; }{}%
```

Print the width and optional height styles:

```
12877 \LWR@traceinfo{minipage: about to print the width of \LWR@printlength{\LWR@minipagewidth}}%
12878 \ifbool{LWR@minipagefullwidth}%
12879 {\global\boolfalse{LWR@minipagefullwidth}}%
12880 {%
12881   \ifbool{LWR@forceminipagefullwidth}%
12882     {}%
12883     {%
12884       \ifdimequal{#4}{\linewidth}%
12885         {}%
12886         {width:\LWR@printlength{\LWR@minipagewidth} ; }%
12887     }%
12888 }%
12889 \LWR@traceinfo{minipage: about to print the height}%
12890 \ifblank{#2}{}{height:\LWR@printlength{\LWR@minipageheight} ; }%
12891 \textquotedbl%
12892 }%
```

Finish with an empty line to start the contents on a new line.

```
12893
12894 % The preceding empty line is required.
```

Set the user-accessible line and text width and height values inside the virtual minipage. These do not affect the actual size of the PDF output, but are used by any reference to `\linewidth`, etc. inside the virtual minipage being created here. `\LWR@minipagewidth` was the original then padded by 3em, which is restored here. This is done instead of settings back to #4, in case #4 was `\linewidth`, which was changed to 6in above.

```
12895 \ifnunequal{\value{LWR@virtualpagedepth}}{1}{}%
12896   \addtolength{\LWR@minipagewidth}{-3em}% undo frame padding
12897 }{}%
12898 \setlength{\linewidth}{\LWR@minipagewidth}%
```

`\raggedright` cancels hyphenation, which will be done by HTML instead.

```
12899 \LWR@print@raggedright%

12900   \LWR@newautopagelabel{page}%
```

Set minipage footnotes:

```
12901 \def\@mpfn{mpfootnote}%
12902 \def\thempfn{\thempfootnote}\c@mpfootnote\z@%
12903 \let\@footnotetext\@mpfootnotetext%
```

Track depth for `lateximage` footnote type:

```
12904 \addtocounter{LWR@minipage@depth}{1}%
```

Resume paragraph tag handling for the contents of the minipage:

```

12905 \LWR@startpars%
12906 \ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%
12907
12908 === begin minipage ===
12909
12910 }{%
12911 \LWR@traceinfo{minipage: finished starting the minipage}%
12912 }% finished \minipage
12913 {% \endminipage

```

Print pending minipage footnotes:

```
12914 \LWR@printpendingmpfootnotes%
```

End the environment with closing tag:

```

12915 \ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%
12916
12917 === end minipage ===
12918
12919 }{%
12920 \LWR@stoppars%
12921
12922 \ifbool{FormatWP}{%
12923
12924 \LWR@htmllementend{div}%
12925
12926 }{%

```

Wrapup:

```

12927 \addtocounter{LWR@minipage@depth}{-1}%
12928 \LWR@htmldivclassend{minipage}%
12929
12930 \end{LWR@setvirtualpage}%
12931 \LWR@startpars%
12932 \ifbool{FormatWP}{\newline}{%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

12933 \global\booltrue{LWR@minipagethispar}%
12934 \LWR@traceinfo{LWR@minipage: done}%
12935 }
12936
12937 \NewDocumentEnvironment{LWR@HTML@minipage}{O{t} O{} O{t} m}
12938   {\LWR@HTML@sub@minipage{#1}{#2}{#3}{#4}}
12939   {\endLWR@HTML@sub@minipage}
12940
12941 \LWR@formattedenv{minipage}

```

94.5 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox

for HTML output:

```
\parbox [pos] [height] [inner-pos] {width} {text}
```

A parbox uses the minipage code:

```

12942 \NewDocumentCommand{\LWR@HTML@parbox}{0{t} 0{} 0{t} m +m}
12943 {
12944 \LWR@traceinfo{parbox of width #4}%
12945 \begin{minipage}[#1][#2][#3]{#4}%
12946 #5
12947 \end{minipage}%
12948 }
12949
12950 \LWR@formatted{parbox}

```

`\mbox` {*⟨text⟩*} Nullified for HTML.

```

12951 \newcommand*{\LWR@HTML@mbox}[1]{#1}
12952
12953 \LWR@formatted{mbox}

```

`\LWR@makebox@paren` {*⟨width⟩*}, {*⟨height⟩*}

Adds to the style in `\LWR@temptwo`.

```

12954 \NewDocumentCommand{\LWR@makebox@paren}{m m}{%
12955 \IfValueTF{#2}{%
12956   \setlength{\LWR@tempwidth}{#1\unitlength}%
12957   \setlength{\LWR@tempheight}{#2\unitlength}%
12958   \appto{\LWR@temptwo}{%
12959     \LWR@print@mbox{width:\LWR@printlength{\LWR@tempwidth}} ; % space
12960     \LWR@print@mbox{height:\LWR@printlength{\LWR@tempheight}} ; % space
12961   }%
12962 }{%
12963   \PackageError{lwarp}%
12964     {(width,height) is missing a comma ',' character}%
12965     {\protect\makebox\space and \protect\framebox\space accept
12966       a size in the format (width,height).}%
12967 }%
12968 }

```

`\LWR@makebox@align` {*⟨alignment character⟩*}

Adds to the style in `\LWR@temptwo`.

```

12969 \newcommand*{\LWR@makebox@align}[1]{%
12970   \def\LWR@align{center}%
12971   \ifstrequal{#1}{l}{\def\LWR@align{left}}{}%
12972   \ifstrequal{#1}{r}{\def\LWR@align{right}}{}%
12973   \ifstrequal{#1}{s}{\def\LWR@align{justify}}{}%
12974   \appto{\LWR@temptwo}{%
12975     \LWR@print@mbox{text-align:\LWR@align} ; %
12976   }%
12977 }

```

`\makebox` (*⟨width,height⟩*) [*⟨width⟩*] [*⟨pos⟩*] {*⟨text⟩*}

```

12978 \NewDocumentCommand{\LWR@HTML@makebox}{>\SplitArgument{1}{,}}d() o o +m}{%

```

Build the style depending on arguments:

```

12979 \begin{LWR@setvirtualpage}%
12980 \def\LWR@temptwo{%
12981 \IfValueTF{#1}%
12982 {% (width,height) ..
12983 \LWR@makebox@paren #1%
12984 \IfValueT{#2}%
12985 {% (width,height) [posn]
12986 \LWR@makebox@align{#2}%
12987 }%
12988 }%
12989 {% [width]
12990 \IfValueT{#2}% [width]
12991 {%
12992 \setlength{\LWR@tempwidth}{#2}%
12993 \ifdimgreater{\LWR@tempwidth}{0pt}{%
12994 \appto{\LWR@temptwo}{%
12995 width:\LWR@printlength{\LWR@tempwidth} ; % space
12996 }%
12997 }{%
12998 }%
12999 }%
13000 \IfValueT{#3}%
13001 {% [width] [posn]
13002 \LWR@makebox@align{#3}%
13003 }%
13004 \InlineClass[%
13005 \LWR@print@ebox{display:inline-block} ; %
13006 \LWR@temptwo
13007 ]%
13008 {makebox}%
13009 {#4}%
13010 \end{LWR@setvirtualpage}%
13011 }
13012 \LWR@formatted{makebox}

```

`\framebox` (*<width,height>*) [*<width>*] [*<pos>*] {*<text>*}

```

13013 \NewDocumentCommand{\LWR@HTML@framebox}{d() o o +m}{%
13014 \fbox{makebox(#1)[#2][#3]{#4}}%
13015 }
13016
13017 \LWR@formatted{framebox}

```

`\LWR@forceminwidth` {*<legth>*}

Sets `\LWR@atleastonept` to be at least 1pt.

```

13018 \newlength{\LWR@atleastonept}
13019
13020 \newcommand*{\LWR@forceminwidth}[1]{%
13021 \setlength{\LWR@atleastonept}{#1}%
13022 \ifthenelse{%
13023 \lengthtest{\LWR@atleastonept>0pt}\AND%
13024 \lengthtest{\LWR@atleastonept<1pt}%
13025 }%
13026 {\setlength{\LWR@atleastonept}{1pt}}%
13027 }%

```

13028 }

`\LWR@fboxstyle` Prints the HTML attributes for a black border and padding.

`\LWR@forceminwidth` must be used first in order to set the border width.

```
13029 \newcommand*\LWR@fboxstyle{%
13030 \LWR@findcurrenttextcolor%
13031 \LWR@traceinfo{LWR@fboxstyle B}%
13032 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@origpound\LWR@tempcolor ; %
13033 padding:\LWR@printlength{\fboxsep} ; %
13034 color:\LWR@origpound\LWR@tempcolor%
13035 }
```

`\fbox` $\langle text \rangle$

Creates a framed inline span enclosing the text.

Create a new HTML version, but don't use it until after `xcolor` may have loaded:

```
13036 \newcommand{\LWR@HTML@fbox}[1]{%
13037   \LWR@traceinfo{HTML fbox}%
13038   \LWR@forceminwidth{\fboxrule}%
13039   \LWR@traceinfo{HTML fbox B}%
13040   \InlineClass[%
13041     \LWR@print@mbbox{display:inline-block} ; %
13042     \LWR@fboxstyle%
13043   ]{fbox}{#1}%
13044   \LWR@traceinfo{HTML fbox: done}%
13045 }
```

`xcolor` lets things to `\fbox` when it is loaded, and this must remain even for HTML output while in a `lateximage`, so `\fbox` is not modified until `\AtBeginDocument`:

```
13046 \AtBeginDocument{\LWR@formatted{fbox}}
```

`\fboxBlock` $\langle text \rangle$ Creates a framed HTML `<div>` of the text.

First, a print-mode version. This is newly defined for print mode, so it is defined inside `warpall`.

for HTML & PRINT:

```
13047 \end{warpHTML}
13048
13049 \begin{warpall}
13050 \let\fboxBlock\fbox
13051 \end{warpall}
13052
13053 \begin{warpHTML}
```

for HTML output: Next, an HTML version:

```
13054 \newcommand{\LWR@HTML@fboxBlock}[1]{%
13055 \LWR@forceminwidth{\fboxrule}%
13056 \LWR@stoppars%
13057 \begin{BlockClass}[\LWR@fboxstyle]{fboxBlock}
13058 #1
13059 \end{BlockClass}
13060 \LWR@startpars%
```

```

13061 }
13062
13063 \LWR@formatted{fboxBlock}
13064
13065 \end{warpHTML}

```

Env `fminipage` [*align*] [*height*] [*align*] {*width*}

Creates a framed HTML `<div>` around its contents.

for HTML & PRINT: Print version:

```

13066 \begin{warpall}
13067
13068 \newsavebox{\LWR@fminipagebox}
13069
13070 \NewDocumentEnvironment{fminipage}{0{t} o 0{t} m}
13071 {%

```

An outer minipage will be used for vertical alignment. An inner minipage will be framed with `\fbox`.

If the optional inner alignment is not given, use the outer instead:

```

13072 \IfValueTF{#3}%
13073 {\def\LWR@thisalign{#3}}
13074 {\def\LWR@thisalign{#1}}%

```

Form the outer minipage depending on whether a height was given. Make the outer minipage larger to compensate for the frame.

```

13075 \IfValueTF{#2}%
13076 {\minipage[#1][#2+2\fboxsep+2\fboxrule][\LWR@thisalign]{#4+2\fboxsep+2\fboxrule}}%
13077 {\minipage[#1]{#4+2\fboxsep+2\fboxrule}}%

```

Capture the contents of the environment:

```

13078 \begin{lrbox}{\LWR@fminipagebox}%

```

Nest the contents inside an inner minipage of the desired size:

```

13079 \IfValueTF{#2}%
13080 {\minipage[#1][#2][\LWR@thisalign]{#4}}%
13081 {\minipage[#1]{#4}}%
13082 }
13083 {%

```

Close the inner minipage and the LR box with the contents:

```

13084 \endminipage%
13085 \end{lrbox}%

```

Create a frame around the contents of the environment:

```

13086 \fbox{\usebox{\LWR@fminipagebox}}%

```

The entire thing is placed inside the outer minipage:

```
13087 \endminipage%
13088 }
13089 \end{warpall}
```

HTML version:

for HTML output: 13090 \begin{warpHTML}

```
13091
13092 \NewDocumentEnvironment{LWR@HTML@fminipage}{O{t} o O{t} m}
13093 {%
13094 \LWR@traceinfo{fminipage #1 #2 #3 #4}%
```

Locally change to the virtual page size before processing the requested sizes:

```
13095 \begin{LWR@setvirtualpage}*%
13096 \setlength{\LWR@tempwidth}{#4}%
13097 \IfValueT{#2}{\setlength{\LWR@tempheight}{#2}}%
```

Use a rule of at least one pixel in width:

```
13098 \LWR@forceminwidth{\fboxrule}%

13099 \LWR@stoppars%

13100 \begin{BlockClass}[%
13101 \LWR@fboxstyle ; %
13102 \IfValueT{#2}{height:\LWR@printlength{\LWR@tempheight} ; }%
13103 \ifbool{LWR@minipagefullwidth}%
13104 {\global\boolfalse{LWR@minipagefullwidth}}%
13105 {%
13106   \ifbool{LWR@forceminipagefullwidth}%
13107     {}%
13108     {%
13109       \ifdimequal{\LWR@tempwidth}{\linewidth}%
13110         {}%
13111         {width:\LWR@printlength{\LWR@tempwidth} ; }%
13112     }%
13113 }%
13114 ]{fminipage}%
13115 }
13116 {%
13117 \end{BlockClass}%
13118 \end{LWR@setvirtualpage}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
13119 \global\booltrue{LWR@minipagethispar}%
13120 \LWR@traceinfo{fminipage done}%
13121 }
13122
13123 \LWR@formattedenv{fminipage}
```

`\raisebox` {<raiselen>} [<height>] [<depth>] {<text>}

```
13124 \NewDocumentCommand{\LWR@HTML@raisebox}{m o o m}{%
13125 #4%
```

```

13126 }
13127
13128 \LWR@formatted{raisebox}

13129 \end{warpHTML}

```

95 Direct formatting

⚠ **\bfseries, etc.** `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ **HTML special chars** `&`, `<`, and `>` have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the `listings` package is supported, and its `literate` option is used to convert `&`, `<`, and `>` to proper HTML entities.

verbatim The various verbatim-related environments do not convert `&`, `<`, and `>`, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

For high-level block and inline custom CSS classes, see section 52.10.

for HTML & PRINT: 13130 `\begin{warpall}`

Bool `FixSmallCaps`

User may set `FixSmallCaps` to `true` if small caps are being incorrectly rendered as all caps.

```

13131 \newbool{FixSmallCaps}
13132 \boolfalse{FixSmallCaps}

13133 \end{warpall}

```

for HTML output: 13134 `\begin{warpHTML}`

`\emph` `{\textit}`

```

13135 \DeclareRobustCommand{\LWR@HTML@emph}[1]{%
13136   {%
13137     \LWR@HTML@itshape%
13138     \LWR@htmlspan{em}{#1}%
13139   }%
13140 }
13141
13142 \LWR@formatted{emph}

```

`\textmd` `{\textnormal}`

```

13143 \DeclareRobustCommand{\LWR@HTML@textmd}[1]{%
13144   {%
13145     \LWR@HTML@mdseries%
13146     \InlineClass(font-weight:normal){textmd}{#1}%
13147   }%

```

```
13148 }
13149
13150 \LWR@formatted{textmd}
```

`\textbf` $\langle text \rangle$

```
13151 \DeclareRobustCommand{\LWR@HTML@textbf}[1]{%
13152   {%
13153     \LWR@HTML@bfseries%
13154     \LWR@htmlspan{b}{#1}%
13155   }%
13156 }
13157
13158 \LWR@formatted{textbf}
```

`\texteb` $\langle text \rangle$ From `nfssect-cfr`.

```
13159 \IfPackageLoadedTF{nfssect-cfr}{
13160 \DeclareRobustCommand{\LWR@HTML@texteb}[1]{%
13161   {%
13162     \LWR@HTML@ebweight%
13163     \InlineClass{texteb}{#1}%
13164   }%
13165 }
13166
13167 \LWR@formatted{texteb}
13168 }{% if not loaded
13169   \providerobustcmd{\texteb}[1]{}
13170 }
```

`\textlg` $\langle text \rangle$ From `nfssect-cfr`.

```
13171 \IfPackageLoadedTF{nfssect-cfr}{
13172 \DeclareRobustCommand{\LWR@HTML@textlg}[1]{%
13173   {%
13174     \LWR@HTML@lgweight%
13175     \InlineClass{textlg}{#1}%
13176   }%
13177 }
13178
13179 \LWR@formatted{textlg}
13180 }{% if not loaded
13181   \providerobustcmd{\textlg}[1]{}
13182 }
```

`\textrm` $\langle text \rangle$

```
13183 \DeclareRobustCommand{\LWR@HTML@textrm}[1]{%
13184   {%
13185     \LWR@HTML@rmfamily%
13186     \InlineClass(font-family:serif){textrm}{#1}%
13187   }%
13188 }
13189
13190 \LWR@formatted{textrm}
```

`\textsf {<text>}`

```
13191 \DeclareRobustCommand{\LWR@HTML@textsf}[1]{%
13192   {%
13193     \LWR@HTML@sfamily%
13194     \InlineClass(font-family:sans){textsf}{#1}%
13195   }%
13196 }
13197
13198 \LWR@formatted{textsf}
```

`\texttt {<text>}`

```
13199 \DeclareRobustCommand{\LWR@HTML@texttt}[1]{%
13200   {%
13201     \LWR@HTML@ttfamily%
13202     \LWR@htmlspan{kbd}{#1}%
13203   }%
13204 }
13205
13206 \LWR@formatted{texttt}
```

`\textup {<text>}`

```
13207 \DeclareRobustCommand{\LWR@HTML@textup}[1]{%
13208   {%
13209     \LWR@HTML@upshape%
13210     \InlineClass(font-style:normal){textup}{#1}%
13211   }%
13212 }
13213
13214 \LWR@formatted{textup}
```

`\textit {<text>}`

```
13215 \DeclareRobustCommand{\LWR@HTML@textit}[1]{%
13216   {%
13217     \LWR@HTML@itshape%
13218     \LWR@htmlspan{i}{#1}%
13219   }%
13220 }
13221
13222 \LWR@formatted{textit}
```

`\textsc {<text>}`

```
13223 \DeclareRobustCommand{\LWR@HTML@textsc}[1]{%
13224   {%
13225     \LWR@HTML@scshape%
13226     \InlineClass{textsc}{#1}%
13227   }%
13228 }
13229
13230 \LWR@formatted{textsc}
```

`\textulc {<text>}` From fontaxes.

```

13231 \DeclareRobustCommand{\LWR@HTML@textulc}[1]{%
13232   {%
13233     \LWR@HTML@ulcshape%
13234     \InlineClass{textulc}{#1}%
13235   }%
13236 }
13237
13238 \LWR@formatted{textulc}

```

`\textsi` {*⟨text⟩*}

```

13239 \@ifundefined{textsi}{
13240   \LetLtxMacro\LWR@print@textsi\LWR@print@textsc
13241 }{}
13242
13243 \DeclareRobustCommand{\LWR@HTML@textsi}[1]{%
13244   {%
13245     \LWR@HTML@sishape%
13246     \textsc{\textit{#1}}%
13247     \InlineClass(
13248       font-style: italic;
13249       font-variant: small-caps ;
13250       font-variant-numeric: oldstyle-nums ;
13251     ){textsi}{#1}%
13252   }%
13253 }
13254
13255 \LWR@formatted{textsi}

```

`\textsl` {*⟨text⟩*}

```

13256 \DeclareRobustCommand{\LWR@HTML@textsl}[1]{%
13257   {%
13258     \slshape%
13259     \InlineClass(font-style:oblique){textsl}{#1}%
13260   }%
13261 }
13262
13263 \LWR@formatted{textsl}

```

`\textssc` {*⟨text⟩*}

```

13264 \newrobustcmd{\LWR@HTML@textssc}[1]{\textsc{#1}}
13265 \LWR@formatted{textssc}

```

`\textnormal` {*⟨text⟩*}

```

13266 \DeclareRobustCommand{\LWR@HTML@textnormal}[1]{%
13267   \LWR@HTML@mdseries%
13268   \LWR@HTML@rmfamily%
13269   \LWR@HTML@upshape%
13270   \LWR@HTML@ulcshape%
13271   \InlineClass(%
13272     font-weight: normal;
13273     font-family: serif;
13274     font-style: normal;
13275     font-variant: normal;

```

```

13276         font-variant-numeric: normal ;
13277     ){textnormal}{#1}%
13278 }
13279
13280 \LWR@formatted{textnormal}

13281 \FilenameNullify{%
13282     \LetLtxMacro\emph\@firstofone%
13283     \LetLtxMacro\textmd\@firstofone%
13284     \LetLtxMacro\textbf\@firstofone%
13285     \LetLtxMacro\texteb\@firstofone%
13286     \LetLtxMacro\textlg\@firstofone%
13287     \LetLtxMacro\textrm\@firstofone%
13288     \LetLtxMacro\textsf\@firstofone%
13289     \LetLtxMacro\texttt\@firstofone%
13290     \LetLtxMacro\textup\@firstofone%
13291     \LetLtxMacro\textit\@firstofone%
13292     \LetLtxMacro\textsc\@firstofone%
13293     \LetLtxMacro\textulc\@firstofone%
13294     \LetLtxMacro\textsi\@firstofone%
13295     \LetLtxMacro\textsl\@firstofone%
13296     \LetLtxMacro\textssc\@firstofone%
13297     \LetLtxMacro\textnormal\@firstofone%
13298 }

```

Remembers the current font family, series, and shape. fontaxes support is integrated here.

```

13299 \newcommand*\LWR@f@family}{rm}
13300 \newcommand*\LWR@f@series}{md}
13301 \newcommand*\LWR@f@shape}{up}
13302 \newcommand*\LWR@f@shapecaps}{ulc}

```

`\LWR@textcurrentfont` {<*text*>}

Prints the text with the current font choices. Avoids nesting repeated font selections.

```

13303 \newcounter{LWR@textcurrentfontdepth}
13304 \setcounter{LWR@textcurrentfontdepth}{0}
13305
13306 \newcommand*\LWR@textcurrentfont}[1]{%
13307     \ifnumcomp{\value{LWR@textcurrentfontdepth}}{>}{0}%
13308     {%
13309         \addtocounter{LWR@textcurrentfontdepth}{1}%
13310         #1%
13311         \addtocounter{LWR@textcurrentfontdepth}{-1}%
13312     }%
13313     {%
13314         \addtocounter{LWR@textcurrentfontdepth}{1}%
13315         \ifboolexpr{%
13316             test {\ifdefstring{\LWR@f@family}{rm}} and
13317             test {\ifdefstring{\LWR@f@series}{md}} and
13318             test {\ifdefstring{\LWR@f@shape}{up}} and
13319             test {\ifdefstring{\LWR@f@shapecaps}{ulc}}
13320         }%
13321         {\InlineClass{textnormal}{#1}}%
13322         {%
13323             \InlineClass{%

```

```

13324             text\LWR@family\LWR@origtilde{}%
13325             text\LWR@series\LWR@origtilde{}%
13326             text\LWR@shape\LWR@origtilde{}%
13327             text\LWR@shapecaps%
13328             }%
13329             {#1}%
13330             }%
13331             \addtocounter{LWR@textcurrentfontdepth}{-1}%
13332             }%
13333 }

```

Env `LWR@blocktextcurrentfont` Prints the contents with the current font choices.

```

13334 \newenvironment*{LWR@blocktextcurrentfont}{%
13335 \LWR@stoppars%
13336 \BlockClass{%
13337     text\LWR@family\LWR@origtilde{}%
13338     text\LWR@series\LWR@origtilde{}%
13339     text\LWR@shape\LWR@origtilde{}%
13340     text\LWR@shapecaps%
13341     }%
13342 }{\endBlockClass\LWR@startpars}

```

`\mdseries`

```

13343 \newrobustcmd*{\LWR@HTML@mdseries}{%
13344     \LWR@print@mdseries%
13345     \renewcommand*{\LWR@f@series}{md}%
13346 }
13347 \LWR@formatted{mdseries}

```

`\bfseries`

```

13348 \newrobustcmd*{\LWR@HTML@bfseries}{%
13349     \LWR@print@bfseries%
13350     \renewcommand*{\LWR@f@series}{bf}%
13351 }
13352 \LWR@formatted{bfseries}

```

`\ebweight` From `nfssect-cfr`.

```

13353 \IfPackageLoadedTF{nfssect-cfr}{
13354 \newrobustcmd*{\LWR@HTML@ebweight}{%
13355     \LWR@print@ebweight%
13356     \renewcommand*{\LWR@f@series}{eb}%
13357 }
13358 \LWR@formatted{ebweight}
13359 }{}

```

`\lgweight` From `nfssect-cfr`.

```

13360 \IfPackageLoadedTF{nfssect-cfr}{
13361 \newrobustcmd*{\LWR@HTML@lgweight}{%
13362     \LWR@print@lgweight%
13363     \renewcommand*{\LWR@f@series}{lg}%

```

```

13364 }
13365 \LWR@formatted{lgweight}
13366 }{}

```

`\rmfamily`

```

13367 \newrobustcmd*{\LWR@HTML@rmfamily}{%
13368   \LWR@print@rmfamily%
13369   \renewcommand*{\LWR@f@family}{rm}%
13370 }
13371 \LWR@formatted{rmfamily}

```

`\sffamily`

```

13372 \newrobustcmd*{\LWR@HTML@sffamily}{%
13373   \LWR@print@sffamily%
13374   \renewcommand*{\LWR@f@family}{sf}%
13375 }
13376 \LWR@formatted{sffamily}

```

`\ttfamily`

```

13377 \newrobustcmd*{\LWR@HTML@ttfamily}{%
13378   \LWR@print@ttfamily%
13379   \renewcommand*{\LWR@f@family}{tt}%
13380 }
13381 \LWR@formatted{ttfamily}

```

The following use `\AtBeginDocument` due to the L^AT_EX core `\reinstall@nfss@defs`, which redefines these `\AtBeginDocument`. See **texdoc source2e**.

`\upshape`

```

13382 \newrobustcmd*{\LWR@HTML@upshape}{%
13383   \LWR@print@upshape%
13384   \renewcommand*{\LWR@f@shape}{up}%
13385 }
13386 \AtBeginDocument{\LWR@formatted{upshape}}

```

`\itshape`

```

13387 \newrobustcmd*{\LWR@HTML@itshape}{%
13388   \LWR@print@itshape%
13389   \renewcommand*{\LWR@f@shape}{it}%
13390 }
13391 \AtBeginDocument{\LWR@formatted{itshape}}

```

`\scshape` Note: `\LWR@print@scshape` is not used here since some fonts, such as `erewhon`, copy/paste as all-caps.

```

13392 \newrobustcmd*{\LWR@HTML@scshape}{%
13393   \ifbool{FixSmallCaps}{}%
13394   \LWR@print@scshape%
13395 }%

```

```

13396 \renewcommand*\LWR@f@shapecaps}{sc}%
13397 }
13398 \AtBeginDocument{\LWR@formatted{scshape}}

```

\ulcshape From fontaxes.

```

13399 \@ifundefined{ulcshape}{
13400 \LetLtxMacro\ulcshape\upshape
13401 }{}
13402 \newrobustcmd*\LWR@HTML@ulcshape}{%
13403 \LWR@print@ulcshape%
13404 \renewcommand*\LWR@f@shapecaps}{ulc}%
13405 }
13406 \AtBeginDocument{\LWR@formatted{ulcshape}}

```

\sishape

```

13407 \@ifundefined{sishape}{
13408 \LetLtxMacro\sishape\scshape
13409 }{}
13410 \newrobustcmd*\LWR@HTML@sishape}{%
13411 \ifbool{FixSmallCaps}}{%
13412 \LWR@print@sishape%
13413 }%
13414 \renewcommand*\LWR@f@shape}{it}
13415 \renewcommand*\LWR@f@shapecaps}{sc}%
13416 }
13417 \AtBeginDocument{\LWR@formatted{sishape}}

```

\slshape

```

13418 \newrobustcmd*\LWR@HTML@slshape}{%
13419 \LWR@print@slshape%
13420 \renewcommand*\LWR@f@shape}{sl}%
13421 }
13422 \AtBeginDocument{\LWR@formatted{slshape}}

```

\sscshape

```

13423 \newrobustcmd*\LWR@HTML@sscshape}{\LWR@HTML@scshape}
13424 \AtBeginDocument{\LWR@formatted{sscshape}}

```

\normalfont

```

13425 \newrobustcmd*\LWR@HTML@normalfont}{\rmfamily\mdseries\upshape\ulcshape}
13426 \LWR@formatted{normalfont}

13427 \FilenameNullify{%
13428 \LetLtxMacro\rmfamily\@empty%
13429 \LetLtxMacro\sffamily\@empty%
13430 \LetLtxMacro\ttfamily\@empty%
13431 \LetLtxMacro\bfseries\@empty%
13432 \LetLtxMacro\ebweight\@empty%
13433 \LetLtxMacro\lgweight\@empty%
13434 \LetLtxMacro\mdseries\@empty%
13435 \LetLtxMacro\upshape\@empty%

```

```

13436 \LetLtxMacro\slshape\@empty%
13437 \LetLtxMacro\sisshape\@empty%
13438 \LetLtxMacro\scshape\@empty%
13439 \LetLtxMacro\itshape\@empty%
13440 \LetLtxMacro\ulcshape\@empty%
13441 \LetLtxMacro\sscshape\@empty%
13442 \LetLtxMacro\normalfont\@empty%
13443 }

```

`\sp` $\langle text \rangle$

For siunitx. Must work in math mode.

```
13444 \renewcommand{\sp}[1]{\text{<sup>#1</sup>}}
```

`\sb` $\langle text \rangle$

For siunitx. Must work in math mode.

```
13445 \renewcommand{\sb}[1]{\text{<sub>#1</sub>}}
```

`\textsuperscript` $\langle text \rangle$

```

13446 \newrobustcmd{\LWR@HTML@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
13447 \LWR@formatted{textsuperscript}

```

`\@textsuperscript` $\langle text \rangle$

```

13448 \newcommand{\LWR@HTML@@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
13449 \LWR@formatted{@textsuperscript}

```

`\textsubscript` $\langle text \rangle$

```

13450 \newrobustcmd{\LWR@HTML@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
13451 \LWR@formatted{textsubscript}

```

`\@textsubscript` $\langle text \rangle$

```

13452 \newcommand{\LWR@HTML@@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
13453 \LWR@formatted{@textsubscript}

```

`\up` $\langle text \rangle$ Prints superscript.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
13454 \AtBeginDocument{\let\up\textsuperscript}
```

`\fup` $\langle text \rangle$ Prints superscript.

Supports `fntcount` package.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
13455 \AtBeginDocument{\let\fup\textsuperscript}
```

`\underline` {<*text*>}

```
13456 \renewcommand{\underline}[1]{%
13457   \InlineClass%
13458     (text-decoration:underline; text-decoration-skip: auto)%
13459     {\underline}{#1}%
13460 }
```

`\LWR@overline` {<*text*>}

```
13461 \newcommand{\LWR@overline}[1]{%
13462   \InlineClass%
13463     (text-decoration:overline; text-decoration-skip: auto)%
13464     {\overline}{#1}%
13465 }
```

`\LWR@currenttextcolor` The color to use for text and `\rule`, defaulting to black:

```
13466 \newcommand*{\LWR@currenttextcolor}{black}
```

`\LWR@tempcolor` The color converted to HTML colorspace.

`\LWR@tempcolortwo`

```
\LWR@tempcolorthree 13467 \newcommand*{\LWR@tempcolor}{}
13468 \newcommand*{\LWR@tempcolortwo}{}
13469 \newcommand*{\LWR@tempcolorthree}{}

```

`\LWR@findcurrenttextcolor` Sets `\LWR@tempcolor` to the current color.

```
13470 \newcommand*{\LWR@findcurrenttextcolor}{%
13471   \renewcommand{\LWR@tempcolor}{000000}%
13472 }
```

`\LWR@textcurrentcolor` {<*text*>} Like `\textcolor` but uses the current `\color` instead.

```
13473 \NewDocumentCommand{\LWR@textcurrentcolor}{m}{%
13474   \renewcommand*{\LWR@currenttextcolor}{black}%
13475   #1%
13476 }
```

```
13477 \end{warphTML}
```

for PRINT output: 13478 `\begin{warpprint}`

`\LWR@textcurrentfont` {<*text*>}

Prints the text with the current font choices.

```
13479 \newcommand*{\LWR@textcurrentfont}[1]{#1}
```

Env `\LWR@blocktextcurrentfont` Prints the contents with the current font choices.

```
13480 \newenvironment*{\LWR@blocktextcurrentfont}{}{}
```

```
\FilenameNullify {⟨macros to nullify⟩}

13481 \newcommand*\FilenameNullify[1]{}

13482 \end{warpprint}
```

96 Skips, spaces, font sizes

for HTML output: 13483 \begin{warpHTML}

`\`, and `\thinspace` may be redefined by other packages, so are redefined `\AtBeginDocument` here.

Direct-formatting space commands become HTML entities:

```
13484 \AtBeginDocument{
13485 \renewrobustcmd*\,}{\HTMLUnicode{202f}} % HTML thin non-breakable space
13486 \renewrobustcmd*\thinspace}{\HTMLUnicode{202f}} % HTML thin non-breakable space
13487 \renewrobustcmd*\negthinspace}{\HTMLUnicode{202f}} % HTML thin non-breakable space
13488 \renewrobustcmd*~}{\HTMLEntity{nbsp}}
13489 \renewrobustcmd*\textellipsis}{\HTMLUnicode{2026}}
13490 \renewrobustcmd*\vdots}{\HTMLUnicode{22EE}}
13491 }
```

Direct-formatting font sizes are remembered for future use:

```
13492 \newcommand*\LWR@font@size}{normalsize}
13493
13494 \newrobustcmd*\LWR@HTML@normalsize}{\renewcommand*\LWR@font@size}{normalsize}}
13495 \LWR@formatted{normalsize}
13496
13497 \newrobustcmd*\LWR@HTML@small}{\renewcommand*\LWR@font@size}{small}}
13498 \LWR@formatted{small}
13499
13500 \newrobustcmd*\LWR@HTML@footnotesize}{\renewcommand*\LWR@font@size}{footnotesize}}
13501 \LWR@formatted{footnotesize}
13502
13503 \newrobustcmd*\LWR@HTML@scriptsize}{\renewcommand*\LWR@font@size}{scriptsize}}
13504 \LWR@formatted{scriptsize}
13505
13506 \newrobustcmd*\LWR@HTML@tiny}{\renewcommand*\LWR@font@size}{tiny}}
13507 \LWR@formatted{tiny}
13508
13509 \newrobustcmd*\LWR@HTML@large}{\renewcommand*\LWR@font@size}{large}}
13510 \LWR@formatted{large}
13511
13512 \newrobustcmd*\LWR@HTML@Large}{\renewcommand*\LWR@font@size}{Large}}
13513 \LWR@formatted{Large}
13514
13515 \newrobustcmd*\LWR@HTML@LARGE}{\renewcommand*\LWR@font@size}{LARGE}}
13516 \LWR@formatted{LARGE}
13517
13518 \newrobustcmd*\LWR@HTML@huge}{\renewcommand*\LWR@font@size}{huge}}
13519 \LWR@formatted{huge}
13520
13521 \newrobustcmd*\LWR@HTML@Huge}{\renewcommand*\LWR@font@size}{Huge}}
13522 \LWR@formatted{Huge}
```

```

13523 \DeclareDocumentCommand{\onecolumn}{}{=}
13524
13525 \DeclareDocumentCommand{\twocolumn}{0}{=}
13526
13527 #1
13528
13529 }

```

\hfill

```

13530 \newcommand*{\LWR@HTML@hfill}{\quad}
13531 \LWR@formatted{hfill}

```

\hrulefill

```

13532 \newcommand*{\LWR@HTML@hrulefill}{%
13533   \ifbool{LWR@doingapar}%
13534     {\rule{1in}{1pt}}%
13535     {%
13536       \LWR@findcurrenttextcolor%
13537       \ifdefstring{\LWR@tempcolor}{000000}%
13538       {%
13539         \begin{BlockClass}{hrule}%
13540         \end{BlockClass}%
13541       }%
13542     }%
13543     \begin{BlockClass}[%
13544       border-top: 1px solid \LWR@origpound\LWR@tempcolor % space
13545     ]{hrule}%
13546     \end{BlockClass}%
13547   }%
13548 }%
13549 }%
13550 \LWR@formatted{hrulefill}

```

\dotfill

```

13551 \newcommand*{\LWR@HTML@dotfill}{\dots}
13552 \LWR@formatted{dotfill}

```

\newpage

```

13553 \renewcommand*{\newpage}{
13554
13555 }

```

\newline

 Uses the HTML `
` element.

```

13556 \newrobustcmd*{\LWR@newlinebr}{\unskip\LWR@htmltag{br /}\LWR@orignewline}%
13557 \LetLtxMacro\newline\LWR@newlinebr

```

Redefined to `\LWR@endofline` or `\LWR@tabularendofline`.

`\LWR@endofline` * [*len*]

`\` is assigned to `\LWR@endofline` at `\LWR@LwarpStart`.

Inside `tabular`, `\` is temporarily changed to `\LWR@tabularendofline`.

```
13558 \LetLtxMacro\LWR@origendofline\
13559 \NewDocumentCommand{\LWR@endofline}{s O{0pt}}
13560 {%
13561 \newline%

13562 \setlength{\LWR@templengthone}{#2}%
13563 \ifdingreater{\LWR@templengthone}{0pt}{\newline}{}%
13564 }
```

`\LWR@minipagestartpars` Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a `<div>` to be inside a `p`, paragraphs must be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, `lwarp` correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to be on its own line. Since people often place small horizontal space between minipages, it is desirable to maintain this space if possible. `lwarp` tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around `\hspace`, `\enskip`, `\quad`, and `\qquad` until the end of the paragraph, when the closing `p` tag is created.

`\hspace`
`\enskip`
`\quad`
`\qquad`

When a minipage is seen, the boolean `LWR@minipagethispar` is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. `LWR@minipagethispar` is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before `\hspace`, `\quad`, or `\qquad`'s HTML output.

```
13565 \newcommand*{\LWR@minipagestartpars}{%
13566   \ifbool{LWR@minipagethispar}{\LWR@startpars}{}%
13567 }
```

`\LWR@minipagestoppars` Placed just after `\hspace`, `\quad`, or `\qquad`'s HTML output.

```
13568 \newcommand*{\LWR@minipagestoppars}{%
13569   \ifbool{LWR@minipagethispar}{\LWR@stoppars}{}%
13570 }
```

`\quad` Handles special minipage & horizontal space interactions. Uses `2003 EM SPACE` to pass validation.

```
13571 \renewrobustcmd*{\quad}{%
13572   \LWR@minipagestoppars%
13573   \HTMLunicode{2003}%
13574   \LWR@minipagestartpars%
13575 }
```

`\qquad` Handles special minipage & horizontal space interactions.

```
13576 \renewrobustcmd*{\qquad}{\quad\quad}
```

`\enskip` Handles special minipage & horizontal space interactions.

```
13577 \renewrobustcmd*{\enskip}{%
13578   \LWR@minipagestoppars%
13579   \HTMLUnicode{2002}%
13580   \LWR@minipagestartpars%
13581 }
```

Len `\LWR@tempwidth` Used to compute span width, height, raise for `\hspace` and `\rule`:

Len `\LWR@tempheight`

Len `\LWR@tempraise`

```
13582 \newlength{\LWR@tempwidth}
13583 \newlength{\LWR@tempheight}
13584 \newlength{\LWR@tempraise}
```

```
\LWR@select@html@hspace * {<length>} * {<length>}
\hspace
```

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

`\hspace{fill}` is converted to `\hspace{2em}`, equal to `\quad`.

```
13585 \newcommand{\LWR@select@html@hspace}{%
13586 \RenewDocumentCommand{\hspace}{s m}{%
13587 \setlength{\LWR@tempwidth}{##2}%
```

If `fill`, change to `\quad`:

```
13588 \ifnum\gluestretchorder\LWR@tempwidth>0%
13589 \setlength{\LWR@tempwidth}{2em}%
13590 \fi%
```

Only if the width is greater than zero:

```
13591 \ifdimcomp{\LWR@tempwidth}{>}{0pt}{%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
13592   \LWR@minipagestoppars%
```

Support the HTML thin wrappable space:

```
13593   \ifdimcomp{\LWR@tempwidth}{=}{.16667em}%
13594   {%
13595     \HTMLUnicode{2009}% thin breakable space
13596   }%
```

Print the span with the converted width. Not rounded.

```
13597   {%
13598     \LWR@htmltagc{%
13599     span style=\textquotedbl{}width:\LWR@printlength{\LWR@tempwidth}; % extra space
13600     display:inline-block\textquotedbl%
13601   }%
```

If formatting for a word processor, approximate with a number of \quads, in case a span of a given width is not supported:

```

13602     \ifbool{FormatWP}{%
13603         \setlength{\LWR@templengthone}{\LWR@tempwidth}%
13604         \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
13605             \quad%
13606             \addtolength{\LWR@templengthone}{-1em}%
13607         }%
13608     }%

```

If NOT formatting for a word processor, include an empty comment to avoid an empty span:

```

13609     {\LWR@htmlcomment{}}%

```

Close the span:

```

13610     \LWR@htmltagc{/span}%
13611 }%

```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```

13612     \LWR@minipagestartpars%
13613 }{}% width greater than 0
13614 }%
13615 }

```

```

\LWR@select@html@nohspace * {\langle length \rangle}
\hspace

```

Used to disable \hspace while creating description \items.

```

13616 \newcommand{\LWR@select@html@nohspace}{%
13617     \RenewDocumentCommand{\hspace}{s m}{}%
13618 }

```

```

\LWR@select@print@hspace

```

```

13619 \newcommand*{\LWR@select@print@hspace}{%
13620     \renewrobustcmd\hspace{\@ifstar\@hspacer\@hspace}%
13621 }

```

```

\hspace * {\langle length \rangle}

```

Handles special minipage & horizontal space interactions.

```

13622 \LWR@select@html@hspace

```

```

\LWR@vspace * {\langle length \rangle} Nullified vspace.

```

```

13623 \NewDocumentCommand{\LWR@HTML@vspace}{s m}{}
13624
13625 \LWR@formatted{vspace}

```

`\linebreak` [$\langle num \rangle$] Inserts an HTML br tag.

```
13626 \renewcommand*\linebreak[1][\newline]
```

`\nolinebreak` [$\langle num \rangle$]

```
13627 \renewcommand*\nolinebreak[1][\]
```

`\pagebreak` [$\langle num \rangle$] Starts a new paragraph.

```
13628 \renewcommand*\pagebreak[1][\par]
13629
13630 }
```

`\nopagebreak` [$\langle num \rangle$]

```
13631 \renewcommand*\nopagebreak[1][\]
```

`\enlargethispage` * $\langle len \rangle$

```
13632 \RenewDocumentCommand{\enlargethispage}{s m}{}
```

`\clearpage`

`\cleardoublepage`

```
13633 \renewcommand*\clearpage{}
13634 \renewcommand*\cleardoublepage{}
```

`\rule` [$\langle raise \rangle$] $\langle width \rangle$ $\langle height \rangle$

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

`\fill` is zero-width, so `\hspace{\fill}` is ignored.

```
13635 \newcommand*\LWR@HTML@rule[3][\%
```

The width is copied into a temporary L^AT_EX length, from which comparisons and conversions may be made:

```
13636 \setlength{\LWR@tempwidth}{#2}%
```

If it's zero-width then skip the entire rule:

```
13637 \ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}%
13638 {}% zero- width
13639 {% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
13640 \ifthenelse{%
13641 \lengthtest{\LWR@tempwidth>0pt}\AND%
13642 \lengthtest{\LWR@tempwidth<1pt}%
```

```

13643   }%
13644     {\setlength{\LWR@tempwidth}{1pt}}%
13645     }%

```

Likewise with height:

```

13646   \setlength{\LWR@tempheight}{#3}%
13647   \ifthenelse{%
13648     \lengthtest{\LWR@tempheight>0pt}\AND%
13649     \lengthtest{\LWR@tempheight<1pt}}%
13650   }%
13651     {\setlength{\LWR@tempheight}{1pt}}%
13652     }%

```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```

13653   \LWR@minipagestoppars%

```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in L^AT_EX code.

```

13654   \LWR@findcurrenttextcolor%
13655   \LWR@htmltagc{%
13656   span\LWR@indentHTML%
13657   style=\textquotedbl%

```

The HTML background color is used to draw the filled rule according to the L^AT_EX foreground color set by `\textcolor`.

```

13658   \ifbool{FormatWP}{\background:\LWR@currenttextcolor ; }%

```

The width and height are printed, converted to PT:

```

13659   width:\LWR@printlength{\LWR@tempwidth} ; %
13660   height:\LWR@printlength{\LWR@tempheight} ; %

```

The raise height is converted to a CSS transform. The *2 raise multiplier is to approximately match HTML output's X height. Conversion to a L^AT_EX length allows a typical L^AT_EX expression to be used as an argument for the raise, whereas printing the raise argument directly to HTML output without conversion to a L^AT_EX length limits the allowable syntax. To do: A superior method would compute a ratio of L^AT_EX ex height, then print that to HTML with an ex unit.

```

13661   \ifblank{#1}%
13662   {}%
13663   {%
13664     \setlength{\LWR@tempraise}{0pt-#1}%
13665     \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
13666     \LWR@indentHTML%
13667     -ms-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
13668     \LWR@indentHTML%
13669     -webkit-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
13670     \LWR@indentHTML%
13671     transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
13672     \LWR@indentHTML%
13673   }%

```

Display inline-block to place the span inline with the text:

```
13674   display:inline-block;\textquotedbl\LWR@orignewline%
13675   }%
```

If formatting for a word processor, approximate with a number of underscores, in case a span of a given width is not supported:

```
13676   \ifbool{FormatWP}{%
13677       \setlength{\LWR@templengthone}{\LWR@tempwidth}%
13678       \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
13679           \_{}%
13680           \addtolength{\LWR@templengthone}{-1em}%
13681       }%
13682   }%
```

If NOT formatting for a word processor, add a comment to avoid an empty :

```
13683   {\LWR@htmlcomment{}}%
```

Close the span:

```
13684   \LWR@htmltagc{/span}%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
13685   \LWR@minipagestartpars%
13686 }% non-zero width
13687 }
13688
13689 \LWR@formatted{rule}

13690 \end{warpHTML}
```

97 \phantomsection

for HTML output: 13691 \begin{warpHTML}

\LWR@phantomsection Emulate the hyperref \phantomsection command, often used to insert the bibliography into the table of contents. Ignores \ForceHTMLTOC.

```
13692 \newrobustcmd*{\LWR@phantomsection}{%
13693   \begingroup%
13694   \boolfalse{\LWR@forcinghtmltoc}%
13695   \section*{}%
13696   \endgroup%
13697 }

13698 \end{warpHTML}
```

98 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally set by \LWR@formatted.

For css conversions, see:

<http://edward.oconnor.cx/2007/08/tex-poshlet>

<http://nitens.org/taraborelli/texlogo>

and the spacing described in the metafont package documentation.

```

for HTML & PRINT: 13699 \begin{warpall}
13700 \newbool{LWR@warnXe}
13701 \boolfalse{LWR@warnXe}
13702
13703 \newrobustcmd*{\Xe}
13704   {%
13705     X\hspace{-.1667em}\raisebox{-.5ex}{E}%
13706     \global\booltrue{LWR@warnXe}%
13707   }
13708
13709 \AtBeginDocument{
13710   \IfPackageLoadedTF{graphics}{
13711     \IfPackageLoadedTF{metalogo}{}{
13712       \renewrobustcmd*{\Xe}
13713         {X\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}}
13714     }
13715   }{}
13716 }
13717
13718 \AtEndDocument{
13719   \ifbool{LWR@warnXe}{
13720     \PackageNoteNoLine{lwarp}{Load graphicx or graphics
13721       for improved XeTeX logo}
13722   }{}
13723 }
13724
13725 \providerobustcmd*{\XeTeX}{\mbox{\Xe\hspace{-.125em}\TeX}}
13726 \providerobustcmd*{\XeLaTeX}{\mbox{\Xe\hspace{-.125em}\LaTeX}}
13727 \providerobustcmd*{\AmS}{%
13728   \leavevmode\hbox{$\mathcal A\kern-.2em\lower.376ex%
13729   \hbox{$\mathcal M\kern-.2em\mathcal S$}%
13730 }
13731 \newrobustcmd*{\LyX}{\textsf{LyX}}
13732 \providerobustcmd*{\LuaTeX}{\mbox{Lua\TeX}}
13733 \providerobustcmd*{\LuaLaTeX}{\mbox{Lua\LaTeX}}
13734 \providerobustcmd*{\BibTeX}{\mbox{B\textsc{ib}\TeX}}
13735 \providerobustcmd*{\MakeIndex}{\mbox{\textit{MakeIndex}}}
13736 \providerobustcmd*{\ConTeXt}{\mbox{Con\TeX{t}}}
13737 \providerobustcmd*{\MiKTeX}{\mbox{MiK\TeX}}
13738 \end{warpall}

```

```

for HTML output: 13739 \begin{warpHTML}

```

The print-mode versions of the following may be changed by metalogo, so their print formatting is recorded \AtBeginDocument.

`\TeX` `TEX`

`latexlogo` is a css class used to properly typeset the E and A in `LATEX` and friends.

`latexlogofont` is a css class used to select the font for the rest of the logo in `LATEX`, `LuaTEX`, `ConTEXt`, etc.

```

13740 \newrobustcmd*{\LWR@HTML@TeX}
13741 {%
13742   \InlineClass{latexlogofont}%
13743   {%
13744     \InlineClass{latexlogo}%
13745     {%
13746       T%
13747       \InlineClass{latexlogosub}{e}%
13748       X%
13749     }%
13750   }%
13751 }
13752 \AtBeginDocument{\LWR@formatted{TeX}}% may have been patched by metalogo

```

`\LaTeX` `LATEX`, `LATEX 2ε`

`\LaTeXe`

```

13753 \newrobustcmd*{\LWR@HTML@LaTeX}
13754 {%
13755   \InlineClass{latexlogofont}%
13756   {%
13757     \InlineClass{latexlogo}%
13758     {%
13759       L%
13760       \InlineClass{latexlogosup}{a}%
13761       T%
13762       \InlineClass{latexlogosub}{e}%
13763       X%
13764     }%
13765   }%
13766 }
13767
13768 \AtBeginDocument{\LWR@formatted{LaTeX}}% may have been patched by metalogo
13769
13770
13771 \newrobustcmd*{\LWR@HTML@LaTeXe}
13772 {%
13773   \LaTeX%
13774   \InlineClass{latexlogofont}{%
13775     \InlineClass{latexlogotwoe}{%
13776       2%
13777       \InlineClass{latexlogotwoesub}{\HTMLUnicode{03B5}}%
13778     }%
13779   }%
13780 }
13781 \AtBeginDocument{\LWR@formatted{LaTeXe}}% may have been patched by metalogo

```

`\LuaTeX` `LuaTEX`, `LuaLATEX`

`\LuaLaTeX`

```

13782 \newrobustcmd*{\LWR@HTML@LuaTeX}{\InlineClass{latexlogofont}{Lua}\TeX}
13783 \AtBeginDocument{\LWR@formatted{LuaTeX}}% may have been patched by metalogo
13784
13785 \newrobustcmd*{\LWR@HTML@LuaLaTeX}{\InlineClass{latexlogofont}{Lua}\LaTeX}

```

13786 \AtBeginDocument{\LWR@formatted{LuaLaTeX}}% may have been patched by metalogo

\XeTeX X_ƎTeX, X_ƎL^ATeX

\XeLaTeX
xetexlogo is a css class which aligns the backwards E in X_ƎTeX and spaces TeX appropriately.

xelatexlogo is a css class which aligns the backwards E in X_ƎL^ATeX and spaces L^ATeX appropriately.

13787 \newrobustcmd*{\LWR@HTML@Xe}

13788 {%

13789 X%

13790 \InlineClass{xelatexlogosub}{\HTMLunicode{18e}}%

13791 }

13792 \AtBeginDocument{\LWR@formatted{Xe}}% may have been patched by metalogo

13793

13794 \newrobustcmd*{\LWR@HTML@XeTeX}{\InlineClass{xetexlogo}{\Xe}\TeX}

13795 \AtBeginDocument{\LWR@formatted{XeTeX}}% may have been patched by metalogo

13796

13797 \newrobustcmd*{\LWR@HTML@XeLaTeX}{\InlineClass{xelatexlogo}{\Xe}\LaTeX}

13798 \AtBeginDocument{\LWR@formatted{XeLaTeX}}% may have been patched by metalogo

\ConTeXt ConTeXt

13799 \newrobustcmd*{\LWR@HTML@ConTeXt}{%

13800 \InlineClass{latexlogofont}{Con}\TeX{}}%

13801 \InlineClass{latexlogofont}{t}}%

13802 }

13803 \LWR@formatted{ConTeXt}

\BibTeX BIB_TEX, *MakeIndex*

\MakeIndex

13804 \newrobustcmd*{\LWR@HTML@BibTeX}

13805 {\InlineClass{latexlogofont}{B\textsc{ib}}\TeX}

13806 \LWR@formatted{BibTeX}

13807

13808 \newrobustcmd*{\LWR@HTML@MakeIndex}

13809 {\InlineClass{latexlogofont}{\textit{MakeIndex}}}

13810 \LWR@formatted{MakeIndex}

\AmS *AMS*

amslogo is a css class used for the *AMS* logo.

13811 \AtBeginDocument{%

13812 \newrobustcmd*{\LWR@HTML@AmS}

13813 {%

13814 \InlineClass{amslogo}{%

13815 \textit{%

13816 A%

13817 \InlineClass{latexlogosub}{M}}%

13818 S%

13819 }%

13820 }%

13821 }%

13822 \LWR@formatted{AmS}

13823 }

`\MiKTeX` `MiKTeX`

```
13824 \newrobustcmd*{\LWR@HTML@MiKTeX}{\InlineClass{latexlogofont}{MiK}\TeX}
13825 \LWR@formatted{MiKTeX}
```

`\LyX` `LyX`

`lyxlogo` is a css class used for the LyX logo.

```
13826 \newrobustcmd*{\LWR@HTML@LyX}{\InlineClass{lyxlogo}{LyX}}
13827 \LWR@formatted{LyX}
```

```
13828 \end{warpHTML}
```

99 Starting and stopping lwarp

for HTML output: `13829 \begin{warpHTML}`

`\LWR@LwarpStart` Automatically sets up the HTML-related actions for the start and end of the document.
`\LWR@LwarpEnd` ment.

```
13830 \AfterEndPreamble{\LWR@LwarpStart}
13831 \AtEndDocument{\LWR@LwarpEnd}
13832 \DeclareHookRule{enddocument}{lwarp}{after}{legacy}

13833 \end{warpHTML}
```

100 Loading array

`array` is required for lwarp's column parsing. It and its patches are now loaded.

for HTML output: `13834 \begin{warpHTML}`
`13835 \RequirePackage{array}`

The following are compared with the tabular preamble > to add css classes to adjust tabular cells. Defined here now that `\arraybackslash` is defined after `array` is loaded.

```
13836 \edef\LWR@detect@centeringarraybackslash{\centering\arraybackslash}
13837 \edef\LWR@detect@raggedrightarraybackslash{\raggedright\arraybackslash}
13838 \edef\LWR@detect@raggedleftarraybackslash{\raggedleft\arraybackslash}
13839 \def\LWR@detect@itshape{\itshape}
13840 \def\LWR@detect@bfseries{\bfseries}
13841 \def\LWR@detect@bfit{\bfseries\itshape}
13842 \end{warpHTML}
```

101 Loading everyshi patches

`everyshi` is emulated by the L^AT_EX core, so its patches are loaded here. `\AtBeginDocument` is used in case an older version of L^AT_EX is used.

```

for HTML output: 13843 \begin{warpHTML}
13844 \AtBeginDocument{
13845   \IfPackageLoadedTF{everyshi}{
13846     \RequirePackage{lwarp-everyshi}
13847   }{}
13848 }
13849 \end{warpHTML}

```

102 Loading textcomp patches

textcomp has now been integrated into the L^AT_EX core, so its patches are loaded now.

```

for HTML output: 13850 \begin{warpHTML}
13851 \RequirePackage{lwarp-textcomp}
13852 \end{warpHTML}

```

103 Loading amsmath, amsthm patches, centernot

amsmath, amsthm, and centernot may have been preloaded, such as by newtx, so their patches are loaded now.

```

for HTML output: 13853 \begin{warpHTML}
13854 \IfPackageLoadedTF{amsthm}{
13855   \RequirePackage{lwarp-amsthm}
13856 }{}

13857 \IfPackageLoadedTF{amsmath}{
13858   \RequirePackage{lwarp-amsmath}
13859 }{}

```

amsthm may load centernot, so centernot must be checked second.

```

13860 \IfPackageLoadedTF{centernot}{
13861   \RequirePackage{lwarp-centernot}
13862 }{}
13863 \end{warpHTML}

```

104 Loading KOMA-SCRIPT class patches

Load patches to koma-script.

```

for HTML output: 13864 \begin{warpHTML}

13865 \IfClassLoadedTF{scrbook}{\RequirePackage{lwarp-patch-komascript}}{}
13866 \IfClassLoadedTF{scrartcl}{\RequirePackage{lwarp-patch-komascript}}{}
13867 \IfClassLoadedTF{scrreprt}{\RequirePackage{lwarp-patch-komascript}}{}

13868 \end{warpHTML}

```

105 Loading MEMOIR class patches

Load patches to memoir.

```
for PRINT output: 13869 \begin{warpprint}
13870 \IfClassLoadedTF{memoir}{\LWR@origRequirePackage{xcolor}}{}
13871 \end{warpprint}
```

```
for HTML output: 13872 \begin{warpHTML}
13873 \IfClassLoadedTF{memoir}{\RequirePackage{lwarp-patch-memoir}}{}
13874 \end{warpHTML}
```

106 ut* class patches

Load patches to uj* and ut* classes, as well as ltj* classes.

```
for HTML output: 13875 \begin{warpHTML}

13876 \newcommand*\LWR@patchujtclasses}{

    uj/t does not use \partname

13877     \def\@partnameformat{}

13878     \def\@partcntformat##1{%
13879         \prepartname%
13880         \csname the##1\endcsname%
13881         \postpartname%
13882         \quad%
13883     }
13884     \@ifundefined{chapter}{}{
13885         \def\@chapcntformat##1{%
13886             \prechaptername%
13887             \csname the##1\endcsname%
13888             \postchaptername%
13889             \quad%
13890         }
13891     }
13892     \renewcommand*\LWR@printchaptername}{}
```

Use decimal points instead of centered dots:

```
13893     \renewcommand{\thepart}{\@Roman\c@part}
13894     \@ifundefined{chapter}{
13895         \renewcommand{\thesection}{\@arabic\c@section}
13896     }{
13897         \renewcommand{\thechapter}{\@arabic\c@chapter}
13898         \renewcommand{\thesection}{\thechapter.\@arabic\c@section}
13899     }
13900     \renewcommand{\thesubsection}{\thesection.\@arabic\c@subsection}
13901     \renewcommand{\thesubsubsection}{%
13902         \thesubsection.\@arabic\c@subsubsection}
13903     \renewcommand{\theparagraph}{%
13904         \thesubsubsection.\@arabic\c@paragraph}
13905     \renewcommand{\thesubparagraph}{%
```

```

13906 \theparagraph.\@arabic\c@subparagraph}
13907 \@ifundefined{chapter}{
13908     \renewcommand{\thefigure}{\@arabic\c@figure}
13909     \renewcommand{\thetable}{\@arabic\c@table}
13910 }{
13911     \renewcommand{\thefigure}{%
13912     \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@figure}
13913     \renewcommand{\thetable}{%
13914     \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@table}
13915 }
13916 }
13917
13918 \IfClassLoadedTF{ujarticle}{\LWR@patchujtclasses}{}
13919 \IfClassLoadedTF{ujbook}{\LWR@patchujtclasses}{}
13920 \IfClassLoadedTF{ujreport}{\LWR@patchujtclasses}{}
13921 \IfClassLoadedTF{utarticle}{\LWR@patchujtclasses}{}
13922 \IfClassLoadedTF{utbook}{\LWR@patchujtclasses}{}
13923 \IfClassLoadedTF{utreport}{\LWR@patchujtclasses}{}
13924 \IfClassLoadedTF{ltjarticle}{\LWR@patchujtclasses}{}
13925 \IfClassLoadedTF{ltjbook}{\LWR@patchujtclasses}{}
13926 \IfClassLoadedTF{ltjreport}{\LWR@patchujtclasses}{}
13927 \IfClassLoadedTF{ltjsarticle}{\LWR@patchujtclasses}{}
13928 \IfClassLoadedTF{ltjsbook}{\LWR@patchujtclasses}{}
13929 \IfClassLoadedTF{ltjsreport}{\LWR@patchujtclasses}{}
13930 \IfClassLoadedTF{ltjskiyou}{\LWR@patchujtclasses}{}
13931 \IfClassLoadedTF{ltjspf}{\LWR@patchujtclasses}{}
13932 \IfClassLoadedTF{ltjtarticle}{\LWR@patchujtclasses}{}
13933 \IfClassLoadedTF{ltjtbook}{\LWR@patchujtclasses}{}
13934 \IfClassLoadedTF{ltjtreport}{\LWR@patchujtclasses}{}

13935 \end{warpHTML}

```

107 C_TE_X patches

Patches for ctex and related classes, which are loaded before lwarp.

All C_TE_X classes and the ctex package seem to load ctexpatch, so its presence is used to decide whether to have lwarp patch C_TE_X.

for HTML output: 13936 \begin{warpHTML}

\AtBeginDocument in case the user set FileSectionNames in the preamble.

```

13937 \AtBeginDocument{
13938     \IfPackageLoadedTF{ctexpatch}{%
13939         \def\@partcntformat#1{%
13940             \LWR@isolate{\CTEX@partname}~%
13941             \CTEX@part@aftername%
13942         }%
13943
13944         \def\@partnameformat{}
13945
13946         \def\@chapcntformat#1{%
13947             \LWR@isolate{\CTEX@chaptername}~%
13948             \CTEX@chapter@aftername%
13949         }%
13950

```

```

13951     \renewcommand*{\LWR@printchaptername}{}
13952   }{}
13953 }

13954 \end{warpHTML}

```

108 kotexutf patches

Patch for kotexutf, which is loaded before lwarp.

kotexutf's `\@setref` was conflicting with lwarp's cross references.

for HTML output: 13955 `\begin{warpHTML}`

If kotexutf's version of `\@setref` is detected, it is reverted to the original.

```

13956 \AtBeginDocument{
13957 \IfPackageLoadedTF{kotexutf}{%
13958   \def\LWR@kotexutf@setref#1#2#3{%
13959     \@setref@dhuucs@orig{#1}{#2}{#3}%
13960     \ifx#1\relax\else
13961       \bgroup
13962         \dhuucs@make@CJKchar@null
13963         \edef\@temp{\expandafter#2#1}\global\josatoks\expandafter{\@temp}%
13964         \egroup
13965       \fi%
13966     }%
13967 }
13968 \ifdefequal{\@setref}{\LWR@kotexutf@setref}{
13969   \let\@setref\@setref@dhuucs@orig
13970 }{}
13971 }{}
13972 }

13973 \end{warpHTML}

```

109 babel and polyglossia warnings

lwarp prints a message instructing the user how to avoid the following error.

(These are not `\PackageWarnings` because there may not be a problem.)

lwarp uses `cleveref`, which has some limitations when using `polyglossia`, possibly resulting in the error

```
! Undefined control sequence. . . . \__hook begindocument
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by `cleveref`, then select other languages using `\setotherlanguages`.

Once the print version works with `cleveref` and `polyglossia`, the HTML version should work as well using `lwarp`.

```
for HTML output: 13974 \begin{warpHTML}
13975 \AtBeginDocument{
13976
13977 \IfPackageLoadedTF{polyglossia}{
13978   \PackageNoteNoLine{lwarp}
13979   {%
13980     Polyglossia has been loaded. Lwarp also uses cleveref.\MessageBreak
13981     See the cleveref documentation regarding\MessageBreak
13982     polyglossia support. Some languages are not supported.\MessageBreak
13983     --- \MessageBreak
13984     If the error\MessageBreak
13985     \space\space Undefined control sequence ...
13986     \protect\__hook begindocument\MessageBreak
13987     occurs here, use the polyglossia macro:\MessageBreak
13988     \space\space\protect\setmainlanguage\protect{...\protect}
13989   }
13990 }{
13991   \IfPackageLoadedTF{babel}{
13992     \PackageNoteNoLine{lwarp}
13993     {%
13994       Babel has been loaded. Lwarp also uses cleveref.\MessageBreak
13995       See the cleveref documentation regarding\MessageBreak
13996       babel support. Some languages are not supported%
13997     }
13998   }{ }
13999 }
14000
14001 }
14002 \end{warpHTML}
```

110 MATHJAX warnings

```
\LWR@mathjaxwarn {<packagename>} {<More text.>}
```

Issue a warning that MATHJAX is emulated. To be done `\AtBeginDocument`.

```
14003 \newcommand*\LWR@mathjaxwarn[2]{%
14004   \IfPackageLoadedTF{lwarp-#1}{%
14005     \ifblank{#2}{%
14006       \PackageWarningNoLine{lwarp}
14007       {%
14008         Lwarp provides emulation for MathJax when used\MessageBreak
14009         with the #1 package%
14010       }
14011     }{%
14012       \PackageWarningNoLine{lwarp}
14013       {%
14014         Lwarp provides emulation for MathJax when used\MessageBreak
14015         with the #1 package.\MessageBreak
```

```

14016             #2%
14017         }
14018     }%
14019 }{}%
14020 }
14021
14022 % \begin{macro}{\LWR@nomathjaxwarn} \marg{packagename} \marg{More text.}
14023 %
14024 % Issue a warning that \MathJax\ is not supported.
14025 % To be done \cs{AtBeginDocument}.
14026 %
14027 % \changes{v0.894}{2020/12/22}{Warn if using packages not supported by \MathJax.}
14028 % \changes{v0.895}{2021/01/08}{Improved \MathJax\ warning.}
14029 % \begin{macrocode}
14030 \newcommand*\LWR@nomathjaxwarn}[2]{%
14031     \IfPackageLoadedTF{lwarp-#1}{%
14032         \ifblank{#2}{%
14033             \PackageWarningNoLine{lwarp}
14034             {%
14035                 Lwarp does not provide MathJax support for #1.\MessageBreak
14036                 Use SVG math by removing the Lwarp mathjax option%
14037             }
14038         }{}%
14039         \PackageWarningNoLine{lwarp}
14040         {%
14041             Lwarp does not provide MathJax support for #1.\MessageBreak
14042             #2%
14043         }
14044     }%
14045 }{}%
14046 }

```

`\LWR@forceSVGmessage` {<*packagename*>}

```

14047 \newcommand*\LWR@forceSVGmessage}[1]{%
14048     SVG math output may be enabled for select math\MessageBreak
14049     expressions to preserve #1 visual\MessageBreak
14050     features for those particular expressions.\MessageBreak
14051     Before the chosen inline math, use \protect\inlinemathother\MessageBreak
14052     to begin using SVG math, and \protect\inlinemathnormal\MessageBreak
14053     afterward to resume using MathJax math.\MessageBreak
14054     Before display math, use \protect\displaymathother\MessageBreak
14055     to begin using SVG math, and use \protect\displaymathnormal\MessageBreak
14056     after to resume using MathJax for the following math.\MessageBreak
14057     Or, use SVG math for all expressions by removing\MessageBreak
14058     the mathjax option for the lwarp package%
14059 }

```

If MATHJAX is being used, issue a warning for certain packages.

```

14060 \AtBeginDocument{
14061     \ifbool{mathjax}{
14062         \LWR@nomathjaxwarn{aligned-overset}{}
14063         \LWR@nomathjaxwarn{amscdx}{\LWR@forceSVGmessage{amscdx}}
14064         \LWR@mathjaxwarn{arydshln}
14065         {In a math array, do not use the optional argument\MessageBreak
14066         for \protect\cdashline.\space\space
14067         Furthermore, \protect\cline\space is not\MessageBreak
14068         supported by MathJax}

```

```

14069 \LWR@nomathjaxwarn{autoalign}{ }
14070 \LWR@mathjaxwarn{autonum}
14071 {MathJax does not support equation+. \MessageBreak
14072 You may use the warpprint and warpHTML \MessageBreak
14073 environments to isolate the package load \MessageBreak
14074 and the equation+ environments}
14075 \LWR@mathjaxwarn{bigdelim}
14076 {Delimiters appear only of the first line}
14077 \LWR@nomathjaxwarn{boldtensors}{ }
14078 \LWR@mathjaxwarn{booktabs}
14079 {\protect\cmidrule\space is not displayed}
14080 \LWR@mathjaxwarn{breqn}
14081 {Each environment becomes an SVG image}
14082 \LWR@mathjaxwarn{colortbl}
14083 {Colors are ignored in MathJax. \MessageBreak
14084 (Text mode tabular does support colortbl.) \MessageBreak
14085 \LWR@forceSVGmessage{colortbl}}
14086 \LWR@mathjaxwarn{delarray}{ \LWR@forceSVGmessage{delarray}}
14087 \LWR@nomathjaxwarn{gauss}{ \LWR@forceSVGmessage{gauss}}
14088 \LWR@mathjaxwarn{hhline}
14089 {A simple \protect\hline\space is used}
14090 \LWR@mathjaxwarn{isomath}
14091 {Some of the symbol font macros such as \protect\mathsfbit \MessageBreak
14092 do not use a sans font because MathJax does not yet \MessageBreak
14093 have sans Greek. Tensors may look like vectors%
14094 }
14095 \LWR@nomathjaxwarn{jkmath}{ \LWR@forceSVGmessage{jkmath}}
14096 \LWR@mathjaxwarn{libertinust1math}
14097 {Some of the symbol font macros such as \protect\mathsfbit \MessageBreak
14098 do not use a sans font because MathJax does not yet \MessageBreak
14099 have sans Greek. Tensors may look like vectors%
14100 }
14101 \LWR@mathjaxwarn{mathtools}
14102 {See the Lwarp manual regarding the disallowspaces \MessageBreak
14103 and showonlyrefs options, the alignat environment, \MessageBreak
14104 and \protect\DeclarePairedDelimiter\space and related%
14105 }
14106 \LWR@mathjaxwarn{mathspec}
14107 {Double quotes are removed, even inside \protect\text}
14108 \LWR@mathjaxwarn{multirow}
14109 {Multirow works as expected in text mode, but \MessageBreak
14110 limited emulation is provided for MathJax math. \MessageBreak
14111 \protect\multirow\space ignores all arguments except \MessageBreak
14112 the text}
14113 \LWR@mathjaxwarn{nicematrix}
14114 {Keys/values are ignored in MathJax. \MessageBreak
14115 \protect\Cdots, etc. do not span multiple cells. \MessageBreak
14116 AutoNiceMatrix, etc. are not supported for MathJax. \MessageBreak
14117 \protect\CodeBefore\space cannot be done with MathJax. \MessageBreak
14118 \LWR@forceSVGmessage{nicematrix}%
14119 }
14120 \LWR@nomathjaxwarn{pb-diagram}{ \LWR@forceSVGmessage{pb-diagram}}
14121 % \LWR@mathjaxwarn{physics}
14122 % {The third-party extension is not used. \MessageBreak
14123 % {The MathJax v3 extension is used. \MessageBreak
14124 % See the Lwarp manual for details}
14125 \LWR@mathjaxwarn{siunitx}
14126 {Place \protect\sisetup\space before \protect\begin{document}. \MessageBreak
14127 Many optional arguments are ignored}
14128 \LWR@nomathjaxwarn{tensind}{ }

```

```
14129 \LWR@mathjaxwarn{unicode-math}
14130     {Do not use embedded Unicode characters.\MessageBreak
14131     (Not all characters are encoded correctly.)\MessageBreak
14132     Some symbol fonts are not supported by MathJax,\MessageBreak
14133     and are only approximated.\MessageBreak
14134     Greek macros such as \protect\alpha\space respond to the math-style\MessageBreak
14135     option. Latin symbols does not, per MathJax\MessageBreak
14136     limitations, unless placed inside \protect\symbit\space or similar}
14137 \LWR@nomathjaxwarn{unitsdef}{}
14138 \LWR@mathjaxwarn{witharrows}
14139     {Arrows can only point to the next line.\MessageBreak
14140     Text is only placed on a single line}
14141 \LWR@nomathjaxwarn{xy}
14142     {In text, xy works as-is. SVG images will be generated.\MessageBreak
14143     \LWR@forceSVGmessage{xy}}
14144 }{}
14145 }
```

File 2 **lwarp-2in1.sty**§ 111 Package **2in1**

Pkg 2in1 2in1 is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{2in1}File 3 **lwarp-2up.sty**§ 112 Package **2up**

Pkg 2up 2up is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{2up}[2010/05/15]

```

2 \def\source#1#2#3{}
3 \def\target#1#2#3{}
4 \def\targetlayout#1{}
5 \newdimen\pageseplength
6 \newdimen\pagesepwidth
7 \newdimen\pagesepoffset
8 \def\twoupemptypage{}
9 \def\twoupclearpage{}
10 \def\twoupeject{}
11 \def\twouparticle{}
12 \def\twoupplain{}
13 \def\twouplegaltarget{}
14 \def\twouplandscape{}
15 \def\twoupwrites{}

```

File 4 **lwarp-a4.sty**§ 113 Package **a4**

Pkg a4 a4 is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{a4}[2004/04/15]

2 \newcommand*{\WideMargins}{}

File 5 **lwarp-a4wide.sty**§ 114 Package **a4wide**

Pkg a4wide a4wide is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{a4wide}[1994/08/30]

File 6 **lwarp-a5comb.sty**§ 115 Package **a5comb**

Pkg a5comb a5comb is ignored.

for HTML output: `1 \LWR@ProvidesPackageDrop{a5comb}`

File 7 **lwarp-abstract.sty**§ 116 Package **abstract**

(Emulates or patches code by PETER WILSON.)

Pkg abstract abstract is supported and patched by lwarp.

 **missing TOC** If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

for HTML output: memoir provides an abstract environment even though it is not an article or report class. Meanwhile, lwarp loads book to emulate memoir, but book does not have an abstract environment, so when the abstract package is loaded for emulation there is no pre-existing abstract to redefine, which would cause an error. Thus, a null abstract is provide here:

```
1 \ProvideDocumentEnvironment{abstract}{}{}{}
```

Accept all options for lwarp-abstract:

```
2 \LWR@ProvidesPackagePass{abstract}[2009/06/08]
```

```
3 \AtBeginDocument{
4 \BeforeBeginEnvironment{abstract}{
5 \LWR@forcenewpage
6 \BlockClass{abstract}
7 }
8 \AfterEndEnvironment{abstract}{\endBlockClass}
9 }
10
11 \renewcommand{\@bsrunintitle}{%
12 \hspace*{\abstitlekip}%
13 {\abstractnamefont%
14 \InlineClass{abstractrunintitle}{\abstractname}%
15 \@bslabeldelim}%
16 }
```

```
17 \IfClassLoadedTF{memoir}
18 {
19 \renewenvironment{abstract}{%
```

```

20% % \titlepage
21% \null\vfil
22% \@beginparpenalty\@lowpenalty
23 \setup@bstract
24 \ifbsrunin
25 \else
26% \ifbsstyle
27% \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
28% \else
29 \ifnumber@bs
30 \num@bs
31 \else
32 \begin{\absnamepos}%
33 \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
34% \endparpenalty\@M
35 \end\absnamepos%
36 \vspace{\abstitlekip}%
37 \fi
38% \fi
39% \vspace{\abstitlekip}%
40 \fi
41 \put@bsintoc%
42 \begin{@bstr@ctlist}\ifbsrunin\@bsrunintitle\fi\abstracttextfont}%
43 {\par\end{@bstr@ctlist}}\vfil\null%\endtitlepage
44 }
45}{% not memoir
46 \if@titlepage
47 \renewenvironment{abstract}{%
48% \titlepage
49 \null\vfil
50 \@beginparpenalty\@lowpenalty
51 \ifbsrunin
52 \else
53 \ifbsstyle
54 \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
55 \else
56 \ifnumber@bs
57 \num@bs
58 \else
59 \begin{\absnamepos}%
60 \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
61 \endparpenalty\@M
62 \end\absnamepos%
63%% \vspace{\abstitlekip}%
64 \fi
65 \fi
66 \vspace{\abstitlekip}%
67 \fi
68 \put@bsintoc%
69 \begin{@bstr@ctlist}\ifbsrunin\@bsrunintitle\fi\abstracttextfont}%
70 {\par\end{@bstr@ctlist}}\vfil\null%\endtitlepage
71 }
72 \else
73 \renewenvironment{abstract}{%
74 \ifbsrunin
75 \else
76 \ifbsstyle
77 \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
78 \else
79 \ifnumber@bs

```

```

80         \num@bs
81         \else
82 \begin{\absnamepos}%
83 \abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
84 \end\absnamepos%
85 %%         \vspace{\abstitleskip}%
86         \fi
87         \fi
88         \vspace{\abstitleskip}%
89         \fi
90         \put@bsintoc%
91         \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
92         {\par\end{@bstr@ctlist}}
93 \fi
94 }% not memoir

```

File 8 **lwarp-academicons.sty**

§ 117 Package **academicons**

(Emulates or patches code by DIOGO A. B. FERNANDES.)

Pkg academicons

academicons is patched for use by lwarp.

If `\aiicon` is used, the name of the icon is used in the `alt` tag. Otherwise, for each of the individual icon macros, a generic `alt` tag is used.

for HTML output:

```

1 \LWR@ProvidesPackagePass{academicons}[2018/06/27]
2 \LetLtxMacro\LWR@orig@symbol\symbol
3
4 \let\LWR@academicons@orig@AI\AI
5
6 \newcommand*{\LWR@academicons@symbol}[1]{%
7   \begin{lateximage}*[academicon][academicons#1]%
8   \begingroup%
9     \LWR@academicons@orig@AI%
10    \LWR@orig@symbol{#1}%
11    \endgroup%
12    \end{lateximage}%
13 }
14
15 \renewcommand*{\AI}{%
16   \LetLtxMacro\symbol\LWR@academicons@symbol%
17 }
18
19 \renewcommand*{\aiicon}[1]
20 {%
21   \begin{lateximage}*[#1 icon][academicons#1]%
22   \AI\csname aiicon@#1\endcsname%
23   \end{lateximage}%
24 }

```

File 9 **lwarp-accents.sty**§ 118 Package **accents***(Emulates or patches code by JAVIER BEZOS.)*

Pkg accents

accents is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{accents}[2006/05/12]

For MATHJAX:

```

2 \begin{warpMathJax}
3 \LWR@inforeprocessingmathjax{accents}
4
5 \CustomizeMathJax{\newcommand{\ring}[1]{\mathring{#1}}}
6 \CustomizeMathJax{\newcommand{\accentset}[2]{\overset{#1}{#2}}}

```

As of this writing, MATHJAX v3 does not yet support groups for macros, so for `\underaccent`, the originals are remembered here, then they are temporarily redefined and used inside `\underaccent`, then restored to their originals. `\LARGE` gives a reasonable size, and `\raise` is used to adjust vertically without introducing extra line space.

```

7 \CustomizeMathJax{\let\LWRgrave\grave}
8 \CustomizeMathJax{\let\LWRacute\acute}
9 \CustomizeMathJax{\let\LWRcheck\check}
10 \CustomizeMathJax{\let\LWRbreve\breve}
11 \CustomizeMathJax{\let\LWRbar\bar}
12 \CustomizeMathJax{\let\LWRhat\hat}
13 \CustomizeMathJax{\let\LWRdot\dot}
14 \CustomizeMathJax{\let\LWRtilde\tilde}
15 \CustomizeMathJax{\let\LWRddot\ddot}
16 \CustomizeMathJax{\let\LWRvec\vec}
17 \CustomizeMathJax{\let\LWRwidetilde\widetilde}
18
19 \CustomizeMathJax{\newcommand{\underaccent}[2]{%
20   {%
21     \renewcommand{\grave}[1]{\LARGE\LWRgrave{##1}}}%
22     \renewcommand{\acute}[1]{\LARGE\LWRacute{##1}}}%
23     \renewcommand{\check}[1]{\LARGE\LWRcheck{##1}}}%
24     \renewcommand{\breve}[1]{\LARGE\LWRbreve{##1}}}%
25     \renewcommand{\bar}[1]{\LARGE\LWRbar{##1}}}%
26     \renewcommand{\hat}[1]{\LARGE\LWRhat{##1}}}%
27     \renewcommand{\dot}[1]{\LARGE\LWRdot{##1}}}%
28     \renewcommand{\tilde}[1]{\LARGE\LWRtilde{##1}}}%
29     \renewcommand{\ddot}[1]{\LARGE\LWRddot{##1}}}%
30     \renewcommand{\vec}[1]{\LARGE\LWRvec{##1}}}%
31     \renewcommand{\widetilde}[1]{\LARGE\LWRwidetilde{\hphantom{#2}}}%
32     \underset{\raise 2pt {#1}}{#2}%
33     \let\grave\LWRgrave%
34     \let\acute\LWRacute%
35     \let\check\LWRcheck%
36     \let\breve\LWRbreve%
37     \let\bar\LWRbar%

```

```

38 \let\hat\LWRhat%
39 \let\dot\LWRdot%
40 \let\tilde\LWRtilde%
41 \let\ddot\LWRddot%
42 \let\vec\LWRvec%
43 \let\widetilde\LWRwidetilde%
44 }%
45 }}
46
47 \CustomizeMathJax{\newcommand{\undertilde}[1]{%
48 \underset{\raise 3pt {\widetilde{\hphantom{#1}}}}{#1}%
49 }}
50 \end{warpMathJax}

```

File 10 **lwarp-accessibility.sty**

§ 119 Package **accessibility**

Pkg accessibility

accessibility is emulated.

for HTML output:

Discard all options for lwarp-accessibility:

```

1 \LWR@ProvidesPackageDrop{accessibility}[2019/10/14]

2 \newcommand{\alt}[1]{\ThisAltText{#1}}
3 \newcommand{\newhref}[3]{\ThisAltText{#2}\LWR@href{#1}{#3}}%
4 \providecommand{\thead}[1]{\textbf{#1}}

```

For MATHJAX:

```

5 \begin{warpMathJax}
6 \CustomizeMathJax{\newcommand{\alt}[1]{}}
7 \CustomizeMathJax{\newcommand{\thead}[1]{\text{\textbf{#1}}}}
8 \end{warpMathJax}

```

File 11 **lwarp-accsupp.sty**

§ 120 Package **accsupp**

Pkg accsupp

accsupp is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{accsupp}[2018/03/28]

2 \newcommand*\BeginAccSupp[1]{}
3 \newcommand*\EndAccSupp[1]{}

```

For MATHJAX:

```

4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\BeginAccSupp}[1]{}
6 \CustomizeMathJax{\newcommand{\EndAccSupp}[1]{}
7 \end{warpMathJax}

```

File 12 **lwarp-acro.sty**§ 121 Package **acro**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg acro

acro is patched for use by lwarp.

 **formats** Define acronymn formats using `\textbf` instead of `\bfseries` etc.

for HTML output: 1 \LWR@ProvidesPackagePass{acro}[2019/10/12]

`\DeclareAcronym` is used in the preamble, where `lwarp` has not yet made the dollar active, so temporarily enable `lwarp` math catcode just for this definition:

```
2 \ExplSyntaxOn
3 \NewDocumentCommand \LWR@DeclareAcronym {mm}
4 {
5   \acro_declare_acronym:nn {#1} {#2}
6   \catcode'\$=3% lwarp
7 }
8 \ExplSyntaxOff
9
10 \RenewDocumentCommand{\DeclareAcronym}{}{
11   \catcode'\$=\active% lwarp
12   \LWR@DeclareAcronym
13 }
```

Replace dot fill with simple dots:

```
14 \ExplSyntaxOn
15 \cs_new_protected:Npn \LWR@HTML@acro_dot_fill: { \dots\space }
16 \LWR@formatted{acro_dot_fill:}
17 \ExplSyntaxOff
```

Modified to activate the current font:

```
18 \ExplSyntaxOn
19 \IfPackageAtLeastTF{acro}{2020/04/29}%
20 { % v3 or later
21 { % before v3
22 \IfPackageAtLeastTF{acro}{2019/09/23}%
23 { % v2.10 or later
24 \cs_gset_protected:Npn \__acro_typeset:nn #1#2
25 {
26   \mode_if_horizontal:F { \leavevmode }
27   \group_begin:
28     \use:x
29     {
30       \bool_if:cTF {l__acro_custom_#1_format_bool}
31       { \exp_not:v {l__acro_custom_#1_format_tl} }
32       { \exp_not:v {l__acro_#1_format_tl} }
33       { \exp_not:N\LWR@textcurrentfont{#2}}% lwarp
34     }
35   \group_end:
```

```

36 }
37
38 \cs_gset_protected:Npn \__acro_ending_format:nn #1#2
39 {
40   \bool_if:NTF \l__acro_include_endings_format_bool
41   {
42     \str_case:nn {#1}
43     {
44       {long}
45       {
46         \bool_if:NTF \l__acro_custom_long_format_bool
47         { \l__acro_custom_long_format_tl }
48         {
49           \bool_if:NTF \l__acro_first_instance_bool
50           { \l__acro_first_long_format_tl }
51           { \l__acro_long_format_tl }
52         }
53       }
54     } {short}
55     {
56       \bool_if:NTF \l__acro_custom_short_format_bool
57       { \l__acro_custom_short_format_tl }
58       { \l__acro_short_format_tl }
59     }
60   } {alt}
61   {
62     \bool_if:NTF \l__acro_custom_alt_format_bool
63     { \l__acro_custom_alt_format_tl }
64     { \l__acro_alt_format_tl }
65   }
66 }
67 }
68 { \use:n }
69 {\exp_not:N\LWR@textcurrentfont{#2}}% lwarp
70 }
71 ]% v2.10 or later
72 {% before v2.10
73 \cs_gset_protected:Npn \acro_write_short:nn #1#2
74 {
75   \mode_if_horizontal:F { \leavevmode }
76   \group_begin:
77     \bool_if:NTF \l__acro_custom_format_bool
78     { \l__acro_custom_format_tl }
79     { \l__acro_short_format_tl }
80     {\LWR@textcurrentfont{#2}}% lwarp
81   \group_end:
82 }
83
84 \cs_gset_protected:Npn \acro_write_alt:nn #1#2
85 {
86   \mode_if_horizontal:F { \leavevmode }
87   \group_begin:
88     \bool_if:NTF \l__acro_custom_format_bool
89     { \l__acro_custom_format_tl }
90     { \l__acro_alt_format_tl }
91     {\LWR@textcurrentfont{#2}}% lwarp
92   \group_end:
93 }
94
95 \cs_gset_protected:Npn \acro_write_long:nn #1#2

```

```

96 {
97   \mode_if_horizontal:F { \leavevmode }
98   \group_begin:
99     \bool_if:NTF \l__acro_custom_long_format_bool
100     { \l__acro_custom_long_format_tl }
101     { \use:n }
102     {
103       \use:x
104       {
105         \exp_not:n {#1}
106         {
107           \bool_if:NTF \l__acro_first_upper_bool
108           { \exp_not:N \__acro_first_upper_case:n { \exp_not:n {
109             \LWR@textcurrentfont{#2}% lwarp
110           } } }
111           { \exp_not:n {\LWR@textcurrentfont{#2}} }% lwarp
112         }
113       }
114     }
115   \group_end:
116 }
117 }% before v2.10
118 }% before v3
119 \ExplSyntaxOff

```

File 13 **lwarp-acronym.sty**

§ 122 Package **acronym**

(Emulates or patches code by TOBIAS OETIKER.)

Pkg acronym

acronym is patched for use by lwarp.



multiply-defined labels

\acresetall does not work with cleveref, causing multiply-defined labels. lwarp patches acronym for HTML, but not for print mode.

for HTML output:

```
1 \LWR@ProvidesPackagePass{acronym}[2020/04/17]
```

Simplifies for HTML:

```

2 \expandafter\def\csname AC@AC@prefix{}@acro\endcsname#1[#2]#3{%
3   \ifAC@nolist%
4   \else%
5   \ifnum%
6     \ifAC@printonlyused 1%
7     \else\ifAC@printonlyreused 1%
8     \else 0\fi\fi%
9   =1\relax%
10  \ifnum%
11    \ifAC@printonlyused%
12    \expandafter\ifx\csname acused@#1@once\endcsname\AC@used 1 \else 0 \fi%
13    \else\ifAC@printonlyreused%
14    \expandafter\ifx\csname acused@#1@twice\endcsname\AC@used 1 \else 0 \fi%
15    \else 0 \fi\fi%
16  =1\relax%
17  \item[\protect\AC@hypertarget{#1}]%
18    \AC@hyperref[acro:#1]{\aclabelfont{#2}\hfill}%

```

```

19    ]]\AC@hyperref[acro:#1]{#3}%
20    \ifAC@withpage%
21        \expandafter\ifx\csname r@acro:#1\endcsname\relax%
22        \PackageInfo{acronym}{%
23            Acronym #1 used in text but not spelled out in
24            full in text}%
25        \else%
26            \nobreak\leaders\hbox{%
27                $\m@th\mkern\@dotsep mu\hbox{.}\mkern\@dotsep mu$%
28            }\hfill%
29            \nobreak\hb@xt@\@pnumwidth{%
30                \hfil\normalfont\normalcolor
31                \quad --- % lwarp
32                \AC@pageref{acro:#1}%
33            }%
34        \fi%
35    \fi%%
36    \fi%
37    \else%
38        \item[\protect\AC@hypertarget{#1}{\AC@hyperref[acro:#1]{\aclabelfont{#2}\hfill}}]%
39        \AC@hyperref[acro:#1]{#3}%
40    \fi%
41    \fi%
42    \begingroup
43        \def\acroextra##1{%
44            \@bsphack
45            \ifAC@printonlyreused%
46                \protected@write\@auxout{}{%
47                    \string\newacro{#1}%
48                    \expandafter\ifx\csname acused@#1@twice\endcsname\AC@used%
49                    \string\AC@hyperlink{#1}{#2}%
50                \else%
51                    {#2}%
52                \fi%
53            ]{#3}%
54        }%
55    \else%
56        \protected@write\@auxout{}{%
57            \string\newacro{#1}[\string\AC@hyperlink{#1}{#2}]{#3}%
58        }%
59    \fi%
60    \@esphack
61    \endgroup
62    \ignorespaces}

```

Uses `\textit` instead of `\itshape`:

```

63 \renewcommand{\acfia}[1]{%
64     {\textit{\AC@acl{#1}}} (\ifAC@starred\acs*{#1}\else\acs{#1}\fi)}

```

Removes the mbox to allow math inside:

```

65 \renewcommand*\AC@acs[1]{%
66     \mbox{
67     \expandafter\AC@get\csname fn@#1\endcsname\@firstoftwo{#1}}
68 }

```

Fix for acronym labels in the captions of floats.

```

69 \renewcommand{\@starttoc}[1]{%
70   \LWR@htmlElementclass{nav}{#1}
71   \LetLtxMacro\@verridelabel\@gobble
72   \LWR@orig@starttoc{#1}
73   \LWR@htmlElementclassend{nav}{#1}
74 }

```

Modified for cleveref and lwarp:

```

75 \renewcommand*\AC@und@newlabel[3]{%
76   \@ifundefined{#1@#3}%
77   {%
78     \global\expandafter\let\csname#2@#3\endcsname\@nnil
79     \global\expandafter\let\csname#2@#3@lwarp\endcsname\@nnil% lwarp
80     \global\expandafter\let\csname#2@#3@cref\endcsname\@nnil% lwarp
81   }%
82   {%
83     \global\expandafter\let\csname#1@#3\endcsname\relax
84     \global\expandafter\let\csname#1@#3@lwarp\endcsname\relax% lwarp
85     \global\expandafter\let\csname#1@#3@cref\endcsname\relax% lwarp
86   }%
87 }%

```

Improve paragraph handling:

```

88 \BeforeBeginEnvironment{acronym}{\LWR@stoppars}
89 \AfterEndEnvironment{acronym}{\LWR@startpars}

```

Create hyperlinks, even though hyperref is only emulated:

```

90 \AtBeginDocument{
91   \LetLtxMacro\AC@hyperlink\hyperlink
92   \LetLtxMacro\AC@hyperref\hyperref
93   \newcommand*\AC@raisedhypertarget[2]{%
94     \Hy@raisedlink{%
95       \hypertarget{#1}}{%
96       }%
97     #2}%
98   \LetLtxMacro\AC@hypertarget\AC@raisedhypertarget
99   \def\AC@phantomsection{%
100     \Hy@GlobalStepCount\Hy@linkcounter
101     \edef\@currentHref{section*. \the \Hy@linkcounter}%
102     \Hy@raisedlink{%
103       \hyper@anchorstart{\@currentHref}\hyper@anchorend
104     }%
105     \phantomsection%
106   }%
107 }
108
109 \appto\LWR@restoreorigformatting{%
110   \LetLtxMacro\AC@hyperlink\@secondoftwo%
111   \LetLtxMacro\AC@hyperref\LWR@nullify@hyperref%
112 }

```

File 14 **lwarp-adjmulticol.sty**§ 123 Package **adjmulticol***(Emulates or patches code by BORIS VEYTSMAN.)*

Pkg adjmulticol

adjmulticol is emulated.

Emulation similar to `multicols` is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, `lwarp` allows a variable number of columns up to three.

for HTML output: 1 \LWR@ProvidesPackageDrop{adjmulticol}[2012/01/20]

2 \RequirePackage{multicol}

adjmulticols * {<numcols>} {<left margin>} {<right margin>}

3 \NewDocumentEnvironment{adjmulticols}{s m m m}

4 {%

Compute the margins, and limit to positive only:

5 \setlength{\LWR@templengthone}{#3}%

6 \ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{%

7 \setlength{\LWR@templengthtwo}{#4}

8 \ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{%

If one column is specified, use a `<div>` of class `singlecolumn`, else use `multicols`:

9 \newcommand*\LWR@mccolstype{multicols}%

10 \ifnumcomp{#2}={1}{\renewcommand*\LWR@mccolstype{singlecolumn}}{%

Help avoid page overflow:

11 \LWR@forcenewpage%

Create the `<div>` with the given margin and class:

12 \BlockClass[%

13 \LWR@print@mbbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %

14 \LWR@print@mbbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%

15]{\LWR@mccolstype}%

16 }

17 {\endBlockClass}

File 15 **lwarp-addlines.sty**§ 124 Package **addlines***(Emulates or patches code by WILL ROBERTSON.)*

Pkg addlines

addlines is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{addlines}[2018/12/05]

2 \newcommand\addlines{\@ifstar\addlines@a\addlines@a}
3 \newcommand\addlines@a[1][1]{}
4 \let\addline\addlines
5 \newcommand\removelines{\@ifstar\removelines@a\removelines@a}
6 \newcommand\removelines@a[1][1]{}
7 \let\removeline\removelines
8 \newcommand\squeezepage[1][0]{}

```

File 16 **lwarp-afterpage.sty**§ 125 Package **afterpage***(Emulates or patches code by DAVID CARLISLE.)*

Pkg afterpage

afterpage is emulated.

for HTML output: Discard all options for lwarp-afterpage:

```

1 \LWR@ProvidesPackageDrop{afterpage}[2014/10/28]

2 \newcommand{\afterpage}[1]{#1}

```

File 17 **lwarp-algorithm2e.sty**§ 126 Package **algorithm2e***(Emulates or patches code by CHRISTOPHE FIORIO.)*

Pkg algorithm2e

algorithm2e is patched for use by lwarp.

For print output, captions are placed according to package options, but for HTML output captions are placed where used. Therefore, to have captions appear at the top of the algorithms for both print and HTML, place each captions at the top of each algorithm.

for HTML output:

```

1 \LWR@ProvidesPackagePass{algorithm2e}[2017/07/18]

```

For the list-of entries:

```

2 \renewcommand{\l@algocf}[2]{\hypertocfloat{1}{algocf}{loa}{#1}{#2}}

```

Select the lwarp float style according to the algorithm2e style:

```

3 \newcommand*\LWR@floatstyle@algocf{ruled}
4
5 \ifdefstring{\algocf@style}{boxed}{%
6 \renewcommand*\LWR@floatstyle@algocf{boxed}
7 }{}
8

```

```

9 \ifdefstring{\algocf@style}{boxruled}{%
10 \renewcommand*\LWR@floatstyle@algocf}{boxruled}
11 }{}
12
13 \ifdefstring{\algocf@style}{plain}{%
14 \renewcommand*\LWR@floatstyle@algocf}{plain}
15 }{}

```

Paragraph handling to allow line numbers under certain conditions:

```

16 \renewcommand{\algocf@everypar}{%
17   \ifbool{LWR@algocf@dopars}{%
18     \ifbool{LWR@doingstartpars}{%
19       \ifnumcomp{\value{LWR@Lateximagedepth}}{>}{0}{%
20         }{%
21         }%

```

`algorithm2e` uses `\everypar`, so the open paragraph tag is generated here instead of `\LWR@openparagraph`:

```

22   \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%
23
24   \algocf@everyparnl\algocf@everyparhanging%
25   }{}%
26 }{}%
27 }

```

lwarp caption handling:

```

28 \renewcommand{\algocf@makecaption}[2]{%
29   \LWR@HTML@caption@begin{algocf}%
30   \LWR@isolate{\algocf@captiontext{#1}{#2}}%
31   \LWR@HTML@caption@end%
32 }

```

Print any caption where it is declared:

```

33 \renewcommand{\algocf@makecaption@plain}[2]{%
34   \LWR@HTML@caption@begin{algocf}%
35   \LWR@isolate{\algocf@captiontext{#1}{#2}}%
36   \LWR@HTML@caption@end%
37 }
38
39 \renewcommand{\algocf@makecaption@boxed}[2]{%
40   \LWR@HTML@caption@begin{algocf}%
41   \LWR@isolate{\algocf@captiontext{#1}{#2}}%
42   \LWR@HTML@caption@end%
43 }
44
45 \renewcommand{\algocf@makecaption@ruled}[2]{%
46   \LWR@HTML@caption@begin{algocf}%
47   \LWR@isolate{\algocf@captiontext{#1}{#2}}%
48   \LWR@HTML@caption@end%
49 }

```

Turn off line numbering while making the caption:

```

50 \long\def\algocf@latexcaption#1[#2]#3{% original definition of caption
51 \boolfalse{LWR@algocf@dopars}%      lwarp
52 \par%
53 \addcontentsline{\csname ext@#1\endcsname}{#1}%
54 {\protect\numberline{\csname the#1\endcsname}{\ignorespaces \LWR@isolate{#2}}}%
55 \begingroup%
56 \@parboxrestore%
57 \if@minipage%
58 \setminipage%
59 \fi%
60 \normalsize%
61 \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par%
62 \endgroup%
63 \booltrue{LWR@algocf@dopars}%      lwarp
64 }

```

Line numbers are printed in a `` of class `alg2elinenum`:

```

65 \renewcommand{\algocf@printnl}[1]{%
66 \InlineClass{alg2elinenum}{\NLSty{#1}}~%
67 }%

```

While initializing an algorithm environment, locally declare the style of a regular figure to be the same as the algorithm style, in case the figure option was used.

```

68 \preto\@algocf@init{%
69 \edef\LWR@floatstyle@figure{\LWR@floatstyle@algocf}%
70 }

```

For `lwarp`, the algorithm is not assembled inside a box, since `lateximages` would not work, so the captions are printed where declared.

```

71 \renewcommand{\@algocf@start}{%
72 \let\@mathsemicolon=\; \def\;{\ifmmode\@mathsemicolon\else\endalgoln\fi}%
73 % \raggedright%
74 \ALFnt{}}%
75 \booltrue{LWR@algocf@dopars}% lwarp
76 }
77
78 \renewcommand{\@algocf@finish}{%
79 \boolfalse{LWR@algocf@dopars}% lwarp
80 \lineskip\normallineskip\setlength{\skiptotal}{\@defaultskiptotal}%
81 \let\;=\@mathsemicolon%
82 \let\]=\@emathdisplay%
83 }

```

Use an HTML break:

```

84 \renewcommand{\BlankLine}{%
85 \LWR@stoppars%
86 \LWR@htmltagc{br /}%
87 \LWR@startpars%
88 }

```

Simplified for HTML. The paragraph handling must be preserved.

```

89 \renewcommand{\SetKwInOut}[2]{%
90 \algocf@newcommand{#1}[1]{%
91 \ifthenelse{\boolean{algocf@hanginginout}}%

```

```

92     {\relax}%
93     {\algocf@seteveryparhanging{\relax}}%
94     \ifthenelse{\boolean{algocf@inoutnumbered}}%
95     {\relax}%
96     {\algocf@seteveryparnl{\relax}}%
97     {%
98         \KwSty{#2\algocf@typo:}%
99         ~##1\par%
100    }%
101    \algocf@linesnumbered% reset the numbering of the lines
102    \ifthenelse{\boolean{algocf@hanginginout}}%
103    {\relax}%
104    {\algocf@reseteveryparhanging}%
105 }%
106 }%
107
108 \renewcommand{\ResetInOut}[1]{%

```

Each of the following creates a <div> of a given class, and turns off line numbering while creating the <div> tags:

```

109 \renewcommand{\algocf@Vline}[1]{%
110     \boolfalse{LWR@algocf@dopars}%
111     \begin{BlockClass}{alg2evline}
112     \booltrue{LWR@algocf@dopars}%
113     #1
114     \boolfalse{LWR@algocf@dopars}%
115     \end{BlockClass}
116     \booltrue{LWR@algocf@dopars}%
117 }

118 \renewcommand{\algocf@Vsline}[1]{%
119     \boolfalse{LWR@algocf@dopars}%
120     \begin{BlockClass}{alg2evsline}
121     \booltrue{LWR@algocf@dopars}%
122     #1
123     \boolfalse{LWR@algocf@dopars}%
124     \end{BlockClass}
125     \booltrue{LWR@algocf@dopars}%
126 }

127 \renewcommand{\algocf@Noline}[1]{%
128     \boolfalse{LWR@algocf@dopars}%
129     \begin{BlockClass}{alg2enoline}
130     \booltrue{LWR@algocf@dopars}%
131     #1
132     \boolfalse{LWR@algocf@dopars}%
133     \end{BlockClass}
134     \booltrue{LWR@algocf@dopars}%
135 }

```

The [H] environment is converted to a regular float, which in HTML is placed where declared. Reusing the regular float allows the [H] version to reuse the ruled and boxed options.

```

136 \LetLtxMacro\algocf@Here\algocf
137 \LetLtxMacro\endalgocf@Here\endalgocf

```

File 18 **lwarp-algorithmicx.sty**

§ 127 Package **algorithmicx**

(Emulates or patches code by SZÁSZ JÁNOS.)

Pkg algorithmicx

algorithmicx is supported with minor adjustments.

for HTML output: 1 \LWR@ProvidesPackagePass{algorithmicx}[2005/04/27]

Inside the algorithmic environment, level indenting is converted to a `` of the required length, and comments are placed inside a `` which is floated right.

 **package conflicts** If using `\newfloat`, `trivfloat`, and/or `algorithmicx` together, see section 636.1.

```

2 \AtBeginEnvironment{algorithmic}{%
3 %
4 \let\origALG@doentity\ALG@doentity%
5 %
6 \renewcommand*\ALG@doentity{%
7 \origALG@doentity%
8 \LWR@htmltagc{%
9   span style=\textquotedbl{}%
10     width:\LWR@printlength{\ALG@thistlm}; display:inline-block;%
11   \textquotedbl%
12 }%
13 \ifbool{FormatWP}{%
14 \setlength{\LWR@templengthone}{\the\ALG@thistlm}%
15 \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
16 \quad%
17 \addtolength{\LWR@templengthone}{-1em}%
18 }%
19 }{%
20 \LWR@htmltagc{/span}%
21 }%
22
23 \let\LWR@origComment\Comment%
24
25 \renewcommand{\Comment}[1]{%
26   \InlineClass{floatright}{\LWR@origComment{#1}}%
27 }%
28 }
29
30 \renewcommand\algorithmiccomment[1]{%
31 \hfill\HTMLUnicode{25B7} #1% white right triangle
32 }%
```

File 19 **lwarp-alltt.sty**

§ 128 Package **alltt**

(Emulates or patches code by JOHANNES BRAAMS.)

Pkg alltt

alltt is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{alltt}[1997/06/16]

2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching alltt.}
4
5 \AtBeginEnvironment{alltt}{%
6   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
7     {}%
8     {%
9       \LWR@forcenewpage

```

Vertical spacing changes if inside a list.

```

10       \LWR@atbeginverbatim{alltt}%
11     }%
12 }
13
14 \AfterEndEnvironment{alltt}{%
15   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
16     {}%
17     {%

```

Vertical spacing changes if inside a list.

```

18       \LWR@afterendverbatim%
19     }%
20 }
21
22 }

```

File 20 **lwarp-amscdx.sty**§ 129 Package **amscdx***(Emulates or patches code by MARTIN VERMEER.)*

Pkg amscdx

amscdx is used as-is for SVG math.

**MATHJAX**For MATHJAX, a warning notes that the CD environment must be enclosed between `\displaymathother` and `\displaymathnormal`.**for HTML output:**

```

1 \LWR@ProvidesPackagePass{amscdx}[2019/07/02]

2 \begin{warpMathJax}
3 \CustomizeMathJax{%
4   \renewenvironment{CD}
5     {\text{(Use \unicode{x005C}displaymathother before the CD envioment.) \quad}}
6     {\quad \text{(Use \unicode{x005C}displaymathnormal after the CD envioment.)}}
7 }
8
9 \CustomizeMathJax{\newcommand{\CDFattrue}}{}
10 \CustomizeMathJax{\newcommand{\CDFatfalse}}{}
11 \CustomizeMathJax{\newcommand{\CDashtrue}}{}
12 \CustomizeMathJax{\newcommand{\CDashfalse}}{}

```

```
13 \CustomizeMathJax{\newcommand{\CDLor}[1]{} }
14 \end{warpMathJax}
```

File 21 **lwarp-amsmath.sty**§ 130 Package **amsmath**

(Emulates or patches code by AMERICAN MATHEMATICAL SOCIETY, L^AT_EX3 PROJECT.)

Pkg amsmath

amsmath is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{amsmath}[2017/09/02]

\dotso

An HTML text-mode version.

```
2 \newcommand*\LWR@HTML@dotso{\textellipsis\ }
3 \LWR@formatted{dotso}
```

Patches to allow \eqref inside a caption:

```
4 \def\maketag@@@#1{\text{#1}}
5 \def\tagform@#1{\maketag@@@{\ignorespaces#1\unskip}}
```

Patches for \mathcal{AMS} math \tag macro to remember the first tag:

```
6 \ifbool{mathjax}{}% not mathjax
7
8 \LetLtxMacro\LWR@origmake@df@tag@@\make@df@tag@@
9 \LetLtxMacro\LWR@origmake@df@tag@@@\make@df@tag@@@
10
11 \renewcommand*\make@df@tag@@[1]{%
12   \LWR@remembertag{#1}%
13   \LWR@origmake@df@tag@@{#1}%
14 }
15
16 \renewcommand*\make@df@tag@@@[1]{%
17   \LWR@remembertag{#1}%
18   \LWR@origmake@df@tag@@@{#1}%
19 }
20
21 }% not mathjax
```

For nesting \mathcal{AMS} environments:

```
22 \newcounter{LWR@amsmathdepth}
23 \setcounter{LWR@amsmathdepth}{0}
```

The following \mathcal{AMS} environments are patched in-place:

Ctr LWR@maxfields@

A copy of maxfields@ as it was passed. This is used to generate the mandatory argument for alignat and alignat* when using MATHJAX.

```
24 \newcounter{LWR@maxfields@}
25
26 \xpatchcmd{\start@align}
```

```

27   {\maxfields@#3\relax}
28   {%
29     \maxfields@#3\relax%
30     \setcounter{LWR@maxfields@}{#3}%
31   }
32   {}
33   {\LWR@patcherror{amsmath}{start@align}}

```

`\LWR@amsmathenv@@before`

* $\langle environment\ name \rangle$

* if the environment was starred.

Embeds the environment inside a `lateximage`.

```

34 \NewDocumentCommand{\LWR@amsmathenv@@before}{s m}{%
35   \IfBooleanTF{#1}{
36     \begin{BlockClass}{displaymath}
37   }{
38     \begin{BlockClass}{displaymathnumbered}
39   }
40   \LWR@newautoidanchor%
41   \booltrue{LWR@indisplaymathimage}%
42   \begin{lateximage}[\LWR@amsmathbodynumbered{#2}]*%
43   \LWR@applyxfakebold%
44 }

```

`\LWR@amsmathenv@before`

* $\langle environment\ name \rangle$

* if the environment was starred.

Embeds the environment with `MATHJAX` or a `lateximage`.

```

45 \NewDocumentCommand{\LWR@amsmathenv@before}{s m}{%
46   \ifnumequal{\value{LWR@amsmathdepth}}{0}{%
47     \LWR@stoppars%
48     \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
49     {
50       \LWR@syncmathjax
51       \boolfalse{LWR@amsmultiline}
52       \ifstrequal{#2}{multline}{\booltrue{LWR@amsmultiline}}{ }
53       \ifstrequal{#2}{multline*}{\booltrue{LWR@amsmultiline}}{ }

```



autonom's "+" environments are not supported by `MATHJAX`.

```

54   \LWR@beginhideamsmath
55   }
56   {
57   \IfBooleanTF{#1}{
58     \LWR@amsmathenv@@before*{#2}
59   }{
60     \LWR@amsmathenv@@before{#2}
61   }
62   }
63 }{}
64 \addtocounter{LWR@amsmathdepth}{1}
65 }

```

`\LWR@amsmathenv@@after`

Embeds the environment inside a `lateximage`.

```

66 \newcommand*{\LWR@amsmathenv@@after}{%
67   \end{lateximage}\end{BlockClass}\LWR@startpars%

```

68 }

\LWR@amsmathenv@after

* $\{environment\ name\}$

* if the environment was starred. Ignored here, only used for a consistent syntax.

Embeds the environment with MATHJAX or a lateximage.

```

69 \NewDocumentCommand{\LWR@amsmathenv@after}{s m}{%
70   \ifnumequal{\value{LWR@amsmathdepth}}{1}{%
71     \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
72     {
73       \LWR@endhideamsmath
74       \boolfalse{LWR@amsmultline}
75       \LWR@addmathjax{#2}{\the\@envbody}
76     }
77     {\LWR@amsmathenv@@after}

```

Clear the single-use alt text:

```

78   \gdef\LWR@ThisAltText{%
79   }{}
80   \addtocounter{LWR@amsmathdepth}{-1}
81 }

```

Env multline

```

82 \BeforeBeginEnvironment{multline}{\LWR@amsmathenv@before{multline}}
83
84 \AfterEndEnvironment{multline}{\LWR@amsmathenv@after{multline}}

```

Env multline*

```

85 \BeforeBeginEnvironment{multline*}{\LWR@amsmathenv@before*{multline*}}
86
87 \AfterEndEnvironment{multline*}{\LWR@amsmathenv@after*{multline*}}
88

```

Env gather

```

89 \BeforeBeginEnvironment{gather}{\LWR@amsmathenv@before{gather}}
90
91 \AfterEndEnvironment{gather}{\LWR@amsmathenv@after{gather}}

```

Env gather*

```

92 \BeforeBeginEnvironment{gather*}{\LWR@amsmathenv@before*{gather*}}
93
94 \AfterEndEnvironment{gather*}{\LWR@amsmathenv@after*{gather*}}

```

Env align

```

95 \BeforeBeginEnvironment{align}{\LWR@amsmathenv@before{align}}
96
97 \AfterEndEnvironment{align}{\LWR@amsmathenv@after{align}}

```

Env align*

```

98 \BeforeBeginEnvironment{align*}{\LWR@amsmathenv@before*{align*}}
99
100 \AfterEndEnvironment{align*}{\LWR@amsmathenv@after*{align*}}

```

Env flalign

```

101 \BeforeBeginEnvironment{flalign}{\LWR@amsmathenv@before{flalign}}
102
103 \AfterEndEnvironment{flalign}{\LWR@amsmathenv@after{flalign}}

```

Env flalign*

```

104 \BeforeBeginEnvironment{flalign*}{\LWR@amsmathenv@before*{flalign*}}
105
106 \AfterEndEnvironment{flalign*}{\LWR@amsmathenv@after*{flalign*}}

```

Env alignat

```

107 \BeforeBeginEnvironment{alignat}{\LWR@amsmathenv@before{alignat}}
108
109 \AfterEndEnvironment{alignat}{\LWR@amsmathenv@after{alignat}}

```

Env alignat*

```

110 \BeforeBeginEnvironment{alignat*}{\LWR@amsmathenv@before*{alignat*}}
111
112 \AfterEndEnvironment{alignat*}{\LWR@amsmathenv@after*{alignat*}}

```

```

113 \AtBeginEnvironment{subequations}{
114   \renewcommand*\theMathJaxsubequations}{1}
115   \renewcommand*\theMathJaxsection}{\theparentequation}
116   \renewcommand*\theMathJaxequation}{\arabic{equation}}
117 }

```

For MATHJAX:

```

118 \begin{warpMathJax}
119 \CustomizeMathJax{\newcommand{\intertext}[1]{\text{#1}\notag \}}
120 \CustomizeMathJax{\let\Hat\hat}
121 \CustomizeMathJax{\let\Check\check}
122 \CustomizeMathJax{\let\Tilde\tilde}
123 \CustomizeMathJax{\let\Acute\acute}
124 \CustomizeMathJax{\let\Grave\grave}
125 \CustomizeMathJax{\let\Dot\dot}
126 \CustomizeMathJax{\let\Ddot\ddot}
127 \CustomizeMathJax{\let\Breve\breve}
128 \CustomizeMathJax{\let\Bar\bar}
129 \CustomizeMathJax{\let\Vec\vec}
130 \end{warpMathJax}

```

File 22 **lwarp-amsthm.sty**

§ 131 Package **amsthm**

(Emulates or patches code by PUBLICATIONS TECHNICAL GROUP — AMERICAN MATHEMATICAL SOCIETY.)

The original source code is located in `amsclass.dtx`, and printed in `amsclass.pdf`.

`amsthm` is patched for use by `lwarp`.

Table 19: `amsthm` package — css styling of theorems and proofs

Theorem: `<div>` of class `amsthmbody<theoremstyle>`

Theorem Name: `` of class `amsthmname<theoremstyle>`

Theorem Number: `` of class `amsthmnumber<theoremstyle>`

Theorem Note: `` of class `amsthmnote<theoremstyle>`

Proof: `<div>` of class `amsthmproof`

Proof Name: `` of class `amsthmproofname`

where `<theoremstyle>` is `plain`, `definition`, etc.

for HTML output:

`amsthm` must be loaded before `mdframed`:

```

1 \IfPackageLoadedTF{mdframed}{
2   \PackageError{lwarp}
3   {%
4     Package mdframed must be loaded after package amsthm.\MessageBreak
5     Enter 'H' for solutions%
6   }
7   {%
8     Move ‘‘\protect\usepackage{amsthm}’’ before
9     ‘‘\protect\usepackage{mdframed}’’.\MessageBreak
10    Package amsthm may be loaded by something else,\MessageBreak
11    which must also be moved before mdframed.%
12  }
13 }
14 {\relax}

```

Necessary for `\text`, used by `\openbox`, etc., below:

```

15 \RequirePackage{amsmath}
16 \LWR@ProvidesPackagePass{amsthm}[2017/10/31]

```

Storage for the style being used for new theorems:

```

17 \newcommand{\LWR@newtheoremstyle}{plain}

```

Patched to remember the style being used for new theorems:

```

18 \renewcommand{\theoremstyle}[1]{%
19   \ifundefined{th@#1}{%
20     \PackageWarning{amsthm}{Unknown theoremstyle ‘#1’}%
21     \thm@style{plain}%
22     \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
23   }{%
24     \thm@style{#1}%
25     \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
26   }%
27 }

```

Patched to remember the style for this theorem type:

```

28 \def\xnthm#1#2{%
29   \csedef{LWR@thmstyle#2}{\LWR@newtheoremstyle}% lwarp
30   \let\@tempa\relax
31   \exp\@ifdefinable\csname #2\endcsname{%
32     \global\@xp\let\csname end#2\endcsname\@endtheorem
33     \ifx *#1% unnumbered, need to get one more mandatory arg
34       \edef\@tempa##1{%
35         \gdef\exp\@nx\csname#2\endcsname{%
36           \@nx\@thm{\@xp\@nx\csname th@\the\thm@style\endcsname}%
37             {##1}}}%
38     \else % numbered theorem, need to check for optional arg
39       \def\@tempa{\@oparg{\@ynthm{#2}}[]}%
40     \fi
41     \AtBeginEnvironment{#2}{%                               lwarp
42       \edef\LWR@thismstyle{\@nameuse{LWR@thmstyle#2}}%   lwarp
43     }%                                                       lwarp
44   }%
45   \@tempa%
46 }

```

Patched to enclose with css:

```

47 \newcommand{\LWR@haveamsthmname}{
48   \renewcommand{\thmname}[1]{%
49     \InlineClass{amsthmname\LWR@thismstyle}{##1}%
50   }
51 }
52
53 \newcommand{\LWR@haveamsthmnumber}{
54   \renewcommand{\thmnumber}[1]{%
55     \InlineClass{amsthmnumber\LWR@thismstyle}{##1}%
56   }
57 }
58
59 \newcommand{\LWR@haveamsthmnote}{
60   \renewcommand{\thmnote}[1]{%
61     \InlineClass{amsthmnote\LWR@thismstyle}{##1}%
62   }
63 }
64
65 \LWR@haveamsthmname
66 \LWR@haveamsthmnumber
67 \LWR@haveamsthmnote

```

Patched for css:

```

68 \def\@begintheorem#1#2[#3]{%

69   \GetTitleString{#3}%                               lwarp
70   \let\@currentlabelname\GetTitleStringResult%     lwarp
71   \item[%

72   \LWR@newautopagelabel{page}\LWR@orignewline%

73 % \deferred@thm@head{
74 %   \the\thm@headfont \thm@indent

```

```

75 \@ifempty{#1}{\let\thmname@gobble}{\LWR@haveamsthmname}% lwarp
76 \@ifempty{#2}{\let\thmnumber@gobble}{\LWR@haveamsthmnumber}% lwarp
77 \@ifempty{#3}{\let\thmnote@gobble}{\LWR@haveamsthmnote}% lwarp
78 \thm@swap\swappedhead\thmhead{#1}{#2}{#3}%
79 \the\thm@headpunct % space
80 \thmheadnl % possibly a newline.
81 \hskip\thm@headsep
82 % }%
83 ]%
84 \ignorespaces}

```

Patched for css:

```

85 \def\@thm#1#2#3{%
86 \ifhmode\unskip\unskip\par\fi
87 \normalfont
88 \LWR@forcenewpage% lwarp

89 \LWR@printpendingfootnotes% lwarp

90 \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
91 \trivlist
92 \let\thmheadnl\relax
93 \let\thm@swap@gobble
94 \thm@notefont{\fontseries\mdefault\upshape}%
95 \thm@headpunct{.}% add period after heading
96 \thm@headsep 5\p@ plus\p@ minus\p@\relax
97 \thm@space@setup
98 #1% style overrides
99 \@topsep \thm@preskip % used by thm head
100 \@topsepadd \thm@postskip % used by \@endparenv
101 \def\@tempa{#2}\ifx\@empty\@tempa
102 \def\@tempa{\@oparg{\@begintheorem{#3}{}}{}}{}}{}}%
103 \else
104 \refstepcounter{#2}%
105 \def\@tempa{\@oparg{\@begintheorem{#3}{\csname the#2\endcsname}}{}}{}}%
106 \fi
107 \@tempa%
108 }

```

cleveref patches \@thm to do \cref@thmoptarg if an optional argument is given.
lwarp then patches \cref@thmoptarg \@AtBeginDocument.

```

109 \@AtBeginDocument{%
110 \def\cref@thmoptarg[#1]#2#3#4{%
111 \ifhmode\unskip\unskip\par\fi%
112 \normalfont%
113 \LWR@forcenewpage% lwarp

114 \LWR@printpendingfootnotes% lwarp

115 \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
116 \trivlist%
117 \let\thmheadnl\relax%
118 \let\thm@swap@gobble%
119 \thm@notefont{\fontseries\mdefault\upshape}%
120 \thm@headpunct{.}% add period after heading
121 \thm@headsep 5\p@ plus\p@ minus\p@\relax%

```

```

122 \thm@space@setup%
123 #2% style overrides
124 \@topsep \thm@preskip           % used by thm head
125 \@topsepadd \thm@postskip       % used by \@endparenv
126 \def\@tempa{#3}\ifx\@empty\@tempa%
127   \def\@tempa{\@oparg{\@begintheorem{#4}{}}{}}{}}{}}%
128 \else%
129   \refstepcounter[#1]{#3}% <<< cleveref modification
130   \def\@tempa{\@oparg{\@begintheorem{#4}{\csname the#3\endcsname}}{}}{}}%
131 \fi%
132 \@tempa
133 }%
134 }% AtBeginDocument
135
136 \def\@endtheorem{%
137   \endtrivlist%

138 \LWR@printpendingfootnotes%                lwarp

139 \endBlockClass%
140 \enddefalse%
141 }

```

Proof QED symbol:

```

142 \AtBeginDocument{
143 \@ifundefined{LWR@orig@openbox}{
144 \LetLtxMacro\LWR@orig@openbox\openbox
145 \LetLtxMacro\LWR@orig@blacksquare\blacksquare
146 \LetLtxMacro\LWR@orig@Box\Box
147
148 \def\openbox{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
149 \def\blacksquare{\text{\HTMLUnicode{220E}}}% UTF-8 end-of-proof
150 \def\Box{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
151
152 \appto\LWR@restoreorigformatting{%
153   \LetLtxMacro\openbox\LWR@orig@openbox%
154   \LetLtxMacro\blacksquare\LWR@orig@blacksquare%
155   \LetLtxMacro\Box\LWR@orig@Box%
156 }% appto
157 }{ }% @ifundefined
158 }% AtBeginDocument

```

Patched to add a :

```

159 \DeclareRobustCommand{\qed}{%
160   \ifmmode \mathqed
161   \else
162 %     \leavevmode\unskip\penalty9999 \hbox{\nobreak\hfill
163 %     \quad\hbox{\qedsymbol}}%
164     \InlineClass{theoremendmark}{\qedsymbol}%   lwarp
165   \fi
166 }

```

Patched for css:

```

167 \renewenvironment{proof}[1][\proofname]{\par
168 \LWR@forcenewpage% lwarp

```

```

169 \LWR@printpendingfootnotes%                lwarp

170 \BlockClass{amsthmproof}% lwarp
171 \LWR@newautopagelabel{page}%
172 \pushQED{\qed}%
173 \normalfont \topsep6\p@\@plus6\p@\relax
174 \trivlist
175 \item[
176 \InlineClass{amsthmproofname}{#1\@addpunct{.}}]\ignorespaces% changes
177 }{%
178 \popQED\endtrivlist%

179 \LWR@printpendingfootnotes%                lwarp

180 \endBlockClass% lwarp
181 \@endpfalse
182 }

```

File 23 **lwarp-anonchap.sty**

§ 132 Package **anonchap**

(Emulates or patches code by PETER WILSON.)

Pkg anonchap

anonchap is emulated.

Pkg tocloft

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its titles option, which tells tocloft to use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

⚠ tocloft & other packages

The code is shared by tocbibind.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{anonchap}[2009/08/03]

2 \newcommand{\simplechapter}[1][\@empty]{%
3 \def\@chapcntformat##1{%
4 #1~\csname the##1\endcsname\simplechapterdelim\quad%
5 }%
6 }
7
8 \newcommand{\restorechapter}{%
9 \let\@chapcntformat\@secntformat%
10 }

```

File 24 **lwarp-anysize.sty**

§ 133 Package **anysize**

(Emulates or patches code by MICHAEL SALZENBERG, THOMAS ESSER.)

Pkg anysize

anysize is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{anysize}[1994/08/13]

```

```
2 \def\papersize#1#2{}
3 \def\marginsize#1#2#3#4{}
```

File 25 **lwarp-appendix.sty**§ 134 Package **appendix**

(Emulates or patches code by PETER WILSON.)

Pkg appendix appendix is patched for use by lwarp.

 **incorrect TOC link** During HTML conversion, the option toc without the option page results in a TOC link to whichever section was before the appendices environment. It is recommended to use both toc and also page at the same time.

for HTML output: 1 \LWR@ProvidesPackagePass{appendix}[2009/09/02]

```
2 \renewcommand*{\@chap@pppage}{%
3 \part*{\appendixpagename}
4 \if@dotoc@pp
5 \addappheadtotoc
6 \fi
7 }
8
9 \renewcommand*{\@sec@pppage}{%
10 \part*{\appendixpagename}
11 \if@dotoc@pp
12 \addappheadtotoc
13 \fi
14 }
```

File 26 **lwarp-ar.sty**§ 135 Package **ar**

(Emulates or patches code by AGOSTINO DE MARCO.)

Pkg ar ar is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{ar}[2012/01/23]

Measure and print the width of the supplied glyph.

```
2 \newlength{\LWR@ar@width}
3
4 \newcommand*{\LWR@ar@printwidth}[1]{%
5 \setlength{\LWR@ar@width}{\widthof{#1}}%
6 width:%
7 \LWR@convertto{em}{\the\LWR@ar@width}em%
8 }
```

The HTML version of \AR:

```
9 \newrobustcmd*{\LWR@HTML@AR}{%
```

Start a hashed `lateximage`, additionally hashed by the font series, with a width depending on the given glyph:

```
10 \begin{lateximage}*[AR][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@AR}]%
```

For text mode, set the font series according to the HTML font series:

```
11 \ifmmode\else\csuse{\LWR@orig\LWR@f@series series}\fi%
```

Print the original glyph using the newly set font series:

```
12 \LWR@print@AR%
```

Done.

```
13 \end{lateximage}%
14 }
```

Combine the print and HTML versions:

```
15 \LWR@formatted{AR}
```

```
16 \newrobustcmd*{\LWR@HTML@ARb}{%
17 \begin{lateximage}*[AR][b][\LWR@ar@printwidth{\LWR@print@ARb}]%
18 \LWR@print@ARb%
19 \end{lateximage}%
20 }
21 \LWR@formatted{ARb}
```

```
22 \newrobustcmd*{\LWR@HTML@ARss}{%
23 \begin{lateximage}*[ARss][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@ARss}]%
24 \ifmmode\else\csuse{\LWR@orig\LWR@f@series series}\fi%
25 \LWR@print@ARss%
26 \end{lateximage}%
27 }
28 \LWR@formatted{ARss}
```

```
29 \newrobustcmd*{\LWR@HTML@ARssb}{%
30 \begin{lateximage}*[AR][ssb][\LWR@ar@printwidth{\LWR@print@ARssb}]%
31 \LWR@print@ARssb%
32 \end{lateximage}%
33 }
34 \LWR@formatted{ARssb}
```

```
35 \newrobustcmd*{\LWR@HTML@ARtt}{%
36 \begin{lateximage}*[AR][tt][\LWR@ar@printwidth{\LWR@print@ARtt}]%
37 \LWR@print@ARtt%
38 \end{lateximage}%
39 }
40 \LWR@formatted{ARtt}
```

For MATHJAX:

```
41 \begin{warpMathJax}
42 \CustomizeMathJax{\newcommand{\AR}{\mathit{A!R}}}
43 \CustomizeMathJax{\newcommand{\ARb}{\boldsymbol{A!R}}}
44 \end{warpMathJax}
```

File 27 **lwarp-arabicfront.sty**§ 136 Package **arabicfront**

Pkg arabicfront

arabicfront is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{arabicfront}[2006/09/03]

File 28 **lwarp-array.sty**§ 137 Package **array**

Pkg array

array is used as-is for print output, and emulated for HTML.

plarray and plectarray do not affect \firsthline or \lasthline, and so are not affected by the following.

for HTML output: If array is not yet loaded, remove the default nullfied macros:

```
1 \IfPackageLoadedTF{array}{}{%
2   \let\firsthline\relax
3   \let\lasthline\relax
4 }
5
6 \LWR@ProvidesPackagePass{array}[2018/12/30]
```

Provide simplified column types for HTML:

```
7 \HTMLnewcolumnntype{w}[2]{#1}
8 \HTMLnewcolumnntype{W}[2]{#1}
```

More HTML versions:

```
9 \newcommand*{\LWR@HTML@firsthline}{\LWR@HTMLhline}%
10 \LWR@expandableformatted{firsthline}
11
12 \newcommand*{\LWR@HTML@lasthline}{\LWR@HTMLhline}%
13 \LWR@expandableformatted{lasthline}
```

```
14 \let\tabularnewline\
15 \providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
16 \LWR@formatted{tabularnewline}
```

For MATHJAX:

```
17 \CustomizeMathJax{
18   \newcommand{\multicolumn}[3]{#3}% only uses one cell
19 }
```

File 29 **lwarp-arydshln.sty**

§ 138 Package **arydshln**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg arydshln

arydshln heavily patches `tabular` code, so the actual package is not used. **arydshln** is emulated for `HTML` `tabular`, and reverts to solid rules for `SVG` `math array` and `tabular` in a `lateximage`.

`css` is not able to display a double-dashed border, so a single-dashed rule is displayed as a single-dashed border, and a double-dashed rule is displayed as a thicker single-dashed border.

For `MATHJAX`, limited emulation is provided for math mode.

for HTML output: `array` is required to allow `\newcolumn` below.

```
1 \RequirePackage{array}
2 \LWR@ProvidesPackageDrop{arydshln}[2018/09/26]
```

Ignored, but included for source compatibility:

```
3 \newdimen\dashlinedash \dashlinedash4pt %
4 \newdimen\dashlinegap \dashlinegap4pt %
5 \let\hdashlinewidth\dashlinedash
6 \let\hdashlinegap\dashlinegap
7
8 \def\ADLnullwide{}
9 \def\ADLsomewide{}
10 \def\ADLnullwidehline{}
11 \def\ADLsomewidehline{}
12
13 \def\ADLactivate{}
14 \def\ADLinactivate{}
15 \newcommand*{\ADLdrawingmode}[1]{}
16 \newcommand*{\ADLnoshorthanded}{}
17 \newcommand*{\dashgapcolor}[2]{}
18 \newcommand*{\nodashgapcolor}{}

```

In a `lateximage`, revert to solid vertical rules:

```
19 \appto\LWR@restoreorigformatting{%
20 \newcolumnntype{;}{|}%
21 \newcolumnntype{;}[1]{|}%
22 \let\LTxMacro\hdashline\hline%
23 }
```

Some of these macros are already defined as temporary placeholders in the `lwarp` core, so they must be redefined here.

The emulated defaults also work for an emulated print mode inside a `lateximage`:

```
24 \def\hdashline{
```

```

25 % \adl@hdashline\adl@ihdashline
26 \adl@hdashline\adl@inactivehdl
27 }
28 \def\adl@hdashline#1{\noalign{\ifnum0='}\fi
29 % \ifadl@zwhrule \vskip-\arrayrulewidth
30 % \else
31 % \adl@hline\adl@connect\arrayrulewidth
32 % \hrule \@height \arrayrulewidth% lwarp
33 % \fi
34 \@ifnextchar[%]
35 % #1}%
36 % #1[%
37 % \dashlinedash/\dashlinegap
38 % 1pt/1pt
39 % ]}}
40 \def\adl@ihdashline[#1/#2]{\ifnum0='{ \fi}%
41 % \multispan{\adl@columns}\unskip \adl@hcline\z[#1/#2]%
42 % \noalign{\ifnum0='}\fi
43 % \futurelet\@tempa\adl@xhline}
44 \def\adl@inactivehdl[#1/#2]{
45 % \ifadl@zwhrule \vskip-\arrayrulewidth \fi
46 % \hrule \@height\arrayrulewidth
47 % \futurelet\@tempa\adl@xhline}
48 \def\adl@xhline{\ifx\@tempa\hline \adl@ixhline\fi
49 \ifx\@tempa\hdashline \adl@ixhline\fi
50 \ifnum0='{ \fi}}
51 \def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
52 \def\adl@hline#1#2{%
53 % \@tempcna#2
54 % \global\advance\adl@totalheight\@tempcna
55 % \xdef\adl@rowsL{\adl@rowsL
56 % (#1/\number\@tempcna);}
57 % \xdef\adl@rowsR{\adl@rowsR
58 % (#1/\number\@tempcna);}
59 }
60
61 \def\cdashline#1{\noalign{\ifnum0='}\fi
62 \@ifnextchar[%]
63 % {\adl@cdline[#1]}%
64 % {\adl@cdline[#1][\dashlinedash/\dashlinegap]}
65 % {\adl@inactivecdl[#1]}%
66 % {\adl@inactivecdl[#1][\dashlinedash/\dashlinegap]}
67 }
68
69 \def\adl@inactivecdl[#1-#2][#3]{\ifnum0='{ \fi}\cline{#1-#2}}

70 \begin{warpMathJax}
71 \CustomizeMathJax{\newcommand{\firsthdashline}[1][[]]{\hdashline}}
72 \CustomizeMathJax{\let\lasthdashline\firsthdashline}
73 \CustomizeMathJax{\let\cdashline\cline}
74 \end{warpMathJax}

```

File 30 **lwarp-asymptote.sty**

§ 139 Package **asymptote**

(Emulates or patches code by ANDY HAMMERLINDL, JOHN BOWMAN, TOM PRINCE.)

Pkg asymptote

asymptote is patched for use by lwarp.

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex
```

```
lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1
```

```
lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

```
for HTML output: 1 \LWR@ProvidesPackagePass{asymptote}[2016/11/26]

2 \BeforeBeginEnvironment{asy}{%
3   \begin{lateximage}[-asymptote-~\PackageDiagramAltText]%
4 }
5 \AfterEndEnvironment{asy}{\end{lateximage}}
6
7 \xpatchcmd{\asyinclude}
8   {\begingroup}
9   {\begin{lateximage}[-asymptote-~\PackageDiagramAltText]}
10  {}
11  {\LWR@patcherror{asymptote}{asyinclude-begingroup}}
12
13 \xpatchcmd{\asyinclude}
14   {\endgroup}
15   {\end{lateximage}}
16   {}
17   {\LWR@patcherror{asymptote}{asyinclude-endgroup}}
```

File 31 **lwarp-atbegshi.sty**§ 140 Package **atbegshi***(Emulates or patches code by HEIKO OBERDIEK.)*

Pkg atbegshi

atbegshi is ignored.

for HTML output: Discard all options for lwarp-atbegshi:

```
1 \LWR@ProvidesPackageDrop{atbegshi}[2011/10/05]

2 \let\AtBeginShipout\relax
3 \let\AtBeginShipoutNext\relax
4 \let\AtBeginShipoutFirst\relax
5 \let\AtBeginShipoutDiscard\relax
6 \let\AtBeginShipoutInit\relax
7 \let\AtBeginShipoutAddToBox\relax
```

```

8 \let\AtBeginShipoutAddToBoxForeground\relax
9 \let\AtBeginShipoutUpperLeft\relax
10 \let\AtBeginShipoutUpperLeftForeground\relax
11 \let\AtBeginShipoutOriginalShipout\relax
12
13 \newcommand*\AtBeginShipout}[1]{}
14 \newbox\AtBeginShipoutBox
15 \newcommand*\AtBeginShipoutNext}[1]{}
16 \newcommand*\AtBeginShipoutFirst}[1]{}
17 \newcommand*\AtBeginShipoutDiscard{}
18 \newcommand*\AtBeginShipoutInit{}
19 \newcommand*\AtBeginShipoutAddToBox}[1]{}
20 \newcommand*\AtBeginShipoutAddToBoxForeground}[1]{}
21 \newcommand*\AtBeginShipoutUpperLeft}[1]{}
22 \newcommand*\AtBeginShipoutUpperLeftForeground}[1]{}
23 \newcommand*\AtBeginShipoutOriginalShipout}[1]{}
24 \def\AtBeginShipoutBoxWidth{0pt}
25 \def\AtBeginShipoutBoxHeight{0pt}
26 \def\AtBeginShipoutBoxDepth{0pt}

```

File 32 **lwarp-attachfile.sty**

§ 141 Package **attachfile**

(Emulates or patches code by SCOTT PAKIN.)

Pkg attachfile

attachfile is patched for use by lwarp.



Metadata is ignored for now.

for HTML output: 1 \LWR@ProvidesPackagePass{attachfile}[2016/09/18]

Encloses each icon:

```

2 \newenvironment*\LWR@attachfile@icon}
3 {
4   \begin{lateximage}*%
5     [-attachfile-%
6     [%
7       \detokenize\expandafter{\atfi@icon@icon}-%
8       \detokenize\expandafter{\atfi@color@rgb}%
9     ]%
10 }
11 {
12   \end{lateximage}
13 }

```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```

14 \xpretocmd{\atfi@acroGraph}\LWR@attachfile@icon}{}{}
15 \xapptocmd{\atfi@acroGraph}\endLWR@attachfile@icon}{}{}
16
17 \xpretocmd{\atfi@acroPaperclip}\LWR@attachfile@icon}{}{}
18 \xapptocmd{\atfi@acroPaperclip}\endLWR@attachfile@icon}{}{}
19
20 \xpretocmd{\atfi@acroPushPin}\LWR@attachfile@icon}{}{}
21 \xapptocmd{\atfi@acroPushPin}\endLWR@attachfile@icon}{}{}

```

```

22
23 \xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
24 \xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}

```

Disable PDF file embedding:

```
25 \DeclareRobustCommand{\atfi@embedfile}[1]{}

```

The displayed output for an `\attachfile` reference:

```

26 \newcommand*{\LWR@attachfile@appearance}{}
27
28 \DeclareRobustCommand{\atfi@set@appearance}[1]{%
29   \def\LWR@attachfile@appearance{#1}%
30 }

```

A file annotation becomes a reference:

```

31 \DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
32   \LWR@href{#1}{\LWR@attachfile@appearance}%
33 }

```

File 33 **lwarp-attachfile2.sty**

§ 142 Package **attachfile2**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg attachfile2

attachfile2 is patched for use by lwarp.



Metadata is ignored for now.

for HTML output: 1 \LWR@ProvidesPackagePass{attachfile2}[2016/05/16]

Adds memory of the selected color:

```

2 \def\LWR@attachfiletwo@color{}%
3
4 \define@key{AtFi}{color}{%
5   \def\LWR@attachfiletwo@color{#1}%   lwarp
6   \HyColor@AttachfileColor{#1}%
7     \atfi@color@tex\atfi@color@inline\atfi@color@annot
8     {attachfile2}{color}%
9 }

```

Encloses each icon:

```

10 \newenvironment*{LWR@attachfile@icon}
11 {
12   \begin{lateximage}*%
13     [-attachfile-]%
14     [%
15       \detokenize\expandafter{\atfi@icon@icon}-%
16       \detokenize\expandafter{\LWR@attachfiletwo@color}%
17     ]%
18 }

```

```

19 {
20   \end{lateximage}
21 }

```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```

22 \xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
23 \xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}
24
25 \xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
26 \xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}
27
28 \xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
29 \xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}
30
31 \xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
32 \xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}

```

Disable PDF file embedding:

```

33 \DeclareRobustCommand{\atfi@embedfile}[1]{}

```

The displayed output for an `\attachfile` reference:

```

34 \newcommand*{\LWR@attachfile@appearance}{}
35
36 \def\atfi@set@appearance@icon{%
37   \atfi@set@appearance{\csname atfi@acro\atfi@icon@icon\endcsname}%
38 }
39
40 \DeclareRobustCommand{\atfi@set@appearance}[1]{%
41   \def\LWR@attachfile@appearance{#1}%
42 }

```

A file annotation becomes a reference:

```

43 \DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
44   \LWR@href{#1}{\LWR@attachfile@appearance}%
45 }

```

Modified for text color:

```

46 \DeclareRobustCommand{\notextattachfile}[2][]{%
47   \begingroup
48     \atfi@setup{#1}%
49     \ifatfi@print
50     \leavevmode
51     \begingroup
52       \HyColor@UseColor\atfi@color@tex
53       \LWR@textcurrentcolor{#2}%      lwarp
54 % \strut
55     \endgroup
56 %   \else
57 %     \sbox\ltx@zero{#2\strut}%
58 %     \makebox[\wd0]{}%
59   \fi
60 \endgroup
61 }

```

Modified to draw the icon:

```

62 \DeclareRobustCommand{\noattachfile}[1][\]{%
63   \begingroup
64     \atfi@setup{#1}%
65     \atfi@set@appearance@icon
66     \ifatfi@print
67     \LWR@attachfile@appearance%   lwarp
68 %   \expandafter
69 %     \atfi@refxform\csname atfi@appobj@atfi@icon@icon\endcsname
70 %   \else
71 %     \makebox[\atfi@appearancewidth]{%
72     \fi
73   \endgroup
74 }

```

File 34 **lwarp-authblk.sty**

§ 143 Package **authblk**

(Emulates or patches code by PATRICK W. DALY.)

Pkg authblk

authblk is patched for HTML.

package support

⚠ load order

lwarp supports the native L^AT_EX titling commands, and also supports the packages `authblk` and `titling`. If both are used, `authblk` should be loaded before `titling`.

\published and \subtitle

If using the `titling` package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 69.8.

(Emulates or patches code by PATRICK W. DALY.)

for HTML output:

Require that `authblk` be loaded before `titling`:

```

1 \IfPackageLoadedTF{titling}{
2   \PackageError{lwarp-authblk}
3     {Package authblk must be loaded before titling}
4     {%
5       Titling appends authblk's author macro,
6       so authblk must be loaded first.%
7     }
8 }
9 {\relax}

```

Load `authblk`:

```
10 \LWR@ProvidesPackagePass{authblk}[2001/02/27]
```

Patch to add a class for the affiliation:

```

11 \LetLtxMacro\LWRAB@affil\affil
12
13 \renewcommand{\affil}[2][\]{%
14 \LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}
15 }

```

Create an HTML break for an `\authorcr`:

```
16 \renewcommand*{\authorcr}{\protect\LWR@newLinebr}
```

File 35 **lwarp-autobreak.sty**

§ 144 Package **autobreak**

(Emulates or patches code by TAKAHIRO UEDA.)

Pkg autobreak

autobreak is used as-is for SVG math, and nullified for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{autobreak}[2017/02/23]

For MATHJAX. The modified align environment is used for SVG math, but is reverted to its original for MATHJAX. (Extraneous commas were appearing in the result.)

```
2 \begin{warpMathJax}
3 \renewenvironment{autobreak}{\newcommand{\MoveEqLeft}[1]{}{}}
4 \let\start@align\@autobreak@oldstart@align
5 \let\endalign\@autobreak@oldendalign
6 \CustomizeMathJax{\newenvironment{autobreak}{}{}}
7 \CustomizeMathJax{\newcommand{\MoveEqLeft}[1]{}{}}
8 \CustomizeMathJax{\newcommand{\everybeforeautobreak}[1]{}{}}
9 \CustomizeMathJax{\newcommand{\everyafterautobreak}[1]{}{}}
10 \end{warpMathJax}
```

File 36 **lwarp-autonum.sty**

§ 145 Package **autonum**

Pkg autonum

autonum is ignored.

 **numbering, +** All equations are numbered in HTML output. MATHJAX does not support the “+” environments.

for HTML output: 1 \LWR@ProvidesPackageDrop{autonum}[2015/01/18]

```
2 \RequirePackage{amsmath}
3
4
5 \newenvironment{equation+}{\equation}{\endequation}
6
7
8 \newenvironment{gather+}{\gather}{\endgather}
9
10 \BeforeBeginEnvironment{gather+}{\LWR@amsmathenv@@before{gather+}}
11
12 \AfterEndEnvironment{gather+}{\LWR@amsmathenv@@after}
13
14
15 \newenvironment{multline+}{\multline}{\endmultline}
16
17 \BeforeBeginEnvironment{multline+}{\LWR@amsmathenv@@before{multline+}}
18
19 \AfterEndEnvironment{multline+}{\LWR@amsmathenv@@after}
```

```

20 \newenvironment{flalign+}{\flalign}\endflalign}
21
22 \BeforeBeginEnvironment{flalign+}{\LWR@amsmathenv@@before{flalign+}}
23
24 \AfterEndEnvironment{flalign+}{\LWR@amsmathenv@@after}
25
26
27 \newenvironment{align+}{\align}\endalign}
28
29 \BeforeBeginEnvironment{align+}{\LWR@amsmathenv@@before{aline+}}
30
31 \AfterEndEnvironment{align+}{\LWR@amsmathenv@@after}
32
33
34 \newenvironment{alignat+}{\alignat}\endalignat}
35
36 \BeforeBeginEnvironment{alignat+}{\LWR@amsmathenv@@before{alineat+}}
37
38 \AfterEndEnvironment{alignat+}{\LWR@amsmathenv@@after}
39
40
41 \newenvironment{split+}{\split}\endsplit}

```

File 37 **lwarp-awesomebox.sty**

§ 146 Package **awesomebox**

(Emulates or patches code by ÉTIENNE DEPARIS.)

Pkg awesomebox

awesomebox is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{awesomebox}[2019/07/27]
2 \newcommand*{\LWR@awesomebox@boxborders}{}%
3 \newcommand*{\LWR@awesomebox@contentsborders}{}%
4
5 \newcommand*{\LWR@awesomebox@ruleborders}{}%
6   border-top: 1px solid black ;
7   border-bottom: 1px solid black%
8 }
9
10 % \awesomebox[1:vrulecolor][2:hrule][3:title]{4:vrulewidth}{5:icon}{6:iconcolor}{7:content}
11 \RenewDocumentCommand \awesomebox { O{abvrulecolor} O{} o m m m +m }{%
12   \begin{awesomeblock}[#1][#2][#3]{#4}{#5}{#6}
13     #7
14   \end{awesomeblock}
15 }
16
17 % \begin{awesomeblock}[1:vrulecolor][2:hrule][3:title]{4:vrulewidth}{5:icon}{6:iconcolor}
18 % <contents>
19 % \end{awesomeblock}
20 \RenewDocumentEnvironment{awesomeblock}{ O{abvrulecolor} O{} o m m m }
21 {%
22   \LWR@forceminwidth{#4}%
23   \convertcolorspec{named}{#1}{HTML}\LWR@tempcolor%
24   \renewcommand*{\LWR@awesomebox@boxborders}{}%
25   \renewcommand*{\LWR@awesomebox@contentsborders}{}%

```

```

26 \ifdefstrequal{\abShortLine}{#2}{%
27   \renewcommand*\LWR@awesomebox@contentsborders{\LWR@awesomebox@ruleborders}%
28 }{%
29 \ifdefstrequal{\abLongLine}{#2}{%
30   \renewcommand*\LWR@awesomebox@boxborders{\LWR@awesomebox@ruleborders}%
31 }{%
32 \begin{BlockClass}[\LWR@awesomebox@boxborders]{awesomebox}
33 \begin{BlockClass}[%
34   margin-left: 2\% ;
35   vertical-align: top
36 ]{minipage}
37   \color{#6}\Huge #5
38 \end{BlockClass}
39 \begin{BlockClass}[%
40   width:75\% ;
41   vertical-align: top ;
42   padding-left: 1em ;
43   \LWR@awesomebox@contentsborders ;
44   border-left: \LWR@printlength{\LWR@atleastonept} %
45     solid \LWR@origpound\LWR@tempcolor%
46 ]{minipage}
47   \IfValueTF{#3}{#3\newline}{}
48 }
49 {%
50 \end{BlockClass}
51 \end{BlockClass}
52 }

```

File 38 **lwarp-axessibility.sty**

§ 147 Package **axessibility**

Pkg axessibility

axessibility is ignored.

for HTML output:

```

1 \PackageInfo{lwarp}{Using the lwarp version of package ‘axessibility’.%
2 \ProvidesPackage{lwarp-axessibility}% no date is declared by the original
3
4 \newif\iftagpdfopt
5
6 \DeclareOption{accsupp}{
7   \tagpdfoptfalse
8 }
9
10 \DeclareOption{tagpdf}{
11   \tagpdfopttrue
12 }
13
14 \ProcessOptions\relax
15
16 \iftagpdfopt
17   \RequirePackage{tagpdf}
18 \else
19   \RequirePackage{accsupp}
20 \fi

21 \long\def\wrap#1{}
22 \long\def\wrapml#1{}

```

```
23 \long\def\wrapmlstar#1{}
24 \long\def\wrapmlalt#1{}
```

For MATHJAX. These usually will not be needed.

```
25 \begin{warpMathJax}
26 \CustomizeMathJax{\newcommand{\wrap}[1]{} }
27 \CustomizeMathJax{\newcommand{\wrapml}[1]{} }
28 \CustomizeMathJax{\newcommand{\wrapmlstar}[1]{} }
29 \CustomizeMathJax{\newcommand{\wrapmlalt}[1]{} }
30 \end{warpMathJax}
```

File 39 **lwarp-axodraw2.sty**

§ 148 Package **axodraw2**

(Emulates or patches code by JOHN C. COLLINS, J.A.M. VERMASEREN.)

Pkg axodraw2

axodraw2 is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{axodraw2}[2018/02/15]
2 \BeforeBeginEnvironment{axopicture}{%
3   \begin{lateximage}[-axopicture-~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{axopicture}{\end{lateximage}}
```

File 40 **lwarp-backnaur.sty**

§ 149 Package **backnaur**

(Emulates or patches code by ADRIAN P. ROBSON.)

Pkg backnaur

backnaur is patched for use by lwarp, and emulated for MATHJAX.

for HTML output:

```
1 \LWR@ProvidesPackagePass{backnaur}[2019/06/18]
2 \renewenvironment{bnf}{\eqnarray}{\endeqnarray}
3 \renewenvironment{bnf*}{\csuse{eqnarray*}}{\csuse{endeqnarray*}}
```

For MATHJAX:

```
4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\bnf}[1]{\langle \text{\textrm{#1}} \rangle}}
6 \CustomizeMathJax{\newcommand{\bnfor}{\; \mid \;}}
7 \CustomizeMathJax{\newcommand{\bnfsp}{\;}}
8 \IfPackageLoadedWithOptionsTF{backnaur}{perp}{
9   \CustomizeMathJax{\newcommand{\bnfes}{\perp}}
10 }{
11   \IfPackageLoadedWithOptionsTF{backnaur}{epsilon}{
12     \CustomizeMathJax{\newcommand{\bnfes}{\epsilon}}
13   }
```

```

14     \CustomizeMathJax{\newcommand{\bnfes}{\lambda}}
15   }
16 }
17 \IfPackageLoadedWithOptionsTF{backnaur}{tsrm}{
18   \CustomizeMathJax{\newcommand{\bnfts}[1]{\text{#1}}}
19 }{
20   \CustomizeMathJax{\newcommand{\bnfts}[1]{\text{\texttt{#1}}}}
21 }
22 \CustomizeMathJax{\newcommand{\bnftd}[1]{\text{\textit{#1}}}}
23 \CustomizeMathJax{\newcommand{\bnfsk}{\dots}}
24 \IfPackageLoadedWithOptionsTF{backnaur}{altpo}{
25   \CustomizeMathJax{\newcommand{\bnfpo}{:=}}
26 }{
27   \CustomizeMathJax{\newcommand{\bnfpo}{\models}}
28 }
29 \CustomizeMathJax{\newcommand{\bnfprod}{\ifstar{\LWRbnfprodnn}{\LWRbnfprodyn}}}
30 \CustomizeMathJax{\newcommand{\LWRbnfprodyn}[2]{\bnfnp{#1} & \bnfpo & #2}}
31 \CustomizeMathJax{\newcommand{\LWRbnfprodnn}[2]{\nonumber \bnfnp{#1} & \bnfpo & #2}}
32 \CustomizeMathJax{\newcommand{\bnfmore}{\ifstar{\LWRbnfmorenn}{\LWRbnfmoreyn}}}
33 \CustomizeMathJax{\newcommand{\LWRbnfmoreyn}[1]{& & #1}}
34 \CustomizeMathJax{\newcommand{\LWRbnfmorenn}[1]{\nonumber & & #1}}
35 \end{warpMathJax}

```

File 41 **lwarp-backref.sty**

§ 150 Package **backref**

(Emulates or patches code by DAVID CARLISLE AND SEBASTIAN RAHTZ.)

Pkg backref

backref is patched for use by lwarp.

 **loading** Note that backref must be explicitly loaded, and is not automatically loaded by hyperref when generating HTML output.

for HTML output: 1 \LWR@ProvidesPackagePass{backref}[2016/05/21]

Force the hyperref option:

```

2 \def\backref{}
3
4 \long\def\hyper@section@backref#1#2#3{%
5   \LWR@refwithsection{#3}%
6 }
7
8 \let\backrefxxx\hyper@section@backref

```

File 42 **lwarp-balance.sty**

§ 151 Package **balance**

(Emulates or patches code by PATRICK W. DALY.)

Pkg balance

balance is ignored.

for HTML output:

Discard all options for `lwarp-balance`:

```
1 \LWR@ProvidesPackageDrop{balance}[1999/02/23]

2 \newcommand*\balance{}
3 \newcommand*\nobalance{}
```

File 43 **lwarp-bbding.sty**

§ 152 Package **bbding**

(Emulates or patches code by KAREL HORAK, PETER MØLLER NEERGAARD.)

Pkg bbding

`bbding` is patched for use by `lwarp`.

for HTML output:

```
1 \LWR@ProvidesPackagePass{bbding}[1999/04/15]

2 \newcommand*\LWR@bbdingsymbol}[2]{\HTMLUnicode{#2}}
3
4 \newcommand{\LWR@HTML@ScissorRightBrokenBottom}{\LWR@bbdingsymbol{000} {2701}}
5 \newcommand{\LWR@HTML@ScissorRight}{\LWR@bbdingsymbol{001} {2702}}
6 \newcommand{\LWR@HTML@ScissorRightBrokenTop}{\LWR@bbdingsymbol{002} {2703}}
7 \newcommand{\LWR@HTML@ScissorLeftBrokenBottom}{\LWR@bbdingsymbol{003} {2701}}
8 \newcommand{\LWR@HTML@ScissorLeft}{\LWR@bbdingsymbol{004} {2702}}
9 \newcommand{\LWR@HTML@ScissorLeftBrokenTop}{\LWR@bbdingsymbol{005} {2703}}
10 \newcommand{\LWR@HTML@ScissorHollowRight}{\LWR@bbdingsymbol{006} {2704}}
11 \newcommand{\LWR@HTML@ScissorHollowLeft}{\LWR@bbdingsymbol{007} {2704}}
12 \newcommand{\LWR@HTML@Phone}{\LWR@bbdingsymbol{010} {260E}}
13 \newcommand{\LWR@HTML@PhoneHandset}{\LWR@bbdingsymbol{011} {2706}}
14 \newcommand{\LWR@HTML@Tape}{\LWR@bbdingsymbol{012} {2707}}
15 \newcommand{\LWR@HTML@Plane}{\LWR@bbdingsymbol{013} {2708}}
16 \newcommand{\LWR@HTML@Envelope}{\LWR@bbdingsymbol{014} {2709}}
17 \newcommand{\LWR@HTML@HandCuffRight}{\LWR@bbdingsymbol{015} {261B}}
18 \newcommand{\LWR@HTML@HandCuffLeft}{\LWR@bbdingsymbol{016} {261A}}
19 \newcommand{\LWR@HTML@HandCuffRightUp}{\LWR@bbdingsymbol{017} {261D}}
20 \newcommand{\LWR@HTML@HandCuffLeftUp}{\LWR@bbdingsymbol{020} {261F}}
21 \newcommand{\LWR@HTML@HandRight}{\LWR@bbdingsymbol{021} {261E}}
22 \newcommand{\LWR@HTML@HandLeft}{\LWR@bbdingsymbol{022} {261C}}
23 \newcommand{\LWR@HTML@HandRightUp}{\LWR@bbdingsymbol{023} {261D}}
24 \newcommand{\LWR@HTML@HandLeftUp}{\LWR@bbdingsymbol{024} {261F}}
25 \newcommand{\LWR@HTML@Peace}{\LWR@bbdingsymbol{025} {270C}}
26 \newcommand{\LWR@HTML@HandPencilLeft}{\LWR@bbdingsymbol{026} {270D}}
27 \newcommand{\LWR@HTML@PencilRight}{\LWR@bbdingsymbol{027} {270F}}
28 \newcommand{\LWR@HTML@PencilLeft}{\LWR@bbdingsymbol{030} {270F}}
29 \newcommand{\LWR@HTML@PencilRightUp}{\LWR@bbdingsymbol{031} {2710}}
30 \newcommand{\LWR@HTML@PencilLeftUp}{\LWR@bbdingsymbol{032} {2710}}
31 \newcommand{\LWR@HTML@PencilRightDown}{\LWR@bbdingsymbol{033} {270E}}
32 \newcommand{\LWR@HTML@PencilLeftDown}{\LWR@bbdingsymbol{034} {270E}}
33 \newcommand{\LWR@HTML@NibRight}{\LWR@bbdingsymbol{035} {2711}}
34 \newcommand{\LWR@HTML@NibLeft}{\LWR@bbdingsymbol{036} {2711}}
35 \newcommand{\LWR@HTML@NibSolidRight}{\LWR@bbdingsymbol{037} {2712}}
36 \newcommand{\LWR@HTML@NibSolidLeft}{\LWR@bbdingsymbol{040} {2712}}
37 \newcommand{\LWR@HTML@Checkmark}{\LWR@bbdingsymbol{041} {2713}}
38 \newcommand{\LWR@HTML@CheckmarkBold}{\LWR@bbdingsymbol{042} {2714}}
39 \newcommand{\LWR@HTML@XSolid}{\LWR@bbdingsymbol{043} {2715}}
40 \newcommand{\LWR@HTML@XSolidBold}{\LWR@bbdingsymbol{044} {2716}}
41 \newcommand{\LWR@HTML@XSolidBrush}{\LWR@bbdingsymbol{045} {2717}}
```

42	\newcommand{\LWR@HTML@PlusOutline}{\LWR@bbdingsymbol{046}}	{2719}}
43	\newcommand{\LWR@HTML@Plus}{\LWR@bbdingsymbol{047}}	{271A}}
44	\newcommand{\LWR@HTML@PlusCenterOpen}{\LWR@bbdingsymbol{050}}	{271C}}
45	\newcommand{\LWR@HTML@PlusThinCenterOpen}{\LWR@bbdingsymbol{051}}	{271B}}
46	\newcommand{\LWR@HTML@Cross}{\LWR@bbdingsymbol{052}}	{271D}}
47	\newcommand{\LWR@HTML@CrossOpenShadow}{\LWR@bbdingsymbol{053}}	{271E}}
48	\newcommand{\LWR@HTML@CrossOutline}{\LWR@bbdingsymbol{054}}	{271F}}
49	\newcommand{\LWR@HTML@CrossBoldOutline}{\LWR@bbdingsymbol{055}}	{271F}}
50	\newcommand{\LWR@HTML@CrossMaltese}{\LWR@bbdingsymbol{056}}	{2720}}
51	\newcommand{\LWR@HTML@DavidStarSolid}{\LWR@bbdingsymbol{057}}	{2721}}
52	\newcommand{\LWR@HTML@DavidStar}{\LWR@bbdingsymbol{060}}	{2721}}
53	\newcommand{\LWR@HTML@FourAsterisk}{\LWR@bbdingsymbol{061}}	{2722}}
54	\newcommand{\LWR@HTML@JackStar}{\LWR@bbdingsymbol{062}}	{2723}}
55	\newcommand{\LWR@HTML@JackStarBold}{\LWR@bbdingsymbol{063}}	{2724}}
56	\newcommand{\LWR@HTML@CrossClowerTips}{\LWR@bbdingsymbol{064}}	{2725}}
57	\newcommand{\LWR@HTML@FourStar}{\LWR@bbdingsymbol{065}}	{2726}}
58	\newcommand{\LWR@HTML@FourStarOpen}{\LWR@bbdingsymbol{066}}	{2727}}
59	\newcommand{\LWR@HTML@FiveStarLines}{\LWR@bbdingsymbol{067}}	{2729}}
60	\newcommand{\LWR@HTML@FiveStar}{\LWR@bbdingsymbol{070}}	{2605}}
61	\newcommand{\LWR@HTML@FiveStarOpen}{\LWR@bbdingsymbol{071}}	{2729}}
62	\newcommand{\LWR@HTML@FiveStarOpenCircled}{\LWR@bbdingsymbol{072}}	{272A}}
63	\newcommand{\LWR@HTML@FiveStarCenterOpen}{\LWR@bbdingsymbol{073}}	{272B}}
64	\newcommand{\LWR@HTML@FiveStarOpenDotted}{\LWR@bbdingsymbol{074}}	{272C}}
65	\newcommand{\LWR@HTML@FiveStarOutline}{\LWR@bbdingsymbol{075}}	{272D}}
66	\newcommand{\LWR@HTML@FiveStarOutlineHeavy}{\LWR@bbdingsymbol{076}}	{272E}}
67	\newcommand{\LWR@HTML@FiveStarConvex}{\LWR@bbdingsymbol{077}}	{272F}}
68	\newcommand{\LWR@HTML@FiveStarShadow}{\LWR@bbdingsymbol{100}}	{2730}}
69	\newcommand{\LWR@HTML@AsteriskBold}{\LWR@bbdingsymbol{101}}	{2731}}
70	\newcommand{\LWR@HTML@AsteriskCenterOpen}{\LWR@bbdingsymbol{102}}	{2732}}
71	\newcommand{\LWR@HTML@AsteriskThin}{\LWR@bbdingsymbol{103}}	{273B}}
72	\newcommand{\LWR@HTML@AsteriskThinCenterOpen}{\LWR@bbdingsymbol{104}}	{273C}}
73	\newcommand{\LWR@HTML@EightStarTaper}{\LWR@bbdingsymbol{105}}	{2733}}
74	\newcommand{\LWR@HTML@EightStarConvex}{\LWR@bbdingsymbol{106}}	{2735}}
75	\newcommand{\LWR@HTML@SixStar}{\LWR@bbdingsymbol{107}}	{2736}}
76	\newcommand{\LWR@HTML@EightStar}{\LWR@bbdingsymbol{110}}	{2737}}
77	\newcommand{\LWR@HTML@EightStarBold}{\LWR@bbdingsymbol{111}}	{2738}}
78	\newcommand{\LWR@HTML@TwelveStar}{\LWR@bbdingsymbol{112}}	{2739}}
79	\newcommand{\LWR@HTML@SixteenStarLight}{\LWR@bbdingsymbol{113}}	{273A}}
80	\newcommand{\LWR@HTML@SixFlowerPetalRemoved}{\LWR@bbdingsymbol{114}}	{273B}}
81	\newcommand{\LWR@HTML@SixFlowerOpenCenter}{\LWR@bbdingsymbol{115}}	{273C}}
82	\newcommand{\LWR@HTML@Asterisk}{\LWR@bbdingsymbol{116}}	{273D}}
83	\newcommand{\LWR@HTML@SixFlowerAlternate}{\LWR@bbdingsymbol{117}}	{273E}}
84	\newcommand{\LWR@HTML@FiveFlowerPetal}{\LWR@bbdingsymbol{120}}	{273F}}
85	\newcommand{\LWR@HTML@SixFlowerPetalDotted}{\LWR@bbdingsymbol{121}}	{2740}}
86	\newcommand{\LWR@HTML@FiveFlowerOpen}{\LWR@bbdingsymbol{122}}	{2740}}
87	\newcommand{\LWR@HTML@EightFlowerPetal}{\LWR@bbdingsymbol{123}}	{2741}}
88	\newcommand{\LWR@HTML@SunshineOpenCircled}{\LWR@bbdingsymbol{124}}	{2742}}
89	\newcommand{\LWR@HTML@SixFlowerAltPetal}{\LWR@bbdingsymbol{125}}	{2743}}
90	\newcommand{\LWR@HTML@FourClowerOpen}{\LWR@bbdingsymbol{126}}	{273F}}
91	\newcommand{\LWR@HTML@FourClowerSolid}{\LWR@bbdingsymbol{127}}	{273F}}
92	\newcommand{\LWR@HTML@AsteriskRoundedEnds}{\LWR@bbdingsymbol{130}}	{2749}}
93	\newcommand{\LWR@HTML@EightFlowerPetalRemoved}{\LWR@bbdingsymbol{131}}	{274A}}
94	\newcommand{\LWR@HTML@EightAsterisk}{\LWR@bbdingsymbol{132}}	{274B}}
95	\newcommand{\LWR@HTML@SixFlowerRemovedOpenPetal}{\LWR@bbdingsymbol{133}}	{2740}}
96	\newcommand{\LWR@HTML@SparkleBold}{\LWR@bbdingsymbol{134}}	{2748}}
97	\newcommand{\LWR@HTML@Sparkle}{\LWR@bbdingsymbol{135}}	{2747}}
98	\newcommand{\LWR@HTML@SnowflakeChevron}{\LWR@bbdingsymbol{136}}	{2744}}
99	\newcommand{\LWR@HTML@SnowflakeChevronBold}{\LWR@bbdingsymbol{137}}	{2746}}
100	\newcommand{\LWR@HTML@Snowflake}{\LWR@bbdingsymbol{140}}	{2744}}
101	\newcommand{\LWR@HTML@CircleSolid}{\LWR@bbdingsymbol{141}}	{25CF}}

102 \newcommand{\LWR@HTML@Ellipse}{\LWR@bbdingsymbol{142}} {274D}}
 103 \newcommand{\LWR@HTML@EllipseSolid}{\LWR@bbdingsymbol{143}} {25CF}}
 104 \newcommand{\LWR@HTML@CircleShadow}{\LWR@bbdingsymbol{144}} {274D}}
 105 \newcommand{\LWR@HTML@EllipseShadow}{\LWR@bbdingsymbol{145}} {274D}}
 106 \newcommand{\LWR@HTML@Square}{\LWR@bbdingsymbol{146}} {25A1}}
 107 \newcommand{\LWR@HTML@SquareSolid}{\LWR@bbdingsymbol{147}} {25A0}}
 108 \newcommand{\LWR@HTML@SquareShadowBottomRight}{\LWR@bbdingsymbol{150}} {2751}}
 109 \newcommand{\LWR@HTML@SquareShadowTopRight}{\LWR@bbdingsymbol{151}} {2752}}
 110 \newcommand{\LWR@HTML@SquareShadowTopLeft}{\LWR@bbdingsymbol{152}} {2752}}
 111 \newcommand{\LWR@HTML@SquareCastShadowBottomRight}{\LWR@bbdingsymbol{153}} {2751}}
 112 \newcommand{\LWR@HTML@SquareCastShadowTopRight}{\LWR@bbdingsymbol{154}} {2752}}
 113 \newcommand{\LWR@HTML@SquareCastShadowTopLeft}{\LWR@bbdingsymbol{155}} {2752}}
 114 \newcommand{\LWR@HTML@TriangleUp}{\LWR@bbdingsymbol{156}} {25B2}}
 115 \newcommand{\LWR@HTML@TriangleDown}{\LWR@bbdingsymbol{157}} {25BC}}
 116 \newcommand{\LWR@HTML@DiamondSolid}{\LWR@bbdingsymbol{160}} {25C6}}
 117 \newcommand{\LWR@HTML@OrnamentDiamondSolid}{\LWR@bbdingsymbol{161}} {2756}}
 118 \newcommand{\LWR@HTML@HalfCircleRight}{\LWR@bbdingsymbol{162}} {25D7}}
 119 \newcommand{\LWR@HTML@HalfCircleLeft}{\LWR@bbdingsymbol{163}} {25D6}}
 120 \newcommand{\LWR@HTML@RectangleThin}{\LWR@bbdingsymbol{164}} {2758}}
 121 \newcommand{\LWR@HTML@Rectangle}{\LWR@bbdingsymbol{165}} {2759}}
 122 \newcommand{\LWR@HTML@RectangleBold}{\LWR@bbdingsymbol{166}} {275A}}
 123 \newcommand{\LWR@HTML@ArrowBoldRightStrobe}{\LWR@bbdingsymbol{167}} {27A0}}
 124 \newcommand{\LWR@HTML@ArrowBoldUpRight}{\LWR@bbdingsymbol{170}} {27A6}}
 125 \newcommand{\LWR@HTML@ArrowBoldDownRight}{\LWR@bbdingsymbol{171}} {27A5}}
 126 \newcommand{\LWR@HTML@ArrowBoldRightShort}{\LWR@bbdingsymbol{172}} {27A7}}
 127 \newcommand{\LWR@HTML@ArrowBoldRightCircled}{\LWR@bbdingsymbol{173}} {27B2}}
 128
 129
 130 \LWR@formatted{ScissorRightBrokenBottom}
 131 \LWR@formatted{ScissorRight}
 132 \LWR@formatted{ScissorRightBrokenTop}
 133 \LWR@formatted{ScissorLeftBrokenBottom}
 134 \LWR@formatted{ScissorLeft}
 135 \LWR@formatted{ScissorLeftBrokenTop}
 136 \LWR@formatted{ScissorHollowRight}
 137 \LWR@formatted{ScissorHollowLeft}
 138 \LWR@formatted{Phone}
 139 \LWR@formatted{PhoneHandset}
 140 \LWR@formatted{Tape}
 141 \LWR@formatted{Plane}
 142 \LWR@formatted{Envelope}
 143 \LWR@formatted{HandCuffRight}
 144 \LWR@formatted{HandCuffLeft}
 145 \LWR@formatted{HandCuffRightUp}
 146 \LWR@formatted{HandCuffLeftUp}
 147 \LWR@formatted{HandRight}
 148 \LWR@formatted{HandLeft}
 149 \LWR@formatted{HandRightUp}
 150 \LWR@formatted{HandLeftUp}
 151 \LWR@formatted{Peace}
 152 \LWR@formatted{HandPencilLeft}
 153 \LWR@formatted{PencilRight}
 154 \LWR@formatted{PencilLeft}
 155 \LWR@formatted{PencilRightUp}
 156 \LWR@formatted{PencilLeftUp}
 157 \LWR@formatted{PencilRightDown}
 158 \LWR@formatted{PencilLeftDown}
 159 \LWR@formatted{NibRight}
 160 \LWR@formatted{NibLeft}
 161 \LWR@formatted{NibSolidRight}

162 \LWR@formatted{NibSolidLeft}
163 \LWR@formatted{Checkmark}
164 \LWR@formatted{CheckmarkBold}
165 \LWR@formatted{XSolid}
166 \LWR@formatted{XSolidBold}
167 \LWR@formatted{XSolidBrush}
168 \LWR@formatted{PlusOutline}
169 \LWR@formatted{Plus}
170 \LWR@formatted{PlusCenterOpen}
171 \LWR@formatted{PlusThinCenterOpen}
172 \LWR@formatted{Cross}
173 \LWR@formatted{CrossOpenShadow}
174 \LWR@formatted{CrossOutline}
175 \LWR@formatted{CrossBoldOutline}
176 \LWR@formatted{CrossMaltese}
177 \LWR@formatted{DavidStarSolid}
178 \LWR@formatted{DavidStar}
179 \LWR@formatted{FourAsterisk}
180 \LWR@formatted{JackStar}
181 \LWR@formatted{JackStarBold}
182 \LWR@formatted{CrossClowerTips}
183 \LWR@formatted{FourStar}
184 \LWR@formatted{FourStarOpen}
185 \LWR@formatted{FiveStarLines}
186 \LWR@formatted{FiveStar}
187 \LWR@formatted{FiveStarOpen}
188 \LWR@formatted{FiveStarOpenCircled}
189 \LWR@formatted{FiveStarCenterOpen}
190 \LWR@formatted{FiveStarOpenDotted}
191 \LWR@formatted{FiveStarOutline}
192 \LWR@formatted{FiveStarOutlineHeavy}
193 \LWR@formatted{FiveStarConvex}
194 \LWR@formatted{FiveStarShadow}
195 \LWR@formatted{AsteriskBold}
196 \LWR@formatted{AsteriskCenterOpen}
197 \LWR@formatted{AsteriskThin}
198 \LWR@formatted{AsteriskThinCenterOpen}
199 \LWR@formatted{EightStarTaper}
200 \LWR@formatted{EightStarConvex}
201 \LWR@formatted{SixStar}
202 \LWR@formatted{EightStar}
203 \LWR@formatted{EightStarBold}
204 \LWR@formatted{TwelveStar}
205 \LWR@formatted{SixteenStarLight}
206 \LWR@formatted{SixFlowerPetalRemoved}
207 \LWR@formatted{SixFlowerOpenCenter}
208 \LWR@formatted{Asterisk}
209 \LWR@formatted{SixFlowerAlternate}
210 \LWR@formatted{FiveFlowerPetal}
211 \LWR@formatted{SixFlowerPetalDotted}
212 \LWR@formatted{FiveFlowerOpen}
213 \LWR@formatted{EightFlowerPetal}
214 \LWR@formatted{SunshineOpenCircled}
215 \LWR@formatted{SixFlowerAltPetal}
216 \LWR@formatted{FourClowerOpen}
217 \LWR@formatted{FourClowerSolid}
218 \LWR@formatted{AsteriskRoundedEnds}
219 \LWR@formatted{EightFlowerPetalRemoved}
220 \LWR@formatted{EightAsterisk}
221 \LWR@formatted{SixFlowerRemovedOpenPetal}

```

222 \LWR@formatted{SparkleBold}
223 \LWR@formatted{Sparkle}
224 \LWR@formatted{SnowflakeChevron}
225 \LWR@formatted{SnowflakeChevronBold}
226 \LWR@formatted{Snowflake}
227 \LWR@formatted{CircleSolid}
228 \LWR@formatted{Ellipse}
229 \LWR@formatted{EllipseSolid}
230 \LWR@formatted{CircleShadow}
231 \LWR@formatted{EllipseShadow}
232 \LWR@formatted{Square}
233 \LWR@formatted{SquareSolid}
234 \LWR@formatted{SquareShadowBottomRight}
235 \LWR@formatted{SquareShadowTopRight}
236 \LWR@formatted{SquareShadowTopLeft}
237 \LWR@formatted{SquareCastShadowBottomRight}
238 \LWR@formatted{SquareCastShadowTopRight}
239 \LWR@formatted{SquareCastShadowTopLeft}
240 \LWR@formatted{TriangleUp}
241 \LWR@formatted{TriangleDown}
242 \LWR@formatted{DiamondSolid}
243 \LWR@formatted{OrnamentDiamondSolid}
244 \LWR@formatted{HalfCircleRight}
245 \LWR@formatted{HalfCircleLeft}
246 \LWR@formatted{RectangleThin}
247 \LWR@formatted{Rectangle}
248 \LWR@formatted{RectangleBold}
249 \LWR@formatted{ArrowBoldRightStrobe}
250 \LWR@formatted{ArrowBoldUpRight}
251 \LWR@formatted{ArrowBoldDownRight}
252 \LWR@formatted{ArrowBoldRightShort}
253 \LWR@formatted{ArrowBoldRightCircled}

```

File 44 **lwarp-beamerarticle.sty**

§ 153 Package **beamerarticle**

(Emulates or patches code by TILL TANTAU, VEDRAN MILETIĆ, LOUIS STUART, JOSEPH WRIGHT.)

Pkg beamerarticle

beamerarticle is patched for use by **lwarp**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{beamerarticle}[2021/05/26]

2 \renewcommand<>{\textcolor}{\only#1{\beameroriginal{\textcolor}}}
3
4 \AtBeginDocument{
5
6 \renewcommand<>{\LWR@listitem}{%
7   \only#1{%
8     \beameroriginal{\LWR@listitem}%
9   }}%
10 }
11
12 \renewcommand<>{\LWR@itemizeitem}{%
13   \only#1{%
14     \beameroriginal{\LWR@itemizeitem}%
15   }}%

```

```

16 }
17
18 \renewcommand<>{\LWR@descitem}{%
19   \only#1{%
20     \beameroriginal{\LWR@descitem}%
21   }%
22 }
23
24 \renewcommand<>{\abstract}{%
25   \only#1{%
26     \beameroriginal{\abstract}%
27   }%
28 }
29
30 \renewcommand<>{\LWR@includegraphicsb}{%
31   \only#1{%
32     \beameroriginal{\LWR@includegraphicsb}%
33   }%
34 }
35
36 \xpretocmd\frame
37   {
38     \LWR@forcenewpage
39     \BlockClass{beamerframe}%
40   }
41   {}
42   {\LWR@patcherror{beamerarticle}{frame}}
43
44 \xapptocmd\beamer@endframe
45   {\endBlockClass}
46   {}
47   {\LWR@patcherror{beamerarticle}{beamer@endframe}}
48
49 % An example in the beamer docs for \cs{includegraphics}
50 % shows the use of \cs{llap} in a frame.
51 \xpretocmd\beamer@article@startframe
52   {\LWR@nulllistfills}
53   {}
54   {\LWR@patcherror{beamerarticle}{beamer@article@startframe}}
55
56 }% AtBeginDocument
57
58 \let\beamer@atmpop@frametitle@default\relax
59 \defbeamer@template<article>*{frametitle}{default}{%
60   \paragraph*{\insertframetitle}\ \par%
61   \ifdefempty{\insertframesubtitle}{%
62     \noindent\emph{\insertframesubtitle}\par%
63   }%
64 }
65
66
67 \NewDocumentCommand{\LWR@beamer@itemize}{o}{%
68   \LWR@itemizestart\LWR@origitemize%
69 }%
70 \NewDocumentCommand{\LWR@beamer@description}{o o}{%
71   \LWR@descriptionstart\LWR@origdescription%
72 }%
73
74 \xapptocmd{\LWR@patchlists}
75   {%

```

```

76     \LetLtxMacro\itemize\LWR@beamer@itemize%
77     \LetLtxMacro\description\LWR@beamer@description%
78   }
79   {}
80   {\LWR@patcherror{beamerarticle}{LWR@patchlists}}
81
82
83 \LetLtxMacro\maketitle\LWR@maketitle
84
85 \renewcommand{\subtitle}[2][{}]{
86   \gdef\@subtitle{#2}
87   \def\insertsubtitle{#2}
88 }
89
90 \xpatchcmd{\@maketitle}
91   {%
92     \LWR@htmltag{\LWR@tagtitleend}%
93     \LWR@startpars%
94   }%
95   {%
96     \LWR@htmltag{\LWR@tagtitleend}%
97     \ifdefvoid{\@subtitle}{}%
98     \begin{BlockClass}{subtitle}%
99     \@subtitle%
100    \end{BlockClass}%
101   }%
102   \LWR@startpars%
103 }%
104 {}
105 {\LWR@patcherror{beamerarticle}{\@maketitle}}
106
107 \RequirePackage{fancyvrb}
108 \DefineVerbatimEnvironment{semiverbatim}{Verbatim}{commandchars=\\\{\}}

```

File 45 **lwarp-biblatex.sty**

§ 154 Package **biblatex**

(Emulates or patches code by PHILIPP LEHMAN.)

Pkg biblatex

When biblatex is used, modifications from newfloat may have to be undone.

for HTML output:

1. lwarp uses newfloat.
2. For classes with chapters which newfloat does not know about, such as CTEX-related classes, newfloat may modify \addtocontents.
3. biblatex, though, wants to patch \addtocontents, which causes an error if \addtocontents has been changed.
4. Therefore, \addtocontents is restored to its original here, since biblatex is about to be loaded.
5. This means that the newfloat's chapterlistsgaps option may no longer work.

```
1 \ifdef{\newfloat@addtocontents@ORI}{
```

```

2 \let\addtocontents\newfloat\addtocontents@ORI
3 {}

```

hyperref emulation is loaded \AtBeginDocument to avoid an options clash.

```

4 \AtBeginDocument{\RequirePackage{hyperref}}
5
6 \LWR@ProvidesPackagePass{biblatex}[2018/03/04]

```

The following create hyperlinks to the references. The original code to use hyperref is recreated here, because hyperref is emulated.

```

7 \AfterPreamble{
8
9 \let\blx@anchors\@empty
10 \protected\def\blx@anchor{%
11   \xifinlist{\the\c@refsection @\abx@field@entrykey}{\blx@anchors}
12   {}
13   {\listadd\blx@anchors{\the\c@refsection @\abx@field@entrykey}%
14     \hypertarget{cite.\the\c@refsection @\abx@field@entrykey}{}}}
15
16 \protected\def\blx@imc@bibhyperref{%
17   \@ifnextchar[%
18     {\blx@bibhyperref}
19     {\blx@bibhyperref[\abx@field@entrykey]}}%
20
21 \long\def\blx@bibhyperref[#1]#2{%
22 %   \blx@sfsave
23 %   \hyperlink{cite.\the\c@refsection @#1}{%
24 %     \blx@sfrst
25 %     #2%
26 %     \blx@sfsave
27 %   }%
28 % \blx@sfrst%
29 }%% \def\blx@nohyperref[#1]#2{#2}%
30
31 \protected\long\def\blx@imc@bibhyperlink#1#2{%
32 %   \blx@sfsave
33 %   \hyperlink{cite.\the\c@refsection:#1}{%
34 %     \blx@sfrst
35 %     #2%
36 %     \blx@sfsave
37 %   }%
38 %   \blx@sfrst%
39 }%%
40
41 \protected\long\def\blx@imc@bibhypertarget#1#2{%
42 %   \blx@sfsave%
43 %   \hypertarget{cite.\the\c@refsection:#1}{%
44 %     \blx@sfrst
45 %     #2%
46 %     \blx@sfsave%
47 %   }%
48 %   \blx@sfrst%
49 }
50
51 \let\blx@imc@ifhyperref\@firstoftwo

```

Ensure that an autopage reference is current where each `\cite` is used, although this is nullified inside footnotes since they now use a L^AT_EX box.

```
52 \xpretocmd{\blx@citecmdinit}
53   {\LWR@newautopagelabel{page}}%
54   {}
55   {\LWR@patcherror{biblatex}{blx@citecmdinit}}
```

Ensure that an autopage reference is current for each backref. If the citation is in a footnote, the backref will point to whatever preceded the footnotes.

```
56 \xpatchcmd{\blx@addbackref@i}
57   {\thepage}
58   {\theLWR@previousautopagelabel}% ref to the most recent object
59   {}
60   {\LWR@patcherror{biblatex}{blx@addbackref@i A}}
61
62 \xpatchcmd{\blx@addbackref@i}
63   {\c@page}
64   {\c@LWR@previousautopagelabel}% ref to the most recent object
65   {}
66   {\LWR@patcherror{biblatex}{blx@addbackref@i B}}
```

The following patches are for back page references.

```
67 \DeclareListFormat{pageref}{%
68   \ifnumless{\abx@pagerefstyle}{0}
69     {\usebibmacro{list:plain}%
70       \ifhyperref
71         {%
72           \hyperlink{page.#1}{#1}%
73           \LWR@refwithsection{\BaseJobname-autopage-#1}% lwarp
74         }
75       {#1}}
76   {\ifnumequal{\value{listcount}}{1}
77     {\usebibmacro{pageref:init}}
78     {}%
79     \usebibmacro{pageref:comp}{#1}%
80     \ifnumequal{\value{listcount}}{\value{liststop}}
81       {\usebibmacro{pageref:dump}}
82       {}}}
83
84 \renewbibmacro*{pageref:comp}[1]{%
85   \numdef\abx@range@prev{\abx@range@prev+1}%
86   \ifinteger{#1}
87     {\def\abx@range@num{#1}%
88       \def\abx@range@this{1}%
89       \ifnumequal{\abx@range@this}{\abx@range@last}
90         {}
91         {\def\abx@range@prev{-1}}}
92     {\ifrmnum{#1}
93       {\numdef\abx@range@num{\rmntonum{#1}}%
94         \def\abx@range@this{2}%
95         \ifnumequal{\abx@range@this}{\abx@range@last}
96           {}
97           {\def\abx@range@prev{-1}}}
98       {\undef\abx@range@num
99         \def\abx@range@this{0}%
100        \def\abx@range@prev{-1}}}%
```

```

101 \ifdef\abx@range@num
102   {\ifnumequal{\abx@range@num}{\abx@range@prev}
103     {\def\abx@range@hold{#1}%
104       \numdef\abx@range@diff{\abx@range@diff+1}}
105     {\usebibmacro{pageref:dump}%
106       \ifnumgreater{\abx@range@last}{-1}
107         {\printdelim{multilistdelim}}
108         {}}%
109     \ifhyperref
110 %       {\hyperlink{page.#1}{#1}}
111       {\LWR@refwithsection{\BaseJobname-autopage-#1}}% lwarp
112       {#1}}%
113   \edef\abx@range@prev{\abx@range@num}}
114 {\usebibmacro{pageref:dump}%
115   \ifnumgreater{\abx@range@last}{-1}
116     {\printdelim{multilistdelim}}
117     {}}%
118   \ifhyperref
119 %     {\hyperlink{page.#1}{#1}}
120     {\LWR@refwithsection{\BaseJobname-autopage-#1}}% lwarp
121     {#1}}%
122   \def\abx@range@prev{-1}}%
123 \edef\abx@range@last{\abx@range@this}}
124
125 \renewbibmacro*{pageref:dump}{%
126   \ifnumgreater{\abx@range@diff}{0}
127     {\ifcase\abx@pagerefstyle\relax % two
128       \bibrangedash
129       \ifhyperref
130 %         {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
131         {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
132         {\abx@range@hold}%
133       \or % three
134         \ifnumless{\abx@range@diff}{2}
135           {\printdelim{multilistdelim}}
136           {\bibrangedash}%
137         \ifhyperref
138 %           {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
139           {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
140           {\abx@range@hold}%
141       \or % two+
142         \ifnumless{\abx@range@diff}{2}
143           {\sqspace
144           \ifhyperref
145 %             {\hyperlink{page.\abx@range@hold}{\bibstring{sequens}}}}
146             {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
147             {\bibstring{sequens}}}}
148         {\bibrangedash
149         \ifhyperref
150 %           {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
151           {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
152           {\abx@range@hold}}%
153       \or % three+
154         \ifnumless{\abx@range@diff}{2}
155           {\sqspace
156           \ifhyperref
157 %             {\hyperlink{page.\abx@range@hold}{\bibstring{sequens}}}}
158             {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
159             {\bibstring{sequens}}}}
160         {\ifnumless{\abx@range@diff}{3}

```

```

161         {\sqspace
162         \ifhyperref
163 %         {\hyperlink{page.\abx@range@hold}{\bibstring{sequentes}}}
164         {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
165         {\bibstring{sequentes}}}
166         {\bibrangedash
167         \ifhyperref
168 %         {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
169         {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
170         {\abx@range@hold}}}%
171 \else % all+
172 \ifnumless{\abx@range@diff}{2}
173     {\sqspace
174     \ifhyperref
175 %     {\hyperlink{page.\abx@range@hold}{\bibstring{sequens}}}
176     {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
177     {\bibstring{sequens}}}
178     {\sqspace
179     \ifhyperref
180 %     {\hyperlink{page.\abx@range@hold}{\bibstring{sequentes}}}
181     {\LWR@refwithsection{\BaseJobname-autopage-\abx@range@hold}}% lwarp
182     {\bibstring{sequentes}}}%
183 \fi
184 \def\abx@range@diff{0}}
185 {}
186
187 }% \AfterPreamble

```

File 46 **lwarp-bibunits.sty**

§ 155 Package **bibunits**

(Emulates or patches code by THORSTEN HANSEN.)

Pkg bibunits

bibunits is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{bibunits}[2004/05/12]

2 \def\bu@bibdata{\BaseJobname}

```

File 47 **lwarp-bigdelim.sty**

§ 156 Package **bigdelim**

(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)

Pkg bigdelim

bigdelim is used as-is for print or lateximage, and patched for HTML.

The delimiters are displayed in HTML by printing the delimiter, the text, and a thick border across the side of the `\multirow` which indicates the actual height of the delimiter. The delimiter character is given a `` class of `ldelim` or `rdelim`, and the default css sets this to `font-size:200%`

⚠ use `\mrowcell` `\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper

number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

```

\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}

```

```

<->   a   b
      {
left  { c   d
      { e   f
      { g   h
<->   i   j

```

For MATHJAX, limited emulation is provided which merely prints the delimiter and optional text in the first row.

for HTML output: First, remove the temporary definitions of `\ldelim` and `\rdelim`, which were previously defined for tabular scanning in case `bigdelim` was not loaded:

```

1 \let\ldelim\relax
2 \let\rdelim\relax

```

Next, load the package's new definitions:

```

3 \LWR@ProvidesPackagePass{bigdelim}[2021/03/15]

\ldelim  {\langle 1:delimiter \rangle} {\langle 2:#rows \rangle} [\langle 3: vmove \rangle] {\langle 4:width \rangle} [\langle 5:text \rangle]
\rdelim

4 \NewDocumentCommand{\LWR@HTML@ldelim}{m m o m O{}}{%
5 \renewcommand{\LWR@multirowborder}{right}%
6 \multirow{#2}{#4}{#5 \InlineClass{ldelim}{#1}}%
7 }
8
9 \LWR@formatted{ldelim}
10
11 \NewDocumentCommand{\LWR@HTML@rdelim}{m m o m O{}}{%
12 \renewcommand{\LWR@multirowborder}{left}%
13 \multirow{#2}{#4}{\InlineClass{rdelim}{#1} #5}%
14 }
15
16 \LWR@formatted{rdelim}

```

Limited emulation for MATHJAX. The delimiter is printed on the first row, along with any optional text.

```

17 \begin{warpMathJax}
18 % \ldelim ( {n}{width}[text]
19 \CustomizeMathJax{\newcommand{\LWRldelimtwo}[1][]{\text{#1}~\LWRbigdelim}}
20 \CustomizeMathJax{\newcommand{\LWRldelimone}[2][]{\LWRldelimtwo}}
21 \CustomizeMathJax{\def\ldelim#1#2{\def\LWRbigdelim{#1}\LWRldelimone}}
22 % \rdelim ) {n}{width}[text]
23 \CustomizeMathJax{\newcommand{\LWRrdelimtwo}[1][]{\LWRbigdelim~\text{#1}}}

```

```

24 \CustomizeMathJax{\newcommand{\LWRrdelimone}[2][\LWRrdelimitwo]}
25 \CustomizeMathJax{\def\rdelim#1#2{\def\LWRbigdelim{#1}\LWRrdelimone}}
26 \end{warpMathJax}

```

File 48 **lwarp-bigfoot.sty**

§ 157 Package **bigfoot**

Pkg bigfoot bigfoot is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{bigfoot}[2015/08/30]

2 \RequirePackage{manyfoot}
3 \RequirePackage{perpage}
4
5 \def\RestyleFootnote#1#2{}
6 \def\FootnoteSpecific#1{}
7 \def\DefineFootnoteStack#1{}
8 \def\PushFootnoteMark#1{}
9 \def\PopFootnoteMark#1{}
10 \def\hfootfraction{0.9}
11 \def\vtypefraction{0.7}
12 \def\FootnoteMinimum{1sp}
13 \def\FootnoteMainMinimum{0pt}
14 \newcount\bigfoottolerance
15 \bigfoottolerance=100
16 \providecommand\footnotecarryratio{2}

```

File 49 **lwarp-bigstrut.sty**

§ 158 Package **bigstrut**

(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)

Pkg bigstrut bigstrut is used as-is for print or lateximage, and patched for HTML.

for HTML output:

```

1 \LWR@ProvidesPackagePass{bigstrut}[2018/08/03]

2 \LetLtxMacro\LWR@origbigstrut\bigstrut
3
4 \renewcommand\bigstrut[1][x]{}
5
6 \appto\LWR@restoreorigformatting{%
7 \LetLtxMacro\bigstrut\LWR@origbigstrut%
8 }
9

10 \begin{warpMathJax}
11 \CustomizeMathJax{\newcommand{\bigstrut}[1][x]{} }
12 \end{warpMathJax}

```

File 50 **lwarp-bitpattern.sty**

§ 159 Package **bitpattern**

(Emulates or patches code by JEAN-MARC BOURGUET.)

Pkg bitpattern bitpattern is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{bitpattern}[2015/12/11]
2 \xpatchcmd{\bitpattern}
3   {\begingroup}
4   {\begin{lateximage}[-bitpattern~\PackageDiagramAltText]}
5   {}
6   {\LWR@patcherror{bitpattern}{bitpattern}}
7
8 \xpatchcmd{\bp@Done}
9   {\endgroup}
10  {\end{lateximage}}
11  {}
12  {\LWR@patcherror{bitpattern}{bp@Done}}
```

File 51 **lwarp-blowup.sty**

§ 160 Package **blowup**

Pkg blowup blowup is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{blowup}[2018/01/02]
2 \newcommand*\blowUp[1]{}

```

File 52 **lwarp-bm.sty**

§ 161 Package **bm**

(Emulates or patches code by DAVID CARLISLE, FRANK MITTELBACH.)

Pkg bm bm is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{bm}[2019/07/24]

\DeclareBoldMathCommand must only be used in the preamble, since it adds to
the MATHJAX setup code.

2 \begin{warpMathJax}
3 \LetLtxMacro\LWR@orig@DeclareBoldMathCommand\DeclareBoldMathCommand
4
5 \renewcommand\DeclareBoldMathCommand[3][bold]{%
```

```

6   \LWR@orig@DeclareBoldMathCommand[#1]{#2}{#3}%
7   \CustomizeMathJax{\newcommand{#2}{\boldsymbol{#3}}}%
8 }
9
10 \onlypreamble\DeclareBoldMathCommand
11
12 \CustomizeMathJax{\newcommand{\bm}[1]{\boldsymbol{#1}}}
13 \end{warpMathJax}

```

File 53 **lwarp-booklet.sty**

§ 162 Package **booklet**

(Emulates or patches code by PETER WILSON.)

Pkg booklet

booklet is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{booklet}[2009/09/02]
2 \newdimen\pageseplength
3 \newdimen\pagesepwidth
4 \newdimen\pagesepoffset
5 \newif\ifsidebyside \sidebysidetrue
6 \newif\ifuselandscape \uselandscapefalse
7 \newif\ifprintoption \printoptionfalse
8 \newcommand*{\pagespersignature}[1]{}
9 \def\magstepminus#1{}
10 \newcommand*{\target}[3]{}
11 \newcommand*{\source}[3]{}
12 \newcommand*{\setpdftargetpages}{}
13 \newcommand*{\setdvipstargetpages}{}
14 \newcommand*{\targettopbottom}{}
15 \newcommand*{\twoupemptypage}{}
16 \newcommand*{\twoupclearpage}{}
17 \newcommand*{\checkforlandscape}{}

```

File 54 **lwarp-bookmark.sty**

§ 163 Package **bookmark**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg bookmark

bookmark is ignored.

for HTML output: Discard all options for lwarp-bookmark:

```

1 \LWR@ProvidesPackageDrop{bookmark}[2016/05/17]
2 \newcommand*{\bookmarksetup}[1]{}
3 \newcommand*{\bookmarksetupnext}[1]{}
4 \newcommand*{\bookmark}[2][{}]{ }
5 \newcommand*{\bookmarkdefinestyle}[2]{}
6 \newcommand*{\bookmarkget}[1]{}
7 \newcommand{\BookmarkAtEnd}[1]{}

```

File 55 **lwarp-booktabs.sty**

§ 164 Package **booktabs**

(Emulates or patches code by SIMON FEAR.)

Pkg booktabs

booktabs is emulated during HTML output, and used as-is during print output and inside an HTML `lateximage`.

△ `\cmidrule` For MATHJAX, emulation is provided in math mode, but `\cmidrule trim` must not be used.

for HTML output: If **booktabs** has already been loaded before **lwarp**, such as by **memoir**, use it as-is. If not, the **lwarp** core will have placed some dummy macros which should be removed before loading the actual **booktabs** definitions.

```

1 \IfPackageLoadedTF{booktabs}{}{
2   \LetLtxMacro\toprule\relax
3   \LetLtxMacro\midrule\relax
4   \LetLtxMacro\cmidrule\cline
5   \LetLtxMacro\bottomrule\relax
6   \LetLtxMacro\addlinespace\relax
7   \LetLtxMacro\morecmidrules\relax
8   \LetLtxMacro\specialrule\relax
9 }

```

Next, load the **booktabs** package:

```
10 \LWR@ProvidesPackagePass{booktabs}[2019/10/08]
```

Adjust to work even if **xltabular** is loaded:

```

11 % \def\LWR@HTML@BLTrule{\@BTnormal}
12 %
13 % \LWR@formatted{@BLTrule}
14 \LetLtxMacro\@BLTrule\@BTnormal

15 \DeclareDocumentCommand{\LWR@HTML@toprule}{o d()}%
16   {%
17     \IfValueTF{#1}%
18       {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
19     {%
20       \ifbool{FormatWP}%
21         {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
22       {\booltrue{LWR@doingtbrule}}}%
23   }%
24   \LWR@getmynexttoken}
25
26 \LWR@expandableformatted{toprule}
27
28 \DeclareDocumentCommand{\LWR@HTML@midrule}{o d()}%
29   {%
30     \IfValueTF{#1}%
31       {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
32     {%

```

```

33         \ifbool{FormatWP}%
34         {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
35         {\defaddtocounter{LWR@hlines}{1}}}%
36     }%
37     \LWR@getmynexttoken}
38
39 \LWR@expandableformatted{midrule}
40
41 \DeclareDocumentCommand{\LWR@HTML@cmidrule}{0{\LWR@cmidrulewidth} d() m}{%
42     \LWR@docmidrule[#1](#2){#3}%
43     \LWR@getmynexttoken%
44 }%
45
46 \LWR@expandableformatted{cmidrule}
47
48 \DeclareDocumentCommand{\LWR@HTML@bottomrule}{o d()}{%
49     \IfValueTF{#1}%
50     {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
51     {%
52         \ifbool{FormatWP}%
53         {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
54         {\booltrue{LWR@doingtbrule}}}%
55     }%
56     \LWR@getmynexttoken%
57 }%
58
59 \LWR@expandableformatted{bottomrule}
60
61 \DeclareDocumentCommand{\LWR@HTML@addlinespace}{o}{}%
62
63 \LWR@expandableformatted{addlinespace}
64
65 \DeclareDocumentCommand{\LWR@HTML@morecmidrules}{}{}%
66
67 \LWR@expandableformatted{morecmidrules}
68
69 \DeclareDocumentCommand{\LWR@HTML@specialrule}{m m m d()}{%
70     {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}\LWR@getmynexttoken}%
71
72 \LWR@expandableformatted{specialrule}

```

For MATHJAX:

```

73 \begin{warpMathJax}
74 \CustomizeMathJax{\newcommand{\toprule}[1][\hline]}
75 \CustomizeMathJax{\let\midrule\toprule}
76 \CustomizeMathJax{\let\bottomrule\toprule}
77 \CustomizeMathJax{\def\LWRbooktabscmidruleparen(#1)#2{}}
78 \CustomizeMathJax{\newcommand{\LWRbooktabscmidrulenoparen}[1]}
79 \CustomizeMathJax{\newcommand{\cmidrule}[1]}%
80     \ifnextchar(\LWRbooktabscmidruleparen\LWRbooktabscmidrulenoparen%
81 }}
82 \CustomizeMathJax{\newcommand{\morecmidrules}{}}
83 \CustomizeMathJax{\newcommand{\specialrule}[3]{\hline}}
84 \CustomizeMathJax{\newcommand{\addlinespace}[1]}
85 \end{warpMathJax}

```

File 56 **lwarp-bophook.sty**

§ 165 Package **bophook**

Pkg bophook

bophook is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{bophook}[2001/03/29]

2 \newcommand*\AtBeginPage}[1]{}

3 \newcommand*\PageLayout}[1]{}

File 57 **lwarp-bounddvi.sty**

§ 166 Package **bounddvi**

Pkg bounddvi

bounddvi is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{bounddvi}[2016/12/28]

File 58 **lwarp-boxedminipage.sty**

§ 167 Package **boxedminipage**

Pkg boxedminipage

(Emulates or patches code by SCOTT PAKIN.)

boxedminipage is emulated for HTML, and used as-is for lateximages.

for HTML output: 1 \LWR@ProvidesPackagePass{boxedminipage}[2020/04/19]

2 \newenvironment{LWR@HTML@boxedminipage}{%

3 \LWR@stoppars%

4 \begin{BlockClass}{framebox}%

5 \minipage%

6 }

7 {%

8 \endminipage%

9 \end{BlockClass}%

10 \LWR@startpars%

11 }

12 \LWR@Formattedenv{boxedminipage}

File 59 **lwarp-boxedminipage2e.sty**

§ 168 Package **boxedminipage2e**

(Emulates or patches code by SCOTT PAKIN.)

Pkg boxedminipage2e boxedminipage2e has been renamed boxedminipage by the author.

for HTML output: Automatically loads boxedminipage:

```
1 \LWR@ProvidesPackagePass{boxedminipage2e}
```

File 60 **lwarp-braket.sty**

§ 169 Package **braket**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg braket braket works as-is for HTML with SVG math. For MATHJAX, the MATHJAX extension is used.

for HTML output: 1 \LWR@ProvidesPackagePass{braket}% No date is provided by the file.

```
2 \begin{warpMathJax}
3   \CustomizeMathJax{\require{braket}}
4 \end{warpMathJax}
```

File 61 **lwarp-breakurl.sty**

§ 170 Package **breakurl**

(Emulates or patches code by VILAR CAMARA NETO.)

Pkg breakurl breakurl is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{breakurl}[2013/04/10]

```
2 \LetLtxMacro\url\LWR@url
3
4 \NewDocumentCommand{\LWR@urlaltb}{O{} +m m}{%
5   \LWR@ensuredoingapar%
6   \LWR@subhyperref{#2}%
7   \LWR@subhyperrefreftext{#3}%
8   \endgroup% restore catcodes
9 }
10
11 \newrobustcmd*{\urlalt}{%
12   \begingroup%
13   \LWR@linkcatcodes%
14   \LWR@urlaltb%
15 }
16
17 \LetLtxMacro\urlalt\urlalt
```

File 62 **lwarp-breqn.sty**

§ 171 Package **breqn**

(Emulates or patches code by MICHAEL J. DOWNES, MORTEN HØGHOLM.)

Pkg breqn

breqn is patched for use by **lwarp**.

 **darray** **darray** is not supported, and in fact does not work in the print version either.

While using **MATHJAX**, **breqn** objects are converted to **svg** images.**for HTML output:**

```

1 \LWR@ProvidesPackagePass{breqn}[2017/01/27]

2 \setkeys{breqn}{spread={5pt}}
3
4 \def\eqnumside{R}
5 % \def\eqnumplace{T}
6
7 \BeforeBeginEnvironment{dmath}{
8   \begin{BlockClass}{displaymathnumbered}
9   \LWR@newautoidanchor%
10  \booltrue{LWR@indisplaymathimage}%
11  \begin{lateximage}[-breqn dmath- \MathImageAltText]
12 }
13
14 \AfterEndEnvironment{dmath}{
15   \end{lateximage}\end{BlockClass}
16 }
17
18 \BeforeBeginEnvironment{dmath*}{
19   \begin{BlockClass}{displaymath}
20   \LWR@newautoidanchor%
21   \booltrue{LWR@indisplaymathimage}%
22   \begin{lateximage}[-breqn dmath*- \MathImageAltText]
23 }
24
25 \AfterEndEnvironment{dmath*}{
26   \end{lateximage}\end{BlockClass}
27 }
28
29 \BeforeBeginEnvironment{dseries}{
30   \begin{BlockClass}{displaymathnumbered}
31   \LWR@newautoidanchor%
32   \booltrue{LWR@indisplaymathimage}%
33   \begin{lateximage}[-breqn dseries- \MathImageAltText]
34 }
35
36 \AfterEndEnvironment{dseries}{
37   \end{lateximage}\end{BlockClass}
38 }
39
40 \BeforeBeginEnvironment{dseries*}{
41   \begin{BlockClass}{displaymath}
42   \LWR@newautoidanchor%
43   \booltrue{LWR@indisplaymathimage}%
44   \begin{lateximage}[-breqn dseries*- \MathImageAltText]
45 }
46
47 \AfterEndEnvironment{dseries*}{
48   \end{lateximage}\end{BlockClass}
49 }
50
51 \BeforeBeginEnvironment{dgroup}{
52   \begin{BlockClass}{displaymath}
53   \LWR@newautoidanchor%
```

```

54 \booltrue{LWR@indisplaymathimage}%
55 \begin{lateximage}[-breqn dgroup- \MathImageAltText]
56 }
57
58 \AfterEndEnvironment{dgroup}{
59 \end{lateximage}\end{BlockClass}
60 }
61
62 \BeforeBeginEnvironment{dgroup*}{
63 \begin{BlockClass}{displaymath}
64 \LWR@newautoidanchor%
65 \booltrue{LWR@indisplaymathimage}%
66 \begin{lateximage}[-breqn dgroup*~ \MathImageAltText]
67 }
68
69 \AfterEndEnvironment{dgroup*}{
70 \end{lateximage}\end{BlockClass}
71 }

```

File 63 **lwarp-bsheaders.sty**

§ 172 Package **bsheaders**

Pkg bsheaders

bsheaders is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{bsheaders}[1997/10/06]

File 64 **lwarp-bussproofs.sty**

§ 173 Package **bussproofs**

(Emulates or patches code by SAMUEL R. BUSS.)

Pkg bussproofs

bussproofs is used as-is for HTML, and emulated by MATHJAX's extension.

 **\DisplayProof** If not using MATHJAX, inline proofs with `\DisplayMath` must be placed inside a math expression.

If using MATHJAX, only the `prooftree` environment may be used, not `\DisplayProof`.

for HTML output: 1 \LWR@ProvidesPackagePass{bussproofs}% no date in file

```

2 \ifbool{mathjax}{
3 \CustomizeMathJax{\require{bussproofs}}
4
5 \NewEnviron{LWR@HTML@prooftree}%
6 {\LWR@doequation{\BODY}{prooftree}}%
7 [\LWR@doendequation{prooftree}]
8 \LWR@formattedenv{prooftree}
9 }{% SVG HTML
10 \BeforeBeginEnvironment{prooftree}{%
11 \begin{lateximage}[-bussproofs~\PackageDiagramAltText]%
12 }
13 \AfterEndEnvironment{prooftree}{\end{lateximage}}
14 }

```

File 65 **lwarp-bxpapersize.sty**§ 174 Package **bxpapersize**Pkg `bxpapersize``bxpapersize` is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{bxpapersize}[2017/10/08]
2 \providecommand*\papersizesetup{\bxpapersizesetup}
3 \newcommand*\bxpapersizesetup[1]{}
```

File 66 **lwarp-bytefield.sty**§ 175 Package **bytefield**Pkg `bytefield`*(Emulates or patches code by SCOTT PAKIN.)*`bytefield` is patched for use by `lwarp`.

for HTML output:

```
1 \LWR@ProvidesPackagePass{bytefield}[2017/09/15]
2 \BeforeBeginEnvironment{bytefield}{%
3   \begin{lateximage}[-bytefield-~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{bytefield}{\end{lateximage}}
```

File 67 **lwarp-cancel.sty**§ 176 Package **cancel**Pkg `cancel``cancel` is used as-is for SVG math, and emulated for HTML text output.

for HTML output:

```
1 \LWR@origRequirePackage{lwarp-xcolor}% for \convertcolorspec
2 \LWR@ProvidesPackagePass{cancel}[2013/04/12]
```

`\cancel` to is math-only, so is used as-is.`\LWR@cancelcolor` $\langle text \rangle \langle color \rangle \langle class \rangle \langle colorstyle \rangle \langle FormatWPstyle \rangle$

Add colors if not empty:

```
3 \newcommand{\LWR@cancelcolor}[5]{%
4   \ifcempty{#2}%
5   {\InlineClass{#5}{#3}{#1}}%
6   {\LWRhtmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}%
7 }
```

`\cancel`

```

{<text>}

8 \DeclareRobustCommand{\LWR@HTML@cancel}[1]{%
9 \begingroup%
10 \CancelColor%
11 \LWR@findcurrenttextcolor%
12 \color{black}%
13 \LWR@cancelcolor{#1}{LWR@tempcolor}{sout}{text-decoration-color}%
14   {text-decoration:line-through}%
15 \endgroup%
16 }
17 \LWR@formatted{cancel}%
18
19 \LetLtxMacro\bcancel\cancel
20 \LetLtxMacro\xcancel\cancel

```

For MATHJAX:

```

21 \begin{warpMathJax}
22 \PackageNoteNoLine{lwarp, cancel}{The MathJax v3 extension will be used}
23 \CustomizeMathJax{\require{cancel}}
24 \end{warpMathJax}

```

File 68 **lwarp-canonlayout.sty**§ 177 Package **canoniclayout**

Pkg canoniclayout

canoniclayout is ignored.

for HTML output: s1 \LWR@ProvidesPackageDrop{canoniclayout}[2011/11/05]

```

2 \newcommand*{\currentfontletters}{}
3 \newcommand*{\charactersperpage}{}

```

File 69 **lwarp-caption.sty**§ 178 Package **caption**

Pkg caption

(Emulates or patches code by AXEL SOMMERFELDT.)

caption is patched for use by lwarp.

for HTML output:

```

1 \typeout{---}
2 \typeout{Packages lwarp and caption:}
3 \typeout{If a ‘Missing \protect\begin\protect{document\protect}’ error occurs here,}
4 \typeout{try using: \space \protect\usepackage\protect{caption\protect}\space%
5   \protect\captionsetup{options}}
6 \typeout{instead of: \protect\usepackage[options]\protect{caption\protect}.}
7 \typeout{---}
8
9 \LWR@ProvidesPackagePass{caption}[2020/10/26]

```

10 \long\def\caption@iibox@#1#2#3#4{%

```

11 % \setbox\@tempboxa\hbox{#4}%
12 \caption@iiibox{#1}{#2}{#3}%
13 % [\wd\@tempboxa]%
14 []% lwarp
15 [\captionbox@hj@default]%
16 % {\unhbox\@tempboxa}%
17 {{#4}}% lwarp
18 }

19 \long\def\caption@iiibox#1#2#3#4#5[#6][#7]#8{%
20 \begingroup
21 #1*% set \caption@position
22 \caption@iftop{%
23 \endgroup

24 \minipagefullwidth% lwarp
25 \parbox[t]{\linewidth}{%
26 #1\relax
27 \caption@setposition t%
28 % #2%
29 {\caption#4{#5}}%
30 % \captionbox@hrule
31 % \csname caption@hj@#7\endcsname
32 #8%
33 }%
34 }{%
35 \endgroup

36 % \parbox[b]{#6}{%
37 \minipagefullwidth% lwarp
38 \parbox[b]{\linewidth}{% lwarp
39 #1\relax
40 \caption@setposition b%
41 % \csname caption@hj@#7\endcsname
42 #8%
43 % \captionbox@hrule
44 % #3
45 {\caption#4{#5}}%
46 }%
47 }%
48 }

```

\caption@makecaption

```

49 \long\def\caption@makecaption#1#2{%
50 % \caption@make@above
51 \caption@make{#1}{#2}%
52 % \caption@make@below
53 }
54
55 \AtBeginDocument{
56 \let\@makecaption\caption@makecaption
57 }

```

Appended to look ahead to the next token for \centering, etc:

```

58 \AtBeginDocument{
59 \xapptocmd{\@xfloat}
60 {\LWR@futurenonspaceset\LWR@mynexttoken\LWR@floatalignment}

```

```

61  {}
62  {\LWR@patcherror{caption}{@xfloat}}
63
64  \xapptocmd{\@xdblfloat}
65  {\LWR@futurenonospacelet\LWR@mynexttoken\LWR@floatalignment}
66  {}
67  {\LWR@patcherror{caption}{@xdblfloat}}
68  }

69  \long\def\caption@@@text#1#2#3[#4]#5{%
70    \begin{BlockClass}{figurecaption}%      lwarp
71    \begingroup
72    #3{\csname c@#1\endcsname #4\relax}%
73    #2{\caption@fnum{#1}}{#5}%
74    \endgroup%
75    \end{BlockClass}%                      lwarp
76  }

```

Updates for late patches for scrextend:

```

77  \caption@AtBeginDocument{
78  \IfPackageLoadedTF{lwarp-scrextend}{
79    \LetLtxMacro\captionbelow\caption
80    \LetLtxMacro\captionabove\caption
81    \LetLtxMacro\captionofbelow\captionof
82    \LetLtxMacro\captionofabove\captionof
83  }{}
84  }

```

File 70 **lwarp-caption3.sty**

§ 179 Package **caption3**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg caption3

caption3 is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{caption3}[2020/10/21]

\caption@@@make

```

{\caption label} {\caption text}

2 \IfPackageAtLeastTF{caption3}{2020/08/23}{
3 \renewcommand\caption@@@make[2]{%
4 \LWR@traceinfo{caption@@@make}%

5   \LWR@stoppars%                          lwarp

6 %   \sbox\@tempboxa{#1}%
7 %   \ifdim\wd\@tempboxa=\z@
8 %     \caption@set{labelseparator}{none}%
9 %   \fi
10  \caption@ifempty{#2}{%
11    \caption@set{labelseparator}{none}%
12    \caption@set{textformat}{simple}%
13  }%
14  \caption@labelseparator % defines \caption@iflabelfont,

```

```

15 %      \caption@labelsep and \caption@labelsep@name
16 %      (the latter is needed by \caption@fmt)
17 %

```

```

18 % \setpar{\@@par\caption@@par}\caption@@par
19 \caption@applyfont

```

\caption@fmt with plain format is defined as {#1#2#3\par}:

```

20 % \caption@fmt
21 {\ifcaption@star\else
22   \begingroup
23   \caption@labelfont
24   \LWR@isolate{#1}%          lwarp
25   \endgroup
26   \fi}%
27 {\ifcaption@star\else
28   \begingroup
29   \caption@iflabelfont\caption@labelfont
30   \relax\caption@labelsep
31   \endgroup
32   \fi}%
33 {{\caption@textfont
34   \let\\newLine%          lwarp
35 %
36   \caption@textstart
37 %
38 %   \caption@ifstrut
39 %   {\vrule\@height\ht\strutbox\@width\z@}%
40 %   {}}%
41 %   \nobreak\hskip\z@skip % enable hyphenation
42 %
43 % \LWR@isolate{\caption@textformat{#2}}%   lwarp
44 %
45 %   \caption@ifstrut
46 %   {\ifhmode\@finalstrut\strutbox\fi}%
47 %   {}}%
48 %   \caption@textend}}%
49 %
50 % \LWR@startpars%          lwarp
51 % \LWR@traceinfo{caption@@@make done}%
52 % }
53 % }% later than 2020/08/23
54 % {% earlier than 2020/08/23
55 % \renewcommand\caption@@@make[2]{%
56 % \LWR@traceinfo{caption@@@make}%
57 % \LWR@stoppars%          lwarp
58 % \sbox\@tempboxa{#1}%
59 % \ifdim\wd\@tempboxa=\z@
60 %   \let\caption@lsep\relax
61 %   \fi
62 % \caption@ifempty{#2}{%
63 %   \let\caption@lsep\empty
64 %   \let\caption@tfmt\@firstofone
65 % }%
66 % \setpar{\@@par\caption@@par}\caption@@par
67 % \caption@applyfont

```

\caption@fmt with plain format is defined as {#1#2#3\par}:

```

64 % \caption@fmt

```

```

65   {\ifcaption@star\else
66     \begingroup
67       \captionlabelfont
68       \LWR@isolate{#1}%           lwarp
69     \endgroup
70   \fi}%
71   {\ifcaption@star\else
72     \begingroup
73       \caption@iflfl\captionlabelfont
74       \relax
75       \caption@lsep
76     \endgroup
77   \fi}%
78   {%
79     \captiontextfont
80     \let\\\newLine%           lwarp
81   % \caption@ifstrut
82   %   {\vrule\@height\ht\strutbox\@width\z@}%
83   %   {}%
84   % \nobreak\hskip\z@skip % enable hyphenation
85   % \LWR@isolate{\caption@tfmt{#2}}%   lwarp
86   % \caption@ifstrut
87   %   {\ifhmode\@finalstrut\strutbox\fi}%
88   %   {}%
89   %}%
90   \LWR@startpars%           lwarp
91 \LWR@traceinfo{caption@@@make done}%
92 }
93 }% earlier than 2020/08/23

```

\caption@@make@

```

{\langle} {\langle}
94 \renewcommand{\caption@@make@[2]{%
95   \caption@stepthecounter%
96   \caption@beginhook%
97 %   \caption@box\hsize{%
98 %   \caption@singlelinecheck{\caption@slc{#1}{#2}\caption@singleline\caption@multiline}{\caption@
99 %   \caption@calcmargin
100 %   \caption@make@leftmargin
101 %   \caption@make@parbox{%
102 %   \caption@make@indentation
103   \caption@@@make{#1}{#2}%
104 %   }
105 %   \caption@make@rightmargin
106 %   }%
107   \caption@endhook%
108 }

109 \DeclareCaptionBox{none}{#2}
110 \DeclareCaptionBox{parbox}{%
111   #2%
112 }

113 \DeclareCaptionBox{colorbox}{%
114   #2%
115 }

```

File 71 **lwarp-cases.sty**§ 180 Package **cases**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg cases

cases is patched for use by **lwarp**.

While using **MATHJAX**, **cases** objects are converted to **svg** math images. The **MathJax 3.2 cases** package does not yet work with **lwarp**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{cases}[2020/03/29]

2 \BeforeBeginEnvironment{numcases}{
3   \begin{BlockClass}{displaymathnumbered}
4   \LWR@newautoidanchor%
5   \booltrue{LWR@indisplaymathimage}%
6   \begin{lateximage}[-cases- \MathImageAltText]
7 }
8
9 \AfterEndEnvironment{numcases}{
10  \end{lateximage}\end{BlockClass}
11 }
12
13 \BeforeBeginEnvironment{subnumcases}{
14   \begin{BlockClass}{displaymathnumbered}
15   \LWR@newautoidanchor%
16   \booltrue{LWR@indisplaymathimage}%
17   \begin{lateximage}[-cases- \MathImageAltText]
18 }
19
20 \AfterEndEnvironment{subnumcases}{
21   \end{lateximage}\end{BlockClass}
22 }

```

File 72 **lwarp-ccicons.sty**§ 181 Package **ccicons**

(Emulates or patches code by MICHAEL UMMELS.)

Pkg ccicons

ccicons is used as **svg** images for **HTML**.

for HTML output:

Discard all options for **lwarp-ccicons**:

```

1 \LWR@ProvidesPackagePass{ccicons}[2017/10/30]

2 \newcommand{\LWR@ccicons}[2]{%
3   {\begin{lateximage}*[#1]\ccicons@font\char#2\end{lateximage}}
4 }
5 \renewcommand{\ccicons@logo}{\LWR@ccicons{ccLogo}{0}}
6 \renewcommand{\ccicons@by}{\LWR@ccicons{ccAttribution}{1}}
7 \renewcommand{\ccicons@sa}{\LWR@ccicons{ccShareAlike}{2}}

```

```

8 \renewcommand{\ccicons@end}{\LWR@ccicons{ccNoDerivatives}{3}}
9 \renewcommand{\ccicons@nc}{\LWR@ccicons{ccNonCommercial}{4}}
10 \renewcommand{\ccicons@nceu}{\LWR@ccicons{ccNonCommercialEU}{5}}
11 \renewcommand{\ccicons@ncjp}{\LWR@ccicons{ccNonCommercialJP}{6}}
12 \renewcommand{\ccicons@pd}{\LWR@ccicons{ccPublicDomain}{7}}
13 \renewcommand{\ccicons@zero}{\LWR@ccicons{ccZero}{8}}
14 \renewcommand{\ccicons@sampling}{\LWR@ccicons{ccSampling}{9}}
15 \renewcommand{\ccicons@share}{\LWR@ccicons{ccShare}{10}}
16 \renewcommand{\ccicons@remix}{\LWR@ccicons{ccRemix}{11}}
17 \renewcommand{\ccicons@copy}{\LWR@ccicons{ccCopy}{12}}
18 \renewcommand{\ccicons@pdalt}{\LWR@ccicons{ccPublicDomainAlt}{13}}

```

File 73 **lwarp-centerlastline.sty**

§ 182 Package **centerlastline**

Pkg centerlastline centerlastline is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{centerlastline}[2020/10/12]

2 \providecommand{\centerlastline}{}
3 \def\endcenterlastline{\par}

```

File 74 **lwarp-centernot.sty**

§ 183 Package **centernot**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg centernot centernot is used as-is for SVG math, and emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{centernot}[2016/05/16]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\require{centernot}}
4 \end{warpMathJax}

```

File 75 **lwarp-changebar.sty**

§ 184 Package **changebar**

Pkg changebar changebar is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{changebar}[2018/03/09]

2 \newcommand*{\cbstart}{}
3 \newcommand*{\cbend}{}
4 \newenvironment*{changebar}{}{}
5 \newcommand*{\cbdelete}{}
6 \newcommand*{\nochnagebars}{}
7 \newcommand*{\cbcolor}[1]{}

```

```

8 \newlength{\changebarwidth}
9 \newlength{\delebarwidth}
10 \newlength{\changebarsep}
11 \newcounter{changebargrey}

```

File 76 **lwarp-changelayout.sty**

§ 185 Package **changelayout**

(Emulates or patches code by AHMED MUSA.)

Pkg changelayout **changelayout** is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{changelayout}[2009/10/07]

2 \renewrobustcmd\cpl@backtodefaults{}
3
4 \renewrobustcmd\cpl@checkifoddpagelayout{%
5   \cpl@oddpagelayoutfalse%
6 }
7
8 \renewrobustcmd\changepagelayout[1]{%
9   \setkeys[KV]{changelayout}{#1}%
10 }
11
12 \renewrobustcmd{\changetextlayout}[1]{\changepagelayout{#1}}
13
14 \renewrobustcmd\adjustpagelayout[1]{%
15   \setkeys[KV@X]{changelayout}{#1}%
16 }
17
18 \renewrobustcmd{\adjusttextlayout}[1]{\adjustpagelayout{#1}}
19
20 \renewrobustcmd\adjusttextwidth[1]{%
21   \setkeys[KV]{changelayout}{#1}%
22   \begin{BlockClass}[color:\LWR@colorstyle{named}{\cpl@textcolor}]{changelayout}
23     \color{\cpl@textcolor}%
24     \cpl@content
25   \end{BlockClass}
26 }

```

File 77 **lwarp-changepage.sty**

§ 186 Package **changepage**

(Emulates or patches code by PETER WILSON.)

Pkg changepage **changepage** is ignored.

for HTML output: Discard all options for lwarp-changepage:

```

1 \LWR@ProvidesPackageDrop{changepage}[2009/10/20]

2 \newif\ifoddpagelayout

```

```

3 \DeclareRobustCommand{\checkoddpage}{\oddpagetrue}
4 \DeclareRobustCommand{\changetext}[5]{}
5 \DeclareRobustCommand{\change page}[9]{}
6
7 \ifundefined{adjustwidth}{
8 \newenvironment{adjustwidth}[2]{}{}
9 \newenvironment{adjustwidth*}[2]{}{}
10 }{
11 \renewenvironment{adjustwidth}[2]{}{}
12 \renewenvironment{adjustwidth*}[2]{}{}
13 }

14 \DeclareDocumentCommand{\strictpagecheck}{}{}
15 \DeclareDocumentCommand{\easypagecheck}{}{}

```

File 78 **lwarp-changes.sty**

§ 187 Package **changes**

(Emulates or patches code by EKKART KLEINOD.)

Pkg changes

changes is patched for use by lwarp.

 `\comment` Use `commandnameprefix=ifneeded` to avoid a conflict with the `\comment` command when using `lwarp`.

for HTML output: 1 \LWR@ProvidesPackagePass{changes}[2021/07/15]

`\BaseJobname` is added to the label in case `xr` or `xr-hyper` are used.

```

2 \renewcommand{\ChangesListline}[4]{%
3   \IfIsInList{#1}{\Changes@loc@show}{%
4     \LWR@startpars%
5     #2: #3 \qqquad
6     \nameref{\BaseJobname-autopage-#4}%
7     \LWR@stoppars%
8   }{}%
9 }
10
11 \renewcommand{\listofchanges}[1][\@empty]{%
12 \setkeys{Changes@loc}{#1}%
13 \ifbool{Changes@optiondraft}%
14 {%
15 \IfIsInList{\Changes@loc@style}{list|summary|compactsummary}%
16 }{}%
17 }%
18 \PackageWarning{changes}{Wrong style for list of changes: '\Changes@loc@style', using 'list' instead.}
19 \def\Changes@loc@style{}%
20 }%
21 \IfIsEmpty{\Changes@loc@style}%
22 {\def\Changes@loc@style{list}}%
23 }{}%
24 \IfStrEq{\Changes@loc@show}{all}%
25 {\def\Changes@loc@show{added|deleted|replaced|highlight|comment}}%
26 }{}%
27 \IfIsInList{\Changes@loc@show}{added|deleted|replaced|highlight|comment}%

```

```

28 {}%
29 {%
30 \PackageWarning{changes}{Wrong show-value for list of changes: '\Changes@loc@show', using 'all' instead}
31 \def\Changes@loc@show{}%
32 }%
33 \IfIsEmpty{\Changes@loc@show}%
34 {\def\Changes@loc@show{added|deleted|replaced|highlight|comment}}%
35 {}%
36 \IfIsEmpty{\Changes@loc@title}%
37 {%
38 \IfStrEq{\Changes@loc@style}{list}%
39 {\def\Changes@heading{\listofchangesname}}{%
40 \IfStrEq{\Changes@loc@style}{summary}%
41 {\def\Changes@heading{\summaryofchangesname}}{%
42 \IfStrEq{\Changes@loc@style}{compactsummary}%
43 {\def\Changes@heading{\compactsummaryofchangesname}}{%
44 }%
45 {\def\Changes@heading{\Changes@loc@title}}%
46 \section*{\Changes@heading}
47 \IfIsInList{\Changes@loc@style}{list}%
48 {%
49 \IfFileExists{\jobname.\Changes@loc@extension}%
50 {%
51 \newread\Changes@InFile%
52 \openin\Changes@InFile=\jobname.\Changes@loc@extension%
53 \loop\unless\ifeof\Changes@InFile%
54 \read\Changes@InFile to \Changes@Line%
55 \ifeof\Changes@InFile\else%
56 \Changes@Line%
57 \fi
58 \repeat
59 \closein\Changes@InFile%
60 }{%
61 \emph{\changesnoloc}%
62 \PackageWarning{changes}{LaTeX rerun needed for list of changes}%
63 }%
64 }{%
65 \IfIsInList{\Changes@loc@style}{summary|compactsummary}%
66 {%
67 \IfFileExists{\jobname.\Changes@soc@extension}%
68 {%
69 \newread\Changes@InFile%
70 \openin\Changes@InFile = \jobname.\Changes@soc@extension%
71 \loop\unless\ifeof\Changes@InFile%
72 \read\Changes@InFile to \Changes@Line%
73 \ifeof\Changes@InFile\else%
74 \expandafter\changes@chopline\Changes@Line\%
75 \textbf{%
76 \IfIsColored%
77 {\color{\Changes@Incolor}}%
78 }%
79 \IfIsAnonymous{\Changes@Inid}%
80 {%
81 \LWR@textcurrentcolor{% lwarp
82 \changesauthorname: \changesanonymousname%
83 }% lwarp
84 }%
85 {%
86 \LWR@textcurrentcolor{% lwarp
87 \changesauthorname: \Changes@Inid%

```

```

88   }% lwarp
89 \IfIsEmpty{\Changes@Inname}%
90 {}%
91 { %
92   \LWR@textcurrentcolor{% lwarp
93 (\Changes@Inname)%
94   }% lwarp
95 }%
96 }%
97 }\\%
98 \numdef{\Changes@InSum}{0}%
99 \renewcommand*\do}[1]{%
100 \numdef{\Changes@InSum}{\Changes@InSum + \csuse{Changes@In#####1}}%
101 }%
102 \expandafter\dopsvlist\expandafter{\Changes@loc@show}%
103 \ifnumcomp{\Changes@InSum}{=}{0}%
104 {%
105   \parbox{\Changes@summary@width}{% lwarp
106     \changesnochanges%
107   }% lwarp
108 % \[1ex]% lwarp
109   \par% \lwarp
110 }%
111 {%
112 \numdef{\Changes@InCount}{0}%
113 \renewcommand*\do}[1]{%
114 \numdef{\Changes@InCount}{\Changes@InCount + \csuse{Changes@In#####1}}%
115 \ifboolexpr{%
116 not test {\IfStrEq{\Changes@loc@style}{compactsummary}} or%
117 test {\ifnumgreater{\csuse{Changes@In#####1}}{0}}%
118 }%
119 {%
120 % \parbox{\Changes@summary@width}{% lwarp
121 \csuse{changes#####1name}~%
122 % \let\cleaders\leaders\dotfill~% lwarp
123 \dotfill~% \lwarp
124 \csuse{Changes@In#####1}%
125 }% lwarp
126 % \ifnumless{\Changes@InCount}{\Changes@InSum}% lwarp
127 {\}%
128 % {\[1ex]}% lwarp
129 }%
130 {}%
131 }%
132 \expandafter\dopsvlist\expandafter{\Changes@loc@show}%
133   \par% lwarp
134 }%
135 \fi%
136 \repeat
137 \closein\Changes@InFile%
138 }{%
139 \emph{\changesnosoc}%
140 \PackageWarning{changes}{LaTeX rerun needed for summary of changes}%
141 }%
142 }{}%
143 }{}%
144 }
145
146
147 \renewcommand{\Changes@Markup@comment}[3]{%

```

```
148 \IfStrEq{\Changes@optioncommentmarkup}{todo}%
149 {%
150 \IfIsColored%
151 {\colorlet{\Changes@todocolor}{authorcolor}}%
152 {\colorlet{\Changes@todocolor}{black}}%
153 \todo[color=\Changes@todocolor!10, bordercolor=\Changes@todocolor, linecolor=\Changes@todocolor!70, no
154 }{}%
155 \IfStrEq{\Changes@optioncommentmarkup}{margin}%
156 {%
157 \marginpar{%
158 \IfIsColored%
159 {\leavevmode\color{authorcolor}}%
160 }{}%
161 \LWR@textcurrentcolor{% lwarp
162 \textbf{[\IfIsAnonymous{#2}]{#3~}\arabic{\Changes@commentCount#2}:} #1%
163 }% lwarp
164 }%
165 }{}%
166 \IfStrEq{\Changes@optioncommentmarkup}{footnote}%
167 {%
168 \footnote{%
169 \LWR@textcurrentcolor{% lwarp
170 \textbf{[\IfIsAnonymous{#2}]{#3~}\arabic{\Changes@commentCount#2}:} #1%
171 }% lwarp
172 }%
173 }{}%
174 \IfStrEq{\Changes@optioncommentmarkup}{uwave}%
175 {%
176 {%
177 \IfIsColored%
178 {\color{authorcolor}}%
179 }{}%
180 \allowbreak%
181 \uwave{%
182 \textbf{[\IfIsAnonymous{#2}]{#3~}\arabic{\Changes@commentCount#2}:} #1%
183 }%
184 }%
185 }{}%
186 }
187
188 \renewrobustcmd{\Changes@output}[7]{%
189 \ifbool{\Changes@optiondraft}%
190 {%
191 \Changes@check@author{#2}%
192 \Changes@set@color{#2}%
193 {%
194 \IfIsInList{#1}{added|deleted|replaced|highlight}%
195 {%
196 \IfIsEmpty{#5}%
197 {%
198 \IfIsAuthorEmptyAtPosition{#2}{left}%
199 }{}%
200 }{}%
201 \IfIsColored%
202 {\color{authorcolor}}%
203 }{}%
204 \LWR@textcurrentcolor{% lwarp
205 \Changes@Markup@author{\Changes@output@author@position{#2}{left}}%
206 }% lwarp
207 }{}%
```

```

208 }{}%
209 {%
210 \IfStrEq{#1}{highlight}%
211 }{}%
212 \IfIsColored%
213 {\color{authorcolor}}%
214 }{}%
215 }%
216 \LWR@textcurrentcolor{% lwarp
217 \IfStrEq{#1}{added}{\Changes@Markup@added{#3}}{}%
218 \IfStrEq{#1}{deleted}{\Changes@Markup@deleted{#4}}{}%
219 \IfStrEq{#1}{replaced}{\Changes@Markup@added{#3}\allowbreak\Changes@Markup@deleted{#4}}{}%
220 \IfStrEq{#1}{highlight}{\Changes@Markup@highlight{#3}}{}%
221 }% lwarp
222 }%
223 \IfIsEmpty{#5}%
224 {%
225 \IfIsAuthorEmptyAtPosition{#2}{right}%
226 }{}%
227 {%
228 \IfIsColored%
229 {\color{authorcolor}}%
230 }{}%
231 \LWR@textcurrentcolor{% lwarp
232 \Changes@Markup@author{\Changes@output@author@position{#2}{right}}%
233 }% lwarp
234 }{}%
235 }{}%
236 \stepcounter{Changes@#1Count#2}%
237 }{}%
238 \IfIsEmpty{#5}%
239 }{}%
240 {%
241 \stepcounter{Changes@commentCount#2}%
242 \Changes@set@commentcount{#2}%
243 \Changes@Markup@comment%
244 {#5}%
245 {#2}%
246 {\Changes@output@author{#2}}%
247 }{}%
248 }{}%
249 \IfIsEmpty{#2}%
250 {\def\Changes@locid{}}%
251 {\def\Changes@locid{~(##2)}}%
252 \addtocontents{\Changes@locextension}{\protect\ChangesListLine{#1}{#6\Changes@locid}{#7}{\thepage}}
253 }{}%
254 {%
255 \IfIsEmpty{#3}%
256 {\@bsphack\@esphack}%
257 {#3}%
258 }{}%
259 }

```

File 79 **lwarp-chappg.sty**

§ 188 Package **chappg**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg chappg

chappg is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{chappg}[2006/05/09]
2 \renewcommand{\pagenumbering}[2][{}]{
3 \providecommand{\chappgsep}{--}
```

File 80 **lwarp-chapterbib.sty**§ 189 Package **chapterbib***(Emulates or patches code by DONALD ARSENEAU.)*

Pkg chapterbib

chapterbib is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{chapterbib}[2010/09/18]
2 \xdef\@savedjobname{\BaseJobname}
3 \let\@currentipfile\@savedjobname
```

File 81 **lwarp-chemfig.sty**§ 190 Package **chemfig***(Emulates or patches code by CHRISTIAN TELLECHEA.)*

Pkg chemfig

chemfig is patched for use by lwarp.

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```
\begin{lateximage}[-chemfig~\PackageDiagramAltText]
\chemfig{. . .}
\polymerdelim[. . .]{. . .}
\end{lateximage}
```

The images are not hashed because they depend on external settings which may be changed at any time, and are unlikely to be reused inline anyhow.

for HTML output:

```
1 \LWR@ProvidesPackagePass{chemfig}[2021/02/28]
2 \catcode'\_ =11
3
4 \IfPackageAtLeastTF{chemfig}{2020/03/05}
5 {
6   \xpretocmd\charge{\begin{lateximage}[-chemfig~\PackageDiagramAltText]}
7     {\LWR@patcherror{chemfig}{charge}}
8   \xpretocmd\Charge{\begin{lateximage}[-chemfig~\PackageDiagramAltText]}
9     {\LWR@patcherror{chemfig}{Charge}}
10  \xapptocmd\charge_c{\end{lateximage}}
11    {\LWR@patcherror{chemfig}{charge_c}}
12 }{}
13
14 \IfPackageAtLeastTF{chemfig}{2019/04/18}%
15 {% 2019/04/18 or newer
```

```

16 \xpretocmd{\CF_chemfiga}
17   {\begin{lateximage}[-chemfig--\PackageDiagramAltText]}
18   {}{\LWR@patcherror{chemfig}{CF_chemfiga}}
19
20 \xpatchcmd{\CF_chemfigb}
21   {\let\CF_flipstate\CF_zero}
22   {\end{lateximage}\let\CF_flipstate\CF_zero}
23   {}{\LWR@patcherror{chemfig}{CF_chemfigb}}
24
25 \GlobalLetLtxMacro\LWR@chemfig@origCF_lewisc\CF_lewisc
26 \gdef\CF_lewisc#1,#2\nil{%
27 \begin{lateximage}[-chemfig--\PackageDiagramAltText]%
28 \LWR@chemfig@origCF_lewisc#1,#2\nil
29 \end{lateximage}
30 }
31
32 \gpreto{\schemestart}{%
33   \begin{lateximage}[-chemfig--\PackageDiagramAltText]%
34   }
35 \gappto{\CF_schemestop}{\end{lateximage}}
36
37}% 2019/04/18 or newer
38{% older than 2019/04/18
39
40 \LetLtxMacro\LWR@chemfig@origchemfig\chemfig
41
42 \DeclareDocumentCommand\chemfig{s O{} O{} m}{%
43   \begin{lateximage}[-chemfig--\PackageDiagramAltText]%
44   \IfBooleanTF{#1}{%
45     \LWR@chemfig@origchemfig*[#2][#3][#4]%
46   }{%
47     \LWR@chemfig@origchemfig[#2][#3][#4]%
48   }
49   \end{lateximage}%
50 }
51
52 \LetLtxMacro\LWR@chemfig@origCF@lewis@b\CF@lewis@b
53
54 \def\CF@lewis@b#1#2{%
55 \begin{lateximage}[-chemfig--\PackageDiagramAltText]%
56 \LWR@chemfig@origCF@lewis@b{#1}{#2}%
57 \end{lateximage}%
58 }
59
60 \preto{\schemestart}{%
61   \begin{lateximage}[-chemfig--\PackageDiagramAltText]%
62   }
63 \appto{\CF@schemestop}{\end{lateximage}}
64
65}% older than 2019/04/18
66
67 \catcode'\_ =8%
68
69
70
71 \LetLtxMacro\LWR@chemfig@origchemleft\chemleft
72
73 \def\chemleft#1#2\chemright#3{%
74 \begin{lateximage}[-chemfig--\PackageDiagramAltText]%
75 \LWR@chemfig@origchemleft#1#2\chemright#3%

```

```

76 \end{lateximage}%
77 }
78
79 \LetLtxMacro\LWR@chemfig@origchemup\chemup
80
81 \def\chemup#1#2\chemdown#3{%
82 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
83 \LWR@chemfig@origchemup#1#2\chemdown#3%
84 \end{lateximage}%
85 }

```

File 82 **lwarp-chemformula.sty**

§ 191 Package **chemformula**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemformula

chemformula is patched for use by lwarp.

The SVG images are hashed according to contents and local options. Global options are assumed to be constant document-wide.

 **chemformula with MATHJAX**

chemformula works best without MATHJAX. If MATHJAX is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The chemformula package adapts to `array`, but does not know about MATHJAX, and MATHJAX does not know about chemformula.)

While using MATHJAX, `\displaymathother` may also be used for other forms of display and inline math which contain chemformula expressions.

for HTML output:

```
1 \LWR@ProvidesPackagePass{chemformula}[2022/01/23]
```

```
2 \ExplSyntaxOn
```

`\ch`

Enclose in an inline SVG image or MATHJAX. The `alt` tag is the contents of the `\ch` expression. The filename is hashed, and also has additional hashing information based on the local options.

```
3 \RenewDocumentCommand \ch { O{}m }
4 {%
```

To work inside `align` with `\displaymathother`, a simple version must be used to work with chemformula's adaptation to `align`.

```
5   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
6   {
7     \chemformula_ch:nn {#1} {#2}% original
8   }
```

If used as the outer level, must temporarily ensure MATHJAX is disabled:

```
9   {
10  \begingroup%
11  \boolfalse{mathjax}%
```

An inline image is used, adjusted for the baseline:

```
12  \LWR@subsingledollar*{% lwarp
```

```

13     \textbackslashash{}%
14     ch%
15     \{%
16         \LWR@HTMLsanitizedetokenized{\detokenize{#2}}%
17     \}% alt text
18     }{%
19     \protect\LWR@HTMLsanitizedetokenized{%
20         \detokenize\expandafter{#1}%
21     }% add'l hashing
22     }%
23     {%
24         \chemformula_ch:nn {#1} {#2}%    original
25     }%
26     \endgroup%
27 }
28 }

```

\chcpd

Similar to \ch.

```

29 \IfPackageAtLeastTF{chemformula}{2019/10/13}{
30 \cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
31 {
32     \begingroup%
33     \boolfalse{mathjax}%
34     \LWR@subsingleddollar*{% lwarp
35         \textbackslashash{}%
36         chcpd%
37         \{%
38             \LWR@HTMLsanitizedetokenized{\detokenize{#2}}%
39         \}%
40     }{%
41         \protect\LWR@HTMLsanitizedetokenized{\detokenize\expandafter{#1}}%
42     }{% original
43     \group_begin:
44         \tl_if_blank:nF {#2}
45         {
46             \keys_set:nn {chemformula} {#1}
47             \__chemformula_save_catcodes:
48             \__chemformula_sanitiz:Nn
49                 \l__chemformula_chemformula_tmpa_tl
50                 {#2}
51             \__chemformula_input_compound_no_check:NV
52                 \l__chemformula_compound_tl
53             \l__chemformula_chemformula_tmpa_tl
54             \__chemformula_prepare_output:NV
55                 \l__chemformula_compound_tl
56                 \l__chemformula_catcodes_tl
57             \chemformula_write:V \l__chemformula_compound_tl
58         }
59     \group_end:
60     }
61     \endgroup
62 }
63 }% later than 2019/10/13
64 {% earlier than 2019/10/13
65 % \changes{v0.903}{2021/12/18}{\pkg{chemformula}: Improved alt tag sanitization.}
66 \cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
67 {
68     \begingroup%
69     \boolfalse{mathjax}%

```

```

70 \LWR@subsingledollar*{% lwarp
71   \textbackslash}%
72   chcpd%
73   \{%
74     \LWR@HTMLsanitizedetokenized{\detokenize{#2}}%
75   \}%
76 }{%
77   \protect\LWR@HTMLsanitizedetokenized{\detokenize\expandafter{#1}}%
78 }{% original
79 \group_begin:
80   \tl_if_blank:nF {#2}
81   {
82     \keys_set:nn {chemformula} {#1}
83     \__chemformula_save_catcodes:
84     \__chemformula_sanitiz:Nn
85     \l__chemformula_chemformula_tmpa_tl
86     {#2}
87     \__chemformula_input_compound_no_check:Nv
88     \l__chemformula_compound_tl
89     \l__chemformula_chemformula_tmpa_tl
90     \__chemformula_prepare_output:N \l__chemformula_compound_tl
91     \chemformula_write:V \l__chemformula_compound_tl
92   }
93 \group_end:
94 }
95 \endgroup
96 }
97}% earlier than 2019/10/13

```

 \backslash charrow

If standalone, appears in a regular lateximage.

```

98 \RenewDocumentCommand \charrow { mO{}O{} }
99 {
100   \begin{lateximage}[-chemformula- charrow]
101   \group_begin:
102     \__chemformula_draw_arrow:nnn {#1} {#2} {#3}
103   \group_end:
104   \end{lateximage}
105 }

```

 \backslash chname

If standalone, appears in a regular lateximage, hashed according to contents.

```

106 \RenewDocumentCommand \chname { R(){}R(){} }
107 {
108   \begin{lateximage}*[%
109     \textbackslash}%
110     chname%
111     (\LWR@HTMLsanitizedetokenized{\detokenize{#1}})%
112     (\LWR@HTMLsanitizedetokenized{\detokenize{#2}})%
113   ]*%
114   \chemformula_chwritebelow:nn {#1} {#2}
115   \end{lateximage}
116 }

```

 \backslash chlewis

Placed inline, hashed according to contents and options.

```

117 \RenewDocumentCommand \chlewis { O{}mm }
118 {
119   \begingroup%

```

```

120 \boolfalse{mathjax}%
121 \LWR@subsingledollar*{\textbackslash{}chlewis\{#2\}\{#3\}}%
122 {
123   \protect\LWR@HTMLsanitizedetokenized{\detokenize\expandafter{#1}}%
124 }{
125   \chemformula_lewis:nnn {#1} {#2} {#3}
126 }
127 \endgroup%
128 }

```

lwarp redefines the \$ character, so special handling is required to escape math expressions inside \ch.

This boolean tracks a new kind of escaped math:

```

129 \bool_new:N      \l__chemformula_first_last_LWRdollar_bool

```

\chemformula_input_escape_math

Adds additional escaping for the new dollar definition:

```

130 \cs_gset_protected:Npn \__chemformula_input_escape_math:n #1
131 {
132   \__chemformula_first_last_math:n {#1}
133   \bool_if:NT \l__chemformula_first_last_dollar_bool
134     {
135       \bool_set_true:N \l__chemformula_first_last_math_bool
136       \__chemformula_read_escape_dollar:w #1 \q_nil
137     }
138   \bool_if:NT \l__chemformula_first_last_mathbraces_bool
139     {
140       \bool_set_true:N \l__chemformula_first_last_math_bool
141       \__chemformula_read_escape_mathbraces:w #1 \q_nil
142     }

```

Added by lwarp:

```

143   \bool_if:NT \l__chemformula_first_last_LWRdollar_bool%   lwarp
144   {
145     \bool_set_true:N \l__chemformula_first_last_math_bool% lwarp
146     \__chemformula_read_escape_LWRdollar:w #1 \q_nil%       lwarp
147   }
148 }

```

\chemformula_read_escape_LWRdollar

The following parses the contents inside the new dollars.

lwarp keeps the dollar as its original math shift until the document starts. While **chemmacros** is being patched, the dollar must temporarily be set to its new meaning during the following definition.

```

149 \begingroup
150 \catcode'\$=\active
151
152 \cs_new_protected:Npn \__chemformula_read_escape_LWRdollar:w $#1$ \q_nil
153 {
154   \__chemformula_read_escape_math:n {#1}
155 }
156

```

157 \endgroup

\chemformula_bool_set_if_first_last

The following looks at the first and last tokens for delimiters to escape math inside \ch. The original definition is modified to look for the control sequences which are used by the new meaning of \$.

```

158 \cs_new_protected:Npn \__chemformula_bool_cs_set_if_first_last:NnNN #1#2#3#4
159 {
160   \int_zero:N \l__chemformula_tmpa_int
161   \int_zero:N \l__chemformula_tmpb_int
162   \int_set:Nn \l__chemformula_tmpa_int { \tl_count:n {#2} }
163   \tl_map_inline:nn {#2}
164   {
165     \int_incr:N \l__chemformula_tmpb_int
166     \int_compare:nT { \l__chemformula_tmpb_int = 1 }
167     {

```

At the start, the cs_ version compares control sequences:

```

168     \ifdefstrequal{##1}{#3}% lwarp
169     {
170       \bool_set_true:N #1
171     }% lwarp
172   {}
173 }

```

At the end, compare more control sequences:

```

174   \int_compare:nT { \l__chemformula_tmpb_int = \l__chemformula_tmpa_int }
175   {
176     \ifdefstrequal{##1}{#4}
177     {}
178     {
179       \bool_set_false:N #1
180     }
181   }
182 }
183 }

```

\chemformula_first_last_math

Modified to check for the new meaning of \$ at first/last:

```

184 \cs_gset_protected:Npn \__chemformula_first_last_math:n #1
185 {
186   \bool_set_false:N \l__chemformula_first_last_math_bool
187   \bool_set_false:N \l__chemformula_first_last_dollar_bool
188   \bool_set_false:N \l__chemformula_first_last_LWRdollar_bool% lwarp
189   \bool_set_false:N \l__chemformula_first_last_mathbraces_bool
190   \__chemformula_bool_set_if_first_last:Nnnn
191   \l__chemformula_first_last_dollar_bool
192   {#1}
193   { $ } { $ }
194   \bool_if:NF \l__chemformula_first_last_dollar_bool
195   {
196     \__chemformula_bool_set_if_first_last:Nnnn
197     \l__chemformula_first_last_mathbraces_bool
198     {#1}

```

```
199      { \ ( ) { \ } }
```

Added by lwarp:

```
200      \bool_if:NF \l__chemformula_first_last_mathbraces_bool%   lwarp
201      {
202          \__chemformula_bool_cs_set_if_first_last:NnNN
203          \l__chemformula_first_last_LWRdollar_bool
204          {#1}
205          { \LWR@newsingledollar } { \LWR@newsingledollar }
206          }%   lwarp
207      }
208  }

209 \ExplSyntaxOff
```

File 83 **lwarp-chemgreek.sty**

§ 192 Package **chemgreek**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemgreek

chemgreek is patched for use by lwarp.

 **Greek symbols**
package selection

To use text-mode symbols, use packages `textalpha` or `textgreek`. Using the other packages supported by `chemgreek` will result in math-mode greek characters, which will result in svg images being used. These images will be hashed.

 **X_YL^AT_EX, Lua^AT_EX**

If using X_YL^AT_EX or Lua^AT_EX, select the fontspec mapping:

```
\selectchemgreekmapping{fontspec}
```

for HTML output:

```
1 \LWR@ProvidesPackagePass{chemgreek}[2020/01/16]
2 \ExplSyntaxOn
3
4 \cs_gset_protected:Npn \chemgreek_text:n #1
5   { { \text {#1} } }
6
7 \appto\LWR@restoreorigformatting{%
8 \cs_set_protected:Npn \chemgreek_text:n #1%
9   { \ensuremath { \text {#1} } } }%
10 }
11
12 \ExplSyntaxOff
```

File 84 **lwarp-chemmacros.sty**

§ 193 Package **chemmacros**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemmacros

chemmacros is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{chemmacros}[2022/02/13]
```

svg file hashing assumes that the relevant options are constant for the entire document.

§ 193.1 **Changes to the user's document**

- ⚠ `\makepolymerdelims` When using `\makepolymerdelims`, enclose the entire expression inside a `polymerdelims` environment, such as (from the `chemmacros` manual):

```
\begin{polymerdelims}
\chemfig{-[@{op,.75}]CH_2-CH(-[6]Cl)-[@{cl,0.25}]}
\makepolymerdelims{5pt}[27pt]{op}{cl}
\end{polymerdelims}
```

- ⚠ **redox reactions** Redox reactions must be enclosed inside a `redoxreaction` environment. For print output, extra space must be included above and/or below the result, so they are declared as arguments to the environment, instead of being manually entered as per the `chemmacros` manual. For HTML output, the extra space is ignored and a `lateximage` is used instead.

```
\begin{redoxreaction}{7mm}{7mm}
\OX{a,Na} $\rightarrow$ \OX{b,Na}\pch\redox(a,b){oxidation}
\end{redoxreaction}
```

§ 193.2 **Code**

```
2 \ExplSyntaxOn
```

§ 193.3 **Loading packages**

Also accept the `lwarp` version:

```
3 \prg_set_conditional:Npnn \chemmacros_if_package_loaded:n #1 {p,T,F,TF}
4 {
5   \cs_if_exist:cTF {ver@#1.sty}
6     { \prg_return_true: }
7     {
8       \cs_if_exist:cTF {ver@lwarp-#1.sty}
9         { \prg_return_true: }
10        { \prg_return_false: }
11    }
12 }
```

Nullify `hyperref` detection:

```
13 \hook_gput_code:nnn {begindocument/end} {chemmacros}
14 {
15   \bool_set_false:N \l__chemmacros_hyperref_bool
16 }
```

§ 193.4 Loading modules

Patching chemmacros modules must be done `\AtBeginDocument`, since modules are invoked by the user in the preamble, and each patch is only done if the module is loaded.

§ 193.5 New environments

`\makepolymerdelims` and redox reactions must be enclosed in a `lateximage` during HTML output. These environments are provided here in HTML mode, and in the `lwarp` core in print mode, as a high-level semantic syntax which automatically embeds the contents in a `lateximage` with an appropriate `alt` tag.

Env `polymerdelims`

```
17 \DeclareDocumentEnvironment{polymerdelims}{}
18 {\begin{lateximage}[-chemmacros- polymer]}
19 {\end{lateximage}}
```

Env `redoxreaction`

`{\space above}` `{\space below}`

For HTML output, the above and below space is ignored, and a `lateximage` is used instead. For the print output version, see section 90.

```
20 \DeclareDocumentEnvironment{redoxreaction}{m m}
21 {\begin{lateximage}[-chemmacros- redoxreaction]}
22 {\end{lateximage}}
```

§ 193.6 Acid-base

```
23 \AtBeginDocument{
24 \chemmacros_module_if_loaded:nTF{{acid-base}}{
25 \PackageInfo{lwarp}{Patching~chemmacros~module~acid-base}
26
27 \cs_gset_protected:Npn \chemmacros_p:n #1
28 {
29   \begingroup
30   \boolfalse{mathjax}
31   \LWR@subsingledollar*{
32     \textbackslashash{}}%
33   p%
34   \{%
35     \LWR@HTMLsanitizedetokenized{\detokenize{#1}}%
36   \}
37   }{
38     chemmacrosp%
39     \protect\LWR@HTMLsanitizedetokenized{\detokenize\expandafter{#1}}%
40   }{
41     \group_begin:
42     \mbox
43     {
44       \chemmacros_p_style:n {p}
45       \ensuremath {#1}
46     }
47     \group_end:
48   }
49   \endgroup
50 }
51
52 \RenewDocumentCommand \pH {} {
```

```
53 \begingroup
54 \boolfalse{mathjax}
55 \LWR@subsingledollar*{\textbackslash}pH}{chemmacros}{
56   \chemmacros_p:n { \chemmacros_formula:n {H} }
57 }
58 \endgroup
59 }
60
61 \RenewDocumentCommand \pOH {} {
62   \begingroup
63   \boolfalse{mathjax}
64   \LWR@subsingledollar*{\textbackslash}pOH}{chemmacros}{
65     \chemmacros_p:n { \chemmacros_formula:n {OH} }
66   }
67   \endgroup
68 }
69
70 \RenewDocumentCommand \pKa {0{}}
71 {
72   \begingroup
73   \boolfalse{mathjax}
74   \LWR@subsingledollar*{\textbackslash}pKa{[]#1{}}{chemmacros #1}{
75     \chemmacros_p:n
76     {
77       \Ka \ifblank {#1} {}
78       { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
79     }
80   }
81   \endgroup
82 }
83
84 \RenewDocumentCommand \pKb {0{}}
85 {
86   \begingroup
87   \boolfalse{mathjax}
88   \LWR@subsingledollar*{\textbackslash}pKb{[]#1{}}{chemmacros #1}{
89     \chemmacros_p:n
90     {
91       \Kb \ifblank {#1} {}
92       { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
93     }
94   }
95   \endgroup
96 }
97
98 \LetLtxMacro\LWR@chemmacros@origKa\Ka
99 \renewcommand*{\Ka}{%
100   \begingroup
101   \boolfalse{mathjax}
102   \LWR@subsingledollar*{\textbackslash}Ka}{chemmacros}{%
103     \LWR@chemmacros@origKa%
104   }%
105   \endgroup
106 }
107
108 \LetLtxMacro\LWR@chemmacros@origKb\Kb
109 \renewcommand*{\Kb}{%
110   \begingroup
111   \boolfalse{mathjax}
112   \LWR@subsingledollar*{\textbackslash}Kb}{chemmacros}{%
```

```

113     \LWR@chemmacros@origKb%
114   }%
115   \endgroup
116 }
117
118 \LetLtxMacro\LWR@chemmacros@origKw\Kw
119 \renewcommand*{\Kw}{%
120   \begingroup
121     \boolfalse{mathjax}
122     \LWR@subsingledollar*{\textbackslash}Kw}{chemmacros}{
123       \LWR@chemmacros@origKw
124     }
125   \endgroup
126 }
127
128 }{}% module loaded
129 }% AtBeginDocument

```

§ 193.7 Charges

```

130 \AtBeginDocument{
131   \chemmacros_module_if_loaded:nTF{{charges}}{
132     \PackageInfo{lwarp}{Patching~chemmacros~module~charges}
133   }
134   \cs_gset_protected:Npn \fplus {
135     \begingroup
136       \boolfalse{mathjax}
137       \LWR@subsingledollar*{\textbackslash}fplus}{chemmacros}
138     { \LWR@origensuredmath{\chemformula_fplus:} }
139     \endgroup
140 }
141   \cs_gset_protected:Npn \fminus {
142     \begingroup
143       \boolfalse{mathjax}
144       \LWR@subsingledollar*{\textbackslash}fminus}{chemmacros}
145     { \LWR@origensuredmath{\chemformula_fminus:} }
146     \endgroup
147 }
148
149 }{}% Module loaded.
150 }% AtBeginDocument

```

§ 193.8 Nomenclature

```

151 \AtBeginDocument{
152   \chemmacros_module_if_loaded:nTF{{nomenclature}}{
153     \PackageInfo{lwarp}{Patching~chemmacros~module~nomenclature}
154   }
155   \cs_gset_protected:Npn \chemmacros_charge:n #1
156   {
157     \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}{
158       {\chemmacros_formula:n { }^{#1} }}
159     {
160       \ifmode
161         {\chemmacros_formula:n { }^{#1} }}
162       \else
163         { \textsuperscript{\ensuremath{#1}} }
164       \fi
165     }
166   }

```

```
167
168
169 \LetLtxMacro\LWR@chemmacros@origchemprime\chemprime
170
171 \protected\def\chemprime { \HTMLUnicode{2032} }
172
173 \appto\LWR@restoreorigformatting{%
174 \LetLtxMacro\chemprime\LWR@chemmacros@origchemprime%
175 }

176 \cs_gset_protected:Npn \__chemmacros_cip:n #1
177 {
178   \tl_set:Nn \l__chemmacros_tmpa_tl {#1}
179   \int_step_inline:nnnn {0} {1} {9}
180   {
181     \tl_replace_all:Nnn \l__chemmacros_tmpa_tl
182     {##1}
183     { { \l__chemmacros_cip_number_tl ##1} }
184   }
185   {
186     \l__chemmacros_cip_inner_tl
187     \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
188       \l__chemmacros_tmpa_tl
189     }}% lwarp
190   }
191 }

192 \RenewDocumentCommand \Sconf { O{S} } {
193 \begin{lateximage}\textbackslash{Sconf{[]#1[]}}*
194   \chemmacros_sconf:n {#1}
195 \end{lateximage}
196 }
197
198 \RenewDocumentCommand \Rconf { O{R} } {
199 \begin{lateximage}\textbackslash{Rconf{[]#1[]}}*
200   \chemmacros_rconf:n {#1}
201 \end{lateximage}
202 }

203 \cs_gset_protected:Npn \chemmacros_hapto:n #1
204 {
205   \begingroup
206   \boolfalse{mathjax}
207   \LWR@subsingledollar*{\textbackslash{hapto\{#1\}}}{chemmacros}{
208     \chemmacros_coordination_symbol:nnnn
209     { \l__chemmacros_coord_use_hyphen_bool }
210     {
211       { \c_true_bool }
212     }
213     { \chemeta }
214     {#1}
215   }
216   \endgroup
217 }
218
219 \cs_gset_protected:Npn \chemmacros_dento:n #1
220 {
221   \begingroup
222   \boolfalse{mathjax}
223   \LWR@subsingledollar*{\textbackslash{dento\{#1\}}}{chemmacros}{
```

```

224     \chemmacros_coordination_symbol:nnnn
225     { \l__chemmacros_coord_use_hyphen_bool }
226     {
227         { \c_true_bool }
228     }
229     { \chemkappa }
230     {#1}
231 }
232 \endgroup
233 }
234
235 \cs_gset_protected:Npn \chemmacros_bridge:n #1
236 {
237     \begingroup
238     \boolfalse{mathjax}
239     \LWR@subsingledollar*{\textbackslash}bridge\{#1\}{chemmacros}{
240         \chemmacros_coordination_symbol:nnnn
241         { \l__chemmacros_coord_use_hyphen_bool }
242         { \l__chemmacros_bridge_super_bool }
243         { \chemmu }
244         {#1}
245     }
246     \endgroup
247 }
248 }{}% Module loaded.
249 }% AtBeginDocument

```

§ 193.9 Particles

```

250 \AtBeginDocument{
251 \chemmacros_module_if_loaded:nTF{{particles}}{
252 \PackageInfo{lwarp}{Patching~chemmacros~module~particles}
253
254 \cs_gset_protected:Npn \chemmacros_declare_nucleophile:Nn #1#2
255 {
256     \cs_set_protected:cpn {__chemmacros_ \chemmacros_remove_backslash:N #1:}
257     {
258         \bool_if:NTF \l__chemmacros_nucleophile_elpair_bool
259         {
260             \chemmacros_elpair:n { #2 }
261             { \skip_horizontal:N \l__chemmacros_nucleophile_dim }
262             \chemmacros_formula:n { {}^{}- } }
263         }
264         { \chemmacros_formula:n { #2^{}- } } }
265     }
266     \DeclareDocumentCommand #1 {o}
267     {%
268         \begin{lateximage}%
269         \group_begin:%
270         \IfNoValueF {##1}%
271             { \chemmacros_set_keys:nn {particles} {##1} }%
272         \use:c {__chemmacros_ \chemmacros_remove_backslash:N #1:}%
273         \group_end:%
274         \end{lateximage}%
275     }
276 }
277
278 \RenewChemNucleophile \Nuc {Nu}
279 \RenewChemNucleophile \ba {ba}
280

```

```
281 }{}% Module loaded.
282 }% AtBeginDocument
```

§ 193.10 Phases

```
283 \AtBeginDocument{
284 \chemmacros_module_if_loaded:nTF{{phases}}{
285 \PackageInfo{lwarp}{Patching~chemmacros~module~phases}
286
287 \cs_undefine:N \chemmacros_phase:n
288 \cs_new_protected:Npn \chemmacros_phase:n #1
289   {

290   \mode_leave_vertical:

291   \bool_if:NTF \l__chemmacros_phases_sub_bool
292     {
293     \ifnumequal{\value{LWR@lateximagedepth}}{0}
294     {
295     \textsubscript{ (#1) }
296     }
297     {
298     \chemformula_subscript:n { (#1) }
299     }
300     }
301     {
302     \skip_horizontal:N \l__chemmacros_phases_space_dim
303     \chemmacros_text:n { (#1) }
304     }
305   }
306
307 }{}% Module loaded.
308 }% AtBeginDocument
```

§ 193.11 Mechanisms

```
309 \AtBeginDocument{
310 \chemmacros_module_if_loaded:nTF{{mechanisms}}{
311 \PackageInfo{lwarp}{Patching~chemmacros~module~mechanisms}
312
313 \chemmacros_define_keys:nn {textmechanisms}
314   {
315   type      .choice: ,
316   type /    .code:n   =
317   {
318     \__chemmacros_set_mechanisms:nnn { S }
319     {
320     \textsubscript{N}
321     }
322     { }
323   } ,
324   type / 1  .code:n   =
325   {
326     \__chemmacros_set_mechanisms:nnn { S }
327     {
328     \textsubscript{N}
329     1
330     }
331     { }
332   } ,
```

```
333 type / 2 .code:n =
334 {
335   \chemmacros_set_mechanisms:nnn { S }
336   {
337     \textsubscript{N}
338     2
339   }
340   { }
341 },
342 type / se .code:n =
343 {
344   \chemmacros_set_mechanisms:nnn { S }
345   {
346     \textsubscript{E}
347   }
348   { }
349 },
350 type / 1e .code:n =
351 {
352   \chemmacros_set_mechanisms:nnn { S }
353   {
354     \textsubscript{E}
355     1
356   }
357   { }
358 },
359 type / 2e .code:n =
360 {
361   \chemmacros_set_mechanisms:nnn { S }
362   {
363     \textsubscript{E}
364     2
365   }
366   { }
367 },
368 type / ar .code:n =
369 {
370   \chemmacros_set_mechanisms:nnn { S }
371   {
372     \textsubscript{E}
373   }
374   { Ar - }
375 },
376 type / e .code:n =
377 { \chemmacros_set_mechanisms:nnn { E } { } { } },
378 type / e1 .code:n =
379 { \chemmacros_set_mechanisms:nnn { E } { 1 } { } },
380 type / e2 .code:n =
381 { \chemmacros_set_mechanisms:nnn { E } { 2 } { } },
382 type / cb .code:n =
383 {
384   \chemmacros_set_mechanisms:nnn { E }
385   {
386     1
387     \textsubscript{cb}
388   }
389   { }
390 },
391 type .default:n =
392 }
```

```

393
394 \cs_gset_protected:Npn \chemmacros_mechanisms:n #1
395 {
396   \tl_if_blank:nTF {#1}
397     { \chemmacros_set_keys:nn {textmechanisms} { type } }
398     { \chemmacros_set_keys:nn {textmechanisms} { type = #1 } }
399   \mbox
400   {
401     \tl_use:N \l__chemmacros_mechanisms_ar_tl
402     \tl_use:N \l__chemmacros_mechanisms_type_tl
403     \tl_use:N \l__chemmacros_mechanisms_mol_tl
404   }
405 }
406
407 \appto\LWR@restoreorigformatting{%
408 \cs_set_protected:Npn \chemmacros_mechanisms:n #1%
409 {%
410   \tl_if_blank:nTF {#1}%
411     { \chemmacros_set_keys:nn {mechanisms} { type } }%
412     { \chemmacros_set_keys:nn {mechanisms} { type = #1 } }%
413   \mbox%
414   {%
415     \tl_use:N \l__chemmacros_mechanisms_ar_tl%
416     \tl_use:N \l__chemmacros_mechanisms_type_tl%
417     \tl_use:N \l__chemmacros_mechanisms_mol_tl%
418   }%
419 }%
420 }
421
422 }{}% Module loaded.
423 }% AtBeginDocument

```

§ 193.12 Newman

There are so many options that it is hard to hash these images for reuse.

```

424 \AtBeginDocument{
425 \chemmacros_module_if_loaded:nTF{{newman}}{
426 \PackageInfo{lwarp}{Patching~chemmacros~module~newman}
427
428 \RenewDocumentCommand \newman {od()m}%
429 {
430   \IfValueTF{#2}
431     {\begin{lateximage}[\textbackslash{}newman(#2)\{#3\}]*}
432     {\begin{lateximage}[\textbackslash{}newman\{#3\}]*}
433   \group_begin:
434     \IfNoValueF {#1} { \chemmacros_set_keys:nn {newman} {#1} }
435     \IfNoValueTF {#2}
436       { \chemmacros_newman:nn { } {#3} }
437       { \chemmacros_newman:nn {#2} {#3} }
438   \group_end:
439   \end{lateximage}
440 }%
441
442 }{}% Module loaded.
443 }% AtBeginDocument

```

§ 193.13 **Orbital**

```

444 \AtBeginDocument{
445 \chemmacros_module_if_loaded:nTF{{orbital}}{
446 \PackageInfo{lwarp}{Patching~chemmacros~module~orbital}
447
448 \RenewDocumentCommand \orbital {om}
449 {
450   \IfValueTF{#1}
451   {
452     \begin{lateximage}[%
453       \textbackslash{}%
454       orbital{[]}%
455       \LWR@HTMLsanitizedetokenized{\detokenize{#1}}%
456       {} \{}#2\}%
457     ]*[][\margin-left: 1em ; margin-right: 1em]
458   }
459   {
460     \begin{lateximage}[%
461       \textbackslash{}orbital\{}#2\}%
462     ]*[][\margin-left: 1em ; margin-right: 1em]
463   }
464   \group_begin:
465     \chemmacros_set_keys:nn {orbital/type} {#2}
466     \IfNoValueTF {#1}
467     { \chemmacros_orbital:n { } }
468     { \chemmacros_orbital:n {#1} }
469   \group_end:
470   \end{lateximage}
471 }
472
473 }{}% Module loaded.
474 }% AtBeginDocument

```

§ 193.14 **Reactions**

```

\chemmacros_declare_reaction_env {<chem>} {<math>} {<args number>} {<argument list ({#2}{#3}...)}
475 \AtBeginDocument{
476 \chemmacros_module_if_loaded:nTF{{reactions}}{
477 \PackageInfo{lwarp}{Patching~chemmacros~module~reactions}
478
479 % #1: chem
480 % #2: math
481 % #3: args number
482 % #4: argument list ({#2}{#3}...)
483 \cs_gset_protected:Npn \__chemmacros_declare_reaction_env:nnnn #1#2#3#4
484 {
485   \exp_args:Nnx \DeclareDocumentEnvironment {#1}
486     { \int_compare:nT { #3+0 = 0 } {!} 0{} \prg_replicate:nn {#3+0} {m} }
487     {
488       \boolfalse{mathjax}%                lwarp
489       \ifdefvoid{\LWR@ThisAltText}{%        lwarp
490         \ThisAltText{-chemmacros~reaction}% lwarp
491       }{}%                                   lwarp
492       \chemmacros_add_reaction_description:n {##1}
493       \__chemmacros_begin_reaction:
494       \__chemmacros_reaction_read:nnw {#2} {#4}
495     }
496   {

```

```

497     \__chemmacros_end_reaction:
498     \gdef\LWR@ThisAltText{%           lwarp
499     \ignorespacesafterend
500     }
501   }
502
503 \cs_generate_variant:Nn \chemmacros_declare_reaction_env:nnnn {nnnV}
504
505 \RenewChemReaction {reaction} {equation}
506 \RenewChemReaction {reaction*} {equation*}
507 \RenewChemReaction {reactions} {align}
508 \RenewChemReaction {reactions*} {align*}
509
510 }{}% Module loaded.
511 }% AtBeginDocument

```

§ 193.15 Reactants

Recompiled for tabular ampersand processing, with the only change being `\StartDefiningTabulars`. `\xpatchcmd` does not work here.

```

512 \StartDefiningTabulars%           lwarp
513
514 % #1: star: include ID in table
515 \RenewDocumentCommand \printreactants {s}
516 {
517   \group_begin:
518   \chemmacros_set_keys:nn {reactants} { switch = false }
519   \int_step_variable:nNn
520   { \seq_count:N \g_chemnum_initiated_compounds_seq }
521   \l__chemmacros_reactants_tmpa_tl
522   {
523     \seq_put_right:Nx
524     \l__chemmacros_reactants_tmpa_seq
525     {
526       \chemnum_cmpd:nnne { \c_false_bool } { \c_true_bool } {}
527       {
528         \seq_item:NV
529         \g_chemnum_initiated_compounds_seq
530         \l__chemmacros_reactants_tmpa_tl
531       }
532       &
533       \bool_if:nT {#1}
534       {
535         \seq_item:NV
536         \g_chemnum_initiated_compounds_seq
537         \l__chemmacros_reactants_tmpa_tl
538         &
539       }
540       % TODO: expl3-command ??
541       \solvent
542       {
543         \seq_item:NV
544         \g_chemnum_initiated_compounds_seq
545         \l__chemmacros_reactants_tmpa_tl
546       }
547       \tabularnewline
548     }
549     \tl_set:Nx
550     \l__chemmacros_reactants_tmpb_tl

```

```

551     {
552         \seq_item:NV
553         \g_chemnum_initiated_compounds_seq
554         \l__chemmacros_reactants_tmpa_tl
555     }
556     \chemmacros_reactants_list_subreactant:Vn
557     \l__chemmacros_reactants_tmpb_tl
558     {#1}
559 }
560 % TODO: longtable ?
561 %     table customizable?
562 % first draft of two styles
563 \par
564 \noindent
565 \bool_if:NTF \l__chemmacros_reactants_printreactants_style_bool
566 {
567     \str_case:Vn \l__chemmacros_reactants_printreactants_style_str
568     {
569         {xltabular}
570         {
571             \chemmacros_if_package_loaded:nTF {xltabular}
572             {
573                 \bool_if:NTF {#1}
574                 {
575                     \begin {xltabular}
576                     { \textwidth }
577                     { @{}ll>{\raggedright\arraybackslash}X@{} }
578                     }
579                     {
580                         \begin {xltabular}
581                         { \textwidth }
582                         { @{}l>{\raggedright\arraybackslash}X@{} }
583                         }
584                     \seq_use:Nn \l__chemmacros_reactants_tmpa_seq { }
585                     \end{xltabular}
586                 }
587                 {
588                     \msg_expandable_error:nnnn
589                     {chemmacros}
590                     {package-not-loaded}
591                     { \printreactants }
592                     {xltabular}
593                 }
594             }
595         }{longtable}
596         {
597             \chemmacros_if_package_loaded:nTF {longtable}
598             {
599                 \bool_if:NTF {#1}
600                 {
601                     \begin {longtable}[l]
602                     { @{}ll>{\raggedright\arraybackslash}p{0.6\textwidth}@{} }
603                     }
604                     {
605                         \begin {longtable}[l]
606                         { @{}l>{\raggedright\arraybackslash}p{0.9\textwidth}@{} }
607                         }
608                     \seq_use:Nn \l__chemmacros_reactants_tmpa_seq { }
609                     \end{longtable}
610                 }

```

```
611         {
612             \msg_expandable_error:nnnn
613             {chemmacros}
614             {package-not-loaded}
615             { \printreactants }
616             {longtable}
617         }
618     }
619 }
620 }
621 {
622     \msg_warning:nn {chemmacros} {missing-printreactants-style}
623 }
624 \group_end:
625 }
626
627 % #1: full ID
628 % #2: star, include ID in table
629 \cs_gset_protected:Npn \chemmacros_reactants_list_subreactant:nn #1#2
630 {
631     \chemnum_if_subcompounds:nT {#1}
632     {
633         \int_step_variable:nNn
634         { \chemnum_count_subcompounds:n {#1} }
635         \l__chemmacros_reactants_tmpa_tl
636         {
637             \seq_put_right:Nx
638             \l__chemmacros_reactants_tmpa_seq
639             {
640                 \chemnum_cmpd:nne { \c_false_bool } { \c_true_bool } {}
641                 {
642                     \exp_not:n {#1}
643                     \exp_not:V \l_chemnum_compound_separator_tl
644                     \chemnum_get_subcompound:nV
645                     {#1}
646                     \l__chemmacros_reactants_tmpa_tl
647                 }
648             }
649             &
650             \bool_if:nT {#2}
651             {
652                 #1
653                 \l_chemnum_compound_separator_tl
654                 \chemnum_get_subcompound:nV
655                 {#1}
656                 \l__chemmacros_reactants_tmpa_tl
657             }
658             % TODO: expl3-command ??
659             \solvent
660             {
661                 #1
662                 \l_chemnum_compound_separator_tl
663                 \chemnum_get_subcompound:nV
664                 {#1}
665                 \l__chemmacros_reactants_tmpa_tl
666             }
667             \tabularnewline
668         }
669     }
670 }
```

```

671 }
672 \cs_generate_variant:Nn \chemmacros_reactants_list_subreactant:nn {V}
673
674 \StopDefiningTabulars%      lwarp

```

§ 193.16 Redox

```

675 \AtBeginDocument{
676 \chemmacros_module_if_loaded:nTF{{redox}}{
677 \PackageInfo{lwarp}{Patching~chemmacros~module~redox}
678
679 \NewDocumentCommand \LWR@chemmacros@ox { s m >{\SplitArgument{1}{,}}m }
680 {
681   \IfBooleanTF {#1}
682     { \chemmacros_ox:nnnn {#1} {#2} #3 }
683     { \chemmacros_ox:nnnn { } {#2} #3 }
684 }
685
686 \RenewDocumentCommand \ox { s O{} m }
687 {
688   \begingroup
689   \boolfalse{mathjax}
690   \IfBooleanTF {#1}
691   {
692     \LWR@subsingledollar*{% yes hash
693       \textbackslashash{}}%
694     ox*%
695     \{%
696       \LWR@HTMLsanitizedetokenized{\detokenize{#3}}%
697     \}% alt
698   }{%
699     star \protect\LWR@HTMLsanitizedetokenized{\detokenize\expandafter{#2}}%
700   }{%
701     \LWR@chemmacros@ox* {#2} {#3}% contents
702   }%
703 }
704 {
705   \LWR@subsingledollar*{% yes hash
706     \textbackslashash{}}%
707     ox%
708     \{%
709       \LWR@HTMLsanitizedetokenized{\detokenize{#3}}%
710     \}% alt
711   }{%
712     \protect\LWR@HTMLsanitizedetokenized{\detokenize\expandafter{#2}}%
713   }{%
714     \LWR@chemmacros@ox {#2} {#3}% contents
715   }%
716 }
717 \endgroup
718 }
719
720 }{%} Module loaded.
721 }% AtBeginDocument

```

§ 193.17 Scheme

Fix for chemmacros as of v5.8b, when using newfloat and babel:

```

722 \AtBeginDocument{
723 \chemmacros_module_if_loaded:nTF{{scheme}}{
724 \PackageInfo{lwarp}{Patching~chemmacros~module~scheme}
725
726 \ifdefstring{\schemename}{los}{
727 \SetupFloatingEnvironment{scheme}{
728 name = \chemmacros_translate:n {scheme-name}
729 }
730 }{ }
731
732 }{ }% Module loaded.
733 }% AtBeginDocument

```

§ 193.18 Spectroscopy

```

734 \AtBeginDocument{
735 \chemmacros_module_if_loaded:nTF{{spectroscopy}}{
736 \PackageInfo{lwarp}{Patching~chemmacros~module~spectroscopy}
737
738 \cs_gset_protected:Npn \__chemmacros_nmr_base:n #1#2
739 {
740   \group_begin:
741     \tl_use:N \l__chemmacros_nmr_base_format_tl
742     \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
743     {
744       \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
745       \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
746     }
747     \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
748 %   \chemmacros_formula:n { ^{#1} }
749     \textsuperscript{#1}
750     \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
751     {
752       \bool_if:NTF \l__chemmacros_nmr_parse_bool
753       { \chemformula_ch:nV { } \g__chemmacros_nmr_element_coupled_tl }
754       { \chemmacros_formula:V \g__chemmacros_nmr_element_coupled_tl }
755     }
756     \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
757     \tl_use:N \l__chemmacros_nmr_method_tl
758   \group_end:
759 }
760
761
762 \cs_gset_protected:Npn \chemmacros_nmr_position:n #1
763 {
764   \chemmacros_formula:x
765   {
766     \exp_not:V \g__chemmacros_nmr_element_tl
767     \bool_if:NF \l__chemmacros_nmr_position_side_bool
768     {
769       \tl_if_eq:NnTF \l__chemmacros_nmr_position_tl {^}% lwarp
770       { \textsuperscript{\exp_not:n { #1} }}}% lwarp
771       { \textsubscript{\exp_not:n { #1} }}}% lwarp
772 %     \exp_not:V \l__chemmacros_nmr_position_tl
773 %     \exp_not:n { #1 }
774     }
775   }
776   \bool_if:NT \l__chemmacros_nmr_position_side_bool
777   {
778     \tl_use:N \l__chemmacros_nmr_position_tl

```

```

779     \chemmacros_nmr_position:n {#1}
780   }
781 }
782
783 \cs_gset_protected:Npn \chemmacros_nmr_coupling:w (#1;#2)
784 {
785   \tl_set:Nn \chemmacros_nmr_coupling_bonds_tl
786     {
787       \chemmacros_nmr_coupling_bonds_pre_tl
788       #1
789       \chemmacros_nmr_coupling_bonds_post_tl
790     }
791   \bool_if:NTF \chemmacros_nmr_coupling_nuclei_sub_bool
792     {
793       \tl_set:Nn \chemmacros_nmr_coupling_nuclei_tl
794         {
795           \c_math_subscript_token
796           \textsubscript% lwarp
797           {
798             \chemmacros_nmr_coupling_nuclei_pre_tl
799             \chemmacros_formula:n {#2}
800             \chemmacros_nmr_coupling_nuclei_post_tl
801           }
802         }
803     }
804   {
805     \tl_set:Nn \chemmacros_nmr_coupling_nuclei_tl
806       {
807         \chemmacros_nmr_coupling_nuclei_pre_tl
808         \chemmacros_formula:n {#2}
809         \chemmacros_nmr_coupling_nuclei_post_tl
810       }
811   }
812   \chemmacros_nmr_coupling_aux_i:w
813 }
814 \AfterEndPreamble{% After \AtBeginDocument
815 % \NMR{<num>,<elem>}<num>,<unit>[<solvent>] ALL arguments are optional
816 % \NMR* same but without ": $\delta$" at end
817 \cs_gset_protected:Npn \chemmacros_nmr:nnnn #1#2#3#4
818   {
819     \bool_if:NT \chemmacros_nmr_list_bool { \item \scan_stop: }
820     \group_begin:

821     \mode_leave_vertical:

822     \bool_set_false:N \chemmacros_nmr_frequency_bool
823     \bool_set_false:N \chemmacros_nmr_solvent_bool
824     \tl_if_empty:nF {#3}
825     { \bool_set_true:N \chemmacros_nmr_frequency_bool }
826     \tl_if_empty:nF {#4}
827     { \bool_set_true:N \chemmacros_nmr_solvent_bool }
828     \bool_if:nT
829     {
830       \chemmacros_nmr_frequency_bool
831       ||
832       \chemmacros_nmr_solvent_bool
833     }
834     { \bool_set_true:N \chemmacros_nmr_delimiters_bool }
835     \bool_if:nT
836     {

```

```

837         \l__chemmacros_nmr_frequency_bool
838         &&
839         \l__chemmacros_nmr_solvent_bool
840     }
841     { \bool_set_true:N \l__chemmacros_nmr_comma_bool }
842     \tl_if_empty:nTF {#2}
843     {
844         \__chemmacros_nmr_nucleus:VV
845         \l__chemmacros_nmr_isotope_default_tl
846         \l__chemmacros_nmr_element_default_tl
847     }
848     { \__chemmacros_nmr_nucleus:w #2 \q_stop }
849     \mode_if_math:TF
850     {
851         \text
852         {
853             \group_begin:
854             \tl_use:N \l__chemmacros_nmr_format_tl
855             \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
856             \__chemmacros_nmr_base:VV
857             \g__chemmacros_nmr_isotope_tl
858             \g__chemmacros_nmr_element_tl
859             \bool_if:NT \l__chemmacros_nmr_delimiters_bool
860             { ~ ( ) }
861             \bool_if:NT \l__chemmacros_nmr_frequency_bool
862             { \__chemmacros_nmr_frequency:n {#3} }
863             \bool_if:NT \l__chemmacros_nmr_comma_bool
864             { , ~ }
865             \bool_if:NT \l__chemmacros_nmr_solvent_bool
866             { \chemmacros_formula:n {#4} }
867             \bool_if:NT \l__chemmacros_nmr_delimiters_bool
868             { ) }
869             \tl_if_blank:nT {#1} {::~}
870 }}% lwarp
871         \group_end:
872     }
873     \tl_if_blank:nT {#1}
874     {
875         \delta
876         \text { \l__chemmacros_nmr_delta_tl }
877         \bool_if:NT \l__chemmacros_nmr_use_equal_bool {=}
878     }
879 }
880 {
881     \group_begin:
882     \tl_use:N \l__chemmacros_nmr_format_tl
883     \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
884     \__chemmacros_nmr_base:VV
885     \g__chemmacros_nmr_isotope_tl
886     \g__chemmacros_nmr_element_tl
887     \bool_if:NT \l__chemmacros_nmr_delimiters_bool
888     {~()}
889     \bool_if:NT \l__chemmacros_nmr_frequency_bool
890     { \__chemmacros_nmr_frequency:n {#3} }
891     \bool_if:NT \l__chemmacros_nmr_comma_bool
892     {,~}
893     \bool_if:NT \l__chemmacros_nmr_solvent_bool
894     {
895         \bool_if:NTF \l__chemmacros_nmr_parse_bool

```

```

896 %           { \chemformula_ch:nn { } {#4} }% original
897           {\ch{#4}}% lwarp
898           {#4}
899         }
900     \bool_if:NT \l__chemmacros_nmr_delimiters_bool
901         {}
902 }}% lwarp
903     \tl_if_blank:nT {#1} {:}
904     \group_end:
905     \tl_if_blank:nT {#1}
906     {
907         \tl_use:N \c_space_tl
908         \c_math_toggle_token
909         \delta
910         \c_math_toggle_token
911         \l__chemmacros_nmr_delta_tl
912         \bool_if:NT \l__chemmacros_nmr_use_equal_bool {~=}
913     }
914 }
915 \group_end:
916 }
917 }% AfterEndPreamble
918
919
920 \RenewDocumentCommand \chemmacros_data:w { smo }
921 {
922     \bool_if:NT \l__chemmacros_nmr_list_bool { \item }
923     {
924         \tl_use:N \l__chemmacros_nmr_format_tl #2
925         \tl_use:N \l__chemmacros_nmr_format_tl
926         \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
927             #2
928             \IfNoValueF {#3} { ~ ( #3 ) }
929             \IfBooleanT {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { : } }
930         }}% lwarp
931     }
932     \IfBooleanF {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { ~ = } }
933 }
934
935 }{}% Module loaded.
936 }% AtBeginDocument

```

§ 193.19 Thermodynamics

```

937 \AtBeginDocument{
938 \chemmacros_module_if_loaded:nTF{{thermodynamics}}{
939 \PackageInfo{lwarp}{Patching~chemmacros~module~thermodynamics}
940
941 \cs_gset_protected:Npn \chemmacros_state:nnnnn #1#2#3#4#5#6
942 {
943     \group_begin:
944     \chemmacros_set_keys:ne {thermodynamics}
945     {
946         \exp_not:n {#1} ,
947         \tl_if_novalue:nF {#2} { subscript-left = \exp_not:n {#2} , }
948         \tl_if_novalue:nF {#3} { superscript-left = \exp_not:n {#3} , }
949         \tl_if_novalue:nF {#5} { subscript-right = \exp_not:n {#5} , }
950         \tl_if_novalue:nF {#6} { superscript-right = \exp_not:n {#6} }
951     }
952     \LWR@subsingledollar*{% yes hashing

```

```

953     \textbackslash{}state%
954     {\LWR@HTMLsanitizeddetokenized{\detokenize{#4}}\}% alt
955   }{%
956     chemmacros_state% add'l hashing
957     #1% options
958     LSP \tl_use:N \l__chemmacros_state_sp_left_tl% super/subscripts
959     LSB \tl_use:N \l__chemmacros_state_sb_left_tl
960     RSP \tl_use:N \l__chemmacros_state_sp_right_tl
961     RSB \tl_use:N \l__chemmacros_state_sb_right_tl
962   }
963   {
964     \LWR@origensuredmath
965     {
966       \chemmacros_text:V \l__chemmacros_state_pre_tl
967       \c_math_superscript_token
968       { \chemmacros_text:V \l__chemmacros_state_sp_left_tl }

```

Only add the subscripts if they are being used. This avoids causing an incorrect depth, as the empty subscript will be measured by TeX but cropped out by *pdfcrop*.

```

969     \tl_if_empty:NTF \l__chemmacros_state_sb_left_tl
970     {}
971     {
972       \c_math_subscript_token
973       { \chemmacros_text:V \l__chemmacros_state_sb_left_tl }
974     }
975     #4
976     \c_math_superscript_token
977     { \chemmacros_text:V \l__chemmacros_state_sp_right_tl }
978     \tl_if_empty:NTF \l__chemmacros_state_sb_right_tl
979     {}
980     {
981       \c_math_subscript_token
982       { \chemmacros_text:V \l__chemmacros_state_sb_right_tl }
983     }
984     \chemmacros_text:V \l__chemmacros_state_post_tl
985   }
986 }
987 \group_end:
988 }
989 \cs_generate_variant:Nn \chemmacros_state:nnnnn { nVVVVV }
990
991 \cs_gset_protected:Npn \chemmacros_declare_state:Nn #1#2
992 {
993   \chemmacros_define_keys:xn
994     {thermodynamics/\chemmacros_remove_backslash:N #1}
995   {
996     pre      .meta:nn = {chemmacros/thermodynamics} { pre = ##1 } ,
997     post     .meta:nn = {chemmacros/thermodynamics} { post = ##1 } ,
998     superscript-left .meta:nn = {chemmacros/thermodynamics} { superscript-left = ##1 } ,
999     superscript-right .meta:nn = {chemmacros/thermodynamics} { superscript-right = ##1 } ,
1000    superscript      .meta:n  = { superscript-right = ##1 } ,
1001    subscript-left   .meta:nn = {chemmacros/thermodynamics} { subscript-left = ##1 } ,
1002    subscript-right  .meta:nn = {chemmacros/thermodynamics} { subscript-right = ##1 } ,
1003    subscript        .meta:n   = { subscript-left = ##1 } ,
1004    subscript-pos    .choices:nn =
1005      { left , right }
1006    { \tl_set_eq:NN \l__chemmacros_state_sb_pos_tl \l_keys_choice_tl } ,
1007    symbol           .tl_set:N = \l__chemmacros_state_symbol_tl ,
1008    unit            .tl_set:N = \l__chemmacros_state_unit_tl

```

```

1009     }
1010     \DeclareDocumentCommand #1 { sO{ }D( ) } m {
1011     {
1012         \group_begin:
1013         \chemmacros_set_keys:en
1014         {thermodynamics/\chemmacros_remove_backslash:N #1}
1015         {#2}
1016         \tl_if_blank:nF {##3}
1017         {
1018             \chemmacros_set_keys:ne {thermodynamics}
1019             { subscript-\l__chemmacros_state_sb_pos_tl = \exp_not:n {##3} }
1020         }
1021 %         \LWR@origensuredmath
1022 %         {
1023             \chemmacros_state:nVVVVV
1024             {##2}
1025             \c_novalue_tl
1026             \c_novalue_tl
1027             \l__chemmacros_state_symbol_tl
1028             \c_novalue_tl
1029             \c_novalue_tl
1030             \chemmacros_set_keys_groups:nnn {thermodynamics} {variables} {##2}
1031             \IfBooleanF {##1} { = \qty {##4} { \l__chemmacros_state_unit_tl } }
1032 %         }
1033     \group_end:
1034     }
1035 }

```

The pre-existing macros are redefined with the new definition:

```

1036 \RenewChemState \enthalpy { symbol = H , unit = \kilo\joule\per\mole }
1037 \RenewChemState \entropy { symbol = S , unit = \joule\per\kelvin\per\mole , pre = }
1038 \RenewChemState \gibbs { symbol = G , unit = \kilo\joule\per\mole }
1039
1040 }{ }% Module loaded.
1041 }% AtBeginDocument

1042 \ExplSyntaxOff

```

File 85 **lwarp-chemnum.sty**

§ 194 Package **chemnum**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemnum

chemnum is patched for use by **lwarp**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{chemnum}[2016/04/14]

2 \ExplSyntaxOn
3
4 \cs_gset_protected:Npn \chemnum_compound_write:n #1
5 {
6   \chemnum_get_compound_property:nn {#1} {pre-main-label-code}
7   \group_begin:
8     \bool_if:NTF \l__chemnum_compound_local_bool
9     { \l__chemnum_local_label_format_tl }

```

```

10     { \chemnum_get_compound_property:nn {#1} {label-format} }
11   {
12     \LWR@textcurrentfont{
13       \chemnum_get_compound_property:nn {#1} {counter-representation}
14     }
15   }
16   \group_end:
17   \chemnum_get_compound_property:nn {#1} {post-main-label-code}
18 }
19
20 \cs_gset_protected:Npn \chemnum_subcompound_write:nn #1#2
21 {
22   \group_begin:
23   \bool_if:NTF \l__chemnum_compound_local_bool
24     { \l__chemnum_local_label_format_tl }
25     { \chemnum_get_compound_property:nn {#1} {label-format} }
26   {
27     \LWR@textcurrentfont{
28       \chemnum_get_subcompound_property:nnn {#1} {#2}
29       {counter-representation}
30     }
31   }
32   \group_end:
33 }
34
35 \ExplSyntaxOff

```

File 86 **lwarp-chkfloat.sty**

§ 195 Package **chkfloat**

Pkg chkfloat

chkfloat is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{chkfloat}[2012/08/19]

File 87 **lwarp-chngpage.sty**

§ 196 Package **chngpage**

(Emulates or patches code by PETER WILSON.)

Pkg chngpage

chngpage is ignored.

for HTML output: Discard all options for lwarp-chngpage:

```

1 \LWR@ProvidesPackageDrop{chngpage}[2009/10/20]
2 \LWR@origRequirePackage{lwarp-chngpage}

```

File 88 **lwarp-cite.sty**

§ 197 Package **cite**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg cite

cite is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{cite}[2015/02/27]

For the [super] option, the \kern must be removed:

```
2 \def\LWRCT@biblabel#1{\@citess{#1}\kern-\labelsep\,}
3
4 \ifdefstrequal{\@biblabel}{\LWRCT@biblabel}
5 {
6   \def\@biblabel#1{\@citess{#1}}
7 }{}
```

For the [super] option, \textsuperscript is used instead of math superscript:

```
8 \def\@citess#1{\textsuperscript{#1}}
9
10 \DeclareDocumentCommand\citepunct{}{\, \, \relax}
```

File 89 **lwarp-citeref.sty**

§ 198 Package **citeref**

(Emulates or patches code by BJÖRN BRIEL.)

Pkg citeref

citeref is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{citeref}[1999/27/05]

```
2 \def\@cprwrite#1={%
3   \write\@auxout{\string\citepageref{#1}{\theLWR@previousautopagelabel}}%
4 }
5
6 \def\citepageref#1#2{%
7   \xdef\cpr@testa{\@nameuse{cpr@last@#1}}%letzte Zitatstelle
8   \xdef\cpr@testb{#2}% Seite dieser Zitatstelle
9   \ifx\cpr@testa\cpr@testb%
10    \relax% Konsekutive identische Seitenangaben weglassen
11   \else%
12     \namexdef{cpr@last@#1}{#2}%
13     \ifundefined{cpr@#1}%
14       {\@namexdef{cpr@#1}{\LWR@refwithsection{\BaseJobname-autopage-#2}}}% lwarp
15       {% lwarp
16         \@namexdef{cpr@#1}{\@nameuse{cpr@#1}, % space
17         \LWR@refwithsection{\BaseJobname-autopage-#2}}}%
18       }%
19   \fi
20 }
```

File 90 **lwarp-CJK.sty**

§ 199 Package **CJK**

Pkg CJK

CJK does not work with lwarp unless called from ctex.

for HTML output:

```

1 \IfPackageLoadedTF{xeCJK}{}{
2   \LWR@loadnever{CJK}{ctex, xeCJK}
3 }
4
5 \LWR@ProvidesPackagePass{CJK}[2015/04/18]
```

File 91 **lwarp-CJKutf8.sty**

§ 200 Package **CJKutf8**

Pkg CJKutf8

CJKutf8 does not work with lwarp unless called from ctex.

for HTML output:

```

1 \IfPackageLoadedTF{xeCJK}{}{
2   \LWR@loadnever{CJKutf8}{ctex, xeCJK}
3 }
4
5 \LWR@ProvidesPackagePass{CJKutf8}[2015/04/18]
```

File 92 **lwarp-classicthesis.sty**

§ 201 Package **classicthesis**

(Emulates or patches code by ANDRÉ MIEDE AND IVO PLETIKOSIĆ.)

Pkg classicthesis

classicthesis is emulated.

for HTML output: Discard all options for lwarp-classicthesis:

```

1 \LWR@ProvidesPackageDrop{classicthesis}[2018/06/03]

2 \RequirePackage{scrlayer-scrpage} % provides headers and footers (KOMA Script)
3 \RequirePackage{scrttime} % time access
4 \PassOptionsToPackage{titles}{tocloft}
5 \RequirePackage{textcase} % for \MakeTextUppercase
6 \RequirePackage[newparttoc]{titlesec} % newparttoc to write \part to .toc with \numberline
7 \RequirePackage{tocloft}
8 \PassOptionsToPackage{headinclude,footinclude}{typearea} % for classes other than KOMA
9 \RequirePackage{typearea}
10 \PassOptionsToPackage{marginal}{footmisc}% marginal flushmargin
11 \RequirePackage{footmisc}%
12 \RequirePackage{prelim2e}
13 \RequirePackage{remreset}%
14
15 \DeclareRobustCommand{\spacedallcaps}[1]{\textsc{\MakeTextUppercase{#1}}}
16 \DeclareRobustCommand{\spacedlowsmallcaps}[1]{\textsc{\MakeTextLowercase{#1}}}
17 \newcommand{\ctparttext}[1]{}
18 \newcommand{\tocEntry}[1]{}
19 \DeclareRobustCommand*{\deactivateaddvspace}{}%
20 \newlength{\beforebibsip}
```

File 93 **lwarp-cleveref.sty**

§ 202 Package **cleveref**

(Emulates or patches code by TOBY CUBITT.)

Pkg cleveref

cleveref is patched for HTML, and limited MATHJAX emulation is added.



cleveref page numbers

cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

Ex:

```
\cpageref{tab:first,tab:second}
in html becomes:
“pages for table 4.1 and for table 4.2”
```

See `\cpagerefFor` at page 730 to redefine the message which is printed for page number references.

Table 16 on page 491 shows the data structure of the label/reference system as revised by `lwarp` and `cleveref`.

For MATHJAX, each references is printed as an `\eqref`, without `cleveref`’s description text. Page references are also printed as simple `\eqrefs`. Multiple labels in a single `\cref` will print as (???) in MATHJAX.



multiple labels

for HTML output: 1 \LWR@ProvidesPackagePass{cleveref}[2018/03/27]

The following patches are applied. Print-mode versions are not required since they all come down to `\ref` eventually, and `\ref` has a print-mode version.

```
\@@@setcref {<kindofref>} {<label>}
```

`\@templabel` becomes the section number.

```
2 \def\LWR@orig@@@setcref#1#2{\cref@getlabel{#2}{\@templabel}#1{\@templabel}{}}%
3
4 \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% before v0.21
5   \renewcommand*{\@@@setcref}[2]{#1{\ref{#2}}{}}
6 }{
7   \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% as of v0.21
8     \renewcommand*{\@@@setcref}[2]{%
9       #1{\ref{#2}}{}}
10  }{
11    \PackageWarningNoLine{lwarp-cleveref}{
12      Unknown version of cleveref.
13      \protect\cref\space will fail.
14    }%
15  }
16 }
```

```
\@@@setcrefrange {<text>} {<label>} {<label>}
```

```

17 \def\LWR@orig@@setcrefrange#1#2#3{%
18   \cref@getlabel{#2}{\@labela}%
19   \cref@getlabel{#3}{\@labelb}%
20   #1{\@labela}{\@labelb}{\@labelc}{\@labeld}}%
21
22 \ifdefequal{\@@setcrefrange}{\LWR@orig@@setcrefrange}{
23   \renewcommand{\@@setcrefrange}[3]{%
24     #1{\ref{#2}}{\ref{#3}}{\@labelc}{\@labeld}}%
25   }
26 }{
27   \ifdefequal{\@@setcrefrange}{\LWR@orig@@setcrefrange}{
28     \renewcommand{\@@setcrefrange}[3]{%
29       #1{\ref{#2}}{\ref{#3}}{\@labelc}{\@labeld}}%
30     }
31   }{
32     \PackageWarningNoLine[lwarp-cleveref]{
33       Unknown version of cleveref.
34       \protect\crefrange\space will fail.
35     }
36   }
37 }

```

`\cpagerefFor` Redefinable word between “page(s)” and the page numbers.

```
38 \newcommand*{\cpagerefFor}{for}
```

`\@@setcpageref` `{\langle typeofref \rangle}{\langle label \rangle}`, where `typeofref` is “page” or “pages”

```

39 \def\LWR@orig@@setcpageref#1#2{% before v0.21
40   \cref@getpageref{#2}{\@temppage}#1{\@temppage}{\@label}}%
41
42 \def\LWR@orig@@setcpageref#1#2{% as of v0.21
43   \cpageref@getlabel{#2}{\@temppage}#1{\@temppage}{\@label}}%
44
45 \ifdefequal{\@@setcpageref}{\LWR@orig@@setcpageref}{
46   \renewcommand*{\@@setcpageref}[2]{%
47     #1{\cpagerefFor\ \cref{#2}}{\@label}}%
48   }
49 }{
50   \ifdefequal{\@@setcpageref}{\LWR@orig@@setcpageref}{
51     \renewcommand*{\@@setcpageref}[2]{%
52       #1{\cpagerefFor\ \cref{#2}}{\@label}}%
53     }
54   }
55   {
56     \PackageWarningNoLine[lwarp-cleveref]{
57       Unknown version of cleveref.
58       \protect\cpageref\space will fail.
59     }
60   }
61 }

62 \def\LWR@orig@@setcpagerefrange#1#2#3{% before v0.21
63   \cref@getpageref{#2}{\@pagea}%
64   \cref@getpageref{#3}{\@pageb}%
65   #1{\@pagea}{\@pageb}{\@labelc}{\@labeld}}%
66

```

```

67 \def\LWR@orig@@@setcpagerefrange#1#2#3{% as of v0.21
68   \cpageref@getlabel{#2}{\@pagea}%
69   \cpageref@getlabel{#3}{\@pageb}%
70   #1{\@pagea}{\@pageb}{\@pagec}{\@paged}%
71
72 \ifdefequal{\@@setcpagerefrange}{\LWR@orig@@setcpagerefrange}{
73   \renewcommand*\@@setcpagerefrange}[3]{%
74     #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{\@pagea}{\@pageb}%
75   }
76 }{
77   \ifdefequal{\@@@setcpagerefrange}{\LWR@orig@@@setcpagerefrange}{
78     \renewcommand*\@@@setcpagerefrange}[3]{%
79       #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{\@pagea}{\@pageb}{\@pagec}{\@paged}%
80     }
81   }
82   {
83     \PackageWarningNoLine{lwarp-cleveref}{
84       Unknown version of cleveref.
85       \protect\cpagerefrange\space will fail.
86     }
87   }
88 }

```

If `hyperref` is loaded, `cleveref` defines starred versions of the following, but since `hyperref` is only emulated, starred versions are defined here:

```

89 \LWR@absorbstar{cref}
90 \LWR@absorbstar{Cref}
91 \LWR@absorbstar{crefrange}
92 \LWR@absorbstar{Crefrange}
93 \LWR@absorbstar{cpageref}
94 \LWR@absorbstar{Cpageref}
95 \LWR@absorbstar{cpagerefrange}
96 \LWR@absorbstar{Cpagerefrange}
97 \LWR@absorbstar{labelcref}
98 \LWR@absorbstar{labelcpageref}

```

If `hyperref` is loaded, `cleveref` also defines starred versions of `varioref` macros, so they are defined here.

```

99 \IfPackageLoadedTF{varioref}{
100   \LWR@absorbstar{vref}
101   \LWR@absorbstar{Vref}
102   \LWR@absorbstar{vrefrange}
103   \LWR@absorbstar{Vrefrange}
104   \LWR@absorbstar{fullref}
105   \LWR@absorbstar{Fullref}
106 }{\}% varioref

107 \IfClassLoadedTF{memoir}{
108   \AtBeginDocument{
109     \def\sf@memsub@label(#1)#2{%
110       \protected@edef\mem@currentlabelname{#1}%
111       \sf@memsub@label{#2}}
112   }
113 }{}

114 \IfPackageLoadedTF{subfig}{

```

```

115 \def\sf@sub@label(#1)#2{%
116   \ifhyperrefloaded
117     \protected@edef\@currentlabelname{%
118       \expandafter\strip@period #1\relax.\relax\@@}%
119   \fi
120   \sf@@@sub@label{#2}}
121 }{}

```

File 94 **lwarp-clrdblpg.sty**

§ 203 Package **clrdblpg**

Pkg clrdblpg

clrdblpg is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{clrdblpg}[2018/04/21]

File 95 **lwarp-cmbright.sty**

§ 204 Package **cmbright**

Pkg cmbright

(Emulates or patches code by WALTER SCHMIDT.)

cmbright is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except `slantedGreek` is honored, and `\mathbold` is available.

The dedicated macros for upright Greek letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```

1 \LWR@ProvidesPackagePass{cmbright}[2005/04/13]
2
3 \LWR@infoprocessingmathjax{cmbright}

4 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
5
6 \begin{warpMathJax}
7
8 \IfPackageLoadedWithOptionsTF{cmbright}{slantedGreek}
9 {
10   \LWR@mathjax@addgreek@u@it*{}{}
11 }
12 {}
13
14 \LWR@mathjax@addgreek@u@up*{up}{}
15
16 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
17
18 \end{warpMathJax}

```

File 96 **lwarp-cmdtrack.sty**

§ 205 Package **cmdtrack**

Pkg cmdtrack

cmdtrack is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{cmdtrack}[2012/12/18]

2 \newcommand{\untrack}[1]{}

```

File 97 **lwarp-colonequals.sty**

§ 206 Package **colonequals**

Pkg colonequals

(Emulates or patches code by HEIKO OBERDIEK.)

colonequals is used as-is for SVG math, and is emulated for MATHJAX.

Since UNICODE symbols are not available for each of the following, only two are used for the single and double colons, and the other symbols are derived in a consistent manner. Occasional negative space is added as well. This may need to be undone for some fonts.

for HTML output:

```

1 \LWR@ProvidesPackagePass{colonequals}[2016/05/16]

2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{colonequals}
4
5 \CustomizeMathJax{\newcommand{\ratio}{\mathrel{\unicode{x2236}}}}
6 \CustomizeMathJax{\newcommand{\coloncolon}{\mathrel{\unicode{x2237}}}}
7 \CustomizeMathJax{\newcommand{\colonequals}{\mathrel{\unicode{x2236}\! =}}}
8 \CustomizeMathJax{\newcommand{\coloncolonequals}{\mathrel{\unicode{x2237}\! =}}}
9 \CustomizeMathJax{\newcommand{\equalscolon}{\mathrel{=!\unicode{x2236}}}}
10 \CustomizeMathJax{\newcommand{\equalscoloncolon}{\mathrel{=!\unicode{x2237}}}}
11 \CustomizeMathJax{\newcommand{\colonminus}{\mathrel{\unicode{x2236}-}}}
12 \CustomizeMathJax{\newcommand{\coloncolonminus}{\mathrel{\unicode{x2237}-}}}
13 \CustomizeMathJax{\newcommand{\minuscoloncolon}{\mathrel{-\unicode{x2236}}}}
14 \CustomizeMathJax{\newcommand{\minuscoloncolon}{\mathrel{-\unicode{x2237}}}}
15 \CustomizeMathJax{\newcommand{\colonapprox}{\mathrel{\unicode{x2236}\! \approx}}}
16 \CustomizeMathJax{\newcommand{\coloncolonapprox}{\mathrel{\unicode{x2237}\! \approx}}}
17 \CustomizeMathJax{\newcommand{\approxcolon}{\mathrel{\approx\! \unicode{x2236}}}}
18 \CustomizeMathJax{\newcommand{\approxcoloncolon}{\mathrel{\approx\! \unicode{x2237}}}}
19 \CustomizeMathJax{\newcommand{\colonsim}{\mathrel{\unicode{x2236}\! \sim}}}
20 \CustomizeMathJax{\newcommand{\coloncolonsim}{\mathrel{\unicode{x2237}\! \sim}}}
21 \CustomizeMathJax{\newcommand{\simcolon}{\mathrel{\sim!\unicode{x2236}}}}
22 \CustomizeMathJax{\newcommand{\simcoloncolon}{\mathrel{\sim!\unicode{x2237}}}}
23 \end{warpMathJax}

```

File 98 **lwarp-color.sty**§ 207 Package **color**

Pkg color

Allowed but ignored. `xcolor` is then required as well.

`color` is superceded by `xcolor`, and `lwarp` requires several of the features of `xcolor`. When `color` is requested, `xcolor` is loaded as well.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{color}[2016/07/10]
2 \RequirePackage{xcolor}
```

`\color@endgroup's \endgraf` was conflicting with `lwarp's` paragraph handling.

```
3 \let\color@endgroup\endgroup
```

File 99 **lwarp-colortbl.sty**§ 208 Package **colortbl**

Pkg colortbl

`colortbl` is used as-is for print output, and emulated for HTML.

 **row/cell color** Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.

`colortbl` ignores the overhang arguments.

for HTML output: A placeholder definition is forgotten first:

```
1 \let\rowcolor\relax
2
3 \LWR@ProvidesPackagePass{colortbl}[2018/12/12]
```

The following `\LWR@HTML` versions are used inside an HTML tabular.

```
[<model>] {<color>} [<left overhang>] [<right overhang>]
```

`\LWR@getmynexttoken` is not used here because `\columncolor` is not used inside the data area of the tabular.

`\columncolor` is provided here to satisfy `\LWR@formatted's` test for the existence of the print-mode macro.

```
4 \ProvideDocumentCommand{\columncolor}{O{named} m o o}{%
5
6 \NewDocumentCommand{\LWR@HTML@columncolor}{O{named} m o o}{%
7   \convertcolorspec{#1}{#2}{HTML}\LWR@columnHTMLcolor%
8   \LWR@addtabularcellcolor%
9 }
10
11 \AtBeginDocument{\LWR@formatted{columncolor}}
```

`\LWR@getmynexttoken` is used for `\rowcolor` because it is used inside the data area of the tabular.

`\columncolor`

`\rowcolor` [*model*] {*color*} [*left overhang*] [*right overhang*]

```
12 \NewDocumentCommand{\LWR@HTML@rowcolor}{O{named} m o o}{%
13   \convertcolorspec{#1}{#2}{HTML}\LWR@rowHTMLcolor%
14   \LWR@getmynexttoken%
15 }
16
17 \AtBeginDocument{\LWR@expandableformatted{rowcolor}}
```

`\cellcolor` [*model*] {*color*} [*left overhang*] [*right overhang*]

```
18 \NewDocumentCommand{\LWR@HTML@cellcolor}{O{named} m o o}{%
19   \convertcolorspec{#1}{#2}{HTML}\LWR@cellHTMLcolor%
20   \LWR@addtabularcellcolor%
21 }
22
23 \AtBeginDocument{\LWR@formatted{cellcolor}}
```

`\arrayrulecolor` [*model*] {*color*}

The HTML version for use outside a tabular. Inside a tabular, `\LWR@HTML@arrayrulecolornexttoken` is used instead.

```
24 \newcommand{\LWR@HTML@arrayrulecolor}[2][named]{%
25   \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
26 }
27
28 \AtBeginDocument{\LWR@expandableformatted{arrayrulecolor}}
```

[*model*] {*color*}

`\LWR@arrayrulecolornexttoken` The HTML version for use inside a tabular.

```
29 \newcommand{\LWR@HTML@arrayrulecolornexttoken}[2][named]{%
30   \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
31   \LWR@getmynexttoken%
32 }
33
34 \AtBeginDocument{\LWR@expandableformatted{arrayrulecolornexttoken}}
```

`\doublerulesepcolor` [*model*] {*color*}

The version for use outside a tabular.

```
35 \newcommand{\LWR@HTML@doublerulesepcolor}[2][named]{%
36
37 \AtBeginDocument{\LWR@expandableformatted{doublerulesepcolor}}
```

[*model*] {*color*}

`\LWR@doublerulesepcolornexttoken` The version for use inside a tabular.

```
38 \newcommand{\LWR@HTML@doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}
39
40 \AtBeginDocument{\LWR@expandableformatted{doublerulesepcolornexttoken}}
```

For MATHJAX, use the MATHJAX package. The unused macro options are ignored.

```
41 \begin{warpMathJax}
```

```

42
43 \CustomizeMathJax{\require{colortbl}}
44 \CustomizeMathJax{\let\LWRorigcolumnncolor\columnncolor}
45 \CustomizeMathJax{\renewcommand{\columnncolor}[2][named]{%
46   \LWRorigcolumnncolor[#1]{#2}%
47   \LWRabsorbtwooptions%
48 }}
49
50 \CustomizeMathJax{\let\LWRorigrowcolor\rowcolor}
51 \CustomizeMathJax{\renewcommand{\rowcolor}[2][named]{%
52   \LWRorigrowcolor[#1]{#2}%
53   \LWRabsorbtwooptions%
54 }}
55
56 \CustomizeMathJax{\let\LWRorigcellcolor\cellcolor}
57 \CustomizeMathJax{\renewcommand{\cellcolor}[2][named]{%
58   \LWRorigcellcolor[#1]{#2}%
59   \LWRabsorbtwooptions%
60 }}
61
62 \end{warpMathJax}

```

File 100 **lwarp-continue.sty**

§ 209 Package **continue**

Pkg continue

continue is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{continue}[2018/12/09]

```

2 \newcommand*{\flagcont}{}
3 \newcommand*{\flagend}{}
4 \newcommand*{\flagword}{}
5 \newcommand*{\preflagword}{}
6 \newcommand*{\postflagword}{}
7 \newlength\contsep
8 \newlength\contdrop

```

File 101 **lwarp-copyrightbox.sty**

§ 210 Package **copyrightbox**

(Emulates or patches code by THOMAS FISCHER, IVES VAN DER FLAAS.)

Pkg copyrightbox

copyrightbox is emulated for use by lwarp.

The entire copyright box is placed inside a <div> of class copyrightbox.

The contents are placed inside a <div> of class copyrightboxcontents.

The copyright notice is placed inside a <div> of class copyrightboxnote.

for HTML output: 1 \LWR@ProvidesPackageDrop{copyrightbox}[2011/11/27]

```

2 \newcommand{\copyrightbox}[3][r]{%
3 \begin{BlockClass}[
4   display: inline-flex;
5   flex-direction: column ;
6 ]{\copyrightbox}
7 \begin{BlockClass}{copyrightboxcontents}
8 #2
9 \end{BlockClass}
10 \begin{BlockClass}{copyrightboxnote}
11 #3
12 \end{BlockClass}
13 \end{BlockClass}
14 }
15
16 \newcommand{\CRB@setcopyrightfont}{}
17 \newcommand{\CRB@setcopyrightparagraphstyle}{}

```

File 102 **lwarp-crop.sty**

§ 211 Package **crop**

(Emulates or patches code by MELCHIOR FRANZ.)

Pkg crop

crop is ignored.

for HTML output: Discard all options for lwarp-crop:

```

1 \LWR@ProvidesPackageDrop{crop}[2003/05/20]
2 \newcommand*{\crop}[1][{}]{
3 \newcommand*{\cropdef}[6][{}]{

```

File 103 **lwarp-ctable.sty**

§ 212 Package **ctable**

(Emulates or patches code by WYBO DEKKER.)

Pkg ctable

ctable is patched for use by lwarp.

 **Misplaced alignment tab character &** Use `\StartDefiningTabulars` before one or more `\ctables`, and `\StopDefiningTabulars` after. These change the meaning of the ampersand `&` character.

for HTML output: 1 \LWR@ProvidesPackagePass{ctable}[2015/10/17]

The following is in the original:

```

2 \newcommand{\LWR@HTML@ctable}[4][{}]{%
3   \let\@CTtaborfig \@dfltCTtaborfig
4   \let\@CTalign \@dfltCTalign
5   \let\@CTsideways \@dfltCTsideways
6   \let\@CTcontinued \empty
7   \let\@CTpos \@dfltCTpos
8   \let\@CTcaption \empty

```

```

9   \let\@CTcap      \undefined
10  \let\@CTlabel    \empty
11  \let\@CTbotcap   \@df\CTbotcap
12  \let\@CTstarred  \@df\CTstarred
13  \let\@CTsuper    \@df\CTsuper
14  \let\@CTnotespar \@df\CTnotespar
15  \let\@CTdoinside \@df\CTdoinside
16  \let\@CTbgopacity \@df\CTbgopacity
17  \@CTframerule    \@df\CTframerule
18  \@CTcaptionskip  \@df\CTcaptionskip
19  \@CTframesep     \@df\CTframesep
20  \@CTwidth        \@df\CTwidth
21  \@CTmaxwidth     \@df\CTmaxwidth
22  \@CTmincapwidth  \@df\CTmincapwidth
23  \@CTfooterwidth  \@df\CTfooterwidth
24  \def\@CTfgactual {\@df\CTframefg}%
25  \def\@CTbgactual {\@df\CTframebg}%
26  \def\@CTbeg      {\begin{\@CTsideways\@CTtaborfig\@CTstarred}}%
27  \def\@CTbegin    {\@CTbeg}%
28  \def\@CTend      {\end{\@CTsideways\@CTtaborfig\@CTstarred}}%
29  \setkeys{CT}{#1}%
30  \ifx\@CTcap\undefined\let\@CTcap\@CTcaption\fi
31  \ifx\@CTcap\empty
32    \if@CTcaptionloaded\else
33      \PackageWarningNoLine{lwarp-ctable}{\MessageBreak
34        An empty cap= option prevents lot/loc entry only\MessageBreak
35        if the caption package is loaded!}
36    \fi
37  \fi
38  \if@CTinmemoir\else
39    \ifx\@CTbotcap\undefined
40      \PackageError{lwarp-ctable}{\MessageBreak
41        You can, currently, use the sidecap option only with\MessageBreak
42        memoir documents. Use topcap or botcap only}
43    {}
44  \fi
45  \fi
46  \ifdim\@CTwidth=0pt\else
47    \ifdim\@CTmaxwidth=0pt\else
48      \PackageError{lwarp-ctable}{\MessageBreak
49        You may not use the width and maxwidth options together\MessageBreak
50        Use either width or maxwidth}
51    {}
52  \fi
53  \fi
54  \ifx\@CTpos\empty
55    \ifx\@CTsideways\empty\else
56      \PackageError{lwarp-ctable}{\MessageBreak
57        You may not use the pos and sideways options together\MessageBreak
58        Rotated tables and figures are always typeset on a separate page}
59    {}
60  \fi
61  \fi
62  \ifx\@CTcaption\empty
63    \ifx\@CTlabel\empty\else
64      \PackageError{lwarp-ctable}{\MessageBreak
65        You may not label a captionless table\MessageBreak
66        Such a label can't be referenced}
67    {}
68  \fi

```

69 \fi

Some of the original, regarding computing the width of \CT@t, is removed here.

```
70 \CTbegin
71 \ifx\CTcontinued\empty\else\addtocounter{\CTtaborfig}{-1}\fi
72 \CTalign
```

lwarp's patches begin here:

```
73 \begin{center}
74 \setlength{\fboxrule}{\CTframerule}
75 \setlength{\fboxsep}{\CTframesep}
76 \LWR@forceminwidth{\fboxrule}% lwarp
77 \convertcolorspec{named}{\CTbgactual}{HTML}\LWR@tempcolor% lwarp
78 \begin{BlockClass}% lwarp
79 border:
80 \LWR@printlength{\LWR@atleastonept}
81 solid
82 \LWR@colorstyle{named}{\CTfgactual} ; %
83 padding:\LWR@printlength{\fboxsep} ; %
84 \ifdefstring{\LWR@tempcolor}{FFFFFF}{}%
85 background: \LWR@colorstyle{named}{\CTbgactual} ; %
86 }%
87 ]{fminipage}% lwarp
88 \ifx\CTbotcap\CTfalse\CTCaption\vskip\CTcaptionskip\fi
89 \ifx\CTbotcap\undefined%
90 \begin{sidecaption}[\CTcap]{\CTcaption}[\CTlabel]
91 \fi
92 \CTdoinside
93 \begin{tabularx}{\linewidth}{#2}% lwarp
94 #4%
95 \end{tabularx}% lwarp
96 \def\CTfootnotes{#3}%
97 \ifx#3\empty\else{% append footnotes, if any
98 \begin{BlockClass}{tnotes}% lwarp
99 #3
100 \end{BlockClass}% lwarp
101 }
102 \fi
103 \ifx\CTbotcap\undefined\end{sidecaption}\fi
104 \ifx\CTbotcap\CTtrue\vskip\CTcaptionskip\CTCaption\fi
105 \end{BlockClass}
106 \end{center}
107 \CTend
108 }
109 \LWR@formatted{ctable}
```

Required to properly detect the toprule:

```
110 \LetLtxMacro\FL\toprule
```

Table notes are redefined for HTML:

```
111 \newcommand{\LWR@HTML@tmark}[1][a]{%
112 \textsuperscript{\textrm{\textit{#1}}}}
113 }
114 \LWR@formatted{tmark}
115
```

```

116 \newcommand{\LWR@HTML@tnote}[2][a]{%
117   \tmark[#1]\,#2\par
118 }
119 \LWR@formatted{tnote}

```

File 104 **lwarp-cuted.sty**

§ 213 Package **cuted**

(Emulates or patches code by SIGITAS TOLUŠIS.)

Pkg cuted

cuted is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{cuted}[2021/10/04]

2 \newenvironment{strip}{}{}
3 \newskip\stripsep
4 \newtoks\preCutedStrip \preCutedStrip{}
5 \newtoks\postCutedStrip \postCutedStrip{}
6 \def\oldcolsbreak#1{}

```

File 105 **lwarp-cutwin.sty**

§ 214 Package **cutwin**

(Emulates or patches code by PETER WILSON AND ALAN HOENIG.)

Pkg cutwin

cutwin is emulated.

for HTML output: Discard all options for lwarp-cutwin:

```

1 \LWR@ProvidesPackageDrop{cutwin}[2010/09/29]

2 \newcommand*\opencutleft{}
3 \newcommand*\opencutright{}
4 \newcommand*\opencutcenter{}
5 \newcommand*\cutfuzz{}
6
7 \newenvironment{cutout}[4]
8 {\marginpar{\windowpagestuff}}
9 {}
10
11 \newcommand*\windowpagestuff{}
12
13 \newcommand*\pageinwindow{%
14 % \begin{minipage}{.3\linewidth}
15 \windowpagestuff
16 % \end{minipage}
17 }
18
19 \newenvironment{shapedcutout}[3]
20 {\marginpar{\picinwindow}}
21 {}
22

```

```

23 \newcommand*\putstuffinpic{}
24
25 \newcommand*\picinwindow{%
26 \begin{picture}(0,0)
27 \putstuffinpic
28 \end{picture}}

```

File 106 **lwarp-dblfloatfix.sty**

§ 215 Package **dblfloatfix**

Pkg dbfloatfix dbfloatfix is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{dblfloatfix}[2012/12/31]

File 107 **lwarp-dblfnote.sty**

§ 216 Package **dblfnote**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg dbfnote dbfnote is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{dblfnote}[1999/07/14]

```

2 \newcounter{DFNsloppiness}
3 \newdimen\DFNcolumnsep
4 \newdimen\DFNcolumnwidth
5 \def\DFNallowcbreak{}
6 \def\DFNinhibitcbreak{}
7 \def\DFNtrysingle{}
8 \def\DFNalwaysdouble{}
9 \def\DFNruleboth{}
10 \def\DFNruleleft{}

```

File 108 **lwarp-dcolumn.sty**

§ 217 Package **dcolumn**

Pkg dcolumn dcolumn is used as-is in a lateximage, and is emulated by the lwarp core.

dcolumn used to be \LWR@ProvidesPackageDrop in prior versions of lwarp, but is now supported for print mode.

1 \LWR@ProvidesPackagePass{dcolumn}[2014/10/28]

Due to how the D column is created, cannot use \HTMLnewcolumn type here. An HTML version neutralizes the lower-level macros, leaving a c column type.

```

2 \newcommand*\LWR@HTML@DC@}[3]{}

```

```

3 \LWR@formatted{DC@}
4
5 \providecommand*\DC@end{}
6
7 \newcommand*\LWR@HTML@DC@end{}
8 \LWR@formatted{DC@end}

```

File 109 **lwarp-decimal.sty**

§ 218 Package **decimal**

(Emulates or patches code by A. SYROPOULOS AND R. W. D. NICKALLS.)

Pkg decimal

decimal works as-is for SVG math, and is emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{decimal}[2011/06/03]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\def\.\{\mbox{.}\}}
4 \end{warpMathJax}

```

File 110 **lwarp-decorule.sty**

§ 219 Package **decorule**

(Emulates or patches code by PETER FLYNN.)

Pkg decorule

decorule is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{decorule}[2020/04/01]

2 \xpretocmd{\decorule}
3   {\begin{lateximage}*{decorule}}
4   {}
5   {\LWR@patcherror{decorule}{decorule A}}
6
7 \xapptocmd{\decorule}
8   {\end{lateximage}}
9   {}
10  {\LWR@patcherror{decorule}{decorule B}}

```

File 111 **lwarp-diagbox.sty**

§ 220 Package **diagbox**

(Emulates or patches code by LEO LIU.)

Pkg diagbox

diagbox is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{diagbox}[2016/12/28]

```

To restore print-mode inside a lateximage:

```

2 \LetLtxMacro\LWR@origdiagbox@double\diagbox@double
3 \LetLtxMacro\LWR@origdiagbox@triple\diagbox@triple
4
5 \appto\LWR@restoreorigformatting{%
6 \LetLtxMacro\diagbox@double\LWR@origdiagbox@double%
7 \LetLtxMacro\diagbox@triple\LWR@origdiagbox@triple%
8 }

```

\LWR@diagbox@AB

```

{\langle E/W \rangle} {\langle A \rangle} {\langle E/W \rangle} {\langle B \rangle}
9 \newcommand{\LWR@diagbox@AB}[4]{
10 \begingroup%
11 \LetLtxMacro\\\newline%
12 \BlockClassSingle{diagbox#1}{#2}%
13 \BlockClassSingle{diagbox#3}{#4}%
14 \endgroup%
15 \LWR@stoppars%
16 }

```

\LWR@diagboxNW

```

{\langle A \rangle} {\langle B \rangle}
17 \newcommand{\LWR@diagboxNW}[2]{%
18 \LWR@diagbox@AB{E}{#2}{W}{#1}%
19 }

```

Likewise for NE, SW, SE:

```

20 \newcommand{\LWR@diagboxNE}[2]{%
21 \LWR@diagbox@AB{W}{#1}{E}{#2}%
22 }
23
24 \let\LWR@diagboxSW\LWR@diagboxNE
25 \let\LWR@diagboxSE\LWR@diagboxNW

```

\diagbox@double

```

{\langle keys \rangle} {\langle A \rangle} {\langle B \rangle}
26 \def\diagbox@double#1#2#3{%
27 \setkeys{diagbox}{dir=NW,#1}%
28 \nameuse{LWR@diagbox\diagbox@dir}{#2}{#3}%
29 }

```

\LWR@diagboxTNW

```

{\langle title \rangle} {\langle A \rangle} {\langle B \rangle}
30 \newcommand{\LWR@diagboxTNW}[3]{%
31 \BlockClassSingle{diagboxtitleN}{#1}
32 \LWR@diagboxNW{#2}{#3}
33 }

```

Likewise for NE, SW, SE:

```

34 \newcommand{\LWR@diagboxTNE}[3]{%
35 \BlockClassSingle{diagboxtitleN}{#1}
36 \LWR@diagboxNE{#2}{#3}
37 }
38
39 \newcommand{\LWR@diagboxTSW}[3]{%

```

```

40 \LWR@diagboxSW{#2}{#3}
41 \BlockClassSingle{diagboxtitleS}{#1}
42 \LWR@stoppars%
43 }
44
45 \newcommand{\LWR@diagboxTSE}[3]{%
46 \LWR@diagboxSE{#2}{#3}
47 \BlockClassSingle{diagboxtitleS}{#1}
48 \LWR@stoppars%
49 }

```

\diagbox@triple

```

{<keys> } {<A>} {<T>} {<B>}

50 \def\diagbox@triple#1#2#3#4{%
51 \setkeys{diagbox}{dir=NW,#1}%
52 \@nameuse{LWR@diagboxT\diagbox@dir}{#3}{#2}{#4}%
53 }

```

File 112 **lwarp-dingbat.sty**§ 221 Package **dingbat***(Emulates or patches code by SCOTT PAKIN.)*

Pkg dingbat

dingbat is patched for use by **lwarp**.**for HTML output:**

```

1 \LWR@ProvidesPackagePass{dingbat}[2001/04/27]

2 \newcommand*{\LWR@dingbatsymbol}[1]{\HTMLunicode{#1}}
3
4 \newcommand{\LWR@HTML@rightpointright}{\LWR@dingbatsymbol{261E}}
5 \newcommand{\LWR@HTML@leftpointright}{\LWR@dingbatsymbol{261E}}
6 \newcommand{\LWR@HTML@leftthumbsdown}{\LWR@dingbatsymbol{1F44E}}
7 \newcommand{\LWR@HTML@leftthumbsup}{\LWR@dingbatsymbol{1F44D}}
8 \newcommand{\LWR@HTML@rightpointleft}{\LWR@dingbatsymbol{261C}}
9 \newcommand{\LWR@HTML@rightthumbsdown}{\LWR@dingbatsymbol{1F44E}}
10 \newcommand{\LWR@HTML@rightthumbsup}{\LWR@dingbatsymbol{1F44D}}
11 \newcommand{\LWR@HTML@squarewithdots}{\LWR@dingbatsymbol{25C7}}
12 \newcommand{\LWR@HTML@filledsquarewithdots}{\LWR@dingbatsymbol{25C6}}
13 \newcommand{\LWR@HTML@Sborder}{\LWR@dingbatsymbol{271A}}
14 \newcommand{\LWR@HTML@Zborder}{\LWR@dingbatsymbol{274B}}
15 \newcommand{\LWR@HTML@largepencil}{\LWR@dingbatsymbol{270E}}
16 \newcommand{\LWR@HTML@anchor}{\LWR@dingbatsymbol{2693}}
17 \newcommand{\LWR@HTML@carriereturn}{\LWR@dingbatsymbol{23CE}}
18 \newcommand{\LWR@HTML@checkmark}{\LWR@dingbatsymbol{2713}}
19 \newcommand{\LWR@HTML@eye}{\LWR@dingbatsymbol{1F441}}
20 \newcommand{\LWR@HTML@satellitedish}{\LWR@dingbatsymbol{1F4E1}}
21 \newcommand{\LWR@HTML@smallpencil}{\LWR@dingbatsymbol{270E}}
22
23 \LWR@formatted{rightpointright}
24 \LWR@formatted{leftpointright}
25 \LWR@formatted{leftthumbsdown}
26 \LWR@formatted{leftthumbsup}
27 \LWR@formatted{rightpointleft}
28 \LWR@formatted{rightthumbsdown}
29 \LWR@formatted{rightthumbsup}
30 \LWR@formatted{squarewithdots}

```

```

31 \LWR@formatted{filledsquarewithdots}
32 \LWR@formatted{Sborder}
33 \LWR@formatted{Zborder}
34 \LWR@formatted{largepencil}
35 \LWR@formatted{anchor}
36 \LWR@formatted{carriagereturn}
37 \LWR@formatted{checkmark}
38 \LWR@formatted{eye}
39 \LWR@formatted{satellitedish}
40 \LWR@formatted{smallpencil}

```

File 113 **lwarp-DotArrow.sty**

§ 222 Package **DotArrow**

(Emulates or patches code by SVEN SCHNEIDER.)

Pkg DotArrow

DotArrow is patched for use by lwarp, and emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{DotArrow}[2007/02/12]

The width must be recomputed each time, depending on print or HTML output.

```

2 \xpretocmd{\dotarrow}{\settowidth{\oneWidth}{\onePartX}}{}{}
3
4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\dotarrow}[1]{\stackrel{\#1}{\unicode{x21E2}}}}
6 \end{warpMathJax}

```

File 114 **lwarp-dotlessi.sty**

§ 223 Package **dotlessi**

(Emulates or patches code by JAVIER BEZOS.)

Pkg dotlessi

dotlessi is used as-is for SVG math, and is emulated for MATHJAX.

 **HTML \dotlessj** Use `\usepackage{cmap}` if `\dotlessj` does not appear in HTML in text mode. See section 7.4.

 **not bold** For MATHJAX, use `\boldsymbol` instead of `\mathbf`.

for HTML output: 1 \LWR@ProvidesPackagePass{dotlessi}[1999/10/12]

For MATHJAX:

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\let\dotlessi\imath}
4 \CustomizeMathJax{\let\dotlessj\jmath}
5 \end{warpMathJax}

```

File 115 **lwarp-dprogress.sty**

§ 224 Package **dprogress**

Pkg dprogress

dprogress is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{dprogress}[2008/02/21]

File 116 **lwarp-draftcopy.sty**

§ 225 Package **draftcopy**

Pkg draftcopy

draftcopy is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{draftcopy}[2002/02/25]

```

2 \newcommand{\draftcopyVersion}[1]{}
3 \newcommand{\draftcopySetGrey}[1]{}
4 \newcommand{\draftcopySetScale}[1]{}
5 \newcommand{\draftcopySetScaleFactor}[1]{}
6 \newcommand{\draftcopyFirstPage}[1]{}
7 \newcommand{\draftcopyLastPage}[1]{}
8 \newcommand{\draftcopyName}[2]{}
9 \newcommand{\draftcopyPageTransform}[1]{}
10 \newcommand{\draftcopyBottomTransform}[1]{}
11 \newcommand{\draftcopyPageX}[1]{}
12 \newcommand{\draftcopyPageY}[1]{}
13 \newcommand{\draftcopyBottomX}[1]{}
14 \newcommand{\draftcopyBottomY}[1]{}

```

File 117 **lwarp-draftfigure.sty**

§ 226 Package **draftfigure**

Pkg draftfigure

draftfigure is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{draftfigure}[2017/07/19]
2 \RequirePackage{xkeyval}

```

3 \define@key{draftfigure}{code}{}
4 \define@key{draftfigure}{noframe}[true]{}
5 \define@key{draftfigure}{filename}[true]{}
6 \define@key{draftfigure}{content}[]{}
7 \define@key{draftfigure}{style}[normal]{}
8 \define@key{draftfigure}{position}[left]{}
9 \define@key{draftfigure}{size}[normal]{}
10 \newcommand\setdf[1]{\setkeys{draftfigure}{#1}}

```

File 118 **lwarp-draftwatermark.sty**

§ 227 Package **draftwatermark**

(Emulates or patches code by SERGIO CALLEGARI.)

Pkg draftwatermark **draftwatermark is ignored.**

for HTML output:

```

1 \LWR@ProvidesPackageDrop{draftwatermark}[2020/03/14]

2 \newcommand{\DraftwatermarkOptions}[1]{}
3 \newcommand{\DraftwatermarkStdMark}{}
4 \newcommand{\SetWatermarkAngle}[1]{}
5 \newcommand{\SetWatermarkColor}[1]{}
6 \newcommand{\SetWatermarkLightness}[1]{}
7 \newcommand{\SetWatermarkFontSize}[1]{}
8 \newcommand{\SetWatermarkScale}[1]{}
9 \newcommand{\SetWatermarkHorCenter}[1]{}
10 \newcommand{\SetWatermarkVertCenter}[1]{}
11 \newcommand{\SetWatermarkText}[1]{}

```

File 119 **lwarp-drftcite.sty**

§ 228 Package **drftcite**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg drftcite **drftcite is patched for use by lwarp.**

for HTML output:

```

1 \LWR@ProvidesPackagePass{drftcite}[1995/01/23]

2 \def\@lbibitem[#1]#2{\global\@HighCite\z@
3 \item[
4 \textsuperscript{\@nameuse{DCN@#2\@extra@b@citeb}}~% lwarp
5 \@biblabel{\@ifundefined{DCN@#2\@extra@b@citeb}{\@warning
6 {Reference ‘#2’ on page \thepage\space was never cited}}}%
7% \DC@llap{$^\@nameuse{DCN@#2\@extra@b@citeb}}$\ \ }%o
8 \@citeverb{#2}}\hfil]\if@filesw{\def\protect##1{\string ##1\space}%
9 \immediate\write\@auxout{\string\bibcite{#2}{#1}}}\fi\ignorespaces}

```

File 120 **lwarp-easy-todo.sty**

§ 229 Package **easy-todo**

(Emulates or patches code by JUAN RADA-VILELA.)

Pkg easy-todo **easy-todo is patched for use by lwarp.**

To remove the “P.” heading for HTML:

```
\warpHTMLOnly{\renewcommand{\todoindexpagetitle}{}}
```

for HTML output: 1 \LWR@ProvidesPackagePass{easy-todo}[2014/01/01]

\listoftodos

Modified to correct buggy use of \flushright.

```
2 \let\LWR@easytodo@origlistoftodos\listoftodos
3
4 \renewcommand{\listoftodos}{%
5 \begingroup
6 \renewcommand{\flushright}{}
7 \LWR@easytodo@origlistoftodos
8 \endgroup
9 }
```

\todoii

Modified to use \textcolor instead of \color.

```
10 \renewcommand{\todoii}[2]{%
11 \ifthenelse{\equal{\@todoobeyfinal}{true}}%
12   {%
13     \ifoptionfinal{\todoenable{false}}{\todoenable{true}}%
14   }%
15   {%
16 \ifthenelse{\equal{\@todoenable}{true}}%
17   {%
18     \refstepcounter{todos}%
19     \noindent{%
20       \todocolor%
21       \LWR@textcurrentcolor{%
22         \normalfont\scriptsize\bfseries{\thetodos.#1}}%
23       }%
24     }%
25     \addcontentsline{lod}{todos}{\protect{\thetodos. }\LWR@isolate{#2}}%
26   }%
27   {%
28 }
```

File 121 **lwarp-ebook.sty**

§ 230 Package **ebook**

(Emulates or patches code by JØRGEN STEENSGAARD.)

Pkg ebook

ebook is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{ebook}

2 \setcounter{secnumdepth}{0}
3 \setcounter{tocdepth}{2}
4
5 \providecommand{\pagefilll}[1][0.001mm]{\noindent}
6
7 \providecommand{\ebook}{
8 \setcounter{secnumdepth}{0}
9 \setcounter{tocdepth}{2}
10 }
```

File 122 **lwarp-econometrics.sty**

§ 231 Package **econometrics**

(Emulates or patches code by ERIK KOLE.)

Pkg econometrics

econometrics is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{econometrics}% no date specified in the original
2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{econometrics}
6
7 \CustomizeMathJax{\newcommand{\SC}{\mathbb{C}}}
8 \CustomizeMathJax{\newcommand{\SN}{\mathbb{N}}}
9 \CustomizeMathJax{\newcommand{\SQ}{\mathbb{Q}}}
10 \CustomizeMathJax{\newcommand{\SR}{\mathbb{R}}}
11 \CustomizeMathJax{\newcommand{\SZ}{\mathbb{Z}}}
12
13 \CustomizeMathJax{\newcommand{\calA}{\mathcal{A}}}
14 \CustomizeMathJax{\newcommand{\calB}{\mathcal{B}}}
15 \CustomizeMathJax{\newcommand{\calC}{\mathcal{C}}}
16 \CustomizeMathJax{\newcommand{\calD}{\mathcal{D}}}
17 \CustomizeMathJax{\newcommand{\calE}{\mathcal{E}}}
18 \CustomizeMathJax{\newcommand{\calF}{\mathcal{F}}}
19 \CustomizeMathJax{\newcommand{\calG}{\mathcal{G}}}
20 \CustomizeMathJax{\newcommand{\calH}{\mathcal{H}}}
21 \CustomizeMathJax{\newcommand{\calI}{\mathcal{I}}}
22 \CustomizeMathJax{\newcommand{\calJ}{\mathcal{J}}}
23 \CustomizeMathJax{\newcommand{\calK}{\mathcal{K}}}
24 \CustomizeMathJax{\newcommand{\calL}{\mathcal{L}}}
25 \CustomizeMathJax{\newcommand{\calM}{\mathcal{M}}}
26 \CustomizeMathJax{\newcommand{\calN}{\mathcal{N}}}
27 \CustomizeMathJax{\newcommand{\calO}{\mathcal{O}}}
28 \CustomizeMathJax{\newcommand{\calP}{\mathcal{P}}}
29 \CustomizeMathJax{\newcommand{\calQ}{\mathcal{Q}}}
30 \CustomizeMathJax{\newcommand{\calR}{\mathcal{R}}}
31 \CustomizeMathJax{\newcommand{\calS}{\mathcal{S}}}
32 \CustomizeMathJax{\newcommand{\calT}{\mathcal{T}}}
33 \CustomizeMathJax{\newcommand{\calU}{\mathcal{U}}}
34 \CustomizeMathJax{\newcommand{\calV}{\mathcal{V}}}
35 \CustomizeMathJax{\newcommand{\calW}{\mathcal{W}}}
36 \CustomizeMathJax{\newcommand{\calX}{\mathcal{X}}}
37 \CustomizeMathJax{\newcommand{\calY}{\mathcal{Y}}}
38 \CustomizeMathJax{\newcommand{\calZ}{\mathcal{Z}}}
39
40 \LWR@mathjax@addlatin@u@bfit{m}% uppercase Latin, bold italic
41 \LWR@mathjax@addlatin@l@bfit{v}% lowercase Latin, bold italic
42
43 \LWR@mathjax@addgreek@l@bfit{v}{% lowercase Greek bold italic
44 \LWR@mathjax@addgreek@u@bfit*{m}{% uppercase Greek bold italic, capitalized macro names
45
46 \CustomizeMathJax{\newcommand{\rb}{\mathrm{b}}}
47 \CustomizeMathJax{\newcommand{\rB}{\mathrm{B}}}

```

```

48 \CustomizeMathJax{\newcommand{\rC}{\mathrm{C}}}
49 \CustomizeMathJax{\newcommand{\rD}{\mathrm{D}}}
50 \CustomizeMathJax{\newcommand{\rf}{\mathrm{f}}}
51 \CustomizeMathJax{\newcommand{\rF}{\mathrm{F}}}
52 \CustomizeMathJax{\newcommand{\rH}{\mathrm{H}}}
53 \CustomizeMathJax{\newcommand{\rL}{\mathrm{L}}}
54 \CustomizeMathJax{\newcommand{\rN}{\mathrm{N}}}
55 \CustomizeMathJax{\newcommand{\rt}{\mathrm{t}}}
56 \CustomizeMathJax{\newcommand{\rU}{\mathrm{U}}}
57 \CustomizeMathJax{\newcommand{\rGam}{\mathrm{Gam}}}
58 \CustomizeMathJax{\newcommand{\rBeta}{\mathrm{Beta}}}
59
60 \CustomizeMathJax{\newcommand{\Bin}{\mathrm{Bin}}}
61 \CustomizeMathJax{\newcommand{\eu}{\mathrm{e}}}
62 \CustomizeMathJax{\newcommand{\iu}{\mathrm{i}}}
63 \CustomizeMathJax{\newcommand{\LN}{\mathrm{LN}}}
64 \CustomizeMathJax{\newcommand{\IN}{\mathrm{IN}}}
65
66 \CustomizeMathJax{\newcommand{\Poi}{\mathrm{Poi}}}
67
68 \CustomizeMathJax{\newcommand{\ped}[1]{\mathrm{#1}}}
69 \CustomizeMathJax{\newcommand{\ap}[1]{\mathrm{#1}}}
70 \CustomizeMathJax{\renewcommand{\Re}{\mathrm{Re}}{\nolimits}}
71 \CustomizeMathJax{\renewcommand{\Im}{\mathrm{Im}}{\nolimits}}
72
73 \CustomizeMathJax{\newcommand{\deriv}[3][]{%
74   \frac{\mathrm{d}^{#1}#2}{\mathrm{d}\,#3^{#1}}%
75 }}
76 \CustomizeMathJax{\newcommand{\pderiv}[3][]{%
77   \frac{\partial^{#1}#2}{\partial \#3^{#1}}%
78 }}
79
80 \CustomizeMathJax{\newcommand{\bias}{\operatorname{bias}}}
81 \CustomizeMathJax{\newcommand{\col}{\operatorname{col}}}
82 \CustomizeMathJax{\newcommand{\corr}{\operatorname{corr}}}
83 \CustomizeMathJax{\newcommand{\cov}{\operatorname{cov}}}
84 \CustomizeMathJax{\newcommand{\dg}{\operatorname{dg}}}
85 \CustomizeMathJax{\newcommand{\diag}{\operatorname{diag}}}
86 \CustomizeMathJax{\newcommand{\E}{\operatorname{E}}}
87 \CustomizeMathJax{\newcommand{\etr}{\operatorname{etr}}}
88 \CustomizeMathJax{\newcommand{\ip}{\mathrm{int}}{\nolimits}}
89 \CustomizeMathJax{\newcommand{\kur}{\operatorname{kur}}}
90 \CustomizeMathJax{\newcommand{\MSE}{\operatorname{MSE}}}
91 \CustomizeMathJax{\newcommand{\MSFE}{\operatorname{MSFE}}}
92 \CustomizeMathJax{\newcommand{\OLS}{\operatorname{OLS}}}
93 \CustomizeMathJax{\newcommand{\plim}{\operatorname{plim}}}
94 \CustomizeMathJax{\newcommand{\resid}{\operatorname{resid}}}
95 \CustomizeMathJax{\newcommand{\rk}{\operatorname{rk}}}
96 \CustomizeMathJax{\newcommand{\SE}{\operatorname{SE}}}
97 \CustomizeMathJax{\newcommand{\sgn}{\operatorname{sgn}}}
98 \CustomizeMathJax{\newcommand{\tr}{\operatorname{tr}}}
99 \CustomizeMathJax{\newcommand{\var}{\operatorname{var}}}
100 \CustomizeMathJax{\renewcommand{\vec}{\operatorname{vec}}}
101 \CustomizeMathJax{\newcommand{\vech}{\operatorname{vech}}}
102
103 \CustomizeMathJax{\newcommand{\distr}{\sim}}
104 \CustomizeMathJax{\newcommand{\adistr}{\stackrel{a}{\distr}}}
105 \CustomizeMathJax{\newcommand{\diff}{\Delta}}
106 \CustomizeMathJax{\newcommand{\fdiff}{\diff_{\rf}}}
107 \CustomizeMathJax{\newcommand{\bdiff}{\diff_{\rb}}}

```

```

108
109 \CustomizeMathJax{\newcommand{\eps}{\epsilon}}
110 \CustomizeMathJax{\newcommand{\epsi}{\varepsilon}}
111
112 \CustomizeMathJax{\newcommand{\longto}{\longrightarrow}}
113 \CustomizeMathJax{\newcommand{\pto}{\stackrel{p}{\longrightarrow}}}
114 \CustomizeMathJax{\newcommand{\dto}{\stackrel{d}{\longrightarrow}}}
115 \CustomizeMathJax{\newcommand{\wto}{\stackrel{w}{\longrightarrow}}}
116
117 \CustomizeMathJax{\newcommand{\Infmat}{\bm\cal I}}
118 \CustomizeMathJax{\newcommand{\Hesmat}{\bm\cal H}}
119 \CustomizeMathJax{\newcommand{\bcdot}{\bullet}}
120
121 \CustomizeMathJax{\newcommand{\vones}{\bm\imath}}
122 \CustomizeMathJax{\newcommand{\vzeros}{\boldsymbol{0}}}
123 \CustomizeMathJax{\newcommand{\mZeros}{\mathbf{0}}}
124
125 \CustomizeMathJax{\newcommand{\e}{\eu}}
126 \CustomizeMathJax{\newcommand{\mply}{\cdot}}
127 \CustomizeMathJax{\newcommand{\rW}{\ensuremath{\mathrm{W}}}}
128 \end{warpMathJax}

```

File 123 **lwarp-ed.sty**

§ 232 Package **ed**

(Emulates or patches code by MICHAEL KOHLHASE.)

ed is patched for use by **lwarp**.

for HTML output: 1 \LWR@ProvidesPackagePass{ed}[2012/01/29]

Bugs:

1. `todolist` fails with the `hide` option, as does `\edexplanation`.
2. `\edstubURI` is actually `\edstuURI`.

```

2 \RequirePackage{xcolor}
3
4 \renewenvironment{edstub}[2][The following blue text]
5 {%
6   \def\@test{#1}%
7   \begin{center}%
8     \huge%
9     \textcolor{red}{%
10      #1 is only a provisional stub\\Large
11      the Office document
12      \ifx\ed@stubURI@empty{#2}\else\LWR@href{\ed@stubURI}{#2}\fi\
13      contains more text\\which will be merged for the final document%
14    }%
15  \end{center}%
16  \BlockClass[color:blue]{edstub}%
17 }
18 {\endBlockClass}

```

File 124 **lwarp-ellipsis.sty**

§ 233 Package **ellipsis**

(Emulates or patches code by PETER J. HESLIN.)

Pkg ellipsis

ellipsis is emulated.

```

1 \LWR@ProvidesPackageDrop{ellipsis}[2004/09/28]
2
3 \newcommand{\ellipsisgap}{0.1em}
4
5 \newcommand*{\midwordellipsis}{\,\textellipsis\,}

```

File 125 **lwarp-embrac.sty**

§ 234 Package **embrac**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg embrac

embrac is patched for HTML and used as-is for print.

for HTML output:

```

1 \LWR@ProvidesPackagePass{embrac}[2017/07/04]
2
3 \ExplSyntaxOn
4 \RenewDocumentCommand{\embrac_kern:n}{m}{}
5 \ExplSyntaxOff
6
7 \LetLtxMacro\LWR@orig@HTML@emph\LWR@HTML@emph
8 \RenewDocumentCommand{\LWR@HTML@emph}{s m}{\LWR@orig@HTML@emph{#2}}
9
10 \LetLtxMacro\LWR@orig@HTML@textit\LWR@HTML@textit
11 \RenewDocumentCommand{\LWR@HTML@textit}{s m}{\LWR@orig@HTML@textit{#2}}
12
13 \LetLtxMacro\LWR@orig@HTML@textsl\LWR@HTML@textsl
14 \RenewDocumentCommand{\LWR@HTML@textsl}{s m}{\LWR@orig@HTML@textsl{#2}}
15
16 \ifxetexorluatex
17 \LetLtxMacro\LWR@orig@HTML@textsi\LWR@HTML@textsi
18 \RenewDocumentCommand{\LWR@HTML@textsi}{s m}{%
19 \LWR@orig@HTML@textsi{#2}}
20 \fi
21
22 \AtBeginDocument{
23 \LWR@formatted{emph}
24 \LWR@formatted{textit}
25 \LWR@formatted{textsl}
26 \ifxetexorluatex
27 \LWR@formatted{textsi}
28 \fi

```

```

29 \newcommand{\LWR@HTML@EmbracOff}{}
30 \LWR@formatted{EmbracOff}
31
32 \newcommand{\LWR@HTML@EmbracOn}{}
33 \LWR@formatted{EmbracOn}

```

File 126 **lwarp-emptypage.sty**

§ 235 Package **emptypage**

Pkg emptypage

emptypage is ignored.

for HTML output: Discard all options for lwarp-emptypage:

```
1 \LWR@ProvidesPackageDrop{emptypage}[2010/05/30]
```

File 127 **lwarp-endfloat.sty**

§ 236 Package **endfloat**

Pkg endfloat

endfloat is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{endfloat}[2019/04/15]

```

2 \newcommand\figureplace{}
3 \newcommand\tableplace{}
4 \newcommand\floatplace[1]{}
5 \newcounter{posttable}
6 \newcounter{postfigure}
7 \newcommand*\theposttbl{}
8 \newcommand*\thepostfig{}
9 \newcommand{\AtBeginFigures}[1]{}
10 \newcommand{\AtBeginTables}[1]{}
11 \newcommand{\AtBeginDelayedFloats}[1]{}
12 \newcommand*\processdelayedfloats{}
13 \newcommand*\efloatseparator{}
14 \def\efloattype{}
15 \providecommand\efloatheading[1]{}
16 \providecommand\efloatpreamble{}
17 \providecommand\efloatpostamble{}
18 \NewDocumentCommand{\addtodelayedfloat}{s m m}{}
19 \providecommand{\efloatbegin}{}
20 \providecommand{\efloatend}{}
21 \providecommand{\efloatbeginlist}{}
22 \providecommand{\efloatendlist}{}

```

File 128 **lwarp-endheads.sty**

§ 237 Package **endheads**

Pkg endheads

endheads is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{endheads}[2017/04/06]

```

2 \newcommand{\changesinglepageabbrev}[1]{}
3 \newcommand{\changemultiplepageabbrev}[1]{}
4 \newcommand{\changenotesname}[1]{}
5 \newcommand{\changenotesheader}[1]{}
6 \newcommand{\changenotescontentsname}[1]{}
7 \newcommand{\changechapternotesline}[1]{}
8 \newcommand{\checknoteheaders}{}
9 \newif\ifnotesincontentson \notesincontentsonfalse
10 \newcommand{\notesincontents}{\notesincontentsontrue}
11 \newif\ifendnoteheaderson \endnoteheadersonfalse
12 \newcommand{\setupendnoteheaders}{%
13   \endnoteheadersontrue%
14 }
15 \newif\iftitleinnotes \titleinnotestru
16 \newcommand{\styleforchapternotebegin}{}
17 \newcommand{\styleforchapternoteend}{}
18 \newcommand{\setstyleforchapternotebegin}[1]{%
19   \renewcommand{\styleforchapternotebegin}{#1}%
20 }
21 \newcommand{\setstyleforchapternoteend}[1]{%
22   \renewcommand{\styleforchapternoteend}{#1}%
23 }
24 \newcommand{\resetendnotes}{}
25 \newif\ifnotesbychapteron \notesbychapteronfalse
26 \newcommand{\notesbychapter}{\notesbychapterontrue}

```

File 129 **lwarp-endnotes.sty**

§ 238 Package **endnotes**

(Emulates or patches code by JOHN LAVAGNINO.)

Pkg endnotes

Patched for HTML.

[table of contents](#) To place the endnotes in the TOC, use:

```

\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional

```

[HTML page](#) To additionally have the endnotes on their own HTML page, if FileDepth allows:

```

\ForceHTMLPage
\theendnotes

```

 [\endnotemark numbering](#) If using MATHJAX, see section 8.5.4 regarding the use of \endnotemark and \endnotetext.

for HTML output: 1 \LWR@ProvidesPackagePass{endnotes}

```

2 \def\enoteformat{%
3 % \rightskip\z@ \leftskip\z@ \parindent=1.8em
4 \leavevmode
5 % \llap{
6 \makeenmark
7 % }
8 }

```

```

9 \def\LWR@HTML@makeenmark{\hbox{\LWR@htmlspan{sup}\normalfont\theenmark}}
10 \LWR@formatted{@makeenmark}
11
12 \def\makeenmark{\@makeenmark}

```

To nullify the endnotes:

```

13 \apptocmd{\LWR>nullifyfootnotes}{%
14   \renewcommand{\endnote}[2][{}]%
15   \renewcommand{\endnotemark}[1]{}%
16 }{}{}

```

For MATHJAX:

```

17 \begin{warpMathJax}
18 \def\endnotename{endnote}
19 \appto\LWR@synctotenumbers{\LWR@synconenotenummer{\LWRendnote}{\theendnote}}
20 \appto\LWR@synctotenames{\LWR@synconenotename{\LWRendnote}{\endnotename}}
21 \CustomizeMathJax{\def\LWRendnote{1}}
22 \CustomizeMathJax{\newcommand{\endnote}[2][\LWRendnote]{{}^{\mathrm{#1}}}}
23 \CustomizeMathJax{\newcommand{\endnotemark}[1][\LWRendnote]{{}^{\mathrm{#1}}}}
24 \end{warpMathJax}

```

File 130 **lwarp-engt1c.sty**

§ 239 Package **engt1c**

(Emulates or patches code by CLAUDIO FIANDRINO.)

engt1c is patched for use by lwarp. MATHJAX is emulated.



For MATHJAX, `\sight`, `\signf`, `\signn`, and `\signz` do not force letter case as they do in SVG math.

for HTML output: 1 \LWR@ProvidesPackagePass{engt1c}[2012/12/18]

```

2 \newcommand{\LWR@HTML@fines}{%
3   \begin{BlockClass}[text-align:right]{exerend}%
4   \HTMLunicode{220E}%
5   \end{BlockClass}%
6 }
7 \LWR@formatted{fines}
8
9 \newcommand{\LWR@HTML@exerend}{\fines}
10 \LWR@formatted{exerend}
11
12 \begin{warpMathJax}
13 \LWR@infoprocessingmathjax{engt1c}
14
15 \CustomizeMathJax{\newcommand{\unit}[1]{\, \mathrm{#1}}}
16 \CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
17 %
18 \CustomizeMathJax{\newcommand{\ho}{\unit{h}}}
19 \CustomizeMathJax{\newcommand{\s}{\unit{s}}}
20 \CustomizeMathJax{\newcommand{\ms}{\unit{ms}}}
21 \CustomizeMathJax{\newcommand{\us}{\unit{\micro s}}}
22 \CustomizeMathJax{\newcommand{\ns}{\unit{ns}}}

```

```
23 \CustomizeMathJax{\newcommand{\ps}{\unit{ps}}}
24 %
25 \CustomizeMathJax{\newcommand{\um}{\unit{\micro m}}}
26 \CustomizeMathJax{\newcommand{\mm}{\unit{mm}}}
27 \CustomizeMathJax{\newcommand{\cm}{\unit{cm}}}
28 \CustomizeMathJax{\newcommand{\dm}{\unit{dm}}}
29 \CustomizeMathJax{\newcommand{\m}{\unit{m}}}
30 \CustomizeMathJax{\newcommand{\km}{\unit{km}}}
31 %
32 \CustomizeMathJax{\newcommand{\MA}{\unit{MA}}}
33 \CustomizeMathJax{\newcommand{\kA}{\unit{kA}}}
34 \CustomizeMathJax{\newcommand{\A}{\unit{A}}}
35 \CustomizeMathJax{\newcommand{\mA}{\unit{mA}}}
36 \CustomizeMathJax{\newcommand{\uA}{\unit{\micro A}}}
37 \CustomizeMathJax{\newcommand{\nA}{\unit{nA}}}
38 %
39 \CustomizeMathJax{\newcommand{\MV}{\unit{MV}}}
40 \CustomizeMathJax{\newcommand{\kV}{\unit{kV }}}
41 \CustomizeMathJax{\newcommand{\V}{\unit{V}}}
42 \CustomizeMathJax{\newcommand{\mV}{\unit{mV}}}
43 \CustomizeMathJax{\newcommand{\uV}{\unit{\micro V}}}
44 %
45 \CustomizeMathJax{\newcommand{\mohm}{\unit{m\Omega}}}
46 \CustomizeMathJax{\newcommand{\ohm}{\unit{\Omega}}}
47 \CustomizeMathJax{\newcommand{\kohm}{\unit{k\Omega}}}
48 \CustomizeMathJax{\newcommand{\Mohm}{\unit{M\Omega}}}
49 %
50 \CustomizeMathJax{\newcommand{\pSi}{\unit{pS}}}
51 \CustomizeMathJax{\newcommand{\nSi}{\unit{nS}}}
52 \CustomizeMathJax{\newcommand{\uSi}{\unit{\micro S}}}
53 \CustomizeMathJax{\newcommand{\mSi}{\unit{mS}}}
54 \CustomizeMathJax{\newcommand{\Si}{\unit{S}}}
55 \CustomizeMathJax{\newcommand{\kSi}{\unit{kS}}}
56 \CustomizeMathJax{\newcommand{\MSi}{\unit{MS}}}
57 %
58 \CustomizeMathJax{\newcommand{\fFa}{\unit{fF}}}
59 \CustomizeMathJax{\newcommand{\pFa}{\unit{pF}}}
60 \CustomizeMathJax{\newcommand{\nFa}{\unit{nF}}}
61 \CustomizeMathJax{\newcommand{\uFa}{\unit{\micro F}}}
62 \CustomizeMathJax{\newcommand{\mFa}{\unit{mF}}}
63 \CustomizeMathJax{\newcommand{\Fa}{\unit{F}}}
64 %
65 \CustomizeMathJax{\newcommand{\fHe}{\unit{fH}}}
66 \CustomizeMathJax{\newcommand{\pHe}{\unit{pH}}}
67 \CustomizeMathJax{\newcommand{\nHe}{\unit{nH}}}
68 \CustomizeMathJax{\newcommand{\uHe}{\unit{\micro H}}}
69 \CustomizeMathJax{\newcommand{\mHe}{\unit{mH}}}
70 \CustomizeMathJax{\newcommand{\He}{\unit{H}}}
71 %
72 \CustomizeMathJax{\newcommand{\dB}{\unit{dB}}}
73 \CustomizeMathJax{\newcommand{\dBm}{\unit{dBm}}}
74 %
75 \CustomizeMathJax{\newcommand{\uW}{\unit{\micro W}}}
76 \CustomizeMathJax{\newcommand{\mW}{\unit{mW}}}
77 \CustomizeMathJax{\newcommand{\W}{\unit{W}}}
78 \CustomizeMathJax{\newcommand{\kW}{\unit{kW}}}
79 \CustomizeMathJax{\newcommand{\MW}{\unit{MW}}}
80 %
81 \CustomizeMathJax{\newcommand{\Hz}{\unit{Hz}}}
82 \CustomizeMathJax{\newcommand{\kHz}{\unit{kHz}}}
```

```

83 \CustomizeMathJax{\newcommand{\MHz}{\unit{MHz}}}
84 \CustomizeMathJax{\newcommand{\GHz}{\unit{GHz}}}
85 \CustomizeMathJax{\newcommand{\THz}{\unit{THz}}}
86 %
87 \CustomizeMathJax{\newcommand{\bit}{\unit{bit}}}
88 \CustomizeMathJax{\newcommand{\kbit}{\unit{Kib}}}
89 \CustomizeMathJax{\newcommand{\Mbit}{\unit{Mib}}}
90 \CustomizeMathJax{\newcommand{\Byte}{\unit{B}}}
91 \CustomizeMathJax{\newcommand{\kByte}{\unit{KiB}}}
92 \CustomizeMathJax{\newcommand{\MByte}{\unit{MiB}}}
93 \CustomizeMathJax{\newcommand{\GByte}{\unit{GiB}}}
94 \CustomizeMathJax{\newcommand{\TByte}{\unit{TiB}}}
95 \CustomizeMathJax{\newcommand{\bits}{\unit{bit/s}}}
96 \CustomizeMathJax{\newcommand{\kbits}{\unit{Kib/s}}}
97 \CustomizeMathJax{\newcommand{\Mbits}{\unit{Mib/s}}}
98 \CustomizeMathJax{\newcommand{\Bytes}{\unit{B/s}}}
99 \CustomizeMathJax{\newcommand{\kBytes}{\unit{KiB/s}}}
100 \CustomizeMathJax{\newcommand{\MBytes}{\unit{MiB/s}}}
101 \CustomizeMathJax{\newcommand{\GBytes}{\unit{GiB/s}}}
102 \CustomizeMathJax{\newcommand{\TBytes}{\unit{TiB/s}}}
103 \CustomizeMathJax{\newcommand{\chips}{\unit{chip/s}}}
104 \CustomizeMathJax{\newcommand{\kchips}{\unit{Ki\mkern2mu chip/s}}}
105 \CustomizeMathJax{\newcommand{\Mchips}{\unit{Mi\mkern2mu chip/s}}}
106 \CustomizeMathJax{\newcommand{\chipsubit}{\unit{chip/bit}}}
107 %
108 \CustomizeMathJax{\newcommand{\frecciadex}[1][0.5]{%
109   \hspace{.25cm}\Longrightarrow \hspace{.25cm}}%
110 }
111 \CustomizeMathJax{\newcommand{\varianzarumore}{\frac{N_0}{2}}}
112 %
113 \CustomizeMathJax{\newcommand{\etsymbolbracearg}[2]{%
114   #1\mathopen{}\left\lbrace#2\right\rbrace\mathclose{}}%
115 }
116 \CustomizeMathJax{\newcommand{\fourier}[1]{\etsymbolbracearg{\mathcal{F}}{#1}}}
117 \CustomizeMathJax{\newcommand{\invfourier}[1]{\etsymbolbracearg{\mathcal{F}}^{-1}{#1}}}
118 \CustomizeMathJax{\newcommand{\partereale}[1]{\etsymbolbracearg{\text{Re}}{#1}}}
119 \CustomizeMathJax{\newcommand{\parteimm}[1]{\etsymbolbracearg{\text{Im}}{#1}}}
120 \CustomizeMathJax{\newcommand{\Info}[1]{I\left(#1\right)}}
121 \CustomizeMathJax{\newcommand{\versore}[1]{\hat{#1}}}
122 \CustomizeMathJax{\newcommand{\vettore}[1]{\overrightarrow{#1}}}
123 \CustomizeMathJax{\newcommand{\coseno}[1]{\cos\left(2\pi#1t\right)}}
124 \CustomizeMathJax{\newcommand{\seno}[1]{\sin\left(2\pi#1t\right)}}
125 \CustomizeMathJax{\newcommand{\energia}[1]{\mathcal{E}_{#1}}}
126 \CustomizeMathJax{\newcommand{\moduloexp}[2]{\left\vert\right\vert#1\right\vert^{\#2}}}
127 \CustomizeMathJax{\newcommand{\modulo}[1]{\left\vert\right\vert#1\right\vert}}
128 \CustomizeMathJax{\newcommand{\indB}[1]{%
129   \mathopen{}\left.#1\right\vert_{\mathrm{dB}}\mathclose{}}%
130 \CustomizeMathJax{\newcommand{\for}[2]{\left.#1\right\vert_{\#2}}}
131 \CustomizeMathJax{\newcommand{\massimo}[1]{\etsymbolbracearg{\max}{#1}}}
132 \CustomizeMathJax{\newcommand{\minimo}[1]{\etsymbolbracearg{\min}{#1}}}
133 \CustomizeMathJax{\newcommand{\valc}{3\cdot 10^8}}
134 \CustomizeMathJax{\newcommand{\loga}[2]{\log_{#1}\#2}}
135 \CustomizeMathJax{\newcommand{\analitic}[1]{\mathring{#1}}}
136 \CustomizeMathJax{\newcommand{\diff}{\mathop{} \mathopen{\mathrm{d}}}}
137 \CustomizeMathJax{\newcommand{\intinf}[1]{\int_{-\infty}^{+\infty}{#1}}}
138 \CustomizeMathJax{\newcommand{\deltain}[1]{\delta\left(#1\right)}}
139 \CustomizeMathJax{\newcommand{\iu}{\mathrm{j}}}
140 \CustomizeMathJax{\newcommand{\ex}[1]{\mathrm{e}^{\#1}}}
141 %
142 \CustomizeMathJax{\newcommand{\gammatens}{{}^{\mathrm{V}}\Gamma}}

```

```

143 \CustomizeMathJax{\newcommand{\gammacorr}{\mathrm{I}}\Gamma}}
144 \CustomizeMathJax{\newcommand{\gammatensin}[1]{\mathrm{V}}\Gamma_{\mathrm{#1}}}}
145 \CustomizeMathJax{\newcommand{\gammacorrin}[1]{\mathrm{I}}\Gamma_{\mathrm{#1}}}}
146 \CustomizeMathJax{\newcommand{\gammmain}[1]{\Gamma_{\mathrm{#1}}}}
147 \CustomizeMathJax{\newcommand{\gammak}{\mathrm{k}}\Gamma}}
148 %
149 \CustomizeMathJax{\newcommand{\lbvt}{\lambda_0}}
150 \CustomizeMathJax{\newcommand{\lbg}{\lambda_g}}
151 \CustomizeMathJax{\newcommand{\lbgvt}{\lambda_{g_0}}}
152 %
153 \CustomizeMathJax{\newcommand{\potin}[1]{P_{\mathrm{#1}}}}
154 \CustomizeMathJax{\newcommand{\potdisp}[1][P_{\mathrm{disp}}^{\mathrm{#1}}}}
155 \CustomizeMathJax{\newcommand{\potDC}[1][P_{\mathrm{DC}}^{\mathrm{#1}}}}
156 \CustomizeMathJax{\newcommand{\potCC}[1][P_{\mathrm{CC}}^{\mathrm{#1}}}}
157 \CustomizeMathJax{\newcommand{\potirr}[1][P_{\mathrm{irr}}^{\mathrm{#1}}}}
158 \CustomizeMathJax{\newcommand{\potdiss}[1][P_{\mathrm{diss}}^{\mathrm{#1}}}}
159 \CustomizeMathJax{\newcommand{\potinc}[1][P_{\mathrm{inc}}^{\mathrm{#1}}}}
160 %
161 \CustomizeMathJax{\newcommand{\z}[1]{Z_{\mathrm{#1}}}}
162 \CustomizeMathJax{\newcommand{\znorm}[1]{z_{\mathrm{#1}}}}
163 \CustomizeMathJax{\newcommand{\y}[1]{Y_{\mathrm{#1}}}}
164 \CustomizeMathJax{\newcommand{\ynorm}[1]{y_{\mathrm{#1}}}}
165 \CustomizeMathJax{\newcommand{\zinf}[1][Z_{\infty\mathrm{#1}}}}
166 \CustomizeMathJax{\newcommand{\zinfn}[1]{zinf\mathrm{#1}}}}
167 \CustomizeMathJax{\newcommand{\yinf}[1][Y_{\infty\mathrm{#1}}}}
168 \CustomizeMathJax{\newcommand{\yinfn}[1]{yinf\mathrm{#1}}}}
169 \CustomizeMathJax{\newcommand{\zvt}{Z_0}}
170 \CustomizeMathJax{\newcommand{\yvt}{Y_0}}
171 %
172 \CustomizeMathJax{\newcommand{\campoe}{\underline{\mathcal{E}}(\underline{r},t)}}
173 \CustomizeMathJax{\newcommand{\campoe fas}{\underline{E}(\underline{r})}}
174 \CustomizeMathJax{\newcommand{\campoh}{\underline{\mathcal{H}}(\underline{r},t)}}
175 \CustomizeMathJax{\newcommand{\campoh fas}{\underline{H}(\underline{r})}}
176 %
177 \CustomizeMathJax{\newcommand{\signt}[1]{\mathrm{#1}(t)}}
178 \CustomizeMathJax{\newcommand{\signf}[1]{\mathrm{#1}(f)}}
179 \CustomizeMathJax{\newcommand{\signn}[1]{\mathrm{#1}(n)}}
180 \CustomizeMathJax{\newcommand{\signz}[1]{\mathrm{#1}(z)}}
181 %
182 \CustomizeMathJax{\newcommand{\prob}[1]{\mathcal{P}\left(\mathrm{#1}\right)}}
183 \CustomizeMathJax{\newcommand{\valatt}[1]{\mathbb{E}\left[\mathrm{#1}\right]}}
184 \CustomizeMathJax{\newcommand{\var}[1]{\mathrm{Var}\left[\mathrm{#1}\right]}}
185 \CustomizeMathJax{\newcommand{\comma}{\ , \ , \ ,}}
186 \CustomizeMathJax{\newcommand{\dato}{\ , | \ ,}}
187 %
188 \CustomizeMathJax{\let\bfRe\partereale}
189 \CustomizeMathJax{\let\bfIm\parteimm}
190 \CustomizeMathJax{\let\noisevar\varianzarumore}
191 % \CustomizeMathJax{\let\exerend\finees}
192 \CustomizeMathJax{\let\Spimplies\frecciadex}
193 \CustomizeMathJax{\let\Downimplies\frecciadown}
194 \CustomizeMathJax{\let\unitvec\versore}
195 \CustomizeMathJax{\let\vector\vettore}
196 \CustomizeMathJax{\let\cosine\coseno}
197 \CustomizeMathJax{\let\sine\seno}
198 \CustomizeMathJax{\let\energy\energia}
199 \CustomizeMathJax{\let\Abs\modulo}
200 \CustomizeMathJax{\let\AbsPow\moduloexp}
201 \CustomizeMathJax{\let\Max\massimo}
202 \CustomizeMathJax{\let\Min\minimo}

```

```

203 \CustomizeMathJax{\let\light\valc}
204 \CustomizeMathJax{\let\Log\loga}
205 \CustomizeMathJax{\let\analytic\analitic}
206 \CustomizeMathJax{\let\infint\intinf}
207 \CustomizeMathJax{\let\deltaimp\deltain}
208 \CustomizeMathJax{\let\Vgamma\gammaten}
209 \CustomizeMathJax{\let\Cgamma\gammacor}
210 \CustomizeMathJax{\let\Vgammain\gammatenin}
211 \CustomizeMathJax{\let\Cgammain\gammacorin}
212 \CustomizeMathJax{\let\Kgamma\gammak}
213 \CustomizeMathJax{\let\powerin\potin}
214 \CustomizeMathJax{\let\availpow\potdisp}
215 \CustomizeMathJax{\let\irrpow\potirr}
216 \CustomizeMathJax{\let\disppow\potdiss}
217 \CustomizeMathJax{\let\incpow\potinc}
218 \CustomizeMathJax{\let\potalim\potCC}
219 \CustomizeMathJax{\let\potDC\potCC}
220 \CustomizeMathJax{\let\Efield\campoe}
221 \CustomizeMathJax{\let\Hfield\campoh}
222 \CustomizeMathJax{\let\phasorEfield\campoe}
223 \CustomizeMathJax{\let\phasorHfield\campoh}
224 \CustomizeMathJax{\let\given\dato}
225 \CustomizeMathJax{\let\expval\valatt}
226 \CustomizeMathJax{\let\rmexp\ex}
227 \end{warpMathJax}

```

File 131 **lwarp-enotez.sty**

§ 240 Package **enotez**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg enotez

enotez is patched for use by **lwarp**.

for HTML output: 1 \LWR@ProvidesPackagePass{enotez}[2020/12/13]

Hyperref is emulated by **lwarp**, so it is forced on for **enotez**:

```

2 \ExplSyntaxOn
3 \AtBeginDocument{
4   \bool_set_true:N \l__enotez_hyperref_bool
5   \bool_set_true:N \l__enotez_hyperfootnotes_bool
6 }

```

Do not move or \hbox the \hypertarget:

```

7 % typeset the actual mark:
8 % #1: id
9 % #2: mark
10 \cs_gset_protected:Npn \enotez_write_mark:nn #1#2
11 {
12   \bool_if:NTF \l__enotez_hyperfootnotes_bool
13   {
14     \enotezwritemark { \hyperlink {enz.#1} { \enmarkstyle #2 } }
15     \bool_if:NT \l__enotez_hyperbackref_bool
16     {
17       \box_move_up:nn {1em} {

```

```

18%             \hbox:n {
19               \hypertarget {enz.#1.backref} { }
20%             }
21%         }
22     }
23 }
24 { \notezwritemark { \markstyle #2 } }
25 }
26 \cs_generate_variant:Nn \notez_write_mark:nn {x}

```

Do not move or \hbox the \hypertarget:

```

27 \cs_gset_protected:Npn \notez_write_list_number:n #1
28 {
29   \bool_if:NT \l__enotez_hyperfootnotes_bool
30   {
31%     \box_move_up:nn {1em} { \hbox:n {
32%       \hypertarget {enz.#1} { }
33%     } }
34   }
35   \tl_use:N \l__enotez_list_number_format_tl
36   \tl_if_eq:nxTF {a} { \prop_item:Nn \g__enotez_endnote_man_prop {#1} }
37   {
38     \bool_if:nTF
39     { \l__enotez_hyperfootnotes_bool && \l__enotez_hyperbackref_bool }
40     {
41       \exp_args:Nnx
42       \hyperlink {enz.#1.backref}
43       { \exp_not:V \l__enotez_endnote_mark_tl }
44     }
45     { \prop_item:Nn \g__enotez_endnote_mark_prop {#1} }
46   }
47   {
48     \bool_if:nTF
49     { \l__enotez_hyperfootnotes_bool && \l__enotez_hyperbackref_bool }
50     {
51       \exp_args:Nnx
52       \hyperlink {enz.#1.backref}
53       { \exp_not:V \l__enotez_endnote_mark_tl }
54     }
55     { \tl_use:N \l__enotez_endnote_mark_tl }
56   }
57 }

```

Do not move the label to the left:

```

58 \DeclareTemplateCode {enotez-list} {paragraph} {1}
59 {
60   heading      = \enotez_list_heading:n      ,
61   format       = \l__enotez_list_format_tl  ,
62   number       = \enotez_list_number:n      ,
63   number-format = \l__enotez_list_number_format_tl ,
64   notes-sep    = \l__enotez_list_notes_sep_dim
65 }
66 {
67   \AssignTemplateKeys
68   \enotez_set_toc:
69   \enotez_list_heading:n { \l__enotez_list_name_tl }
70   \enotez_list_preamble:
71   \enotez_build_print_list:nnnn {#1}

```

```

72     {}
73     {
74         \par\noindent
75         \group_begin:
76         \tl_use:N \l__enotez_list_format_tl
77 %         \hbox_overlap_left:n
78 %         {
79             \enotez_list_number:n
80             { \enotez_write_list_number:n {##1} }
81             \tl_use:N \c_space_tl
82 %         }
83         % \cs_set:cpn {@currentlabel}
84         % { \p@endnote \l__enotez_endnote_mark_tl }
85         \tl_use:N \g__enotez_endnote_text_tl
86         \par
87         \dim_compare:nT { \l__enotez_list_notes_sep_dim != 0pt }
88         { \addvspace { \l__enotez_list_notes_sep_dim } }
89         \group_end:
90     }
91     {}
92     \enotez_list_postamble:
93 }
94
95 \ExplSyntaxOff

```

For MATHJAX:

```

96 \begin{warpMathJax}
97 \def\endnotename{endnote}
98 \appto\LWR@syncnotenumbers{\LWR@synconenotenummer{\LWRendnote}{\theendnote}}
99 \appto\LWR@syncnotenames{\LWR@synconenotename{\LWRendnote}{\endnotename}}
100 \CustomizeMathJax{\def\LWRendnote{1}}
101 \CustomizeMathJax{\newcommand{\endnote}[2][\LWRendnote]{{}^{\mathrm{#1}}}}
102 \CustomizeMathJax{\newcommand{\endnotemark}[1][\LWRendnote]{{}^{\mathrm{#1}}}}
103 \end{warpMathJax}

```

File 132 **lwarp-enumerate.sty**

§ 241 Package **enumerate**

Pkg enumerate

enumerate is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by lwarp and thus must no longer be dropped.

for HTML output: 1 \LWR@ProvidesPackagePass{enumerate}[2015/07/23]

File 133 **lwarp-enumitem.sty**

§ 242 Package **enumitem**

(Emulates or patches code by JAVIER BEZOS.)

Pkg enumitem

enumitem is supported with minor adjustments.

for HTML output: 1 \LWR@ProvidesPackagePass{enumitem}[2018/11/30]

```
\newlist {<name>} {<type>} {<maxdepth>}
\renewlist {<name>} {<type>} {<maxdepth>}
```

For enumitem lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

```
2 \let\LWR@enumitem@orignewlist\newlist
3
4 \renewcommand*{\newlist}[3]{%
5 \LWR@enumitem@orignewlist{#1}{#2}{#3}%
6 \AtBeginEnvironment{#1}{\@nameuse{LWR@#2start}}%
7 \AtEndEnvironment{#1}{\@nameuse{LWR@#2end}}%
8 }
9
10 \def\DrawEnumitemLabel{}
```

File 134 **lwarp-epigraph.sty**§ 243 Package **epigraph***(Emulates or patches code by PETER WILSON.)*

Pkg epigraph

epigraph is emulated for HTML, and used as-is for print output.

Use css to format epigraphs.

for HTML output: 1 \LWR@ProvidesPackagePass{epigraph}[2020/01/02]

```
2 \DeclareDocumentCommand{\LWR@HTML@qitem}{m m}
3 {%
4   \begin{BlockClass}{qitem}%
5   #1%
6   \LWR@stoppars%
7   \ifbool{FormatWP}%
8     {\begin{BlockClass}[border-top:1px solid gray]{epigraphsource}}%
9     {\begin{BlockClass}{epigraphsource}}%
10  #2%
11  \end{BlockClass}%
12  \end{BlockClass}%
13 }
14 \LWR@formatted{qitem}
```

epigraph: Added ARIA role.

```
15 \DeclareDocumentCommand{\LWR@HTML@epigraph}{m m}
16 {%
17   \begin{LWR@BlockClassWP}{\LWR@print@mbx{text-align:right}}{(note){epigraph}}%
18   \qitem{#1}{#2}%
19   \end{LWR@BlockClassWP}%
20 }
21 \LWR@formatted{epigraph}
```

```

22
23 \DeclareDocumentEnvironment{LWR@HTML@epigraphs}{}
24   {\LWR@BlockClassWP{\LWR@print@mbbox{text-align:right}}{ }(note){epigraph}}%
25   {\endLWR@BlockClassWP}
26 \LWR@formattedenv{epigraphs}

```

The following cannot be used in print mode while generating HTML:

```

27 \renewcommand{\epigraphhead}[2][0]{#2}
28 \renewcommand{\dropchapter}[1]{}
29 \renewcommand*\undodrop{}

```

File 135 **lwarp-epsf.sty**

§ 244 Package **epsf**

(Emulates or patches code by TOM ROKICKI.)

Pkg epsf

epsf is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{epsf}% not date given

2 \xpretocmd{\epsfsetgraph}
3   {\begin{lateximage}}
4   {}
5   {\LWR@patcherror{lwarp-epsf}{epsfsetgraph-begin}}
6
7 \xapptocmd{\epsfsetgraph}
8   {\end{lateximage}}
9   {}
10  {\LWR@patcherror{lwarp-epsf}{epsfsetgraph-end}}

```

File 136 **lwarp-epsfig.sty**

§ 245 Package **epsfig**

Pkg epsfig

epsfig is emulated for use by lwarp.



Only the L^AT_EX₂ε syntax is emulated.

for HTML output:

```

1 \LWR@ProvidesPackagePass{epsfig}[2017/06/25]

```

A few additional keys to capture the filename:

```

2 \RequirePackage{graphics}
3
4 \define@key{igraph}{file}{%
5   \xdef\LWR@epsfig@filename{#1}%
6 }
7
8 \define@key{igraph}{figure}{%
9   \xdef\LWR@epsfig@filename{#1}%
10 }
11

```

```

12 \define@key{igraph}{prolog}{}
13
14 \define@key{igraph}{silent}[]{}

```

The captured filename is used as the argument to `\includegraphics`:

```

15 \newcommand{\LWR@HTML@epsfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
16 \LWR@formatted{epsfig}
17
18 \newcommand{\LWR@HTML@psfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
19 \LWR@formatted{psfig}

```

File 137 **lwarp-epstopdf.sty**

§ 246 Package **epstopdf**

Pkg epstopdf

Previous versions of `lwarp` had a nullified version, but now `epstopdf-base` is supported. `lwarp-epstopdf` becomes a placeholder to overwrite previous versions.

See package `epstopdf-base` for details.

for HTML output: 1 \LWR@ProvidesPackagePass{epstopdf}[2020-01-24]

File 138 **lwarp-epstopdf-base.sty**

§ 247 Package **epstopdf-base**

Pkg epstopdf-base



convert to .svg

Images with an `.eps` extension will be converted to `.pdf`. The HTML output uses the `.svg` version, so use

```
Enter ⇒ lwarpmk pdftosvg <listofPDFfiles>
```

to generate `.svg` versions.

for HTML output: 1 \LWR@ProvidesPackagePass{epstopdf-base}[2020-01-24]

Redefine to remember the image filename, replacing `.pdf` with `.svg`. Use the `epstopdf print` version inside a `lateximage`.

```

2 \newcommand*{\LWR@HTML@ETE@OrgGin@setfile}[3]{%
3   \edef\LWR@tempone{#3}%
4   \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
5   \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
6   \xdef\LWR@parsedfilename{\LWR@tempone}%
7 }
8
9 \LWR@formatted{ETE@OrgGin@setfile}

```

`\includegraphics` in HTML mode redefines `\Gin@setfile` to be `\LWR@HTML@Gin@setfile`, which is now redirected to `epstopdf`'s version:

```

10 \renewcommand*\LWR@HTML@Gin@setfile}[3]{%
11   \ETE@Gin@setfile{#1}{#2}{#3}%
12 }

```

Allow .eps images to be found if a suffix is not provided:

```

13 \AtBeginDocument{
14 \DeclareGraphicsExtensions{%
15   .eps, .EPS, .svg, .SVG, .gif, .GIF, .png, .PNG, .jpg, .JPG, .jpeg, .JPEG%
16 }
17 \DeclareGraphicsRule{.svg}{svg}{.svg}{}
18 \DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
19 }

```

Likewise when inside a lateximage:

```

20 \appto\LWR@restoreorigformatting{%
21 \DeclareGraphicsExtensions{%
22   .eps, .EPS, .pdf, .PDF, .gif, .GIF, .png, .PNG, .jpg, .JPG, .jpeg, .JPEG%
23 }%
24 }

```

File 139 **lwarp-eqlist.sty**

§ 248 Package **eqlist**

Pkg eqlist

eqlist is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{eqlist}[2002/08/15]

2 \newenvironment{eqlist}[1][\description]{\enddescription}
3 \newenvironment{eqlist*}[1][\description]{\enddescription}
4 \newenvironment{Eqlist}[2][\description]{\enddescription}
5 \newenvironment{Eqlist*}[2][\description]{\enddescription}
6 \newcommand*\longitem[1][\item[#1]]
7 \newcommand*\eqlistinit{}
8 \newcommand*\eqliststarinit{}
9 \newcommand*\eqlistinitpar{}
10 \def\eqlistlabel#1{#1}
11 \newcommand{\eqlistauto}[1]{}
12 \newcommand{\eqlistnoauto}{}

```

File 140 **lwarp-eqparbox.sty**

§ 249 Package **eqparbox**

(Emulates or patches code by SCOTT PAKIN.)

Pkg eqparbox

eqparbox is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{eqparbox}[2017/09/03]

2 \NewDocumentCommand{\LWR@HTML@eqparbox}{O{t} O{ } O{t} m +m}{%

```

```

3   {%
4     \minipagefullwidth%
5     \parbox[#1][#2][#3]{\linewidth}{#5}%
6   }%
7 }
8 \LWR@formatted{eqparbox}
9
10 \NewDocumentCommand{\LWR@HTML@eqmakebox}{o o m}{%
11   \makebox[#2][#3]%
12 }
13 \LWR@formatted{eqmakebox}
14
15 \NewDocumentCommand{\LWR@HTML@eqframebox}{o o m}{%
16   \framebox[#2][#3]%
17 }
18 \LWR@formatted{eqframebox}
19
20 \NewDocumentEnvironment{LWR@HTML@eqminipage}{O{t} O{} O{t} m}
21 {%
22   \begingroup%
23   \minipagefullwidth%
24   \minipage[#1][#2][#3]{\linewidth}%
25 }%
26 {%
27   \endminipage%
28   \endgroup%
29 }
30
31 \newcommand*\LWR@HTML@eqboxwidth[1]{.25\linewidth}
32 \LWR@formatted{eqboxwidth}
33
34 \newcommand*\LWR@HTML@eqsetminwidth[2]{}
35 \newcommand*\LWR@HTML@eqsetmaxwidth[2]{}
36
37 \newcommand*\LWR@HTML@eqsetminwidthto[2]{}
38 \newcommand*\LWR@HTML@eqsetmaxwidthto[2]{}

```

File 141 **lwarp-errata.sty**

§ 250 Package **errata**

(Emulates or patches code by MICHAEL KOHLHASE.)

Pkg errata

errata is patched for use by lwarp.

This is for v0.3 of errata. A newer version of errata with more features is under development, at which time the lwarp version will have to be updated.

for HTML output: Macros are being defined with the math dollar, so enable the HTML version during package loading:

```
1 \StartDefiningMath
```

Now load the package:

```
2 \LWR@ProvidesPackagePass{errata}[2006/11/12]
```

Patches for dynamic inline math:

```

3 \xpatchcmd{\erratumAdd}
4   {$_a^{\arabic{erratum}}$}
5%   {\inlinemathother$_a^{\arabic{erratum}}$\inlinemathnormal}
6   {\textsubscript{a}\textsuperscript{\arabic{erratum}}}
7   {}
8   {\LWR@patcherror{erratum}{erratumAdd}}
9
10 \xpatchcmd{\erratumDelete}
11  {$_d^{\arabic{erratum}}$}
12%  {\inlinemathother$_d^{\arabic{erratum}}$\inlinemathnormal}
13  {\textsubscript{d}\textsuperscript{\arabic{erratum}}}
14  {}
15  {\LWR@patcherror{erratum}{erratumDelete}}
16
17 \xpatchcmd{\erratumReplace}
18  {$_r^{\arabic{erratum}}$}
19%  {\inlinemathother$_r^{\arabic{erratum}}$\inlinemathnormal}
20  {\textsubscript{r}\textsuperscript{\arabic{erratum}}}
21  {}
22  {\LWR@patcherror{erratum}{erratumReplace}}
23
24 \xpatchcmd{\erratum}
25  {$_a$}
26%  {\inlinemathother$_a$\inlinemathnormal}
27  {\textsubscript{a}}
28  {}
29  {\LWR@patcherror{erratum}{erratumDelete}}
30
31 \xpatchcmd{\erratum}
32  {$_d^{\@thefnmark}$}
33%  {\inlinemathother$_d^{\@thefnmark}}$\inlinemathnormal}
34  {\textsubscript{d}\textsuperscript{\@thefnmark}}
35  {}
36  {\LWR@patcherror{erratum}{eDelete}}
37
38 \xpatchcmd{\erratum}
39  {$_r^{\@thefnmark}}$}
40%  {\inlinemathother$_r^{\@thefnmark}}$\inlinemathnormal}
41  {\textsubscript{r}\textsuperscript{\@thefnmark}}
42  {}
43  {\LWR@patcherror{erratum}{eReplace}}

```

Finish the current page's errata before closing and reloading the list:

```
44 \preto\PrintErrata{\LWR@maybe@orignewpage}
```

No longer defining math macros with the HTML \$:

```
45 \StopDefiningMath
```

File 142 **lwarp-eso-pic.sty**

§ 251 Package **eso-pic**

(Emulates or patches code by ROLF NIEPRASCHK.)

Pkg eso-pic

eso-pic is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{eso-pic}[2018/04/12]

2 \newcommand*\LenToUnit{}
3 \newcommand{\AtPageUpperLeft}[1]{}
4 \newcommand{\AtPageLowerLeft}[1]{}
5 \newcommand{\AtPageCenter}[1]{}
6 \newcommand{\AtStockLowerLeft}[1]{}
7 \newcommand{\AtStockUpperLeft}[1]{}
8 \newcommand{\AtStockCenter}[1]{}
9 \newcommand{\AtTextUpperLeft}[1]{}
10 \newcommand{\AtTextLowerLeft}[1]{}
11 \newcommand{\AtTextCenter}[1]{}
12 \NewDocumentCommand\AddToShipoutPictureBG{s +m}{}

13 \newcommand\AddToShipoutPicture{\AddToShipoutPictureBG}
14 \NewDocumentCommand\AddToShipoutPictureFG{s +m}{}
15 \newcommand*\ClearShipoutPictureBG{}
16 \newcommand*\ClearShipoutPicture{}
17 \newcommand*\ClearShipoutPictureFG{}
18 \newcommand\gridSetup[6][1]{}

```

File 143 **lwarp-esvect.sty**§ 252 Package **esvect***(Emulates or patches code by EDDIE SAUDRAIS.)*

Pkg esvect

esvect is used as-is for SVG math, and emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{esvect}% no date given

2 \begin{warpMathJax}
3 \CustomizeMathJax{newcommand\LWRresvectv}[1]{\overrightarrow{#1}}
4 \CustomizeMathJax{newcommand\LWRresvectvstar}[2]{\overrightarrow{#1}\!_{#2}}
5 \CustomizeMathJax{newcommand\v{v}}{\ifstar\LWRresvectvstar\LWRresvectv}
6 \end{warpMathJax}

```

File 144 **lwarp-etoc.sty**§ 253 Package **etoc**

Pkg etoc

etoc is ignored. All commands are nullified.

**\tableofcontents with \ref**

The etoc package uses a non-standard syntax which looks ahead after a `\tableofcontents` for a following `\ref`. These `\refs` appear in the HTML result unless they are removed. Where a `\tableofcontents` is followed by `\ref`, and perhaps also `\label` as well, enclose all of them inside `\warpprintonly`:

```

\warpprintonly{\tableofcontents
\label{toc:def}}
\ref{toc:abc}

```

or place all code related to a local `\tableofcontents` inside a `warpprint` environment.

 **home page** Be sure to keep the initial `\tableofcontents` on the home page, perhaps in its own `\warpHTMLonly` macro or `warpHTML` environment.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{etoc}[2019/11/17]

2 \def\etocsetlevel#1#2{}
3 \def\etocskipfirstprefix{}
4 \let\etocthename \empty
5 \let\etocthenumber \empty
6 \let\etocthepage \empty
7 \let\etocthelinkedname \empty
8 \let\etocthelinkednumber \empty
9 \let\etocthelinkedpage \empty
10 \let\etocthelink \@firstofone % prior to 1.08j its was \let to \empty
11 \DeclareRobustCommand*\etocname {}
12 \DeclareRobustCommand*\etocnumber{}
13 \DeclareRobustCommand*\etocpage {}
14 \DeclareRobustCommand*\etoclink {} \@firstofone
15 \DeclareRobustCommand*\etocifnumbered{\@firstoftwo}
16 \DeclareRobustCommand*\etociffirst{\@firstoftwo}
17 \DeclareRobustCommand*\etocifwasempty{\@firstoftwo}
18 \let\etocaftertitlehook \empty
19 \let\etocaftercontentshook \empty
20 \def\etoc\tableofcontents{}
21 \newcommand*\localtableofcontents{}
22 \newcommand*\localtableofcontentswithrelativedepth[1]{}
23 \newcommand\etocsettocstyle[2]{}
24 \long\def\etocsetstyle#1#2#3#4#5{}
25 \def\etocfontminustwo {\normalfont \LARGE \bfseries}
26 \def\etocfontminusone {\normalfont \large \bfseries}
27 \def\etocfontzero {\normalfont \large \bfseries}
28 \def\etocfontone {\normalfont \normalsize \bfseries}
29 \def\etocfonttwo {\normalfont \normalsize}
30 \def\etocfontthree {\normalfont \footnotesize}
31 \def\etocsepminustwo {4ex \@plus .5ex \@minus .5ex}
32 \def\etocsepminusone {4ex \@plus .5ex \@minus .5ex}
33 \def\etocsepzero {2.5ex \@plus .4ex \@minus .4ex}
34 \def\etocseppone {1.5ex \@plus .3ex \@minus .3ex}
35 \def\etocseptwo {.5ex \@plus .1ex \@minus .1ex}
36 \def\etocseptthree {.25ex \@plus .05ex \@minus .05ex}
37 \def\etocbaselinespreadminustwo {1}
38 \def\etocbaselinespreadminusone {1}
39 \def\etocbaselinespreadzero {1}
40 \def\etocbaselinespreadone {1}
41 \def\etocbaselinespreadtwo {1}
42 \def\etocbaselinespreadthree {.9}
43 \def\etocminustwoleftmargin {1.5em plus 0.5fil}
44 \def\etocminustworightmargin {1.5em plus -0.5fil}
45 \def\etocminusoneleftmargin {1em}
46 \def\etocminusonerightmargin {1em}
47 \def\etoc\clineleaders
48 {\hbox{\normalfont\normalsize\hb@xt@2ex {\hss.\hss}}}
49 \def\etocabbrevpagename {p.~}
50 \def\etocpartname {Part}% modified 1.08b
51 \def\etocbookname {Book}
52 \def\etocdefaultlines{}
53 \def\etocabovetocskip{3.5ex \@plus 1ex \@minus .2ex}

```

```

54 \def\etocbelowtocskip{3.5ex \@plus 1ex \@minus .2ex}
55 \def\etoccolumnsep{2em}
56 \def\etocmulticolsep{0ex}
57 \def\etocmulticolpretolerance{-1}
58 \def\etocmulticoltolerance{200}
59 \def\etocdefaultnbcol{2}
60 \def\etocinnertopsep{2ex}
61 \newcommand\etocmulticolstyle[2][{}]{
62 \def\etocinnerbottomsep{3.5ex}
63 \def\etocinnerleftsep{2em}
64 \def\etocinnerrightsep{2em}
65 \def\etocoprul{\hrule}
66 \def\etocleftrule{\vrule}
67 \def\etocrightrule{\vrule}
68 \def\etocbottomrule{\hrule}
69 \def\etocoprulecolorcmd{\relax}
70 \def\etocbottomrulecolorcmd{\relax}
71 \def\etocleftrulecolorcmd{\relax}
72 \def\etocrightrulecolorcmd{\relax}
73 \newcommand*\etocruledstyle[2][{}]{
74 \def\etocframedmphook{\relax}
75 \long\def\etocbkgcolorcmd{\relax}
76 \newcommand*\etocframedstyle[2][{}]{
77 \def\etocmulticol{}
78 \def\etocruled{}
79 \def\etocframed{}
80 \def\etoclocalmulticol{}
81 \def\etoclocalruled{}
82 \def\etoclocalframed{}
83 \def\etocarticlestyle{}
84 \def\etocarticlestylenomarks{}
85 \def\etocbookstyle{}
86 \def\etocbookstylenomarks{}
87 \let\etocreportstyle\etocbookstyle
88 \let\etocreportstylenomarks\etocbookstylenomarks
89 \def\etocmemoirtocstofmt #1#2{}
90 \def\etocmemoirstyle{}
91 \def\etocscrartclstyle{}
92 \let\etocscrbookstyle\etocscrartclstyle
93 \let\etocscrreprtstyle\etocscrartclstyle
94 \def\etocstandarddisplaystyle{\etocarticlestyle}
95 \newcommand*\etocmarkboth[1]{}
96 \newcommand*\etocmarkbothnouc[1]{}
97 \newcommand\etocstocstyle[3][section]{}
98 \newcommand\etocstocstylewithmarks[4][section]{}
99 \newcommand\etocstocstylewithmarksnouc[4][section]{}
100 \def\etocignoretoctocdepth{}
101 \def\etocsettocdepth[1]{}
102 \def\etocdepthtag #1#{\Etoc@depthtag }
103 \def\Etoc@depthtag #1{}
104 \def\etocignoredepthtags {}
105 \def\etocobeydepthtags {}
106 \def\etocsettagdepth #1#2{}
107 \def\invisibletableofcontents {}
108 \def\invisiblelocaltableofcontents{}
109 \def\etocsetnexttocdepth #1{}
110 \def\etocsetlocaltop #1#{\Etoc@set@localtop}
111 \def\Etoc@set@localtop #1{}
112 \def\etocstandardlines {}
113 \def\etococlines {}

```

```

114 \let\etocaftertohook \@empty
115 \let\etocbeforetitlehook \@empty
116 \appto\tableofcontents{\def\tableofcontents{}}
```

File 145 **lwarp-eurosym.sty**

§ 254 Package **eurosym**

(Emulates or patches code by HENRIK THEILING.)

Pkg eurosym eurosym is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{eurosym}[1998/08/06]

2 \renewrobustcmd\officialeuro{\HTMLentity{euro}}
3 \let\geneuro\officialeuro
4 \let\geneuronarrow\officialeuro
5 \let\geneurowide\officialeuro
6 \let\euro\officialeuro
7 \renewrobustcmd\eurobars{}
8 \renewrobustcmd\eurobarsnarrow{}
9 \renewrobustcmd\eurobarswide{}

```

File 146 **lwarp-everypage.sty**

§ 255 Package **everypage**

(Emulates or patches code by SERGIO CALLEGARI.)

Pkg everypage everypage is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{everypage}[2007/06/20]

2 \newcommand*\AddEverypageHook[1]{}
3 \newcommand*\AddThispageHook[1]{}

```

File 147 **lwarp-everyshi.sty**

§ 256 Package **everyshi**

(Emulates or patches code by MARTIN SCHRÖDER.)

Pkg everyshi ignored.

for HTML output: Discard all options for lwarp-everyshi:

```

1 \LWR@ProvidesPackageDrop{everyshi}[2001/05/15]

2 \let\EveryShipout\relax
3 \newcommand*\EveryShipout[1]{}
4
5 \let\AtNextShipout\relax
6 \newcommand*\AtNextShipout[1]{}

```

File 148 **lwarp-extarrows.sty**

§ 257 Package **extarrows**

(Emulates or patches code by HUYNH KY ANH.)

Pkg extarrows

extarrows is used as-is for SVG math, and emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{extarrows}[2008/05/15]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\Newextarrow\xLongleftarrow{10,10}{0x21D0}}
4 \CustomizeMathJax{\Newextarrow\xLongrightarrow{10,10}{0x21D2}}
5 \CustomizeMathJax{\Newextarrow\xLonglefttrightarrow{10,10}{0x21D4}}
6 \CustomizeMathJax{\Newextarrow\xLeftrightarrow{10,10}{0x21D4}}
7 \CustomizeMathJax{\Newextarrow\xlonglefttrightarrow{10,10}{0x2194}}
8 \CustomizeMathJax{\Newextarrow\xleftrightarrow{10,10}{0x2194}}
9 \CustomizeMathJax{\let\xlongleftarrow\xleftarrow}
10 \CustomizeMathJax{\let\xlongrightarrow\xrightarrow}
11 \end{warpMathJax}

```

File 149 **lwarp-extramarks.sty**

§ 258 Package **extramarks**

(Emulates or patches code by PIET VAN OOSTRUM.)

Pkg extramarks

extramarks is ignored.

for HTML output: Discard all options for lwarp-extramarks:

```

1 \LWR@ProvidesPackageDrop{extramarks}[2019/01/31]

2 \newcommand*{\extramarks}[2]{}
3 \newcommand*{\firstleftxmark}{}
4 \newcommand*{\lastleftxmark}{}
5 \newcommand*{\firstrightxmark}{}
6 \newcommand*{\lastrightxmark}{}
7 \newcommand*{\firstxmark}{}
8 \newcommand*{\lastxmark}{}
9 \newcommand*{\topxmark}{}
10 \newcommand*{\topleftxmark}{}
11 \newcommand*{\toprightxmark}{}
12 \newcommand*{\firstleftmark}{}
13 \newcommand*{\lastrightmark}{}
14 \newcommand*{\firstrightmark}{}
15 \newcommand*{\lastleftmark}{}

```

File 150 **lwarp-fancybox.sty**

§ 259 Package **fancybox**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg fancybox

fancybox is supported with some patches.

[framed equation example](#) fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
... }{...
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

[framing alternatives](#) \fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

[framed table example](#) The fancybox documentation's example of a framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method does lose some HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
...
\end{tabular}
\end{fminipage}
\end{table}
```

 [framed verbatim](#) lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
\VerbatimEnvironment
\fminipage{#1}
\beginVerbatim
}{
\endVerbatim
\endfminipage
}
```

framed <code>\VerbBox</code>	<code>fancybox</code> 's <code>\VerbBox</code> may be used inside <code>\fbox</code> .
indented alignment	<code>LVerbatim</code> , <code>\LVerbatimInput</code> , and <code>\LUseVerbatim</code> indent with horizontal space which may not line up exactly with what <i>pdftotext</i> detects. Some lines may be off slightly in their left edge.
fancybox, fancyvrb ⚠ <code>\VerbatimFootnotes</code> ⚠ sectioning or displaymath	<p>If using <code>fancybox</code> or <code>fancyvrb</code> with <code>\VerbatimFootnotes</code>, and using footnotes in a sectioning command or display math, use <code>\footnotemark</code> and <code>\footnotetext</code>:</p> <pre style="margin-left: 20px;">\subsection[Subsection Name] {Subsection Name\protect\footnotemark} \footnotetext{A footnote with \verb+verbtim+.}</pre> <p>and likewise for equations or display math.</p> <p>At present there is a bug such that paragraph closing tags are not present in footnotes when <code>\VerbatimFootnotes</code> are selected. The browser usually compensates.</p> <pre style="margin-left: 20px;">1 \LWR@ProvidesPackagePass{fancybox}[2010/05/15]</pre> <p>After the preamble is loaded, after any patches to <code>Verbatim</code>:</p> <pre style="margin-left: 20px;">2 \AfterEndPreamble{ 3 \LWR@traceinfo{Patching fancybox.}</pre> <p><code>\VerbatimFootnotes</code> Patched to use the new version.</p> <pre style="margin-left: 20px;">4 \def\VerbatimFootnotes{% 5 \let\@footnotetext\@footnotetext% 6 \let\LWR@footnotetext\@footnotetext% lwarp 7 }</pre> <p><code>\V@footnotetext</code> Patches in a subset of <code>lwarp</code>'s <code>\LWR@footnotetext</code> to the <code>fancyvrb</code> version of <code>\V@footnotetext</code>.</p> <pre style="margin-left: 20px;">8 \def\V@footnotetext{% 9 \LWR@traceinfo{V@footnotetext}%</pre> <p>Place an autopage marker so that back references to citations inside a footnote will link closer to the footnote text, if possible.</p> <pre style="margin-left: 20px;">10 \LWR@newautopagelabel{page}%</pre> <p>Take the current footnote box, then append:</p> <pre style="margin-left: 20px;">11 \global\setbox\LWR@footnotebox=\vbox\bgroup%</pre> <p>Add to any current footnotes:</p> <pre style="margin-left: 20px;">12 \unvbox\LWR@footnotebox%</pre> <p>Remember the footnote number for <code>\ref</code>:</p> <pre style="margin-left: 20px;">13 \protected@edef\@currentlabel{% 14 \csname p@footnote\endcsname\@thefnmark% 15 }% @currentlabel</pre> <p>Use HTML superscripts in the footnote even inside a <code>lateximage</code>:</p> <pre style="margin-left: 20px;">16 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%</pre> <p>Use paragraph tags if in a tabular data cell or a <code>lateximage</code>:</p> <pre style="margin-left: 20px;">17 \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%</pre>

Append the footnote to the list:

```
18 \@makefntext{}
```

The footnote text will follow after \V@@@footnotetext has completed.

```
19 \bgroup%
20 \aftergroup\V@@@footnotetext%
```

Do not generate autpages inside the footnotes, since they are accumulated at the moment before finally being used perhaps on a later page.

```
21 \let\LWR@newautopagelabel\LWR@null@newautopagelabel%
```

```
22 \ignorespaces%
23 }%
```

\V@@@footnotetext

```
24 \def\V@@@footnotetext{%
25   \LWR@origtilde\LWR@orignewline%
26   \LWR@htmltagc{/\LWR@tagregularparagraph}\LWR@orignewline%
27   \strut\egroup%
28 }
```

```
29 }% AfterEndPreamble
```

```
30 \renewcommand*\@shadowbox}[1]{%
31 \ifbool{FormatWP}%
32 {\InlineClass[border:1px solid black]{shadowbox}{#1}}%
33 {\InlineClass{shadowbox}{#1}}%
34 }
35
36 \renewcommand*\@doublebox}[1]{%
37 \ifbool{FormatWP}%
38 {\InlineClass[border:1px double black]{doublebox}{#1}}%
39 {\InlineClass{doublebox}{#1}}%
40 }
41
42 \renewcommand*\@ovalbox}[2]{%
43 \ifbool{FormatWP}%
44 {\InlineClass[border:1px solid black; border-radius:1ex]{ovalbox}{#2}}%
45 {%
46   \ifthenelse{\isequivalentto{#1}{\thinlines}}%
47     {\InlineClass{ovalbox}{#2}}%
48     {\InlineClass{Ovalbox}{#2}}%
49 }%
50 }
```

Convert minipages, parboxes, and lists into linear text using the LWR@nestspan environment:

```
51 \let\LWR@origSbox\Sbox
52
53 \def\Sbox{\LWR@origSbox\LWR@nestspan}
54
55
56 \let\LWR@origendSbox\endSbox
57
58 \def\endSbox{\endLWR@nestspan\LWR@origendSbox}
```

Beqnarray is adapted for MATHJAX or enclosed inside a lateximage:

```
59 \RenewEnviron{Beqnarray}
60 {\LWR@eqnarrayfactor}
61
62 \csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}
```

\GenericCaption is enclosed in an HTML block:

```
63 \renewcommand{\GenericCaption}[1]{%
64   \LWR@figcaption%
65   \LWR@isolate{#1}%
66   \endLWR@figcaption%
67 }
```

Btrivlist is enclosed in an HTML block. This is a tabular, and does not use \item.

\trivlist

```
{\l/c/r} [\t/c/b]
68 \RenewDocumentEnvironment{Btrivlist}{m o}
69 {%
70   \LWR@stoppars%
71   \begin{BlockClass}{Btrivlist}%
72   \tabular{#1}%
73 }
74 {%
75   \endtabular%
76   \end{BlockClass}%
77   \LWR@startpars%
78 }
```

Btrivlist is also neutralized when used inside a span:

```
79 \AtBeginEnvironment{LWR@nestspan}{%
80   \RenewDocumentEnvironment{Btrivlist}{m o}{}{}%
81 }
```

lwarp's handling of \item is patched to accept fancybox's optional arguments:

```
82 \let\LWRFB@origitemizeitem\LWR@itemizeitem
83 \let\LWRFB@origdescitem\LWR@descitem
84
85 \RenewDocumentCommand{\LWR@itemizeitem}{d()o}{%
86   \IfValueTF{#2}{%
87     \LWRFB@origitemizeitem[#2]%
88   }{%
89     \LWRFB@origitemizeitem%
90   }%
91 }
92
93 \RenewDocumentCommand{\LWR@descitem}{d()o}{%
94   \IfValueTF{#2}{%
95     \LWRFB@origdescitem[#2]~%
96   }{%
97     \LWRFB@origdescitem%
98   }%
99 }
```

```

100 \RenewDocumentCommand{\LWR@nestspanitem}{d()}{%
101   \if@newlist\else{
102     \LWR@htmltagc{br /}%
103     \LWR@orignewline%
104   }\fi%
105   \LWR@origitem%
106 }

```

The various boxed lists become regular lists:

```

107 \renewenvironment{Bitemize}[1]{}
108   {%
109     \LWR@spanwarnformat{Bitemize}%
110     \booltrue{LWR@starting@fancybox}%
111     \begin{itemize}%
112     \boolfalse{LWR@starting@fancybox}%
113   }
114   {\end{itemize}}
115
116 \renewenvironment{Benumerate}[1]{}
117   {%
118     \LWR@spanwarnformat{Benumerate}%
119     \booltrue{LWR@starting@fancybox}%
120     \begin{enumerate}%
121     \boolfalse{LWR@starting@fancybox}%
122   }
123   {\end{enumerate}}
124
125 \renewenvironment{Bdescription}[1]{}
126   {%
127     \LWR@spanwarnformat{Bdescription}%
128     \booltrue{LWR@starting@fancybox}%
129     \begin{description}%
130     \boolfalse{LWR@starting@fancybox}%
131   }
132   {\end{description}}

```

`\boxput` simply prints one then the other argument, side-by-side instead of above and behind:

```

133 \RenewDocumentCommand{\boxput}{s d() m m}{%
134   \IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
135 }

```

Neutralized commands:

```

136 \RenewDocumentCommand{\fancyput}{s d() m}{%
137 \RenewDocumentCommand{\thisfancyput}{s d() m}{%
138
139 \RenewDocumentCommand{\fancypage}{m m}{%
140 \RenewDocumentCommand{\thisfancypage}{m m}{%
141
142 \def\LandScape#1{}
143 \def\endLandScape{}
144 \def\@Landscape#1#2#3{}
145 \def\endLandscape{}

```

Low-level patches for UseVerbatim and friends:

```

146 \let\LWRFB@UseVerbatim\UseVerbatim
147 \renewcommand*\UseVerbatim}[1]{%
148   \LWR@atbeginverbatim{Verbatim}%
149   \LWRFB@UseVerbatim{#1}%
150   \LWR@afterendverbatim%
151 }
152
153 \let\LWRFB@LUseVerbatim\LUseVerbatim
154
155 \renewcommand*\LUseVerbatim}[1]{%
156   \LWR@atbeginverbatim{LVerbatim}%
157   \noindent%
158   \LWRFB@LUseVerbatim{#1}%
159   \LWR@afterendverbatim%
160 }
161
162 \def\@BUseVerbatim[#1]#2{%
163   \LWR@atbeginverbatim{BVerbatim}%
164   \LWRFB@UseVerbatim{#2}%
165   \LWR@afterendverbatim%
166 }

```

File 151 **lwarp-fancyhdr.sty**

§ 260 Package **fancyhdr**

(Emulates or patches code by PIET VAN OOSTRUM.)

Pkg fancyhdr

fancyhdr is ignored.

for HTML output: Discard all options for lwarp-fancyhdr:

```

1 \LWR@ProvidesPackageDrop{fancyhdr}[2021/01/04]

2 \newcommand*\fancyhead}[2][{}
3 \newcommand*\fancyfoot}[2][{}
4 \newcommand*\fancyhf}[2][{}
5
6 \newcommand*\lhead}[2][{}
7 \newcommand*\chead}[2][{}
8 \newcommand*\rhead}[2][{}
9 \newcommand*\lfoot}[2][{}
10 \newcommand*\cfoot}[2][{}
11 \newcommand*\rfoot}[2][{}
12 \newcommand*\headrulewidth{}
13 \newcommand*\footrulewidth{}
14 \providecommand*\headruleskip{0pt}
15 \providecommand*\footruleskip{0pt}
16 \newcommand*\plainheadrulewidth{0pt}
17 \newcommand*\plainfootrulewidth{0pt}
18 \def\fancyplain#1#2{#1}
19 \newcommand*\headrule{}
20 \newcommand*\footrule{}
21 \newlength\headwidth
22 \newcommand*\fancycenter}[1][1em]{}

```

```

23 \newcommand*\fancyheadoffset}[2][{}
24 \newcommand*\fancyfootoffset}[2][{}
25 \newcommand*\fancyhfoffset}[2][{}
26 \newcommand*\fancyheadinit}[1]{
27 \newcommand*\fancyfootinit}[1]{
28 \newcommand*\fancyhfinit}[1]{
29 \newcommand*\iffloatpage}[2]{#2}
30 \newcommand*\ifftopfloat}[2]{#2}
31 \newcommand*\iffbotfloat}[2]{#2}
32 \newcommand*\iffootnote}[2]{#2}
33
34 \newcommand*\fancypagestyle}[1]{%
35   \@ifnextchar[{\f@nch@pagestyle{#1}}{\f@nch@pagestyle{#1}}{}%
36 }
37 \long\def\f@nch@pagestyle#1[#2]#3{

```

File 152 **lwarp-fancypar.sty**

§ 261 Package **fancypar**

(Emulates or patches code by GONZALO MEDINA.)

Pkg fancypar

fancypar is used as-is for print output, and emulated for HTML.

⚠ **css classes** \NotebookPar and related are used as-is inside a lateximage, but for HTML these are emulated as a <div> of class NotebookPar, etc. For HTML, the package options and the macro optional arguments are ignored. The user must provide custom css for each if visual effects are required. See section 7.7.

⚠ **custom styles** If using a custom paragraph style, such as \MyStylePar from the documentation, use the following to generate an HTML <div> of class MyStylePar:

```

... (existing definiton of \MyStylePar, print version) ...
\begin{warpHTML}
\AddFancyparClass{MyStyle}
\end{warpHTML}

```

\MyStylePar is then modified to emulate HTML. An optional argument is allowed, which is ignored.

for HTML output: 1 \LWR@ProvidesPackagePass{fancypar}[2019/01/18]

```

2 \begin{warpHTML}
3 \makeatletter
4
5 \newcommand*\LWR@fancypar}[2]{%
6   \begin{BlockClass}{#1Par}
7     #2
8   \end{BlockClass}
9 }
10
11 \newcommand*\LWR@HTML@NotebookPar}[2][\LWR@fancypar{Notebook}{#2}]
12 \LWR@formatted{NotebookPar}
13
14 \newcommand*\LWR@HTML@ZebraPar}[2][\LWR@fancypar{Zebra}{#2}]
15 \LWR@formatted{ZebraPar}

```

```

16
17 \newcommand{\LWR@HTML@DashedPar}[2][\LWR@fancy@par{Dashed}{#2}}
18 \LWR@formatted{DashedPar}
19
20 \newcommand{\LWR@HTML@MarkedPar}[2][\LWR@fancy@par{Marked}{#2}}
21 \LWR@formatted{MarkedPar}
22
23 \newcommand{\LWR@HTML@UnderlinedPar}[2][\LWR@fancy@par{Underlined}{#2}}
24 \LWR@formatted{UnderlinedPar}
25
26
27 \newcommand{\LWR@HTML@add@fancy@format}{}
28 \LWR@formatted{add@fancy@format}
29
30
31 \newcommand{\AddFancy@par@Class}[1]{%
32   \expandafter\newcommand\csname LWR@HTML@#1Par\endcsname[2][\LWR@fancy@par{#1}{##2}%
33     \LWR@formatted{#1Par}
34   }
35   \LWR@formatted{#1Par}
36 }
37
38 \makeatother
39 \end{warpHTML}

```

File 153 **lwarp-fancyref.sty**

§ 262 Package **fancyref**

(Emulates or patches code by AXEL REICHERT.)

Pkg fancyref fancyref is modified for HTML output.

for HTML output: 1 \LWR@ProvidesPackagePass{fancyref}[1999/02/03]

Hook [fancyref] \fancyrefhook To remove the margin option, if \fancyrefhook is anything other than the paren option, then force it to the default instead. (Comparing to the margin option was not possible since lwarp has revised the meaning of \mbox so the comparison failed.)

```

2 \newcommand*\LWR@fref@paren@fancyrefhook[1]{(#1)}
3
4 \ifdefstrequal{\fancyrefhook}{\LWR@fref@paren@fancyrefhook}
5 {}{
6   \renewcommand*\fancyrefhook[1]{#1}%
7 }

```

File 154 **lwarp-fancytabs.sty**

§ 263 Package **fancytabs**

Pkg fancytabs fancytabs is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fancytabs}[2016/03/29]

```

2 \newcommand{\fancytab}[3][RIGHT]{
3 \newcommand{\fancytabsStyle}[1]{
4 \newcommand{\fancytabsHeight}[1]{
5 \newcommand{\fancytabsWidth}[1]{
6 \newcommand{\fancytabsCount}[1]{
7 \newcommand{\fancytabsLeftColor}[1]{
8 \newcommand{\fancytabsRightColor}[1]{
9 \newcommand{\fancytabsTop}[1]{
10 \newcommand{\fancytabsTextVPos}[1]{
11 \newcommand{\fancytabsTextHPos}[1]{
12 \newcommand{\fancytabsGap}[1]{
13 \newcommand{\fancytabsFloor}[1]{
14 \newcommand{\fancytabsRotate}[1]{

```

File 155 **lwarp-fancyvrb.sty**

§ 264 Package **fancyvrb**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg fancyvrb

fancyvrb is supported with some patches.

HTML classes The fancy verbatim environment is placed inside a `<div>` of class `fancyvrb`. The label is placed inside a `<div>` of class `fancyvrblabel`. The verbatim text itself is placed inside a `<div>` of class `verbatim`.

fancybox, fancyvrb If using `fancybox` or `fancyvrb` with `\VerbatimFootnotes`, and using footnotes in a sectioning command or display math, use `\footnotemark` and `\footnotetext`:

⚠ `\VerbatimFootnotes`
 ⚠ sectioning or displaymath

```

\subsection[Subsection Name]
  {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbatim+.}

```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

```

1 \AtBeginDocument{\RequirePackage{xcolor}}% for \convertcolorspec
2
3 \LWR@ProvidesPackagePass{fancyvrb}[2008/02/07]

```

Initial default patch for `fancyvrb`:

```
4 \fvset{frame=none}%
```

After the preamble is loaded, after any patches to `Verbatim`:

```
5 \AfterEndPreamble{
6 \LWR@traceinfo{Patching fancyvrb.}

```

`\VerbatimFootnotes`

Patched to use the new version.

```
7 \def\VerbatimFootnotes{%
8   \let\@footnotetext\@footnotetext%

```

```

9   \let\footnote\V@footnote%
10  \let\LWR@footnotetext\V@footnotetext% lwarp
11 }

```

\V@@footnotetext

Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@@footnotetext.

```

12 \def\V@@footnotetext{%
13 \LWR@traceinfo{V@footnotetext}%

```

Place an autopage marker so that back references to citations inside a footnote will link closer to the footnote text, if possible.

```

14 \LWR@newautopagelabel{page}%

```

Take the current footnote box, then append:

```

15 \global\setbox\LWR@footnotebox=\vbox\bgroup%

```

Add to any current footnotes:

```

16 \unvbox\LWR@footnotebox%

```

Remember the footnote number for \ref:

```

17 \protected@edef\@currentlabel{%
18 \csname p@footnote\endcsname\@thefnmark%
19 }% @currentlabel

```

Use HTML superscripts in the footnote even inside a lateximage:

```

20 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%

```

Use paragraph tags if in a tabular data cell or a lateximage:

```

21 \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%

```

Append the footnote mark to the list:

```

22 \@makefntext{}%

```

The footnote text will follow after \V@@@footnotetext has completed.

```

23 \bgroup%
24 \aftergroup\V@@@footnotetext%

```

Do not generate autopages inside the footnotes, since they are accumulated at the moment before finally being used perhaps on a later page.

```

25 \let\LWR@newautopagelabel\LWR@null@newautopagelabel%

```

```

26 \ignorespaces%
27 }%

```

\V@@@footnotetext

```

28 \def\V@@@footnotetext{%
29 \LWR@origtilde\LWR@orignewline%
30 \LWR@htmltagc{/\LWR@tagregularparagraph}\LWR@orignewline%
31 \strut\bgroup%
32 }

```

```

33 \preto\FVB@Verbatim{\LWR@forcenewpage}
34 \preto\FVB@LVerbatim{\LWR@forcenewpage}
35 % \preto\FVB@BVerbatim{\LWR@forcenewpage}% Fails, so done below.

```

Simplified to remove PDF formatting:

```

36 \def\FV@BeginListFrame@Single{%
37   \FV@SingleFrameLine{\z}%
38 }
39
40 \def\FV@EndListFrame@Single{%
41   \FV@SingleFrameLine{\@ne}%
42 }
43
44 \def\FV@BeginListFrame@Lines{%
45   \FV@SingleFrameLine{\z}%
46 }
47
48 \def\FV@EndListFrame@Lines{%
49   \FV@SingleFrameLine{\@ne}%
50 }
51
52 \renewcommand*\FV@SingleFrameSep{}
```

Adds HTML formatting:

```

53 \def\FV@BUseVerbatim#1{%
54   \FV@BVerbatimBegin#1\FV@BVerbatimEnd%
55 }
```

`\LWR@FVstyle` Holds the style of the verbatim.

```

56 \newcommand*\LWR@FVstyle{}
```

The following patches to `Verbatim` are executed at the start and end of the environment, depending on the choice of frame. Original code is from the `fancyvrb` package.

```

57 \newcommand*\LWR@fvstartnone{%
58 \LWR@traceinfo{fvstartnone}%
59 % \hbox to\z@{
60 \BlockClass[\LWR@FVstyle]{fancyvrb}
61 \LWR@stoppars
62 \ifx\FV@LabelPositionTopLine\relax\else
63   \ifx\FV@LabelBegin\relax\else
64     \FancyVerbRuleColor{\LWR@FVfindbordercolor}
65     \LWR@htmltagc{%
66       div class=\textquotedbl{}fancyvrblabel\textquotedbl % space
67       style=\textquotedbl{}color: \LWR@origpound\LWR@tempcolor\textquotedbl%
68     }
69     \LWR@print@textrm{\FV@LabelBegin}% \textrm preserves emdash
70     \LWR@htmltagc{/div}\LWR@orignewline%
71   \fi
72 \fi
73 \LWR@atbeginverbatim{verbatim}%
74 % }%
75 }
76
77 \newcommand*\LWR@fvendnone{%
78 \LWR@traceinfo{fvendnone}%
79 % \hbox to\z@{
80 \LWR@afterendverbatim%
```

```

81 \LWR@stoppars%
82 \ifx\FV@LabelPositionBottomLine\relax\else
83   \ifx\FV@LabelEnd\relax\else
84     \FancyVerbRuleColor{\LWR@FVfindbordercolor}
85     \LWR@htmltagc{%
86       div class=\textquotedbl{}fancyvrblabel\textquotedbl\ % space
87       style=\textquotedbl{}color:\LWR@origpound\LWR@tempcolor\textquotedbl%
88     }
89     \LWR@print@textrm{\FV@LabelEnd}
90     \LWR@htmltagc{/div}\LWR@orignewline%
91   \fi
92 \fi
93 \endBlockClass
94 }
95
96 \newcommand*\LWR@fvstartsingle}{%
97 \LWR@traceinfo{fvstartsingle}%
98 \LWR@fvstartnone%
99 \FV@BeginListFrame@Single%
100 }
101
102 \newcommand*\LWR@fvendsingle}{%
103 \LWR@traceinfo{fvendsingle}%
104 \FV@EndListFrame@Single%
105 \LWR@fvendnone%
106 }
107
108 \newcommand*\LWR@fvstartline}{%
109 \LWR@traceinfo{fvstartline}%
110 \LWR@fvstartnone%
111 % \setlength{\LWR@templengthone}{\baselineskip}%
112 \FV@BeginListFrame@Lines%
113 % \setlength{\baselineskip}{\LWR@templengthone}%
114 % \setlength{\baselineskip}{5pt}%
115 }
116
117 \newcommand*\LWR@fvendline}{%
118 \LWR@traceinfo{fvendline}%
119 \FV@EndListFrame@Lines%
120 \LWR@fvendnone%
121 }

```

The following patches select the start/left/right/end behaviors depending on frame. Original code is from the fancyvrb package.

```

122 \newcommand*\LWR@FVfindbordercolor}{%
123 \FancyVerbRuleColor%
124 \LWR@findcurrenttextcolor%
125 \color{black}%
126 }
127
128 % border width of \FV@FrameRule
129 \newcommand*\LWR@FVborderstyle}[1]{%
130 padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ; % space
131 \LWR@FVfindbordercolor\LWR@indentHTMLtwo%
132 border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt % space
133 solid {\FancyVerbRuleColor{\LWR@origpound\LWR@tempcolor}} ; % space
134 }
135
136 \def\FV@Frame@none{%

```

```

137 \renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle}%
138 \let\FV@BeginListFrame\LWR@fvstartnone%
139 \let\FV@LeftListFrame\relax%
140 \let\FV@RightListFrame\relax%
141 \let\FV@EndListFrame\LWR@fvendnone}
142
143 \FV@Frame@none% default values
144
145 \def\FV@Frame@single{%
146 \renewcommand*{\LWR@FVstyle}{%
147   \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
148   \LWR@FVborderstyle{}}%
149 }%
150 \let\FV@BeginListFrame\LWR@fvstartsingle%
151 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
152 \let\FV@RightListFrame\FV@RightListFrame@Single%
153 \let\FV@EndListFrame\LWR@fvendsingle}
154
155 \def\FV@Frame@lines{%
156 \renewcommand*{\LWR@FVstyle}{%
157   \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
158   \LWR@FVborderstyle{-top}%
159   \LWR@indentHTMLtwo%
160   \LWR@FVborderstyle{-bottom}%
161 }%
162 \let\FV@BeginListFrame\LWR@fvstartline%
163 \let\FV@LeftListFrame\relax%
164 \let\FV@RightListFrame\relax%
165 \let\FV@EndListFrame\LWR@fvendline}
166
167 \def\FV@Frame@topline{%
168 \renewcommand*{\LWR@FVstyle}{%
169   \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
170   \LWR@FVborderstyle{-top}%
171 }%
172 \let\FV@BeginListFrame\LWR@fvstartline%
173 \let\FV@LeftListFrame\relax%
174 \let\FV@RightListFrame\relax%
175 \let\FV@EndListFrame\LWR@fvendnone}
176
177 \def\FV@Frame@bottomline{%
178 \renewcommand*{\LWR@FVstyle}{%
179   \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
180   \LWR@FVborderstyle{-bottom}%
181 }%
182 \let\FV@BeginListFrame\LWR@fvstartnone%
183 \let\FV@LeftListFrame\relax%
184 \let\FV@RightListFrame\relax%
185 \let\FV@EndListFrame\LWR@fvendline}

```

Seems to be required in some situations:

```

186 \def\FV@FrameFillLine{}%

187 \def\FV@Frame@leftline{%
188 \renewcommand*{\LWR@FVstyle}{%
189   \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
190   \LWR@FVborderstyle{-left}%
191 }%
192 % To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)

```

```

193 \ifx\FancyVerbFillColor\relax%
194 \let\FV@FrameFillLine\relax%
195 \else%
196 \@tempdima\FV@FrameRule\relax%
197 \multiply\@tempdima-\tw@%
198 \edef\FV@FrameFillLine{%
199 {\noexpand\FancyVerbFillColor{\vrule\@width\number\@tempdima sp}}%
200 \kern-\number\@tempdima sp}}%
201 \fi%
202 \let\FV@BeginListFrame\LWR@fvstartnone%
203 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
204 \let\FV@RightListFrame\relax%
205 \let\FV@endListFrame\LWR@fvendnone}

```

Adds the optional label to the top and bottom edges. Original code is from the fancyvrb package.

```

206 \def\FV@SingleFrameLine#1{%
207 % \hbox to\z@{%
208 % \kern\leftmargin
209 % \ifnum#1=\z@\relax
210 % \let\FV@Label\FV@LabelBegin
211 % \else
212 % \let\FV@Label\FV@LabelEnd
213 % \fi
214 % \ifx\FV@Label\relax
215 % \FancyVerbRuleColor{\vrule \@width\linewidth \@height\FV@FrameRule}%
216 % \else
217 % \ifnum#1=\z@
218 % \setbox\z@\hbox{\strut\enspace\FV@LabelBegin\enspace\strut}%
219 % \ifx\FV@LabelPositionTopLine\relax
220 % \else
221 % \fi
222 % \else
223 % \setbox\z@\hbox{\strut\enspace\FV@LabelEnd\enspace\strut}%
224 % \ifx\FV@LabelPositionBottomLine\relax
225 % \else
226 % \fi
227 % \fi
228 % \fi
229 % \hss
230 % }
231 }

```

Processes each line, adding optional line numbers. Original code is from the fancyvrb package.

```

232 \def\FV@ListProcessLine#1{%
233 \hbox to \hsize{%
234 % \kern\leftmargin
235 % \hbox to \VerbatimHTMLWidth {%
236 % \ifcvoid{FV@LeftListNumber}{\kern 2.5em}%
237 % FV@LeftListNumber%
238 % FV@LeftListFrame
239 % FancyVerbFormatLine{#1}%
240 % \hss%
241 % FV@RightListFrame
242 % FV@RightListNumber%
243 % }%

```

```

244     \hss% required to avoid underfull hboxes
245 }
246 }

247 \def\FV@ListProcessLine@i#1{%
248 %   \hbox{%
249     \ifvoid\@labels\else
250       \hbox to \z@\kern\@totalleftmargin\box\@labels\hss}%
251     \fi
252     \FV@ListProcessLine{#1}%
253 %   }%
254 %   \let\FV@ProcessLine\FV@ListProcessLine@ii%
255 }

256 \def\FV@ListProcessLastLine{}

```

Env BVerbatim

```

257
258 \xpretocmd{\FV@BeginVBox}
259   {%
260     \LWR@forcenewpage% instead of \preto
261     \LWR@atbeginverbatim{bverbatim}%
262   }
263 {}
264 {\LWR@patcherror{fancyvrb}{FV@BeginVBox}}
265
266 \xapptocmd{\FV@EndVBox}
267   {%
268     \LWR@afterendverbatim%
269   }
270 {}
271 {\LWR@patcherror{fancyvrb}{FV@EndVBox}}

```

End of the modifications to make at the end of the preamble:

```
272 } % \AfterEndPreamble
```

File 156 **lwarp-fbox.sty**

§ 265 Package **fbox**

(Emulates or patches code by HERBERT VOSS.)

fbox is patched for use by **lwarp**.

for HTML output: 1 \LWR@ProvidesPackagePass{fbox}[2022/02/20]

This will be \LWR@formatted when \AtBeginDocument:

```
2 \LetLtxMacro\LWR@HTML@fbox\fbox
```

Instead of using the original, the new version is used with all borders:

```
3 \renewcommand*\orig@fbox{\FBox@i[tblr]}
```

\WR@fboxpkg@border

{\langle 1: top/bottom/left/right \rangle}{\langle 2: t/b/l/r \rangle}{\langle 3: padding, or empty \rangle}

Accumulates HTML styles for border, and padding if given:

```

4 \newcommand*\LWR@fboxpkg@border}[3]{%
5   \colorlet{\LWR@border@color}{\csuse{fbox@#2color}}%
6   \protect\convertcolorspec{named}{\LWR@border@color}{HTML}\LWR@tempbordercolor\relax%
7   \appto\LWR@tempone{%
8     border-#1: % space
9     \LWR@printlength{\LWR@atleastonept} % space
10    solid \LWR@origpound%
11  }%
12  \expandafter\appto\expandafter\LWR@tempone\expandafter\LWR@tempbordercolor}%
13  \appto\LWR@tempone[ ;\LWR@indentHTML]%
14  \ifblank{#3}{%
15    \appto\LWR@tempone{%
16      padding-#1: \LWR@printlength{#3} ;\LWR@indentHTML
17    }%
18  }%
19 }
```

A hack to reuse the same code for inline and blocks:

```

20 \newbool{\LWR@fboxpkg@ispar}
21 \boolfalse{\LWR@fboxpkg@ispar}
```

Accumulate HTML styles for left and right padding, depending on \if@fbox@space@left, \if@fbox@space@right:

```

22 \newcommand{\LWR@fboxpkg@lrpadding}[1]{%
23   \csuse{\if@fbox@space@#1}%
24   \appto\LWR@tempone{%
25     padding-#1: \LWR@printlength{\fbox@@sep};\LWR@indentHTML
26   }
27   \else%
28     \appto\LWR@tempone{%
29       padding-#1: 0pt;\LWR@indentHTML
30     }
31   \fi%
32 }
```

The HTML version, modified to use HTML styles and either an \InlineClass or BlockClass:

```

33 \newcommand{\LWR@HTML@FBox@iii}[1]{%
```

Find and set the text color, rule width, margin:

```

34   \LWR@forceminwidth{\fbox@@rule}%
35   \LWR@findcurrenttextcolor%
36   \def\LWR@tempone{%
37     color: \LWR@origpound\LWR@tempcolor ; \LWR@indentHTML
38     margin: 1ex ; \LWR@indentHTML
39   }%
```

Add left/right padding:

```

40   \LWR@fboxpkg@lrpadding{left}%
41   \LWR@fboxpkg@lrpadding{right}%
```

Per the original to decode the borders, in a new way:

```

42 \ifnum\the\@tempcntb>8\relax
43   \advance\@tempcntb by -8\relax
44   \LWR@fboxpkg@border{top}{t}{\fbox@sep}%
45 \fi
46 \ifnum\@tempcntb>3
47   \advance\@tempcntb by -4\relax
48   \LWR@fboxpkg@border{left}{l}{}%
49 \fi
50 \ifnum\@tempcntb>1\relax
51   \LWR@fboxpkg@border{right}{r}{}%
52 \fi
53 \ifodd\@tempcntb
54   \LWR@fboxpkg@border{bottom}{b}{\fbox@sep}%
55 \fi

```

Generate a BlockClass or \InlineClass with the contents:

```

56 \color@begingroup
57 \ifbool{LWR@fboxpkg@ispar}%
58   {%
59     \begin{BlockClass}[\LWR@tempone]{fboxpkg}%
60     #1%
61     \end{BlockClass}%
62   }%
63   {%
64     \InlineClass[\LWR@tempone]{fboxpkg}{%
65     #1%
66     }%
67   }%
68 \color@endgroup
69 \boolfalse{LWR@fboxpkg@ispar}% globally
70 }
71 \LWR@formatted{FBox@iii}

```

For \fparbox, set the use of BlockClass, then reuse the above:

```

72 \long\def\LWR@HTML@FParBox@i[#1]#2{%
73   \booltrue{LWR@fboxpkg@ispar}%
74   \FBox@i[#1]{#2}
75 }
76 \LWR@formatted{FParBox@i}
77
78 \long\def\LWR@HTML@FParBox@ii#1{%
79   \booltrue{LWR@fboxpkg@ispar}%
80   \FBox@i[tblr]{#1}%
81 }
82 \LWR@formatted{FParBox@ii}

```

For MATHJAX, absorb and ignore star and optional arguments:

```

83 \CustomizeMathJax{\let\LWRorigfbox\fbox}
84 \CustomizeMathJax{\newcommand{\LWRfboxpkgtwo}[2][\LWRorigfbox{#2}}
85 \CustomizeMathJax{\renewcommand{\fbox}{\ifstar\LWRfboxpkgtwo\LWRfboxpkgtwo}}
86 \CustomizeMathJax{\newcommand{\fparbox}{\fbox}}

```

File 157 **lwarp-fewerfloatpages.sty**

§ 266 Package **fewerfloatpages**

Pkg fewerfloatpages fewerfloatpages is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fewerfloatpages}[2020/02/14]

```
2 \newcommand\floatpagekeepfraction{\textfraction}
3 \newcounter{floatpagedeferlimit}
4 \newcounter{floatpagekeeplimit}
```

File 158 **lwarp-figcaps.sty**

§ 267 Package **figcaps**

(Emulates or patches code by PATRICK W. DALY.)

Pkg figcaps figcaps is ignored.

for HTML output: Discard all options for lwarp-figcaps:

```
1 \LWR@ProvidesPackageDrop{figcaps}[1999/02/23]

2 \newcommand*\figcapson{}
3 \newcommand*\figcapsoff{}
4 \newcommand*\printfigures{}
5 \newcommand*\figmarkon{}
6 \newcommand*\figmarkoff{}
7 \def\figurecapname{Figure Captions}
8 \def\tablepagename{Tables}
9 \def\figurepagename{Figures}
```

File 159 **lwarp-figsize.sty**

§ 268 Package **figsize**

(Emulates or patches code by ANTHONY A. TANBAKUCHI.)

Pkg figsize figsize is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{figsize}[2002/03/18]

Emulates a virtual 6×9 inch textsize.

```
2 \newlength{\figwidth}
3 \newlength{\figheight}
4
5 \newcommand{\SetFigLayout}[3][0]{%
```

```

6 \setlength{\figheight}{8in}%
7 \setlength{\figheight}{\figheight / #2}%
8 %
9 \setlength{\figwidth}{5.5in}%
10 \setlength{\figwidth}{\figwidth / #3}%
11 }

```

File 160 **lwarp-fitbox.sty**

§ 269 Package **fitbox**

Pkg fitbox fitbox is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fitbox}[2019/02/20]

```

2 \NewDocumentCommand{\fitbox}{s o m}{%
3   \begin{BlockClass}{fitbox}
4   #3
5   \end{BlockClass}
6 }
7
8 \newcommand*\fitboxset[1]{}
9
10 \newdimen\fitboxnatheight
11 \newdimen\fitboxnatwidth
12
13 \newcommand\SetFitboxLayout[3][{}]{

```

File 161 **lwarp-fix2col.sty**

§ 270 Package **fix2col**

Pkg fix2col fix2col is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fix2col}[2015/11/13]

File 162 **lwarp-fixmath.sty**

§ 271 Package **fixmath**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg fixmath fixmath is used as-is for SVG math, and emulated for MATHJAX.

 **limitations** MATHJAX does not have full font support for bold italic Greek.

for HTML output: 1 \LWR@ProvidesPackagePass{fixmath}[2000/04/11]

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}

```

```

5 \LWR@mathjax@addgreek@u@it*{}{}
6 \LWR@mathjax@addletter{\BooleanTrue}{up}{}{\delta}{0394}
7 \LWR@mathjax@addletter{\BooleanTrue}{up}{}{\omega}{03A9}
8 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
9 \end{warpMathJax}

```

File 163 **lwarp-fixme.sty**

§ 272 Package **fixme**

(Emulates or patches code by DIDIER VERNA.)

Pkg fixme

fixme is patched for use by lwarp.

 **external layouts** External layouts (`\fxloadlayouts`) are not supported.

Customized layouts are overwritten by lwarp’s versions `\AtBeginDocument` in order to provide the HTML conversion. If creating a new layout, see lwarp’s changes to provide similar for the new layout, inside a `warpHTML` environment.

User control is provided for setting the HTML styling of the “faces”. The defaults are as follows, and may be changed in the preamble after `fixme` is loaded:

```

\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}

```

for HTML output: 1 \LWR@ProvidesPackagePass{fixme}[2019/01/03]

Restore lwarp’s version of `\@wrindex`, ignoring the `fixme` package’s target option:

```
2 \let\@wrindex\LWR@wrindex
```

Float-related macros required by lwarp:

```

3 \newcommand{\ext@fixme}{lox}
4
5 \renewcommand{\l@fixme}[2]{%
6   \hypertocfloat{1}{fixme}{lox}%
7   {\LWR@nameref{\BaseJobname-autopage-\arabic{LWR@nextautopage}} --- #1}%
8   {#2}
9 }

```

Other modifications. Done `\AtBeginDocument` to hopefully work if the user customizes the layouts.

```

10 \AtBeginDocument{
11
12 \def\FXFaceInlineHTMLStyle{font-weight:bold}
13
14 \renewcommand*\FXLayoutInline[3]{ % space
15   \InlineClass[\FXFaceInlineHTMLStyle]{fixmeinline}%
16   {\@fxttextstd{#1}{#2}{#3}}%
17 }
18

```

```

19 \def\FXFaceEnvHTMLStyle{font-weight:bold}
20
21 \renewcommand*\FXEnvLayoutPlainBegin[2]{%
22   \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
23   \ignorespaces#2 \fxnotename{#1}: \ignorespaces%
24 }
25
26 \renewcommand*\FXEnvLayoutPlainEnd[2]{\endBlockClass}
27
28 \renewcommand*\FXEnvLayoutSignatureBegin[2]{%
29   \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
30   \fxnotename{#1}: \ignorespaces%
31 }
32
33 \renewcommand*\FXEnvLayoutSignatureEnd[2]{\@fxsignature{#2}\endBlockClass}
34
35 \def\FXFaceSignatureHTMLStyle{font-style:italic}
36
37 \DeclareRobustCommand*\@fxsignature[1]{%
38   \ifthenelse{\equal{#1}{}}%
39     {}%
40     { -- {\InlineClass[\FXFaceSignatureHTMLStyle]{fixmesignature}{#1}}}%
41 }
42
43
44 \def\FXFaceTargetHTMLStyle{font-style:italic}
45
46 \renewcommand\FXTargetLayoutPlain[2]{%
47   \InlineClass[\FXFaceTargetHTMLStyle]{fixmetarget}{#2}%
48 }
49
50 }% \AtBeginDocument

```

File 164 **lwarp-fixmetodonotes.sty**

§ 273 Package **fixmetodonotes**

(Emulates or patches code by GIOELE BARABUCCI.)

Pkg fixmetodonotes

fixmetodonotes is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{fixmetodonotes}[2013/04/28]
2 \renewcommand{\NOTES@addtolist}[2]{%
3   \refstepcounter{NOTES@note}%
4 % \phantomsection% REMOVED
5   \addcontentsline{notes}{NOTES@note}{%
6     \protect\numberline{\theNOTES@note}{#1}: {#2}}%
7   }%
8 }
9
10 \renewcommand{\NOTES@marker}[2]{\fbox{%
11   \textcolor{#2}{% WAS \color
12     \textbf{#1}}}%
13   }}
14
15 \renewcommand{\NOTES@colorline}[2]{%

```

```

16 \bgroup%
17 \ULon{\LWR@backgroundcolor{#1}{#2}}%
18 }

```

File 165 **lwarp-flafter.sty**

§ 274 Package **flafter**

Pkg flafter

flafter is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{flafter}[2018/01/08]
2 \providecommand\fl@trace[1]{}

```

File 166 **lwarp-flippdf.sty**

§ 275 Package **flippdf**

Pkg flippdf

flippdf is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{flippdf}[2006/06/30]

2 \newcommand\FlipPDF{}
3 \newcommand\UnFlipPDF{}

```

File 167 **lwarp-float.sty**

§ 276 Package **float**

Pkg float

(Emulates or patches code by ANSELM LINGNAU.)

float is emulated.

Float styles boxed and ruled are emulated by css and a float class according to style.

The HTML `<figure>` class is set to the float type, so css may also be used to format the float and its caption, according to float type. Furthermore, an additional class is set to the float style: plain, plaintop, boxed, or ruled, so css may be used to format by float style as well. Default formatting by css is provided for ruled and boxed styles.

 **not seem to be a floating environment** Always declare a `\newfloat` before modifying it with `\floatname`, etc.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{float}[2001/11/08]

```

`\LWR@floatstyle` The default float style.

```

2 \newcommand*{\LWR@floatstyle}{plain}

```

`\newfloat``{\langle 1: type \rangle} {\langle 2: placement \rangle} {\langle 3: ext \rangle} [\langle 4: within \rangle]`

Emulates the `\newfloat` command from the `float` package.

“placement” is ignored.

```
3 \NewDocumentCommand{\newfloat}{m m m o}{%
4   \IfValueTF{#4}%
5     {\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}%
6     {\DeclareFloatingEnvironment[fileext=#3]{#1}}%
```

Remember the float style:

```
7   \csdef{LWR@floatstyle@#1}{\LWR@floatstyle}%
```

`newfloat` package automatically creates the `\listof` command for new floats, but `float` does not, so remove `\listof` here in case it is manually created later.

```
8   \cslet{listof#1s}\relax%
9   \cslet{listof#1es}\relax%
```

Like `size`, `newfloat` also creates `\l@<type>`, but `float` does not, so remove it here:

```
10  \cslet{l@#1}\relax%
11 }
```

`\floatname``{\langle type \rangle} {\langle name \rangle}`

Sets the text name of the float, such as “Figure”. Avoids trying to set a recursive name, from `trivfloat`.

```
12 \NewDocumentCommand{\floatname}{m +m}{%
13   \def\LWR@tempone{#2}%
14   \def\LWR@temptwo{\@nameuse{#1name}}%
15   \ifdefequal{\LWR@tempone}{\LWR@temptwo}{%}{%
16     \SetupFloatingEnvironment{#1}{name=#2}%
17   }%
18 }
```

`\floatplacement``{\langle type \rangle} {\langle placement \rangle}`

Float placement is ignored.

```
19 \newcommand*{\floatplacement}[2]{%
20   \SetupFloatingEnvironment{#1}{placement=#2}%
21 }
```

`\floatstyle``{\langle style \rangle}`

Remember the style for future floats:

```
22 \newcommand{\floatstyle}[1]{%
23   \def\LWR@floatstyle{#1}%
24 }
```

`\restylefloat``* {\langle type \rangle}`

Remember the style for this float:

```
25 \NewDocumentCommand{\restylefloat}{s m}{%
26   \csdef{LWR@floatstyle@#2}{\LWR@floatstyle}%
27 }
```

`\listof` See section 78.2 for the `\LWR@listof` command in the `lwarp` core.

```
28 \newcommand{\listof}{\LWR@listof}
```

File 168 **lwarp-floatflt.sty**

§ 277 Package **floatflt**

(Emulates or patches code by MATS DAHLGREN.)

Pkg floatflt **floatflt** is emulated.

for HTML output: Discard all options for `lwarp-floatflt`:

```
1 \LWR@ProvidesPackageDrop{floatflt}[1997/07/16]
```

Env [`<>`] **offset** [`<type>`] [`<width>`] Borrowed from the `lwarp` version of `keyfloat`:

```
2 \NewDocumentEnvironment{KFLTfloatflt@marginfloat}{0{-1.2ex} m m}
3 {%
4   \begin{LWR@setvirtualpage}*%
5   \ifblank{#3}{%
6     \LWR@BlockClassWP{%
7       float:right; %
8       width: 1.5in; % reasonable dummy width for word processor
9       margin:10pt%
10    }{%
11    (note)%
12    {marginblock}%
13   }{%
14     \setlength{\LWR@templengthone}{#3}%
15     \LWR@BlockClassWP{%
16       float:right; %
17       width:\LWR@printlength{\LWR@templengthone}; % extra space
18       margin:10pt%
19     }{%
20     width:\LWR@printlength{\LWR@templengthone}%
21     }%
22     (note)%
23     {marginblock}%
24   }%
25   \renewcommand*\@capttype{#2}%
26 }
27 {%
28   \endLWR@BlockClassWP%
29   \end{LWR@setvirtualpage}%
30 }
```

Env floatingfigure [`<placement>`] [`<width>`]

```
31 \DeclareDocumentEnvironment{floatingfigure}{o m}
32 {\begin{KFLTfloatflt@marginfloat}{figure}{#2}}
33 {\end{KFLTfloatflt@marginfloat}}
```

Env floatingtable [`<placement>`]

```
34 \DeclareDocumentEnvironment{floatingtable}{o}
```

```

35 {\begin{KFLTfloatflt@marginfloat}{table}{}}
36 {\end{KFLTfloatflt@marginfloat}}

```

File 169 **lwarp-floatpag.sty**

§ 278 Package **floatpag**

(Emulates or patches code by VYTAS STATULEVIČIUS AND SIGITAS TOLUŠIS.)

Pkg floatpag

floatpag is ignored.

for HTML output: Discard all options for lwarp-floatpag:

```

1 \LWR@ProvidesPackageDrop{floatpag}[2012/05/29]

2 \newcommand*\floatpagestyle[1]{}
3 \newcommand*\rotfloatpagestyle[1]{}
4 \newcommand*\thisfloatpagestyle[1]{}

```

File 170 **lwarp-floatrow.sty**

§ 279 Package **floatrow**

(Emulates or patches code by OLGA LAPKO.)

Pkg floatrow

floatrow is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{floatrow}[2008/08/02]

⚠ **Misplaced alignment tab character &** Use \StartDefiningTabulars and \StopDefiningTabulars before and after defining macros using \ttabbox with a tabular inside. See section 8.10.1.

⚠ **subfig package** When combined with the subfig package, while inside a subfloatrow \ffigbox and \ttabbox must have the caption in the first of the two of the mandatory arguments.

⚠ **\FBwidth, \FBheight** The emulation of floatrow does not support \FBwidth or \FBheight. These values are pre-set to .3\linewidth and 2in. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use warpprint and warpHTML environments to select appropriate values for each case.
- Inside a warpHTML environment, manually change \FBwidth or \FBheight before the \ffigbox or \ttabbox. Use \FBwidth or \FBheight normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether subcaption was loaded. If not, it is assumed that subfig is used instead:

```

2 \newbool{LWR@subcaptionloaded}
3
4 \AtBeginDocument{
5 \IfPackageLoadedTF{subcaption}
6   {\booltrue{LWR@subcaptionloaded}}
7   {\boolfalse{LWR@subcaptionloaded}}
8 }

```

\floatbox

`[{<1 preamble>}]{<2 captype>}[<3 width>][<4 height>][<5 vert pos>]{<6 caption>}{<7 object>}`

Only parameters for captype, width, caption, and object are used.

LWR@insubfloatrow is true if inside a subfloatrow environment.

There are two actions, depending on the use of subcaption or subfig.

```

9 \NewDocumentCommand{\floatbox}{o m o o +m +m}{%
10 \ifbool{LWR@subcaptionloaded}%
11 {% subcaption

```

For subcaption:

```

12   \ifbool{LWR@insubfloatrow}%
13   {% subcaption in a subfloatrow

```

subfigure and subtable environments take width as an argument.

```

14       \IfValueTF{#3}%
15       {\@nameuse{sub#2}{#3}}%
16       {\@nameuse{sub#2}{\linewidth}}%
17   }% subcaption in a subfloatrow
18   {% subcaption not in subfloatrow

```

figure and table environments do not take a width argument.

```

19       \@nameuse{#2}%
20   }% subcaption not in subfloatrow
21   #6
22
23   #7

```

End the environments:

```

24   \ifbool{LWR@insubfloatrow}%
25   {\@nameuse{endsub#2}}%
26   {\@nameuse{end#2}}%
27 }% subcaption
28 {% assume subfig

```

For subfig:

```

29 \ifbool{LWR@insubfloatrow}%
30 {% subfig in a subfloatrow

```

\subfloat is a macro, not an environment.

Package subfig's \subfloat command takes an optional argument which is the caption, but \floatbox argument #6 contains commands to create the caption and label, not the caption itself. Thus, \caption is temporarily disabled to return its own argument without braces.

```

31   \begingroup
32   \let\caption\@firstofone
33   \subfloat[#6]{#7}
34   \endgroup
35 }% subfig in a subfloatrow

```

36 {% subfig package, but not a subfig

figure and table are environments:

```
37 \@nameuse{#2}
38 #6
39
40 #7
41 \@nameuse{end#2}
42 }% subfig package, but not a subfig
43 }% assume subfig
44 }
```

Not used:

```
45 \newcommand*\nocapbeside{}
46 \newcommand*\capbeside{}
47 \newcommand*\captop{}
48 \newlength{\FBwidth}
49 \setlength{\FBwidth}{.3\linewidth}
50 \newlength{\FBheight}
51 \setlength{\FBheight}{2in}
52 \newcommand*\useFCwidth{}
53 \newcommand{\floatsetup}[2][{}]{
54 \newcommand{\thisfloatsetup}[1]{
55 \newcommand{\clearfloatsetup}[1]{
56 \newcommand*\killfloatstyle{}
```

`\newfloatcommand` $\langle 1 \text{ command} \rangle \langle 2 \text{ capttype} \rangle [\langle 3 \text{ preamble} \rangle] [\langle 4 \text{ default width} \rangle]$

Preamble and default width are ignored.

```
57 \NewDocumentCommand{\newfloatcommand}{m m o o}{%
58 \@namedef{#1}{
59 \floatbox{#2}
60 }
61 }
```

`\renewfloatcommand` $\langle 1 \text{ command} \rangle \langle 2 \text{ capttype} \rangle [\langle 3 \text{ preamble} \rangle] [\langle 4 \text{ default width} \rangle]$

Preamble and default width are ignored.

```
62 \NewDocumentCommand{\renewfloatcommand}{m m o o}{%
63 \@namedef{#1}{%
64 \floatbox{#2}
65 }
66 }
```

`\ffigbox` $[\langle width \rangle] [\langle height \rangle] [\langle vposn \rangle] \langle caption \text{ commands} \rangle \langle contents \rangle$

```
67 \newfloatcommand{ffigbox}{figure}[\nocapbeside][
```

`\ttabbox` $[\langle width \rangle] [\langle height \rangle] [\langle vposn \rangle] \langle caption \text{ commands} \rangle \langle contents \rangle$

```
68 \newfloatcommand{ttabbox}{table}[\captop][\FBwidth]
```

`\fcapside` $[\langle width \rangle] [\langle height \rangle] [\langle vposn \rangle] \langle caption \text{ commands} \rangle \langle contents \rangle$

```
69 \newfloatcommand{fcapside}{figure}[\capbeside][
```

Env floatrow

[*<numfloats>*]

The row of floats is placed into a `<div>` of class `floatrow`.

```

70 \newenvironment*{floatrow}[1][2]
71 {%
72   \begin{LWR@setvirtualpage}*%
73   \BlockClass{floatrow}%
74 }
75 {
76   \endBlockClass%
77   \end{LWR@setvirtualpage}%
78 }

```

Keys for `\DeclareNewFloatType`:

```

79 \newcommand*{\LWR@frowkeyplacement}{}
80 \newcommand*{\LWR@frowkeyname}{}
81 \newcommand*{\LWR@frowkeyfileext}{}
82 \newcommand*{\LWR@frowkeywithin}{}
83 \newcommand*{\LWR@frowkeycapstyle}{}
84
85 \define@key{frowkeys}{placement}{}%
86 \define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}%
87 \define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}%
88 \define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}%
89 \define@key{frowkeys}{relatedcapstyle}{}%

```

`\DeclareNewFloatType`*{<type>}* *{<options>}*

Use `\listof{type}{Title}` to print a list of the floats.

```
90 \newcommand*{\DeclareNewFloatType}[2]{%
```

Reset key values:

```

91 \renewcommand*{\LWR@frowkeyplacement}{}%
92 \renewcommand*{\LWR@frowkeyname}{}%
93 \renewcommand*{\LWR@frowkeyfileext}{}%
94 \renewcommand*{\LWR@frowkeywithin}{}%
95 \renewcommand*{\LWR@frowkeycapstyle}{}%

```

Read new key values:

```

96 \LWR@traceinfo{about to setkeys frowkeys}%
97 \setkeys{frowkeys}{#2}%
98 \LWR@traceinfo{finished setkeys frowkeys}%

```

Create a new float with optional `[within]`:

```

99 \ifthenelse{\equal{\LWR@frowkeywithin}{} }%
100 {%
101   \DeclareFloatingEnvironment[
102     placement=\LWR@frowkeyplacement,
103     fileext=\LWR@frowkeyfileext
104   ]{#1}%
105 }%
106 {%
107   \DeclareFloatingEnvironment[
108     placement=\LWR@frowkeyplacement,
109     fileext=\LWR@frowkeyfileext,
110     within=\LWR@frowkeywithin
111   ]{#1}%
112 %   \LWR@traceinfo{finished newfloat #1}%

```

113 }%

Rename the float if a name was given:

```
114 \ifthenelse{\equal{\LWR@frowkeyname}{}}%
115   {}%
116   {%
117     \SetupFloatingEnvironment{#1}{name={\LWR@frowkeyname}}%
118   }%
119 }
```

Not used:

```
120 \newcommand{\buildFBBOX}[2]{}
121 \newcommand*\CenterFloatBoxes{}
122 \newcommand*\TopFloatBoxes{}
123 \newcommand*\BottomFloatBoxes{}
124 \newcommand*\PlainFloatBoxes{}
125
126 \newcommand{\capsubrowsettings}{}
127
128 \NewDocumentCommand{\RawFloats}{o o}{}

```

\RawCaption

{*text*}

To be used inside a minipage or parbox.

```
129 \newcommand{\RawCaption}[1]{#1}
```

\floatfoot

{*text*}

Places additional text inside a float, inside a css <div> of class floatfoot.

```
130 \NewDocumentCommand{\floatfoot}{s +m}{%
131   \begin{BlockClass}{floatfoot}
132   #2
133   \end{BlockClass}
134 }
```

Used to compute \linewidth.

```
135 \newbool{LWR@insubfloatrow}
136 \boolfalse{LWR@insubfloatrow}
```

Env subfloatrow

[*num_floats*]

```
137 \newenvironment*{subfloatrow}[1][2]
138 {
```

The row of floats is placed into a <div> of class floatrow:

```
139   \LWR@forcenewpage
140   \BlockClass{floatrow}
```

While inside the floatrow, LWR@insubfloatrow is set true, which tells \floatbox to use \subfigure or \subtable.

```
141   \begingroup%
142   \booltrue{LWR@insubfloatrow}%
143 }
144 {%
145   \endgroup%
```

```

146   \endBlockClass%
147   \boolfalse{LWR@insubfloatrow}%
148 }

```

File 171 **lwarp-fltrace.sty**

§ 280 Package **fltrace**

Pkg fltrace

fltrace is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fltrace}[2018/01/08]

```

2 \def\tracefloats{}
3 \def\tracefloatsoff{}
4 \def\tracefloatvals{}

```

File 172 **lwarp-flushend.sty**

§ 281 Package **flushend**

Pkg flushend

(Emulates or patches code by SIGITAS TOLUŠIS.)

flushend is ignored.

for HTML output: Discard all options for lwarp-flushend:

```

1 \LWR@ProvidesPackageDrop{flushend}[2021/10/04]

2 \newcommand*\flushend{}
3 \newcommand*\raggedend{}
4 \newcommand*\flushcolsend{}
5 \newcommand*\raggedcolsend{}
6 \newtoks\atColsBreak \atColsBreak={}
7 \newtoks\atColsEnd \atColsEnd={}
8 \newcommand*\showcolsendrule{}

```

File 173 **lwarp-fnbreak.sty**

§ 282 Package **fnbreak**

Pkg fnbreak

fnbreak is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fnbreak}[2012/01/01]

```

2 \newcommand*\fnbreakverbose{}
3 \newcommand*\fnbreaknonverbose{}
4 \newcommand*\fnbreaklabel{}
5 \newcommand*\fnbreaknoLabel{}

```

File 174 **lwarp-fncychap.sty**

§ 283 Package **fncychap**

(Emulates or patches code by ULF A. LINDGREN.)

Pkg fncychap

fncychap is ignored.

for HTML output: Discard all options for lwarp-fncychap:

```

1 \LWR@ProvidesPackageDrop{fncychap}[2007/07/30]

2 \def\mghrulefill#1{}
3 \def\ChNameLowerCase{}
4 \def\ChNameUpperCase{}
5 \def\ChNameAsIs{}
6 \def\ChTitleLowerCase{}
7 \def\ChTitleUpperCase{}
8 \def\ChTitleAsIs{}
9 \newcommand{\ChRuleWidth}[1]{}
10 \newcommand{\ChNameVar}[1]{}
11 \newcommand{\ChNumVar}[1]{}
12 \newcommand{\ChTitleVar}[1]{}
13 \newcommand{\TheAlphaChapter}{}
14 \newcommand{\DOCH}{}
15 \newcommand{\DOTI}[1]{}
16 \newcommand{\DOTIS}[1]{}
17 \newlength{\mylen}
18 \newlength{\myhi}
19 \newlength{\px}
20 \newlength{\py}
21 \newlength{\ppy}
22 \newlength{\pxx}
23 \newlength{\RW}
24 \newcommand{\FmN}[1]{#1}
25 \newcommand{\FmTi}[1]{#1}

```

File 175 **lwarp-fnlineno.sty**

§ 284 Package **fnlineno**

Pkg fnlineno

fnlineno is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fnlineno}[2011/01/07]

File 176 **lwarp-fnpara.sty**

§ 285 Package **fnpara**

Pkg fnpara

fnpara is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fnpara}

File 177 **lwarp-fnpos.sty**

§ 286 Package **fnpos**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg fnpos **fnpos** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fnpos}[1999/07/14]

```
2 \newcommand*\makeFNbottom{}
3 \newcommand*\makeFNmid{}
4 \newcommand*\makeFNbelow{}
5 \newcommand*\makeFNabove{}
```

File 178 **lwarp-fontawesome.sty**

§ 287 Package **fontawesome**

(Emulates or patches code by XAVIER DANAUX.)

Pkg fontawesome **fontawesome** is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

 **poppler syntax warning** If using PDF L^AT_EX, *poppler* may issue a syntax warning regarding parsing a ligature component. X_HL^AT_EX or LuaL^AT_EX may be used to avoid this warning.

In the following, the general strategy is to intercept `\symbol` and embed it inside a `lateximage`. These changes are done inside a local group.

For PDF L^AT_EX, the `alt` tag includes the icon (symbol) number. For X_HL^AT_EX and LuaL^AT_EX, the `alt` tag is generic.

for HTML output: 1 \LWR@ProvidesPackagePass{fontawesome}[2016/05/15]

```
2 \LetLtxMacro\LWR@orig@symbol\symbol
3
4 \ifxetexorluatex
5
6 \newfontfamily{\LWR@orig@FA}{FontAwesome}
7
8 \newcommand*\LWR@fontawesome@xelatex@symbol[1]{%
9   \LWR@findcurrenttextcolor%
10  \begin{lateximage}*[icon][fontawesomexetex#1SZ\LWR@font@size{}CL\LWR@tempcolor]%
11    \csuse{\LWR@font@size}%
12    \LWR@orig@FA%
13    \LWR@orig@symbol{#1}%
14    \end{lateximage}%
15 }
16
17 \RenewDocumentCommand{\FA}{*}{%
```

```

18   \LetLtxMacro\symbol\LWR@fontawesome@xelatex@symbol%
19 }
20
21 \else
22
23 \newcommand*\LWR@fontawesome@symbolX}[2]{%
24   \LWR@findcurrenttextcolor%
25   \begin{lateximage}*[icon #1][fontawesome#2#1SZ\LWR@font@size{ }CL\LWR@tempcolor]%
26   \csuse{\LWR@font@size}%
27   \fontencoding{U}\fontfamily{fontawesome#2}\selectfont%
28   \LWR@orig@symbol{#1}%
29   \end{lateximage}%
30 }
31
32 \newcommand*\LWR@fontawesome@symbolone}[1]{%
33   \LWR@fontawesome@symbolX{#1}{one}%
34 }
35
36 \newcommand*\LWR@fontawesome@symboltwo}[1]{%
37   \LWR@fontawesome@symbolX{#1}{two}%
38 }
39
40 \newcommand*\LWR@fontawesome@symbolthree}[1]{%
41   \LWR@fontawesome@symbolX{#1}{three}%
42 }
43
44 \renewrobustcmd\FAone{%
45   \LetLtxMacro\symbol\LWR@fontawesome@symbolone%
46 }
47
48 \renewrobustcmd\FAtwo{%
49   \LetLtxMacro\symbol\LWR@fontawesome@symboltwo%
50 }
51
52 \renewrobustcmd\FAthree{%
53   \LetLtxMacro\symbol\LWR@fontawesome@symbolthree%
54 }
55 \fi

```

File 179 **lwarp-fontawesome5.sty**

§ 288 Package **fontawesome5**

(Emulates or patches code by MARCEL KRÜGER.)

Pkg fontawesome5

fontawesome5 is patched for use by **lwarp**.

Hashed inline images are used, as there may not be Unicode support for all icons.

The `alt` tag has the name of the icon.

for HTML output:

```

1 \LWR@ProvidesPackagePass{fontawesome5}[2018/07/27]
2 \ExplSyntaxOn
3 \cs_set:Nn\fontawesome_use_icon:nn{
4   \LWR@findcurrenttextcolor
5   \cs_if_exist:cTF{c__fontawesome_slot_#2_tl}{

```

```

6 \begin{lateximage}*[#2][fontawesome5#1SZ\LWR@font@size{}CL\LWR@tempcolor]
7 \csuse{\LWR@font@size}
8 \exp_last_unbraced:Nv
9 \__fontawesome_icon_at:nnnn
10 {c__fontawesome_slot_#2_tl}
11 {#1}{#2}
12 \end{lateximage}
13 }{
14 \msg_error:nxxx{fontawesome5}{icon-not-found}{#2}{#1}
15 }
16 }
17 \ExplSyntaxOff

```

File 180 **lwarp-fontaxes.sty**

§ 289 Package **fontaxes**

(Emulates or patches code by ANDREAS BÜHMANN, MICHAEL UMMELS.)

Pkg fontaxes

fontaxes is emulated for HTML, and used as-is for print output.

Functionality for small caps is in the lwarp core. Swashes and figure styles are ignored for HTML.

for HTML output:

```

1 \LWR@ProvidesPackagePass{fontaxes}[2014/03/23]

2 \ifdef{\LWR@HTML@swshape}{}% duplicated by nfssect-cfr
3 \newcommand{\LWR@HTML@swshape}{}
4 \LWR@formatted{swshape}
5
6 \newrobustcmd{\LWR@HTML@textsw}[1]{#1}
7 \LWR@formatted{textsw}
8
9 \FilenameNullify{%
10 \LetLtxMacro\swshape\@empty%
11 \LetLtxMacro\textsw\firstofone%
12 }
13 }

```

File 181 **lwarp-fontenc.sty**

§ 290 Package **fontenc**

Pkg fontenc

If using PDF L^AT_EX, lwarp used to require fontenc be loaded before lwarp, but now lwarp itself loads \fontenc with T1 encoding, which lwarp requires. fontenc is now allowed to be loaded with another encoding after lwarp.

lwarp-fontenc is no longer necessary, but is still provided to overwrite older versions.

for HTML output:

```

1 \LWR@ProvidesPackagePass{fontenc}[2017/04/05]

```

File 182 **lwarp-footmisc.sty**

§ 291 Package **footmisc**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg footmisc

footmisc is emulated.

lwarp incidentally happens to emulate the stable option.

```
1 \LWR@ProvidesPackageDrop{footmisc}[2011/06/06]
```

Some nullified commands:

```
2 \newcommand{\footnotelayout}{}
3 \newcommand{\setfnsymbol}[1]{}
4 \NewDocumentCommand{\DefineFNsymbols}{s m o m}{}
5
6 \newdimen\footnotemargin
7 \footnotemargin1.8em\relax
8
9 \newcommand*\hangfootparskip{0.5\baselineskip}
10 \newcommand*\hangfootparindent{0em}%
11
12 \let\pagefootnoterule\footnoterule
13 \let\mpfootnoterule\footnoterule
14 \def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}
15
16 \providecommand*\multiplefootnotemark}{3sp}
17 \providecommand*\multfootsep}{,}
```

Using `cleveref`. `\labelcref` only prints the number of the object, not its type.

```
18 \providecommand*\footref}[1]{\labelcref{#1}}
```

The following work as-is:

```
19 \newcommand\mpfootnotemark{%
20   \@ifnextchar[%
21     \xmpfootnotemark%
22     {%
23       \stepcounter\@mpfn%
24       \protected@xdef\@thefnmark{\thempfn}%
25       \@footnotemark%
26     }%
27 }
28 \def\xmpfootnotemark[#1]{%
29   \begingroup%
30   \csname c@\@mpfn\endcsname #1\relax%
31   \unrestored@protected@xdef\@thefnmark{\thempfn}%
32   \endgroup%
33   \@footnotemark%
34 }
```

File 183 **lwarp-footnote.sty**

§ 292 Package **footnote**

(Emulates or patches code by MARK WOODING.)

Pkg footnote

footnote is used with minor patches.

for HTML output:

footnote patches `\@makefn`text in a strange way. It must be restored to the expected definition before loading footnote, then replaced again after.

```

1 \long\def\@makefn#1{\textsuperscript{\@thefnmark}~#1}
2
3 \LWR@ProvidesPackagePass{footnote}[1997/01/28]
4
5 \long\def\@makefn#1{\textsuperscript{\@thefnmark}~{#1}}

6 \def\spewnotes{%
7   \endgroup%
8   \if@savingnotes\else\ifvoid\fn@notes\else\beginngroup%
9     \let\@makefn\empty%
10    \let\@finalstrut\@gobble%
11    \let\rule\@gobbletwo%
12    \booltrue{LWR@spewingnotes}%          lwarp
13    \@footnotetext{\unvbox\fn@notes}%
14    \endgroup\fi\fi%
15 }
16 \let\endsavenotes\spewnotes
17
18
19 \def\fn@fntext#1{%
20   \ifx\ifmeasuring@\@undefined%
21     \expandafter\@secondoftwo\else\expandafter\@iden%
22     \fi%
23   {\ifmeasuring@\expandafter\@gobble\else\expandafter\@iden\fi}%
24   {%
25     \global\setbox\fn@notes\vbox{%
26       \unvbox\fn@notes%
27       \LWR@htmltagc{\LWR@tagregularparagraph}%          lwarp
28       \LWR@orignewline%                                lwarp
29       \fn@startnote%
30       \@makefn#1{%
31         \rule\z@\footnotesep%
32         \ignorespaces%
33         #1%
34         \@finalstrut\strutbox%
35       }%
36       \fn@endnote%
37     }%
38   }%
39 }

```

Removed print-version formatting:

```
40 \def\fn@startnote{%
```

```

41 % \@parboxrestore%
42 \protected@edef\@currentlabel{\csname p@\@mpfn@endcsname\@thefnmark}%
43 % \color@begingroup% *** conflicts with lwarp
44 }
45
46 % \let\fn@endnote\color@endgroup% *** conflicts with lwarp
47 \def\fn@endnote{%
48 \LWR@origtilde\LWR@orignewline%
49 \LWR@htmltagc{/\LWR@tagregularparagraph}\LWR@orignewline%
50 \LWR@origtilde\LWR@orignewline%
51 }

```

Removed print-version formatting:

```

52 \def\fn@startfntext{%
53 \setbox\z@\vbox\bgroup%
54 \LWR@htmltagc{\LWR@tagregularparagraph}% lwarp
55 \LWR@orignewline% lwarp
56 \fn@startnote%
57 \fn@prefntext% Req'd for numbering.
58 % \rule\z@\footnotesep%
59 \ignorespaces%
60 }
61

```

Removed print-version formatting, added closing paragraph tag:

```

62 \def\fn@endfntext{%
63 \fn@postfntext%
64 \LWR@origtilde\LWR@orignewline%
65 \LWR@htmltagc{/\LWR@tagregularparagraph}%
66 \LWR@orignewline%
67 \egroup%
68 \begingroup%
69 \let\@makefntext\@empty%
70 \let\@finalstrut\@gobble%
71
72 \letLtxMacro\rule\@gobbletwo%
73 \booltrue{LWR@spewingnotes}% lwarp
74 \endgroup%
75 }

```

These have been redefined, so re-\let them again:

```

76 \let\endfootnote\fn@endfntext
77 \let\endfootnotetext\endfootnote

```

File 184 **lwarp-footnotebackref.sty**

§ 293 Package **footnotebackref**

Pkg footnotebackref footnotebackref is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{footnotebackref}[2012/07/01]

File 185 **lwarp-footnotehyper.sty**

§ 294 Package **footnotehyper**

Pkg footnotehyper footnotehyper is a hyperref-safe version of footnote. For lwarp, footnotehyper is emulated.

for HTML output: Discard all options for lwarp-footnotehyper:

```
1 \RequirePackage{footnote}
2
3 \LWR@ProvidesPackageDrop{footnotehyper}[2018/01/23]
```

File 186 **lwarp-footnoterange.sty**

§ 295 Package **footnoterange**

(Emulates or patches code by H.-MARTIN MÜNCH.)

Pkg footnoterange footnoterange is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{footnoterange}[2012/02/17]

```
2 \csletcs{footnoterange}{footnoterange*}
3 \csletcs{endfootnoterange}{endfootnoterange*}
```

File 187 **lwarp-footnpag.sty**

§ 296 Package **footnpag**

Pkg footnpag footnpag is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{footnpag}

File 188 **lwarp-foreign.sty**

§ 297 Package **foreign**

(Emulates or patches code by PHILIP G. RATCLIFFE.)

Pkg foreign foreign is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{foreign}[2012/09/25]

```
2 \renewcommand\foreignabbrfont{\emph}
```

File 189 **lwarp-forest.sty**

§ 298 Package **forest**

(Emulates or patches code by SAŠO ŽIVANOVIĆ.)

Pkg forest

forest is patched for use by lwarp.

 **\Forest*** The starred version of the macro `\Forest*` is not supported. `lwarp` encases each `lateximage` in an environment, so the global results of the starred `\Forest*` are lost.

for HTML output:

```

1 \LWR@ProvidesPackagePass{forest}[2017/07/14]

2 \BeforeBeginEnvironment{forest}{%
3   \begin{lateximage}[-forest~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{forest}{\end{lateximage}}
7
8 \RenewDocumentCommand{\Forest}{s D(){} m}{%
9   \forest@config{#2}%
10  \IfBooleanTF{#1}{%
11    \PackageError{lwarp-forest}%
12      {\protect\Forest* is not supported}%
13      {Lwarp uses an environment for images,\MessageBreak
14        but \protect\Forest* cannot work in an environment.}%
15    \let\forest@next\forest@env%
16  }{\let\forest@next\forest@group@env}%
17  \begin{lateximage}[-forest~\PackageDiagramAltText]   lwarp
18  \forest@next{#3}%
19  \end{lateximage}%                                   lwarp
20 }
```

File 190 **lwarp-fouridx.sty**

§ 299 Package **fouridx**

(Emulates or patches code by STEFAN KARRMANN.)

Pkg fouridx

fouridx works as-is with `svg math`, and is emulated for `MATHJAX`.

for HTML output:

```

1 \LWR@ProvidesPackagePass{fouridx}[2013/11/21]

2 \begin{warpMathJax}
3 \CustomizeMathJax{%
4   \newcommand{\fourIdx}[5]{%
5     \vphantom{#5}^{\hphantom{#2}#1}_{\hphantom{#1}#2}{#5}^{\#3}_{\#4}%
6   }%
7 }
8 \end{warpMathJax}
```

File 191 **lwarp-fourier.sty**

§ 300 Package **fourier**

(Emulates or patches code by MICHEL BOVANI.)

Pkg fourier

fourier is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except `sloped` and `upright` are honored for Greek characters, but MATHJAX cannot yet honor these for Latin characters.

The dedicated macros for upright and italic Greek letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```

1 \LWR@ProvidesPackagePass{fourier}[2020/03/03]
2
3 \LWR@infoprocessingmathjax{fourier}

4 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
5
6 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
7
8 \begin{warpMathJax}
9
10 \IfPackageLoadedWithOptionsTF{fourier}{sloped}
11   {
12     \LWR@mathjax@addgreek@l@up{other}{}
13     \LWR@mathjax@addgreek@u@it*{other}{}
14   }% sloped
15   {% not sloped
16     \IfPackageLoadedWithOptionsTF{fourier}{upright}
17     {% upright option
18       \LWR@mathjax@addgreek@l@up{}{}
19       \LWR@mathjax@addgreek@u@up*{}{}
20       \LWR@mathjax@addgreek@l@it{other}{}
21       \LWR@mathjax@addgreek@u@it*{other}{}
22     }
23     {% neither sloped nor upright
24       \LWR@mathjax@addgreek@l@up{other}{}
25       \LWR@mathjax@addgreek@u@it*{other}{}
26     }
27   }
28
29 \CustomizeMathJax{\newcommand{\othergreek}[1]{#1}}
30 \CustomizeMathJax{\let\varvarrho\varrho}
31 \CustomizeMathJax{\let\varvarpi\varpi}
32 \CustomizeMathJax{\let\othervarvarpi\othervarpi}
33 \CustomizeMathJax{\let\othervarvarrho\othervarrho}
34 \CustomizeMathJax{\let\varpartialdiff\partial}

```

lwarp_mathjax.txt adds `\left/\right` support for delimiters.

```

35 \CustomizeMathJax{\let\llbracket\lBrack}

```

```

36 \CustomizeMathJax{\let\rrbracket\rBrack}
37 \CustomizeMathJax{\let\dblbrackleft\lBrack}
38 \CustomizeMathJax{\let\dblbrackright\rBrack}
39
40 \CustomizeMathJax{\let\VERT|}
41
42 \CustomizeMathJax{\newcommand{\parallelslant}{\mathrel{\unicode{x02AFD}}}}
43 \CustomizeMathJax{\newcommand{\thething}{\mathord{\unicode{x1F60E}}}}
44 \CustomizeMathJax{\newcommand{\nparallelslant}{%
45   \mathrel{\LWRoverlaysymbols{-}{\unicode{x02AFD}}}%
46 }}
47 \CustomizeMathJax{\newcommand{\xswordsup}{\mathord{\unicode{x2694}}}}
48 \CustomizeMathJax{\newcommand{\xswordsdown}{\mathord{\unicode{x2694}}}}% up
49 \CustomizeMathJax{\newcommand{\notowns}{\mathrel{\unicode{x220C}}}}
50
51 \CustomizeMathJax{\newcommand{\iintop}{\mathop{\unicode{x222C}}\limits}}
52 \CustomizeMathJax{\newcommand{\iiintop}{\mathop{\unicode{x222D}}\limits}}
53 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
54 \CustomizeMathJax{\let\oiintop\oiint}
55 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x2230}}\limits}}
56 \CustomizeMathJax{\let\oiintop\oiint}
57 \CustomizeMathJax{\newcommand{\slashint}{\mathop{\unicode{x2A0D}}\limits}}
58 \CustomizeMathJax{\let\slashintop\slashint}
59
60 \CustomizeMathJax{\let\overgroup\overparen}
61 \CustomizeMathJax{\let\wideparen\overparen}
62 \CustomizeMathJax{\let\widearc\overparen}
63 \CustomizeMathJax{\let\wide0arc\overrightarrow}
64 \CustomizeMathJax{\newcommand{\widering}[1]{\stackrel{\unicode{x2218}}{\overgroup{#1}}}}
65
66 \end{warpMathJax}

```

File 192 **lwarp-framed.sty**

§ 301 Package **framed**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg framed

framed is supported and patched by lwarp.

for HTML output: Accept all options for lwarp-framed:

```

1 \LWR@ProvidesPackagePass{framed}[2011/10/22]
2
3 \AtBeginDocument{\RequirePackage{xcolor}}% for \convertcolorspec

4 \renewenvironment{framed}
5 {%
6   \LWR@forcenewpage
7   \BlockClass{framed}%
8 }
9 {\endBlockClass}
10
11 \renewenvironment{oframed}
12 {%
13   \LWR@forcenewpage
14   \BlockClass{framed}%
15 }

```

```

16 {\endBlockClass}
17
18
19 \renewenvironment{shaded}
20 {%
21   \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
22   \LWR@forcenewpage
23   \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
24 }
25 {\endBlockClass}
26
27 \renewenvironment{shaded*}
28 {%
29   \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
30   \LWR@forcenewpage
31   \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
32 }
33 {\endBlockClass}
34
35
36 \renewenvironment{leftbar}{%
37   \LWR@forcenewpage
38   \BlockClass{framedleftbar}
39   \def\FrameCommand{%
40     \MakeFramed {}
41 }%
42 {\endMakeFramed\endBlockClass}
43
44
45 \renewenvironment{snugshade}
46 {%
47   \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
48   \LWR@forcenewpage
49   \BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
50 }
51 {\endBlockClass}
52
53 \renewenvironment{snugshade*}
54 {%
55   \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
56   \LWR@forcenewpage
57   \BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
58 }
59 {\endBlockClass}
60
61 \let\oframed\framed
62 \let\endoframed\endframed
63
64
65 \RenewEnviron{titled-frame}[1]{%
66   \CustomFBox{#1}{0pt}{0pt}{0pt}{0pt}{\BODY}
67 }

\CustomFBox

    {\langle toptitle \rangle} {\langle bottitle \rangle} {\langle thicknessstop \rangle} {\langle bottom \rangle} {\langle left \rangle} {\langle right \rangle} {\langle text
contents \rangle}

68 \renewcommand{\CustomFBox}[7]{%
69   \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
70   \LWR@forcenewpage

```

```

71 \begin{BlockClass}[border: 3px solid \LWR@origpound\LWR@tempcolor]{framed}%
72 \ifthenelse{\isempty{#1}}{\}% not empty
73 \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
74 \textcolor{TFTitleColor}{\textbf{#1}}%
75 \end{BlockClass}%
76 }% not empty
77
78 #7
79
80 \ifthenelse{\isempty{#2}}{\}% not empty
81 \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
82 \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
83 \textcolor{TFTitleColor}{\textbf{#2}}%
84 \end{BlockClass}%
85 }% not empty
86 \end{BlockClass}%
87 }

```

`\TitleBarFrame``{<marker>} {<title>} {<contents>}`

```

88 \renewcommand\TitleBarFrame[3][\%
89 \CustomFBox%
90 {#2}]{%
91 \fboxrule\fboxrule\fboxrule%
92 {#3}%
93 }

94 \renewcommand{\TF@Title}[1]{#1}

```

`Env MakeFramed``{<settings>}`

```

95 \let\MakeFramed\relax
96 \let\endMakeFramed\relax
97
98 \NewEnviron{MakeFramed}[1]{%
99 \FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
100 }

```

`\fb@put@frame``{<frame cmd no split>} {<frame cmd split>}`

```

101 \renewcommand*\fb@put@frame[2]{%
102 \relax%
103 \@tempboxa%
104 }

```

File 193 **lwarp-froufrou.sty**§ 302 Package **froufrou***(Emulates or patches code by NELSON LAGO.)*

Pkg froufrou

froufrou is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{froufrou}[2020/12/22]

2 \ExplSyntaxOn

```

3 \xpretocmd{\setfroufrou}
4   {\edef\LWR@latestfroufrou{\detokenize{#1}}}
5   {}
6   {\LWR@patcherror{froufrou}{setfroufrou}}
7 \ExplSyntaxOff
8
9 \RenewDocumentCommand{\froufrou}{s O{}}{%
10  \nopagebreak[4]\par
11
12  \IfBooleanTF{#1}{\@afterindenttrue}{\@afterindentfalse}
13
14  \nopagebreak[4]\@froufrouspacebefore\nopagebreak[4]
15
16  \bgroup
17   \setfroufrou{#2}%
18   \normalsize
19   \ifdefvoid{\setstretch}{\setstretch{\setspace@inglespace}}% normally 1
20   \setlength{\parskip}{0pt}
21   \noindent\centering\bgroup%
22     \begin{center}%                               lwarp
23     \begin{lateximage}*[froufrou][\LWR@latestfroufrou]%   lwarp
24     \@froufrouOrnament%
25     \end{lateximage}%                               lwarp
26     \end{center}%                                   lwarp
27   \egroup\par
28 \egroup
29
30 \nopagebreak[4]\@froufrouspaceafter\nopagebreak[4]
31
32 \@froufrouFixSpacingAfter
33
34 \nopagebreak[3]
35
36 \@afterheading
37 }

```

File 194 **lwarp-ftcap.sty**

§ 303 Package **ftcap**

Pkg ftcap ftcap is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{ftcap}

File 195 **lwarp-ftnright.sty**

§ 304 Package **ftnright**

Pkg ftnright ftnright is ignored.

for HTML output: Discard all options for lwarp-ftnright:

1 \LWR@ProvidesPackageDrop{ftnright}[2014/10/28]

File 196 **lwarp-fullminipage.sty**

§ 305 Package **fullminipage**

Pkg fullminipage fullminipage is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fullminipage}[2014/07/06]
2 \newenvironment{fullminipage}[1][{}]{}

File 197 **lwarp-fullpage.sty**

§ 306 Package **fullpage**

Pkg fullpage fullpage is ignored.

for HTML output: Discard all options for lwarp-fullpage:
1 \LWR@ProvidesPackageDrop{fullpage}[1994/06/01]

File 198 **lwarp-fullwidth.sty**

§ 307 Package **fullwidth**

(Emulates or patches code by MARCO DANIEL.)

Pkg fullwidth fullwidth is emulated.

A minipage is used, of no HTML width.

for HTML output: 1 \LWR@ProvidesPackageDrop{fullwidth}[2011/11/18]
2 \newenvironment*{fullwidth}[1][{}]{%
3 \minipagefullwidth%
4 \minipage{\linewidth}%
5 }
6 {%
7 \endminipage%
8 }

File 199 **lwarp-fvextra.sty**

§ 308 Package **fvextra**

(Emulates or patches code by GEOFFREY M. POORE.)

Pkg fvextra fvextra is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{fvextra}[2019/02/04]

Ignored are `highlight`, `showtabs`, `obeytabs`, `tab`, `tabcolor`. Also ignored are all options regarding line breaking except `breaklines`, which is emulated as `true`.

`tabsize` is honored.

If line numbers on the right side are used along with `breaklines`, the line numbers will not be aligned.

```

2
3 \define@booleankey{FV}{obeytabs}%
4 %   {\let\FV@ObeyTabsInit\FV@@ObeyTabsInit}%
5   {\let\FV@ObeyTabsInit\relax}
6   {\let\FV@ObeyTabsInit\relax}
7
8 \define@key{FV}{tabcolor}%
9 {}
10
11 \define@key{FV}{tab}{}
12
13 \define@booleankey{FV}{showtabs}%
14 %   {\def\FV@TabChar{\FV@TabColor{\FancyVerbTab}}}%
15   {\let\FV@TabChar\relax}
16   {\let\FV@TabChar\relax}
17
18 \newbool{LWR@FV@breaklines}
19
20 \define@booleankey{FV}{breaklines}%
21   {\FV@BreakLinesfalse}
22   \booltrue{LWR@FV@breaklines}
23   \let\FV@ListProcessLine\FV@ListProcessLine@NoBreak}
24   {\FV@BreakLinesfalse}
25   \boolfalse{LWR@FV@breaklines}
26   \let\FV@ListProcessLine\FV@ListProcessLine@NoBreak}
27 % \fvset{breaklines}
28
29 \define@key{FV}{breakanywheresymbolpre}{\def\FancyVerbBreakAnywhereSymbolPre{}}
30 \fvset{breakanywheresymbolpre={}}
31
32 \define@key{FV}{breakanywheresymbolpost}{\def\FancyVerbBreakAnywhereSymbolPost{}}
33 \fvset{breakanywheresymbolpost={}}
34
35 \define@key{FV}{breakbeforesymbolpre}{\def\FancyVerbBreakBeforeSymbolPre{}}
36 \fvset{breakbeforesymbolpre={}}
37
38 \define@key{FV}{breakbeforesymbolpost}{\def\FancyVerbBreakBeforeSymbolPost{}}
39 \fvset{breakbeforesymbolpost={}}
40
41 \define@key{FV}{breakaftersymbolpre}{\def\FancyVerbBreakAfterSymbolPre{}}
42 \fvset{breakaftersymbolpre={}}
43
44 \define@key{FV}{breakaftersymbolpost}{\def\FancyVerbBreakAfterSymbolPost{}}
45 \fvset{breakaftersymbolpost={}}
46
47 \define@key{FV}{breaksymbolleft}{\def\FancyVerbBreakSymbolLeft{}}
48
49 \define@key{FV}{breaksymbol}{\fvset{breaksymbolleft={}}}
50
51 \fvset{breaksymbolleft={}}
52
53 \define@key{FV}{breaksymbolright}{\def\FancyVerbBreakSymbolRight{}}

```

```

54 \fvset{breaksymbolright={}}
55
56 \def\FV@ListProcessLine@NoBreak#1{%
57 %   \hbox to \hsize{%
58 %     \kern\leftmargin
59 %     \hbox to \linewidth{%
60 %       \FV@LeftListNumber%
61 %       \FV@LeftListFrame%
62 %       \FancyVerbFormatLine{%
63 %         \FancyVerbHighLightLine{%
64 %           \FV@ObeyTabs{\FancyVerbFormatText{#1}}}}}%\hss
65 %       \FV@RightListFrame%
66 %       \FV@RightListNumber%
67 %     }%
68 %   \hss}%
69 \null\par%           lwarp
70 }
71
72
73 \newcommand*\LWR@FV@linethensep}{%
74   \ifbool{LWR@FV@breaklines}%
75     {\theFancyVerbLine\kern\FV@NumberSep}%
76     {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}%
77 }
78
79 \newcommand*\LWR@FV@sephenline}{%
80   \ifbool{LWR@FV@breaklines}%
81     {\kern\FV@NumberSep\theFancyVerbLine}%
82     {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}%
83 }
84
85 \xpatchcmd{\FV@Numbers@left}
86   {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
87   {\LWR@FV@linethensep}
88   {}
89   {\LWR@patcherror{fvextra}{FV@Numbers@left A}}
90
91 \xpatchcmd{\FV@Numbers@left}
92   {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
93   {\LWR@FV@linethensep}
94   {}
95   {\LWR@patcherror{fvextra}{FV@Numbers@left B}}
96
97 \xpatchcmd{\FV@Numbers@left}
98   {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
99   {\LWR@FV@linethensep}
100  {}
101  {\LWR@patcherror{fvextra}{FV@Numbers@left C}}
102
103 \xpatchcmd{\FV@Numbers@right}
104   {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
105   {\LWR@FV@sephenline}
106   {}
107   {\LWR@patcherror{fvextra}{FV@Numbers@right A}}
108
109 \xpatchcmd{\FV@Numbers@right}
110   {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
111   {\LWR@FV@sephenline}
112   {}
113   {\LWR@patcherror{fvextra}{FV@Numbers@right B}}

```

```

114
115 \xpatchcmd{\FV@Numbers@right}
116   {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
117   {\LWR@FV@Linethensep}
118   {}
119   {\LWR@patcherror{fvextra}{FV@Numbers@right C}}
120
121 \xpatchcmd{\FV@Numbers@both}
122   {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
123   {\LWR@FV@Linethensep}
124   {}
125   {\LWR@patcherror{fvextra}{FV@Numbers@both A}}
126
127 \xpatchcmd{\FV@Numbers@both}
128   {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
129   {\LWR@FV@Linethensep}
130   {}
131   {\LWR@patcherror{fvextra}{FV@Numbers@both B}}
132
133 \xpatchcmd{\FV@Numbers@both}
134   {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
135   {\LWR@FV@Linethensep}
136   {}
137   {\LWR@patcherror{fvextra}{FV@Numbers@both C}}
138
139 \xpatchcmd{\FV@Numbers@both}
140   {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
141   {\LWR@FV@septhenline}
142   {}
143   {\LWR@patcherror{fvextra}{FV@Numbers@both D}}
144
145 \xpatchcmd{\FV@Numbers@both}
146   {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
147   {\LWR@FV@septhenline}
148   {}
149   {\LWR@patcherror{fvextra}{FV@Numbers@both E}}
150
151 \xpatchcmd{\FV@Numbers@both}
152   {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
153   {\LWR@FV@linethensep}
154   {}
155   {\LWR@patcherror{fvextra}{FV@Numbers@both F}}

```

File 200 **lwarp-fwlw.sty**

§ 309 Package **fwlw**

Pkg fwlw

fwlw is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fwlw}

2 \newbox\FirstWordBox \global\setbox\FirstWordBox\hbox{}

3 \newbox\NextWordBox \global\setbox\NextWordBox\hbox{}

4 \newbox>LastWordBox \global\setbox>LastWordBox\hbox{}

5 \def\ps@fwlwhead{}

6 \def\ps@NextWordFoot{}

File 201 **lwarp-gensymb.sty**

§ 310 Package **gensymb**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg gensymb

gensymb works as-is for SVG math, and uses the MATHJAX package.

for HTML output: 1 \LWR@ProvidesPackagePass{gensymb}[2003/07/02]

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\require{gensymb}}
4 \end{warpMathJax}
```

File 202 **lwarp-gentombow.sty**

§ 311 Package **gentombow**

Pkg gentombow

gentombow is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{gentombow}[2018/05/17]

```
2 \newcommand{\settombowbanner}[1]{}
3 \newcommand{\settombowbannerfont}[1]{}
4 \newcommand{\settombowwidth}[1]{}
5 \newcommand{\settombowbleed}[1]{}
6 \newcommand{\settombowcolor}[1]{}

```

File 203 **lwarp-geometry.sty**

§ 312 Package **geometry**

(Emulates or patches code by HIDEO UMEKI.)

Pkg geometry

geometry is preloaded by lwarp, but must be nullified as seen by the user's source code.

for HTML output: Discard all options for lwarp-geometry:

```
1 \LWR@ProvidesPackageDropA{geometry}{2018/04/16}
```

If geometry is never loaded by the user, it will be loaded by lwarp \AtBeginDocument. If this is the case, the page layout should not be changed but the user macros should still be nullified.

```
2 \ifbool{LWR@allowanothergeometry}{%
```

Assign and set the selected geometry with reset prepended. \AtEndPreamble lwarp will save this, then set its own geometry.

```
3 \edef\LWR@tempone{reset,\@ptionlist{\@currname.\@currentt}}%
4 \expandafter\LWR@origgeometry\expandafter{\LWR@tempone}%
5 }{}% LWR@allowanothergeometry
```

The user-level commands are nullified:

```
6 \renewcommand*{\geometry}[1]{}
7 \renewcommand*{\newgeometry}[1]{}
8 \renewcommand*{\restoregeometry}{}
9 \renewcommand*{\savegeometry}[1]{}
10 \renewcommand*{\loadgeometry}[1]{}

```

File 204 **lwarp-ghsystem.sty**

§ 313 Package **ghsystem**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg ghsystem

ghsystem is patched for use by lwarp.

 **\ghspic images** Images must be provided in svg format, unless jpg is specified. It is recommended to create a local images directory, copy into it the relevant PDF ghsystem images, and then convert them with

```
Enter => lwarpmk pdftosvg images/*.pdf
```

for HTML output:

```
1 \LWR@ProvidesPackagePass{ghsystem}[2020/02/17]
2 \ExplSyntaxOn
3
4 \cs_set_protected:Npn \ghsystem_filler:n #1
5 { \emph { \textless #1 \textgreater } }
6
7 \cs_set_protected:Npn \ghsystem_pic:n #1
8 {
9   \__ghsystem_includegraphics:xn
10  {
11    scale = \fp_to_tl:N \__ghsystem_picture_scale_fp
12    width = 1.25cm
13    \exp_not:V \__ghsystem_picture_includegraphics_tl
14  }
15  { ghsystem_ #1 . \__ghsystem_picture_type_tl }
16 }
17
18 \ExplSyntaxOff
```

File 205 **lwarp-gindex.sty**

§ 314 Package **gindex**

(Emulates or patches code by JAVIER BEZOS.)

Pkg gindex

gindex is patched for use by **lwarp**.

See section [8.6.15](#).

for HTML output: 1 \LWR@ProvidesPackagePass{gindex}[2019/10/07]

Set the index page and range separators. These are set \AtBeginDocument to allow the user to change them. They are then protected so that the **lwarp** core looks for the tokens instead of their expanded contents, since the *.ind files will contain \indexpagesep and \indexrangesep instead of their literal contents. Finally, **lwarp** is told of the **gindex** macros.

```
2 \AtBeginDocument{
3   \robustify{\indexpagesep}
4   \robustify{\indexrangesep}
5   \renewcommand*\IndexPageSeparator{\indexpagesep}
6   \renewcommand*\IndexRangeSeparator{\indexrangesep}
7 }
```

\hyperindexref is added:

```
8 \def\addindexitem#1#2{%
9   \indexflushitem
10  \gix@getspecial#1\indexspecial\indexspecial\@@\indexitem{\hyperindexref{#2}}
11
12 \def\addindexsubitem#1#2{%
13   \stepcounter{indexsubitems}%
14  \gix@getspecial#1\indexspecial\indexspecial\@@\indexsubitem{\hyperindexref{#2}}
15
16 \def\addindexsubsubitem#1#2{%
17  \gix@getspecial#1\indexspecial\indexspecial\@@\indexsubsubitem{\hyperindexref{#2}}
```

Uses a <div> of class `indexheading`:

```
18 \renewcommand\indexheading[1]{%
19   \begin{BlockClass}{indexheading}
20   \MakeUppercase{#1}%
21   \end{BlockClass}
22 }
```

File 206 **lwarp-gloss.sty**

§ 315 Package **gloss**

(Emulates or patches code by JOSE LUIS DÍAZ, JAVIER BEZOS.)

Pkg gloss

gloss is patched for use by **lwarp**.

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

for HTML output: 1 \LWR@ProvidesPackagePass{gloss}[2002/07/26]

\BaseJobname is added to the label in case `xr` or `xr-hyper` are used.

```

2 \xpatchcmd{\gls@gloss@iii}
3   {\thepage}
4   {\theLWR@previousautopagelabel}
5   {}
6   {\LWR@patcherror{gloss}{gls@gloss@iii}}
7
8 \def\gls@page@i#1#2{%
9   \endgroup%
10  \global\@namedef{gls@p#1}{\nameref{\BaseJobname-autopage-#2}}}%

```

File 207 **lwarp-glossaries.sty**

§ 316 Package **glossaries**

(Emulates or patches code by NICOLA L.C. TALBOT.)

Pkg `glossaries` **processing glossaries** *lwarpmk* has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the `glossaries` package using that package's `makeglossaries` program.

Opt `GlossaryCmd`
 Default: `makeglossaries`

Opt [`lwarpmk`] `printglossary` The shell command to execute is set by the `lwarp` option `GlossaryCmd`, which defaults to **makeglossaries**. The print or HTML glossary filename is appended to this command.

Opt [`lwarpmk`] `htmlglossary`

⚠ **makeglossaries not found** In some situations it may be required to modify the default command, such as to add the `perl` command in front:

```

\usepackage[
  GlossaryCmd={perl makeglossaries},
] {lwarp}

```

xindy language To set the language to use for processing glossaries with *xindy*:

```

\usepackage[
  GlossaryCmd={makeglossaries -L english},
] {lwarp}

```

Other options for `makeglossaries` may be set as well.

placement and toc options The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```

\usepackage[xindy,toc,numberedsection=no]{glossaries}
...
\printglossaries

```

Unnumbered section, inline with the current HTML page:

```

\usepackage[xindy,toc]{glossaries}
...
\printglossaries

```

Unnumbered section, on its own HTML page:

```

\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries

```

△ **glossary style** The default `style=item` option for `glossaries` conflicts with `lwarp`, so the style is forced to `index` instead.

△ **number list** The page number list in the printed form would become `\namerrefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

for HTML output:

```

1 \PassOptionsToPackage{xindy}{glossaries}
2
3 \LWR@ProvidesPackagePass{glossaries}[2018/07/23]
4
5 \setupglossaries{nonumberlist}
6 \setglossarystyle{index}

```

Patched to fix TOC pointing to the previous page:

```

7 \renewcommand*{\@pglossarysection}[2]{%
8   \glsclearpage
9   \LWR@phantomsection
10  \ifdefempty\@glossarysecstar
11  {%
12   \csname\@glossarysec\endcsname{#2}%
13  }%
14  {%

```

In the original, the TOC entry was made before the section, thus linking to the `phantomsection` in the printed version, but for HTML, this caused the link to point to the page before the glossaries, which could be a different HTML file. Here, the TOC entry is made after the section is created:

```

15   \csname\@glossarysec\endcsname*{#2}%
16   \@gls@toc{#1}{\@glossarysec}% Moved after the previous line.
17 }%
18 \@glossaryseclabel
19 }

```

`lwarp`'s sectioning commands cannot handle robust macros when splitting HTML into named filenames. `glossaries` uses `\translate` in sectioning names, and `\translate` is robust and cannot be expanded. The following pre-expands the translations at this moment, making use of `\translatelet`.

```

20 \newcommand*{\LWR@comp@glossaryname}{\translate{Glossary}}
21
22 \ifdefstrequal{\glossaryname}{\LWR@comp@glossaryname}{
23   \translatelet\LWR@translatetemp{Glossary}
24   \edef\glossaryname{\LWR@translatetemp}
25 }{ }
26
27 \newcommand*{\LWR@comp@acronymname}{\translate{Acronym}}
28
29 \ifdefstrequal{\acronymname}{\LWR@comp@acronymname}{
30   \translatelet\LWR@translatetemp{Acronym}
31   \edef\acronymname{\LWR@translatetemp}
32 }{ }

```

```

33
34 \newcommand*\LWR@comp@glssymbolsgroupname{\translate{Symbols (glossaries)}}
35
36 \ifdefstrequal{\glssymbolsgroupname}{\LWR@comp@glssymbolsgroupname}{
37   \translatelet\LWR@translatetemp{Symbols (glossaries)}
38   \edef\glssymbolsgroupname{\LWR@translatetemp}
39 }{}
40
41 \newcommand*\LWR@comp@glnumbersgroupname{\translate{Numbers (glossaries)}}
42
43 \ifdefstrequal{\glnumbersgroupname}{\LWR@comp@glnumbersgroupname}{
44   \translatelet\LWR@translatetemp{Numbers (glossaries)}
45   \edef\glnumbersgroupname{\LWR@translatetemp}
46 }{}

```

File 208 **lwarp-gmeometric.sty**

§ 317 Package **gmeometric**

Pkg gmeometric gmeometric is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{gmeometric}[2008/11/22]
2 \RequirePackageWithOptions{geometry}

```

File 209 **lwarp-graphics.sty**

§ 318 Package **graphics**

(Emulates or patches code by D. P. CARLISLE.)

Pkg graphics graphics is emulated.

for HTML output:

```

1 \LWR@ProvidesPackagePass{graphics}[2020/08/30]

```

§ 318.1 **Graphics extensions**

`\DeclareGraphicsExtensions` `{\list}`

`\AtBeginDocument` allow SVG files instead of PDF:

```

2 \AtBeginDocument{
3 \DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}
4 \DeclareGraphicsRule{.svg}{svg}{.svg}{}
5 \DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
6 }

```

Inside a `lateximage`, allow PDF instead of SVG:

```

7 \ifpdf
8 \appto\LWR@restoreorigformatting%
9 \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
10 }
11 \else% \ifpdf
12   \ifXeTeX

```

```

13 \appto\LWR@restoreorigformatting{%
14 \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
15 }
16     \else
17 \appto\LWR@restoreorigformatting{%
18 \DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
19 }
20     \fi
21 \fi

```

§ 318.2 Length conversions and graphics options



whitespace

A scaled image in L^AT_EX by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

Used to store the user's selected dimensions and HTML class.

The class defaults to “inlineimage” unless changed by a `class=xyx` option.

```

22 \newlength{\LWR@igwidth}
23 \newlength{\LWR@igheight}
24 \newcommand*\LWR@igwidthstyle{}
25 \newcommand*\LWR@igheightstyle{}
26 \newcommand*\LWR@igorigin{}
27 \newcommand*\LWR@igangle{}
28 \newcommand*\LWR@igxscale{1}
29 \newcommand*\LWR@igyscale{1}
30
31 \newbool{\LWR@igkeepaspectratio}
32 \boolfalse{\LWR@igkeepaspectratio}
33
34 \newcommand*\LWR@igclass{inlineimage}

35 \newcommand*\LWR@igalt{\ImageAltText}

```

Set the actions of each of the key/value combinations for `\includegraphics`. Many are ignored.

If an optional width was given, set an HTML style:

```

36 \define@key{igraph}{width}{%
37 \setlength{\LWR@igwidth}{#1}%
38 \ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}%
39 {%

```

Default to use the converted fixed length given:

```

40 \renewcommand*\LWR@igwidthstyle{width:\LWR@printlength{\LWR@igwidth}}%

```

If ex or em dimensions were given, use those instead:

```

41 \IfEndWith{#1}{ex}%
42 {\renewcommand*\LWR@igwidthstyle{width:#1}}% yes ex
43 {}% not ex
44 \IfEndWith{#1}{em}%
45 {\renewcommand*\LWR@igwidthstyle{width:#1}}% yes em
46 {}% not em

```

```

47 \IfEndWith{#1}{\}%
48 {\renewcommand*\LWR@igwidthstyle}{width:#1}}% yes percent
49 {}% not percent
50 \IfEndWith{#1}{px}%
51 {\renewcommand*\LWR@igwidthstyle}{width:#1}}% yes px
52 {}% not px
53 }{}% end of length > 0pt
54 }

```

If an optional height was given, set an HTML style:

```

55 \define@key{igraph}{height}{%
56 \setlength{\LWR@igheight}{#1}%
57 \ifthenelse{\lengthtest{\LWR@igheight > 0pt}}%
58 {%

```

Default to use the converted fixed length given:

```

59 \renewcommand*\LWR@igheightstyle){%
60 height:\LWR@printlength{\LWR@igheight} % extra space
61 }%

```

If ex or em dimensions were given, use those instead:

```

62 \IfEndWith{#1}{ex}%
63 {\renewcommand*\LWR@igheightstyle}{height:#1}}% yes ex
64 {}% not ex
65 \IfEndWith{#1}{em}%
66 {\renewcommand*\LWR@igheightstyle}{height:#1}}% yes em
67 {}% not em
68 \IfEndWith{#1}{\}%
69 {\renewcommand*\LWR@igheightstyle}{height:#1}}% yes percent
70 {}% not percent
71 \IfEndWith{#1}{px}%
72 {\renewcommand*\LWR@igheightstyle}{height:#1}}% yes px
73 {}% not px
74 }{}% end of length > 0pt
75 }

```

Handle keepaspectratio key:

```

76 \define@key{igraph}{keepaspectratio}[false]{%
77 \booltrue{\LWR@igkeepaspectratio}%
78 }

```

Handle origin key:

```

79 \define@key{igraph}{origin}[c]{%
80 \renewcommand*\LWR@igorigin}{#1}%
81 }

```

Handle angle key:

```

82 \define@key{igraph}{angle}{\renewcommand*\LWR@igangle}{#1}}

```

Handle class key:

```

83 \define@key{igraph}{class}{\renewcommand*\LWR@igclass}{#1}}

```

Handle alt key:

```
84 \define@key{igraph}{alt}{\renewcommand*\LWR@igalt}{#1}}
```

It appears that **graphicx** does not have separate keys for `xscale` and `yscale`. `scale` adjusts both at the same time.

```
85 \define@key{igraph}{scale}{%
86   \ifthenelse{\equal{#1}{1}}{}{}% must expand #1
87   \PackageNote{lwarp}{%
88     It is recommended to use ‘‘[width=xx\protect\linewidth]’’\MessageBreak
89     instead of ‘‘[scale=yy]’’,%
90   }%
91 }%
92 \renewcommand*\LWR@igxscale}{#1}%
93 \renewcommand*\LWR@igyyscale}{#1}%
94 }
```

Numerous ignored keys:

```
95 \define@key{igraph}{bb}{}
96 \define@key{igraph}{bblx}{}
97 \define@key{igraph}{bbly}{}
98 \define@key{igraph}{bburx}{}
99 \define@key{igraph}{bbury}{}
100 \define@key{igraph}{natwidth}{}
101 \define@key{igraph}{natheight}{}
102 \define@key{igraph}{hiresbb}[true]{}
103 \define@key{igraph}{viewport}{}
104 \define@key{igraph}{trim}{}
105 \define@key{igraph}{totalheight}{}
106 \define@key{igraph}{clip}[true]{}
107 \define@key{igraph}{draft}[true]{}
108 \define@key{igraph}{type}{}
109 \define@key{igraph}{ext}{}
110 \define@key{igraph}{read}{}
111 \define@key{igraph}{command}{}

```

New in v1.1a:

```
112 \define@key{igraph}{quite}{}
113 \define@key{igraph}{page}{}
114 \define@key{igraph}{pagebox}{}
115 \define@key{igraph}{interpolate}[true]{}

```

New in v1.1b:

```
116 \define@key{igraph}{decodearray}{}

```

§ 318.3 Printing HTML styles

`\LWR@rotstyle`

`{\langle prefix \rangle}{\langle degrees \rangle}`

Prints the rotate style with the given prefix.

prefix is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:rotate` style.

```
117 \newcommand*\LWR@rotstyle[2]{%
118   \edef\LWR@tempone{#2}%
119   \setcounter{LWR@tempcountone}{-1*\real{\LWR@tempone}} % space
120   #1transform:rotate(\arabic{LWR@tempcountone}deg); % space
121 }
```

`\LWR@scalestyle`

`{\langle prefix \rangle}{\langle xscale \rangle}{\langle yscale \rangle}`

Prints the scale style with the given prefix.

prefix is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:scale` style.

```
122 \newcommand*\LWR@scalestyle[3]{%
123   #1transform:scale(#2,#3);
124 }
```

§ 318.4 `\includegraphics`

`\LWR@opacity`

For HTML, used only for `\includegraphics`.

`\LWR@opacity` may be set by the `transparent` package.

```
125 \def\LWR@opacity{1}
```

`\LWR@imagesizebox`

Used to determine the actual image size if needed.

```
126 \newsavebox{\LWR@imagesizebox}
```

`\LWR@HTML@Gin@setfile`

`{\langle w \rangle}{\langle h \rangle}{\langle filename \rangle}` Sets the parsed filename for HTML output.

```
127 \newcommand*\LWR@HTML@Gin@setfile[3]{%
128   \xdef\LWR@parsedfilename{#3}%
129 }
```

Key [Gin] class

css class for the image.

Define the new class `key` for the print-mode version of `\includegraphics`, which is enabled inside a `lateximage`.

```
130 \AtBeginDocument{
131   \define@key{Gin}{class}{}
132 }
```

`\LWR@replaceEPSVG`

Usually, references to EPS files become SVG files, but if the `epstopdf` package is being used, it automatically converts EPS to PDF, and the following must NOT be done.

```
133 \AtBeginDocument{
134   \IfPackageLoadedTF{epstopdf}
135   {
136     \newcommand*\LWR@replaceEPSVG{}
137   }{%
```

```

138 \newcommand*\LWR@replaceEPSSVG{%
139   \StrSubstitute{\LWR@tempone}{.eps}{.svg}[\LWR@tempone]%
140   \StrSubstitute{\LWR@tempone}{.EPS}{.SVG}[\LWR@tempone]%
141 }
142 }%
143 }

```

* [*2: options*] [*3: options*] [*4: filename*]

\LWR@ig@useactualimagesize

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```

144 \newcommand*\LWR@ig@useactualimagesize[4]{%
145   \begingroup%
146   \LWR@restoreorigformatting%
147   \ifpdf%
148   \appto\LWR@restoreorigformatting{%
149     \DeclareGraphicsExtensions{%
150       .pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
151     }%
152   }%
153   \else% \ifpdf
154     \ifXeTeX%
155     \appto\LWR@restoreorigformatting{%
156       \DeclareGraphicsExtensions{%
157         .pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
158       }%
159     }%
160     \else%
161     \appto\LWR@restoreorigformatting{%
162       \DeclareGraphicsExtensions{%
163         .eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
164       }%
165     }%
166     \fi%
167   \fi% \ifpdf

```

For a word processor, do not use rotation:

```

168   \ifbool{FormatWP}{\define@key{Gin}{angle}{}{}}{%
169   \IfBooleanTF{#1}%
170   {% starred
171     \IfValueTF{#3}%
172     {%
173       \global\setbox\LWR@imagesizebox{%
174         \LWR@originincludegraphics*[#2][#3]{#4}%
175       }%
176     }%
177     {%
178       \IfValueTF{#2}%
179       {%
180         \global\setbox\LWR@imagesizebox{%
181           \LWR@originincludegraphics*[#2]{#4}%
182         }%
183       }%
184       \global\setbox\LWR@imagesizebox{%
185         \LWR@originincludegraphics*{#4}%
186       }%
187     }%
188   }%
189   }% starred

```

```

190   {% not starred
191     \IfValueTF{#3}%
192     {%
193       \global\sbox{\LWR@imagesizebox}{%
194         \LWR@originincludegraphics[#2][#3]{#4}%
195       }%
196     }%
197     {%
198       \IfValueTF{#2}%
199       {%
200         \global\sbox{\LWR@imagesizebox}{%
201           \LWR@originincludegraphics[#2]{#4}%
202         }%
203       }{%
204         \global\sbox{\LWR@imagesizebox}{%
205           \LWR@originincludegraphics{#4}%
206         }%
207       }%
208     }%
209   }% not starred
210 \endgroup%
211 \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
212 \global\renewcommand*\LWR@igwidthstyle{%
213   width:\LWR@printlength{\LWR@igwidth}%
214 }%
215 \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
216 \global\renewcommand*\LWR@igheightstyle{%
217   height:\LWR@printlength{\LWR@igheight}%
218 }%
219 }

```

\LWR@ig@htmltag

For the HTML reference, add the graphicspath, filename, extension, alt tag, style, and class.

```

220 \newcommand*\LWR@ig@htmltag{%
221   img\LWR@indentHTML%
222   src=\textquotedbl%
223   \detokenize\expandafter{\LWR@parsedfilename}%
224   \textquotedbl\LWR@indentHTML%

```

Only include a style tag if a width, height, angle, or scale was given:

```

225   \ifthenelse{
226     \NOT\equal{\LWR@igwidthstyle}{ } \OR
227     \NOT\equal{\LWR@igheightstyle}{ } \OR
228     \NOT\equal{\LWR@igorigin}{ } \OR
229     \NOT\equal{\LWR@igangle}{ } \OR
230     \NOT\equal{\LWR@igxscale}{1} \OR
231     \NOT\equal{\LWR@igyscale}{1}
232   }%
233   {%
234     style=\textquotedbl\LWR@indentHTML
235     \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{ }}%
236       {\LWR@igwidthstyle;\LWR@indentHTML}{ }%
237     \ifthenelse{\NOT\equal{\LWR@igheightstyle}{ }}%
238       {\LWR@igheightstyle;\LWR@indentHTML}{ }%
239     \ifthenelse{\NOT\equal{\LWR@igorigin}{ }}%
240       {
241         transform-origin: \LWR@originnames{\LWR@igorigin};%

```

```

242         \LWR@indentHTML%
243     }{}%
244     \ifthenelse{\NOT\equal{\LWR@igangle}{}}%
245     {%
246         \LWR@rotstyle{-ms-}{\LWR@igangle}\LWR@indentHTML
247         \LWR@rotstyle{-webkit-}{\LWR@igangle}\LWR@indentHTML
248         \LWR@rotstyle{}{\LWR@igangle }\LWR@indentHTML
249     }{}%
250     \ifthenelse{%
251         \NOT\equal{\LWR@igxscale}{1}\OR%
252         \NOT\equal{\LWR@igyscale}{1}%
253     }%
254     {%
255         \LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale}%
256         \LWR@indentHTML
257         \LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale}%
258         \LWR@indentHTML
259         \LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}%
260         \LWR@indentHTML
261     }{}%
262     %
263     \ifthenelse{\NOT\equal{\LWR@opacity}{1}}%
264     {opacity:\LWR@opacity;\LWR@indentHTML}{}%
265     %
266     \textquotedbl\LWR@indentHTML%
267 }{}%

```

Set the class and alt tag:

```

268     class=\textquotedbl\LWR@igclass\textquotedbl\LWR@indentHTML%
269     alt=\textquotedbl\AltTextOpen\LWR@igalt\AltTextClose\textquotedbl\ \LWR@orignewline%
270 }% end of image tags

```

\LWR@includegraphicsb

* [*2: options*] [*3: options*] [*4: filename*]

graphics syntax is `\includegraphics * [llx, lly] [urx, ury] {filename}`

graphicx syntax is `\includegraphics [key values] {filename}`

If #3 is empty, only one optional argument was given, thus `graphicx` syntax.

If using `\epsfig` or `\psfig` from the `epsfig` package, #4 will be `\LWR@epsfig@filename`, which will have been set by the `file` or `figure` keys. Therefore, #4 must not be used until after the keys have been processed.

```

271 \NewDocumentCommand{\LWR@includegraphicsb}{s o m}
272 {%

```

Start the image tag on a new line, allow PDF output word wrap:

```

273     \LWR@origtilde \LWR@orignewline%

```

Temporarily compute `\linewidth`, `\textwidth`, `\textheight` arguments with a 6x9 inch size until the next `\endgroup`.

```

274     \begin{LWR@setvirtualpage}%

```

For correct em sizing during the width and height conversions:

```

275     \large%

```

Temporarily prevent underfull `\hbox` warnings.

```

276     \hbadness=10000\relax%

```

Reset some defaults, possibly will be changed below if options were given:

```

277 \setlength{\LWR@igwidth}{0pt}%
278 \setlength{\LWR@igheight}{0pt}%
279 \renewcommand*\LWR@igwidthstyle{}%
280 \renewcommand*\LWR@igheightstyle{}%
281 \renewcommand*\LWR@igorigin{}%
282 \renewcommand*\LWR@igangle{}%
283 \renewcommand*\LWR@igxscale{1}%
284 \renewcommand*\LWR@igyscale{1}%
285 \renewcommand*\LWR@igclass{inlineimage}%
286 \boolfalse\LWR@igkeepaspectratio%

287 \ifdefvoid{\LWR@ThisAltText}{%
288   \edef\LWR@igalt{\ImageAltText}%
289 }{%
290   \edef\LWR@igalt{\LWR@ThisAltText}%
291 }%

```

If #3 is empty, only one optional argument was given, thus `graphicx` syntax:

```

292 \IfValueF{#3}{%
293   \IfValueTF{#2}%
294     {\setkeys{igraph}{#2}}%
295     {\setkeys{igraph}{}}%
296 }%

```

Fully expand and detokenize the filename, changing the file extension to `.svg` if necessary.

Note that uppercase file extensions are detected and reported as lowercase, so `lwarp` can only report to the browser lowercase extensions, so all images must have lowercase file extensions.

```

297 \begingroup%
298 \LetLtxMacro\Gin@setfile\LWR@HTML@Gin@setfile%
299 \edef\LWR@tempone{#4}%

```

PDF extensions are removed to allow a search for another graphics format such as SVG or PNG.

```

300 \StrSubstitute{\LWR@tempone}{.pdf}{}[\LWR@tempone]%
301 \StrSubstitute{\LWR@tempone}{.PDF}{}[\LWR@tempone]%

302 \LWR@replaceEPSSVG%
303 \xdef\LWR@parsedfilename{\LWR@tempone}%
304 \Gin@include@graphics{\detokenize\expandafter{\LWR@parsedfilename}}%
305 \endgroup%
306 \filename@parse{\LWR@parsedfilename}%

```

Remove doubled `//` in the directory path, from the 2020/10/01 L^AT_EX kernel change.

```

307 \StrSubstitute{\LWR@parsedfilename}{//}{}[\LWR@parsedfilename]%
308 \LWR@traceinfo{\LWR@parsedfilename is \LWR@parsedfilename}%

```

If formatting for a word processor, or if using `keepaspectratio`, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```

309 \ifbool{expr{
310   bool {FormatWP} or
311   bool {\LWR@igkeepaspectratio}
312 }}{\LWR@ig@useactualimagesize{#1}{#2}{#3}{#4}}{}%

```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class:

```

313 \LWR@traceinfo{LWR@includegraphicsb: about to create href}%
314 \LWR@href{\LWR@parsedfilename}%
315 {% start of href
316     \LWR@traceinfo{LWR@includegraphicsb: about to LWR@htmltag}%
317     \LWR@htmltag{\LWR@ig@htmltag}%
318 }% end of href

```

Return to original page size and font size:

```

319 \end{LWR@setvirtualpage}%

```

Clear the single-use alt text:

```

320 \gdef\LWR@ThisAltText{}%
321 \LWR@traceinfo{LWR@includegraphicsb done}%
322 }

```

`\includegraphics` [*<key=val>*] {*<filename>*}

Handles width and height, converted to fixed width and heights.

The user should always use no file suffix in the document source.

```

323 \AtBeginDocument{
324
325 \LWR@traceinfo{Patching includegraphics.}
326
327 \let\ltxmacro\LWR@originincludegraphics\includegraphics

328 \renewrobustcmd*{\includegraphics}
329 {%

```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```

330 \LWR@traceinfo{includegraphics}%
331 \LWR@ensuredoingapar%
332 \LWR@includegraphicsb%
333 }% includegraphics
334 }% AtBeginDocument

```

§ 318.5 Boxes

`\LWR@rotboxorigin`

Holds the origin key letters.

```

335 \newcommand*\LWR@rotboxorigin{}

```

`\LWR@originname`

{*<letter>*}

Given one L^AT_EX origin key value, translate into an HTML origin word:

```

336 \newcommand*\LWR@originname[1]{%
337     \ifthenelse{\equal{#1}{t}}{top}{}%
338     \ifthenelse{\equal{#1}{b}}{bottom}{}%
339     \ifthenelse{\equal{#1}{c}}{center}{}%
340     \ifthenelse{\equal{#1}{l}}{left}{}%
341     \ifthenelse{\equal{#1}{r}}{right}{}%
342 }

```

`\LWR@originnames``{\langle letters \rangle}`

Given one- or two-letter L^AT_EX origin key values, translate into HTML origin words:

```
343 \newcommand*\LWR@originnames[1]{%
344 \StrChar{#1}{1}[\LWR@strresult]%
345 \LWR@originname{\LWR@strresult}
346 \StrChar{#1}{2}[\LWR@strresult]%
347 \LWR@originname{\LWR@strresult}
348 }
```

Handle the origin key for `\rotatebox`:

```
349 \define@key{krotbox}{origin}{%
350 \renewcommand*\LWR@rotboxorigin{#1}%
351 }
```

These keys are ignored:

```
352 \define@key{krotbox}{x}{}
353 \define@key{krotbox}{y}{}
354 \define@key{krotbox}{units}{}

```

`\rotatebox` [*keyval list*] [*angle*] [*text*]

```
355 \AtBeginDocument{
```

The HTML version:

```
356 \NewDocumentCommand{\LWR@HTML@rotatebox}{O{} m +m}{%
```

Reset the origin to “none-given”:

```
357 \renewcommand*\LWR@rotboxorigin{}
```

Process the optional keys, which may set `\LWR@rotateboxorigin`:

```
358 \setkeys{krotbox}{#1}%
```

Select inline-block so that HTML will transform this span:

```
359 \LWR@htmltagc{%
360   span\LWR@indentHTML
361   style=\textquotedbl\LWR@indentHTML
362   display: inline-block;\LWR@indentHTML
```

If an origin was given, translate and print the origin information:

```
363   \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{}}{%
364     {transform-origin: \LWR@originnames{\LWR@rotboxorigin};\LWR@indentHTML}%
365     {}}%
```

Print the rotation information:

```
366   \LWR@rotstyle{-ms-}{#2}\LWR@indentHTML
367   \LWR@rotstyle{-webkit-}{#2}\LWR@indentHTML
368   \LWR@rotstyle{}{#2}\textquotedbl\LWR@originewline%
369 }\LWR@originewline%
```

Print the text to be rotated:

```
370 \begin{LWR@nestspan}%
371 #3%
```

Close the span:

```
372 \LWR@htmltagc{/span}%
373 \end{LWR@nestspan}%
374 }
```

The high-level interface:

```
375 \LWR@formatted{rotatebox}
376
377 }% AtBeginDocument
```

`\scalebox` $\{\langle h\text{-scale}\rangle\} [\langle v\text{-scale}\rangle] \{\langle \text{text}\rangle\}$

```
378 \AtBeginDocument{
```

The HTML version:

```
379 \NewDocumentCommand{\LWR@HTML@scalebox}{m o m}{%
```

Select inline-block so that HTML will transform this span:

```
380 \LWR@htmltagc{%
381   span\LWR@indentHTML
382   style=\textquotedbl\LWR@indentHTML
383   display: inline-block;\LWR@indentHTML
```

Print the scaling information:

```
384   \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
385   \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
386   \LWR@scalestyle{}{#1}{\IfNoValueTF{#2}{#1}{#2}}
387   \textquotedbl\LWR@orignewline
388 }\LWR@orignewline%
```

Print the text to be scaled:

```
389 \begin{LWR@nestspan}%
390 #3%
```

Close the span:

```
391 \LWR@htmltagc{/span}%
392 \end{LWR@nestspan}%
393 }
```

The high-level interface:

```
394 \LWR@formatted{scalebox}
395
396 }% AtBeginDocument
```

`\reflectbox` $\{\langle text \rangle\}$

```
397 \AtBeginDocument{
398
399 \newcommand{\LWR@HTML@reflectbox}[1]{%
400   \scalebox{-1}[1]{#1}%
401 }% \reflectbox
402
403 \LWR@formatted{reflectbox}
404
405 }% AtBeginDocument
```

`\resizebox` $\{\langle h-length \rangle\} \{\langle v-length \rangle\} \{\langle text \rangle\}$

Simply prints its text argument.

```
406 \AtBeginDocument{
407
408 \NewDocumentCommand{\LWR@HTML@resizebox}{s m m m}{%
409   #4%
410 }
411
412 \LWR@formatted{resizebox}
413
414 }% AtBeginDocument
```

File 210 **lwarp-graphicx.sty**

§ 319 Package **graphicx**

Pkg graphicx

graphicx is emulated.

graphicx loads graphics, which also loads lwarp-graphics, which remembers the original graphics definitions for use inside a lateximage, and then patches them \AtBeginDocument for HTML output.

lwarp-graphics handles the syntax of either graphics or graphicx.

for HTML output: 1 \LWR@ProvidesPackagePass{graphicx}[2020/09/09]

File 211 **lwarp-grffile.sty**

§ 320 Package **grffile**

Pkg grffile

grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

lwarp-grffile now exists as a placeholder since grffile used to be emulated by lwarp, and thus older versions of lwarp-grffile may exist and should be overwritten by this newer version.

for HTML output: 1 \LWR@ProvidesPackagePass{grffile}[2017/06/30]



matching PDF and SVG

File 212 **lwarp-grid.sty**§ 321 Package **grid**

Pkg grid grid is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{grid}[2009/06/16]

2 \newenvironment*{gridenv}{}{}

File 213 **lwarp-grid-system.sty**§ 322 Package **grid-system***(Emulates or patches code by MARCUS BITZL.)*

Pkg grid-system grid-system is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{grid-system}[2014/02/16]

(\ifdef is in case the older syntax is removed.)

2 \AtBeginEnvironment{Row}{\setlength{\linewidth}{6in}}

3

4 \ifdef{\endrow}{

5 \AtBeginEnvironment{row}{\setlength{\linewidth}{6in}}

6 }{}

7

8 \renewcommand{\gridssystem@finishcell}{\hspace{\gridssystem@cellsep}}

File 214 **lwarp-gridset.sty**§ 323 Package **gridset**

Pkg gridset gridset is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{gridset}[2020-02-12]

2 \newcommand*{\gridbase}{}{}

3 \newcommand*{\gridinterval}{}{}

4 \newcommand*{\SavePos}[1]{}{}

5 \ifLuaTeX

6 \else

7 \let\savepos\SavePos

8 \fi

9 \newcommand*{\vskipnextgrid}{}{}

10 \newcommand*{\thegridinfo}[1]{(thegridinfo)}

11 \newcommand*{\theposinfo}[1]{(theposinfo)}

12 \newcommand*{\theypos}[1]{(theypos)}

File 215 **lwarp-hang.sty**

§ 324 Package **hang**

(Emulates or patches code by ANDREAS NOLDA.)

Pkg hang

hang is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{hang}[2017/02/18]
2 \newlength{\hangingindent}
3 \setlength{\hangingindent}{1em}
4 \newlength{\hangingleftmargin}
5 \setlength{\hangingleftmargin}{0em}
6
7 \newcommand*\LWR@findhangingleftmargin{%
8 \setlength{\LWR@templengthone}{\hangingleftmargin}%
9 \addtolength{\LWR@templengthone}{\hangingindent}%
10 }
11
12 \newenvironment{hangingpar}
13 {
14   \LWR@findhangingleftmargin%
15   \BlockClass[%
16     \LWR@print@embox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
17     \LWR@print@embox{text-indent:-\LWR@printlength{\hangingindent}}%
18   ]%
19   {hangingpar}%
20 }
21 {\endBlockClass}
22
23 \newenvironment{hanginglist}
24 {%
25   \renewcommand*\LWR@printcloselist{\LWR@printcloseitemize}%
26   \renewcommand*\LWR@printopenlist{%
27     \LWR@findhangingleftmargin%
28     ul style=\textquotedbl%
29     \LWR@print@embox{list-style-type:none;} % extra space
30     \LWR@print@embox{%
31       margin-left:\LWR@printlength{\LWR@templengthone}%
32     } ; % extra space
33     \LWR@print@embox{%
34       text-indent:-\LWR@printlength{\hangingindent}%
35     }%
36     \textquotedbl%
37   }%
38   \LetLtxMacro\item\LWR@itemizeitem%
39   \list{}{}%
40 }
41 {\endlist}
42
43 \newenvironment{compacthang}
44 {\hanginglist}
45 {\endhanginglist}
46
47 \newlength{\labeledleftmargin}

```

```

48 \setlength{\labeledleftmargin}{0em}
49
50 \newenvironment{labeledpar}[2]
51 {%
52   \BlockClass[%
53     \LWR@findhangingleftmargin%
54     \LWR@print@embox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
55     \LWR@print@embox{text-indent:-\LWR@printlength{\hangingindent}}%
56   ][labeledpar]#2%
57 }
58 {\endBlockClass}
59
60 \newenvironment{labeledlist}[1]
61 {\hanginglist}
62 {\endhanginglist}
63
64 \newenvironment{compactlabel}[1]
65 {\hanginglist}
66 {\endhanginglist}

```

File 216 **lwarp-hanging.sty**

§ 325 Package **hanging**

Pkg hanging

hanging is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{hanging}[2009/09/02]
```

```

2 \IfClassLoadedTF{memoir}{
3 \let\hangpara\relax
4 \let\hangparas\relax
5 \let\endhangparas\relax
6 \let\hangpunct\relax
7 \let\endhangpunct\relax
8 }{}

```

\hangpara

```
{\langle indent \rangle} {\langle afternum \rangle}
```

Use hangparas instead.

```
9 \newcommand*{\hangpara}[2]{}

```

Env hangparas

```
{\langle indent \rangle} {\langle afternum \rangle}
```

```

10 \newenvironment*{hangparas}[2]
11 {%
12   \BlockClass[%
13     \LWR@print@embox{margin-left:\LWR@printlength{#1}} ; %
14     \LWR@print@embox{text-indent:-\LWR@printlength{#1}}%
15   ]%
16   {hangingpar}%
17 }
18 {\endBlockClass}

```

Env hangpunct

```

19 \newenvironment*{hangpunct}
20 {\BlockClass{hangpunct}}
21 {\endBlockClass}

22 \newcommand{\nhpt}{.}
23 \newcommand{\nhlq}{‘}
24 \newcommand{\nhrq}{’}

```

File 217 **lwarp-hepunits.sty**

§ 326 Package **hepunits**

(Emulates or patches code by ANDY BUCKLEY.)

Pkg hepunits

hepunits is used as-is, and emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{hepunits}[2020/04/10]

2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{hepunits}
4
5 \ifx\@HEPopt@sicmids\@yes
6 \CustomizeMathJax{\newcommand{\micron}{\micro\metre}}
7 \CustomizeMathJax{\newcommand{\mrad}{\milli\radian}}
8 \fi
9
10 \CustomizeMathJax{\newcommand{\gauss}{\mathrm{G}}}
11
12 \CustomizeMathJax{\newcommand{\invcmsq}{\centi\metre\tothe{-2}}}
13 \CustomizeMathJax{\newcommand{\invcmsqpersecond}{\invcmsq\second\tothe{-1}}}
14 \CustomizeMathJax{\newcommand{\invcmsqpersec}{\invcmsqpersecond}}
15
16 %% (Inverse) cross-sections
17 \CustomizeMathJax{\newcommand{\invbarn}{\barn\tothe{-1}}}
18
19 \ifx\@HEPopt@noprefixcmds\@empty
20 \CustomizeMathJax{\newcommand{\millibarn}{\milli\barn}}
21 \CustomizeMathJax{\newcommand{\microbarn}{\micro\barn}}
22 \CustomizeMathJax{\newcommand{\nanobarn}{\nano\barn}}
23 \CustomizeMathJax{\newcommand{\picobarn}{\pico\barn}}
24 \CustomizeMathJax{\newcommand{\femtobarn}{\femto\barn}}
25 \CustomizeMathJax{\newcommand{\attobarn}{\atto\barn}}
26 \CustomizeMathJax{\newcommand{\zeptobarn}{\zepto\barn}}
27 \CustomizeMathJax{\newcommand{\yoctobarn}{\yocto\barn}}
28 \CustomizeMathJax{\newcommand{\invnanobarn}{\nano\invbarn}}
29 \CustomizeMathJax{\newcommand{\invpicobarn}{\pico\invbarn}}
30 \CustomizeMathJax{\newcommand{\invfemtobarn}{\femto\invbarn}}
31 \CustomizeMathJax{\newcommand{\invattobarn}{\atto\invbarn}}
32 \CustomizeMathJax{\newcommand{\invzeptobarn}{\zepto\invbarn}}
33 \CustomizeMathJax{\newcommand{\invyoctobarn}{\yocto\invbarn}}
34 \CustomizeMathJax{\newcommand{\invnb}{\invnanobarn}}
35 \CustomizeMathJax{\newcommand{\invpb}{\invpicobarn}}
36 \CustomizeMathJax{\newcommand{\invfb}{\invfemtobarn}}
37 \CustomizeMathJax{\newcommand{\invab}{\invattobarn}}
38 \CustomizeMathJax{\newcommand{\invzb}{\invzeptobarn}}
39 \CustomizeMathJax{\newcommand{\invyb}{\invyoctobarn}}
40 \fi

```

```

41
42 \CustomizeMathJax{\newcommand{\electronvolt}{\electronvolt\per\mathit{c}}}
43 \CustomizeMathJax{\newcommand{\electronvoltsq}{\electronvolt\per\mathit{c}\squared}}
44 \CustomizeMathJax{\let\TeV\electronvolt}
45 \CustomizeMathJax{\let\TeVsq\electronvoltsq}
46
47 \ifx\@HEPopt@noprefixcmds\@empty
48 \CustomizeMathJax{\newcommand{\meV}{\milli\TeV}}
49 \CustomizeMathJax{\newcommand{\keV}{\kilo\TeV}}
50 \CustomizeMathJax{\newcommand{\MeV}{\mega\TeV}}
51 \CustomizeMathJax{\newcommand{\GeV}{\giga\TeV}}
52 \CustomizeMathJax{\newcommand{\TeV}{\tera\TeV}}
53 \CustomizeMathJax{\newcommand{\meVc}{\milli\TeVc}}
54 \CustomizeMathJax{\newcommand{\keVc}{\kilo\TeVc}}
55 \CustomizeMathJax{\newcommand{\MeVc}{\mega\TeVc}}
56 \CustomizeMathJax{\newcommand{\GeVc}{\giga\TeVc}}
57 \CustomizeMathJax{\newcommand{\TeVc}{\tera\TeVc}}
58 \CustomizeMathJax{\newcommand{\meVcsq}{\milli\TeVcsq}}
59 \CustomizeMathJax{\newcommand{\keVcsq}{\kilo\TeVcsq}}
60 \CustomizeMathJax{\newcommand{\MeVcsq}{\mega\TeVcsq}}
61 \CustomizeMathJax{\newcommand{\GeVcsq}{\giga\TeVcsq}}
62 \CustomizeMathJax{\newcommand{\TeVcsq}{\tera\TeVcsq}}
63 \fi
64 \end{warpMathJax}

```

File 218 **lwarp-hhline.sty**

§ 327 Package **hhline**

(Emulates or patches code by DAVID CARLISLE.)

Pkg hhline

hhline is patched for use by lwarp.

Only a rudimentary emulation is provided so far. If the argument contains any = characters, the result is a double \hline. If none, the result is a single \hline.

for HTML output:

```

1 \LWR@ProvidesPackagePass{hhline}[2014/10/28]
2 \newrobustcmd*{\LWR@HTML@hhline}[1]{%
3   \edef\LWR@tempone{\detokenize\expandafter{#1}}%
4   \IfSubStr[1]{\LWR@tempone}{=}{\hline\hline}{\hline}%
5 }
6 % ^^A or:
7 % ^^A \newrobustcmd*{\LWR@HTML@hhline}[1]{\LWR@getmynexttoken}
8
9 \AtBeginDocument{\LWR@expandableformatted{hhline}}

```

For MATHJAX. A simple \hline is used.

```

10 \begin{warpMathJax}
11 \CustomizeMathJax{\newcommand{\hhline}[1]{\hline}}
12 \end{warpMathJax}

```

File 219 **lwarp-hhtensor.sty**

§ 328 Package **hhtensor**

(Emulates or patches code by HARALD HARDERS.)

Pkg hhtensor

hhtensor is used as-is, and emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{hhtensor}[2011/12/29]

2 \begin{warpMathJax}
3 \iftensor@bold
4   \CustomizeMathJax{\newcommand{\vec}[1]{\boldsymbol{#1}}}
5   \CustomizeMathJax{\newcommand{\matr}[1]{\boldsymbol{#1}}}
6   \CustomizeMathJax{\newcommand{\tens}[2]{\boldsymbol{#1}}}
7 \else
8   \iftensor@uLine
9     \CustomizeMathJax{\newcommand{\vec}[1]{\ushort{#1}}}
10    \CustomizeMathJax{\newcommand{\matr}[1]{\ushorTd{#1}}}
11    \CustomizeMathJax{\newcommand{\tens}[2]{
12      \underset{
13        \raise{.5ex}{\underset{#2}{\sim}}
14      }{#1}
15    }}
16 \else
17   \CustomizeMathJax{\newcommand{\matr}[1]{\vec{\vec{#1}}}}
18   \CustomizeMathJax{\newcommand{\tens}[2]{
19     \underset{
20       \raise{.5ex}{\underset{#2}{\sim}}
21     }{#1}
22   }}
23 \fi
24 \fi
25 \CustomizeMathJax{\newcommand{\dcdot}{\mathrel{\cdot\mkern 0.0mu \cdot}}}
26 \CustomizeMathJax{\newcommand{\trans}{\textsuperscript{\mathrm{T}}}}
27 \end{warpMathJax}

```

File 220 **lwarp-hypbmsec.sty**

§ 329 Package **hypbmsec**

Pkg hypbmsec

hypbmsec is emulated by the lwarp core.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{hypbmsec}[2016/05/16]

```

File 221 **lwarp-hypcap.sty**

§ 330 Package **hypcap**

Pkg hypcap

hypcap is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{hypcap}[2016/05/16]

2 \newcommand*\capstart{}
3 \newcommand*\hypcapspace{}
4 \newcommand*\hypcapredef[1]{}
5 \newcommand*\capstartfalse{}
6 \newcommand*\capstarttrue{}

```

File 222 **lwarp-hypdestopt.sty**

§ 331 Package **hypdestopt**

Pkg hypdestopt hypdestopt is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{hypdestopt}[2016/05/21]

File 223 **lwarp-hypernat.sty**

§ 332 Package **hypernat**

Pkg hypernat hypernat is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{hypernat}[2001/07/09]

File 224 **lwarp-hyperref.sty**

§ 333 Package **hyperref**

(Emulates or patches code by SEBASTIAN RAHTZ, HEIKO OBERDIEK, THE L^AT_EX3 PROJECT.)

Pkg hyperref hyperref is emulated.

for HTML output:

```

1 % \LWR@ProvidesPackageDrop{hyperref}% not allowed
2 % \ProvidesPackage{lwarp-#1-#2}% not allowed
3 \PackageInfo{lwarp}{%
4 Using the lwarp HTML version of package ‘hyperref’,\MessageBreak
5 and discarding options except backref, pagebackref.\MessageBreak
6 (Not using \protect\ProvidesPackage, so that other packages\MessageBreak
7 do not attempt to patch lwarp’s version of ‘hyperref’.)\MessageBreak}

8 \SetupKeyvalOptions{family=LWR@hyperref,prefix=LWR@hyperref@}
9
10 \newcommand{\hypersetup}[1]{\setkeys{LWR@hyperref}{#1}}
11
12 \define@key{LWR@hyperref}{a4paper}[]{}
13 \define@key{LWR@hyperref}{a5paper}[]{}
14 \define@key{LWR@hyperref}{b5paper}[]{}
15 \define@key{LWR@hyperref}{letterpaper}[]{}
16 \define@key{LWR@hyperref}{legalpaper}[]{}
17 \define@key{LWR@hyperref}{executivepaper}[]{}
18 \define@key{LWR@hyperref}{implicit}[]{}

```

```
19 \define@key{LWR@hyperref}{draft}[]{}
20 \define@key{LWR@hyperref}{final}[]{}
21 \define@key{LWR@hyperref}{setpagesize}[]{}
22 \define@key{LWR@hyperref}{debug}[]{}
23 \define@key{LWR@hyperref}{linktocpage}[]{}
24 \define@key{LWR@hyperref}{linktoc}[]{}
25 \define@key{LWR@hyperref}{extension}[]{}
26 \define@key{LWR@hyperref}{verbose}[]{}
27 \define@key{LWR@hyperref}{typexml}[]{}
28 \define@key{LWR@hyperref}{raiselinks}[]{}
29 \define@key{LWR@hyperref}{breaklinks}[]{}
30 \define@key{LWR@hyperref}{localanchorname}[]{}
31 \define@key{LWR@hyperref}{pageanchor}[]{}
32 \define@key{LWR@hyperref}{plainpages}[]{}
33 \define@key{LWR@hyperref}{naturalnames}[]{}
34 \define@key{LWR@hyperref}{hypertextnames}[]{}
35 \define@key{LWR@hyperref}{nesting}[]{}
36 \define@key{LWR@hyperref}{destlabel}[]{}
37 \define@key{LWR@hyperref}{unicode}[]{}
38 \define@key{LWR@hyperref}{pdfencoding}[]{}
39 \define@key{LWR@hyperref}{psdextra}[]{}
40 \define@key{LWR@hyperref}{pdfversion}[]{}
41 \define@key{LWR@hyperref}{dviptdmx-outline-open}[]{}
42 \define@key{LWR@hyperref}{driverfallback}[]{}
43 \define@key{LWR@hyperref}{customdriver}[]{}
44 \define@key{LWR@hyperref}{hyperfigures}[]{}
45 \define@key{LWR@hyperref}{hyperfootnotes}[]{}
46 \define@key{LWR@hyperref}{hyperindex}[]{}
47 \define@key{LWR@hyperref}{encap}[]{}
48 \define@key{LWR@hyperref}{colorlinks}[]{}
49 \define@key{LWR@hyperref}{ocgcolorlinks}[]{}
50 \define@key{LWR@hyperref}{frenchlinks}[]{}
51 \define@key{LWR@hyperref}{bookmarks}[]{}
52 \define@key{LWR@hyperref}{bookmarksopen}[]{}
53 \define@key{LWR@hyperref}{bookmarksdepth}[]{}
54 \define@key{LWR@hyperref}{bookmarksopenlevel}[]{}
55 \define@key{LWR@hyperref}{bookmarkstype}[]{}
56 \define@key{LWR@hyperref}{bookmarksnumbered}[]{}
57 \define@key{LWR@hyperref}{CJKbookmarks}[]{}
58 \define@key{LWR@hyperref}{link}[]{}
59 \define@key{LWR@hyperref}{anchor}[]{}
60 \define@key{LWR@hyperref}{cite}[]{}
61 \define@key{LWR@hyperref}{file}[]{}
62 \define@key{LWR@hyperref}{url}[]{}
63 \define@key{LWR@hyperref}{menu}[]{}
64 \define@key{LWR@hyperref}{run}[]{}
65 \define@key{LWR@hyperref}{linkbordercolor}[]{}
66 \define@key{LWR@hyperref}{anchorbordercolor}[]{}
67 \define@key{LWR@hyperref}{citebordercolor}[]{}
68 \define@key{LWR@hyperref}{filebordercolor}[]{}
69 \define@key{LWR@hyperref}{urlbordercolor}[]{}
70 \define@key{LWR@hyperref}{menubordercolor}[]{}
71 \define@key{LWR@hyperref}{runbordercolor}[]{}
72 \define@key{LWR@hyperref}{pagecolor}[]{}
73 \define@key{LWR@hyperref}{baseurl}[]{}
74 \define@key{LWR@hyperref}{linkfileprefix}[]{}
75 \define@key{LWR@hyperref}{pdfpagetransition}[]{}
76 \define@key{LWR@hyperref}{pdfpageduration}[]{}
77 \define@key{LWR@hyperref}{pdfpagehidden}[]{}
78 \define@key{LWR@hyperref}{pagebordercolor}[]{}

```

```
79 \define@key{LWR@hyperref}{allbordercolors}[]{}
80 \define@key{LWR@hyperref}{pdfhighlight}[]{}
81 \define@key{LWR@hyperref}{pdfborder}[]{}
82 \define@key{LWR@hyperref}{pdfborderstyle}[]{}
83 \define@key{LWR@hyperref}{pdfprintpagerange}[]{}
84 \define@key{LWR@hyperref}{pdfusetitle}[]{}
85 \define@key{LWR@hyperref}{pdftitle}[]{}
86 \define@key{LWR@hyperref}{pdfauthor}[]{}
87 \define@key{LWR@hyperref}{pdfproducer}[]{}
88 \define@key{LWR@hyperref}{pdfcreator}[]{}
89 \define@key{LWR@hyperref}{addtopdfcreator}[]{}
90 \define@key{LWR@hyperref}{pdfcreationdate}[]{}
91 \define@key{LWR@hyperref}{pdfmoddate}[]{}
92 \define@key{LWR@hyperref}{pdfsubject}[]{}
93 \define@key{LWR@hyperref}{pdfkeywords}[]{}
94 \define@key{LWR@hyperref}{pdftrapped}[]{}
95 \define@key{LWR@hyperref}{pdfinfo}[]{}
96 \define@key{LWR@hyperref}{pdfview}[]{}
97 \define@key{LWR@hyperref}{pdflinkmargin}[]{}
98 \define@key{LWR@hyperref}{pdfstartpage}[]{}
99 \define@key{LWR@hyperref}{pdfstartview}[]{}
100 \define@key{LWR@hyperref}{pdfremotestartview}[]{}
101 \define@key{LWR@hyperref}{pdfpagescrop}[]{}
102 \define@key{LWR@hyperref}{pdftoolbar}[]{}
103 \define@key{LWR@hyperref}{pdfmenubar}[]{}
104 \define@key{LWR@hyperref}{pdfwindowui}[]{}
105 \define@key{LWR@hyperref}{pdffitwindow}[]{}
106 \define@key{LWR@hyperref}{pdfcenterwindow}[]{}
107 \define@key{LWR@hyperref}{pdfdisplaydoctitle}[]{}
108 \define@key{LWR@hyperref}{pdfa}[]{}
109 \define@key{LWR@hyperref}{pdfnewwindow}[]{}
110 \define@key{LWR@hyperref}{pdflang}[]{}
111 \define@key{LWR@hyperref}{pdfpageLabels}[]{}
112 \define@key{LWR@hyperref}{pdfescapeform}[]{}
113 \define@key{LWR@hyperref}{english}[]{}
114 \define@key{LWR@hyperref}{UKenglish}[]{}
115 \define@key{LWR@hyperref}{british}[]{}
116 \define@key{LWR@hyperref}{USenglish}[]{}
117 \define@key{LWR@hyperref}{american}[]{}
118 \define@key{LWR@hyperref}{german}[]{}
119 \define@key{LWR@hyperref}{austrian}[]{}
120 \define@key{LWR@hyperref}{ngerman}[]{}
121 \define@key{LWR@hyperref}{naustrian}[]{}
122 \define@key{LWR@hyperref}{russian}[]{}
123 \define@key{LWR@hyperref}{brazil}[]{}
124 \define@key{LWR@hyperref}{brazilian}[]{}
125 \define@key{LWR@hyperref}{portuguese}[]{}
126 \define@key{LWR@hyperref}{spanish}[]{}
127 \define@key{LWR@hyperref}{catalan}[]{}
128 \define@key{LWR@hyperref}{afrikaans}[]{}
129 \define@key{LWR@hyperref}{french}[]{}
130 \define@key{LWR@hyperref}{frenchb}[]{}
131 \define@key{LWR@hyperref}{français}[]{}
132 \define@key{LWR@hyperref}{acadian}[]{}
133 \define@key{LWR@hyperref}{canadien}[]{}
134 \define@key{LWR@hyperref}{italian}[]{}
135 \define@key{LWR@hyperref}{magyar}[]{}
136 \define@key{LWR@hyperref}{hungarian}[]{}
137 \define@key{LWR@hyperref}{greek}[]{}
138 \define@key{LWR@hyperref}{dutch}[]{}

```

```
139 \define@key{LWR@hyperref}{tex4ht}[]{}
140 \define@key{LWR@hyperref}{pdftex}[]{}
141 \define@key{LWR@hyperref}{luatex}[]{}
142 \define@key{LWR@hyperref}{nativepdf}[]{}
143 \define@key{LWR@hyperref}{dvi pdfm}[]{}
144 \define@key{LWR@hyperref}{dvi pdfmx}[]{}
145 \define@key{LWR@hyperref}{xetex}[]{}
146 \define@key{LWR@hyperref}{pdfmark}[]{}
147 \define@key{LWR@hyperref}{dvips}[]{}
148 \define@key{LWR@hyperref}{hypertex}[]{}
149 \define@key{LWR@hyperref}{vtex}[]{}
150 \define@key{LWR@hyperref}{vtex pdfmark}[]{}
151 \define@key{LWR@hyperref}{dviwindo}[]{}
152 \define@key{LWR@hyperref}{dvipsone}[]{}
153 \define@key{LWR@hyperref}{textures}[]{}
154 \define@key{LWR@hyperref}{latex2html}[]{}
155 \define@key{LWR@hyperref}{ps2pdf}[]{}
156 \define@key{LWR@hyperref}{vietnamese}[]{}
157 \define@key{LWR@hyperref}{vietnam}[]{}
158 \define@key{LWR@hyperref}{arabic}[]{}
159 \define@key{LWR@hyperref}{hide links}[]{}
160 \define@key{LWR@hyperref}{draft}[]{}
161 \define@key{LWR@hyperref}{no links}[]{}
162 \define@key{LWR@hyperref}{final}[]{}
163 \define@key{LWR@hyperref}{pdfa}[]{}
164 \define@key{LWR@hyperref}{pdfversion}[]{}
165 \define@key{LWR@hyperref}{typexml}[]{}
166 \define@key{LWR@hyperref}{tex4ht}[]{}
167 \define@key{LWR@hyperref}{pdftex}[]{}
168 \define@key{LWR@hyperref}{nativepdf}[]{}
169 \define@key{LWR@hyperref}{dvi pdfm}[]{}
170 \define@key{LWR@hyperref}{dvi pdfmx}[]{}
171 \define@key{LWR@hyperref}{dvi pdfmx-outline-open}[]{}
172 \define@key{LWR@hyperref}{pdfmark}[]{}
173 \define@key{LWR@hyperref}{dvips}[]{}
174 \define@key{LWR@hyperref}{hypertex}[]{}
175 \define@key{LWR@hyperref}{vtex}[]{}
176 \define@key{LWR@hyperref}{vtex pdfmark}[]{}
177 \define@key{LWR@hyperref}{dviwindo}[]{}
178 \define@key{LWR@hyperref}{dvipsone}[]{}
179 \define@key{LWR@hyperref}{textures}[]{}
180 \define@key{LWR@hyperref}{latex2html}[]{}
181 \define@key{LWR@hyperref}{ps2pdf}[]{}
182 \define@key{LWR@hyperref}{xetex}[]{}
183 \define@key{LWR@hyperref}{driver fallback}[]{}
184 \define@key{LWR@hyperref}{custom driver}[]{}
185 \define@key{LWR@hyperref}{pdfversion}[]{}
186 \define@key{LWR@hyperref}{bookmarks}[]{}
187 \define@key{LWR@hyperref}{ocg color links}[]{}
188 \define@key{LWR@hyperref}{color links}[]{}
189 \define@key{LWR@hyperref}{french links}[]{}
190 \define@key{LWR@hyperref}{backref}[]{}
191 \define@key{LWR@hyperref}{page backref}[]{}
192 \define@key{LWR@hyperref}{dest label}[]{}
193 \define@key{LWR@hyperref}{pdf pages crop}[]{}
194 \define@key{LWR@hyperref}{pdf page mode}[]{}
195 \define@key{LWR@hyperref}{pdf non full screen page mode}[]{}
196 \define@key{LWR@hyperref}{pdf direction}[]{}
197 \define@key{LWR@hyperref}{pdf view area}[]{}
198 \define@key{LWR@hyperref}{pdf view clip}[]{}

```

```

199 \define@key{LWR@hyperref}{pdfprintarea}[]{}
200 \define@key{LWR@hyperref}{pdfprintclip}[]{}
201 \define@key{LWR@hyperref}{pdfprintscaling}[]{}
202 \define@key{LWR@hyperref}{pdfduplex}[]{}
203 \define@key{LWR@hyperref}{pdfpicktraybypdfsize}[]{}
204 \define@key{LWR@hyperref}{pdfprintpagerange}[]{}
205 \define@key{LWR@hyperref}{pdfnumcopies}[]{}
206 \define@key{LWR@hyperref}{pdfstartview}[]{}
207 \define@key{LWR@hyperref}{pdfstartpage}[]{}
208 \define@key{LWR@hyperref}{pdftoolbar}[]{}
209 \define@key{LWR@hyperref}{pdfmenubar}[]{}
210 \define@key{LWR@hyperref}{pdfwindowui}[]{}
211 \define@key{LWR@hyperref}{pdffitwindow}[]{}
212 \define@key{LWR@hyperref}{pdfcenterwindow}[]{}
213 \define@key{LWR@hyperref}{pdfdisplaydoctitle}[]{}
214 \define@key{LWR@hyperref}{pdfpagelayout}[]{}
215 \define@key{LWR@hyperref}{pdflang}[]{}
216 \define@key{LWR@hyperref}{baseurl}[]{}
217 \define@key{LWR@hyperref}{pdfusetitle}[]{}
218 \define@key{LWR@hyperref}{pdfpagelabels}[]{}
219 \define@key{LWR@hyperref}{hyperfootnotes}[]{}
220 \define@key{LWR@hyperref}{hyperfigures}[]{}
221 \define@key{LWR@hyperref}{hyperindex}[]{}
222 \define@key{LWR@hyperref}{encap}[]{}
223 \define@key{LWR@hyperref}{linkcolor}[]{}
224 \define@key{LWR@hyperref}{anchorcolor}[]{}
225 \define@key{LWR@hyperref}{citecolor}[]{}
226 \define@key{LWR@hyperref}{filecolor}[]{}
227 \define@key{LWR@hyperref}{urlcolor}[]{}
228 \define@key{LWR@hyperref}{menucolor}[]{}
229 \define@key{LWR@hyperref}{runcolor}[]{}
230 \define@key{LWR@hyperref}{allcolors}[]{}
231
232 \DeclareStringOption[false]{backref}[section]
233
234 \DeclareBoolOption{pagebackref}
235
236 \DeclareDefaultOption{}
237
238 \ProcessKeyvalOptions*\relax

```

Maybe load backref:

```

239 \ifdefstring{\LWR@hyperref@backref}{section}
240   {\RequirePackage{backref}}
241   {}
242
243 \ifdefstring{\LWR@hyperref@backref}{slide}
244   {\RequirePackage{backref}}
245   {}
246
247 \ifdefstring{\LWR@hyperref@backref}{page}
248   {\RequirePackage{backref}}
249   {}
250
251 \ifLWR@hyperref@pagebackref
252   \RequirePackage{backref}
253 \fi

```

```

254 \LetLtxMacro\href\LWR@href
255 \LetLtxMacro\nolinkurl\LWR@nolinkurl
256 \LetLtxMacro\url\LWR@url
257 \LetLtxMacro\phantomsection\LWR@phantomsection

```

```
258 \newcommand*{\hyperbaseurl}[1]{}
```

No application for lwarp:

```

259 \newcommand*{\HyperDestNameFilter}[1]{#1}
260 \newcommand*{\HyperDestLabelReplace}[1]{#1}
261 \newcommand*{\HyperDestRename}[2]{}

```

No application for lwarp:

```
262 \newcommand*{\hyperget}[2]{}{}
```

\hyperimage

`{<URL>} {<alt text>}`

Insert an image with alt text:

```

263 \NewDocumentCommand{\LWR@hyperimageb}{m +m}{%
264   \LWR@ensuredoingapar%
265   \def\LWR@templink{#1}%
266   \@onelevel@sanitize\LWR@templink%
267   \LWR@htmltag{%
268     img src=\textquotedbl\LWR@templink\textquotedbl\ %
269     alt=\textquotedbl#2\textquotedbl\ %
270     class=\textquotedbl{}hyperimage\textquotedbl%
271   }%
272   \LWR@ensuredoingapar%
273   \endgroup%
274 }
275
276 \newrobustcmd*{\hyperimage}{%
277   \begingroup%
278   \LWR@linkcatcodes%
279   \LWR@hyperimageb%
280 }
281

```

\hyperdef

`{<1: category>} {<2: name>} {<3: text>}`

Creates an HTML anchor to category.name with the given text.

```

282 \NewDocumentCommand{\LWR@hyperdefb}{m m +m}{%
283   \LWR@ensuredoingapar%
284   \LWR@label@createtag{#1.#2}%
285   #3%
286   \endgroup%
287 }
288
289 \newcommand*{\hyperdef}{%
290   \begingroup%
291   \LWR@linkcatcodes%
292   \LWR@hyperdefb%
293 }
294

```

`\LWR@hyperrefb``{\langle 1: URL\rangle} {\langle 2: category\rangle} {\langle 3: name\rangle} {\langle 4: text\rangle}`Creates an HTML link to `URL#category.name` with the given text.

```

295 \newcommand{\LWR@hyperreffinish}[1]{%
296   \begingroup%
297   \RenewDocumentCommand{\ref}{s m}{\LWR@print@ref{##2}}%
298   #1%
299   \endgroup%
300   \LWR@htmltag{/a}%
301 }
302
303 \newcommand*\LWR@hyperrefbb[3]{%
304   \LWR@htmltag{%
305     a href=\textquotedbl%
306       \detokenize\expandafter{#1}\LWR@hashmark%
307       \detokenize\expandafter{#2}.\detokenize\expandafter{#3}%
308     \textquotedbl%
309     \LWR@addlinktitle%
310   }%
311   \endgroup%
312   \LWR@hyperreffinish%
313 }
314
315 \newrobustcmd*\LWR@hyperrefb}{%
316   \begingroup%
317   \LWR@linkcatcodes%
318   \LWR@hyperrefbb%
319 }

```

`\LWR@hyperrefc``[\langle label\rangle] {\langle text\rangle}`Creates text as an HTML link to the L^AT_EX label.

```

320 \NewDocumentCommand{\LWR@hyperrefcb}{O{label}}{%
321   \LWR@startref{#1}%
322   \endgroup%
323   \LWR@hyperreffinish%
324 }
325
326 \newcommand*\LWR@hyperrefc}{%
327   \begingroup%
328   \LWR@linkcatcodes%
329   \LWR@hyperrefcb%
330 }

```

`\hyperref`
`{\langle 1: URL\rangle} {\langle 2: category\rangle} {\langle 3: name\rangle} {\langle 4: text\rangle} — or —`
`[\langle 1: label\rangle] {\langle 2: text\rangle}`

```

331 \DeclareRobustCommand*\hyperref}{%
332   \LWR@ensuredoingapar%
333   \@ifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
334 }

```

`\hypertarget``{\langle name\rangle} {\langle text\rangle}`

Creates an anchor to name with the given text.

```

335 \NewDocumentCommand{\LWR@hypertargetb}{m +m}{%
336   \Label{\LWR-ht-#1}%
337   #2%

```

```

338   \endgroup%
339 }
340
341 \newcommand*{\hypertarget}{%
342   \LWR@ensuredoingapar%
343   \beginingroup%
344   \LWR@linkcatcodes%
345   \LWR@hypertargetb%
346 }

```

`\hyperlink`

`{\langle name \rangle} {\langle text \rangle}`

Creates a link to the anchor created by `hypertarget`, with the given link text.

Declared because also defined by `memoir`.

```

347 \DeclareDocumentCommand{\LWR@hyperlinkb}{m}{%
348   \ifbool{\LWR@insidemathcomment}%
349     {\endgroup}%
350     {\LWR@hyperrefcb[\LWR-ht-#1]}%
351 }
352
353 \DeclareDocumentCommand{\hyperlink}{}{%
354   \LWR@ensuredoingapar%
355   \beginingroup%
356   \LWR@linkcatcodes%
357   \LWR@hyperlinkb%
358 }

```

`\LWR@nullify@hyperref`

`{\langle 1: URL \rangle} {\langle 2: category \rangle} {\langle 3: name \rangle} {\langle 4: text \rangle}` — or —
`[\langle 1: label \rangle] {\langle 2: text \rangle}`

```

359 \newcommand{\LWR@nullify@hyperrefb}[2][{}]{
360
361 \newcommand*{\LWR@nullify@hyperref}{%
362   \@ifnextchar[\LWR@nullify@hyperrefb\@fourthoffour%
363 }

```

To nullify in a `lateximage` or `svg math`. `\hypertarget` must be left active for references to work, and does not harm.

```

364 \appto\LWR@restoreorigformatting{%
365   \LetLtxMacro\hyperdef\@thirdofthree
366   \LetLtxMacro\hyperlink\@secondoftwo%
367   \LetLtxMacro\hyperref\LWR@nullify@hyperref%
368 }

```

`\autoref`

`* {\langle label \rangle}`

For HTML, `\cleveref` is used instead.

```

369 \NewDocumentCommand{\autoref}{s m}{%
370   \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
371 }

```

`\autopageref`

`{\langle label \rangle}`

For HTML, `\cleveref` is used instead.

```

372 \NewDocumentCommand{\autopageref}{s m}{%

```

```

373 \IfBooleanTF{#1}{\cpageref{#2}}{\cref{#2}}%
374 }

```

Default names:

```

375 \def\equationautorefname{Equation}%
376 \def\footnoteautorefname{footnote}%
377 \def\itemautorefname{item}%
378 \def\figureautorefname{Figure}%
379 \def\tableautorefname{Table}%
380 \def\partautorefname{Part}%
381 \def\appendixautorefname{Appendix}%
382 \def\chapterautorefname{chapter}%
383 \def\sectionautorefname{section}%
384 \def\subsectionautorefname{subsection}%
385 \def\subsubsectionautorefname{subsubsection}%
386 \def\paragraphautorefname{paragraph}%
387 \def\subparagraphautorefname{subparagraph}%
388 \def\FancyVerbLineautorefname{line}%
389 \def\theoremautorefname{Theorem}%
390 \def\pageautorefname{page}%

```

```
\pdfstringdef      {\langle macroname \rangle} {\langle TEXstring \rangle}
```

```
391 \newcommand{\pdfstringdef}[2]{}
```

```
\pdfbookmark      [ \langle level \rangle ] {\langle text \rangle} {\langle name \rangle}
```

```
392 \newcommand{\pdfbookmark}[3][[]]{}
```

```
\currentpdfbookmark      {\langle text \rangle} {\langle name \rangle}
```

```
393 \newcommand{\currentpdfbookmark}[2]{}
```

```
\subpdfbookmark      {\langle text \rangle} {\langle name \rangle}
```

```
394 \newcommand{\subpdfbookmark}[2]{}
```

```
\belowpdfbookmark      {\langle text \rangle} {\langle name \rangle}
```

```
395 \newcommand{\belowpdfbookmark}[2]{}
```

```
\texorpdfstring      {\langle TEXstring \rangle} {\langle PDFstring \rangle}
```

```
396 \let\texorpdfstring\relax
```

```
397 \newcommand{\texorpdfstring}[2]{#1}
```

```
{\langle commands \rangle}
```

```
\pdfstringdefDisableCommands
```

```
398 \newcommand{\pdfstringdefDisableCommands}[1]{}
```

```
\hypercalcbp      {\langle dimen \rangle} From hyperref.
```

```
399 \def\hypercalcbp#1{%
```

```
400 \strip@pt\dimexpr 0.99626401\dimexpr(#1)\relax\relax
```

```
401 }%
```

<code>\Acrobatmenu</code>	<code>{\langle menuoption \rangle} {\langle text \rangle}</code> 402 <code>\newcommand{\Acrobatmenu}[2]{}</code>
<code>\TextField</code>	<code>[\langle parameters \rangle] {\langle label \rangle}</code> 403 <code>\DeclareRobustCommand{\TextField}[2][{}]</code>
<code>\CheckBox</code>	<code>[\langle parameters \rangle] {\langle label \rangle}</code> 404 <code>\DeclareRobustCommand{\CheckBox}[2][{}]</code>
<code>\ChoiceMenu</code>	<code>[\langle parameters \rangle] {\langle label \rangle} {\langle choices \rangle}</code> 405 <code>\DeclareRobustCommand{\ChoiceMenu}[3][{}]</code>
<code>\PushButton</code>	<code>[\langle parameters \rangle] {\langle label \rangle}</code> 406 <code>\DeclareRobustCommand{\PushButton}[2][{}]</code>
<code>\Submit</code>	<code>[\langle parameters \rangle] {\langle label \rangle}</code> 407 <code>\DeclareRobustCommand{\Submit}[2][{}]</code>
<code>\Reset</code>	<code>[\langle parameters \rangle] {\langle label \rangle}</code> 408 <code>\DeclareRobustCommand{\Reset}[2][{}]</code>
<code>\Gauge</code>	<code>[\langle parameters \rangle] {\langle label \rangle}</code> 409 <code>\DeclareRobustCommand{\Gauge}[2][{}]</code>
<code>\LayoutTextField</code>	<code>{\langle label \rangle} {\langle field \rangle}</code> 410 <code>\newcommand*{\LayoutTextField}[2]{}</code>
<code>\LayoutChoiceField</code>	<code>{\langle label \rangle} {\langle field \rangle}</code> 411 <code>\newcommand*{\LayoutChoiceField}[2]{}</code>
<code>\LayoutCheckField</code>	<code>{\langle label \rangle} {\langle field \rangle}</code> 412 <code>\newcommand*{\LayoutCheckField}[2]{}</code>
<code>\MakeRadioField</code>	<code>{\langle width \rangle} {\langle height \rangle}</code> 413 <code>\newcommand*{\MakeRadioField}[2]{}</code>
<code>\MakeCheckField</code>	<code>{\langle width \rangle} {\langle height \rangle}</code> 414 <code>\newcommand*{\MakeCheckField}[2]{}</code>
<code>\MakeTextField</code>	<code>{\langle width \rangle} {\langle height \rangle}</code>

```
415 \newcommand*\MakeTextField}[2]{}
```

```
\MakeChoiceField      {\langle width \rangle} {\langle height \rangle}
```

```
416 \newcommand*\MakeChoiceField}[2]{}
```

```
\MakeFieldButton      {\langle text \rangle}
```

```
417 \newcommand\MakeFieldButton}[1]{}
```

File 225 **lwarp-hyperxmp.sty**

§ 334 Package **hyperxmp**

Pkg hyperxmp

hyperxmp is ignored.

for HTML output: Discard all options for lwarp-hyperxmp:

```
1 \LWR@ProvidesPackageDrop{hyperxmp}[2018/11/27]
2
3 \define@key{LWR@hyperref}{pdfdate}[]{}
4 \define@key{LWR@hyperref}{pdfmetadate}[]{}
5 \define@key{LWR@hyperref}{pdfcopyright}[]{}
6 \define@key{LWR@hyperref}{pdfstype}[]{}
7 \define@key{LWR@hyperref}{pdflicenseurl}[]{}
8 \define@key{LWR@hyperref}{pdfauthortitle}[]{}
9 \define@key{LWR@hyperref}{pdfcaptionwriter}[]{}
10 \define@key{LWR@hyperref}{pdfmetalang}[]{}
11 \define@key{LWR@hyperref}{pdfapart}[]{}
12 \define@key{LWR@hyperref}{pdfaconformance}[]{}
13 \define@key{LWR@hyperref}{pdfuapart}[]{}
14 \define@key{LWR@hyperref}{pdfxstandard}[]{}
15 \define@key{LWR@hyperref}{pdfsource}[]{}
16 \define@key{LWR@hyperref}{pdfdocumentid}[]{}
17 \define@key{LWR@hyperref}{pdfinstanceid}[]{}
18 \define@key{LWR@hyperref}{pdfversionid}[]{}
19 \define@key{LWR@hyperref}{pdfrendition}[]{}
20 \define@key{LWR@hyperref}{pdfpublication}[]{}
21 \define@key{LWR@hyperref}{pdfpubtype}[]{}
22 \define@key{LWR@hyperref}{pdfbytes}[]{}
23 \define@key{LWR@hyperref}{pdfnumpages}[]{}
24 \define@key{LWR@hyperref}{pdfissn}[]{}
25 \define@key{LWR@hyperref}{pdfeissn}[]{}
26 \define@key{LWR@hyperref}{pdfisbn}[]{}
27 \define@key{LWR@hyperref}{pdfbookedition}[]{}
28 \define@key{LWR@hyperref}{pdfpublisher}[]{}
29 \define@key{LWR@hyperref}{pdfvolumenum}[]{}
30 \define@key{LWR@hyperref}{pdfissuenum}[]{}
31 \define@key{LWR@hyperref}{pdfpagerange}[]{}
32 \define@key{LWR@hyperref}{pdfdoi}[]{}
33 \define@key{LWR@hyperref}{pdfurl}[]{}
34 \define@key{LWR@hyperref}{pdfidentifier}[]{}
35 \define@key{LWR@hyperref}{pdfsubtitle}[]{}
36 \define@key{LWR@hyperref}{pdfpubstatus}[]{}
37 \define@key{LWR@hyperref}{pdfcontactaddress}[]{}
38 \define@key{LWR@hyperref}{pdfcontactcity}[]{}
39 \define@key{LWR@hyperref}{pdfcontactregion}[]{}

```

```

40 \define@key{LWR@hyperref}{pdfcontactpostcode}[]{}
41 \define@key{LWR@hyperref}{pdfcontactcountry}[]{}
42 \define@key{LWR@hyperref}{pdfcontactphone}[]{}
43 \define@key{LWR@hyperref}{pdfcontactemail}[]{}
44 \define@key{LWR@hyperref}{pdfcontacturl}[]{}
45 \define@key{LWR@hyperref}{keeppdfinfo}[]{}
46 \define@key{LWR@hyperref}{pdfauthor}[]{}
47 \define@key{LWR@hyperref}{pdfkeywords}[]{}

```

File 226 **lwarp-hyphenat.sty**

§ 335 Package **hyphenat**

Pkg hyphenat

hyphenat is emulated during HTML output, while the print-mode version is used inside a lateximage.

for HTML output:

```

1 \LWR@ProvidesPackagePass{hyphenat}[2009/09/02]

2 \LetLtxMacro\LWRHYNAT@origtextnhtt\textnhtt
3 \LetLtxMacro\LWRHYNAT@originhttfamily\nhttfamily
4 \LetLtxMacro\LWRHYNAT@originohyphens\nohyphens
5 \LetLtxMacro\LWRHYNAT@origbshyp\bshyp
6 \LetLtxMacro\LWRHYNAT@origfshyp\fshyp
7 \LetLtxMacro\LWRHYNAT@origdothyp\dothyp
8 \LetLtxMacro\LWRHYNAT@origcolonyhyp\colonyhyp
9 \LetLtxMacro\LWRHYNAT@orighyp\hyp
10
11 \LetLtxMacro\textnhtt\texttt
12 \LetLtxMacro\nhttfamily\ttfamily
13
14 \renewcommand{\nohyphens}[1]{#1}
15 \renewrobustcmd{\bshyp}{%
16   \ifmode\backslash\else\textbackslash\fi%
17 }
18 \renewrobustcmd{\fshyp}{/}
19 \renewrobustcmd{\dothyp}{.}
20 \renewrobustcmd{\colonyhyp}{:}
21 \renewrobustcmd{\hyp}{-}
22
23 \appto\LWR@restoreorigformatting{%
24 \LetLtxMacro\textnhtt\LWRHYNAT@origtextnhtt%
25 \LetLtxMacro\nhttfamily\LWRHYNAT@originhttfamily%
26 \LetLtxMacro\nohyphens\LWRHYNAT@originohyphens%
27 \LetLtxMacro\bshyp\LWRHYNAT@origbshyp%
28 \LetLtxMacro\fshyp\LWRHYNAT@origfshyp%
29 \LetLtxMacro\dothyp\LWRHYNAT@origdothyp%
30 \LetLtxMacro\colonyhyp\LWRHYNAT@origcolonyhyp%
31 \LetLtxMacro\hyp\LWRHYNAT@orighyp%
32 }

```

File 227 **lwarp-idxlayout.sty**

§ 336 Package **idxlayout**

(Emulates or patches code by THOMAS TITZ.)

Pkg idxlayout

idxlayout is emulated.

for HTML output:

Discard all options for lwarp-idxlayout:

```
1 \LWR@ProvidesPackageDrop{idxlayout}[2012/03/30]
```

```
2 \newcommand{\LWR@indexprenote}{}

```

\AtBeginDocument to help with package load order.

```
3 \AtBeginDocument{
4   \preto\printindex{
5
6   \LWR@maybe@orignewpage
7   \LWR@startpars
8
9   \LWR@indexprenote
10
11  }
12 }
```

```
13 \newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
14 \newcommand*\@noindexprenote{\renewcommand{\LWR@indexprenote}{} }
15
16 \newcommand{\idxlayout}[1]{}
17 \newcommand*\@indexfont{}
18 \newcommand*\@indexjustific{}
19 \newcommand*\@indexsubsdelim{}
20 \newcommand*\@indexstheadcase{}

```

File 228 **lwarp-ifoddpag.sty**§ 337 Package **ifoddpag***(Emulates or patches code by MARTIN SCHARRER.)*

Pkg ifoddpag

ifoddpag is emulated.

for HTML output:

Discard all options for lwarp-ifoddpag:

```
1 \LWR@ProvidesPackageDrop{ifoddpag}[2016/04/23]
```

```
2 \newif\ifoddpag
3
4 \newif\ifoddpagoroneside
5
6 \DeclareRobustCommand{\checkoddpag}{\oddpagtrue\oddpagoronesidetrue}
7
8 \def\oddpag@page{1}
9
10 \def\@ifoddpag{%
11   \expandafter\@firstoftwo
12 }
13
14 \def\@ifoddpagoroneside{%
15   \expandafter\@firstoftwo
16 }
```

File 229 **lwarp-imakeidx.sty**

§ 338 Package **imakeidx**

(Emulates or patches code by ENRICO GREGORIO.)

Pkg imakeidx

imakeidx is patched for use by lwarp.

letter headings When using *makeindex*, to match the print and HTML output's display of index letter headings, specify the `lwarp.ist` style:

```
\makeindex[options={-s lwarp.ist}]
```

(For HTML the `lwarp.ist` style is used automatically, which displays letter headings. When using *xindy* the default style also displays letter headings.)

index setup See section 8.6.18 for how to setup *lwarpmk* to process the indexes with imakeidx, both with and without shell escape.

for HTML output: 1 \LWR@ProvidesPackagePass{imakeidx}[2016/10/15]

Use the new HTML suffix:

```
2 \catcode'\_ =12%
3 \define@key{imki}{name}{\def\imki@name{#1_html}}
4 \catcode'\_ =8%
```

\printindex

The HTML version of \printindex:

```
5 \catcode'\_ =12%
6
7 \renewcommand*\printindex[1][\imki@jobname]{%
8 \LWR@maybe@orignewpage%
9 \LWR@startpars%
10 \ifstrequal{#1}{\imki@jobname}{%
11 \@ifundefined{#1@idxfile}{%
12 \imki@error{#1}%
13 }{%
14 \imki@putindex{#1}%
15 }%
16 }{%
17 \@ifundefined{#1_html@idxfile}{\imki@error{#1_html}}{\imki@putindex{#1_html}}%
18 }%
19 }
20
21 \catcode'\_ =8%
```

\@index

The HTML version of \@index:

```
22 \catcode'\_ =12%
23
24 \def\@index[1]{%
25 \ifstrequal{#1}{\imki@jobname}%
26 {%
27 \@ifundefined{#1@idxfile}%
```

```

28     {%
29     \PackageWarning{lwarp-imakeidx}{Undefined index file '#1'}%
30     \begingroup
31     \@sanitize
32     \imki@nowrindex%
33     }%
34     {%
35     \edef\@idxfile{#1}%
36     \begingroup
37     \@sanitize
38     \@wrindex\@idxfile%
39     }%
40 }%
41 {%
42 \@ifundefined{#1_html@idxfile}%
43 {%
44 \PackageWarning{lwarp-imakeidx}{Undefined index file '#1_html'}%
45 \begingroup
46 \@sanitize
47 \imki@nowrindex%
48 }%
49 {%
50 \edef\@idxfile{#1_html}%
51 \begingroup
52 \@sanitize
53 \@wrindex\@idxfile%
54 }%
55 }%
56 }
57
58 \catcode'\_ =8%
```

\item

\subitem

\subsubitem

HTML versions of \item, etc.:

```

59 \appto\theindex{%
60 \LetLtxMacro\item\LWR@indexitem%
61 \LetLtxMacro\subitem\LWR@indexsubitem%
62 \LetLtxMacro\subsubitem\LWR@indexsubsubitem%
63 }
```

\imki@wrindexentrysplit {<file>}{<entry>}{<page>}

\imki@wrindexentryunique {<file>}{<entry>}{<page>}

While writing index entries, adds an HTML label, and writes the label's index instead of the page number:

```

64 \renewcommand\imki@wrindexentrysplit[3]{%
65 \addtocounter{LWR@autoindex}{1}%
66 \expandafter\protected@write\csname#1@idxfile\endcsname{%
67 \string\indexentry{#2}{\arabic{LWR@autoindex}}}%
68 }
```

The label is assigned after the file write to avoid conflict with cleveref.

```

68 \label{LWRindex-\arabic{LWR@autoindex}}%
69 }
70
71 \renewcommand\imki@wrindexentryunique[3]{%
72 \addtocounter{LWR@autoindex}{1}%
73 }
```

```

73   \protected@write\@indexfile{%
74     {\string\indexentry[#1]{#2}{\arabic{LWR@autoindex}}}%

```

The label is assigned after the file write to avoid conflict with `cleveref`.

```

75   \label{LWRindex-\arabic{LWR@autoindex}}%
76 }
77
78 \def\imki@wrindexsplit#1#2{%
79 \imki@wrindexentrysplit{#1}{#2}{\thepage}%
80 \endgroup\imki@showindexentry{#1}{#2}%
81   \@esphack%
82 }
83
84 \def\imki@wrindexunique#1#2{%
85 \imki@wrindexentryunique{#1}{#2}{\thepage}%
86 \endgroup\imki@showindexentry{#1}{#2}%
87   \@esphack%
88 }
89

```

`\LWR@imki@setxdydefopts`

Sets the *xindy* HTML options, ignoring the user's settings.

```

90 \newcommand*\LWR@imki@setxdydefopts{%
91   \edef\imki@options{ \space %
92     -M \space \LWR@xindyStyle\space %
93     -L \space \LWR@xindyLanguage\space %
94     -C \space \LWR@xindyCodepage\space %
95   }%
96 }

```

`\LWR@imki@setdefopts`

`{\langle user options \rangle}`

Sets the HTML options, added to the user's settings, depending on whether *makeindex* or *xindy* are used.

For *makeindex*, the user's choice is ignored, and only the `lwarp` version is used. (Only one style at a time is possible.)

For *xindy*, multiple modules may be specified, and the `lwarp` version is appended.

```

97 \newcommand*\LWR@imki@setdefopts}[1]{%
98 \ifblank{#1}{%
99   \edef\imki@options{\space -s \space \LWR@makeindexStyle \space}%
100  \ifdefstring{\imki@progdefault}{xindy}{\LWR@imki@setxdydefopts}{}%
101  \ifdefstring{\imki@progdefault}{texindy}{\LWR@imki@setxdydefopts}{}%
102  \ifdefstring{\imki@progdefault}{truexindy}{\LWR@imki@setxdydefopts}{}%
103 }{%
104  \edef\imki@options{\space #1 \space}%
105 }%
106 }

```

`\imki@makeindex`

Use the new HTML options:

```

107 \xpatchcmd{\imki@makeindex}
108   {\let\imki@options\space}
109   {\LWR@imki@setdefopts}{}%
110   {}
111   {\LWR@patcherror{imakeidx}{makeindex}}

```

Use the new HTML options.

```
112 \define@key{imki}{options}{\LWR@imki@setdefopts{#1}}
```

\imki@resetdefaults

Use the new HTML options:

```
113 \xpatchcmd{\imki@resetdefaults}
114   {\def\imki@options{ }}
115   {\LWR@imki@setdefopts{}}
116   {}
117   {\LWR@patcherror{imakeidx}{resetdefaults}}
```

theindex was already defined \AtBeginDocument by the lwarp core, so it must be redefined here similarly, but patched for imakeidx:

Env theindex

```
118 \AtBeginDocument{
119 \renewenvironment*{theindex}{%
120   \imki@maybeaddtotoc
121   \imki@indexlevel{\indexname}
122   \LetLtxMacro\item\LWR@indexitem%
123   \LetLtxMacro\subitem\LWR@indexsubitem%
124   \LetLtxMacro\subsubitem\LWR@indexsubsubitem%
125 }{}
126 }% AtBeginDocument
```

Update to the new defaults:

```
127 \imki@resetdefaults
```

Update to the new patches:

\AtBeginDocument is because \@wrindex is previously defined as \AtBeginDocument in the lwarp core.

```
128 \ifimki@splitindex
129   \let\imki@startidx\imki@startidxunique
130   \AtBeginDocument{\let\@wrindex\imki@wrindexunique}
131   \let\imki@putindex\imki@putindexunique
132   \let\imki@wrindexentry\imki@wrindexentryunique
133   \let\imki@startidxsplit\@undefined
134   \let\imki@wrindexsplit\@undefined
135   \let\imki@putindexsplit\@undefined
136 \else
137   \let\imki@startidx\imki@startidxsplit
138   \AtBeginDocument{\let\@wrindex\imki@wrindexsplit}
139   \let\imki@putindex\imki@putindexsplit
140   \let\imki@wrindexentry\imki@wrindexentrysplit
141   \let\imki@startidxunique\@undefined
142   \let\imki@wrindexunique\@undefined
143   \let\imki@putindexunique\@undefined
144 \fi
```

File 230 **lwarp-impnatty.sty**

§ 339 Package **impnatty**

Pkg impnatty impnatty is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{impnatty}[2019/03/04]

File 231 **lwarp-index.sty**

§ 340 Package **index**

(Emulates or patches code by DAVID M. JONES.)

Pkg index index is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{index}[2004/01/20]

Use `\theLWR@autoindex` instead of `\thepage`. `\@tempwatrue` is used to force an immediate write to the index file instead of waiting until the end of the page.

```

2 \xpatchcmd{\newindex}
3   {\x@newindex[thepage]}
4   {%
5     \@tempwatrue%
6     \x@newindex[theLWR@autoindex]%
7   }
8   {}
9   {\LWR@patcherror{index}{newindex}}
10
11 \xpatchcmd{\renewindex}
12   {\x@renewindex[thepage]}
13   {%
14     \@tempwatrue%
15     \x@renewindex[theLWR@autoindex]%
16   }
17   {}
18   {\LWR@patcherror{index}{renewindex}}
```

Patched to set a new autoindex:

```

19 \xpatchcmd{\@wrindex}
20   {\begingroup}
21   {%
22     \addtocounter{LWR@autoindex}{1}%           lwarp
23     \label{LWRindex-\arabic{LWR@autoindex}}%   lwarp
24     \begingroup%
25   }
26   {}
27   {\LWR@patcherror{index}{@wrindex}}
```

\AtBeginDocument **lwarp** core \lets \@wrindex to \LWR@wrindex. Since the **index** package has been loaded, \let to its version instead:

```
28 \let\LWR@index@wrindex\@wrindex
29
30 \AtBeginDocument{
31 \let\@wrindex\LWR@index@wrindex
32 }
```

Modified to add \index@prologue:

```
33 \AtBeginDocument{
34 \renewenvironment*{theindex}{%
35   \LWR@indexsection{\indexname}%
36   \ifx\index@prologue\@empty\else
37     \index@prologue
38     \bigskip
39   \fi
40   \LetLtxMacro\item\LWR@indexitem%
41   \LetLtxMacro\subitem\LWR@indexsubitem%
42   \LetLtxMacro\subsubitem\LWR@indexsubsubitem%
43 }{ }
44 }% AtBeginDocument
```

Disabled:

```
45 \def\@showidx#1{ }
46 \let\@texttop\relax
47 \renewcommand*{\raggedbottom}{ }
48 \renewcommand*{\flushbottom}{ }
49 \renewcommand*{\markboth}[2]{ }
50 \renewcommand*{\markright}[1]{ }
```

File 232 **lwarp-inputtrc.sty**

§ 341 Package **inputtrc**

(Emulates or patches code by UWE LÜCK.)

Pkg inputtrc

inputtrc is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{inputtrc}[2012/10/10]

Patched to remove extraneous spaces, which sometimes showed up in logos inside a lateximage.

```
2 \renewcommand*{\IT@prim@input}[1]{%
3   \typeout{\IT@indent\IT@currfile INPUTTING #1}%
4 % ... TODO: option to write to '.log' only.
5   \xdef\IT@filestack{{\IT@currfile}\IT@filestack}%
6   \xdef\IT@currfile{#1}%
7   \expandafter \gdef\expandafter \IT@indent\expandafter{%
8     \IT@indent \IT@indent@unit}%          lwarp
9   \@@input#1%                            lwarp
10  \expandafter\IT@pop@indent\IT@indent   \@nil% lwarp
11  \expandafter\IT@pop@file \IT@filestack \@nil% lwarp
```

```
12 \IT@maybe@returnmessage% v0.2          lwarp
13 }
```

File 233 **lwarp-intopdf.sty**

§ 342 Package **intopdf**

Pkg intopdf

intopdf is emulated.

The filespec, MIME type, and description are ignored for now.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{intopdf}[2019/05/28]
2 \NewDocumentCommand{\attachandlink}{o m o m m}{%
3   \LWR@href{#2}{#5}%
4 }
```

File 234 **lwarp-isomath.sty**

§ 343 Package **isomath**

Pkg isomath

(Emulates or patches code by GÜNTER MILDE.)

isomath is used as-is for SVG math, and emulated for MATHJAX.

 **MATHJAX sans** MATHJAX does not provide a sans math font, so sans is typeset as roman.

for HTML output:

```
1 \LWR@ProvidesPackagePass{isomath}[2012/09/04]
2 \begin{warpMathJax}
3 \CustomizeMathJax{\let\mathbfit\boldsymbol}
4 \CustomizeMathJax{\let\mathsfbfit\mathbfit}% not sans
5 \CustomizeMathJax{\let\mathsfit\mathit}% not sans
6 \CustomizeMathJax{\let\vectorsym\mathbfit}
7 \CustomizeMathJax{\let\matrixsym\mathbfit}
8 \CustomizeMathJax{\let\tensorsym\mathsfbfit}
9 \CustomizeMathJax{\let\mathboldsans\mathsfbfit}
10 \CustomizeMathJax{\let\mathbold\mathbfit}
11 \CustomizeMathJax{\let\mathsans\mathrm}% not sans
12 \end{warpMathJax}
```

File 235 **lwarp-isotope.sty**

§ 344 Package **isotope**

Pkg isotope

(Emulates or patches code by HEIKO BAUKE.)

isotope is patched for use by lwarp with svg math, and emulated for MATHJAX.

for HTML output:

```
1 \LWR@ProvidesPackagePass{isotope}[2011/08/26]
```

```

2 \newcommand{\LWR@HTML@isotope@two}[2][]{%
3   \renewcommand{\isotope@atomicnumber}{#1}%
4   \edef\LWR@isotope@alttag{%
5     \textbackslash{
6     \textbackslash{isotope
7     [\isotope@nucleonnumber]%
8     [\isotope@atomicnumber]%
9     \{#2\}
10    \textbackslash}%
11  }%
12 \ifbool{mathjax}%
13  {\LWR@isotope@alttag}%
14  {% SVG
15    \m@th%
16    \LWR@subsingledollar*%
17    {% alt tag
18      \LWR@isotope@alttag%
19    }%
20    {isotope}% add'l hashing
21    {% contents
22      \settowidth\@tempdimb{%
23        \ensuremath{\scriptstyle\isotope@nucleonnumber}%
24      }%
25      \settowidth\@tempdimc{%
26        \ensuremath{\scriptstyle\isotope@atomicnumber}%
27      }%
28      \ifdim\@tempdimb<\@tempdimc\@tempdimb=\@tempdimc\fi%
29      \ensuremath{
30        {%
31          ^{\makebox[\@tempdimb][r]{%
32            \ensuremath{%
33              \scriptstyle\isotope@nucleonnumber%
34            }% ensuremath
35          }}%
36          _{\makebox[\@tempdimb][r]{%
37            \ensuremath{%
38              \scriptstyle\isotope@atomicnumber%
39            }% ensuremath
40          }}%
41          \isotopestyle{#2}%
42        }% ensuremath
43      }% contents
44    }% SVG
45  \endgroup%
46 }%
47 \LWR@formatted{isotope@two}
48
49 \begin{warpMathJax}
50 \CustomizeMathJax{%
51   \newcommand{\LWRisotopetwo}[2][]{%
52     {%
53       \vphantom{\mathrm{#2}}%
54       }^{\LWRisotopenucleonnumber}_{#1}%
55       \mathrm{#2}%
56     }%
57   }%
58 }
59
60 \CustomizeMathJax{%
61   \newcommand{\isotope}[1][]{%

```

```

62     \def\LWRisotopenucleonnumber{#1}%
63     \LWRisotopetwo%
64   }%
65 }
66 \end{warpMathJax}

```

File 236 **lwarp-jurabib.sty**

§ 345 Package **jurabib**

(Emulates or patches code by JENS BERGER.)

Pkg jurabib

jurabib is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{jurabib}[2004/01/25]
2 \renewrobustcmd{\jblangle}{\textless}
3
4 \renewrobustcmd{\jbrangle}{\textgreater}
5
6 \renewcommand*{\jb@biblaw@item}{%
7   \hspace{0.5em}%
8   $\triangleright$
9   \HTMLunicode{25B7}%    lwarp
10  \hspace{0.5em}%
11 }
12
13 \renewrobustcmd{\jbarchsig}[2]{%
14   \ifjbweereinbib
15     \settowidth{\jb@subarchitemwidth}{\jbsamesubarchindent+#1}%
16     \setlength{\jb@subarchentrywidth}{\textwidth-\jb@subarchitemwidth-4em}%
17   \begin{tabular}{@{}p{\jb@subarchitemwidth}@{}j{\jb@subarchentrywidth}@{}}%
18     #1\ifjb@dot\unskip\unskip\unskip.\fi
19     &
20     \quad%    lwarp
21     \ifthenelse{\equal{#2}{}}{\jbarchnameformat{#2}}%
22   \end{tabular}
23   \fi
24 }%
25
26
27 \xpatchcmd{\jb@do@post@item}
28   {\begin{tabular}{p{\jb@biblaw@item@width}j{\jb@biblaw@entry@width}}
29   {}
30   {}
31   {\LWR@patcherror{jurabib}{jb@do@post@item 1}}
32
33 \xpatchcmd{\jb@do@post@item}
34   {\multicolumn{2}{p{\columnwidth}}{\jb@ename}}
35   {\jb@ename}
36   {}
37   {\LWR@patcherror{jurabib}{jb@do@post@item 2}}
38
39 \xpatchcmd{\jb@do@post@item}
40   {\jb@biblaw@item & \jb@fulltitle}
41   {\jb@biblaw@item \quad \jb@fulltitle}
42   {}

```

```

43   {\LWR@patcherror{jurabib}{jb@do@post@item 3}}
44
45 \xpatchcmd{\jb@do@post@item}
46   {\end{tabular}}
47   {}
48   {}
49   {\LWR@patcherror{jurabib}{jb@do@post@item 4}}
50
51 \xpatchcmd{\jb@do@post@item}
52   {\begin{minipage}[t]{\bibnumberwidth}}
53   {}
54   {}
55   {\LWR@patcherror{jurabib}{jb@do@post@item 5}}
56
57 \xpatchcmd{\jb@do@post@item}
58   {\end{minipage}}
59   {\quad}
60   {}
61   {\LWR@patcherror{jurabib}{jb@do@post@item 6}}

```

File 237 **lwarp-karnaugh-map.sty**

§ 346 Package **karnaugh-map**

(Emulates or patches code by MATTIAS JACOBSSON.)

Pkg karnaugh-map

karnaugh-map is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{karnaugh-map}[2017/02/20]

This patch is needed only because `lwarp` changes the definition of `\&`, and the original uses `\ifnum` to compare `0` with `\&`. It is hard to patch this environment, so the entire thing is redefined here, with the `lwarp` modifications identified in comments.

```

2 \RenewDocumentEnvironment{karnaugh-map}{s O{4} O{4} O{1} O{${X_1X_0$} O{${X_3X_2$} O{${X_5X_4$}} }{%
3   \begingroup
4     % store map size {[START]
5     \renewcommand{\@karnaughmap@var@mapsize@}{#2}%
6     \renewcommand{\@karnaughmap@var@mapsize@}{#3}%
7     \renewcommand{\@karnaughmap@var@mapsize@}{#4}%
8     % [END]}
9     % determinate if markings should be color or black and white
10    \IfBooleanTF{#1}{%
11      % should be black and white
12      \renewcommand{\@karnaughmap@var@bw@}{1}%
13    }{%
14      % should be color
15      \renewcommand{\@karnaughmap@var@bw@}{0}%
16    }%
17    %
18    % find matching matrix template and alignment parameters {[START]
19    \newcommand{\@karnaughmap@local@matrixtemplate@}{0}'0' is considered as missing matrix template
20    \newcommand{\@karnaughmap@local@mapprealignment@}{0}%
21    \newcommand{\@karnaughmap@local@mapprealignment@}{0}%
22    \ifnum\@karnaughmap@var@mapsize@\@karnaughmap@var@mapsize@=\@karnaughmap@var@mapsize@=221
23      \renewcommand{\@karnaughmap@local@matrixtemplate@}{%

```

```

24          \&          0 \&          1 \& \phantom{0} \\
25      0 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&          \\
26      1 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&          \\
27      \phantom{0} \&          \&          \&          \\
28      }%
29  \fi
30  \ifnum\@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@=241
31      \renewcommand{\@karnaughmap@local@matrixtemplate}{%
32          \&          0 \&          1 \& \phantom{00} \\
33          00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&          \\
34          01 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&          \\
35          11 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \&          \\
36          10 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \&          \\
37          \phantom{00} \&          \&          \&          \\
38          }%
39  \fi
40  \ifnum\@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@=421
41      \renewcommand{\@karnaughmap@local@matrixtemplate}{%
42          \&          00 \&          01 \&          11 \&          10 \& \phantom{0}
43          0 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(000010)|
44          1 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(000110)|
45          \phantom{00} \&          \&          \&          \&          \&
46          }%
47  \fi
48  \ifnum\@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@=441
49      \renewcommand{\@karnaughmap@local@matrixtemplate}{%
50          \&          00 \&          01 \&          11 \&          10 \& \phantom{0}
51          00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(000010)|
52          01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(000110)|
53          11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(001110)|
54          10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(001010)|
55          \phantom{00} \&          \&          \&          \&          \&
56          }%
57  \fi
58  \ifnum\@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@=442
59      \renewcommand{\@karnaughmap@local@matrixtemplate}{%
60          \&          00 \&          01 \&          11 \&          10 \& \phantom{0}
61          00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(000010)|
62          01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(000110)|
63          11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(001110)|
64          10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(001010)|
65          \phantom{00} \&          \&          \&          \&          \&
66          }%
67      \renewcommand{\@karnaughmap@local@maprealignmentx}{2.5}%
68  \fi
69  \ifnum\@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@ \@karnaughmap@var@mapsize@=444
70      \renewcommand{\@karnaughmap@local@matrixtemplate}{%
71          \&          00 \&          01 \&          11 \&          10 \& \phantom{0}
72          00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(000010)|
73          01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(000110)|
74          11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(001110)|
75          10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(001010)|
76          \phantom{00} \&          \&          \&          \&          \&
77          00 \& |(100000)| \phantom{0} \& |(100001)| \phantom{0} \& |(100011)| \phantom{0} \& |(100010)|
78          01 \& |(100100)| \phantom{0} \& |(100101)| \phantom{0} \& |(100111)| \phantom{0} \& |(100110)|
79          11 \& |(101100)| \phantom{0} \& |(101101)| \phantom{0} \& |(101111)| \phantom{0} \& |(101110)|
80          10 \& |(101000)| \phantom{0} \& |(101001)| \phantom{0} \& |(101011)| \phantom{0} \& |(101010)|
81          \phantom{00} \&          \&          \&          \&          \&
82          }%
83      \renewcommand{\@karnaughmap@local@maprealignmentx}{2.5}%

```

```

84     \renewcommand{\@karnaughmap@local@maprealignments@}{-2.5}%
85     \fi
86     % [END]}
87 % test if a matrix template is found or not(aka "\@karnaughmap@local@matrixtemplate@" equals to '0')
88 \ifdefstring{\@karnaughmap@local@matrixtemplate@}{0}{% lwarp
89%     \ifnum0=\@karnaughmap@local@matrixtemplate@% original
90     % print error if no template could be found
91     \PackageError{lwarp-karnaugh-map}{%
92     Can not find a template fitting your specification
93     (\@karnaughmap@var@mapsizex@\space x \@karnaughmap@var@mapsizex@\space x
94     \@karnaughmap@var@mapsizex@)%
95     }{%
96     Existing templates have the following dimensions:
97     2x2x1, 2x4x1, 4x2x1, 4x4x1, 4x4x2, and 4x4x4.
98     }%
99%     \fi original
100 }{\relax}% lwarp
101 \begin{tikzpicture}
102     % grid
103     % for all dimensions
104     \draw[color=black, ultra thin] (0,0) grid (\@karnaughmap@var@mapsizex@,\@karnaughmap@var@mapsizex@);
105     % when there are 2 sub maps
106     \ifnum\@karnaughmap@var@mapsizex@=2
107         \draw[color=black, ultra thin] (5,0) grid (9,4);
108     \fi
109     % when there are 4 sub maps
110     \ifnum\@karnaughmap@var@mapsizex@=4
111         \draw[color=black, ultra thin] (5,0) grid (9,4);
112         \draw[color=black, ultra thin] (0,-5) grid (4,-1);
113         \draw[color=black, ultra thin] (5,-5) grid (9,-1);
114     \fi
115     % labels
116     % for all dimensions
117     \node[above] at (\@karnaughmap@var@mapsizex@*0.5,\@karnaughmap@var@mapsizex@*0.9) {\small{#5}};
118     \node[left] at (-0.9,\@karnaughmap@var@mapsizex@*0.5) {\small{#6}};
119     % when there are 2 sub maps
120     \ifnum\@karnaughmap@var@mapsizex@=2
121         \node[above] at (7,4.9) {\small{#5}};
122         % extra sub maps labels
123         \node[below] at (2,-0.1) {\small{#7$=0$}};
124         \node[below] at (7,-0.1) {\small{#7$=1$}};
125     \fi
126     % when there are 4 sub maps
127     \ifnum\@karnaughmap@var@mapsizex@=4
128         \node[above] at (7,4.9) {\small{#5}};
129         \node[left] at (-0.9,-3) {\small{#6}};
130         % extra sub maps labels
131         \node[below] at (2,-0.1) {\small{#7$=00$}};
132         \node[below] at (7,-0.1) {\small{#7$=01$}};
133         \node[below] at (2,-5.1) {\small{#7$=10$}};
134         \node[below] at (7,-5.1) {\small{#7$=11$}};
135     \fi
136     % data
137     \matrix[
138     matrix of nodes,
139     ampersand replacement=\&,
140     column sep={1cm,between origins},
141     row sep={1cm,between origins},
142 ] at (\@karnaughmap@var@mapsizex@*0.5+\@karnaughmap@local@maprealignments@,\@karnaughmap@var@mapsizex@*\@karnaughmap@local@matrixtemplate@%
143     \@karnaughmap@local@matrixtemplate@%

```

```

144     };
145 }{
146   \end{tikzpicture}
147 \endgroup
148 }

```

File 238 **lwarp-keyfloat.sty**

§ 347 Package **keyfloat**

(Emulates or patches code by BRIAN DUNN.)

Pkg keyfloat

keyfloat is supported with a considerable amount of hacking. (It's a mashup of lwarp, keyfloat, and tocdata.)

 **keywrap** If placing a `\keyfig[H]` inside a keywrap, use an absolute width for `\keyfig`, instead of lw-proportional widths. (The [H] option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the lw option.)

For wrapped figures, overhang and number of lines are ignored.

for HTML output:

```

1 \LWR@ProvidesPackagePass{keyfloat}[2019/09/23]
2
3 \IfPackageAtLeastTF{keyfloat}{2019/09/23}{\relax}{
4   \PackageError{lwarp-keyfloat}
5   {%
6     The keyfloat package is out of date.\MessageBreak
7     Update to keyfloat v2.01 2019/09/23 or later%
8   }
9   {%
10    Please update the keyfloat package.  It's worth it!%
11  }
12 }

```

After keyfloat has loaded:

```

13 \AtBeginDocument{

```

Hook

[keyfloat]

Integration for keyfloat.

\KFLT@LWR@hook@boxouter

```

14 \providecommand*{\KFLT@LWR@hook@boxouter}{}
15
16 \renewcommand*{\KFLT@LWR@hook@boxouter}{%
17   \ifbool{KFLT@keywrap}{%
18     }{%
19       \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
20         \setlength{\linewidth}{6in}%
21         \setlength{\textwidth}{6in}%
22         \setlength{\textheight}{9in}%
23       }{%
24     }%
25   \normalcolor%
26 }

```

Hook

[keyfloat]

Integration for keyfloat.

\KFLT@LWR@hook@keysubfloats

```
27 \LetLtxMacro\KFLT@LWR@hook@keysubfloats\KFLT@LWR@hook@boxouter
```

Hook [keyfloat] Integration for keyfloat.

```
\KFLT@LWR@hook@keyfloatsminipage
28 \let\KFLT@LWR@hook@keyfloatsminipage\relax
29 \let\endKFLT@LWR@hook@keyfloatsminipage\relax
30 \newenvironment*{KFLT@LWR@hook@keyfloatsminipage}[1]{}{}
```

Hook [keyfloat] Integration for keyfloat.

```
\KFLT@LWR@hook@keyfloats
31 \LetLtxMacro\KFLT@LWR@hook@keyfloats\KFLT@LWR@hook@boxouter
32
33 \renewcommand*{\KFLT@maybeendfloatrow}{%
34   \ifnumless{\value{KFLT@thiscol}}{\value{KFLT@numcols}}%
35     {}% thiscol < numcols
36     {% >=
37       \defcounter{KFLT@thiscol}{0}%
38     }%
39 }%
40
41 \renewcommand{\KFLT@trackrows}%
42 {%
```

If are nested inside a keyfloats or a subfloat:

```
43   \ifboolexpr{%
44     test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or%
45     bool{KFLT@inkeysubfloats}%
46   }%
47   {% nested
```

Tracks row start and end:

```
48   \KFLT@maybestartfloatrow%
```

Possibly fill space between columns:

```
49   \ifnumgreater{\value{KFLT@thiscol}}{1}%
50   {%
51 %     \hfill%
52   }%
53   {}%
54 }% nested
55 {}% not nested
56 }
```

```
57 \RenewDocumentCommand{\KFLT@onefigureimage}{m}
58 {%
59 \LWR@traceinfo{KFLT@onefigureimage}%
60 % \begin{lrbox}{\KFLT@envbox}%
61 \ifthenelse{\NOT\equal{\KFLT@lw}}{}%
62   {%
```

```
63   \ifdimgreater{\KFLT@h}{0pt}%
64   {%
65     \KFLT@frame{%
66       \includegraphics%
```

```

67         [%
68         scale=\KFLT@s,%
69         width=\KFLT@imagewidth,%
70         height=\KFLT@h,%
71         \KFLT@keepaspectratio,%
72         ]{#1}%
73     }%
74 }%
75 {%
76     \KFLT@frame{\includegraphics%
77     [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
78 }%
79 }%
80 {% not linewidth
81     \ifthenelse{\dimtest{\KFLT@w}{>}{0pt}}%
82     {% width is given
83         \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
84         {% w and h
85             \KFLT@frame{\includegraphics[%
86             scale=\KFLT@s,%
87             width=\KFLT@imagewidth,%
88             height=\KFLT@h,%
89             \KFLT@keepaspectratio,%
90             ]{#1}}%
91         }% w and h
92         {% only w
93             \KFLT@frame{\includegraphics%
94             [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
95         }% only w
96     }% width is given
97     {% width is not given
98         \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
99         {%
100             \KFLT@frame{\includegraphics%
101             [scale=\KFLT@s,height=\KFLT@h]{#1}}%
102         }%
103         {%
104             \KFLT@frame{\includegraphics%
105             [scale=\KFLT@s]{#1}}%
106         }%
107     }% width is not given
108 }% not linewidth
109 % \end{lrbox}%
110 % \unskip%
111 % \KFLT@findenvboxwidth%
112 % \begin{turn}{\KFLT@r}%
113 % \KFLT@frame{\usebox{\KFLT@envbox}}%
114 % \unskip%
115 % \end{turn}%
116 %\LWR@traceinfo{KFLT@onefigureimage: done}%
117 }

118 \RenewDocumentEnvironment{KFLT@boxinner}{}
119 {%
120     \LWR@traceinfo{KFLT@boxinner}%
121     \LWR@stoppars%
122     \minipagefullwidth%
123     \ifbool{bool{KFLT@ft} or bool{KFLT@ef}}{%
124         \fminipage{\KFLT@imagewidth}%
125     }{%

```

```

126     \minipage{\KFLT@imagewidth}%
127   }%
128 }
129 {%
130   \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{%
131     \endfminipage%
132   }{%
133     \endminipage%
134   }%
135   \LWR@startpars%
136   \LWR@traceinfo{KFLT@boxinner: done}%
137 }

138 \newcommand*\LWR@KFLT@settextalign}[1]{%
139   \def\LWR@KFLT@textalign{justify}%
140   \ifcsstring{KFLT@#1textalign}{\centering}%
141     {\def\LWR@KFLT@textalign{center}}%
142   }%
143   \ifcsstring{KFLT@#1textalign}{\raggedleft}%
144     {\def\LWR@KFLT@textalign{right}}%
145   }%
146   \ifcsstring{KFLT@#1textalign}{\raggedright}%
147     {\def\LWR@KFLT@textalign{left}}%
148   }%
149 }
150
151 \renewcommand{\KFLT@addtext}[1]
152 {%

```

Is there text to add?

```

153   \ifcseempty{KFLT@#1t}%
154   }% no text
155   {% text to add
156     {% local

```

Add some space, then create a <div> to contain the text:

```

157     \addvspace{\smallskipamount}%
158     \LWR@KFLT@settextalign{#1}%
159     \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%

```

Set the alignment and some text parameters:

```

160 %     \csuse{KFLT@#1textalign}%
161 %     \footnotesize%
162     \setlength{\parskip}{1.5ex}%
163     \setlength{\parindent}{0em}%

```

Typeset the actual text:

```

164     \csuse{KFLT@#1t}%

```

Close it all out with a little more space:

```

165     \end{BlockClass}%
166 %     \par\addvspace{2ex}%
167     }% local

```

```

168   }% text to add
169 }
170
171 \IfPackageLoadedTF{tocdata}
172 {}
173 {% tocdata not loaded
174
175   \newcommand*{\LWR@KFLT@setnamealign}[1]{%
176     \def\LWR@KFLT@textalign{justify}%
177     \ifstrequal{#1}{\centering}%
178       {\def\LWR@KFLT@textalign{center}}%
179       {}%
180     \ifstrequal{#1}{\raggedleft}%
181       {\def\LWR@KFLT@textalign{right}}%
182       {}%
183     \ifstrequal{#1}{\raggedright}%
184       {\def\LWR@KFLT@textalign{left}}%
185       {}%
186   }
187
188   \renewcommand*{\KFLT@@addartisttext}[3]{%
189

```

Add space and create the name inside a <div>:

```

190 %       \addvspace{\medskipamount}%
191 %       \begin{minipage}{\linewidth}%
192   \LWR@KFLT@setnamealign{#3}%
193   \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%
194

```

Text alignment is #3, and depends on artist or author:

```

195 %       #3%
196

```

#1 is empty or 'subgrp'

#2 is empty for artist, 'u' for author:

```

197   \footnotesize\textsc{%
198     \KFLT@optionalname{\csuse{KFLT@#1a#2p}}%
199     \KFLT@optionalname{\csuse{KFLT@#1a#2f}}%
200     \csuse{KFLT@#1a#2l}%
201     \csuse{KFLT@#1a#2s}%
202   }%
203 %       \end{minipage}%
204   \end{BlockClass}
205 %       \par\addvspace{2ex}%
206   }
207
208 }% tocdata not loaded

```

Env KFLT@marginfloat

[<offset>] {<type>}

```

209 \DeclareDocumentEnvironment{KFLT@marginfloat}{0{-1.2ex} m}
210 {%
211   \uselengthunit{PT}%
212   \LWR@BlockClassWP%
213   {float:right; width:2in; margin:10pt}%

```

```

214     {}%
215     (note)%
216     {marginblock}%
217     \renewcommand*{\@capttype}{#2}%
218     \minipage{1.2\LWR@usersmarginparwidth}%
219     \setlength{\marginparwidth}{.95\LWR@usersmarginparwidth}%
220 }
221 {%
222     \endminipage%
223     \endLWR@BlockClassWP%
224 }

225 \DeclareDocumentEnvironment{marginfigure}{o}
226   {\begin{KFLT@marginfloat}{figure}}
227   {\end{KFLT@marginfloat}}
228
229 \DeclareDocumentEnvironment{margintable}{o}
230   {\begin{KFLT@marginfloat}{table}}
231   {\end{KFLT@marginfloat}}

```

Env keywrap

```

    {\langle width \rangle} {\langle keyfloat \rangle}

232 \DeclareDocumentEnvironment{keywrap}{m +m}
233 {%
234     \begin{LWR@setvirtualpage}*
235     \setlength{\LWR@templengthone}{#1}%
236     \begin{LWR@BlockClassWP}%
237         {%
238             float:right; width:\LWR@printlength{\LWR@templengthone}; % extra space
239             margin:10pt%
240         }%
241     }%
242     (note)%
243     {marginblock}%
244     \setlength{\linewidth}{.95\LWR@templengthone}%
245     \booltrue{KFLT@keywrap}%
246     #2%
247     \end{LWR@BlockClassWP}%
248     \end{LWR@setvirtualpage}%
249 }
250 {}

251 }% AtBeginDocument

```

File 239 **lwarp-keystroke.sty**

§ 348 Package **keystroke**

(Emulates or patches code by WERNER FINK.)

Pkg keystroke

keystroke is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{keystroke}[2010/04/23]

2 \newcommand*{\LWR@HTML@keystroke}[1]{
3   \InlineClass{keystroke}{#1}

```

```

4 }
5 \LWR@formatted{keystroke}
6
7
8 \newcommand*\LWR@HTML@Return{\keystroke{\HTMLUnicode{021A9}}}
9 \LWR@formatted{Return}
10
11 \newcommand*\LWR@HTML@BSpace{\keystroke{\HTMLUnicode{027FB}}}
12 \LWR@formatted{BSpace}
13
14 \newcommand*\LWR@HTML@Tab{\keystroke{| \HTMLUnicode{021C6}|}}
15 \LWR@formatted{Tab}
16
17 \newcommand*\LWR@HTML@UArrow{\keystroke{\HTMLUnicode{02191}}}
18 \LWR@formatted{UArrow}
19
20 \newcommand*\LWR@HTML@DArrow{\keystroke{\HTMLUnicode{02193}}}
21 \LWR@formatted{DArrow}
22
23 \newcommand*\LWR@HTML@LArrow{\keystroke{\HTMLUnicode{02190}}}
24 \LWR@formatted{LArrow}
25
26 \newcommand*\LWR@HTML@RArrow{\keystroke{\HTMLUnicode{02192}}}
27 \LWR@formatted{RArrow}
28
29 % Preserves the language options:
30 \LetLtxMacro\LWR@HTML@Shift\Shift
31 \xpatchcmd{\LWR@HTML@Shift}
32   {\$ \uparrow$}
33   {\HTMLUnicode{21D1}}
34   {}
35   {}
36 \LWR@formatted{Shift}
37
38 \LetLtxMacro\LWR@HTML@PgUp\PgUp
39 \xpatchcmd{\LWR@HTML@PgUp}
40   {\$ \uparrow$}
41   {\HTMLUnicode{2191}}
42   {}
43   {}
44 \LWR@formatted{PgUp}
45
46 \LetLtxMacro\LWR@HTML@PgDown\PgDown
47 \xpatchcmd{\LWR@HTML@PgDown}
48   {\$ \downarrow$}
49   {\HTMLUnicode{2193}}
50   {}
51   {}
52 \LWR@formatted{PgDown}

```

File 240 **lwarp-kpfonts.sty**

§ 349 Package **kpfonts**

(Emulates or patches code by CHRISTOPHE CAIGNAERT.)

Pkg kpfonts

kpfonts is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation honors the options `uprightRoman` for `\D` only, `classicReIm`, `frenchstyle` for Greek only, `upright` for Greek only, `uprightgreeks`, `slantedGreeks`, and `mathcalasscript`.

The dedicated macros for Greek work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```

1 \LWR@ProvidesPackagePass{kpfonts}[2010/08/20]
2
3 \LWR@infoprocessingmathjax{kpfonts}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-newpctxmath}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 \ifkp@calasscr
12   \CustomizeMathJax{\let\LWRorigmathscr\mathscr}
13   \CustomizeMathJax{\let\LWRorigmathcal\mathcal}
14   \CustomizeMathJax{\let\mathscr\LWRorigmathcal}
15   \CustomizeMathJax{\let\mathcal\LWRorigmathscr}
16 \fi
17
18 \ifkp@upgrk % lowercase
19   \LWR@mathjax@addgreek@l@up*{}{}
20   \LWR@mathjax@addgreek@l@it{other}{}
21 \else
22   \LWR@mathjax@addgreek@l@up{other}{}
23 \fi
24
25 \ifkp@slGrk
26   \LWR@mathjax@addgreek@u@it*{}{}
27   \LWR@mathjax@addgreek@u@up*{other}{}
28   \LWR@mathjax@addgreek@u@up*{var}{}
29 \else
30   \LWR@mathjax@addgreek@u@it*{other}{}
31   \LWR@mathjax@addgreek@u@it*{var}{}
32 \fi
33
34 \LWR@mathjax@addgreek@u@up*{}{up}
35 \LWR@mathjax@addgreek@l@up*{}{up}
36
37 \LWR@mathjax@addgreek@u@it*{}{sl}
38 \LWR@mathjax@addgreek@l@it*{}{sl}
39
40 \CustomizeMathJax{\newcommand{\partialsl}{\mathord{\unicode{x1D715}}}}
41 \CustomizeMathJax{\let\partialup\uppartial}% not upright
42
43 \ifkp@oldReIm
44 \else
45   \CustomizeMathJax{\renewcommand{\Re}{\mathfrak{Re}}}
46   \CustomizeMathJax{\renewcommand{\Im}{\mathfrak{Im}}}
47 \fi
48
49 \ifkp@Dcommand
50   \ifkp@upRm%
51     \CustomizeMathJax{
52       \def\D#1{\mathclose{\, \mathrm{d}}#1}

```

```

53     }
54   \else
55     \CustomizeMathJax{
56       \def\D#1{\mathclose{\,\mathit{d}}#1}
57     }
58   \fi
59 \fi
60
61 \CustomizeMathJax{\let\pounds\mathsterling}
62 \CustomizeMathJax{\let\kppounds\mathsterling}
63
64 \CustomizeMathJax{\newcommand{\mathup}[1]{\mathrm{#1}}}% never sans
65 \CustomizeMathJax{\let\mathupright\mathup}
66
67 \end{warpMathJax}

```

File 241 **lwarp-kpfonts-otf.sty**

§ 350 Package **kpfonts-otf**

(Emulates or patches code by DANIEL FLIPO.)

Pkg kpfonts-otf

kpfonts-otf is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation honors the options fancyReIm, mathcal, frenchstyle for Greek only, and mathcalasscript.

Also see the options for unicode-math, which is loaded by kpfonts-otf.

The unicode-math dedicated macros for Greek work correctly.

 **\mathversion** The MATHJAX emulation does not change with the use of \mathversion. Whatever emulation is established at the begin of the document will remain.

SVG math should appear the same as the printed output.

for HTML output:

```

1 \LWR@ProvidesPackagePass{kpfonts-otf}[2020/06/20]
2
3 \LWR@infoprocessingmathjax{kpfonts-otf}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-nonunicode}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 \ifkp@calasscr
12   \CustomizeMathJax{\let\mathscr\mathcal}
13 \else
14   \CustomizeMathJax{\let\mathcal\mathscr}
15 \fi
16
17 \ifkp@frenchstyle
18   \LWR@mathjax@addgreek@l@up{}{}
19   \LWR@mathjax@addgreek@u@up*{}{}
20 \fi
21
22 \ifkp@oldReIm

```

```
23 \CustomizeMathJax{\renewcommand{\Re}{\mathfrak{Re}}}
24 \CustomizeMathJax{\renewcommand{\Im}{\mathfrak{Im}}}
25 \else
26 \fi
27
28 \ifkp@Dcommand
29 \CustomizeMathJax{
30   \def\D#1{\mathclose{\, \mathrm{d}}#1}
31 }
32 \fi
33
34 \CustomizeMathJax{\let\varint\int}
35 \CustomizeMathJax{\let\variint\iint}
36 \CustomizeMathJax{\let\variiint\iiint}
37 \CustomizeMathJax{\let\variiiint\iiiint}
38 \CustomizeMathJax{\let\varidotsint\idotsint}
39
40 \CustomizeMathJax{\newcommand{\varointctrlockwise}{%
41   \mathop{\unicode{x2939}}\!\!\!\unicode{x0222E}}%
42 }}
43
44 \CustomizeMathJax{\newcommand{\oiintclockwise}{%
45   \mathop{\unicode{x0222F}}\!\!\!\unicode{x2938}}%
46 }}
47
48 \CustomizeMathJax{\newcommand{\oiintctrlockwise}{%
49   \mathop{\unicode{x2939}}\!\!\!\unicode{x0222F}}%
50 }}
51
52 \CustomizeMathJax{\newcommand{\varoiintclockwise}{%
53   \mathop{\unicode{x0222F}}\!\!\!\unicode{x2938}}%
54 }}
55
56 \CustomizeMathJax{\newcommand{\varoiintctrlockwise}{%
57   \mathop{\unicode{x2939}}\!\!\!\unicode{x0222F}}%
58 }}
59
60 \CustomizeMathJax{\newcommand{\oiintclockwise}{%
61   \mathop{\unicode{x02230}}\!\!\!\unicode{x2938}}%
62 }}
63
64 \CustomizeMathJax{\newcommand{\oiintctrlockwise}{%
65   \mathop{\unicode{x2939}}\!\!\!\unicode{x02230}}%
66 }}
67
68 \CustomizeMathJax{\newcommand{\varoiintclockwise}{%
69   \mathop{\unicode{x02230}}\!\!\!\unicode{x2938}}%
70 }}
71
72 \CustomizeMathJax{\newcommand{\varoiintctrlockwise}{%
73   \mathop{\unicode{x2939}}\!\!\!\unicode{x02230}}%
74 }}
75
76 \CustomizeMathJax{\newcommand{\sqiint}{%
77   \mathop{\unicode{x2A16}}\!\!\!\unicode{x2A16}}%
78 }}
79
80 \CustomizeMathJax{\newcommand{\sqiint}{%
81   \mathop{\unicode{x2A16}}\!\!\!\unicode{x2A16}}\!\!\!\unicode{x2A16}}%
82 }}
```

```

83
84 \CustomizeMathJax{\let\widearc\overparen}
85 \CustomizeMathJax{\let\widearcarrow\overrightarrow}
86 \CustomizeMathJax{\let\overrightarc\overrightarrow}
87
88 \end{warpMathJax}

```

File 242 **lwarp-layaureo.sty**

§ 351 Package **layaureo**

Pkg layaureo layaureo is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{layaureo}[2004/09/16]

File 243 **lwarp-layout.sty**

§ 352 Package **layout**

Pkg layout layout is ignored.

for HTML output: Discard all options for lwarp-layout:

```
1 \LWR@ProvidesPackageDrop{layout}[2014/10/28]
```

```
2 \NewDocumentCommand{\layout}{s}{}

```

File 244 **lwarp-layouts.sty**

§ 353 Package **layouts**

Pkg layouts layouts is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{layouts}[2009/09/02]

```

2 \newif\ifoddpagelayout
3 \oddpagelayouttrue
4 \newif\iftwocolumnlayout
5 \twocolumnlayoutfalse
6 \newif\ifdrawmarginpars
7 \drawmarginparstrue
8 \newif\ifdrawparameters
9 \drawparameterstrue
10 \newif\iflistaspara
11 \listasparatrue
12 \newif\ifruninhead
13 \runinheadfalse
14 \newif\ifprintparameters
15 \printparameterstrue
16 \newif\ifdrawdimensions
17 \drawdimensionsfalse

```

```
18 \newif\ifprintheadings
19 \printheadingstrue
20 \newcommand{\testdrawdimensions}{}
21 \newcommand{\testprintparameters}{}
22 \newcommand{\setlabelfont}[1]{}
23 \newcommand{\setparameterfont}[1]{}
24 \newcommand{\setvaluetextsize}[1]{}
25 \newcommand{\setlayoutscale}[1]{}
26 \newcommand{\setuplayouts}{}
27 \newcommand{\printinunitsof}[1]{}
28 \newcommand{\prntlen}[1]{}
29 \newcommand{\trypaperwidth}[1]{}
30 \newcommand{\trypaperheight}[1]{}
31 \newcommand{\tryoffset}[1]{}
32 \newcommand{\tryvoffset}[1]{}
33 \newcommand{\trytopmargin}[1]{}
34 \newcommand{\tryheadheight}[1]{}
35 \newcommand{\tryheadsep}[1]{}
36 \newcommand{\trytextheight}[1]{}
37 \newcommand{\tryfootskip}[1]{}
38 \newcommand{\tryoddsidemargin}[1]{}
39 \newcommand{\tryevensidemargin}[1]{}
40 \newcommand{\trytextwidth}[1]{}
41 \newcommand{\trymarginparsep}[1]{}
42 \newcommand{\trymarginparwidth}[1]{}
43 \newcommand{\trymarginparpush}[1]{}
44 \newcommand{\trycolumnsep}[1]{}
45 \newcommand{\trycolumnseprule}[1]{}
46 \newcommand{\setfootbox}[2]{}
47 \newcommand{\currentpage}{}
48 \newcommand{\drawpage}{(draw page)}
49 \newcommand{\pagediagram}{(page diagram)}
50 \newcommand{\pagedesign}{(page design)}
51 \newcommand{\pagevalues}{(page values)}
52 \newcommand{\trystockwidth}[1]{}
53 \newcommand{\trystockheight}[1]{}
54 \newcommand{\trytrimedge}[1]{}
55 \newcommand{\trytrimtop}[1]{}
56 \newcommand{\tryuppermargin}[1]{}
57 \newcommand{\tryspinemargin}[1]{}
58 \newcommand{\currentstock}{}
59 \newcommand{\drawstock}{(draw stock)}
60 \newcommand{\stockdiagram}{(stock diagram)}
61 \newcommand{\stockdesign}{(stock design)}
62 \newcommand{\stockvalues}{(stock values)}
63 \newcommand{\tryitemindent}[1]{}
64 \newcommand{\trylabelwidth}[1]{}
65 \newcommand{\trylabelsep}[1]{}
66 \newcommand{\tryleftmargin}[1]{}
67 \newcommand{\tryrightmargin}[1]{}
68 \newcommand{\trylistparindent}[1]{}
69 \newcommand{\trytopsep}[1]{}
70 \newcommand{\tryparskip}[1]{}
71 \newcommand{\tryparttopsep}[1]{}
72 \newcommand{\tryparsep}[1]{}
73 \newcommand{\tryitemsep}[1]{}
74 \newcommand{\currentlist}{}
75 \newcommand{\drawlist}{(draw list)}
76 \newcommand{\listdiagram}{(list diagram)}
77 \newcommand{\listdesign}{(list design)}
```

```
78 \newcommand{\listvalues}{(list values)}
79 \newcommand{\tryfootins}[1]{}
80 \newcommand{\tryfootnotesep}[1]{}
81 \newcommand{\tryfootnotebaseline}[1]{}
82 \newcommand{\tryfootruleheight}[1]{}
83 \newcommand{\tryfootrulefrac}[1]{}
84 \newcommand{\currentfootnote}{}
85 \newcommand{\drawfootnote}{(draw footnote)}
86 \newcommand{\footnotediagram}{(footnote diagram)}
87 \newcommand{\footnotedesign}{(footnote design)}
88 \newcommand{\footnotevalues}{(footnote values)}
89 \newcommand{\tryparindent}[1]{}
90 \newcommand{\tryparlinewidth}[1]{}
91 \newcommand{\tryparbaselineskip}[1]{}
92 \newcommand{\currentparagraph}{}
93 \newcommand{\drawparagraph}{(draw paragraph)}
94 \newcommand{\paragraphdiagram}{(paragraph diagram)}
95 \newcommand{\paragraphdesign}{(paragraph design)}
96 \newcommand{\paragraphvalues}{(paragraph values)}
97 \newcommand{\trybeforeskip}[1]{}
98 \newcommand{\tryafterskip}[1]{}
99 \newcommand{\tryindent}[1]{}
100 \newcommand{\currentheading}{}
101 \newcommand{\drawheading}[1]{(draw heading)}
102 \newcommand{\headingdiagram}[1]{(heading diagram)}
103 \newcommand{\headingdesign}[1]{(heading design)}
104 \newcommand{\headingvalues}{(heading values)}
105 \newcommand{\trytextfloatsep}[1]{}
106 \newcommand{\tryfloatsep}[1]{}
107 \newcommand{\tryintextsep}[1]{}
108 \newcommand{\trytopfigrule}[1]{}
109 \newcommand{\trybotfigrule}[1]{}
110 \newcommand{\currentfloat}{}
111 \newcommand{\drawfloat}{(draw float)}
112 \newcommand{\floatdiagram}{(float diagram)}
113 \newcommand{\floatdesign}{(float design)}
114 \newcommand{\floatvalues}{(float values)}
115 \newcommand{\trytotalnumber}[1]{}
116 \newcommand{\trytopnumber}[1]{}
117 \newcommand{\trybottomnumber}[1]{}
118 \newcommand{\trytopfraction}[1]{}
119 \newcommand{\trytextfraction}[1]{}
120 \newcommand{\trybottomfraction}[1]{}
121 \newcommand{\currentfloatpage}{}
122 \newcommand{\drawfloatpage}{(draw floatpage)}
123 \newcommand{\floatpagediagram}{(floatpage diagram)}
124 \newcommand{\floatpagedesign}{(floatpage design)}
125 \newcommand{\floatpagevalues}{(floatpage values)}
126 \newcommand{\trytocindent}[1]{}
127 \newcommand{\trytocnumwidth}[1]{}
128 \newcommand{\trytoclinewidth}[1]{}
129 \newcommand{\trytocrmarg}[1]{}
130 \newcommand{\trytocpnumwidth}[1]{}
131 \newcommand{\trytocdotsep}[1]{}
132 \newcommand{\currenttoc}{}
133 \newcommand{\drawtoc}{(draw toc)}
134 \newcommand{\tocdiagram}{(toc diagram)}
135 \newcommand{\tocdesign}{(toc design)}
136 \newcommand{\tocvalues}{(toc values)}
137 \newcommand{\drawaspread}[8][0]{(a spread)}
```

```
138 \newcommand{\drawfontframe}[1]{(font frame)}
139 \newcommand{\drawfontframeLabel}[1]{}
```

File 245 **lwarp-leading.sty**

§ 354 Package **leading**

Pkg leading

leading is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{leading}[2008/12/11]
2 \newcommand\leading[1]{}
```

File 246 **lwarp-leftidx.sty**

§ 355 Package **leftidx**

Pkg leftidx

(Emulates or patches code by HARALD HARDERS.)

leftidx works as-is with SVG math, and is emulated for MATHJAX.

for HTML output:

```
1 \LWR@ProvidesPackagePass{leftidx}[2003/09/24]
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\leftidx}[3]{\vphantom{#2}}#1#2#3}
4 \CustomizeMathJax{\newcommand{\ltrans}[1]{\leftidx{^\mathrm{t}}{!\#1}}}
5 \end{warpMathJax}
```

File 247 **lwarp-letterspace.sty**

§ 356 Package **letterspace**

Pkg letterspace

(Emulates or patches code by R SCHLICHT.)

letterspace is a subset of microtype, which is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output: Discard all options for lwarp-letterspace:

```
1 \LWR@ProvidesPackageDrop{letterspace}[2018/01/14]
2 \newcommand*\lsstyle{}
3 \newcommand\textls[2][1]{}
4 \def\textls#1#{}
5 \newcommand*\lslig[1]{#1}
```

File 248 **lwarp-lettrine.sty**

§ 357 Package **lettrine**

(Emulates or patches code by DANIEL FLIPO.)

Pkg Lettrine

lettrine is emulated.

for HTML output: Discard all options for lwarp-lettrine:

```
1 \LWR@ProvidesPackageDrop{lettrine}[2018-08-28]
```

The initial letter is in a `` of class `lettrine`, and the following text is in a `` of class `lettrinertext`. `\lettrine [keys] {letter} {additional text}`

```
2 \DeclareDocumentCommand{\lettrine}{o m m}{%
3   \InlineClass{lettrine}{#2}\InlineClass{lettrinertext}{#3} % extra space
4 }
5
6 \newcounter{DefaultLines}
7 \setcounter{DefaultLines}{2}
8 \newcounter{DefaultDepth}
9 \newcommand*\DefaultOptionsFile{\relax}
10 \newcommand*\DefaultLoversize{0}
11 \newcommand*\DefaultLraise{0}
12 \newcommand*\DefaultLhang{0}
13 \newdimen\DefaultFindent
14 \setlength{\DefaultFindent}{\z@}
15 \newdimen\DefaultNindent
16 \setlength{\DefaultNindent}{0.5em}
17 \newdimen\DefaultSlope
18 \setlength{\DefaultSlope}{\z@}
19 \newdimen\DiscardVskip
20 \setlength{\DiscardVskip}{0.2\p@}
21 \newif\ifLettrineImage
22 \newif\ifLettrineOnGrid
23 \newif\ifLettrineRealHeight
24
25 \newcommand*\LettrineTextFont{\scshape}
26 \newcommand*\LettrineFontHook{}
27 \newcommand*\LettrineFont[1]{\InlineClass{lettrine}{#1}}
28 \newcommand*\LettrineFontEPS[1]{\includegraphics[height=1.5ex]{#1}}
```

File 249 **lwarp-libertinust1math.sty**§ 358 Package **libertinust1math***(Emulates or patches code by MICHAEL SHARPE.)*

Pkg Libertinust1math

libertinust1math is used as-is for SVG math, and is emulated for MATHJAX.

The MATHJAX emulation honors frenchmath for Greek but not Latin characters, and slantedGreek, uprightGreek, and ISO also adjust Greek characters. MATHJAX cannot yet honor options for adjusting Latin characters.

The dedicated macros for upright and italic Greek letters do work correctly.

Some of the symbol font macros such as `\mathsfbf` do not use a sans font because MATHJAX does not yet have sans Greek.

SVG math honors all font choices, and should appear the same as the printed output.

for HTML output:

```

1 \LWR@ProvidesPackagePass{libertinust1math}[2020/06/10]
2
3 \LWR@infoprocessingmathjax{libertinust1math}

4 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
5
6 \begin{warpMathJax}
7
8 \iflibus@slantedG
9   \LWR@mathjax@addgreek@u@it*{}{}
10 \else
11   \LWR@mathjax@addgreek@u@up*{}{}
12 \fi
13
14 \LWR@mathjax@addgreek@u@it*{}{it}
15 \LWR@mathjax@addgreek@u@up*{}{up}
16 \LWR@mathjax@addgreek@u@up*{}{up}
17
18 \iflibus@frenchm
19   \LWR@mathjax@addgreek@l@up{}{}
20 \else
21   \LWR@mathjax@addgreek@l@it{}{}
22 \fi
23
24 \LWR@mathjax@addgreek@l@it{}{it}
25 \LWR@mathjax@addgreek@l@up{}{up}
26 \LWR@mathjax@addgreek@l@up{}{up}
27
28 \CustomizeMathJax{\let\upartial\partial}% not upright

29 \CustomizeMathJax{\let\mathsfbf\mathbf}% not sans
30 \CustomizeMathJax{\newcommand{\mathsfbf}[1]{%
31 %   \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}% not greek
32 % }}% not sans
33
34 % \CustomizeMathJax{\newcommand{\mathbfit}[1]{\boldsymbol{#1}}}
35 \CustomizeMathJax{\let\mathbfit\boldsymbol}

36 % \CustomizeMathJax{\newcommand{\mathsfbfit}[1]{\boldsymbol{#1}}}% not sans
37 \CustomizeMathJax{\let\mathsfbfit\mathbfit}% not sans
38 % \CustomizeMathJax{\newcommand{\mathsfbfit}[1]{%
39 %   \mmlToken{mi}[mathvariant="sans-serif-bold-italic"]{#1}% not greek
40 % }}%

41 \CustomizeMathJax{\let\mathsfit\mathit}% not sans
42 % \CustomizeMathJax{\newcommand{\mathsfit}[1]{%
43 %   \mmlToken{mi}[mathvariant="sans-serif-italic"]{#1}% not greek
44 % }}
45
46 \CustomizeMathJax{\let\vectorsym\mathbfit}
47 \CustomizeMathJax{\let\matrixsym\mathbfit}
48 \CustomizeMathJax{\let\tensorsym\mathsfbfit}
49 \CustomizeMathJax{\let\mathboldsans\mathsfbfit}
50 \CustomizeMathJax{\let\mathbold\mathbfit}

```

lwarp_mathjax.txt adds \left/\right support for delimiters.

```

51 \CustomizeMathJax{\let\dlb\lBrack}
52 \CustomizeMathJax{\let\drb\rBrack}
53
54 \CustomizeMathJax{\let\sqrtsign\sqrt}
55
56 \CustomizeMathJax{\let\smallintsl\smallint}
57 \CustomizeMathJax{\newcommand{\smalliintsl}{\mathop{\unicode{x222C}}\limits}}
58 \CustomizeMathJax{\newcommand{\smalliiintsl}{\mathop{\unicode{x222D}}\limits}}
59 \CustomizeMathJax{\newcommand{\smalliiintsl}{\mathop{\unicode{x2A0C}}\limits}}
60 \CustomizeMathJax{\newcommand{\smalllointsl}{\mathop{\unicode{x222E}}\limits}}
61 \CustomizeMathJax{\newcommand{\smalllointsl}{\mathop{\unicode{x222F}}\limits}}
62
63 \CustomizeMathJax{\let\smallintup\smallint}
64 \CustomizeMathJax{\newcommand{\smalliintup}{\mathop{\unicode{x222C}}\limits}}
65 \CustomizeMathJax{\newcommand{\smalliiintup}{\mathop{\unicode{x222D}}\limits}}
66 \CustomizeMathJax{\newcommand{\smalliiintup}{\mathop{\unicode{x2A0C}}\limits}}
67 \CustomizeMathJax{\newcommand{\smalllointup}{\mathop{\unicode{x222E}}\limits}}
68 \CustomizeMathJax{\newcommand{\smalllointup}{\mathop{\unicode{x222F}}\limits}}
69
70 \CustomizeMathJax{\let\intsl\int}
71 \CustomizeMathJax{\newcommand{\iintsl}{\mathop{\unicode{x222C}}\limits}}
72 \CustomizeMathJax{\newcommand{\iiintsl}{\mathop{\unicode{x222D}}\limits}}
73 \CustomizeMathJax{\newcommand{\iiintsl}{\mathop{\unicode{x2A0C}}\limits}}
74 \CustomizeMathJax{\let\ointsl\oint}
75 \CustomizeMathJax{\newcommand{\oiintsl}{\mathop{\unicode{x222F}}\limits}}
76 \CustomizeMathJax{\newcommand{\oiiintsl}{\mathop{\unicode{x2230}}\limits}}
77
78 \CustomizeMathJax{\let\intup\int}
79 \CustomizeMathJax{\newcommand{\iintup}{\mathop{\unicode{x222C}}\limits}}
80 \CustomizeMathJax{\newcommand{\iiintup}{\mathop{\unicode{x222D}}\limits}}
81 \CustomizeMathJax{\newcommand{\iiintup}{\mathop{\unicode{x2A0C}}\limits}}
82 \CustomizeMathJax{\let\ointup\oint}
83 \CustomizeMathJax{\newcommand{\oiintup}{\mathop{\unicode{x222F}}\limits}}
84 \CustomizeMathJax{\newcommand{\oiiintup}{\mathop{\unicode{x2230}}\limits}}
85
86 \CustomizeMathJax{\newcommand{\smalliint}{\mathop{\unicode{x222C}}\limits}}
87 \CustomizeMathJax{\newcommand{\smalliiint}{\mathop{\unicode{x222D}}\limits}}
88 \CustomizeMathJax{\newcommand{\smalliiint}{\mathop{\unicode{x2A0C}}\limits}}
89 \CustomizeMathJax{\newcommand{\smallloint}{\mathop{\unicode{x222E}}\limits}}
90 \CustomizeMathJax{\newcommand{\smallloint}{\mathop{\unicode{x222F}}\limits}}
91
92 \CustomizeMathJax{\let\int\int}
93 \CustomizeMathJax{\newcommand{\iint}{\mathop{\unicode{x222C}}\limits}}
94 \CustomizeMathJax{\newcommand{\iiint}{\mathop{\unicode{x222D}}\limits}}
95 \CustomizeMathJax{\newcommand{\iiint}{\mathop{\unicode{x2A0C}}\limits}}
96 \CustomizeMathJax{\let\oint\oint}
97 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
98 \CustomizeMathJax{\newcommand{\oiiint}{\mathop{\unicode{x2230}}\limits}}
99
100 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
101
102 \CustomizeMathJax{\newcommand{\bigcupdot}{\mathop{\unicode{x2A03}}}}
103 \CustomizeMathJax{\newcommand{\bigsqcap}{\mathop{\unicode{x2A05}}}}
104 \CustomizeMathJax{\newcommand{\xsol}{\mathop{\unicode{x29F8}}}}
105 \CustomizeMathJax{\newcommand{\xbsol}{\mathop{\unicode{x29F9}}}}
106 \CustomizeMathJax{\let\prodop\prod}
107 \CustomizeMathJax{\let\coprodop\coprod}
108 \CustomizeMathJax{\let\sumop\sum}
109 \CustomizeMathJax{\let\bigwedgeop\bigwedge}
110 \CustomizeMathJax{\let\bigveeop\bigvee}

```

```

111 \CustomizeMathJax{\let\bigcapop\bigcap}
112 \CustomizeMathJax{\let\bigcupop\bigcup}
113 \CustomizeMathJax{\let\xsolop\xsol}
114 \CustomizeMathJax{\let\xbsolop\xbsol}
115 \CustomizeMathJax{\let\bigodotop\bigodot}
116 \CustomizeMathJax{\let\bigoplusop\bigoplus}
117 \CustomizeMathJax{\let\bigotimesop\bigotimes}
118 \CustomizeMathJax{\let\bigcupdotop\bigcupdot}
119 \CustomizeMathJax{\let\biguplusop\biguplus}
120 \CustomizeMathJax{\let\bigsqcapop\bigsqcap}
121 \CustomizeMathJax{\let\bigsqcupop\bigsqcup}
122
123 \CustomizeMathJax{\newcommand{\ovhook}[1]{\mathord{#1\unicode{x00309}}}}
124 \CustomizeMathJax{\newcommand{\candra}[1]{\mathord{#1\unicode{x00310}}}}
125 \CustomizeMathJax{\newcommand{\oturnedcomma}[1]{\mathord{#1\unicode{x00312}}}}
126 \CustomizeMathJax{\newcommand{\ocommatopright}[1]{\mathord{#1\unicode{x00315}}}}
127 \CustomizeMathJax{\newcommand{\droang}[1]{\mathord{#1\unicode{x0031A}}}}
128 \CustomizeMathJax{\newcommand{\leftharpoonaccent}[1]{\mathord{#1\unicode{x020D0}}}}
129 \CustomizeMathJax{\newcommand{\rightharpoonaccent}[1]{\mathord{#1\unicode{x020D1}}}}
130 \CustomizeMathJax{\newcommand{\leftarrowaccent}[1]{\mathord{#1\unicode{x020D0}}}}
131 \CustomizeMathJax{\let\rightarrowaccent\vec}
132
133 \CustomizeMathJax{\newcommand{\leftrightarrowaccent}[1]{\mathord{#1\unicode{x020E1}}}}
134 \CustomizeMathJax{\newcommand{\annuity}[1]{\mathord{#1\unicode{x020E7}}}}
135 \CustomizeMathJax{\newcommand{\widebridgeabove}[1]{\mathord{#1\unicode{x020E9}}}}
136 \CustomizeMathJax{\newcommand{\asteraccent}[1]{\mathord{#1\unicode{x020F0}}}}
137
138 % neutralized:
139 \CustomizeMathJax{\newcommand{\bracedl}{}}
140 \CustomizeMathJax{\newcommand{\bracerd}{}}
141 \CustomizeMathJax{\newcommand{\bracelu}{}}
142 \CustomizeMathJax{\newcommand{\braceru}{}}
143 \CustomizeMathJax{\newcommand{\braceex}{}}
144 \CustomizeMathJax{\newcommand{\bracemu}{}}
145 \CustomizeMathJax{\newcommand{\bracemd}{}}
146 \CustomizeMathJax{\newcommand{\parenld}{}}
147 \CustomizeMathJax{\newcommand{\parenrd}{}}
148 \CustomizeMathJax{\newcommand{\parenlu}{}}
149 \CustomizeMathJax{\newcommand{\parenru}{}}
150 \CustomizeMathJax{\newcommand{\bracketld}{}}
151 \CustomizeMathJax{\newcommand{\bracketrd}{}}
152 \CustomizeMathJax{\newcommand{\bracketlu}{}}
153 \CustomizeMathJax{\newcommand{\bracketru}{}}
154 \CustomizeMathJax{\newcommand{\bracketex}{}}
155 \CustomizeMathJax{\newcommand{\parenex}{}}
156
157 \CustomizeMathJax{\newcommand{\lhook}{~}}
158 \CustomizeMathJax{\newcommand{\rhook}{~}}
159 \CustomizeMathJax{\newcommand{\relbar}{-}}
160 \CustomizeMathJax{\newcommand{\Relbar}{=}}
161
162 \CustomizeMathJax{\newcommand{\mapstochar}{\mathrel{\unicode{x21A6}}}}
163
164 \CustomizeMathJax{\newcommand{\Zbar}{\mathord{\unicode{x0001B5}}}}
165 \CustomizeMathJax{\newcommand{\notchar}{\mathrel{\unicode{x000AC}}}}
166 \CustomizeMathJax{\newcommand{\upbackepsilon}{\mathord{\unicode{x03F6}}}}
167 \CustomizeMathJax{\newcommand{\smlkcircle}{\mathbin{\unicode{x02022}}}}
168 \CustomizeMathJax{\newcommand{\enleaderwtdots}{\mathord{\unicode{x02025}}}}
169 \CustomizeMathJax{\newcommand{\unicodeellipsis}{\mathord{\unicode{x02026}}}}
170 \CustomizeMathJax{\newcommand{\matheellipsis}{\mathinner{\unicode{x02026}}}}

```

```

171 \CustomizeMathJax{\newcommand{\dprime}{\mathord{\unicode{x02033}}}}
172 \CustomizeMathJax{\newcommand{\trprime}{\mathord{\unicode{x02034}}}}
173 \CustomizeMathJax{\newcommand{\backdprime}{\mathord{\unicode{x02036}}}}
174 \CustomizeMathJax{\newcommand{\backtrprime}{\mathord{\unicode{x02037}}}}
175 \CustomizeMathJax{\newcommand{\caretinsert}{\mathord{\unicode{x02038}}}}
176 \CustomizeMathJax{\newcommand{\Exclam}{\mathord{\unicode{x0203C}}}}
177
178 \CustomizeMathJax{\newcommand{\hyphenbullet}{\mathord{\unicode{x02043}}}}
179 \CustomizeMathJax{\newcommand{\fracslash}{\mathbin{\unicode{x02044}}}}
180 \CustomizeMathJax{\newcommand{\Question}{\mathord{\unicode{x02047}}}}
181 \CustomizeMathJax{\newcommand{\closure}{\mathrel{\unicode{x02050}}}}
182 \CustomizeMathJax{\newcommand{\qprime}{\mathord{\unicode{x02057}}}}
183 \CustomizeMathJax{\newcommand{\vertoverlay}{\mathrel{\unicode{x020D2}}}}
184 \CustomizeMathJax{\newcommand{\enclosecircle}{\mathord{\unicode{x020DD}}}}
185 \CustomizeMathJax{\newcommand{\enclosesquare}{\mathord{\unicode{x020DE}}}}
186 \CustomizeMathJax{\newcommand{\enclosetriangle}{\mathord{\unicode{x020E4}}}}
187 \CustomizeMathJax{\newcommand{\Eulerconst}{\mathord{\unicode{x02107}}}}
188 \CustomizeMathJax{\newcommand{\turnediota}{\mathord{\unicode{x02129}}}}
189 \CustomizeMathJax{\newcommand{\Angstrom}{\mathord{\unicode{x0212B}}}}
190
191 \CustomizeMathJax{\newcommand{\sansLturned}{\mathord{\unicode{x02142}}}}
192 \CustomizeMathJax{\newcommand{\sansLmirrored}{\mathord{\unicode{x02143}}}}
193 \CustomizeMathJax{\newcommand{\Yup}{\mathord{\unicode{x02144}}}}
194 \CustomizeMathJax{\newcommand{\upand}{\mathbin{\unicode{x0214B}}}}
195 \CustomizeMathJax{\newcommand{\increment}{\mathord{\unicode{x02206}}}}
196 \CustomizeMathJax{\newcommand{\smallin}{\mathrel{\unicode{x0220A}}}}
197 \CustomizeMathJax{\newcommand{\nni}{\mathrel{\unicode{x0220C}}}}
198
199 \CustomizeMathJax{\newcommand{\smallni}{\mathrel{\unicode{x0220D}}}}
200 \CustomizeMathJax{\newcommand{\QED}{\mathord{\unicode{x0220E}}}}
201 \CustomizeMathJax{\newcommand{\vysmwhtcircle}{\mathbin{\unicode{x02218}}}}
202 \CustomizeMathJax{\newcommand{\vysmblkcircle}{\mathbin{\unicode{x02219}}}}
203 \CustomizeMathJax{\newcommand{\rightangle}{\mathord{\unicode{x0221F}}}}
204
205 \CustomizeMathJax{\newcommand{\Colon}{\mathrel{\unicode{x02237}}}}
206 \CustomizeMathJax{\newcommand{\dotminus}{\mathbin{\unicode{x02238}}}}
207 \CustomizeMathJax{\newcommand{\dashcolon}{\mathrel{\unicode{x02239}}}}
208 \CustomizeMathJax{\newcommand{\dotsminusdots}{\mathrel{\unicode{x0223A}}}}
209 \CustomizeMathJax{\newcommand{\kernelcontraction}{\mathrel{\unicode{x0223B}}}}
210 \CustomizeMathJax{\newcommand{\invlazys}{\mathbin{\unicode{x0223E}}}}
211
212 \CustomizeMathJax{\newcommand{\sinewave}{\mathord{\unicode{x0223F}}}}
213 \CustomizeMathJax{\newcommand{\nsime}{\mathrel{\unicode{x02244}}}}
214 \CustomizeMathJax{\newcommand{\simneqq}{\mathrel{\unicode{x02246}}}}
215 \CustomizeMathJax{\newcommand{\napprox}{\mathrel{\unicode{x02249}}}}
216 \CustomizeMathJax{\newcommand{\approxident}{\mathrel{\unicode{x0224B}}}}
217 \CustomizeMathJax{\newcommand{\backcong}{\mathrel{\unicode{x0224C}}}}
218
219 \CustomizeMathJax{\newcommand{\nasymp}{\mathrel{\unicode{x0226D}}}}
220 \CustomizeMathJax{\newcommand{\nlesssim}{\mathrel{\unicode{x02274}}}}
221 \CustomizeMathJax{\newcommand{\ngtrsim}{\mathrel{\unicode{x02275}}}}
222 \CustomizeMathJax{\newcommand{\nlessgtr}{\mathrel{\unicode{x02278}}}}
223 \CustomizeMathJax{\newcommand{\ngtrless}{\mathrel{\unicode{x02279}}}}
224
225 \CustomizeMathJax{\newcommand{\nsubset}{\mathrel{\unicode{x02284}}}}
226 \CustomizeMathJax{\newcommand{\nsupset}{\mathrel{\unicode{x02285}}}}
227
228 \CustomizeMathJax{\newcommand{\cupleftarrow}{\mathbin{\unicode{x0228C}}}}
229 \CustomizeMathJax{\newcommand{\cupdot}{\mathbin{\unicode{x0228D}}}}
230 \CustomizeMathJax{\newcommand{\circledequal}{\mathbin{\unicode{x0229C}}}}

```

```

231
232 \CustomizeMathJax{\newcommand{\assert}{\mathrel{\unicode{x022A6}}}}
233 \CustomizeMathJax{\newcommand{\VDash}{\mathrel{\unicode{x022AB}}}}
234 \CustomizeMathJax{\newcommand{\prurel}{\mathrel{\unicode{x022B0}}}}
235
236 \CustomizeMathJax{\newcommand{\origof}{\mathrel{\unicode{x022B6}}}}
237 \CustomizeMathJax{\newcommand{\smallprod}{\mathop{\unicode{x0220F}}}}% not small
238 \CustomizeMathJax{\newcommand{\smallcoprod}{\mathop{\unicode{x02210}}}}% not small
239 \CustomizeMathJax{\newcommand{\smallsum}{\mathop{\unicode{x02211}}}}% not small
240 \CustomizeMathJax{\newcommand{\Hfraktur}{\mathord{\unicode{x1D525}}}}
241 \CustomizeMathJax{\newcommand{\dsol}{\mathbin{\unicode{x029F6}}}}
242 \CustomizeMathJax{\newcommand{\rso lbar}{\mathbin{\unicode{x029F7}}}}
243
244 \CustomizeMathJax{\newcommand{\eqless}{\mathrel{\unicode{x022DC}}}}
245 \CustomizeMathJax{\newcommand{\eqgtr}{\mathrel{\unicode{x022DD}}}}
246 \CustomizeMathJax{\newcommand{\npreccurlyeq}{\mathrel{\unicode{x022E0}}}}
247 \CustomizeMathJax{\newcommand{\nsucccurlyeq}{\mathrel{\unicode{x022E1}}}}
248 \CustomizeMathJax{\newcommand{\nqssubseteq}{\mathrel{\unicode{x022E2}}}}
249 \CustomizeMathJax{\newcommand{\nqsupseteq}{\mathrel{\unicode{x022E3}}}}
250 \CustomizeMathJax{\newcommand{\sqsubseteq}{\mathrel{\unicode{x022E4}}}}
251 \CustomizeMathJax{\newcommand{\sqsupseteq}{\mathrel{\unicode{x022E5}}}}
252 \CustomizeMathJax{\newcommand{\nvartriangleleft}{\mathrel{\unicode{x022EA}}}}
253 \CustomizeMathJax{\newcommand{\nvartriangleright}{\mathrel{\unicode{x022EB}}}}
254
255 \CustomizeMathJax{\newcommand{\vdotsmath}{\mathrel{\unicode{x022EE}}}}
256 \CustomizeMathJax{\newcommand{\unicodecdots}{\mathord{\unicode{x022EF}}}}
257 \CustomizeMathJax{\newcommand{\adots}{\mathrel{\unicode{x022F0}}}}
258 \CustomizeMathJax{\newcommand{\succneq}{\mathrel{\unicode{x02AB2}}}}
259 \CustomizeMathJax{\newcommand{\preceqq}{\mathrel{\unicode{x02AB3}}}}
260 \CustomizeMathJax{\newcommand{\succeqq}{\mathrel{\unicode{x02AB4}}}}
261 \CustomizeMathJax{\newcommand{\precneq}{\mathrel{\unicode{x02AB1}}}}
262
263 \CustomizeMathJax{\newcommand{\mapsfrom}{\mathrel{\unicode{x021A4}}}}
264
265 \CustomizeMathJax{\newcommand{\longmapsfrom}{\mathrel{\unicode{x027FB}}}}
266
267 \CustomizeMathJax{\newcommand{\diameter}{\mathord{\unicode{x02300}}}}
268 \CustomizeMathJax{\newcommand{\coloneq}{\mathrel{\unicode{x02254}}}}
269 \CustomizeMathJax{\newcommand{\eqcolon}{\mathrel{\unicode{x02255}}}}
270 \CustomizeMathJax{\newcommand{\arceq}{\mathrel{\unicode{x02258}}}}
271 \CustomizeMathJax{\newcommand{\wedg eq}{\mathrel{\unicode{x02259}}}}
272 \CustomizeMathJax{\newcommand{\veeeq}{\mathrel{\unicode{x0225A}}}}
273
274 \CustomizeMathJax{\newcommand{\stareq}{\mathrel{\unicode{x0225B}}}}
275 \CustomizeMathJax{\newcommand{\eqdef}{\mathrel{\unicode{x0225D}}}}
276 \CustomizeMathJax{\newcommand{\measeq}{\mathrel{\unicode{x0225E}}}}
277 \CustomizeMathJax{\newcommand{\questeq}{\mathrel{\unicode{x0225F}}}}
278 \CustomizeMathJax{\newcommand{\nequiv}{\mathrel{\unicode{x02262}}}}
279 \CustomizeMathJax{\newcommand{\Equip}{\mathrel{\unicode{x02263}}}}
280
281 \CustomizeMathJax{\newcommand{\house}{\mathord{\unicode{x02302}}}}
282
283 \CustomizeMathJax{\newcommand{\musicalnote}{\mathord{\unicode{x0266A}}}}
284 \CustomizeMathJax{\newcommand{\degree}{\mathord{\unicode{x000B0}}}}
285 \CustomizeMathJax{\newcommand{\mathsection}{\mathord{\unicode{x000A7}}}}
286 \CustomizeMathJax{\newcommand{\mathparagraph}{\mathord{\unicode{x000B6}}}}
287 \CustomizeMathJax{\newcommand{\checkmarkmath}{\mathord{\unicode{x02713}}}}
288 \CustomizeMathJax{\newcommand{\invnot}{\mathord{\unicode{x02310}}}}
289
290 \CustomizeMathJax{\newcommand{\mathvisiblespace}{\mathord{\unicode{x02423}}}}

```

```

291 \CustomizeMathJax{\newcommand{\mdlgblksquare}{\mathord{\unicode{x025A0}}}}
292 \CustomizeMathJax{\newcommand{\mdlgwhtsquare}{\mathord{\unicode{x025A1}}}}
293
294 \CustomizeMathJax{\newcommand{\bigblacktriangleup}{\mathord{\unicode{x025B2}}}}
295 \CustomizeMathJax{\newcommand{\varbigtriangleup}{\mathord{\unicode{x025B3}}}}
296
297 \CustomizeMathJax{\newcommand{\bigblacktriangledown}{\mathord{\unicode{x025BC}}}}
298 \CustomizeMathJax{\newcommand{\varbigtriangledown}{\mathord{\unicode{x025BD}}}}
299 \CustomizeMathJax{\newcommand{\Longmapsfrom}{\mathrel{\unicode{x027FD}}}}
300
301 % bug in print font:
302 \CustomizeMathJax{\newcommand{\mdlgblkdiamond}{\mathord{\unicode{x025C6}}}}
303
304 \CustomizeMathJax{\newcommand{\mdlgwhtdiamond}{\mathord{\unicode{x025C7}}}}
305 \CustomizeMathJax{\newcommand{\Longmapsto}{\mathrel{\unicode{x027FE}}}}
306 \CustomizeMathJax{\newcommand{\fisheye}{\mathord{\unicode{x025C9}}}}
307 \CustomizeMathJax{\newcommand{\mdlgwhtlozenge}{\mathord{\unicode{x025CA}}}}
308 \CustomizeMathJax{\newcommand{\mdlgwhtcircle}{\mathbin{\unicode{x025CB}}}}
309 \CustomizeMathJax{\newcommand{\bullseye}{\mathord{\unicode{x025CE}}}}
310 \CustomizeMathJax{\newcommand{\mdlgblkcircle}{\mathord{\unicode{x025CF}}}}
311
312 \CustomizeMathJax{\newcommand{\Nwarrow}{\mathrel{\unicode{x021D6}}}}
313 \CustomizeMathJax{\newcommand{\Nearrow}{\mathrel{\unicode{x021D7}}}}
314 \CustomizeMathJax{\newcommand{\Searrow}{\mathrel{\unicode{x021D8}}}}
315 \CustomizeMathJax{\newcommand{\Swarrow}{\mathrel{\unicode{x021D9}}}}
316
317 \CustomizeMathJax{\newcommand{\Mapsfrom}{\mathord{\unicode{x02906}}}}
318 \CustomizeMathJax{\newcommand{\smwhtcircle}{\mathord{\unicode{x025E6}}}}
319 \CustomizeMathJax{\newcommand{\smwhtdiamond}{\mathbin{\unicode{x022C4}}}}
320 \CustomizeMathJax{\newcommand{\Mapsto}{\mathord{\unicode{x02907}}}}
321
322 \CustomizeMathJax{\let\ngets\leftarrow}
323 \CustomizeMathJax{\let\nsimeq\nsime}
324 \CustomizeMathJax{\let\nle\leq}
325 \CustomizeMathJax{\let\nge\geq}
326
327 \end{warpMathJax}

```

File 250 **lwarp-lineno.sty**

§ 359 Package **lineno**

(Emulates or patches code by STEPHAN I. BÖTTCHER.)

Pkg `lineno`

`lineno` is partly emulated, but mostly ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{lineno}[2005/11/02]

```

2 \newcommand*\resetlinenumber[1][\@ne]{
3
4 \def\linenumbers{%
5   \@ifnextchar[\resetlinenumber]%
6     {\@ifstar{\resetlinenumber}}{}%
7 }
8
9 \newcommand*\nolinenumbers{}
10

```

```

11 \@namedef{linenumbers*}{\par\linenumbers*}
12 \@namedef{runninglinenumbers*}{\par\runninglinenumbers*}
13
14 \def\endlinenumbers{\par}
15 \let\endrunninglinenumbers\endlinenumbers
16 \let\endpagewiselinenumbers\endlinenumbers
17 \expandafter\let\csname endlinenumbers*\endcsname\endlinenumbers
18 \expandafter\let\csname endrunninglinenumbers*\endcsname\endlinenumbers
19 \let\endnolinenumbers\endlinenumbers
20
21 \def\pagewiselinenumbers{\linenumbers\setpagewiselinenumbers}
22
23 \def\runninglinenumbers{\setrunninglinenumbers\linenumbers}
24
25 \def\setpagewiselinenumbers{}
26
27 \def\setrunninglinenumbers{}
28
29 \def\linenomath{}%
30 \@namedef{linenomath*}{}%
31 \def\endlinenomath{}
32 \expandafter\let\csname endlinenomath*\endcsname\endlinenomath
33
34 \let\linelabel\label
35
36 \def\switchlinenumbers{\@ifstar{}{}}
37 \def\setmakelinenumbers#1{\@ifstar{}{}}
38
39 \def\leftlinenumbers{\@ifstar{}{}}
40 \def\rightlinenumbers{\@ifstar{}{}}
41
42 \newcounter{linenumber}
43 \newcount\c@pagewiselinenumber
44 \let\c@runninglinenumber\c@linenumber
45
46 \def\runningpagewiselinenumbers{}
47 \def\realpagewiselinenumbers{}
48
49
50 \NewDocumentCommand\modulolinenumbers{s o}{}
51
52 \chardef\c@linenumbermodulo=5
53 \modulolinenumbers[1]
54
55 \newcommand*\firstlinenumber[1]{}
56
57 \newcommand\internallinenumbers{}
58 \let\endinternallinenumbers\endlinenumbers
59 \@namedef{internallinenumbers*}{\internallinenumbers}
60 \expandafter\let\csname endinternallinenumbers*\endcsname\endlinenumbers
61
62 \newcommand*\linenoplaceholder}[1]{% redefine per language
63   (line number reference for \detokenize\expandafter{#1})
64 }
65
66 \newcommand*\lineref}[2][]{\linenoplaceholder{#2}}
67 \newcommand*\linerefp}[2][]{\linenoplaceholder{#2}}
68 \newcommand*\linerefr}[2][]{\linenoplaceholder{#2}}
69
70 \newcommand\quotelinenumbers

```

```

71  {\@ifstar\linenumbers{\@ifnextchar[\linenumbers{\linenumbers*}}}
72
73 \newdimen\linenumbersep
74 \newdimen\linenumberwidth
75 \newdimen\quotelinenumbersep
76
77 \quotelinenumbersep=\linenumbersep
78 \let\quotelinenumberfont\linenumberfont
79
80 \def\linenumberfont{\normalfont\tiny\sffamily}
81
82
83 \linenumberwidth=10pt
84 \linenumbersep=10pt
85
86 \def\thelinenumber{}
87
88 \def\LineNumber{}
89 \def\makeLineNumber{}
90 \def\makeLineNumberLeft{}
91 \def\makeLineNumberRight{}
92 \def\makeLineNumberOdd{}
93 \def\makeLineNumberEven{}
94 \def\makeLineNumberRunning{}
95
96
97 \newenvironment{numquote}      {\quote}{\endquote}
98 \newenvironment{numquotation} {\quotation}{\endquotation}
99 \newenvironment{numquote*}    {\quote}{\endquote}
100 \newenvironment{numquotation*}{\quotation}{\endquotation}
101
102 \newdimen\bframerule
103 \bframerule=\fboxrule
104
105 \newdimen\bframesep
106 \bframesep=\fboxsep
107
108 \newenvironment{bframe}
109 {%
110   \LWR@forceminwidth{\bframerule}%
111   \BlockClass[
112     border:\LWR@printlength{\LWR@atleastonept} solid black ; %
113     padding:\LWR@printlength{\bframesep}%
114   ]{bframe}
115 }
116 {\endBlockClass}

```

File 251 **lwarp-lips.sty**

§ 360 Package **lips**

(Emulates or patches code by MATT SWIFT.)

lips is emulated.

```

1% \LWR@ProvidesPackageDrop{lips}
2\PackageInfo{lwarp}{Using the lwarp version of package ‘lips’.%}

```

```

3 \ProvidesPackage{lwarp-lips}[2001/08/31]
4
5 \NewDocumentCommand{\Lips}{}{\textellipsis}
6
7 \NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}
8
9 \let\lips\Lips
10 \let\olips\lips
11
12 \DeclareOption*{}
13 \DeclareOption{mla}{
14 \let\lips\BracketedLips
15 }
16 \ProcessOptions\relax
17
18 \newcommand \LPNobreakList {}

```

File 252 **lwarp-lipsum.sty**

§ 361 Package **lipsum**

(Emulates or patches code by PATRICK HAPPEL.)

Pkg lipsum

lipsum is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{lipsum}[2021-03-03]
2
3 \SetLipsumParListItemEnd{%
4   \LWR@closeparagraph%
5
6   \leavevmode\LWR@orignewline%
7 }

```

File 253 **lwarp-listings.sty**

§ 362 Package **listings**

(Emulates or patches code by CARSTEN HEINZ, BROOKS MOSES, JOBST HOFFMANN.)

Pkg listings

listings is supported with some limitations. Text formatting and escape characters are not yet supported.

```

1 \LWR@ProvidesPackagePass{listings}[2018/09/02]

```

Force flexible columns. Fixed columns inserts spaces in the PDF output.

```

2 \lst@column@flexible

```

Patches to embed listings inside pre tags:

```

3 \let\LWR@origlst@Init\lst@Init

```

```

4 \let\LWR@origlst@DeInit\lst@DeInit
5
6 \let\LWR@origlsthkEveryPar\lsthk@EveryPar
7
8 \renewcommand{\l@lstlisting}[2]{\hypertocfloat{1}{\lstlisting}{lol}{#1}{#2}}

```

\lstset

*{<options>}*Use the listings `literate` option to replace HTML entities:

```

9 \def\lstset#1{\endgroup%
10% \ifx\@empty#1%
11%     \@empty%
12% \else%
13     \setkeys{lst}{%
14         #1%
15         ,literate=%
16         {<}\HTMLentity{lt}}{4}%
17         {>}\HTMLentity{gt}}{4}%
18         {'}\HTMLentity{apos}}{6}%
19         {'}\HTMLentity{grave}}{7}%

```

The ampersand is not treated here, as the result is inconsistent spacing. It is nevertheless converted to `&`; elsewhere. Sanitizing the double quote interferes with listings' conversion of visible spaces inside strings.

```

20     }%
21% \fi%
22}

```

\lst@Init

{<backslash-processing>} Done at the start of a listing.

```
23 \renewcommand{\lst@Init}[1]{%
```

Perform the listings initialization:

```
24 \LWR@traceinfo{\lst@Init}%
```

`\LWR@forcenewpage` is moved to the start to avoid a spurious bug with paragraph handling and conditionals.

```

25 \lst@ifdisplaystyle%         lwarp
26   \LWR@forcenewpage%         lwarp
27 \fi%                           lwarp

```

Escapes do not work yet, and are disabled:

```

28 \let\lst@ifmathescape\iffalse%     lwarp
29 \let\lst@DefEsc\relax%             lwarp
30 \def\lst@escapebegin{}%           lwarp
31 \def\lst@escapeend{}%             lwarp

32 \renewcommand*{\@capttype}{\lstlisting}%     lwarp
33   \let\lst@aboveskip\z@\let\lst@belowskip\z@%     lwarp
34   \gdef\lst@boxpos{t}%             lwarp
35   \let\lst@frame\@empty%           lwarp
36   \let\lst@frametshape\@empty%     lwarp
37   \let\lst@framershape\@empty%     lwarp
38   \let\lst@framebshape\@empty%     lwarp
39   \let\lst@framefshape\@empty%     lwarp
40   \lstframe@\lst@frameround ffff\relax%     lwarp
41   \lst@multicols\@empty%           lwarp
42   \begingroup%

```

Inside the listing, temporarily prevent underfull \hbox warnings.

```

43         \hbadness=10000\relax%
44     \ifx\lst@float\relax\else%
45         \edef\@tempa{\noexpand\lst@beginfloat{\lstlisting}[\lst@float]}%
46         \expandafter\@tempa%
47     \fi%
48     \ifx\lst@multicols\empty\else%
49         \edef\lst@next{\noexpand\multicols{\lst@multicols}}%
50         \expandafter\lst@next%
51     \fi%
52     \ifhmode\ifinner \lst@boxtrue \fi\fi%
53     \lst@ifbox%
54         \lsthk@BoxUnsafe%
55         \hbox to\z@\bgroup%
56             $\if t\lst@boxpos \vtop%
57             \else \if b\lst@boxpos \vbox%
58             \else \vcenter \fi\fi%
59         \bgroup \par\noindent%
60     \else%
61         \lst@ifdisplaystyle%
62             \lst@EveryDisplay%
63             \par\penalty-50\relax%
64             \vspace\lst@aboveskip%
65         \fi%
66     \fi%
67     \normalbaselines%
68     \abovecaptionskip\lst@abovecaption\relax%
69     \belowcaptionskip\lst@belowcaption\relax%
70     \lst@MakeCaption t%

```

Use the overall listing label instead of the line number label:

```

71 \LWR@traceinfo{\lst@Init: defining current label !\@currentlabel!}%
72     \let\LWR@listings@currentlabel\@currentlabel%          lwarp
73 \LWR@traceinfo{\lst@Init: defining current label !\cref@currentlabel!}%
74     \let\LWR@listings@cref@currentlabel\cref@currentlabel% lwarp

75 \LWR@traceinfo{\lst@Init: preinit and init}%
76     \lsthk@PreInit \lsthk@Init%

77     \let\@currentlabel\LWR@listings@currentlabel%          lwarp
78     \let\cref@currentlabel\LWR@listings@cref@currentlabel% lwarp

79 \LWR@traceinfo{\lst@Init: M}%
80     \lst@ifdisplaystyle
81         \global\let\lst@ltxlabel\empty
82         \if@inlabel
83             \lst@ifresetmargins
84                 \leavevmode
85             \else
86                 \xdef\lst@ltxlabel{\the\everypar}%
87                 \lst@AddTo\lst@ltxlabel{%
88                     \global\let\lst@ltxlabel\empty
89                     \everypar{\lsthk@EveryLine\lsthk@EveryPar}}%
90             \fi
91         \fi
92         \everypar\expandafter{\lst@ltxlabel
93                     \lsthk@EveryLine\lsthk@EveryPar}%
94     \else
95         \everypar{}
96         \let\lst@NewLine\empty

```

```

97  \fi
98  \LWR@traceinfo{lst@Init: P}%
99  \lsthk@InitVars \lsthk@InitVarsBOL
100 \let\lst@Let{13}\lst@MProcessListing
101 \let\lst@Backslash#1%
102 \lst@EnterMode{\lst@Pmode}{\lst@SelectCharTable}%
103 \lst@InitFinalize%
104 \LWR@traceinfo{lst@Init: S}%

```

Avoids extra horizontal space:

```

105 \def\lst@frame{lr{}}%      lwarp
106 \LWR@traceinfo{lst@Init: finished origlst@Init}%
107 \lst@ifdisplaystyle%      lwarp

```

Creating a display.

Disable line numbers, produce the <pre>, then reenable line numbers.

```

108 \LWR@traceinfo{lst@Init: About to create verbatim.}% lwarp
109 \let\lsthk@EveryPar\relax%      lwarp
110 \LWR@atbeginverbatim{programlisting}%      lwarp
111
112 \let\lsthk@EveryPar\LWR@origlsthkEveryPar% lwarp
113 \else%      lwarp

```

Inline, so open a :

```

114 \ifbool{LWR@verbtags}{\LWR@htmltag%      lwarp
115   span class=\textquotedbl{}inlineprogramlisting\textquotedbl%      lwarp
116 }}{}%      lwarp
117 \fi%      lwarp
118 \LWR@traceinfo{lst@Init: done}%
119 }

```

\lst@DeInit

Done at the end of a listing.

```

120 \renewcommand*\lst@DeInit{}%
121 \LWR@traceinfo{lst@DeInit}%
122 \lst@ifdisplaystyle%

```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```

123 \let\lsthk@EveryPar\relax%
124 \LWR@afterendverbatim%
125 \let\lsthk@EveryPar\LWR@origlsthkEveryPar%
126 \else%

```

Inline, so create the closing :

```

127 \ifbool{LWR@verbtags}{\noindent\LWR@htmltag{/span}}{}%
128 \fi%

```

Final listings deinit:

```

129 \lst@XPrintToken \lst@EOLUpdate
130 \global\advance\lst@newlines\m@ne
131 \lst@ifshowlines
132 \lst@DoNewLines
133 \else
134 \setbox\@tempboxa\vbox{\lst@DoNewLines}%
135 \fi

```

```

136 \lst@ifdisplaystyle \par\removelastskip \fi
137 \lsthk@ExitVars\everypar{}\lsthk@DeInit\normalbaselines\normalcolor
138 \lst@MakeCaption b%
139 \lst@ifbox
140     \egroup $\hss \egroup
141     \vrule\@width\lst@maxwidth\@height\z@\@depth\z@
142 \else
143     \lst@ifdisplaystyle
144         \par\penalty-50\vspace\lst@belowskip
145     \fi
146 \fi
147 \ifx\lst@multicols\@empty\else
148     \def\lst@next{\global\let\@checkend\@gobble
149                 \endmulticols
150                 \global\let\@checkend\lst@@checkend}
151     \expandafter\lst@next
152 \fi
153 \ifx\lst@float\relax\else
154     \expandafter\lst@endfloat
155 \fi
156 \endgroup
157 \LWR@traceinfo{\lst@DeInit done}%
158 }

```

\lst@MakeCaption

{\t/b}}

This is called BOTH at the top and at the bottom of each listing.

Patched for lwarp.

```

159 \def\lst@MakeCaption#1{%
160 \LWR@traceinfo{\lst@MakeCaption at #1}%
161 \lst@ifdisplaystyle
162 \LWR@traceinfo{\lst@MakeCaption: making a listings display caption}%
163 \ifx #1t%
164     \ifx\lst@caption\@empty\expandafter\lst@HRefStepCounter \else
165         \expandafter\refstepcounter
166     \fi {\lstlisting}%
167 % \LWR@traceinfo{About to assign label: !\lst@label!}%
168 % \ifx\lst@label\@empty\else
169 % \label{\lst@label}\fi
170 % \LWR@traceinfo{Finished assigning the label.}%
171     \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
172     \global\let\lst@name\lst@arg \global\let\lst@name\lst@name
173     \lst@ifno\@else
174         \ifx\lst@caption\@empty
175             \ifx\lst@caption\@empty
176                 \ifx\lst@intname\@empty
177                     \else
178                         \def\lst@temp{ }%
179                     \ifx\lst@intname\lst@temp \else

```

This code places a contents entry for a non-float. This would have to be modified for lwarp:

```

180 \LWR@traceinfo{\lst@MakeCaption: addcontents lst@name: -\lst@name-}%
181 % \addcontentsline{lol}{\lstlisting}{\lst@name}
182     \fi
183 \fi
184 \fi
185 \else

```

This would have to be modified for lwarp:

```

186 \LWR@traceinfo{lst@MakeCaption: addcontents lst@caption: -\lst@caption-}%
187         \addcontentsline{lol}{lstlisting}%
188 {\protect\numberline{\thelstlisting}%
189 {\protect\ignorespaces \LWR@isolate{\lst@caption} \protect\relax}}%
190         \fi
191     \fi
192 \fi
193 \ifx\lst@caption\empty\else
194 \LWR@traceinfo{lst@MakeCaption: lst@caption not empty-}%
195     \lst@ifsubstring #1\lst@captionpos
196     {\begingroup
197 \LWR@traceinfo{lst@MakeCaption: at the selected position}%

```

These space and box commands are not needed for HTML output:

```

198 %             \let\@vskip\vskip
199 %             \def\vskip{\afterassignment\lst@vskip \@tempskipa}%
200 %             \def\lst@vskip{\nobreak\@vskip\@tempskipa\nobreak}%
201 %             \par\@parboxrestore\normalsize\normalfont % \noindent (AS)
202 %             \ifx #1t\allowbreak \fi
203             \ifx\lst@title\empty

```

New lwarp code to create a caption:

```

204             \LWR@stoppars%         lwarp
205             \lst@makecaption\fnum@lstlisting{\ignorespaces \lst@caption}
206             \else

```

New lwarp code to create a title:

```

207 %             \lst@maketitle\lst@title % (AS)
208 \LWR@traceinfo{lst@MakeCaption: Making title: \lst@title}%
209 \begin{BlockClass}{lstlistingtitle}%         lwarp
210 \lst@maketitle\lst@title%                     lwarp
211 \end{BlockClass}%                             lwarp
212         \fi%
213 \LWR@traceinfo{lst@MakeCaption: About to assign label: !\lst@label!}%
214     \ifx\lst@label\empty\else%
215 \leavevmode% gets rid of bad space factor error
216 \GetTitleStringExpand{\lst@caption}%
217 \edef\LWR@lntemp{\GetTitleStringResult}%
218 \edef\@currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
219 \label{\lst@label}\fi%
220 \LWR@traceinfo{lst@MakeCaption: Finished assigning the label.}%

```

Not needed for lwarp:

```

221 %             \ifx #1b\allowbreak \fi
222             \endgroup}{}%
223     \fi
224 \LWR@traceinfo{lst@MakeCaption: end of making a listings display caption}%
225 \else
226 \LWR@traceinfo{lst@MakeCaption: INLINE}%
227 \fi
228 \LWR@traceinfo{lst@MakeCaption: done at #1}%
229 }
230
231 \renewcommand{\lst@maketitle}[1]{%
232     \LWR@isolate{#1}%
233 }%
234

```

line numbers Patched to keep left line numbers outside of the left margin, and place right line numbers in a field `\VerbatimHTMLWidth` wide.

```

235 \lst@Key{numbers}{none}{%
236   \let\lst@PlaceNumber\@empty
237   \lstKV@SwitchCases{#1}%
238   {none:\%
239     left:\def\lst@PlaceNumber{%

```

For now, `lwarp` places left line numbers inline. Ideally the entire line would be moved to the right, but conflicts with list indenting occurs.

```

240 %       \LWR@origllap{
241         \LWR@orignormalfont%
242         \lst@numberstyle{\the\lstnumber}\kern\lst@numbersep%
243 %       }
244   }\\%
245   right:\def\lst@PlaceNumber{\LWR@origrllap{\LWR@orignormalfont
246     \kern 6in \kern\lst@numbersep
247     \lst@numberstyle{\the\lstnumber}}}%
248   }\PackageError{lwarp-listings}{Numbers #1 unknown}\@ehc}

```

File 254 **lwarp-listliketab.sty**

§ 363 Package **listliketab**

Pkg listliketab

listliketab is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{listliketab}[2005/01/09]

2 \newcommand*\storestyleof}[1]{}
3 \newcommand*\storeliststyle{}
4 \newenvironment{listliketab}{}{}

```

File 255 **lwarp-lltjext.sty**

§ 364 Package **lltjext**

Pkg lltjext

(Emulates or patches code by THE L^AT_EX-JA PROJECT TEAM.)

lltjext is patched for use by `lwarp`.

for HTML output:

```

1 \LWR@ProvidesPackagePass{lltjext}[2018/10/07]

2 \protected\def\yoko{%
3   \directlua{luatexja.direction.set_list_direction(4, 'yoko')}%
4 }
5 \protected\def\tate{\yoko}
6 \protected\def\dtou{\yoko}
7 \protected\def\utod{\yoko}
8
9 \define@key[ltj]{japaram}{direction}{}
10

```

```

11 \yoko
12
13 \DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}
14
15 \DeclareDocumentCommand{\layoutfloat}{d() o m}{}
16
17 \DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}
18
19 \LetLtxMacro\pcaption\caption
20
21 \DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}
22
23 \let\captiondir\relax
24 \RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
25   {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
26   {\endLWR@HTML@sub@minipage}
27
28 \RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
29 {
30 \LWR@traceinfo{parbox of width #4}%
31 \begin{minipage}[#2][#3][#4]{#5}%
32 #6
33 \end{minipage}%
34 }
35
36 \RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
37 \global\booltrue{LWR@minipagefullwidth}%
38 \parbox{#2}{#4}%
39 }

```

File 256 **lwarp-lltjp-siunitx.sty**

§ 365 Package **lltjp-siunitx**

(Emulates or patches code by THE L^AT_EX-JA PROJECT TEAM.)

Pkg lltjp-siunitx **lltjp-siunitx** is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{lltjp-siunitx}% 2021-10-31, no date assigned in file

This is the siunitx v3 file, as patched by lltjp-siunitx.

```

2 \ExplSyntaxOn
3
4 \cs_set_protected:Npn \siunitx_print_text:n #1
5 {
6   \text
7   {
8     \ltj@allalchar % <--- LuaTeX-ja
9     \bool_if:NT \l__siunitx_print_text_family_bool
10    { \fontfamily { \familydefault } }
11    \bool_if:NT \l__siunitx_print_text_series_bool
12    { \fontseries { \seriesdefault } }
13    \bool_if:NT \l__siunitx_print_text_shape_bool
14    { \fontshape { \shapedefault } }
15    \bool_lazy_any:nT
16    {

```

```

17         { \l__siunitx_print_text_family_bool }
18         { \l__siunitx_print_text_series_bool }
19         { \l__siunitx_print_text_shape_bool }
20     }
21     { \selectfont }
22     \tl_use:N \l__siunitx_print_text_font_tl
23     \exp_args:NnV \tl_if_head_eq_meaning:nNTF {#1} \l_siunitx_unit_fraction_tl
24     {
25         \__siunitx_print_text_fraction:Nnn #1
26     }
27     {
28         \__siunitx_print_text_replace:n {#1}
29     }
30 }
31 }
32
33 \ExplSyntaxOff

```

File 257 **lwarp-lltjp-tascmac.sty**

§ 366 Package **lltjp-tascmac**

Pkg lltjp-tascmac

lltjp-tascmac is a patch for tascmac, and is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{lltjp-tascmac}[2020/12/24]

File 258 **lwarp-longtable.sty**

§ 367 Package **longtable**

(Emulates or patches code by DAVID CARLISLE.)

Pkg longtable

longtable is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{longtable}[2014/10/28]

Use one of either `\endhead` or `\endfirsthead` for both print and HTML, and use a `\warpprintonly` macro to disable the other head phrase, and also the `\endfoot` and `\endfirstfoot` phrases. (See section 8.10.4 if using `threeparttablex`.)

```

\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[ . . . ] \endhead % or \endfirsthead
[ . . . ] \endfoot
[ <lastfoot macros> ] \endlastfoot
}
. . . table contents . . .
\warppHTMLonly{
[ <lastfoot macros> ] % HTML last footer, without \endfoot
% or \endlastfoot.
}
\end{longtable}

```

⚠ **Misplaced `\noalign`** Use the `\warpprintonly` macro instead of the `warpprint` environment. Doing so helps avoid “Misplaced `\noalign`.” when using `\begin{warpprint}`.

⚠ **`\kill`** `\kill` is ignored, place a `\kill` line inside

```
\begin{warpprint} . . . \end{warpprint}
```

or place it inside `\warpprintonly`.

⚠ **`lateximage`** `longtable` is not supported inside a `lateximage`.

See:

<http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable>

Used to detect more than one of `\endhead` and `\endfirsthead` in use for HTML at the same time.

```
2 \newbool{LWR@longtable@havehead}
3 \boolfalse{LWR@longtable@havehead}
```

Env `longtable` * [`<horizontalignment>`] [`<colspec>`] Emulates the `longtable` environment.

Per the `caption` package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options `[c]`, `[l]`, and `[r]` are ignored.

```
4 \newenvironment{longtable*}[2][]{%
5   \LWR@floatbegin{table}%
6   \ifdef{\setcaptiontype}{% caption package:
7     \setcaptiontype{\LTcaptiontype}%
8     \caption@setoptions{longtable}%
9     \caption@setoptions{@longtable}%
10    \caption@LT@setup%
11  }{% w/o caption package:
12    \renewcommand*{\@captiontype}{\LTcaptiontype}%
13  }%
14  \booltrue{LWR@starredlongtable}%
15  \boolfalse{LWR@longtable@havehead}%
16  \let\captionlistentry\LWR@LTcaptionlistentry%
17  \tabular{#2}%
18 }
19 {\endtabular\LWR@floatend}
20
21 \newenvironment{longtable}[2][]{%
22   \LWR@floatbegin{table}%
23   \ifdef{\setcaptiontype}{% caption package:
24     \setcaptiontype{\LTcaptiontype}%
25     \caption@setoptions{longtable}%
26     \caption@setoptions{@longtable}%
27     \caption@LT@setup%
28  }{% w/o caption package:
29     \renewcommand*{\@captiontype}{\LTcaptiontype}%
30  }%
31  \refstepcounter{\LTcaptiontype}%
32  \boolfalse{LWR@longtable@havehead}%
33  \let\captionlistentry\LWR@LTcaptionlistentry%
34  \tabular{#2}%
```

```
35 }
36 {\endtabular\LWR@floatend}
```

Provided for compatibility, but ignored:

```
37 \newcounter{LTchunksize}
```

Error for heads which should have been in `\warpprintonly`:

```
38 \newcommand*{\LWR@longtable@headerror}{%
39   \PackageError{lwarp-longtable}
40   {For longtable:\MessageBreak
41   1: Keep either one of an \protect\endhead\space or\MessageBreak
42     \space\protect\endfirsthead\space phrase as-is,\MessageBreak
43     \space to be used by both print and HTML.\MessageBreak
44   2: Place any other \protect\end... phrases inside a\MessageBreak
45     \space\protect\warpprintonly\space macro,
46     to be ignored by HTML.\MessageBreak
47   3: At the end of the table,\MessageBreak
48     \space add a final footer for HTML\MessageBreak
49     \space inside a \protect\warpprintonly\space macro.
50     This can be\MessageBreak
51     \space a copy of an \protect\endfoot\space or
52     \protect\endfirstfoot\space\MessageBreak
53     \space phrase, but without the actual \protect\endfoot\space\MessageBreak
54     \space or \protect\endfirstfoot\space macros.\MessageBreak
55     \space If using threeparttablex, add\MessageBreak
56     \space \protect\insertTableNotes\space here,
57     optionally with\MessageBreak
58     \space \protect\UseMinipageWidths\space in front.\MessageBreak
59   See the Lwarp documentation regarding\MessageBreak
60   longtables and threeparttablex}
61   {See the Lwarp documentation regarding longtables and threeparttablex.}
62 }
```

Error if more than one of `\endhead` or `\endfirsthead` is outside of `\warpprintonly`.

```
63 \newcommand*{\LWR@longtable@maybeheaderror}{%
64 \ifbool{\LWR@longtable@havehead}%
65   {\LWR@longtable@headerror}%
66   {%
67     \booltrue{\LWR@longtable@havehead}
68     \LWR@tabularendofline% throws away options //[dim] and //*
69   }%
70 }
```

Error if more than one of these is outside of `\warpprint`.

```
71 \def\endhead{\LWR@longtable@maybeheaderror}
72 \def\endfirsthead{\LWR@longtable@maybeheaderror}
```

Error if ANY of these is outside of `\warpprint`.

```
73 \def\endfoot{\LWR@longtable@headerror}
74 \def\endlastfoot{\LWR@longtable@headerror}
```

```
75 \let\tabularnewline\
```

```

76 \providecommand*\LWR@HTML@tabularnewline{\LWR@tabularendofline}
77 \LWR@formatted{tabularnewline}

78 \newcommand{\setlongtables}{}% Obsolete command, does nothing.
79 \newlength{\LTleft}
80 \newlength{\LTright}
81 \newlength{\LTpre}
82 \newlength{\LTpost}
83 \newlength{\LTcapwidth}

84 \LetLtxMacro\LWR@origkill\kill
85 \renewcommand*\kill{\LWR@tabularendofline}
86 \appto\LWR@restoreorigformatting{%
87 \LetLtxMacro\kill\LWR@origkill%
88 }

```

File 259 **lwarp-lpic.sty**

§ 368 Package **lpic**

(Emulates or patches code by R. MATVEYEV.)

Pkg lpic

lpic is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{lpic}[2010/12/23]

2 \BeforeBeginEnvironment{lpic}{%
3   \begin{lateximage}[-lpic-~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{lpic}{\end{lateximage}}

```

File 260 **lwarp-lscape.sty**

§ 369 Package **lscape**

(Emulates or patches code by D. P. CARLISLE.)

Pkg lscape

lscape is ignored.

for HTML output: Discard all options for lwarp-lscape.

```

1 \LWR@ProvidesPackageDrop{lscape}[2000/10/22]

2 \newenvironment*{landscape}{}{}

```

File 261 **lwarp-ltablex.sty**

§ 370 Package **ltablex**

(Emulates or patches code by ANIL K. GOEL.)

Pkg ltablex

ltablex is emulated by lwarp.

for HTML output:

Relies on tabularx.

```

1 \RequirePackage{longtable}
2 \RequirePackage{tabularx}
3
4 \LWR@ProvidesPackageDrop{ltablex}[2014/08/13]
5
6 \DeclareDocumentEnvironment{tabularx}{m o m}
7 {\longtable{#3}}
8 {\endlongtable}
9
10 \DeclareDocumentEnvironment{tabularx*}{m o m}
11 {\longtable{#3}}
12 {\endlongtable}
13
14 \newcommand*\keepXColumns{}
15 \newcommand*\convertXColumns{}

```

File 262 **lwarp-ltcaption.sty**

§ 371

Package

ltcaption*(Emulates or patches code by AXEL SOMMERFELDT.)*

Pkg ltcaption

ltcaption is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{ltcaption}[2018/08/26]
```

\LTcaptype is already defined by lwarp.

longtable* is already defined by lwarp-longtable.

```

2 \newlength{\LTcapskip}
3 \newlength{\LTcapleft}
4 \newlength{\LTcapright}
5 \newcommand*\LTcapmarginsfalse{}

```

File 263 **lwarp-ltxgrid.sty**

§ 372

Package

ltxgrid

Pkg ltxgrid

ltxgrid is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{ltxgrid}[2010/07/25]
2 \newcommand*\onecolumngrid{}
3 \newcommand*\twocolumngrid{}
4 \newcommand*\removestuff{}
5 \newcommand*\addstuff}[2]{}
6 \newcommand*\replacestuff}[2]{}

```

File 264 **lwarp-ltxtable.sty**

§ 373 Package **ltxtable**

Pkg ltxtable

ltxtable is emulated.

 **table numbering** The print version does not seem to honor longtable* from the caption package, while lwarp does.

for HTML output:

```
1 \RequirePackage{tabularx, longtable}
2 \LWR@ProvidesPackageDrop{ltxtable}[1995/12/11]
```

\LTxtable

```
{\width} {\file}
3 \newcommand*\LTxtable[2]{%
4   \input{#2}%
5 }
```

File 265 **lwarp-lua-check-hyphen.sty**

§ 374 Package **lua-check-hyphen**

Pkg lua-check-hyphen

lua-check-hyphen is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{lua-check-hyphen}[2018/04/19]
2 \newcommand*\LuaCheckHyphen[1]{}
```

File 266 **lwarp-lua-visual-debug.sty**

§ 375 Package **lua-visual-debug**

Pkg lua-visual-debug

lua-visual-debug is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{lua-visual-debug}[2016/05/30]
```

File 267 **lwarp-luacolor.sty**

§ 376 Package **luacolor**

Pkg luacolor

luacolor is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{luacolor}[2016/05/16]
2 \newcommand*\LuacolorProcessBox[1]{}
```

File 268 **lwarp-luamplib.sty**

§ 377 Package **luamplib**

(Emulates or patches code by HANS HAGEN, TACO HOEKWATER, ELIE ROUX, PHILIPP GESANG, KIM DO-HYUN.)

Pkg luamplib

luamplib is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{luamplib}[2020/02/24]

2 \BeforeBeginEnvironment{mplibcode}{%
3   \begin{lateximage}[-mplibcode~\PackageDiagramAltText]%
4 }
5 \AfterEndEnvironment{mplibcode}{\end{lateximage}}
```

File 269 **lwarp-luatexko.sty**

§ 378 Package **luatexko**

(Emulates or patches code by DOHYUN KIM, SOOJIN NAM.)

Pkg luatexko

luatexko is patched for use by lwarp.

Modern HTML is used for \dotemph, \ruby, and offset and thickness control for \uline, etc.

for HTML output:

```

1 \LWR@ProvidesPackagePass{luatexko}[2021/07/10]

2 \protected\def\typesetvertical{}
3 \protected\def\typesethorizontal{}
4
5 \def\verticaltypesetting{\BlockClass{verticalrl}}
6 \def\beginverticaltypesetting{\BlockClass{verticalrl}}
7 \def\endverticaltypesetting{\endBlockClass}
8
9 \protected\def\vertical#1{\BlockClass{verticalrl}}
10 \protected\def\endvertical{\endBlockClass}
11 \protected\def\horizontal#1{\BlockClass{horizontaltb}}
12 \protected\def\endhorizontal{\endBlockClass}
13 \DeclareDocumentCommand{\vertlatin}{m}{#1}

14 \newcommand{\LWR@HTML@dotemph}[1]{%
15 %   \uline{#1}%
16   \InlineClass[text-emphasis-style: dot]{dotemph}{#1}%
17 }
18 \LWR@formatted{dotemph}

19 \newcommand{\LWR@HTML@ruby}[2]{%
20   \LWR@htmltagc{ruby}%
21   #1%
22   \LWR@htmltagc{rp}\LWR@htmltagc{/rp}%
```

```

23 \LWR@htmltagc{rt}#2\LWR@htmltagc{/rt}%
24 \LWR@htmltagc{rp})\LWR@htmltagc{/rp}%
25 \LWR@htmltagc{/ruby}%
26 }
27 \LWR@formatted{ruby}

```

The following is modified from lwarp-ulem:

```

28 \NewDocumentCommand{\LWR@HTML@uline}{+m}{%
29 \InlineClass%
30 (text-decoration:underline; text-decoration-skip: auto)%
31 [%
32 text-decoration:underline; text-decoration-skip: auto;
33 text-decoration-thickness: \ulinewidth%
34 ]%
35 {uline}{\LWR@isolate{#1}}%
36 }
37 \LWR@formatted{uline}
38
39 \NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
40 \InlineClass%
41 (%
42 text-decoration:underline; text-decoration-skip: auto;%
43 text-decoration-style:double%
44 )%
45 [%
46 text-decoration:underline; text-decoration-skip: auto;
47 text-decoration-thickness: \ulinewidth%
48 ]%
49 {uuline}{\LWR@isolate{#1}}%
50 }
51 \LWR@formatted{uuline}
52
53 \NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
54 \InlineClass%
55 (%
56 text-decoration:underline; text-decoration-skip: auto;%
57 text-decoration-style:wavy%
58 )%
59 [%
60 text-decoration:underline; text-decoration-skip: auto;
61 text-decoration-thickness: \ulinewidth%
62 ]%
63 {uwave}{\LWR@isolate{#1}}%
64 }
65 \LWR@formatted{uwave}
66
67 \NewDocumentCommand{\LWR@HTML@sout}{+m}{%
68 \InlineClass%
69 (text-decoration:line-through)%
70 [text-decoration-thickness: \ulinewidth]%
71 {sout}{\LWR@isolate{#1}}%
72 }
73 \LWR@formatted{sout}
74
75 \NewDocumentCommand{\LWR@HTML@xout}{+m}{%
76 \InlineClass%
77 (text-decoration:line-through)%
78 [text-decoration-thickness: \ulinewidth]%
79 {xout}{\LWR@isolate{#1}}%

```

```

80 }
81 \LWR@formatted{xout}
82
83 \NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
84   \InlineClass%
85   (%
86     text-decoration:underline;%
87     text-decoration-skip: auto;%
88     text-decoration-style:dashed%
89   )%
90   [%
91     text-underline-offset: \linedown ;
92     text-decoration-thickness: \linewidth%
93   ]%
94   {dashuline}{\LWR@isolate{#1}}%
95 }
96 \LWR@formatted{dashuline}
97
98 \NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
99   \InlineClass%
100  (%
101    text-decoration:underline;%
102    text-decoration-skip: auto;%
103    text-decoration-style: dotted%
104  )%
105  [%
106    text-underline-offset: \linedown ;
107    text-decoration-thickness: \linewidth%
108  ]%
109  {dotuline}{\LWR@isolate{#1}}%
110 }
111 \LWR@formatted{dotuline}

```

File 270 **lwarp-luatodonotes.sty**

§ 379 Package **luatodonotes**

(Emulates or patches code by FABIAN LIPP.)

Pkg luatodonotes

luatodonotes is emulated.

The documentation for `todonotes` and `luatodonotes` have an example with a `todo` inside a caption. If this example does not work it will be necessary to move the `todo` outside of the caption.

for HTML output: 1 \LWR@ProvidesPackagePass{luatodonotes}[2017/09/30]

Nullify options:

```

2 \@todonotes@additionalMarginEnabledfalse

3 \if@todonotes@disabled
4 \else
5
6 \newcommand{\ext@todo}{tdo}
7
8 \renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}

```

```

9 \let\LWRTODONOTES@orig@todototoc\todototoc
10
11 \renewcommand*\todototoc{%
12 \LWR@phantomsection%
13 \LWRTODONOTES@orig@todototoc%
14 }
15
16
17 \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
18 \fcolorbox
19   {\@todonotes@currentbordercolor}
20   {\@todonotes@currentbackgroundcolor}
21   {\arabic{\@todonotes@numberoftodonotes}}
22 \marginpar{\@todonotes@drawMarginNote}
23 }
24
25 \renewcommand{\@todonotes@drawInlineNote}{%
26 \fcolorboxBlock%
27   {\@todonotes@currentbordercolor}%
28   {\@todonotes@currentbackgroundcolor}%
29   {%
30     \if@todonotes@authorgiven%
31     {\@todonotes@author:\,}%
32     \fi%
33     \@todonotes@text%
34   }%
35 }
36
37 \newcommand{\@todonotes@drawMarginNote}{%
38   \if@todonotes@authorgiven%
39     \@todonotes@author\par%
40   \fi%
41   \arabic{\@todonotes@numberoftodonotes}: %
42   \fcolorbox%
43   {\@todonotes@currentbordercolor}%
44   {\@todonotes@currentbackgroundcolor}%
45   {%
46     \@todonotes@sizecommand%
47     \@todonotes@text %
48   }%
49 }%
50
51 \renewcommand{\missingfigure}[2][]{%
52 \setkeys{todonotes}{#1}%
53 \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
54 \fcolorboxBlock%
55   {\@todonotes@currentbordercolor}%
56   {\@todonotes@currentfigcolor}%
57   {%
58     \setlength{\fboxrule}{4pt}%
59     \fcolorbox{red}{white}{Missing figure} \quad #2%
60   }
61 }
62
63 \LetLtxMacro\LWRTODONOTES@orig@todocommon\@todocommon
64
65 \RenewDocumentCommand{\@todocommon}{m m}{%
66 \begingroup%
67 \renewcommand*\phantomsection{}%
68 \LWRTODONOTES@orig@todocommon{#1}{#2}%

```

```

69 \endgroup%
70 }
71
72 \renewcommand{\@todoarea}[3][[]]{%
73   \@todonotes@areaselectedtrue%
74   \@todocommon{#1}{#2}%
75   \@todonotes@textmark@highlight{#3}%
76   \zref@label{\@todonotes@arabic{\@todonotes@numberoftodonotes}@end}%
77 }%
78
79
80 \DeclareDocumentCommand{\todonotes@textmark@highlight}{m}{%
81 \InlineClass[background:\LWR@origpound{ }B3FFB3]{highlight}{#1}%
82 }
83
84 \fi% \if@todonotes@disabled

```

File 271 **lwarp-luavlna.sty**

§ 380 Package **luavlna**

(Emulates or patches code by MICHAL HOFTICH, MIRO HRONČOK.)

Pkg luavlna

luavlna is patched for use by lwarp.

The package is disabled for HTML output, due to incompatibilities with lwarp's handling of math SVG images.

for HTML output:

```

1 \LWR@ProvidesPackagePass{luavlna}[2019/10/30]
2 \preventsingloff
3 \LetLtxMacro\preventsingleon\preventsingloff

```

File 272 **lwarp-lyluatex.sty**

§ 381 Package **lyluatex**

(Emulates or patches code by FR. JACQUES PERON, URS LISKA, BR. SAMUEL SPRINGUEL.)

Pkg lyluatex

lyluatex is patched for use by lwarp.

For the first compile, to set *lwarpmk*'s configuration, use:

```
lualatex --shell-escape <filename>
```

 **images** After compiling the document with **lwarpmk html**, use **lwarpmk limages** to convert the Lilypond images for HTML.

css The option `insert=systems` results in an image per system. Each music image “system” is placed inside a `` of class `lyluatex`, which defaults to `display: inline-block`.

 **insert=fullpage** The option `insert=fullpage` results in a single image per page of printed output. Each music “fullpage” image is placed inside a `<div>` of class `lyluatex`. To

css

match the number of measures per line with the printed version, use the `geometry` package to select the page geometry, or use the `lyluatex` options for page and staff sizes.

- ⚠ **options** To use `\linewidth` or `\textwidth` inside the package options for `lyluatex`, use the `kvoptions-patch` package first:

```
\usepackage{kvoptions-patch}
\usepackage[... ,line-width=0.8\linewidth,...]{lyluatex}
```

- ⚠ **raw-pdf** If using `raw-pdf`, the resulting PDF images must be converted to `svg`:

```
Enter ⇒ lwarpmk pdftosvg tmp-ly/*.pdf
```

for HTML output:

```
1 \LWR@origRequirePackage{luacode}
2
3 \LWR@ProvidesPackagePass{lyluatex}[2019/05/27]
```

User-redefinable ALT tag:

```
4 \newcommand*{\LyluatexImageAltText}{-lilypond--\PackageDiagramAltText}
```

`\ly@compilescore`

```
{(Lilypond object)}
5 \LetLtxMacro\LWR@orig@ly@compilescore\ly@compilescore
6
7 \renewcommand*{\ly@compilescore}[1]{%
```

A local group holds a number of changes:

```
8 \begingroup%
```

The user's original geometry and font size are restored to match the print version. This allows for correct spacing in the musical score.

```
9 \LWR@maybe@orignewpage%
10 \LWR@origloadgeometry{\LWR@usergeometry}%
11 \LWR@print@normalsize%
```

A local group holds a redefined `\includegraphics` which is used by `lyluatex.lua` to insert the *Lilypond* score if `insert=systems` is used. This is now placed inside a `lateximage`, which itself is placed inside a `` of class `lyluatex`.

`\LWR@addbaselinemarker` preserves the left margins.

```
12 \renewcommand{\includegraphics}[2][]{%
13   \InlineClass{lyluatex}{%
14     \begin{lateximage}[\LyluatexImageAltText]%
15     \LWR@addbaselinemarker%
16     \LWR@originincludegraphics{##2}%
17     \end{lateximage}%
18   }%
19 }
```

From the original:

```
20 \ly@setunits%
21 \directlua{
22   ly_opts:set_option('currfiledir', [[\currfiledir]])
23   ly_opts:set_option('twoside', '\ly@istwosided')
24   #1
25 }
```

```

26 \ly@resetunits%
27 \ly@currentfonts%

```

The fullpage version is set inside an HTML <div>:

```

28 \directlua{
29     if (ly.score.insert == 'fullpage') then
30         tex.print{[[\string\begin{BlockClass}{lyluatex}]]}
31     end
32 }%

```

Generate the score:

```

33 \directlua{ly.score:process()}%

```

Close the <div>:

```

34 \directlua{
35     if (ly.score.insert == 'fullpage') then
36         tex.print{[[\string\end{BlockClass}]]}
37     end
38 }%

```

Move to a new page and renew the regular page geometry:

```

39 \LWR@maybe@orignewpage%
40 \LWR@origrestoregeometry%

```

End of the local group.

```

41 \endgroup%
42 }

```

In HTML the following generates an error, so is removed:

```

43 \xpatchcmd{\endly@bufferenv}
44   {\hspace{0pt}}{\}
45   {}
46   {}
47   {\LWR@patcherror{lyluatex}{endly@bufferenv}}

```

File 273 **lwarp-magaz.sty**

§ 382 Package **magaz**

Pkg magaz

magaz is emulated.

```

for HTML output: 1 \LWR@ProvidesPackageDrop{magaz}[2011/11/24]

2 \newcommand\FirstLine[1]{%
3   \begingroup%
4   \FirstLineFont{%
5     \LWR@textcurrentcolor{%
6       \LWR@textcurrentfont{%
7         #1%
8       }%
9     }%
10  }%
11  \endgroup%
12 }
13
14 \providecommand\FirstLineFont{\scshape}

```

File 274 **lwarp-makeidx.sty**

§ 383 Package **makeidx**

(Emulates or patches code by L^AT_EX PROJECT TEAM.)

Pkg makeidx

makeidx is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{makeidx}[2014/09/29]

\@wrindex is redefined \@AtBeginDocument by the lwarp core.

\printindex

```
2 \preto\printindex{%
3   \LWR@maybe@orignewpage%
4   \LWR@startpars%
5 }
```

File 275 **lwarp-manyfoot.sty**

§ 384 Package **manyfoot**

Pkg manyfoot

manyfoot is emulated.

bigfoot, **manyfoot** Verbatim footnotes are not yet supported.

 **verbatim**

If using the **bigfoot** package, and possibly also **manyfoot**, problems may occur with counter allocation because **lwarp** uses many counters, and there is a difference in how counters numbered 256 and up are handled in PDF L^AT_EX. With **bigfoot** this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as an input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining **bigfoot** or **manyfoot** footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use X_YL^AT_EX or LuaL^AT_EX instead of PDF L^AT_EX.

lwarp's emulation of **bigfoot** uses **manyfoot**, so some of the **bigfoot** enhancements are included here.

The **bigfoot** “default” footnote is ignored, using the **lwarp** version instead.

for HTML output: 1 \LWR@ProvidesPackageDrop{manyfoot}[2005/09/11]

```
2 \RequirePackage{nccfoots}
3
4 \newcommand{\extrafootnoterule}{}
5
```

```

6 \let\defaultfootnoterule\footnoterule
7
8 \newcommand*\SelectFootnoteRule[2][0]{
9
10 \newcommand{\footnoterulepriority}{1}
11
12 \newcommand{\SetFootnoteHook}[1]{
13 \@onlypreamble\SetFootnoteHook
14
15 \newcommand{\SplitNote}{
16
17 \newcommand*\ExtraParaSkip[1]{
18
19 \newcommand*\newfootnote[2][plain]{%
20   \ifstrequal{#2}{default}{}% not "default"
21     \expandafter\newbox\csname LWR@footnote#2box\endcsname%
22     \appto{\LWR@printpendingfootnotes}{%
23       \LWR@@printpendingfootnotes{footnote#2}%
24     }
25     \long\csdef{Footnotetext#2}##1##2{%
26       \NCC@makefnmark{##1}%
27       \LWR@@footnotetext{##2}{LWR@footnote#2box}%
28     }%
29     \long\csdef{Footnotetext#2+}##1##2{%
30       \NCC@makefnmark{##1}%
31       \LWR@@footnotetext{##2}{LWR@footnote#2box}%
32     }%
33   }% not "default"
34 }
35 \@onlypreamble\newfootnote
36
37 \newcommand*\DeclareNewFootnote[2][plain]{%
38   \ifnextchar[%
39     {\LWR@manyfoot@declare{#1}{#2}}%
40     {\LWR@manyfoot@declare{#1}{#2}[arabic]}%
41 }
42
43 \def\LWR@manyfoot@declare#1#2[#3]{%
44 \ifstrequal{#2}{default}{}% not "default"
45   \newfootnote[#1]{#2}%
46   \newcounter{footnote#2}%
47   \newcounter{footnote#2Reset}%
48   \setcounter{footnote#2Reset}{0}%
49   \csdef{thefootnote#2}{%
50     \expandafter\noexpand\csname @#3\endcsname%
51     \expandafter\noexpand\csname c@footnote#2\endcsname%
52   }%

```

For **bigfoot**, the footnote commands may be appended with one or two plusses or one or two minuses, which are ignored in HTML.

```

53   \expandafter\NewDocumentCommand\csname footnote#2\endcsname{t{+}t{+}t{-}t{-}}{%
54     \stepcounter{footnote#2}%
55     \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
56     \@footnotemark%
57     \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
58   }%
59   \csdef{footnotemark#2}{%
60     \stepcounter{footnote#2}%
61     \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%

```

```

62     \@footnotemark%
63   }%
64   \expandafter\NewDocumentCommand\csname footnotetext#2\endcsname{t{+}t{+}t{-}t{-}}{%
65     \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
66     \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
67   }%
68   \csdef{Footnotemark#2}{%
69     \Footnotemark%
70   }%
71   \csdef{Footnote#2}##1{%
72     \Footnotemark{##1}%
73     \csuse{Footnotetext#2}{##1}%
74   }%
75 }% not "default"
76 }
77 \onlypreamble\DeclareNewFootnote

```

File 276 **lwarp-marginal.sty**

§ 385 Package **marginal**

Pkg marginal marginal is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{marginal}

2 \newcommand*{\showlostmarginals}{}
3 \newcommand*{\enlargefreelist}{}
4 \newcommand*{\onesidemarginals}{}

```

File 277 **lwarp-marginfit.sty**

§ 386 Package **marginfit**

Pkg marginfit marginfit is ignored.

for HTML output: Discard all options for lwarp-marginfit:

```

1 \LWR@ProvidesPackageDrop{marginfit}[2018/06/08]

```

File 278 **lwarp-marginfix.sty**

§ 387 Package **marginfix**

(Emulates or patches code by STEPHEN HICKS.)

Pkg marginfix marginfix is ignored.

for HTML output: Discard all options for lwarp-marginfix:

```

1 \LWR@ProvidesPackageDrop{marginfix}[2013/09/08]

```

```

2 \newcommand*\marginkip}[1]{}
3 \newcommand*\clearmargin{}
4 \newcommand*\softclearmargin{}
5 \newcommand*\extendmargin}[1]{}
6 \newcommand*\mparshift}[1]{}
7 \newdimen\marginheightadjustment
8 \newdimen\marginposadjustment
9 \newcommand*\blockmargin}[1][1]{}
10 \newcommand*\unblockmargin}[1][1]{}
11 \newcommand*\marginphantom}[2][1]{}

```

File 279 **lwarp-marginnote.sty**

§ 388 Package **marginnote**

(Emulates or patches code by MARKUS KOHM.)

Pkg marginnote

marginnote is emulated.

for HTML output:

Discard all options for lwarp-marginnote:

```
1 \LWR@ProvidesPackageDrop{marginnote}[2018/08/09]
```

```
2 \NewDocumentCommand{\marginnote}{+o +m o}{\marginpar{#2}}
```

```

3 \newcommand*\marginnoteleftadjust{}
4 \newcommand*\marginnoterightadjust{}
5 \newcommand*\marginnotetextwidth{}
6 \let\marginnotetextwidth\textwidth
7 \newcommand*\marginnotevadjust{}
8 \newcommand*\marginfont{}
9 \newcommand*\raggedleftmarginnote{}
10 \newcommand*\raggedrightmarginnote{}

```

```

11 \appto\LWR@restoreorigformatting{%
12   \RenewDocumentCommand{\marginnote}{+o +m o}{}
13 }

```

For MATHJAX:

```

14 \begin{warpMathJax}
15 \CustomizeMathJax{\newcommand{\LWRmarginnote}[1][1]{}
16 \CustomizeMathJax{\newcommand{\marginnote}[2][1]{\quad\small\texttrm{#2}}\LWRmarginnote}}
17 \end{warpMathJax}

```

File 280 **lwarp-marvosym.sty**

§ 389 Package **marvosym**

(Emulates or patches code by THOMAS HENLICH, MOJCA MIKLAVEC.)

Pkg marvosym

marvosym is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```

1 \LWR@ProvidesPackagePass{marvosym}[2011/07/20]
2 \renewcommand{\mvchr}[1]{%
3   \begin{lateximage}*{symbol #1}[marvosym #1]%
4   \mvs\char#1%
5   \end{lateximage}%
6 }
7
8 \renewcommand{\textmvs}[1]{%
9   \begin{lateximage}%
10  \mvs #1%
11  \end{lateximage}%
12 }
```

File 281 **lwarp-mathalpha.sty**

§ 390 Package **mathalpha**

(Emulates or patches code by MICHAEL SHARPE.)

Pkg mathalpha

mathalpha is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, and some bold fonts may not be not supported by MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{mathalpha}[2021/11/18]
2
3 \begin{warpMathJax}
4 \CustomizeMathJax{\newcommand{\mathbfbb}[1]{\boldsymbol{\mathbb{#1}}}}% not bold
5 \CustomizeMathJax{\newcommand{\mathbfcal}[1]{\boldsymbol{\mathcal{#1}}}}
6 \CustomizeMathJax{\newcommand{\mathbffrak}[1]{\boldsymbol{\mathfrak{#1}}}}
7 \CustomizeMathJax{\newcommand{\mathbfscr}[1]{\boldsymbol{\mathscr{#1}}}}% not bold
8
9 \IfPackageLoadedWithOptionsTF{mathalpha}{oldbold}
10 {
11 \CustomizeMathJax{\newcommand{\mathbbb}[1]{\boldsymbol{\mathbb{#1}}}}% not bold
12 \CustomizeMathJax{\newcommand{\mathbcal}[1]{\boldsymbol{\mathcal{#1}}}}
13 \CustomizeMathJax{\newcommand{\mathbfrak}[1]{\boldsymbol{\mathfrak{#1}}}}
14 \CustomizeMathJax{\newcommand{\mathbscr}[1]{\boldsymbol{\mathscr{#1}}}}% not bold
15 }{}
16 \end{warpMathJax}
```

File 282 **lwarp-mathastext.sty**

§ 391 Package **mathastext**

(Emulates or patches code by JEAN-FRANÇOIS BURNOL.)

Pkg mathastext

mathastext is used as-is for SVG math, and emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{mathastext}[2019/11/16]
```

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \ifmst@itgreek
6 %   \LWR@mathjax@addgreek@l@it{}{}
7 \else
8   \ifmst@upgreek
9     \LWR@mathjax@addgreek@l@up{}{}
10  \else
11    \ifmst@frenchmath
12      \LWR@mathjax@addgreek@l@up{}{}
13    \else
14      \ifmst@italic
15 %     \LWR@mathjax@addgreek@l@it{}{}
16     \else
17       \LWR@mathjax@addgreek@l@up{}{}
18     \fi
19   \fi
20 \fi
21 \fi
22
23 \ifcase\mst@greek@select
24   \or{\LWR@mathjax@addgreek@u@it*{}{}}
25 %   \or{\LWR@mathjax@addgreek@u@up*{}{}}
26 \fi
27
28 \CustomizeMathJax{\newcommand{\mathnormalbold}[1]{\boldsymbol{#1}}}
29 \CustomizeMathJax{\newcommand{\MathEulerBold}[1]{\boldsymbol{#1}}}
30 \CustomizeMathJax{\newcommand{\MathEuler}[1]{#1}}
31 \CustomizeMathJax{\newcommand{\MathPSymbol}[1]{#1}}
32 \CustomizeMathJax{\let\fouriervec\vec}
33 \CustomizeMathJax{\let\pvec\vec}
34 \CustomizeMathJax{\let\inodot\imath}
35 \CustomizeMathJax{\let\jnodot\jmath}
36 \CustomizeMathJax{\let\shortiff\iff}
37 \CustomizeMathJax{\let\longto\longrightarrow}
38 \CustomizeMathJax{\newcommand{\infitypsy}{\mathord{\unicode{x221E}}}}
39 \CustomizeMathJax{\newcommand{\proptopsy}{\mathrel{\unicode{x221D}}}}
40 \CustomizeMathJax{\let\prodpsy\prod}
41 \CustomizeMathJax{\let\sumpsy\sum}
42 \CustomizeMathJax{\let\MToriginalprod\prod}
43 \CustomizeMathJax{\let\MToriginalsum\sum}
44 \CustomizeMathJax{\newcommand{\DotTriangle}{\mathord{\unicode{x2234}}}}
45 \end{warpMathJax}

```

File 283 **lwarp-mathcomp.sty**

§ 392 Package **mathcomp**

(Emulates or patches code by TILMANN BÖß.)

Pkg mathcomp

mathcomp is supported as-is for SVG math, and is emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{mathcomp}[2001/01/07]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\tcohm}{\mathrm{\Omega}}}

```

```

4 \CustomizeMathJax{\newcommand{\tccelsius}{\unicode{x2103}}}
5 \CustomizeMathJax{\newcommand{\tcmu}{\mathrm{\unicode{x00B5}}}}
6 \CustomizeMathJax{\newcommand{\tcpertousand}{\unicode{x2030}}}
7 \CustomizeMathJax{\newcommand{\tcpertenthousand}{\unicode{x2031}}}
8 \CustomizeMathJax{\newcommand{\tcdegree}{\mathrm{^\circ}}}
9 \CustomizeMathJax{\newcommand{\tcdigitoldstyle}[1]{\oldstyle{#1}}}
10 \end{warpMathJax}

```

File 284 **lwarp-mathdesign.sty**

§ 393 Package **mathdesign**

(Emulates or patches code by PAUL PICHAREAU.)

Pkg mathdesign

mathdesign is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options except greekuppercase and greeklowercase. The dedicated macros for upright and italic greek letters work correctly, although the user may wish to swap the definitions for epsilon and phi.

SVG math should appear the same as the printed output.

for HTML output: 1 \LWR@ProvidesPackagePass{mathdesign}[2013/08/29]

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
5
6 \begin{warpMathJax}
7 \LWR@infoprocessingmathjax{mathdesign}

```

Default greek upright or italicized:

```

8 \if@MD@grupright
9 \LWR@mathjax@addgreek@l@up{}{}
10 \fi
11
12 \if@MD@GRupright
13 \else
14 \LWR@mathjax@addgreek@u@it*{}{}
15 \fi

```

Upright:

```

16 \LWR@mathjax@addgreek@l@up{}{up}
17 \LWR@mathjax@addgreek@u@up*{}{up}

```

Italicized:

```

18 \LWR@mathjax@addgreek@l@it{}{it}
19 \LWR@mathjax@addgreek@u@it*{}{it}

```

Adapt to mathdesign inconsistency:

```
20 \CustomizeMathJax{\let\digammaup\Digammaup}
21 \CustomizeMathJax{\renewcommand{\digammait}{\mathit{\digammaup}}}
```

Extra symbols:

```
22 \CustomizeMathJax{\newcommand{\smallin}{\mathrel{\unicode{x220A}}}}
23 \CustomizeMathJax{\newcommand{\smallowns}{\mathrel{\unicode{x220D}}}}
24 \CustomizeMathJax{\newcommand{\notsmallin}{\mathrel{\LWOverlaysymbols{/}{\unicode{x220A}}}}}
25 \CustomizeMathJax{\newcommand{\notsmallowns}{\mathrel{\LWOverlaysymbols{/}{\unicode{x220D}}}}}
26 \CustomizeMathJax{\newcommand{\rightangle}{\mathord{\unicode{x221F}}}}
```

Integrals:

```
27 \CustomizeMathJax{\newcommand{\intclockwise}{\mathop{\unicode{x2231}}\limits}}
28 \CustomizeMathJax{\newcommand{\ointclockwise}{\mathop{\unicode{x2232}}\limits}}
29 \CustomizeMathJax{\newcommand{\ointctrlockwise}{\mathop{\unicode{x2233}}\limits}}
30 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
31 \CustomizeMathJax{\newcommand{\oiiint}{\mathop{\unicode{x2230}}\limits}}
```

Math and text mode:

```
32 \CustomizeMathJax{\newcommand{\ddag}{\unicode{x2021}}}
33 \CustomizeMathJax{\newcommand{\P}{\unicode{x00B6}}}
34 \CustomizeMathJax{\newcommand{\copyright}{\unicode{x00A9}}}
35 \CustomizeMathJax{\newcommand{\dag}{\unicode{x2020}}}
36 \CustomizeMathJax{\newcommand{\pounds}{\unicode{x00A3}}}
```

Extra symbols:

```
37 \CustomizeMathJax{\newcommand{\iddots}{\mathinner{\unicode{x22F0}}}}
38 \CustomizeMathJax{\newcommand{\utimes}{\mathbin{\overline{\times}}}}
39 \CustomizeMathJax{\newcommand{\dtimes}{\mathbin{\underline{\times}}}}
40 \CustomizeMathJax{\newcommand{\udtimes}{\mathbin{\overline{\underline{\times}}}}}
41 \CustomizeMathJax{\newcommand{\leftwave}{\left\{}}
42 \CustomizeMathJax{\newcommand{\rightwave}{\right\}}}
43
44 \end{warpMathJax}
```

File 285 **lwarp-mathdots.sty**

§ 394 Package **mathdots**

(Emulates or patches code by DAN LUECKING.)

mathdots is used as-is for SVG math, and emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{mathdots}[2014/06/11]

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\iddots}{\mathinner{\unicode{x22F0}}}}
4 \CustomizeMathJax{\let\fixedddots\ddots}
5 \CustomizeMathJax{\let\fixedvdots\vdots}
6 \CustomizeMathJax{\let\fixediddots\iddots}
7 \CustomizeMathJax{\let\originalddots\ddots}
8 \CustomizeMathJax{\let\originalvdots\vdots}
9 \CustomizeMathJax{\let\originaliddots\iddots}
```

```

10 \CustomizeMathJax{\let\originalddot\ddot}
11 \CustomizeMathJax{\let\originalddd\ddd}
12 \end{warpMathJax}

```

File 286 **lwarp-mathfixs.sty**

§ 395 Package **mathfixs**

(Emulates or patches code by NIKLAS BEISERT.)

Pkg mathfixs

mathfixs is used as-is for SVG math, and is emulated for MATHJAX.



Greek letters are unchanged.

for HTML output:

```

1 \LWR@ProvidesPackagePass{mathfixs}[2018/12/30]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\frac}[2]{\tfrac{#1}{#2}}}
4 \CustomizeMathJax{\newcommand{\vfrac}[2]{\mathinner{\{ }^{\#1}\!/_{\#2}}}}
5 \CustomizeMathJax{\newcommand{\ProvideMathFix}[1]{} }
6 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
7 \CustomizeMathJax{\newcommand{\.}{\,}}
8 \end{warpMathJax}

```

File 287 **lwarp-mathpazo.sty**

§ 396 Package **mathpazo**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg mathpazo

mathpazo is used as-is for SVG math, and is emulated for MATHJAX.



limitations

The MATHJAX emulation ignores all package options. The dedicated macros for upright greek letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```

1 \LWR@ProvidesPackagePass{mathpazo}[2020/03/25]

```

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{mathpazo}
6
7 \ifpazo@slGreek
8 \LWR@mathjax@addgreek@u@it*{}{}
9 \fi
10
11 \LWR@mathjax@addgreek@u@up*{up}{}
12
13 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
14 \end{warpMathJax}

```

File 288 **lwarp-mathptmx.sty**

§ 397 Package **mathptmx**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg mathptmx

mathptmx is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options. The dedicated macros for upright greek letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output: 1 \LWR@ProvidesPackagePass{mathptmx}[2020/03/25]

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{mathptmx}
6
7 \IfPackageLoadedWithOptionsTF{mathptmx}{slantedGreek}
8   {\LWR@mathjax@addgreek@u@it*{}{}}
9   {}
10
11 \LWR@mathjax@addgreek@u@up*{up}{}}
12 \end{warpMathJax}

```

File 289 **lwarp-mathspec.sty**

§ 398 Package **mathspec**

(Emulates or patches code by ANDREW GILBERT MOSCHOU.)

Pkg mathspec

mathspec is used as-is with SVG math, and is emulated for MATHJAX.

 **quotes** Double quotes (\ " and the " character) are removed during MATHJAX emulation, but this also includes inside \text.

for HTML output: 1 \LWR@ProvidesPackagePass{mathspec}[2016/12/22]

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}

```

Neutralize double quotes (" and \"):

```
5 \booltrue{LWR@MathJax@silentquotes}
```

Sort options for out Greek emulation:

```

6 \AtBeginDocument{
7 \ifcase\eu@GreekUppercase@@value %% If Greek Uppercase Regular
8   \LWR@mathjax@addgreek@u@up*{}{}
9 \or %% If Greek Uppercase Italic
10  \LWR@mathjax@addgreek@u@it*{}{}
11 \or %% If Greek Uppercase Plain
12  \LWR@mathjax@addgreek@u@up*{}{}
13 \fi
14 \ifcase\eu@GreekLowercase@@value %% If Greek Lowercase Regular
15  \LWR@mathjax@addgreek@l@up{}{}
16 \or %% If Greek Lowercase Italic
17  \LWR@mathjax@addgreek@l@it{}{}
18 \or %% If Greek Lowercase Plain
19  \LWR@mathjax@addgreek@l@it{}{}
20 \fi
21 }

```

Swap definitions according the mathspec conditionals:

```

22 \newcommand*{\LWR@mathspec@varforms}{%
23 \eu@ifbooltrue{GreekLowercase}{
24   \eu@ifbooltrue{exchangebetaforms}{
25     \CustomizeMathJax{\let\LWRorigbeta\beta}
26     \CustomizeMathJax{\let\beta\varbeta}
27     \CustomizeMathJax{\let\varbeta\LWRorigbeta}
28   }
29   \eu@ifbooltrue{exchangeepsilonforms}{
30     \CustomizeMathJax{\let\LWRorigepsilon\epsilon}
31     \CustomizeMathJax{\let\epsilon\varepsilon}
32     \CustomizeMathJax{\let\varepsilon\LWRorigepsilon}
33   }
34   \eu@ifbooltrue{exchangethetaforms}{
35     \CustomizeMathJax{\let\LWRorigtheta\theta}
36     \CustomizeMathJax{\let\theta\vartheta}
37     \CustomizeMathJax{\let\vartheta\LWRorigtheta}
38   }
39   \eu@ifbooltrue{exchangekappaforms}{
40     \CustomizeMathJax{\let\LWRorigkappa\kappa}
41     \CustomizeMathJax{\let\kappa\varkappa}
42     \CustomizeMathJax{\let\varkappa\LWRorigkappa}
43   }
44   \eu@ifbooltrue{exchangepiforms}{
45     \CustomizeMathJax{\let\LWRorigpi\pi}
46     \CustomizeMathJax{\let\pi\varpi}
47     \CustomizeMathJax{\let\varpi\LWRorigpi}
48   }
49   \eu@ifbooltrue{exchangerhoforms}{
50     \CustomizeMathJax{\let\LWRorigrho\rho}
51     \CustomizeMathJax{\let\rho\varrho}
52     \CustomizeMathJax{\let\varrho\LWRorigrho}
53   }
54   \eu@ifbooltrue{exchangephiforms}{
55     \CustomizeMathJax{\let\LWRorigphi\phi}
56     \CustomizeMathJax{\let\phi\varphi}
57     \CustomizeMathJax{\let\varphi\LWRorigphi}
58   }
59 }
60 \eu@ifbooltrue{GreekUppercase}{
61   \eu@ifbooltrue{exchangeThetaforms}{
62     \CustomizeMathJax{\let\LWRorigTheta\Theta}

```

```

63     \CustomizeMathJax{\let\Theta\varTheta}
64     \CustomizeMathJax{\let\varTheta\LWRorigTheta}
65   }
66 }
67 }

```

Append new action to `mathspec's \AtBeginDocument` code:

```

68 \xapptocmd{\exchangeforms}
69   {\AtBeginDocument{\LWR@mathspec@varforms}}
70   {}
71   {\LWR@patcherror{mathspec}{exchangeforms}}
72
73 \end{warpMathJax}

```

File 290 **lwarp-mathtools.sty**

§ 399 Package **mathtools**

(Emulates or patches code by MORTEN HØGHOLM, LARS MADSEN.)

Pkg mathtools

 **equation numbering**

`mathtools` is patched for use by `lwarp`. Emulation macros are provided for `MATHJAX`.

`showonlyrefs` is disabled, as it conflicts with `cleveref`, which is used by `lwarp`. Equation numbers may not match the print version.

 **italic correction** `mathic` is not emulated for HTML.

 **MATHJAX** If using `MATHJAX`:

- `mathtools disallowspaces` does not work for `MATHJAX`. Protect brackets which are not optional arguments, such as:

```

\begin{gathered}{}
[p]=1 . . .
\end{gathered}

```

- `showonlyrefs` does not work in `MATHJAX`, and will result in a difference in equation numbering compared to the print version.
- `alignat` in `MATHJAX` requires math mode, but in `LATEX` it doesn't. It may be required to use `warpHTML` and `warpprint` to isolate a version for each mode.
- `\DeclarePairedDelimiter` and related must be in the preamble before `\begin{document}`.

for HTML output: 1 `\LWR@ProvidesPackagePass{mathtools}[2018/01/08]`

2 `\RequirePackage{graphicx}`

3 `\MHInternalSyntaxOn`

Forces `showonlyrefs` off because `lwarp` uses `cleveref`, which is not compatible with `showonlyrefs`.

```

4 \renewcommand*{\MT_showonlyrefs_true:}{%
5   \PackageWarningNoLine{lwarp}
6   {%
7     Mathtools \space showonlyrefs \space conflicts \space
8     with \space cleveref,\MessageBreak
9     which \space is \space used \space by \space lwarp, \space
10    so \space showonlyrefs \space is\MessageBreak
11    forced \space off. \space\space
12    Equation \space numbers \space may \space not \space match%
13  }
14  \MT_showonlyrefs_false:
15 }
16 \mathtoolsset{showonlyrefs=false}

```

Forces math italic correction off. Not patched for lwarp.

```

17 \renewcommand*{\MT_mathic_true:}{\MT_mathic_false:}
18 \mathtoolsset{mathic=false}

```

```

19 \MHInternalSyntaxOff

```

For MATHJAX.

The MATHJAX package is used, and improvements are added.

```

20 \begin{warpMathJax}
21 \CustomizeMathJax{\require{mathtools}}
22
23 \LWR@infoprocessingmathjax{mathtools}
24
25 \CustomizeMathJax{\newenvironment{crampedsubarray}[1]{}{}}
26
27 \CustomizeMathJax{\newcommand{\smashoperator}[2][\#2\limits]}
28
29 \CustomizeMathJax{\newcommand{\SwapAboveDisplaySkip}{}{}}
30
31 \CustomizeMathJax{\newcommand{\LaTeXunderbrace}[1]{\underbrace{\#1}}}
32 \CustomizeMathJax{\newcommand{\LaTeXoverbrace}[1]{\overbrace{\#1}}}
33
34
35 \CustomizeMathJax{\newcommand{\LWRmultlined}[1][\begin{multline*}]}
36 \CustomizeMathJax{\newenvironment{multlined}[1][\LWRmultlined]{\end{multline*}}}
37
38 \CustomizeMathJax{\let\LWRorigshoveleft\shoveleft}
39 \CustomizeMathJax{\renewcommand{\shoveleft}[1][\LWRorigshoveleft]}
40 \CustomizeMathJax{\let\LWRorigshoveright\shoveright}
41 \CustomizeMathJax{\renewcommand{\shoveright}[1][\LWRorigshoveright]}
42
43 \CustomizeMathJax{\newcommand{\shortintertext}[1]{\text{\#1}\notag \ \}}
44
45 \LetLtxMacro\LWR@mathtools@orig@DeclarePairedDelimiter\DeclarePairedDelimiter
46 \renewcommand{\DeclarePairedDelimiter}[3]{
47   \LWR@mathtools@orig@DeclarePairedDelimiter{\#1}{\#2}{\#3}
48 % starred:
49   \appto\LWR@customizedMathJax{\LWRbackslash()}
50   \appto\LWR@customizedMathJax{%
51     \LWRbackslash}newcommand{\LWRbackslash\macroto{name{\#1}LWRsubstar}\}%
52   }%
53   \appto\LWR@customizedMathJax[2][\%

```

```

54 \appto\LWR@customizedMathJax{\{\}%
55 \LWR@subcustomizedmathjax{##1\left##2##1\right##3}%
56 \appto\LWR@customizedMathJax{\}\}%
57 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
58% not starred:
59 \appto\LWR@customizedMathJax{\LWRbackslash()}
60 \appto\LWR@customizedMathJax{%
61 \LWRbackslash}newcommand{\LWRbackslash\macroto{name{#1}LWRsubnstar\}%
62 }%
63 \appto\LWR@customizedMathJax{[2][[]]}%
64 \appto\LWR@customizedMathJax{\{\}%
65 \LWR@subcustomizedmathjax{##1##2##1##3}%
66 \appto\LWR@customizedMathJax{\}\}%
67 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
68% user macro:
69 \appto\LWR@customizedMathJax{\LWRbackslash()}
70 \appto\LWR@customizedMathJax{%
71 \LWRbackslash}newcommand{\LWRbackslash\macroto{name{#1}\}%
72 \{\LWRbackslash}ifstar%
73 \LWRbackslash\macroto{name{#1}LWRsubstar%
74 \LWRbackslash\macroto{name{#1}LWRsubnstar%
75 \}%
76 }%
77 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
78 }
79 \@onlypreamble\DeclarePairedDelimiter
80
81% (DeclarePairedDelimiterX is already defined to use \DeclarePairedDelimiterXPP.)
82
83 \LetLtxMacro\LWR@mathtools@orig@DeclarePairedDelimiterXPP\DeclarePairedDelimiterXPP
84 \DeclareDocumentCommand{\DeclarePairedDelimiterXPP}{m O{1} m m m m m}{
85 \LWR@mathtools@orig@DeclarePairedDelimiterXPP{#1}[#2]{#3}{#4}{#5}{#6}{#7}
86% subsubstar, second opt arg
87 \appto\LWR@customizedMathJax{\LWRbackslash()}%
88 \appto\LWR@customizedMathJax{%
89 \LWRbackslash}newcommand{\LWRbackslash\macroto{name{#1}LWRsubsubstar\}%
90 }%
91 \appto\LWR@customizedMathJax{[#2]}%
92 \appto\LWR@customizedMathJax{\{\LWRbackslash}left}%
93 \LWR@subcustomizedmathjax{#3##4##7}%
94 \appto\LWR@customizedMathJax{\LWRbackslash}right}%
95 \LWR@subcustomizedmathjax{#5##6}%
96 \appto\LWR@customizedMathJax{\}\}%
97 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
98% substar, first opt arg
99 \appto\LWR@customizedMathJax{\LWRbackslash()}%
100 \appto\LWR@customizedMathJax{%
101 \LWRbackslash}newcommand{\LWRbackslash\macroto{name{#1}LWRsubstar}[1][[]]}%
102 }%
103 \appto\LWR@customizedMathJax{%
104 \{
105 \LWRbackslash}def\LWRbackslash}delimsizel\{#1\}
106 \LWRbackslash\macroto{name{#1}LWRsubsubstar
107 \}%
108 }%
109 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
110% subsubnstar, second opt arg
111 \appto\LWR@customizedMathJax{\LWRbackslash()}%
112 \appto\LWR@customizedMathJax{%
113 \LWRbackslash}newcommand{\LWRbackslash\macroto{name{#1}LWRsubsubnstar\}%

```

```

114 }%
115 \appto\LWR@customizedMathJax{[#2]}%
116 \appto\LWR@customizedMathJax{\{\LWRbackslash\}delimsize}%
117 \LWR@subcustomizedmathjax{#3#4#7}%
118 \appto\LWR@customizedMathJax{\LWRbackslash\}delimsize}%
119 \LWR@subcustomizedmathjax{#5#6}%
120 \appto\LWR@customizedMathJax{\}\}%
121 \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
122 % subnostar, first opt arg
123 \appto\LWR@customizedMathJax{\LWRbackslash()}%
124 \appto\LWR@customizedMathJax{%
125   \LWRbackslash\}newcommand{\LWRbackslash\macrotocname{#1}LWRsubnostar\}[1][]%
126 }%
127 \appto\LWR@customizedMathJax{%
128   \{
129     \LWRbackslash\}def\LWRbackslash\}delimsize\{#1\}
130     \LWRbackslash\macrotocname{#1}LWRsubsubnostar
131   \}%
132 }%
133 \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
134 % user macro:
135 \appto\LWR@customizedMathJax{\LWRbackslash()}
136 \appto\LWR@customizedMathJax{%
137   \LWRbackslash\}newcommand{\%
138     \LWRbackslash\}\macrotocname{#1}%
139   \}%
140   \{\LWRbackslash\}ifstar%
141     \LWRbackslash\}\macrotocname{#1}LWRsubstar%
142     \LWRbackslash\}\macrotocname{#1}LWRsubnostar%
143   \}%
144 }%
145 \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
146 }
147 \@onlypreamble\DeclareParedDelimiterXPP
148 \@onlypreamble\DeclareParedDelimiterX
149
150 \CustomizeMathJax{\newcommand{\vcentcolon}{\mathrel{\unicode{x2236}}}}
151
152 \LetLtxMacro\LWR@mathtools@orig@newgathered\newgathered
153 \renewcommand{\newgathered}[4]{%
154   \LWR@mathtools@orig@newgathered{#1}{#2}{#3}{#4}%
155   \appto\LWR@customizedMathJax{\LWRbackslash()}%
156   \LWR@subcustomizedmathjax{%
157     \newenvironment{#1}{\begin{gathered}}{\end{gathered}}}%
158   }%
159   \appto\LWR@customizedMathJax{\LWRbackslash)}%
160 }
161 \@onlypreamble\newgathered
162
163 \end{warpMathJax}

```

File 291 **lwarp-mattens.sty**

§ 400 Package **mattens**

(Emulates or patches code by DANIE ELS.)

Pkg mattens

mattens is used as-is for SVG math, and is emulated for MATHJAX.

```

for HTML output: 1 \LWR@ProvidesPackagePass{mattens}[2010/03/26]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\LWRmattensnull}{}}
4
5 \CustomizeMathJax{\newcommand{\LWRmattensnostar}[2][]{%
6   {#1{\LWRmattensundercmd{\LWRmattensovercmd{\LWRmattenscross{\boldsymbol{#2}}}}}}}%
7 }}
8
9 \CustomizeMathJax{\newcommand{\LWRmattensstar}[2][]{%
10  {#1{\LWRmattensundercmd{\LWRmattensovercmd{\LWRmattenscross{#2}}}}}}%
11 }}
12
13 \CustomizeMathJax{\newcommand{\LWRmattens}{
14   \ifstar\LWRmattensstar\LWRmattensnostar%
15 }}
16
17 \CustomizeMathJax{\newcommand{\aS}{%
18   \let\LWRmattenscross\LWRmattensnull%
19   \let\LWRmattensovercmd\overrightarrow%
20   \let\LWRmattensundercmd\LWRmattensnull%
21   \LWRmattens%
22 }}
23
24 \CustomizeMathJax{\newcommand{\Sa}{%
25   \let\LWRmattenscross\LWRmattensnull%
26   \let\LWRmattensovercmd\underrightarrow%
27   \let\LWRmattensundercmd\LWRmattensnull%
28   \LWRmattens%
29 }}
30
31 \CustomizeMathJax{\newcommand{\bS}{%
32   \let\LWRmattenscross\LWRmattensnull%
33   \let\LWRmattensovercmd\overline%
34   \let\LWRmattensundercmd\LWRmattensnull%
35   \LWRmattens%
36 }}
37
38 \CustomizeMathJax{\newcommand{\Sb}{%
39   \let\LWRmattenscross\LWRmattensnull%
40   \let\LWRmattensovercmd\underline%
41   \let\LWRmattensundercmd\LWRmattensnull%
42   \LWRmattens%
43 }}
44
45 \CustomizeMathJax{\newcommand{\aSa}{%
46   \let\LWRmattenscross\LWRmattensnull%
47   \let\LWRmattensovercmd\overrightarrow%
48   \let\LWRmattensundercmd\underrightarrow%
49   \LWRmattens%
50 }}
51
52 \CustomizeMathJax{\newcommand{\aSb}{%
53   \let\LWRmattenscross\LWRmattensnull%
54   \let\LWRmattensovercmd\overrightarrow%
55   \let\LWRmattensundercmd\underline%
56   \LWRmattens%
57 }}
58
59 \CustomizeMathJax{\newcommand{\bSa}{%

```

```

60 \let\LWRmattenscross\LWRmattensnull%
61 \let\LWRmattensovercmd\overline%
62 \let\LWRmattensundercmd\underline%
63 \LWRmattens%
64 }}
65
66 \CustomizeMathJax{\newcommand{\bSb}{%
67 \let\LWRmattenscross\LWRmattensnull%
68 \let\LWRmattensovercmd\overline%
69 \let\LWRmattensundercmd\underline%
70 \LWRmattens%
71 }}
72
73 \CustomizeMathJax{\newcommand{\aCSa}{%
74 \let\LWRmattenscross\tilde%
75 \let\LWRmattensovercmd\overrightarrow%
76 \let\LWRmattensundercmd\underrightarrow%
77 \LWRmattens%
78 }}
79
80 \CustomizeMathJax{\newcommand{\bCSb}{%
81 \let\LWRmattenscross\tilde%
82 \let\LWRmattensovercmd\overline%
83 \let\LWRmattensundercmd\underline%
84 \LWRmattens%
85 }}
86 \end{warpMathJax}

```

File 292 **lwarp-maybemath.sty**

§ 401 Package **maybemath**

(Emulates or patches code by ANDY BUCKLEY.)

Pkg maybemath

maybemath is used as-is for SVG math, and is emulated for MATHJAX.

 **no effect** MATHJAX is not able to detect the surrounding text font, so all maybemath macros are ignored.

for HTML output: 1 \LWR@ProvidesPackagePass{maybemath}[2005/2/22]

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\mayberm}[1]{\{#1\}}}
4 \CustomizeMathJax{\let\maybebm\mayberm}
5 \CustomizeMathJax{\let\maybeit\mayberm}
6 \CustomizeMathJax{\let\maybeitrm\mayberm}
7 \CustomizeMathJax{\let\maybeitsubscript\mayberm}
8 \CustomizeMathJax{\let\maybesf\mayberm}
9 \CustomizeMathJax{\let\maybebmsf\mayberm}
10 \end{warpMathJax}

```

File 293 **lwarp-mcaption.sty**

§ 402 Package **mcaption**

(Emulates or patches code by STEPHAN HENNIG.)

Pkg mcaption

mcaption is ignored.

for HTML output: Discard all options for lwarp-mcaption:

```
1 \LWR@ProvidesPackageDrop{mcaption}[2009/03/13]
2 \newenvironment{margincap}{}{}
3 \newcommand*{\margincapalign}{}
4 \newlength{\margincapsep}
```

File 294 **lwarp-mdframed.sty**

§ 403 Package **mdframed**

(Emulates or patches code by MARCO DANIEL, ELKE SCHUBERT.)

Pkg mdframed

mdframed is loaded with options forced to framemethod=none.

§ 403.1 **Limitations**

support Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

 **loading** When used, lwarp loads mdframed in HTML with framemethod=none.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont `theoremtitlefont` is not supported, since the following text is not in braces in the mdframed source.

ignored options `userdefinedwidth` and `align` are currently ignored.

css classes Environments created or encapsulated by mdframed are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class `|mdframedtitle|`. Subtitles are in a `<div>` of class `|mdframedsubtitle|`, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

§ 403.2 Package loading

for HTML output:

```
1 \RequirePackage{xcolor}% for \convertcolorspec
2
3 \LWR@ProvidesPackageDrop{mdframed}[2013/07/01]
```

Do not require Tikz or pstricks:

```
4 \LWR@origRequirePackage[framemethod=none]{mdframed}
```

§ 403.3 Patches

Patch to remove PDF formatting and add HTML tags:

```
5 \AtBeginDocument{
6 \def\mdf@trivlist#1{%
7 \edef\mdf@temp{%
8 % \topsep=\the\topsep\relax%
9 % \partopsep=\the\partopsep\relax%
10 % \parsep=\the\parsep\relax%
11 }%
12 \setlength{\topsep}{#1}%
13 % \topskip\z@%
14 % \partopsep\z@%
15 % \parsep\z@%
16 % \@nibrlistfalse%
17 % \@trivlist%
18 % \labelwidth\z@%
19 % \leftmargin\z@%
20 % \itemindent\z@%
21 \let\itemlabel\empty%
22 \def\makelabel##1{##1}%
23 % \item\relax\mdf@temp\relax%
24 }
25
26 \renewcommand*{\endmdf@trivlist}{%
27 \LWR@traceinfo{endmdf@trivlist}%
28 \endtrivlist%
29 \LWR@listend%
30 }
31 }% AtBeginDocument
```

§ 403.4 Initial setup

To handle CSS and paragraphs, patch code at start and end of environment and contents. `\LWR@print@raggedright` helps avoid hyphenation.

```
32 \mdfsetup{
33 startcode={\LWR@mdframedstart\LWR@print@raggedright},
34 endcode={\LWR@mdframedend},
35 startinnercode={\LWR@startpars\LWR@print@raggedright},
36 endinnercode={\LWR@stoppars},
37 }
```

§ 403.5 Color and length HTML conversion

`\LWR@mdfprintcolor`

`{\mdfcolorkey}`

Given the `mdframed` key, print the color.

```
38 \newcommand*\LWR@mdfprintcolor[1]{%
39 \convertcolorspec{named}{\@nameuse{mdf@#1}}{HTML}\LWR@tempcolor%
40 \LWR@origpound\LWR@tempcolor
41 }
```

`\LWR@mdfprintlength`

`{\mdflengthkey}`

Given the `mdframed` key, print the length.

```
42 \newcommand*\LWR@mdfprintlength[1]{%
43 \LWR@forceminwidth{\@nameuse{mdf@#1@length}}%
44 \LWR@printlength{\LWR@atleastonept}%
45 }
```

§ 403.6 Environment encapsulation

`\LWR@mdframedstart`

Actions before an `mdframe` starts.

Encapsulate a frame inside a `<div>` of the desired class.

```
46 \newcommand*\LWR@mdframedstart{%
47 \LWR@traceinfo{\LWR@mdframedstart start}%
```

Warn if starting a frame inside a ``:

```
48 \LWR@spanwarninvalid{mdframe}%
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
49 \LWR@stoppars%
```

Open a `<div>` and with custom class and custom style. A `BlockClass` environment is not used because this `<div>` is created by the `mdframed` startcode and encode settings, which do not properly nest the `<div>` inside the `mdframed` environment.

```
50 \LWR@htmltagc{div class=\textquotedbl%
51 mdframed%
52 \ifdefstring{\LWR@mdthisenv}{mdframed}}{\LWR@mdthisenv}%
53 \textquotedbl \LWR@orignewline
54 style=\textquotedbl\LWR@orignewline
```

Convert and print the background color:

```
55 background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
56 border: \LWR@mdfprintlength{linewidth} solid
57 \LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
58 border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
59 \ifbool{mdf@shadow}{%
60 box-shadow:
61 \LWR@mdfprintlength{shadowsize}
62 \LWR@mdfprintlength{shadowsize}
63 \LWR@mdfprintlength{shadowsize}
```

```

64 \LWR@mdfprintcolor{shadowcolor} ;
65 }
66 {box-shadow: none ;}
67 \LWR@orignewline

68 \textquotedbl}
69 % \LWR@htmldivclass{\LWR@mdthisenv}

```

mdframed environment may not work with the HTML versions of the following, so restore them to their originals while inside mdframed:

```

70 \LWR@select@print@hspace%
71 \renewcommand*{\rule}{\LWR@print@rule}
72 \LetLtxMacro\makebox\LWR@print@makebox%

73 \LWR@startpars%
74 \LWR@traceinfo{\LWR@mdframedstart done}%
75 }

```

\LWR@mdframedend

Actions after an mdframe ends.

After closing the <div>, globally restore to the default environment type:

```

76 \newcommand*{\LWR@mdframedend}{
77 \LWR@traceinfo{\LWR@mdframedend start}%

```

Close the custom <div>:

```

78 \LWR@htmldivclassend{\LWR@mdthisenv}

```

Reset future custom class to the default:

```

79 \gdef\LWR@mdthisenv{mdframed}

```

Resume paragraph handling:

```

80 \LWR@startpars%
81 \LWR@traceinfo{\LWR@mdframedend done}%
82 }

```

§ 403.7 Mdf framed environment

```

83 \renewenvironment{mdframed}[1][[]]{%
84 \color@begingroup%
85 \mdfsetup{userdefinedwidth=\linewidth,#1}%
86 \mdf@startcode%
87 \mdf@preenvsetting%
88 \ifdefempty{\mdf@firstframetitle}{}%
89     {\let\mdf@frametitlesave\mdf@frametitle%
90      \let\mdf@frametitle\mdf@firstframetitle%
91      }%
92 \ifvmode\nointerlineskip\fi%
93 \ifdefempty{\mdf@frametitle}{}%
94     {\mdfframedtitleenv{\mdf@frametitle}%
95      \mdf@@frametitle@use%
96      }%
97 \mdf@trivlist{\mdf@skipabove@length}%%
98 \mdf@settings%
99 % \mdf@lrbox{\mdf@splitbox@one}%
100 % \mdf@startinnercode%
101 }%
102 {%
103 % \mdf@@ignorelastdescenders%
104 \par%

```

```

105 % \unskip\ifvmode\nointerlineskip\hrule \@height\z@ \@width\hsize\fi%
106 \ifmdf@footnoteinside%
107 \def\mdf@reserveda{%
108 \mdf@footnoteoutput%
109 \mdf@endinnercode%
110 \endmdf@lrbbox%
111 \ifdefempty{\mdf@frametitle}{}%
112 {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
113 \detected@mdf@put@frame
114 }%
115 \else%
116 \def\mdf@reserveda{%
117 \mdf@endinnercode%
118 \endmdf@lrbbox%
119 \ifdefempty{\mdf@frametitle}{}%
120 {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
121 \detected@mdf@put@frame%
122 \mdf@footnoteoutput%
123 }%
124 \fi%
125 \mdf@reserveda%
126 \aftergroup\endmdf@trivlist%
127 \color@endgroup%
128 \mdf@endcode%
129 }

```

\mdf@footnoteoutput

```

130 \renewrobustcmd*\mdf@footnoteoutput{%
131 \LWR@printpendingmpfootnotes%
132 }

```

§ 403.8 Titles and subtitles

\mdfframedtitleenv

{*title*}

Place the title inside a <div> of class mdfframedtitle:

```

133 \newlength{\LWR@titleroundcorner}
134
135 \renewrobustcmd\mdfframedtitleenv[1]{%
136 \LWR@traceinfo{\LWR@mdfframedtitleenv start}%

```

Open a <div> with a custom class and custom style:

```
137 \begin{BlockClass}[%
```

Convert and print the title background color:

```

138 background:
139 \LWR@mdfprintcolor{frametitlebackgroundcolor}
140 ; \LWR@orignewline

```

Convert and print the title rule:

```

141 \ifbool{mdf@frametitlerule}{%
142 border-bottom:
143 \LWR@mdfprintlength{frametitlerulewidth}
144 solid
145 \LWR@mdfprintcolor{frametitlerulecolor}
146 ; \LWR@orignewline
147 }{}%

```

Finish the custom style and the opening <div> tag:

148]{mdframedtitle}%

Print the title inside the <div>:

149 \mdf@frametitlefont{\LWR@textcurrentfont{#1}}%

Close the <div>:

150 \end{BlockClass}%

151 \LWR@traceinfo{\LWR@mdframedtitleenv end}%

152 }

\LWR@mdfsubtitlecommon

{<sub — or — subsub>} [<options>] {<title>}

Common code for \LWR@mdfsubtitle and \LWR@mdfsubsubtitle.

Encapsulate the subtitle inside a <div> of class mdframedsubtitle:

153 \NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}

154 {% the following empty line is required

155

156 \LWR@traceinfo{\LWR@mdframedsubtitlecommon start}%

Open a <div> with a custom class and custom style:

157 \begin{BlockClass}[%

Convert and print the background color:

158 background:

159 \LWR@mdfprintcolor{#1titlebackgroundcolor}

160 ; \LWR@orignewline

Convert and print the above line:

161 \ifbool{mdf@#1titleaboveline}{%

162 border-top:

163 \LWR@mdfprintlength{#1titleabovelinewidth}

164 solid

165 \LWR@mdfprintcolor{#1titleabovelinecolor}

166 ; \LWR@orignewline

167 }{ }%

Convert and print the below line:

168 \ifbool{mdf@#1titlebelowline}{%

169 border-bottom:

170 \LWR@mdfprintlength{#1titlebelowlinewidth}

171 solid

172 \LWR@mdfprintcolor{#1titlebelowlinecolor}

173 ; \LWR@orignewline

174 }{ }%

Finish the custom style and the opening <div> tag:

175]{mdframed#1title}%

Perform the original subtitle action:

176 \IfNoValueTF{#2}

177 {\@nameuse{\LWR@origmdf#1title}{\cuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%

178 {\@nameuse{\LWR@origmdf#1title}[#2]{\cuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%

Close the <div>:

179 \end{BlockClass}%

180 \LWR@traceinfo{\LWR@mdframedsubtitlecommon end}%

181 }

```

\LWR@mdfsubtitle      [⟨options⟩] {⟨title⟩}
182 \newcommand*{\LWR@mdfsubtitle}{%
183 \LWR@mdfsubtitlecommon{sub}%
184 }
185 \let\mdfsubtitle\LWR@mdfsubtitle

```

```

\LWR@mdfsubsubtitle  [⟨options⟩] {⟨title⟩}
186 \newcommand*{\LWR@mdfsubsubtitle}{%
187 \LWR@mdfsubsubtitlecommon{subsub}%
188 }
189 \let\mdfsubsubtitle\LWR@mdfsubsubtitle

```

§ 403.9 New environments

`\LWR@mdthisenv` Stores the environment of the frame about to be created:

```

190 \newcommand*{\LWR@mdthisenv}{mdframed}

```

`\newmdenv` [⟨options⟩] {⟨env-name⟩}

Modified from the original to remember the environment.

```

191 \renewrobustcmd*\newmdenv[2][]{%
192 \newenvironment{#2}%
193 {%
194 \mdfsetup{#1}%
195 \renewcommand*{\LWR@mdthisenv}{md#2}%
196 \begin{mdframed}%
197 }
198 {\end{mdframed}}%
199 }

```

`\surroundwithmdframed` [⟨options⟩] {⟨environment⟩}

Modified from the original to remember the environment.

```

200 \renewrobustcmd*{\surroundwithmdframed}[2][]{%
201 \BeforeBeginEnvironment{#2}%
202 \renewcommand*{\LWR@mdthisenv}{md#2}%
203 \begin{mdframed}[#1]}%
204 \AfterEndEnvironment{#2}{\end{mdframed}}%
205 }

```

`\mdtheorem` [⟨mdframed-options⟩] {⟨envname⟩} [⟨numberedlike⟩] {⟨caption⟩} [⟨within⟩]

Modified from the original to remember the environment.

```

206 \DeclareDocumentCommand{\mdtheorem}{ O{} m o m o }%
207 {\ifcsdef{#2}%
208   {\mdf@PackageWarning{Environment #2 already exists\MessageBreak}}%
209   {%
210     \IfNoValueTF {#3}%
211     {%#3 not given -- number relationship
212       \IfNoValueTF {#5}%
213       {%#3+#5 not given
214         \@definecounter{#2}%
215         \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
216         \newenvironment{#2}[1][]{%

```

```

217     \refstepcounter{#2}%
218     \ifstrempy{##1}%
219     {\let\@temptitle\relax}%
220     {%
221     \def\@temptitle{\mdf@theoremseparator%
222     \mdf@theoremspace%
223     \mdf@theoremtitlefont%
224     \LWR@textcurrentfont{##1}}% lwarp
225     \mdf@thm@caption{#2}{#4}{\csname the#2\endcsname}{##1}}%
226     }%
227 \begin{mdframed}[#1,frametitle={\strut#4 \csname the#2\endcsname%
228     \@temptitle}]]%
229     {\end{mdframed}}%
230 \newenvironment{#2*}[1][]{%
231     \ifstrempy{##1}{\let\@temptitle\relax}{\def\@temptitle{: \ ##1}}%
232     \begin{mdframed}[#1,frametitle={\strut#4 \@temptitle}]]%
233     {\end{mdframed}}%
234     }%
235 {%#5 given -- reset counter
236 \definecounter{#2}\@newctr{#2}[#5]%
237 \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
238 \expandafter\xdef\csname the#2\endcsname{%
239     \expandafter\noexpand\csname the#5\endcsname \@thmcountersep%
240     \@thmcounter{#2}}%
241 \newenvironment{#2}[1][]{%
242     \refstepcounter{#2}%
243     \ifstrempy{##1}%
244     {\let\@temptitle\relax}%
245     {%
246     \def\@temptitle{\mdf@theoremseparator%
247     \mdf@theoremspace%
248     \mdf@theoremtitlefont%
249     \LWR@textcurrentfont{##1}}% lwarp
250     \mdf@thm@caption{#2}{#4}{\csname the#2\endcsname}{##1}}%
251     }
252 \begin{mdframed}[#1,frametitle={\strut#4 \csname the#2\endcsname%
253     \@temptitle}]]%
254     {\end{mdframed}}%
255 \newenvironment{#2*}[1][]{%
256     \ifstrempy{##1}%
257     {\let\@temptitle\relax}%
258     {%
259     \def\@temptitle{\mdf@theoremseparator%
260     \mdf@theoremspace%
261     \mdf@theoremtitlefont%
262     \LWR@textcurrentfont{##1}}% lwarp
263     \mdf@thm@caption{#2}{#4}{\csname the#2\endcsname}{##1}}%
264     }%
265     \begin{mdframed}[#1,frametitle={\strut#4 \@temptitle}]]%
266     {\end{mdframed}}%
267     }%
268     }%
269 {%#3 given -- number relationship
270 \global\@namedef{the#2}{\@nameuse{the#3}}%
271 \newenvironment{#2}[1][]{%
272     \refstepcounter{#3}%
273     \ifstrempy{##1}%
274     {\let\@temptitle\relax}%
275     {%
276     \def\@temptitle{\mdf@theoremseparator%

```

```

277             \mdf@theoremspace%
278             \mdf@theoremtitlefont%
279             \LWR@textcurrentfont{##1}}% lwarp
280         \mdf@thm@caption{#2}{#4}{\csname the#2\endcsname}{##1}}%
281         }
282     \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
283             \@temptitle}]]%
284         {\end{mdframed}}%
285     \newenvironment{#2*}[1][]{%
286         \ifstrempy{##1}{\let\@temptitle\relax}{\def\@temptitle{: \ ##1}}%
287         \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]]%
288         {\end{mdframed}}%
289     }%
290 \BeforeBeginEnvironment{#2}{\renewcommand*\LWR@mdthisenv}{md#2}}% lwarp
291 \BeforeBeginEnvironment{#2*}{\renewcommand*\LWR@mdthisenv}{md#2}}% lwarp
292 }%
293 }

```

\newmdtheoremenv

[<1: *mdframed-options*>] {<2: *envname*>} [<3: *numberedlike*>] {<4: *caption*>}
 [<5: *within*>]

Modified from the original to remember the environment.

```

294 \DeclareDocumentCommand\newmdtheoremenv{0}{ m o m o }{%
295   \ifboolexpr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }%
296     {\newtheorem{#2}{#4}}%
297     {%
298       \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}%
299       \IfValueT{#5}{\newtheorem{#2}{#4}[#5]}%
300     }%
301 \BeforeBeginEnvironment{#2}{%
302 \renewcommand*\LWR@mdthisenv}{md#2}%
303 \begin{mdframed}[#1]}%
304 \AfterEndEnvironment{#2}{%
305 \end{mdframed}}%
306 }

```

File 295 **lwarp-mdwmath.sty**

§ 404 Package **mdwmath**

(Emulates or patches code by MARK WOODING.)

Pkg mdwmath

mdwmath is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{mdwmath}[1996/04/11]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\let\LWRmdwmathsqrt\sqrt}
4 \CustomizeMathJax{\renewcommand{\sqrt}{\ifstar\LWRmdwmathsqrt\LWRmdwmathsqrt}}
5 \CustomizeMathJax{\newcommand{\bitand}{\mathbin\&}}
6 \CustomizeMathJax{\def\bitor{\mathbin\mid}}
7 \CustomizeMathJax{\def\dblort{\mathbin{\mid\mid}}}
8 \CustomizeMathJax{\def\dblortand{\mathbin{\mathrel\bitand\mathrel\bitand}}}
9 \end{warpMathJax}

```

File 296 **lwarp-media9.sty**

§ 405 Package **media9**

Pkg media9

media9 is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addressource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YOUTUBE™ video, use an “embedded” URL with .../embed/... instead of .../v/...

 **& in a URL** Many special characters are converted to regular catcode 12 characters for use inside a URL. & is used in the flash variables fields, which are split with xparse \SplitList, which does not seem to work with a catcode 12 divider token, so & is not converted to catcode 12, and will not work in a URL with media9. Using & in a URL in a flashvars field may also cause parsing problems with print output, as well.

for HTML output: 1 \LWR@ProvidesPackageDrop{media9}[2019/02/21]

2 \LWR@origRequirePackage{lwarp-common-multimedia}

```

3
4 \RequirePackage{xkeyval}

```

\addmediapath

{*<path>*}

Supported.

```

5 \newcommand*\LWR@medianine@path{}
6
7 \newcommand*\addmediapath[1]{\appto\LWR@medianine@path{#1}}

```

The options and poster text are reused in several places.

```

8 \newcommand*\LWR@medianine@postertext{}
9 \newcommand*\LWR@medianine@options{}

```

Each addressource can generate a multimedia object.

```

10 \define@key{LWR@medianine}{addressource}{%
11   \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]
12     {\LWR@medianine@postertext}
13     {#1}
14 }

```

Each flashvars source can generate a multimedia object.

```

15 \newcommand*\LWR@medianine@flashvarsb[1]{%
16   \IfBeginWith{#1}{source=}{%
17     \StrGobbleLeft{#1}{7}[\LWR@tempone]%
18     \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
19       {\LWR@medianine@postertext}%
20       {\LWR@tempone}%
21   }{%
22     \IfBeginWith{#1}{src=}{%
23       \StrGobbleLeft{#1}{4}[\LWR@tempone]%
24       \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
25         {\LWR@medianine@postertext}%
26         {\LWR@tempone}%
27     }{%
28   }
29
30 \NewDocumentCommand{\LWR@medianine@flashvars}{ >{\SplitList{&}} m }{%
31   \ProcessList {#1}{\LWR@medianine@flashvarsb}%
32 }
33
34 \define@key{LWR@medianine}{flashvars}{%
35   \LWR@medianine@flashvars{#1}%
36 }

```

\includemedia

[*<options>*] [*<poster text>*] [*<file or url>*]

```

37 \newcommand*\LWR@includemediab[3][[]]{%
38   \let\input@path\LWR@medianine@path%
39   \renewcommand*\LWR@medianine@options{#1}%
40   \renewcommand*\LWR@medianine@postertext{#2}%
41   \setkeys*LWR@medianine{#1}%
42   \IfBeginWith{#3}{http}{\LWR@multimedia[#1]{#2}{#3}}{%
43     \IfBeginWith{#3}{HTTP}{\LWR@multimedia[#1]{#2}{#3}}{%
44     \IfBeginWith{#3}{ftp}{\LWR@multimedia[#1]{#2}{#3}}{%

```

```

45 \IfBeginWith{#3}{FTP}{\LWR@multimedia[#1]{#2}{#3}}{%
46   }}}%
47 \endgroup%
48 }
49
50 \newrobustcmd*\includemedia{%
51   \begingroup%
52   \LWR@linkmediacatcodes%
53   \LWR@includemediab%
54 }

```

`\mediabutton`

`[<options>] {<text>}`

Ignored.

```
55 \newcommand*\mediabutton[2][{}]
```

File 297 **lwarp-memhfixc.sty**

§ 406 Package **memhfixc**

Pkg memhfixc

memhfixc is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{memhfixc}[2013/05/30]

File 298 **lwarp-menukeys.sty**

§ 407 Package **menukeys**

Pkg menukeys

(Emulates or patches code by TOBIAS WEH.)

menukeys is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{menukeys}[2020/12/19]

Patch to use a `lateximage` whose `alt` text is the contents of this use of the macro. A hash on these contents allows the reuse of the image for each instance of the same contents.

```

2 \xpatchcmd\tw@define@menu@macro@
3   {\@nameuse{tw@style@#4@pre}}
4   {%
5     \begin{lateximage}*\detokenize{##2}}%
6     \@nameuse{tw@style@#4@pre}%
7   }
8   {}
9   {\LWR@patcherror{menukeys}{tw@define@menu@macro@}}
10
11 \xpatchcmd\tw@define@menu@macro@
12   {\@nameuse{tw@style@#4@post}}
13   {%
14     \@nameuse{tw@style@#4@post}%
15     \end{lateximage}%
16   }

```

```

17 {}
18 {\LWR@patcherror{menukeys}{tw@define@menu@macro@ B}}

```

Patch the existing macros:

```

19 \renewmenumacro{\menu}[>]{menus}
20 \renewmenumacro{\directory}[/]{paths}
21 \renewmenumacro{\keys}[+]{roundedkeys}

```

File 299 **lwarp-metalogo.sty**

§ 408 Package **metalogo**

(Emulates or patches code by ANDREW GILBERT MOSCHOU.)

Pkg metalogo

metalogo is used in print mode, and emulated in HTML.

for HTML output:

```

1 \LWR@ProvidesPackagePass{metalogo}[2010/05/29]

2 \newcommand*\LWR@HTML@setlogokern}[2]{}
3 \newcommand*\LWR@HTML@setlogodrop}[2][XeTeX]{}
4 \newcommand*\LWR@HTML@setLaTeXa}[1]{}
5 \newcommand*\LWR@HTML@setLaTeXee}[1]{}
6 \newcommand*\LWR@HTML@seteverylogo}[1]{}
7 \newcommand*\LWR@HTML@everylogo}[1]{}
8
9 \LWR@formatted{setlogokern}
10 \LWR@formatted{setlogodrop}
11 \LWR@formatted{setLaTeXa}
12 \LWR@formatted{setLaTeXee}
13 \LWR@formatted{seteverylogo}
14 \LWR@formatted{everylogo}

```

File 300 **lwarp-metalogox.sty**

§ 409 Package **metalogox**

(Emulates or patches code by BRIAN DUNN.)

Pkg metalogox

metalogox is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{metalogox}[2019/01/20]

```

\AtBeginDocument, adjust the logo setting according to the font which is active at that moment.

```

2 \AtBeginDocument{
3   \let\LWR@metalogox@currentformatting\LWR@formatting
4   \renewcommand*\LWR@formatting}{print}%
5   \autoadjustlogos*
6   \let\LWR@formatting\LWR@metalogox@currentformatting
7 }

```

File 301 **lwarp-mhchem.sty**

§ 410 Package **mhchem**

(Emulates or patches code by MARTIN HENSEL.)

Pkg mhchem

mhchem is patched for use by lwarp.

without MATHJAX Without MATHJAX, mhchem expressions are converted to svg math. Inline expressions use hashed filenames to allow reuse, and assume that any mhchem options are global.

MATHJAX with mhchem extension For MATHJAX, the mhchem extension is used if the mhchem expression is used inside a math expression:

```
 $\ce{C6H5-CHO}$ 
```

To force the use of svg math for an expression which does not work with MATHJAX, place the expression between `\displaymathother` and `\displaymathnormal`:

```
\displaymathother
\[ \ce{ . . . } \] . . . $ \ce { . . . } $
\displaymathnormal
```

not inside math

If *not* used inside a math expression, lwarp converts standalone mhchem expressions into svg math images.

 **nested math** When producing HTML output without the MATHJAX mhchem extension, lwarp does not support the use of nested dollar signs in mhchem expressions.

For some examples from the mhchem manual, change as follows:

<code>$\ce{NaOH(aq, \infty)}$</code>	% old
<code>$\ce{NaOH(aq, \infty)}$</code>	% new
<code>$\ce{Fe(CN)_{\frac{6}{2}}}$</code>	% old
<code>$\ce{Fe(CN)_{\frac{6}{2}}}$</code>	% new
<code>$\ce{NO_x}$</code>	% old
<code>$\ce{NO_x}$</code>	% new
<code>$\ce{NO_x}$</code>	% old
<code>$\ce{NO_x}$</code>	% new
<code>$\ce{\mathit{cis}[PtCl2(NH3)2]}$</code>	% old
<code>$\ce{\mathit{cis}[PtCl2(NH3)2]}$</code>	% new

for HTML output: 1 \LWR@ProvidesPackagePass{mhchem}[2018/06/22]

The original definition of `\ce`:

```
2 \LetLtxMacro\LWR@mhchem@orig\ce
```

The new definition, called from the new `\ce` after math shift is set. The starred `lateximage` uses a hashed filename for the svg image. The `alt` tag is set to the `mhchem` expression.

```

3 \newcommand{\LWR@mhchem@HTML@ce}[1]{%
4   \LWR@findcurrenttextcolor% sets \LWR@tempcolor
5   \ifbool{\LWR@xfakebold}%
6     {\def\LWR@tempone{Y}}%
7     {\def\LWR@tempone{N}}%
8   \begin{lateximage}%
9     *%
10    [%
11      \textbackslashash{%
12        ce%
13        \{\LWR@HTMLsanitizedetokenized{\detokenize{#1}}\}%
14      ]%
15    *%
16    [%
17      FM\LWR@family%
18      SR\LWR@series%
19      SH\LWR@shape%
20      SHC\LWR@shapecaps%
21      CL\LWR@tempcolor%
22      FB\LWR@tempone% xfakebold
23    ]%
24    \LWR@setcurrentfont%
25    \LWR@mhchem@origce{#1}%
26    \end{lateximage}%
27    \endgroup%
28    \addtocounter{\LWR@mhchem@cedepth}{-1}%
29 }

```

Only set math shift if outer depth:

```

30 \newcounter{\LWR@mhchem@cedepth}
31 \setcounter{\LWR@mhchem@cedepth}{0}

```

The new `\ce`. Sets math shift then continues.

```

32 \renewcommand{\ce}{%
33   \begingroup%
34   \ifnumequal{\value{\LWR@mhchem@cedepth}}{0}{%
35     \catcode'\$=3% math shift
36   }{%
37     \addtocounter{\LWR@mhchem@cedepth}{1}%
38     \LWR@mhchem@HTML@ce%
39 }

```

The original definition of `\cesplit`:

```

40 \LetLtxMacro\LWR@mhchem@origcesplit\cesplit

```

The new definition, called from the new `\cesplit` after math shift is set. The starred `lateximage` uses a hashed filename for the svg image. The `alt` tag is set to the `mhchem` expression.

```

41 \newcommand*{\LWR@mhchem@HTML@cesplit}[2]
42 {%
43   \LWR@findcurrenttextcolor% sets \LWR@tempcolor

```

```

44 \ifbool{LWR@xfakebold}%
45   {\def\LWR@tempone{Y}}%
46   {\def\LWR@tempone{N}}%
47 \begin{lateximage}%
48   *%
49   [%
50     \textbackslashash{}%
51     cesplit%
52     {\LWR@HTMLsanitizedetokenized{\detokenize{#2}}}%
53   ]%
54   *%
55   [%
56     FM\LWR@f@family%
57     SR\LWR@f@series%
58     SH\LWR@f@shape%
59     SHC\LWR@f@shapecaps%
60     CL\LWR@tempcolor%
61     FB\LWR@tempone% xfakebold
62   ]%
63 \LWR@setcurrentfont%
64 \LWR@mhchem@origcesplit{#1}{#2}%
65 \end{lateximage}%
66 \endgroup%
67 }

```

Only set math shift if outer depth:

```

68 \newcounter{LWR@mhchem@cesplitdepth}
69 \setcounter{LWR@mhchem@cesplitdepth}{0}

```

The new `\cesplit`. Sets math shift then continues.

```

70 \renewcommand{\cesplit}{%
71   \begingroup%
72   \ifnumequal{\value{LWR@mhchem@cesplitdepth}}{0}{%
73     \catcode'\$=3% math shift
74   }{%
75     \addtocounter{LWR@mhchem@cesplitdepth}{1}%
76     \LWR@mhchem@HTML@cesplit%
77 }

```

Resore originals inside a lateximage:

```

78 \appto\LWR@restoreorigformatting{%
79 \LetLtxMacro\ce\LWR@mhchem@origce%
80 \LetLtxMacro\cesplit\LWR@mhchem@origcesplit%
81 }
82
83 \begin{warpMathJax}
84 \CustomizeMathJax{\require{mhchem}}
85 \end{warpMathJax}

```

File 302 **lwarp-microtype.sty**

§ 411 Package **microtype**

(Emulates or patches code by R SCHLICHT.)

Pkg microtype

microtype is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output:

Discard all options for lwarp-microtype:

```

1 \LWR@ProvidesPackageDrop{microtype}[2018/01/14]

2 \DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m}{}
3 \DeclareDocumentCommand{\UseMicrotypeSet}{o m}{}
4 \DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m}{}
5 \DeclareDocumentCommand{\SetProtrusion}{o m m}{}
6 \DeclareDocumentCommand{\SetExpansion}{o m m}{}
7 \DeclareDocumentCommand{\SetTracking}{o m m}{}
8 \DeclareDocumentCommand{\SetExtraKerning}{o m m}{}
9 \DeclareDocumentCommand{\SetExtraSpacing}{o m m}{}
10 \DeclareDocumentCommand{\DisableLigatures}{o m}{}
11 \DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m}{}
12 \DeclareDocumentCommand{\DeclareMicrotypeVariants}{m}{}
13 \DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m}{}
14 \DeclareDocumentCommand{\LoadMicrotypeFile}{m}{}
15 \DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m}{}
16 \DeclareDocumentCommand{\microtypesetup}{m}{}
17 \DeclareDocumentCommand{\microtypecontext}{m}{}
18 \DeclareDocumentCommand{\textmicrotypecontext}{m m}{#2}
19 \IfPackageLoadedTF{letterspace}{\let\MT@textls\relax}{%
20 \DeclareDocumentCommand{\lsstyle}{}{}
21 \DeclareDocumentCommand{\textls}{o +m}{}
22 \DeclareDocumentCommand{\lslig}{m}{#1}
23 }
24 \def\DeclareMicrotypeSet#1#{\@gobbletwo}
25 \def\DeclareMicrotypeVariants#1#{\@gobble}
26 \@onlypreamble\DeclareMicrotypeSet
27 \@onlypreamble\UseMicrotypeSet
28 \@onlypreamble\DeclareMicrotypeSetDefault
29 \@onlypreamble\DisableLigatures
30 \@onlypreamble\DeclareMicrotypeVariants
31 \@onlypreamble\DeclareMicrotypeBabelHook

```

File 303 **lwarp-midfloat.sty**

§ 412 Package **midfloat**

(Emulates or patches code by SIGITAS TOLUŠIS.)

Pkg midfloat

midfloat is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{midfloat}[2012/05/29]

2 \newenvironment{strip}[1][[]]{}{}
3 \newskip\stripsep

```

File 304 **lwarp-midpage.sty**

§ 413 Package **midpage**

Pkg midpage

midpage is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{midpage}[2009/09/03]

```

2 \newenvironment{midpage}
3 {\begin{BlockClass}[%
4   \LWR@print@mbx{margin-top:6ex} ; \LWR@print@mbx{margin-bottom:6ex}%
5 ]{midpage}}
6 {\end{BlockClass}}
```

File 305 **lwarp-minibox.sty**

§ 414 Package **minibox**

Pkg minibox

(Emulates or patches code by WILL ROBERTSON.)

minibox is patched for use by lwarp.

Due to HTML limitations regarding paragraphs and <div>s, miniboxes inline with other text will appear on their own line.

for HTML output: 1 \LWR@ProvidesPackagePass{minibox}[2013/06/21]

```

2 \ExplSyntaxOn
3 \newcommand\LWR@HTML@minibox[2][]{%
4   \LWR@stoppars%
5   \group_begin:
6   \keys_set:nn {minibox} {#1}
7   \bool_if:NTF \l_minibox_frame_bool
8   {
9     \setlength\fbxrule{\l_minibox_rule_dim}
10    \setlength\fbxsep{\l_minibox_pad_dim}
11    \fbxBlock{%
12      \begin{tabular}[\l_minibox_tabular_valign_tl]%
13        {\l_minibox_tabular_preamble_tl}
14        {#2}
15      \end{tabular}
16    }%
17  }
18  {
19    \begin{BlockClass}[display:inline-block]{minibox}
20    \begin{tabular}[\l_minibox_tabular_valign_tl]%
21      {\l_minibox_tabular_preamble_tl}
22      {#2}
23    \end{tabular}
24    \end{BlockClass}
25  }
26  \group_end:
```

```

27 \LWR@startpars%
28 }
29 \ExplSyntaxOff
30
31 \LWR@formatted{minibox}

```

File 306 **lwarp-minitoc.sty**

§ 415 Package **minitoc**

Pkg minitoc

minitoc is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{minitoc}[2018/07/12]

mtcoff disables minitoc.

```
2 \usepackage{mtcoff}
```

File 307 **lwarp-minted.sty**

§ 416 Package **minted**

Pkg minted

(Emulates or patches code by GEOFFREY M. POORE.)

minted is patched for use by lwarp.

 **limitations** mathescape and highlightlines don't work. Line numbers on the right will not be aligned. Due to *pdf_latex*, extra spaces may appear in broken lines if other formatting is included.

for HTML output: 1 \LWR@ProvidesPackagePass{minted}[2021/12/24]

```

2 \xpatchcmd{\minted}
3   {\setkeys{minted@opt@cmd}{#1}}
4   {%
5     \setkeys{minted@opt@cmd}{%
6       #1,%
7       mathescape=false,breaklines,texcomments=false,highlightlines={}%
8     }%
9   }
10  {}
11  {\LWR@patcherror{minted}{minted}}
12
13 \xpatchcmd{\mintinline}
14   {\setkeys{minted@opt@cmd}{#1}}
15   {\setkeys{minted@opt@cmd}{%
16     #1,%
17     mathescape=false,breaklines,texcomments=false,highlightlines={}%
18   }%
19   }
20   {}
21   {\LWR@patcherror{minted}{mintinline}}
22
23 \xpatchcmd{\mint}

```

```

24   {\setkeys{minted@opt@cmd}{#1}}
25   {%
26       \setkeys{minted@opt@cmd}{%
27           #1,%
28           mathescape=false,breaklines,texcomments=false,highlightlines={}%
29       }%
30   }
31   {}
32   {\LWR@patcherror{minted}{mint}}
33
34 \xpatchcmd{\inputminted}
35   {\setkeys{minted@opt@cmd}{#1}}
36   {\setkeys{minted@opt@cmd}{%
37       #1,%
38       mathescape=false,breaklines,texcomments=false,highlightlines={}%
39   }%
40   }
41   {}
42   {\LWR@patcherror{minted}{inputminted}}
43
44 \renewenvironment{minted@snugshade*}[1]%
45 {%
46   \colorlet{shadecolor}{#1}%
47   \begin{snugshade*}%
48 }
49 {%
50   \end{snugshade*}%
51 }

```

File 308 **lwarp-mismath.sty**

§ 417 Package **mismath**

(Emulates or patches code by ANTOINE MISSIER.)

Pkg mismath

mismath is patched for SVG math, and emulated for MATHJAX.

 **MATHJAX** `\enumber`, `\inumber`, `\jnumber`, and `\pinumber` are ignored for MATHJAX, except that `\itpi` is made available as a clone of `\pi`.

For MATHJAX, `\boldvect` and `\arrowvect` are honored if in the preamble.

If `\boldvectcommand` is set to `\mathbf` in the preamble, it will be used for MATHJAX, otherwise it will default to `\mathit`. `\boldvectcommand` may also be set with `\CustomizeMathJax` in the preamble. See section 8.7.6. Note that as of this writing there is not a bold italic font across all MATHJAX fonts.

If `\probastyle` is set to `\mathbb` in the preamble, it will be used for MATHJAX, otherwise it will default to `\mathrm`. `\probastyle` may be set with `\CustomizeMathJax` in the preamble.

If `\mathset` is set to `\mathbb` in the preamble, it will be used for MATHJAX, otherwise it will default to `\mathbf`. `\mathset` may be set with `\CustomizeMathJax` in the preamble.

for HTML output: 1 \LWR@ProvidesPackagePass{mismath}[2019/12/27]

For MATHJAX, used in the HTML comment before the environment.

```

2 \ifbool{mathjax}{
3   \RenewEnviron{mathcols}{%
4     \preto\BODY{\begin{aligned}\displaystyle}
5     \appto\BODY{\end{aligned}}
6     \expandafter\(\\BODY\)
7   }
8 }% mathjax

```

For svg math. The lateximage restores the original defintion of the math environment.

```

9 {% svg
10  \renewenvironment{mathcols}{
11    \begin{lateximage}
12    \begin{math}
13    \begin{aligned}\displaystyle
14  }{
15    \end{aligned}%
16    \end{math}
17    \end{lateximage}
18  }
19 }% svg
20
21 \renewcommand{\changeacol}{
22   \end{aligned} \quad
23   \begin{aligned}\displaystyle
24 }
25
26 \begin{warpMathJax}
27 \CustomizeMathJax{\newcommand{\mathup}[1]{\mathrm{#1}}}
28 \CustomizeMathJax{\newcommand{\e}{\mathrm{e}}}
29 \CustomizeMathJax{\newcommand{\i}{\mathrm{i}}}
30 \CustomizeMathJax{\newcommand{\j}{\mathrm{j}}}
31
32 \CustomizeMathJax{\newcommand{\boldvect}{}{}}
33 \CustomizeMathJax{\newcommand{\arrowvect}{}{}}
34 \CustomizeMathJax{\newcommand{\pinumber}[1][{}]}
35 \CustomizeMathJax{\newcommand{\hvect}[1]{\vec{\vphantom{h}#1}}}
36 \CustomizeMathJax{\newcommand{\hvec}[1]{\vec{\vphantom{t}#1}}}
37 \CustomizeMathJax{%
38   \newcommand{\norm}[1]{\left\|\right\|_{1}\left\|\right\|_{1}\right\|\right\|}
39 }
40 \CustomizeMathJax{\newcommand{\di}{\mathop{\!|\!|}\mathrm{d}}}
41
42 \CustomizeMathJax{\newcommand{\P}{\operatorname{\probastyle{P}}}}
43 \CustomizeMathJax{\newcommand{\E}{\operatorname{\probastyle{E}}}}
44 \CustomizeMathJax{\newcommand{\V}{\operatorname{\probastyle{V}}}}
45 \CustomizeMathJax{\newcommand{\Par}{\unicode{x00B6}}}
46
47 \CustomizeMathJax{\DeclareMathOperator{\adj}{adj}}
48 \CustomizeMathJax{\DeclareMathOperator{\Aut}{Aut}}
49 \CustomizeMathJax{\DeclareMathOperator{\Conv}{Conv}}
50 \CustomizeMathJax{\DeclareMathOperator{\cov}{cov}}
51 \CustomizeMathJax{\DeclareMathOperator{\Cov}{Cov}}
52 \CustomizeMathJax{\newcommand{\curl}{\operatorname{\vect{\mathrm{curl}}}}}
53 \CustomizeMathJax{\DeclareMathOperator{\divg}{div}}
54 \CustomizeMathJax{\DeclareMathOperator{\End}{End}}
55

```

```

56 \CustomizeMathJax{\DeclareMathOperator{\erf}{erf}}
57 \CustomizeMathJax{\newcommand{\grad}{\operatorname{\vect{\mathrm{grad}}}}}
58 \CustomizeMathJax{\DeclareMathOperator{\id}{id}}
59 \CustomizeMathJax{\DeclareMathOperator{\Id}{Id}}
60 \CustomizeMathJax{\DeclareMathOperator{\im}{im}}
61 \CustomizeMathJax{\let\oldIm\Im}
62 \CustomizeMathJax{\renewcommand{\Im}{\operatorname{Im}}}
63 \CustomizeMathJax{\DeclareMathOperator{\lb}{lb}}
64 \CustomizeMathJax{\DeclareMathOperator{\lcm}{lcm}}
65
66 \CustomizeMathJax{\DeclareMathOperator{\rank}{rank}}
67 \CustomizeMathJax{\let\oldRe\Re}
68 \CustomizeMathJax{\renewcommand{\Re}{\operatorname{Re}}}
69 \CustomizeMathJax{\newcommand{\rot}{\operatorname{\vect{\mathrm{rot}}}}}
70 \CustomizeMathJax{\DeclareMathOperator{\sgn}{sgn}}
71 \CustomizeMathJax{\DeclareMathOperator{\spa}{span}}
72 \CustomizeMathJax{\DeclareMathOperator{\tr}{tr}}
73 \CustomizeMathJax{\DeclareMathOperator{\Var}{Var}}
74 \CustomizeMathJax{\DeclareMathOperator{\Zu}{Z}}
75
76 \CustomizeMathJax{\DeclareMathOperator{\arccot}{arccot}}
77 \CustomizeMathJax{\DeclareMathOperator{\sech}{sech}}
78 \CustomizeMathJax{\DeclareMathOperator{\csch}{csch}}
79 \CustomizeMathJax{\DeclareMathOperator{\arsinh}{arsinh}}
80 \CustomizeMathJax{\DeclareMathOperator{\arcosh}{arcosh}}
81 \CustomizeMathJax{\DeclareMathOperator{\artanh}{artanh}}
82 \CustomizeMathJax{\DeclareMathOperator{\arcoth}{arcoth}}
83 \CustomizeMathJax{\DeclareMathOperator{\arsech}{arsech}}
84 \CustomizeMathJax{\DeclareMathOperator{\arcsch}{arcsch}}
85
86 \CustomizeMathJax{\DeclareMathOperator{\bigO}{\mathcal{O}}}
87 \CustomizeMathJax{\DeclareMathOperator{\bigo}{O}}
88 \CustomizeMathJax{\DeclareMathOperator{\lito}{o}}
89
90 \CustomizeMathJax{\newcommand{\R}{\mathset{R}}}
91 \CustomizeMathJax{\newcommand{\C}{\mathset{C}}}
92 \CustomizeMathJax{\newcommand{\N}{\mathset{N}}}
93 \CustomizeMathJax{\newcommand{\Z}{\mathset{Z}}}
94 \CustomizeMathJax{\newcommand{\Q}{\mathset{Q}}}
95 \CustomizeMathJax{\newcommand{\F}{\mathset{F}}}
96 \CustomizeMathJax{\newcommand{\K}{\mathset{K}}}
97
98 \CustomizeMathJax{\newcommand{\ds}{\displaystyle}}
99 \CustomizeMathJax{\newcommand{\dlim}{\lim\limits}}
100 \CustomizeMathJax{\newcommand{\dsum}{\sum\limits}}
101 \CustomizeMathJax{\newcommand{\dprod}{\prod\limits}}
102 \CustomizeMathJax{\newcommand{\dcup}{\bigcup\limits}}
103 \CustomizeMathJax{\newcommand{\dcap}{\bigcap\limits}}
104 \CustomizeMathJax{\newcommand{\lbar}{\overline}}
105 \CustomizeMathJax{\newcommand{\hlbar}[1]{\overline{\vphantom{h}\#1}}}
106 \CustomizeMathJax{\newcommand{\eqdef}{\stackrel{\mathrm{def}}{=}}}
107 \CustomizeMathJax{\newcommand{\unbr}{\underbrace}}
108 \CustomizeMathJax{\newcommand{\iif}{if and only if}}
109
110 \CustomizeMathJax{\newcommand{\mul}{\mathord{\times}}}
111 \CustomizeMathJax{\newcommand{\then}{\ \Longrightarrow \ \mbox{ } }}
112 \CustomizeMathJax{\newcommand{\txt}[1]{\quad\text{\#1}\quad}}
113 \CustomizeMathJax{\newcommand{\paren}[1]{\mathopen{\left(\#1\right)}}}
114 \CustomizeMathJax{\newcommand{\pow}[2]{\left(\ #1 \right)^{\! \#2}}}}
115 \CustomizeMathJax{\newcommand{\abs}[1]{\left\vert\#1\right\vert}}

```

```

116 \CustomizeMathJax{\newcommand{\lfrac}[2]{\frac{\: #1\:}{\: #2\:}}}
117
118 \CustomizeMathJax{\newenvironment{system}[1][L]%
119   {\left\{\begin{array}{@{.15em}#1@{}}
120   {\end{array}\right.}
121 }
122
123 \CustomizeMathJax{\newenvironment{spmatrix}
124   {\left(\begin{smallmatrix}
125   {\end{smallmatrix}\right)}
126 }
127
128 \CustomizeMathJax{%
129   \newenvironment{mathcols}
130     {\begin{aligned}\displaystyle}
131     {\end{aligned}}
132 }
133 \CustomizeMathJax{\newcommand{\changeacol}{\end{aligned}\quad\begin{aligned}}}

```

User-adjustable settings, detected if in the preamble.

```

134 \AtBeginDocument{
135   \ifdef{\itpi}{
136     \CustomizeMathJax{\let\itpi\pi}
137   }{ }
138   \ifdefstring{\boldvectcommand}{\mathbf}{
139     \CustomizeMathJax{\newcommand{\boldvectcommand}[1]{\mathbf{#1}}}
140   }{
141     \CustomizeMathJax{\newcommand{\boldvectcommand}[1]{\boldsymbol{#1}}}
142   }
143   \ifbool{arrowvect}{
144     \CustomizeMathJax{\newcommand{\vect}[1]{\overrightarrow{#1}}}
145   }{
146     \CustomizeMathJax{\newcommand{\vect}[1]{\boldvectcommand{#1}}}
147   }
148   \ifdefstring{\probastyle}{\mathbb}{
149     \CustomizeMathJax{\newcommand{\probastyle}[1]{\mathbb{#1}}}
150   }{
151     \CustomizeMathJax{\newcommand{\probastyle}[1]{\mathrm{#1}}}
152   }
153   \ifdefstring{\mathset}{\mathbb}{
154     \CustomizeMathJax{\newcommand{\mathset}[1]{\mathbb{#1}}}
155   }{
156     \CustomizeMathJax{\newcommand{\mathset}[1]{\mathbf{#1}}}
157   }
158 }
159 \end{warpMathJax}

```

File 309 **lwarp-mleftright.sty**

§ 418 Package **mleftright**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg mleftright

mleftright is used as-is, and is emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{mleftright}[2019/12/03]

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\mleft}{\left}}
4 \CustomizeMathJax{\newcommand{\mright}{\right}}
5 \CustomizeMathJax{\newcommand{\mleftright}{}}
6 \CustomizeMathJax{\newcommand{\mleftrighthrestore}{}}
7 \end{warpMathJax}

```

File 310 **lwarp-morefloats.sty**

§ 419 Package **morefloats**

Pkg morefloats morefloats is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{morefloats}[2015/07/22]

File 311 **lwarp-moreverb.sty**

§ 420 Package **moreverb**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg moreverb moreverb is supported with some patches.

```

1 \LWR@ProvidesPackagePass{moreverb}[2008/06/03]

2 \BeforeBeginEnvironment{verbatim}{%
3 \LWR@forcenewpage
4 \LWR@atbeginverbatim{Verbatim}%
5 }
6 \AfterEndEnvironment{verbatim}{%
7 \LWR@afterendverbatim%
8 }
9
10
11 \LetLtxMacro\LWRMV@orig@verbatiminput\verbatiminput
12
13 \renewcommand{\@verbatiminput}[2][]{%
14 \LWR@forcenewpage
15 \LWR@atbeginverbatim{Verbatim}%
16 \LWRMV@orig@verbatiminput[#1]{#2}%
17 \LWR@afterendverbatim%
18 }
19
20 \BeforeBeginEnvironment{listing}{%
21 \LWR@forcenewpage
22 \LWR@atbeginverbatim{programlisting}%
23 }
24
25 \AfterEndEnvironment{listing}{%
26 \LWR@afterendverbatim%
27 }
28
29 \BeforeBeginEnvironment{listingcont}{%
30 \LWR@forcenewpage

```

```

31 \LWR@atbeginverbatim{programlisting}%
32 }
33
34 \AfterEndEnvironment{listingcont}{%
35 \LWR@afterendverbatim%
36 }

37 \LetLtxMacro\LWRMV@@@listinginput\@listinginput
38
39 \renewcommand{\@listinginput}[3][[]]{
40 \LWR@forcenewpage
41 \LWR@atbeginverbatim{programlisting}%
42 \LWRMV@@@listinginput[#1]{#2}{#3}%
43 \LWR@afterendverbatim%
44 }
45
46
47 \renewenvironment*{boxedverbatim}
48 {
49 \LWR@forcenewpage
50 \LWR@atbeginverbatim{boxedverbatim}%
51 \verbatim%
52 }
53 {
54 \endverbatim%
55 \LWR@afterendverbatim%
56 }

```

File 312 **lwarp-movie15.sty**

§ 421 Package **movie15**

Pkg movie15

movie15 is emulated.

The packages **multimedia**, **movie15**, and **media9** are supported.

HTML5 `<audio>` and `<video>` objects are created for `.mp3` and `.mp4` files.

HTML5 `<embed>` objects are created for `http` and `ftp` links.

`\href` links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For **media9**, a multimedia object is inserted for each `addressource=`, as well as each `flashvars source=` and `src=`. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside `\warpprintonly` or the `warpprint` environment.

Each HTML multimedia object includes the poster text, except for `<embed>` objects. For **movie15**, the `text` option is supported to specify the poster text.

The `width`, `height`, and `totalheight` options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

`media9 \addmediapath` is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each `<audio>` and `<video>` object.

`media9` slideshows are not supported.

`\hyperlinkmovie`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YouTube™ video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

for HTML output:

```

1 \LWR@ProvidesPackageDrop{movie15}[2012/05/16]
2 \LWR@origRequirePackage{lwarp-common-multimedia}
3
4 \RequirePackage{xkeyval}
5
6 \newcommand*\LWR@moviefifteen@text{}
7
8 \define@key{LWR@moviefifteen}{text}{\renewcommand{LWR@moviefifteen@text}{#1}}
9
10 \newcommand*\LWR@includemovieb}[4][[]]{%
11   \renewcommand{LWR@moviefifteen@text}{(multimedia)}
12   \setkeys{LWR@moviefifteen}{#1}%
13   \LWR@multimediab[#1,width=#2,height=#3]{LWR@moviefifteen@text}{#4}%
14 }
15
16 \newrobustcmd*\includemovie{%
17   \begingroup%
18   \LWR@linkmediacatcodes%
19   \LWR@includemovieb%
20 }
21
22
23 \newcommand*\movieref}[3][[]]{}
24
25 \LetLtxMacro\movie\LWR@multimedia
26 % \LetLtxMacro\sound\LWR@multimedia% not in media15
27
28 \newcommand*\hyperlinkmovie}[3][[]]{}

```

File 313 **lwarp-mparhack.sty**

§ 422 Package **mparhack**

Pkg mparhack

mparhack is ignored.

for HTML output: Discard all options for `lwarp-mparhack`:

```

1 \LWR@ProvidesPackageDrop{mparhack}[2005/04/17]

```

File 314 **lwarp-multibib.sty**

§ 423 Package **multibib**

(Emulates or patches code by THORSTEN HANSEN.)

Pkg multibib multibib is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{multibib}[2008/12/10]
2 \xpatchcmd{\newcites}
3   {\@suffix}}
4   {\@suffix_html}}
5   {}
6   {\LWR@patcherror{multibib}{newcites}}
```

File 315 **lwarp-multicap.sty**

§ 424 Package **multicap**

Pkg multicap multicap is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{multicap}[2002/05/04]
2 \newcommand*{\mfcaption}{\captionof{figure}}
3 \newcommand*{\mtcaption}{\captionof{table}}
4 \newcounter{mcapsize}
5 \newcounter{mcapskip}
6 \newlength{\abvmcapskip}
7 \newlength{\blwmcapskip}
```

File 316 **lwarp-multicol.sty**

§ 425 Package **multicol**

(Emulates or patches code by FRANK MITTELBACH.)

Pkg multicol multicol is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{multicol}[2021/10/28]
```

Multicolns are converted into a 1–3 column display, browser-supported.

The optional multicolns heading is placed inside a <div> of class multicolnsheading.

The content is placed inside a <div> of class multicolns.

```

Env multicolns * {\<numcols>} [\<heading>]
2 \NewDocumentEnvironment{multicolns}{s m o}
```

HTML <div> class to contain everything:

```
3 {
4   \LWR@forcenewpage
5   \BlockClass{multicols}
```

Optional HTML <div> class for the heading:

```
6   \IfValueT{#3}{\begin{BlockClass}{multicolsheading}#3\end{BlockClass}}%
```

Change \linewidth to compensate for expected size:

```
7   \setlength{\linewidth}{\linewidth/#2}
```

Locally force any minipages to be fullwidth:

```
8   \booltrue{LWR@forceminipagefullwidth}
9 }
```

When done with the environment, close the <div>:

```
10 {\endBlockClass}
```

Emulated null functions which are not used in HTML:

```
11 \newcommand*{\columnbreak}{}
12 \newcommand*{\newcolumn}{}
13 \newcommand*{\RLmulticolcolumns}{}
14 \newcommand*{\LRmulticolcolumns}{}
15
16 \newlength{\premulticols}
17 \newlength{\postmulticols}
18 \newlength{\multicolsep}
19 \newlength{\multicolbaselineskip}
20 \newlength{\multicoltolerance}
21 \newlength{\multicolpretolerance}
22 \newcommand*{\columnseprulecolor}{\normalcolor}
23 \newcounter{columnbadness}
24 \newcounter{finalcolumnbadness}
25 \newcounter{collectmore}
26 \newcounter{unbalance}
27 \newlength{\multicolovershoot}
28 \newlength{\multicolundershoot}

29 \NewDocumentCommand{\docolaction}{s o m m}{%
30   \IfValueTF{#2}{#2}{#3}%
31 }
```

File 317 **lwarp-multicolrule.sty**

§ 426 Package **multicolrule**

Pkg multicolrule

multicolrule is ignored.

for HTML output:

```
1 \RequirePackage{multicol}
2
3 \LWR@ProvidesPackageDrop{multicolrule}[2019/01/01]

4 \newcommand*{\SetMCRule}[1]{}
5 \NewDocumentCommand{\DeclareMCRulePattern}{m m}{}

```

File 318 **lwarp-multimedia.sty**

§ 427 Package **multimedia**

Pkg multimedia

multimedia is emulated.

The packages `multimedia`, `movie15`, and `media9` are supported.

HTML5 `<audio>` and `<video>` objects are created for `.mp3` and `.mp4` files.

HTML5 `<embed>` objects are created for `http` and `ftp` links.

`\href` links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For `media9`, a multimedia object is inserted for each `addressource=`, as well as each `flashvars source=` and `src=`. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside `\warpprintonly` or the `warpprint` environment.

Each HTML multimedia object includes the poster text, except for `<embed>` objects. For `movie15`, the `text` option is supported to specify the poster text.

The `width`, `height`, and `totalheight` options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

`media9 \addmediapath` is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each `<audio>` and `<video>` object.

`media9` slideshows are not supported.

`\hyperlinkmovie`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YOUTUBE™ video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

for HTML output:

```

1 \LWR@ProvidesPackageDrop{multimedia}[2012/05/02]
2 \LWR@origRequirePackage{lwarp-common-multimedia}
3
4 \LetLtxMacro\movie\LWR@multimedia
5 \LetLtxMacro\sound\LWR@multimedia
6
7 \newcommand{\hyperlinkmovie}[3][{}]{
8
9 \newcommand{\hyperlinksound}[3][{}]{
10
```

```
11 \newcommand{\hyperlinkmute}
```

File 319 **lwarp-multiobjective.sty**

§ 428 Package **multiobjective**

(Emulates or patches code by LUIS MARTÍ.)

Pkg multiobjective

multiobjective is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output:

```
1 \LWR@ProvidesPackagePass{multiobjective}[2008/08/19]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\dom}{\prec}}
4 \CustomizeMathJax{\newcommand{\negdom}{\not\prec}}
5 \CustomizeMathJax{\newcommand{\weakdom}{\preccurlyeq}}
6 \CustomizeMathJax{\newcommand{\negweakdom}{\not\preccurlyeq}}

7 \CustomizeMathJax{\newcommand{\strictdom}{\mathord{\prec}\!\!\!\mathord{\prec}}}
8 \CustomizeMathJax{\newcommand{\negstrictdom}{\mathord{\not\prec}\!\!\!\mathord{\prec}}}
9 \CustomizeMathJax{\newcommand{\multepsilondom}{\preccurlyeq_{\epsilon\cdot}}}
10 \CustomizeMathJax{\newcommand{\addiepsilondom}{\preccurlyeq_{\epsilon +}}}
11 \CustomizeMathJax{\newcommand{\better}{\triangleleft}}
12 \CustomizeMathJax{\def\vec#1{%
13   \mathchoice%
14     {\displaystyle\boldsymbol{#1}}%
15     {\textstyle\boldsymbol{#1}}%
16     {\scriptstyle\boldsymbol{#1}}%
17     {\scriptscriptstyle\boldsymbol{#1}}%
18 }}
19
20 \CustomizeMathJax{\newcommand{\set}[1]{%
21   \mathchoice%
22     {\displaystyle\mathcal{#1}}%
23     {\textstyle\mathcal{#1}}%
24     {\scriptstyle\mathcal{#1}}%
25     {\scriptscriptstyle\mathcal{#1}}%
26 }}
27 \CustomizeMathJax{\def\argmax{\mathop{\{\mathrm{arg}\}\}, \max}}
28 \CustomizeMathJax{\def\argmin{\mathop{\{\mathrm{arg}\}\}, \min}
29 }}
30 \end{warpMathJax}
```

File 320 **lwarp-multirow.sty**

§ 429 Package **multirow**

(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)

Pkg multirow

multirow is emulated during HTML output, and used as-is while inside a `LatexImage`.

[vposn](#)

- Note that recent versions of multirow include a new optional `vposn` argument.

multirow cells

- For `multirow`, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
... & \multirow{2}{.5in}{text} & ...
... & \mrowcell & ...
```

colored cells

- The `multirow` documentation regarding colored cells recommends using a negative number of rows. This will not work with `lwarp`, so `\warpprintonly` and `\warpHTMLonly` must be used to make versions for print and HTML.

with `\multicolumn`

⚠ `\multicolumn` &
`\multirow`

- See section 429.2 for `\multicolumnrow`.

`lwarp` does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines, `\mcolrowcell` must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```
... & \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text} & ...
... & \mcolrowcell & \mcolrowcell & ...
... & \mcolrowcell & \mcolrowcell & ...
```

⚠ **skipped cells**

⚠ **empty cells**

⚠ **MathJax**

- `MATHJAX` does not support `multirow`, so it is emulated to only print its text on the first row. `\multirow` works as expected in text tabulars or SVG math.

In a `lateximage`, the print versions are restored.

See section 75.24 for the print-mode versions.

for HTML output:

Remove the placeholder macro which was used if `multirow` was not loaded:

```
1 \LetLtxMacro\multirow\relax
```

```
2 \LWR@ProvidesPackagePass{multirow}[2021/03/15]
```

`\LWR@multirowborder`

Set to left or right to create a thick border for the cell, for use by `bigdelim`:

```
3 \newcommand{\LWR@multirowborder}{}
```

§ 429.1 **Multirow**`\LWR@multirow@par``\par inside a \multirow.`

```

4 \newcommand*{\LWR@multirow@par}{%
5   \LWR@htmltag{br /}%
6 }%

```

`\multirow`

```

[⟨1: vpos⟩] {⟨2: numRows⟩} [⟨3: bigstruts⟩] {⟨4: width⟩} [⟨5: vmove⟩] {⟨6: text⟩}

```

```

7 \NewDocumentCommand{\LWR@HTML@multirow}{O{c} m o m o +m}%
8 {%
9   \LWR@traceinfo{\LWR@HTML@multirow #1 #2 #4}%

```

```

10   \booltrue{\LWR@usedmultirow}%

```

```

11   \LWR@maybenewtablerow%
12   \LWR@tabularleftedge%

```

Print the start of a new table data cell:

```

13   \LWR@htmltag{%
14     td rowspan=\textquotedbl#2\textquotedbl\ %

```

A class adds the column spec and the rule:

```

15     class=\textquotedbl{}td%

```

Append this column's spec:

```

16     \LWR@getexparray{\LWR@tablecolspec}{\arabic{\LWR@tableLaTeXcolindex}}%

```

If this column has a `cmidrule`, add “rule” to the end of the HTML class tag. Also add the vertical bar class.

```

17     \LWR@addcmidruletrim%
18     \LWR@addleftmostbartag%
19     \LWR@printbartag{\arabic{\LWR@tableLaTeXcolindex}}%
20     \textquotedbl%

```

```

21     \LWR@tdstartstyles%

```

The vertical alignment, if given:

```

22     \ifstrequal{#1}{c}{\LWR@tdaddstyle\LWR@print@mbbox{vertical-align:middle}}{%
23     \ifstrequal{#1}{b}{\LWR@tdaddstyle\LWR@print@mbbox{vertical-align:bottom}}{%
24     \ifstrequal{#1}{t}{\LWR@tdaddstyle\LWR@print@mbbox{vertical-align:top}}{%

```

The left/right border, if given:

```

25     \ifdefvoid{\LWR@multirowborder}{}%
26     \LWR@tdaddstyle%
27     \LWR@print@mbbox{border-\LWR@multirowborder:} 2px dotted black ; %
28     \LWR@print@mbbox{padding-\LWR@multirowborder:} 2px%
29     }%

```

Additional style elements:

```

30     \LWR@addcmidrulewidth%
31     \LWR@addcdashline%
32     \LWR@addtabularrulecolors%
33     \LWR@tdendstyles%
34 }%
```

The column's < spec:

```
35 \LWR@getexparray{LWR@colbefore-spec}{\arabic{LWR@tableLaTeXcolindex}}%
```

While printing the text, redefine `\` to generate a new line. If a nested tabular occurs, `\` is redefined to `\LWR@tabularendofline` at the start of the tabular, then `\LWR@endofline` before again printing any `\multirow` contents inside the nested tabular.

`\par` is redefined to insert an HTML break, and if tabular is nested, it is redefined at the start of tabular.

```

36 \begingroup%
37   \LetLtxMacro{\}{\LWR@endofline}%
38   \booltrue{LWR@in@multirow@par}%
39   #6%
40 \endgroup%
41 \LWR@stoppars%
42 \boolfalse{LWR@intabularmetadata}%
43 \renewcommand{\LWR@multirowborder}{}%
44 \LWR@traceinfo{LWR@HTML@multirow done}%
45}%
46
47 \LWR@formatted{multirow}
```

§ 429.2 Combined multicolumn and multirow

```
\multicolumnrow {<1:cols>} {<2:halign>} [<3:vpos>] {<4:numrows>} [<5:bigstruts>] {<6:width>} [<7:fixup>]
{<8:text>}
```

`\IfPackageLoadedTF{multirow}` determines if v2.0 or later of `multirow` was used, which included the `\ProvidesPackage` macro.

The HTML version follows.

`\AtBeginDocument` because the print version had to see if `multirow` was loaded before determining how to define `\LWR@print@multicolumnrow`.

```

48 \AtBeginDocument{
49
50 \NewExpandableDocumentCommand{\LWR@HTML@multicolumnrow}{m m O{} m O{} m O{} +m}{%

51 \booltrue{LWR@usedmultirow}}%
```

Figure out how many extra HTML columns to add for @ and ! columns:

```
52 \LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn/multirow tag, temporarily redefining the end of line. (Using a group caused problems with a nested tabular.)

```
53 \LetLtxMacro{\}\{LWR@endofline}%
54 \LWR@domulticolumn[#3][#4]{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#8}%
55 \LetLtxMacro{\}\{LWR@tabularendofline}%
```

Move to the next L^AT_EX column:

```
56 \defaddtocounter{LWR@tableLaTeXcolindex}{#1}%
57 \defaddtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
58 \booltrue{LWR@skipatbang}%
59 }
60
61 \LWR@expandableformatted{multicolumnrow}
62
63 }% \AtBeginDocument
```

For MATHJAX. Only the text is used. All other parameters are ignored.

```
64 \begin{warpMathJax}
65 % \multirow[vpos]{num}[bigstruts]{width}[vmove]{text}
66 \CustomizeMathJax{\newcommand{LWRsubmultirow}[2][]{#2}}
67 \CustomizeMathJax{\newcommand{LWRmultirow}[2][]{LWRsubmultirow}}
68 \CustomizeMathJax{\newcommand{\multirow}[2][]{LWRmultirow}}
69 %
70 \CustomizeMathJax{\newcommand{\mrowcell}}{}
71 \CustomizeMathJax{\newcommand{\mcolrowcell}}{}
72 \CustomizeMathJax{\newcommand{\STneed}[1]}{}
73 \end{warpMathJax}
```

File 321 **lwarp-multitoc.sty**

§ 430 Package **multitoc**

Pkg multitoc

multitoc is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{multitoc}[1999/06/08]
2 \newcommand{\multicolumntoc}{2}
3 \newcommand{\multicolumnlot}{2}
4 \newcommand{\multicolumnlof}{2}
5 \newcommand*{\immediateaddtocontents}[2]{}

```

File 322 **lwarp-musicography.sty**

§ 431 Package **musicography**

(Emulates or patches code by ANDREW A. CASHNER.)

musicography is patched for use by lwarp.

Images are used for the meter symbols and fingered bass, since the HTML fonts tend not to be the correct size and HTML cannot stack items. The HTML alt tag copies C and 3/2, etc. Hashes are used for the meter images, which are then reused as necessary.



Note that browser support for musical symbols may be buggy. ALT text and copy/paste into a text editor work well.

for HTML output:

```

1 \LWR@ProvidesPackagePass{musicography}[2019/05/28]

2 \NewDocumentCommand{\LWR@HTML@musSymbol}{ O{\musFont} m m m m }{%
3 \begin{lateximage}%
4 {#1\kern#2\raisebox{#3}{#5}\kern#4}%
5 \end{lateximage}%
6 }
7
8 \LWR@formatted{musSymbol}
9
10 \NewDocumentCommand{\LWR@HTML@musStemmedNote}{ m }{%
11 \begin{lateximage}%
12 \musSymbol{0.05em}{0.5ex}{0.2em}{#1\musStem}%
13 \end{lateximage}%
14 }
15
16 \LWR@formatted{musStemmedNote}
17
18 \NewDocumentCommand{\LWR@HTML@musFlaggedNote}{ m m }{%
19 \begin{lateximage}%
20 \musSymbol{0.05em}{0.5ex}{0pt}{#1\musStem}%
21 \musSymbol{0pt}{0pt}{0.9em}{#2}%
22 \end{lateximage}%
23 }
24
25 \LWR@formatted{musFlaggedNote}
26
27 \NewDocumentCommand{\LWR@HTML@musDottedNote}{ m }{%
28 \begin{lateximage}%
29 #1\musDot%
30 \end{lateximage}%
31 }
32
33 \LWR@formatted{musDottedNote}
34
35 \NewDocumentCommand{\LWR@HTML@musMeter}{ m m }{%
36 \begin{lateximage}*[#1/#2][#1#2]*%
37 \musStack{#1 #2}\kern0.05em%
38 \end{lateximage}%
39 }
40
41 \LWR@formatted{musMeter}
42
43 \NewDocumentCommand{\LWR@HTML@meterCplus}{ m }{%
44 \begin{lateximage}*[C#1]*%
45 \meterC{}\kern-0.7pt#1%
46 \end{lateximage}%
47 }
48
49 \LWR@formatted{meterCplus}

```

```

50
51 \NewDocumentCommand{\LWR@HTML@meterC}{*}{%
52 \begin{lateximage}*[C]*%
53 \musSymbolMeter{\symbol{83}}%
54 \end{lateximage}%
55 }
56
57 \LWR@formatted{meterC}
58
59 \NewDocumentCommand{\LWR@HTML@meterCutC}{*}{%
60 \begin{lateximage}*[C]*%
61 \musSymbolMeter{\symbol{82}}%
62 \end{lateximage}%
63 }
64
65 \LWR@formatted{meterCutC}
66
67 \NewDocumentCommand{\LWR@HTML@meterCThreeTwo}{*}{%
68 \begin{lateximage}*[C3/2]*%
69 \meterCplus{\musStack{3 2}}%
70 \end{lateximage}%
71 }
72
73 \LWR@formatted{meterCThreeTwo}
74
75 \NewDocumentCommand{\LWR@HTML@meterO}{*}{\HTMLUnicode{25EF}}
76
77 \LWR@formatted{meterO}
78
79 \newcommand{\LWR@null@noFig}[1][*]{%
80
81 \NewDocumentCommand{\LWR@HTML@musFig}{ m }{%
82 \begin{lateximage}*[%
83   {% ALT text for copy/paste
84     \LetLtxMacro\noFig\LWR@null@noFig%
85     \LetLtxMacro\musSharp\LWR@HTML@musSharp%
86     \LetLtxMacro\musDoubleSharp\LWR@HTML@musDoubleSharp%
87     \LetLtxMacro\musFlat\LWR@HTML@musFlat%
88     \LetLtxMacro\musDoubleFlat\LWR@HTML@musDoubleFlat%
89     \LetLtxMacro\musNatural\LWR@HTML@musNatural%
90     {#1}% braces here because \noFig uses []
91   }%
92 ]*%
93   \musStack[\musFigFont]{#1}%
94 \end{lateximage}%
95 }
96
97 \LWR@formatted{musFig}
98
99 \NewDocumentCommand{\LWR@HTML@musFlat}      {}{\HTMLUnicode{266D}}
100 \NewDocumentCommand{\LWR@HTML@musDoubleFlat} {}{\HTMLUnicode{1D12B}}
101 \NewDocumentCommand{\LWR@HTML@musSharp}     {}{\HTMLUnicode{266F}}
102 \NewDocumentCommand{\LWR@HTML@musDoubleSharp} {}{\HTMLUnicode{1D12A}}
103 \NewDocumentCommand{\LWR@HTML@musNatural}  {}{\HTMLUnicode{266E}}
104
105 \LWR@formatted{musFlat}
106 \LWR@formatted{musDoubleFlat}
107 \LWR@formatted{musSharp}
108 \LWR@formatted{musDoubleSharp}
109 \LWR@formatted{musNatural}

```

```

110
111 \NewDocumentCommand{\LWR@HTML@musWhole}      {}{\HTMLUnicode{1D15D}}
112 \NewDocumentCommand{\LWR@HTML@musHalf}       {}{\HTMLUnicode{1D15E}}
113 \NewDocumentCommand{\LWR@HTML@musQuarter}    {}{\HTMLUnicode{1D15F}}
114 \NewDocumentCommand{\LWR@HTML@musEighth}     {}{\HTMLUnicode{1D160}}
115 \NewDocumentCommand{\LWR@HTML@musSixteenth}  {}{\HTMLUnicode{1D161}}
116 \NewDocumentCommand{\LWR@HTML@musThirtySecond} {}{\HTMLUnicode{1D162}}
117 \NewDocumentCommand{\LWR@HTML@musSixtyFourth} {}{\HTMLUnicode{1D163}}
118
119 \LWR@formatted{musWhole}
120 \LWR@formatted{musHalf}
121 \LWR@formatted{musQuarter}
122 \LWR@formatted{musEighth}
123 \LWR@formatted{musSixteenth}
124 \LWR@formatted{musThirtySecond}
125 \LWR@formatted{musSixtyFourth}
126
127 \NewDocumentCommand{\LWR@HTML@musWholeDotted}{}
128   {\HTMLUnicode{1D15D}\HTMLUnicode{1D16D}}
129 \NewDocumentCommand{\LWR@HTML@musHalfDotted}{}
130   {\HTMLUnicode{1D15E}\HTMLUnicode{1D16D}}
131 \NewDocumentCommand{\LWR@HTML@musQuarterDotted}{}
132   {\HTMLUnicode{1D15F}\HTMLUnicode{1D16D}}
133 \NewDocumentCommand{\LWR@HTML@musEighthDotted}{}
134   {\HTMLUnicode{1D160}\HTMLUnicode{1D16D}}
135 \NewDocumentCommand{\LWR@HTML@musSixteenthDotted}{}
136   {\HTMLUnicode{1D161}\HTMLUnicode{1D16D}}
137 \NewDocumentCommand{\LWR@HTML@musThirtySecondDotted}{}
138   {\HTMLUnicode{1D162}\HTMLUnicode{1D16D}}
139 \NewDocumentCommand{\LWR@HTML@musSixtyFourthDotted}{}
140   {\HTMLUnicode{1D163}\HTMLUnicode{1D16D}}
141
142 \LWR@formatted{musWholeDotted}
143 \LWR@formatted{musHalfDotted}
144 \LWR@formatted{musQuarterDotted}
145 \LWR@formatted{musEighthDotted}
146 \LWR@formatted{musSixteenthDotted}
147 \LWR@formatted{musThirtySecondDotted}
148 \LWR@formatted{musSixtyFourthDotted}

```

File 323 **lwarp-mwe.sty**

§ 432 Package **mwe**

(Emulates or patches code by MARTIN SCHARRER.)

Pkg mwe

mwe is used as-is, but a warning is issued to copy the images to the local directory.

for HTML output: 1 \LWR@ProvidesPackagePass{mwe}[2018/03/30]

```

2 \AtEndDocument{%
3   \PackageWarningNoLine{lwarp}{%
4     For package mwe, copy any mwe images to be used for\MessageBreak
5     HTML, such as PNG or JPG, to the document's base\MessageBreak
6     directory. Neither a subdirectory nor the mwe\MessageBreak
7     directory will work, due to the TeX file search\MessageBreak
8     algorithm%

```

```

9   }%
10 }%

```

File 324 **lwarp-nameauth.sty**

§ 433 Package **nameauth**

(Emulates or patches code by CHARLES P. SCHAUM.)

Pkg nameauth nameauth is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{nameauth}[2017/03/22]

Hook [nameauth] lwarp formatting is inserted.

\@nameauth@Hook

```

2 \renewcommand*\@nameauth@Hook[1]
3 {%
4   \if@nameauth@Lock
5     \@nameauth@InHooktrue%
6     \protected@edef\test{#1}%
7     \expandafter\@nameauth@TestDot\expandafter{\test}%
8     \if@nameauth@InAKA
9       \if@nameauth@AlwaysFormat
10      \@nameauth@FirstFormattrue%
11     \else
12       \unless\if@nameauth@AKAFormat
13       \@nameauth@FirstFormatfalse\fi
14     \fi
15     \if@nameauth@MainFormat
16       \if@nameauth@FirstFormat
17         \bgroup\NamesFormat{%
18           \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%   lwarp
19         }\egroup%
20       \else
21         \bgroup\MainNameHook{%
22           \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%   lwarp
23         }\egroup%
24       \fi
25     \else
26       \if@nameauth@FirstFormat
27         \bgroup\FrontNamesFormat{%
28           \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%   lwarp
29         }\egroup%
30       \else
31         \bgroup\FrontNameHook{%
32           \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%   lwarp
33         }\egroup%
34       \fi
35     \fi
36   \else
37     \if@nameauth@AlwaysFormat
38       \@nameauth@FirstFormattrue%
39     \fi
40     \if@nameauth@MainFormat
41       \if@nameauth@FirstFormat
42         \bgroup\NamesFormat{%
43           \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%   lwarp

```

```

44     }\egroup%
45     \else
46     \bgroup\MainNameHook{%
47     \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%   lwarp
48     }\egroup%
49     \fi
50     \else
51     \if@nameauth@FirstFormat
52     \bgroup\FrontNamesFormat{%
53     \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%   lwarp
54     }\egroup%
55     \else
56     \bgroup\FrontNameHook{%
57     \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%   lwarp
58     }\egroup%
59     \fi
60     \fi
61     \fi
62     \@nameauth@FirstFormatfalse%
63     \@nameauth@InHookfalse%
64     \fi
65 }

```

File 325 **lwarp-nameref.sty**

§ 434 Package **nameref**

Pkg nameref

nameref is emulated by lwarp.

for HTML output: Discard all options for lwarp-nameref:

```

1 \PackageInfo{lwarp}{%
2 Using the lwarp HTML version of package ‘nameref’,\MessageBreak
3 and discarding options.\MessageBreak
4 (Not using \protect\ProvidesPackage, so that other packages\MessageBreak
5 do not attempt to patch lwarp’s version of ‘nameref’.)\MessageBreak
6 }
7 \DeclareOption*{}
8 \ProcessOptions\relax

```

File 326 **lwarp-natbib.sty**

§ 435 Package **natbib**

(Emulates or patches code by PATRICK W. DALY.)

Pkg natbib

natbib is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{natbib}[2010/09/13]

Replace math $<$ and $>$ with `\textless` and `\textgreater`:

A macro to compare:

```
2 \newcommand{\LWRNB@NAT@open}{$<$}
```

To patch \NAT@open and \NAT@close

```

3 \newcommand{\LWRNB@patchnatbibopenclose}{
4 \ifdefstrequal{\NAT@open}{\LWRNB@NAT@open}
5 {
6   \renewcommand{\NAT@open}{\textless}
7   \renewcommand{\NAT@close}{\textgreater}
8 }{}}
9 }

```

Do it now in case angle was selected as an option:

```
10 \LWRNB@patchnatbibopenclose
```

Also patch \setcitestyle to patch after settings are made:

```

11 \let\LWRNB@origsetcitestyle\setcitestyle
12
13 \renewcommand{\setcitestyle}[1]{%
14 \LWRNB@origsetcitestyle{#1}%
15 \LWRNB@patchnatbibopenclose%
16 }

```

Synchronize the autopage labels:

```

17 \xpretocmd{\NAT@reset@parser}
18   {\LWR@newautopageLabel{page}}%
19   {}
20   {\LWR@patcherror{natbib}{\NAT@reset@parser}}

```

File 327 **lwarp-nccfancyhdr.sty**

§ 436 Package **nccfancyhdr**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg nccfancyhdr

nccfancyhdr is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nccfancyhdr}[2004/12/07]

```

2 \newcommand*{\headrulewidth}{}
3 \newcommand*{\footrulewidth}{}
4 \newcommand{\headstrutheight}{}
5 \newcommand{\footstrutheight}{}
6 \newcommand*{\headrule}{}
7 \newcommand*{\footrule}{}
8
9 \newdimen\headwidth
10 \newcommand*{\extendedheaders}{}
11 \newcommand*{\normalheaders}{}
12
13 \newcommand*{\fancyhead}[2][{}]{
14 \newcommand*{\fancyfoot}[2][{}]{
15 \newcommand*{\fancyhf}[2][{}]{
16 \newcommand*{\fancypagestyle}[2]{
17 \newcommand*{\lhead}[2][{}]{

```

```

18 \newcommand*\thead}[2][{}]{
19 \newcommand*\rhead}[2][{}]{
20 \newcommand*\lfoot}[2][{}]{
21 \newcommand*\cfoot}[2][{}]{
22 \newcommand*\rfoot}[2][{}]{
23
24 \newcommand{\nouppercase}[1]{#1}
25
26 \NewDocumentCommand{\fancycenter}{o o m m}{}
27
28 \NewDocumentCommand{\newpagestyle}{m o m}{}
29
30 \newcommand*\iffloatpage}[2]{#2}
31 \newcommand*\ifftopfloat}[2]{#2}
32 \newcommand*\iffbotfloat}[2]{#2}

```

File 328 **lwarp-nccfoots.sty**

§ 437 Package **nccfoots**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg nccfoots

nccfoots is used as-is, and emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{nccfoots}[2005/02/03]

To nullify the footnotes where necessary:

```

2 \apptocmd{\LWR@nullifyfootnotes}{%
3   \renewcommand*\Footnote}[1]{}%
4   \renewcommand*\Footnotemark}[1]{}%
5 }{}{}

```



For MATHJAX. There is no way to test for an empty argument, so the mark is not automatically duplicated.

```

6 \begin{warpMathJax}
7 \CustomizeMathJax{\newcommand{\Footnotemark}[1]{\^{\mathrm{#1}}}}
8 \CustomizeMathJax{\newcommand{\Footnote}[2]{\Footnotemark{#1}}}
9 \end{warpMathJax}

```

File 329 **lwarp-nccmath.sty**

§ 438 Package **nccmath**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg nccmath

nccmath is patched for use by lwarp, and emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{nccmath}[2006/01/20]

```

2 \let\LWR@origeqnarray\eqnarray
3 \let\LWR@origendeqnarray\endeqnarray
4

```

```

5 \csletcs{LWR@origeqnarraystar}{eqnarray*}
6 \csletcs{LWR@origendeqnarraystar}{endeqnarray*}
7
8 \RenewEnviron{eqnarray}
9 {%
10
11   \LWR@eqnarrayfactor
12
13 }
14
15 \RenewEnviron{eqnarray*}
16 {%
17
18   \begingroup
19   \csletcs{LWR@origeqnarray}{LWR@origeqnarraystar}
20   \csletcs{LWR@origendeqnarray}{LWR@origendeqnarraystar}
21   \boolfalse{LWR@numbereqnarray}
22   \LWR@eqnarrayfactor
23   \endgroup
24
25 }
26
27 \def\eqs{%
28   \ifstar\LWR@nccmath@eqsstar\LWR@nccmath@eqs%
29 }
30 \newcommand*{\LWR@nccmath@eqsstar}[2][\begin{eqnarray*}#2\end{eqnarray*}]{}
31 \newcommand*{\LWR@nccmath@eqs}[2][\begin{eqnarray}#2\end{eqnarray}]{}
32
33 \begin{warpMathJax}

34 \CustomizeMathJax{\renewcommand{\intertext}[2][\text{#2}\notag \\\]}
35 \CustomizeMathJax{\newenvironment{fleqn}[1][\{}]}
36 \CustomizeMathJax{\newenvironment{ceqn}[\]}
37 \CustomizeMathJax{\newenvironment{darray}[2][c]{\begin{array}[#1]{#2}{\end{array}}]}
38 \CustomizeMathJax{\newcommand{\dmulticolumn}[3][#3]}

```

As of v0.86, MATHJAX v3 does not offer $\backslash*$, so the unstarred version is used here.

```

39 \CustomizeMathJax{\newcommand{\LWRnrnstar}[1][0.5ex]{\{#1\}}
40 \CustomizeMathJax{\newcommand{\nr}{\ifstar\LWRnrnstar\LWRnrnstar}}
41
42 \CustomizeMathJax{\newcommand{\mrel}[1]{\begin{aligned}#1\end{aligned}}}
43 \CustomizeMathJax{\newcommand{\underrel}[2]{\underset{#2}{#1}}}
44 \CustomizeMathJax{\newcommand{\medmath}[1]{#1}}
45 \CustomizeMathJax{\newcommand{\medop}[1]{#1}}
46 \CustomizeMathJax{\newcommand{\medint}[1]{#1}}
47 \CustomizeMathJax{\newcommand{\medintcorr}[1]{#1}}
48 \CustomizeMathJax{\newcommand{\mfrac}[2]{\frac{#1}{#2}}}
49 \CustomizeMathJax{\newcommand{\mbinom}[2]{\binom{#1}{#2}}}
50 \CustomizeMathJax{\newenvironment{mmatrix}{\begin{matrix}}{\end{matrix}}}

51 \CustomizeMathJax{\newcommand{\displaybreak}[1][\]}

```

$\backslash eq$, $\backslash eqs$, $\backslash eqalign$ are created by L^AT_EX, not MATHJAX.

```

52 \end{warpMathJax}

```

File 330 **lwarp-needspace.sty**

§ 439 Package **needspace**

(Emulates or patches code by PETER WILSON.)

Pkg needspace

needspace is ignored.

for HTML output: Discard all options for lwarp-needspace:

```
1 \LWR@ProvidesPackageDrop{needspace}[2010/09/12]
2
3 \DeclareDocumentCommand{\needspace}{m}{}
4 \DeclareDocumentCommand{\Needspace}{s m}{}

```

File 331 **lwarp-newpxmath.sty**

§ 440 Package **newpxmath**

(Emulates or patches code by MICHAEL SHARPE.)

Pkg newpxmath

newpxmath is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except `slantedGreek` is honored. The dedicated macros for upright and italic Greek do work correctly.

SVG math should appear the same as the printed output.

for HTML output: The MATHJAX code from `newtxmath` is used:

```
1 \LWR@ProvidesPackagePass{newpxmath}[2020/01/09]
2
3 \LWR@infoprocessingmathjax{newpxmath}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-newpctxmath}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 % * \marg{2: prefix} \marg{3: postfix} \marg{4: i/u: italic/upright}
12 \LWR@mathjax@addgreek@u@up*{}{up}
13 \LWR@mathjax@addgreek@u@up*{up}{}
14 \LWR@mathjax@addgreek@l@up{up}{}
15 \LWR@mathjax@addgreek@l@up{}{up}
16 \LWR@mathjax@addgreek@u@it*{}{it}
17 \LWR@mathjax@addgreek@l@it{}{it}

```

Optional slanted Greek:

```
18 \ifpx@slantedG
19 \LWR@mathjax@addgreek@u@it*{}{}
20 \fi
21

```

```
22 \end{warpMathJax}
```

File 332 **lwarp-newtxmath.sty**

§ 441 Package **newtxmath**

(Emulates or patches code by MICHAEL SHARPE.)

Pkg newtxmath

newtxmath is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except `slantedGreek` is honored, and except that bold italic Latin letters are not defined for MATHJAX if the option is not selected.

The dedicated macros for upright and italic Greek and bold italic Latin letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```
1 \LWR@ProvidesPackagePass{newtxmath}[2020/08/04]
2
3 \LWR@infoprocessingmathjax{newtxmath}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-newpctxmath}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 % * \marg{2: prefix} \marg{3: postfix} \marg{4: i/u: italic/upright}
12 \LWR@mathjax@addgreek@u@up*{}{up}
13 \LWR@mathjax@addgreek@u@up*{}{}
14 \LWR@mathjax@addgreek@l@up{}{}
15 \LWR@mathjax@addgreek@l@up{}{up}
16 \LWR@mathjax@addgreek@u@it*{}{it}
17 \LWR@mathjax@addgreek@l@it{}{it}
18
19 % only newtxmath, not newpctxmath:
20 \LWR@mathjax@addgreek@u@it*{}{}
21 \LWR@mathjax@addgreek@l@it{}{}
22
23 % only newtxmath, not newpctxmath:
24 \ifdef{\iftx@BI}{
25   \iftx@BI
26     \LWR@mathjax@addlatin@u@bfit{BI}
27     \LWR@mathjax@addlatin@l@bfit{BI}
28   \fi
29 }{}
```

Optional slanted Greek:

```
30 \iftx@slantedG
31   \LWR@mathjax@addgreek@u@it*{}{}
32 \fi
33
34 \end{warpMathJax}
```

File 333 **lwarp-newtxsf.sty**

§ 442 Package **newtxsf**

(Emulates or patches code by MICHAEL SHARPE.)

Pkg newtxsf

newtxsf is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except `slantedGreek` is honored. The dedicated macros for upright and italic Greek and bold italic Latin letters do work correctly.

SVG math should appear the same as the printed output.

for HTML output:

```

1 \LWR@ProvidesPackagePass{newtxsf}[2020/05/02]
2
3 \LWR@infoprocessingmathjax{newtxsf}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-newpctxmath}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 % * \marg{2: prefix} \marg{3: postfix} \marg{4: i/u: italic/upright}
12 \LWR@mathjax@addgreek@u@up*{}{up}
13 \LWR@mathjax@addgreek@u@up*{up}{}
14 \LWR@mathjax@addgreek@l@up{}{up}
15 \LWR@mathjax@addgreek@l@up{}{up}
16 \LWR@mathjax@addgreek@u@it*{}{it}
17 \LWR@mathjax@addgreek@l@it{}{it}
18
19 % only newtxmath, not newpxmath:
20 \LWR@mathjax@addgreek@u@it*{it}{}
21 \LWR@mathjax@addgreek@l@it{it}{}
22 %
23 % only newtxmath, not newpxmath:
24 \ifdef{\iftx@BI}{
25   \iftx@BI
26     \LWR@mathjax@addlatin@u@bfit{BI}
27     \LWR@mathjax@addlatin@l@bfit{BI}
28   \fi
29 }{}

```

Optional slanted Greek:

```

30 \iftx@slantedG
31   \LWR@mathjax@addgreek@u@it*{}{}
32 \fi
33
34 \end{warpMathJax}

```

File 334 **lwarp-nextpage.sty**§ 443 Package **nextpage**

(Emulates or patches code by PETER WILSON.)

Pkg nextpage

nextpage is ignored.

for HTML output: Discard all options for lwarp-nextpage.

```
1 \LWR@ProvidesPackageDrop{nextpage}[2009/09/03]

2 \DeclareDocumentCommand{\cleartoevenpage}{o}{}
3 \DeclareDocumentCommand{\movetoevenpage}{o}{}
4 \DeclareDocumentCommand{\cleartooddpage}{o}{}
5 \DeclareDocumentCommand{\movetooddpage}{o}{}

```

File 335 **lwarp-nfssext-cfr.sty**§ 444 Package **nfssext-cfr**

(Emulates or patches code by CLEA F. REES.)

Pkg nfssext-cfr

nfssext-cfr is emulated in HTML, and used as-is in print output.

Results depend on the browser's font.

for HTML output: 1 \LWR@ProvidesPackagePass{nfssext-cfr}[2017/03/28]

Macros which are present in the lwarp core are commented out here.

```
2 \newrobustcmd{\LWR@HTML@lnstyle}{}
3 \newrobustcmd{\LWR@HTML@osstyle}{\LWR@HTML@scshape}
4 \newrobustcmd{\LWR@HTML@instyle}{}
5 \newrobustcmd{\LWR@HTML@sustyle}{}
6 \newrobustcmd{\LWR@HTML@swstyle}{}
7 \newrobustcmd{\LWR@HTML@pstyle}{}
8 \newrobustcmd{\LWR@HTML@tistyle}{}
9 \newrobustcmd{\LWR@HTML@ostyle}{\LWR@HTML@scshape}
10 \newrobustcmd{\LWR@HTML@postyle}{\LWR@HTML@scshape}
11 \newrobustcmd{\LWR@HTML@ltstyle}{}
12 \newrobustcmd{\LWR@HTML@ofstyle}{}
13 \newrobustcmd{\LWR@HTML@altstyle}{}
14 \newrobustcmd{\LWR@HTML@regstyle}{}
15 \newrobustcmd{\LWR@HTML@embosstyle}{}
16 \newrobustcmd{\LWR@HTML@ornamentalstyle}{}
17 \newrobustcmd{\LWR@HTML@qtstyle}{}
18 \newrobustcmd{\LWR@HTML@shstyle}{}
19 \newrobustcmd{\LWR@HTML@swashstyle}{}
20 \newrobustcmd{\LWR@HTML@tmstyle}{\renewcommand*{\LWR@f@family}{tt}}
21 \newrobustcmd{\LWR@HTML@tvstyle}{\renewcommand*{\LWR@f@family}{tt}}
22 \newrobustcmd{\LWR@HTML@tstyle}{}
23 \newrobustcmd{\LWR@HTML@lstyle}{}

```

```

24 \newrobustcmd{\LWR@HTML@tstyle}{}
25 \newrobustcmd{\LWR@HTML@plstyle}{}
26 \newrobustcmd{\LWR@HTML@tostyle}{\LWR@HTML@scshape}
27 % \newrobustcmd{\LWR@HTML@sihape}{}
28 \newrobustcmd{\LWR@HTML@olshape}{}
29 \newrobustcmd{\LWR@HTML@scolshape}{}
30 \newrobustcmd{\LWR@HTML@ushape}{}
31 \newrobustcmd{\LWR@HTML@scushape}{}
32 \newrobustcmd{\LWR@HTML@uihape}{\LWR@HTML@itshape}
33 \newrobustcmd{\LWR@HTML@rihape}{}
34 \newrobustcmd{\LWR@HTML@regwidth}{}
35 \newrobustcmd{\LWR@HTML@nwidth}{}
36 \newrobustcmd{\LWR@HTML@cdwidth}{}
37 \newrobustcmd{\LWR@HTML@ecwidth}{}
38 \newrobustcmd{\LWR@HTML@ucwidth}{}
39 \newrobustcmd{\LWR@HTML@etwidth}{}
40 \newrobustcmd{\LWR@HTML@epwidth}{}
41 \newrobustcmd{\LWR@HTML@exwidth}{}
42 \newrobustcmd{\LWR@HTML@uxwidth}{}
43 \newrobustcmd{\LWR@HTML@mbweight}{\renewcommand*{\LWR@f@series}{md}}
44 \newrobustcmd{\LWR@HTML@dbweight}{\renewcommand*{\LWR@f@series}{db}}
45 \newrobustcmd{\LWR@HTML@sbweight}{\renewcommand*{\LWR@f@series}{sb}}
46 % \newrobustcmd{\LWR@HTML@ebweight}{\renewcommand*{\LWR@f@series}{eb}}
47 \newrobustcmd{\LWR@HTML@ubweight}{\renewcommand*{\LWR@f@series}{ub}}
48 % \newrobustcmd{\LWR@HTML@lgweight}{\renewcommand*{\LWR@f@series}{lg}}
49 \newrobustcmd{\LWR@HTML@elweight}{\renewcommand*{\LWR@f@series}{el}}
50 \newrobustcmd{\LWR@HTML@ulweight}{\renewcommand*{\LWR@f@series}{ul}}
51 % \newrobustcmd{\LWR@HTML@itshape}{}
52 % \newrobustcmd{\LWR@HTML@scshape}{}
53 % \newrobustcmd{\LWR@HTML@upshape}{}
54 \newrobustcmd{\LWR@HTML@dfshape}{}
55
56 \ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
57   \newrobustcmd{\LWR@HTML@swshape}{}
58 }
59
60 \newrobustcmd{\LWR@HTML@ornament}[1]{}
61
62 \LWR@formatted{lnstyle}
63 \LWR@formatted{osstyle}
64 \LWR@formatted{instyle}
65 \LWR@formatted{sustyle}
66 \LWR@formatted{swstyle}
67 \LWR@formatted{pstyle}
68 \LWR@formatted{tistyle}
69 \LWR@formatted{ostyle}
70 \LWR@formatted{postyle}
71 \LWR@formatted{ltstyle}
72 \LWR@formatted{ofstyle}
73 \LWR@formatted{altstyle}
74 \LWR@formatted{regstyle}
75 \LWR@formatted{embosstyle}
76 \LWR@formatted{ornamentalstyle}
77 \LWR@formatted{qtstyle}
78 \LWR@formatted{shstyle}
79 \LWR@formatted{swashstyle}
80 \LWR@formatted{tmstyle}
81 \LWR@formatted{tvstyle}
82 \LWR@formatted{tstyle}
83 \LWR@formatted{lstyle}

```

```

84 \LWR@formatted{tlstyle}
85 \LWR@formatted{plstyle}
86 \LWR@formatted{tostyle}
87 % \LWR@formatted{sisshape}
88 \LWR@formatted{olshape}
89 \LWR@formatted{scolshape}
90 \LWR@formatted{ushape}
91 \LWR@formatted{scushape}
92 \LWR@formatted{uishape}
93 \LWR@formatted{rishape}
94 \LWR@formatted{regwidth}
95 \LWR@formatted{nwwidth}
96 \LWR@formatted{cdwidth}
97 \LWR@formatted{ecwidth}
98 \LWR@formatted{ucwidth}
99 \LWR@formatted{etwidth}
100 \LWR@formatted{epwidth}
101 \LWR@formatted{exwidth}
102 \LWR@formatted{uxwidth}
103 \LWR@formatted{mbweight}
104 \LWR@formatted{dbweight}
105 \LWR@formatted{sbweight}
106 % \LWR@formatted{ebweight}
107 \LWR@formatted{ubweight}
108 % \LWR@formatted{lgweight}
109 \LWR@formatted{elweight}
110 \LWR@formatted{ulweight}
111 \LWR@formatted{itshape}% adapt to the new print version
112 \LWR@formatted{scshape}% adapt to the new print version
113 \LWR@formatted{upshape}% adapt to the new print version
114 \LWR@formatted{dfshape}
115
116 \ifdef{\LWR@HTML@swshape}{ }{% duplicated by fontaxes
117   \LWR@formatted{swshape}
118 }
119
120 \LWR@formatted{ornament}

121 \FilenameNullify{%
122   \LetLtxMacro\lnstyle\@empty%
123   \LetLtxMacro\osstyle\@empty%
124   \LetLtxMacro\instyle\@empty%
125   \LetLtxMacro\sustyle\@empty%
126   \LetLtxMacro\swstyle\@empty%
127   \LetLtxMacro\pstyle\@empty%
128   \LetLtxMacro\tistyle\@empty%
129   \LetLtxMacro\ostyle\@empty%
130   \LetLtxMacro\postyle\@empty%
131   \LetLtxMacro\ltstyle\@empty%
132   \LetLtxMacro\ofstyle\@empty%
133   \LetLtxMacro\altstyle\@empty%
134   \LetLtxMacro\regstyle\@empty%
135   \LetLtxMacro\embossstyle\@empty%
136   \LetLtxMacro\ornamentalstyle\@empty%
137   \LetLtxMacro\qtstyle\@empty%
138   \LetLtxMacro\shstyle\@empty%
139   \LetLtxMacro\swashstyle\@empty%
140   \LetLtxMacro\tmstyle\@empty%
141   \LetLtxMacro\tvstyle\@empty%
142   \LetLtxMacro\tstyle\@empty%

```

```

143 \LetLtxMacro\lstyle\@empty%
144 \LetLtxMacro\lstyle\@empty%
145 \LetLtxMacro\plstyle\@empty%
146 \LetLtxMacro\tostyle\@empty%
147 % \LetLtxMacro\sihape\@empty%
148 \LetLtxMacro\olshape\@empty%
149 \LetLtxMacro\scolshape\@empty%
150 \LetLtxMacro\ushape\@empty%
151 \LetLtxMacro\scushape\@empty%
152 \LetLtxMacro\uishape\@empty%
153 \LetLtxMacro\rihape\@empty%
154 \LetLtxMacro\regwidth\@empty%
155 \LetLtxMacro\nwidth\@empty%
156 \LetLtxMacro\cdwidth\@empty%
157 \LetLtxMacro\ecwidth\@empty%
158 \LetLtxMacro\ucwidth\@empty%
159 \LetLtxMacro\etwidth\@empty%
160 \LetLtxMacro\epwidth\@empty%
161 \LetLtxMacro\exwidth\@empty%
162 \LetLtxMacro\uxwidth\@empty%
163 \LetLtxMacro\mbweight\@empty%
164 \LetLtxMacro\dbweight\@empty%
165 \LetLtxMacro\sbweight\@empty%
166 % \LetLtxMacro\ebweight\@empty%
167 \LetLtxMacro\ubweight\@empty%
168 % \LetLtxMacro\lgweight\@empty%
169 \LetLtxMacro\elweight\@empty%
170 \LetLtxMacro\ulweight\@empty%
171 % \LetLtxMacro\itshape\@empty%
172 % \LetLtxMacro\scshape\@empty%
173 % \LetLtxMacro\upshape\@empty%
174 \LetLtxMacro\dfshape\@empty%
175 \LetLtxMacro\swshape\@empty%
176 \LetLtxMacro\ornament\@gobble%
177 }
178
179 \newrobustcmd{\LWR@HTML@textln}[1]{\InlineClass{textln}{#1}}
180 \newrobustcmd{\LWR@HTML@textos}[1]{\textsc{#1}}
181 \newrobustcmd{\LWR@HTML@textin}[1]{#1}
182 \newrobustcmd{\LWR@HTML@textsu}[1]{#1}
183 % \newrobustcmd{\LWR@HTML@textsi}[1]{#1}
184 \newrobustcmd{\LWR@HTML@textdf}[1]{#1}

185 \ifdef{\LWR@HTML@textsw}{% duplicated by fontaxes
186 \newrobustcmd{\LWR@HTML@textsw}[1]{#1}
187 \LWR@formatted{textsw}
188 }
189
190 \newrobustcmd{\LWR@HTML@textti}[1]{#1}
191 \newrobustcmd{\LWR@HTML@textlt}[1]{#1}
192 \newrobustcmd{\LWR@HTML@textof}[1]{#1}
193 \newrobustcmd{\LWR@HTML@textalt}[1]{#1}
194 \newrobustcmd{\LWR@HTML@textreg}[1]{#1}
195 \newrobustcmd{\LWR@HTML@emboss}[1]{#1}
196 \newrobustcmd{\LWR@HTML@textorn}[1]{#1}
197 \newrobustcmd{\LWR@HTML@textqt}[1]{#1}
198 \newrobustcmd{\LWR@HTML@textsh}[1]{#1}
199 \newrobustcmd{\LWR@HTML@texttm}[1]{\texttt{#1}}
200 \newrobustcmd{\LWR@HTML@texttv}[1]{\texttt{#1}}
201 \newrobustcmd{\LWR@HTML@textl}[1]{\InlineClass{textln}{#1}}

```

202 \newrobustcmd{\LWR@HTML@texto}[1]{\textsc{#1}}
203 \newrobustcmd{\LWR@HTML@textp}[1]{\InlineClass{textp}{#1}}
204 \newrobustcmd{\LWR@HTML@textt}[1]{\InlineClass{textt}{#1}}
205 \newrobustcmd{\LWR@HTML@textpl}[1]{#1}
206 \newrobustcmd{\LWR@HTML@textpo}[1]{\textsc{#1}}
207 \newrobustcmd{\LWR@HTML@texttl}[1]{\InlineClass{textln}{#1}}
208 \newrobustcmd{\LWR@HTML@textto}[1]{\textsc{#1}}
209 \newrobustcmd{\LWR@HTML@textol}[1]{#1}
210 \newrobustcmd{\LWR@HTML@textswash}[1]{#1}
211 \newrobustcmd{\LWR@HTML@textu}[1]{#1}
212 \newrobustcmd{\LWR@HTML@textscu}[1]{#1}
213 \newrobustcmd{\LWR@HTML@textui}[1]{\LWR@HTML@textit{#1}}
214 \newrobustcmd{\LWR@HTML@textri}[1]{#1}
215 \newrobustcmd{\LWR@HTML@textnw}[1]{#1}
216 \newrobustcmd{\LWR@HTML@textcd}[1]{#1}
217 \newrobustcmd{\LWR@HTML@textec}[1]{#1}
218 \newrobustcmd{\LWR@HTML@textuc}[1]{#1}
219 \newrobustcmd{\LWR@HTML@textet}[1]{#1}
220 \newrobustcmd{\LWR@HTML@textep}[1]{#1}
221 \newrobustcmd{\LWR@HTML@textex}[1]{#1}
222 \newrobustcmd{\LWR@HTML@textux}[1]{#1}
223 \newrobustcmd{\LWR@HTML@textrw}[1]{#1}
224 \newrobustcmd{\LWR@HTML@textmb}[1]{\{\LWR@HTML@mbweight\InlineClass{textmb}{#1}\}}
225 \newrobustcmd{\LWR@HTML@textdb}[1]{\{\LWR@HTML@dbweight\InlineClass{textdb}{#1}\}}
226 \newrobustcmd{\LWR@HTML@textsb}[1]{\{\LWR@HTML@sbweight\InlineClass{textsb}{#1}\}}
227 % \newrobustcmd{\LWR@HTML@texteb}[1]{#1}
228 \newrobustcmd{\LWR@HTML@textub}[1]{\{\LWR@HTML@ubweight\InlineClass{textub}{#1}\}}
229 % \newrobustcmd{\LWR@HTML@textlg}[1]{#1}
230 \newrobustcmd{\LWR@HTML@textel}[1]{\{\LWR@HTML@elweight\InlineClass{textel}{#1}\}}
231 \newrobustcmd{\LWR@HTML@textul}[1]{\{\LWR@HTML@ulweight\InlineClass{textul}{#1}\}}
232
233 \LWR@formatted{textln}
234 \LWR@formatted{textos}
235 \LWR@formatted{textin}
236 \LWR@formatted{textsu}
237 % \LWR@formatted{textsi}
238 \LWR@formatted{textdf}
239 \LWR@formatted{textti}
240 \LWR@formatted{textlt}
241 \LWR@formatted{textof}
242 \LWR@formatted{textalt}
243 \LWR@formatted{textreg}
244 \LWR@formatted{emboss}
245 \LWR@formatted{textorn}
246 \LWR@formatted{textqt}
247 \LWR@formatted{textsh}
248 \LWR@formatted{texttm}
249 \LWR@formatted{texttv}
250 \LWR@formatted{textl}
251 \LWR@formatted{texto}
252 \LWR@formatted{textp}
253 \LWR@formatted{textt}
254 \LWR@formatted{textpl}
255 \LWR@formatted{textpo}
256 \LWR@formatted{texttl}
257 \LWR@formatted{textto}
258 \LWR@formatted{textol}
259 \LWR@formatted{textswash}
260 \LWR@formatted{textu}
261 \LWR@formatted{textscu}

```
262 \LWR@formatted{textui}
263 \LWR@formatted{textri}
264 \LWR@formatted{textnw}
265 \LWR@formatted{textcd}
266 \LWR@formatted{textec}
267 \LWR@formatted{textuc}
268 \LWR@formatted{textet}
269 \LWR@formatted{textep}
270 \LWR@formatted{textex}
271 \LWR@formatted{textux}
272 \LWR@formatted{textrw}
273 \LWR@formatted{textmb}
274 \LWR@formatted{textdb}
275 \LWR@formatted{textsb}
276 % \LWR@formatted{texteb}
277 \LWR@formatted{textub}
278 % \LWR@formatted{textlg}
279 \LWR@formatted{textel}
280 \LWR@formatted{textul}
281

282 \FilenameNullify{%
283   \LetLtxMacro\textln\@firstofone%
284   \LetLtxMacro\textos\@firstofone%
285   \LetLtxMacro\textin\@firstofone%
286   \LetLtxMacro\textsu\@firstofone%
287 % \LetLtxMacro\textsi\@firstofone%
288   \LetLtxMacro\textdf\@firstofone%
289   \LetLtxMacro\textsw\@firstofone%
290   \LetLtxMacro\textti\@firstofone%
291   \LetLtxMacro\textlt\@firstofone%
292   \LetLtxMacro\textof\@firstofone%
293   \LetLtxMacro\textalt\@firstofone%
294   \LetLtxMacro\textreg\@firstofone%
295   \LetLtxMacro\emboss\@firstofone%
296   \LetLtxMacro\textorn\@firstofone%
297   \LetLtxMacro\textqt\@firstofone%
298   \LetLtxMacro\textsh\@firstofone%
299   \LetLtxMacro\texttm\@firstofone%
300   \LetLtxMacro\texttv\@firstofone%
301   \LetLtxMacro\textl\@firstofone%
302   \LetLtxMacro\texto\@firstofone%
303   \LetLtxMacro\textp\@firstofone%
304   \LetLtxMacro\textt\@firstofone%
305   \LetLtxMacro\textpl\@firstofone%
306   \LetLtxMacro\textpo\@firstofone%
307   \LetLtxMacro\texttl\@firstofone%
308   \LetLtxMacro\textto\@firstofone%
309   \LetLtxMacro\textol\@firstofone%
310   \LetLtxMacro\textswash\@firstofone%
311   \LetLtxMacro\textu\@firstofone%
312   \LetLtxMacro\textscu\@firstofone%
313   \LetLtxMacro\textui\@firstofone%
314   \LetLtxMacro\textri\@firstofone%
315   \LetLtxMacro\textnw\@firstofone%
316   \LetLtxMacro\textcd\@firstofone%
317   \LetLtxMacro\textec\@firstofone%
318   \LetLtxMacro\textuc\@firstofone%
319   \LetLtxMacro\textet\@firstofone%
320   \LetLtxMacro\textep\@firstofone%
```

```

321 \LetLtxMacro\textex\@firstofone%
322 \LetLtxMacro\textux\@firstofone%
323 \LetLtxMacro\textrw\@firstofone%
324 \LetLtxMacro\textmb\@firstofone%
325 \LetLtxMacro\textdb\@firstofone%
326 \LetLtxMacro\textsb\@firstofone%
327 % \LetLtxMacro\texteb\@firstofone%
328 \LetLtxMacro\textub\@firstofone%
329 % \LetLtxMacro\textlg\@firstofone%
330 \LetLtxMacro\textel\@firstofone%
331 \LetLtxMacro\textul\@firstofone%
332 }
333
334 \providecommand*\zeroslash{}{0}
335 \newrobustcmd*\LWR@HTML@zeroslash{}{0}
336 \LWR@formatted{zeroslash}

```

File 336 **lwarp-nicefrac.sty**

§ 445 Package **nicefrac**

(Emulates or patches code by AXEL REICHERT.)

Pkg nicefrac

nicefrac is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{nicefrac}[1998/08/04]
2 \DeclareRobustCommand*\LWR@HTML@@UnitsNiceFrac}[3][[]]{%
3   {% localize font selection
4     #1{%
5       \LWR@textcurrentfont{%
6         \InlineClass{numerator}{#2}%
7         /%
8         \InlineClass{denominator}{#3}%
9       }%
10    }%
11  }%
12 }
13
14 \LWR@formatted{@UnitsNiceFrac}
15
16 \DeclareRobustCommand*\LWR@HTML@@UnitsUglyFrac}[3][[]]{%
17   {% localize font selection
18     #1{\LWR@textcurrentfont{#2/#3}}%
19   }%
20 }
21
22 \LWR@formatted{@UnitsUglyFrac}

```

For MATHJAX:

```

23 \begin{warpMathJax}
24 \CustomizeMathJax{newcommand{\nicefrac}[3][[]]{\mathinner{{}^{\#2}\!/_{\#3}}}}
25 \end{warpMathJax}

```

File 337 **lwarp-niceframe.sty**

§ 446 Package **niceframe**

Pkg niceframe

niceframe is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{niceframe}% the original date is in yyyy/dd/mm format
2 \newcommand{\LWR@niceframe}[3]{%
3   \begin{LWR@setvirtualpage}*%
4   \setlength{\LWR@templengthone}{#1}%
5   \begin{BlockClass}[max-width:\LWR@printlength{\LWR@templengthone}]{#3}%
6   #2
7   \end{BlockClass}%
8   \end{LWR@setvirtualpage}%
9 }
10
11 \newcommand{\niceframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{niceframe}}
12 \newcommand{\curlyframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{curlyframe}}
13 \newcommand{\artdecoframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{artdecoframe}}
14
15 \newcommand{\generalframe}[9]{\LWR@niceframe{\textwidth}{#9}{generalframe}}
```

File 338 **lwarp-nicematrix.sty**

§ 447 Package **nicematrix**

Pkg nicematrix

(Emulates or patches code by F. PANTIGNY.)

nicematrix is used as-is for SVG math, and is emulated for MATHJAX.

 **MATHJAX** Keys/values are ignored in MATHJAX. \backslash Cdots, etc. do not span multiple cells. AutoNiceMatrix, etc. are not supported for MATHJAX. SVG math output preserves all nicematrix features. To force SVG output for one or more consecutive math expressions, for inline math use \backslash inlinemathother and \backslash inlinemathnormal, or for display math use \backslash displaymathother and \backslash displaymathnormal.

for HTML output:

```

1 \LWR@ProvidesPackagePass{nicematrix}[2020/11/23]
```

NiceTabular must be converted to SVG to support the various nicematrix options:

```

2 \begin{warpHTML}
3 \BeforeBeginEnvironment{NiceTabular}{%
4   \begin{lateximage}[-nicematrix~\PackageDiagramAltText]%
5 }
6 \AfterEndEnvironment{NiceTabular}{\end{lateximage}}
7 \BeforeBeginEnvironment{NiceTabular*}{%
8   \begin{lateximage}[-nicematrix~\PackageDiagramAltText]%
9 }
10 \AfterEndEnvironment{NiceTabular*}{\end{lateximage}}
11 \end{warpHTML}
```

Special handling for the optional arguments, and the lack of a delimiter:

```

12 \begin{warpMathJax}
13 \CustomizeMathJax{\newcommand{\LWRnicearrayarray}[1]{\begin{array}{#1}}}
14 \CustomizeMathJax{\def\LWRnicearrayarrayopt#1[#2] {\begin{array}{#1}}}
15
16 \CustomizeMathJax{%
17   \newenvironment{NiceArray}[2][{}%
18     {\ifnextchar[{\LWRnicearrayarrayopt{#2}}{\LWRnicearrayarray{#2}}}%
19     {\end{array}}}%
20 }
21
22 \CustomizeMathJax{%
23   \newcommand{\LWRnicearraywithdelimitwo}[2][{}%
24     {\ifnextchar[{\LWRnicearrayarrayopt{#2}}{\LWRnicearrayarray{#2}}}%
25     }%
26 }

```

General case with left / right delimiters:

```

27 \CustomizeMathJax{%
28   \newenvironment{NiceArrayWithDelims}[2]%
29     {%
30       \def\LWRnicearrayrightdelim{\right#2}%
31       \left#1%
32       \LWRnicearraywithdelimitwo%
33     }%
34     {\end{array}\LWRnicearrayrightdelim}%
35 }

```

Instances of specific delimiters:

```

36 \CustomizeMathJax{%
37   \newenvironment{pNiceArray}
38     {\begin{NiceArrayWithDelims}{(}{)}}
39     {\end{NiceArrayWithDelims}}
40 }
41
42 \CustomizeMathJax{%
43   \newenvironment{bNiceArray}
44     {\begin{NiceArrayWithDelims}{[}{]}}
45     {\end{NiceArrayWithDelims}}
46 }
47
48 \CustomizeMathJax{%
49   \newenvironment{BNiceArray}
50     {\begin{NiceArrayWithDelims}{\{}{\}}}}
51     {\end{NiceArrayWithDelims}}
52 }
53
54 \CustomizeMathJax{%
55   \newenvironment{vNiceArray}
56     {\begin{NiceArrayWithDelims}{\vert}{\vert}}
57     {\end{NiceArrayWithDelims}}
58 }
59
60 \CustomizeMathJax{%
61   \newenvironment{VNiceArray}
62     {\begin{NiceArrayWithDelims}{\Vert}{\Vert}}
63     {\end{NiceArrayWithDelims}}

```

64 }

Ignore optional arg and use standard environments:

```
65 \CustomizeMathJax{\newenvironment{NiceMatrix}[1][\begin{matrix}]{\end{matrix}}}
66 \CustomizeMathJax{\newenvironment{pNiceMatrix}[1][\begin{pmatrix}]{\end{pmatrix}}}
67 \CustomizeMathJax{\newenvironment{bNiceMatrix}[1][\begin{bmatrix}]{\end{bmatrix}}}
68 \CustomizeMathJax{\newenvironment{BNiceMatrix}[1][\begin{Bmatrix}]{\end{Bmatrix}}}
69 \CustomizeMathJax{\newenvironment{vNiceMatrix}[1][\begin{vmatrix}]{\end{vmatrix}}}
70 \CustomizeMathJax{\newenvironment{VNiceMatrix}[1][\begin{Vmatrix}]{\end{Vmatrix}}}
```

Ignore optional argument and size. Print contents.

```
71 \CustomizeMathJax{\newcommand{\LWRnicematrixBlock}[1]{#1}}
72 \CustomizeMathJax{\def\LWRnicematrixBlockopt<#1>#2{#2}}
73
74 \CustomizeMathJax{%
75   \newcommand{\Block}[2][\ifnextchar<\LWRnicematrixBlockopt\LWRnicematrixBlock}%
76 }
```

Form an approximation:

```
77 \CustomizeMathJax{%
78   \newcommand{\diagbox}[2]{%
79     \begin{array}{L}\hfill\quad#2\\\hline#1\quad\hfill\end{array}%
80   }%
81 }
```

More approximations:

```
82 \CustomizeMathJax{\let\hdottedline\hdashline}

83 \CustomizeMathJax{\let\Hline\hline}
84
85 \CustomizeMathJax{\newcommand{\ldots}[1][\dots]}
86 \CustomizeMathJax{\newcommand{\Cdots}[1][\cdots]}
87 \CustomizeMathJax{\newcommand{\Vdots}[1][\vdots]}
88 \CustomizeMathJax{\newcommand{\Ddots}[1][\ddots]}
89 \CustomizeMathJax{\newcommand{\Iddots}[1][\mathinner{\unicode{x22F0}}]}
90
91 \CustomizeMathJax{\newcommand{\Hdotsfor}[1][\ldots]}
92 \CustomizeMathJax{\newcommand{\Vdotsfor}[1][\vdots]}
```

There is no way to emulate AutoNiceMatrix in MATHJAX.

```
93 \CustomizeMathJax{\newcommand{\AutoNiceMatrix}[2]{\text{(AutoNiceMatrix #1)}}}
94 \CustomizeMathJax{\let\pAutoNiceMatrix\AutoNiceMatrix}
95 \CustomizeMathJax{\let\bAutoNiceMatrix\AutoNiceMatrix}
96 \CustomizeMathJax{\let\BAutoNiceMatrix\AutoNiceMatrix}
97 \CustomizeMathJax{\let\vAutoNiceMatrix\AutoNiceMatrix}
98 \CustomizeMathJax{\let\VAutoNiceMatrix\AutoNiceMatrix}
99 \end{warpMathJax}
```

File 339 **lwarp-noitcrul.sty**

§ 448 Package **noitcrul**

(Emulates or patches code by PAUL EBERMANN.)

Pkg noitcrul

noitcrul is used as-is for SVG and emulated for MATHJAX.

for HTML output:

```
1 \LWR@ProvidesPackagePass{noitcrul}[2006/04/11]
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\noitUnderline}[1]{\underline{#1}\!}}
4 \end{warpMathJax}
```

File 340 **lwarp-nolbreaks.sty**

§ 449 Package **nolbreaks**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg nolbreaks

nolbreaks is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{nolbreaks}[2012/05/31]
2 \NewDocumentCommand{\nolbreaks}{s m}{\InlineClass{nolbreaks}{#2}}
```

File 341 **lwarp-nomencl.sty**

§ 450 Package **nomencl**

(Emulates or patches code by BORIS VEYTSMAN, BERND SCHANDL, LEE NETHERTON, CV RADHAKRISHNAN.)

Pkg nomencl

nomencl is patched for use by lwarp.

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o
<project>_html.nls
```

for HTML output:

```
1 \LWR@ProvidesPackagePass{nomencl}[2005/09/22]
```

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
2 \def\@@@nomenclature[#1]#2#3{%
3 \def\@tempa{#2}\def\@tempb{#3}%
4 \protected@write\@nomenclaturefile{%
5 {\string\@nomenclatureentry{#1\nom@verb\@tempa @[\nom@verb\@tempa]}%
6 \begingroup\nom@verb\@tempb\protect\nomeqref{\theequation}%
7 |nompageref}{\theLWR@previousautopagelabel}}% lwarp
8 \endgroup
```

```

9 \@esphack}
10
11 \renewcommand*{\pagedeclaration}[1]{, \nameref{\BaseJobname-autopage-#1}}%

```

File 342 **lwarp-nonfloat.sty**

§ 451 Package **nonfloat**

(Emulates or patches code by KAI RASCHER.)

Pkg nonfloat nonfloat is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{nonfloat}[1999/07/05]

```

2 \LetLtxMacro\topcaption\caption
3 \newcommand{\figcaption}{\def\@capttype{figure}\caption}
4 \newcommand{\tabcaption}{\def\@capttype{table}\topcaption}
5 \newenvironment{narrow}[2]{}{}

```

File 343 **lwarp-nonumonpart.sty**

§ 452 Package **nonumonpart**

Pkg nonumonpart nonumonpart is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nonumonpart}[2011/04/15]

File 344 **lwarp-nopageno.sty**

§ 453 Package **nopageno**

Pkg nopageno nopageno is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nopageno}[1989/01/01]

File 345 **lwarp-notes.sty**

§ 454 Package **notes**

Pkg notes notes is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{notes}[2002/10/29]

```

2 \newcommand*\LWR@notes@onenote}[2]{%
3 \newenvironment{#1}
4   {
5     \BlockClass{notes#1}
6     \begin{BlockClass}{notesicon}\textcircled{~#2~}\end{BlockClass}

```

```

7      \BlockClass{notescontents}
8    }
9    {\endBlockClass\endBlockClass}
10 }
11
12 \LWR@notes@onenote{importantnote}{!}
13
14 \LWR@notes@onenote{warningnote}{--}
15
16 \LWR@notes@onenote{informationnote}{i}

```

File 346 **lwarp-notespages.sty**

§ 455 Package **notespages**

Pkg notespages

notespages is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{notespages}[2016/08/21]

```

2 \newcommand*\npnotesname{}
3 \newcommand*\npnotestext{}
4 \newcommand*\remainingtextheight{}
5 \newdimen\remainingtextheight
6 \newcommand*\notestitletext{}
7 \newcommand*\notesareatext{}
8 \newcommand*\npnpinfo[1]{}
9 \newcommand*\tracingnmarks{}
10 \newcommand*\notespage[1][1]{}
11 \newcommand*\notespages[1][1]{}
12 \newcommand*\notesfill[1][1]{}
13 \newcommand*\setnotespages[1]{}
14 \newcommand*\definenotesoption[2]{}
15 \newcommand*\definenotesstyle[2]{}
16 \newcommand*\definetitlestyle[2]{}
17 \newcommand*\nppatchchapter[1]{}
18 \newcommand*\npunpatchchapter{}

```

File 347 **lwarp-nowidow.sty**

§ 456 Package **nowidow**

(Emulates or patches code by RAPHAËL PINSON.)

Pkg nowidow

nowidow is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nowidow}[2011/09/20]

```

\nowidow      [⟨lines⟩]
\setnowidow   [⟨lines⟩]

2 \newcommand*\nowidow[1][1]{}
3 \newcommand*\setnowidow[1][1]{}

```

```

\noclub          [⟨lines⟩]
\setnoclub       [⟨lines⟩]
4 \newcommand*{\noclub}[1][{}]{
5 \newcommand*{\setnoclub}[1][{}]{

```

File 348 **lwarp-ntheorem.sty**

§ 457 Package **ntheorem**

(Emulates or patches code by WOLFGANG MAY, ANDREAS SCHEDLER.)

Pkg ntheorem ntheorem is patched for use by lwarp.

Table 20: Ntheorem package — css styling of theorems and proofs

Theorem: <div> of class theorembody<theoremstyle>

Theorem Header: of class theoremheader<style>

where <theoremstyle> is plain, break, etc.

§ 457.1 Limitations

 **Font control** This conversion is not total. Font control is via css, and the custom L^AT_EX font settings are ignored.

 **Equation numbering** ntheorem has a bug with equation numbering in $\mathcal{A}\mathcal{M}\mathcal{S}$ environments when the option thref is used. lwarp does not share this bug, so equations with \split, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's thref option.

§ 457.2 Options

Options amsthm or standard choose which set of theorems and proofs to initialize.

 **Disabled options** The options thmmarks and amsmath are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option thref is disabled because cleveref functions are used instead. \thref is emulated.

Option hyperref is disabled because lwarp emulated hyperref.

for HTML output: Some disabled options:

```

1 \DeclareOption{thref}{
2   \AtEndDocument{
3     \PackageWarningNoLine{lwarp}{%
4       Lwarp uses cleveref, which takes over ntheorem's\MessageBreak
5       referencing, including
6         \protect\label \space and \protect\thref.\MessageBreak
7       Cleveref does not accept ntheorem's optional\MessageBreak
8       argument for \protect\label, so it will appear\MessageBreak

```

```

9         in the text. It is recommended to remove the\MessageBreak
10        thref option, \protect\usepackage{cleveref} instead,\MessageBreak
11        and remove any trailing optional arguments for \protect\label%
12        }%
13    }
14 }
15
16
17 \newbool{LWR@theoremmarks}
18 \boolfalse{LWR@theoremmarks}
19
20 \DeclareOption{thmmarks}{
21 \booltrue{LWR@theoremmarks}
22 \newif\ifsetendmark\setendmarktrue
23 }
24
25
26 \newbool{LWR@theoremamsthm}
27 \boolfalse{LWR@theoremamsthm}
28
29 \DeclareOption{amsthm}{\booltrue{LWR@theoremamsthm}}
30
31
32 \DeclareOption{amsmath}{}
33 \DeclareOption{hyperref}{}
34
35 \LWR@ProvidesPackagePass{ntheorem}[2011/08/15]

```

§ 457.3 Remembering the theorem style

Storage for the style being used for new theorems.

```

36 \newcommand{\LWR@newtheoremstyle}{plain}

37 \AtBeginDocument{
38 \IfPackageLoadedTF{cleveref}{
39 \gdef\@thm#1#2#3{%
40   \if@thmmarks
41     \stepcounter{end\InTheoType ctr}%
42   \fi
43   \renewcommand{\InTheoType}{#1}%
44   \if@thmmarks
45     \stepcounter{curr#1ctr}%
46     \setcounter{end#1ctr}{0}%
47   \fi
48   \refstepcounter[#1]{#2}% <<< cleveref modification
49   \theorem@prework
50   \LWR@forcenewpage% lwarp

51   \LWR@printpendingfootnotes%           lwarp

52   \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
53   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
54   \ifuse@newframeskips % cf. latex.ltx for topsepadd: \@trivlist
55     \ifthm@inframe
56       \thm@topsep\theoreminframepreskipamount
57     \thm@topsepadd\theoreminframepostskipamount
58     \else
59       \thm@topsep\theorempreskipamount

```

```

60     \thm@topsepadd\theorempostskipamount
61     \fi
62     \else% oldframeskips
63     \thm@topsep\theorempreskipamount
64     \thm@topsepadd \theorempostskipamount
65     \ifvmode\advance\thm@topsepadd\partopsep\fi
66     \fi
67     \@topsep\thm@topsep
68     \@topsepadd\thm@topsepadd
69     \advance\linewidth -\theorem@indent
70     \advance\linewidth -\theorem@rightindent
71     \advance\@totalleftmargin \theorem@indent
72     \parshape \@ne \@totalleftmargin \linewidth
73     \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
74 }
75 }{% not @ifpackageloaded{cleveref}
76 \gdef\@thm#1#2#3{%
77     \if@thmmarks
78         \stepcounter{end\InTheoType ctr}%
79         \fi
80     \renewcommand{\InTheoType}{#1}%
81     \if@thmmarks
82         \stepcounter{curr#1ctr}%
83         \setcounter{end#1ctr}{0}%
84     \fi
85     \refstepcounter{#2}%
86     \theorem@prework
87     \LWR@forcenewpage% lwarp

88     \LWR@printpendingfootnotes%                lwarp

89     \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
90     \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
91     \ifuse@newframeskips % cf. latex.ltx for topsepadd: \@trivlist
92         \ifthm@inframe
93             \thm@topsep\theoreminframepreskipamount
94             \thm@topsepadd\theoreminframepostskipamount
95         \else
96             \thm@topsep\theorempreskipamount
97             \thm@topsepadd\theorempostskipamount
98         \fi
99     \else% oldframeskips
100     \thm@topsep\theorempreskipamount
101     \thm@topsepadd \theorempostskipamount
102     \ifvmode\advance\thm@topsepadd\partopsep\fi
103     \fi
104     \@topsep\thm@topsep
105     \@topsepadd\thm@topsepadd
106     \advance\linewidth -\theorem@indent
107     \advance\linewidth -\theorem@rightindent
108     \advance\@totalleftmargin \theorem@indent
109     \parshape \@ne \@totalleftmargin \linewidth
110     \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
111 }
112 }
113 }% AtBeginDocument

```

Patched to remember the style being used for new theorems:

```

114 \gdef\theoremstyle#1{%
115   \ifundefined{th@#1}{\@warning
116     {Unknown theoremstyle '#1'. Using 'plain'}}%
117     \theoremstyle{plain}
118     \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
119   }%
120   {
121     \theoremstyle{#1}
122     \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
123   }
124 }

```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

125
126 \gdef\xnthm#1#2[#3]{%
127   \ifthm@tempif
128     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
129     \expandafter\ifundefined{c@#1}%
130       {\definecounter{#1}}}%
131     \@newctr{#1}[#3]%
132     \expandafter\xdef\csname the#1\endcsname{%
133       \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
134         {\noexpand\csname\the\theoremnumbering\endcsname{#1}}}%
135     \expandafter\gdef\csname mkheader@#1\endcsname
136       {\csname setparms@#1\endcsname
137         \@thm{#1}{#1}{#2}
138       }%
139     \global\@namedef{end#1}{\@endtheorem}
140     \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
141   \fi
142 }
143
144 \gdef\ynthm#1#2{%
145   \ifthm@tempif
146     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
147     \expandafter\ifundefined{c@#1}%
148       {\definecounter{#1}}}%
149     \expandafter\xdef\csname the#1\endcsname
150       {\noexpand\csname\the\theoremnumbering\endcsname{#1}}}%
151     \expandafter\gdef\csname mkheader@#1\endcsname
152       {\csname setparms@#1\endcsname
153         \@thm{#1}{#1}{#2}
154       }%
155     \global\@namedef{end#1}{\@endtheorem}
156     \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
157   \fi
158 }
159
160 \gdef\othm#1[#2]#3{%
161   \ifundefined{c@#2}{\@nocounterr{#2}}%
162   {\ifthm@tempif
163     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
164     \global\@namedef{the#1}{\@nameuse{the#2}}%
165     \expandafter\protected@xdef\csname num@addtheoremline#1\endcsname{%
166       \noexpand\@num@addtheoremline{#1}{#3}}%
167     \expandafter\protected@xdef\csname nonum@addtheoremline#1\endcsname{%
168       \noexpand\@nonum@addtheoremline{#1}{#3}}%
169     \theoremkeyword{#3}%

```

```

170 \expandafter\protected@xdef\csname #1Keyword\endcsname
171     {\the\theoremkeyword}%
172 \expandafter\gdef\csname mkheader@#1\endcsname
173     {\csname setparms@#1\endcsname
174       \@thm{#1}{#2}{#3}
175     }%
176 \global\@namedef{end#1}{\@endtheorem}
177 \AtBeginEnvironment{#1}{\edef\LWR@thmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
178 \fi}
179 }

```

§ 457.4 HTML cross-referencing

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```

180 \newcommand{\LWR@intheorem}{%
181 \addtocounter{LWR@thisautoid}{1}%
182 \LWR@stoppars%
183 \LWR@htmltag{%
184   a id=\textquotedbl\LWR@print@mbbox{autoid-\arabic{LWR@thisautoid}}\textquotedbl%
185 }%
186 \LWR@htmltag{/a}\LWR@orignewline%
187 \LWR@startpars%
188 }

```

§ 457.5 \newtheoremstyle

The following are patched for css.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a BlockClass environment of class theorembody<style>.

Each header is encased in an InlineClass of class theoremheader<style>.

```

189 \gdef\newtheoremstyle#1#2#3{%
190 \expandafter\@ifundefined{th@#1}%
191   {\expandafter\gdef\csname th@#1\endcsname{%
192     \def\@begintheorem####1####2{%
193       \LWR@intheorem% lwarp
194       #2}%
195     \def\@opargbegintheorem####1####2####3{%
196       \LWR@intheorem% lwarp
197       #3}%
198   }%
199 }%
200 {\PackageError{\basename}{Theorem style #1 already defined}\@eha}
201 }

```

§ 457.6 **Standard styles**

```

202 \renewtheoremstyle{plain}%
203   {\item[
204     \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]]%
205   {\item[
206     \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]]}
207
208 \renewtheoremstyle{break}%
209   {\item[
210     \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
211   ]}%
212   {\item[
213     \InlineClass{theoremheaderbreak}%
214     {##1\ ##2\ (##3)\theorem@separator}\newline
215   ]}
216
217 \renewtheoremstyle{change}%
218   {\item[
219     \InlineClass{theoremheaderchange}{##2\ ##1\theorem@separator}]]%
220   {\item[
221     \InlineClass{theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]]}
222
223 \renewtheoremstyle{changebreak}%
224   {\item[
225     \InlineClass{theoremheaderchangebreak}%
226     {##2\ ##1\theorem@separator}\newline
227   ]}%
228   {\item[
229     \InlineClass{theoremheaderchangebreak}%
230     {##2\ ##1\ (##3)\theorem@separator}\newline
231   ]}
232
233 \renewtheoremstyle{margin}%
234   {\item[
235     \InlineClass{theoremheadermargin}{##2 \quad ##1\theorem@separator}
236   ]}%
237   {\item[
238     \InlineClass{theoremheadermargin}{##2 \quad ##1\ (##3)\theorem@separator}
239   ]}
240
241 \renewtheoremstyle{marginbreak}%
242   {\item[
243     \InlineClass{theoremheadermarginbreak}%
244     {##2 \quad ##1\theorem@separator}\newline
245   ]}%
246   {\item[
247     \InlineClass{theoremheadermarginbreak}%
248     {##2 \quad ##1\ (##3)\theorem@separator}\newline
249   ]}
250
251 \renewtheoremstyle{nonumberplain}%
252   {\item[
253     \InlineClass{theoremheaderplain}{##1\theorem@separator}]]%
254   {\item[
255     \InlineClass{theoremheaderplain}{##1\ (##3)\theorem@separator}]]}
256
257 \renewtheoremstyle{nonumberbreak}%
258   {\item[
259     \InlineClass{theoremheaderbreak}{##1\theorem@separator}\newline

```

```

260   ]}%
261   {\item[
262     \InlineClass{theoremheaderbreak}{##1\ (##3)\theorem@separator}\newline
263   ]}
264
265 \renewtheoremstyle{empty}%
266   {\item[]}%
267   {\item[
268     \InlineClass{theoremheaderplain}{##3}]}
269
270 \renewtheoremstyle{emptybreak}%
271   {\item[]}%
272   {\item[
273     \InlineClass{theoremheaderplain}{##3}] \ \newline}

```

§ 457.7 Additional objects

The following manually adjust the css for the standard configuration objects which are not a purely plain style:

```
274 \ifbool{LWR@theoremamsthm}{}{%
```

Upright text via CSS:

```

275   \newtheoremstyle{plainupright}%
276   {\item[
277     \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
278   {\item[
279     \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}

```

Upright text and small caps header via CSS:

```

280   \newtheoremstyle{nonumberplainuprightsc}%
281   {\item[
282     \InlineClass{theoremheadersc}{##1\theorem@separator}]}%
283   {\item[
284     \InlineClass{theoremheadersc}{##1\ (##3)\theorem@separator}]}
285 ]% not amsthm

```

§ 457.8 Renewed standard configuration

The following standard configuration is renewed using the new css:

```

286 \ifbool{LWR@theoremamsthm}{}{%

287 \ifx\thm@usestd\@undefined
288 \else
289   \theoremnumbering{arabic}
290   \theoremstyle{plain}
291   \RequirePackage{latexsym}
292   \theoremsymbol{\Box}
293   \theorembodyfont{\itshape}
294   \theoremheaderfont{\normalfont\bfseries}
295   \theoremseparator{}
296   \renewtheorem{Theorem}{Theorem}
297   \renewtheorem{theorem}{Theorem}
298   \renewtheorem{Satz}{Satz}
299   \renewtheorem{satz}{Satz}

```

```

300 \renewtheorem{Proposition}{Proposition}
301 \renewtheorem{proposition}{Proposition}
302 \renewtheorem{Lemma}{Lemma}
303 \renewtheorem{lemma}{Lemma}
304 \renewtheorem{Korollar}{Korollar}
305 \renewtheorem{korollar}{Korollar}
306 \renewtheorem{Corollary}{Corollary}
307 \renewtheorem{corollary}{Corollary}
308
309 \theoremstyle{plainupright}
310 \theorembodyfont{\upshape}
311 \theoremsymbol{\HTMLUnicode{25A1}}% UTF-8 white box
312 \renewtheorem{Example}{Example}
313 \renewtheorem{example}{Example}
314 \renewtheorem{Beispiel}{Beispiel}
315 \renewtheorem{beispiel}{Beispiel}
316 \renewtheorem{Bemerkung}{Bemerkung}
317 \renewtheorem{bemerkung}{Bemerkung}
318 \renewtheorem{Anmerkung}{Anmerkung}
319 \renewtheorem{anmerkung}{Anmerkung}
320 \renewtheorem{Remark}{Remark}
321 \renewtheorem{remark}{Remark}
322 \renewtheorem{Definition}{Definition}
323 \renewtheorem{definition}{Definition}
324
325 \theoremstyle{nonumberplainuprightsc}
326 \theoremsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
327 \renewtheorem{Proof}{Proof}
328 \renewtheorem{proof}{Proof}
329 \renewtheorem{Beweis}{Beweis}
330 \renewtheorem{beweis}{Beweis}
331 \qedsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
332
333 \theoremsymbol{}
334 \fi
335 }% not amsthm

```

§ 457.9 amsthm option

Only if the amsthm option was given:

```

336 \ifbool{LWR@ntheoremamsthm}{
337
338 \gdef\th@plain{%
339 \def\theorem@headerfont{\normalfont\bfseries}\itshape%
340 \def\@begintheorem##1##2{%
341 \LWR@intheorem% lwarp
342 \item[
343 \InlineClass{theoremheaderplain}{##1\ ##2.}
344 ]}%
345 \def\@opargbegintheorem##1##2##3{%
346 \LWR@intheorem% lwarp
347 \item[
348 \InlineClass{theoremheaderplain}{##1\ ##2\ (##3).}
349 ]}}
350
351 \gdef\th@nonumberplain{%
352 \def\theorem@headerfont{\normalfont\bfseries}\itshape%
353 \def\@begintheorem##1##2{%
354 \LWR@intheorem% lwarp

```

```
355     \item[
356 \InlineClass{theoremheaderplain}{##1.}
357     ]}%
358 \def\@opargbegintheorem##1##2##3{%
359     \LWR@intheorem% lwarp
360     \item[
361 \InlineClass{theoremheaderplain}{##1\ (#3).}
362     ]}}
363
364 \gdef\th@definition{%
365 \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
366 \def\@begintheorem##1##2{%
367     \LWR@intheorem% lwarp
368     \item[
369 \InlineClass{theoremheaderdefinition}{##1\ ##2.}
370     ]}%
371 \def\@opargbegintheorem##1##2##3{%
372     \LWR@intheorem% lwarp
373     \item[
374 \InlineClass{theoremheaderdefinition}{##1\ ##2\ (#3).}
375     ]}}
376
377 \gdef\th@nonumberdefinition{%
378 \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
379 \def\@begintheorem##1##2{%
380     \LWR@intheorem% lwarp
381     \item[
382 \InlineClass{theoremheaderdefinition}{##1.}
383     ]}%
384 \def\@opargbegintheorem##1##2##3{%
385     \LWR@intheorem% lwarp
386     \item[
387 \InlineClass{theoremheaderdefinition}{##1\ (#3).}
388     ]}}
389
390 \gdef\th@remark{%
391 \def\theorem@headerfont{\itshape}\normalfont%
392 \def\@begintheorem##1##2{%
393     \LWR@intheorem% lwarp
394     \item[
395 \InlineClass{theoremheaderremark}{##1\ ##2.}
396     ]}%
397 \def\@opargbegintheorem##1##2##3{%
398     \LWR@intheorem% lwarp
399     \item[
400 \InlineClass{theoremheaderremark}{##1\ ##2\ (#3).}
401     ]}}
402
403 \gdef\th@nonumberremark{%
404 \def\theorem@headerfont{\itshape}\normalfont%
405 \def\@begintheorem##1##2{%
406     \LWR@intheorem% lwarp
407     \item[
408 \InlineClass{theoremheaderremark}{##1.}
409     ]}%
410 \def\@opargbegintheorem##1##2##3{%
411     \LWR@intheorem% lwarp
412     \item[
413 \InlineClass{theoremheaderremark}{##1\ (#3).}
414     ]}}
```

```

415
416 \gdef\th@proof{%
417   \def\theorem@headerfont{\normalfont\bfseries}\itshape%
418   \def\@begintheorem##1##2{%
419     \LWR@intheorem% lwarp
420     \item[
421       \InlineClass{theoremheaderproof}{##1.}
422     ]}%
423   \def\@opargbegintheorem##1##2##3{%
424     \LWR@intheorem% lwarp
425     \item[
426       \InlineClass{theoremheaderproof}{##1\ (##3).}
427     ]}}
428
429
430
431 \newcounter{proof}%
432 \if@thmmarks
433   \newcounter{currproofctr}%
434   \newcounter{endproofctr}%
435 \fi
436
437 \gdef\proofSymbol{\openbox}
438
439 \newcommand{\proofname}{Proof}
440
441 \newenvironment{proof}[1][\proofname]{
442   \th@proof
443   \def\theorem@headerfont{\itshape}%
444   \normalfont
445   \theoremsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
446   \@thm{proof}{proof}{#1}
447 }%
448 {\@endtheorem}
449
450 }{% amsthm option

```

§ 457.10 Ending a theorem

Patched for CSS:

```

451 \let\LWR@origendtheorem\@endtheorem
452 \renewcommand{\@endtheorem}{%
453   \ifbool{LWR@theoremmarks}{%
454     \ifsetendmark%
455     \InlineClass{theoremendmark}{\csname\InTheoType Symbol\endcsname}%
456     \setendmarkfalse%
457     \fi%
458   }{%
459     \LWR@origendtheorem% also does \@endtrivlist
460     \ifbool{LWR@theoremmarks}{\global\setendmarktrue}{%
461       \LWR@printpendingfootnotes%
462       lwarp
463     }

```

§ 457.11 **\NoEndMark**

```
464 \gdef\NoEndMark{\global\setendmarkfalse}
```

§ 457.12 **List-of**

Redefined to reuse the float mechanism to add list-of-theorem links:

```
\thm@thmline {<1: printed type>} {<2: #>} {<3: optional>} {<4: page>}
```

```
465 \renewcommand{\thm@thmline@noname}[4]{%
466 \hypertocfloat{1}{theorem}{thm}{#2 #3}{}%
467 }
468
469 \renewcommand{\thm@thmline@name}[4]{%
470 \hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}%
471 }
```

This was redefined by `ntheorem` when loaded, so it is now redefined for `lwarp`:

```
472 \def\thm@thmline{\thm@thmline@name}
```

Patch for css:

```
473 \def\listtheorems#1{
474 \LWR@htmlElementclass{nav}{lothm}%
475 \begingroup
476 \c@tocdepth=-2%
477 \def\thm@list{#1}\thm@processlist
478 \endgroup
479 \LWR@htmlElementclassend{nav}{lothm}%
480 }
```

§ 457.13 **Symbols**

Proof QED symbol:

```
481 \newcommand{\qed}{\quad\the\qedsymbol}
482
483 \AtBeginDocument{
484 \@ifundefined{LWR@orig@openbox}{
485 \LetLtxMacro\LWR@orig@openbox\openbox
486 \LetLtxMacro\LWR@orig@blacksquare\blacksquare
487 \LetLtxMacro\LWR@orig@Box\Box
488
489 \def\openbox{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
490 \def\blacksquare{\text{\HTMLUnicode{220E}}}% UTF-8 end-of-proof
491 \def\Box{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
492
493 \appto\LWR@restoreorigformatting{%
494 \LetLtxMacro\openbox\LWR@orig@openbox%
495 \LetLtxMacro\blacksquare\LWR@orig@blacksquare%
496 \LetLtxMacro\Box\LWR@orig@Box%
497 }% appto
498 }{}% @ifundefined
499 }% AtBeginDocument
```

§ 457.14 **Cross-referencing**

```
\thref {<label>}
```

```
500 \newcommand*{\thref}[1]{\cref{#1}}%
```

File 349 **lwarp-octave.sty**§ 458 Package **octave**

(Emulates or patches code by ANDREW A. CASHNER.)

Pkg octave

octave is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{octave}[2017/10/31]

Remove the leading 1pt kern:

```
2 \RenewDocumentCommand{\@PrintTicks}{ m }{%
3 \kern-1pt% lwarp
4 \@TickNum = #1%
5 \loop
6 \@Tick{}%
7 \advance\@TickNum by -1
8 \ifnum\@TickNum > 0
9 \repeat
10 }
```

Use unicode for the prime character:

```
11 \RenewDocumentCommand{\@Tick}{\}{\HTMLunicode{2032}}
```

Catch the inline font:

```
12 \RenewDocumentCommand{\pitch}{ m o m }{%
13 \if@OctaveNumber%
14 {%
15   \pitchfont{%
16     \LWR@textcurrentfont{% lwarp
17       \MakeUppercase{#1}%
18       \IfValueTF{#2}{#2}{\textsubscript{#3}}%
19     }%
20   }%
21 }%
22 \else%
23 {%
24   \pitchfont{%
25     \LWR@textcurrentfont{% lwarp
26       \@GetOctaveTick{#1}[#2]{#3}%
27     }%
28   }%
29 }%
30 \fi%
31 }
```

The original was hard to adapt to lwarp's handling of &.

```

32 \StartDefiningTabulars
33 \renewcommand{\octavetable}{%
34 \begin{tabular}{ll}
35 \octaveprimes \pitch{C}{0} & \octavenumbers \pitch{C}{0} \\
36 \octaveprimes \pitch{C}{1} & \octavenumbers \pitch{C}{1} \\
37 \octaveprimes \pitch{C}{2} & \octavenumbers \pitch{C}{2} \\
38 \octaveprimes \pitch{C}{3} & \octavenumbers \pitch{C}{3} \\
39 \octaveprimes \pitch{C}{4} & \octavenumbers \pitch{C}{4} \\
40 \octaveprimes \pitch{C}{5} & \octavenumbers \pitch{C}{5} \\
41 \octaveprimes \pitch{C}{6} & \octavenumbers \pitch{C}{6} \\
42 \octaveprimes \pitch{C}{7} & \octavenumbers \pitch{C}{7} \\
43 \end{tabular}
44 }
45 \StopDefiningTabulars

```

File 350 **lwarp-orcidlink.sty**

§ 459 Package **orcidlink**

(Emulates or patches code by LEO C. STEIN.)

Pkg orcidlink

orcidlink is patched for use by lwarp.

for HTML output:

```

1 \RequirePackage{lwarp-scalerel}
2
3 \LWR@ProvidesPackagePass{orcidlink}[2020/11/21]
4
5 \renewcommand\orcidlink[1]{%
6   \texorpdfstring%
7     {%
8       \href%
9         {https://orcid.org/#1}%
10        {%
11          \begin{lateximage}[orcid #1]%   lwarp
12            \mbox{%
13              \scalerel*{%
14                \begin{tikzpicture}[yscale=-1,transform shape]
15                  \pic{orcidlogo};
16                  \end{tikzpicture}
17                }{|}%
18              }%
19            \end{lateximage}%   lwarp
20          }%
21        }%
22 }
23
24 \begin{warpMathJax}
25 \CustomizeMathJax{\newcommand{\orcidlink}[1]{} }
26 \end{warpMathJax}

```

File 351 **lwarp-overpic.sty**§ 460 Package **overpic***(Emulates or patches code by ROLF NIEPRASCHK.)*

Pkg overpic

overpic is patched for use by lwarp.

 **scaling**

The macros `\overpicfontsize` and `\overpicfontskip` are used during HTML generation. These are sent to `\fontsize` to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the `overpic` and `Overpic` environments.

See section 88.2 for the print-mode version of `\overpicfontsize` and `\overpicfontskip`.

for HTML output:

```

1 \LWR@ProvidesPackagePass{overpic}[2017/10/06]
2 \newcommand*\overpicfontsize{12}
3 \newcommand*\overpicfontskip{14}
4
5 \BeforeBeginEnvironment{overpic}{%
6   \begin{lateximage}%
7     \fontsize{\overpicfontsize}{\overpicfontskip}%
8     \selectfont%
9 }
10
11 \AfterEndEnvironment{overpic}{\end{lateximage}}
12
13 \BeforeBeginEnvironment{Overpic}{%
14   \begin{lateximage}%
15     \fontsize{\overpicfontsize}{\overpicfontskip}%
16     \selectfont%
17 }
18
19 \AfterEndEnvironment{Overpic}{\end{lateximage}}
```

File 352 **lwarp-pagegrid.sty**§ 461 Package **pagegrid**

Pkg pagegrid

pagegrid is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{pagegrid}[2016/05/16]
2 \newcommand*\pagegridsetup[1]{}

```

File 353 **lwarp-pagenote.sty**§ 462 Package **pagenote**

Pkg pagenote

pagenote works as-is, but the `page` option is disabled.

 **labels** Note that labels in page notes do not appear as expected, even in the print version.

for HTML output:

```
1 \DeclareOption{page}{}
2 \LWR@ProvidesPackagePass{pagenote}[2009/09/03]
```

For MATHJAX:

```
3 \begin{warpMathJax}
4 \appto\LWR@syncnotenumbers{\LWR@synconenotenummer{LWRpagenote}{\thepagenote}}
5 \CustomizeMathJax{\def\LWRpagenote{1}}
6 \CustomizeMathJax{\newcommand{\pagenote}[2][\LWRpagenote]{{}^{\mathrm{#1}}}}
7 \end{warpMathJax}
```

There is no `\pagenotemark`, so the following are not required:

```
\providecommand{\pagenotename}{pagenote}
\appto\LWR@syncnotenames{\LWR@synconenotename{LWRpagenote}{\pagenotename}}
```

File 354 **lwarp-pagesel.sty**

§ 463 Package **pagesel**

Pkg pagesel pagesel is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{pagesel}[2016/05/16]
```

File 355 **lwarp-paralist.sty**

§ 464 Package **paralist**

(Emulates or patches code by BERND SCHANDL.)

Pkg paralist paralist is supported with minor changes.

for HTML output:

```
1 \LWR@ProvidesPackagePass{paralist}[2017/01/22]
```

The compact environments are identical to the regular ones:

```
2 \LetLtxMacro\compactitem\itemize
3 \LetLtxMacro\compactenum\enumerate
4 \LetLtxMacro\compactdesc\description
5 \LetLtxMacro\endcompactitem\enditemize
6 \LetLtxMacro\endcompactenum\endenumerate
7 \LetLtxMacro\endcompactdesc\enddescription
```

For the inline environments, revert `\item` to its original print-mode version:

```
8 \AtBeginEnvironment{inparaitem}{\LetLtxMacro\item\LWR@origitem}
9 \AtBeginEnvironment{inparaenum}{\LetLtxMacro\item\LWR@origitem}
10 \AtBeginEnvironment{inparadesc}{\LetLtxMacro\item\LWR@origitem}
```

Manual formatting of the description labels:

```
11 \def\paradescriptionlabel#1{\normalfont\textbf{#1}}
```

File 356 **lwarp-parallel.sty**

§ 465 Package **parallel**

(Emulates or patches code by MATTHIAS ECKERMANN.)

Pkg parallel

parallel is emulated.

Package options are ignored. Footnotes are treated as normal lwarp footnotes.

Environment option `c` gives side-by-side `<div>`s of class `minipage`, each of whose width is a percent depending on the given left and right widths, proportional to `\linewidth`.

Inside each environment, `\linewidth` and `\textwidth` are set for the print-output sizes.

for HTML output: Discard all options for `lwarp-parallel`:

```

1 \LWR@ProvidesPackageDrop{parallel}[2003/04/13]

2 \newcounter{LWR@parallel@Lwidth}
3 \newcounter{LWR@parallel@Rwidth}
4 \newcommand*{\LWR@parallel@border}
5
6 \newenvironment*{Parallel}[3][[%
7   {%
8     \LWR@printpendingfootnotes%
9     \setlength{\linewidth}{\LWR@userstextwidth}%
10    \setlength{\textwidth}{\LWR@userstextwidth}%
11    \renewcommand*{\LWR@parallel@border}{}%
12    \ifstrequal{#1}{v}%
13      {%
14        \renewcommand*{\LWR@parallel@border}{ ; border-left: 2px solid black}%
15      }%
16    }%
17  \ifblank{#2}{%
18    \ifblank{#3}{% {}{}
19      \setcounter{LWR@parallel@Lwidth}{45}%
20      \setcounter{LWR@parallel@Rwidth}{45}%
21    }% {}{}
22    {% {}{x}
23      \setlength{\LWR@templengthone}{\linewidth-#3}%
24      \setcounter{LWR@parallel@Lwidth}{%
25        90*\ratio{\LWR@templengthone}{\linewidth}%
26      }%
27      \setcounter{LWR@parallel@Rwidth}{%
28        90*\ratio{#3}{\linewidth}%
29      }%
30    }% {}{x}
31  }% #2 blank
32  {% #2 non-blank
33    \ifblank{#3}{% {}{}
34      \setcounter{LWR@parallel@Lwidth}{%
35        90*\ratio{#2}{\linewidth}%
36    }%

```

```

37         \setlength{\LWR@templengthone}{\linewidth-#2}%
38         \setcounter{LWR@parallel@Rwidth}{%
39             90*\ratio{\LWR@templengthone}{\linewidth}%
40         }%
41     }% {x}{
42     }% {x}{x}
43         \setcounter{LWR@parallel@Lwidth}{%
44             90*\ratio{#2}{\linewidth}%
45         }%
46         \setcounter{LWR@parallel@Rwidth}{%
47             90*\ratio{#3}{\linewidth}%
48         }%
49     }% {x}{x}
50 }% #2 non-blank
51 }
52 {%
53     \ParallelAtEnd%
54     \renewcommand*\ParallelAtEnd{}%
55     \LWR@printpendingfootnotes%
56 }
57
58 \newcommand*\ParallelLText}[1]{%
59     \begin{BlockClass}[%
60         width:\arabic{LWR@parallel@Lwidth}\% ; % space
61         padding: .5ex 1\% ; % space
62     ]{minipage}%
63     #1%
64     \end{BlockClass}%
65 }
66
67 \newcommand*\ParallelRText}[1]{%
68     \begin{BlockClass}[%
69         width:\arabic{LWR@parallel@Rwidth}\% ; % space
70         padding: .5ex 1\% ; % space
71         \LWR@parallel@border%
72     ]{minipage}%
73     #1%
74     \end{BlockClass}%
75 }
76
77 \newcommand*\ParallelPar{\LWR@printpendingfootnotes}
78
79 \newcommand*\ParallelAtEnd{}

```

File 357 **lwarp-parcolumns.sty**

§ 466 Package **parcolumns**

(Emulates or patches code by JONATHAN SAUER.)

Pkg parcolumns

parcolumns is emulated.

rulebetween is honored. The other keys are ignored, including colwidths.

Each column is placed inside a <div> of class minipage, each of whose width is fixed at 85% divided by the number of columns. In most cases, this results in side-by-side minipages adapting to the browser width. Inside each minipage,

`\linewidth`, `\textwidth`, and `\textheight` are set for a virtual 6×9 inch page, with `\linewidth` divided by the number of columns.

for HTML output: Discard all options for `lwarp-parcolumns`:

```

1 \RequirePackage{keyval}%
2
3 \LWR@ProvidesPackageDrop{parcolumns}[2004/11/25]

4 \newcounter{LWR@parcolumns@numcols}
5 \newcounter{LWR@parcolumns@thiscol}
6 \newcounter{LWR@parcolumns@width}
7 \newbool{LWR@parcolumns@started}
8 \newbool{LWR@parcolumns@rule}
9
10 \define@key{LWRparcols}{colwidths}{}
11 \define@key{LWRparcols}{distance}{}
12 \define@key{LWRparcols}{rulebetween}[true]{%
13   \setbool{LWR@parcolumns@rule}{#1}%
14 }
15 \define@key{LWRparcols}{nofirstindent}{}
16 \define@key{LWRparcols}{sloppy}{}
17 \define@key{LWRparcols}{sloppyspaces}{}
18
19 \newenvironment*{parcolumns}[2][
20   {%
21     \begin{LWR@setvirtualpage}*[#2]%
22     \setcounter{LWR@parcolumns@numcols}{#2}%
23     \setcounter{LWR@parcolumns@thiscol}{1}%
24     \boolfalse{LWR@parcolumns@started}%
25     \boolfalse{LWR@parcolumns@rule}%
26     \setcounter{LWR@parcolumns@width}{%
27       85/#2
28     }%
29     \setkeys{LWRparcols}{#1}%
30   }
31   {%

32     \colplacechunks%
33     \end{LWR@setvirtualpage}%
34   }
35
36 \newcommand{\LWR@parcolumns@onecol}[1]{%
37   \ifbool{LWR@parcolumns@started}%
38     {}%
39     {%
40       \LWR@htmldivclass{parcolumns}%
41       \booltrue{LWR@parcolumns@started}%
42     }%
43   \ifboolexpr{%
44     bool {LWR@parcolumns@rule} and
45     test {%
46       \ifnumgreater
47         {\value{LWR@parcolumns@thiscol}}
48         {1}
49     }%
50   }%
51   {\renewcommand{\LWR@tempone}{ ; border-left: 2px solid black}}%
52   {\renewcommand{\LWR@tempone}{}}%
53   \begin{BlockClass}[%

```

```

54     width:\arabic{LWR@parcolumns@width}\% ; % space
55     padding: .5ex 1\% ; % space
56     \LWR@tempone%
57   ]{minipage}%
58   #1%
59   \end{BlockClass}%
60   \addtocounter{LWR@parcolumns@thiscol}{1}%
61 }
62
63 \newcommand{\colchunk}[2][\value{LWR@parcolumns@thiscol}]{%
64   \whilebool{expr{%
65     test {%
66       \ifnumcomp%
67         {\value{LWR@parcolumns@thiscol}}
68         {<}
69         {#1}%
70     }%
71   }{%
72     \LWR@parcolumns@onecol}%
73   }%
74   \LWR@parcolumns@onecol{#2}%
75 }
76
77 \newcommand*\colplacechunks{%
78   \ifbool{LWR@parcolumns@started}%
79   {%
80     \LWR@htmldivclassend{div}%
81     \boolfalse{LWR@parcolumns@started}%
82   }%
83   {%
84     \setcounter{LWR@parcolumns@thiscol}{1}%
85 }

```

File 358 **lwarp-parnotes.sty**

§ 467 Package **parnotes**

(Emulates or patches code by CHELSEA HUGHES.)

Pkg parnotes

parnotes is supported with some patches.

for HTML output:

```

1 \LWR@ProvidesPackagePass{parnotes}[2019/07/23]
2 \long\def\PN@parnote@real#1#2{%
3   \parnotemark{#1}%
4   % Unless this is the first parnote in \PN@text, add a separator first
5   \unless\ifx\PN@text\@empty\g@addto@macro\PN@text{\parnoteintercmd}\fi
6   % Redefine \@currentlabel to the parnote label, so \label works
7   \g@addto@macro\PN@text{%
8     \phantomsection%
9     \def\@currentlabel{#1}%
10    \def\cref@currentlabel{%          lwarp
11      [parnotemark][\arabic{parnotemark}][\theparnotemark%
12    }%
13  }%
14  \g@addto@macro\PN@text{%
15    \LWR@textcurrentfont{%          lwarp

```

```

16         \parnotemark{#1}\nolinebreak\thinspace#2%
17     }%
18 }%
19 }
20
21 \def\PN@parnotes@real{%

```

```

22 \ifPN@inparnotes
23 \else

```

```

24 \LWR@stoppars%

```

Avoid nested paragraphs:

```

25 \addtocounter{LWR@spandepth}{1}%

26 % We call \par later, so this avoids recursion with \PN@parnotes@auto
27 \PN@inparnotestruer
28 % \unless\ifvmode\par\fi
29 % Avoid page breaks between a paragraph and its parnotes
30 % \nopagebreak\addvspace{\parnotevskip}%
31 \begin{BlockClass}(note){footnotes}% lwarp
32 \leavevmode\LWR@orignewline%

```

Typeset the parnote inside its own group to avoid global changes:

```

33 {%
34     \parnotefmt{\PN@text}%
35 }%
36 \leavevmode\LWR@orignewline%
37 \end{BlockClass}% lwarp

38 \leavevmode\LWR@orignewline%
39 \global\def\PN@text{%
40 %
41 % These can be enabled or disabled by package options
42 %
43 \PN@disable@indent
44 \PN@reset@optional
45 \PN@inparnotesfalse

```

Reenable normal paragraph handling:

```

46 \addtocounter{LWR@spandepth}{-1}%
47 \fi
48 }

49 \newbool{LWR@parnotes@doingauto}
50 \boolfalse{LWR@parnotes@doingauto}

51 \def\PN@parnotes@auto{%
52     \ifbool{LWR@parnotes@doingauto}{
53         \ifx\@currrent\@PN@autopn
54             \unless\ifPN@inparnotes
55                 \unless\ifx\PN@text\@empty
56                 \expandafter\PN@parnotes@real

```

```

57             \fi
58         \fi
59     \fi
60 }{}%
61 }

```

Replace original logic due to the use of new L^AT_EX paragraph hook handling:

```

62 \renewenvironment{autopn}%
63     {\booltrue{LWR@parnotes@doingauto}}
64     {\PN@parnotes@auto}%

```

If `cleveref` is in use, name the new notes:

```

65 \AtBeginDocument{
66     \ifdef{\crefname}{
67         \crefname{parnotemark}{paragraph note}{paragraph notes}
68         \Crefname{parnotemark}{Paragraph note}{Paragraph notes}
69     }{}
70 }

```

To nullify the footnotes where necessary:

```

71 \apptocmd{\LWR@nullifyfootnotes}{%
72     \renewcommand{\parnote}[2][{}]{}%
73     \renewcommand\parnotemark[1]{}%
74 }{}{}

```

For MATHJAX:

```

75 \begin{warpMathJax}
76 \providecommand{\parnotename}{parnote}
77 \appto\LWR@syncnotenumbers{%
78     \addtocounter{parnotemark}{-1}% specific to parnotes
79     \LWR@syncnotenotenummer{\LWRparnote}{\theparnotemark}%
80     \addtocounter{parnotemark}{1}% specific to parnotes
81 }
82 \appto\LWR@syncnotenames{\LWR@syncnotenotename{\LWRparnote}{\parnotename}}
83 \CustomizeMathJax{\def\LWRparnote{1}}
84 \CustomizeMathJax{\newcommand{\parnote}[2][\LWRparnote]{\mathrm{#1}}}
85 \CustomizeMathJax{\newcommand{\parnotemark}[1][\LWRparnote]{\mathrm{#1}}}
86 \end{warpMathJax}

```

File 359 **lwarp-parskip.sty**

§ 468 Package **parskip**

Pkg parskip

parskip is ignored.

for HTML output: Discard all options for `lwarp-parskip`.

```
1 \LWR@ProvidesPackageDrop{parskip}[2001/04/09]
```

File 360 **lwarp-pbalance.sty**

§ 469 Package **pbalance**

Pkg pbalance

pbalance is ignored.

for HTML output:

```

1 \RequirePackage{balance}
2
3 \LWR@ProvidesPackageDrop{pbalance}[2020/12/16]

4 \newcommand\shrinkLastPage[1]{}
```

File 361 **lwarp-pbox.sty**

§ 470 Package **pbox**

Pkg pbox

(Emulates or patches code by SIMON LAW.)

pbox is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{pbox}[2011/12/07]

2 \NewDocumentCommand{\pbox}{0{t} 0{ } 0{t} m +m}{%
3 \global\booltrue\LWR@minipagefullwidth}%
4 \parbox[#1][#2][#3][#4]{#5}%
5 }
6
7 \newcommand{\settomewidth}[3][\columnwidth]{%
8 \settowidth{#2}{#3}%
9 }
10
11 \newcommand{\widthofpbox}[1]{%
12 \widthof{#1}%
13 }
```

File 362 **lwarp-pdfcol.sty**

§ 471 Package **pdfcol**

Pkg pdfcol

pdfcol is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{pdfcol}[2018/11/01]
2
3 \ltx@newif\ifpdfcolAvailable
4 \pdfcolAvailablefalse
5
6 \def\pdfcolErrorNoStacks{
7   \PackageInfo{lwarp-pdfcol}{Ignoring pdfcol for HTML output.}
8 }
```

```

9
10 \def\pdfcolInitStack#1{%
11
12 \long\def\pdfcolIfStackExists#1#2#3{#3}%
13
14 \def\pdfcolSwitchStack#1{%
15
16 \def\pdfcolSetCurrentColor{%
17
18 \def\pdfcolSetCurrent#1{%

```

File 363 **lwarp-pdfcolfoot.sty**

§ 472 Package **pdfcolfoot**

Pkg pdfcolfoot pdfcolfoot is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{pdfcolfoot}[2016/05/16]
2
3 \newcommand*\pdfcolfoot@switch{}
4
5 \newcommand*\pdfcolfoot@current{}

```

File 364 **lwarp-pdfcolmk.sty**

§ 473 Package **pdfcolmk**

Pkg pdfcolmk pdfcolmk is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{pdfcolmk}[2016/05/16]

```

File 365 **lwarp-pdfcolparallel.sty**

§ 474 Package **pdfcolparallel**

Pkg pdfcolparallel pdfcolparallel is ignored.

for HTML output:

```

1 \RequirePackage{keyval}%
2
3 \LWR@ProvidesPackageDropA{pdfcolparallel}{2016/05/16}

```

Pass options to parallel:

```

4 \DeclareOption*{%
5   \PassoptionsToPackage{\CurrentOption}{parallel}%
6 }

```

Process the options:

```

7 \LWR@ProvidesPackageDropB

```

Require parallel with the given options:

```
8 \RequirePackage{parallel}[2003/04/13]
```

Ignore the new key:

```
9 \define@key{parallel}{rulebetweencolor}{}
```

File 366 **lwarp-pdfcolparcolumns.sty**

§ 475 Package **pdfcolparcolumns**

Pkg pdfcolparcolumns pdfcolparcolumns is ignored.

for HTML output: 1 \LWR@ProvidesPackageDropA{pdfcolparcolumns}{2016/05/16}

Pass options to parcolumns:

```
2 \DeclareOption*{%
3   \PassoptionsToPackage{\CurrentOption}{parcolumns}%
4 }
```

Process the options:

```
5 \LWR@ProvidesPackageDropB
```

Require parcolumns with the given options:

```
6 \RequirePackage{parcolumns}[2004/11/25]
```

Ignore the new key:

```
7 \define@key{LWRparcols}{rulebetweencolor}{}
```

File 367 **lwarp-pdfcomment.sty**

§ 476 Package **pdfcomment**

Pkg pdfcomment pdfcomment is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pdfcomment}[2016/06/13]

```
2 \newenvironment{pdfsidelinecomment}[2][{}]{ }
3 \newcommand{\pdfcomment}[2][{}]{ }
4 \newcommand{\pdfmargincomment}[2][{}]{ }
5 \newcommand{\pdfmarkupcomment}[3][{}]{#2}
6 \newcommand{\pdfreetextcomment}[2][{}]{ }
7 \newcommand{\pdfsquarecomment}[2][{}]{ }
8 \newcommand{\pdfcirclecomment}[2][{}]{ }
9 \newcommand{\pdflinecomment}[2][{}]{ }
10 \newcommand{\pdftooltip}[3][{}]{#2}
11 \newcommand{\pdfcommentsetup}[2][{}]{ }
```

```

12 \newcommand{\listofpdfcomments}[1]{}
13 \newcommand{\setliststyle}[1]{}
14 \newcommand{\defineliststyle}[2]{}
15 \newcommand{\defineavatar}[2]{}
16 \newcommand{\definestyle}[2]{}

```

For MATHJAX:

```

17 \begin{warpMathJax}
18 \CustomizeMathJax{\newcommand{\pdfmarkupcomment}[3][]{#2}}
19 \CustomizeMathJax{\newcommand{\pdftooltip}[3][]{#2}}
20 \end{warpMathJax}

```

File 368 **lwarp-pdfcrypt.sty**

§ 477 Package **pdfcrypt**

Pkg pdfcrypt pdfcrypt is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{pdfcrypt}[2016/05/16]

2 \newcommand*{\pdfcryptsetup}[1]{}

```

File 369 **lwarp-pdflandscape.sty**

§ 478 Package **pdflandscape**

Pkg pdflandscape pdflandscape is ignored.

for HTML output: Discard all options for lwarp-pdflandscape:

```

1 \LWR@ProvidesPackageDrop{pdflandscape}[2019/12/05]

2 \let\landscape\relax
3 \let\endlandscape\relax
4
5 \newenvironment*{landscape}{}{}

```

File 370 **lwarp-pdfmarginpar.sty**

§ 479 Package **pdfmarginpar**

Pkg pdfmarginpar pdfmarginpar is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{pdfmarginpar}[2011/08/05]

2 \newcommand{\pdfmarginpar}[2]{}
3 \newcommand{\pdfmarginparset}[1]{}

```

File 371 **lwarp-pdfpages.sty**

§ 480 Package **pdfpages**

(Emulates or patches code by ANDREAS MATTHIAS.)

Pkg pdfpages

pdfpages is patched for use by lwarp.

Option link and linkname work:

```
\hyperlink{<filename>.pdf.<pagenumber>}{some text}
\hyperlink{<linkname>.<pagenumber>}{some text}
```

Options which make no sense in HTML are disabled.

for HTML output: 1 \LWR@ProvidesPackagePass{pdfpages}[2017-10-31]

Disable option which have no meaning for HTML output:

```
2 \define@key{pdfpages}{fitpaper}[false]{}
3 \define@key{pdfpages}{landscape}[false]{}
4 \define@key{pdfpages}{openright}[false]{}
5 \define@key{pdfpages}{signature}{}
6 \define@key{pdfpages}{signature*}{}
7 \define@key{pdfpages}{booklet}[false]{}
8 \define@key{pdfpages}{rotateoversize}[false]{}
9 \define@key{pdfpages}{doublepages}[false]{}
10 \define@key{pdfpages}{doublepagetwist}[false]{}
11 \define@key{pdfpages}{doublepagetwistodd}[false]{}
12 \define@key{pdfpages}{doublepagetwist*}[false]{}
13 \define@key{pdfpages}{doublepagetwistodd*}[false]{}
14 \define@key{pdfpages}{duplicatepages}[2]{}
15 \define@key{pdfpages}{thread}[false]{}
16 \define@key{pdfpages}{threadname}{}
17 \define@key{pdfpages}{linkfit}{}
18 \define@key{pdfpages}{linktodoc}[false]{}
19 \define@key{pdfpages}{linktodocfit}{}
20 \define@key{pdfpages}{linkfilename}{}
21 \define@key{pdfpages}{survey}[false]{}
22 \define@key{pdfpages}{survey-nolink}[false]{}
23 \define@key{pdfpages}{newwindow}[false]{}

```

Use print mode while measuring the page numbers:

```
24 \xpretocmd{\AM@getpagecount}{\LWR@restoreorigformatting}{}{}
```

Emulate a bit of eso-pic:

```
25 \newif\ifESO@texcoord
26
27 \newcommand{\ESO@HookIIBG}{}
28
```

```

29 \renewcommand{\AM@AddToShipoutPicture}{\g@addto@macro\ESO@HookIIBG}
30
31 \renewcommand{\ClearShipoutPicture}{}

```

\LWR@esopic@newpage

At each \newpage.

```

32 \newcommand*{\LWR@esopic@newpage}{%

```

Is there something to draw?

```

33 \ifdefvoid{\ESO@HookIIBG}%
34 {}%
35 {%

```

If the link option was specified, add a hyper target:

```

36   \ifAM@link%
37     \hypertarget{\AM@linkname.\AM@page}{}%
38   \fi%

```

Draw inside a picture environment of the size of a virtual page:

```

39   \begingroup%
40   \setlength{\unitlength}{1in}%
41   \begin{picture}(8,10.5)%
42   \ESO@HookIIBG%
43   \end{picture}%
44   \endgroup%
45   \global\let\ESO@HookIIBG\@empty%
46 }
47 }

```

\AM@output

Patched to use \LWR@esopic@newpage.

```

48 \xpatchcmd{\AM@output}
49   {\newpage}
50   {\LWR@esopic@newpage}
51   {}
52   {\LWR@patcherror{pdfpages}{AM@output-1}}
53
54 \xpatchcmd{\AM@output}
55   {\newpage}
56   {\LWR@esopic@newpage}
57   {}
58   {\LWR@patcherror{pdfpages}{AM@output-2}}
59
60 \xpatchcmd{\AM@output}
61   {\newpage}
62   {\LWR@esopic@newpage}
63   {}
64   {\LWR@patcherror{pdfpages}{AM@output-3}}

```

\includepdf

Patched to set the user's paper size.

```

65 \xpretocmd{\includepdf}{%
66   \begingroup%
67   \setlength{\paperwidth}{\LWR@userspaperwidth}%
68   \setlength{\paperheight}{\LWR@userspaperheight}%
69 }{}{}
70
71 \xapptocmd{\includepdf}{%

```

```
72 \endgroup%
73 }{}{}
```

`\includepdfmerge`

Patched to set the user's paper size.

```
74 \xpretocmd{\includepdfmerge}{%
75 \begingroup%
76 \setlength{\paperwidth}{\LWR@userspaperwidth}%
77 \setlength{\paperheight}{\LWR@userspaperheight}%
78 }{}{}}
79
80 \xapptocmd{\includepdfmerge}{%
81 \endgroup%
82 }{}{}}
```

`\AM@hyper@begin@i`Hyper links are created by `\LWR@esopic@newpage`, so don't create them here:

```
83 \renewcommand{\AM@hyper@begin@i}{}
```

File 372 **lwarp-pdfprivacy.sty**

§ 481 Package **pdfprivacy**

Pkg pdfprivacy

pdfprivacy is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pdfprivacy}[2017/12/03]

File 373 **lwarp-pdfreender.sty**

§ 482 Package **pdfreender**

Pkg pdfreender

pdfreender is allowed during HTML, but it has no effect on HTML text output. pdfreender is enabled for use with `xfakebold`, and it is enabled during HTML so that it may be in use when an SVG math image is started. I.e. `xfakebold`'s `\setBold` may be used outside of a math expression and still be detected when the math begins.

The `lwarp-pdfreender` package is present because it used to disable pdfreender, so this newer version is to overwrite older versions.

for HTML output: 1 \LWR@ProvidesPackagePass{pdfreender}[2019/12/29]

File 374 **lwarp-pdfsync.sty**

§ 483 Package **pdfsync**

Pkg pdfsync

pdfsync is ignored.

for HTML output:

Discard all options for `lwarp-pdftosync`:

```
1 \LWR@ProvidesPackageDrop{pdftosync}[2008/01/26]

2 \newcommand*\pdftosync{}
3 \newcommand*\pdftosyncstart{}
4 \newcommand*\pdftosyncstop{}
```

File 375 **lwarp-pdftricks.sty**

§ 484 Package **pdftricks**

(Emulates or patches code by C. V. RADHAKRISHNAN, C. V. RAJAGOPAL, ANTOINE CHAMBERT-LOIR.)

Pkg pdftricks

pdftricks is patched for use by lwarp.

 **convert image files** The pdftricks image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ `lwarpmk pdftosvg <jobname>-fig*.pdf`

for HTML output: 1 \LWR@ProvidesPackagePass{pdftricks}[2003/08/10]

Reuse the print-mode images:

```
2 \def\PDFTfigname{\BaseJobname-fig\thepsfig}
```

If the `.pdf` images have not yet been converted to `.svg` then an error about a missing file will occur. Warn the user to convert the images.

```
3 \PackageWarning{lwarp-pdftricks}{%
4 When the pdftricks images change,
5 remember to convert PDF images to SVG using 'lwarpmk pdftosvg *-fig.pdf',
6 }
7
8 \AfterEndDocument{\typeout{***}}
9 \AfterEndDocument{\typeout{*** Note: If pdftricks images are not found, new, or updated,}}
10 \AfterEndDocument{\typeout{*** \space use 'lwarpmk pdftosvg \BaseJobname-fig*.pdf'}}
11 \AfterEndDocument{\typeout{***}}
```

File 376 **lwarp-pdfx.sty**

§ 485 Package **pdfx**

Pkg pdfx

pdfx is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pdfx}[2017/05/18]

File 377 **lwarp-perpage.sty**

§ 486 Package **perpage**

(Emulates or patches code by DAVID KASTRUP.)

Pkg perpage

perpage is mostly ignored, but support is added for footnote counters.

There is no page number in HTML, so most counters are not reset. If the document redefines `\the<countname>` to include `\theperpage`, it is necessary to place that redefinition inside a `warpprint` environment to avoid modifying the HTML definitions.

`\AddAbsoluteCounter` must not be inside `warpprint`, as the counter must be added for HTML also, although it is not incremented.

[footnote numbering](#) To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For `bigfoot`, `manyfoot`, or `perpage`:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{perpage}[2014/10/25]
2 \newcommand\AddAbsoluteCounter[1]
3 {
4   \@ifundefined{c@abs#1}{%
5     \expandafter\newcount\csname c@abs#1\endcsname
6     \global\value{abs#1}\@ne
7     \global\expandafter\let\csname cl@abs#1\endcsname\@empty
8     \expandafter\def\csname theabs#1\endcsname{%
9       \noexpand\number \csname c@abs#1\endcsname
10    }%
11   \global\@namedef{c@pabs@#1}{\pp@cl@begin
12     \stepcounter{abs#1}%
13     \pp@cl@end}%
14   \@addtoreset{pabs@#1}{#1}
15 }
16 {}
17 }
18
19 \AddAbsoluteCounter{page}
20 \def\theabspage{1}
21
22 \newcommand*\MakePerPage[2][1]{%
23   \ifltxcounter{#2Reset}{%
24     \setcounter{#2Reset}{#1}%
```

```

25   }{
26
27 }%
28 }
29
30 \newcommand*\MakeSorted[1]{}
31
32 \newcommand*\MakeSortedPerPage[2][1]{%
33   \ifltxcounter{#2Reset}{%
34     \setcounter{#2Reset}{#1}%
35   }{
36 }%
37 }
38
39 \newcommand*\theperpage{1}

```

File 378 **lwarp-pfnote.sty**

§ 487 Package **pfnote**

Pkg pfnote

pfnote is ignored.

pfnote While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

 **pfnote numbers**

for HTML output: 1 \LWR@ProvidesPackageDrop{pfnote}[1999/07/14]

File 379 **lwarp-phfqit.sty**

§ 488 Package **phfqit**

(Emulates or patches code by PHILIPPE FAIST.)

Pkg phfqit

phfqit is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{phfqit}[2017/08/16]

```

2 \LetLtxMacro\LWR@origbitstring\bitstring
3
4 \renewcommand\bitstring[1]{%
5 \InlineClass[%
6   text-decoration: overline underline ;
7 ]{bitstring}{#1}%
8 % \phfqit@bitstring{#1}%
9 }
10
11 \appto\LWR@restoreorigformatting{%
12 \LetLtxMacro\bitstring\LWR@origbitstring%
13 }

```

File 380 **lwarp-physics.sty**

§ 489 Package **physics**

(Emulates or patches code by SERGIO C. DE LA BARRERA.)

Pkg physics

physics works as-is for HTML with SVG math.

For MATHJAX, the MATHJAX v3 physics extension is used.

for HTML output:

```

1 \LWR@ProvidesPackagePass{physics}% No date is provided by the package.

2 \begin{warpMathJax}
3 \PackageNoteNoLine{lwarp, physics}{The MathJax v3 extension will be used}
4 \CustomizeMathJax{\require{physics}}
5 \end{warpMathJax}

```

File 381 **lwarp-physicsunits.sty**

§ 490 Package **physicsunits**

(Emulates or patches code by BRIAN W. MULLIGAN.)

Pkg physicsunits

physicsunits is supported as-is for SVG math, and is emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{physicsunits}[2020/03/26]

2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{physicsunits}
4
5 \CustomizeMathJax{\newcommand{\micro}{\mu}}
6 \CustomizeMathJax{\newcommand{\V}[1][ ]{\, \mathrm{#1V}}}
7 \CustomizeMathJax{\newcommand{\Volt}[1][ ]{\, \mathrm{#1V}}}
8 \CustomizeMathJax{\newcommand{\Coulomb}[1][ ]{\, \mathrm{#1C}}}
9 \CustomizeMathJax{\newcommand{\esu}{\, \mathrm{esu}}}
10 \CustomizeMathJax{\newcommand{\Ohm}[1][ ]{\, \mathrm{#1\Omega}}}
11 \CustomizeMathJax{\newcommand{\Amp}[1][ ]{\, \mathrm{#1A}}}
12 \CustomizeMathJax{\newcommand{\Farad}[1][ ]{\, \mathrm{#1F}}}
13 \CustomizeMathJax{\newcommand{\Tesla}[1][ ]{\, \mathrm{#1T}}}
14 \CustomizeMathJax{\newcommand{\Gauss}[1][ ]{\, \mathrm{#1G}}}
15 \CustomizeMathJax{\newcommand{\Henry}[1][ ]{\, \mathrm{#1H}}}
16 \CustomizeMathJax{\newcommand{\eV}[1][ ]{\, \mathrm{#1eV}}}
17 \CustomizeMathJax{\newcommand{\keV}{\, \mathrm{keV}}}
18 \CustomizeMathJax{\newcommand{\MeV}{\, \mathrm{MeV}}}
19 \CustomizeMathJax{\newcommand{\J}[1][ ]{\, \mathrm{#1J}}}
20 \CustomizeMathJax{\newcommand{\Joule}[1][ ]{\, \mathrm{#1J}}}
21 \CustomizeMathJax{\newcommand{\erg}{\, \mathrm{erg}}}
22 \CustomizeMathJax{\newcommand{\kcal}{\, \mathrm{kcal}}}
23 \CustomizeMathJax{\newcommand{\Cal}{\, \mathrm{Cal}}}
24 \CustomizeMathJax{\newcommand{\calorie}[1][ ]{\, \mathrm{#1cal}}}
25 \CustomizeMathJax{\newcommand{\BTU}{\, \mathrm{BTU}}}
26 \CustomizeMathJax{\newcommand{\tnt}{\, \mathrm{ton\, of\, TNT}}}
27 \CustomizeMathJax{\newcommand{\Watt}[1][ ]{\, \mathrm{#1W}}}

```

```

28 \CustomizeMathJax{\newcommand{\hpi}{\, \mathrm{hp(I)}}}
29 \CustomizeMathJax{\newcommand{\hpm}{\, \mathrm{hp(M)}}}
30 \CustomizeMathJax{\newcommand{\hp}{\, \mathrm{hp}}}
31 \CustomizeMathJax{\newcommand{\meter}[1][ ]{\, \mathrm{#1m}}}
32 \CustomizeMathJax{\newcommand{\m}[1][ ]{\, \mathrm{#1m}}}
33 \CustomizeMathJax{\newcommand{\km}{\, \mathrm{km}}}
34 \CustomizeMathJax{\newcommand{\au}{\, \mathrm{au}}}
35 \CustomizeMathJax{\newcommand{\pc}[1][ ]{\, \mathrm{#1pc}}}
36 \CustomizeMathJax{\newcommand{\ly}[1][ ]{\, \mathrm{#1ly}}}
37 \CustomizeMathJax{\newcommand{\cm}{\, \mathrm{cm}}}
38 \CustomizeMathJax{\newcommand{\nm}{\, \mathrm{nm}}}
39 \CustomizeMathJax{\newcommand{\ft}{\, \mathrm{ft}}}
40 \CustomizeMathJax{\newcommand{\inch}{\, \mathrm{in}}}
41 \CustomizeMathJax{\newcommand{\mi}{\, \mathrm{mi}}}
42 \CustomizeMathJax{\newcommand{\s}[1][ ]{\, \mathrm{#1s}}}
43 \CustomizeMathJax{\newcommand{\Sec}[1][ ]{\, \mathrm{#1s}}}
44 \CustomizeMathJax{\newcommand{\Min}{\, \mathrm{min}}}
45 \CustomizeMathJax{\newcommand{\h}{\, \mathrm{h}}}
46 \CustomizeMathJax{\newcommand{\y}[1][ ]{\, \mathrm{#1y}}}
47 \CustomizeMathJax{\newcommand{\Day}{\, \mathrm{d}}}
48
49 \CustomizeMathJax{\newcommand{\gm}[1][ ]{\, \mathrm{#1g}}}
50 \CustomizeMathJax{\newcommand{\kg}{\, \mathrm{kg}}}
51 \CustomizeMathJax{\newcommand{\lb}{\, \mathrm{lb}}}
52 \CustomizeMathJax{\newcommand{\amu}{\, \mathrm{amu}}}
53 \CustomizeMathJax{\newcommand{\N}[1][ ]{\, \mathrm{#1N}}}
54 \CustomizeMathJax{\newcommand{\Newton}[1][ ]{\, \mathrm{#1N}}}
55 \CustomizeMathJax{\newcommand{\dyne}[1][ ]{\, \mathrm{#1dyn}}}
56 \CustomizeMathJax{\newcommand{\lbf}{\, \mathrm{lbf}}}
57 \CustomizeMathJax{\newcommand{\kmphs}{\, \mathrm{km}\, \mathrm{s}^{-1}}}
58 \CustomizeMathJax{\newcommand{\kmph}{\, \mathrm{km}\, \mathrm{h}^{-1}}}
59 \CustomizeMathJax{\newcommand{\mps}[1][ ]{\, \mathrm{#1m}\, \mathrm{s}^{-1}}}
60 \CustomizeMathJax{\newcommand{\miph}{\, \mathrm{mi}\, \mathrm{h}^{-1}}}
61 \CustomizeMathJax{\newcommand{\kts}{\, \mathrm{kts}}}
62
63 \CustomizeMathJax{\newcommand{\mpss}[1][ ]{\, \mathrm{#1m}\, \mathrm{s}^{-2}}}
64 \CustomizeMathJax{\newcommand{\gacc}{\, \mathrm{g}}}
65 \CustomizeMathJax{\newcommand{\ftpss}{\, \mathrm{ft}\, \mathrm{s}^{-2}}}
66 \CustomizeMathJax{\newcommand{\K}[1][ ]{\, \mathrm{#1K}}}
67 \CustomizeMathJax{\newcommand{\Kelvin}[1][ ]{\, \mathrm{#1K}}}
68 \CustomizeMathJax{\newcommand{\Celsius}{\, ^\circ\mathrm{C}}}
69 \CustomizeMathJax{\newcommand{\Rankine}{\, ^\circ\mathrm{R}}}
70 \CustomizeMathJax{\newcommand{\Fahrenheit}{\, ^\circ\mathrm{F}}}
71
72 \CustomizeMathJax{\newcommand{\rpm}{\, \mathrm{rev}\, \mathrm{Min}^{-1}}}
73
74 \CustomizeMathJax{\newcommand{\Hz}[1][ ]{\, \mathrm{#1Hz}}}
75 \CustomizeMathJax{\newcommand{\barP}[1][ ]{\, \mathrm{#1bar}}}
76 \CustomizeMathJax{\newcommand{\atm}{\, \mathrm{atm}}}
77 \CustomizeMathJax{\newcommand{\Pa}[1][ ]{\, \mathrm{#1Pa}}}
78 \CustomizeMathJax{\newcommand{\mmHg}{\, \mathrm{mmHg}}}
79 \CustomizeMathJax{\newcommand{\inHg}{\, \mathrm{inHg}}}
80 \CustomizeMathJax{\newcommand{\lpsi}{\, \mathrm{psi}}}
81 \CustomizeMathJax{\newcommand{\lpsf}{\, \mathrm{psf}}}
82 \CustomizeMathJax{\newcommand{\Ba}[1][ ]{\, \mathrm{#1Ba}}}
83 \CustomizeMathJax{\newcommand{\Torr}[1][ ]{\, \mathrm{#1Torr}}}
84 \CustomizeMathJax{\newcommand{\mol}{\, \mathrm{mol}}}
85 \end{warpMathJax}

```

File 382 **lwarp-picinpar.sty**

§ 491 Package **picinpar**

(Emulates or patches code by FRIEDHELM SOWA.)

Pkg picinpar

picinpar is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{picinpar}% No date is assigned.

The window is floated by a BlockClass style.

```

2 \long\def\LWR@HTML@window[#1,#2,#3,#4] {%
3   \if #2r%
4     \begin{BlockClass}[float:right](note){marginblock}%
5   \else%
6     \begin{BlockClass}[float:left](note){marginblock}%
7   \fi%
8   #3\par%
9   #4%
10  \end{BlockClass}%
11 }
12
13 \def\endLWR@HTML@window{}
14
15 \LWR@formattedenv{window}

```

The framepic and wframepic are placed inside a BlockClass of class framebox.

```

16 \def\LWR@HTML@framepic#1{%
17   \begin{BlockClass}{framebox}
18   \expandafter\box\csname #1box\endcsname%
19   \end{BlockClass}
20 }
21 \LWR@formatted{framepic}

22 \def\LWR@HTML@wframepic#1{%
23   \begin{BlockClass}{framebox}
24   \expandafter\box\csname #1box\endcsname%
25   \end{BlockClass}
26 }
27 \LWR@formatted{wframepic}

```

The caption is placed inside a BlockClass of class figurecaption.

```

28 \long\def\LWR@HTML@makewincaption#1#2{%
29 \begin{BlockClass}{figurecaption}
30 #1: #2
31 \end{BlockClass}
32 }
33 \LWR@formatted{@makewincaption}

```

With HTML output, figwindow and tabwindow must not pre-decrement their counters.

```

34 \long\def\LWR@HTML@figwindow[#1,#2,#3,#4] {%
35 %   \advance\c@figure -1
36   \window[#1,#2,{#3},{\def\@capttype{figure}%
37     \wincaption#4\par}] }
38
39 \def\endLWR@HTML@figwindow{\endwindow}
40
41 \LWR@formattedenv{figwindow}

```

For `tabwindow`, to change the catcode of `&`, `\StartDefiningTabulars` is used before absorbing the arguments, and `\EndDefiningTabulars` is used at the end of the environment.

```

42 \long\def\LWR@HTML@subtabwindow[#1,#2,#3,#4] {%
43 %   \advance\c@table -1
44   \window[#1,#2,{#3},{\def\@capttype{table}%
45     \wincaption#4\par}] }
46
47 \newcommand*\LWR@HTML@tabwindow{%
48   \StartDefiningTabulars%
49   \LWR@HTML@subtabwindow%
50 }
51
52 \def\endLWR@HTML@tabwindow{%
53   \endwindow%
54   \StopDefiningTabulars%
55 }
56
57 \LWR@formattedenv{tabwindow}

```

File 383 **lwarp-pifont.sty**

§ 492 Package **pifont**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg pifont

pifont is patched for use by **lwarp**.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```

1 \LWR@ProvidesPackagePass{pifont}[2005/04/12]
2 \renewcommand{\Pisymbol}[2]{%
3   \begin{lateximage}*\Pisymbol[pisymbol#1#2]%
4   {\Pifont{#1}\char#2}%
5   \end{lateximage}%
6 }
7
8 \newcommand{\LWR@HTML@Pifill}[2]{
9   \Pisymbol{#1}{#2} \Pisymbol{#1}{#2} \Pisymbol{#1}{#2}
10 }
11 \LWR@formatted{Pifill}
12
13 \newcommand{\LWR@HTML@Piline}[2]{%
14   \par\noindent\hspace*{0.5in}
15   \Pifill{#1}{#2} \Pifill{#1}{#2} \Pifill{#1}{#2}
16 }

```

```
17 \LWR@formatted{Piline}
```

File 384 **lwarp-pinlabel.sty**

§ 493 Package **pinlabel**

(Emulates or patches code by COLIN ROURKE.)

Pkg pinlabel

pinlabel is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{pinlabel}% no date given

```
2 \xpretocmd{\psfig}
3   {\begin{lateximage}[-pinlabel--\PackageDiagramAltText]}
4   {}
5   {\LWR@patcherror{pinlabel}{psfigA}}
6
7 \xapptocmd{\psfig}
8   {\end{lateximage}}
9   {}
10  {\LWR@patcherror{pinlabel}{psfigB}}
```

File 385 **lwarp-placeins.sty**

§ 494 Package **placeins**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg placeins

placeins is ignored.

Discard all options for lwarp-placeins:

for HTML output: 1 \LWR@ProvidesPackageDrop{placeins}[2005/04/18]

```
2 \newcommand*\FloatBarrier{}
```

File 386 **lwarp-plarydshln.sty**

§ 495 Package **plarydshln**

Pkg plarydshln

plarydshln is emulated by lwarp-arydshln.

for HTML output: 1 \LWR@ProvidesPackageDrop{plarydshln}[2018/10/20]

```
2 \LWR@origRequirePackage{lwarp-arydshln}
```

File 387 **lwarp-plext.sty**

§ 496 Package **plext**

Pkg plext

plext is preloaded by jrticle and related classes.

for HTML output:

```

1 \LWR@loadbefore{plext}
2
3 \LWR@ProvidesPackagePass{plext}[2017/07/21]

4 \let\tate\relax
5
6 \DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}
7
8 % \layoutfloat(width,height)[pos]#4
9 \DeclareDocumentCommand{\layoutfloat}{d() o m}{}
10
11 % \DeclareLayoutCaption{type} <dir>(width)[pos1pos2]
12 \DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}
13
14 \LetLtxMacro\pccaption\caption
15
16 % \layoutcaption<dir>(width)[pos]
17 \DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}
18
19 \let\captiondir\relax

```

Add the optional <t/y> direction:

```

20 \RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
21   {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
22   {\endLWR@HTML@sub@minipage}
23
24 \RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
25 {
26 \LWR@traceinfo{parbox of width #4}%
27 \begin{minipage}[#2][#3][#4]{#5}%
28 #6
29 \end{minipage}%
30 }
31
32 % \pbox <t/y> [width] [l/r] {contents}
33 \RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
34 \global\booltrue{LWR@minipagefullwidth}%
35 \parbox{#2}{#4}%
36 }

```

picture, as modified by pext, is encapsulated by the lwarp core.

File 388 **lwarp-plextarydshln.sty**

§ 497 Package **plextarydshln**

Pkg plextarydshln plextarydshln is emulated by lwarp-arydshln.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{plextarydshln}[2018/10/20]

2 \LWR@origRequirePackage{lwarp-arydshln}

```

File 389 **lwarp-plextcolortbl.sty**

§ 498 Package **plextcolortbl**

Pkg plextcolortbl plextcolortbl is emulated by lwarp-colortbl.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{plextcolortbl}[2018/09/19]
2 \LWR@origRequirePackage{lwarp-colortbl}
```

File 390 **lwarp-plimsoll.sty**

§ 499 Package **plimsoll**

(Emulates or patches code by PALLE JØRGENSEN.)

Pkg plimsoll plimsoll is used as-is for SVG math, and emulated for MATHJAX.

The circ option is honored. For MATHJAX, \plimsollsans is the same as \plimsollroman.

for HTML output:

```
1 \LWR@ProvidesPackagePass{plimsoll}[2020/10/09]
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\plimsollroman}{\unicode{x029B5}}}
4
5 \CustomizeMathJax{\let\plimsoll\plimsollroman}
6 \CustomizeMathJax{\let\plimsollsans\plimsoll}
7
8 \ifdefstring{\stst}{^{\circ}}
9   {\CustomizeMathJax{\newcommand{\stst}{^{\circ}}}}
10  {\CustomizeMathJax{\newcommand{\stst}{^{\plimsoll}}}}
11 \end{warpMathJax}
```

File 391 **lwarp-prelim2e.sty**

§ 500 Package **prelim2e**

(Emulates or patches code by MARTIN SCHRÖDER.)

Pkg prelim2e prelim2e is ignored.

for HTML output: Discard all options for lwarp-prelim2e:

```
1 \LWR@ProvidesPackageDrop{prelim2e}[2009/05/29]
2 \newcommand{\PrelimText}{}
3 \newcommand{\PrelimTextStyle}{}
4 \newcommand{\PrelimWords}{}

```

File 392 **lwarp-prettyref.sty**§ 501 Package **prettyref***(Emulates or patches code by KEVIN S. RULAND.)*

Pkg prettyref prettyref is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{prettyref}[1998/07/09]2 \newrefformat{fig}{Figure \ref{#1}}
3 \newrefformat{tab}{Table \ref{#1}}File 393 **lwarp-preview.sty**§ 502 Package **preview**

Pkg preview preview is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{preview}[2017/04/24]2 \newenvironment{preview}{}{}
3 \newenvironment{nopreview}{}{}
4 \NewDocumentCommand{\PreviewMacro}{s o o +m}{}
5 \NewDocumentCommand{\PreviewEnvironment}{s o o +m}{}
6 \newcommand{\PreviewSnarfEnvironment}[2][[]]{}
7 \NewDocumentCommand{\PreviewOpen}{s o}{}
8 \NewDocumentCommand{\PreviewClose}{s o}{}
9 \let\ifPreview\iffalse% \fi for syntax highlightingFile 394 **lwarp-psfrag.sty**§ 503 Package **psfrag***(Emulates or patches code by MICHAEL C. GRANT, DAVID CARLISLE.)*

Pkg psfrag psfrag is patched for use by lwarp.

 **use psfrags** The psfrags environment is modified to use `lateximage` to encapsulate the image. Always use a psfrags environment to contain any local `\psfrag` macros and the associated `\includegraphics` or `\epsfig` calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp. **Tip:** Use a mono-spaced font for the tags in the EPS file.**for HTML output:** 1 \LWR@ProvidesPackagePass{psfrag}[1998/04/11]A `lateximage` captures the modified image from the document.

```

2 \BeforeBeginEnvironment{psfrags}{%
3   \begin{lateximage}[-psfrags~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{psfrags}{\end{lateximage}}
```

File 395 **lwarp-psfragx.sty**

§ 504 Package **psfragx**

(Emulates or patches code by PASCAL KOCKAERT.)

Pkg psfragx

psfragx is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{psfragx}[2012/05/02]

A lateximage captures the modified image from the document.

```

2 \def\pfx@includegraphicx#1#2{%
3   \begin{lateximage}[-psfragx~\PackageDiagramAltText]%
4   \mbox{\pfx@overpix{#1}{#2}\endpfx@overpix}%
5   \end{lateximage}%
6 }
7
8 \def\@@@overpix[#1]<#2>[#3]#4{%
9   \begin{lateximage}[-psfragx~\PackageDiagramAltText]%
10  \pfx@overpix{#1,ovpfgd={#2},ovpbgd={#3}}{#4}%
11 }
12
13 \def\endoverpix{%
14   \endpfx@overpix%
15   \end{lateximage}%
16 }
```

File 396 **lwarp-pst-eps.sty**

§ 505 Package **pst-eps**

(Emulates or patches code by HERBERT VOSS.)

Pkg pst-eps

pst-eps is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{pst-eps}[2005/05/20]

```

2 \renewenvironment{TeXtoEPS}{}{}
3 \renewcommand{\PSTtoEPS}[3][{}]
```

File 397 **lwarp-pstool.sty**

§ 506 Package **pstool**

(Emulates or patches code by ZEBB PRIME, WILL ROBERTSON.)

Pkg pstool

pstool is patched for use by lwarp.

`\graphicspath` is ignored, and the file directory must be stated.

 **path and filename** The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk images**

.

for HTML output: 1 \LWR@ProvidesPackagePass{pstool}[2018/01/20]

Each image is placed inside a `lateximage` to capture the results of `psfrag`.

```

2 \renewcommand\pstool@alwaysprocess[3][]{%
3   \begin{lateximage}[-pstool-~\PackageDiagramAltText]%
4     \includegraphics{#2.pdf}%
5   \end{lateximage}%
6 }
7 \LetLtxMacro\pstool@neverprocess\pstool@alwaysprocess
8 \LetLtxMacro\pstool@maybeprocess\pstool@alwaysprocess
9
10 \renewcommand\pstool@psfragfig[4]{%
11   \begin{lateximage}[-pstool-~\PackageDiagramAltText]%
12     \includegraphics{#2.pdf}%
13   \end{lateximage}%
14 }
```

File 398 **lwarp-pstricks.sty**§ 507 Package **pstricks***(Emulates or patches code by TIMOTHY VAN ZANDT.)*

Pkg pstricks

pstricks is patched for use by lwarp.

 **use pspicture** All pstricks content should be contained inside a `pspicture` environment.

for HTML output: 1 \LWR@ProvidesPackagePass{pstricks}[2018/01/06]

```

2 \BeforeBeginEnvironment{pspicture}{%
3   \begin{lateximage}[pspicture]%
4 }
5 \AfterEndEnvironment{pspicture}{\end{lateximage}}
6
7 \BeforeBeginEnvironment{pspicture*}{%
8   \begin{lateximage}[pspicture]%
9 }
10 \AfterEndEnvironment{pspicture*}{\end{lateximage}}
```

File 399 **lwarp-pxatbegshi.sty**

§ 508 Package **pxatbegshi**

Pkg pxatbegshi pxatbegshi is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pxatbegshi}[2017/11/04]

2 \LWR@origRequirePackage{lwarp-atbegshi}

File 400 **lwarp-pxeveryshi.sty**

§ 509 Package **pxeveryshi**

Pkg pxeveryshi pxeveryshi is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pxeveryshi}[2012/05/19]

2 \LWR@origRequirePackage{lwarp-everyshi}

File 401 **lwarp-pxfonts.sty**

§ 510 Package **pxfonts**

(Emulates or patches code by YOUNG RYU.)

Pkg pxfonts pxfonts is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{pxfonts}[2008/01/22]

For MATHJAX:

```
2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{pxfonts}
6
7 \LWR@mathjax@addgreek@L@up{}{}up}
8 \end{warpMathJax}
```

File 402 **lwarp-pxftnright.sty**

§ 511 Package **pxftnright**

Pkg pxftnright pxftnright is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pxftnright}[2017/02/28]

```
2 \LWR@origRequirePackage{lwarp-ftnright}
```

File 403 **lwarp-pxjahyper.sty**

§ 512 Package **pxjahyper**

Pkg pxjahyper

pxjahyper is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pxjahyper}[2018/07/15]

File 404 **lwarp-quotchap.sty**

§ 513 Package **quotchap**

(Emulates or patches code by KARSTEN TINNEFELD, JAN KLEVER.)

Pkg quotchap

quotchap is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{quotchap}[2019/07/09]

```
2 \newcommand{\@quotchap}{}
3 \newlength{\LWR@quotchapwidth}
4
5 \let\@printcites\relax
6
7 \newcommand*{\@iprintcites}{%
```

Place the quotes inside a <div> of class quotchap, of the maximum selected width:

```
8 \begin{BlockClass}[max-width: \LWR@printlength{\LWR@quotchapwidth}]{quotchap}
9 %\begin{minipage}{\LWR@quotchapwidth}
10 \@quotchap
11 %\end{minipage}
12 \end{BlockClass}
```

Deactivate the quote printing:

```
13 \global\let\@printcites\relax
14 }
15
16 \NewEnviron{savequote}[1][\linewidth]{%
```

Remember the width, adjusted for HTML, and make the length assignment global, per:

<https://tex.stackexchange.com/questions/300823/>

[why-is-setlength-ineffective-inside-a-tabular-environment](https://tex.stackexchange.com/questions/300823/why-is-setlength-ineffective-inside-a-tabular-environment)

```
17 \setlength{\LWR@quotchapwidth}{#1*2}%
18 \global\LWR@quotchapwidth=\LWR@quotchapwidth%
```

Remember the body, and activate the quote printing:

```

19 \global\let\@quotchap\BODY
20 \global\let\@printcites\@iprintcites%
21 }

```

The quotation author is placed inside a <div> of class qauthor:

```

22 \newcommand{\qauthor}[1]{%
23   \LWR@stoppars%
24   \begin{BlockClass}{qauthor}%
25     {#1}%
26   \end{BlockClass}%
27   \LWR@startpars%
28 }

```

Fonts are ignored. Use css.

```

29 \newcommand{\qsetcnfont}[1]{}
30 \providecommand*\quotefont{}
31 \providecommand*\qauthorfont{}

```

File 405 **lwarp-quoting.sty**

§ 514 Package **quoting**

(Emulates or patches code by THOMAS TITZ.)

Pkg quoting

quoting is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{quoting}[2014/01/28]

2 \xpatchcmd{\quoting}{\quo@begintext}
3   {\begin{LWR@blocktextcurrentfont}\quo@begintext}
4   {}
5   {\LWR@patcherror{quoting}{quoting}}
6
7 \xpatchcmd{\endquoting}{\quo@endtext}
8   {\quo@endtext\end{LWR@blocktextcurrentfont}\LWR@stoppars}
9   {}
10  {\LWR@patcherror{quoting}{endquoting}}

```

File 406 **lwarp-ragged2e.sty**

§ 515 Package **ragged2e**

(Emulates or patches code by MARTIN SCHRÖDER.)

Pkg ragged2e

ragged2e is emulated.

Discard all options for lwarp-ragged2e:

for HTML output:

```

1 \LWR@ProvidesPackageDrop{ragged2e}[2009/05/21]

2 \LetLtxMacro\Centering\centering
3 \LetLtxMacro\RaggedLeft\raggedleft

```

```

4 \LetLtxMacro\RaggedRight\raggedright
5 \newcommand*\justifying{}
6 \newlength{\CenteringLeftskip}
7 \newlength{\RaggedLeftLeftskip}
8 \newlength{\RaggedRightLeftskip}
9 \newlength{\CenteringRightskip}
10 \newlength{\RaggedLeftRightskip}
11 \newlength{\RaggedRightRightskip}
12 \newlength{\CenteringParfillskip}
13 \newlength{\RaggedLeftParfillskip}
14 \newlength{\RaggedRightParfillskip}
15 \newlength{\JustifyingParfillskip}
16 \newlength{\CenteringParindent}
17 \newlength{\RaggedLeftParindent}
18 \newlength{\RaggedRightParindent}
19 \newlength{\JustifyingParindent}
20 \newenvironment*{Center}{\center}{\endcenter}
21 \newenvironment*{FlushLeft}{\flushleft}{\endflushleft}
22 \newenvironment*{FlushRight}{\flushright}{\endflushright}
23 \newenvironment*{justify}{\justifying}{\endjustifying}

```

File 407 **lwarp-realscripts.sty**

§ 516 Package **realscripts**

(Emulates or patches code by WILL ROBERTSON.)

Pkg realscripts

realscripts is emulated. See lwarp.css for the `` of class `supsubscript`.

for HTML output: 1 \LWR@ProvidesPackagePass{realscripts}[2016/02/13]

The following are copied verbatim from the original, but given new names, since `xparse` definitions should not be `\let`.

```

2 \ExplSyntaxOn
3
4 \DeclareDocumentCommand \LWR@print@realsubscript {m} {
5   \fontspec_if_fontspec_font:TF {
6     \fontspec_if_opentype:TF
7     { \fontspec_if_feature:nTF {+subs}
8       { \addfontfeature{VerticalPosition=Inferior}#1 }
9       { \fontspec_if_feature:nTF {+sinf}
10        { \addfontfeature{VerticalPosition=ScientificInferior}#1 } }
11        { \fakesubscript{#1} }
12      }
13   }
14   { \fontspec_if_aat_feature:nnTF {10} {2}
15     { \addfontfeature{VerticalPosition=Inferior}#1 }
16     { \fakesubscript{#1} }
17   }
18 }
19 { \fakesubscript{#1} }
20 }
21
22 \DeclareDocumentCommand \LWR@HTML@realsubscript {m} {
23   \LWR@HTML@textsubscript{#1}
24 }

```

```

25
26 \LWR@formatted{realsubscript}
27
28
29 \DeclareDocumentCommand \LWR@print@realsuperscript {m} {
30   \fontspec_if_fontspec_font:TF
31   {
32     \fontspec_if_opentype:TF
33     { \fontspec_if_feature:nTF {+sups}
34       { {\addfontfeature{VerticalPosition=Superior}#1} }
35       { \fakesuperscript{#1} }
36     }
37     { \fontspec_if_aat_feature:nnTF {10} {1}
38       { {\addfontfeature{VerticalPosition=Superior}#1} }
39       { \fakesuperscript{#1} }
40     }
41   }
42   { \fakesuperscript{#1} }
43 }
44
45 \DeclareDocumentCommand \LWR@HTML@realsuperscript {m} {
46   \LWR@HTML@textsuperscript{#1}
47 }
48
49 \LWR@formatted{realsuperscript}
50
51
52 \DeclareDocumentCommand \LWR@print@textsubsuperscript {s 0{l} mm} {
53   \leavevmode
54   \group_begin:
55   \IfBooleanTF #1
56   {
57     \hbox_set:Nn \l_tmpa_box {\textsubscript*{#3}}
58     \hbox_set:Nn \l_tmpb_box {\textsuperscript*{#4}}
59   }
60   {
61     \hbox_set:Nn \l_tmpa_box {\textsubscript{#3}}
62     \hbox_set:Nn \l_tmpb_box {\textsuperscript{#4}}
63   }
64   \hbox_set:Nn \l_tmpa_box
65   { \box_move_down:nn \subsupersep {\box_use:N \l_tmpa_box} }
66   \hbox_set:Nn \l_tmpb_box
67   { \box_move_up:nn \subsupersep {\box_use:N \l_tmpb_box} }
68   \str_case:nnF {#2}
69   {
70     {l}{\use_i:nnn}
71     {c}{\use_ii:nnn}
72     {r}{\use_iii:nnn}
73   }
74   {
75     \PackageWarning{realscripts}{
76       Unknown~alignment~option~‘#2’. \MessageBreak
77       One~ of~ ‘l’,~ ‘c’,~ ‘r’,~ only
78     }
79     \use_i:nnn
80   }
81   {
82     \hbox_overlap_right:n { \box_use:N \l_tmpa_box }
83     \hbox_overlap_right:n { \box_use:N \l_tmpb_box }
84     \skip_horizontal:n {

```

```

85     \dim_max:nn {\box_wd:N \l_tmpa_box} {\box_wd:N \l_tmpb_box}
86   }
87 }
88 {
89   \dim_compare:nTF { \box_wd:N \l_tmpa_box > \box_wd:N \l_tmpb_box }
90   {
91     \skip_horizontal:n {
92       0.5\box_wd:N \l_tmpa_box-0.5\box_wd:N \l_tmpb_box
93     }
94     \box_use:N \l_tmpb_box
95     \skip_horizontal:n {
96       -0.5\box_wd:N \l_tmpa_box-0.5\box_wd:N \l_tmpb_box
97     }
98     \box_use:N \l_tmpa_box
99   }
100  {
101    \skip_horizontal:n {
102      0.5\box_wd:N \l_tmpb_box-0.5\box_wd:N \l_tmpa_box
103    }
104    \box_use:N \l_tmpa_box
105    \skip_horizontal:n {
106      -0.5\box_wd:N \l_tmpb_box-0.5\box_wd:N \l_tmpa_box
107    }
108    \box_use:N \l_tmpb_box
109  }
110 }
111 {
112   \skip_horizontal:n {
113     \dim_max:nn {\box_wd:N \l_tmpa_box} {\box_wd:N \l_tmpb_box}
114   }
115   \hbox_overlap_left:n { \box_use:N \l_tmpa_box }
116   \hbox_overlap_left:n { \box_use:N \l_tmpb_box }
117 }
118 \group_end:
119 }
120
121 \ExplSyntaxOff
122
123
124 \newcommand*{\LWR@realscriptsalign}{}
125
126 \newcommand*{\LWR@setrealscriptsalign}[1]{%
127   \renewcommand*{\LWR@realscriptsalign}{}%
128   \ifthenelse{\equal{#1}{c}}{%
129     \renewcommand{\LWR@realscriptsalign}{%
130       \LWR@print@inbox{text-align:center} ; %
131     }%
132   }{%
133     \ifthenelse{\equal{#1}{r}}{%
134       \renewcommand{\LWR@realscriptsalign}{%
135         \LWR@print@inbox{text-align:right} ; %
136       }%
137     }{%
138   }%
139 }
140 \DeclareDocumentCommand \LWR@HTML@textsubsuperscript {s O{1} mm} {%
141   \LWR@setrealscriptsalign{#2}%
142   \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
143     \textsuperscript{#4}\textsubscript{#3}%
144   }%

```

```

145 }
146 \LWR@formatted{textsubsuperscript}
147
148 \FilenameNullify{%
149   \RenewDocumentCommand{\textsuperscript}{s m}{}%
150   \RenewDocumentCommand{\textsubscript}{s m}{}%
151   \renewcommand{\fakesubscript}[1]{}%
152   \renewcommand{\fakesuperscript}[1]{}%
153   \renewcommand{\realsubscript}[1]{}%
154   \renewcommand{\realsuperscript}[1]{}%
155   \renewcommand{\textsubsuperscript}[2]{}%
156   \renewcommand{\textsupersubscript}[2]{}%
157 }

```

File 408 **lwarp-refcheck.sty**

§ 517 Package **refcheck**

Pkg refcheck refcheck is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{refcheck}[2013/02/14]

2 \def\showrefnames{}
3 \def\norefnames{}
4 \def\showcitenames{}
5 \def\nocitenames{}
6 \def\setonmsgs{}
7 \def\setoffmsgs{}
8 \def\checkunlbd{}
9 \def\ignoreunlbd{}
10 \newcommand*{\refcheckxrdoc}[2][{}]{

```

File 409 **lwarp-register.sty**

§ 518 Package **register**

(Emulates or patches code by MATTHEW LOVELL.)

Pkg register register is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{register}[2019/01/01]

2 \xpatchcmd{\register}
3   {\centering}
4   {%
5     \begin{center}%
6     \begin{lateximage}[-register--\PackageDiagramAltText]%
7   }
8   {}
9   {\LWR@patcherror{register}{register}}
10
11 \xpatchcmd{\endregister}
12   {\leftskip}
13   {%

```

```

14     \end{lateximage}\end{center}%
15     \leftskip%
16   }%
17   {}
18   {\LWR@patcherror{register}{endregister}}
19
20 \expandafter\xapptocmd\csname register*\endcsname
21   {%
22     \begin{center}%
23     \begin{lateximage}[-register--\PackageDiagramAltText]%
24   }
25   {}
26   {\LWR@patcherror{register}{register*}}
27
28 \expandafter\xpatchcmd\csname endregister*\endcsname
29   {\leftskip}
30   {%
31     \end{lateximage}\end{center}%
32     \leftskip%
33   }%
34   {}
35   {\LWR@patcherror{register}{endregister*}}
36
37 \setlength{\regWidth}{5in}

```

File 410 **lwarp-reysize.sty**

§ 519 Package **reysize**

(Emulates or patches code by DONALD ARSENEAU, BERNIE COSELL, MATT SWIFT.)

Pkg reysize

reysize is patched for use by lwarp, and emulated for MATHJAX.

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified font-size.

`\reysize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarily restored, and so should work as expected.

 **not small** The HTML browser's setting for minimum font size may limit how small the output will be displayed.

for HTML output:

```

1 \LWR@ProvidesPackagePass{reysize}[2013/03/29]
2 \let\LWR@origreysize\reysize
3 \LetLtxMacro\LWR@origlarger\larger
4 \LetLtxMacro\LWR@origsmaller\smaller
5 \let\LWR@relscale\relscale
6 \LetLtxMacro\LWR@origtextlarger\textlarger
7 \LetLtxMacro\LWR@origtextsmaller\textsmaller
8 \let\LWR@textscale\textscale
9
10 \appto\LWR@restoreorigformatting{%
11 \let\reysize\LWR@origreysize%
12 \LetLtxMacro\larger\LWR@origlarger%

```

```

13 \LetLtxMacro\smaller\LWR@origsmaller%
14 \let\relscale\LWR@relscale%
15 \LetLtxMacro\textlarger\LWR@origtextlarger%
16 \LetLtxMacro\textsmaller\LWR@origtextsmaller%
17 \let\textscale\LWR@textscale%
18 }
19
20 \newcounter{LWR@relsizetemp}
21
22 \renewcommand*\relsize}[1]{%
23 \renewcommand*\larger}[1][1]{%
24 \renewcommand*\smaller}[1][1]{%
25 \renewcommand*\relscale}[1]{%
26
27 \renewcommand*\textlarger}[2][1]{%
28 \setcounter{LWR@relsizetemp}{100+(#1*20)}%
29 \InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textlarger}{#2}%
30 }
31
32 \renewcommand*\textsmaller}[2][1]{%
33 \setcounter{LWR@relsizetemp}{100-(#1*20)}%
34 \InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textsmaller}{#2}%
35 }
36
37 \renewcommand*\textscale}[2]{%
38 \setcounter{LWR@relsizetemp}{100*\real{#1}}%
39 \InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textscale}{#2}%
40 }

```

For MATHJAX:

```

41 \begin{warpMathJax}
42 \CustomizeMathJax{\newcommand{\mathlarger}[1]{#1}}
43 \CustomizeMathJax{\newcommand{\mathsmaller}[1]{#1}}
44 \end{warpMathJax}

```

File 411 **lwarp-repeatindex.sty**

§ 520 Package **repeatindex**

Pkg repeatindex

repeatindex is emulated for lwarp.

 **style file** lwarp must be used with a special style file:

```
\usepackage[makeindex,makeindexStyle={lwarp_repeatindex}]{lwarp}
```

where lwarp_repeatindex.ist may be copied from the following modified version of lwarp.ist:

```

preamble
"\begin{theindex}
  \providecommand*\lettergroupDefault[1]{}
  \providecommand*\lettergroup[1]{%
    \par\textbf{#1}\par
    \nopagebreak
  }

```

```
"
headings_flag 1
heading_prefix "
  \lettergroup{"
heading_suffix "}"
delim_0 "[", \hyperindexref{"
delim_1 " ", \hyperindexref{"
delim_2 " ", \hyperindexref{"
delim_n "}", \hyperindexref{"
delim_r "} -- \hyperindexref{"
delim_t "}"

item_0 "\n \item ["
```

(The modifications are the `delim_0` and `item_0` entries.)

for HTML output: 1 \LWR@ProvidesPackageDrop{repeatindex}[2001/10/13]

In the `lwarp` core, `\LWR@indexitem` is modified to accept the optional `\item` argument.

```
2 \RequirePackage{makeidx}
3 \def\entryprefix{\itshape}
4 \def\entrypostfix{\dots}
```

File 412 **lwarp-repltext.sty**

§ 521 Package **repltext**

Pkg repltext

repltext is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{repltext}[2020/09/25]

```
2 \newcommand{\repltext}[2]{#2}
3 \newcommand*{\prevrepl}{}
```

For MATHJAX:

```
4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\repltext}[2]{#2}}
6 \end{warpMathJax}
```

File 413 **lwarp-resizegather.sty**

§ 522 Package **resizegather**

Pkg resizegather

resizegather is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{resizegather}[2016/05/16]

```
2 \newcommand*{\resizegathersetup}[1]{}
```

File 414 **lwarp-returntogrid.sty**

§ 523 Package **returntogrid**

Pkg returntogrid returntogrid is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{returntogrid}[2018/08/21]

2 \NewDocumentCommand\returntogrid{ 0 {} }{}
3 \NewDocumentCommand\returntogridsetup { m } {}
4 \NewDocumentCommand\showdebugpagegrid {} {}
```

File 415 **lwarp-rlepsz.sty**

§ 524 Package **rlepsz**

(Emulates or patches code by MICHAEL GREENE, COLIN ROURKE.)

Pkg rlepsz rlepsz is patched for use by lwarp.

 **Rename the style file!** The file rlepsz.tex must be copied to rlepsz.sty for lwarp to detect and patch it.

for HTML output:

```
1 \LWR@ProvidesPackagePass{rlepsz}% No date given.

2 \xpretocmd{\relabelbox}
3   {\begin{lateximage}}
4   {}
5   {\LWR@patcherror{rlepsz}{relabelbox}}
6
7 \xapptocmd{\endrelabelbox}
8   {\end{lateximage}}
9   {}
10  {\LWR@patcherror{rlepsz}{endrelabelbox}}
```

File 416 **lwarp-rmathbr.sty**

§ 525 Package **rmathbr**

(Emulates or patches code by DENIS RYABOV.)

Pkg rmathbr rmathbr is used as-is for SVG math, and emulated for MATHJAX.

for HTML output:

```
1 \LWR@ProvidesPackagePass{rmathbr}[2020/12/11]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\def\*{~}}
4 \CustomizeMathJax{\newcommand{\cdott}{\cdot}}
5 \CustomizeMathJax{\newcommand{\nobr}{}}
6 \end{warpMathJax}
```

File 417 **lwarp-rmpage.sty**

§ 526 Package **rmpage**

Pkg rmpage rmpage is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{rmpage}[1997/09/29]

File 418 **lwarp-romanbar.sty**

§ 527 Package **romanbar**

(Emulates or patches code by H.-MARTIN MÜNCH.)

Pkg romanbar romanbar is patched for use by lwarp.

An inline class with an overline and underline is used.

for HTML output: 1 \LWR@ProvidesPackagePass{romanbar}[2012/01/01]

```

2 \DeclareRobustCommand{\Roman@bar}[1]{% #1 is in Roman, i.e. MMXII
3 \InlineClass[%
4   text-decoration: overline underline ;
5 ]{romanbar}{#1}%
6 }
```

File 419 **lwarp-romanbarpagenumber.sty**

§ 528 Package **romanbarpagenumber**

Pkg romanbarpagenumber romanbarpagenumber is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{romanbarpagenumber}[2015/02/06]

File 420 **lwarp-rotating.sty**

§ 529 Package **rotating**

(Emulates or patches code by ROBIN FAIRBAIRNS, SEBASTIAN RAHTZ, LEONOR BARROCA.)

Pkg rotating rotating is emulated.

All rotations are ignored in HTML output.

for HTML output: 1 \LWR@ProvidesPackagePass{rotating}[2016/08/11]
2 \RequirePackage{graphicx}

```

3 \LetLtxMacro\LWR@HTML@sidewaystable\table
4 \let\endLWR@HTML@sidewaystable\endtable
5 \LWR@formattedenv{sidewaystable}
6
7 \LetLtxMacro\LWR@HTML@sidewaysfigure\figure
8 \let\endLWR@HTML@sidewaysfigure\endfigure
9 \LWR@formattedenv{sidewaysfigure}
10
11 \newenvironment*{LWR@HTML@sideways}{}{}
12 \LWR@formattedenv{sideways}
13
14 \newenvironment*{LWR@HTML@turn}[1]{}{}
15 \LWR@formattedenv{turn}
16
17 \newenvironment*{LWR@HTML@rotate}[1]{}{}
18 \LWR@formattedenv{rotate}
19
20 \NewDocumentCommand{\LWR@HTML@turnbox}{m +m}{#2}
21 \LWR@formatted{turnbox}
22
23 \let\LWR@HTML@rotcaption\caption
24 \LWR@formatted{rotcaption}
25
26 \let\LWR@HTML@makerotcaption\makecaption
27 \LWR@formatted{@makerotcaption}

```

File 421 **lwarp-rotfloat.sty**

§ 530 Package **rotfloat**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg rotfloat

rotfloat is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{rotfloat}[2004/01/04]
2
3 \RequirePackage{float}
4 \RequirePackage{rotating}

```

`\newfloat` {<1: type>} {<2: placement>} {<3: ext>} [<4: within >]

Emulates the `\newfloat` command from the `float` package. Sideways floats are `\let` to the same as regular floats.

“placement” is ignored.

```

5 \RenewDocumentCommand{\newfloat}{m m m o}{%
6 \IfValueTF{#4}%
7 {%
8   \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}%
9 }%
10 {%
11   \DeclareFloatingEnvironment[fileext=#3]{#1}%
12 }%
13 \csletcs{sideways#1}{#1}%
14 \csletcs{endsideways#1}{end#1}%

```

Remember the float style:

```
15 \csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
16 \csedef{LWR@floatstyle@sideways#1}{\LWR@floatstyle}%
```

`newfloat` package automatically creates the `\listof` command for new floats, but `float` does not, so remove `\listof` here in case it is manually created later:

```
17 \cslet{listof#1s}\relax%
18 \cslet{listof#1es}\relax%
19 \cslet{listofsideways#1s}\relax%
20 \cslet{listofsideways#1es}\relax%
21 }
```

File 422 **lwarp-rviewport.sty**

§ 531 Package **rviewport**

Pkg rviewport

`rviewport` is honored inside a `lateximage`, and otherwise ignored for HTML output.

If `rviewport` is important for an image, enclose the image inside a `lateximage` environment.

for HTML output:

```
1 \LWR@ProvidesPackagePass{rviewport}[2011/08/27]
2 \define@key{igraph}{rviewport}{}
```

File 423 **lwarp-savetrees.sty**

§ 532 Package **savetrees**

Pkg savetrees

`savetrees` is ignored.

for HTML output: Discard all options for `lwarp-savetrees`:

```
1 \LWR@ProvidesPackageDrop{savetrees}[2016/04/13]
```

File 424 **lwarp-scalefnt.sty**

§ 533 Package **scalefnt**

Pkg scalefnt

(Emulates or patches code by D. CARLISLE.)

`scalefnt` is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{scalefnt}
2 \DeclareRobustCommand\scalefont[1]{} 
```

File 425 **lwarp-scalerel.sty**

§ 534 Package **scalerel**

(Emulates or patches code by STEVEN B. SEGLETES.)

Pkg scalerel

scalerel is used as-is for SVG math, and is emulated and ignored for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{scalerel}[2016/12/29]

For MATHJAX:

```

2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{scalerel}
4
5 \CustomizeMathJax{\newcommand{\scalerel}{\ifstar{\scalerelplain}{\scalerelplus}}}
6 \CustomizeMathJax{\newcommand{\scalerelplain}[3][\#2]}
7 \CustomizeMathJax{\newcommand{\scalerelplus}[3][\#2\#3]}
8 \CustomizeMathJax{\newcommand{\stretchrel}{\ifstar{\stretchrelplain}{\stretchrelplus}}}
9 \CustomizeMathJax{\newcommand{\stretchrelplain}[3][\#2]}
10 \CustomizeMathJax{\newcommand{\stretchrelplus}[3][\#2\#3]}
11 \CustomizeMathJax{\newcommand{\scaleto}[3][\#2]}
12 \CustomizeMathJax{\newcommand{\stretchto}[3][\#2]}
13 \CustomizeMathJax{\newcommand{\scaleleftright}[4][\#2\#3\#4]}
14 \CustomizeMathJax{\newcommand{\stretchleftright}[4][\#2\#3\#4]}
15 \CustomizeMathJax{\newcommand{\hstretch}[2][\#2]}
16 \CustomizeMathJax{\newcommand{\vstretch}[2][\#2]}
17 \CustomizeMathJax{\newcommand{\scaleobj}[2][\#2]}
18 \CustomizeMathJax{\newcommand{\ThisStyle}[1][\#1]}
19 \CustomizeMathJax{\newcommand{\SavedStyle}{}}
20 \CustomizeMathJax{\def\scriptstyleScaleFactor{.7}}
21 \CustomizeMathJax{\def\scriptscriptstyleScaleFactor{.5}}
22 \CustomizeMathJax{\newcommand{\discernmathstyle}{}}
23 \CustomizeMathJax{\newcommand{\ignoremathstyle}[1][T]}
24 \CustomizeMathJax{\newcommand{\Isnextbyte}[3][v]}
25 \end{warpMathJax}

```

File 426 **lwarp-schemata.sty**

§ 535 Package **schemata**

(Emulates or patches code by CHARLES P. SCHAUM.)

Pkg schemata

schemata is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{schemata}[2020/11/23]

```

2 \LetLtxMacro\LWR@schemata@origschema\schema
3 \LetLtxMacro\LWR@schemata@origSchema\Schema
4
5 \renewcommand{\schema}[3][open]{%
6   \begin{lateximage}[-schemata-~\PackageDiagramAltText]%
7     \LWR@print@normalsize%

```

```

8   \LWR@schemata@origschema[#1]{#2}{#3}%
9   \end{lateximage}%
10 }
11
12 \renewcommand{\Schema}[5][Open]{%
13   \begin{lateximage}[-schemata--\PackageDiagramAltText]%
14   \LWR@print@normalsize%
15   \LWR@schemata@origSchema[#1]{#2}{#3}{#4}{#5}%
16   \end{lateximage}%
17 }

```

File 427 **lwarp-scrextend.sty**

§ 536 Package **scrextend**

Pkg scrextend

scrextend is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. `\DeclareDocumentCommand` is used to overwrite the koma-script definitions.

for HTML output: 1 \LWR@ProvidesPackageDrop{scrextend}[2020/01/24]

```

2 \DeclareDocumentCommand{\setkomafont}{m m}{}
3 \DeclareDocumentCommand{\addkomafont}{m m}{}
4 \DeclareDocumentCommand{\usekomafont}{m}{}
5
6 \DeclareDocumentCommand{\usefontofkomafont}{m}{}
7 \DeclareDocumentCommand{\useencodingofkomafont}{m}{}
8 \DeclareDocumentCommand{\usesizeofkomafont}{m}{}
9 \DeclareDocumentCommand{\usefamilyofkomafont}{m}{}
10 \DeclareDocumentCommand{\useseriesofkomafont}{m}{}
11 \DeclareDocumentCommand{\useshapeofkomafont}{m}{}
12
13 \providecommand*\coverpagetopmargin{}
14 \providecommand*\coverpagebottommargin{}
15 \providecommand*\coverpageleftmargin{}
16 \providecommand*\coverpagerightmargin{}
17

```

Title page:

```

18 \AtBeginDocument{
19   \let\LWR@koma@orig@maketitle\maketitle
20   \DeclareDocumentCommand{\maketitle}{o}{\LWR@koma@orig@maketitle}
21 }
22
23 \providecommand*\@maketitle{}
24 \renewrobustcmd{\@maketitle}{%
25   \ifdefvoid{\@titlehead}{}{%
26     \begin{BlockClass}{titlehead}%
27     \@titlehead%
28     \end{BlockClass}%
29   }%
30   \ifdefvoid{\@subject}{}{%
31     \begin{BlockClass}{subject}%

```

```

32     \@subject%
33     \end{BlockClass}%
34 }%
35 \LWR@stoppars%
36 \LWR@htmltag{\LWR@tagtitle}%
37 \@title%
38 \LWR@htmltag{\LWR@tagtitleend}%
39 \ifdefvoid{\@subtitle}{}%
40     \begin{BlockClass}{subtitle}%
41     \@subtitle%
42     \end{BlockClass}%
43 }%
44 \LWR@startpars%
45 \begin{BlockClass}{author}%

46 \renewcommand*{\cr}{}%
47 \renewcommand*{\rcrcr}{}%
48 \renewcommand*{\noalign}{}%

49     \renewcommand{\and}{%
50         \end{BlockClass}%
51         \begin{BlockClass}{oneauthor}%
52     }%
53     \begin{BlockClass}{oneauthor}%
54         \@author%
55     \end{BlockClass}%
56 \end{BlockClass}%
57 \begin{BlockClass}{titledate}%
58 \@date%
59 \end{BlockClass}%
60 \ifdefvoid{\@published}{}%
61     \begin{BlockClass}{published}%
62     \@published%
63     \end{BlockClass}%
64 }%
65 }
66
67 \AddSubtitlePublished
68
69 \DeclareDocumentCommand{\extratitle}{m}{}
70 \DeclareDocumentCommand{\frontispiece}{m}{}
71
72 \def\@titlehead{}%
73 \DeclareDocumentCommand{\titlehead}{m}{\gdef\@titlehead{#1}}%
74
75 \def\@subject{}%
76 \DeclareDocumentCommand{\subject}{m}{\gdef\@subject{#1}}%
77
78 % \subtitle and \published are defined by \AddSubtitlePublished
79
80 \DeclareDocumentCommand{\publishers}{m}{\published{#1}}
81
82 \DeclareDocumentCommand{\uppertitleback}{m}{}
83 \DeclareDocumentCommand{\lowertitleback}{m}{}
84 \DeclareDocumentCommand{\dedication}{m}{}
85
86 \DeclareDocumentCommand{\ifthispageodd}{m m}{#1}
87
88 \DeclareDocumentCommand{\cleardoublepageusingstyle}{m}{}
89 \DeclareDocumentCommand{\cleardoubleemptypage}{}{}

```

```

90 \DeclareDocumentCommand{\cleardoubleplainpage}{}{}
91 \DeclareDocumentCommand{\cleardoublestandardpage}{}{}
92 \DeclareDocumentCommand{\cleardoubleoddpge}{}{}
93 \DeclareDocumentCommand{\cleardoubleoddpgeusingstyle}{m}{}
94 \DeclareDocumentCommand{\cleardoubleoddpgeemptypage}{}{}
95 \DeclareDocumentCommand{\cleardoubleoddpgeplainpage}{}{}
96 \DeclareDocumentCommand{\cleardoubleoddpgestandardpage}{}{}
97 \DeclareDocumentCommand{\cleardoubleevenpage}{}{}
98 \DeclareDocumentCommand{\cleardoubleevenpageusingstyle}{m}{}
99 \DeclareDocumentCommand{\cleardoubleevenemptypage}{}{}
100 \DeclareDocumentCommand{\cleardoubleevenplainpage}{}{}
101 \DeclareDocumentCommand{\cleardoubleevenstandardpage}{}{}
102
103 \DeclareDocumentCommand{\multiplefootnoteseparator}{}{%
104   \begingroup\let\thefootnotemark\multfootsep\@makefnmark\endgroup
105 }
106
107 \DeclareDocumentCommand{\multfootsep}{}{,}
108
109 \DeclareDocumentCommand{\footref}{m}{%
110   \begingroup
111     \unrestored@protected@xdef\thefnmark{\ref{#1}}%
112   \endgroup
113   \@footnotemark
114 }
115
116 \DeclareDocumentCommand{\deffootnote}{o m m}{}
117 \DeclareDocumentCommand{\deffootnotemark}{m}{}
118 \DeclareDocumentCommand{\setfootnoterule}{o m}{}
119 \DeclareDocumentCommand{\raggedfootnote}{}{}

120 \DeclareDocumentCommand{\dictum}{o m}{
121   \begin{LWR@BlockClassWP}{\LWR@print@ebox{text-align:right}}{}{\dictum}
122     #2
123     \IfValueT{#1}
124     {
125       \LWR@stoppars%
126       \ifbool{FormatWP}
127         {\begin{BlockClass}[\LWR@print@ebox{border-top:} 1px solid gray]{dictumauthor}}
128         {\begin{BlockClass}{dictumauthor}}
129       \dictumauthorformat{#1}
130       \end{BlockClass}
131     }
132   \end{LWR@BlockClassWP}
133 }
134
135 \DeclareDocumentCommand{\dictumwidth}{}{}
136 \DeclareDocumentCommand{\dictumauthorformat}{m}{(#1)}
137 \DeclareDocumentCommand{\dictumrule}{}{}
138 \DeclareDocumentCommand{\raggeddictum}{}{}
139 \DeclareDocumentCommand{\raggeddictumtext}{}{}
140 \DeclareDocumentCommand{\raggeddictumauthor}{}{}
141
142 \DeclareDocumentEnvironment{labeling}{o m}
143 {%
144   \def\sc@septext{#1}%
145   \list{}{}%
146   \let\makelabel\labelinglabel%
147 }
148 {

```

```

149 \endlist
150 }
151
152 \DeclareDocumentCommand{\labelinglabel}{m}{%
153 #1 \quad \sc@septext%
154 }
155
156 \let\addmargin\relax
157 \let\endaddmargin\relax
158 \cslet{addmargin*}{\relax}
159 \cslet{endaddmargin*}{\relax}

160 \NewDocumentEnvironment{addmargin}{s O{} m}
161 {
162 \LWR@stoppars%
163 \setlength{\LWR@templengthtwo}{#3}
164 \ifblank{#2}
165 {
166   \begin{BlockClass}[
167     \LWR@print@mbbox{margin-left:\LWR@printlength{\LWR@templengthtwo}} ;
168     \LWR@print@mbbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
169   ]{addmargin}
170 }
171 {
172   \setlength{\LWR@templengthone}{#2}
173   \begin{BlockClass}[
174     \LWR@print@mbbox{margin-left:\LWR@printlength{\LWR@templengthone}} ;
175     \LWR@print@mbbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
176   ]{addmargin}
177 }
178 }
179 {\end{BlockClass}\LWR@startpars}

```

Ref to create a starred environment:

<https://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment>

```

180
181 \ExplSyntaxOn
182 \cs_new:cpn {addmargin*} {\addmargin*}
183 \cs_new_eq:cN {endaddmargin*} \endaddmargin
184 \ExplSyntaxOff
185
186 \DeclareDocumentCommand{\marginline}{m}{\marginpar{#1}}

```

File 428 **lwarp-scrhack.sty**

§ 537 Package **scrhack**

Pkg scrhack

scrhack is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{scrhack}[2018/03/30]

File 429 **lwarp-scrlayer.sty**

§ 538 Package **scrlayer**

(Emulates or patches code by MARKUS KOHM.)

Pkg scrlayer

scrlayer is emulated.

 **Not fully tested!** [Please send bug reports!](#)

for HTML output: 1 \LWR@ProvidesPackageDrop{scrlayer}[2018/03/30]

```

2 \newcommand*\DeclareSectionNumberDepth}[2]{}
3 \newcommand*\DeclareLayer}[2]{}{}
4 \newcommand*\DeclareNewLayer}[2]{}{}
5 \newcommand*\ProvideLayer}[2]{}{}
6 \newcommand*\RedeclareLayer}[2]{}{}
7 \newcommand*\ModifyLayer}[2]{}{}
8 \newcommand*\layerhalign{}{}
9 \newcommand*\layervalign{}{}
10 \newcommand*\layerxoffset{}{}
11 \newcommand*\layeryoffset{}{}
12 \newcommand*\layerwidth{}{}
13 \newcommand*\layerheight{}{}
14 \providecommand*\LenToUnit}[1]{\strip@pt\dimexpr#1*\p@/\unitlength}
15 \newcommand*\putUL}[1]{}
16 \newcommand*\putUR}[1]{}
17 \newcommand*\putLL}[1]{}
18 \newcommand*\putLR}[1]{}
19 \newcommand*\putC}[1]{}
20 \newcommand*\GetLayerContents}[1]{}
21 \newcommand*\IfLayerExists}[3]{#3}
22 \newcommand*\DestroyLayer}[1]{}
23 \newcommand*\layercontentsmeasure{}{}
24 \newcommand*\currentpagestyle{}{}
25 \newcommand*\BeforeSelectAnyPageStyle}[1]{}
26 \newcommand*\AfterSelectAnyPageStyle}[1]{}
27 \newcommand*\DeclarePageStyleAlias}[2]{}
28 \newcommand*\DeclareNewPageStyleAlias}[2]{}
29 \newcommand*\ProvidePageStyleAlias}[2]{}
30 \newcommand*\RedeclarePageStyleAlias}[2]{}
31 \newcommand*\DestroyPageStyleAlias}[1]{}
32 \newcommand*\GetRealPageStyle}[1]{}
33 \newcommand*\DeclarePageStyleByLayers}[3]{}{}
34 \newcommand*\DeclareNewPageStyleByLayers}[3]{}{}
35 \newcommand*\ProvidePageStyleByLayers}[3]{}{}
36 \newcommand*\RedeclarePageStyleByLayers}[3]{}{}
37 \NewDocumentCommand*\ForEachLayerOfPageStyle}{s m m}{}
38 \newcommand*\AddLayersToPageStyle}[2]{}
39 \newcommand*\AddLayersAtBeginOfPageStyle}[2]{}
40 \newcommand*\AddLayersAtEndOfPageStyle}[2]{}
41 \newcommand*\RemoveLayersFromPageStyle}[2]{}
42 \newcommand*\AddLayersToPageStyleBeforeLayer}[3]{}
43 \newcommand*\AddLayersToPageStyleAfterLayer}[3]{}
44 \newcommand*\UnifyLayersAtPageStyle}[1]{}
45 \newcommand*\ModifyLayerPageStyleOptions}[2]{}

```

```

46 \newcommand*\AddToLayerPageStyleOptions}[2]{}
47 \newcommand{\IfLayerPageStyleExists}[3]{#3}
48 \newcommand{\IfRealLayerPageStyleExists}[3]{#3}
49 \newcommand{\IfLayerAtPageStyle}[4]{#4}
50 \newcommand{\IfSomeLayerAtPageStyle}[4]{#4}
51 \newcommand{\IfLayersAtPageStyle}[4]{#4}
52 \newcommand*\DestroyRealLayerPageStyle}[1]{}
53 \ifundefined{footheight}{\newlength\footheight}{}
54 \DeclareDocumentCommand{\automark}{s o m}{}
55 \DeclareDocumentCommand{\manualmark}{}{}
56 \DeclareDocumentCommand{\MakeMarkcase}{m}{#1}

57 \newcommand{\partmarkformat}{}
58 \if@chapter
59 \newcommand{\chaptermarkformat}{}
60 \fi
61 \newcommand{\sectionmarkformat}{}
62 \DeclareDocumentCommand{\GenericMarkFormat}{m}{}

63 \newcommand*\@mkleft}[1]{}
64 \newcommand*\@mkright}[1]{}
65 \newcommand*\@mkdouble}[1]{}
66 \newcommand*\@mkboth}[2]{}
67 \newcommand*\sclayerInitInterface}[1][{}]{
68 \newcommand{\sclayerAddToInterface}[3][{}]{
69 \newcommand{\sclayerAddCsToInterface}[3][{}]{
70 \newcommand{\sclayerOnAutoRemoveInterface}[2][{}]{

```

File 430 **lwarp-sclayer-notecolumn.sty**

§ 539 Package **sclayer-notecolumn**

(Emulates or patches code by MARKUS KOHM.)

Pkg sclayer-notecolumn sclayer-notecolumn is emulated.

 **Not fully tested!** [Please send bug reports!](#)

for HTML output: 1 \LWR@ProvidesPackageDrop{sclayer-notecolumn}[2018/02/02]

```

2 \newcommand*\DeclareNoteColumn}[2][{}]{
3 \newcommand*\DeclareNewNoteColumn}[2][{}]{
4 \newcommand*\ProvideNoteColumn}[2][{}]{
5 \newcommand*\RedeclareNoteColumn}[2][{}]{
6 \NewDocumentCommand{\makenote}{s o m}{\marginpar{#3}}
7 \newcommand*\syncwithnotecolumn}[1][{}]{
8 \newcommand*\syncwithnotecolumns}[1][{}]{
9 \newcommand*\clearnotecolumn}[1][{}]{
10 \newcommand*\clearnotecolumns}[1][{}]{

```

File 431 **lwarp-sclayer-scrpage.sty**

§ 540 Package **sclayer-scrpage**

(Emulates or patches code by MARKUS KOHM.)

Pkg scrlayer-scrpage

scrlayer-scrpage is ignored.

 **Not fully tested!** [Please send bug reports!](#)

for HTML output:

```

1 \LWR@ProvidesPackageDrop{scrlayer-scrpage}[2018/03/30]

2 \@ifundefined{footheight}{\newlength\footheight}{}
3 \NewDocumentCommand{\lehead}{s o m}{}
4 \NewDocumentCommand{\cehead}{s o m}{}
5 \NewDocumentCommand{\rehead}{s o m}{}
6 \NewDocumentCommand{\lohead}{s o m}{}
7 \NewDocumentCommand{\cohead}{s o m}{}
8 \NewDocumentCommand{\rohead}{s o m}{}
9 \NewDocumentCommand{\lefoot}{s o m}{}
10 \NewDocumentCommand{\cefoot}{s o m}{}
11 \NewDocumentCommand{\refoot}{s o m}{}
12 \NewDocumentCommand{\lofoot}{s o m}{}
13 \NewDocumentCommand{\cofoot}{s o m}{}
14 \NewDocumentCommand{\rofoot}{s o m}{}
15 \NewDocumentCommand{\ohead}{s o m}{}
16 \NewDocumentCommand{\chead}{s o m}{}
17 \NewDocumentCommand{\ihead}{s o m}{}
18 \NewDocumentCommand{\ofoot}{s o m}{}
19 \NewDocumentCommand{\cfoot}{s o m}{}
20 \NewDocumentCommand{\ifoot}{s o m}{}

21 \NewDocumentCommand{\automark}{som}{}
22 \newcommand*{\manualmark}{}

23 \DeclareDocumentCommand{\MakeMarkcase}{m}{#1}

24 \let\headmark\leftmark
25 \providecommand{\pnumfont}{\normalfont}%
26 \DeclareRobustCommand\pagemark{{\pnumfont{\thepage}}}%

27 \newcommand*{\defpairofpagestyles}[3][{}]{
28 \newcommand*{\newpairofpagestyles}[3][{}]{
29 \newcommand*{\renewpairofpagestyles}[3][{}]{
30 \newcommand*{\providepairofpagestyles}[3][{}]{

31 \newcommand*{\clearmainofpairofpagestyles}{}
32 \newcommand*{\clearplainofpairofpagestyles}{}
33 \newcommand*{\clearpairofpagestyles}{}
34 \newcommand*{\clearscrheadings}{}
35 \newcommand*{\clearscrheadfoot}{}
36 \newcommand*{\clearscrplain}{}

37 \NewDocumentCommand{\deftriplepagestyle}{m o m m m m m m}{}
38 \NewDocumentCommand{\newtriplepagestyle}{m o m m m m m m}{}
39 \NewDocumentCommand{\renewtriplepagestyle}{m o m m m m m m}{}
40 \NewDocumentCommand{\providetriplepagestyle}{m o m m m m m m}{}
41 \newcommand*{\defpagestyle}[3]{}
42 \newcommand*{\newpagestyle}[3]{}
43 \newcommand*{\providepagestyle}[3]{}
44 \newcommand*{\renewpagestyle}[3]{}

```

File 432 **lwarp-scrpage2.sty**

§ 541 Package **scrpage2**

(Emulates or patches code by MARKUS KOHM.)

Pkg scrpage2

scrpage2 is ignored.

 **Not fully tested!** [Please send bug reports!](#)

for HTML output: 1 \LWR@ProvidesPackageDrop{scrpage2}[2018/03/30]

```

2 \@ifundefined{footheight}{\newlength\footheight}{}
3 \NewDocumentCommand{\lehead}{o m}{}
4 \NewDocumentCommand{\cehead}{o m}{}
5 \NewDocumentCommand{\rehead}{o m}{}
6 \NewDocumentCommand{\lohead}{o m}{}
7 \NewDocumentCommand{\cohead}{o m}{}
8 \NewDocumentCommand{\rohead}{o m}{}
9 \NewDocumentCommand{\lefoot}{o m}{}
10 \NewDocumentCommand{\cefoot}{o m}{}
11 \NewDocumentCommand{\refoot}{o m}{}
12 \NewDocumentCommand{\lofoot}{o m}{}
13 \NewDocumentCommand{\cofoot}{o m}{}
14 \NewDocumentCommand{\rofoot}{o m}{}
15 \NewDocumentCommand{\ohead}{o m}{}
16 \NewDocumentCommand{\chead}{o m}{}
17 \NewDocumentCommand{\ihead}{o m}{}
18 \NewDocumentCommand{\ofoot}{o m}{}
19 \NewDocumentCommand{\cfoot}{o m}{}
20 \NewDocumentCommand{\ifoot}{o m}{}
21 \DeclareDocumentCommand{\automark}{o m}{}
22 \DeclareDocumentCommand{\manualmark}{}{}
23 \DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
24 \NewDocumentCommand{\deftripstyle}{m o o m m m m m}{}
25 \NewDocumentCommand{\defpagestyle}{s m m}{}
26 \NewDocumentCommand{\newpagestyle}{s m m}{}
27 \NewDocumentCommand{\renewpagestyle}{s m m}{}
28 \NewDocumentCommand{\providepagestyle}{s m m}{}
29 \newcommand{\partmarkformat}{}
30 \if@chapter
31 \newcommand{\chaptermarkformat}{}
32 \fi
33 \newcommand{\sectionmarkformat}{}
34 \newcommand{\subsectionmarkformat}{}
35 \newcommand{\subsubsectionmarkformat}{}
36 \newcommand{\paragraphmarkformat}{}
37 \newcommand{\subparagraphmarkformat}{}
38
39 \newcommand*\clearscrheadings{}
40 \newcommand*\clearscrheadfoot{}
41 \newcommand*\clearscrplain{}

```

File 433 **lwarp-section.sty**

§ 542 Package **section**

Pkg section

section is ignored.

(Emulates or patches code by OLIVER PRETZEL.)

for HTML output:

```

1 \LWR@ProvidesPackageDrop{section}

2 \ifx\chapter\undefined
3 \def\chsize{\Large}\def\hdsiize{\huge}\else
4 \def\chsize{\huge}\def\hdsiize{\Huge}
5 \fi
6 \let\ttsize\LARGE
7 \let\ausize\large
8 \let\dasize\large
9 \let\secsize\Large
10 \let\subsize\large
11 \let\hdpos\raggedright
12 \newcounter{hddepth}
13 \let\fpind\relax
14 \def\ttfnt{}
15 \def\hdfnt{}
16 \def\fefnt{}
17 \def\thfnt{}
18 \def\pgfnt{}
19 \def\hmkfnt{}
20 \let\mkcse\uppercase
21 \def\hddot{}
22 \def\cpdot{:}
23 \def\nmdot{}
24 \ifx\secindent\undefined
25 \newdimen\secindent
26 \newskip\secpreskp
27 \newskip\secpstskp
28 \newdimen\subindent
29 \newskip\subpreskp
30 \newskip\subpstskp
31 \newskip\parpstskp
32 \newcount\c@hddepth
33 \fi
```

File 434 **lwarp-sectionbreak.sty**

§ 543 Package **sectionbreak**

Pkg sectionbreak

sectionbreak is patched for use by lwarp.

(Emulates or patches code by MICHAL HOFTICH.)

for HTML output:

```

1 \LWR@ProvidesPackagePass{sectionbreak}[2018-01-03]
```

```

2 \renewcommand\asterism{\HTMLunicode{2042}}
3
4 \renewcommand\pre@sectionbreak{}
5 \renewcommand\post@sectionbreak{}
6
7 \renewcommand\print@sectionbreak[1]{%
8 \begin{center}
9 #1
10 \end{center}
11 }
12

```

File 435 **lwarp-sectsty.sty**

§ 544 Package **sectsty**

(Emulates or patches code by ROWLAND McDONNELL.)

Pkg sectsty

sectsty is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{sectsty}[2002/02/25]
```

```

2 \newcommand*\partfont [1] {}
3 \newcommand*\partnumberfont [1] {}
4 \newcommand*\parttitlefont [1] {}
5 \newcommand*\chapterfont [1] {}
6 \newcommand*\chapternumberfont [1] {}
7 \newcommand*\chaptertitlefont [1] {}
8 \newcommand*\sectionfont [1] {}
9 \newcommand*\subsectionfont [1] {}
10 \newcommand*\subsubsectionfont [1] {}
11 \newcommand*\paragraphfont [1] {}
12 \newcommand*\subparagraphfont [1] {}
13 \newcommand*\minisecfont [1] {}
14 \newcommand*\allsectionsfont[1] {}
15 \newcommand{\nohang}{}

```

`\sectionrule` is only to be used in `*font` commands, thus it is ignored.

```

16 \newcommand*\sectionrule[5]{}
17
18 \def\ulemheading#1#2{}

```

File 436 **lwarp-selectp.sty**

§ 545 Package **selectp**

Pkg selectp

selectp is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{selectp}% no date given
```

```
2 \newcommand*\outputonly[1]{}

```

File 437 **lwarp-semantic-markup.sty**

§ 546 Package **semantic-markup**

(Emulates or patches code by ANDREW A. CASHNER.)

Pkg semantic-markup

semantic-markup is patched for use by lwarp.



If using the endnotes option, add `\theendnotes` where desired.

for HTML output: 1 \LWR@ProvidesPackagePass{semantic-markup}[2018/05/21]

The endnotes must be printed by the user before the end of the document, since the end is after the HTML footer, etc.

```

2 \ifendnotes
3 \RenewDocumentCommand{\SetupEndnotes}{ }{%
4   \let\footnote=\endnote
5 %   \AtEndDocument{\DoBeforeEndnotes{\EndnoteFont\theendnotes}}%
6 }
7 \fi

```

HTML unicode characters from musicography are used.

```

8 \RequirePackage{musicography}
9
10 \let\fl\musFlat
11 \let\sh\musSharp
12 \let\na\musNatural

```

The `\musfig` is placed inside a hashed image, with a simple alt tag.

```

13 \RequirePackage{amsmath}
14
15 \RenewDocumentCommand{\musfig}{ m m }{%
16   \LWR@subsingledollar*%
17   {#1/#2}% alt tag
18   {musfig}% addL' hashing
19   {% contents
20     \LWR@origensuredmath{%
21       \genfrac{}{}{0pt}{1}{\text{#1}}{\text{#2}}%
22     }%
23   }%
24 }

```

The `\meter` is taken from musicography, and becomes a hashed image with a simple alt tag.

```

25 \RenewDocumentCommand{\meter}{ m m }{%
26   \musMeter{#1}{#2}%
27 }

```

File 438 **lwarp-seqspl.it.sty**

§ 547 Package **seqsplit**

(Emulates or patches code by BORIS VEYTSMAN.)

Pkg seqsplit

seqsplit is patched for use by lwarp.

For HTML output, the results are similar to print mode, and respond to window size.

 **svg math results** For SVG math, the output differs from print mode in that the contents are formatted in a minipage, which is then inline with the surrounding math.

For MATHJAX, the contents are used as-is.

for HTML output: 1 \LWR@ProvidesPackagePass{seqsplit}[2006/08/07]

Special handling because lwarp uses a box for svg math, which does not normally allow line breaks, so a print-mode minipage must be used to allow line breaks. The minipage will not be wrapped inline with any surrounding math.

```

2 \begin{warpHTML}
3 \LetLtxMacro\LWR@orig@seqsplit\seqsplit
4
5 \renewcommand*\seqsplit[1]{%
6   \ifmmode%
7     \begin{LWR@print@minipage}{6in}%
8     \LWR@orig@seqsplit{#1}%
9     \end{LWR@print@minipage}%
10  \else%
11    \InlineClass[word-wrap:break-word]{seqsplit}\LWR@orig@seqsplit{#1}}%
12  \fi
13 }
```

Between characters, an empty HTML comment is placed to allow a line wrap in the HTML source, without adding spaces in the output.

```

14 \AtBeginDocument{
15   \newcommand*\LWR@HTML@seqinsert}{%
16     \LWR@htmlcomment{ }}%
17   }
18   \LWR@formatted{seqinsert}
19 }
20 \end{warpHTML}
21
22 \begin{warpMathJax}
23 \CustomizeMathJax{\newcommand{\seqsplit}[1]{#1}}
24 \end{warpMathJax}
```

File 439 **lwarp-setspace.sty**

§ 548 Package **setspace**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg setspace

setspace is emulated.

Discard all options for lwarp-setspace:

for HTML output:

```

1 \LWR@ProvidesPackageDrop{setspace}[2011/12/19]
2
3 \newcommand*\setstretch[1]{}
4 \newcommand*\SetSinglespace[1]{}
5 \newcommand*\singlespacing{}
6 \newcommand*\onehalfspacing{}
7 \newcommand*\doublespacing{}
8
9 \newenvironment{singlespace}
10 {
11 \LWR@forcenewpage
12 \BlockClass{singlespace}
13 }
14 {\endBlockClass}
15
16 \newenvironment{singlespace*}
17 {
18 \LWR@forcenewpage
19 \BlockClass{singlespace}
20 }
21 {\endBlockClass}
22
23 \newenvironment{spacing}[1]{
24
25 }{
26
27 }
28
29 \newenvironment{onehalfspace}
30 {
31 \LWR@forcenewpage
32 \BlockClass{onehalfspace}
33 }
34 {\endBlockClass}
35
36 \newenvironment{doublespace}
37 {
38 \LWR@forcenewpage
39 \BlockClass{doublespace}
40 }
41 {\endBlockClass}

```

File 440 **lwarp-shadethm.sty**

§ 549 Package **shadethm**

(Emulates or patches code by JIM HEFFERON.)

Pkg shadethm shadethm is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{shadethm}[1999/11/23]

2 \newenvironment{LWR@HTML@shadebox}
3 {%
4   \convertcolorspec{named}{shadethmcolor}{HTML}\LWR@tempcolor%
5   \convertcolorspec{named}{shaderulecolor}{HTML}\LWR@tempcolortwo%
6   \begin{BlockClass}[%
7     background: \LWR@origpound\LWR@tempcolor ;
8     border: 1px solid \LWR@origpound\LWR@tempcolortwo ;
9   ]{shadebox}
10 }%
11 {\end{BlockClass}}
12 \LWR@formattedenv{shadebox}

```

File 441 **lwarp-shadow.sty**

§ 550 Package **shadow**

(Emulates or patches code by MAURO ORLANDINI.)

Pkg shadow shadow is emulated.

for HTML output: Discard all options for lwarp-shadow:

```

1 \LWR@ProvidesPackageDrop{shadow}[2003/02/19]

2 \newdimen\sboxsep
3 \newdimen\sboxrule
4 \newdimen\sdim
5
6 \newcommand{\shabox}[1]{%
7 \InlineClass{shabox}{#1}%
8 }

```

File 442 **lwarp-shapepar.sty**

§ 551 Package **shapepar**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg shapepar shapepar is patched for use by lwarp. Shapes appear in print mode, as well as inside a `lateximage`, but are ignored for HTML.

for HTML output:

```

1 \LWR@ProvidesPackagePass{shapepar}[2013/03/26]
2 \newcommand*\LWR@HTML@shapepar}[2][{}]{
3 \LWR@formatted{shapepar}
4
5 \NewDocumentCommand{\LWR@HTML@cutout}{m d()}{}
6 \LWR@formatted{cutout}

```

File 443 **lwarp-showidx.sty**

§ 552 Package **showidx**

Pkg showidx

showidx is ignored.

for HTML output: Discard all options for lwarp-showidx:

```
1 \LWR@ProvidesPackageDrop{showidx}[2014/09/29]
```

\@wrindex is redefined \@AtBeginDocument by the lwarp core.

File 444 **lwarp-showkeys.sty**

§ 553 Package **showkeys**

Pkg showkeys

showkeys is ignored.

for HTML output: Discard all options for lwarp-showkeys:

```
1 \LWR@ProvidesPackageDrop{showkeys}[2014/10/28]
```

```
2 \NewDocumentCommand{\showkeys}{s}{}

```

File 445 **lwarp-showlabels.sty**

§ 554 Package **showlabels**

Pkg showlabels

showlabels is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{showlabels}[2021/10/27]
```

```

2 \providecommand{\showlabelfont}{}
3 \providecommand{\showlabelsetlabel}[1]{}
4 \newcommand*\showlabels}[2][{}]{
5 \newcommand*\showlabelrefline}{}
6 \newcommand*\showlabelsinline}{}

```

File 446 **lwarp-showtags.sty**

§ 555 Package **showtags**

Pkg showtags

showtags is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{showtags}% no version is given
2 \newcommand{\thecitetag}[1]{}
```

File 447 **lwarp-shuffle.sty**

§ 556 Package **shuffle**

Pkg shuffle

(Emulates or patches code by JULIAN GILBEY AND ANTOINE LEJAY.)

shuffle is emulated for SVG math, and also emulated for MATHJAX.

The font used for shuffle may not render correctly when converted to SVG math, so a picture environment drawing is used instead.

For MATHJAX, the Unicode character is used, and for \cshuffle a \bar is added.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{shuffle}[2008/10/27]
2 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}

3 \newcommand*\LWR@shuffle@start}{%
4   \hspace*{.2em}
5   \begin{picture}(.75,0.65)
6     \setlength{\unitlength}{1em}
7     \put(0,0){\line(1,0){.75}}
8     \put(0,0){\line(0,1){.5}}
9     \put(.375,0){\line(0,1){.5}}
10    \put(.75,0){\line(0,1){.5}}
11 }
12
13 \newcommand*\LWR@shuffle@finish}{%
14   \end{picture}
15   \hspace*{.75em}
16   \hspace*{.2em}
17 }
18
19 \newcommand*\shuffle}{%
20   \LWR@shuffle@start%
21   \LWR@shuffle@finish%
22 }
23
24 \newcommand*\cshuffle}{%
25   \LWR@shuffle@start%
26   \put(.05,.65){\line(1,0){.65}}%
27   \LWR@shuffle@finish%
28 }
```

```

29 \begin{warpMathJax}
30 \CustomizeMathJax{\newcommand{\shuffle}{\mathbin{\unicode{0x29E2}}}}
31 \CustomizeMathJax{\newcommand{\cshuffle}{%
32   \mathbin{\LWRoverlaysymbols{\raise{.6ex}{-}}{\unicode{0x29E2}}}%
33 }}
34 \end{warpMathJax}

```

File 448 **lwarp-sidecap.sty**

§ 557 Package **sidecap**

(Emulates or patches code by ROLF NIEPRASCHK, HUBERT GÄSSLEIN.)

Pkg sidecap

sidecap is emulated.

for HTML output:

Discard all options for lwarp-sidecap.

```
1 \LWR@ProvidesPackageDrop{sidecap}[2003/06/06]
```

See:

<http://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment>
regarding the creation of starred environments with xparse.

```

2 \NewDocumentEnvironment{SCtable}{soo}
3 {\IfValueTF{#3}{\table[#3]}{\table}}
4 {\endtable}
5
6 \ExplSyntaxOn
7 \cs_new:cpn {SCtable*} {\SCtable*}
8 \cs_new_eq:cN {endSCtable*} \endSCtable
9 \ExplSyntaxOff
10
11
12 \NewDocumentEnvironment{SCfigure}{soo}
13 {\IfValueTF{#3}{\figure[#3]}{\figure}}
14 {\endfigure}
15
16 \ExplSyntaxOn
17 \cs_new:cpn {SCfigure*} {\SCfigure*}
18 \cs_new_eq:cN {endSCfigure*} \endSCfigure
19 \ExplSyntaxOff
20
21
22 \newenvironment*{wide}{}{}

```

File 449 **lwarp-sidenotes.sty**

§ 558 Package **sidenotes**

(Emulates or patches code by ANDY THOMAS, OLIVER SCHEBAUM.)

Pkg sidenotes

Patched for lwarp.

for HTML output:

Load the original package:

```
1 \LWR@ProvidesPackagePass{sidenotes}
```

The following patch sidenotes for use with lwarp.

An ARIA note role is not assigned since the caption is an important part of the figure.

\sidecaption

```
* [\langle entry \rangle] [\langle offset \rangle] {\langle text \rangle}
2 \RenewDocumentCommand \sidecaption {s o o m}
3 {
4   \LWR@stoppars
5   \begingroup
6   \captionsetup{style=sidecaption}%
7   \IfBooleanTF{#1}
8   { % starred
9     \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}%
10    \caption*{#4}%
11    \end{BlockClass}
12  }
13  { % unstarred
14    \IfNoValueOrEmptyTF{#2}
15    {\def\@sidenotes@sidecaption@tof{#4}}
16    {\def\@sidenotes@sidecaption@tof{#2}}
17    \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}%
18    \caption[\@sidenotes@sidecaption@tof]{#4}
19    \end{BlockClass}
20  }
21  \endgroup
22  \LWR@startpars
23 }
```

Borrowed from the lwarp version of keyfloat:

```
24 \NewDocumentEnvironment{KFLT sidenotes@marginfloat}{0}{-1.2ex} m}
25 {% start
26   \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{\marginblock}%
27   \renewcommand*{\capttype}{#2}%
28 }
29 {%
30   \endLWR@BlockClassWP%
31 }
32
33 \RenewDocumentEnvironment{marginfigure}{0}
34 {\begin{KFLT sidenotes@marginfloat}{figure}}
35 {\end{KFLT sidenotes@marginfloat}}
36
37 \RenewDocumentEnvironment{margintable}{0}
38 {\begin{KFLT sidenotes@marginfloat}{table}}
39 {\end{KFLT sidenotes@marginfloat}}
```

The following were changed by sidenotes, and now are reset back to their lwarp-supported originals:

Restoring the definition from the L^AT_EX 2_ε article.cls source:

```
40 \renewenvironment{figure*}
```

```

41         {\@dblfloat{figure}}
42         {\end@dblfloat}
43
44 \renewenvironment{table*}
45         {\@dblfloat{table}}
46         {\end@dblfloat}

```

For MATHJAX:



Note that `\sidenotes` does not support `\sidenote` inside math in print mode. Use `\sidenotemark` and `\sidenotetext` instead.

```

47 \begin{warpMathJax}
48 \providecommand{\sidenotename}{\sidenote}
49 \appto\LWR@syncnotenumbers{\LWR@synconenotenummer[LWRsidenote]{\thesidenote}}
50 \appto\LWR@syncnotenames{\LWR@synconenotename[LWRsidenote]{\sidenotename}}
51 \CustomizeMathJax{\def\LWRsidenote{1}}
52 \CustomizeMathJax{\newcommand{\sidenotemark}[1][\LWRsidenote]{{}^{\mathrm{#1}}}}
53 \end{warpMathJax}

```

The following is not defined since is not allowed inside math in print mode, and also would have to be modified to parse the optional offset argument:

```
\CustomizeMathJax{\newcommand{\sidenote}[2][\LWRsidenote]{{}^{\mathrm{#1}}}}
```

File 450 **lwarp-simplebnf.sty**

§ 559 Package **simplebnf**

(Emulates or patches code by JAY LEE.)

Pkg simplebnf

simplebnf is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{simplebnf}[2020/09/01]

The entire object is placed inside a `lateximage` whose alt text is the L^AT_EX source BNF expression.

```

2 \ExplSyntaxOn
3
4 \RenewDocumentEnvironment { bnfgrammar } { +b }
5 {
6   %% \l__input_seq is a list of term definitions.
7   \regex_split:nnN { ; ; } { #1 } \l__input_seq
8   \begin{center}
9     \begin{lateximage}[#1]%   lwarp
10      \tl_set:Nn \l__table_tl
11        {
12          \begin{tabular}{lcll}
13          }
14      \bool_set_true:N \l_tmp_first_term % Is this the first term in this grammar?
15      \seq_map_inline:Nn \l__input_seq
16        {
17          %% \l__term_seq - (term, rhses)...
18          %% \l__term_tl - term
19          %% \l__keypairs_tl - rhses

```

```

20     \regex_split:nnN { ::= } { ##1 } \l__term_seq
21     \seq_pop_left:NN \l__term_seq \l__term_tl
22     \seq_pop_left:NN \l__term_seq \l__keypairs_tl
23
24     \regex_replace_once:nnN { ^\s+ } {} \l__term_tl
25
26     \bool_if:NTF \l_tmp_first_term
27     {
28         \bool_set_false:N \l_tmp_first_term
29     }
30     {
31         \tl_put_right:Nn \l__table_tl { \ }
32     }
33     \tl_put_right:Nx \l__table_tl
34     {
35         \bnfexpr { \l__term_tl } & \g__simplebnf_defeq_tl &
36     }
37     %\l__keypairs_seq - (rhs:annot | rhs)...
38     \seq_set_split:NnV \l__keypairs_seq { | } \l__keypairs_tl
39
40     \bool_set_true:N \l__first_rhs
41     \seq_map_function:NN \l__keypairs_seq \simplebnf_typeset_rhs:n
42 }
43
44 \tl_put_right:Nn \l__table_tl { \end{tabular} }
45 \tl_use:N \l__table_tl
46 \end{lateximage}%     lwarp
47 \end{center}
48 }
49 { }
50
51 \ExplSyntaxOff

```

File 451 **lwarp-SIunits.sty**

§ 560 Package **SIunits**

(Emulates or patches code by MARCEL HELDOORN.)

Pkg SIunits

SIunits is patched for use by lwarp.

For SVG math, it is recommended to use `\unit` where possible, which combines the entire expression into a single `lateximage`, and adds the `alt` tag containing the L^AT_EX code, allowing for copy/paste. When units are used outside of the `\unit` macro, each unit macro will have its own `lateximage`, and each will have the `alt` tag set according to `\MathImageAltText`, which defaults to `(math image)`.

For MATHJAX, individual units used in text will appear as SVG images, since `\ensuremath` is used in the original definitions, and `\ensuremath` often has expressions which do not work well in MATHJAX, so it is always forced to an SVG image. If, however, `\unit` is used, the result is expressed with MATHJAX instead of an SVG image.

for HTML output: `1 \LWR@ProvidesPackagePass{SIunits}[2007/12/02]`

Patched for copy/paste with the HTML `alt` tag:

```

2 \ifbool{mathjax}{
3   \DeclareRobustCommand{\LWR@HTML@unit}[2]{%
4     \LWR@subsingledollar*% lwarp
5     {% alt tag
6       \textbackslash{}unit%
7       \{\LWR@HTMLsanitizeddetokenized{\detokenize{#1}}\}%
8       \{\LWR@HTMLsanitizeddetokenized{\detokenize{#2}}\}% extra space
9     }%
10    {SIunits}% add'l hashing
11    {%
12      #1\,{#2}%
13    }% contents
14  }
15 }{% not MathJax
16   \DeclareRobustCommand{\LWR@HTML@unit}[2]{%
17     \@inunitcommandtrue% original
18     \LWR@subsingledollar*% lwarp
19     {% alt tag
20       \textbackslash{}unit\{\LWR@HTMLsanitizeddetokenized{\detokenize{#1}}\}%
21       \{\LWR@HTMLsanitizeddetokenized{\detokenize{#2}}\}% extra space
22     }%
23     {SIunits}% add'l hashing
24     {%
25       \LWR@origensuredmath{% lwarp modification
26         \SI@fstyle{%
27           {#1}\@qsk\period@active{#2}%
28         }% original
29       }%
30     }% contents
31     \@inunitcommandfalse% original
32   }
33 }{% not MathJax
34 \LWR@formatted{unit}

```

FOR MATHJAX:

```

35 \begin{warpMathJax}
36 \LWR@infoprocessingmathjax{SIunits}
37
38 \CustomizeMathJax{\newcommand{\one}{}{}}
39 \CustomizeMathJax{\newcommand{\meter}{\metre}}
40 \CustomizeMathJax{\newcommand{\deka}{\deca}}
41 \CustomizeMathJax{\newcommand{\dekad}{\decad}}
42 \CustomizeMathJax{\newcommand{\per}{/}}
43 \CustomizeMathJax{\newcommand{\usk}{\;}}
44 \CustomizeMathJax{\newcommand{\unit}[2]{#1\,{#2}}}
45 \CustomizeMathJax{\newcommand{\power}[2]{#1^{#2}}}
46
47 \AtBeginDocument{%
48   \if@redefsquare
49     \CustomizeMathJax{\renewcommand{\square}[1]{\power{#1}{2}}}
50   \else
51     \if@defsquaren
52       \CustomizeMathJax{\newcommand{\square}[1]{\power{#1}{2}}}
53     \else
54       \CustomizeMathJax{\renewcommand{\square}[1]{\power{#1}{2}}}
55     \fi %\if@defsquaren
56   \fi %\if@redefsquare
57 } %\AtBeginDocument
58

```

```

59 \CustomizeMathJax{\newcommand{\squared}{^{\{2\}}}
60 \CustomizeMathJax{\newcommand{\cubic}[1]{\power{\#1}{3}}}
61 \CustomizeMathJax{\newcommand{\cubed}{^{\{3\}}}
62 \CustomizeMathJax{\newcommand{\fourth}[1]{\power{\#1}{4}}}
63 \CustomizeMathJax{\newcommand{\reciprocal}[1]{\power{\#1}{-1}}}
64 \CustomizeMathJax{\newcommand{\rp}{\reciprocal}}
65 \CustomizeMathJax{\newcommand{\rpsquare}[1]{\power{\#1}{-2}}}
66 \CustomizeMathJax{\newcommand{\rpsquared}{^{\{-2\}}}
67 \CustomizeMathJax{\newcommand{\rpcubic}[1]{\power{\#1}{-3}}}
68 \CustomizeMathJax{\newcommand{\rpcubed}{^{\{-3\}}}
69 \CustomizeMathJax{\newcommand{\rpfourth}[1]{\power{\#1}{-4}}}
70 \CustomizeMathJax{\newcommand{\yocto}{\mathrm{y}}}
71 \CustomizeMathJax{\newcommand{\zepto}{\mathrm{z}}}
72 \CustomizeMathJax{\newcommand{\atto}{\mathrm{a}}}
73 \CustomizeMathJax{\newcommand{\femto}{\mathrm{f}}}
74 \CustomizeMathJax{\newcommand{\pico}{\mathrm{p}}}
75 \CustomizeMathJax{\newcommand{\nano}{\mathrm{n}}}
76 \CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
77 \CustomizeMathJax{\newcommand{\milli}{\mathrm{m}}}
78 \CustomizeMathJax{\newcommand{\centi}{\mathrm{c}}}
79 \CustomizeMathJax{\newcommand{\deci}{\mathrm{d}}}
80 \CustomizeMathJax{\newcommand{\deca}{\mathrm{da}}}
81 \CustomizeMathJax{\newcommand{\hecto}{\mathrm{h}}}
82 \CustomizeMathJax{\newcommand{\kilo}{\mathrm{k}}}
83 \CustomizeMathJax{\newcommand{\mega}{\mathrm{M}}}
84 \CustomizeMathJax{\newcommand{\giga}{\mathrm{G}}}
85 \CustomizeMathJax{\newcommand{\tera}{\mathrm{T}}}
86 \CustomizeMathJax{\newcommand{\peta}{\mathrm{P}}}
87 \CustomizeMathJax{\newcommand{\exa}{\mathrm{E}}}
88 \CustomizeMathJax{\newcommand{\zetta}{\mathrm{Z}}}
89 \CustomizeMathJax{\newcommand{\yotta}{\mathrm{Y}}}
90 \CustomizeMathJax{\newcommand{\yoctod}{\power{10}{-24}}}
91 \CustomizeMathJax{\newcommand{\zeptod}{\power{10}{-21}}}
92 \CustomizeMathJax{\newcommand{\attod}{\power{10}{-18}}}
93 \CustomizeMathJax{\newcommand{\femtod}{\power{10}{-15}}}
94 \CustomizeMathJax{\newcommand{\picod}{\power{10}{-12}}}
95 \CustomizeMathJax{\newcommand{\nanod}{\power{10}{-9}}}
96 \CustomizeMathJax{\newcommand{\microd}{\power{10}{-6}}}
97 \CustomizeMathJax{\newcommand{\millid}{\power{10}{-3}}}
98 \CustomizeMathJax{\newcommand{\centid}{\power{10}{-2}}}
99 \CustomizeMathJax{\newcommand{\decid}{\power{10}{-1}}}
100 \CustomizeMathJax{\newcommand{\decad}{\power{10}{1}}}
101 \CustomizeMathJax{\newcommand{\hectod}{\power{10}{2}}}
102 \CustomizeMathJax{\newcommand{\kilod}{\power{10}{3}}}
103 \CustomizeMathJax{\newcommand{\megad}{\power{10}{6}}}
104 \CustomizeMathJax{\newcommand{\gigad}{\power{10}{9}}}
105 \CustomizeMathJax{\newcommand{\terad}{\power{10}{12}}}
106 \CustomizeMathJax{\newcommand{\petad}{\power{10}{15}}}
107 \CustomizeMathJax{\newcommand{\exad}{\power{10}{18}}}
108 \CustomizeMathJax{\newcommand{\zettad}{\power{10}{21}}}
109 \CustomizeMathJax{\newcommand{\yottad}{\power{10}{24}}}
110 \CustomizeMathJax{\newcommand{\gram}{\mathrm{g}}}
111 \CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
112 \CustomizeMathJax{\newcommand{\kilogram}{\kilo\gram}}
113 \CustomizeMathJax{\newcommand{\second}{\mathrm{s}}}
114 \CustomizeMathJax{\newcommand{\ampere}{\mathrm{A}}}
115 \CustomizeMathJax{\newcommand{\kelvin}{\mathrm{K}}}
116 \CustomizeMathJax{\newcommand{\mole}{\mathrm{mol}}}
117 \CustomizeMathJax{\newcommand{\candela}{\mathrm{cd}}}
118 \CustomizeMathJax{\newcommand{\radian}{\mathrm{rad}}}

```

```

119 \CustomizeMathJax{\newcommand{\steradian}{\mathrm{sr}}}
120 \CustomizeMathJax{\newcommand{\hertz}{\mathrm{Hz}}}
121 \CustomizeMathJax{\newcommand{\newton}{\mathrm{N}}}
122 \CustomizeMathJax{\newcommand{\pascal}{\mathrm{Pa}}}
123 \CustomizeMathJax{\newcommand{\joule}{\mathrm{J}}}
124 \CustomizeMathJax{\newcommand{\watt}{\mathrm{W}}}
125 \CustomizeMathJax{\newcommand{\coulomb}{\mathrm{C}}}
126 \CustomizeMathJax{\newcommand{\volt}{\mathrm{V}}}
127 \CustomizeMathJax{\newcommand{\farad}{\mathrm{F}}}
128 \CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
129 \CustomizeMathJax{\newcommand{\siemens}{\mathrm{S}}}
130 \CustomizeMathJax{\newcommand{\weber}{\mathrm{Wb}}}
131 \CustomizeMathJax{\newcommand{\tesla}{\mathrm{T}}}
132 \CustomizeMathJax{\newcommand{\henry}{\mathrm{H}}}
133 \CustomizeMathJax{\newcommand{\degreecelsius}{\mathrm{\unicode{x2103}}}}
134 \CustomizeMathJax{\newcommand{\celsius}{\degreecelsius}}
135 \CustomizeMathJax{\newcommand{\lumen}{\mathrm{lm}}}
136 \CustomizeMathJax{\newcommand{\lux}{\mathrm{lx}}}
137 \CustomizeMathJax{\newcommand{\becquerel}{\mathrm{Bq}}}
138 \CustomizeMathJax{\newcommand{\sievert}{\mathrm{Sv}}}
139 \CustomizeMathJax{\newcommand{\katal}{\mathrm{kat}}}
140
141 \ifdef{\radianbase}{
142 \CustomizeMathJax{\newcommand{\radianbase}%
143     {\metre\usk\reciprocal\metre}}
144 \CustomizeMathJax{\newcommand{\steradianbase}%
145     {\squaremetre\usk\rpsquare\metre}}
146 \CustomizeMathJax{\newcommand{\hertzbase}%
147     {\reciprocal\second}}
148 \CustomizeMathJax{\newcommand{\newtonbase}%
149     {\metre\usk\kilogram\usk\second\rpsquared}}
150 \CustomizeMathJax{\newcommand{\pascalbase}%
151     {\reciprocal\metre\usk\kilogram\usk\second\rpsquared}}
152 \CustomizeMathJax{\newcommand{\joulebase}%
153     {\squaremetre\usk\kilogram\usk\second\rpsquared}}
154 \CustomizeMathJax{\newcommand{\wattbase}%
155     {\squaremetre\usk\kilogram\usk\rpcubic\second}}
156 \CustomizeMathJax{\newcommand{\coulombbase}%
157     {\ampere\usk\second}}
158 \CustomizeMathJax{\newcommand{\voltbase}%
159     {\squaremetre\usk\kilogram\usk\rpcubic\second\usk\reciprocal\ampere}}
160 \CustomizeMathJax{\newcommand{\faradbase}%
161     {\rpsquare\metre\usk\reciprocal\kilogram\usk\fourth\second\usk\ampere\squared}}
162 \CustomizeMathJax{\newcommand{\ohmbase}%
163     {\squaremetre\usk\kilogram\usk\rpcubic\second\usk\rpsquare\ampere}}
164 \CustomizeMathJax{\newcommand{\siemensbase}%
165     {\rpsquare\metre\usk\reciprocal\kilogram\usk\cubic\second\usk\ampere\squared}}
166 \CustomizeMathJax{\newcommand{\weberbase}%
167     {\squaremetre\usk\kilogram\usk\second\rpsquared\usk\reciprocal\ampere}}
168 \CustomizeMathJax{\newcommand{\teslabase}%
169     {\kilogram\usk\second\rpsquared\usk\reciprocal\ampere}}
170 \CustomizeMathJax{\newcommand{\henrybase}%
171     {\squaremetre\usk\kilogram\usk\second\rpsquared\usk\rpsquare\ampere}}
172 \CustomizeMathJax{\newcommand{\celsiusbase}%
173     {\kelvin}}
174 \CustomizeMathJax{\newcommand{\lumenbase}%
175     {\candela\usk\squaremetre\usk\rpsquare\metre}}
176 \CustomizeMathJax{\newcommand{\luxbase}%
177     {\candela\usk\squaremetre\usk\rpfourth\metre}}
178 \CustomizeMathJax{\newcommand{\becquerelbase}%

```

```
179     {\hertzbase}}
180 \CustomizeMathJax{\newcommand{\graybase}%
181     {\squaremetre\usk\second\rpsquared}}
182 \CustomizeMathJax{\newcommand{\sievertbase}%
183     {\graybase}}
184 \CustomizeMathJax{\newcommand{\katalbase}%
185     {\rp\second\usk\mole }}
186 }{}
187
188 \ifdef{\derradian}{
189 \CustomizeMathJax{\newcommand{\derradian}%
190     {\metre\usk\reciprocal\metre}}
191 \CustomizeMathJax{\newcommand{\dersteradian}%
192     {\squaremetre\usk\rpsquare\metre}}
193 \CustomizeMathJax{\newcommand{\derhertz}%
194     {\reciprocal\second}}
195 \CustomizeMathJax{\newcommand{\dernewton}%
196     {\metre\usk\kilogram\usk\second\rpsquared}}
197 \CustomizeMathJax{\newcommand{\derpascal}%
198     {\newton\usk\rpsquare\metre}}
199 \CustomizeMathJax{\newcommand{\derjoule}%
200     {\newton\usk\metre}}
201 \CustomizeMathJax{\newcommand{\derwatt}%
202     {\joule\usk\reciprocal\second}}
203 \CustomizeMathJax{\newcommand{\dercoulomb}%
204     {\ampere\usk\second}}
205 \CustomizeMathJax{\newcommand{\dervolt}%
206     {\watt\usk\reciprocal\ampere}}
207 \CustomizeMathJax{\newcommand{\derfarad}%
208     {\coulomb\usk\reciprocal\volt}}
209 \CustomizeMathJax{\newcommand{\derohm}%
210     {\volt\usk\reciprocal\ampere}}
211 \CustomizeMathJax{\newcommand{\dersiemens}%
212     {\ampere\usk\reciprocal\volt}}
213 \CustomizeMathJax{\newcommand{\derweber}%
214     {\squaremetre\usk\kilogram\usk\second\rpsquared\usk\reciprocal\ampere}}
215 \CustomizeMathJax{\newcommand{\dertesla}%
216     {\weber\usk\rpsquare\metre}}
217 \CustomizeMathJax{\newcommand{\derhenry}%
218     {\weber\usk\reciprocal\ampere}}
219 \CustomizeMathJax{\newcommand{\dercelsius}%
220     {\kelvin}}
221 \CustomizeMathJax{\newcommand{\derlumen}%
222     {\candela\usk\steradian}}
223 \CustomizeMathJax{\newcommand{\derlux}%
224     {\lumen\usk\rpsquare\metre}}
225 \CustomizeMathJax{\newcommand{\derbecquerel}%
226     {\derhertz}}
227 \CustomizeMathJax{\newcommand{\dergray}%
228     {\joule\usk\reciprocal\kilogram}}
229 \CustomizeMathJax{\newcommand{\dersievert}%
230     {\dergray}}
231 \CustomizeMathJax{\newcommand{\derkatal}%
232     {\katalbase}}
233 }{}
234
235 \CustomizeMathJax{\newcommand{\minute}{\mathrm{min}}}
236 \CustomizeMathJax{\newcommand{\hour}{\mathrm{h}}}
237 \CustomizeMathJax{\newcommand{\dday}{\mathrm{d}}}
238 \CustomizeMathJax{\newcommand{\degree}{\mathrm{^\circ}}}
```

```

239 \CustomizeMathJax{\newcommand{\paminute}{^\prime}}
240 \CustomizeMathJax{\newcommand{\arcminute}{^\prime}}
241 \CustomizeMathJax{\newcommand{\pasecond}{^\prime\prime}}
242 \CustomizeMathJax{\newcommand{\arcsecond}{^\prime\prime}}
243 \CustomizeMathJax{\newcommand{\ton}{\mathrm{t}}}
244 \CustomizeMathJax{\newcommand{\tonne}{\mathrm{t}}}
245 \CustomizeMathJax{\newcommand{\liter}{\mathrm{L}}}
246 \CustomizeMathJax{\newcommand{\litre}{\mathrm{L}}}
247 \CustomizeMathJax{\newcommand{\neper}{\mathrm{Np}}}
248 \CustomizeMathJax{\newcommand{\bel}{\mathrm{B}}}
249 \CustomizeMathJax{\newcommand{\curie}{\mathrm{Ci}}}
250 \CustomizeMathJax{\newcommand{\rad}{\mathrm{rad}}}
251 \CustomizeMathJax{\newcommand{\arad}{\mathrm{rd}}}
252 \CustomizeMathJax{\newcommand{\rem}{\mathrm{rem}}}
253 \CustomizeMathJax{\newcommand{\roentgen}{\mathrm{R}}}
254 \CustomizeMathJax{\newcommand{\electronvolt}{\mathrm{\mathrm{eV}}}}
255 \CustomizeMathJax{\newcommand{\atomicmass}{\mathrm{u}}}
256 \CustomizeMathJax{\newcommand{\atomicmassunit}{\mathrm{u}}}
257 \CustomizeMathJax{\newcommand{\dalton}{\mathrm{Da}}}
258 \CustomizeMathJax{\newcommand{\are}{\mathrm{a}}}
259 \CustomizeMathJax{\newcommand{\hectare}{\mathrm{\hecto\are}}}
260 \CustomizeMathJax{\newcommand{\barn}{\mathrm{b}}}
261 \CustomizeMathJax{\newcommand{\bbar}{\mathrm{bar}}}
262 \CustomizeMathJax{\newcommand{\gal}{\mathrm{Gal}}}
263 \CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\unicode{x212B}}}}
264 \CustomizeMathJax{\newcommand{\rperminute}{\mathrm{r}\per\minute}}
265 \CustomizeMathJax{\newcommand{\rpersecond}{\mathrm{r}\per\second}}
266 \CustomizeMathJax{\newcommand{\squaremetre}{\power{\metre}{2}}}
267 \CustomizeMathJax{\newcommand{\cubicmetre}{\cubic\metre}}
268 \CustomizeMathJax{\newcommand{\graypersecond}{\gray\per\second}}
269 \CustomizeMathJax{\newcommand{\graypersecondnp}{\gray\usk\reciprocal\second}}
270 \CustomizeMathJax{\newcommand{\metrepersecond}{\metre\per\second\squared}}
271 \CustomizeMathJax{\newcommand{\metrepersecondnp}{\metre\usk\second\rpsquared}}
272 \CustomizeMathJax{\newcommand{\joulepermole}{\joule\per\mole}}
273 \CustomizeMathJax{\newcommand{\joulepermolenp}{\joule\usk\reciprocal\mole}}
274 \CustomizeMathJax{\newcommand{\molepercubicmetre}{\mole\per\cubic\metre}}
275 \CustomizeMathJax{\newcommand{\molepercubicmetrenp}{\mole\usk\rpcubic\metre}}
276 \CustomizeMathJax{\newcommand{\radianpersquaresecond}{\radian\per\second\squared}}
277 \CustomizeMathJax{\newcommand{\radianpersquaresecondnp}{\radian\usk\second\rpsquared}}
278 \CustomizeMathJax{\newcommand{\kilogramsquaremetrepersecond}{%
279   \kilogram\usk\squaremetre\per\second%
280 }}
281 \CustomizeMathJax{\newcommand{\kilogramsquaremetrepersecondnp}{%
282   \kilogram\usk\squaremetre\usk\reciprocal\second%
283 }}
284 \CustomizeMathJax{\newcommand{\radianpersecond}{\radian\per\second}}
285 \CustomizeMathJax{\newcommand{\radianpersecondnp}{\radian\usk\reciprocal\second}}
286 \CustomizeMathJax{\newcommand{\squaremetrepercubicmetre}{\squaremetre\per\cubic\metre}}
287 \CustomizeMathJax{\newcommand{\squaremetrepercubicmetrenp}{%
288   \squaremetre\usk\rpcubic\metre%
289 }}
290 \CustomizeMathJax{\newcommand{\katalpercubicmetre}{\katal\per\cubic\metre}}
291 \CustomizeMathJax{\newcommand{\katalpercubicmetrenp}{\katal\usk\rpcubic\metre}}
292 \CustomizeMathJax{\newcommand{\coulombpermole}{\coulomb\per\mole}}
293 \CustomizeMathJax{\newcommand{\coulombpermolnp}{\coulomb\usk\reciprocal\mole}}
294 \CustomizeMathJax{\newcommand{\amperepersquaremetre}{\ampere\per\squaremetre}}
295 \CustomizeMathJax{\newcommand{\amperepersquaremetrenp}{\ampere\usk\rpsquare\metre}}
296 \CustomizeMathJax{\newcommand{\kilogrampercubicmetre}{\kilogram\per\cubic\metre}}
297 \CustomizeMathJax{\newcommand{\kilogrampercubicmetrenp}{\kilogram\usk\rpcubic\metre}}
298 \CustomizeMathJax{\newcommand{\squaremetrepernewtonsecond}{%

```

```

299   \squaremetre\per\newton\usk\second%
300 }}
301 \CustomizeMathJax{\newcommand{\squaremetrepernewtonsecondnp}{%
302   \squaremetre\usk\reciprocal\newton\usk\reciprocal\second%
303 }}
304 \CustomizeMathJax{\newcommand{\pascalsecond}{\pascal\usk\second}}
305 \CustomizeMathJax{\newcommand{\coulombpercubicmetre}{\coulomb\per\cubic\metre}}
306 \CustomizeMathJax{\newcommand{\coulombpercubicmetrenp}{\coulomb\usk\rpcubic\metre}}
307 \CustomizeMathJax{\newcommand{\amperepermetresecond}{\ampere\usk\metre\usk\second}}
308 \CustomizeMathJax{\newcommand{\voltpermetre}{\volt\per\metre}}
309 \CustomizeMathJax{\newcommand{\voltpermetrenp}{\volt\usk\reciprocal\metre}}
310 \CustomizeMathJax{\newcommand{\coulombpersquaremetre}{\coulomb\per\squaremetre}}
311 \CustomizeMathJax{\newcommand{\coulombpersquaremetrenp}{\coulomb\usk\rpsquare\metre}}
312 \CustomizeMathJax{\newcommand{\faradpermetre}{\farad\per\metre}}
313 \CustomizeMathJax{\newcommand{\faradpermetrenp}{\farad\usk\reciprocal\metre}}
314 \CustomizeMathJax{\newcommand{\ohmmetre}{\ohm\usk\metre}}
315 \CustomizeMathJax{\newcommand{\kilowatthour}{\kilo\watt\hour}}
316 \CustomizeMathJax{\newcommand{\wattpersquaremetre}{\watt\per\squaremetre}}
317 \CustomizeMathJax{\newcommand{\wattpersquaremetrenp}{\watt\usk\rpsquare\metre}}
318 \CustomizeMathJax{\newcommand{\joulepersquaremetre}{\joule\per\squaremetre}}
319 \CustomizeMathJax{\newcommand{\joulepersquaremetrenp}{\joule\usk\rpsquare\metre}}
320 \CustomizeMathJax{\newcommand{\newtonpercubicmetre}{\newton\per\cubic\metre}}
321 \CustomizeMathJax{\newcommand{\newtonpercubicmetrenp}{\newton\usk\rpcubic\metre}}
322 \CustomizeMathJax{\newcommand{\newtonperkilogram}{\newton\per\kilogram}}
323 \CustomizeMathJax{\newcommand{\newtonperkilogramnp}{\newton\usk\reciprocal\kilogram}}
324 \CustomizeMathJax{\newcommand{\jouleperkelvin}{\joule\per\kelvin}}
325 \CustomizeMathJax{\newcommand{\jouleperkelvinnp}{\joule\usk\reciprocal\kelvin}}
326 \CustomizeMathJax{\newcommand{\jouleperkilogram}{\joule\per\kilogram}}
327 \CustomizeMathJax{\newcommand{\jouleperkilogramnp}{\joule\usk\reciprocal\kilogram}}
328 \CustomizeMathJax{\newcommand{\coulombperkilogram}{\coulomb\per\kilogram}}
329 \CustomizeMathJax{\newcommand{\coulombperkilogramnp}{\coulomb\usk\reciprocal\kilogram}}
330 \CustomizeMathJax{\newcommand{\squaremetrepersecond}{\squaremetre\per\second}}
331 \CustomizeMathJax{\newcommand{\squaremetrepersecondnp}{%
332   \squaremetre\usk\reciprocal\second%
333 }}
334 \CustomizeMathJax{\newcommand{\squaremetrepersquaresecond}{%
335   \squaremetre\per\second\squared%
336 }}
337 \CustomizeMathJax{\newcommand{\squaremetrepersquaresecondnp}{%
338   \squaremetre\usk\second\rpsquared%
339 }}
340 \CustomizeMathJax{\newcommand{\kilogrammetrepersecond}{%
341   \kilogram\usk\metre\per\second%
342 }}
343 \CustomizeMathJax{\newcommand{\kilogrammetrepersecondnp}{%
344   \kilogram\usk\metre\usk\reciprocal\second%
345 }}
346 \CustomizeMathJax{\newcommand{\candelapersquaremetre}{\candela\per\squaremetre}}
347 \CustomizeMathJax{\newcommand{\candelapersquaremetrenp}{\candela\usk\rpsquare\metre}}
348 \CustomizeMathJax{\newcommand{\amperepermetre}{\ampere\per\metre}}
349 \CustomizeMathJax{\newcommand{\amperepermetrenp}{\ampere\usk\reciprocal\metre}}
350 \CustomizeMathJax{\newcommand{\joulepertesla}{\joule\per\tesla}}
351 \CustomizeMathJax{\newcommand{\jouleperteslanp}{\joule\usk\reciprocal\tesla}}
352 \CustomizeMathJax{\newcommand{\henrypermetre}{\henry\per\metre}}
353 \CustomizeMathJax{\newcommand{\henrypermetrenp}{\henry\usk\reciprocal\metre}}
354 \CustomizeMathJax{\newcommand{\kilogrampersecond}{\kilogram\per\second}}
355 \CustomizeMathJax{\newcommand{\kilogrampersecondnp}{\kilogram\usk\reciprocal\second}}
356 \CustomizeMathJax{\newcommand{\kilogrampersquaremetresecond}{%
357   \kilogram\per\squaremetre\usk\second%
358 }}

```

```
359 \CustomizeMathJax{\newcommand{\kilogrampersquaremetresecondnp}{%
360   \kilogram\usk\rpsquare\metre\usk\reciprocal\second%
361 }}
362 \CustomizeMathJax{\newcommand{\kilogrampersquaremetre}{\kilogram\per\squaremetre}}
363 \CustomizeMathJax{\newcommand{\kilogrampersquaremetrenp}{\kilogram\usk\rpsquare\metre}}
364 \CustomizeMathJax{\newcommand{\kilogrampermetre}{\kilogram\per\metre}}
365 \CustomizeMathJax{\newcommand{\kilogrampermetrenp}{\kilogram\usk\reciprocal\metre}}
366 \CustomizeMathJax{\newcommand{\joulepermolekelvin}{\joule\per\mole\usk\kelvin}}
367 \CustomizeMathJax{\newcommand{\joulepermolekelvinnp}{%
368   \joule\usk\reciprocal\mole\usk\reciprocal\kelvin%
369 }}
370 \CustomizeMathJax{\newcommand{\kilogramperkilomole}{\kilogram\per\kilo\mole}}
371 \CustomizeMathJax{\newcommand{\kilogramperkilomolenp}{%
372   \kilogram\usk\kilo\reciprocal\mole%
373 }}
374 \CustomizeMathJax{\newcommand{\kilogramsquaremetre}{\kilogram\usk\squaremetre}}
375 \CustomizeMathJax{\newcommand{\kilogramsquaremetrenp}{\kilogramsquaremetre}}
376 \CustomizeMathJax{\newcommand{\kilogrammetrepersquaresecond}{%
377   \kilogram\usk\metre\per\second\squared%
378 }}
379 \CustomizeMathJax{\newcommand{\kilogrammetrepersquaresecondnp}{%
380   \kilogram\usk\metre\usk\second\rpsquared%
381 }}
382 \CustomizeMathJax{\newcommand{\newtonpersquaremetre}{\newton\per\squaremetre}}
383 \CustomizeMathJax{\newcommand{\newtonpersquaremetrenp}{\newton\usk\rpsquare\metre}}
384 \CustomizeMathJax{\newcommand{\persquaremetresecond}{1\per\squaremetre\usk\second}}
385 \CustomizeMathJax{\newcommand{\persquaremetresecondnp}{%
386   \rpsquare\metre\usk\reciprocal\second%
387 }}
388 \CustomizeMathJax{\newcommand{\wattperkilogram}{\watt\per\kilogram}}
389 \CustomizeMathJax{\newcommand{\wattperkilogramnp}{\watt\usk\reciprocal\kilogram}}
390 \CustomizeMathJax{\newcommand{\wattpercubicmetre}{\watt\per\cubic\metre}}
391 \CustomizeMathJax{\newcommand{\wattpercubicmetrenp}{\watt\usk\rpcubic\metre}}
392 \CustomizeMathJax{\newcommand{\wattpersquaremetresteradian}{%
393   \watt\per\squaremetre\usk\steradian%
394 }}
395 \CustomizeMathJax{\newcommand{\wattpersquaremetresteradiannp}{%
396   \watt\usk\rpsquare\metre\usk\rp\steradian%
397 }}
398 \CustomizeMathJax{\newcommand{\jouleperkilogramkelvin}{\joule\per\kilogram\usk\kelvin}}
399 \CustomizeMathJax{\newcommand{\jouleperkilogramkelvinnp}{%
400   \joule\usk\reciprocal\kilogram\usk\reciprocal\kelvin%
401 }}
402 \CustomizeMathJax{\newcommand{\squaremetreperkilogram}{\squaremetre\per\kilogram}}
403 \CustomizeMathJax{\newcommand{\rsquaremetreperkilogram}{%
404   \squaremetre\usk\reciprocal\kilogram%
405 }}
406 \CustomizeMathJax{\newcommand{\cubicmetreperkilogram}{\cubic\metre\per\kilogram}}
407 \CustomizeMathJax{\newcommand{\rpcubicmetreperkilogram}{%
408   \cubic\metre\usk\reciprocal\kilogram%
409 }}
410 \CustomizeMathJax{\newcommand{\newtonpermetre}{\newton\per\metre}}
411 \CustomizeMathJax{\newcommand{\newtonpermetrenp}{\newton\usk\reciprocal\metre}}
412 \CustomizeMathJax{\newcommand{\Celsius}{\unicode{x2103}}}
413 \CustomizeMathJax{\newcommand{\wattpermetrekelvin}{\watt\per\metre\usk\kelvin}}
414 \CustomizeMathJax{\newcommand{\wattpermetrekelvinnp}{%
415   \watt\usk\reciprocal\metre\usk\reciprocal\kelvin%
416 }}
417 \CustomizeMathJax{\newcommand{\newtonmetre}{\newton\usk\metre}}
418 \CustomizeMathJax{\newcommand{\newtonmetrenp}{\newtonmetre}}}
```

```

419 \CustomizeMathJax{\newcommand{\squaremetrepercubicsecond}{%
420   \squaremetre\per\cubic\second%
421 }}
422 \CustomizeMathJax{\newcommand{\squaremetrepercubicsecondnp}{%
423   \squaremetre\usk\rpcubic\second%
424 }}
425 \CustomizeMathJax{\newcommand{\metrepersecond}{\metre\per\second}}
426 \CustomizeMathJax{\newcommand{\metrepersecondnp}{\metre\usk\reciprocal\second}}
427 \CustomizeMathJax{\newcommand{\joulepercubicmetre}{\joule\per\cubicmetre}}
428 \CustomizeMathJax{\newcommand{\joulepercubicmetrenp}{\joule\usk\rpcubic\metre}}
429 \CustomizeMathJax{\newcommand{\kilogrampercubicmetrecoulomb}{%
430   \kilogram\per\cubic\metre\usk\coulomb%
431 }}
432 \CustomizeMathJax{\newcommand{\kilogrampercubicmetrecoulombnp}{%
433   \kilogram\usk\rpcubic\metre\usk\reciprocal\coulomb%
434 }}
435 \CustomizeMathJax{\newcommand{\cubicmetrepersecond}{\cubicmetre\per\second}}
436 \CustomizeMathJax{\newcommand{\rpcubicmetrepersecond}{\cubicmetre\usk\reciprocal\second}}
437 \CustomizeMathJax{\newcommand{\kilogrampersecondcubicmetre}{%
438   \kilogram\per\second\usk\cubicmetre%
439 }}
440 \CustomizeMathJax{\newcommand{\kilogrampersecondcubicmetrenp}{%
441   \kilogram\usk\reciprocal\second\usk\rpcubic\metre%
442 }}
443 \end{warpMathJax}

```

File 452 **lwarp-siunitx.sty**

§ 561 Package **siunitx**

(Emulates or patches code by JOSEPH WRIGHT.)

Pkg siunitx

siunitx is patched for use by lwarp, and is emulated for MATHJAX.

for HTML output:

```

1 \providecommand\DeclareRelease[3]{}
2 \providecommand\DeclareCurrentRelease[2]{}
3
4 \DeclareRelease{2}{2010-05-23}{lwarp-siunitx-v2.sty}
5 \DeclareRelease{v2}{2010-05-23}{lwarp-siunitx-v2.sty}
6 \DeclareCurrentRelease{}{2021-05-17}
7
8 \RequirePackage{xcolor}% for \convertcolorspec
9
10 \LWR@ProvidesPackagePass{siunitx}[2022-02-15]
11
12 \ExplSyntaxOn

13 \cs_set_protected:Npn \siunitx_number_format:nN #1#2
14 {
15   \group_begin:
16     \bool_if:NTF \l_siunitx_number_parse_bool
17       {
18         \siunitx_number_parse:nN {#1} \l__siunitx_number_parsed_tl
19         \siunitx_number_process:NN \l__siunitx_number_parsed_tl \l__siunitx_number_parsed_tl
20         \tl_set:Nx \l__siunitx_number_outputted_tl
21           { \siunitx_number_output:N \l__siunitx_number_parsed_tl }
22       }

```

```

23     {
24     \tl_set:Nn \l__siunitx_number_outputted_tl
25     {
26         \LWR@subsingledollar{%           lwarp
27         \textbackslash( % space
28         \LWR@HTMLsanitizedetokenized{%
29         \detokenize{#1}%
30         } \textbackslash)%           lwarp
31     }%
32     {siunitx unparsed}%
33     {\ensuremath{#1}}%           lwarp
34     }
35     }
36     \exp_args:NNNV \group_end:
37     \tl_set:Nn #2 \l__siunitx_number_outputted_tl
38     }

39 \cs_set_protected:Npn \__siunitx_compound_unparsed:n #1
40 {
41     \tl_if_blank:nF {#1}
42     { \seq_put_right:Nn \l__siunitx_compound_tmp_seq
43     {
44         \LWR@subsingledollar{%           lwarp
45         \textbackslash( % space
46         \LWR@HTMLsanitizedetokenized{%
47         \detokenize{#1}%
48         } \textbackslash)%           lwarp
49     }%
50     {siunitx unparsed}%
51     {\ensuremath{#1}}%           lwarp
52     }
53     }
54     }

```

If not in a lateximage, always use text mode. Ignore current text font if resetting text family, series, and shape.

```

55 \cs_set_protected:Npn \__siunitx_print_aux:nn #1#2
56 {
57     \tl_if_empty:cTF { \l__siunitx_print_ #1 _color_tl }
58     { \use:n }
59     { \exp_args:Nv \textcolor { \l__siunitx_print_ #1 _color_tl } }
60     {
61         \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%           lwarp
62         {
63             \use:c
64             {
65                 siunitx_print_
66                 \tl_use:c { \l__siunitx_print_ #1 _mode_tl } :n
67             }
68             {#2}
69         }
70         {
71             \bool_lazy_all:nTF%           lwarp
72             {
73                 {\l__siunitx_print_text_family_bool}
74                 {\l__siunitx_print_text_series_bool}
75                 {\l__siunitx_print_text_shape_bool}
76             }
77             {% No font control if reset-text-family/series/shape

```

```

78             \use:c
79             {
80                 siunitx_print_%           lwarp
81                 text%                     lwarp
82                 :n%                       lwarp
83             }%                             lwarp
84             {#2}%                           lwarp
85         }
86     {
87         \LWR@textcurrentfont{%           lwarp
88         \use:c
89         {
90             siunitx_print_%           lwarp
91             text%                     lwarp
92             :n%                       lwarp
93         }%                             lwarp
94         {#2}%                           lwarp
95     }
96 }
97 }
98 }
99 }

```

To determine whether to make a complex root be italic or upright, `\l__siunitx_complex_output_root_tl` is compared to `\LWR@siunitx@complexrm<i/j>`, and the css style is set appropriately.

```

100 \newcommand*{\LWR@siunitx@complexrootstyle}{textrm}
101
102 \newcommand*{\LWR@siunitx@complexrmi}{\mathrm{i}}
103 \newcommand*{\LWR@siunitx@complexrmj}{\mathrm{j}}
104
105 \newcommand*{\LWR@siunitx@setcomplexroot}{%
106     \renewcommand*{\LWR@siunitx@complexrootstyle}{textit}%
107     \ifdefequal{\l__siunitx_complex_output_root_tl}{\LWR@siunitx@complexrmi}%
108         {\renewcommand*{\LWR@siunitx@complexrootstyle}{textrm}}%
109         {}%
110     \ifdefequal{\l__siunitx_complex_output_root_tl}{\LWR@siunitx@complexrmj}%
111         {\renewcommand*{\LWR@siunitx@complexrootstyle}{textrm}}%
112         {}%
113 }
114
115 \cs_set_protected:Npn \l__siunitx_complex_format_auxii:n #1
116 {
117     \LWR@siunitx@setcomplexroot%           lwarp
118     \__siunitx_complex_format_units:n {#1}
119     \tl_if_empty:NF \l__siunitx_complex_real_tl
120     { \exp_after:wN \__siunitx_complex_drop_exponent:nnnnnn \l__siunitx_complex_real_tl }
121     \exp_after:wN \__siunitx_complex_format_sign:nnnnnn \l__siunitx_complex_img_tl
122     \tl_set:Nx \l__siunitx_complex_tmp_tl
123     { \siunitx_number_output:NN \l__siunitx_complex_img_tl \q_nil }
124     \exp_after:wN \__siunitx_complex_extract_exponent:w \l__siunitx_complex_tmp_tl \q_stop
125     \tl_set:Nx \l__siunitx_complex_tmp_tl
126     {
127         \bool_lazy_or:nnTF
128         {
129             \bool_lazy_and:p:nn
130             { \l__siunitx_number_bracket_ambiguous_bool }
131             { ! \tl_if_empty_p:N \l__siunitx_complex_exp_tl }
132         }
133     }

```

```

132     {
133       ! \bool_lazy_any_p:n
134       {
135         { \tl_if_blank_p:n {#1} }
136         { \tl_if_empty_p:N \l__siunitx_complex_real_tl }
137         { \tl_if_empty_p:N \l__siunitx_complex_img_tl }
138       }
139     }
140     { \__siunitx_complex_format_bracket:n }
141     { \use:n }
142     {
143       \siunitx_number_output:N \l__siunitx_complex_real_tl
144       \exp_not:V \l__siunitx_complex_sign_tl
145       \bool_if:NF \l__siunitx_complex_root_after_bool
146       {
147         \InlineClass{\LWR@siunitx@complexrootstyle}% lwarp
148         {
149           \exp_not:V \l__siunitx_complex_output_root_tl
150         }
151       }
152       \exp_not:V \l__siunitx_complex_tmp_tl
153       \bool_if:NT \l__siunitx_complex_root_after_bool
154       {
155         \InlineClass{\LWR@siunitx@complexrootstyle}% lwarp
156         {
157           \exp_not:V \l__siunitx_complex_output_root_tl
158         }
159       }
160     }
161     \exp_not:V \l__siunitx_complex_exp_tl
162   }
163 }

```

$\langle 1: \text{deg/min/sec character} \rangle \langle 2: ? \rangle \langle 3: ? \rangle \langle 4: \text{integer part of angle} \rangle \langle 5: \text{decimal point character} \rangle \langle 6: \text{decimal part of angle} \rangle \langle 7: ? \rangle \langle 8: ? \rangle$

If not in a lateximage, print a simplified verison without the box measurement things which conflict with lwarp:

```

164 \cs_set_protected:Npn \__siunitx_angle_arc_print_auxii:nw
165 #1#2 \q_nil #3 \q_nil #4 \q_nil #5 \q_nil #6 \q_nil #7 \q_nil #8 \q_stop
166 {
167   \mode_if_math:TF
168   { \bool_set_true:N \l__siunitx_angle_tmp_bool }
169   { \bool_set_false:N \l__siunitx_angle_tmp_bool }
170   \siunitx_print_number:n {#2#3#4}
171   \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}% lwarp
172   {% lwarp
173     \tl_if_blank:nTF {#6}
174     { \__siunitx_angle_arc_print_auxvi:n {#1} }
175     {
176       \hbox_set:Nn \l__siunitx_angle_marker_box
177       {
178         \__siunitx_angle_arc_print_auxiii:n
179         { \siunitx_print_number:n {#5} }
180       }
181       \hbox_set:Nn \l__siunitx_angle_unit_box
182       {
183         \__siunitx_angle_arc_print_auxiii:n
184         {

```

```

185         \siunitx_unit_format:nN {#1} \l__siunitx_angle_tmp_tl
186         \siunitx_print_unit:V \l__siunitx_angle_tmp_tl
187         \skip_horizontal:n { -\scriptspace }
188     }
189 }
190 \dim_compare:nNnTF { \box_wd:N \l__siunitx_angle_marker_box } >
191 { \box_wd:N \l__siunitx_angle_unit_box }
192 {
193     \__siunitx_angle_arc_print_auxiv:NN
194     \l__siunitx_angle_marker_box
195     \l__siunitx_angle_unit_box
196 }
197 {
198     \__siunitx_angle_arc_print_auxiv:NN
199     \l__siunitx_angle_unit_box
200     \l__siunitx_angle_marker_box
201 }
202 \hbox_set_to_wd:Nnn \l__siunitx_angle_marker_box
203 \l__siunitx_angle_tmp_dim
204 {
205     \hbox_overlap_right:n
206     { \box_use_drop:N \l__siunitx_angle_marker_box }
207     \hbox_overlap_right:n
208     { \box_use_drop:N \l__siunitx_angle_unit_box }
209     \tex_hfil:D
210 }
211 \box_use:N \l__siunitx_angle_marker_box
212 \skip_horizontal:N \scriptspace
213 \siunitx_print_number:n {#6}
214 }
215 }%

```

{<1: deg/min/sec character>} {<2: ?>} {<3: ?>} {<4: integer part of angle>} {<5: decimal point character>} {<6: decimal part of angle>} {<7: ?>} {<8: ?>}

```

216 {%         lwarp: not in a lateximage, simplify for HTML
217     \tl_if_blank:nTF {#6}
218     { \__siunitx_angle_arc_print_auxvi:n {#1} }
219     {
220         \__siunitx_angle_arc_print_auxiii:n
221         {
222             \siunitx_print_number:n {#5}
223         }
224         \__siunitx_angle_arc_print_auxiii:n
225         {
226             \siunitx_unit_format:nN {#1} \l__siunitx_angle_tmp_tl
227             \siunitx_print_unit:V \l__siunitx_angle_tmp_tl
228         }
229         \siunitx_print_number:n {#6}
230     }
231 }%         lwarp
232 }

```

If not in a lateximage, print a simple inline fraction, avoiding the use of svg math:

```

233 \cs_set_protected:Npn \__siunitx_print_text_fraction:Nnn #1#2#3
234 {
235     \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
236     {%
237         \ensuremath

```

```

238     {
239     #1
240     { \mbox { \__siunitx_print_text_replace:n {#2} } }
241     { \mbox { \__siunitx_print_text_replace:n {#3} } }
242     }
243     }%
244     {%                                     lwarp
245     { \mbox { \__siunitx_print_text_replace:n {#2} } }% lwarp
246     /%                                     lwarp
247     { \mbox { \__siunitx_print_text_replace:n {#3} } }% lwarp
248     }%                                     lwarp
249     }

```

If not in a lateximage, print a \textsubscript:

```

250 \cs_set_protected:Npn \__siunitx_unit_format_qualifier_subscript:
251 {
252   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
253   {%
254     \__siunitx_unit_format_font:
255     \tl_set:Nx \l__siunitx_unit_part_tl
256     {
257       \c__siunitx_unit_math_subscript_tl
258       {
259         \exp_not:V \l__siunitx_unit_font_tl
260         { \exp_not:V \l__siunitx_unit_part_tl }
261       }
262     }
263   }
264   {% lwarp simplified for HTML:
265     \__siunitx_unit_format_font:
266     \tl_set:Nx \l__siunitx_unit_part_tl
267     {
268       \textsubscript
269       {
270         \exp_not:V \l__siunitx_unit_font_tl
271         { \exp_not:V \l__siunitx_unit_part_tl }
272       }
273     }
274   }
275 }

276 \cs_set_protected:Npn \siunitx_quantity:nn #1#2
277 {
278   \group_begin:
279   \siunitx_unit_options_apply:n {#2}
280   \tl_if_blank:nTF {#1}
281   {
282     \siunitx_unit_format:nN {#2} \l__siunitx_quantity_unit_tl
283     \siunitx_print_unit:V \l__siunitx_quantity_unit_tl
284   }
285   {
286     \bool_if:NTF \l__siunitx_number_parse_bool
287     { \__siunitx_quantity_parsed:nn {#1} {#2} }
288     {
289       \tl_set:Nn \l__siunitx_quantity_number_tl {
290         \LWR@subsingledollar{% lwarp
291           \textbackslash( % space
292           \LWR@HTMLsanitizedetokenized{%
293           \detokenize{#1}%

```

```

294         } \textbackslash)%          lwarp
295     }%
296     {siunitx unparsed}%
297     {\ensuremath{#1}}%          lwarp
298 }
299 \siunitx_unit_format:nN {#2} \l__siunitx_quantity_unit_tl
300 \siunitx_quantity_print:VV
301 \l__siunitx_quantity_number_tl \l__siunitx_quantity_unit_tl
302 }
303 }
304 \group_end:
305 }

```

\cancel for HTML does not work yet.

```

306 \newcommand*{\LWR@siunitx@nocancel}[1]{%
307   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
308     {\cancel{#1}}% SVG
309     {#1}% HTML
310 }
311
312 \AtBeginDocument{
313   \__siunitx_unit_set_symbolic:Npnn \cancel
314   { }
315   { \__siunitx_unit_parse_special:n { \cancel } }
316   { \__siunitx_unit_parse_special:n { \LWR@siunitx@nocancel } }% lwarp
317 }

```

For HTML, use a simple unaligned \num:

```

318 \newcommand{\LWR@HTML@tablenum}[2][\num{#1}{#2}]
319 \LWR@formatted{tablenum}

```

For HTML, the S column is simplified to a c column. Keys are set locally, allowing drop-exponent, etc.

```

320 \AtBeginDocument{
321 \HTMLnewcolumnntype{S}[1][>{\begingroup\sisetup{#1}}c<{\endgroup}}
322 }

```

To define simplified units for HTML:

\HTMLDeclareSIUnit [*options*] {*name*} {*definition*}

```

323 \NewDocumentCommand{\HTMLDeclareSIUnit}{o +m m}
324 {
325   \ifcsdef{__siunitx_unit_ \token_to_str:N #2 :w }
326     {}
327     {
328       \PackageError{lwarp}
329         {%
330           First~use~MessageBreak
331           \space\space\protect\DeclareSIUnit{
332             \token_to_str:N#2}{...}\MessageBreak
333           before~using~MessageBreak
334           \space\space\protect\HTMLDeclareSIUnit{
335             \token_to_str:N#2}{...}%
336         }

```

```

337             {%
338             See~the~Lwarp~manual~section~about~special~cases,~
339             regarding~siunitx.%
340             }
341         }
342     \csNewCommandCopycs
343     { __orig_siunitx_unit_ \token_to_str:N #2 :w }
344     { __siunitx_unit_ \token_to_str:N #2 :w }
345     \DeclareSIUnit[#1]{#2}
346     {
347         \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}
348         {\csuse{ __orig_siunitx_unit_ \token_to_str:N #2 :w }}
349         {#3}
350     }
351 }

```

```
352 \ExplSyntaxOff
```

HTML versions for existing units:

```

353 \AtBeginDocument{
354 \HTMLDeclareSIUnit\celsius{\LWR@siunitx@textcelsius}
355 \HTMLDeclareSIUnit\arcminute{\LWR@siunitx@textprime}
356 \HTMLDeclareSIUnit\arcsecond{\LWR@siunitx@textdblprime}
357 \HTMLDeclareSIUnit\elementarycharge{\textit{e}}
358 %
359 \HTMLDeclareSIUnit\clicht{\text{\textit{c}}\textsubscript{0}}
360 \HTMLDeclareSIUnit\bohr{\text{\textit{a}}\textsubscript{0}}
361 \HTMLDeclareSIUnit\electronmass{\text{\textit{m}}\textsubscript{e}}
362 \HTMLDeclareSIUnit\hartree{\text{\textit{E}}\textsubscript{h}}
363 \HTMLDeclareSIUnit\planckbar{\LWR@siunitx@textplanckbar}
364 }% \AtBeginDocument

```

Initial options:

```

365 \AtBeginDocument{
366 \sisetup{
367     per-mode=symbol, % fraction is not seen by pdftotext
368     angle-symbol-degree = {\LWR@siunitx@textdegree},
369     angle-symbol-minute = {\LWR@siunitx@textprime} ,
370     angle-symbol-second = {\LWR@siunitx@textdblprime} ,
371 }
372 }

```

Load late patches for lltjp-siunitx:

```

373 \AtBeginDocument{
374 \ifdef{\ltj@allalchar}
375     {\LWR@origRequirePackage{lwarp-lltjp-siunitx}}
376     {}
377 }

```

For MATHJAX:

```

378 \LWR@origRequirePackage{lwarp-common-mathjax-siunitx}
379
380 \CustomizeMathJax{\let\unit\si}
381 \CustomizeMathJax{\let\qty\SI}
382 \CustomizeMathJax{\let\qtyList\SIlist}

```

```

383 \CustomizeMathJax{\let\qtyrange\SIrange}
384 \CustomizeMathJax{\let\numproduct\num}
385 \CustomizeMathJax{\let\qtyproduct\SI}
386 \CustomizeMathJax{\let\complexnum\num}
387 \CustomizeMathJax{\newcommand{\complexqty}[3][][{\complexnum{#2}}\si{#3}}}
```

Pass range-phrase to common-mathjax-siunitx:

```

388 \ExplSyntaxOn
389 \AtBeginDocument{
390 \edef\LWR@siunitx@rangephrase{\l_siunitx_range_phrase_tl}
391 \expandafter\CustomizeMathJax\expandafter{%
392   \expandafter\def\expandafter\LWRsiunitxrangephrase%
393   \expandafter{\LWR@siunitx@rangephrase}%
394 }
395 }
396 \ExplSyntaxOff
```

File 453 **lwarp-siunitx-v2.sty**

§ 562 Package **siunitx-v2**

(Emulates or patches code by JOSEPH WRIGHT.)

Pkg siunitx-v2

siunitx-v2 is patched for use by lwarp, and is emulated for MATHJAX.

siunitx is well supported by lwarp.

Limitations Some general limitations:

fractions Due to *pdftotext* limitations, fraction output is replaced by symbol output for per-mode and quotient-mode.

\cancel is not currently supported for siunitx v3.

Negative values are not automatically colored.

 **tabular**

Tabular S and s columns are rendered as simple c columns, although key settings will be set. If using scientific notation, table-format, table-align-uncertainty, drop-exponent, etc.. use \tablenum for each cell. This is especially required for drop-exponent, without which the value will be shown incorrectly.

 **drop-exponent**

 **table-auto-round**

table-auto-round is ignored.

Math rendering Math may be rendered in several ways in the same document:

For math mode with `svg display`: The original siunitx code is used while generating the SVG image.

For HTML text mode: lwarp uses siunitx code patched for HTML, and simplified units.

For math expressions while using `MATHJAX`: A limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. The result usually looks fine, and otherwise is enough to get the meaning across.

Custom units siunitx allows customized units:

`\DeclareSIUnit`

```
{⟨name⟩} {⟨definition⟩}
```

`\DeclareSIUnit` declares a version of the unit for the print version. This is also used when the unit is printed in `svg math` or a `lateximage`. It is also used for HTML if an HTML-specific version is not defined with `\HTMLDeclareSIUnit`.

```
\DeclareSIUnit\myunit{\ensuremath{\text{m}_y}}
```

`\HTMLDeclareSIUnit`

```
{⟨name⟩} {⟨definition⟩}
```

 **v3 only!** Use this after the print unit has been defined. For siunitx v3, `\HTMLDeclareSIUnit` declares a simplified version of the unit for HTML, for example if the print-mode unit uses `TeX boxes` or `\ensuremath`:

```
\HTMLDeclareSIUnit\myunit{\text{m}\textsubscript{\textit{y}}}
```

It is also possible to provide a custom unit for `MATHJAX`:

```
\CustomizeMathJax{\newcommand{\myunit}{\text{m}_y}}
```

Predefined units Most units work as-is with HTML. For the following units, lwarp has already set `\HTMLDeclareSIUnit`: `\celsius`, `\arcminute`, `\arcsecond`, `\elementarycharge`, `\clight`, `\bohr`, `\electronmass`, `\hartree`, `\planckbar`.

 **MathJax**

Document modifications required for `MATHJAX`

 **`\sisetup`**

- Place `\sisetup` in the preamble before `\begin{document}`. Changes made later may be ignored, especially with `MATHJAX`. The `MATHJAX` emulation also ignores most macro options.

 **complex numbers**

- Complex numbers are displayed as entered, ignoring `output-complex-root`.

custom units

- Custom units may be added with `\CustomizeMathJax`. For example, from `lwarp-common-mathjax-siunitx`:

```
\CustomizeMathJax{\newcommand{\hartree}{\mathit{E}_{\mathrm{h}}}}
\CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\unicode{x212B}}}}
```

 **unit spacing**

- Units work better using `~` between units instead of using periods.

⚠ `\square`, `\cubic`

- To square or cube compound units, enclose the following compound units in braces:

```
\cubic{\centi\meter}
```

Single units do not require braces.

- For `\numlist`, the argument is printed as text as-is, so use space between semicolons for improved readability.

⚠ Missing \$ inserted

- If using `parse-numbers = false`, also use `\num` or `\qty`. `siunitx=siunitx>Missing $ inserted`.

Also see **MATHJAX option**, section 8.7.4.

for HTML output:

```
1 \RequirePackage{xcolor}% for \convertcolorspec
2
3 \LWR@ProvidesPackagePass{siunitx}[=v2]% 2021-04-17

4 \AtBeginDocument{% in case textcomp was not loaded
5   \DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
6   \DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
7   \DeclareSIUnit\elementarycharge{\textit{e}}
8   \DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
9   \DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
10  \DeclareSIUnit\planckbar{\LWR@siunitx@textplanckbar}
11 }% AtBeginDocument
```

Support the S and s column types:

```
12 \AtBeginDocument{
13 \HTMLnewcolumntype{S}[1][>{\begingroup\sisetup{#1}}c<{\endgroup}}
14 \HTMLnewcolumntype{s}[1][>{\begingroup\sisetup{#1}}c<{\endgroup}}
15 }
```

`\@ensuredmath` is not supported inside an `\hbox`, so it must temporarily be restored to its original. Similar for `\mbox`. SVG math is created explicitly when necessary, using `\LWR@subsingledollar`.

```
16
17 \ExplSyntaxOn
18 %
```

Modified to use the print version of `\@ensuredmath` to avoid having a `lateximage` each time.

```
19 \AtBeginDocument{
20 \cs_set_protected:Npn \__siunitx_print_text:
21 {
22   \LetLtxMacro\@ensuredmath\LWR@origensuredmath%          lwarp
23   \tl_replace_all:Nnn \l__siunitx_print_arg_tl { - }
24   { \textminus }
25   \__siunitx_print_text_aux:
26   \tl_replace_all:Nnn \l__siunitx_print_arg_tl { \mp }
27   { \ensuremath { \mp } }
28   \tl_remove_all:Nn \l__siunitx_print_arg_tl { \mathord }
29   \cs_set_eq:NN \PrintSubscript \__siunitx_print_text_sub:n
30   \cs_set_eq:NN \PrintSuperscript \__siunitx_print_text_super:n
31   \__siunitx_print_text_aux:NnN
```

```

32   _ { math_subscript }  \__siunitx_print_text_sub:n
33   _ { active }          \__siunitx_print_text_sub:n
34   ^ { math_superscript } \__siunitx_print_text_super:n
35   ^ { active }          \__siunitx_print_text_super:n
36   \q_recursion_tail ? ?
37   \q_recursion_stop
38   \l__siunitx_print_arg_tl
39 }
40 }

```

Modified to set set HTML \textcolor if not black:

```

41 \cs_new_protected:Npn \LWR@HTML@__siunitx_print_aux:
42 {
43   \text
44   {
45     \__siunitx_ensure_ltr:n
46     {
47       \color@begingroup
48 %
49       \__siunitx_print_color:
50       \__siunitx_font_shape:
51       \__siunitx_font_weight:
52       \use:c
53       {
54         __siunitx_ \l__siunitx_print_type_tl _
55         text \l__siunitx_font_family_tl :
56       }
57 %
58 %       \bool_if:NTF \l__siunitx_font_math_mode_bool
59 %       {
60 %         \__siunitx_print_math:
61 %       }
62 %       {
63 %         \LWR@findcurrenttextcolor% lwarp
64 %         \ifdefstring{\LWR@tempcolor}{000000}% lwarp
65 %         {\__siunitx_print_text:}% lwarp
66 %         {% lwarp
67 %           \LWR@textcurrentcolor{% lwarp
68 %             \__siunitx_print_text:
69 %           }% lwarp
70 %         }% lwarp
71 %       }
72 %       \color@endgroup
73 %     }
74 %   }
75 % }
76 \LWR@formatted{__siunitx_print_aux:}
77
78 \cs_new_protected:Npn \LWR@HTML@__siunitx_set_math_fam:n #1 {
79   \group_begin:
80 %   \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
81 %   \LetLtxMacro\mbox\LWR@print@mbox% lwarp
82 %   \hbox_set:Nn \l__siunitx_tmp_box
83 %   {
84 %     \ensuremath
85 %     {
86 %       \use:c { math #1 }
87 %     }

```

```

88         \int_const:cn { c__siunitx_math #1 _int } { \fam }
89     }
90 }
91% }
92 \group_end:
93 }
94 \LWR@formatted{__siunitx_set_math_fam:n}
95
96 \cs_new_protected:Npn \LWR@HTML@__siunitx_combined_output:n #1 {
97%
98     \group_begin:% lwarp
99     \bool_if:NTF \l__siunitx_number_parse_bool
100    {
101        \tl_clear:N \l__siunitx_number_out_tl
102        \bool_set_false:N \l__siunitx_number_compound_bool
103        \__siunitx_number_output_parse:n {#1}
104    }
105    {

```

For parse-numbers=false:

```

106        \__siunitx_unit_output_pre_print:
107        \begingroup%                               lwarp
108            \boolfalse{mathjax}%                   lwarp
109%        \__siunitx_print:nn { number } { \ensuremath {#1} }
110            \LWR@subsingledollar%                 lwarp
111                {% alt text
112                    \textbackslash( % space
113                        \LWR@HTMLsanitizedetokenized{%
114                            \detokenize{#1}%
115                        } \textbackslash)%           lwarp
116                }
117                {siunitx}% addl hashing
118                {%
119                    \__siunitx_print:nn { number } {%
120                        \LWR@origensuredmath{#1}%
121                    }%
122                }%                                 lwarp
123            \endgroup%                             lwarp
124        \__siunitx_unit_output_print:
125    }
126 \group_end:% lwarp
127%
128 }
129 \LWR@formatted{__siunitx_combined_output:n}

```

For parse-numbers=false:

```

130 \cs_new_protected:Npn \LWR@HTML@__siunitx_range_numbers_aux:n #1
131 {
132     \bool_if:NTF \l__siunitx_number_parse_bool
133     {
134         \tl_clear:N \l__siunitx_number_out_tl
135         \tl_clear:N \l__siunitx_number_out_saved_tl
136         \bool_set_false:N \l__siunitx_number_compound_bool
137         \__siunitx_number_output_parse:n {#1}
138         \bool_if:NT \l__siunitx_number_compound_bool
139         { \msg_error:nxx { siunitx } { multi-part-range } {#1} }
140     }
141     {

```

```

142     \__siunitx_unit_output_pre_print:
143     \begingroup%     lwarp
144         \boolfalse{mathjax}%     lwarp
145 %     \__siunitx_print:nn { number } {#1}
146         \LWR@subsingledollar%     lwarp
147         {% alt text
148             \textbackslash( % space
149             \LWR@HTMLsanitizedetokenized{%
150                 \detokenize{#1}%
151             } \textbackslash)%     lwarp
152         }%
153         {siunitx}% addl hashing
154         {%
155             \__siunitx_print:nn { number } {%
156                 \LWR@origensuredmath{#1}%
157             } %     lwarp
158         }%     lwarp
159     \endgroup%     lwarp
160     \__siunitx_unit_output_print:
161 }
162 }
163 \LWR@formatted{__siunitx_range_numbers_aux:n}

```

For parse-numbers=false:

```

164 \cs_new_protected:Npn \LWR@HTML@__siunitx_angle_print_direct_aux:nn #1#2 {
165     \tl_if_empty:nF {#1}
166     {
167         \tl_set:Nn \l__siunitx_unit_tl {#2}
168         \begingroup%     lwarp
169             \boolfalse{mathjax}%     lwarp
170 %     \__siunitx_print:nn { number } {#1}
171             \LWR@subsingledollar{%     lwarp
172                 \textbackslash( % space
173                 \LWR@HTMLsanitizedetokenized{%
174                     \detokenize{#1}%
175                 } \textbackslash)%     lwarp
176             }%
177             {siunitx}%
178             {%
179                 \__siunitx_print:nn { number } {
180                     \LWR@origensuredmath{#1}%
181                 }%     lwarp
182             }%     lwarp
183         \endgroup%     lwarp
184         \__siunitx_unit_output_print:
185     }
186 }
187 \LWR@formatted{__siunitx_angle_print_direct_aux:nn}
188 %

```

For quotients, the fraction code is replaced by the symbol code:

```

189 \cs_new_protected:Npn \LWR@HTML@__siunitx_number_output_quotient_fraction: {
190     \bool_set_true:N \l__siunitx_number_compound_bool
191     \__siunitx_number_output_quotient_aux_i:
192     \tl_set_eq:NN \l__siunitx_number_out_tl
193         \l__siunitx_number_numerator_tl
194     \tl_put_right:NV \l__siunitx_number_out_tl \l__siunitx_output_quotient_tl
195     \tl_put_right:NV \l__siunitx_number_out_tl

```

```

196 \l__siunitx_number_denominator_tl
197 \__siunitx_number_output_single_aux:
198 }
199 \LWR@formatted{__siunitx_number_output_quotient_fraction:}

```

For units, the fraction code is replaced by the symbol code:

```

200 \cs_new_protected:Npn \LWR@HTML@__siunitx_unit_format_fraction_fraction: {
201 \__siunitx_unit_format_fraction_symbol_aux:
202 \int_compare:nNnT { \l__siunitx_unit_denominator_int } > { 1 }
203 {
204 \bool_if:NT \l__siunitx_unit_denominator_bracket_bool
205 {
206 \tl_put_left:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_open_tl
207 \tl_put_right:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_close_tl
208 }
209 }
210 \tl_set_eq:NN \l__siunitx_unit_tl \l__siunitx_unit_numerator_tl
211 \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_per_symbol_tl
212 \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_unit_denominator_tl
213 }
214 \LWR@formatted{__siunitx_unit_format_fraction_fraction:}

215 \cs_new_protected:Npn \LWR@HTML@__siunitx_angle_print_astronomy_aux: {
216 \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-integer }
217 \l__siunitx_tmpa_tl
218 { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
219 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
220 {% lateximage
221 \hbox_set:Nn \l__siunitx_angle_marker_box
222 {
223 \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
224 }
225 \hbox_set:Nn \l__siunitx_angle_unit_box
226 {
227 \__siunitx_print:nV { unit } \l__siunitx_unit_tl
228 \skip_horizontal:n { -\scriptspace }
229 }
230 \__siunitx_angle_print_astronomy_aux:n { marker }
231 \__siunitx_angle_print_astronomy_aux:n { unit }
232 \hbox_set:Nn \l__siunitx_angle_marker_box
233 {
234 \box_use:N \l__siunitx_angle_marker_box
235 \box_use:N \l__siunitx_angle_unit_box
236 }
237 \dim_compare:nNnTF
238 { \l__siunitx_angle_marker_dim } > { \l__siunitx_angle_unit_dim }
239 { \__siunitx_angle_print_astronomy_marker: }
240 { \__siunitx_angle_print_astronomy_unit: }
241 }% lateximage
242 {% not a lateximage
243 \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
244 \__siunitx_print:nV { unit } \l__siunitx_unit_tl
245 }% not a lateximage
246 \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-decimal }
247 \l__siunitx_tmpa_tl
248 { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
249 }
250 \LWR@formatted{__siunitx_angle_print_astronomy_aux:}

```

```

251 \cs_new_protected:Npn \LWR@HTML@__siunitx_textsuperscript:n #1 {\textsuperscript{#1}}
252 \LWR@formatted{__siunitx_textsuperscript:n}
253
254 \cs_new_eq:NN \LWR@HTML@__siunitx_print_text_super:n \textsuperscript
255 \LWR@formatted{__siunitx_print_text_super:n}
256
257 \cs_new_eq:NN \LWR@HTML@__siunitx_print_text_sub:n \textsubscript
258 \LWR@formatted{__siunitx_print_text_sub:n}

```

\LWR@origenduresmath is added here in case the user asks for \mathrm , etc. for output-exponent-marker.

```

259 \cs_new_protected:Npn \LWR@HTML@__siunitx_number_format_final_exponent: {
260   \prop_get:NnN \l__siunitx_number_out_prop { exponent }
261   \l__siunitx_tmpa_tl
262   \tl_if_empty:NTF \l__siunitx_output_exponent_tl
263   {
264     \tl_set:Nx \l__siunitx_tmpa_tl
265     { ^ { \exp_not:V \l__siunitx_tmpa_tl } }
266     \tl_put_left:NV \l__siunitx_tmpa_tl \l__siunitx_exponent_base_tl
267   }
268   {
269     \tl_set:Nx \l__siunitx_tmpa_tl
270     {
271       \LWR@origensuredmath{%   lwarp
272         \exp_not:V \l__siunitx_output_exponent_tl
273         }%   lwarp
274       \exp_not:N \mathord
275       \exp_not:V \l__siunitx_tmpa_tl
276     }
277   }
278   \prop_put:NnV \l__siunitx_number_out_prop { exponent-result }
279   \l__siunitx_tmpa_tl
280 }
281 \LWR@formatted{__siunitx_number_format_final_exponent:}

```

\LWR@origensuredmath is added here to avoid using an image for the exponent product.

```

282 \cs_new_protected:Npn \LWR@HTML@__siunitx_number_format_final_combined: {
283   \__siunitx_number_format_brackets:n { mantissa }
284   \prop_get:NnN \l__siunitx_number_out_prop { mantissa-result }
285   \l__siunitx_tmpa_tl
286   \tl_if_empty:NT \l__siunitx_output_exponent_tl
287   {
288     \tl_put_right:Nx \l__siunitx_tmpa_tl
289     {
290       \exp_not:N \LWR@origensuredmath%   lwarp
291       {
292         \bool_if:NTF \l__siunitx_tight_bool
293         { { \exp_not:V \l__siunitx_exponent_product_tl } }
294         { { } \exp_not:V \l__siunitx_exponent_product_tl { } }
295       }
296     }
297   }
298   \prop_get:NnN \l__siunitx_number_out_prop { exponent-result }
299   \l__siunitx_tmpb_tl
300   \tl_put_right:NV \l__siunitx_tmpa_tl \l__siunitx_tmpb_tl
301   \prop_put:NnV \l__siunitx_number_out_prop { result }

```

```

302 \l__siunitx_tmpa_tl
303 \prop_put:Nnn \l__siunitx_number_out_prop
304 { result-bracket-exponent } { true }
305 }
306 \LWR@formatted{__siunitx_number_format_final_combined:}

```

\LWR@origensuredmath is added here to avoid using an image for the exponent product.

```

307 \cs_new_protected:Npn \LWR@HTML@__siunitx_number_output_parts_aux: {
308   \bool_if:NTF \l__siunitx_multi_repeat_bool
309     {
310       \prop_if_in:NnT \l__siunitx_number_out_prop { mantissa-result }
311       {
312         \__siunitx_number_output_parts_aux:n { mantissa }
313         \__siunitx_number_output_parts_aux:n { complex }
314       }
315       \prop_get:NnNT \l__siunitx_number_out_prop { exponent-result }
316       \l__siunitx_tmpa_tl
317       {
318         \prop_if_in:NnT \l__siunitx_number_out_prop { mantissa-result }
319         {
320           \tl_put_left:Nx \l__siunitx_tmpa_tl
321           {
322             \exp_not:N \LWR@origensuredmath
323             {
324               \bool_if:NTF \l__siunitx_tight_bool
325                 { { \exp_not:V \l__siunitx_exponent_product_tl } }
326                 { { } \exp_not:V \l__siunitx_exponent_product_tl { } }
327             }
328           }
329           \prop_put:NnV \l__siunitx_number_out_prop { exponent }
330           \l__siunitx_tmpa_tl
331         }
332         \__siunitx_number_output_parts_print:n { exponent }
333       }
334     }
335     { \__siunitx_number_output_single: }
336 }
337 \LWR@formatted{__siunitx_number_output_parts_aux:}

```

\LWR@origensuredmath is added here to avoid using an image for the exponent product.

```

338 \cs_new_protected:Npn \LWR@HTML@__siunitx_unit_output_print: {
339   \int_compare:nNnF { \l__siunitx_unit_prefix_int } = { 0 }
340   {
341     \tl_set:Nx \l__siunitx_tmpa_tl
342     {
343       \bool_if:NTF \l__siunitx_tight_bool
344       {
345         \exp_not:N \LWR@origensuredmath% \lwrap
346         { { \exp_not:V \l__siunitx_exponent_product_tl } }
347       }
348       {
349         \exp_not:N \LWR@origensuredmath% \lwrap
350         { { } \exp_not:V \l__siunitx_exponent_product_tl { } }
351       }
352       \int_use:N \l__siunitx_unit_prefix_base_int
353       ^ { \int_use:N \l__siunitx_unit_prefix_int }

```

```

354     }
355     \__siunitx_print:nV { number } \l__siunitx_tmpa_tl
356   }
357   \tl_if_empty:NF \l__siunitx_unit_tl
358   {
359     \__siunitx_unit_output_number_sep:
360     \__siunitx_print:nV { unit } \l__siunitx_unit_tl
361   }
362 }
363 \LWR@formatted{__siunitx_unit_output_print:}

```

`\LWR@origensuredmath` is added here to avoid using an image for the exponent product.

```

364 \cs_new_protected:Npn \LWR@HTML@__siunitx_range_exponent:
365 {
366   \bool_if:NT \l__siunitx_process_fixed_bool
367   {
368     \tl_set_eq:NN \l__siunitx_tmpa_tl \l__siunitx_exponent_product_tl
369     \bool_if:NT \l__siunitx_tight_bool
370     {
371       \tl_set:Nx \l__siunitx_tmpa_tl
372         { \exp_not:N \mathord \exp_not:o \l__siunitx_tmpa_tl }
373     }
374     \tl_set:Nx \l__siunitx_tmpa_tl
375     {
376       \exp_not:N \LWR@origensuredmath { %      lwarp
377         { } \exp_not:o \l__siunitx_tmpa_tl { }
378       }
379       10 \exp_not:N \PrintSuperscript
380       { \int_use:N \l__siunitx_process_fixed_int }
381     }
382     \__siunitx_print:nV { number } \l__siunitx_tmpa_tl
383   }
384 }
385 \LWR@formatted{__siunitx_range_exponent:}

```

`\LWR@origensuredmath` is added here to avoid using an image for the exponent product.

```

386 \cs_new_protected:Npn \LWR@HTML@__siunitx_table_print_S_reserved_exponent_product:
387 {
388   \tl_set_eq:NN \l__siunitx_tmpb_tl \l__siunitx_exponent_product_tl
389   \bool_if:NT \l__siunitx_tight_bool
390   {
391     \tl_set:Nx \l__siunitx_tmpb_tl
392       { \exp_not:N \mathord \exp_not:o \l__siunitx_tmpb_tl }
393   }
394   \tl_set:Nx \l__siunitx_tmpa_tl
395   {
396     \exp_not:N \LWR@origensuredmath { { } \exp_not:o \l__siunitx_tmpb_tl { } }
397     \exp_not:o \l__siunitx_tmpa_tl
398   }
399 }
400 \LWR@formatted{__siunitx_table_print_S_reserved_exponent_product:}

```

`\LWR@origensuredmath` is added here to avoid using an image for the output product.

```

401 \cs_new_protected:Npn \LWR@HTML@__siunitx_number_output_product_aux: {
402   \bool_set_true:N \l__siunitx_number_compound_bool
403   \__siunitx_number_preprocess:V \l__siunitx_number_arg_tl
404   \bool_if:NF \l__siunitx_error_bool
405   {
406     \tl_if_empty:NTF \l__siunitx_number_multi_tl
407     { \__siunitx_number_output_parse_aux: }
408     { \__siunitx_number_output_quotient: }
409     \tl_if_empty:NF \l__siunitx_number_next_tl
410     {
411       \bool_if:NTF \l__siunitx_tight_bool
412       {
413         \__siunitx_print:nn { number }
414         { \LWR@origensuredmath { \l__siunitx_output_product_tl } }
415       }
416       {
417         \__siunitx_print:nn { number }
418         { \LWR@origensuredmath { { } \l__siunitx_output_product_tl { } } }
419       }
420       \__siunitx_number_output_parse:V \l__siunitx_number_next_tl
421     }
422   }
423 }
424 \LWR@formatted{__siunitx_number_output_product_aux:}

```

Used to detect the math font.

```

425 \cs_set_protected:Npn \__siunitx_set_math_fam:n #1 {
426   \group_begin:
427   \hbox_set:Nn \l__siunitx_tmp_box
428   {
429     \LWR@origensuredmath%      lwarp
430     {
431       \use:c { math #1 }
432       {
433         \int_const:cn { c__siunitx_math #1 _int } { \fam }
434       }
435     }
436   }
437   \group_end:
438 }

```

Force \text:

```

439 \cs_set_protected:Npn \__siunitx_range_numbers:nn #1#2
440 {
441   \__siunitx_range_numbers_aux:n {#1}
442   \text{\l__siunitx_range_phrase_tl}%      lwarp
443   \__siunitx_range_numbers_aux:n {#2}
444 }

```

Force \text:

```

445 \cs_set_protected:Npn \__siunitx_range_unit:nnnn #1#2#3#4 {
446   \__siunitx_unit_parse_options:nn {#1} {#2}
447   \bool_if:NTF \l__siunitx_range_repeat_bool
448   {
449     \__siunitx_unit_in:nn {#1} {#2}
450     \__siunitx_range_numbers_aux:n {#3}
451     \text{\l__siunitx_range_phrase_tl}%      lwarp

```

```

452   \__siunitx_range_numbers_aux:n {#4}
453   }
454   {
455   \bool_if:NT \__siunitx_process_fixed_bool
456     { \bool_set_true:N \__siunitx_process_drop_exponent_bool }
457   \bool_if:NT \__siunitx_range_brackets_bool
458     { \__siunitx_print:nV { number } \__siunitx_bracket_open_tl }
459   \__siunitx_range_numbers:nn {#3} {#4}
460   \bool_if:NT \__siunitx_range_brackets_bool
461     { \__siunitx_print:nV { number } \__siunitx_bracket_close_tl }
462   \__siunitx_range_exponent:
463   \__siunitx_unit_output_number_sep:
464   \__siunitx_unit_output:nn {#1} {#2}
465   }
466 }

467 \ExplSyntaxOff

468 \AtBeginDocument{
469 \sisetup{
470   detect-mode=true,
471   per-mode=symbol, % fraction is not seen by pdftotext
472   text-celsius = {\LWR@siunitx@textcelsius},
473   text-degree = {\LWR@siunitx@textdegree},
474   text-arcminute = {\LWR@siunitx@textprime} ,
475   text-arcsecond = {\LWR@siunitx@textdblprime} ,
476 }
477 }

478 \LWR@origRequirePackage{lwarp-common-mathjax-siunitx}

```

Passing range-phrase to `common-mathjax-siunitx` does not seem to work with v2 using `translator` as it does with v3 using `translations`. The range-phrase therefore is set to an en-dash.

```

479 \AtBeginDocument{
480 \CustomizeMathJax{\def\LWRsiunitxrangephrase{\unicode{x2013}}}
481 }

```

File 454 **lwarp-common-mathjax-siunitx.sty**

§ 563 Package **common-mathjax-siunitx**

(Emulates or patches code by JOSEPH WRIGHT.)

Pkg common-mathjax-siunitx common-mathjax-siunitx adds MATHJAX for siunitx and siunitx-v2.

for HTML output:
MATHJAX

For MATHJAX.

The following runs much faster as separate `\CusomizeMathJax` calls instead of one single call.

```

1 \begin{warpMathJax}
2 \LWR@infoprocessingmathjax{siunitx}

3 \CustomizeMathJax{\newcommand{\tothe}[1]{^{#1}}}
4 \CustomizeMathJax{\newcommand{\raiseto}[2]{^{#2}^{#1}}}

```

Used as an end marker when parsing values:

```
5 \CustomizeMathJax{\newcommand{\LWRsiunitxEND}{}}
```

\ang

[<options>] {<value>}

```
6 \CustomizeMathJax{\def\LWRsiunitxang#1;#2;#3;#4\LWRsiunitxEND{%
7   \ifblank{#1}{\num{#1}\degree}%
8   \ifblank{#2}{\num{#2}^{\unicode{x2032}}}% \prime
9   \ifblank{#3}{\num{#3}^{\unicode{x2033}}}% \dblprime
10 }}
11 \CustomizeMathJax{\newcommand{\ang}[2][]{\LWRsiunitxang#2;;;\LWRsiunitxEND}}
```

\num

[<options>] {<value>}

\num handles optional powers (e, E, d, D), multiples (x), plus and minus, and period or comma decimal output.

To split the string, \def is used with parameter delimiters. When each of the following macros is used, extra delimiters are padded to the end of the arguments of each macro when used, and the final argument of each collects any extra unused delimiters.

The number is split by dimensions (x), then by powers (E, e, D, d), then by plus / minus (+-, \pm), then by plus and minus (+, -), then into pieces before and after the decimal point or decimal comma.

Determine if the number is output with a decimal period or a decimal comma. The enclosing braces tell MATHJAX to not add extra space after the punctuation.

```
12 \ExplSyntaxOn
13 \AtBeginDocument{
14   \ifdefstring{\l__siunitx_output_decimal_tl}{,}{.}
15   {\CustomizeMathJax{\def\LWRsiunitxdecimal{,}}}
16   {\CustomizeMathJax{\def\LWRsiunitxdecimal{.}}}
17 }
18 \ExplSyntaxOff
```

Any units which must be distributed across multiple dimensions:

```
19 \CustomizeMathJax{\def\LWRsiunitxdistribunit{}}
```

siunitx accepts either commas or periods as decimal points. \LWRsiunitxprintdecimal splits its input by periods then commas, parsing out before and after sections to print on either side of the decimal point.

\LWRsiunitxENDTWO is used only by \LWRsiunitxprintdecimalsubtwo, to avoid a parsing conflict with the more widely-used \LWRsiunitxEND.

The following splits by decimal commas:

```
20 \CustomizeMathJax{\newcommand{\LWRsiunitxENDTWO}{}}
21
22 \CustomizeMathJax{\def\LWRsiunitxprintdecimalsubtwo#1,#2,#3\LWRsiunitxENDTWO{}}
```

If nothing is ahead of the decimal comma, add a leading zero:

```
23   \ifblank{#1}{0}{\mathrm{#1}}%
```

If something is after the decimal comma, print the decimal and the fraction:

```
24   \ifblank{#2}%
25     {}%
26     {%
27       {\LWRsiunitxdecimal}%
```

```

28         \mathrm{#2}%
29     }%
30 }}

```

The following splits by decimal periods:

```

31 \CustomizeMathJax{\def\LWRsiunitxprintdecimalsub#1.#2.#3\LWRsiunitxEND{%
32     \LWRsiunitxprintdecimalsubtwo#1,,\LWRsiunitxENDTWO%
33     \ifblank{#2}%
34     {}%
35     {%
36         {\LWRsiunitxdecimal}%
37         \LWRsiunitxprintdecimalsubtwo#2,,\LWRsiunitxENDTWO%
38     }%
39 }}
40
41 \CustomizeMathJax{\newcommand{\LWRsiunitxprintdecimal}[1]{%
42     \LWRsiunitxprintdecimalsub#1...\LWRsiunitxEND%
43 }}

```

The following splits by +

```

44 \CustomizeMathJax{\def\LWRsiunitxnumplus#1+#2+#3\LWRsiunitxEND{%
45     \ifblank{#2}%
46     {%
47         \LWRsiunitxprintdecimal{#1}%
48     }% no plus
49     {%
50         \ifblank{#1}%
51         {\LWRsiunitxprintdecimal{#2}}% leading plus, ignore
52         {% a+b
53             \LWRsiunitxprintdecimal{#1}%
54             \unicode{x002B}% plus sign
55             \LWRsiunitxprintdecimal{#2}%
56         }%
57     }%
58     \LWRsiunitxdistribunit%
59 }}

```

The following splits by -

```

60 \CustomizeMathJax{\def\LWRsiunitxnumminus#1-#2-#3\LWRsiunitxEND{%
61     \ifblank{#2}%
62     {\LWRsiunitxnumplus#1+++\LWRsiunitxEND}%
63     {%
64         \ifblank{#1}{\LWRsiunitxprintdecimal{#1}}%
65         \unicode{x002D}% mathematical minus sign
66         \LWRsiunitxprintdecimal{#2}%
67         \LWRsiunitxdistribunit%
68     }%
69 }}

```

The following splits by \pm

```

70 \CustomizeMathJax{\def\LWRsiunitxnumpmmacro#1\pm#2\pm#3\LWRsiunitxEND{%
71     \ifblank{#2}%
72     {\LWRsiunitxnumminus#1---\LWRsiunitxEND}%
73     {%
74         \LWRsiunitxprintdecimal{#1}%
75         \unicode{x00B1}% \pm
76         \LWRsiunitxprintdecimal{#2}%
77         \LWRsiunitxdistribunit%
78     }%
79 }}

```

The following splits by +-

```

80 \CustomizeMathJax{\def\LWRsiunitxnumpm#1+-#2+-#3\LWRsiunitxEND{%
81   \ifblank{#2}%
82     {\LWRsiunitxnumpmmacro#1\pm\pm\pm\LWRsiunitxEND}%
83     {%
84       \LWRsiunitxprintdecimal{#1}%
85       \unicode{x0B1}% \pm
86       \LWRsiunitxprintdecimal{#2}%
87       \LWRsiunitxdistribunit%
88     }%
89 }}

```

Processes scientific notation. Special handling for a mantissa which is either empty or only a minus sign.

```

90 \CustomizeMathJax{\newcommand{\LWRsiunitxnumscientific}[2]{%
91   \ifblank{#1}%
92     {}%
93     {%
94       \ifstrequal{#1}{-}%
95         {-}%
96         {\LWRsiunitxprintdecimal{#1}\times}%
97       }%
98   10^{\LWRsiunitxprintdecimal{#2}}%
99   \LWRsiunitxdistribunit%
100 }}

```

The following splits by D

```

101 \CustomizeMathJax{\def\LWRsiunitxnumD#1D#2D#3\LWRsiunitxEND{%
102   \ifblank{#2}%
103     {\LWRsiunitxnumpm#1+-+\LWRsiunitxEND}%
104     {\mathrm{\LWRsiunitxnumscientific{#1}{#2}}}%
105 }}

```

The following splits by d

```

106 \CustomizeMathJax{\def\LWRsiunitxnumd#1d#2d#3\LWRsiunitxEND{%
107   \ifblank{#2}%
108     {\LWRsiunitxnumD#1DDD\LWRsiunitxEND}%
109     {\mathrm{\LWRsiunitxnumscientific{#1}{#2}}}%
110 }}

```

The following splits by E

```

111 \CustomizeMathJax{\def\LWRsiunitxnumE#1E#2E#3\LWRsiunitxEND{%
112   \ifblank{#2}%
113     {\LWRsiunitxnumd#1ddd\LWRsiunitxEND}%
114     {\mathrm{\LWRsiunitxnumscientific{#1}{#2}}}%
115 }}

```

The following splits by e

```

116 \CustomizeMathJax{\def\LWRsiunitxnume#1e#2e#3\LWRsiunitxEND{%
117   \ifblank{#2}%
118     {\LWRsiunitxnumE#1EEE\LWRsiunitxEND}%
119     {\mathrm{\LWRsiunitxnumscientific{#1}{#2}}}%
120 }}

```

The following splits by x

```

121 \CustomizeMathJax{\def\LWRsiunitxnumx#1x#2x#3x#4\LWRsiunitxEND{%
122   \ifblank{#2}%
123     {\LWRsiunitxnume#1eee\LWRsiunitxEND}%

```

```

124      {%
125          \ifblank{#3}%
126          {%
127              \LWRsiunitxnume#1eee\LWRsiunitxEND%
128              \times%
129              \LWRsiunitxnume#2eee\LWRsiunitxEND%
130          }%
131      {%
132          \LWRsiunitxnume#1eee\LWRsiunitxEND%
133          \times%
134          \LWRsiunitxnume#2eee\LWRsiunitxEND%
135          \times%
136          \LWRsiunitxnume#3eee\LWRsiunitxEND%
137      }%
138  }%
139 }}

```

```

140 \CustomizeMathJax{\newcommand{\num}[2][]{%
141     \LWRsiunitxnumx#2xxxxx\LWRsiunitxEND%
142 }}

```

 \backslash si

[*options*] {*unit*}

~ is converted to a thin space. Not able to convert period to thin space because the period might be in \raiseto , for example.

```

143 \CustomizeMathJax{\newcommand{\si}[2][]{%
144     \mathrm{\gsubstitute{#2}{~}{\,}}%
145 }}

```

 \backslash SI

[*options*] {*value*} [*prefix*] {*unit*}

\backslash SI has a second optional arg, which is parsed using \ifnextchar .

```

146 \CustomizeMathJax{\def\LWRsiunitxSIopt#1[#2]#3{%
147     \def\LWRsiunitxdistribunit{\, \si{#3}}%
148     {#2}\num{#1}%
149     \def\LWRsiunitxdistribunit{}}%
150 }}
151
152 \CustomizeMathJax{\newcommand{\LWRsiunitxSI}[2]{%
153     \def\LWRsiunitxdistribunit{\, \si{#2}}%
154     \num{#1}%
155     \def\LWRsiunitxdistribunit{}}%
156 }}
157 \CustomizeMathJax{\newcommand{\SI}[2][]{%
158     \ifnextchar[%
159         {\LWRsiunitxSIopt{#2}}%
160         {\LWRsiunitxSI{#2}}%
161 }}

```

 \backslash numlist

[*options*] {*list*}

\backslash numList should only be used in text mode. If used in MATHJAX, it is merely printed as text, so add space around the semicolons.

```

162 \CustomizeMathJax{\newcommand{\numList}[2][]{\text{#2}}}

```

 \backslash numrange

[*options*] {*value1*} {*value2*}

`\numrange` should only be used in text mode. If used in MATHJAX math, an en-dash is used instead of the range-phrase.

```
163 \CustomizeMathJax{\newcommand{\numrange}[3][]{%
164   \num{#2}\ \LWRsiunitxrangephrase\ \num{#3}%
165 }}
```

`\SIlist` [*options*] {*list*}

`\SIlist` and `\SIrange` should only be used in text mode. If used in MATHJAX, a simple emulation is provided.

```
166 \CustomizeMathJax{\newcommand{\SIlist}[3][]{\text{#2}\, \si{#3}}}
```

`\SIrange` [*options*] {*value1*} {*value2*} {*unit*}

```
167 \CustomizeMathJax{\newcommand{\SIrange}[4][]{%
168   \num{#2}\, #4\ \LWRsiunitxrangephrase\ \num{#3}\, #4%
169 }}
```

`\tablenum` [*options*] {*value*}

```
170 \CustomizeMathJax{\newcommand{\tablenum}[2][]{\mathrm{#2}}}
```

```
171 \CustomizeMathJax{\newcommand{\ampere}{\mathrm{A}}}
172 \CustomizeMathJax{\newcommand{\candela}{\mathrm{cd}}}
173 \CustomizeMathJax{\newcommand{\kelvin}{\mathrm{K}}}
174 \CustomizeMathJax{\newcommand{\kilogram}{\mathrm{kg}}}
175 \CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
176 \CustomizeMathJax{\newcommand{\mole}{\mathrm{mol}}}
177 \CustomizeMathJax{\newcommand{\second}{\mathrm{s}}}
178 %
179 \CustomizeMathJax{\newcommand{\becquerel}{\mathrm{Bq}}}
180 \CustomizeMathJax{\newcommand{\degreeCelsius}{\unicode{x2103}}}
181 \CustomizeMathJax{\newcommand{\coulomb}{\mathrm{C}}}
182 \CustomizeMathJax{\newcommand{\farad}{\mathrm{F}}}
183 \CustomizeMathJax{\newcommand{\gray}{\mathrm{Gy}}}
184 \CustomizeMathJax{\newcommand{\hertz}{\mathrm{Hz}}}
185 \CustomizeMathJax{\newcommand{\henry}{\mathrm{H}}}
186 \CustomizeMathJax{\newcommand{\joule}{\mathrm{J}}}
187 \CustomizeMathJax{\newcommand{\katal}{\mathrm{kat}}}
188 \CustomizeMathJax{\newcommand{\lumen}{\mathrm{lm}}}
189 \CustomizeMathJax{\newcommand{\lux}{\mathrm{lx}}}
190 \CustomizeMathJax{\newcommand{\newton}{\mathrm{N}}}
191 \CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
192 \CustomizeMathJax{\newcommand{\pascal}{\mathrm{Pa}}}
193 \CustomizeMathJax{\newcommand{\radian}{\mathrm{rad}}}
194 \CustomizeMathJax{\newcommand{\siemens}{\mathrm{S}}}
195 \CustomizeMathJax{\newcommand{\sievert}{\mathrm{Sv}}}
196 \CustomizeMathJax{\newcommand{\steradian}{\mathrm{sr}}}
197 \CustomizeMathJax{\newcommand{\tesla}{\mathrm{T}}}
198 \CustomizeMathJax{\newcommand{\volt}{\mathrm{V}}}
199 \CustomizeMathJax{\newcommand{\watt}{\mathrm{W}}}
200 \CustomizeMathJax{\newcommand{\weber}{\mathrm{Wb}}}
201 \CustomizeMathJax{\newcommand{\day}{\mathrm{d}}}
202 \CustomizeMathJax{\newcommand{\degree}{\mathrm{^\circ}}}
203 \CustomizeMathJax{\newcommand{\hectare}{\mathrm{ha}}}
204 \CustomizeMathJax{\newcommand{\hour}{\mathrm{h}}}
205 \CustomizeMathJax{\newcommand{\litre}{\mathrm{L}}}
206 \CustomizeMathJax{\newcommand{\liter}{\mathrm{L}}}
```

```
207 \CustomizeMathJax{\newcommand{\arcminute}{^\prime}}
208 \CustomizeMathJax{\newcommand{\minute}{\mathrm{min}}}
209 \CustomizeMathJax{\newcommand{\arcsecond}{^{\prime\prime}}}
210 \CustomizeMathJax{\newcommand{\tonne}{\mathrm{t}}}
211 \CustomizeMathJax{\newcommand{\astronomicalunit}{au}}
212 \CustomizeMathJax{\newcommand{\atomicmassunit}{u}}
213 \CustomizeMathJax{\newcommand{\bohr}{\mathit{a}_0}}
214 \CustomizeMathJax{\newcommand{\cflight}{\mathit{c}_0}}
215 \CustomizeMathJax{\newcommand{\dalton}{\mathrm{D}_\mathrm{a}}}
216 \CustomizeMathJax{\newcommand{\electronmass}{\mathit{m}_\mathrm{e}}}
217 \CustomizeMathJax{\newcommand{\electronvolt}{\mathrm{eV}}}
218 \CustomizeMathJax{\newcommand{\elementarycharge}{\mathit{e}}}
219 \CustomizeMathJax{\newcommand{\hartree}{\mathit{E}_\mathrm{h}}}
220 \CustomizeMathJax{\newcommand{\planckbar}{\mathit{\unicode{x210F}}}}
221 \CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\unicode{x212B}}}}
222 \CustomizeMathJax{\let\LRor\bar}
223 \CustomizeMathJax{\newcommand{\bar}{\mathrm{bar}}}
224 \CustomizeMathJax{\newcommand{\barn}{\mathrm{b}}}
225 \CustomizeMathJax{\newcommand{\bel}{\mathrm{B}}}
226 \CustomizeMathJax{\newcommand{\decibel}{\mathrm{dB}}}
227 \CustomizeMathJax{\newcommand{\knot}{\mathrm{kn}}}
228 \CustomizeMathJax{\newcommand{\mmHg}{\mathrm{mmHg}}}
229 \CustomizeMathJax{\newcommand{\nauticalmile}{\mathrm{M}}}
230 \CustomizeMathJax{\newcommand{\neper}{\mathrm{Np}}}
231 %
232 \CustomizeMathJax{\newcommand{\yocto}{\mathrm{y}}}
233 \CustomizeMathJax{\newcommand{\zepto}{\mathrm{z}}}
234 \CustomizeMathJax{\newcommand{\atto}{\mathrm{a}}}
235 \CustomizeMathJax{\newcommand{\femto}{\mathrm{f}}}
236 \CustomizeMathJax{\newcommand{\pico}{\mathrm{p}}}
237 \CustomizeMathJax{\newcommand{\nano}{\mathrm{n}}}
238 \CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
239 \CustomizeMathJax{\newcommand{\milli}{\mathrm{m}}}
240 \CustomizeMathJax{\newcommand{\centi}{\mathrm{c}}}
241 \CustomizeMathJax{\newcommand{\deci}{\mathrm{d}}}
242 \CustomizeMathJax{\newcommand{\deca}{\mathrm{da}}}
243 \CustomizeMathJax{\newcommand{\hecto}{\mathrm{h}}}
244 \CustomizeMathJax{\newcommand{\kilo}{\mathrm{k}}}
245 \CustomizeMathJax{\newcommand{\mega}{\mathrm{M}}}
246 \CustomizeMathJax{\newcommand{\giga}{\mathrm{G}}}
247 \CustomizeMathJax{\newcommand{\tera}{\mathrm{T}}}
248 \CustomizeMathJax{\newcommand{\peta}{\mathrm{P}}}
249 \CustomizeMathJax{\newcommand{\exa}{\mathrm{E}}}
250 \CustomizeMathJax{\newcommand{\zetta}{\mathrm{Z}}}
251 \CustomizeMathJax{\newcommand{\yotta}{\mathrm{Y}}}
252 %
253 \CustomizeMathJax{\newcommand{\percent}{\mathrm{\%}}}
254 %
255 \CustomizeMathJax{\newcommand{\meter}{\mathrm{m}}}
256 \CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
257 %
258 \CustomizeMathJax{\newcommand{\gram}{\mathrm{g}}}
259 \CustomizeMathJax{\newcommand{\kg}{\kilo\gram}}
260 \CustomizeMathJax{\newcommand{\of}[1]{_\mathrm{#1}}}
261 \CustomizeMathJax{\newcommand{\squared}{^2}}
262 \CustomizeMathJax{\newcommand{\square}[1]{\mathrm{#1}^2}}
263 \CustomizeMathJax{\newcommand{\cubed}{^3}}
264 \CustomizeMathJax{\newcommand{\cubic}[1]{\mathrm{#1}^3}}

265 \CustomizeMathJax{\newcommand{\per}{\, \mathrm{/}}}
```

```
266 \CustomizeMathJax{\newcommand{\celsius}{\unicode{x2103}}}
267 %
268 \CustomizeMathJax{\newcommand{\fg}{\femto\gram}}
269 \CustomizeMathJax{\newcommand{\pg}{\pico\gram}}
270 \CustomizeMathJax{\newcommand{\ng}{\nano\gram}}
271 \CustomizeMathJax{\newcommand{\ug}{\micro\gram}}
272 \CustomizeMathJax{\newcommand{\mg}{\milli\gram}}
273 \CustomizeMathJax{\newcommand{\g}{\gram}}
274 \CustomizeMathJax{\newcommand{\kg}{\kilo\gram}}
275 %
276 \CustomizeMathJax{\newcommand{\amu}{\mathrm{u}}}
277 %
278 \CustomizeMathJax{\newcommand{\pm}{\pico\metre}}
279 \CustomizeMathJax{\newcommand{\nm}{\nano\metre}}
280 \CustomizeMathJax{\newcommand{\um}{\micro\metre}}
281 \CustomizeMathJax{\newcommand{\mm}{\milli\metre}}
282 \CustomizeMathJax{\newcommand{\cm}{\centi\metre}}
283 \CustomizeMathJax{\newcommand{\dm}{\deci\metre}}
284 \CustomizeMathJax{\newcommand{\m}{\metre}}
285 \CustomizeMathJax{\newcommand{\km}{\kilo\metre}}
286 %
287 \CustomizeMathJax{\newcommand{\as}{\atto\second}}
288 \CustomizeMathJax{\newcommand{\fs}{\femto\second}}
289 \CustomizeMathJax{\newcommand{\ps}{\pico\second}}
290 \CustomizeMathJax{\newcommand{\ns}{\nano\second}}
291 \CustomizeMathJax{\newcommand{\us}{\micro\second}}
292 \CustomizeMathJax{\newcommand{\ms}{\milli\second}}
293 \CustomizeMathJax{\newcommand{\s}{\second}}
294 %
295 \CustomizeMathJax{\newcommand{\fmol}{\femto\mol}}
296 \CustomizeMathJax{\newcommand{\pmol}{\pico\mol}}
297 \CustomizeMathJax{\newcommand{\nmol}{\nano\mol}}
298 \CustomizeMathJax{\newcommand{\umol}{\micro\mol}}
299 \CustomizeMathJax{\newcommand{\mmol}{\milli\mol}}
300 \CustomizeMathJax{\newcommand{\mol}{\mol}}
301 \CustomizeMathJax{\newcommand{\kmol}{\kilo\mol}}
302 %
303 \CustomizeMathJax{\newcommand{\pA}{\pico\ampere}}
304 \CustomizeMathJax{\newcommand{\nA}{\nano\ampere}}
305 \CustomizeMathJax{\newcommand{\uA}{\micro\ampere}}
306 \CustomizeMathJax{\newcommand{\mA}{\milli\ampere}}
307 \CustomizeMathJax{\newcommand{\A}{\ampere}}
308 \CustomizeMathJax{\newcommand{\kA}{\kilo\ampere}}
309 %
310 \CustomizeMathJax{\newcommand{\ul}{\micro\litre}}
311 \CustomizeMathJax{\newcommand{\ml}{\milli\litre}}
312 \CustomizeMathJax{\newcommand{\l}{\litre}}
313 \CustomizeMathJax{\newcommand{\hl}{\hecto\litre}}
314 \CustomizeMathJax{\newcommand{\uL}{\micro\liter}}
315 \CustomizeMathJax{\newcommand{\mL}{\milli\liter}}
316 \CustomizeMathJax{\newcommand{\L}{\liter}}
317 \CustomizeMathJax{\newcommand{\hL}{\hecto\liter}}
318 %
319 \CustomizeMathJax{\newcommand{\mHz}{\milli\hertz}}
320 \CustomizeMathJax{\newcommand{\Hz}{\hertz}}
321 \CustomizeMathJax{\newcommand{\kHz}{\kilo\hertz}}
322 \CustomizeMathJax{\newcommand{\MHz}{\mega\hertz}}
323 \CustomizeMathJax{\newcommand{\GHz}{\giga\hertz}}
324 \CustomizeMathJax{\newcommand{\THz}{\tera\hertz}}
325 %
```

```

326 \CustomizeMathJax{\newcommand{\mN}{\milli\newton}}
327 \CustomizeMathJax{\newcommand{\N}{\newton}}
328 \CustomizeMathJax{\newcommand{\kN}{\kilo\newton}}
329 \CustomizeMathJax{\newcommand{\MN}{\mega\newton}}
330 %
331 \CustomizeMathJax{\newcommand{\Pa}{\pascal}}
332 \CustomizeMathJax{\newcommand{\kPa}{\kilo\pascal}}
333 \CustomizeMathJax{\newcommand{\MPa}{\mega\pascal}}
334 \CustomizeMathJax{\newcommand{\GPa}{\giga\pascal}}
335 %
336 \CustomizeMathJax{\newcommand{\mohm}{\milli\ohm}}
337 \CustomizeMathJax{\newcommand{\kohm}{\kilo\ohm}}
338 \CustomizeMathJax{\newcommand{\Mohm}{\mega\ohm}}
339 %
340 \CustomizeMathJax{\newcommand{\pV}{\pico\volt}}
341 \CustomizeMathJax{\newcommand{\nV}{\nano\volt}}
342 \CustomizeMathJax{\newcommand{\uV}{\micro\volt}}
343 \CustomizeMathJax{\newcommand{\mV}{\milli\volt}}
344 \CustomizeMathJax{\newcommand{\V}{\volt}}
345 \CustomizeMathJax{\newcommand{\kV}{\kilo\volt}}
346 %
347 \CustomizeMathJax{\newcommand{\W}{\watt}}
348 \CustomizeMathJax{\newcommand{\uW}{\micro\watt}}
349 \CustomizeMathJax{\newcommand{\mW}{\milli\watt}}
350 \CustomizeMathJax{\newcommand{\kW}{\kilo\watt}}
351 \CustomizeMathJax{\newcommand{\MW}{\mega\watt}}
352 \CustomizeMathJax{\newcommand{\GW}{\giga\watt}}
353 %
354 \CustomizeMathJax{\newcommand{\J}{\joule}}
355 \CustomizeMathJax{\newcommand{\uJ}{\micro\joule}}
356 \CustomizeMathJax{\newcommand{\mJ}{\milli\joule}}
357 \CustomizeMathJax{\newcommand{\kJ}{\kilo\joule}}
358 %
359 \CustomizeMathJax{\newcommand{\eV}{\electronvolt}}
360 \CustomizeMathJax{\newcommand{\meV}{\milli\electronvolt}}
361 \CustomizeMathJax{\newcommand{\keV}{\kilo\electronvolt}}
362 \CustomizeMathJax{\newcommand{\MeV}{\mega\electronvolt}}
363 \CustomizeMathJax{\newcommand{\GeV}{\giga\electronvolt}}
364 \CustomizeMathJax{\newcommand{\TeV}{\tera\electronvolt}}
365 %
366 \CustomizeMathJax{\newcommand{\kWh}{\kilo\watt\hour}}
367 %
368 \CustomizeMathJax{\newcommand{\F}{\farad}}
369 \CustomizeMathJax{\newcommand{\fF}{\femto\farad}}
370 \CustomizeMathJax{\newcommand{\pF}{\pico\farad}}
371 %
372 \CustomizeMathJax{\newcommand{\K}{\mathrm{K}}}
373 %
374 \CustomizeMathJax{\newcommand{\dB}{\mathrm{dB}}}
375 %
376 \CustomizeMathJax{\newcommand{\kibi}{\mathrm{Ki}}}
377 \CustomizeMathJax{\newcommand{\mebi}{\mathrm{Mi}}}
378 \CustomizeMathJax{\newcommand{\gibi}{\mathrm{Gi}}}
379 \CustomizeMathJax{\newcommand{\tebi}{\mathrm{Ti}}}
380 \CustomizeMathJax{\newcommand{\pebi}{\mathrm{Pi}}}
381 \CustomizeMathJax{\newcommand{\exbi}{\mathrm{Ei}}}
382 \CustomizeMathJax{\newcommand{\zebi}{\mathrm{Zi}}}
383 \CustomizeMathJax{\newcommand{\yobi}{\mathrm{Yi}}}
384 \end{warpMathJax}

```

File 455 **lwarp-skmath.sty**

§ 564 Package **skmath**

(Emulates or patches code by SIMON SIGURDHSSON.)

Pkg skmath

skmath is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{skmath}[2019/10/15]

Only defined if package option requested:

```

2 \begin{warpMathJax}
3 \ExplSyntaxOn
4 \bool_if:NT\g__skmath_define_common_sets_bool{
5 \CustomizeMathJax{\newcommand{\N}{\mathbb{N}}}
6 \CustomizeMathJax{\newcommand{\Z}{\mathbb{Z}}}
7 \CustomizeMathJax{\newcommand{\Q}{\mathbb{Q}}}
8 \CustomizeMathJax{\newcommand{\R}{\mathbb{R}}}
9 \CustomizeMathJax{\newcommand{\C}{\mathbb{C}}}
10 }

```

skmath is using `l3keys`, which does not seem to have an equivalent to `\ifpackagewith`. To detect package options, comparisons with the following are made to see if various macros have been defined as follows:

```

11 \cs_gset_nopar:Npn\LWR__skmath_imaginary_unit:n#1{#1}
12 \cs_gset_nopar:Npn\LWR__skmath_natural_log_e:{{e}}
13 \cs_gset_nopar:Npn\LWR__skmath_integral_d:{{d}}
14 \cs_gset_nopar:Npn\LWR__skmath_total_derivative_d:{{d}}

```

If notation=iso, use upright, else italic:

```

15 \cs_if_eq:NNTF \__skmath_imaginary_unit:n \LWR__skmath_imaginary_unit:n
16 {
17   \CustomizeMathJax{\newcommand{ii}{\mathit{i}}}
18   \CustomizeMathJax{\newcommand{jj}{\mathit{j}}}
19 }
20 {
21   \CustomizeMathJax{\newcommand{ii}{\mathrm{i}}}
22   \CustomizeMathJax{\newcommand{jj}{\mathrm{j}}}
23 }

```

If notation=iso, use upright, else italic:

```

24 \cs_if_eq:NNTF \__skmath_natural_log_e: \LWR__skmath_natural_log_e:
25 { \CustomizeMathJax{\newcommand{\ee}{\mathit{e}}} }
26 { \CustomizeMathJax{\newcommand{\ee}{\mathrm{e}}} }

```

skmath uses `\DeclarePairedDelimiter` from `mathtools` for `\abs` and `\norm`, and `lwarp` uses this to automatically define MATHJAX definitions for each.

If notation=english, use slanted, else upright:

```

27 \cs_if_eq:NNTF \__skmath_integral_d: \LWR__skmath_integral_d:
28   { \CustomizeMathJax{\newcommand{\d}{\mathit{d}}}} }
29   { \CustomizeMathJax{\newcommand{\d}{\mathrm{d}}}} }

```

Used to parse comma and caret arguments for `\pd` and `\td`:

```
30 \CustomizeMathJax{\def\LWRskmathEND{}}
```

Parse the arguments with up to four commas. Argument 6 contains any leftover commas.

```

31 \CustomizeMathJax{\def\LWRskmathpdstarsub#1#2,#3,#4,#5,#6\LWRskmathEND{
32   #1_{#2#3#4#5}%
33 }}
34
35 \CustomizeMathJax{\newcommand{\LWRskmathpdstar}[2]{%
36   \LWRskmathpdstarsub{#1}#2,,,\LWRskmathEND%
37 }}

```

Parse the arguments with up to two carets. Argument 3 contains any leftover carets. `\LWRskmathpdplus` is used to only place a plus sign starting after the first term. `\LWRskmathpdone` is used to only place a 1 digit if a second or later term does not have a power.

```

38 \CustomizeMathJax{\def\LWRskmathpdnumerator#1^#2^#3\LWRskmathEND{%
39   \ifblank{#1}{%
40     \ifblank{#2}{\LWRskmathpdplus\LWRskmathpdone}{\LWRskmathpdplus#2}
41   }
42 }}

```

Parse the arguments with up to two carets. Argument 3 contains any leftover carets.

```

43 \CustomizeMathJax{\def\LWRskmathpd denominator#1^#2^#3\LWRskmathEND{%
44   \ifblank{#1}{%
45     \ifblank{#2}%
46       {\partial{#1}}%
47       {\partial{#1}^{#2}}%
48   }%
49 }}

```

Factored from `\LWRskmathpdnostarsub`, following:

The phrase `^{}` appears to be required while parsing the carets. `\LWRskmathpdplus` is used to only place a plus sign starting after the first term. `\LWRskmathpdone` is used to only place a 1 digit if a second or later term does not have a power.

This may not be recursion-safe. (Is there really such a thing as nested differentials?)

```

50 \CustomizeMathJax{\newcommand{\LWRskmathdonominator}[5]{%
51   \partial^{%
52     \def\LWRskmathpdplus{}%
53     \LWRskmathpdnumerator#2^{}}^{\LWRskmathEND%
54     \def\LWRskmathpdplus{+%
55     \def\LWRskmathpdone{1}%
56     \LWRskmathpdnumerator#3^{}}^{\LWRskmathEND%
57     \LWRskmathpdnumerator#4^{}}^{\LWRskmathEND%

```

```

58     \LWRskmathpdnumerator#5^{^}\LWRskmathEND%
59   }%
60   {#1}%
61 }}
62
63 \CustomizeMathJax{\newcommand{\LWRskmathdoddenominator}[4]{%
64   \LWRskmathpddenominator#1^{^}\LWRskmathEND%
65   \ifblank{#2}{\,\,}%
66   \LWRskmathpddenominator#2^{^}\LWRskmathEND%
67   \ifblank{#3}{\,\,}%
68   \LWRskmathpddenominator#3^{^}\LWRskmathEND%
69   \ifblank{#4}{\,\,}%
70   \LWRskmathpddenominator#4^{^}\LWRskmathEND%
71 }}

```

Parse the arguments with up to four commas. Argument 6 contains any leftover commas.

```

72 \CustomizeMathJax{\def\LWRskmathpdnostarsub#1#2,#3,#4,#5,#6\LWRskmathEND{
73   \ifblank{#3}{\def\LWRskmathpdone{}}{\def\LWRskmathpdone{1}}
74   \frac%
75     {\LWRskmathdonumerator{#1}{#2}{#3}{#4}{#5}}%
76     {\LWRskmathdoddenominator{#2}{#3}{#4}{#5}}%
77 }}
78
79 \CustomizeMathJax{\newcommand{\LWRskmathpdnostar}[2]{%
80   \LWRskmathpdnostarsub{#1}#2,,,,,\LWRskmathEND%
81 }}
82 \CustomizeMathJax{\newcommand{\pd}{\ifstar\LWRskmathpdstar\LWRskmathpdnostar}}

```

If notation=english or legacy, use slanted, else upright:

```

83 \cs_if_eq:NNTF \__skmath_total_derivative_d: \LWR__skmath_total_derivative_d:
84   { \CustomizeMathJax{\newcommand{\LWRskmathtd}{\mathit{d}}} }
85   { \CustomizeMathJax{\newcommand{\LWRskmathtd}{\mathrm{d}}} }
86 \CustomizeMathJax{\def\LWRskmathtdsub#1#2^#3\LWRskmathEND{%
87   \frac
88     {\LWRskmathtd^{#3}{#1}}
89     {\LWRskmathtd{#2}^{#3}}
90 }}
91
92 \CustomizeMathJax{\newcommand{\td}[2]{%
93   \LWRskmathtdsub{#1}#2^{\LWRskmathEND%
94 }}
95 \CustomizeMathJax{\newcommand{\E}[1]{%
96   \operatorname{E}\left[#1\right]%
97 }}
98 \CustomizeMathJax{\let\given\mid}
99
100 \CustomizeMathJax{\newcommand{\P}[1]{%
101   \operatorname{P}%
102   \left(#1\right)%
103 }}

```

```

104 \CustomizeMathJax{\newcommand{\var}[1]{%
105   \operatorname{Var}\left(#1\right)%
106 }}
107
108 \CustomizeMathJax{\newcommand{\cov}[2]{%
109   \operatorname{Cov}\left(#1,#2\right)%
110 }}

```

Common code for `\sin` etc:

```

111 \CustomizeMathJax{\newcommand{\LWRskmathtrigtwo}[2][]{%
112   \ifblank{#1}{\^{#1}}%
113   \ifblank{#2}{\left(#2\right)%
114 }}
115
116 \CustomizeMathJax{\newcommand{\LWRskmathtrig}[1]{%
117   \operatorname{#1}%
118   \LWRskmathtrigtwo%
119 }}

120 \CustomizeMathJax{\renewcommand{\sin}{\LWRskmathtrig{sin}}}
121 \CustomizeMathJax{\renewcommand{\arcsin}{\LWRskmathtrig{arcsin}}}
122
123 \CustomizeMathJax{\renewcommand{\cos}{\LWRskmathtrig{cos}}}
124 \CustomizeMathJax{\renewcommand{\arccos}{\LWRskmathtrig{arccos}}}
125
126 \CustomizeMathJax{\renewcommand{\tan}{\LWRskmathtrig{tan}}}
127 \CustomizeMathJax{\renewcommand{\arctan}{\LWRskmathtrig{arctan}}}
128
129 \CustomizeMathJax{\renewcommand{\cot}{\LWRskmathtrig{cot}}}
130
131 \CustomizeMathJax{\renewcommand{\sinh}{\LWRskmathtrig{sinh}}}
132 \CustomizeMathJax{\renewcommand{\cosh}{\LWRskmathtrig{cosh}}}
133 \CustomizeMathJax{\renewcommand{\tanh}{\LWRskmathtrig{tanh}}}

```

Common code for `\ln` and `\log`:

```

134 \CustomizeMathJax{\newcommand{\LWRskmathlogtwo}[2][]{%
135   \ifblank{#1}{\_{#1}}%
136   \ifblank{#2}{\left(#2\right)%
137 }}
138
139 \CustomizeMathJax{\newcommand{\LWRskmathlog}[1]{%
140   \operatorname{#1}%
141   \LWRskmathlogtwo%
142 }}

143 \CustomizeMathJax{\renewcommand{\ln}{\LWRskmathlog{ln}}}
144 \CustomizeMathJax{\renewcommand{\log}{\LWRskmathlog{log}}}

145 \CustomizeMathJax{\newcommand{\LWRskmathexpparens}[1]{%
146   \operatorname{exp}%
147   \ifblank{#1}{\left(#1\right)%
148 }}

```

See the `skmath` source for the original of the following:

```

149 \CustomizeMathJax{\newcommand{\LWRskmathexpnostar}[1]{%

```

```

150 \mathchoice
151   {\ee^{#1}}
152   {\LWRskmathexpparens{#1}}
153   {\LWRskmathexpparens{#1}}
154   {\LWRskmathexpparens{#1}}
155 }}
156
157 \CustomizeMathJax{\renewcommand{\exp}{\ifstar\LWRskmathexpparens\LWRskmathexpnostar}}

```

Common code for `\min` etc:

```

158 \CustomizeMathJax{\newcommand{\LWRskmathminstar}[2][]{%
159   \operatorname{\LWRskmathminname}%
160   \ifblank{#1}{}{%
161     _{\mathchoice{\mathclap{#1}}{#1}{#1}{#1}}
162   }%
163   \ifblank{#2}{}{#2}%
164 }}

165 \CustomizeMathJax{\newcommand{\LWRskmathminnostar}[2][]{%
166   \ifblank{#1}{%
167     {\operatorname{\LWRskmathminname}}%
168     {%
169       \underset%
170         {\mathchoice{\mathclap{#1}}{#1}{#1}{#1}}%
171         {\operatorname{\LWRskmathminname}}%
172       }%
173   \ifblank{#2}{}{\left\{#2\right\}}%
174 }}

```

`\LWRskmathminname` seems to be recursion-safe since it is used immediately.

```

175 \CustomizeMathJax{\newcommand{\LWRskmathmin}[1]{%
176   \def\LWRskmathminname{#1}%
177   \ifstar\LWRskmathminstar\LWRskmathminnostar%
178 }}

179 \CustomizeMathJax{\renewcommand{\min}{\LWRskmathmin{min}}}
180 \CustomizeMathJax{\renewcommand{\argmin}{\arg\LWRskmathmin{min}}}
181
182 \CustomizeMathJax{\renewcommand{\max}{\LWRskmathmin{max}}}
183 \CustomizeMathJax{\renewcommand{\argmax}{\arg\LWRskmathmin{max}}}
184 \CustomizeMathJax{\renewcommand{\sup}{\LWRskmathmin{sup}}}
185 \CustomizeMathJax{\renewcommand{\inf}{\LWRskmathmin{inf}}}

186 \CustomizeMathJax{\let\bar\overline}
187
188 \CustomizeMathJax{\let\vec\boldsymbol}

```

Remember the original definitions:

```

189 \CustomizeMathJax{\let\LWRskmathRe\Re}
190 \CustomizeMathJax{\let\LWRskmathIm\Im}

```

Redefine depending on notation=iso:

```

191 \bool_if:NTF\g__skmath_iso_complex_parts_bool{
192   \CustomizeMathJax{\renewcommand{\Re}[1]{%

```

```

193     \LWRskmathRe%
194     \ifblank{#1}{\left(#1\right)}%
195   }}
196   \CustomizeMathJax{\renewcommand{\Im}[1]{%
197     \LWRskmathIm%
198     \ifblank{#1}{\left(#1\right)}%
199   }}
200 }{
201   \CustomizeMathJax{\renewcommand{\Re}[1]{%
202     \operatorname{Re}%
203     \ifblank{#1}{#1}%
204   }}
205   \CustomizeMathJax{\renewcommand{\Im}[1]{%
206     \operatorname{Im}%
207     \ifblank{#1}{#1}%
208   }}
209 }
210
211 \ExplSyntaxOff
212 \end{warpMathJax}

```

File 456 **lwarp-slantsc.sty**

§ 565 Package **slantsc**

(Emulates or patches code by HARALD HARDERS.)

Pkg slantsc

slantsc is emulated for HTML, and used as-is for print output.

for HTML output:

```

1 \LWR@ProvidesPackagePass{slantsc}[2012/01/01]

2 \newcommand*\LWR@HTML@nosshape{}
3 \LWR@formatted{nosshape}
4
5 \FilenameNullify{%
6   \LetLtxMacro\nosshape\@empty%
7 }

```

File 457 **lwarp-slashed.sty**

§ 566 Package **slashed**

(Emulates or patches code by DAVID CARLISLE.)

Pkg slashed

slashed works as-s for HTML SVG math. For MATHJAX, emulation is provided.

for HTML output:

```

1 \LWR@ProvidesPackagePass{slashed}[1997/01/16]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\slashed}[1]{\cancel{#1}}}
4 \end{warpMathJax}

```

File 458 **lwarp-soul.sty**

§ 567 Package **soul**

(Emulates or patches code by MELCHIOR FRANZ.)

Pkg soul

soul is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{soul}[2003/11/17]
2 \RequirePackage{xcolor}% for \convertcolorspec

Storage for the colors to use:

```
3 \newcommand*\LWR@soululcolor{}
4
5 \newcommand*\LWR@soulstcolor{}
6
7 % \definecolor{LWR@soulhlcolordefault}{HTML}{F8E800}
8 % \newcommand*\LWR@soulhlcolor{LWR@soulhlcolordefault}
9 \newcommand*\LWR@soulhlcolor{}
```

\so

{<text>}

Basic markup with css:

```
10 \newcommand{\so}[1]{%
11 \InlineClass(letter-spacing:.2ex){letterspacing}{#1}%
12 }
```

\caps

{<text>}

```
13 \newcommand{\caps}[1]{%
14   \InlineClass%
15     (font-variant:small-caps;letter-spacing:.1ex)%
16     {capsspacing}{#1}%
17 }
```

\LWR@soulcolor

{<text>} {<color>} {<class>} {<colorstyle>} {<FormatWPstyle>}

Add colors if not empty:

```
18 \newcommand{\LWR@soulcolor}[5]{%
19 \ifcempty{#2}%
20 {%
21   \InlineClass(#5){#3}{#1}%
22 }%
23 {%
24   \convertcolorspec{named}{\@nameuse{#2}}{HTML}\LWR@tempcolor%
25   \LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}%
26 }%
27 }
```

```
28 \newcommand{\ul}[1]{%
29 \LWR@soulcolor{#1}{LWR@soululcolor}{uline}{text-decoration-color}%
30   {text-decoration:underline; text-decoration-skip: auto;}
```

```

31 }
32
33 \newcommand{\st}[1]{
34 \LWR@soulcolor{#1}{LWR@soulstcolor}{sout}{text-decoration-color}%
35   {text-decoration:line-through}%
36 }
37
38 \newcommand{\hl}[1]{
39 \LWR@soulcolor{#1}{LWR@soulhlcolor}{highlight}{background-color}%
40   {background:LWR@origpound{ }F8E800}
41 }

```

Nullified:

```

42 \newcommand*\soulaccent}[1]{}
43 \newcommand*\soulregister}[2]{}
44 \newcommand*\sloppyword}[1]{#1}
45 \newcommand*\sodef}[5]{\DeclareRobustCommand*#1[1]{\so{##1}}}
46 \newcommand*\resetso{}
47 \newcommand*\capsdef}[5]{}
48 \newcommand*\capsreset{}
49 \newcommand*\capssave}[1]{}
50 \newcommand*\capselect}[1]{}
51 \newcommand*\setul}[2]{}
52 \newcommand*\resetul{}
53 \newcommand*\setuldepth}[1]{}
54 \newcommand*\setuloverlap}[1]{}
55 \newcommand*\<{}

```

Set colors:

```

56 \newcommand*\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}
57 \newcommand*\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}
58 \newcommand*\sethlcolor}[1]{\renewcommand{\LWR@soulhlcolor}{#1}}

```

Long versions of the user-level macros:

```

59 \let\textso\so
60 \let\textul\ul
61 \let\texthl\hl
62 \let\textcaps\caps

```

File 459 **lwarp-soulpos.sty**

§ 568 Package **soulpos**

(Emulates or patches code by JAVIER BEZOS.)

Pkg soulpos

soulpos is emulated.

for HTML output:

```

1 \RequirePackage{soul}
2 \RequirePackage{soulutf8}
3 \LWR@ProvidesPackageDrop{soulpos}[2012/02/25]

4 \NewDocumentCommand{\ulposdef}{m o m}{}
5

```

```

6 \newdimen\ulwidth
7
8 \newcommand\ifulstarttype[1]{%
9 \expandafter\@secondoftwo%
10 }
11
12 \newcommand\ifulendtype[1]{%
13 \expandafter\@secondoftwo%
14 }
15
16 \newcommand{\ulstarttype}{0}
17 \newcommand{\ulendtype}{0}
18 \newcommand\ulpostolerance{0}%

```

File 460 **lwarp-soulutf8.sty**

§ 569 Package **soulutf8**

Pkg soulutf8

soulutf8 is emulated.

lwarp's HTML output naturally supports UTF-8 encoding.

for HTML output: 1 \LWR@ProvidesPackageDrop{soulutf8}[2016/05/16]
2 \RequirePackage{soul}

File 461 **lwarp-splitbib.sty**

§ 570 Package **splitbib**

Pkg splitbib

(Emulates or patches code by NICOLAS MARKEY.)

splitbib is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{splitbib}[2005/12/22]

```

2 \def\NMSB@stylebox#1#2{%
3 \begin{BlockClass}[text-align:center ; border: 1px solid black]{splitbibbox}
4   \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{#1#2}}
5 \end{BlockClass}
6 }
7
8 \def\NMSB@stylebar#1#2{%
9 \begin{BlockClass}[%
10   text-align:center ;
11   border-top: 1px solid black ;
12   border-bottom: 1px solid black ;
13 ]{splitbibbar}
14   \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{#1#2}}
15 \end{BlockClass}
16 }
17
18 \def\NMSB@styledash#1#2{%
19 \begin{BlockClass}[%
20   text-align:center ;

```

```

21 ]{\splitibdash}
22   \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{---~#1#2~---}}
23 \end{BlockClass}
24 }
25
26 \def\NMSB@stylenone#1#2{%
27   \par
28 }
29
30 \def\NMSB@stylesimple#1#2{%
31 \par
32 \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{#1#2}}
33 \par
34 }

```

File 462 **lwarp-splitidx.sty**

§ 571 Package **splitidx**

(Emulates or patches code by MARKUS KOHM.)

Pkg splitidx

splitidx is patched for use by lwarp.

If the `latexmk` option is selected for `lwarp`, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

 `\thepage` When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to `\thepage` during HTML output, as the concept of a page number is meaningless. Instead, do

```

\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}

```

where the `\index`-like action occurs, and then refer to `\arabic{LWR@autoindex}` instead of `\thepage` where the reference should occur.

See section 692.17 in the `lwarp-patch-memoir` package for the `\@wrsindexhyp` macro as an example.

for HTML output: 1 \LWR@ProvidesPackagePass{splitidx}[2016/02/18]

```

2 \catcode'\_ =12%
3 \xpatchcmd{\newindex}
4   {\jobname-#2.idx}
5   {\jobname-#2_html.idx}
6   {}
7   {\LWR@patcherror{splitidx}{\newindex}}
8 \catcode'\_ =8%

```

Patched to use `lwarp`'s automatic indexing counter instead of `\thepage`:

```

9 \renewcommand*{\@wrsindex}[2][]{%
10   \ifx\relax#1\relax
11     \if@splitidx
12       \@wrsindex[idx]{#2}%

```

```

13  \else
14  \def\@tempa{#2}%
15  \if@verbindex\@onelevel@sanitize\@tempa\fi
16  \wrindex{\@tempa}%
17  \fi
18  \else
19  \def\@tempa{#2}%
20  \csname index@#1@hook\endcsname
21%  \expandafter\ifx\csname @wrsindex\endcsname\relax
22  \addtocounter{LWR@autoindex}{1}%          lwarp
23%  \@wrsindex{#1}{\@tempa}{\thepage}}%
24  \@wrsindex{#1}{\@tempa}{\arabic{LWR@autoindex}}%
25%  \else
26%  \def\@tempb{\@wrsindex{#1}}%
27%  \expandafter\@tempb\@tempa||\%
28%  \fi

```

The label is assigned after the file write to avoid conflict with cleveref.

```

29  \label{LWRindex-\arabic{LWR@autoindex}}%   lwarp
30  \endgroup
31  \@esphack
32  \fi
33 }

```

lwarp defines sectioning commands with xparse, so the below patches are done as temporary redefinitions instead of being \let.

```

34 \xpatchcmd{\printsubindex}
35  {\let\section\subsection}
36  {\renewcommand*\section{\subsection}}
37  {}
38  {\LWR@patcherror{splitidx}{printsubindex-section}}
39
40 \xpatchcmd{\printsubindex}
41  {\let\chapter\section}
42  {\renewcommand*\chapter{\section}}
43  {}
44  {\LWR@patcherror{splitidx}{printsubindex-chapter}}
45
46 \xpatchcmd{\printsubindex}
47  {\let\@makechapterhead\section}
48  {\def\@makechapterhead{\section}}
49  {}
50  {\LWR@patcherror{splitidx}{printsubindex-chapter}}

```

File 463 **lwarp-srcltx.sty**

§ 572 Package **srcltx**

Pkg srcltx

srcltx is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{srcltx}[2006/11/12]
2 \newif\ifSRCOK \SRCOKfalse
3 \newcommand*{srcIncludeHook[1]}{

```

```

4 \newcommand*\srcInputHook[1]{}
5 \newcommand*\MainFile{}
6 \def\MainFile{\jobname.tex}
7 \newcommand*\CurrentInput{}
8 \gdef\CurrentInput{\MainFile}
9 \newcommand\Input{}
10 \let\Input\input

```

File 464 **lwarp-srctex.sty**

§ 573 Package **srctex**

Pkg srctex

srctex is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{srctex}[2006/11/12]
2 \LWR@origRequirePackage{lwarp-srcltx}

```

File 465 **lwarp-stabular.sty**

§ 574 Package **stabular**

Pkg stabular

(Emulates or patches code by SIGITAS TOLUŠIS.)

stabular is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{stabular}[2014/03/20]

```

Env stabular [*vpos*] [*colspec*]

```

2 \newenvironment{stabular}[2][c]
3 {
4 \begin{tabular}[#1]{#2}
5 \renewcommand{\noalign}[1]{}
6 }
7 {\end{tabular}}

```

Env stabular {*width*} [*vpos*] [*colspec*]

```

8 \NewDocumentEnvironment{stabular*}{m o m}
9 {
10 \begin{tabular}[#2]{#3}
11 \renewcommand{\noalign}[1]{}
12 }
13 {\end{tabular}}

```

File 466 **lwarp-stackengine.sty**

§ 575 Package **stackengine**

(Emulates or patches code by STEVEN B. SEGLETES.)

Pkg stackengine

stackengine is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{stackengine}[2017/02/13]

The original version is necessary for the patched `\@stack` and `\stackanchor`, where nesting `lateximages` does not work:

```
2 \LetLtxMacro\LWR@orig@stackengine\stackengine
3 \renewcommand*{\stackengine}[8]{%
4   \ifstrequal{#4}{0}%
5     {\begin{lateximage}[\ImageAltText]}%
6     {\begin{lateximage}[\ImageAltText][vertical-align:top]}%
7   \LWR@orig@stackengine{#1}{#2}{#3}{#4}{#5}{#6}{#7}{#8}%
8   \end{lateximage}%
9 }
```

`\@stack` uses a `lateximage` with a vertical alignment:

```
10 \LetLtxMacro\LWR@orig@@stack\@stack
11
12 \xpatchcmd{\LWR@orig@@stack}{\stackengine}{\LWR@orig@stackengine}
13   {}
14   {\LWR@patcherror{stackengine}{\LWR@orig@@stack}}
15
16 \renewcommand*{\@stack}[4]{%
17   \ifstrequal{#3}{0}%
18     {\begin{lateximage}[\ImageAltText]}%
19     {\begin{lateximage}[\ImageAltText][vertical-align:top]}%
20   \LWR@orig@@stack{#1}{#2}{#3}{#4}%
21   \end{lateximage}%
22 }
```

The lapping macros are disabled for HTML:

```
23 \newcommand*\LWR@HTML@@stacklap[4]{#3}
24 \LWR@formatted{@stacklap}
```

`\stackanchor` is patched for two instances of `\stackengine`. A `lateximage` with vertical alignment is used.

```
25 \xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
26   {}
27   {\LWR@patcherror{stackengine}{stackanchor patch 1}}
28
29 \xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
30   {}
31   {\LWR@patcherror{stackengine}{stackanchor patch 2}}
32
33 \xpretocmd{\stackanchor}
34   {\begin{lateximage}[\ImageAltText][vertical-align:middle]}
35   {}
36   {\LWR@patcherror{stackengine}{stackanchor pre}}
37
38 \xapptocmd{\stackanchor}{\end{lateximage}}
39   {}
40   {\LWR@patcherror{stackengine}{stackanchor app}}
```

`\Centerstack` is simply placed inside a `lateximage` with a vertical alignment:

```

41 \xpretocmd{\Centerstack}
42   {\begin{lateximage}[\ImageAltText][vertical-align:middle]}
43   {}
44   {\LWR@patcherror{stackengine}{Centerstack pre}}
45
46 \xapptocmd{\Centerstack}{\end{lateximage}}
47   {}
48   {\LWR@patcherror{stackengine}{Centerstack app}}

```

`\savestack` reverts to print mode while saving the box, then places it inside a `lateximage` when used:

```

49 \renewcommand*\savestack[2]{%
50   \xdef\sv@name{\stack@macro@name{#1}}%
51   \@ifundefined{sv@name content}{%
52     \expandafter\newsavebox\expandafter{\csname\sv@name content\endcsname}%
53     }{}%
54   \begingroup%      lwarp
55     \LWR@restoreorigformatting%      lwarp
56     \RenewDocumentEnvironment{lateximage}{s o s o d()}{}{} lwarp: inside group
57     \expandafter\LWR@gsavebox\csname\sv@name content\endcsname{#2}%
58     \expandafter\gdef\expandafter#1\expandafter{%
59       \expandafter\begin\expandafter{lateximage\expandafter}%      lwarp
60       \expandafter\usebox\expandafter%
61       {\csname\sv@name content\endcsname}%
62       \expandafter\end\expandafter{lateximage\expandafter}%      lwarp
63     }%
64     \endgroup%      lwarp
65 }

```

File 467 **lwarp-stackrel.sty**

§ 576 Package **stackrel**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg stackrel

stackrel is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{stackrel}[2016/05/16]
2 \begin{warpMathJax}
3 \CustomizeMathJax{\renewcommand{\stackrel}[3][[]]{%
4   \mathrel{\mathop{#3}\limits_{#1}^{#2}}}%
5 }}
6
7 \CustomizeMathJax{\newcommand{\stackbin}[3][[]]{%
8   \mathbin{\mathop{#3}\limits_{#1}^{#2}}}%
9 }}
10 \end{warpMathJax}

```

File 468 **lwarp-statem2.sty**

§ 577 Package **statex2**

(Emulates or patches code by RODNEY A SPARAPANL.)

Pkg statex2

statex2 is patched for use by lwarp, and emulated for MATHJAX.

⚠ As of this version, option autobold does not appear to work for PDF output.

⚠ For MATHJAX, the tilde character ~ does not create \sim. Use \sim directly.

⚠ Because MATHJAX has limited conditional processing:

- \wrap only creates square braces, no matter what its optional arguments.
- \P, \pCau, \pN, and \pU do not handle special cases.

⚠ **\and** To have \and work if using \maketitle, place the following after the start of the document:

```
\newcommand*\and{%
  \relax\ifmmode
    \expandafter\;\mb{\mathrm{and}}\;%
  \else%
    \expandafter\STATEXand%
  \fi%
}
```

for HTML output:

```
1 \LWR@ProvidesPackagePass{statex2}[2011/09/14]
2 \newcommand*\LWR@HTML@Alpha}[1][{}]{%
3   \fcolorbox{black}{ForestGreen}{\textcolor{white}{\textsf{ALPHA}}}%
4   \textbf{\textcolor{ForestGreen}{\textsf{#1}}}%
5 }
6 \LWR@formatted{Alpha}
7
8 \newcommand*\LWR@HTML@List}[1][{}]{%
9   \textbf{\textcolor{Dandelion}{\textsf{L}}\textsubscript{\textit{#1}}}%
10 }
11 \LWR@formatted{List}
12
13 \newcommand*\LWR@HTML@Snd}[1][{}]{%
14   \fcolorbox{black}{Dandelion}{\textcolor{white}{\textsf{2nd}}}%
15   \textbf{\textcolor{Dandelion}{\textsf{#1}}}%
16 }
17 \LWR@formatted{Snd}
18
19 \begin{warpMathJax}
20 \LWR@infoprocessingmathjax{statex2}
21
22 \CustomizeMathJax{\newcommand{\cpi}{\boldsymbol{\pi}}}
23 \CustomizeMathJax{\newcommand{\c}[1]{\boldsymbol{\mathrm{#1}}}}
```

```

24 \CustomizeMathJax{\newcommand{\sfsl}[1]{\mathsf{#1}}%      not slanted
25
26 \if@manualbold
27 \CustomizeMathJax{\newcommand{\mb}[1]{#1}}
28 \else
29 \CustomizeMathJax{\newcommand{\mb}[1]{\boldsymbol{#1}}}
30 \fi
31
32 \CustomizeMathJax{\newcommand{\diag}{\mb{\mathrm{diag}}}}
33 \CustomizeMathJax{\newcommand{\blockdiag}{\mb{\mathrm{blockdiag}}}}
34 \CustomizeMathJax{\newcommand{\verf}{\mb{\mathrm{erf}}}}
35 \CustomizeMathJax{\newcommand{\logit}{\mb{\mathrm{logit}}}}
36 \CustomizeMathJax{\newcommand{\trace}{\mb{\mathrm{trace}}}}
37
38 \CustomizeMathJax{\newcommand{\chisq}{\mb{\chi^2}}}
39 \CustomizeMathJax{\newcommand{\deriv}[2]{\mb{\frac{d}{d{#1}}}\wrap{\mb{#2}}}}
40 \CustomizeMathJax{\newcommand{\derivf}[2]{\mb{\frac{d}{d{#2}}}\wrap{\mb{#1}}}}
41 \CustomizeMathJax{\newcommand{\e}[1]{\mb{\mathrm{e}^{#1}}}}
42 \CustomizeMathJax{\newcommand{\E}[2][\mb{\mathrm{E}}_{\mb{#1}} \wrap{\mb{#2}}}}
43 \CustomizeMathJax{\newcommand{\ha}{\mb{\frac{\alpha}{2}}}}
44 \CustomizeMathJax{\newcommand{\I}[2][\%
45   \mb{\mathrm{I}}_{\mb{#1}} \LWRwrapparen{\mb{#2}}}%
46 ]}
47 \CustomizeMathJax{\newcommand{\IBeta}[2][\%
48   \mb{\frac{\Gamma[#+#2]}{\Gamma[#+1]\Gamma[#+2]}}}%
49 ]}
50 \CustomizeMathJax{\newcommand{\If}{\; \mb{\mathrm{if}}\; \; \;}
51 \CustomizeMathJax{\newcommand{\im}{\mb{\mathrm{i}}}}
52 \CustomizeMathJax{\newcommand{\ol}{\overline{}}}
53 \CustomizeMathJax{\newcommand{\ow}{\; \mb{\mathrm{otherwise}}\; \; \;}
54 \CustomizeMathJax{\newcommand{\pderiv}[2][\%
55   \mb{\frac{\partial}{\partial #1}}\wrap{\mb{#2}}}%
56 ]}
57 \CustomizeMathJax{\newcommand{\pderivf}[2][\%
58   \mb{\frac{\partial}{\partial #2}}\wrap{\mb{#1}}}%
59 ]}
60 \CustomizeMathJax{\newcommand{\sd}{\mb{\sigma}}}
61 \CustomizeMathJax{\newcommand{\ul}{\underline{}}}
62 \CustomizeMathJax{\newcommand{\V}[2][\mb{\mathrm{V}}_{\mb{#1}} \wrap{\mb{#2}}}}
63 \CustomizeMathJax{\newcommand{\vs}{\; \mb{\mathrm{vs.}}\; \; \;}
64 \CustomizeMathJax{\newcommand{\where}{\; \mb{\mathrm{where}}\; \; \;}
65 \CustomizeMathJax{\newcommand{\wrap}[2][\left[ #2 \right]]}%      only []
66 \CustomizeMathJax{\newcommand{\LWRwrapparen}[1]{\left( #1 \right)}}% lwarp
67
68 % \CustomizeMathJax{\renewcommand{\sim}{\mb{\sim}}}% doesn't work,
69 % replace <space>~<space> with <space>\sim<space>
70
71 \CustomizeMathJax{\newcommand{\iid}{\; \stackrel{\mb{\mathrm{iid}}}{\mb{\sim}}\; \;}
72 \CustomizeMathJax{\newcommand{\ind}{\; \stackrel{\mb{\mathrm{ind}}}{\mb{\sim}}\; \;}
73 \CustomizeMathJax{\newcommand{\indpr}{\%
74   \; \stackrel{\mb{\mathrm{ind}}}{\mb{\sim}}\stackrel{\mb{\mathrm{prior}}}{\mb{\sim}}\; \;}
75 ]}
76 \CustomizeMathJax{\newcommand{\post}{\; \stackrel{\mb{\mathrm{post}}}{\mb{\sim}}\; \;}
77 \CustomizeMathJax{\newcommand{\prior}{\; \stackrel{\mb{\mathrm{prior}}}{\mb{\sim}}\; \;}
78
79 \CustomizeMathJax{\let\STATEXGamma=\Gamma}
80 \CustomizeMathJax{\renewcommand{\Gamma}[1][\mb{\STATEXGamma}\LWRwrapparen{\mb{#1}}}}
81 %
82 \CustomizeMathJax{\renewcommand{\and}{\; \mb{\mathrm{and}}\; \; \;}
83 %

```

```

84 \CustomizeMathJax{\newcommand{\H}{\mb{\mathrm{H}}}}
85 %
86 \CustomizeMathJax{\newcommand{\P}[2][\mb{\mathrm{P}}_{\mb{\#1}}\wrap{\mb{\#2}}}}
87 %
88 \CustomizeMathJax{\newcommand{\|}{\mb{\mid}}}
89
90 \CustomizeMathJax{\newcommand{\B}[1]{\mb{\mathrm{B}}\LWRwrapparen{\mb{\#1}}}}
91 \CustomizeMathJax{\newcommand{\BB}[1]{\mb{\mathrm{BetaBin}}\LWRwrapparen{\mb{\#1}}}}
92 \CustomizeMathJax{\newcommand{\Bin}[2]{\mb{\mathrm{Bin}}\LWRwrapparen{\mb{\#1}, \ #2}}}
93 \CustomizeMathJax{\newcommand{\Dir}[1]{\mb{\mathrm{Dirichlet}}\LWRwrapparen{\mb{\#1}}}}
94 \CustomizeMathJax{\newcommand{\HG}[3]{%
95   \mb{\mathrm{Hypergeometric}}\LWRwrapparen{\mb{\#1}, \ #2, \ #3}}%
96 }}
97 \CustomizeMathJax{\newcommand{\M}[2]{%
98   \mb{\mathrm{Multinomial}}\LWRwrapparen{\mb{\#1}, \ #2}}%
99 }}
100 \CustomizeMathJax{\newcommand{\NB}[2]{\mb{\mathrm{NegBin}}\LWRwrapparen{\mb{\#1}, \ #2}}}
101 \CustomizeMathJax{\newcommand{\Poi}[1]{\mb{\mathrm{Poisson}}\LWRwrapparen{\mb{\#1}}}}
102 \CustomizeMathJax{\let\Poisson=\Poi}
103
104 \CustomizeMathJax{\newcommand{\pBB}[4][x]{%
105   \mb{\frac{\Gamma[\#2+1]\Gamma[\#3+\#1]\Gamma[\#2+\#4-\#1]\Gamma[\#3+\#4]}
106     {\Gamma[\#1+1]\Gamma[\#2-\#1+1]\Gamma[\#2+\#3+\#4]\Gamma[\#3]\Gamma[\#4]}}%
107   \I[\#1]{\{0, 1, \., \ #2\}}, \where \#3>0, \; \#4>0 \and n=1, 2, \.}%
108 }}
109 \CustomizeMathJax{\newcommand{\pBin}[3][x]{%
110   \mb{\binom{\#2}{\#1}\#3^{\#1}} \LWRwrapparen{\mb{\{1-\#3\}^{\#2-\#1}}}%
111   \mb{\I[\#1]{\{0, 1, \., \ #2\}}, \where p \in (0, 1) \and n=1, 2, \.}%
112 }}
113 \CustomizeMathJax{\newcommand{\pPoi}[2][x]{%
114   \mb{\frac{1}{\#1!}\#2^{\#1}\e^{-\#2}\I[\#1]{\{0, 1, \. \}}, \where \#2>0}}%
115 }}
116
117 \CustomizeMathJax{\newcommand{\Cau}[2]{\mb{\mathrm{Cauchy}}\LWRwrapparen{\mb{\#1}, \ #2}}}}
118 \CustomizeMathJax{\let\Cauchy=\Cau}
119 \CustomizeMathJax{\newcommand{\Chi}[2][x]{%
120   \chisq_{\mb{\#1}}\LWRwrapparen{\mb{\#2}}}%
121 }}
122 \CustomizeMathJax{\let\Chisq=\Chi}
123 \CustomizeMathJax{\newcommand{\Bet}[2]{\mb{\mathrm{Beta}}\LWRwrapparen{\mb{\#1}, \ #2}}}}
124 \CustomizeMathJax{\let\Beta=\Bet}
125 \CustomizeMathJax{\newcommand{\Exp}[1]{\mb{\mathrm{Exp}}\LWRwrapparen{\mb{\#1}}}}
126 \CustomizeMathJax{\newcommand{\F}[2]{\mb{\mathrm{F}}\LWRwrapparen{\mb{\#1}, \ #2}}}}
127 \CustomizeMathJax{\newcommand{\Gam}[2]{\mb{\mathrm{Gamma}}\LWRwrapparen{\mb{\#1}, \ #2}}}}
128 \CustomizeMathJax{\newcommand{\IC}[1]{\mb{\mathrm{\chi^{-2}}}\LWRwrapparen{\mb{\#1}}}}
129 \CustomizeMathJax{\newcommand{\IG}[2]{%
130   \mb{\mathrm{Gamma}^{-1}}\LWRwrapparen{\mb{\#1}, \ #2}}%
131 }}
132 \CustomizeMathJax{\newcommand{\IW}[2]{%
133   \mb{\mathrm{Wishart}^{-1}}\LWRwrapparen{\mb{\#1}, \ #2}}%
134 }}
135 \CustomizeMathJax{\newcommand{\Log}[2]{%
136   \mb{\mathrm{Logistic}}\LWRwrapparen{\mb{\#1}, \ #2}}%
137 }}
138 \CustomizeMathJax{\newcommand{\LogN}[2]{%
139   \mb{\mathrm{Log}!\-!N}\LWRwrapparen{\mb{\#1}, \ #2}}%
140 }}
141 \CustomizeMathJax{\newcommand{\N}[3][x]{%
142   \mb{\mathrm{N}}_{\mb{\#1}}\LWRwrapparen{\mb{\#2}, \ #3}}%
143 }}

```

```

144 \CustomizeMathJax{\newcommand{\Par}[2]{\mb{\mathrm{Pareto}}\LWRwrapparen{\mb{#1, \ #2}}}}
145 \CustomizeMathJax{\let\Pareto=\Par}
146 \CustomizeMathJax{\newcommand{\Tsq}[2]{\mb{\mathrm{T}^2}}\LWRwrapparen{\mb{#1, \ #2}}}}
147 \CustomizeMathJax{\newcommand{\U}[1]{\mb{\mathrm{U}}\LWRwrapparen{\mb{#1}}}}
148 \CustomizeMathJax{\newcommand{\W}[2]{\mb{\mathrm{Wishart}}\LWRwrapparen{\mb{#1, \ #2}}}}
149
150 \CustomizeMathJax{\renewcommand{\t}[1]{\mb{\mathrm{t}}\LWRwrapparen{\mb{#1}}}}
151
152 \CustomizeMathJax{\newcommand{\pBet}[3][x]{%
153   \IBeta{#2}{#3}%
154   #1^{#2-1}\LWRwrapparen{#1-#1}^{#3-1}\I[#1]{0, \ 1}, \where #2>0 \and #3>0%
155 }}
156 \CustomizeMathJax{\newcommand{\pCau}[3][x]{%
157 %   \ifthenelse{\equal{#2, #3}{0, 1}}{\frac{1}{\cpi}\LWRwrapparen{1+#1}^2}}%
158   {\frac{1}{#3\cpi}\left\{1+\wrap{\LWRwrapparen{x-#2}/#3}^2\right\}}, \where #3>0}%
159 }}% no special case for 0,1
160 \CustomizeMathJax{\newcommand{\pChi}[2][x]{%
161   \frac{2^{-#2/2}}{\Gamma[#2/2]}#1^{#2/2-1}\e^{-#1/2}%
162   \I[#1]{0, \infty}, \where #2>0%
163 }}
164 \CustomizeMathJax{\newcommand{\pExp}[2][x]{%
165   \frac{1}{#2}\e^{-#1/#2}\I[#1]{0, \infty},%
166   \where #2>0%
167 }}
168 \CustomizeMathJax{\newcommand{\pGam}[3][x]{%
169   \frac{#3^{#2}}{\Gamma[#2]}#1^{#2-1}\e^{-#3#1}%
170   \I[#1]{0, \infty}, \where #2>0 \and #3>0%
171 }}
172 \CustomizeMathJax{\newcommand{\pN}[3][x]{%
173 %   \ifthenelse{\equal{#2, #3}{0, 1}}%
174 %   {\frac{1}{\sqrt{2\cpi}}\e^{-#1^2/2}}%
175   {\frac{1}{\sqrt{2\cpi \cdot #3}}\e^{-\LWRwrapparen{#1-#2}^2/2 \cdot #3}}%
176 }}% no test for 0,1, must add \cdot
177 \CustomizeMathJax{\newcommand{\pPar}[3][x]{%
178   \frac{#3}{#2}\LWRwrapparen{1+#1/#2}^{#3+1}\I[#1]{0, \infty},%
179   \where #2>0 \and #3>0%
180 }}
181 \CustomizeMathJax{\newcommand{\pU}[3][x]{%
182 %   \ifthenelse{\equal{#2, #3}{0, 1}}{\I[#1]{0, \ 1}}%
183   {\frac{1}{#3-#2}\I[#1]{#2, \ #3}, \where #2<#3}%
184 }}% no special case for 0,1
185
186 \CustomizeMathJax{\newcommand{\=} [1]{\bar{#1}}}
187 \CustomizeMathJax{\let\^{\widehat}}
188 \CustomizeMathJax{\let\~{\widetilde}}
189 \CustomizeMathJax{\newcommand{\'} [1]{\LWRwrapparen{\mb{#1}}}}
190 \CustomizeMathJax{\newcommand{\b} [1]{\bar{#1}}}
191 \CustomizeMathJax{\newcommand{\c} [1]{\mb{\mathrm{#1}}}}
192 \CustomizeMathJax{\newcommand{\d} [1]{\, \mb{\mathrm{d}}{#1}}}
193 \CustomizeMathJax{\newcommand{\.} {\mb{\ldots}}}
194 \end{warpMathJax}

```

File 469 **lwarp-statistics.sty**

§ 578 Package **statistics**

(Emulates or patches code by JULIEN RIVAUD.)

Pkg statistics

statistics is patched for use by lwarp.

⚠ `\color` The statistics documentation examples include the use of the `\color` macro. Use `\textcolor` instead.

⚠ `math` The statistics package uses math arrays, but the HTML version uses text tabulars to allow text copy/paste. If math is required, use `\ensuremath` or `\(` and `\)` as needed.

Pre/postline is ignored, and `\hline` is used instead. Each table will have an `\hline` above and below as a frame.

for HTML output:

```
1 \LWR@ProvidesPackagePass{statistics}[2019/09/29]
2 \ExplSyntaxOn
```

To use text tabular instead of math array. This allows text copy/paste of the results.

In the following, all changes for the Lwarp package are labelled "lwarp".

Redefined using the lwarp version of &:

```
3 \StartDefiningTabulars%      lwarp
4 \cs_set_protected_nopar:Nn \__statistics_table_make:nn {
5   \int_compare:nT
6     { 0 < \l__statistics_table_maxcols_int
7       = \l__statistics_nbvals_int } {
8     \__statistics_table_end:
9     \tl_use:N \l__statistics_table_sep_tl
10    \__statistics_table_start:
11   }
12   \int_incr:N \l__statistics_nbvals_int
13   \int_incr:N \l__statistics_currange_int
14   \fp_add:Nn \l__statistics_curtotal_fp { #2 }
15   \__statistics_set_if_shown:N \l_tmpa_bool
16   \tl_set:Nx \l_tmpa_tl {
17     \exp_not:n { & \tl_set:Nn \currentcolumn } {
18       \int_use:N \l__statistics_currange_int
19     }
20   }
21   \bool_if:NTF \l_tmpa_bool {
22     \tl_put_right:Nn \l_tmpa_tl
23       { \__statistics_table_shown_format:n }
24   } {
25     \tl_put_right:Nn \l_tmpa_tl
26       { \__statistics_table_hidden_format:n }
27   }
28   \seq_put_right:Nn \l__statistics_store_values_seq { #1 }
29   \bool_if:NT \l__statistics_table_values_bool {
30     \tl_put_right:Nx \l__statistics_table_values_tl {
31       \exp_not:V \l_tmpa_tl {
32         \exp_not:n {
33           \__statistics_table_values_format:n { #1 }
34         }
35       }
36     }
37   }
38   \seq_put_right:Nx \l__statistics_store_counts_seq { \fp_eval:n {#2} }
39   \bool_if:NT \l__statistics_table_counts_bool {
```

```

40     \tl_put_right:Nx \l__statistics_table_counts_tl {
41         \exp_not:V \l_tmpa_tl {
42             \exp_not:n {
43                 \__statistics_table_counts_format:n {
44                     { \__statistics_table_allcounts_format:n { #2 } }
45                 }
46             }
47         }
48     }
49 }
50 \bool_if:NT \l__statistics_table_icc_bool {
51     \tl_put_right:Nx \l__statistics_table_icc_tl {
52         \exp_not:V \l_tmpa_tl {
53             \exp_not:n { \__statistics_table_icc_format:n }
54             {
55                 \exp_not:n{ \__statistics_table_allcounts_format:n }
56                 { \fp_use:N \l__statistics_curtotal_fp }
57             }
58         }
59     }
60 }
61 \bool_if:NT \l__statistics_table_dcc_bool {
62     \tl_put_right:Nx \l__statistics_table_dcc_tl {
63         \exp_not:V \l_tmpa_tl {
64             \exp_not:n { \__statistics_table_dcc_format:n }
65             {
66                 \exp_not:n{ \__statistics_table_allcounts_format:n }
67                 {
68                     \fp_eval:n {
69                         \l__statistics_total_fp
70                         - \l__statistics_curtotal_fp
71                         + #2
72                     }
73                 }
74             }
75         }
76     }
77 }
78 \fp_set:Nn \l__statistics_table_curICF_fp {
79     round(\l__statistics_curtotal_fp
80         / \l__statistics_total_fp,
81         \l__statistics_table_round_int)
82 }
83 \bool_if:NT \l__statistics_table_frequencies_bool {
84     \tl_put_right:Nx \l__statistics_table_frequencies_tl {
85         \exp_not:V \l_tmpa_tl {
86             \exp_not:n { \__statistics_table_frequencies_format:n }
87             {
88                 \exp_not:n{ \__statistics_table_allfreqs_format:n }
89                 {
90                     \fp_eval:n {
91                         \l__statistics_table_curICF_fp
92                         - \l__statistics_table_prevICF_fp
93                     }
94                 }
95             }
96         }
97     }
98 }
99 \bool_if:NT \l__statistics_table_icf_bool {

```

```

100     \tl_put_right:Nx \l__statistics_table_icf_tl {
101         \exp_not:V \l_tmpa_tl {
102             \exp_not:n { \l__statistics_table_icf_format:n }
103             {
104                 \exp_not:n{ \l__statistics_table_allfreqs_format:n }
105                 { \fp_to_decimal:N \l__statistics_table_curICF_fp }
106             }
107         }
108     }
109 }
110 \bool_if:NT \l__statistics_table_dcf_bool {
111     \tl_put_right:Nx \l__statistics_table_dcf_tl {
112         \exp_not:V \l_tmpa_tl {
113             \exp_not:n { \l__statistics_table_dcf_format:n }
114             {
115                 \exp_not:n{ \l__statistics_table_allfreqs_format:n }
116                 {
117                     \fp_eval:n {
118                         1 - \l__statistics_table_prevICF_fp
119                     }
120                 }
121             }
122         }
123     }
124 }
125 \fp_set_eq:NN
126     \l__statistics_table_prevICF_fp
127     \l__statistics_table_curICF_fp
128 }
129 \StopDefiningTabulars% lwarp

```

Redefined using tabular. Also, preline and postline do not work correctly with lwarp, which looks for certain tokens to detect \hlines, so \hline is used instead.

```

130 \cs_set_protected_nopar:Nn \l__statistics_table_end: {
131     \tl_set:Nx \l__statistics_table_preamble_tl {
132 %         \exp_not:n { \begin{array}[ ] }
133         \exp_not:n { \begin{tabular}[ ] }% lwarp
134         \exp_not:V \l__statistics_table_valign_tl
135         \exp_not:n { ] }
136         { \exp_not:V \l__statistics_table_headcoltype_tl
137           \prg_replicate:nn { \l__statistics_nbvals_int }
138           { \exp_not:V \l__statistics_table_coltype_tl } }
139     }
140     \seq_clear:N \l__statistics_table_contents_seq
141     \clist_map_inline:nn { values, counts, icc, dcc, frequencies, icf, dcf } {
142         \bool_if:cT { l__statistics_table_##1_bool } {
143             \seq_put_right:Nv
144                 \l__statistics_table_contents_seq
145                 { l__statistics_table_##1_tl }
146         }
147     }
148 %     $
149     \tl_use:N \l__statistics_table_preamble_tl
150     \hline% lwarp
151 %     \l__statistics_table_preline_tl
152     \seq_use:Nn
153         \l__statistics_table_contents_seq
154         { \l__statistics_table_newline_tl }
155     \\\

```

```

156 %      \l__statistics_table_postline_tl
157      \hline%      lwarp
158 %      \end{array}$
159      \end{tabular}%      lwarp
160 }

```

With `lwarp`, `\ensuremath` creates an SVG image, but its `alt` tag does not contain the text of the contents for copy/paste, since these expressions are usually not simple text. For the statistics package, copy/paste is restored by using text instead of math output.

For the leftmost column. Redefined to use text output:

```

161 \cs_set_protected_nopar:Nn \l__statistics_table_start: {
162   \int_zero:N \l__statistics_nbvals_int
163   \clist_pop:NNT \l__statistics_table_maxcols_clist \l_tmpa_tl {
164     \int_set:Nn \l__statistics_table_maxcols_int { \l_tmpa_tl }
165   }
166   \clist_map_inline:nn { values, counts, frequencies, icc, icf, dcc, dcf } {
167     \tl_set:cx { l__statistics_table_##1_tl } {
168 %       \exp_not:N \ensuremath {
169         \exp_not:N \hbox {
170           \exp_not:c { l__statistics_table_##1_name_tl }
171         }
172 %     }
173   }
174 }
175 }

```

For the first row. Redefined to use text output:

```

176 \RenewDocumentCommand \l__statistics_IN:w { m u{;} u{;} m } {
177 %   \ensuremath{ \left#1 \num{#2} \mathbin{;} \num{#3} \right#4 }
178   #1 #2 ; #3 #4%      lwarp
179 }
180
181 \l__statistics_setup:nn { table } {
182 %   values/format = \ensuremath{#1},
183   values/format = {#1},%      lwarp
184 }

```

Added `\ExplSyntaxOn/Off` to avoid errors. (In once instance, a double subscript error appeared.)

```

185 \RenewDocumentCommand \StatsGraph { +O{} +m +O{} } {
186   \group_begin:
187   \int_gincr:N \g__statistics_graph_last_int
188   \tl_set:Nx \l_tmpa_tl {
189     \exp_not:n { g__statistics_graph_xstep_ }
190     \int_use:N \g__statistics_graph_last_int
191     \exp_not:n { _tl }
192   }
193   \tl_if_exist:cTF { \l_tmpa_tl } {
194     \fp_gset:Nn \g__statistics_graph_xstep_fp
195       { \tl_use:c { \l_tmpa_tl } }
196   }{
197     \fp_gset:Nn \g__statistics_graph_xstep_fp { \c_one_int }
198   }
199   \l__statistics_setup:nn { graph } { #1, #3 }

```

```

200 \tl_if_single:nTF { #2 } {
201   \cs_if_exist:NF #2 { #2 }
202   \tl_set_eq:NN \l__statistics_data_tl #2
203 }{
204   \tl_set:Nn \l__statistics_data_tl { #2 }
205 }
206 \fp_zero:N \l__statistics_graph_maxheight_fp
207 \fp_set:Nn \l__statistics_graph_minvalue_fp {inf}
208 \fp_set:Nn \l__statistics_graph_maxvalue_fp {-inf}
209 \fp_zero:N \l__statistics_total_fp
210 \int_zero:N \l__statistics_nbvals_int
211 \bool_set_true:N \l__statistics_graph_allranges_bool
212 \keyval_parse:NNV
213   \__statistics_graph_prepare:n
214   \__statistics_graph_prepare:nn
215   \l__statistics_data_tl
216 \tl_clear:N \l__statistics_graph_tikzdata_tl
217 \tl_clear:N \l__statistics_graph_tikzinfo_tl
218 \int_zero:N \l__statistics_currange_int
219 \bool_if:NTF \l__statistics_graph_allranges_bool {
220   \bool_if:NTF \l__statistics_graph_cumulative_bool {
221 \ExplSyntaxOn%   lwarp
222   \__statistics_graph_dopicture_cumulative:
223 \ExplSyntaxOff%   lwarp
224   }{
225 \ExplSyntaxOn%   lwarp
226   \__statistics_graph_dopicture_hist:
227 \ExplSyntaxOff%   lwarp
228   }
229 }{
230 \ExplSyntaxOn%   lwarp
231   \__statistics_graph_dopicture_comb:
232 \ExplSyntaxOff%   lwarp
233   }
234 \iow_now:Nx \@auxout {
235   \exp_not:n {
236     \ExplSyntaxOn
237     \tl_gset:cn
238   }
239   {
240     \exp_not:n {g__statistics_graph_xstep_}
241     \int_use:N \g__statistics_graph_last_int
242     \exp_not:n {_tl}
243   }
244   {
245     \fp_to_decimal:N \g__statistics_graph_xstep_fp
246   }
247   \exp_not:n {
248     \ExplSyntaxOff
249   }
250 }
251 \group_end:
252 }
253
254 \ExplSyntaxOff

```

File 470 **lwarp-statmath.sty**

§ 579 Package **statmath**

(Emulates or patches code by SEBASTIAN ANKARGREN.)

Pkg statmath

statmath is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{statmath}[2018/03/08]
2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{statmath}
6
7 \ifdefequal{\abcbf}{\mathbf}
8   {\CustomizeMathJax{\newcommand{\abcbf}[1]{\mathbf{#1}}}}
9   {\CustomizeMathJax{\newcommand{\abcbf}[1]{\boldsymbol{#1}}}}
10
11 \CustomizeMathJax{\newcommand{\greekbf}[1]{\boldsymbol{#1}}}
12
13 \CustomizeMathJax{\newcommand{\bfA}{\abcbf A}}
14 \CustomizeMathJax{\newcommand{\bfB}{\abcbf B}}
15 \CustomizeMathJax{\newcommand{\bfC}{\abcbf C}}
16 \CustomizeMathJax{\newcommand{\bfD}{\abcbf D}}
17 \CustomizeMathJax{\newcommand{\bfE}{\abcbf E}}
18 \CustomizeMathJax{\newcommand{\bfF}{\abcbf F}}
19 \CustomizeMathJax{\newcommand{\bfG}{\abcbf G}}
20 \CustomizeMathJax{\newcommand{\bfH}{\abcbf H}}
21 \CustomizeMathJax{\newcommand{\bfI}{\abcbf I}}
22 \CustomizeMathJax{\newcommand{\bfJ}{\abcbf J}}
23 \CustomizeMathJax{\newcommand{\bfK}{\abcbf K}}
24 \CustomizeMathJax{\newcommand{\bfL}{\abcbf L}}
25 \CustomizeMathJax{\newcommand{\bfM}{\abcbf M}}
26 \CustomizeMathJax{\newcommand{\bfN}{\abcbf N}}
27 \CustomizeMathJax{\newcommand{\bfO}{\abcbf O}}
28 \CustomizeMathJax{\newcommand{\bfP}{\abcbf P}}
29 \CustomizeMathJax{\newcommand{\bfQ}{\abcbf Q}}
30 \CustomizeMathJax{\newcommand{\bfR}{\abcbf R}}
31 \CustomizeMathJax{\newcommand{\bfS}{\abcbf S}}
32 \CustomizeMathJax{\newcommand{\bfT}{\abcbf T}}
33 \CustomizeMathJax{\newcommand{\bfU}{\abcbf U}}
34 \CustomizeMathJax{\newcommand{\bfV}{\abcbf V}}
35 \CustomizeMathJax{\newcommand{\bfW}{\abcbf W}}
36 \CustomizeMathJax{\newcommand{\bfX}{\abcbf X}}
37 \CustomizeMathJax{\newcommand{\bfY}{\abcbf Y}}
38 \CustomizeMathJax{\newcommand{\bfZ}{\abcbf Z}}
39 \CustomizeMathJax{\newcommand{\bfa}{\abcbf a}}
40 \CustomizeMathJax{\newcommand{\bfb}{\abcbf b}}
41 \CustomizeMathJax{\newcommand{\bfc}{\abcbf c}}
42 \CustomizeMathJax{\newcommand{\bfd}{\abcbf d}}
43 \CustomizeMathJax{\newcommand{\bfe}{\abcbf e}}
44 \CustomizeMathJax{\newcommand{\bff}{\abcbf f}}
45 \CustomizeMathJax{\newcommand{\bfg}{\abcbf g}}
46 \CustomizeMathJax{\newcommand{\bfh}{\abcbf h}}
47 \CustomizeMathJax{\newcommand{\bf i}{\abcbf i}}

```

```

48 \CustomizeMathJax{\newcommand{\bfj}{\abcbf j}}
49 \CustomizeMathJax{\newcommand{\bfk}{\abcbf k}}
50 \CustomizeMathJax{\newcommand{\bfl}{\abcbf l}}
51 \CustomizeMathJax{\newcommand{\bfm}{\abcbf m}}
52 \CustomizeMathJax{\newcommand{\bfn}{\abcbf n}}
53 \CustomizeMathJax{\newcommand{\bfo}{\abcbf o}}
54 \CustomizeMathJax{\newcommand{\bfp}{\abcbf p}}
55 \CustomizeMathJax{\newcommand{\bfq}{\abcbf q}}
56 \CustomizeMathJax{\newcommand{\bfr}{\abcbf r}}
57 \CustomizeMathJax{\newcommand{\bfs}{\abcbf s}}
58 \CustomizeMathJax{\newcommand{\bft}{\abcbf t}}
59 \CustomizeMathJax{\newcommand{\bfu}{\abcbf u}}
60 \CustomizeMathJax{\newcommand{\bfv}{\abcbf v}}
61 \CustomizeMathJax{\newcommand{\bfw}{\abcbf w}}
62 \CustomizeMathJax{\newcommand{\bfx}{\abcbf x}}
63 \CustomizeMathJax{\newcommand{\bfy}{\abcbf y}}
64 \CustomizeMathJax{\newcommand{\bfz}{\abcbf z}}
65
66 \LWR@mathjax@addgreek@l@bfit{bf}{\}% Greek lowercase bold face italic
67 \LWR@mathjax@addgreek@u@bfup*{bf}{\}% Greek uppercase bold face upright, cap macros.
68
69 \CustomizeMathJax{\newcommand{\bfzero}{\greekbf 0}}
70
71 \CustomizeMathJax{\DeclareMathOperator{\cov}{Cov}}
72 \CustomizeMathJax{\DeclareMathOperator{\E}{E}}
73 \CustomizeMathJax{\DeclareMathOperator{\V}{V}}
74 \CustomizeMathJax{\newcommand{\inas}{\overset{a. s.}{\to}}}
75 \CustomizeMathJax{\newcommand{\indist}{\overset{d}{\to}}}
76 \CustomizeMathJax{\newcommand{\inprob}{\overset{p}{\to}}}
77 \CustomizeMathJax{\DeclareMathOperator{\plim}{plim}}
78 \CustomizeMathJax{\DeclareMathOperator{\tr}{tr}}
79 \CustomizeMathJax{\DeclareMathOperator{\vc}{vec}}
80 \CustomizeMathJax{\DeclareMathOperator{\vcs}{vecs}}
81 \CustomizeMathJax{\DeclareMathOperator{\vch}{vech}}
82 \CustomizeMathJax{\DeclareMathOperator{\diag}{diag}}
83 \CustomizeMathJax{\DeclareMathOperator{\argmin}{arg\,min}}
84 \CustomizeMathJax{\DeclareMathOperator{\argmax}{arg\,max}}
85 \end{warpMathJax}

```

File 471 **lwarp-steinmetz.sty**

§ 580 Package **steinmetz**

(Emulates or patches code by ENRICO GREGORIO.)

Pkg steinmetz

steinmetz is patched for use by lwarp. Emulation is provided for MATHJAX

for HTML output:

```

1 \LWR@ProvidesPackagePass{steinmetz}[2009/06/14]
2 \renewcommand{\phase}[2][\%
3   \begin{lateximage}*{steinmetz\{\detokenize{#2}\}}
4   \ensuremath{\underline{/#2}}
5   \end{lateximage}
6 }
7
8 \begin{warpMathJax}
9 \CustomizeMathJax{\newcommand{\phase}[2][\underline{/#2}}
10 \end{warpMathJax}

```

File 472 **lwarp-stfloats.sty**

§ 581 Package **stfloats**

Pkg stfloats

stfloats is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{stfloats}[2017/03/27]

stfloats may have been preloaded by a `ltj*` class.

The following are provided in case they have not yet been defined:

```
2 \providecommand*\fnbelowfloat{}
3 \providecommand*\fnunderfloat{}
4 \providecommand*\setbaselinefloat{}
5 \providecommand*\setbaselinefixed{}
```

Nullified for HTML:

```
6 \renewcommand*\fnbelowfloat{}
7 \renewcommand*\fnunderfloat{}
8 \renewcommand*\setbaselinefloat{}
9 \renewcommand*\setbaselinefixed{}
```

File 473 **lwarp-struktex.sty**

§ 582 Package **struktex**

(Emulates or patches code by JOBST HOFFMANN.)

Pkg struktex

struktex is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{struktex}

```
2 \BeforeBeginEnvironment{struktogramm}{%
3   \begin{lateximage}[-struktex-~\PackageDiagramAltText]%
4 }
5 \AfterEndEnvironment{struktogramm}{\end{lateximage}}
6
7 \newenvironment{LWR@HTML@centernss}{\begin{center}}{\end{center}}
8 \LWR@formattedenv{centernss}
9
10 \newcommand{\LWR@HTML@CenterNssFile}[1]{%
11   \begin{center}
12     \input{#1.nss}
13   \end{center}
14 }
15 \LWR@formatted{CenterNssFile}
16
17 \newcommand{\LWR@HTML@centernssfile}{\LWR@HTML@CenterNssFile}
18 \LWR@formatted{centernssfile}
```

File 474 **lwarp-subcaption.sty**

§ 583 Package **subcaption**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg subcaption subcaption is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{subcaption}[2018/05/01]

Tells **lwarp** to ignore minipage widths inside a subfigure or subtable. In print mode the minipages are used to place the items next to each other. In **HTML** they are placed side-by-side automatically.

```
2 \xpretocmd{\subcaption@iiminipage}
3   {\minipagefullwidth}
4   {}
5   {\LWR@patcherror{subcaption}{subcaption@iiminipage}}
```

Likewise for a `\subcaptionbox`:

```
6 \xpretocmd{\subcaptionbox}
7   {\minipagefullwidth}
8   {}
9   {\LWR@patcherror{subcaption}{subcaptionbox}}
```

File 475 **lwarp-subfig.sty**

§ 584 Package **subfig**

(Emulates or patches code by STEVEN DOUGLAS COCHRAN.)

Pkg subfig subfig is supported and patched by lwarp.

 **table numbering** To have correct sub table numbers:

```
\usepackage{caption}
\captionsetup[table]{position=top}
```

 **lof/lotdepth** At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

 **horizontal spacing** In the document source, use `\hfill` and `\hspace*` between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

for HTML output: Accept all options for **lwarp-subfig**:

```
1 \LWR@ProvidesPackagePass{subfig}[2005/06/28]
```

```
\sf@@@subfloat {<1 type>} [<2 lof entry>] [<3 caption>] {<4 contents>}
```

The outer minipage allows side-by-side subfloats with `\hfill` between.

```

2 \long\def\sfloat@@@subfloat#1[#2][#3]#4{%
3 \begin{minipage}{\linewidth}% lwarp

4 \IfValueTF{#2}{%
5   \LWR@setlatestname{#2}%
6 }{%
7   \IfValueTF{#3}{%
8     \LWR@setlatestname{#3}%
9   }{%
10 }%
11 \LWR@stoppars% lwarp
12 \ifundefined{FBsc@max}{%
13   {\FB@readaux{\let\FBsuboheight\relax}}%
14 \@tempcnta=\@ne
15 \ifminipage
16   \@tempcnta=\z@
17 \else\ifdim \lastskip=\z@ \else
18   \@tempcnta=\tw@
19 \fi\fi
20 \ifmaincaptiontop
21   \sf@top=\sf@nearskip
22   \sf@bottom=\sf@farskip
23 \else
24   \sf@top=\sf@farskip
25   \sf@bottom=\sf@nearskip
26 \fi
27 \leavevmode

28%   \setbox\@tempboxa \hbox{#4}%
29%   \@tempdima=\wd\@tempboxa
30%   \ifundefined{FBsc@max}{%
31%     {\global\advance\Xhsize-\wd\@tempboxa
32%       \dimen@=\ht\@tempboxa
33%       \advance\dimen@\dp\@tempboxa
34%       \ifdim\dimen@>\FBso@max
35%         \global\FBso@max\dimen@
36%       \fi}%

```

Do not use boxes, which interfere with `lateximages`:

```

37%   \vtop%
38 \bgroup
39%   \vbox%
40 \bgroup
41   \ifcase\@tempcnta
42     \@minipagefalse
43   \or
44%     \vskip\sf@top
45   \or
46     \ifdim \lastskip=\z@ \else
47%       \@tempkipb\sf@top\relax\@xaddvskip
48     \fi
49   \fi
50 \sf@ifpositiontop{%
51   \ifx \@empty#3\relax \else
52     \sf@subcaption{#1}{#2}{#3}%
53%     \vskip\sf@capskip
54%     \vskip\sf@captopadj
55   \fi\egroup

```

```

56 %           \hrule width0pt height0pt depth0pt
57             \LWR@startpars% lwarp
58 % \box\@tempboxa
59           #4
60           \LWR@stoppars% lwarp
61         }{%
62         \LWR@startpars% lwarp
63         \@ifundefined{FBsc@max}%
64         {
65 % \box\@tempboxa
66           #4
67         }%
68         {\ifx\FBsuboheight\relax
69 %           \box\@tempboxa
70           #4
71         \else
72 %           \vbox to \FBsuboheight{\FBafil\box\@tempboxa\FBbfil}%
73           #4
74         \fi}%
75       \LWR@stoppars% lwarp
76       \egroup
77       \ifx \@empty#3\relax \else
78 %         \vskip\sf@capskip
79 %         \hrule width0pt height0pt depth0pt
80 %         \sf@subcaption{#1}{#2}{#3}%
81       \fi
82     }%
83 %   \vskip\sf@bottom
84   \egroup
85   \@ifundefined{FBsc@max}{%
86     {\addtocounter{FRobj}{-1}%
87     \ifnum\c@FRobj=0\else
88       \subfloatrowsep
89     \fi}%
90   \ifmaincaptiontop\else
91     \global\advance\@nameuse{c@\@capttype}\m@ne
92   \fi
93 \end{minipage}% lwarp
94 \LWR@startpars% lwarp
95 \endgroup\ignorespaces%
96 }%

```

\sf@subcaption

{<1 type>} {<2 lof entry>} {<3 caption>}

```

97 \long\def\sf@subcaption#1#2#3{%
98 \LWR@stoppars% lwarp
99 \ifx \relax#2\relax \else
100   \bgroup
101     \let\label=\@gobble
102     \let\protect=\string
103     \def\@subcaplabel{%
104       \caption\lstfmt{\@nameuse{p@#1}}{\@nameuse{the#1}}}%
105     \sf@updatecaptionlist{#1}{#2}{\the\value{\@capttype}}{\the\value{#1}}%
106   \egroup
107   \fi
108   \bgroup
109   \ifx \relax#3\relax
110     \let\captionlabelsep=\relax
111   \fi
112 %   \setbox0\vbox{%

```

```

113 %      \hb@xt@\the\@tempdima{%
114 %
115 % %      \hss
116 % %      \parbox[t]{\the\@tempdima}{%
117 %      \caption@make
118 %          {\@nameuse{sub\@capttype name}}}%
119 %          {\@nameuse{thesub\@capttype}}}%
120 %          {#3}
121 % % }%
122 % %      \hss
123 % }
124 % }%
125 \@ifundefined{FBsc@max}%
126 %     {\box0}%
127 {
128 % \parbox[t]{\the\@tempdima}{%
129 \LWR@traceinfo{sfsubcap B1}%      lwarp
130     \LWR@figcaption%      lwarp
131     \caption@make
132         {\@nameuse{sub\@capttype name}}}%
133         {\@nameuse{thesub\@capttype}}}%
134         {\LWR@isolate{#3}}}%

135     \endLWR@figcaption%      lwarp
136 \LWR@traceinfo{sfsubcap B2}%      lwarp
137 % }%
138 }%
139 {\dimen@ht0%
140 \advance\dimen@dp0%
141 \ifdim\dimen@>\FBsc@max
142 \global\FBsc@max\dimen@
143 \fi
144 \FB@readaux{\let\FBsubcheight\relax}%
145 \ifx\FBsubcheight\relax
146 \def\next{
147 % \parbox[t]{\the\@tempdima}
148 }%
149 \else
150 \def\next{
151 % \parbox[t][\FBsubcheight][t]{\the\@tempdima}
152 }%
153 \fi
154 % \vbox{%
155 %     \hb@xt@\the\@tempdima{%
156
157 %         \hss
158 %         \next{%
159 \LWR@traceinfo{sfsubcap C1}% lwarp
160     \caption@make
161         {\@nameuse{sub\@capttype name}}}%
162         {\@nameuse{thesub\@capttype}}}%
163         {#3}
164 \LWR@traceinfo{sfsubcap C1}% lwarp
165 % }%
166 %     \hss
167
168 % }
169 % }
170 % }%
171 \egroup

```

```
172 \LWR@startpars% lwarp
173 }
```

`\subfloat@label`Patches for `\sf@sub@label`:

```
174 \xpretocmd{\subfloat@label}
175   {\LWR@ensuredoingapar}
176   {}
177   {\LWR@patcherror{subfig}{subfloat@label}}
```

Patches for `\subref`.`\sf@subref``{\langle label \rangle}`

The unstarred version uses a `\ref` link whose printed text comes from the `sub@<label>`:

```
178 \renewcommand{\sf@subref}[1]{%
179   \LWR@subnewref{#1}{sub@#1}%
180 }
```

`\sf@@subref``{\langle label \rangle}`

The starred version uses the printed `sub@<label>` which is stored as if it were a page number:

```
181 \renewcommand{\sf@@subref}[1]{\LWR@orig@pageref{sub@#1}}
```

Defining new subfloats. The `l@sub<type>` for each is redefined.

`\@newsubfloat``[{\langle keys/values \rangle}]{\langle float name \rangle}`

```
182 \LetLtxMacro\LWR@orig@newsubfloat\@newsubfloat
183
184 \def\@newsubfloat[#1]#2{%
185   \LWR@orig@newsubfloat[#1]{#2}%
186   \renewcommand{\l@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
187 }
```

Pre-defined for figures and tables:

`\l@subfigure``{\langle text \rangle}{\langle pagenum \rangle}`

```
188 \renewcommand{\l@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}
```

`\l@subtable``{\langle text \rangle}{\langle pagenum \rangle}`

```
189 \renewcommand{\l@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
```

File 476 **lwarp-subfigure.sty**

§ 585 Package **subfigure**

Pkg subfigure

subfigure is emulated by subfig.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{subfigure}[2002/03/15]
2 \RequirePackage{subfig}
```

```

3 \LetLtxMacro\subfigure\subfloat
4 \LetLtxMacro\subtable\subfloat
5 \LetLtxMacro\Subref\subref
6 \@ifundefined{figuretopcaptrue}{\newif\iffiguretopcap}{}
7 \newif\ifsubfiguretopcap
8 \newif\ifsubcaphang
9 \newif\ifsubcapcenter
10 \newif\ifsubcapcenterlast
11 \newif\ifsubcapnooneline
12 \newif\ifsubcapraggedright
13 \newskip\subfigtopskip
14 \newskip\subfigcapskip
15 \newdimen\subfigcaptopadj
16 \newskip\subfigbottomskip
17 \newdimen\subfigcapmargin
18 \newskip\subfiglabelskip
19 \newcommand*{\subcapsize}{}
20 \newcommand*{\subcaplabelfont}{}
21 \newcommand*{\subcapfont}{}

```

File 477 **lwarp-subsubscripts.sty**

§ 586 Package **subsubscripts**

(Emulates or patches code by RICCARDO BRESCIANI.)

Pkg subsubscripts

subsubscripts is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{subsubscripts}[2009/10/27]

The larger skips are used here.

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{%
4   \newcommand{\fourscriptsC}[7]{%
5     { }^{#2}_{#3}\hspace{#6}\hspace{#7}}^{#4}_{#5}%
6   }
7 }
8 \CustomizeMathJax{%
9   \newcommand{\lrsubscriptsC}[5]{%
10    \fourscriptsC{#1}{#2}{#3}{#4}{#5}%
11  }
12 }
13 \CustomizeMathJax{%
14   \newcommand{\lrsuperscriptsC}[5]{%
15    \fourscriptsC{#1}{#2}{#3}{#4}{#5}%
16  }
17 }
18 \CustomizeMathJax{%
19   \newcommand{\fourscripts}[5]{%
20    \fourscriptsC{#1}{#2}{#3}{#4}{#5}{0ex}{0ex}%
21  }
22 }
23 \CustomizeMathJax{%
24   \newcommand{\lrsubscripts}[3]{\fourscripts{#1}{#2}{#3}}
25 }
26 \CustomizeMathJax{%

```

```

27 \newcommand{\lrsuperscripts}[3]{\fourscripts{#1}{#2}{#3}}
28 }
29 \CustomizeMathJax{%
30 \newcommand{\twolscripts}[4][-.16ex]{\^{\#3}_{\#4}\hspace{#1}#2}
31 }
32 \CustomizeMathJax{%
33 \newcommand{\tworscripts}[4][-.07ex]{\#2\hspace{#1}{\^{\#3}_{\#4}}
34 }
35 \CustomizeMathJax{%
36 \newcommand{\lsubscript}[3][-.16ex]{\twolscripts[#1]{#2}{#3}}
37 }
38 \CustomizeMathJax{%
39 \newcommand{\lsuperscript}[3][-.16ex]{\twolscripts[#1]{#2}{#3}}
40 }
41 \CustomizeMathJax{%
42 \newcommand{\rsubscript}[3][-.07ex]{\tworscripts[#1]{#2}{#3}}
43 }
44 \CustomizeMathJax{%
45 \newcommand{\rsuperscript}[3][-.07ex]{\tworscripts[#1]{#2}{#3}}
46 }
47 \end{warpMathJax}

```

File 478 **lwarp-supertabular.sty**

§ 587 Package **supertabular**

(Emulates or patches code by JOHANNES BRAAMS, THEO JURRIENS.)

Pkg supertabular **supertabular** is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{supertabular}[2004/02/20]

⚠ **Misplaced alignment tab character &** For `\tablefirsthead`, etc., enclose them as follows:

```

\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars

```

See section 8.10.1.

⚠ **lateximage** **supertabular** and **xtab** are not supported inside a **lateximage**.

```

2 \newcommand{\LWRST@firsthead}{}
3
4 \newcommand{\tablefirsthead}[1]{%
5 \long\gdef\LWRST@firsthead{#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}
9 \newcommand{\tabletail}[1]{}
10
11 \newcommand{\LWRST@lasttail}{}
12
13 \newcommand{\tablelasttail}[1]{%
14 \long\gdef\LWRST@lasttail{#1}%
15 }

```

```

16 \newcommand{\tablecaption}[2][]{%
17   \long\gdef\LWRST@caption{%
18     \ifblank{#1}%
19       {\caption{#2}}%
20       {\caption[#1]{#2}}%
21   }%
22 }
23
24 \let\topcaption\tablecaption
25 \let\bottomcaption\tablecaption

26 \newcommand*\LWRST@caption{}
27
28 \newcommand*\shrinkheight}[1]{}
29
30 \NewDocumentEnvironment{supertabular}{s o m}
31 {%
32 \LWR@traceinfo{supertabular}%
33 \begin{table}%
34 \LWRST@caption%
35 \begin{tabular}{#3}%
36 \TabularMacro\ifdefvoid{\LWRST@firsthead}%
37 {\LWR@getmynexttoken}%
38 {\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
39 }%
40 {%
41 \ifdefvoid{\LWRST@lasttail}%
42 {}%
43 {%
44 \TabularMacro\ResumeTabular%
45 \LWRST@lasttail%
46 }%
47 \end{tabular}%
48 \end{table}%

49 \gdef\LWRST@caption{}%

50 \LWR@traceinfo{supertabular done}%
51 }
52
53 \NewDocumentEnvironment{mpsupertabular}{s o m}
54 {\minipage{\linewidth}\supertabular{#3}}
55 {\endsupertabular\endminipage}

```

File 479 **lwarp-svg.sty**

§ 588 Package **svg**

(Emulates or patches code by PHILIP ILTEN, FALK HANISCH.)

Pkg `svg`

svg is patched for use by **lwarp**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{svg}[2020/10/23]
2 \xpretocmd{\includesvg}%

```

```

3   {\begin{lateximage}}%
4   {}%
5   {\LWR@patcherror{svg}{includesvg}}
6
7   \xapptocmd{\includesvg}%
8   {\end{lateximage}}%
9   {}%
10  {\LWR@patcherror{svg}{includesvg}}
11
12  \xpretocmd{\includeinkscape}%
13  {\begin{lateximage}}%
14  {}%
15  {\LWR@patcherror{svg}{includeinkscape}}
16
17  \xapptocmd{\includeinkscape}%
18  {\end{lateximage}}%
19  {}%
20  {\LWR@patcherror{svg}{includeinkscape}}

```

File 480 **lwarp-swfigure.sty**

§ 589 Package **swfigure**

(Emulates or patches code by CLAUDIO BECCARI.)

Pkg swfigure

swfigure is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{swfigure}[2020-11-10]

2 \NewDocumentEnvironment{DFimage}%
3   {O{SW} m O{#4} m o D(){0.8} D<>{0} D||{0.25} D!!{}}%
4   {%
5     \begin{figure}
6     \centering
7     \includegraphics{#2}
8     \caption[#3]{#4}
9     \IfValueT{#5}{\label{#5}}
10    \end{figure}
11   }%
12   {}%

```

File 481 **lwarp-sympytex.sty**

§ 590 Package **sympytex**

(Emulates or patches code by TIM MOLTENO.)

Pkg sympytex

sympytex is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{sympytex}[2014/05/16]

2 \AfterEndPreamble{
3
4 \AtBeginEnvironment{sympyblock}{%

```

```

5   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
6     {}%
7     {%
8       \LWR@forcenewpage%
9       \LWR@atbeginverbatim{verbatim}%
10      }%
11 }
12
13 \AfterEndEnvironment{sympyblock}{%
14   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
15     {}%
16     {%
17       \LWR@afterendverbatim%
18     }%
19 }
20
21 }

```

File 482 **lwarp-syntonly.sty**

§ 591 Package **syntonly**

(Emulates or patches code by FRANK MITTELBACH, RAINER SCHÖPF.)

Pkg syntonly

syntonly is ignored.

for HTML output: Discard all options for lwarp-syntonly:

```

1 \LWR@ProvidesPackageDrop{syntonly}[2017/06/30]
2 \newif\ifsyntax@
3 \syntax@false
4
5 \newcommand*{\syntaxonly}{}
6
7 \@onlypreamble\syntaxonly
8
8 \def\nopages@{}

```

File 483 **lwarp-tabfigures.sty**

§ 592 Package **tabfigures**

Pkg tabfigures

tabfigures is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{tabfigures}[2012/01/24]

File 484 **lwarp-tablefootnote.sty**

§ 593 Package **tablefootnote**

Pkg tablefootnote

tablefootnote is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{tablefootnote}[2014/01/26]

This works because in HTML tables are no longer floats.

2 \LetLtxMacro\tablefootnote\footnote

File 485 **lwarp-tables.sty**

§ 594 Package **tables**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg tables **tables** is emulated. \LWR@hline is used to handle the optional argument when **tables** is loaded.

for HTML output: 1 \LWR@ProvidesPackageDrop{tables}

2 \newdimen\tablinesep
3 \newdimen\arraylinesep
4 \newdimen\extrarulesep

File 486 **lwarp-tabularx.sty**

§ 595 Package **tabularx**

(Emulates or patches code by DAVID CARLISLE.)

Pkg tabularx **tabularx** is emulated by **lwarp**.

for HTML output: Discard all options for **lwarp-tabularx**:

1 \LWR@ProvidesPackageDrop{tabularx}[2016/02/03]
2 \RequirePackage{array}

\tabularxcolumn is ignored. All X columns will be p for now. The width is ignored.

3 \def\tabularxcolumn#1{p{#1}}
4 \newcolumnntype{X}{p{1in}}

5 \DeclareDocumentEnvironment{tabularx}{m o m}
6 {\tabular{#3}}
7 {\endtabular}
8
9 \DeclareDocumentEnvironment{tabularx*}{m o m}
10 {\tabular{#3}}
11 {\endtabular}

File 487 **lwarp-tabulary.sty**

§ 596 Package **tabulary**

(Emulates or patches code by DAVID CARLISLE.)

Pkg tabulary

tabulary is emulated by lwarp.

for HTML output:

Discard all options for lwarp-tabulary.

Column types L, C, R, and J are emulated by lwarp core code.

```

1 \LWR@ProvidesPackageDrop{tabulary}[2014/06/11]
2 \RequirePackage{array}

3 \NewDocumentEnvironment{tabulary}{m o m}
4 {\tabular{#3}}
5 {\endtabular}
6
7 \NewDocumentEnvironment{tabulary*}{m o m}
8 {\tabular{#3}}
9 {\endtabular}

10 \newcolumnntype{L}{l}
11 \newcolumnntype{C}{c}
12 \newcolumnntype{R}{r}
13 \newcolumnntype{J}{l}

14 \newdimen\tymin
15 \newdimen\tymax
16 \def\tyformat{}
```

File 488 **lwarp-tagpdf.sty**

§ 597

Package

tagpdf

Pkg tagpdf

tagpdf is mostly ignored, but emulates alt text, for images only. (HTML only has alternate text for images.)

(If left enabled for HTML output, tagpdf errors when producing HTML, somehow due to the HTML page numbers.)

for HTML output:

```

1 \LWR@ProvidesPackageDrop{tagpdf}[2021-08-27]

2 \ExplSyntaxOn
3
4 \tl_new:N \l__uftag_mc_key_label_tl
5
6 \keys_define:nn { __tag / mc }
7 {
8   stash .bool_set:N = \l__tag_mc_key_stash_bool,
9   __artifact-bool .bool_set:N = \l__tag_mc_artifact_bool,
10  __artifact-type .choice:,
11  __artifact-type / pagination .code:n =
12  {},
13  __artifact-type / pagination/header .code:n =
14  {},
15  __artifact-type / pagination/footer .code:n =
16  {},
17  __artifact-type / layout .code:n =
18  {},
19  __artifact-type / page .code:n =
```

```

20     {},
21     __artifact-type / background .code:n =
22     {},
23     __artifact-type / notype .code:n =
24     {},
25     __artifact-type / .code:n =
26     {},
27 }
28
29 \keys_define:nn { __tag / mc }
30 {
31   tag .code:n = % the name (H,P,Span) etc
32   {},
33   raw .code:n =
34   {},
35   alttext .code:n = % Alt property
36   {
37     \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
38   },
39   actualtext .code:n = % ActualText property
40   {},
41   label .tl_set:N = \l__tag_mc_key_label_tl,
42   artifact .code:n =
43   {},
44   artifact .default:n = {notype}
45 }
46
47 \keys_define:nn { __tag / struct }
48 {
49   label .tl_set:N = \l__tag_struct_key_label_tl,
50   stash .bool_set:N = \l__tag_struct_elem_stash_bool,
51   tag .code:n = % S property
52   {},
53   title .code:n = % T property
54   {},
55   title-o .code:n = % T property
56   {},
57   alttext .code:n = % Alt property
58   {
59     \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
60   },
61   actualtext .code:n = % ActualText property
62   {},
63   lang .code:n = % Lang property
64   {},
65   ref .code:n = % Lang property
66   {},
67   E .code:n = % E property
68   {},
69 }
70
71 \keys_define:nn { __tag / struct }
72 {
73   AF .code:n = % AF property
74   {},
75   ,AFinline .code:n =
76   {}
77   ,AFinline-o .code:n =
78   {}
79 }

```

```

80
81 \keys_define:nn { __tag / struct }
82 {
83   attribute-class .code:n =
84   {}
85 }
86
87 \keys_define:nn { __tag / struct }
88 {
89   attribute .code:n = % A property (attribute, value currently a dictionary)
90   {},
91 }
92
93 \cs_new_protected:Npn \__tag_ref_label:nn #1 #2 % #1 label, #2 name of list mc or struct
94 {
95   \@bsphack
96   \ref_label:nv {#1}{c__tag_ref#2_clist}
97   \@esphack
98 }
99 \cs_generate_variant:Nn \__tag_ref_label:nn {en}
100
101 \cs_new:Npn \__tag_ref_value:nnn #1 #2 #3 % #1 label, #2 attribute, #3 default
102 {
103   \ref_value:nnn {#1}{#2}{#3}
104 }
105 \cs_generate_variant:Nn \__tag_ref_value:nnn {enn}
106 \cs_new:Npn \__tag_ref_value_lastpage:nn #1 #2
107 {
108   \ref_value:nnn {\__tag_LastPage}{#1}{#2}
109 }
110
111
112 \NewDocumentCommand \tagpdfsetup { m }{}
113
114 \cs_set_eq:NN\tagpdfifluatexTF \sys_if_engine_luatex:TF
115 \cs_set_eq:NN\tagpdfifluatexT \sys_if_engine_luatex:T
116 \cs_set_eq:NN\tagpdfifpdfstexT \sys_if_engine_pdfstex:T
117 \cs_new:Npn \tagpdfget #1 {}
118 \cs_new:Npn \uftag_get:n #1 {}
119
120 \NewDocumentCommand \tagmcifinTF { m m }{}
121
122 \NewDocumentCommand \tagmcbegin { m }{%
123   \tag_mc_begin:n {#1}%\ignorespaces
124 }
125
126 \cs_new_protected:Npn \tag_mc_begin:n #1 % #1 keyval
127 {
128   \keys_set:nn { __tag / mc } {#1}
129 }
130
131 \NewDocumentCommand \tagmcend {}{\ThisAltText{}}
132
133 \NewDocumentCommand \tagmcuse { m }{}
134
135 \cs_new_protected:Nn \uftag_mc_use:n {}
136
137 \NewDocumentCommand \tagstructbegin { m }
138 {
139   \tag_struct_begin:n {#1}

```

```

140 }
141
142 \cs_new_protected:Npn \tag_struct_begin:n #1 %#1 key-val
143 {
144   \keys_set:nn { __tag / struct } { #1 }
145 }
146
147
148 \NewDocumentCommand \tagstructend { }
149 {
150   \tag_struct_end:
151 }
152
153 \cs_new_protected:Nn \tag_struct_end:
154   {\ThisAltText{}}
155
156 \NewDocumentCommand \tagstructuse { m }{}
157
158 \NewDocumentCommand \ShowTagging { m }
159   {}
160
161 \sys_if_engine luatex:T
162 {
163   \NewDocumentCommand \pdffakepace { }
164   {}
165 }
166
167 \newcommand \tagpdfparaOn {}
168
169 \newcommand \tagpdfparaOff{}
170
171 \NewDocumentCommand \tagpdfsuppressmarks{m}{}
172
173 \ExplSyntaxOff

```

File 489 **lwarp-tascmac.sty**

§ 598 Package **tascmac**

Pkg tascmac

tascmac is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{tascmac}[2018/03/09]
2 \newenvironment*{boxnote}
3   {
4     \BlockClass[
5       padding: .5ex ;
6       border: 1px solid black ;
7       border-top: 1px dashed black ;
8     ]{boxnote}
9   }
10  {\endBlockClass}
11
12 \newenvironment*{screen}[1][]
13   {
14     \BlockClass[
15       padding: .5ex ;

```

```
16         border: 1px solid gray ;
17         border-radius: 8pt
18     ]{boxnote}
19 }
20 {\endBlockClass}
21
22 \newenvironment*{itembox}[2][[]
23     {
24         \BlockClass[
25             padding: .5ex ;
26             border: 1px solid gray ;
27             border-radius: 8pt
28         ]{boxnote}
29         \InlineClass{itemboxtitle}{#2}\par
30     }
31     {\endBlockClass}
32
33 \newenvironment*{shadebox}
34     {
35         \BlockClass[
36             padding: .5ex ;
37             border: 1px solid black ;
38             box-shadow: 3px 3px 3px \#808080 ;
39         ]{boxnote}
40     }
41     {\endBlockClass}
42
43 \newcommand*{\mask}[2]{%
44     \InlineClass[background: lightgray]{mask}{#1}%
45 }
46
47 \newcommand*{\maskbox}[5]{%
48     \InlineClass[background: lightgray]{mask}{#5}%
49 }
50
51 \newcommand*{\Maskbox}[6]{%
52     \InlineClass[
53         background: lightgray ;
54         border: #5 solid black
55     ]{mask}{#6}%
56 }
57
58 \newcommand*{\keytop}[2][[]{%
59     \InlineClass[%
60         padding: .2ex ;
61         border: 1px solid black ;
62         border-radius: .7ex ;
63     ]{keytop}{#2}%
64 }
65
66 \def\yen{\HTMLUnicode{00A5}}
67
68 \def\return{\HTMLUnicode{23CE}}
69
70 \def\Return{\HTMLUnicode{23CE}}
71
72 \def\ascii{ASCII Corporation}
73
74 \def\Ascii{ASCII Corporation}
75
```

```
76 \def\ASCII{ASCII Corporation}
```

File 490 **lwarp-tcolorbox.sty**

§ 599 Package **tcolorbox**

(Emulates or patches code by THOMAS F. STURM.)

Pkg tcolorbox

tcolorbox is patched for use by lwarp.

See section 8.3.8 for limitations.

for HTML output:

```
1 \LWR@ProvidesPackagePass{tcolorbox}[2020/04/28]
```

```
2 \newbool{LWR@havetcblower}
3 \boolfalse{LWR@havetcblower}
```

Colors are supported via HTML styles:

```
4 \newcommand{\LWR@tcolorbox@findcolors}{%
5   \convertcolorspec{named}{tcbcolback}{HTML}\LWR@tcbcolback
6   \convertcolorspec{named}{tcbcolframe}{HTML}\LWR@tcbcolframe
7   \iftcb@titlefilled%
8     \convertcolorspec{named}{tcbcolbacktitle}{HTML}\LWR@tcbcolbacktitle
9   \else
10    \convertcolorspec{named}{tcbcolframe}{HTML}\LWR@tcbcolbacktitle
11  \fi
12  \convertcolorspec{named}{tcbcoltitle}{HTML}\LWR@tcbcoltitle
13  \convertcolorspec{named}{tcbcolupper}{HTML}\LWR@tcbcolupper
14  \convertcolorspec{named}{tcbcollower}{HTML}\LWR@tcbcollower
15 }
16
17 \newcommand*{\LWR@tcolorbox@titlecolorstyles}{%
18   border-top: 1px solid \LWR@origpound\LWR@tcbcolframe ;
19   border-bottom: 1px solid \LWR@origpound\LWR@tcbcolframe ;
20   background: \LWR@origpound\LWR@tcbcolbacktitle ;
21   color: \LWR@origpound\LWR@tcbcoltitle ;
22 }
```

The title is placed inside its own <div> of class tcolorboxtitle.

```
23 \newcommand*{\LWR@showtitle@[1]}{%
24   \begin{BlockClass}[
25     \LWR@tcolorbox@titlecolorstyles
26   ]{tcolorboxtitle}
27 %       \cmdKV@LWR@tcolorbox@title\par
28   \kvtcb@before@title#1\kvtcb@after@title
29   \end{BlockClass}
30 }
```

If no title, a non-breakable space is used to take some vertical space.

```
31 \newcommand*{\LWR@showtitle@[1]}{%
32   \iftcb@titlevisible
33   \LWR@showtitle@{#1}
34   \else
```

```

35 \LWR@showtitle@{~}
36 \fi
37 }
38
39 \newcommand*\LWR@tcolorbox@dophantom}{%
40 % \sbox\tcb@phantombox{\kvtcb@phantom}%
41 % \iftcb@hasPhantom%
42 % \box\tcb@phantombox%
43 % \tcb@hasPhantomfalse%
44 % \fi%
45 \kvtcb@phantom
46 \let\kvtcb@phantom\empty%
47 }

```

The tcolorbox is placed inside an external <div> of class #1, which is tcolorbox or tcolorbox inlineminipage. The upper and lower parts are placed into their own internal <div>s of class tcolorboxupper and tcolorboxlower.

```

48 \newcommand*\LWR@tcolorboxstart}[1]{
49 \LWR@tcolorbox@findcolors
50 \begin{BlockClass}[
51 border: 1px solid \LWR@origpound\LWR@tcbcolframe ;
52 background: \LWR@origpound\LWR@tcbcolback ;
53 ]{#1}
54 \LWR@tcolorbox@dophantom%
55 \ifdefined\kvtcb@title
56 {}
57 {
58 \LWR@showtitle{\kvtcb@title}
59 }
60 \begin{BlockClass}[
61 color: \LWR@origpound\LWR@tcbcolupper ;
62 ]{tcolorboxupper}
63 }

```

Floats enclose the tcolorbox.

```

64 \newcommand*\LWR@tcolorbox@dostartfloat}{%
65 \ifx\kvtcb@float\empty%
66 % \tcb@set@normal@unbroken@beforeafter%
67 \else%
68 % \edef\tcb@before@unbroken{%
69 % \noexpand\tcb@float@env@begin{tcbfloat}[\kvtcb@float]%
70 % \noexpand\kvtcb@everyfloat%
71 % }%
72 % \let\tcb@after@unbroken=\tcb@float@env@end%
73 \tcb@float@env@begin{tcbfloat}[\kvtcb@float]
74 \noexpand\kvtcb@everyfloat
75 \fi%
76 }
77
78 \newcommand*\LWR@tcolorbox@doendfloat}{%
79 \ifx\kvtcb@float\empty%
80 \else%
81 \tcb@float@env@end%
82 \fi%
83 }

```

Footnotes are handled via the main footnote mechanism, and pending notes are printed before and after each tcolorbox. Footnote numbering will not match the print output.

```

84 \renewenvironment{tcolorbox}[1][
85   {
86     \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
87     {
88       \PackageError{lwarp}
89         {%
90           Lwarp cannot process a tcolorbox inside a lateximage\MessageBreak
91             or SVG math.\MessageBreak
92             Enter 'H' for possible solutions%
93         }
94         {%
95           Use \protect\tcbbox, \protect\tcbboxmath, or
96             \protect\tcbhighmath\space instead.\MessageBreak%
97             (Inside math, you probably want to use these anyhow.)%
98         }
99       }\relax}
100   \LWR@printpendingfootnotes
101   \tcb@layer@inc
102   \tcb@apply@box@options{#1}
103   \LWR@tcolorbox@dostartfloat%
104   \tcbset{title=#1}
105   \boolfalse{LWR@havetcblower}
106   \LWR@tcolorboxstart{tcolorbox}
107   \tcb@insert@before@upper%
108 }
109 {
110   \ifbool{LWR@havetcblower}{%
111     \tcb@insert@after@lower%
112   }{%
113     \tcb@insert@after@upper%
114   }%
115   \end{BlockClass}
116   \LWR@printpendingfootnotes
117   \tcb@layer@dec
118   \end{BlockClass}
119   \LWR@tcolorbox@doendfloat%
120 }

```

For the lower part, the upper part is finished then the lower is started. \tcblower is only temporarily defined where appropriate, so the HTML version is defined globally via \newcommand instead of \renewcommand.

```

121 \newcommand{\tcblower}{
122   \tcb@insert@after@upper%
123   \end{BlockClass}
124   \begin{BlockClass}[%
125     border-top: 1px dashed \LWR@origpound\LWR@tcbcolframe ;
126     color: \LWR@origpound\LWR@tcbcollower ;
127   ]{tcolorboxlower}
128   \tcb@insert@before@lower%
129 }

```

Starred and unstarred \tcbline are simple \hrules.

```

130 \AtBeginDocument{

```

```

131 \ifdef{\tcbline}{
132   \newcommand*\LWR@sub@tcbline}{%
133     \begin{BlockClass}{hrule}
134     \end{BlockClass}
135   }
136   \newcommand{\LWR@HTML@tcbline}{\@ifstar\LWR@sub@tcbline\LWR@sub@tcbline}
137   \LWR@formatted{tcbline}
138 }{}
139 }
140
141 \newcommand{\LWR@HTML@tcbox}[2][{}{
142   \LWR@printpendingfootnotes
143   \LWR@tcolorbox@dostartfloat%
144   \begingroup
145   \tcb@layer@inc
146   \tcb@apply@box@options{#1}
147 %   \tcbset{title=#1}
148   \boolfalse{LWR@havetcblower}
149   \LWR@tcolorboxstart{tcolorbox inlineminipage}
150   \tcb@insert@before@upper%
151   #2
152   \ifbool{LWR@havetcblower}{%
153     \tcb@insert@after@lower%
154   }{%
155     \tcb@insert@after@upper%
156   }%
157   \end{BlockClass}
158   \LWR@printpendingfootnotes
159   \end{BlockClass}
160   \tcb@layer@dec%
161   \endgroup%
162   \LWR@tcolorbox@dostartfloat%
163   \global\booltrue{LWR@minipagethispar}%
164 }
165 \LWR@formatted{tcbox}
166
167 \appto\LWR@restoreMathJaxformatting{%
168   \renewcommand{\tcbox}[2][{}{#2}%
169 }

```

Patches for the subtitle, which is placed inside a <div> of class tcolorboxsubtitle.

```

170 \xpatchcmd{\tcbsubtitle}
171   {\begingroup}
172   {\begingroup\let\kvtcb@title\relax\begin{BlockClass}{tcolorboxsubtitle}}
173   {}
174   {\LWR@patcherror{tcolorbox}{tcbsubtitle}}
175
176 \xpatchcmd{\tcbsubtitle}
177   {\endgroup}
178   {\end{BlockClass}\endgroup}
179   {}
180   {\LWR@patcherror{tcolorbox}{tcbsubtitleB}}

```

\tcboxfit is the same as \tcbox.

```

181 \AtBeginDocument{
182   \ifdef{\tcboxfit}{%
183     \let\LWR@HTML@tcboxfit\tcbox%
184     \LWR@formatted{tcboxfit}

```

```
185   }{}
186 }
```

`\tcbtitle` is patched to support the text font.

```
187 \LetLtxMacro\LWR@HTML@tcbtitle\tcbtitle
188 \xpatchcmd{\LWR@HTML@tcbtitle}
189   {\kvtcb@before@title\tcbtitletext}
190   {\kvtcb@before@title\LWR@textcurrentfont{\LWR@textcurrentcolor{\tcbtitletext}}}
191   {}
192   {\LWR@patcherror{tcolorbox}{LWR@HTML@tcbtitle}}
193 \LWR@formatted{tcbtitle}
```

List-of:

```
194 \renewcommand*\l@tcolorbox[2]{\hypertocfloat{1}{tcolorbox}{lof}{#1}{#2}}
```

Theorem limitations. An error is printed if the document uses `math`, `ams equation`, etc. `\tcbboxmath` and `\tcbhighmath` are ignored for HTML.

```
195 \AtBeginDocument{
196 \pgfkeysifdefined{/tcb/libload/theorems}{
197
198   \def\LWR@HTML@tcb@hack@amsmath{%
199     \PackageError{lwarp}
200     {%
201       tcolorbox ‘math’, ‘ams equation’, and related\MessageBreak
202       are not supported.\MessageBreak
203       \protect\tcbboxmath\space and
204       \protect\tcbhighmath\space are emulated.\MessageBreak
205       Enter ‘H’ for possible solutions%
206     }
207     {%
208       Remove tcolorbox math-related options, and instead\MessageBreak
209       use the usual math environments inside each tcolorbox.%
210     }
211   }
212   \LWR@formatted{tcb@hack@amsmath}
213
214   % Cause an error if using math:
215   \tcbset{%
216     math upper/.style={before upper*=\tcb@hack@amsmath,after upper*=$},%
217     math lower/.style={before lower*=\tcb@hack@amsmath,after lower*=$},%
218   }
219
220   \appto\LWR@restoreorigformatting{%
221     \tcbset{%
222       math upper/.style={before upper*=$\displaystyle,after upper*=$},%
223       math lower/.style={before lower*=$\displaystyle,after lower*=$},%
224     }%
225   }
226
227   \newcommand{\LWR@HTML@tcbboxmath}[2][{}]{#2}
228   \LWR@formatted{tcbboxmath}
229   \newcommand{\LWR@HTML@tcbhighmath}[2][{}]{#2}
230   \LWR@formatted{tcbhighmath}
231   \appto\LWR@restoreMathJaxformatting{%
232     \renewcommand{\tcbboxmath}[2][{}]{#2}%
233     \renewcommand{\tcbhighmath}[2][{}]{#2}%

```

```

234 }
235 }{}% theorems loaded
236 }% AtBeginDocument

```

For MATHJAX:

```

237 \CustomizeMathJax{\newcommand{\tcbset}[1]{} }
238 \CustomizeMathJax{\newcommand{\tcbsetforeverylayer}[1]{} }
239 \CustomizeMathJax{\newcommand{\tcbbox}[2][\boxed{\text{#2}}]}
240 \CustomizeMathJax{\newcommand{\tcbboxfit}[2][\boxed{#2}}]}
241 \CustomizeMathJax{\newcommand{\tcblower}{} }
242 \CustomizeMathJax{\newcommand{\tcbline}{} }
243 \CustomizeMathJax{\newcommand{\tcbtitle}{} }
244 \CustomizeMathJax{\newcommand{\tcbstitle}[2][\mathrm{#2}]}
245 \CustomizeMathJax{\newcommand{\tcbboxmath}[2][\boxed{#2}}]}
246 \CustomizeMathJax{\newcommand{\tcbhighmath}[2][\boxed{#2}}]}

```

File 491 **lwarp-tensor.sty**

§ 600 Package **tensor**

(Emulates or patches code by PHILIP G. RATCLIFFE.)

tensor is used as-is for SVG math, and is emulated for MATHJAX.

 **spacing** Compressed spacing and left justification are not possible with MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{tensor}[2004/12/20]

For MATHJAX. Special handling is required to parse the superscript and subscript arguments.

When a superscript or subscript is seen, it is processed and then the remainder is processed recursively.

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\def\LWRtensorindicesub#1#2{{_#2}}\LWRtensorindicesthree}}
4 \CustomizeMathJax{\def\LWRtensorindicesub#1#2{{^#2}}\LWRtensorindicesthree}}

```

If not a superscript nor a subscript, processing stops.

```

5 \CustomizeMathJax{\newcommand{\LWRtensorindicesthreeotsup}{} }

```

Check ahead for a superscript or a subscript.

```

6 \CustomizeMathJax{\newcommand{\LWRtensorindicesthreeotsub}{
7   \ifnextchar ^ \LWRtensorindicesthreeotsup \LWRtensorindicesthreeotsup
8 }}
9
10 \CustomizeMathJax{\newcommand{\LWRtensorindicesthree}{
11   \ifnextchar _ \LWRtensorindicesthreeotsub \LWRtensorindicesthreeotsub
12 }}

```

Ignore star.

```

13 \CustomizeMathJax{\newcommand{\LWRtensorindicestwo}{

```

```

14 \ifstar\LWRtensorindicesthree\LWRtensorindicesthree
15 }}

```

Remove the outer brace of the argument.

```

16 \CustomizeMathJax{\newcommand{\indices}[1]{\LWRtensorindicestwo#1}}

```

Attempting to use `\vphantom` here does not work:

```

17 \CustomizeMathJax{\newcommand{\LWRtensortwo}[3][{}]{\indices{#1}{#2}\indices{#3}}}

```

Ignore star.

```

18 \CustomizeMathJax{\newcommand{\tensor}{\ifstar\LWRtensortwo\LWRtensortwo}}

```

In text mode, `\nuclide` is converted to an svg image.

```

19 \CustomizeMathJax{%
20   \newcommand{\LWRnuclidetwo}[2][{}]{%
21     {%
22       \vphantom{\mathrm{#2}}%
23       }^{\LWRtensornucleonnumber}_{#1}%
24       \mathrm{#2}%
25     }%
26   }%
27 }

28 \CustomizeMathJax{%
29   \newcommand{\nuclide}[1][{}]{%
30     \def\LWRtensornucleonnumber{#1}%
31     \LWRnuclidetwo%
32   }%
33 }
34 \end{warpMathJax}

```

File 492 **lwarp-termcal.sty**

§ 601 Package **termcal**

(Emulates or patches code by BILL MITCHELL.)

Pkg termcal

termcal is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{termcal}% questionable date in the .sty file

Nullify the @ because everything is being done in a token list.

```

2 \xpatchcmd{\endcalendar}
3   {@{}}
4   {}
5   {}
6   {\LWR@patcherror{termcal}{endcalendar}}

```

Remove the hbox:

```

7 \xpatchcmd{\ca@doaday}
8   {\hbox to \hsize{\calprintdate\hfill\ifclassday\calprintclass\fi}}
9   {%
10      \calprintdate\hfill\ifclassday\calprintclass\fi%
11   }
12   {}
13   {\LWR@patcherror{termcal}{ca@doaday}}

```

Change each of two ampersands to call the lwarp tabular version:

```

14 \xpatchcmd{\calday}
15   {&}
16   {\LWR@tabularampersand}
17   {}
18   {\LWR@patcherror{termcal}{calday}}
19
20 \xpatchcmd{\calday}
21   {&}
22   {\LWR@tabularampersand}
23   {}
24   {\LWR@patcherror{termcal}{calday B}}

```

File 493 **lwarp-textarea.sty**

§ 602 Package **textarea**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg textarea

textarea is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{textarea}[2005/12/26]

```

2 \newcommand\StartFromTextArea{}
3 \newcommand\StartFromHeaderArea{}
4 \newcommand*\RestoreTextArea{}
5 \newcommand*\ExpandTextArea[1][*]{}
6 \let\NCC@restoretextarea\empty

```

File 494 **lwarp-textcomp.sty**

§ 603 Package **textcomp**

(Emulates or patches code by FRANK MITTELBACH, ROBIN FAIRBAIRNS, WERNER LEMBERG.)

Pkg textcomp

textcomp is patched for use by lwarp.

For MATHJAX, the MATHJAX package is used.

§ 603.1 Limitations

Some `textcomp` symbols do not have Unicode equivalents, and thus are not supported.

 **missing symbols** Many `textcomp` symbols are not supported by many system / browser fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

§ 603.2 Package loading

for HTML output: `1 \LWR@ProvidesPackagePass{textcomp}[2017/04/05]`

§ 603.3 HTML symbols

For HTML, use HTML entities or direct Unicode, depending on the engine.

`\AtBeginDocument` improves support for `LuaATeX` and `X3LaTeX`.

§ 603.3.1 pdf^ATeX symbols

```

2 \AtBeginDocument{
3 \ifPDFTeX% pdfATeX or dviATeX
4 \newcommand*\LWR@HTML@textdegree{\HTMLentity{deg}}
5 \newcommand*\LWR@HTML@textcelsius{\HTMLunicode{2103}}
6 \newcommand*\LWR@HTML@textohm{\HTMLunicode{2126}}
7 \newcommand*\LWR@HTML@textmu{\HTMLunicode{00B5}}
8 \newcommand*\LWR@HTML@textlquill{\HTMLunicode{2045}}
9 \newcommand*\LWR@HTML@textrquill{\HTMLunicode{2046}}
10 \newcommand*\LWR@HTML@textcircledP{\HTMLunicode{2117}}
11 \newcommand*\LWR@HTML@texttwelveudash{\HTMLunicode{2014}}% emdash
12 \newcommand*\LWR@HTML@textthreequartersemdash{\HTMLunicode{2014}}% emdash
13 \newcommand*\LWR@HTML@textmho{\HTMLunicode{2127}}
14 \newcommand*\LWR@HTML@textnaira{\HTMLunicode{20A6}}
15 \newcommand*\LWR@HTML@textpeso{\HTMLunicode{20B1}}
16 \newcommand*\LWR@HTML@textrecipe{\HTMLunicode{211E}}
17 \newcommand*\LWR@HTML@textinterrobang{\HTMLunicode{203D}}
18 \newcommand*\LWR@HTML@textinterrobangdown{\HTMLunicode{2E18}}
19 \newcommand*\LWR@HTML@textperthousand{\HTMLunicode{2030}}
20 \newcommand*\LWR@HTML@textpertenthousand{\HTMLunicode{2031}}
21 \newcommand*\LWR@HTML@textbaht{\HTMLunicode{0E3F}}
22 \newcommand*\LWR@HTML@textdiscount{\}%
23 \newcommand*\LWR@HTML@textservicemark{\HTMLunicode{2120}}
24 \else

```

§ 603.3.2 X₃LaTeX and Lua^ATeX symbols

NOTE: Some of the following do not print well in the listing. Consult the `.dtx` or `.sty` file for the actual characters.

```

25 \newcommand*\LWR@HTML@textdegree{\°}
26 \newcommand*\LWR@HTML@textcelsius{\°C}
27 \newcommand*\LWR@HTML@textohm{\Ω}
28 \newcommand*\LWR@HTML@textmu{\μ}
29 \newcommand*\LWR@HTML@textlquill{\{ }
30 \newcommand*\LWR@HTML@textrquill{\} }
31 \newcommand*\LWR@HTML@textcircledP{\Ⓟ}

```

```

32 \newcommand*\LWR@HTML@texttwelveudash}{-}% emdash
33 \newcommand*\LWR@HTML@textthreequartersemdash}{-}% emdash
34 \newcommand*\LWR@HTML@textmho}{\U}
35 \newcommand*\LWR@HTML@textnaira}{\#}
36 \newcommand*\LWR@HTML@textpeso}{\P}
37 \newcommand*\LWR@HTML@textrecipe}{\R}
38 \newcommand*\LWR@HTML@textinterrobang}{\?}
39 \newcommand*\LWR@HTML@textinterrobangdown}{\d}
40 \newcommand*\LWR@HTML@textperthousand}{\%}
41 \newcommand*\LWR@HTML@textpertenthousand}{\‰}
42 \newcommand*\LWR@HTML@textbaht}{\฿}
43 \newcommand*\LWR@HTML@textdiscount}{\%}
44 \newcommand*\LWR@HTML@textservicemark}{\SM}
45 \fi
46
47 \LWR@formatted{textdegree}
48 \LWR@formatted{textcelsius}
49 \LWR@formatted{textohm}
50 \LWR@formatted{textmu}
51 \LWR@formatted{textlquill}
52 \LWR@formatted{textrquill}
53 \LWR@formatted{textcircledP}
54 \LWR@formatted{texttwelveudash}
55 \LWR@formatted{textthreequartersemdash}
56 \LWR@formatted{textmho}
57 \LWR@formatted{textnaira}
58 \LWR@formatted{textpeso}
59 \LWR@formatted{textrecipe}
60 \LWR@formatted{textinterrobang}
61 \LWR@formatted{textinterrobangdown}
62 \LWR@formatted{textperthousand}
63 \LWR@formatted{textpertenthousand}
64 \LWR@formatted{textbaht}
65 \LWR@formatted{textdiscount}
66 \LWR@formatted{textservicemark}

```

§ 603.4 HTML diacritics

For HTML, Unicode diacritical marks are used:

```

67 \newcommand*\LWR@HTML@capitalcedilla}[1]{\#1\HTMLUnicode{0327}}
68 \newcommand*\LWR@HTML@capitalogonek}[1]{\#1\HTMLUnicode{0328}}
69 \newcommand*\LWR@HTML@capitalgrave}[1]{\#1\HTMLUnicode{0300}}
70 \newcommand*\LWR@HTML@capitalacute}[1]{\#1\HTMLUnicode{0301}}
71 \newcommand*\LWR@HTML@capitalcircumflex}[1]{\#1\HTMLUnicode{0302}}
72 \newcommand*\LWR@HTML@capitaltilde}[1]{\#1\HTMLUnicode{0303}}
73 \newcommand*\LWR@HTML@capitaldieresis}[1]{\#1\HTMLUnicode{0308}}
74 \newcommand*\LWR@HTML@capitalhungarumlaut}[1]{\#1\HTMLUnicode{030B}}
75 \newcommand*\LWR@HTML@capitalring}[1]{\#1\HTMLUnicode{030A}}
76 \newcommand*\LWR@HTML@capitalcaron}[1]{\#1\HTMLUnicode{030C}}
77 \newcommand*\LWR@HTML@capitalbreve}[1]{\#1\HTMLUnicode{0306}}
78 \newcommand*\LWR@HTML@capitalmacron}[1]{\#1\HTMLUnicode{0304}}
79 \newcommand*\LWR@HTML@capitaldotaccent}[1]{\#1\HTMLUnicode{0307}}

```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with `xunicode`.

```

80 \providecommand*\LWR@HTML@textcircled}[1]{%
81   \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{\#1}%
82 }

```

```

83
84 \LWR@formatted{capitalcedilla}
85 \LWR@formatted{capitalogonek}
86 \LWR@formatted{capitalgrave}
87 \LWR@formatted{capitalacute}
88 \LWR@formatted{capitalcircumflex}
89 \LWR@formatted{capitaltilde}
90 \LWR@formatted{capitaldieresis}
91 \LWR@formatted{capitalhungarumlaut}
92 \LWR@formatted{capitalring}
93 \LWR@formatted{capitalcaron}
94 \LWR@formatted{capitalbreve}
95 \LWR@formatted{capitalmacron}
96 \LWR@formatted{capitaldotaccent}
97
98 \LWR@formatted{textcircled}

```

Nullify textcomp macros when generating filenames:

```

99 \FilenameNullify{%
100   \renewcommand*\textdegree{}%
101   \renewcommand*\textcelsius{}%
102   \renewcommand*\textohm{}%
103   \renewcommand*\textmu{}%
104   \renewcommand*\textlquill{}%
105   \renewcommand*\textrquill{}%
106   \renewcommand*\textcircledP{}%
107   \renewcommand*\texttwelveudash{}%
108   \renewcommand*\textthreequartersemdash{}%
109   \renewcommand*\textmho{}%
110   \renewcommand*\textnaira{}%
111   \renewcommand*\textpeso{}%
112   \renewcommand*\textrecipe{}%
113   \renewcommand*\textinterrobang{}%
114   \renewcommand*\textinterrobangdown{}%
115   \renewcommand*\textperthousand{}%
116   \renewcommand*\textpertenthousand{}%
117   \renewcommand*\textbaht{}%
118   \renewcommand*\textdiscount{}%
119   \renewcommand*\textservicemark{}%
120   \renewcommand*\textcircled}[1]{#1}%
121   \renewcommand*\capitalcedilla}[1]{#1}%
122   \renewcommand*\capitalogonek}[1]{#1}%
123   \renewcommand*\capitalgrave}[1]{#1}%
124   \renewcommand*\capitalacute}[1]{#1}%
125   \renewcommand*\capitalcircumflex}[1]{#1}%
126   \renewcommand*\capitaltilde}[1]{#1}%
127   \renewcommand*\capitaldieresis}[1]{#1}%
128   \renewcommand*\capitalhungarumlaut}[1]{#1}%
129   \renewcommand*\capitalring}[1]{#1}%
130   \renewcommand*\capitalcaron}[1]{#1}%
131   \renewcommand*\capitalbreve}[1]{#1}%
132   \renewcommand*\capitalmacron}[1]{#1}%
133   \renewcommand*\capitaldotaccent}[1]{#1}%
134 }% FilenameNullify
135
136 }% AtBeginDocument

```

For MATHJAX:

```
137 \CustomizeMathJax{\require{textcomp}}
```

File 495 **lwarp-textfit.sty**

§ 604 Package **textfit**

Pkg textfit

textfit is emulated.

Text is placed into a `` of class `textfit`. Sizes are approximated, and also limited by browser min/max font-size settings.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{textfit}[1994/04/15]
2 \newsavebox{\LWR@textfitbox}
3
4 \newcommand*\LWR@textfitscale[2]{%
5 \setlength{\LWR@templengthone}{#1}%
6 \setlength{\LWR@templengthone}{%
7   1em*\ratio{\LWR@templengthone}{\LWR@templengthtwo}%
8 }%
9 \InlineClass[font-size:\LWR@printlength{\LWR@templengthone}]{textfit}{#2}%
10 }
11
12 \newcommand*\scaletowidth[2]{%
13 \sbox{\LWR@textfitbox}{#2}%
14 \settowidth{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
15 \LWR@textfitscale{#1}{#2}%
16 }
17
18 \newcommand*\scaletoheight[2]{%
19 \sbox{\LWR@textfitbox}{#2}%
20 \settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
21 \LWR@textfitscale{#1}{#2}%
22 }
```

File 496 **lwarp-textpos.sty**

§ 605 Package **textpos**

Pkg textpos

textpos is emulated.

(Emulates or patches code by NORMAN GRAY.)

for HTML output:

```
1 \LWR@ProvidesPackageDrop{textpos}[2020/09/26]
2 \NewDocumentEnvironment{textblock}{m o r()}{}{}
3 \NewDocumentEnvironment{textblock*}{m o r()}{}{}
4 \newcommand*\TPGrid[3]{}{}
5 \def\TPShowGrid{\@ifstar{\@TPShowGrid}{\@TPShowGrid}}
6 \def\@TPShowGrid#1#2{}
7 \NewDocumentCommand{\TPMargin}{s o}{}
8 \newcommand*\textblockcolour[1]{}
9 \newcommand*\textblockrulecolour[1]{}
10 \newcommand*\textblockcolor[1]{}

```

```

11 \newcommand*\textblockrulecolor}[1]{}
12 \newcommand*\tekstblokkulur}[1]{}
13 \newcommand*\tekstblokrulekulur}[1]{}
14 \newlength\TPHorizModule
15 \newlength\TPVertModule
16 \newlength\TPboxrulesize
17 \newcommand*\textblocklabel}[1]{}
18 \newcommand*\showtextsize{}
19 \newcommand*\textblockorigin}[2]{}
20 \newcommand*\TPOptions}[1]{}
21 \newcommand*\TPReferencePosition}[1]{}

```

File 497 **lwarp-theorem.sty**

§ 606 Package **theorem**

(Emulates or patches code by FRANK MITTELBACH.)

Pkg theorem

theorem is patched for use by lwarp.

Table 21: Theorem package — css styling of theorems and proofs

Theorem: <div> of class theorembody<theoremstyle>

Theorem Header: of class theoremheader

where <theoremstyle> is plain, break, etc.

for HTML output: 1 \LWR@ProvidesPackagePass{theorem}[2014/10/28]

§ 606.1 Remembering the theorem style

Storage for the style being used for new theorems:

```
2 \newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```

3 \gdef\theoremstyle#1{%
4   \ifundefined{th@#1}{\@warning
5     {Unknown theoremstyle ‘#1’. Using ‘plain’}%
6     \theorem@style{plain}%
7     \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
8     }%
9   {%
10    \theorem@style{#1}%
11    \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
12   }%
13   \begingroup
14   \csname th@the\theorem@style \endcsname
15   \endgroup}

```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

16 \gdef\xnthm#1#2[#3]{%
17   \expandafter\@ifdefinable\csname #1\endcsname
18   {%
19     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
20     \definecounter{#1}\@newctr{#1}[#3]%
21     \expandafter\xdef\csname the#1\endcsname
22       {\expandafter \noexpand \csname the#3\endcsname
23         \@thmcountersep \@thmcounter{#1}}}%
24     \def\@tempa{\global\@namedef{#1}}}%
25     \expandafter \@tempa \expandafter{%
26       \csname th@the \theorem@style
27         \expandafter \endcsname \the \theorem@bodyfont
28         \@thm{#1}{#2}}}%
29     \global \expandafter \let \csname end#1\endcsname \@endtheorem
30     \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
31   }}
32
33 \gdef\ynthm#1#2{%
34   \expandafter\@ifdefinable\csname #1\endcsname
35   {
36     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
37     \definecounter{#1}%
38     \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
39     \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
40     \expandafter{\csname th@the \theorem@style \expandafter
41       \endcsname \the\theorem@bodyfont \@thm{#1}{#2}}}%
42     \global \expandafter \let \csname end#1\endcsname \@endtheorem
43     \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
44   }}
45
46 \gdef\@othm#1[#2]#3{%
47   \expandafter\ifx\csname c@#2\endcsname\relax
48     \@nocounterr{#2}%
49   \else
50     \expandafter\@ifdefinable\csname #1\endcsname
51     {
52       \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
53       \expandafter \xdef \csname the#1\endcsname
54         {\expandafter \noexpand \csname the#2\endcsname}%
55       \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
56       \expandafter{\csname th@the \theorem@style \expandafter
57         \endcsname \the\theorem@bodyfont \@thm{#2}{#3}}}%
58       \global \expandafter \let \csname end#1\endcsname \@endtheorem
59       \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
60     }%
61   \fi}

```

§ 606.2 **css patches**

The following are patched for CSS.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `InlineClass` of class `theoremheader`.

```

62 \gdef\th@plain{%
63   \def\@begintheorem##1##2{%

```

```
64     \item[
65         \InlineClass{theoremheader}{##1\ ##2}
66     ]
67 ]%
68 \def\@opargbegintheorem##1##2##3{%
69     \item[
70         \InlineClass{theoremheader}{##1\ ##2\ (##3)}
71     ]
72     }
73 }
74
75 \gdef\th@break{%
76     \def\@begintheorem##1##2{%
77         \item[
78             \InlineClass{theoremheader}{##1\ ##2}\newline%
79         ]
80     }%
81 \def\@opargbegintheorem##1##2##3{%
82     \item[
83         \InlineClass{theoremheader}{##1\ ##2\ (##3)}\newline
84     ]
85     }
86 }
87
88 \gdef\th@marginbreak{%
89     \def\@begintheorem##1##2{%
90         \item[
91             \InlineClass{theoremheader}{##2 \quad ##1}\newline
92         ]
93     }%
94 \def\@opargbegintheorem##1##2##3{%
95     \item[
96         \InlineClass{theoremheader}{##2 \quad ##1\ %
97             (##3)}\newline
98     ]
99     }
100 }
101
102 \gdef\th@changebreak{%
103     \def\@begintheorem##1##2{%
104         \item[
105             \InlineClass{theoremheader}{##2\ ##1}\newline
106         ]
107     }%
108 \def\@opargbegintheorem##1##2##3{%
109     \item[
110         \InlineClass{theoremheader}{ ##2\ ##1\ %
111             (##3)}\newline
112     ]
113     }
114 }
115
116 \gdef\th@change{%
117     \def\@begintheorem##1##2{%
118         \item[
119             \InlineClass{theoremheader}{##2\ ##1}
120         ]
121     }%
122 \def\@opargbegintheorem##1##2##3{%
123     \item[
```

```

124     \InlineClass{theoremheader}{##2\ ##1\ (##3)}
125   ]
126   }
127 }
128
129 \gdef\th@margin{%
130   \def\@begintheorem##1##2{
131     \item[
132       \InlineClass{theoremheader}{##2 \quad ##1}
133     ]
134   }%
135 \def\@opargbegintheorem##1##2##3{%
136   \item[
137     \InlineClass{theoremheader}{##2 \quad ##1\ (##3)}
138   ]
139   }
140 }

```

Patched for css:

```

141 \gdef\@thm#1#2{\refstepcounter{#1}%
142 \LWR@forcenewpage% lwarp

143   \LWR@printpendingfootnotes%           lwarp

144   \BlockClass{theorembody\LWR@thisthmstyle}% lwarp
145   \trivlist
146   \@topsep \theorempreskipamount         % used by first \item
147   \@topsepadd \theorempostskipamount     % used by \@endparenv
148   \@ifnextchar [%
149     {\@ythm{#1}{#2}}%
150     {\@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}}
151
152 \gdef\@endtheorem{%
153 \endtrivlist

154   \LWR@printpendingfootnotes%           lwarp

155 \endBlockClass
156 }

```

File 498 **lwarp-thinsp.sty**

§ 607 Package **thinsp**

Pkg thinsp thinsp is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{thinsp}[2016/10/02]

```

2 \AtBeginDocument{
3 \let\thinthinspace\relax% defined by some packages
4 \newcommand*{\thinthinspace}{\thinspace}
5 }
6
7 \newcommand*{\stretchthinspace}{\thinspace}

```

```
8 \newcommand*\stretchthinthinspace{\thinthinspace}
9 \newcommand*\stretchnegthinspace{\negthinspace}
```

File 499 **lwarp-thm-listof.sty**

§ 608 Package **thm-listof**

(Emulates or patches code by ULRICH M. SCHWARZ, YUKAI CHOU.)

Pkg thm-listof

thm-listof is part of thmtools, and is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{thm-listof}[2019/12/22]

For font control, see the generated HTML and use CSS per amsthm or ntheorem.

Other thm-* package may be loaded by thm-listof.

```
2 \IfPackageAtLeastTF{thm-listof}{2020/08/01}{% v0.72
3   \def\thmtlo@newentry{%
4     \csdef{l@thmt@envname}##1##2{\hypertocfloat{1}{figure}{lof}{##1}{##2}}%
5   }
6 }{% earlier than v0.72
7   \xpatchcmd{\listoftheorems}
8     {%
9       \@xa\protected@edef\csname l@thmt@envname\endcsname{%
10        \@nx@dottedtocline{1}{1.5em}{\@nx\thmt@listnumwidth}%
11      }%
12    }
13    {%
14      \csdef{l@thmt@envname}##1##2{\hypertocfloat{1}{figure}{lof}{##1}{##2}}%
15    }
16    {}
17    {\LWR@patcherror{thm-listof}{listoftheorems}}
18
19   \xpatchcmd{\thmt@mklisctcmd}
20     {%
21       \@xa\protected@edef\csname l@thmt@envname\endcsname{%
22        \@nx@dottedtocline{1}{1.5em}{\@nx\thmt@listnumwidth}%
23      }%
24    }
25    {%
26      \csdef{l@thmt@envname}##1##2{\hypertocfloat{1}{figure}{lof}{##1}{##2}}%
27    }
28    {}
29    {\LWR@patcherror{thm-listof}{thmt@mklisctcmd}}
30 }
```

File 500 **lwarp-thm-restate.sty**

§ 609 Package **thm-restate**

(Emulates or patches code by ULRICH M. SCHWARZ.)

Pkg thm-restate

thm-restate is part of thmtools, and is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{thm-restate}[2020/08/01]

2 \xpatchcmd{\thmt@restatable}
3   {\@ifstar}
4   {\edef\LWR@thisthmstyle{#2}\@ifstar}
5   {}
6   {\LWR@patcherror{thm-restate}{thmt@restatable}}
```

File 501 **lwarp-thmbox.sty**

§ 610 Package **thmbox**

(Emulates or patches code by EMMANUEL BEFFARA.)

Pkg thmbox

thmbox is emulated for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{thmbox}[2005/04/24]

2 \renewenvironment{thmbox}[2][[%
3   {%
4     \begin{BlockClass}{thmbox}
5     \begin{BlockClass}{thmboxtitle}
6     #2
7     \end{BlockClass}
8   }
9   {\end{BlockClass}}
10
11 \renewenvironment{proof}[1][[%
12   {%
13     \begin{BlockClass}{thmboxproof}%
14     \InlineClass{thmboxproofname}{\proofname\ #1\unskip\,:}
15   }
16   {%
17     \quad\HTMLUnicode{220E}% end of proof symbol
18     \end{BlockClass}
19   }
20
21 \renewenvironment{example}[1][\examplename]%
22   {%
23     \begin{BlockClass}{thmboxexample}%
24     \InlineClass{thmboxexamplename}{#1\,:}
25   }
26   {\end{BlockClass}}
27
28 \renewenvironment{leftbar}[1][[%
29   {\begin{BlockClass}{thmboxleftbar}}
30   {\end{BlockClass}}
```

File 502 **lwarp-thmtools.sty**

§ 611 Package **thmtools**

(Emulates or patches code by ULRICH M. SCHWARZ.)

Pkg thmtools

thmtools is patched for use by lwarp.

Also see thm-listof and thm-restate.

for HTML output: 1 \LWR@ProvidesPackagePass{thmtools}[2020/08/01]

The following patches either thm-amsthm or thm-ntheorem.

```

2 \def\thmt@headstyle@margin{%
3   \InlineClass{amsthmnumbertheorem}{\NUMBER}
4   \
5   \InlineClass{amsthmnametheorem}{\NAME}
6   \InlineClass{amsthmnotetheorem}{\NOTE}
7 }
8
9 \let\thmt@headstyle@swapnumber\thmt@headstyle@margin

```

File 503 **lwarp-threadcol.sty**§ 612 Package **threadcol**

Pkg threadcol

threadcol is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{threadcol}[2013/01/06]2 \newcommand{\setthreadname}[1]{}

File 504 **lwarp-threeparttable.sty**§ 613 Package **threeparttable***(Emulates or patches code by DONALD ARSENEAU.)*

Pkg threeparttable

threeparttable is emulated.

Table note are contained inside a CSS <div> of class tnotes. If enumitem is used, the note item labels are also individually highlighted with an additional CSS of class tnoteitemheader, otherwise they are plain text.

for HTML output: 1 \LWR@ProvidesPackageDrop{threeparttable}[2003/06/13]

Env threeparttable

```

[<alignment>]
2 \newenvironment*{threeparttable}[1][b]
3   {\def\@capttype{table}}
4   {}

```

Env tablenotes

```

[<options>]
5 \newenvironment*{tablenotes}[1][]
6 {}
7 \LWR@forcenewpage
8 \BlockClass{tnotes}%

```

```

9 \description%
10 }
11 {%
12 \enddescription%
13 \endBlockClass%
14 }

```

`\tnote``{\langle text \rangle}`

```
15 \newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}
```

Env `measuredfigure``[\langle alignment \rangle]`

```

16 \newenvironment*{measuredfigure}[1][t]
17   {\def\@capttype{figure}}
18   {}

```

File 505 **lwarp-threeparttablex.sty**

§ 614 Package

threeparttablexPkg `threeparttablex``threeparttablex` is patched for use by `lwarp`.`threeparttablex` is used with `longtable` and `booktabs` as follows:

```

\begin{longtable}[ [column specifiers] ]
[ . . . ] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[ . . . ] \endhead % or \endfirsthead
[ . . . ] \endfoot
\bottomrule \insertTableNotes \endlastfoot
}
. . . table contents . . .
\warpHTMLonly{ % HTML last footer
\bottomrule
\UseMinipageWidths % optional
\insertTableNotes
\endlastfoot
}
\end{longtable}

```

table width The table notes are created using a `\multicolumn`. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, `lwarp` guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use `\UseMinipageWidths` before `\insertTableNotes`. The width is then specified, and in many cases the result is an improvement in overall table layout.

for HTML output: 1 `\LWR@ProvidesPackagePass{threeparttablex}[2013/07/23]`

The width is guessed depending on the number of columns, then limited to a min/max.

```
2 \renewcommand\insertTableNotes{%
```

```

3   \setlength{\LWR@templengthone}{.375in*\value{LWR@tabletotalLaTeXcols}}%
4   \setlength{\LWR@templengthone}{\minof{\textwidth}{\LWR@templengthone}}%
5   \setlength{\LWR@templengthone}{\maxof{2.5in}{\LWR@templengthone}}%
6   \multicolumn{\value{LWR@tabletotalLaTeXcols}}{c}{%
7     \parbox{\LWR@templengthone}{%
8       \begin{tablenotes}[\TPTL@optarg]%
9         \TPTL@font%
10        \TPTL@body%
11        \end{tablenotes}%
12      }%
13    }%
14  }

15 \providecommand{\TPTL@tnotex}{}
16 \renewcommand{\TPTL@tnotex}[2]{\tnote{\nameref{#2}}}
```

File 506 **lwarp-thumb.sty**

§ 615 Package **thumb**

Pkg thumb thumb is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{thumb}[1997/12/24]

```

2 \newcommand*\Overviewpage{}
3 \newlength{\thumbheight}
4 \newlength{\thumbwidth}
```

File 507 **lwarp-thumbs.sty**

§ 616 Package **thumbs**

Pkg thumbs thumbs is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{thumbs}[2014/03/09]

```

2 \newcommand{\addthumb}[4]{}
3 \newcommand{\addtitlethumb}[5]{}
4 \newcommand{\stopthumb}{}
5 \newcommand{\continuethumb}{}
6 \newcommand{\thumbsoverview}[1]{}
7 \newcommand{\thumbsoverviewback}[1]{}
8 \newcommand{\thumbsoverviewverso}[1]{}
9 \newcommand{\thumbsoverviewdouble}[1]{}
10 \newcommand{\thumbnewcolumn}{}
11 \newcommand{\addthumbsoverviewtocontents}[2]{}
12 \newcommand{\thumbsnophantom}{}

```

File 508 **lwarp-tikz.sty**

§ 617 Package **tikz**

(Emulates or patches code by TILL TANTAU.)

Pkg tikz tikz is supported.

 **displaymath and matrices** If using display math with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the `tikz` expression must be replaced with `\&`.

Accept all options for `lwarp-tikz`:

```
1 \LWR@ProvidesPackagePass{tikz}[2015/08/07]
```

catcodes `lwarp` changes the catcode of `$` for its own use. The `Tikz babel` library temporarily changes catcodes back to normal for `Tikz`'s use. `tikz v3.0.0` introduced the `babel` library which handles catcode changes. For older versions, `lwarp` must change `$`'s catcode itself.

Also see:

<https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded>

```
2 \newbool{LWR@tikzbabel}
3
4 \IfPackageAtLeastTF{tikz}{2013/12/20}% Test for Tikz version v3.0.0
5 {\usetikzlibrary{babel}\booltrue{LWR@tikzbabel}}
6 {\boolfalse{LWR@tikzbabel}}
```

Env `pgfpicture` The `\pgfpicture` environment is enclosed inside a `\lateximage`. Enclose the low-level `\pgfpicture` in a `lateximage`. This is also used by the higher-level `\tikz` and `tikzpicture`.

```
7 \preto\pgfpicture{%
8   \begin{lateximage}[-tikz-~\PackageDiagramAltText]%
9     \ifbool{LWR@tikzbabel}% Test for Tikz version v3.0.0
10    {%
11      {\catcode'\$=3}% dollar sign is math shift
12    }
13  }
14 \appto\endpgfpicture{\end{lateximage}}
```

`Tikz` is placed inside an `svg` image, so use the original meanings of the following:

```
15 \LetLtxMacro\pgfutil@minipage\LWR@print@minipage
16 \let\pgfutil@endminipage\endLWR@print@minipage
17
18 \let\pgfutil@raggedleft\LWR@print@raggedleft
19 \let\pgfutil@raggedright\LWR@print@raggedright

20 \def\pgfutil@font@tiny{\LWR@print@tiny}
21 \def\pgfutil@font@scriptsize{\LWR@print@scriptsize}
22 \def\pgfutil@font@footnotesize{\LWR@print@footnotesize}
23 \def\pgfutil@font@small{\LWR@print@small}
24 \def\pgfutil@font@normalsize{\LWR@print@normalsize}
25 \def\pgfutil@font@large{\LWR@print@large}
26 \def\pgfutil@font@Large{\LWR@print@Large}
```

```

27 \def\pgfutil@font@huge{\LWR@print@huge}
28 \def\pgfutil@font@Huge{\LWR@print@Huge}
29
30 \def\pgfutil@font@itshape{\LWR@print@itshape}
31 \def\pgfutil@font@bfseries{\LWR@print@bfseries}
32
33 \def\pgfutil@font@normalfont{\LWR@print@normalfont}

```

File 509 **lwarp-tikz-imagelabels.sty**

§ 618 Package **tikz-imagelabels**

(Emulates or patches code by TOBIAS PLÜSS.)

Pkg tikz-imagelabels tikz-imagelabels is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{tikz-imagelabels}[2019/06/27]
2 \BeforeBeginEnvironment{annotationimage}{%
3   \begin{lateximage}[-tikz-imagelabels-~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{annotationimage}{\end{lateximage}}

```

File 510 **lwarp-titles.sty**

§ 619 Package **titles**

(Emulates or patches code by JAVIER BEZOS.)

Pkg titles titles is loaded and used by lwarp during HTML output. All user options and macros are ignored and disabled.

Discard all options for lwarp-titles:

for HTML output:

```

1 \LWR@ProvidesPackageDrop{titles}[2016/03/15]

```

`\pagestyle` and `\thispagestyle` are already disabled in the lwarp code.

```

\newpagestyle      {<name>} [<style>] {<commands>}
2 \NewDocumentCommand{\newpagestyle}{m o m}{ }

```

```

\renewpagestyle    {<name>} [<style>] {<commands>}
3 \NewDocumentCommand{\renewpagestyle}{m o m}{ }

```

```

\sethead           [<el>] [<ec>] [<er>] {<ol>} {<oc>} {<or>}
4 \NewDocumentCommand{\sethead}{o o o m m m}{ }

```

```

\setfoot           [<el>] [<ec>] [<er>] {<ol>} {<oc>} {<or>}
5 \NewDocumentCommand{\setfoot}{o o o m m m}{ }

```

<code>\settlemarks</code>	<code>* {<names>}</code> <code>6 \NewDocumentCommand{\settlemarks}{s m}{}</code>
<code>\headrule</code>	<code>7 \newcommand*{\headrule}{}</code>
<code>\footrule</code>	<code>8 \newcommand*{\footrule}{}</code>
<code>\setheadrule</code>	<code>{<length>}</code> <code>9 \newcommand*{\setheadrule}[1]{}</code>
<code>\setfootrule</code>	<code>{<length>}</code> <code>10 \newcommand*{\setfootrule}[1]{}</code>
<code>\makeheadrule</code>	<code>11 \newcommand*{\makeheadrule}{}</code>
<code>\makefootrule</code>	<code>12 \newcommand*{\makefootrule}{}</code>
<code>\setmarkboth</code>	<code>{<code>}</code> <code>13 \newcommand{\setmarkboth}[1]{}</code>
<code>\widenhead</code>	<code>14 \NewDocumentCommand{\widenhead}{s o o m m}{}</code>
<code>\bottitlemarks</code>	<code>15 \newcommand*{\bottitlemarks}{}</code>
<code>\toptitlemarks</code>	<code>16 \newcommand*{\toptitlemarks}{}</code>
<code>\firsttitlemarks</code>	<code>17 \newcommand*{\firsttitlemarks}{}</code>
<code>\nexttitlemarks</code>	<code>18 \newcommand*{\nexttoptitlemarks}{}</code>
<code>\outertitlemarks</code>	<code>19 \newcommand*{\outertitlemarks}{}</code>

<code>\innertitlemarks</code>		<code>20 \newcommand*\innertitlemarks{}</code>
<code>\newtitlemark</code>	<code>* {<name>}</code>	<code>21 \NewDocumentCommand{\newtitlemark}{s m}{}</code>
<code>\pretitlemark</code>	<code>* {<section> } {<text>}</code>	<code>22 \NewDocumentCommand{\pretitlemark}{s m m}{}</code>
<code>\ifsamemark</code>	<code>{<group> } {<command> } {<>true> } {<>false>}</code>	<code>23 \newcommand{\ifsamemark}[4]{}</code>
<code>\setfloathead</code>	<code>* [<.>] [<.>] [<.>] {<.>} {<.>} {<.>} {<extra>} [<which>]</code>	<code>24 \NewDocumentCommand{\setfloathead}{s o o m m m m m}{}</code>
<code>\setfloatfoot</code>	<code>* [<.>] [<.>] [<.>] {<.>} {<.>} {<.>} {<extra>} [<which>]</code>	<code>25 \NewDocumentCommand{\setfloatfoot}{s o o m m m m m}{}</code>
<code>\nextfloathead</code>	<code>* [<.>] [<.>] [<.>] {<.>} {<.>} {<.>} {<extra>} [<which>]</code>	<code>26 \NewDocumentCommand{\nextfloathead}{s o o m m m m m}{}</code>
<code>\nextfloatfoot</code>	<code>* [<.>] [<.>] [<.>] {<.>} {<.>} {<.>} {<extra>} [<which>]</code>	<code>27 \NewDocumentCommand{\nextfloatfoot}{s o o m m m m m}{}</code>
<code>\newmarkset</code>	<code>{<markset>}</code>	<code>28 \newcommand{\newmarkset}[1]{}</code>
<code>\newextramark</code>	<code>* {<markset> } {<macro-name>}</code>	<code>29 \NewDocumentCommand{\newextramarkset}{s m m}{}</code>
<code>\botextramarks</code>	<code>{<markset>}</code>	<code>30 \newcommand{\botextramarks}[1]{}</code>
<code>\topextramarks</code>	<code>{<markset>}</code>	<code>31 \newcommand{\topextramarks}[1]{}</code>
<code>\firstextramarks</code>	<code>{<markset>}</code>	<code>32 \newcommand{\firstextramarks}[1]{}</code>
<code>\nextextramarks</code>	<code>{<markset>}</code>	<code>33 \newcommand{\nexttopextramarks}[1]{}</code>

`\outerextramarks` $\langle\mathit{markset}\rangle$
`34 \newcommand{\outerextramarks}[1]{}`

`\innerextramarks` $\langle\mathit{markset}\rangle$
`35 \newcommand{\innerextramarks}[1]{}`

File 511 **lwarp-titleref.sty**

§ 620 Package **titleref**

Pkg titleref titleref is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{titleref}[2001/04/05]
2
3 \LetLtxMacro\titleref\nameref
4
5 \providecounter{LWR@currenttitle}
6
7 \newcommand*{\currenttitle}{%
8   \addtocounter{LWR@currenttitle}{1}%
9   \label{currenttitle\arabic{LWR@currenttitle}}%
10  \nameref{currenttitle\arabic{LWR@currenttitle}}%
11 }
12
13 \newcommand*{\theTitleReference}[2]{}
```

File 512 **lwarp-titlesec.sty**

§ 621 Package **titlesec**

(Emulates or patches code by JAVIER BEZOS.)

Pkg titlesec titlesec is emulated. All user options and macros are ignored and disabled.

Discard all options for `lwarp-titlesec`:

for HTML output:

```

1 \PackageInfo{lwarp}{Using the lwarp version of package ‘titlesec’.%}
2 \ProvidesPackage{lwarp-titlesec}[2016/03/21]
3
4 \newbool{LWR@loadtitleps}
5 \boolfalse{LWR@loadtitleps}
6
7 \DeclareOption{pagestyles}{
8   \booltrue{LWR@loadtitleps}
9 }
10
11 \DeclareOption*{}
12
13 \ProcessOptions\relax
14
15 \ifbool{LWR@loadtitleps}{
16   \RequirePackage{lwarp-titleps}
```

17 }{}

`\titlelabel` $\langle label-format \rangle$

18 `\newcommand*\titlelabel[1]{}{}`

`\titleformat*` $\langle command \rangle \langle format \rangle$

`\titleformat` $\langle command \rangle [\langle shape \rangle] \langle format \rangle \langle label \rangle \langle sep \rangle \langle before \rangle [\langle after \rangle]$

19 `\newcommand\titleformat%`

20 `\ifstar{\ttl@format@s}%`

21 `\ttl@format@i}`

22 `\newcommand{\ttl@format@s}[1]{}{}`

23 `\NewDocumentCommand{\ttl@format@i}{m o m m m o}{}{}`

`\chaptertitlename`

24 `\ifundefined{@chapapp}{\let\@chapapp\chaptername}{}{}`

25 `\newcommand\chaptertitlename{\@chapapp}`

`\titlespacing` * $\langle command \rangle \langle left \rangle \langle before \rangle \langle after \rangle [\langle right \rangle]$

26 `\NewDocumentCommand{\titlespacing}{s m m m m o}{}{}`

`\filright`

27 `\newcommand*\filright{}{}`

`\filcenter`

28 `\newcommand*\filcenter{}{}`

`\filleft`

29 `\newcommand*\filleft{}{}`

`\filllast`

30 `\newcommand*\filllast{}{}`

`\filinner`

31 `\newcommand*\filinner{}{}`

`\filouter`

32 `\newcommand*\filouter{}{}`

`\wordsep`

33 `\newcommand\wordsep{\fontdimen\tw@font \@plus`

34 `\fontdimen\thr@font \@minus \fontdimen4\font}`

`\titleline` * $[\langle align \rangle] \langle material \rangle$

```
35 \NewDocumentCommand{\titleline}{s o m}{}

```

\titlerule

[*<height>*]

```
36 \providecommand*\titlerule{\@ifstar{\ttl@row}{\ttl@rule}}
37 \newcommand*\ttl@rule[1]{}{}
38 \newcommand*\ttl@row[2]{}{}

```

\iftitlemeasuring

{*<true>*} {*<false>*}

```
39 \newcommand{\iftitlemeasuring}[2]{#2}

```

\assignpagestyle

{*<command>*} {*<pagestyle>*}

```
40 \newcommand{\assignpagestyle}[2]{#2}

```

\titleclass

{*<name>*} [*<startlevel>*] {*<class>*} [*<cmd>*]

```
41 \NewDocumentCommand{\titleclass}{m o m o}{}

```

File 513 **lwarp-titletoc.sty**

§ 622 Package **titletoc**

(Emulates or patches code by JAVIER BEZOS.)

Pkg titletoc

titletoc is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titletoc:

for HTML output: 1 \LWR@ProvidesPackageDrop{titletoc}[2011/12/15]

\dottedcontents

{*<section>*} [*<left>*] {*<above>*} {*<label>*} {*<leader>*}

```
2 \NewDocumentCommand{\dottedcontents}{m o m m m}{}

```

\titlecontents

* {*<section>*} [*<left>*] {*<above>*} {*<numbered>*} {*<numberless>*} {*<filler>*} [*<below or begin>*] [*<separator>*] [*<end>*]

```
3 \newcommand{\titlecontents}{\@ifstar{\ttl@tcstar}{\ttl@tcnostar}}
4 \NewDocumentCommand{\ttl@tcstar}{m o m m m o o}{}
5 \NewDocumentCommand{\ttl@tcnostar}{m o m m m m o}{}

```

\contentsmargin

[*<correction>*] {*<right>*}

```
6 \newcommand{\contentsmargin}[2]{}{}

```

\thecontentslabel

```
7 \newcommand*\thecontentslabel{\thecontentslabel}

```

\thecontentspage

```
8 \newcommand*\thecontentspage{\thecontentspage}

```

<code>\contentslabel</code>	<code>[\langle format \rangle] {\langle space \rangle}</code> 9 <code>\newcommand{\contentslabel}[2][\thecontentslabel]</code>
<code>\contentspage</code>	<code>[\langle format \rangle]</code> 10 <code>\newcommand{\contentspage}[1][\thecontentspage]</code>
<code>\contentspush</code>	<code>{\langle text \rangle}</code> 11 <code>\newcommand{\contentspush}[1]{}</code>
<code>\contentsuse</code>	<code>{\langle name \rangle} {\langle text \rangle}</code> 12 <code>\newcommand{\contentsuse}[2]{}</code>
<code>\startcontents</code>	<code>[\langle name \rangle]</code> 13 <code>\newcommand*\startcontents[1][{}]</code>
<code>\stopcontents</code>	<code>[\langle name \rangle]</code> 14 <code>\newcommand*\stopcontents[1][{}]</code>
<code>\resumecontents</code>	<code>[\langle name \rangle]</code> 15 <code>\newcommand*\resumecontents[1][{}]</code>
<code>\printcontents</code>	<code>[\langle name \rangle] {\langle prefix \rangle} {\langle start \rangle} {\langle code \rangle}</code> 16 <code>\newcommand{\printcontents}[4][{}]</code>
<code>\startlist</code>	<code>[\langle name \rangle] {\langle list \rangle}</code> 17 <code>\newcommand{\startlist}[2][{}]</code>
<code>\stoplist</code>	<code>[\langle name \rangle] {\langle list \rangle}</code> 18 <code>\newcommand{\stoplist}[2][{}]</code>
<code>\resumelist</code>	<code>[\langle name \rangle] {\langle list \rangle}</code> 19 <code>\newcommand{\resumelist}[2][{}]</code>
<code>\printlist</code>	<code>[\langle name \rangle] {\langle list \rangle} {\langle prefix \rangle} {\langle code \rangle}</code> 20 <code>\newcommand{\printlist}[4][{}]</code>

File 514 **lwarp-titling.sty**

§ 623 Package **titling**

(Emulates or patches code by PETER WILSON.)

Pkg titling

package support lwarp supports the native L^AT_EX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

 **load order**

\published and \subtitle If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 69.8.

The various titling footnote restyling commands have no effect.

Pass all options to lwarp-titling:

for HTML output: `1 \LWR@ProvidesPackagePass{titling}[2009/09/04]`

\bsmtitleempty Patch \bsmtitleempty:

```
2 \let\LWR@orig@bsmtitleempty\bsmtitleempty
3 \renewcommand*{\bsmtitleempty}{%
4 \LWR@orig@bsmtitleempty%
5 }
```

\keepthetitle Patch \keepthetitle:

```
6 \let\LWR@origkeepthetitle\keepthetitle
7 \renewcommand*{\keepthetitle}{%
8 \LWR@orig@keepthetitle%
9 }
```

\killtitle Patch \killtitle:

```
10 \let\LWR@origkilltitle\killtitle
11 \renewcommand*{\killtitle}{%
12 \LWR@orig@killtitle%
13 }
```

Env titlingpage

```
14 \renewenvironment*{titlingpage}
15 {%
```

Start an HTML titlepage div:

```
16 \LWR@printpendingfootnotes
17 \begin{titlepage}
```

Prepare for a custom version of \maketitle inside the titlingpage:

```
18 \LWR@maketitlesetup
19 \let\maketitle\LWR@titlingmaketitle
20 }
21 {
```

At the end of the environment, end the HTML titlepage div:

```
22 \end{titlepage}
23 }
```

Patch the pre/post title/author/date to add HTML tags, then initialize:

```

24 \AtBeginDocument{
25   \pretitle{}
26   \posttitle{}
27
28   \preauthor{}
29   \postauthor{}
30
31   \predate{}
32   \postdate{}
33 }

```

`\LWR@maketitlesetup` Patches `\thanks` macros.

```
34 \renewcommand*\LWR@maketitlesetup{%
```

Redefine the footnote mark:

```

35   \def\@makefnmark{\textsuperscript{\@thefnmark}}%
        \thefootnote ⇒ \nameuse{arabic}{footnote}, or
        \thefootnote ⇒ \nameuse{fnsymbol}{footnote}

```

Redefine the footnote text:

```
36   \long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```

37       \makethanksmark~%
        \makethanksmark ⇒ \thanksfootmark ⇒ \tamark ⇒
        \@thefnmark ⇒ \itshape a (or similar)

```

Print the text:

```

38       {##1}%
39   }% \@makefntext
40 }

```

`\thanksfootmark`

```

41 \renewcommand{\thanksfootmark}{%
42 %   \hb@xt@\thanksmarkwidth{\hfil\normalfont%
43     \thanksscript{%
44       \thanksfootpre \tamark \thanksfootpost%
45     }}%
46 %   }%
47 }

```

`\maketitle` HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
48 \renewcommand*\maketitle{%
```

An HTML titlepage <div> is used for all classes.

```
49 \begin{titlepage}
```

Select which kind of footnote marks to use:

```
50 \@bsmarkseries
```

Set up special patches:

```
51 \LWR@maketitlesetup
```

Typeset the title, etc:

```
52 \@maketitle
```

Immediately generate any \thanks footnotes:

```
53 \LWR@stoppars\@thanks\LWR@startpars
```

Close the HTML titlepage div:

```
54 \end{titlepage}
```

Reset the footnote counter:

```
55 \@bscontmark
```

```
56 }
```

`\@maketitle` Typesets the title, etc. Patched for HTML.

```
57 \providecommand*{\@maketitle}{}
58 \renewrobustcmd{\@maketitle}{%
59   \maketitlehooka
60   {
61     \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
62     \@spretitle \@title \@bsposttitle%
63     \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
64   }
65   \maketitlehookb
66   {
67     \begin{BlockClass}{author}
68     \renewcommand{\and}{%
69       \end{BlockClass}%
70       \begin{BlockClass}{oneauthor}%
71     }
72     \begin{BlockClass}{oneauthor}%
73     \@bspreauthor \@author \@bspostauthor%
74     \end{BlockClass}%
75     \end{BlockClass}%
76   }
77   \maketitlehookc
78   {
79     \begin{BlockClass}{titledate}%
80     \@bspredate \@date \@bspostdate%
81     \end{BlockClass}%
82   }
```

```
83 \maketitlehookd
84 }
```

`\LWR@titlingmaketitle` `\maketitle` for use inside an HTML titlingpage environment.

```
85 \renewcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
86 \LWR@stoppars\@thanks\LWR@startpars
```

Select which kind of footnote marks to use:

```
87 \@bsmarkseries
```

Set up special patches:

```
88 \LWR@maketitlesetup
```

Typeset the title, etc:

```
89 \@maketitle
```

Immediately generate any `\thanks` footnotes:

```
90 \LWR@stoppars\@thanks\LWR@startpars
```

Reset the footnote counter:

```
91 \@bscontmark
92 }
```

`\thanksmarkseries` `{\series}`

Sets the type of footnote marks used by `\thanks`, where type is ‘arabic’, ‘roman’, ‘fnsymbol’, etc.

```
93 \renewcommand{\thanksmarkseries}[1]{%
94 \def\@bsmarkseries{\renewcommand{\thefootnote}{\@nameuse{#1}{footnote}}}%
95 }
```

Set default titlepage thanks footnote marks. See section [69.7](#).

```
96 \IfClassLoadedTF{memoir}{
97   \thanksmarkseries{arabic}
98 }{% not memoir
99 \if@titlepage
100   \thanksmarkseries{arabic}
101 \else
102   \thanksmarkseries{fnsymbol}
103 \fi
104 }% not memoir
```

File 515 **lwarp-tocbasic.sty**

§ 624 Package **tocbasic**

(Emulates or patches code by MARKUS KOHM.)

Pkg tocbasic

tocbasic is nullified for lwarp.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. `\DeclareDocumentCommand` is used to overwrite the koma-script definitions.

for HTML output:

```
1 \LWR@ProvidesPackagePass{tocbasic}[2018/12/30]

2 \DeclareDocumentCommand{\usetocbasicnumberline}{o}{}
3 \DeclareDocumentCommand{\DeclareTOCStyleEntry}{o m m}{}
4 \DeclareDocumentCommand{\DeclareTOCStyleEntries}{o m m}{}
5 \DeclareDocumentCommand{\DeclareTOCEntryStyle}{m o m}{}
6 \DeclareDocumentCommand{\DefineTOCEntryOption}{m o m}{}
7 \DeclareDocumentCommand{\DefineTOCEntryBooleanOption}{m o m m}{}
8 \DeclareDocumentCommand{\DefineTOCEntryCommandOption}{m o m m}{}
9 \DeclareDocumentCommand{\DefineTOCEntryIfOption}{m o m m}{}
10 \DeclareDocumentCommand{\DefineTOCEntryLengthOption}{m o m m}{}
11 \DeclareDocumentCommand{\DefineTOCEntryNumberOption}{m o m m}{}
12 \DeclareDocumentCommand{\CloneTOCEntryStyle}{m m}{}
13 \DeclareDocumentCommand{\TOCEntryStyleInitCode}{m m}{}
14 \DeclareDocumentCommand{\TOCEntryStyleStartInitCode}{m m}{}

```

File 516 **lwarp-tocbibind.sty**

§ 625 Package **tocbibind**

(Emulates or patches code by PETER WILSON.)

Pkg tocbibind

tocbibind is patched for use by lwarp.

[placement and toc options](#)

An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx

Inline, with a manual toc entry:

A commonly-used method to introduce an index in a \LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex

```

Pkg makeidx

On its own HTML page, with a manual TOC entry:

```

\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex

```

Pkg tocbibind

Inline, with an automatic TOC entry:

The tocbibind package may be used to automatically place an entry in the TOC.

```

\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex

```

Pkg tocbibind

On its own HTML page, with an automatic TOC entry:

```

\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex

```

Opt [tocbibind] numindex

numbered index section

Use the tocbibind numindex option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

for HTML output:

```

1 \let\simplechapterdelim\relax
2
3 \LWR@ProvidesPackagePass{tocbibind}[2010/10/13]

4 \renewenvironment{theindex}%
5 {%
6   \if@bibchapter
7     \if@donumindex
8       \chapter{\indexname}
9     \else
10      \if@dotocind
11        \chapter*{\indexname}
12        \addcontentsline{toc}{chapter}{\LWR@isolate{\indexname}}
13      \else
14        \chapter*{\indexname}
15      \fi
16    \fi
17  \else
18    \if@donumindex
19      \section{\indexname}
20    \else
21      \if@dotocind
22        \section*{\indexname}
23        \addcontentsline{toc}{\@tocextra}{\LWR@isolate{\indexname}}
24      \else

```

```

25         \section*{\indexname}
26         \fi
27     \fi
28     \fi
29 \LetLtxMacro\item\LWR@indexitem%
30 \LetLtxMacro\subitem\LWR@indexsubitem%
31 \LetLtxMacro\subsubitem\LWR@indexsubsubitem%
32 }{}

```

The following code is shared by anonchap.

```

33 \DeclareDocumentCommand{\simplechapter}{0{\@empty}}{%
34     \def\@chapcntformat##1{%
35         #1~\csname the##1\endcsname\simplechapterdelim\quad%
36     }%
37 }
38
39 \DeclareDocumentCommand{\restorechapter}{}{%
40 \let\@chapcntformat\@seccntformat%
41 }

```

File 517 **lwarp-tocdata.sty**

§ 626 Package **tocdata**

(Emulates or patches code by BRIAN DUNN.)

Pkg tocdata

tocdata is patched for use by lwarp.

```

for HTML output: 1 \LWR@ProvidesPackagePass{tocdata}[2019/07/06]

2 \renewcommand*{\LWR@maybetocdata}{%
3     \ifdefempty{\TD@thistocdata}}{%
4         \qqquad \InlineClass{authorartist}{\tocdataformat{\TD@thistocdata}}%
5         \def\TD@thistocdata{}
6     }
7 }

8 \renewrobustcmd{\tocdatapartprint}[4]
9 {%
10     \InlineClass{authorartist}{%
11         \qqquad --- %
12         \TDOptionalnameprint{#1}\TDOptionalnameprint{#2}#3#4%
13     }%
14 }
15
16 \@ifundefined{chapter}{}{
17     \let\tocdatachapterprint\tocdatapartprint
18 }
19 \let\tocdatasectionprint\tocdatapartprint
20 \let\tocdatasubsectionprint\tocdatapartprint
21
22 \newcommand*{\LWR@TD@settetextalign}[1]{%
23     \def\LWR@TD@textalign{justify}%
24     \ifcsstring{TD@#1align}{\centering}%

```

```

25     {\def\LWR@TD@textalign{center}}%
26     {}%
27     \ifcsstring{TD@#1align}{\raggedleft}%
28     {\def\LWR@TD@textalign{right}}%
29     {}%
30     \ifcsstring{TD@#1align}{\raggedright}%
31     {\def\LWR@TD@textalign{left}}%
32     {}%
33 }
34
35 \renewcommand{\TDartistauthorprint}[5]{%
36   \LWR@TD@setttextalign{#1}%
37   \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
38   \InlineClass{authorartist}{\TDoptionalnameprint{#2}\TDoptionalnameprint{#3}#4#5}%
39   \end{BlockClass}%
40 }
41
42 \newcommand*\LWR@TD@setnamealign[1]{%
43   \def\LWR@TD@textalign{justify}%
44   \ifcsstring{TD@#1textalign}{\centering}%
45   {\def\LWR@TD@textalign{center}}%
46   {}%
47   \ifcsstring{TD@#1textalign}{\raggedleft}%
48   {\def\LWR@TD@textalign{right}}%
49   {}%
50   \ifcsstring{TD@#1textalign}{\raggedright}%
51   {\def\LWR@TD@textalign{left}}%
52   {}%
53 }
54
55 \renewcommand{\TDartistauthortextprint}[2]{%
56   \LWR@TD@setnamealign{#1}%
57   \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
58   #2%
59   \end{BlockClass}%
60 }

```

File 518 **lwarp-tocenter.sty**

§ 627 Package **tocenter**

Pkg tocenter

tocenter is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{tocenter}[2004/12/09]

2 \NewDocumentCommand{\ToCenter}{s o m m}{}
3 \NewDocumentCommand{\FromMargins}{s o m m m m}{}

```

File 519 **lwarp-tocloft.sty**

§ 628 Package **tocloft**

(Emulates or patches code by PETER WILSON.)

Pkg tocloft

tocloft is emulated. Most user options and macros are ignored and disabled.

`\newlistof` and `\cftchapterprecis` are supported.

Pkg `tocloft`

 **tocloft & other packages**

If using `tocloft` with `tocbibind`, `anonchap`, `fnycchap`, or other packages which change chapter title formatting, load `tocloft` with its `titles` option, which tells `tocloft` to use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

Discard all options for `lwarp-tocloft`:

for HTML output:

1 `\LWR@ProvidesPackageDrop{tocloft}[2017/08/31]`

`\tocloftpagestyle`

`{\langle style \rangle}`

2 `\newcommand{\tocloftpagestyle}[1]{}{}`

`\cftmarktoc`

3 `\newcommand*{\cftmarktoc}{}{}`

`\cfttoctitlefont`

4 `\newcommand*{\cfttoctitlefont}{}{}`

`\cftaftertocitle`

5 `\newcommand*{\cftaftertocitle}{}{}`

6 `\newlength{\cftbeforetoctitleskip}`

7 `\newlength{\cftaftertocitleskip}`

`\cftmarklof`

8 `\newcommand*{\cftmarklof}{}{}`

`\cftloftitlefont`

9 `\newcommand*{\cftloftitlefont}{}{}`

`\cftafterloftitle`

10 `\newcommand*{\cftafterloftitle}{}{}`

11 `\newlength{\cftbeforeloftitleskip}`

12 `\newlength{\cftafterloftitleskip}`

`\cftmarklot`

13 `\newcommand*{\cftmarklot}{}{}`

`\cftlottitlefont`

14 `\newcommand*{\cftlottitlefont}{}{}`

`\cftafterlottitle`

15 `\newcommand*{\cftafterlottitle}{}{}`

```

16 \newlength{\cftbeforelottitleskip}
17 \newlength{\cftafterlottitleskip}

\cftdot
18 \providecommand*\cftdot}{.}

\cftdotsep
19 \providecommand*\cftdotsep}{1}

\cftnodots
20 \providecommand*\cftnodots}{5000}

\cftdotfill
  {<sep>}
21 \providecommand{\cftdotfill}[1]{

\cftsetpnumwidth
  {<length>}
22 \DeclareDocumentCommand{\cftsetpnumwidth}{m}{}

\cftsetrmarg
  {<length>}
23 \DeclareDocumentCommand{\cftsetrmarg}{m}{}

\cftpnumalign
  {<alignment>}
24 \DeclareDocumentCommand{\cftpnumalign}{m}{}

25 \LWR@providelength{\cftparskip}

```

The part-related items are also provided by memoir:

```

26 \LWR@providelength{\cftbeforepartskip}
27 \LWR@providelength{\cftpartindent}
28 \LWR@providelength{\cftpartnumwidth}
29 \providecommand*\cftpartfont}{}
30 \providecommand*\cftpartpresnum}{}
31 \providecommand*\cftpartaftersnum}{}
32 \providecommand*\cftpartaftersnumb}{}
33 \providecommand*\cftpartleader}{}
34 \providecommand*\cftpartdotsep}{1}
35 \providecommand*\cftpartpagefont}{}
36 \providecommand*\cftpartafterpnum}{}

```

memoir uses the full name “chapter” instead of “chap”:

```

37 \LWR@providelength{\cftbeforechapskip}
38 \LWR@providelength{\cftchapindent}
39 \LWR@providelength{\cftchapnumwidth}
40 \newcommand*\cftchapfont}{}
41 \newcommand*\cftchappresnum}{}
42 \newcommand*\cftchapaftersnum}{}
43 \newcommand*\cftchapaftersnumb}{}
44 \newcommand*\cftchapleader}{}

```

```

45 \newcommand*\cftchapdotsep}{1}
46 \newcommand*\cftchappagefont}{}
47 \newcommand*\cftchapafterpnum}{}

```

The following do not appear in memoir:

```

48 \LWR@providelength{\cftbeforesecskip}
49 \LWR@providelength{\cftsecindent}
50 \LWR@providelength{\cftsecnumwidth}
51 \newcommand*\cftsecfont}{}
52 \newcommand*\cftsecpresnum}{}
53 \newcommand*\cftsecaftersnum}{}
54 \newcommand*\cftsecaftersnumb}{}
55 \newcommand*\cftsecleader}{}
56 \newcommand*\cftsecdotsep}{1}
57 \newcommand*\cftsecpagefont}{}
58 \newcommand*\cftsecafterpnum}{}

```

```

59 \LWR@providelength{\cftbeforesubsecskip}
60 \LWR@providelength{\cftsubsecindent}
61 \LWR@providelength{\cftsubsecnumwidth}
62 \newcommand*\cftsubsecfont}{}
63 \newcommand*\cftsubsecpresnum}{}
64 \newcommand*\cftsubsecaftersnum}{}
65 \newcommand*\cftsubsecaftersnumb}{}
66 \newcommand*\cftsubsecleader}{}
67 \newcommand*\cftsubsecdotsep}{1}
68 \newcommand*\cftsubsecpagefont}{}
69 \newcommand*\cftsubsecafterpnum}{}

```

```

70 \LWR@providelength{\cftbeforesubsubsecskip}
71 \LWR@providelength{\cftsubsubsecindent}
72 \LWR@providelength{\cftsubsubsecnumwidth}
73 \newcommand*\cftsubsubsecfont}{}
74 \newcommand*\cftsubsubsecpresnum}{}
75 \newcommand*\cftsubsubsecaftersnum}{}
76 \newcommand*\cftsubsubsecaftersnumb}{}
77 \newcommand*\cftsubsubsecleader}{}
78 \newcommand*\cftsubsubsecdotsep}{1}
79 \newcommand*\cftsubsubsecpagefont}{}
80 \newcommand*\cftsubsubsecafterpnum}{}

```

```

81 \LWR@providelength{\cftbeforeparaskip}
82 \LWR@providelength{\cftparaindent}
83 \LWR@providelength{\cftparanumwidth}
84 \newcommand*\cftparafont}{}
85 \newcommand*\cftparapresnum}{}
86 \newcommand*\cftparaaftersnum}{}
87 \newcommand*\cftparaaftersnumb}{}
88 \newcommand*\cftparaleader}{}
89 \newcommand*\cftparadotsep}{1}
90 \newcommand*\cftparapagefont}{}
91 \newcommand*\cftparaafterpnum}{}

```

```

92 \LWR@providelength{\cftbeforesubparaskip}
93 \LWR@providelength{\cftsubparindent}
94 \LWR@providelength{\cftsubparanumwidth}
95 \newcommand*\cftsubparafont}{}
96 \newcommand*\cftsubparapresnum}{}

```

```
97 \newcommand*\cftsubparaaftersnum}{  
98 \newcommand*\cftsubparaaftersnumb}{  
99 \newcommand*\cftsubparaleader}{  
100 \newcommand*\cftsubparadotsep}{1}  
101 \newcommand*\cftsubparapagefont}{  
102 \newcommand*\cftsubparaafterpnum}{  
  
103 \LWR@providelength{\cftbeforefigskip}  
104 \LWR@providelength{\cftfigindent}  
105 \LWR@providelength{\cftfignumwidth}  
106 \newcommand*\cftfigfont}{  
107 \newcommand*\cftfigpresnum}{  
108 \newcommand*\cftfigaftersnum}{  
109 \newcommand*\cftfigaftersnumb}{  
110 \newcommand*\cftfigleader}{  
111 \newcommand*\cftfigdotsep}{1}  
112 \newcommand*\cftfigpagefont}{  
113 \newcommand*\cftfigafterpnum}{  
  
114 \LWR@providelength{\cftbeforesubfigskip}  
115 \LWR@providelength{\cftsubfigindent}  
116 \LWR@providelength{\cftsubfignumwidth}  
117 \newcommand*\cftsubfigfont}{  
118 \newcommand*\cftsubfigpresnum}{  
119 \newcommand*\cftsubfigaftersnum}{  
120 \newcommand*\cftsubfigaftersnumb}{  
121 \newcommand*\cftsubfigleader}{  
122 \newcommand*\cftsubfigdotsep}{1}  
123 \newcommand*\cftsubfigpagefont}{  
124 \newcommand*\cftsubfigafterpnum}{  
  
125 \LWR@providelength{\cftbeforetabskip}  
126 \LWR@providelength{\cfttabindent}  
127 \LWR@providelength{\cfttabnumwidth}  
128 \newcommand*\cfttabfont}{  
129 \newcommand*\cfttabpresnum}{  
130 \newcommand*\cfttabaftersnum}{  
131 \newcommand*\cfttabaftersnumb}{  
132 \newcommand*\cfttableader}{  
133 \newcommand*\cfttabdotsep}{1}  
134 \newcommand*\cfttabpagefont}{  
135 \newcommand*\cfttabafterpnum}{  
  
136 \LWR@providelength{\cftbeforesubtabskip}  
137 \LWR@providelength{\cftsubtabindent}  
138 \LWR@providelength{\cftsubtabnumwidth}  
139 \newcommand*\cftsubtabfont}{  
140 \newcommand*\cftsubtabpresnum}{  
141 \newcommand*\cftsubtabaftersnum}{  
142 \newcommand*\cftsubtabaftersnumb}{  
143 \newcommand*\cftsubtableader}{  
144 \newcommand*\cftsubtabdotsep}{1}  
145 \newcommand*\cftsubtabpagefont}{  
146 \newcommand*\cftsubtabafterpnum}{  
  
147 \DeclareDocumentCommand{\cftsetindents}{m m m}{  
  
148 \providecommand{\cftpagenumbersoff}[1]{  
149 \providecommand{\cftpagenumberson}[1]{
```

`\newlistentry`

```

[<within>] {<counter>} {<ext>} {<level-1>}
150 \DeclareDocumentCommand{\newlistentry}{o m m m}
151 {%
152 \LWR@traceinfo{newlistentry #2 #3 #4}%
153 \IfValueTF{#1}%
154 {%
155   \ifundefined{c@#2}{%
156     \newcounter{#2}[#1]%
157     \expandafter\edef\csname the#2\endcsname{%
158       \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}%
159     }%
160   }{%
161 }%
162 {%
163   \ifundefined{c@#2}{%
164     \newcounter{#2}%
165   }{%
166 }%
167 \@namedef{l@#2}##1##2{%
168   \hypertocfloat{1}{#2}{#3}{##1}{##2}%
169   \def\cftwhatismyname{#2}% from memoir
170 }%
171 \expandafter\newlength\csname cftbefore#2skip\endcsname%
172 \expandafter\newlength\csname cft#2indent\endcsname%
173 \expandafter\newlength\csname cft#2numwidth\endcsname%
174 \@namedef{cft#2font}{}%
175 \@namedef{cft#2presnum}{}%
176 \@namedef{cft#2aftersnum}{}%
177 \@namedef{cft#2aftersnumb}{}%
178 \@namedef{cft#2leader}{}%
179 \@namedef{cft#2dotsep}{1}%
180 \@namedef{cft#2pagefont}{}%
181 \@namedef{cft#2afterpnum}{}%
182 \@namedef{toclevel@#2}{#4}%
183 \@namedef{cft#2filnum}##1{}%
184 \LWR@traceinfo{newlistentry done}%
185 }

```

`\newlistof`

[<within>] {<type>} {<ext>} {<listofname>}

Emulated through the `\newfloat` mechanism.

```

186 \DeclareDocumentCommand{\newlistof}{o m m m}
187 {%
188   \IfValueTF{#1}%
189     {\newlistentry[#1]{#2}{#3}{0}}%
190     {\newlistentry{#2}{#3}{0}}%
191   \@namedef{ext@#2}{#3}%
192   \ifundefined{c@#3depth}{\newcounter{#3depth}}{}%
193   \setcounter{#3depth}{1}%
194   \@namedef{cftmark#3}{}%
195   \@namedef{listof#2}{\LWR@listof{#2}{#4}}%
196   \@namedef{cftmake#3title}{}%
197   \expandafter\newlength\csname cftbefore#3titleskip\endcsname%
198   \expandafter\newlength\csname cftafter#3titleskip\endcsname%
199   \@namedef{cft#3titlefont}{}%
200   \@namedef{cftafter#3title}{}%
201   \@namedef{cft#3prehook}{}%
202   \@namedef{cft#3posthook}{}%

```

203 }

\cftchapterprecis

{*<text>*}

```

204 \newcommand{\cftchapterprecis}[1]{%
205   \cftchapterprecishere{#1}
206   \cftchapterprecistoc{#1}}
207 \newcommand{\cftchapterprecishere}[1]{%
208   \begin{quote}\textit{#1}\end{quote}}
209 \newcommand{\cftchapterprecistoc}[1]{
210   \addtocontents{toc}{%
211     {
212       \protect\begin{quote}#1\protect\end{quote}}
213   }
214 }
```

File 520 **lwarp-tocstyle.sty**

§ 629 Package **tocstyle**

Pkg tocstyle

tocstyle is ignored.

 **Not fully tested!** [Please send bug reports!](#)

for HTML output: 1 \LWR@ProvidesPackageDrop{tocstyle}[2017/02/23]

```

2 \newcommand*\usetocstyle[2][{}]{
3 \newcommand*\deactivatetocstyle[1][{}]{
4 \newcommand*\reactivatetocstyle[1][{}]{
5 \NewDocumentCommand{\settocfeature}{o o m m}{}
6 \NewDocumentCommand{\settocstylefeature}{o m m}{}
7 \NewDocumentCommand{\newtocstyle}{o o m m}{}
8 \newcommand*\aliastoc[2][{}]{
9 \newcommand*\showtoc[2][{}]{
10 \newcommand{\iftochasdepth}[4][{}]
```

File 521 **lwarp-todo.sty**

§ 630 Package **todo**

(Emulates or patches code by FEDERICO GARCIA.)

Pkg todo

todo is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{todo}[2010/03/31]

```

2 \renewcommand\todoitem[2]{%
3   \refstepcounter{todo}%
4   \item[%
5     \HTMLUnicode{2610} \quad
6     \ref{todopage:\thetodo}
7   ] : {\todoformat\ifx#1\todotocmark\else\textbf{#1} \fi}#2%
8   \label{todo:lbl:\thetodo}%
9 }
```

```

10
11 \renewcommand\doneitem[2]{%
12   \stepcounter{todo}%
13   \item[%
14     \HTMLUnicode{2611} \quad
15     \ref{todopage:\thetodo}
16   ] \@nameuse{@done\the\c@todo}:
17     {\todoformat\ifx#1\todotmark\else\textbf{#1} \fi}#2%
18 }

```

The following are not errors because the code will still compile and be usable if the patch is not possible.

```

19 \xpatchcmd{\@displaytodo}
20   {\todoformat #1}{\todoformat \textbf{#1}}{}
21   {\PackageWarning{lwarp-todo}{Unable to patch @displaytodo.}}
22
23 \xpatchcmd{\@displayfulltodo}
24   {\todoformat #1}{\todoformat \textbf{#1}}{}
25   {\PackageWarning{lwarp-todo}{Unable to patch @displayfulltodo.}}
26
27 \patchcmd{\todoenv}{\itshape see text.}{\textit{see text.}}{}
28   {\PackageWarning{lwarp-todo}{Unable to patch todoenv.}}
29
30 \patchcmd{\astodos}{\todoformat #1}{\todoformat \textbf{#1}}{}
31   {\PackageWarning{lwarp-todo}{Unable to patch astodos.}}

```

If `cleveref` is in use, name the new todo notes:

```

32 \AtBeginDocument{
33 \ifdef{\crefname}{
34   \crefname{todo}{todo}{todos}
35   \Crefname{todo}{Todo}{Todos}
36 }{}
37 }

```

File 522 **lwarp-todonotes.sty**

§ 631 Package **todonotes**

(Emulates or patches code by HENRIK SKOV MIDTIBY.)

Pkg todonotes

todonotes is emulated.

The documentation for `todonotes` and `luatodonotes` have an example with a `todo` inside a caption. If this example does not work it will be necessary to move the `todo` outside of the caption.

```

for HTML output: 1 \LWR@ProvidesPackagePass{todonotes}[2012/07/25]

2 \if@todonotes@disabled
3 \else
4
5 \newcommand{\ext@todo}{tdo}
6
7 \renewcommand{\l@todo}[2]{\hypertocfloat{1}{\todo}{ldo}{#1}{#2}}

```

```

8 \let\LWRTODONOTES@orig@todotoc\todotoc
9
10 \renewcommand*\todotoc{%
11 \LWR@phantomsection%
12 \LWRTODONOTES@orig@todotoc%
13 }
14
15 \renewcommand{\@todonotes@drawMarginNoteWithLine}{
16 \fcolorbox
17   {\@todonotes@currentbordercolor}
18   {\@todonotes@currentbackgroundcolor}
19   {\arabic{\@todonotes@numberoftodonotes}}
20 \marginpar{\@todonotes@drawMarginNote}
21 }
22
23 \renewcommand{\@todonotes@drawInlineNote}{%
24 \fcolorboxBlock%
25   {\@todonotes@currentbordercolor}%
26   {\@todonotes@currentbackgroundcolor}%
27   {%
28     \if@todonotes@authorgiven%
29     {\@todonotes@author:\,}%
30     \fi%
31     \@todonotes@text%
32   }%
33 }
34
35 \renewcommand{\@todonotes@drawMarginNote}{%
36   \if@todonotes@authorgiven%
37     \@todonotes@author\par%
38   \fi%
39   \arabic{\@todonotes@numberoftodonotes}: %
40   \fcolorbox%
41     {\@todonotes@currentbordercolor}%
42     {\@todonotes@currentbackgroundcolor}%
43     {%
44       \@todonotes@sizecommand%
45       \@todonotes@text %
46     }%
47 }%
48
49 \renewcommand{\@todonotes@drawLineToRightMargin}{}
50
51 \renewcommand{\@todonotes@drawLineToLeftMargin}{}
52
53 \renewcommand{\missingfigure}[2][{}]{%
54 \setkeys{todonotes}{#1}%
55 \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
56 \fcolorboxBlock%
57   {\@todonotes@currentbordercolor}%
58   {\@todonotes@currentfigcolor}%
59   {%
60     \setlength{\fboxrule}{4pt}%
61     \fcolorbox{red}{white}{Missing figure} \quad #2%
62   }
63 }
64
65 \LetLtxMacro\LWRTODONOTES@orig@todo\@todo
66
67 \RenewDocumentCommand{\@todo}{o m}{%

```

```

68 \begingroup%
69 \renewcommand*{\phantomsection}{}%
70 \IfValueTF{#1}{%
71   \LWRTODONOTES@orig@todo[#1]{#2}%
72 }{%
73   \LWRTODONOTES@orig@todo{#2}%
74 }
75 \endgroup%
76 }
77
78 \fi% \if@todonotes@disabled

```

File 523 **lwarp-topcapt.sty**

§ 632 Package **topcapt**

Pkg topcapt

topcapt is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{topcapt}[2004/12/11]

2 \LetLtxMacro\topcaption\caption

```

File 524 **lwarp-tram.sty**

§ 633 Package **tram**

Pkg tram

tram is emulated.

 **block only** The HTML emulation uses a <div>, which must not appear inside an HTML or an HTML paragraph. For this reason, the tram environment should only be used to contain paragraphs inside a \parbox or minipage. tram should not be used to mark up inline text.

To disable tram, allowing source compatibility with inline uses:

```

\begin{warpHTML}
\renewenvironment{tram}[1][[]]{}{}
\end{warpHTML}

```

for HTML output:

```

1 \LWR@ProvidesPackageDrop{tram}[2013/04/04]

```

```

2 \newenvironment{tram}[1][[]%
3   {\BlockClass[background:lightgray]{tram}}
4   {\endBlockClass}

```

File 525 **lwarp-transparent.sty**

§ 634 Package **transparent**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg transparent

transparent is emulated. `\texttransparent` works for inline objects. `\transparent` only works for `\includegraphics`.

 **Not X_gL^AT_EX!** Note that transparent does not work with X_gL^AT_EX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{transparent}[2019/11/29]
2 \newcommand*\LWR@HTML@transparent[1]{\edef\LWR@opacity{#1}}
3
4 \LWR@formatted{transparent}
5
6
7 \newcommand*\LWR@HTML@texttransparent[2]{%
8 \begingroup%
9 \transparent{#1}%
10 \InlineClass[opacity: #1]{transparent}{#2}%
11 \endgroup%
12 }
13
14 \LWR@formatted{texttransparent}

```

File 526 **lwarp-trimclip.sty**

§ 635 Package **trimclip**

Pkg trimclip

trimclip is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{trimclip}[2018/04/08]

```

The third argument, the text, is not touched. This allows `\bgroup / \egroup`, and verbatim content.

```

2 \csdef{trimbox}{\@ifstar\@gobble\@gobble}
3 \csletcs{trimbox*}{trimbox}
4 \def\endtrimbox{}
5 \csletcs{endtrimbox*}{endtrimbox}
6
7 \csletcs{clipbox}{trimbox}
8 \csletcs{clipbox*}{trimbox}
9 \csletcs{endclipbox}{endtrimbox}
10 \csletcs{endclipbox*}{endtrimbox}
11
12 \csletcs{marginbox}{trimbox}
13 \csletcs{marginbox*}{trimbox}
14 \csletcs{endmarginbox}{endtrimbox}
15 \csletcs{endmarginbox*}{endtrimbox}

```

File 527 **lwarp-trivfloat.sty**

§ 636 Package **trivfloat**

(Emulates or patches code by JOSEPH WRIGHT.)

Pkg trivfloat

trivfloat is forced to use the built-in lwarp emulation for floats.

To create a new float type and change its name:

```
\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}
```

Discard all options for `lwarp-trivfloat`. This tells `trivfloat` not to use `floatrow` or `memoir`.

```
1 \LWR@ProvidesPackageDrop{trivfloat}[2009/04/23]
2 \LWR@origRequirePackage{trivfloat}
```

`\tfl@chapter@fix`

Nullified at the beginning of the document. Is used by `trivfloat` to correct float chapter numbers, but is not needed for `lwarp`.

```
3 \AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{{}}
```

§ 636.1 **Combining `\newfloat`, `\trivfloat`, and `algorithmicx`**

For both print and HTML output:



When using `float`, `trivfloat`, or `algorithmicx` at the same time, be aware of conflicting file usage. `algorithmicx` uses `.loa`. `trivfloat` by default starts with `.loa` and goes up for additional floats, skipping `.lof` and `.lot`.



When using `\newfloat`, be sure to manually assign higher letters to the `\newfloat` files to avoid `.loa` used by `algorithmicx`, and any files used by `trivfloat`. Also avoid using `.lof` and `.lot`.



When using `\trivfloat`, you may force it to avoid conflicting with `algorithmicx` by starting `trivfloat`'s file extensions with `.lob`:

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
```

File 528 **`lwarp-truncate.sty`**

§ 637 Package **`truncate`**

Pkg `truncate`

`truncate` is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{truncate}[2001/08/20]

2 \providecommand{\TruncateMarker}{}
3 \newcommand{\truncate}[3][\TruncateMarker]{#3}
```

File 529 **lwarp-turnthepage.sty**

§ 638 Package **turnthepage**

Pkg turnthepage turnthepage is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{turnthepage}[2011/03/24]

2 \newcommand{\turnthepage}{}

File 530 **lwarp-twoup.sty**

§ 639 Package **twoup**

Pkg twoup twoup is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{twoup}[2007/02/26]

2 \newcommand{\cleartolastpage}{}

File 531 **lwarp-txfonts.sty**

§ 640 Package **txfonts**

(Emulates or patches code by YOUNG RYU.)

Pkg txfonts txfonts is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{txfonts}[2008/01/22]

For MATHJAX:

```
2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{txfonts}
6
7 \LWR@mathjax@addgreek@l@up[]{}{up}
8 \end{warpMathJax}
```

File 532 **lwarp-txgreeks.sty**

§ 641 Package **txgreeks**

(Emulates or patches code by JEAN-FRANÇOIS BURNOL.)

Pkg txgreek

txgreek is used as-is for SVG math, and is emulated for MATHJAX.

The MATHJAX emulation honors all package options.

for HTML output:

```

1 \LWR@ProvidesPackagePass{txgreek}[2011/03/16]
2
3 \LWR@infoprocessingmathjax{txgreek}

4 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
5
6 \begin{warpMathJax}
7 \iftgs@uplower% upright lowercase Greek
8   \LWR@mathjax@addgreek@l@up{}{}
9   \LWR@mathjax@addgreek@l@it{other}{}
10 \else% italic lowercase Greek
11   \LWR@mathjax@addgreek@l@it{}{}
12   \LWR@mathjax@addgreek@l@up{other}{}
13 \fi
14
15 \iftgs@itupper % italic uppercase Greek
16   \LWR@mathjax@addgreek@u@it*{}{}
17   \LWR@mathjax@addgreek@u@up*{other}{}
18   \LWR@mathjax@addgreek@u@up*{var}{}
19 \else% upright uppercase Greek
20   \LWR@mathjax@addgreek@u@up*{}{}
21   \LWR@mathjax@addgreek@u@it*{other}{}
22   \LWR@mathjax@addgreek@u@it*{var}{}
23 \fi
24 \end{warpMathJax}

```

File 533 **lwarp-typearea.sty**

§ 642 Package **typearea**

(Emulates or patches code by MARKUS KOHM.)

Pkg typearea

typearea is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. `\DeclareDocumentCommand` is used to overwrite the koma-script definitions.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{typearea}[2018/03/30]

2 \DeclareDocumentCommand{\typearea}{o m}{}
3 \DeclareDocumentCommand{\recalctypearea}{}{}
4 \ifundefined{footheight}{\newlength{footheight}}{}
5 \DeclareDocumentCommand{\areaset}{o m m}{}
6 \DeclareDocumentCommand{\activateareas}{}{}
7 \DeclareDocumentCommand{\storeareas}{m}{}
8 \DeclareDocumentCommand{\BeforeRestoreareas}{s m}{}
9 \DeclareDocumentCommand{\AfterRestoreareas}{s m}{}
10 \DeclareDocumentCommand{\AfterCalculatingTypearea}{s m}{}
11 \DeclareDocumentCommand{\AfterSettingArea}{s m}{}

```

File 534 **lwarp-typicons.sty**

§ 643 Package **typicons**

(Emulates or patches code by ARTHUR VIGIL, XAVIER DANAUX.)

Pkg typicons

typicons is patched for use by lwarp.

If `\ticon` is used, the name of the icon is used in the `alt` tag. Otherwise, for each of the individual icon macros, a generic `alt` tag is used.

for HTML output:

```

1 \LWR@ProvidesPackagePass{typicons}[2015/05/20]

2 \LetLtxMacro\LWR@orig@symbol\symbol
3
4 \let\LWR@orig@typicon@TI\TI
5
6 \newcommand*{\LWR@typicon@symbol}[1]{%
7   \begin{lateximage}*[typicon][typicon#1]%
8   \begingroup%
9   \LWR@orig@typicon@TI%
10  \LWR@orig@symbol{#1}%
11  \endgroup%
12  \end{lateximage}%
13 }
14
15 \renewcommand*{\TI}{%
16   \LetLtxMacro\symbol\LWR@typicon@symbol%
17 }
18
19 \renewcommand*{\ticon}[1]
20 {%
21   \begin{lateximage}*[#1 icon][typicon#1]%
22   \TI\csname ticon#1\endcsname%
23   \end{lateximage}%
24 }
```

File 535 **lwarp-ulem.sty**

§ 644 Package **ulem**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg ulem

Patched for use by lwarp.

for HTML output: Use the original package:

```

1 \LWR@ProvidesPackagePass{ulem}[2012/05/18]
```

Basic markup commands, using CSS:

```

2 \NewDocumentCommand{\LWR@HTML@uline}{+m}{%
3   \InlineClass%
```

```
4      (text-decoration:underline; text-decoration-skip: auto)%
5      {uline}{\LWR@isolate{#1}}%
6  }
7  \LWR@formatted{uline}
8
9  \NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
10   \InlineClass%
11   (%
12     text-decoration:underline; text-decoration-skip: auto;%
13     text-decoration-style:doubled%
14   )%
15   {uuline}{\LWR@isolate{#1}}%
16 }
17 \LWR@formatted{uuline}
18
19 \NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
20   \InlineClass%
21   (%
22     text-decoration:underline; text-decoration-skip: auto;%
23     text-decoration-style:wavy%
24   )%
25   {uwave}{\LWR@isolate{#1}}%
26 }
27 \LWR@formatted{uwave}
28
29 \NewDocumentCommand{\LWR@HTML@sout}{+m}{%
30   \InlineClass%
31   (text-decoration:line-through)%
32   {sout}{\LWR@isolate{#1}}%
33 }
34 \LWR@formatted{sout}
35
36 \NewDocumentCommand{\LWR@HTML@xout}{+m}{%
37   \InlineClass%
38   (text-decoration:line-through)%
39   {xout}{\LWR@isolate{#1}}%
40 }
41 \LWR@formatted{xout}
42
43 \NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
44   \InlineClass%
45   (%
46     text-decoration:underline;%
47     text-decoration-skip: auto;%
48     text-decoration-style:dashed%
49   )%
50   {dashuline}{\LWR@isolate{#1}}%
51 }
52 \LWR@formatted{dashuline}
53
54 \NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
55   \InlineClass%
56   (%
57     text-decoration:underline;%
58     text-decoration-skip: auto;%
59     text-decoration-style: dotted%
60   )%
61   {dotuline}{\LWR@isolate{#1}}%
62 }
63 \LWR@formatted{dotuline}
```

Nullified/emulated macros:

```
64 \NewDocumentCommand{\LWR@HTML@markoverwith}{m}{}
65 \LWR@formatted{markoverwith}
66
67 \NewDocumentCommand{\LWR@HTML@ULon}{+m}{\uline{#1}\egroup}
68 \LWR@formatted{ULon}
```

File 536 **lwarp-umoline.sty**

§ 645 Package **umoline**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg umoline

umoline is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{umoline}[2000/07/11]
2 \newcommand*\LWR@HTML@Underline[1]{%
3   \InlineClass{uline}{#1}%
4 }
5 \LWR@formatted{Underline}
6
7 \newcommand*\LWR@HTML@Midline[1]{%
8   \InlineClass{sout}{#1}%
9 }
10 \LWR@formatted{Midline}
11
12 \newcommand*\LWR@HTML@Overline[1]{%
13   \InlineClass{oline}{#1}%
14 }
15 \LWR@formatted{Overline}
16
17 \newcommand*\LWR@HTML@UMoline[2]{%
18   \InlineClass{uline}{#2}%
19 }
20 \LWR@formatted{UMoline}
21
22 \NewDocumentCommand{\LWR@HTML@UMospace}{s m o}{\hspace*{#2}}
23 \LWR@formatted{UMospace}
24
25 \NewDocumentCommand{\LWR@HTML@UMOnewline}{s}{\newline}
26 \LWR@formatted{UMOnewline}
```

File 537 **lwarp-underscore.sty**

§ 646 Package **underscore**

Pkg underscore

underscore is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{underscore}[2006/09/13]
```

File 538 **lwarp-unicode-math.sty**

§ 647 Package **unicode-math**

(Emulates or patches code by WILL ROBERTSON.)

Pkg unicode-math

unicode-math is supported as-is for HTML with SVGmath.

 **MATHJAX** If the document source includes embedded Unicode characters, these may not be reproduced correctly for *pdftotext*, and thus not display correctly in MATHJAX.

Symbol font commands are emulated, but not all combinations are supported by MATHJAX, especially with the dedicated Greek macros. Symbol macros such as `\symbfsf` may not be sans or bold. For Greek, use the Unicode equivalent, if necessary.

 **\mathversion** The MATHJAX emulation does not change with the use of `\mathversion`. Whatever emulation is established at the begin of the document will remain.

The option `sans-style` honors `upright` and `italic`, but `italic` will not be sans, in order to support Greek macros.

Greek macros such as `\alpha` respond to the `math-style` option. Latin symbols does not, per MATHJAX limitations, unless placed inside `\symbit` or similar.

Macros from the categories `\mathopen`, `\mathclose`, and `\mathfence` are emulated. Due to current MATHJAX limitations, not all stretch to the correct height.

Also emulated are macros from the categories `\mathpunct`, `\mathover`, `\mathunder`, `\mathaccent`, `\mathbotaccent`, and `\mathop`.

The individual `unicode-math` macros of categories `\mathbin`, `\mathord`, and `\mathrel` are not emulated for MATHJAX, as there are more than two thousand of them, but they may be added as needed. Place the following in the document preamble after loading `unicode-math`, including a definition for each macro which is used in the document but undefined in MATHJAX:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\uplus}{\mathbin{\unicode{x0228E}}}}
...
\end{warpMathJax}
```

Use `\mathrel`, `\mathbin`, etc. depending on the category of each macro. For a list of macro names and symbols, see **texdoc unimath-symbols**.

for HTML output:

```
1 \LWR@ProvidesPackagePass{unicode-math}[2019/09/26]
2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{unicode-math}
6
7 % Not all are possible in MathJax.
8 \CustomizeMathJax{\let\symnormal\mathit}
```

```

 9 \CustomizeMathJax{\let\symliteral\mathrm}
10 \CustomizeMathJax{\let\symlb\mathbb}
11 \CustomizeMathJax{\let\symlbbit\mathbb}% not italic
12 \CustomizeMathJax{\let\symcal\mathcal}
13 \CustomizeMathJax{\let\symscr\mathscr}
14 \CustomizeMathJax{\let\symfrac\mathfrak}
15
16 \CustomizeMathJax{\let\symsfup\mathsf}
17
18 \CustomizeMathJax{\let\symsfit\mathit}% not sans
19 % \CustomizeMathJax{\newcommand{\symsfit}[1]{%
20 %     \mmlToken{mi}[mathvariant="sans-serif-italic"]{#1}}% not greek
21 % }
22
23 \CustomizeMathJax{\let\symsfsf\mathbf}% not sans
24 % \CustomizeMathJax{\newcommand{\symsfsf}[1]{%
25 %     \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}}% not greek
26 % }
27
28 \CustomizeMathJax{\let\symsfbfup\mathbf}
29 \CustomizeMathJax{\newcommand{\symsfbfit}[1]{\boldsymbol{#1}}}
30 \CustomizeMathJax{\let\symsfbcal\mathcal}% not bold
31
32 \CustomizeMathJax{\let\symsfbfscr\mathscr}% not bold
33 % \CustomizeMathJax{\newcommand{\symsfbfscr}[1]{
34 %     \mmlToken{mi}[mathvariant="math-bold-script"]{#1}}% not greek
35 % }
36
37 \CustomizeMathJax{\let\symsfbfrac\mathfrak}% not bold
38 % \CustomizeMathJax{\newcommand{\symsfbfrac}[1]{%
39 %     \mmlToken{mi}[mathvariant="math-bold-fraktur"]{#1}}% not greek
40 % }
41
42 \CustomizeMathJax{\let\symsbfsfup\mathbf}% not sans
43 % \CustomizeMathJax{\newcommand{\symsbfsfup}[1]{%
44 %     \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}}% not greek
45 % }
46
47 \CustomizeMathJax{\newcommand{\symsbfsfit}[1]{\boldsymbol{#1}}}% not sans
48 % \CustomizeMathJax{\newcommand{\symsbfsfit}[1]{%
49 %     \mmlToken{mi}[mathvariant="sans-serif-bold-italic"]{#1}}% not greek
50 % }
51
52 % Duplicates below are commented out.
53 \CustomizeMathJax{\let\symup\mathrm}
54 \CustomizeMathJax{\let\symlb\mathbf}% \symlb defined above
55 \CustomizeMathJax{\let\symlit\mathit}
56 % \CustomizeMathJax{\let\symlbfit\mathit}% not bold

57 \ExplSyntaxOn
58 \AtBeginDocument{
59 \bool_if:NTF \g__um_sfliteral_bool
60   {\CustomizeMathJax{\let\symsf\symsfup}}
61   {
62     \bool_if:NTF \g__um_upsans_bool
63       {\CustomizeMathJax{\let\symsf\symsfup}}
64       {\CustomizeMathJax{\let\symsf\symsfit}}
65   }
66 }
67 \ExplSyntaxOff

```

```

68% \CustomizeMathJax{\let\symbfsfup\mathbf}% not sans
69% \CustomizeMathJax{\let\symsfit\mathit}% not sans
70% \CustomizeMathJax{\let\symbfsfit\mathit}% not bold nor sans
71 \CustomizeMathJax{\let\symtt\mathtt}
72% \CustomizeMathJax{\let\sybbb\mathbb}
73% \CustomizeMathJax{\let\sybbit\mathbb}% not italic
74% \CustomizeMathJax{\let\symscr\mathscr}
75% \CustomizeMathJax{\let\sybfscr\mathscr}% not bold
76% \CustomizeMathJax{\let\symfrac\mathfrak}
77 \CustomizeMathJax{\let\sybfrac\mathbfrac}

```

Some symbol categories defined by unicode-math, in case they are used inside custom macros:

```

78 \CustomizeMathJax{\newcommand{\mathfence}[1]{\mathord{#1}}}
79 \CustomizeMathJax{\newcommand{\mathover}[1]{#1}}
80 \CustomizeMathJax{\newcommand{\mathunder}[1]{#1}}
81 \CustomizeMathJax{\newcommand{\mathaccent}[1]{#1}}
82 \CustomizeMathJax{\newcommand{\mathbotaccent}[1]{#1}}
83 \CustomizeMathJax{\newcommand{\mathalpha}[1]{\mathord{#1}}}

```

math-style is one of: ISO, TeX, french, upright, or literal, which set `\g__um_upGreek_bool` and `\g__um_upgreek_bool`.

```

84 \ExplSyntaxOn
85
86 \AtBeginDocument{
87 \bool_if:NTF \g__um_upGreek_bool
88   {\LWR@mathjax@addgreek@u@up*{}}{}
89   {\LWR@mathjax@addgreek@u@it*{}}{}
90
91 \bool_if:NTF \g__um_upgreek_bool
92   {\LWR@mathjax@addgreek@l@up{}}{}
93   {\LWR@mathjax@addgreek@l@it{}}{}
94 }
95
96 \LWR@mathjax@addgreek@u@up*{up}{}
97 \LWR@mathjax@addgreek@u@it*{it}{}
98 \LWR@mathjax@addgreek@l@up{up}{}
99 \LWR@mathjax@addgreek@l@it{it}{}
100
101 \ExplSyntaxOff
102
103 \CustomizeMathJax{\let\lparen()}
104 \CustomizeMathJax{\let\rparen)}
105 \CustomizeMathJax{\newcommand{\cuberoot}[1]{\,\,{}^3\!\!\sqrt{#1}}\,}
106 \CustomizeMathJax{\newcommand{\fourthroot}[1]{\,\,{}^4\!\!\sqrt{#1}}\,}

```

Many `\mathopen/\mathclose` delimiters are defined in `lwarp_mathjax.txt`, where `\left/\right` support is added.

```

107 \CustomizeMathJax{\newcommand{\longdivision}[1]{\mathord{\unicode{x027CC}#1}}}
108
109 \CustomizeMathJax{\newcommand{\mathcomma}{,}}
110 \CustomizeMathJax{\newcommand{\mathcolon}{:}}
111 \CustomizeMathJax{\newcommand{\mathsemicolon}{;}}
112
113 \CustomizeMathJax{\newcommand{\overbracket}[1]{\mathinner{\overline{\ulcorner#1\urcorner}}}}
114 \CustomizeMathJax{\newcommand{\underbracket}[1]{\mathinner{\underline{\llcorner#1\lrcorner}}}}

```

```

115
116 \CustomizeMathJax{\newcommand{\overbar}[1]{\mathord{#1\unicode{x00305}}}}
117 \CustomizeMathJax{\newcommand{\ovhook}[1]{\mathord{#1\unicode{x00309}}}}
118 \CustomizeMathJax{\newcommand{\ocirc}[1]{\mathord{#1\unicode{x0030A}}}}
119 \CustomizeMathJax{\newcommand{\candra}[1]{\mathord{#1\unicode{x00310}}}}
120 \CustomizeMathJax{\newcommand{\oturnedcomma}[1]{\mathord{#1\unicode{x00312}}}}
121 \CustomizeMathJax{\newcommand{\ocommatopright}[1]{\mathord{#1\unicode{x00315}}}}
122 \CustomizeMathJax{\newcommand{\droang}[1]{\mathord{#1\unicode{x0031A}}}}
123 \CustomizeMathJax{\newcommand{\leftharpoonaccent}[1]{\mathord{#1\unicode{x020D0}}}}
124 \CustomizeMathJax{\newcommand{\rightharpoonaccent}[1]{\mathord{#1\unicode{x020D1}}}}
125 \CustomizeMathJax{\newcommand{\vertoverlay}[1]{\mathord{#1\unicode{x020D2}}}}
126 \CustomizeMathJax{\newcommand{\leftarrowaccent}[1]{\mathord{#1\unicode{x020D0}}}}
127 \CustomizeMathJax{\newcommand{\annuity}[1]{\mathord{#1\unicode{x020E7}}}}
128 \CustomizeMathJax{\newcommand{\widebridgeabove}[1]{\mathord{#1\unicode{x020E9}}}}
129 \CustomizeMathJax{\newcommand{\asteraccent}[1]{\mathord{#1\unicode{x020F0}}}}
130 \CustomizeMathJax{\newcommand{\threeunderdot}[1]{\mathord{#1\unicode{x020E8}}}}
131
132 \CustomizeMathJax{\newcommand{\Bbbsum}{\mathop{\unicode{x2140}}\limits}}
133 \CustomizeMathJax{\newcommand{\vooint}{\mathop{\unicode{x222F}}\limits}}
134 \CustomizeMathJax{\newcommand{\voiiint}{\mathop{\unicode{x2230}}\limits}}
135 \CustomizeMathJax{\newcommand{\ointclockwise}{\mathop{\unicode{x2231}}\limits}}
136 \CustomizeMathJax{\newcommand{\ointclockwise}{\mathop{\unicode{x2232}}\limits}}
137 \CustomizeMathJax{\newcommand{\ointctrlockwise}{\mathop{\unicode{x2233}}\limits}}
138 \CustomizeMathJax{\newcommand{\varointclockwise}{\mathop{\unicode{x2232}}\limits}}
139 \CustomizeMathJax{\newcommand{\leftouterjoin}{\mathop{\unicode{x27D5}}\limits}}
140 \CustomizeMathJax{\newcommand{\rightouterjoin}{\mathop{\unicode{x27D6}}\limits}}
141 \CustomizeMathJax{\newcommand{\fullouterjoin}{\mathop{\unicode{x27D7}}\limits}}
142 \CustomizeMathJax{\newcommand{\bigbot}{\mathop{\unicode{x27D8}}\limits}}
143 \CustomizeMathJax{\newcommand{\bigtop}{\mathop{\unicode{x27D9}}\limits}}
144 \CustomizeMathJax{\newcommand{\xsol}{\mathop{\unicode{x29F8}}\limits}}
145 \CustomizeMathJax{\newcommand{\xbsol}{\mathop{\unicode{x29F9}}\limits}}
146 \CustomizeMathJax{\newcommand{\bigcupdot}{\mathop{\unicode{x2A03}}\limits}}
147 \CustomizeMathJax{\newcommand{\bigsqcap}{\mathop{\unicode{x2A05}}\limits}}
148 \CustomizeMathJax{\newcommand{\conjqunt}{\mathop{\unicode{x2A07}}\limits}}
149 \CustomizeMathJax{\newcommand{\disjqunt}{\mathop{\unicode{x2A08}}\limits}}
150 \CustomizeMathJax{\newcommand{\bigtimes}{\mathop{\unicode{x2A09}}\limits}}
151 \CustomizeMathJax{\newcommand{\modtwosum}{\mathop{\unicode{x2A0A}}\limits}}
152 \CustomizeMathJax{\newcommand{\sumint}{\mathop{\unicode{x2A0B}}\limits}}
153 \CustomizeMathJax{\newcommand{\intbar}{\mathop{\unicode{x2A0D}}\limits}}
154 \CustomizeMathJax{\newcommand{\intBar}{\mathop{\unicode{x2A0E}}\limits}}
155 \CustomizeMathJax{\newcommand{\fint}{\mathop{\unicode{x2A0F}}\limits}}
156 \CustomizeMathJax{\newcommand{\cirfnint}{\mathop{\unicode{x2A10}}\limits}}
157 \CustomizeMathJax{\newcommand{\awint}{\mathop{\unicode{x2A11}}\limits}}
158 \CustomizeMathJax{\newcommand{\rrpolint}{\mathop{\unicode{x2A12}}\limits}}
159 \CustomizeMathJax{\newcommand{\scpolint}{\mathop{\unicode{x2A13}}\limits}}
160 \CustomizeMathJax{\newcommand{\npolint}{\mathop{\unicode{x2A14}}\limits}}
161 \CustomizeMathJax{\newcommand{\pointint}{\mathop{\unicode{x2A15}}\limits}}
162 \CustomizeMathJax{\newcommand{\sqint}{\mathop{\unicode{x2A16}}\limits}}
163 \CustomizeMathJax{\newcommand{\intLarhk}{\mathop{\unicode{x2A17}}\limits}}
164 \CustomizeMathJax{\newcommand{\intx}{\mathop{\unicode{x2A18}}\limits}}
165 \CustomizeMathJax{\newcommand{\intcap}{\mathop{\unicode{x2A19}}\limits}}
166 \CustomizeMathJax{\newcommand{\intcup}{\mathop{\unicode{x2A1A}}\limits}}
167 \CustomizeMathJax{\newcommand{\upint}{\mathop{\unicode{x2A1B}}\limits}}
168 \CustomizeMathJax{\newcommand{\lowint}{\mathop{\unicode{x2A1C}}\limits}}
169 \CustomizeMathJax{\newcommand{\bigtriangleleft}{\mathop{\unicode{x2A1E}}\limits}}
170 \CustomizeMathJax{\newcommand{\zcmp}{\mathop{\unicode{x2A1F}}\limits}}
171 \CustomizeMathJax{\newcommand{\zpipe}{\mathop{\unicode{x2A20}}\limits}}
172 \CustomizeMathJax{\newcommand{\zproject}{\mathop{\unicode{x2A21}}\limits}}
173 \CustomizeMathJax{\newcommand{\biginterleave}{\mathop{\unicode{x2AFC}}\limits}}
174 \CustomizeMathJax{\newcommand{\bigtalloblong}{\mathop{\unicode{x2AFF}}\limits}}

```

```

175 \CustomizeMathJax{\newcommand{\arabicmaj}{\mathop{\unicode{x1EEF0}}\limits}}
176 \CustomizeMathJax{\newcommand{\arabichad}{\mathop{\unicode{x1EEF1}}\limits}}
177
178 \end{warpMathJax}

```

File 539 **lwarp-units.sty**

§ 648 Package **units**

(Emulates or patches code by AXEL REICHERT.)

units is patched for use by lwarp.

Values are not styled by css, and take the style of the surrounding HTML text.

Units are styled according to the print version, so they will be forced to upright roman in HTML if the print version does so. It may be necessary to adjust the document's body css to match the print version.

for HTML output:

```

1 \LWR@ProvidesPackagePass{units}[1998/08/04]

2 \DeclareRobustCommand*\LWR@HTML@unit}[2][[]]{%
3 \ifblank{#1}%
4   {\LWR@textcurrentfont{#2}}%
5   {%
6     #1%
7     \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,%
8     \LWR@textcurrentfont{#2}}%
9   }%
10 }
11 \LWR@formatted{unit}

12 \DeclareRobustCommand*\LWR@HTML@unitfrac}[3][[]]{%
13 \ifblank{#1}%
14   {%
15     \nicefrac{#2}{#3}%
16   }%
17   {%
18     #1%
19     \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,%
20     \nicefrac{#2}{#3}}%
21   }%
22 }
23
24 \LWR@formatted{unitfrac}

```

For MATHJAX:

```

25 \begin{warpMathJax}
26 \CustomizeMathJax{\newcommand{\unit}[2][[]]{#1 \mathinner{#2}}}
27 \CustomizeMathJax{\newcommand{\unitfrac}[3][[]]{#1 \mathinner{{}^{\#2}\!/_{\#3}}}}
28 \end{warpMathJax}

```

File 540 **lwarp-unitsdef.sty**

§ 649 Package **unitsdef**

(Emulates or patches code by PATRICK HAPPEL.)

Pkg unitsdef

unitsdef is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{unitsdef}[2005/01/04]
2 \renewcommand{\unitvaluesep}{\,}
3
4 \renewcommand{\unittimes}{\@@setunitsepfalse\HTMLUnicode{22c5}}% \cdot
5
6 \renewunit{\arcmin}{%
7   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
8     {\ensuremath{{}^{\prime}}}%
9     {\HTMLUnicode{2032}}% prime
10 }
11
12 \renewunit{\arcsec}{%
13   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
14     {\ensuremath{{}^{\prime\prime}}}%
15     {\HTMLUnicode{2033}}% dbl prime
16 }
17
18 \renewrobustcmd{\SI}[2]{%
19   \begingroup%
20     \let\unit@xspace\relax%
21     \unitSIdf\selectfont%
22     \LWR@textcurrentfont{#1#2}% lwarp
23   \endgroup%
24 }
```

File 541 **lwarp-upgreek.sty**

§ 650 Package **upgreek**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg upgreek

upgreek is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{upgreek}[2003/02/12]
```

For MATHJAX:

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\require{upgreek}}
4 \end{warpMathJax}
```

File 542 **lwarp-upref.sty**§ 651 Package **upref**

Pkg upref

upref is ignored.

for HTML output: Discard all options for lwarp-upref:

```
1 \LWR@ProvidesPackageDrop{upref}[2007/03/14]
```

File 543 **lwarp-url.sty**§ 652 Package **url**

Pkg url

(Emulates or patches code by DONALD ARSENEAU.)

url is patched for use by lwarp.

for HTML output:

```
1 \LetLtxMacro\LWR@url@orig@url\LWR@url
2
3 \LWR@ProvidesPackagePass{url}[2013/09/16]

4 \newcommand*\LWR@HTML@Url@FormatString{%
5   \expandafter\LWR@url@orig@url\expandafter\@Url@String}%
6 }
7 \LWR@formatted{Url@FormatString}
```

File 544 **lwarp-ushort.sty**§ 653 Package **ushort**

Pkg ushort

(Emulates or patches code by MARTIN VÄTH.)

ushort is used as-is, and emulated for MATHJAX.

for HTML output:

```
1 \LWR@ProvidesPackagePass{ushort}[2001/06/13]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\ushortdline}[1]{%
4   \kern{.1em}\underline{\underline{#1}}\kern{.1em}%
5 }}
6 \CustomizeMathJax{\newcommand{\ushort}[1]{\kern{.1em}\underline{#1}\kern{.1em}}}
7 \CustomizeMathJax{\newcommand{\ushortd}[1]{\ushortdline{#1}}}
8 \CustomizeMathJax{\newcommand{\ushortw}[1]{\kern{.1em}\underline{#1}\kern{.1em}}}
9 \CustomizeMathJax{\newcommand{\ushortdw}[1]{\ushortdline{#1}}}
10 \end{warpMathJax}
```

File 545 **lwarp-ospace.sty**§ 654 Package **ospace**

Pkg ospace

ospace is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{ospace}[2016/11/06]File 546 **lwarp-varioref.sty**§ 655 Package **varioref**

Pkg varioref

(Emulates or patches code by FRANK MITTELBACH.)

varioref is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{varioref}[2020/01/23]

Page-related output is not used for HTML output.

```

2 \def\reftextfaceafter {\unskip}%
3 \def\reftextfacebefore{\unskip}%
4 \def\reftextafter     {\unskip}%
5 \def\reftextbefore   {\unskip}%
6 \def\reftextcurrent  {\unskip}%
7 \def\reftextfaraway#1{\unskip}%
8 \def\reftextpagerange#1#2{\unskip}%

```

File 547 **lwarp-verse.sty**§ 656 Package **verse**

Pkg verse

(Emulates or patches code by PETER WILSON.)

verse is supported and patched by lwarp.

for HTML output: Pass all options for lwarp-verse:

1 \LWR@ProvidesPackagePass{verse}[2009/09/04]

When using verse or memoir, always place a \\ after each line.

\attrib

The documentation for the `verse` and `memoir` packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. `lwarp` provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```

\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}

```

Len `\vleftskip` These lengths are used by `verse` and `memoir` to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

⚠ **spacing** Horizontal spacing relies on *pdftotext*’s ability to discern the layout (`-layout` option) of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space. During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused *pdftotext* to shift everything over.

⚠ **verse margin** During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused *pdftotext* to shift everything over.

Env `verse` The `verse` environment will be placed inside a HTML `<pre>`.

```
2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching verse.}
```

At the beginning of the `verse` environment:

```
4 \AtBeginEnvironment{verse}
5 {%
```

Use the original `list` environment inside a `<pre>` to attempt to preserve formatting.

```
6 \LWR@restoreoriglists%
```

Pkg `verse` The `verse` or `memoir` packages can place stanza numbers to the left with their `\flagverse` command. The following does not allow them to go into the left margin, which would cause *pdfcrop* to crop the entire page further to the left.

```
Len \vleftskip
7 \ifdef{\vleftskip}{%
8 \setlength{\vleftskip}{\HTMLvleftskip}
9 \setlength{\leftmargini}{\HTMLleftmargini}
10 }{}
11 \LWR@forcenewpage
12 \LWR@atbeginverbatim{verse}%
13 }
```

After the end of the `verse` environment, which places the `<pre>` tag at the regular left margin:

```
14 \AtEndEnvironment{verse}{%
15 \leavevmode%
16 \LWR@afterendverbatim%
17 }
```

Patch to place `poemtitle` inside an HTML `` of class `poemtitle`:

```
18 \ifdef{\poemtitle}{
19 \DeclareDocumentCommand{\vstypeptitle}{m}{%
20 \space{\beforepoemtitleskip}%
```

```

21  {\InlineClass{poemtitle}{\poemtitlefont #1}\par}%
22  \vspace{\afterpoemtitleskip}%
23  }
24  }{}
25
26  \LWR@traceinfo{Finished patching verse.}
27  }% AfterEndPreamble

```

File 548 **lwarp-versonotes.sty**

§ 657 Package **versonotes**

(Emulates or patches code by NORMAN GRAY.)

Pkg versonotes **versonotes** is emulated.

for HTML output:

```

1  \LWR@ProvidesPackageDrop{versonotes}[2019/07/06]

2  \newcommand{\versonote}[1]{\marginpar{#1}}
3  \newdimen\versotextwidth
4  \newdimen\versoleftmargin
5  \newcommand*{\versolayout}{}

```

In case the user changed the page number before loading versonotes:

```

6  \setcounter{page}{1}

```

File 549 **lwarp-vertbars.sty**

§ 658 Package **vertbars**

(Emulates or patches code by PETER WILSON.)

Pkg vertbars **vertbars** is emulated.

for HTML output:

```

1  \LWR@ProvidesPackageDrop{vertbars}[2010/11/27]

2  \newlength{\barwidth}
3  \setlength{\barwidth}{0.4pt}
4  \newlength{\barspace}
5  \setlength{\barspace}{1em}
6
7  \newenvironment{vertbar}{
8    \LWR@forcenewpage
9    \LWR@forceminwidth{\barwidth}
10   \begin{BlockClass}[%
11     border-left: \LWR@printlength{\LWR@atleastonept} solid black ; %
12     padding-left: \LWR@printlength{\barspace}%
13   ]{vertbar}
14 }{
15   \end{BlockClass}
16 }

```

File 550 **lwarp-vmargin.sty**

§ 659 Package **vmargin**

Pkg vmargin

vmargin is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{vmargin}[2004/07/15]

2 \newcommand*\LWRVM@customsize}[2]{}
3 \newcommand*\setpapersize}[2][\ifstrequal{#2}{custom}\LWRVM@customsize}{}
4 \newcommand*\setmargins}[8]{}
5 \newcommand*\setmarginsrb}[8]{}
6 \newcommand*\setmargnohf}[4]{}
7 \newcommand*\setmargnohfrb}[4]{}
8 \newcommand*\setmarg}[4]{}
9 \newcommand*\setmargrb}[4]{}
10 \newlength{\PaperWidth}
11 \setlength{\PaperWidth}{8.5in}
12 \newlength{\PaperHeight}
13 \setlength{\PaperHeight}{11in}
14 \newif\ifLandscape

```

File 551 **lwarp-vowel.sty**

§ 660 Package **vowel**

Pkg vowel

(Emulates or patches code by FUKUI REL.)

vowel is patched for use by lwarp.

This package has been tested with *pdf_latex* and the Type 1 TIPA fonts using the following package load sequence:

```

\usepackage[T3,T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[noenc]{tipa}
\usepackage{vowel}

```

for HTML output:

```

1 \LWR@ProvidesPackagePass{vowel}[2002/08/08]

2 \renewenvironment{vowel}[1][
3   {%
4     \begin{lateximage}[-vowel-~\PackageDiagramAltText]%
5     \@vowel[#1]%
6   }
7   {%
8     \@@vowel%
9     \end{lateximage}%
10  }

```

File 552 **lwarp-vpe.sty**

§ 661 Package **vpe**

Pkg vpe

vpe is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{vpe}[2012/04/18]

File 553 **lwarp-vwcol.sty**

§ 662 Package **vwcol**

Pkg vwcol

(Emulates or patches code by WILL ROBERTSON.)

vwcol is patched for use with lwarp.

The width option is ignored. All vwcol environments adjust to 1–3 equal-width columns, depending on the width of the browser window.

The remaining options are supported, except for lines and maxrecursion.

for HTML output: 1 \LWR@ProvidesPackagePass{vwcol}[2015/02/10]

Factored from \vwcol. Each is given a style tag to append to the final style.

\LWR@vwcol@addrule

```
{\style tag}
2 \newcommand*\LWR@vwcol@addrule[1]{%
3   \appto{\LWR@vwcolstyle}{%
4     #1: %
5     \LWR@printlength{\vwcol@rule} solid \LWR@origpound\LWR@vwcol@rulecolor ; %
6   }%
7 }
```

\LWR@vwcol@addrule

```
{\style tag}
8 \newcommand*\LWR@vwcol@addgap[1]{%
9   \appto{\LWR@vwcolstyle}{%
10    #1: %
11    \LWR@printlength{\vwcol@sep} ; %
12  }%
13 }
```

Env vwcol

{\key/values}

Redefine the environment to add a HTML style. The style is built depending on the required options.

```
14 \renewenvironment{vwcol}[1][[]]{%
```

New paragraph, and process the options:

```
15 \LWR@stoppars%
16 \vwcolsetup{#1}%
```

Begin with no style:

```
17 \newcommand*{\LWR@vwcolstyle}{}

```

presep and postsep are created with HTML margins:

```
18 \if@vwcol@presep
19   \appto{\LWR@vwcolstyle}{margin-left: 1em ; padding-left: .5em ; }
20 \fi
21 \if@vwcol@postsep
22   \appto{\LWR@vwcolstyle}{margin-right: 1em ; padding-right: .5em ; }
23 \fi

```

sep becomes column-gap:

```
24 \ifdimgreater{\vwcol@sep}{1sp}{
25   \LWR@vwcol@addgap{column-gap}
26   \LWR@vwcol@addgap{-moz-column-gap}
27   \LWR@vwcol@addgap{-webkit-column-gap}
28 }{}

```

rule become column-rule, while prerule and postrule become HTML borders:

```
29 \convertcolorspec{named}{\vwcol@rulecol}{HTML}\LWR@vwcol@rulecolor%
30 \ifdimgreater{\vwcol@rule}{0pt}{
31   \ifdimless{\vwcol@rule}{1pt}{
32     \setlength{\vwcol@rule}{1pt}
33   }{}
34   \LWR@vwcol@addrule{column-rule}
35   \LWR@vwcol@addrule{-moz-column-rule}
36   \LWR@vwcol@addrule{-webkit-column-rule}
37   \if@vwcol@prerule\LWR@vwcol@addrule{border-left}\fi
38   \if@vwcol@postrule\LWR@vwcol@addrule{border-right}\fi
39 }{}

```

Each of the justify options becomes a text-align. Indentation is added where appropriate.

```
40 \ifdefequal{\vwcol@justify}{\RaggedRight}{
41   \appto{\LWR@vwcolstyle}{text-align: left ; }
42   \ifdimgreater{\vwcol@parindent}{0pt}{
43     \appto{\LWR@vwcolstyle}{%
44       text-indent: \LWR@printlength{\vwcol@parindent} ; %
45     }
46   }{}
47 }{}

48 \ifdefequal{\vwcol@justify}{\RaggedLeft}{
49   \appto{\LWR@vwcolstyle}{text-align: right ; }
50 }{}

51 \ifdefequal{\vwcol@justify}{\Centering}{
52   \appto{\LWR@vwcolstyle}{text-align: center ; }
53 }{}

54 \ifdefequal{\vwcol@justify}{\justifying}{
55   \appto{\LWR@vwcolstyle}{text-align: justify ; }
56   \ifdimgreater{\vwcol@parindent}{0pt}{
57     \appto{\LWR@vwcolstyle}{%
58       text-indent: \LWR@printlength{\vwcol@parindent} ; %
59     }
60   }{}
61 }{}

```

Create the <div> with the assembled style:

```
62 \BlockClass[\LWR@vwcolstyle]{multicols}
63 }
```

When the environment ends:

```
64 {
65   \endBlockClass
66   \LWR@startpars
67 }
```

File 554 **lwarp-wallpaper.sty**

§ 663 Package **wallpaper**

(Emulates or patches code by MICHAEL H.F. WILKINSON.)

Pkg wallpaper

wallpaper is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{wallpaper}[2005/01/18]

```
2 \newcommand*\CenterWallPaper}[2]{}
3 \newcommand*\ThisCenterWallPaper}[2]{}
4 \newcommand*\TileWallPaper}[3]{}
5 \newcommand*\ThisTileWallPaper}[3]{}
6 \newcommand*\TileSquareWallPaper}[2]{}
7 \newcommand*\ThisTileSquareWallPaper}[2]{}
8 \newcommand*\ULCornerWallPaper}[2]{}
9 \newcommand*\ThisULCornerWallPaper}[2]{}
10 \newcommand*\LLCornerWallPaper}[2]{}
11 \newcommand*\ThisLLCornerWallPaper}[2]{}
12 \newcommand*\URCornerWallPaper}[2]{}
13 \newcommand*\ThisURCornerWallPaper}[2]{}
14 \newcommand*\LRCornerWallPaper}[2]{}
15 \newcommand*\ThisLRCornerWallPaper}[2]{}
16 \newcommand*\ClearWallPaper}{}
17 \newlength{\wpXoffset}
18 \newlength{\wpYoffset}
```

File 555 **lwarp-watermark.sty**

§ 664 Package **watermark**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg watermark

watermark is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{watermark}[2004/12/09]

```
2 \newcommand\watermark}[1]{}
3 \newcommand\leftwatermark}[1]{}
4 \newcommand\rightwatermark}[1]{}
5 \newcommand\thiswatermark}[1]{}
6 \newcommand\thispageheading}[1]{}

```

File 556 **lwarp-widetable.sty**

§ 665 Package **widetable**

(Emulates or patches code by CLAUDIO BECCARI.)

Pkg widetable

widetable is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{widetable}[2019-06-25]
2 \newenvironment{widetable}{\begin{tabular*}}{\end{tabular*}}
```

File 557 **lwarp-widows-and-orphans.sty**

§ 666 Package **widows-and-orphans**

Pkg widows-and-orphans

widows-and-orphans is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{widows-and-orphans}[2018/09/01]
2 \NewDocumentCommand\WaOsetup{m}{}
3 \NewDocumentCommand\WaOparameters{}{}
4 \NewDocumentCommand\WaOignorenext{}{}
```

File 558 **lwarp-witharrows.sty**

§ 667 Package **witharrows**

(Emulates or patches code by F. PANTIGNY.)

Pkg witharrows

witharrows is patched for use by lwarp. Emulation is provided for MATHJAX.

for HTML output:

```
1 \LWR@ProvidesPackagePass{witharrows}[2019/12/27]
2 \ifbool{mathjax}{
3   % For the hidden print version in the HTML:
4   \newcommand{\Arrow}[2][{}]{
5     \newcommand{\unicode}[1]{
6       \NewDocumentEnvironment { DispWithArrows } { ! d < > ! 0 { } +b}
7       {
8         \IfValueTF{#1}{
9           \begin{displaymath}
10          #1 \left\lbracket
11          \begin{align}
12          #3
13          \end{align}
14          \right .
15          \end{displaymath}
16        }{
```

```

17         \begin{displaymath}
18         \begin{align}
19         #3
20         \end{align}
21         \end{displaymath}
22     }
23 }
24 {}
25 \NewDocumentEnvironment { DispWithArrows* } { ! d < > ! 0 { } +b}
26 {
27     \IfValueTF{#1}{
28         \begin{displaymath}
29         #1 \left\lbracket
30         \begin{align*}
31         #3
32         \end{align*}
33         \right .
34         \end{displaymath}
35     }{
36         \begin{displaymath}
37         \begin{align*}
38         #3
39         \end{align*}
40         \end{displaymath}
41     }
42 }
43 {}
44 }{
45     % If not MathJax, use SVG images.
46 \BeforeBeginEnvironment{WithArrows}{\global\booltrue{LWR@unknownmathsize}}
47 \BeforeBeginEnvironment{DispWithArrows}{%
48     \begin{BlockClass}{displaymathnumbered}%
49     \begin{lateximage}%
50 }
51 \AfterEndEnvironment{DispWithArrows}{\end{lateximage}\end{BlockClass}}
52 \BeforeBeginEnvironment{DispWithArrows*}{%
53     \begin{BlockClass}{displaymath}%
54     \begin{lateximage}%
55 }
56 \AfterEndEnvironment{DispWithArrows*}{\end{lateximage}\end{BlockClass}}
57 }
58
59 \begin{warpMathJax}
60 \CustomizeMathJax{\newenvironment{WithArrows}[1][[]]{\begin{aligned}}{\end{aligned}}}
61 % Unable to make a sized box.
62 \CustomizeMathJax{\newcommand{\Arrow}[2][[]]{&{\Large\unicode{x2938}}~\textit{#2}}}
63 \end{warpMathJax}

```

File 559 **lwarp-wrapfig.sty**

§ 668 Package **wrapfig**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg wrapfig

wrapfig is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{wrapfig}[2003/01/31]

```

2 \newcommand*\LWR@wrapposition}{
3
4 \newcommand{\LWR@wrapfig@printHTMLwidth}{\LWR@printlength{\LWR@templengthone}}
5
6 \AtBeginDocument{
7   \IfPackageLoadedTF{keyfloat}{
8     \renewcommand{\LWR@wrapfig@printHTMLwidth}{%
9       \ifboolexpr{
10         test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or
11         bool {KFLT@inkeysubfloats}
12       }%
13       {\LWR@printpercentlength{\LWR@templengthone}{\linewidth}\%; }%
14       {\LWR@printlength{\LWR@templengthone}}%
15     }%
16   }{
17 }
18
19 \newcommand*\LWR@subwrapfigure}[2]{%
20   \renewcommand*\LWR@wrapposition}{}%
21   \ifthenelse{%
22     \equal{#1}{r}\OR\equal{#1}{R}\OR%
23     \equal{#1}{o}\OR\equal{#1}{O}%
24   }%
25     {\renewcommand*\LWR@wrapposition}{float:right}}%
26     {\renewcommand*\LWR@wrapposition}{float:left}}%
27   \setlength{\LWR@templengthone}{#2}%
28   \LWR@BlockClassWP{%
29     width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
30     margin:10pt%
31   }%
32   {%
33     width:\LWR@wrapfig@printHTMLwidth; %
34     \LWR@wrapposition; %
35   }%
36   (note)%
37   {marginblock}%
38
39   \setlength{\linewidth}{\LWR@templengthone}%
40 }
41
42 \NewDocumentEnvironment{wrapfigure}{o m o m}
43 {%
44   \begin{LWR@setvirtualpage}*%
45   \LWR@subwrapfigure{#2}{#4}%
46   \renewcommand*\@capttype}{figure}%
47 }
48 {%
49   \endLWR@BlockClassWP%
50   \end{LWR@setvirtualpage}%
51 }
52
53
54 \NewDocumentEnvironment{wraptable}{o m o m}
55 {%
56   \begin{LWR@setvirtualpage}*%
57   \LWR@subwrapfigure{#2}{#4}%
58   \renewcommand*\@capttype}{table}%
59 }
60 {%

```

```

61 \endLWR@BlockClassWP%
62 \end{LWR@setvirtualpage}%
63 }
64
65
66 \NewDocumentEnvironment{wrapfloat}{m o m o m}
67 {%
68 \begin{LWR@setvirtualpage}*%
69 \LWR@subwrapfigure{#3}{#5}%
70 \renewcommand*{\@capttype}{#1}%
71 }
72 {%
73 \endLWR@BlockClassWP%
74 \end{LWR@setvirtualpage}%
75 }
76
77 \newlength{\wrapoverhang}

```

File 560 **lwarp-wrapfig2.sty**

§ 669 Package **wrapfig2**

(Emulates or patches code by DONALD ARSENEAU, CLAUDIO BECCARI.)

Pkg wrapfig2

wrapfig2 is emulated via a modified version of the wrapfig emulation.

for HTML output:

```

1 \@ifpackageloaded{color}{}%
2 \@ifpackageloaded{xcolor}{\LWR@origRequirePackage{xcolor}}%
3 }
4
5 \RequirePackage{float}
6
7 \IfPackageLoadedWithOptionsTF{wrapfig2}{WFold}
8 {}% v4.0
9 {% v5+
10 \floatstyle{plain}
11 \ifcsname chapter\endcsname
12 \newfloat{text}{tbp}{lotx}[chapter]
13 \else
14 \newfloat{text}{tbp}{lotx}
15 \fi
16 \floatname{text}{Text}
17 % \let\WF@text@caption\float@caption
18 }
19
20
21 \LWR@ProvidesPackageDrop{wrapfig2}[2022-02-16]
22
23 \LWR@origRequirePackage{lwarp-wrapfig}

24 \RenewDocumentEnvironment{wrapfigure}{o m o G{0pt} s}% original
25 {\wrapfloat{figure}[#1][#2][#3][#4]}%
26 {\endwrapfloat}
27
28 \RenewDocumentEnvironment{wraptable}{o m o G{0pt} s}% original
29 {\wrapfloat{table}[#1][#2][#3][#4]}%
30 {\endwrapfloat}

```

```

31
32 \RenewDocumentEnvironment{wrapfloat}{m o m o G{0pt}}% lwarp
33 {%
34   \begin{LWR@setvirtualpage}*%
35   \LWR@subwrapfigure{#3}{#5}%
36   \renewcommand*{\@capttype}{#1}%
37 }
38 {%
39   \endLWR@BlockClassWP%
40   \end{LWR@setvirtualpage}%
41 }

42 \IfPackageLoadedWithOptionsTF{wrapfig2}{WFold}
43 {% v4.0:
44   \NewDocumentEnvironment{wraptext}%
45     {O{l} D||{0.5\columnwidth} D<>{0} D(){figure}}%
46     {%
47       \wrapfloat{#4}[]{}{#1}[]{}{#2}%
48       \tcolorbox%
49     }
50     {%
51       \endtcolorbox%
52       \endwrapfloat%
53       \ignorespaces%
54     }
55 }{}
56
57 \IfPackageLoadedWithOptionsTF{wrapfig2}{WFfive}
58 {% v5
59   \definecolor{WFbackground}{rgb}{0.95,0.95,0.95}
60   \definecolor{WFframe}{rgb}{0.1,0.1,0.1}
61   \colorlet{WFtext}{black}
62   \def\SetWFbgd#1{\colorlet{WFbackground}{#1}}
63   \def\SetWFfrm#1{\colorlet{WFframe}{#1}}
64   \def\SetWFtxt#1{\colorlet{WFtext}{#1}}
65   \def\WFsplitdimens#1,#2!{\fboxrule=#1\relax\fboxsep=#2\relax}
66
67   \NewDocumentEnvironment{wraptext}{O{0} m O{0pt} G{0.5\columnwidth}}
68   {%
69     \wrapfloat{text}[]{}{#2}[]{}{#4}%
70   }
71   {%
72     \endwrapfloat%
73     \ignorespaces%
74   }
75
76   \NewDocumentCommand\includeframedtext{O{\insertwidth} m O{1pt,1ex} o}%
77   {%
78     \WFsplitdimens #3!
79     \convertcolorspec{named}{WFtext}{HTML}\LWR@tempcolor%
80     \LWR@HTML@fcolorboxBlock%
81     [named]{WFframe}[named]{WFbackground}{#2}%
82     (%
83       color:\ \LWR@origpound\LWR@tempcolor ; %
84       border-radius:\ 1ex%
85     )%
86   }
87 }{} v6+
88 \RequirePackage{xkeyval}
89

```

```

90 \definecolor{WFbackground}{rgb}{0.95,0.95,0.95}
91 \definecolor{WFframe}{rgb}{0.1,0.1,0.1}
92 \colorlet{WFtext}{black}
93 \def\SetWFbgd#1{\colorlet{WFbackground}{#1}}
94 \def\SetWFfrm#1{\colorlet{WFframe}{#1}}
95 \def\SetWFtxt#1{\colorlet{WFtext}{#1}}
96 \def\WFSplitdimens#1,#2!{\fboxrule=#1\relax\fboxsep=#2\relax}
97
98 \newlength{\LWR@wrapfigtwo@radius}
99 \setlength{\LWR@wrapfigtwo@radius}{1ex}
100
101 \DeclareOptionX<wraptext>{scalefactor}[0.8]{%
102 %     \def\WFscalefactor{#1}%
103 }
104 \DeclareOptionX<wraptext>{fboxrule}[1pt]{\fboxrule=#1}
105 \DeclareOptionX<wraptext>{fboxsep}[1ex]{\fboxsep=#1}
106 \DeclareOptionX<wraptext>{framecolor}[WFframe]{\SetWFfrm{#1}}
107 \DeclareOptionX<wraptext>{backgroundcolor}[WFbackground]{\SetWFbgd{#1}}
108 \DeclareOptionX<wraptext>{textcolor}[WFtext]{\SetWFtxt{#1}}
109 \DeclareOptionX<wraptext>{fontstyle}[\normalfont]{#1}
110 \DeclareOptionX<wraptext>{radius}[\fboxsep]{%
111     \setlength{\LWR@wrapfigtwo@radius}{#1}%
112 }
113 \DeclareOptionX<wraptext>{insertionwidth}[0.5\columnwidth]{%
114 %     \insertwidth=#1%
115 }
116
117 \DeclareOptionX*{\PackageWarning{wrapfig2}{'\CurrentOption' ignored}}
118
119 \ExecuteOptionsX<wraptext>{scalefactor, fboxrule, fboxsep, framecolor,
120 backgroundcolor, textcolor, fontstyle, radius, insertionwidth}
121
122 \ProcessOptionsX*
123
124 \NewDocumentEnvironment{wraptext}{0{0} m 0{0pt} G{0.5\columnwidth}}
125 {%
126     \wrapfloat{text}[][#2][]{#4}%
127 }
128 {%
129     \endwrapfloat%
130     \ignorespaces%
131 }
132
133 \NewDocumentCommand\includeframedtext{O{\insertwidth} m O{ } o}
134 {%
135     \ExecuteOptionsX<wraptext>{#3}%     executes possible key=value options
136     \convertcolorspec{named}{WFtext}{HTML}\LWR@tempcolor%
137     \LWR@HTML@fcolorboxBlock%
138     [named]{WFframe}[named]{WFbackground}%
139     {\LWR@textcurrentfont{#2}}%
140     (%
141         color:\LWR@origpound\LWR@tempcolor ; %
142         border-radius:\LWR@printlength{\LWR@wrapfigtwo@radius}%
143     )%
144 }
145 }

```

File 561 **lwarp-xbmks.sty**

§ 670 Package **xbmks**

Pkg xbmks xbmks is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{xbmks}[2018/07/04]

```
2 \newcommand{\xbmksetup}[1]{}
3 \NewDocumentCommand{\pdfbookmarkx}{o m o m}{}
4 \NewDocumentCommand{\currentpdfbookmarkx}{m o m}{}
5 \NewDocumentCommand{\subpdfbookmarkx}{m o m}{}
6 \NewDocumentCommand{\belowpdfbookmarkx}{m o m}{}

```

File 562 **lwarp-xcolor.sty**

§ 671 Package **xcolor**

(Emulates or patches code by DR. UWE KERN.)

Pkg xcolor xcolor is supported by lwarp.

§ 671.1 **Limitations**

\colorboxBlock and \fcolorboxBlock \colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a <div> instead of a . These <div>s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none \fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support Color definitions, models, and mixing are fully supported without any changes required.

colored tables \rowcolors is supported, except that the optional argument is ignored so far.

colored text and boxes \textcolor, \colorbox, and \fcolorbox are supported.

\color and \pagecolor \color and \pagecolor are ignored. Use css or \textcolor where possible.

§ 671.2 **xcolor definitions: location and timing**

The `lwarp` core and its `lwarp-xcolor` package are tightly integrated to allow comparable results for print, HTML, and print inside an HTML lateximage. This requires a number of definitions and redefinitions depending on whether each of `xcolor` and `lateximage` is being used, and whether print or HTML is being generated. Some of these actions are one-time when `xcolor` is loaded, and others are temporary as `lateximage` is used.

When `xcolor` is loaded in print mode: No special actions are taken at the time that `xcolor` is loaded in print mode, but see `\AtBeginDocument` below.

When `lwarp-xcolor` is loaded in HTML mode: `xcolor`'s original definitions are saved for later restoration. `\LWR@restoreorigformatting` is appended to restore these definitions for use inside a `lateximage`. New HTML-mode definitions are created for `\textcolor`, `\pagecolor`, `\nopagecolor`, `\colorbox`, `\colorboxBlock`, `\fcolorbox`, `\fcolorboxBlock`, and `fcolorminipage`.

`\AtBeginDocument` in print or HTML mode: See Section 89. If `xcolor` has been loaded, the print-mode `\fcolorbox` is modified to accept a background color of none, and additional definitions are created for `lwarp`'s new macros print-mode macros `\colorboxBlock`, `\fcolorboxBlock`, and `fcolorminipage`. The HTML versions of these macros will already have been created by `lwarp-xcolor` if it has been loaded.

For use inside an HTML `lateximage`, `\LWR@restoreorigformatting` is appended to temporarily set these functions to their print-mode versions.

In a `lateximage` in HTML mode: `\LWR@restoreorigformatting` temporarily restores the print-mode definitions of `xcolor`'s functions. See `\LWR@restoreorigformatting` on page 528.

`\color:`

Print: Used as-is.

HTML: Ignored by `pdftotext`, and will not appear.

HTML lateximage: Colors will appear in a `lateximage`.

`\textcolor:`

Print: Used as-is.

HTML: Redefined by `lwarp-xcolor`, page 1220.

HTML lateximage: Remembers and reuses the print version.

`\pagecolor:`

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a `lateximage`.

`\nopagecolor:`

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a `lateximage`.

\colorbox:**Print:** Used as-is.**HTML:** Redefined by lwarp-xcolor, page 1220.**HTML lateximage:** Remembers and reuses the print version.**\colorboxBlock:****Print:** Becomes \colorbox.**HTML:** Newly defined by lwarp-xcolor to use a <div>, page 1220.**HTML lateximage:** Remembers and reuses the print version \colorbox.**\fcolorbox:****Print:** Modified to allow a background of none.`\LWR@print@fcolorbox` at section 89**HTML:** Redefined by lwarp-xcolor, page 1221.**HTML lateximage:** Remembers and reuses the print version.**\fcolorboxBlock:****Print:** Becomes \fcolorbox. Section 89**HTML:** Newly defined by lwarp-xcolor to use a <div>, page 1221.**HTML lateximage:** Remembers and reuses the print version \fcolorbox.**fcolorminipage:****Print:** Newly defined in the lwarp core.`LWR@print@fcolorminipage` at section 89**HTML:** Newly defined by lwarp-xcolor, page 1222.**HTML lateximage:** Uses the print version.**\boxframe:****Print:** Used as-is.**HTML:** Redefined by lwarp-xcolor, page 1223.**HTML lateximage:** Remembers and reuses the print version.§ 671.3 **Package loading****for HTML output:** `1 \LWR@ProvidesPackagePass{xcolor}[2016/05/11]``\color@endgroup's \endgraf` was conflicting with lwarp's paragraph handling.`2 \let\color@endgroup\endgroup`

§ 671.4 Remembering and restoring original definitions

Remember the following print-mode actions to be restored when inside a `lateximage` environment:

```
3 \LetLtxMacro\LWR@print@pagecolor\pagecolor
4 \LetLtxMacro\LWR@print@npagecolor\npagecolor
```

`\LWR@restoreorigformatting` Inside a `lateximage` the following gets restored to their print-mode actions:

```
5 \appto\LWR@restoreorigformatting{%
6   \LetLtxMacro\pagecolor\LWR@print@pagecolor%
7   \LetLtxMacro\npagecolor\LWR@print@npagecolor%
8 }
```

§ 671.5 `\normalcolor`

`\normalcolor`

```
9 \DeclareRobustCommand{\LWR@HTML@normalcolor}{\color{black}}%
10
11 \LWR@formatted{normalcolor}
```

§ 671.6 HTML color style

`\LWR@findcurrenttextcolor` Sets `\LWR@tempcolor` to the current color.

```
12 \renewcommand*{\LWR@findcurrenttextcolor}{%
13   \LWR@traceinfo{\LWR@findcurrenttextcolor}%
14   \protect\colorlet{\LWR@current@color}{.}%
15   \LWR@traceinfo{\LWR@findcurrenttextcolor B}%
16   \protect\convertcolorspec{named}{\LWR@current@color}{HTML}\LWR@tempcolor\relax%
17   \LWR@traceinfo{\LWR@findcurrenttextcolor: done}%
18 }
```

Prints a color style for the current color.

`\LWR@currenttextcolorstyle`

```
19 \newcommand*{\LWR@currenttextcolorstyle}{%
20   \LWR@findcurrenttextcolor%
21   \ifdefstring{\LWR@tempcolor}{000000}%
22   {}%
23   {color: \LWR@origpound\LWR@tempcolor ; }%
24 }
```

`\LWR@textcurrentcolor` `{\text}` Like `\textcolor` but uses the current `\color` instead.

```
25 \DeclareDocumentCommand{\LWR@textcurrentcolor}{m}{%
26   \begingroup%
27   \LWR@hook@processingtags%
28   \LWR@findcurrenttextcolor%
29   \InlineClass[color:\LWR@origpound\LWR@tempcolor]{textcolor}{%
30     \renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
31     #1%
32   }%
33   \endgroup%
34 }
```

`\LWR@colorstyle``{\langle 1: model \rangle} {\langle 2: color \rangle}`

For a color style, prints the color converted to HTML colors.

```
35 \NewDocumentCommand{\LWR@colorstyle}{m m}{%
36   \begingroup%
37   \LWR@hook@processingtags%
```

Use the `xcolor` package to convert to an HTML color space:

```
38   \convertcolourspec{#1}{#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```
39   \LWR@origpound\LWR@tempcolor%
40   \endgroup%
41 }
```

`\LWR@backgroundcolor``[\langle model \rangle] {\langle color \rangle} {\langle text \rangle}`

Similar to `\textcolor`, but prints black text against a color background.

Converted into an HTML hex color span.

```
42 \NewDocumentCommand{\LWR@backgroundcolor}{O{named} m m}{%
43   \begingroup%
44   \LWR@hook@processingtags%
45   \InlineClass[background:\LWR@colorstyle{#1}{#2}]{backgroundcolor}{%
46     #3%
47   }%
48   \endgroup%
49 }
```

§ 671.7 HTML border

`\LWR@borderpadding``{\langle colorstyle \rangle} {\langle color \rangle}` Prints the HTML attributes for a color border and padding.

`\LWR@forceminwidth` must be used first in order to set the border width.

```
50 \newcommand*{\LWR@borderpadding}[2]{%
51   border:\LWR@printlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
52   padding:\LWR@printlength{\fboxsep}%
53 }
```

§ 671.8 High-level macros

`\color` `[\langle model \rangle] {\langle color \rangle}`

The current `\color` is used by HTML rules and frames, but does not affect the current HTML text output, due to the lack of HTML states and scoping limitations. Use `\textcolor` if possible.

```
54 \NewDocumentCommand{\LWR@HTML@color}{o m}{%
55   \IfValueTF{#1}{%
56     \LWR@print@color[#1]{#2}%
57     \convertcolourspec{#1}{#2}{HTML}\LWR@tempcolor%
58   }{%
59     \LWR@print@color{#2}%
60     \convertcolourspec{named}{#2}{HTML}\LWR@tempcolor%
61   }%
62   \edef\LWR@currenttextcolor{\LWR@origpound\LWR@tempcolor}%
63 }
```

```
64
65 \LWR@formatted{color}
```

`\textcolor` [*<model>*] {*<color>*} {*<text>*}

Converted into an HTML hex color span.

```
66 \NewDocumentCommand{\LWR@HTML@textcolor}{o m m}{%
67   \begingroup%
68   \LWR@hook@processingtags%
69   \IfValueTF{#1}{%
70     \color[#1]{#2}%
71   }{%
72     \color{#2}%
73   }%
74   \InlineClass[color:\LWR@currenttextcolor]{textcolor}{#3}%
75   \endgroup%
76 }%
77
78 \LWR@formatted{textcolor}
```

`\pagecolor` [*<model>*] {*<color>*}

Ignored. Use CSS instead.

```
79 \renewcommand*{\pagecolor}[2][named]{}
```

`\nopagecolor` Ignored.

```
80 \renewcommand*{\nopagecolor}{}%
```

`\colorbox` [*<model>*] {*<color>*} {*<text>*}

Converted into an HTML hex background color ``.

```
81 \NewDocumentCommand{\LWR@HTML@colorbox}{O{named} m +m}{%
82   \begingroup%
83   \LWR@hook@processingtags%
84   \InlineClass[%
85     background:\LWR@colorstyle{#1}{#2} ; %
86     padding:\LWR@printlength{\fboxsep}%
87   ]{colorbox}{#3}%
88   \endgroup%
89 }
```

`\colorboxBlock` [*<model>*] {*<color>*} {*<text>*}

Converted into an HTML hex background color `<div>`.

```
90 \NewDocumentCommand{\LWR@HTML@colorboxBlock}{O{named} m +m}{%
91   \begingroup%
92   \LWR@hook@processingtags%
93   \LWR@stoppars%
```

```

94   \begin{BlockClass}[%
95     background:\LWR@colorstyle{#1}{#2} ; %
96     padding:\LWR@printlength{\fboxsep}%
97   ]{colorboxBlock}
98   #3
99   \end{BlockClass}%
100  \endgroup%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

101  \global\booltrue{LWR@minipagethispar}%
102 }

```

`\fcolorbox` [*<framemodel>*] {<framecolor>} [*<boxmodel>*] {<boxcolor>} {<text>}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

103 \NewDocumentCommand{\LWR@HTML@fcolorbox}{O{named} m O{#1} m +m}{%
104   \LWR@traceinfo{HTML fcolorbox #2 #4}%
105   \begingroup%
106   \LWR@hook@processingtags%
107   \LWR@forceminwidth{\fboxrule}%
108   \ifthenelse{\equal{#4}{none}}{%
109     {% no background color
110       \InlineClass[%
111         \LWR@borderpadding{#1}{#2}%
112       ]{fcolorbox}{#5}%
113     }%
114     {% yes background color
115       \InlineClass[%
116         \LWR@borderpadding{#1}{#2} ; %
117         background:\LWR@colorstyle{#3}{#4}%
118       ]{fcolorbox}{#5}%
119     }%
120   \endgroup%
121 }

```

`\fcolorboxBlock` [*<framemodel>*] {<framecolor>} [*<boxmodel>*] {<boxcolor>} {<text>} (<add'l html style>)

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

122 \NewDocumentCommand{\LWR@HTML@fcolorboxBlock}{O{named} m O{#1} m +m d()}{%
123   \LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
124   \begingroup%
125   \LWR@hook@processingtags%
126   \LWR@forceminwidth{\fboxrule}%
127   \LWR@stoppars%

```

```

128 \ifthenelse{\equal{#4}{none}}%
129   {% no background color
130     \begin{BlockClass}[%
131       \LWR@borderpadding{#1}{#2}%
132       \IfValueT{#6}{ ; #6}%
133     ]{fcolorboxBlock}
134     #5
135     \end{BlockClass}%
136   }%
137   {% yes background color
138     \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
139     \begin{BlockClass}[%
140       background:\LWR@origpound\LWR@tempcolortwo\ ; %
141       \LWR@borderpadding{#1}{#2}%
142       \IfValueT{#6}{ ; #6}%
143     ]{fcolorboxBlock}
144     #5
145     \end{BlockClass}%
146   }%
147 \endgroup%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

148 \global\booltrue{LWR@minipagethispar}%
149 \LWR@traceinfo{HTML fcolorboxBlock done}%
150 }

```

Creates a framed HTML <div> around its contents.

A print-output version is defined in the lwarp core: section 89

```

\LWR@subfcolorminipage   {<framemodel>} {<framecolor>} {<background tag>} {<height>}
151 \NewDocumentCommand{\LWR@subfcolorminipage}{m m m m}{%
152   \LWR@stoppars%
153   \begin{BlockClass}[%
154     #3%
155     \LWR@borderpadding{#1}{#2} ; %
156     \IfValueT{#4}{height:\LWR@printlength{\LWR@tempheight} ; }%
157     width:\LWR@printlength{\LWR@tempwidth}%
158   ]{fcolorminipage}%
159 }

```

```

Env fcolorminipage  [<1:framemodel>] {<2:framecolor>} [<3:boxmodel>] {<4:boxcolor>} [<5:align>]
[<6:height>] [<7:inner-align>] {<8:width>}

```

```

160 \NewDocumentEnvironment{LWR@HTML@fcolorminipage}{O{named} m O{#1} m O{c} o o m}
161 {%
162   \LWR@hook@processingtags%
163   \setlength{\LWR@tempwidth}{#8}%
164   \IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
165   \LWR@forceminwidth{\fboxrule}%
166   \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
167   \ifthenelse{\equal{#4}{none}}%
168     {\LWR@subfcolorminipage{#1}{#2}{#6}}%

```

```

169     {%
170         \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
171         \LWR@subfcolorminipage{#1}{#2}%
172         {background:\LWR@origpound\LWR@tempcolortwo\ ;}%
173         {#6}%
174     }%
175 }%
176 {%
177     \end{BlockClass}%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

178     \global\booltrue\LWR@minipagethispar%
179 }

```

`\boxframe` $\langle width \rangle$ $\langle height \rangle$ $\langle depth \rangle$

The depth is added to the height, but the box is not decended below by the depth. `\textcolor` is honored.

```

180 \newcommand*\LWR@HTML@boxframe[3]{%
181     {%
182         \setlength{\LWR@tempwidth}{#1}%
183         \setlength{\LWR@tempheight}{#2}%
184         \addtolength{\LWR@tempheight}{#3}%
185         \LWR@forceminwidth{\fboxrule}%
186         \LWR@findcurrenttextcolor%
187         \InlineClass[%
188             display:inline-block ; %
189             border:%
190             \LWR@printlength{\LWR@atleastonept} % space
191             solid % space
192             \LWR@currenttextcolor{} ; % space
193             width:\LWR@printlength{\LWR@tempwidth} ; %
194             height:\LWR@printlength{\LWR@tempheight}%
195         ]{boxframe}{}%
196     }%
197 }
198
199 \LWR@formatted{boxframe}

```

§ 671.9 Row colors

`\rowcol@rs`

$\langle cmds \rangle$ $\langle startrow \rangle$ $\langle odd color \rangle$ $\langle even color \rangle$

```

200 \newcommand*\LWR@xcolortempcolor{}
201
202 \def\rowcol@rs[#1]#2#3#4%
203 {%
204     \rownum=1%
205     \@rowcolorstrue%
206     \@ifxempty{#3}%
207     {\def\@oddrowcolor{\@norowcolor}}%
208     {%
209         \convertcolorspec{named}{#3}{HTML}\LWR@xcolortempcolor%
210         \edef\@oddrowcolor{%
211             \csdef{\LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%

```

```

212     }%
213   }%
214   \@ifxempty{#4}%
215     {\def\@evenrowcolor{\@norowcolor}}%
216     {%
217       \convertcolorspec{named}{#4}{HTML}\LWR@xcolortempcolor%
218       \edef\@evenrowcolor{%
219         \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
220       }%
221     }%
222   \if@rowcmd
223     \def\@rowcolors
224     {%
225 %       #1%
226       \if@rowcolors
227 %         \noalign{%
228 %           \relax\ifnum\rownum<#2\@norowcolor\else
229 %             \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi\fi%
230 %         }%
231       \fi%
232     }%
233   \else
234     \def\@rowcolors
235     {%
236       \if@rowcolors
237         \ifnum\rownum<#2%
238 %           \noalign{%
239 %             \@norowcolor
240 %           }
241         \else
242 %           #1%
243 %           \noalign{%
244 %             \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi%
245 %           }%
246         \fi
247       \fi%
248     }%
249   \fi
250   \ignorespaces%
251 }

```

`\@norowcolor`

Turns off color for this row.

```

252 \def\@norowcolor{%
253   \renewcommand{LWR@xcolorrowHTMLcolor}{}%
254 }

```

`\@rowc@lors`

Executed at the end of each row.

```

255 \def\@rowc@lors{%
256 %   \noalign{%
257 %     \advance\rownum\@ne%
258 %   }%
259   \@rowcolors%
260 }

```

File 563 **lwarp-xexchangebar.sty**

§ 672 Package **xexchangebar**

Pkg xexchangebar

xexchangebar is ignored

for HTML output:

```
1 \LWR@ProvidesPackageDrop{xexchangebar}[2017/08/03]
2 \LWR@origRequirePackage{lwarp-changebar}
```

File 564 **lwarp-xellipsis.sty**

§ 673 Package **xellipsis**

Pkg xellipsis

(Emulates or patches code by DONALD P. GOODMAN III.)

xellipsis is patched for use by lwarp.

When non-zero, each of the spaces is converted to an HTML thin unbreakable space.

for HTML output:

```
1 \LWR@ProvidesPackagePass{xellipsis}[2015/11/01]

2 \newcommand*{\LWR@xellipsespace}[1]{%
3 \ifdim#1=0pt\else%
4   \ifdim#1<\fontdimen2\font%
5     \,%
6   \else%
7     ~%
8   \fi%
9 \fi%
10 }
11
12 \def\xelip{%
13 \mbox{%
14   \LWR@xellipsespace{\xelipprebef}%
15   \xelipprechar%
16   \LWR@xellipsespace{\xelippreaft}%
17   \LWR@xellipsespace{\xelipbef}%
18   \xelipchar%
19   \xel@loopi = 1%
20   \loop\ifnum\xelipnum>\xel@loopi%
21     \advance\xel@loopi by1%
22     \LWR@xellipsespace{\xelipgap}%
23     \xelipchar%
24   \repeat%
25   \LWR@xellipsespace{\xelipaft}%
26   \LWR@xellipsespace{\xelippostbef}%
27   \xelippostchar%
28   \LWR@xellipsespace{\xelippostaft}%
29 }%
30 }%
```

File 565 **lwarp-xetexko.sty**

§ 674 Package **xetexko**

(Emulates or patches code by DOHYUN KIM.)

Pkg xetexko

xetexko is patched for use by lwarp.

for HTML output:

```

1 \LWR@Loadbefore{xetexko}
2
3 \LWR@ProvidesPackagePass{xetexko}[2021/09/06]

4 \protected\def\typesetvertical{}
5 \protected\def\typesethorizontal{}
6
7 \def\verticaltypesetting{\BlockClass{verticalrl}}
8 \def\beginverticaltypesetting{\BlockClass{verticalrl}}
9 \def\endverticaltypesetting{\endBlockClass}
10
11 \protected\def\vertical#1{\BlockClass{verticalrl}}
12 \protected\def\endvertical{\endBlockClass}
13 \protected\def\horizontal#1{\BlockClass{horizontalrb}}
14 \protected\def\endhorizontal{\endBlockClass}
15 \DeclareDocumentCommand{\vertlatin}{m}{#1}

```

File 566 **lwarp-xevlna.sty**

§ 675 Package **xevlna**

(Emulates or patches code by ZDENĚK WAGNER.)

Pkg xevlna

xevlna is patched for use by lwarp.

Non-breakable spaces are inserted into HTML.

for HTML output:

```

1 \LWR@ProvidesPackagePass{xevlna}[2016/09/05]

2 \def\ProcessCSpreposition{\ifx\next\xevlnaXeTeXspace\HTMLentity{nbsp}\fi}
3
4 \appto{\LWR@hook@processingtags}{\xevlnaDisable}%

```

File 567 **lwarp-xfakebold.sty**

§ 676 Package **xfakebold**

(Emulates or patches code by HERBERT VOSS.)

Pkg xfakebold

xfakebold is patched for use by lwarp, and additional underlying support is found in the lwarp core.

 **text mode** `xfakebold` is only used in `svg math` and `lateximages`. Text mode is not set bold, but `\setBold` in text will be applied to any following `svg math`.

for HTML output:

```

1 \LWR@ProvidesPackagePass{xfakebold}[2020/06/24]
2 \newcommand*\LWR@HTML@setBold{\booltrue{LWR@xfakebold}}
3 \LWR@formatted{setBold}
4
5 \newcommand*\LWR@HTML@unsetBold{\boolfalse{LWR@xfakebold}}
6 \LWR@formatted{unsetBold}
7
8 \renewcommand*\LWR@applyxfakebold{%
9   \ifbool{LWR@xfakebold}{\LWR@print@setBold}{\LWR@print@unsetBold}%
10 }
```

For `MATHJAX`, `xfakebold` is ignored.

```

11 \begin{warpMathJax}
12 \CustomizeMathJax{\newcommand{\setBold}[1][{}]}
13 \CustomizeMathJax{\newcommand{\unsetBold}{}}
14 \end{warpMathJax}
```

File 568 **lwarp-xfrac.sty**

§ 677 Package **xfrac**

(Emulates or patches code by THE L^AT_EX3 PROJECT.)

Pkg xfrac

Supported by adding `xfrac` instances, and emulated for `MATHJAX`.

for HTML output:

```

1 \LWR@ProvidesPackagePass{xfrac}[2018-08-23]
```

 **font size** In the user's document preamble, `lwarp` should be loaded after font-related setup. During `HTML` conversion, this font is used by `lwarp` to generate its initial `PDF` output containing `HTML` tags, later to be converted by `pdftotext` to a plain text file. While the text may be in any font which `pdftotext` can read, the math is directly converted into `svg` images using this same user-selected font. `xfrac` below is set for the Latin Modern (`lmr`) font. If another font is used, it may be desirable to redefine `\xfracHTMLfontsize` with a different `em` size.

\sfrac

```
[\instance] {\num} [\sep] {\denom}
```

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in `HTML` tags. `\scalebox` is made null inside the numerator and denominator, since the `HTML` tags should not be scaled, and we do not want to introduce additional `HTML` tags for scaling.

In math mode, which will appear inside a `lateximage`, no adjustments are necessary.

`\xfracHTMLfontsize` User-redefinable macro which controls the font size of the fraction.

```

2 \newcommand*\xfracHTMLfontsize{.6em}
```

instances Instances of `xfrac` for various font choices:

Produce CSS for a small raised numerator and a small denominator.

Scaling is turned off so that *pdftotext* correctly reads the result.

```

3 \DeclareInstance{xfrac}{default}{text}{
4   numerator-format = {%
5     \begingroup%
6     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
7     \InlineClass{numerator}{#1}\,%
8     \endgroup%
9   },
10  denominator-format = {%
11    \begingroup%
12    \RenewDocumentCommand{\scalebox}{m o m}{##3}%
13    \InlineClass{denominator}{#1}%
14    \endgroup%
15  },

```

For *pdftotext*, do not scale the text:

```

16   scaling = false
17 }
18
19 \DeclareInstance{xfrac}{lmr}{text}{
20   numerator-format = {%
21     \begingroup%
22     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
23     \InlineClass{numerator}{#1}\,%
24     \endgroup%
25   },
26   denominator-format = {%
27     \begingroup%
28     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
29     \InlineClass{denominator}{#1}%
30     \endgroup%
31   },

```

For *pdftotext*, do not scale the text:

```

32   scaling = false
33 }
34
35 \DeclareInstance{xfrac}{lmss}{text}{
36   numerator-format = {%
37     \begingroup%
38     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
39     \InlineClass{numerator}{#1}\,%
40     \endgroup%
41   },
42   denominator-format = {%
43     \begingroup%
44     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
45     \InlineClass{denominator}{#1}%
46     \endgroup%
47   },

```

For *pdftotext*, do not scale the text:

```

48   scaling = false

```

```

49 }
50
51 \DeclareInstance{xfrac}{lmtt}{text}{
52   numerator-format = {%
53     \begingroup%
54     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
55     \InlineClass{numerator}{#1}\,%
56     \endgroup%
57   },
58   denominator-format = {%
59     \begingroup%
60     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
61     \InlineClass{denominator}{#1}%
62     \endgroup%
63   },

```

For *pdftotext*, do not scale the text:

```

64   scaling = false
65 }

```

For MATHJAX:

```

66 \begin{warpMathJax}
67 \CustomizeMathJax{\newcommand{\LWRsfrac}[2][/{\}^{\LWRsfracnumerator\!#1}_{#2}}}{
68 \CustomizeMathJax{\newcommand{\sfrac}[2][\def\LWRsfracnumerator{#2}\LWRsfrac}}
69 \end{warpMathJax}

```

File 569 **lwarp-xltabular.sty**

§ 678 Package **xltabular**

(Emulates or patches code by ROLF NIEPRASCHK, HERBERT VOSS.)

Pkg xltabular

xltabular is emulated by lwarp.

for HTML output: Relies on tabularx.

 **table numbering** At present, an xltabular without a caption or with only a \caption* may be misnumbered in HTML, so it may be necessary to place at the end of the table:

```
\warpHTMLonly{\addtocounter{table}{-1}}
```

```

1 \RequirePackage{tabularx}
2 \RequirePackage{ltablex}
3
4 \LWR@ProvidesPackageDrop{xltabular}[2018/05/23]
5
6 \DeclareDocumentEnvironment{xltabular}{o m m}
7 {\longtable{#3}}
8 {\endlongtable}

```

File 570 **lwarp-xltxtra.sty**

§ 679 Package **xltxtra**

(Emulates or patches code by WILL ROBERTSON, JONATHAN KEW.)

Pkg xltxtra

xltxtra is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{xltxtra}[2016/01/21]
2 \RequirePackage{realscripts}
3 \RequirePackage{metalogo}
4 \newcommand*\TeX@Logo@spacing[6]{}
5
6 \newcommand*\vfrac[2]{%
7 \textsuperscript{#1}/\textsubscript{#2}%
8 }
9
10 \newcommand\namedglyph[1]{%
11 \@tempcnta=\XeTeXglyphindex "#1"\relax
12 \ifnum\@tempcnta>0
13 \XeTeXglyph\@tempcnta
14 \else
15 \xxt@namedglyph@fallback{#1}%
16 \fi}
17
18 \newcommand\xxt@namedglyph@fallback[1][{#1}]
19
20 \DeclareDocumentCommand{\showhyphens}{m}{}

```

File 571 **lwarp-xmpincl.sty**

§ 680 Package **xmpincl**

(Emulates or patches code by MAARTEN SNEEP.)

Pkg xmpincl

xmpincl is ignored.

for HTML output: Discard all options for lwarp-xmpincl:

```

1 \LWR@ProvidesPackageDrop{xmpincl}[2008/05/10]
2 \newcommand*\includexp[1]{}

```

File 572 **lwarp-xpiano.sty**

§ 681 Package **xpiano**

(Emulates or patches code by ENRICO GREGORIO.)

Pkg xpiano

xpiano is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{xpiano}

2 \ExplSyntaxOn
3 \NewDocumentCommand{\LWR@print@keyboard}{ O{}m }
4 {
5   \xpiano_keyboard:nn { #1 } { #2 }
6 }
7
8 \NewDocumentCommand{\LWR@HTML@keyboard}{ O{}m }
9 {
10 \begin{lateximage}*
11   [%
12     -xpiano-~\PackageDiagramAltText{}: \detokenize\expandafter{#2}%
13   ]
14   [\detokenize\expandafter{#1}]
15 \xpiano_keyboard:nn { #1 } { #2 }
16 \end{lateximage}
17 }
18 \ExplSyntaxOff
19
20 \LWR@formatted{keyboard}

```

File 573 **lwarp-xpinyin.sty**§ 682 Package **xpinyin***(Emulates or patches code by SOBEN LEE.)*

Pkg xpinyin

xpinyin is supported.

Pinyin is disabled for file names, the sideroc, and regular footnotes, but is left enabled for minipage footnotes, as per the print mode.

for HTML output: 1 \LWR@ProvidesPackagePass{xpinyin}[2019-04-07]

The original's boxes are not used, instead the contents are used with `<ruby>`, `<rt>`, and `<rp>` tags per modern HTML. Color is detected. `ratio` is ignored for *pdftotext* to work correctly. Extra spaces are placed inside the tags to allow line breaks in the HTML text.

```

2 \ExplSyntaxOn
3 \cs_new_protected_nopar:Npn \LWR@HTML@__xpinyin_make_pinyin_box:nnn #1#2#3
4 {
5   \color_group_begin: \color_ensure_current:
6   \l__xpinyin_pinyin_box_hook_tl
7   \renewcommand*{\l__xpinyin_ratio_tl}{1}% for pdftotext
8   \__xpinyin_select_font:
9   \clist_if_exist:cTF { c__xpinyin_multiple_ #1 _clist }
10    { \l__xpinyin_multiple_tl \l__xpinyin_format_tl }
11    { \l__xpinyin_format_tl }
12   \ifdefempty{\l__xpinyin_format_tl}
13     {#3}
14     {\LWR@textcurrentcolor{#3}}
15   \color_group_end:

```

```

16 }
17 \LWR@formatted{__xpinyin_make_pinyin_box:nnn}

18 \cs_new_protected_nopar:Npn \LWR@HTML@__xpinyin_CJKsymbol:nn #1#2
19 {
20   \__xpinyin_leavevmode:
21   \LWR@htmltagc{ruby}
22   \__xpinyin_save_CJKsymbol:n {#2}\null% \null removes extra space
23   \LWR@htmltagc{rp}\LWR@htmltagc{/rp\space}
24   \LWR@htmltagc{rt}
25   \__xpinyin_make_pinyin_box:nnn {#1} {#2} { \use:c { c__xpinyin_ #1 _tl } }
26   \LWR@htmltagc{/rt\space}
27   \LWR@htmltagc{rp})\LWR@htmltagc{/rp\space}
28   \LWR@htmltagc{/ruby\space}\null
29 }
30 \LWR@formatted{__xpinyin_CJKsymbol:nn}

31 \cs_new_protected_nopar:Npn \LWR@HTML@__xpinyin_single_CJKsymbol:nn #1#2
32 {
33   \__xpinyin_leavevmode:
34   \LWR@htmltagc{ruby}
35   \__xpinyin_save_CJKsymbol:n {#1}\null% \null removes extra space
36   \LWR@htmltagc{rp}\LWR@htmltagc{/rp\space}
37   \LWR@htmltagc{rt}
38   \__xpinyin_make_pinyin_box:xnn
39   { \__xpinyin_to_unicode:n {#1} } {#1} { \__xpinyin_pinyin:n {#2} }
40   \LWR@htmltagc{/rt\space}
41   \LWR@htmltagc{rp})\LWR@htmltagc{/rp\space}
42   \LWR@htmltagc{/ruby\space}\null
43 }
44 \LWR@formatted{__xpinyin_single_CJKsymbol:nn}
45
46 \ExplSyntaxOff

```

The `lwarp` core uses the following to disable CJK xpinyin for filenames, sideroc, and footnotes.

```

47 \renewcommand*{\LWR@disablepinyin}{\disablepinyin}
48
49 \FilenameNullify{\LWR@disablepinyin}

```

File 574 **lwarp-xr.sty**

§ 683 Package **Xr**

(Emulates or patches code by JEAN-PIERRE DRUCBERT, DAVID CARLISLE.)

Pkg xr

`xr` is patched for use by `lwarp`. The `*_html.aux` file is used. `\externaldocument` is modified to also accept the optional arguments for `xr-hyper`, which currently uses `xr` for HTML output.

See section 5.17.

for HTML output: 1 \LWR@ProvidesPackagePass{xr}[2019/07/22]%

```

2 \LetLtxMacro\LWR@orig@externaldocument\externaldocument
3
4 \RenewDocumentCommand{\externaldocument}{O{} O{} m O{}}{%
5   \ifblank{#1}{%
6     \LWR@orig@externaldocument{#3_html}%
7   }{%
8     \LWR@orig@externaldocument[#1]{#3_html}%
9   }%
10 }

```

File 575 **lwarp-xr-hyper.sty**

§ 684 Package **xr-hyper**

(Emulates or patches code by DAVID CARLISLE.)

Pkg xr-hyper

xr-hyper is replaced by xr, which is modified to accept the optional arguments for \externaldocument. So far, no hyperlinks are provided for citations.

See section 5.17.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{xr-hyper}[2019/10/03]%
2
3 \LWR@origRequirePackage{lwarp-xr}

```

File 576 **lwarp-xtab.sty**

§ 685 Package **xtab**

(Emulates or patches code by PETER WILSON.)

Pkg xtab

xtab is emulated.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{xtab}[2011/07/31]

```

 **Misplaced alignment tab character &** For \tablefirsthead, etc., enclose them as follows:

```

\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars

```

See section 8.10.1.

 **lateximage** supertabular and xtab are not supported inside a lateximage.

```

2 \newcommand{\LWRXT@firsthead}{}
3
4 \newcommand{\tablefirsthead}[1]{%
5   \long\gdef\LWRXT@firsthead{#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}
9
10 \newcommand{\tablelasthead}[1]{}

```

```
11
12 \newcommand{\notablelasthead}{}
13
14 \newcommand{\tabletail}[1]{}
15
16 \newcommand{\LWRXT@lasttail}{}
17
18 \newcommand{\tablelasttail}[1]{%
19     \long\gdef\LWRXT@lasttail{#1}%
20 }

21 \newcommand{\tablecaption}[2][1]{%
22     \long\gdef\LWRXT@caption{%
23         \ifblank{#1}%
24             {\caption{#2}}%
25             {\caption[#1]{#2}}%
26     }%
27 }
28
29 \let\topcaption\tablecaption
30 \let\bottomcaption\tablecaption

31 \newcommand*{\LWRXT@caption}{}
32
33 \newcommand*{\shrinkheight}[1]{}
34
35 \newcommand*{\xentrystretch}[1]{}
36
37 \NewDocumentEnvironment{xtabular}{s o m}
38 {%
39 \LWR@traceinfo{xtabular}%
40 \table%
41 \LWRXT@caption%
42 \begin{tabular}{#3}%
43 \TabularMacro\ifdefvoid{\LWRXT@firsthead}%
44 {\LWR@getmynexttoken}%
45 {\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
46 }%
47 {%
48 \ifdefvoid{\LWRXT@lasttail}%
49 }%
50 {%
51 \TabularMacro\ResumeTabular%
52 \LWRXT@lasttail%
53 }%
54 \end{tabular}%
55 \endtable%

56 \gdef\LWRXT@caption{}%

57 \LWR@traceinfo{xtabular done}%
58 }
59
60 \NewDocumentEnvironment{mpxtabular}{s o m}
61 {\minipage{\linewidth}\xtabular{#3}}
62 {\endxtabular\endminipage}
```

File 577 **lwarp-xunicode.sty**

§ 686 Package **xunicode**

Pkg xunicode

Error if xunicode is loaded after lwarp.

Patch lwarp-xunicode, but also verify that it was loaded before lwarp:

for HTML output:

```
1 \LWR@loadbefore{xunicode}%
2
3 \LWR@ProvidesPackagePass{xunicode}[2011/09/09]
```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with `textcomp`.

```
4 \providecommand*\LWR@HTML@textcircled[1]{%
5   \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
6 }
7
8 \LWR@formatted{textcircled}
```

Nullify xunicode macros when generating filenames:

```
9 \FilenameNullify{%
10   \renewcommand*\textdegree{}%
11   \renewcommand*\textcelsius{}%
12   \renewcommand*\textohm{}%
13   \renewcommand*\textmu{}%
14   \renewcommand*\textlquill{}%
15   \renewcommand*\textrquill{}%
16   \renewcommand*\textcircledP{}%
17   \renewcommand*\texttwelveudash{}%
18   \renewcommand*\textthreequartersemdash{}%
19   \renewcommand*\textmho{}%
20   \renewcommand*\textnaira{}%
21   \renewcommand*\textpeso{}%
22   \renewcommand*\textrecipe{}%
23   \renewcommand*\textinterrobang{}%
24   \renewcommand*\textinterrobangdown{}%
25   \renewcommand*\textperthousand{}%
26   \renewcommand*\textpertenthousand{}%
27   \renewcommand*\textbaht{}%
28   \renewcommand*\textdiscount{}%
29   \renewcommand*\textservicemark{}%
30   \renewcommand*\textcircled[1]{#1}%
31   \renewcommand*\capitalcedilla[1]{#1}%
32   \renewcommand*\capitalogonek[1]{#1}%
33   \renewcommand*\capitalgrave[1]{#1}%
34   \renewcommand*\capitalacute[1]{#1}%
35   \renewcommand*\capitalcircumflex[1]{#1}%
36   \renewcommand*\capitaltilde[1]{#1}%
37   \renewcommand*\capitaldieresis[1]{#1}%
38   \renewcommand*\capitalhungarumlaut[1]{#1}%
39   \renewcommand*\capitalring[1]{#1}%
40   \renewcommand*\capitalcaron[1]{#1}%
```

```

41 \renewcommand*{\capitalbreve}[1]{#1}%
42 \renewcommand*{\capitalmacron}[1]{#1}%
43 \renewcommand*{\capitaldotaccent}[1]{#1}%
44 }% FilenameNullify

```

File 578 **lwarp-xurl.sty**

§ 687 Package **xurl**

Pkg xurl xurl is ignored.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{xurl}[2020/01/14]
2
3 \def\useOriginalUrlSetting{}

```

File 579 **lwarp-xy.sty**

§ 688 Package **xy**

(Emulates or patches code by KRISTOFFER H. ROSE, ROSS MOORE.)

Pkg xy xy is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{xy}[2013/10/06]

```

After xy modules have been loaded:

```

2 \AtBeginDocument{

```

The original definitions without a lateximage:

```

3 \LetLtxMacro\LWR@orig@xy\xy
4 \LetLtxMacro\LWR@orig@endxy\endxy

```

The outer-most xy environment is placed in a lateximage, but not more than one level deep, which would conflict with xy:

```

5 \renewcommand*{\xy}{%
6   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
7     {\addtocounter{LWR@lateximagedepth}{1}}%
8     {\begin{lateximage}[-xy~\PackageDiagramAltText]}%
9     \LWR@orig@xy%
10 }
11
12 \renewcommand*{\endxy}{%
13   \LWR@orig@endxy%
14   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
15     {\addtocounter{LWR@lateximagedepth}{-1}}%
16     {\end{lateximage}}%
17 }

```

The `\xybox` must use the original definitions of `\xy`, `\endxy`:

```

18 \def\xybox#1{%
19   \LWR@orig@xy#1\LWR@orig@endxy%
20   \Edge@c={\rectangleEdge}\computeLeftUpness@%
21 }

```

If `\xygraph` is used, it is placed inside a `lateximage`:

```

22 \@ifundefined{xygraph}{}{
23
24 \LetLtxMacro\LWR@origxygraph\xygraph
25
26 \renewcommand{\xygraph}[1]{%
27   \begin{lateximage}[-xy- xygraph \PackageDiagramAltText]
28   \LWR@origxygraph{#1}
29   \end{lateximage}
30 }
31
32 }% xygraph defined
33
34 }% AtBeginDocument

```

File 580 **lwarp-zhlineskip.sty**

§ 689 Package **zhlineskip**

Pkg zhlineskip

zhlineskip is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{zhlineskip}[2019/05/15]

```

2 \newcommand*\SetTextEnvironmentSinglespace[1]{}
3 \newcommand*\RestoreTextEnvironmentLeading[1]{}
4 \newcommand*\SetMathEnvironmentSinglespace[1]{}
5 \newcommand*\RestoreMathEnvironmentLeading[1]{}

```

File 581 **lwarp-zwpageLayout.sty**

§ 690 Package **zwpageLayout**

(Emulates or patches code by ZDENĚK WAGNER.)

Pkg zwpageLayout

zwpageLayout is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{zwpageLayout}[2013/01/13]

```

2 \def\noBboxes{}
3 \@onlypreamble\noBboxes
4
5 \expandafter\ifx\csname definecolor\endcsname\relax \else
6   \definecolor{cmykblack}{cmyk}{0,0,0,1}
7   \definecolor{grblack}{gray}{0}
8 %   \ifzwpL@redefineblack
9 %     \definecolor{black}{cmyk}{0,0,0,1}\color{black}
10 %   \fi
11   \definecolor{cmykred}{cmyk}{0,1,1,0}

```

```

12 \definecolor{cmykgreen}{cmyk}{1,0,1,0}
13 \definecolor{cmykblue}{cmyk}{1,1,0,0}
14 \definecolor{rgbred}{rgb}{1,0,0}
15 \definecolor{rgbgreen}{rgb}{0,1,0}
16 \definecolor{rgbbblue}{rgb}{0,0,1}
17% \ifzwpl@redefinetcmyk
18% \definecolor{red}{cmyk}{0,1,1,0}
19% \definecolor{green}{cmyk}{1,0,1,0}
20% \definecolor{blue}{cmyk}{1,1,0,0}
21% \fi
22 \fi
23
24 \let\OverprintXeTeXExtGState\relax
25
26 \DeclareRobustCommand\SetOverprint{\ignorespaces}
27 \DeclareRobustCommand\SetKnockout{\ignorespaces}
28 \DeclareRobustCommand\textoverprint[1]{\SetOverprint#1}
29 \DeclareRobustCommand\textknockout[1]{\SetKnockout#1}
30
31 \def\SetPDFminorversion#1{
32 \@onlypreamble\SetPDFminorversion
33
34 \newcommand*\Vcorr{
35
36 \DeclareRobustCommand\vb[1][{}]{
37 \NewDocumentCommand{\NewOddPage}{* o}{
38 \NewDocumentCommand{\NewEvenPage}{* o}{
39 \def\SetOddPageMessage#\gdef\ZW@oddwarning}
40 \def\SetEvenPageMessage#\gdef\Z@evenwarning}
41 \def\ZW@oddwarning{Empty page inserted}\let\ZW@evenwarning\ZW@oddwarning
42
43 \def\clap#1{#1}
44
45 \def\CropFlap{2in}
46 \def\CropSpine{1in}
47 \def\CropXSpine{1in}
48 \def\CropXtrim{.25in}
49 \def\CropYtrim{.25in}
50 \def\UserWidth{5in}
51 \def\UserLeftMargin{1in}
52 \def\UserRightMargin{1in}
53 \def\UserTopMargin{1in}
54 \def\UserBotMargin{1in}
55 \def\thePageNumber{\LWR@origpound\,\arabic{page}}
56 \ifXeTeX
57 \def\ifcaseZWdriver{\ifcase2}
58 \else
59 \def\ifcaseZWdriver{\ifcase1}
60 \fi
61 \DeclareRobustCommand\ZWifdriver[2]{

```

File 582 **lwarp-patch-komascript.sty**

§ 691 Package **patch-komascript**

Pkg lwarp-patch-komascript Patches for komascript classes.

lwarp loads this package when scrbook, scartcl, or screprt classes are detected.

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

`\captionformat`, `\figureformat`, and `\tableformat` are not yet emulated.

 **Not fully tested!** [Please send bug reports!](#)

Some features have not yet been tested. Please contact the author with any bug reports.

for HTML output: 1 `\ProvidesPackage{lwarp-patch-komascript}`

`typearea` is emulated.

2 `\RequirePackage{lwarp-typearea}`

`tocbasic` is emulated.

3 `\RequirePackage{lwarp-tocbasic}`

`scrextend` patches most of the new macros.

4 `\RequirePackage{lwarp-scrextend}`

Indexing macros, simplified for `lwarp`:

```

5 \AtBeginDocument{
6
7 \renewcommand*{\idx@heading}{%
8   \idx@@heading{\indexname}%
9 }
10
11 \renewenvironment{theindex}{%
12   \idx@heading%
13   \index@preamble\par\nobreak
14   \LetLtxMacro\item\LWR@indexitem%
15   \LetLtxMacro\subitem\LWR@indexsubitem%
16   \LetLtxMacro\subsubitem\LWR@indexsubsubitem%
17 }
18 {}
19
20 \renewcommand*\indexspace{}
21
22 }% AtBeginDocument

```

The `\minisec` is placed inside a `<div>` of class `minisec`.

```

23 \renewcommand*{\minisec}[1]{
24   \begin{BlockClass}{minisec}
25     #1
26   \end{BlockClass}
27 }

```

The part and chapter preambles are placed as plain text just after each heading.

```

28 \@ifundefined{setpartpreamble}{}{
29 \RenewDocumentCommand{\setpartpreamble}{o o +m}{%
30   \renewcommand{\part@preamble}{#3}%

```

```

31 }
32 }
33
34 \@ifundefined{setchapterpreamble}{}{
35 \RenewDocumentCommand{\setchapterpreamble}{o o +m}{%
36   \renewcommand{\chapter@preamble}{#3}%
37 }
38 }

```

Do not use `\chaptername`:

```
39 \renewcommand*{\LWR@printchaptername}{}{}
```

Simple captions are used in all cases.

```

40 \AtBeginDocument{
41 \AtBeginDocument{
42   \LetLtxMacro\captionbelow\caption
43   \LetLtxMacro\captionabove\caption
44
45   \LetLtxMacro\captionofbelow\captionof
46   \LetLtxMacro\captionofabove\captionof
47 }
48 }
49
50 \RenewDocumentEnvironment{captionbeside}{o m o o o s}
51 {}
52 {%
53   \IfValueTF{#1}%
54     {\caption[#1]{#2}}%
55     {\caption{#2}}%
56 }
57
58 \RenewDocumentEnvironment{captionofbeside}{m o m o o o s}
59 {}
60 {%
61   \IfValueTF{#2}%
62     {\captionof{#1}[#2]{#3}}%
63     {\captionof{#1}{#3}}%
64 }
65
66 \RenewDocumentCommand{\setcapindent}{s m}{}
67 \renewcommand*{\setcaphanging}{}
68 \renewcommand*{\setcapwidth}[2][{}]{
69 \renewcommand*{\setcapdynwidth}[2][{}]{
70 \RenewDocumentCommand{\setcapmargin}{s o m}{}

```

File 583 **lwarp-patch-memoir.sty**

§ 692 Package **patch-memoir**

(Emulates or patches code by PETER WILSON.)

Pkg lwarp-patch-memoir Patches for memoir class.

 **Not fully tested!** [Please send bug reports!](#)

lwarp loads this package when the memoir class is detected.

- ⚠ **captions** lwarp uses `caption`, which causes a warning from memoir. This is normal. Adjust captions via `caption`, instead of memoir.

While emulating memoir, lwarp pre-loads a number of packages (section 692.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

- ⚠ **options clash**

```
\documentclass{memoir}
...
\PassOptionsToPackage{options_list}{package_name}
...
\usepackage{lwarp}
...
\usepackage{package_name}
```

- ⚠ **version numbers**

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

`\label(bookmark){tag}` `\label` accepts an optional (bookmark) argument, but this is ignored in HTML.

- ⚠ **comment** The `comment` environment is from the `comment` package, and thus requires that the `\begin` and `\end` each be on its own line:

```
\begin{comment}
This is a comment.
\end{comment}
```

`\newcomment` Comments defined with `\newcomment` use memoir's definitions, and behave as expected, where the `\begin` and `\end` do have to each be on its own line.

- ⚠ **verbatim footnotes** `\verbfootnote` is not supported.

- ⚠ **\newfootnoteseries** `\newfootnoteseries`, etc. are not supported.

- ⚠ **page notes** lwarp loads `pagenote` to perform memoir's pagenote functions, but there are minor differences in `\pagenotesubhead` and related macros.

page notes with cleveref To add support for pagenotes with `cleveref`, add:

```
\crefname{pagenote}{page note}{page notes}
\Crefname{pagenote}{Page note}{Page notes}
```

page note \nameref Note that for print mode, `\nameref` print the section name where the page notes are declared in the text, but for HTML it prints the name where the page notes are printed.

- ⚠ **poems** Poem numbering is not supported.

- ⚠ **verbatim** The `verbatim` environment does not yet support the memoir enhancements. It is currently recommended to load and use `fancyvrb` instead.

- ⚠ **glossaries** The memoir glossary system is not yet supported by `lwarpmk`. The `glossaries` pack-

age may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

for HTML output: 1 \ProvidesPackage{lwarp-patch-memoir}

§ 692.1 Packages

These are pre-loaded to provide emulation for many of memoir's functions. memoir pretends that abstract, etc. are already loaded, via its "emulated" package mechanism, but lwarp is directly loading the "lwarp-" version of each, which happens to avoid memoir's emulation system.

```

2 \RequirePackage{lwarp-abstract}% req'd
3 % \RequirePackage{lwarp-array}% no longer req'd
4 \RequirePackage{lwarp-booktabs}% req'd
5 % \RequirePackage{lwarp-ccaption}% emulated below
6 \RequirePackage{lwarp-changepage}% req'd
7 \RequirePackage{lwarp-crop}
8 % \RequirePackage{lwarp-dcolumn}% no longer req'd
9 \RequirePackage{lwarp-enumerate}% req'd
10 \RequirePackage{lwarp-epigraph}% req'd
11 \RequirePackage{lwarp-fancyvrb}% req'd
12 \RequirePackage{lwarp-footmisc}% req'd

13 \let\framed\relax \let\endframed\relax
14 \let\shaded\relax \let\endshaded\relax
15 \let\leftbar\relax \let\endleftbar\relax
16 \let\snugshade\relax \let\endsnugshade\relax
17 \RequirePackage{lwarp-framed}% req'd
18
19 \RequirePackage{lwarp-hanging}% req'd
20 \RequirePackage{lwarp-makeidx}% req'd
21 \DisemulatePackage{moreverb}
22 \RequirePackage{lwarp-moreverb}
23 \RequirePackage{lwarp-mparhack}
24 \RequirePackage{lwarp-needspace}% req'd
25 \RequirePackage{lwarp-nextpage}% req'd
26 \RequirePackage{lwarp-pagenote}% req'd
27 \RequirePackage{lwarp-parskip}
28 \RequirePackage{lwarp-setspace}% req'd
29 \RequirePackage{lwarp-showidx}

30 \makeindex

31 % \RequirePackage{lwarp-tabularx}% no longer req'd
32 \RequirePackage{lwarp-titling}% req'd
33 % \RequirePackage{lwarp-tocbibind}% not emulated by memoir
34 \RequirePackage{lwarp-tocloft}% req'd
35 \RequirePackage{lwarp-verse}% req'd

```

§ 692.2 Label handling

Insert the `lwarp` label mechanism into the memoir package mechanism:

- `\@mem@old@label` is the L^AT_EX definition of `\label`.
- `\LWR@orig@label` becomes the memoir definition.
- `lwarp`'s `\LWR@new@label` uses `\LWR@orig@label`.
- Want memoir's `\label` to use `lwarp`'s `\label`, which then would use L^AT_EX's `\label`.
- So:
 - `\@mem@old@label` is set to `\LWR@new@label`.
 - `\LWR@orig@label` is set to `\@mem@old@label`.
- `cleveref` then encapsulates all the above with `\cref@old@label`.
- For a subcaption, `cleveref` modifies memoir's `\sf@memsub@label`, but that change is undone by `lwarp`.

```
36 \LetLtxMacro\LWR@orig@label\@mem@old@label
37 \LetLtxMacro\@mem@old@label\LWR@new@label
```

Patches for subfloats to support additional `lwarp` labels. This is the non-hyperref version from memoir.

```
38 \AtBeginDocument{
39   \renewcommand*{\sf@memsub@label}[1]{%
40     \@bsphack
41     \sf@memsub@label@hook{#1}%
42 %     \@memoldlabel{#1}%
43     \cref@label{#1}%           lwarp
44     \LWR@label@createtag{sub@#1}%       lwarp
45     \protected@write\@auxout{}{%
46       \string\newlabel{sub@#1}%
47       {\@nameuse{@@thesub\@capttype}}%
48       {\thepage}}}%
49     \LWR@write@lwarplabel{sub@#1}%       lwarp
50     \@esphack
51   }
52 }
```

§ 692.3 Page layout

memoir already set the page size to a default, so it must be forced large for `lwarp`'s use, to avoid tag overflows off the page.

```
53 \setstocksize{190in}{20in}
54 \setlrmarginsandblock{2in}{2in}{*}
55 \setulmarginsandblock{1in}{1in}{*}

56 \renewcommand*{\stockavi}{}
57 \renewcommand*{\stockav}{}
58 \renewcommand*{\stockaiv}{}
59 \renewcommand*{\stockaiii}{}

```

```
60 \renewcommand*\stockavii{}
61 \renewcommand*\stockbvi{}
62 \renewcommand*\stockbv{}
63 \renewcommand*\stockbiv{}
64 \renewcommand*\stockbiii{}
65 \renewcommand*\stockbvii{}
66 % \renewcommand*\stockmetriccrownvo{}% in docs but not in the package
67 \renewcommand*\stockmlargecrownvo{}
68 \renewcommand*\stockmdemyvo{}
69 \renewcommand*\stocksmallroyalvo{}
70 \renewcommand*\pageavi{}
71 \renewcommand*\pageavii{}
72 \renewcommand*\pageav{}
73 \renewcommand*\pageaiv{}
74 \renewcommand*\pageaiii{}
75 \renewcommand*\pagebvi{}
76 \renewcommand*\pagebvii{}
77 \renewcommand*\pagebv{}
78 \renewcommand*\pagebiv{}
79 \renewcommand*\pagebiii{}
80 % \renewcommand*\pagemetriccrownvo{}% in docs but not in the package
81 \renewcommand*\pagemlargecrownvo{}
82 \renewcommand*\pagemdemyvo{}
83 \renewcommand*\pagemsmallroyalvo{}
84
85 \renewcommand*\stockdbill{}
86 \renewcommand*\stockstatement{}
87 \renewcommand*\stockexecutive{}
88 \renewcommand*\stockletter{}
89 \renewcommand*\stockold{}
90 \renewcommand*\stocklegal{}
91 \renewcommand*\stockledger{}
92 \renewcommand*\stockbroadsheet{}
93 \renewcommand*\pagedbill{}
94 \renewcommand*\pagestatement{}
95 \renewcommand*\pageexecutive{}
96 \renewcommand*\pageletter{}
97 \renewcommand*\pageold{}
98 \renewcommand*\pagelegal{}
99 \renewcommand*\pageledger{}
100 \renewcommand*\pagebroadsheet{}
101
102 \renewcommand*\stockpottvo{}
103 \renewcommand*\stockfoolscapvo{}
104 \renewcommand*\stockcrownvo{}
105 \renewcommand*\stockpostvo{}
106 \renewcommand*\stocklargecrownvo{}
107 \renewcommand*\stocklargepostvo{}
108 \renewcommand*\stocksmalldemyvo{}
109 \renewcommand*\stockdemyvo{}
110 \renewcommand*\stockmediumvo{}
111 \renewcommand*\stocksmallroyalvo{}
112 \renewcommand*\stockroyalvo{}
113 \renewcommand*\stocksuperroyalvo{}
114 \renewcommand*\stockimperialvo{}
115 \renewcommand*\pagepottvo{}
116 \renewcommand*\pagefoolscapvo{}
117 \renewcommand*\pagecrownvo{}
118 \renewcommand*\pagepostvo{}
119 \renewcommand*\pagelargecrownvo{}

```

```
120 \renewcommand*{\pagelargepostvo}{}
121 \renewcommand*{\pagesmalldemyvo}{}
122 \renewcommand*{\pagedemyvo}{}
123 \renewcommand*{\pagemediumvo}{}
124 \renewcommand*{\pagesmallroyalvo}{}
125 \renewcommand*{\pageroyalvo}{}
126 \renewcommand*{\pagesuperroyalvo}{}
127 \renewcommand*{\pageimperialvo}{}
128
129 \renewcommand*{\memfontfamily}{}
130 \renewcommand*{\memfontenc}{}
131 \renewcommand*{\memfontpack}{}
132
133 \renewcommand*{\anyptfilebase}{}
134 \renewcommand*{\anyptsizesize}{10}
135
136 \renewcommand*{\setstocksize}[2]{}
137 \renewcommand*{\settrimmedsize}[3]{}
138 \renewcommand*{\settrims}[2]{}
139
140 % \newlength{\lxvchars}
141 % \setlength{\lxvchars}{305pt}
142 % \newlength{\xlvchars}
143 % \setlength{\xlvchars}{190pt}
144 \renewcommand*{\setxlvchars}[1]{}
145 \renewcommand*{\setlxvchars}[1]{}
146
147 \renewcommand*{\settypeblocksize}[3]{}
148 \renewcommand*{\setlrmargins}[3]{}
149 \renewcommand*{\setlrmarginsandblock}[3]{}
150 \renewcommand*{\setbinding}[1]{}
151 \renewcommand*{\setulmargins}[3]{}
152 \renewcommand*{\setulmarginsandblock}[3]{}
153 \renewcommand*{\setcolsepandrul}[2]{}
154
155 \renewcommand*{\setheadfoot}[2]{}
156 \renewcommand*{\setheaderspaces}[3]{}
157 \renewcommand*{\setmarginnotes}[3]{}
158 \renewcommand*{\setfootins}[2]{}
159 \renewcommand*{\checkandfixthelayout}[1][1]{}
160 \renewcommand*{\checkthelayout}[1]{}
161 \renewcommand*{\fixthelayout}{}
162 %
163 % \newlength{\stockheight}
164 % \newlength{\trimtop}
165 % \newlength{\trimedge}
166 % \newlength{\stockwidth}
167 % \newlength{\spinmargin}
168 % \newlength{\foremargin}
169 % \newlength{\uppermargin}
170 % \newlength{\headmargin}
171 %
172 \renewcommand*{\typeoutlayout}{}
173 \renewcommand*{\typeoutstandardlayout}{}
174 \renewcommand*{\settypeoutlayoutunit}[1]{}
175 \renewcommand*{\fixpdflayout}{}
176 \renewcommand*{\fixdvipslayout}{}
177
178 \renewcommand*{\medievalpage}[1][1]{}
179 \renewcommand*{\isopage}[1][1]{}

```

```

180 \renewcommand*\semiisopage}[1]{}
181
182 \renewcommand{\setpagebl}[3]{}
183 \renewcommand{\setpageml}[3]{}
184 \renewcommand{\setpagetl}[3]{}
185 \renewcommand{\setpagetm}[3]{}
186 \renewcommand{\setpagetr}[3]{}
187 \renewcommand{\setpagemr}[3]{}
188 \renewcommand{\setpagebr}[3]{}
189 \renewcommand{\setpagebm}[3]{}
190 \renewcommand{\setpagecc}[3]{}

```

§ 692.4 Text and fonts

```

191 \let\miniscule\tiny
192 \let\HUGE\Huge
193
194 \renewcommand*\abnormalparskip}[1]{}
195 \renewcommand*\nonzeroparskip{}
196 \renewcommand*\traditionalparskip{}
197
198 \let\onelineskip\baselineskip
199
200 \let\OnehalfSpacing\onehalfspacing
201 \let\DoubleSpacing\doublespacing
202 \renewcommand*\setPagenoteSpacing}[1]{}
203 \renewcommand*\setFloatSpacing}[1]{}

204 \renewcommand{\SingleSpacing}{\@ifstar\singlespacing\singlespacing}

205 \let\setSingleSpace\SetSinglespace
206 \let\SingleSpace\singlespace
207 \let\endSingleSpace\endsinglespace
208 \let\Spacing\spacing
209 \let\endSpacing\endspacing
210 \let\OnehalfSpace\onehalfspace
211 \let\endOnehalfSpace\endonehalfspace
212 \csletcs{OnehalfSpace*}{onehalfspace}
213 \csletcs{endOnehalfSpace*}{endonehalfspace}
214 \let\DoubleSpace\doublespace
215 \let\endDoubleSpace\enddoublespace
216 \csletcs{DoubleSpace*}{doublespace}
217 \csletcs{endDoubleSpace*}{enddoublespace}
218 \renewcommand*\setDisplayskipStretch}[1]{}
219 \renewcommand*\memdskipstretch{}
220 \renewcommand*\noDisplayskipStretch{}
221 \renewcommand*\memdskips{}
222
223 \renewcommand*\midsloppy{}
224 \renewenvironment*{midsloppypar}{}{}
225
226 \renewcommand*\sloppybottom{}

```

§ 692.5 Titles

```

227 \csletcs{titlingpage*}{titlingpage}
228 \csletcs{endtitlingpage*}{endtitlingpage}
229 \let\titlingpageend\relax
230 \newcommand{\titlingpageend}[2]{}
231 \let\andnext\and

```

```

232 \renewcommand*{\thanksmarkstyle}[1]{}
233
234 \renewcommand{\thanksfootmark}{%
235   \thanksscript{\tamark}%
236 }
237
238 % \newlength{\thanksmarksep}% already provided by memoir

239 \renewcommand\titlingpageend[2]{}

```

§ 692.6 Abstracts

```

240 % \newlength{\absindent}
241 % \newlength{\absparsep}
242 \renewcommand*{\abstractcol}{}
243 \renewcommand*{\abstractintoc}{}
244 \renewcommand*{\abstractnum}{}
245 \renewcommand*{\abstractrunin}{}

```

§ 692.7 Document divisions

\book

```
* (<{2:PDF name}>) [<{3:TOC name}>] [<{4:PDF name}>] (<{5:PDF name}>) {<{6:name}>}
```

```

246 \DeclareDocumentCommand{\book}{s d() o o d() m}{%
247   \LWR@section{#1}{#3}{#6}{book}%
248 }

249 \def\@apppage{%
250   \part*{\appendixpagename}
251 }
252 \renewcommand\mempreaddapppagetotochook{}
253 \renewcommand\mempostaddapppagetotochook{}
254
255 \def\@sapppage{%
256   \part*{\appendixpagename}
257 }

258 \DeclareDocumentCommand{\mainmatter}{s}{%
259   \booltrue{LWR@mainmatter}%
260 }
261
262 \DeclareDocumentCommand{\frontmatter}{s}{%
263   \boolfalse{LWR@mainmatter}%
264 }

265 \renewcommand*{\raggedbottomsection}{}
266 \renewcommand*{\normalbottomsection}{}
267 \renewcommand*{\bottomsectionskip}{}
268 \renewcommand*{\bottomsectionpenalty}{}
269 \csletcs{appendixpage*}{appendixpage}
270 \renewcommand*{\namedsubappendices}{}
271 \renewcommand*{\unnamedsubappendices}{}
272 \renewcommand*{\beforebookskip}{}
273 \renewcommand*{\afterbookskip}{}
274 \renewcommand*{\beforepartskip}{}
275 \renewcommand*{\afterpartskip}{}
276 \renewcommand*{\midbookskip}{}

```

```
277 \renewcommand*\midpartskip{}
278 \renewcommand*\printbookname{}
279 \renewcommand*\booknamefont{}
280 \renewcommand*\booknamenenum{}
281 \renewcommand*\printbooknum{}
282 \renewcommand*\booknumfont{}
283 \renewcommand*\printpartname{}
284 \renewcommand*\partnamefont{}
285 \renewcommand*\partnamenenum{}
286 \renewcommand*\printpartnum{}
287 \renewcommand*\partnumfont{}
288 \renewcommand*\printbooktitle}[1]{}
289 \renewcommand*\booktitlefont{}
290 \renewcommand*\printparttitle}[1]{}
291 \renewcommand*\parttitlefont{}
292 \renewcommand*\bookpageend{}
293 \renewcommand*\bookblankpage{}
294 \renewcommand*\nobookblankpage{}
295 \renewcommand*\partpageend{}
296 \renewcommand*\partblankpage{}
297 \renewcommand*\nopartblankpage{}
298 \RenewDocumentCommand\newleadpage{s o m m}{}% todo
299 \RenewDocumentCommand\renewleadpage{s o m m}{}% todo
300 \renewcommand*\leadpagetoclevel}{chapter}
301
302 \renewcommand*\openright{}
303 \renewcommand*\openleft{}
304 \renewcommand*\openany{}
305 \renewcommand*\clearforchapter{}
306 \renewcommand*\memendofchapterhook{}
307 \renewcommand*\chapterheadstart{}
308 % \newlength\beforechapskip
309 \renewcommand*\afterchapterskip{}
310 % \newlength\midchapskip
311 \renewcommand*\afterchapterskip{}
312 % \newlength\afterchapskip
313 \renewcommand*\printchaptername{}
314 \renewcommand*\chapnamefont{}
315 \renewcommand*\chapternamenenum{}
316 \renewcommand*\printchapternum{}
317 \renewcommand*\chapnumfont{}
318 \renewcommand*\printchapterskip}[1]{}
319 \renewcommand*\chapterskipfont{}
320 \renewcommand*\printchapterskipnonum{}
321 \renewcommand*\indentafterchapter{}
322 \renewcommand*\noindentafterchapter{}
323 \renewcommand*\insertchapterspace{}
324
325 \renewcommand*\chapterstyle}[1]{}
326 \renewcommand*\makechapterstyle}[2]{}
327 \renewcommand*\chapindent{}
328 \let\chapterprecis\cftchapterprecis
329 \let\chapterprecishere\cftchapterprecishere
330 \let\chapterprecistoc\cftchapterprecistoc
331 \renewcommand*\precisfont{}
332 \renewcommand*\prechapterprecis{}
333 \renewcommand*\postchapterprecis{}
334 \renewcommand*\precistocfont}[1]{}
335 \renewcommand*\precistocfont{}
336 \renewcommand*\precistocformat{}

```

```

337% \newlength{\prechapterprecisshift}
338
339 \renewcommand*\setbeforesecskip}[1]{
340 \renewcommand*\setaftersecskip}[1]{
341 \renewcommand*\setsecindent}[1]{
342 \renewcommand*\setsecheadstyle}[1]{
343 \renewcommand*\setbeforesubsecskip}[1]{
344 \renewcommand*\setaftersubsecskip}[1]{
345 \renewcommand*\setsubsecindent}[1]{
346 \renewcommand*\setsubsecheadstyle}[1]{
347 \renewcommand*\setbeforesubsubsecskip}[1]{
348 \renewcommand*\setaftersubsubsecskip}[1]{
349 \renewcommand*\setsubsubsecindent}[1]{
350 \renewcommand*\setsubsubsecheadstyle}[1]{
351 \renewcommand*\setbeforeparaskip}[1]{
352 \renewcommand*\setafterparaskip}[1]{
353 \renewcommand*\setparaindent}[1]{
354 \renewcommand*\setparaheadstyle}[1]{
355 \renewcommand*\setbeforesubparaskip}[1]{
356 \renewcommand*\setaftersubparaskip}[1]{
357 \renewcommand*\setsubparaindent}[1]{
358 \renewcommand*\setsubparaheadstyle}[1]{
359 \renewcommand{\@hangfrom}[1]{#1}
360 \renewcommand{\sethangfrom}[1]{
361 \renewcommand{\setsecnumformat}[1]{
362
363 \renewcommand*\hangsecnum{}
364 \renewcommand*\defaultsecnum{}
365
366 \renewcommand*\sechook{}
367 \renewcommand{\setsechook}[1]{
368 \renewcommand*\subsechook{}
369 \renewcommand{\setsubsechook}[1]{
370 \renewcommand*\subsubsechook{}
371 \renewcommand{\setsubsubsechook}[1]{
372 \renewcommand*\parahook{}
373 \renewcommand{\setparahook}[1]{
374 \renewcommand*\subparahook{}
375 \renewcommand{\setsubparahook}[1]{
376
377 \RenewDocumentCommand{\plainbreak}{s m}{\begin{center}~\end{center}}
378
379 \RenewDocumentCommand{\fancybreak}{s +m}{%
380   \begin{center}#2\end{center}%
381 }
382
383 \RenewDocumentCommand{\plainfancybreak}{s m m +m}{%
384   \begin{center}#4\end{center}%
385 }
386
387 \RenewDocumentCommand{\pfbreak}{s}{%
388   \begin{center}
389     \pfbreakdisplay
390   \end{center}
391 }
392
393% \newlength{\pfbreakskip}
394 \renewcommand{\pfbreakdisplay}{*\quad*\quad*}
395
396 \renewcommand{\makeheadstyles}[2]{

```

397 \renewcommand*{\headstyles}[1]{}

§ 692.8 **Pagination and headers**

398 \renewcommand*{\savepagenumber}{}
 399 \renewcommand*{\restorepagenumber}{}
 400 \renewcommand*{\uppercaseheads}{}
 401 \renewcommand*{\nouppercaseheads}{}
 402
 403 \renewcommand*{\bookpagemark}[1]{}
 404 \renewcommand*{\partmark}[1]{}
 405 \renewcommand*{\bibmark}{}
 406 \renewcommand*{\indexmark}{}
 407 \renewcommand*{\glossarymark}{}
 408
 409 \LWR@origpagestyle{empty}
 410 \renewcommand*{\ps@empty}{}
 411 \renewcommand*{\makepagestyle}[1]{}
 412 \renewcommand*{\emptyshook}{}%
 413 % \renewcommand*{\empty@oddhead}{}
 414 % \renewcommand*{\empty@oddfoot}{}
 415 % \renewcommand*{\empty@evenhead}{}
 416 % \renewcommand*{\empty@evenfoot}{}
 417 \renewcommand*{\@oddhead}{}
 418 \renewcommand*{\@oddfoot}{}
 419 \renewcommand*{\@evenhead}{}
 420 \renewcommand*{\@evenfoot}{}
 421 \renewcommand*{\aliaspagestyle}[2]{}
 422 \renewcommand*{\copypagestyle}[2]{}
 423
 424 \renewcommand*{\makeevenhead}[4]{}
 425 \renewcommand*{\makeoddhead}[4]{}
 426 \renewcommand*{\makeevenfoot}[4]{}
 427 \renewcommand*{\makeoddfoot}[4]{}
 428 \renewcommand*{\makerunningwidth}[3]{}
 429 % \newlength{\headwidth}
 430 \renewcommand*{\makeheadrule}[3]{}
 431 \renewcommand*{\makefootrule}[3]{}
 432 \renewcommand*{\makeheadfootruleprefix}[3]{}
 433 % \newlength{\normalrulethickness}
 434 % \setlength{\normalrulethickness}{.4pt}
 435 % \newlength{\footruleheight}
 436 % \newlength{\footruleskip}
 437 \renewcommand*{\makeheadposition}[5]{}
 438 \renewcommand*{\makepsmarks}[2]{}
 439 \renewcommand*{\makeheadfootstrut}[3]{}

440 \renewcommand{\createmark}[5]{\csdef{#1mark}[1]{}}
 441 \renewcommand{\createplainmark}[3]{\csdef{#1mark}{}}

442 \renewcommand{\memUChad}[1]{}
 443 \renewcommand*{\clearplainmark}[1]{}
 444 \renewcommand*{\clearmark}[1]{}
 445 \renewcommand{\addtopsmarks}[3]{}
 446 \renewcommand{\ifonlyfloats}[2]{#2}
 447 \renewcommand*{\mergepagefloatstyle}[3]{}
 448
 449 \renewcommand*{\framepichead}{}
 450 \renewcommand*{\framepictextfoot}{}
 451 \renewcommand*{\framepichook}{}
 452

```
452 \renewcommand*\showheadfootlocoff{}
453 \renewcommand*\showtextblocklocoff{}
```

§ 692.9 Paragraphs and lists

```
454 \renewcommand{\hangfrom}[1]{#1}
455 \let\centerfloat\centering
456 \renewcommand*\raggedyright}[1]{}
457 % \newlength{\ragrparindent}
458 \renewcommand{\sourcetrigh}[2][\attribution{#2}]
459 \let\memorigdbs\LWR@endofline

460 \renewcommand*\memorigpar{\par}

461 \let\atcentercr\LWR@endofline
462
463 \renewcommand*\linenottooshort}[1]{}
464 \renewcommand*\russianpar{}
465 \renewcommand*\lastlinerulefill{}
466 \renewcommand*\lastlineparrule{}
467 \renewcommand*\justlastraggedleft{}
468 \renewcommand*\raggedrightthenleft{}
469 \renewcommand*\leftcenterright{}
470
471 \renewcommand{\leftspringright}[4]{%
472   \begin{minipage}{#1\linewidth}#3\end{minipage}\quad%
473   \begin{minipage}{#2\linewidth}\begin{flushright}#4\end{flushright}\end{minipage}%
474 }
475
476 \renewenvironment*{blockdescription}
477 {\LWR@descriptionstart\LWR@origdescription}
478 {\enddescription}
479
480 \renewcommand*\blockdescriptionlabel}[1]{\textbf{#1}}
481 \renewenvironment*{labelled}[1]{\begin{description}}{\end{description}}
482 \renewenvironment*{flexlabelled}[6]{\begin{description}}{\end{description}}
483 \renewcommand*\tightlists{}
484 \renewcommand*\defaultlists{}
485 \RenewDocumentCommand{\firmlists}{s}{}
486 \renewcommand*\firmelist{}
487 \renewcommand*\tightlist{}
488 \renewcommand*\zerotrivseps{}
489 \renewcommand*\savetrivseps{}
490 \renewcommand*\restoretrivseps{}
```

§ 692.10 Contents lists

```
491 \csletcs{tableofcontents*}{tableofcontents}
492 \csletcs{listoffigures*}{listoffigures}
493 \csletcs{listoftables*}{listoftables}
494 \renewenvironment{KeepFromToc}{}{}
495 \renewcommand*\onecoltocetc{}
496 \renewcommand*\twocoltocetc{}
497 \renewcommand*\ensureonecol{}
498 \renewcommand*\restorefromonecol{}
499 \renewcommand*\doccoltocetc{}
500
501 \renewcommand{\toheadstart}{}
502 \renewcommand{\printtoctitle}[1]{}
503 \renewcommand{\tocmark}{}

```

```

504 \renewcommand{\aftertoctitle}{}
505 \renewcommand{\lofheadstart}{}
506 \renewcommand{\printloftitle}[1]{}
507 \renewcommand{\lofmark}{}
508 \renewcommand{\afterloftitle}{}
509 \renewcommand{\lotheadstart}{}
510 \renewcommand{\printlottitle}[1]{}
511 \renewcommand{\lotmark}{}
512 \renewcommand{\afterlottitle}{}
513
514 \renewcommand*\setpnumwidth[1]{}
515 \renewcommand*\setrmarg[1]{}
516 \renewcommand*\cftbookbreak{}
517 \renewcommand*\cftpartbreak{}
518 \renewcommand*\cftchapterbreak{}

519 % \newlength{\cftbeforebookskip}
520 % \newlength{\cftbookindent}
521 % \newlength{\cftbooknumwidth}
522 \renewcommand*\cftbookfont{}
523 \renewcommand*\cftbookname{}
524 \renewcommand*\cftbookpresnum{}
525 \renewcommand*\cftbookaftersnum{}
526 \renewcommand*\cftbookaftersnumb{}
527 \renewcommand*\cftbookleader{}
528 \renewcommand*\cftbookdotsep{1}
529 \renewcommand*\cftbookpagefont{}
530 \renewcommand*\cftbookafterpnum{}
531 \renewcommand*\cftbookformatpnum[1]{}
532 \renewcommand*\cftbookformatpnumhook[1]{}

```

Part is already defined by tocloft.

```

533 % \newlength{\cftbeforechapterskip}
534 % \newlength{\cftchapterindent}
535 % \newlength{\cftchapternumwidth}
536 \renewcommand*\cftchapterfont{}
537 \renewcommand*\cftchaptername{}
538 \renewcommand*\cftchapterpresnum{}
539 \renewcommand*\cftchapteraftersnum{}
540 \renewcommand*\cftchapteraftersnumb{}
541 \renewcommand*\cftchapterleader{}
542 \renewcommand*\cftchapterdotsep{1}
543 \renewcommand*\cftchapterpagefont{}
544 \renewcommand*\cftchapterafterpnum{}
545 \renewcommand*\cftchapterformatpnum[1]{}
546 \renewcommand*\cftchapterformatpnumhook[1]{}

547 % \newlength{\cftbeforesectionsip}
548 % \newlength{\cftsectionindent}
549 % \newlength{\cftsectionnumwidth}
550 \renewcommand*\cftsectionfont{}
551 \renewcommand*\cftsectionname{}
552 \renewcommand*\cftsectionpresnum{}
553 \renewcommand*\cftsectionaftersnum{}
554 \renewcommand*\cftsectionaftersnumb{}
555 \renewcommand*\cftsectionleader{}
556 \renewcommand*\cftsectiondotsep{1}
557 \renewcommand*\cftsectionpagefont{}
558 \renewcommand*\cftsectionafterpnum{}

```

```
559 \renewcommand*{\cftsectionformatpnum}[1]{}
560 \renewcommand*{\cftsectionformatpnumhook}[1]{}

561 % \newlength{\cftbeforesubsectionskip}
562 % \newlength{\cftsubsectionindent}
563 % \newlength{\cftsubsectionnumwidth}
564 \renewcommand*{\cftsubsectionfont}{}
565 \renewcommand*{\cftsubsectionname}{}
566 \renewcommand*{\cftsubsectionpresnum}{}
567 \renewcommand*{\cftsubsectionaftersnum}{}
568 \renewcommand*{\cftsubsectionaftersnumb}{}
569 \renewcommand*{\cftsubsectionleader}{}
570 \renewcommand*{\cftsubsectiondotsep}{1}
571 \renewcommand*{\cftsubsectionpagefont}{}
572 \renewcommand*{\cftsubsectionafterpnum}{}
573 \renewcommand*{\cftsubsectionformatpnum}[1]{}
574 \renewcommand*{\cftsubsectionformatpnumhook}[1]{}

575 % \newlength{\cftbeforesubsubsectionskip}
576 % \newlength{\cftsubsubsectionindent}
577 % \newlength{\cftsubsubsectionnumwidth}
578 \renewcommand*{\cftsubsubsectionfont}{}
579 \renewcommand*{\cftsubsubsectionname}{}
580 \renewcommand*{\cftsubsubsectionpresnum}{}
581 \renewcommand*{\cftsubsubsectionaftersnum}{}
582 \renewcommand*{\cftsubsubsectionaftersnumb}{}
583 \renewcommand*{\cftsubsubsectionleader}{}
584 \renewcommand*{\cftsubsubsectiondotsep}{1}
585 \renewcommand*{\cftsubsubsectionpagefont}{}
586 \renewcommand*{\cftsubsubsectionafterpnum}{}
587 \renewcommand*{\cftsubsubsectionformatpnum}[1]{}
588 \renewcommand*{\cftsubsubsectionformatpnumhook}[1]{}

589 % \newlength{\cftbeforeparagraphskip}
590 % \newlength{\cftparagraphindent}
591 % \newlength{\cftparagraphnumwidth}
592 \renewcommand*{\cftparagraphfont}{}
593 \renewcommand*{\cftparagraphname}{}
594 \renewcommand*{\cftparagraphpresnum}{}
595 \renewcommand*{\cftparagraphaftersnum}{}
596 \renewcommand*{\cftparagraphaftersnumb}{}
597 \renewcommand*{\cftparagraphleader}{}
598 \renewcommand*{\cftparagraphdotsep}{1}
599 \renewcommand*{\cftparagraphpagefont}{}
600 \renewcommand*{\cftparagraphafterpnum}{}
601 \renewcommand*{\cftparagraphformatpnum}[1]{}
602 \renewcommand*{\cftparagraphformatpnumhook}[1]{}

603 % \newlength{\cftbeforesubparagraphskip}
604 % \newlength{\cftsubparagraphindent}
605 % \newlength{\cftsubparagraphnumwidth}
606 \renewcommand*{\cftsubparagraphfont}{}
607 \renewcommand*{\cftsubparagraphname}{}
608 \renewcommand*{\cftsubparagraphpresnum}{}
609 \renewcommand*{\cftsubparagraphaftersnum}{}
610 \renewcommand*{\cftsubparagraphaftersnumb}{}
611 \renewcommand*{\cftsubparagraphleader}{}
612 \renewcommand*{\cftsubparagraphdotsep}{1}
613 \renewcommand*{\cftsubparagraphpagefont}{}
614 \renewcommand*{\cftsubparagraphafterpnum}{}
615 \renewcommand*{\cftsubparagraphformatpnum}[1]{}

```

616 \renewcommand*{\cftsubparagraphformatpnumhook}[1]{}

617 % \newlength{\cftbeforefigureskip}

618 % \newlength{\cftfigureindent}

619 % \newlength{\cftfigureenumwidth}

620 \renewcommand*{\cftfigurefont}{}

621 \renewcommand*{\cftfigurename}{}

622 \renewcommand*{\cftfigurepresnum}{}

623 \renewcommand*{\cftfigureaftersnum}{}

624 \renewcommand*{\cftfigureaftersnumb}{}

625 \renewcommand*{\cftfigureleader}{}

626 \renewcommand*{\cftfiguredotsep}{1}

627 \renewcommand*{\cftfigurepagefont}{}

628 \renewcommand*{\cftfigureafterpnum}{}

629 \renewcommand*{\cftfigureformatpnum}[1]{}

630 \renewcommand*{\cftfigureformatpnumhook}[1]{}

631 % \newlength{\cftbeforesubfigureskip}

632 % \newlength{\cftsubfigureindent}

633 % \newlength{\cftsubfigureenumwidth}

634 \newcommand*{\cftsubfigurefont}{}

635 \newcommand*{\cftsubfigurename}{}

636 \newcommand*{\cftsubfigurepresnum}{}

637 \newcommand*{\cftsubfigureaftersnum}{}

638 \newcommand*{\cftsubfigureaftersnumb}{}

639 \newcommand*{\cftsubfigureleader}{}

640 \newcommand*{\cftsubfiguredotsep}{1}

641 \newcommand*{\cftsubfigurepagefont}{}

642 \newcommand*{\cftsubfigureafterpnum}{}

643 \newcommand*{\cftsubfigureformatpnum}[1]{}

644 \newcommand*{\cftsubfigureformatpnumhook}[1]{}

645 % \newlength{\cftbeforetableskip}

646 % \newlength{\cfttableindent}

647 % \newlength{\cfttableenumwidth}

648 \renewcommand*{\cfttablefont}{}

649 \renewcommand*{\cfttablename}{}

650 \renewcommand*{\cfttablepresnum}{}

651 \renewcommand*{\cfttableaftersnum}{}

652 \renewcommand*{\cfttableaftersnumb}{}

653 \renewcommand*{\cfttableleader}{}

654 \renewcommand*{\cfttabledotsep}{1}

655 \renewcommand*{\cfttablepagefont}{}

656 \renewcommand*{\cfttableafterpnum}{}

657 \renewcommand*{\cfttableformatpnum}[1]{}

658 \renewcommand*{\cfttableformatpnumhook}[1]{}

659 % \newlength{\cftbeforesubtableskip}

660 % \newlength{\cftsubtableindent}

661 % \newlength{\cftsubtableenumwidth}

662 \newcommand*{\cftsubtablefont}{}

663 \newcommand*{\cftsubtablename}{}

664 \newcommand*{\cftsubtablepresnum}{}

665 \newcommand*{\cftsubtableaftersnum}{}

666 \newcommand*{\cftsubtableaftersnumb}{}

667 \newcommand*{\cftsubtableleader}{}

668 \newcommand*{\cftsubtabledotsep}{1}

669 \newcommand*{\cftsubtablepagefont}{}

670 \newcommand*{\cftsubtableafterpnum}{}

671 \newcommand*{\cftsubtableformatpnum}[1]{}

672 \newcommand*{\cftsubtableformatpnumhook}[1]{}

```

673 \renewcommand*\booknumberline}[1]{}
674 \renewcommand*\partnumberline}[1]{}
675 \renewcommand*\chapternumberline}[1]{}
676 \renewcommand*\numberlinehook}[1]{}
677 % \renewcommand*\cftwhatismyname}{}%
678 \renewcommand*\booknumberlinehook}[1]{}
679 \renewcommand*\partnumberlinehook}[1]{}
680 \renewcommand*\chapternumberlinehook}[1]{}
681 \renewcommand\numberlinebox}[2]{}
682 \renewcommand\booknumberlinebox}[2]{}
683 \renewcommand\partnumberlinebox}[2]{}
684 \renewcommand\chapternumberlinebox}[2]{}
685 %
686 % \newlength\cftparfillskip}
687 \renewcommand*\cftpagenumbersoff}[1]{}
688 \renewcommand*\cftpagenumberson}[1]{}
689 \renewcommand*\cftlocalchange}[3]{}
690 \renewcommand*\cftaddtitleline}[4]{}
691 \renewcommand*\cftaddnumtitleline}[4]{}
692 \renewcommand\cftinsertcode}[2]{}
693 \renewcommand\cftinserthook}[2]{}
694 \renewcommand\settocpreprocessor}[2]{}
695 \DeclareRobustCommand\cftpagenumbersoff}[1]{}
696 \DeclareRobustCommand\cftpagenumberson}[1]{}

```

§ 692.11 Floats and captions

\@xfloat

\@xdblfloat

Reestablish lwarp's takeover the float handing, which memoir tried to grab:

```

697 \AtBeginDocument{
698 \def\@xfloat #1[#2]{%
699   \LWR@floatbegin{#1}[#2]
700   \normalsize
701   \@nameuse{#1adjustment}%
702   \LWR@futurenonspacel\LWR@mynexttoken\LWR@floatalignment%
703 }
704 \def\@xdblfloat #1[#2]{%
705   \LWR@floatbegin{#1}[#2]
706   \normalsize
707   \@nameuse{#1adjustment}%
708   \LWR@futurenonspacel\LWR@mynexttoken\LWR@floatalignment%
709 }
710 }

```

\newfloat

[<1: *within*>] {<2: *type*>} {<3: *ext*>} {<4: *capname*>}

```

711 \RenewDocumentCommand\newfloat}{o m m m}{%
712   \def\LWR@tempone{#4}%
713   \def\LWR@temptwo{\@nameuse{#2name}}%
714   \ifdefequal\LWR@tempone{\LWR@temptwo}{% recursive name, already defined
715     \IfValueTF{#1}%
716       {\DeclareFloatingEnvironment[fileext=#3,within=#1]{#2}}%
717       {\DeclareFloatingEnvironment[fileext=#3]{#2}}%
718   }{% not recursive name
719     \IfValueTF{#1}%
720     {\DeclareFloatingEnvironment[fileext=#3,within=#1,name={#4}]{#2}}%
721     {\DeclareFloatingEnvironment[fileext=#3,name={#4}]{#2}}%
722   }%

```

`newfloat` package automatically creates the `\listof` command for new floats, but `float` does not, so remove `\listof` here in case it is manually created later.

```
723 \cslet{listof#2s}\relax%
724 \cslet{listof#2es}\relax%
725 }
```

`\newlistof`

`[<within>] <type> <ext> <listofname>`

Emulated through the `\newfloat` mechanism. Note that `memoir` uses a different syntax than `tocloft` for the name.

```
726 \RenewDocumentCommand{\newlistof}{o m m m}
727 {%
728   \IfValueTF{#1}%
729     {\newlistentry[#1]{#2}{#3}{0}}%
730     {\newlistentry{#2}{#3}{0}}%
731   \@namedef{ext@#2}{#3}%
732   \@ifundefined{c@#3depth}{\newcounter{#3depth}}{}%
733   \setcounter{#3depth}{1}%
734   \@namedef{#3mark}{}%
735   \@namedef{#2}{\LWR@listof{#2}{#4}}%
736   \@namedef{@cftmake#3title}{}%
737   \@ifundefined{cftbefore#3titleskip}{}%
738     \expandafter\newlength\csname cftbefore#3titleskip\endcsname%
739     \expandafter\newlength\csname cftafter#3titleskip\endcsname%
740   }{}%
741   \@namedef{cft#3titlefont}{}%
742   \@namedef{cftafter#3title}{}%
743   \@namedef{cft#3prehook}{}%
744   \@namedef{cft#3posthook}{}%
745 }

746 \renewcommand{\setfloatadjustment}[2]{}

```

Borrowed from the `lwarp` version of `keyfloat`:

```
747 \NewDocumentEnvironment{KFLTmemoir@marginfloat}{0{-1.2ex} m}
748 {% start
749   \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}(note){marginblock}%
750   \renewcommand*{\@capttype}{#2}%
751 }
752 {%
753   \endLWR@BlockClassWP%
754 }
755
756 \DeclareDocumentEnvironment{marginfigure}{o}
757   {\begin{KFLTmemoir@marginfloat}{figure}}
758   {\end{KFLTmemoir@marginfloat}}
759
760 \DeclareDocumentEnvironment{margintable}{o}
761   {\begin{KFLTmemoir@marginfloat}{table}}
762   {\end{KFLTmemoir@marginfloat}}

763 \renewcommand{\setmarginfloatcaptionadjustment}[2]{}
764 \renewcommand{\setmpjustification}[2]{}
765 \renewcommand*{\mpjustification}{}
766 \renewcommand*{\setfloatlocations}[2]{}
767 \DeclareDocumentCommand{\suppressfloats}{o}{}
768 \renewcommand*{\FloatBlock}{}

```

```

769 \renewcommand*\FloatBlockAllowAbove{}
770 \renewcommand*\FloatBlockAllowBelow{}
771 \renewcommand*\setFloatBlockFor{}
772
773 \renewcommand{\captiontitlefinal}[1]{}

```

`\flegtable`, `\flegfigure`, `\flegtocfigure` are defined by memoir using `\newfloat`. These are defined with an @ in `caption`.

```

774 \renewcommand{\flegtable}{\tablename}
775 \renewcommand{\flegfigure}{\figurename}
776 \renewcommand{\flegtocfigure}{}
777 \renewcommand{\flegtocfigure}{}

778 \renewcommand{\@makesubfloatcaption}[2]{%
779   \minipagefullwidth
780   \begin{minipage}{\linewidth}%
781   #1 \ignorespaces #2 \unskip%
782   \end{minipage}
783 }
784
785 \renewcommand*\tightsubcaptions{}
786 \renewcommand*\loosesubcaptions{}
787
788 \renewcommand*\subcaptionsize[1]{}
789 \renewcommand*\subcaptionlabelfont[1]{}
790 \renewcommand*\subcaptionfont[1]{}
791 \renewcommand*\subcaptionstyle[1]{}
792
793 \renewcommand*\hangsubcaption{}
794 \renewcommand*\shortsubcaption{}
795 \renewcommand*\normalsubcaption{}
796
797 \RenewDocumentEnvironment{sidecaption}{o m o}
798 {}
799 {%
800   \IfValueTF{#1}{\caption[#1]{#2}}{\caption{#2}}%
801   \IfValueT{#3}{\label{#3}}%
802 }
803
804 % \newlength{\sidecapwidth}
805 % \newlength{\sidecapsep}
806 \renewcommand*\setsidecaps[2]{}
807 \renewcommand*\sidecapmargin[1]{}
808 % \newif\ifscapmargleft
809 \scapmargleftfalse
810 \renewcommand*\setsidecapps[1]{}

```

Env sidecontcaption

```

811 \RenewDocumentEnvironment{sidecontcaption}{m o}
812 {}
813 {%
814   \ifdef{\ContinuedFloat}%
815     {\ContinuedFloat}%
816     {\addtocounter{\@capttype}{-1}}%
817   \caption{#1}%

```

Without `\@capttype`, the section is referred to instead.

```
818 \IfValueT{#2}{\label[\@capttype]{#2}}%
819 }
```

`\sidenamedlegend` does not appear to use the `toc` argument.

```
820 \renewenvironment{sidenamedlegend}[2][]{
821   \begin{center}
822     \nameuse{\@capttype name}\CaptionSeparator#2
823   \end{center}
824 }
825 {}
826
827 \renewenvironment{sidelegend}[1]
828 {\begin{center}
829   #1
830
831 }
832 {\end{center}}
833
834 \renewcommand*\sidedcapstyle{}
835 \renewcommand*\overridescapmargin[1]{}
836 % \newlength\sidedcapraise
837 \renewcommand*\sidedcapfloatwidth{\linewidth}
838
839 \LetLtxMacro\ctabular\tabular
840 \LetLtxMacro\endctabular\endtabular
841
842 \renewcommand{\autorows}[5][]{%
843   #5%
844 }
845
846 \renewcommand{\autocolS}[5][]{%
847   #5%
848 }
```

§ 692.12 Footnotes and page notes

```
849 \renewcommand*\feetabovefloat{}
850 \renewcommand*\feetbelowfloat{}
851 \renewcommand*\feetatbottom{}
852
853 \renewcommand*\verbfootnote[2][]{%
854   \PackageError{lwarp,memoir}%
855     {Verbatim footnotes are not yet supported by lwarp}%
856     {This may be improved some day.}%
857 }
858
859 \renewcommand*\plainfootnotes{}
860 \renewcommand*\twocolumnfootnotes{}
861 \renewcommand*\threecolumnfootnotes{}
862 \renewcommand*\paragraphfootnotes{}
863 \renewcommand*\footfudgefiddle{}
864
865 \renewcommand*\newfootnoteseries[1][%
866   \PackageError{lwarp,memoir}%
867     {Memoir footnote series are not yet supported by lwarp}%
868     {This may be improved some day.}%
869 }
870
```

```
871 \renewcommand*{\plainfootstyle}[1]{}
872 \renewcommand*{\twocolumnfootstyle}[1]{}
873 \renewcommand*{\threecolumnfootstyle}[1]{}
874 \renewcommand*{\paragraphfootstyle}[1]{}
875
876 \renewcommand*{\footfootmark}{}
877 \renewcommand*{\footmarkstyle}[1]{}
878
879 % \newlength{\footmarkwidth}
880 % \newlength{\footmarksep}
881 % \newlength{\footparindent}
882
883 \renewcommand*{\foottextfont}{}
884
885 \renewcommand*{\marginparmargin}[1]{}
886 \renewcommand*{\sideparmargin}[1]{}
887
888 \LetLtxMacro\sidepar\marginpar
889 \renewcommand*{\sideparfont}{}
890 \renewcommand*{\sideparform}{}
891 \LWR@providelength{\sideparvshift}
892
893 \renewcommand*{\parnopar}{}
894
895 \renewcommand{\sidebar}[1]{\begin{quote}#1\end{quote}}
896 \renewcommand*{\sidebarmargin}[1]{}
897 \renewcommand*{\sidebarfont}{}
898 \renewcommand*{\sidebarform}{}
899 % \newlength{\sidebarhsep}
900 % \newlength{\sidebarvsep}
901 % \newlength{\sidebarwidth}
902 % \newlength{\sidebartopsep}
903 \renewcommand{\setsidebarheight}[1]{}
904 \renewcommand*{\setsidebars}[6]{}
905 \renewcommand*{\footnotesatfoot}{}
906 \renewcommand*{\footnotesinmargin}{}
907
908 \LetLtxMacro\sidefootnote\footnote
909 \LetLtxMacro\sidefootnotemark\footnotemark
910 \LetLtxMacro\sidefootnotetext\footnotetext
911
912 \renewcommand*{\sidefootmargin}[1]{}
913 % \newlength{\sidefoothsep}
914 % \newlength{\sidefootvsep}
915 % \newlength{\sidefootwidth}
916 % \newlength{\sidefootadjust}
917 % \newlength{\sidefootheight}
918 \renewcommand*{\setsidefootheight}[1]{}
919 % \renewcommand*{\sidefootfont}{}% in docs but not in the package
920 \renewcommand*{\setsidefeet}[6]{}
921 \renewcommand*{\sidefootmarkstyle}[1]{}
922 \renewcommand*{\sidefoottextfont}{}
923 \renewcommand*{\sidefootform}{}

924 \renewcommand*{\continuousnotenums}{\pncontopttrue}% from pagenote
925 \renewcommand*{\notepageref}{}
926 \renewcommand*{\prenotetext}{}
927 \renewcommand*{\postnotetext}{}
928 \LetLtxMacro\printpageinnoteshyperref\printpageinnotes
929 \renewcommand*{\foottopagenote}{}

```

```
930 \renewcommand*{\pagetofootnote}{}
```

```
\m@m@wrpnote
```

```
\startnoteentrystart
```

To have `cleveref` work with page note labels, the following patch writes `\thepagenote` and also adds `\arabic{pagenote}` to the first argument written to the `.ent` file:

```
\startnoteentry{\thepagenote}{\arabic{pagenote}} . . .
```

The arabic value is required for `cleveref`. `\thepagenote` becomes `\@firstoftwo#1` and the arabic value becomes `\@secondoftwo#1`.

 `\nameref` Note that for print mode, `\nameref` print the section name where the page notes are declared in the text, but for HTML it prints the name where the page notes are printed.

```
931 \xpatchcmd{\m@m@wrpnote}
932   {\string\startnoteentry{\thepagenote}}
933   {\string\startnoteentry{\thepagenote}{\arabic{pagenote}}}}
934   {}
935   {\LWR@patcherror{memoir}{m@m@wrpnote}}
936
937 \renewcommand\startnoteentrystart[4]{%
938   \prenoteinnotes%
939   \noteidinnotes{\@firstoftwo#1}{#2}%
940   \ifmtarg{#2}{%
941     \phantomsection\def\@currentlabel{#1}%           original
942     \def\@currentlabel{\@firstoftwo#1}%             lwarp
943     \def\cref@currentlabel{%                       lwarp
944       [pagenote][\@secondoftwo#1][\@firstoftwo#1% lwarp
945       ]%                                           lwarp
946     }{}%
947   \pagenoteanchor{#4}%
948   \pageinnotes{#3}%
949   \prenotetext%
950 }
```

§ 692.13 Decorative text

```
951 \renewcommand*{\epigraphposition}[1]{}
952 \renewcommand*{\epigraphtextposition}[1]{}
953 \renewcommand*{\epigraphsourceposition}[1]{}
954 \renewcommand*{\epigraphfontsize}[1]{}
955 \renewcommand*{\epigraphforheader}[2][1]{}
956 \renewcommand*{\epigraphpicture}{}
```

§ 692.14 Poetry

```
957 \renewcommand*{\vinphantom}{}
958 \renewcommand*{\vleftofline}[1]{#1}
959 % \let\linenumberfrequency\poemlines
960 % \renewcommand*{\linenumberfont}[1]{}
961
962 \DeclareDocumentCommand{\PoemTitle}{s o m}{%
963   \IfValueTF{#2}%
964     {\poemtitle[#2]{#4}}%
965     {\poemtitle{#4}}%
966 }
967
968 \renewcommand*{\NumberPoemTitle}{}
969 \renewcommand*{\PlainPoemTitle}{}
970 \renewcommand*{\poemtitlepstyle}{}

```

```

971 \renewcommand*\poemtitlestar*mark}[1]{}
972 \renewcommand*\poemtitlestar*style}{}
973 \renewcommand*\PoemTitleheadstart}{}
974 \renewcommand*\printPoemTitlenonum}{}
975 \renewcommand*\printPoemTitlenum}{}
976 \renewcommand*\afterPoemTitlenum}{}
977 \renewcommand*\printPoemTitle*title}[1]{}
978 \renewcommand*\afterPoemTitle}{}
979 \newlength{\midpoemtitleskip}
980 \renewcommand*\PoemTitlenumfont}{}
981 \renewcommand*\PoemTitlefont}{}

```

§ 692.15 **Boxes, verbatims and files**

```

982 \renewenvironment{qframe}{\fboxed}\endfboxed}
983 \renewenvironment{qshade}{\shaded}\endshaded}

984 \renewcommand*\setverbatimfont}[1]{}
985 \renewcommand*\tabson}[1]{}
986 \renewcommand*\tabsoff}{}
987 \renewcommand*\wrappingon}{}
988 \renewcommand*\wrappingoff}{}
989 \renewcommand*\verbatimindent}{}
990 \renewcommand*\verbatimbreakchar}[1]{}

991 \DefineVerbatimEnvironment{fboxverbatim}{Verbatim}{frame=single}

```

boxedverbatim is already defined by moreverb. boxedverbatim* does not appear to work at all, even in a minimal print memoir document.

```

992 \renewcommand*\bvbox}{}
993 \renewcommand*\bvtopandtail}{}
994 \renewcommand*\bv*sid*es}{}
995 \renewcommand*\nobvbox}{}
996 % \newlength\bvboxsep
997 \renewcommand*\bvtoprulehook}{}
998 \renewcommand*\bvtopmidhook}{}
999 \renewcommand*\bvendrulehook}{}
1000 \renewcommand*\bvleftsidehook}{}
1001 \renewcommand*\bvrightsidehook}{}
1002 \renewcommand*\bvperpagetrue}{}
1003 \renewcommand*\bvperpagefalse}{}
1004 \renewcommand{\bvtopofpage}[1]{}
1005 \renewcommand{\bvendofpage}[1]{}
1006 \renewcommand*\linenumberfrequency}[1]{}
1007 \renewcommand*\resetbvl*in*umber}{}
1008 \renewcommand*\setbvl*in*ums}[2]{}
1009 \renewcommand*\linenumberfont}[1]{}
1010 \renewcommand*\bvnumbersinside}{}
1011 \renewcommand*\bvnumbersoutside}{}

```

§ 692.16 **Cross referencing**

```

1012 \renewcommand*\fref}[1]{\cref{#1}}
1013 \renewcommand*\tref}[1]{\cref{#1}}
1014 \renewcommand*\pref}[1]{\cpageref{#1}}
1015 \renewcommand*\Aref}[1]{\cref{#1}}
1016 \renewcommand*\Bref}[1]{\cref{#1}}
1017 \renewcommand*\Pref}[1]{\cref{#1}}

```

```

1018 \renewcommand*\Sref}[1]{\cref{#1}}
1019 \renewcommand*\figurerefname}{Figure}
1020 \renewcommand*\tablerefname}{Table}
1021 \renewcommand*\pagerefname}{page}
1022 \renewcommand*\bookrefname}{Book~}
1023 \renewcommand*\partrefname}{Part~}
1024 \renewcommand*\chapterrefname}{Chapter~}
1025 \renewcommand*\sectionrefname}{\S}
1026 \renewcommand*\appendixrefname}{Appendix~}
1027 \LetLtxMacro\titleref\nameref
1028 \renewcommand*\headnameref){}
1029 \renewcommand*\tocnameref){}
1030
1031 \providecounter{LWR@currenttitle}
1032
1033 \renewcommand*\currenttitle){%
1034   \addtocounter{LWR@currenttitle}{1}%
1035   \label{currenttitle\arabic{LWR@currenttitle}}%
1036   \nameref{currenttitle\arabic{LWR@currenttitle}}%
1037 }
1038
1039 \renewcommand*\theTitleReference}[2]{}
1040 \renewcommand*\namerefon){}
1041 \renewcommand*\namerefoff){}

```

§ 692.17 **Back matter**

\@@wrindexhyp

Redefined to write the LWR@autoindex counter instead of page. Note that memoir has two versions, depending on the use of hyperref.

```

1042 \AtBeginDocument{
1043
1044 \def\@@wrindexhyp#1||\{\%
1045   \addtocounter{LWR@autoindex}{1}%           lwarp
1046 %   \ifshowindexmark\@showidx{#1}\fi
1047   \protected@write\@auxout{)%
1048 %     {\string\@@wrindexm@m{\@idxfile}{#1}{\thepage}}%
1049     {\string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}}% lwarp

```

The label is assigned after the file write to avoid conflict with cleveref.

```

1050   \label{LWRindex-\arabic{LWR@autoindex}}%   lwarp
1051   \endgroup
1052   \@esphack}%

```

\@@wrspindexhyp

\specialindex behaves like a regular \index, pointing to where \specialindex is used. If \specialindex is used inside a figure or table after the \caption, then the hyperlink will be given the name of that particular figure or table.

```

1053 \def\@@wrspindexhyp#1||\{\%
1054   \addtocounter{LWR@autoindex}{1}%
1055 %   \ifshowindexmark\@showidx{#1}\fi
1056   \protected@write\@auxout{)%
1057 %     {\string\@@wrindexm@m{\@idxfile}{#1}{\@nameuse{the\@sptheidx}}}%
1058     {\string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}}%

```

The label is assigned after the file write to avoid conflict with cleveref.

```

1059   \label{LWRindex-\arabic{LWR@autoindex}}%
1060   \endgroup
1061   \@esphack}%
1062

```

```
1063 }% \AtBeginDocument
```

\spindex

Patched to append _html to the file:

```
1064 \renewcommand{\spindex}[2]{%
1065   \ifundefined{#1@idxfile}%
1066   {\ifreportnoidxfile
1067     \@memwarn{Undefined index file #1}%
1068     \fi
1069     \begingroup
1070     \@sanitize
1071     \@nowrindex}%
1072   {\def\@idxfile{#1_html}%
1073     \def\@sptheidx{#2}%
1074     \begingroup
1075     \@sanitize
1076     \@wrspindex}}
```

\makeindex

Patched to use _html filename and \BaseJobname:

```
1077 \catcode'\_ =12%
1078 \renewcommand*\makeindex[1][\BaseJobname]{%
1079   \if@filesw
1080     \def\gindex{\@bsphack%
1081       \ifnextchar [{\@index}{\@index[\BaseJobname]}}
1082     \def\specialindex{\@bsphack\@spindex}%
1083     \makememindexhook
1084     \expandafter\newwrite\csname #1@idxfile\endcsname
1085     \expandafter\immediate\openout \csname #1@idxfile\endcsname #1_html.idx\relax
1086     \typeout{Writing index file #1_html.idx }%
1087     \fi}
1088 \catcode'\_ =8%
```

\printindex

Patched to use _html filename and \BaseJobname. This will later be patched by the lwarp core.

```
1089 \catcode'\_ =12%
1090 \renewcommand{\printindex}[1][\BaseJobname]{\@input@{#1_html.ind}}
1091 \catcode'\_ =8%

1092 \DeclareDocumentCommand{\newblock}{}{}
1093 %
1094 \renewcommand*\showindexmarks{}
1095 \renewcommand*\hideindexmarks{}
1096
1097 \renewcommand*\xindyindex{}
```

§ 692.18 Miscellaneous

```
1098 \renewcommand*\changemarks{}
1099 \renewcommand*\nochangemarks{}
1100 \renewcommand*\added[1]{}
1101 \renewcommand*\deleted[1]{}
1102 \renewcommand*\changed[1]{}
1103
1104 \renewcommand*\showtrimsoff{}
1105 \renewcommand*\showtrimson{}
1106 \renewcommand*\trimXmarks{}
1107 \renewcommand*\trimLmarks{}
```

```

1108 \renewcommand*\trimFrame{}
1109 \renewcommand*\trimNone{}
1110 \renewcommand*\trimmarkscolor{}
1111 \renewcommand*\trimmarks{}
1112 \renewcommand*\tmarktl{}
1113 \renewcommand*\tmarktr{}
1114 \renewcommand*\tmarkbr{}
1115 \renewcommand*\tmarkbl{}
1116 \renewcommand*\tmarktm{}
1117 \renewcommand*\tmarkmr{}
1118 \renewcommand*\tmarkbm{}
1119 \renewcommand*\tmarkml{}
1120 \renewcommand*\trimmark{}
1121 \renewcommand*\quarkmarks{}
1122 \renewcommand*\registrationColour}[1]{}
1123
1124 \renewcommand*\leavespergathering}[1]{}
1125
1126 \renewcommand*\noprelistbreak{}
1127
1128 \renewcommand*\cleartorecto{}
1129 \renewcommand*\cleartoverso{}
1130
1131 \renewenvironment{vplace}[1][1]{}{}

```

§ 692.19 **ccaption emulation**

```

1132 \renewcommand*\captiondelim}[1]{\renewcommand*\CaptionSeparator{#1}}
1133 \renewcommand*\captionnamefont}[1]{}
1134 \renewcommand*\captiontitlefont}[1]{}
1135 \renewcommand*\flushleft{}
1136 \renewcommand*\centerlastline{}
1137 \renewcommand*\captionstyle}[2][1]{}
1138 \DeclareDocumentCommand{\captionwidth}{m}{}
1139 \renewcommand*\changecaptionwidth{}
1140 \renewcommand*\normalcaptionwidth{}
1141 \renewcommand*\hangcaption{}
1142 \renewcommand*\indentcaption}[1]{}
1143 \renewcommand*\normalcaption{}
1144 \renewcommand{\precaption}[1]{}
1145 \renewcommand{\postcaption}[1]{}
1146 \renewcommand{\midbicapTION}[1]{}
1147 \renewcommand{\contcaption}[1]{%
1148 % \ContinuedFloat%
1149 % \caption{#1}%
1150 \begin{LWR@figcaption}% later becomes \caption*
1151 \LWR@isolate{\@nameuse{\@capytype name}}~%
1152 \thechapter.\the\value{\@capytype}\CaptionSeparator\LWR@isolate{#1}%
1153 \end{LWR@figcaption}%
1154 }

1155 \newlength{\abovelegendskip}
1156 \setlength{\abovelegendskip}{0.5\baselineskip}
1157 \newlength{\belowlegendskip}
1158 \setlength{\belowlegendskip}{\abovelegendskip}

```

The extra `\\` here forces a `
` in HTML when `\legend` is used in a `\marginpar`.

```

1159 \renewcommand{\legend}[1]{\begin{center}#1\\end{center}}
1160

```

```

1161 \renewcommand{\namedlegend}[2][{}]{%
1162   \begin{center}
1163     \@nameuse{fleg\@capttype}\CaptionSeparator#2\
1164   \end{center}
1165   \@nameuse{flegtoc\@capttype}{#1}
1166 }

```

`\flegtable`, `\flegfigure`, `\flegtocable`, `\flegtocfigure` are defined by memoir using `\newfloat`. These are defined with an @ in `ccaption`.

```

1167 \renewcommand{\newfixedcaption}[3][\caption]{%
1168   \renewcommand{#2}{\def\@capttype{#3}#1}}
1169 \renewcommand{\rennewfixedcaption}[3][\caption]{%
1170   \renewcommand{#2}{\def\@capttype{#3}#1}}
1171 \renewcommand{\providfixedcaption}[3][\caption]{%
1172   \providecommand{#2}{\def\@capttype{#3}#1}}
1173
1174 \renewcommand{\bitwonumcaption}[6][{}]{%
1175   \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
1176   \addtocounter{\@capttype}{-1}%
1177   \begingroup%
1178   \csdef{\@capttype name}{#4}%
1179   \ifblank{#5}{\caption{#6}}{\caption[#5]{#6}}%
1180   \endgroup%
1181   \ifblank{#1}{}{\label{#1}}%
1182 }
1183
1184 \LetLtxMacro\bionenumcaption\bitwonumcaption% todo
1185
1186 \renewcommand{\bicaption}[5][{}]{%
1187   \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
1188   \begin{LWR@figcaption}% later becomes \caption*
1189     \LWR@isolate{#4} % space
1190     \thechapter.\the\value{\@capttype}\CaptionSeparator\LWR@isolate{#5}%
1191   \end{LWR@figcaption}%
1192   \ifblank{#1}{}{\label{#1}}%
1193 }
1194
1195 \renewcommand{\bicontcaption}[3]{%
1196   \contcaption{#1}%
1197   \begingroup%
1198   \csdef{\@capttype name}{#2}%
1199   \contcaption{#3}%
1200   \endgroup%
1201 }

```

Only in `ccaption`, not in memoir:

```

1202 % \LetLtxMacro\longbitwonumcaption\bitwonumcaption%
1203 % \LetLtxMacro\longbionenumcaption\bitwonumcaption%
1204 % \LetLtxMacro\longbicaption\bicaption%

```

Patches for subfloats to support additional lwarp labels:

```

1205 \renewcommand{\@memsubbody}{%
1206   \bgroup
1207   \let\label=\memsub@label
1208   \ifdonemaincaption\else
1209     \advance\csname c@\@capttype\endcsname\@ne
1210   \fi

```

```

1211 % \refstepcounter{sub\@capttype}\@contkeep%
1212 % \leavevmode%          lwarp
1213 \@ifnextchar [%
1214   {\@memsubfig}%
1215   {\@memsubfig[\@empty]}}
1216
1217 \renewcommand{\@memcontsubbody}{%
1218   \bgroup
1219   \let\label=\memsub@label
1220   \@contset
1221   % \refstepcounter{sub\@capttype}\@contkeep%
1222 % \leavevmode%          lwarp
1223 \@ifnextchar [%
1224   {\@memsubfig}%
1225   {\@memsubfig[\@empty]}}
1226
1227
1228 \long\def\@memsubfloat#1[#2][#3]#4{%
1229 % \@tempcnta=\@ne
1230 % \if@tightsubcap
1231 % \if@minipage
1232 % \@tempcnta=\z@
1233 % \else
1234 % \ifdim\lastskip=\z@
1235 % \@tempcnta=\@ne
1236 % \else
1237 % \@tempcnta=\tw@
1238 % \fi
1239 % \fi
1240 % \fi
1241 % \if@contbotsub
1242 % \def\subfig@top{\subfloattopskip}%
1243 % \def\subfig@bottom{\subfloatbottomskip}%
1244 % \else
1245 % \def\subfig@top{\subfloatbottomskip}%
1246 % \def\subfig@bottom{\subfloattopskip}%
1247 % \fi
1248 % \setbox\@tempboxa \hbox{#4}%
1249 % \@tempdima=\wd\@tempboxa
1250 % \vbox
1251 \bgroup%
1252 \mem@step@subcounter%
1253 % \vbox
1254 \LWR@stoppars%
1255 \minipagefullwidth%          lwarp
1256 \begin{minipage}{\linewidth}% lwarp
1257 \bgroup
1258 % \ifcase\@tempcnta
1259 % \@minipagefalse
1260 % \or
1261 % \vspace{\subfig@top}
1262 % \or
1263 % \ifdim \lastskip=\z@ \else
1264 % \@tempskip\subfig@top\@xaddvskip
1265 % \fi
1266 % \fi
1267 \if@contbotsub
1268 #4% \box\@tempboxa
1269 \egroup
1270 \ifx \@empty#3\relax \else

```

```

1271 %      \vskip\subfloatcapskip
1272      \@memsubcaption{#1}{#2}{#3}%
1273      \fi
1274      \else
1275      \ifx \@empty#3\relax \else
1276      \@memsubcaption{#1}{#2}{#3}%
1277 %      \vskip\subfloatcapskip
1278 %      \vskip\subfloatcaptopadj
1279      \fi\egroup
1280      #4% \box\@tempboxa
1281      \fi
1282 %      \vspace{\subfig@bottom}
1283      \end{minipage}%          lwarp
1284      \LWR@startpars%        lwarp
1285      \egroup
1286 \egroup
1287 }

```

§ 692.20 Final patchwork

```

1288 \newlistof{tableofcontents}{toc}{\contentsname}
1289 \newlistof{listoffigures}{lof}{\listfigurename}
1290 \newlistof{listoftables}{lot}{\listtablename}

```

File 584 **lwarp-common-multimedia.sty**

§ 693 Package **common-multimedia**

Pkg lwarp-common-multimedia Common code for multimedia, movie15, and media9.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addressource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each `<audio>` and `<video>` object.

media9 slideshows are not supported.

`\hyperlinkmovie`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YouTube™ video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

for HTML output:

```

1 \ProvidesPackage{lwarp-common-multimedia}[2019/04/22]
2 \RequirePackage{xkeyval}
3
4 \define@key{LWR@multimedia}{width}{\setlength{LWR@multimedia@width}{#1}}
5 \define@key{LWR@multimedia}{height}{\setlength{LWR@multimedia@height}{#1}}
6 \define@key{LWR@multimedia}{totalheight}{\setlength{LWR@multimedia@height}{#1}}
7
8 \newlength{LWR@multimedia@width}
9 \newlength{LWR@multimedia@height}
10 \newlength{LWR@multimedia@maxdimension}

```

`\LWR@multimedia@printsiz` Proportional to `\linewidth` and the viewport’s smaller dimension. This scales each object such that it will always fit on the screen, even if a tall or wide object inside a tall or wide viewport.

```

10 \newcommand*{\LWR@multimedia@printsiz}{%
11   \setlength{LWR@multimedia@maxdimension}{%
12     \maxof%
13       {\linewidth}%
14       {\maxof{LWR@multimedia@width}{LWR@multimedia@height}}%
15   }%
16   \setlength{LWR@multimedia@maxdimension}{1.1LWR@multimedia@maxdimension}%
17   \ifdimgreater{LWR@multimedia@width}{0pt}{%
18     width:%
19     \LWR@printpercentlength%
20       {LWR@multimedia@width}%
21       {LWR@multimedia@maxdimension}vmin ; % space
22   }%
23   \ifdimgreater{LWR@multimedia@height}{0pt}{%
24     height:%
25     \LWR@printpercentlength%
26       {LWR@multimedia@height}%
27       {LWR@multimedia@maxdimension}vmin ; % space
28   }%
29 }

```

`\LWR@multimedia@fileAV` `{\langle poster text \rangle} {\langle filename \rangle} {\langle audio/video \rangle} {\langle mimetype \rangle}`

Creates a video or audio from a file. The 2019/10 update of the L^AT_EX kernel may cause extra quotes to be added in the filenames. They are removed here.

```

30 \newcommand*{\LWR@multimedia@fileAV}[4]{%
31 \IfFileExists{#2}{% also sets \@filef@und
32 \StrSubstitute[100]{\@filef@und}{"}{ }[\LWR@parsedfilename]}%

```

The container `<div>` is sized as desired.

```

33 \ifstrequal{#3}{audio}{%

```

```

34     \begin{BlockClass}{AVviewport}
35   }{%
36     \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{AVviewport}
37   }

```

Paragraph tags are unnecessary for the A/v tags.

```
38   \LWR@stoppars
```

The A/v element is 100% of the container.

```

39   \LWR@htmltag{%
40     #3\ % space
41     \ifstrequal{#3}{audio}{}{%
42       width=\textquotedbl{}100%\textquotedbl\ % space
43       height=\textquotedbl{}100%\textquotedbl\ % space
44     }%
45     controls%
46   }\LWR@orignewline

```

The file source and type:

```

47   \LWR@htmltag{%
48     source % space
49     src=\textquotedbl%
50     \LWR@parsedfilename\unskip\textquotedbl\ % space
51     type=\textquotedbl{}#4\textquotedbl}

```

The poster text inside paragraph tags, along with a reference to the file.

```

52   \LWR@startpars
53   \LWR@href{\LWR@parsedfilename}{#1}
54   \LWR@stoppars

```

Finish.

```

55   \LWR@htmltag{/#3}\LWR@orignewline
56   \end{BlockClass}
57 }{%
58   \PackageError{lwarp-common-multimedia}
59     {File '#2' not found}
60     {Perhaps an incorrect path?}
61 }%
62 }

```

`\LWR@multimedia@httpAV` `{\langle poster text \rangle} {\langle filename \rangle} {\langle audio/video \rangle} {\langle mimetype \rangle}`

Creates a video or audio from a URL link.

```
63 \newcommand*{\LWR@multimedia@httpAV}[4]{%
```

The container <div> is sized as desired.

```

64   \ifstrequal{#3}{audio}{%
65     \begin{BlockClass}{AVviewport}
66   }{%
67     \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{AVviewport}
68   }

```

Paragraph tags are unnecessary for the A/v tags.

```
69   \LWR@stoppars
```

The A/v element is 100% of the container.

```

70   \LWR@htmltag{%
71     #3\ % space

```

```

72     \ifstrequal{#3}{audio}{}{%
73         width=\textquotedbl{}100%\textquotedbl\ % space
74         height=\textquotedbl{}100%\textquotedbl\ controls%
75     }%
76 } \LWR@orignewline

```

The file source and type:

```

77 \LWR@htmltag{%
78     source % space
79     src=\textquotedbl#2\textquotedbl\ % space
80     type=\textquotedbl#4\textquotedbl}

```

The poster text inside paragraph tags, along with a reference to the URL.

```

81 \LWR@startpars
82 \LWR@href{#2}{#1}
83 \LWR@stoppars

```

Finish.

```

84 \LWR@htmltag{/#3}\LWR@orignewline
85 \end{BlockClass}
86 }

```

\LWR@multimedia@AV

{<poster text>} {<filename>} {<audio/video>} {<mimetype>}

Creates an audio or video from a file or a URL.

```

87 \newcommand*\LWR@multimedia@AV[4]{%
88     \IfBeginWith{#2}{http}%
89     {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
90     {%
91         \IfBeginWith{#2}{HTTP}%
92         {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
93         {\LWR@multimedia@fileAV{#1}{#2}{#3}{#4}}%
94     }%
95 }

```

\LWR@multimedia@embed

{<poster text>} {<URL or filename>} {<mime type>}

Embeds multimedia of an arbitrary type. The poster text is not used, as it would appear along with the video if the <embed> element is supported.

```

96 \newcommand*\LWR@multimedia@embed[3]{%
97     \begin{BlockClass}[width:100%\AVviewport]%
98     \LWR@stoppars
99     \LWR@htmltag{%
100         embed % space
101         \ifblank{#3}{}{type=\textquotedbl#3\textquotedbl\ }%
102         style=\textquotedbl\LWR@multimedia@printsizes\ margin:auto\textquotedbl\ % space
103         src=\textquotedbl#2\textquotedbl\ % space
104     }%
105     \LWR@startpars
106     \end{BlockClass}
107 }

```

Error message if the comment character is used among the arguments of

\LWR@multimedia@percenterror

\LWR@multimediab.

```

108 \newcommand*\LWR@multimedia@percenterror){%
109     \PackageError{lwarp-media9}
110     {%

```

```

111         Do not use a percent comment between\MessageBreak
112         \protect\includemedia\space arguments%
113     }
114     {%
115         Percent is changed to a regular character\MessageBreak
116         to allow its use inside a URL.%
117     }
118 }

```

\LWR@multimediab

[*<options>*] [*<poster text>*] [*<filename>*]

Creates multimedia. Examines the file extension to determine the type. If not a supported type, creates an embedded object if it has a URL. If neither, create a link to the unsupported object.

```
119 \newcommand*\LWR@multimediab[3][[]]{%
```

Error if the percent character appears among the arguments. This could happen since the comment character has been temporarily disabled, for use in a URL.

```

120     \if#1\@percentchar\LWR@multimedia@percenterror\fi%
121     \if#2\@percentchar\LWR@multimedia@percenterror\fi%
122     \if#3\@percentchar\LWR@multimedia@percenterror\fi%

```

Paragraph handling:

```
123     \LWR@stoppars%
```

Record the desired size.

```

124     \setlength{\LWR@multimedia@width}{0pt}%
125     \setlength{\LWR@multimedia@height}{0pt}%
126     \setkeys*\LWR@multimedia}{#1}%

```

If a known A/V type, create an HTML5 <video> or <audio>.

```

127     \IfEndWith{#3}{.mp4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
128     \IfEndWith{#3}{.MP4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
129     \IfEndWith{#3}{.mp3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
130     \IfEndWith{#3}{.MP3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%

```

If an arbitrary URL, embed it.

```

131     \IfBeginWith{#3}{http}{\LWR@multimedia@embed{#2}{#3}}{%
132     \IfBeginWith{#3}{HTTP}{\LWR@multimedia@embed{#2}{#3}}{%
133     \IfBeginWith{#3}{ftp}{\LWR@multimedia@embed{#2}{#3}}{%
134     \IfBeginWith{#3}{FTP}{\LWR@multimedia@embed{#2}{#3}}{%

```

If unknown, create a link to it.

```

135         \LWR@href{#3}{#2}% unknown format
136     }}}}]}%

```

Paragraph handling:

```

137     \LWR@startpars%
138     \endgroup%
139 }

```

Catcodes which may appear in a URL.

```

140 \newrobustcmd*\LWR@multimedia){%
141     \begingroup%
142     \LWR@linkmediacatcodes%
143     \LWR@multimediab%
144 }

```

File 585 **lwarp-common-mathjax-letters.sty**

§ 694 Package **common-mathjax-letters**

Pkg Common code used by a number of packages to generate Greek math characters for MATHJAX.
lwarp-common-mathjax-letters

for HTML output: 1 \ProvidesPackage{lwarp-common-mathjax-letters}[2020/08/10]

\LWR@mathjax@addletter * {\<2: capitalize name?\>} {\<3: prefix?\>} {\<4: postfix?\>} {\<5: name?\>} {\<6: unicode?\>}
Star to italicize the result, used when the unicode character does not exist.

```

2 \begin{warpMathJax}
3
4 \NewDocumentCommand{\LWR@mathjax@addletter}{s m m m m m}{
5   \IfBooleanTF{#2}%
6     {\edef\LWR@tempone{\LWRtexttitlecase{#5}}}%
7     {\edef\LWR@tempone{#5}}%
8   \xdef\LWR@customizedMathJax{%
9     \LWR@customizedMathJax%
10    \LWRbackslash(%
11    \LWRbackslash def\LWRbackslash%
12    #3% prefix
13    \LWR@tempone%name
14    #4% postfix
15    \LWRleftbrace%
16  }%
17  \IfBooleanTF{#1}{%
18    \xdef\LWR@customizedMathJax{%
19      \LWR@customizedMathJax%
20      \LWRbackslash mathit\LWRleftbrace%
21      \LWRbackslash unicode\LWRleftbrace x#6\LWRrightbrace%
22      \LWRrightbrace%
23    }%
24  }{%
25    \xdef\LWR@customizedMathJax{%
26      \LWR@customizedMathJax%
27      \LWRbackslash unicode\LWRleftbrace x#6\LWRrightbrace%
28    }%
29  }%
30  \xdef\LWR@customizedMathJax{%
31    \LWR@customizedMathJax%
32    \LWRrightbrace\LWRbackslash)\par%
33  }%
34 }

```

* {\<2: prefix?\>} {\<3: postfix?\>}

\LWR@mathjax@addgreek@l@up

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, lowercase upright.

```

35 \NewDocumentCommand{\LWR@mathjax@addgreek@l@up}{s m m}{
36   \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{03B1}

```

```

37 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{03B2}
38 \LWR@mathjax@addLetter{#1}{#2}{#3}{varbeta}{03D0}
39 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{03B3}
40 \LWR@mathjax@addLetter{#1}{#2}{#3}{digamma}{03DD}
41 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{03B4}
42 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{03F5}
43 \LWR@mathjax@addLetter{#1}{#2}{#3}{varepsilon}{03B5}
44 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{03B6}
45 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{03B7}
46 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{03B8}
47 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{03D1}
48 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{03B9}
49 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{03BA}
50 \LWR@mathjax@addLetter{#1}{#2}{#3}{varkappa}{03F0}
51 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{03BB}
52 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{03BC}
53 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{03BD}
54 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{03BE}
55 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{03BF}
56 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{03C0}
57 \LWR@mathjax@addLetter{#1}{#2}{#3}{varpi}{03D6}
58 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{03C1}
59 \LWR@mathjax@addLetter{#1}{#2}{#3}{varrho}{03F1}
60 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{03C3}
61 \LWR@mathjax@addLetter{#1}{#2}{#3}{varsigma}{03C2}
62 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{03C4}
63 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{03C5}
64 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{03D5}
65 \LWR@mathjax@addLetter{#1}{#2}{#3}{varphi}{03C6}
66 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{03C7}
67 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{03C8}
68 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{03C9}
69 }

```

* $\langle 2: prefix \rangle \langle 3: postfix \rangle$

\LWR@mathjax@addgreek@u@up

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, uppercase upright.

```

70 \NewDocumentCommand{\LWR@mathjax@addgreek@u@up}{s m m}{
71 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{0391}
72 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{0392}
73 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{0393}
74 \LWR@mathjax@addLetter{#1}{#2}{#3}{digamma}{03DC}
75 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{0394}
76 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{0395}
77 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{0396}
78 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{0397}
79 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{0398}
80 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{03F4}
81 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{0399}
82 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{039A}
83 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{039B}
84 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{039C}
85 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{039D}
86 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{039E}
87 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{039F}
88 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{03A0}
89 \LWR@mathjax@addLetter{#1}{#2}{#3}{varpi}{03D6}

```

```

90 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{03A1}
91 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{03A3}
92 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{03A4}
93 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{03A5}
94 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{03A6}
95 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{03A7}
96 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{03A8}
97 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{03A9}
98 }

```

* {<2: prefix>} {<3: postfix>}

\LWR@mathjax@addgreek@l@it

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, lowercase italic.

```

99 \NewDocumentCommand{\LWR@mathjax@addgreek@l@it}{s m m}{
100 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{1D6FC}
101 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{1D6FD}
102 \LWR@mathjax@addLetter{#1}{#2}{#3}{varbeta}{03D0}
103 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{1D6FE}
104 \LWR@mathjax@addLetter*{#1}{#2}{#3}{digamma}{03DD}
105 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{1D6FF}
106 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{1D716}
107 \LWR@mathjax@addLetter{#1}{#2}{#3}{varepsilon}{1D700}
108 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{1D701}
109 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{1D702}
110 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{1D703}
111 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{1D717}
112 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{1D704}
113 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{1D705}
114 \LWR@mathjax@addLetter{#1}{#2}{#3}{varkappa}{1D718}
115 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{1D706}
116 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{1D707}
117 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{1D708}
118 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{1D709}
119 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{1D70A}
120 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{1D70B}
121 \LWR@mathjax@addLetter{#1}{#2}{#3}{varpi}{1D71B}
122 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{1D70C}
123 \LWR@mathjax@addLetter{#1}{#2}{#3}{varrho}{1D71A}
124 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{1D70E}
125 \LWR@mathjax@addLetter{#1}{#2}{#3}{varsigma}{1D70D}
126 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{1D70F}
127 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{1D710}
128 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{1D719}
129 \LWR@mathjax@addLetter{#1}{#2}{#3}{varphi}{1D711}
130 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{1D712}
131 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{1D713}
132 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{1D714}
133 }

```

* {<2: prefix>} {<3: postfix>}

\LWR@mathjax@addgreek@u@it

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, uppercase italic.

```

134 \NewDocumentCommand{\LWR@mathjax@addgreek@u@it}{s m m}{
135 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{1D6E2}

```

```

136 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{1D6E3}
137 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{1D6E4}
138 \LWR@mathjax@addLetter*{#1}{#2}{#3}{digamma}{03DC}
139 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{1D6E5}
140 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{1D6E6}
141 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{1D6E7}
142 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{1D6E8}
143 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{1D6E9}
144 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{1D6F3}
145 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{1D6EA}
146 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{1D6EB}
147 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{1D6EC}
148 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{1D6ED}
149 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{1D6EE}
150 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{1D6EF}
151 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{1D6F0}
152 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{1D6F1}
153 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{1D6F2}
154 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{1D6F4}
155 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{1D6F5}
156 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{1D6F6}
157 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{1D6F7}
158 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{1D6F8}
159 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{1D6F9}
160 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{1D6FA}
161 }

```

* {<2: prefix>} {<3: postfix>}

\LWR@mathjax@addgreek@l@bfit

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, lowercase boldface italic.

```

162 \NewDocumentCommand{\LWR@mathjax@addgreek@l@bfit}{s m m}{
163   \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{1D736}
164   \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{1D737}
165   \LWR@mathjax@addLetter{#1}{#2}{#3}{varbeta}{03D0}
166   \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{1D738}
167   \LWR@mathjax@addLetter*{#1}{#2}{#3}{digamma}{03DD}
168   \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{1D739}
169   \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{1D750}
170   \LWR@mathjax@addLetter{#1}{#2}{#3}{varepsilon}{1D73A}
171   \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{1D73B}
172   \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{1D73C}
173   \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{1D73D}
174   \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{1D751}
175   \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{1D73E}
176   \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{1D73F}
177   \LWR@mathjax@addLetter{#1}{#2}{#3}{varkappa}{1D752}
178   \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{1D740}
179   \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{1D741}
180   \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{1D742}
181   \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{1D743}
182   \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{1D744}
183   \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{1D745}
184   \LWR@mathjax@addLetter{#1}{#2}{#3}{varpi}{1D755}
185   \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{1D746}
186   \LWR@mathjax@addLetter{#1}{#2}{#3}{varrho}{1D754}
187   \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{1D748}
188   \LWR@mathjax@addLetter{#1}{#2}{#3}{varsigma}{1D747}

```

```

189 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{1D749}
190 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{1D74A}
191 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{1D753}
192 \LWR@mathjax@addLetter{#1}{#2}{#3}{varphi}{1D74B}
193 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{1D74C}
194 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{1D74D}
195 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{1D74E}
196 }

```

* {<2: prefix>} {<3: postfix>}

\LWR@mathjax@addgreek@u@bfit

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, uppercase boldface italic.

```

197 \NewDocumentCommand{\LWR@mathjax@addgreek@u@bfit}{s m m}{
198 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{1D71C}
199 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{1D71D}
200 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{1D71E}
201 \LWR@mathjax@addLetter*{#1}{#2}{#3}{digamma}{03DC}
202 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{1D71F}
203 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{1D720}
204 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{1D721}
205 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{1D722}
206 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{1D723}
207 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{1D72D}
208 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{1D724}
209 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{1D725}
210 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{1D726}
211 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{1D727}
212 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{1D728}
213 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{1D729}
214 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{1D72A}
215 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{1D72B}
216 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{1D72C}
217 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{1D72E}
218 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{1D72F}
219 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{1D730}
220 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{1D731}
221 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{1D732}
222 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{1D733}
223 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{1D734}
224 }

```

\LWR@mathjax@addgreek@u@bfup is not needed.

* {<2: prefix>} {<3: postfix>}

\LWR@mathjax@addgreek@u@bfup

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, uppercase boldface upright.

```

225 \NewDocumentCommand{\LWR@mathjax@addgreek@u@bfup}{s m m}{
226 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{1D6A8}
227 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{1D6A9}
228 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{1D6AA}
229 \LWR@mathjax@addLetter*{#1}{#2}{#3}{digamma}{03DC}
230 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{1D6AB}
231 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{1D6AC}
232 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{1D6AD}

```

```

233 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{1D6AE}
234 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{1D6AF}
235 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{1D6B9}
236 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{1D6B0}
237 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{1D6B1}
238 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{1D6B2}
239 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{1D6B3}
240 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{1D6B4}
241 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{1D6B5}
242 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{1D6B6}
243 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{1D6B7}
244 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{1D6B8}
245 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{1D6BA}
246 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{1D6BB}
247 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{1D6BC}
248 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{1D6BD}
249 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{1D6BE}
250 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{1D6BF}
251 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{1D6C0}
252 }

```

{\prefix}

`\LWR@mathjax@addLatin@u@bfit`

Adds `\CustomizeMathjax` expressions to define a set of macros for bold-face italic Latin letters, uppercase and lowercase.

```

253 \NewDocumentCommand{\LWR@mathjax@addLatin@u@bfit}{m}{
254   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{A}{1D468}
255   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{B}{1D469}
256   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{C}{1D46A}
257   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{D}{1D46B}
258   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{E}{1D46C}
259   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{F}{1D46D}
260   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{G}{1D46E}
261   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{H}{1D46F}
262   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{I}{1D470}
263   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{J}{1D471}
264   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{K}{1D472}
265   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{L}{1D473}
266   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{M}{1D474}
267   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{N}{1D475}
268   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{O}{1D476}
269   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{P}{1D477}
270   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{Q}{1D478}
271   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{R}{1D479}
272   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{S}{1D47A}
273   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{T}{1D47B}
274   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{U}{1D47C}
275   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{V}{1D47D}
276   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{W}{1D47E}
277   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{X}{1D47F}
278   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{Y}{1D480}
279   \LWR@mathjax@addLetter{\BooleanFalse}{#1}{Z}{1D481}
280 }

```

{\prefix}

`\LWR@mathjax@addLatin@l@bfit`

Adds `\CustomizeMathjax` expressions to define a set of macros for bold-face italic Latin letters, uppercase and lowercase.

```

281 \NewDocumentCommand{\LWR@mathjax@addLatin@l@bfit}{m}{

```

```

282 \LWR@mathjax@addletter{\BooleanFalse}{#1}{a}{1D482}
283 \LWR@mathjax@addletter{\BooleanFalse}{#1}{b}{1D483}
284 \LWR@mathjax@addletter{\BooleanFalse}{#1}{c}{1D484}
285 \LWR@mathjax@addletter{\BooleanFalse}{#1}{d}{1D485}
286 \LWR@mathjax@addletter{\BooleanFalse}{#1}{e}{1D486}
287 \LWR@mathjax@addletter{\BooleanFalse}{#1}{f}{1D487}
288 \LWR@mathjax@addletter{\BooleanFalse}{#1}{g}{1D488}
289 \LWR@mathjax@addletter{\BooleanFalse}{#1}{h}{1D489}
290 \LWR@mathjax@addletter{\BooleanFalse}{#1}{i}{1D48A}
291 \LWR@mathjax@addletter{\BooleanFalse}{#1}{j}{1D48B}
292 \LWR@mathjax@addletter{\BooleanFalse}{#1}{k}{1D48C}
293 \LWR@mathjax@addletter{\BooleanFalse}{#1}{l}{1D48D}
294 \LWR@mathjax@addletter{\BooleanFalse}{#1}{m}{1D48E}
295 \LWR@mathjax@addletter{\BooleanFalse}{#1}{n}{1D48F}
296 \LWR@mathjax@addletter{\BooleanFalse}{#1}{o}{1D490}
297 \LWR@mathjax@addletter{\BooleanFalse}{#1}{p}{1D491}
298 \LWR@mathjax@addletter{\BooleanFalse}{#1}{q}{1D492}
299 \LWR@mathjax@addletter{\BooleanFalse}{#1}{r}{1D493}
300 \LWR@mathjax@addletter{\BooleanFalse}{#1}{s}{1D494}
301 \LWR@mathjax@addletter{\BooleanFalse}{#1}{t}{1D495}
302 \LWR@mathjax@addletter{\BooleanFalse}{#1}{u}{1D496}
303 \LWR@mathjax@addletter{\BooleanFalse}{#1}{v}{1D497}
304 \LWR@mathjax@addletter{\BooleanFalse}{#1}{w}{1D498}
305 \LWR@mathjax@addletter{\BooleanFalse}{#1}{x}{1D499}
306 \LWR@mathjax@addletter{\BooleanFalse}{#1}{y}{1D49A}
307 \LWR@mathjax@addletter{\BooleanFalse}{#1}{z}{1D49B}
308 }

309 \end{warpMathJax}

```

File 586 **lwarp-common-mathjax-newpctxmath.sty**

§ 695 Package **common-mathjax-newpctxmath**

(Emulates or patches code by MICHAEL SHARPE.)

Pkg Common code used by newpctxmath, newtxmath, and newtxsf for MATHJAX.

lwarp-common-mathjax-newpctxmath
for HTML output: 1 \ProvidesPackage{lwarp-common-mathjax-newpctxmath}[2020/09/20]

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-nonunicode}
3 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
4
5 \begin{warpMathJax}
6 \CustomizeMathJax{\newcommand{\fAlt}{f}}
7 \CustomizeMathJax{\newcommand{\rhoAlt}{\rho}}
8
9 \CustomizeMathJax{\newcommand{\imathscr}{\mathord{\mathscr{i}}}}
10 \CustomizeMathJax{\newcommand{\jmathscr}{\mathord{\mathscr{j}}}}

```

lwarp_mathjax.txt adds \left/\right support for delimiters.

```

11 \CustomizeMathJax{\let\llbracket\lBrack}
12 \CustomizeMathJax{\let\rrbracket\rBrack}

```

```

13
14 \CustomizeMathJax{\let\smlbrace\{}}
15 \CustomizeMathJax{\let\smrbrace\}}
16 \CustomizeMathJax{\newcommand{\Perp}{\mathrel{\unicode{x02AEB}}}}
17 \CustomizeMathJax{\newcommand{\nPerp}{\mathrel{\not{\!\unicode{x02AEB}}}}}
18 \CustomizeMathJax{\newcommand{\Zbar}{\mathord{\unicode{x01B5}}}}
19 \CustomizeMathJax{\newcommand{\Angstrom}{\mathord{\unicode{x212B}}}}
20 \CustomizeMathJax{\newcommand{\Euler}{\mathord{\unicode{x2107}}}}
21 \CustomizeMathJax{\newcommand{\transp}{\mathord{\unicode{xFF34}}}}
22 \CustomizeMathJax{\newcommand{\hermtransp}{\mathord{\unicode{xFF28}}}}
23 \CustomizeMathJax{\let\htransp=\hermtransp}
24 \CustomizeMathJax{\newcommand{\circledplus}{\mathbin{\unicode{x2295}}}}
25 \CustomizeMathJax{\newcommand{\circledminus}{\mathbin{\unicode{x2296}}}}
26 \CustomizeMathJax{\newcommand{\circledtimes}{\mathbin{\unicode{x2297}}}}

27 \CustomizeMathJax{\newcommand{\circledslash}{\mathbin{\unicode{x2298}}}}
28 %
29 \CustomizeMathJax{\newcommand{\circleddot}{\mathbin{\unicode{x2299}}}}
30 \CustomizeMathJax{\let\overgroup\overparen}
31 \CustomizeMathJax{\let\overgrouppra\overrightarrow}
32 \CustomizeMathJax{\let\undergroup\underparen}
33 \CustomizeMathJax{\let\undergrouppla\underleftarrow}
34 \CustomizeMathJax{\newcommand{\widering}[1]{%
35   \stackrel{\unicode{x2218}}{\overgroup{#1}}%
36 }}
37 \CustomizeMathJax{\let\widearc\overparen}
38 \CustomizeMathJax{\let\wideOarc\overrightarrow}
39 \CustomizeMathJax{\newcommand{\LWRvstar}[2]{\overrightarrow{#1}_{#2}}}
40 \CustomizeMathJax{\newcommand{\vv}{\ifstar\LWRvstar\overrightarrow}}
41 %
42 \CustomizeMathJax{\let\smallintsl\smallint}
43 \CustomizeMathJax{\newcommand{\smalliintsl}{\mathop{\unicode{x222C}}\limits}}
44 \CustomizeMathJax{\newcommand{\smalliiintsl}{\mathop{\unicode{x222D}}\limits}}
45 \CustomizeMathJax{\newcommand{\smalliiiintsl}{\mathop{\unicode{x2A0C}}\limits}}
46 \CustomizeMathJax{\newcommand{\smallointsl}{\mathop{\unicode{x222E}}\limits}}
47 \CustomizeMathJax{\newcommand{\smallloointsl}{\mathop{\unicode{x222F}}\limits}}
48 \CustomizeMathJax{\newcommand{\smalllooiintsl}{\mathop{\unicode{x2230}}\limits}}
49 \CustomizeMathJax{\newcommand{\smallvarointclockwisel}{%
50   \mathop{\unicode{x2232}}\limits%
51 }}
52 \CustomizeMathJax{\newcommand{\smalllointctrclockwisel}{%
53   \mathop{\unicode{x2233}}\limits%
54 }}
55 \CustomizeMathJax{\newcommand{\smallsumintsl}{\mathop{\unicode{x2A0B}}\limits}}
56 \CustomizeMathJax{\newcommand{\smallfintsl}{\mathop{\unicode{x2A0F}}\limits}}
57 \CustomizeMathJax{\newcommand{\smallsqintsl}{\mathop{\unicode{x2A16}}\limits}}
58 %
59 \CustomizeMathJax{\let\smallintup\smallint}
60 \CustomizeMathJax{\newcommand{\smalliintup}{\mathop{\unicode{x222C}}\limits}}
61 \CustomizeMathJax{\newcommand{\smalliiintup}{\mathop{\unicode{x222D}}\limits}}
62 \CustomizeMathJax{\newcommand{\smalliiiintup}{\mathop{\unicode{x2A0C}}\limits}}
63 \CustomizeMathJax{\newcommand{\smallointup}{\mathop{\unicode{x222E}}\limits}}
64 \CustomizeMathJax{\newcommand{\smallloointup}{\mathop{\unicode{x222F}}\limits}}
65 \CustomizeMathJax{\newcommand{\smalllooiintup}{\mathop{\unicode{x2230}}\limits}}
66 \CustomizeMathJax{\newcommand{\smallvarointclockwiseup}{%
67   \mathop{\unicode{x2232}}\limits%
68 }}
69 \CustomizeMathJax{\newcommand{\smalllointctrclockwiseup}{%
70   \mathop{\unicode{x2233}}\limits%
71 }}

```

```

72 \CustomizeMathJax{\newcommand{\smallsumintup}{\mathop{\unicode{x2A0B}}\limits}}
73 \CustomizeMathJax{\newcommand{\smallfintup}{\mathop{\unicode{x2A0F}}\limits}}
74 \CustomizeMathJax{\newcommand{\smallsqintup}{\mathop{\unicode{x2A16}}\limits}}
75 %
76 \CustomizeMathJax{\newcommand{\iint}{\mathop{\unicode{x222C}}\limits}}
77 \CustomizeMathJax{\newcommand{\iiint}{\mathop{\unicode{x222D}}\limits}}
78 \CustomizeMathJax{\newcommand{\iiiint}{\mathop{\unicode{x2A0C}}\limits}}
79 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
80 \CustomizeMathJax{\newcommand{\oiiint}{\mathop{\unicode{x2230}}\limits}}
81 \CustomizeMathJax{\newcommand{\varointclockwise}{\mathop{\unicode{x2232}}\limits}}
82 \CustomizeMathJax{\newcommand{\ointctrlockwise}{\mathop{\unicode{x2233}}\limits}}
83 \CustomizeMathJax{\newcommand{\sumint}{\mathop{\unicode{x2A0B}}\limits}}
84 \CustomizeMathJax{\newcommand{\fint}{\mathop{\unicode{x2A0F}}\limits}}
85 \CustomizeMathJax{\newcommand{\sqint}{\mathop{\unicode{x2A16}}\limits}}
86 %
87 \CustomizeMathJax{\let\intsl\int}
88 \CustomizeMathJax{\newcommand{\iintsl}{\mathop{\unicode{x222C}}\limits}}
89 \CustomizeMathJax{\newcommand{\iiintsl}{\mathop{\unicode{x222D}}\limits}}
90 \CustomizeMathJax{\newcommand{\iiiintsl}{\mathop{\unicode{x2A0C}}\limits}}
91 \CustomizeMathJax{\let\ointsl\oint}
92 \CustomizeMathJax{\newcommand{\oiintsl}{\mathop{\unicode{x222F}}\limits}}
93 \CustomizeMathJax{\newcommand{\oiiintsl}{\mathop{\unicode{x2230}}\limits}}
94 \CustomizeMathJax{\newcommand{\varointclockwisel}{\mathop{\unicode{x2232}}\limits}}
95 \CustomizeMathJax{\newcommand{\ointctrlockwisel}{\mathop{\unicode{x2233}}\limits}}
96 \CustomizeMathJax{\newcommand{\sumintsl}{\mathop{\unicode{x2A0B}}\limits}}
97 \CustomizeMathJax{\newcommand{\fintsl}{\mathop{\unicode{x2A0F}}\limits}}
98 \CustomizeMathJax{\newcommand{\sqintsl}{\mathop{\unicode{x2A16}}\limits}}
99 %
100 \CustomizeMathJax{\let\intup\int}
101 \CustomizeMathJax{\newcommand{\iintup}{\mathop{\unicode{x222C}}\limits}}
102 \CustomizeMathJax{\newcommand{\iiintup}{\mathop{\unicode{x222D}}\limits}}
103 \CustomizeMathJax{\newcommand{\iiiintup}{\mathop{\unicode{x2A0C}}\limits}}
104 \CustomizeMathJax{\let\ointup\oint}
105 \CustomizeMathJax{\newcommand{\oiintup}{\mathop{\unicode{x222F}}\limits}}
106 \CustomizeMathJax{\newcommand{\oiiintup}{\mathop{\unicode{x2230}}\limits}}
107 \CustomizeMathJax{\newcommand{\varointclockwiseup}{%
108   \mathop{\unicode{x2232}}\limits}%
109 }}
110 \CustomizeMathJax{\newcommand{\ointctrlockwiseup}{%
111   \mathop{\unicode{x2233}}\limits}%
112 }}
113 \CustomizeMathJax{\newcommand{\sumintup}{\mathop{\unicode{x2A0B}}\limits}}
114 \CustomizeMathJax{\newcommand{\fintup}{\mathop{\unicode{x2A0F}}\limits}}
115 \CustomizeMathJax{\newcommand{\sqintup}{\mathop{\unicode{x2A16}}\limits}}
116 %
117 \CustomizeMathJax{\newcommand{\bigcupdot}{\mathop{\unicode{x2A03}}}}
118 \CustomizeMathJax{\newcommand{\bigcupplus}{\mathop{\unicode{x2A04}}}}
119 \CustomizeMathJax{\newcommand{\bigsqcap}{\mathop{\unicode{x2A05}}}}
120 %
121 %
122 \CustomizeMathJax{\newcommand{\bigtimes}{\mathop{\unicode{x2A09}}}}
123 \CustomizeMathJax{\let\varprod\bigtimes}
124 %
125 \CustomizeMathJax{\newcommand{\mappedfrom}{\mathrel{\unicode{x021A4}}}}
126 \CustomizeMathJax{\let\mappedfromchar\mappedfrom}
127 \CustomizeMathJax{\newcommand{\mapsfrom}{\mathrel{\unicode{x021A4}}}}
128 \CustomizeMathJax{\newcommand{\longmappedfrom}{\mathrel{\unicode{x027FB}}}}

```

```

129 %
130 \CustomizeMathJax{\newcommand{\Mapsto}{\mathrel{\unicode{x02907}}}}
131 \CustomizeMathJax{\let\Mapstochar\Mapsto}
132 \CustomizeMathJax{\newcommand{\Longmapsto}{\mathrel{\unicode{x027FE}}}}
133 \CustomizeMathJax{\newcommand{\Mappedfrom}{\mathrel{\unicode{x02906}}}}
134 \CustomizeMathJax{\let\Mappedfromchar\Mappedfrom}
135 \CustomizeMathJax{\newcommand{\Mapsfrom}{\mathrel{\unicode{x02906}}}}
136 \CustomizeMathJax{\newcommand{\Longmappedfrom}{\mathrel{\unicode{x27FD}}}}
137 %

138 \CustomizeMathJax{\newcommand{\medcirc}{\mathbin{\unicode{x025CB}}}}
139 \CustomizeMathJax{\newcommand{\medbullet}{\mathbin{\unicode{x025CF}}}}
140 \CustomizeMathJax{\newcommand{\varparallel}{\mathrel{\unicode{x02AFD}}}}
141 \CustomizeMathJax{\newcommand{\varparallelinv}{\mathrel{\unicode{x244A}}}}
142 \CustomizeMathJax{\newcommand{\nvarparallel}{%
143   \mathrel{\LWROverlaysymbols{-}{\unicode{x02AFD}}}}%
144 }}
145 \CustomizeMathJax{\newcommand{\nvarparallelinv}{%
146   \mathrel{\LWROverlaysymbols{-}{\unicode{x244A}}}}%
147 }}
148 %

149 \CustomizeMathJax{\newcommand{\coloneq}{\mathrel{\unicode{x02254}}}}
150 \CustomizeMathJax{\newcommand{\eqcolon}{\mathrel{\unicode{x02255}}}}
151 %
152 \CustomizeMathJax{\newcommand{\VDash}{\mathrel{\unicode{x22AB}}}}

153 %
154 \CustomizeMathJax{\newcommand{\preceqq}{\mathrel{\unicode{x02AB3}}}}
155 \CustomizeMathJax{\newcommand{\succeqq}{\mathrel{\unicode{x02AB4}}}}
156 %
157
158 \CustomizeMathJax{\newcommand{\nprecsim}{%
159   \mathrel{\LWROverlaysymbols{/}{\unicode{x0227E}}}}%
160 }}
161 \CustomizeMathJax{\newcommand{\nsucsim}{%
162   \mathrel{\LWROverlaysymbols{/}{\unicode{x0227F}}}}%
163 }}
164 \CustomizeMathJax{\newcommand{\nlessim}{\mathrel{\unicode{x02274}}}}
165 \CustomizeMathJax{\newcommand{\ngtrsim}{\mathrel{\unicode{x02275}}}}
166 %

167 \CustomizeMathJax{\newcommand{\nsubset}{\mathrel{\unicode{x02284}}}}
168 \CustomizeMathJax{\newcommand{\nsupset}{\mathrel{\unicode{x02285}}}}
169 \CustomizeMathJax{\newcommand{\notni}{\mathrel{\unicode{x220C}}}}
170 \CustomizeMathJax{\let\notowns\notni}
171 %
172 \CustomizeMathJax{\newcommand{\nlessapprox}{%
173   \mathrel{\LWROverlaysymbols{/}{\unicode{x02A85}}}}%
174 }}
175 \CustomizeMathJax{\newcommand{\ngtrapprox}{%
176   \mathrel{\LWROverlaysymbols{/}{\unicode{x02A86}}}}%
177 }}
178 %
179 \CustomizeMathJax{\newcommand{\npreccurlyeq}{%
180   \mathrel{\LWROverlaysymbols{/}{\unicode{x0227C}}}}%
181 }}

```

```

182 \CustomizeMathJax{\newcommand{\succcurlyeq}{%
183   \mathrel{\LWOverlaysymbols{/}{\unicode{x0227D}}}%
184 }}
185 \CustomizeMathJax{\newcommand{\ngtrless}{\mathrel{\unicode{x02279}}}}
186 \CustomizeMathJax{\newcommand{\nlessgtr}{\mathrel{\unicode{x2278}}}}
187 \CustomizeMathJax{\newcommand{\nbumpeq}{%
188   \mathrel{\LWOverlaysymbols{/}{\unicode{x0224F}}}%
189 }}
190 \CustomizeMathJax{\newcommand{\nBumpeq}{%
191   \mathrel{\LWOverlaysymbols{/}{\unicode{x0224E}}}%
192 }}
193 %
194 \CustomizeMathJax{\newcommand{\nbacksim}{%
195   \mathrel{\LWOverlaysymbols{/}{\unicode{x0223D}}}%
196 }}
197 \CustomizeMathJax{\newcommand{\nbacksimeq}{%
198   \mathrel{\LWOverlaysymbols{/}{\unicode{x022CD}}}%
199 }}
200 \CustomizeMathJax{\newcommand{\nasymp}{\mathrel{\unicode{x226D}}}}
201 \CustomizeMathJax{\newcommand{\nequiv}{\mathrel{\unicode{x2262}}}}
202 \CustomizeMathJax{\newcommand{\napprox}{\mathrel{\unicode{x2249}}}}
203 %
204 \CustomizeMathJax{\newcommand{\nll}{%
205   \mathrel{\LWOverlaysymbols{/}{\unicode{x0226A}}}%
206 }}
207 \CustomizeMathJax{\newcommand{\ngg}{%
208   \mathrel{\LWOverlaysymbols{/}{\unicode{x0226B}}}%
209 }}
210 \CustomizeMathJax{\newcommand{\nthickapprox}{%
211   \mathrel{\LWOverlaysymbols{/}{\mathbf{\unicode{x02248}}}}}%
212 }}
213 \CustomizeMathJax{\newcommand{\napproxeq}{%
214   \mathrel{\LWOverlaysymbols{/}{\unicode{x0224A}}}%
215 }}
216 \CustomizeMathJax{\newcommand{\nprecapprox}{%
217   \mathrel{\LWOverlaysymbols{/}{\unicode{x02AB7}}}%
218 }}
219 \CustomizeMathJax{\newcommand{\nsuccapprox}{%
220   \mathrel{\LWOverlaysymbols{/}{\unicode{x02AB8}}}%
221 }}
222 \CustomizeMathJax{\newcommand{\npreceqq}{%
223   \mathrel{\LWOverlaysymbols{/}{\unicode{x02AB3}}}%
224 }}
225 \CustomizeMathJax{\newcommand{\nsucceqq}{%
226   \mathrel{\LWOverlaysymbols{/}{\unicode{x02AB4}}}%
227 }}
228 \CustomizeMathJax{\newcommand{\nsimeq}{\mathrel{\unicode{x02244}}}}
229 %
230 \CustomizeMathJax{\newcommand{\nSubset}{%
231   \mathrel{\LWOverlaysymbols{/}{\unicode{x022D0}}}%
232 }}
233 \CustomizeMathJax{\newcommand{\nSupset}{%
234   \mathrel{\LWOverlaysymbols{/}{\unicode{x022D1}}}%
235 }}
236 \CustomizeMathJax{\newcommand{\nqssubseteq}{\mathrel{\unicode{x022E2}}}}
237 \CustomizeMathJax{\newcommand{\nqsupseteq}{\mathrel{\unicode{x022E3}}}}
238 %
239 \CustomizeMathJax{\newcommand{\coloneqq}{\mathrel{\unicode{x02254}}}}
240 \CustomizeMathJax{\newcommand{\eqqcolon}{\mathrel{\unicode{x02255}}}}
241 \CustomizeMathJax{\newcommand{\Coloneqq}{\mathrel{\unicode{x02A74}}}}

```

```

242 \CustomizeMathJax{\newcommand{\Coloneq}{\mathrel{\unicode{x2237}-}}}
243 \CustomizeMathJax{\newcommand{\Eqcolon}{\mathrel{-\unicode{x2237}}}}
244 %
245 \CustomizeMathJax{\newcommand{\lvec}[1]{%
246   \mathord{\overset{\unicode{x02190}}{#1}}%
247 }}
248 \CustomizeMathJax{\newcommand{\rvec}[1]{%
249   \mathord{\overset{\unicode{x2194}}{#1}}%
250 }}
251 \CustomizeMathJax{\newcommand{\harpoonacc}[1]{%
252   \mathord{\overset{\unicode{x021C0}}{#1}}%
253 }}
254 \CustomizeMathJax{\newcommand{\lharpoonacc}[1]{%
255   \mathord{\overset{\unicode{x021BC}}{#1}}%
256 }}
257 \CustomizeMathJax{\newcommand{\rharpoonacc}[1]{%
258   \mathord{\overset{\unicode{x0294E}}{#1}}%
259 }}
260 \CustomizeMathJax{\newcommand{\barbar}[1]{\mathord{\overset{=}{#1}}}}
261 \CustomizeMathJax{\newcommand{\bartilde}[1]{\mathord{\overset{\simeq}{#1}}}}
262 \CustomizeMathJax{\newcommand{\barhat}[1]{\mathord{\hat{\bar{#1}}}}}
263 \CustomizeMathJax{\newcommand{\tildebar}[1]{\mathord{\overset{\eqsim}{#1}}}}
264 \CustomizeMathJax{\newcommand{\tildetilde}[1]{\mathord{\overset{\approx}{#1}}}}
265 \CustomizeMathJax{\newcommand{\tildehat}[1]{\mathord{\hat{\tilde{#1}}}}}
266 \CustomizeMathJax{\newcommand{\hatbar}[1]{\mathord{\bar{\hat{#1}}}}}
267 \CustomizeMathJax{\newcommand{\hattilde}[1]{\mathord{\tilde{\hat{#1}}}}}
268 \CustomizeMathJax{\newcommand{\hathat}[1]{\mathord{\hat{\hat{#1}}}}}
269
270 \CustomizeMathJax{\newcommand{\cdotB}{\mathord{\boldsymbol{\cdot}}}}
271 \CustomizeMathJax{\newcommand{\cdotBB}{\mathord{\unicode{x2022}}}}
272 \CustomizeMathJax{\newcommand{\circS}{\boldsymbol{\circ}}}
273 \CustomizeMathJax{\newcommand{\bulletSSS}{\bullet}}
274 \CustomizeMathJax{\newcommand{\bulletSS}{\mathord{\unicode{x025CF}}}}
275 \CustomizeMathJax{\newcommand{\bulletS}{\mathord{\unicode{x02B24}}}}
276 \CustomizeMathJax{\newcommand{\primeS}{\prime}}
277
278 \CustomizeMathJax{\newcommand{\invamp}{\mathbin{\unicode{x0214B}}}}

```

lwarp_mathjax.txt adds \left/\right support for delimiters.

```

279 \CustomizeMathJax{\newcommand{\Lbag}{\mathopen{\large\unicode{x027C5}}}}
280 \CustomizeMathJax{\newcommand{\Rbag}{\mathclose{\large\unicode{x027C6}}}}
281 \CustomizeMathJax{\newcommand{\circledless}{\mathrel{\unicode{x029C0}}}}
282 \CustomizeMathJax{\newcommand{\circledgtr}{\mathrel{\unicode{x029C1}}}}
283 \CustomizeMathJax{\newcommand{\circledbslash}{\mathbin{\unicode{x029B8}}}}

284 \CustomizeMathJax{\newcommand{\lJoin}{\mathrel{\unicode{x22C9}}}}
285 \CustomizeMathJax{\newcommand{\rJoin}{\mathrel{\unicode{x22CA}}}}
286 \CustomizeMathJax{\newcommand{\lrJoin}{\mathrel{\unicode{x2A1D}}}}
287
288 \CustomizeMathJax{\newcommand{\lRtimes}{\mathrel{\unicode{x2A1D}}}}
289 \CustomizeMathJax{\newcommand{\Diamondblack}{\mathord{\unicode{x025C6}}}}
290 \CustomizeMathJax{\newcommand{\nplus}{%
291   \mathrel{\LWRoverlaysymbols+}{\unicode{x02229}}}%
292 }}
293 \CustomizeMathJax{\newcommand{\nsqsubset}{%
294   \mathrel{\LWRoverlaysymbols/}{\unicode{x0228F}}}%
295 }}
296 \CustomizeMathJax{\newcommand{\nsqsupset}{%

```

```

297 \mathrel{\LWOverlaysymbols{/}{\unicode{x02290}}}%
298 }}
299 \CustomizeMathJax{\newcommand{\dasharrow}{\mathrel{\unicode{x021E2}}}}
300 \CustomizeMathJax{\newcommand{\leftsquigarrow}{\mathrel{\unicode{x021DC}}}}
301 \CustomizeMathJax{\newcommand{\twoheadrightarrow}{\mathrel{\unicode{x02900}}}}
302 \CustomizeMathJax{\newcommand{\twoheadleftarrow}{\mathrel{\unicode{x02B34}}}}
303 \CustomizeMathJax{\newcommand{\boxast}{\mathbin{\unicode{x029C6}}}}
304 \CustomizeMathJax{\newcommand{\boxslash}{\mathbin{\unicode{x29C5}}}}
305 \CustomizeMathJax{\newcommand{\boxbar}{\mathbin{\unicode{x025EB}}}}
306 \CustomizeMathJax{\newcommand{\boxslash}{\mathbin{\unicode{x029C4}}}}
307
308 \CustomizeMathJax{\newcommand{\varclubsuit}{\mathord{\unicode{x02667}}}}
309 \CustomizeMathJax{\newcommand{\vardiamondsuit}{\mathord{\unicode{x02666}}}}
310 \CustomizeMathJax{\newcommand{\varheartsuit}{\mathord{\unicode{x02665}}}}
311 \CustomizeMathJax{\newcommand{\varspadesuit}{\mathord{\unicode{x02664}}}}
312
313 \CustomizeMathJax{\newcommand{\Nearrow}{\mathrel{\unicode{x021D7}}}}
314 \CustomizeMathJax{\newcommand{\Searrow}{\mathrel{\unicode{x021D8}}}}
315 \CustomizeMathJax{\newcommand{\Nwarrow}{\mathrel{\unicode{x021D6}}}}
316 \CustomizeMathJax{\newcommand{\Swarrow}{\mathrel{\unicode{x021D9}}}}
317 \CustomizeMathJax{\newcommand{\Top}{\mathord{\unicode{x02AEA}}}}
318 \CustomizeMathJax{\newcommand{\Bot}{\mathord{\unicode{x02AEB}}}}
319
320 \CustomizeMathJax{\newcommand{\leadstoext}{\mathrel{\unicode{x02294}}}}
321
322 \CustomizeMathJax{\newcommand{\sqcupplus}{%
323 \mathbin{\LWOverlaysymbols{+}{\unicode{x02294}}}%
324 }}
325 \CustomizeMathJax{\newcommand{\sqcapplus}{%
326 \mathbin{\LWOverlaysymbols{+}{\unicode{x02293}}}%
327 }}
328
329 \CustomizeMathJax{\newcommand{\dlb}{\mathopen{\unicode{x027E6}}}}
330 \CustomizeMathJax{\newcommand{\drb}{\mathopen{\unicode{x027E7}}}}
331
332 \CustomizeMathJax{\newcommand{\varg}{g}}
333 \CustomizeMathJax{\newcommand{\vary}{y}}
334 \CustomizeMathJax{\newcommand{\varv}{v}}
335 \CustomizeMathJax{\newcommand{\varw}{w}}
336
337 \CustomizeMathJax{\newcommand{\nexistsAlt}{\mathord{\unicode{x02204}}}}
338 \CustomizeMathJax{\newcommand{\existsAlt}{\mathord{\unicode{x02203}}}}
339 \CustomizeMathJax{\newcommand{\forallAlt}{\mathord{\unicode{x02200}}}}
340 \CustomizeMathJax{\newcommand{\emptysetAlt}{\mathord{\unicode{x02205}}}}
341
342 \CustomizeMathJax{\newcommand{\uppartial}{%
343 \mathord{\unicode{x02202}}%
344 }}% not upright
345
346 \CustomizeMathJax{\let\varmathbb\mathbb}
347 \CustomizeMathJax{\let\vmathbb\mathbb}
348 \CustomizeMathJax{\let\vvmathbb\mathbb}
349
350 \CustomizeMathJax{\let\smallprod\prod}
351 \CustomizeMathJax{\let\smallsum\sum}
352 \CustomizeMathJax{\let\smallcoprod\coprod}
353
354 \CustomizeMathJax{\newcommand{\openbox}{\mathord{\unicode{x25FD}}}}
355 \CustomizeMathJax{\let\textsquare\openbox}

```

```

356 \CustomizeMathJax{\let\varepsilon\emptyset}
357 %
358 % for newpxmath:
359 \CustomizeMathJax{\newcommand{\mathsterling}{\mathord{\unicode{x000A3}}}}
360 \CustomizeMathJax{\newcommand{\mathcent}{\mathord{\unicode{x000A2}}}}
361
362 \end{warpMathJax}

```

File 587 **lwarp-common-mathjax-nonunicode.sty**

§ 696 Package **common-mathjax-nonunicode**

(Emulates or patches code by DANIEL FLIPO, MICHAEL SHARPE.)

Pkg Common code used by newpxmath, newtxmath, newtxsf, kpfonts-otf for MATH-
lwarp-common-mathjax-nonunicode. These are symbols not found in UNICODE.

Factored from lwarp-common-mathjax-newpctxmath.

for HTML output: 1 \ProvidesPackage{lwarp-common-mathjax-nonunicode}[2020/09/20]

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
3
4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\mmapsto}{\mathrel{\unicode{x021A6}}}}
6 \CustomizeMathJax{\let\mmapstochar\mmapsto}
7 \CustomizeMathJax{\newcommand{\longmmapsto}{\mathrel{\unicode{x021A6}}}}
8 \CustomizeMathJax{\newcommand{\mmappedfrom}{\mathrel{\unicode{x021A4}}}}
9 \CustomizeMathJax{\let\mmappedfromchar\mmappedfrom}
10 \CustomizeMathJax{\newcommand{\longmmappedfrom}{\mathrel{\unicode{x021A4}}}}
11 \CustomizeMathJax{\let\mmapsfrom\mmappedfrom}% from kpfonts-otf
12 \CustomizeMathJax{\let\longmmapsfrom\longmmappedfrom}% from kpfonts-otf
13
14 \CustomizeMathJax{\newcommand{\Mmapsto}{\mathrel{\unicode{x02907}}}}
15 \CustomizeMathJax{\let\Mmapstochar\Mmapsto}
16 \CustomizeMathJax{\newcommand{\Longmmapsto}{\mathrel{\unicode{x027FE}}}}
17 \CustomizeMathJax{\newcommand{\Mmappedfrom}{\mathrel{\unicode{x02906}}}}
18 \CustomizeMathJax{\let\Mmappedfromchar\Mmappedfrom}
19 \CustomizeMathJax{\newcommand{\Longmmappedfrom}{\mathrel{\unicode{x027FD}}}}
20 \CustomizeMathJax{\let\Mmapsfrom\Mmappedfrom}% from kpfonts-otf
21 \CustomizeMathJax{\let\Longmmapsfrom\Longmmappedfrom}% from kpfonts-otf
22 %
23 \CustomizeMathJax{\newcommand{\boxright}{%
24   \mathrel{\unicode{x025A1}\!\!\unicode{x02192}}%
25 }}
26 \CustomizeMathJax{\newcommand{\boxleft}{%
27   \mathrel{\unicode{x02190}\!\!\unicode{x025A1}}%
28 }}
29 \CustomizeMathJax{\newcommand{\boxdotright}{%
30   \mathrel{\unicode{x022A1}\!\!\unicode{x02192}}%
31 }}
32 \CustomizeMathJax{\newcommand{\boxdotleft}{%
33   \mathrel{\unicode{x02190}\!\!\unicode{x022A1}}%
34 }}
35

```

```

36 \CustomizeMathJax{\newcommand{\Diamondright}{%
37   \mathrel{\unicode{x025C7}\!\unicode{x02192}}%
38 }}
39 \CustomizeMathJax{\newcommand{\Diamondleft}{%
40   \mathrel{\unicode{x02190}\!\unicode{x025C7}}%
41 }}
42 \CustomizeMathJax{\newcommand{\Diamonddotright}{%
43   \mathrel{\unicode{x027D0}\!\unicode{x02192}}%
44 }}
45 \CustomizeMathJax{\newcommand{\Diamonddotleft}{%
46   \mathrel{\unicode{x02190}\!\unicode{x027D0}}%
47 }}
48
49 \CustomizeMathJax{\newcommand{\boxRight}{%
50   \mathrel{\unicode{x025A1}\!\unicode{x021D2}}%
51 }}
52 \CustomizeMathJax{\newcommand{\boxLeft}{%
53   \mathrel{\unicode{x021D0}\!\unicode{x025A1}}%
54 }}
55 \CustomizeMathJax{\newcommand{\boxdotRight}{%
56   \mathrel{\unicode{x022A1}\!\unicode{x021D2}}%
57 }}
58 \CustomizeMathJax{\newcommand{\boxdotLeft}{%
59   \mathrel{\unicode{x021D0}\!\unicode{x022A1}}%
60 }}
61
62 \CustomizeMathJax{\newcommand{\DiamondRight}{%
63   \mathrel{\unicode{x025C7}\!\unicode{x021D2}}%
64 }}
65 \CustomizeMathJax{\newcommand{\DiamondLeft}{%
66   \mathrel{\unicode{x021D0}\!\unicode{x025C7}}%
67 }}
68 \CustomizeMathJax{\newcommand{\DiamonddotRight}{%
69   \mathrel{\unicode{x027D0}\!\unicode{x021D2}}%
70 }}
71 \CustomizeMathJax{\newcommand{\DiamonddotLeft}{%
72   \mathrel{\unicode{x021D0}\!\unicode{x027D0}}%
73 }}
74 \CustomizeMathJax{\newcommand{\Diamonddot}{\mathrel{\unicode{x027D0}}}}
75
76 \CustomizeMathJax{\newcommand{\circleright}{%
77   \mathrel{\unicode{x025CB}\!\unicode{x02192}}%
78 }}
79 \CustomizeMathJax{\newcommand{\circleleft}{%
80   \mathrel{\unicode{x02190}\!\unicode{x025CB}}%
81 }}
82 \CustomizeMathJax{\newcommand{\circledotright}{%
83   \mathrel{\unicode{x02299}\!\unicode{x02192}}%
84 }}
85 \CustomizeMathJax{\newcommand{\circledotleft}{%
86   \mathrel{\unicode{x02190}\!\unicode{x02299}}%
87 }}
88 \CustomizeMathJax{\let\circleddotright\circledotright}
89 \CustomizeMathJax{\let\circleddotleft\circledotleft}
90
91 \CustomizeMathJax{\newcommand{\multimapinv}{\mathrel{\unicode{x027DC}}}}
92 \CustomizeMathJax{\newcommand{\multimapboth}{\mathrel{\unicode{x029DF}}}}
93 \CustomizeMathJax{\newcommand{\multimapdot}{\mathrel{-\!\bullet}}}
94 \CustomizeMathJax{\newcommand{\multimapdotinv}{\mathrel{\bullet\!-}}}
95 \CustomizeMathJax{\newcommand{\multimapdotboth}{%

```

```

96  \mathrel{\bullet\!\!\!-\!\!\!\bullet}}%
97 }}
98 \CustomizeMathJax{\newcommand{\multimapdotbothA}{\mathrel{\unicode{x022B6}}}}
99 \CustomizeMathJax{\newcommand{\multimapdotbothB}{\mathrel{\unicode{x22B7}}}}
100
101 \CustomizeMathJax{\newcommand{\multimapbothvert}{%
102  \mathrel{\overset{\unicode{x025CB}}{\underset{\unicode{x025CB}}{|}}}}%
103 }}
104 \CustomizeMathJax{\newcommand{\multimapdotbothvert}{%
105  \mathrel{\overset{\unicode{x025CF}}{\underset{\unicode{x025CF}}{|}}}}%
106 }}
107 \CustomizeMathJax{\newcommand{\multimapdotbothBvert}{% bug in kpfonts-otf
108  \mathrel{\overset{\unicode{x025CF}}{\underset{\unicode{x025CB}}{|}}}}%
109 }}
110 \CustomizeMathJax{\newcommand{\multimapdotbothAvert}{% bug in kpfonts-otf
111  \mathrel{\overset{\unicode{x025CB}}{\underset{\unicode{x025CF}}{|}}}}%
112 }}
113
114 \CustomizeMathJax{\newcommand{\bignplus}{%
115  \mathop{\LWROverlaysymbols{\unicode{xFF0B}}{\unicode{x22C2}}}}%
116 }}
117 \CustomizeMathJax{\let\bigcapplus\bignplus}
118 \CustomizeMathJax{\let\capplus\bignplus}% from kpfonts-otf
119
120 \CustomizeMathJax{\newcommand{\bigsqcapplus}{%
121  \mathop{\LWROverlaysymbols{\unicode{xFF0B}}{\unicode{x2A05}}}}
122 }}
123 \CustomizeMathJax{\let\sqcapplus\bigsqcapplus}% from kpfonts-otf
124
125 \CustomizeMathJax{\newcommand{\bigsqcupplus}{%
126  \mathop{\LWROverlaysymbols{\unicode{xFF0B}}{\unicode{x2A06}}}}
127 }}
128 \CustomizeMathJax{\let\sqcupplus\bigsqcupplus}% from kpfonts-otf
129
130 \CustomizeMathJax{\newcommand{\parallelslant}{\mathrel{\unicode{x02AFD}}}}
131 \CustomizeMathJax{\newcommand{\parallelbackslant}{%
132  \mathrel{\unicode{x0005C}\!\!\!\unicode{x0005C}}}%
133 }}
134
135 \CustomizeMathJax{\newcommand{\Eqqcolon}{\mathrel{=\!\!\!\unicode{x2237}}}}
136 \CustomizeMathJax{\let\eqqColon\Eqqcolon}% for kpfonts-otf
137 \CustomizeMathJax{\newcommand{\dashColon}{\mathrel{-\!\!\!\unicode{x2237}}}}
138 \CustomizeMathJax{\newcommand{\Colondash}{\mathrel{\unicode{x2237}-}}}
139
140 \CustomizeMathJax{\newcommand{\colonapprox}{\mathrel{: \approx}}}
141 \CustomizeMathJax{\newcommand{\colonsim}{\mathrel{: \sim}}}
142 \CustomizeMathJax{\newcommand{\Colonapprox}{%
143  \mathrel{\unicode{x2237}\!\!\!\approx}}%
144 }}
145 \CustomizeMathJax{\newcommand{\Colonsim}{\mathrel{\unicode{x2237}\!\!\!\sim}}}
146
147 \CustomizeMathJax{\newcommand{\strictif}{%
148  \mathrel{\unicode{x0297D}}}%
149 }}% right fish tail
150 \CustomizeMathJax{\newcommand{\strictfi}{%
151  \mathrel{\unicode{x0297C}}}%
152 }}% left fish tail
153 \CustomizeMathJax{\newcommand{\strictiff}{%
154  \mathrel{\unicode{x0297C}\!\!\!\unicode{x0297D}}}%
155 }}% left/right fish tails

```

```

156
157 \CustomizeMathJax{\newcommand{\circledwedge}{%
158   \mathbin{\LWROverlaysymbols{\unicode{x025EF}}{\unicode{x02227}}}%
159 }}
160 \CustomizeMathJax{\newcommand{\circledvee}{%
161   \mathbin{\LWROverlaysymbols{\unicode{x025EF}}{\unicode{x02228}}}%
162 }}
163 \CustomizeMathJax{\newcommand{\circledbar}{\mathbin{\unicode{x029B6}}}}
164
165 \CustomizeMathJax{\newcommand{\openJoin}{%
166   \mathrel{\unicode{x2AA4}}%
167 }}% overlapping ><
168 \CustomizeMathJax{\newcommand{\openTimes}{%
169   \mathrel{\unicode{x2AA4}}%
170 }}% overlapping ><
171
172 \CustomizeMathJax{\newcommand{\VvDash}{\mathrel{\unicode{x22AA}}}}
173
174 \CustomizeMathJax{\newcommand{\lambdabar}{%
175   \mathord{\LWROverlaysymbols{\raise{.5ex}{-}}{\Lambda}}%
176 }}
177
178 \CustomizeMathJax{\newcommand{\lambdaslash}{\mathord{\unicode{x019B}}}}
179
180 \CustomizeMathJax{\newcommand{\Wr}{%
181   \mathbin{\unicode{x02240}\!\!\unicode{x02240}}%
182 }}
183
184 \CustomizeMathJax{\newcommand{\dashleftarrow}{%
185   \mathrel{\unicode{x021E0}\!\!\unicode{x021E2}}%
186 }}
187 \CustomizeMathJax{\let\leftrighthdasharrow\dashleftarrow}% for kpfonts-otf
188
189 \end{warpMathJax}

```

File 588 **lwarp-common-mathjax-overlaysymbols.sty**

§ 697 Package **common-mathjax-overlaysymbols**

Pkg Common code used by a number of packages to overlay two symbols for MATHJAX.

lwarp-common-mathjax-overlaysymbols

for HTML output: 1 \ProvidesPackage{lwarp-common-mathjax-overlaysymbols}[2020/08/17]

\LWROverlaysymbols

$\langle symbol \rangle \langle symbol \rangle$

Overlays one symbol over another.

```

2 \begin{warpMathJax}
3
4 \CustomizeMathJax{\newcommand{\LWROverlaysymbols}[2]{%
5   \mathord{%
6     \smash{%
7       \mathop{\#2\strut}%
8       \limits^{\smash{\lower3ex{\#1}}}%
9     }%
10    \strut%
11  }%

```

```
12 }}  
13  
14 \end{warpMathJax}
```

Change History

§ 698 Chg Hist

For the most recent changes, see page [1330](#).

v0.10	Added.	801
General: 2016/03/08 Initial version	1	
v0.11	Ampersand (&): Fixed handling	438
General: 2016/03/11	1	
Added section: Operating-System		
portability.	225	
Added section: Selecting the		
operating system.	115	
Test Suite: MS-WINDOWS in		
README.txt	1	
Test Suite: limages and index in		
README.txt	1	
v0.12	Docs: Added warning icons for	
\LWR@newhtmlfile: Bugfix: TOC		
with numbered files.	383	
General: 2016/03/14	1	
Global: Uses \p@(type) in float		
captions.	1	
Test Suite: Sub-figures	1	
v0.13	Docs: Clarify print/HTML output.	115
\CaptionSeparator: Fix for newer		
babel package.	507	
\LWR@LwarpStart: \up and \fup	402	
General: 2016/03/24	1	
Fix dollar-redefined bug for		
newer package.	1163	
Removed package: subfig	1	
Test Suite: Ordinals, Subcaption	1	
v0.14	Docs: Moved the supported	
\LWR@htmlsectionfilename: Fix:		
Links to home page.	337	
General: 2016/03/31	1	
floatrow: Added.	797	
Docs: Commands for a		
successful HTML conversion.	119	
Docs: Commands into a		
warpprint environment.	116	
Docs: Newclude limitations.	170	
Docs: Table: Cross-referencing		
data structures.	490	
Docs: Table: Float data		
structures.	503	
Docs: Trademarks section.	197	
Docs: Troubleshooting		
cross-references.	192	
Test Suite: Assigned cleveref		
name for Test Float.	1	
Test Suite: Floatrow	1	
v0.15	Files: lwarp_formal.css added.	1
General: 2016/04/06	1	
Fix: steps counter	801	
Fixed & handling.	799	
Test Suite: test_suite_formal.css		
file added.	1	
v0.16	Test Suite: test_suite_formal.css	
General: 2016/04/11	1	
\titlingpage: Improved		
print-output spacing.	410	
xfrac: Adjusted for the use of any		
font:	1228	
Added XeLaTeX, LuaLaTeX		
support.	201	
Docs: Font and UTF-8 support.	100	
Docs: Moved location of		
\usepackage{lwarp}.	102	
Docs: Text not converting.	192	
Lwarp no longer selects		
fonts.	100, 235	
Removed package: suffix	1	
Test Suite: Improved titlingpage.	410	
Test Suite: Lwarp no longer		
selects fonts.	1	
Test Suite: Supports XeLaTeX,		
LuaLaTeX.	1	
v0.17	Test Suite: test_suite_formal.css	
\LWR@htmlsectionfilename: Fix:		
Links when entire doc is one		
HTML page.	337	
General: 2016/04/14	1	
mdframed: Added.	931	
Test Suite: Fix: Print-version		
front-matter page numbers.	1	
Test Suite: Mdframed	1	
v0.18	Added.	801
\LWR@myshorttoc: Reorganize		
\HomeHTMLFilename logic.	511	
\LWR@newhtmlfile: sideroc after		
title, improving responsive		
design.	383	

\LWR@requesttoc: Reorganize	
\HomeHTMLfilename logic.	404
\LWR@subhyperref: Improved HTML	
output linebreaks.	500
\LWR@subhyperrefclass: Improved	
HTML output linebreaks.	500
\LWR@subinlineimage: Suppress	
extra space.	501
\hspace: \hspace supported.	604
General: 2016/05/19	1
graphics: Add: svg file extension.	833
graphics: Fix: \linewidth,	
\textwidth, \textheight	
inside a minipage.	833
graphics: Improved HTML output	
linebreaks.	833
graphics: em, ex, %, px	
dimensions preserved.	833
File: lwarp.css: Improved roc	
outline display.	1
Files: lwarp.css and	
lwarp_formal.css: Improved	
responsive design.	1
Microtype disabled during HTML	
generation	236
PDF Unicode input characters.	218
Test Suite: Verse package	1
lateximage: pdfcrop: --hires	
added.	562
Reorganize \HomeHTMLfilename	
logic.	562
Suppress extra space.	562
verse: Supports verse, memoir	
packages.	1203
minipage: Fix: \linewidth,	
\textwidth, \textheight	
inside a minipage.	582
v0.19	
\HTMLfilename: Docs: Escape	
filename underscores.	336
\HomeHTMLfilename: Docs: Escape	
filename underscores.	336
\LWR@LwarpStart: Enabled \\ equal	
to \newline.	401
\LWR@doequation: MATHJAX	
support.	550
\LWR@doubledollar: MATHJAX	
support.	543
\LWR@filestart: lwarp_mathjax.txt	
loaded.	398
\LWR@minipagestartpars:	
Suppresses paragraph tags	
between minipages.	603
\LWR@subsingledollar: MATHJAX	
support.	542
\LateximageFontSizeName: Add:	
User-adjustable	
math/lateximage font size.	559
\hspace: Fix: \hspace length	
computations.	604
\minipagefullwidth: Added: No	
width tag for the next minipage	
in HTML.	582
\warpHTMLonly: Added.	233
\warpprintonly: Replaces	
\rowprintedonly.	233
\xfracHTMLfontsize: Added.	1227
General: 2016/06/08	1
css for table note item.	1160
MATHJAX support added.	547, 555
multirow: Added optional args.	962
xcolor: Supports colored \rule.	1219
Adapts to tikz version.	1163
Avoids MATHJAX.	535
cleveref: Loaded	
\AtEndPreamble.	579
Docs: Math options.	102
Docs: Table: Cross-referencing	
data structures, updated.	490
File: lwarp.css:	
tnoteitemheader added.	1
File: lwarp_mathjax.txt added.	1
Introduction: MATHJAX support	
mentioned.	63
Options: mathsvg and mathjax	228
titles: null \pagestyle and	
\thispagestyle for HTML.	1164
v0.20	
\BlockClassSingle: Renamed from	
"LWR@htmldivclassline".	352
\HTMLDescription: Added	
\NewHTMLdescription.	
(Renamed in v0.30.)	362
\HTMLfilename: No longer escape	
underscores.	336
\HomeHTMLfilename: No longer	
escape underscores.	336
\InlineClass: Renamed from	
"inlineclass".	352
\LWR@closeparagraph: \unskip	
extra spaces.	356
No break tags in the start/end of	
a tabular.	356
\LWR@endofline: Fix: \\	602
\LWR@filestart: Adds meta	
description.	398
\LWR@htmldivclass: Added	
optional style.	350
\LWR@htmlElementclass: Added	
optional style.	350
\LWR@htmlSectionfilename:	
HTMLfilename: removed	
additional trailing '-', and may	
be empty.	337
Sections called "Index" or "index"	
have an underscore prepended	
to their filenames if no prefix.	337
\LWR@hyperindexrefsSubtwo: Print	
mode provided in case hyperref	
not used.	526

<code>\LWR@longtabledatacaptiontag:</code>		<code>wallpaper:</code> Added.	1208
Fix: Pars in captions.	474	<code>wrapfig:</code> Added.	1210
<code>\LWR@section: Combined</code>		<code>xetexko:</code> Added.	1226
higher-level sections together		Added @, <, > columns.	431
into files.	389	Added single-expansion data	
<code>\LWR@setOSWindows: Auto-detects</code>		arrays.	332
operating system.	226	Code factored into independent	
<code>\LWR@subhtmlElementclass:</code>		<code>lwarp_html</code> files.	620
Factored code.	349	Docs: Examples for generating	
<code>\SetHTMLFileNumber: Add: Control</code>		HTML file names.	113
file numbers.	336	Docs: Improved index.	1
<code>\cpagerefFor: User-redefinable</code>		Enhanced titling support.	409
word for page references.	730	File: <code>lwarp.css</code> : Minor fixes for	
<code>\dotfill: Inserts an ellipsis.</code>	602	validation.	1
<code>\hfill: Inserts a \quad.</code>	602	File: <code>lwarpmk</code> used to compile	
<code>\hrulefill: Inserts a short rule.</code>	602	print, HTML, indexes, and	
<code>\hspace: Add: Supports HTML thin</code>		<code>lateximages</code>	1
breakable space.	604	Fix: <code>\linewidth</code> in a floatrow.	800
<code>\pageref: Added.</code>	498	Moved sidebar and example code	
<code>\tracinglwarp: Added.</code>	249	to test suite.	1
General: 2017/02/09	1	Page geometry set to 6in wide	
afterpage: Added.	633	with large margins.	236
alltt: Added.	638	Parallel versions of aux files for	
bookmark: Added.	677	print/HTML.	1
caption and subcaption		Removed reliance on make, grep,	
supported.	1	gawk.	1
cleveref and referencing patches:		Tabular: <code>\unskip</code> extra spaces.	431
Applied <code>\AfterEndPreamble</code>	729	Test Suite: HTML meta	
draftwatermark: Added.	747	descriptions.	1
eso-pic: Added.	767	verbatim: Added.	420
everypage: Added.	771	BlockClass: Added optional style.	351
extramarks: Added.	772	Renamed from "blockclass".	351
fancyhdr: Added.	778	<code>LWR@nestspan</code> : Fix: Minipages	
float: Improved float caption type		inside a span.	347
handling.	794	v0.21	
graphics: Fix: Expands filename.	833	<code>\LWR@LwarpStart</code> : Changed	
graphics: Fix: <code>\linewidth</code> in a		<code>lateximages</code> to a .txt file.	401
floatrow.	833	<code>\LWR@filestart</code> : Skip title if not	
hyperref: Additional user		given.	398
macros.	845	<code>\LWR@newhtmlfile</code> : Skip title if not	
keyfloat: Added.	870	given.	383
letterspace: User-interface		<code>\marginpar</code> : Fixed source listing.	369
emulated.	883	<code>\marginparBlock</code> : Fixed source	
listings: Added.	893	listing.	369
lrcaption: Added.	905	General: 2017/02/23	1
lwarp-newproject: Added.	260	fontenc: Added.	806
microtype: User-interface		<i>lwarpmk</i> : Fix: <i>lwarpmk</i> again for	
emulated.	947	WINDOWS.	311
needspace: Added.	973	<i>lwarpmk</i> : Fix: <i>lwarpmk</i> images	
nowidow: Added.	988	for WINDOWS.	311
placeins: Added.	1024	<i>lwarpmk</i> : Fix: <i>lwarpmk</i> uses	
ragged2e: Added.	1032	<code>lateximages</code> text file instead of	
setspace: Improved support.	1057	shell script.	311
symptex: Added.	1134	Add: Errors for misplaced	
textpos: Added.	1153	packages.	201
titles: Added.	1164	Docs: Added internet class.	72
titlesec: Added.	1167	Docs: Added TeX2page, GladTeX.	72
titletoc: Added.	1169	Docs: Installing on WINDOWS.	78
titling: Improved compatibility.	1171	File: <code>lwarp_tutorial.txt</code>	
tocloft: Added.	1179	added.	82

v0.22		lips: Added.	892
	\LWR@parsebangcolumn: Added	mdframed: Help avoid	
	tabular ! column.	hyphenation.	932
	\LWR@parsetablecols: Unknown	ntheorem: Added.	989
	table column types become L.	showidx: Added.	1059
	Added tabular D, !, X columns.	theorem: Added.	1154
	452	Basic L ^A T _E X theorems: improved	
	\LWR@printmccoldata: Added	css.	421
	tabular D, !, and X columns. . .	Docs: Adds credits for patched	
	469	code.	1
	General: 2017/03/02	Docs: Testing lwarp.	188
	1	Fix: Allows XeL ^A T _E X and LuaL ^A T _E X	
	abstract: Added.	to preload graphics and	
	622	graphicx.	207
	changepage: Added.	v0.26	
	692	General: 2017/03/31	1
	dcolumn: Added.	lwarp.css: Improved responsive	
	741	marginpar and marginblock.	267
	ftnright: Added.	cutwin: Added.	740
	816	endnotes: Added.	754
	geometry: Nullified commands.	floatflt: Added.	796
	821	footmisc: Added.	807
	layout: Added.	footnotehyper: Added.	810
	880	footnote: Added.	808
	lscap: Added.	marginfix: Added.	916
	904	marginnote: Added.	917
	mcaption: Added.	mparhack: Added.	956
	931	pagenote: Supported as-is.	1003
	nameref: Added.	sidenotes: Added.	1061
	969	Docs: Improved MiK _T E _X install	
	nextpage: Added.	instructions.	77, 78
	976	Dollar span avoided in a	
	parskip: Added.	lateximage.	535
	1009	Footnotes now are L ^A T _E X boxes	
	showkeys: Added.	instead of pagenotes.	364
	1059	lateximage: Labels track page	
	sidecap: Added.	numbers of lateximages.	562
	1061	Print mode now uses a minipage	
	tabularx: Added.	of \linewidth.	562
	1136	picture: Fix for \makebox in	
	variref: Supported.	picture.	580
	128	v0.27	
	verse: Added.	\LWR@@footnotetext: Fix for table	
	1202	footnote par tags.	365
v0.23		General: 2017/04/04	1
	\LWR@parsetablecols: Fix for vert	lettrine: Added.	884
	bar column type.	microtype: Fix with XeL ^A T _E X,	
	452	LuaL ^A T _E X.	947
	\LWR@printmccoldata: Fix for vert	soul: Added.	1106
	bar column type.	ulem: Added.	1192
	469	Docs: Installing utilities for	
	General: 2017/03/02	MACOS.	80
	1	Docs: Limitations of saveboxes.	122
v0.24		Page geometry modified to	
	\LWR@htmlfileref: Fix: Index links	reduce line overflow.	236
	while \tracinglwarp.	v0.28	
	492	\@wrindex: Improved indexing.	521
	\hspace: Add: \hspace \fill	\HTMLAuthor: Added \HTMLauthor.	
	converts to 2em	(Renamed in v0.30.)	362
	604		
	\hypertocfloat: List of floats		
	responds to lofdepth,		
	lotdepth.		
	518		
	General: 2017/03/15		
	1		
	floatrow: Support for subfig. . . .		
	797		
	subfig: Added.		
	1126		
	tikz: For tikz v3.0.0 or later,		
	auto-loads tikz babel library if		
	necessary.		
	1163		
	Docs: Filename underscore.		
	102, 121		
	Fix for inline images.		
	1163		
	No longer preloads subcaption;		
	conflicted with subfig.		
	240		
	picture: Fix for inline images. . . .		
	580		
v0.25			
	\LWR@loadnever: Added the ability		
	to prevent conflicting packages. . .		
	203		
	\addcontentsline: Handles		
	theorems.		
	510		
	General: 2016/03/22		
	1		
	amsthm: Added.		
	643		
	ellipsis: Added.		
	752		
	emptypage: Added.		
	753		
	framed: Added.		
	813		

\LWR@LwarpEnd: If FormatEPUB or FormatWP, no bottom nav.	404	v0.30	\CSSFilename: Renamed from \NewCSS.	361
\LWR@LwarpStart: FormatWordProcessor forces single-file output.	401		\HTMLAuthor: Renamed from \HTMLauthor.	362
\LWR@filestart: Adds HTML meta author.	398		\HTMLDescription: Renamed from \NewHTMLdescription.	362
\LWR@forcenewpage: Forces new PDF page before major environments.	343		\HTMLFirstPageTop: Renamed from \SetFirstPageTop.	360
\LWR@htmlcomment: Breaks ligatures in HTML comments.	349		\HTMLLanguage: Renamed from \MetaLanguage.	397
\LWR@hyperindexrefsbtwo: Improved indexing.	526		\HTMLPageBottom: Renamed from \SetPageBottom.	361
\LWR@newhtmlfile: If FormatEPUB or FormatWP: skips headers, footers, nav.	383		\HTMLPageTop: Renamed from \SetPageTop.	360
\LWR@parsetablecols: Added L, C, R, J column types.	452	General: 2017/04/29	1	<i>lwrap</i> -newproject removed, and combined with <i>lwrap</i>
\LWR@startref: Removed space.	495		311	<i>lwrapmk</i> : Add: <i>xdyfile</i> configuration option.
\chapter: If EPUB, prints footnotes before each section.	396		311	<i>lwrapmk</i> : Fix: <i>xindy</i> and <i>texindy</i> adjusted for <i>pdflatex</i> , <i>xelatex</i> and <i>lualatex</i>
\textup: Fixed span class.	593		311	<i>lwrapmk</i> : Fix: <i>xindy</i> now used for print index generation with <i>latexmk</i>
General: 2017/04/14	1		311	<i>lwrapmk</i> : language now used for both index and glossary generation.
glossaries: Added.	825		306	File: <i>lwrap_html</i> . <i>xdy</i> renamed to <i>lwrap</i> . <i>xdy</i>
graphics: Adapts to graphics syntax.	833		267	Fix: *.css files only written in print mode.
graphics: Added.	826		306	Fix: <i>lwrap</i> . <i>xdy</i> only written in print mode.
tabularx: Fix for optional pos.	1136		307	Fix: <i>lwrap_mathjax</i> . <i>txt</i> : Only written in print mode.
tabulary: Added.	1137		229	Option <i>lwrapmklang</i> changed to <i>IndexLanguage</i>
<i>lwrapmk</i> : Add: printglossary and htmlglossary commands.	311		229	Option <i>OSWindows</i> replaces macro <i>\warpOSWindows</i>
Added boolean FormatEPUB.	254		228	Option <i>xdyFilename</i> added.
Added boolean FormatWP.	254		230	Option <i>latexmk</i> replaces macro <i>\UseLatexmk</i>
Added boolean HTMLDebugComments.	249		229	Options <i>HomeHTMLFilename</i> and <i>HTMLFilename</i> replace macros <i>\HomeHTMLFilename</i> and <i>\HTMLFilename</i>
Added boolean HTMLMarkFloats, changed to WPMarkFloats as of v0.42.	254		870	
Docs: Modifying <i>lwrapmk</i> and index processing.	189	v0.31	1	General: 2017/05/15
File: <i>lwrap_mathjax</i> . <i>txt</i> : Updated CDN repository.	307		870	<i>keyfloat</i> : Improved compatibility.
Forced oneside to maintain large right margin.	236	v0.32	243	<i>\RequirePackage</i> : Fix: Ignores blanks in package list.
v0.29			1	General: 2016/06/09
General: 2017/04/15	1		527	<i>glossaries</i> : Prevent error with <i>\glo@name</i> not defined.
*.lwrapmkconf: Add: language option for config files.	267			
<i>lwrapmk</i> .conf: Add: language option for config files.	266			
graphics: Fix: Error when no optional arguments.	833			
<i>lwrapmk</i> : Add: language option for config files.	311			
Add: <i>lwrapmklang</i> option for <i>lwrap</i>	229			
Docs: Using a glossary	93			

	<i>lwarpmk</i> : Fix: <code>io.lines()</code> changed to <code>file:lines()</code> due to <i>luatex</i> changes.	311		<code>\LWR@tabledatacolumnntag</code> : <code>booktabs</code> : Works inside <code>lateximage</code>	480
v0.33	<code>\HTMLAuthor</code> : Fix: Provides empty default author if none given. . .	362	<code>\fboxBlock</code> : Added.	588	
	<code>\LWR@loadbefore</code> : Fix: No <code>\PackageError</code> if already loaded.	203	<code>\makebox</code> : Fix: Handles paren arg. .	586	
	<code>\LWR@parseatcolumn</code> : Fix: Column alignment with <code>leftmost@</code> . . .	442	General: 2017/08/08	1	
	<code>\LWR@tabledatasinglecolumnntag</code> : Fix: Macros in <code>tabular</code> could cause extra data cell.	457	<code>babel-french</code> : Adds fixed-width HTML spaces to punctuation. . . .	344	
	<code>\LWR@vspace</code> : Add: <code>\vspace</code> nullified.	605	<code>balance</code> : Added.	662	
	<code>\StartDefiningTabulars</code> : Add: Avoids error: Misplaced alignment tab character &.	333	<code>booktabs</code> : Works inside <code>lateximage</code>	483, 678	
	General: 2017/07/10	1	<code>boxedminipage2e</code> : Added.	680	
	<code>amsmath</code> : Removed <code>fleqn</code> option.	639	<code>crop</code> : Added.	737	
	<code>fancyhdr</code> : Fix: Optional args for <code>\thead</code> , etc.	778	<code>enumerate</code> : Added.	761	
	Add: <code>Tabular at and bang</code> columns now have their own HTML columns.	431	<code>enumitem</code> : Added, no longer required.	762	
	<code>cleveref</code> : Fix: Loaded <code>\AtEndPreamble</code>	579	<code>everyshi</code> : Added.	771	
	Fix: Incorrectly-inline math environments.	555	<code>fancybox</code> : Added.	774	
	New handling of & to localize catcode changes.	431	<code>fancyvrb</code> : Added, no longer required.	781	
v0.34	<code>\@fnsymbol</code> : Text symbols instead of math.	412	<code>figcaps</code> : Added.	790	
	<code>\InlineClass</code> : Moved optional argument in front of mandatory.	352	<code>filecontents</code> : Required. Patched for <code>morewrites</code>	239	
	<code>\LWR@htmldivclass</code> : Moved optional argument in front of mandatory.	350	<code>floatpag</code> : Added.	797	
	<code>\LWR@htmlclass</code> : Moved optional argument in front of mandatory.	350	<code>flushend</code> : Added.	802	
	<code>\LWR@htmlclassline</code> : Moved optional argument in front of mandatory.	351	<code>fullpage</code> : Added.	817	
	<code>\LWR@htmlspanclass</code> : Moved optional argument in front of mandatory.	348	<code>hyperxmp</code> : Added.	855	
	<code>\LWR@nullfont</code> : Improved font control.	530	<code>idxlayout</code> : Added.	857	
	<code>\LWR@restoreorigformatting</code> : <code>booktabs</code> : Works inside <code>lateximage</code>	528	<code>marginfit</code> : Added.	916	
	Improved font control.	528	<code>mdframed</code> : Improved <code>mdtheorem</code> patch.	937	
	<code>\LWR@subhtmlclass</code> : Moved optional argument in front of mandatory.	349	<code>moreverb</code> : Added.	954	
			<code>paralist</code> : Added.	1003	
			<code>pdfscape</code> : Added.	1013	
			<code>pdfsync</code> : Added.	1016	
			<code>prelim2e</code> : Added.	1026	
			<code>rotfloat</code> : Added.	1042	
			<code>savetrees</code> : Added.	1043	
			<code>shadow</code> : Added.	1058	
			<code>syntonly</code> : Added.	1135	
			<code>titles</code> : No longer required. . .	1164	
			<code>titleref</code> : Prevented.	1167	
			<code>xcolor</code> : Added <code>\LWR@subfcolorminipage</code> . . .	1222	
			<code>xmpincl</code> : Added.	1230	
			Docs: Horizontal space limitations.	1	
			Docs: Misplaced alignment character.	192	
			File: <code>lwrap_mathjax.txt</code> : Version change.	307	
			File: <code>README.txt</code> : updated. . . .	1	
			Fix: Added the <code>eqnarray</code> environments.	555	
			Improved font control.	591	
			Lists refactored to remove <code>enumitem</code> requirement.	423	
			Verbatim refactored to remove <code>fancyvrb</code> requirement.	418	

tabular: booktabs: Works inside lateximage.	485	xcolor: Uses \fboxrule and \fboxsep.	1215
lateximage: Fix: lateximage with minipage, \parbox, \makebox, \fbox, \framebox, \raisebox, \scalebox, \reflectbox.	562	xcolor: \fcolorbox etc. now work inside lateximage.	1215
BlockClass: Moved optional argument in front of mandatory.	351	Docs: Reorganized: Special cases and limitations.	119
fminipage: Added.	589	Source: Improved formatting.	1
LWR@nestspar: Fix: Minipages, BlocksClass, and lists inside a span.	347	tabular: Fix for babel-french.	485
v0.35		lateximage: Footnotes appear in regular text instead of the lateximage minipage.	562
General: 2017/08/08	1	v0.37	
Fix: \textbf and related.	591	\@include: Maintains independent aux files for HTML.	247
v0.36		General: 2017/08/19	1
\LWR@footnotetext: Extra HTML source space after paragraphs.	365	L ^A T _E X accents: Added.	258
Force HTML superscripts.	365	babel-french: Adjustment for load order.	344
\LWR@HTMLsanitizeexpanded: Fix for babel-french.	378	color: Prevented.	734
\LWR@closeparagraph: Extra HTML source space after paragraphs.	356	siunitx: Improved symbol support.	1082
\LWR@currenttextcolor: Fix for \rule when xcolor not loaded.	600	textcomp: Improved support.	1150
\LWR@nullfont: Fix: Filenames while using MATHJAX.	530	<i>lwarpmk</i> : Removes additional HTML aux files.	311
\LWR@restoreorigformatting: siunitx: Improved super/subscripts in a lateximage.	528	File handles reorganized.	246
\LWR@section: Improved spacing.	389	v0.38	
\LWR@stoppars: Extra HTML source space after paragraphs.	359	\@secntformat: Added for appendix.	389
\LWR@subHTMLsanitize: Fix for babel-french.	377	\ForceHTMLPage: Added.	386
\fbox: Fix: Uses \fboxrule and \fboxsep.	588	\ForceHTMLTOC: Added.	387
\framebox: Fix: Handles width and horiz position.	587	\LWR@section: \part* starts a new HTML page, for appendix.	389
\makebox: Fix: Handles width and horiz position.	586	Modified spacing, uses \numberline.	389
General: 2017/08/17	1	\numberline: Added trailing \quad.	516
babel-french: Adjustments for French variants, load order, footnotes, ellipses.	344	\part: Fix with article class.	395
footnote: Extra HTML source space after paragraphs.	808	General: 2017/08/27	1
siunitx: Fix for babel-french.	572	appendix: Added.	648
siunitx: Improved symbol support.	1082	arabicfront: Added.	650
transparent: Added.	1188	chappg: Added.	698
upref: Added.	1201	color: Forces xcolor as well.	734
xcolor: Added \fcolorboxBlock, \colorboxBlock.	1215	fix2col: Added.	791
xcolor: Fix: Background none in print mode.	1215	fncychap: Added.	803
xcolor: Refactored		grffile: Added.	838
\LWR@colorstyle.	1219	metalogo: Added.	943
		nonumonpart: Added.	987
		nopageno: Added.	987
		pagenote: Option page disabled.	1003
		realscripts: Added.	1033
		resize: Added.	1037
		romanbarpagenumber: Added.	1041
		romanbar: Added.	1041
		scalefnt: Added.	1043
		siunitx: Removed from lwrap core.	1082
		textcomp: Removed from lwrap core.	1150
		tocbibind: Added.	1176
		xltxtra: Added.	1230

<i>lwarpmk</i> : Added print1 and html1 actions.	311	<i>zwpage</i> layout: Added.	1237
Added <code>\markboth</code> , <code>\sloppy</code> , etc.	343	Docs: Reorganized tabular discussion.	161
Docs: Enhanced <i>Supported Features</i> table.	66	Titlepage <code>\published</code> and <code>\subtitle</code> removed. <code>\AddSubtitlePublished</code> restores.	414
Docs: Index, <code>tocbibind</code>	134	<code>titlepage</code> : Clear pending footnotes.	409
Docs: Starred sections.	130	Removed minipages.	409
v0.39		<code>titlingpage</code> : Clear pending footnotes.	1171
<code>\@maketitle</code> : titling version.	1173	v0.40	
Native L ^A T _E X version.	413	<code>\@chapcntformat</code> : Added for <code>tocbibind</code> , <code>anonchap</code>	389
Removed minipages.	413, 1173	<code>\LWR@HTMLhline</code> : Added.	484
Supports <code>authblk</code> with <code><div></code> s of class <code>oneauthor</code> instead of <code>tabular</code>	413, 1173	<code>\LWR@nullfonts</code> : Fix: Long arguments for expandable command.	530
<code>\AddSubtitlePublished</code> : Added.	414	<code>\LWR@restoreorigformatting</code> : Improved L ^A T _E X logos inside a <code>lateximage</code>	528
<code>\LWR@domulticolumn</code> : Add: Optional <code>vpos</code> and <code># rows</code>	471	Improved symbols inside a <code>lateximage</code>	528
<code>\LWR@restoreorigformatting</code> : Appended with <code>\appto</code> instead of calling various macros.	528	Nullified <code>\InlineClass</code> , etc. inside a <code>lateximage</code>	528
<code>\LWR@tabledatacolumn</code> tag: Don't start a data cell if see <code>\TabularMacro</code>	480	<code>\LWR@tabledatacolumn</code> tag: Fix for <code>bigdelim</code> : <code>\ldelim</code> , <code>\rdelim</code>	480
<code>\ResumeTabular</code> : Added.	479	<code>\chapter</code> : Added support for <code>quotchap</code>	396
<code>\TabularMacro</code> : Added.	479	<code>\multicolumnrow</code> : Fix: Adapts to older <code>multirow</code> and <code>xparse</code>	478
<code>\multicolumnrow</code> : multirow : Added.	963	<code>\simplechapterdelim</code> : Added for <code>tocbibind</code> , <code>anonchap</code>	389
Added.	478	<code>\underline</code> : Added.	600
<code>\printauthor</code> : Removed minipages.	410	General: 2017/09/25	1
Supports <code>authblk</code> with <code><div></code> s of class <code>oneauthor</code> instead of <code>tabular</code>	410	<code>adjmulticol</code> : Added.	632
<code>\thanksmarkseries</code> : Removed minipage footnotes.	1174	<code>anonchap</code> : Added.	647
General: 2017/09/05	1	<code>bigdelim</code> : Improved documentation.	674
<code>a4wide</code> : Added.	621	<code>cuted</code> : Added.	740
<code>a4</code> : Added.	621	<code>dblfnote</code> : Added.	741
<code>a5comb</code> : Added.	622	<code>fnpos</code> : Added.	804
<code>addlines</code> : Added.	633	<code>graphics</code> : Add: Full <code>\graphicspath</code> support.	833
<code>ansize</code> : Added.	647	<code>graphics</code> : Moved out of the <i>lwarpcore</i>	826
<code>authblk</code> : Added.	657	<code>graphics</code> : Restores <code>\includegraphics</code> and <code>\DeclareGraphicsExtensions</code> in a <code>lateximage</code>	826
<code>bigdelim</code> : Added.	674	<code>graphicx</code> : Moved out of the <i>lwarpcore</i>	838
<code>bigstrut</code> : Added.	675	<code>grffile</code> : Directly supported.	838
<code>ebook</code> : Added.	748	<code>midfloat</code> : Added.	947
<code>fullwidth</code> : Added.	817	<code>multirow</code> : Improved <code>bigdelim</code> borders.	962
<code>midpage</code> : Added.	948	<code>pfnote</code> : Added.	1019
<code>multirow</code> : Add: New optional <code>vpos</code> argument.	962	<code>quotchap</code> : Added.	1031
<code>multirow</code> : Add: Supports left/right border for <code>bigdelim</code>	962	<code>sectsty</code> : Added.	1054
<code>multirow</code> : Fix: Long text argument.	962		
<code>supertabular</code> : Added.	1132		
<code>textarea</code> : Added.	1149		
<code>titling</code> : Improved compatibility.	1171		
<code>titling</code> : Removed extraneous center environments.	1172		
<code>typearea</code> : Added.	1191		
<code>xtabular</code> : Added.	1233		

stabular: Added.	1111	\LWR@addformatwpalignment: If	
tabs: Added.	1136	FormatWP add explicit style for	
textcomp: Additional symbols,		cell alignment.	464
improved XeLaTeX and		\LWR@addrulewidth: If FormatWP	
LuaLaTeX support.	1150	force explicit border.	462
tocbibind: Improved for		\LWR@amsmathbody: Fix: Numbering	
\simplechapter.	1176	and naming AMS math	
xfrac: No longer preloaded. . . .	240	environments.	561
xltxtra: Fix for \showhyphens		\LWR@amsmathbodynumbered: Fix:	
with XeLaTeX.	1230	Numbering and naming AMS	
v0.41		math environments.	561
\LWR@addcmidruletrim: Add:		\LWR@doequation: If FormatWP print	
\cmidrule trims.	462	LaTeX expression.	551
\LWR@clearmidrules: Add:		\LWR@domulticolumn: If FormatWP	
\cmidrule trims.	460	add cell alignment.	473
\LWR@closetabledatcell: Add:		\LWR@doubledollar: If FormatWP	
Mute > for \bottomrule.	436	print LaTeX expression.	543
Fix: At/bang column with		Improved \ensuremath.	543
\multirow.	437	Improved line spacing with	
Fix: Cancel < for \multicolumn. .	437	mathjax.	543
\LWR@domulticolumn: Add:		\LWR@floatbegin: If FormatWP add	
\cmidrule trims.	471	a text frame.	504
Added vertical rules.	472	\LWR@floatend: If FormatWP add a	
\LWR@nullifyNoAutoSpacing:		text frame.	505
babel-french: Fix:		\LWR@remembertag: Fix: Numbering	
\NoAutoSpacing in a tabular. . .	484	and naming AMS math	
\LWR@parsebarcolumn: Added		environments.	561
vertical rules.	445	\LWR@restoreorigformatting:	
\LWR@printatbang: Add: \cmidrule		Improved \ensuremath.	529
trims.	456	\LWR@subaddcmidruletrim: Opt if	
Add: Mute at and bang columns		no rule given.	462
for \bottomrule.	456	\LWR@subsingledollar: If	
\LWR@printbartag: Added vertical		FormatWP print LaTeX	
rules.	456	expression.	542
\LWR@subaddcmidruletrim: Added. .	462	\LWR@tabledatasinglegolumntag:	
\LWR@subcmidrule: Add: \cmidrule		If FormatWP add cell alignment. .	458
trims.	460	\LaTeX: If FormatWP use explicit	
\LWR@tabledatasinglegolumntag:		style.	610
Add: \cmidrule trims.	457	\TeX: If FormatWP use explicit style. .	610
Add: Mute < for \bottomrule. . .	457	\hspace: If FormatWP add \quads. . .	605
\LWR@tabularfinishrow:		\listoffigures: Added boolean	
Unfinished tabular rows		WPMarkLOFT.	513
automatically filled.	439	\listoftables: Added boolean	
\mcolrowcell: Added for		WPMarkLOFT.	514
\multicolumrow cells.	483	\marginpar: If FormatWP emulate a	
General: 2017/10/07	1	wrapfig.	369
booktabs: Improved rules.	678	\marginparBlock: If FormatWP	
multirow: Add: \cmidrule trims. .	962	emulate a wrapfig.	369
multirow: Added vertical rules. . .	962	\rule: If FormatWP add \quads. . . .	608
multirow: Fix: < spec.	963	\tableofcontents: Added boolean	
tabular: Fix: \NoAutoSpacing in a		WPMarkTOC.	513
tabular with babel-french.	485	\underline: If FormatWP, use	
v0.42		explicit styles for \underline,	
\@ensuredmath: Improved		etc.	600
\ensuremath.	545	General: 2017/10/30	1
\@textsubscript: Added.	599	\textbf and related: If FormatWP,	
\@textsuperscript: Added.	599	use explicit styles for \textsc,	
\LWR@HTMLhline: If FormatWP force		etc.	591
explicit border.	484	algorithmicx: If FormatWP add	
		\quads.	637

booktabs: If FormatWP force explicit border.	678	If FormatWP print LaTeX expression.	556
epigraph: If FormatWP add HTML styles.	762	LWR@BlockClassWP: Added to factor code.	352
fancybox: If FormatWP add HTML styles.	774	LWR@figcaption: If FormatWP forces italic captions.	508
floatflt: Added width.	796	v0.43	
graphics: Fix: Class key.	830	\LWR@domulticolumn: Fix for vertical rules.	472
graphics: Fix: Filename expansion.	833	Fix: Multicolumn trim.	472
graphics: If FormatWP, use explicit size.	831	\LWR@href: Made robust.	500
keyfloat: If FormatWP add explicit HTML style.	874	\LWR@maybeprintpendingfootnotes: Added FootnoteDepth.	368
moreverb: Simplified formatting of listings.	954	\LWR@nolinkurl: Made robust.	501
multirow: If FormatWP add cell alignment.	962	\LWR@nullfonts: Fix: Nullify dollar inside filenames.	530
overpic: Added.	1002	\LWR@parsetablecols: Ignore spaces in col spec.	452
realscripts: Fix for subscripts in a lateximage.	1033	\LWR@section: Fix: Expansion in comparison.	390
sidenotes: If FormatWP add explicit HTML style.	1062	Fix: Math in section name.	391, 394
siunitx-v2: Improved \ensuremath.	1082	Fix: Nullify fonts inside HTML comment.	391
soul: If FormatWP, add explicit styles.	1106	\LWR@url: Made robust.	501
textcomp: Improved \interrobangdown.	1150	\TabularMacro: \newcommand instead of \relax to fix supertabular and xtab.	479
wrapfig: If FormatWP add explicit HTML style.	1211	\nameref: Made robust.	498
Added boolean WPMarkLOFT.	255	General: 2017/11/08	1
Added boolean WPMarkMath.	255	LWR@currentautosecpage: Added.	370
Added boolean WPMarkMinipages.	254	breakurl: Added.	681
Added boolean WPMarkTOC.	255	hyperref: Made robust. 850, 851, 854	
Added boolean WPTitleHeading.	255	hyperref: \Gauge added.	854
Docs: Added support page.	2	luatodonotes: Added.	909
Docs: Improper \prevdepth.	192	todonotes: Added.	1185
Docs: Reorganized math limitations	147	Added FootnoteDepth.	364
File: lwrap_mathjax.txt: Updated siunitx script.	307	Docs: HTML settings table.	107
Fix: Numbering and naming AMS math environments.	560	Docs: Reorganized HTML customization.	107
If FormatWP, shift section headings.	255	v0.44	
tabbing: Added.	421	\@currentlabelname: Adjustment for koma-script.	490
lateximage: Fix: Numbering and naming AMS math environments.	563	\HTMLTitle: Added.	362
center: If FormatWP use explicit text-align.	568	\LWR@addformatwpalignment: Fix for multicolumn alignment if FormatWP.	464
minipage: Added boolean WPMarkMinipages.	584, 585	\LWR@backgroundcolor: xcolor: Added \LWR@backgroundcolor.	1219
If FormatWP add a text frame.	583	\LWR@filestart: Add \HTMLTitle.	399
eqnarray: Fix: Numbering and naming AMS math environments.	556	Fix \HTMLAuthor.	399
		\LWR@listitem: Added list and trivlist.	425
		\LWR@patchlists: Added list and trivlist.	428
		\LWR@strresult: Fix: \providecommand.	435

<code>\LWR@textcurrentcolor: xcolor:</code>	Adjustment for koma-script. 216
Added	AMS environments: Fix: Groups
<code>\LWR@textcurrentcolor.</code> 1218	for lateximages. 639
<code>\addcontentsline: Automatic</code>	If pdfLaTeX, require T1 and UTF-8
<code>\LWR@newfloatanchor.</code> 510	encoding. 218
<code>\chapter: Add preamble for</code>	picture: <code>overpic</code> : Fix: Groups for
koma-script. 396	lateximages. 580
<code>\marginparBlock: Added.</code> 369	list: Added list and <code>trivlist.</code> 425
<code>\nopagecolor: xcolor: Fix for</code>	LWR@nestspan: Added list and
<code>\nopagecolor.</code> 1220	<code>trivlist.</code> 347
<code>\part: Add preamble for</code>	v0.45
koma-script. 395	<code>\@currentHref: Added.</code> 499
<code>\title: Added \thetitle.</code> 362	<code>\@donoparitem: Modified for HTML.</code> 423
General: 2017/11/22 1	<code>\@item: Modified for HTML.</code> 423
<code>algorithmicx: Improved comment</code>	<code>\@mklab: Modified for HTML.</code> 423
symbol. 637	<code>\CSSFilename: Improved filenames</code>
<code>atbegshi: Added.</code> 653	with underscores. 361
<code>cancel: Added.</code> 684	<code>\LWR@LwarpStart: Fix: Lateximages</code>
<code>changepage: Additional options.</code> 693	on incorrect pages with
<code>easy-todo: Added.</code> 748	MATHJAX. 402
<code>fancyref: Added.</code> 780	<code>\LWR@label@createtag: Fix: Labels</code>
<code>fixmetodonotes: Added.</code> 793	with underscores. 494
<code>fixme: Added.</code> 792	<code>\LWR@newautoidanchor: Fix: No</code>
<code>fontenc: Allowed after lwarp.</code> 806	anchor if frozen autoid. 506
<code>hang: Added.</code> 840	<code>\LWR@noLinkurl: Fix: Underscore in</code>
<code>ifoddpages: Added.</code> 857	URL. 501
<code>ltxtable: Added.</code> 906	<code>\LWR@notmemoirloadafter: Added.</code> 202
<code>luatodonotes: Improved.</code> 909	<code>\LWR@printpendingmpfootnotes:</code>
<code>lwarp-patch-komascript:</code>	Added. 368
Added. 1239	<code>\LWR@startref: Fix: Labels with</code>
<code>overpic: Fix: Groups for</code>	underscores. 496
lateximages. 1002	<code>\LWR@subhyperref: Improved URLs</code>
<code>pdfsync: Fixes.</code> 1016	with underscores. 500
<code>preview: Added.</code> 1027	<code>\LWR@subhyperrefclass: Improved</code>
<code>scrxextend: Added.</code> 1045	URLs with underscores. 500
<code>scrhack: Added.</code> 1048	<code>\LWR@tabledatacolumnstag: Fix:</code>
<code>scrlayer-notecolumn: Added.</code> 1050	Empty line between rows. 482
<code>scrlayer-scrpage: Added.</code> 1051	<code>\LWR@url: Improved URLs with</code>
<code>scrlayer: Added.</code> 1049	underscores. 501
<code>section: Added.</code> 1053	<code>\chapter: Add optional heading</code>
<code>soulpos: Added.</code> 1107	title for memoir. 396
<code>soulutf8: Added.</code> 1108	<code>\newpage: Added.</code> 602
<code>supertabular: Fix for caption.</code> 1133	<code>\normalmarginpar: Added.</code> 370
<code>tikz: Fix: Groups for</code>	<code>\reversemarginpar: Added.</code> 370
lateximages. 1163	<code>\section: Add optional heading</code>
<code>tocbasic: Added.</code> 1175	title for memoir. 396
<code>tocloft: Added \newlistentry.</code> 1183	<code>\tableofcontents: Fix: Empty</code>
<code>tocloft: Improved \newlistof.</code> 1183	<code>sidetoc.</code> 513
<code>tocstyle: Added.</code> 1184	Fix: Patch <code>\AtBeginDocument.</code> 513
<code>todonotes: Improved.</code> 1185	General: 2018/01/14 1
<code>todo: Added.</code> 1184	<code>array: Added.</code> 650
<code>typearea: Added expert</code>	babel-french: Robust
commands. 1191	commands. 344
<code>watermark: Added.</code> 1208	<code>backref: Added.</code> 662
<code>xcolor: Added</code>	<code>breakurl: Fix: Underscore in URL.</code> 681
<code>\LWR@currenttextcolorstyle.</code>	<code>changebar: Added.</code> 691
. 1218	<code>cite: Added.</code> 727
<code>xcolor: Added</code>	<code>continue: Added.</code> 736
<code>\LWR@findcurrenttextcolor.</code> 1218	<code>endfloat: Added.</code> 753
<code>xtab: Fix for caption.</code> 1234	<code>fancyvrb: Improvements.</code> 781–783

flafter: Added.	794	\LWRPrintStack: Name changed	
fltrace: Added.	802	from \PrintStack.	341
footnpag: Added.	810	General: 2018/01/23	1
fwlw: Added.	820	LWR@tabularpardepth added.	434
graphics: Improved URLs with		amsthm: Adapted to trivlist	
underscores.	833	changes.	645
hanging: Added.	841	mdframed: Fixes for svg math or	
hyperref: Fix: Underscore in		lateximage in title.	934
URL.	850, 851	mdframed: Fixes for footnotes.	935
lwrap-patch-memoir: Added.	1242	nththeorem: Adapted to trivlist	
memhfix: Added.	942	changes.	989
memoir: Added.	614	theorem: Adapt to trivlist	
natbib: Added.	969	changes.	1155, 1157
pagesel: Added.	1003	tabular: Fix: Tabular empty lines.	488
prettyref: Added.	1027	list: Fix: Stack unnesting.	426
subfigure: Added.	1130	v0.47	
subfig: Fix for subcaption end		\LWR@HTML@caption@begin: Fix:	
tag.	1129	Argument passed to	
subfig: Fix: Math in		\LWR@origcaption@begin.	509
subcaptions.	1127	\LWR@LwrapStart: Fix for svg math	
textfit: Added.	1153	in \nameref.	403
titleref: Added.	1167	\LWR@WPcell: Fix: Line wrap at	
turnthepage: Added.	1190	HTML hyphen.	463
Allows memoir's preloaded		\LWR@createautosec: Fix: Line	
packages.	207	wrap at HTML hyphen.	388
Docs: Fix for double hyphens.	80	\LWR@domulticolumn: Fix: Line	
Docs: Improved install		wrap at HTML hyphen.	473
instructions.	80	\LWR@floatbegin: Fix: Line wrap at	
Docs: Improved MiKTeX install		HTML hyphen.	504
instructions.	77	\LWR@htmlclosecomment: Add	
Docs: Moved table so doesn't		\mbox to prevent line breaks.	348
interfere with install docs.	76	\LWR@label@createtag: Fix: Line	
File: lwrap_mathjax.txt: Allow		wrap at HTML hyphen.	494
MATHJAX inside tabbing.	307	\LWR@newautoidanchor: Fix: Line	
File: lwrap_mathjax.txt: Allow		wrap at HTML hyphen.	506
MATHJAX inside verse.	307	\LWR@printopenlist: Fix: Line	
Fix: Empty sidetoc.	513	wrap at HTML hyphen.	423
Improved: Robust \, , \ , and		\LWR@startref: Fix: Line wrap at	
\textellipsis commands.	601	HTML hyphen.	495
Separate LWR@thisautoidWP for		\LWR@subsingledollar: Added svg	
word processor <div>s.	506	math image baseline adjust and	
thebibliography: Patched to		em sizing.	542
emphasize titles.	528	\LWR@subsingledollarsvg: Fix:	
minipage: Fix: Improper		Line wrap at HTML hyphen.	539
\prevdepth.	585	\captionlistentry: Fix: Line wrap	
v0.46		at HTML hyphen.	510
\LWR@closeparagraph: Fix: Tabular		\hypertoc: Fix: Line wrap at HTML	
empty lines.	357	hyphen.	517
\LWR@closeprevious: Fix: Stack		\hypertocfloat: Fix: Line wrap at	
unnesting.	342	HTML hyphen.	518
\LWR@forcenewpage: Fix: Improper		General: 2018/01/30	1
\prevdepth.	343	adjmulticol: Fix: Line wrap at	
\LWR@lookforpackagename: Fix:		HTML hyphen.	632
Spaces in \usepackage.	243	blowup: Added.	676
\LWR@popclose: Fix: Stack		caption: Added.	685
unnesting.	331	changepage: Fix for pagecheck	
\LWR@providelength: Added.	220	macros.	693
\LWR@pushclose: Fix: Stack		endheads: Added.	753
unnesting.	330	epigraph: Fix: Line wrap at HTML	
		hyphen.	762

hanging: Fix: Line wrap at HTML		\LWR@addtabularhrulecolor:	
hyphen.	841	colortbl: Added.	464
hang: Fix: Line wrap at HTML		\LWR@addtabularrulecolors:	
hyphen.	840	colortbl: Added.	465
keyfloat: Fix for SVG math in		\LWR@closetabledatcell:	
captions.	871	colortbl: Added.	437, 438
midpage: Fix: Line wrap at HTML		\LWR@lookforpackagename: Fix:	
hyphen.	948	Parsing similar package names.	242
multirow: Fix: Line wrap at HTML		\LWR@newautopagelabel: Fix: TOC,	
hyphen.	962	LOF, LOT links.	371
multitoc: Added.	964	\LWR@newhtmlfile: Fix: TOC, LOF,	
ntheorem: Fix: Line wrap at		LOT links.	385
HTML hyphen.	993	\LWR@nullfonts: Fix: \newline in	
realscripts: Fix: Line wrap at		title.	530
HTML hyphen.	1033	\LWR@parsedrequirepackagenames:	
scrextend: Fix: Line wrap at		Fix: Parsing similar package	
HTML hyphen.	1045	names.	241
sectionbreak: Added.	1053	\LWR@parsetablecols: Fix: Ignore	
sidenotes: Fix for SVG math in		optional tabular column	
captions.	1062	arguments.	453
subfig: Fix for SVG math in		\LWR@restoreorigformatting: Fix:	
captions.	1127	Spacing in SVG math,	
subfig: Fix: Support \nameref.	1127	lateximage, Tikz.	529
xurl: Added.	1236	\LWR@section: Fix: TOC, LOF, LOT	
<i>lwarpmk: pdfcrop</i> : Removed		links.	394
hires option for improved crop		\LWR@tabledatasinglecolumnntag:	
accuracy.	311	colortbl: Added.	458
lateximage: Added CSS style		\LWR@textcurrentfont: Added.	
option.	562	Improves font control.	595
Fix: Line wrap at HTML hyphen.	567	\centerline: Added.	569
center: Fix: Line wrap at HTML		\l@part: Adapts to classes without	
hyphen.	568	\part.	518
minipage: Fix: Line wrap at HTML		\leftline: Added.	569
hyphen.	583	\mbox: Nullified for HTML.	586
flushleft: Fix: Line wrap at HTML		\rightline: Added.	569
hyphen.	568	\thempfootnote: Removed	
flushright: Fix: Line wrap at HTML		\itshape.	367
hyphen.	568	General: 2018/02/14	1
enumerate: Fix: Line wrap at HTML		acronym: Added.	629
hyphen.	427	acro: Added.	627
itemize: Fix: Line wrap at HTML		chapterbib: Added.	698
hyphen.	426	colortbl: Added.	454, 464, 734
LWR@BlockClassWP: Fix: Line wrap		fancyref: Now directly	
at HTML hyphen.	352	supported.	780
v0.48		graphics: Fix: Virtual page size	
\@@@setcpageref: Fix for new v0.21		limited to a group.	833, 835
of cleveref.	730	hypcap: Added.	844
\@@@setcref: Fix for new v0.21 of		hypernat: Added.	845
cleveref.	729	hyperref: \texorpdfstring now	
\@@@setcrefrange: Fix for new		uses the TeX string.	853
v0.21 of cleveref.	729	luatodonotes: Improved	
\@biblabel: Improved bibliography		\todotoc.	910
label.	527	siunitx-v2: Changes fraction to	
\@item: Honors \makelabel.	423	symbol.	1085, 1086
\@maketitle: Fix: Errors with		siunitx-v2: Improved SVG	
IEEEtran class.	413	math.	1082, 1084
\LWR@LWarpStart: Adjusted space		siunitx-v2: Improved color	
around captions.	402	output.	1083
\LWR@ProvidesPackageDropB: Fix:		stfloats: Added.	1125
Options with braces.	246		

todonotes: Improved	
\todotoc.	1186
vmargin: Added.	1205
xfrac: Fix: Added groups around super/subscripts to localize LWR@nestspan changes. ...	1228
Docs: Converting an existing document.	97
Improved font control. ..	595, 596
tabular: colortbl: Added.	486
abstract: Allow optional name. ..	415
v0.49	
\LWR@addtabularcellcolor: xcolor: Added tabular row colors. ...	467
\LWR@domulticolumn: xcolor: Added tabular row colors. ...	473
\LWR@href: Fix: Adapt to classes. .	500
\LWR@printlength: Fix: Group printlen changes.	240
\LWR@url: Fix: Adapt to classes. ..	501
\affiliation: Fix: Adapts to classes which already provide.	408
\noalign: Fix: \noalign inside tabular.	483
General: 2018/02/19	1
amsmath: Fix: Patches for \eqref.	639
eso-pic: Fix for \AddToShipoutPicture.	768
figsize: Added.	790
fncineno: Added.	803
hypdestopt: Added.	845
hyphenat: Added.	856
lineno: Added.	890
luacolor: Added.	906
pagegrid: Added.	1002
pdfrender: Added.	1016
resizgather: Added.	1039
vertbars: Added.	1204
vwcol: Added.	1206
xcolor: Added tabular row colors.	454, 1223
Fix: Adapt to classes.	602
v0.50	
\@ensuredmath: Fix: Use \lateximage even if MATHJAX.	545
Improved svg math alt tags. ..	545
\LWR@footnotetext: Robustify macros.	366
\LWR@atbeginverbatim: Improved column alignment.	419
\LWR@doequation: Improved svg math display.	551
\LWR@doubledollar: Improved svg math alt tags.	544
Improved svg math display. ...	544
\LWR@htmlrefsectionfilename: Fix: svg math in a section name.	338
\LWR@newhtmlfile: Fix: svg math in a section name.	384
\LWR@nullfont: Fix: \underline in sectioning file name.	532
\LWR@overline: Added.	600
\LWR@subsingledollar: Fix: Use \lateximage even if MATHJAX.	542
Improved svg math alt tags. ..	542
\LWR@subsingledollarsvg: MD5 hash avoids duplicate svg math.	540
\LWR@vspace: Robustify macros. ..	605
\newline: Robustify macros.	602
\textsubscript: Robustify macros.	599
\textsuperscript: Robustify macros.	599
General: 2018/03/03	1
lwrap.css: Improved svg display math centering.	267
lwrap_one_limage.txt: Added.	306
amsmath: Fix: Upright tags for svgmath.	639
axodraw2: Added.	661
bytefield: Added.	684
dbfloatfix: Added.	741
diagbox: Added.	742
epstopdf: Added.	764
listings: Force flexible columns.	893
morefloats: Added.	954
nonfloat: Added.	987
ntheorem: Fix: Not standard nor amsthm selected.	995
pbox: Added.	1010
phfqit: Added.	1019
schemata: Added.	1044
siunitx-v2: Improved svg math alt tags.	1084
siunitx-v2: Improved units.	1082, 1086
siunitx: Fix: Loads xcolor.	1082
siunitx: Improved units.	573
xy: Added.	1236
lwrapmk: Error if \lateximages.txt does not exist.	311
lwrapmk: Error if lwrapmk.conf points to lwrap.	311
lwrapmk: Improved error messages.	311
lwrapmk: MD5 hash avoids duplicate svg math.	311
lwrapmk: Multiprocess support making lateximages.	311
AMS environments: Improved svg math display.	639
Fix: Load fontspec if necessary.	235
Robustify macros.	596
\lateximage: Fix: svg math in a section name.	566

MD5 hash avoids duplicate svg math.	564, 567	General: 2018/03/24	1
eqnarray: Improved svg math display.	556, 557	MATHJAX: Nullifies \ensuremath.	380
v0.51		lwrap_one_limage.txt:	
\@ensuredmath: Hashes		<i>pdftocairo</i> -noshrink added.	306
\ensuremath.	545	afterpackage: No longer	
\@item: Restored list label space.	424	required.	238
\LWR@HTMLsanitizeexpanded: Fix:		chemfig: Added.	698
Escapes double quotes.	378	chemformula: Added.	700
\LWR@LwrapStart: MathJax:		chemgreek: Added.	705
Nullifies \ensuremath.	403	chemmacros: Added.	705
\LWR@addbaselinemarker:		chemnum: Added.	725
Improved svg math baseline.	536	epstopdf-base: Added.	764
\LWR@atbeginverbatim: Adds		fancybox: Fix: Optional tag for	
vertical offset.	419	\item in a span.	777
\LWR@doequation: Fix:		grid: Added.	839
\addcontentsline inside svg		listings: Forces cleared options.	894
math. Provides an autoid		ltxgrid: Added.	905
anchor.	551	mhchem: Added.	944
\LWR@doubledollar: Fix:		tikz: Fix for \tikz macro.	1163
\addcontentsline inside svg		tikz: Fix for tikz with optional	
math. Provides an autoid		argument.	1163
anchor.	544	titling: Fix for \thanks mark.	1172
\LWR@findcurrenttextcolor:		<i>lwrapmk</i> : <i>pdfcrop</i> : Restored hires	
Added		option.	311
\LWR@findcurrenttextcolor		<i>lwrapmk</i> : <i>pdftocairo</i> -noshrink	
when no xcolor.	600	added.	311
\LWR@newautoidanchor: Fix: No		AMS environments: Fix:	
autoid is inside a lateximage.	506	\addcontentsline inside svg	
\LWR@singledollarmeasure: Fix:		math. Provides an autoid	
lateximage inside \mathcal{AMS}		anchor.	639
\text.	537	Docs: tikz limitations.	157
Fix: Honors text font around svg		Docs: Multiple authors and	
math.	537	affiliations.	130
Improved svg math baseline.	538	Docs: Things to avoid.	119
Typeset svg math only once		Docs: Updated Converting an	
during measurement.	537	existing document.	97
\LWR@subHTMLsanitize: Fix:		Fix: Remember original \# in	
Escapes double quotes.	377	case is redefined.	257
\LWR@subsingledollar: Fix:		Named HTML entity used for text	
\ensuredmath inside svg		dollar.	535
image.	542	lateximage: Added additional	
\LWR@subsingledollarsvg: Fix:		hashing option.	562
svg math with enclosed		Fix: lateximage inside \mathcal{AMS}	
lateximage.	539	\text.	563
SVG math baseline improved		Processing for complicated	
with invisible rule at corner.	541	display math.	566
\LWR@textcurrentcolor: xcolor:		alignat: amsmath: Fix: Added.	642
\LWR@textcurrentcolor if		eqnarray: Fix: \addcontentsline	
xcolor not loaded.	600	inside svg math. Provides an	
\addcontentsline: Add missing		autoid anchor.	556, 557
support for float mechanism if		LWR@displaymathother: Processing	
necessary.	510	for complicated display math.	547
No anchor ID if inside svg		LWR@equationother: Processing for	
image.	510	complicated display math.	547
\displaymathnormal: Processing		v0.52	
for complicated display math.	554	\@ensuredmath: Improved hashing	
\displaymathother: Processing for		expansion.	545
complicated display math.	554	\@mpfootnotetext: Fix: Paragraph	
		handling.	367
		\CustomizeMathJax: Added.	379

<code>\LWR@addbaselinemarker:</code>	If pdfLaTeX, allow other input encoding.	218
Warnings if	Restore <code>\kill</code> in a <code>lateximage</code> .	904
<code>lwarp_baseline_marker.png</code> is not present or if <code>graphicx/s</code> not loaded.	<code>tabbing</code> : Fix to allow inside <code>lateximage</code>	421
536	<code>lateximage</code> : Fix for hash expansion.	564
<code>\LWR@customizedMathJax</code> : Added.	v0.53	
379	General: 2018/04/01	1
<code>\LWR@doequation</code> : Fix: <code>equation*</code> now based on <code>equation</code> instead of <code>displaymath</code>	<code>lwarpmk</code> : Added	
551	<code>lwarpmk cleanimages</code>	311
Fix: <code>equation*</code> with <code>split</code>	<code>lwarpmk</code> : Added warning for corrupted images.	311
550	Docs: <code>lwarpmk cleanimages</code>	94
<code>\LWR@filenameno blanks</code> : Fix:	Docs: <code>lwarpmk pdftohtml</code>	94
<code>\FileDepth</code> with non-utf8 encoding.	v0.54	
376	<code>\xdlbfloat</code> : Honor <code>\centering</code> , etc. in floats.	505
<code>\LWR@href</code> : Fix: <code>#, %, &, ~, _</code> in URL.	<code>\LWR@afterendverbatim</code> : Added	
500	<code>vspace</code> argument.	419
<code>\LWR@nolinkurl</code> : Fix: <code>#, %, &, ~, _</code> in URL.	<code>\LWR@atbeginverbatim</code> : Improved column alignment.	419
501	<code>\LWR@endfloatalignment</code> : Honor <code>\centering</code> , etc. in floats.	507
<code>\LWR@nullfonts</code> : Fix:	<code>\LWR@floatalignment</code> : Honor <code>\centering</code> , etc. in floats.	506
<code>\texorpdfstring</code> in section names.	<code>\LWR@floatend</code> : Honor <code>\centering</code> , etc. in floats.	505
533	<code>\LateximageFontSizeName</code> : Defaults to <code>normalsize</code>	559
<code>\LWR@section</code> : Fix: Footnote numbering: Limited HTML comment if starred.	<code>\centering</code> : Added debug comment.	568
391	<code>\raggedleft</code> : Added debug comment.	569
Fix: Footnote numbering: Use short toc entry for HTMLDebug comments.	<code>\raggedright</code> : Added debug comment.	569
391	General: 2018/04/22	1
<code>\LWR@singledollarmeasure</code> : Added user-adjustable SVG math font scaling.	<code>*.lwarpmkconf</code> : Option	
538	<code>IndexLanguage</code> changed to <code>xindyLanguage</code>	267
<code>\LWR@url</code> : Fix: <code>#, %, &, ~, _</code> in URL.	<code>*.lwarpmkconf</code> : Option	
501	<code>pdftotextEnc</code> added.	267
<code>\LateximageFontScale</code> : Added user-adjustable SVG math font scaling.	<code>*.lwarpmkconf</code> : Option	
560	<code>xdyFilename</code> changed to <code>xindyStyle</code>	267
<code>\theHTMLTitleSeparator</code> : Fix:	<code>*.lwarpmkconf</code> : Option	
<code>\FileDepth</code> with non-utf8 encoding.	<code>xindyCodepage</code> added.	267
397	<code>lwarp.css</code> : Fix:	
General: 2018/04/01	<code>Text-decoration-skip</code> : auto.	267
1	<code>lwarpmk.conf</code> : Option	
<code>breakurl</code> : Fix: <code>#, %, &, ~, _</code> in URL.	<code>IndexLanguage</code> changed to <code>xindyLanguage</code>	266
681	<code>lwarpmk.conf</code> : Option	
<code>endfloat</code> : Updated for v2.6.	<code>pdftotextEnc</code> added.	266
753	<code>lwarpmk.conf</code> : Option	
<code>fancybox</code> : Initial support for <code>\VerbatimFootnotes</code>	<code>xdyFilename</code> changed to <code>xindyStyle</code>	266
774	<code>lwarpmk.conf</code> : Option	
<code>fancyvrb</code> : Initial support for <code>\VerbatimFootnotes</code>	<code>xindyCodepage</code> added.	266
781	<code>bibunits</code> : Added.	673
<code>graphics</code> : Added defaults.		
828, 829		
<code>graphics</code> : Updated for v1.1a.		
829		
<code>graphics</code> : Updated for v1.1b.		
829		
<code>hyperref</code> : Fix: <code>#, %, &, ~, _</code> in URL.		
850–852		
<code>nicefrac</code> : Added.		
982		
<code>url</code> : Added.		
1201		
<code>lwarpmk</code> : Fix: Memory overflow when spawning tasks.		
311		
<code>lwarpmk</code> : Fix: Skip image generation if from page 0.		
311		
Changed <code>FootnoteDepth</code> default to <code>\subsubsection</code>		
364		
Docs: Improved install instructions.		
78		
Fix: <code>MATHJAX</code> script line wraps. Reduced right margin.		
236		

chnpage: Added.	726	General: 2018/04/26	1
forest: Added.	811	<code>clrdblpg</code> : Added.	732
glossaries: Fix when not using babel or polyglossia.	825	Fix: <code>\centering</code> , etc. for koma-script.	504
gridset: Added.	839	Fix: QED symbols in lateximage.	646, 999
hyperref: Fix: <code>\hyperref</code> and <code>\hyperlink</code> with special chars in text.	851, 852	v0.56	
hyperref: Fix: <code>\ref</code> in <code>\hyperref</code> and <code>\hyperlink</code> caused nested link.	851, 852	<code>\LWR@addcdashline: arydshln</code> : Added.	463
lwarp-patch-memoir: Update for v3.7g.	1246	<code>\LWR@admmulticolvertrulecolor</code> : Adds support for dashed vertical rules.	470
magaz: Added.	913	Adds support for double vertical rules.	470
ragged2e: Fix: <code>\centering</code> , etc.	1032	<code>\LWR@addtabularhrulecolor</code> : Adds support for <code>arydshln</code> dashed rules.	464
textcomp: Fix for <code>\textperthousand</code>	1150	Adds support for double <code>\hlines</code> and <code>\midrules</code>	464
tikz: Fixes for <code>\pgfpicture</code> , minipages, fit, align, font. . .	1163	<code>\LWR@addtabularrulecolors</code> : Adds support for dashed vertical rules.	465
<i>lwarpmk</i> : Added <code>pdftotextenc</code>	311	Adds support for double vertical rules.	465
<i>lwarpmk</i> : Added <code>xindycodepage</code>	311	<code>\LWR@closeparagraph</code> : Added support for <code>parnotes</code>	357
<i>lwarpmk</i> : Changed language to xindylanguage.	311	<code>\LWR@domulticolumn</code> : Adds support for dashed vertical rules.	472
<i>lwarpmk</i> : Changed xdyfile to xindystyle.	311	Adds support for double vertical rules.	472
<i>lwarpmk</i> : Improved error if configuration file does not exist.	311	<code>\LWR@floatbegin</code> : Adds a <code><class></code> per float package style.	504
<i>lwarpmk</i> : Increased prominence for error for an unknown command.	311	<code>\LWR@openparagraph</code> : Added support for <code>parnotes</code>	355
<i>lwarpmk</i> : Verifies HTML version exists before <code>lwarpmk</code> images.	311	<code>\LWR@parsebarcolumn</code> : Adds support for double vertical rules.	445
<i>lwarpmk</i> : Verifies image references before <code>lwarpmk</code> images.	311	<code>\LWR@parsecoloncolumn: arydshln</code> : Added.	446
Add: <code>pdftotextEnc</code>	229	<code>\LWR@parsesemicoloncolumn</code> : <code>arydshln</code> : Added.	446
Add: <code>xindyCodepage</code>	229	<code>\LWR@tabledatacolumn: tag</code> : Fix: <code>\morecmidrules</code>	481
Added early check for disallowed packages.	205	<code>\LWR@textcurrentfont</code> : Added <code>span.textbf</code> , etc.	595
Docs: BibTeX.	132	General: 2018/05/12	1
Docs: Macros in sectioning names.	119	<code>*.lwarpmkconf</code> : Records <code>--shell-escape</code>	267
Never load <code>aecompl</code>	205	<code>lwarp.css</code> : Added <code>div.textbf</code> , etc.	267
Option <code>IndexLanguage</code> changed to <code>xindyLanguage</code>	229	<code>lwarp.css</code> : Added <code>span.textbf</code> , etc.	267
Option <code>xdyFilename</code> changed to <code>xindyStyle</code>	228	<code>lwarpmk.conf</code> : Records <code>--shell-escape</code>	266
verse: Fix: Line spacing.	417	<code>arydshln</code> : Added.	431, 651
v0.55		<code>lua-check-hyphen</code> : Added.	906
<code>\@xdlbfloat</code> : Fix: Float optional args.	505	<code>paralist</code> : Fixes for <code>compactenum</code> , <code>compactitem</code> , <code>compactdesc</code>	1003
<code>\LWR@LwarpStart</code> : Fix: Overfull boxes in <code>lateximages</code>	401	<code>parnotes</code> : Added.	1007
<code>\LWR@nullfonts</code> : Removed extraneous space which appeared in file links.	532	<code>quoting</code> : Added.	1032
<code>\LWR@phantomsection</code> : Fix: <code>\ForceHTMLTOC</code> with <code>\phantomsection</code>	608		

tocenter: Added.	1178	Improved print/HTML output selection.	478
underscore: Added.	1194	\newfloat: rotfloat: Added float styles.	1043
<i>lwarpmk</i> : Added		rotfloat: Fix for listof sideways floats.	1043
lwarpmk pdftosvg.	311	\parbox: Improved print/HTML output selection.	586
<i>lwarpmk</i> : Supports		\raisebox: Improved print/HTML output selection.	590
--shell-escape.	311	\reflectbox: Improved print/HTML output selection.	838
Added \thinspace.	601	\resizebox: Improved print/HTML output selection.	838
Docs: lwarpmk pdftosvg	94	\rotatebox: Improved print/HTML output selection.	836
LWR@blocktextcurrentfont: Added		\rule: Fix: Colored rules.	607
div.textbf, etc.	596	\scalebox: Improved print/HTML output selection.	837
v0.57		\textcolor: xcolor: New system for switching print and HTML outputs.	1220
\BlockClassSingle: Improved print/HTML output selection.	352	General: 2018/06/06	1
\InlineClass: Improved print/HTML output selection.	352	MATHJAX: Supports \footnote, \footnotemark.	380
\LWR@href: Fix: Text catcodes.	500	lwrap.css: Added ruled, boxed, boxruled floats.	267
\LWR@listof: Fix: Provide \l@name if not defined.	514	lwrap.css: Increased float vertical margins.	267
\LWR@singledollarmeasure: Fix: Dynamic inline math expressions.	537	algorithm2e: Added.	633
\LWR@subhyperref: Fix: Text catcodes.	500	bigdelim: Improved print/HTML output selection.	674
\LWR@subhyperreftext: Fix: Text catcodes.	500	breakurl: Fix: Text catcodes.	681
\LWR@subsingledollar: Fix: Dynamic inline math expressions.	542	colortbl: New system for switching print and HTML outputs.	734, 735
\LWR@subsingledollarsvg: Fix: Dynamic inline math expressions.	540	ellipsis: Added	
\LWR@vspace: Improved print/HTML output selection.	605	\midwordellipsis.	752
\MathImageAltText: Added.	534	errata: Added.	766
\PackageDiagramAltText: Added.	534	float: Added float styles.	795
\StartDefiningMath: Added.	333	float: Fix: Do not pre-define \l@name.	795
\boxframe: xcolor: Fix: Colored \boxframe.	1223	ltablex: Added.	905
\colorbox: xcolor: New system for switching print and HTML outputs.	1220	marginnote: Fix: Long optional argument.	917
\colorboxBlock: xcolor: New system for switching print and HTML outputs.	1220	multirow: Improved print/HTML output selection.	962
\fbboxBlock: Improved print/HTML output selection.	588	register: Added.	1036
\fcolorbox: xcolor: New system for switching print and HTML outputs.	1221	subcaption: Fix: \subref.	851
\framebox: Improved print/HTML output selection.	587	trimclip: Added.	1188
\inlinemathother: Added.	334	vowel: Added.	1205
\makebox: Improved print/HTML output selection.	586	xellipsis: Added.	1225
\mbox: Improved print/HTML output selection.	586	xfrac: Improved print/HTML \scalebox control.	1228
\multicolumnrow: multirow: Improved print/HTML output selection.	963	xltabular: Added.	1229
		xpiano: Added.	1231
		<i>lwarpmk</i> : Improved code factoring.	311
		<i>lwarpmk</i> : Improved error handling.	311

Docs: Recompiling <i>lwarpmk</i> or css files.	188	attachfile2: Added.	655
Docs: Recreating the index for <i>lwarpmk</i> source.	186	attachfile: Added.	654
New system for switching print and HTML outputs.	251	cases: Added.	690
minipage: Improved print/HTML output selection.	582	imakeidx: Added.	858
BlockClass: Improved print/HTML output selection.	351	index: Added.	862
fminipage: Improved print/HTML output selection.	589	intopdf: Added.	864
LWR@BlockClassWP: Improved print/HTML output selection.	352	<i>lwarpmk</i> : Added makeindex and xindy options.	311
v0.58		<i>lwarpmk</i> : Added <code>-p</code> option for project name.	311
\LWR@HTML@caption@begin: Improved print/HTML output selection.	509	<i>lwarpmk</i> : Added optional list of names for lwarpmk printindex and <code>/cmdslwarpmk htmlindex</code>	311
\LWR@HTML@caption@end: Improved print/HTML output selection.	509	<i>lwarpmk</i> : Glossary generation now uses <i>makeglossaries</i>	311
\LWR@HTML@ref: Improved print/HTML output selection.	497	<i>lwarpmk</i> : lwarpmk clean removes all <code>*.ind</code> and <code>*.idx</code> files.	311
\LWR@doindexentrysubsub: Adds support for <code>\see</code> , <code>\seealso</code> , <code>\emph</code> , <code>\textbf</code> , etc.	524	Added makeindex option.	230
\LWR@hyperindexrefnullified: Adds support for <code>\see</code> , <code>\seealso</code> , <code>\emph</code> , <code>\textbf</code> , etc.	525	Added xindy option.	230
\LWR@hyperindexrefsubtwo: Adds support for <code>\see</code> , <code>\seealso</code> , <code>\emph</code> , <code>\textbf</code> , etc.	526	Added option <code>makeindexStyle</code>	228
\LWR@indexitem: Accepts optional arg for <code>repeatindex</code>	520	Docs: Index, <i>makeindex</i> , <i>imakeidx</i>	134
\dotfill: Improved print/HTML output selection.	602	Docs: Misplaced <code>\omit</code>	192
\hfill: Improved print/HTML output selection.	602	Fix: memoir and <code>ccaption</code>	207
\hrulefill: Improved print/HTML output selection.	602	Improved print/HTML output selection.	601
\printindex: Fix: Extra <code>\newpage</code> to flush pending <code>\index</code> writes.	914	Replaced each <code>\csuse</code> with <code>\@nameuse</code> to force error if undefined.	1
General: 2018/07/07	1	tabbing: Improved print/HTML output selection.	421
*.lwarpmkconf: Added option <code>makeindexstyle</code>	267	v0.59	
*.lwarpmkconf: Added options <code>makeindex</code> and <code>xindy</code>	267	\LWR@addbaselinemarker: Uses <code>.eps</code> if DVI <i>latex</i>	536
*.lwarpmkconf: Generated <code>\AtBeginDocument</code>	267	\LWR@latexmkcmd: Fix: <code>--shell-escape</code> with <i>latexmk</i>	262
<i>lwarpmk</i> .xdy: Requires <code>makeindex.xdy</code>	306	\LWR@writeconf: Compilation commands now preassigned by <i>lwarpmk</i> instead of being computed by <i>lwarpmk</i>	266
<i>lwarpmk</i> .xdy: Supports bold, italic.	306	\[: Fix with <code>\displaymathnormal</code>	545
<i>lwarpmk_html.ist</i> : Added.	305	General: 2018/09/07	1
<i>lwarpmk.conf</i> : Added option <code>makeindexstyle</code>	266		
<i>lwarpmk.conf</i> : Added options <code>makeindex</code> and <code>xindy</code>	266		
<i>lwarpmk.conf</i> : Generated <code>\AtBeginDocument</code>	266		
array: Improved print/HTML output selection.	650		

Slunits: Added.	1064	General: 2018/09/19	1
accsupp: Added.	626	tabular: Improved memory	
amsmath: Moved from the <i>lwarp</i>		management: Global boolean.	433
core.	639	tabular: Improved memory	
asymptote: Added.	653	management: Not using	
axessibility: Added.	660	xstring.	434
breqn: Added.	682	2up: Added.	621
bxpapersize: Added.	684	booklet: Added.	677
canoniclayout: Added.	685	bophook: Added.	680
chemformula: Fix for \backslash NMR.	722	diagbox: Fix for par tags.	743
draftcopy: Added.	746	drafftfigure: Added.	746
epstopdf-base: Improved.	764	fancytabs: Added.	780
epstopdf: Improved.	764	fullminipage: Added.	817
fnbreak: Added.	802	grid-system: Added.	839
graphics: Fix: Expand filename.	834	layaureo: Added.	880
graphics: Now works with .pdf		leading: Added.	883
and .eps filename extensions.	833	listings: Fix for HTML entities.	894
nccfancyhdr: Added.	970	listings: Fix if inside a list.	896, 899
pdftricks: Added.	1017	multirow: tabular: Improved	
pst-eps: Added.	1028	memory management: Not	
pstricks: Added.	1029	using xstring.	962
units: Added support for		thumbs: Added.	1162
MathJax.	1199	thumb: Added.	1162
xunicode: Added.	1235	widows-and-orphans: Added.	1209
<i>lwarpmk</i> : Added			
<i>lwarpmk epstopdf</i>	311	v0.61	
<i>lwarpmk</i> : Consolidated compiling		\backslash DeclareGraphicsExtensions: Fix:	
options into printlatexcmd		EPS for DVI \LaTeX	826
and HTMLlatexcmd.	311	\backslash LWR@HTMLLatexCmd: Added	
<i>lwarpmk</i> : Double instead of		HTMLLatexCmd option.	266
single-dashed <code>--shell-escape</code>		Added PrintLatexCmd option.	266
option.	311	\backslash LWR@addcompilecmd: Removed	
<i>lwarpmk</i> : Error if <i>lwarpmk.conf</i>		spaces.	261
format changed.	311	\backslash LWR@closetabledatocell: Fix: Par	
<i>lwarpmk</i> : Warning if operating		tags in tabular.	436
system changed.	311	\backslash LWR@hyperindexrefnullified:	
Added option <code>dvipdfmx</code>	231	Made robust,	525
Added option <code>dvipdfm</code>	231	\backslash LWR@listof: Fix: newfloat lists.	514
Added option <code>dvips</code>	231	\backslash LWR@ropseq: Added spaces.	226
Docs: <i>lwarpmk epstopdf</i>	94	\backslash RequirePackage: Support up to 20	
File: <i>lwarp_mathjax.txt</i> : Fix:		packages.	243
Removed chapter number from		\backslash inlinemathnormal: Changed	
tagged non-numeric MATHJAX		name from \backslash StopDynamicMath	
equations.	307	to \backslash inlinemathnormal.	334
File: <i>lwarp_mathjax.txt</i> :		\backslash inlinemathother: Changed name	
Updated to MATHJAX v2.7.4.	307	from \backslash StartDynamicMath to	
picture: Added an alt tag.	580	\backslash inlinemathother.	334
v0.60		\backslash lwarpsetup: Added.	227
\backslash LWR@clearmidrules: tabular: Fix		General: 2018/10/13	1
for midrules.	460	<i>lwarp.css</i> : Footnotes text align	
\backslash LWR@parsenormalcolumn: tabular:		left.	267
Improved memory		<i>lwarp.css</i> : Minipage table and	
management: Not using		footnotes: tighter margin.	267
xstring.	447	chkfloat: Added.	726
\backslash LWR@tabledatasinglecolumn: tag:		cmdtrack: Added.	733
tabular: Improved memory		copyrightbox: Added.	736
management: Not using		dprogress: Added.	746
xstring.	458	epsfig: Added.	763
\backslash LWR@tabularendofline: Fix:		graphics: Fix: EPS for DVI \LaTeX	831
Slowdown for long tables.	441	graphics: Set keys before using	
		filename, for epsfig.	834

lua-visual-debug: Added.	906	\theHTMLTitleSeparator:	
pdfprivacy: Added.	1016	Refactored.	397
psfrag: Added.	1028	General: 2018/11/19	1
psfrag: Added.	1027	\textbf and related: Improved	
pstool: Added.	1029	font detection.	591
refcheck: Added.	1036	lwrap.css: Added css for xfrac,	
srcltx: Added.	1110	nicefrac.	267
srctex: Added.	1111	lwrap.css: Fixed css for	
supertabular: Fix for caption w/o		\textup.	267
opt arg.	1133	lwrap.css: Reduced margins in	
thinsp: Added.	1157	titlepage.	267
theadcol: Added.	1160	lwrap_formal.css: Fix: Font for	
uspace: Added.	1202	verse.	301
vpe: Added.	1206	2in1: Added.	621
xbmks: Added.	1215	CJKutF8: Prevented unless xeCJK.	728
xTAB: Fix for caption w/o opt		CJK: Prevented unless xeCJK.	727
arg.	1234	asymptote: Improved alt tags.	653
Added HTMLLatexCmd option.	230	bitpattern: Added.	676
Added PrintLatexCmd option.	230	calc: Fix: Required for print	
Docs: \tracinglwrap	248	version.	238
Docs: HTML entities.	120	chngepage: Fix: Loads	
Docs: Compiling using custom		lwrap-chngepage.	726
shell commands.	173	ctexpatch: Added patch.	615
Docs: Fonts.	100	flippdf: Added.	794
Docs:		graphics: Fix: Filename	
HTMLDebugComments	107, 248	expansion.	832
Docs: Multiple indexes.	197	graphics: Fix: FormatWP.	831
Don't write configuration files if		musicography: Added.	965
processing pstool image.	260	nicefrac: Improved font control	
Spaces redefined		and css, honors nice, ugly.	982
\AtBeginDocument.	601	notespages: Added.	988
v0.62		octave: Added.	1000
\@partcntformat: Added for ctex.	389	pdfcomment: Added.	1012
\@partnameformat: Added for ctex.	389	pdfmarginpar: Added.	1013
\InlineClass: Added optional		register: Updated to v1.8.	1036
word-processing style. Replaces		rviewport: Added.	1043
\LWR@HTMLtextstyle.	352	semantic-markup: Added.	1055
\LWR@PreloadedPackage: Added.	569	textcomp: Fix conflict with	
\LWR@ProvidesPackagePass: Fix:		xunicode.	1151
Unknown option error.	245	tram: Added.	1187
\LWR@endofLine: Extra space if		twoup: Added.	1190
optional arg.	603	ulem: Improved compatibility	
\LWR@filestart: Refactored.	399	with CJKulem.	1192
\LWR@isolate: Added.	222	ulem: Now works in a	
\LWR@textcurrentfont: Added		lateximage.	1192
print version.	600	unitsdef: Added.	1200
Tracks depth to avoid nesting		units: Improved font control and	
repeated font changes.	595	css, honors loose, tight.	1199
\colorboxBlock: xcolor: Fix: Horiz		xcolor: Fix: Horiz white space.	1222
white space.	1220, 1221	xexchangebar: Added.	1225
\fcolorbox: Fix: No longer requires		xfrac: Improved css.	1228
xifthen.	576	xunicode: Fix conflict with	
\fcolorboxBlock: xcolor: Fix: Horiz		textcomp.	1235
white space.	1221, 1222	Added early checks for CJK,	
\l@chapter: Don't define if no		CJKutF8.	205
\chapter. Fix for algorithm2e.	519	Docs: asymptote.	159
\slshape: Added.	598	Docs: miktex-poppler-bin-*	81
\textup: Fixed WP span class.	593	Docs: <i>MiKTeX Console</i>	77
\theHTMLSection: Added.	397	Docs: Improved MiKTeX install	
\theHTMLTitleSection: Added.	397	instructions.	77

Docs: UTF-8 locale.	176	Added pTeXsupport.	201
File: lwarp_mathjax.txt:		Docs: \linkhomenam.	107
Removed inoperable siunitx		Docs: \sidetocname.	109
extension.	307	Fix: Default \LWR@mdfive.	217
Logos: CSS instead of [,]		Improved titles.	935, 936
<sub>.	609	pTeX: Encoding.	218
Logos: Fix for X _Y TeX logo if		pTeX: Load upquote.	219
graphics is not loaded.	609	pTeX: No newunicodechar.	218
Logos: Improved CSS.	609	LWR@BlockClassWP: Fix for xeCJK.	352
Logos: Made robust.	609	v0.64	
fcolorminipage: xcolor: Fix: Horiz		\LWR@HTMLLatexCmd: utarticle and	
white space.	1223	related: Added.	265
Fix: No longer requires xifthen.	577	\LWR@checkloadfilename:	
fminipage: Fix: Horiz white space.	590	Prevented bitfield, doublespace,	
LWR@blocktextcurrentfont: Added		newthm, rplain, si.	242
print version.	600	\LWR@section: Support for	
v0.63		ujarticle and related.	392
\LWR@HTMLLatexCmd: ujarticle and		\enskip: Made robust.	604
related: Compile options.	265	\qqquad: Made robust.	603
\LWR@LwarpStart: Fixes for xeCJK.	401	\quad: Made robust.	603
\LWR@atbeginverbatim: Fix for		\theHTMLTitleSeparator: Added	
xeCJK.	419	utarticle and related.	397
\LWR@checkloadbefore: Added.	203	General: 2018/12/08	1
\LWR@checkloadfilename: Added		addlines: Updated to v0.3.	633
to reduce number of lwarp-*		biblatex: Added patch for CTeX.	669
files.	242	bsheaders: Added.	683
\LWR@compileuplatex: Added.	262	gmeometric: Added.	826
\LWR@createautosec: Fix for		marginal: Added.	916
xeCJK.	388	rmpage: Added.	1041
\LWR@earlyclassloadnever:		scrlayer-scrpage: Fixes.	1051
Added.	204	scrlayer: Fixes.	1050
\LWR@filestart: Fix: Break ligature		scrpage2: Added.	1052
for luatexko.	399	ujarticle and related: Improved	
\LWR@firstoffive: Added.	222	\today.	614
\LWR@htmlclosecomment: Fix: Break		Added utarticle and related.	614
ligature for luatexko.	348	v0.65	
\LWR@isolate: Fix for xeCJK.	222	\LWR@LwarpEnd: Improved css for	
\LWR@notltjloadafter: Added		page layout.	404
more classes.	202	\LWR@LwarpStart: Improved css for	
Added.	202	page layout.	403
\LWR@subhtmlElementclass: Fix for		\LWR@PreloadedPackage:	
xeCJK.	349	\AtBeginDocument to avoid	
\LinkHome: Fix: Print version.	339	option clashes.	569
\linkhomenam: Added.	339	\LWR@hyperindexrefnullified:	
General: 2018/12/03	1	Added \textsi.	525
lwarp.css: Added css for vertical		\LWR@newhtmlfile: Error if	
writing.	267	duplicate file name.	383
lwarp.css: Improved css for		Improved css for page	
mdframed.	267	layout.	383, 385
amsthm, mdframed: Fix for		\LWR@nullfonts: Added \textsi.	530
enforced load order.	643	\LWR@restoreorigformatting: Fix:	
emumitem: v3.6: Nullify		tabular*.	529
\DrawEnumitemLabel.	762	\enskip: Changed to Unicode EN	
geometry: Fix for bxjs* classes.	237	SPACE.	604
mdframed: Avoid thin rules.	933	\quad: Changed to Unicode EM	
mdframed: Improved font		SPACE.	603
control.	936, 937	\sishape: Added \sishape.	598
stfloats: Adapted to ltj* classes.	1125	\textsi: Added.	594
xpinyin: Added.	1231	General: 2018/12/22	1
zhlineskip: Added.	1237		

lwrap.css: Added \sishape, \textsi.	267	Improved HTML formatting.	357
lwrap.css: Improved css for page layout.	267	\LWR@closeparagraph@br: Factored.	356
lwrap.css: Improved css for quotations.	267	\LWR@fboxstyle: Use current text color.	588
lwrap.css: Siderocto left for improved \marginpars.	267	\LWR@filenamenoblanks: Fix: Section names detokenized.	374
lwrap_formal.css: Siderocto left for improved \marginpars.	301	Fix: Section names with macros.	375
lwrap_sagebrush.css: Siderocto left for improved \marginpars.	297	Fix: Section names with percent.	375
bounddvi: Added.	680	Improved file name generation.	373
embrac: Added.	752	Limits filename length.	376
footnoterange: Added.	810	\LWR@findcurrenttextcolor: Fix: Color if xcolor not loaded.	600
gentombow: Added.	821	\LWR@htmlfileref: No longer use zref.	492
geometry: Fix for bxjs* classes.	237	\LWR@htmlsectionfilename: Sanitize underscores.	337
graphics: Added \includegraphics alt key.	575, 827, 829, 830, 833, 834	\LWR@hyperindexrefsbtwo: Fix: Long index entries.	526
ltjext: Added.	899	\LWR@indentHTML: Added.	346
multicolrule: Added.	958	\LWR@lateximagedepthref: No longer use zref.	492
multicol: Added \docolaction.	958	\LWR@lateximagenumberref: No longer use zref.	492
plarydshln: Added.	1024	\LWR@nameref: No longer use zref.	492
plextarydshln: Added.	1025	\LWR@nullfonts: Logos.	532
plextcolortbl: Added.	1026	\LWR@openparagraph: Improved HTML formatting.	356
plext: Added.	1024	\LWR@section: Fix: TOC, LOF, LOT links.	394
pxatbegshi: Added.	1030	Improved HTML formatting.	393, 394
pxeveryshi: Added.	1030	\LWR@setexparray: Fix with \par.	332
pxftright: Added.	1030	\LWR@setref: No longer use zref.	492
pxjahyper: Added.	1031	\LWR@simplifiname: Added.	372
tascmac: Added.	1140	\LWR@startref: No longer use zref.	495
versonotes: Added.	1204	\LWR@stoppars: Improved HTML formatting.	359
Added early checks for jarticle, tarticle, and related.	205	\LWR@subhtml-elementclass: Improved HTML formatting.	349
Fix for \rensuji.	614	\LWR@subhyperrefclass: Improved HTML formatting.	500
Fix space between class and id.	353	\LWR@subinlineimage: Improved HTML formatting.	501
tabular: Added support for plect.	485	\LWR@write@lwraplabel: No longer use zref.	493
Fix: tabular*.	485	\LWR@writeconf: Added ImagesDirectory and ImagesName.	266
Fix: Rule color.	486	\LinkHome: Fix: Document cross-references.	339
minipage: Refactored to later allow Japanese <t/y> argument.	582	\UseMinipageWidths: Added,	582
LWR@figcaption: Uses <figurecaption> instead of <figcaption>.	508	\fbox: Fix: Removed extra space.	588
v0.66		\minipagefullwidth: Made \global.	582
\@mpfootnotetext: Improved HTML formatting.	367	\rotatebox: Improved HTML formatting.	836
\IgnoreMinipageWidths: Added,	582	\rule: Improved HTML formatting.	607
\LWR@@footnotetext: Improved HTML formatting.	366	\scalebox: Improved HTML formatting.	837
\LWR@LwrapStart: Fix: TOC, LOF, LOT links.	403	\textgreater: Made robust.	336
\LWR@checkloadfilename: Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs.	242		
\LWR@closeparagraph: Fix: Combined span, tabular, and lateximage.	357		

\textless: Made robust.	336	\LWR@doequation: xfakebold:	
General: 2019/02/08	1	Added support.	551
LWR@currentautosecpage: Fix		\LWR@doubledollar: xfakebold:	
for LOF, LOTfloat in home page.	370	Added support.	544
lwrap.css: Added niceframe. . .	267	\LWR@filenamenoblanks: Improved	
lwrap.css: Improved css for		file name generation.	373
definition lists.	267	\LWR@lookforpackagename:	
lwrap_formal.css: Improved		easyReview: Supported.	243
css for table notes.	301	\LWR@nullfonts: Add'l symbols. .	530
lwrap_one_image.txt: Image		\LWR@simplifycustom: Added. . .	373
directory and prefix.	306	\LWR@subsingledollar: xfakebold:	
acronym: Fix for acronym in		Added support.	542
caption.	630	\LWR@subsingledollarsvg:	
acronym: No longer uses zref. .	631	xfakebold: Added support. 540, 541	
ar: Added.	648	General: 2019/02/23	1
ed: Added.	751	academicons: Added.	624
extramarks: Updated to v3.10. .	772	bbding: Added.	663
fancybox: Improved HTML		changes: Added.	693
formatting.	774	color: Fix for version number. .	734
fancyhdr: Updated to v3.10. . .	778	dingbat: Added.	744
graphics: Improved HTML		eurosym: Added.	771
formatting.	833	fitbox: Added.	791
kotexutf: Patch for references. .	616	fontawesome5: Added.	805
memoir: Docs re: version		fontawesome: Added.	804
numbers.	168	foreign: Added.	810
multicolrule: Updated for v1.2. .	958	gloss: Added.	823
nameauth: Added.	968	karnaugh-map: Added.	867
register: Verified for v1.9. . . .	1036	marvosym: Added.	918
subcaption: Added.	1126	multicap: Added.	957
tocbasic: Updated to v3.26a. .	1175	nomencl: Added.	986
truncate: Added.	1189	notes: Added.	987
zref: No longer used.	240	pifont: Added.	1023
lwrapmk: Added		struktex: Added.	1125
ImagesDirectory and		textcomp: Nullify in filenames. 1152	
ImagesName.	311	typicons: Added.	1192
lwrapmk: Fix for cLeanImages. 311		umoline: Added.	1194
Added early checks for colortab,		xfakebold: Added support.	534
epsf, hyper, picinpar, picins,		xfakebold: Added.	1227
sistyle, ucs.	205	xunicode: Nullify in filenames. 1235	
Added option ImagesDirectory. 228		AMS environments: Added	
Added option ImagesName.	228	xfakebold support.	639
Added support for indentfirst. .	360	eqnarray: xfakebold: Added	
Docs: Updated Converting an		support.	557
existing document.	97	v0.68	
Fix: Minipages inside multicol. 958		\LWR@footnotetext: Factored for	
Improved HTML formatting.	782	multiple foot boxes.	365
Package dates added where		\LWR@checkloadfilename:	
possible.	621	Prevented alg, algorithmic,	
Sanitize filenames.	231	fncylab, pdfcpot.	242
tabular: Fix: Minipages inside		\LWR@printpendingfootnotes:	
tabular.	488	Factored for multiple footnote	
lateximage: Added \BaseJobname		boxes.	368
for multiple projects.	562	\LWR@tabular@warpprintonly:	
Improved HTML formatting.	564	Added.	484
minipage: Honor		General: 2019/03/05	1
\LWR@forceminipagefullwidth.		bigfoot: Added.	675
.	584	fnpara: Added.	803
v0.67		footnotebackref: Added.	809
\FilenameNullify: Added.	533, 601	layouts: Added.	880
\FilenameSimplify: Added.	373, 382	listings: Fix for listings v1.7. . .	899

longtable: Improved error handling.	903	v0.70	\LWR@closeparagraph: Reduced underfull \hbox warnings.	357
manyfoot: Added.	914		\LWR@lookforpackagename: changes: Updated to v3.1.2.	243
niceframe: Added.	983		\LWR@mathjaxfilename: Added.	361
perpage: Added.	1018		\LWR@restoreorigformatting: Fix: & in a lateximage.	529
showtags: Added.	1060		\MathJaxFilename: Added.	361
tablefootnote: Added.	1135		\enddocument: If labels changed, require recompile before making limages.	405
threeparttable: Added.	1161		\framebox: Fix: Accept long arg.	587
threeparttable: Fix for caption type.	1160		\makebox: Fix: Accept long arg.	586
lwarpmk: Improved error handling if incomplete compile.	311		Fix: Ignore width of Opt.	586
Prevented alg, algorithmic, fncylab, pdfcpot.	205		Fix: No width given.	586
tabular: Fix: \warpprintonly inside tabular.	486		General: 2019/04/03	1
v0.69			autonum: Added.	658
\LWR@maybetocdata: Added support for tocdata.	516		changelayout: Added.	692
\framebox: Fix: Handle paren arg.	587		changes: Updated to v3.1.2.	693
\hypertoc: Added support for tocdata.	517		inputtrc: Added.	863
\hypertocfloat: Added support for tocdata.	518		mathtools: Added.	925
\makebox: Fix: Handle paren arg.	586		metalogo: Added.	943
\multicolumnrow: multirow: Error if \multirow without \mrowcell.	963		metalogo: Used in print mode.	943
General: 2019/03/21	1		textcomp: Fix for \textinterrobang.	1150
array: Fix for \tabularnewline.	650		textpos: Added optional arg to textblock.	1153
ctable: Added.	737		xunicode: Fix for \textinterrobang.	1235
eqlist: Added.	765		AMS environments: Refactored.	639
eqparbox: Added.	765		Ensure vector font.	219
ftcap: Added.	816		File: lwrap_mathjax.txt: Loads autoload-all.js extension.	307
graphics: Warning if using scale option.	829		File: lwrap_mathjax.txt: Updated to MATHJAX v2.7.5.	307
keyfloat: Updated for v2.00.	870		Logos: Improved for metalogox, lateximages.	609
listliketab: Added.	899		LWR@nestspan: Improved minipage, \parbox inside a span.	347
longtable: Fix for \tabularnewline.	903	v0.71	\@mpfootnotetext: Improved HTML formatting.	367
minitoc: Added.	949		Reduced underfull \hbox warnings.	367
multirow: Error if \multirow without \mrowcell.	962		\LWR@closeparagraph: Flush left captions.	357
rotating: Requires graphicx.	1041		\LWR@closetabledatcell: Fix: Tabular par tags.	437
supertabular: Fix: Clear caption after use.	1133		\LWR@stoppars: Reduced underfull \hbox warnings.	359
tabularx: Require array.	1136		General: 2019/04/29	1
tabulary: Require array.	1137		caption: Reduced underfull \hbox warnings.	686
tocdata: Added.	1177		chemfig: Updated to v1.4.	698
topcapt: Added.	1187		endfloat: Updated for v2.7.	753
xtab: Fix: Clear caption after use.	1234		lwrap-common-multimedia: Added.	1268
tabular: Error if \multirow without \mrowcell.	485, 487, 489		media9: Added.	940
lateximage: Fix for <i>pdfototext</i> errors from font size change.	566		movie15: Added.	956
fminipage: Honors \minipagefullwidth.	590			

multimedia: Added.	959	tabfigures: Added.	1135
textpos: Updated for v1.9.1. . .	1153	xr-hyper: Added.	1233
<i>lwarpmk</i> : If wrong <i>lwarpmk.conf</i>		xr: Added.	1232
version, or wrong OS, displays		zhlineskip: Updated to v1.0e. . .	1237
the print command to		Use <code>\LWR@formatted</code> for	
recompile.	311	<code>\bfseries</code> , etc.	257, 596
Docs: Error testing.	190	v0.73	
quotation: Fix: blockquotation		<code>\@include</code> : Fix: <code>\newpage</code> instead of	
tag.	416	<code>\clearpage</code>	247
v0.72		<code>\HTMLtitle</code> : Added default title if	
<code>\LWR@newautopagelabel</code> : Fix:		none specified.	362
References for <code>xr</code> , <code>xr-hyper</code> . . .	371	<code>\LWR@LwarpStart</code> : Fix: Empty	
<code>\LWR@restoreorigformatting</code> : Use		header/footer.	402
<code>\LWR@formatted</code> for <code>\bfseries</code> ,		<code>\LWR@addbaselinemarker</code> :	
etc.	529	Improved warning messages.	536
<code>\chapter</code> : Added support for		<code>\LWR@createfooter</code> : Fix: Empty	
<code>hypbmsec</code>	396	header/footer.	382
<code>\ebweight</code> : <code>nfssext-cfr</code> : Added. . .	596	<code>\LWR@descitem</code> : Fix: HTML tags. . .	427
<code>\hypertoc</code> : Fix: References for <code>xr</code> ,		<code>\LWR@forceemptyline</code> : Added. . .	222
<code>xr-hyper</code>	517	<code>\LWR@gsavebox</code> : Added global save	
<code>\hypertocfloat</code> : Fix: References for		boxes.	223
<code>xr</code> , <code>xr-hyper</code>	518	<code>\LWR@htmlElementclass</code> : Vertical	
<code>\lgweight</code> : <code>nfssext-cfr</code> : Added. . .	596	space.	350
<code>\paragraph</code> : Added support for		<code>\LWR@htmlElementclassline</code> :	
<code>hypbmsec</code>	396	Vertical space.	351
<code>\part</code> : Added support for		<code>\LWR@indentHTMLtwo</code> : Added. . .	346
<code>hypbmsec</code>	395	<code>\LWR@indexitem</code> : Fix: Avoid empty	
<code>\section</code> : Added support for		<code></code>	520
<code>hypbmsec</code>	396	<code>\LWR@indexsubitem</code> : Fix: Avoid	
<code>\subparagraph</code> : Added support for		empty <code></code>	520
<code>hypbmsec</code>	396	<code>\LWR@indexsubsubitem</code> : Fix: Avoid	
<code>\subsection</code> : Added support for		empty <code></code>	520
<code>hypbmsec</code>	396	<code>\LWR@newhtmlfile</code> : Fix: Empty	
<code>\texteb</code> : <code>nfssext-cfr</code> : Added. . . .	592	header/footer.	385
<code>\textlg</code> : <code>nfssext-cfr</code> : Added. . . .	592	<code>\LWR@nullfonts</code> : Fix: <code>\hspace</code> in	
<code>\textulc</code> : <code>fontaxes</code> : Added.	593	sectioning file name.	532
<code>\ulcshape</code> : <code>fontaxes</code> : Added.	598	<code>\LWR@titlingmaketitle</code> : <code>titling</code> :	
General: 2019/06/08	1	Fix: Paragraph tags.	413, 1174
<code>lwarp.css</code> : Added <code>backnaur</code> . . .	267	Fix: Paragraph tags.	414
<code>lwarp.css</code> : Removed unneeded		<code>\attribution</code> : Fix: Paragraph tags. . .	416
support for <code>\sishape</code> , <code>\textsi</code> . . .	267	<code>\color</code> : <code>xcolor</code> : Added HTML	
<code>backnaur</code> : Added.	661	support.	1219
<code>boxedminipage2e</code> : Added		<code>\fboxBlock</code> : Fix: Paragraph tags. . .	588
support for <code>lateximages</code>	680	<code>\hspace</code> : Fix: Avoid empty <code></code> . . .	605
changes: Fix references for <code>xr</code> ,		<code>\l@book</code> : Added <code>\book</code> for memoir. . .	518
<code>xr-hyper</code>	693	<code>\maketitle</code> : <code>titling</code> : Fix: Paragraph	
<code>fontaxes</code> : Added.	595, 806	tags.	1173
<code>gloss</code> : Fix references for <code>xr</code> ,		Fix: Paragraph tags.	412
<code>xr-hyper</code>	823	<code>\marginparBlock</code> : Fix: Paragraph	
<code>hypbmsec</code> : Added.	844	tags.	369
<code>minibox</code> : Added.	948	<code>\postbookname</code> : Added <code>\book</code> for	
<code>nfssext-cfr</code> : Added.	976	memoir.	395
<code>nomencl</code> : Fix references for <code>xr</code> ,		<code>\printthanks</code> : Fix: Paragraph tags. . .	409
<code>xr-hyper</code>	986	<code>\rule</code> : Fix: Avoid empty <code></code> . . .	608
<code>pdfcrypt</code> : Added.	1013	General: 2019/07/11	1
<code>shapepar</code> : Added.	1058	<code>lwarp.css</code> : Added <code>\book</code> for	
<code>slantsc</code> : Added.	1105	memoir.	267
<code>soulutf8</code> : Fix: Loads <code>soul</code>	1108	<code>lwarp.css</code> : Improved <code>pkgtoadata</code>	
		formatting.	267

lwrap_formal.css: Added \book	\AltTextOpen: Added.	533
for memoir.	\ImageAltText: Added.	533
boxedminipage2e: Fix: Paragraph	\LWR@ThisAltText: Add	
tags.	\ThisAltText.	534
epigraph: Fix: Paragraph tags. . .	\LWR@addlinktitle: Added. . . .	495
fancyvrb: Fix: Nested	\LWR@doequation: Add	
<div>/<pre>.	\ThisAltText.	552
fancyvrb: Btrivlist: Fixed	\LWR@doubledollar: Add	
paragraph tags.	\ThisAltText.	544
intopdf: Updated to v0.2.1. . . .	\LWR@lateximage@oneimage:	
listings: Fix: Paragraph tags. . .	Factored from lateximage. . .	562
lwrap-common-multimedia: Fix:	\LWR@lateximage@oneimageb:	
No size for audio file.	Factored from lateximage. . .	561
lwrap-common-multimedia: Fix:	\LWR@setcurrentfont: Factored. .	535
Paragraph tags.	\LWR@singledollar: Add	
lwrap-patch-komascript: Fix for	\ThisAltText.	545
captions.	\LWR@singledollarmeasure: Fix:	
lwrap-patch-memoir: Added	Font control.	537
\book.	\LWR@subinlineimage: Add	
lwrap-patch-memoir: Fix for	\ThisAltText.	501
\frontmatter* and	\LWR@subsingledollar: Add	
\mainmatter*.	\ThisAltText.	543
lyluatex: Added.	\LWR@subsingledollarsvg: Adds	
musicography: Updated to	star argument for lateximage. .	540
2019/05/28. Now supports	\LateximageFontScale: Adjusted	
lateximages.	svg math font scaling default to	
quotchap: Fix: Paragraph tags. .	1.	560
quotchap: Updated to v1.2. . . .	\MathImageAltText: Renamed from	
quoting: Fix: Paragraph tags. . .	\mathimage.	534
scrextend: Fix: Paragraph	\PackageDiagramAltText:	
tags.	Renamed from	
stackengine: Added.	\packagediagramname.	534
threeparttable: Added	\ThisAltText: Add \ThisAltText. .	534
measuredfigure.	\hspace: Ignore negative space. . .	604
tocdata: Honors	General: 2019/09/02	1
\tocdataformat.	lwrap.css: Added lyluatex. . . .	267
tocdata: Improved formatting. . .	amsmath: Add \ThisAltText. . .	641
tocdata: Updated to v2.03. . . .	forest: alt text.	811
versionotes: Updated to v0.4. . .	geometry: Remembers user's	
vwcol: Fix: Paragraph tags. . . .	geometry.	821
xy: Fix for \xybox.	graphics: Add	
xy: Improved xy, reverted	\ThisAltText.	829, 834, 835
\xymatrix, for qcicuit.	lyluatex: Adapts to user's	
Added \book for memoir.	geometry.	912
AMS environments: Fix: alt	lyluatex: Preserves left margin. .	912
tags.	lyluatex: Renamef	
AMS environments: Fix:	\lyluateximagenam.	912
Paragraph tags.	lyluatex: Split system images,	
Numbered HTML entity used for	assign class.	912
text dollar.	mhchem: Modified for new	
tabular: Fix and warning for	lateximage.	944
tabular inside a	pdfpages: Adjust to user's paper	
LWR@blocktextcurrentfont: Fix:	size.	1015, 1016
Paragraph tags.	stackengine: alt tags.	1112
LWR@nestspan: Fix: quote,	struktex: alt text.	1125
quotation inside a span.	tikz: Added alt text.	1163
v0.74	lwrapmk: lwrapmk clean	
\@ensuredmath: Add	removes add'l files.	311
\ThisAltText.	lwrapmk: lwrapmk epstopdf and	
\AltTextClose: Added.	pdftosvg honor directories. . .	311

Remembers user's geometry. . .	236	graphics: Fix: alt tag expansion.	834
Lateximage: Add \ThisAltText. . .	567	lwarp-common-multimedia: Fix	
Added second starred argument.	562	links with new LaTeX	
Improved alt text.	564	kernel.	1268, 1269
New syntax for		titlesec: Fix for \titleclass. .	1169
\LWR@subinlineimage.	567	v0.79	
eqnarray: Add \ThisAltText. . .	557	\CustomizeMathJax: Fix: Sanitize	
LWR@displaymathother: Uses		for HTML.	379
\MathImageAltText.	547	\LWR@ProvidesPackagePass: Fix:	
LWR@equationother: Uses		catoptions.	245
\MathImageAltText.	547	\LWR@checkloadfilename:	
v0.75		Prevented bxcjkatype, hangul.	242
\normalcolor: xcolor: Added for		\LWR@closetabledatacell: Fix:	
HTML.	1218	Nested tabulars.	438
General: 2019/09/23	1	\LWR@customizeMathJax: MathJax:	
lwarp.css: Improved		Hide definitions.	381
marginblock.	267	\LWR@forcenewautoanchor:	
keyfloat: Fix: \normalcolor. 870, 871		Factored.	506
wrapfig: Fix for \linewidth. . .	1211	\LWR@mathjaxwarn: Warn if using	
wrapfig: Fix for width.	1211	packages partially supported by	
minipage: Fix: \linewidth.	584	MATHJAX.	617
v0.76		\LWR@parseaftercolumn: Remove	
General: 2019/10/08	1	outermost braces.	445
lwarp.css: Fix for small caps. . .	267	\LWR@parseatcolumn: Remove	
acro: Updated for v2.10.	627	outermost braces.	442
xr-hyper: Updated for v6.1. . .	1233	\LWR@parsebangcolumn: Remove	
xr: Updated for v5.05 and		outermost braces.	443
xr-hyper v6.1.	1232	\LWR@parsebeforecolumn: Remove	
Docs expanded: Multiple		outermost braces.	444
projects.	94	\LWR@setexparray: Fix: Nested	
File: lwarp_mathjax.txt:		tabulars.	332
Updated to MATHJAX v2.7.6. . .	307	\LWR@singledollarmeasure:	
v0.77		Factored.	537
General: 2019/10/15	1	\LWR@subHTMLsanitize: Fix: \&	
booktabs: Updated to		Factored.	377
v1.6180339.	678	\LWR@subsingledollarsvg: Adjust	
chemformula: Updated to v4.15.	701	for unknown size.	540
v0.78		Factored.	539
\LWR@linkcatcodes: babel-french:		\LWR@tabularendofline: Fix:	
Fix: Hyperlinks.	499	Nested tabulars.	441
Factored.	499	\captionlistentry: Fix: Duplicate	
\LWR@linkmediacatcodes:		auto-id.	510
babel-french: Fix: Hyperlinks.	500	\macrotocname: Added.	224
Factored.	499	\makebox: Fix: Adjust for virtual	
\LWR@nullifyNoAutoSpacing:		page size.	586
babel-french: Fix: Hyperlinks.	484	\multicolumnrow: multirow: Fix:	
\LWR@subhyperrefclass: Remove		Nested tabulars.	964
extra space.	500	\noalign: Fix: Nested tabulars. .	483
\normalfont: Uses		General: 2020/02/01	1
\LWR@formatted.	598	MATHJAX: Additional macros. . .	380
General: 2019/11/07	1	lwarp.css: Fix: Nested	
accessibility: Added.	626	tabulars.	267
babel-french: Fix: Hyperlinks. . .	345	amsmath: Added MATHJAX	
caption: Added warning		emulation.	642
regarding passing options. . .	685	arydshln: Added MATHJAX	
filecontents: Fix to overwrite		emulation.	652
existing files using new		ar: Added MATHJAX emulation. .	649
filecontents environment. . .	239	awesomebox: Added.	659
geometry: Cleaner option		babel and polyglossia: Added	
handling.	822	info messages.	616

bigdelim: Added MATHJAX emulation.	674	AMS environments: Fix: Nested. Factored to <code>\LWR@setvirtualpage</code> . . .	800, 833
bigstrut: Added MATHJAX emulation.	675	Fix: Use <code>newfloat</code> instead of <code>float</code>	800
bm: Added.	676	Fix: Use full <code>\linewidth</code>	800
booktabs: Added MATHJAX emulation.	679	Remember HTML font size.	601
booktabs: Fix for memoir with <code>lateximage</code>	483, 678	tabular: <code>colortbl</code> : Fix: Nested tabulars.	486
braket: Added.	681	Fix: Nested tabulars.	489
floatflt: Improved width control.	796	warpMathJax: Added.	235
fontawesome5: Supports font size, color.	805	lateximage: Improved <code>\linewidth</code>	565
fontawesome: Refactored with fix for <code>\FAthree</code>	804	minipage: Fix: <code>\linewidth</code> frame padding.	584
fontawesome: Supports font size, color.	804	Fix: Adjust for virtual page size.	583
geometry: Also save <code>\textwidth</code> , <code>\textheight</code>	237	fminipage: Fix: Adjust for virtual page size.	590
graphics: Factored from <code>\LWR@includegraphicsb</code>	831, 832	LWR@setvirtualpage: Factored. . .	581
graphics: Fix for negative angles.	830	v0.80 <code>\CustomizeMathJax</code> : Fix: Made <code>\@onlypreamble</code>	379
ifpdf, ifptex: Provided by iftex. .	201	Warn of slow compile.	379
keyfloat: Factored to <code>\LWR@setvirtualpage</code>	875	<code>\LWR@checkloadfilename</code> : Prevented formula, <code>shadethm</code> , <code>slashbox</code>	242
ltablex: Fix: Require <code>longtable</code> . .	905	<code>\LWR@infoprocessingmathjax</code> : Add: Info message.	380
ltxtable: Fix: Required packages.	906	<code>\LWR@restoreorigformatting</code> : Improved math, <code>displaymath</code>	529
luatex85: Removed.	201	<code>\fcolorbox</code> : Made robust.	577
mathtools: Added MATHJAX emulation.	926	<code>\fcolorboxBlock</code> : Made robust.	577
multirow: Add: MATHJAX emulation.	964	<code>\includegraphics</code> : Made robust.	835
multirow: Fix: Centered vertical alignment.	962	General: 2020/02/19	1
niceframe: Fix: Adjust for virtual page size.	983	<code>\textbf</code> and related: Use HTML series, etc.	591
parallel: Added.	1004	accessibility: Added MATHJAX emulation.	626
parcolumns: Added.	1006	accsupp: Added MATHJAX emulation.	626
pdfcolfoot: Added.	1011	autobreak: Added.	658
pdfcolmk: Added.	1011	biblatex: Creates hyperlinks. . . .	670
pdfcolparallel: Added.	1011	centernot: Added.	691
pdfcolparcolumns: Added.	1012	chemmacros: Updated to v5.10.	712, 721
pdfcol: Added.	1010	extrarrows: Added.	772
physics: Added.	1020	fewerfloatpages: Added.	790
siunitx-v2: Fix: <code>\square</code> , <code>\cubed</code>	1087	fouridx: Added.	811
siunitx-v2: Improved MATHJAX.	1084, 1085	gensymb: Added.	821
slashed: Added.	1105	ghsystem: Added.	822
steinmetz: Added.	1124	gmeometric: Requires geometry.	826
svg: Added.	1133	hline: Added.	843
transparent: Supports <code>lateximages</code>	1188	leftidx: Added.	883
unicode-math: Added.	1195	mathcomp: Added.	919
widetable: Added.	1209	mathdots: Added.	921
witharrows: Added.	1209	mathfixs: Added.	922
xcolor: Fix: Nested tabulars.	1223, 1224	mismatch: Added.	950
xltabular: Fix: Require <code>ltablex</code> .	1229	nccmath: Added.	971
xurl: Updated to v0.08.	1236	noitcrl: Added.	986

pdfcomment: Added MATHJAX	v0.82
emulation. 1013	\LWR@disablepinyin: Added. 222
resize: Added MATHJAX	\LWR@doequation: MATHJAX:
emulation. 1038	Improved footnotes. 552
rmathbr: Added. 1040	\LWR@syncmathjax: Removed <par>
subsupscripts: Added. 1131	tags. 548
tagpdf: Added. 1137	General: 2020/03/25 1
unicode-math: Improved	MATHJAX: Improved
MATHJAX. 1195, 1197	footnotes. 380, 552
url: Creates hyperlinks. 1201	amsmath: Fixed: \intertext for
xfrac: Added MATHJAX	MATHJAX. 642
emulation. 1229	chemfig: Updated to v1.5. 698
AMS environments: Fix:	draftwatermark: Updated to v2.0. 747
Centering starred envs. 640, 641	endnotes: Added MATHJAX
Improved math, displaymath. 546	emulation. 755
Prevented formula, shadethm,	endnotes: Fix: Mark in print
slashbox. 205	mode. 755
lateximage: Fix: Rule color in	etoc: Added. 769
lateximage. 565	luatexko: Added. 907
eqnarray: Fix: eqnarray*. 557	lwrap-patch-memoir: Supports
v0.81	tocvsec2. 1247, 1251
\LWR@addbaselinemarker:	marginnote: Added MATHJAX
Improved warning messages. 536	emulation. 917
\LWR@checkloadfilename:	marginnote: Fix: Neutralize in
Prevented statex. 242	print mode. 917
\LWR@replacestrings: Added. 377	nccfoots: Added MATHJAX
\LWR@subHTMLsanitize: Faster. 377	emulation. 971
\textcolor: xcolor: \textcolor:	pagenote: Added MATHJAX
Spurious space. 1220	emulation. 1003
General: 2020/03/04 1	parnotes: Added MATHJAX
lwrap.css: Added nolbreaks. 267	emulation. 1009
DotArrow: Added. 745	sidenotes: Added MATHJAX
Slunits: Improved \unit. Fixed in	emulation. 1063
math mode. Added MATHJAX	soul: Fixed: \<. 1106
emulation. 1064	syntonly: Added \nopages@. 1135
axessibility: Added MATHJAX	syntonly: Added to
emulation. 661	\LWR@loadafter. 207
axessibility: Updated to	ulem: Fixed: \dashuline. 1192
2020/01/08 version. 660	xpinyin: Added full pinyin
colonequals: Added. 733	support. 1231
decimal: Added. 742	v0.83
dotlessi: Added. 745	General: 2020/03/27 1
econometrics: Added. 749	lwrap-patch-memoir: Fixed
engtlc: Added. 755	framed. 1242
gridset: Updated to v0.3. 839	lwrap-patch-memoir: Fixed:
hyperref: Added	\specialindex. 1263
\pdfstringdefDisableCommands.	lwrap-patch-memoir: No longer
. 853	requires subfigure. 1242
luamplib: Added. 907	lwrap-patch-memoir: Updated
multiobjective: Added. 960	for new sizes. 1243
nolbreaks: Added. 986	lwrap-patch-memoir:
physunits: Added. 1020	Updated. 1246, 1247
returntogrid: Added. 1040	physunits: Updated to v1.0.4. 1020
stackrel: Added. 1113	v0.84
statex2: Added. 1114	\@currentHref: backref: Fixed from
statmath: Added. 1123	lwrap v0.72 changes. 499
lwrapmk: Improved error if in	\@currentlabelname: Default name
lwrap source directory. 311	for previous/next links. 490
Prevented statex. 205	\@fnsymbol: \LWR@formatted, fixed
	double bar. 412

<code>\@makecaption: caption now</code>	<code>\caption@end: caption now</code>
optional. 507	optional. 509
Warn inside a <code></code> 507	<code>\captionlistentry: caption now</code>
<code>\@textsubscript: Use</code>	optional. 510
<code>\LWR@formatted</code> . No longer	<code>\captionof: caption now optional</code> . 511
<code>\AtBeginDocument</code> 599	<code>\end@dlbfloat: caption now</code>
<code>\@textsuperscript: Use</code>	optional. 505
<code>\LWR@formatted</code> 599	<code>\linknextname: Added prev/next</code>
<code>\@xdlbfloat: caption now</code>	links. 340
optional. 505	<code>\linkpreviousname: Added</code>
<code>\AddSubtitlePublished: Added</code>	prev/next links. 340
<code>\subtitle</code> , <code>\published</code> for	<code>\printthanks: Fix: \printthanks</code>
<code>koma*</code> 415	in print mode. 409
Fixed <code>\subtitle</code> ,	<code>\sscshape: Moved to core</code> 598
<code>\printsubtitle if no titling</code> . . 415	<code>\textssc: Moved to core</code> 594
<code>\HTMLFirstPageBottom: Added</code>	<code>\textsubscript: Use</code>
<code>\FirstPageBottom</code> 360	<code>\LWR@formatted</code> . No longer
<code>\LWR@LwarpEnd: Added prev/next</code>	<code>\AtBeginDocument</code> 599
links. 404	<code>\textsuperscript: Use</code>
Fix: No footer for EPUB 404	<code>\LWR@formatted</code> 599
<code>\LWR@LwarpStart: Added prev/next</code>	<code>\theHTMLTitleSeparator:</code>
links. 403	Improved spacing for xeCJK. . 397
<code>\LWR@createfooter: Added</code>	<code>\verbatiminput: Added print</code>
<code>\FirstPageBottom</code> 382	mode. 420
<code>\LWR@domulticolumn: Fix:</code>	General: 2020/04/24 1
Multicolumn style. 472	<code>LATEX accents: Add'l symbols</code> . . 258
<code>\LWR@excludacomment:</code>	<code>lwrap.css: Added koma-*</code>
Independent cut files. 234	subject. 267
<code>\LWR@filenamoblanks: Fix:</code>	<code>lwrap.css: Fix: Minipage tex</code>
Dashes in filename. 376	align. 267
<code>\LWR@filestart: Improved HTML</code>	<code>lwrap.css: Fix: Top nav if narrow</code>
title. 398	window. 267
<code>\LWR@floatbegin: Warn inside a</code>	<code>lwrap.css: Improved</code>
<code></code> 503	<code>nfssect-cfr</code> 267
<code>\LWR@forcenewautoidanchor:</code>	<code>lwrap.css: Improved realscripts</code> . 267
<code><par></code> handling. 506	<code>abstract: Updated for memoir</code> . . 622
<code>\LWR@htmlsectionfilename: Fix:</code>	<code>alltt: Added print mode</code> 638
Sections called "Index" or	<code>amsthm: Fix for \nameref</code> 644
"index" have <code>-0</code> appended to	<code>backref: Fixed from lwrap v0.72</code>
their filenames if no prefix. . . 337	changes. 662
<code>\LWR@new@label: Removed optional</code>	<code>biblatex: Fixed: Requires</code>
args. 495	hyperref. 670
<code>\LWR@newhtmlfile: Added</code>	<code>boxedminipage: Renamed from</code>
prev/next links. 383, 385	<code>boxedminipage2e</code> per
<code>\LWR@nullfonts: Add'l symbols</code> . . 530	author. 680, 681
Factored out redefinitions. . . . 530	<code>caption: Improved integration</code> . . 686
Fix: Accents. 530	<code>caption: Non-width \parboxes</code> . 685
Revised <code>\texorpdfstring</code> 533	<code>caption: Simplified</code> 685
<code>\LWR@section: Added prev/next</code>	<code>epigraph: Added print mode</code> . . . 762
links. 394	<code>fixme: Added section name</code> 792
Warn inside a <code></code> 389	<code>float: Fix: Recursive name</code> 795
<code>\LWR@startpars: Ignore if in</code>	<code>fontaxes: Moved sscshape to</code>
<code>lateximage</code> 358	core. <code>\FilenameNullify</code> 806
<code>\LWR@stoppars: Ignore if in</code>	<code>lwrap-patch-memoir: Creates</code>
<code>lateximage</code> 359	mark macros. 1250
<code>\LinkNext: Added prev/next links</code> . 341	<code>lwrap-patch-memoir: Fix:</code>
<code>\LinkPrevious: Added prev/next</code>	<code>\label</code> 1243
links. 340	<code>lwrap-patch-memoir: Fixed</code>
<code>\attribution: Added print mode</code> . 416	pagenotes. 1259

lwrap-patch-memoir: Improved cleveref support.	1260	quotation: Added print mode.	416
lwrap-patch-memoir: No longer requires subcaption.	1242	quote: Added print mode.	416
lwrap-patch-memoir: No longer uses subcaption.	1257	LWR@nestspan: Issue warnings inside a span.	347
lwrap-patch-memoir: Use L ^A T _E X captions.	1255	Nullified minipage, \parbox inside a span.	347
lwrap-patch-memoir: Uses memoir's \newcomment, \commentsoff, \commentson.	1261	v0.85	
lwrap-patch-memoir: \contsubtop, etc. now as-is.	1267	\LWR@atbeginverbatim: Fix: Added print macros for fontspec.	419
lwrap-patch-memoir: caption now optional, removed dup caption.	1257	\LWR@htmlclosecomment: Fix: Added print macros for fontspec.	348
mdframed: Warn inside a	933	\LWR@htmlcomment: Fix: Added print macros for fontspec.	349
memoir: Preloads xcolor.	614	\LWR@htmltagc: Fix: Added print macros for fontspec.	346
multirow: Fix: Multirow style.	962	General: 2020/05/01	1
nfsexxt-cfr: Improved.	976	idxlayout: Fixed:	
nfsexxt-cfr: \FilenameNullify.	978, 981	\AtBeginDocument for load order.	857
ntheorem: Warning if thref.	989	titlesec: pagestyles option.	1167
parcolumns: Fixed: Missing \colplacechunks.	1006	url: Fixed print mode.	1201
realscripts: Added print mode.	1033	Fix: Added print macros for fontspec.	596
realscripts: Fixed starred \textsuperscript, \textsubscript.	1033	v0.86	
realscripts: Improved supersubscripts.	1033	\LWR@filenamoblanks: Fix: *, (,), . in filename.	374
rotfloat: Fix: Requires rotating.	1042	\LWR@filestart: Error if missing file.	400
scrextend: Added \titlehead, \subject, \subtitle, \published.	1045	\LWR@href: hyperref: Adjusted emulation.	500
scrextend: Updated to v3.29.	1045	\LWR@label@createtag: Fix: Labels in eqnarray.	494
sidenotes: \sidecaption not long arg.	1062	\LWR@label@inmathcomment: Fix: Labels in eqnarray.	493
slantsc: \FilenameNullify.	1105	\LWR@noLinkurl: hyperref: Adjusted emulation.	501
symptex: Added print mode.	1134	\LWR@phantomsection: hyperref: Adjusted emulation.	608
titling: \AtBeginDocument.	1172	\LWR@startref: Fixed: \label inside lateximage.	496
xpinyin: Disables pinyin when null fonts.	1232	\LWR@syncmathjax: Improved MATHJAX equation numbers.	548
<i>lwrapmk</i> : clean also removes comment_*.cut	311	\LWR@url: hyperref: Adjusted emulation.	501
Added \FirstPageBottom.	360	\textcolor: xcolor: \textcolor: Fixed for babel-french.	1220
Added prev/next links.	337	General: 2020/05/12	1
Docs: JETBRAIN MONO font.	101	LWR@insidemathcomment: Added.	534
Docs: \linkpreviousname.	107	amsmath: Added support for MATHJAX.	642
Fixed: textcomp now in kernel.	613	hyperref: Adjusted emulation.	849
Logos: Only warn about graphics if actually use \Xe.	609	nccmath: Added \displaybreak.	972
tabbing: Restore spacing.	421	nccmath: Fixed \nr, added starred.	972
center: Added print mode.	568	File: lwrap_mathjax.txt: Added support for starred macros.	307
verbatim: Added print mode.	420		
verse: Added print mode.	417		
flushleft: Added print mode.	568		
flushright: Added print mode.	568		
longtable: caption now optional.	902		

File: lwarp_mathjax.txt:	
Improved equation numbering.	307
File: lwarp_mathjax.txt:	
Updated to MATHJAX v3	
current.	307
v0.87	
\LWR@checkloadfilename:	
Prevented csvtools.	242
\bibliography: Reverted to	
original.	527
\scshape: Added FixSmallCaps to	
remove \LWR@print@scshape	
for erewhon, et. al.	597
\sishape: Added FixSmallCaps to	
remove \LWR@print@scshape	
for erewhon, et. al.	598
General: 2020/06/03	1
cancel: Now uses MATHJAX v3	
extension.	684
citeref: Added.	727
drftcite: Added.	747
embrac: Neutralized kerning. . .	752
ifpdf, ifptex: Restored to work on	
TL2019 and earlier.	201
jurabib: Added.	866
mathtools: Improved	
\underbracket, \overbracket. . .	926
mathtools: Updated starred	
macros.	926
mhchem: Now uses MATHJAX v3	
extension.	944
multibib: Added.	957
nccmath: Updated starred,	
improved \underref.	972
physics: Now uses MATHJAX v3	
extension.	1020
splitbib: Added.	1108
statex2: \pBin exponent.	1114
Added FixSmallCaps to remove	
\LWR@print@scshape for	
erewhon, et. al.	591
Docs: Updated docs to compile	
lwarp documentation.	186
File: lwarp_mathjax.txt: Now	
provides \ifstar,	
\ifnextchar.	307
Prevented csvtools.	205
v0.88	
\@wrindex: Added support for	
xindex.	521
\IndexRangeSeparator: Added. . .	520
\LWR@HTML@ref: Added MATHJAX. .	498
Fixed: Starred.	497
\LWR@LetLtxMacros: Added.	224
\LWR@absorbstar: Added.	224
\LWR@checkloadfilename:	
Prevented shadethm.	242
\LWR@doindexentry: Adapts to	
gindex.	525
\LWR@doindexentrysub: Adapts to	
gindex.	524
\LWR@doindexentrysubsub:	
Handles a range, for xindex. . .	524
\LWR@forcenewautoidanchor:	
Inline handling.	506
\LWR@hyperindexrefsbtwo: Adds	
support for a range, for xindex.	526
\LWR@indexnameref: Added	
IndexRef option, refactored. . .	524
\LWR@maybe@orignewpage: Added.	223
\LWR@printchaptername:	
Conditionally print	
\chaptername.	389
\LWR@restoreMathJaxformatting:	
Added.	528
\LWR@restoreorigformatting:	
Added \vdots.	529
Support for MATHJAX.	530
\LWR@section: Conditionally print	
\chaptername.	393
\LWR@xindex@modifyentry: Added	
support for xindex.	521
\hrulefill: Full line <div> if not	
started paragraph.	602
\hyperindexformat: Added.	527
\hyperindexref: Rewritten to parse	
commas and ranges.	525
\hyperpage: Added.	527
\nohyperpage: Added.	527
General: 2020/07/19	1
lwarp.css: Added indexheading	
for gindex.	267
lwarp.css: Added tcolorbox,	
thmbox.	267
amsmath: Added \dotso text	
mode.	639
amsthm: Requires amsmath. . . .	643
caption, scrextend: Fixed	
\caption*.	687
cleveref, varioref: Fix for starred	
macros.	731
fancyref: Now uses varioref	
which ignores page-related	
output.	780
fbox: Added.	787
gindex: Added.	823
hhtensor: Added.	844
mlefttright: Added.	953
pdfreder: Restored for	
xfakebold.	1016
shadethm: Added.	1058
tcolorbox: Added.	1142
termcal: Added.	1148
thm-listof: Added.	1158
thm-restore: Added.	1158
thmbox: Added.	1159
ushort: Added.	1201
varioref: Removed page-related	
text.	1202

xfakebold: Now works with pdfrender.	1227	mathptmx: Added.	923
Added \vdots.	257, 601	mismatch: Improved math operators.	950
Added LWR@texboxdepth.	223	newpxmath: Added.	973
Added IndexRef option.	230	newtxmath: Added.	974
Added xindex option.	230	newtxsf: Added.	975
Option xindexConfig added.	229	pxfonts: Added.	1030
Prevented shadethm.	205	shuffle: Added.	1060
v0.883		siunitx: Fix: MATHJAX for \tothe, \raiseto.	1091
General: nfssect-cfr: Fixed		siunitx: Unicode for endash.	1096
\textsw.	979	statmath: Fixed abcbm, uses lwarp-common-mathjax-letters.	1123
v0.89		thm-listof: Updated to v0.72.	1158
\@opargbegintheorem: Allow preload of amsmath, amsthm, centernot.	422	thm-restate: Updated to v0.72, no changes needed.	1158
\LWR@HTMLsanitizeexpanded: Fix: Nested MATHJAX environments.	378	thmtools: Added.	1160
\LWR@LwarpStart: MathJax: Improved info message.	403	txfonts: Added.	1190
\LWR@addmathjax: TT font for MATHJAX.	550	upgreek: Added.	1200
\LWR@amsmathbodiednumbered: \textendash for number range.	561	<i>lwarpmk</i> : clean also removes *.bbl	311
\LWR@customizeMathJax: Print MATHJAX customizations with typewriter font.	382	Allow preload of amsmath, amsthm, centernot.	207, 613
\LWR@doubledollar: TT font for MATHJAX.	543	AMS environments: Fix: <ALT> text env name.	640
\LWR@patcherror: Improved message.	221	Foreground/background hooks: Adapt to L ^A T _E X core changes.	406
\LWR@singledollar: TT font for MATHJAX.	545	MATHJAX: Added \protect, and \mathcode and related.	381
\LWR@subsingledollar: TT font for MATHJAX.	542	Removed \let of \[, \].	547
\endocument: Adapt to L ^A T _E X core changes.	405	eqnarray: \textendash for number range.	556
General: 2020/09/03	1	v0.891	
accents: Added.	625	\LWR@atbeginverbatim: Fix for verbatim, alltt with lists	419
atbegshi: Adapt to L ^A T _E Xkernel changes.	653	\LWR@checkloadfilename: Prevented libgreek.	242
caption3: Split from lwarp-caption.	687	\LWR@excludecomment: Error if nested comment.	234
caption: Adapt to v3.5.	685	\LWR@subHTMLsanitize: Neutralized single quotes.	377
centernot: Improved.	691	\verb: \verb as \texttt.	418
econometrics: Uses lwarp-common-mathjax-letters.	749	General: 2020/09/22	1
everyshi: Adapt to L ^A T _E Xkernel changes.	771	biblatex: Fixed: Back page references.	671
everyshi: Included in L ^A T _E X core.	612	bussproofs: Added.	683
hepunits: Added.	842	caption: Improved integration.	686
lwarp-common-mathjax-letters: Added.	1272	cmbright: Added.	732
lwarp-common-mathjax-newpxmath: Added.	1278	colonequals: Uses Unicode and \mathrel.	733
lwarp-common-mathjax-overlaysymbols: Added.	1288	fancyvrb: Fix: BVerbatim with labels.	783
mathalpha: Added.	918	fourier: Added.	812
mathdesign: Added.	920	hyperref: Added backref, pagebackref.	845
mathpazo: Added.	922	hyperref: Fixed \texorpdfstring with babel-french.	853
		kpfonts-otf: Added.	878
		kpfonts: Added.	877

libertinustlmath: Added.	884	\fcolorbox: xcolor: Fixed second optional arg.	1221
listings: Fix for MATHJAX: Moved \LWR@forcenewpage to start.	894, 896	\fcolorboxBlock: xcolor: Fixed second optional arg.	1221
listings: Improved HTML sanitizing.	894	General: 2020/10/07	1
listings: Improved spacing around ampersand.	894	fancyvrb: Adapted to fvextra.	787
lwrap-common-mathjax-newpctxmath: Expanded for kpfnts.	1279–1281, 1285	fancyvrb: Provided \FV@FrameFillLine.	785
lwrap-common-mathjax-newpctxmath: Factored non-UNICODE.	1280, 1281, 1283	fourier: Added \left/\right support in lwrap_mathjax.txt.	812
lwrap-common-mathjax-newpctxmath: Reverse factored out Greek, non-UNICODE.	1278	fvextra: Added.	817
lwrap-common-mathjax-nonunicode: Added.	1285	graphics: Fix path from kernel change.	834
mathdesign: Added \mathinner, \mathbin.	921	libertinustlmath: Added \left/\right support in lwrap_mathjax.txt.	885
mathdesign: Added \mathop.	921	lineno: Fix for internallinenums*.	890
mathdesign: Added \mathrel, \mathord.	921	lwrap-common-mathjax-newpctxmath: Added \left/\right support in lwrap_mathjax.txt.	1278, 1283
mathdesign: Honors greekuppercase, greeklowercase.	920	minted: Added.	949
mathdots: Added more macros, \mathinner.	921	unicode-math: Added MATHJAX support for \left/\right.	1197
mathfixs: Added \mathinner.	922	File: lwrap_mathjax.txt: Added \left/\right delimiters.	307
mathpazo: Honors slantedGreek.	922	fcolorminipage: xcolor: Fixed second optional arg.	1222
mathptmx: Honors slantedGreek.	923	v0.893	
mathtools: Improved \underbracket, \overbracket.	926	\LWR@checkloadfilename: Allowed picinpar.	242
multiobjective: Improved.	960	\LWR@expandableformatted: Improved error handling.	252
newpctxmath: Honors uprightGreek, slantedGreek.	973, 975	\LWR@expandableformattedenv: Improved error handling.	253
newtxmath: Honors uprightGreek, slantedGreek.	974	\LWR@formatted: Improved error handling.	252
nicefrac: Added \mathinner, improved fraction.	982	\LWR@formatted@checkendname: Added.	252
scalerel: Added.	1044	\LWR@formatted@checkname: Added.	251
shuffle: Added \mathbin, improved bar.	1061	\LWR@formattedenv: Improved error handling.	253
txgreek: Added.	1191	\LWR@htmlcomment: Disabled in math mode.	349
unicode-math: Added sans-style.	1196	\LWR@subHTMLsanitize: Optionally neutralized single quotes.	377
units: Added \mathinner, improved fraction.	1199	General: 2020/11/26	1
File: lwrap_mathjax.txt: Renamed tagformat extension.	307	MATHJAX: Added \mathnormal.	380
Prevented libgreek.	205	lwrap.css: Added keystroke.	267
BVerbatim: fancyvrb: Fix: BVerbatim with labels.	787	bracket: Now uses MATHJAX extension.	681
v0.892		caption3: Updated date to v2.2e.	687
\LWR@subhtmlclass: Ignored empty class.	349	caption: Updated date to v3.5g.	685
		epstopdf-base: Updated date to v2.11.	764
		epstopdf: Updated date to v2.11.	764
		esvect: Added.	768
		fixmath: Added.	791

graphics: Updated date to v1.4c.	826	\LWR@hook@processingtags:	
graphicx: Updated date to v1.2b.	838	Added.	344
keystroke: Added.	875	\LWR@label@subcreatetag:	
lwarp-common-mathjax-letters:		Improved HTML quotes.	493
Added \varbeta.	1272	\LWR@mathjaxwarn: Added MATHJAX	
mathastext: Added.	918	warnings for aligned-overset,	
mathspec: Added.	923	autoaligne, boldtensors,	
menukeys: Added.	942	libertinustlmath, tensind.	618
menukeys: Updated to v1.6.1.	942	Improved MATHJAX warning for	
picinpar: Added.	1022	unicode-math.	618
plimsoll: Added.	1026	\LWR@maybenewtablerow: Improved	
pstricks: Fixed pspicture*.	1029	HTML quotes.	455
repltext: Added.	1039	\LWR@printatbang: Improved HTML	
schemata: Added <alt> text.	1044	quotes.	456
selectp: Added.	1054	\LWR@printopenlist: Improved	
seqsplit: Added.	1056	HTML quotes.	423
simplebnf: Added.	1063	\LWR@startref: Improved HTML	
statistics: Added.	1118	quotes.	495, 496
struktex: Removed package		\LWR@subaddtabularcellcolor:	
date.	1125	Improved HTML quotes.	467
svg: Updated date to v2.02j.	1133	\LWR@subhyperref: Improved HTML	
swfigure: Added.	1134	quotes.	500
tikz: Fixed font macros.	1163	\LWR@subhyperrefclass: Improved	
tocloft: Fix:		HTML quotes.	500
\cftpagenumbersoff,		\LWR@subinlineimage: Improved	
\cftpagenumberson.	1182	HTML quotes.	501
Allowed picinpar.	205	\LWR@tabledatasinglecolumnntag:	
v0.894		Improved HTML quotes.	458
\LWR@forceSVGmessage: Improved		\LWR@tdaddstyle: Improved HTML	
MATHJAX warnings.	618	quotes.	461
\LWR@mathjaxwarn: Improved		\LWR@tdendstyles: Improved HTML	
MATHJAX warnings.	618	quotes.	461
General: 2020/12/24	1	\hspace: Improved HTML quotes.	604
MATHJAX: Accept starred		\rotatebox: Improved HTML	
\hspace.	380	quotes.	836
MATHJAX: Added \arabic,		\rule: Improved HTML quotes.	607, 608
\number, \noalign.	380	\scalebox: Improved HTML quotes.	837
lwarp.css: T _E X logos no longer		\verb: Improved HTML quotes.	418
below baseline.	267	General: 2021/02/18	1
booktabs: MATHJAX: Absorb		acro: Updated to v3.5.	627
\cmidrule trim arg.	679	amscdx: Added.	638
colortbl: Added MATHJAX		amsmath: Added \Hat, etc..	642
emulation.	735	changes: Updated to v4.0.1.	693
nicematrix: Added.	983	epsfig: Supports lateximage.	763
rmathbr: Updated to v1.1.	1040	epsf: Added.	763
v0.895		fancyhdr: Updated to v4.0.	778
\LWR@addlinktitle: Improved		imprnatypo: Added.	862
HTML quotes.	495	isomath: Added.	864
\LWR@checkloadfilename: kpfons		isotope: Added.	864
load before lwarp.	242	libertinustlmath: MATHJAX: Fixed	
Allowed epsf.	242	for Greek, ignoring sans.	885
\LWR@domulticolumn: Improved		lpic: Added.	904
HTML quotes.	472, 473	luavlna: Added.	911
\LWR@floatbegin: Improved HTML		mattens: Added.	928
quotes.	504	maybemath: Added.	930
\LWR@forceSVGmessage: Improved		mdwmath: Added.	939
MATHJAX warning.	618	multirow: Allow \par.	963
\LWR@forcenewautoidanchor:		multirow: Improved HTML	
Improved HTML quotes.	506	quotes.	962
		pinlabel: Added.	1024

rlpsf: Added.	1040	\LWR@htmlspanclass: Added ARIA	
rotating: Supports lateximage.	1041	role.	348
siunitx, MATHJAX: Scientific		\LWR@lateximage@oneimage: Added	
notation.	1094	ARIA role.	562
siunitx, MATHJAX: \num sci		\LWR@lateximage@oneimageb:	
notation, multiples, +-,		Added ARIA role.	561
decimals, comma.	1092	\LWR@new@label: Revert to a simple	
siunitx: Fix: MATHJAX for \ang.	1092	\newcommand*.	495
siunitx: MATHJAX: \SI prefix		\LWR@newautopagelabel: Fix: Refs	
parsing.	1095	if page changed.	371
skmath: Added.	1100	\LWR@newhtmlfile: Added	
tensor: Added MATHJAX.	1147	<main>.	383, 385
tikz-image\labels: Added.	1164	\LWR@null@newautopagelabel: Fix:	
xevl\na: Added.	1226	Refs in footnotes.	371
Allowed epsf.	205	\LWR@nullfonts: Added ARIA role.	532
File: l\warp_mathjax.txt: Added		Added groups.	532
\ifblank, \ifstrequal		\LWR@popclose: Stack 19 deep. . .	331
macros.	307	\LWR@printpendingmpfootnotes:	
Fixed libertinus-otf		Added ARIA role.	368
\textquotedbl kern.	257	\LWR@pushclose: Error if stack	
Improved HTML quotes. 255, 344,		overflow.	330
637, 783,		Stack 19 deep.	330
832, 833, 840, 850, 851, 896, 933, 993		\LWR@refwithsection: Added. . . .	497
Use kpf\onts-otf if LuaL\ATEX,		\LWR@subhtml\elementclass: Added	
X\qL\ATEX.	220	ARIA role.	349
lateximage: Improved HTML		\LWR@subinlineimage: Added ARIA	
quotes.	564	role.	501
minipage: Improved HTML quotes.	583	\LWR@subsingledollarsvg: Added	
enumerate: Improved HTML quotes.	427	ARIA role.	540
itemize: Improved HTML quotes. .	426	\LWR@synconenotename: Fix:	
v0.896		MATHJAX: Footnote names. . . .	552
\@begintheorem: Intersperse		\LWR@write@l\warp\label: Added	
footnotes.	422	\LWR@currentautosecpage. . . .	493
\@currentHref: backref: Improved		\LWRPrintStack: Stack 19 deep. . .	341
back refs.	499	\RequirePackage: Warn if package	
\@endtheorem: Intersperse		option has braces.	244
footnotes.	422	\marginpar: Added ARIA role. . . .	369
\LWR@footnotetext: Fix: autopage		\marginparBlock: Added ARIA role.	369
references in footnotes.	365	\mbox: Added a group.	586
\LWR@@printpendingfootnotes:		General: 2021/04/08	1
Added ARIA role.	368	l\warp.css: Added <main>,	
Fix: Backref to footnote.	368	adjusted <sidetoccontainer>	
\LWR@L\warpEnd: Added <main>. . .	404	margin.	267
Fix: Footnotes at end of		762	
document.	404	amsthm: Improved back	
\LWR@L\warpStart: Added <main>. .	403	refs.	644, 646
\LWR@currentautosecpageref:		amsthm: Intersperse	
Added.	492	footnotes.	645–647
\LWR@doequation: Added ARIA role.	551	backref: Improved backrefs. . . .	662
\LWR@doubledollar: Added ARIA		biblatex: Fix: Back references. . .	671
role.	544	biblatex: Fix: Citation references.	671
Fix: Displaymath notes with		biblatex: Improved refs: \ref to	
MATHJAX.	543	\LWR@refwithsection.	671
\LWR@firstoffive: Changed to		bigdelim: Updated to v2.8.	674
firstoffive instead of four.	222	ccicons: Added.	690
\LWR@html\divclass: Added ARIA		chemfig: Updated to v1.6a. 698, 699	
role.	350	citeref: Improved refs: \ref to	
\LWR@html\elementclass: Added		\LWR@refwithsection.	727
ARIA role.	350	classthesis: Added.	728
		cleveref: Undo memoir changes.	731

cleveref: Undo subfig changes. . .	731	v0.897	
enotez: Added.	759	\LWR@afterloadnever: Refactored.	204
fancybox: Fix: autopage		\LWR@checkloadfilename:	
references in footnotes.	774	Refactored.	242
floatflt: Added ARIA role.	796	\LWR@checkloadnever: Refactored.	207
hyperref: Fix: Added		\LWR@checkloadnevers:	
*autorefname macros.	853	Refactored.	205
hyperref: Fix: No \hyperlink in		\LWR@earlyclassloadnever:	
HTML comment.	852	Replacements now optional.	204
hyperxmp: Added keys.	855	\LWR@earlyloadnever: Refactored.	204
keyfloat: Added ARIA role.	874, 875	\LWR@listof: Improved	
listings: Escapes accepted but		compatibility with newfloat,	
disabled.	894	keyfloat.	514
listings: Fix: Labels.	895	\LWR@loadnever: Replacements	
lwarp-patch-memoir: Added		now optional.	203
ARIA role.	1256	\RequirePackage: Fixed warning.	244
natbib: Fix: Citation references..	970	General: 2021/05/24	1
ntheorem: Intersperse		centerlastline: Added.	691
footnotes.	990, 991, 998	decorule: Added.	742
orcidlink: Added.	1001	fancypar: Added.	779
parnotes: Added ARIA role.	1007	fixme: Modified	
pdfscape: Fix: Added		\AtBeginDocument.	792
landscape.	1013	float: Improved compatibility	
picinpar: Added ARIA role.	1022	with newfloat, keyfloat.	796
scrlayer-scrpage: Added		froufrou: Added.	815
\automark, \manualmark.	1051	pbalance: Added.	1010
scrlayer-scrpage: Added		siunitx-v2: Do not use math	
\headmark, \pagemark.	1051	mode.	1083
theorem: Intersperse footnotes.	1157	siunitx-v2: Rollback for v2.	1082
threeparttablex: Fix:		siunitx: Rollback for v2.	573, 1072
\TPTL@tnotex if not		v0.898	
referrable.	1162	\LWR@atbeginverbatim: Reduced	
tocloft: Fix:		underfull \hbox warnings.	419
\cftpagenumbersoff,		\LWR@beginhideamsmath: Reduced	
\cftpagenumberon with		underfull \hbox warnings.	555
memoir.	1182	\LWR@hidelatexequation: Reduced	
wrapfig: Added ARIA role.	1211	underfull \hbox warnings.	549
Docs: Theorem references.	152	General: 2021/05/29	1
Fix: autopage references in		listings: Reduced underfull \hbox	
footnotes.	782	warnings.	895
Stack 19 deep.	329	wrapfig: Improved integration	
Lateximage: Added ARIA role.	562, 567	with keyfloat.	1211
center: Spurious space in a		Reduced underfull \hbox	
.	568	warnings.	833
description: Fix: Footnotes inside		Lateximage: Reduced underfull	
description label.	427	\hbox warnings.	563
minipage: Improved back refs.	584	LWR@figcaption: Reduced	
BlockClass: Added ARIA role.	351	underfull \hbox warnings.	508
flushleft: Spurious space in a		v0.899	
.	568	\LWR@LwarpStart: Warn if lwarp	
flushright: Spurious space in a		package not detected.	402
.	568	General: 2021/06/29	1
LWR@BlockClassWP: Added ARIA		lwarp.css: Improved multicol.	267
role.	352	graphics: Supports	
LWR@displaymathother: Added		keepaspectratio.	828, 834
ARIA role.	547	keyfloat: Fix: lw w/ h.	871
LWR@equationother: Added ARIA		lwarpmk: Warn if lwarp package	
role.	547	not detected.	311
LWR@nestspan: Issue BlockClassWP			
warning inside a span.	347		

v0.900			
	<code>\LWR@addmathjax: Fix: alignat</code>		
	with <code>MATHJAX</code>	550	
	<code>\LWR@filestart: Spurious space</code>	400	
	General: 2021/07/17	1	
	changes: Updated to v4.2.1.	693	
	froufrou: Updated to v1.4.0.	815	
	lipsum: Added.	893	
	Fix: alignat with <code>MATHJAX</code>	639	
	Fix: flalign name.	659	
v0.901			
	<code>\HTMLnewcolumnntype: Improved</code>		
	<code>\newcolumnntype</code> emulation.	451	
	<code>\LWR@checkmathcolpar: Error if</code>		
	math in column specifier.	443	
	<code>\LWR@formatted@checkendname:</code>		
	Improved error handling.	252	
	<code>\LWR@formatted@checkname:</code>		
	Improved error handling.	251	
	<code>\LWR@modifycolumnntype: Improved</code>		
	<code>\newcolumnntype</code> emulation.	448	
	<code>\LWR@parseaftercolumn: Error if</code>		
	math in column specifier.	445	
	<code>\LWR@parsebeforecolumn: Error if</code>		
	math in column specifier.	444	
	Tabular cell text alignment.	444	
	<code>\LWR@parsenormalcolumn:</code>		
	Improved <code>\newcolumnntype</code>		
	emulation.	447	
	<code>\LWR@parsetablecols: Improved</code>		
	<code>\newcolumnntype</code> emulation.	453	
	<code>\LWR@printmccoldata: Improved</code>		
	<code>\newcolumnntype</code> emulation.	469	
	<code>\LWR@printmccoltype: Improved</code>		
	<code>\newcolumnntype</code> emulation.	468	
	<code>\LWR@tabledatasinglecolumnntag:</code>		
	Tabular cell text alignment.	458	
	General: 2021/08/27	1	
	<code>lwrap.css</code> : Improved captions.	267	
	<code>lwrap.css</code> : Tabular cell text		
	alignment.	267	
	array: Fixed if array already		
	loaded.	650	
	array: Improved <code>\newcolumnntype</code>		
	emulation.	650	
	array: Now required.	612	
	centernot: Now uses <code>MATHJAX</code>		
	3.2 package.	691	
	dcolumn: Works inside		
	<code>lateximage</code>	741	
	gensymb: Use <code>MATHJAX 3.2</code>		
	package.	821	
	keyfloat: More room.	874	
	<code>ltpj-tascmac</code> : Added.	901	
	mathtools: Uses <code>MATHJAX 3.2</code>		
	package.	926	
	mwe: Added.	967	
	nicematrix: Added <code>\HLine</code>	985	
	siunitx-v2: Improved		
	<code>\newcolumnntype</code> emulation.	1082	
	<code>tabularx: Improved</code>		
	<code>\newcolumnntype</code> emulation.	1136	
	<code>tabulary: Improved</code>		
	<code>\newcolumnntype</code> emulation.	1137	
	<code>textcomp: Uses MathJax 3.2</code>		
	package.	1152	
	<code>upgreek: Use MATHJAX package</code>	1200	
	<code>xcolor: Moved \LWR@formatted</code>	578	
	Added print versions of		
	<code>\LWR@formatted</code> , etc.	253	
	<code>warpsvg: Added</code>	235	
v0.902			
	<code>\@makefnrtxt: Fixed: Footnotes</code>		
	inside square brackets.	365	
	<code>\@mpfootnotetext: Improved par</code>		
	tags.	367	
	<code>\LWR@footnotetext: Improved</code>		
	footnote par tags.	366	
	<code>\LWR@closeparagraph: Improved</code>		
	parnotes.	357	
	<code>\LWR@nameref: Nullify footnotes in</code>		
	<code>\nameref</code>	492	
	<code>\LWR@openparagraph: Improved</code>		
	parnotes.	355	
	Improved par tags.	355	
	<code>\LWR@restoreorigformatting:</code>		
	Improved minipage footnotes.	530	
	<code>\maketitle: Now named</code>		
	<code>\LWR@maketitle</code> to avoid being		
	overwritten later.	412	
	<code>\textnormal: Reduce nested spans</code>	594	
	General: 2021/10/01	1	
	<code>lwrap.css</code> : Added <code>textnormal</code>	267	
	<code>lwrap.css</code> : Added		
	<code>beamerarticle</code>	267	
	<code>lwrap.css</code> : Centered <code><div></code>		
	author.	267	
	amsthm: Fixed empty		
	theoremendmark <code></code>	646	
	<code>beamerarticle</code> : Added.	667	
	<code>fancybox</code> : Improved footnote par		
	tags.	774, 775	
	<code>fancyvrb</code> : Improved footnote par		
	tags.	782	
	footnote: Fixed missing number.	809	
	footnote: Improved par		
	tags.	808, 809	
	<code>luatexko</code> : Removed deprecated		
	<code><rb></code>	907	
	<code>luatexko</code> : Updated to v3.3.	907	
	memoir: Fixed <code>\memorigpar</code>	1251	
	multimedia: Added		
	<code>\hyperlinksound</code> ,		
	<code>\hyperlinkmute</code>	959	
	<code>sympytex</code> : Improved		
	<code>sympyblock</code>	1134	
	<code>xetexko</code> : Updated to v4.0.	1226	
	<code>xpinyin</code> : Removed deprecated		
	<code><rb></code>	1232	

Fixed: Footnotes inside square brackets.	365	\LWR@subsingledollar: Improved math sanitization.	543
Forbid beamer.	207	\NewEnvironmentCopy: Added.	221
Improved footnote par tags.	365	\csNewCommandCopycs: Added.	221
Improved footnotes.	582	General: 2022/02/01	1
Improved par tags.	355	lwarp.css: Improved pars in lists.	267
MATHJAX: Added std. intl. symbols.	381	Slunits: Improved alt tag sanitization.	1064
Lateximage: Improved footnotes.	565	chemformula: Improved alt tag sanitization.	700–702
Removed varwidth.	567	chemmacros: Improved alt tag sanitization. 707, 715, 719, 723, 945	
description: Improved footnotes.	427	color: Par handling.	734
minipage: Improved footnotes. 584, 585		cuted: Updated to v2.0.	740
v0.903		endnotes: Nullify endnotes.	755
\@ensuredmath: Improved math sanitization.	545	etoolbox: Patch for \NewCommandCopy.	201
\InlineClass: Now using \NewCommandCopy.	352	fancybox: Par handling.	777
\LWR@HTMMLatexCmd: Allow transparency.	265	fancybox: Warn if span.	777
\LWR@HTMLsanitizedetokenized: Added.	378	flushend: Updated to v4.0.	802
\LWR@LwarpStart: Par handling.	402	graphics: alt now in graphicx core.	575, 830
\LWR@checkloadnevers: Alternative for cellspace.	205	lipsum: Par handling.	893
\LWR@closeparagraph: Par handling.	356	mathalpha: Updated for v1.14+.	918
\LWR@closeparagraph@br: Par handling.	356	mhchem: Improved alt tag sanitization.	945
\LWR@doubledollar: Improved alt tag sanitization.	544	minted: Updated to v2.6.	949
Improved math sanitization.	544	multirow: Par handling.	963
\LWR@expandableformatted: Now using \NewCommandCopy.	252	nccfoots: Nullify footnotes.	971
\LWR@expandableformattedenv: Now using \NewCommandCopy.	253	parnotes: Fixed if no cleveref.	1009
\LWR@formatted: Now using \NewCommandCopy.	252	parnotes: Nullify footnotes.	1009
\LWR@formattedenv: Now using \NewCommandCopy.	253	parnotes: Par handling.	1008, 1009
\LWR@futurenonamespacelet: Now ignores \par.	432	showlabels: Added.	1059
\LWR@itemizeitem: Par handling.	426	siunitx-v2: Improved alt tag sanitization.	1084, 1085
\LWR@listitem: Par handling.	425	siunitx, MATHJAX: Improved decimal commas.	1092, 1093, 1095
\LWR@nullifyfootnotes: Added.	369	siunitx, MATHJAX: Leading zero.	1092
\LWR@openparagraph: Par handling.	356	siunitx: Improved \per.	1097
\LWR@refwithsection: Fixed: Ref undefined or w/o label.	497	siunitx: MATHJAX: Improved \SIlist.	1096
\LWR@restoreorigformatting: Par handling.	529	siunitx: MATHJAX: Improved \numlist.	1095
\LWR@section: Add: Sectioning HTML comment divider.	391	todo: Fix if no cleveref.	1185
Fix: Nullify footnotes in HTML comment.	391	wrapfig2: Added.	1212
\LWR@setexparray: Par handling.	332	wrapfig: Fix: width style.	1211
\LWR@singledollar: Improved alt tag sanitization.	545	xcolor: Par handling.	1217
\LWR@startpars: Par handling.	358	lwarpmk: Error if pdftotext not available.	311
\LWR@stoppars: Par handling.	359	Docs: Math images.	87
		Docs: Now using \NewCommandCopy, xparse OK.	249
		Now uses \IfPackageLoadedTF, etc.	1
		Par handling.	354, 358
		tabbing: Converted to env.	421
		tabular: Par handling.	485, 486
		fcolorminipage: Now using \NewCommandCopy.	577

verbatim: Added verbatim*.	420	siunitx-v2: Updated to v2.8e.	1082
BlockClass: Now using		siunitx, MATHJAX: Fixed \pm.	1093
\NewCommandCopy.	351	siunitx, MATHJAX: Split by x	
fminipage: Now using		before e.	1094
\NewCommandCopy.	589	siunitx, MATHJAX: Use	
LWR@BlockClassWP: Now using		range-phrase.	1080, 1096
\NewCommandCopy.	352	siunitx: Added v3.	573, 1072
LWR@nestspan: Par handling.	347	wrapfig2: Update to v5.0.	1213
v0.904		File: lwarp_mathjax.txt: Added	
\HTMLentity: Improved font		\gsub macro.	307
control.	335	File: lwarp_mathjax.txt:	
\HTMLnewcolumnstype: Added		Defaults to SVG instead of	
optional arg.	451	CHTML.	307
\LWR@fontfortags: Improved font		Warn if & outside tabular.	333
control.	335	v0.904a	
\LWR@htmltagc: Improved font		General: 2022/03/16	1
control.	346	Fixed missing	
\LWR@textcurrentfont: Uses		common-mathjax-siunitx.	1
textnormal if possible.	595	v0.905	
\colorboxBlock: xcolor: Added		\@wrindex: Label after file write.	522
optional HTML style.	1221	\LWR@LwarpEnd: Fixed	
\textnormal: Improved.	594	\LWR@LwarpEnd hook order.	612
General: 2022/03/09	1	\LWR@myshorttoc: Disable \ref and	
array: Improved W and w		CJK pinyin in toc, etc.	512
processing.	650	\listoffigures: Disable \ref and	
cancel: Now \LWR@formatted.	684	CJK pinyin in toc, etc.	514
caption: Added \captiontext.	687	\listoftables: Disable \ref and	
chemmacros: Accept lwarp		CJK pinyin in toc, etc.	514
version of pkgs.	706	\tableofcontents: Disable \ref	
chemmacros: Nullify hyperref		and CJK pinyin in toc, etc.	513
detection.	706	General: 2022/03/22	1
common-mathjax-siunitx:		acronym: Add hyperlinks.	631
Factored from siunitx-v2.	1091	acronym: Improved pars.	631
fbox: Added border colors.	788, 789	acronym: Updated to v1.47.	629
hyperref: Added \HyperDest*.	850	cases: Removed microtype bug	
hyperref: Added \hyperget.	850	fix.	690
lltjp-siunitx: Added.	900	hyperref: Fix: No HTML tags if	
multicol: Added \newcolumn.	958	math mode.	852
siunitx-v2, MATHJAX: Use		Added last of three, four.	222
range-phrase.	1091	Label after file	
siunitx-v2: Improved range		write.	859, 860, 1110, 1262
phrase.	1090		

Index of Objects

This is an index of macros, environments, booleans, counters, lengths, packages, classes, options, keys, files, and various other programming objects. Each is listed by itself, and also by category. In some cases, they are further subdivided by [class].

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

Symbols	
\\$	535
\&	<i>336</i> , <i>8867</i>
\(<u>11957</u>
*-images.txt (file)	<i>562</i>
*_html.aux (file)	<i>370</i> , <i>490</i> , <i>562</i>
*_html.lof (file)	<i>508</i>
*_html.lot (file)	<i>508</i>
*_html.tex (file)	<i>260</i>
\,	<i>120</i>
--shell-escape (option)	<i>100</i>
\@@@setcpageref	<u>39</u>
\@@@setcref	<u>2</u>
\@@@setcrefrange	<u>17</u>
\@author	<i>407</i>
\@begintheorem	<u>8483</u>
\@biblabel	<u>11392</u>
\@caption	<u>10806</u>
\@capttype	<u>10783</u>
\@chapcntformat	<u>7539</u>
\@currenthref	<u>10582</u>
\@currentlabelname	<u>10362</u>
\@date	<i>407</i>
\@donoparitem	<u>8515</u>
\@endtheorem	<u>8498</u>
\@ensuredmath	<u>11967</u>
\@fnsymbol	<u>8202</u>
\@footnotetext	<u>6879</u>
\@include	<u>1649</u>
\@item	<u>8528</u>
\@makecaption	<u>10806</u>
\@makefnmark	<u>6848</u>
\@makefntext	<u>6847</u>
\@maketitle	<i>57</i> , <u>8236</u>
\@mklab	<u>8509</u>
\@mpfootnotetext	<u>6881</u>
\@nbitem	<u>8593</u>
\@opargbegintheorem	<u>8490</u>
\@partcntformat	<u>7540</u>
\@partnameformat	<u>7541</u>
\@rowcol	<u>9290</u>
\@rowcolors	<u>9289</u>
\@secntformat	<u>7537</u>
\@starttoc	<u>10947</u>
\@textsubscript	<u>13452</u>
\@textsuperscript	<u>13448</u>
\@title	<i>407</i>
\@wrglossary	<u>11211</u>
\@wrintindex	<u>11186</u>
\@xdlbfloat	<u>10727</u>
\@xfloat	<u>10727</u>
\[<u>11957</u>
\]	<i>602</i>
\$	<i>543</i>
\$\$	<i>543</i>
\@nameauth@Hook (hook) [nameauth]	<i>968</i>
\KFLT@LWR@hook@boxouter (hook)	
[keyfloat]	<i>870</i>
\KFLT@LWR@hook@keyfloatsminipage (hook) [keyfloat]	<i>871</i>
\KFLT@LWR@hook@keyfloats (hook)	
[keyfloat]	<i>871</i>
\KFLT@LWR@hook@keysubfloats (hook)	
[keyfloat]	<i>870</i>
\LWR@hook@processingtags (hook)	
[lwarp]	<i>344</i>
\fancyrefhook (hook) [fancyref]	<i>780</i>
2in1 (package)	<i>621</i>
2up (package)	<i>621</i>

A	
a4 (package)	<i>621</i>
a4wide (package)	<i>621</i>
a5comb (package)	<i>622</i>
abstract (environment)	<u>8304</u>
abstract (package)	<i>131</i> , <i>622</i>
\abstractname	<i>110</i> , <u>8303</u>
academicons (package)	<i>624</i>
accents (package)	<i>625</i>
accessibility (package)	<i>626</i>
accsupp (package)	<i>626</i>
acro (package)	<i>627</i>
acronym (package)	<i>629</i>
\addcontentsline	<u>10895</u>
addlines (package)	<i>633</i>
\AddSubtitlePublished	<u>8267</u>
adjmulticol (package)	<i>632</i>
Adobe (program)	<i>73</i>
\affiliation	<u>8100</u>
afterpage (package)	<i>633</i>
algorithm2e (package)	<i>633</i>
algorithmicx (package)	<i>166</i> , <i>637</i>
align (environment)	<u>95</u>
align* (environment)	<u>98</u>
alignat (environment)	<u>107</u>
alignat* (environment)	<u>110</u>

alltt (package)	638	booktabs (package)	678
\AltTextClose	112, 11609	boolean:	
\AltTextOpen	112, 11608	CombineHigherDepths	109, 372
\AmS	13811	FileSectionNames	109, 337
amscdx (package)	638	FixSmallCaps	109, 120, 591
amsmath (package)	639	FormatEpub	178, 254
amsthm (package)	643	FormatWP	180, 254
\and	407	HTMLDebugComments	110, 249
anonchap (package)	647	LWR@algocf@dopars	355
anysize (package)	647	LWR@allowanothergeometry	237
appendix (package)	132, 648	LWR@amsmultiline	555
ar (package)	648	LWR@copiedsidetoc	513
arabicfront (package)	650	LWR@doingapar	354
array (package)	650	LWR@doingcmidrule	433
\arrayrulecolor	9297	LWR@doingparhooks	354
\arrayrulecolornexttoken	9297	LWR@doingstartpars	354
arydshln (package)	651	LWR@doingtbrule	433
AsciiDoc (program)	73	LWR@dynamicmath	334
AsciiDoctor (program)	73	LWR@emptyatbang	434
Asciidoctor-LaTeX (program)	73	LWR@exitingtabular	434
asymptote (package)	159, 653	LWR@forceminipagefullwidth	582
atbegshi (package)	653	LWR@foundmrowcell	433
attachfile (package)	654	LWR@freezethisautoid	506
attachfile2 (package)	655	LWR@in@multirow@par	354
\attrib	170, 417, 1202	LWR@indisplaymathimage	534
\attribution	8314	LWR@insidemathcomment	534
authblk (package)	131, 657	LWR@intabularmetadata	434
\author	117, 407	LWR@isstartingequation	560
autobreak (package)	658	LWR@MathJax@silentquotes	377
autonum (package)	658	LWR@mathmacro	333
autosec	388	LWR@minipagefullwidth	582
awesomebox (package)	659	LWR@minipagethispar	582
axessibility (package)	660	LWR@opttablecol	434
axodraw2 (package)	661	LWR@origmathjax	227
		LWR@setseqfilelabel	337
		LWR@skipatbang	433
		LWR@skippingmcolrowcell	433
		LWR@skippingmrowcell	433
		LWR@spewingnotes	365
		LWR@starredlongtable	436
		LWR@startedrow	432
		LWR@starting@fancybox	354
		LWR@tableparcell	433
		LWR@tabularcelladded	433
		LWR@tabularmutemods	434
		LWR@tracinglwarp	249
		LWR@unknownmathsize	537
		LWR@usedmultirow	433
		LWR@validtablecol	434
		LWR@verbtags	418
		LWR@warnbaselinemarker	536
		LWR@warnedcustomizemathjax	379
		LWR@xfakebold	534
		LWR@index@tricked	521
		mathjax	227
		usingOSWindows	226
		warpingHTML	227
		warpingprint	227
		WPMarkFloats	181, 254
		WPMarkLOFT	182, 255
B			
babel (package)	171		
\backmatter	7515		
backnaur (package)	661		
backref (package)	662		
balance (package)	662		
\BaseJobname	6042		
BaseJobname (option)	106, 228		
bbding (package)	663		
beamerarticle (package)	667		
\bfseries	13348		
biblatex (package)	669		
\bibliography	11392		
\BibTeX	13804		
bibunits (package)	673		
bigdelim (package)	166, 673		
bigfoot (package)	675		
bigstrut (package)	675		
bitpattern (package)	676		
BlockClass (environment)	115, 6520		
\BlockClassSingle	6531		
blowup (package)	676		
bm (package)	676		
booklet (package)	677		
bookmark (package)	677		

WPMarkMath	182, 255	classicthesis (package)	728
WPMarkMinipages	181, 254	\cleardoublepage	13633
WPMarkTOC	182, 255	\clearpage	13633
WPTitleHeading	182, 255	cleveref (package)	128, 729
bophook (package)	680	clrdblpg (package)	732
bounddvi (package)	680	cm-super (package)	100
boxedminipage (package)	680	cmap (package)	101
boxedminipage2e (package)	681	cmbright (package)	732
\boxframe	180	cmdtrack (package)	733
braket (package)	681	colonequals (package)	733
breakurl (package)	681	\color	54
breqn (package)	682	color (package)	158, 734
bsheaders (package)	683	\colorbox	81
bussproofs (package)	683	\colorboxBlock	90, 12692
BVerbatim (environment)	257	colortbl (package)	165, 734
bxpapersize (package)	684	CombineHigherDepths (boolean)	109, 372
bytefield (package)	684	comment (package)	233
C			
calc (package)	238	common-mathjax-siunitx (package)	1091
cancel (package)	684	\ConTeXt	13799
canoniclayout (package)	685	continue (package)	736
capt-of (package)	510	copyrightbox (package)	736
caption (package)	166, 510, 685	core.ins (file)	188
caption3 (package)	687	counter:	
\caption@begin	10863	FileDepth	109, 372
\caption@end	10863	FootnoteDepth	109, 364
\captionlistentry	10870	footnoteReset	364
\captionof	10911	lofdepth	517
\CaptionSeparator	10805	lotdepth	517
cases (package)	690	LWR@cellcolordepth	435
ccicons (package)	690	LWR@currentautosecfloatpage	371
center (environment)	12570	LWR@currentautosecpage	370
\centering	12600	LWR@externalfilecnt	534
centerlastline (package)	691	LWR@hdashedlines	433
\centerline	12619	LWR@hlines	433
centernot (package)	691	LWR@htmlfilenumber	337
changebar (package)	691	LWR@htmlseqfilenumber	337
changelayout (package)	692	LWR@lateximagedepth	559
changepage (package)	692	LWR@lateximagenumber	559
changes (package)	693	LWR@Lipage	559
chappg (package)	698	LWR@maxfields@	639
\chapter	7761	LWR@midrulecounter	436
chapterbib (package)	698	LWR@minipage@depth	582
chemfig (package)	698	LWR@mpfootnote@store	582
chemformula (package)	700	LWR@nextautoid	508
chemgreek (package)	705	LWR@nextautopage	508
chemmacros (package)	705	LWR@nextequation	547
chemnum (package)	725	LWR@prevFileDepth	388
chkfloat (package)	726	LWR@previousautopagelabel	371
chnpage (package)	726	LWR@spandepth	354
cite (package)	727	LWR@startingequation	560
citeref (package)	727	LWR@tablecolspecindex	435
CJK (package)	727	LWR@tablecolspecwidth	435
CJKutf8 (package)	728	LWR@tableLaTeXcolindex	435
class (key) [Gin]	830	LWR@tabletotalLaTeXcols	435
class:		LWR@tabletotalLaTeXcolsnext	435
internet	72	LWR@tabularDepth	434
komascript	168	LWR@tabularpardepth	434
memoir	168, 170, 1203	LWR@thisautoid	505
		LWR@thisautoidWP	506
		LWR@virtualpagedepth	581

SideTOCDepth	107, 515	\enlargethispage	13632
tocdepth	107	enotez (package)	759
\cpagerefFor	38	\enskip	603, 13577
crop (package)	737	enumerate (environment)	8655
\csNewCommandCopycs	951	enumerate (package)	761
\CSSFilename	110, 113, 6785	enumitem (package)	762
ctable (package)	737	environ (package)	240
\CustomizeMathJax	7258, 7369	environment:	
cuted (package)	740	BlockClass	115
cutwin (package)	740	fminipage	123
		lateximage	558
		picture	580
		titlepage	117
		titlingpage	117
		warpall	116
		warpHTML	112, 115
		warpMathJax	116
		warpprint	112, 116
		warpsvg	116
		environments:	
		abstract	8304
		align	95
		align*	98
		alignat	107
		alignat*	110
		BlockClass	6520
		BVerbatim	257
		center	12570
		description	8681
		enumerate	8655
		eqnarray	12272
		equation	12202
		equation*	12210
		fcolorminipage	160, 12732
		flalign	101
		flalign*	104
		flushleft	12590
		flushright	12580
		fminipage	13066
		gather	89
		gather*	92
		itemize	8647
		lateximage	12416, 12566
		list	8615
		longtable	4
		LWR@BlockClassWP	6559
		LWR@blocktextcurrentfont	13334, 13480
		LWR@displaymathnormal	12011
		LWR@displaymathother	12014
		LWR@equationother	12027
		LWR@figcaption	10833
		LWR@glrbox	1004
		LWR@nestspan	6353
		LWR@setvirtualpage	12815
		LWR@createlwarpmk	1315
		math	12010
		minipage	12844
		multline	82
		multline*	85
D			
\date	117		
dblfloatfix (package)	741		
dblfnote (package)	741		
dcolumn (package)	741		
decimal (package)	742		
\DeclareGraphicsExtensions	2		
\DeclareSIUnit	154, 572, 1081		
decorule (package)	742		
\defaddtocounter	939		
dejavu (package)	100		
description (environment)	8681		
diagbox (package)	742		
dingbat (package)	744		
\displaymathnormal	152, 553, 12224		
\displaymathother	152, 554, 12235		
ditaa (package)	177		
DotArrow (package)	745		
\dotfill	13551		
dotlessi (package)	745		
\doublerulesepcolor	9299		
\doublerulesepcolornexttoken	9299		
dprogress (package)	746		
draftcopy (package)	746		
draftfigure (package)	746		
draftwatermark (package)	747		
drftcite (package)	747		
dvipdfm (option)	102, 231		
dvipdfmx (option)	102, 231		
dvips (option)	102, 231		
E			
easy-todo (package)	747		
ebook (package)	748		
\ebweight	13353		
econometrics (package)	749		
ed (package)	751		
ellipsis (package)	752		
embrac (package)	752		
\emph	13135		
emptypage (package)	753		
\end@dlbfloat	10752		
\end@float	10752		
\enddocument	8036		
enddocument/info (hook) [LaTeX]	405		
endfloat (package)	753		
endheads (package)	753		
endnotes (package)	132, 754		
engtlc (package)	755		

picture	12806	*_html.aux	370, 490, 562
quotation	8341	*_html.lof	508
quote	8333	*_html.lot	508
tabbing	8462	*_html.tex	260
tabular	10204	core.ins	188
thebibliography	11393	glyphtounicode.tex	101
theindex	11135	lwarp.css	114, 267
titlepage	8117	lwarp.ist	143, 305
titlingpage	14	lwarp.xdy	144, 306
verbatim	8428	lwarp_baseline_marker.eps	535
verse	2, 8351	lwarp_baseline_marker.png	535
warpall	1290	lwarp_formal.css	301
warpHTML	1291	lwarp_mathjax.txt	307
warpMathJax	1297	lwarp_one_limage.cmd	306
warpprint	1294	lwarp_sagebrush.css	297
warpsvg	1306	lwarp_tutorial.txt	82
epigraph (package)	762	lwarpmk.conf	266
epsf (package)	763	lwarpmk.lua	189
epsfig (package)	763	project.css	114
epstopdf (package)	158, 764	project.lwarpmkconf	267
epstopdf (program)	156, 574	sample_project.css	114, 305
epstopdf-base (package)	764	tutorial.tex	82
eqlist (package)	765	filecontents (package)	239
eqnarray (environment)	12272	FileDepth (counter)	109, 372
eqparbox (package)	765	\FilenameLimit	109, 7010
equation (environment)	12202	\FilenameNullify	127, 11603, 13481
equation* (environment)	12210	\FilenameSimplify	126, 7031, 7370
errata (package)	766	FileSectionNames (boolean)	109, 337
eso-pic (package)	768	fitbox (package)	791
esvect (package)	768	fix2col (package)	791
\etalchar	132	fixmath (package)	791
etoc (package)	768	fixme (package)	171, 792
etoolbox (package)	201	fixmetodonotes (package)	793
eurosym (package)	771	FixSmallCaps (boolean)	109, 120, 591
everypage (package)	771	flafter (package)	794
everyshi (package)	771	\flagverse	1203
expl3 (package)	238	flalign (environment)	101
extrarrows (package)	772	flalign* (environment)	104
extramarks (package)	772	Flare (program)	73
		flippdf (package)	794
F		float (package)	166, 794
fancybox (package)	124, 773	floatflt (package)	796
fancyhdr (package)	778	floatpag (package)	797
fancypar (package)	779	floatrow (package)	167, 797
[fancyref]:		fltrace (package)	802
\fancyrefhook (hook)	780	\flushbottom	6241
fancyref (package)	780	flushend (package)	802
fancytabs (package)	780	flushleft (environment)	12590
fancyvrb (package)	781	flushright (environment)	12580
\fbox	123, 13036	fminipage (environment)	123, 13066
fbox (package)	787	fnbreak (package)	802
\fboxBlock	123, 13047	fncychap (package)	803
\fcolorbox	103, 12694	fnlineno (package)	803
\fcolorboxBlock	122, 12730	fnpara (package)	803
fcolorminipage (environment)	160, 12732	fnpos (package)	804
fewerfloatpages (package)	790	fontawesome (package)	804
figcaps (package)	790	fontawesome5 (package)	805
figsize (package)	790	fontaxes (package)	806
file:		fontenc (package)	101, 806
*-images.txt	562	fontspec (package)	100, 235

footmisc (package)	807
footnote (package)	808
footnotebackref (package)	809
FootnoteDepth (counter)	109, 364
footnotehyper (package)	810
footnoterange (package)	810
footnoteReset (counter)	364
footnpag (package)	810
\ForceHTMLPage	131, 7490
\ForceHTMLTOC	131, 7496
foreign (package)	810
forest (package)	811
FormatEPUB (boolean)	178, 254
FormatWP (boolean)	180, 254
fouridx (package)	811
fourier (package)	812
\framebox	13013
framed (package)	813
FrameMaker (program)	73
\frontmatter	7512
froufrou (package)	815
ftcap (package)	816
ftnright (package)	816
fullminipage (package)	817
fullpage (package)	817
fullwidth (package)	817
\fup	13455
\fussy	6243
fvextra (package)	817
fwlw (package)	820
G	
gather (environment)	89
gather* (environment)	92
GELLMU (program)	72
gensymb (package)	821
gentombow (package)	821
geometry (package)	236, 821
getttitlestring (package)	239
ghsystem (package)	822
[Gin]:	
class (key)	830
gindex (package)	135, 823
GladTeX (program)	72
gloss (package)	132, 823
glossaries (package)	133, 824
GlossaryCmd (option) ..	106, 133, 230, 824
glyphtounicode.tex (file)	101
gmeometric (package)	826
graphics (package)	155, 826
graphicx (package)	155, 838
grffile (package)	157, 838
grid (package)	839
grid-system (package)	839
gridset (package)	839
H	
hang (package)	840
hanging (package)	841
hepunits (package)	842
Hevea (program)	72
\hfill	13530
hhline (package)	843
hhtensor (package)	844
\HomeHTMLFilename	6044
HomeHTMLFilename (option) ...	102, 229
hook:	
[LaTeX]:	
enddocument/info	405
para/begin	358
para/end	358
shipout/background	406
shipout/foreground	406
[fancyref]:	
\fancyrefhook	780
[keyfloat]:	
\KFLT@LWR@hook@boxouter ...	870
\KFLT@LWR@hook@keyfloatsminipage	871
\KFLT@LWR@hook@keyfloats ..	871
\KFLT@LWR@hook@keysubfloats	870
[lwarp]:	
\LWR@hook@processingtags ..	344
[nameauth]:	
\@nameauth@Hook	968
\hrule	120
\hrulefill	120, 13532
\hskip	120
\hspace ..	120, 603, 13585, 13616, 13622
htlatex (program)	72
\HTMLAuthor	111, 118, 6822
HTMLDebugComments (boolean) ..	110, 249
\HTMLDeclareSIUnit ..	154, 323, 572, 1081
\HTMLDescription	111, 118, 6827
\HTMLEntity	6025
\HTMLFilename	6043
HTMLFilename (option)	102, 229
\HTMLFirstPageBottom	107, 6773
\HTMLFirstPageTop	107, 6770
htmlglossary (option) [lwarpmk]	133, 824
HTMLIndexCmd (option)	105, 230
\HTMLLanguage	110, 7794
HTMLLatexCmd (option)	104, 173, 230
\HTMLleftmargini (length)	170, 417, 418, 1203
\HTMLnewcolumnntype	112, 9205
\HTMLPageBottom	111, 407, 6779
\HTMLPageTop	111, 6776
\HTMLTitle	110, 118, 6817
\HTMLTitleAfterSection	110, 7817
\HTMLTitleBeforeSection ...	110, 7812
\HTMLUnicode	6034
\HTMLvleftskip (length) 170, 417, 418, 1203	
hypbmsec (package)	844
hypcap (package)	844
hypdestopt (package)	845
\hyperindexformat	11381
\hyperindexref	11339
hypernat (package)	845
\hyperpage	11379

hyperref (package)	128, 499, 845	kotex (package)	172
\hypertoc	11068	kpfonts (package)	876
\hypertocfloat	11091	kpfonts-otf (package)	878
hyperxmp (package)	855	kvoptions (package)	227
hyphenat (package)	856		
		L	
I		\l@book	11111
idxlayout (package)	857	\l@chapter	11113
\if@titlepage	8095	\l@figure	11124
\ifnextchar	150	\l@paragraph	11122
ifoddpage (package)	857	\l@part	11112
ifplatform (package)	201	\l@section	11119
\ifstar	150	\l@subparagraph	11123
\IgnoreMinipageWidths	123, 580, 12831	\l@subsection	11120
\ImageAltText	111, 11610	\l@subsubsection	11121
ImagesDirectory (option)	102, 228	\l@table	11125
ImagesName (option)	102, 228	[LaTeX]:	
imakeidx (package)	858	enddocument/info (hook)	405
imakeidx (program)	138	para/begin (hook)	358
imnatty (package)	862	para/end (hook)	358
\includegraphics	323	shipout/background (hook)	406
indentfirst (package)	360	shipout/foreground (hook)	406
InDesign (program)	73	\LaTeX	13753
index (package)	862	LaTeX2HTML (program)	72
index (program)	136	\LaTeXe	13753
\IndexPageSeparator	110, 11133	lateximage (environment)	558, 12416, 12566
\IndexRangeSeparator	110, 11133	12345
IndexRef (option)	105, 230	\LateximageFontScale	12344
\InlineClass	115, 6541	\LateximageFontSizeName	12344
\inlinemathnormal	152, 5994	latexmk (option)	102, 230
\inlinemathother	152, 5990	latexmk (program)	174
inputenc (package)	101	LatexmkIndexCmd (option)	105, 230
inputenx (package)	101	LaTeXML (program)	72
inputtrc (package)	863	layaureo (package)	880
internet (class)	72	layout (package)	880
intopdf (package)	864	layouts (package)	880
isomath (package)	864	leading (package)	883
isotope (package)	864	leftidx (package)	883
itemize (environment)	8647	\leftline	12618
\itshape	13387	length:	
		\HTMLleftmargini	170, 417, 418, 1203
J		\HTMLvleftskip	170, 417, 418, 1203
jurabib (package)	866	\LWR@cmidrulewidth	459
		\LWR@heavyrulewidth	459
K		\LWR@lightrulewidth	459
karnaugh-map (package)	867	\LWR@minipageheight	581
\kern	120	\LWR@minipagewidth	581
key:		\LWR@tempheight	604
[Gin]:		\LWR@tempraise	604
class	830	\LWR@tempwidth	604
[keyfloat]:		\LWR@thiscmidrulewidth	460
\KFLT@LWR@hook@boxouter (hook)	870	\VerbatimHTMLwidth	418
\KFLT@LWR@hook@keyfloatsminipage		\vleftmargini	170, 417, 1203
(hook)	871	\vleftskip	170, 417, 1203
\KFLT@LWR@hook@keyfloats (hook)	871	letltxmacro (package)	201
\KFLT@LWR@hook@keysubfloats		letterspace (package)	883
(hook)	870	lettrine (package)	884
keyfloat (package)	168, 870	\lgweight	13360
keystroke (package)	875	libertinust1math (package)	884
komascript (class)	168	LibreOffice (program)	73

<code>\linebreak</code>	13626	<code>lwrap_mathjax.txt</code> (file)	307
<code>lineno</code> (package)	890	<code>lwrap_one_limage.cmd</code> (file)	306
<code>\LinkHome</code>	111, 6113, 6118	<code>lwrap_sagebrush.css</code> (file)	297
<code>\linkhomename</code>	107, 6110	<code>lwrap_tutorial.txt</code> (file)	82
<code>\LinkNext</code>	111, 6146, 6159	[lwrapmk]:	
<code>\linknextname</code>	107, 6142	<code>htmlglossary</code> (option)	133, 824
<code>\LinkPrevious</code>	111, 6145, 6149	<code>printglossary</code> (option) ...	133, 824
<code>\linkpreviousname</code>	107, 6141	<code>lwrapmk</code> (option)	106, 229, 311
<code>Linux</code> (program)	115, 225	<code>lwrapmk</code> (program)	189, 311
<code>lips</code> (package)	892	<code>lwrapmk epstopdf</code> (program) ..	156, 574
<code>lipsum</code> (package)	893	<code>lwrapmk pdftosvg</code> (program) ..	156, 574
<code>list</code> (environment)	8615	<code>lwrapmk.conf</code> (file)	266
<code>listings</code> (package)	893	<code>lwrapmk.lua</code> (file)	189
<code>listliketab</code> (package)	899	<code>\lwrapsetup</code>	1078
<code>\listoffigures</code>	10981	<code>\LWR@footnotetext</code>	6851
<code>\listoftables</code>	10998	<code>\LWR@makebox@align</code>	12969
<code>lltjext</code> (package)	899	<code>\LWR@makebox@paren</code>	12954
<code>lltjp-siunitx</code> (package)	900	<code>\LWR@printpendingfootnotes</code> ...	6906
<code>lltjp-tasclmac</code> (package)	901	<code>\LWR@absorbstar</code>	1031
<code>lmodern</code> (package)	100, 101	<code>\LWR@addbaselinemarker</code>	11645
<code>lofdepth</code> (counter)	517	<code>\LWR@addcdashline</code>	9562
<code>longtable</code> (environment)	4	<code>\LWR@addcmidruletrim</code>	9528
<code>longtable</code> (package)	164, 901	<code>\LWR@addcmidrulewidth</code>	9559
<code>lotdepth</code> (counter)	517	<code>\LWR@addcompilecmd</code>	2089
<code>lpic</code> (package)	904	<code>\LWR@addformatwppalignment</code> ...	9578
<code>lscapc</code> (package)	904	<code>\LWR@addleftmostbartag</code>	9369
<code>ltablex</code> (package)	905	<code>\LWR@addlinktitle</code>	10483
<code>ltxcaption</code> (package)	905	<code>\LWR@addmathjax</code>	12107
<code>ltxgrid</code> (package)	905	<code>\LWR@addmulticolvertulecolor</code> ..	9792
<code>ltxtable</code> (package)	906	<code>\LWR@addrulewidth</code>	9533
<code>lua-check-hyphen</code> (package)	906	<code>\LWR@addtabularcellcolor</code>	9704
<code>lua-visual-debug</code> (package)	906	<code>\LWR@addtabularhrulecolor</code>	9603
<code>luacolor</code> (package)	906	<code>\LWR@addtabulararrowcolor</code>	9588
<code>\LuaLaTeX</code>	13782	<code>\LWR@addtabulararrulecolors</code> ...	9649
<code>LuaLaTeX</code> (program) [requirement] ..	76	<code>\LWR@afterrendverbatim</code>	8412
<code>luamplib</code> (package)	907	<code>\LWR@afterloadnever</code>	94
<code>\LuaTeX</code>	13782	<code>LWR@algocf@dopars</code> (boolean)	355
<code>luatexko</code> (package)	907	<code>LWR@allowanothergeometry</code> (boolean)	237
<code>luatodonotes</code> (package)	171, 909	<code>\LWR@amsmathbody</code>	12378
<code>luavlna</code> (package)	911	<code>\LWR@amsmathbodynumbered</code>	12384
[lwrap]:		<code>LWR@amsmultline</code> (boolean)	555
<code>\LWR@hook@processingtags</code> (hook) ..	344	<code>\LWR@applyxfakebold</code>	11627
<code>lwrap</code> (package)	102	<code>\LWR@atbeginverbatim</code>	8391
<code>lwrap-common-mathjax-letters</code> (pack-		<code>\LWR@avoiddupfilenames</code>	7042
age)	1272	<code>\LWR@backgroundcolor</code>	42
<code>lwrap-common-mathjax-newpctxmath</code>		<code>\LWR@beginhideamsmath</code>	12254
(package)	1278	<code>LWR@BlockClassWP</code> (environment) ..	6559
<code>lwrap-common-mathjax-nonunicode</code>		<code>LWR@blocktextcurrentfont</code> (environ-	
(package)	1285	ment)	13334, 13480
<code>lwrap-common-mathjax-overlaysymbols</code>		<code>\LWR@botnavigation</code>	6136
(package)	1288	<code>LWR@cdashlines</code>	459
<code>lwrap-common-multimedia</code> (package) ..	1267	<code>LWR@cellcolordepth</code> (counter)	435
<code>lwrap-patch-komascript</code> (package) ..	1238	<code>\LWR@cellHTMLcolor</code>	9294
<code>lwrap-patch-memoir</code> (package)	1240	<code>\LWR@checkbeforeaddclass</code>	9017
<code>lwrap.css</code> (file)	114, 267	<code>\LWR@checkloadbefore</code>	68
<code>lwrap.ist</code> (file)	143, 305	<code>\LWR@checkloadfilename</code>	1477
<code>lwrap.xdy</code> (file)	144, 306	<code>\LWR@checkloadnever</code>	233, 1476
<code>lwrap_baseline_marker.eps</code> (file) ..	535	<code>\LWR@checkloadnevers</code>	125
<code>lwrap_baseline_marker.png</code> (file) ..	535	<code>\LWR@checkmathcolpar</code>	9025
<code>lwrap_formal.css</code> (file)	301	<code>\LWR@clearmidrules</code>	9448

<code>\LWR@closeparagraph</code>	6675	<code>\LWR@expandableformattedenv</code>	1815
<code>\LWR@closeparagraph@br</code>	6663	<code>\LWR@expandpreamble</code>	9141
<code>\LWR@closeprevious</code>	6204	<code>LWR@externalfilecnt (counter)</code>	534
<code>\LWR@closetabledatacell</code>	8820	<code>\LWR@fboxstyle</code>	13029
<code>\LWR@cmidrulewidth (length)</code>	459	<code>\LWR@fifthoffive</code>	973
<code>LWR@coladdclass</code>	435	<code>LWR@figcaption (environment)</code>	10833
<code>LWR@colafterspec</code>	435	<code>\LWR@filenamoblanks</code>	7055
<code>LWR@colatspec</code>	435	<code>\LWR@filestart</code>	7826
<code>LWR@colbangspec</code>	435	<code>\LWR@findcurrenttextcolor</code>	13470
<code>LWR@colbarspec</code>	435	<code>\LWR@findword</code>	1473
<code>LWR@colbeforespec</code>	435	<code>\LWR@firstoffive</code>	973
<code>\LWR@columnHTMLcolor</code>	9292	<code>\LWR@floatalignment</code>	10785
<code>\LWR@columnspeclookahead</code>	8951	<code>\LWR@floatalignmentname</code>	10784
<code>\LWR@compilecmd</code>	2086	<code>\LWR@floatbegin</code>	10690
<code>\LWR@compileuplatex</code>	2121	<code>\LWR@floatend</code>	10737
<code>\LWR@convertto</code>	934	<code>\LWR@floatstyle</code>	2
<code>LWR@copiedsidetoc (boolean)</code>	513	<code>\LWR@fontfortags</code>	6001
<code>\LWR@copyfile</code>	1684	<code>\LWR@footnotebox</code>	6845
<code>\LWR@createautosec</code>	7521	<code>\LWR@footnotetext</code>	6878
<code>\LWR@createfooter</code>	7373	<code>\LWR@forceemptyline</code>	969
<code>LWR@currentautosecfloatpage (counter)</code>	371	<code>LWR@forceminipagefullwidth (boolean)</code>	582
<code>LWR@currentautosecpage (counter)</code>	370	<code>\LWR@forceminwidth</code>	13018
<code>\LWR@currentautosecpage (counter) . . .</code>	10384	<code>\LWR@forcenewautoidanchor</code>	10760
<code>\LWR@currentcss</code>	6784	<code>\LWR@forcenewpage</code>	6224
<code>\LWR@currenttextcolor</code>	13466	<code>\LWR@forceSVGmessage</code>	14047
<code>\LWR@customizedMathJax</code>	7243	<code>\LWR@formatted</code>	1771
<code>\LWR@customizeMathJax</code>	7350	<code>\LWR@formatted@checkendname</code>	1751
<code>\LWR@descitem</code>	8663	<code>\LWR@formatted@checkname</code>	1731
<code>\LWR@disablepinyin</code>	968	<code>\LWR@formattedenv</code>	1801
<code>LWR@displaymathnormal (environ- ment)</code>	12011	<code>\LWR@formatting</code>	1730
<code>LWR@displaymathother (environment)</code>	12014	<code>LWR@foundmrowcell (boolean)</code>	433
<code>\LWR@docdashline</code>	9497	<code>\LWR@fourthoffive</code>	973
<code>\LWR@docmidrule</code>	9481	<code>\LWR@fourthoffour</code>	973
<code>\LWR@doequation</code>	12132	<code>LWR@freezethisautoid (boolean)</code>	506
<code>\LWR@doindexentry</code>	11320	<code>\LWR@futurenonspaclet</code>	8740
<code>\LWR@doindexentrysub</code>	11318	<code>\LWR@FVstyle</code>	56
<code>\LWR@doindexentrysubsub</code>	11307	<code>\LWR@getexparray</code>	5954
<code>LWR@doingapar (boolean)</code>	354	<code>\LWR@getmynexttoken</code>	8757
<code>LWR@doingcmidrule (boolean)</code>	433	<code>LWR@glrbox (environment)</code>	1004
<code>LWR@doingparhooks (boolean)</code>	354	<code>\LWR@gsavebox</code>	990
<code>LWR@doingstartpars (boolean)</code>	354	<code>LWR@hdashedlines (counter)</code>	433
<code>LWR@doingtbrule (boolean)</code>	433	<code>\LWR@heavyrulewidth (length)</code>	459
<code>\LWR@domulticolumn</code>	9830	<code>\LWR@hidelatexequation</code>	12090
<code>LWR@doubleddollar</code>	11891	<code>LWR@hlines (counter)</code>	433
<code>LWR@dynamicmath (boolean)</code>	334	<code>\LWR@hook@processingtags</code>	6267
<code>\LWR@earlyclassloadnever</code>	104	<code>\LWR@href</code>	10626
<code>\LWR@earlyloadnever</code>	99	<code>\LWR@HTML@caption@begin</code>	10843
<code>LWR@emptyatbang (boolean)</code>	434	<code>\LWR@HTML@caption@end</code>	10854
<code>\LWR@endfloatalignment</code>	10799	<code>\LWR@HTML@ref</code>	10526
<code>\LWR@endhideamsmath</code>	12264	<code>\LWR@htmlblockcomment</code>	6451
<code>\LWR@endofline</code>	13558	<code>\LWR@htmlblocktag</code>	6453
<code>\LWR@ensuredoingapar</code>	6635	<code>\LWR@HTMLcline</code>	10185
<code>LWR@equationother (environment)</code>	12027	<code>\LWR@htmlclosecomment</code>	6422
<code>\LWR@equationtag</code>	12364	<code>\LWR@htmlcomment</code>	6439
<code>LWR@excludacomment</code>	1250	<code>\LWR@htmldivclass</code>	6494
<code>LWR@exitingtabular (boolean)</code>	434	<code>\LWR@htmldivclassend</code>	6499
<code>\LWR@expandableformatted</code>	1786	<code>\LWR@html element</code>	6510
		<code>\LWR@html elementclass</code>	6478
		<code>\LWR@html elementclassend</code>	6486

<code>\LWR@html elementclassline</code>	6502	<code>\LWR@linkmediacatcodes</code>	10593
<code>\LWR@html elementend</code>	6513	<code>LWR@Lpage (counter)</code>	559
<code>LWR@htmlfilenumber (counter)</code>	337	<code>\LWR@listitem</code>	8598
<code>\LWR@htmlfileref</code>	10387	<code>\LWR@listof</code>	11015
<code>\LWR@HTMLhline</code>	10166	<code>\LWR@loadafter</code>	21
<code>\LWR@HTMLLatexCmd</code>	2131	<code>\LWR@loadbefore</code>	56
<code>\LWR@htmlmulticolumn</code>	9898	<code>\LWR@loadnever</code>	73
<code>\LWR@htmlopencomment</code>	6422	<code>\LWR@longtabledatacaptiontag</code>	9907
<code>\LWR@htmlrefsectionfilename</code>	6100	<code>\LWR@lookforpackagename</code>	1499
<code>\LWR@HTMLsanitizedetokenized</code>	7211	<code>\LWR@Lwarpconfversion</code>	2080
<code>\LWR@HTMLsanitizeexpanded</code>	7221	<code>\LWR@LwarpEnd</code>	8016, 13830
<code>\LWR@htmlsectionfilename</code>	6060	<code>\LWR@LwarpStart</code>	7928, 13830
<code>LWR@htmlseqfilenumber (counter)</code>	337	<code>\LWR@maketitlesetup</code>	34, 8192
<code>\LWR@htmlspan</code>	6399	<code>LWR@MathJax@silentquotes (boolean)</code>	377
<code>\LWR@htmlspanclass</code>	6407	<code>\LWR@mathjaxfilename</code>	6795
<code>\LWR@htmltag</code>	6419	<code>\LWR@mathjaxwarn</code>	14003
<code>\LWR@htmltagc</code>	6327	<code>LWR@mathmacro (boolean)</code>	333
<code>\LWR@hyperindexref@comma</code>	11350	<code>LWR@maxfields@ (counter)</code>	639
<code>\LWR@hyperindexref@comma</code>	11343	<code>\LWR@maybe@orignewpage</code>	983
<code>\LWR@hyperindexref@range</code>	11355	<code>\LWR@maybenewtablerow</code>	9301
<code>\LWR@hyperindexrefnullified</code>	11324	<code>\LWR@maybeprintpendingfootnotes</code>	6926
<code>\LWR@hyperindexrefsub</code>	11358	<code>\LWR@maybetocdata</code>	11067
<code>\LWR@hyperindexrefsubtwo</code>	11365	<code>LWR@midrulecounter (counter)</code>	436
<code>LWR@in@multirow@par (boolean)</code>	354	<code>LWR@midrules</code>	459
<code>\LWR@includecomment</code>	1250	<code>LWR@minipage@depth (counter)</code>	582
<code>\LWR@indentHTML</code>	6321	<code>LWR@minipagefullwidth (boolean)</code>	582
<code>\LWR@indentHTMLtwo</code>	6324	<code>\LWR@minipageheight (length)</code>	581
<code>\LWR@indexitem</code>	11150	<code>\LWR@minipagestartpars</code>	13565
<code>\LWR@indexnameref</code>	11278	<code>\LWR@minipagestoppars</code>	13568
<code>\LWR@indexnameref@anonref</code>	11219	<code>LWR@minipagethispar (boolean)</code>	582
<code>\LWR@indexnameref@cref</code>	11245	<code>\LWR@minipagewidth (length)</code>	581
<code>\LWR@indexnameref@crefnameref</code>	11262	<code>\LWR@modifycolumn type</code>	9149
<code>\LWR@indexnameref@ref</code>	11224	<code>LWR@mpfootnote@store (counter)</code>	582
<code>\LWR@indexnameref@refnameref</code>	11233	<code>\LWR@multirowborder</code>	3
<code>\LWR@indexsubitem</code>	11154	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@indexsubsubitem</code>	11158	<code>\LWR@mynexttoken</code>	8739
<code>LWR@indisplaymathimage (boolean)</code>	534	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@infoprocessingmathjax</code>	7278	<code>\LWR@mynexttoken</code>	8739
<code>LWR@insidemathcomment (boolean)</code>	534	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@instertatbangcols</code>	8812	<code>\LWR@mynexttoken</code>	8739
<code>LWR@intabularmetadata (boolean)</code>	434	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@isolate</code>	959	<code>\LWR@mynexttoken</code>	8739
<code>LWR@isstartingequation (boolean)</code>	560	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@itemizeitem</code>	8638	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@label@createtag</code>	10434	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@label@inmathcomment</code>	10420	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@label@subcreatetag</code>	10416	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@lateximage@oneimage</code>	12400	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@lateximage@oneimageb</code>	12391	<code>\LWR@mynexttoken</code>	8739
<code>LWR@lateximage@depth (counter)</code>	559	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@lateximage@depthref</code>	10390	<code>\LWR@mynexttoken</code>	8739
<code>LWR@lateximage@number (counter)</code>	559	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@lateximage@numberref</code>	10393	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@lateximage@files</code>	1646	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@latexmkcmd</code>	2107	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@latexmkdvipdfm</code>	2112	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@latexmkvar</code>	2101	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@LetLtxMacros</code>	1027	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@lightrulewidth (length)</code>	459	<code>\LWR@mynexttoken</code>	8739
<code>\LWR@linkcatcodes</code>	10585	<code>\LWR@mynexttoken</code>	8739
		<code>\LWR@nameref</code>	10378
		<code>LWR@nestspan (environment)</code>	6353
		<code>\LWR@new@label</code>	10463
		<code>\LWR@newautoidanchor</code>	10778
		<code>\LWR@newautopagelabel</code>	6993
		<code>\LWR@newhtmlfile</code>	7392
		<code>LWR@nextautoid (counter)</code>	508
		<code>LWR@nextautopage (counter)</code>	508
		<code>LWR@nextequation (counter)</code>	547
		<code>\LWR@nolinkurl</code>	10638
		<code>\LWR@notltjloadafter</code>	43
		<code>\LWR@notmemoirloadafter</code>	40
		<code>\LWR@null@newautopagelabel</code>	7004
		<code>\LWR@nullfonts</code>	11470
		<code>\LWR@nullifycomment</code>	1467
		<code>\LWR@nullifyfootnotes</code>	6945
		<code>\LWR@nullifyNoAutoSpacing</code>	10191
		<code>\LWR@nulllistfills</code>	8607
		<code>\LWR@openparagraph</code>	6635
		<code>LWR@opttablecol (boolean)</code>	434
		<code>\LWR@orig@setBold</code>	11625
		<code>\LWR@orig@unsetBold</code>	11626
		<code>\LWR@orig@colspec</code>	8795
		<code>LWR@orig@mathjax (boolean)</code>	227

<code>\LWR@overline</code>	13461	<code>\LWR@ruleHTMLcolor</code>	9295
<code>\LWR@parseaftercolumn</code>	9061	<code>\LWR@sanitize</code>	1152
<code>\LWR@parseatcolumn</code>	8961	<code>\LWR@sanitized</code>	1151
<code>\LWR@parsebangcolumn</code>	8991	<code>\LWR@secondoffive</code>	973
<code>\LWR@parsebarcolumn</code>	9074	<code>\LWR@section</code>	7545
<code>\LWR@parsebeforecolumn</code>	9040	<code>\LWR@sectionnumber</code>	7518
<code>\LWR@parsecoloncolumn</code>	9099	<code>\LWR@select@html@hspace</code>	13585
<code>\LWR@parsedrequirepackagenames</code>	1466	<code>\LWR@select@html@nohspace</code>	13616
<code>\LWR@parsenormalcolumn</code>	9123	<code>\LWR@select@print@hspace</code>	13619
<code>\LWR@parsesemicoloncolumn</code>	9120	<code>\LWR@setcurrentfont</code>	11628
<code>\LWR@parsestarcolumn</code>	9140	<code>\LWR@setexparray</code>	5940
<code>\LWR@parsetablecols</code>	9223	<code>\LWR@setlatestname</code>	10364
<code>\LWR@patcherror</code>	942	<code>\LWR@setOSWindows</code>	1066
<code>\LWR@patchlists</code>	8687	<code>\LWR@setref</code>	10372
<code>\LWR@pdfencoding</code>	845	<code>\LWR@setseqfilelabel (boolean)</code>	337
<code>\LWR@phantomsection</code>	13692	<code>\LWR@setvirtualpage (environment)</code>	12815
<code>\LWR@popclose</code>	5899	<code>\LWR@shellescapecmd</code>	2081
<code>\LWR@PreloadedPackage</code>	12623	<code>\LWR@sidetoc</code>	11041
<code>\LWR@prevFileDepth (counter)</code>	388	<code>\LWR@simplifycustom</code>	7030
<code>\LWR@previousautopagelabel (counter)</code>	371	<code>\LWR@simplifyname</code>	7019
<code>\LWR@printatbang</code>	9344	<code>\LWR@singledollar</code>	11934
<code>\LWR@printbartag</code>	9334	<code>\LWR@singledollarmeasure</code>	11700
<code>\LWR@printchaptername</code>	7542	<code>\LWR@skipatbang (boolean)</code>	433
<code>\LWR@printcloselist</code>	8505	<code>\LWR@skippingmcolrowcell (boolean)</code>	433
<code>\LWR@PrintLatexCmd</code>	2131	<code>\LWR@skippingmrowcell (boolean)</code>	433
<code>\LWR@printlength</code>	1450	<code>\LWR@spandepth (counter)</code>	354
<code>\LWR@printmccoldata</code>	9766	<code>\LWR@spanwarnformat</code>	6337
<code>\LWR@printmccoldata@normal</code>	9756	<code>\LWR@spanwarninvalid</code>	6345
<code>\LWR@printmccoldata@other</code>	9746	<code>\LWR@spewingnotes (boolean)</code>	365
<code>\LWR@printmccoldata@paragraph</code>	9760	<code>\LWR@starredlongtable (boolean)</code>	436
<code>\LWR@printmccoldata@skip</code>	9752	<code>\LWR@startedrow (boolean)</code>	432
<code>\LWR@printmccoltype</code>	9737	<code>\LWR@starting@fancybox (boolean)</code>	354
<code>\LWR@printmccoltype@colon</code>	9731	<code>\LWR@startingequation (counter)</code>	560
<code>\LWR@printmccoltype@ignore</code>	9725	<code>\LWR@startingequationtag</code>	12363
<code>\LWR@printmccoltype@normal</code>	9721	<code>\LWR@startnewdepth</code>	7531
<code>\LWR@printmccoltype@semicolon</code>	9736	<code>\LWR@startpars</code>	6721
<code>\LWR@printmccoltype@vertbar</code>	9726	<code>\LWR@startref</code>	10489
<code>\LWR@printopenlist</code>	8506	<code>\LWR@stoppars</code>	6736
<code>\LWR@printpendingfootnotes</code>	6923	<code>\LWR@stripperperiod</code>	10363
<code>\LWR@printpendingmpfootnotes</code>	6935	<code>\LWR@strresult</code>	8793
<code>\LWR@printpercentlength</code>	935	<code>\LWR@subaddcmidruletrim</code>	9515
<code>\LWR@printthetitle</code>	8144	<code>\LWR@subaddtabularcellcolor</code>	9696
<code>\LWR@providelength</code>	931	<code>\LWR@subcdashline</code>	9484
<code>\LWR@ProvidesPackageDrop</code>	1636	<code>\LWR@subcmidrule</code>	9466
<code>\LWR@ProvidesPackageDropA</code>	1621	<code>\LWR@subcustomizedmathjax</code>	7246
<code>\LWR@ProvidesPackageDropB</code>	1630	<code>\LWR@subhtml@elementclass</code>	6458
<code>\LWR@ProvidesPackagePass</code>	1590	<code>\LWR@subHTML@sanitize</code>	7191
<code>\LWR@pushclose</code>	5851	<code>\LWR@subhyperref</code>	10601
<code>\LWR@pushhoneyclose</code>	7527	<code>\LWR@subhyperrefclass</code>	10615
<code>\LWR@quickfile</code>	1643	<code>\LWR@subhyperref@text</code>	10610
<code>\LWR@refwithsection</code>	10535	<code>\LWR@subinlineimage</code>	10664
<code>\LWR@remembertag</code>	12368	<code>\LWR@subnewref</code>	10520
<code>\LWR@replacestrings</code>	7170	<code>\LWR@subsingledollar</code>	11831
<code>\LWR@requesttoc</code>	8009	<code>\LWR@subsingledollarsvg</code>	11746
<code>\LWR@requirepackagenames</code>	1465	<code>\LWR@subtableofcontents</code>	10937
<code>\LWR@restoreMathJax@formatting</code>	11417	<code>\LWR@subtabularhtml@columns</code>	9978
<code>\LWR@restoreorigaccents</code>	2029	<code>\LWR@syncmathjax</code>	12078
<code>\LWR@restoreorigformatting</code>	11418	<code>\LWR@syncnotenames</code>	12195
<code>\LWR@restoreoriglists</code>	8715	<code>\LWR@syncnotennumbers</code>	12189
<code>\LWR@rowHTMLcolor</code>	9293	<code>\LWR@syncnotenotename</code>	12190

<code>\LWR@synconenotenummer</code>	12184	<code>\LWR@xcolorrowHTMLcolor</code>	9291
<code>LWR@tablecolspec</code>	434	<code>LWR@xfakebold (boolean)</code>	534
<code>LWR@tablecolspecindex (counter)</code>	435	<code>\LWR@index@modifyentry</code>	11162
<code>LWR@tablecolspecwidth (counter)</code>	435	<code>LWR@index@tricked (boolean)</code>	521
<code>\LWR@tabledatacolumntag</code>	10067	<code>LWRcreateLwarpmk (environment)</code>	1315
<code>\LWR@tabledatasinglecolumntag</code>	9383	<code>\LWRopquote</code>	1061
<code>LWR@tableLaTeXcolindex (counter)</code>	435	<code>\LWRopseq</code>	1062
<code>LWR@tableparcell (boolean)</code>	433	<code>\LWRPrintStack</code>	6179
<code>LWR@tabletotalLaTeXcols (counter)</code>	435	<code>\LWRsetnextfloat</code>	10829
<code>LWR@tabletotalLaTeXcolsnext (counter)</code>	435	<code>\LWRtexttitlecase</code>	1022
<code>\LWR@tabular@warpprintonly</code>	10187	<code>lyluatex (package)</code>	911
<code>LWR@tabularcelladded (boolean)</code>	433	<code>\LyX</code>	13826
<code>LWR@tabularDepth (counter)</code>	434		
<code>\LWR@tabularendofline</code>	8930	M	
<code>\LWR@tabularfinishrow</code>	8881	<code>Mac OS (program)</code>	115, 225
<code>\LWR@tabularhtmlcolumns</code>	9988	<code>\macrotoCSname</code>	1016
<code>\LWR@tabularleftedge</code>	9374	<code>Madcap (program)</code>	73
<code>LWR@tabularmutemods (boolean)</code>	434	<code>magaz (package)</code>	913
<code>LWR@tabularpardepth (counter)</code>	434	<code>\mainmatter</code>	7508
<code>\LWR@tdaddstyle</code>	9502	<code>make (program)</code>	176
<code>\LWR@tdendstyles</code>	9508	<code>\makebox</code>	12978
<code>\LWR@tdstartstyles</code>	9501	<code>makeidx (package)</code>	146, 914, 1175, 1176
<code>\LWR@tempcolor</code>	13467	<code>\MakeIndex</code>	13804
<code>\LWR@tempcolorthree</code>	13467	<code>makeindex (option)</code>	104, 230
<code>\LWR@tempcolortwo</code>	13467	<code>makeindex (program)</code>	134, 143
<code>\LWR@tempheight (length)</code>	604	<code>makeindexStyle (option)</code>	104, 144, 228
<code>\LWR@tempraise (length)</code>	604	<code>\makeLabel</code>	423
<code>\LWR@tempwidth (length)</code>	604	<code>\maketitle</code>	48, 117, 8215
<code>\LWR@textcurrentcolor</code>	25, 13473	<code>manyfoot (package)</code>	914
<code>\LWR@textcurrentfont</code>	13303, 13479	<code>marginal (package)</code>	916
<code>\LWR@thirdoffive</code>	973	<code>marginfit (package)</code>	916
<code>\LWR@thirdofthree</code>	973	<code>marginfix (package)</code>	916
<code>\LWR@ThisAltText</code>	11612	<code>marginnote (package)</code>	917
<code>LWR@thisautoid (counter)</code>	505	<code>\marginpar</code>	122, 369, 6951
<code>LWR@thisautoidWP (counter)</code>	506	<code>\marginparBlock</code>	122, 369, 6963, 6985
<code>\LWR@thiscmidrulewidth (length)</code>	460	<code>\markboth</code>	6238
<code>\LWR@thiscolspec</code>	9382	<code>\markright</code>	6239
<code>\LWR@thisfilename</code>	7013	<code>marvosym (package)</code>	917
<code>\LWR@thisnewfilename</code>	7018	<code>math (environment)</code>	12010
<code>\LWR@titlingmaketitle</code>	85, 8259	<code>mathalpha (package)</code>	918
<code>\LWR@topnavigation</code>	6133	<code>mathastext (package)</code>	918
<code>\LWR@traceinfo</code>	1712	<code>mathcomp (package)</code>	919
<code>LWR@tracinglwrap (boolean)</code>	249	<code>mathdesign (package)</code>	920
<code>LWR@trimlrules</code>	459	<code>mathdots (package)</code>	921
<code>LWR@trimrrules</code>	459	<code>mathfixs (package)</code>	922
<code>\LWR@unknownengine</code>	2093	<code>\MathImageAltText</code>	112, 11611
<code>LWR@unknownmathsize (boolean)</code>	537	<code>MathJax (program)</code>	148, 150
<code>\LWR@url</code>	10651	<code>MathJax (program) [requirement]</code>	76
<code>LWR@usedmultirow (boolean)</code>	433	<code>mathjax (boolean)</code>	227
<code>LWR@validtablecol (boolean)</code>	434	<code>mathjax (option)</code>	102, 228
<code>LWR@verbtags (boolean)</code>	418	<code>\MathJaxFilename</code>	110, 6796
<code>LWR@virtualpagedepth (counter)</code>	581	<code>mathpazo (package)</code>	922
<code>\LWR@vspace</code>	13623	<code>mathptmx (package)</code>	923
<code>LWR@warnbaselinemarker (boolean)</code>	536	<code>mathspec (package)</code>	923
<code>LWR@warnedcustomizemathjax (boolean)</code>	379	<code>mathsvg (option)</code>	102, 228
<code>\LWR@WPcell</code>	9574	<code>mathtools (package)</code>	153, 925
<code>\LWR@write@lwarplabel</code>	10396	<code>mattens (package)</code>	928
<code>\LWR@writeconf</code>	2233	<code>maybemath (package)</code>	930
		<code>\mbox</code>	12951
		<code>mcaption (package)</code>	931

<code>\mcolrowcell</code>	10145
<code>mdframed</code> (package)	125, 931
<code>\mdseries</code>	13343
<code>mdwmath</code> (package)	939
<code>media9</code> (package)	160, 940
<code>memhfixc</code> (package)	942
<code>memoir</code> (class)	168, 170, 1203
<code>menukeys</code> (package)	942
<code>metalogo</code> (package)	943
<code>metalogox</code> (package)	943
<code>mhchem</code> (package)	944
<code>microtype</code> (package)	236, 947
<code>midfloat</code> (package)	947
<code>midpage</code> (package)	948
<code>\MiKTeX</code>	13824
<code>minibox</code> (package)	948
<code>minipage</code> (environment)	12844
<code>\minipagefullwidth</code>	12829
<code>minitoc</code> (package)	949
<code>minted</code> (package)	949
<code>mismatch</code> (package)	950
<code>mleftright</code> (package)	953
<code>mmap</code> (package)	101
<code>morefloats</code> (package)	954
<code>moreverb</code> (package)	954
<code>movie15</code> (package)	160, 955
<code>mparhack</code> (package)	956
<code>\mrowcell</code>	10142
<code>MS-Windows</code> (program)	115, 225
<code>multibib</code> (package)	957
<code>multicap</code> (package)	957
<code>multicol</code> (package)	957
<code>multicolrule</code> (package)	958
<code>\multicolumnrow</code>	48, 10011
<code>multimedia</code> (package)	160, 959
<code>multiobjective</code> (package)	960
<code>\multirow</code>	962
<code>multirow</code> (package)	960
<code>multitoc</code> (package)	964
<code>multiline</code> (environment)	82
<code>multiline*</code> (environment)	85
<code>musicography</code> (package)	965
<code>mwe</code> (package)	967
N	
<code>[nameauth]</code> :	
<code>\@nameauth@Hook</code> (hook)	968
<code>nameauth</code> (package)	968
<code>\Nameref</code>	10579
<code>\nameref</code>	10570
<code>nameref</code> (package)	969
<code>natbib</code> (package)	969
<code>nccfancyhdr</code> (package)	970
<code>nccfoots</code> (package)	971
<code>nccmath</code> (package)	971
<code>needspace</code> (package)	973
<code>newclude</code> (package)	170
<code>\NewEnvironmentCopy</code>	955
<code>\newfloat</code>	5
<code>newfloat</code> (package)	240
<code>\newline</code>	13556
<code>\newpage</code>	13553
<code>newpxmath</code> (package)	973
<code>\newtheorem</code>	421
<code>newtxmath</code> (package)	974
<code>newtxsf</code> (package)	975
<code>newunicodechar</code> (package)	101
<code>nextpage</code> (package)	976
<code>nfssexct-cfr</code> (package)	976
<code>nicefrac</code> (package)	155, 982
<code>niceframe</code> (package)	983
<code>nicematrix</code> (package)	983
<code>\noalign</code>	10155
<code>\nohyperpage</code>	11380
<code>noitcrl</code> (package)	986
<code>nolbreaks</code> (package)	986
<code>\nolinebreak</code>	13627
<code>nomencl</code> (package)	134, 986
<code>nonfloat</code> (package)	987
<code>nonumonpart</code> (package)	987
<code>\nopagebreak</code>	13631
<code>\nopagecolor</code>	80
<code>nopageno</code> (package)	987
<code>\normalcolor</code>	9
<code>\normalfont</code>	13425
<code>\normalmarginpar</code>	6982
<code>notes</code> (package)	987
<code>notespages</code> (package)	988
<code>nowidow</code> (package)	988
<code>ntheorem</code> (package)	153, 989
<code>\numberline</code>	11062
<code>numindex</code> (option) [tocbibind] .	147, 1176
O	
<code>octave</code> (package)	1000
<code>OpenOffice</code> (program)	73
<code>option:</code>	
<code>--shell-escape</code>	100
<code>[lwarpmk]</code> :	
<code>htmlglossary</code>	133, 824
<code>printglossary</code>	133, 824
<code>[tocbibind]</code> :	
<code>numindex</code>	147, 1176
<code>[tocloft]</code> :	
<code>titles</code>	131
<code>BaseJobname</code>	106, 228
<code>dvipdfm</code>	102, 231
<code>dvipdfmx</code>	102, 231
<code>dvips</code>	102, 231
<code>GlossaryCmd</code>	106, 133, 230, 824
<code>HomeHTMLFilename</code>	102, 229
<code>HTMLFilename</code>	102, 229
<code>HTMLIndexCmd</code>	105, 230
<code>HTMLLatexCmd</code>	104, 173, 230
<code>ImagesDirectory</code>	102, 228
<code>ImagesName</code>	102, 228
<code>IndexRef</code>	105, 230
<code>latexmk</code>	102, 230
<code>LatexmkIndexCmd</code>	105, 230
<code>lwarpmk</code>	106, 229, 311

makeindex	104, 230	axodraw2	661
makeindexStyle	104, 144, 228	babel	171
mathjax	102, 228	backaur	661
mathsvg	102, 228	backref	662
OSWindows	106, 115, 225, 229	balance	662
pdftotextEnc	106, 229	bbding	663
PrintIndexCmd	104, 230	beamerarticle	667
PrintLatexCmd	104, 173, 230	biblatex	669
warpHTML	106, 227, 228	bibunits	673
warpprint	106, 227	bigdelim	166, 673
xindex	104, 230	bigfoot	675
xindexConfig	104, 145, 229	bigstrut	675
xindy	104, 230	bitpattern	676
xindyCodepage	104, 229	blowup	676
xindyLanguage	104, 229	bm	676
xindyStyle	104, 145, 228	booklet	677
orcidlink (package)	1001	bookmark	677
\OSPathSymbol	1065	booktabs	678
OSWindows (option)	106, 115, 225, 229	bophook	680
overpic (package)	159, 1002	bounddvi	680
P			
package:		boxedminipage	680
2in1	621	boxedminipage2e	681
2up	621	braket	681
a4	621	breakurl	681
a4wide	621	breqn	682
a5comb	622	bsheaders	683
abstract	131, 622	bussproofs	683
academicons	624	bxpapersize	684
accents	625	bytefield	684
accessibility	626	calc	238
accsupp	626	cancel	684
acro	627	canoniclayout	685
acronym	629	capt-of	510
addlines	633	caption	166, 510, 685
adjmulticol	632	caption3	687
afterpage	633	cases	690
algorithm2e	633	ccicons	690
algorithmicx	166, 637	centerlastline	691
alltt	638	centernot	691
amscdx	638	changebar	691
amsmath	639	changelayout	692
amsthm	643	changegepage	692
anonchap	647	changes	693
ansize	647	chappg	698
appendix	132, 648	chapterbib	698
ar	648	chemfig	698
arabicfront	650	chemformula	700
array	650	chemgreek	705
arydshln	651	chemmacros	705
asymptote	159, 653	chemnum	725
atbegshi	653	chkfloat	726
attachfile	654	chngepage	726
attachfile2	655	cite	727
authblk	131, 657	citeref	727
autobreak	658	CJK	727
autonum	658	CJKutf8	728
awesomebox	659	classicthesis	728
axessibility	660	cleveref	128, 729
		clrdblpg	732
		cm-super	100

cmap	101	expl3	238
cmbright	732	extrarrows	772
cmdtrack	733	extramarks	772
colonequals	733	fancybox	124, 773
color	158, 734	fancyhdr	778
colortbl	165, 734	fancypar	779
comment	233	fancyref	780
common-mathjax-siunitx	1091	fancytabs	780
continue	736	fancyvrb	781
copyrightbox	736	fbox	787
crop	737	fewerfloatpages	790
ctable	737	figcaps	790
cuted	740	figsize	790
cutwin	740	filecontents	239
dblfloatfix	741	fitbox	791
dblfnote	741	fix2col	791
dcolumn	741	fixmath	791
decimal	742	fixme	171, 792
decorule	742	fixmetodonotes	793
dejavu	100	flafter	794
diagbox	742	flippdf	794
dingbat	744	float	166, 794
ditaa	177	floatflt	796
DotArrow	745	floatpag	797
dotlessi	745	floatrow	167, 797
dprogress	746	fltrace	802
draftcopy	746	flushend	802
draftfigure	746	fnbreak	802
draftwatermark	747	fncychap	803
drftcite	747	fnlineno	803
easy-todo	747	fnpara	803
ebook	748	fnpos	804
econometrics	749	fontawesome	804
ed	751	fontawesome5	805
ellipsis	752	fontaxes	806
embrac	752	fontenc	101, 806
emptypage	753	fontspec	100, 235
endfloat	753	footmisc	807
endheads	753	footnote	808
endnotes	132, 754	footnotebackref	809
engtlc	755	footnotehyper	810
enotez	759	footnoterange	810
enumerate	761	footnpag	810
enumitem	762	foreign	810
environ	240	forest	811
epigraph	762	fouridx	811
epsf	763	fourier	812
epsfig	763	framed	813
epstopdf	158, 764	froufrou	815
epstopdf-base	764	ftcap	816
eqlist	765	ftnright	816
eqparbox	765	fullminipage	817
errata	766	fullpage	817
eso-pic	768	fullwidth	817
esvect	768	fvextra	817
etoc	768	fwlw	820
etoolbox	201	gensymb	821
eurosym	771	gentombow	821
everypage	771	geometry	236, 821
everyshi	771	getttitlestring	239

ghsystem	822	lltjp-tascmac	901
gindex	135, 823	lmodern	100, 101
gloss	132, 823	longtable	164, 901
glossaries	133, 824	lpic	904
gmeometric	826	lscap	904
graphics	155, 826	ltablex	905
graphicx	155, 838	ltxcaption	905
grffile	157, 838	ltxgrid	905
grid	839	ltxtable	906
grid-system	839	lua-check-hyphen	906
gridset	839	lua-visual-debug	906
hang	840	luacolor	906
hanging	841	luamplib	907
hepunits	842	luatexko	907
hhline	843	luatodonotes	171, 909
hhtensor	844	luavlna	911
hypbmsc	844	lwarp	102
hypcap	844	lwarp-common-mathjax-letters	1272
hypdestopt	845	lwarp-common-mathjax-newpctxmath	1278
hypernat	845	lwarp-common-mathjax-nonunicode	1285
hyperref	128, 499, 845	lwarp-common-mathjax-overlaysymbols	1288
hyperxmp	855	lwarp-common-multimedia	1267
hyphenat	856	lwarp-patch-komascript	1238
idxlayout	857	lwarp-patch-memoir	1240
ifoddpag	857	lyluatex	911
ifplatform	201	magaz	913
imakeidx	858	makeidx	146, 914, 1175, 1176
impnatty	862	manyfoot	914
indentfirst	360	marginal	916
index	862	marginfit	916
inputenc	101	marginfix	916
inputenx	101	marginnote	917
inputtrc	863	marvosym	917
intopdf	864	mathalpha	918
isomath	864	mathastext	918
isotope	864	mathcomp	919
jurabib	866	mathdesign	920
karnaugh-map	867	mathdots	921
keyfloat	168, 870	mathfixs	922
keystroke	875	mathpazo	922
kotex	172	mathptmx	923
kpfonts	876	mathspec	923
kpfonts-otf	878	mathtools	153, 925
kvoptions	227	mattens	928
layaureo	880	maybemath	930
layout	880	mcaption	931
layouts	880	mdframed	125, 931
leading	883	mdwmath	939
leftidx	883	media9	160, 940
letltxmacro	201	memhfixc	942
letterspace	883	menukeys	942
lettrine	884	metalogo	943
libertinustlmath	884	metalogo	943
lineno	890	mhchem	944
lips	892	microtype	236, 947
lipsum	893	midfloat	947
listings	893	midpage	948
listliketab	899		
lltjext	899		
lltjp-siunitx	900		

minibox	948	pbox	1010
minitoc	949	pdfcol	1010
minted	949	pdfcolfoot	1011
mismath	950	pdfcolmk	1011
mleftright	953	pdfcolparallel	1011
mmap	101	pdfcolparcolumns	1012
morefloats	954	pdfcomment	1012
moreverb	954	pdfcrypt	1013
movie15	160, 955	pdfscape	1013
mparhack	956	pdfmarginpar	1013
multibib	957	pdfpages	1014
multicap	957	pdfprivacy	1016
multicol	957	pdfrender	1016
multicolrule	958	pdfsync	1016
multimedia	160, 959	pdftricks	158, 1017
multiobjective	960	pdfx	1017
multirow	960	perltex	175
multitoc	964	perpage	1018
musicography	965	pfnote	1019
mwe	967	phfqit	1019
nameauth	968	physics	155, 1020
nameref	969	physunits	1020
natbib	969	picinpar	1022
nccfancyhdr	970	pifont	1023
nccfoots	971	pinlabel	1024
nccmath	971	placeins	1024
needspace	973	plarydshln	1024
newclude	170	plext	1024
newfloat	240	plextarydshln	1025
newpxmath	973	plextcolortbl	1026
newtxmath	974	plimsoll	1026
newtxsf	975	polyglossia	171
newunicodechar	101	prelim2e	1026
nextpage	976	prettyref	1027
nfssext-cfr	976	preview	1027
nicefrac	155, 982	printlen	240
niceframe	983	psfrag	159, 1027
nicematrix	983	psfragx	1028
noitcrul	986	pst-eps	1028
nolbreaks	986	pstool	159, 1029
nomencl	134, 986	pstricks	158, 1029
nonfloat	987	pxatbegshi	1030
nonumonpart	987	pxeveryshi	1030
nopageno	987	pxfonts	1030
notes	987	pxftnright	1030
notespages	988	pxjahyper	1031
nowidow	988	pythontex	175
ntheorem	153, 989	quotchap	1031
octave	1000	quoting	1032
orcidlink	1001	ragged2e	1032
overpic	159, 1002	realscripts	1033
pagegrid	1002	refcheck	1036
pagenote	132, 1002	refcount	240
pagesel	1003	register	1036
paralist	1003	reysize	122, 1037
parallel	1004	repeatindex	1038
parcolumns	1005	repltext	1039
parnotes	1007	resizegather	1039
parskip	1009	returntograd	1040
pbalance	1010	rlepsz	1040

rmathbr	1040	subfig	167, 1126
rmpage	1041	subfigure	1130
romanbar	1041	subsubscripts	1131
romanbarpagenumber	1041	supertabular	165, 1132
rotating	1041	svg	1133
rotfloat	1042	swfigure	1134
rterface	176	sympytex	175, 1134
rviewport	1043	syntonly	1135
sagetex	174	tabfigures	1135
savetrees	1043	tablefootnote	1135
scaleft	1043	tabls	1136
scalereel	1044	tabularx	1136
schemata	1044	tabulary	1137
scrextend	1045	tagpdf	1137
scrhack	1048	tascmac	1140
scrlayer	1049	tcolorbox	126, 1142
scrlayer-notecolumn	1050	tensor	1147
scrlayer-scrpage	1051	termcal	1148
scrpage2	1052	textarea	1149
section	1053	textcomp	101, 121, 1149
sectionbreak	1053	textfit	1153
sectsty	1054	textpos	1153
selectp	1054	theorem	1154
semantic-markup	1055	thinsp	1157
seqsplit	1056	thm-listof	1158
setspace	1057	thm-restate	1158
shadethm	1058	thmbox	1159
shadow	1058	thmtools	1160
shapepar	1058	threadcol	1160
showidx	1059	threeparttable	1160
showkeys	1059	threeparttablex	165, 1161
showlabels	1059	thumb	1162
showtags	1060	thumbs	1162
shuffle	1060	tikz	157, 1163
sidecap	1061	tikz-image-labels	1164
sidenotes	1061	titlesp	1164
simplebnf	1063	titleref	1167
SIunits	1064	titlesec	1167
siunitx	153, 571, 1072	titletoc	1169
siunitx-v2	1080	titling	131, 1171
skmath	1100	tocbasic	1175
slantsc	1105	tocbibind	146, 147, 1175, 1176
slashed	1105	tocdata	1177
soul	1106	tocenter	1178
soulpos	1107	tocloft	131, 147, 647, 1178, 1179
soulutf8	1108	tocstyle	1184
splitbib	1108	todo	1184
splitidx	1109	todonotes	171, 1185
srcltx	1110	topcapt	1187
srctex	1111	tram	1187
stabular	1111	transparent	1188
stackengine	1112	trimclip	1188
stackrel	1113	trivfloat	166, 1188
statex2	1114	truncate	1189
statistics	1118	turnthepage	1190
statmath	1123	twoup	1190
steinmetz	1124	txfonts	1190
stfloats	1125	txgreek	1191
struktex	1125	typearea	1191
subcaption	166, 1126	typicons	1192

ulem	1192	pagesel (package)	1003
umoline	1194	\pagestyle	6236
underscore	1194	Pandoc (program)	73
unicode-math	1195	para/begin (hook) [LaTeX]	358
units	155, 1199	para/end (hook) [LaTeX]	358
unitsdef	1200	\paragraph	7786
upgreek	1200	paralist (package)	1003
upref	1201	parallel (package)	1004
url	128, 1201	\parbox	12942
ushort	1201	parcolumns (package)	1005
uspace	1202	parnotes (package)	1007
varioref	128, 1202	\parsemulticolumnalignment	9777
verbatim	240	parskip (package)	1009
verse	170, 1202, 1203	\part	7753
versonotes	1204	pbalance (package)	1010
vertbars	1204	pbox (package)	1010
vmargin	1205	pdfcol (package)	1010
vowel	1205	pdfcolfoot (package)	1011
vpe	1206	pdfcolmk (package)	1011
vwcol	1206	pdfcolparallel (package)	1011
wallpaper	1208	pdfcolparcolumns (package)	1012
watermark	1208	pdfcomment (package)	1012
widetable	1209	pdfcrop (program) [requirement]	76
widows-and-orphans	1209	pdfcrypt (package)	1013
witharrows	1209	pdfLaTeX (program) [requirement]	76
wrapfig	1210	pdflscape (package)	1013
wrapfig2	1212	pdfmarginpar (package)	1013
xbmks	1215	pdfpages (package)	1014
xcolor	158, 575, 1215	pdfprivacy (package)	1016
xexchangebar	1225	pdfrender (package)	1016
xellipsis	1225	pdfseparate (program) [requirement]	76, 80
xetexko	1226	pdfsync (package)	1016
xevlna	1226	pdftocairo (program)	156, 574
xfakebold	1226	pdftocairo (program) [requirement]	76, 80
xfrac	1227	pdftotext (program) [requirement]	76, 80
xifthen	240	pdftotextEnc (option)	106, 229
xltabular	1229	pdftricks (package)	158, 1017
xltxtra	1230	pdfx (package)	1017
xmpincl	1230	perl (program) [requirement]	81
xparse	238	perltex (package)	175
xpatch	201	perpage (package)	1018
xpiano	1231	pfnote (package)	1019
xpinyin	1231	phfqit (package)	1019
xr	1232	physics (package)	155, 1020
xr-hyper	1233	physunits (package)	1020
xstring	240	picinpar (package)	1022
xtab	165, 1233	picture (environment)	580, 12806
xunicode	1235	pifont (package)	1023
xurl	1236	pinlabel (package)	1024
xy	1236	placeins (package)	1024
zhlineskip	1237	plarydshln (package)	1024
zwpagelayout	1237	Plastex (program)	72
\PackageDiagramAltText	112, 11616	plext (package)	1024
\pagebreak	13628	plextarydshln (package)	1025
\pagecolor	79	plextcolortbl (package)	1026
pagegrid (package)	1002	plimsoll (package)	1026
pagenote (package)	132, 1002	\PN@parnotes@auto	6634
\pagenumbering	6244	polyglossia (package)	171
\pageref	10565		
\pagerefPageFor	10564		

<code>\postbookname</code>	7733	Pandoc	73
<code>\postchaptername</code>	7737	pdftocairo	156, 574
<code>\postpartname</code>	7735	Plastex	72
<code>\postsectionname</code>	7739	splitidx	136
<code>\prebookname</code>	7733	TeX2page	72
<code>\prechaptername</code>	7737	TeX4ht	72
<code>prelim2e</code> (package)	1026	TeXMaths	182
<code>\prepartname</code>	7735	TtH	72
<code>\presectionname</code>	7739	Unix	115, 225
<code>prettyref</code> (package)	1027	Windows	115, 225
<code>preview</code> (package)	1027	Word	73
<code>\printauthor</code>	407, 8152, 8171	xindex	135, 145
<code>\printdate</code>	407, 8163, 8173	xindy	135, 144
<code>printglossary</code> (option) [lwarpmk]	133, 824	project.css (file)	114
<code>\printindex</code>	2	project.lwarpmkconf (file)	267
<code>PrintIndexCmd</code> (option)	104, 230	psfrag (package)	159, 1027
<code>PrintLatexCmd</code> (option)	104, 173, 230	psfragx (package)	1028
<code>printlen</code> (package)	240	pst-eps (package)	1028
<code>\printthanks</code>	407, 8129	pstool (package)	159, 1029
<code>\printtitle</code>	407, 8136, 8170	pstricks (package)	158, 1029
program:		pxatbegshi (package)	1030
[requirement]:		pxeveryshi (package)	1030
LuaLaTeX	76	pxfonts (package)	1030
MathJax	76	pxftnright (package)	1030
pdfcrop	76	pxjahyper (package)	1031
pdfLaTeX	76	pythontex (package)	175
pdfseparate	76, 80		
pdftocairo	76, 80	Q	
pdftotext	76, 80	<code>\qqquad</code>	603, 13576
perl	81	<code>\quad</code>	603, 13571
XeLaTeX	76	quotation (environment)	8341
Adobe	73	quotchap (package)	1031
AsciiDoc	73	quote (environment)	8333
AsciiDoctor	73	quoting (package)	1032
Asciidoctor-LaTeX	73		
epstopdf	156, 574	R	
Flare	73	ragged2e (package)	1032
FrameMaker	73	<code>\raggedbottom</code>	6240
GELLMU	72	<code>\raggedleft</code>	12606
GladTeX	72	<code>\raggedright</code>	12612
Hevea	72	<code>\raisebox</code>	13124
htlatex	72	realscripts (package)	1033
imakeidx	138	<code>\ref</code>	10526
InDesign	73	refcheck (package)	1036
index	136	refcount (package)	240
LaTeX2HTML	72	<code>\reflectbox</code>	397
latexmk	174	register (package)	1036
LaTeXML	72	relsize (package)	122, 1037
LibreOffice	73	repeatindex (package)	1038
Linux	115, 225	repltext (package)	1039
lwarpmk	189, 311	[requirement]:	
lwarpmk epstopdf	156, 574	LuaLaTeX (program)	76
lwarpmk pdftosvg	156, 574	MathJax (program)	76
Mac OS	115, 225	pdfcrop (program)	76
Madcap	73	pdfLaTeX (program)	76
make	176	pdfseparate (program)	76, 80
makeindex	134, 143	pdftocairo (program)	76, 80
MathJax	148, 150	pdftotext (program)	76, 80
MS-Windows	115, 225	perl (program)	81
OpenOffice	73	XeLaTeX (program)	76

<code>\RequirePackage</code>	1532	<code>sidenotes</code> (package)	1061
<code>\resizebox</code>	406	<code>SideTOCDepth</code> (counter)	107, 515
<code>resizegather</code> (package)	1039	<code>\sitetocname</code>	109, 11038
<code>\ResumeTabular</code>	10056	<code>simplebnf</code> (package)	1063
<code>returntogrid</code> (package)	1040	<code>\simplechapterdelim</code>	7538
<code>\reversemarginpar</code>	6981	<code>\sishape</code>	13407
<code>\rightline</code>	12620	<code>SIunits</code> (package)	1064
<code>rlepsf</code> (package)	1040	<code>siunitx</code> (package)	153, 571, 1072
<code>rmathbr</code> (package)	1040	<code>siunitx-v2</code> (package)	1080
<code>\rmfamily</code>	13367	<code>skmath</code> (package)	1100
<code>rmpage</code> (package)	1041	<code>slantsc</code> (package)	1105
<code>romanbar</code> (package)	1041	<code>slashed</code> (package)	1105
<code>romanbarpagenumber</code> (package)	1041	<code>\sloppy</code>	6242
<code>\rotatex</code>	355	<code>\slshape</code>	13418
<code>rotating</code> (package)	1041	<code>soul</code> (package)	1106
<code>rotfloat</code> (package)	1042	<code>soulpos</code> (package)	1107
<code>\rowcolor</code>	9296	<code>soulutf8</code> (package)	1108
<code>\rownum</code>	9288	<code>\sp</code>	13444
<code>rterface</code> (package)	176	<code>splitbib</code> (package)	1108
<code>\rule</code>	120, 13635	<code>splitidx</code> (package)	1109
<code>rviewport</code> (package)	1043	<code>splitidx</code> (program)	136
S			
<code>sagetex</code> (package)	174	<code>srcltx</code> (package)	1110
<code>sample_project.css</code> (file)	114, 305	<code>srctex</code> (package)	1111
<code>savetrees</code> (package)	1043	<code>\sscshape</code>	13423
<code>\sb</code>	13445	<code>stabular</code> (package)	1111
<code>\scalebox</code>	378	<code>stackengine</code> (package)	1112
<code>scaleftnt</code> (package)	1043	<code>stackrel</code> (package)	1113
<code>scalerel</code> (package)	1044	<code>\StartDefiningMath</code>	5969
<code>schemata</code> (package)	1044	<code>\StartDefiningTabulars</code>	5959
<code>scrextend</code> (package)	1045	<code>statex2</code> (package)	1114
<code>scrhack</code> (package)	1048	<code>statistics</code> (package)	1118
<code>scrlayer</code> (package)	1049	<code>statmath</code> (package)	1123
<code>scrlayer-notecolumn</code> (package)	1050	<code>steinmetz</code> (package)	1124
<code>scrlayer-scrpage</code> (package)	1051	<code>stfloats</code> (package)	1125
<code>scrpage2</code> (package)	1052	<code>\StopDefiningMath</code>	5973
<code>\scshape</code>	13392	<code>\StopDefiningTabulars</code>	5963
<code>\section</code>	7777	<code>struktex</code> (package)	1125
<code>section</code> (package)	1053	<code>subcaption</code> (package)	166, 1126
<code>sectionbreak</code> (package)	1053	<code>subfig</code> (package)	167, 1126
<code>sectsty</code> (package)	1054	<code>subfigure</code> (package)	1130
<code>selectp</code> (package)	1054	<code>\subparagraph</code>	7789
<code>semantic-markup</code> (package)	1055	<code>\subsection</code>	7780
<code>seqsplit</code> (package)	1056	<code>\subsubsection</code>	7783
<code>\SetHTMLFileNumber</code>	6045	<code>subsupscripts</code> (package)	1131
<code>setspace</code> (package)	1057	<code>supertabular</code> (package)	165, 1132
<code>\sffamily</code>	13372	<code>svg</code> (package)	1133
<code>\sfrac</code>	1227	<code>swfigure</code> (package)	1134
<code>shadethm</code> (package)	1058	<code>sympytex</code> (package)	175, 1134
<code>shadow</code> (package)	1058	<code>syntonly</code> (package)	1135
<code>shapepar</code> (package)	1058	T	
<code>shipoout/background</code> (hook) [LaTeX]	406	<code>tabbing</code> (environment)	8462
<code>shipoout/foreground</code> (hook) [LaTeX]	406	<code>tabfigures</code> (package)	1135
<code>showidx</code> (package)	1059	<code>tablefootnote</code> (package)	1135
<code>showkeys</code> (package)	1059	<code>\tableofcontents</code>	111, 10956
<code>showlabels</code> (package)	1059	<code>tbls</code> (package)	1136
<code>showtags</code> (package)	1060	<code>tabular</code> (environment)	10204
<code>shuffle</code> (package)	1060	<code>\TabularMacro</code>	10054
<code>sidecap</code> (package)	1061	<code>tabularx</code> (package)	1136
		<code>tabulary</code> (package)	1137

tagpdf (package)	1137	\title	117, 6806
tascmac (package)	1140	titlepage (environment)	117, 8117
tcolorbox (package)	126, 1142	titleps (package)	1164
tensor (package)	1147	titleref (package)	1167
termcal (package)	1148	titles (option) [tocloft]	131
\TeX	13740	titlesec (package)	1167
TeX2page (program)	72	titletoc (package)	1169
TeX4ht (program)	72	titling (package)	131, 1171
TeXMaths (program)	182	titlingpage (environment)	14, 117
textarea (package)	1149	tocbasic (package)	1175
\textbf	13151	[tocbibind]:	
\textcolor	66	numindex (option)	147, 1176
textcomp (package)	101, 121, 1149	tocbibind (package)	146, 147, 1175, 1176
\texteb	13159	tocdata (package)	1177
textfit (package)	1153	tocdepth (counter)	107
\textgreater	6038	tocenter (package)	1178
\textit	13215	[tocloft]:	
\textless	6036	titles (option)	131
\textlg	13171	tocloft (package)	131, 147, 647, 1178, 1179
\textmd	13143	tocstyle (package)	1184
\textnormal	13266	todo (package)	1184
textpos (package)	1153	todonotes (package)	171, 1185
\textrm	13183	topcapt (package)	1187
\textsc	13223	\tracinglwrap	196, 1711
\textsf	13191	tram (package)	1187
\textsi	13239	transparent (package)	1188
\textsl	13256	trimclip (package)	1188
\textssc	13264	trivfloat (package)	166, 1188
\textsubscript	13450	truncate (package)	1189
\textsuperscript	13446	\ttfamily	13377
\texttt	13199	TtH (program)	72
\textulc	13231	turnthepage (package)	1190
\textup	13207	tutorial.tex (file)	82
\tfl@chapter@fix	1189	twoup (package)	1190
\thanks	118	txfonts (package)	1190
\thanksmarkseries	93	txgreek (package)	1191
\theauthor	407	typearea (package)	1191
thebibliography (environment) ..	11393	typicons (package)	1192
\thedata	407		
\theHTMLSection	7823		
\theHTMLTitleSection	7822		
\theHTMLTitleSeparator	7799		
theindex (environment)	11135		
\thempfootnote	6903		
theorem (package)	1154		
\thetitle	407		
thinsp (package)	1157		
\ThisAltText	111, 11613		
\thispagestyle	6237		
thm-listof (package)	1158		
thm-restate (package)	1158		
thmbox (package)	1159		
thmtools (package)	1160		
threadcol (package)	1160		
threeparttable (package)	1160		
threeparttablex (package) ..	165, 1161		
thumb (package)	1162		
thumbs (package)	1162		
tikz (package)	157, 1163		
tikz-image\labels (package)	1164		

U

\ulcshape	13399
ulem (package)	1192
umoline (package)	1194
\underline	13456
underscore (package)	1194
unicode-math (package)	1195
units (package)	155, 1199
unitsdef (package)	1200
Unix (program)	115, 225
\up	13454
upgreek (package)	1200
upref (package)	1201
\upshape	13382
url (package)	128, 1201
\UseMinipageWidths ..	123, 580, 12830
ushort (package)	1201
usingOSWindows (boolean)	226
uspace (package)	1202

V	
varioref (package)	128, 1202
\verb	8376
verbatim (environment)	8428
verbatim (package)	240
\VerbatimHTMLwidth (length)	418
\verbatiminput	8420
verse (environment)	2, 8351
verse (package)	170, 1202, 1203
versionotes (package)	1204
vertbars (package)	1204
\leftmargini (length)	170, 417, 1203
\leftskip (length)	170, 417, 1203
vmargin (package)	1205
vowel (package)	1205
vpe (package)	1206
\vrule	120
\vspace	120
wcol (package)	1206
W	
wallpaper (package)	1208
warpall (environment)	116, 1290
warpHTML (environment)	112, 115, 1291
warpHTML (option)	106, 227, 228
\warpHTMLonly	113, 116, 1248
warpingHTML (boolean)	227
warpingprint (boolean)	227
warpMathJax (environment)	116, 1297
warpprint (environment)	112, 116, 1294
warpprint (option)	106, 227
\warpprintonly	112, 116, 1247
warpsvg (environment)	116, 1306
watermark (package)	1208
widetable (package)	1209
widows-and-orphans (package)	1209
Windows (program)	115, 225
witharrows (package)	1209
Word (program)	73
WPMarkFloats (boolean)	181, 254
WPMarkLOFT (boolean)	182, 255
WPMarkMath (boolean)	182, 255
WPMarkMinipages (boolean)	181, 254
WPMarkTOC (boolean)	182, 255
X	
WPTitleHeading (boolean)	182, 255
wrapfig (package)	1210
wrapfig2 (package)	1212
X	
xbmks (package)	1215
xcolor (package)	158, 575, 1215
xexchangebar (package)	1225
\XeLaTeX	13787
XeLaTeX (program) [requirement]	76
xellipsis (package)	1225
\XeTeX	13787
xetexko (package)	1226
xevlna (package)	1226
xfakebold (package)	1226
xfrac (package)	1227
\xfracHTMLfontsize	2
xifthen (package)	240
xindex (option)	104, 230
xindex (program)	135, 145
xindexConfig (option)	104, 145, 229
xindy (option)	104, 230
xindy (program)	135, 144
xindyCodepage (option)	104, 229
xindyLanguage (option)	104, 229
xindyStyle (option)	104, 145, 228
xltable (package)	1229
xltxtra (package)	1230
xmpincl (package)	1230
xparse (package)	238
xpatch (package)	201
xpiano (package)	1231
xpinyin (package)	1231
xr (package)	1232
xr-hyper (package)	1233
xstring (package)	240
xtab (package)	165, 1233
xunicode (package)	1235
xurl (package)	1236
xy (package)	1236
Z	
zhlineskip (package)	1237
zwpagelayout (package)	1237

General Index

This is an index of instructions and concepts. Look here when wondering how to do something, and check the Troubleshooting Index when something goes wrong.

Symbols		CSS	
<code>\@ifnextchar</code> with <code>MATHJAX</code>	150	<code>class</code>	114
<code>\@ifstar</code> with <code>MATHJAX</code>	150	file selection	114
<code>\,</code>	120	<code>lwrap.css</code>	114
<code>~</code>	120	per HTML page	114
A		project-specific changes	114
accents		<code>span</code>	114
in section & file names	386	<code>ctable</code>	165
accessibility	98	D	
adapting		danger icon	200
class	188	debugging	190
document	97	HTML debug comments	248
package	187	tracing log	248
affiliation		defining print / HTML macros / envs ..	249
multiple authors	130	Deja Vu	100
algorithmicx		description	
with <code>newfloat</code> , <code>trivfloat</code>	1189	HTML meta tag	118, 362
<code>alt</code> text	98	display math	
ARIA	98	complicated objects	152
array		document	
<code>mhchem</code>	944	convert existing	97
<code>\newcolumn</code> and <code>\HTMLnewcolumn</code> ..	112	documentation	
audio	160	compile	186
author		DVI <code>L^AT_EX</code>	92, 100
HTML meta tag	118, 362	dynamic math	152
multiple	130	dynamic math expressions	334
B		E	
baseline		endnotes	
tabular	448	HTML page and toc	130
bibliography		EPS image	
HTML page and toc	130	converting	94
bitmapped fonts	100	using	156, 573
bugs	190	EPUB	
C		conversion software	178
<i>Calibre</i>	178	HTML conversion settings ..	178, 254
chemistry		equation numbering	
Greek symbols	705	<code>MATHJAX</code>	149
class		error messages	190
modifying for <code>lwrap</code>	188	export	
code listings	120	to word processor	180
compiling		F	
custom	173	FAQ	190
Computer Modern	100	filename	
converting		accent in	386
class	188	graphics	155, 573
document	97	hashed	541, 562
package	187	images	155, 573
		international languages	170
		length	109

simplify	126
underscore in	102, 121
unique	109
font	
Computer Modern	100
Deja Vu	100
ligatures	101
MATHJAX	149
packages	101
selection	100
size	
lateximage	148, 559
math, SVG	148, 559
xfrac	1227
type 1 vector	100
type 3 bitmapped	100
footnotes	363
MATHJAX	129
numbering	129
foreign	
section names	170
framed objects	123
Frequently Asked Questions	190
G	
generator	
HTML meta tag	399
GIF images	156, 574
gindex	135
gloss	132
glossaries	
HTML page and TOC	130
language	133
options	133
processing	93
graphics	
file formats	156, 573
file names	155, 573
Greek	
chemistry symbols	705
H	
hash	
SVG image filename	541, 562
heading, word processor	183
horizontal and vertical space	120
horizontal rule	120
horizontal space	
between minipages	603
\hrule	120
HTML	
alt text	98
class	114
conversion settings	107
debug comments	248
EPUB	178, 254
word processor	180, 254
conversion suggestions	119
defining print/HTML macros/envs	249
<div>	114
entities, conversion	120
filename generation	113
headings	199
meta tag	
author	118, 362
description	118, 362
generator	399
title	110, 118, 362
viewport	399
	114
style	114
tabular column conversion	449
verbatim, in	120
\HTMLnewcolumnmtype and \newcolumnmtype	112
hyperref	
and <i>xindy</i>	134
title text	98
I	
icon	
warning	200
\@ifnextchar with MATHJAX	150
\@ifnextstar with MATHJAX	150
image	
alt text	98
file formats	156, 573
file names	155, 573
GIF	156, 574
graphicx package	573
hashed filename	541, 562
PDF or EPS	
converting	94, 156, 574
using	156, 573
PNG and JPG	156, 574
processing	311
\includegraphics	
file names	155, 573
using	156, 573
index	
custom display styles	146
formatting	525
gindex	
setup	135
HTML page and TOC	130
<i>imakeidx</i>	
setup	138
<i>index</i>	
setup	136
letter headings	858
<i>makeindex</i>	
custom style file	143
setup	134
memoir	
setup	141
placement	146
placement and toc options	146, 1175
processing	86, 87, 134
see, seealso, ranges	134
source code	134

<i>splitidx</i>		
setup	136	
table of contents	146, 1175	
tocbibind	146	
UTF-8	101	
<i>xindex</i>		
custom configuration file	145	
setup	135	
<i>xindy</i>		
custom style file	144	
and hyperref	134	
setup	135	
inline math		
complicated objects	152	
international		
section names	170	
item		
empty	422	
J		
JAVASCRIPT		
MATHJAX	147	
JPG images	156, 574	
L		
language		
glossaries	133	
localization	98	
language HTML metadata	397	
lateximage		
font size	148, 559	
processing	311	
Latin Modern font	100	
LIBREOFFICE		
conversion recommendations	183	
import into	180	
section headings	183	
ligatures	101, 236	
line numbers	200	
link		
home/previous/next page	111	
title text	98	
list		
empty item	422	
filename	121	
listings, program code	120	
locale	176	
localization	98	
LuaL ^A T _E X		
detection	201	
file & section names	386	
lwarp		
compiling documentation	186	
loading	102	
options	102	
lwarp.ist		
customizing	143	
lwarp.xdy		
customizing	144	
<i>lwarpmk</i>		
customizing	189	
\LWR@formatted print/HTML	249	
M		
make utility	176	
<i>makeindex</i>	134	
customizing	143	
margin		
numbers	200	
tags	200	
markup languages	73	
math		
alt text	98	
display with complicated objects	152	
dynamic	152, 334	
MATHJAX	149	
font size — SVG	148, 559	
inline with complicated objects	152	
MATHJAX custom functions	149	
MATHJAX summary	148	
mathjax option	228	
mathsvg option	228	
mhchem	944	
SVG summary	148	
word processor conversion	182	
MATHJAX		
@ifnextchar macros	150	
@ifstar macros	150	
accessibility	98	
custom functions	149	
custom script	307	
equation numbering	149	
font	149	
mathjax option	228	
rendering	149	
starred macros	150	
summary	148	
\mcolrowcell	163	
MD5 hash		
SVG image filename	541, 562	
memoir		
framewithtitle, titledframe	169	
meta tag, HTML		
author	118, 362	
description	118, 362	
generator	399	
title	118, 362	
viewport	399	
minipage		
framed	123	
horizontal space between	603	
modifying		
class	188	
document	97	
package	187	
\mrowcell	163	
\multicolumn		
with \multirow	163	
multimedia	160	

multiple projects in a directory	94	sideroc	
\multirow		depth	107
with \multicolumn	163	siunitx	
multirow		with <i>TeXMaths</i>	182
\mrowcell and \mcolrowcell	163	space	
N			
navigation		horizontal	
link to home/previous/next page	111	between minipages	603
\newcolumnntype and \HTMLnewcolumnntype		horizontal and vertical	120
.	112	stack depths	199
newfloat		starred macros	150
with trivfloat, algorithmicx	1189	\StartDefiningTabulars	161, 429
nomencl	134	\subtitle	414
numbers		SVG	
left margin	200	converting from PDF or EPS	94
P			
package		dynamic math	334
modifying for lwarp	187	image processing	311
required	235	math summary	148
PDF image		mathsvg option	228
converting	94	T	
using	156, 573	tabular	
PERL	81	baseline	448
PNG images	156, 574	column specifier	162, 430
POPPLER	76, 80	HTML columnn conversion	449
print		in environments, catcode of &	161, 429
defining print/HTML macros/envs	249	macros inside	162, 430
problems	190	\multicolumn with \multirow	163
program listings	120	multirow \mrowcell and \mcolrowcell	
programs		163
utility	75	\newcolumnntype and \HTMLnewcolumnntype	
projects	94	112
\published	414	\StartDefiningTabulars	161, 429
R			
roles		text-align	162, 430
ARIO	98	text-align	162, 430
rule		tikz	
horizontal	120	catcodes	1163
S			
section		dollar redefined	1163
depths	199	title	
file names	126	HTML meta tag	118, 362
heading, word processor	183	titlepage	
international languages	170	\subtitle and \published	414
settings		tracing log	248
accessibility	98	trivfloat	
CSS project-specific	114	with newfloat, algorithmicx	1189
CSS selection	114	troubleshooting	190
filenames	107	HTML debug comments	248
HTML conversion	107	tracing log	248
language	98	type 1 vector fonts	100
lwarp package options	102	type 3 bitmapped fonts	100
selecting print/HTML output	115	U	
title page	117	underscore	
shell escape	100	filename	102, 121
sideroc		Unicode	
name	98	enhanced coverage	100
		file & section names	386
		input characters	218
		selection	100
		UTF-8	
		enhanced coverage	100

file & section names	386	word processor	
index	101	conversion recommendations ...	183
locale	176	HTML conversion settings ..	180, 254
selection	100	section headings	183
utility			
programs	75		
		X	
V		xcite	94
vector fonts	100	Xe _L A _T E _X	
verbatim		detection	201
code and HTML tags	120	file & section names	386
vertical space	120	<i>xindex</i>	135
video	160	customizing	145
viewport		<i>xindy</i>	135
HTML meta tag	399	and hyperref	134
		customizing	144
W		xr	94
warning icon	200	xr-hyper	94

Troubleshooting Index

This index is a sorted reference of problems and solutions. In order to make it easier to locate a solution, the same issue may be addressed by more than one entry.

Entries starting with page 200 are often duplicates of entries with lower page numbers, as the same warning may occur within the user manual and again within the source code.

A		breqn	
abstract		darray 682	
missing TOC	131, 622	bussproofs 683	
accents		C	
file names	386	<i>Calibre</i>	
acro	172	EPUB conversion	178
acronym		caption	
multiply-defined labels	629	numbering	167
\AddSubtitlePublished	414	options	119
affiliation	408	changes	693
alt tags	152, 194	character encoding	
amscdx	638	MATHJAX	151
AMSMath		chemfig	172
ntheorem		chemformula	
numbering	153, 989	MATHJAX	172, 700
appendix		chemgreek	
incorrect TOC link	132, 648	fontspec mapping	705
array		text-mode symbols	705
chemformula	172	chemmacros	
MATHJAX	150	\makepolymerdelims	706
\newcolumntype and \HTMLnewcolumntype		redox reactions	706
.....	112	Chinese	
arydshln	651	font	120
audio	160	CJK	
authblk		font	120
\theauthor	407, 408	cleveref	
titling	131, 406, 657, 1171	cref reference format undefined ..	152
author		cmbright	732
affiliation	408	colortbl	165, 734
formatting	117	Command \textquoteright invalid in	
autonum	658	math mode	193
B		comment	168, 1241
babel		compiling	
French	171	slow MATHJAX	149
backref	662	cref reference format undefined ..	152
backref	128	cross reference	
bibliography		incorrect link	194
HTML page and TOC	130	MATHJAX	151
bibtex		missing	194
\etalchar	132	CSS	195
Improper \prevdepth	132	ctable	165
bigdelim	166, 673	D	
bigfoot	130, 914	ditaa	177
booktabs	678	documentation	
boxes	122	index cross-references	186

dotless j	101	ligatures	101
dotlessj	192	MATHJAX	149
duplicate filename	127	missing symbols	121, 1150
E			
encoding		monospace	101
MATHJAX	151	package conflicts	100
\endhead, etc.	164	selection	100
endnotes		small caps	120
HTML page and TOC	130	UTF-8	100
numbering	132	fontspec	
\ensurermath	193	with monospaced fonts	101
epstopdf	158, 764	with X _Ǝ L _A T _E X, LuaL _A T _E X.	100
E PUB		footmisc	129, 363
encoding	178	footnote	
page order	178	displaymath	129, 774, 781
search order	178	in math	129
section breaks	178	in sectioning command	129
equation numbering		MATHJAX	129
MATHJAX	149	memoir	129, 363
error messages	190	numbering	129
\etalchar	132	paragraph tags	129, 774, 781
F			
fancybox		sectioning, footmisc	129, 363
\VerbatimFootnotes	129, 774, 781	sectioning, verbatim	129, 774, 781
fancypar	779	title	407
fancyvrb		verbatim	129
\VerbatimFootnotes	129, 774, 781	\VerbatimFootnotes	129, 774, 781
figure		forest	811
macro in name	193	formatting	
file		\bfseries etc.	120, 591
inaccessible	109	fourier	812
multiple projects in directory	94	frames	123
File ended while scanning use of \next	192	framewithtitle	169
filename		G	
accents	386	gloss	132
corrupted	127, 170	glossaries	
duplicate	127	HTML page and TOC	130
image extension	155, 573	<i>makeglossaries</i> not found	133, 824
international, UTF-8	170	page numbers	133, 825
Korean	172	style	133, 825
macro in name	127	graphics	
math in	97, 127, 147	\graphicspath	155, 573
Missing \$ inserted	192	\rotatebox, \scalebox, \reflectbox	157, 575
fixme	171, 792	image format priorities	156, 574
float		image not displayed	
alignment	121, 166	duplicate file	156, 574
not seem to be a floating environ-		extension	155, 573
ment	794	incorrect	
numbering	167	added or removed	88, 195
out of sequence	195	page counter	88, 195
float	794	multimedia	160
floatrow		optional arguments	157, 574
\FBwidth and \FBheight	167, 797	scale option	97, 157, 575
\ttboxed	161, 429	scaled	827
with subfig	167, 797	viewport	157, 574
font		\graphicspath	156, 574
CJK	120	Greek packages	705
JETBRAIN MONO	101	grffile	158, 838

H	
<code>\hrule</code>	120
HTML	
&, <, >	120, 591
alt tags	152
author	362
corrupted 101, 117, 122, 191, 192, 195	
entities	120, 591
image appear as HTML code .	88, 195
inaccessible pages	109, 111
starred section	131
invalid	119
missing pages	
filename not unique	109
recompile	195
SideTOCDepth and FileDepth .	109
SideTOCDepth and tocdepth ..	109
page did not update	109, 195
settings	
changed	107
undefined	192
validation	119
<code>\HTMLAuthor</code>	362
HTMLIndexCmd	
filenames	105
<code>\HTMLnewcolumn</code> type	112
hyperref	
backref	128
comments between arguments ..	128
incorrect link	194
Token not allowed in a PDF string	193
I	
image	
appears as HTML code	88, 195
filename extension	155, 573
format priorities	156, 574
incorrect	
added or removed	88, 195
page counter	88, 195
not displayed	
duplicate file	156, 574
extension	155, 573
svg math size and baseline	148
viewport	157, 574
Improper <code>\prevdepth</code>	
bibtex	132
boxes	193
<code>\includegraphics</code>	
optional arguments	157, 574
scale	97, 157, 575
index	
?? and non-functional link	106
documentation references	186
empty	146
empty link	127, 194
formatting	106, 525
HTML page and TOC	130
missing entries	134
numbers, not links	240
reference ranges	146
see and seealso	146
styling references	146
xindy	
and hyperref	146
xstring bug	240
isomath	864
J	
<code>\j</code>	101
Japanese	
font	120
JETBRAIN MONO	101
K	
keyfloat	168, 870
Korean	
font	120
kpfonts	877
kpfonts-otf	878
L	
label	
<code>\nameref</code> empty	127, 194
characters	127, 194
Label(s) may have changed	193
LaTeX was unable to guess the total...	193
<code>\LateximageFontSizeName</code>	559
Leaders not followed by proper glue .	193
<i>LibreOffice</i>	
import	180
ligatures	101
link	
empty	127, 194
LINUX	115, 225
list	
empty item	121, 422
listings	194
lists	
label formatting	423
locale	176
longtable	
<code>\endhead</code> , etc.	164
<code>lrbox</code>	122
ltxtable	
numbering	906
luaL ^A T _E X	100
<code>lwarpmk.conf</code>	86, 87
<i>lwarpmk</i>	86, 87
<code>\LWRbackslash</code>	173
<code>\LWRdollar</code>	173
<code>\LWRhash</code>	173
<code>\LWRopquote</code>	173
<code>\LWRopseq</code>	173
<code>\LWRpercent</code>	173
M	
MAC OS	115, 225
<i>makeglossaries</i>	
not found	133, 824
<code>\makeLabel</code>	423

manyfoot 130, 914
\marginpar 122, 369
math
 @ifnextchar macros and MATHJAX 150
 @ifstar macros and MATHJAX . . 150
 alt tags 194
 appears as HTML code 88, 195
 baseline incorrect 148
 chemformula 172
 Command \textquoteright invalid
 in math mode 193
 custom macros 193
 dynamic 334
 equation numbering
 MATHJAX 149
 ntheorem 153, 989
 file name 97, 127, 147
 footnote 129
 MATHJAX 129
 in T_EX boxes 148
 incorrect
 added or removed 88, 195
 dynamic 334
 non-math contents 193
 section name 97, 127, 147
 size incorrect 148
 slow or failed compile 194
 MATHJAX 150
 tabbing 160, 421
 Tikz 152
mathalpha 918
mathdesign 920
MATHJAX
 @ifnextchar macros 150
 @ifstar macros 150
 arydshln 651
 booktabs 678
 character encoding 151
 chemformula 172, 700
 custom script 307
 encoding 151
 equation numbering 149
 errors 152, 194, 334
 font 149
 footnotes 129
 mathtools 153, 925
 mhchem 944
 \multicolumn 150
 \multirow 150, 164, 961
 physics 155
 references 151
 rendering 149
 siunitx 154, 572, 1081
 slow compilation 149
 starred macros 150
 Unicode 151
 unicode-math 1195
 unsupported packages 151, 194
mathpazo 922
mathptmx 923
mathspec 923
mathtools 153, 925
maybemath 930
\mcolrowcell 163
media9 160
memoir
 framewithtitle, titledframe . . . 169
 captions 168, 1241
 comment 168, 1241
 footmisc 129, 363
 options clash 168, 1241
 page notes 169, 1241
 verse
 margin 170, 417, 1203
 version clash 168, 1241
mhchem
 MATHJAX 944
 nested dollar signs 944
minipage
 alignment 123, 581
 horizontal space between 603
 in a span 122, 580
 inline 122, 580
 multicols, width in 123, 580
 size 123, 580
 tabular, width in 123, 580
minted 949
Misplaced \noalign 164, 902
 tabular
 rules 163, 431
Misplaced \omit
 tabular 251
Misplaced alignment tab character &
 ctable 165, 737
 floatrow 167, 797
 frames 124
 supertabular 165, 1132, 1233
 tabular
 macros 161, 332, 429
Missing \$ inserted
 filename or URL 192
Missing \begin{document}
 package options 119
morewrites 146, 192
movie15 160
\mrowcell 163
MS-WINDOWS 115, 225
multicol
 \linewidth 123, 581
\multicolumn
 MATHJAX 150
multimedia 160
multiple projects in a directory 94
multiply-defined labels
 acronym 629
\multirow and \multicolumn . . 164, 961
multirow
 MATHJAX 150, 164, 961
 \mrowcell and \mcolrowcell . . . 163

N		R	
newclude	171	reference	
\newcolumnntype	112, 162, 430	% character between arguments	194
newpxmath	973	empty link	127, 194
newtxmath	974	incorrect link	194
newtxsf	975	label characters	127, 194
nicefrac	155	MATHJAX	151
nicematrix	983	missing or incorrect	194
No room for a new \write	192	page number	128, 194, 729
nomencl	134	undefined	
ntheorem	989	tcolorbox	126
cref reference format undefined	152	repeatindex	1038
font	153, 989	rlepsf	1040
numbering	153, 989	rterface	176
O		Runaway argument? File ended ...	192
operating system	115, 225	S	
options		sample_projects.css	
clash with memoir	168, 1241	overwritten	114
with braces	119	\savebox	122
overpic	159, 1002	\sbox	122
P		scale (\includegraphics option)	97, 157, 575
package		sectioning	
MATHJAX support	151	accents	386
options with braces	119	duplicate name	127
version numbers with memoir	168, 1241	international language	170
page		macro in name	127, 193
inaccessible	109	math in name	97, 127, 147
page counter		missing	109
references	128	starred section	131
SVG images	88, 195	word processor import	183
page numbers	128, 194, 729	seqsplit	1056
pagenote	132, 1003	sidenotes	
pdfcrop	80	numbering	129
pdfseparate	80	siunitx	
pdfcairo	80	\HTMLDeclareSIUnit	154, 572, 1081
pdftotex	80	drop-exponent	153, 571, 1080
pdftricks	158, 1017	MATHJAX	154, 572, 1081
perl	80	S column	163, 431
perltex	175	table-auto-roound	153, 571, 1080
pfnote		tabular S and s columns	153, 571, 1080
numbering	130, 1019	with <i>TeXMaths</i>	182
physics		small caps	120
MATHJAX	155	splitidx	
polyglossia		\thepage and \AtWriteToIndex	136, 1109
Undefined control seq ... begindoc-		statistics	1118
ument	171, 616	subcaption	
poppler		numbering	167
install	80	subfig	
Syntax Warning (ligature)	804	inline	167, 1126
PrintIndexCmd	104	numbering	167, 1126
projects		options	167, 1126
multiple	94	with floatrow	167, 797
psfrag	159	subtable	
pstool	159, 1029	numbering	
pstricks	158, 1029	subfig	167, 1126
pythontex	175	SVG image	
		appears as HTML code	88, 195

incorrect	
added or removed	195
page counter	88, 195
math incorrect	
dynamic	334
math size and baseline	148
out of order	88, 195
sympytex	175
Syntax Warning (ligature)	804
T	
tabbing	
math	160, 421
table	
macro in name	193
numbering	
<code>ltxtable</code>	906
<code>subfig</code>	167, 1126
Table of Contents	
missing	111
tabular	
baselines	448
column specifier	162, 430
corrupt rows	161, 429, 479
<code>\endhead</code> , <code>\endfoot</code> , <code>\endlastfoot</code>	164, 901
inside an environment	161, 429, 479
<code>\kill</code>	164, 902
macro inside	162, 430
Misplaced <code>\noalign</code>	163, 431
Misplaced alignment tab character &	
macros	161, 429
rules	332
<code>\multicolumn</code> with <code>\multirow</code>	163
<code>\multirow</code> <code>\mrowcell</code> and <code>\mcolrowcell</code>	163
<code>\newcolumn</code> and <code>\HTMLnewcolumn</code>	112, 162, 430
numbering	1229
row corruption	162, 430
rules	163, 431
S column	163, 431
<code>text-align</code>	162, 430
<code>tcolorbox</code>	126
Temporary page ... unable to guess ...	193
tensor	1147
TeX capacity exceeded	
Text input levels equals 15	192
TeXMaths	182
text	
<code>&</code> , <code><</code> , <code>></code>	120, 591
<code>\bfseries</code> etc.	120, 591
corrupted	100
Text input levels equals 15	192
<code>text-align</code>	162, 430
<code>textcomp</code>	
missing symbols	121, 1150
<code>\textquoteright</code> invalid in math mode	193
<code>\theauthor</code> and <code>authblk</code>	407, 408
theorem	
<code>cref</code> reference format undefined	152
<code>threeparttable</code>	165
<code>tikz</code>	
in math	152
matrices, &	157, 1163
title	
affiliation	408
newlines	117
<code>\thanks</code>	407
<code>titledframe</code>	169
titling	
<code>authblk</code>	131, 406, 657, 1171
hooks	414
<code>tocloft</code>	
chapter titles	131, 147, 647, 1179
<code>todonotes</code>	171, 909, 1185
Token not allowed in a PDF string	193
tracing <code>lwrap</code>	196
<code>tram</code>	1187
transparent	1188
U	
Undefined control seq ... <code>begindocument</code>	
<code>polyglossia</code>	171, 616
Unicode	
fonts	100
MATHJAX	151
UTF-8 locale	176
<code>unicode-math</code>	1195
units	155
UNIX	115, 225
URL	
Missing \$ inserted	192
<code>\usebox</code>	122
UTF-8	
locale	176
V	
<code>varioref</code>	128
<code>verbatim</code>	
footnote	129
framed	125, 773
<code>VerbatimFootnotes</code>	129, 774, 781
verse	
spacing	170, 417, 1203
verse	
margin	170, 417, 1203
version numbers	
with memoir	168, 1241
video	160
<code>viewport</code>	157, 574
W	
warning messages	190
<code>warpall</code>	116, 192
<code>warpHTML</code>	116, 192
<code>warpMathJax</code>	116, 192
<code>warpprint</code>	116, 192

warpsvg	116	<i>xindy</i>	
WINDOWS	115, 225	and hyperref	146
word processor		options	
import	180	HTMLIndexCmd	105
sectioning headings	183	LatexmkIndexCmd	105
		PrintIndexCmd	104
		<i>xltabular</i>	
		numbering	1229
X		xr	94
xcite	94	xr-hyper	94
xel ^A T _E X	100	xstring	240
xfakebold	1227		
xfrac	1227		

Index of Indexes

	C		I
Change History	1290	Index of Objects	1331
	G		T
General Index	1354	Troubleshooting Index	1359