

# The medmath package

Jianrui Lyu (tolvjr@163.com)

Version 2024B (2024-01-11)

## 1 The mediummath option in nccmath package

There are several problems with `mediummath` option in `nccmath` package.

1. The big operators in superscripts and subscripts are too large.

```
\[A^{\sum_0^1 x}=B\]
```

$$A \sum_0^1 x = B$$

2. The definite integrals inside `cases` environment sometimes cause infinite loops.

```
\[\begin{cases} \\int_1^t \\end{cases}\]
```

3. The `\oint` operators are not scaled to medium size.

```
\[\oint_{\Sigma} xyz dS=\frac{\sqrt{3}}{120}\]
```

$$\iint_{\Sigma} xyz dS = \frac{\sqrt{3}}{120}$$

## 2 The medmath package

The `medmath` package fixes and improves `mediummath` option in `nccmath` package.

1. The big operators in superscripts and subscripts are in medium size.

```
\[A^{\sum_0^1 x}=B\]
```

$$A \sum_0^1 x = B$$

2. The definite integrals inside `cases` environment always work.

```
\[\begin{cases} \\int_1^t \\end{cases}\]
```

$$\left\{ a \quad \int_1^t \right\}$$

3. The `\oint` operators are scaled to medium size.

```
\[\oint_{\Sigma} xyz dS=\frac{\sqrt{3}}{120}\]
```

$$\iint_{\Sigma} xyz dS = \frac{\sqrt{3}}{120}$$