

The L^AT_EX metalogox package

v1.04 — 2024/01/26

© 2019, 2023–2024 Brian Dunn
<https://github.com/bdtc/metalogox>

Automatically adjusts the T_EX logo and related, depending on the font.

Font	Default	metalogox
Latin Modern	L ^A T _E X 2 _ε	L ^A T _E X 2 _ε
Erewhon	L ^A T _E X 2 _ε	L ^A T _E X 2 _ε
Libre Caslon	L ^A T _E X 2 _ε	L ^A T _E X 2 _ε
IM Fell English	L ^A T _E X 2 _ε	L ^A T _E X 2 _ε
Coelacanth	L ^A T _E X 2 _ε	L ^A T _E X 2 _ε
Alegreya	L ^A T _E X 2 _ε	L ^A T _E X 2 _ε
Helvetica	L ^A T _E X 2 _ε	L ^A T _E X 2 _ε
Antiqua	L ^A T _E X 2 _ε	L ^A T _E X 2 _ε

Abstract

The metalogox package extends the metago package to automatically adjust the appearance of the logos T_EX, L^AT_EX, L^AT_EX 2_ε, X_EL^AT_EX, and LuaL^AT_EX, depending on the font detected or the option given to metalogox.

Most of the serif and sans fonts listed at [The L^AT_EX Font Catalogue](#) are supported.

Contents

1	Introduction	3
2	Using the metalogox package	3
3	Code	5
3.1	Required packages	5
3.2	Package options	5
3.2.1	Common synonyms	15
3.2.2	Similar fonts	16
3.3	Manual adjust selection	17
3.4	Font detection	17
3.5	Option declaration	24
3.6	Default settings	24
3.7	Option trigger	25
3.8	Support for the <code>hologo</code> and <code>hvlogos</code> packages	25
A	Change History	27
B	Index	27

1 Introduction

The rendering of the logos \TeX , \LaTeX , $\text{\LATEX}_2\epsilon$, \XeLaTeX , \XeTeX , and \LuaLaTeX depends on the font, and in some cases the appearance of these logos may be improved with some minor adjustments of the positions of each of the elements. The **metalogox** package, by ANDREW GILBERT MOSCHOU, allows the user to specify these adjustments, but it is left to the user to determine the values to use. The correct value may depend on the font size, but in most cases predefined settings may be used.

The **metalogox** package assigns these settings for **metalogox**. The default is for **LATIN MODERN** and similar. If the font in use is supported by **metalogox**, settings for that font are automatically assigned, overriding the **LATIN MODERN** default. If the user specifies a package option, its settings override the default and also anything set by font detection.

The **\LaTeX** packages **hologo** and **hvlogos** are also supported when used with **metalogox**.

2 Using the **metalogox** package

- metalogox (Pkg)** In most cases, it is sufficient to simply load the **metalogox** package after the fonts have been selected:

```
\usepackage{<font packages>}
\setmainfont{Font Name}                                (if using fontspec)
. . . etc . .
% \renewcommand{\familydefault}{\sfdefault}           (optional)
. .
\usepackage{metalogox}
```

Many fonts are supported by **metalogox**, and if one of these is in use then the appropriate settings are assigned automatically, according to the default text body font: $\text{\LATEX}_2\epsilon$

- options** If several font packages are used, or a font is not recognized, it may be necessary to specify a **metalogox** package option, which overrides the font detection:

```
\usepackage[baskerville]{metalogox}
\adjustlogos {\langle package option \rangle}
```

\adjustlogos may be used to adjust the logos for an unknown font. The mandatory argument is the same as the package options. This is a local change, and may be adjusted as needed.

```
\Fontskrivan                                     (from the aurical package)
\adjustlogos{default} \LaTeXe
\adjustlogos{baskerville} \LaTeXe
\Fontskrivan                                     \LATEX_2\epsilon
\adjustlogos{baskerville} \LaTeXe
\Fontskrivan                                     \LATEX_2\epsilon
```

\autoadjustlogos \autoadjustlogos may be used to make local changes according to the current font:

\textsf{Using \autoadjustlogos\LaTeXe} Using L^AT_EX 2_<
\textsf{Using \textrm{\autoadjustlogos\LaTeXe}} Using L^AT_EX 2_>

\autoadjustlogos* The starred form, \autoadjustlogos*, is used by metalogox at the beginning of the document to set according to the default text body font.

Notes:

- metalogox option names may be found in the following pages, or in the index.
- metalogox options are always lowercase, even if a related package name may have uppercase letters.
- Many options, such as `times`, are used to cover an entire category of related fonts.
- Other options, such as `baskerville`, may be used for unrelated fonts which just happen to work well with the same logo settings.
- For some fonts, X_{EL}L^AT_EX renders the reversed E in the X_{EL}L^AT_EX logo differently than pdfL^AT_EX and LuaL^AT_EX.
- There are sometimes differences between the `Type1` and the `OTF/TTF` fonts.
- PDF display software may not render logos well on the screen at small display sizes. Zoom in to judge the quality of the logos.
- The metalogox parameters were set according to the design preferences of the author of the metalogo package. Some may disagree with the design choices which were made, but the results are probably better than the defaults, and the user may take control using the metalogo package directly.
- Since the same settings are usually shared by many fonts, some logos may not be perfect.
- If a font is not known by metalogox then a warning is issued, and a few common options are recommended.

[Unknown font?](#)

- Please contact the author of metalogox if an unknown font is found, especially if it is a common font, as sometimes the font family names are changed. See the contact link on the title page of this document.

3 Code

3.1 Required packages

```

1 \RequirePackage{metalogo}
2
3 \RequirePackage{xparse}
4
5 \RequirePackage{etoolbox}
```

3.2 Package options

Each of the following is a macro which is activated by passing the option of the same name to `metalogox`, or by calling `\adjustlogos`.

For example, either of the following sets the default `metalogo` logo adjustments:

```
\usepackage[default]{matalogox}
— or —
\adjustlogos{default}
```

`default` (*Opt*) The L^AT_EX and `metalogo` default settings.

```

6 \newcommand*{\MLX@default}{%
7   \setlogokern{Te}{-0.1667em}%
8   \setlogokern{eX}{-0.125em}%
9   \setlogokern{La}{-.36em}%
10  \setlogokern{aT}{-.15em}%
11  \setlogokern{Xe}{-.125em}%
12  \setlogokern{eT}{-.1667em}%
13  \setlogokern{eL}{-.125em}%
14  \setlogodrop{0.5ex}%
15 }
```

`accanthis` (*Opt*)

```

16 \newcommand*{\MLX@accanthis}{%
17   \setlogokern{Te}{-0.07em}%
18   \setlogokern{eX}{-0.05em}%
19   \setlogokern{La}{-.26em}%
20   \setlogokern{aT}{-.07em}%
21   \setlogokern{Xe}{-.06em}%
22   \setlogokern{eT}{-.05em}%
23   \setlogokern{eL}{-.06em}%
24   \setlogodrop{0.25ex}%
25 }
```

`alegreya` (*Opt*)

```

26 \newcommand*{\MLX@alegreya}{%
27   \setlogokern{Te}{-0.14em}%
28   \setlogokern{eX}{-0.12em}%
```

```

29      \setlogokern{La}{-.23em}%
30      \setlogokern{aT}{-.07em}%
31      \setlogokern{Xe}{-.06em}%
32      \setlogokern{eT}{-.10em}%
33      \setlogokern{eL}{-.12em}%
34      \setlogodrop{0.36ex}%
35 }

```

algolrevived (*Opt*)

```

36 \newcommand*{\MLX@algolrevived}{%
37     \setlogokern{Te}{-.17em}%
38     \setlogokern{eX}{-.17em}%
39     \setlogokern{La}{-.40em}%
40     \setlogokern{aT}{-.06em}%
41     \setlogokern{Xe}{-.18em}%
42     \setlogokern{eT}{-.18em}%
43     \setlogokern{eL}{-.12em}%
44     \setlogodrop{0.28ex}%
45 }

```

antpolt (*Opt*)

```

46 \newcommand*{\MLX@antpolt}{%
47     \setlogokern{Te}{-.09em}%
48     \setlogokern{eX}{-.08em}%
49     \setlogokern{La}{-.33em}%
50     \setlogokern{aT}{-.07em}%
51     \setlogokern{Xe}{-.07em}%
52     \setlogokern{eT}{-.10em}%
53     \setlogokern{eL}{-.06em}%
54     \setlogodrop{0.36ex}%
55 }

```

avantgarde (*Opt*)

```

56 \newcommand*{\MLX@avantgarde}{%
57     \setlogokern{Te}{-.10em}%
58     \setlogokern{eX}{-.04em}%
59     \setlogokern{La}{-.26em}%
60     \setlogokern{aT}{-.10em}%
61     \setlogokern{Xe}{-.04em}%
62     \setlogokern{eT}{-.10em}%
63     \setlogokern{eL}{-.02em}%
64     \setlogodrop{0.40ex}%
65 }

```

baskerville (*Opt*)

```

66 \newcommand*{\MLX@baskerville}{%
67     \setlogokern{Te}{-.07em}%
68     \setlogokern{eX}{-.05em}%
69     \setlogokern{La}{-.26em}%

```

```

70      \setlogokern{aT}{-.07em}%
71      \setlogokern{Xe}{-.06em}%
72      \setlogokern{eT}{-.07em}%
73      \setlogokern{eL}{-.06em}%
74      \setlogodrop{0.36ex}%
75 }

```

berenis (*Opt*)

```

76 \newcommand*{\MLX@berenis}{%
77     \setlogokern{Te}{-.07em}%
78     \setlogokern{eX}{-.05em}%
79     \setlogokern{La}{-.23em}%
80     \setlogokern{aT}{-.07em}%
81     \setlogokern{Xe}{-.06em}%
82     \setlogokern{eT}{-.10em}%
83     \setlogokern{eL}{-.02em}%
84     \setlogodrop{0.58ex}%
85 }

```

bodoni (*Opt*) Also see *librebodoni*.

```

86 \newcommand*{\MLX@bodoni}{%
87     \setlogokern{Te}{-.11em}%
88     \setlogokern{eX}{-.05em}%
89     \setlogokern{La}{-.26em}%
90     \setlogokern{aT}{-.07em}%
91     \setlogokern{Xe}{-.06em}%
92     \setlogokern{eT}{-.10em}%
93     \setlogokern{eL}{-.10em}%
94     \setlogodrop{0.37ex}%
95 }

```

boisik (*Opt*)

```

96 \newcommand*{\MLX@boisik}{%
97     \setlogokern{Te}{-.09em}%
98     \setlogokern{eX}{-.07em}%
99     \setlogokern{La}{-.35em}%
100    \setlogokern{aT}{-.07em}%
101    \setlogokern{Xe}{-.07em}%
102    \setlogokern{eT}{-.10em}%
103    \setlogokern{eL}{-.06em}%
104    \setlogodrop{0.55ex}%
105 }

```

bookman (*Opt*)

```

106 \newcommand*{\MLX@bookman}{%
107     \setlogokern{Te}{-.03em}%
108     \setlogokern{eX}{-.035em}%
109     \setlogokern{La}{-.25em}%
110     \setlogokern{aT}{-.00em}%

```

```

111      \setlogokern{Xe}{-.030em}%
112      \setlogokern{eT}{-.02em}%
113      \setlogokern{eL}{-.06em}%
114      \setlogodrop{.36ex}%
115 }

```

charter (*Opt*)

```

116 \newcommand*{\MLX@charter}{%
117     \setlogokern{Te}{-.10em}%
118     \setlogokern{eX}{-.07em}%
119     \setlogokern{La}{-.24em}%
120     \setlogokern{aT}{-.06em}%
121     \setlogokern{Xe}{-.07em}%
122     \setlogokern{eT}{-.10em}%
123     \setlogokern{eL}{-.06em}%
124     \setlogodrop{.28ex}%
125 }

```

crimson (*Opt*)

```

126 \newcommand*{\MLX@crimson}{%
127     \setlogokern{Te}{-.05em}%
128     \setlogokern{eX}{-.05em}%
129     \setlogokern{La}{-.23em}%
130     \setlogokern{aT}{-.07em}%
131     \setlogokern{Xe}{-.06em}%
132     \setlogokern{eT}{-.05em}%
133     \setlogokern{eL}{-.06em}%
134     \setlogodrop{.36ex}%
135 }

```

coelacanth (*Opt*)

```

136 \newcommand*{\MLX@coelacanth}{%
137     \setlogokern{Te}{-.09em}%
138     \setlogokern{eX}{-.05em}%
139     \setlogokern{La}{-.26em}%
140     \setlogokern{aT}{-.07em}%
141     \setlogokern{Xe}{-.06em}%
142     \setlogokern{eT}{-.10em}%
143     \setlogokern{eL}{-.06em}%
144     \setlogodrop{.32ex}%
145 }

```

didot (*Opt*)

```

146 \newcommand*{\MLX@didot}{%
147     \setlogokern{Te}{-.11em}%
148     \setlogokern{eX}{-.09em}%
149     \setlogokern{La}{-.34em}%
150     \setlogokern{aT}{-.11em}%
151     \setlogokern{Xe}{-.06em}%

```

```

152     \setlogokern{eT}{-.12em}%
153     \setlogokern{eL}{-.09em}%
154     \setlogodrop{0.44ex}%
155 }
```

droidserif (*Opt*)

```

156 \newcommand*{\MLX@droidserif}{%
157     \setlogokern{Te}{-.11em}%
158     \setlogokern{eX}{-.10em}%
159     \setlogokern{La}{-.30em}%
160     \setlogokern{aT}{-.08em}%
161     \setlogokern{Xe}{-.07em}%
162     \setlogokern{eT}{-.10em}%
163     \setlogokern{eL}{-.08em}%
164     \setlogodrop{0.30ex}%
165 }
```

droidsans (*Opt*)

```

166 \newcommand*{\MLX@droidsans}{%
167     \setlogokern{Te}{-.11em}%
168     \setlogokern{eX}{-.10em}%
169     \setlogokern{La}{-.24em}%
170     \setlogokern{aT}{-.08em}%
171     \setlogokern{Xe}{-.07em}%
172     \setlogokern{eT}{-.10em}%
173     \setlogokern{eL}{-.08em}%
174     \setlogodrop{0.30ex}%
175 }
```

gentium (*Opt*)

```

176 \newcommand*{\MLX@gentium}{%
177     \setlogokern{Te}{-.07em}%
178     \setlogokern{eX}{-.07em}%
179     \setlogokern{La}{-.26em}%
180     \setlogokern{aT}{-.07em}%
181     \setlogokern{Xe}{-.06em}%
182     \setlogokern{eT}{-.06em}%
183     \setlogokern{eL}{-.06em}%
184     \setlogodrop{0.24ex}%
185 }
```

helvetica (*Opt*)

```

186 \newcommand*{\MLX@helvetica}{%
187     \setlogokern{Te}{-.15em}%
188     \setlogokern{eX}{-.08em}%
189     \setlogokern{La}{-.26em}%
190     \setlogokern{aT}{-.08em}%
191     \setlogokern{Xe}{-.07em}%
192     \setlogokern{eT}{-.15em}%
193 }
```

```

193     \setlogokern{eL}{-.04em}%
194     \setlogodrop{0.40ex}%
195 }
```

kerkis (*Opt*)

```

196 \newcommand*{\MLX@kerkis}{%
197     \setlogokern{Te}{-.02em}%
198     \setlogokern{eX}{-.02em}%
199     \setlogokern{La}{-.25em}%
200     \setlogokern{aT}{-.00em}%
201     \setlogokern{Xe}{-.00em}%
202     \setlogokern{eT}{-.10em}%
203     \setlogokern{eL}{-.05em}%
204     \setlogodrop{0.38ex}%
205 }
```

kpfonts (*Opt*)

```

206 \newcommand*{\MLX@kpfonts}{%
207     \setlogokern{Te}{-.11em}%
208     \setlogokern{eX}{-.08em}%
209     \setlogokern{La}{-.30em}%
210     \setlogokern{aT}{-.11em}%
211     \setlogokern{Xe}{-.10em}%
212     \setlogokern{eT}{-.10em}%
213     \setlogokern{eL}{-.06em}%
214     \setlogodrop{0.33ex}%
215 }
```

libertine (*Opt*) Also see **libertinus**, below.

```

216 \newcommand*{\MLX@libertine}{%
217     \setlogokern{Te}{-.05em}%
218     \setlogokern{eX}{-.06em}%
219     \setlogokern{La}{-.25em}%
220     \setlogokern{aT}{-.05em}%
221     \setlogokern{Xe}{-.05em}%
222     \setlogokern{eT}{-.05em}%
223     \setlogokern{eL}{-.02em}%
224     \setlogodrop{0.32ex}%
225 }
```

libertinus (*Opt*) There is a difference in the raised ‘A’ vs. **libertine**.

```

226 \newcommand*{\MLX@libertinus}{%
227     \setlogokern{Te}{-.05em}%
228     \setlogokern{eX}{-.06em}%
229     \setlogokern{La}{-.28em}%
230     \setlogokern{aT}{-.05em}%
231     \setlogokern{Xe}{-.05em}%
232     \setlogokern{eT}{-.05em}%
233     \setlogokern{eL}{-.02em}%
}
```

```
234     \setlogodrop{0.32ex}%
235 }
```

`librebodoni` (*Opt*) Specific to LibreBodoni only.

```
236 \newcommand*{\MLX@librebodoni}{%
237     \setlogokern{Te}{-0.07em}%
238     \setlogokern{eX}{-0.05em}%
239     \setlogokern{La}{-.26em}%
240     \setlogokern{aT}{-.07em}%
241     \setlogokern{Xe}{-.06em}%
242     \setlogokern{eT}{-.10em}%
243     \setlogokern{eL}{-.02em}%
244     \setlogodrop{0.49ex}%
245 }
```

`lmodern` (*Opt*)

```
246 \newcommand*{\MLX@lmodern}{%
247     \setlogokern{Te}{-0.10em}%
248     \setlogokern{eX}{-0.06em}%
249     \setlogokern{La}{-.33em}%
250     \setlogokern{aT}{-.15em}%
251     \setlogokern{Xe}{-.07em}%
252     \setlogokern{eT}{-.10em}%
253     \setlogokern{eL}{-.08em}%
254     \setlogodrop{0.52ex}%
255 }
```

`lmodernsans` (*Opt*)

```
256 \newcommand*{\MLX@lmodernsans}{%
257     \setlogokern{Te}{-0.20em}%
258     \setlogokern{eX}{-0.06em}%
259     \setlogokern{La}{-.29em}%
260     \setlogokern{aT}{-.12em}%
261     \setlogokern{Xe}{-.07em}%
262     \setlogokern{eT}{-.20em}%
263     \setlogokern{eL}{-.08em}%
264     \setlogodrop{0.45ex}%
265 }
```

`merriweather` (*Opt*)

```
266 \newcommand*{\MLX@merriweather}{%
267     \setlogokern{Te}{-0.09em}%
268     \setlogokern{eX}{-0.09em}%
269     \setlogokern{La}{-.26em}%
270     \setlogokern{aT}{-.07em}%
271     \setlogokern{Xe}{-.06em}%
272     \setlogokern{eT}{-.10em}%
273     \setlogokern{eL}{-.06em}%
274     \setlogodrop{0.32ex}%
```

275 }

newcent (*Opt*)

```
276 \newcommand*{\MLX@newcent}{%
277     \setlogokern{Te}{-.08em}%
278     \setlogokern{eX}{-.09em}%
279     \setlogokern{La}{-.30em}%
280     \setlogokern{aT}{-.07em}%
281     \setlogokern{Xe}{-.07em}%
282     \setlogokern{eT}{-.10em}%
283     \setlogokern{eL}{-.06em}%
284     \setlogodrop{.49ex}%
285 }
```

noto (*Opt*)

```
286 \newcommand*{\MLX@noto}{%
287     \setlogokern{Te}{-.11em}%
288     \setlogokern{eX}{-.10em}%
289     \setlogokern{La}{-.30em}%
290     \setlogokern{aT}{-.07em}%
291     \setlogokern{Xe}{-.10em}%
292     \setlogokern{eT}{-.10em}%
293     \setlogokern{eL}{-.06em}%
294     \setlogodrop{.26ex}%
295 }
```

palatino (*Opt*)

```
296 \newcommand*{\MLX@palatino}{%
297     \setlogokern{Te}{-.07em}%
298     \setlogokern{eX}{-.09em}%
299     \setlogokern{La}{-.33em}%
300     \setlogokern{aT}{-.10em}%
301     \setlogokern{Xe}{-.09em}%
302     \setlogokern{eT}{-.08em}%
303     \setlogokern{eL}{-.07em}%
304     \setlogodrop{.35ex}%
305 }
```

pandora (*Opt*)

```
306 \newcommand*{\MLX@pandora}{%
307     \setlogokern{Te}{-.09em}%
308     \setlogokern{eX}{-.08em}%
309     \setlogokern{La}{-.32em}%
310     \setlogokern{aT}{-.07em}%
311     \setlogokern{Xe}{-.08em}%
312     \setlogokern{eT}{-.10em}%
313     \setlogokern{eL}{-.06em}%
314     \setlogodrop{.53ex}%
315 }
```

paratype (*Opt*)

```

316 \newcommand*{\MLX@paratype}{%
317   \setlogokern{Te}{-.07em}%
318   \setlogokern{eX}{-.10em}%
319   \setlogokern{La}{-.26em}%
320   \setlogokern{aT}{-.07em}%
321   \setlogokern{Xe}{-.06em}%
322   \setlogokern{eT}{-.10em}%
323   \setlogokern{eL}{-.06em}%
324   \setlogodrop{.34ex}%
325 }
```

plexserif (*Opt*)

```

326 \newcommand*{\MLX@plexserif}{%
327   \setlogokern{Te}{-.1667em}%
328   \setlogokern{eX}{-.125em}%
329   \setlogokern{La}{-.30em}%
330   \setlogokern{aT}{-.10em}%
331   \setlogokern{Xe}{-.125em}%
332   \setlogokern{eT}{-.16em}%
333   \setlogokern{eL}{-.10em}%
334   \setlogodrop{.05ex}%
335 }
```

plexsans (*Opt*)

```

336 \newcommand*{\MLX@plexsans}{%
337   \setlogokern{Te}{-.1667em}%
338   \setlogokern{eX}{-.10em}%
339   \setlogokern{La}{-.25em}%
340   \setlogokern{aT}{-.10em}%
341   \setlogokern{Xe}{-.10em}%
342   \setlogokern{eT}{-.17em}%
343   \setlogokern{eL}{-.10em}%
344   \setlogodrop{.05ex}%
345 }
```

quattrocento (*Opt*) Compromises must be made here. It appears that the height of 1ex is incorrect for serif with X_EL^AT_EX, L_AU_L^AT_EX.

```

346 \newcommand*{\MLX@quattrocento}{%
347   \setlogokern{Te}{-.09em}%
348   \setlogokern{eX}{-.05em}%
349   \setlogokern{La}{-.26em}%
350   \setlogokern{aT}{-.07em}%
351   \setlogokern{Xe}{-.06em}%
352   \setlogokern{eT}{-.10em}%
353   \setlogokern{eL}{-.06em}%
354   \setlogodrop{.4ex}%
355 }
```

sourceserifpro (Opt)

```

356 \newcommand*{\MLX@sourceserifpro}{%
357     \setlogokern{Te}{-.12em}%
358     \setlogokern{eX}{-.09em}%
359     \setlogokern{La}{-.29em}%
360     \setlogokern{aT}{-.07em}%
361     \setlogokern{Xe}{-.09em}%
362     \setlogokern{eT}{-.10em}%
363     \setlogokern{eL}{-.09em}%
364     \setlogodrop{.30ex}%
365 }
```

sourcesanspro (Opt)

```

366 \newcommand*{\MLX@sourcesanspro}{%
367     \setlogokern{Te}{-.12em}%
368     \setlogokern{eX}{-.09em}%
369     \setlogokern{La}{-.22em}%
370     \setlogokern{aT}{-.07em}%
371     \setlogokern{Xe}{-.09em}%
372     \setlogokern{eT}{-.10em}%
373     \setlogokern{eL}{-.09em}%
374     \setlogodrop{.30ex}%
375 }
```

times (Opt)

```

376 \newcommand*{\MLX@times}{%
377     \setlogokern{Te}{-.06em}%
378     \setlogokern{eX}{-.05em}%
379     \setlogokern{La}{-.28em}%
380     \setlogokern{aT}{-.07em}%
381     \setlogokern{Xe}{-.06em}%
382     \setlogokern{eT}{-.06em}%
383     \setlogokern{eL}{-.02em}%
384     \setlogodrop{.34ex}%
385 }
```

utopia (Opt)

```

386 \newcommand*{\MLX@utopia}{%
387     \setlogokern{Te}{-.08em}%
388     \setlogokern{eX}{-.04em}%
389     \setlogokern{La}{-.21em}%
390     \setlogokern{aT}{-.10em}%
391     \setlogokern{Xe}{-.02em}%
392     \setlogokern{eT}{-.10em}%
393     \setlogokern{eL}{-.06em}%
394     \setlogodrop{.30ex}%
395 }
```

venturis (Opt)

```

396 \newcommand*{\MLX@venturis}{%
397     \setlogokern{Te}{-.07em}%
398     \setlogokern{eX}{-.05em}%
399     \setlogokern{La}{-.22em}%
400     \setlogokern{aT}{-.07em}%
401     \setlogokern{Xe}{-.06em}%
402     \setlogokern{eT}{-.06em}%
403     \setlogokern{eL}{-.06em}%
404     \setlogodrop{.36ex}%
405 }

```

vera (*Opt*)

```

406 \newcommand*{\MLX@vera}{%
407     \setlogokern{Te}{-.12em}%
408     \setlogokern{eX}{-.14em}%
409     \setlogokern{La}{-.32em}%
410     \setlogokern{aT}{-.05em}%
411     \setlogokern{Xe}{-.14em}%
412     \setlogokern{eT}{-.10em}%
413     \setlogokern{eL}{-.10em}%
414     \setlogodrop{.235ex}%
415 }

```

verasans (*Opt*)

```

416 \newcommand*{\MLX@verasans}{%
417     \setlogokern{Te}{-.12em}%
418     \setlogokern{eX}{-.10em}%
419     \setlogokern{La}{-.28em}%
420     \setlogokern{aT}{-.05em}%
421     \setlogokern{Xe}{-.10em}%
422     \setlogokern{eT}{-.10em}%
423     \setlogokern{eL}{-.10em}%
424     \setlogodrop{.35ex}%
425 }

```

3.2.1 Common synonyms

Synonyms for commonly-used fonts.

tgbonum (*Opt*)

```
426 \newcommand*{\MLX@tgbonum}{\MLX@bookman}
```

tgheros (*Opt*)

```
427 \newcommand*{\MLX@tgheros}{\MLX@helvetica}
```

tgpagella (*Opt*)

```
428 \newcommand*{\MLX@tgpagella}{\MLX@palatino}
```

tgschola (*Opt*)

```
429 \newcommand*\{\MLX@tgschola\}{\MLX@newcent}
```

tgtermes (*Opt*)

```
430 \newcommand*\{\MLX@tgtermes\}{\MLX@times}
```

3.2.2 Similar fonts

The following work well enough that a separate definition is probably not necessary.

antiqua (*Opt*)

```
431 \newcommand*\{\MLX@antiqua\}{\MLX@baskerville}
```

anttor (*Opt*)

```
432 \newcommand*\{\MLX@anttor\}{\MLX@antpolt}
```

artemisia (*Opt*)

```
433 \newcommand*\{\MLX@artemisia\}{\MLX@baskerville}
```

caladea (*Opt*)

```
434 \newcommand*\{\MLX@caladea\}{\MLX@baskerville}
```

caslon (*Opt*)

```
435 \newcommand*\{\MLX@caslon\}{\MLX@baskerville}
```

cochineal (*Opt*)

```
436 \newcommand*\{\MLX@cochineal\}{\MLX@baskerville}
```

concmath (*Opt*)

```
437 \newcommand*\{\MLX@concmath\}{\MLX@lmodern}
```

drm (*Opt*)

```
438 \newcommand*\{\MLX@drm\}{\MLX@lmodern}
```

garamond (*Opt*)

```
439 \newcommand*\{\MLX@garamond\}{\MLX@baskerville}
```

imfellenglish (*Opt*)

```
440 \newcommand*\{\MLX@imfellenglish\}{\MLX@baskerville}
```

`literat (Opt)`

```
441 \newcommand*{\MLX@literat}{\MLX@baskerville}
```

`roboto (Opt)`

```
442 \newcommand*{\MLX@roboto}{\MLX@pandora}
```

`romande (Opt)`

```
443 \newcommand*{\MLX@romande}{\MLX@baskerville}
```

3.3 Manual adjust selection

`\adjustlogos {⟨package option⟩}`

If the given option matches a predefined `\MLX@...` macro, use it.

```
444 \newcommand*{\adjustlogos}[1]{%
445     \ifcsdef{MLX@#1}{%
446         \PackageInfo{metalogox}{Setting #1}%
447         \csuse{MLX@#1}%
448     }{%
449         \PackageError{metalogox}{Unknown setting #1}%
450         {See the metalogox documentation for a list of options.}%
451     }%
452 }
```

3.4 Font detection

`MLX@@foundfont (bool)` Found the font?

```
453 \newbool{MLX@@foundfont}
```

`\MLX@@detectvariant {⟨1:family⟩} {⟨2:variant⟩} {⟨3:name⟩} {⟨4:setting⟩}`

If the font variant matches, adjust accordingly.

(The doubled @ is to distinguish this from a valid `metalogox` option.)

```
454 \newcommand*{\MLX@@detectvariant}[4]{%
455 \ifdefstring{\MLX@thisfont}{#1#2}{%
456     \booltrue{MLX@@foundfont}%
457     \PackageInfo{metalogox}{Detected #1#2, #3. Using #4}%
458     \adjustlogos{#4}%
459 }{%
460 }
```

```
\MLX@@detectone {⟨1:family⟩} {⟨2:name⟩} {⟨3:setting⟩}
```

Tests variants. If a font family and variant matches, select the **metalogox** option.

(The doubled @ is to distinguish this from a valid **metalogox** option.)

```
461 \NewDocumentCommand{\MLX@@detectone}{m m m}{%
462 \MLX@@detectvariant{#1}{ }{#2}{#3}%
463 \MLX@@detectvariant{#1}{-TLF}{#2}{#3}%
464 \MLX@@detectvariant{#1}{-LF}{#2}{#3}%
465 \MLX@@detectvariant{#1}{-OsF}{#2}{#3}%
466 \MLX@@detectvariant{#1}{-T0sF}{#2}{#3}%
467 \MLX@@detectvariant{#1}{Condensed-TLF}{#2}{#3}%
468 \MLX@@detectvariant{#1}{Condensed-LF}{#2}{#3}%
469 \MLX@@detectvariant{#1}{Condensed-OsF}{#2}{#3}%
470 \MLX@@detectvariant{#1}{Condensed-T0sF}{#2}{#3}%
471 \MLX@@detectvariant{#1}{(0)}{#2}{#3}%
472 \MLX@@detectvariant{#1}{(1)}{#2}{#3}%
473 }
```

```
\autoadjustlogos *
```

Search a list of fonts and variants, looking for a match with the current one.

```
474 \NewDocumentCommand{\autoadjustlogos}{s}{%
```

Not yet discovered the font:

```
475 \boolfalse{\MLX@@foundfont}%
```

If starred, use the text body font, else use the local font:

```
476 \IfBooleanTF{#1}{%
477   \edef\MLX@@thisfont{\familydefault}%
478 }{%
479   \edef\MLX@@thisfont{\f@family}%
480 }%
```

Announce the desired font:

```
481 \PackageInfo{metalogox}{Searching for \MLX@@thisfont} %
```

Default if nothing is found:

```
482 \adjustlogos{lmodern} %
```

Seach a list of possibilities:

```
483 \MLX@@detectone{AccanthisADFStdNoThree}{accanthis}{accanthis}%
484 \MLX@@detectone{AccanthisADFStdNo3}{accanthis}{accanthis}%
485 \MLX@@detectone{Alegreya}{Alegreya}{alegreya}%
486 \MLX@@detectone{AlegreyaSans}{AlegreyaSans}{alegreya} %
```

```
487 \MLX@@detectone{AlgolRevived}{algolrevived}{algolrevived}%
488 \MLX@@detectone{uaq}{antiqua}{baskerville}%
489 \MLX@@detectone{antp}{antpolt}{antpolt}%
490 \MLX@@detectone{AntykwaPoltawskiego}{antpolt}{antpolt}%
491 \MLX@@detectone{antt}{anttor}{antpolt}%%%
492 \MLX@@detectone{AntykwaTorunska}{anttor}{antpolt}%
493 \MLX@@detectone{ArchivZero-OsF}{Archiv0}{helvetica}%
494 \MLX@@detectone{Archiv0(0)}{Archiv0}{helvetica}%
495 \MLX@@detectone{fav}{arev}{vera}%
496 \MLX@@detectone{Arimo}{Arimo}{helvetica}%
497 \MLX@@detectone{atkinsn-LF}{Atkinson Hyperlegible}{helvetica}%
498 \MLX@@detectone{AtkinsonHyperlegible(0)}{Atkinson Hyperlegible}{helvetica}%
499 \MLX@@detectone{pag}{Avant Garde}{avantgarde}%
500 \MLX@@detectone{qag}{tgadventor}{avantgarde}%
501 \MLX@@detectone{ybv}{baskervald}{baskerville}%
502 \MLX@@detectone{ybwv}{baskervald}{baskerville}%
503 \MLX@@detectone{Baskervaldx}{Baskervaldx}{baskerville}%
504 \MLX@@detectone{BaskervilleF}{baskervillef}{baskerville}%
505 \MLX@@detectone{fve}{beraserif}{vera}%
506 \MLX@@detectone{fvs}{berasans}{verasans}%
507 \MLX@@detectone{ybd}{berenis}{berenis}%
508 \MLX@@detectone{ybd2}{berenis}{berenis}%
509 \MLX@@detectone{ybd2j}{berenis}{berenis}%
510 \MLX@@detectone{ybdj}{berenis}{berenis}%
511 \MLX@@detectone{BerenisADFPro}{berenis}{berenis}%
512 \MLX@@detectone{LinuxBiolinumT}{biolinum}{helvetica}%
513 \MLX@@detectone{Cabin}{Cabin}{helvetica}%
514 \MLX@@detectone{CabinCondensed}{CabinCondensed}{helvetica}%
515 \MLX@@detectone{Caladea}{caladea}{baskerville}%
516 \MLX@@detectone{cantarell}{cantarell}{helvetica}%
517 \MLX@@detectone{Crlt}{Carlito}{crimson}%
518 \MLX@@detectone{Carlito}{Carlito}{crimson}%
519 \MLX@@detectone{charssil}{CharisSIL}{times}%
520 \MLX@@detectone{CharisSIL}{CharisSIL}{times}%
521 \MLX@@detectone{mdbch}{mdbch - Math Design Bitstream Charter}{charter}%
522 \MLX@@detectone{Chivo}{Chivo}{helvetica}%
523 \MLX@@detectone{ClearSans}{Clear Sans}{helvetica}%
524 \MLX@@detectone{Cochineal}{cochineal}{baskerville}%
525 \MLX@@detectone{Coelacanth}{coelacanth}{coelacanth}%
526 \MLX@@detectone{comfortaa}{comfortaa}{avantgarde}%
527 \MLX@@detectone{ComicNeue}{comicneue}{avantgarde}%
528 \MLX@@detectone{cmbr}{Computer Modern Bright}{lmodern}%
529 \MLX@@detectone{lcmss}{Computer Modern Sans Quote}{lmodern}%
530 \MLX@@detectone{cmr}{Computer Modern Roman}{lmodern}%
531 \MLX@@detectone{cmss}{Computer Modern Sans}{lmodernsans}%
532 \MLX@@detectone{ccr}{concmath}{lmodern}%
533 \MLX@@detectone{CormorantGaramond}{CormorantGaramond}{garamond}%
534 \MLX@@detectone{Crimson}{crimson}{crimson}%
535 \MLX@@detectone{CrimsonPro}{CrimsonPro}{crimson}%
536 \MLX@@detectone{cpr}{Cuprum}{utopia}%
537 \MLX@@detectone{Cuprum(0)}{Cuprum}{utopia}%
538 \MLX@@detectone{cyklop}{Cyklop}{lmodern}%
539 \MLX@@detectone{DejaVuSerif}{DejaVuSerif}{vera}%
540 \MLX@@detectone{DejaVuSerifCondensed}{DejaVuSerif Condensed}{vera}%
```

```
541 \MLX@@detectone{DejaVuSans}{DejaVuSans}{verasans}%
542 \MLX@@detectone{drm}{DRM}{lmodern}%
543 \MLX@@detectone{droidserif}{Droid Serif}{droidserif}%%
544 \MLX@@detectone{droidsans}{Droid Sans}{droidsans}%%
545 \MLX@@detectone{DroidSerif}{Droid Serif}{droidserif}%%
546 \MLX@@detectone{DroidSans}{Droid Sans}{droidsans}%%
547 \MLX@@detectone{EBGaramond}{EB Garamond}{garamond}%
548 \MLX@@detectone{EBGaramond12}{EB Garamond}{garamond}%
549 \MLX@@detectone{Eczar(0)}{Eczar}{times}%
550 \MLX@@detectone{erewhon}{erewhon}{utopia}%
551 \MLX@@detectone{Erewhon-Regular}{erewhon}{utopia}%
552 \MLX@@detectone{fbb}{fbb}{baskerville}%
553 \MLX@@detectone{FiraSans}{Fira Sans}{helvetica}%
554 \MLX@@detectone{FiraSansBook}{Fira Sans}{helvetica}%
555 \MLX@@detectone{FiraSansThin}{Fira Sans}{helvetica}%
556 \MLX@@detectone{FiraSansLight}{Fira Sans}{helvetica}%
557 \MLX@@detectone{FiraSansExtraLight}{Fira Sans}{helvetica}%
558 \MLX@@detectone{FiraSansUltraLight}{Fira Sans}{helvetica}%
559 \MLX@@detectone{futs}{fourier}{utopia}%
560 \MLX@@detectone{fnc}{fouriernc}{newcent}%
561 \MLX@@detectone{gentium}{gentium}{gentium}%
562 \MLX@@detectone{GentiumPlus}{gentium}{gentium}%
563 \MLX@@detectone{artemisia}{gfsartemisia}{baskerville}%
564 \MLX@@detectone{GFSArtemisia}{gfsartemisia}{baskerville}%
565 \MLX@@detectone{artemisiaeuler}{gfsartemisia}{baskerville}%
566 \MLX@@detectone{bodoni}{gfsbodoni}{bodoni}%
567 \MLX@@detectone{GFSBodoni}{gfsbodoni}{bodoni}%
568 \MLX@@detectone{udidot}{gfsdidot}{didot}%
569 \MLX@@detectone{FreeSerif}{GNU Freeserif}{times}%
570 \MLX@@detectone{FreeSans}{GNU Freesans}{helvetica}%
571 \MLX@@detectone{neohellenic}{GFS Neohellenic}{helvetica}%
572 \MLX@@detectone{GFSNeohellenic}{GFS Neohellenic}{helvetica}%
573 \MLX@@detectone{Gillius}{Gillius}{avantgarde}%
574 \MLX@@detectone{GilliusADF}{Gillius}{avantgarde}%
575 \MLX@@detectone{GilliusADFCond}{Gillius}{avantgarde}%
576 \MLX@@detectone{GilliusADFNo2}{Gillius}{avantgarde}%
577 \MLX@@detectone{GilliusADFNo2Cond}{Gillius}{avantgarde}%
578 \MLX@@detectone{Go}{Go Sans}{helvetica}%
579 \MLX@@detectone{phv}{helvet}{helvetica}%
580 \MLX@@detectone{Heuristica}{heuristica}{utopia}%
581 \MLX@@detectone{heuristica}{heuristica}{utopia}%
582 \MLX@@detectone{IbarraRealNova-LF}{Ibarra}{times}%
583 \MLX@@detectone{IbarraRealNova(0)}{Ibarra}{times}%
584 \MLX@@detectone{IMFELLEnglish}{imfellEnglish}{baskerville}%
585 \MLX@@detectone{InriaSans}{Inria Sans}{helvetica}%
586 \MLX@@detectone{InriaSerif}{Inria Serif}{baskerville}%
587 \MLX@@detectone{Inter}{Inter}{helvetica}%
588 \MLX@@detectone{iwona}{Iwona}{helvetica}%
589 \MLX@@detectone{Iwona}{Iwona}{helvetica}%
590 \MLX@@detectone{IwonaLight}{Iwona}{helvetica}%
591 \MLX@@detectone{IwonaMedium}{Iwona}{helvetica}%
592 \MLX@@detectone{IwonaHeavy}{Iwona}{helvetica}%
593 \MLX@@detectone{IwonaCond}{Iwona}{helvetica}%
594 \MLX@@detectone{IwonaCondLight}{Iwona}{helvetica}%
```

```
595 \MLX@@detectone{IwonaCondMedium}{Iwona}{helvetica}%
596 \MLX@@detectone{IwonaCondHeavy}{Iwona}{helvetica}%
597 \MLX@@detectone{Junicode}{Junicode}{times}%
598 \MLX@@detectone{mak}{kerkis}{kerkis}%
599 \MLX@@detectone{maksf}{kerkis sans}{kerkis}%
600 \MLX@@detectone{jkp}{kpfonts}{kpfonts}%
601 \MLX@@detectone{jkpf}{kpfonts}{kpfonts}%
602 \MLX@@detectone{jkfosn}{kpfonts}{kpfonts}%
603 \MLX@@detectone{jkpk}{kpfonts}{kpfonts}%
604 \MLX@@detectone{jkpkf}{kpfonts}{kpfonts}%
605 \MLX@@detectone{jkpkfosn}{kpfonts}{kpfonts}%
606 \MLX@@detectone{jkpkos}{kpfonts}{kpfonts}%
607 \MLX@@detectone{jkpkosn}{kpfonts}{kpfonts}%
608 \MLX@@detectone{jkpkvos}{kpfonts}{kpfonts}%
609 \MLX@@detectone{jkpl}{kpfonts}{kpfonts}%
610 \MLX@@detectone{jkplf}{kpfonts}{kpfonts}%
611 \MLX@@detectone{jkplfosn}{kpfonts}{kpfonts}%
612 \MLX@@detectone{jkplk}{kpfonts}{kpfonts}%
613 \MLX@@detectone{jkplkf}{kpfonts}{kpfonts}%
614 \MLX@@detectone{jkplkfosn}{kpfonts}{kpfonts}%
615 \MLX@@detectone{jkplkos}{kpfonts}{kpfonts}%
616 \MLX@@detectone{jkplkosn}{kpfonts}{kpfonts}%
617 \MLX@@detectone{jkplkvos}{kpfonts}{kpfonts}%
618 \MLX@@detectone{jkplos}{kpfonts}{kpfonts}%
619 \MLX@@detectone{jkplosn}{kpfonts}{kpfonts}%
620 \MLX@@detectone{jkplvos}{kpfonts}{kpfonts}%
621 \MLX@@detectone{jkpos}{kpfonts}{kpfonts}%
622 \MLX@@detectone{jkposn}{kpfonts}{kpfonts}%
623 \MLX@@detectone{jkpss}{kpfonts}{kpfonts}%
624 \MLX@@detectone{jkpssf}{kpfonts}{kpfonts}%
625 \MLX@@detectone{jkpssfosn}{kpfonts}{kpfonts}%
626 \MLX@@detectone{jkpssk}{kpfonts}{kpfonts}%
627 \MLX@@detectone{jkpsskf}{kpfonts}{kpfonts}%
628 \MLX@@detectone{jkpsskfosn}{kpfonts}{kpfonts}%
629 \MLX@@detectone{jkpsskos}{kpfonts}{kpfonts}%
630 \MLX@@detectone{jkpsskosn}{kpfonts}{kpfonts}%
631 \MLX@@detectone{jkpsskvos}{kpfonts}{kpfonts}%
632 \MLX@@detectone{jkpssos}{kpfonts}{kpfonts}%
633 \MLX@@detectone{jkpssosn}{kpfonts}{kpfonts}%
634 \MLX@@detectone{jkpssvos}{kpfonts}{kpfonts}%
635 \MLX@@detectone{jkptt}{kpfonts}{kpfonts}%
636 \MLX@@detectone{jkpttos}{kpfonts}{kpfonts}%
637 \MLX@@detectone{jkpttosn}{kpfonts}{kpfonts}%
638 \MLX@@detectone{jkpttvos}{kpfonts}{kpfonts}%
639 \MLX@@detectone{jkpvos}{kpfonts}{kpfonts}%
640 \MLX@@detectone{jkpx}{kpfonts}{kpfonts}%
641 \MLX@@detectone{jkpxf}{kpfonts}{kpfonts}%
642 \MLX@@detectone{jkpxfosn}{kpfonts}{kpfonts}%
643 \MLX@@detectone{jkpxk}{kpfonts}{kpfonts}%
644 \MLX@@detectone{jkpxkf}{kpfonts}{kpfonts}%
645 \MLX@@detectone{jkpxkfosn}{kpfonts}{kpfonts}%
646 \MLX@@detectone{jkpxkos}{kpfonts}{kpfonts}%
647 \MLX@@detectone{jkpxkosn}{kpfonts}{kpfonts}%
648 \MLX@@detectone{jkpxkvos}{kpfonts}{kpfonts}%
```

```
649 \MLX@@detectone{jkpxos}{kpfonts}{kpfonts}%
650 \MLX@@detectone{jkpxosn}{kpfonts}{kpfonts}%
651 \MLX@@detectone{jkpxvos}{kpfonts}{kpfonts}%
652 \MLX@@detectone{JosefinSans}{Josefin}{lmodern}%
653 \MLX@@detectone{kurier}{Kurier}{helvetica}%
654 \MLX@@detectone{Kurier}{Kurier}{helvetica}%
655 \MLX@@detectone{KurierLight}{Kurier}{helvetica}%
656 \MLX@@detectone{KurierMedium}{Kurier}{helvetica}%
657 \MLX@@detectone{KurierHeavy}{Kurier}{helvetica}%
658 \MLX@@detectone{KurierCond}{Kurier}{helvetica}%
659 \MLX@@detectone{KurierCondLight}{Kurier}{helvetica}%
660 \MLX@@detectone{KurierCondMedium}{Kurier}{helvetica}%
661 \MLX@@detectone{KurierCondHeavy}{Kurier}{helvetica}%
662 \MLX@@detectone{lato}{Lato}{helvetica}%
663 \MLX@@detectone{Lato}{Lato}{helvetica}%
664 \MLX@@detectone{lmr}{lmodern}{lmodern}%
665 \MLX@@detectone{mlmr}{MLModern}{lmodern}%
666 \MLX@@detectone{mlmss}{MLModern}{lmodern}%
667 \MLX@@detectone{lmss}{lmodern sans}{lmodernsans}%
668 \MLX@@detectone{lmssq}{lmodern sans}{lmodernsans}%
669 \MLX@@detectone{LatinModernRoman}{Latin Modern Roman}{lmodern}%
670 \MLX@@detectone{LatinModernSans}{Latin Modern Sans}{lmodernsans}%
671 \MLX@@detectone{LinuxLibertineT}{libertine}{libertine}%
672 \MLX@@detectone{LinLibertine}{libertine}{libertine}%
673 \MLX@@detectone{LinBiolinum}{libertine}{helvetica}%
674 \MLX@@detectone{LibertinusSerif}{libertinus-type1}{libertinus}%
675 \MLX@@detectone{LibertinusSans}{libertinus-type1}{helvetica}%
676 \MLX@@detectone{libertinusserif}{libertinus-otf}{libertinus}%
677 \MLX@@detectone{libertinussans}{libertinus-otf}{helvetica}%
678 \MLX@@detectone{LibreBskvl}{librebaskerville}{baskerville}%
679 \MLX@@detectone{LibreBaskerville}{librebaskerville}{baskerville}%
680 \MLX@@detectone{LibreBodoni}{LibreBodoni}{librebodoni}%
681 \MLX@@detectone{LibreCaslonText}{Libre Caslon}{baskerville}%
682 \MLX@@detectone{LibreCsln}{Libre Caslon}{baskerville}%
683 \MLX@@detectone{ly}{libris}{avantgarde}%
684 \MLX@@detectone{l1cmss}{LX Fonts}{avantgarde}%
685 \MLX@@detectone{ptm}{mathptmx}{times}%
686 \MLX@@detectone{ppl}{mathpazo}{palatino}%
687 \MLX@@detectone{bch}{mdbch}{charter}%
688 \MLX@@detectone{mdput}{mdput - Math Design Utopia}{utopia}%
689 \MLX@@detectone{mdugm}{mdugm - Math Design URW Garamond}{baskerville}%
690 \MLX@@detectone{Merriwthr}{merriweather}{merriweather}%
691 \MLX@@detectone{MerriwthrSans}{merriweather}{merriweather}%
692 \MLX@@detectone{Merriweather}{merriweather}{merriweather}%
693 \MLX@@detectone{MerriweatherSans}{merriweather}{merriweather}%
694 \MLX@@detectone{MintSpirit}{Mint Spirit}{avantgarde}%
695 \MLX@@detectone{MintSpiritNoTwo}{Mint Spirit No 2}{avantgarde}%
696 \MLX@@detectone{MintSpiritNo2}{Mint Spirit No 2}{avantgarde}%
697 \MLX@@detectone{Montserrat}{Montserrat}{helvetica}%
698 \MLX@@detectone{MontserratAlternates}{Montserrat}{helvetica}%
699 \MLX@@detectone{pnc}{newcent}{newcent}%
700 \MLX@@detectone{zpltlf}{newpxtext}{palatino}%
701 \MLX@@detectone{minntx}{newtxtext}{times}%
702 \MLX@@detectone{ntxtlf}{newtxtext}{times}%
```

```
703 \MLX@@detectone{nimbussans}{nimbussans}{helvetica}%
704 \MLX@@detectone{NimbusSans}{nimbusserif}{helvetica}%
705 \MLX@@detectone{NimbusSerif}{nimbusserif}{times}%
706 \MLX@@detectone{NimbusSansL}{nimbussans}{helvetica}%
707 \MLX@@detectone{ztm}{nimbusserif}{times}%
708 \MLX@@detectone{zhv}{nimbussans}{helvetica}%
709 \MLX@@detectone{NotoSerif}{noto}{noto}%
710 \MLX@@detectone{NotoSans}{noto}{noto}%
711 \MLX@@detectone{Nunito-T0sF}{Nunito}{helvetica}%
712 \MLX@@detectone{Nunito(0)}{Nunito}{helvetica}%
713 \MLX@@detectone{OldStandard}{Old Standard}{didot}%
714 \MLX@@detectone{fosj}{opensans}{avantgarde}%
715 \MLX@@detectone{opensans}{opensans}{avantgarde}%
716 \MLX@@detectone{OpenSans}{Open Sans}{avantgarde}%
717 \MLX@@detectone{Zeroswald}{Oswald}{utopia}%
718 \MLX@@detectone{Ovrlck}{Overlock}{avantgarde}% bug with XeLaTeX%
719 \MLX@@detectone{Overlock}{Overlock}{avantgarde}% bug with XeLaTeX%
720 \MLX@@detectone{panr}{pandora}{pandora}%
721 \MLX@@detectone{pss}{pandora}{pandora}%
722 \MLX@@detectone{PTSerif}{paratype}{paratype}%
723 \MLX@@detectone{PTSans}{paratype}{paratype}%
724 \MLX@@detectone{PTSansNarrow}{paratype}{paratype}%
725 \MLX@@detectone{IBMPlexSerif}{plex-serif}{plexserif}%
726 \MLX@@detectone{IBMPlexSans}{plex-sans}{plexsans}%
727 \MLX@@detectone{pxr}{pxfonts}{palatino}%
728 \MLX@@detectone{pxss}{pxfonts}{helvetica}%
729 \MLX@@detectone{Quattro}{quattrocento}{quattrocento}%
730 \MLX@@detectone{QuattroSans}{quattrocento}{quattrocento}%
731 \MLX@@detectone{Quattrocento}{quattrocento}{quattrocento}%
732 \MLX@@detectone{QuattrocentoSans}{quattrocento}{quattrocento}%
733 \MLX@@detectone{Raleway}{raleway}{helvetica}%
734 \MLX@@detectone{Roboto}{roboto}{helvetica}%
735 \MLX@@detectone{RobotoSlab}{roboto}{roboto}%
736 \MLX@@detectone{RobotoCondensed}{roboto}{helvetica}%
737 \MLX@@detectone{yrd}{romande}{baskerville}%
738 \MLX@@detectone{yrda}{romande}{baskerville}%
739 \MLX@@detectone{yrdw}{romande}{baskerville}% todo swash style%
740 \MLX@@detectone{yrdaw}{romande}{baskerville}% todo swash style%
741 \MLX@@detectone{Shobhika}{Shobhika}{paratype}%
742 \MLX@@detectone{SourceSerifPro}{sourceserifpro}{sourcereserifpro}%
743 \MLX@@detectone{SourceSansPro}{sourcesanspro}{sourcesanspro}%
744 \MLX@@detectone{SticksTooText}{stickstootext}{times}%
745 \MLX@@detectone{stix}{stix}{times}%
746 \MLX@@detectone{stix2}{stix2}{times}%
747 \MLX@@detectone{STIXTwoText}{stix2}{times}%
748 \MLX@@detectone{pbk}{bookman}{bookman}%
749 \MLX@@detectone{qbk}{tgbonum}{bookman}%
750 \MLX@@detectone{qhv}{tgheros}{helvetica}%
751 \MLX@@detectone{qpl}{tgpagella}{palatino}%
752 \MLX@@detectone{qcs}{tgscola}{newcent}%
753 \MLX@@detectone{qtm}{tgtermes}{times}%
754 \MLX@@detectone{TeXGyreAdventor}{TeX Gyre Adventor}{avantgarde}%
755 \MLX@@detectone{TeXGyreBonum}{TeX Gyre Bonum}{bookman}%
756 \MLX@@detectone{TeXGyreHeros}{TeX Gyre Heros}{helvetica}%
```

```

757 \MLX@@detectone{TeXGyrePagella}{TeX Gyre Pagella}{palatino}%
758 \MLX@@detectone{TeXGyreSchola}{TeX Gyre Schola}{newcent}%
759 \MLX@@detectone{TeXGyreTermes}{TeX Gyre Termes}{times}%
760 \MLX@@detectone{txr}{txfonts}{times}%
761 \MLX@@detectone{txss}{txfonts}{times}%
762 \MLX@@detectone{UniversalisADFStd}{Universalis ADF Std}{crimson}%
763 \MLX@@detectone{ugq}{URW Grotesk}{crimson}%
764 \MLX@@detectone{put}{utopia}{utopia}%
765 \MLX@@detectone{yvt}{venturis}{venturis}%
766 \MLX@@detectone{yvtj}{venturis}{venturis}%
767 \MLX@@detectone{yvtw}{venturis}{venturis}%
768 \MLX@@detectone{yvtjw}{venturis}{venturis}%
769 \MLX@@detectone{yvtaw}{venturis}{venturis}%
770 \MLX@@detectone{yvtajw}{venturis}{venturis}%
771 \MLX@@detectone{yv1}{venturissans}{venturis}%
772 \MLX@@detectone{yv2}{venturis2}{venturis}%
773 \MLX@@detectone{yv3}{venturissans2}{venturis}%
774 \MLX@@detectone{yvo}{venturisold}{venturis}%
775 \MLX@@detectone{yvoa}{venturisold}{venturis}%
776 \MLX@@detectone{XCharter}{XCharter}{charter}%
777 \MLX@@detectone{XITS}{XITS}{times}%

```

Warning if font was not found:

```

778 \ifbool{\MLX@@foundfont}%
779   {}%
780   {%
781     \PackageWarningNoLine{metalogox}%
782     {%
783       Did not find font \MLX@@thisfont.\MessageBreak
784       To improve \string\LaTeX, and related logos:\MessageBreak%
785       \string\usepackage[option]{metalogox}\MessageBreak%
786       Common options: times, bookman for serif,\MessageBreak%
787       helvetica, avantgarde for sans%
788     }%
789   }%
790 }

```

3.5 Option declaration

```

791 \DeclareOption*{%
792   \adjustlogos{\CurrentOption}%
793 }

```

3.6 Default settings

Adjust according to the text body font, if detected, or use defaults otherwise:

```
794 \autoadjustlogos*
```

3.7 Option trigger

Any metalogox package option will next override the above settings.

```
795 \ProcessOptions\relax
```

3.8 Support for the **hologo** and **hvlogos** packages

If **hologo** is used, a few macros are defined to use metalogo kerning. (**hvlogos** uses **hologo**, so is also supported.)

```
796 \AtBeginDocument{
797
798 \IfPackageLoadedTF{hologo}
799 {
800 \def\HoLogo@TeX#1{\TeX}
801
802 \def\HoLogo@La#1{%
803   \x@l@everylogo
804   \kern\xl@kern@La@La
805   {\ifxetex
806     \XeTeXuseglyphmetrics@ne
807   \fi
808   \sbox{z@ T%
809   \sbox@ne{\xl@LaTeX@a}%
810   \vbox to\ht{z@{%
811     \hbox{%
812       \ltx@sh@ft{\ht{z@}%
813       \xl@sh@ft{\ht@ne}%
814       \xl@LaTeX@a
815       \xl@sh@ft{\ht{z@}%
816       \ltx@sh@ft{\ht@ne}}%
817     \vss}%
818   }%
819
820 \def\HoLogo@LaTeX#1{\HoLogo@La{La}\kern\xl@kern@LaTeX@aT\TeX}
821
822 \def\HoLogo@LaTeXe#1{%
823   \hologo{LaTeX}%
824   \kern\xl@kern@LaTeXe@Xii%
825   \hbox{%
826     \HOLOGO@MathSetup
827     2%
828     ${}_{\textstyle \texttt{\textbackslash textstyle\textbackslash varepsilon}}$%
829   }%
830
831
832 \def\HoLogo@LaTeXTeX#1{%
833   (%
834   \kern\xl@kern@LaTeX@aT
835   \hologo{La}%
836 }
```

```
836     \kern\xl@kern@LaTeX@aT
837   )%
838     \kern\xl@kern@LaTeX@aT
839   \hologo{TeX}%
840 }
841 \expandafter\let\csname HoLogo@(La)TeX\endcsname\HoLogo@LaTeXTeX
842
843 \def\HoLogo@XeTeX#1{\Xe\kern\xl@kern@XeTeX@eT\TeX}
844
845 \def\HoLogo@XeLaTeX#1{\Xe\kern\xl@kern@XeLaTeX@eL\LaTeX}
846
847 }
848 {}% hologo not loaded
849
850 }% AtBeginDocument
```

A Change History

v1.00	Inria, Inter, MLModern, Nunito, Oswald.	1
General: 2019/01/20 Initial version.		1
v1.01	Improved TOC change log and index entries.	1
General: 2023/01/03	1	
Docs adjusted for <code>dtxdescribe</code>	1	
Updated L ^A T _E X Font Catalog website.	1	
v1.02	\autoadjustlogos: Updated many fonts for changed family names.	18
General: 2024/01/12	1	
Updated contact info.	1	
v1.03	Warning if font was not found.	17
General: 2024/01/19	1	
Added Atkinson Hyperlegible, Charis SIL, Cuprum, Eczar, Ibarra,		
v1.04	\autoadjustlogos*: Updated many fonts for changed family names.	18
General: 2024/01/26	1	
Added support for <code>hologo</code> , <code>hvlogos</code>	25	

B Index

A	D
accanthis (option)	5
\adjustlogos	3, 444
alegreya (option)	5
algolrevived (option)	6
antiqua (option)	16
antpol (option)	6
anttor (option)	16
artemisia (option)	16
\autoadjustlogos	4, 474
\autoadjustlogos_*	4
avantgarde (option)	6
default (option)	5
didot (option)	8
drm (option)	16
droidsans (option)	9
droidserif (option)	9
G	H
garamond (option)	16
gentium (option)	9
helvetica (option)	9
B	I
baskerville (option)	6
berenis (option)	7
bodoni (option)	7
boisik (option)	7
bookman (option)	7
Booleans:	
MLX@ <code>foundfont</code>	17
C	K
caladea (option)	16
caslon (option)	16
charter (option)	8
cochineal (option)	16
coelacanth (option)	8
concmath (option)	16
crimson (option)	8
imfellenglish (option)	16
L	M
libertine (option)	10
libertinus (option)	10
librebodoni (option)	11
literat (option)	17
lmodern (option)	11
lmodernsans (option)	11
merriweather (option)	11
metalogox (package)	3

\MLX@detectone	<u>461</u>	plexsans	<u>13</u>
\MLX@detectvariant	<u>454</u>	plexserif	<u>13</u>
MLX@foundfont (boolean)	<u>17</u>	quattrocento	<u>13</u>
N			
newcent (option)	<u>12</u>	roboto	<u>17</u>
noto (option)	<u>12</u>	romande	<u>17</u>
O			
Options:			
accanthis	<u>5</u>	tgschola	<u>16</u>
alegreya	<u>5</u>	tgtermes	<u>16</u>
algolrevived	<u>6</u>	times	<u>14</u>
antiqua	<u>16</u>	utopia	<u>14</u>
antpolt	<u>6</u>	venturis	<u>14</u>
anttor	<u>16</u>	vera	<u>15</u>
artemisia	<u>16</u>	verasans	<u>15</u>
avantgarde	<u>6</u>	P	
baskerville	<u>6</u>	Packages:	
berenis	<u>7</u>	metalogo	<u>3</u>
bodoni	<u>7</u>	palatino (option)	<u>12</u>
boisik	<u>7</u>	pandora (option)	<u>12</u>
bookman	<u>7</u>	paratype (option)	<u>13</u>
caladea	<u>16</u>	plexsans (option)	<u>13</u>
caslon	<u>16</u>	plexserif (option)	<u>13</u>
charter	<u>8</u>	Q	
cochineal	<u>16</u>	quattrocento (option)	<u>13</u>
coelacanth	<u>8</u>	R	
concmath	<u>16</u>	roboto (option)	<u>17</u>
crimson	<u>8</u>	romande (option)	<u>17</u>
default	<u>5</u>	S	
didot	<u>8</u>	sourcesanspro (option)	<u>14</u>
drm	<u>16</u>	sourceresifpro (option)	<u>14</u>
droidsans	<u>9</u>	T	
droidserif	<u>9</u>	tgbonum (option)	<u>15</u>
garamond	<u>16</u>	tgheros (option)	<u>15</u>
gentium	<u>9</u>	tgpagella (option)	<u>15</u>
helvetica	<u>9</u>	tgschola (option)	<u>16</u>
imfellenglish	<u>16</u>	tgtermes (option)	<u>16</u>
kerkis	<u>10</u>	times (option)	<u>14</u>
kpfonts	<u>10</u>	U	
libertine	<u>10</u>	utopia (option)	<u>14</u>
libertinus	<u>10</u>	V	
librebodoni	<u>11</u>	venturis (option)	<u>14</u>
literat	<u>17</u>	vera (option)	<u>15</u>
lmodern	<u>11</u>	verasans (option)	<u>15</u>
lmodernnsans	<u>11</u>		
merriweather	<u>11</u>		
newcent	<u>12</u>		
noto	<u>12</u>		
palatino	<u>12</u>		
pandora	<u>12</u>		
paratype	<u>13</u>		