

The package **nicematrix**^{*}

F. Pantigny

fpantigny@wanadoo.fr

July 4, 2021

Abstract

The LaTeX package **nicematrix** provides new environments similar to the classical environments `{tabular}`, `{array}` and `{matrix}` of `array` and `amsmath` but with extended features.

$$\begin{bmatrix} \textcolor{blue}{C_1} & \textcolor{blue}{C_2} & \cdots & \textcolor{blue}{C_n} \\ \textcolor{blue}{L_1} & a_{11} & a_{12} & \cdots & a_{1n} \\ \textcolor{blue}{L_2} & a_{21} & a_{22} & \cdots & a_{2n} \\ \vdots & \vdots & \ddots & \ddots & \vdots \\ \textcolor{blue}{L_n} & a_{n1} & a_{n2} & \cdots & a_{nn} \end{bmatrix}$$

Product	dimensions (cm)			Price
	L	l	h	
small	3	5.5	1	30
standard	5.5	8	1.5	50.5
premium	8.5	10.5	2	80
extra	8.5	10	1.5	85.5
special	12	12	0.5	70

The package **nicematrix** is entirely contained in the file `nicematrix.sty`. This file may be put in the current directory or in a `texmf` tree. However, the best is to install **nicematrix** with a TeX distribution as MiKTeX, TeXlive or MacTeX.

Remark: If you use LaTeX via Internet with, for example, Overleaf, you can upload the file `nicematrix.sty` in the repertory of your project in order to take full advantage of the latest version de **nicematrix**.¹

This package can be used with `xelatex`, `lualatex`, `pdflatex` but also by the classical workflow `latex-dvips-ps2pdf` (or Adobe Distiller). However, the file `nicematrix.dtx` of the present documentation should be compiled with XeLaTeX.

This package requires and **loads** the packages `l3keys2e`, `array`, `amsmath`, `pgfcore` and the module `shapes` of PGF (tikz, which is a layer over PGF is *not* loaded). The final user only has to load the package with `\usepackage{nicematrix}`.

The idea of **nicematrix** is to create PGF nodes under the cells and the positions of the rules of the tabular created by `array` and to use these nodes to develop new features. As usual with PGF, the coordinates of these nodes are written in the `.aux` to be used on the next compilation and that's why **nicematrix** may need **several compilations**.²

Most features of **nicematrix** may be used without explicit use of PGF or Tikz (which, in fact, is not loaded by default).

A command `\NiceMatrixOptions` is provided to fix the options (the scope of the options fixed by this command is the current TeX group: they are semi-global).

^{*}This document corresponds to the version 5.17a of **nicematrix**, at the date of 2021/07/04.

¹The latest version of the file `nicematrix.sty` may be downloaded from the SVN server of TeXLive:

<https://www.tug.org/svn/texlive/trunk/Master/texmf-dist/tex/latex/nicematrix/nicematrix.sty>

²If you use Overleaf, Overleaf will do automatically the right number of compilations.

1 The environments of this package

The package `nicematrix` defines the following new environments.

```
{NiceTabular}    {NiceArray}    {NiceMatrix}
{NiceTabular*}   {pNiceArray}   {pNiceMatrix}
                {bNiceArray}   {bNiceMatrix}
                {BNiceArray}   {BNiceMatrix}
                {vNiceArray}   {vNiceMatrix}
                {VNiceArray}   {VNiceMatrix}
```

The environments `{NiceArray}`, `{NiceTabular}` and `{NiceTabular*}` are similar to the environments `{array}`, `{tabular}` and `{tabular*}` of the package `array` (which is loaded by `nicematrix`).

The environments `{pNiceArray}`, `{bNiceArray}`, etc. have no equivalent in `array`.

The environments `{NiceMatrix}`, `{pNiceMatrix}`, etc. are similar to the corresponding environments of `amsmath` (which is loaded by `nicematrix`): `{matrix}`, `{pmatrix}`, etc.

It's recommended to use primarily the classical environments and to use the environments of `nicematrix` only when some feature provided by these environments is used (this will save memory).

All the environments of the package `nicematrix` accept, between square brackets, an optional list of `key=value` pairs. **There must be no space before the opening bracket (`[`) of this list of options.**

Important

Before the version 5.0, it was mandatory to use, for technical reasons, the letters `L`, `C` et `R` instead of `l`, `c` et `r` in the preambles of the environments of `nicematrix`. If we want to be able to go on using these letters, `nicematrix` must be loaded with the option `define-L-C-R`.

```
\usepackage[define-L-C-R]{nicematrix}
```

This key will probably be deleted in a future version of `nicematrix`.

2 The vertical space between the rows

It's well known that some rows of the arrays created by default with LaTeX are, by default, too close to each other. Here is a classical example.

```
$\begin{pmatrix}
 \frac{1}{2} & -\frac{1}{2} \\
 \frac{1}{3} & \frac{1}{4}
\end{pmatrix}
```

Inspired by the package `cellspace` which deals with that problem, the package `nicematrix` provides two keys `cell-space-top-limit` and `cell-space-bottom-limit` similar to the parameters `\cellspacetoplimit` and `\cellspacebottomlimit` of `cellspace`.

There is also a key `cell-space-limits` to set both parameters at once.

The initial value of these parameters is 0 pt in order to have for the environments of `nicematrix` the same behaviour as those of `array` and `amsmath`. However, a value of 1 pt would probably be a good choice and we suggest to set them with `\NiceMatrixOptions`.³

```
\NiceMatrixOptions{cell-space-limits = 1pt}
```

³One should remark that these parameters apply also to the columns of type `S` of `siunitx` whereas the package `cellspace` is not able to act on such columns of type `S`.

```
$\begin{pNiceMatrix}
\frac{1}{2} & -\frac{1}{2} \\
\frac{1}{3} & \frac{1}{4}
\end{pNiceMatrix}$
```

$$\begin{pmatrix} \frac{1}{2} & -\frac{1}{2} \\ \frac{1}{3} & \frac{1}{4} \end{pmatrix}$$

3 The vertical position of the arrays

The package `nicematrix` provides a option `baseline` for the vertical position of the arrays. This option takes in as value an integer which is the number of the row on which the array will be aligned.

```
$A = \begin{pNiceMatrix} [baseline=2]
\frac{1}{\sqrt{1+p^2}} & p & 1-p \\
1 & 1 & 1 \\
1 & p & 1+p
\end{pNiceMatrix}$
```

$$A = \begin{pmatrix} \frac{1}{\sqrt{1+p^2}} & p & 1-p \\ 1 & 1 & 1 \\ 1 & p & 1+p \end{pmatrix}$$

It's also possible to use the option `baseline` with one of the special values `t`, `c` or `b`. These letters may also be used absolutely like the option of the environments `{tabular}` and `{array}` of `array`. The initial value of `baseline` is `c`.

In the following example, we use the option `t` (equivalent to `baseline=t`) immediately after an `\item` of list. One should remark that the presence of a `\hline` at the beginning of the array doesn't prevent the alignment of the baseline with the baseline of the first row (with `{tabular}` or `{array}` of `array`, one must use `\firsthline`).

```
\begin{enumerate}
\item an item
\smallskip
\item \renewcommand{\arraystretch}{1.2}
$\begin{NiceArray}[t]{lcccccc}
\hline
n & 0 & 1 & 2 & 3 & 4 & 5 \\
u_n & 1 & 2 & 4 & 8 & 16 & 32
\hline
\end{NiceArray}$
\end{enumerate}
```

$$1. \begin{array}{ccccccc} n & 0 & 1 & 2 & 3 & 4 & 5 \\ u_n & 1 & 2 & 4 & 8 & 16 & 32 \end{array}$$

However, it's also possible to use the tools of `booktabs`⁴: `\toprule`, `\bottomrule`, `\midrule`, etc.

```
\begin{enumerate}
\item an item
\smallskip
\item \renewcommand{\arraystretch}{1.2}
$\begin{NiceArray}[t]{lcccccc}
\toprule
n & 0 & 1 & 2 & 3 & 4 & 5 \\
\midrule
u_n & 1 & 2 & 4 & 8 & 16 & 32
\bottomrule
\end{NiceArray}$
\end{enumerate}
```

$$2. \begin{array}{ccccccc} n & 0 & 1 & 2 & 3 & 4 & 5 \\ u_n & 1 & 2 & 4 & 8 & 16 & 32 \end{array}$$

It's also possible to use the key `baseline` to align a matrix on an horizontal rule (drawn by `\hline`). In this aim, one should give the value `line-i` where i is the number of the row following the horizontal rule.

```
\NiceMatrixOptions{cell-space-limits=1pt}
```

⁴The extension `booktabs` is *not* loaded by `nicematrix`.

```
$A=\begin{pNiceArray}{cc|cc}[baseline=line-3]
\frac{1}{A} & \frac{1}{B} & 0 & 0 \\
\frac{1}{C} & \frac{1}{D} & 0 & 0 \\
\hline
0 & A & B & \\
0 & D & D & \\
\end{pNiceArray}$
```

$$A = \left(\begin{array}{cc|cc}
\frac{1}{A} & \frac{1}{B} & 0 & 0 \\
\frac{1}{C} & \frac{1}{D} & 0 & 0 \\
\hline
0 & 0 & A & B \\
0 & 0 & D & D
\end{array} \right)$$

4 The blocks

4.1 General case

In the environments of `nicematrix`, it's possible to use the command `\Block` in order to place an element in the center of a rectangle of merged cells of the array.⁵

The command `\Block` must be used in the upper leftmost cell of the array with two arguments.

- The first argument is the size of the block with the syntax $i-j$ where i is the number of rows of the block and j its number of columns.
- If this argument is empty, its default value is `1-1`. If the number of rows is not specified, or equal to `*`, the block extends until the last row (idem for the columns).
- The second argument is the content of the block. It's possible to use `\\\` in that content to have a content on several lines. In `{NiceTabular}` the content of the block is composed in text mode whereas, in the other environments, it is composed in math mode.

Here is an example of utilisation of the command `\Block` in mathematical matrices.

```
$\begin{bNiceArray}{ccc|c}[margin]
\Block{3-3}{A} & & & 0 \\
& \hspace*{1cm} & & \vdots \\
& & & 0 \\
\hline
0 & \cdots & 0 & 0
\end{bNiceArray}$
```

$$\left[\begin{array}{ccc|c}
& & & 0 \\
& A & & \vdots \\
& & & 0 \\
\hline
0 & \cdots & 0 & 0
\end{array} \right]$$

One may wish to raise the size of the “ A ” placed in the block of the previous example. Since this element is composed in math mode, it's not possible to use directly a command like `\large`, `\Large` and `\LARGE`. That's why the command `\Block` provides an option between angle brackets to specify some TeX code which will be inserted before the beginning of the math mode.⁶

```
$\begin{bNiceArray}{ccc|c}[margin]
\Block{3-3}{\Large A} & & & 0 \\
& \hspace*{1cm} & & \vdots \\
& & & 0 \\
\hline
0 & \cdots & 0 & 0
\end{bNiceArray}$
```

$$\left[\begin{array}{ccc|c}
& & & 0 \\
& A & & \vdots \\
& & & 0 \\
\hline
0 & \cdots & 0 & 0
\end{array} \right]$$

It's possible to set the horizontal position of the block with one of the keys `l`, `c` and `r`.

⁵The spaces after a command `\Block` are deleted.

⁶This argument between angular brackets may also be used to insert a command of font such as `\bfseries` when the command `\\\` is used in the content of the block.

```
$\begin{bNiceArray}{ccc|c} [margin]
\Block[r]{3-3}<\text{\LARGE}>{A} & & & 0 \\
& \hspace*{1cm} & & \vdots \\
& & & 0 \\
\hline
0 & \cdots & 0 & 0
\end{bNiceArray}$
```

$$\left[\begin{array}{ccc|c} & & & 0 \\ & & & \vdots \\ & & & 0 \\ \hline 0 & \dots & 0 & 0 \end{array} \right]$$

In fact, the command `\Block` accepts as first optional argument (between square brackets) a list of couples key-value. The available keys are as follows:

- the keys `l`, `c` and `r` are used to fix the horizontal position of the content of the block, as explained previously;
- the key `fill` takes in as value a color and fills the block with that color;
- the key `draw` takes in as value a color and strokes the frame of the block with that color (the default value of that key is the current color of the rules of the array);
- the key `color` takes in as value a color and apply that color the content of the block but draws also the frame of the block with that color;
- the key `line-width` is the width (thickness) of the frame (this key should be used only when the key `draw` is in force);
- the key `rounded-corners` requires rounded corners (for the frame drawn by `draw` and the shape drawn by `fill`) with a radius equal to the value of that key (the default value is 4 pt⁷);
- the key `borders` provides the ability to draw only some borders of the blocks; the value of that key is a (comma-separated) list of elements covered by `left`, `right`, `top` and `bottom`;
- the keys `t` and `b` fix the base line that will be given to the block when it has a multi-line content (the lines are separated by `\backslash\backslash`);
- **New 5.15** the keys `hvlines` draws all the vertical and horizontal rules in the block.

One must remark that, by default, the commands `\Blocks` don't create space. There is exception only for the blocks mono-row and the blocks mono-column as explained just below.

In the following example, we have had to enlarge by hand the columns 2 and 3 (with the construction `wc{...}` of `array`).

```
\begin{NiceTabular}{cwc{2cm}wc{3cm}c}
rose & tulipe & marguerite & dahlia \\
violette
& \Block[draw=red,fill=[RGB]{204,204,255},rounded-corners]{2-2}
& {\text{\LARGE De très jolies fleurs}} \\
& & souci \\
pervenche & & lys \\
arum & iris & jacinthe & muguet
\end{NiceTabular}
```

rose	tulipe	marguerite	dahlia
violette			souci
pervenche			lys
arum	iris	jacinthe	muguet

De très jolies fleurs

⁷This value is the initial value of the *rounded corners* of Tikz.

4.2 The mono-column blocks

The mono-column blocks have a special behaviour.

- The natural width of the contents of these blocks is taken into account for the width of the current column.
- The specification of the horizontal position provided by the type of column (`c`, `r` or `l`) is taken into account for the blocks.
- The specifications of font specified for the column by a construction `>{...}` in the preamble of the array are taken into account for the mono-column blocks of that column (this behaviour is probably expected).

<code>\begin{NiceTabular}{@{}>{\bfseries}lr@{}} \hline</code>		
<code>\Block{2-1}{John} & 12 \\</code>	John	12
<code> & 13 \\ \hline</code>		13
<code>Steph & 8 \\ \hline</code>	Steph	8
<code>\Block{3-1}{Sarah} & 18 \\</code>		18
<code> & 17 \\</code>	Sarah	17
<code> & 15 \\ \hline</code>		15
<code>Ashley & 20 \\ \hline</code>	Ashley	20
<code>Henry & 14 \\ \hline</code>	Henry	14
<code>\Block{2-1}{Madison} & 15 \\</code>		15
<code> & 19 \\ \hline</code>	Madison	19
<code>\end{NiceTabular}</code>		

4.3 The mono-row blocks

For the mono-row blocks, the natural height and depth are taken into account for the height and depth of the current row (as does a standard `\multicolumn` of LaTeX).

4.4 The mono-cell blocks

A mono-cell block inherits all the properties of the mono-row blocks and mono-column blocks.

At first sight, one may think that there is no point using a mono-cell block. However, there are some good reasons to use such a block.

- It's possible to use the command `\\"` in a (mono-cell) block.
- It's possible to use the option of horizontal alignment of the block in derogation of the type of column given in the preamble of the array.
- It's possible do draw a frame around the cell with the key `draw` of the command `\Block` and to fill the background with rounded corners with the keys `fill` and `rounded-corners`.⁸
- It's possible to draw one or several borders of the cell with the key `borders`.

<code>\begin{NiceTabular}{cc}</code>		
<code>\toprule</code>		
<code>Writer & \Block[1]{}{year\\ of birth} \\</code>	Writer	year of birth
<code>\midrule</code>		
<code>Hugo & 1802 \\</code>	Hugo	1802
<code>Balzac & 1799 \\</code>	Balzac	1799
<code>\bottomrule</code>		
<code>\end{NiceTabular}</code>		

We recall that if the first mandatory argument of `\Block` is left blank, the block is mono-cell.⁹

⁸If one simply wishes to color the background of a unique celle, there is no point using the command `\Block`: it's possible to use the command `\cellcolor` (when the key `colortbl-like` is used).

⁹One may consider that the default value of the first mandatory argument of `\Block` is `1-1`.

4.5 Horizontal position of the content of the block

By default, the horizontal position of the content of a block is computed by using the positions of the *contents* of the columns implied in that block. That's why, in the following example, the header “First group” is correctly centered despite the instruction `!{\qquad}` in the preamble which has been used to increase the space between the columns (this is not the behaviour of `\multicolumn`).

```
\begin{NiceTabular}{@{}c!{\qquad}ccc!{\qquad}ccc@{}}
\toprule
Rank & \Block{1-3}{First group} & & & \Block{1-3}{Second group} \\
& 1A & 1B & 1C & 2A & 2B & 2C \\
\midrule
1 & 0.657 & 0.913 & 0.733 & 0.830 & 0.387 & 0.893\\
2 & 0.343 & 0.537 & 0.655 & 0.690 & 0.471 & 0.333\\
3 & 0.783 & 0.885 & 0.015 & 0.306 & 0.643 & 0.263\\
4 & 0.161 & 0.708 & 0.386 & 0.257 & 0.074 & 0.336\\
\bottomrule
\end{NiceTabular}
```

Rank	First group			Second group		
	1A	1B	1C	2A	2B	2C
1	0.657	0.913	0.733	0.830	0.387	0.893
2	0.343	0.537	0.655	0.690	0.471	0.333
3	0.783	0.885	0.015	0.306	0.643	0.263
4	0.161	0.708	0.386	0.257	0.074	0.336

New 5.17 In order to have an horizontal positionning of the content of the block computed with the limits of the columns of the LaTeX array (and not with the contents of those columns), one may use the key `L`, `R` and `C` of the command `\Block`.

5 The rules

The usual techniques for the rules may be used in the environments of `nicematrix` (excepted `\vline`). However, there is some small differences with the classical environments.

5.1 Some differences with the classical environments

5.1.1 The vertical rules

In the environments of `nicematrix`, the vertical rules specified by `|` in the preambles of the environments are never broken, even by an incomplete row or by a double horizontal rule specified by `\hline\hline` (there is no need to use `hhline`).

```
\begin{NiceTabular}{|c|c|} \hline
First & Second \\ \hline\hline
Peter \\ \hline
Mary & George\\ \hline
\end{NiceTabular}
```

First	Second
Peter	
Mary	George

However, the vertical rules are not drawn in the blocks (created by `\Block`: cf. p. 4) nor in the corners (created by the key `corner`: cf. p. 10).

If you use `booktabs` (which provides `\toprule`, `\midrule`, `\bottomrule`, etc.) and if you really want to add vertical rules (which is not in the spirit of `booktabs`), you should notice that the vertical rules drawn by `nicematrix` are compatible with `booktabs`.

```
\begin{NiceArray}{|cccc|} \toprule
a & b & c & d \\ \midrule
1 & 2 & 3 & 4 \\
1 & 2 & 3 & 4 \\ \bottomrule
\end{NiceArray}
```

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>
1	2	3	4
1	2	3	4

However, it's still possible to define a specifier (named, for instance, `I`) to draw vertical rules with the standard behaviour of `array`.

```
\newcolumntype{I}{!{\vrule}}
```

However, in this case, it is probably more clever to add a command `\OnlyMainNiceMatrix` (cf. p. 38):

```
\newcolumntype{I}{!{\OnlyMainNiceMatrix{\vrule}}}
```

5.1.2 The command `\cline`

The horizontal and vertical rules drawn by `\hline` and the specifier “|” make the array larger or wider by a quantity equal to the width of the rule (with `array` and also with `nicematrix`).

For historical reasons, this is not the case with the command `\cline`, as shown by the following example.

```
\setlength{\arrayrulewidth}{2pt}
\begin{tabular}{cccc} \hline
A&B&C&D \\ \cline{2-2}
A&B&C&D \\ \hline
\end{tabular}
```

A	B	C	D
A	<u>B</u>	C	D

In the environments of `nicematrix`, this situation is corrected (it's still possible to go to the standard behaviour of `\cline` with the key `standard-cline`).

```
\setlength{\arrayrulewidth}{2pt}
\begin{NiceTabular}{cccc} \hline
A&B&C&D \\ \cline{2-2}
A&B&C&D \\ \hline
\end{NiceTabular}
```

A	B	C	D
A	<u>B</u>	C	D

5.2 The thickness and the color of the rules

The environments of `nicematrix` provide a key `rules/width` to set the width (in fact the thickness) of the rules in the current environment. In fact, this key merely sets the value of the length `\arrayrulewidth`.

It's well known that `colortbl` provides the command `\arrayrulecolor` in order to specify the color of the rules.

With `nicematrix`, it's possible to specify the color of the rules even when `colortbl` is not loaded. For sake of compatibility, the command is also named `\arrayrulecolor`. The environments of `nicematrix` also provide a key `rules/color` to fix the color of the rules in the current environment. This key sets the value locally (whereas `\arrayrulecolor` acts globally).

```
\begin{NiceTabular}{|ccc|}[rules/color=[gray]{0.9},rules/width=1pt]
\hline
rose & tulipe & lys \\
arum & iris & violette \\
muguet & dahlia & souci \\
\hline
\end{NiceTabular}
```

rose	tulipe	lys
arum	iris	violette
muguet	dahlia	souci

If one wishes to define new specifiers for columns in order to draw vertical rules (for example with a specific color or thicker than the standard rules), he should consider the command `\OnlyMainNiceMatrix` described on page 38.

5.3 The tools of nicematrix for the rules

Here are the tools provided by `nicematrix` for the rules.

- the keys `hlines`, `vlines` and `hvlines`;
- the specifier “`!`” in the preamble (for the environments with preamble);
- the command `\Hline`.

All these tools don't draw the rules in the blocks nor in the empty corners (when the key `corners` is used).

- These blocks are:
 - the blocks created by the command `\Block`¹⁰ presented p. 4;
 - the blocks implicitely delimited by the continuous dotted lines created by `\Cdots`, `\Vdots`, etc. (cf. p. 19).
- The corners are created by the key `corners` explained below (see p. 10).

In particular, this remark explains the difference between the standard command `\hline` and the command `\Hline` provided by `nicematrix`.

5.3.1 The keys `hlines` and `vlines`

The keys `hlines` and `vlines` (which draw, of course, horizontal and vertical rules) take in as value a list of numbers which are the numbers of the rules to draw.

In fact, for the environments with delimiters (such as `{pNiceMatrix}` or `{bNiceArray}`), the key `vlines` don't draw the exterior rules (this is certainly the expected behaviour).

```
$\begin{pNiceMatrix} [vlines, rules/width=0.2pt]
1 & 2 & 3 & 4 & 5 & 6 \\
1 & 2 & 3 & 4 & 5 & 6 \\
1 & 2 & 3 & 4 & 5 & 6
\end{pNiceMatrix}$
```

$$\left(\begin{array}{c|c|c|c|c|c} 1 & 2 & 3 & 4 & 5 & 6 \\ 1 & 2 & 3 & 4 & 5 & 6 \\ 1 & 2 & 3 & 4 & 5 & 6 \end{array} \right)$$

5.3.2 The key `hvlines`

The key `hvlines` (no value) is the conjunction of the keys `hlines` and `vlines`.

```
\setlength{\arrayrulewidth}{1pt}
\begin{NiceTabular}{cccc} [hvlines, rules/color=blue]
rose & tulipe & marguerite & dahlia \\
violette & \Block[draw=red]{2-2}{\LARGE fleurs} & & souci \\
pervenche & & lys \\
arum & iris & jacinthe & muguet
\end{NiceTabular}
```

rose	tulipe	marguerite	dahlia
violette	fleurs		souci
pervenche	lys		
arum	iris	jacinthe	muguet

New 5.17 The key `hvlines-except-corners` is similar to the key `hvlines` but does not draw the rules on the horizontal and vertical borders of the array.

¹⁰ And also the command `\multicolumn` also it's recommended to use instead `\Block` in the environments of `nicematrix`.

5.3.3 The (empty) corners

The four **corners** of an array will be designed by **NW**, **SW**, **NE** and **SE** (*north west*, *south west*, *north east* and *south east*).

For each of these corners, we will call *empty corner* (or simply *corner*) the reunion of all the empty rectangles starting from the cell actually in the corner of the array.¹¹

However, it's possible, for a cell without content, to require **nicematrix** to consider that cell as not empty with the key **\NotEmpty**.

			A		
A	A	A			
	A				
	A	A	A	A	A
A	A	A	A	A	A
A	A	A	A	A	A
	A	A	A		
B			A		
		A			

In the example on the right (where B is in the center of a block of size 2×2), we have colored in blue the four (empty) corners of the array.

When the key **corners** is used, **nicematrix** computes the (empty) corners and these corners will be taken into account by the tools for drawing the rules (the rules won't be drawn in the corners). *Remark:* In the previous versions of **nicematrix**, there was only a key **hvlines-except-corners** (now considered as obsolete).

```
\NiceMatrixOptions{cell-space-top-limit=3pt}
\begin{NiceTabular}{*{6}{c}}[corners,hvlines]
& & & A \\
& & A & A & A \\
& & & A \\
& & A & A & A & A \\
A & A & A & A & A & A \\
A & A & A & A & A & A \\
& A & A & A \\
& \Block{2-2}{B} & & A \\
& & & A \\
\end{NiceTabular}
```

			A		
A	A	A			
	A				
	A	A	A	A	A
A	A	A	A	A	A
A	A	A	A	A	A
	A	A	A		
B			A		
		A			

It's also possible to provide to the key **corners** a (comma-separated) list of corners (designed by **NW**, **SW**, **NE** and **SE**).

```
\NiceMatrixOptions{cell-space-top-limit=3pt}
\begin{NiceTabular}{*{6}{c}}[corners=NE,hvlines]
1\\
1&1\\
1&2&1\\
1&3&3&1\\
1&4&6&4&1\\
& & & &1
\end{NiceTabular}
```

1					
1	1				
1	2	1			
1	3	3	1		
1	4	6	4	1	
					1

▷ The corners are also taken into account by the tools provided by **nicematrix** to color cells, rows and columns. These tools don't color the cells which are in the corners (cf. p. 12).

¹¹For sake of completeness, we should also say that a cell contained in a block (even an empty cell) is not taken into account for the determination of the corners. That behaviour is natural.

5.4 The command \diagbox

The command `\diagbox` (inspired by the package `diagbox`), allows, when it is used in a cell, to slash that cell diagonally downwards.¹²

```
$\begin{NiceArray}{*{5}{c}}[hvlines]
\diagbox{x}{y} & e & a & b & c \\
e & e & a & b & c \\
a & a & e & c & b \\
b & b & c & e & a \\
c & c & b & a & e
\end{NiceArray}$
```

x	y	e	a	b	c
e		e	a	b	c
a		a	e	c	b
b		b	c	e	a
c		c	b	a	e

It's possible to use the command `\diagbox` in a `\Block`.

5.5 Dotted rules

In the environments of the package `nicematrix`, it's possible to use the command `\hdottedline` (provided by `nicematrix`) which is a counterpart of the classical commands `\hline` and `\hdashline` (the latter is a command of `arydshln`).

```
\begin{pNiceMatrix}
1 & 2 & 3 & 4 & 5 \\
\hdottedline
6 & 7 & 8 & 9 & 10 \\
11 & 12 & 13 & 14 & 15
\end{pNiceMatrix}
```

$$\left(\begin{array}{ccccc} 1 & 2 & 3 & 4 & 5 \\ \cdots & \cdots & \cdots & \cdots & \cdots \\ 6 & 7 & 8 & 9 & 10 \\ 11 & 12 & 13 & 14 & 15 \end{array} \right)$$

In the environments with an explicit preamble (like `{NiceTabular}`, `{NiceArray}`, etc.), it's possible to draw a vertical dotted line with the specifier ":".

```
\left(\begin{NiceArray}{cccc:c}
1 & 2 & 3 & 4 & 5 \\
6 & 7 & 8 & 9 & 10 \\
11 & 12 & 13 & 14 & 15
\end{NiceArray}\right)
```

$$\left(\begin{array}{ccccc} 1 & 2 & 3 & 4 & : 5 \\ 6 & 7 & 8 & 9 & : 10 \\ 11 & 12 & 13 & 14 & : 15 \end{array} \right)$$

It's possible to change in `nicematrix` the letter used to specify a vertical dotted line with the option `letter-for-dotted-lines` available in `\NiceMatrixOptions`. Thus released, the letter ":" can be used otherwise (for example by the package `arydshln`¹³).

Remark: In the package `array` (on which the package `nicematrix` relies), horizontal and vertical rules make the array larger or wider by a quantity equal to the width of the rule¹⁴. In `nicematrix`, the dotted lines drawn by `\hdottedline` and ":" do likewise.

6 The color of the rows and columns

6.1 Use of `colortbl`

We recall that the package `colortbl` can be loaded directly with `\usepackage{colortbl}` or by loading `xcolor` with the key `table`: `\usepackage[table]{xcolor}`.

Since the package `nicematrix` is based on `array`, it's possible to use `colortbl` with `nicematrix`.

However, there is two drawbacks:

¹²The author of this document considers that type of construction as graphically poor.

¹³However, one should remark that the package `arydshln` is not fully compatible with `nicematrix`.

¹⁴In fact, with `array`, this is true only for `\hline` and ":" but not for `\cline`: cf p. 8

- The package `colortbl` patches `array`, leading to some incompatibilities (for instance with the command `\hdotsfor`).
 - The package `colortbl` constructs the array row by row, alternating colored rectangles, rules and contents of the cells. The resulting PDF is difficult to interpret by some PDF viewers and may lead to artefacts on the screen.
 - Some rules seem to disappear. This is because many PDF viewers give priority to graphical element drawn posteriorly (which is in the spirit of the “painting model” of PostScript and PDF). Concerning this problem, MuPDF (which is used, for instance, by SumatraPDF) gives better results than Adobe Reader).
 - A thin white line may appear between two cells of the same color. This phenomenon occurs when each cell is colored with its own instruction `fill` (the PostScript operator `fill` noted `f` in PDF). This is the case with `colortbl`: each cell is colored on its own, even when `\columncolor` or `\rowcolor` is used.
- As for this phenomenon, Adobe Reader gives better results than MuPDF.

The package `nicematrix` provides tools to avoid those problems.

6.2 The tools of `nicematrix` in the `\CodeBefore`

The package `nicematrix` provides some tools (independent of `colortbl`) to draw the colored panels first, and, then, the content of the cells and the rules. This strategy is more conform to the “painting model” of the formats PostScript and PDF and is more suitable for the PDF viewers. However, it requires several compilations.¹⁵

The extension `nicematrix` provides a key `code-before` for some code that will be executed before the drawing of the tabular.

An alternative syntax is provided: it’s possible to put the content of that `code-before` between the keywords `\CodeBefore` and `\Body` at the beginning of the environment.

```
\begin{pNiceArray}{preamble}
\CodeBefore
instructions of the code-before
\Body
contents of the environnement
\end{pNiceArray}
```

New commands are available in that `\CodeBefore`: `\cellcolor`, `\rectanglecolor`, `\rowcolor`, `\columncolor`, `\rowcolors`, `\chessboardcolors` and `arraycolor`.¹⁶

All these commands accept an optional argument (between square brackets and in first position) which is the color model for the specification of the colors.

New 5.15 These commands don’t color the cells which are in the “corners” if the key `corners` is used. This key has been described p. 10.

- The command `\cellcolor` takes its name from the command `\cellcolor` of `colortbl`.
This command takes in as mandatory arguments a color and a list of cells, each of which with the format $i-j$ where i is the number of the row and j the number of the column of the cell.

¹⁵If you use Overleaf, Overleaf will do automatically the right number of compilations.

¹⁶Remark that, in the `\CodeBefore`, PGF/Tikz nodes of the form “ $(i-l|j)$ ” are also available to indicate the position to the potential rules: cf. p. 36.

```
\begin{NiceTabular}{|c|c|c|c|}
\CodeBefore
    \cellcolor[HTML]{FFFF88}{3-1,2-2,1-3}
\Body
\hline
a & b & c & \\
e & f & g & \\
h & i & j & \\
\end{NiceTabular}
```

a	b	c
e	f	g
h	i	j

- The command `\rectanglecolor` takes three mandatory arguments. The first is the color. The second is the upper-left cell of the rectangle and the third is the lower-right cell of the rectangle.

```
\begin{NiceTabular}{|c|c|c|c|}
\CodeBefore
    \rectanglecolor{blue!15}{2-2}{3-3}
\Body
\hline
a & b & c & \\
e & f & g & \\
h & i & j & \\
\end{NiceTabular}
```

a	b	c
e	f	g
h	i	j

- The command `\arraycolor` takes in as mandatory argument a color and color the whole tabular with that color (excepted the potential exterior rows and columns: cf. p. 17). It's only a particular case of `\rectanglecolor`.

- The command `\chessboardcolors` takes in as mandatory arguments two colors and it colors the cells of the tabular in quincunx with these colors.

```
$\begin{pNiceMatrix}[r,margin]
\CodeBefore
    \chessboardcolors{red!15}{blue!15}
\Body
1 & -1 & 1 & \\
-1 & 1 & -1 & \\
1 & -1 & 1 & \\
\end{pNiceMatrix}$
```

$$\begin{pmatrix} 1 & -1 & 1 \\ -1 & 1 & -1 \\ 1 & -1 & 1 \end{pmatrix}$$

We have used the key `r` which aligns all the columns rightwards (cf. p. 31).

- The command `\rowcolor` takes its name from the command `\rowcolor` of `colortbl`. Its first mandatory argument is the color and the second is a comma-separated list of rows or interval of rows with the form $a-b$ (an interval of the form $a-$ represent all the rows from the row a until the end).

```
$\begin{NiceArray}{lll}[hvlines]
\CodeBefore
    code-before = \rowcolor{red!15}{1,3-5,8-}
\Body
a_1 & b_1 & c_1 \\
a_2 & b_2 & c_2 \\
a_3 & b_3 & c_3 \\
a_4 & b_4 & c_4 \\
a_5 & b_5 & c_5 \\
a_6 & b_6 & c_6 \\
a_7 & b_7 & c_7 \\
a_8 & b_8 & c_8 \\
a_9 & b_9 & c_9 \\
a_{10} & b_{10} & c_{10} \\
\end{NiceArray}$
```

a_1	b_1	c_1
a_2	b_2	c_2
a_3	b_3	c_3
a_4	b_4	c_4
a_5	b_5	c_5
a_6	b_6	c_6
a_7	b_7	c_7
a_8	b_8	c_8
a_9	b_9	c_9
a_{10}	b_{10}	c_{10}

- The command `\columncolor` takes its name from the command `\columncolor` of `colortbl`. Its syntax is similar to the syntax of `\rowcolor`.
- The command `\rowcolors` (with a *s*) takes its name from the command `\rowcolors` of `xcolor`¹⁷. The *s* emphasizes the fact that there is *two* colors. This command colors alternately the rows of the tabular with the two colors (provided in second and third argument), beginning with the row whose number is given in first (mandatory) argument.

In fact, the first (mandatory) argument is, more generally, a comma separated list of intervals describing the rows involved in the action of `\rowcolors` (an interval of the form *i*- describes in fact the interval of all the rows of the tabular, beginning with the row *i*).

The last argument of `\rowcolors` is an optional list of pairs key-value (the optional argument in the first position corresponds to the colorimetric space). The available keys are `cols`, `restart` and `respect-blocks`.

- The key `cols` describes a set of columns. The command `\rowcolors` will color only the cells of these columns. The value is a comma-separated list of intervals of the form *i-j* (where *i* or *j* may be replaced by *).
- With the key `restart`, each interval of rows (specified by the first mandatory argument) begins with the same color.¹⁸
- With the key `respect-blocks` the “rows” alternately colored may extend over several rows if they have to incorporate blocks (created with the command `\Block`: cf. p. 4).

```
\begin{NiceTabular}{clr}[hvlines]
\CodeBefore
  \rowcolors[gray]{2}{0.8}{}[cols=2-3,restart]
\Body
\Block{1-*}{Results} \\
John & 12 \\
Stephen & 8 \\
Sarah & 18 \\
Ashley & 20 \\
Henry & 14 \\
Madison & 15
\end{NiceTabular}
```

Results		
A	John	12
	Stephen	8
B	Sarah	18
	Ashley	20
	Henry	14
	Madison	15

```
\begin{NiceTabular}{lr}[hvlines]
\CodeBefore
  \rowcolors{1}{blue!10}{}[respect-blocks]
\Body
\Block{2-1}{John}   & 12 \\
                      & 13 \\
Steph                & 8 \\
\Block{3-1}{Sarah}   & 18 \\
                      & 17 \\
                      & 15 \\
Ashley               & 20 \\
Henry                & 14 \\
\Block{2-1}{Madison} & 15 \\
                      & 19
\end{NiceTabular}
```

John	12
	13
Steph	8
	18
Sarah	17
	15
Ashley	20
Henry	14
Madison	15
	19

¹⁷The command `\rowcolors` of `xcolor` is available when `xcolor` is loaded with the option `table`. That option also loads the package `colortbl`.

¹⁸Otherwise, the color of a given row relies only upon the parity of its absolute number.

We recall that all the color commands we have described don't color the cells which are in the "corners". In the following example, we use the key `corners` to require the determination of the corner *north east* (NE).

```
\begin{NiceTabular}{ccccccc}[corners=NE,margin,hvlines,first-row,first-col]
\CodeBefore
    \rowcolors{1}{blue!15}{}
\Body
    & 0 & 1 & 2 & 3 & 4 & 5 & 6 \\
0 & 1 & \\ 
1 & 1 & 1 & \\ 
2 & 1 & 2 & 1 & \\ 
3 & 1 & 3 & 3 & 1 & \\ 
4 & 1 & 4 & 6 & 4 & 1 & 1 & \\ 
5 & 1 & 5 & 10 & 10 & 5 & 1 & \\ 
6 & 1 & 6 & 15 & 20 & 15 & 6 & 1 & \\ 
\end{NiceTabular}
```

	0	1	2	3	4	5	6
0	1						
1		1					
2	1	2	1				
3	1	3	3	1			
4	1	4	6	4	1		
5	1	5	10	10	5	1	
6	1	6	15	20	15	6	1

One should remark that all the previous commands are compatible with the commands of `booktabs` (`\toprule`, `\midrule`, `\bottomrule`, etc). However, `booktabs` is not loaded by `nicematrix`.

```
\begin{NiceTabular}{c}[lSSSS]
\CodeBefore
    \rowcolor{red!15}{1-2}
    \rowcolors{3}{blue!15}{}
\Body
\toprule
\Block{2-1}{Product} &
\Block{1-3}{dimensions (cm)} & & &
\Block{2-1}{\rotate Price} \\
\cmidrule(r1){2-4}
& L & 1 & h & \\
\midrule
small & 3 & 5.5 & 1 & 30 \\
standard & 5.5 & 8 & 1.5 & 50.5 \\
premium & 8.5 & 10.5 & 2 & 80 \\
extra & 8.5 & 10 & 1.5 & 85.5 \\
special & 12 & 12 & 0.5 & 70 \\
\bottomrule
\end{NiceTabular}
```

We have used the type of column `S` of `siunitx`.

Product	dimensions (cm)			Price
	L	1	h	
small	3	5.5	1	30
standard	5.5	8	1.5	50.5
premium	8.5	10.5	2	80
extra	8.5	10	1.5	85.5
special	12	12	0.5	70

6.3 Color tools with the syntax of `colortbl`

It's possible to access the preceding tools with a syntax close to the syntax of `colortbl`. For that, one must use the key `colortbl-like` in the current environment.¹⁹

There are three commands available (they are inspired by `colortbl` but are *independent* of `colortbl`):

- `\cellcolor` which colorizes a cell;
- `\rowcolor` which must be used in a cell and which colorizes the end of the row;
- `\columncolor` which must be used in the preamble of the environment with the same syntax as the corresponding command of `colortbl` (however, unlike the command `\columncolor` of `colortbl`, this command `\columncolor` can appear within another command, itself used in the preamble of the array).

¹⁹Up to now, this key is *not* available in `\NiceMatrixOptions`.

```
\NewDocumentCommand { \Blue } { } { \columncolor{blue!15} }
\begin{NiceTabular}[colortbl-like]{>{\Blue}c>{\Blue}cc}
\toprule
\rowcolor{red!15}
Last name & First name & Birth day \\
\midrule
Achard & Jacques & 5 juin 1962 \\
Lefebvre & Mathilde & 23 mai 1988 \\
Vanesse & Stephany & 30 octobre 1994 \\
Dupont & Chantal & 15 janvier 1998 \\
\bottomrule
\end{NiceTabular}
```

Last name	First name	Birth day
Achard	Jacques	5 juin 1962
Lefebvre	Mathilde	23 mai 1988
Vanesse	Stephany	30 octobre 1994
Dupont	Chantal	15 janvier 1998

7 The width of the columns

In the environments with an explicit preamble (like `{NiceTabular}`, `{NiceArray}`, etc.), it's possible to fix the width of a given column with the standard letters `w` and `W` of the package `array`.

```
\begin{NiceTabular}{Wc{2cm}cc}[hvlines]
Paris & New York & Madrid \\
Berlin & London & Roma \\
Rio & Tokyo & Oslo
\end{NiceTabular}
```

Paris	New York	Madrid
Berlin	London	Roma
Rio	Tokyo	Oslo

In the environments of `nicematrix`, it's also possible to fix the *minimal* width of all the columns of an array directly with the key `columns-width`.

```
$\begin{pNiceMatrix}[\text{columns-width} = 1cm]
1 & 12 & -123 \\
12 & 0 & 0 \\
4 & 1 & 2
\end{pNiceMatrix}$
```

$$\begin{pmatrix} 1 & 12 & -123 \\ 12 & 0 & 0 \\ 4 & 1 & 2 \end{pmatrix}$$

Note that the space inserted between two columns (equal to `2 \tabcolsep` in `{NiceTabular}` and to `2 \arraycolsep` in the other environments) is not suppressed (of course, it's possible to suppress this space by setting `\tabcolsep` or `\arraycolsep` equal to 0 pt before the environment).

It's possible to give the special value `auto` to the option `columns-width`: all the columns of the array will have a width equal to the widest cell of the array.²⁰

```
$\begin{pNiceMatrix}[\text{columns-width} = \text{auto}]
1 & 12 & -123 \\
12 & 0 & 0 \\
4 & 1 & 2
\end{pNiceMatrix}$
```

$$\begin{pmatrix} 1 & 12 & -123 \\ 12 & 0 & 0 \\ 4 & 1 & 2 \end{pmatrix}$$

²⁰The result is achieved with only one compilation (but PGF/Tikz will have written informations in the `.aux` file and a message requiring a second compilation will appear).

Without surprise, it's possible to fix the minimal width of the columns of all the matrices of a current scope with the command `\NiceMatrixOptions`.

```
\NiceMatrixOptions{columns-width=10mm}
$\begin{pNiceMatrix}
a & b \\ c & d
\end{pNiceMatrix}
=
\begin{pNiceMatrix}
1 & 1245 \\ 345 & 2
\end{pNiceMatrix}$
```

$$\left(\begin{array}{cc} a & b \\ c & d \end{array} \right) = \left(\begin{array}{cc} 1 & 1245 \\ 345 & 2 \end{array} \right)$$

But it's also possible to fix a zone where all the matrices will have their columns of the same width, equal to the widest cell of all the matrices. This construction uses the environment `{NiceMatrixBlock}` with the option `auto-columns-width`²¹. The environment `{NiceMatrixBlock}` has no direct link with the command `\Block` presented previously in this document (cf. p. 4).

```
\begin{NiceMatrixBlock}[auto-columns-width]
$\begin{array}{c}
\begin{bNiceMatrix}
9 & 17 \\ -2 & 5
\end{bNiceMatrix} \\
\begin{bNiceMatrix}
1 & 1245345 \\ 345 & 2
\end{bNiceMatrix}
\end{array}$
\end{NiceMatrixBlock}
```

$$\left[\begin{array}{cc} 9 & 17 \\ -2 & 5 \end{array} \right] \quad \left[\begin{array}{cc} 1 & 1245345 \\ 345 & 2 \end{array} \right]$$

8 The exterior rows and columns

The options `first-row`, `last-row`, `first-col` and `last-col` allow the composition of exterior rows and columns in the environments of `nicematrix`.

A potential “first row” (exterior) has the number 0 (and not 1). Idem for the potential “first column”.

```
$\begin{pNiceMatrix}[\texttt{first-row},\texttt{last-row},\texttt{first-col},\texttt{last-col},\texttt{nullify-dots}]
& C_1 & \cdots & C_4 & \\
L_1 & a_{11} & a_{12} & a_{13} & a_{14} & L_1 \\
\vdots & a_{21} & a_{22} & a_{23} & a_{24} & \vdots \\
& a_{31} & a_{32} & a_{33} & a_{34} & \\
L_4 & a_{41} & a_{42} & a_{43} & a_{44} & L_4 \\
& C_1 & \cdots & C_4 & \\
\end{pNiceMatrix}$
```

$$L_1 \left(\begin{array}{cccc} C_1 & \cdots & \cdots & C_4 \\ a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \\ a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{array} \right) L_1$$

$$\vdots \qquad \qquad \qquad \vdots$$

$$L_4 \left(\begin{array}{cccc} C_1 & \cdots & \cdots & C_4 \\ a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \\ a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{array} \right) L_4$$

$$C_1 \cdots \cdots C_4$$

The dotted lines have been drawn with the tools presented p. 19.

²¹At this time, this is the only usage of the environment `{NiceMatrixBlock}` but it may have other usages in the future.

We have several remarks to do.

- For the environments with an explicit preamble (i.e. `{NiceTabular}`, `{NiceArray}` and its variants), no letter must be given in that preamble for the potential first column and the potential last column: they will automatically (and necessarily) be of type `r` for the first column and `l` for the last one.²²
- One may wonder how `nicematrix` determines the number of rows and columns which are needed for the composition of the “last row” and “last column”.
 - For the environments with explicit preamble, like `{NiceTabular}` and `{pNiceArray}`, the number of columns can obviously be computed from the preamble.
 - When the option `light-syntax` (cf. p. 33) is used, `nicematrix` has, in any case, to load the whole body of the environment (and that’s why it’s not possible to put verbatim material in the array with the option `light-syntax`). The analysis of this whole body gives the number of rows (but not the number of columns).
 - In the other cases, `nicematrix` compute the number of rows and columns during the first compilation and write the result in the `aux` file for the next run.

However, it’s possible to provide the number of the last row and the number of the last column as values of the options `last-row` and `last-col`, tending to an acceleration of the whole compilation of the document. That’s what we will do throughout the rest of the document.

It’s possible to control the appearance of these rows and columns with options `code-for-first-row`, `code-for-last-row`, `code-for-first-col` and `code-for-last-col`. These options specify tokens that will be inserted before each cell of the corresponding row or column.

```
\NiceMatrixOptions{code-for-first-row = \color{red},
                  code-for-first-col = \color{blue},
                  code-for-last-row = \color{green},
                  code-for-last-col = \color{magenta}}
$\begin{pNiceArray}{cc|cc}[first-row,last-row=5,first-col,last-col,nullify-dots]
& C_1 & \cdots & C_4 \\
L_1 & a_{11} & a_{12} & a_{13} & a_{14} & L_1 \\
\vdots & a_{21} & a_{22} & a_{23} & a_{24} & \vdots \\
& a_{21} & a_{22} & a_{23} & a_{24} & \vdots \\
\hline
& a_{31} & a_{32} & a_{33} & a_{34} & \\
L_4 & a_{41} & a_{42} & a_{43} & a_{44} & L_4 \\
& C_1 & \cdots & C_4 & &
\end{pNiceArray}$
```

$$\begin{array}{c|c} C_1 & \dots & C_4 \\ \hline L_1 & \left(\begin{array}{cc|cc} a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \end{array} \right) & L_1 \\ \vdots & \vdots & \vdots \\ L_4 & \left(\begin{array}{cc|cc} a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{array} \right) & L_4 \\ C_1 & \dots & C_4 \end{array}$$

Remarks

- As shown in the previous example, the horizontal and vertical rules doesn’t extend in the exterior rows and columns.

However, if one wishes to define new specifiers for columns in order to draw vertical rules (for example thicker than the standard rules), he should consider the command `\OnlyMainNiceMatrix` described on page 38.

²²The users wishing exteriors columns with another type of alignment should consider the command `\SubMatrix` available in the `\CodeAfter` (cf. p. 25).

- A specification of color present in `code-for-first-row` also applies to a dotted line draw in this exterior “first row” (excepted if a value has been given to `xdots/color`). Idem for the other exterior rows and columns.
- Logically, the potential option `columns-width` (described p. 16) doesn’t apply to the “first column” and “last column”.
- For technical reasons, it’s not possible to use the option of the command `\\"\\` after the “first row” or before the “last row”. The placement of the delimiters would be wrong. If you are looking for a workaround, consider the command `\SubMatrix` in the `\CodeAfter` described p. 25.

9 The continuous dotted lines

Inside the environments of the package `nicematrix`, new commands are defined: `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, and `\Iddots`. These commands are intended to be used in place of `\dots`, `\cdots`, `\vdots`, `\ddots` and `\iddots`.²³

Each of them must be used alone in the cell of the array and it draws a dotted line between the first non-empty cells²⁴ on both sides of the current cell. Of course, for `\Ldots` and `\Cdots`, it’s an horizontal line; for `\Vdots`, it’s a vertical line and for `\Ddots` and `\Iddots` diagonal ones. It’s possible to change the color of these lines with the option `color`.²⁵

```
\begin{bNiceMatrix}
a_1 & \Cdots & & a_1 & \\
\Vdots & a_2 & \Cdots & a_2 & \\
& \Vdots & \Ddots[color=red] & \\
& a_1 & a_2 & & a_n
\end{bNiceMatrix}
```

$$\left[\begin{array}{ccccc} a_1 & \cdots & \cdots & \cdots & a_1 \\ \vdots & & & & \vdots \\ & a_2 & \cdots & \cdots & a_2 \\ \vdots & & \vdots & & \vdots \\ a_1 & a_2 & & & a_n \end{array} \right]$$

In order to represent the null matrix, one can use the following codage:

```
\begin{bNiceMatrix}
0 & \Cdots & 0 & \\
\Vdots & & \Vdots & \\
0 & \Cdots & 0
\end{bNiceMatrix}
```

$$\left[\begin{array}{ccc} 0 & \cdots & 0 \\ \vdots & & \vdots \\ 0 & \cdots & 0 \end{array} \right]$$

However, one may want a larger matrix. Usually, in such a case, the users of LaTeX add a new row and a new column. It’s possible to use the same method with `nicematrix`:

```
\begin{bNiceMatrix}
0 & \Cdots & \Cdots & 0 & \\
\Vdots & & & \Vdots & \\
\Vdots & & & \Vdots & \\
0 & \Cdots & \Cdots & 0
\end{bNiceMatrix}
```

$$\left[\begin{array}{ccccc} 0 & \cdots & \cdots & \cdots & 0 \\ \vdots & & & & \vdots \\ \vdots & & & & \vdots \\ 0 & \cdots & \cdots & \cdots & 0 \end{array} \right]$$

In the first column of this exemple, there are two instructions `\Vdots` but, of course, only one dotted line is drawn.

²³The command `\iddots`, defined in `nicematrix`, is a variant of `\ddots` with dots going forward. If `mathdots` is loaded, the version of `mathdots` is used. It corresponds to the command `\adots` of `unicode-math`.

²⁴The precise definition of a “non-empty cell” is given below (cf. p. 39).

²⁵It’s also possible to change the color of all theses dotted lines with the option `xdots/color` (`xdots` to remind that it works for `\Cdots`, `\Ldots`, `\Vdots`, etc.): cf. p. 22.

In fact, in this example, it would be possible to draw the same matrix more easily with the following code:

```
\begin{bNiceMatrix}
0 & \Cdots & 0 & \\
\Vdots & & & \\
& & & \Vdots \\
0 & & \Cdots & 0
\end{bNiceMatrix}
```

$$\begin{bmatrix} 0 & \cdots & 0 \\ \vdots & & \vdots \\ 0 & \cdots & 0 \end{bmatrix}$$

There are also other means to change the size of the matrix. Someone might want to use the optional argument of the command `\\"\\` for the vertical dimension and a command `\hspace*` in a cell for the horizontal dimension.²⁶

However, a command `\hspace*` might interfere with the construction of the dotted lines. That's why the package `nicematrix` provides a command `\Hspace` which is a variant of `\hspace` transparent for the dotted lines of `nicematrix`.

```
\begin{bNiceMatrix}
0 & \Cdots & \Hspace*[1cm] & 0 & \\
\Vdots & & & \Vdots \\[1cm]
0 & \Cdots & & 0
\end{bNiceMatrix}
```

$$\begin{bmatrix} 0 & \cdots & 0 \\ \vdots & & \vdots \\ 0 & \cdots & 0 \end{bmatrix}$$

9.1 The option `nullify-dots`

Consider the following matrix composed classically with the environment `{pmatrix}` of `amsmath`.

```
$A = \begin{pmatrix}
h & i & j & k & l & m \\
x & & & & & x
\end{pmatrix}
```

$$A = \begin{pmatrix} h & i & j & k & l & m \\ x & & & & & x \end{pmatrix}$$

If we add `\ldots` instructions in the second row, the geometry of the matrix is modified.

```
$B = \begin{pmatrix}
h & i & j & k & l & m \\
x & \ldots & \ldots & \ldots & \ldots & x
\end{pmatrix}
```

$$B = \begin{pmatrix} h & i & j & k & l & m \\ x & \dots & \dots & \dots & \dots & x \end{pmatrix}$$

By default, with `nicematrix`, if we replace `{pmatrix}` by `{pNiceMatrix}` and `\ldots` by `\Ldots`, the geometry of the matrix is not changed.

```
$C = \begin{pNiceMatrix}
h & i & j & k & l & m \\
x & \Ldots & \Ldots & \Ldots & \Ldots & x
\end{pNiceMatrix}
```

$$C = \begin{pmatrix} h & i & j & k & l & m \\ x & \cdots & \cdots & \cdots & \cdots & x \end{pmatrix}$$

However, one may prefer the geometry of the first matrix A and would like to have such a geometry with a dotted line in the second row. It's possible by using the option `nullify-dots` (and only one instruction `\Ldots` is necessary).

```
$D = \begin{pNiceMatrix} [nullify-dots]
h & i & j & k & l & m \\
x & \Ldots & & & & x
\end{pNiceMatrix}
```

$$D = \begin{pmatrix} h & i & j & k & l & m \\ x & \cdots & & & & x \end{pmatrix}$$

The option `nullify-dots` smashes the instructions `\Ldots` (and the variants) horizontally but also vertically.

²⁶In `nicematrix`, one should use `\hspace*` and not `\hspace` for such an usage because `nicematrix` loads `array`. One may also remark that it's possible to fix the width of a column by using the environment `{NiceArray}` (or one of its variants) with a column of type `w` or `W`: see p. 16

9.2 The commands `\Hdotsfor` and `\Vdotsfor`

Some people commonly use the command `\hdotsfor` of `amsmath` in order to draw horizontal dotted lines in a matrix. In the environments of `nicematrix`, one should use instead `\Hdotsfor` in order to draw dotted lines similar to the other dotted lines drawn by the package `nicematrix`.

As with the other commands of `nicematrix` (like `\Cdots`, `\Ldots`, `\Vdots`, etc.), the dotted line drawn with `\Hdotsfor` extends until the contents of the cells on both sides.

```
$\begin{pNiceMatrix}
1 & 2 & 3 & 4 & 5 \\
1 & \Hdotsfor{3} & 5 \\
1 & 2 & 3 & 4 & 5 \\
1 & 2 & 3 & 4 & 5
\end{pNiceMatrix}$
```

$$\begin{pmatrix} 1 & 2 & 3 & 4 & 5 \\ 1 & \dots & & & 5 \\ 1 & 2 & 3 & 4 & 5 \\ 1 & 2 & 3 & 4 & 5 \end{pmatrix}$$

However, if these cells are empty, the dotted line extends only in the cells specified by the argument of `\Hdotsfor` (by design).

```
$\begin{pNiceMatrix}
1 & 2 & 3 & 4 & 5 \\
& \Hdotsfor{3} \\
1 & 2 & 3 & 4 & 5 \\
1 & 2 & 3 & 4 & 5
\end{pNiceMatrix}$
```

$$\begin{pmatrix} 1 & 2 & 3 & 4 & 5 \\ & \dots & & & \\ 1 & 2 & 3 & 4 & 5 \\ 1 & 2 & 3 & 4 & 5 \end{pmatrix}$$

Remark: Unlike the command `\hdotsfor` of `amsmath`, the command `\Hdotsfor` may be used even when the package `colortbl`²⁷ is loaded (but you might have problem if you use `\rowcolor` on the same row as `\Hdotsfor`).

The package `nicematrix` also provides a command `\Vdotsfor` similar to `\Hdotsfor` but for the vertical dotted lines. The following example uses both `\Hdotsfor` and `\Vdotsfor`:

```
\begin{bNiceMatrix}
C[a_1,a_1] & \Cdots & C[a_1,a_n]
& \hspace*{20mm} & C[a_1,a_1^{(p)}] & \Cdots & C[a_1,a_n^{(p)}] \\
\end{bNiceMatrix}
```

```
\Vdots & \Ddots & \Vdots
& \Hdotsfor{1} & \Vdots & \Ddots & \Vdots \\
C[a_n,a_1] & \Cdots & C[a_n,a_n]
& & C[a_n,a_1^{(p)}] & \Cdots & C[a_n,a_n^{(p)}] \\
\end{bNiceMatrix}
```

```
\rule{0pt}{15mm}\NotEmpty & \Vdotsfor{1} & & \Ddots & & \Vdotsfor{1} \\
C[a_1^{(p)},a_1] & \Cdots & C[a_1^{(p)},a_n]
& & C[a_1^{(p)},a_1^{(p)}] & \Cdots & C[a_1^{(p)},a_n^{(p)}] \\
\end{bNiceMatrix}
```

```
\Vdots & \Ddots & \Vdots
& \Hdotsfor{1} & \Vdots & \Ddots & \Vdots \\
C[a_n^{(p)},a_1] & \Cdots & C[a_n^{(p)},a_n]
& & C[a_n^{(p)},a_1^{(p)}] & \Cdots & C[a_n^{(p)},a_n^{(p)}]
\end{bNiceMatrix}
```

$$\left[\begin{array}{ccccc} C[a_1,a_1] & \dots & C[a_1,a_n] & & C[a_1,a_1^{(p)}] & \dots & C[a_1,a_n^{(p)}] \\ \vdots & & \vdots & & \vdots & & \vdots \\ C[a_n,a_1] & \dots & C[a_n,a_n] & & C[a_n,a_1^{(p)}] & \dots & C[a_n,a_n^{(p)}] \\ & & & & \ddots & & \ddots \\ & & & & C[a_1^{(p)},a_1] & \dots & C[a_1^{(p)},a_n] \\ \vdots & & \vdots & & \vdots & & \vdots \\ C[a_n^{(p)},a_1] & \dots & C[a_n^{(p)},a_n] & & C[a_n^{(p)},a_1^{(p)}] & \dots & C[a_n^{(p)},a_n^{(p)}] \end{array} \right]$$

²⁷We recall that when `xcolor` is loaded with the option `table`, the package `colortbl` is loaded.

9.3 How to generate the continuous dotted lines transparently

Imagine you have a document with a great number of mathematical matrices with ellipsis. You may wish to use the dotted lines of `nicematrix` without having to modify the code of each matrix. It's possible with the keys `renew-dots` and `renew-matrix`.²⁸

- The option `renew-dots`

With this option, the commands `\ldots`, `\cdots`, `\vdots`, `\ddots`, `\iddots`²³ and `\hdotsfor` are redefined within the environments provided by `nicematrix` and behave like `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, `\Iddots` and `\Hdotsfor`; the command `\dots` (“automatic dots” of `amsmath`) is also redefined to behave like `\Ldots`.

- The option `renew-matrix`

With this option, the environment `{matrix}` is redefined and behave like `{NiceMatrix}`, and so on for the five variants.

Therefore, with the keys `renew-dots` and `renew-matrix`, a classical code gives directly the output of `nicematrix`.

```
\NiceMatrixOptions{renew-dots,renew-matrix}
\begin{pmatrix}
1 & \cdots & \cdots & \cdots & 1 \\
0 & \ddots & & & \\
\vdots & \ddots & \ddots & \vdots & \\
0 & \cdots & 0 & \cdots & 1
\end{pmatrix}
```

$$\begin{pmatrix} 1 & \cdots & \cdots & \cdots & 1 \\ 0 & \ddots & & & \\ \vdots & \ddots & \ddots & \vdots & \\ 0 & \cdots & 0 & \cdots & 1 \end{pmatrix}$$

9.4 The labels of the dotted lines

The commands `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, `\Iddots` and `\Hdotsfor` (and the command `\line` in the `\CodeAfter` which is described p. 24) accept two optional arguments specified by the tokens `_` and `^` for labels positionned below and above the line. The arguments are composed in math mode with `\scriptstyle`.

```
$\begin{bNiceMatrix}
1 & \hspace*{1cm} & & & & 0 \\ 
& \text{\hspace*{1cm}} & & & & \\
& \text{\hspace*{1cm}} & & & & \\
0 & & & & & 1
\end{bNiceMatrix}$
```

$$\begin{bmatrix} 1 & & & & 0 \\ & \ddots & \cdots & \cdots & \\ & & n \text{ times} & & \\ 0 & & & & 1 \end{bmatrix}$$

9.5 Customisation of the dotted lines

The dotted lines drawn by `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, `\Iddots` and `\Hdotsfor` (and by the command `\line` in the `\CodeAfter` which is described p. 24) may be customized by three options (specified between square brackets after the command):

- `color`;
- `shorten`;
- `line-style`.

These options may also be fixed with `\NiceMatrixOptions`, as options of `\CodeAfter` or at the level of a given environment but, in those cases, they must be prefixed by `xdots`, and, thus have for names:

²⁸The options `renew-dots`, `renew-matrix` can be fixed with the command `\NiceMatrixOptions` like the other options. However, they can also be fixed as options of the command `\usepackage`. There is also a key `transparent` which is an alias for the conjunction of `renew-dots` and `renew-matrix` but it must be considered as obsolete.

- `xdots/color;`
- `xdots/shorten;`
- `xdots/line-style.`

For the clarity of the explanations, we will use those names.

The option `xdots/color`

The option `xdots/color` fixes the color or the dotted line. However, one should remark that the dotted lines drawn in the exterior rows and columns have a special treatment: cf. p. 17.

The option `xdots/shorten`

The option `xdots/shorten` fixes the margin of both extremities of the line. The name is derived from the options “`shorten >`” and “`shorten <`” of Tikz but one should notice that `nicematrix` only provides `xdots/shorten`. The initial value of this parameter is 0.3 em (it is recommended to use a unit of length dependent of the current font).

The option `xdots/line-style`

It should be pointed that, by default, the lines drawn by Tikz with the parameter `dotted` are composed of square dots (and not rounded ones).²⁹

```
\tikz \draw [dotted] (0,0) -- (5,0) ; .....
```

In order to provide lines with rounded dots in the style of those provided by `\ldots` (at least with the *Computer Modern* fonts), the package `nicematrix` embeds its own system to draw a dotted line (and this system uses PGF and not Tikz). This style is called `standard` and that's the initial value of the parameter `xdots/line-style`.

However (when Tikz is loaded) it's possible to use for `xdots/line-style` any style provided by Tikz, that is to say any sequence of options provided by Tikz for the Tizk pathes (with the exception of “`color`”, “`shorten >`” and “`shorten <`”).

Here is for example a tridiagonal matrix with the style `loosely dotted`:

```
$\begin{pNiceMatrix} [nullify-dots, xdots/line-style=loosely dotted]
a & b & 0 & & \Cdots & 0 & \\
b & a & b & & \Ddots & & \Vdots \\
0 & b & a & & \Ddots & & \\
& \Ddots & \Ddots & \Ddots & & 0 & \\
\Vdots & & & & & b & \\
0 & & \Cdots & 0 & b & a
\end{pNiceMatrix}$
```

$$\begin{pmatrix} a & b & 0 & \cdots & 0 \\ b & a & b & \ddots & \vdots \\ 0 & b & a & \ddots & \vdots \\ \vdots & \ddots & \ddots & \ddots & 0 \\ \vdots & \ddots & \ddots & \ddots & b \\ 0 & \cdots & 0 & b & a \end{pmatrix}$$

9.6 The dotted lines and the rules

The dotted lines determine virtual blocks which have the same behaviour regarding the rules (the rules specified by the specifier `|` in the preamble, by the command `\Hline` and by the keys `hlines`, `vlines` and `hvlines` are not drawn within the blocks).³⁰

²⁹The first reason of this behaviour is that the PDF format includes a description for dashed lines. The lines specified with this descriptor are displayed very efficiently by the PDF readers. It's easy, starting from these dashed lines, to create a line composed by square dots whereas a line of rounded dots needs a specification of each dot in the PDF file.

³⁰On the other side, the command `\line` in the `\CodeAfter` (cf. p. 24) does *not* create block.

```
$\begin{bNiceMatrix} [margin,hvlines]
\Block{3-3}<\LARGE>{A} & & 0 \\
& \hspace*{1cm} & \Vdots \\
& & 0 \\
0 & \Cdots & 0 & 0
\end{bNiceMatrix}$
```

$$\left[\begin{array}{c|c} A & \begin{matrix} 0 \\ \vdots \\ 0 \end{matrix} \\ \hline \begin{matrix} 0 & \dots & 0 \end{matrix} & 0 \end{array} \right]$$

10 The \CodeAfter

The option `code-after` may be used to give some code that will be executed *after* the construction of the matrix.³¹

For the legibility of the code, an alternative syntax is provided: it's possible to give the instructions of the `code-after` at the end of the environment, after the keyword `\CodeAfter`. Although `\CodeAfter` is a keyword, it takes in an optional argument (between square brackets). The keys accepted form a subset of the keys of the command `\WithArrowsOptions`.

The experienced users may, for instance, use the PGF/Tikz nodes created by `nicematrix` in the `\CodeAfter`. These nodes are described further beginning on p. 34.

Moreover, two special commands are available in the `\CodeAfter`: `line` and `\SubMatrix`.

10.1 The command \line in the \CodeAfter

The command `\line` draws directly dotted lines between nodes. It takes in two arguments for the two cells to link, both of the form $i-j$ where i is the number of the row and j is the number of the column. The options available for the customisation of the dotted lines created by `\Cdots`, `\Vdots`, etc. are also available for this command (cf. p. 22).

This command may be used, for example, to draw a dotted line between two adjacent cells.

```
\NiceMatrixOptions{xdots/shorten = 0.6 em}
\begin{pNiceMatrix}
I & 0 & \Cdots & 0 & \\
0 & I & \Ddots & \Vdots & \\
\Vdots & \Ddots & I & 0 & \\
0 & \Cdots & 0 & I & \\
\CodeAfter \line{2-2}{3-3}
\end{pNiceMatrix}
```

$$\begin{pmatrix} I & 0 & \cdots & 0 \\ 0 & I & \ddots & \vdots \\ \vdots & \ddots & \ddots & 0 \\ 0 & \cdots & 0 & I \end{pmatrix}$$

It can also be used to draw a diagonal line not parallel to the other diagonal lines (by default, the dotted lines drawn by `\Ddots` are “parallelized”: cf. p. 38).

```
\begin{bNiceMatrix}
1 & \Cdots & 1 & 2 & \Cdots & 2 & \\
0 & \Ddots & & \Vdots & \hspace*{2.5cm} & \Vdots & \\
\Vdots & \Ddots & & & & & \\
0 & \Cdots & 0 & 1 & 2 & \Cdots & 2 \\
\CodeAfter \line[shorten=6pt]{1-5}{4-7}
\end{bNiceMatrix}
```

$$\begin{bmatrix} 1 & \cdots & 1 & 2 & \cdots & 2 \\ 0 & \cdots & \vdots & \vdots & \cdots & \vdots \\ \vdots & \cdots & \vdots & \vdots & \cdots & \vdots \\ 0 & \cdots & 0 & 1 & 2 & \cdots & 2 \end{bmatrix}$$

³¹There is also a key `code-before` described p. 12.

10.2 The command \SubMatrix in the \CodeAfter

The command `\SubMatrix` provides a way to put delimiters on a portion of the array considered as a submatrix. The command `\SubMatrix` takes in five arguments:

- the first argument is the left delimiter, which may be any extensible delimiter provided by LaTeX : (, [, \{, \langle, \lgroup, \lfloor, etc. but also the null delimiter .;
- the second argument is the upper-left corner of the submatrix with the syntax $i-j$ where i the number of row and j the number of column;
- the third argument is the lower-right corner with the same syntax;
- the fourth argument is the right delimiter;
- the last argument, which is optional, is a list of key-value pairs.³²

One should remark that the command `\SubMatrix` draws the delimiters after the construction of the array: no space is inserted by the command `\SubMatrix` itself. That's why, in the following example, we have used the key `margin` and you have added by hand some space between the third and fourth column with `@{\hspace{1.5em}}` in the preamble of the array.

```
\begin{NiceArray}{ccc@{\hspace{1.5em}}c}[cell-space-limits=2pt,margin]
 1 & 1 & 1 & x \\
 \dfrac{1}{4} & \dfrac{1}{2} & \dfrac{1}{4} & y \\
 1 & 2 & 3 & z
\CodeAfter
  \SubMatrix({1-1}{3-3})
  \SubMatrix({1-4}{3-4})
\end{NiceArray}
```

$$\left(\begin{array}{ccc|c} 1 & 1 & 1 & x \\ \hline \frac{1}{4} & \frac{1}{2} & \frac{1}{4} & y \\ 1 & 2 & 3 & z \end{array} \right)$$

The options of the command `\SubMatrix` are as follows:

- `left-xshift` and `right-shift` shift horizontally the delimiters (there exists also the key `xshift` which fixes both parameters);
- `extra-height` adds a quantity to the total height of the delimiters (height `\ht` + depth `\dp`);
- `delimiters/color` fixes the color of the delimiters (also available in `\NiceMatrixOptions`, in the environments with delimiters and as option of the keyword `\CodeAfter`);
- `slim` is a boolean key: when that key is in force, the horizontal position of the delimiters is computed by using only the contents of the cells of the submatrix whereas, in the general case, the position is computed by taking into account the cells of the whole columns implied in the submatrix (see example below). ;
- `vlines` contents a list of numbers of vertical rules that will be drawn in the sub-matrix (if this key is used without value, all the vertical rules of the sub-matrix are drawn);
- `hlines` is similar to `vlines` but for the horizontal rules;
- `hvlines`, which must be used without value, draws all the vertical and horizontal rules.

One should remark that these keys add their rules after the construction of the main matrix: no space is added between the rows and the columns of the array for theses rules.

All these keys are also available in `\NiceMatrixOptions`, at the level of the environments of `nicematrix` or as option of the command `\CodeAfter` with the prefix `sub-matrix` which means that their names are therefore `sub-matrix/left-xshift`, `sub-matrix/right-xshift`, `sub-matrix/xshift`, etc.

³²There is no optional argument between square brackets in first position because a square bracket just after `\SubMatrix` must be interpreted as the first (mandatory) argument of the command `\SubMatrix`: that bracket is the left delimiter of the sub-matrix to construct (eg.: `\SubMatrix[{2-2}{4-7}]`).

```
$\begin{NiceArray}{cc@{\hspace{5mm}}l}[cell-space-limits=2pt]
& & \frac{1}{2} \\
& & \frac{1}{4} \\
a & b & \frac{1}{2}a + \frac{1}{4}b \\
c & d & \frac{1}{2}c + \frac{1}{4}d \\
\CodeAfter
\SubMatrix({1-3}{2-3})
\SubMatrix({3-1}{4-2})
\SubMatrix({3-3}{4-3})
\end{NiceArray}$
```

$$\begin{pmatrix} a & b \\ c & d \end{pmatrix} \begin{pmatrix} \frac{1}{2} & \\ \frac{1}{4} & \end{pmatrix}$$

Here is the same example with the key `slim` used for one of the submatrices.

```
$\begin{NiceArray}{cc@{\hspace{5mm}}l}[cell-space-limits=2pt]
& & \frac{1}{2} \\
& & \frac{1}{4} \\
a & b & \frac{1}{2}a + \frac{1}{4}b \\
c & d & \frac{1}{2}c + \frac{1}{4}d \\
\CodeAfter
\SubMatrix({1-3}{2-3}) [slim]
\SubMatrix({3-1}{4-2})
\SubMatrix({3-3}{4-3})
\end{NiceArray}$
```

$$\begin{pmatrix} a & b \\ c & d \end{pmatrix} \begin{pmatrix} \frac{1}{2} & \\ \frac{1}{4} & \end{pmatrix}$$

There is also a key `name` which gives a name to the submatrix created by `\SubMatrix`. That name is used to create PGF/Tikz nodes: cf p. 37.

New 5.15 It's also possible to specify some delimiters³³ by placing them in the preamble of the environment (for the environments with a preamble: `{NiceArray}`, `{pNiceArray}`, etc.). This syntax is inspired by the extension `blkarray`.

When there are two successive delimiters (necessarily a closing one following by an opening one for another submatrix), a space equal to `\enskip` is automatically inserted.

```
$\begin{pNiceArray}{(c)(c)(c)}
a_{11} & a_{12} & & a_{13} \\
a_{21} & \displaystyle \int_0^1 \frac{1}{x^2+1} dx & a_{23} \\
a_{31} & a_{32} & a_{33}
\end{pNiceArray}$
```

$$\begin{pmatrix} a_{11} \\ a_{21} \\ a_{31} \end{pmatrix} \left(\int_0^1 \frac{1}{x^2+1} dx \right) \begin{pmatrix} a_{13} \\ a_{23} \\ a_{33} \end{pmatrix}$$

11 The notes in the tabulars

11.1 The footnotes

The package `nicematrix` allows, by using `footnote` or `footnotehyper`, the extraction of the notes inserted by `\footnote` in the environments of `nicematrix` and their composition in the footpage with the other notes of the document.

If `nicematrix` is loaded with the option `footnote` (with `\usepackage[footnote]{nicematrix}` or with `\PassOptionsToPackage`), the package `footnote` is loaded (if it is not yet loaded) and it is used to extract the footnotes.

³³Those delimiters are `(`, `[`, `\{` and the closing ones. Of course, it's also possible to put `|` and `||` in the preamble of the environement.

If `nicematrix` is loaded with the option `footnotehyper`, the package `footnotehyper` is loaded (if it is not yet loaded) and it is used to extract footnotes.

Caution: The packages `footnote` and `footnotehyper` are incompatible. The package `footnotehyper` is the successor of the package `footnote` and should be used preferentially. The package `footnote` has some drawbacks, in particular: it must be loaded after the package `xcolor` and it is not perfectly compatible with `hyperref`.

11.2 The notes of `tabular`

The package `nicematrix` also provides a command `\tabularnote` which gives the ability to specify notes that will be composed at the end of the array with a width of line equal to the width of the array (excepted the potential exterior columns). With no surprise, that command is available only in the environments without delimiters, that is to say `{NiceTabular}`, `{NiceArray}` and `{NiceMatrix}`. In fact, this command is available only if the extension `enumitem` has been loaded (before or after `nicematrix`). Indeed, the notes are composed at the end of the array with a type of list provided by the package `enumitem`.

```
\begin{NiceTabular}{@{}llr@{}}
  [first-row, code-for-first-row = \bfseries]
  \toprule
  Last name & First name & Birth day \\
  \midrule
  Achard\tabularnote{Achard is an old family of the Poitou.} \\
  & Jacques & 5 juin 1962 \\
  Lefebvre\tabularnote{The name Lefebvre is an alteration of the name Lefebure.} \\
  & Mathilde & 23 mai 1988 \\
  Vanesse & Stephany & 30 octobre 1994 \\
  Dupont & Chantal & 15 janvier 1998 \\
  \bottomrule
\end{NiceTabular}
```

Last name	First name	Birth day
Achard ^a	Jacques	June 5, 2005
Lefebvre ^b	Mathilde	January 23, 1975
Vanesse	Stephany	October 30, 1994
Dupont	Chantal	January 15, 1998

^a Achard is an old family of the Poitou.

^b The name Lefebvre is an alteration of the name Lefebure.

- If you have several successive commands `\tabularnote{...}` with no space at all between them, the labels of the corresponding notes are composed together, separated by commas (this is similar to the option `multiple` of `footmisc` for the footnotes).
- If a command `\tabularnote{...}` is exactly at the end of a cell (with no space at all after), the label of the note is composed in an overlapping position (towards the right). This structure may provide a better alignment of the cells of a given column.
- If the key `notes/para` is used, the notes are composed at the end of the array in a single paragraph (as with the key `para` of `threeparttable`).
- There is a key `tabularnote` which provides a way to insert some text in the zone of the notes before the numbered tabular notes.
- If the package `booktabs` has been loaded (before or after `nicematrix`), the key `notes/bottomrule` draws a `\bottomrule` of `booktabs` after the notes.

- The command `\tabularnote` may be used *before* the environment of `nicematrix`. Thus, it's possible to use it on the title inserted by `\caption` in an environment `{table}` of LaTeX.
- It's possible to create a reference to a tabular note created by `\tabularnote` (with the usual command `\label` used after the `\tabularnote`).

For an illustration of some of those remarks, see table 1, p. 28. This table has been composed with the following code.

```
\begin{table}
\setlength{\belowcaptionskip}{1ex}
\centering
\caption{Use of \texttt{\textbackslash tabularnote}\texttt{\{It's possible to put a note in the caption.\}}}
\label{t:tabularnote}
\begin{NiceTabular}{@{}llc@{}}
[notes/bottomrule, tabularnote = Some text before the notes.]
\toprule
Last name & First name & Length of life \\
\midrule
Churchill & Wiston & 91\\
Nightingale\tabularnote{Considered as the first nurse of history.}\tabularnote{Nicknamed ``the Lady with the Lamp''.}\\
& Florence & 90 \\
Schoelcher & Victor & 89\tabularnote{The label of the note is overlapping.}\\
Touchet & Marie & 89 \\
Wallis & John & 87 \\
\bottomrule
\end{NiceTabular}
\end{table}
```

Table 1: Use of `\tabularnotea`

Last name	First name	Length of life
Churchill	Wiston	91
Nightingale ^{b,c}	Florence	90
Schoelcher	Victor	89 ^d
Touchet	Marie	89
Wallis	John	87

Some text before the notes.

^a It's possible to put a note in the caption.

^b Considered as the first nurse of history.

^c Nicknamed “the Lady with the Lamp”.

^d The label of the note is overlapping.

11.3 Customisation of the tabular notes

The tabular notes can be customized with a set of keys available in `\NiceMatrixOptions`. The name of these keys is prefixed by `notes`.

- `notes/para`
- `notes/bottomrule`
- `notes/style`
- `notes/label-in-tabular`

- `notes/label-in-list`
- `notes/enumitem-keys`
- `notes/enumitem-keys-para`
- `notes/code-before`

For sake of commodity, it is also possible to set these keys in `\NiceMatrixOptions` via a key `notes` which takes in as value a list of pairs `key=value` where the name of the keys need no longer be prefixed by `notes`:

```
\NiceMatrixOptions
{
    notes =
    {
        bottomrule ,
        style = ... ,
        label-in-tabular = ... ,
        enumitem-keys =
        {
            labelsep = ... ,
            align = ... ,
            ...
        }
    }
}
```

We detail these keys.

- The key `notes/para` requires the composition of the notes (at the end of the tabular) in a single paragraph.

Initial value: `false`

That key is also available within a given environment.

- The key `notes/bottomrule` adds a `\bottomrule` of `booktabs` *after* the notes. Of course, that rule is drawn only if there is really notes in the tabular. The package `booktabs` must have been loaded (before or after the package `nicematrix`). If it is not, an error is raised.

Initial value: `false`

That key is also available within a given environment.

- The key `notes/style` is a command whose argument is specified by `#1` and which gives the style of numerotation of the notes. That style will be used by `\ref` when referencing a tabular note marked with a command `\label`. The labels formatted by that style are used, separated by commas, when the user puts several consecutive commands `\tabularnote`. The marker `#1` is meant to be the name of a LaTeX counter.

Initial value: `\textit{\alph{#1}}`

Another possible value should be a mere `\arabic{#1}`

- The key `notes/label-in-tabular` is a command whose argument is specified by `#1` which is used when formatting the label of a note in the tabular. Internally, this number of note has already been formatted by `notes/style` before sent to that command.

Initial value: `#1`

In French, it's a tradition of putting a small space before the label of note. That tuning could be achieved by the following code:

```
\NiceMatrixOptions{notes/label-in-tabular = \,\textsuperscript{#1}}
```

- The key `notes/label-in-list` is a command whose argument is specified by `#1` which is used when formatting the label in the list of notes at the end of the tabular. Internally, this number of note has already been formatted by `notes/style` before sent to that command.

Initial value: `#1`

In French, the labels of notes are not composed in upper position when composing the notes. Such behaviour could be achieved by:

```
\NiceMatrixOptions{notes/label-in-list = #1.\nobreak\hspace{0.25em}}
```

The command `\nobreak` is for the event that the option `para` is used.

- The notes are composed at the end of the tabular by using internally a style of list of `enumitem`. The key `notes/enumitem-keys` specifies a list of pairs `key=value` (following the specifications of `enumitem`) to customize that type of list.

Initial value: `noitemsep , leftmargin = * , align = left , labelsep = 0pt`

This initial value contains the specification `align = left` which requires a composition of the label leftwards in the box affected to that label. With that tuning, the notes are composed flush left, which is pleasant when composing tabulars in the spirit of `booktabs` (see for example the table 1, p. 28).

- The key `notes/enumitem-keys-para` is similar to the previous one but corresponds to the type of list used when the option `para` is in force. Of course, when the option `para` is used, a list of type `inline` (as called by `enumitem`) is used and the pairs `key=value` should correspond to such a list of type `inline`.

Initial value: `afterlabel = \nobreak, itemjoin = \quad`

- The key `notes/code-before` is a token list inserted by `nicematrix` just before the composition of the notes at the end of the tabular.

Initial value: `empty`

For example, if one wishes to compose all the notes in gray and `\footnotesize`, he should use that key:

```
\NiceMatrixOptions{notes/code-before = \footnotesize \color{gray}}
```

It's also possible to add `\raggedright` or `\RaggedRight` in that key (`\RaggedRight` is a command of `ragged2e`).

For an example of customisation of the tabular notes, see p. 40.

11.4 Use of `{NiceTabular}` with `threeparttable`

If you wish to use the environment `{NiceTabular}` or `{NiceTabular*}` in an environment `{threeparttable}` of the eponymous package, you have to patch the environment `{threeparttable}` with the following code (with a version of LaTeX at least 2020/10/01).

```
\makeatletter
\AddToHook{env/threeparttable/begin}
  {\TPT@hookin{NiceTabular}\TPT@hookin{NiceTabular*}}
\makeatother
```

12 Other features

12.1 Use of the column type S of siunitx

If the package `siunitx` is loaded (before or after `nicematrix`), it's possible to use the `S` column type of `siunitx` in the environments of `nicematrix`. The implementation doesn't use explicitly any private macro of `siunitx`.

```
$\begin{pNiceArray}{ScWc{1cm}c}[nullify-dots,first-row]
{C_1} & \Cdots & C_n \\
2.3 & 0 & \Cdots & 0 \\
12.4 & \Vdots & & \Vdots \\
1.45 \\
7.2 & 0 & \Cdots & 0
\end{pNiceArray}$
```

$$\left(\begin{array}{ccccc} C_1 & \cdots & \cdots & \cdots & C_n \\ 2.3 & 0 & \cdots & \cdots & 0 \\ 12.4 & \vdots & & \vdots & \vdots \\ 1.45 & & & \vdots & \vdots \\ 7.2 & 0 & \cdots & \cdots & 0 \end{array} \right)$$

On the other hand, the `d` columns of the package `dcolumn` are not supported by `nicematrix`.

12.2 Alignment option in {NiceMatrix}

The environments without preamble (`{NiceMatrix}`, `{pNiceMatrix}`, `{bNiceMatrix}`, etc.) provide two options `l` and `r` which generate all the columns aligned leftwards (or rightwards).

```
$\begin{bNiceMatrix}[r]
\cos x & -\sin x \\
\sin x & \cos x
\end{bNiceMatrix}$
```

$$\begin{bmatrix} \cos x & -\sin x \\ \sin x & \cos x \end{bmatrix}$$

12.3 The command `\rotate`

The package `nicematrix` provides a command `\rotate`. When used in the beginning of a cell, this command composes the contents of the cell after a rotation of 90° in the direct sens.

In the following command, we use that command in the `code-for-first-row`.

```
\NiceMatrixOptions%
{code-for-first-row = \scriptstyle \rotate \text{image of } ,
 code-for-last-col = \scriptstyle }
$A = \begin{pNiceMatrix}[first-row,last-col=4]
e_1 & e_2 & e_3 & \\
1 & 2 & 3 & e_1 \\
4 & 5 & 6 & e_2 \\
7 & 8 & 9 & e_3
\end{pNiceMatrix}$
```

$$A = \begin{pmatrix} 1 & 2 & 3 & \text{image of } e_1 \\ 4 & 5 & 6 & \text{image of } e_2 \\ 7 & 8 & 9 & \text{image of } e_3 \end{pmatrix}_{e_1 e_2 e_3}$$

If the command `\rotate` is used in the “last row” (exterior to the matrix), the corresponding elements are aligned upwards as shown below.

```
\NiceMatrixOptions%
{code-for-last-row = \scriptstyle \rotate ,
 code-for-last-col = \scriptstyle }
$A = \begin{pNiceMatrix}[last-row=4,last-col=4]
1 & 2 & 3 & e_1 \\
4 & 5 & 6 & e_2 \\
7 & 8 & 9 & e_3 \\
\text{image of } e_1 & e_2 & e_3 & e_1
\end{pNiceMatrix}$
```

$$A = \begin{pmatrix} 1 & 2 & 3 & e_1 \\ 4 & 5 & 6 & e_2 \\ 7 & 8 & 9 & e_3 \\ \text{image of } e_1 & e_2 & e_3 & e_1 \end{pmatrix}_{e_1 e_2 e_3 e_1}$$

12.4 The option `small`

With the option `small`, the environments of the package `nicematrix` are composed in a way similar to the environment `{smallmatrix}` of the package `amsmath` (and the environments `{psmallmatrix}`, `{bsmallmatrix}`, etc. of the package `mathtools`).

```
$\begin{bNiceArray}{cccc|c}[\small,
    last-col,
    code-for-last-col = \scriptscriptstyle,
    columns-width = 3mm ]
1 & -2 & 3 & 4 & 5 \\
0 & 3 & 2 & 1 & 2 & \gets 2 L_1 - L_2 \\
0 & 1 & 2 & 3 & L_3 & \gets L_1 + L_3
\end{bNiceArray}$
```

$$\left[\begin{array}{ccccc|c} 1 & -2 & 3 & 4 & 5 \\ 0 & 3 & 2 & 1 & 2 \\ 0 & 1 & 2 & 3 & L_3 \end{array} \right] \begin{array}{l} L_2 \leftarrow 2L_1 - L_2 \\ L_3 \leftarrow L_1 + L_3 \end{array}$$

One should note that the environment `{NiceMatrix}` with the option `small` is not composed *exactly* as the environment `{smallmatrix}`. Indeed, all the environments of `nicematrix` are constructed upon `{array}` (of the package `array`) whereas the environment `{smallmatrix}` is constructed directly with an `\halign` of TeX.

In fact, the option `small` corresponds to the following tuning:

- the cells of the array are composed with `\scriptstyle`;
- `\arraystretch` is set to 0.47;
- `\arraycolsep` is set to 1.45 pt;
- the characteristics of the dotted lines are also modified.

12.5 The counters `iRow` and `jCol`

In the cells of the array, it's possible to use the LaTeX counters `iRow` and `jCol` which represent the number of the current row and the number of the current column³⁴. Of course, the user must not change the value of these counters which are used internally by `nicematrix`.

In the `\CodeBefore` (cf. p. 12) and in the `\CodeAfter` (cf. p. 24), `iRow` represents the total number of rows (excepted the potential exterior rows) and `jCol` represents the total number of columns (excepted the potential exterior columns).

```
$\begin{pNiceMatrix}% don't forget the %
    [first-row,
     first-col,
     code-for-first-row = \mathbf{\alpha{p{jCol}}},           & \mathbf{a} & \mathbf{b} & \mathbf{c} & \mathbf{d} \\
     code-for-first-col = \mathbf{\alpha{p{iRow}}}]           & \mathbf{1} & \begin{pmatrix} 1 & 2 & 3 & 4 \\ 5 & 6 & 7 & 8 \\ 9 & 10 & 11 & 12 \end{pmatrix} \\
& & & & \\
& 1 & 2 & 3 & 4 \\
& 5 & 6 & 7 & 8 \\
& 9 & 10 & 11 & 12
\end{pNiceMatrix}$
```

If LaTeX counters called `iRow` and `jCol` are defined in the document by packages other than `nicematrix` (or by the final user), they are shadowed in the environments of `nicematrix`.

³⁴We recall that the exterior “first row” (if it exists) has the number 0 and that the exterior “first column” (if it exists) has also the number 0.

The package `nicematrix` also provides commands in order to compose automatically matrices from a general pattern. These commands are `\AutoNiceMatrix`, `\pAutoNiceMatrix`, `\bAutoNiceMatrix`, `\vAutoNiceMatrix`, `\VAutoNiceMatrix` and `\BAutoNiceMatrix`.

These commands take in two mandatory arguments. The first is the format of the matrix, with the syntax $n-p$ where n is the number of rows and p the number of columns. The second argument is the pattern (it's a list of tokens which are inserted in each cell of the constructed matrix, excepted in the cells of the potential exterior rows and columns).

```
$C = \pAutoNiceMatrix{3-3}{C_{\arabic{iRow},\arabic{jCol}}}$
```

$$C = \begin{pmatrix} C_{1,1} & C_{1,2} & C_{1,3} \\ C_{2,1} & C_{2,2} & C_{2,3} \\ C_{3,1} & C_{3,2} & C_{3,3} \end{pmatrix}$$

12.6 The option light-syntax

The option `light-syntax` (inspired by the package `spalign`) allows the user to compose the arrays with a lighter syntax, which gives a better legibility of the TeX source.

When this option is used, one should use the semicolon for the end of a row and spaces or tabulations to separate the columns. However, as usual in the TeX world, the spaces after a control sequence are discarded and the elements between curly braces are considered as a whole.

```
$\begin{bNiceMatrix}[light-syntax,first-row,first-col]
{} a           b ;           a
a 2\cos a     {\cos a + \cos b} ;   2\cos a   \cos a + \cos b
b \cos a+\cos b { 2 \cos b }      \cos a + \cos b 2\cos b
\end{bNiceMatrix}$
```

It's possible to change the character used to mark the end of rows with the option `end-of-row`. As said before, the initial value is a semicolon.

When the option `light-syntax` is used, it is not possible to put verbatim material (for example with the command `\verb`) in the cells of the array.³⁵

12.7 Color of the delimiters

For the environements with delimiters (`{pNiceArray}`, `{pNiceMatrix}`, etc.), it's possible to change the color of the delimiters with the key `delimiters/color`.

```
$\begin{bNiceMatrix}[delimiters/color=red]
1 & 2 \\
3 & 4
\end{bNiceMatrix}$
```

$$\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix}$$

12.8 The environment `{NiceArrayWithDelims}`

In fact, the environment `{pNiceArray}` and its variants are based upon a more general environment, called `{NiceArrayWithDelims}`. The first two mandatory arguments of this environment are the left and right delimiters used in the construction of the matrix. It's possible to use `{NiceArrayWithDelims}` if we want to use atypical or asymmetrical delimiters.

```
$\begin{NiceArrayWithDelims}
{\downarrow}{\uparrow}{ccc}[margin]
1 & 2 & 3 \\
4 & 5 & 6 \\
7 & 8 & 9
\end{NiceArrayWithDelims}$
```

$$\begin{array}{|c c c|} \hline 1 & 2 & 3 \\ \hline 4 & 5 & 6 \\ \hline 7 & 8 & 9 \\ \hline \end{array}$$

³⁵The reason is that, when the option `light-syntax` is used, the whole content of the environment is loaded as a TeX argument to be analyzed. The environment doesn't behave in that case as a standard environment of LaTeX which only put TeX commands before and after the content.

13 Use of Tikz with nicematrix

13.1 The nodes corresponding to the contents of the cells

The package `nicematrix` creates a PGF/Tikz node for each (non-empty) cell of the considered array. These nodes are used to draw the dotted lines between the cells of the matrix (inter alia).

Caution : By default, no node is created in a empty cell.

However, it's possible to impose the creation of a node with the command `\NotEmpty`.³⁶

The nodes of a document must have distinct names. That's why the names of the nodes created by `nicematrix` contains the number of the current environment. Indeed, the environments of `nicematrix` are numbered by a internal global counter.

In the environment with the number n , the node of the row i and column j has for name `nm-n-i-j`.

The command `\NiceMatrixLastEnv` provides the number of the last environment of `nicematrix` (for LaTeX, it's a “fully expandable” command and not a counter).

However, it's advisable to use instead the key `name`. This key gives a name to the current environment. When the environment has a name, the nodes are accessible with the name “`name-i-j`” where `name` is the name given to the array and i and j the numbers of row and column. It's possible to use these nodes with PGF but the final user will probably prefer to use Tikz (which is a convenient layer upon PGF). However, one should remind that `nicematrix` doesn't load Tikz by default. In the following examples, we assume that Tikz has been loaded.

```
$\begin{pNiceMatrix} [name=mymatrix]
1 & 2 & 3 \\
4 & 5 & 6 \\
7 & 8 & 9
\end{pNiceMatrix}$
\tikz[remember picture,overlay]
\draw (mymatrix-2-2) circle (2mm) ;
```

$$\begin{pmatrix} 1 & 2 & 3 \\ 4 & \textcircled{5} & 6 \\ 7 & 8 & 9 \end{pmatrix}$$

Don't forget the options `remember picture` and `overlay`.

In the `\CodeAfter`, the things are easier : one must refer to the nodes with the form $i-j$ (we don't have to indicate the environment which is of course the current environment).

```
$\begin{pNiceMatrix}
1 & 2 & 3 \\
4 & 5 & 6 \\
7 & 8 & 9
\CodeAfter
\tikz \draw (2-2) circle (2mm) ;
\end{pNiceMatrix}$
```

$$\begin{pmatrix} 1 & 2 & 3 \\ 4 & \textcircled{5} & 6 \\ 7 & 8 & 9 \end{pmatrix}$$

In the following example, we have underlined all the nodes of the matrix (we explain below the technic used : cf. p. 46).

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix}$$

13.2 The “medium nodes” and the “large nodes”

In fact, the package `nicematrix` can create “extra nodes”: the “medium nodes” and the “large nodes”. The first ones are created with the option `create-medium-nodes` and the second ones with the option `create-large-nodes`.³⁷

³⁶One should note that, with that command, the cell is considered as non-empty, which has consequences for the continuous dotted lines (cf. p. 19) and the computation of the “corners” (cf. p. 10).

³⁷There is also an option `create-extra-nodes` which is an alias for the conjunction of `create-medium-nodes` and `create-large-nodes`.

These nodes are not used by `nicematrix` by default, and that's why they are not created by default.

The names of the “medium nodes” are constructed by adding the suffix “`-medium`” to the names of the “normal nodes”. In the following example, we have underlined the “medium nodes”. We consider that this example is self-explanatory.³⁸

$$\begin{pmatrix} a & \underline{a+b} & \underline{a+b+c} \\ a & \underline{a} & \underline{a+b} \\ a & \underline{a} & \underline{a} \end{pmatrix}$$

The names of the “large nodes” are constructed by adding the suffix “`-large`” to the names of the “normal nodes”. In the following example, we have underlined the “large nodes”. We consider that this example is self-explanatory.³⁹

$$\begin{pmatrix} a & \underline{a+b} & \underline{a+b+c} \\ \underline{a} & \underline{a} & \underline{a+b} \\ a & \underline{a} & \underline{a} \end{pmatrix}$$

The “large nodes” of the first column and last column may appear too small for some usage. That's why it's possible to use the options `left-margin` and `right-margin` to add space on both sides of the array and also space in the “large nodes” of the first column and last column. In the following example, we have used the options `left-margin` and `right-margin`.³⁹

$$\begin{pmatrix} a & \underline{a+b} & \underline{a+b+c} \\ \underline{a} & \underline{a} & \underline{a+b} \\ a & \underline{a} & \underline{a} \end{pmatrix}$$

It's also possible to add more space on both side of the array with the options `extra-left-margin` and `extra-right-margin`. These margins are not incorporated in the “large nodes”. It's possible to fix both values with the option `extra-margin` and, in the following example, we use `extra-margin` with the value 3 pt.

$$\begin{pmatrix} a & \underline{a+b} & \underline{a+b+c} \\ \underline{a} & \underline{a} & \underline{a+b} \\ a & \underline{a} & \underline{a} \end{pmatrix}$$

Be careful : These nodes are reconstructed from the contents of the cells of the array. Usually, they do not correspond to the cells delimited by the rules (if we consider that these rules are drawn).

Here is an array composed with the following code:

```
\large
\begin{NiceTabular}{wl{2cm}ll}[hvlines]
fraise & amande & abricot \\
prune & pêche & poire \\
noix & noisette & brugnon
\end{NiceTabular}
```

fraise	amande	abricot
prune	pêche	poire
noix	noisette	brugnon

Here, we have colored all the cells of the array with `\chessboardcolors`.

fraise	amande	abricot
prune	pêche	poire
noix	noisette	brugnon

³⁸There is no “large nodes” created in the exterior rows and columns (for these rows and columns, cf. p. 17).

³⁹The options `left-margin` and `right-margin` take dimensions as values but, if no value is given, the default value is used, which is `\arraycolsep` (by default: 5 pt). There is also an option `margin` to fix both `left-margin` and `right-margin` to the same value.

Here are the “large nodes” of this array (without use of `margin` nor `extra-margin`).

fraise	amande	abricot
prune	pêche	poire
noix	noisette	brugnon

The nodes we have described are not available by default in the `\CodeBefore` (described p. 12).

New 5.16 It’s possible to have these nodes available in the `\CodeBefore` by using the key `create-cell-nodes` of the keyword `\CodeBefore` (in that case, the nodes are created first before the construction of the array by using informations written on the `aux` file and created a second time during the construction of the array itself).

13.3 The nodes which indicate the position of the rules

The package `nicematrix` creates a PGF/Tikz node merely called i (with the classical prefix) at the intersection of the horizontal rule of number i and the vertical rule of number i (more specifically the potential position of those rules because maybe there are not actually drawn). The last node has also an alias called `last`. There is also a node called $i.5$ midway between the node i and the node $i+1$. These nodes are available in the `\CodeBefore` and the `\CodeAfter`.

1	1.5	tulipe
arum	2	lys
muguet	dahlia	violette mauve

If we use Tikz (we remind that `nicematrix` does not load Tikz by default, by only PGF, which is a sub-layer of Tikz), we can access, in the `\CodeAfter` but also in the `\CodeBefore`, to the intersection of the (potential) horizontal rule i and the (potential) vertical rule j with the syntax $(i-|j)$.

```
\begin{NiceMatrix}
\CodeBefore
\tikz \draw [fill=red!15] (7-|4) |- (8-|5) |- (9-|6) |- cycle ;
\Body
1 \\
1 & 1 \\
1 & 2 & 1 \\
1 & 3 & 3 & 1 \\
1 & 4 & 6 & 4 & 1 \\
1 & 5 & 10 & 10 & 5 & 1 \\
1 & 6 & 15 & 20 & 15 & 6 & 1 \\
1 & 7 & 21 & 35 & 35 & 21 & 7 & 1 \\
1 & 8 & 28 & 56 & 70 & 56 & 28 & 8 & 1
\end{NiceMatrix}
```

```

1
1 1
1 2 1
1 3 3 1
1 4 6 4 1
1 5 10 10 5 1
1 6 15 20 15 6 1
1 7 21 35 35 21 7 1
1 8 28 56 70 56 28 8 1

```

The nodes of the form $i.5$ may be used, for example to cross a row of a matrix (if Tikz is loaded).

```

$ \begin{pNiceArray}{ccc|c}
2 & 1 & 3 & 0 \\
3 & 3 & 1 & 0 \\
3 & 3 & 1 & 0
\CodeAfter
\tikz \draw [red] (3.5-|1) -- (3.5-|last) ;
\end{pNiceArray}

```

$$\left(\begin{array}{ccc|c} 2 & 1 & 3 & 0 \\ 3 & 3 & 1 & 0 \\ 3 & 3 & 1 & 0 \end{array} \right)$$

13.4 The nodes corresponding to the command \SubMatrix

The command `\SubMatrix` available in the `\CodeAfter` has been described p. 25.

If a command `\SubMatrix` has been used with the key `name` with an expression such as `name=MyName` three PGF/Tikz nodes are created with the names `MyName-left`, `MyName` and `MyName-right`.

The nodes `MyName-left` and `MyName-right` correspond to the delimiters left and right and the node `MyName` correspond to the submatrix itself.

In the following example, we have highlighted these nodes (the submatrix itself has been created with `\SubMatrix\{{2-2}\{3-3\}\}`).

$$\left(\begin{array}{cccc} 121 & 23 & 345 & 345 \\ 45 & \left\{ \begin{array}{cc} 346 & 863 \end{array} \right\} 444 & & \\ 3462 & \left[\begin{array}{cc} 38458 & 34 \end{array} \right] 294 & & \\ 34 & 7 & 78 & 309 \end{array} \right)$$

14 API for the developers

The package `nicematrix` provides two variables which are internal but public⁴⁰:

- `\g_nicematrix_code_before_tl` ;
- `\g_nicematrix_code_after_tl`.

These variables contain the code of what we have called the “code-before” and the “code-after”. The developer can use them to add code from a cell of the array (the affectation must be global, allowing to exit the cell, which is a TeX group).

One should remark that the use of `\g_nicematrix_code_before_tl` needs one compilation more (because the instructions are written on the `aux` file to be used during the next run).

Example : We want to write a command `\hatchcell` to hatch the current cell (with an optional argument between brackets for the color). It’s possible to program such command `\hatchcell` as follows, explicitly using the public variable `\g_nicematrix_code_before_tl` (this code requires the Tikz library `patterns`: `\usetikzlibrary{patterns}`).

```

ExplSyntaxOn
\cs_new_protected:Nn \__pantigny_hatch:nnn
{
    \tikz \fill [ pattern = north-west-lines , pattern~color = #3 ]
        ( #1 -| #2) rectangle ( \int_eval:n { #1 + 1 } -| \int_eval:n { #2 + 1 } ) ;
}

\NewDocumentCommand \hatchcell { ! O { black } }
{
    \tl_gput_right:Nx \g_nicematrix_code_before_tl
}

```

⁴⁰According to the LaTeX3 conventions, each variable with name beginning with `\g_nicematrix` ou `\l_nicematrix` is public and each variable with name beginning with `\g_nicematrix` or `\l_nicematrix` is private.

```

    { \__pantigny_hatch:nnn { \arabic { iRow } } { \arabic { jCol } } { #1 } }
}
\ExplSyntaxOff

```

Here is an example of use:

```
\begin{NiceTabular}{ccc}[hvlines]
Tokyo & Paris & London \\
Lima & \hatchcell[blue!30]{Oslo} & Miami \\
Los Angeles & Madrid & Roma
\end{NiceTabular}
```

Tokyo	Paris	London
Lima	 Oslo	Miami
Los Angeles	Madrid	Roma

15 Technical remarks

15.1 Definition of new column types

The package `nicematrix` provides the command `\OnlyMainNiceMatrix` which is meant to be used in definitions of new column types. Its argument is evaluated if and only if we are in the main part of the array, that is to say not in a potential exterior row.

For example, one may wish to define a new column type `?` in order to draw a (black) heavy rule of width 1 pt. The following definition will do the job⁴¹:

```
\newcolumntype{?}{!{\OnlyMainNiceMatrix{\vrule width 1 pt}}}
```

The heavy vertical rule won't extend in the exterior rows.⁴²

```
$\begin{pNiceArray}{cc?cc}[first-row,last-row=3]
C_1 & C_2 & C_3 & C_4 \\
a & b & c & d \\
e & f & g & h \\
C_1 & C_2 & C_3 & C_4
\end{pNiceArray}$
```

$$\left(\begin{array}{cc|cc} C_1 & C_2 & C_3 & C_4 \\ a & b & c & d \\ e & f & g & h \\ \hline C_1 & C_2 & C_3 & C_4 \end{array} \right)$$

This specifier `?` may be used in the standard environments `{tabular}` and `{array}` (of the package `array`) and, in this case, the command `\OnlyMainNiceMatrix` is no-op.

15.2 Diagonal lines

By default, all the diagonal lines⁴³ of a same array are “parallelized”. That means that the first diagonal line is drawn and, then, the other lines are drawn parallel to the first one (by rotation around the left-most extremity of the line). That's why the position of the instructions `\Ddots` in the array can have a marked effect on the final result.

In the following examples, the first `\Ddots` instruction is written in color:

Example with parallelization (default):

```
$A = \begin{pNiceMatrix}
1 & \cdots & & & \\
& \Ddots & & & \\
a+b & & \vdots & & \\
& \ddots & & & \\
& & a+b & & 1
\end{pNiceMatrix}$
```

$$A = \begin{pmatrix} 1 & \cdots & & & 1 \\ & \ddots & & & \vdots \\ a+b & & \ddots & & \vdots \\ & \ddots & & \ddots & \vdots \\ & & a+b & \cdots & a+b & 1 \end{pmatrix}$$

⁴¹The command `\vrule` is a TeX (and not LaTeX) command.

⁴²Of course, such rule is defined by the classical technics of `nicematrix` and, for this reason, won't cross the double rules of `\hline\hline`.

⁴³We speak of the lines created by `\Ddots` and not the lines created by a command `\line` in `code-after`.

```
$A = \begin{pNiceMatrix}
1 & \cdots & & 1 \\
1+b & & \cdots & \cdots & \backslash Vdots \\
\backslash Vdots & \backslash Ddots & \backslash Ddots & & \\
a+b & \cdots & a+b & & 1 \\
\end{pNiceMatrix}$
```

$$A = \begin{pmatrix} 1 & \cdots & \cdots & \cdots & 1 \\ a+b & \cdots & \cdots & \cdots & \\ \vdots & & & & \\ a+b & \cdots & a+b & \cdots & 1 \end{pmatrix}$$

It's possible to turn off the parallelization with the option `parallelize-diags` set to `false`:

The same example without parallelization:

$$A = \begin{pmatrix} 1 & \cdots & \cdots & \cdots & 1 \\ a+b & \cdots & \cdots & \cdots & \\ \vdots & & & & \\ a+b & \cdots & a+b & \cdots & 1 \end{pmatrix}$$

It's possible to specify the instruction `\Ddots` which will be drawn first (and which will be used to draw the other diagonal dotted lines when the parallelization is in force) with the key `draw-first:\Ddots[draw-first]`.

15.3 The “empty” cells

An instruction like `\Ldots`, `\Cdots`, etc. tries to determine the first non-empty cell on both sides. However, an “empty cell” is not necessarily a cell with no TeX content (that is to say a cell with no token between the two ampersands `&`). The precise rules are as follow.

- An implicit cell is empty. For example, in the following matrix:

```
\begin{pmatrix}
a & b \\
c
\end{pmatrix}
```

the last cell (second row and second column) is empty.

- Each cell whose TeX output has a width equal to zero is empty.
- A cell containing the command `\NotEmpty` is not empty (and a PGF/Tikz node) is created in that cell.
- A cell with a command `\Hspace` (or `\Hspace*`) is empty. This command `\Hspace` is a command defined by the package `nicematrix` with the same meaning as `\hspace` except that the cell where it is used is considered as empty. This command can be used to fix the width of some columns of the matrix without interfering with `nicematrix`.
- A cell of a column of type `p`, `m` or `t` is always considered as not empty. *Caution* : One should not rely upon that point because it may change if a future version of `nicematrix`.

15.4 The option `exterior-arraycolsep`

The environment `{array}` inserts an horizontal space equal to `\arraycolsep` before and after each column. In particular, there is a space equal to `\arraycolsep` before and after the array. This feature of the environment `{array}` was probably not a good idea⁴⁴. The environment `{matrix}` of `amsmath` and its variants (`{pmatrix}`, `{vmatrix}`, etc.) of `amsmath` prefer to delete these spaces

⁴⁴In the documentation of `{amsmath}`, we can read: *The extra space of `\arraycolsep` that `array` adds on each side is a waste so we remove it [in `{matrix}`] (perhaps we should instead remove it from `array` in general, but that's a harder task).*

with explicit instructions `\hskip -\arraycolsep`⁴⁵. The package `nicematrix` does the same in all its environments, `{NiceArray}` included. However, if the user wants the environment `{NiceArray}` behaving by default like the environment `{array}` of `array` (for example, when adapting an existing document) it's possible to control this behaviour with the option `exterior-arraycolsep`, set by the command `\NiceMatrixOptions`. With this option, exterior spaces of length `\arraycolsep` will be inserted in the environments `{NiceArray}` (the other environments of `nicematrix` are not affected).

15.5 Incompatibilities

The package `nicematrix` is not fully compatible with the package `arydshln` (because this package redefines many internal of `array`).

Anyway, in order to use `arydshln`, one must first free the letter ":" by giving a new letter for the vertical dotted rules of `nicematrix`:

```
\NiceMatrixOptions{letter-for-dotted-lines=;}
```

Up to now, the package `nicematrix` is not compatible with `aastex63`. If you want to use `nicematrix` with `aastex63`, send me an email and I will try to solve the incompatibilities.

the package `nicematrix` is not compatible with the class `ieeaccess` (because that class is not compatible with PGF/Tikz).

16 Examples

16.1 Notes in the tabulars

The tools provided by `nicematrix` for the composition of the tabular notes have been presented in the section 11 p. 26.

Let's consider that we wish to number the notes of a tabular with stars.⁴⁶

First, we write a command `\stars` similar the well-known commands `\arabic`, `\alph`, `\Alpha`, etc. which produces a number of stars equal to its argument⁴⁷

```
\ExplSyntaxOn
\NewDocumentCommand \stars { m }
  { \prg_replicate:nn { \value{#1} } { $ \star $ } }
\ExplSyntaxOff
```

Of course, we change the style of the labels with the key `notes/style`. However, it would be interesting to change also some parameters in the type of list used to compose the notes at the end of the tabular. First, we required a composition flush right for the labels with the setting `align=right`. Moreover, we want the labels to be composed on a width equal to the width of the widest label. The widest label is, of course, the label with the greatest number of stars. We know that number: it is equal to `\value{tabularnote}` (because `tabularnote` is the LaTeX counter used by `\tabularnote` and, therefore, at the end of the tabular, its value is equal to the total number of tabular notes). We use the key `widest*` of `enumitem` in order to require a width equal to that value: `widest*=\value{tabularnote}`.

⁴⁵ And not by inserting `@{}` on both sides of the preamble of the array. As a consequence, the length of the `\hline` is not modified and may appear too long, in particular when using square brackets.

⁴⁶ Of course, it's realistic only when there is very few notes in the tabular.

⁴⁷ In fact: the value of its argument.

```

\niceMatrixOptions
{
  notes =
  {
    style = \stars{#1} ,
    enumitem-keys =
    {
      widest* = \value{tabularnote} ,
      align = right
    }
  }
}

\begin{NiceTabular}{llr}[first-row,code-for-first-row = \bfseries]
\toprule
Last name & First name & Birth day \\
\midrule
Achard\tabularnote{Achard is an old family of the Poitou.}
& Jacques & 5 juin 1962 \\
Lefebvre\tabularnote{The name Lefebvre is an alteration of the name Lefebure.}
& Mathilde & 23 mai 1988 \\
Vanesse & Stephany & 30 octobre 1994 \\
Dupont & Chantal & 15 janvier 1998 \\
\bottomrule
\end{NiceTabular}

```

Last name	First name	Birth day
Achard*	Jacques	June 5, 2005
Lefebvre**	Mathilde	January 23, 1975
Vanesse	Stephany	October 30, 1994
Dupont	Chantal	January 15, 1998

*Achard is an old family of the Poitou.
 **The name Lefebvre is an alteration of the name Lefebure.

16.2 Dotted lines

An example with the resultant of two polynoms:

```

\setlength{\extrarowheight}{1mm}
\[\begin{vNiceArray}{cccc:ccc}[columns-width=6mm]
a_0 & & & & b_0 & & \\
a_1 & \&\dots & & b_1 & \&\dots & \\
\vdots & \&\dots & & \vdots & \&\dots & \\
a_p & \&&a_0 & & b_1 & \\
& \&\dots &&a_1 & b_q & \&\dots & \\
& \&&\vdots & & \&\dots & \\
& \&&a_p & & b_q &
\end{vNiceArray}\]

```

The diagram illustrates two sets of points, a_i and b_i , arranged in descending order from top-left to bottom-right. The a_i points are located on the left side, and the b_i points are on the right side. Dotted lines connect corresponding points a_i and b_i across the vertical axis.

An example for a linear system:

```

\$\\begin{pNiceArray}{*6c|c}[nullify-dots,last-col,code-for-last-col=\\scriptstyle]
1      & 1 & 1 & \\Cdots &   & 1      & 0      & \\
0      & 1 & 0 & \\Cdots &   & 0      &       & L_2 \\gets L_2-L_1 \\
0      & 0 & 1 & \\Ddots &   & \\Vdots &       & L_3 \\gets L_3-L_1 \\
          &   &   & \\Ddots &   &       & \\Vdots & \\Vdots \\
\\Vdots &   &   & \\Ddots &   & 0      & \\
0      &   &   & \\Cdots & 0 & 1      & 0      & L_n \\gets L_n-L_1
\\end{pNiceArray}$

```

$$\left(\begin{array}{cccc|c} 1 & 1 & 1 & \dots & 1 & 0 \\ 0 & 1 & 0 & \dots & 0 & \vdots \\ 0 & 0 & 1 & \ddots & \ddots & L_2 \leftarrow L_2 - L_1 \\ \vdots & \ddots & & & 0 & L_3 \leftarrow L_3 - L_1 \\ \vdots & & & & & \vdots \\ 0 & \dots & \dots & \dots & 0 & 1 \\ \end{array} \right) \quad L_n \leftarrow L_n - L_1$$

16.3 Dotted lines which are no longer dotted

The option `line-style` controls the style of the lines drawn by `\Ldots`, `\Cdots`, etc. Thus, it's possible with these commands to draw lines which are not longer dotted.

```

\NiceMatrixOptions{code-for-first-row = \scriptstyle,code-for-first-col = \scriptstyle }
\setcounter{MaxMatrixCols}{12}
\newcommand{\blue}{\color{blue}}
\begin{pNiceMatrix}[last-row,last-col,nullify-dots,xdots/line-style={dashed,blue}]
1 & & \Vdots & & & \Vdots \\
& \Ddots[line-style=standard] \\
& 1 \\
\cdots[color=blue,line-style=dashed]& & \blue 0 &
\cdots & \blue 1 & \cdots & \blue \leftarrow i \\
& & 1 \\
& & \Vdots & \Ddots[line-style=standard] & \Vdots \\
& & & 1 \\
\cdots & \cdots & \blue 1 & \cdots & \blue 0 & \cdots & \cdots & \blue \leftarrow j \\
& & & & & & & 1 \\
& & & & & \Ddots[line-style=standard] \\
& & & \Vdots & & \Vdots & & 1 \\
& & & \blue \overrightarrow{i} & & \blue \overrightarrow{j} \\
\end{pNiceMatrix}

```

In fact, it's even possible to draw solid lines with the commands `\Cdots`, `\Vdots`, etc.

```
\NiceMatrixOptions
{nullify-dots,code-for-first-col = \color{blue},code-for-first-col=\color{blue}}
$\begin{pNiceMatrix}[first-row,first-col]
    & \& \Ldots[line-style={solid,<->},shorten=0pt]^{\text{ columns}} \\
    & 1 \& 1 \& 1 \& \Ldots & 1 \\
    & 1 \& 1 \& 1 \& 1 \& 1 \\
\end{pNiceMatrix}
$
```

n columns						
n rows	1	1	1	1	1	1
	1	1	1	1	1	1
	1	1	1	1	1	1
	1	1	1	1	1	1
	1	1	1	1	1	1
	1	1	1	1	1	1

16.4 Stacks of matrices

We often need to compose mathematical matrices on top of each other (for example for the resolution of linear systems).

In order to have the columns aligned one above the other, it's possible to fix a width for all the columns. That's what is done in the following example with the environment `{NiceMatrixBlock}` and its option `auto-columns-width`.

```

\begin{NiceMatrixBlock}[auto-columns-width]
\NiceMatrixOptions
{
    light-syntax,
    last-col, code-for-last-col = \color{blue} \scriptstyle,
}
\setlength{\extrarowheight}{1mm}

$\begin{pNiceArray}{rrrr|r}
12 & -8 & 7 & 5 & 3 {} ; \\
3 & -18 & 12 & 1 & 4 & ; \\
-3 & -46 & 29 & -2 & -15 & ; \\
9 & 10 & -5 & 4 & 7
\end{pNiceArray}$

```

```

\smallskip
$\begin{pNiceArray}{rrrr|r}
12 & -8 & 7 & 5 & 3 \\
0 & 64 & -41 & 1 & 19 \\
0 & -192 & 123 & -3 & -57 \\
0 & -64 & 41 & -1 & -19 \\
\end{pNiceArray}$

```

```

\smallskip
$\begin{pNiceArray}{rrrr|r}
12 & -8 & 7 & 5 & 3 \\
0 & 64 & -41 & 1 & 19 \\
0 & 0 & 0 & 0 & \gets 3L_2 + L_3 \\
\end{pNiceArray}$

```

```

\smallskip
$\begin{pNiceArray}{rrrr|r}
12 & -8 & 7 & 5 & 3 \\
0 & 64 & -41 & 1 & 19 \\
0 & -192 & 123 & -3 & -57 \\
0 & -64 & 41 & -1 & -19 \\
\end{pNiceArray}$

```

\end{NiceMatrixBlock}

$$\left(\begin{array}{rrrr|r}
12 & -8 & 7 & 5 & 3 \\
3 & -18 & 12 & 1 & 4 \\
-3 & -46 & 29 & -2 & -15 \\
9 & 10 & -5 & 4 & 7
\end{array} \right)$$

$$\left(\begin{array}{rrrr|r}
12 & -8 & 7 & 5 & 3 \\
0 & 64 & -41 & 1 & 19 \\
0 & -192 & 123 & -3 & -57 \\
0 & -64 & 41 & -1 & -19
\end{array} \right) \begin{matrix} L_2 \leftarrow L_1 - 4L_2 \\ L_3 \leftarrow L_1 + 4L_3 \\ L_4 \leftarrow 3L_1 - 4L_4 \end{matrix}$$

$$\left(\begin{array}{rrrr|r}
12 & -8 & 7 & 5 & 3 \\
0 & 64 & -41 & 1 & 19 \\
0 & 0 & 0 & 0 & 0
\end{array} \right) \begin{matrix} L_3 \leftarrow 3L_2 + L_3 \end{matrix}$$

$$\left(\begin{array}{rrrr|r}
12 & -8 & 7 & 5 & 3 \\
0 & 64 & -41 & 1 & 19
\end{array} \right)$$

However, one can see that the last matrix is not perfectly aligned with others. That's why, in LaTeX, the parenthesis have not exactly the same width (smaller parenthesis are a bit slimmer).

In order to solve that problem, it's possible to require the delimiters to be composed with the maximal width, thanks to the boolean key `delimiters/max-width`.

```

\begin{NiceMatrixBlock}[auto-columns-width]
\niceMatrixOptions
{
    delimiters/max-width,
    light-syntax,
    last-col, code-for-last-col = \color{blue}\scriptstyle,
}
\setlength{\extrarowheight}{1mm}

$\begin{pNiceArray}{rrrr|r}
12 & -8 & 7 & 5 & 3 \\
3 & -18 & 12 & 1 & 4 \\
-3 & -46 & 29 & -2 & -15 \\
9 & 10 & -5 & 4 & 7
\end{pNiceArray}$

```

```

\end{pNiceArray}$
...
\end{NiceMatrixBlock}


$$\left( \begin{array}{cccc|c} 12 & -8 & 7 & 5 & 3 \\ 3 & -18 & 12 & 1 & 4 \\ -3 & -46 & 29 & -2 & -15 \\ 9 & 10 & -5 & 4 & 7 \end{array} \right)$$


$$\left( \begin{array}{cccc|c} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & -192 & 123 & -3 & -57 \\ 0 & -64 & 41 & -1 & -19 \end{array} \right) \begin{matrix} L_2 \leftarrow L_1 - 4L_2 \\ L_3 \leftarrow L_1 + 4L_3 \\ L_4 \leftarrow 3L_1 - 4L_4 \end{matrix}$$


$$\left( \begin{array}{cccc|c} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \\ 0 & 0 & 0 & 0 & 0 \end{array} \right) \begin{matrix} L_3 \leftarrow 3L_2 + L_3 \end{matrix}$$


$$\left( \begin{array}{cccc|c} 12 & -8 & 7 & 5 & 3 \\ 0 & 64 & -41 & 1 & 19 \end{array} \right)$$


```

If you wish an alignment of the different matrices without the same width for all the columns, you can construct a unique array and place the parenthesis with commands `\SubMatrix` in the `\CodeAfter`. Of course, that array can't be broken by a page break.

```

\setlength{\extrarowheight}{1mm}
\begin{NiceMatrix}[ r, last-col=6, code-for-last-col = \scriptstyle \color{blue} ]
12 & -8 & 7 & 5 & 3 \\
3 & -18 & 12 & 1 & 4 \\
-3 & -46 & 29 & -2 & -15 \\
9 & 10 & -5 & 4 & 7 \\[1mm]
12 & -8 & 7 & 5 & 3 \\
0 & 64 & -41 & 1 & 19 \\
0 & 0 & 0 & 0 & 0 \\[1mm]
12 & -8 & 7 & 5 & 3 \\
0 & 64 & -41 & 1 & 19
\CodeAfter [sub-matrix/vlines=4]
\SubMatrix({1-1}{4-5})
\SubMatrix({5-1}{8-5})
\SubMatrix({9-1}{11-5})
\SubMatrix({12-1}{13-5})
\end{NiceMatrix}

```

$$\left(\begin{array}{cccc|c}
 12 & -8 & 7 & 5 & 3 \\
 3 & -18 & 12 & 1 & 4 \\
 -3 & -46 & 29 & -2 & -15 \\
 9 & 10 & -5 & 4 & 7
 \end{array} \right)$$

$$\left(\begin{array}{cccc|c}
 12 & -8 & 7 & 5 & 3 \\
 0 & 64 & -41 & 1 & 19 \\
 0 & -192 & 123 & -3 & -57 \\
 0 & -64 & 41 & -1 & -19
 \end{array} \right) \begin{matrix} L_2 \leftarrow L_1 - 4L_2 \\ L_3 \leftarrow L_1 + 4L_3 \\ L_4 \leftarrow 3L_1 - 4L_4 \end{matrix}$$

$$\left(\begin{array}{cccc|c}
 12 & -8 & 7 & 5 & 3 \\
 0 & 64 & -41 & 1 & 19 \\
 0 & 0 & 0 & 0 & 0 \\
 12 & -8 & 7 & 5 & 3
 \end{array} \right) \begin{matrix} L_3 \leftarrow 3L_2 + L_3 \end{matrix}$$

$$\left(\begin{array}{cccc|c}
 12 & -8 & 7 & 5 & 3 \\
 0 & 64 & -41 & 1 & 19 \\
 0 & 0 & 0 & 0 & 0 \\
 0 & 64 & -41 & 1 & 19
 \end{array} \right)$$

16.5 How to highlight cells of a matrix

In order to highlight a cell of a matrix, it's possible to "draw" that cell with the key `draw` of the command `\Block` (this is one of the uses of a mono-cell block⁴⁸).

```
$\begin{pNiceArray}{>{\strut}cccc}[margin, rules/color=blue]
\Block[draw]{}{a_{11}} & a_{12} & a_{13} & a_{14} \\
a_{21} & \Block[draw]{}{a_{22}} & a_{23} & a_{24} \\
a_{31} & a_{32} & \Block[draw]{}{a_{33}} & a_{34} \\
a_{41} & a_{42} & a_{43} & \Block[draw]{}{a_{44}}
\end{pNiceArray}$
```

$$\left(\begin{array}{cccc}
 \boxed{a_{11}} & a_{12} & a_{13} & a_{14} \\
 a_{21} & \boxed{a_{22}} & a_{23} & a_{24} \\
 a_{31} & a_{32} & \boxed{a_{33}} & a_{34} \\
 a_{41} & a_{42} & a_{43} & \boxed{a_{44}}
 \end{array} \right)$$

We should remark that the rules we have drawn are drawn *after* the construction of the array and thus, they don't spread the cells of the array. We recall that, on the other side, the commands `\hline` and `\Hline`, the specifier "`|`" and the options `hlines`, `vlines` and `hvlines` spread the cells.⁴⁹

It's possible to color a row with `\rowcolor` in the `code-before` (or with `\rowcolor` in the first cell of the row if the key `colortbl-like` is used—even when `colortbl` is not loaded).

```
\begin{pNiceArray}{>{\strut}cccc}[margin, extra-margin=2pt, colortbl-like]
\rowcolor{red!15}A_{11} & A_{12} & A_{13} & A_{14} \\
A_{21} & \rowcolor{red!15}A_{22} & A_{23} & A_{24} \\
A_{31} & A_{32} & \rowcolor{red!15}A_{33} & A_{34} \\
A_{41} & A_{42} & A_{43} & \rowcolor{red!15}A_{44}
\end{pNiceArray}
```

⁴⁸We recall that, if the first mandatory argument of the command `\Block` is left empty, that means that the block is a mono-cell block

⁴⁹For the command `\cline`, see the remark p. 8.

$$\begin{pmatrix} A_{11} & A_{12} & A_{13} & A_{14} \\ A_{21} & A_{22} & A_{23} & A_{24} \\ A_{31} & A_{32} & A_{33} & A_{34} \\ A_{41} & A_{42} & A_{43} & A_{44} \end{pmatrix}$$

However, it's not possible to do a fine tuning. That's why we describe now a method to highlight a row of the matrix. We create a rectangular Tikz node which encompasses the nodes of the second row with the Tikz library `fit`. This Tikz node is filled after the construction of the matrix. In order to see the text *under* this node, we have to use transparency with the `blend mode` equal to `multiply`.

Caution : Some PDF readers are not able to show transparency.⁵⁰

That example and the following ones require Tikz (by default, `nicematrix` only loads PGF, which is a sub-layer of Tikz) and the Tikz library `fit`. The following lines in the preamble of your document do the job:

```
\usepackage{tikz}
\usetikzlibrary{fit}
```

We create a rectangular Tikz node which encompasses the nodes of the second row by using the tools of the Tikz library `fit`. Those nodes are not available by default in the `\CodeBefore` (for efficiency). We have to require their creation with the key `create-cell-nodes` of the keyword `\CodeBefore`.

```
\tikzset{highlight/.style={rectangle,
    fill=red!15,
    rounded corners = 0.5 mm,
    inner sep=1pt,
    fit=#1}}

$\begin{bNiceMatrix}
\CodeBefore [create-cell-nodes]
\tikz \node [highlight = (2-1) (2-3)] {} ;
\Body
0 & \Cdots & 0 \\
1 & \Cdots & 1 \\
0 & \Cdots & 0 \\
\end{bNiceMatrix}$
```

$$\begin{bmatrix} 0 & \dots & 0 \\ 1 & \dots & 1 \\ 0 & \dots & 0 \end{bmatrix}$$

We consider now the following matrix. If we want to highlight each row of this matrix, we can use the previous technique three times.

```
\[\begin{pNiceArray}{ccc}[last-col]
\CodeBefore [create-cell-nodes]
\begin{tikzpicture}
\node [highlight = (1-1) (1-3)] {} ;
\node [highlight = (2-1) (2-3)] {} ;
\node [highlight = (3-1) (3-3)] {} ;
\end{tikzpicture}
\Body
```

⁵⁰In Overleaf, the “built-in” PDF viewer does not show transparency. You can switch to the “native” viewer in that case.

```

a & a + b & a + b + c & L_1 \\
a & a     & a + b     & L_2 \\
a & a     & a         & L_3
\end{pNiceArray}\]

```

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix} L_1 \\ L_2 \\ L_3$$

The result may seem disappointing. We can improve it by using the “medium nodes” instead of the “normal nodes”.

```

\[\begin{pNiceArray}{ccc}[last-col,create-medium-nodes]
\CodeBefore [create-cell-nodes]
\begin{tikzpicture} [name suffix = -medium]
\node [highlight = (1-1) (1-3)] {} ;
\node [highlight = (2-1) (2-3)] {} ;
\node [highlight = (3-1) (3-3)] {} ;
\end{tikzpicture}
\Body
a & a + b & a + b + c & L_1 \\
a & a     & a + b     & L_2 \\
a & a     & a         & L_3
\end{pNiceArray}\]

```

$$\begin{pmatrix} a & a+b & a+b+c \\ a & a & a+b \\ a & a & a \end{pmatrix} L_1 \\ L_2 \\ L_3$$

16.6 Utilisation of \SubMatrix in the \CodeBefore

In the following example, we illustrate the mathematical product of two matrices. The whole figure is an environment `{NiceArray}` and the three pairs of parenthesis have been added with `\SubMatrix` in the `\CodeBefore`.

$$L_i \begin{pmatrix} a_{11} & \dots & a_{1n} \\ \vdots & & \vdots \\ a_{i1} & \dots & a_{ik} & \dots & a_{in} \\ \vdots & & & & \vdots \\ a_{n1} & \dots & \dots & \dots & a_{nn} \end{pmatrix} \begin{pmatrix} \vdots & & & & \vdots \\ \dots & \dots & \dots & \dots & \dots \\ \vdots & & & & \vdots \\ b_{1j} & \dots & b_{1n} \\ \vdots & & \vdots \\ b_{kj} \\ \vdots \\ b_{nj} & \dots & b_{nn} \end{pmatrix} = C_{ij}$$

```

\tikzset{highlight/.style={rectangle,
    fill=red!15,
    rounded corners = 0.5 mm,
    inner sep=1pt,
    fit=#1}}

```

```

\[\begin{NiceArray}{*{6}{c}}@{\hspace{6mm}}*{5}{c}][nullify-dots]
\CodeBefore [create-cell-nodes]
\SubMatrix({2-7}{6-11})
\SubMatrix({7-2}{11-6})
\SubMatrix({7-7}{11-11})
\begin{tikzpicture}
\node [highlight = (9-2) (9-6)] { } ;
\node [highlight = (2-9) (6-9)] { } ;
\end{tikzpicture}
\end{NiceArray}
\Body
& & & & & & \color{blue}\scriptstyle C_j \\
& & & & & & b_{11} & \cdots & b_{1j} & \cdots & b_{in} \\
& & & & & & \vdots & & \vdots & & \vdots \\
& & & & & & & & & b_{kj} \\
& & & & & & & & & \vdots \\
& & & & & & & & & b_{n1} & \cdots & b_{nj} & \cdots & b_{nn} \\
& a_{11} & \cdots & & & a_{1n} \\
& \vdots & & & & \vdots & & & & \vdots \\
\color{blue}\scriptstyle L_i
& a_{i1} & \cdots & a_{ik} & \cdots & a_{in} & \cdots & c_{ij} \\
& \vdots & & & & \vdots & & \\
& a_{n1} & \cdots & & & a_{nn} & \cdots & \\
\CodeAfter
\tikz \draw [gray,shorten > = 1mm, shorten < = 1mm] (9-4.north) to [bend left] (4-9.west) ;
\end{NiceArray}

```

17 Implementation

By default, the package `nicematrix` doesn't patch any existing code.

However, when the option `renew-dots` is used, the commands `\cdots`, `\ldots`, `\dots`, `\vdots`, `\ddots` and `\iddots` are redefined in the environments provided by `nicematrix` as explained previously. In the same way, if the option `renew-matrix` is used, the environment `{matrix}` of `amsmath` is redefined.

On the other hand, the environment `{array}` is never redefined.

Of course, the package `nicematrix` uses the features of the package `array`. It tries to be independent of its implementation. Unfortunately, it was not possible to be strictly independent. For example, the package `nicematrix` relies upon the fact that the package `{array}` uses `\ialign` to begin the `\halign`.

Declaration of the package and packages loaded

The prefix `nicematrix` has been registered for this package.

See: [<@=@=nicematrix>](http://mirrors.ctan.org/macros/latex/contrib/13kernel/13prefixes.pdf)

First, we load `pgfcore` and the module `shapes`. We do so because it's not possible to use `\usepgfmodule` in `\ExplSyntaxOn`.

```

1 \RequirePackage{pgfcore}
2 \usepgfmodule{shapes}

```

We give the traditional declaration of a package written with `expl3`:

```

3 \RequirePackage{13keys2e}
4 \ProvidesExplPackage
5   {nicematrix}
6   {\myfiledate}
7   {\myfileversion}
8   {Enhanced arrays with the help of PGF/TikZ}

```

The command for the treatment of the options of `\usepackage` is at the end of this package for technical reasons.

We load some packages. The package `xparse` is still loaded for use on Overleaf.

```

9  \RequirePackage { xparse }
10 \RequirePackage { array }
11 \RequirePackage { amsmath }

12 \cs_new_protected:Npn \@@_error:n { \msg_error:nn { nicematrix } }
13 \cs_new_protected:Npn \@@_error:nn { \msg_error:nnn { nicematrix } }
14 \cs_new_protected:Npn \@@_error:nnn { \msg_error:nnnn { nicematrix } }
15 \cs_new_protected:Npn \@@_fatal:n { \msg_fatal:nn { nicematrix } }
16 \cs_new_protected:Npn \@@_fatal:nn { \msg_fatal:nnn { nicematrix } }
17 \cs_new_protected:Npn \@@_msg_new:nn { \msg_new:nnn { nicematrix } }
18 \cs_new_protected:Npn \@@_msg_new:nnn { \msg_new:nnnn { nicematrix } }

19 \cs_new_protected:Npn \@@_msg_redirect_name:nn
20   { \msg_redirect_name:nnn { nicematrix } }
```

Technical definitions

```

21 \bool_new:N \c_@@_in_preamble_bool
22 \bool_set_true:N \c_@@_in_preamble_bool
23 \AtBeginDocument { \bool_set_false:N \c_@@_in_preamble_bool }

24 \bool_new:N \c_@@_arydshln_loaded_bool
25 \bool_new:N \c_@@_booktabs_loaded_bool
26 \bool_new:N \c_@@_enumitem_loaded_bool
27 \bool_new:N \c_@@_tikz_loaded_bool
28 \AtBeginDocument
29   {
30     \@ifpackageloaded { arydshln }
31       { \bool_set_true:N \c_@@_arydshln_loaded_bool }
32     { }
33     \@ifpackageloaded { booktabs }
34       { \bool_set_true:N \c_@@_booktabs_loaded_bool }
35     { }
36     \@ifpackageloaded { enumitem }
37       { \bool_set_true:N \c_@@_enumitem_loaded_bool }
38     { }
39     \@ifpackageloaded { tikz }
40   }
```

In some constructions, we will have to use a `{pgfpicture}` which *must* be replaced by a `{tikzpicture}` if Tikz is loaded. However, this switch between `{pgfpicture}` and `{tikzpicture}` can't be done dynamically with a conditional because, when the Tikz library `external` is loaded by the user, the pair `\tikzpicture-\endtikzpicture` (or `\begin{tikzpicture}-\end{tikzpicture}`) must be statically “visible” (even when externalization is not activated).

That's why we create `\c_@@_pgfortikzpicture_tl` and `\c_@@_endpgfortikzpicture_tl` which will be used to construct in a `\AtBeginDocument` the correct version of some commands.

```

41   \bool_set_true:N \c_@@_tikz_loaded_bool
42   \tl_const:Nn \c_@@_pgfortikzpicture_tl { \exp_not:N \tikzpicture }
43   \tl_const:Nn \c_@@_endpgfortikzpicture_tl { \exp_not:N \endtikzpicture }
44 }
45 {
46   \tl_const:Nn \c_@@_pgfortikzpicture_tl { \exp_not:N \pgfpicture }
47   \tl_const:Nn \c_@@_endpgfortikzpicture_tl { \exp_not:N \endpgfpicture }
48 }
49 }
```

We test whether the current class is `revtex4-1` (deprecated) or `revtex4-2` because these classes redefines `\array` (of `array`) in a way incompatible with our programmation. At the date January 2021, the current version `revtex4-2` is 4.2e (compatible with `booktabs`).

```

50 \bool_new:N \c_@@_revtex_bool
51 \ifclassloaded { revtex4-1 }
52   { \bool_set_true:N \c_@@_revtex_bool }
53   { }
54 \ifclassloaded { revtex4-2 }
55   { \bool_set_true:N \c_@@_revtex_bool }
56   { }

```

Maybe one of the previous classes will be loaded inside another class... We try to detect that situation.

```

57 \cs_if_exist:NT \rvtx@iffORMAT@geq { \bool_set_true:N \c_@@_revtex_bool }

58 \cs_generate_variant:Nn \tl_if_single_token_p:n { V }

```

The following regex will be used to modify the preamble of the array when the key `colortbl-like` is used.

```
59 \regex_const:Nn \c_@@_columncolor_regex { \c { columncolor } }
```

If the final user uses `nicematrix`, PGF/Tikz will write instruction `\pgfsyspdfmark` in the `aux` file. If he changes its mind and no longer loads `nicematrix`, an error may occur at the next compilation because of remanent instructions `\pgfsyspdfmark` in the `aux` file. With the following code, we try to avoid that situation.

```

60 \cs_new_protected:Npn \@@_provide_pgfsyspdfmark:
61   {
62     \iow_now:Nn \mainaux
63     {
64       \ExplSyntaxOn
65       \cs_if_free:NT \pgfsyspdfmark
66         { \cs_set_eq:NN \pgfsyspdfmark \gobblethree }
67       \ExplSyntaxOff
68     }
69   \cs_gset_eq:NN \@@_provide_pgfsyspdfmark: \prg_do_nothing:
70 }

```

We define a command `\iddots` similar to `\ddots` (\cdots) but with dots going forward ($\cdot\cdot\cdot$). We use `\ProvideDocumentCommand` and so, if the command `\iddots` has already been defined (for example by the package `mathdots`), we don't define it again.

```

71 \ProvideDocumentCommand \iddots { }
72   {
73     \mathinner
74     {
75       \tex_mkern:D 1 mu
76       \box_move_up:nn { 1 pt } { \hbox:n { . } }
77       \tex_mkern:D 2 mu
78       \box_move_up:nn { 4 pt } { \hbox:n { . } }
79       \tex_mkern:D 2 mu
80       \box_move_up:nn { 7 pt }
81         { \vbox:n { \kern 7 pt \hbox:n { . } } }
82       \tex_mkern:D 1 mu
83     }
84   }

```

This definition is a variant of the standard definition of `\ddots`.

In the `aux` file, we will have the references of the PGF/Tikz nodes created by `nicematrix`. However, when `booktabs` is used, some nodes (more precisely, some `row` nodes) will be defined twice because their position will be modified. In order to avoid an error message in this case, we will redefine `\pgfutil@check@rerun` in the `aux` file.

```
85 \AtBeginDocument
```

```

86   {
87     \@ifpackageloaded { booktabs }
88     { \iow_now:Nn \mainaux \nicematrix@redefine@check@rerun }
89     { }
90   }
91 \cs_set_protected:Npn \nicematrix@redefine@check@rerun
92 {
93   \cs_set_eq:NN \@@_old_pgfutil@check@rerun \pgfutil@check@rerun

```

The new version of `\pgfutil@check@rerun` will not check the PGF nodes whose names start with `nm-` (which is the prefix for the nodes created by `nicematrix`).

```

94   \cs_set_protected:Npn \pgfutil@check@rerun ##1 ##2
95   {
96     \str_if_eq:eeF { nm- } { \tl_range:nnn { ##1 } 1 3 }
97     { \@@_old_pgfutil@check@rerun { ##1 } { ##2 } }
98   }
99 }

```

We have to know whether `colortbl` is loaded in particular for the redefinition of `\everycr`.

```

100 \bool_new:N \c_@@_colortbl_loaded_bool
101 \AtBeginDocument
102 {
103   \ifpackageloaded { colortbl }
104   { \bool_set_true:N \c_@@_colortbl_loaded_bool }
105   {

```

The command `\CT@arc@` is a command of `colortbl` which sets the color of the rules in the array. We will use it to store the instruction of color for the rules even if `colortbl` is not loaded.

```

106   \cs_set_protected:Npn \CT@arc@ { }
107   \cs_set:Npn \arrayrulecolor #1 # { \CT@arc { #1 } }
108   \cs_set:Npn \CT@arc #1 #2
109   {
110     \dim_compare:nNnT \baselineskip = \c_zero_dim \noalign
111     { \cs_gset:Npn \CT@arc@ { \color #1 { #2 } } }
112   }

```

Idem for `\CT@drs@`.

```

113   \cs_set_protected:Npn \CT@drsc@ { }
114   \cs_set:Npn \doublerulesepcolor #1 # { \CT@drs { #1 } }
115   \cs_set:Npn \CT@drs #1 #2
116   {
117     \dim_compare:nNnT \baselineskip = \c_zero_dim \noalign
118     { \cs_gset:Npn \CT@drsc@ { \color #1 { #2 } } }
119   }
120   \cs_set:Npn \hline
121   {
122     \noalign { \ifnum 0 = `} \fi
123     \cs_set_eq:NN \hskip \vskip
124     \cs_set_eq:NN \vrule \hrule
125     \cs_set_eq:NN \width \height
126     { \CT@arc@ \vline }
127     \futurelet \reserved@a
128     \xhline
129   }
130 }
131 }

```

We have to redefine `\cline` for several reasons. The command `\@@_cline` will be linked to `\cline` in the beginning of `{NiceArrayWithDelims}`. The following commands must *not* be protected.

```

132 \cs_set:Npn \@@_standard_cline #1 { \@@_standard_cline:w #1 \q_stop }
133 \cs_set:Npn \@@_standard_cline:w #1-#2 \q_stop
134 {
135   \int_compare:nNnT \l_@@_first_col_int = 0 { \omit & }
136   \int_compare:nNnT { #1 } > 1 { \multispan { \@@_pred:n { #1 } } & }
137   \multispan { \int_eval:n { #2 - #1 + 1 } }

```

```

138   {
139     \CT@arc@
140     \leaders \hrule \height \arrayrulewidth \hfill

```

The following `\skip_horizontal:N \c_zero_dim` is to prevent a potential `\unskip` to delete the `\leaders`⁵¹

```

141     \skip_horizontal:N \c_zero_dim
142   }

```

Our `\everycr` has been modified. In particular, the creation of the `row` node is in the `\everycr` (maybe we should put it with the incrementation of `\c@iRow`). Since the following `\cr` correspond to a “false row”, we have to nullify `\everycr`.

```

143   \everycr { }
144   \cr
145   \noalign { \skip_vertical:N -\arrayrulewidth }
146 }

```

The following version of `\cline` spreads the array of a quantity equal to `\arrayrulewidth` as does `\hline`. It will be loaded excepted if the key `standard-cline` has been used.

```

147 \cs_set:Npn \@@_cline

```

We have to act in a fully expandable way since there may be `\noalign` (in the `\multispan`) to detect. That’s why we use `\@@_cline_i:en`.

```

148 { \@@_cline_i:en \l_@@_first_col_int }

```

The command `\cline_i:nn` has two arguments. The first is the number of the current column (it *must* be used in that column). The second is a standard argument of `\cline` of the form $i-j$.

```

149 \cs_set:Npn \@@_cline_i:nn #1 #2 { \@@_cline_i:w #1-#2 \q_stop }
150 \cs_set:Npn \@@_cline_i:w #1-#2-#3 \q_stop
151 {

```

Now, `#1` is the number of the current column and we have to draw a line from the column `#2` to the column `#3` (both included).

```

152 \int_compare:nNnT { #1 } < { #2 }
153   { \multispan { \int_eval:n { #2 - #1 } } & }
154 \multispan { \int_eval:n { #3 - #2 + 1 } }
155 {
156   \CT@arc@
157   \leaders \hrule \height \arrayrulewidth \hfill
158   \skip_horizontal:N \c_zero_dim
159 }

```

You look whether there is another `\cline` to draw (the final user may put several `\cline`).

```

160 \peek_meaning_remove_ignore_spaces:NTF \cline
161   { & \@@_cline_i:en { \@@_succ:n { #3 } } }
162   { \everycr { } \cr }
163 }
164 \cs_generate_variant:Nn \@@_cline_i:nn { e n }

```

The following commands are only for efficiency. They must *not* be protected because it will be used (for instance) in names of PGF nodes.

```

165 \cs_new:Npn \@@_succ:n #1 { \the \numexpr #1 + 1 \relax }
166 \cs_new:Npn \@@_pred:n #1 { \the \numexpr #1 - 1 \relax }

```

The following command is a small shortcut.

```

167 \cs_new:Npn \@@_math_toggle_token:
168   { \bool_if:NF \l_@@_NiceTabular_bool \c_math_toggle_token }

169 \cs_new_protected:Npn \@@_set_Carc@:
170   { \peek_meaning:NTF [ \@@_set_Carc@_i: \@@_set_Carc@_ii: ]
171 \cs_new_protected:Npn \@@_set_Carc@_i: [ #1 ] #2 \q_stop
172   { \cs_set:Npn \CT@arc@ { \color [ #1 ] { #2 } } }

```

⁵¹See question 99041 on TeX StackExchange.

```

173 \cs_new_protected:Npn \@@_set_CTC@arc@ii: #1 \q_stop
174   { \cs_set:Npn \CTC@arc@ { \color { #1 } } }
175 \cs_set_eq:NN \@@_old_pgfpointanchor \pgfpointanchor

```

The column S of siunitx

We want to know whether the package `siunitx` is loaded and, if it is loaded, we redefine the `S` columns of `siunitx`.

```

176 \bool_new:N \c_@@_siunitx_loaded_bool
177 \AtBeginDocument
178 {
179   \ifpackageloaded { siunitx }
180     { \bool_set_true:N \c_@@_siunitx_loaded_bool }
181   { }
182 }

```

The command `\@@_renew_NCC@rewrite@S:` will be used in each environment of `nicematrix` in order to “rewrite” the `S` column in each environment.

```

183 \AtBeginDocument
184 {
185   \bool_if:nTF { ! \c_@@_siunitx_loaded_bool }
186     { \cs_set_eq:NN \@@_renew_NCC@rewrite@S: \prg_do_nothing: }
187   {

```

For version of `siunitx` at least equal to 3.0, the adaptation is different from previous ones. We test the version of `siunitx` by the existence of the control sequence `\siunitx_cell_begin:w`.

```

188 \cs_if_exist:NTF \siunitx_cell_begin:w
189 {
190   \cs_new_protected:Npn \@@_renew_NCC@rewrite@S:
191   {
192     \renewcommand*\{NCC@rewrite@S}[1] []
193     {
194       \@temptokena \exp_after:wN
195       {
196         \tex_the:D \@temptokena
197         > {
198           \@@_Cell:
199           \keys_set:nn { siunitx } { ##1 }
200           \siunitx_cell_begin:w
201         }
202     }

```

`\@@_true_c:` will be replaced statically by `c` at the end of the construction of the preamble.

```

203   \@@_true_c:
204     < { \siunitx_cell_end: \@@_end_Cell: }
205   }
206   \NC@find
207   }
208 }
209 {
210   \cs_new_protected:Npn \@@_renew_NCC@rewrite@S:
211   {
212     \renewcommand*\{NCC@rewrite@S}[1] []
213     {
214       \@temptokena \exp_after:wN
215       {
216         \tex_the:D \@temptokena
217         > { \@@_Cell: \c_@@_table_collect_begin_tl S {##1} }
218         \@@_true_c:
219         < { \c_@@_table_print_tl \@@_end_Cell: }
220       }
221       \NC@find
222     }

```

```

223         }
224     }
225   }
226 }

The following code is used to define \c_@@_table_collect_begin_tl and \c_@@_table_print_tl when the version of siunitx is prior to 3.0. The command \@@_adapt_S_column is used in the environment {NiceArrayWithDelims}.

227 \AtBeginDocument
228 {
229   \cs_set_eq:NN \@@_adapt_S_column: \prg_do_nothing:
230   \bool_lazy_and:nnT
231     { \c_@@_siunitx_loaded_bool }
232     { ! \cs_if_exist_p:N \siunitx_cell_begin:w }
233   {
234     \cs_set_protected:Npn \@@_adapt_S_column:
235     {
236       \group_begin:
237       \temptokena = { }
238       \cs_set_eq:NN \NC@find \prg_do_nothing:
239       \NC@rewrite@S { }
240       \tl_gset:NV \g_tmpa_tl \temptokena
241       \group_end:
242       \tl_new:N \c_@@_table_collect_begin_tl
243       \tl_set:Nx \l_tmpa_tl { \tl_item:Nn \g_tmpa_tl 2 }
244       \tl_gset:Nx \c_@@_table_collect_begin_tl { \tl_item:Nn \l_tmpa_tl 1 }
245       \tl_new:N \c_@@_table_print_tl
246       \tl_gset:Nx \c_@@_table_print_tl { \tl_item:Nn \g_tmpa_tl { -1 } }
247       \cs_gset_eq:NN \@@_adapt_S_column: \prg_do_nothing:
248     }
249   }
250 }

```

Parameters

For compatibility with versions prior to 5.0, we provide a load-time option `define_L_C_R`. With this option, it's possible to use the letters L, C and R instead of l, c and r in the preamble of the environments of `nicematrix` as it was mandatory before version 5.0.

```

251 \bool_new:N \c_@@_define_L_C_R_bool
252 \cs_new_protected:Npn \@@_define_L_C_R:
253 {
254   \newcolumntype L l
255   \newcolumntype C c
256   \newcolumntype R r
257 }

```

The following counter will count the environments {NiceArray}. The value of this counter will be used to prefix the names of the Tikz nodes created in the array.

```
258 \int_new:N \g_@@_env_int
```

The following command is only a syntactic shortcut. It must *not* be protected (it will be used in names of PGF nodes).

```
259 \cs_new:Npn \@@_env: { nm - \int_use:N \g_@@_env_int }
```

The command `\NiceMatrixLastEnv` is not used by the package `nicematrix`. It's only a facility given to the final user. It gives the number of the last environment (in fact the number of the current environment but it's meant to be used after the environment in order to refer to that environment — and its nodes — without having to give it a name). This command *must* be expandable since it will be used in pgf nodes.

```

260 \NewExpandableDocumentCommand \NiceMatrixLastEnv { }
261   { \int_use:N \g_@@_env_int }

```

The following command is only a syntactic shortcut. The `q` in `qpoint` means *quick*.

```

262 \cs_new_protected:Npn \@@_qpoint:n #1
263   { \pgfpointanchor { \@@_env: - #1 } { center } }

```

The following counter will count the environments `{NiceMatrixBlock}`.

```

264 \int_new:N \g_@@_NiceMatrixBlock_int

```

The dimension `\l_@@_columns_width_dim` will be used when the options specify that all the columns must have the same width (but, if the key `columns-width` is used with the special value `auto`, the boolean `l_@@_auto_columns_width_bool` also will be raised).

```

265 \dim_new:N \l_@@_columns_width_dim

```

The following counters will be used to count the numbers of rows and columns of the array.

```

266 \int_new:N \g_@@_row_total_int
267 \int_new:N \g_@@_col_total_int

```

The following token list will contain the type of the current cell (`l`, `c` or `r`). It will be used by the blocks.

```

268 \tl_new:N \l_@@_cell_type_tl
269 \tl_set:Nn \l_@@_cell_type_tl { c }

```

When there is a mono-column block (created by the command `\Block`), we want to take into account the width of that block for the width of the column. That's why we compute the width of that block in the `\g_@@_blocks_wd_dim` and, after the construction of the box `\l_@@_cell_box`, we change the width of that box to take into account the length `\g_@@_blocks_wd_dim`.

```

270 \dim_new:N \g_@@_blocks_wd_dim

```

Idem pour the mono-row blocks.

```

271 \dim_new:N \g_@@_blocks_ht_dim
272 \dim_new:N \g_@@_blocks_dp_dim

```

The sequence `\g_@@_names_seq` will be the list of all the names of environments used (via the option `name`) in the document: two environments must not have the same name. However, it's possible to use the option `allow-duplicate-names`.

```

273 \seq_new:N \g_@@_names_seq

```

We want to know whether we are in an environment of `nicematrix` because we will raise an error if the user tries to use nested environments.

```

274 \bool_new:N \l_@@_in_env_bool

```

If the user uses `{NiceArray}` or `{NiceTabular}` the flag `\l_@@_NiceArray_bool` will be raised.

```

275 \bool_new:N \l_@@_NiceArray_bool

```

In fact, if there is delimiters in the preamble of `{NiceArray}` (eg: `[cccc]`), this boolean will be set to false.

If the user uses `{NiceTabular}` or `{NiceTabular*}`, we will raise the following flag.

```

276 \bool_new:N \l_@@_NiceTabular_bool

```

If the user uses `{NiceTabular*}`, the width of the tabular (in the first argument of the environment `{NiceTabular*}`) will be stored in the following dimension.

```

277 \dim_new:N \l_@@_tabular_width_dim

```

If the user uses an environment without preamble, we will raise the following flag.

```
278 \bool_new:N \l_@@_Matrix_bool
```

The following boolean will be raised when the command `\rotate` is used.

```
279 \bool_new:N \g_@@_rotate_bool
```

We will write in `\g_@@_aux_t1` all the instructions that we have to write on the `aux` file for the current environment. The contain of that token list will be written on the `aux` file at the end of the environment (in an instruction `\tl_gset:cn { c_@@_int_use:N \g_@@_env_int _ t1 }`).

```
280 \tl_new:N \g_@@_aux_t1
```

```
281 \cs_new_protected:Npn \@@_test_if_math_mode:
282 {
283     \if_mode_math: \else:
284         \@@_fatal:n { Outside~math~mode }
285     \fi:
286 }
```

The letter used for the vlines which will be drawn only in the sub-matrices. `vlism` stands for *vertical lines in sub-matrices*.

```
287 \tl_new:N \l_@@_letter_vlism_t1
```

The list of the columns where vertical lines in sub-matrices (`vlism`) must be drawn. Of course, the actual value of this sequence will be known after the analyse of the preamble of the array.

```
288 \seq_new:N \g_@@_cols_vlism_seq
```

The following colors will be used to memorize the color of the potential “first col” and the potential “first row”.

```
289 \colorlet { nicematrix-last-col } { . }
290 \colorlet { nicematrix-last-row } { . }
```

The following string is the name of the current environment or the current command of `nicematrix` (despite its name which contains `env`).

```
291 \str_new:N \g_@@_name_env_str
```

The following string will contain the word *command* or *environment* whether we are in a command of `nicematrix` or in an environment of `nicematrix`. The default value is *environment*.

```
292 \tl_set:Nn \g_@@_com_or_env_str { environment }
```

The following command will be able to reconstruct the full name of the current command or environment (despite its name which contains `env`). This command must *not* be protected since it will be used in error messages and we have to use `\str_if_eq:VnTF` and not `\tl_if_eq:NnTF` because we need to be fully expandable).

```
293 \cs_new:Npn \@@_full_name_env:
294 {
295     \str_if_eq:VnTF \g_@@_com_or_env_str { command }
296     { command \space \c_backslash_str \g_@@_name_env_str }
297     { environment \space \{ \g_@@_name_env_str \} }
298 }
```

The following token list corresponds to the option `code-after` (it's also possible to set the value of that parameter with the keyword `\CodeAfter`).

```
299 \tl_new:N \g_nicematrix_code_after_t1
```

For the key `code` of the command `\SubMatrix` (itself in the main `\CodeAfter`), we will use the following token list.

```
300 \tl_new:N \l_@@_code_t1
```

The following token list has a function similar to `\g_nicematrix_code_after_tl` but it is used internally by `nicematrix`. In fact, we have to distinguish between `\g_nicematrix_code_after_tl` and `\g_@@_internal_code_after_tl` because we must take care of the order in which instructions stored in that parameters are executed.

```
301 \tl_new:N \g_@@_internal_code_after_tl
```

The counters `\l_@@_old_iRow_int` and `\l_@@_old_jCol_int` will be used to save the values of the potential LaTeX counters `iRow` and `jCol`. These LaTeX counters will be restored at the end of the environment.

```
302 \int_new:N \l_@@_old_iRow_int
303 \int_new:N \l_@@_old_jCol_int
```

The TeX counters `\c@iRow` and `\c@jCol` will be created in the beginning of `{NiceArrayWithDelims}` (if they don't exist previously).

The following token list corresponds to the key `rules/color` available in the environments.

```
304 \tl_new:N \l_@@_rules_color_tl
```

This boolean will be used only to detect in an expandable way whether we are at the beginning of the (potential) column zero, in order to raise an error if `\Hdotsfor` is used in that column.

```
305 \bool_new:N \g_@@_after_col_zero_bool
```

A kind of false row will be inserted at the end of the array for the construction of the `col` nodes (and also to fix the width of the columns when `columns-width` is used). When this special row will be created, we will raise the flag `\g_@@_row_of_col_done_bool` in order to avoid some actions set in the redefinition of `\everycr` when the last `\cr` of the `\halign` will occur (after that row of `col` nodes).

```
306 \bool_new:N \g_@@_row_of_col_done_bool
```

It's possible to use the command `\NotEmpty` to specify explicitly that a cell must be considered as non empty by `nicematrix` (the Tikz nodes are constructed only in the non empty cells).

```
307 \bool_new:N \g_@@_not_empty_cell_bool
```

`\l_@@_code_before_tl` may contain two types of informations:

- A `code-before` written in the aux file by a previous run. When the aux file is read, this `code-before` is stored in `\g_@@_code_before_i_tl` (where *i* is the number of the environment) and, at the beginning of the environment, it will be put in `\l_@@_code_before_tl`.
- The final user can explicitly add material in `\l_@@_code_before_tl` by using the key `code-before` or the keyword `\CodeBefore` (with the keyword `\Body`).

```
308 \tl_new:N \l_@@_code_before_tl
309 \bool_new:N \l_@@_code_before_bool
```

The following dimensions will be used when drawing the dotted lines.

```
310 \dim_new:N \l_@@_x_initial_dim
311 \dim_new:N \l_@@_y_initial_dim
312 \dim_new:N \l_@@_x_final_dim
313 \dim_new:N \l_@@_y_final_dim
```

`expl3` provides scratch dimensions `\l_tmpa_dim` and `\l_tmpb_dim`. We creates two more in the same spirit (if they don't exist yet: that's why we use `\dim_zero_new:N`).

```
314 \dim_zero_new:N \l_tmpc_dim
315 \dim_zero_new:N \l_tmpd_dim
```

Some cells will be declared as "empty" (for example a cell with an instruction `\Cdots`).

```
316 \bool_new:N \g_@@_empty_cell_bool
```

The following dimensions will be used internally to compute the width of the potential “first column” and “last column”.

```
317 \dim_new:N \g_@@_width_last_col_dim
318 \dim_new:N \g_@@_width_first_col_dim
```

The following sequence will contain the characteristics of the blocks of the array, specified by the command `\Block`. Each block is represented by 6 components surrounded by curly braces:
`{imin}-{jmin}-{imax}-{jmax}-{options}-{contents}`.

The variable is global because it will be modified in the cells of the array.

```
319 \seq_new:N \g_@@_blocks_seq
```

We also manage a sequence of the *positions* of the blocks. Of course, it’s redundant with the previous sequence, but it’s for efficiency. In that sequence, each block is represented by only the four first components: `{imin}-{jmin}-{imax}-{jmax}`.

```
320 \seq_new:N \g_@@_pos_of_blocks_seq
```

In fact, this sequence will also contain the positions of the cells with a `\diagbox`. The sequence `\g_@@_pos_of_blocks_seq` will be used when we will draw the rules (which respect the blocks).

We will also manage a sequence for the positions of the dotted lines. These dotted lines are created in the array by `\Cdots`, `\Vdots`, `\Ddots`, etc. However, their positions, that is to say, their extremities, will be determined only after the construction of the array. In this sequence, each item contains four components: `{imin}-{jmin}-{imax}-{jmax}`.

```
321 \seq_new:N \g_@@_pos_of_xdots_seq
```

The sequence `\g_@@_pos_of_xdots_seq` will be used when we will draw the rules required by the key `hvlines` (these rules won’t be drawn within the virtual blocks corresponding to the dotted lines).

The final user may decide to “stroke” a block (using, for example, the key `draw=red!15` when using the command `\Block`). In that case, the rules specified, for instance, by `hvlines` must not be drawn around the block. That’s why we keep the information of all that stroken blocks in the following sequence.

```
322 \seq_new:N \g_@@_pos_of_stroken_blocks_seq
```

If the user has used the key `corners` (or the key `hvlines-except-corners`), all the cells which are in an (empty) corner will be stored in the following sequence.

```
323 \seq_new:N \l_@@_corners_cells_seq
```

The list of the names of the potential `\SubMatrix` in the `\CodeAfter` of an environment. Unfortunately, that list has to be global (we have to use it inside the group for the options of a given `\SubMatrix`).

```
324 \seq_new:N \g_@@_submatrix_names_seq
```

The sequence `\g_@@_multicolumn_cells_seq` will contain the list of the cells of the array where a command `\multicolumn{n}{...}{...}` with $n > 1$ is issued. In `\g_@@_multicolumn_sizes_seq`, the “sizes” (that is to say the values of n) correspondant will be stored. These lists will be used for the creation of the “medium nodes” (if they are created).

```
325 \seq_new:N \g_@@_multicolumn_cells_seq
326 \seq_new:N \g_@@_multicolumn_sizes_seq
```

The following counters will be used when searching the extremities of a dotted line (we need these counters because of the potential “open” lines in the `\SubMatrix`—the `\SubMatrix` in the `code-before`).

```
327 \int_new:N \l_@@_row_min_int
328 \int_new:N \l_@@_row_max_int
329 \int_new:N \l_@@_col_min_int
330 \int_new:N \l_@@_col_max_int
```

The following sequence will be used when the command `\SubMatrix` is used in the `code-before` (and not in the `\CodeAfter`). It will contain the position of all the sub-matrices specified in the `code-before`. Each sub-matrix is represented by an “object” of the forme $\{i\}\{j\}\{k\}\{l\}$ where i and j are the number of row and column of the upper-left cell and k and l the number of row and column of the lower-right cell.

```
331 \seq_new:N \g_@@_submatrix_seq
```

We are able to determine the number of columns specified in the preamble (for the environments with explicit preamble of course and without the potential exterior columns).

```
332 \int_new:N \g_@@_static_num_of_col_int
```

The following parameters correspond to the keys `fill`, `draw`, `borders` and `rounded-corners` of the command `\Block`.

```
333 \tl_new:N \l_@@_fill_tl
334 \tl_new:N \l_@@_draw_tl
335 \clist_new:N \l_@@_borders_clist
336 \dim_new:N \l_@@_rounded_corners_dim
```

The last parameter has no direct link with the [empty] corners of the array (which are computed and taken into account by `nicematrix` when the key `corners` is used).

The following token list correspond to the key `color` of the command `\Block`.

```
337 \tl_new:N \l_@@_color_tl
```

Here is the dimension for the width of the rule when a block (created by `\Block`) is stroked.

```
338 \dim_new:N \l_@@_line_width_dim
```

The parameters of the horizontal position of the label of a block. If the user uses the key `c` or `C`, the value is `c`. If the user uses the key `l` or `L`, the value is `l`. If the user uses the key `r` or `R`, the value is `r`. If the user has used a capital letter, the boolean `\l_@@_hpos_of_block_cap_bool` will be raised (in the second pass of the analyze of the keys of the command `\Block`).

```
339 \tl_new:N \l_@@_hpos_of_block_tl
340 \tl_set:Nn \l_@@_hpos_of_block_tl { c }
341 \bool_new:N \l_@@_hpos_of_block_cap_bool
```

For the vertical position, the possible values are `c`, `t` and `b`. Of course, it would be interesting to program a key `T` and a key `B`.

```
342 \tl_new:N \l_@@_vpos_of_block_tl
343 \tl_set:Nn \l_@@_vpos_of_block_tl { c }
```

Used when the key `draw-first` is used for `\Ddots` or `\Iddots`.

```
344 \bool_new:N \l_@@_draw_first_bool
```

The following flag corresponds to the key `hvlines` of the command `\Block`.

```
345 \bool_new:N \l_@@_hvlines_block_bool
```

The blocks which use the key `-` will store their content in a box. These boxes are numbered with the following counter.

```
346 \int_new:N \g_@@_block_box_int

347 \dim_new:N \l_@@_submatrix_extra_height_dim
348 \dim_new:N \l_@@_submatrix_left_xshift_dim
349 \dim_new:N \l_@@_submatrix_right_xshift_dim
350 \clist_new:N \l_@@_hlines_clist
351 \clist_new:N \l_@@_vlines_clist
352 \clist_new:N \l_@@_submatrix_hlines_clist
353 \clist_new:N \l_@@_submatrix_vlines_clist
```

Variables for the exterior rows and columns

The keys for the exterior rows and columns are `first-row`, `first-col`, `last-row` and `last-col`. However, internally, these keys are not coded in a similar way.

- **First row**

The integer `\l_@@_first_row_int` is the number of the first row of the array. The default value is 1, but, if the option `first-row` is used, the value will be 0.

```
354   \int_new:N \l_@@_first_row_int
355   \int_set:Nn \l_@@_first_row_int 1
```

- **First column**

The integer `\l_@@_first_col_int` is the number of the first column of the array. The default value is 1, but, if the option `first-col` is used, the value will be 0.

```
356   \int_new:N \l_@@_first_col_int
357   \int_set:Nn \l_@@_first_col_int 1
```

- **Last row**

The counter `\l_@@_last_row_int` is the number of the potential “last row”, as specified by the key `last-row`. A value of `-2` means that there is no “last row”. A value of `-1` means that there is a “last row” but we don’t know the number of that row (the key `last-row` has been used without value and the actual value has not still been read in the `aux` file).

```
358   \int_new:N \l_@@_last_row_int
359   \int_set:Nn \l_@@_last_row_int { -2 }
```

If, in an environment like `{pNiceArray}`, the option `last-row` is used without value, we will globally raise the following flag. It will be used to know if we have, after the construction of the array, to write in the `aux` file the number of the “last row”.⁵²

```
360   \bool_new:N \l_@@_last_row_without_value_bool
```

Idem for `\l_@@_last_col_without_value_bool`

```
361   \bool_new:N \l_@@_last_col_without_value_bool
```

- **Last column**

For the potential “last column”, we use an integer. A value of `-2` means that there is no last column. A value of `-1` means that we are in an environment without preamble (e.g. `{bNiceMatrix}`) and there is a last column but we don’t know its value because the user has used the option `last-col` without value. A value of 0 means that the option `last-col` has been used in an environment with preamble (like `{pNiceArray}`): in this case, the key was necessary without argument.

```
362   \int_new:N \l_@@_last_col_int
363   \int_set:Nn \l_@@_last_col_int { -2 }
```

However, we have also a boolean. Consider the following code:

```
\begin{pNiceArray}{cc}[last-col]
  1 & 2 \\
  3 & 4
\end{pNiceArray}
```

In such a code, the “last column” specified by the key `last-col` is not used. We want to be able to detect such a situation and we create a boolean for that job.

```
364   \bool_new:N \g_@@_last_col_found_bool
```

This boolean is set to `false` at the end of `\@_pre_array_i::`.

⁵²We can’t use `\l_@@_last_row_int` for this usage because, if `nicematrix` has read its value from the `aux` file, the value of the counter won’t be `-1` any longer.

The command \tabularnote

The LaTeX counter `tabularnote` will be used to count the tabular notes during the construction of the array (this counter won't be used during the composition of the notes at the end of the array). You use a LaTeX counter because we will use `\refstepcounter` in order to have the tabular notes referenceable.

```
365 \newcounter{tabularnote}
```

We will store in the following sequence the tabular notes of a given array.

```
366 \seq_new:N \g_@@_tabularnotes_seq
```

However, before the actual tabular notes, it's possible to put a text specified by the key `tabularnote` of the environment. The token list `\l_@@_tabularnote_tl` corresponds to the value of that key.

```
367 \tl_new:N \l_@@_tabularnote_tl
```

The following counter will be used to count the number of successive tabular notes such as in `\tabularnote{Note 1}\tabularnote{Note 2}\tabularnote{Note 3}`. In the tabular, the labels of those nodes are composed as a comma separated list (e.g. `a,b,c`).

```
368 \int_new:N \l_@@_number_of_notes_int
```

The following function can be redefined by using the key `notes/style`.

```
369 \cs_new:Npn \@@_notes_style:n #1 { \textit{ \alph{#1} } }
```

The following fonction can be redefined by using the key `notes/label-in-tabular`.

```
370 \cs_new:Npn \@@_notes_label_in_tabular:n #1 { \textsuperscript{#1} }
```

The following function can be redefined by using the key `notes/label-in-list`.

```
371 \cs_new:Npn \@@_notes_label_in_list:n #1 { \textsuperscript{#1} }
```

We define `\thetabularnote` because it will be used by LaTeX if the user want to reference a footnote which has been marked by a `\label`. The TeX group is for the case where the user has put an instruction such as `\color{red}` in `\@@_notes_style:n`.

```
372 \cs_set:Npn \thetabularnote { \@@_notes_style:n { tabularnote } }
```

The tabular notes will be available for the final user only when `enumitem` is loaded. Indeed, the tabular notes will be composed at the end of the array with a list customized by `enumitem` (a list `tabularnotes` in the general case and a list `tabularnotes*` if the key `para` is in force). However, we can test whether `enumitem` has been loaded only at the beginning of the document (we want to allow the user to load `enumitem` after `nicematrix`).

```
373 \AtBeginDocument
374 {
375   \bool_if:nTF { ! \c_@@_enumitem_loaded_bool }
376   {
377     \NewDocumentCommand \tabularnote { m }
378     { \@@_error:n { enumitem-not-loaded } }
379   }
380 }
```

The type of list `tabularnotes` will be used to format the tabular notes at the end of the array in the general case and `tabularnotes*` will be used if the key `para` is in force.

```
381 \newlist{tabularnotes}{enumerate}{1}
382 \setlist[tabularnotes]
383 {
384   topsep = 0pt ,
385   noitemsep ,
386   leftmargin = * ,
```

```

387         align = left ,
388         labelsep = Opt ,
389         label =
390             \@@_notes_label_in_list:n { \@@_notes_style:n { tabularnotesi } } ,
391         }
392     \newlist { tabularnotes* } { enumerate* } { 1 }
393     \setlist [ tabularnotes* ]
394     {
395         afterlabel = \nobreak ,
396         itemjoin = \quad ,
397         label =
398             \@@_notes_label_in_list:n { \@@_notes_style:n { tabularnotes*i } }
399     }

```

The command `\tabularnote` is available in the whole document (and not only in the environments of `nicematrix`) because we want it to be available in the caption of a `{table}` (before the following `{NiceTabular}` or `{NiceArray}`). That's also the reason why the variables `\c@tabularnote` and `\g_@@_tabularnotes_seq` will be cleared at the end of the environment of `nicematrix` (and not at the beginning).

Unfortunately, if the package `caption` is loaded, the command `\caption` evaluates its argument twice and since it is not aware (of course) of `\tabularnote`, the command `\tabularnote` is, in fact, not usable in `\caption` when `caption` is loaded.⁵³

```

400     \NewDocumentCommand \tabularnote { m }
401     {
402         \bool_if:nTF { ! \l_@@_NiceArray_bool && \l_@@_in_env_bool }
403             { \@@_error:n { tabularnote-forbidden } }
404         {

```

`\l_@@_number_of_notes_int` is used to count the number of successive tabular notes such as in `\tabularnote{Note 1}\tabularnote{Note 2}\tabularnote{Note 3}`. We will have to compose the labels of these notes as a comma separated list (e.g. `a,b,c`).

```

405         \int_incr:N \l_@@_number_of_notes_int

```

We expand the content of the note at the point of use of `\tabularnote` as does `\footnote`.

```

406         \seq_gput_right:Nn \g_@@_tabularnotes_seq { #1 }
407         \peek_meaning:NF \tabularnote
408         {

```

If the following token is *not* a `\tabularnote`, we have finished the sequence of successive commands `\tabularnote` and we have to format the labels of these tabular notes (in the array). We compose those labels in a box `\l_tmpa_box` because we will do a special construction in order to have this box in a overlapping position if we are at the end of a cell.

```

409         \hbox_set:Nn \l_tmpa_box
410         {

```

We remind that it is the command `\@@_notes_label_in_tabular:n` that will (most of the time) put the labels in a `\textsuperscript`.

```

411         \@@_notes_label_in_tabular:n
412         {
413             \stepcounter { tabularnote }
414             \@@_notes_style:n { tabularnote }
415             \prg_replicate:nn { \l_@@_number_of_notes_int - 1 }
416             {
417                 ,
418                 \stepcounter { tabularnote }
419                 \@@_notes_style:n { tabularnote }
420             }
421         }
422     }

```

⁵³We should try to find a solution to that problem.

We use `\refstepcounter` in order to have the (last) tabular note referenceable (with the standard command `\label`) and that's why we have to go back with a decrementation of the counter `tabularnote` first.

```

423           \addtocounter { tabularnote } { -1 }
424           \refstepcounter { tabularnote }
425           \int_zero:N \l_@@_number_of_notes_int
426           \hbox_overlap_right:n { \box_use:N \l_tmpa_box }

```

If the command `\tabularnote` is used exactly at the end of the cell, the `\unskip` (inserted by `array?`) will delete the skip we insert now and the label of the footnote will be composed in an overlapping position (by design).

```

427           \skip_horizontal:n { \box_wd:N \l_tmpa_box }
428       }
429   }
430 }
431 }
432 }

```

Command for creation of rectangle nodes

The following command should be used in a `{pgfpicture}`. It creates a rectangle (empty but with a name).

#1 is the name of the node which will be created; #2 and #3 are the coordinates of one of the corner of the rectangle; #4 and #5 are the coordinates of the opposite corner.

```

433 \cs_new_protected:Npn \@@_pgf_rect_node:nnnn #1 #2 #3 #4 #5
434 {
435     \begin { pgfscope }
436     \pgfset
437     {
438         outer_sep = \c_zero_dim ,
439         inner_sep = \c_zero_dim ,
440         minimum_size = \c_zero_dim
441     }
442     \pgftransformshift { \pgfpoint { 0.5 * ( #2 + #4 ) } { 0.5 * ( #3 + #5 ) } }
443     \pgfnode
444     {
445         rectangle
446         center
447     }
448     \vbox_to_ht:nn
449     {
450         \dim_abs:n { #5 - #3 }
451         \vfill
452         \hbox_to_wd:nn { \dim_abs:n { #4 - #2 } }
453     }
454     { #1 }
455     {}
456     \end { pgfscope }
457 }

```

The command `\@@_pgf_rect_node:nnn` is a variant of `\@@_pgf_rect_node:nnnn`: it takes two PGF points as arguments instead of the four dimensions which are the coordinates.

```

458 \cs_new_protected:Npn \@@_pgf_rect_node:nnn #1 #2 #3
459 {
460     \begin { pgfscope }
461     \pgfset
462     {
463         outer_sep = \c_zero_dim ,
464         inner_sep = \c_zero_dim ,
465         minimum_size = \c_zero_dim
466     }
467     \pgftransformshift { \pgfpointscale { 0.5 } { \pgfpointadd { #2 } { #3 } } }

```

```

468 \pgfpointdiff { #3 } { #2 }
469 \pgfgetlastxy \l_tmpa_dim \l_tmpb_dim
470 \pgfnode
471   { rectangle }
472   { center }
473   {
474     \vbox_to_ht:nn
475       { \dim_abs:n \l_tmpb_dim }
476       { \vfill \hbox_to_wd:nn { \dim_abs:n \l_tmpa_dim } { } }
477   }
478   { #1 }
479   { }
480 \end { pgfscope }
481 }
```

The options

By default, the commands `\cellcolor` and `\rowcolor` are available for the user in the cells of the tabular (the user may use the commands provided by `\colortbl`). However, if the key `colortbl-like` is used, these commands are available.

```
482 \bool_new:N \l_@@_colortbl_like_bool
```

By default, the behaviour of `\cline` is changed in the environments of `nicematrix`: a `\cline` spreads the array by an amount equal to `\arrayrulewidth`. It's possible to disable this feature with the key `\l_@@_standard_cline_bool`.

```
483 \bool_new:N \l_@@_standard_cline_bool
```

The following dimensions correspond to the options `cell-space-top-limit` and co (these parameters are inspired by the package `cellspace`).

```

484 \dim_new:N \l_@@_cell_space_top_limit_dim
485 \dim_new:N \l_@@_cell_space_bottom_limit_dim
```

The following dimension is the distance between two dots for the dotted lines (when `line-style` is equal to `standard`, which is the initial value). The initial value is 0.45 em but it will be changed if the option `small` is used.

```

486 \dim_new:N \l_@@_inter_dots_dim
487 \AtBeginDocument { \dim_set:Nn \l_@@_inter_dots_dim { 0.45 em } }
```

The `\AtBeginDocument` is only a security in case `revtex4-1` is used (even though it is obsolete).

The following dimension is the minimal distance between a node (in fact an anchor of that node) and a dotted line (we say “minimal” because, by definition, a dotted line is not a continuous line and, therefore, this distance may vary a little).

```

488 \dim_new:N \l_@@_xdots_shorten_dim
489 \AtBeginDocument { \dim_set:Nn \l_@@_xdots_shorten_dim { 0.3 em } }
```

The `\AtBeginDocument` is only a security in case `revtex4-1` is used (even though it is obsolete).

The following dimension is the radius of the dots for the dotted lines (when `line-style` is equal to `standard`, which is the initial value). The initial value is 0.53 pt but it will be changed if the option `small` is used.

```

490 \dim_new:N \l_@@_radius_dim
491 \AtBeginDocument { \dim_set:Nn \l_@@_radius_dim { 0.53 pt } }
```

The `\AtBeginDocument` is only a security in case revtex4-1 is used (even if it is obsolete).

The token list `\l_@@_xdots_line_style_tl` corresponds to the option `tikz` of the commands `\Cdots`, `\Ldots`, etc. and of the options `line-style` for the environments and `\NiceMatrixOptions`. The constant `\c_@@_standard_tl` will be used in some tests.

```
492 \tl_new:N \l_@@_xdots_line_style_tl
493 \tl_const:Nn \c_@@_standard_tl { standard }
494 \tl_set_eq:NN \l_@@_xdots_line_style_tl \c_@@_standard_tl
```

The boolean `\l_@@_light_syntax_bool` corresponds to the option `light-syntax`.

```
495 \bool_new:N \l_@@_light_syntax_bool
```

The string `\l_@@_baseline_tl` may contain one of the three values `t`, `c` or `b` as in the option of the environment `{array}`. However, it may also contain an integer (which represents the number of the row to which align the array).

```
496 \tl_new:N \l_@@_baseline_tl
497 \tl_set:Nn \l_@@_baseline_tl c
```

The flag `\l_@@_exterior_arraycolsep_bool` corresponds to the option `exterior-arraycolsep`. If this option is set, a space equal to `\arraycolsep` will be put on both sides of an environment `{NiceArray}` (as it is done in `{array}` of `array`).

```
498 \bool_new:N \l_@@_exterior_arraycolsep_bool
```

The flag `\l_@@_parallelize_diags_bool` controls whether the diagonals are parallelized. The initial value is `true`.

```
499 \bool_new:N \l_@@_parallelize_diags_bool
500 \bool_set_true:N \l_@@_parallelize_diags_bool
```

The following parameter correspond to the key `corners`. The elements of that `clist` must be in NW, SW, NE and SE.

```
501 \clist_new:N \l_@@_corners_clist
```

```
502 \dim_new:N \l_@@_notes_above_space_dim
503 \AtBeginDocument { \dim_set:Nn \l_@@_notes_above_space_dim { 1 mm } }
```

The `\AtBeginDocument` is only a security in case revtex4-1 is used (even if it is obsolete).

The flag `\l_@@_nullify_dots_bool` corresponds to the option `nullify-dots`. When the flag is down, the instructions like `\vdots` are inserted within a `\phantom` (and so the constructed matrix has exactly the same size as a matrix constructed with the classical `{matrix}` and `\ldots`, `\vdots`, etc.).

```
504 \bool_new:N \l_@@_nullify_dots_bool
```

The following flag will be used when the current options specify that all the columns of the array must have the same width equal to the largest width of a cell of the array (except the cells of the potential exterior columns).

```
505 \bool_new:N \l_@@_auto_columns_width_bool
```

The following boolean corresponds to the key `create-cell-nodes` of the keyword `\CodeBefore`.

```
506 \bool_new:N \g_@@_recreate_cell_nodes_bool
```

The string `\l_@@_name_str` will contain the optional name of the environment: this name can be used to access to the Tikz nodes created in the array from outside the environment.

```
507 \str_new:N \l_@@_name_str
```

The boolean `\l_@@_medium_nodes_bool` will be used to indicate whether the “medium nodes” are created in the array. Idem for the “large nodes”.

```
508 \bool_new:N \l_@@_medium_nodes_bool
509 \bool_new:N \l_@@_large_nodes_bool
```

The boolean `\l_@@_except_borders_bool` will be raised when the key `hvlines-except-borders` will be used (but that key has also other effects).

```
510 \bool_new:N \l_@@_except_borders_bool
```

The dimension `\l_@@_left_margin_dim` correspond to the option `left-margin`. Idem for the right margin. These parameters are involved in the creation of the “medium nodes” but also in the placement of the delimiters and the drawing of the horizontal dotted lines (`\hdottedline`).

```
511 \dim_new:N \l_@@_left_margin_dim
512 \dim_new:N \l_@@_right_margin_dim
```

The dimensions `\l_@@_extra_left_margin_dim` and `\l_@@_extra_right_margin_dim` correspond to the options `extra-left-margin` and `extra-right-margin`.

```
513 \dim_new:N \l_@@_extra_left_margin_dim
514 \dim_new:N \l_@@_extra_right_margin_dim
```

The token list `\l_@@_end_of_row_tl` corresponds to the option `end-of-row`. It specifies the symbol used to mark the ends of rows when the light syntax is used.

```
515 \tl_new:N \l_@@_end_of_row_tl
516 \tl_set:Nn \l_@@_end_of_row_tl { ; }
```

The following parameter is for the color the dotted lines drawn by `\Cdots`, `\Ldots`, `\Vdots`, `\Ddots`, `\Iddots` and `\Hdotsfor` but *not* the dotted lines drawn by `\hdottedline` and “`:`”.

```
517 \tl_new:N \l_@@_xdots_color_tl
```

The following token list corresponds to the key `delimiters/color`.

```
518 \tl_new:N \l_@@_delimiters_color_tl
```

Sometimes, we want to have several arrays vertically juxtaposed in order to have an alignment of the columns of these arrays. To achieve this goal, one may wish to use the same width for all the columns (for example with the option `columns-width` or the option `auto-columns-width` of the environment `{NiceMatrixBlock}`). However, even if we use the same type of delimiters, the width of the delimiters may be different from an array to another because the width of the delimiter is function of its size. That’s why we create an option called `delimiters/max-width` which will give to the delimiters the width of a delimiter (of the same type) of big size. The following boolean corresponds to this option.

```
519 \bool_new:N \l_@@_delimiters_max_width_bool
```

```
520 \keys_define:nn { NiceMatrix / xdots }
  {
    line-style .code:n =
    {
      \bool_lazy_or:nnTF
      {
        { \cs_if_exist_p:N \tikzpicture }
        { \str_if_eq_p:nn { #1 } { standard } }
        { \tl_set:Nn \l_@@_xdots_line_style_tl { #1 } }
        { \@@_error:n { bad-option-for-line-style } }
      }
    },
    line-style .value_required:n = true ,
    color .tl_set:N = \l_@@_xdots_color_tl ,
    color .value_required:n = true ,
    shorten .dim_set:N = \l_@@_xdots_shorten_dim ,
    shorten .value_required:n = true ,
```

We can’t use `\c_@@_tikz_loaded_bool` to test whether tikz is loaded because `\NiceMatrixOptions` may be used in the preamble of the document.

```
525   { \cs_if_exist_p:N \tikzpicture }
  526   { \str_if_eq_p:nn { #1 } { standard } }
  527   { \tl_set:Nn \l_@@_xdots_line_style_tl { #1 } }
  528   { \@@_error:n { bad-option-for-line-style } }
  529 },
  line-style .value_required:n = true ,
  color .tl_set:N = \l_@@_xdots_color_tl ,
  color .value_required:n = true ,
  shorten .dim_set:N = \l_@@_xdots_shorten_dim ,
  shorten .value_required:n = true ,
```

The options `down` and `up` are not documented for the final user because he should use the syntax with `^` and `_`.

```

535     down .tl_set:N = \l_@@_xdots_down_tl ,
536     up .tl_set:N = \l_@@_xdots_up_tl ,
537     draw-first .code:n = \prg_do_nothing: ,
538     unknown .code:n = \@_error:n { Unknown-key-for-xdots }
539 }
```

```

540 \keys_define:nn { NiceMatrix / rules }
541 {
542     color .tl_set:N = \l_@@_rules_color_tl ,
543     color .value_required:n = true ,
544     width .dim_set:N = \arrayrulewidth ,
545     width .value_required:n = true
546 }
```

First, we define a set of keys “`NiceMatrix / Global`” which will be used (with the mechanism of `.inherit:n`) by other sets of keys.

```

547 \keys_define:nn { NiceMatrix / Global }
548 {
549     delimiters .code:n =
550         \keys_set:nn { NiceMatrix / delimiters } { #1 } ,
551     delimiters .value_required:n = true ,
552     rules .code:n = \keys_set:nn { NiceMatrix / rules } { #1 } ,
553     rules .value_required:n = true ,
554     standard-cline .bool_set:N = \l_@@_standard_cline_bool ,
555     standard-cline .default:n = true ,
556     cell-space-top-limit .dim_set:N = \l_@@_cell_space_top_limit_dim ,
557     cell-space-top-limit .value_required:n = true ,
558     cell-space-bottom-limit .dim_set:N = \l_@@_cell_space_bottom_limit_dim ,
559     cell-space-bottom-limit .value_required:n = true ,
560     cell-space-limits .meta:n =
561     {
562         cell-space-top-limit = #1 ,
563         cell-space-bottom-limit = #1 ,
564     },
565     cell-space-limits .value_required:n = true ,
566     xdots .code:n = \keys_set:nn { NiceMatrix / xdots } { #1 } ,
567     light-syntax .bool_set:N = \l_@@_light_syntax_bool ,
568     light-syntax .default:n = true ,
569     end-of-row .tl_set:N = \l_@@_end_of_row_tl ,
570     end-of-row .value_required:n = true ,
571     first-col .code:n = \int_zero:N \l_@@_first_col_int ,
572     first-row .code:n = \int_zero:N \l_@@_first_row_int ,
573     last-row .int_set:N = \l_@@_last_row_int ,
574     last-row .default:n = -1 ,
575     code-for-first-col .tl_set:N = \l_@@_code_for_first_col_tl ,
576     code-for-first-col .value_required:n = true ,
577     code-for-last-col .tl_set:N = \l_@@_code_for_last_col_tl ,
578     code-for-last-col .value_required:n = true ,
579     code-for-first-row .tl_set:N = \l_@@_code_for_first_row_tl ,
580     code-for-first-row .value_required:n = true ,
581     code-for-last-row .tl_set:N = \l_@@_code_for_last_row_tl ,
582     code-for-last-row .value_required:n = true ,
583     hlines .clist_set:N = \l_@@_hlines_clist ,
584     vlines .clist_set:N = \l_@@_vlines_clist ,
585     hlines .default:n = all ,
586     vlines .default:n = all ,
```

```

587 vlines-in-sub-matrix .code:n =
588 {
589     \tl_if_single_token:nTF { #1 }
590     { \tl_set:Nn \l_@@_letter_vlism_tl { #1 } }
591     { \@@_error:n { One-letter~allowed } }
592 },
593 vlines-in-sub-matrix .value_required:n = true ,
594 hvlines .code:n =
595 {
596     \clist_set:Nn \l_@@_vlines_clist { all }
597     \clist_set:Nn \l_@@_hlines_clist { all }
598 },
599 hvlines-except-borders .code:n =
600 {
601     \clist_set:Nn \l_@@_vlines_clist { all }
602     \clist_set:Nn \l_@@_hlines_clist { all }
603     \bool_set_true:N \l_@@_except_borders_bool
604 },
605 parallelize-diags .bool_set:N = \l_@@_parallelize_diags_bool ,

```

With the option `renew-dots`, the command `\cdots`, `\ldots`, `\vdots`, `\ddots`, etc. are redefined and behave like the commands `\Cdots`, `\Ldots`, `\Vdots`, `\Ddots`, etc.

```

606 renew-dots .bool_set:N = \l_@@_renew_dots_bool ,
607 renew-dots .value_forbidden:n = true ,
608 nullify-dots .bool_set:N = \l_@@_nullify_dots_bool ,
609 create-medium-nodes .bool_set:N = \l_@@_medium_nodes_bool ,
610 create-large-nodes .bool_set:N = \l_@@_large_nodes_bool ,
611 create-extra-nodes .meta:n =
612     { create-medium-nodes , create-large-nodes } ,
613 left-margin .dim_set:N = \l_@@_left_margin_dim ,
614 left-margin .default:n = \arraycolsep ,
615 right-margin .dim_set:N = \l_@@_right_margin_dim ,
616 right-margin .default:n = \arraycolsep ,
617 margin .meta:n = { left-margin = #1 , right-margin = #1 } ,
618 margin .default:n = \arraycolsep ,
619 extra-left-margin .dim_set:N = \l_@@_extra_left_margin_dim ,
620 extra-right-margin .dim_set:N = \l_@@_extra_right_margin_dim ,
621 extra-margin .meta:n =
622     { extra-left-margin = #1 , extra-right-margin = #1 } ,
623 extra-margin .value_required:n = true ,
624 }

```

We define a set of keys used by the environments of `nicematrix` (but not by the command `\NiceMatrixOptions`).

```

625 \keys_define:nn { NiceMatrix / Env }
626 {
627

```

The key `hvlines-except-corners` is now deprecated.

```

628 hvlines-except-corners .code:n =
629 {
630     \clist_set:Nn \l_@@_corners_clist { #1 }
631     \clist_set:Nn \l_@@_vlines_clist { all }
632     \clist_set:Nn \l_@@_hlines_clist { all }
633 },
634 hvlines-except-corners .default:n = { NW , SW , NE , SE } ,
635 corners .clist_set:N = \l_@@_corners_clist ,
636 corners .default:n = { NW , SW , NE , SE } ,
637 code-before .code:n =
638 {
639     \tl_if_empty:nF { #1 }
640     {

```

```

641         \tl_put_right:Nn \l_@@_code_before_tl { #1 }
642         \bool_set_true:N \l_@@_code_before_bool
643     }
644 },
```

The options `c`, `t` and `b` of the environment `{NiceArray}` have the same meaning as the option of the classical environment `{array}`.

```

645   c .code:n = \tl_set:Nn \l_@@_baseline_tl c ,
646   t .code:n = \tl_set:Nn \l_@@_baseline_tl t ,
647   b .code:n = \tl_set:Nn \l_@@_baseline_tl b ,
648   baseline .tl_set:N = \l_@@_baseline_tl ,
649   baseline .value_required:n = true ,
650   columns-width .code:n =
651     \tl_if_eq:nnTF { #1 } { auto }
652       { \bool_set_true:N \l_@@_auto_columns_width_bool }
653       { \dim_set:Nn \l_@@_columns_width_dim { #1 } } ,
654   columns-width .value_required:n = true ,
655   name .code:n =
```

We test whether we are in the measuring phase of an environment of `amsmath` (always loaded by `nicematrix`) because we want to avoid a fallacious message of duplicate name in this case.

```

656   \legacy_if:nF { measuring@ }
657   {
658     \str_set:Nn \l_tmpa_str { #1 }
659     \seq_if_in:NVTf \g_@@_names_seq \l_tmpa_str
660       { \@@_error:nn { Duplicate-name } { #1 } }
661       { \seq_gput_left:NV \g_@@_names_seq \l_tmpa_str }
662     \str_set_eq:NN \l_@@_name_str \l_tmpa_str
663   },
664   name .value_required:n = true ,
665   code-after .tl_gset:N = \g_nicematrix_code_after_tl ,
666   code-after .value_required:n = true ,
667   colortbl-like .code:n =
668     \bool_set_true:N \l_@@_colortbl_like_bool
669     \bool_set_true:N \l_@@_code_before_bool ,
670   colortbl-like .value_forbidden:n = true
671 }
```

```

672 \keys_define:nn { NiceMatrix / notes }
673 {
674   para .bool_set:N = \l_@@_notes_para_bool ,
675   para .default:n = true ,
676   code-before .tl_set:N = \l_@@_notes_code_before_tl ,
677   code-before .value_required:n = true ,
678   code-after .tl_set:N = \l_@@_notes_code_after_tl ,
679   code-after .value_required:n = true ,
680   bottomrule .bool_set:N = \l_@@_notes_bottomrule_bool ,
681   bottomrule .default:n = true ,
682   style .code:n = \cs_set:Nn \@@_notes_style:n { #1 } ,
683   style .value_required:n = true ,
684   label-in-tabular .code:n =
685     \cs_set:Nn \@@_notes_label_in_tabular:n { #1 } ,
686   label-in-tabular .value_required:n = true ,
687   label-in-list .code:n =
688     \cs_set:Nn \@@_notes_label_in_list:n { #1 } ,
689   label-in-list .value_required:n = true ,
690   enumitem-keys .code:n =
691   {
692     \bool_if:NTF \c_@@_in_preamble_bool
693     {
694       \AtBeginDocument
695       {
696         \bool_if:NT \c_@@_enumitem_loaded_bool
697           { \setlist* [ tabularnotes ] { #1 } }
```

```

698         }
699     }
700     {
701         \bool_if:NT \c_@@_enumitem_loaded_bool
702             { \setlist* [ tabularnotes ] { #1 } }
703     }
704     },
705     enumitem-keys .value_required:n = true ,
706     enumitem-keys-para .code:n =
707     {
708         \bool_if:NTF \c_@@_in_preamble_bool
709         {
710             \AtBeginDocument
711             {
712                 \bool_if:NT \c_@@_enumitem_loaded_bool
713                     { \setlist* [ tabularnotes* ] { #1 } }
714             }
715         }
716         {
717             \bool_if:NT \c_@@_enumitem_loaded_bool
718                 { \setlist* [ tabularnotes* ] { #1 } }
719         }
720     },
721     enumitem-keys-para .value_required:n = true ,
722     unknown .code:n = \@@_error:n { Unknown-key-for-notes }
723 }
724 \keys_define:nn { NiceMatrix / delimiters }
725 {
726     max-width .bool_set:N = \l_@@_delimiters_max_width_bool ,
727     max-width .default:n = true ,
728     color .tl_set:N = \l_@@_delimiters_color_tl ,
729     color .value_required:n = true ,
730 }

```

We begin the construction of the major sets of keys (used by the different user commands and environments).

```

731 \keys_define:nn { NiceMatrix }
732 {
733     NiceMatrixOptions .inherit:n =
734         { NiceMatrix / Global } ,
735     NiceMatrixOptions / xdots .inherit:n = NiceMatrix / xdots ,
736     NiceMatrixOptions / rules .inherit:n = NiceMatrix / rules ,
737     NiceMatrixOptions / notes .inherit:n = NiceMatrix / notes ,
738     NiceMatrixOptions / delimiters .inherit:n = NiceMatrix / delimiters ,
739     NiceMatrixOptions / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
740     SubMatrix / rules .inherit:n = NiceMatrix / rules ,
741     CodeAfter / xdots .inherit:n = NiceMatrix / xdots ,
742     NiceMatrix .inherit:n =
743         {
744             NiceMatrix / Global ,
745             NiceMatrix / Env ,
746         } ,
747     NiceMatrix / xdots .inherit:n = NiceMatrix / xdots ,
748     NiceMatrix / rules .inherit:n = NiceMatrix / rules ,
749     NiceMatrix / delimiters .inherit:n = NiceMatrix / delimiters ,
750     NiceTabular .inherit:n =
751         {
752             NiceMatrix / Global ,
753             NiceMatrix / Env
754         } ,
755     NiceTabular / xdots .inherit:n = NiceMatrix / xdots ,
756     NiceTabular / rules .inherit:n = NiceMatrix / rules ,

```

```

757 NiceTabular / delimiters .inherit:n = NiceMatrix / delimiters ,
758 NiceArray .inherit:n =
759 {
760     NiceMatrix / Global ,
761     NiceMatrix / Env ,
762 },
763 NiceArray / xdots .inherit:n = NiceMatrix / xdots ,
764 NiceArray / rules .inherit:n = NiceMatrix / rules ,
765 NiceArray / delimiters .inherit:n = NiceMatrix / delimiters ,
766 pNiceArray .inherit:n =
767 {
768     NiceMatrix / Global ,
769     NiceMatrix / Env ,
770 },
771 pNiceArray / xdots .inherit:n = NiceMatrix / xdots ,
772 pNiceArray / rules .inherit:n = NiceMatrix / rules ,
773 pNiceArray / delimiters .inherit:n = NiceMatrix / delimiters ,
774 }

```

We finalise the definition of the set of keys “`NiceMatrix / NiceMatrixOptions`” with the options specific to `\NiceMatrixOptions`.

```

775 \keys_define:nn { NiceMatrix / NiceMatrixOptions }
776 {
777     last-col .code:n = \tl_if_empty:nF { #1 }
778         { \@@_error:n { last-col~non~empty~for~NiceMatrixOptions } }
779         \int_zero:N \l_@@_last_col_int ,
780     small .bool_set:N = \l_@@_small_bool ,
781     small .value_forbidden:n = true ,

```

With the option `renew-matrix`, the environment `{matrix}` of `amsmath` and its variants are redefined to behave like the environment `{NiceMatrix}` and its variants.

```

782 renew-matrix .code:n = \@@_renew_matrix: ,
783 renew-matrix .value_forbidden:n = true ,

```

The key `transparent` is now considered as obsolete (because its name is ambiguous).

```

784 transparent .code:n =
785 {
786     \@@_renew_matrix:
787     \bool_set_true:N \l_@@_renew_dots_bool
788     \@@_error:n { Key~transparent }
789 },
790 transparent .value_forbidden:n = true ,

```

The option `exterior-arraycolsep` will have effect only in `{NiceArray}` for those who want to have for `{NiceArray}` the same behaviour as `{array}`.

```

791 exterior-arraycolsep .bool_set:N = \l_@@_exterior_arraycolsep_bool ,

```

If the option `columns-width` is used, all the columns will have the same width.
In `\NiceMatrixOptions`, the special value `auto` is not available.

```

792 columns-width .code:n =
793     \tl_if_eq:nnTF { #1 } { auto }
794     { \@@_error:n { Option~auto~for~columns-width } }
795     { \dim_set:Nn \l_@@_columns_width_dim { #1 } } ,

```

Usually, an error is raised when the user tries to give the same name to two distinct environments of `nicematrix` (theses names are global and not local to the current TeX scope). However, the option `allow-duplicate-names` disables this feature.

```

796 allow-duplicate-names .code:n =
797     \@@_msg_redirect_name:nn { Duplicate-name } { none } ,
798     allow-duplicate-names .value_forbidden:n = true ,

```

By default, the specifier used in the preamble of the array (for example in `\pNiceArray`) to draw a vertical dotted line between two columns is the colon “:”. However, it’s possible to change this letter with `letter-for-dotted-lines` and, by the way, the letter “:” will remain free for other packages (for example `arydshln`).

```

799 letter-for-dotted-lines .code:n =
800 {
801     \tl_if_single_token:nTF { #1 }
802     { \str_set:Nx \l_@@_letter_for_dotted_lines_str { #1 } }
803     { \@@_error:n { One-letter-allowed } }
804 },
805 letter-for-dotted-lines .value_required:n = true ,
806 notes .code:n = \keys_set:nn { NiceMatrix / notes } { #1 } ,
807 notes .value_required:n = true ,
808 sub-matrix .code:n =
809     \keys_set:nn { NiceMatrix / sub-matrix } { #1 } ,
810 sub-matrix .value_required:n = true ,
811 unknown .code:n = \@@_error:n { Unknown-key-for-NiceMatrixOptions }
812 }

813 \str_new:N \l_@@_letter_for_dotted_lines_str
814 \str_set_eq:NN \l_@@_letter_for_dotted_lines_str \cColonStr

```

`\NiceMatrixOptions` is the command of the `nicematrix` package to fix options at the document level. The scope of these specifications is the current TeX group.

```

815 \NewDocumentCommand \NiceMatrixOptions { m }
816   { \keys_set:nn { NiceMatrix / NiceMatrixOptions } { #1 } }

```

We finalise the definition of the set of keys “`NiceMatrix / NiceMatrix`” with the options specific to `{NiceMatrix}`.

```

817 \keys_define:nn { NiceMatrix / NiceMatrix }
818 {
819     last-col .code:n = \tl_if_empty:nTF {#1}
820     {
821         \bool_set_true:N \l_@@_last_col_without_value_bool
822         \int_set:Nn \l_@@_last_col_int { -1 }
823     }
824     { \int_set:Nn \l_@@_last_col_int { #1 } } ,
825     l .code:n = \tl_set:Nn \l_@@_type_of_col_tl l ,
826     r .code:n = \tl_set:Nn \l_@@_type_of_col_tl r ,
827     small .bool_set:N = \l_@@_small_bool ,
828     small .value_forbidden:n = true ,
829     unknown .code:n = \@@_error:n { Unknown-option-for-NiceMatrix }
830 }

```

We finalise the definition of the set of keys “`NiceMatrix / NiceArray`” with the options specific to `{NiceArray}`.

```

831 \keys_define:nn { NiceMatrix / NiceArray }
832 {

```

In the environments `{NiceArray}` and its variants, the option `last-col` must be used without value because the number of columns of the array is read from the preamble of the array.

```

833     small .bool_set:N = \l_@@_small_bool ,
834     small .value_forbidden:n = true ,
835     last-col .code:n = \tl_if_empty:nF { #1 }
836         { \@@_error:n { last-col-non-empty-for-NiceArray } }
837         \int_zero:N \l_@@_last_col_int ,
838     notes / para .bool_set:N = \l_@@_notes_para_bool ,
839     notes / para .default:n = true ,
840     notes / bottomrule .bool_set:N = \l_@@_notes_bottomrule_bool ,
841     notes / bottomrule .default:n = true ,
842     tabularnote .tl_set:N = \l_@@_tabularnote_tl ,

```

```

843 tabularnote .value_required:n = true ,
844 r .code:n = \@@_error:n { r~or~l~with~preamble } ,
845 l .code:n = \@@_error:n { r~or~l~with~preamble } ,
846 unknown .code:n = \@@_error:n { Unknown~option~for~NiceArray }
847 }
848 \keys_define:nn { NiceMatrix / pNiceArray }
849 {
850   first-col .code:n = \int_zero:N \l_@@_first_col_int ,
851   last-col .code:n = \tl_if_empty:nF {#1}
852     { \@@_error:n { last-col~non~empty~for~NiceArray } }
853     \int_zero:N \l_@@_last_col_int ,
854   first-row .code:n = \int_zero:N \l_@@_first_row_int ,
855   small .bool_set:N = \l_@@_small_bool ,
856   small .value_forbidden:n = true ,
857   r .code:n = \@@_error:n { r~or~l~with~preamble } ,
858   l .code:n = \@@_error:n { r~or~l~with~preamble } ,
859   unknown .code:n = \@@_error:n { Unknown~option~for~NiceMatrix }
860 }

```

We finalise the definition of the set of keys “NiceMatrix / NiceTabular” with the options specific to {NiceTabular}.

```

861 \keys_define:nn { NiceMatrix / NiceTabular }
862 {
863   notes / para .bool_set:N = \l_@@_notes_para_bool ,
864   notes / para .default:n = true ,
865   notes / bottomrule .bool_set:N = \l_@@_notes_bottomrule_bool ,
866   notes / bottomrule .default:n = true ,
867   tabularnote .tl_set:N = \l_@@_tabularnote_tl ,
868   tabularnote .value_required:n = true ,
869   last-col .code:n = \tl_if_empty:nF {#1}
870     { \@@_error:n { last-col~non~empty~for~NiceArray } }
871     \int_zero:N \l_@@_last_col_int ,
872   r .code:n = \@@_error:n { r~or~l~with~preamble } ,
873   l .code:n = \@@_error:n { r~or~l~with~preamble } ,
874   unknown .code:n = \@@_error:n { Unknown~option~for~NiceTabular }
875 }

```

Important code used by {NiceArrayWithDelims}

The pseudo-environment \@@_Cell:-\@@_end_Cell: will be used to format the cells of the array. In the code, the affectations are global because this pseudo-environment will be used in the cells of a \halign (via an environment {array}).

```

876 \cs_new_protected:Npn \@@_Cell:
877 {

```

At the beginning of the cell, we link \CodeAfter to a command which do *not* begin with \omit (whereas the standard version of \CodeAfter begins with \omit).

```

878   \cs_set_eq:NN \CodeAfter \@@_CodeAfter_i:n

```

We increment \c@jCol, which is the counter of the columns.

```

879   \int_gincr:N \c@jCol

```

Now, we increment the counter of the rows. We don't do this incrementation in the \everycr because some packages, like arydshln, create special rows in the \halign that we don't want to take into account.

```

880   \int_compare:nNnT \c@jCol = 1
881     { \int_compare:nNnT \l_@@_first_col_int = 1 \@@_begin_of_row: }

```

The content of the cell is composed in the box `\l_@@_cell_box` because we want to compute some dimensions of the box. The `\hbox_set_end:` corresponding to this `\hbox_set:Nw` will be in the `\@@_end_Cell:` (and the potential `\c_math_toggle_token` also).

```

882 \hbox_set:Nw \l_@@_cell_box
883 \bool_if:NF \l_@@_NiceTabular_bool
884 {
885     \c_math_toggle_token
886     \bool_if:NT \l_@@_small_bool \scriptstyle
887 }

```

We will call *corners* of the matrix the cases which are at the intersection of the exterior rows and exterior columns (of course, the four corners doesn't always exist simultaneously).

The codes `\l_@@_code_for_first_row_tl` and `al` don't apply in the corners of the matrix.

```

888 \int_compare:nNnTF \c@iRow = 0
889 {
890     \int_compare:nNnT \c@jCol > 0
891     {
892         \l_@@_code_for_first_row_tl
893         \xglobal \colorlet{nicematrix-first-row}{.}
894     }
895 }
896 {
897     \int_compare:nNnT \c@iRow = \l_@@_last_row_int
898     {
899         \l_@@_code_for_last_row_tl
900         \xglobal \colorlet{nicematrix-last-row}{.}
901     }
902 }
903 }

```

The following macro `\@@_begin_of_row` is usually used in the cell number 1 of the row. However, when the key `first-col` is used, `\@@_begin_of_row` is executed in the cell number 0 of the row.

```

904 \cs_new_protected:Npn \@@_begin_of_row:
905 {
906     \int_gincr:N \c@iRow
907     \dim_gset_eq:NN \g_@@_dp_ante_last_row_dim \g_@@_dp_last_row_dim
908     \dim_gset:Nn \g_@@_dp_last_row_dim {\box_dp:N \carstrutbox}
909     \dim_gset:Nn \g_@@_ht_last_row_dim {\box_ht:N \carstrutbox}
910     \pgfpicture
911     \pgfrememberpicturepositiononpagetrue
912     \pgfcoordinate
913     { \@@_env: - row - \int_use:N \c@iRow - base }
914     { \pgfpoint \c_zero_dim { 0.5 \arrayrulewidth } }
915     \str_if_empty:NF \l_@@_name_str
916     {
917         \pgfnodealias
918         { \l_@@_name_str - row - \int_use:N \c@iRow - base }
919         { \@@_env: - row - \int_use:N \c@iRow - base }
920     }
921     \endpgfpicture
922 }

```

Remark: If the key `recreate-cell-nodes` of the `\CodeBefore` is used, then we will add some lines to that command.

The following code is used in each cell of the array. It actualises quantities that, at the end of the array, will give informations about the vertical dimension of the two first rows and the two last rows. If the user uses the `last-row`, some lines of code will be dynamically added to this command.

```

923 \cs_new_protected:Npn \@@_update_for_first_and_last_row:
924 {
925     \int_compare:nNnTF \c@iRow = 0

```

```

926     {
927         \dim_gset:Nn \g_@@_dp_row_zero_dim
928             { \dim_max:nn \g_@@_dp_row_zero_dim { \box_dp:N \l_@@_cell_box } }
929         \dim_gset:Nn \g_@@_ht_row_zero_dim
930             { \dim_max:nn \g_@@_ht_row_zero_dim { \box_ht:N \l_@@_cell_box } }
931     }
932     {
933         \int_compare:nNnT \c@iRow = 1
934             {
935                 \dim_gset:Nn \g_@@_ht_row_one_dim
936                     { \dim_max:nn \g_@@_ht_row_one_dim { \box_ht:N \l_@@_cell_box } }
937             }
938     }
939 }
940 \cs_new_protected:Npn \@@_rotate_cell_box:
941 {
942     \box_rotate:Nn \l_@@_cell_box { 90 }
943     \int_compare:nNnT \c@iRow = \l_@@_last_row_int
944     {
945         \vbox_set_top:Nn \l_@@_cell_box
946             {
947                 \vbox_to_zero:n {}
948                 \skip_vertical:n { - \box_ht:N \carstrutbox + 0.8 ex }
949                 \box_use:N \l_@@_cell_box
950             }
951     }
952     \bool_gset_false:N \g_@@_rotate_bool
953 }
954 \cs_new_protected:Npn \@@_adjust_size_box:
955 {
956     \dim_compare:nNnT \g_@@_blocks_wd_dim > \c_zero_dim
957     {
958         \box_set_wd:Nn \l_@@_cell_box
959             { \dim_max:nn { \box_wd:N \l_@@_cell_box } \g_@@_blocks_wd_dim }
960         \dim_gzero:N \g_@@_blocks_wd_dim
961     }
962     \dim_compare:nNnT \g_@@_blocks_dp_dim > \c_zero_dim
963     {
964         \box_set_dp:Nn \l_@@_cell_box
965             { \dim_max:nn { \box_dp:N \l_@@_cell_box } \g_@@_blocks_dp_dim }
966         \dim_gzero:N \g_@@_blocks_dp_dim
967     }
968     \dim_compare:nNnT \g_@@_blocks_ht_dim > \c_zero_dim
969     {
970         \box_set_ht:Nn \l_@@_cell_box
971             { \dim_max:nn { \box_ht:N \l_@@_cell_box } \g_@@_blocks_ht_dim }
972         \dim_gzero:N \g_@@_blocks_ht_dim
973     }
974 }
975 \cs_new_protected:Npn \@@_end_Cell:
976 {
977     \@@_math_toggle_token:
978     \hbox_set_end:
979     \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
980     \@@_adjust_size_box:
981     \box_set_ht:Nn \l_@@_cell_box
982         { \box_ht:N \l_@@_cell_box + \l_@@_cell_space_top_limit_dim }
983     \box_set_dp:Nn \l_@@_cell_box
984         { \box_dp:N \l_@@_cell_box + \l_@@_cell_space_bottom_limit_dim }

```

We want to compute in $\g_@@_max_cell_width_dim$ the width of the widest cell of the array (except the cells of the “first column” and the “last column”).

```

985 \dim_gset:Nn \g_@@_max_cell_width_dim
986     { \dim_max:nn \g_@@_max_cell_width_dim { \box_wd:N \l_@@_cell_box } }

```

The following computations are for the “first row” and the “last row”.

```

987 \@@_update_for_first_and_last_row:

```

If the cell is empty, or may be considered as if, we must not create the PGF node, for two reasons:

- it’s a waste of time since such a node would be rather pointless;
- we test the existence of these nodes in order to determine whether a cell is empty when we search the extremities of a dotted line.

However, it’s very difficult to determine whether a cell is empty. Up to now we use the following technic:

- if the width of the box `\l_@@_cell_box` (created with the content of the cell) is equal to zero, we consider the cell as empty (however, this is not perfect since the user may have used a `\rlap`, a `\llap` or a `\mathclap` of `mathtools`).
- the cells with a command `\Ldots` or `\Cdots`, `\Vdots`, etc., should also be considered as empty; if `nullify-dots` is in force, there would be nothing to do (in this case the previous commands only write an instruction in a kind of `\CodeAfter`); however, if `nullify-dots` is not in force, a phantom of `\ldots`, `\cdots`, `\vdots` is inserted and its width is not equal to zero; that’s why these commands raise a boolean `\g_@@_empty_cell_bool` and we begin by testing this boolean.

```

988 \bool_if:NTF \g_@@_empty_cell_bool
989     { \box_use_drop:N \l_@@_cell_box }
990     {
991         \bool_lazy_or:nnTF
992             \g_@@_not_empty_cell_bool
993             { \dim_compare_p:nNn { \box_wd:N \l_@@_cell_box } > \c_zero_dim }
994             \@@_node_for_cell:
995             { \box_use_drop:N \l_@@_cell_box }
996         }
997         \int_gset:Nn \g_@@_col_total_int { \int_max:nn \g_@@_col_total_int \c@jCol }
998         \bool_gset_false:N \g_@@_empty_cell_bool
999         \bool_gset_false:N \g_@@_not_empty_cell_bool
1000     }

```

The following command creates the PGF name of the node with, of course, `\l_@@_cell_box` as the content.

```

1001 \cs_new_protected:Npn \@@_node_for_cell:
1002     {
1003         \pgfpicture
1004         \pgfsetbaseline \c_zero_dim
1005         \pgfrememberpicturepositiononpagetrue
1006         \pgfset
1007             {
1008                 inner-sep = \c_zero_dim ,
1009                 minimum-width = \c_zero_dim
1010             }
1011         \pgfnode
1012             { rectangle }
1013             { base }
1014             { \box_use_drop:N \l_@@_cell_box }
1015             { \@@_env: - \int_use:N \c@iRow - \int_use:N \c@jCol }
1016             { }
1017         \str_if_empty:NF \l_@@_name_str
1018             {
1019                 \pgfnodealias
1020                     { \l_@@_name_str - \int_use:N \c@iRow - \int_use:N \c@jCol }
1021                     { \@@_env: - \int_use:N \c@iRow - \int_use:N \c@jCol }
1022             }
1023         \endpgfpicture
1024     }

```

As its name says, the following command is a patch for the command `\@@_node_for_cell`. This patch will be appended on the left of `\@@_node_for_the_cell`: when the construction of the cell nodes (of the form $(i-j)$) in the `\CodeBefore` is required.

```

1025 \cs_new_protected:Npn \@@_patch_node_for_cell:n #1
1026 {
1027     \cs_new_protected:Npn \@@_patch_node_for_cell:
1028     {
1029         \hbox_set:Nn \l_@@_cell_box
1030         {
1031             \box_move_up:nn { \box_ht:N \l_@@_cell_box}
1032             \hbox_overlap_left:n
1033             {
1034                 \pgfsys@markposition
1035                 { \@@_env: - \int_use:N \c@iRow - \int_use:N \c@jCol - NW }
1036             }
1037         }
1038         \box_use:N \l_@@_cell_box
1039         \box_move_down:nn { \box_dp:N \l_@@_cell_box }
1040         \hbox_overlap_left:n
1041         {
1042             \pgfsys@markposition
1043             { \@@_env: - \int_use:N \c@iRow - \int_use:N \c@jCol - SE }
1044             #1
1045         }
1046     }
1047 }
1048 }
```

I don't know why the following adjustement is needed when the compilation is done with XeLaTeX or with the classical way `latex`, `dvips`, `ps2pdf` (or Adobe Distiller). However, it seems to work.

```

1036         #1
1037     }
1038     \box_use:N \l_@@_cell_box
1039     \box_move_down:nn { \box_dp:N \l_@@_cell_box }
1040     \hbox_overlap_left:n
1041     {
1042         \pgfsys@markposition
1043         { \@@_env: - \int_use:N \c@iRow - \int_use:N \c@jCol - SE }
1044         #1
1045     }
1046 }
1047 }
1048 }
```

We have no explanation for the different behaviour between the TeX engines...

```

1049 \bool_lazy_or:nnTF \sys_if_engine_xetex_p: \sys_if_output_dvi_p:
1050 {
1051     \@@_patch_node_for_cell:n
1052     { \skip_horizontal:n { 0.5 \box_wd:N \l_@@_cell_box } }
1053 }
1054 { \@@_patch_node_for_cell:n { } }
```

The second argument of the following command `\@@_instruction_of_type:nnn` defined below is the type of the instruction (`Cdots`, `Vdots`, `Ddots`, etc.). The third argument is the list of options. This command writes in the corresponding `\g_@@_type_lines_tl` the instruction which will actually draw the line after the construction of the matrix.

For example, for the following matrix,

```
\begin{pNiceMatrix}
1 & 2 & 3 & 4 \\
5 & \Cdots & & 6 \\
7 & \Cdots [color=red]
\end{pNiceMatrix}
```

$$\begin{pmatrix} 1 & 2 & 3 & 4 \\ 5 & \cdots & & 6 \\ 7 & \cdots & & \end{pmatrix}$$

the content of `\g_@@_Cdots_lines_tl` will be:

```
\@@_draw_Cdots:nnn {2}{2}{}
\@@_draw_Cdots:nnn {3}{2}{color=red}
```

The first argument is a boolean which indicates whether you must put the instruction on the left or on the right on the list of instructions.

```

1055 \cs_new_protected:Npn \@@_instruction_of_type:nnn #1 #2 #3
1056 {
1057     \bool_if:nTF { #1 } \tl_gput_left:cx \tl_gput_right:cx
1058     { g_@@_ #2 _ lines _ tl }
```

```

1059     {
1060         \use:c { @@_draw _ #2 : nnn }
1061         { \int_use:N \c@iRow }
1062         { \int_use:N \c@jCol }
1063         { \exp_not:n { #3 } }
1064     }
1065 }
```

We want to use `\array` of `array`. However, if the class used is `revtex4-1` or `revtex4-2`, we have to do some tuning and use the command `\@array@array` instead of `\array` because these classes do a redefinition of `\array` incompatible with our use of `\array`.

```

1066 \cs_new_protected:Npn \@@_revtex_array:
1067 {
1068     \cs_set_eq:NN \acolll \arrayacol
1069     \cs_set_eq:NN \acolr \arrayacol
1070     \cs_set_eq:NN \acol \arrayacol
1071     \cs_set_nopar:Npn \Ohalignto { }
1072     \@array@array
1073 }
1074 \cs_new_protected:Npn \@@_array:
1075 {
1076     \bool_if:NTF \c_@@_revtex_bool
1077         \@@_revtex_array:
1078     {
1079         \bool_if:NTF \l_@@_NiceTabular_bool
1080             { \dim_set_eq:NN \col@sep \tabcolsep }
1081             { \dim_set_eq:NN \col@sep \arraycolsep }
1082         \dim_compare:nNnTF \l_@@_tabular_width_dim = \c_zero_dim
1083             { \cs_set_nopar:Npn \Ohalignto { } }
1084             { \cs_set_nopar:Npx \Ohalignto { to \dim_use:N \l_@@_tabular_width_dim } }
```

It `colortbl` is loaded, `\@tabarray` has been redefined to incorporate `\CT@start`.

```

1085     \@tabarray
1086 }
\l_@@_baseline_tl may have the value t, c or b. However, if the value is b, we compose the
\array (of array) with the option t and the right translation will be done further. Remark that
\str_if_eq:VnTF is fully expandable and you need something fully expandable here.
1087     [ \str_if_eq:VnTF \l_@@_baseline_tl c c t ]
1088 }
```

We keep in memory the standard version of `\ialign` because we will redefine `\ialign` in the environment `{NiceArrayWithDelims}` but restore the standard version for use in the cells of the array.

```
1089 \cs_set_eq:NN \@@_old_ialign: \ialign
```

The following command creates a `row` node (and not a row of nodes!).

```

1090 \cs_new_protected:Npn \@@_create_row_node:
1091 {
```

The `\hbox:n` (or `\hbox`) is mandatory.

```

1092 \hbox
1093 {
1094     \bool_if:NT \l_@@_code_before_bool
1095     {
1096         \vtop
1097         {
1098             \skip_vertical:N 0.5\arrayrulewidth
1099             \pgfsys@markposition { \@@_env: - row - \@@_succ:n \c@iRow }
1100             \skip_vertical:N -0.5\arrayrulewidth
1101         }
1102     }
1103     \pgfpicture
1104     \pgfrememberpicturepositiononpagetrue
```

```

1105     \pgfcoordinate { \@@_env: - row - \@@_succ:n \c@iRow }
1106     { \pgfpoint \c_zero_dim { - 0.5 \arrayrulewidth } }
1107     \str_if_empty:NF \l_@@_name_str
1108     {
1109         \pgfnodealias
1110         { \l_@@_name_str - row - \int_use:N \c@iRow }
1111         { \@@_env: - row - \int_use:N \c@iRow }
1112     }
1113     \endpgfpicture
1114 }
1115 }
```

The following must *not* be protected because it begins with `\noalign`.

```

1116 \cs_new:Npn \@@_everycr: { \noalign { \@@_everycr_i: } }
1117 \cs_new_protected:Npn \@@_everycr_i:
1118 {
1119     \int_gzero:N \c@jCol
1120     \bool_gset_false:N \g_@@_after_col_zero_bool
1121     \bool_if:NF \g_@@_row_of_col_done_bool
1122     {
1123         \@@_create_row_node:
```

We don't draw the rules of the key `hlines` (or `hvlines`) but we reserve the vertical space for theses rules.

```

1124 \tl_if_empty:NF \l_@@_hlines_clist
1125 {
1126     \tl_if_eq:NnF \l_@@_hlines_clist { all }
1127     {
1128         \exp_args:NNx
1129         \clist_if_in:NnT
1130         \l_@@_hlines_clist
1131         { \@@_succ:n \c@iRow }
1132     }
1133 }
```

The counter `\c@iRow` has the value -1 only if there is a “first row” and that we are before that “first row”, i.e. just before the beginning of the array.

```

1134     \int_compare:nNnT \c@iRow > { -1 }
1135     {
1136         \int_compare:nNnF \c@iRow = \l_@@_last_row_int
```

The command `\CT@arc@` is a command of `colortbl` which sets the color of the rules in the array. The package `nicematrix` uses it even if `colortbl` is not loaded. We use a TeX group in order to limit the scope of `\CT@arc@`.

```

1137         { \hrule height \arrayrulewidth width \c_zero_dim }
1138     }
1139 }
1140 }
1141 }
1142 }
```

The command `\@@_newcolumntype` is the command `\newcolumntype` of `array` without the warnings for redefinitions of columns types (we will use it to redefine the columns types `w` and `W`).

```

1143 \cs_set_protected:Npn \@@_newcolumntype #1
1144 {
1145     \cs_set:cpn { NC @ find @ #1 } ##1 #1 { \NC@ { ##1 } }
1146     \peek_meaning:NTF [
1147     { \newcol@ #1 }
1148     { \newcol@ #1 [ 0 ] }
1149 }
```

When the key `renew-dots` is used, the following code will be executed.

```
1150 \cs_set_protected:Npn \@@_renew_dots:
1151 {
1152     \cs_set_eq:NN \ldots \@@_Ldots
1153     \cs_set_eq:NN \cdots \@@_Cdots
1154     \cs_set_eq:NN \vdots \@@_Vdots
1155     \cs_set_eq:NN \ddots \@@_Ddots
1156     \cs_set_eq:NN \iddots \@@_Idots
1157     \cs_set_eq:NN \dots \@@_Ldots
1158     \cs_set_eq:NN \hdotsfor \@@_Hdotsfor:
1159 }
```

When the key `colortbl-like` is used, the following code will be executed.

```
1160 \cs_new_protected:Npn \@@_colortbl_like:
1161 {
1162     \cs_set_eq:NN \cellcolor \@@_cellcolor_tabular
1163     \cs_set_eq:NN \rowcolor \@@_rowcolor_tabular
1164     \cs_set_eq:NN \columncolor \@@_columncolor_preamble
1165 }
```

The following code `\@@_pre_array_ii:` is used in `{NiceArrayWithDelims}`. It exists as a standalone macro only for legibility.

```
1166 \cs_new_protected:Npn \@@_pre_array_ii:
1167 {
```

If `booktabs` is loaded, we have to patch the macro `\@BTnormal` which is a macro of `booktabs`. The macro `\@BTnormal` draws an horizontal rule but it occurs after a vertical skip done by a low level TeX command. When this macro `\@BTnormal` occurs, the `row` node has yet been inserted by `nicematrix` before the vertical skip (and thus, at a wrong place). That why we decide to create a new `row` node (for the same row). We patch the macro `\@BTnormal` to create this `row` node. This new `row` node will overwrite the previous definition of that `row` node and we have managed to avoid the error messages of that redefinition ⁵⁴.

```
1168 \bool_if:NT \c_@@_booktabs_loaded_bool
1169     { \tl_put_left:Nn \@BTnormal \@@_create_row_node: }
1170 \box_clear_new:N \l_@@_cell_box
1171 \normalbaselines
```

If the option `small` is used, we have to do some tuning. In particular, we change the value of `\arraystretch` (this parameter is used in the construction of `\carstrutbox` in the beginning of `{array}`).

```
1172 \bool_if:NT \l_@@_small_bool
1173 {
1174     \cs_set_nopar:Npn \arraystretch { 0.47 }
1175     \dim_set:Nn \arraycolsep { 1.45 pt }
1176 }
```



```
1177 \bool_if:NT \g_@@_recreate_cell_nodes_bool
1178 {
1179     \tl_put_right:Nn \@@_begin_of_row:
1180     {
1181         \pgf@sys@markposition
1182         { \@@_env: - row - \int_use:N \c@iRow - base }
1183     }
1184 }
```

⁵⁴cf. `\nicematrix@redefine@check@rerun`

The environment `{array}` uses internally the command `\ialign`. We change the definition of `\ialign` for several reasons. In particular, `\ialign` sets `\everycr` to `{ }` and we *need* to have to change the value of `\everycr`.

```

1185 \cs_set_nopar:Npn \ialign
1186 {
1187     \bool_if:NTF \c_@@_colortbl_loaded_bool
1188     {
1189         \CT@everycr
1190         {
1191             \noalign { \cs_gset_eq:NN \CT@row@color \prg_do_nothing: }
1192             \c_@@_everycr:
1193         }
1194     }
1195     { \everycr { \c_@@_everycr: } }
1196     \tabskip = \c_zero_skip

```

The box `\@arstrutbox` is a box constructed in the beginning of the environment `{array}`. The construction of that box takes into account the current value of `\arraystretch`⁵⁵ and `\extrarowheight` (of `array`). That box is inserted (via `\@arstrut`) in the beginning of each row of the array. That's why we use the dimensions of that box to initialize the variables which will be the dimensions of the potential first and last row of the environment. This initialization must be done after the creation of `\@arstrutbox` and that's why we do it in the `\ialign`.

```

1197     \dim_gzero_new:N \g_@@_dp_row_zero_dim
1198     \dim_gset:Nn \g_@@_dp_row_zero_dim { \box_dp:N \@arstrutbox }
1199     \dim_gzero_new:N \g_@@_ht_row_zero_dim
1200     \dim_gset:Nn \g_@@_ht_row_zero_dim { \box_ht:N \@arstrutbox }
1201     \dim_gzero_new:N \g_@@_ht_row_one_dim
1202     \dim_gset:Nn \g_@@_ht_row_one_dim { \box_ht:N \@arstrutbox }
1203     \dim_gzero_new:N \g_@@_dp_ante_last_row_dim
1204     \dim_gzero_new:N \g_@@_ht_last_row_dim
1205     \dim_gset:Nn \g_@@_ht_last_row_dim { \box_ht:N \@arstrutbox }
1206     \dim_gzero_new:N \g_@@_dp_last_row_dim
1207     \dim_gset:Nn \g_@@_dp_last_row_dim { \box_dp:N \@arstrutbox }

```

After its first use, the definition of `\ialign` will revert automatically to its default definition. With this programmation, we will have, in the cells of the array, a clean version of `\ialign`.

```

1208     \cs_set_eq:NN \ialign \c_@@_old_ialign:
1209     \halign
1210 }

```

We keep in memory the old versions or `\ldots`, `\cdots`, etc. only because we use them inside `\phantom` commands in order that the new commands `\Ldots`, `\Cdots`, etc. give the same spacing (except when the option `nullify-dots` is used).

```

1211     \cs_set_eq:NN \c_@@_old_ldots \ldots
1212     \cs_set_eq:NN \c_@@_old_cdots \cdots
1213     \cs_set_eq:NN \c_@@_old_vdots \vdots
1214     \cs_set_eq:NN \c_@@_old_ddots \ddots
1215     \cs_set_eq:NN \c_@@_old_iddots \iddots
1216     \bool_if:NTF \l_@@_standard_cline_bool
1217     { \cs_set_eq:NN \cline \c_@@_standard_cline }
1218     { \cs_set_eq:NN \cline \c_@@_cline }
1219     \cs_set_eq:NN \Ldots \c_@@_Ldots
1220     \cs_set_eq:NN \Cdots \c_@@_Cdots
1221     \cs_set_eq:NN \Vdots \c_@@_Vdots
1222     \cs_set_eq:NN \Ddots \c_@@_Ddots
1223     \cs_set_eq:NN \Iddots \c_@@_Iddots
1224     \cs_set_eq:NN \hdottedline \c_@@_hdottedline:
1225     \cs_set_eq:NN \Hline \c_@@_Hline:
1226     \cs_set_eq:NN \Hspace \c_@@_Hspace:
1227     \cs_set_eq:NN \Hdotsfor \c_@@_Hdotsfor:

```

⁵⁵The option `small` of `nicematrix` changes (among other) the value of `\arraystretch`. This is done, of course, before the call of `{array}`.

```

1228 \cs_set_eq:NN \Vdotsfor \@@_Vdotsfor:
1229 \cs_set_eq:NN \multicolumn \@@_multicolumn:nnn
1230 \cs_set_eq:NN \Block \@@_Block:
1231 \cs_set_eq:NN \rotate \@@_rotate:
1232 \cs_set_eq:NN \OnlyMainNiceMatrix \@@_OnlyMainNiceMatrix:n
1233 \cs_set_eq:NN \dotfill \@@_old_dotfill:
1234 \cs_set_eq:NN \CodeAfter \@@_CodeAfter:
1235 \cs_set_eq:NN \diagbox \@@_diagbox:nn
1236 \cs_set_eq:NN \NotEmpty \@@_NotEmpty:
1237 \bool_if:NT \l_@@_colortbl_like_bool \@@_colortbl_like:
1238 \bool_if:NT \l_@@_renew_dots_bool \@@_renew_dots:

```

The sequence `\g_@@_multicolumn_cells_seq` will contain the list of the cells of the array where a command `\multicolumn{n}{...}{...}` with $n > 1$ is issued. In `\g_@@_multicolumn_sizes_seq`, the “sizes” (that is to say the values of n) correspondant will be stored. These lists will be used for the creation of the “medium nodes” (if they are created).

```

1239 \seq_gclear:N \g_@@_multicolumn_cells_seq
1240 \seq_gclear:N \g_@@_multicolumn_sizes_seq

```

The counter `\c@iRow` will be used to count the rows of the array (its incrementation will be in the first cell of the row).

```

1241 \int_gset:Nn \c@iRow { \l_@@_first_row_int - 1 }

```

At the end of the environment `{array}`, `\c@iRow` will be the total number of rows.

`\g_@@_row_total_int` will be the number of rows excepted the last row (if `\l_@@_last_row_bool` has been raised with the option `last-row`).

```

1242 \int_gzero_new:N \g_@@_row_total_int

```

The counter `\c@jCol` will be used to count the columns of the array. Since we want to know the total number of columns of the matrix, we also create a counter `\g_@@_col_total_int`. These counters are updated in the command `\@@_Cell:` executed at the beginning of each cell.

```

1243 \int_gzero_new:N \g_@@_col_total_int
1244 \cs_set_eq:NN \c@ifnextchar \new@ifnextchar
1245 \@@_renew_NC@rewrite@S:
1246 \bool_gset_false:N \g_@@_last_col_found_bool

```

During the construction of the array, the instructions `\Cdots`, `\Ldots`, etc. will be written in token lists `\g_@@_Cdots_lines_tl`, etc. which will be executed after the construction of the array.

```

1247 \tl_gclear_new:N \g_@@_Cdots_lines_tl
1248 \tl_gclear_new:N \g_@@_Ldots_lines_tl
1249 \tl_gclear_new:N \g_@@_Vdots_lines_tl
1250 \tl_gclear_new:N \g_@@_Ddots_lines_tl
1251 \tl_gclear_new:N \g_@@_Iddots_lines_tl
1252 \tl_gclear_new:N \g_@@_HVdotsfor_lines_tl

1253 \tl_gclear_new:N \g_nicematrix_code_before_tl
1254 }

```

This is the end of `\@@_pre_array_i::`.

The command `\@@_pre_array:` will be executed after analyse of the keys of the environment.

```

1255 \cs_new_protected:Npn \@@_pre_array:
1256 {
1257 \cs_if_exist:NT \theiRow { \int_set_eq:NN \l_@@_old_iRow_int \c@iRow }
1258 \int_gzero_new:N \c@iRow
1259 \cs_if_exist:NT \thejCol { \int_set_eq:NN \l_@@_old_jCol_int \c@jCol }
1260 \int_gzero_new:N \c@jCol

```

We recall that `\l_@@_last_row_int` and `\l_@@_last_column_int` are *not* the numbers of the last row and last column of the array. There are only the values of the keys `last-row` and `last-column` (maybe the user has provided erroneous values). The meaning of that counters does not change during the environment of `nicematrix`. There is only a slight adjustment: if the user have used one of those keys without value, we provide now the right value as read on the `aux` file (of course, it's possible only after the first compilation).

```

1261 \int_compare:nNnT \l_@@_last_row_int = { -1 }
1262 {
1263     \bool_set_true:N \l_@@_last_row_without_value_bool
1264     \bool_if:NT \g_@@_aux_found_bool
1265         { \int_set:Nn \l_@@_last_row_int { \seq_item:Nn \c_@@_size_seq 3 } }
1266     }
1267 \int_compare:nNnT \l_@@_last_col_int = { -1 }
1268 {
1269     \bool_if:NT \g_@@_aux_found_bool
1270         { \int_set:Nn \l_@@_last_col_int { \seq_item:Nn \c_@@_size_seq 6 } }
1271 }
```

If there is a exterior row, we patch a command used in `\@@_Cell`: in order to keep track of some dimensions needed to the construction of that “last row”.

```

1272 \int_compare:nNnT \l_@@_last_row_int > { -2 }
1273 {
1274     \tl_put_right:Nn \@@_update_for_first_and_last_row:
1275     {
1276         \dim_gset:Nn \g_@@_ht_last_row_dim
1277             { \dim_max:nn \g_@@_ht_last_row_dim { \box_ht:N \l_@@_cell_box } }
1278         \dim_gset:Nn \g_@@_dp_last_row_dim
1279             { \dim_max:nn \g_@@_dp_last_row_dim { \box_dp:N \l_@@_cell_box } }
1280     }
1281 }
```

1282 \seq_gclear:N \g_@@_submatrix_seq

Now the `\CodeBefore`.

```
1283 \bool_if:NT \l_@@_code_before_bool \@@_exec_code_before:
```

The value of `\g_@@_pos_of_blocks_seq` has been written on the `aux` file and loaded before the (potential) execution of the `\CodeBefore`. Now, we clear that variable because it will be reconstructed during the creation of the array.

```
1284 \seq_gclear:N \g_@@_pos_of_blocks_seq
```

Idem for other sequences written on the `aux` file.

```
1285 \seq_gclear_new:N \g_@@_multicolumn_cells_seq
1286 \seq_gclear_new:N \g_@@_multicolumn_sizes_seq
```

The code in `\@@_pre_array_ii`: is used only here.

```
1287 \@@_pre_array_ii:
```

The array will be composed in a box (named `\l_@@_the_array_box`) because we have to do manipulations concerning the potential exterior rows.

```
1288 \box_clear_new:N \l_@@_the_array_box
```

If the user has loaded `nicematrix` with the option `define-L-C-R`, he will be able to use `L`, `C` and `R` instead of `l`, `c` and `r` in the preambles of the environments of `nicematrix` (it's a compatibility mode since `L`, `C` and `R` were mandatory before version 5.0).

```
1289 \bool_if:NT \c_@@_define_L_C_R_bool \@@_define_L_C_R:
```

The preamble will be constructed in `\g_@@_preamble_tl`.

```
1290     \@@_construct_preamble:
```

Now, the preamble is constructed in `\g_@@_preamble_tl`

We compute the width of both delimiters. We remember that, when the environment `{NiceArray}` is used, it's possible to specify the delimiters in the preamble (eg `[ccc]`).

```
1291     \dim_zero_new:N \l_@@_left_delim_dim
1292     \dim_zero_new:N \l_@@_right_delim_dim
1293     \bool_if:NTF \l_@@_NiceArray_bool
1294     {
1295         \dim_gset:Nn \l_@@_left_delim_dim { 2 \arraycolsep }
1296         \dim_gset:Nn \l_@@_right_delim_dim { 2 \arraycolsep }
1297     }
1298 }
```

The command `\bBigg@` is a command of `amsmath`.

```
1299     \hbox_set:Nn \l_tmpa_box { $ \bBigg@ 5 \g_@@_left_delim_tl $ }
1300     \dim_set:Nn \l_@@_left_delim_dim { \box_wd:N \l_tmpa_box }
1301     \hbox_set:Nn \l_tmpa_box { $ \bBigg@ 5 \g_@@_right_delim_tl $ }
1302     \dim_set:Nn \l_@@_right_delim_dim { \box_wd:N \l_tmpa_box }
1303 }
```

Here is the beginning of the box which will contain the array. The `\hbox_set_end:` corresponding to this `\hbox_set:Nw` will be in the second part of the environment (and the closing `\c_math_toggle_token` also).

```
1304     \hbox_set:Nw \l_@@_the_array_box
1305     \skip_horizontal:N \l_@@_left_margin_dim
1306     \skip_horizontal:N \l_@@_extra_left_margin_dim
1307     \c_math_toggle_token
1308     \bool_if:NTF \l_@@_light_syntax_bool
1309     {
1310         \use:c { @@-light-syntax } }
1311     {
1312         \use:c { @@-normal-syntax } }
```

The following command `\@@_pre_array_i:w` will be used when the keyword `\CodeBefore` is present at the beginning of the environment.

```
1312 \cs_new_protected:Npn \@@_pre_array_i:w #1 \Body
1313 {
1314     \tl_put_right:Nn \l_@@_code_before_tl { #1 }
1315     \bool_set_true:N \l_@@_code_before_bool
```

We go on with `\@@_pre_array:` which will (among other) execute the `\CodeBefore` (specified in the key `code-before` or after the keyword `\CodeBefore`). By definition, the `\CodeBefore` must be executed before the body of the array...

```
1316     \@@_pre_array:
1317 }
```

The `\CodeBefore`

The following command will be executed if the `\CodeBefore` has to be actually executed.

```
1318 \cs_new_protected:Npn \@@_pre_code_before:
1319 {
```

First, we give values to the LaTeX counters `iRow` and `jCol`. We remind that, in the `code-before` (and in the `\CodeAfter`) they represent the numbers of rows and columns of the array (without the potential last row and last column). The value of `\g_@@_row_total_int` is the number of the last row (with potentially a last exterior row) and `\g_@@_col_total_int` is the number of the last column (with potentially a last exterior column).

```
1320     \int_set:Nn \c@iRow { \seq_item:Nn \c_@@_size_seq 2 }
```

```

1321 \int_set:Nn \c@jCol { \seq_item:Nn \c_@@_size_seq 5 }
1322 \int_set_eq:NN \g_@@_row_total_int { \seq_item:Nn \c_@@_size_seq 3 }
1323 \int_set_eq:NN \g_@@_col_total_int { \seq_item:Nn \c_@@_size_seq 6 }

```

Now, we will create all the `col` nodes and `row` nodes with the informations written in the `aux` file. You use the technique described in the page 1229 of `pgfmanual.pdf`, version 3.1.4b.

```

1324 \pgfsys@markposition { \c@env: - position }
1325 \pgfsys@getposition { \c@env: - position } \c@picture_position:
1326 \pgfpicture
1327 \pgf@relevantforpicturesizefalse

```

First, the recreation of the `row` nodes.

```

1328 \int_step_inline:nnn \l_@@_first_row_int { \g_@@_row_total_int + 1 }
1329 {
1330     \pgfsys@getposition { \c@env: - row - ##1 } \c@node_position:
1331     \pgfcoordinate { \c@env: - row - ##1 }
1332         { \pgfpointdiff \c@picture_position: \c@node_position: }
1333 }

```

Now, the recreation of the `col` nodes.

```

1334 \int_step_inline:nnn \l_@@_first_col_int { \g_@@_col_total_int + 1 }
1335 {
1336     \pgfsys@getposition { \c@env: - col - ##1 } \c@node_position:
1337     \pgfcoordinate { \c@env: - col - ##1 }
1338         { \pgfpointdiff \c@picture_position: \c@node_position: }
1339 }

```

Now, you recreate the diagonal nodes by using the `row` nodes and the `col` nodes.

```
1340 \c@create_diag_nodes:
```

Now, the creation of the cell nodes ($i-j$), and, maybe also the “medium nodes” and the “large nodes”.

```

1341 \bool_if:NT \g_@@_recreate_cell_nodes_bool \c@recreate_cell_nodes:
1342 \endpgfpicture
1343 \bool_if:NT \c_@@_tikz_loaded_bool
1344 {
1345     \tikzset
1346     {
1347         every~picture / .style =
1348             { overlay , name~prefix = \c@env: - }
1349     }
1350 }
1351 \cs_set_eq:NN \cellcolor \c@cellcolor
1352 \cs_set_eq:NN \rectanglecolor \c@rectanglecolor
1353 \cs_set_eq:NN \roundedrectanglecolor \c@roundedrectanglecolor
1354 \cs_set_eq:NN \rowcolor \c@rowcolor
1355 \cs_set_eq:NN \rowcolors \c@rowcolors
1356 \cs_set_eq:NN \arraycolor \c@arraycolor
1357 \cs_set_eq:NN \columncolor \c@columncolor
1358 \cs_set_eq:NN \chessboardcolors \c@chessboardcolors
1359 \cs_set_eq:NN \SubMatrix \c@SubMatrix_in_code_before
1360 }

```

```

1361 \cs_new_protected:Npn \c@exec_code_before:
1362 {
1363     \seq_gclear_new:N \g_@@_colors_seq
1364     \bool_gset_false:N \g_@@_recreate_cell_nodes_bool
1365     \group_begin:

```

We compose the `code-before` in math mode in order to nullify the spaces put by the user between instructions in the `code-before`.

```
1366 \bool_if:NT \l_@@_NiceTabular_bool \c_math_toggle_token
```

Here is the `\CodeBefore`. The construction is a bit complicated because `\l_@@_code_before_tl` may begin with keys between square brackets. Moreover, after the analyze of those keys, we sometimes have to decide to do *not* execute the rest of `\l_@@_code_before_tl` (when it is asked for the creation of cell nodes in the `\CodeBefore`). That's why we begin with a `\q_stop`: it will be used to discard the rest of `\l_@@_code_before_tl`.

```
1367 \exp_last_unbraced:NV \@@_CodeBefore_keys: \l_@@_code_before_tl \q_stop
```

Now, all the cells which are specified to be colored by instructions in the `\CodeBefore` will actually be colored. It's a two-stages mechanism because we want to draw all the cells with the same color at the same time to absolutely avoid thin white lines in some PDF viewers.

```
1368 \@@_actually_color:
1369 \bool_if:NT \l_@@_NiceTabular_bool \c_math_toggle_token
1370 \group_end:
1371 \bool_if:NT \g_@@_recreate_cell_nodes_bool
1372 { \tl_put_left:Nn \@@_node_for_cell: \@@_patch_node_for_cell: }
1373 }

1374 \keys_define:nn { NiceMatrix / CodeBefore }
1375 {
1376   create-cell-nodes .bool_gset:N = \g_@@_recreate_cell_nodes_bool ,
1377   create-cell-nodes .default:n = true ,
1378   sub-matrix .code:n = \keys_set:nn { NiceMatrix / sub-matrix } { #1 } ,
1379   sub-matrix .value_required:n = true ,
1380   delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
1381   delimiters / color .value_required:n = true ,
1382   unknown .code:n = \@@_error:n { Unknown-key-for~CodeAfter }
1383 }
1384 \NewDocumentCommand \@@_CodeBefore_keys: { O { } }
1385 {
1386   \keys_set:nn { NiceMatrix / CodeBefore } { #1 }
1387   \@@_CodeBefore:w
1388 }
```

We have extracted the options of the keyword `\CodeBefore` in order to see whether the key `create-cell-nodes` has been used. Now, you can execute the rest of the `\CodeAfter`, excepted, of course, if we are in the first compilation.

```
1389 \cs_new_protected:Npn \@@_CodeBefore:w #1 \q_stop
1390 {
1391   \bool_if:NT \g_@@_aux_found_bool
1392   {
1393     \@@_pre_code_before:
1394     #1
1395   }
1396 }
```

By default, if the user uses the `\CodeBefore`, only the `col` nodes, `row` nodes and `diag` nodes are available in that `\CodeBefore`. With the key `create-cell-nodes`, the cell nodes, that is to say the nodes of the form $(i-j)$ (but not the extra nodes) are also available because those nodes also are recreated and that recreation is done by the following command.

```
1397 \cs_new_protected:Npn \@@_recreate_cell_nodes:
1398 {
1399   \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
1400   {
1401     \pgfsys@getposition { \@@_env: - ##1 - base } \@@_node_position:
1402     \pgfcoordinate { \@@_env: - row - ##1 - base }
1403     { \pgfpointdiff \@@_picture_position: \@@_node_position: }
1404   \int_step_inline:nnn \l_@@_first_col_int \g_@@_col_total_int
1405   {
1406     \cs_if_exist:cT
1407     { \pgf @ sys @ pdf @ mark @ pos @ \@@_env: - ##1 - ####1 - NW }
```

```

1408 {
1409     \pgfsys@getposition
1410     { \@@_env: - ##1 - #####1 - NW }
1411     \@@_node_position:
1412     \pgfsys@getposition
1413     { \@@_env: - ##1 - #####1 - SE }
1414     \@@_node_position_i:
1415     \@@_pgf_rect_node:nnn
1416     { \@@_env: - ##1 - #####1 }
1417     { \pgfpointdiff \@@_picture_position: \@@_node_position: }
1418     { \pgfpointdiff \@@_picture_position: \@@_node_position_i: }
1419 }
1420 }
1421 }
1422 \@@_create_extra_nodes:
1423 }

```

The environment {NiceArrayWithDelims}

```

1424 \NewDocumentEnvironment { NiceArrayWithDelims }
1425   { m m O { } m ! O { } t \CodeBefore }
1426   {
1427     \@@_provide_pgfsyspdfmark:
1428     \bool_if:NT \c_@@_footnote_bool \savenotes

```

The aim of the following `\bgroup` (the corresponding `\egroup` is, of course, at the end of the environment) is to be able to put an exposant to a matrix in a mathematical formula.

```

1429 \bgroup
1430   \tl_gset:Nn \g_@@_left_delim_tl { #1 }
1431   \tl_gset:Nn \g_@@_right_delim_tl { #2 }
1432   \tl_gset:Nn \g_@@_preamble_tl { #4 }

1433   \int_gzero:N \g_@@_block_box_int
1434   \dim_zero:N \g_@@_width_last_col_dim
1435   \dim_zero:N \g_@@_width_first_col_dim
1436   \bool_gset_false:N \g_@@_row_of_col_done_bool
1437   \str_if_empty:NT \g_@@_name_env_str
1438   { \str_gset:Nn \g_@@_name_env_str { NiceArrayWithDelims } }

```

The following line will be deleted when we will consider that only versions of `siunitx` after v3.0 are compatible with `nicematrix`.

```

1439 \@@_adapt_S_column:
1440 \bool_if:NTF \l_@@_NiceTabular_bool
1441   \mode_leave_vertical:
1442   \@@_test_if_math_mode:
1443   \bool_if:NT \l_@@_in_env_bool { \@@_fatal:n { Yet-in-env } }
1444   \bool_set_true:N \l_@@_in_env_bool

```

The command `\CT@arc@` contains the instruction of color for the rules of the array⁵⁶. This command is used by `\CT@arc@` but we use it also for compatibility with `colortbl`. But we want also to be able to use color for the rules of the array when `colortbl` is *not* loaded. That's why we do the following instruction which is in the patch of the beginning of arrays done by `colortbl`. Of course, we restore the value of `\CT@arc@` at the end of our environment.

```

1445 \cs_gset_eq:NN \@@_old_CT@arc@ \CT@arc@

```

We deactivate Tikz externalization because we will use PGF pictures with the options `overlay` and `remember picture` (or equivalent forms). We deactivate with `\tikzexternaldisable` and not with `\tikzset{external/export=false}` which is *not* equivalent.

⁵⁶e.g. `\color[rgb]{0.5,0.5,0}`

```

1446 \cs_if_exist:NT \tikz@library@external@loaded
1447 {
1448     \tikzexternaldisable
1449     \cs_if_exist:NT \ifstandalone
1450     { \tikzset { external / optimize = false } }
1451 }

```

We increment the counter `\g_@@_env_int` which counts the environments of the package.

```

1452 \int_gincr:N \g_@@_env_int
1453 \bool_if:NF \l_@@_block_auto_columns_width_bool
1454 { \dim_gzero_new:N \g_@@_max_cell_width_dim }

```

The sequence `\g_@@_blocks_seq` will contain the characteristics of the blocks (specified by `\Block`) of the array. The sequence `\g_@@_pos_of_blocks_seq` will contain only the position of the blocks. Of course, this is redundant but it's for efficiency.

```

1455 \seq_gclear:N \g_@@_blocks_seq
1456 \seq_gclear:N \g_@@_pos_of_blocks_seq

```

In fact, the sequence `\g_@@_pos_of_blocks_seq` will also contain the positions of the cells with a `\diagbox`.

```

1457 \seq_gclear:N \g_@@_pos_of_stroken_blocks_seq
1458 \seq_gclear:N \g_@@_pos_of_xdots_seq
1459 \tl_gclear_new:N \g_@@_code_before_tl

```

We load all the informations written in the `.aux` file during previous compilations corresponding to the current environment.

```

1460 \bool_gset_false:N \g_@@_aux_found_bool
1461 \tl_if_exist:cT { c_@@_ \int_use:N \g_@@_env_int _ tl }
1462 {
1463     \bool_gset_true:N \g_@@_aux_found_bool
1464     \use:c { c_@@_ \int_use:N \g_@@_env_int _ tl }
1465 }

```

Now, we prepare the token list for the instructions that we will have to write on the `.aux` file at the end of the environment.

```

1466 \tl_gclear:N \g_@@_aux_tl
1467 \tl_if_empty:NF \g_@@_code_before_tl
1468 {
1469     \bool_set_true:N \l_@@_code_before_bool
1470     \tl_put_right:NV \l_@@_code_before_tl \g_@@_code_before_tl
1471 }

```

The set of keys is not exactly the same for `{NiceArray}` and for the variants of `{NiceArray}` (`{pNiceArray}`, `{bNiceArray}`, etc.) because, for `{NiceArray}`, we have the options `t`, `c`, `b` and `baseline`.

```

1472 \bool_if:NTF \l_@@_NiceArray_bool
1473 { \keys_set:nn { NiceMatrix / NiceArray } }
1474 { \keys_set:nn { NiceMatrix / pNiceArray } }
1475 { #3 , #5 }

1476 \tl_if_empty:NF \l_@@_rules_color_tl
1477 { \exp_after:wN \@@_set_CTabarc@: \l_@@_rules_color_tl \q_stop }
1478 % \bigskip

```

The argument `#6` is the last argument of `{NiceArrayWithDelims}`. With that argument of type “`t \CodeBefore`”, we test whether there is the keyword `\CodeBefore` at the beginning of the environment. If that keyword is present, we have now to extract all the content between that keyword `\CodeBefore` and the (other) keyword `\Body`. It’s the job that will do the command `\@@_pre_array_i:w`. After that job, the command `\@@_pre_array_i:w` will go on with `\@@_pre_array:`

```

1479 \IfBooleanTF { #6 } \@@_pre_array_i:w \@@_pre_array:
1480 }
1481 {
1482 \bool_if:NTF \l_@@_light_syntax_bool
1483 { \use:c { end @@-light-syntax } }

```

```

1484 { \use:c { end @@-normal-syntax } }
1485 \c_math_toggle_token
1486 \skip_horizontal:N \l_@@_right_margin_dim
1487 \skip_horizontal:N \l_@@_extra_right_margin_dim
1488 \hbox_set_end:

```

End of the construction of the array (in the box `\l_@@_the_array_box`).

If the user has used the key `last-row` with a value, we control that the given value is correct (since we have just constructed the array, we know the real number of rows of the array).

```

1489 \int_compare:nNnT \l_@@_last_row_int > { -2 }
1490 {
1491     \bool_if:nF \l_@@_last_row_without_value_bool
1492     {
1493         \int_compare:nNnF \l_@@_last_row_int = \c@iRow
1494         {
1495             \@@_error:n { Wrong~last~row }
1496             \int_gset_eq:NN \l_@@_last_row_int \c@iRow
1497         }
1498     }
1499 }

```

Now, the definition of `\c@jCol` and `\g_@@_col_total_int` change: `\c@jCol` will be the number of columns without the “last column”; `\g_@@_col_total_int` will be the number of columns with this “last column”.⁵⁷

```

1500 \int_gset_eq:NN \c@jCol \g_@@_col_total_int
1501 \bool_if:nTF \g_@@_last_col_found_bool
1502 {
1503     \int_gdecr:N \c@jCol
1504     {
1505         \int_compare:nNnT \l_@@_last_col_int > { -1 }
1506         { \@@_error:n { last~col~not~used } }
1507     }
1508 }

```

We fix also the value of `\c@iRow` and `\g_@@_row_total_int` with the same principle.

```

1509 \int_gset_eq:NN \g_@@_row_total_int \c@iRow
1510 \int_compare:nNnT \l_@@_last_row_int > { -1 } { \int_gdecr:N \c@iRow }

```

Now, we begin the real construction in the output flow of TeX. First, we take into account a potential “first column” (we remind that this “first column” has been constructed in an overlapping position and that we have computed its width in `\g_@@_width_first_col_dim`: see p. 112).

```

1509 \int_compare:nNnT \l_@@_first_col_int = 0
1510 {
1511     \skip_horizontal:N \col@sep
1512     \skip_horizontal:N \g_@@_width_first_col_dim
1513 }

```

The construction of the real box is different when `\l_@@_NiceArray_bool` is true (`{NiceArray}` or `{NiceTabular}`) and in the other environments because, in `{NiceArray}` or `{NiceTabular}`, we have no delimiter to put (but we have tabular notes to put). We begin with this case.

Remark that, in all cases, `@@_use_arraybox_with_notes_c`: is used.

```

1514 \bool_if:NTF \l_@@_NiceArray_bool
1515 {
1516     \str_case:VnF \l_@@_baseline_tl
1517     {
1518         b \@@_use_arraybox_with_notes_b:
1519         c \@@_use_arraybox_with_notes_c:
1520     }
1521     \@@_use_arraybox_with_notes:
1522 }

```

Now, in the case of an environment `{pNiceArray}`, `{bNiceArray}`, etc. We compute `\l_tmpa_dim` which is the total height of the “first row” above the array (when the key `first-row` is used).

⁵⁷We remind that the potential “first column” (exterior) has the number 0.

```

1523     {
1524         \int_compare:nNnTF \l_@@_first_row_int = 0
1525         {
1526             \dim_set_eq:NN \l_tmpa_dim \g_@@_dp_row_zero_dim
1527             \dim_add:Nn \l_tmpa_dim \g_@@_ht_row_zero_dim
1528         }
1529         { \dim_zero:N \l_tmpa_dim }

```

We compute \l_{tmpb_dim} which is the total height of the “last row” below the array (when the key `last-row` is used). A value of -2 for $\l_@@_last_row_int$ means that there is no “last row”.⁵⁸

```

1530         \int_compare:nNnTF \l_@@_last_row_int > { -2 }
1531         {
1532             \dim_set_eq:NN \l_tmpb_dim \g_@@_ht_last_row_dim
1533             \dim_add:Nn \l_tmpb_dim \g_@@_dp_last_row_dim
1534         }
1535         { \dim_zero:N \l_tmpb_dim }

1536 \hbox_set:Nn \l_tmpa_box
1537 {
1538     \c_math_toggle_token
1539     \tl_if_empty:NF \l_@@_delimiters_color_tl
1540         { \color { \l_@@_delimiters_color_tl } }
1541     \exp_after:wN \left \g_@@_left_delim_tl
1542     \vcenter
1543     {

```

We take into account the “first row” (we have previously computed its total height in \l_{tmpa_dim}). The `\hbox:n` (or `\hbox`) is necessary here.

```

1544     \skip_vertical:N -\l_tmpa_dim
1545     \hbox
1546     {
1547         \bool_if:NTF \l_@@_NiceTabular_bool
1548             { \skip_horizontal:N -\tabcolsep }
1549             { \skip_horizontal:N -\arraycolsep }
1550         \@@_use_arraybox_with_notes_c:
1551         \bool_if:NTF \l_@@_NiceTabular_bool
1552             { \skip_horizontal:N -\tabcolsep }
1553             { \skip_horizontal:N -\arraycolsep }
1554     }

```

We take into account the “last row” (we have previously computed its total height in \l_{tmpb_dim}).

```

1555     \skip_vertical:N -\l_tmpb_dim
1556 }

```

Curiously, we have to put again the following specification of color. Otherwise, with XeLaTeX (and not with the other engines), the closing delimiter is not colored.

```

1557     \tl_if_empty:NF \l_@@_delimiters_color_tl
1558         { \color { \l_@@_delimiters_color_tl } }
1559         \exp_after:wN \right \g_@@_right_delim_tl
1560         \c_math_toggle_token
1561     }

```

Now, the box \l_{tmpa_box} is created with the correct delimiters.

We will put the box in the TeX flow. However, we have a small work to do when the option `delimiters/max-width` is used.

```

1562     \bool_if:NTF \l_@@_delimiters_max_width_bool
1563     {
1564         \@@_put_box_in_flow_bis:nn
1565             \g_@@_left_delim_tl \g_@@_right_delim_tl
1566     }
1567     \@@_put_box_in_flow:
1568 }

```

⁵⁸A value of -1 for $\l_@@_last_row_int$ means that there is a “last row” but the user have not set the value with the option `last row` (and we are in the first compilation).

We take into account a potential “last column” (this “last column” has been constructed in an overlapping position and we have computed its width in `\g_@@_width_last_col_dim`: see p. 113).

```

1569 \bool_if:NT \g_@@_last_col_found_bool
1570 {
1571     \skip_horizontal:N \g_@@_width_last_col_dim
1572     \skip_horizontal:N \col@sep
1573 }
1574 \bool_if:NF \l_@@_Matrix_bool
1575 {
1576     \int_compare:nNnT \c@jCol < \g_@@_static_num_of_col_int
1577     { \@@_error:n { columns-not-used } }
1578 }
1579 \group_begin:
1580 \globaldefs = 1
1581 \@@_msg_redirect_name:nn { columns-not-used } { error }
1582 \group_end:
1583 \@@_after_array:
1584 \egroup

```

The aim of the following `\egroup` (the corresponding `\bgroup` is, of course, at the beginning of the environment) is to be able to put an exposant to a matrix in a mathematical formula.

```
1584 \egroup
```

We want to write on the `aux` file all the informations corresponding to the current environment.

```

1585 \iow_now:Nn \mainaux { \ExplSyntaxOn }
1586 \iow_now:Nx \mainaux
1587 {
1588     \tl_gset:cn { c_@@_int_use:N \g_@@_env_int _ tl }
1589     \iow_newline: { \iow_newline: \exp_not:V \g_@@_aux_tl }
1590 }
1591 \iow_now:Nn \mainaux { \ExplSyntaxOff }

1592 \bool_if:NT \c_@@_footnote_bool \endsavenotes
1593 }

```

This is the end of the environment `{NiceArrayWithDelims}`.

We construct the preamble of the array

The transformation of the preamble is an operation in several steps.

The preamble given by the final user is in `\g_@@_preamble_t1` and the modified version will be stored in `\g_@@_preamble_t1` also.

```

1594 \cs_new_protected:Npn \@@_construct_preamble:
1595 {

```

First, we will do an “expansion” of the preamble with the tools of the package `array` itself. This “expansion” will expand all the constructions with `*` and with all column types (defined by the user or by various packages using `\newcolumntype`).

Since we use the tools of `array` to do this expansion, we will have a programmation which is not in the style of `expl3`.

We redefine the column types `w` and `W`. We use `\@@_newcolumntype` instead of `\newcolumntype` because we don’t want warnings for column types already defined. These redefinitions are in fact *protections* of the letters `w` and `W`. We don’t want these columns type expanded because we will do the patch ourselves after. We want to be able the standard column types `w` and `W` in potential `{tabular}` of `array` in some cells of our array. That’s why we do those redefinitions in a TeX group.

```
1596 \group_begin:
```

If we are in an environment without explicit preamble, we have nothing to do (excepted the treatment on both sides of the preamble which will be done at the end).

```
1597 \bool_if:NF \l_@@_Matrix_bool
1598 {
1599   \@@_newcolumntype w [ 2 ] { \@@_w: { ##1 } { ##2 } }
1600   \@@_newcolumntype W [ 2 ] { \@@_W: { ##1 } { ##2 } }
```

First, we have to store our preamble in the token register `\@temptokena` (those “token registers” are *not* supported by `expl3`).

```
1601 \exp_args:NV \@temptokena \g_@@_preamble_t1
```

Initialisation of a flag used by `array` to detect the end of the expansion.

```
1602 \@tempswattrue
```

The following line actually does the expansion (it’s has been copied from `array.sty`). The expanded version is still in `\@temptokena`.

```
1603 \@whilesw \if@tempswa \fi { \@tempswafalse \the \NC@list }
```

Now, we have to “patch” that preamble by transforming some columns. We will insert in the TeX flow the preamble in its actual form (that is to say after the “expansion”) following by a marker `\q_stop` and we will consume these tokens constructing the (new form of the) preamble in `\g_@@_preamble_t1`. This is done recursively with the command `\@@_patch_preamble:n`. In the same time, we will count the columns with the counter `\c@jCol`.

```
1604 \int_gzero:N \c@jCol
1605 \tl_gclear:N \g_@@_preamble_t1
```

`\g_tmpb_bool` will be raised if you have a `|` at the end of the preamble.

```
1606 \bool_gset_false:N \g_tmpb_bool
1607 \tl_if_eq:NnTF \l_@@_vlines_clist { all }
1608 {
1609   \tl_gset:Nn \g_@@_preamble_t1
1610   { ! { \skip_horizontal:N \arrayrulewidth } }
1611 }
1612 {
1613   \clist_if_in:NnT \l_@@_vlines_clist 1
1614   {
1615     \tl_gset:Nn \g_@@_preamble_t1
1616     { ! { \skip_horizontal:N \arrayrulewidth } }
1617   }
1618 }
```

The sequence `\g_@@_cols_vlsim_seq` will contain the numbers of the columns where you will have to draw vertical lines in the potential sub-matrices (hence the name `vlism`).

```
1619 \seq_clear:N \g_@@_cols_vlism_seq
```

The counter `\l_tmpa_int` will count the number of consecutive occurrences of the symbol `|`.

```
1620 \int_zero:N \l_tmpa_int
```

Now, we actually patch the preamble (and it is constructed in `\g_@@_preamble_t1`).

```
1621 \exp_after:wN \@@_patch_preamble:n \the \@temptokena \q_stop
1622 \int_gset_eq:NN \g_@@_static_num_of_col_int \c@jCol
1623 }
```

Now, we replace `\columncolor` by `\@@_columncolor_preamble`.

```
1624 \bool_if:NT \l_@@_colortbl_like_bool
1625 {
1626   \regex_replace_all:NnN
1627   \c_@@_columncolor_regex
1628   { \c { @@_columncolor_preamble } }
1629   \g_@@_preamble_t1
1630 }
```

Now, we can close the TeX group which was opened for the redefinition of the columns of type `w` and `W`.

```
1631 \group_end:
```

If there was delimiters at the beginning or at the end of the preamble, the environment `{NiceArray}` is transformed into an environment `{xNiceMatrix}`.

```
1632 \bool_lazy_or:nnT
1633   { ! \str_if_eq_p:Vn \g_@@_left_delim_tl { . } }
1634   { ! \str_if_eq_p:Vn \g_@@_right_delim_tl { . } }
1635   { \bool_set_false:N \l_@@_NiceArray_bool }
```

We want to remind whether there is a specifier `|` at the end of the preamble.

```
1636 \bool_if:NT \g_tmpb_bool { \bool_set_true:N \l_@@_bar_at_end_of_pream_bool }
```

We complete the preamble with the potential “exterior columns”.

```
1637 \int_compare:nNnTF \l_@@_first_col_int = 0
1638   { \tl_gput_left:NV \g_@@_preamble_tl \c_@@_preamble_first_col_tl }
1639   {
1640     \bool_lazy_all:nT
1641     {
1642       \l_@@_NiceArray_bool
1643       { \bool_not_p:n \l_@@_NiceTabular_bool }
1644       { \tl_if_empty_p:N \l_@@_vlines_clist }
1645       { \bool_not_p:n \l_@@_exterior_arraycolsep_bool }
1646     }
1647     { \tl_gput_left:Nn \g_@@_preamble_tl { @ { } } }
1648   }
1649 \int_compare:nNnTF \l_@@_last_col_int > { -1 }
1650   { \tl_gput_right:NV \g_@@_preamble_tl \c_@@_preamble_last_col_tl }
1651   {
1652     \bool_lazy_all:nT
1653     {
1654       \l_@@_NiceArray_bool
1655       { \bool_not_p:n \l_@@_NiceTabular_bool }
1656       { \tl_if_empty_p:N \l_@@_vlines_clist }
1657       { \bool_not_p:n \l_@@_exterior_arraycolsep_bool }
1658     }
1659     { \tl_gput_right:Nn \g_@@_preamble_tl { @ { } } }
1660   }
```

We add a last column to raise a good error message when the user put more columns than allowed by its preamble. However, for technical reasons, it's not possible to do that in `{NiceTabular*}` (`\l_@@_tabular_width_dim=0pt`).

```
1661 \dim_compare:nNnT \l_@@_tabular_width_dim = \c_zero_dim
1662   {
1663     \tl_gput_right:Nn \g_@@_preamble_tl
1664     { > { \@@_error_too_much_cols: } 1 }
1665   }
1666 }

1667 \cs_new_protected:Npn \@@_patch_preamble:n #1
1668   {
1669     \str_case:nnF { #1 }
1670     {
1671       c { \@@_patch_preamble_i:n #1 }
1672       l { \@@_patch_preamble_i:n #1 }
1673       r { \@@_patch_preamble_i:n #1 }
1674       > { \@@_patch_preamble_ii:nn #1 }
1675       ! { \@@_patch_preamble_ii:nn #1 }
1676       @ { \@@_patch_preamble_ii:nn #1 }
1677       | { \@@_patch_preamble_jiii:n #1 }
1678       p { \@@_patch_preamble_iv:nnn t #1 }
1679       m { \@@_patch_preamble_iv:nnn c #1 }
1680       b { \@@_patch_preamble_iv:nnn b #1 }
1681       \@@_w: { \@@_patch_preamble_v:nnnn { } } #1 }
1682       \@@_W: { \@@_patch_preamble_v:nnnn { \cs_set_eq:NN \hss \hfil } #1 }
```

```

1683     \@@_true_c: { \@@_patch_preamble_vi:n #1 }
1684     ( { \@@_patch_preamble_vii:nn #1 }
1685     [ { \@@_patch_preamble_vii:nn #1 }
1686     \{ { \@@_patch_preamble_vii:nn #1 }
1687     ) { \@@_patch_preamble_viii:nn #1 }
1688     ] { \@@_patch_preamble_viii:nn #1 }
1689     \} { \@@_patch_preamble_viii:nn #1 }
1690     C { \@@_error:nn { old~column~type } #1 }
1691     L { \@@_error:nn { old~column~type } #1 }
1692     R { \@@_error:nn { old~column~type } #1 }
1693     \q_stop { }
1694   }
1695   {
1696     \str_if_eq:VnTF \l_@@_letter_for_dotted_lines_str { #1 }
1697     { \@@_patch_preamble_xi:n #1 }
1698     {
1699       \str_if_eq:VnTF \l_@@_letter_vlism_tl { #1 }
1700       {
1701         \seq_gput_right:Nx \g_@@_cols_vlism_seq
1702           { \int_eval:n { \c@jCol + 1 } }
1703         \tl_gput_right:Nx \g_@@_preamble_tl
1704           { \exp_not:N ! { \skip_horizontal:N \arrayrulewidth } }
1705         \@@_patch_preamble:n
1706       }
1707       {
1708         \bool_lazy_and:nnTF
1709           { \str_if_eq_p:nn { : } { #1 } }
1710           \c_@@_arydshln_loaded_bool
1711           {
1712             \tl_gput_right:Nn \g_@@_preamble_tl { : }
1713             \@@_patch_preamble:n
1714           }
1715           { \@@_fatal:nn { unknown~column~type } { #1 } }
1716       }
1717     }
1718   }
1719 }
```

For c, l and r

```

1720 \cs_new_protected:Npn \@@_patch_preamble_i:n #1
1721   {
1722     \tl_gput_right:Nn \g_@@_preamble_tl
1723     {
1724       > { \@@_Cell: \tl_set:Nn \l_@@_cell_type_tl { #1 } }
1725       #1
1726       < \@@_end_Cell:
1727     }
1728 }
```

We increment the counter of columns and then we test for the presence of a <.

```

1728   \int_gincr:N \c@jCol
1729   \@@_patch_preamble_x:n
1730 }
```

For >, ! and @

```

1731 \cs_new_protected:Npn \@@_patch_preamble_ii:nn #1 #2
1732   {
1733     \tl_gput_right:Nn \g_@@_preamble_tl { #1 { #2 } }
1734     \@@_patch_preamble:n
1735   }
```

For |

```

1736 \cs_new_protected:Npn \@@_patch_preamble_iii:n #1
1737   {
```

```

\l_tma_int is the number of successive occurrences of |
1738   \int_incr:N \l_tma_int
1739   \@@_patch_preamble_iii_i:n
1740 }
1741 \cs_new_protected:Npn \@@_patch_preamble_iii_i:n #1
1742 {
1743   \str_if_eq:nnTF { #1 } |
1744   { \@@_patch_preamble_iii:n | }
1745   {
1746     \tl_gput_right:Nx \g_@@_preamble_tl
1747     {
1748       \exp_not:N !
1749     }
1750     \skip_horizontal:n
1751     {
1752       \dim_eval:n
1753       {
1754         \arrayrulewidth * \l_tma_int
1755         + \doublerulesep * ( \l_tma_int - 1 )
1756       }
1757     }
1758   }
1759 }
1760 \tl_gput_right:Nx \g_@@_internal_code_after_tl
1761   { \@@_vline:nn { \@@_succ:n \c@jCol } { \int_use:N \l_tma_int } }
1762 \int_zero:N \l_tma_int
1763 \str_if_eq:nnT { #1 } { \q_stop }
1764   { \bool_gset_true:N \g_tmpb_bool }
1765 \@@_patch_preamble:n #1
1766 }
1767 }
1768 \bool_new:N \l_@@_bar_at_end_of_pream_bool

```

For p, m and b

```

1769 \cs_new_protected:Npn \@@_patch_preamble_iv:nnn #1 #2 #3
1770 {
1771   \tl_gput_right:Nn \g_@@_preamble_tl
1772   {
1773     > {
1774       \@@_Cell:
1775       \begin{minipage} [ #1 ] { \dim_eval:n { #3 } }
1776       \mode_leave_vertical:
1777       \arraybackslash
1778       \vrule height \box_ht:N \carstrutbox depth 0 pt width 0 pt
1779     }
1780     c
1781     < {
1782       \vrule height 0 pt depth \box_dp:N \carstrutbox width 0 pt
1783       \end{minipage}
1784       \@@_end_Cell:
1785     }
1786   }

```

We increment the counter of columns, and then we test for the presence of a <.

```

1787   \int_gincr:N \c@jCol
1788   \@@_patch_preamble_x:n
1789 }

```

For w and W

```

1790 \cs_new_protected:Npn \@@_patch_preamble_v:nnnn #1 #2 #3 #4
1791 {
1792   \tl_gput_right:Nn \g_@@_preamble_tl

```

```

1793   {
1794     > {
1795       \hbox_set:Nw \l_@@_cell_box
1796       \@@_Cell:
1797       \tl_set:Nn \l_@@_cell_type_tl { #3 }
1798     }
1799     c
1800     < {
1801       \@@_end_Cell:
1802       #1
1803       \hbox_set_end:
1804       \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
1805       \@@_adjust_size_box:
1806       \makebox [ #4 ] [ #3 ] { \box_use_drop:N \l_@@_cell_box }
1807     }
1808   }

```

We increment the counter of columns and then we test for the presence of a <.

```

1809   \int_gincr:N \c@jCol
1810   \@@_patch_preamble_x:n
1811 }

```

For \@@_true_c: which will appear in our redefinition of the columns of type S (of siunitx).

```

1812 \cs_new_protected:Npn \@@_patch_preamble_vi:n #1
1813 {
1814   \tl_gput_right:Nn \g_@@_preamble_tl { c }

```

We increment the counter of columns and then we test for the presence of a <.

```

1815   \int_gincr:N \c@jCol
1816   \@@_patch_preamble_x:n
1817 }

```

For (, [, and \{.

```

1818 \cs_new_protected:Npn \@@_patch_preamble_vii:nn #1 #2
1819 {
1820   \bool_if:NT \l_@@_small_bool { \@@_fatal:n { Delimiter-with-small } }

```

If we are before the column 1 and not in {NiceArray}, we reserve space for the left delimiter.

```

1821 \int_compare:nNnTF \c@jCol = \c_zero_int
1822 {
1823   \str_if_eq:VnTF \g_@@_left_delim_tl { . }
1824   {

```

In that case, in fact, the first letter of the preamble must be considered as the left delimiter of the array.

```

1825   \tl_gset:Nn \g_@@_left_delim_tl { #1 }
1826   \tl_gset:Nn \g_@@_right_delim_tl { . }
1827   \@@_patch_preamble:n #2
1828 }
1829 {
1830   \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } }
1831   \@@_patch_preamble_vii_i:nn { #1 } { #2 }
1832 }
1833 }
1834 { \@@_patch_preamble_vii_i:nn { #1 } { #2 } }

1835 }

1836 \cs_new_protected:Npn \@@_patch_preamble_vii_i:nn #1 #2
1837 {
1838   \tl_gput_right:Nx \g_@@_internal_code_after_tl
1839   { \@@_delimiter:nnn #1 { \@@_succ:n \c@jCol } \c_true_bool }
1840   \tl_if_in:nnTF { ( [ \{ ) ] \} } { #2 }
1841   {
1842     \@@_error:nn { delimiter-after-opening } { #2 }
1843     \@@_patch_preamble:n

```

```

1844     }
1845     { \@@_patch_preamble:n #2 }
1846 }

```

For),] and \}. We have two arguments for the following command because we directly read the following letter in the preamble (we have to see whether we have a opening delimiter following and we also have to see whether we are at the end of the preamble because, in that case, our letter must be considered as the right delimiter of the environment if the environment is {NiceArray}).

```

1847 \cs_new_protected:Npn \@@_patch_preamble_viii:nn #1 #2
1848 {
1849     \bool_if:NT \l_@@_small_bool { \@@_fatal:n { Delimiter-with-small } }
1850     \tl_if_in:nnTF { ) } [ \} ] { #2 }
1851     { \@@_patch_preamble_viii_i:nnn #1 #2 }
1852     {
1853         \tl_if_eq:nnTF { \q_stop } { #2 }
1854         {
1855             \str_if_eq:VnTF \g_@@_right_delim_tl { . }
1856             { \tl_gset:Nn \g_@@_right_delim_tl { #1 } }
1857             {
1858                 \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } }
1859                 \tl_gput_right:Nx \g_@@_internal_code_after_tl
1860                 { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } \c_false_bool }
1861                 \@@_patch_preamble:n #2
1862             }
1863         }
1864         {
1865             \tl_if_in:nnT { ( [ \{ } { #2 }
1866             { \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } } }
1867             \tl_gput_right:Nx \g_@@_internal_code_after_tl
1868             { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } \c_false_bool }
1869             \@@_patch_preamble:n #2
1870         }
1871     }
1872 }
1873 \cs_new_protected:Npn \@@_patch_preamble_viii_i:nnn #1 #2 #3
1874 {
1875     \tl_if_eq:nnTF { \q_stop } { #3 }
1876     {
1877         \str_if_eq:VnTF \g_@@_right_delim_tl { . }
1878         {
1879             \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } }
1880             \tl_gput_right:Nx \g_@@_internal_code_after_tl
1881             { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } \c_false_bool }
1882             \tl_gset:Nn \g_@@_right_delim_tl { #2 }
1883         }
1884         {
1885             \tl_gput_right:Nn \g_@@_preamble_tl { ! { \enskip } }
1886             \tl_gput_right:Nx \g_@@_internal_code_after_tl
1887             { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } \c_false_bool }
1888             \@@_error:nn { double-closing-delimiter } { #2 }
1889         }
1890     }
1891     {
1892         \tl_gput_right:Nx \g_@@_internal_code_after_tl
1893         { \@@_delimiter:nnn #1 { \int_use:N \c@jCol } \c_false_bool }
1894         \@@_error:nn { double-closing-delimiter } { #2 }
1895         \@@_patch_preamble:n #3
1896     }
1897 }
1898 \cs_new_protected:Npn \@@_patch_preamble_xi:n #1
1899 {
1900     \tl_gput_right:Nn \g_@@_preamble_tl

```

```
1901 { ! { \skip_horizontal:N 2\l_@@_radius_dim } }
```

The command `\@@_vdottedline:n` is protected, and, therefore, won't be expanded before writing on `\g_@@_internal_code_after_tl`.

```
1902 \tl_gput_right:Nx \g_@@_internal_code_after_tl
1903   { \@@_vdottedline:n { \int_use:N \c@jCol } }
1904   \@@_patch_preamble:n
1905 }
```

After a specifier of column, we have to test whether there is one or several `<{ .. }>` because, after those potential `<{ .. }>`, we have to insert `!{\skip_horizontal:N ...}` when the key `vlines` is used.

```
1906 \cs_new_protected:Npn \@@_patch_preamble_x:n #1
1907 {
1908   \str_if_eq:nnTF { #1 } { < }
1909     \@@_patch_preamble_ix:n
1910   {
1911     \tl_if_eq:NnTF \l_@@_vlines_clist { all }
1912     {
1913       \tl_gput_right:Nn \g_@@_preamble_tl
1914         { ! { \skip_horizontal:N \arrayrulewidth } }
1915     }
1916   {
1917     \exp_args:NNx
1918     \clist_if_in:NnT \l_@@_vlines_clist { \@@_succ:n \c@jCol }
1919     {
1920       \tl_gput_right:Nn \g_@@_preamble_tl
1921         { ! { \skip_horizontal:N \arrayrulewidth } }
1922     }
1923   }
1924   \@@_patch_preamble:n { #1 }
1925 }
1926 }
1927 \cs_new_protected:Npn \@@_patch_preamble_ix:n #1
1928 {
1929   \tl_gput_right:Nn \g_@@_preamble_tl { < { #1 } }
1930   \@@_patch_preamble_x:n
1931 }
```

The redefinition of `\multicolumn`

The following command must *not* be protected since it begins with `\multispan` (a TeX primitive).

```
1932 \cs_new:Npn \@@_multicolumn:nnn #1 #2 #3
1933 {
```

The following lines are from the definition of `\multicolumn` in `array` (and *not* in standard LaTeX). The first line aims to raise an error if the user has put more than one column specifier in the preamble of `\multicolumn`.

```
1934 \multispan { #1 }
1935 \begingroup
1936 \cs_set:Npn \c@addamp { \if@firstamp \c@firstampfalse \else \c@preamerr 5 \fi }
```

You do the expansion of the (small) preamble with the tools of `array`.

```
1937 \c@temptokena = { #2 }
1938 \c@tempswatru
1939 \c@whilesw \if@tempswa \fi { \c@tempswafalse \the \c@NC@list }
```

Now, we patch the (small) preamble as we have done with the main preamble of the array.

```
1940 \tl_gclear:N \g_@@_preamble_tl
1941 \exp_after:wN \@@_patch_m_preamble:n \the \c@temptokena \q_stop
```

The following lines are an adaptation of the definition of `\multicolumn` in array.

```
1942 \exp_args:NV \omkpream \g_@@_preamble_tl
1943 \addtopreamble \empty
1944 \endgroup
```

Now, you do a treatment specific to nicematrix which has no equivalent in the original definition of `\multicolumn`.

```
1945 \int_compare:nNnT { #1 } > 1
1946 {
1947     \seq_gput_left:Nx \g_@@_multicolumn_cells_seq
1948     { \int_use:N \c@iRow - \@@_succ:n \c@jCol }
1949     \seq_gput_left:Nn \g_@@_multicolumn_sizes_seq { #1 }
1950     \seq_gput_right:Nx \g_@@_pos_of_blocks_seq
1951     {
1952         { \int_use:N \c@iRow }
1953         { \int_eval:n { \c@jCol + 1 } }
1954         { \int_use:N \c@iRow }
1955         { \int_eval:n { \c@jCol + #1 } }
1956     }
1957 }
```

The following lines were in the original definition of `\multicolumn`.

```
1958 \cs_set:Npn \sharp { #3 }
1959 \carstrut
1960 \preamble
1961 \null
```

We add some lines.

```
1962 \int_gadd:Nn \c@jCol { #1 - 1 }
1963 \int_compare:nNnT \c@jCol > \g_@@_col_total_int
1964 { \int_gset_eq:NN \g_@@_col_total_int \c@jCol }
1965 \ignorespaces
1966 }
```

The following commands will patch the (small) preamble of the `\multicolumn`. All those commands have a `m` in their name to recall that they deal with the redefinition of `\multicolumn`.

```
1967 \cs_new_protected:Npn \patch_m_preamble:n #1
1968 {
1969     \str_case:nnF { #1 }
1970     {
1971         c { \patch_m_preamble_i:n #1 }
1972         l { \patch_m_preamble_i:n #1 }
1973         r { \patch_m_preamble_i:n #1 }
1974         > { \patch_m_preamble_ii:nn #1 }
1975         ! { \patch_m_preamble_ii:nn #1 }
1976         @ { \patch_m_preamble_ii:nn #1 }
1977         | { \patch_m_preamble_iii:n #1 }
1978         p { \patch_m_preamble_iv:nnn t #1 }
1979         m { \patch_m_preamble_iv:nnn c #1 }
1980         b { \patch_m_preamble_iv:nnn b #1 }
1981         \@@_w: { \patch_m_preamble_v:nnnn { } } #1 }
1982         \@@_W: { \patch_m_preamble_v:nnnn { \cs_set_eq:NN \hss \hfil } #1 }
1983         \@@_true_c: { \patch_m_preamble_vi:n #1 }
1984         C { \patch_error:nn { old-column-type } #1 }
1985         L { \patch_error:nn { old-column-type } #1 }
1986         R { \patch_error:nn { old-column-type } #1 }
1987         \q_stop { }
1988     }
1989     { \@@_fatal:nn { unknown-column-type } { #1 } }
1990 }
```

For c, l and r

```
1991 \cs_new_protected:Npn \@@_patch_m_preamble_i:n #1
1992 {
1993     \tl_gput_right:Nn \g_@@_preamble_tl
1994     {
1995         > { \@@_Cell: \tl_set:Nn \l_@@_cell_type_tl { #1 } }
1996         #1
1997         < \@@_end_Cell:
1998     }
1999 }
```

We test for the presence of a <.

```
2000 }
```

For >, ! and @

```
2001 \cs_new_protected:Npn \@@_patch_m_preamble_ii:nn #1 #2
2002 {
2003     \tl_gput_right:Nn \g_@@_preamble_tl { #1 { #2 } }
2004     \@@_patch_m_preamble:n
2005 }
```

For |

```
2006 \cs_new_protected:Npn \@@_patch_m_preamble_iii:n #1
2007 {
2008     \tl_gput_right:Nn \g_@@_preamble_tl { #1 }
2009     \@@_patch_m_preamble:n
2010 }
```

For p, m and b

```
2011 \cs_new_protected:Npn \@@_patch_m_preamble_iv:nnn #1 #2 #3
2012 {
2013     \tl_gput_right:Nn \g_@@_preamble_tl
2014     {
2015         > {
2016             \@@_Cell:
2017             \begin{minipage} [ #1 ] { \dim_eval:n { #3 } }
2018             \mode_leave_vertical:
2019             \arraybackslash
2020             \vrule height \box_ht:N \carstrutbox depth 0 pt width 0 pt
2021         }
2022         c
2023         < {
2024             \vrule height 0 pt depth \box_dp:N \carstrutbox width 0 pt
2025             \end{minipage}
2026             \@@_end_Cell:
2027         }
2028     }
2029 }
```

We test for the presence of a <.

```
2030 }
```

For w and W

```
2031 \cs_new_protected:Npn \@@_patch_m_preamble_v:nnnn #1 #2 #3 #4
2032 {
2033     \tl_gput_right:Nn \g_@@_preamble_tl
2034     {
2035         > {
2036             \hbox_set:Nw \l_@@_cell_box
2037             \@@_Cell:
2038             \tl_set:Nn \l_@@_cell_type_tl { #3 }
2039         }
2040         c
2041         < {
```

```

2042         \@@_end_Cell:
2043         #1
2044         \hbox_set_end:
2045         \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
2046         \@@_adjust_size_box:
2047         \makebox [ #4 ] [ #3 ] { \box_use_drop:N \l_@@_cell_box }
2048     }
2049 }

```

We test for the presence of a <.

```

2050     \@@_patch_m_preamble_x:n
2051 }

```

For \@@_true_c: which will appear in our redefinition of the columns of type S (of siunitx).

```

2052 \cs_new_protected:Npn \@@_patch_m_preamble_vi:n #1
2053 {
2054     \tl_gput_right:Nn \g_@@_preamble_tl { c }

```

We test for the presence of a <.

```

2055     \@@_patch_m_preamble_x:n
2056 }

```

After a specifier of column, we have to test whether there is one or several <{..} because, after those potential <{...}, we have to insert !{\skip_horizontal:N ...} when the key vlines is used.

```

2057 \cs_new_protected:Npn \@@_patch_m_preamble_x:n #1
2058 {
2059     \str_if_eq:nnTF { #1 } { < }
2060     \@@_patch_m_preamble_ix:n
2061     {
2062         \tl_if_eq:NnTF \l_@@_vlines_clist { all }
2063         {
2064             \tl_gput_right:Nn \g_@@_preamble_tl
2065             { ! { \skip_horizontal:N \arrayrulewidth } }
2066         }
2067         {
2068             \exp_args:NNx
2069             \clist_if_in:NnT \l_@@_vlines_clist { \@@_succ:n \c@jCol }
2070             {
2071                 \tl_gput_right:Nn \g_@@_preamble_tl
2072                 { ! { \skip_horizontal:N \arrayrulewidth } }
2073             }
2074         }
2075         \@@_patch_m_preamble:n { #1 }
2076     }
2077 }
2078 \cs_new_protected:Npn \@@_patch_m_preamble_ix:n #1
2079 {
2080     \tl_gput_right:Nn \g_@@_preamble_tl { < { #1 } }
2081     \@@_patch_m_preamble_x:n
2082 }

```

The command \@@_put_box_in_flow: puts the box \l_tmpa_box (which contains the array) in the flow. It is used for the environments with delimiters. First, we have to modify the height and the depth to take back into account the potential exterior rows (the total height of the first row has been computed in \l_tmpa_dim and the total height of the potential last row in \l_tmpb_dim).

```

2083 \cs_new_protected:Npn \@@_put_box_in_flow:
2084 {
2085     \box_set_ht:Nn \l_tmpa_box { \box_ht:N \l_tmpa_box + \l_tmpa_dim }
2086     \box_set_dp:Nn \l_tmpa_box { \box_dp:N \l_tmpa_box + \l_tmpb_dim }
2087     \tl_if_eq:NnTF \l_@@_baseline_tl { c }
2088     { \box_use_drop:N \l_tmpa_box }
2089     \@@_put_box_in_flow_i:
2090 }

```

The command `\@@_put_box_in_flow_i:` is used when the value of `\l_@@_baseline_tl` is different of `c` (which is the initial value and the most used).

```
2091 \cs_new_protected:Npn \@@_put_box_in_flow_i:
2092 {
2093     \pgfpicture
2094         \@@_qpoint:n { row - 1 }
2095         \dim_gset_eq:NN \g_tmpa_dim \pgf@y
2096         \@@_qpoint:n { row - \@@_succ:n \c@iRow }
2097         \dim_gadd:Nn \g_tmpa_dim \pgf@y
2098         \dim_gset:Nn \g_tmpa_dim { 0.5 \g_tmpa_dim }
```

Now, `\g_tmpa_dim` contains the y -value of the center of the array (the delimiters are centered in relation with this value).

```
2099     \str_if_in:NnTF \l_@@_baseline_tl { line- }
2100     {
2101         \int_set:Nn \l_tmpa_int
2102         {
2103             \str_range:Nnn
2104                 \l_@@_baseline_tl
2105                 6
2106                 { \tl_count:V \l_@@_baseline_tl }
2107         }
2108         \@@_qpoint:n { row - \int_use:N \l_tmpa_int }
2109     }
2110     {
2111         \str_case:Vnf \l_@@_baseline_tl
2112         {
2113             { t } { \int_set:Nn \l_tmpa_int 1 }
2114             { b } { \int_set_eq:NN \l_tmpa_int \c@iRow }
2115         }
2116         { \int_set:Nn \l_tmpa_int \l_@@_baseline_tl }
2117         \bool_lazy_or:nnT
2118             { \int_compare_p:nNn \l_tmpa_int < \l_@@_first_row_int }
2119             { \int_compare_p:nNn \l_tmpa_int > \g_@@_row_total_int }
2120         {
2121             \@@_error:n { bad-value-for-baseline }
2122             \int_set:Nn \l_tmpa_int 1
2123         }
2124         \@@_qpoint:n { row - \int_use:N \l_tmpa_int - base }
```

We take into account the position of the mathematical axis.

```
2125     \dim_gsub:Nn \g_tmpa_dim { \fontdimen22 \textfont2 }
2126     }
2127     \dim_gsub:Nn \g_tmpa_dim \pgf@y
```

Now, `\g_tmpa_dim` contains the value of the y translation we have to do.

```
2128     \endpgfpicture
2129     \box_move_up:nn \g_tmpa_dim { \box_use_drop:N \l_tmpa_box }
2130     \box_use_drop:N \l_tmpa_box
2131 }
```

The following command is *always* used by `{NiceArrayWithDelims}` (even if, in fact, there is no tabular notes: in fact, it's not possible to know whether there is tabular notes or not before the composition of the blocks).

```
2132 \cs_new_protected:Npn \@@_use_arraybox_with_notes_c:
2133 {
```

We need a `{minipage}` because we will insert a LaTeX list for the tabular notes (that means that a `\vtop{\hspace{...}}` is not enough).

```
2134     \begin{minipage} [ t ] { \box_wd:N \l_@@_the_array_box }
2135     \box_use_drop:N \l_@@_the_array_box
```

We have to draw the blocks right now because there may be tabular notes in some blocks (which are not mono-column: the blocks which are mono-column have been composed in boxes yet)... and we have to create (potentially) the extra nodes before creating the blocks since there are `medium` nodes to create for the blocks.

```

2136 \@@_create_extra_nodes:
2137 \seq_if_empty:NF \g_@@_blocks_seq \@@_draw_blocks:
2138 \bool_lazy_or:nnT
2139 { \int_compare_p:nNn \c@tabularnote > 0 }
2140 { ! \tl_if_empty_p:V \l_@@_tabularnote_tl }
2141 \@@_insert_tabularnotes:
2142 \end { minipage }
2143 }

2144 \cs_new_protected:Npn \@@_insert_tabularnotes:
2145 {
2146     \skip_vertical:N 0.65ex

```

The TeX group is for potential specifications in the `\l_@@_notes_code_before_tl`.

```

2147 \group_begin:
2148 \l_@@_notes_code_before_tl
2149 \tl_if_empty:NF \l_@@_tabularnote_tl { \l_@@_tabularnote_tl \par }

```

We compose the tabular notes with a list of `enumitem`. The `\strut` and the `\unskip` are designed to give the ability to put a `\bottomrule` at the end of the notes with a good vertical space.

```

2150 \int_compare:nNnT \c@tabularnote > 0
2151 {
2152     \bool_if:NTF \l_@@_notes_para_bool
2153     {
2154         \begin { tabularnotes* }
2155             \seq_map_inline:Nn \g_@@_tabularnotes_seq { \item ##1 } \strut
2156         \end { tabularnotes* }

```

The following `\par` is mandatory for the event that the user has put `\footnotesize` (for example) in the `notes/code-before`.

```

2157         \par
2158     }
2159     {
2160         \tabularnotes
2161             \seq_map_inline:Nn \g_@@_tabularnotes_seq { \item ##1 } \strut
2162         \endtabularnotes
2163     }
2164 }
2165 \unskip
2166 \group_end:
2167 \bool_if:NT \l_@@_notes_bottomrule_bool
2168 {
2169     \bool_if:NTF \c_@@_booktabs_loaded_bool
2170     {

```

The two dimensions `\aboverulesep` et `\heavyrulewidth` are parameters defined by `booktabs`.

```
2171     \skip_vertical:N \aboverulesep
```

`\CT@arc@` is the specification of color defined by `colortbl` but you use it even if `colortbl` is not loaded.

```

2172     { \CT@arc@ \hrule height \heavyrulewidth }
2173     }
2174     { \@@_error:n { bottomrule~without~booktabs } }
2175     }
2176 \l_@@_notes_code_after_tl
2177 \seq_gclear:N \g_@@_tabularnotes_seq
2178 \int_gzero:N \c@tabularnote
2179 }
```

The case of `baseline` equal to `b`. Remember that, when the key `b` is used, the `{array}` (of `array`) is constructed with the option `t` (and not `b`). Now, we do the translation to take into account the option `b`.

```

2180 \cs_new_protected:Npn \@@_use_arraybox_with_notes_b:
2181 {
2182     \pgfpicture
2183         \@@_qpoint:n { row - 1 }
2184         \dim_gset_eq:NN \g_tmpa_dim \pgf@y
2185         \@@_qpoint:n { row - \int_use:N \c@iRow - base }
2186         \dim_gsub:Nn \g_tmpa_dim \pgf@y
2187     \endpgfpicture
2188     \dim_gadd:Nn \g_tmpa_dim \arrayrulewidth
2189     \int_compare:nNnT \l_@@_first_row_int = 0
2190     {
2191         \dim_gadd:Nn \g_tmpa_dim \g_@@_ht_row_zero_dim
2192         \dim_gadd:Nn \g_tmpa_dim \g_@@_dp_row_zero_dim
2193     }
2194     \box_move_up:nn \g_tmpa_dim { \hbox { \@@_use_arraybox_with_notes_c: } }
2195 }

```

Now, the general case.

```

2196 \cs_new_protected:Npn \@@_use_arraybox_with_notes:
2197 {

```

We convert a value of t to a value of 1.

```

2198 \tl_if_eq:NnT \l_@@_baseline_tl { t }
2199     { \tl_set:Nn \l_@@_baseline_tl { 1 } }

```

Now, we convert the value of $\l_@@_baseline_tl$ (which should represent an integer) to an integer stored in \l_tmpa_int .

```

2200 \pgfpicture
2201     \@@_qpoint:n { row - 1 }
2202     \dim_gset_eq:NN \g_tmpa_dim \pgf@y
2203     \str_if_in:NnTF \l_@@_baseline_tl { line- }
2204     {
2205         \int_set:Nn \l_tmpa_int
2206             {
2207                 \str_range:Nnn
2208                     \l_@@_baseline_tl
2209                     6
2210                     { \tl_count:V \l_@@_baseline_tl }
2211             }
2212         \@@_qpoint:n { row - \int_use:N \l_tmpa_int }
2213     }
2214     {
2215         \int_set:Nn \l_tmpa_int \l_@@_baseline_tl
2216         \bool_lazy_or:nnT
2217             { \int_compare_p:nNn \l_tmpa_int < \l_@@_first_row_int }
2218             { \int_compare_p:nNn \l_tmpa_int > \g_@@_row_total_int }
2219             {
2220                 \@@_error:n { bad-value~for~baseline }
2221                 \int_set:Nn \l_tmpa_int 1
2222             }
2223         \@@_qpoint:n { row - \int_use:N \l_tmpa_int - base }
2224     }
2225     \dim_gsub:Nn \g_tmpa_dim \pgf@y
2226     \endpgfpicture
2227     \dim_gadd:Nn \g_tmpa_dim \arrayrulewidth
2228     \int_compare:nNnT \l_@@_first_row_int = 0
2229     {
2230         \dim_gadd:Nn \g_tmpa_dim \g_@@_ht_row_zero_dim
2231         \dim_gadd:Nn \g_tmpa_dim \g_@@_dp_row_zero_dim
2232     }
2233     \box_move_up:nn \g_tmpa_dim { \hbox { \@@_use_arraybox_with_notes_c: } }
2234 }

```

The command `\@@_put_box_in_flow_bis:` is used when the option `delimiters/max-width` is used because, in this case, we have to adjust the widths of the delimiters. The arguments `#1` and `#2` are the delimiters specified by the user.

```
2235 \cs_new_protected:Npn \@@_put_box_in_flow_bis:nn #1 #2
2236 {
```

We will compute the real width of both delimiters used.

```
2237 \dim_zero_new:N \l_@@_real_left_delim_dim
2238 \dim_zero_new:N \l_@@_real_right_delim_dim
2239 \hbox_set:Nn \l_tmpb_box
2240 {
2241     \c_math_toggle_token
2242     \left #1
2243     \vcenter
2244     {
2245         \vbox_to_ht:nn
2246         { \box_ht:N \l_tmpa_box + \box_dp:N \l_tmpa_box }
2247         { }
2248     }
2249     \right .
2250     \c_math_toggle_token
2251 }
2252 \dim_set:Nn \l_@@_real_left_delim_dim
2253 { \box_wd:N \l_tmpb_box - \nulldelimiterspace }
2254 \hbox_set:Nn \l_tmpb_box
2255 {
2256     \c_math_toggle_token
2257     \left .
2258     \vbox_to_ht:nn
2259     { \box_ht:N \l_tmpa_box + \box_dp:N \l_tmpa_box }
2260     { }
2261     \right #2
2262     \c_math_toggle_token
2263 }
2264 \dim_set:Nn \l_@@_real_right_delim_dim
2265 { \box_wd:N \l_tmpb_box - \nulldelimiterspace }
```

Now, we can put the box in the TeX flow with the horizontal adjustments on both sides.

```
2266 \skip_horizontal:N \l_@@_left_delim_dim
2267 \skip_horizontal:N -\l_@@_real_left_delim_dim
2268 \@@_put_box_in_flow:
2269 \skip_horizontal:N \l_@@_right_delim_dim
2270 \skip_horizontal:N -\l_@@_real_right_delim_dim
2271 }
```

The construction of the array in the environment `{NiceArrayWithDelims}` is, in fact, done by the environment `{@@-light-syntax}` or by the environment `{@@-normal-syntax}` (whether the option `light-syntax` is in force or not). When the key `light-syntax` is not used, the construction is a standard environment (and, thus, it's possible to use verbatim in the array).

```
2272 \NewDocumentEnvironment { @@-normal-syntax } { }
```

First, we test whether the environment is empty. If it is empty, we raise a fatal error (it's only a security). In order to detect whether it is empty, we test whether the next token is `\end` and, if it's the case, we test if this is the end of the environment (if it is not, an standard error will be raised by LaTeX for incorrect nested environments).

```
2273 {
2274     \peek_meaning_ignore_spaces:NTF \end \@@_analyze_end:Nn
```

Here is the call to `\array` (we have a dedicated macro `\@@_array:` because of compatibility with the classes `revtex4-1` and `revtex4-2`).

```
2275 { \exp_args:NV \@@_array: \g_@@_preamble_tl }
2276 }
2277 {
```

```

2278     \@@_create_col_nodes:
2279     \endarray
2280 }
```

When the key `light-syntax` is in force, we use an environment which takes its whole body as an argument (with the specifier `b` of `xparse`).

```

2281 \NewDocumentEnvironment { @@-light-syntax } { b }
2282 {
```

First, we test whether the environment is empty. It's only a security. Of course, this test is more easy than the similar test for the "normal syntax" because we have the whole body of the environment in `#1`.

```

2283 \tl_if_empty:nT { #1 } { \@@_fatal:n { empty~environment } }
2284 \tl_map_inline:nn { #1 }
2285 {
2286     \str_if_eq:nnT { ##1 } { & }
2287     { \@@_fatal:n { ampersand-in-light-syntax } }
2288     \str_if_eq:nnT { ##1 } { \\ }
2289     { \@@_fatal:n { double-backslash-in-light-syntax } }
2290 }
```

Now, you extract the `\CodeAfter` of the body of the environment. Maybe, there is no command `\CodeAfter` in the body. That's why you put a marker `\CodeAfter` after `#1`. If there is yet a `\CodeAfter` in `#1`, this second (or third...) `\CodeAfter` will be catched in the value of `\g_nicematrix_code_after_tl`. That doesn't matter because `\CodeAfter` will be set to `no-op` before the execution of `\g_nicematrix_code_after_tl`.

```

2291     \@@_light_syntax_i #1 \CodeAfter \q_stop
2292 }
```

Now, the second part of the environment. It is empty. That's not surprising because we have caught the whole body of the environment with the specifier `b` provided by `xparse`.

```

2293 { }
2294 \cs_new_protected:Npn \@@_light_syntax_i #1\CodeAfter #2\q_stop
2295 {
2296     \tl_gput_right:Nn \g_nicematrix_code_after_tl { #2 }
```

The body of the array, which is stored in the argument `#1`, is now splitted into items (and *not* tokens).

```

2297 \seq_gclear_new:N \g_@@_rows_seq
2298 \tl_set_rescan:Nno \l_@@_end_of_row_tl { } \l_@@_end_of_row_tl
2299 \exp_args:NNV \seq_gset_split:Nnn \g_@@_rows_seq \l_@@_end_of_row_tl { #1 }
```

If the environment uses the option `last-row` without value (i.e. without saying the number of the rows), we have now the opportunity to know that value. We do it, and so, if the token list `\l_@@_code_for_last_row_tl` is not empty, we will use directly where it should be.

```

2300 \int_compare:nNnT \l_@@_last_row_int = { -1 }
2301     { \int_set:Nn \l_@@_last_row_int { \seq_count:N \g_@@_rows_seq } }
```

Here is the call to `\array` (we have a dedicated macro `\@@_array`: because of compatibility with the classes `revtex4-1` and `revtex4-2`).

```

2302 \exp_args:NV \@@_array: \g_@@_preamble_tl
```

We need a global affectation because, when executing `\l_tmpa_tl`, we will exit the first cell of the array.

```

2303 \seq_gpop_left:NN \g_@@_rows_seq \l_tmpa_tl
2304 \exp_args:NV \@@_line_with_light_syntax_i:n \l_tmpa_tl
2305 \seq_map_function:NN \g_@@_rows_seq \@@_line_with_light_syntax:n
2306 \@@_create_col_nodes:
2307 \endarray
2308 }
2309 \cs_new_protected:Npn \@@_line_with_light_syntax:n #1
2310     { \tl_if_empty:nF { #1 } { \\ \@@_line_with_light_syntax_i:n { #1 } } }
```

```

2311 \cs_new_protected:Npn \@@_line_with_light_syntax_i:n #1
2312 {
2313     \seq_gclear_new:N \g_@@_cells_seq
2314     \seq_gset_split:Nnn \g_@@_cells_seq { ~ } { #1 }
2315     \seq_gpop_left:NN \g_@@_cells_seq \l_tmpa_tl
2316     \l_tmpa_tl
2317     \seq_map_inline:Nn \g_@@_cells_seq { & ##1 }
2318 }
```

The following command is used by the code which detects whether the environment is empty (we raise a fatal error in this case: it's only a security).

```

2319 \cs_new_protected:Npn \@@_analyze_end:Nn #1 #2
2320 {
2321     \str_if_eq:VnT \g_@@_name_env_str { #2 }
2322     { \@@_fatal:n { empty~environment } }
2323     \end { #2 }
2324 }
```

We reput in the stream the `\end{...}` we have extracted and the user will have an error for incorrect nested environments.

```

2325 \cs_new:Npn \@@_create_col_nodes:
2326 {
2327     \crcr
2328     \int_compare:nNnT \l_@@_first_col_int = 0
2329     {
2330         \omit
2331         \hbox_overlap_left:n
2332         {
2333             \bool_if:NT \l_@@_code_before_bool
2334             { \pgf@sys@markposition { \@@_env: - col - 0 } }
2335             \pgfpicture
2336             \pgfrememberpicturepositiononpagetrue
2337             \pgfcoordinate { \@@_env: - col - 0 } \pgfpointorigin
2338             \str_if_empty:NF \l_@@_name_str
2339             { \pgfnodealias { \l_@@_name_str - col - 0 } { \@@_env: - col - 0 } }
2340             \endpgfpicture
2341             \skip_horizontal:N 2\col@sep
2342             \skip_horizontal:N \g_@@_width_first_col_dim
2343         }
2344         &
2345     }
2346     \omit
```

The following instruction must be put after the instruction `\omit`.

```
2347 \bool_gset_true:N \g_@@_row_of_col_done_bool
```

First, we put a `col` node on the left of the first column (of course, we have to do that *after* the `\omit`).

```

2348 \int_compare:nNnTF \l_@@_first_col_int = 0
2349 {
2350     \bool_if:NT \l_@@_code_before_bool
2351     {
2352         \hbox
2353         {
2354             \skip_horizontal:N -0.5\arrayrulewidth
2355             \pgf@sys@markposition { \@@_env: - col - 1 }
2356             \skip_horizontal:N 0.5\arrayrulewidth
2357         }
2358     }
```

```

2359 \pgfpicture
2360 \pgfrememberpicturepositiononpagetrue
2361 \pgfcoordinate { \l_@@_env: - col - 1 }
2362   { \pgfpoint { - 0.5 \arrayrulewidth } \c_zero_dim }
2363 \str_if_empty:NF \l_@@_name_str
2364   { \pgfnodealias { \l_@@_name_str - col - 1 } { \l_@@_env: - col - 1 } }
2365 \endpgfpicture
2366 }
2367 {
2368   \bool_if:NT \l_@@_code_before_bool
2369   {
2370     \hbox
2371     {
2372       \skip_horizontal:N 0.5\arrayrulewidth
2373       \pgfsys@markposition { \l_@@_env: - col - 1 }
2374       \skip_horizontal:N -0.5\arrayrulewidth
2375     }
2376   }
2377 \pgfpicture
2378 \pgfrememberpicturepositiononpagetrue
2379 \pgfcoordinate { \l_@@_env: - col - 1 }
2380   { \pgfpoint { 0.5 \arrayrulewidth } \c_zero_dim }
2381 \str_if_empty:NF \l_@@_name_str
2382   { \pgfnodealias { \l_@@_name_str - col - 1 } { \l_@@_env: - col - 1 } }
2383 \endpgfpicture
2384 }

```

We compute in `\g_tmpa_skip` the common width of the columns (it's a skip and not a dimension). We use a global variable because we are in a cell of an `\halign` and because we have to use this variable in other cells (of the same row). The affectation of `\g_tmpa_skip`, like all the affectations, must be done after the `\omit` of the cell.

We give a default value for `\g_tmpa_skip` (0 pt plus 1 fill) but it will just after be erased by a fixed value in the concerned cases.

```

2385 \skip_gset:Nn \g_tmpa_skip { 0 pt~plus 1 fill }
2386 \bool_if:NF \l_@@_auto_columns_width_bool
2387   { \dim_compare:nNnT \l_@@_columns_width_dim > \c_zero_dim }
2388   {
2389     \bool_lazy_and:nnTF
2390       \l_@@_auto_columns_width_bool
2391       { \bool_not_p:n \l_@@_block_auto_columns_width_bool }
2392       { \skip_gset_eq:NN \g_tmpa_skip \g_@@_max_cell_width_dim }
2393       { \skip_gset_eq:NN \g_tmpa_skip \l_@@_columns_width_dim }
2394     \skip_gadd:Nn \g_tmpa_skip { 2 \col@sep }
2395   }
2396 \skip_horizontal:N \g_tmpa_skip
2397 \hbox
2398   {
2399     \bool_if:NT \l_@@_code_before_bool
2400     {
2401       \hbox
2402       {
2403         \skip_horizontal:N -0.5\arrayrulewidth
2404         \pgfsys@markposition { \l_@@_env: - col - 2 }
2405         \skip_horizontal:N 0.5\arrayrulewidth
2406       }
2407     }
2408 \pgfpicture
2409 \pgfrememberpicturepositiononpagetrue
2410 \pgfcoordinate { \l_@@_env: - col - 2 }
2411   { \pgfpoint { - 0.5 \arrayrulewidth } \c_zero_dim }
2412 \str_if_empty:NF \l_@@_name_str
2413   { \pgfnodealias { \l_@@_name_str - col - 2 } { \l_@@_env: - col - 2 } }
2414 \endpgfpicture

```

```
2415 }
```

We begin a loop over the columns. The integer `\g_tmpa_int` will be the number of the current column. This integer is used for the Tikz nodes.

```
2416 \int_gset:Nn \g_tmpa_int 1
2417 \bool_if:NTF \l_@@_last_col_found_bool
2418 { \prg_replicate:nn { \g_@@_col_total_int - 2 } }
2419 { \prg_replicate:nn { \g_@@_col_total_int - 1 } }
2420 {
2421   &
2422   \omit
2423   \int_gincr:N \g_tmpa_int
```

The incrementation of the counter `\g_tmpa_int` must be done after the `\omit` of the cell.

```
2424   \skip_horizontal:N \g_tmpa_skip
2425   \bool_if:NT \l_@@_code_before_bool
2426   {
2427     \hbox
2428     {
2429       \skip_horizontal:N -0.5\arrayrulewidth
2430       \pgfsys@markposition { \@@_env: - col - \@@_succ:n \g_tmpa_int }
2431       \skip_horizontal:N 0.5\arrayrulewidth
2432     }
2433   }
```

We create the `col` node on the right of the current column.

```
2434 \pgfpicture
2435   \pgfrememberpicturepositiononpagetrue
2436   \pgfcoordinate { \@@_env: - col - \@@_succ:n \g_tmpa_int }
2437   { \pgfpoint { - 0.5 \arrayrulewidth } \c_zero_dim }
2438   \str_if_empty:NF \l_@@_name_str
2439   {
2440     \pgfnodealias
2441     { \l_@@_name_str - col - \@@_succ:n \g_tmpa_int }
2442     { \@@_env: - col - \@@_succ:n \g_tmpa_int }
2443   }
2444 \endpgfpicture
2445 }
```

We want to remove the exterior `\arraycolsep` of a environment `{NiceArray}`.

```
2446 \bool_lazy_all:nT
2447 {
2448   \l_@@_NiceArray_bool
2449   { \bool_not_p:n \l_@@_NiceTabular_bool }
2450   { \clist_if_empty_p:N \l_@@_vlines_clist }
2451   { \bool_not_p:n \l_@@_exterior_arraycolsep_bool }
2452   { ! \l_@@_bar_at_end_of_pream_bool }
2453 }
2454 { \skip_horizontal:n { - \col@sep } }

2455 \bool_if:NT \g_@@_last_col_found_bool
2456 {
2457   \hbox_overlap_right:n
2458   {
2459     \skip_horizontal:N \g_@@_width_last_col_dim
2460     \bool_if:NT \l_@@_code_before_bool
2461     {
2462       \pgfsys@markposition
2463       { \@@_env: - col - \@@_succ:n \g_@@_col_total_int }
2464     }
2465   \pgfpicture
2466   \pgfrememberpicturepositiononpagetrue
2467   \pgfcoordinate { \@@_env: - col - \@@_succ:n \g_@@_col_total_int }
```

```

2468     \pgfpointorigin
2469     \str_if_empty:NF \l_@@_name_str
2470     {
2471         \pgfnodealias
2472             { \l_@@_name_str - col - \@@_succ:n \g_@@_col_total_int }
2473             { \@@_env: - col - \@@_succ:n \g_@@_col_total_int }
2474     }
2475     \endpgfpicture
2476 }
2477 }
2478 \cr
2479 }
```

Here is the preamble for the “first column” (if the user uses the key `first-col`)

```

2480 \tl_const:Nn \c_@@_preamble_first_col_tl
2481 {
2482 >
2483 {
```

At the beginning of the cell, we link `\CodeAfter` to a command which do *not* begin with `\omit` (whereas the standard version of `\CodeAfter` begins with `\omit`).

```

2484 \cs_set_eq:NN \CodeAfter \@@_CodeAfter_i:n
2485 \bool_gset_true:N \g_@@_after_col_zero_bool
2486 \@@_begin_of_row:
```

The contents of the cell is constructed in the box `\l_@@_cell_box` because we have to compute some dimensions of this box.

```

2487 \hbox_set:Nw \l_@@_cell_box
2488 \@@_math_toggle_token:
2489 \bool_if:NT \l_@@_small_bool \scriptstyle
```

We insert `\l_@@_code_for_first_col_tl`... but we don’t insert it in the potential “first row” and in the potential “last row”.

```

2490 \bool_lazy_and:nnT
2491     { \int_compare_p:nNn \c@iRow > 0 }
2492     {
2493         \bool_lazy_or_p:nn
2494             { \int_compare_p:nNn \l_@@_last_row_int < 0 }
2495             { \int_compare_p:nNn \c@iRow < \l_@@_last_row_int }
2496     }
2497     {
2498         \l_@@_code_for_first_col_tl
2499         \xglobal \colorlet{nicematrix-first-col}{.}
2500     }
2501 }
```

Be careful: despite this letter `l` the cells of the “first column” are composed in a `R` manner since they are composed in a `\hbox_overlap_left:n`.

```

2502 l
2503 <
2504 {
2505     \@@_math_toggle_token:
2506     \hbox_set_end:
2507     \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
2508     \@@_adjust_size_box:
2509     \@@_update_for_first_and_last_row:
```

We actualise the width of the “first column” because we will use this width after the construction of the array.

```

2510 \dim_gset:Nn \g_@@_width_first_col_dim
2511     { \dim_max:nn \g_@@_width_first_col_dim { \box_wd:N \l_@@_cell_box } }
```

The content of the cell is inserted in an overlapping position.

```

2512 \hbox_overlap_left:n
2513 {
2514     \dim_compare:nNnTF { \box_wd:N \l_@@_cell_box } > \c_zero_dim
2515         \@@_node_for_cell:
2516             { \box_use_drop:N \l_@@_cell_box }
2517             \skip_horizontal:N \l_@@_left_delim_dim
2518             \skip_horizontal:N \l_@@_left_margin_dim
2519             \skip_horizontal:N \l_@@_extra_left_margin_dim
2520         }
2521     \bool_gset_false:N \g_@@_empty_cell_bool
2522     \skip_horizontal:N -2\col@sep
2523 }
2524 }
```

Here is the preamble for the “last column” (if the user uses the key `last-col`).

```

2525 \tl_const:Nn \c_@@_preamble_last_col_tl
2526 {
2527     >
2528 }
```

At the beginning of the cell, we link `\CodeAfter` to a command which do *not* begin with `\omit` (whereas the standard version of `\CodeAfter` begins with `\omit`).

```
2529 \cs_set_eq:NN \CodeAfter \c_@@_CodeAfter_i:n
```

With the flag `\g_@@_last_col_found_bool`, we will know that the “last column” is really used.

```

2530 \bool_gset_true:N \g_@@_last_col_found_bool
2531 \int_gincr:N \c@jCol
2532 \int_gset_eq:NN \g_@@_col_total_int \c@jCol
```

The contents of the cell is constructed in the box `\l_tmpa_box` because we have to compute some dimensions of this box.

```

2533 \hbox_set:Nw \l_@@_cell_box
2534     \@@_math_toggle_token:
2535     \bool_if:NT \l_@@_small_bool \scriptstyle
```

We insert `\l_@@_code_for_last_col_tl`... but we don’t insert it in the potential “first row” and in the potential “last row”.

```

2536 \int_compare:nNnT \c@iRow > 0
2537 {
2538     \bool_lazy_or:nnT
2539         { \int_compare_p:nNn \l_@@_last_row_int < 0 }
2540         { \int_compare_p:nNn \c@iRow < \l_@@_last_row_int }
2541     {
2542         \l_@@_code_for_last_col_tl
2543         \xglobal \colorlet{nicematrix-last-col}{.}
2544     }
2545 }
2546 }
2547 1
2548 <
2549 {
2550     \@@_math_toggle_token:
2551     \hbox_set_end:
2552     \bool_if:NT \g_@@_rotate_bool \c_@@_rotate_cell_box:
2553     \c_@@_adjust_size_box:
2554     \c_@@_update_for_first_and_last_row:
```

We actualise the width of the “last column” because we will use this width after the construction of the array.

```

2555 \dim_gset:Nn \g_@@_width_last_col_dim
2556     { \dim_max:nn \g_@@_width_last_col_dim { \box_wd:N \l_@@_cell_box } }
2557 \skip_horizontal:N -2\col@sep
```

The content of the cell is inserted in an overlapping position.

```

2558 \hbox_overlap_right:n
2559 {
2560     \dim_compare:nNnT { \box_wd:N \l_@@_cell_box } > \c_zero_dim
2561     {
2562         \skip_horizontal:N \l_@@_right_delim_dim
2563         \skip_horizontal:N \l_@@_right_margin_dim
2564         \skip_horizontal:N \l_@@_extra_right_margin_dim
2565         \@@_node_for_cell:
2566     }
2567 }
2568 \bool_gset_false:N \g_@@_empty_cell_bool
2569 }
2570 }
```

The environment `{NiceArray}` is constructed upon the environment `{NiceArrayWithDelims}` but, in fact, there is a flag `\l_@@_NiceArray_bool`. In `{NiceArrayWithDelims}`, some special code will be executed if this flag is raised.

```

2571 \NewDocumentEnvironment { NiceArray } { }
2572 {
2573     \bool_set_true:N \l_@@_NiceArray_bool
2574     \str_if_empty:NT \g_@@_name_env_str
2575     { \str_gset:Nn \g_@@_name_env_str { NiceArray } }
```

We put `.` and `.` for the delimiters but, in fact, that doesn't matter because these arguments won't be used in `{NiceArrayWithDelims}` (because the flag `\l_@@_NiceArray_bool` is raised).

```

2576     \NiceArrayWithDelims . .
2577 }
2578 { \endNiceArrayWithDelims }
```

We create the variants of the environment `{NiceArrayWithDelims}`.

```

2579 \cs_new_protected:Npn \@@_def_env:nnn #1 #2 #3
2580 {
2581     \NewDocumentEnvironment { #1 NiceArray } { }
2582     {
2583         \str_if_empty:NT \g_@@_name_env_str
2584         { \str_gset:Nn \g_@@_name_env_str { #1 NiceArray } }
2585         \@@_test_if_math_mode:
2586         \NiceArrayWithDelims #2 #3
2587     }
2588     { \endNiceArrayWithDelims }
2589 }
2590 \@@_def_env:nnn p ( )
2591 \@@_def_env:nnn b [ ]
2592 \@@_def_env:nnn B \{ \}
2593 \@@_def_env:nnn v | |
2594 \@@_def_env:nnn V \| \|
```

The environment `{NiceMatrix}` and its variants

```

2595 \cs_new_protected:Npn \@@_begin_of_NiceMatrix:nn #1 #2
2596 {
2597     \bool_set_true:N \l_@@_Matrix_bool
2598     \use:c { #1 NiceArray }
2599     {
2600         *
2601         {
2602             \int_compare:nNnTF \l_@@_last_col_int < 0
```

```

2603         \c@MaxMatrixCols
2604         { \@@_pred:n \l_@@_last_col_int }
2605     }
2606     { > \@@_Cell: #2 < \@@_end_Cell: }
2607   }
2608 }
2609 \clist_map_inline:nn { { } , p , b , B , v , V }
2610 {
2611   \NewDocumentEnvironment { #1 NiceMatrix } { ! O { } }
2612   {
2613     \str_gset:Nn \g_@@_name_env_str { #1 NiceMatrix }
2614     \tl_set:Nn \l_@@_type_of_col_tl c
2615     \keys_set:nn { NiceMatrix / NiceMatrix } { ##1 }
2616     \exp_args:Nne \@@_begin_of_NiceMatrix:nn { #1 } \l_@@_type_of_col_tl
2617   }
2618   { \use:c { end #1 NiceArray } }
2619 }

```

The following command will be linked to \NotEmpty in the environments of `nicematrix`.

```

2620 \cs_new_protected:Npn \@@_NotEmpty:
2621   { \bool_gset_true:N \g_@@_not_empty_cell_bool }

```

The environments `{NiceTabular}` and `{NiceTabular*}`

```

2622 \NewDocumentEnvironment { NiceTabular } { O { } m ! O { } }
2623 {
2624   \str_gset:Nn \g_@@_name_env_str { NiceTabular }
2625   \keys_set:nn { NiceMatrix / NiceTabular } { #1 , #3 }
2626   \bool_set_true:N \l_@@_NiceTabular_bool
2627   \NiceArray { #2 }
2628 }
2629 { \endNiceArray }

2630 \NewDocumentEnvironment { NiceTabular* } { m O { } m ! O { } }
2631 {
2632   \str_gset:Nn \g_@@_name_env_str { NiceTabular* }
2633   \dim_set:Nn \l_@@_tabular_width_dim { #1 }
2634   \keys_set:nn { NiceMatrix / NiceTabular } { #2 , #4 }
2635   \bool_set_true:N \l_@@_NiceTabular_bool
2636   \NiceArray { #3 }
2637 }
2638 { \endNiceArray }

```

After the construction of the array

```

2639 \cs_new_protected:Npn \@@_after_array:
2640   {
2641     \group_begin:

```

When the option `last-col` is used in the environments with explicit preambles (like `{NiceArray}`, `{pNiceArray}`, etc.) a special type of column is used at the end of the preamble in order to compose the cells in an overlapping position (with `\hbox_overlap_right:n`) but (if `last-col` has been used), we don't have the number of that last column. However, we have to know that number for the color of the potential `\Vdots` drawn in that last column. That's why we fix the correct value of `\l_@@_last_col_int` in that case.

```

2642   \bool_if:NT \g_@@_last_col_found_bool
2643     { \int_set_eq:NN \l_@@_last_col_int \g_@@_col_total_int }

```

If we are in an environment without preamble (like `{NiceMatrix}` or `{pNiceMatrix}`) and if the option `last-col` has been used without value we also fix the real value of `\l_@@_last_col_int`.

```

2644   \bool_if:NT \l_@@_last_col_without_value_bool

```

```

2645 { \int_set_eq:NN \l_@@_last_col_int \g_@@_col_total_int }

It's also time to give to \l_@@_last_row_int its real value.
2646 \bool_if:NT \l_@@_last_row_without_value_bool
2647 { \int_set_eq:NN \l_@@_last_row_int \g_@@_row_total_int }

2648 \tl_gput_right:Nx \g_@@_aux_tl
2649 {
2650     \seq_gset_from_clist:Nn \exp_not:N \c_@@_size_seq
2651 {
2652     \int_use:N \l_@@_first_row_int ,
2653     \int_use:N \c@iRow ,
2654     \int_use:N \g_@@_row_total_int ,
2655     \int_use:N \l_@@_first_col_int ,
2656     \int_use:N \c@jCol ,
2657     \int_use:N \g_@@_col_total_int
2658 }
2659 \iow_newline:
2660 }

```

We write also the potential content of \g_@@_pos_of_blocks_seq (it will be useful if the command \rowcolors is used with the key respect-blocks).

```

2661 \seq_if_empty:NF \g_@@_pos_of_blocks_seq
2662 {
2663     \tl_gput_right:Nx \g_@@_aux_tl
2664 {
2665     \seq_gset_from_clist:Nn \exp_not:N \g_@@_pos_of_blocks_seq
2666     { \seq_use:Nnnn \g_@@_pos_of_blocks_seq , , , }
2667     \iow_newline:
2668 }
2669 }
2670 \seq_if_empty:NF \g_@@_multicolumn_cells_seq
2671 {
2672     \tl_gput_right:Nx \g_@@_aux_tl
2673 {
2674     \seq_gset_from_clist:Nn \exp_not:N \g_@@_multicolumn_cells_seq
2675     { \seq_use:Nnnn \g_@@_multicolumn_cells_seq , , , }
2676     \iow_newline:
2677     \seq_gset_from_clist:Nn \exp_not:N \g_@@_multicolumn_sizes_seq
2678     { \seq_use:Nnnn \g_@@_multicolumn_sizes_seq , , , }
2679     \iow_newline:
2680 }
2681 }

```

Now, you create the diagonal nodes by using the `row` nodes and the `col` nodes.

```
2682 \@@_create_diag_nodes:
```

By default, the diagonal lines will be parallelized⁵⁹. There are two types of diagonals lines: the \Ddots diagonals and the \Iddots diagonals. We have to count both types in order to know whether a diagonal is the first of its type in the current {NiceArray} environment.

```

2683 \bool_if:NT \l_@@_parallelize_diags_bool
2684 {
2685     \int_gzero_new:N \g_@@_ddots_int
2686     \int_gzero_new:N \g_@@_iddots_int

```

The dimensions \g_@@_delta_x_one_dim and \g_@@_delta_y_one_dim will contain the Δ_x and Δ_y of the first \Ddots diagonal. We have to store these values in order to draw the others \Ddots diagonals parallel to the first one. Similarly \g_@@_delta_x_two_dim and \g_@@_delta_y_two_dim are the Δ_x and Δ_y of the first \Iddots diagonal.

```

2687     \dim_gzero_new:N \g_@@_delta_x_one_dim
2688     \dim_gzero_new:N \g_@@_delta_y_one_dim
2689     \dim_gzero_new:N \g_@@_delta_x_two_dim

```

⁵⁹It's possible to use the option `parallelize-diags` to disable this parallelization.

```

2690     \dim_gzero_new:N \g_@@_delta_y_two_dim
2691 }
2692 \int_zero_new:N \l_@@_initial_i_int
2693 \int_zero_new:N \l_@@_initial_j_int
2694 \int_zero_new:N \l_@@_final_i_int
2695 \int_zero_new:N \l_@@_final_j_int
2696 \bool_set_false:N \l_@@_initial_open_bool
2697 \bool_set_false:N \l_@@_final_open_bool

```

If the option `small` is used, the values `\l_@@_radius_dim` and `\l_@@_inter_dots_dim` (used to draw the dotted lines created by `\hdottedline` and `\vdotteline` and also for all the other dotted lines when `line-style` is equal to `standard`, which is the initial value) are changed.

```

2698 \bool_if:NT \l_@@_small_bool
2699 {
2700     \dim_set:Nn \l_@@_radius_dim { 0.37 pt }
2701     \dim_set:Nn \l_@@_inter_dots_dim { 0.25 em }

```

The dimension `\l_@@_xdots_shorten_dim` corresponds to the option `xdots/shorten` available to the user. That's why we give a new value according to the current value, and not an absolute value.

```

2702 \dim_set:Nn \l_@@_xdots_shorten_dim { 0.6 \l_@@_xdots_shorten_dim }
2703 }

```

Now, we actually draw the dotted lines (specified by `\Cdots`, `\Vdots`, etc.).

```
2704 \@@_draw_dotted_lines:
```

The following computes the “corners” (made up of empty cells) but if there is no corner to compute, it won't do anything. The corners are computed in `\l_@@_corners_cells_seq` which will contain all the cells which are empty (and not in a block) considered in the corners of the array.

```
2705 \@@_compute_corners:
```

The sequence `\g_@@_pos_of_blocks_seq` must be “adjusted” (for the case where the user have written something like `\Block{1-*}`).

```
2706 \@@_adjust_pos_of_blocks_seq:
```

The following code is only for efficiency. We determine whether the potential horizontal and vertical rules are “complete”, that is to say drawn in the whole array. We are sure that all the rules will be complete when there is no block, no virtual block (determined by a command such as `\Cdots`, `\Vdots`, etc.) and no corners. In that case, we switch to a shortcut version of `\@@_vline_i:nn` and `\@@_hline:nn`.

```

2707 \bool_lazy_all:nT
2708 {
2709     { \seq_if_empty_p:N \g_@@_pos_of_blocks_seq }
2710     { \seq_if_empty_p:N \g_@@_pos_of_xdots_seq }
2711     { \seq_if_empty_p:N \l_@@_corners_cells_seq }
2712 }
2713 {
2714     \cs_set_eq:NN \@@_vline_i:nn \@@_vline_i_complete:nn
2715     \cs_set_eq:NN \@@_hline_i:nn \@@_hline_i_complete:nn
2716 }
2717 \tl_if_empty:NF \l_@@_hlines_clist \@@_draw_hlines:
2718 \tl_if_empty:NF \l_@@_vlines_clist \@@_draw_vlines:
2719 \cs_set_eq:NN \SubMatrix \@@_SubMatrix

```

Now, the internal `code-after` and then, the `\CodeAfter`.

```

2720 \bool_if:NT \c_@@_tikz_loaded_bool
2721 {
2722     \tikzset
2723     {
2724         every~picture / .style =
2725         {
2726             overlay ,

```

```

2727         remember-picture ,
2728         name~prefix = \@@_env: -
2729     }
2730   }
2731 }
2732 \cs_set_eq:NN \line \@@_line
2733 \g_@@_internal_code_after_tl
2734 \tl_gclear:N \g_@@_internal_code_after_tl

```

When `light-syntax` is used, we insert systematically a `\CodeAfter` in the flow. Thus, it's possible to have two instructions `\CodeAfter` and the second may be in `\g_nicematrix_code_after_tl`. That's why we set `\Code-after` to be *no-op* now.

```
2735 \cs_set_eq:NN \CodeAfter \prg_do_nothing:
```

We clear the list of the names of the potential `\SubMatrix` that will appear in the `\CodeAfter` (unfortunately, that list has to be global).

```
2736 \seq_gclear:N \g_@@_submatrix_names_seq
```

We compose the `code-after` in math mode in order to nullify the spaces put by the user between instructions in the `code-after`.

```
2737 % \bool_if:NT \l_@@_NiceTabular_bool \c_math_toggle_token
```

And here's the `\CodeAfter`. Since the `\CodeAfter` may begin with an “argument” between square brackets of the options, we extract and treat that potential “argument” with the command `\@@_CodeAfter_keys`:

```

2738 \exp_last_unbraced:NV \@@_CodeAfter_keys: \g_nicematrix_code_after_tl
2739 \scan_stop:
2740 % \bool_if:NT \l_@@_NiceTabular_bool \c_math_toggle_token
2741 \tl_gclear:N \g_nicematrix_code_after_tl
2742 \group_end:

```

`\g_nicematrix_code_before_tl` is for instructions in the cells of the array such as `\rowcolor` and `\cellcolor` (when the key `colortbl-like` is in force). These instructions will be written on the `aux` file to be added to the `code-before` in the next run.

```

2743 \tl_if_empty:NF \g_nicematrix_code_before_tl
2744 {

```

The command `\rowcolor` in tabular will in fact use `\rectanglecolor` in order to follow the behaviour of `\rowcolor` of `colortbl`. That's why there may be a command `\rectanglecolor` in `\g_nicematrix_code_before_tl`. In order to avoid an error during the expansion, we define a protected version of `\rectanglecolor`.

```

2745 \cs_set_protected:Npn \rectanglecolor { }
2746 \cs_set_protected:Npn \columncolor { }
2747 \tl_gput_right:Nx \g_@@_aux_tl
2748 {
2749   \tl_gset:Nn \exp_not:N \g_@@_code_before_tl
2750   { \exp_not:V \g_nicematrix_code_before_tl }
2751   \iow_newline:
2752 }
2753 \bool_set_true:N \l_@@_code_before_bool
2754 }
2755 % \bool_if:NT \l_@@_code_before_bool \@@_write_aux_for_cell_nodes:

2756 \str_gclear:N \g_@@_name_env_str
2757 \@@_restore_iRow_jCol:

```

The command `\CT@arc@` contains the instruction of color for the rules of the array⁶⁰. This command is used by `\CT@arc@` but we use it also for compatibility with `colortbl`. But we want also to be able to use color for the rules of the array when `colortbl` is *not* loaded. That's why we do the following instruction which is in the patch of the end of arrays done by `colortbl`.

```

2758 \cs_gset_eq:NN \CT@arc@ \@@_old_CT@arc@
2759 }

```

⁶⁰e.g. `\color[rgb]{0.5,0.5,0}`

The following command will extract the potential options (between square brackets) at the beginning of the `\CodeAfter` (that is to say, when `\CodeAfter` is used, the options of that “command” `\CodeAfter`). Idem for the `\CodeBefore`.

```
2760 \NewDocumentCommand \@@_CodeAfter_keys: { 0 { } }
2761   { \keys_set:nn { NiceMatrix / CodeAfter } { #1 } }
```

We remind that the first mandatory argument of the command `\Block` is the size of the block with the special format $i-j$. However, the user is allowed to omit i or j (or both). This will be interpreted as: the last row (resp. column) of the block will be the last row (resp. column) of the block (without the potential exterior row—resp. column—of the array). By convention, this is stored in `\g_@@_pos_of_blocks_seq` (and `\g_@@_blocks_seq`) as a number of rows (resp. columns) for the block equal to 100. It’s possible, after the construction of the array, to replace these values by the correct ones (since we know the number of rows and columns of the array).

```
2762 \cs_new_protected:Npn \@@_adjust_pos_of_blocks_seq:
2763   {
2764     \seq_gset_map_x:NNn \g_@@_pos_of_blocks_seq \g_@@_pos_of_blocks_seq
2765     { \@@_adjust_pos_of_blocks_seq_i:nnnn ##1 }
2766   }
```

The following command must *not* be protected.

```
2767 \cs_new:Npn \@@_adjust_pos_of_blocks_seq_i:nnnn #1 #2 #3 #4
2768   {
2769     { #1 }
2770     { #2 }
2771     {
2772       \int_compare:nNnTF { #3 } > { 99 }
2773         { \int_use:N \c@iRow }
2774         { #3 }
2775     }
2776     {
2777       \int_compare:nNnTF { #4 } > { 99 }
2778         { \int_use:N \c@jCol }
2779         { #4 }
2780     }
2781 }
```

We recall that, when externalization is used, `\tikzpicture` and `\endtikzpicture` (or `\pgfpicture` and `\endpgfpicture`) must be directly “visible”. That’s why we have to define the adequate version of `\@@_draw_dotted_lines`: whether Tikz is loaded or not (in that case, only PGF is loaded).

```
2782 \AtBeginDocument
2783   {
2784     \cs_new_protected:Npx \@@_draw_dotted_lines:
2785     {
2786       \c_@@_pgfortikzpicture_tl
2787       \@@_draw_dotted_lines_i:
2788       \c_@@_endpgfortikzpicture_tl
2789     }
2790 }
```

The following command *must* be protected because it will appear in the construction of the command `\@@_draw_dotted_lines`:

```
2791 \cs_new_protected:Npn \@@_draw_dotted_lines_i:
2792   {
2793     \pgfrememberpicturepositiononpagetrue
2794     \pgf@relevantforpicturesizefalse
2795     \g_@@_Hdotsfor_lines_tl
2796     \g_@@_Vdots_lines_tl
2797     \g_@@_Ddots_lines_tl
2798     \g_@@_Iddots_lines_tl
2799     \g_@@_Cdots_lines_tl
2800     \g_@@_Ldots_lines_tl
2801 }
```

```

2802 \cs_new_protected:Npn \@@_restore_iRow_jCol:
2803 {
2804     \cs_if_exist:NT \theiRow { \int_gset_eq:NN \c@iRow \l_@@_old_iRow_int }
2805     \cs_if_exist:NT \thejCol { \int_gset_eq:NN \c@jCol \l_@@_old_jCol_int }
2806 }
2807
2808 \pgfdeclareshape { @@_diag_node }
2809 {
2810     \savedanchor {\five}
2811     {
2812         \dim_gset_eq:NN \pgf@x \l_tmpa_dim
2813         \dim_gset_eq:NN \pgf@y \l_tmpb_dim
2814     }
2815     \anchor { 5 } { \five }
2816     \anchor { center } { \pgfpointorigin }
2817 }
2818
2819 \cs_new_protected:Npn \@@_write_aux_for_cell_nodes:
2820 {
2821     \pgfpicture
2822     \pgfrememberpicturepositiononpagetrue
2823     \pgf@relevantforpicturesizefalse
2824     \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
2825     {
2826         \int_step_inline:nnn \l_@@_first_col_int \g_@@_col_total_int
2827         {
2828             \cs_if_exist:cT { pgf @ sh @ ns @ \@@_env: - ##1 - #####1 }
2829             {
2830                 \pgfscope
2831                 \pgftransformshift
2832                     { \pgfpointanchor { \@@_env: - ##1 - #####1 } { north-west } }
2833                 \pgfnode
2834                     { rectangle }
2835                     { center }
2836                     {
2837                         \hbox
2838                             { \pgfsys@markposition { \@@_env: - ##1 - #####1 - NW } }
2839                     }
2840                     {
2841                     }
2842                     {
2843                     }
2844                 \endpgfscope
2845                 \pgfscope
2846                 \pgftransformshift
2847                     { \pgfpointanchor { \@@_env: - ##1 - #####1 } { south-east } }
2848                 \pgfnode
2849                     { rectangle }
2850                     { center }
2851                     {
2852                         \hbox
2853                             { \pgfsys@markposition { \@@_env: - ##1 - #####1 - SE } }
2854                     }
2855                     {
2856                     }
2857                     {
2858                     }
2859                 \endpgfscope
2860             }
2861         }
2862     }
2863     \endpgfpicture
2864     \@@_create_extra_nodes:
2865 }
2866 % \end{macrocode}

```

```

2861 %
2862 % \bigskip
2863 % The following command creates the diagonal nodes (in fact, if the matrix is
2864 % not a square matrix, not all the nodes are on the diagonal).
2865 % \begin{macrocode}
2866 \cs_new_protected:Npn \@@_create_diag_nodes:
2867 {
2868   \pgfpicture
2869   \pgfrememberpicturepositiononpagetrue
2870   \int_step_inline:nn { \int_max:nn \c@iRow \c@jCol }
2871   {
2872     \@@_qpoint:n { col - \int_min:nn { ##1 } { \c@jCol + 1 } }
2873     \dim_set_eq:NN \l_tmpa_dim \pgf@x
2874     \@@_qpoint:n { row - \int_min:nn { ##1 } { \c@iRow + 1 } }
2875     \dim_set_eq:NN \l_tmpb_dim \pgf@y
2876     \@@_qpoint:n { col - \int_min:nn { ##1 + 1 } { \c@jCol + 1 } }
2877     \dim_set_eq:NN \l_tmpc_dim \pgf@x
2878     \@@_qpoint:n { row - \int_min:nn { ##1 + 1 } { \c@iRow + 1 } }
2879     \dim_set_eq:NN \l_tmpd_dim \pgf@y
2880     \pgftransformshift { \pgfpoint \l_tmpa_dim \l_tmpb_dim }

```

Now, `\l_tmpa_dim` and `\l_tmpb_dim` become the width and the height of the node (of shape `\@_diag_node`) that we will construct.

```

2881   \dim_set:Nn \l_tmpa_dim { ( \l_tmpc_dim - \l_tmpa_dim ) / 2 }
2882   \dim_set:Nn \l_tmpb_dim { ( \l_tmpd_dim - \l_tmpb_dim ) / 2 }
2883   \pgfnode { @_diag_node } { center } { } { \@@_env: - ##1 } { }
2884 }

```

Now, the last node. Of course, that is only a coordinate because there is not `.5` anchor for that node.

```

2885 \int_set:Nn \l_tmpa_int { \int_max:nn \c@iRow \c@jCol + 1 }
2886 \@@_qpoint:n { row - \int_min:nn { \l_tmpa_int } { \c@iRow + 1 } }
2887 \dim_set_eq:NN \l_tmpa_dim \pgf@y
2888 \@@_qpoint:n { col - \int_min:nn { \l_tmpa_int } { \c@jCol + 1 } }
2889 \pgfcoordinate
2890   { \@@_env: - \int_use:N \l_tmpa_int } { \pgfpoint \pgf@x \l_tmpa_dim }
2891 \pgfnodealias
2892   { \@@_env: - last }
2893   { \@@_env: - \int_eval:n { \int_max:nn \c@iRow \c@jCol + 1 } }
2894 \endpgfpicture
2895 }

```

We draw the dotted lines

A dotted line will be said *open* in one of its extremities when it stops on the edge of the matrix and *closed* otherwise. In the following matrix, the dotted line is closed on its left extremity and open on its right.

$$\begin{pmatrix} a+b+c & a+b & a \\ a & \dots & \dots \\ a & a+b & a+b+c \end{pmatrix}$$

The command `\@@_find_extremities_of_line:nnnn` takes four arguments:

- the first argument is the row of the cell where the command was issued;
- the second argument is the column of the cell where the command was issued;
- the third argument is the *x*-value of the orientation vector of the line;
- the fourth argument is the *y*-value of the orientation vector of the line.

This command computes:

- `\l_@@_initial_i_int` and `\l_@@_initial_j_int` which are the coordinates of one extremity of the line;
- `\l_@@_final_i_int` and `\l_@@_final_j_int` which are the coordinates of the other extremity of the line;
- `\l_@@_initial_open_bool` and `\l_@@_final_open_bool` to indicate whether the extremities are open or not.

```
2896 \cs_new_protected:Npn \@@_find_extremities_of_line:n #1 #2 #3 #4
2897 {
```

First, we declare the current cell as “dotted” because we forbide intersections of dotted lines.

```
2898 \cs_set:cpn { @@ _ dotted _ #1 - #2 } { }
```

Initialization of variables.

```
2899 \int_set:Nn \l_@@_initial_i_int { #1 }
2900 \int_set:Nn \l_@@_initial_j_int { #2 }
2901 \int_set:Nn \l_@@_final_i_int { #1 }
2902 \int_set:Nn \l_@@_final_j_int { #2 }
```

We will do two loops: one when determinating the initial cell and the other when determinating the final cell. The boolean `\l_@@_stop_loop_bool` will be used to control these loops. In the first loop, we search the “final” extremity of the line.

```
2903 \bool_set_false:N \l_@@_stop_loop_bool
2904 \bool_do_until:Nn \l_@@_stop_loop_bool
2905 {
2906     \int_add:Nn \l_@@_final_i_int { #3 }
2907     \int_add:Nn \l_@@_final_j_int { #4 }
```

We test if we are still in the matrix.

```
2908 \bool_set_false:N \l_@@_final_open_bool
2909 \int_compare:nNnTF \l_@@_final_i_int > \l_@@_row_max_int
2910 {
2911     \int_compare:nNnTF { #3 } = 1
2912     { \bool_set_true:N \l_@@_final_open_bool }
2913     {
2914         \int_compare:nNnT \l_@@_final_j_int > \l_@@_col_max_int
2915         { \bool_set_true:N \l_@@_final_open_bool }
2916     }
2917 }
2918 {
2919     \int_compare:nNnTF \l_@@_final_j_int < \l_@@_col_min_int
2920     {
2921         \int_compare:nNnT { #4 } = { -1 }
2922         { \bool_set_true:N \l_@@_final_open_bool }
2923     }
2924 {
2925     \int_compare:nNnT \l_@@_final_j_int > \l_@@_col_max_int
2926     {
2927         \int_compare:nNnT { #4 } = 1
2928         { \bool_set_true:N \l_@@_final_open_bool }
2929     }
2930 }
2931 }
2932 \bool_if:NTF \l_@@_final_open_bool
```

If we are outside the matrix, we have found the extremity of the dotted line and it's an *open* extremity.

```
2933 {
```

We do a step backwards.

```
2934 \int_sub:Nn \l_@@_final_i_int { #3 }
2935 \int_sub:Nn \l_@@_final_j_int { #4 }
2936 \bool_set_true:N \l_@@_stop_loop_bool
2937 }
```

If we are in the matrix, we test whether the cell is empty. If it's not the case, we stop the loop because we have found the correct values for `\l_@@_final_i_int` and `\l_@@_final_j_int`.

```

2938 {
2939   \cs_if_exist:cTF
2940   {
2941     @@ _ dotted _
2942     \int_use:N \l_@@_final_i_int -
2943     \int_use:N \l_@@_final_j_int
2944   }
2945   {
2946     \int_sub:Nn \l_@@_final_i_int { #3 }
2947     \int_sub:Nn \l_@@_final_j_int { #4 }
2948     \bool_set_true:N \l_@@_final_open_bool
2949     \bool_set_true:N \l_@@_stop_loop_bool
2950   }
2951   {
2952     \cs_if_exist:cTF
2953     {
2954       pgf @ sh @ ns @ \@@_env:
2955       - \int_use:N \l_@@_final_i_int
2956       - \int_use:N \l_@@_final_j_int
2957     }
2958     { \bool_set_true:N \l_@@_stop_loop_bool }
```

If the case is empty, we declare that the cell as non-empty. Indeed, we will draw a dotted line and the cell will be on that dotted line. All the cells of a dotted line have to be marked as “dotted” because we don't want intersections between dotted lines. We recall that the research of the extremities of the lines are all done in the same TeX group (the group of the environment), even though, when the extremities are found, each line is drawn in a TeX group that we will open for the options of the line.

```

2959   {
2960     \cs_set:cpn
2961     {
2962       @@ _ dotted _
2963       \int_use:N \l_@@_final_i_int -
2964       \int_use:N \l_@@_final_j_int
2965     }
2966     { }
2967   }
2968 }
2969 }
2970 }
```

For `\l_@@_initial_i_int` and `\l_@@_initial_j_int` the programmation is similar to the previous one.

```

2971 \bool_set_false:N \l_@@_stop_loop_bool
2972 \bool_do_until:Nn \l_@@_stop_loop_bool
2973 {
2974   \int_sub:Nn \l_@@_initial_i_int { #3 }
2975   \int_sub:Nn \l_@@_initial_j_int { #4 }
2976   \bool_set_false:N \l_@@_initial_open_bool
2977   \int_compare:nNnTF \l_@@_initial_i_int < \l_@@_row_min_int
2978   {
2979     \int_compare:nNnTF { #3 } = 1
2980     { \bool_set_true:N \l_@@_initial_open_bool }
2981     {
2982       \int_compare:nNnT \l_@@_initial_j_int = { \l_@@_col_min_int -1 }
2983       { \bool_set_true:N \l_@@_initial_open_bool }
2984     }
2985   }
2986   {
2987     \int_compare:nNnTF \l_@@_initial_j_int < \l_@@_col_min_int
2988     { }
```

```

2989         \int_compare:nNnT { #4 } = 1
2990             { \bool_set_true:N \l_@@_initial_open_bool }
2991     }
2992     {
2993         \int_compare:nNnT \l_@@_initial_j_int > \l_@@_col_max_int
2994             {
2995                 \int_compare:nNnT { #4 } = { -1 }
2996                     { \bool_set_true:N \l_@@_initial_open_bool }
2997             }
2998     }
2999 }
3000 \bool_if:NTF \l_@@_initial_open_bool
3001 {
3002     \int_add:Nn \l_@@_initial_i_int { #3 }
3003     \int_add:Nn \l_@@_initial_j_int { #4 }
3004     \bool_set_true:N \l_@@_stop_loop_bool
3005 }
3006 {
3007     \cs_if_exist:cTF
3008     {
3009         @@ _ dotted _
3010         \int_use:N \l_@@_initial_i_int -
3011         \int_use:N \l_@@_initial_j_int
3012     }
3013 {
3014     \int_add:Nn \l_@@_initial_i_int { #3 }
3015     \int_add:Nn \l_@@_initial_j_int { #4 }
3016     \bool_set_true:N \l_@@_initial_open_bool
3017     \bool_set_true:N \l_@@_stop_loop_bool
3018 }
3019 {
3020     \cs_if_exist:cTF
3021     {
3022         pgf @ sh @ ns @ \@@_env:
3023             - \int_use:N \l_@@_initial_i_int
3024             - \int_use:N \l_@@_initial_j_int
3025     }
3026     \bool_set_true:N \l_@@_stop_loop_bool
3027     {
3028         \cs_set:cpn
3029         {
3030             @@ _ dotted _
3031             \int_use:N \l_@@_initial_i_int -
3032             \int_use:N \l_@@_initial_j_int
3033         }
3034         { }
3035     }
3036 }
3037 }
3038 }

```

We remind the rectangle described by all the dotted lines in order to respect the corresponding virtual “block” when drawing the horizontal and vertical rules.

```

3039 \seq_gput_right:Nx \g_@@_pos_of_xdots_seq
3040 {
3041     { \int_use:N \l_@@_initial_i_int }
3042     { \int_use:N \l_@@_initial_j_int }
3043     { \int_use:N \l_@@_final_i_int }
3044     { \int_use:N \l_@@_final_j_int }
3045 }
3046 }

```

The following command (*when it will be written*) will set the four counters $\l_@@_row_min_int$, $\l_@@_row_max_int$, $\l_@@_col_min_int$ and $\l_@@_col_max_int$ to the intersections of the sub-

matrices which contains the cell of row #1 and column #2. As of now, it's only the whole array (excepted exterior rows and columns).

```

3047 \cs_new_protected:Npn \@@_adjust_to_submatrix:nn #1 #2
3048 {
3049     \int_set:Nn \l_@@_row_min_int 1
3050     \int_set:Nn \l_@@_col_min_int 1
3051     \int_set_eq:NN \l_@@_row_max_int \c@iRow
3052     \int_set_eq:NN \l_@@_col_max_int \c@jCol

```

We do a loop over all the submatrices specified in the `code-before`. We have stored the position of all those submatrices in `\g_@@_submatrix_seq`.

```

3053 \seq_map_inline:Nn \g_@@_submatrix_seq
3054     { \@@_adjust_to_submatrix:nnnnnn { #1 } { #2 } ##1 }
3055 }

```

#1 and #2 are the numbers of row and columns of the cell where the command of dotted line (ex.: `\Vdots`) has been issued. #3, #4, #5 and #6 are the specification (in i and j) of the submatrix where are analysing.

```

3056 \cs_set_protected:Npn \@@_adjust_to_submatrix:nnnnnn #1 #2 #3 #4 #5 #6
3057 {
3058     \bool_if:nT
3059     {
3060         \int_compare_p:n { #3 <= #1 }
3061         && \int_compare_p:n { #1 <= #5 }
3062         && \int_compare_p:n { #4 <= #2 }
3063         && \int_compare_p:n { #2 <= #6 }
3064     }
3065     {
3066         \int_set:Nn \l_@@_row_min_int { \int_max:nn \l_@@_row_min_int { #3 } }
3067         \int_set:Nn \l_@@_col_min_int { \int_max:nn \l_@@_col_min_int { #4 } }
3068         \int_set:Nn \l_@@_row_max_int { \int_min:nn \l_@@_row_max_int { #5 } }
3069         \int_set:Nn \l_@@_col_max_int { \int_min:nn \l_@@_col_max_int { #6 } }
3070     }
3071 }

3072 \cs_new_protected:Npn \@@_set_initial_coords:
3073 {
3074     \dim_set_eq:NN \l_@@_x_initial_dim \pgf@x
3075     \dim_set_eq:NN \l_@@_y_initial_dim \pgf@y
3076 }
3077 \cs_new_protected:Npn \@@_set_final_coords:
3078 {
3079     \dim_set_eq:NN \l_@@_x_final_dim \pgf@x
3080     \dim_set_eq:NN \l_@@_y_final_dim \pgf@y
3081 }
3082 \cs_new_protected:Npn \@@_set_initial_coords_from_anchor:n #1
3083 {
3084     \pgfpointanchor
3085     {
3086         \@@_env:
3087         - \int_use:N \l_@@_initial_i_int
3088         - \int_use:N \l_@@_initial_j_int
3089     }
3090     { #1 }
3091     \@@_set_initial_coords:
3092 }
3093 \cs_new_protected:Npn \@@_set_final_coords_from_anchor:n #1
3094 {
3095     \pgfpointanchor
3096     {
3097         \@@_env:
3098         - \int_use:N \l_@@_final_i_int
3099         - \int_use:N \l_@@_final_j_int

```

```

3100      }
3101      { #1 }
3102      \@@_set_final_coords:
3103  }

3104 \cs_new_protected:Npn \@@_open_x_initial_dim:
3105  {
3106      \dim_set_eq:NN \l_@@_x_initial_dim \c_max_dim
3107      \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
3108      {
3109          \cs_if_exist:cT
3110          { pgf @ sh @ ns @ \@@_env: - ##1 - \int_use:N \l_@@_initial_j_int }
3111          {
3112              \pgfpointanchor
3113              { \@@_env: - ##1 - \int_use:N \l_@@_initial_j_int }
3114              { west }
3115              \dim_set:Nn \l_@@_x_initial_dim
3116              { \dim_min:nn \l_@@_x_initial_dim \pgf@x }
3117          }
3118      }
3119 }

```

If, in fact, all the cells of the columns are empty (no PGF/Tikz nodes in those cells).

```

3119 \dim_compare:nNnT \l_@@_x_initial_dim = \c_max_dim
3120  {
3121      \@@_qpoint:n { col - \int_use:N \l_@@_initial_j_int }
3122      \dim_set_eq:NN \l_@@_x_initial_dim \pgf@x
3123      \dim_add:Nn \l_@@_x_initial_dim \col@sep
3124  }
3125 }

3126 \cs_new_protected:Npn \@@_open_x_final_dim:
3127  {
3128      \dim_set:Nn \l_@@_x_final_dim { - \c_max_dim }
3129      \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
3130      {
3131          \cs_if_exist:cT
3132          { pgf @ sh @ ns @ \@@_env: - ##1 - \int_use:N \l_@@_final_j_int }
3133          {
3134              \pgfpointanchor
3135              { \@@_env: - ##1 - \int_use:N \l_@@_final_j_int }
3136              { east }
3137              \dim_set:Nn \l_@@_x_final_dim
3138              { \dim_max:nn \l_@@_x_final_dim \pgf@x }
3139          }
3140      }
3141 }

```

If, in fact, all the cells of the columns are empty (no PGF/Tikz nodes in those cells).

```

3141 \dim_compare:nNnT \l_@@_x_final_dim = { - \c_max_dim }
3142  {
3143      \@@_qpoint:n { col - \@@_succ:n \l_@@_final_j_int }
3144      \dim_set_eq:NN \l_@@_x_final_dim \pgf@x
3145      \dim_sub:Nn \l_@@_x_final_dim \col@sep
3146  }
3147 }

```

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```

3148 \cs_new_protected:Npn \@@_draw_Ldots:nnn #1 #2 #3
3149  {
3150      \@@_adjust_to_submatrix:nn { #1 } { #2 }
3151      \cs_if_free:cT { @@ _ dotted _ #1 - #2 }
3152      {
3153          \@@_find_extremities_of_line:nnnn { #1 } { #2 } 0 1

```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```
3154     \group_begin:
3155         \int_compare:nNnT { #1 } = 0
3156             { \color { nicematrix-first-row } }
3157             {
```

We remind that, when there is a “last row” $\l_@_last_row_int$ will always be (after the construction of the array) the number of that “last row” even if the option `last-row` has been used without value.

```
3158     \int_compare:nNnT { #1 } = \l_@_last_row_int
3159         { \color { nicematrix-last-row } }
3160     }
3161     \keys_set:nn { NiceMatrix / xdots } { #3 }
3162     \tl_if_empty:VF \l_@_xdots_color_tl { \color { \l_@_xdots_color_tl } }
3163     \@@_actually_draw_Ldots:
3164     \group_end:
3165 }
3166 }
```

The command `\@@_actually_draw_Ldots:` has the following implicit arguments:

- $\l_@_initial_i_int$
- $\l_@_initial_j_int$
- $\l_@_initial_open_bool$
- $\l_@_final_i_int$
- $\l_@_final_j_int$
- $\l_@_final_open_bool$.

The following function is also used by `\Hdotsfor`.

```
3167 \cs_new_protected:Npn \@@_actually_draw_Ldots:
3168 {
3169     \bool_if:NTF \l_@_initial_open_bool
3170     {
3171         \@@_open_x_initial_dim:
3172         \@@_qpoint:n { row - \int_use:N \l_@_initial_i_int - base }
3173         \dim_set_eq:NN \l_@_y_initial_dim \pgf@y
3174     }
3175     { \@@_set_initial_coords_from_anchor:n { base-east } }
3176     \bool_if:NTF \l_@_final_open_bool
3177     {
3178         \@@_open_x_final_dim:
3179         \@@_qpoint:n { row - \int_use:N \l_@_final_i_int - base }
3180         \dim_set_eq:NN \l_@_y_final_dim \pgf@y
3181     }
3182     { \@@_set_final_coords_from_anchor:n { base-west } }
```

We raise the line of a quantity equal to the radius of the dots because we want the dots really “on” the line of text. Of course, maybe we should not do that when the option `line-style` is used (?).

```
3183     \dim_add:Nn \l_@_y_initial_dim \l_@_radius_dim
3184     \dim_add:Nn \l_@_y_final_dim \l_@_radius_dim
3185     \@@_draw_line:
3186 }
```

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```
3187 \cs_new_protected:Npn \@@_draw_Cdots:nnn #1 #2 #3
3188 {
3189     \@@_adjust_to_submatrix:nn { #1 } { #2 }
3190     \cs_if_free:cT { @_ dotted _ #1 - #2 }
3191     {
3192         \@@_find_extremities_of_line:nnnn { #1 } { #2 } 0 1
```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```
3193     \group_begin:
3194         \int_compare:nNnTF { #1 } = 0
3195             { \color { nicematrix-first-row } }
3196             {
```

We remind that, when there is a “last row” $\l_@@_last_row_int$ will always be (after the construction of the array) the number of that “last row” even if the option `last-row` has been used without value.

```
3197         \int_compare:nNnT { #1 } = \l_@@_last_row_int
3198             { \color { nicematrix-last-row } }
3199             }
3200             \keys_set:nn { NiceMatrix / xdots } { #3 }
3201                 \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
3202                     \@@_actually_draw_Cdots:
3203             \group_end:
3204             }
3205 }
```

The command `\@@_actually_draw_Cdots:` has the following implicit arguments:

- $\l_@@_initial_i_int$
- $\l_@@_initial_j_int$
- $\l_@@_initial_open_bool$
- $\l_@@_final_i_int$
- $\l_@@_final_j_int$
- $\l_@@_final_open_bool$.

```
3206 \cs_new_protected:Npn \@@_actually_draw_Cdots:
3207 {
3208     \bool_if:NTF \l_@@_initial_open_bool
3209         { \@@_open_x_initial_dim: }
3210         { \@@_set_initial_coords_from_anchor:n { mid-east } }
3211     \bool_if:NTF \l_@@_final_open_bool
3212         { \@@_open_x_final_dim: }
3213         { \@@_set_final_coords_from_anchor:n { mid-west } }
3214     \bool_lazy_and:nnTF
3215         { \l_@@_initial_open_bool
3216         \l_@@_final_open_bool
3217         {
3218             \@@_qpoint:n { row - \int_use:N \l_@@_initial_i_int }
3219             \dim_set_eq:NN \l_tmpa_dim \pgf@y
3220             \@@_qpoint:n { row - \@@_succ:n \l_@@_initial_i_int }
3221             \dim_set:Nn \l_@@_y_initial_dim { ( \l_tmpa_dim + \pgf@y ) / 2 }
3222             \dim_set_eq:NN \l_@@_y_final_dim \l_@@_y_initial_dim
3223         }
3224         {
3225             \bool_if:NT \l_@@_initial_open_bool
3226                 { \dim_set_eq:NN \l_@@_y_initial_dim \l_@@_y_final_dim }
3227             \bool_if:NT \l_@@_final_open_bool
3228                 { \dim_set_eq:NN \l_@@_y_final_dim \l_@@_y_initial_dim }
3229         }
3230     \@@_draw_line:
3231 }
```

```
3232 \cs_new_protected:Npn \@@_open_y_initial_dim:
3233 {
3234     \@@_qpoint:n { row - \int_use:N \l_@@_initial_i_int - base }
3235     \dim_set:Nn \l_@@_y_initial_dim
3236         { \pgf@y + ( \box_ht:N \strutbox + \extrarowheight ) * \arraystretch }
3237     \int_step_inline:nnn \l_@@_first_col_int \g_@@_col_total_int
```

```

3238     {
3239         \cs_if_exist:cT
3240             { pgf @ sh @ ns @ \@@_env: - \int_use:N \l_@@_initial_i_int - ##1 }
3241             {
3242                 \pgfpointanchor
3243                     { \@@_env: - \int_use:N \l_@@_initial_i_int - ##1 }
3244                     { north }
3245                 \dim_set:Nn \l_@@_y_initial_dim
3246                     { \dim_max:nn \l_@@_y_initial_dim \pgf@y }
3247             }
3248         }
3249     }
3250 \cs_new_protected:Npn \@@_open_y_final_dim:
3251     {
3252         \@@_qpoint:n { row - \int_use:N \l_@@_final_i_int - base }
3253         \dim_set:Nn \l_@@_y_final_dim
3254             { \pgf@y - ( \box_dp:N \strutbox ) * \arraystretch }
3255         \int_step_inline:nnn \l_@@_first_col_int \g_@@_col_total_int
3256             {
3257                 \cs_if_exist:cT
3258                     { pgf @ sh @ ns @ \@@_env: - \int_use:N \l_@@_final_i_int - ##1 }
3259                     {
3260                         \pgfpointanchor
3261                             { \@@_env: - \int_use:N \l_@@_final_i_int - ##1 }
3262                             { south }
3263                         \dim_set:Nn \l_@@_y_final_dim
3264                             { \dim_min:nn \l_@@_y_final_dim \pgf@y }
3265                     }
3266                 }
3267             }
3268     }

```

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```

3268 \cs_new_protected:Npn \@@_draw_Vdots:nnn #1 #2 #3
3269     {
3270         \@@_adjust_to_submatrix:nn { #1 } { #2 }
3271         \cs_if_free:cT { @_ dotted _ #1 - #2 }
3272             {
3273                 \@@_find_extremities_of_line:nnnn { #1 } { #2 } 1 0

```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```

3274     \group_begin:
3275         \int_compare:nNnTF { #2 } = 0
3276             { \color { nicematrix-first-col } }
3277             {
3278                 \int_compare:nNnT { #2 } = \l_@@_last_col_int
3279                     { \color { nicematrix-last-col } }
3280             }
3281             \keys_set:nn { NiceMatrix / xdots } { #3 }
3282             \tl_if_empty:VF \l_@@_xdots_color_tl
3283                 { \color { \l_@@_xdots_color_tl } }
3284             \@@_actually_draw_Vdots:
3285             \group_end:
3286         }
3287     }

```

The command `\@@_actually_draw_Vdots:` has the following implicit arguments:

- `\l_@@_initial_i_int`
- `\l_@@_initial_j_int`
- `\l_@@_initial_open_bool`

- `\l_@@_final_i_int`
- `\l_@@_final_j_int`
- `\l_@@_final_open_bool.`

The following function is also used by `\Vdotsfor`.

```
3288 \cs_new_protected:Npn \@@_actually_draw_Vdots:
3289 {
```

The boolean `\l_tmpa_bool` indicates whether the column is of type 1 or may be considered as if.

```
3290 \bool_set_false:N \l_tmpa_bool
```

First the case when the line is closed on both ends.

```
3291 \bool_lazy_or:nnF \l_@@_initial_open_bool \l_@@_final_open_bool
3292 {
3293     \@@_set_initial_coords_from_anchor:n { south-west }
3294     \@@_set_final_coords_from_anchor:n { north-west }
3295     \bool_set:Nn \l_tmpa_bool
3296         { \dim_compare_p:nNn \l_@@_x_initial_dim = \l_@@_x_final_dim }
3297 }
```

Now, we try to determine whether the column is of type c or may be considered as if.

```
3298 \bool_if:NTF \l_@@_initial_open_bool
3299     \@@_open_y_initial_dim:
3300     { \@@_set_initial_coords_from_anchor:n { south } }
3301 \bool_if:NTF \l_@@_final_open_bool
3302     \@@_open_y_final_dim:
3303     { \@@_set_final_coords_from_anchor:n { north } }
3304 \bool_if:NTF \l_@@_initial_open_bool
3305 {
3306     \bool_if:NTF \l_@@_final_open_bool
3307     {
3308         \@@_qpoint:n { col - \int_use:N \l_@@_initial_j_int }
3309         \dim_set_eq:NN \l_tmpa_dim \pgf@x
3310         \@@_qpoint:n { col - \@@_succ:n \l_@@_initial_j_int }
3311         \dim_set:Nn \l_@@_x_initial_dim { ( \pgf@x + \l_tmpa_dim ) / 2 }
3312         \dim_set_eq:NN \l_@@_x_final_dim \l_@@_x_initial_dim
```

We may think that the final user won't use a "last column" which contains only a command `\Vdots`. However, if the `\Vdots` is in fact used to draw, not a dotted line, but an arrow (to indicate the number of rows of the matrix), it may be really encountered.

```
3313 \int_compare:nNnT \l_@@_last_col_int > { -2 }
3314 {
3315     \int_compare:nNnT \l_@@_initial_j_int = \g_@@_col_total_int
3316     {
3317         \dim_set_eq:NN \l_tmpa_dim \l_@@_right_margin_dim
3318         \dim_add:Nn \l_tmpa_dim \l_@@_extra_right_margin_dim
3319         \dim_add:Nn \l_@@_x_initial_dim \l_tmpa_dim
3320         \dim_add:Nn \l_@@_x_final_dim \l_tmpa_dim
3321     }
3322 }
3323 {
3324     \dim_set_eq:NN \l_@@_x_initial_dim \l_@@_x_final_dim
3325 }
3326 {
3327     \bool_if:NTF \l_@@_final_open_bool
3328     {
3329         \dim_set_eq:NN \l_@@_x_final_dim \l_@@_x_initial_dim
3330     }
```

Now the case where both extremities are closed. The first conditional tests whether the column is of type c or may be considered as if.

```
3330 \dim_compare:nNnF \l_@@_x_initial_dim = \l_@@_x_final_dim
3331 {
3332     \dim_set:Nn \l_@@_x_initial_dim
3333     {
```

```

3334         \bool_if:NTF \l_tmpa_bool \dim_min:nn \dim_max:nn
3335             \l_@@_x_initial_dim \l_@@_x_final_dim
3336         }
3337     \dim_set_eq:NN \l_@@_x_final_dim \l_@@_x_initial_dim
3338   }
3339 }
3340 }
3341 \@@_draw_line:
3342 }
```

For the diagonal lines, the situation is a bit more complicated because, by default, we parallelize the diagonals lines. The first diagonal line is drawn and then, all the other diagonal lines are drawn parallel to the first one.

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```

3343 \cs_new_protected:Npn \@@_draw_Ddots:nnn #1 #2 #3
3344 {
3345     \@@_adjust_to_submatrix:nn { #1 } { #2 }
3346     \cs_if_free:cT { @ _ dotted _ #1 - #2 }
3347     {
3348         \@@_find_extremities_of_line:nnnn { #1 } { #2 } 1 1
```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```

3349     \group_begin:
3350         \keys_set:nn { NiceMatrix / xdots } { #3 }
3351         \tl_if_empty:VF \l_@@_xdots_color_t1 { \color { \l_@@_xdots_color_t1 } }
3352         \@@_actually_draw_Ddots:
3353     \group_end:
3354 }
3355 }
```

The command `\@@_actually_draw_Ddots:` has the following implicit arguments:

- `\l_@@_initial_i_int`
- `\l_@@_initial_j_int`
- `\l_@@_initial_open_bool`
- `\l_@@_final_i_int`
- `\l_@@_final_j_int`
- `\l_@@_final_open_bool`.

```

3356 \cs_new_protected:Npn \@@_actually_draw_Ddots:
3357 {
3358     \bool_if:NTF \l_@@_initial_open_bool
3359     {
3360         \@@_open_y_initial_dim:
3361         % \@@_qpoint:n { col - \int_use:N \l_@@_initial_j_int }
3362         % \dim_set_eq:NN \l_@@_x_initial_dim \pgf@x
3363         \@@_open_x_initial_dim:
3364     }
3365     { \@@_set_initial_coords_from_anchor:n { south-east } }
3366     \bool_if:NTF \l_@@_final_open_bool
3367     {
3368         % \@@_open_y_final_dim:
3369         % \@@_qpoint:n { col - \@@_succ:n \l_@@_final_j_int }
3370         \@@_open_x_final_dim:
3371         \dim_set_eq:NN \l_@@_x_final_dim \pgf@x
3372     }
3373     { \@@_set_final_coords_from_anchor:n { north-west } }
```

We have retrieved the coordinates in the usual way (they are stored in `\l_@@x_initial_dim`, etc.). If the parallelization of the diagonals is set, we will have (maybe) to adjust the fourth coordinate.

```
3374 \bool_if:NT \l_@@parallelize_diags_bool
3375   {
3376     \int_gincr:N \g_@@ddots_int
```

We test if the diagonal line is the first one (the counter `\g_@@ddots_int` is created for this usage).

```
3377   \int_compare:nNnTF \g_@@ddots_int = 1
```

If the diagonal line is the first one, we have no adjustment of the line to do but we store the Δ_x and the Δ_y of the line because these values will be used to draw the others diagonal lines parallels to the first one.

```
3378   {
3379     \dim_gset:Nn \g_@@delta_x_one_dim
3380       { \l_@@x_final_dim - \l_@@x_initial_dim }
3381     \dim_gset:Nn \g_@@delta_y_one_dim
3382       { \l_@@y_final_dim - \l_@@y_initial_dim }
3383   }
```

If the diagonal line is not the first one, we have to adjust the second extremity of the line by modifying the coordinate `\l_@@x_initial_dim`.

```
3384   {
3385     \dim_set:Nn \l_@@y_final_dim
3386       {
3387         \l_@@y_initial_dim +
3388           ( \l_@@x_final_dim - \l_@@x_initial_dim ) *
3389             \dim_ratio:nn \g_@@delta_y_one_dim \g_@@delta_x_one_dim
3390       }
3391     }
3392   }
3393   \@@_draw_line:
3394 }
```

We draw the `\Iddots` diagonals in the same way.

The first and the second arguments are the coordinates of the cell where the command has been issued. The third argument is the list of the options.

```
3395 \cs_new_protected:Npn \@@_draw_Iddots:nnn #1 #2 #3
3396   {
3397     \@@_adjust_to_submatrix:nn { #1 } { #2 }
3398     \cs_if_free:cT { @ _ dotted _ #1 - #2 }
3399     {
3400       \@@_find_extremities_of_line:nnnn { #1 } { #2 } 1 { -1 }
```

The previous command may have changed the current environment by marking some cells as “dotted”, but, fortunately, it is outside the group for the options of the line.

```
3401   \group_begin:
3402     \keys_set:nn { NiceMatrix / xdots } { #3 }
3403     \tl_if_empty:VF \l_@@xdots_color_tl { \color { \l_@@xdots_color_tl } }
3404     \@@_actually_draw_Iddots:
3405   \group_end:
3406 }
3407 }
```

The command `\@@_actually_draw_Iddots:` has the following implicit arguments:

- `\l_@@initial_i_int`
- `\l_@@initial_j_int`
- `\l_@@initial_open_bool`
- `\l_@@final_i_int`
- `\l_@@final_j_int`

```

• \l_@@_final_open_bool.

3408 \cs_new_protected:Npn \@@_actually_draw_Iddots:
3409 {
3410     \bool_if:NTF \l_@@_initial_open_bool
3411     {
3412         \@@_open_y_initial_dim:
3413         \@@_open_x_initial_dim:
3414     }
3415     { \@@_set_initial_coords_from_anchor:n { south-west } }
3416 \bool_if:NTF \l_@@_final_open_bool
3417 {
3418     \@@_open_y_final_dim:
3419     \@@_open_x_final_dim:
3420 }
3421 { \@@_set_final_coords_from_anchor:n { north-east } }
3422 \bool_if:NT \l_@@_parallelize_diags_bool
3423 {
3424     \int_gincr:N \g_@@_iddots_int
3425     \int_compare:nNnTF \g_@@_iddots_int = 1
3426     {
3427         \dim_gset:Nn \g_@@_delta_x_two_dim
3428         { \l_@@_x_final_dim - \l_@@_x_initial_dim }
3429         \dim_gset:Nn \g_@@_delta_y_two_dim
3430         { \l_@@_y_final_dim - \l_@@_y_initial_dim }
3431     }
3432     {
3433         \dim_set:Nn \l_@@_y_final_dim
3434         {
3435             \l_@@_y_initial_dim +
3436             ( \l_@@_x_final_dim - \l_@@_x_initial_dim ) *
3437             \dim_ratio:nn \g_@@_delta_y_two_dim \g_@@_delta_x_two_dim
3438         }
3439     }
3440 }
3441 \@@_draw_line:
3442 }

```

The actual instructions for drawing the dotted line with Tikz

The command `\@@_draw_line:` should be used in a `{pgfpicture}`. It has six implicit arguments:

- `\l_@@_x_initial_dim`
- `\l_@@_y_initial_dim`
- `\l_@@_x_final_dim`
- `\l_@@_y_final_dim`
- `\l_@@_initial_open_bool`
- `\l_@@_final_open_bool`

```

3443 \cs_new_protected:Npn \@@_draw_line:
3444 {
3445     \pgfrememberpicturepositiononpagetrue
3446     \pgf@relevantforpicturesizefalse
3447     \tl_if_eq:NNTF \l_@@_xdots_line_style_tl \c_@@_standard_tl
3448     \@@_draw_standard_dotted_line:
3449     \@@_draw_non_standard_dotted_line:
3450 }

```

We have to do a special construction with `\exp_args:N` to be able to put in the list of options in the correct place in the Tikz instruction.

```
3451 \cs_new_protected:Npn \@@_draw_non_standard_dotted_line:
3452 {
3453     \begin { scope }
3454     \exp_args:No \@@_draw_non_standard_dotted_line:n
3455         { \l_@@_xdots_line_style_tl , \l_@@_xdots_color_tl }
3456 }
```

We have used the fact that, in PGF, un color name can be put directly in a list of options (that's why we have put directly `\l_@@_xdots_color_tl`).

The argument of `\@@_draw_non_standard_dotted_line:n` is, in fact, the list of options.

```
3457 \cs_new_protected:Npn \@@_draw_non_standard_dotted_line:n #1
3458 {
3459     \@@_draw_non_standard_dotted_line:nVV
3460         { #1 }
3461         \l_@@_xdots_up_tl
3462         \l_@@_xdots_down_tl
3463 }

3464 \cs_new_protected:Npn \@@_draw_non_standard_dotted_line:nnn #1 #2 #3
3465 {
3466     \draw
3467     [
3468         #1 ,
3469         shorten~> = \l_@@_xdots_shorten_dim ,
3470         shorten~< = \l_@@_xdots_shorten_dim ,
3471     ]
3472     ( \l_@@_x_initial_dim , \l_@@_y_initial_dim )
```

Be careful: We can't put `\c_math_toggle_token` instead of \$ in the following lines because we are in the contents of Tikz nodes (and they will be *rescanned* if the Tikz library `babel` is loaded).

```
-- node [ sloped , above ] { $ \scriptstyle #2 $ }
node [ sloped , below ] { $ \scriptstyle #3 $ }
( \l_@@_x_final_dim , \l_@@_y_final_dim ) ;
\end { scope }
}
\cs_generate_variant:Nn \@@_draw_non_standard_dotted_line:nnn { n V V }
```

The command `\@@_draw_standard_dotted_line:` draws the line with our system of dots (which gives a dotted line with real round dots).

```
3479 \cs_new_protected:Npn \@@_draw_standard_dotted_line:
3480 {
3481     \bool_lazy_and:nnF
3482         { \tl_if_empty_p:N \l_@@_xdots_up_tl }
3483         { \tl_if_empty_p:N \l_@@_xdots_down_tl }
3484     {
3485         \pgfscope
3486         \pgftransformshift
3487         {
3488             \pgfpointlineattime { 0.5 }
3489                 { \pgfpoint \l_@@_x_initial_dim \l_@@_y_initial_dim }
3490                 { \pgfpoint \l_@@_x_final_dim \l_@@_y_final_dim }
3491         }
3492         \pgftransformrotate
3493         {
3494             \fp_eval:n
3495             {
3496                 atand
3497                 (
3498                     \l_@@_y_final_dim - \l_@@_y_initial_dim ,
3499                     \l_@@_x_final_dim - \l_@@_x_initial_dim
3500                 )
3501             }
```

```

3501         }
3502     }
3503     \pgfnode
3504     { rectangle }
3505     { south }
3506     {
3507         \c_math_toggle_token
3508         \scriptstyle \l_@@_xdots_up_tl
3509         \c_math_toggle_token
3510     }
3511     { }
3512     { \pgfusepath { } }
3513     \pgfnode
3514     { rectangle }
3515     { north }
3516     {
3517         \c_math_toggle_token
3518         \scriptstyle \l_@@_xdots_down_tl
3519         \c_math_toggle_token
3520     }
3521     { }
3522     { \pgfusepath { } }
3523     \endpgfscope
3524 }
3525 \group_begin:

```

The dimension $\l_@@_l_dim$ is the length ℓ of the line to draw. We use the floating point reals of `expl3` to compute this length.

```

3526     \dim_zero_new:N \l_@@_l_dim
3527     \dim_set:Nn \l_@@_l_dim
3528     {
3529         \fp_to_dim:n
3530         {
3531             sqrt
3532             (
3533                 ( \l_@@_x_final_dim - \l_@@_x_initial_dim ) ^ 2
3534                 +
3535                 ( \l_@@_y_final_dim - \l_@@_y_initial_dim ) ^ 2
3536             )
3537         }
3538     }

```

It seems that, during the first compilations, the value of $\l_@@_l_dim$ may be erroneous (equal to zero or very large). We must detect these cases because they would cause errors during the drawing of the dotted line. Maybe we should also write something in the `aux` file to say that one more compilation should be done.

```

3539     \bool_lazy_or:nnF
3540     { \dim_compare_p:nNn { \dim_abs:n \l_@@_l_dim } > \c_@@_max_l_dim }
3541     { \dim_compare_p:nNn \l_@@_l_dim = \c_zero_dim }
3542     \@@_draw_standard_dotted_line_i:
3543     \group_end:
3544 }
3545 \dim_const:Nn \c_@@_max_l_dim { 50 cm }
3546 \cs_new_protected:Npn \@@_draw_standard_dotted_line_i:
3547 {

```

The number of dots will be $\l_tmpa_int + 1$.

```

3548     \bool_if:NTF \l_@@_initial_open_bool
3549     {
3550         \bool_if:NTF \l_@@_final_open_bool
3551         {
3552             \int_set:Nn \l_tmpa_int
3553             { \dim_ratio:nn \l_@@_l_dim \l_@@_inter_dots_dim }

```

```

3554     }
3555     {
3556         \int_set:Nn \l_tmpa_int
3557         {
3558             \dim_ratio:nn
3559             { \l_@@_l_dim - \l_@@_xdots_shorten_dim }
3560             \l_@@_inter_dots_dim
3561         }
3562     }
3563 }
3564 {
3565     \bool_if:NTF \l_@@_final_open_bool
3566     {
3567         \int_set:Nn \l_tmpa_int
3568         {
3569             \dim_ratio:nn
3570             { \l_@@_l_dim - \l_@@_xdots_shorten_dim }
3571             \l_@@_inter_dots_dim
3572         }
3573     }
3574 {
3575     \int_set:Nn \l_tmpa_int
3576     {
3577         \dim_ratio:nn
3578         { \l_@@_l_dim - 2 \l_@@_xdots_shorten_dim }
3579         \l_@@_inter_dots_dim
3580     }
3581 }
3582 }

```

The dimensions \l_tmpa_dim and \l_tmpb_dim are the coordinates of the vector between two dots in the dotted line.

```

3583 \dim_set:Nn \l_tmpa_dim
3584 {
3585     ( \l_@@_x_final_dim - \l_@@_x_initial_dim ) *
3586     \dim_ratio:nn \l_@@_inter_dots_dim \l_@@_l_dim
3587 }
3588 \dim_set:Nn \l_tmpb_dim
3589 {
3590     ( \l_@@_y_final_dim - \l_@@_y_initial_dim ) *
3591     \dim_ratio:nn \l_@@_inter_dots_dim \l_@@_l_dim
3592 }

```

The length ℓ is the length of the dotted line. We note Δ the length between two dots and n the number of intervals between dots. We note $\delta = \frac{1}{2}(\ell - n\Delta)$. The distance between the initial extremity of the line and the first dot will be equal to $k \cdot \delta$ where $k = 0, 1$ or 2 . We first compute this number k in \l_tmpb_int .

```

3593 \int_set:Nn \l_tmpb_int
3594 {
3595     \bool_if:NTF \l_@@_initial_open_bool
3596     { \bool_if:NTF \l_@@_final_open_bool 1 0 }
3597     { \bool_if:NTF \l_@@_final_open_bool 2 1 }
3598 }

```

In the loop over the dots, the dimensions $\l_@@_x_initial_dim$ and $\l_@@_y_initial_dim$ will be used for the coordinates of the dots. But, before the loop, we must move until the first dot.

```

3599 \dim_gadd:Nn \l_@@_x_initial_dim
3600 {
3601     ( \l_@@_x_final_dim - \l_@@_x_initial_dim ) *
3602     \dim_ratio:nn
3603     { \l_@@_l_dim - \l_@@_inter_dots_dim * \l_tmpa_int }
3604     { 2 \l_@@_l_dim }
3605     * \l_tmpb_int
3606 }

```

```

3607 \dim_gadd:Nn \l_@@_y_initial_dim
3608 {
3609     ( \l_@@_y_final_dim - \l_@@_y_initial_dim ) *
3610     \dim_ratio:nn
3611     { \l_@@_l_dim - \l_@@_inter_dots_dim * \l_tmpa_int }
3612     { 2 \l_@@_l_dim }
3613     * \l_tmpb_int
3614 }
3615 \pgf@relevantforpicturesizefalse
3616 \int_step_inline:nnn 0 \l_tmpa_int
3617 {
3618     \pgfpathcircle
3619     { \pgfpoint \l_@@_x_initial_dim \l_@@_y_initial_dim }
3620     { \l_@@_radius_dim }
3621     \dim_add:Nn \l_@@_x_initial_dim \l_tmpa_dim
3622     \dim_add:Nn \l_@@_y_initial_dim \l_tmpb_dim
3623 }
3624 \pgfusepathqfill
3625 }

```

User commands available in the new environments

The commands `\@@_Ldots`, `\@@_Cdots`, `\@@_Vdots`, `\@@_Ddots` and `\@@_Idots` will be linked to `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots` and `\Idots` in the environments `{NiceArray}` (the other environments of `nicematrix` rely upon `{NiceArray}`).

The syntax of these commands uses the character `_` as embellishment and that's why we have to insert a character `_` in the *arg spec* of these commands. However, we don't know the future catcode of `_` in the main document (maybe the user will use `underscore`, and, in that case, the catcode is 13 because `underscore` activates `_`). That's why these commands will be defined in a `\AtBeginDocument` and the *arg spec* will be rescanned.

```

3626 \AtBeginDocument
3627 {
3628     \tl_set:Nn \l_@@_argspec_tl { 0 { } E { _^ } { { } { } } }
3629     \tl_set_rescan:Nno \l_@@_argspec_tl { } \l_@@_argspec_tl
3630     \exp_args:NNV \NewDocumentCommand \@@_Ldots \l_@@_argspec_tl
3631     {
3632         \int_compare:nNnTF \c@jCol = 0
3633         { \@@_error:nn { in-first-col } \Ldots }
3634         {
3635             \int_compare:nNnTF \c@jCol = \l_@@_last_col_int
3636             { \@@_error:nn { in-last-col } \Ldots }
3637             {
3638                 \@@_instruction_of_type:nnn \c_false_bool { \Ldots }
3639                 { #1 , down = #2 , up = #3 }
3640             }
3641         }
3642         \bool_if:NF \l_@@_nullify_dots_bool
3643         { \phantom { \ensuremath { \@@_old_ldots } } }
3644         \bool_gset_true:N \g_@@_empty_cell_bool
3645     }

3646 \exp_args:NNV \NewDocumentCommand \@@_Cdots \l_@@_argspec_tl
3647 {
3648     \int_compare:nNnTF \c@jCol = 0
3649     { \@@_error:nn { in-first-col } \Cdots }
3650     {
3651         \int_compare:nNnTF \c@jCol = \l_@@_last_col_int

```

```

3652     { \@@_error:nn { in-last-col } \Cdots }
3653     {
3654         \@@_instruction_of_type:nnn \c_false_bool { Cdots }
3655         { #1 , down = #2 , up = #3 }
3656     }
3657 }
3658 \bool_if:NF \l_@@_nullify_dots_bool
3659     { \phantom { \ensuremath { \@@_old_cdots } } } }
3660 \bool_gset_true:N \g_@@_empty_cell_bool
3661 }

3662 \exp_args:NNV \NewDocumentCommand \@@_Vdots \l_@@_argspec_tl
3663 {
3664     \int_compare:nNnTF \c@iRow = 0
3665     { \@@_error:nn { in-first-row } \Vdots }
3666     {
3667         \int_compare:nNnTF \c@iRow = \l_@@_last_row_int
3668         { \@@_error:nn { in-last-row } \Vdots }
3669         {
3670             \@@_instruction_of_type:nnn \c_false_bool { Vdots }
3671             { #1 , down = #2 , up = #3 }
3672         }
3673     }
3674     \bool_if:NF \l_@@_nullify_dots_bool
3675     { \phantom { \ensuremath { \@@_old_vdots } } } }
3676     \bool_gset_true:N \g_@@_empty_cell_bool
3677 }

3678 \exp_args:NNV \NewDocumentCommand \@@_Ddots \l_@@_argspec_tl
3679 {
3680     \int_case:nnF \c@iRow
3681     {
3682         0           { \@@_error:nn { in-first-row } \Ddots }
3683         \l_@@_last_row_int { \@@_error:nn { in-last-row } \Ddots }
3684     }
3685     {
3686         \int_case:nnF \c@jCol
3687         {
3688             0           { \@@_error:nn { in-first-col } \Ddots }
3689             \l_@@_last_col_int { \@@_error:nn { in-last-col } \Ddots }
3690         }
3691         {
3692             \keys_set_known:nn { NiceMatrix / Ddots } { #1 }
3693             \@@_instruction_of_type:nnn \l_@@_draw_first_bool { Ddots }
3694             { #1 , down = #2 , up = #3 }
3695         }
3696     }
3697 }
3698 \bool_if:NF \l_@@_nullify_dots_bool
3699     { \phantom { \ensuremath { \@@_old_ddots } } } }
3700     \bool_gset_true:N \g_@@_empty_cell_bool
3701 }

3702 \exp_args:NNV \NewDocumentCommand \@@_Iddots \l_@@_argspec_tl
3703 {
3704     \int_case:nnF \c@iRow
3705     {
3706         0           { \@@_error:nn { in-first-row } \Iddots }
3707         \l_@@_last_row_int { \@@_error:nn { in-last-row } \Iddots }
3708     }
3709     {

```

```

3710          \int_case:nnF \c@jCol
3711          {
3712              0           { \@@_error:nn { in-first-col } \Iddots }
3713              \l_@@_last_col_int { \@@_error:nn { in-last-col } \Iddots }
3714          }
3715          {
3716              \keys_set_known:nn { NiceMatrix / Ddots } { #1 }
3717              \@@_instruction_of_type:nnn \l_@@_draw_first_bool { Iddots }
3718                  { #1 , down = #2 , up = #3 }
3719          }
3720      }
3721      \bool_if:N \l_@@_nullify_dots_bool
3722          { \phantom { \ensuremath { \old_@@_iddots } } }
3723          \bool_gset_true:N \g_@@_empty_cell_bool
3724      }
3725  }

```

End of the `\AtBeginDocument`.

Despite its name, the following set of keys will be used for `\Ddots` but also for `\Iddots`.

```

3726 \keys_define:nn { NiceMatrix / Ddots }
3727  {
3728      draw-first .bool_set:N = \l_@@_draw_first_bool ,
3729      draw-first .default:n = true ,
3730      draw-first .value_forbidden:n = true
3731  }

```

The command `\@@_Hspace:` will be linked to `\hspace` in `{NiceArray}`.

```

3732 \cs_new_protected:Npn \@@_Hspace:
3733  {
3734      \bool_gset_true:N \g_@@_empty_cell_bool
3735      \hspace
3736  }
3737 \cs_set_eq:NN \@@_old_multicolumn \multicolumn

```

The command `\@@_Hdotsfor` will be linked to `\Hdotsfor` in `{NiceArrayWithDelims}`. Tikz nodes are created also in the implicit cells of the `\Hdotsfor` (maybe we should modify that point).

This command must *not* be protected since it begins with `\multicolumn`.

```

3738 \cs_new:Npn \@@_Hdotsfor:
3739  {
3740      \bool_lazy_and:nnTF
3741          { \int_compare_p:nNn \c@jCol = 0 }
3742          { \int_compare_p:nNn \l_@@_first_col_int = 0 }
3743          {
3744              \bool_if:NTF \g_@@_after_col_zero_bool
3745                  {
3746                      \multicolumn { 1 } { c } { }
3747                      \@@_Hdotsfor_i
3748                  }
3749                  { \@@_fatal:n { Hdotsfor-in-col-0 } }
3750          }
3751      {
3752          \multicolumn { 1 } { c } { }
3753          \@@_Hdotsfor_i
3754      }
3755  }

```

The command `\@@_Hdotsfor_i` is defined with `\NewDocumentCommand` because it has an optional argument. Note that such a command defined by `\NewDocumentCommand` is protected and that's why we have put the `\multicolumn` before (in the definition of `\@@_Hdotsfor:`).

```
3756 \AtBeginDocument
```

```

3757  {
3758    \tl_set:Nn \l_@@_argspec_tl { 0 { } m 0 { } E { _ ^ } { { } { } } }
3759    \tl_set_rescan:Nno \l_@@_argspec_tl { } \l_@@_argspec_tl

```

We don't put ! before the last optionnal argument for homogeneity with \Cdots, etc. which have only one optional argument.

```

3760  \exp_args:NNV \NewDocumentCommand \@@_Hdotsfor_i \l_@@_argspec_tl
3761  {
3762    \tl_gput_right:Nx \g_@@_Hdotsfor_lines_tl
3763    {
3764      \@@_Hdotsfor:nnnn
3765      { \int_use:N \c@iRow }
3766      { \int_use:N \c@jCol }
3767      { #2 }
3768      {
3769        #1 , #3 ,
3770        down = \exp_not:n { #4 } ,
3771        up = \exp_not:n { #5 }
3772      }
3773    }
3774    \prg_replicate:nn { #2 - 1 } { & \multicolumn { 1 } { c } { } }
3775  }
3776}

```

End of \AtBeginDocument.

```

3777 \cs_new_protected:Npn \@@_Hdotsfor:nnnn #1 #2 #3 #4
3778 {
3779   \bool_set_false:N \l_@@_initial_open_bool
3780   \bool_set_false:N \l_@@_final_open_bool

```

For the row, it's easy.

```

3781   \int_set:Nn \l_@@_initial_i_int { #1 }
3782   \int_set_eq:NN \l_@@_final_i_int \l_@@_initial_i_int

```

For the column, it's a bit more complicated.

```

3783   \int_compare:nNnTF { #2 } = 1
3784   {
3785     \int_set:Nn \l_@@_initial_j_int 1
3786     \bool_set_true:N \l_@@_initial_open_bool
3787   }
3788   {
3789     \cs_if_exist:cTF
3790     {
3791       pgf @ sh @ ns @ \@@_env:
3792       - \int_use:N \l_@@_initial_i_int
3793       - \int_eval:n { #2 - 1 }
3794     }
3795     { \int_set:Nn \l_@@_initial_j_int { #2 - 1 } }
3796     {
3797       \int_set:Nn \l_@@_initial_j_int { #2 }
3798       \bool_set_true:N \l_@@_initial_open_bool
3799     }
3800   }
3801   \int_compare:nNnTF { #2 + #3 - 1 } = \c@jCol
3802   {
3803     \int_set:Nn \l_@@_final_j_int { #2 + #3 - 1 }
3804     \bool_set_true:N \l_@@_final_open_bool
3805   }
3806   {
3807     \cs_if_exist:cTF
3808     {
3809       pgf @ sh @ ns @ \@@_env:
3810       - \int_use:N \l_@@_final_i_int
3811       - \int_eval:n { #2 + #3 }

```

```

3812         }
3813         { \int_set:Nn \l_@@_final_j_int { #2 + #3 } }
3814         {
3815             \int_set:Nn \l_@@_final_j_int { #2 + #3 - 1 }
3816             \bool_set_true:N \l_@@_final_open_bool
3817         }
3818     }

3819 \group_begin:
3820 \int_compare:nNnTF { #1 } = 0
3821     { \color { nicematrix-first-row } }
3822     {
3823         \int_compare:nNnT { #1 } = \g_@@_row_total_int
3824             { \color { nicematrix-last-row } }
3825     }
3826 \keys_set:nn { NiceMatrix / xdots } { #4 }
3827 \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
3828 \@@_actually_draw_Ldots:
3829 \group_end:

```

We declare all the cells concerned by the `\Hdotsfor` as “dotted” (for the dotted lines created by `\Cdots`, `\Ldots`, etc., this job is done by `\@@_find_extremities_of_line:nnnn`). This declaration is done by defining a special control sequence (to nil).

```

3830     \int_step_inline:nnn { #2 } { #2 + #3 - 1 }
3831         { \cs_set:cpn { @@ _ dotted _ #1 - ##1 } { } }
3832     }

```

```

3833 \AtBeginDocument
3834 {
3835     \tl_set:Nn \l_@@_argspec_tl { 0 { } m 0 { } E { _ ^ } { { } { } } }
3836     \tl_set_rescan:Nno \l_@@_argspec_tl { } \l_@@_argspec_tl
3837     \exp_args:NNV \NewDocumentCommand \@@_Vdotsfor: \l_@@_argspec_tl
3838     {
3839         \tl_gput_right:Nx \g_@@_Hdotsfor_lines_tl
3840         {
3841             \@@_Vdotsfor:nnnn
3842                 { \int_use:N \c@iRow }
3843                 { \int_use:N \c@jCol }
3844                 { #2 }
3845                 {
3846                     #1 , #3 ,
3847                     down = \exp_not:n { #4 } , up = \exp_not:n { #5 }
3848                 }
3849             }
3850         }
3851     }

```

Enf of `\AtBeginDocument`.

```

3852 \cs_new_protected:Npn \@@_Vdotsfor:nnnn #1 #2 #3 #4
3853 {
3854     \bool_set_false:N \l_@@_initial_open_bool
3855     \bool_set_false:N \l_@@_final_open_bool

```

For the column, it's easy.

```

3856     \int_set:Nn \l_@@_initial_j_int { #2 }
3857     \int_set_eq:NN \l_@@_final_j_int \l_@@_initial_j_int

```

For the row, it's a bit more complicated.

```

3858     \int_compare:nNnTF #1 = 1
3859     {
3860         \int_set:Nn \l_@@_initial_i_int 1
3861         \bool_set_true:N \l_@@_initial_open_bool
3862     }
3863     {

```

```

3864 \cs_if_exist:cTF
3865 {
3866     pgf @ sh @ ns @ \@@_env:
3867     - \int_eval:n { #1 - 1 }
3868     - \int_use:N \l_@@_initial_j_int
3869 }
3870 { \int_set:Nn \l_@@_initial_i_int { #1 - 1 } }
3871 {
3872     \int_set:Nn \l_@@_initial_i_int { #1 }
3873     \bool_set_true:N \l_@@_initial_open_bool
3874 }
3875 }
3876 \int_compare:nNnTF { #1 + #3 -1 } = \c@iRow
3877 {
3878     \int_set:Nn \l_@@_final_i_int { #1 + #3 - 1 }
3879     \bool_set_true:N \l_@@_final_open_bool
3880 }
3881 {
3882     \cs_if_exist:cTF
3883     {
3884         pgf @ sh @ ns @ \@@_env:
3885         - \int_eval:n { #1 + #3 }
3886         - \int_use:N \l_@@_final_j_int
3887     }
3888 { \int_set:Nn \l_@@_final_i_int { #1 + #3 } }
3889 {
3890     \int_set:Nn \l_@@_final_i_int { #1 + #3 - 1 }
3891     \bool_set_true:N \l_@@_final_open_bool
3892 }
3893 }

3894 \group_begin:
3895 \int_compare:nNnTF { #2 } = 0
3896 { \color { nicematrix-first-col } }
3897 {
3898     \int_compare:nNnT { #2 } = \g_@@_col_total_int
3899     { \color { nicematrix-last-col } }
3900 }
3901 \keys_set:nn { NiceMatrix / xdots } { #4 }
3902 \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
3903 \@@_actually_draw_Vdots:
3904 \group_end:

```

We declare all the cells concerned by the `\Vdots` as “dotted” (for the dotted lines created by `\Cdots`, `\Ldots`, etc., this job is done by `\@@_find_extremities_of_line:nnnn`). This declaration is done by defining a special control sequence (to nil).

```

3905 \int_step_inline:nnn { #1 } { #1 + #3 - 1 }
3906 { \cs_set:cpn { @@ _ dotted _ ##1 - #2 } { } }
3907 }

```

The command `\@@_rotate:` will be linked to `\rotate` in `{NiceArrayWithDelims}`.

```

3908 \cs_new_protected:Npn \@@_rotate: { \bool_gset_true:N \g_@@_rotate_bool }

```

The command `\line` accessible in code-after

In the `\CodeAfter`, the command `\@@_line:nn` will be linked to `\line`. This command takes two arguments which are the specifications of two cells in the array (in the format $i-j$) and draws a dotted line between these cells.

First, we write a command with an argument of the format $i-j$ and applies the command `\int_eval:n` to i and j ; this must *not* be protected (and is, of course fully expandable).⁶¹

```
3909 \cs_new:Npn \@@_double_int_eval:n #1-#2 \q_stop
3910   { \int_eval:n { #1 } - \int_eval:n { #2 } }
```

With the following construction, the command `\@@_double_int_eval:n` is applied to both arguments before the application of `\@@_line_i:nn` (the construction uses the fact the `\@@_line_i:nn` is protected and that `\@@_double_int_eval:n` is fully expandable).

```
3911 \AtBeginDocument
3912 {
3913   \tl_set:Nn \l_@@_argspec_tl { 0 { } m m ! 0 { } E { _ ^ } { { } { } } }
3914   \tl_set_rescan:Nno \l_@@_argspec_tl { } \l_@@_argspec_tl
3915   \exp_args:NNV \NewDocumentCommand \@@_line \l_@@_argspec_tl
3916   {
3917     \group_begin:
3918     \keys_set:nn { NiceMatrix / xdots } { #1 , #4 , down = #5 , up = #6 }
3919     \tl_if_empty:VF \l_@@_xdots_color_tl { \color { \l_@@_xdots_color_tl } }
3920     \use:e
3921     {
3922       \@@_line_i:nn
3923         { \@@_double_int_eval:n #2 \q_stop }
3924         { \@@_double_int_eval:n #3 \q_stop }
3925     }
3926     \group_end:
3927   }
3928 }

3929 \cs_new_protected:Npn \@@_line_i:nn #1 #2
3930 {
3931   \bool_set_false:N \l_@@_initial_open_bool
3932   \bool_set_false:N \l_@@_final_open_bool
3933   \bool_if:nTF
3934   {
3935     \cs_if_free_p:c { pgf @ sh @ ns @ \@@_env: - #1 }
3936     ||
3937     \cs_if_free_p:c { pgf @ sh @ ns @ \@@_env: - #2 }
3938   }
3939   {
3940     \@@_error:nnn { unknown-cell-for-line-in-CodeAfter } { #1 } { #2 }
3941   }
3942   { \@@_draw_line_ii:nn { #1 } { #2 } }
3943 }

3944 \AtBeginDocument
3945 {
3946   \cs_new_protected:Npx \@@_draw_line_ii:nn #1 #2
3947   {
```

We recall that, when externalization is used, `\tikzpicture` and `\endtikzpicture` (or `\pgfpicture` and `\endpgfpicture`) must be directly “visible” and that why we do this static construction of the command `\@@_draw_line_ii:nn`.

```
3948   \c_@@_pgfortikzpicture_tl
3949   \@@_draw_line_iii:nn { #1 } { #2 }
3950   \c_@@_endpgfortikzpicture_tl
3951 }
3952 }
```

The following command *must* be protected (it’s used in the construction of `\@@_draw_line_ii:nn`).

```
3953 \cs_new_protected:Npn \@@_draw_line_iii:nn #1 #2
3954 {
```

⁶¹Indeed, we want that the user may use the command `\line` in `\CodeAfter` with LaTeX counters in the arguments — with the command `\value`.

```

3955 \pgfrememberpicturepositiononpagetrue
3956 \pgfpointshapeborder { \@@_env: - #1 } { \@@_qpoint:n { #2 } }
3957 \dim_set_eq:NN \l_@_x_initial_dim \pgf@x
3958 \dim_set_eq:NN \l_@_y_initial_dim \pgf@y
3959 \pgfpointshapeborder { \@@_env: - #2 } { \@@_qpoint:n { #1 } }
3960 \dim_set_eq:NN \l_@_x_final_dim \pgf@x
3961 \dim_set_eq:NN \l_@_y_final_dim \pgf@y
3962 \@@_draw_line:
3963 }

```

The commands `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, and `\Iddots` don't use this command because they have to do other settings (for example, the diagonal lines must be parallelized).

Colors of cells, rows and columns

We want to avoid the thin white lines that are shown in some PDF viewers (eg: with the engine MuPDF used by SumatraPDF). That's why we try to draw rectangles of the same color in the same instruction `\pgfusepath { fill }` (and they will be in the same instruction `fill`—coded `f`—in the resulting PDF).

The commands `\@@_rowcolor`, `\@@_columncolor` and `\@@_rectanglecolor` (which are linked to `\rowcolor`, `\columncolor` and `\rectanglecolor` before the execution of the `code-before`) don't directly draw the corresponding rectangles. Instead, they store their instructions color by color:

- A sequence `\g_@@_colors_seq` will be built containing all the colors used by at least one of these instructions. Each *color* may be prefixed by its color model (eg: `[gray]{0.5}`).
- For the color whose index in `\g_@@_colors_seq` is equal to *i*, a list of instructions which use that color will be constructed in the token list `\g_@@_color_i_t1`. In that token list, the instructions will be written using `\@@_rowcolor:n`, `\@@_columncolor:n` and `\@@_rectanglecolor:nn` (corresponding of `\rowcolor`, `\columncolor` and `\rectanglecolor`).

`bigskip #1` is the color and `#2` is an instruction using that color. Despite its name, the command `\@@_add_to_color_seq` doesn't only add a color to `\g_@@_colors_seq`: it also updates the corresponding token list `\g_@@_color_i_t1`. We add in a global way because the final user may use the instructions such as `\cellcolor` in a loop of `pgffor` in the `\CodeBefore` (and we recall that a loop of `pgffor` is encapsulated in a group).

```

3964 \cs_new_protected:Npn \@@_add_to_colors_seq:nn #1 #2
3965 {

```

First, we look for the number of the color and, if it's found, we store it in `\l_tmpa_int`. If the color is not present in `\g_@@_colors_seq`, `\l_tmpa_int` will remain equal to 0.

```

3966 \int_zero:N \l_tmpa_int
3967 \seq_map_indexed_inline:Nn \g_@@_colors_seq
3968 { \tl_if_eq:nnT { #1 } { ##2 } { \int_set:Nn \l_tmpa_int { ##1 } } }
3969 \int_compare:nNnTF \l_tmpa_int = \c_zero_int

```

First, the case where the color is a *new* color (not in the sequence).

```

3970 {
3971     \seq_gput_right:Nn \g_@@_colors_seq { #1 }
3972     \tl_gset:cx { g_@@_color _ \seq_count:N \g_@@_colors_seq _ tl } { #2 }
3973 }
3974 { \tl_gput_right:cx { g_@@_color _ \int_use:N \l_tmpa_int _ tl } { #2 } }
3975 }
3976 \cs_generate_variant:Nn \@@_add_to_colors_seq:nn { x n }

```

The macro `\@@_actually_color:` will actually fill all the rectangles, color by color (using the sequence `\l_@@_colors_seq` and all the token lists of the form `\l_@@_color_i_tl`).

```

3977 \cs_new_protected:Npn \@@_actually_color:
3978 {
3979   \pgfpicture
3980   \pgf@relevantforpicturesizefalse
3981   \seq_map_indexed_inline:Nn \g_@@_colors_seq
3982   {
3983     \color ##2
3984     \use:c { g_@@_color _ ##1 _ tl }
3985     \tl_gclear:c { g_@@_color _ ##1 _ tl }
3986     \pgfusepath { fill }
3987   }
3988   \endpgfpicture
3989 }

3990 \cs_set_protected:Npn \@@_cut_on_hyphen:w #1-#2\q_stop
3991 {
3992   \tl_set:Nn \l_tmpa_tl { #1 }
3993   \tl_set:Nn \l_tmpb_tl { #2 }
3994 }
```

Here is an example : `\@@_rowcolor {red!15} {1,3,5-7,10-}`

```

3995 \NewDocumentCommand \@@_rowcolor { O { } m m }
3996 {
3997   \tl_if_blank:nF { #2 }
3998   {
3999     \@@_add_to_colors_seq:xn
4000     { \tl_if_blank:nF { #1 } { [ #1 ] } { #2 } }
4001     { \@@_rowcolor:n { #3 } }
4002   }
4003 }

4004 \cs_new_protected:Npn \@@_rowcolor:n #1
4005 {
4006   \tl_set:Nn \l_@@_rows_tl { #1 }
4007   \tl_set:Nn \l_@@_cols_tl { - }
```

The command `\@@_cartesian_path:` takes in two implicit arguments: `\l_@@_cols_tl` and `\l_@@_rows_tl`.

```

4008   \@@_cartesian_path:
4009 }
```

Here an example : `\@@_columncolor:nn {red!15} {1,3,5-7,10-}`

```

4010 \NewDocumentCommand \@@_columncolor { O { } m m }
4011 {
4012   \tl_if_blank:nF { #2 }
4013   {
4014     \@@_add_to_colors_seq:xn
4015     { \tl_if_blank:nF { #1 } { [ #1 ] } { #2 } }
4016     { \@@_columncolor:n { #3 } }
4017   }
4018 }

4019 \cs_new_protected:Npn \@@_columncolor:n #1
4020 {
4021   \tl_set:Nn \l_@@_rows_tl { - }
4022   \tl_set:Nn \l_@@_cols_tl { #1 }
```

The command `\@@_cartesian_path:` takes in two implicit arguments: `\l_@@_cols_tl` and `\l_@@_rows_tl`.

```

4023   \@@_cartesian_path:
4024 }
```

Here is an example : \@@_rectanglecolor{red!15}{2-3}{5-6}

```

4025 \NewDocumentCommand \@@_rectanglecolor { 0 { } m m m }
4026 {
4027     \tl_if_blank:nF { #2 }
4028     {
4029         \@@_add_to_colors_seq:xn
4030         { \tl_if_blank:nF { #1 } { [ #1 ] } { #2 } }
4031         { \@@_rectanglecolor:nnn { #3 } { #4 } { 0 pt } }
4032     }
4033 }
```

The last argument is the radius of the corners of the rectangle.

```

4034 \NewDocumentCommand \@@_roundedrectanglecolor { 0 { } m m m m }
4035 {
4036     \tl_if_blank:nF { #2 }
4037     {
4038         \@@_add_to_colors_seq:xn
4039         { \tl_if_blank:nF { #1 } { [ #1 ] } { #2 } }
4040         { \@@_rectanglecolor:nnn { #3 } { #4 } { #5 } }
4041     }
4042 }
```

The last argument is the radius of the corners of the rectangle.

```

4043 \cs_new_protected:Npn \@@_rectanglecolor:nnn #1 #2 #3
4044 {
4045     \@@_cut_on_hyphen:w #1 \q_stop
4046     \tl_clear_new:N \l_tmpc_tl
4047     \tl_clear_new:N \l_tmpd_tl
4048     \tl_set_eq:NN \l_tmpc_tl \l_tmpa_tl
4049     \tl_set_eq:NN \l_tmpd_tl \l_tmpb_tl
4050     \@@_cut_on_hyphen:w #2 \q_stop
4051     \tl_set:Nx \l_@@_rows_tl { \l_tmpc_tl - \l_tmpa_tl }
4052     \tl_set:Nx \l_@@_cols_tl { \l_tmpd_tl - \l_tmpb_tl }
```

The command \@@_cartesian_path:n takes in two implicit arguments: \l_@@_cols_tl and \l_@@_rows_tl.

```

4053     \@@_cartesian_path:n { #3 }
4054 }
```

Here is an example : \@@_cellcolor[rgb]{0.5,0.5,0}{2-3,3-4,4-5,5-6}

```

4055 \NewDocumentCommand \@@_cellcolor { 0 { } m m }
4056 {
4057     \clist_map_inline:nn { #3 }
4058     { \@@_rectanglecolor [ #1 ] { #2 } { ##1 } { ##1 } }
```

```

4060 \NewDocumentCommand \@@_chessboardcolors { 0 { } m m }
4061 {
4062     \int_step_inline:nn { \int_use:N \c@iRow }
4063     {
4064         \int_step_inline:nn { \int_use:N \c@jCol }
4065         {
4066             \int_if_even:nTF { #####1 + ##1 }
4067             { \@@_cellcolor [ #1 ] { #2 } }
4068             { \@@_cellcolor [ #1 ] { #3 } }
4069             { ##1 - #####1 }
4070         }
4071     }
4072 }
```

```

4073 \keys_define:nn { NiceMatrix / arraycolor }
4074   { except-corners .code:n = \@@_error:n { key except-corners } }

```

The command `\@@_arraycolor` (linked to `\arraycolor` at the beginning of the `\CodeBefore`) will color the whole tabular (excepted the potential exterior rows and columns). The third argument is a optional argument which a list of pairs key-value.

```

4075 \NewDocumentCommand \@@_arraycolor { O{ } m O{ } }
4076   {
4077     \keys_set:nn { NiceMatrix / arraycolor } { #3 }
4078     \@@_rectanglecolor [ #1 ] { #2 }
4079       { 1 - 1 }
4080       { \int_use:N \c@iRow - \int_use:N \c@jCol }
4081   }

4082 \keys_define:nn { NiceMatrix / rowcolors }
4083   {
4084     respect-blocks .bool_set:N = \l_@@_respect_blocks_bool ,
4085     respect-blocks .default:n = true ,
4086     cols .tl_set:N = \l_@@_cols_tl ,
4087     restart .bool_set:N = \l_@@_rowcolors_restart_bool ,
4088     restart .default:n = true ,
4089     unknown .code:n = \@@_error:n { Unknown-key-for-rowcolors }
4090   }

```

The command `\rowcolors` (accessible in the `code-before`) is inspired by the command `\rowcolors` of the package `xcolor` (with the option `table`). However, the command `\rowcolors` of `nicematrix` has *not* the optional argument of the command `\rowcolors` of `xcolor`. Here is an example: `\rowcolors{1}{blue!10}{}[respect-blocks]`.

#1 (optional) is the color space ; #2 is a list of intervals of rows ; #3 is the first color ; #4 is the second color ; #5 is for the optional list of pairs key-value.

```

4091 \NewDocumentCommand \@@_rowcolors { O{ } m m m O{ } }
4092   {

```

The group is for the options.

```

4093 \group_begin:
4094   \tl_clear_new:N \l_@@_cols_tl
4095   \tl_set:Nn \l_@@_cols_tl { - }
4096   \keys_set:nn { NiceMatrix / rowcolors } { #5 }

```

The boolean `\l_tmpa_bool` will indicate whereas we are in a row of the first color or of the second color.

```

4097 \bool_set_true:N \l_tmpa_bool
4098 \bool_if:NT \l_@@_respect_blocks_bool
4099   {

```

We don't want to take into account a block which is completely in the "first column" of (number 0) or in the "last column" and that's why we filter the sequence of the blocks (in a the sequence `\l_tmpa_seq`).

```

4100   \seq_set_eq:NN \l_tmpb_seq \g_@@_pos_of_blocks_seq
4101   \seq_set_filter:NNn \l_tmpa_seq \l_tmpb_seq
4102     { \@@_not_in_exterior_p:nnnn ##1 }
4103   }
4104 \pgfpicture
4105 \pgf@relevantforpicturesizefalse
4106 \clist_map_inline:nn { #2 }
4107   {
4108     \tl_set:Nn \l_tmpa_tl { ##1 }
4109     \tl_if_in:NnTF \l_tmpa_tl { - }
4110       { \@@_cut_on_hyphen:w ##1 \q_stop }
4111       { \tl_set:Nx \l_tmpb_tl { \int_use:N \c@iRow } }

```

The counter `\l_tmpa_int` will be the index of the loop.

```

4112 \int_set:Nn \l_tmpa_int \l_tmpa_tl
4113 \bool_if:NTF \l_@@_rowcolors_restart_bool
4114   { \bool_set_true:N \l_tmpa_bool }
4115   { \bool_set:Nn \l_tmpa_bool { \int_if_odd_p:n { \l_tmpa_tl } } }
4116 \int_zero_new:N \l_tmpc_int
4117 \int_set:Nn \l_tmpc_int \l_tmpb_tl
4118 \int_do_until:nNnn \l_tmpa_int > \l_tmpc_int
4119   {

```

We will compute in `\l_tmpb_int` the last row of the “block”.

```

4120 \int_set_eq:NN \l_tmpb_int \l_tmpa_int

```

If the key `respect-blocks` is in force, we have to adjust that value (of course).

```

4121 \bool_if:NT \l_@@_respect_blocks_bool
4122   {
4123     \seq_set_filter:NNn \l_tmpb_seq \l_tmpa_seq
4124       { \@@_intersect_our_row_p:nnnn #####1 }
4125     \seq_map_inline:Nn \l_tmpb_seq { \@@_rowcolors_i:nnnn #####1 }

```

Now, the last row of the block is computed in `\l_tmpb_int`.

```

4126   }
4127   \tl_set:Nx \l_@@_rows_tl
4128     { \int_use:N \l_tmpa_int - \int_use:N \l_tmpb_int }
4129 \bool_if:NTF \l_tmpa_bool
4130   {
4131     \tl_if_blank:nF { #3 }
4132     {
4133       \tl_if_empty:nTF { #1 }
4134         \color
4135           { \color [ #1 ] }
4136         { #3 }

```

The command `\@@_cartesian_path:` takes in two implicit arguments: `\l_@@_cols_tl` and `\l_@@_rows_tl`.

```

4137   \@@_cartesian_path:
4138     \pgfusepath { fill }
4139   }
4140   \bool_set_false:N \l_tmpa_bool
4141 }
4142 {
4143   \tl_if_blank:nF { #4 }
4144   {
4145     \tl_if_empty:nTF { #1 }
4146       \color
4147         { \color [ #1 ] }
4148         { #4 }

```

The command `\@@_cartesian_path:` takes in two implicit arguments: `\l_@@_cols_tl` and `\l_@@_row_tl`.

```

4149   \@@_cartesian_path:
4150     \pgfusepath { fill }
4151   }
4152   \bool_set_true:N \l_tmpa_bool
4153 }
4154   \int_set:Nn \l_tmpa_int { \l_tmpb_int + 1 }
4155 }
4156 }
4157 \endpgfpicture
4158 \group_end:
4159 }

4160 \cs_new_protected:Npn \@@_rowcolors_i:nnnn #1 #2 #3 #4
4161   {

```

```

4162 \int_compare:nNnT { #3 } > \l_tmpb_int
4163   { \int_set:Nn \l_tmpb_int { #3 } }
4164 }

4165 \prg_new_conditional:Nnn \@@_not_in_exterior:nnn p
4166 {
4167   \bool_lazy_or:nnTF
4168   { \int_compare_p:nNn { #4 } = \c_zero_int }
4169   { \int_compare_p:nNn { #2 } = { \@@_succ:n { \c@jCol } } }
4170   \prg_return_false:
4171   \prg_return_true:
4172 }

```

The following command return `true` when the block intersects the row `\l_tmpa_int`.

```

4173 \prg_new_conditional:Nnn \@@_intersect_our_row:nnn p
4174 {
4175   \bool_if:nTF
4176   {
4177     \int_compare_p:n { #1 <= \l_tmpa_int }
4178     &&
4179     \int_compare_p:n { \l_tmpa_int <= #3 }
4180   }
4181   \prg_return_true:
4182   \prg_return_false:
4183 }

```

The following command uses two implicit arguments: `\l_@@_rows_t1` and `\l_@@_cols_t1` which are specifications for a set of rows and a set of columns. It creates a path but does *not* fill it. It must be filled by another command after. The argument is the radius of the corners. We define below a command `\@@_cartesian_path:` which corresponds to a value 0 pt for the radius of the corners. This command is in particular used in `\@@_rectanglecolor:nnn` (used in `\@@_rectanglecolor`, itself used in `\@@_cellcolor`).

```

4184 \cs_new_protected:Npn \@@_cartesian_path:n #1
4185 {
4186   \bool_lazy_and:nnT
4187   { ! \seq_if_empty_p:N \l_@@_corners_cells_seq }
4188   { \dim_compare_p:nNn { #1 } = \c_zero_dim }
4189   {
4190     \@@_expand_clist:NN \l_@@_cols_t1 \c@jCol
4191     \@@_expand_clist:NN \l_@@_rows_t1 \c@iRow
4192   }

```

We begin the loop over the columns.

```

4193 \clist_map_inline:Nn \l_@@_cols_t1
4194 {
4195   \tl_set:Nn \l_tmpa_t1 { ##1 }
4196   \tl_if_in:NnTF \l_tmpa_t1 { - }
4197   { \@@_cut_on_hyphen:w ##1 \q_stop }
4198   { \@@_cut_on_hyphen:w ##1 - ##1 \q_stop }
4199   \bool_lazy_or:nnT
4200   { \tl_if_blank_p:V \l_tmpa_t1 }
4201   { \str_if_eq_p:Vn \l_tmpa_t1 { * } }
4202   { \tl_set:Nn \l_tmpa_t1 { 1 } }
4203   \bool_lazy_or:nnT
4204   { \tl_if_blank_p:V \l_tmpb_t1 }
4205   { \str_if_eq_p:Vn \l_tmpb_t1 { * } }
4206   { \tl_set:Nx \l_tmpb_t1 { \int_use:N \c@jCol } }
4207   \int_compare:nNnT \l_tmpb_t1 > \c@jCol
4208   { \tl_set:Nx \l_tmpb_t1 { \int_use:N \c@jCol } }

```

`\l_tmpc_t1` will contain the number of column.

```

4209   \tl_set_eq:NN \l_tmpc_t1 \l_tmpa_t1

```

If we decide to provide the commands `\cellcolor`, `\rectanglecolor`, `\rowcolor`, `\columncolor`, `\rowcolors` and `\chessboardcolors` in the `code-before` of a `\SubMatrix`, we will have to modify the following line, by adding a kind of offset. We will have also some other lines to modify.

```

4210      \@@_qpoint:n { col - \l_tmpa_t1 }
4211      \int_compare:nNnTF \l_@@_first_col_int = \l_tmpa_t1
4212          { \dim_set:Nn \l_tmpc_dim { \pgf@x - 0.5 \arrayrulewidth } }
4213          { \dim_set:Nn \l_tmpc_dim { \pgf@x + 0.5 \arrayrulewidth } }
4214      \@@_qpoint:n { col - \@@_succ:n \l_tmpb_t1 }
4215      \dim_set:Nn \l_tmpa_dim { \pgf@x + 0.5 \arrayrulewidth }

```

We begin the loop over the rows.

```

4216      \clist_map_inline:Nn \l_@@_rows_t1
4217      {
4218          \tl_set:Nn \l_tmpa_t1 { #####1 }
4219          \tl_if_in:NnTF \l_tmpa_t1 { - }
4220              { \@@_cut_on_hyphen:w #####1 \q_stop }
4221              { \@@_cut_on_hyphen:w #####1 - #####1 \q_stop }
4222          \tl_if_empty:NT \l_tmpa_t1 { \tl_set:Nn \l_tmpa_t1 { 1 } }
4223          \tl_if_empty:NT \l_tmpb_t1
4224              { \tl_set:Nx \l_tmpb_t1 { \int_use:N \c@iRow } }
4225          \int_compare:nNnT \l_tmpb_t1 > \c@iRow
4226              { \tl_set:Nx \l_tmpb_t1 { \int_use:N \c@iRow } }

```

Now, the numbers of both rows are in `\l_tmpa_t1` and `\l_tmpb_t1`.

```

4227      \seq_if_in:NxF \l_@@_corners_cells_seq
4228          { \l_tmpa_t1 - \l_tmpc_t1 }
4229          {
4230              \@@_qpoint:n { row - \@@_succ:n \l_tmpb_t1 }
4231              \dim_set:Nn \l_tmpb_dim { \pgf@y + 0.5 \arrayrulewidth }
4232              \@@_qpoint:n { row - \l_tmpa_t1 }
4233              \dim_set:Nn \l_tmpd_dim { \pgf@y + 0.5 \arrayrulewidth }
4234              \pgfsetcornersarced { \pgfpoint { #1 } { #1 } }
4235              \pgfpathrectanglecorners
4236                  { \pgfpoint \l_tmpc_dim \l_tmpd_dim }
4237                  { \pgfpoint \l_tmpa_dim \l_tmpb_dim }
4238          }
4239      }
4240  }
4241 }

```

The following command corresponds to a radius of the corners equal to 0 pt. This command is used by the commands `\@@_rowcolors`, `\@@_columncolor` and `\@@_rowcolor:n` (used in `\@@_rowcolor`).

```
4242 \cs_new_protected:Npn \@@_cartesian_path: { \@@_cartesian_path:n { 0 pt } }
```

The following command will be used only with `\l_@@_cols_t1` and `\c@jCol` (first case) or with `\l_@@_rows_t1` and `\c@iRow` (second case). For instance, with `\l_@@_cols_t1` equal to 2,4-6,8-* and `\c@jCol` equal to 10, the clist `\l_@@_cols_t1` will be replaced by 2,4,5,6,8,9,10.

```

4243 \cs_new_protected:Npn \@@_expand_clist:NN #1 #2
4244  {
4245      \clist_set_eq:NN \l_tmpa_clist #1
4246      \clist_clear:N #1
4247      \clist_map_inline:Nn \l_tmpa_clist
4248      {
4249          \tl_set:Nn \l_tmpa_t1 { ##1 }
4250          \tl_if_in:NnTF \l_tmpa_t1 { - }
4251              { \@@_cut_on_hyphen:w ##1 \q_stop }
4252              { \@@_cut_on_hyphen:w ##1 - ##1 \q_stop }
4253          \bool_lazy_or:nnT
4254              { \tl_if_blank_p:V \l_tmpa_t1 }
4255              { \str_if_eq_p:Vn \l_tmpa_t1 { * } }
4256              { \tl_set:Nn \l_tmpa_t1 { 1 } }
4257          \bool_lazy_or:nnT

```

```

4258     { \tl_if_blank_p:V \l_tmpb_tl }
4259     { \str_if_eq_p:Vn \l_tmpb_tl { * } }
4260     { \tl_set:Nx \l_tmpb_tl { \int_use:N #2 } }
4261     \int_compare:nNnT \l_tmpb_tl > #2
4262     { \tl_set:Nx \l_tmpb_tl { \int_use:N #2 } }
4263     \int_step_inline:nnn \l_tmpa_tl \l_tmpb_tl
4264     { \clist_put_right:Nn #1 { #####1 } }
4265   }
4266 }

```

When the user uses the key `colortbl-like`, the following command will be linked to `\cellcolor` in the tabular.

```

4267 \NewDocumentCommand \@@_cellcolor_tabular { 0 { } m }
4268 {
4269   \peek_remove_spaces:n
4270   {
4271     \tl_gput_right:Nx \g_nicematrix_code_before_tl
4272     {

```

We must not expand the color (#2) because the color may contain the token ! which may be activated by some packages (ex.: babel with the option french on latex and pdflatex).

```

4273   \cellcolor [ #1 ] { \exp_not:n { #2 } }
4274   { \int_use:N \c@iRow - \int_use:N \c@jCol }
4275 }
4276 }
4277 }

```

When the user uses the key `colortbl-like`, the following command will be linked to `\rowcolor` in the tabular.

```

4278 \NewDocumentCommand \@@_rowcolor_tabular { 0 { } m }
4279 {
4280   \peek_remove_spaces:n
4281   {
4282     \tl_gput_right:Nx \g_nicematrix_code_before_tl
4283     {
4284       \exp_not:N \rectanglecolor [ #1 ] { \exp_not:n { #2 } }
4285       { \int_use:N \c@iRow - \int_use:N \c@jCol }
4286       { \int_use:N \c@iRow - \exp_not:n { \int_use:N \c@jCol } }
4287     }
4288   }
4289 }
4290 \NewDocumentCommand \@@_columncolor_preamble { 0 { } m }
4291 {

```

With the following line, we test whether the cell is the first one we encounter in its column (don't forget that some rows may be incomplete).

```

4292   \int_compare:nNnT \c@jCol > \g_@@_col_total_int
4293   {

```

You use `gput_left` because we want the specification of colors for the columns drawn before the specifications of color for the rows (and the cells). Be careful: maybe this is not effective since we have an analyze of the instructions in the `\CodeBefore` in order to fill color by color (to avoid the thin white lines).

```

4294   \tl_gput_left:Nx \g_nicematrix_code_before_tl
4295   {
4296     \exp_not:N \columncolor [ #1 ]
4297     { \exp_not:n { #2 } } { \int_use:N \c@jCol }
4298   }
4299 }
4300 }

```

The vertical rules

We give to the user the possibility to define new types of columns (with `\newcolumntype` of `array`) for special vertical rules (*e.g.* rules thicker than the standard ones) which will not extend in the potential exterior rows of the array.

We provide the command `\OnlyMainNiceMatrix` in that goal. However, that command must be no-op outside the environments of `nicematrix` (and so the user will be allowed to use the same new type of column in the environments of `nicematrix` and in the standard environments of `array`).

That's why we provide first a global definition of `\OnlyMainNiceMatrix`.

```
4301 \cs_set_eq:NNN \OnlyMainNiceMatrix \use:n
```

Another definition of `\OnlyMainNiceMatrix` will be linked to the command in the environments of `nicematrix`. Here is that definition, called `\@@_OnlyMainNiceMatrix:n`.

```
4302 \cs_new_protected:Npn \@@_OnlyMainNiceMatrix:n #1
  {
    \int_compare:nNnTF \l_@@_first_col_int = 0
      { \@@_OnlyMainNiceMatrix_i:n { #1 } }
    {
      \int_compare:nNnTF \c@jCol = 0
        {
          \int_compare:nNnF \c@iRow = { -1 }
            { \int_compare:nNnF \c@iRow = { \l_@@_last_row_int - 1 } { #1 } }
        }
      { \@@_OnlyMainNiceMatrix_i:n { #1 } }
    }
  }
```

This definition may seem complicated by we must remind that the number of row `\c@iRow` is incremented in the first cell of the row, *after* a potential vertical rule on the left side of the first cell.

The command `\@@_OnlyMainNiceMatrix_i:n` is only a short-cut which is used twice in the above command. This command must *not* be protected.

```
4315 \cs_new_protected:Npn \@@_OnlyMainNiceMatrix_i:n #1
  {
    \int_compare:nNnF \c@iRow = 0
      { \int_compare:nNnF \c@iRow = \l_@@_last_row_int { #1 } }
  }
```

Remember that `\c@iRow` is not always inferior to `\l_@@_last_row_int` because `\l_@@_last_row_int` may be equal to -2 or -1 (we can't write `\int_compare:nNnT \c@iRow < \l_@@_last_row_int`).

The following command will be executed in the `internal-code-after`. The rule will be drawn *before* the column `#1` (that is to say on the left side). `#2` is the number of consecutive occurrences of `\`.

```
4320 \cs_new_protected:Npn \@@_vline:nn #1 #2
  {
```

The following test is for the case where the user don't use all the columns specified in the preamble of the environment (for instance, a preamble of `|c|c|c|` but only two columns used).

```
4322 \int_compare:nNnT { #1 } < { \c@jCol + 2 }
  {
    \pgfpicture
    \@@_vline_i:nn { #1 } { #2 }
    \endpgfpicture
  }
}

4329 \cs_new_protected:Npn \@@_vline_i:nn #1 #2
  {
```

`\l_tmpa_t1` is the number of row and `\l_tmpb_t1` the number of column. When we have found a row corresponding to a rule to draw, we note its number in `\l_tmpc_t1`.

```
4331 \tl_set:Nx \l_tmpb_t1 { #1 }
4332 \tl_clear_new:N \l_tmpc_t1
4333 \int_step_variable:nNn \c@iRow \l_tmpa_t1
  {
```

The boolean `\g_tmpa_bool` indicates whether the small vertical rule will be drawn. If we find that it is in a block (a real block, created by `\Block` or a virtual block corresponding to a dotted line, created by `\Cdots`, `\Vdots`, etc.), we will set `\g_tmpa_bool` to `false` and the small vertical rule won't be drawn.

```

4335 \bool_gset_true:N \g_tmpa_bool
4336 \seq_map_inline:Nn \g_@@_pos_of_blocks_seq
4337   { \@@_test_vline_in_block:nnnn ##1 }
4338 \seq_map_inline:Nn \g_@@_pos_of_xdots_seq
4339   { \@@_test_vline_in_block:nnnn ##1 }
4340 \seq_map_inline:Nn \g_@@_pos_of_stroken_blocks_seq
4341   { \@@_test_vline_in_stroken_block:nnnn ##1 }
4342 \clist_if_empty:NF \l_@@_corners_clist
4343   \@@_test_in_corner_v:
4344 \bool_if:NTF \g_tmpa_bool
4345   {
4346     \tl_if_empty:NT \l_tmpc_tl

```

We keep in memory that we have a rule to draw.

```

4347   { \tl_set_eq:NN \l_tmpc_tl \l_tmpa_tl }
4348   }
4349   {
4350     \tl_if_empty:NF \l_tmpc_tl
4351     {
4352       \@@_vline_ii:nnnn
4353         { #1 }
4354         { #2 }
4355         \l_tmpc_tl
4356         { \int_eval:n { \l_tmpa_tl - 1 } }
4357         \tl_clear:N \l_tmpc_tl
4358     }
4359   }
4360 }
4361 \tl_if_empty:NF \l_tmpc_tl
4362 {
4363   \@@_vline_ii:nnnn
4364   { #1 }
4365   { #2 }
4366   \l_tmpc_tl
4367   { \int_use:N \c@jRow }
4368   \tl_clear:N \l_tmpc_tl
4369 }

4370 }

4371 \cs_new_protected:Npn \@@_test_in_corner_v:
4372 {
4373   \int_compare:nNnTF \l_tmpb_tl = { \@@_succ:n \c@jCol }
4374   {
4375     \seq_if_in:NxT
4376       \l_@@_corners_cells_seq
4377       { \l_tmpa_tl - \@@_pred:n \l_tmpb_tl }
4378       { \bool_set_false:N \g_tmpa_bool }
4379   }
4380   {
4381     \seq_if_in:NxT
4382       \l_@@_corners_cells_seq
4383       { \l_tmpa_tl - \l_tmpb_tl }
4384       {
4385         \int_compare:nNnTF \l_tmpb_tl = 1
4386           { \bool_set_false:N \g_tmpa_bool }
4387           {
4388             \seq_if_in:NxT
4389               \l_@@_corners_cells_seq
4390               { \l_tmpa_tl - \@@_pred:n \l_tmpb_tl }

```

```

4391           { \bool_set_false:N \g_tmpa_bool }
4392       }
4393   }
4394 }
4395 }

#1 is the number of the column; #2 is the number of vertical rules to draw (with potentially a color
between); #3 and #4 are the numbers of the rows between which the rule has to be drawn.

4396 \cs_new_protected:Npn \@@_vline_i:nnn #1 #2 #3 #4
4397 {
4398     \pgfrememberpicturepositiononpagetrue
4399     \pgf@relevantforpicturesizefalse
4400     \@@_qpoint:n { row - #3 }
4401     \dim_set_eq:NN \l_tmpa_dim \pgf@y
4402     \@@_qpoint:n { col - #1 }
4403     \dim_set_eq:NN \l_tmpb_dim \pgf@x
4404     \@@_qpoint:n { row - \@@_succ:n { #4 } }
4405     \dim_set_eq:NN \l_tmpc_dim \pgf@y
4406     \bool_lazy_and:nnT
4407         { \int_compare_p:nNn { #2 } > 1 }
4408         { ! \tl_if_blank_p:V \CT@drsc@ }
4409     {
4410         \group_begin:
4411         \CT@drsc@
4412         \dim_add:Nn \l_tmpa_dim { 0.5 \arrayrulewidth }
4413         \dim_sub:Nn \l_tmpc_dim { 0.5 \arrayrulewidth }
4414         \dim_set:Nn \l_tmpd_dim
4415             { \l_tmpb_dim - ( \doublerulesep + \arrayrulewidth ) * ( #2 - 1 ) }
4416         \pgfpathrectanglecorners
4417             { \pgfpoint \l_tmpb_dim \l_tmpa_dim }
4418             { \pgfpoint \l_tmpd_dim \l_tmpc_dim }
4419         \pgfusepath { fill }
4420         \group_end:
4421     }
4422     \pgfpathmoveto { \pgfpoint \l_tmpb_dim \l_tmpa_dim }
4423     \pgfpathlineto { \pgfpoint \l_tmpb_dim \l_tmpc_dim }
4424     \prg_replicate:nn { #2 - 1 }
4425     {
4426         \dim_sub:Nn \l_tmpb_dim \arrayrulewidth
4427         \dim_sub:Nn \l_tmpb_dim \doublerulesep
4428         \pgfpathmoveto { \pgfpoint \l_tmpb_dim \l_tmpa_dim }
4429         \pgfpathlineto { \pgfpoint \l_tmpb_dim \l_tmpc_dim }
4430     }
4431     \CT@arc@
4432     \pgfsetlinewidth { 1.1 \arrayrulewidth }
4433     \pgfsetrectcap
4434     \pgfusepathqstroke
4435 }

```

The following command draws a complete vertical rule in the column #1 (#2 is the number of consecutive rules specified by the number of | in the preamble). This command will be used if there is no block in the array (and the key `corners` is not used).

```

4436 \cs_new_protected:Npn \@@_vline_i_complete:nn #1 #2
4437     { \@@_vline_i:nnn { #1 } { #2 } 1 { \int_use:N \c@iRow } }

```

The command `\@@_draw_vlines:` draws all the vertical rules excepted in the blocks, in the virtual blocks (determined by a command such as `\Cdots`) and in the corners (if the key `corners` is used).

```

4438 \cs_new_protected:Npn \@@_draw_vlines:
4439 {
4440     \int_step_inline:nnn
4441         {

```

```

4442 \bool_if:nTF { \l_@@_NiceArray_bool && ! \l_@@_except_borders_bool }
4443   1 2
4444 }
4445 {
4446   \bool_if:nTF { \l_@@_NiceArray_bool && ! \l_@@_except_borders_bool }
4447     { \@@_succ:n \c@jCol }
4448     \c@jCol
4449 }
4450 {
4451   \tl_if_eq:NnF \l_@@_vlines_clist { all }
4452     { \clist_if_in:NnT \l_@@_vlines_clist { ##1 } }
4453     { \@@_vline:nn { ##1 } 1 }
4454 }
4455 }

```

The horizontal rules

The following command will be executed in the `internal-code-after`. The rule will be drawn *before* the row #1. #2 is the number of consecutive occurrences of `\Hline`.

```

4456 \cs_new_protected:Npn \@@_hline:nn #1 #2
4457 {
4458   \pgfpicture
4459   \@@_hline_i:nn { #1 } { #2 }
4460   \endpgfpicture
4461 }
4462 \cs_new_protected:Npn \@@_hline_i:nn #1 #2
4463 {

```

`\l_tmpa_tl` is the number of row and `\l_tmpb_tl` the number of column. When we have found a column corresponding to a rule to draw, we note its number in `\l_tmpc_tl`.

```

4464 \tl_set:Nn \l_tmpa_tl { #1 }
4465 \tl_clear_new:N \l_tmpc_tl
4466 \int_step_variable:nNn \c@jCol \l_tmpb_tl
4467 {

```

The boolean `\g_tmpa_bool` indicates whether the small horizontal rule will be drawn. If we find that it is in a block (a real block, created by `\Block` or a virtual block corresponding to a dotted line, created by `\Cdots`, `\Vdots`, etc.), we will set `\g_tmpa_bool` to `false` and the small horizontal rule won't be drawn.

```

4468 \bool_gset_true:N \g_tmpa_bool
4469 \seq_map_inline:Nn \g_@@_pos_of_blocks_seq
4470   { \@@_test_hline_in_block:nnnn ##1 }
4471 \seq_map_inline:Nn \g_@@_pos_of_xdots_seq
4472   { \@@_test_hline_in_block:nnnn ##1 }
4473 \seq_map_inline:Nn \g_@@_pos_of_stroken_blocks_seq
4474   { \@@_test_hline_in_stroken_block:nnnn ##1 }
4475 \clist_if_empty:NF \l_@@_corners_clist \@@_test_in_corner_h:
4476 \bool_if:NTF \g_tmpa_bool
4477 {
4478   \tl_if_empty:NT \l_tmpc_tl

```

We keep in memory that we have a rule to draw.

```

4479   { \tl_set_eq:NN \l_tmpc_tl \l_tmpb_tl }
4480 }
4481 {
4482   \tl_if_empty:NF \l_tmpc_tl
4483   {
4484     \@@_hline_ii:nnnn
4485       { #1 }
4486       { #2 }
4487     \l_tmpc_tl

```

```

4488          { \int_eval:n { \l_tmpb_tl - 1 } }
4489          \tl_clear:N \l_tmpc_tl
4490      }
4491  }
4492 \tl_if_empty:NF \l_tmpc_tl
4493 {
4495     \@@_hline_ii:nnnn
4496     { #1 }
4497     { #2 }
4498     \l_tmpc_tl
4499     { \int_use:N \c@jCol }
4500     \tl_clear:N \l_tmpc_tl
4501 }
4502 }

4503 \cs_new_protected:Npn \@@_test_in_corner_h:
4504 {
4505     \int_compare:nNnTF \l_tmpa_tl = { \@@_succ:n \c@iRow }
4506     {
4507         \seq_if_in:NxT
4508         \l_@@_corners_cells_seq
4509         { \@@_pred:n \l_tmpa_tl - \l_tmpb_tl }
4510         { \bool_set_false:N \g_tmpa_bool }
4511     }
4512 {
4513     \seq_if_in:NxT
4514         \l_@@_corners_cells_seq
4515         { \l_tmpa_tl - \l_tmpb_tl }
4516     {
4517         \int_compare:nNnTF \l_tmpa_tl = 1
4518         { \bool_set_false:N \g_tmpa_bool }
4519         {
4520             \seq_if_in:NxT
4521                 \l_@@_corners_cells_seq
4522                 { \@@_pred:n \l_tmpa_tl - \l_tmpb_tl }
4523                 { \bool_set_false:N \g_tmpa_bool }
4524         }
4525     }
4526 }
4527 }

```

#1 is the number of the row; #2 is the number of horizontal rules to draw (with potentially a color between); #3 and #4 are the number of the columns between which the rule has to be drawn.

```

4528 \cs_new_protected:Npn \@@_hline_ii:nnnn #1 #2 #3 #4
4529 {
4530     \pgfrememberpicturepositiononpagetrue
4531     \pgf@relevantforpicturesizefalse
4532     \@@_qpoint:n { col - #3 }
4533     \dim_set_eq:NN \l_tmpa_dim \pgf@x
4534     \@@_qpoint:n { row - #1 }
4535     \dim_set_eq:NN \l_tmpb_dim \pgf@y
4536     \@@_qpoint:n { col - \@@_succ:n { #4 } }
4537     \dim_set_eq:NN \l_tmpc_dim \pgf@x
4538     \bool_lazy_and:nnT
4539     { \int_compare_p:nNn { #2 } > 1 }
4540     { ! \tl_if_blank_p:V \CT@drsc@ }
4541     {
4542         \group_begin:
4543         \CT@drsc@
4544         \dim_set:Nn \l_tmpd_dim
4545         { \l_tmpb_dim - ( \doublerulesep + \arrayrulewidth ) * ( #2 - 1 ) }

```

```

4546     \pgfpathrectanglecorners
4547         { \pgfpoint \l_tmpa_dim \l_tmpb_dim }
4548         { \pgfpoint \l_tmpc_dim \l_tmpd_dim }
4549     \pgfusepathqfill
4550     \group_end:
4551     }
4552 \pgfpathmoveto { \pgfpoint \l_tmpa_dim \l_tmpb_dim }
4553 \pgfpathlineto { \pgfpoint \l_tmpc_dim \l_tmpb_dim }
4554 \prg_replicate:nn { #2 - 1 }
4555     {
4556         \dim_sub:Nn \l_tmpb_dim \arrayrulewidth
4557         \dim_sub:Nn \l_tmpb_dim \doublerulesep
4558         \pgfpathmoveto { \pgfpoint \l_tmpa_dim \l_tmpb_dim }
4559         \pgfpathlineto { \pgfpoint \l_tmpc_dim \l_tmpb_dim }
4560     }
4561 \CT@arc@  

4562 \pgfsetlinewidth { 1.1 \arrayrulewidth }
4563 \pgfsetrectcap
4564 \pgfusepathqstroke
4565 }

4566 \cs_new_protected:Npn \@@_hline_i_complete:nn #1 #2
4567     { \@@_hline_ii:nnnn { #1 } { #2 } 1 { \int_use:N \c@jCol } }


```

The command `\@@_draw_hlines`: draws all the horizontal rules excepted in the blocks (even the virtual drawn determined by commands such as `\Cdots` and in the corners (if the key `corners` is used).

```

4568 \cs_new_protected:Npn \@@_draw_hlines:
4569     {
4570         \int_step_inline:nnn
4571             {
4572                 \bool_if:nTF { \l_@@_NiceArray_bool && ! \l_@@_except_borders_bool }
4573                     1 2
4574             }
4575             {
4576                 \bool_if:nTF { \l_@@_NiceArray_bool && ! \l_@@_except_borders_bool }
4577                     { \@@_succ:n \c@iRow }
4578                     \c@iRow
4579             }
4580             {
4581                 \tl_if_eq:NnF \l_@@_hlines_clist { all }
4582                     { \clist_if_in:NnT \l_@@_hlines_clist { ##1 } }
4583                     { \@@_hline:nn { ##1 } 1 }
4584             }
4585     }


```

The command `\@@_Hline:` will be linked to `\Hline` in the environments of `nicematrix`.

```

4586 \cs_set:Npn \@@_Hline: { \noalign { \ifnum 0 = `} \fi \@@_Hline_i:n { 1 } }


```

The argument of the command `\@@_Hline_i:n` is the number of successive `\Hline` found.

```

4587 \cs_set:Npn \@@_Hline_i:n #1
4588     {
4589         \peek_meaning_ignore_spaces:NTF \Hline
4590             { \@@_Hline_ii:nn { #1 + 1 } }
4591             { \@@_Hline_iii:n { #1 } }
4592     }

4593 \cs_set:Npn \@@_Hline_ii:nn #1 #2 { \@@_Hline_i:n { #1 } }
4594 \cs_set:Npn \@@_Hline_iii:n #1
4595     {
4596         \skip_vertical:n
4597             {


```

```

4598     \arrayrulewidth * ( #1 )
4599     + \doublerulesep * ( \int_max:nn 0 { #1 - 1 } )
4600   }
4601 \tl_gput_right:Nx \g_@@_internal_code_after_tl
4602   { \@@_hline:nn { \@@_succ:n { \c@iRow } } { #1 } }
4603   \ifnum 0 = `{ \fi }
4604 }

```

The key `hvlines`

The following command tests whether the current position in the array (given by `\l_tmpa_tl` for the row and `\l_tmpb_tl` for the column) would provide an horizontal rule towards the right in the block delimited by the four arguments `#1`, `#2`, `#3` and `#4`. If this rule would be in the block (it must not be drawn), the boolean `\l_tmpa_bool` is set to `false`.

```

4605 \cs_new_protected:Npn \@@_test_hline_in_block:nnnn #1 #2 #3 #4
4606 {
4607   \bool_lazy_all:nT
4608   {
4609     { \int_compare_p:nNn \l_tmpa_tl > { #1 } }
4610     { \int_compare_p:nNn \l_tmpa_tl < { #3 + 1 } }
4611     { \int_compare_p:nNn \l_tmpb_tl > { #2 - 1 } }
4612     { \int_compare_p:nNn \l_tmpb_tl < { #4 + 1 } }
4613   }
4614   { \bool_gset_false:N \g_tmpa_bool }
4615 }

```

The same for vertical rules.

```

4616 \cs_new_protected:Npn \@@_test_vline_in_block:nnnn #1 #2 #3 #4
4617 {
4618   \bool_lazy_all:nT
4619   {
4620     { \int_compare_p:nNn \l_tmpa_tl > { #1 - 1 } }
4621     { \int_compare_p:nNn \l_tmpa_tl < { #3 + 1 } }
4622     { \int_compare_p:nNn \l_tmpb_tl > { #2 } }
4623     { \int_compare_p:nNn \l_tmpb_tl < { #4 + 1 } }
4624   }
4625   { \bool_gset_false:N \g_tmpa_bool }
4626 }

4627 \cs_new_protected:Npn \@@_test_hline_in_stroken_block:nnnn #1 #2 #3 #4
4628 {
4629   \bool_lazy_all:nT
4630   {
4631     { \int_compare_p:nNn \l_tmpa_tl > { #1 - 1 } }
4632     { \int_compare_p:nNn \l_tmpa_tl < { #3 + 2 } }
4633     { \int_compare_p:nNn \l_tmpb_tl > { #2 - 1 } }
4634     { \int_compare_p:nNn \l_tmpb_tl < { #4 + 1 } }
4635   }
4636   { \bool_gset_false:N \g_tmpa_bool }
4637 }

4638 \cs_new_protected:Npn \@@_test_vline_in_stroken_block:nnnn #1 #2 #3 #4
4639 {
4640   \bool_lazy_all:nT
4641   {
4642     { \int_compare_p:nNn \l_tmpa_tl > { #1 - 1 } }
4643     { \int_compare_p:nNn \l_tmpa_tl < { #3 + 1 } }
4644     { \int_compare_p:nNn \l_tmpb_tl > { #2 - 1 } }
4645     { \int_compare_p:nNn \l_tmpb_tl < { #4 + 2 } }
4646   }
4647   { \bool_gset_false:N \g_tmpa_bool }
4648 }

```

The key corners

When the key `corners` is raised, the rules are not drawn in the corners. Of course, we have to compute the corners before we begin to draw the rules.

```
4649 \cs_new_protected:Npn \@@_compute_corners:
4650 {
```

The sequence `\l_@@_corners_cells_seq` will be the sequence of all the empty cells (and not in a block) considered in the corners of the array.

```
4651   \seq_clear_new:N \l_@@_corners_cells_seq
4652   \clist_map_inline:Nn \l_@@_corners_clist
4653   {
4654     \str_case:nnF { ##1 }
4655     {
4656       { NW }
4657       { \@@_compute_a_corner:nnnnnn 1 1 1 1 \c@iRow \c@jCol }
4658       { NE }
4659       { \@@_compute_a_corner:nnnnnn 1 \c@jCol 1 { -1 } \c@iRow 1 }
4660       { SW }
4661       { \@@_compute_a_corner:nnnnnn \c@iRow 1 { -1 } 1 1 \c@jCol }
4662       { SE }
4663       { \@@_compute_a_corner:nnnnnn \c@iRow \c@jCol { -1 } { -1 } 1 1 }
4664     }
4665     { \@@_error:nn { bad-corner } { ##1 } }
4666   }
```

Even if the user has used the key `corners` (or the key `hvlines-except-corners`), the list of cells in the corners may be empty.

```
4667 \seq_if_empty:NF \l_@@_corners_cells_seq
4668 {
```

You write on the aux file the list of the cells which are in the (empty) corners because you need that information in the `\CodeBefore` since the commands which color the `rows`, `columns` and `cells` must not color the cells in the corners.

```
4669   \tl_gput_right:Nx \g_@@_aux_tl
4670   {
4671     \seq_set_from_clist:Nn \exp_not:N \l_@@_corners_cells_seq
4672     { \seq_use:Nnnn \l_@@_corners_cells_seq , , , }
4673     \iow_newline:
4674   }
4675 }
```

“Computing a corner” is determining all the empty cells (which are not in a block) that belong to that corner. These cells will be added to the sequence `\l_@@_corners_cells_seq`.

The six arguments of `\@@_compute_a_corner:nnnnnn` are as follow:

- #1 and #2 are the number of row and column of the cell which is actually in the corner;
- #3 and #4 are the steps in rows and the step in columns when moving from the corner;
- #5 is the number of the final row when scanning the rows from the corner;
- #6 is the number of the final column when scanning the columns from the corner.

```
4677 \cs_new_protected:Npn \@@_compute_a_corner:nnnnnn #1 #2 #3 #4 #5 #6
4678 {
```

For the explanations and the name of the variables, we consider that we are computing the left-upper corner.

First, we try to determine which is the last empty cell (and not in a block: we won’t add that precision any longer) in the column of number 1. The flag `\l_tmpa_bool` will be raised when a non-empty cell is found.

```
4679   \bool_set_false:N \l_tmpa_bool
```

```

4680 \int_zero_new:N \l_@@_last_empty_row_int
4681 \int_set:Nn \l_@@_last_empty_row_int { #1 }
4682 \int_step_inline:nnnn { #1 } { #3 } { #5 }
4683 {
4684     \@@_test_if_cell_in_a_block:nn { ##1 } { \int_eval:n { #2 } }
4685     \bool_lazy_or:nnTF
4686     {
4687         \cs_if_exist_p:c
4688         { pgf @ sh @ ns @ \@@_env: - ##1 - \int_eval:n { #2 } }
4689     }
4690     \l_tmpb_bool
4691     { \bool_set_true:N \l_tmpa_bool }
4692     {
4693         \bool_if:NF \l_tmpa_bool
4694         { \int_set:Nn \l_@@_last_empty_row_int { ##1 } }
4695     }
4696 }

```

Now, you determine the last empty cell in the row of number 1.

```

4697 \bool_set_false:N \l_tmpa_bool
4698 \int_zero_new:N \l_@@_last_empty_column_int
4699 \int_set:Nn \l_@@_last_empty_column_int { #2 }
4700 \int_step_inline:nnnn { #2 } { #4 } { #6 }
4701 {
4702     \@@_test_if_cell_in_a_block:nn { \int_eval:n { #1 } } { ##1 }
4703     \bool_lazy_or:nnTF
4704     \l_tmpb_bool
4705     {
4706         \cs_if_exist_p:c
4707         { pgf @ sh @ ns @ \@@_env: - \int_eval:n { #1 } - ##1 }
4708     }
4709     { \bool_set_true:N \l_tmpa_bool }
4710     {
4711         \bool_if:NF \l_tmpa_bool
4712         { \int_set:Nn \l_@@_last_empty_column_int { ##1 } }
4713     }
4714 }

```

Now, we loop over the rows.

```

4715 \int_step_inline:nnnn { #1 } { #3 } \l_@@_last_empty_row_int
4716 {

```

We treat the row number ##1 with another loop.

```

4717 \bool_set_false:N \l_tmpa_bool
4718 \int_step_inline:nnnn { #2 } { #4 } \l_@@_last_empty_column_int
4719 {
4720     \@@_test_if_cell_in_a_block:nn { ##1 } { #####1 }
4721     \bool_lazy_or:nnTF
4722     \l_tmpb_bool
4723     {
4724         \cs_if_exist_p:c
4725         { pgf @ sh @ ns @ \@@_env: - ##1 - #####1 }
4726     }
4727     { \bool_set_true:N \l_tmpa_bool }
4728     {
4729         \bool_if:NF \l_tmpa_bool
4730         {
4731             \int_set:Nn \l_@@_last_empty_column_int { #####1 }
4732             \seq_put_right:Nn
4733             \l_@@_corners_cells_seq
4734             { ##1 - #####1 }
4735         }
4736     }
4737 }
4738 }

```

```
4739 }
```

The following macro tests whether a cell is in (at least) one of the blocks of the array (or in a cell with a \diagbox).

The flag \l_tmpb_bool will be raised if the cell #1-#2 is in a block (or in a cell with a \diagbox).

```
4740 \cs_new_protected:Npn \@@_test_if_cell_in_a_block:n#1#2
4741 {
4742     \int_set:Nn \l_tmpa_int { #1 }
4743     \int_set:Nn \l_tmpb_int { #2 }
4744     \bool_set_false:N \l_tmpb_bool
4745     \seq_map_inline:Nn \g_@_pos_of_blocks_seq
4746         { \@@_test_if_cell_in_block:nnnnnn \l_tmpa_int \l_tmpb_int ##1 }
4747 }
4748 \cs_new_protected:Npn \@@_test_if_cell_in_block:nnnnnnn#1#2#3#4#5#6
4749 {
4750     \int_compare:nNnT { #3 } < { \@@_succ:n { #1 } }
4751     {
4752         \int_compare:nNnT { #1 } < { \@@_succ:n { #5 } }
4753         {
4754             \int_compare:nNnT { #4 } < { \@@_succ:n { #2 } }
4755             {
4756                 \int_compare:nNnT { #2 } < { \@@_succ:n { #6 } }
4757                 { \bool_set_true:N \l_tmpb_bool }
4758             }
4759         }
4760     }
4761 }
```

The commands to draw dotted lines to separate columns and rows

These commands don't use the normal nodes, the medium nor the large nodes. They only use the col nodes and the row nodes.

Horizontal dotted lines

The following command must *not* be protected because it's meant to be expanded in a \noalign.

```
4762 \cs_new:Npn \@@_hdottedline:
4763 {
4764     \noalign { \skip_vertical:N 2\l_@@_radius_dim }
4765     \@@_hdottedline_i:
4766 }
```

On the other side, the following command should be protected.

```
4767 \cs_new_protected:Npn \@@_hdottedline_i:
4768 {
```

We write in the code-after the instruction that will actually draw the dotted line. It's not possible to draw this dotted line now because we don't know the length of the line (we don't even know the number of columns).

```
4769 \tl_gput_right:Nx \g_@@_internal_code_after_tl
4770     { \@@_hdottedline:n { \int_use:N \c@iRow } }
4771 }
```

The command \@@_hdottedline:n is the command written in the \CodeAfter that will actually draw the dotted line. Its argument is the number of the row *before* which we will draw the row.

```
4772 \AtBeginDocument
4773 {
```

We recall that, when externalization is used, `\tikzpicture` and `\endtikzpicture` (or `\pgfpicture` and `\endpgfpicture`) must be directly “visible”. That’s why we construct now a version of `\@@_hdottedline:n` with the right environment (`\begin{pgfpicture}\end{pgfpicture}` or `\begin{tikzpicture}...\end{tikzpicture}`).

```

4774 \cs_new_protected:Npx \@@_hdottedline:n #1
4775 {
4776     \bool_set_true:N \exp_not:N \l_@@_initial_open_bool
4777     \bool_set_true:N \exp_not:N \l_@@_final_open_bool
4778     \c_@@_pgfortikzpicture_tl
4779     \@@_hdottedline_i:n { #1 }
4780     \c_@@_endpgfortikzpicture_tl
4781 }
4782 }
```

The following command *must* be protected since it is used in the construction of `\@@_hdottedline:n`.

```

4783 \cs_new_protected:Npn \@@_hdottedline_i:n #1
4784 {
4785     \pgfrememberpicturepositiononpagetrue
4786     \@@_qpoint:n { row - #1 }
```

We do a translation par `-\l_@@_radius_dim` because we want the dotted line to have exactly the same position as a vertical rule drawn by “|” (considering the rule having a width equal to the diameter of the dots).

```

4787 \dim_set_eq:NN \l_@@_y_initial_dim \pgf@y
4788 \dim_sub:Nn \l_@@_y_initial_dim \l_@@_radius_dim
4789 \dim_set_eq:NN \l_@@_y_final_dim \l_@@_y_initial_dim
```

The dotted line will be extended if the user uses `margin` (or `left-margin` and `right-margin`).

The aim is that, by standard the dotted line fits between square brackets (`\hline` doesn’t).

```
\begin{bNiceMatrix}
1 & 2 & 3 & 4 \\
\hline
1 & 2 & 3 & 4 \\
\hdottedline
1 & 2 & 3 & 4
\end{bNiceMatrix}
```

$$\begin{bmatrix} 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ \vdots & \vdots & \vdots & \vdots \\ 1 & 2 & 3 & 4 \end{bmatrix}$$

But, if the user uses `margin`, the dotted line extends to have the same width as a `\hline`.

```
\begin{bNiceMatrix}[margin]
1 & 2 & 3 & 4 \\
\hline
1 & 2 & 3 & 4 \\
\hdottedline
1 & 2 & 3 & 4
\end{bNiceMatrix}
```

$$\begin{bmatrix} 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ \vdots & \vdots & \vdots & \vdots \\ 1 & 2 & 3 & 4 \end{bmatrix}$$

```

4790 \@@_qpoint:n { col - 1 }
4791 \dim_set:Nn \l_@@_x_initial_dim
4792 {
4793     \pgf@x +
```

We do a reduction by `\arraycolsep` for the environments with delimiters (and not for the other).

```

4794 \bool_if:NTF \l_@@_NiceArray_bool \c_zero_dim \arraycolsep
4795 - \l_@@_left_margin_dim
4796 }
4797 \@@_qpoint:n { col - \@@_succ:n \c@jCol }
4798 \dim_set:Nn \l_@@_x_final_dim
4799 {
5000     \pgf@x -
5001     \bool_if:NTF \l_@@_NiceArray_bool \c_zero_dim \arraycolsep
5002 + \l_@@_right_margin_dim
5003 }
```

For reasons purely aesthetic, we do an adjustment in the case of a rounded bracket. The correction by $0.5 \l_@@_inter_dots_dim$ is *ad hoc* for a better result.

```
4804 \tl_if_eq:NnF \g_@@_left_delim_tl (
4805   { \dim_gadd:Nn \l_@@_x_initial_dim { 0.5 \l_@@_inter_dots_dim } }
4806 \tl_if_eq:NnF \g_@@_right_delim_tl )
4807   { \dim_gsub:Nn \l_@@_x_final_dim { 0.5 \l_@@_inter_dots_dim } }
```

Up to now, we have no option to control the style of the lines drawn by `\hdottedline` and the specifier ":" in the preamble. That's why we impose the style `standard`.

```
4808 \tl_set_eq:NN \l_@@_xdots_line_style_tl \c_@@_standard_tl
4809 \@@_draw_line:
4810 }
```

Vertical dotted lines

```
4811 \cs_new_protected:Npn \@@_vdottedline:n #1
4812 {
4813   \bool_set_true:N \l_@@_initial_open_bool
4814   \bool_set_true:N \l_@@_final_open_bool
```

We recall that, when externalization is used, `\tikzpicture` and `\endtikzpicture` (or `\pgfpicture` and `\endpgfpicture`) must be directly “visible”.

```
4815 \bool_if:NTF \c_@@_tikz_loaded_bool
4816 {
4817   \tikzpicture
4818   \@@_vdottedline_i:n { #1 }
4819   \endtikzpicture
4820 }
4821 {
4822   \pgfpicture
4823   \@@_vdottedline_i:n { #1 }
4824   \endpgfpicture
4825 }
4826 }
```

```
4827 \cs_new_protected:Npn \@@_vdottedline_i:n #1
4828 {
```

The command `\CT@arc@` is a command of `colortbl` which sets the color of the rules in the array. The package `nicematrix` uses it even if `colortbl` is not loaded.

```
4829 \CT@arc@
4830 \pgfrememberpicturepositiononpagetrue
4831 \@@_qpoint:n { col - \int_eval:n { #1 + 1 } }
```

We do a translation `par -\l_@@_radius_dim` because we want the dotted line to have exactly the same position as a vertical rule drawn by “|” (considering the rule having a width equal to the diameter of the dots).

```
4832 \dim_set:Nn \l_@@_x_initial_dim { \pgf@x - \l_@@_radius_dim }
4833 \dim_set:Nn \l_@@_x_final_dim { \pgf@x - \l_@@_radius_dim }
4834 \@@_qpoint:n { row - 1 }
```

We arbitrary decrease the height of the dotted line by a quantity equal to `\l_@@_inter_dots_dim` in order to improve the visual impact.

```
4835 \dim_set:Nn \l_@@_y_initial_dim { \pgf@y - 0.5 \l_@@_inter_dots_dim }
4836 \@@_qpoint:n { row - \@@_succ:n \c@iRow }
4837 \dim_set:Nn \l_@@_y_final_dim { \pgf@y + 0.5 \l_@@_inter_dots_dim }
```

Up to now, we have no option to control the style of the lines drawn by `\hdottedline` and the specifier ":" in the preamble. That's why we impose the style `standard`.

```
4838 \tl_set_eq:NN \l_@@_xdots_line_style_tl \c_@@_standard_tl
4839 \@@_draw_line:
4840 }
```

The environment {NiceMatrixBlock}

The following flag will be raised when all the columns of the environments of the block must have the same width in “auto” mode.

```
4841 \bool_new:N \l_@@_block_auto_columns_width_bool
```

Up to now, there is only one option available for the environment {NiceMatrixBlock}.

```
4842 \keys_define:nn { NiceMatrix / NiceMatrixBlock }
4843 {
4844     auto-columns-width .code:n =
4845     {
4846         \bool_set_true:N \l_@@_block_auto_columns_width_bool
4847         \dim_gzero_new:N \g_@@_max_cell_width_dim
4848         \bool_set_true:N \l_@@_auto_columns_width_bool
4849     }
4850 }
```



```
4851 \NewDocumentEnvironment { NiceMatrixBlock } { ! O { } }
4852 {
4853     \int_gincr:N \g_@@_NiceMatrixBlock_int
4854     \dim_zero:N \l_@@_columns_width_dim
4855     \keys_set:nn { NiceMatrix / NiceMatrixBlock } { #1 }
4856     \bool_if:NT \l_@@_block_auto_columns_width_bool
4857     {
4858         \cs_if_exist:cT { @@_max_cell_width_ \int_use:N \g_@@_NiceMatrixBlock_int }
4859         {
4860             \exp_args:NNo \dim_set:Nn \l_@@_columns_width_dim
4861             { @@_max_cell_width_ \int_use:N \g_@@_NiceMatrixBlock_int }
4862         }
4863     }
4864 }
```

At the end of the environment {NiceMatrixBlock}, we write in the main .aux file instructions for the column width of all the environments of the block (that’s why we have stored the number of the first environment of the block in the counter \l_@@_first_env_block_int).

```
4865 {
4866     \bool_if:NT \l_@@_block_auto_columns_width_bool
4867     {
4868         \iow_shipout:Nn \o mainaux \ExplSyntaxOn
4869         \iow_shipout:Nx \o mainaux
4870         {
4871             \cs_gset:cpn
4872             { @@ _ max _ cell _ width _ \int_use:N \g_@@_NiceMatrixBlock_int }
4873         }
4874     }
4875     \iow_shipout:Nn \o mainaux \ExplSyntaxOff
4876 }
4877 }
```

The extra nodes

First, two variants of the functions \dim_min:nn and \dim_max:nn.

```
4878 \cs_generate_variant:Nn \dim_min:nn { v n }
4879 \cs_generate_variant:Nn \dim_max:nn { v n }
```

The following command is called in \@@_use_arraybox_with_notes_c: just before the construction of the blocks (if the creation of medium nodes is required, medium nodes are also created for the blocks and that construction uses the standard medium nodes).

```

4880 \cs_new_protected:Npn \@@_create_extra_nodes:
4881 {
4882     \bool_if:nTF \l_@@_medium_nodes_bool
4883     {
4884         \bool_if:NTF \l_@@_large_nodes_bool
4885             \@@_create_medium_and_large_nodes:
4886             \@@_create_medium_nodes:
4887     }
4888     { \bool_if:NT \l_@@_large_nodes_bool \@@_create_large_nodes: }
4889 }

```

We have three macros of creation of nodes: `\@@_create_medium_nodes:`, `\@@_create_large_nodes:` and `\@@_create_medium_and_large_nodes:`.

We have to compute the mathematical coordinates of the “medium nodes”. These mathematical coordinates are also used to compute the mathematical coordinates of the “large nodes”. That’s why we write a command `\@@_computations_for_medium_nodes:` to do these computations.

The command `\@@_computations_for_medium_nodes:` must be used in a `{pgfpicture}`.

For each row i , we compute two dimensions `l_@@_row_i_min_dim` and `l_@@_row_i_max_dim`. The dimension `l_@@_row_i_min_dim` is the minimal y -value of all the cells of the row i . The dimension `l_@@_row_i_max_dim` is the maximal y -value of all the cells of the row i .

Similarly, for each column j , we compute two dimensions `l_@@_column_j_min_dim` and `l_@@_column_j_max_dim`. The dimension `l_@@_column_j_min_dim` is the minimal x -value of all the cells of the column j . The dimension `l_@@_column_j_max_dim` is the maximal x -value of all the cells of the column j .

Since these dimensions will be computed as maximum or minimum, we initialize them to `\c_max_dim` or `-\c_max_dim`.

```

4890 \cs_new_protected:Npn \@@_computations_for_medium_nodes:
4891 {
4892     \int_step_variable:nnNn \l_@@_first_row_int \g_@@_row_total_int \@@_i:
4893     {
4894         \dim_zero_new:c { l_@@_row_\@@_i: _min_dim }
4895         \dim_set_eq:cN { l_@@_row_\@@_i: _min_dim } \c_max_dim
4896         \dim_zero_new:c { l_@@_row_\@@_i: _max_dim }
4897         \dim_set:cn { l_@@_row_\@@_i: _max_dim } { - \c_max_dim }
4898     }
4899     \int_step_variable:nnNn \l_@@_first_col_int \g_@@_col_total_int \@@_j:
4900     {
4901         \dim_zero_new:c { l_@@_column_\@@_j: _min_dim }
4902         \dim_set_eq:cN { l_@@_column_\@@_j: _min_dim } \c_max_dim
4903         \dim_zero_new:c { l_@@_column_\@@_j: _max_dim }
4904         \dim_set:cn { l_@@_column_\@@_j: _max_dim } { - \c_max_dim }
4905     }

```

We begin the two nested loops over the rows and the columns of the array.

```

4906     \int_step_variable:nnNn \l_@@_first_row_int \g_@@_row_total_int \@@_i:
4907     {
4908         \int_step_variable:nnNn
4909             \l_@@_first_col_int \g_@@_col_total_int \@@_j:

```

If the cell $(i-j)$ is empty or an implicit cell (that is to say a cell after implicit ampersands `&`) we don’t update the dimensions we want to compute.

```

4910     {
4911         \cs_if_exist:cT
4912             { pgf @ sh @ ns @ \@@_env: - \@@_i: - \@@_j: }

```

We retrieve the coordinates of the anchor `south west` of the (normal) node of the cell $(i-j)$. They will be stored in `\pgf@x` and `\pgf@y`.

```

4913     {
4914         \pgfpointanchor { \@@_env: - \@@_i: - \@@_j: } { south-west }
4915         \dim_set:cn { l_@@_row_\@@_i: _min_dim}

```

```

4916     { \dim_min:vn { l_@@_row _ \@@_i: _min_dim } \pgf@y }
4917     \seq_if_in:NxF \g_@@_multicolumn_cells_seq { \@@_i: - \@@_j: }
4918     {
4919         \dim_set:cn { l_@@_column _ \@@_j: _min_dim}
4920         { \dim_min:vn { l_@@_column _ \@@_j: _min_dim } \pgf@x }
4921     }

```

We retrieve the coordinates of the anchor `north east` of the (normal) node of the cell $(i-j)$. They will be stored in `\pgf@x` and `\pgf@y`.

```

4922     \pgfpointanchor { \@@_env: - \@@_i: - \@@_j: } { north-east }
4923     \dim_set:cn { l_@@_row _ \@@_i: _ max_dim }
4924     { \dim_max:vn { l_@@_row _ \@@_i: _ max_dim } \pgf@y }
4925     \seq_if_in:NxF \g_@@_multicolumn_cells_seq { \@@_i: - \@@_j: }
4926     {
4927         \dim_set:cn { l_@@_column _ \@@_j: _ max_dim }
4928         { \dim_max:vn { l_@@_column _ \@@_j: _ max_dim } \pgf@x }
4929     }
4930     }
4931 }
4932 }

```

Now, we have to deal with empty rows or empty columns since we don't have created nodes in such rows and columns.

```

4933 \int_step_variable:nnNn \l_@@_first_row_int \g_@@_row_total_int \@@_i:
4934 {
4935     \dim_compare:nNnT
4936     { \dim_use:c { l_@@_row _ \@@_i: _ min _ dim } } = \c_max_dim
4937     {
4938         \@@_qpoint:n { row - \@@_i: - base }
4939         \dim_set:cn { l_@@_row _ \@@_i: _ max _ dim } \pgf@y
4940         \dim_set:cn { l_@@_row _ \@@_i: _ min _ dim } \pgf@y
4941     }
4942 }
4943 \int_step_variable:nnNn \l_@@_first_col_int \g_@@_col_total_int \@@_j:
4944 {
4945     \dim_compare:nNnT
4946     { \dim_use:c { l_@@_column _ \@@_j: _ min _ dim } } = \c_max_dim
4947     {
4948         \@@_qpoint:n { col - \@@_j: }
4949         \dim_set:cn { l_@@_column _ \@@_j: _ max _ dim } \pgf@y
4950         \dim_set:cn { l_@@_column _ \@@_j: _ min _ dim } \pgf@y
4951     }
4952 }
4953 }

```

Here is the command `\@@_create_medium_nodes:`. When this command is used, the “medium nodes” are created.

```

4954 \cs_new_protected:Npn \@@_create_medium_nodes:
4955 {
4956     \pgfpicture
4957     \pgfrememberpicturepositiononpagetrue
4958     \pgf@relevantforpicturesizefalse
4959     \@@_computations_for_medium_nodes:

```

Now, we can create the “medium nodes”. We use a command `\@@_create_nodes:` because this command will also be used for the creation of the “large nodes”.

```

4960     \tl_set:Nn \l_@@_suffix_tl { -medium }
4961     \@@_create_nodes:
4962     \endpgfpicture
4963 }

```

The command `\@_create_large_nodes:` must be used when we want to create only the “large nodes” and not the medium ones⁶². However, the computation of the mathematical coordinates of the “large nodes” needs the computation of the mathematical coordinates of the “medium nodes”. Hence, we use first `\@_computations_for_medium_nodes:` and then the command `\@_computations_for_large_nodes:`.

```

4964 \cs_new_protected:Npn \@_create_large_nodes:
4965 {
4966     \pgfpicture
4967         \pgfrememberpicturepositiononpagetrue
4968         \pgf@relevantforpicturesizefalse
4969         @_computations_for_medium_nodes:
4970         @_computations_for_large_nodes:
4971         \tl_set:Nn \l_@@_suffix_tl { - large }
4972         @_create_nodes:
4973     \endpgfpicture
4974 }
4975 \cs_new_protected:Npn \@_create_medium_and_large_nodes:
4976 {
4977     \pgfpicture
4978         \pgfrememberpicturepositiononpagetrue
4979         \pgf@relevantforpicturesizefalse
4980         @_computations_for_medium_nodes:

```

Now, we can create the “medium nodes”. We use a command `\@_create_nodes:` because this command will also be used for the creation of the “large nodes”.

```

4981     \tl_set:Nn \l_@@_suffix_tl { - medium }
4982     @_create_nodes:
4983     @_computations_for_large_nodes:
4984     \tl_set:Nn \l_@@_suffix_tl { - large }
4985     @_create_nodes:
4986 \endpgfpicture
4987 }
```

For “large nodes”, the exterior rows and columns don’t interfer. That’s why the loop over the columns will start at 1 and stop at `\c@jCol` (and not `\g_@@_col_total_int`). Idem for the rows.

```

4988 \cs_new_protected:Npn \@_computations_for_large_nodes:
4989 {
4990     \int_set:Nn \l_@@_first_row_int 1
4991     \int_set:Nn \l_@@_first_col_int 1
```

We have to change the values of all the dimensions `l_@@_row_i_min_dim`, `l_@@_row_i_max_dim`, `l_@@_column_j_min_dim` and `l_@@_column_j_max_dim`.

```

4992     \int_step_variable:nNn { \c@iRow - 1 } \@_i:
4993     {
4994         \dim_set:cn { l_@@_row _ \@@_i: _ min _ dim }
4995         {
4996             (
4997                 \dim_use:c { l_@@_row _ \@@_i: _ min _ dim } +
4998                 \dim_use:c { l_@@_row _ \@@_succ:n \@@_i: _ max _ dim }
4999             )
5000             / 2
5001         }
5002         \dim_set_eq:cc { l_@@_row _ \@@_succ:n \@@_i: _ max _ dim }
5003         { l_@@_row_\@@_i: _min_dim }
5004     }
5005     \int_step_variable:nNn { \c@jCol - 1 } \@_j:
5006     {
5007         \dim_set:cn { l_@@_column _ \@@_j: _ max _ dim }
5008         {
```

⁶²If we want to create both, we have to use `\@_create_medium_and_large_nodes:`

```

5009      (
5010          \dim_use:c { l_@@_column _ \@@_j: _ max _ dim } +
5011          \dim_use:c
5012              { l_@@_column _ \@@_succ:n \@@_j: _ min _ dim }
5013      )
5014      / 2
5015  }
5016 \dim_set_eq:cc { l_@@_column _ \@@_succ:n \@@_j: _ min _ dim }
5017     { l_@@_column _ \@@_j: _ max _ dim }
5018 }

```

Here, we have to use `\dim_sub:cn` because of the number 1 in the name.

```

5019 \dim_sub:cn
5020     { l_@@_column _ 1 _ min _ dim }
5021     \l_@@_left_margin_dim
5022 \dim_add:cn
5023     { l_@@_column _ \int_use:N \c@jCol _ max _ dim }
5024     \l_@@_right_margin_dim
5025 }

```

The command `\@@_create_nodes:` is used twice: for the construction of the “medium nodes” and for the construction of the “large nodes”. The nodes are constructed with the value of all the dimensions `l_@@_row_i_min_dim`, `l_@@_row_i_max_dim`, `l_@@_column_j_min_dim` and `l_@@_column_j_max_dim`. Between the construction of the “medium nodes” and the “large nodes”, the values of these dimensions are changed.

The function also uses `\l_@@_suffix_tl` (-medium or -large).

```

5026 \cs_new_protected:Npn \@@_create_nodes:
5027 {
5028     \int_step_variable:nnNn \l_@@_first_row_int \g_@@_row_total_int \@@_i:
5029         {
5030             \int_step_variable:nnNn \l_@@_first_col_int \g_@@_col_total_int \@@_j:
5031                 {

```

We draw the rectangular node for the cell $(\text{\@@}_i - \text{\@@}_j)$.

```

5032     \@@_pgf_rect_node:nnnn
5033         { \@@_env: - \@@_i: - \@@_j: \l_@@_suffix_tl }
5034         { \dim_use:c { l_@@_column_ \@@_j: _min_dim } }
5035         { \dim_use:c { l_@@_row_ \@@_i: _min_dim } }
5036         { \dim_use:c { l_@@_column_ \@@_j: _max_dim } }
5037         { \dim_use:c { l_@@_row_ \@@_i: _max_dim } }
5038     \str_if_empty:NF \l_@@_name_str
5039         {
5040             \pgfnodealias
5041                 { \l_@@_name_str - \@@_i: - \@@_j: \l_@@_suffix_tl }
5042                 { \@@_env: - \@@_i: - \@@_j: \l_@@_suffix_tl }
5043         }
5044     }
5045 }

```

Now, we create the nodes for the cells of the `\multicolumn`. We recall that we have stored in `\g_@@_multicolumn_cells_seq` the list of the cells where a `\multicolumn{n}{...}{...}` with $n > 1$ was issued and in `\g_@@_multicolumn_sizes_seq` the correspondant values of n .

```

5046 \seq_mapthread_function:NNN
5047     \g_@@_multicolumn_cells_seq
5048     \g_@@_multicolumn_sizes_seq
5049     \@@_node_for_multicolumn:nn
5050 }

5051 \cs_new_protected:Npn \@@_extract_coords_values: #1 - #2 \q_stop
5052 {
5053     \cs_set_nopar:Npn \@@_i: { #1 }
5054     \cs_set_nopar:Npn \@@_j: { #2 }
5055 }

```

The command `\@@_node_for_multicolumn:nn` takes two arguments. The first is the position of the cell where the command `\multicolumn{n}{...}{...}` was issued in the format $i-j$ and the second is the value of n (the length of the “multi-cell”).

```

5056 \cs_new_protected:Npn \@@_node_for_multicolumn:nn #1 #2
5057 {
5058     \@@_extract_coords_values: #1 \q_stop
5059     \@@_pgf_rect_node:nnnn
5060     { \@@_env: - \@@_i: - \@@_j: \l_@@_suffix_tl }
5061     { \dim_use:c { l_@@_column _ \@@_j: _ min _ dim } }
5062     { \dim_use:c { l_@@_row _ \@@_i: _ min _ dim } }
5063     { \dim_use:c { l_@@_column _ \int_eval:n { \@@_j: +#2-1 } _ max _ dim } }
5064     { \dim_use:c { l_@@_row _ \@@_i: _ max _ dim } }
5065     \str_if_empty:NF \l_@@_name_str
5066     {
5067         \pgfnodealias
5068         { \l_@@_name_str - \@@_i: - \@@_j: \l_@@_suffix_tl }
5069         { \int_use:N \g_@@_env_int - \@@_i: - \@@_j: \l_@@_suffix_tl}
5070     }
5071 }
```

The blocks

The code deals with the command `\Block`. This command has no direct link with the environment `{NiceMatrixBlock}`.

The options of the command `\Block` will be analyzed first in the cell of the array (and once again when the block will be put in the array). Here is the set of keys for the first pass.

```

5072 \keys_define:nn { NiceMatrix / Block / FirstPass }
5073 {
5074     l .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl l ,
5075     l .value_forbidden:n = true ,
5076     r .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl r ,
5077     r .value_forbidden:n = true ,
5078     c .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl c ,
5079     c .value_forbidden:n = true ,
5080     L .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl l ,
5081     L .value_forbidden:n = true ,
5082     R .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl r ,
5083     R .value_forbidden:n = true ,
5084     C .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl c ,
5085     C .value_forbidden:n = true ,
5086     t .code:n = \tl_set:Nn \l_@@_vpos_of_block_tl t ,
5087     t .value_forbidden:n = true ,
5088     b .code:n = \tl_set:Nn \l_@@_vpos_of_block_tl b ,
5089     b .value_forbidden:n = true ,
5090     color .tl_set:N = \l_@@_color_tl ,
5091     color .value_required:n = true ,
5092 }
```

The following command `\@@_Block:` will be linked to `\Block` in the environments of `nicematrix`. We define it with `\NewExpandableDocumentCommand` because it has an optional argument between `<` and `>` (for TeX instructions put before the math mode of the label and before the beginning of the small array of the block). It’s mandatory to use an expandable command.

```

5093 \NewExpandableDocumentCommand \@@_Block: { O { } m D < > { } m }
5094 {
```

If the first mandatory argument of the command (which is the size of the block with the syntax $i-j$) has not be provided by the user, you use `1-1` (that is to say a block of only one cell).

```

5095 \peek_remove_spaces:n
5096 {
```

```

5097     \tl_if_blank:nTF { #2 }
5098     { \@@_Block_i 1-1 \q_stop }
5099     { \@@_Block_i #2 \q_stop }
5100     { #1 } { #3 } { #4 }
5101   }
5102 }
```

With the following construction, we extract the values of i and j in the first mandatory argument of the command.

```
5103 \cs_new:Npn \@@_Block_i #1-#2 \q_stop { \@@_Block_ii:nnnn { #1 } { #2 } }
```

Now, the arguments have been extracted: #1 is i (the number of rows of the block), #2 is j (the number of columns of the block), #3 is the list of key-values, #4 are the tokens to put before the math mode and the beginning of the small array of the block and #5 is the label of the block.

```

5104 \cs_new_protected:Npn \@@_Block_ii:nnnn { #1 } { #2 } { #3 } { #4 } { #5 }
5105 {
```

We recall that #1 and #2 have been extracted from the first mandatory argument of \Block (which is of the syntax $i-j$). However, the user is allowed to omit i or j (or both). We detect that situation by replacing a missing value by 100 (it's a convention: when the block will actually be drawn these values will be detected and interpreted as *maximal possible value* according to the actual size of the array).

```

5106 \bool_lazy_or:nnTF
5107 { \tl_if_blank_p:n { #1 } }
5108 { \str_if_eq_p:nn { #1 } { * } }
5109 { \int_set:Nn \l_tmpa_int { 100 } }
5110 { \int_set:Nn \l_tmpa_int { #1 } }
5111 \bool_lazy_or:nnTF
5112 { \tl_if_blank_p:n { #2 } }
5113 { \str_if_eq_p:nn { #2 } { * } }
5114 { \int_set:Nn \l_tmpb_int { 100 } }
5115 { \int_set:Nn \l_tmpb_int { #2 } }
```

If the block is mono-column.

```

5116 \int_compare:nNnTF \l_tmpb_int = 1
5117 {
5118   \tl_if_empty:NTF \l_@@_cell_type_tl
5119   { \tl_set:Nn \l_@@_hpos_of_block_tl c }
5120   { \tl_set_eq:NN \l_@@_hpos_of_block_tl \l_@@_cell_type_tl }
5121 }
5122 { \tl_set:Nn \l_@@_hpos_of_block_tl c }
```

The value of \l_@@_hpos_of_block_tl may be modified by the keys of the command \Block that we will analyze now.

```

5123 \keys_set_known:nn { NiceMatrix / Block / FirstPass } { #3 }
5124 \tl_set:Nx \l_tmpa_tl
5125 {
5126   { \int_use:N \c@iRow }
5127   { \int_use:N \c@jCol }
5128   { \int_eval:n { \c@iRow + \l_tmpa_int - 1 } }
5129   { \int_eval:n { \c@jCol + \l_tmpb_int - 1 } }
5130 }
```

Now, \l_tmpa_tl contains an “object” corresponding to the position of the block with four components, each of them surrounded by curly brackets:

{imin}{jmin}{imax}{jmax}.

If the block is mono-column or mono-row, we have a special treatment. That's why we have two macros: \@@_Block_iv:nnnn and \@@_Block_v:nnnn (the five arguments of those macros are provided by curryfication).

```

5131 \bool_lazy_or:nnTF
5132 { \int_compare_p:nNn { \l_tmpa_int } = 1 }
```

```

5133 { \int_compare_p:nNn { \l_tmpb_int } = 1 }
5134 { \exp_args:Nxx \@@_Block_iv:nnnn }
5135 { \exp_args:Nxx \@@_Block_v:nnnn }
5136 { \l_tmpa_int } { \l_tmpb_int } { #3 } { #4 } { #5 }
5137 }

```

The following macro is for the case of a `\Block` which is mono-row or mono-column (or both). In that case, the content of the block is composed right now in a box (because we have to take into account the dimensions of that box for the width of the current column or the height and the depth of the current row). However, that box will be put in the array *after the construction of the array* (by using PGF).

```

5138 \cs_new_protected:Npn \@@_Block_iv:nnnn #1 #2 #3 #4 #5
5139 {
5140     \int_gincr:N \g_@@_block_box_int
5141     \cs_set_protected_nopar:Npn \diagbox ##1 ##2
5142     {
5143         \tl_gput_right:Nx \g_@@_internal_code_after_tl
5144         {
5145             \@@_actually_diagbox:nnnnn
5146             { \int_use:N \c@iRow }
5147             { \int_use:N \c@jCol }
5148             { \int_eval:n { \c@iRow + #1 - 1 } }
5149             { \int_eval:n { \c@jCol + #2 - 1 } }
5150             { \exp_not:n { ##1 } } { \exp_not:n { ##2 } }
5151         }
5152     }
5153     \box_gclear_new:c
5154     { g_@@_block _ box _ \int_use:N \g_@@_block_box_int _ box }
5155     \hbox_gset:cn
5156     { g_@@_block _ box _ \int_use:N \g_@@_block_box_int _ box }
5157     {

```

For a mono-column block, if the user has specified a color for the column in the preamble of the array, we want to fix that color in the box we construct. We do that with `\set@color` and not `\color_ensure_current`: because that command seems to be bugged: it doesn't work in XeLaTeX when `fontspec` is loaded.

```

5158     \tl_if_empty:NTF \l_@@_color_tl
5159     { \int_compare:nNnT { #2 } = 1 \set@color }
5160     { \color { \l_@@_color_tl } }
5161     \group_begin:
5162     \cs_set:Npn \arraystretch { 1 }
5163     \dim_set_eq:NN \extrarowheight \c_zero_dim
5164     #4

```

If the box is rotated (the key `\rotate` may be in the previous `#4`), the tabular used for the content of the cell will be constructed with a format `c`. In the other cases, the tabular will be constructed with a format equal to the key of position of the box. In other words: the alignment internal to the tabular is the same as the external alignment of the tabular (that is to say the position of the block in its zone of merged cells).

```

5165     \bool_if:NT \g_@@_rotate_bool { \tl_set:Nn \l_@@_hpos_of_block_tl c }
5166     \bool_if:NTF \l_@@_NiceTabular_bool
5167     {
5168         \use:x
5169         {
5170             \exp_not:N \begin { tabular } [ \l_@@_vpos_of_block_tl ]
5171             { @ { } \l_@@_hpos_of_block_tl @ { } }
5172         }
5173         #5
5174         \end { tabular }
5175     }
5176     {
5177         \c_math_toggle_token
5178         \use:x

```

```

5179      {
5180          \exp_not:N \begin { array } [ \l_@@_vpos_of_block_tl ]
5181          { @ { } \l_@@_hpos_of_block_tl @ { } }
5182      }
5183      #5
5184      \end { array }
5185      \c_math_toggle_token
5186  }
5187  \group_end:
5188 }
5189 \bool_if:NT \g_@@_rotate_bool
5190 {
5191     \box_grotrate:cn
5192     { g_@@_block _ box _ \int_use:N \g_@@_block_box_int _ box }
5193     { 90 }
5194     \bool_gset_false:N \g_@@_rotate_bool
5195 }

```

If we are in a mono-column block, we take into account the width of that block for the width of the column.

```

5196 \int_compare:nNnT { #2 } = 1
5197 {
5198     \dim_gset:Nn \g_@@_blocks_wd_dim
5199     {
5200         \dim_max:nn
5201         \g_@@_blocks_wd_dim
5202         {
5203             \box_wd:c
5204             { g_@@_block _ box _ \int_use:N \g_@@_block_box_int _ box }
5205         }
5206     }
5207 }

```

If we are in a mono-row block, we take into account the height and the depth of that block for the height and the depth of the row.

```

5208 \int_compare:nNnT { #1 } = 1
5209 {
5210     \dim_gset:Nn \g_@@_blocks_ht_dim
5211     {
5212         \dim_max:nn
5213         \g_@@_blocks_ht_dim
5214         {
5215             \box_ht:c
5216             { g_@@_block _ box _ \int_use:N \g_@@_block_box_int _ box }
5217         }
5218     }
5219     \dim_gset:Nn \g_@@_blocks_dp_dim
5220     {
5221         \dim_max:nn
5222         \g_@@_blocks_dp_dim
5223         {
5224             \box_dp:c
5225             { g_@@_block _ box _ \int_use:N \g_@@_block_box_int _ box }
5226         }
5227     }
5228 }
5229 \seq_gput_right:Nx \g_@@_blocks_seq
5230 {
5231     \l_tmpa_tl

```

In the list of options #3, maybe there is a key for the horizontal alignment (`l`, `r` or `c`). In that case, that key has been read and stored in `\l_@@_hpos_of_block_tl`. However, maybe there were no key of the horizontal alignment and that's why we put a key corresponding to the value of `\l_@@_hpos_of_block_tl`, which is fixed by the type of current column.

```

5232 { \exp_not:n { #3 } , \l_@@_hpos_of_block_tl }
5233 {
5234     \box_use_drop:c
5235     { g_@@_block _ box _ \int_use:N \g_@@_block_box_int _ box }
5236 }
5237 }
5238 }
```

The following macro is for the standard case, where the block is not mono-row and not mono-column. In that case, the content of the block is *not* composed right now in a box. The composition in a box will be done further, just after the construction of the array.

```

5239 \cs_new_protected:Npn \@@_Block_v:nnnnn #1 #2 #3 #4 #5
5240 {
5241     \seq_gput_right:Nx \g_@@_blocks_seq
5242     {
5243         \l_tmpa_tl
5244         { \exp_not:n { #3 } }
5245         \exp_not:n
5246         {
5247             {
5248                 \bool_if:NTF \l_@@_NiceTabular_bool
5249                 {
5250                     \group_begin:
5251                     \cs_set:Npn \arraystretch { 1 }
5252                     \dim_set_eq:NN \extrarowheight \c_zero_dim
5253                     #4
5254     }
```

If the box is rotated (the key `\rotate` may be in the previous #4), the tabular used for the content of the cell will be constructed with a format *c*. In the other cases, the tabular will be constructed with a format equal to the key of position of the box. In other words: the alignment internal to the tabular is the same as the external alignment of the tabular (that is to say the position of the block in its zone of merged cells).

```

5254 \bool_if:NT \g_@@_rotate_bool
5255     { \tl_set:Nn \l_@@_hpos_of_block_tl c }
5256 \use:x
5257     {
5258         \exp_not:N \begin { tabular } [ \l_@@_vpos_of_block_tl ]
5259         { @ { } \l_@@_hpos_of_block_tl @ { } }
5260     }
5261     #5
5262     \end { tabular }
5263     \group_end:
5264 }
5265 {
5266     \group_begin:
5267     \cs_set:Npn \arraystretch { 1 }
5268     \dim_set_eq:NN \extrarowheight \c_zero_dim
5269     #4
5270     \bool_if:NT \g_@@_rotate_bool
5271     { \tl_set:Nn \l_@@_hpos_of_block_tl c }
5272     \c_math_toggle_token
5273     \use:x
5274     {
5275         \exp_not:N \begin { array } [ \l_@@_vpos_of_block_tl ]
5276         { @ { } \l_@@_hpos_of_block_tl @ { } }
5277     }
5278     #5
5279     \end { array }
5280     \c_math_toggle_token
5281     \group_end:
5282 }
5283 }
```

```

5285     }
5286 }

We recall that the options of the command \Block are analyzed twice: first in the cell of the array
and once again when the block will be put in the array after the construction of the array (by using
PGF).

5287 \keys_define:nn { NiceMatrix / Block / SecondPass }
5288 {
5289   fill .tl_set:N = \l_@@_fill_tl ,
5290   fill .value_required:n = true ,
5291   draw .tl_set:N = \l_@@_draw_tl ,
5292   draw .default:n = default ,
5293   rounded-corners .dim_set:N = \l_@@_rounded_corners_dim ,
5294   rounded-corners .default:n = 4 pt ,
5295   color .code:n = \color { #1 } \tl_set:Nn \l_@@_draw_tl { #1 } ,
5296   color .value_required:n = true ,
5297   borders .clist_set:N = \l_@@_borders_clist ,
5298   borders .value_required:n = true ,
5299   hlines .bool_set:N = \l_@@_hlines_block_bool ,
5300   hlines .default:n = true ,
5301   line-width .dim_set:N = \l_@@_line_width_dim ,
5302   line-width .value_required:n = true ,
5303   l .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl l ,
5304   l .value_forbidden:n = true ,
5305   r .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl r ,
5306   r .value_forbidden:n = true ,
5307   c .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl c ,
5308   c .value_forbidden:n = true ,
5309   L .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl l
5310           \bool_set_true:N \l_@@_hpos_of_block_cap_bool ,
5311   L .value_forbidden:n = true ,
5312   R .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl r
5313           \bool_set_true:N \l_@@_hpos_of_block_cap_bool ,
5314   R .value_forbidden:n = true ,
5315   C .code:n = \tl_set:Nn \l_@@_hpos_of_block_tl c
5316           \bool_set_true:N \l_@@_hpos_of_block_cap_bool ,
5317   C .value_forbidden:n = true ,
5318   t .code:n = \tl_set:Nn \l_@@_vpos_of_block_tl t ,
5319   t .value_forbidden:n = true ,
5320   b .code:n = \tl_set:Nn \l_@@_vpos_of_block_tl b ,
5321   b .value_forbidden:n = true ,
5322   unknown .code:n = \@@_error:n { Unknown~key~for~Block }
5323 }

```

The command \@@_draw_blocks: will draw all the blocks. This command is used after the construction of the array. We have to revert to a clean version of \ialign because there may be tabulars in the \Block instructions that will be composed now.

```

5324 \cs_new_protected:Npn \@@_draw_blocks:
5325 {
5326   \cs_set_eq:NN \ialign \@@_old_ialign:
5327   \seq_map_inline:Nn \g_@@_blocks_seq { \@@_Block_iv:nnnnnn ##1 }
5328 }

5329 \cs_new_protected:Npn \@@_Block_iv:nnnnnn #1 #2 #3 #4 #5 #6
5330 {

```

The integer \l_@@_last_row_int will be the last row of the block and \l_@@_last_col_int its last column.

```

5331   \int_zero_new:N \l_@@_last_row_int
5332   \int_zero_new:N \l_@@_last_col_int

```

We remind that the first mandatory argument of the command `\Block` is the size of the block with the special format $i-j$. However, the user is allowed to omit i or j (or both). This will be interpreted as: the last row (resp. column) of the block will be the last row (resp. column) of the block (without the potential exterior row—resp. column—of the array). By convention, this is stored in `\g_@@_blocks_seq` as a number of rows (resp. columns) for the block equal to 100. That's what we detect now.

```

5333 \int_compare:nNnTF { #3 } > { 99 }
5334   { \int_set_eq:NN \l_@@_last_row_int \c@iRow }
5335   { \int_set:Nn \l_@@_last_row_int { #3 } }
5336 \int_compare:nNnTF { #4 } > { 99 }
5337   { \int_set_eq:NN \l_@@_last_col_int \c@jCol }
5338   { \int_set:Nn \l_@@_last_col_int { #4 } }
5339 \int_compare:nNnTF \l_@@_last_col_int > \g_@@_col_total_int
5340   {
5341     \int_compare:nTF
5342       { \l_@@_last_col_int <= \g_@@_static_num_of_col_int }
5343       {
5344         \msg_error:nnnn { nicematrix } { Block-too-large~2 } { #1 } { #2 }
5345         \@@_msg_redirect_name:nn { Block-too-large~2 } { none }
5346         \group_begin:
5347         \globaldefs = 1
5348         \@@_msg_redirect_name:nn { columns-not-used } { none }
5349         \group_end:
5350       }
5351       { \msg_error:nnnn { nicematrix } { Block-too-large~1 } { #1 } { #2 } }
5352     }
5353   {
5354     \int_compare:nNnTF \l_@@_last_row_int > \g_@@_row_total_int
5355       { \msg_error:nnnn { nicematrix } { Block-too-large~1 } { #1 } { #2 } }
5356       { \@@_Block_v:nnnnnn { #1 } { #2 } { #3 } { #4 } { #5 } { #6 } }
5357   }
5358 }
5359 \cs_new_protected:Npn \@@_Block_v:nnnnnn #1 #2 #3 #4 #5 #6
5360 {

```

The sequence of the positions of the blocks will be used when drawing the rules (in fact, there is also the `\multicolumn` and the `\diagbox` in that sequence).

```
5361 \seq_gput_left:Nn \g_@@_pos_of_blocks_seq { { #1 } { #2 } { #3 } { #4 } }
```

The group is for the keys.

```

5362 \group_begin:
5363 \keys_set:nn { NiceMatrix / Block / SecondPass } { #5 }
5364 \tl_if_empty:NF \l_@@_draw_tl
5365   {
5366     \tl_gput_right:Nx \g_nicematrix_code_after_tl
5367     {
5368       \@@_stroke_block:nnn
5369         { \exp_not:n { #5 } }
5370         { #1 - #2 }
5371         { \int_use:N \l_@@_last_row_int - \int_use:N \l_@@_last_col_int }
5372     }
5373     \seq_gput_right:Nn \g_@@_pos_of_stroken_blocks_seq
5374       { { #1 } { #2 } { #3 } { #4 } }
5375   }
5376 \bool_if:NT \l_@@_hvlines_block_bool
5377   {
5378     \tl_gput_right:Nx \g_nicematrix_code_after_tl
5379     {
5380       \@@_hvlines_block:nnn
5381         { \exp_not:n { #5 } }
5382         { #1 - #2 }
5383         { \int_use:N \l_@@_last_row_int - \int_use:N \l_@@_last_col_int }

```

```

5384         }
5385     }
5386     \clist_if_empty:NF \l_@@_borders_clist
5387     {
5388         \tl_gput_right:Nx \g_nicematrix_code_after_tl
5389         {
5390             \@@_stroke_borders_block:nnn
5391             { \exp_not:n { #5 } }
5392             { #1 - #2 }
5393             { \int_use:N \l_@@_last_row_int - \int_use:N \l_@@_last_col_int }
5394         }
5395     }
5396     \tl_if_empty:NF \l_@@_fill_tl
5397     {

```

The command `\@@_extract_brackets` will extract the potential specification of color space at the beginning of `\l_@@_fill_tl` and store it in `\l_tmpa_tl` and store the color itself in `\l_tmpb_tl`.

```

5398     \exp_last_unbraced:NV \@@_extract_brackets \l_@@_fill_tl \q_stop
5399     \tl_gput_right:Nx \g_nicematrix_code_before_tl
5400     {
5401         \exp_not:N \roundedrectanglecolor
5402         [ \l_tmpa_tl ]
5403         { \exp_not:V \l_tmpb_tl }
5404         { #1 - #2 }
5405         { \int_use:N \l_@@_last_row_int - \int_use:N \l_@@_last_col_int }
5406         { \dim_use:N \l_@@_rounded_corners_dim }
5407     }
5408 }

5409 \cs_set_protected_nopar:Npn \diagbox ##1 ##2
5410 {
5411     \tl_gput_right:Nx \g_@@_internal_code_after_tl
5412     {
5413         \@@_actually_diagbox:nnnnn
5414         { #1 }
5415         { #2 }
5416         { \int_use:N \l_@@_last_row_int }
5417         { \int_use:N \l_@@_last_col_int }
5418         { \exp_not:n { ##1 } } { \exp_not:n { ##2 } }
5419     }
5420 }

5421 \hbox_set:Nn \l_@@_cell_box { \set@color #6 }
5422 \bool_if:NT \g_@@_rotate_bool \@@_rotate_cell_box:
```

Let's consider the following `\begin{NiceTabular}`. Because of the instruction `!{\hspace{1cm}}` in the preamble which increases the space between the columns (by adding, in fact, that space to the previous column, that is to say the second column of the tabular), we will create *two* nodes relative to the block: the node `1-1-block` and the node `1-1-block-short`.

```

\begin{NiceTabular}{cc!{\hspace{1cm}}c}
\Block{2-2}{our block} & one & \\
& two & \\
three & four & five \\
six & seven & eight \\
\end{NiceTabular}
```

We highlight the node `1-1-block`

our block	one
	two
three	four
six	seven

We highlight the node `1-1-block-short`

our block	one
	two
three	four
six	seven

The construction of the node corresponding to the merged cells.

```

5423 \pgfpicture
5424   \pgfrememberpicturepositiononpagetrue
5425   \pgf@relevantforpicturesizefalse
5426   \@@_qpoint:n { row - #1 }
5427   \dim_set_eq:NN \l_tmpa_dim \pgf@y
5428   \@@_qpoint:n { col - #2 }
5429   \dim_set_eq:NN \l_tmpb_dim \pgf@x
5430   \@@_qpoint:n { row - \@@_succ:n { \l_@@_last_row_int } }
5431   \dim_set_eq:NN \l_tmpc_dim \pgf@y
5432   \@@_qpoint:n { col - \@@_succ:n { \l_@@_last_col_int } }
5433   \dim_set_eq:NN \l_tmpd_dim \pgf@x

```

We construct the node for the block with the name (#1-#2-block).

The function `\@@_pgf_rect_node:nnnn` takes in as arguments the name of the node and the four coordinates of two opposite corner points of the rectangle.

```

5434 \begin{ { pgfscope }
5435   \@@_pgf_rect_node:nnnn
5436   { \@@_env: - #1 - #2 - block }
5437   \l_tmpb_dim \l_tmpa_dim \l_tmpd_dim \l_tmpc_dim
5438 \end { pgfscope }

```

Now, we create the “short node” which, in general, will be used to put the label (that is to say the content of the node). However, if one the keys L, C or R is used (that information is provided by the boolean `\l_@@_hpos_of_block_cap_bool`), we don’t need to create that node since the normal node is used to put the label.

```

5439 \bool_if:NF \l_@@_hpos_of_block_cap_bool
5440 {
5441   \dim_set_eq:NN \l_tmpb_dim \c_max_dim

```

The short node is constructed by taking into account the *contents* of the columns involved in at least one cell of the block. That’s why we have to do a loop over the rows of the array.

```

5442 \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
5443 {

```

We recall that, when a cell is empty, no (normal) node is created in that cell. That’s why we test the existence of the node before using it.

```

5444 \cs_if_exist:cT
5445   { \pgf @ sh @ ns @ \@@_env: - ##1 - #2 }
5446   {
5447     \seq_if_in:NnF \g_@@_multicolumn_cells_seq { ##1 - #2 }
5448     {
5449       \pgfpointanchor { \@@_env: - ##1 - #2 } { west }
5450       \dim_set:Nn \l_tmpb_dim { \dim_min:nn \l_tmpb_dim \pgf@x }
5451     }
5452   }
5453 }

```

If all the cells of the column were empty, `\l_tmpb_dim` has still the same value `\c_max_dim`. In that case, you use for `\l_tmpb_dim` the value of the position of the vertical rule.

```

5454 \dim_compare:nNnT \l_tmpb_dim = \c_max_dim
5455 {
5456   \@@_qpoint:n { col - #2 }
5457   \dim_set_eq:NN \l_tmpb_dim \pgf@x
5458 }
5459 \dim_set:Nn \l_tmpd_dim { - \c_max_dim }
5460 \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
5461 {
5462   \cs_if_exist:cT
5463   { \pgf @ sh @ ns @ \@@_env: - ##1 - \int_use:N \l_@@_last_col_int }
5464   {
5465     \seq_if_in:NnF \g_@@_multicolumn_cells_seq { ##1 - #2 }
5466     {
5467       \pgfpointanchor

```

```

5468          { \@@_env: - ##1 - \int_use:N \l_@@_last_col_int }
5469          { east }
5470          \dim_set:Nn \l_tmpd_dim { \dim_max:nn \l_tmpd_dim \pgf@x }
5471      }
5472  }
5473 }
5474 \dim_compare:nNnT \l_tmpd_dim = { - \c_max_dim }
5475 {
5476     \@@_qpoint:n { col - \@@_succ:n { \l_@@_last_col_int } }
5477     \dim_set_eq:NN \l_tmpd_dim \pgf@x
5478 }
5479 \@@_pgf_rect_node:nnnn
5480     { \@@_env: - #1 - #2 - block - short }
5481     \l_tmpb_dim \l_tmpa_dim \l_tmpd_dim \l_tmpc_dim
5482 }

```

If the creation of the “medium nodes” is required, we create a “medium node” for the block. The function `\@@_pgf_rect_node:nnn` takes in as arguments the name of the node and two PGF points.

```

5483 \bool_if:NT \l_@@_medium_nodes_bool
5484 {
5485     \@@_pgf_rect_node:nnn
5486     { \@@_env: - #1 - #2 - block - medium }
5487     { \pgfpointanchor { \@@_env: - #1 - #2 - medium } { north-west } }
5488 {
5489     \pgfpointanchor
5490     { \@@_env:
5491         - \int_use:N \l_@@_last_row_int
5492         - \int_use:N \l_@@_last_col_int - medium
5493     }
5494     { south-east }
5495 }
5496 }

```

Now, we will put the label of the block beginning with the case of a `\Block` of one row.

```

5497 \int_compare:nNnTF { #1 } = { #3 }
5498 {

```

We take into account the case of a block of one row in the “first row” or the “last row”.

```

5499 \int_compare:nNnTF { #1 } = 0
5500     { \l_@@_code_for_first_row_tl }
5501 {
5502     \int_compare:nNnT { #1 } = \l_@@_last_row_int
5503         \l_@@_code_for_last_row_tl
5504 }

```

If the block has only one row, we want the label of the block perfectly aligned on the baseline of the row. That’s why we have constructed a `\pgfcoordinate` on the baseline of the row, in the first column of the array. Now, we retrieve the y -value of that node and we store it in `\l_tmpa_dim`.

```

5505 \pgfextracty \l_tmpa_dim { \@@_qpoint:n { row - #1 - base } }

```

We retrieve (in `\pgf@x`) the x -value of the center of the block.

```

5506 \pgfpointanchor
5507 {
5508     \@@_env: - #1 - #2 - block
5509     \bool_if:NF \l_@@_hpos_of_block_cap_bool { - short }
5510 }
5511 {
5512     \str_case:Vn \l_@@_hpos_of_block_tl
5513     {
5514         c { center }
5515         l { west }
5516         r { east }
5517     }
5518 }

```

We put the label of the block which has been composed in `\l_@@_cell_box`.

```

5519 \pgftransformshift { \pgfpoint \pgf@x \l_tmpa_dim }
5520 \pgfset { inner-sep = \c_zero_dim }
5521 \pgfnode
5522   { rectangle }
5523 {
5524   \str_case:Vn \l_@@_hpos_of_block_tl
5525   {
5526     c { base }
5527     l { base-west }
5528     r { base-east }
5529   }
5530 }
5531 { \box_use_drop:N \l_@@_cell_box } { } { }
5532 }
```

If the number of rows is different of 1, we will put the label of the block by using the short node (the label of the block has been composed in `\l_@@_cell_box`).

```
5533 {
```

If we are in the first column, we must put the block as if it was with the key `r`.

```

5534 \int_compare:nNnT { #2 } = 0
5535   { \tl_set:Nn \l_@@_hpos_of_block_tl r }
5536 \bool_if:nT \g_@@_last_col_found_bool
5537   {
5538     \int_compare:nNnT { #2 } = \g_@@_col_total_int
5539       { \tl_set:Nn \l_@@_hpos_of_block_tl l }
5540   }
5541 \pgftransformshift
5542   {
5543     \pgfpointanchor
5544     {
5545       \@@_env: - #1 - #2 - block
5546       \bool_if:NF \l_@@_hpos_of_block_cap_bool { - short }
5547     }
5548   {
5549     \str_case:Vn \l_@@_hpos_of_block_tl
5550     {
5551       c { center }
5552       l { west }
5553       r { east }
5554     }
5555   }
5556 \pgfset { inner-sep = \c_zero_dim }
5557 \pgfnode
5558   { rectangle }
5559 {
5560   \str_case:Vn \l_@@_hpos_of_block_tl
5561   {
5562     c { center }
5563     l { west }
5564     r { east }
5565   }
5566 }
5567 }
5568 { \box_use_drop:N \l_@@_cell_box } { } { }
5569 }
5570 \endpgfpicture
5571 \group_end:
5572 }
```



```

5573 \NewDocumentCommand \@@_extract_brackets { 0 { } }
5574 {
```

```

5575   \tl_set:Nn \l_tmpa_tl { #1 }
5576   \@@_store_in_tmpb_t1
5577 }
5578 \cs_new_protected:Npn \@@_store_in_tmpb_t1 #1 \q_stop
5579 { \tl_set:Nn \l_tmpb_t1 { #1 } }

```

The first argument of `\@@_stroke_block:nnn` is a list of options for the rectangle that you will stroke. The second argument is the upper-left cell of the block (with, as usual, the syntax $i-j$) and the third is the last cell of the block (with the same syntax).

```

5580 \cs_new_protected:Npn \@@_stroke_block:nnn #1 #2 #3
5581 {
5582   \group_begin:
5583   \tl_clear:N \l_@@_draw_t1
5584   \dim_set_eq:NN \l_@@_line_width_dim \arrayrulewidth
5585   \keys_set_known:nn { NiceMatrix / BlockStroke } { #1 }
5586   \pgfpicture
5587   \pgfrememberpicturepositiononpage true
5588   \pgf@relevantforpicturesize false
5589   \tl_if_empty:NF \l_@@_draw_t1
5590   {

```

If the user has used the key `color` of the command `\Block` without value, the color fixed by `\arrayrulecolor` is used.

```

5591     \str_if_eq:VnTF \l_@@_draw_t1 { default }
5592     { \CT@arc@ }
5593     { \exp_args:NV \pgfsetstrokecolor \l_@@_draw_t1 }
5594   }
5595   \pgfsetcornersarced
5596   {
5597     \pgfpoint
5598     { \dim_use:N \l_@@_rounded_corners_dim }
5599     { \dim_use:N \l_@@_rounded_corners_dim }
5600   }
5601   \@@_cut_on_hyphen:w #2 \q_stop
5602   \bool_lazy_and:nnT
5603   { \int_compare_p:n { \l_tmpa_t1 <= \c@iRow } }
5604   { \int_compare_p:n { \l_tmpb_t1 <= \c@jCol } }
5605   {
5606     \@@_qpoint:n { row - \l_tmpa_t1 }
5607     \dim_set:Nn \l_tmpb_dim { \pgf@y }
5608     \@@_qpoint:n { col - \l_tmpb_t1 }
5609     \dim_set:Nn \l_tmpc_dim { \pgf@x }
5610     \@@_cut_on_hyphen:w #3 \q_stop
5611     \int_compare:nNnT \l_tmpa_t1 > \c@iRow
5612     { \tl_set:Nx \l_tmpa_t1 { \int_use:N \c@iRow } }
5613     \int_compare:nNnT \l_tmpb_t1 > \c@jCol
5614     { \tl_set:Nx \l_tmpb_t1 { \int_use:N \c@jCol } }
5615     \@@_qpoint:n { row - \@@_succ:n \l_tmpa_t1 }
5616     \dim_set:Nn \l_tmpa_dim { \pgf@y }
5617     \@@_qpoint:n { col - \@@_succ:n \l_tmpb_t1 }
5618     \dim_set:Nn \l_tmpd_dim { \pgf@x }
5619     \pgfpathrectanglecorners
5620     { \pgfpoint \l_tmpc_dim \l_tmpb_dim }
5621     { \pgfpoint \l_tmpd_dim \l_tmpa_dim }
5622     \pgfsetlinewidth { 1.1 \l_@@_line_width_dim }

```

We can't use `\pgfusepathqstroke` because of the key `rounded-corners`.

```

5623   \pgfusepath { stroke }
5624 }
5625 \endpgfpicture
5626 \group_end:
5627 }

```

Here is the set of keys for the command `\@@_stroke_block:nnn`.

```

5628 \keys_define:nn { NiceMatrix / BlockStroke }
5629 {
5630   color .tl_set:N = \l_@@_draw_tl ,
5631   draw .tl_set:N = \l_@@_draw_tl ,
5632   draw .default:n = default ,
5633   line-width .dim_set:N = \l_@@_line_width_dim ,
5634   rounded-corners .dim_set:N = \l_@@_rounded_corners_dim ,
5635   rounded-corners .default:n = 4 pt
5636 }
```

The first argument of `\@@_hvlines_block:nnn` is a list of options for the rules that we will draw. The second argument is the upper-left cell of the block (with, as usual, the syntax $i-j$) and the third is the last cell of the block (with the same syntax).

```

5637 \cs_new_protected:Npn \@@_hvlines_block:nnn #1 #2 #3
5638 {
5639   \dim_set_eq:NN \l_@@_line_width_dim \arrayrulewidth
5640   \keys_set_known:nn { NiceMatrix / BlockBorders } { #1 }
5641   \@@_cut_on_hyphen:w #2 \q_stop
5642   \tl_set_eq:NN \l_tmpc_tl \l_tmpa_tl
5643   \tl_set_eq:NN \l_tmpd_tl \l_tmpb_tl
5644   \@@_cut_on_hyphen:w #3 \q_stop
5645   \tl_set:Nx \l_tmpa_tl { \int_eval:n { \l_tmpa_tl + 1 } }
5646   \tl_set:Nx \l_tmpb_tl { \int_eval:n { \l_tmpb_tl + 1 } }
5647   \pgfpicture
5648   \pgfrememberpicturepositiononpagetrue
5649   \pgf@relevantforpicturesizefalse
5650   \CT@arc@C
5651   \pgfsetlinewidth { 1.1 \l_@@_line_width_dim }
```

First, the vertical rules.

```

5652 \@@_qpoint:n { row - \l_tmpa_tl }
5653 \dim_set_eq:NN \l_tmpa_dim \pgf@y
5654 \@@_qpoint:n { row - \l_tmpc_tl }
5655 \dim_set_eq:NN \l_tmpb_dim \pgf@y
5656 \int_step_inline:nnn \l_tmpd_tl \l_tmpb_tl
5657 {
5658   \@@_qpoint:n { col - ##1 }
5659   \pgfpathmoveto { \pgfpoint \pgf@x \l_tmpa_dim }
5660   \pgfpathlineto { \pgfpoint \pgf@x \l_tmpb_dim }
5661   \pgfusepathqstroke
5662 }
```

Now, the horizontal rules.

```

5663 \@@_qpoint:n { col - \l_tmpb_tl }
5664 \dim_set:Nn \l_tmpa_dim { \pgf@x + 0.5 \arrayrulewidth }
5665 \@@_qpoint:n { col - \l_tmpd_tl }
5666 \dim_set:Nn \l_tmpb_dim { \pgf@x - 0.5 \arrayrulewidth }
5667 \int_step_inline:nnn \l_tmpc_tl \l_tmpa_tl
5668 {
5669   \@@_qpoint:n { row - ##1 }
5670   \pgfpathmoveto { \pgfpoint \l_tmpa_dim \pgf@y }
5671   \pgfpathlineto { \pgfpoint \l_tmpb_dim \pgf@y }
5672   \pgfusepathqstroke
5673 }
5674 \endpgfpicture
5675 }
```

The first argument of `\@@_stroke_borders_block:nnn` is a list of options for the borders that you will stroke. The second argument is the upper-left cell of the block (with, as usual, the syntax $i-j$) and the third is the last cell of the block (with the same syntax).

```
5676 \cs_new_protected:Npn \@@_stroke_borders_block:nnn #1 #2 #3
```

```

5677 {
5678   \dim_set_eq:NN \l_@@_line_width_dim \arrayrulewidth
5679   \keys_set_known:nn { NiceMatrix / BlockBorders } { #1 }
5680   \dim_compare:nNnTF \l_@@_rounded_corners_dim > \c_zero_dim
5681     { \@@_error:n { borders-forbidden } }
5682   {
5683     \clist_map_inline:Nn \l_@@_borders_clist
5684     {
5685       \clist_if_in:nnF { top , bottom , left , right } { ##1 }
5686         { \@@_error:nn { bad-border } { ##1 } }
5687     }
5688   \@@_cut_on_hyphen:w #2 \q_stop
5689   \tl_set_eq:NN \l_tmpc_tl \l_tmpa_tl
5690   \tl_set_eq:NN \l_tmpd_tl \l_tmpb_tl
5691   \@@_cut_on_hyphen:w #3 \q_stop
5692   \tl_set:Nx \l_tmpa_tl { \int_eval:n { \l_tmpa_tl + 1 } }
5693   \tl_set:Nx \l_tmpb_tl { \int_eval:n { \l_tmpb_tl + 1 } }
5694   \pgfpicture
5695   \pgfrememberpicturepositiononpagetrue
5696   \pgf@relevantforpicturesizefalse
5697   \CT@arc@
5698   \pgfsetlinewidth { 1.1 \l_@@_line_width_dim }
5699   \clist_if_in:NnT \l_@@_borders_clist { right }
5700     { \@@_stroke_vertical:n \l_tmpb_tl }
5701   \clist_if_in:NnT \l_@@_borders_clist { left }
5702     { \@@_stroke_vertical:n \l_tmpd_tl }
5703   \clist_if_in:NnT \l_@@_borders_clist { bottom }
5704     { \@@_stroke_horizontal:n \l_tmpa_tl }
5705   \clist_if_in:NnT \l_@@_borders_clist { top }
5706     { \@@_stroke_horizontal:n \l_tmpc_tl }
5707   \endpgfpicture
5708 }
5709 }

```

The following command is used to stroke the left border and the right border. The argument #1 is the number of column (in the sense of the `col` node).

```

5710 \cs_new_protected:Npn \@@_stroke_vertical:n #1
5711 {
5712   \@@_qpoint:n \l_tmpc_tl
5713   \dim_set:Nn \l_tmpb_dim { \pgf@y + 0.5 \l_@@_line_width_dim }
5714   \@@_qpoint:n \l_tmpa_tl
5715   \dim_set:Nn \l_tmpc_dim { \pgf@y + 0.5 \l_@@_line_width_dim }
5716   \@@_qpoint:n { #1 }
5717   \pgfpathmoveto { \pgfpoint \pgf@x \l_tmpb_dim }
5718   \pgfpathlineto { \pgfpoint \pgf@x \l_tmpc_dim }
5719   \pgfusepathqstroke
5720 }

```

The following command is used to stroke the top border and the bottom border. The argument #1 is the number of row (in the sense of the `row` node).

```

5721 \cs_new_protected:Npn \@@_stroke_horizontal:n #1
5722 {
5723   \@@_qpoint:n \l_tmpd_tl
5724   \clist_if_in:NnTF \l_@@_borders_clist { left }
5725     { \dim_set:Nn \l_tmpa_dim { \pgf@x - 0.5 \l_@@_line_width_dim } }
5726     { \dim_set:Nn \l_tmpa_dim { \pgf@x + 0.5 \l_@@_line_width_dim } }
5727   \@@_qpoint:n \l_tmpb_tl
5728   \dim_set:Nn \l_tmpb_dim { \pgf@x + 0.5 \l_@@_line_width_dim }
5729   \@@_qpoint:n { #1 }
5730   \pgfpathmoveto { \pgfpoint \l_tmpa_dim \pgf@y }
5731   \pgfpathlineto { \pgfpoint \l_tmpb_dim \pgf@y }
5732   \pgfusepathqstroke
5733 }

```

Here is the set of keys for the command `\@@_stroke_borders_block:nnn`.

```

5734 \keys_define:nn { NiceMatrix / BlockBorders }
5735 {
5736   borders .clist_set:N = \l_@@_borders_clist ,
5737   rounded-corners .dim_set:N = \l_@@_rounded_corners_dim ,
5738   rounded-corners .default:n = 4 pt ,
5739   line-width .dim_set:N = \l_@@_line_width_dim
5740 }
```

How to draw the dotted lines transparently

```

5741 \cs_set_protected:Npn \@@_renew_matrix:
5742 {
5743   \RenewDocumentEnvironment { pmatrix } { }
5744   { \pNiceMatrix }
5745   { \endpNiceMatrix }
5746   \RenewDocumentEnvironment { vmatrix } { }
5747   { \vNiceMatrix }
5748   { \endvNiceMatrix }
5749   \RenewDocumentEnvironment { Vmatrix } { }
5750   { \VNiceMatrix }
5751   { \endVNiceMatrix }
5752   \RenewDocumentEnvironment { bmatrix } { }
5753   { \bNiceMatrix }
5754   { \endbNiceMatrix }
5755   \RenewDocumentEnvironment { Bmatrix } { }
5756   { \BNiceMatrix }
5757   { \endBNiceMatrix }
5758 }
```

Automatic arrays

```

5759 \cs_new_protected:Npn \@@_set_size:n #1-#2 \q_stop
5760 {
5761   \int_set:Nn \l_@@_nb_rows_int { #1 }
5762   \int_set:Nn \l_@@_nb_cols_int { #2 }
5763 }
```

We will extract the potential keys `l`, `r` and `c` and pass the other keys to the environment `{NiceArrayWithDelims}`.

```

5764 \keys_define:nn { NiceMatrix / Auto }
5765 {
5766   l .code:n = \tl_set:Nn \l_@@_type_of_col_tl l ,
5767   r .code:n = \tl_set:Nn \l_@@_type_of_col_tl r ,
5768   c .code:n = \tl_set:Nn \l_@@_type_of_col_tl c
5769 }
5770 \NewDocumentCommand \AutoNiceMatrixWithDelims { m m 0 { } m 0 { } m ! 0 { } }
5771 {
5772   \int_zero_new:N \l_@@_nb_rows_int
5773   \int_zero_new:N \l_@@_nb_cols_int
5774   \@@_set_size:n #4 \q_stop
```

The group is for the protection of `\l_@@_type_of_col_tl`.

```

5775 \group_begin:
5776 \tl_set:Nn \l_@@_type_of_col_tl c
5777 \keys_set_known:nnN { NiceMatrix / Auto } { #3, #5, #7 } \l_tmpa_tl
5778 \use:x
5779 {
5780   \exp_not:N \begin { NiceArrayWithDelims } { #1 } { #2 }
5781   { * { \int_use:N \l_@@_nb_cols_int } { \l_@@_type_of_col_tl } }
5782   [ \l_tmpa_tl ]
5783 }
```

```

5784 \int_compare:nNnT \l_@@_first_row_int = 0
5785 {
5786     \int_compare:nNnT \l_@@_first_col_int = 0 { & }
5787     \prg_replicate:nn { \l_@@_nb_cols_int - 1 } { & }
5788     \int_compare:nNnT \l_@@_last_col_int > { -1 } { & } \\
5789 }
5790 \prg_replicate:nn \l_@@_nb_rows_int
5791 {
5792     \int_compare:nNnT \l_@@_first_col_int = 0 { & }
5793
5794     \prg_replicate:nn { \l_@@_nb_cols_int - 1 } { { } #6 & } #6
5795     \int_compare:nNnT \l_@@_last_col_int > { -1 } { & } \\
5796 }
5797 \int_compare:nNnT \l_@@_last_row_int > { -2 }
5798 {
5799     \int_compare:nNnT \l_@@_first_col_int = 0 { & }
5800     \prg_replicate:nn { \l_@@_nb_cols_int - 1 } { & }
5801     \int_compare:nNnT \l_@@_last_col_int > { -1 } { & } \\
5802 }
5803 \end { NiceArrayWithDelims }
5804 \group_end:
5805
5806 \cs_set_protected:Npn \@@_define_com:nnn #1 #2 #3
5807 {
5808     \cs_set_protected:cpx { #1 AutoNiceMatrix }
5809     {
5810         \str_gset:Nx \g_@@_name_env_str { #1 AutoNiceMatrix }
5811         \AutoNiceMatrixWithDelims { #2 } { #3 }
5812     }
5813 \@@_define_com:nnn p ( )
5814 \@@_define_com:nnn b [ ]
5815 \@@_define_com:nnn v | |
5816 \@@_define_com:nnn V \| \|
5817 \@@_define_com:nnn B \{ \}

```

We define also a command `\AutoNiceMatrix` similar to the environment `{NiceMatrix}`.

```

5818 \NewDocumentCommand \AutoNiceMatrix { O { } m O { } m ! O { } }
5819 {
5820     \group_begin:
5821     \bool_set_true:N \l_@@_NiceArray_bool
5822     \AutoNiceMatrixWithDelims . . { #2 } { #4 } [ #1 , #3 , #5 ]
5823     \group_end:
5824 }

```

The redefinition of the command `\dotfill`

```

5825 \cs_set_eq:NN \@@_old_dotfill \dotfill
5826 \cs_new_protected:Npn \@@_dotfill:
5827 {

```

First, we insert `\@@_dotfill` (which is the saved version of `\dotfill`) in case of use of `\dotfill` “internally” in the cell (e.g. `\hbox to 1cm {\dotfill}`).

```

5828     \@@_old_dotfill
5829     \bool_if:NT \l_@@_NiceTabular_bool
5830         { \group_insert_after:N \@@_dotfill_ii: }
5831         { \group_insert_after:N \@@_dotfill_i: }
5832     }
5833 \cs_new_protected:Npn \@@_dotfill_i: { \group_insert_after:N \@@_dotfill_ii: }
5834 \cs_new_protected:Npn \@@_dotfill_ii: { \group_insert_after:N \@@_dotfill_iii: }

```

Now, if the box if not empty (unfortunately, we can't actually test whether the box is empty and that's why we only consider it's width), we insert `\@@_dotfill` (which is the saved version of `\dotfill`) in the cell of the array, and it will extend, since it is no longer in `\l_@@_cell_box`.

```
5835 \cs_new_protected:Npn \@@_dotfill_iii:
5836   { \dim_compare:nNnT { \box_wd:N \l_@@_cell_box } = \c_zero_dim \@@_old_dotfill }
```

The command `\diagbox`

The command `\diagbox` will be linked to `\diagbox:nn` in the environments of `nicematrix`.

```
5837 \cs_new_protected:Npn \@@_diagbox:nn #1 #2
5838   {
5839     \tl_gput_right:Nx \g_@@_internal_code_after_tl
5840     {
5841       \@@_actually_diagbox:nnnnnn
5842         { \int_use:N \c@iRow }
5843         { \int_use:N \c@jCol }
5844         { \int_use:N \c@iRow }
5845         { \int_use:N \c@jCol }
5846         { \exp_not:n { #1 } }
5847         { \exp_not:n { #2 } }
5848     }
5849 }
```

We put the cell with `\diagbox` in the sequence `\g_@@_pos_of_blocks_seq` because a cell with `\diagbox` must be considered as non empty by the key `corners`.

```
5849 \seq_gput_right:Nx \g_@@_pos_of_blocks_seq
5850   {
5851     { \int_use:N \c@iRow }
5852     { \int_use:N \c@jCol }
5853     { \int_use:N \c@iRow }
5854     { \int_use:N \c@jCol }
5855   }
5856 }
```

The command `\diagbox` is also redefined locally when we draw a block.

The first four arguments of `\@@_actually_diagbox:nnnnnn` correspond to the rectangle (=block) to slash (we recall that it's possible to use `\diagbox` in a `\Block`). The two other are the elements to draw below and above the diagonal line.

```
5857 \cs_new_protected:Npn \@@_actually_diagbox:nnnnnn #1 #2 #3 #4 #5 #6
5858   {
5859     \pgfpicture
5860     \pgf@relevantforpicturesizefalse
5861     \pgfrememberpicturepositiononpagetrue
5862     \@@_qpoint:n { row - #1 }
5863     \dim_set_eq:NN \l_tmpa_dim \pgf@y
5864     \@@_qpoint:n { col - #2 }
5865     \dim_set_eq:NN \l_tmpb_dim \pgf@x
5866     \pgfpathmoveto { \pgfpoint \l_tmpb_dim \l_tmpa_dim }
5867     \@@_qpoint:n { row - \@@_succ:n { #3 } }
5868     \dim_set_eq:NN \l_tmpc_dim \pgf@y
5869     \@@_qpoint:n { col - \@@_succ:n { #4 } }
5870     \dim_set_eq:NN \l_tmpd_dim \pgf@x
5871     \pgfpathlineto { \pgfpoint \l_tmpd_dim \l_tmpc_dim }
5872   }
```

The command `\CT@arc@` is a command of `colortbl` which sets the color of the rules in the array. The package `nicematrix` uses it even if `colortbl` is not loaded.

```
5873 \CT@arc@
5874 \pgfsetroundcap
5875 \pgfusepathqstroke
5876 }
5877 \pgfset { inner~sep = 1 pt }
5878 \pgfscope
```

```

5879 \pgftransformshift { \pgfpoint \l_tmpb_dim \l_tmpc_dim }
5880 \pgfnode { rectangle } { south-west }
5881   { \@@_math_toggle_token: #5 \@@_math_toggle_token: } { } { }
5882 \endpgfscope
5883 \pgftransformshift { \pgfpoint \l_tmpd_dim \l_tmpa_dim }
5884 \pgfnode { rectangle } { north-east }
5885   { \@@_math_toggle_token: #6 \@@_math_toggle_token: } { } { }
5886 \endpgfpicture
5887 }

```

The keyword \CodeAfter

The `\CodeAfter` (inserted with the key `code-after` or after the keyword `\CodeAfter`) may always begin with a list of pairs *key-value* between square brackets. Here is the corresponding set of keys.

```

5888 \keys_define:nn { NiceMatrix }
5889 {
5890   CodeAfter / rules .inherit:n = NiceMatrix / rules ,
5891   CodeAfter / sub-matrix .inherit:n = NiceMatrix / sub-matrix
5892 }
5893 \keys_define:nn { NiceMatrix / CodeAfter }
5894 {
5895   sub-matrix .code:n = \keys_set:nn { NiceMatrix / sub-matrix } { #1 } ,
5896   sub-matrix .value_required:n = true ,
5897   delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
5898   delimiters / color .value_required:n = true ,
5899   rules .code:n = \keys_set:nn { NiceMatrix / rules } { #1 } ,
5900   rules .value_required:n = true ,
5901   unknown .code:n = \@@_error:n { Unknown-key-for-CodeAfter }
5902 }

```

In fact, in this subsection, we define the user command `\CodeAfter` for the case of the “normal syntax”. For the case of “light-syntax”, see the definition of the environment `{@@-light-syntax}` on p. 107.

In the environments of `nicematrix`, `\CodeAfter` will be linked to `\@@_CodeAfter:..`. That macro must *not* be protected since it begins with `\omit`.

```
5903 \cs_new:Npn \@@_CodeAfter: { \omit \@@_CodeAfter_i:n }
```

However, in each cell of the environment, the command `\CodeAfter` will be linked to the following command `\@@_CodeAfter_i:n` which do *not* begin with `\omit` (and thus, the user will be able to use `\CodeAfter` without error and without the need to prefix by `\omit`).

We have to catch everything until the end of the current environment (of `nicematrix`). First, we go until the next command `\end`.

```

5904 \cs_new_protected:Npn \@@_CodeAfter_i:n #1 \end
5905 {
5906   \tl_gput_right:Nn \g_nicematrix_code_after_tl { #1 }
5907   \@@_CodeAfter_ii:n
5908 }

```

We catch the argument of the command `\end` (in `#1`).

```

5909 \cs_new_protected:Npn \@@_CodeAfter_ii:n #1
5910 {

```

If this is really the end of the current environment (of `nicematrix`), we put back the command `\end` and its argument in the TeX flow.

```
5911 \str_if_eq:eeTF \currenvir { #1 } { \end { #1 } }
```

If this is not the `\end` we are looking for, we put those tokens in `\g_nicematrix_code_after_tl` and we go on searching for the next command `\end` with a recursive call to the command `\@@_CodeAfter:n`.

```
5912 {
```

```

5913     \tl_gput_right:Nn \g_nicematrix_code_after_tl { \end { #1 } }
5914     \@@_CodeAfter_i:n
5915   }
5916 }

```

The delimiters in the preamble

The command `\@@_delimiter:nnn` will be used to draw delimiters inside the matrix when delimiters are specified in the preamble of the array. It does *not* concern the exterior delimiters added by `{NiceArrayWithDelims}` (and `{pNiceArray}`, `{pNiceMatrix}`, etc.).

A delimiter in the preamble of the array will write an instruction `\@@_delimiter:nnn` in the `\g_@@_internal_code_after_tl` (and also potentially add instructions in the preamble provided to `\array` in order to add space between columns).

The first argument is the type of delimiter ((, [, \{,),] or \}). The second argument is the number of columnm. The third argument is a boolean equal to `\c_true_bool` (resp. `\c_false_true`) when the delimiter must be put on the left (resp. right) side.

```

5917 \cs_new_protected:Npn \@@_delimiter:nnn #1 #2 #3
5918 {
5919   \pgfpicture
5920   \pgfrememberpicturepositiononpagetrue
5921   \pgf@relevantforpicturesizefalse

```

`\l_@@_y_initial_dim` and `\l_@@_y_final_dim` will be the *y*-values of the extremities of the delimiter we will have to construct.

```

5922 \@@_qpoint:n { row - 1 }
5923 \dim_set_eq:NN \l_@@_y_initial_dim \pgf@y
5924 \@@_qpoint:n { row - \@@_succ:n \c@iRow }
5925 \dim_set_eq:NN \l_@@_y_final_dim \pgf@y

```

We will compute in `\l_tmpa_dim` the *x*-value where we will have to put our delimiter (on the left side or on the right side).

```

5926 \bool_if:nTF { #3 }
5927   { \dim_set_eq:NN \l_tmpa_dim \c_max_dim }
5928   { \dim_set:Nn \l_tmpa_dim { - \c_max_dim } }
5929 \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int
5930   {
5931     \cs_if_exist:cT
5932       { \pgf @ sh @ ns @ \@@_env: - ##1 - #2 }
5933       {
5934         \pgfpointanchor
5935           { \@@_env: - ##1 - #2 }
5936           { \bool_if:nTF { #3 } { west } { east } }
5937         \dim_set:Nn \l_tmpa_dim
5938           { \bool_if:nTF { #3 } \dim_min:nn \dim_max:nn \l_tmpa_dim \pgf@x }
5939       }
5940   }

```

Now we can put the delimiter with a node of PGF.

```

5941 \pgfset { inner_sep = \c_zero_dim }
5942 \dim_zero:N \nulldelimiterspace
5943 \pgftransformshift
5944   {
5945     \pgfpoint
5946       { \l_tmpa_dim }
5947       { ( \l_@@_y_initial_dim + \l_@@_y_final_dim + \arrayrulewidth ) / 2 }
5948   }
5949 \pgfnode
5950   { rectangle }
5951   { \bool_if:nTF { #3 } { east } { west } }
5952   {

```

Here is the content of the PGF node, that is to say the delimiter, constructed with its right size.

```

5953 \nullfont
5954 \c_math_toggle_token
5955 \tl_if_empty:NF \l_@@_delimiters_color_tl
5956   { \color { \l_@@_delimiters_color_tl } }
5957 \bool_if:nTF { #3 } { \left #1 } { \left . }
5958 \vcenter
5959   {
5960     \nullfont
5961     \hrule \c@height
5962       \dim_eval:n { \l_@@_y_initial_dim - \l_@@_y_final_dim }
5963       \c@depth \c_zero_dim
5964       \c@width \c_zero_dim
5965     }
5966   \bool_if:nTF { #3 } { \right . } { \right #1 }
5967   \c_math_toggle_token
5968 }
5969 {
5970 }
5971 \endpgfpicture
5972 }
```

The command `\SubMatrix`

```

5973 \keys_define:nn { NiceMatrix / sub-matrix }
5974 {
5975   extra-height .dim_set:N = \l_@@_submatrix_extra_height_dim ,
5976   extra-height .value_required:n = true ,
5977   left-xshift .dim_set:N = \l_@@_submatrix_left_xshift_dim ,
5978   left-xshift .value_required:n = true ,
5979   right-xshift .dim_set:N = \l_@@_submatrix_right_xshift_dim ,
5980   right-xshift .value_required:n = true ,
5981   xshift .meta:n = { left-xshift = #1, right-xshift = #1 } ,
5982   xshift .value_required:n = true ,
5983   delimiters / color .tl_set:N = \l_@@_delimiters_color_tl ,
5984   delimiters / color .value_required:n = true ,
5985   slim .bool_set:N = \l_@@_submatrix_slim_bool ,
5986   slim .default:n = true ,
5987   hlines .clist_set:N = \l_@@_submatrix_hlines_clist ,
5988   hlines .default:n = all ,
5989   vlines .clist_set:N = \l_@@_submatrix_vlines_clist ,
5990   vlines .default:n = all ,
5991   hvlines .meta:n = { hlines, vlines } ,
5992   hvlines .value_forbidden:n = true ,
5993 }
5994 \keys_define:nn { NiceMatrix }
5995 {
5996   SubMatrix .inherit:n = NiceMatrix / sub-matrix ,
5997   CodeAfter / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
5998   NiceMatrix / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
5999   NiceArray / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
6000   pNiceArray / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
6001   NiceMatrixOptions / sub-matrix .inherit:n = NiceMatrix / sub-matrix ,
6002 }
```

The following keys set is for the command `\SubMatrix` itself (not the tuning of `\SubMatrix` that can be done elsewhere).

```

6003 \keys_define:nn { NiceMatrix / SubMatrix }
6004 {
6005   hlines .clist_set:N = \l_@@_submatrix_hlines_clist ,
6006   hlines .default:n = all ,
6007   vlines .clist_set:N = \l_@@_submatrix_vlines_clist ,
```

```

6008 vlines .default:n = all ,
6009 hlines .meta:n = { hlines, vlines } ,
6010 hlines .value_forbidden:n = true ,
6011 name .code:n =
6012 \tl_if_empty:nTF { #1 }
6013 { \@@_error:n { Invalid-name-format } }
6014 {
6015 \regex_match:nnTF { \A[A-Za-z][A-Za-z0-9]*\Z } { #1 }
6016 {
6017 \seq_if_in:NnTF \g_@@_submatrix_names_seq { #1 }
6018 { \@@_error:nn { Duplicate-name-for-SubMatrix } { #1 } }
6019 {
6020 \str_set:Nn \l_@@_submatrix_name_str { #1 }
6021 \seq_gput_right:Nn \g_@@_submatrix_names_seq { #1 }
6022 }
6023 }
6024 { \@@_error:n { Invalid-name-format } }
6025 },
6026 rules .code:n = \keys_set:nn { NiceMatrix / rules } { #1 } ,
6027 rules .value_required:n = true ,
6028 code .tl_set:N = \l_@@_code_tl ,
6029 code .value_required:n = true ,
6030 name .value_required:n = true ,
6031 unknown .code:n = \@@_error:n { Unknown-key-for-SubMatrix }
6032 }

6033 \NewDocumentCommand \@@_SubMatrix_in_code_before { m m m m ! O { } }
6034 {
6035 \peek_remove_spaces:n
6036 {
6037 \@@_cut_on_hyphen:w #3 \q_stop
6038 \tl_clear_new:N \l_tmpc_tl
6039 \tl_clear_new:N \l_tmpd_tl
6040 \tl_set_eq:NN \l_tmpc_tl \l_tmpa_tl
6041 \tl_set_eq:NN \l_tmpd_tl \l_tmpb_tl
6042 \@@_cut_on_hyphen:w #2 \q_stop
6043 \seq_gput_right:Nx \g_@@_submatrix_seq
6044 { { \l_tmpa_tl } { \l_tmpb_tl } { \l_tmpc_tl } { \l_tmpd_tl } }
6045 \tl_gput_right:Nn \g_@@_internal_code_after_tl
6046 { \SubMatrix { #1 } { #2 } { #3 } { #4 } [ #5 ] }
6047 }
6048 }

```

In the internal `code-after` and in the `\CodeAfter` the following command `\@@_SubMatrix` will be linked to `\SubMatrix`.

- #1 is the left delimiter;
- #2 is the upper-left cell of the matrix with the format $i-j$;
- #3 is the lower-right cell of the matrix with the format $i-j$;
- #4 is the right delimiter;
- #5 is the list of options of the command.

```

6049 \NewDocumentCommand \@@_SubMatrix { m m m m O { } }
6050 {
6051 \peek_remove_spaces:n
6052 { \@@_sub_matrix:nnnn { #1 } { #2 } { #3 } { #4 } { #5 } }
6053 }
6054 \cs_new_protected:Npn \@@_sub_matrix:nnnnn #1 #2 #3 #4 #5
6055 {
6056 \group_begin:

```

The four following token lists correspond to the position of the \SubMatrix.

```

6057 \tl_clear_new:N \l_@@_first_i_tl
6058 \tl_clear_new:N \l_@@_first_j_tl
6059 \tl_clear_new:N \l_@@_last_i_tl
6060 \tl_clear_new:N \l_@@_last_j_tl

```

The command \@@_cut_on_hyphen:w cuts on the hyphen an argument of the form $i-j$. The value of i is stored in \l_tmpa_tl and the value of j is stored in \l_tmpb_tl.

```

6061 \@@_cut_on_hyphen:w #2 \q_stop
6062 \tl_set_eq:NN \l_@@_first_i_tl \l_tmpa_tl
6063 \tl_set_eq:NN \l_@@_first_j_tl \l_tmpb_tl
6064 \@@_cut_on_hyphen:w #3 \q_stop
6065 \tl_set_eq:NN \l_@@_last_i_tl \l_tmpa_tl
6066 \tl_set_eq:NN \l_@@_last_j_tl \l_tmpb_tl
6067 \bool_lazy_or:nTF
  { \int_compare_p:nNn \l_@@_last_i_tl > \g_@@_row_total_int }
  { \int_compare_p:nNn \l_@@_last_j_tl > \g_@@_col_total_int }
  { \@@_error:n { SubMatrix-too-large } }
  {
    \str_clear_new:N \l_@@_submatrix_name_str
    \keys_set:nn { NiceMatrix / SubMatrix } { #5 }
    \pgfpicture
    \pgfrememberpicturepositiononpagetrue
    \pgf@relevantforpicturesizefalse
    \pgfset { inner-sep = \c_zero_dim }
    \dim_set_eq:NN \l_@@_x_initial_dim \c_max_dim
    \dim_set:Nn \l_@@_x_final_dim { - \c_max_dim }

```

The last value of \int_step_inline:nnn is provided by currification.

```

6080 \bool_if:NTF \l_@@_submatrix_slim_bool
  { \int_step_inline:nnn \l_@@_first_i_tl \l_@@_last_i_tl }
  { \int_step_inline:nnn \l_@@_first_row_int \g_@@_row_total_int }
  {
    \cs_if_exist:cT
      { \pgf @ sh @ ns @ \@@_env: - ##1 - \l_@@_first_j_tl }
      {
        \pgfpointanchor { \@@_env: - ##1 - \l_@@_first_j_tl } { west }
        \dim_set:Nn \l_@@_x_initial_dim
          { \dim_min:nn \l_@@_x_initial_dim \pgf@x }
      }
    \cs_if_exist:cT
      { \pgf @ sh @ ns @ \@@_env: - ##1 - \l_@@_last_j_tl }
      {
        \pgfpointanchor { \@@_env: - ##1 - \l_@@_last_j_tl } { east }
        \dim_set:Nn \l_@@_x_final_dim
          { \dim_max:nn \l_@@_x_final_dim \pgf@x }
      }
    }
  \dim_compare:nNnTF \l_@@_x_initial_dim = \c_max_dim
    { \@@_error:nn { impossible-delimiter } { left } }
    {
      \dim_compare:nNnTF \l_@@_x_final_dim = { - \c_max_dim }
        { \@@_error:nn { impossible-delimiter } { right } }
        { \@@_sub_matrix_i:nn { #1 } { #4 } }
    }
  \endpgfpicture
}
\group_end:
}

```

#1 is the left delimiter dans #2 is the right one.

```

6110 \cs_new_protected:Npn \@@_sub_matrix_i:nn #1 #2
6111   {

```

```

6112 \@@_qpoint:n { row - \l_@@_first_i_tl - base }
6113 \dim_set:Nn \l_@@_y_initial_dim
6114   { \pgf@y + ( \box_ht:N \strutbox + \extrarowheight ) * \arraystretch }
6115 \@@_qpoint:n { row - \l_@@_last_i_tl - base }
6116 \dim_set:Nn \l_@@_y_final_dim
6117   { \pgf@y - ( \box_dp:N \strutbox ) * \arraystretch }
6118 \int_step_inline:nnn \l_@@_first_col_int \g_@@_col_total_int
6119   {
6120     \cs_if_exist:cT
6121       { \pgf @ sh @ ns @ \@@_env: - \l_@@_first_i_tl - ##1 }
6122       {
6123         \pgfpointanchor { \@@_env: - \l_@@_first_i_tl - ##1 } { north }
6124         \dim_set:Nn \l_@@_y_initial_dim
6125           { \dim_max:nn \l_@@_y_initial_dim \pgf@y }
6126       }
6127     \cs_if_exist:cT
6128       { \pgf @ sh @ ns @ \@@_env: - \l_@@_last_i_tl - ##1 }
6129       {
6130         \pgfpointanchor { \@@_env: - \l_@@_last_i_tl - ##1 } { south }
6131         \dim_set:Nn \l_@@_y_final_dim
6132           { \dim_min:nn \l_@@_y_final_dim \pgf@y }
6133       }
6134   }
6135 \dim_set:Nn \l_tmpa_dim
6136   {
6137     \l_@@_y_initial_dim - \l_@@_y_final_dim +
6138     \l_@@_submatrix_extra_height_dim - \arrayrulewidth
6139   }
6140 \dim_set_eq:NN \nulldelimerspace \c_zero_dim

```

We will draw the rules in the `\SubMatrix`.

```

6141 \group_begin:
6142 \pgfsetlinewidth { 1.1 \arrayrulewidth }
6143 \tl_if_empty:NF \l_@@_rules_color_tl
6144   { \exp_after:wN \@@_set_C T@arc@: \l_@@_rules_color_tl \q_stop }
6145 \CT@arc@

```

Now, we draw the potential vertical rules specified in the preamble of the environments with the letter fixed with the key `vlines-in-sub-matrix`. The list of the columns where there is such rule to draw is in `\g_@@_cols_vlism_seq`.

```

6146 \seq_map_inline:Nn \g_@@_cols_vlism_seq
6147   {
6148     \int_compare:nNnT \l_@@_first_j_tl < { ##1 }
6149     {
6150       \int_compare:nNnT
6151         { ##1 } < { \int_eval:n { \l_@@_last_j_tl + 1 } }
6152     }

```

First, we extract the value of the abscissa of the rule we have to draw.

```

6153   \@@_qpoint:n { col - ##1 }
6154   \pgfpathmoveto { \pgfpoint \pgf@x \l_@@_y_initial_dim }
6155   \pgfpathlineto { \pgfpoint \pgf@x \l_@@_y_final_dim }
6156   \pgfusepathqstroke
6157   }
6158 }
6159 }

```

Now, we draw the vertical rules specified in the key `vlines` of `\SubMatrix`. The last argument of `\int_step_inline:nn` or `\clist_map_inline:Nn` is given by currying.

```

6160 \tl_if_eq:NnTF \l_@@_submatrix_vlines_clist { all }
6161   { \int_step_inline:nn { \l_@@_last_j_tl - \l_@@_first_j_tl } }
6162   { \clist_map_inline:Nn \l_@@_submatrix_vlines_clist }
6163   {

```

```

6164     \bool_lazy_and:nnTF
6165     { \int_compare_p:nNn { ##1 } > 0 }
6166     {
6167         \int_compare_p:nNn
6168         { ##1 } < { \l_@@_last_j_tl - \l_@@_first_j_tl + 1 }
6169     {
6170         \qpoint:n { col - \int_eval:n { ##1 + \l_@@_first_j_tl } }
6171         \pgfpathmoveto { \pgfpoint \pgf@x \l_@@_y_initial_dim }
6172         \pgfpathlineto { \pgfpoint \pgf@x \l_@@_y_final_dim }
6173         \pgfusepathqstroke
6174     }
6175     { \error:n { Wrong-line-in-SubMatrix } { vertical } { ##1 } }
6176 }

```

Now, we draw the horizontal rules specified in the key `hlines` of `\SubMatrix`. The last argument of `\int_step_inline:nn` or `\clist_map_inline:Nn` is given by curryification.

```

6177 \tl_if_eq:NnTF \l_@@_submatrix_hlines_clist { all }
6178 { \int_step_inline:nn { \l_@@_last_i_tl - \l_@@_first_i_tl } }
6179 { \clist_map_inline:Nn \l_@@_submatrix_hlines_clist }
6180 {
6181     \bool_lazy_and:nnTF
6182     { \int_compare_p:nNn { ##1 } > 0 }
6183     {
6184         \int_compare_p:nNn
6185         { ##1 } < { \l_@@_last_i_tl - \l_@@_first_i_tl + 1 }
6186     {
6187         \qpoint:n { row - \int_eval:n { ##1 + \l_@@_first_i_tl } }

```

We use a group to protect `\l_tmpa_dim` and `\l_tmpb_dim`.

```
6188 \group_begin:
```

We compute in `\l_tmpa_dim` the *x*-value of the left end of the rule.

```

6189 \dim_set:Nn \l_tmpa_dim
6190 { \l_@@_x_initial_dim - \l_@@_submatrix_left_xshift_dim }
6191 \str_case:nn { #1 }
6192 {
6193     ( { \dim_sub:Nn \l_tmpa_dim { 0.9 mm } }
6194     [ { \dim_sub:Nn \l_tmpa_dim { 0.2 mm } }
6195     \{ { \dim_sub:Nn \l_tmpa_dim { 0.9 mm } }
6196 }
6197 \pgfpathmoveto { \pgfpoint \l_tmpa_dim \pgf@y }

```

We compute in `\l_tmpb_dim` the *x*-value of the right end of the rule.

```

6198 \dim_set:Nn \l_tmpb_dim
6199 { \l_@@_x_final_dim + \l_@@_submatrix_right_xshift_dim }
6200 \str_case:nn { #2 }
6201 {
6202     ) { \dim_add:Nn \l_tmpb_dim { 0.9 mm } }
6203     ] { \dim_add:Nn \l_tmpb_dim { 0.2 mm } }
6204     \} { \dim_add:Nn \l_tmpb_dim { 0.9 mm } }
6205 }
6206 \pgfpathlineto { \pgfpoint \l_tmpb_dim \pgf@y }
6207 \pgfusepathqstroke
6208 \group_end:
6209 }
6210 { \error:n { Wrong-line-in-SubMatrix } { horizontal } { ##1 } }
6211 }

```

If the key `name` has been used for the command `\SubMatrix`, we create a PGF node with that name for the submatrix (this node does not encompass the delimiters that we will put after).

```

6212 \str_if_empty:NF \l_@@_submatrix_name_str
6213 {
6214     \q_rect_node:nnnn \l_@@_submatrix_name_str
6215     \l_@@_x_initial_dim \l_@@_y_initial_dim

```

```

6216      \l_@@_x_final_dim \l_@@_y_final_dim
6217  }
6218 \group_end:
```

The group was for `\CT@arc@` (the color of the rules).

Now, we deal with the left delimiter. Of course, the environment `{pgfscope}` is for the `\pgftransformshift`.

```

6219 \begin{ { pgfscope }
6220 \pgftransformshift
6221 {
6222   \pgfpoint
6223     { \l_@@_x_initial_dim - \l_@@_submatrix_left_xshift_dim }
6224     { ( \l_@@_y_initial_dim + \l_@@_y_final_dim ) / 2 }
6225   }
6226 \str_if_empty:NTF \l_@@_submatrix_name_str
6227   { \@@_node_left:nn #1 { } }
6228   { \@@_node_left:nn #1 { \@@_env: - \l_@@_submatrix_name_str - left } }
6229 \end { pgfscope }
```

Now, we deal with the right delimiter.

```

6230 \pgftransformshift
6231 {
6232   \pgfpoint
6233     { \l_@@_x_final_dim + \l_@@_submatrix_right_xshift_dim }
6234     { ( \l_@@_y_initial_dim + \l_@@_y_final_dim ) / 2 }
6235   }
6236 \str_if_empty:NTF \l_@@_submatrix_name_str
6237   { \@@_node_right:nn #2 { } }
6238   {
6239     \@@_node_right:nn #2 { \@@_env: - \l_@@_submatrix_name_str - right }
6240   }
6241 \cs_set_eq:NN \pgfpointanchor \@@_pgfpointanchor:n
6242 \flag_clear_new:n { nicematrix }
6243 \l_@@_code_tl
6244 }
```

In the key `code` of the command `\SubMatrix` there may be Tikz instructions. We want that, in these instructions, the i and j in specifications of nodes of the forms $i-j$, `row-i`, `col-j` and $i-|j$ refer to the number of row and column *relative* of the current `\SubMatrix`. That's why we will patch (locally in the `\SubMatrix`) the command `\pgfpointanchor`.

```
6245 \cs_set_eq:NN \@@_old_pgfpoinanchor \pgfpointanchor
```

The following command will be linked to `\pgfpointanchor` just before the execution of the option `code` of the command `\SubMatrix`. In this command, we catch the argument `#1` of `\pgfpointanchor` and we apply to it the command `\@@_pgfpointanchor_i:nn` before passing it to the original `\pgfpointanchor`. We have to act in an expandable way because the command `\pgfpointanchor` is used in names of Tikz nodes which are computed in an expandable way.

```

6246 \cs_new_protected:Npn \@@_pgfpointanchor:n #1
6247 {
6248   \use:e
6249   { \exp_not:N \@@_old_pgfpoinanchor { \@@_pgfpointanchor_i:nn #1 } }
6250 }
```

In fact, the argument of `\pgfpointanchor` is always of the form `\a_command { name_of_node }` where “`name_of_node`” is the name of the Tikz node without the potential prefix and suffix. That's why we catch two arguments and work only on the second by trying (first) to extract an hyphen `-`.

```

6251 \cs_new:Npn \@@_pgfpointanchor_i:nn #1 #2
6252   { #1 { \@@_pgfpointanchor_ii:w #2 - \q_stop } }
```

Since `\seq_if_in:NnTF` and `\clist_if_in:NnTF` are not expandable, we will use the following token list and `\str_case:nVTF` to test whether we have an integer or not.

```

6253 \tl_const:Nn \c_@@_integers alist tl
6254 {
6255   { 1 } { } { 2 } { } { 3 } { } { 4 } { } { 5 } { }
6256   { 6 } { } { 7 } { } { 8 } { } { 9 } { } { 10 } { }
6257   { 11 } { } { 12 } { } { 13 } { } { 14 } { } { 15 } { }
6258   { 16 } { } { 17 } { } { 18 } { } { 19 } { } { 20 } { }
6259 }
```



```

6260 \cs_new:Npn \@@_pgfpointanchor_i:w #1-#2\q_stop
6261 {
```

If there is no hyphen, that means that the node is of the form of a single number (ex.: 5 or 11). In that case, we are in an analysis which result from a specification of node of the form $i-j$. In that case, the i of the number of row arrives first (and alone) in a `\pgfpointanchor` and, the, the j arrives (alone) in the following `\pgfpointanchor`. In order to know whether we have a number of row of a number of column, we keep track of the number of such treatments by the expandable flag called `nicematrix`.

```

6262 \tl_if_empty:nTF { #2 }
6263 {
6264   \str_case:nVTF { #1 } \c_@@_integers alist tl
6265   {
6266     \flag_raise:n { nicematrix }
6267     \int_if_even:nTF { \flag_height:n { nicematrix } }
6268     { \int_eval:n { #1 + \l_@@_first_i_tl - 1 } }
6269     { \int_eval:n { #1 + \l_@@_first_j_tl - 1 } }
6270   }
6271   { #1 }
6272 }
```

If there is an hyphen, we have to see whether we have a node of the form $i-j$, `row-i` or `col-j`.

```

6273 { \@@_pgfpointanchor_iii:w { #1 } #2 }
6274 }
```

There was an hyphen in the name of the node and that's why we have to retrieve the extra hyphen we have put (cf. `\@@_pgfpointanchor_i:nn`).

```

6275 \cs_new:Npn \@@_pgfpointanchor_iii:w #1 #2 -
6276 {
6277   \str_case:nnF { #1 }
6278   {
6279     { row } { row - \int_eval:n { #2 + \l_@@_first_i_tl - 1 } }
6280     { col } { col - \int_eval:n { #2 + \l_@@_first_j_tl - 1 } }
6281   }
```

Now the case of a node of the form $i-j$.

```

6282 {
6283   \int_eval:n { #1 + \l_@@_first_i_tl - 1 }
6284   - \int_eval:n { #2 + \l_@@_first_j_tl - 1 }
6285 }
```

The command `\@@_node_left:nn` puts the left delimiter with the correct size. The argument `#1` is the delimiter to put. The argument `#2` is the name we will give to this PGF node (if the key `name` has been used in `\SubMatrix`).

```

6287 \cs_new_protected:Npn \@@_node_left:nn #1 #2
6288 {
6289   \pgfnode
6290   { rectangle }
6291   { east }
6292   {
6293     \nullfont
```

```

6294     \c_math_toggle_token
6295     \tl_if_empty:NF \l_@@_delimiters_color_tl
6296         { \color { \l_@@_delimiters_color_tl } }
6297     \left #1
6298     \vcenter
6299     {
6300         \nullfont
6301         \hrule \Oheight \l_tmpa_dim
6302             \Odepth \c_zero_dim
6303             \Owidth \c_zero_dim
6304     }
6305     \right .
6306     \c_math_toggle_token
6307 }
6308 { #2 }
6309 { }
6310 }

```

The command `\@@_node_right:nn` puts the right delimiter with the correct size. The argument `#1` is the delimiter to put. The argument `#2` is the name we will give to this PGF node (if the key `name` has been used in `\SubMatrix`).

```

6311 \cs_new_protected:Npn \@@_node_right:nn #1 #2
6312 {
6313     \pgfnode
6314         { rectangle }
6315         { west }
6316         {
6317             \nullfont
6318             \c_math_toggle_token
6319             \tl_if_empty:NF \l_@@_delimiters_color_tl
6320                 { \color { \l_@@_delimiters_color_tl } }
6321             \left .
6322             \vcenter
6323             {
6324                 \nullfont
6325                 \hrule \Oheight \l_tmpa_dim
6326                     \Odepth \c_zero_dim
6327                     \Owidth \c_zero_dim
6328             }
6329             \right #1
6330             \c_math_toggle_token
6331         }
6332 { #2 }
6333 { }
6334 }

```

We process the options at package loading

We process the options when the package is loaded (with `\usepackage`) but we recommend to use `\NiceMatrixOptions` instead.

We must process these options after the definition of the environment `{NiceMatrix}` because the option `renew-matrix` executes the code `\cs_set_eq:NN \env@matrix \NiceMatrix`.

Of course, the command `\NiceMatrix` must be defined before such an instruction is executed.

The boolean `\g_@@_footnotehyper_bool` will indicate if the option `footnotehyper` is used.

```
6335 \bool_new:N \c_@@_footnotehyper_bool
```

The boolean `\c_@@_footnote_bool` will indicate if the option `footnote` is used, but quickly, it will also be set to true if the option `footnotehyper` is used.

```
6336 \bool_new:N \c_@@_footnote_bool
```

```

6337 \@@_msg_new:nnn { Unknown-option-for-package }
6338 {
6339   The-key-'l_keys_key_str'~is~unknown. \\
6340   If~you~go~on,~it~will~be~ignored. \\
6341   For~a~list~of~the~available~keys,~type~H~<return>.
6342 }
6343 {
6344   The~available~keys~are~(in~alphabetic~order):~
6345   define-L-C-R,~
6346   footnote,~
6347   footnotehyper,~
6348   renew-dots,~and
6349   renew-matrix.
6350 }

```

Maybe we will completely delete the key 'transparent' in a future version.

```

6351 \@@_msg_new:nn { Key-transparent }
6352 {
6353   The-key-'transparent'~is~now~obsolete~(because~it's~name~
6354   is~not~clear).~You~should~use~the~conjunction~of~'renew-dots'~
6355   and~'renew-matrix'.~However,~you~can~go~on.
6356 }

6357 \@@_msg_new:nn { define-L-C-R }
6358 {
6359   You~have~used~the~key~'define-L-C-R'.~Please~note~that~this~key~
6360   will~probably~be~deleted~in~a~future~version~of~'nicematrix'.\\\
6361   However,~you~can~go~on.
6362 }

6363 \keys_define:nn { NiceMatrix / Package }
6364 {
6365   define-L-C-R .code:n =
6366     \@@_error:n { define-L-C-R }
6367     \bool_set_true:N \c_@@_define_L_C_R_bool ,
6368   renew-dots .bool_set:N = \l_@@_renew_dots_bool ,
6369   renew-dots .value_forbidden:n = true ,
6370   renew-matrix .code:n = \@@_renew_matrix: ,
6371   renew-matrix .value_forbidden:n = true ,
6372   transparent .code:n =
6373   {
6374     \@@_renew_matrix:
6375     \bool_set_true:N \l_@@_renew_dots_bool
6376     \@@_error:n { Key-transparent }
6377   },
6378   transparent .value_forbidden:n = true,
6379   footnote .bool_set:N = \c_@@_footnote_bool ,
6380   footnotehyper .bool_set:N = \c_@@_footnotehyper_bool ,
6381   unknown .code:n = \@@_error:n { Unknown-option-for-package }
6382 }
6383 \ProcessKeysOptions { NiceMatrix / Package }


```

```

6384 \@@_msg_new:nn { footnote-with-footnotehyper-package }
6385 {
6386   You~can't~use~the~option~'footnote'~because~the~package~
6387   footnotehyper~has~already~been~loaded.~
6388   If~you~want,~you~can~use~the~option~'footnotehyper'~and~the~footnotes~
6389   within~the~environments~of~nicematrix~will~be~extracted~with~the~tools~
6390   of~the~package~footnotehyper.\\
6391   If~you~go~on,~the~package~footnote~won't~be~loaded.
6392 }

6393 \@@_msg_new:nn { footnotehyper-with-footnote-package }
6394 {

```

```

6395 You~can't~use~the~option~'footnotehyper'~because~the~package~
6396 footnote~has~already~been~loaded.~
6397 If~you~want,~you~can~use~the~option~'footnote'~and~the~footnotes~
6398 within~the~environments~of~nicematrix~will~be~extracted~with~the~tools~
6399 of~the~package~footnote.\\
6400 If~you~go~on,~the~package~footnotehyper~won't~be~loaded.
6401 }

```

```

6402 \bool_if:NT \c_@@_footnote_bool
6403 {

```

The class beamer has its own system to extract footnotes and that's why we have nothing to do if beamer is used.

```

6404 \@ifclassloaded { beamer }
6405   { \bool_set_false:N \c_@@_footnote_bool }
6406   {
6407     \@ifpackageloaded { footnotehyper }
6408       { \@@_error:n { footnote-with-footnotehyper-package } }
6409       { \usepackage { footnote } }
6410   }
6411 }
6412 \bool_if:NT \c_@@_footnotehyper_bool
6413 {

```

The class beamer has its own system to extract footnotes and that's why we have nothing to do if beamer is used.

```

6414 \@ifclassloaded { beamer }
6415   { \bool_set_false:N \c_@@_footnote_bool }
6416   {
6417     \@ifpackageloaded { footnote }
6418       { \@@_error:n { footnotehyper-with-footnote-package } }
6419       { \usepackage { footnotehyper } }
6420   }
6421 \bool_set_true:N \c_@@_footnote_bool
6422 }

```

The flag `\c_@@_footnote_bool` is raised and so, we will only have to test `\c_@@_footnote_bool` in order to know if we have to insert an environment `{savenotes}`.

Error messages of the package

The following message will be deleted when we will delete the key `except-corners` for the command `\arraycolor`.

```

6423 \@@_msg_new:nn { key except-corners }
6424 {
6425   The~key~'except-corners'~has~been~deleted~for~the~command~\token_to_str:N
6426   \arraycolor\ in~the~\token_to_str:N \CodeBefore.~You~should~instead~use~
6427   the~key~'corners'~in~your~\@@_full_name_env:.\\
6428   If~you~go~on,~this~key~will~be~ignored.
6429 }

6430 \seq_new:N \c_@@_types_of_matrix_seq
6431 \seq_set_from_clist:Nn \c_@@_types_of_matrix_seq
6432 {
6433   NiceMatrix ,
6434   pNiceMatrix , bNiceMatrix , vNiceMatrix, BNiceMatrix, VNiceMatrix
6435 }
6436 \seq_set_map_x>NNn \c_@@_types_of_matrix_seq \c_@@_types_of_matrix_seq
6437   { \tl_to_str:n { #1 } }

```

If the user uses too much columns, the command `\@@_error_too_much_cols:` is executed. This command raises an error but try to give the best information to the user in the error message. The command `\seq_if_in:NVT` is not expandable and that's why we can't put it in the error message itself. We have to do the test before the `\@@_fatal:n`.

```

6438 \cs_new_protected:Npn \@@_error_too_much_cols:
6439 {
6440     \seq_if_in:NVT \c_@@_types_of_matrix_seq \g_@@_name_env_str
6441     {
6442         \int_compare:nNnTF \l_@@_last_col_int = { -2 }
6443         { \@@_fatal:n { too-much-cols-for-matrix } }
6444         {
6445             \bool_if:NF \l_@@_last_col_without_value_bool
6446             { \@@_fatal:n { too-much-cols-for-matrix-with-last-col } }
6447         }
6448     }
6449     { \@@_fatal:n { too-much-cols-for-array } }
6450 }
```

The following command must *not* be protected since it's used in an error message.

```

6451 \cs_new:Npn \@@_message_hdotsfor:
6452 {
6453     \tl_if_empty:VF \g_@@_Hdotsfor_lines_tl
6454     { ~Maybe~your~use~of~\token_to_str:N \Hdotsfor\ is~incorrect.}
6455 }

6456 \@@_msg_new:nn { too-much-cols-for-matrix-with-last-col }
6457 {
6458     You~try~to~use~more~columns~than~allowed~by~your~
6459     \@@_full_name_env:.\@@_message_hdotsfor:\ The~maximal~number~of~
6460     columns~is~\int_eval:n { \l_@@_last_col_int - 1 }~(plus~the~
6461     exterior~columns).~This~error~is~fatal.
6462 }

6463 \@@_msg_new:nn { too-much-cols-for-matrix }
6464 {
6465     You~try~to~use~more~columns~than~allowed~by~your~
6466     \@@_full_name_env:.\@@_message_hdotsfor:\ Recall~that~the~maximal~
6467     number~of~columns~for~a~matrix~is~fixed~by~the~LaTeX~counter~
6468     'MaxMatrixCols'.~Its~actual~value~is~\int_use:N \c@MaxMatrixCols.~
6469     This~error~is~fatal.
6470 }
```

For the following message, remind that the test is not done after the construction of the array but in each row. That's why we have to put `\c@jCol-1` and not `\c@jCol`.

```

6471 \@@_msg_new:nn { too-much-cols-for-array }
6472 {
6473     You~try~to~use~more~columns~than~allowed~by~your~
6474     \@@_full_name_env:.\@@_message_hdotsfor:\ The~maximal~number~of~columns~is~
6475     \int_use:N \g_@@_static_num_of_col_int\
6476     ~(plus~the~potential~exterior~ones).~
6477     This~error~is~fatal.
6478 }

6479 \@@_msg_new:nn { last-col-not-used }
6480 {
6481     The~key~'last-col'~is~in~force~but~you~have~not~used~that~last~column~
6482     in~your~\@@_full_name_env:~However,~you~can~go~on.
6483 }

6484 \@@_msg_new:nn { columns-not-used }
6485 {
6486     The~preamble~of~your~\@@_full_name_env:~announces~\int_use:N
6487     \g_@@_static_num_of_col_int\~columns~but~you~use~only~\int_use:N \c@jCol.\\
6488     You~can~go~on~but~the~columns~you~did~not~use~won't~be~created.
6489 }
```

```

6490 \@@_msg_new:nn { in-first-col }
6491 {
6492   You~can't~use~the~command~#1~in~the~first~column~(number~0)~of~the~array.\\
6493   If~you~go~on,~this~command~will~be~ignored.
6494 }

6495 \@@_msg_new:nn { in-last-col }
6496 {
6497   You~can't~use~the~command~#1~in~the~last~column~(exterior)~of~the~array.\\
6498   If~you~go~on,~this~command~will~be~ignored.
6499 }

6500 \@@_msg_new:nn { in-first-row }
6501 {
6502   You~can't~use~the~command~#1~in~the~first~row~(number~0)~of~the~array.\\
6503   If~you~go~on,~this~command~will~be~ignored.
6504 }

6505 \@@_msg_new:nn { in-last-row }
6506 {
6507   You~can't~use~the~command~#1~in~the~last~row~(exterior)~of~the~array.\\
6508   If~you~go~on,~this~command~will~be~ignored.
6509 }

6510 \@@_msg_new:nn { double-closing-delimiter }
6511 {
6512   You~can't~put~a~second~closing~delimiter~"#1"~just~after~a~first~closing~
6513   delimiter.~This~delimiter~will~be~ignored.
6514 }

6515 \@@_msg_new:nn { delimiter-after-opening }
6516 {
6517   You~can't~put~a~second~delimiter~"#1"~just~after~a~first~opening~
6518   delimiter.~This~delimiter~will~be~ignored.
6519 }

6520 \@@_msg_new:nn { bad-option-for-line-style }
6521 {
6522   Since~you~haven't~loaded~Tikz,~the~only~value~you~can~give~to~'line-style'~
6523   is~'standard'.~If~you~go~on,~this~key~will~be~ignored.
6524 }

6525 \@@_msg_new:nn { Unknown-key-for-xdots }
6526 {
6527   As~for~now,~there~is~only~three~key~available~here:~'color',~'line-style'~
6528   and~'shorten'~(and~you~try~to~use~'\l_keys_key_str').~If~you~go~on,~
6529   this~key~will~be~ignored.
6530 }

6531 \@@_msg_new:nn { Unknown-key-for-rowcolors }
6532 {
6533   As~for~now,~there~is~only~two~keys~available~here:~'cols'~and~'respect-blocks'~
6534   (and~you~try~to~use~'\l_keys_key_str').~If~you~go~on,~
6535   this~key~will~be~ignored.
6536 }

6537 \@@_msg_new:nn { ampersand-in-light-syntax }
6538 {
6539   You~can't~use~an~ampersand~(\token_to_str:N~&)~to~separate~columns~because~
6540   ~you~have~used~the~key~'light-syntax'.~This~error~is~fatal.
6541 }

6542 \@@_msg_new:nn { SubMatrix-too-large }
6543 {
6544   Your~command~\token_to_str:N~\SubMatrix~\\
6545   can't~be~drawn~because~your~matrix~is~too~small.\\
6546   If~you~go~on,~this~command~will~be~ignored.
6547 }

```

```

6548 \@@_msg_new:nn { double-backslash-in-light-syntax }
6549 {
6550     You~can't~use~\token_to_str:N \\~to~separate~rows~because~you~have~used~
6551     the~key~'light-syntax'.~You~must~use~the~character~'\l_@@_end_of_row_tl'~
6552     (set~by~the~key~'end-of-row').~This~error~is~fatal.
6553 }
6554 \@@_msg_new:nn { standard-cline-in-document }
6555 {
6556     The~key~'standard-cline'~is~available~only~in~the~preamble.\\
6557     If~you~go~on~this~command~will~be~ignored.
6558 }
6559 \@@_msg_new:nn { old-column-type }
6560 {
6561     The~column~type~'#1'~is~no~longer~defined~in~'nicematrix'.~
6562     Since~version~5.0,~you~have~to~use~'l',~'c'~and~'r'~instead~of~'L',~
6563     'C'~and~'R'.~You~can~also~use~the~key~'define-L-C-R'.\\
6564     This~error~is~fatal.
6565 }
6566 \@@_msg_new:nn { bad-value-for-baseline }
6567 {
6568     The~value~given~to~'baseline'~(\int_use:N \l_tmpa_int)~is~not~
6569     valid.~The~value~must~be~between~\int_use:N \l_@@_first_row_int~and~
6570     \int_use:N \g_@@_row_total_int~or~equal~to~'t',~'c'~or~'b'.\\
6571     If~you~go~on,~a~value~of~1~will~be~used.
6572 }
6573 \@@_msg_new:nn { Invalid-name-format }
6574 {
6575     You~can't~give~the~name~'\l_keys_value_tl'~to~a~\token_to_str:N
6576     \SubMatrix.\\
6577     A~name~must~be~accepted~by~the~regular~expression~[A-Za-z] [A-Za-z0-9]*.\\
6578     If~you~go~on,~this~key~will~be~ignored.
6579 }
6580 \@@_msg_new:nn { Wrong-line-in-SubMatrix }
6581 {
6582     You~try~to~draw~a~#1~line~of~number~'#2'~in~a~  

6583     \token_to_str:N \SubMatrix~of~your~\@@_full_name_env:\~but~that~
6584     number~is~not~valid.~If~you~go~on,~it~will~be~ignored.
6585 }
6586 \@@_msg_new:nn { impossible-delimiter }
6587 {
6588     It's~impossible~to~draw~the~#1~delimiter~of~your~  

6589     \token_to_str:N \SubMatrix~because~all~the~cells~are~empty~  

6590     in~that~column.
6591     \bool_if:NT \l_@@_submatrix_slim_bool
6592         { ~Maybe~you~should~try~without~the~key~'slim'. } \\
6593     If~you~go~on,~this~\token_to_str:N \SubMatrix~will~be~ignored.
6594 }
6595 \@@_msg_new:nn { empty-environment }
6596 {
6597     Your~\@@_full_name_env:\~is~empty.~This~error~is~fatal. }
6598 \@@_msg_new:nn { Delimiter-with-small }
6599 {
6600     You~can't~put~a~delimiter~in~the~preamble~of~your~\@@_full_name_env:\~  

6601     because~the~key~'small'~is~in~force.\\
6602     This~error~is~fatal.
6603 }
6604 \@@_msg_new:nn { unknown-cell-for-line-in-CodeAfter }
6605 {
6606     Your~command~\token_to_str:N\nline{\#1}\{\#2\}~in~the~'code-after'~
6607     can't~be~executed~because~a~cell~doesn't~exist.\\
6608     If~you~go~on~this~command~will~be~ignored.
6609 }

```

```

6609 \@@_msg_new:nnn { Duplicate~name~for~SubMatrix }
6610 {
6611   The~name~'#1'~is~already~used~for~a~\token_to_str:N \SubMatrix\
6612   in~this~\@@_full_name_env:.\\
6613   If~you~go~on,~this~key~will~be~ignored.\\
6614   For~a~list~of~the~names~already~used,~type~H~<return>.
6615 }
6616 {
6617   The~names~already~defined~in~this~\@@_full_name_env:~are:~
6618   \seq_use:Nnnn \g_@@_submatrix_names_seq { ~and~ } { ,~ } { ~and~ }.
6619 }

6620 \@@_msg_new:nn { r-or-l-with-preamble }
6621 {
6622   You~can't~use~the~key~'\l_keys_key_str'~in~your~\@@_full_name_env:~
6623   You~must~specify~the~alignment~of~your~columns~with~the~preamble~of~
6624   your~\@@_full_name_env:.\\
6625   If~you~go~on,~this~key~will~be~ignored.
6626 }

6627 \@@_msg_new:nn { Hdotsfor-in-col-0 }
6628 {
6629   You~can't~use~\token_to_str:N \Hdotsfor~in~an~exterior~column~of~
6630   the~array.~This~error~is~fatal.
6631 }

6632 \@@_msg_new:nn { bad-corner }
6633 {
6634   #1~is~an~incorrect~specification~for~a~corner~(in~the~keys~
6635   'corners'~and~'except-corners').~The~available~
6636   values~are:~NW,~SW,~NE~and~SE.\\
6637   If~you~go~on,~this~specification~of~corner~will~be~ignored.
6638 }

6639 \@@_msg_new:nn { bad-border }
6640 {
6641   #1~is~an~incorrect~specification~for~a~border~(in~the~key~
6642   'borders'~of~the~command~\token_to_str:N \Block).~The~available~
6643   values~are:~left,~right,~top~and~bottom.\\
6644   If~you~go~on,~this~specification~of~border~will~be~ignored.
6645 }

6646 \@@_msg_new:nn { last-col-non-empty-for-NiceArray }
6647 {
6648   In~the~\@@_full_name_env:,~you~must~use~the~key~
6649   'last-col'~without~value.\\
6650   However,~you~can~go~on~for~this~time~
6651   (the~value~'\l_keys_value_tl'~will~be~ignored).
6652 }

6653 \@@_msg_new:nn { last-col-non-empty-for-NiceMatrixOptions }
6654 {
6655   In~\NiceMatrixoptions,~you~must~use~the~key~
6656   'last-col'~without~value.\\
6657   However,~you~can~go~on~for~this~time~
6658   (the~value~'\l_keys_value_tl'~will~be~ignored).
6659 }

6660 \@@_msg_new:nn { Block-too-large-1 }
6661 {
6662   You~try~to~draw~a~block~in~the~cell~#1-#2~of~your~matrix~but~the~matrix~is~
6663   too~small~for~that~block.~\\
6664 }

6665 \@@_msg_new:nn { Block-too-large-2 }
6666 {
6667   The~preamble~of~your~\@@_full_name_env:~announces~\int_use:N~
6668   \g_@@_static_num_of_col_int\
```

```

6669 columns~but~you~use~only~\int_use:N \c@jCol\ and~that's~why~a~block~
6670 specified~in~the~cell~#1-#2~can't~be~drawn.~You~should~add~some~ampersands~
6671 (&)~at~the~end~of~the~first~row~of~your~
6672 \@@_full_name_env:\\
6673 If~you~go~on,~this~block~and~maybe~others~will~be~ignored.
6674 }

6675 \@@_msg_new:nn { unknown~column~type }
6676 {
6677   The~column~type~'#1'~in~your~\@@_full_name_env:\\
6678   is~unknown. \\
6679   This~error~is~fatal.
6680 }

6681 \@@_msg_new:nn { tabularnote~forbidden }
6682 {
6683   You~can't~use~the~command~\token_to_str:N\tabularnote\\
6684   ~in~a~\@@_full_name_env.:~This~command~is~available~only~in~
6685   \{NiceTabular\},~\{NiceArray\}~and~\{NiceMatrix\}. \\
6686   If~you~go~on,~this~command~will~be~ignored.
6687 }

6688 \@@_msg_new:nn { borders~forbidden }
6689 {
6690   You~can't~use~the~key~'borders'~of~the~command~\token_to_str:N \Block\\
6691   because~the~option~'rounded-corners'~
6692   is~in~force~with~a~non-zero~value.\\
6693   If~you~go~on,~this~key~will~be~ignored.
6694 }

6695 \@@_msg_new:nn { bottomrule~without~booktabs }
6696 {
6697   You~can't~use~the~key~'tabular/bottomrule'~because~you~haven't~
6698   loaded~'booktabs'.\\
6699   If~you~go~on,~this~key~will~be~ignored.
6700 }

6701 \@@_msg_new:nn { enumitem~not~loaded }
6702 {
6703   You~can't~use~the~command~\token_to_str:N\tabularnote\\
6704   ~because~you~haven't~loaded~'enumitem'.\\
6705   If~you~go~on,~this~command~will~be~ignored.
6706 }

6707 \@@_msg_new:nn { Wrong~last~row }
6708 {
6709   You~have~used~'last-row=\int_use:N \l_@@_last_row_int'~but~your~
6710   \@@_full_name_env:\\ seems~to~have~\int_use:N \c@iRow \\ rows.~
6711   If~you~go~on,~the~value~of~\int_use:N \c@iRow \\ will~be~used~for~
6712   last~row.~You~can~avoid~this~problem~by~using~'last-row'~
6713   without~value~(more~compilations~might~be~necessary).
6714 }

6715 \@@_msg_new:nn { Yet~in~env }
6716 {
6717   Environments~of~nicematrix~can't~be~nested.\\ This~error~is~fatal. }

6718 \@@_msg_new:nn { Outside~math~mode }
6719 {
6720   The~\@@_full_name_env:\\ can~be~used~only~in~math~mode~
6721   (and~not~in~\token_to_str:N \vcenter).\\
6722   This~error~is~fatal.
6723 }

6724 \@@_msg_new:nn { One~letter~allowed }
6725 {
6726   The~value~of~key~'\l_keys_key_str'~must~be~of~length~1.\\
6727   If~you~go~on,~it~will~be~ignored.
6728 }

```

```

6728 \@@_msg_new:nnn { Unknown-key-for-Block }
6729 {
6730   The-key-'l_keys_key_str'~is~unknown~for~the~command~\token_to_str:N
6731   \Block.\\ If~you~go~on,~it~will~be~ignored. \\
6732   For~a~list~of~the~available~keys,~type~H~<return>.
6733 }
6734 {
6735   The~available~keys~are~(in~alphabetic~order):~b,~borders,~c,~draw,~fill,~
6736   hvlines,~l,~line-width,~rounded-corners,~r~and~t.
6737 }
6738 \@@_msg_new:nnn { Unknown-key-for-CodeAfter }
6739 {
6740   The-key-'l_keys_key_str'~is~unknown.\\
6741   If~you~go~on,~it~will~be~ignored. \\
6742   For~a~list~of~the~available~keys~in~\token_to_str:N
6743   \CodeAfter,~type~H~<return>.
6744 }
6745 {
6746   The~available~keys~are~(in~alphabetic~order):~delimiters/color,~
6747   rules~(with~the~subkeys~'color'~and~'width'),~
6748   sub-matrix~(several~subkeys)~
6749   and~xdots~(several~subkeys).~
6750   The~latter~is~for~the~command~\token_to_str:N \line.
6751 }
6752
6753 \@@_msg_new:nnn { Unknown-key-for-SubMatrix }
6754 {
6755   The-key-'l_keys_key_str'~is~unknown.\\
6756   If~you~go~on,~this~key~will~be~ignored. \\
6757   For~a~list~of~the~available~keys~in~\token_to_str:N
6758   \SubMatrix,~type~H~<return>.
6759 }
6760 {
6761   The~available~keys~are~(in~alphabetic~order):~'delimiters/color',~
6762   'extra-height',~
6763   'hlines',~
6764   'hvlines',~
6765   'left-xshift',~
6766   'name',~
6767   'right-xshift',~
6768   'rules'~(with~the~subkeys~'color'~and~'width'),~
6769   'slim',~
6770   'vlines'-and~'xshift'~(which~sets~both~'left-xshift'~
6771   and~'right-xshift').\\
6772 }
6773
6774 \@@_msg_new:nnn { Unknown-key-for-notes }
6775 {
6776   The-key-'l_keys_key_str'~is~unknown.\\
6777   If~you~go~on,~it~will~be~ignored. \\
6778   For~a~list~of~the~available~keys~about~notes,~type~H~<return>.
6779 }
6780 {
6781   The~available~keys~are~(in~alphabetic~order):~bottomrule,~
6782   code-after,~
6783   code-before,~
6784   enumitem-keys,~
6785   enumitem-keys-para,~
6786   para,~
6787   label-in-list,~
6788   label-in-tabular~and~
6789   style.
6790 }
```

```

6791 }
6792 \@@_msg_new:nnn { Unknown-key-for-NiceMatrixOptions }
6793 {
6794   The~key~'\l_keys_key_str'~is~unknown~for~the~command~
6795   \token_to_str:N \NiceMatrixOptions. \\%
6796   If~you~go~on,~it~will~be~ignored. \\%
6797   For~a~list~of~the~*principal*~available~keys,~type~H~<return>.
6798 }
6799 {
6800   The~available~keys~are~(in~alphabetic~order):~
6801   allow-duplicate-names,~
6802   cell-space-bottom-limit,~
6803   cell-space-limits,~
6804   cell-space-top-limit,~
6805   code-for-first-col,~
6806   code-for-first-row,~
6807   code-for-last-col,~
6808   code-for-last-row,~
6809   corners,~
6810   create-extra-nodes,~
6811   create-medium-nodes,~
6812   create-large-nodes,~
6813   delimiters~(several~subkeys),~
6814   end-of-row,~
6815   first-col,~
6816   first-row,~
6817   hlines,~
6818   hvlines,~
6819   last-col,~
6820   last-row,~
6821   left-margin,~
6822   letter-for-dotted-lines,~
6823   light-syntax,~
6824   notes~(several~subkeys),~
6825   nullify-dots,~
6826   renew-dots,~
6827   renew-matrix,~
6828   right-margin,~
6829   rules~(with~the~subkeys~'color'~and~'width'),~
6830   small,~
6831   sub-matrix~(several~subkeys),
6832   vlines,~
6833   xdots~(several~subkeys).
6834 }

6835 \@@_msg_new:nnn { Unknown-option-for-NiceArray }
6836 {
6837   The~key~'\l_keys_key_str'~is~unknown~for~the~environment~\{NiceArray\}. \\
6838   If~you~go~on,~it~will~be~ignored. \\%
6839   For~a~list~of~the~*principal*~available~keys,~type~H~<return>.
6840 }
6841 {
6842   The~available~keys~are~(in~alphabetic~order):~
6843   b,~
6844   baseline,~
6845   c,~
6846   cell-space-bottom-limit,~
6847   cell-space-limits,~
6848   cell-space-top-limit,~
6849   code-after,~
6850   code-for-first-col,~
6851   code-for-first-row,~
6852   code-for-last-col,~
6853

```

```

6854 code-for-last-row,~
6855 colortbl-like,~
6856 columns-width,~
6857 corners,~
6858 create-extra-nodes,~
6859 create-medium-nodes,~
6860 create-large-nodes,~
6861 delimiters/color,~
6862 extra-left-margin,~
6863 extra-right-margin,~
6864 first-col,~
6865 first-row,~
6866 hlines,~
6867 hvlines,~
6868 last-col,~
6869 last-row,~
6870 left-margin,~
6871 light-syntax,~
6872 name,~
6873 notes/bottomrule,~
6874 notes/para,~
6875 nullify-dots,~
6876 renew-dots,~
6877 right-margin,~
6878 rules~(with~the~subkeys~'color'~and~'width'),~
6879 small,~
6880 t,~
6881 tabularnote,~
6882 vlines,~
6883 xdots/color,~
6884 xdots/shorten-and-
6885 xdots/line-style.
6886 }

```

This error message is used for the set of keys `NiceMatrix/NiceMatrix` and `NiceMatrix/pNiceArray` (but not by `NiceMatrix/NiceArray` because, for this set of keys, there is also the keys `t`, `c` and `b`).

```

6887 \@@_msg_new:nnn { Unknown-option-for-NiceMatrix }
6888 {
6889   The~key~'\l_keys_key_str'~is~unknown~for~the~
6890   \@@_full_name_env:.. \\
6891   If~you~go~on,~it~will~be~ignored. \\
6892   For~a~list~of~the~*principal*~available~keys,~type~H~<return>.
6893 }
6894 {
6895   The~available~keys~are~(in~alphabetic~order):~
6896   b,~
6897   baseline,~
6898   c,~
6899   cell-space-bottom-limit,~
6900   cell-space-limits,~
6901   cell-space-top-limit,~
6902   code-after,~
6903   code-for-first-col,~
6904   code-for-first-row,~
6905   code-for-last-col,~
6906   code-for-last-row,~
6907   colortbl-like,~
6908   columns-width,~
6909   corners,~
6910   create-extra-nodes,~
6911   create-medium-nodes,~
6912   create-large-nodes,~
6913   delimiters~(several~subkeys),~

```

```

6914 extra-left-margin,~
6915 extra-right-margin,~
6916 first-col,~
6917 first-row,~
6918 hlines,~
6919 hvlines,~
6920 l,~
6921 last-col,~
6922 last-row,~
6923 left-margin,~
6924 light-syntax,~
6925 name,~
6926 nullify-dots,~
6927 r,~
6928 renew-dots,~
6929 right-margin,~
6930 rules~(with~the~subkeys~'color'~and~'width'),~
6931 small,~
6932 t,~
6933 vlines,~
6934 xdots/color,~
6935 xdots/shorten~and~
6936 xdots/line-style.
6937 }

6938 \@@_msg_new:nnn { Unknown-option-for-NiceTabular }
6939 {
6940   The~key~'\l_keys_key_str'~is~unknown~for~the~environment~`{NiceTabular}`. \\
6941   If~you~go~on,~it~will~be~ignored. \\
6942   For~a~list~of~the~*principal*~available~keys,~type~H~<return>.
6943 }
6944 {
6945   The~available~keys~are~(in~alphabetic~order):~
6946   b,~
6947   baseline,~
6948   c,~
6949   cell-space-bottom-limit,~
6950   cell-space-limits,~
6951   cell-space-top-limit,~
6952   code-after,~
6953   code-for-first-col,~
6954   code-for-first-row,~
6955   code-for-last-col,~
6956   code-for-last-row,~
6957   colortbl-like,~
6958   columns-width,~
6959   corners,~
6960   create-extra-nodes,~
6961   create-medium-nodes,~
6962   create-large-nodes,~
6963   extra-left-margin,~
6964   extra-right-margin,~
6965   first-col,~
6966   first-row,~
6967   hlines,~
6968   hvlines,~
6969   last-col,~
6970   last-row,~
6971   left-margin,~
6972   light-syntax,~
6973   name,~
6974   notes/bottomrule,~
6975   notes/para,~
6976

```

```

6977   nullify-dots,~
6978   renew-dots,~
6979   right-margin,~
6980   rules~(with~the~subkeys~'color'~and~'width'),~
6981   t,~
6982   tabularnote,~
6983   vlines,~
6984   xdots/color,~
6985   xdots/shorten-and~
6986   xdots/line-style.
6987 }
6988 \@@_msg_new:nnn { Duplicate~name }
6989 {
6990   The~name~'\l_keys_value_tl'~is~already~used~and~you~shouldn't~use~
6991   the~same~environment~name~twice.~You~can~go~on,~but,~
6992   maybe,~you~will~have~incorrect~results~especially~
6993   if~you~use~'columns-width=auto'.~If~you~don't~want~to~see~this~
6994   message~again,~use~the~key~'allow-duplicate-names'~in~
6995   '\token_to_str:N \NiceMatrixOptions'\\.\\\
6996   For~a~list~of~the~names~already~used,~type~H~<return>. \\\
6997 }
6998 {
6999   The~names~already~defined~in~this~document~are:~
7000   \seq_use:Nnnn \g_@@_names_seq { ~and~ } { ,~ } { ~and~ }.
7001 }

7002 \@@_msg_new:nn { Option~auto~for~columns~width }
7003 {
7004   You~can't~give~the~value~'auto'~to~the~key~'columns-width'~here.~
7005   If~you~go~on,~the~key~will~be~ignored.
7006 }

```

18 History

The successive versions of the file `nicematrix.sty` provided by TeXLive are available on the SVN server of TeXLive:

<https://www.tug.org/svn/texlive/trunk/Master/texmf-dist/tex/latex/nicematrix/nicematrix.sty>

Changes between versions 1.0 and 1.1

The dotted lines are no longer drawn with Tikz nodes but with Tikz circles (for efficiency).
Modification of the code which is now twice faster.

Changes between versions 1.1 and 1.2

New environment `{NiceArray}` with column types L, C and R.

Changes between version 1.2 and 1.3

New environment `{pNiceArrayC}` and its variants.
Correction of a bug in the definition of `{BNiceMatrix}`, `{vNiceMatrix}` and `{VNiceMatrix}` (in fact, it was a typo).
Options are now available locally in `{pNiceMatrix}` and its variants.
The names of the options are changed. The old names were names in “camel style”.

Changes between version 1.3 and 1.4

The column types `w` and `W` can now be used in the environments `{NiceArray}`, `{pNiceArrayC}` and its variants with the same meaning as in the package `array`.

New option `columns-width` to fix the same width for all the columns of the array.

Changes between version 1.4 and 2.0

The versions 1.0 to 1.4 of `nicematrix` were focused on the continuous dotted lines whereas the version 2.0 of `nicematrix` provides different features to improve the typesetting of mathematical matrices.

Changes between version 2.0 and 2.1

New implementation of the environment `{pNiceArrayRC}`. With this new implementation, there is no restriction on the width of the columns.

The package `nicematrix` no longer loads `mathtools` but only `amsmath`.

Creation of “medium nodes” and “large nodes”.

Changes between version 2.1 and 2.1.1

Small corrections: for example, the option `code-for-first-row` is now available in the command `\NiceMatrixOptions`.

Following a discussion on TeX StackExchange⁶³, Tikz externalization is now deactivated in the environments of the package `nicematrix`.⁶⁴

Changes between version 2.1.2 and 2.1.3

When searching the end of a dotted line from a command like `\Cdots` issued in the “main matrix” (not in the exterior column), the cells in the exterior column are considered as outside the matrix. That means that it’s possible to do the following matrix with only a `\Cdots` command (and a single `\Vdots`).

$$\begin{pmatrix} & & C_j \\ 0 & \vdots & 0 \\ 0 & a \cdots \cdots & 0 \end{pmatrix}_{L_i}$$

Changes between version 2.1.3 and 2.1.4

Replacement of some options `0 { }` in commands and environments defined with `xparse` by `! 0 { }` (because a recent version of `xparse` introduced the specifier `!` and modified the default behaviour of the last optional arguments).

See www.texdev.net/2018/04/21/xparse-optional-arguments-at-the-end

Changes between version 2.1.4 and 2.1.5

Compatibility with the classes `revtex4-1` and `revtex4-2`.

Option `allow-duplicate-names`.

⁶³cf. tex.stackexchange.com/questions/450841/tikz-externalize-and-nicematrix-package

⁶⁴Before this version, there was an error when using `nicematrix` with Tikz externalization. In any case, it’s not possible to externalize the Tikz elements constructed by `nicematrix` because they use the options `overlay` and `remember picture`.

Changes between version 2.1.5 and 2.2

Possibility to draw horizontal dotted lines to separate rows with the command `\hdottedline` (similar to the classical command `\hline` and the command `\dashline` of `arydshln`).

Possibility to draw vertical dotted lines to separate columns with the specifier ":" in the preamble (similar to the classical specifier "|" and the specifier ":" of `arydshln`).

Changes between version 2.2 and 2.2.1

Improvement of the vertical dotted lines drawn by the specifier ":" in the preamble.

Modification of the position of the dotted lines drawn by `\hdottedline`.

Changes between version 2.2.1 and 2.3

Compatibility with the column type S of `siunitx`.

Option `hlines`.

Changes between version 2.3 and 3.0

Modification of `\Hdotsfor`. Now `\Hdotsfor` erases the `\vlines` (of "|") as `\hdotsfor` does.

Composition of exterior rows and columns on the four sides of the matrix (and not only on two sides) with the options `first-row`, `last-row`, `first-col` and `last-col`.

Changes between version 3.0 and 3.1

Command `\Block` to draw block matrices.

Error message when the user gives an incorrect value for `last-row`.

A dotted line can no longer cross another dotted line (excepted the dotted lines drawn by `\cdottedline`, the symbol ":" (in the preamble of the array) and `\line` in `code-after`).

The starred versions of `\Cdots`, `\Ldots`, etc. are now deprecated because, with the new implementation, they become pointless. These starred versions are no longer documented.

The vertical rules in the matrices (drawn by "|") are now compatible with the color fixed by `colortbl`.

Correction of a bug: it was not possible to use the colon ":" in the preamble of an array when `pflatex` was used with `french-babel` (because `french-babel` activates the colon in the beginning of the document).

Changes between version 3.1 and 3.2 (and 3.2a)

Option `small`.

Changes between version 3.2 and 3.3

The options `first-row`, `last-row`, `first-col` and `last-col` are now available in the environments `{NiceMatrix}`, `{pNiceMatrix}`, `{bNiceMatrix}`, etc.

The option `columns-width=auto` doesn't need any more a second compilation.

The options `renew-dots`, `renew-matrix` and `transparent` are now available as package options (as said in the documentation).

The previous version of `nicematrix` was incompatible with a recent version of `expl3` (released 2019/09/30). This version is compatible.

Changes between version 3.3 and 3.4

Following a discussion on TeX StackExchange⁶⁵, optimization of Tikz externalization is disabled in the environments of `nicematrix` when the class `standalone` or the package `standalone` is used.

Changes between version 3.4 and 3.5

Correction on a bug on the two previous versions where the `code-after` was not executed.

Changes between version 3.5 and 3.6

LaTeX counters `iRow` and `jCol` available in the cells of the array.

Addition of `\normalbaselines` before the construction of the array: in environments like `{align}` of `amsmath` the value of `\baselineskip` is changed and if the options `first-row` and `last-row` were used in an environment of `nicematrix`, the position of the delimiters was wrong.

A warning is written in the `.log` file if an obsolete environment is used.

There is no longer artificial errors `Duplicate~name` in the environments of `amsmath`.

Changes between version 3.6 and 3.7

The four “corners” of the matrix are correctly protected against the four codes: `code-for-first-col`, `code-for-last-col`, `code-for-first-row` and `code-for-last-row`.

New command `\pAutoNiceMatrix` and its variants (suggestion of Christophe Bal).

Changes between version 3.7 and 3.8

New programmation for the command `\Block` when the block has only one row. With this programmation, the vertical rules drawn by the specifier “`|`” at the end of the block is actually drawn. In previous versions, they were not because the block of one row was constructed with `\multicolumn`. An error is raised when an obsolete environment is used.

Changes between version 3.8 and 3.9

New commands `\NiceMatrixLastEnv` and `\OnlyMainNiceMatrix`.

New options `create-medium-nodes` and `create-large-nodes`.

Changes between version 3.9 and 3.10

New option `light-syntax` (and `end-of-row`).

New option `dotted-lines-margin` for fine tuning of the dotted lines.

Changes between versions 3.10 and 3.11

Correction of a bug linked to `first-row` and `last-row`.

⁶⁵cf. tex.stackexchange.com/questions/510841/nicematrix-and-tikz-external-optimize

Changes between versions 3.11 and 3.12

Command `\rotate` in the cells of the array.

Options `vlines`, `hlines` and `hvlines`.

Option `baseline` pour `{NiceArray}` (not for the other environments).

The name of the Tikz nodes created by the command `\Block` has changed: when the command has been issued in the cell $i-j$, the name is `i-j-block` and, if the creation of the “medium nodes” is required, a node `i-j-block-medium` is created.

If the user tries to use more columns than allowed by its environment, an error is raised by `nicematrix` (instead of a low-level error).

The package must be loaded with the option `obsolete-environments` if we want to use the deprecated environments.

Changes between versions 3.12 and 3.13

The behaviour of the command `\rotate` is improved when used in the “last row”.

The option `dotted-lines-margin` has been renamed in `xdots/shorten` and the options `xdots/color` and `xdots/line-style` have been added for a complete customisation of the dotted lines.

In the environments without preamble (`{NiceMatrix}`, `{pNiceMatrix}`, etc.), it's possible to use the options `l` (=L) or `r` (=R) to specify the type of the columns.

The starred versions of the commands `\Cdots`, `\Ldots`, `\Vdots`, `\Ddots` and `\Idots` are deprecated since the version 3.1 of `nicematrix`. Now, one should load `nicematrix` with the option `starred-commands` to avoid an error at the compilation.

The code of `nicematrix` no longer uses Tikz but only PGF. By default, Tikz is *not* loaded by `nicematrix`.

Changes between versions 3.13 and 3.14

Correction of a bug (question 60761504 on [stackoverflow](#)).

Better error messages when the user uses & or \\" when `light-syntax` is in force.

Changes between versions 3.14 and 3.15

It's possible to put labels on the dotted lines drawn by `\Ldots`, `\Cdots`, `\Vdots`, `\Ddots`, `\Idots`, `\Hdotsfor` and the command `\line` in the `code-after` with the tokens `_` and `^`.

The option `baseline` is now available in all the environments of `nicematrix`. Before, it was available only in `{NiceArray}`.

New keyword `\CodeAfter` (in the environments of `nicematrix`).

Changes between versions 3.15 and 4.0

New environment `{NiceTabular}`

Commands to color cells, rows and columns with a perfect result in the PDF.

Changes between versions 4.0 and 4.1

New keys `cell-space-top-limit` and `cell-space-bottom-limit`

New command `\diagbox`

The key `hvline` don't draw rules in the blocks (commands `\Block`) and in the virtual blocks corresponding to the dotted lines.

Changes between versions 4.1 and 4.2

It's now possible to write `\begin{pNiceMatrix}a&b\\c&d\end{pNiceMatrix}^2` with the expected result.

Changes between versions 4.2 and 4.3

The horizontal centering of the content of a `\Block` is correct even when an instruction such as `!{\quad}` is used in the preamble of the array.

It's now possible to use the command `\Block` in the “last row”.

Changes between versions 4.3 and 4.4

New key `hvlines-except-corners`.

Changes between versions 4.4 and 5.0

Use of the standard column types `l`, `c` and `r` instead of `L`, `C` and `R`.

It's now possible to use the command `\diagbox` in a `\Block`.

Command `\tabularnote`

Changes between versions 5.0 and 5.1

The vertical rules specified by `|` in the preamble are not broken by `\hline\hline` (and other).

Environment `{NiceTabular*}`

Command `\Vdotsfor` similar to `\Hdotsfor`

The variable `\g_nicematrix_code_after_t1` is now public.

Changes between versions 5.1 and 5.2

The vertical rules specified by `|` or `||` in the preamble respect the blocks.

Key `respect-blocks` for `\rowcolors` (with a `s`) in the `code-before`.

The variable `\g_nicematrix_code_before_t1` is now public.

The key `baseline` may take in as value an expression of the form `line-i` to align the `\hline` in the row *i*.

The key `hvlines-except-corners` may take in as value a list of corners (eg: NW,SE).

Changes between versions 5.2 and 5.3

Keys `c`, `r` and `l` for the command `\Block`.

It's possible to use the key `draw-first` with `\Ddots` and `\Idots` to specify which dotted line will be drawn first (the other lines will be drawn parallel to that one if parallelization is activated).

Changes between versions 5.3 and 5.4

Key `tabularnote`.

Different behaviour for the mono-column blocks.

Changes between versions 5.4 and 5.5

The user must never put `\omit` before `\CodeAfter`.

Correction of a bug: the tabular notes `\tabularnotes` were not composed when present in a block (except a mono-column block).

Changes between versions 5.5 and 5.6

Different behaviour for the mono-row blocks.

New command `\NotEmpty`.

Changes between versions 5.6 and 5.7

New key `delimiters-color`

Keys `fill`, `draw` and `line-width` for the command `\Block`.

Changes between versions 5.7 and 5.8

Keys `cols` and `restart` of the command `\rowcolors` in the `code-before`.

Modification of the behaviour of `\\"` in the columns of type `p`, `m` or `b` (for a behaviour similar to the environments of `array`).

Better error messages for the command `\Block`.

Changes between versions 5.8 and 5.9

Correction of a bug: in the previous versions, it was not possible to use the key `line-style` for the continuous dotted lines when the Tikz library `babel` was loaded.

New key `cell-space-limits`.

Changes between versions 5.9 and 5.10

New command `\SubMatrix` available in the `\CodeAfter`.

It's possible to provide options (between brackets) to the keyword `\CodeAfter`.

A (non fatal) error is raised when the key `transparent`, which is deprecated, is used.

Changes between versions 5.10 and 5.11

It's now possible, in the `code-before` and in the `\CodeAfter`, to use the syntax `| (i-|j)` for the Tikz node at the intersection of the (potential) horizontal rule number *i* and the (potential) vertical rule number *j*.

Changes between versions 5.11 and 5.12

Keywords `\CodeBefore` and `\Body` (alternative syntax to the key `code-before`).

New key `delimiters/max-width`.

New keys `hlines`, `vlines` and `hvlines` for the command `\SubMatrix` in the `\CodeAfter`.

New key `rounded-corners` for the command `\Block`.

Changes between versions 5.12 and 5.13

New command `\arraycolor` in the `\CodeBefore` (with its key `except-corners`).

New key `borders` for the command `\Block`.

New command `\Hline` (for horizontal rules not drawn in the blocks).

The keys `vlines` and `hlines` takes in as value a (comma-separated) list of numbers (for the rules to draw).

Changes between versions 5.13 and 5.14

Nodes of the form `(1.5)`, `(2.5)`, `(3.5)`, etc.

Keys `t` and `b` for the command `\Block`.

Key `corners`.

Changes between versions 5.14 and 5.15

Key `hvlines` for the command `\Block`.

The commands provided by `nicematrix` to color cells, rows and columns don't color the cells which are in the "corners" (when the key `corner` is used).

It's now possible to specify delimiters for submatrices in the preamble of an environment.

The version 5.15b is compatible with the version 3.0+ of `siunitx` (previous versions were not).

Changes between versions 5.15 and 5.16

It's now possible to use the cells corresponding to the contents of the nodes (of the form `i-j`) in the `\CodeBefore` when the key `create-cell-nodes` of that `\CodeBefore` is used. The medium and the large nodes are also available if the corresponding keys are used.

Changes between versions 5.16 and 5.17

The key `define-L-C-R` (only available at load-time) now raises a (non fatal) error (that key will probably be deleted in a future version of `nicematrix`).

Keys L, C and R for the command `\Block`.

Key `hvlines-except-borders`.

It's now possible to use a key `l`, `r` or `c` with the command `\pAutoNiceMatrix` (and the similar ones).

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
<code>\@C commands:</code>	
<code>\@C_Block:</code>	1230, 5093
<code>\@C_Block_i</code>	5098, 5099, 5103
<code>\@C_Block_ii:nnnn</code>	5103, 5104
<code>\@C_Block_iv:nnnn</code>	5134, 5138
<code>\@C_Block_iv:nnnnnn</code>	5327, 5329
<code>\@C_Block_v:nnnnn</code>	5135, 5239
<code>\@C_Block_v:nnnnnn</code>	5356, 5359
<code>\@C_Cdots</code>	1153, 1220, 3646
<code>\g_@C_Cdots_lines_tl</code>	1247, 2799
<code>\@C_Cell:</code>	198, 217, 876, 1724, 1774, 1796, 1995, 2016, 2037, 2606
<code>\@C_CodeAfter:</code>	1234, 5903
<code>\@C_CodeAfter_i:n</code>	878, 2484, 2529, 5903, 5904, 5914
<code>\@C_CodeAfter_ii:n</code>	5907, 5909
<code>\@C_CodeAfter_keys:</code>	2738, 2760
<code>\@C_CodeBefore:w</code>	1387, 1389
<code>\@C_CodeBefore_keys:</code>	1367, 1384
<code>\@C_Ddots</code>	1155, 1222, 3678
<code>\g_@C_Ddots_lines_tl</code>	1250, 2797
<code>\g_@C_HVdotsfor_lines_tl</code>	1252, 2795, 3762, 3839, 6453
<code>\@C_Hdotsfor:</code>	1158, 1227, 3738
<code>\@C_Hdotsfor:nnnn</code>	3764, 3777
<code>\@C_Hdotsfor_i</code>	3747, 3753, 3760
<code>\@C_Hline:</code>	1225, 4586
<code>\@C_Hline_i:n</code>	4586, 4587, 4593
<code>\@C_Hline_ii:nn</code>	4590, 4593
<code>\@C_Hline_iii:n</code>	4591, 4594
<code>\@C_Hspace:</code>	1226, 3732
<code>\@C_Iddots</code>	1156, 1223, 3702
<code>\g_@C_Iddots_lines_tl</code>	1251, 2798
<code>\@C_Ldots</code>	1152, 1157, 1219, 3630
<code>\g_@C_Ldots_lines_tl</code>	1248, 2800
<code>\l_@C_Matrix_bool</code>	278, 1574, 1597, 2597
<code>\l_@C_NiceArray_bool</code>	275, 402, 1293, 1472, 1514, 1635, 1642, 1654, 2448, 2573, 4442, 4446, 4572, 4576, 4794, 4801, 5821
<code>\g_@C_NiceMatrixBlock_int</code>	264, 4853, 4858, 4861, 4872
<code>\l_@C_NiceTabular_bool</code>	168, 276, 883, 1079, 1366, 1369, 1440, 1547, 1551, 1643, 1655, 2449, 2626, 2635, 2737, 2740, 5166, 5248, 5829
<code>\@C_NotEmpty:</code>	1236, 2620
<code>\@C_OnlyMainNiceMatrix:n</code>	1232, 4302
<code>\@C_OnlyMainNiceMatrix_i:n</code>	4305, 4312, 4315
<code>\@C_SubMatrix</code>	2719, 6049
<code>\@C_SubMatrix_in_code_before</code>	1359, 6033
<code>\@C_Vdots</code>	1154, 1221, 3662
<code>\g_@C_Vdots_lines_tl</code>	1249, 2796
<code>\@C_Vdotsfor:</code>	1228, 3837
<code>\@C_Vdotsfor:nnnn</code>	3841, 3852
<code>\@C_W:</code>	1600, 1682, 1982
<code>\@C_actually_color:</code>	1368, 3977
<code>\@C_actually_diagbox:nnnnnn</code>	5145, 5413, 5841, 5857
<code>\@C_actually_draw_Cdots:</code>	3202, 3206
<code>\@C_actually_draw_Ddots:</code>	3352, 3356
<code>\@C_actually_draw_Iddots:</code>	3404, 3408

```

\@_actually_draw_Ldots: . 3163, 3167, 3828
\@_actually_draw_Vdots: . 3284, 3288, 3903
\@_adapt_S_column: .... 229, 234, 247, 1439
\@_add_to_colors_seq:nn .. 3964, 3976, 3999, 4014, 4029, 4038
\@_adjust_pos_of_blocks_seq: .. 2706, 2762
\@_adjust_pos_of_blocks_seq_i:nnnn .. 2765, 2767
\@_adjust_size_box: ..... 954, 980, 1805, 2046, 2508, 2553
\@_adjust_to_submatrix:nn .. 3047, 3150, 3189, 3270, 3345, 3397
\@_adjust_to_submatrix:nnnnnn . 3054, 3056
\@_after_array: ..... 1583, 2639
\g @_after_col_zero_bool .. 305, 1120, 2485, 3744
\@_analyze_end:Nn ..... 2274, 2319
\l @_argspec_t1 ..... 3628, 3629, 3630, 3646, 3662, 3678, 3702, 3758, 3759, 3760, 3835, 3836, 3837, 3913, 3914, 3915
\@_array: ..... 1074, 2275, 2302
\@_arraycolor ..... 1356, 4075
\c @_arydshln_loaded_bool ... 24, 31, 1710
\l @_auto_columns_width_bool .. 505, 652, 2386, 2390, 4848
\g @_aux_found_bool ..... 1264, 1269, 1391, 1460, 1463
\g @_aux_t1 ..... 280, 1466, 1589, 2648, 2663, 2672, 2747, 4669
\l @_bar_at_end_of_pream_bool .. 1636, 1768, 2452
\l @_baseline_t1 496, 497, 645, 646, 647, 648, 1087, 1516, 2087, 2099, 2104, 2106, 2111, 2116, 2198, 2199, 2203, 2208, 2210, 2215
\@_begin_of_NiceMatrix:nn .... 2595, 2616
\@_begin_of_row: .... 881, 904, 1179, 2486
\l @_block_auto_columns_width_bool .. 1453, 2391, 4841, 4846, 4856, 4866
\g @_block_box_int ..... 346, 1433, 5140, 5154, 5156, 5192, 5204, 5216, 5225, 5235
\g @_blocks_dp_dim ..... 272, 962, 965, 966, 5219, 5222
\g @_blocks_ht_dim ..... 271, 968, 971, 972, 5210, 5213
\g @_blocks_seq ..... 319, 1455, 2137, 5229, 5241, 5327
\g @_blocks_wd_dim ..... 270, 956, 959, 960, 5198, 5201
\c @_booktabs_loaded_bool 25, 34, 1168, 2169
\l @_borders_clist ..... 335, 5297, 5386, 5683, 5699, 5701, 5703, 5705, 5724, 5736
\@_cartesian_path: ..... 4008, 4023, 4137, 4149, 4242
\@_cartesian_path:n .... 4053, 4184, 4242
\l @_cell_box 882, 928, 930, 936, 942, 945, 949, 958, 959, 964, 965, 970, 971, 981, 982, 983, 984, 986, 989, 993, 995, 1014, 1029, 1031, 1038, 1039, 1052, 1170, 1277, 1279, 1795, 1806, 2036, 2047, 2487, 2511, 2514, 2516, 2533, 2556, 2560, 5421, 5531, 5568, 5836
\l @_cell_space_bottom_limit_dim ... 485, 558, 984
\l @_cell_space_top_limit_dim 484, 556, 982
\l @_cell_type_t1 .. 268, 269, 1724, 1797, 1995, 2038, 5118, 5120
\@_cellcolor ..... 1351, 4055, 4067, 4068
\@_cellcolor_tabular ..... 1162, 4267
\g @_cells_seq .. 2313, 2314, 2315, 2317
\@_chessboardcolors ..... 1358, 4060
\@_cline ..... 147, 1218
\@_cline_i:nn ..... 148, 149, 161, 164
\@_cline_i:w ..... 149, 150
\l @_code_before_bool ..... 309, 642, 669, 1094, 1283, 1315, 1469, 2333, 2350, 2368, 2399, 2425, 2460, 2753, 2755
\g @_code_before_t1 . 1459, 1467, 1470, 2749
\l @_code_before_t1 ..... 308, 641, 1314, 1367, 1470
\l @_code_for_first_col_t1 ..... 575, 2498
\l @_code_for_first_row_t1 . 579, 892, 5500
\l @_code_for_last_col_t1 ..... 577, 2542
\l @_code_for_last_row_t1 . 581, 899, 5503
\l @_code_t1 ..... 300, 6028, 6243
\l @_col_max_int ..... 330, 2914, 2925, 2993, 3052, 3069
\l @_col_min_int ..... 329, 2919, 2982, 2987, 3050, 3067
\g @_col_total_int 267, 997, 1243, 1323, 1334, 1404, 1500, 1963, 1964, 2418, 2419, 2463, 2467, 2472, 2473, 2532, 2643, 2645, 2657, 2824, 3237, 3255, 3315, 3898, 4292, 4899, 4909, 4943, 5030, 5339, 5538, 6069, 6118
\l @_color_t1 ..... 337, 5090, 5158, 5160
\g @_cols_vlism_seq .. 288, 1619, 1701, 6146
\@_columncolor ..... 1357, 4010
\@_columncolor:n ..... 4016, 4019
\@_columncolor_preamble ..... 1164, 4290
\c @_columncolor_regex ..... 59, 1627
\l @_columns_width_dim ..... 265, 653, 795, 2387, 2393, 4854, 4860
\g @_com_or_env_str ..... 292, 295
\@_computations_for_large_nodes: ... 4970, 4983, 4988
\@_computations_for_medium_nodes: ... 4890, 4959, 4969, 4980
\@_compute_a_corner:nnnnnn ..... 4657, 4659, 4661, 4663, 4677
\@_compute_corners: ..... 2705, 4649
\@_construct_preamble: ..... 1290, 1594
\l @_corners_cells_seq ..... 323, 2711, 4187, 4227, 4376, 4382, 4389, 4508, 4514, 4521, 4651, 4667, 4671, 4672, 4733
\l @_corners_clist ..... 501, 630, 635, 4342, 4475, 4652
\@_create_col_nodes: .... 2278, 2306, 2325
\@_create_diag_nodes: ... 1340, 2682, 2866
\@_create_extra_nodes: ..... 1422, 2136, 2858, 4880
\@_create_large_nodes: ..... 4888, 4964

```

```

\@_create_medium_and_large_nodes: ...  

..... 4885, 4975  

\@_create_medium_nodes: ..... 4886, 4954  

\@_create_nodes: 4961, 4972, 4982, 4985, 5026  

\@_create_row_node: ..... 1090, 1123, 1169  

\@_cut_on_hyphen:w .....  

..... 3990, 4045, 4050, 4110, 4197,  

4198, 4220, 4221, 4251, 4252, 5601, 5610,  

5641, 5644, 5688, 5691, 6037, 6042, 6061, 6064  

\g_@@ddots_int ..... 2685, 3376, 3377  

\@_def_env:nnn .....  

..... 2579, 2590, 2591, 2592, 2593, 2594  

\@_define_L_C_R: ..... 252, 1289  

\c_@@_define_L_C_R_bool ... 251, 1289, 6367  

\@_define_com:nnn .....  

..... 5805, 5813, 5814, 5815, 5816, 5817  

\@_delimiter:nnn .....  

... 1839, 1860, 1868, 1881, 1887, 1893, 5917  

\l_@@_delimiters_color_tl .....  

.. 518, 728, 1380, 1539, 1540, 1557, 1558,  

5897, 5955, 5956, 5983, 6295, 6296, 6319, 6320  

\l_@@_delimiters_max_width_bool .....  

..... 519, 726, 1562  

\g_@@_delta_x_one_dim .... 2687, 3379, 3389  

\g_@@_delta_x_two_dim .... 2689, 3427, 3437  

\g_@@_delta_y_one_dim .... 2688, 3381, 3389  

\g_@@_delta_y_two_dim .... 2690, 3429, 3437  

\@_diagbox:nn ..... 1235, 5837  

\@_dotfill: ..... 5826  

\@_dotfill_i: ..... 5831, 5833  

\@_dotfill_ii: ..... 5830, 5833, 5834  

\@_dotfill_iii: ..... 5834, 5835  

\@_double_int_eval:n .... 3909, 3923, 3924  

\g_@@_dp_ante_last_row_dim .... 907, 1203  

\g_@@_dp_last_row_dim .....  

.... 907, 908, 1206, 1207, 1278, 1279, 1533  

\g_@@_dp_row_zero_dim .....  

.... 927, 928, 1197, 1198, 1526, 2192, 2231  

\@_draw_Cdots:nnn ..... 3187  

\@_draw_Ddots:nnn ..... 3343  

\@_draw_Idots:nnn ..... 3395  

\@_draw_Ldots:nnn ..... 3148  

\@_draw_Vdots:nnn ..... 3268  

\@_draw_blocks: ..... 2137, 5324  

\@_draw_dotted_lines: ..... 2704, 2784  

\@_draw_dotted_lines_i: ..... 2787, 2791  

\l_@@_draw_first_bool . 344, 3693, 3717, 3728  

\@_draw_hlines: ..... 2717, 4568  

\@_draw_line: ..... 3185,  

3230, 3341, 3393, 3441, 3443, 3962, 4809, 4839  

\@_draw_line_ii:nn ..... 3942, 3946  

\@_draw_line_iii:nn ..... 3949, 3953  

\@_draw_non_standard_dotted_line: ..  

..... 3449, 3451  

\@_draw_non_standard_dotted_line:n ..  

..... 3454, 3457  

\@_draw_non_standard_dotted_line:nnn  

..... 3459, 3464, 3478  

\@_draw_standard_dotted_line: . 3448, 3479  

\@_draw_standard_dotted_line_i: 3542, 3546  

\l_@@_draw_tl ..... 334, 5291,  

5295, 5364, 5583, 5589, 5591, 5593, 5630, 5631  

\@_draw_vlines: ..... 2718, 4438  

\g_@@_empty_cell_bool .... 316, 988, 998,  

2521, 2568, 3644, 3660, 3676, 3700, 3723, 3734  

\@_end_Cell: ..... 203, 219,  

975, 1726, 1784, 1801, 1997, 2026, 2042, 2606  

\l_@@_end_of_row_tl .....  

..... 515, 516, 569, 2298, 2299, 6551  

\c_@@_endpgfornikzpicture_tl .....  

..... 43, 47, 2788, 3950, 4780  

\c_@@_enumitem_loaded_bool .....  

..... 26, 37, 375, 696, 701, 712, 717  

\@_env: .. 259, 263, 913, 919, 1015, 1021,  

1035, 1043, 1099, 1105, 1111, 1182, 1324,  

1325, 1330, 1331, 1336, 1337, 1348, 1401,  

1402, 1407, 1410, 1413, 1416, 2334, 2337,  

2339, 2355, 2361, 2364, 2373, 2379, 2382,  

2404, 2410, 2413, 2430, 2436, 2442, 2463,  

2467, 2473, 2728, 2826, 2830, 2836, 2843,  

2849, 2883, 2890, 2892, 2893, 2954, 3022,  

3086, 3097, 3110, 3113, 3132, 3135, 3240,  

3243, 3258, 3261, 3791, 3809, 3866, 3884,  

3935, 3937, 3956, 3959, 4688, 4707, 4725,  

4912, 4914, 4922, 5033, 5042, 5060, 5436,  

5445, 5449, 5463, 5468, 5480, 5486, 5487,  

5490, 5508, 5545, 5932, 5935, 6085, 6087,  

6092, 6094, 6121, 6123, 6128, 6130, 6228, 6239  

\g_@@_env_int .....  

.. 258, 259, 261, 1452, 1461, 1464, 1588, 5069  

\@_error:n .. 12, 378, 403, 528, 538, 591,  

722, 778, 788, 794, 803, 811, 829, 836, 844,  

845, 846, 852, 857, 858, 859, 870, 872, 873,  

874, 1382, 1495, 1505, 1577, 2121, 2174,  

2220, 4074, 4089, 5322, 5681, 5901, 6013,  

6024, 6031, 6070, 6366, 6376, 6381, 6408, 6418  

\@_error:nn ..... 13,  

660, 1690, 1691, 1692, 1842, 1888, 1894,  

1984, 1985, 1986, 3633, 3636, 3649, 3652,  

3665, 3668, 3682, 3683, 3688, 3689, 3706,  

3707, 3712, 3713, 4665, 5686, 6018, 6100, 6103  

\@_error:nnn ..... 14, 3940, 6175, 6210  

\@_error_too_much_cols: ..... 1664, 6438  

\@_everycr: ..... 1116, 1192, 1195  

\@_everycr_i: ..... 1116, 1117  

\l_@@_except_borders_bool .....  

..... 510, 603, 4442, 4446, 4572, 4576  

\@_exec_code_before: ..... 1283, 1361  

\@_expand_clist:NN ..... 4190, 4191, 4243  

\l_@@_exterior_arraycolsep_bool .....  

..... 498, 791, 1645, 1657, 2451  

\l_@@_extra_left_margin_dim .....  

..... 513, 619, 1306, 2519  

\l_@@_extra_right_margin_dim .....  

..... 514, 620, 1487, 2564, 3318  

\@_extract_brackets ..... 5398, 5573  

\@_extract_coords_values: .... 5051, 5058  

\@_fatal:n .... 15, 284, 1443, 1820, 1849,  

2283, 2287, 2289, 2322, 3749, 6443, 6446, 6449  

\@_fatal:nn ..... 16, 1715, 1989  

\l_@@_fill_tl ..... 333, 5289, 5396, 5398  

\l_@@_final_i_int .....  

..... 2694, 2901, 2906, 2909, 2934,  

2942, 2946, 2955, 2963, 3043, 3098, 3179,  

3252, 3258, 3261, 3782, 3810, 3878, 3888, 3890

```

```

\l_@@_final_j_int ..... 2695, 2902, 2907, 2914, 2919, 2925, 2935,
2943, 2947, 2956, 2964, 3044, 3099, 3132,
3135, 3143, 3369, 3803, 3813, 3815, 3857, 3886
\l_@@_final_open_bool ..... 2697, 2908,
2912, 2915, 2922, 2928, 2932, 2948, 3176,
3211, 3216, 3227, 3291, 3301, 3306, 3327,
3366, 3416, 3550, 3565, 3596, 3597, 3780,
3804, 3816, 3855, 3879, 3891, 3932, 4777, 4814
\@_find_extremities_of_line:nnnn ... .... 2896, 3153, 3192, 3273, 3348, 3400
\l_@@_first_col_int ..... 135, 148, 356, 357, 571, 850, 881,
1334, 1404, 1509, 1637, 2328, 2348, 2655,
2824, 3237, 3255, 3742, 4211, 4304, 4899,
4909, 4943, 4991, 5030, 5786, 5792, 5798, 6118
\l_@@_first_i_t1 6057, 6062, 6081, 6112,
6121, 6123, 6178, 6185, 6187, 6268, 6279, 6283
\l_@@_first_j_t1 ..... 6058, 6063, 6085,
6087, 6148, 6161, 6168, 6170, 6269, 6280, 6284
\l_@@_first_row_int ..... 354, 355, 572, 854, 1241,
1328, 1399, 1524, 2118, 2189, 2217, 2228,
2652, 2822, 3107, 3129, 4892, 4906, 4933,
4990, 5028, 5442, 5460, 5784, 5929, 6082, 6569
\c_@@_footnote_bool ..... 1428, 1592, 6336, 6379, 6402, 6405, 6415, 6421
\c_@@_footnotehyper_bool . 6335, 6380, 6412
\@_full_name_env: ..... 293, 6427, 6459, 6466, 6474, 6482, 6486,
6583, 6596, 6599, 6612, 6617, 6622, 6624,
6648, 6667, 6672, 6677, 6684, 6710, 6719, 6890
\@_hdottedline: ..... 1224, 4762
\@_hdottedline:n ..... 4770, 4774
\@_hdottedline_i: ..... 4765, 4767
\@_hdottedline_i:n ..... 4779, 4783
\@_hline:nn ..... 4456, 4583, 4602
\@_hline_i:nn ..... 2715, 4459, 4462
\@_hline_i_complete:nn ..... 2715, 4566
\@_hline_ii:nnnn ... 4484, 4495, 4528, 4567
\l_@@_hlines_clist ..... 350, 583, 597,
602, 632, 1124, 1126, 1130, 2717, 4581, 4582
\l_@@_hpos_of_block_cap_bool ..... 341, 5310, 5313, 5316, 5439, 5509, 5546
\l_@@_hpos_of_block_t1 ..... 339, 340,
5074, 5076, 5078, 5080, 5082, 5084, 5119,
5120, 5122, 5165, 5171, 5181, 5232, 5255,
5259, 5271, 5276, 5303, 5305, 5307, 5309,
5312, 5315, 5512, 5524, 5535, 5539, 5549, 5561
\g_@@_ht_last_row_dim ..... 909, 1204, 1205, 1276, 1277, 1532
\g_@@_ht_row_one_dim .. 935, 936, 1201, 1202
\g_@@_ht_row_zero_dim ..... 929, 930, 1199, 1200, 1527, 2191, 2230
\@_hvlines_block:nnn ..... 5380, 5637
\l_@@_hvlines_block_bool .. 345, 5299, 5376
\@_i: ..... 4892, 4894,
4895, 4896, 4897, 4906, 4912, 4914, 4915,
4916, 4917, 4922, 4923, 4924, 4925, 4933,
4936, 4938, 4939, 4940, 4992, 4994, 4997,
4998, 5002, 5003, 5028, 5033, 5035, 5037,
5041, 5042, 5053, 5060, 5062, 5064, 5068, 5069
\g_@@_iddots_int ..... 2686, 3424, 3425
\l_@@_in_env_bool .... 274, 402, 1443, 1444
\c_@@_in_preamble_bool .. 21, 22, 23, 692, 708
\l_@@_initial_i_int ..... 2692,
2899, 2974, 2977, 3002, 3010, 3014, 3023,
3031, 3041, 3087, 3172, 3218, 3220, 3234,
3240, 3243, 3781, 3782, 3792, 3860, 3870, 3872
\l_@@_initial_j_int ..... 2693, 2900, 2975, 2982,
2987, 2993, 3003, 3011, 3015, 3024, 3032,
3042, 3088, 3110, 3113, 3121, 3308, 3310,
3315, 3361, 3785, 3795, 3797, 3856, 3857, 3868
\l_@@_initial_open_bool ..... 2696, 2976, 2980, 2983, 2990, 2996,
3000, 3016, 3169, 3208, 3215, 3225, 3291,
3298, 3304, 3358, 3410, 3548, 3595, 3779,
3786, 3798, 3854, 3861, 3873, 3931, 4776, 4813
\@_insert_tabularnotes: ..... 2141, 2144
\@_instruction_of_type:nnn ..... 1055, 3638, 3654, 3670, 3693, 3717
\c_@@_integers_alist_t1 ..... 6253, 6264
\l_@@_inter_dots_dim ..... 486, 487, 2701, 3553, 3560, 3571, 3579,
3586, 3591, 3603, 3611, 4805, 4807, 4835, 4837
\g_@@_internal_code_after_t1 301, 1760,
1838, 1859, 1867, 1880, 1886, 1892, 1902,
2733, 2734, 4601, 4769, 5143, 5411, 5839, 6045
\@_intersect_our_row:nnnn ..... 4173
\@_intersect_our_row_p:nnnn ..... 4124
\@_j: ..... 4899, 4901,
4902, 4903, 4904, 4909, 4912, 4914, 4917,
4919, 4920, 4922, 4925, 4927, 4928, 4943,
4946, 4948, 4949, 4950, 5005, 5007, 5010,
5012, 5016, 5017, 5030, 5033, 5034, 5036,
5041, 5042, 5054, 5060, 5061, 5063, 5068, 5069
\l_@@_l_dim ..... 3526, 3527, 3540, 3541, 3553, 3559,
3570, 3578, 3586, 3591, 3603, 3604, 3611, 3612
\l_@@_large_nodes_bool 509, 610, 4884, 4888
\g_@@_last_col_found_bool ..... 364,
1246, 1501, 1569, 2417, 2455, 2530, 2642, 5536
\l_@@_last_col_int ..... 362, 363, 779, 822, 824, 837,
853, 871, 1267, 1270, 1504, 1649, 2602,
2604, 2643, 2645, 3278, 3313, 3635, 3651,
3689, 3713, 5332, 5337, 5338, 5339, 5342,
5371, 5383, 5393, 5405, 5417, 5432, 5463,
5468, 5476, 5492, 5788, 5794, 5800, 6442, 6460
\l_@@_last_col_without_value_bool ...
361, 821, 2644, 6445
\l_@@_last_empty_column_int ..... 4698, 4699, 4712, 4718, 4731
\l_@@_last_empty_row_int ..... 4680, 4681, 4694, 4715
\l_@@_last_i_t1 ..... 6059,
6065, 6068, 6081, 6115, 6128, 6130, 6178, 6185
\l_@@_last_j_t1 ..... 6060, 6066, 6069, 6092, 6094, 6151, 6161, 6168
\l_@@_last_row_int ..... 358, 359, 573, 897, 943, 1136,
1261, 1265, 1272, 1489, 1493, 1496, 1508,
1530, 2300, 2301, 2494, 2495, 2539, 2540,
2647, 3158, 3197, 3667, 3683, 3707, 4310,

```

4318, 5331, 5334, 5335, 5354, 5371, 5383,
 5393, 5405, 5416, 5430, 5491, 5502, 5796, 6709
 $\backslash l_{@@_last_row_without_value_bool}$
 360, 1263, 1491, 2646
 $\backslash l_{@@_left_delim_dim}$
 1291, 1295, 1300, 2266, 2517
 $\backslash g_{@@_left_delim_tl}$
 1299, 1430, 1541, 1565, 1633, 1823, 1825, 4804
 $\backslash l_{@@_left_margin_dim}$
 511, 613, 1305, 2518, 4795, 5021
 $\backslash l_{@@_letter_for_dotted_lines_str}$
 802, 813, 814, 1696
 $\backslash l_{@@_letter_vlism_tl}$ 287, 590, 1699
 $\backslash l_{@@_light_syntax_bool}$ 495, 567, 1308, 1482
 $\backslash @@_light_syntax_i$ 2291, 2294
 $\backslash @@_line$ 2732, 3915
 $\backslash @@_line_i:nn$ 3922, 3929
 $\backslash l_{@@_line_width_dim}$
 338, 5301, 5584, 5622, 5633, 5639, 5651,
 5678, 5698, 5713, 5715, 5725, 5726, 5728, 5739
 $\backslash @@_line_with_light_syntax:n$ 2305, 2309
 $\backslash @@_line_with_light_syntax_i:n$
 2304, 2310, 2311
 $\backslash @@_math_toggle_token:$
 167, 977, 2488, 2505, 2534, 2550, 5881, 5885
 $\backslash g_{@@_max_cell_width_dim}$
 985, 986, 1454, 2392, 4847, 4873
 $\backslash c_{@@_max_l_dim}$ 3540, 3545
 $\backslash l_{@@_medium_nodes_bool}$ 508, 609, 4882, 5483
 $\backslash @@_message_hdotsfor:$ 6451, 6459, 6466, 6474
 $\backslash @@_msg_new:nn$
 17, 6351, 6357, 6384, 6393, 6423, 6456,
 6463, 6471, 6479, 6484, 6490, 6495, 6500,
 6505, 6510, 6515, 6520, 6525, 6531, 6537,
 6542, 6548, 6554, 6559, 6566, 6573, 6580,
 6586, 6595, 6597, 6603, 6620, 6627, 6632,
 6639, 6646, 6653, 6660, 6665, 6675, 6681,
 6688, 6695, 6701, 6707, 6715, 6717, 6723, 7002
 $\backslash @@_msg_new:nnn$ 18, 6337, 6609, 6728,
 6738, 6753, 6774, 6792, 6835, 6887, 6938, 6988
 $\backslash @@_msg_redirect_name:nn$
 19, 797, 1581, 5345, 5348
 $\backslash @@_multicolumn:nnn$ 1229, 1932
 $\backslash g_{@@_multicolumn_cells_seq}$
 325, 1239, 1285, 1947,
 2670, 2674, 2675, 4917, 4925, 5047, 5447, 5465
 $\backslash g_{@@_multicolumn_sizes_seq}$
 326, 1240, 1286, 1949, 2677, 2678, 5048
 $\backslash g_{@@_name_env_str}$ 291,
 296, 297, 1437, 1438, 2321, 2574, 2575,
 2583, 2584, 2613, 2624, 2632, 2756, 5809, 6440
 $\backslash l_{@@_name_str}$ 507, 662,
 915, 918, 1017, 1020, 1107, 1110, 2338,
 2339, 2363, 2364, 2381, 2382, 2412, 2413,
 2438, 2441, 2469, 2472, 5038, 5041, 5065, 5068
 $\backslash g_{@@_names_seq}$ 273, 659, 661, 7000
 $\backslash l_{@@_nb_cols_int}$
 5762, 5773, 5781, 5787, 5793, 5799
 $\backslash l_{@@_nb_rows_int}$ 5761, 5772, 5790
 $\backslash @@_newcolumntype$ 1143, 1599, 1600
 $\backslash @@_node_for_cell:$ 994, 1001, 1372, 2515, 2565
 $\backslash @@_node_for_multicolumn:nn$ 5049, 5056
 $\backslash @@_node_left:nn$ 6227, 6228, 6287
 $\backslash @@_node_position:$
 1330, 1332, 1336, 1338, 1401, 1403, 1411, 1417
 $\backslash @@_node_position_i:$ 1414, 1418
 $\backslash @@_node_right:nn$ 6237, 6239, 6311
 $\backslash g_{@@_not_empty_cell_bool}$ 307, 992, 999, 2621
 $\backslash @@_not_in_exterior:nnnn$ 4165
 $\backslash @@_not_in_exterior_p:nnnn$ 4102
 $\backslash l_{@@_notes_above_space_dim}$ 502, 503
 $\backslash l_{@@_notes_bottomrule_bool}$
 680, 840, 865, 2167
 $\backslash l_{@@_notes_code_after_tl}$ 678, 2176
 $\backslash l_{@@_notes_code_before_tl}$ 676, 2148
 $\backslash @@_notes_label_in_list:n$ 371, 390, 398, 688
 $\backslash @@_notes_label_in_tabular:n$ 370, 411, 685
 $\backslash l_{@@_notes_para_bool}$ 674, 838, 863, 2152
 $\backslash @@_notes_style:n$
 369, 372, 390, 398, 414, 419, 682
 $\backslash l_{@@_nullify_dots_bool}$
 504, 608, 3642, 3658, 3674, 3698, 3721
 $\backslash l_{@@_number_of_notes_int}$ 368, 405, 415, 425
 $\backslash @@_old_CT@arc@$ 1445, 2758
 $\backslash @@_old_cdots$ 1212, 3659
 $\backslash @@_old_ddots$ 1214, 3699
 $\backslash @@_old_dotfill$ 5825, 5828, 5836
 $\backslash @@_old_dotfill:$ 1233
 $\backslash l_{@@_old_iRow_int}$ 302, 1257, 2804
 $\backslash @@_old_ialign:$ 1089, 1208, 5326
 $\backslash @@_old_iddots$ 1215, 3722
 $\backslash l_{@@_old_jCol_int}$ 303, 1259, 2805
 $\backslash @@_old_ldots$ 1211, 3643
 $\backslash @@_old_multicolumn$ 3737
 $\backslash @@_old_pgfpointanchor$ 175, 6245, 6249
 $\backslash @@_old_pgfutil@check@rerun$ 93, 97
 $\backslash @@_old_vdots$ 1213, 3675
 $\backslash @@_open_x_final_dim:$
 3126, 3178, 3212, 3370, 3419
 $\backslash @@_open_x_initial_dim:$
 3104, 3171, 3209, 3363, 3413
 $\backslash @@_open_y_final_dim:$ 3250, 3302, 3368, 3418
 $\backslash @@_open_y_initial_dim:$
 3232, 3299, 3360, 3412
 $\backslash l_{@@_parallelize_diags_bool}$
 499, 500, 605, 2683, 3374, 3422
 $\backslash @@_patch_m_preamble:n$
 1941, 1967, 2004, 2009, 2075
 $\backslash @@_patch_m_preamble_i:n$
 1971, 1972, 1973, 1991
 $\backslash @@_patch_m_preamble_ii:nn$
 1974, 1975, 1976, 2001
 $\backslash @@_patch_m_preamble_iii:n$ 1977, 2006
 $\backslash @@_patch_m_preamble_iv:nnn$
 1978, 1979, 1980, 2011
 $\backslash @@_patch_m_preamble_ix:n$ 2060, 2078
 $\backslash @@_patch_m_preamble_v:nnnn$ 1981, 1982, 2031
 $\backslash @@_patch_m_preamble_vi:n$ 1983, 2052
 $\backslash @@_patch_m_preamble_x:n$
 1999, 2029, 2050, 2055, 2057, 2081
 $\backslash @@_patch_node_for_cell:$ 1027, 1372
 $\backslash @@_patch_node_for_cell:n$ 1025, 1051, 1054
 $\backslash @@_patch_preamble:n$
 1621, 1667, 1705, 1713, 1734, 1765,
 1827, 1843, 1845, 1861, 1869, 1895, 1904, 1924
 $\backslash @@_patch_preamble_i:n$ 1671, 1672, 1673, 1720

\@_patch_preamble_ii:nn
..... 1674, 1675, 1676, 1731
\@_patch_preamble_iii:n . 1677, 1736, 1744
\@_patch_preamble_iii_i:n 1739, 1741
\@_patch_preamble_iv:nnn
..... 1678, 1679, 1680, 1769
\@_patch_preamble_ix:n 1909, 1927
\@_patch_preamble_v:nnnn 1681, 1682, 1790
\@_patch_preamble_vi:n 1683, 1812
\@_patch_preamble_vii:nn
..... 1684, 1685, 1686, 1818
\@_patch_preamble_vii_i:nn 1831, 1834, 1836
\@_patch_preamble_viii:nn
..... 1687, 1688, 1689, 1847
\@_patch_preamble_viii_i:nnn .. 1851, 1873
\@_patch_preamble_x:n
..... 1729, 1788, 1810, 1816, 1906, 1930
\@_patch_preamble_xi:n 1697, 1898
\@_pgf_rect_node:nnn 458, 1415, 5485
\@_pgf_rect_node:nnnnn
..... 433, 5032, 5059, 5435, 5479, 6214
\c @_pgfortikzpicture_tl
..... 42, 46, 2786, 3948, 4778
\@_pgfpointanchor:n 6241, 6246
\@_pgfpointanchor_i:nn .. 6249, 6251
\@_pgfpointanchor_ii:w 6252, 6260
\@_pgfpointanchor_iii:w 6273, 6275
\@_picture_position:
..... 1325, 1332, 1338, 1403, 1417, 1418
\g @_pos_of_blocks_seq
..... 320, 1284, 1456, 1950, 2661, 2665, 2666,
2709, 2764, 4100, 4336, 4469, 4745, 5361, 5849
\g @_pos_of_stroken_blocks_seq
..... 322, 1457, 4340, 4473, 5373
\g @_pos_of_xdots_seq
..... 321, 1458, 2710, 3039, 4338, 4471
\@_pre_array: 1255, 1316, 1479
\@_pre_array_i:w 1312, 1479
\@_pre_array_ii: 1166, 1287
\@_pre_code_before: 1318, 1393
\c @_preamble_first_col_tl 1638, 2480
\c @_preamble_last_col_tl 1650, 2525
\g @_preamble_tl
..... 1432, 1601, 1605, 1609, 1615,
1629, 1638, 1647, 1650, 1659, 1663, 1703,
1712, 1722, 1733, 1746, 1771, 1792, 1814,
1830, 1858, 1866, 1879, 1885, 1900, 1913,
1920, 1929, 1940, 1942, 1993, 2003, 2008,
2013, 2033, 2054, 2064, 2071, 2080, 2275, 2302
\@_pred:n
.... 136, 166, 2604, 4377, 4390, 4509, 4522
\@_provide_pgfsyspdfmark: ... 60, 69, 1427
\@_put_box_in_flow: 1567, 2083, 2268
\@_put_box_in_flow_bis:nn 1564, 2235
\@_put_box_in_flow_i: 2089, 2091
\@_qpoint:n 262, 2094, 2096, 2108,
2124, 2183, 2185, 2201, 2212, 2223, 2872,
2874, 2876, 2878, 2886, 2888, 3121, 3143,
3172, 3179, 3218, 3220, 3234, 3252, 3308,
3310, 3361, 3369, 3956, 3959, 4210, 4214,
4230, 4232, 4400, 4402, 4404, 4532, 4534,
4536, 4786, 4790, 4797, 4831, 4834, 4836,
4938, 4948, 5426, 5428, 5430, 5432, 5456,
5476, 5505, 5606, 5608, 5615, 5617, 5652,
5654, 5658, 5663, 5665, 5669, 5712, 5714,
5716, 5723, 5727, 5729, 5862, 5864, 5867,
5869, 5922, 5924, 6112, 6115, 6153, 6170, 6187
\l @_radius_dim 490, 491, 1901,
2700, 3183, 3184, 3620, 4764, 4788, 4832, 4833
\l @_real_left_delim_dim 2237, 2252, 2267
\l @_real_right_delim_dim 2238, 2264, 2270
\@_recreate_cell_nodes: 1341, 1397
\g @_recreate_cell_nodes_bool
..... 506, 1177, 1341, 1364, 1371, 1376
\@_rectanglecolor .. 1352, 4025, 4058, 4078
\@_rectanglecolor:nnn ... 4031, 4040, 4043
\@_renew_NC@rewrite@S: 186, 190, 210, 1245
\@_renew_dots: 1150, 1238
\l @_renew_dots_bool
..... 606, 787, 1238, 6368, 6375
\@_renew_matrix: 782, 786, 5741, 6370, 6374
\l @_respect_blocks_bool 4084, 4098, 4121
\@_restore_iRow_jCol: 2757, 2802
\@_revtex_array: 1066, 1077
\c @_revtex_bool 50, 52, 55, 57, 1076
\l @_right_delim_dim
..... 1292, 1296, 1302, 2269, 2562
\g @_right_delim_tl .. 1301, 1431, 1559,
1565, 1634, 1826, 1855, 1856, 1877, 1882, 4806
\l @_right_margin_dim
.... 512, 615, 1486, 2563, 3317, 4802, 5024
\@_rotate: 1231, 3908
\g @_rotate_bool
..... 279, 952, 979, 1804, 2045, 2507,
2552, 3908, 5165, 5189, 5194, 5254, 5270, 5422
\@_rotate_cell_box:
.... 940, 979, 1804, 2045, 2507, 2552, 5422
\l @_rounded_corners_dim
..... 336, 5293, 5406, 5598, 5599, 5634, 5680, 5737
\@_roundedrectanglecolor 1353, 4034
\l @_row_max_int 328, 2909, 3051, 3068
\l @_row_min_int 327, 2977, 3049, 3066
\g @_row_of_col_done_bool
..... 306, 1121, 1436, 2347
\g @_row_total_int 266, 1242, 1322,
1328, 1399, 1507, 2119, 2218, 2647, 2654,
2822, 3107, 3129, 3823, 4892, 4906, 4933,
5028, 5354, 5442, 5460, 5929, 6068, 6082, 6570
\@_rowcolor 1354, 3995
\@_rowcolor:n 4001, 4004
\@_rowcolor_tabular 1163, 4278
\@_rowcolors 1355, 4091
\@_rowcolors_i:nnn 4125, 4160
\l @_rowcolors_restart_bool ... 4087, 4113
\g @_rows_seq . 2297, 2299, 2301, 2303, 2305
\l @_rows_tl
..... 4006, 4021, 4051, 4127, 4191, 4216
\l @_rules_color_tl
..... 304, 542, 1476, 1477, 6143, 6144
\@_set_CT@arc@: 169, 1477, 6144
\@_set_CT@arc@_i: 170, 171
\@_set_CT@arc@_ii: 170, 173
\@_set_final_coords: 3077, 3102
\@_set_final_coords_from_anchor:n ..
... 3093, 3182, 3213, 3294, 3303, 3373, 3421
\@_set_initial_coords: 3072, 3091

```

\@_set_initial_coords_from_anchor:n .
... 3082, 3175, 3210, 3293, 3300, 3365, 3415
\@_set_size:n ..... 5759, 5774
\c @_siunitx_loaded_bool 176, 180, 185, 231
\c @_size_seq ..... 1265, 1270, 1320, 1321, 1322, 1323, 2650
\l @_small_bool ..... 780, 827, 833, 855, 886, 1172, 1820, 1849, 2489, 2535, 2698
\@_standard_cline ..... 132, 1217
\@_standard_cline:w ..... 132, 133
\l @_standard_cline_bool .. 483, 554, 1216
\c @_standard_t1 493, 494, 3447, 4808, 4838
\g @_static_num_of_col_int ..... 332, 1576, 1622, 5342, 6475, 6487, 6668
\l @_stop_loop_bool ..... 2903, 2904, 2936, 2949, 2958, 2971, 2972, 3004, 3017, 3026
\@_store_in_tmpb_t1 ..... 5576, 5578
\@_stroke_block:nnn ..... 5368, 5580
\@_stroke_borders_block:nnn ... 5390, 5676
\@_stroke_horizontal:n ... 5704, 5706, 5721
\@_stroke_vertical:n .... 5700, 5702, 5710
\@_sub_matrix:nnnnn ..... 6052, 6054
\@_sub_matrix_i:nn ..... 6104, 6110
\l @_submatrix_extra_height_dim .... 347, 5975, 6138
\l @_submatrix_hlines_clist ..... 352, 5987, 6005, 6177, 6179
\l @_submatrix_left_xshift_dim .... 348, 5977, 6190, 6223
\l @_submatrix_name_str ..... 6020, 6072, 6212, 6214, 6226, 6228, 6236, 6239
\g @_submatrix_names_seq ..... 324, 2736, 6017, 6021, 6618
\l @_submatrix_right_xshift_dim .... 349, 5979, 6199, 6233
\g @_submatrix_seq ... 331, 1282, 3053, 6043
\l @_submatrix_slim_bool 5985, 6080, 6591
\l @_submatrix_vlines_clist ..... 353, 5989, 6007, 6160, 6162
\@_succ:n ..... 161, 165, 1099, 1105, 1131, 1761, 1839, 1918, 1948, 2069, 2096, 2430, 2436, 2441, 2442, 2463, 2467, 2472, 2473, 3143, 3220, 3310, 3369, 4169, 4214, 4230, 4373, 4404, 4447, 4505, 4536, 4577, 4602, 4750, 4752, 4754, 4756, 4797, 4836, 4998, 5002, 5012, 5016, 5430, 5432, 5476, 5615, 5617, 5867, 5869, 5924
\l @_suffix_t1 ..... 4960, 4971, 4981, 4984, 5033, 5041, 5042, 5060, 5068, 5069
\c @_table_collect_begin_t1 . 217, 242, 244
\c @_table_print_t1 ..... 219, 245, 246
\l @_tabular_width_dim ..... 277, 1082, 1084, 1661, 2633
\l @_tabularnote_t1 367, 842, 867, 2140, 2149
\g @_tabularnotes_seq ..... 366, 406, 2155, 2161, 2177
\@_test_hline_in_block:nnnn ..... 4470, 4472, 4605
\@_test_hline_in_stroken_block:nnnn . ..... 4474, 4627
\@_test_if_cell_in_a_block:nn ..... 4684, 4702, 4720, 4740
\@_test_if_cell_in_block:nnnnnn ... ..... 4746, 4748
\@_test_if_math_mode: ..... 281, 1442, 2585
\@_test_in_corner_h: ..... 4475, 4503
\@_test_in_corner_v: ..... 4343, 4371
\@_test_vline_in_block:nnnn ..... 4337, 4339, 4616
\@_test_vline_in_stroken_block:nnnn . ..... 4341, 4638
\l @_the_array_box .. 1288, 1304, 2134, 2135
\c @_tikz_loaded_bool ..... 27, 41, 1343, 2720, 4815
\@_true_c: ..... 202, 218, 1683, 1983
\l @_type_of_col_t1 ..... 825, 826, 2614, 2616, 5766, 5767, 5768, 5776, 5781
\c @_types_of_matrix_seq ..... 6430, 6431, 6436, 6440
\@_update_for_first_and_last_row: .. 923, 987, 1274, 2509, 2554
\@_use_arraybox_with_notes: ... 1521, 2196
\@_use_arraybox_with_notes_b: . 1518, 2180
\@_use_arraybox_with_notes_c: ..... 1519, 1550, 2132, 2194, 2233
\@_vdottedline:n ..... 1903, 4811
\@_vdottedline_i:n ..... 4818, 4823, 4827
\@_vline:nn ..... 1761, 4320, 4453
\@_vline_i:nn ..... 2714, 4325, 4329
\@_vline_i_complete:nn ..... 2714, 4436
\@_vline_ii:nnnn ... 4352, 4363, 4396, 4437
\l @_vlines_clist ..... 351, 584, 596, 601, 631, 1607, 1613, 1644, 1656, 1911, 1918, 2062, 2069, 2450, 2718, 4451, 4452
\l @_vpos_of_block_t1 ..... 342, 343, 5086, 5088, 5170, 5180, 5258, 5275, 5318, 5320
\@_w: ..... 1599, 1681, 1981
\g @_width_first_col_dim ..... 318, 1435, 1512, 2342, 2510, 2511
\g @_width_last_col_dim ..... 317, 1434, 1571, 2459, 2555, 2556
\@_write_aux_for_cell_nodes: .. 2755, 2817
\l @_x_final_dim ..... 312, 3079, 3128, 3137, 3138, 3141, 3144, 3145, 3296, 3312, 3320, 3324, 3328, 3330, 3332, 3335, 3337, 3362, 3380, 3388, 3428, 3436, 3472, 3489, 3499, 3533, 3585, 3599, 3601, 3619, 3621, 3957, 4791, 4805, 4832, 6078, 6088, 6089, 6099, 6190, 6215, 6223
\l @_x_initial_dim ..... 310, 3074, 3106, 3115, 3116, 3119, 3122, 3123, 3296, 3311, 3312, 3319, 3324, 3328, 3330, 3332, 3335, 3337, 3362, 3380, 3388, 3428, 3436, 3472, 3489, 3499, 3533, 3585, 3599, 3601, 3619, 3621, 3957, 4791, 4805, 4832, 6078, 6088, 6089, 6099, 6190, 6215, 6223
\l @_xdots_color_t1 517, 531, 3162, 3201, 3282, 3283, 3351, 3403, 3455, 3827, 3902, 3919
\l @_xdots_down_t1 ... 535, 3462, 3483, 3518
\l @_xdots_line_style_t1 ..... 492, 494, 527, 3447, 3455, 4808, 4838
\l @_xdots_shorten_dim ..... 488, 489, 533, 2702, 3469, 3470, 3559, 3570, 3578
\l @_xdots_up_t1 ... 536, 3461, 3482, 3508
\l @_y_final_dim ..... 313, 3080, 3180, 3184, 3222, 3226,

```

\texttt{\textbackslash 3228}, \texttt{\textbackslash 3253}, \texttt{\textbackslash 3263}, \texttt{\textbackslash 3264}, \texttt{\textbackslash 3382}, \texttt{\textbackslash 3385}, \texttt{\textbackslash 3430},	3228, 3253, 3263, 3264, 3382, 3385, 3430,
\texttt{\textbackslash 3433}, \texttt{\textbackslash 3475}, \texttt{\textbackslash 3490}, \texttt{\textbackslash 3498}, \texttt{\textbackslash 3535}, \texttt{\textbackslash 3590}, \texttt{\textbackslash 3609},	3433, 3475, 3490, 3498, 3535, 3590, 3609,
\texttt{\textbackslash 3961}, \texttt{\textbackslash 4789}, \texttt{\textbackslash 4837}, \texttt{\textbackslash 5925}, \texttt{\textbackslash 5947}, \texttt{\textbackslash 5962}, \texttt{\textbackslash 6116},	3961, 4789, 4837, 5925, 5947, 5962, 6116,
\texttt{\textbackslash 6131}, \texttt{\textbackslash 6132}, \texttt{\textbackslash 6137}, \texttt{\textbackslash 6155}, \texttt{\textbackslash 6172}, \texttt{\textbackslash 6216}, \texttt{\textbackslash 6224}, \texttt{\textbackslash 6234}	6131, 6132, 6137, 6155, 6172, 6216, 6224, 6234
\texttt{\textbackslash l_@@_y_initial_dim}	311, 3075, 3173, 3183, 3221,
.	3222, 3226, 3228, 3235, 3245, 3246, 3382,
.	3387, 3430, 3435, 3472, 3489, 3498, 3535,
.	3590, 3607, 3609, 3619, 3622, 3958, 4787,
.	4788, 4789, 4835, 5923, 5947, 5962, 6113,
.	6124, 6125, 6137, 6154, 6171, 6215, 6224, 6234
\texttt{\textbackslash \}}	2288, 2310, 5788, 5794,
.	5800, 6339, 6340, 6360, 6390, 6399, 6427,
.	6487, 6492, 6497, 6502, 6507, 6545, 6550,
.	6556, 6563, 6570, 6576, 6577, 6592, 6600,
.	6606, 6612, 6613, 6624, 6636, 6643, 6649,
.	6656, 6663, 6672, 6678, 6685, 6692, 6698,
.	6704, 6716, 6720, 6725, 6731, 6740, 6741,
.	6755, 6756, 6772, 6776, 6777, 6795, 6796,
.	6838, 6839, 6890, 6891, 6941, 6942, 6995, 6996
\texttt{\textbackslash \{}}	297, 1686, 1840,
.	1865, 2592, 5817, 6195, 6605, 6685, 6838, 6941
\texttt{\textbackslash \}}	297, 1689, 1840,
.	1850, 2592, 5817, 6204, 6605, 6685, 6838, 6941
\texttt{\textbackslash \ }}	2594, 5816
\texttt{\textbackslash \u}}	6426, 6454, 6459, 6466, 6474, 6475, 6486,
.	6487, 6544, 6569, 6570, 6583, 6589, 6593,
.	6596, 6599, 6611, 6617, 6629, 6667, 6668,
.	6669, 6677, 6683, 6690, 6703, 6710, 6711, 6719
A	
\texttt{\textbackslash A}	6015
\texttt{\textbackslash aboverulesep}	2171
\texttt{\textbackslash addtocounter}	423
\texttt{\textbackslash alph}	369
\texttt{\textbackslash anchor}	2814, 2815
\texttt{\textbackslash arraybackslash}	1777, 2019
\texttt{\textbackslash arraycolor}	1356, 6426
\texttt{\textbackslash arraycolsep}	614, 616, 618,
.	1081, 1175, 1295, 1296, 1549, 1553, 4794, 4801
\texttt{\textbackslash arrayrulecolor}	107
\texttt{\textbackslash arrayrulewidth}	140, 145, 157, 544,
.	914, 1098, 1100, 1106, 1137, 1610, 1616,
.	1704, 1754, 1914, 1921, 2065, 2072, 2188,
.	2227, 2354, 2356, 2362, 2372, 2374, 2380,
.	2403, 2405, 2411, 2429, 2431, 2437, 4212,
.	4213, 4215, 4231, 4233, 4412, 4413, 4415,
.	4426, 4432, 4545, 4556, 4562, 4598, 4873,
.	5584, 5639, 5664, 5666, 5678, 5947, 6138, 6142
\texttt{\textbackslash arraystretch}	1174, 3236, 3254, 5162, 5251, 5267, 6114, 6117
\texttt{\textbackslash AtBeginDocument}	23, 28, 85, 101,
.	177, 183, 227, 373, 487, 489, 491, 503, 694,
.	710, 2782, 3626, 3756, 3833, 3911, 3944, 4772
\texttt{\textbackslash AutoNiceMatrix}	5818
\texttt{\textbackslash AutoNiceMatrixWithDelims}	5770, 5810, 5822
B	
\texttt{\textbackslash baselineskip}	110, 117
\texttt{\textbackslash begin{group}}	1935
\texttt{\textbackslash bgroup}	1429
\texttt{\textbackslash bigskip}	1478, 2862
C	
\texttt{\textbackslash Block}	1230, 6642, 6690, 6731
\texttt{\textbackslash BNiceMatrix}	5756
\texttt{\textbackslash bNiceMatrix}	5753
\texttt{\textbackslash Body}	1312
bool commands:	
\texttt{\textbackslash bool_do_until:Nn}	2904, 2972
\texttt{\textbackslash bool_gset_false:N}	952,
.	998, 999, 1120, 1246, 1364, 1436, 1460,
.	1606, 2521, 2568, 4614, 4625, 4636, 4647, 5194
\texttt{\textbackslash bool_gset_true:N}	
.	1463, 1764, 2347, 2485, 2530, 2621, 3644,
.	3660, 3676, 3700, 3723, 3734, 3908, 4335, 4468
\texttt{\textbackslash bool_if:NTF}	
.	168, 696, 701, 712, 717, 883, 886, 979,
.	1094, 1121, 1168, 1172, 1177, 1237, 1238,
.	1264, 1269, 1283, 1289, 1341, 1343, 1366,
.	1369, 1371, 1391, 1428, 1443, 1453, 1491,
.	1569, 1574, 1592, 1597, 1624, 1636, 1804,
.	1820, 1849, 2045, 2167, 2333, 2350, 2368,
.	2386, 2399, 2425, 2455, 2460, 2489, 2507,
.	2535, 2552, 2642, 2644, 2646, 2683, 2698,
.	2720, 2737, 2740, 2755, 3225, 3227, 3374,
.	3422, 3642, 3658, 3674, 3698, 3721, 4098,
.	4121, 4693, 4711, 4729, 4856, 4866, 4888,
.	5165, 5189, 5254, 5270, 5376, 5422, 5439,
.	5483, 5509, 5546, 5829, 6402, 6412, 6445, 6591
\texttt{\textbackslash bool_if:nTF}	185, 375, 402, 1057, 1501,
.	3058, 3933, 4175, 4442, 4446, 4572, 4576,
.	4882, 5536, 5926, 5936, 5938, 5951, 5957, 5966
\texttt{\textbackslash bool_lazy_all:nTF}	
.	1640, 1652, 2446, 2707, 4607, 4618, 4629, 4640
\texttt{\textbackslash bool_lazy_and:nnTF}	
.	230, 1708, 2389, 2490, 3214,
.	3481, 3740, 4186, 4406, 4538, 5602, 6164, 6181
\texttt{\textbackslash bool_lazy_or:nnTF}	
.	524, 991, 1049, 1632, 2117, 2138, 2216,
.	2538, 3291, 3539, 4167, 4199, 4203, 4253,
.	4257, 4685, 4703, 4721, 5106, 5111, 5131, 6067
\texttt{\textbackslash bool_lazy_or_p:nn}	2493
\texttt{\textbackslash bool_not_p:n}	
.	1643, 1645, 1655, 1657, 2391, 2449, 2451
\texttt{\textbackslash bool_set:Nn}	3295, 4115
\texttt{\textbackslash c_false_bool}	
.	1860, 1868, 1881, 1887, 1893, 3638, 3654, 3670
\texttt{\textbackslash g_tmpa_bool}	
.	4335, 4344, 4378, 4386, 4391, 4468,
.	4476, 4510, 4518, 4523, 4614, 4625, 4636, 4647
\texttt{\textbackslash g_tmpb_bool}	1606, 1636, 1764
\texttt{\textbackslash l_tmpb_bool}	4690, 4704, 4722, 4744, 4757
\texttt{\textbackslash c_true_bool}	1839
box commands:	
\texttt{\textbackslash box_clear_new:N}	1170, 1288
\texttt{\textbackslash box_dp:N}	908,
.	928, 965, 984, 1039, 1198, 1207, 1279,
.	1782, 2024, 2086, 2246, 2259, 3254, 5224, 6117
\texttt{\textbackslash box_gclear_new:N}	5153
\texttt{\textbackslash box_grotate:Nn}	5191
\texttt{\textbackslash box_ht:N}	909, 930, 936, 948,
.	971, 982, 1031, 1200, 1202, 1205, 1277,
.	1778, 2020, 2085, 2246, 2259, 3236, 5215, 6114
\texttt{\textbackslash box_move_down:nn}	1039
\texttt{\textbackslash box_move_up:nn}	
.	76, 78, 80, 1031, 2129, 2194, 2233

\box_rotate:Nn	942
\box_set_dp:Nn	964, 983, 2086
\box_set_ht:Nn	970, 981, 2085
\box_set_wd:Nn	958
\box_use:N	426, 949, 1038
\box_use_drop:N	989, 995, 1014, 1806, 2047, 2088, 2129, 2130, 2135, 2516, 5234, 5531, 5568
\box_wd:N	427, 959, 986, 993, 1052, 1300, 1302, 2134, 2253, 2265, 2511, 2514, 2556, 2560, 5203, 5836
\l_tmpa_box	409, 426, 427, 1299, 1300, 1301, 1302, 1536, 2085, 2086, 2088, 2129, 2130, 2246, 2259
\l_tmpb_box	2239, 2253, 2254, 2265
C	
\c	59, 1628
\Cdots	1220, 3649, 3652
\cdots	1153, 1212
\cellcolor	1162, 1351, 4273
\chessboardcolors	1358
\cline	160, 1217, 1218
clist commands:	
\clist_clear:N	4246
\clist_if_empty:N _{TF}	4342, 4475, 5386
\clist_if_empty_p:N	2450
\clist_if_in:N _{N_{TF}}	1129, 1613, 1918, 2069, 4452, 4582, 5699, 5701, 5703, 5705, 5724
\clist_if_in:nN _{TF}	5685
\clist_map_inline:Nn	4193, 4216, 4247, 4652, 5683, 6162, 6179
\clist_map_inline:nn	2609, 4057, 4106
\clist_new:N	335, 350, 351, 352, 353, 501
\clist_put_right:Nn	4264
\clist_set:Nn	596, 597, 601, 602, 630, 631, 632
\clist_set_eq:N _N	4245
\l_tmpa_clist	4245, 4247
\CodeAfter	878, 1234, 2291, 2294, 2484, 2529, 2735, 6743
\CodeBefore	1425, 6426
\color	111, 118, 172, 174, 1540, 1558, 3156, 3159, 3162, 3195, 3198, 3201, 3276, 3279, 3283, 3351, 3403, 3821, 3824, 3827, 3896, 3899, 3902, 3919, 3983, 4134, 4135, 4146, 4147, 5160, 5295, 5956, 6296, 6320
\colorlet	289, 290, 893, 900, 2499, 2543
\columnncolor	1164, 1357, 2746, 4296
\cr	144, 162, 2478
\crcr	2327
cs commands:	
\cs_generate_variant:Nn	58, 164, 3478, 3976, 4878, 4879
\cs_gset:N _p	111, 118, 4871
\cs_gset_eq:N _N	69, 247, 1191, 1445, 2758
\cs_if_exist:N _{TF}	57, 188, 1257, 1259, 1406, 1446, 1449, 2804, 2805, 2826, 2939, 2952, 3007, 3020, 3109, 3131, 3239, 3257, 3789, 3807, 3864, 3882, 4858, 4911, 5444, 5462, 5931, 6084, 6091, 6120, 6127
\cs_if_exist_p:N	232, 525, 4687, 4706, 4724
\cs_if_free:N _{TF}	65, 3151, 3190, 3271, 3346, 3398
\cs_if_free_p:N	3935, 3937
\cs_new_protected:N _p	2784, 3946, 4774
\cs_set:Nn	682, 685, 688
\cs_set:N _p	107, 108, 114, 115, 120, 132, 133, 147, 149, 150, 172, 174, 372, 1145, 1936, 1958, 2898, 2960, 3028, 3831, 3906, 4586, 4587, 4593, 4594, 5162, 5251, 5267
\cs_set_nopar:N _p	1071, 1083, 1174, 1185, 5053, 5054
\cs_set_nopar:N _p x	1084
\cs_set_protected:N _p	5807
\cs_set_protected_nopar:N _p	5141, 5409
D	
\Ddots	1222, 3682, 3683, 3688, 3689
\ddots	1155, 1214
\diagbox	1235, 5141, 5409
dim commands:	
\dim_add:Nn	5022
\dim_compare:nN _n _{TF}	110, 117, 956, 962, 968, 1661, 2387, 2560, 3119, 3141, 3330, 4935, 4945, 5454, 5474, 5836
\dim_gzero:N	960, 966, 972
\dim_max:nn	4924, 4928
\dim_min:nn	4916, 4920
\dim_ratio:nn	3389, 3437, 3553, 3558, 3569, 3577, 3586, 3591, 3602, 3610
\dim_set:Nn	4897, 4904, 4915, 4919, 4923, 4927, 4939, 4940, 4949, 4950, 4994, 5007
\dim_set_eq:N _N	4895, 4902, 5002, 5016
\dim_sub:Nn	5019
\dim_use:N	4936, 4946, 4997, 4998, 5010, 5011, 5034, 5035, 5036, 5037, 5061, 5062, 5063, 5064
\dim_zero_new:N	4894, 4896, 4901, 4903
\c_max_dim	3106, 3119, 3128, 3141, 4895, 4897, 4902, 4904, 4936, 4946, 5441, 5454, 5459, 5474, 5927, 5928, 6078, 6079, 6099, 6102
\dotfill	1233, 5825
\dots	1157
\doublerulesep	1755, 4415, 4427, 4545, 4557, 4599
\doublerulesepcolor	114
\draw	3466
E	
\egroup	1584
\else	1936
else commands:	
\else	283
\endarray	2279, 2307
\endBNiceMatrix	5757
\endbNiceMatrix	5754
\endgroup	1944
\endNiceArray	2629, 2638
\endNiceArrayWithDelims	2578, 2588
\endpgfscope	2840, 2853, 3523, 5882
\endpNiceMatrix	5745
\endsavenotes	1592
\endtabularnotes	2162
\endVNiceMatrix	5751
\endvNiceMatrix	5748
\enskip	1830, 1858, 1866, 1879, 1885
\ensuremath	3643, 3659, 3675, 3699, 3722
\everycr	143, 162, 1195

exp commands:	
\exp_after:wN	140, 157
194, 214, 1477, 1541, 1559, 1621, 1941, 6144	
\exp_args:NNc	4860
\exp_args:Nne	2616
\exp_args:NNV	2299,
3630, 3646, 3662, 3678, 3702, 3760, 3837, 3915	
\exp_args:NNx	1128, 1917, 2068
\exp_args:No	3454
\exp_args:NV 1601, 1942, 2275, 2302, 2304, 5593	
\exp_args:Nxx	5134, 5135
\exp_last_unbraced:NV	1367, 2738, 5398
\exp_not:N	
.. 42, 43, 46, 47, 1704, 1748, 2650, 2665,	
2674, 2677, 2749, 4284, 4296, 4671, 4776,	
4777, 5170, 5180, 5258, 5275, 5401, 5780, 6249	
\exp_not:n	
.... 1063, 1589, 2750, 3770, 3771, 3847,	
4273, 4284, 4286, 4297, 5150, 5232, 5244,	
5245, 5369, 5381, 5391, 5403, 5418, 5846, 5847	
\ExplSyntaxOff	67, 1591, 4875
\ExplSyntaxOn	64, 1585, 4868
\extrarrowheight	3236, 5163, 5252, 5268, 6114
F	
\fi	122, 1603, 1936, 1939, 4586, 4603
fi commands:	
\fi:	285
\five	2809, 2814
flag commands:	
\flag_clear_new:n	6242
\flag_height:n	6267
\flag_raise:n	6266
\fontdimen	2125
fp commands:	
\fp_eval:n	3494
\fp_to_dim:n	3529
\futurelet	127
G	
\globaldefs	1580, 5347
group commands:	
\group_insert_after:N 5830, 5831, 5833, 5834	
H	
\halign	1209
\hbox	1092, 1545, 2194,
2233, 2352, 2370, 2397, 2401, 2427, 2835, 2848	
hbox commands:	
\hbox:n	76, 78, 81
\hbox_gset:Nn	5155
\hbox_overlap_left:n .	1032, 1040, 2331, 2512
\hbox_overlap_right:n .	426, 2457, 2558
\hbox_set:Nn	
409, 1029, 1299, 1301, 1536, 2239, 2254, 5421	
\hbox_set:Nw 882, 1304, 1795, 2036, 2487, 2533	
\hbox_set_end:	
.... 978, 1488, 1803, 2044, 2506, 2551	
\hbox_to_wd:nn	451, 476
\Hdotsfor	1227, 6454, 6629
\vdotsfor	1158
\hdottedline	1224
\heavyrulewidth	2172
\hfil	1682, 1982
\hfill	140, 157
\Hline	1225, 4589
\hline	120
\hrule 124, 140, 157, 1137, 2172, 5961, 6301, 6325	
\hskip	123
\Hspace	1226
\hspace	3735
\hss	1682, 1982
I	
\ialign	1089, 1185, 1208, 5326
\Iddots	1223, 3706, 3707, 3712, 3713
\iddots	71, 1156, 1215
if commands:	
\if_mode_math:	283
\IfBooleanTF	1479
\ifnum	122, 4586, 4603
\ifandalone	1449
\ignorespaces	1965
int commands:	
\int_case:nnTF	3680, 3686, 3704, 3710
\int_compare:nNnTF	135, 136, 152,
880, 881, 890, 897, 933, 943, 1134, 1136,	
1261, 1267, 1272, 1489, 1493, 1504, 1508,	
1509, 1576, 1945, 1963, 2150, 2189, 2228,	
2300, 2328, 2536, 2914, 2921, 2925, 2927,	
2982, 2989, 2993, 2995, 3158, 3197, 3278,	
3313, 3315, 3823, 3898, 4162, 4207, 4225,	
4261, 4292, 4309, 4310, 4317, 4318, 4322,	
4750, 4752, 4754, 4756, 5159, 5196, 5208,	
5502, 5534, 5538, 5611, 5613, 5784, 5786,	
5788, 5792, 5794, 5796, 5798, 5800, 6148, 6150	
\int_compare_p:n	
3060, 3061, 3062, 3063, 4177, 4179, 5603, 5604	
\int_do_until:nNn	4118
\int_gadd:Nn	1962
\int_gincr:N	879, 906, 1452, 1728, 1787,
1809, 1815, 2423, 2531, 3376, 3424, 4853, 5140	
\int_if_even:nTF	4066, 6267
\int_if_odd_p:n	4115
\int_incr:N	405, 1738
\int_min:nn	
2872, 2874, 2876, 2878, 2886, 2888, 3068, 3069	
\int_step_inline:nn	
.... 2870, 4062, 4064, 6161, 6178	
\int_step_inline:nnnn	4682, 4700, 4715, 4718
\c_zero_int	1821, 3969, 4168
iow commands:	
\iow_newline:	
.... 1589, 2659, 2667, 2676, 2679, 2751, 4673	
\iow_now:Nn	62, 88, 1585, 1586, 1591
\iow_shipout:Nn	4868, 4869, 4875
\item	2155, 2161
K	
\kern	81
keys commands:	
\keys_define:nn	520, 540, 547, 625, 672,
724, 731, 775, 817, 831, 848, 861, 1374,	
3726, 4073, 4082, 4842, 5072, 5287, 5628,	
5734, 5764, 5888, 5893, 5973, 5994, 6003, 6363	
\l_keys_key_str	
.... 6339, 6528, 6534, 6622, 6725,	
6730, 6740, 6755, 6776, 6794, 6837, 6889, 6940	

\keys_set:nn	199, 550, 552, 566, 806, 809, 816, 1378, 1386, 1473, 1474, 2615, 2625, 2634, 2761, 3161, 3200, 3281, 3350, 3402, 3826, 3901, 3918, 4077, 4096, 4855, 5363, 5895, 5899, 6026, 6073	\null	1961
\keys_set_known:nn	3692, 3716, 5123, 5585, 5640, 5679	\nulldelimiterspace	2253, 2265, 5942, 6140
\keys_set_known:nnN	5777	\nullfont	5953, 5960, 6293, 6300, 6317, 6324
\l_keys_value_t1	6575, 6651, 6658, 6990	\numexpr	165, 166
L			
\Ldots	1219, 3633, 3636	O	
\ldots	1152, 1211	\omit	135, 2330, 2346, 2422, 5903
\leaders	140, 157	\OnlyMainNiceMatrix	1232, 4301
\left	1541, 2242, 2257, 5957, 6297, 6321	P	
legacy commands:		\par	2149, 2157
\legacy_if:nTF	656	peek commands:	
\line	2732, 6605, 6751	\peek_meaning:NTF	170, 407, 1146
M		\peek_meaning_ignore_spaces:NTF	2274, 4589
\makebox	1806, 2047	\peek_meaning_remove_ignore_spaces:NTF	160
\mathinner	73	\peek_remove_spaces:n	
mode commands:	 4269, 4280, 5095, 6035, 6051	
\mode_leave_vertical:	1441, 1776, 2018	\pgfdeclareshape	2807
msg commands:		\pgfextracty	5505
\msg_error:nn	12	\pgfgetlastxy	469
\msg_error:nnn	13	\pgfpathcircle	3618
\msg_error:nnnn	14, 5344, 5351, 5355	\pgfpathlineto	4423, 4429, 4553, 4559, 5660, 5671, 5718, 5731, 5871, 6155, 6172, 6206
\msg_fatal:nn	15	\pgfpathmoveto	4422, 4428, 4552, 4558, 5659, 5670, 5717, 5730, 5866, 6154, 6171, 6197
\msg_fatal:nnn	16	\pgfpathrectanglecorners	4235, 4416, 4546, 5619
\msg_new:nnn	17	\pgfpointadd	467
\msg_new:nnnn	18	\pgfpointanchor	175, 263, 2830, 2843, 3084, 3095, 3112, 3134, 3242, 3260, 4914, 4922, 5449, 5467, 5487, 5489, 5506, 5543, 5934, 6087, 6094, 6123, 6130, 6241, 6245
\msg_redirect_name:nnn	20	\pgfpointdiff	468, 1332, 1338, 1403, 1417, 1418
\multicolumn	1229, 3737, 3746, 3752, 3774	\pgfpointlineattime	3488
\multispan	136, 137, 153, 154, 1934	\pgfpointorigin	2337, 2468, 2815
\myfiledate	6	\pgfpointscale	467
\myfileversion	7	\pgfpointshapeborder	3956, 3959
N			
\newcolumntype	254, 255, 256	\pgfrememberpicturepositiononpagetrue	
\newcounter	365 911, 1005, 1104, 2336, 2360, 2378, 2409, 2435, 2466, 2793, 2820, 2869, 3445, 3955, 4398, 4530, 4785, 4830, 4957, 4967, 4978, 5424, 5587, 5648, 5695, 5861, 5920, 6075	
\NewDocumentCommand		\pgfscope	2828, 2841, 3485, 5878
... 377, 400, 815, 1384, 2760, 3630, 3646, 3662, 3678, 3702, 3760, 3837, 3915, 3995, 4010, 4025, 4034, 4055, 4060, 4075, 4091, 4267, 4278, 4290, 5573, 5770, 5818, 6033, 6049	\pgfset	436, 461, 1006, 5520, 5557, 5877, 5941, 6077	
\NewDocumentEnvironment	1424, 2272, 2281, 2571, 2581, 2611, 2622, 2630, 4851	\pgfsetbaseline	1004
\NewExpandableDocumentCommand	260, 5093	\pgfsetcornersarced	4234, 5595
\newlist	381, 392	\pgfsetlinewidth	
\NiceArray	2627, 2636 4432, 4562, 5622, 5651, 5698, 6142	
\NiceArrayWithDelims	2576, 2586	\pgfsetrectcap	4433, 4563
nicematrix commands:		\pgfsetroundcap	5874
\g_nicematrix_code_after_t1	299, 665, 2296, 2738, 2741, 5366, 5378, 5388, 5906, 5913	\pgfsetstrokecolor	5593
\g_nicematrix_code_before_t1	1253, 2743, 2750, 4271, 4282, 4294, 5399	\pgfsyspdfmark	65, 66
\NiceMatrixLastEnv	260	\pgftransformrotate	3492
\NiceMatrixOptions	815, 6795, 6995	\pgftransformshift	442, 467, 2829, 2842, 2880, 3486, 5519, 5541, 5879, 5883, 5943, 6220, 6230
\NiceMatrixoptions	6655	\pgfusepath	
\noalign	110, 117, 122, 145, 1116, 1191, 4586, 4764 3512, 3522, 3986, 4138, 4150, 4419, 5623	
\nobreak	395	\pgfusepathqfill	3624, 4549
\normalbaselines	1171	\pgfusepathqstroke	4434, 4564, 5661, 5672, 5719, 5732, 5875, 6156, 6173, 6207
\NotEmpty	1236	\phantom	3643, 3659, 3675, 3699, 3722
prg commands:		\pNiceMatrix	5744
\prg_do_nothing:		\prg_do_nothing:	
..... 69, 186, 229, 238, 247, 537, 1191, 2735			

\prg_new_if:NNNN	4165, 4173
\prg_replicate:nn	415, 2418, 2419, 3774, 4424, 4554, 5787, 5790, 5793, 5799
\prg_return_false:	4170, 4182
\prg_return_true:	4171, 4181
\ProcessKeysOptions	6383
\ProvideDocumentCommand	71
\ProvidesExplPackage	4
Q	
\quad	396
quark commands:	
\q_stop	132, 133, 149, 150, 171, 173, 1367, 1389, 1477, 1621, 1693, 1763, 1853, 1875, 1941, 1987, 2291, 2294, 3909, 3923, 3924, 3990, 4045, 4050, 4110, 4197, 4198, 4220, 4221, 4251, 4252, 5051, 5058, 5098, 5099, 5103, 5398, 5578, 5601, 5610, 5641, 5644, 5688, 5691, 5759, 5774, 6037, 6042, 6061, 6064, 6144, 6252, 6260
R	
\rectanglecolor	1352, 2745, 4284
\refstepcounter	424
regex commands:	
\regex_const:Nn	59
\regex_match:nnTF	6015
\regex_replace_all:NnN	1626
\relax	165, 166
\renewcommand	192, 212
\RenewDocumentEnvironment	5743, 5746, 5749, 5752, 5755
\RequirePackage	1, 3, 9, 10, 11
\right	1559, 2249, 2261, 5966, 6305, 6329
\rotate	1231
\roundedrectanglecolor	1353, 5401
\rowcolor	1163, 1354
\rowcolors	1355
S	
\savedanchor	2809
\savenotes	1428
scan commands:	
\scan_stop:	2739
\scriptstyle	886, 2489, 2535, 3473, 3474, 3508, 3518
seq commands:	
\seq_clear:N	1619
\seq_clear_new:N	4651
\seq_count:N	2301, 3972
\seq_gclear:N	1239, 1240, 1282, 1284, 1455, 1456, 1457, 1458, 2177, 2736
\seq_gclear_new:N	1285, 1286, 1363, 2297, 2313
\seq_gpop_left:NN	2303, 2315
\seq_gput_left:Nn	661, 1947, 1949, 5361
\seq_gput_right:Nn	406, 1701, 1950, 3039, 3971, 5229, 5241, 5373, 5849, 6021, 6043
\seq_gset_from_clist:Nn	2650, 2665, 2674, 2677
\seq_gset_map_x>NNn	2764
\seq_gset_split:Nnn	2299, 2314
\seq_if_empty:NTF	2137, 2661, 2670, 4667
\seq_if_empty_p:N	2709, 2710, 2711, 4187
\seq_if_in:NnTF	659, 4227, 4375, 4381, 4388, 4507, 4513, 4520, 4917, 4925, 5447, 5465, 6017, 6440
\seq_item:Nn	1265, 1270, 1320, 1321, 1322, 1323
\seq_map_function:NN	2305
\seq_map_indexed_inline:Nn	3967, 3981
\seq_map_inline:Nn	2155, 2161, 2317, 3053, 4125, 4336, 4338, 4340, 4469, 4471, 4473, 4745, 5327, 6146
\seq_mapthread_function:NNN	5046
\seq_new:N	273, 288, 319, 320, 321, 322, 323, 324, 325, 326, 331, 366, 6430
\seq_put_right:Nn	4732
\seq_set_eq:NN	4100
\seq_set_filter:NNn	4101, 4123
\seq_set_from_clist:Nn	4671, 6431
\seq_set_map_x>NNn	6436
\seq_use:Nnnn	2666, 2675, 2678, 4672, 6618, 7000
\l_tmpa_seq	4101, 4123
\l_tmpb_seq	4100, 4101, 4123, 4125
\setlist	382, 393, 697, 702, 713, 718
siunitx commands:	
\siunitx_cell_begin:w	188, 200, 232
\siunitx_cell_end:	203
skip commands:	
\skip_gadd:Nn	2394
\skip_gset:Nn	2385
\skip_gset_eq:NN	2392, 2393
\skip_horizontal:N	141, 158, 1305, 1306, 1486, 1487, 1511, 1512, 1548, 1549, 1552, 1553, 1571, 1572, 1610, 1616, 1704, 1901, 1914, 1921, 2065, 2072, 2266, 2267, 2269, 2270, 2341, 2342, 2354, 2356, 2372, 2374, 2396, 2403, 2405, 2424, 2429, 2431, 2459, 2517, 2518, 2519, 2522, 2557, 2562, 2563, 2564
\skip_horizontal:n	427, 1052, 1750, 2454
\skip_vertical:N	145, 1098, 1100, 1544, 1555, 2146, 2171, 4764
\skip_vertical:n	948, 4596
\g_tmpa_skip	2385, 2392, 2393, 2394, 2396, 2424
\c_zero_skip	1196
\space	296, 297
\stepcounter	413, 418
str commands:	
\c_backslash_str	296
\c_colon_str	814
\str_case:nn	5512, 5524, 5549, 5561, 6191, 6200
\str_case:nnTF	1516, 1669, 1969, 2111, 4654, 6264, 6277
\str_clear_new:N	6072
\str_gclear:N	2756
\str_gset:Nn	1438, 2575, 2584, 2613, 2624, 2632, 5809
\str_if_empty:NTF	915, 1017, 1107, 1437, 2338, 2363, 2381, 2412, 2438, 2469, 2574, 2583, 5038, 5065, 6212, 6226, 6236
\str_if_eq:nnTF	96, 295, 1087, 1696, 1699, 1743, 1763, 1823, 1855, 1877, 1908, 2059, 2286, 2288, 2321, 5591, 5911
\str_if_eq_p:nn	526, 1633, 1634, 1709, 4201, 4205, 4255, 4259, 5108, 5113
\str_if_in:NnTF	2099, 2203

\str_new:N	291, 507, 813
\str_range:Nnn	2103, 2207
\str_set:Nn	658, 802, 6020
\str_set_eq:NN	662, 814
\l_tmpa_str	658, 659, 661, 662
\strut	2155, 2161
\strutbox	3236, 3254, 6114, 6117
\SubMatrix	1359, 2719, 6046, 6544, 6576, 6583, 6589, 6593, 6611, 6758
sys commands:	
\sys_if_engine_xetex_p:	1049
\sys_if_output_dvi_p:	1049
T	
\tabcolsep	1080, 1548, 1552
\tabskip	1196
\tabularnote	377, 400, 407, 6683, 6703
\tabularnotes	2160
TeX and L ^A T _E X 2 _{&} commands:	
\@BTnormal	1169
\@acol	1070
\@acoll	1068
\@acolr	1069
\@addamp	1936
\@addtopreamble	1943
\@array@array	1072
\@arrayacol	1068, 1069, 1070
\@arstrut	1959
\@arstrutbox	908, 909, 948, 1198, 1200, 1202, 1205, 1207, 1778, 1782, 2020, 2024
\@currenvir	5911
\@depth	5963, 6302, 6326
\@empty	1943
\@firststampfalse	1936
\@gobblethree	66
\@halignto	1071, 1083, 1084
\@height	125, 140, 157, 5961, 6301, 6325
\@ifclassloaded	51, 54, 6404, 6414
\@ifnextchar	1244
\@ifpackageloaded	30, 33, 36, 39, 87, 103, 179, 6407, 6417
\@mainaux	62, 88, 1585, 1586, 1591, 4868, 4869, 4875
\@mkpream	1942
\@preamble	1960
\@preamerr	1936
\@sharp	1958
\@tabarray	1085
\@tempswafalse	1603, 1939
\@tempswatrue	1602, 1938
\@temptokena	194, 196, 214, 216, 237, 240, 1601, 1621, 1937, 1941
\@whilesw	1603, 1939
\@width	125, 5964, 6303, 6327
\@xhline	128
\bBigg@	1299, 1301
\c@MaxMatrixCols	2603, 6468
\c@tabularnote	2139, 2150, 2178
\col@sep	1080, 1081, 1511, 1572, 2341, 2394, 2454, 2522, 2557, 3123, 3145
\CT@arc	107, 108
\CT@arc@	106, 111, 126, 139, 156, 172, 174, 1445, 2172, 2758, 4431, 4561, 4829, 5592, 5650, 5697, 5873, 6145
\CT@drs	114, 115
\CT@drsc@	113, 118, 4408, 4411, 4540, 4543
\CT@everycr	1189
\CT@row@color	1191
\if@firstamp	1936
\if@tempswa	1603, 1939
\NC@	1145
\NC@find	205, 221, 238
\NC@list	1603, 1939
\NC@rewrite@S	192, 212, 239
\new@ifnextchar	1244
\newcol@	1147, 1148
\nicematrix@redefine@check@rerun	88, 91
\pgf@relevantforpicturesizefalse	
.....	1327, 2794, 2821, 3446, 3615, 3980, 4105, 4399, 4531, 4958, 4968, 4979, 5425, 5588, 5649, 5696, 5860, 5921, 6076
\pgfsys@getposition	
.....	1325, 1330, 1336, 1401, 1409, 1412
\pgfsys@markposition	
.....	1034, 1042, 1099, 1181, 1324, 2334, 2355, 2373, 2404, 2430, 2462, 2836, 2849
\pgfutil@check@rerun	93, 94
\reserved@a	127
\rvtx@ifformat@geq	57
\set@color	5159, 5421
\tikz@library@external@loaded	1446
tex commands:	
\tex_mkern:D	75, 77, 79, 82
\tex_the:D	196, 216
\textfont	2125
\textit	369
\textsuperscript	370, 371
\the	165, 166, 1603, 1621, 1939, 1941
\thetabularnote	372
\tikzexternaldisabled	1448
\tikzset	1345, 1450, 2722
tl commands:	
\tl_clear:N	4357, 4368, 4489, 4500, 5583
\tl_clear_new:N	4046, 4047, 4094, 4332, 4465, 6038, 6039, 6057, 6058, 6059, 6060
\tl_const:Nn	
.....	42, 43, 46, 47, 493, 2480, 2525, 6253
\tl_count:n	2106, 2210
\tl_gclear:N	1466, 1605, 1940, 2734, 2741, 3985
\tl_gclear_new:N	
.....	1247, 1248, 1249, 1250, 1251, 1252, 1253, 1459
\tl_gput_left:Nn	1057, 1638, 4294
\tl_gput_right:Nn	1057, 1650, 1703, 1746, 1760, 1838, 1859, 1867, 1880, 1886, 1892, 1902, 2648, 2663, 2672, 2747, 3762, 3839, 3974, 4271, 4282, 4601, 4669, 4769, 5143, 5366, 5378, 5388, 5399, 5411, 5839
\tl_gset:Nn	
...	240, 244, 246, 1430, 1431, 1432, 1588, 1609, 1615, 1825, 1826, 1856, 1882, 2749, 3972
\tl_if_blank:nTF	3997, 4000, 4012, 4015, 4027, 4030, 4036, 4039, 4131, 4143, 5097
\tl_if_blank_p:n	
...	4200, 4204, 4254, 4258, 4408, 4540, 5107, 5112
\tl_if_empty:NTF	1124, 1467, 1476, 1539, 1557, 2149, 2717, 2718, 2743, 4222, 4223,

4346, 4350, 4361, 4478, 4482, 4493, 5118, 5158, 5364, 5396, 5589, 5955, 6143, 6295, 6319	
\tl_if_empty:nTF	
..... 639, 777, 819, 835, 851, 869, 2283, 2310, 3162, 3201, 3282, 3351, 3403, 3827, 3902, 3919, 4133, 4145, 6012, 6262, 6453	
\tl_if_empty_p:N	1644, 1656, 3482, 3483
\tl_if_empty_p:n	2140
\tl_if_eq:NNTF	3447
\tl_if_eq:NnTF	1126, 1607, 1911, 2062, 2087, 2198, 4451, 4581, 4804, 4806, 6160, 6177
\tl_if_eq:nnTF	651, 793, 1853, 1875, 3968
\tl_if_exist:NTF	1461
\tl_if_in:NnTF	4109, 4196, 4219, 4250
\tl_if_in:nnTF	1840, 1850, 1865
\tl_if_single_token:nTF	589, 801
\tl_if_single_token_p:n	58
\tl_item:Nn	243, 244, 246
\tl_map_inline:nn	2284
\tl_new:N	242, 245, 268, 280, 287, 299, 300, 301, 304, 308, 333, 334, 337, 339, 342, 367, 492, 496, 515, 517, 518
\tl_put_left:Nn	1169, 1372
\tl_put_right:Nn	641, 1179, 1274, 1314, 1470
\tl_range:nnn	96
\tl_set:Nn	243, 4051, 4052, 4111, 4127, 4206, 4208, 4224, 4226, 4260, 4262, 4331, 5124, 5612, 5614, 5645, 5646, 5692, 5693
\tl_set_eq:NN	494, 4048, 4049, 4209, 4347, 4479, 4808, 4838, 5120, 5642, 5643, 5689, 5690, 6040, 6041, 6062, 6063, 6065, 6066
\tl_set_rescan:Nnn	2298, 3629, 3759, 3836, 3914
\tl_to_str:n	6437
\g_tmpa_tl	240, 243, 246
tmpc commands:	
\l_tmpc_dim	314, 2877, 2881, 4212, 4213, 4236, 4405, 4413, 4418, 4423, 4429, 4537, 4548, 4553, 4559, 5431, 5437, 5481, 5609, 5620, 5715, 5718, 5868, 5871, 5879
\l_tmpc_int	4116, 4117, 4118
\l_tmpc_tl	4046, 4048, 4051, 4209, 4228, 4332, 4346, 4347, 4350, 4355, 4357, 4361, 4366, 4368, 4465, 4478, 4479, 4482, 4487, 4489, 4493, 4498, 4500, 5642, 5654, 5667, 5689, 5706, 5712, 6038, 6040, 6044
tmpd commands:	
\l_tmpd_dim	315, 2879, 2882, 4233, 4236, 4414, 4418, 4544, 4548, 5433, 5437, 5459, 5470, 5474, 5477, 5481, 5618, 5621, 5870, 5871, 5883
\l_tmpd_t1	4047, 4049, 4052, 5643, 5656, 5665, 5690, 5702, 5723, 6039, 6041, 6044
token commands:	
\token_to_str:N	6425, 6426, 6454, 6539, 6544, 6550, 6575, 6583, 6589, 6593, 6605, 6611, 6629, 6642, 6683, 6690, 6703, 6720, 6730, 6742, 6751, 6757, 6795, 6995
U	
\unskip	2165
use commands:	
\use:N	1060, 1309, 1310, 1464, 1483, 1484, 2598, 2618, 3984
\use:n	3920, 4301, 5168, 5178, 5256, 5273, 5778, 6248
\usepackage	6409, 6419
\usepgfmodule	2
V	
vbox commands:	
\vbox:n	81
\vbox_set_top:Nn	945
\vbox_to_ht:nn	447, 474, 2245, 2258
\ vbox_to_zero:n	947
\vcenter	1542, 2243, 5958, 6298, 6322, 6720
\Vdots	1221, 3665, 3668
\vdots	1154, 1213
\Vdotsfor	1228
\vfill	450, 476
\vline	126
\VNiceMatrix	5750
\vNiceMatrix	5747
\vrule	124, 1778, 1782, 2020, 2024
\vskip	123
\vtop	1096
X	
\xglobal	893, 900, 2499, 2543
Z	
\z	6015

Contents

1 The environments of this package	2
2 The vertical space between the rows	2
3 The vertical position of the arrays	3
4 The blocks	4
4.1 General case	4
4.2 The mono-column blocks	6

4.3	The mono-row blocks	6
4.4	The mono-cell blocks	6
4.5	Horizontal position of the content of the block	7
5	The rules	7
5.1	Some differences with the classical environments	7
5.1.1	The vertical rules	7
5.1.2	The command <code>\cline</code>	8
5.2	The thickness and the color of the rules	8
5.3	The tools of nicematrix for the rules	9
5.3.1	The keys <code>hlines</code> and <code>vlines</code>	9
5.3.2	The key <code>hvlines</code>	9
5.3.3	The (empty) corners	10
5.4	The command <code>\diagbox</code>	11
5.5	Dotted rules	11
6	The color of the rows and columns	11
6.1	Use of <code>colortbl</code>	11
6.2	The tools of nicematrix in the <code>\CodeBefore</code>	12
6.3	Color tools with the syntax of <code>colortbl</code>	15
7	The width of the columns	16
8	The exterior rows and columns	17
9	The continuous dotted lines	19
9.1	The option <code>nullify-dots</code>	20
9.2	The commands <code>\Hdotsfor</code> and <code>\Vdotsfor</code>	21
9.3	How to generate the continuous dotted lines transparently	22
9.4	The labels of the dotted lines	22
9.5	Customisation of the dotted lines	22
9.6	The dotted lines and the rules	23
10	The <code>\CodeAfter</code>	24
10.1	The command <code>\line</code> in the <code>\CodeAfter</code>	24
10.2	The command <code>\SubMatrix</code> in the <code>\CodeAfter</code>	25
11	The notes in the tabulars	26
11.1	The footnotes	26
11.2	The notes of tabular	27
11.3	Customisation of the tabular notes	28
11.4	Use of <code>{NiceTabular}</code> with <code>threeparttable</code>	30
12	Other features	31
12.1	Use of the column type <code>S</code> of <code>siunitx</code>	31
12.2	Alignment option in <code>{NiceMatrix}</code>	31
12.3	The command <code>\rotate</code>	31
12.4	The option <code>small</code>	32
12.5	The counters <code>iRow</code> and <code>jCol</code>	32
12.6	The option <code>light-syntax</code>	33
12.7	Color of the delimiters	33
12.8	The environment <code>{NiceArrayWithDelims}</code>	33
13	Use of Tikz with nicematrix	34
13.1	The nodes corresponding to the contents of the cells	34
13.2	The “medium nodes” and the “large nodes”	34
13.3	The nodes which indicate the position of the rules	36
13.4	The nodes corresponding to the command <code>\SubMatrix</code>	37
14	API for the developpers	37

15	Technical remarks	38
15.1	Definition of new column types	38
15.2	Diagonal lines	38
15.3	The “empty” cells	39
15.4	The option exterior-arraycolsep	39
15.5	Incompatibilities	40
16	Examples	40
16.1	Notes in the tabulars	40
16.2	Dotted lines	41
16.3	Dotted lines which are no longer dotted	42
16.4	Stacks of matrices	43
16.5	How to highlight cells of a matrix	46
16.6	Utilisation of \SubMatrix in the \CodeBefore	48
17	Implementation	49
18	History	206
Index		213