

The etexcmds package

Heiko Oberdiek*

2016/05/16 v1.6

Abstract

New primitive commands are introduced in ε -TeX. Sometimes the names collide with existing macros. This package solves this name clashes by adding a prefix to ε -TeX's commands. For example, ε -TeX's `\unexpanded` is provided as `\etex@unexpanded`.

Contents

1	Documentation	2
1.1	<code>\unexpanded</code>	2
1.2	<code>\expanded</code>	2
2	Implementation	2
2.1	Reload check and package identification	2
2.2	Catcodes	3
2.3	Provide <code>\newif</code>	4
2.4	Load package <code>infwarerr</code>	4
2.5	<code>\unexpanded</code>	5
2.6	<code>\expanded</code>	6
3	Test	7
3.1	Catcode checks for loading	7
3.2	Macro tests	9
4	Installation	10
4.1	Download	10
4.2	Bundle installation	10
4.3	Package installation	10
4.4	Refresh file name databases	10
4.5	Some details for the interested	11
5	History	11
	[2007/05/06 v1.0]	11
	[2007/09/09 v1.1]	11
	[2007/12/12 v1.2]	11
	[2010/01/28 v1.3]	11
	[2011/01/30 v1.4]	11
	[2011/02/16 v1.5]	11
	[2016/05/16 v1.6]	12

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 Documentation

1.1 `\unexpanded`

`\etex@unexpanded`

New primitive commands are introduced in ε -TeX. Unhappily `\unexpanded` collides with a macro in ConTeXt with the same name. This also affects the LaTeX world. For example, package `m-ch-de` loads `base/syst-gen.tex` that redefines `\unexpanded`. Thus this package defines `\etex@unexpanded` to get rid of the name clash.

`\ifetex@unexpanded`

Package `etexcmds` can be loaded even if ε -TeX is not present or `\unexpanded` cannot be found. The switch `\ifetex@unexpanded` tells whether it is safe to use `\etex@unexpanded`. The switch is true (`\iftrue`) only if the primitive `\unexpanded` has been found and `\etex@unexpanded` is available.

1.2 `\expanded`

Probably `\expanded` will be added in pdfTeX 1.50 and LuaTeX. Again ConTeXt defines this as macro. Therefore version 1.2 of this packages also provides `\etex@expanded` and `\ifetex@unexpanded`.

2 Implementation

```
1 (*package)
```

2.1 Reload check and package identification

Reload check, especially if the package is not used with LaTeX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@etexcmds.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17 \def\empty{}%
18 \ifx\x\empty % LaTeX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }
```

```

25     \else
26     \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27     \fi
28     \x{etexcmds}{The package is already loaded}%
29     \aftergroup\endinput
30   \fi
31 \fi
32 \endgroup%
Package identification:
33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34   \catcode13=5 % ^~M
35   \endlinechar=13 %
36   \catcode35=6 % #
37   \catcode39=12 % '
38   \catcode40=12 % (
39   \catcode41=12 % )
40   \catcode44=12 % ,
41   \catcode45=12 % -
42   \catcode46=12 % .
43   \catcode47=12 % /
44   \catcode58=12 % :
45   \catcode64=11 % @
46   \catcode91=12 % [
47   \catcode93=12 % ]
48   \catcode123=1 % {
49   \catcode125=2 % }
50   \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51     \def\x#1#2#3[#4]{\endgroup
52       \immediate\write-1{Package: #3 #4}%
53       \xdef#1{#4}%
54     }%
55   \else
56     \def\x#1#2[#3]{\endgroup
57       #2[#{#3}]%
58       \ifx#1\@undefined
59         \xdef#1{#3}%
60       \fi
61       \ifx#1\relax
62         \xdef#1{#3}%
63       \fi
64     }%
65   \fi
66   \expandafter\x\csname ver@etexcmds.sty\endcsname
67   \ProvidesPackage{etexcmds}%
68   [2016/05/16 v1.6 Avoid name clashes with e-TeX commands (HO)]%

```

2.2 Catcodes

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70   \catcode13=5 % ^~M
71   \endlinechar=13 %
72   \catcode123=1 % {
73   \catcode125=2 % }
74   \catcode64=11 % @
75   \def\x{\endgroup
76     \expandafter\edef\csname etexcmds@AtEnd\endcsname{%
77       \endlinechar=\the\endlinechar\relax
78       \catcode13=\the\catcode13\relax

```

```

79     \catcode32=\the\catcode32\relax
80     \catcode35=\the\catcode35\relax
81     \catcode61=\the\catcode61\relax
82     \catcode64=\the\catcode64\relax
83     \catcode123=\the\catcode123\relax
84     \catcode125=\the\catcode125\relax
85   }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95   \edef\etexcmds@AtEnd{%
96     \etexcmds@AtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{39}{12}% '
102 \TMP@EnsureCode{40}{12}% (
103 \TMP@EnsureCode{41}{12}% )
104 \TMP@EnsureCode{44}{12}% ,
105 \TMP@EnsureCode{45}{12}% -
106 \TMP@EnsureCode{46}{12}% .
107 \TMP@EnsureCode{47}{12}% /
108 \TMP@EnsureCode{60}{12}% <
109 \TMP@EnsureCode{91}{12}% [
110 \TMP@EnsureCode{93}{12}% ]
111 \edef\etexcmds@AtEnd{%
112   \etexcmds@AtEnd
113   \escapechar\the\escapechar\relax
114   \noexpand\endinput
115 }
116 \escapechar=92 % backslash

```

2.3 Provide \newif

\etexcmds@newif

```

117 \def\etexcmds@newif#1{%
118   \expandafter\edef\csname etex@#1false\endcsname{%
119     \let
120     \expandafter\noexpand\csname ifetex@#1\endcsname
121     \noexpand\iffalse
122   }%
123   \expandafter\edef\csname etex@#1true\endcsname{%
124     \let
125     \expandafter\noexpand\csname ifetex@#1\endcsname
126     \noexpand\iftrue
127   }%
128   \csname etex@#1false\endcsname
129 }

```

2.4 Load package infwarerr

```

130 \begingroup\expandafter\expandafter\expandafter\endgroup
131 \expandafter\ifx\csname RequirePackage\endcsname\relax
132   \def\TMP@RequirePackage#1[#2]{%
133     \begingroup\expandafter\expandafter\expandafter\endgroup
134     \expandafter\ifx\csname ver@#1.sty\endcsname\relax
135       \input #1.sty\relax
136     \fi
137   }%
138   \TMP@RequirePackage{infwarerr}[2007/09/09]%
139   \TMP@RequirePackage{ifluatex}[2010/03/01]%
140 \else
141   \RequirePackage{infwarerr}[2007/09/09]%
142   \RequirePackage{ifluatex}[2010/03/01]%
143 \fi

```

2.5 \unexpanded

\ifetex@unexpanded

```

144 \etexcmds@newif{unexpanded}

```

\etex@unexpanded

```

145 \begingroup
146 \edef\x{\string\unexpanded}%
147 \edef\y{\meaning\unexpanded}%
148 \ifx\x\y
149   \endgroup
150   \let\etex@unexpanded\unexpanded
151   \etex@unexpandedtrue
152 \else
153   \edef\y{\meaning\normalunexpanded}%
154   \ifx\x\y
155     \endgroup
156     \let\etex@unexpanded\normalunexpanded
157     \etex@unexpandedtrue
158   \else
159     \edef\y{\meaning\@@unexpanded}%
160     \ifx\x\y
161       \endgroup
162       \let\etex@unexpanded\@@unexpanded
163       \etex@unexpandedtrue
164     \else
165       \ifluatex
166         \ifnum\luatexversion<36 %
167         \else
168           \begingroup
169             \directlua{%
170               tex.enableprimitives('etex@',{'unexpanded'})}%
171             }%
172             \global\let\etex@unexpanded\etex@unexpanded
173           \endgroup
174         \fi
175       \fi
176       \edef\y{\meaning\etex@unexpanded}%
177       \ifx\x\y
178         \endgroup
179         \etex@unexpandedtrue
180       \else
181         \endgroup
182         \@PackageInfoNoLine{etexcmds}{%

```

```

183         Could not find \string\unexpanded.\MessageBreak
184         That can mean that you are not using e-TeX or%
185         \MessageBreak
186         that some package has redefined \string\unexpanded.%
187         \MessageBreak
188         In the latter case, load this package earlier%
189     }%
190     \etex@unexpandedfalse
191 \fi
192 \fi
193 \fi
194 \fi

```

2.6 \expanded

\ifetex@expanded

```

195 \etexcmds@newif{expanded}

```

\etex@expanded

```

196 \begingroup
197 \edef\x{\string\expanded}%
198 \edef\y{\meaning\expanded}%
199 \ifx\x\y
200     \endgroup
201     \let\etex@expanded\expanded
202     \etex@expandedtrue
203 \else
204     \edef\y{\meaning\normalexpanded}%
205     \ifx\x\y
206         \endgroup
207         \let\etex@expanded\normalexpanded
208         \etex@expandedtrue
209     \else
210         \edef\y{\meaning\@@expanded}%
211         \ifx\x\y
212             \endgroup
213             \let\etex@expanded\@@expanded
214             \etex@expandedtrue
215         \else
216             \ifluatex
217                 \ifnum\luatexversion<36 %
218                 \else
219                     \begingroup
220                     \directlua{%
221                         tex.enableprimitives('etex@',{'expanded'})%
222                     }%
223                     \global\let\etex@expanded\etex@expanded
224                 \endgroup
225             \fi
226         \fi
227         \edef\y{\meaning\etex@expanded}%
228         \ifx\x\y
229             \endgroup
230             \etex@expandedtrue
231         \else
232             \endgroup
233             \@PackageInfoNoLine{etexcmds}{%
234                 Could not find \string\expanded.\MessageBreak

```

```

235         That can mean that you are not using pdfTeX 1.50 or%
236         \MessageBreak
237         that some package has redefined \string\expanded.%
238         \MessageBreak
239         In the latter case, load this package earlier%
240     }%
241     \etex@expandedfalse
242 \fi
243 \fi
244 \fi
245 \fi

246 \etexcmds@AtEnd%
247 \endpackage

```

3 Test

3.1 Catcode checks for loading

```

248 \test1)

249 \catcode`\{=1 %
250 \catcode`\}=2 %
251 \catcode`\#=6 %
252 \catcode`\@=11 %
253 \expandafter\ifx\csname count\endcsname\relax
254   \countdef\count@=255 %
255 \fi
256 \expandafter\ifx\csname @gobble\endcsname\relax
257   \long\def@gobble#1{%
258 \fi
259 \expandafter\ifx\csname @firstofone\endcsname\relax
260   \long\def@firstofone#1{#1}%
261 \fi
262 \expandafter\ifx\csname loop\endcsname\relax
263   \expandafter@firstofone
264 \else
265   \expandafter@gobble
266 \fi
267 {%
268   \def\loop#1\repeat{%
269     \def\body{#1}%
270     \iterate
271   }%
272   \def\iterate{%
273     \body
274     \let\next\iterate
275   \else
276     \let\next\relax
277   \fi
278   \next
279 }%
280 \let\repeat=\fi
281 }%
282 \def\RestoreCatcodes{
283 \count@=0 %
284 \loop
285   \edef\RestoreCatcodes{%

```

```

286 \RestoreCatcodes
287 \catcode\the\count@=\the\catcode\count@\relax
288 }%
289 \ifnum\count@<255 %
290 \advance\count@ 1 %
291 \repeat
292
293 \def\RangeCatcodeInvalid#1#2{%
294 \count@=#1\relax
295 \loop
296 \catcode\count@=15 %
297 \ifnum\count@<#2\relax
298 \advance\count@ 1 %
299 \repeat
300 }
301 \def\RangeCatcodeCheck#1#2#3{%
302 \count@=#1\relax
303 \loop
304 \ifnum#3=\catcode\count@
305 \else
306 \errmessage{%
307 Character \the\count@\space
308 with wrong catcode \the\catcode\count@\space
309 instead of \number#3%
310 }%
311 \fi
312 \ifnum\count@<#2\relax
313 \advance\count@ 1 %
314 \repeat
315 }
316 \def\space{ }
317 \expandafter\ifx\csname LoadCommand\endcsname\relax
318 \def\LoadCommand{\input etexcmds.sty\relax}%
319 \fi
320 \def\Test{%
321 \RangeCatcodeInvalid{0}{47}%
322 \RangeCatcodeInvalid{58}{64}%
323 \RangeCatcodeInvalid{91}{96}%
324 \RangeCatcodeInvalid{123}{255}%
325 \catcode`\@=12 %
326 \catcode`\=0 %
327 \catcode`\%=14 %
328 \LoadCommand
329 \RangeCatcodeCheck{0}{36}{15}%
330 \RangeCatcodeCheck{37}{37}{14}%
331 \RangeCatcodeCheck{38}{47}{15}%
332 \RangeCatcodeCheck{48}{57}{12}%
333 \RangeCatcodeCheck{58}{63}{15}%
334 \RangeCatcodeCheck{64}{64}{12}%
335 \RangeCatcodeCheck{65}{90}{11}%
336 \RangeCatcodeCheck{91}{91}{15}%
337 \RangeCatcodeCheck{92}{92}{0}%
338 \RangeCatcodeCheck{93}{96}{15}%
339 \RangeCatcodeCheck{97}{122}{11}%
340 \RangeCatcodeCheck{123}{255}{15}%
341 \RestoreCatcodes
342 }
343 \Test

```



```

344 \csname @@end\endcsname
345 \end
346 </test1>

```

3.2 Macro tests

```

347 <*test2>
348 \immediate\write16{etexcmds-test2.tex: test file for plainTeX}
349 \input etexcmds.sty\relax
350 \catcode`\@=11 %
351 \edef\x{\string\unexpanded}
352 \edef\y{\meaning\etex@unexpanded}
353 \ifx\x\y
354 \else
355   \@PackageError{etexcmds-test2}{Test failed}\@ehc
356 \fi
357 \end
358 </test2>

359 <*test3>
360 \NeedsTeXFormat{LaTeX2e}
361 \ProvidesFile{etexcmds-test3.tex}[2016/05/16 v1.6 Test file for LaTeX]
362 \RequirePackage{etexcmds}
363 \makeatletter
364 \edef\x{\string\unexpanded}
365 \edef\y{\meaning\etex@unexpanded}
366 \ifx\x\y
367 \else
368   \@PackageError{etexcmds-test3}{Test failed}\@ehc
369 \fi
370 \stop
371 </test3>

372 <*test4>
373 \NeedsTeXFormat{LaTeX2e}
374 \ProvidesFile{etexcmds-test4.tex}[2016/05/16 v1.6 Test file for LaTeX]
375 \documentclass{article}
376 \usepackage{m-pictex}
377 \def\normalwritestatus#1#2{%
378   \typeout{EMERGENCY HACK \string\normalwritestatus}%
379   \typeout{#1: #2}%
380 }
381 \usepackage{m-ch-de}
382 \usepackage{etexcmds}
383 \makeatletter
384 \ifetex@unexpanded
385   \edef\x{\string\unexpanded}%
386   \edef\y{\meaning\etex@unexpanded}%
387   \ifx\x\y
388   \else
389     \@PackageWarningNoLine{etexcmds-test4}{Test failed}%
390   \fi
391 \else
392   \@PackageWarningNoLine{etexcmds-test4}{%
393     Test failed because of ConTeXt%
394   }%
395 \fi
396 \stop
397 </test4>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

`CTAN:macros/latex/contrib/oberdiek/etexcmds.dtx` The source file.

`CTAN:macros/latex/contrib/oberdiek/etexcmds.pdf` Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

`CTAN:install/macros/latex/contrib/oberdiek.tds.zip`

TDS refers to the standard “A Directory Structure for \TeX Files” (`CTAN:tds/tds.pdf`). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps.

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain \TeX :

```
tex etexcmds.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>etexcmds.sty</code>	\rightarrow <code>tex/generic/oberdiek/etexcmds.sty</code>
<code>etexcmds.pdf</code>	\rightarrow <code>doc/latex/oberdiek/etexcmds.pdf</code>
<code>test/etexcmds-test1.tex</code>	\rightarrow <code>doc/latex/oberdiek/test/etexcmds-test1.tex</code>
<code>test/etexcmds-test2.tex</code>	\rightarrow <code>doc/latex/oberdiek/test/etexcmds-test2.tex</code>
<code>test/etexcmds-test3.tex</code>	\rightarrow <code>doc/latex/oberdiek/test/etexcmds-test3.tex</code>
<code>test/etexcmds-test4.tex</code>	\rightarrow <code>doc/latex/oberdiek/test/etexcmds-test4.tex</code>
<code>etexcmds.dtx</code>	\rightarrow <code>source/latex/oberdiek/etexcmds.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution (`te \TeX` , `mik \TeX` , ...) relies on file name databases, you must refresh these. For example, `te \TeX` users run `texhash` or `mktextlsr`.

¹`CTAN:pkg/etexcmds`

4.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the `autodetect` routine about your intention:

```
latex \let\install=y\input{etexcmds.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex etexcmds.dtx
makeindex -s gind.ist etexcmds.idx
pdflatex etexcmds.dtx
makeindex -s gind.ist etexcmds.idx
pdflatex etexcmds.dtx
```

5 History

[2007/05/06 v1.0]

- First version.

[2007/09/09 v1.1]

- Documentation for `\ifetex@unexpanded` added.
- Catcode section rewritten.

[2007/12/12 v1.2]

- `\etex@expanded` added.

[2010/01/28 v1.3]

- Compatibility to iniT_EX added.

[2011/01/30 v1.4]

- Already loaded package files are not input in plain T_EX.

[2011/02/16 v1.5]

- Using LuaT_EX's `tex.enableprimitives` if available.

[2016/05/16 v1.6]

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols		
\#	251	\escapechar 113, 116
\%	327	\etex@expanded 196
\@	252, 325, 350	\etex@expandedfalse 241
\@expanded	210, 213	\etex@expandedtrue 202, 208, 214, 230
\@unexpanded	159, 162	\etex@unexpanded 2, 145, 352, 365, 386
\@PackageError	355, 368	\etex@unexpandedfalse 190
\@PackageInfoNoLine	182, 233	\etex@unexpandedtrue 151, 157, 163, 179
\@PackageWarningNoLine	389, 392	\etexcmds@AtEnd 95, 96, 111, 112, 246
\@ehc	355, 368	\etexcmds@newif 117, 144, 195
\@firstofone	260, 263	\expanded 197, 198, 201, 234, 237
\@gobble	257, 265	
\@undefined	58	
\\	326	
\{	249	
\}	250	
A		I
\advance	290, 298, 313	\ifetex@expanded 195
\aftergroup	29	\ifetex@unexpanded 2, 144, 384
B		\iffalse 121
\body	269, 273	\ifluatex 165, 216
C		\ifnum 166, 217, 289, 297, 304, 312
\catcode	2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 69, 70, 72, 73, 74, 78, 79, 80, 81, 82, 83, 84, 87, 88, 90, 91, 92, 93, 97, 99, 249, 250, 251, 252, 287, 296, 304, 308, 325, 326, 327, 350	\iftrue 126
\count@	254, 283, 287, 289, 290, 294, 296, 297, 298, 302, 304, 307, 308, 312, 313	\ifx 15, 18, 21, 50, 58, 61, 131, 134, 148, 154, 160, 177, 199, 205, 211, 228, 253, 256, 259, 262, 317, 353, 366, 387
\countdef	254	\immediate 23, 52, 348
\csname	14, 21, 50, 66, 76, 118, 120, 123, 125, 128, 131, 134, 253, 256, 259, 262, 317, 344	\input 135, 318, 349
D		\iterate 270, 272, 274
\directlua	169, 220	
\documentclass	375	
E		L
\empty	17, 18	\LoadCommand 318, 328
\end	345, 357	\loop 268, 284, 295, 303
\endcsname	14, 21, 50, 66, 76, 118, 120, 123, 125, 128, 131, 134, 253, 256, 259, 262, 317, 344	\luatexversion 166, 217
\endinput	29, 114	
\endlinechar	4, 35, 71, 77, 89	
\errmessage	306	
		M
		\makeatletter 363, 383
		\meaning 147, 153, 159, 176, 198, 204, 210, 227, 352, 365, 386
		\MessageBreak 183, 185, 187, 234, 236, 238
		N
		\NeedsTeXFormat 360, 373
		\next 274, 276, 278
		\normalexpanded 204, 207
		\normalunexpanded 153, 156
		\normalwritestatus 377, 378
		\number 309
		P
		\PackageInfo 26
		\ProvidesFile 361, 374
		\ProvidesPackage 19, 67

R		<code>\typeout</code> 378, 379
<code>\RangeCatcodeCheck</code>		
. 301, 329, 330, 331, 332, 333,		
334, 335, 336, 337, 338, 339, 340		
<code>\RangeCatcodeInvalid</code>		
..... 293, 321, 322, 323, 324		
<code>\repeat</code> 268, 280, 291, 299, 314		
<code>\RequirePackage</code> 141, 142, 362		
<code>\RestoreCatcodes</code> .. 282, 285, 286, 341		
S		U
<code>\space</code> 307, 308, 316		<code>\unexpanded</code> 146,
<code>\stop</code> 370, 396		147, 150, 183, 186, 351, 364, 385
T		<code>\usepackage</code> 376, 381, 382
<code>\Test</code> 320, 343		
<code>\the</code> 77, 78, 79, 80,		
81, 82, 83, 84, 97, 113, 287, 307, 308		
<code>\TMP@EnsureCode</code> . 94, 101, 102, 103,		
104, 105, 106, 107, 108, 109, 110		
<code>\TMP@RequirePackage</code> ... 132, 138, 139		
		W
		<code>\write</code> 23, 52, 348
		X
		<code>\x</code> 14, 15, 18, 22, 26, 28,
		51, 56, 66, 75, 87, 146, 148, 154,
		160, 177, 197, 199, 205, 211,
		228, 351, 353, 364, 366, 385, 387
		Y
		<code>\y</code> 147, 148, 153,
		154, 159, 160, 176, 177, 198,
		199, 204, 205, 210, 211, 227,
		228, 352, 353, 365, 366, 386, 387