

The stampinclude package

Heiko Oberdiek*

2016/05/16 v1.1

Abstract

The package replaces `\includeonly` and selects the files for `\include` by inspecting the time stamp of the `.aux` file. The file is selected for inclusion if the `.aux` file does not yet exist or is older than the corresponding `.tex` file.

Contents

| | | |
|----------|------------------------------------|----------|
| 1 | Documentation | 1 |
| 1.1 | Introduction | 1 |
| 1.2 | Usage | 2 |
| 1.3 | Limitations | 2 |
| 1.3.1 | Other file dependencies | 2 |
| 1.3.2 | <code>\include</code> dependencies | 3 |
| 1.3.3 | Summary | 3 |
| 1.4 | Requirements | 3 |
| 2 | Implementation | 3 |
| 3 | Installation | 5 |
| 3.1 | Download | 5 |
| 3.2 | Bundle installation | 5 |
| 3.3 | Package installation | 5 |
| 3.4 | Refresh file name databases | 6 |
| 3.5 | Some details for the interested | 6 |
| 4 | References | 6 |
| 5 | History | 6 |
| | [2008/07/14 v1.0] | 6 |
| | [2016/05/16 v1.1] | 7 |

1 Documentation

1.1 Introduction

L^AT_EX provides two commands `\include` and `\includeonly` that helps in organizing large projects. Example for a master file:

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

```

\documentclass{book}
\l\% \includeonly{}
\begin{document}
\l\include{fileA}
\l\include{fileB}
\l\include{fileC}
\end{document}

```

All files are read and compiled if `\includeonly` is not executed. Otherwise you can give `\includeonly` a list of files in the preamble, e.g.:

```
\includeonly{fileA,fileC}
```

Now only files `fileA.tex` and `fileC.tex` are read and compiled.

If you change file `fileB.tex` and want to see only this file, then you must change the line with `\includeonly` to

```
\includeonly{fileB}
```

It is tedious to do this again and again, if different files are changed.

Package `askinclude` [1] offers a solution for this problem. It interactively asks for the files to be included and saves the user from editing the master file.

This package `stampinclude` goes another way. \LaTeX reads and writes a separate `.aux` file for each file that is included by `\include`. There \LaTeX remembers counter values. Changed `.tex` files can therefore be detected by comparing the file date stamp of the `.tex` file with the date stamp of its `.aux` file. Since version 1.30.0 `pdf\text{\TeX}` provides `\pdffilemoddate` that reads the file date stamp. Thus this package uses this command and redefines `\include` to include the files that do not have `.aux` files yet or that are newer than its `.aux` file. `\includeonly` is ignored.

1.2 Usage

The package is loaded as normal \LaTeX package without options:

```
\usepackage{stampinclude}
```

Alternatively the package may be loaded on the command line (Example for shell ‘bash’):

```
latex '\AtBeginDocument{\usepackage{stampinclude}}\input{master}'
```

Without `\AtBeginDocument` (and `\RequirePackage` instead of `\usepackage`) \TeX would name the document `stampinclude.dvi` instead of `master.dvi`.

1.3 Limitations

1.3.1 Other file dependencies

A file that is included by `\include` may input ore reference other files:

- other \TeX files using `\input`,
- graphics files (`\includegraphics`),
- listings of external files,
- ...

Updates of those files are not detected by this package. It limits the date stamp comparison of an `.aux` file to its `.tex` file.

1.3.2 `\include` dependencies

In the example, given in the introduction [1.1](#), three files `fileA`, `fileB`, and `fileC` are included in this order. Now file `fileA` is changed by adding four pages, `fileB` remains untouched, and `fileC` is also updated. Then the package only selects `fileA` and `fileC` for inclusion. File `fileB` is not included. But \LaTeX has stored the counter values that are active at the end of `fileB` in `fileB.aux` in one of the previous runs when `fileB` was included. However the later addition of four pages in `fileA` was not known at that time. Therefore `fileB.aux` is out of date and the inclusion of file `fileC` starts with wrong counter values (especially the page counter).

1.3.3 Summary

This package `stampinclude` and the `\include` feature helps in accelerating the \LaTeX compilation. But it is not intended for generating the final version. For the final version of the document it is better to include *all* files to get all counter values right. Then this package and any `\includeonly` lines should be commented out:

```
% \usepackage{stampinclude}
% \includeonly{...}
```

1.4 Requirements

- pdf\TeX v1.30.0 (because of `\pdffilemoddate` and `\pdfstrcmp`), both modes for DVI and PDF are supported.
- Alternatively Lua\TeX may be used. It lacks `\pdffilemoddate` and `\pdfstrcmp`. But its services are provided by package `pdftexcmds` [\[2\]](#) that is automatically loaded.

2 Implementation

```
1 <*package>
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{stampinclude}
4 [2016/05/16 v1.1 Include files based on time stamps (H0)]%
5 \RequirePackage{pdftexcmds}[2007/12/12]%
6 \begingroup
7   \chardef\x=1 %
8   \expandafter\ifx\csname pdf@filemoddate\endcsname\relax
9     \chardef\x=0 %
10  \fi
11  \expandafter\ifx\csname pdf@strcmp\endcsname\relax
12    \chardef\x=0 %
13  \fi
14 \expandafter\endgroup\ifcase\x
15   \PackageWarningNoLine{stampinclude}{%
16     \string\pdffilemoddate\space or %
17     \string\pdfstrcmp\space are not found,\MessageBreak
18     that are provided by pdfTeX >= 1.30.0.\MessageBreak
19     Also LuaTeX is not detected.\MessageBreak
20     Therefore package loading is aborted%
21   }%
22 \expandafter\endinput
23 \fi
```

\SInc@org@include

```
24 \let\SInc@org@include\include
```

\@include

```
25 \def\@include#1 {%
26   \IfFileExists{#1.aux}{%
27     \ifnum\pdf@strcmp{\pdf@filemoddate{#1.aux}}%
28       {\pdf@filemoddate{#1.tex}}<0 %
29     \ifx\@partlist\@empty
30       \gdef\@partlist{#1}%
31     \else
32       \g@addto@macro\@partlist{, #1}%
33     \fi
34   \fi
35 }{%
36   \ifx\@partlist\@empty
37     \gdef\@partlist{#1}%
38   \else
39     \g@addto@macro\@partlist{, #1}%
40   \fi
41 }%
42 \SInc@org@include{#1} \relax
43 }
```

\includeonly Macro \includeonly is ignored.

```
44 \renewcommand*\includeonly[1]{%
45   \PackageInfo{stampinclude}{%
46     Ignoring \string\includeonly
47   }%
48 }
```

Simulate \includeonly.

```
49 \@partswtrue
50 \gdef\@partlist{}

Print included files at end of document.

51 \AtEndDocument{%
52   \begingroup
53     \expandafter\let\expandafter\@partlist\expandafter\@empty
54     \expandafter\@for\expandafter\reserved@a
55     \expandafter:\expandafter=\@partlist\do{%
56       \ifx\@partlist\@empty
57         \edef\@partlist{\reserved@a}%
58       \else
59         \edef\@partlist{\@partlist, \reserved@a}%
60       \fi
61     }%
62     \typeout{*****%
63               *****%
64               *****%
65               *****%
66     }%
67     \ifx\@partlist\@empty
68       \typeout{[stampinclude] No included files.}%
69     \else
70       \typeout{[stampinclude] Included files:}%
71       \typeout{\@partlist}%
72     \fi
```

```

73 \typeout{*****%
74          *****%
75          *****%
76          *****%
77 }%
78 \endgroup
79 }
80 \</package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/stampinclude.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/stampinclude.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain \TeX :

```
tex stampinclude.dtx
```

¹[CTAN:pkg/stampinclude](#)

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
stampinclude.sty → tex/latex/oberdiek/stampinclude.sty
stampinclude.pdf → doc/latex/oberdiek/stampinclude.pdf
stampinclude.dtx → source/latex/oberdiek/stampinclude.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your `TEX` distribution (`teTEX`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `teTEX` users run `texhash` or `mktextlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{stampinclude.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdfLATEX`:

```
pdflatex stampinclude.dtx
makeindex stampinclude.idx
pdflatex stampinclude.dtx
makeindex stampinclude.idx
pdflatex stampinclude.dtx
```

4 References

- [1] Pablo A. Straub, Heiko Oberdiek: *The askinclude package*; 2007/10/23 v2.0; [CTAN:macros/latex/contrib/oberdiek/askinclude.pdf](#).
- [2] Heiko Oberdiek: *The pdftexcmds package*; 2007/12/12 v0.3; [CTAN:macros/latex/contrib/oberdiek/pdftexcmds.pdf](#).

5 History

[2008/07/14 v1.0]

- First version.

[2016/05/16 v1.1]

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

| Symbols | |
|---------------------------------|---|
| \@empty | 29, 36, 53, 56, 67 |
| \@for | 54 |
| \@include | 24, <u>25</u> |
| \@partlist | 29, 30, 32, 36, 37, 39, 50, 53, 55, 56, 57, 59, 67, 71 |
| \@partswtrue | 49 |
| A | |
| \AtEndDocument | 51 |
| C | |
| \chardef | 7, 9, 12 |
| \csname | 8, 11 |
| D | |
| \do | 55 |
| E | |
| \endcsname | 8, 11 |
| \endinginput | 22 |
| G | |
| \g@addto@macro | 32, 39 |
| \gdef | 30, 37, 50 |
| I | |
| \ifcase | 14 |
| \IfFileExists | 26 |
| \ifnum | 27 |
| \ifx | 8, 11, 29, 36, 56, 67 |
| \includeonly | <u>44</u> |
| M | |
| \MessageBreak | 17, 18, 19 |
| N | |
| \NeedsTeXFormat | 2 |
| P | |
| \PackageInfo | 45 |
| \PackageWarningNoLine | 15 |
| \pdf@filemoddate | 27, 28 |
| \pdf@strcmp | 27 |
| \pdf@filemoddate | 16 |
| \pdfstrcmp | 17 |
| \ProvidesPackage | 3 |
| R | |
| \renewcommand | 44 |
| \RequirePackage | 5 |
| \reserved@a | 54, 57, 59 |
| S | |
| \Sinc@org@include | 24, 42 |
| \space | 16, 17 |
| T | |
| \typeout | 62, 68, 70, 71, 73 |
| X | |
| \x | 7, 9, 12, 14 |