

The `telprint` package

Heiko Oberdiek*

2016/05/16 v1.11

Abstract

Package `telprint` provides `\telprint` for formatting German phone numbers.

Contents

1 Documentation	2
1.1 Introduction	2
1.2 Short overview in English	2
1.2.1 Configuration	2
1.3 Documentation in German	2
2 Implementation	3
2.1 Reload check and package identification	3
2.2 Catcodes	5
2.3 Package macros	5
3 Test	8
3.1 Catcode checks for loading	8
4 Installation	9
4.1 Download	9
4.2 Bundle installation	10
4.3 Package installation	10
4.4 Refresh file name databases	10
4.5 Some details for the interested	10
5 History	11
[1996/11/28 v1.0]	11
[1997/09/16 v1.1]	11
[1997/10/16 v1.2]	11
[1997/12/09 v1.3]	11
[2004/11/02 v1.4]	11
[2005/09/30 v1.5]	11
[2006/02/12 v1.6]	12
[2006/08/26 v1.7]	12
[2007/04/11 v1.8]	12
[2007/09/09 v1.9]	12
[2008/08/11 v1.10]	12
[2016/05/16 v1.11]	12

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 Documentation

1.1 Introduction

This is a very old package that I have written to format phone numbers. It follows German conventions and the documentation is mainly in German.

1.2 Short overview in English

LATEX:

```
\usepackage{telprint}
\telprint{123/456-789}
```

plain TEX:

```
\input telprint.sty
\telprint{123/456-789}
```

\telprint \telprint{...} formats the explicitly given number. Digits, spaces and some special characters ('+', '/', '−', '(', ')', '~, ' ') are supported. Numbers are divided into groups of two digits from the right. Examples:

```
\telprint{0761/12345}    ==> 07\,61/1\,23\,45
\telprint{01234/567-89}  ==> 0\,12\,34/5\,67\leavevmode\hbox{-
}89
\telprint{+49 (6221) 297} ==> +49~(62\,21)~2\,97
```

1.2.1 Configuration

The output of the symbols can be configured by \telhyphen, \telslash, \telleftparen, \telrightparen, \telplus, \teltilde. Example:

```
\telslash{\,/\,}\ \telprint{12/34} ==> 12\,/\,34
```

\telspace \telspace configures the space between digit groups.

\telnumber \telnumber only formats a number in digit groups; special characters are not recognized.

1.3 Documentation in German

\telprint • **telprint#1**

Der eigentliche Anwenderbefehl zur formatierten Ausgabe von Telefonnummern. Diese dürfen dabei nur als Zahlen angegeben werden (, da sie tokenweise analysiert werden). Als Trenn- oder Sonderzeichen werden unterstützt: '+', '/', '−', '(', ')', '~, ' '. Einfache Leerzeichen werden erkannt und durch Tilden ersetzt, um Trennungen in der Telefonnummer zu verhindern. (Man beachte aus gleichem Grunde die \hbox bei '−'.) Beispiele:

```
\telprint{0761/12345}    ==> 07\,61/1\,23\,45
\telprint{01234/567-89}  ==> 0\,12\,34/5\,67\leavevmode\hbox{-
}89
\telprint{+49 (6221) 297} ==> +49~(62\,21)~2\,97
```

Der Rest enthält eher Technisches:

- `\telspace#1`
Mit diesem Befehl wird der Abstand zwischen den Zifferngruppen angegeben (Default: `\,`). (Durch `\telspace{}` kann dieser zusätzliche Abstand abgestellt werden.)
- `\telhyphen#1`
Dieser Befehl gibt die Art des Bindestriches, wie er ausgegeben werden soll. In der Eingabe darf jedoch nur der einfache Bindestrich stehen: `\telprint{123-45}`, jedoch NIE `\telprint{123--45}`! Kopka-Bindestrich-Fans geben an: `\telhyphen{\leavevmode\hbox{--}}`
- `\telslash#1, \telleftparen#1, \telrightparen#1, \telplus#1, \teltilde#1`
Diese Befehle konfigurieren die Zeichen `'/'`, `'('`, `')'`, `'+'` und `'~'`. Sie funktionieren analog zu `\telhyphen`.
- `\telnumber#1`
Richtung interner Befehl: Er dient dazu, eine Zifferngruppe in Zweiergruppen auszugeben. Die einzelnen Zahlen werden im Tokenregister `\TELtoks` gespeichert. Abwechselnd werden dabei zwischen zwei Token (Zahlen) `\TELx` bzw. `\TELy` eingefügt, abhängig von dem wechselnden Wert von `\TELswitch`. Zum Schluss kann dann einfach festgestellt werden ob die Nummer nun eine geradzahlige oder ungeradzahlige Zahl von Ziffern aufwies. Dem entsprechend wird `\TELx` mit dem Zusatzabstand belegt und `\TELy` leer definiert oder umgekehrt.)
- `\TEL... interne Befehle, Technisches:`
`\TELsplit` dient zur Aufteilung einer zusammengesetzten Telefonnummer (Vorwahl, Hauptnummer, Nebenstelle). In dieser Implementation werden als Trennzeichen nur `'/'` und `'-'` erkannt. Die einzelnen Bestandteile wie Vorwahl werden dann dem Befehl `\telnumber` zur Formatierung uebergeben.
- Die Erkennung von einfachen Leerzeichen ist um einiges schwieriger: Die Tokentrennung ueber Parameter `#1#2` funktioniert nicht für einfache Leerzeichen, da TeX sie *niemals* als eigenständige Argumente behandelt! (The TeXbook, Chapter 20, p. 201)
(Anmerkung am Rande: Deshalb funktionieren die entsprechenden Tokenmakros auf S. 149 des Buches „Einführung in TeX“ von N. Schwarz (3. Aufl.) nicht, wenn im Tokenregister als erstes ein einfaches Leerzeichen steht!)

2 Implementation

1 `(*package)`

2.1 Reload check and package identification

Reload check, especially if the package is not used with L^AT_EX.

```

2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^~M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @

```

```

12  \catcode123=1 %
13  \catcode125=2 %
14  \expandafter\let\expandafter\x\csname ver@telprint.sty\endcsname
15  \ifx\x\relax % plain-TeX, first loading
16  \else
17      \def\empty{}%
18      \ifx\x\empty % LaTeX, first loading,
19          % variable is initialized, but \ProvidesPackage not yet seen
20      \else
21          \expandafter\ifx\csname PackageInfo\endcsname\relax
22              \def\x#1#2{%
23                  \immediate\write-1{Package #1 Info: #2.}%
24              }%
25      \else
26          \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27      \fi
28      \x{telprint}{The package is already loaded}%
29      \aftergroup\endinput
30  \fi
31 \fi
32 \endgroup%

```

Package identification:

```

33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34  \catcode13=5 % ^~M
35  \endlinechar=13 %
36  \catcode35=6 % #
37  \catcode39=12 %
38  \catcode40=12 %
39  \catcode41=12 %
40  \catcode44=12 %
41  \catcode45=12 %
42  \catcode46=12 %
43  \catcode47=12 %
44  \catcode58=12 %
45  \catcode64=11 %
46  \catcode91=12 %
47  \catcode93=12 %
48  \catcode123=1 %
49  \catcode125=2 %
50  \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51      \def\x#1#2#3[#4]{\endgroup
52          \immediate\write-1{Package: #3 #4}%
53          \xdef#1{#4}%
54      }%
55  \else
56      \def\x#1#2[#3]{\endgroup
57          #2[{#3}]%
58          \ifx#1\undefined
59              \xdef#1{#3}%
60          \fi
61          \ifx#1\relax
62              \xdef#1{#3}%
63          \fi
64      }%
65  \fi
66 \expandafter\x\csname ver@telprint.sty\endcsname
67 \ProvidesPackage{telprint}%
68 [2016/05/16 v1.11 Format German phone numbers (HO)]%

```

2.2 Catcodes

```
69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70   \catcode13=5 % ^M
71   \endlinechar=13 %
72   \catcode123=1 %
73   \catcode125=2 %
74   \catcode64=11 %
75   \def\x{\endgroup
76     \expandafter\edef\csname TELAtEnd\endcsname{%
77       \endlinechar=\the\endlinechar\relax
78       \catcode13=\the\catcode13\relax
79       \catcode32=\the\catcode32\relax
80       \catcode35=\the\catcode35\relax
81       \catcode61=\the\catcode61\relax
82       \catcode64=\the\catcode64\relax
83       \catcode123=\the\catcode123\relax
84       \catcode125=\the\catcode125\relax
85     }%
86   }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 %
92 \catcode123=1 %
93 \catcode125=2 %
94 \def\TMP@EnsureCode#1#2{%
95   \edef\TELAtEnd{%
96     \TELAtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{33}{12}!
102 \TMP@EnsureCode{36}{3} $ %
103 \TMP@EnsureCode{40}{12} (
104 \TMP@EnsureCode{41}{12} )
105 \TMP@EnsureCode{42}{12} *
106 \TMP@EnsureCode{43}{12} +
107 \TMP@EnsureCode{44}{12} ,
108 \TMP@EnsureCode{45}{12} -
109 \TMP@EnsureCode{46}{12} .
110 \TMP@EnsureCode{47}{12} /
111 \TMP@EnsureCode{91}{12} [
112 \TMP@EnsureCode{93}{12} ]
113 \TMP@EnsureCode{126}{13} ~ (active)
114 \edef\TELAtEnd{\TELAtEnd\noexpand\endinput}
```

2.3 Package macros

```
115 \ifx\DeclareRobustCommand\UnDeFiNeD
116   \def\DeclareRobustCommand*#1[1]{\def#1##1}%
117   \def\TELreset{\let\DeclareRobustCommand=\UnDeFiNeD}%
118   \input infwarerr.sty\relax
119   \QPackageInfo{telprint}{%
120     Macros are not robust!%
121   }%
122 \else
```

```

123 \let\TELreset=\relax
124 \fi

\telspace
125 \DeclareRobustCommand*\{\telspace}[1]{\def\TELspace{\#1}}
126 \telspace{${}\$\\${}{}}

\telhyphen
127 \DeclareRobustCommand*\{\telhyphen}[1]{\def\TELhyphen{\#1}}
128 \telhyphen{\leavevmode\hbox{-}}% \hbox zur Verhinderung der Trennung

\telslash
129 \DeclareRobustCommand*\{\telslash}[1]{\def\TELslash{\#1}}
130 \telslash{/}%

\telleftparen
131 \DeclareRobustCommand*\{\telleftparen}[1]{\def\TELleftparen{\#1}}
132 \telleftparen{()}

\telrightparen
133 \DeclareRobustCommand*\{\telrightparen}[1]{\def\TELrightparen{\#1}}
134 \telrightparen{)}%

\telplus
135 \DeclareRobustCommand*\{\telplus}[1]{\def\TELplus{\#1}}
136 \telplus{+}%

\teltilde
137 \DeclareRobustCommand*\{\teltilde}[1]{\def\TELtilde{\#1}}
138 \teltilde{~}%

\TELtoks
139 \newtoks\TELtoks

\TELnumber
140 \def\TELnumber#1#2\TELnumberEND{%
141   \begingroup
142   \def\0{\#2}%
143   \expandafter\endgroup
144   \ifx\0\empty
145     \TELtoks=\expandafter{\the\TELtoks#1}%
146     \ifnum\TELswitch=0 %
147       \def\TELx{\TELspace}\def\TELy{\}%
148     \else
149       \def\TELx{\}\def\TELy{\TELspace}%
150     \fi
151     \the\TELtoks
152   \else
153     \ifnum\TELswitch=0 %
154       \TELtoks=\expandafter{\the\TELtoks#1\TELx}%
155       \def\TELswitch{1}%
156     \else
157       \TELtoks=\expandafter{\the\TELtoks#1\TELy}%
158       \def\TELswitch{0}%
159     \fi
160     \TELnumber#2\TELnumberEND
161   \fi
162 }

```

```

\telnumber
163 \DeclareRobustCommand*{\telnumber}[1]{%
164   \TELtoks={}%
165   \def\TELswitch{0}%
166   \TELnumber#1{}\TELnumberEND
167 }

\TELsplit
168 \def\TELsplit{\futurelet\TELfuture\TELdosplit}

\TELdosplit
169 \def\TELdosplit#1#2\TELsplitEND
170 {%
171   \def\TELsp{ }%
172   \expandafter\ifx\TELsp\TELfuture
173     \let\TELfuture=\relax
174     \expandafter\telnumber\expandafter{\the\TELtoks}~%
175     \telprint{#1#2}% Das Leerzeichen kann nicht #1 sein!
176   \else
177     \def\TELfirst{#1}%
178     \ifx\TELfirst\empty
179       \expandafter\telnumber\expandafter{\the\TELtoks}%
180       \TELtoks={}%
181     \else\if-\TELfirst
182       \expandafter\telnumber\expandafter{\the\TELtoks}\TELhyphen
183       \telprint{#2}%
184     \else\if/\TELfirst
185       \expandafter\telnumber\expandafter{\the\TELtoks}\TELslash
186       \telprint{#2}%
187     \else\if(\TELfirst
188       \expandafter\telnumber\expandafter{\the\TELtoks}\TELleftparen
189       \telprint{#2}%
190     \else\if)\TELfirst
191       \expandafter\telnumber\expandafter{\the\TELtoks}\TELrightparen
192       \telprint{#2}%
193     \else\if+\TELfirst
194       \expandafter\telnumber\expandafter{\the\TELtoks}\TELplus
195       \telprint{#2}%
196     \else\def\TELtemp{-}\ifx\TELtemp\TELfirst
197       \expandafter\telnumber\expandafter{\the\TELtoks}\TELtilde
198       \telprint{#2}%
199     \else
200       \TELtoks=\expandafter{\the\TELtoks#1}%
201       \TELsplit#2{}\TELsplitEND
202     \fi\fi\fi\fi\fi\fi
203   \fi
204 }

\telprint
205 \DeclareRobustCommand*{\telprint}[1]{%
206   \TELtoks={}%
207   \TELsplit#1{}\TELsplitEND
208 }

209 \TELreset\let\TELreset=\UnDeFiNeD
210 \TELAtEnd%
211 </package>

```

3 Test

3.1 Catcode checks for loading

```
212 /*test1>
213 \catcode`\\#=1 %
214 \catcode`\\#=2 %
215 \catcode`\\#=6 %
216 \catcode`\\@=11 %
217 \expandafter\ifx\csname count@\endcsname\relax
218   \countdef\count@=255 %
219 \fi
220 \expandafter\ifx\csname @gobble\endcsname\relax
221   \long\def@gobble#1{}%
222 \fi
223 \expandafter\ifx\csname @firstofone\endcsname\relax
224   \long\def@firstofone#1{#1}%
225 \fi
226 \expandafter\ifx\csname loop\endcsname\relax
227   \expandafter@\firstofone
228 \else
229   \expandafter@\gobble
230 \fi
231 {%
232   \def\loop#1\repeat{%
233     \def\body{#1}%
234     \iterate
235   }%
236   \def\iterate{%
237     \body
238     \let\next\iterate
239   \else
240     \let\next\relax
241   \fi
242   \next
243 }%
244 \let\repeat=\fi
245 }%
246 \def\RestoreCatcodes{}%
247 \count@=0 %
248 \loop
249   \edef\RestoreCatcodes{%
250     \RestoreCatcodes
251     \catcode`\the\count@=\the\catcode\count@\relax
252   }%
253 \ifnum\count@<255 %
254   \advance\count@ 1 %
255 \repeat
256
257 \def\RangeCatcodeInvalid#1#2{%
258   \count@=#1\relax
259   \loop
260     \catcode\count@=15 %
261   \ifnum\count@<#2\relax
262     \advance\count@ 1 %
263   \repeat
264 }
265 \def\RangeCatcodeCheck#1#2#3{%
```

```

266 \count@=#1\relax
267 \loop
268   \ifnum#3=\catcode\count@
269   \else
270     \errmessage{%
271       Character \the\count@\space
272       with wrong catcode \the\catcode\count@\space
273       instead of \number#3%
274     }%
275   \fi
276 \ifnum\count@<#2\relax
277   \advance\count@ 1 %
278 \repeat
279 }
280 \def\space{ }
281 \expandafter\ifx\csname LoadCommand\endcsname\relax
282 \def\LoadCommand{\input telprint.sty\relax}%
283 \fi
284 \def\Test{%
285   \RangeCatcodeInvalid{0}{47}%
286   \RangeCatcodeInvalid{58}{64}%
287   \RangeCatcodeInvalid{91}{96}%
288   \RangeCatcodeInvalid{123}{255}%
289   \catcode`\@=12 %
290   \catcode`\\=0 %
291   \catcode`\%=14 %
292   \LoadCommand
293   \RangeCatcodeCheck{0}{36}{15}%
294   \RangeCatcodeCheck{37}{37}{14}%
295   \RangeCatcodeCheck{38}{47}{15}%
296   \RangeCatcodeCheck{48}{57}{12}%
297   \RangeCatcodeCheck{58}{63}{15}%
298   \RangeCatcodeCheck{64}{64}{12}%
299   \RangeCatcodeCheck{65}{90}{11}%
300   \RangeCatcodeCheck{91}{91}{15}%
301   \RangeCatcodeCheck{92}{92}{0}%
302   \RangeCatcodeCheck{93}{96}{15}%
303   \RangeCatcodeCheck{97}{122}{11}%
304   \RangeCatcodeCheck{123}{255}{15}%
305   \RestoreCatcodes
306 }
307 \Test
308 \csname @@end\endcsname
309 \end
310 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/telprint.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/telprint.pdf](#) Documentation.

¹[CTAN:pkg/telprint](#)

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain \TeX :

```
tex telprint.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>telprint.sty</code>	→ <code>tex/generic/oberdiek/telprint.sty</code>
<code>telprint.pdf</code>	→ <code>doc/latex/oberdiek/telprint.pdf</code>
<code>test/telprint-test1.tex</code>	→ <code>doc/latex/oberdiek/test/telprint-test1.tex</code>
<code>telprint.dtx</code>	→ <code>source/latex/oberdiek/telprint.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution ($\text{\TeX} \text{ Live}$, $\text{mik}\text{\TeX}$, ...) relies on file name databases, you must refresh these. For example, $\text{\TeX} \text{ Live}$ users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain \TeX : Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{telprint.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex telprint.dtx
makeindex -s gind.ist telprint.idx
pdflatex telprint.dtx
makeindex -s gind.ist telprint.idx
pdflatex telprint.dtx
```

5 History

[1996/11/28 v1.0]

- Erste lauffähige Version.
- Nur '-' und '/' als zulässige Sonderzeichen.

[1997/09/16 v1.1]

- Dokumentation und Kommentare (Posting in de.comp.text.tex).
- Erweiterung um Sonderzeichen '(', ')', '+', '~' und ' '.
- Trennungsverhinderung am 'hyphen'.

[1997/10/16 v1.2]

- Schutz vor wiederholtem Einlesen.
- Unter L^AT_EX 2_ε Nutzung des \DeclareRobustCommand-Features.

[1997/12/09 v1.3]

- Temporäre Variable eingespart.
- Posted in newsgroup `de.comp.text.tex`:
“Re: Generisches Markup für Telefonnummern?”²

[2004/11/02 v1.4]

- Fehler in der Dokumentation korrigiert.

[2005/09/30 v1.5]

- Konfigurierbare Symbole: '/', '(', ')', '+' und '~'.

²Url: <https://groups.google.com/group/de.comp.text.tex/msg/86b3a86140007309>

[2006/02/12 v1.6]

- LPPL 1.3.
- Kurze Übersicht in Englisch.
- CTAN.

[2006/08/26 v1.7]

- New DTX framework.

[2007/04/11 v1.8]

- Line ends sanitized.

[2007/09/09 v1.9]

- Catcode section added.
- Missing docstrip tag added.

[2008/08/11 v1.10]

- Code is not changed.
- URLs updated.

[2016/05/16 v1.11]

- Documentation updates.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	B
\#	215
\%	291
\,	126
\@	216, 289
\@PackageInfo	119
\@firstofone	224, 227
\@gobble	221, 229
\@undefined	58
\\"	290
\{	213
\}	214
Numbers	C
\o	142, 144
A	B
\advance	254, 262, 277
\aftergroup	29
count@	218, 247,
countdef	251, 253, 254, 258, 260, 261,
csname	262, 266, 268, 271, 272, 276, 277
countdef	218
csname	14, 21, 50,
aftergroup	66, 76, 217, 220, 223, 226, 281, 308

D	T
\DeclareRobustCommand	\TELAtEnd 95, 96, 114, 210
. 115, 116, 117, 125, 127,	\TELdosplit 168, <u>169</u>
129, 131, 133, 135, 137, 163, 205	\TELfirst 177,
	178, 181, 184, 187, 190, 193, 196
E	\TELfuture 168, 172, 173
\empty 17, 18, 144, 178	\TELhyphen 127, 182
\end 309	\telhyphen 3, <u>127</u>
\endcsname 14, 21, 50,	\TELleftparen 131, 188
66, 76, 217, 220, 223, 226, 281, 308	\telleftparen 3, <u>131</u>
\endinput 29, 114	\TELnumber <u>140</u> , 166
\endlinechar 4, 35, 71, 77, 89	\telnumber 2, 3, <u>163</u> , 174,
\errmessage 270	179, 182, 185, 188, 191, 194, 197
F	\TELnumberEND 140, 160, 166
\futurelet 168	\TELplus 135, 194
	\telplus 3, <u>135</u>
H	\telprint 2, 2, 175,
\hbox 128	183, 186, 189, 192, 195, 198, <u>205</u>
	\TELreset 117, 123, 209
I	\TELrightparen 133, 191
\if 181, 184, 187, 190, 193	\telrightparen 3, <u>133</u>
\ifnum 146, 153, 253, 261, 268, 276	\TELslash 129, 185
\ifx 15,	\telslash 3, <u>129</u>
18, 21, 50, 58, 61, 115, 144, 172,	\TELsp 171, 172
178, 196, 217, 220, 223, 226, 281	\TELspace 125, 147, 149
\immediate 23, 52	\telspace 2, 3, <u>125</u>
\input 118, 282	\TELsplit <u>168</u> , 201, 207
\iterate 234, 236, 238	\TELsplitEND 169, 201, 207
	\TELswitch 146, 153, 155, 158, 165
L	\TELtemp 196
\leavevmode 128	\TELtilde 137, 197
\LoadCommand 282, 292	\teltilde 3, <u>137</u>
\loop 232, 248, 259, 267	\TELtoks 139, 145, 151, 154,
	157, 164, 174, 179, 180, 182,
N	185, 188, 191, 194, 197, 200, 206
\newtoks 139	\TELx 147, 149, 154
\next 238, 240, 242	\TELy 147, 149, 157
\number 273	\Test 284, 307
	\the 77, 78, 79, 80,
P	81, 82, 83, 84, 97, 145, 151, 154,
\PackageInfo 26	157, 174, 179, 182, 185, 188,
\ProvidesPackage 19, 67	191, 194, 197, 200, 251, 271, 272
	\TMP@EnsureCode 94,
R	101, 102, 103, 104, 105, 106,
\RangeCatcodeCheck	107, 108, 109, 110, 111, 112, 113
. 265, 293, 294, 295, 296, 297,	
298, 299, 300, 301, 302, 303, 304	U
\RangeCatcodeInvalid	\UnDeFiNeD 115, 117, 209
. 257, 285, 286, 287, 288	
\repeat 232, 244, 255, 263, 278	W
\RestoreCatcodes 246, 249, 250, 305	\write 23, 52
S	
\space 271, 272, 280	X
	\x 14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87