

Examples of `paresse` package usage.

le T_EXnicien de surface

2011-04-19

This file loads the `lmodern` package if it locally exists.

Caution: the `paresse` package is loaded with the option `tame` to show the usage of macro `\ActiveLaParesse` and environment `ParesseActive`.

With the macro `\ActiveLaParesse` to make the § character active.

```
{\ActiveLaParesse
\($a^{$b}_{$g}\) and also \($D^$a_$d\)
}
```

to obtain: α_γ^β and also Δ_δ^α

With the environment `ParesseActive`.

```
\begin{ParesseActive}\large
\begin{tabular}{*4{||>{\ttfamily \$}c|c}||} \hline
a & $a & b & $b & g & $g & d & $d\\ \hline
e & $e & z & $z & h & $h & v & $v\\ \hline
...
X & $X & P & $P & S & $S & U & $U\\ \hline
F & $F & Q & $Q & W & $W & Z & $Z\\ \hline
\end{tabular}
\end{ParesseActive}
```

\$a	α	\$b	β	\$g	γ	\$d	δ
\$e	ε	\$z	ζ	\$h	η	\$v	θ
\$i	ι	\$k	κ	\$l	λ	\$m	μ
\$n	ν	\$x	ξ	\$p	π	\$r	ρ
\$s	σ	\$y	τ	\$u	υ	\$f	φ
\$c	χ	\$q	ψ	\$w	ω		
\$G	Γ	\$D	Δ	\$V	Θ	\$L	Λ
\$X	Ξ	\$P	Π	\$S	Σ	\$U	Υ
\$F	Φ	\$Q	Ψ	\$W	Ω	\$Z	\S