

The ltdocinit module

The L^AT_EX Project*

Version 0.95e, released 2021-06-14

1 ltdocinit documentation

This small module defines `\DeclareDocumentMetadata` and the related keys. It also defines commands to store document properties in a global container.

1.1 `\DeclareDocumentMetadata`

<code>\DeclareDocumentMetadata</code>	<code>\DeclareDocumentMetadata{<key-value list>}</code>
---------------------------------------	---

Currently there is no dedicated location to declare settings concerning a document as a whole. Settings are placed somewhere in the preamble or with the class options or even with some package options. For some settings this can be too late, for example the pdf version can no longer be changed if a package has used code which already opened the PDF.

`\DeclareDocumentMetadata` as a new command should unify such settings in one place. It should be used before `\documentclass`, directly after loading `pdfmanagement-testphase`. `\DeclareDocumentMetadata` can be used more than once.

The keys defined for `\DeclareDocumentMetadata` currently allows to set the PDF version, to set the PDF /Lang, to uncompress a pdf, to set the language and to declare a few PDF standards and some colorprofiles.

`\DeclareDocumentMetadata` is also used to activate the new PDF management code and it loads a number of required files for the PDF management code. As this forces the loading of the backend files, a backend which can't be detected automatically like `dvipdfmx`, must be set in the first `\DeclareDocumentMetadata`.

Currently the following keys are implemented

backend passes the backend name to `expl3`. This will probably be extended to pass the value also to packages.

pdfversion e.g. `pdfversion=1.7`

uncompress no value. Forces an uncompressed pdf.

lang to set the Lang entry in the Catalog. E.g. `lang=de-DE`. The initial value is `en-US`

*E-mail: latex-team@latex-project.org

pdfstandard Choice key to set the pdf standard. Currently A-1b, A-2b, A-2u, A-3b and A-3u are accepted as values. The casing is irrelevant, a-1b works too. The underlying code to ensure the requirements (as far as they can be ensured) is incomplete, but a color profile is included and the /OutputIntent is set. The u variants for example do not force unicode, but they will pass the information to hyperref and hyperxmp. More information can be found in the documentation of l3pdfmeta.

colorprofiles This allows to load icc-colorprofiles. Details are described in the documentation of l3pdfmeta.

pdfmanagement Boolean. This activates/deactivates the core management code. By default the value is true.

firstaidoff This accepts a comma lists of keyword and disable the patches related to them. More information can be found in the documentation of pdfmanagement-firstaid.

1.2 Container for document properties

The module provides a container where classes, packages and users can store properties of the document which are perhaps of interest or use for other packages or the author.

The properties are stored with a key `label/property`. The values can be retrieved expandably.

<code>\AddToDocumentProperties</code>	<code>\AddToDocumentProperties[⟨label⟩]{⟨property⟩}{⟨value⟩}</code>
---------------------------------------	---

This stores `⟨value⟩` under the key `⟨label⟩/⟨property⟩`. By default `⟨label⟩` is the current package name `\@currname`. If another label is choosen, it should be one which avoids clashes with other packages using the container. The label `document` is reserved.

<code>\GetDocumentProperties</code>	<code>\GetDocumentProperties{⟨label/property⟩}</code>
-------------------------------------	---

Expands to the `⟨value⟩` corresponding to `⟨label/property⟩` in the container. If `⟨label/property⟩` is missing, this has an empty expansion. The result is returned within `\exp_not:n`, which means that the `⟨value⟩` does not expand further when appearing in an x-type argument expansion.

<code>\ShowDocumentProperties</code>	<code>\ShowDocumentProperties</code>
--------------------------------------	--------------------------------------

This show the current content of the container.

2 ltdocinit implementation

2.1 \DeclareDocumentMetadata

```

1 <@@=pdfmanagement>
2 <*header>
3 \ProvidesExplPackage{ltdocinit}{2021-06-14}{0.95e}
4   {Initialize document metadata}
5 </header>
```

`\DeclareDocumentMetadata` should for now not be used after `\documentclass` so we error in this case. It can be used more than once but follow-up calls should not do the initialization code.

```

6  (*package)
7  \msg_new:nnn { document } { setup-after-documentclass }
8      {
9          \token_to_str:N \DeclareDocumentMetadata \c_space_tl
10         should-be-used-only-before-\token_to_str:N\documentclass
11     }

```

`\DeclareDocumentMetadata`

```

12 \NewDocumentCommand\DeclareDocumentMetadata { m }
13 {
14     \cs_if_eq:NNTF \documentclass \@twoclasseserror
15     { \msg_error:nn { document } { setup-after-documentclass } }
16     {

```

The wanted backend must be detected first, we read the init key and then force the loading by either loading l3pdf (+ expl3) or only expl3. The backend contains now management command, so the boolean should true first.

```

17     \keys_set_groups:nnn { document / metadata } {init}{ #1 }
18     %should be loaded after the backend is set, and only if not in the kernel
19     \bool_gset_true:N \g__pdfmanagement_active_bool
20     \cs_if_free:NTF \pdf_uncompress:
21     { \RequirePackage{l3pdf} } { \RequirePackage{expl3} }

```

Now we load the extra backend code

```

22     \ExplSyntaxOn\makeatletter
23     \file_input:n {l3backend-testphase-\c_sys_backend_str.def}
24     \ExplSyntaxOff\makeatother

```

set the default language, process the rest of the keys, and setup the generic driver

```

25     \keys_set_filter:nnn { document / metadata } { init } { lang=en-US, #1 }
26     \bool_if:NT \g__pdfmanagement_active_bool
27     {
28         \PassOptionsToPackage{customdriver=hgeneric-testphase}{hyperref}
29     }

```

`\pdfmanagement_add:nnn` has collected values in this hook.

```

30     \hook_use_once:n {pdfmanagement/add}

```

Redefine `\DeclareDocumentMetadata` so that it only process the keys. We need to update the `hyperref` option if the active status changes.

```

31     \RenewDocumentCommand\DeclareDocumentMetadata { m }
32     {
33         \keys_set_filter:nnn { document / metadata } { init } { ##1 }
34         \bool_if:NNTF \g__pdfmanagement_active_bool
35         {
36             \str_remove_all:cn {opt@hyperref.sty}{customdriver=hgeneric-testphase}
37             \PassOptionsToPackage{customdriver=hgeneric-testphase}{hyperref}
38         }
39         {
40             \str_remove_all:cn {opt@hyperref.sty}{customdriver=hgeneric-testphase}
41         }
42     }

```

Load more modules and the firstaid code.

```

43     \RequirePackage{pdfmanagement-firstaid}
44   }
45 }

```

(End definition for \DeclareDocumentMetadata. This function is documented on page 1.)

2.2 Container for document Properties

The container for the document properties is a prop

\g__pdfmanagement_documentproperties_prop

```

46 \prop_new:N \g__pdfmanagement_documentproperties_prop %

```

(End definition for \g__pdfmanagement_documentproperties_prop.)

\AddToDocumentProperties

```

47 \NewDocumentCommand\AddToDocumentProperties{0{\@currname}mm}
48 {
49   \exp_args:NNx
50   \prop_gput:Nnn \g__pdfmanagement_documentproperties_prop
51   {
52     \tl_if_blank:eTF {#1}{top-level/}{#1/} #2
53   }
54   { #3}
55 }

```

(End definition for \AddToDocumentProperties. This function is documented on page 2.)

\GetDocumentProperties

```

56 \NewExpandableDocumentCommand\GetDocumentProperties{m}
57 {
58   \prop_item:Nn \g__pdfmanagement_documentproperties_prop {#1}
59 }

```

(End definition for \GetDocumentProperties. This function is documented on page 2.)

\ShowDocumentProperties

```

60 \msg_new:nnn { pdfmanagement } { show-properties }
61 {
62   The~following~document~properties~have~been~stored:
63   #1
64 }
65 \NewDocumentCommand\ShowDocumentProperties {}
66 {
67   \msg_show:nnx {pdfmanagement}{show-properties}
68   {
69     \prop_map_function:NN \g__pdfmanagement_documentproperties_prop \msg_show_item:nn
70   }
71 }

```

(End definition for \ShowDocumentProperties. This function is documented on page 2.)

2.3 The keys for \DeclareDocumentMetadata

As they use \AddToDocumentProperties they have to come after it has been defined.

```
\g__pdfmanagement_firstaidoff_clist A list to store the firstaid code which should be disabled
72 \clist_new:N \g__pdfmanagement_firstaidoff_clist
(End definition for \g__pdfmanagement_firstaidoff_clist.)
73 \keys_define:nn { document / metadata }
74 {
75     backend .code:n =
76     {
77         \PassOptionsToPackage { driver=#1 } {expl3}
78         \AddToDocumentProperties [document] {backend} {#1}
79     },
80     backend .groups:n = { init } ,
81 }
82
83 \keys_define:nn { document / metadata }
84 {
85     ,pdfversion .code:n =
86     {
87         \pdf_version_gset:n { #1 }
88         \AddToDocumentProperties [document] {pdfversion} {#1}
89     }
90     ,uncompress .code:n =
91     {
92         \pdf_uncompress:
93     }
94     ,uncompress .value_forbidden:n = true
95     ,lang .code:n =
96     {
97         \pdfmanagement_add:nnn {Catalog} {Lang} {(#1)}
98         \AddToDocumentProperties [document] {lang} {#1}
99     }
100     %,xmpmeta .bool_gset:N = \g_pdfmeta_xmp_bool %see pdfmeta unused and undefined for now!
101     % this uses internal command from pdfmeta, it should probably move there ...
102     ,pdfstandard .code:n =
103     {
104         \exp_args:Nnx
105         \keys_set:nn {document / metadata} {_pdfstandard=\str_uppercase:n{#1}}
106     }
107     ,_pdfstandard .choices:nn =
108     {A-1B,A-2B,A-2U,A-3B,A-3U}
109     {
110         \prop_if_exist:cT { g__pdfmeta_standard_pdf/#1_prop }
111         {
112             \prop_gset_eq:Nc \g__pdfmeta_standard_prop { g__pdfmeta_standard_pdf/#1 _prop }
113         }
114         \AddToDocumentProperties [document] {pdfstandard} {#1}
115     }
116     ,_pdfstandard / unknown .code:n =
117     {
118         \msg_warning:nnn {pdf} {unknown-standard} {#1}
```

```

119     }
120     ,pdfmanagement .bool_gset:N = \g__pdfmanagement_active_bool
121     ,firstaidoff .clist_gset:N = \g__pdfmanagement_firstaidoff_clist
122 }
123 \end{package}

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A	
\AddToDocumentProperties	\keys_set:nn 105
..... 2, 5, <u>47</u> , 78, 88, 98, 114	\keys_set_filter:nnn 25, 33
	\keys_set_groups:nnn 17
B	
bool commands:	M
\bool_gset_true:N 19	\makeatletter 22
\bool_if:NTF 26, 34	\makeatother 24
C	
clist commands:	msg commands:
\clist_new:N 72	\msg_error:nn 15
cs commands:	\msg_new:nnn 7, 60
\cs_if_eq:NNTF 14	\msg_show:nnn 67
\cs_if_free:NTF 20	\msg_show_item:nn 69
D	
\DeclareDocumentMetadata ... 1–3, 5, 9, <u>12</u>	\msg_warning:nnn 118
\documentclass 1, 3, 10, 14	N
E	
exp commands:	\NewDocumentCommand 12, 47, 65
\exp_args:NNx 49	\NewExpandableDocumentCommand 56
\exp_args:Nnx 104	P
\exp_not:n 2	\PassOptionsToPackage 28, 37, 77
\ExplSyntaxOff 24	pdf commands:
\ExplSyntaxOn 22	\pdf_uncompress: 20, 92
F	
file commands:	\pdf_version_gset:n 87
\file_input:n 23	pdfmanagement commands:
G	
\GetDocumentProperties 2, <u>56</u>	\pdfmanagement_add:nnn 3, 97
H	
hook commands:	pdfmanagement internal commands:
\hook_use_once:n 30	\g__pdfmanagement_active_bool ...
K	
keys commands: 19, 26, 34, 120
\keys_define:nn 73, 83	\g__pdfmanagement_documentproperties_
	prop 46, 50, 58, 69
	\g__pdfmanagement_firstaidoff_
	clist 72, 121
	pdfmeta commands:
	\g_pdfmeta_xmp_bool 100
	pdfmeta internal commands:
	\g__pdfmeta_standard_prop 112
	prop commands:
	\prop_gput:Nnn 50
	\prop_gset_eq:NN 112
	\prop_if_exist:NTF 110
	\prop_item:Nn 58

<code>\prop_map_function:NN</code>	69	sys commands:	
<code>\prop_new:N</code>	46	<code>\c_sys_backend_str</code>	23
<code>\ProvidesExplPackage</code>	3		
		T	
R		TeX and L ^A T _E X 2 _ε commands:	
<code>\RenewDocumentCommand</code>	31	<code>\currname</code>	47
<code>\RequirePackage</code>	21, 43	<code>\twoclasseserror</code>	14
		tl commands:	
S		<code>\c_space_tl</code>	9
<code>\ShowDocumentProperties</code>	2, 60	<code>\tl_if_blank:nTF</code>	52
str commands:		token commands:	
<code>\str_remove_all:Nn</code>	36, 40	<code>\token_to_str:N</code>	9, 10
<code>\str_uppercase:n</code>	105		