

A L^AT_EX Package for the frontmatter and title page ^{*†}

Arthur Ogawa [‡]

October 1, 2020

This file embodies the `ltxfront` package, the implementation and its user documentation.

The distribution point for this work is <https://journals.aps.org/revtex>, which contains fully unpacked, prebuilt runtime files and documentation.

The `ltxfront` package was commissioned by the American Physical Society and is distributed under the terms of the L^AT_EX Project Public License 1.3c, the same license under which all the portions of L^AT_EX itself is distributed. Please see <http://ctan.tug.org/macros/latex/base/lppl.txt> for details.

To use this document class, you must have a working T_EX installation equipped with L^AT_EX 2_ε and possibly pdf_{te}x and Adobe Acrobat Reader or equivalent.

To install, retrieve the distribution, unpack it into a directory on the target computer, and move the file `ltxfront.sty` into a location in your filesystem where it will be found by L^AT_EX.

To use, read the user documentation `ltxfront.pdf`.

Contents

1	Processing Instructions	3
1.1	Build Instructions	3
1.2	Change Log	4
1.3	Bill of Materials	4
1.3.1	Primary Source	4
1.3.2	Generated by <code>latex ltxfront.dtx</code>	4
1.3.3	Generated by <code>tex ltxfront.dtx</code>	4
1.3.4	Documentation	4
1.3.5	Auxiliary	4
2	Code common to all modules	4

^{*}This file has version number 4.2d, last revised 2020/09/30.

[†]Version 4.2d © 2019 American Physical Society

[‡]mailto:arthur_ogawa@sbcglobal.net

3	The doc module doc	5
3.1	The Preamble	5
3.1.1	Docstrip and info directives	6
3.2	The “Read Me” File	6
3.3	A Gnuly Created Sample Document	9
3.4	The Document Body	10
4	Using this package	10
4.1	Invoking the package	10
5	Frontmatter commands	11
6	The Front Matter	11
6.1	Setting the title	11
6.2	Specifying a date	11
6.3	Specifying authors and affiliations	11
6.3.1	Collaborations	13
6.3.2	Footnotes for authors, collaborations, affiliations or title	13
6.3.3	Specifying first names and surnames	15
6.4	The abstract	15
6.5	PACS codes	15
6.6	Keywords	15
6.7	Institutional report numbers	16
6.8	maketitle	16
7	Compatability with L^AT_EX’s Required Packages	16
8	Implementation of package	16
8.1	Beginning of the package DOCSTRIP module	16
8.2	Prerequisites	16
8.3	Options	17
8.4	Process package options	18
9	Kernel of Front Matter	18
9.1	Initialization	19
9.2	The title command	19
9.3	The author, affiliation, and related commands	19
9.3.1	Commands for author or collaboration	20
9.3.2	Commands for affiliation	23
9.3.3	Commands for auxiliary information	30
9.3.4	Procedures for author, collaboration, and affiliation	31
9.4	The keywords command	34
9.5	The \date command and related commands	35
9.6	The pacs command	35
9.7	The \preprint command	35
9.8	The abstract environment	36

9.9	Formatting the title block	39
9.9.1	Authors and affiliations in superscriptaddress style	42
9.9.2	Authors and affiliations in groupedaddress style	47
10	Package defaults	52
10.1	Printing out the “list-of” elements	55
10.2	Syntax switch	56
10.3	End of the <code>ltxfront</code> kernel	57
10.4	Remainder of the <code>ltxfront</code> package	57
	Index	59

1 Processing Instructions

The package file `ltxfront.sty` is generated from this file, `ltxfront.dtx`, using the DOCSTRIP facility of L^AT_EX via `tex ltxfront.dtx`. The typeset documentation that you are now reading is generated from the same file by typesetting it with L^AT_EX or pdf_{tex} via `latex ltxfront.dtx` or `pdflatex ltxfront.dtx`.

1.1 Build Instructions

You may bootstrap this suite of files solely from `ltxfront.dtx`. Prepare by installing L^AT_EX 2_ε (and either `tex` or `pdftex`) on your computer, then carry out the following steps:

1. Within an otherwise empty directory, typeset `ltxfront.dtx` with T_EX or pdf_{tex}, thereby generating the package file `ltxfront.sty`.
2. Next typeset `ltxfront.dtx` with L^AT_EX or pdf_{flat}ex; you will obtain the typeset documentation you are now reading, along with the sample document `ltxfront-test.tex` and the file `README-LTXFRONT`.

Note: you will have to run L^AT_EX, then `makeindex -s gind.ist ltxfront.idx`, then `makeindex -s gglo.ist -o ltxfront.gls ltxfront.glo`, then L^AT_EX again in order to obtain a valid index and table of contents.

3. Now typeset `ltxfront.dtx` with T_EX(not L^AT_EX), thereby generating the package file `ltxfront.sty`.
4. Install the following files into indicated locations within your TDS-compliant `texmf` tree (you may need root access):

- `$TEXMF/tex/latex/revtex/ltxfront.sty`
- `$TEXMF/source/latex/revtex/ltxfront.dtx`
- `$TEXMF/doc/latex/revtex/ltxfront.pdf`

where `$TEXMF/` stands for `texmf-local/`, or some other `texmf` tree in your installation.

5. Run `mktexlsr` on `$TEXMF/` (you may need root access).
6. Build and installation are now complete; now put a `\usepackage{ltxfront}` in your document preamble!

1.2 Change Log

1.3 Bill of Materials

Following is a list of the files in this distribution arranged according to provenance.

1.3.1 Primary Source

One single file generates all.

`ltxfront.dtx`

1.3.2 Generated by `latex ltxfront.dtx`

Typesetting the source file under \LaTeX generates the readme and the documentation.

`README-LTXFRONT`

1.3.3 Generated by `tex ltxfront.dtx`

Typesetting the installer generates the package files.

`ltxfront.sty`

1.3.4 Documentation

The following are the online documentation:

`ltxfront.pdf`

1.3.5 Auxiliary

The following are auxiliary files generated in the course of running \LaTeX :

`ltxfront.aux ltxfront.idx ltxfront.ind ltxfront.log ltxfront.toc`

2 Code common to all modules

We want to require only one place in this file where the version number is stated, and we also want to ensure that the version number is embedded into every generated file.

Now we declare that these files can only be used with L^AT_EX 2_ε. An appropriate message is displayed if a different T_EX format is used.

```
1 %<*doc|package>
2 \NeedsTeXFormat{LaTeX2e}[1995/12/01]%
3 %</doc|package>
```

As desired, the following modules all take common version information:

```
4 %<kernel&!package&!doc>\typeout{%
5 %<*package|doc>
6 \ProvidesFile{%
7 %</package|doc>
8 %<*kernel|package|doc>
9 ltxfront%
10 %</kernel|package|doc>
11 %<*doc>
12 .dtx%
13 %</doc>
14 %<package>.sty%
15 %<*package|doc>
16 }%
17 %</package|doc>
```

The following line contains, for once and for all, the version and date information. By various means, this information is reproduced consistently in all generated files and in the typeset documentation.

```
18 %<*doc|package|kernel>
19 %<version>
20 [2020/09/30 4.2d frontmatter package (AO,DPC,MD)]% \fileversion
21 %</doc|package|kernel>
22 %<kernel&!package&!doc>}%
```

3 The doc module doc

This module, consisting of the present section, typesets the programmer's documentation, generating the README-LTXFRONT and sample document as needed.

Because the only uncommented-out lines of code at the beginning of this file constitute the doc module itself, we can simply typeset the .dtx file directly, and there is thus rarely any need to generate the “doc” DOCSTRIP module. Module delimiters are nonetheless required so that this code does not find its way into the other modules.

The `\end{document}` command concludes the typesetting run.

```
23 %<*doc>
```

3.1 The Preamble

The programmers documentation is formatted with the `ltxdoc` class with local customizations, and with the usual code line indexing.

```
24 \documentclass{ltxdoc}
25 \RequirePackage{ltxdocext}%
26 \let\url\undefined
27 \RequirePackage[colorlinks=true,linkcolor=blue]{hyperref}%
28 %\expandafter\ifx\csname package@font\endcsname\@undefined\else
29 % \expandafter\RequirePackage\expandafter{\csname package@font\endcsname}%
30 %\fi
31 \CodelineIndex\EnableCrossrefs % makeindex -s gind.ist ltxfront
32 \RecordChanges % makeindex -s gglo.ist -o ltxfront.gls ltxfront.glo
```

3.1.1 Docstrip and info directives

We use so many `DOCSTRIP` modules that we set the `StandardModuleDepth` counter to 1.

```
33 \setcounter{StandardModuleDepth}{1}
```

The following command retrieves the date and version information from this file.

```
34 \expandafter\GetFileInfo\expandafter{\jobname.dtx}%
```

3.2 The “Read Me” File

As promised above, here is the contents of the “Read Me” file. That file serves a double purpose, since it also constitutes the beginning of the programmer’s documentation. What better thing, after all, to have appear at the beginning of the typeset documentation?

A good discussion of how to write a ReadMe file can be found in Engst, Tonya, “Writing a ReadMe File? Read This” *MacTech* October 1998, p. 58.

Note the appearance of the `\StopEventually` command, which marks the dividing line between the user documentation and the programmer documentation.

The usual user will not be asked to do a full build, not to speak of the bootstrap. Instructions for carrying these processes begin in the programmer’s manual.

```
35 \begin{filecontents*}{README-LTXFRONT.tex}
36 \title{%
37 A \LaTeX\ Package for\\the frontmatter and title page%
38 \thanks{%
39 This file has version number \fileversion,
40 last revised \filedate.%
41 }%
42 \thanks{%
43 Version \fileversion\ \copyright\ 2019 American Physical Society
44 }%
45 }%
46
47 \author{%
```

```

48 Arthur Ogawa%
49 \thanks{\texttt{mailto:arthur\_ogawa at sbcglobal.net}}%
50}%
51%\iffalse
52% For version number and date,
53% search on "\fileversion" in the .dtx file,
54% or see the end of the README-LTXFRONT file.
55%\fi
56\maketitle
57
58 This file embodies the \classname{ltxfront} package,
59 the implementation and its user documentation.
60
61 The distribution point for this work is
62 \url{https://journals.aps.org/revtex},
63 which contains fully unpacked, prebuilt runtime files and documentation.
64
65 The \classname{ltxfront} package was commissioned by the American Physical Society
66 and is distributed under the terms of the \LaTeX\ Project Public License 1.3c,
67 the same license under which all the portions of \LaTeX\ itself is distributed.
68 Please see \url{http://ctan.tug.org/macros/latex/base/lppl.txt} for details.
69
70 To use this document class, you must have a working
71 \TeX\ installation equipped with \LaTeXe\
72 and possibly pdftex and Adobe Acrobat Reader or equivalent.
73
74 To install, retrieve the distribution,
75 unpack it into a directory on the target computer,
76 and move the file \file{ltxfront.sty}
77 into a location in your filesystem where it will be found by \LaTeX.
78
79 To use, read the user documentation \file{ltxfront.pdf}.
80
81 \tableofcontents
82
83 \section{Processing Instructions}
84
85 The package file \file{ltxfront.sty}
86 is generated from this file, \file{ltxfront.dtx},
87 using the {\sc docstrip} facility of \LaTeX
88 via |tex ltxfront.dtx|.
89 The typeset documentation that you are now reading is generated from
90 the same file by typesetting it with \LaTeX\ or pdftex
91 via |latex ltxfront.dtx| or |pdflatex ltxfront.dtx|.
92
93 \subsection{Build Instructions}
94
95 You may bootstrap this suite of files solely from \file{ltxfront.dtx}.
96 Prepare by installing \LaTeXe\ (and either tex or pdftex) on your computer,
97 then carry out the following steps:

```

```

98 \begin{enumerate}
99
100 \item
101 Within an otherwise empty directory,
102 typeset \file{ltxfront.dtx} with \TeX\ or pdftex,
103 thereby generating the package file \file{ltxfront.sty}.
104
105 \item
106 Next typeset \file{ltxfront.dtx} with \LaTeX\ or pdflatex;
107 you will obtain the typeset documentation you are now reading,
108 along with
109 the sample document \file{ltxfront-test.tex}
110 and the file \file{README-LTXFRONT}.
111
112 Note: you will have to run \LaTeX, then
113 \file{makeindex} \texttt{-s gind.ist ltxfront.idx}, then
114 \file{makeindex} \texttt{-s gglo.ist -o ltxfront.gls ltxfront.glo}, then
115 \LaTeX\ again in order to obtain a valid index and table of contents.
116 \item
117 Now typeset \file{ltxfront.dtx} with \TeX (not \LaTeX),
118 thereby generating the package file \file{ltxfront.sty}.
119 \item
120 Install the following files into indicated locations within your
121 TDS-compliant \texttt{texmf} tree (you may need root access):
122 \begin{itemize}
123 \item
124 \file{$TEXMF/}\file{tex/}\file{latex/}\file{revtex/}\classname{ltxfront.sty}
125 \item
126 \file{$TEXMF/}\file{source/}\file{latex/}\file{revtex/}\classname{ltxfront.dtx}
127 \item
128 \file{$TEXMF/}\file{doc/}\file{latex/}\file{revtex/}\classname{ltxfront.pdf}
129 \end{itemize}
130 where \file{$TEXMF/} stands for \file{texmf-local/}, or some other \texttt{texmf} tree
131 in your installation.
132 \item
133 Run \texttt{mktexlsr} on \file{$TEXMF/} (you may need root access).
134 \item
135 Build and installation are now complete;
136 now put a \cmd\usepackage\texttt{\{ltxfront\}} in your document preamble!
137 \end{enumerate}
138
139 \subsection{Change Log}
140 \changes{4.0b}{1999/06/20}{Change handling of \cs{@author} to prevent parsing problems. (Helps
141 \changes{4.0b}{1999/06/20}{Gathered all code for the abstract environment together and abstract
142 \changes{4.0b}{1999/06/20}{Separate option now controls production}
143 \changes{4.0b}{1999/06/20}{Set \cs{footnote} to \LaTeX\ standard version for this scope.}
144 \changes{4.0c}{1999/11/13}{grid changes with ltxgrid}
145 \changes{4.0d}{1998/01/31}{\cs{comma@space}}
146 \changes{4.0d}{1998/01/31}{change name from \cs{tempaffiliation}}
147 \changes{4.0d}{1998/01/31}{hookify}

```



```

148 \changes{4.0d}{1998/01/31}{If empty \cs{abstractname} omit spacing}
149 \changes{4.0d}{1998/01/31}{PACS boxed to width of abstract}
150 \changes{4.0e}{2000/09/20}{Keywords on same footing as PACS}
151 \changes{4.0e}{2000/09/20}{Warn if no production}
152 \changes{4.0f}{2001/02/13}{Actually append \cs{AU@grp} to \cs{@AAClist}.}
153 \changes{4.0g}{1998/06/10}{multiple preprint commands}
154 \changes{4.0h}{1998/06/25}{Changes to support groups of affiliations}
155 \changes{4.0h}{1998/06/25}{new hook}
156 \changes{4.0l}{1998/09/01}{add optional argument handling back}
157 \changes{4.0l}{1998/09/01}{Changes to add collaboration processing, which now means doing comma
158 \changes{4.0l}{1998/09/01}{macro added}
159 \changes{4.1a}{2008-06-30}{(AO, 443) create an entry in the PDF bookmarks for the abstract via
160 \changes{4.1a}{2008-07-01}{(AO, 496) remove default prependation to \cs{email}.}
161 \changes{4.1a}{2008-07-01}{(AO, 496) remove default prependation to \cs{homepage}.}
162 \changes{4.1a}{2008/06/16}{removed code that had been commented out}
163 \changes{4.1b}{2008/06/29}{(AO, 455) provide a \texttt{description} environment for the abstract
164 \changes{4.1b}{2008/08/02}{(AO, 486) \cs{collaboration} to work with \texttt{groupedaddress}}
165 \changes{4.1b}{2008/08/02}{Change csname \cs{AFS@opr} to \cs{AFG@opr}}
166 \changes{4.1b}{2008/08/02}{Make the syntax of this package switch optional}%
167 \changes{4.1b}{2008/08/02}{Provide for diagnostics via \cs{frontmatterverbose@sw}}
168 \changes{4.1b}{2008/08/02}{Use \cs{@affil@def} for all access to \cs{@affil}}
169 \changes{4.1b}{2008/08/02}{Use \cs{frontmatter@init} as the vehicle for all initialization}
170 \changes{4.1b}{2008/08/04}{(AO, 443) PDF Bookmark for title page}%
171 \changes{4.1b}{2008/08/04}{Provide facility \cs{affil@cutoff}: if there is only one affiliation}
172 \changes{4.1c}{2008/08/04}{Hyperref compatibility: take \cs{maketitle} back.}
173 \changes{4.1c}{2008/08/04}{Parametrize the production after the address}%
174 \changes{4.1c}{2008/08/04}{Produce PACS, keywords only if specified}%
175 \changes{4.1d}{2008/10/17}{(AO, 410) compare \cs{@tempa} to \cs{blankaffiliation}.}%
176 \changes{4.1f}{2009/07/07}{(AO, 515) Use \cs{set@footnotefont}, which is defined in ltxutil}
177 \changes{4.1g}{2009/10/05}{(AO, 535) Robustify \cs{footnote} while \cs{class@warn} is expanding}
178 \changes{4.1g}{2009/10/05}{(AO, 539) Robustify \cs{class@warn} against TOC processing}%
179 \changes{4.1i}{2009/10/18}{(AO, 540) More runtime diagnostics via \cs{frontmatterverbose@sw}}
180 \changes{4.1i}{2009/10/23}{(AO, 540) Rationalize code that appends to \cs{AF@grp}}
181 \changes{4.1i}{2009/10/23}{(AO, 540) Optimize boolean logic }
182 \changes{4.1i}{2009/10/23}{(AO, 544) Class options runinaddress and unsortedaddress stopped wor
183 \changes{4.1m}{2009/11/20}{(AO, 563) \cs{collaboration} to work with both \texttt{groupedaddress}
184 \changes{4.1m}{2009/11/20}{(AO, 563) More complete runtime diagnostics via \cs{frontmatterverbo
185 \changes{4.1m}{2009/11/20}{(AO, 563) Let \cs{@collaboration@gobble} parse all three arguments o
186 \changes{4.1n}{2009/11/30}{(AO, 567) Handle \cs{noaffiliation} case}
187 \changes{4.1n}{2009/11/30}{(AO, 567) Handle punctuation for \classoption{superscriptaddress} st
188 \changes{4.1n}{2009/12/03}{(AO) remove http:// from \cs{href} call}
189 \changes{4.1n}{2010/01/02}{(AO, 571) Interface \cs{set@footnotewidth} for determining the set w
190 \changes{4.1n}{2010/01/02}{(AO, 571) allow split after last line of footnote}%
191 \changes{4.1n}{2010/01/02}{(AO, 572) Independent footnote counter for title block. Abstract foo
192 \changes{4.2a}{2018/12/12}{(MD) Updated name of README file and use standard fonts when typeset
193
194 \end{filecontents*}

```

3.3 A Gnuly Created Sample Document

```
195 \begin{filecontents*}{ltxfront-test.tex}
196 \documentclass{article}% use any combination of titlepage, twocolumn
197 \usepackage[]{}{ltxfront}% use inactive to turn off features
198 \begin{document}
199
200 \title{Gnu Veldt Cuisine}
201
202 \author{G. Picking}
203 \thanks{Supported by a grant from the GSF.}
204 \affiliation{Acme Kitchen Products}
205
206 \author{R. Dillo}
207 \thanks{On leave during 1985.}
208 \affiliation{Cordon Puce School}
209
210 \date{24 July 1984}%
211 \revised{5 January 1985}%
212
213 \maketitle
214
215 \section{Introduction}%
216 We reproduce most features of \LaTeX\ manual, Figure C.4, p. 183.
217 \end{document}
218 \end{filecontents*}
```

3.4 The Document Body

Here is the document body, containing only a `\DocInput` directive—referring to this very file. This very cute self-reference is a common `ltxdoc` idiom.

```
219 \begin{document}%
220 \expandafter\DocInput\expandafter{\jobname.dtx}%
221 % ^^A\PrintChanges
222 \end{document}
223 %</doc>
```

4 Using this package

Once this package is installed on your filesystem, you can employ it in adding functionality to \LaTeX by invoking it in your document or document class.

4.1 Invoking the package

In your document, you can simply call it up in your preamble:

```
%\documentclass{book}%
%\usepackage{ltxfront}%
%\begin{document}
```

```
%\your document here>
%\end{document}
```

However, the preferred way is to invoke this package from within your customized document class:

```
%\NeedsTeXFormat{LaTeX2e}[1995/12/01]%
%\ProvidesClass{myclass}%
%\RequirePackage{ltxfront}%
%\LoadClass{book}%
%\class customization commands>
%\endinput
```

Once loaded, the package gives you access to certain procedures, usually to be invoked by a \LaTeX command or environment.

5 Frontmatter commands

A document using this package will use commands like \title , \author , \thanks , the **abstract** environment and \maketitle . These are part of \LaTeX 's standard document classes. But this package supplements \LaTeX syntax with additional commands, such as \affiliation , \collaboration , \email , \homepage , and others.

Furthermore, you can have multiple \author , \affiliation , and \collaboration commands, each with their own set of \email , \homepage , etc. commands.

6 The Front Matter

This section describes the macros this package provides for formatting the front matter of an article. The behavior and usage of these macros can be quite different from those provided in $\text{\LaTeX 2}_{\epsilon}$.

6.1 Setting the title

The title of the manuscript is simply specified by using the $\text{\title}\{\langle title \rangle\}$ macro. A \textbackslash may be used to put a line break in a long title. The \title command takes an optional argument, which you will use to give an abbreviated title for use in the running header.

6.2 Specifying a date

The $\text{\date}\langle date \rangle$ command outputs the date on the manuscript. Using \today will cause \LaTeX to insert the current date whenever the file is run:

```
\date{\today}
```

6.3 Specifying authors and affiliations

Commands specifying author and affiliation have been improved to save labor for authors and in production. Authors and affiliations are arranged into groupings called, appropriately enough, *author groups*. Each author group is a set of authors who share the same set of affiliations. Author names are specified with the `\author` macro while affiliations (or addresses) are specified with the `\affiliation` macro. Author groups are specified by sequences of `\author` macros followed by `\affiliation` macros. An `\affiliation` macro applies to all previously specified `\author` macros which don't already have an affiliation supplied.

For example, if Bugs Bunny and Roger Rabbit are both at Looney Tune Studios, while Mickey Mouse is at Disney World, the markup would be:

```
% \author{Bugs Bunny}
% \author{Roger Rabbit}
% \affiliation{Looney Tune Studios}
% \author{Mickey Mouse}
% \affiliation{Disney World}
```

The default is to display this as

Bugs Bunny and Roger Rabbit
Looney Tune Studios
Mickey Mouse
Disney World

This layout style for displaying authors and their affiliations is chosen by selecting the class option `groupedaddress`. This option is the default for all APS journal styles, so it does not need to be specified explicitly. The other major way of displaying this information is to use superscripts on the authors and affiliations. This can be accomplished by selecting the class option `superscriptaddress`. To achieve the display

Bugs Bunny,¹ Roger Rabbit,^{1,2} and Mickey Mouse²
¹*Looney Tune Studios*
²*Disney World*

one would use the markup

```
% \author{Bugs Bunny}
% \affiliation{Looney Tune Studios}
% \author{Roger Rabbit}
% \affiliation{Looney Tune Studios}
% \affiliation{Disney World}
% \author{Mickey Mouse}
% \affiliation{Disney World}
```

Note that this package takes care of any commas and *and*'s that join the author names together and font selection, as well as any superscript numbering. Only the author names and affiliations should be given within their respective macros.

There is a third class option, `unsortedaddress`, for controlling author/affiliation display. The default `groupedaddress` will actually sort authors into the appropriate author groups if one chooses to specify an affiliation for each author. The markup:

```
% \author{Bugs Bunny}
% \affiliation{Looney Tune Studios}
% \author{Mickey Mouse}
% \affiliation{Disney World}
% \author{Roger Rabbit}
% \affiliation{Looney Tune Studios}
```

will result in the same display as for the first case given above even though Roger Rabbit is specified after Mickey Mouse. To avoid Roger Rabbit being moved into the same author group as Bugs Bunny, use the `unsortedaddress` option instead. In general, it is safest to list authors in the order they should appear and specify affiliations for multiple authors rather than one at a time. This will afford the most independence for choosing the display option. Finally, it should be mentioned that the affiliations for the `superscriptaddress` are presented and numbered in the order that they are encountered. This means that the order will usually follow the order of the authors. An alternative ordering can be forced by including a list of `\affiliation` commands before the first `\author` in the desired order. Then use the exact same text for each affiliation when specifying them for each author.

If an author doesn't have an affiliation, the `\noaffiliation` macro may be used in the place of an `\affiliation` macro.

6.3.1 Collaborations

A collaboration name can be specified with the `\collaboration` command. This is very similar to the `\author` command. It should appear at the end of an author group. The collaboration name will appear centered in parentheses. You may have multiple author groups, each with its own `\collaboration`. Because collaborations don't normally have affiliations, one needs to follow the `\collaboration` with `\noaffiliation`.

6.3.2 Footnotes for authors, collaborations, affiliations or title

Often one wants to specify additional information associated with an author, collaboration, or affiliation such as an e-mail address, an alternate affiliation, or some other ancillary information. This package introduces several new macros just for this purpose. They are:

- `\email[<optional text>]{<e-mail address>}`
- `\homepage[<optional text>]{<URL>}`
- `\altaffiliation[<optional text>]{<affiliation>}`
- `\thanks{<miscellaneous text>}`

In the first three, the *optional text* will be prepended before the actual information specified in the required argument. `\email` and `\homepage` each have a default text for their optional arguments (‘Electronic address:’ and ‘URL:’ respectively). The `\thanks` macro should only be used if one of the other three do not apply. Any author name can have multiple instances of these four commands. Note that unlike the `\affiliation` macro, these macros only apply to the `\author` that directly precedes it. Any `\affiliation` *must* follow the other author-specific macros. A typical usage might be as follows:

```
% \author{Bugs Bunny}
% \email[E-mail me at: ]{bugs@looney.com}
% \homepage[Visit: ]{http://looney.com/}
% \altaffiliation[Permanent address: ]
%                               {Warner Brothers}
% \affiliation{Looney Tunes}
```

This would result in the footnote “E-mail me at: bugs@looney.com, Visit: http://looney.com/, Permanent address: Warner Brothers” being attached to Bugs Bunny. Note that:

- Only an e-mail address, URL, or affiliation should go in the required argument in the curly braces.
- The font is automatically taken care of.
- An explicit space is needed at the end of the optional text if one is desired in the output.
- Use the optional arguments to provide customized text only if there is a good reason to.

The `\collaboration`, `\affiliation`, or even `\title` can also have footnotes attached via these commands. If any ancillary data (`\thanks`, `\email`, `\homepage`, or `\altaffiliation`) are given in the wrong context (e.g., before any `\title`, `\author`, `\collaboration`, or `\affiliation` command has been given), then a warning is given in the \TeX log, and the command is ignored.

Duplicate sets of ancillary data are merged, giving rise to a single shared footnote. However, this only applies if the ancillary data are identical: even the order of the commands specifying the data must be identical. Thus, for example, two authors can share a single footnote indicating a group e-mail address.

Duplicate `\affiliation` commands may be given in the course of the front matter, without the danger of producing extraneous affiliations on the title page. However, ancillary data should be specified for only the first instance of any particular institution’s `\affiliation` command; a later instance with different ancillary data will result in a warning in the \TeX log.

It is preferable to arrange authors into sets. Within each set all the authors share the same group of affiliations. For each author, give the `\author` (and appropriate ancillary data), then follow this author group with the needed group of `\affiliation` commands.

If affiliations have been listed before the first `\author` macro to ensure a particular ordering, be sure that any later `\affiliation` command for the given institution is an exact copy of the first, and also ensure that no ancillary data is given in these later instances.

A journal may determine the placement of these ancillary information footnotes. One journal may put all such footnotes at the start of the bibliography while another journal may display them on the first page, as a footnote. One can override a journal style's default behavior by specifying explicitly the class option `bibnotes` (puts the footnotes at the start of the bibliography) or `nobibnotes` (puts them on the first page).

6.3.3 Specifying first names and surnames

Many authors have names in which either the surname appears first or in which the surname is made up of more than one name. To ensure that such names are accurately captured for indexing and other purposes, the `\surname` macro should be used to indicate which portion of a name is the surname. Similarly, there is a `\firstname` macro as well, although usage of `\surname` should be sufficient. If an author's surname is a single name and written last, it is not necessary to use these macros. These macros do nothing but indicate how a name should be indexed. Here are some examples;

```
% \author{Andrew \surname{Lloyd Weber}}
% \author{\surname{Mao} Tse-Tung}
```

6.4 The abstract

An abstract for a paper is specified by using the `abstract` environment:

```
% \begin{abstract}
% Text of abstract
% \end{abstract}
```

Note that with this package, the abstract must be specified before the `\maketitle` command, and there is no need to embed it in an explicit minipage environment.

6.5 PACS codes

Some authors are asked to supply suggested PACS codes with their submissions. The `\pacs` macro is provided as a way to do this:

```
\pacs{23.23.+x, 56.65.Dy}
```

The actual display of the PACS numbers below the abstract is controlled by two class options: `showpacs` and `noshowpacs`. In particular, this is now independent of the `preprint` option. `showpacs` must be explicitly included in the class options to display the PACS codes.

6.6 Keywords

A `\keywords` macro may also be used to indicate keywords for the article.

```
\keywords{nuclear form; yrast level}
```

This will be displayed below the abstract and PACS (if supplied). Like PACS codes, the actual display of the the keywords is controlled by two classoptions: `showkeys` and `noshowkeys`. An explicit `showkeys` must be included in the `\documentclass` line to display the keywords.

6.7 Institutional report numbers

Institutional report numbers can be specified using the `\preprint` macro. These will be displayed in the upper lefthand corner of the first page. Multiple `\preprint` macros may be supplied (space is limited though, so only three or less may actually fit).

6.8 maketitle

After specifying the title, authors, affiliations, abstract, PACS codes, and report numbers, the final step for formatting the front matter of the manuscript is to issue the `\maketitle` command:

```
\maketitle
```

This command must follow all of the macros listed above. The macro will format the front matter in accordance with the various class options that were specified in the `\documentclass` line (either implicitly through defaults or explicitly).

7 Compatability with L^AT_EX's Required Packages

Certain packages, usually ones written by members of the L^AT_EX Project itself, have been designated “required” and are distributed as part of standard L^AT_EX. These packages have been placed in a privileged position vis á vis the L^AT_EX kernel in that they override the definitions of certain kernel macros.

The `ltxfront` package will be incompatible with any package that redefines any of the kernel macros that `ltxfront` patches—if that package is loaded *after* `ltxfront`.

Hereinafter follows some notes on specific L^AT_EX packages.

8 Implementation of package

8.1 Beginning of the package DOCSTRIP module

```
224 %<*package>
225 \def\package@name{ltxfront}%
```



```

226 \expandafter\PackageInfo\expandafter{\package@name}{%
227 Title page macros for \protect\LaTeXe,
228 by A. Ogawa (arthur_ogawa at sbcglobal.net)%
229 }%

```

8.2 Prerequisites

This package requires the use of the ltxutil package.

```

230 \let\class@name\package@name
231 \RequirePackage{ltxutil}%
232 %</package>

```

End of the preliminary portion of the package code.

8.3 Options

Package options are treated in this portion of the dtx file. This portion is guarded by the `options docstrip` code so that it can be merged into a larger package gracefully.

```

233 %<*options>

```

Package option turns on diagnostics that trace its operation. `\frontmatterverbose@sw` is set false by default: we do not elect to monitor the workings of these procedures.

```

234 \DeclareOption{frontmatterverbose}{\@booleantrue\frontmatterverbose@sw}%
235 \@booleanfalse\frontmatterverbose@sw

```

Package option inactivates its syntax, for testing purposes.

```

236 \DeclareOption{inactive}{\@booleanfalse\frontmatter@syntax@sw}%
237 \@booleantrue\frontmatter@syntax@sw

```

`\runinaddress@sw` The flag `\runinaddress@sw` signifies that author addresses are to be set on the same line with the author.

The `runinaddress` option is the only one that sets `\runinaddress@sw` to true.

FIXME: this option pertains to cases where `\groupauthors@sw` is true, but is independant of `\@affils@sw`. So, it should be possible to assert both `runinaddress` and `unsortedaddress` as well as each separately.

```

238 \@booleanfalse\runinaddress@sw

```

`\@affils@sw` If `\@affils@sw` is false, an address is never recognised as “new” and is therefore always entered into the affiliation list, stopping groups of authors at the same address being consolidated into the same list: the address will be printed the same number of times it is entered.

The `unsortedaddress` option is the only one that sets `\@affils@sw` to false.

```

239 \@booleantrue\@affils@sw

```

`\groupauthors@sw` The flag `\groupauthors@sw` signifies that authors are to be grouped, affecting the meaning of `\@author@present`.

Clients will want to set `\groupauthors@sw` true if they want grouped addresses or either of the following variants: for unsorted addresses: set `\@affils@sw` false; for run-in addresses, set `\runinaddress@sw` true.

```
240 \@booleanfalse\groupauthors@sw
```

groupedaddress If we take the **groupedaddress** option as the default, then we can look upon the **superscriptaddress** option as simply turning `\groupauthors@sw` to `\false@sw`. **groupedaddress**, the default in APS journals, groups authors above a common address.

```
241 \DeclareOption{groupedaddress}{\clo@groupedaddress}%
242 \def\clo@groupedaddress{%
243   \@booleantrue\groupauthors@sw
244   \@booleantrue\@affils@sw
245   \@booleanfalse\runinaddress@sw
246 }%
```

unsortedaddress **unsortedaddress** is similar to **groupedaddress**, but turns off `\@affils@sw`, with the result that each address that is entered will be printed.

```
247 \DeclareOption{unsortedaddress}{\clo@unsortedaddress}%
248 \def\clo@unsortedaddress{%
249   \@booleantrue\groupauthors@sw
250   \@booleanfalse\@affils@sw
251   \@booleanfalse\runinaddress@sw
252 }%
```

runinaddress **runinaddress** is similar to **groupedaddress**, with the addition of the Boolean `\runinaddress@sw`, which causes the authors associated with a particular address group to be formatted in a paragraph instead of on separate lines.

```
253 \DeclareOption{runinaddress}{\clo@runinaddress}%
254 \def\clo@runinaddress{%
255   \@booleantrue\groupauthors@sw
256   \@booleantrue\@affils@sw
257   \@booleantrue\runinaddress@sw
258 }%
```

superscriptaddress **superscriptaddress** presents author affiliations as superscripts. Authors with like affiliations share the same superscript.

FIXME: if `\groupauthors@sw` is false, would not `\@affils@sw` be a don't care?

```
259 \DeclareOption{superscriptaddress}{\clo@superscriptaddress}%
260 \def\clo@superscriptaddress{%
261   \@booleanfalse\groupauthors@sw
262   \@booleantrue\@affils@sw
263   \@booleanfalse\runinaddress@sw
264 }%
```

```
265 %</options>
```

8.4 Process package options

```
266 %<*package>
267 \DeclareOption*{\OptionNotUsed}%
268 \ProcessOptions*
```

269 %</package>

9 Kernel of Front Matter

Here begins the kernel of the `frontmatter` package.

270 %<*kernel>

This package implements a new syntax for the title page of an article.

Special acknowledgment: this package uses concepts pioneered and first realized by William Baxter (mailto:web at superscript.com) in his SuperScript line of commercial typesetting tools, and which are used here with his permission.

These macros were first coded by David P. Carlisle for the American Physical society in the late 1990s as part of the development of REVTeX4. That development work was taken over by Arthur Ogawa, who is the author of this package.

9.1 Initialization

`\frontmatter@init` The `\frontmatter@init` procedure sets up all the registers for processing the title page. At present, this is done once, at `\class@documenthook` time. If multiple title pages are to be processed within a job, the initialization must be done for each.

271 \appdef\class@documenthook{\frontmatter@init}%

272 \let\frontmatter@init\empty

9.2 The title command

`\title` The author uses `\title` to specify the title. As in the AMS classes, `\title` has an optional argument specifying a short form for use in running heads.

`\do@title`

Once the `\title` is given, you can specify any combination of `\thanks`, `\email`, `\homepage`, and `\altaffiliation` commands, applying to the title of the document.

Compatibility note: as with all of the standard L^AT_EX commands that we override, we make here a private definition and later switch it in if so required.

273 \newcommand\frontmatter@title[2][]{%

274 \def\@title{#2}%

275 \def\@shorttitle{#1}%

276 \let\@AF@join\@title@join

277 }%

`\@title` The arguments to `\title` are saved in these internal macros, which are set up to produce a warning if `\title` has not been used before `\maketitle`.

`\@shorttitle`

Extensibility note: by using `\frontmatter@init` as the initialization procedure, we open the possibility of more than one title page per document.

278 \appdef\frontmatter@init{%

279 \def\@title{\class@warn{No title}}%

280 \let\@shorttitle\empty

281 \let\@title@aux\@title@aux@cleared

282 }%

```

\@title@join
\@title@join@ 283 \def\@title@join{\expandafter\@title@join@\@title@aux}%
\@title@aux@cleared 284 \def\@title@join@#1#2{%
285 \def\@title@aux{{\@join{\@separator}{#1}{#2}}}%
286 }%
287 \def\@title@aux@cleared{{}}%

```

9.3 The author, affiliation, and related commands

`\c@affil` `\c@affil` stores the affiliation numbers used for the superscript marks. The `\c@collab` `\newcounter` command defines `\theaffil`, which we never use: this counter is evaluated solely via `\the`.

`\c@collab` stores the collaboration numbers. The `\newcounter` command defines `\thecollab`. As with `\c@affil`, we never use `\thecollab`; only `\the` `\c@collab`.

Each counter must be cleared before frontmatter can be processed.

```

288 \newcounter{affil}%
289 \newcounter{collab}%
290 \appdef\frontmatter@init{%
291 \c@affil\z@
292 \c@collab\z@
293 }%

```

9.3.1 Commands for author or collaboration

`\author` Each author is given in a *separate* `\author` command. This is similar to the AMS classes, but the AMS also try to support the `article` class's `\and` command for putting multiple authors in one `\author` command. This package, however, does not support the `\and` command.

When the `\author` command is encountered, the previous author, author group, affiliation, and affiliation group are at an end. This procedure moves the previous author to the author group (`\move@AU`), moves the previous affiliation to the affiliation group (`\move@AF`), and terminates the previous author/affiliation group (`\move@AUAF`) as the case may require.

Compatibility note: as with all of the standard \LaTeX commands that we override, we make here a private definition and later switch it in if so required.

```

294 \newcommand\frontmatter@author{% implicit #1
295 \@author@def{}}% implicit #2
296 }%

```

`\collaboration` Specify the collaboration (given after a group of authors).

This procedure does exactly what `\author` does, and sets a flag signifying that the `\collaboration` command was given.

Note: earlier versions attempted to ignore the collaboration command if it was considered inappropriate. We must not do this, however, because it throws the state machine out of kilter.

```

297 \def\collaboration{% implicit #1

```

```

298 \@author@def{\@booleantrue\collaboration@sw}% implicit #2
299 }%
300 \appdef\frontmatter@init{%
301 \@booleanfalse\collaboration@sw
302 }%

\@author@init Here are all the access procedures for the author data structure.
\@author@cleared We define a flag value for \@author(private), a procedure \@author@gobble
\@authorclear@sw to read author data without any effect, a procedure for setting \@author
\@author@def to the flag value (\@author@init), a Boolean to test against the flag value
\@author@join@ (\@authorclear@sw), and a procedure to add new ancillary data to the author.
\@author@join Note that expanding the functionality of the \collaboration command en-
tailed changing the data structures, because now all authors must remember the
collaboration they belong to. This change affects procedures \@author@cleared
and \@author@gobble.

303 \def\@author@cleared{\}\}\}%
304 \def\@author@gobble#1#2#3{\}%
305 \def\@author@init{%
306 \let\@author\@author@cleared
307 \@booleanfalse\collaboration@sw
308 }%
309 \def\@authorclear@sw{\@ifx{\@author\@author@cleared}}%
310 \appdef\frontmatter@init{%
311 \@author@init
312 }%

313 \def\@author@def#1#2{\}%
314 \frontmatterverbose@sw{\typeout{\string\author\space\string\collaboration}}{\}%
315 \move@AU\move@AF\move@AUAF
316 \let\@AF@join\@author@join
317 #1%
318 \def\@author{{#2}}{\}%
319 }%
320 \def\@author@join@#1#2#3{\}%
321 \def\@author{{#1}}{\@join{\@separator}{#2}{#3}}{\}%
322 }%
323 \def\@author@join{\expandafter\@author@join@\@author}%

\move@AU The \move@AU procedure moves the most recent author to the current author group
\add@AUCO@grp \AU@grp, or the most recent collaboration to the collaboration group \CO@grp. If
we recently did a \@author@init, this is a no-op.

To accommodate the expanded syntax of \collaboration, we add a new field
to those associated with an author (collaborator), namely the value of the collab-
oration counter.

324 \def\move@AU{%
325 \@authorclear@sw{\}%
326 \collaboration@sw{\}%
327 \advance\c@collab\@ne
328 \@argswap{\CO@grp\CO@opr}%

```

```

329 }{%
330   \@argswap{\AU@grp\AU@opr}%
331 }%
332 {%
333   \expandafter\@argswap@val
334   \expandafter{\@author}%
335   {\expandafter\@argswap@val\expandafter{\the\c@collab}{\add@AUCO@grp}}%
336 }%
337 }%
338 \@author@init
339 }%

```

The procedure `\add@AUCO@grp` adds to the specified group #3 using the given intercolated operator #4, with arguments {#1} and #2, where the first argument is the collaboration number, the second is the author name, and the third the joined attributes of the author. For example, `\move@AU` could finally execute: `\appdef \AU@grp {\AU@opr{1}}{A. Author}{}}`.

```

340 \def\add@AUCO@grp#1#2#3#4{%
341   \appdef#3{#4{#1}#2}%
342   \frontmatterverbose@sw{\say#3}{}%
343 }%

```

`\@author@finish` We define a procedure to terminate author/affiliation parsing just before the title block is formatted. We detect the case where an author group is not followed by an affiliation group.

We first finish off any author- or affiliation groups in progress. Next, we detect the case where there is an author group or a collaboration group in progress, but no affiliation group. If so, we emit a diagnostic message and act as if a `\noaffiliation` command had been given. In any case, we finish off any author/affiliation pair that may remain. Formatting of the title block may now proceed.

```

344 \def\@author@finish{%
345   \frontmatterverbose@sw{\typeout{\string\@author@finish}}}%
346   \move@AU\move@AF
347   \ifx{\AU@grp\@empty}{%
348     \ifx{\CO@grp\@empty}%
349   }{%
350     \false@sw
351   }%
352   }{%
353     \ifx{\AF@grp\@empty}{%
354       \begingroup
355       \let\href\@secondoftwo
356       \let\AU@opr\@secondofthree
357       \let\CO@opr\@secondofthree
358       \let\footnote\@gobble
359       \ifx{\CO@grp\@empty}{%
360         \class@warn{Assuming \string\noaffiliation\space for authors}%
361         \frontmatterverbose@sw{\say\AU@grp}%

```

```

362    }{%
363    \class@warn{Assuming \string\noaffiliation\space for collaboration}%
364    \frontmatterverbose@sw{\say\C0@grp}{}%
365    }%
366    \endgroup
367    \@affil@none\move@AF
368  }{%
369  }%
370  \move@AUAF
371 }%
372 \def\@secondofthree#1#2#3{#2}%

```

`\@join` The procedure `\@join` inserts a separator between two tokens, or, if the first token is nil, elides both that token and the separator.

```

373 \def\@join#1#2#3{%
374   \@ifempty{#2}{#3}{#2#1#3}%
375 }%
376 \def\@separator{;\space}%

```

`\surname` No-op to allow better post-processing of the file.

`\firstname`

```

377 \let\surname\@firstofone
378 \let\firstname\@firstofone

```

`\and` The original L^AT_EX idea of using one `\author` command to capture all authors and their address just doesn't work with multiple authors possibly sharing addresses, so in this class disable `\and`.

```

379 \newcommand\frontmatter@and{\class@err{\protect\and\space is not supported}}

```

9.3.2 Commands for affiliation

`\affiliation` After each group of authors with the same address, give that address in `\affiliation`. If later in the list you have an author with the address of an earlier author, repeat the `\affiliation` command: the system will detect the equivalence and (if using the `superscriptaddress` option) only print the affiliation once, reusing the superscript marker.

When the `\affiliation` command is encountered, the current author and author group (if any) are at an end. Also, the current affiliation is at an end.

FIXME: changes to catcode required elsewhere now?

```

380 \def\cat@comma@active{\catcode'\,\active}%
381 {\cat@comma@active\gdef,{\active@comma}}%
382 \def\active@comma{,\penalty-300\relax}%
383 \newcommand\affiliation{%
384   \frontmatterverbose@sw{\typeout{\string\affiliation}}{%
385     \move@AU\move@AF
386     \begingroup
387     \cat@comma@active
388     \@affiliation
389   }%

```

```

390 \def\@affiliation#1{%
391   \endgroup
392   \let\@AF@join\@affil@join
393   \@affil@def{#1}%
394 }%

```

\noaffiliation User-level command **\noaffiliation** signifies that the current group of authors, or the current collaboration, has *no* affiliation.

This is implemented by acting as if the **\affiliation** command has been given, and using a flag value of **{\relax}**, which adds an element to the affiliation group of this author, albeit a nil one (**\AFF@opr {\relax} {}**).

Note that this procedure does substantially the same as **\@author@finish**. (the latter, If it does not bail out altogether, differs chiefly in providing diagnostics).

```

395 \newcommand\frontmatter@noaffiliation{%
396   \frontmatterverbose@sw{\typeout{\string\noaffiliation}}{}%
397   \move@AU\move@AF

```

In **\@author@finish**, there is code testing if an effective **\noaffiliation** should be executed now. Here, we do so in any case.

```

398   \@affil@none\move@AF
399   \move@AUAF
400 }%
401 \def\blankaffiliation{ }%

```

\@affil@cleared Here are all the access procedures for the affiliation data structure. Note the similarity to those of the **\@author** data structure.

\@affil@init We define a flag value for **\@affil** (private), a procedure for setting **\@affil** to the flag value (**\@affil@init**), a Boolean to test against the flag value **\@affil@none** (**\@affilclear@sw**), a procedure **\@affil@def** to load a value into the structure, and a procedure to add new ancillary data to the affiliation.

```

\@affil@join@ 402 \def\@affil@cleared{ }{}%
\@affil@join 403 \def\@affil@nil{ {\relax} }{}%
404 \appdef\frontmatter@init{%
405   \@affil@init
406 }%
407 \def\@affil@none{%
408   \let\@affil\@affil@nil
409 }%
410 \def\@affil@init{%
411   \let\@affil\@affil@cleared
412 }%
413 \def\@affilclear@sw{\@ifx{\@affil\@affil@cleared}}%
414 \def\@affil@def#1{%
415   \def\@affil{#1}{}%
416 }%
417 \def\@affil@join@#1#2#3{%
418   \def\@affil{#1}{\@join{\@separator}{#2}{#3}}%
419 }%

```



```
420 \def\@affil@join{\expandafter\@affil@join@\@affil}%
```

\move@AF Move the most recent affiliation to the affiliation group. If we recently did a **\@affil@init**, this is a no-op.

Set the **\temp@sw** to false, then execute the affiliation list (**\@AFF@list**) with the intercolated operator set to **\@affil@match** and with **\@tempa** holding the first component of **\@affil**, the current affiliation, which is to be matched.

If the current affiliation has been seen before, then by side effect **\temp@sw** will be set to true, **\@tempc** will be set to the matching affiliation number, and **\@tempd** will be set to the affiliation's ancillary data. The Boolean **\@affils@sw** being false prevents this test from ever returning a “true” result.

This procedure uses **\@tempa** and sets **\@tempc**, **\@tempd**, and **\temp@sw**.

```
421 \def\move@AF{%
422   \@affilclear@sw}{%
423   \@booleanfalse\temp@sw
424   \let\@tempd\@empty
425   \@affils@sw{%
426     \expandafter\@affil@addr\def\expandafter\@tempa\@affil
427     \def\AFF@opr{\@affil@match\@tempa}%
428     \@AFF@list
429   }{\}\temp@sw
```

True clause: This affiliation has been seen before. If ancillary data for the affiliation have been given, but are not identical to those seen before, give a warning.

```
430   {%
431     \expandafter\@affil@aux\def\expandafter\@tempb\@affil
432     \@ifx{\@tempb\@empty}{\}%
433     \@ifx{\@tempb\@tempd}{\}%
434     \class@warn{%
435       Ancillary information for \@tempa\space must not be different!
436       Please put all of it on the first instance%
437     }%
438   }%
439 }%
440 }%
```

False clause: This affiliation is a new one: increment the affiliation counter to get a unique affiliation ID and append the new ID, collaboration number, address, and auxiliary information to the list **\@AFF@list**.

Note that, with the expanded syntax of **\collaboration**, we need to label each address with its associated collaboration.

Note also that the **\noaffiliation** case is handled by recognizing the flag value **\@affil@nil**.

```
441   {%
442     \@ifx{\@affil\@affil@nil}{%
443       \def\@tempc{0}%
444       \@argswap@val{0}%
445     }{%
446       \advance\c@affil\@ne
```

```

447 \expandafter\def\expandafter\@tempc\expandafter{\the\c@affil}%
448 \expandafter\@argswap@val\expandafter{\the\c@affil}%
449 }%
450 {%
451 \expandafter\@argswap@val\expandafter{\the\c@collab}{%
452 \expandafter\@argswap@val\expandafter{\@affil}{%
453 \add@list@val@val@val\@AFF@list\AFF@opr
454 }%
455 }%
456 }%
457 }%

```

In either case, append this affiliation number to the `\AF@grp`, the affiliation group of the current author group. (It will later be considered for the `\@AFG@list`.) Then assign the flag value to `\@affil` that signifies it has been cleared.

```

458 \appdef@eval\AF@grp\@tempc
459 \frontmatterverbose@sw{\say\AF@grp}{}%
460 \@affil@init
461 }%
462 }%
463 \def\@affil@addr@def#1#2#3{%
464 \def#1{#2}%
465 }%
466 \def\@affil@aux@def#1#2#3{%
467 \def#1{#3}%
468 }%

```

Procedure `\add@list@val@val@val` appends to the given list #1 using the given intercollated operator #2, with arguments #5 (affiliation ID) and #4 (collaboration ID) delimited by braces, and #3 bare. In the end, `\move@AF` may execute something like `\appdef \@AFF@list \AFF@opr {1} {3} {My Institution} {thanks}`.

```

469 \def\add@list@val@val@val#1#2#3#4#5{%
470 \appdef#1{#2{#5}{#4}#3}%
471 \frontmatterverbose@sw{\say#1}{}%
472 }%

```

`\@affil@match` The procedure `\@affil@match` is the definition for `\AFF@opr`, the intercollated operator for `\@AFF@list`, when adding a new affiliation: it seeks a match with any earlier affiliation. When the affiliation list is executed, this procedure tests each entry against the ‘new’ affiliation (which has been stored in `\@tempa`) and its associated collaboration number (in `\@tempb`).

If `\groupauthors@sw` is true, then we require the collaboration ID to match, otherwise there is no such requirement, as is appropriate for the `superscriptaddress` class option.

Uses `\temp@sw`, `\@tempc`, and `\@tempd` to communicate back: if it returns `\temp@sw` true, a match was found. Then `\@tempc` will be the affiliation ID of the matching entry and `\@tempd` will be the auxiliary information of the matching entry.

```

473 \def\@affil@match#1#2#3#4#5{%

```

```

474 \temp@sw{%
475 \def\@tempifx{#4}%
476 \@ifx{\@tempifx#1}{%
477 \groupauthors@sw{%
478 \ifnum{#3=\c@collab}{%
479 \true@sw
480 }{%
481 \false@sw
482 }%
483 }{%
484 \true@sw
485 }%
486 }{%
487 \false@sw
488 }%
489 {%
490 \@booleantrue\temp@sw
491 \def\@tempc{#2}%
492 \def\@tempd{#5}%
493 }{%
494 }%
495 }%
496 }%

```

\move@AUAF Append \AF@grp, \AU@grp, and \CO@grp to \@AAC@list, append \CO@grp to \@AFG@list, and merge any new \AF@grp to \@AFG@list.

The entire procedure is predicated on something non-trivial to move.

If both author group \AU@grp and affiliation group \AF@grp are nil, bail out.

No, try that again:

If we have seen any affiliations (\AF@grp is not nil), then it is time to move the current affiliation group and author group to \@AAC@list. If not, we are picking up authors into an author group, and we should bail out.

To extend this scheme to the new \collaboration abilities, we must append an affiliation \AF@opr to \@AAC@list also in the case where there was no affiliation specified (e.g., \noaffiliation). This affiliation will be a nil affiliation: \AF@opr{{0}}.

FIXME: only one of \CO@grp or \AU@grp is non-empty at this point, but this code does not appear to recognize this fact!

```

497 \def\move@AUAF{%
498 \frontmatterverbose@sw{\say\AU@grp\say\AF@grp\say\CO@grp}{}%
499 \@ifx{\AF@grp\@empty}{%
500 \ifx{\@empty\CO@grp}{%

```

Both \AF@grp and \CO@grp are empty: nothing to do. But what if \AU@grp is not empty?

```

501 }{%

```

Append the nil \AF@opr to \@AAC@list.

```

502 \appdef \@AAC@list{\AF@opr{{0}}}%

```

Append the collaboration group to the \@AAC@list; no intercollated operator need be added, because we already have \CO@opr.

```

503     \appdef@e    \@AAC@list{\CO@grp}%
504     \appdef@e    \@AFG@list{\CO@grp}%
505     \let\CO@grp\@empty
506   }%
507 }%

```

Append current affiliation group (expansion of \AF@grp) to the author/affiliation list (\@AAC@list), using \AF@opr as the intercollated operator; also append the current authors (\AU@grp).

```

508     \appdef      \@AAC@list{\AF@opr}%
509     \appdef@eval \@AAC@list{\AF@grp}%
510     \appdef@e    \@AAC@list{\AU@grp}%

```

Determine if either \AU@grp or \CO@grp is non-empty.

```

511     \@ifx{\@empty\AU@grp}{%
512       \@ifx{\@empty\CO@grp}%
513     }{%
514       \false@sw
515     }%

```

At this point, there is a Boolean in T_EX's scanner; it will parse the following two brace-delimited sequences and select one of them.

```

516   {%

```

This branch is executed if and only if both \AU@grp and \CO@grp are empty.

```

517   }%

```

There was either a \author or a \collaboration command. Append the current affiliation group to \@AFG@list, (only if it is not already there) using \AFG@opr as the intercollated operator.

Note that \@AFG@list is a list of *unique* affiliation *groups*, and building it entails an N^2 computation.

```

518     \@booleanfalse\temp@sw
519     \def\AFG@opr{x@match\AF@grp}%
520     \let\CO@opr\@author@gobble
521     \@AFG@list
522     \temp@sw}{%
523       \appdef      \@AFG@list{\AFG@opr}%
524       \appdef@eval \@AFG@list{\AF@grp}%
525     }%

```

If the collaboration \CO@grp is not empty, we append it to the \@AFG@list and to the \@AAC@list.

```

526     \@ifx{\@empty\CO@grp}{%
527       \appdef@e    \@AAC@list{\CO@grp}%
528       \appdef@e    \@AFG@list{\CO@grp}%
529       \let\CO@grp\@empty
530     }%
531   }%

```

Finally, null out the macros holding the author group `\AU@grp`, affiliation group `\AF@grp`, and collaboration group `\CO@grp`.

```

532 \let\CO@grp\@empty
533 \let\AU@grp\@empty
534 \let\AF@grp\@empty
535 }%
536 \frontmatterverbose@sw{\say\@AAC@list\say\@AFG@list}{}%
537 }%

```

`\AU@grp` The control sequence name `\AU@grp` accumulates consecutive `\author` entries (with `\AU@opr` as the intercollated operator) and `\collaboration` entries (with `\CO@opr` as the intercollated operator). Ultimately, its contents are appended to the author/affiliation list `\@AAC@list` and to the list of affiliation groups, `\@AFG@list`. It must be initialized to `\@empty`.

Note on `\AU@opr` and `\CO@opr`: it is essential to treat these two operators to the greatest extent possible on an equal footing. Therefore we invariably assign values to the pair of them within the same procedure.

The macro `\AF@grp` accumulates affiliation IDs into an affiliation group. It must be empty at the beginning of the frontmatter.

The `\@AAC@list` macro accumulates authors (using `\AU@opr` as the intercollated operator), collaborations (using `\CO@opr` as the intercollated operator), and affiliations (using `\AF@opr` as the intercollated operator).

It must be empty at the beginning of the frontmatter.

The macro `\@AFG@list` accumulates affiliation groups, with `\AFG@opr` as the intercollated operator, and collaborations, with no intercollated operator. This token list is employed when and only when `groupedaddress` is in effect.

The macro `\@AFF@list` accumulates the list of affiliations with `\AFF@opr` as the intercollated operator. It must be empty at the beginning of the frontmatter.

Each `\affiliation` command in the document contributes to this list, as long as the argument of that instance of the command is “new”.

Each entry in this list consists of the `\AFF@opr` intercollated operator followed by three brace-delimited tokens, representing, in order:

1. the affiliation’s unique ID, a number increasing monotonically for each new entry,
2. the optional argument of the `\affiliation` command, the footnote to the affiliation, and
3. the text of the affiliation.

At various junctures in the code, the control sequence name `\AFF@opr` assumes the meaning of `\@affil@group`, `\affil@script`, or is defined to expand to `\@affil@match\@tempa`, and the list `\@AFF@list` is expanded.

For each of these lists, here is the syntax of an element and the usage of the associated operator:

```

%\@AFF@list \AFF@opr{\affiliation ID}{\collaboration ID}{\address}{\auxiliary info} \frontmatter
%\@AFG@list \AFG@opr{\affiliation ID}..\affiliation ID} \frontmatter@author@produce@group
%\@AAC@list \AF@opr{\affiliation ID}..\affiliation ID} (\AU@opr\CO@opr){\collaboration ID}{
%
%\AFF@opr \@affil@match\@tempa \@affil@script \@affil@group
%\AFG@opr \affils@present@group \x@match\AF@grp
%\AF@opr \@gobble \@affilID@def \@affilID@count\AF@temp\@tempcnta \@affilID@match\AF@temp
%\AU@opr \@secondofthree \@author@count\@tempcnta \@author@present \@author@gobble \@author@count
%\CO@opr \@secondofthree \@collaboration@count\AU@temp\@tempcnta \@collaboration@present\AU@temp
%
%\CO@opr\@author@cleared
%

538 \appdef\frontmatter@init{%
539 \let\AU@grp\@empty
540 \let\CO@grp\@empty
541 \let\AF@grp\@empty
542 \let\@AAC@list\@empty
543 \let\@AFG@list\@empty
544 \let\@AFF@list\@empty
545 }%

```

`\@AF@join` The `\csname \@AF@join` is a procedure used within `\email`, `\homepage`, `\thanks`, and `\altaffiliation`. When such a command appears after an `\author`, `\collaboration`, or `\affiliation` command, the `\@AF@join` procedure appends the argument given to the appropriate macro. Its default is to give an error message, since these commands are legal only within the particular context mentioned.

```

546 \appdef\frontmatter@init{%
547 \let\@AF@join\@AF@join@error
548 }%
549 \def\@AF@join@error#1{%
550 \class@warn{%
551 \string\email, \string\homepage, \string\thanks, or \string\altaffiliation\space
552 appears in wrong context.
553 }%
554 }%

```

9.3.3 Commands for auxiliary information

`\email` Just tacks the email address on to the current author or affiliation.

```

555 \def\sanitize@url{%
556 \@makeother\%
557 \@makeother\~
558 \@makeother\_
559 }%
560 \newcommand*\email[1][]{\begingroup\sanitize@url\@email{#1}}%
561 \def\@email#1#2{%
562 \endgroup
563 \@AF@join{#1\href{mailto:#2}{#2}}%
564 }%

```

`\homepage` Just tacks the URL on to the current author or affiliation. Note: group opened in `\homepage` is closed in `\@homepage`.

```
565 \newcommand*\homepage[1] []{\begingroup\sanitize@url\@homepage{#1}}%
566 \def\@homepage#1#2{%
567   \endgroup
568   \@AF@join{#1\href{#2}{#2}}%
569 }%
```

`\href` The document may load a package that defines either of these commands; if not, we give a default meaning.

```
570 \appdef\class@documenthook{%
571   \providecommand\href[1] {}%
572 }%
```

`\thanks` The operative version of `\thanks` appends an item to `\@author`, or `\@affil`'s auxiliary data.

```
573 \def\frontmatter@thanks{% implicit #1
574   \@AF@join
575 }%
```

`\altaffiliation` Implemented more or less like `\thanks` but shares the affiliation counter. Optional argument may be used to give explanatory text eg 'currently staying at' This will be placed before the address, if used in a footnote.

```
576 \newcommand*\altaffiliation[2] []{%
577   \@AF@join{#1#2}%
578 }%
```

9.3.4 Procedures for author, collaboration, and affiliation

Macros that list off, say, authors, and which require punctuation, like "A, B, and C", will use `\set@listcomma@list`, `\set@listcomma@count`, `\@listand`, and `\@listcomma`. These macros use the `\@tempcnta` register to keep track of how many items remain to be listed off.

At present, `\@author@present` will decrement that counter.

`\set@listcomma@list` Pop the author count for this collaboration.

`\set@listcomma@count` Note: by side effect, it assigns `\@listcomma`: for a list of length two, suppress comma addition.

```
579 \def\set@listcomma@list#1{%
580   \expandafter\@reset@ac\expandafter#1#1{0}\@reset@ac{%
581     \let\@listcomma\relax
582   }{%
583     \let\@listcomma\@listcomma@comma
584   }%
585 }%
586 \def\set@listcomma@count#1{%
587   \@ifnum{#1=\tw@}{%
588     \let\@listcomma\relax
```

```

589 }{%
590 \let\@listcomma\@listcomma@comma
591 }%
592 }%

```

Does the actual pop operation, then generates a Boolean which selects one of the two assignments for \@listcomma.

Note: this procedure sets \@tempcnta to reflect the number of items to list off.

```

593 \def\@reset@ac#1#2#3\@reset@ac{%
594 \def#1{#3}%
595 \@tempcnta#2\relax
596 \@ifnum{#2=\tw@}%
597 }%

```

\listand Might need extending with penalties etc.

Note: this procedure expects \@tempcnta to reflect the current number of items remaining to list off.

```

598 \def\@listand{\@ifnum{\@tempcnta=\tw@}{\andname\space}{}}%

```

\@listcomma This definition, with \@one puts a comma before and.

David Carlisle says: In UK English (at least) would have \tw@ here, which would then implement the convention of indicating conjunction with comma or “and”, but not both.

Note: this procedure expects \@tempcnta to reflect the current number of items remaining to list off.

```

599 \def\@listcomma@comma{\@ifnum{\@tempcnta>\@one}{,}{}}%
600 \def\@listcomma@comma@UK{\@ifnum{\@tempcnta>\tw@}{,}{}}%

```

\@collaboration@gobble This command will be the synonym of \CO@grp during the expansion of \@AAC@list, within \affils@present@groupexecution (in a groupedaddress situation).

```

601 \def\@collaboration@gobble#1#2#3{}%

```

\doauthor Main control over how authors are typeset.

#1 is loaded by \author

#2 is loaded by \email, \homepage, \altaffiliation, or \thanks

#3 is the superscript affiliation, if at all used.

First, the author name is formatted, followed by a comma, then come any marks relating to affiliation (if present), then come the homepage URL and email address, if any, with appropriate punctuation.

Here, as in \@affil@script, the parameter \affil@cutoff controls whether the argument #3 is produced as a superscript label connecting this author with its affiliation. (If there is only one affiliation on the title page, it makes sense to remove the superscript.)

Note that argument #3 must effectively execute either \aftergroup\true@sw or \aftergroup\false@sw (exactly once!). In the case of superscriptaddress, this is done when \@author@present@script invokes \doauthor with its third argument containing \@affil@present@script. Otherwise (e.g., groupedaddress),

`\doauthor` is invoked by `\@author@present@group` with its third argument containing `\@affil@present@group`.

```
602 \def\doauthor#1#2#3{%
603   \ignorespaces#1\unskip\@listcomma
604   \begingroup
605   #3%
```

At this point, we must have queued up a Boolean (either `\true@sw` or `\false@sw`).

```
606   \@ifempty{#2}{\endgroup{}}{\endgroup{\comma@space}}{\frontmatter@footnote{#2}}%
607   \space \@listand
608 }%
```

`\x@match` Procedure `\x@match` is used as an alias `\AFG@opr`, probing the list of affiliation groups and setting a Boolean if a match is found to `#1` (usually the current affiliation group).

Procedure `\y@match` is used as an alias to `\@TBN@opr`, probing the list of unique title block footnotes for a match to the footnote text: when the first match is found it sets a Boolean, defining `\@tempb` to the number of that footnote.

```
609 \def\x@match#1#2{%
610   \temp@sw{}{%
611     \def\@tempifx{#2}%
612     \@ifx{\@tempifx#1}{%
613       \@booleantrue\temp@sw
614     }{%
615     }%
616   }%
617 }%
618 \def\y@match#1#2#3{%
619   \temp@sw{}{%
620     \def\@tempifx{#3}%
621     \@ifx{\@tempifx#1}{%
622       \@booleantrue\temp@sw
623     }{\def\@tempb{#2}}%
624   }{%
625   }%
626 }%
627 }%
```

`\frontmatter@footnote` Used when typesetting a title block footnote. (Item 290: merge duplicates.)

Maintains a list of frontmatter footnotes along with associated device. Uniquifies each footnote by traversing the list and looking for a match to the footnote text. If found, define `\@tempb` to the corresponding footnote device, and typeset it with `\@footnotemark`. If never found, manually increment footnote counter, determine the corresponding footnote device, and add footnote text and device to the list of frontmatter footnotes.

The list `\@FMN@list` is processed later in the title block production.

Note that this method of making footnotes runs afoul of `hyperref`'s patches of the \LaTeX kernel. Therefore, we avoid trouble by refraining from using `\@footnotemark` and by creating our own hypertext links.

```

628 \def\frontmatter@footnote#1{%
629   \begingroup
630   \@booleanfalse\temp@sw
631   \def\@tempa{#1}%
632   \let\@tempb\empty
633   \def\@TBN@opr{\y@match\@tempa}%
634   \@FMN@list

```

By side effect, \@tempb holds the value of the footnote counter if This note has been seen before. Otherwise \temp@sw is false.

```

635   \temp@sw{%
636     \expandafter\frontmatter@footnotemark
637     \expandafter{\@tempb}%
638   }%

```

Execute \frontmatter@foot@mark, feeding it the value of the current footnote counter. This call requires two levels of pre-expansion to accomplish, the first to expand \csname, the second to evaluate \the.

```

639   \stepcounter\@mpfn
640   \expandafter\expandafter
641   \expandafter\frontmatter@foot@mark
642   \expandafter\expandafter
643   \expandafter{%
644     \expandafter \the\csname c@\@mpfn\endcsname
645     }{#1}%
646   }%
647 \endgroup
648 }%

```

Procedure \frontmatter@foot@mark lays down the footnote device (mark) and takes care of the footnote text. The latter merely involves queueing that text (along with its associated device) into \@FMN@list.

```

649 \def\frontmatter@foot@mark#1#2{%
650   \frontmatter@footnotemark{#1}%
651   \g@addto@macro\@FMN@list{\@TBN@opr{#1}{#2}}%
652 }%
653 \appdef\frontmatter@init{%
654   \global\let\@FMN@list\empty
655 }%

```

```

656 \def\frontmatter@footnotemark#1{%
657   \leavevmode
658   \ifhmode\edef\@x@sf{\the\spacefactor}\nobreak\fi
659   \begingroup
660     \hyper@linkstart {link}{\frontmatter.#1}%
661     \csname c@\@mpfn\endcsname#1\relax
662     \def\@thefnmark{\frontmatter@thefootnote}%
663     \makefnmark
664     \hyper@linkend
665   \endgroup
666   \ifhmode\spacefactor\@x@sf\fi

```

```
667 \relax
668 }%
```

9.4 The keywords command

`\keywords` Usual game, save text in a macro for processing by `\maketitle`.

```
\@keywords 669 \def\keywords#1{%
670   \aftermaketitle@chk{\keywords}%
671   \gdef\@keywords{#1}%
672 }%
673 \appdef\frontmatter@init{%
674   \let\@keywords\@empty
675 }%
```

9.5 The \date command and related commands

`\date` Use the `\date` command to specify the document date, the `\received` command to specify the date received, `\revised` for date revised, `\accepted` for date accepted, `\revised` and `\published` for date published. Normally only `\date` to be used by author, `\accepted` the remainder used only by editors.

`\published` DPC: As for `\keywords`, but this time don't flag a warning if there is no revision date specified.

`\@date` In each case the user-level command defines the value of a macro which buffers the data entered by the user. For instance, `\received` causes `\@received` to acquire a value. The optional argument allows the user to override the text that will be typeset along with the date; the default value of that text is itself a localized macro.

```
676 \newcommand*\frontmatter@date[2][\Dated@name]{\def\@date{#1#2}}%
677 \def\@date{}%
678 \newcommand*\received[2][\Received@name]{\def\@received{#1#2}}%
679 \def\@received{}%
680 \newcommand*\revised[2][\Revised@name]{\def\@revised{#1#2}}%
681 \def\@revised{}%
682 \newcommand*\accepted[2][\Accepted@name]{\def\@accepted{#1#2}}%
683 \def\@accepted{}%
684 \newcommand*\published[2][\Published@name]{\def\@published{#1#2}}%
685 \def\@published{}%
```

9.6 The pacs command

PACS, the Physics and Astronomy Classification Scheme.

`\pacs` As for `\keywords`

```
\@pacs 686 \def\pacs#1{%
687   \aftermaketitle@chk{\pacs}%
688   \gdef\@pacs{#1}%
689 }%
690 \appdef\frontmatter@init{%
```

```

691 \let\@pacs\@empty
692 }%

```

9.7 The `\preprint` command

```

693 \def\preprint#1{\gappdef\@preprint{\preprint{#1}}}%
694 \appdef\frontmatter@init{%
695 \let\@preprint\@empty
696 }%

```

9.8 The abstract environment

`\absbox`

```

697 \newbox\absbox

```

abstract Abstract, as in AMS classes, must be specified *before* `\maketitle`. It just saves everything up in `\absbox`. Note that the specifics of how the abstract is to be formatted are set by `\frontmatter@abstractwidth`, `\frontmatter@abstractheading`, and `\frontmatter@abstractfont`.

Here we wish to set the abstract into type but save it away in a box, much like the `\minipage` command does.

Note that the `\endabstract` portion of the environment begins with code that mostly duplicates `\endminipage`, but without the `\@iiparbox`. At the end, we simply transfer the contents of the `\minipage` into a box of our own.

However, we also have to end the gratuitous paragraph begun by `\minipage`. We ensure that no trace of that paragraph is left, by absorbing the `\parindent` box. Doing so destroys the paragraph entirely, except for the `\parskip` glue, and that morsel is pruned, because we are at the top of a page.

This mechanism is vulnerable, however, because anything placed into the horizontal list after the `\parindent` box will confound it. And that is exactly what happens under MikTeX: There seems to be an extension to the TeX standard operating here which inserts a `\special` at the beginning of every paragraph. (The mechanism is *not* based on `\everypar`.)

To accomodate this state of affairs, we have a new mechanism that offers an even more complete rewrite of `minipage`.

Note that an entry is made in the toc for the abstract; this has the side effect of creating a PDF bookmark for this element if the `hyperref` package is in effect.

```

698 \def\toclevel@abstract{1}%
699 \def\addcontents@abstract{%
700 \phantomsection
701 \expandafter\def\csname Parent0\endcsname{section*.2}%
702 \expandafter\@argswap@val\expandafter{\abstractname}{\addcontentsline{toc}{abstract}}%
703 }%
704 \newenvironment{frontmatter@abstract}{%
705 \aftermaketitle@chk{\begin{abstract}}%
706 \global\setbox\absbox\vbox\bgroup
707 \color@begingroup

```

```

708 \columnwidth\textwidth
709 \hsize\columnwidth
710 \@parboxrestore

```

The following line switches footnotes to the `mpfootnote` series. This action should rather be taken by `\frontmatter@abstractfont`, which can be customized. There is also an interaction with `\mini@note`.

```

711 \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
712 \let\@footnotetext\frontmatter@footnotetext
713 \minipagefootnote@init
714 \let\set@listindent\set@listindent@
715 \let\@listdepth\@mplistdepth \@mplistdepth\z@
716 \let\@environment{description}{\frontmatter@description}%
717 \@minipagerestore
718 \@setminipage
719 \frontmatter@abstractheading
720 \frontmatter@abstractfont
721 \let\footnote\mini@note
722 \expandafter\everypar\expandafter{\the\everypar\addcontents@abstract\everypar{}}%
723 }{%
724 \par
725 \unskip
726 \minipagefootnote@here
727 \@minipagefalse %% added 24 May 89
728 \color@endgroup
729 \egroup
730 }%

```

`\frontmatter@footnotetext` We reimplement `\@mpfootnotetext` under a new name (so as not to be overridden by the `hyperref` package) and extend it to accomodate hyperrefs.

Note that this procedure is very like `ltxutil`'s `\mp@footnotetext`, except that it uses `\frontmatter@makefntext` instead of `\@makefntext`.

```

731 \long\def\frontmatter@footnotetext#1{%
732 \minipagefootnote@pick
733 \set@footnotefont
734 \set@footnotewidth
735 \@parboxrestore
736 \protected@edef\@currentlabel{\csname p@\@mpfn\endcsname\@thefnmark}%
737 \color@begingroup
738 \frontmatter@makefntext{%
739 \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox\vadjust{\vskip\z@skip}%
740 }%
741 \color@endgroup
742 \minipagefootnote@drop
743 }%

```

`\ltx@no@footwarn`

```

744 \def\ltx@no@footnote{%
745 \let\ltx@xfootnote\ltx@no@xfootnote\let\ltx@yfootnote\ltx@no@yfootnote

```

```

746 \let\ltx@xfootmark\ltx@no@xfootmark\let\ltx@yfootmark\ltx@no@yfootmark
747 \let\ltx@xfoottext\ltx@no@xfoottext\let\ltx@yfoottext\ltx@no@yfoottext
748 }%
749 \def\ltx@no@xfootnote[#1]#2{\ltx@no@footwarn\footnote}%
750 \def\ltx@no@yfootnote#1{\ltx@no@footwarn\footnote}%
751 \def\ltx@no@xfootmark[#1]{\ltx@no@footwarn\footnotemark}%
752 \def\ltx@no@yfootmark{\ltx@no@footwarn\footnotemark}%
753 \def\ltx@no@xfoottext[#1]#2{\ltx@no@footwarn\footnotetext}%
754 \def\ltx@no@yfoottext#1{\ltx@no@footwarn\footnotetext}%
755 \def\ltx@no@footwarn#1{%
756 \class@warn{%
757 The \string#1\space command is not legal on the title page;
758 using \string\thanks\space instead might suit you: consult the manual for details%
759 }%
760 }%

```

`\frontmatter@abstractheading` The default abstract head; journals will override this procedure.

```

761 \def\frontmatter@abstractheading{%
762 \begingroup
763 \centering\large
764 \abstractname
765 \par
766 \endgroup
767 }%

```

`\frontmatter@abstractfont` The default type specification for the body of the abstract. Journals will override this setting.

```

768 \def\frontmatter@abstractfont{}%

```

`frontmatter@description` Within the abstract, the description environment is defined as follows:

```

769 \newenvironment{frontmatter@description}{%
770 \list{}{%
771 \leftmargin\z@
772 \labelwidth\z@

% \itemindent-\leftmargin
%

773 \itemindent\z@
774 \let\makelabel\frontmatter@descriptionlabel
775 }%
776 }{%
777 \endlist
778 }%
779 \def\frontmatter@descriptionlabel#1{%
780 \hspace\labelsep
781 \normalfont\bfseries
782 #1:%
783 }%

```

`\frontmatter@abstractwidth` The default setting is the full text width; journals can override this setting.

```
784 \def\frontmatter@abstractwidth{\textwidth}
```

`\frontmatter@abstract@produce` This procedure determines how the abstract is incorporated into the title block. We split this out in anticipation of the need to lift the limitation that the abstract not break over pages.

If we are in preprint style, we provide an easy pagebreak point immediately above the abstract. This means that the abstract will either fit entirely on the same page as the title block, or it will start a page of its own (which may itself break onto a subsequent page if necessary).

```
785 \def\frontmatter@abstract@produce{%
786   \par
787   \preprintsty@sw{%
788     \do@output@MVL{%
789       \vskip\frontmatter@preabstractspace
790       \vskip200\p@\@plus1fil
791       \penalty-200\relax
792       \vskip-200\p@\@plus-1fil
793     }%
794   }{%
795     \addvspace{\frontmatter@preabstractspace}%
796   }%
797   \begingroup
798   \dimen@baselineskip
799   \setbox\z@\vtop{\unvcopy\absbox}%
800   \advance\dimen@-\ht\z@\advance\dimen@-\prevdepth
801   \@ifdim{\dimen@>\z@}{\vskip\dimen@}{}%
802   \endgroup
803   \begingroup
804   \prep@absbox
805   \unvbox\absbox
806   \post@absbox
807   \endgroup
808   \@ifx{\@empty\mini@notes}{\mini@notes\par}%
809   \addvspace\frontmatter@postabstractspace
810 }%
811 \appdef\frontmatter@init{\let\mini@notes\@empty}%
812 \let\prep@absbox\@empty
813 \let\post@absbox\@empty
```

`\frontmatter@preabstractspace` Space above and space below abstract in title block

```
\frontmatter@postabstractspace 814 \def\frontmatter@preabstractspace{.5\baselineskip}
815 \def\frontmatter@postabstractspace{.5\baselineskip}
```

9.9 Formatting the title block

`titlepage` This is L^AT_EX 2_ε's article class version, with modifications.

```
816 \newenvironment{frontmatter@titlepage}{%
```

```

817     \twocolumn@sw{\onecolumngrid}{\newpage}%
818     \thispagestyle{titlepage}%
819     \setcounter{page}\@ne
820 }{%
821     \twocolumn@sw{\twocolumngrid}{\newpage}%
822     \twoside@sw}{%
823         \setcounter{page}\@ne
824     }%
825 }%

```

`\maketitle` Put it all together to format the title block.

Gotcha! If you expand `\csnameundefined\endcsname`, you change the meaning of `\undefined` from “Undefined” to `\relax`. Watchout!

```

826 \def\frontmatter@maketitle{%
827     \@author@finish
828     \title@column\titleblock@produce
829     \suppressfloats[t]%
      Now save some memory.
830     \let\and\relax
831     \let\affiliation\@gobble
832     \let\author\@gobble
833     \let\@AAC@list\@empty
834     \let\@AFF@list\@empty
835     \let\@AFG@list\@empty
836     \let\@AF@join\@AF@join@error
837     \let\email\@gobble
838     \let\@address\@empty
839     \let\maketitle\relax
840     \let\thanks\@gobble
841     \let\abstract\@undefined\let\endabstract\@undefined
842     \titlepage@sw{%
843         \vfil
844         \clearpage
845     }{}%
846 }%

```

`\maketitle@Hy` We provide the means to take back the definition of `\maketitle` from `hyperref`: we do not need its help in providing hypertext services in the title page.

```

847 \def\maketitle@Hy{%
848     \let\Hy@saved@footnotemark\@footnotemark
849     \let\Hy@saved@footnotetext\@footnotetext
850     \let\@footnotemark\H@@footnotemark
851     \let\@footnotetext\H@@footnotetext
852     \ifnextchar[%]
853         \Hy@maketitle@optarg
854     {%
855         \HyOrg@maketitle
856         \Hy@maketitle@end
857     }%

```



```

858 }%
859 \appdef\class@documenthook{%
860   \@ifx{\maketitle\maketitle@Hy}{%
861     \class@info{Taking \string\maketitle\space back from hyperref}%
862     \let\maketitle\frontmatter@maketitle
863   }{%
864   }%
865 }%

```

`\titleblock@produce` This procedure produces the title block.

It effectively executes inside a group and always returns us to vertical mode.

Note: we assume that it is OK to set the footnote counter to zero at this point.

Is this a safe assumption?

```

866 \def\titleblock@produce{%
867   \begingroup

```

First, we restore the footnote mechanism to its default state, then we customize the way the footnote mark is produced and how it is formatted.

```

868   \ltx@footnote@pop

```

The following three lines establish an independent footnote counter for use in the title block.

```

869   \def\@mpfn{mpfootnote}%
870   \def\thempfn{\thempfootnote}%
871   \c@mpfootnote\z@
872   \let\@makefnmark\frontmatter@makefnmark
873   \frontmatter@setup
874   \thispagestyle{titlepage}\label{FirstPage}%

```

Produce the title:

```

875   \frontmatter@title@produce

```

Produce the author list:

```

876   \groupauthors@sw{%
877     \frontmatter@author@produce@group
878   }{%
879     \frontmatter@author@produce@script
880   }%

```

Produce the dates:

```

881   \frontmatter@RRAPformat{%
882     \expandafter\produce@RRAP\expandafter{\@date}%
883     \expandafter\produce@RRAP\expandafter{\@received}%
884     \expandafter\produce@RRAP\expandafter{\@revised}%
885     \expandafter\produce@RRAP\expandafter{\@accepted}%
886     \expandafter\produce@RRAP\expandafter{\@published}%
887   }%

```

Produce the abstract, PACS, and keywords, and end any paragraph.

```

888   \frontmatter@abstract@produce
889   \@ifx@empty\@pacs{}{%

```

```

890 \@pacs@produce\@pacs
891 }%
892 \@ifx@empty\@keywords{}\{%
893 \@keywords@produce\@keywords
894 }%
895 \par
896 \frontmatter@finalspace
897 \endgroup
898 }%

```

`\frontmatter@title@produce` The default formatting procedure for the article title. This procedure should take care of the vertical space below the title.

Clients may override this procedure, but it is more likely that they will use the hooks `\frontmatter@title@above`, `\frontmatter@title@format`, and `\frontmatter@title@below`.

```

899 \def\toclevel@title{0}%
900 \def\frontmatter@title@produce{%
901 \begingroup
902 \frontmatter@title@above
903 \frontmatter@title@format
904 \@title
905 \unskip
906 \phantomsection\expandafter\@argswap@val\expandafter{\@title}\addcontentsline{toc}{title}}%
907 \@ifx{\@title@aux\@title@aux@cleared}\{%
908 \expandafter\frontmatter@footnote\expandafter{\@title@aux}%
909 }%
910 \par
911 \frontmatter@title@below
912 \endgroup
913 }%
914 \appdef\let@mark{\let\\relax}%

```

`\frontmatter@title@above` The default values for formatting specifications for the article title.

`\frontmatter@title@format` The procedure `\frontmatter@title@above` should take care of the vertical space above the title; `\frontmatter@title@below` below. The procedure `\frontmatter@title@format` should invoke any font switches, etc. that may apply to the title.

Journals will override this procedure.

```

915 \def\frontmatter@title@above{}%
916 \def\frontmatter@title@format{}%
917 \def\frontmatter@title@below{\addvspace{\baselineskip}}%

```

9.9.1 Authors and affiliations in superscriptaddress style

`\frontmatter@author@produce@script` `\frontmatter@author@produce@script` is an alias for `\frontmatter@author@produce`, the procedure that formats the author/affiliation list.

In this case, the authors affiliations are being superscripted (class option `superscriptaddress`).

This procedure must ensure that any paragraph that it starts gets ended finally.

```

918 \def\frontmatter@author@produce@script{%
919   \begingroup
920   \let\@author@present\@author@present@script
921   \frontmatterverbose@sw{\typeout{\string\frontmatter@author@produce@script:}\say\@AAC@list\s

```

When the author/affiliation list `\@AAC@list` is executed, `\@tempcnt` counts each author, and `\@tempa` stores a list of author indices for the current collaboration.

Note: this procedure uses `\AU@temp` to hold a list of author counts for each collaboration. Note: also uses `\@tempcnta` to communicate between procedures. This usage of `\@tempcnta` is OK, because the expansion of `\@AAC@list` will trigger only the execution of our own procedures.

```

922   \let\AU@temp\@empty
923   \@tempcnta\z@

```

We wish to know how many authors are in each collaboration, for the purposes of `\listcomma` and `\listand`.

Here we assign values for the intercolated operators appearing within `\@AAC@list`, then execute that macro, registering the authors in each collaboration. Afterwards, clean up by emulating an empty collaboration.

The result, stored in `\AU@temp`, is a list of brace-delimited tokens, each a number representing the number of authors in that collaboration.

```

924   \let\AF@opr \@gobble
925   \def\AU@opr{\@author@count\@tempcnta}%
926   \def\CO@opr{\@collaboration@count\AU@temp\@tempcnta}%
927   \@AAC@list
928   \expandafter\CO@opr\@author@cleared

```

Next, present the authors and their affiliations, with the collaborations interleaved.

We assign values for the intercolated operators appearing within `\@AAC@list`. Next, assign `\@listcomma` based on the number of authors in the first collaboration. Then expand `\@AAC@list`.

Upon completion, there will be two space tokens following the last author because of `\listand` processing; remove them, then end the last paragraph.

FIXME: this juncture would be a good time to effectively eliminate the unused affiliations in `\@AFF@list`.

```

929   \begingroup
930   \frontmatter@author@format
931   \let\AF@opr \@affilID@def
932   \let\AU@opr \@author@present
933   \def\CO@opr{\@collaboration@present\AU@temp}%
934   \set@listcomma@list\AU@temp
935   \@AAC@list
936   \unskip\unskip
937   \par
938   \endgroup

```

We now list out the affiliations in the order they appeared.

```

939     \begingroup
940     \frontmatter@above@affiliation@script
941     \let\AFF@opr \@affil@script
942     \@AFF@list
943     \frontmatter@footnote@produce
944     \par
945     \endgroup
946 \endgroup
947 }%

\@author@count This version of \AU@opr counts the number of authors it processes.
948 \def\@author@count#1{%
949   \advance#1\@ne
950   \@author@gobble
951 }%

\@collaboration@present Format a collaboration. Note that we immediately end the paragraph thus begun,
because we only support superscriptaddress-style processing.
    Note also that the execution of the production procedures takes place inside
    of a group; for reasons of protective programming.
    Bug note: originally, the number of authors in each collaboration was stored
    in \@tempa, but this exposed us to procedures in our production that modified
    the meaning of \@tempa.
    The last action done in this procedure is to assign \@listcomma based on the
    number of authors in the next collaboration.
952 \def\@collaboration@present#1#2#3#4{%
953   \par
954   \begingroup
955   \frontmatter@collaboration@above
956   \@affilID@def{}%
957   \@tempcnta\z@
958   \@author@present{}{(\ignorespaces#3\unskip)}{#4}%
959   \par
960   \endgroup
961   \set@listcomma@list#1%
962 }%
963 \def\frontmatter@collaboration@above{%

\@collaboration@count Simply register each author in this collaboration. Note: #1 is a \csname to hold
the value, #2 is the \count register holding the count of interest.
964 \def\@collaboration@count#1#2{%
965   \appdef@eval#1{\the#2}#2\z@
966   \@author@gobble
967 }%

\@affilID@def The \@affilID@def procedure, an alias of \AF@opr used during \frontmatter@author@produce@script
processing, memorizes the affiliation in \@affilID@temp.
968 \def\@affilID@def{\def\@affilID@temp}%

```

`\@affilID@temp` The macro `\@affilID@temp` is used to communicate between `\doauthor` and instances of `\AF@opr` within the author list.

```
969 \let\@affilID@temp\@empty
```

`\affils@present@script` An alias of `\AFG@opr`, this procedure is applied to elements in `\@AFG@list`. It builds `\@AFU@list`, a list of unique affiliations found within affiliation groups.

```

%\def\affils@present@script#1{%
% \get@affil#1{%
%}%
%\def\get@affil#1{%
% \def\@tempa{#1}%
% \ifx{\@empty\@tempa}{}%
% \booleanfalse\temp@sw
% \def\AF@opr{\x@match\@tempa}%
% \@AFU@list
% \temp@sw{}{%
% \appdef\@AFU@list{\AF@opr{#1}}%
%}%
% \get@affil
%}%
%}%
%
```

`\affil@present@script` An alias of `\AF@opr`, this procedure is applied to `\@AFU@list` when formatting the affiliations under `superscriptaddress`. It in turn applies `\affil@script` to `\@AFF@list`, thereby formatting the affiliation associated with this affiliation index.

Note: it traverses the `\@AFF@list` for each entry in the `\@AFU@list`, thereby making this portion of code execute in N^2 time.

```

%\def\affil@present@script#1{%
% \def\@tempa{#1}%
% \begingroup
% \frontmatter@affiliationfont
% \let\AFF@opr \affil@script
% \@AFF@list
% \endgroup
%}%
%
```

`\affil@script` Alias of `\AFF@opr`, this procedure is applied to `\@AFF@list` when formatting the affiliations under `superscriptaddress`. It rejects all entries not matching the affiliation index held in `\@tempa`.

```

970 \def\affil@script#1#2#3{%
971 \def\@tempifx{#1}\@ifx{\@tempifx\@tempa}{%
972 \if@empty{#2}{}%
973 \par
974 \begingroup

```

```

975 \def\@thefnmark{#1}\@makefnmark\ignorespaces
976 #2%
977 \ifempty{#3}{\frontmatter@footnote{#3}}%
978 \par
979 \endgroup
980 }%
981 }{}%
982 }%

```

`\@affil@script` Alias of `\AFF@opr`: The affiliations are being formatted in the case where affiliations are being superscripted: make a list out of the affiliations with the numbers printed. Society-specific code can change the formatting by overriding the definition of `\frontmatter@affiliationfont`.

A client may choose to set `\affil@cutoff` to either `\@ne` (the default) or `\tw@`. The latter setting will enforce a rule to the effect that if a single affiliation appears on the title page, then no affiliation superscript at all is produced.

- #1—Affiliation ID: a number; zero signifies a `\noaffiliation`.
- #2—Collaboration ID
- #3—Affiliation address
- #4—Auxiliary info

```

983 \def\@affil@script#1#2#3#4{%
    If the affiliation is the \noaffiliation, then we do nothing.
984 \@ifnum{#1=\z@}{\%
985 \par
986 \begingroup
987 \frontmatter@affiliationfont
988 \@ifnum{\c@affil<\affil@cutoff}{\%
989 \def\@thefnmark{#1}\@makefnmark
990 }%
991 \ignorespaces#3%
992 \@ifempty{#4}{\frontmatter@footnote{#4}}%
993 \par
994 \endgroup
995 }%
996 }%
997 \let\affil@cutoff\@ne

```

`\@author@present@script` This version of `\AU@opr` applies to the `superscriptaddress` class option. Need to add commas between groups of address numbers, which are passed in the macro `\@affilID@temp` in the form `{3}{4}{7}` if this set of authors is related to addresses, 3, 4 and 7.

```

998 \def\@author@present@script#1#2#3{%
999 \begingroup
1000 \gdef\comma@space{\textsuperscript{,\,}}%
1001 \doauthor{#2}{#3}{\@affil@present@script}%
1002 \endgroup
1003 \advance\@tempcnta\m@ne
1004 }%

```

```

1005 \def\@affilcomma#1#2{%
1006   \@ifx{\z@#1}{%
1007     \@ifx{\relax#2}{}%
1008     \@affilcomma{#2}%
1009   }%
1010 }{%
1011   #1%
1012   \@ifx{\relax#2}{}%
1013   \@ifx{\z@#2}{%
1014     \@affilcomma
1015   }{%
1016     ,\,\@affilcomma{#2}%
1017   }%
1018 }%
1019 }%
1020 }%

```

`\@affil@present@script` The `\@affil@present@script` procedure presents the reference to the affiliations in the case of superscript addresses.

The affiliations are presented to `\@affil@present@script@` as a list of brace-delimited tokens, each containing the affiliation ID (a number). The list is terminated by the token `\relax`. The macro recurses (via tail recursion) until the terminating token is encountered. Note that an affiliation ID of zero signifies a `\noaffiliation`: references to the `\noaffiliation` are passed over.

Upon termination, the affiliations, if any, are produced via `\textsuperscript` and the appropriate boolean is queued via `\aftergroup`. The boolean signifies that a non-trivial affiliation was produced, so that the proper punctuation can be produced. The group in question is that opened and closed by the `\doauthor` procedure.

This procedure uses `\@tempa` as a scratch register.

```

1021 \def\@affil@present@script{%
1022   \let\@tempa\@empty
1023   \expandafter\@affil@present@script@\@affilID@temp\relax
1024 }%
1025 \def\@affil@present@script@#1{%
1026   \@ifx{\relax#1}{%
1027     \@ifx{\@tempa\@empty}{%
1028       \aftergroup\false@sw
1029     }{%
1030       \textsuperscript{\expandafter\@affilcomma\@tempa\relax\relax}%
1031       \aftergroup\true@sw
1032     }%
1033   }{%
1034     \ifnum{#1=\z@}{\appdef\@tempa{#1}}%
1035     \@affil@present@script@
1036   }%
1037 }%
1038 \@provide\@author@parskip{\z@skip}%

```

9.9.2 Authors and affiliations in groupedaddress style

`\frontmatter@author@produce@group` Alias for `\frontmatter@author@produce` when `groupedaddress` is in effect, the procedure that formats the author/affiliation list.

In this case, the authors are being grouped above their shared addresses. How it works: the `\@AFG@list`, a list of all unique affiliation groups, is expanded. For each such group, all authors belonging to that group are formatted above the affiliation group. Collaborations are silently passed over.

This procedure must ensure that any paragraph that it starts gets ended finally.

```

1039 \def\frontmatter@author@produce@group{%
1040   \begingroup
1041     \let\@author@present\@author@present@group
1042     \frontmatter@author@format
1043     \frontmatter@verbose@sw{\typeout{\string\frontmatter@author@produce@group:}\say\@AAC@list\sa
1044     \let\AU@temp\@empty
1045     \set@listcomma@list\AU@temp
1046     \def\CO@opr{\@collaboration@present\AU@temp}%
1047     \let\AFG@opr \affils@present@group
1048     \let\@listcomma\relax
1049     \@AFG@list
1050     \frontmatter@footnote@produce
1051     \par
1052   \endgroup
1053   \frontmatter@author@below
1054 }%
1055 \@provide\frontmatter@author@below{}%
```

`\affils@present@group` Alias of `\AFG@opr`, this procedure is used on every element of `\@AFG@list`, the list of unique affiliation groups, when formatting the author/affiliation block: It presents all authors sharing this affiliation group.

This procedure is called via the procedure `\frontmatter@author@produce@group`, an alias for `\frontmatter@author@produce`,

Its use pertains to the class options `groupedaddress`, `unsortedaddress`, and `runinaddress` (that is, `\groupauthors@sw` is true).

For each invocation, the entire `\@AAC@list` is run through (twice), making this process execute in N^2 time. (Is this really true?)

```

1056 \def\affils@present@group#1{%
```

Count (using `\@tempcnta`) the authors in the author list whose affiliation group matches the argument `#1`.

Note that `\AF@temp` is used as a storage register for the argument of the procedure, for purposes of comparison using `\ifx`.

Note: here we use `\@tempcnta` to accumulate the number of authors in the current affiliation set.

QUERY: do the value of `\AF@temp` and `\AF@opr` need to persist?

QUERY: what value does `\AU@opr` have at this point? ANSWER: the `\@affilID@count` and `\@affilID@match` procedures assign meanings to `\AU@opr`

and \C0@opr dynamically. We initialize the two operators to \@undefined so as to catch the pathological cases.

```

1057 \begingroup
1058   \def\AF@temp{#1}%
1059   \@tempcnta\z@
1060   \let\AU@opr \@undefined
1061   \let\C0@opr \@undefined
1062   \def\AF@opr{\@affilID@count\AF@temp\@tempcnta}%
1063   \@AAC@list

```

If there are no authors using this affiliation group, skip it.

```

1064   \@ifnum{\@tempcnta=\z@}{\%

```

DPC: If we have a list of length two, need to locally zap a comma.

```

1065     \begingroup
1066     \frontmatter@above@affilgroup
1067     \set@listcomma@count\@tempcnta

```

Run through the author list, presenting (with \@author@present) those authors whose affiliation matched the given one.

```

1068     \let\AU@opr \@undefined
1069     \let\C0@opr \@undefined
1070     \def\AF@opr{\@affilID@match\AF@temp}%
1071     \@AAC@list
1072   \endgroup

```

Now that the authors have all been presented, present the affiliations, grouped.

Note: \@tempcnta is the number of affiliations for this set of authors.

```

1073   \begingroup
1074   \par
1075   \frontmatter@above@affiliation
1076   \frontmatter@affiliationfont
1077   \let\\ \frontmatter@addressnewline
1078   \@tempcnta\z@
1079   \@tfor\AF@temp:=#1\do{%
1080     \expandafter\@ifx\expandafter{\expandafter\z@\AF@temp}{\%
1081       \advance\@tempcnta\@ne
1082     }%
1083   }%
1084   \@ifnum{\@tempcnta=\tw@}{\%
1085     \let\@listcomma\relax
1086   }{\%
1087     \def@after@address
1088     \runinaddress@sw{%
1089     }{\%
1090     \tightenlines@sw}{\%

```

The following line determines the space between affiliations in grouped mode

```

1091     \parskip\z@
1092   }%
1093   \appdef\after@address\par

```

```

1094     }%
1095     \let\AFF@opr \@affil@group
1096     \do@affil@fromgroup\@AFF@list#1\relax
1097 \endgroup
    End of branch handling authors.
1098 }%
1099 \par
1100 \endgroup
1101 }%

```

`\def@after@address` Each of these procedures assigns a meaning to `\after@address`, the first a useful default, the second a nil. A society or journal substyle may define it according to its own requirements.

```

1102 \def\def@after@address{\def\after@address{\@listcomma\ \@listand}}%
1103 \def\def@after@address@empty{\let\after@address\@empty}%

```

`\@affilID@count` The control sequence name `\AF@opr` is placed in the author/affiliation list (`\@AAC@list`) for each (new) affiliation, with that affiliation as its argument.

The control sequence name `\AF@opr` is an alias of a procedure to count the number of authors at a given affiliation (`\@affilID@count`) or to present the given authors (`\@affilID@match`). These two procedures are executed when formatting under the `groupedaddress` class option.

```

1104 \def\@affilID@count#1#2#3{%
1105   \def\@tempifx{#3}%
1106   \@ifx{\@tempifx#1}{%
1107     \def\AU@opr{\@author@count#2}%
1108   }{%
1109     \let\AU@opr \@author@gobble
1110   }%
1111   \let\CO@opr \@collaboration@gobble
1112 }%
1113 \def\@affilID@match#1#2{%
1114   \def\@tempifx{#2}%
1115   \@ifx{\@tempifx#1}{%
1116     \let\AU@opr \@author@present
1117   }{%
1118     \let\AU@opr \@author@gobble
1119   }%
1120   \let\CO@opr \@collaboration@gobble
1121 }%

```

`\do@affil@fromgroup` Executes iteratively: selects the next address ID to print, and then re-execute the list of addresses to print the text of that address.

Note: an argument of `\relax` breaks out of this iteration, while an argument of `\z@` (`\noaffiliation`) is a no-op.

Note: we have created an N^2 computing process. FIXME: can use hashing instead, you know.

```

1122 \def\do@affil@fromgroup#1#2{%
1123   \ifx{\relax#2}{}%
1124     \count@#2\relax
1125     \ifnum{\z@=\count@}{-}{#1}%
1126     \do@affil@fromgroup#1%
1127   }%
1128 }%

```

\@affil@group The alias of **\AFF@opr** when the list **\@AFF@list** is executed by **\do@affil@fromgroup** (groupedaddress): Print the address if its number matches **\count@** (value set by **\do@affil@fromgroup**).

Note that we detect a **\noaffiliation** here by the affiliation address being the same as the expansion of **\blankaffiliation**.

I made a mistake when coding the comparison to **\blankaffiliation**: it originally read **\ifx{#3\blankaffiliation}**. This is obviously wrong once you think twice.

```

1129 \def\@affil@group#1#2#3#4{%
1130   \ifnum{#1=\count@}{%
1131     \def\@tempa{#3}%
1132     \ifx{\@tempa\blankaffiliation}{}%
1133       #3%
1134       \ifempty{#4}{}%
1135       \frontmatter@footnote{#4}%
1136     }%
1137     \after@address
1138   }%
1139   \advance\@tempcnta\m@ne
1140 }{}%
1141 }%

```

\@author@present@group This version of **\AU@opr** applies to the **groupedaddress** class option and its ilk.

\@affil@present@group Traverse the list calling the **\doauthor** hook on each author.

The third argument of **\doauthor** fulfills the requirement that it queue up a boolean via **\aftergroup**.

```

1142 \def\@author@present@group#1#2#3{%
1143   \gdef\comma@space{\gdef\comma@space{\textsuperscript{,},}}%
1144   \doauthor{#2}{#3}{\@affil@present@group}%
1145   \advance\@tempcnta\m@ne
1146 }%
1147 \def\@affil@present@group{%
1148   \aftergroup\false@sw
1149 }%

```

\@pacs@produce PACS, keywords and dates.

```

1150 \def\@pacs@produce#1{%
1151   \showPACS@sw{%
1152     \begingroup
1153     \frontmatter@PACS@format

```

```

1154 \@pacs@name#1\par
1155 \endgroup
1156 }{%
1157 \@if@empty{#1}{-}{%
1158 \class@warn{\PACS@warn}%
1159 }%
1160 }%
1161 }%
1162 \def\PACS@warn{If you want your PACS to appear in your output, use document class option showpa

\@keywords@produce
1163 \def\@keywords@produce#1{%
1164 \showKEYS@sw{%
1165 \begingroup
1166 \frontmatter@keys@format
1167 \@keys@name#1\par
1168 \endgroup
1169 }{%
1170 \@if@empty{#1}{-}{%
1171 \class@warn{If you want your keywords to appear in your output, use document class option sh
1172 }%
1173 }%
1174 }%

\frontmatter@footnote@produce@footnote Produce any footnotes to appear at the bottom of the title page.
\frontmatter@footnote@produce@endnote If frontmatter footnotes have been redirected to the bibliography, this will be
a no-op. ref.: \present@bibnote.
1175 \def\frontmatter@footnote@produce@footnote{%
1176 \let\@TBN@opr\present@FM@footnote
1177 \@FMN@list
1178 \global\let\@FMN@list\@empty
1179 }%

1180 \def\present@FM@footnote#1#2{%
1181 \begingroup
1182 \csname c@\@mpfn\endcsname#1\relax
1183 \def\@thefnmark{\frontmatter@thefootnote}%
1184 \frontmatter@footnotetext{#2}%
1185 \endgroup
1186 }%
1187 \def\frontmatter@footnote@produce@endnote{%
1188 }%

```

10 Package defaults

```

\title@column We give meanings to the Booleans and other macros that a client document class
\preprintsty@sw would set on our behalf.
\collaboration@sw 1189 \appdef\frontmatter@init{%
\frontmatter@footnote@produce
\do@output@MVL
\comma@space

```

```

1190 \@ifxundefined\title@column      {\let\title@column\@empty}{}%
1191 \@ifxundefined\preprintsty@sw     {\@booleanfalse\preprintsty@sw}{}%
1192 \@ifxundefined\frontmatter@footnote@produce{\let\frontmatter@footnote@produce\frontmatter@footnote@produce}{}%
1193 \@ifxundefined\do@output@MVL      {\let\do@output@MVL\@firstofone}{}%
1194 \@ifxundefined\comma@space        {\let\comma@space\@empty}{}%
1195 }%

\frontmatter@thefootnote In the title block, the footnote symbol (used for alternate affiliation and sundry)
                          is a \fnsymbol or a lowercase letter, as selected by a boolean. The society or
                          journal may override this definition.
1196 \def\frontmatter@thefootnote{%
1197   \altaffilletter@sw{\@alpha}{\fnsymbol}{\csname c@\@mpfn\endcsname}%
1198 }%
1199 \@ifx{\altaffilletter@sw\@undefined}{\@booleantrue\altaffilletter@sw}{}%

\frontmatter@makefnmark The default procedure for setting the footnote mark within the frontmatter. A
                          client may override this procedure.
1200 \def\frontmatter@makefnmark{%
1201   \@textsuperscript{%
1202     \normalfont\@thefnmark
1203   }%
1204 }%

\frontmatter@makefntext This procedure is used when setting footnotes within the title block.
                          Note that we are hyperref friendly: we invoke \Hy@raisedlink so that this
                          footnote becomes a hypertext anchor. If hyperref is not loaded, then ltxutil
                          has our act covered via some stubs.
1205 \long\def\frontmatter@makefntext#1{%
1206   \parindent 1em
1207   \noindent
1208   \Hy@raisedlink{\hyper@anchorstart{frontmatter.\expandafter\the\csname c@\@mpfn\endcsname}\hyper@anchorend}
1209   \@makefnmark
1210   #1%
1211 }%

\frontmatter@setup The default type specification for the title page. Clients will override this definition.
1212 \def\frontmatter@setup{%

\frontmatter@RRAPformat The procedure \frontmatter@RRAPformat is the formatting procedure for the
\punct@RRAP "Received, Revised, etc." block on the title page. The macro \punct@RRAP produces
\produce@RRAP the punctuation between the entries. Clients will override these two definitions.

                          The procedure \produce@RRAP is fairly general, and should be used by most
                          journal substyles.
                          The procedure \frontmatter@RRAP@format will be overridden by the journal.
1213 \def\frontmatter@RRAPformat#1{%
1214   \removeatlastskip

```

```

1215 \begingroup
1216 \frontmatter@RRAP@format
1217 #1\par
1218 \endgroup
1219 }%
1220 \def\punct@RRAP{; }%
1221 \def\produce@RRAP#1{%
1222 \ifempty{#1}{}%
1223 \ifvmode{\leavevmode}{\unskip\punct@RRAP\ignorespaces}%
1224 #1%
1225 }%
1226 }%

\frontmatter@authorformat The default type specification for the author list. Clients will override this defini-
tion. For one alternative, see the revtex4 document class.
1227 \def\frontmatter@authorformat{}%

\frontmatter@above@affilgroup The default amount of space above an affiliation group (in a \affils@present@group
production). Clients will override this definition.
1228 \def\frontmatter@above@affilgroup{}%

\frontmatter@above@affiliation The \frontmatter@above@affiliation is the amount of space above affiliations
matter@above@affiliation@script in the groupedaddress style, and \frontmatter@above@affiliation@script is
that for superscriptaddress. Clients will override this definition. For one alter-
native, see the revtex4 document class.
1229 \def\frontmatter@above@affiliation{}%
1230 \def\frontmatter@above@affiliation@script{}%

\frontmatter@affiliationfont The default type specification for the affiliation. Clients will override this defini-
tion. For one alternative, see the revtex4 document class, where several alterna-
tive definitions are made.
1231 \def\frontmatter@affiliationfont{\itshape\selectfont}%

\frontmatter@RRAP@format The default type specification for the dates. Clients will override this definition.
1232 \def\frontmatter@RRAP@format{}%

\frontmatter@PACS@format Specify the formatting of the title page PACS statement.
Journals will override.
1233 \def\frontmatter@PACS@format{}%

\frontmatter@keys@format Specify the formatting of the title page keywords statement.
Journals will override.
1234 \def\frontmatter@keys@format{}%

\frontmatter@finalspace
1235 \def\frontmatter@finalspace{\addvspace{18\p@}}

```

`\frontmatter@addressnewline` The definition of `\\` for address handling. Default puts all the ‘lines’ on a run-in line, separated by comma and space. DPC: was space between lines of addresss.

```
1236 \def\frontmatter@addressnewline{%
1237   \@ifhmode{\skip@\lastskip\unskip\unpenalty\break\hskip\skip@}{}%
1238   % was: \vskip-.5ex
1239 }%
```

`\frontmatter@preabstractspace` Space above and space below abstract in title block

```
\frontmatter@postabstractspace 1240 \def\frontmatter@preabstractspace{5.5\p@}
1241 \def\frontmatter@postabstractspace{6.5\p@}
```

`\aftermaketitle@chk` Error-checking code.

```
1242 \def\aftermaketitle@chk#1{%
1243   \@ifx{\maketitle\relax}{%
1244     \class@err{\protect#1 must be used before \protect\maketitle}%
1245   }{}%
1246 }%
```

`\ps@titlepage` Default page style for title page. Journals will override this procedure.

```
1247 \def\ps@titlepage{\ps@empty}%
```

FIXME: there is a limitation to the default meaning of `\@startpage`: the label “FirstPage” is only defined if the document has a `\maketitle` command.

```
1248 \def\volumeyear#1{\gdef\@volumeyear{#1}}%
1249 \def\@volumeyear{}%
1250 \def\volumenumber#1{\gdef\@volumenumber{#1}}%
1251 \def\@volumenumber{}%
1252 \def\issuenumber#1{\gdef\@issuenumber{#1}}%
1253 \def\@issuenumber{}%
1254 \def\eid#1{\gdef\@eid{#1}}%
1255 \def\@eid{}%
1256 %
1257 \def\startpage#1{\gdef\@startpage{#1}\c@page#1\relax}%
1258 \def\@startpage{\pageref{FirstPage}}%
1259 \def\endpage#1{\gdef\@endpage{#1}}%
1260 \def\@endpage{\pageref{LastPage}}%
```

10.1 Printing out the “list-of” elements

FIXME: The `\appendix@toc` procedure should change the meaning of `\l@section` so that the `\sections` can be appropriately formatted, reflecting their status as appendices.

```
1261 \def\print@toc#1{%
1262   \begingroup
1263   \expandafter\section
1264   \expandafter*%
1265   \expandafter{%
```

```

1266             \csname#1name\endcsname
1267             }%
1268   \let\appendix\appendix@toc
1269   \@starttoc{#1}%
1270 \endgroup
1271 }%
1272 \def\appendix@toc{%

\Dated@name  These strings are used in the \date, et al. commands.
\Received@name 1273 \def\Dated@name{Dated }%
\Revised@name 1274 \def\Received@name{Received }%
\Accepted@name 1275 \def\Revised@name{Revised }%
\Published@name 1276 \def\Accepted@name{Accepted }%
1277 \def\Published@name{Published }%

```

Two commands require robustifying against harsh treatment when TOC entries are written out. Note that `\class@warn` is not user-level markup, but crops up when the `\title` command is missing from the document.

```

1278 \appdef\robustify@contents{%
1279   \let\thanks\@gobble\let\class@warn\@gobble
1280   \def\begin{\string\begin}\def\end{\string\end}%
1281 }%

```

10.2 Syntax switch

Shall we take over the syntax of L^AT_EX? By default, Yes, unless the Boolean below has already been defined. In the package version, this is controlled by an option; in the kernel version, the Boolean remains undefined.

`\maketitle` presents a complication. If this code will execute under `ltxgrid`, then its version of the procedure will do fine.

As a package, under `article`, things are different. In this case, what should be done depends upon `\if@titlepage`. If true, then just execute `\maketitle` as it stands. If false, then the `article` class has defined its wrapper procedure, and we should take over the meaning of `\@maketitle` instead.

Here is a list of the commands defined by this package that potentially override those of standard L^AT_EX: `\frontmatter@title`, `\frontmatter@author`, `\frontmatter@and`, `\frontmatter@thanks`, `\frontmatter@date`, `frontmatter@abstract`, `frontmatter@titlepage`, `\frontmatter@maketitle`.

The following code will perform that override, given the appropriate state of the Boolean.

```

1282 \@ifundefined\frontmatter@syntax@sw{\@booleantrue\frontmatter@syntax@sw}{}%
1283 \frontmatter@syntax@sw{%
1284   \let\title          \frontmatter@title
1285   \let\author         \frontmatter@author
1286   \let\date           \frontmatter@date
1287   \@ifundefined\@maketitle{%
1288     \let\maketitle     \frontmatter@maketitle
1289     \@booleantrue      \titlepage@sw

```



```

1290 }{%
1291   \let\@maketitle \frontmatter@maketitle
1292   \prepdef\maketitle\@author@finish
1293 }%
1294 \let\noaffiliation \frontmatter@noaffiliation
1295 \let\thanks@latex \thanks
1296 \let\thanks \frontmatter@thanks
1297 \let\and@latex \and
1298 \let\and \frontmatter@and
1299 \let@environment{titlepage}{frontmatter@titlepage}%
1300 \let@environment{abstract}{frontmatter@abstract}%
1301 }{%
1302 \let\noaffiliation\@empty
1303 }%

```

10.3 End of the ltxfront kernel

The kernel portion of the ltxfront package is complete.

```
1304 %</kernel>
```

10.4 Remainder of the ltxfront package

Include any code here that ought to be incorporated into the package, but should not be part of the kernel.

```
1305 %<*package>
```

Define formatting as like as possible to the article class. Comands that prepare for \maketitle: \author, \title, \date.

Argument of the above three may contain \ and \thanks; argument of \author may contain \and. The \ and \and may still work fine; \and will be ignored (warning); \thanks even though it should not reside in the argument, will work.

An explicit \footnotes should be treated as if it were \thanks.

```

% \@maketitle: \frontmatter@footnote@produce
%

```

```

1306 \def\thanks@latex#1{%
1307   \footnotemark
1308   \expandafter\expandafter
1309   \expandafter\gappdef
1310   \expandafter\expandafter
1311   \expandafter\@thanks
1312   \expandafter\expandafter
1313   \expandafter{%
1314   \expandafter\expandafter
1315   \expandafter\footnotetext
1316   \expandafter\expandafter
1317   \expandafter[%

```

```

1318 \expandafter\the\csname c@\@mpfn\endcsname][#1}}%
1319 }%
1320 \@booleanfalse\altaffilletter@sw
1321 \@if@sw@if@titlepage\fi{\@booleantrue}{\@booleanfalse}\titlepage@sw
1322 \def\frontmatter@title@above{\newpage\null\vskip2em\relax}%
1323 \def\frontmatter@title@format{\centering\LARGE\let\thanks\thanks@latex}%
1324 \def\frontmatter@title@below{\vskip1.5em\relax}%
1325 \def\frontmatter@author@format{\centering\large\advance\baselineskip\p@\parskip1.5\p@\let\thank
1326 \def\frontmatter@author@below{\vskip 1em\relax}%
1327 \def\frontmatter@above@affiliation{}}%
1328 \def\frontmatter@above@affiliation@script{}}%
1329 \def\frontmatter@affiliationfont{\centering\itshape}%
1330 \def\frontmatter@RRAP@format{\centering\large}%
1331 \def\frontmatter@preabstractspace{1.5em}%

1332 \long\def\frontmatter@footnotetext{%
1333 \expandafter\expandafter
1334 \expandafter\footnotetext
1335 \expandafter\expandafter
1336 \expandafter[%
1337 \expandafter\the\csname c@\@mpfn\endcsname]%
1338 }%
1339 \def\and@space{\}%
1340 \def\andname{and}%

```

Implement the feature of the article class whereby there is a default `\@date`, left over from the L^AT_EX kernel. This package does not have a default date. The user must put in an explicit command, like `\date{(\today)}`, which will restore L^AT_EX's default behavior.

What if the abstract environment falls after the `\maketitle` command? The environment will be undefined; the user will have to deal with this.

End of the package.

```
1341 %</package>
```

Here ends the programmer's documentation.

Index

Symbols

$\$TEXMF/$ 3
 $\%$ 556
 \backslash , 380, 1000, 1016, 1143
 $\backslash.dtx$ 5
 $\backslash@AAC@list$ 27–29, 32, 42, 43, 48, 50
 $\backslash@AAC@list$ 502, 503, 508–510, 527, 536, 538, 833, 921, 927, 935, 1043, 1063, 1071
 $\backslash@AF@join$ 30
 $\backslash@AF@join$ 276, 316, 392, 546, 563, 568, 574, 577, 836
 $\backslash@AF@join@error$.. 547, 549, 836
 $\backslash@AFF@list$. 24–26, 29, 43, 45, 51
 $\backslash@AFF@list$.. 428, 453, 538, 834, 921, 942, 1043, 1096
 $\backslash@AFG@list$... 26–29, 44, 47, 48
 $\backslash@AFG@list$ 504, 521, 523, 524, 528, 536, 538, 835, 921, 1043, 1049
 $\backslash@AFU@list$ 44, 45
 $\backslash@FMN@list$ 33, 34
 $\backslash@FMN@list$. 634, 651, 654, 1177, 1178
 $\backslash@TBN@opr$ 33
 $\backslash@TBN@opr$ 633, 651, 1176
 $\backslash@accepted$ 676, 885
 $\backslash@address$ 838
 $\backslash@affil$ 24, 26, 31
 $\backslash@affil$.. 408, 411, 413, 415, 418, 420, 426, 431, 442, 452
 $\backslash@affil@addr@def$ 426, 463
 $\backslash@affil@aux@def$ 431, 466
 $\backslash@affil@cleared$ 402
 $\backslash@affil@def$ 24
 $\backslash@affil@def$ 393, 402
 $\backslash@affil@group$ 29
 $\backslash@affil@group$ 1095, 1129
 $\backslash@affil@init$ 24
 $\backslash@affil@init$ 402, 460
 $\backslash@affil@join$ 392, 402
 $\backslash@affil@join@$ 402
 $\backslash@affil@match$ 24, 26, 29
 $\backslash@affil@match$ 427, 473
 $\backslash@affil@nil$ 25
 $\backslash@affil@nil$ 402, 442
 $\backslash@affil@none$ 367, 398, 402
 $\backslash@affil@present@group$ 32
 $\backslash@affil@present@group$... 1142
 $\backslash@affil@present@script$. 32, 47
 $\backslash@affil@present@script$.. 1001, 1021
 $\backslash@affil@present@script@$... 47
 $\backslash@affil@present@script@$. 1021
 $\backslash@affil@script$ 32
 $\backslash@affil@script$ 941, 983
 $\backslash@affilID@count$ 48, 50
 $\backslash@affilID@count$ 1062, 1104
 $\backslash@affilID@def$ 44
 $\backslash@affilID@def$ 931, 956, 968
 $\backslash@affilID@match$ 48, 50
 $\backslash@affilID@match$ 1070, 1104
 $\backslash@affilID@temp$ 44, 46
 $\backslash@affilID@temp$.. 968, 969, 1023
 $\backslash@affilclear@sw$ 24
 $\backslash@affilclear@sw$ 402, 422
 $\backslash@affilcomma$. 1005, 1008, 1014, 1016, 1030
 $\backslash@affiliation$ 388, 390
 $\backslash@affils@sw$ 17, 18, 24
 $\backslash@affils@sw$. 239, 244, 250, 256, 262, 425
 $\backslash@cargswap$ 328, 330
 $\backslash@cargswap@val$ 333, 335, 444, 448, 451, 452, 702, 906
 $\backslash@author$ 20, 24, 31
 $\backslash@author$. 306, 309, 318, 321, 323, 334
 $\backslash@author@cleared$ 21
 $\backslash@author@cleared$ 303, 928
 $\backslash@author@count$.. 925, 948, 1107
 $\backslash@author@def$ 295, 298, 303
 $\backslash@author@finish$ 24
 $\backslash@author@finish$. 344, 827, 1292
 $\backslash@author@gobble$ 20, 21

<code>\@author@gobble</code> .. 304, 520, 950, 966, 1109, 1118	<code>\@homepage</code> 565, 566
<code>\@author@init</code> 20, 21	<code>\@if@empty</code> .. 374, 606, 972, 977, 992, 1134, 1157, 1170, 1222
<code>\@author@init</code> 303, 338	<code>\@if@sw</code> 1321
<code>\@author@join</code> 303	<code>\@ifdim</code> 801
<code>\@author@join@</code> 303	<code>\@ifhmode</code> 1237
<code>\@author@parskip</code> 1038	<code>\@ifnextchar</code> 852
<code>\@author@present</code> 17, 31, 49	<code>\@ifnum</code> .. 478, 587, 596, 598–600, 984, 988, 1034, 1064, 1084, 1125, 1130
<code>\@author@present</code> . 920, 932, 958, 1041, 1116	<code>\@ifvmode</code> 1223
<code>\@author@present@group</code> 32	<code>\@ifx</code> 51
<code>\@author@present@group</code> .. 1041, 1142	<code>\@ifx</code> 309, 347, 348, 353, 359, 413, 432, 433, 442, 476, 499, 500, 511, 512, 526, 612, 621, 808, 860, 907, 971, 1006, 1007, 1012, 1013, 1026, 1027, 1080, 1106, 1115, 1123, 1132, 1199, 1243
<code>\@author@present@script</code> ... 32	<code>\@ifx@empty</code> 889, 892
<code>\@author@present@script</code> .. 920, 998	<code>\@ifxundefined</code> 1190–1194, 1282, 1287
<code>\@authorclear@sw</code> 20	<code>\@iiiparbox</code> 36
<code>\@authorclear@sw</code> 303, 325	<code>\@issuenum</code> 1252, 1253
<code>\@booleanfalse</code> 235, 236, 238, 240, 245, 250, 251, 261, 263, 301, 307, 423, 518, 630, 1191, 1320, 1321	<code>\@join</code> 23
<code>\@booleantrue</code> 234, 237, 239, 243, 244, 249, 255–257, 262, 298, 490, 613, 622, 1199, 1282, 1289, 1321	<code>\@join</code> 285, 321, 373, 418
<code>\@collaboration@count</code> . 926, 964	<code>\@keys@name</code> 1167
<code>\@collaboration@gobble</code> ... 601, 1111, 1120	<code>\@keywords</code> 669, 892, 893
<code>\@collaboration@present</code> .. 933, 952, 1046	<code>\@keywords@produce</code> .. 893, 1163
<code>\@currentlabel</code> 736	<code>\@listand</code> 31
<code>\@date</code> 58	<code>\@listand</code> 598, 607, 1102
<code>\@date</code> 676, 882	<code>\@listcomma</code> 31, 43, 44
<code>\@eid</code> 1254, 1255	<code>\@listcomma</code> . 581, 583, 588, 590, 599, 603, 1048, 1085, 1102
<code>\@email</code> 560, 561	<code>\@listcomma@comma</code> 583, 590, 599
<code>\@empty</code> 29	<code>\@listcomma@comma@UK</code> 600
<code>\@endpage</code> 1259, 1260	<code>\@listdepth</code> 715
<code>\@finalstrut</code> 739	<code>\@makefnmark</code> 663, 872, 975, 989, 1209
<code>\@firstofone</code> 377, 378, 1193	<code>\@makefntext</code> 37
<code>\@fnsymbol</code> 52	<code>\@makeother</code> 556–558
<code>\@fnsymbol</code> 1197	<code>\@maketitle</code> 56
<code>\@footnotemark</code> 33	<code>\@maketitle</code> 1287, 1291
<code>\@footnotemark</code> 848, 850	<code>\@minipagefalse</code> 727
<code>\@footnotetext</code> 712, 849, 851	<code>\@minipagerestore</code> 717
<code>\@homepage</code> 30	<code>\@mpfn</code> 639, 644, 661, 711,

736, 869, 1182, 1197, 1208,
1318, 1337

\@mpfootnotetext 37

\@mplistdepth 715

\@ne 32, 46

\@pacs 686, 889, 890

\@pacs@name 1154

\@pacs@produce 890, 1150

\@parboxrestore 710, 735

\@preprint 693, 695

\@provide 1038, 1055

\@published 676, 886

\@received 35

\@received 676, 883

\@reset@ac 580, 593

\@revised 676, 884

\@secondofthree .. 356, 357, 372

\@secondoftwo 355

\@separator .. 285, 321, 376, 418

\@setminipage 718

\@shorttitle 275, 278

\@startpage 55

\@startpage 1257, 1258

\@starttoc 1269

\@tempa . 24–26, 29, 42, 44, 45, 47

\@tempa 426, 427, 435, 631,
633, 971, 1022, 1027, 1030,
1034, 1131, 1132

\@tempb 26, 33

\@tempb .. 431–433, 623, 632, 637

\@tempc 24–26

\@tempc 443, 447, 458, 491

\@tempcnt 42

\@tempcnta 31, 32, 43, 48, 49

\@tempd 24–26

\@tempd 424, 433, 492

\@tempfix 475, 476, 611, 612, 620,
621, 971, 1105, 1106, 1114,
1115

\@textsuperscript 1201

\@tfor 1079

\@thanks 1311

\@thefnmark . 662, 736, 975, 989,
1183, 1202

\@title 274, 278, 904, 906

\@title@aux . 281, 283, 285, 907,
908

\@title@aux@cleared . 281, 283,
907

\@title@join 276, 283

\@title@join@ 283

\@undefined 48

\@undefined 28, 841, 1060, 1061,
1068, 1069, 1199

\@volumenumber 1250, 1251

\@volumeyear 1248, 1249

\@x@sf 658, 666

\\ 54, 57

\{ 136

\cmd_0ctober_1,_2020, argument
..... 58

\} 136

_ 49, 558

\~ 557

_ . 37, 43, 66, 67, 71, 90, 96, 102,
106, 115, 143, 216, 1102

A

\absbox 36

\absbox 697, 706, 799, 805

\abstract 841

abstract (environment) 698

abstract environment . 2, 15, 36

\abstractname 702, 764

\accepted 35

\accepted 676

\Accepted@name 682, 1273

\active 380

\active@comma 381, 382

\add@AUCC@grp 22

\add@AUCC@grp 324

\add@list@val@val@val 26

\add@list@val@val@val . 453, 469

\addcontents@abstract . 699, 722

\addcontentsline 702, 906

<address> placeholder 29

\AF@grp 26–29

\AF@grp .. 353, 458, 459, 498, 499,
509, 519, 524, 534, 538

<code>\AF@opr</code>	27, 29, 44, 45, 48, 50
<code>\AF@opr</code>	502, 508, 924, 931, 1062, 1070
<code>\AF@temp</code>	48
<code>\AF@temp</code>	1058, 1062, 1070, 1079, 1080
<code>\AFF@opr</code>	23, 26, 29, 45, 46, 51
<code>\AFF@opr</code>	427, 453, 941, 1095
<code>\affil@cutoff</code>	32, 46
<code>\affil@cutoff</code>	988, 997
<code>\affil@present@script</code>	970
<code>\affil@script</code>	29, 45
<code>\affil@script</code>	970
<code>\affiliation</code> 11, 13, 14, 23, 29, 30	
affiliation, argument	13
<code>\affiliation</code>	204, 208, 380, 831
<code><affiliation ID></code> placeholder	29
<code>\affils@present@group</code>	32, 54
<code>\affils@present@group</code>	1047, 1056
<code>\affils@present@script</code>	970
<code>\AFG@opr</code>	28, 29, 33, 44, 48
<code>\AFG@opr</code>	519, 523, 1047
<code>\after@address</code>	50
<code>\after@address</code>	1093, 1102, 1103, 1137
<code>\aftergroup</code>	32, 47, 51
<code>\aftergroup</code>	1028, 1031, 1148
<code>\aftermaketitle@chk</code>	670, 687, 705, 1242
<code>\altaffiliation</code> 13, 14, 19, 30, 32	
<code>\altaffiliation</code>	551, 576
<code>\altaffilletter@sw</code>	1197, 1199, 1320
<code>\and</code>	20, 23, 57
<code>\and</code>	379, 830, 1297, 1298, 1325
<code>\and@latex</code>	1297
<code>\and@space</code>	1325, 1339
<code>\andname</code>	598, 1340
<code>\appdef</code>	22, 26
<code>\appdef</code>	271, 278, 290, 300, 310, 341, 404, 470, 502, 508, 523, 538, 546, 570, 653, 673, 690, 694, 811, 859, 914, 1034, 1093, 1189, 1278
<code>\appdef@e</code>	503, 504, 510, 527, 528
<code>\appdef@eval</code>	458, 509, 524, 965
<code>\appendix</code>	1268
<code>\appendix@toc</code>	55
<code>\appendix@toc</code>	1268, 1272
argument	
<code>\cmd_0ctober_1,_2020</code>	58
affiliation	13
e-mail_address	13
miscellaneous_text	13
title	11
URL	13
argument, optional	
optional_text	13
article document class	20, 39, 56
<code>\AU@grp</code>	21, 22, 27, 28
<code>\AU@grp</code>	330, 347, 361, 498, 510, 511, 533, 538
<code>\AU@opr</code>	22, 28, 29, 44, 46, 48, 51
<code>\AU@opr</code>	330, 356, 925, 932, 1060, 1068, 1107, 1109, 1116, 1118
<code>\AU@temp</code>	43
<code>\AU@temp</code>	922, 926, 933, 934, 1044–1046
<code>\author</code> 11, 13, 14, 20, 23, 28, 30, 32, 57	
<code><author></code> placeholder	29
<code>\author</code>	47, 202, 206, 294, 314, 832, 1285
<code><auxiliary info></code> placeholder	29
<code><auxilliary info></code> placeholder	29
B	
<code>\baselineskip</code>	798, 814, 815, 917, 1325
bibnotes document class option	14
<code>\blankaffiliation</code>	51
<code>\blankaffiliation</code>	401, 1132
<code>\break</code>	1237
C	
<code>\c@affil</code>	19, 20
<code>\c@affil</code>	288, 446–448, 988
<code>\c@collab</code>	20
<code>\c@collab</code>	288, 327, 335, 451, 478
<code>\c@mpfootnote</code>	711, 871

`\c@page` 1257
`\cat@comma@active` 380, 381, 387
`\catcode` 380
`\centering` 763, 1323, 1325, 1329, 1330
`\changes` 140–192
`\class@documenthook` 19
`\class@documenthook` . 271, 570, 859
`\class@err` 379, 1244
`\class@info` 861
`\class@name` 230
`\class@warn` 56
`\class@warn` . 279, 360, 363, 434, 550, 756, 1158, 1171, 1279
`\class customization commands` placeholder 10
`\classname` . 58, 65, 124, 126, 128
`\classoption` 187
`\clearpage` 844
`\clo@groupedaddress` .. 241, 242
`\clo@runinaddress` 253, 254
`\clo@superscriptaddress` .. 259, 260
`\clo@unsortedaddress` . 247, 248
`\cmd` 136
`\CO@grp` 21, 27, 28, 32
`\CO@grp` .. 328, 348, 359, 364, 498, 500, 503–505, 512, 526–529, 532, 540
`\CO@opr` 27, 29, 48
`\CO@opr` 328, 357, 520, 926, 928, 933, 1046, 1061, 1069, 1111, 1120
`\collaboration` 11, 13, 14, 20, 21, 25, 27, 28, 30
`\collaboration` 297, 314
`\collaboration@sw` 298, 301, 307, 326, 1189
`\collaboration ID` placeholder . 29
`\color@begingroup` 707, 737
`\color@endgroup` 728, 741
`\columnwidth` 708, 709
`\comma@space` .. 606, 1000, 1143, 1189
`\copyright` 43

`\count` 44
`\count@` 51
`\count@` 1124, 1125, 1130
`\cs` . 140, 143, 145, 146, 148, 152, 160, 161, 164, 165, 167–169, 171, 172, 175–180, 183–189
`\csname` 30, 34, 40, 44
`\csname` 28, 29, 644, 661, 701, 736, 1182, 1197, 1208, 1266, 1318, 1337

D

`\date` 11, 35, 55, 57, 58
`\date` placeholder 11
`\date` 210, 676, 1286
`\Dated@name` 676, 1273
`\def@after@address` . 1087, 1102
`\def@after@address@empty` 1102
`\dimen@` 798, 800, 801
`\do` 1079
`\do@affil@fromgroup` 51
`\do@affil@fromgroup` 1096, 1122
`\do@output@MVL` 788, 1189
`\do@title` 273
`\doauthor` 32, 44, 47, 51
`\doauthor` 602, 1001, 1144
`doc` 5
`doc/` 3
`\DocInput` 10
`docstrip document class` 17
`document class`
 `article` 20, 39, 56
 `docstrip` 17
 `frontmatter` 18
 `hyperref` .. 33, 36, 37, 40, 53
 `ltxdoc` 5, 10
 `ltxfront` 1, 3, 16, 57
 `ltxfront.dtx` 3
 `ltxfront.pdf` 3
 `ltxfront.sty` 3
 `ltxgrid` 56
 `ltxutil` 16, 37, 53
 `revtex4` 54
`document class option`
 `bibnotes` 14

groupedaddress . 12, 17, 18,
29, 32, 47, 48, 50, 51, 54

nobibnotes 14

noshowkeys 15

noshowpacs 15

preprint 15

runinaddress 17, 18, 48

showkeys 15

showpacs 15

superscriptaddress . 12, 13,
17, 18, 23, 26, 32, 42, 44–46,
54, 73

unsortedaddress 12, 13, 17,
18, 48

document environment 5

\documentclass 15, 16

E

e-mail_␣address, argument . . . 13

\edef 658

\eid 1254

\email 11, 13, 14, 19, 30, 32

\email 551, 555, 837

\endabstract 36

\endabstract 841

\endcsname 40

\endcsname 28, 29, 644, 661,
701, 736, 1182, 1197, 1208,
1266, 1318, 1337

\endminipage 36

\endpage 1259

environment

 abstract 2, 15, 36

 document 5

 frontmatter@abstract . . 56

 frontmatter@titlepage . 56

 minipage 36

environments:

 abstract 698

 titlepage 816

\everypar 36

F

\false@sw 17, 32

\false@sw . . . 350, 481, 487, 514,
1028, 1148

file

 \$TEXMF/ 3

 .dtx 5

 doc 5

 doc/ 3

 latex/ 3

 ltxfront 3, 57

 ltxfront-test.tex 3

 ltxfront.dtx 3

 ltxfront.pdf 1

 ltxfront.sty 1, 3

 makeindex 3

 package 2, 16

 README-LTXFRONT 3, 5

 revtex/ 3

 source/ 3

 tex/ 3

 texmf-local/ 3

\file . 76, 79, 85, 86, 95, 102, 103,
106, 109, 110, 113, 114, 117,
118, 124, 126, 128, 130, 133

\firstname 15

\firstname 377

\footnote 57

\footnote 358, 721, 749, 750

\footnotemark . . . 751, 752, 1307

\footnotesep 739

\footnotetext . . . 753, 754, 1315,
1334

frontmatter document class . . 18

\frontmatter@above@aaffilgroup
 1066, 1228

\frontmatter@above@aaffiliation
 54

\frontmatter@above@aaffiliation
 . . . 1075, 1229, 1327

\frontmatter@above@aaffiliation@script
 54

\frontmatter@above@aaffiliation@script
 940, 1229, 1328

frontmatter@abstract environment
 56

\frontmatter@abstract@produce
 785, 888

\frontmatter@abstractfont . 36

\frontmatter@abstractfont	720, 768	 943, 1050, 1189
\frontmatter@abstractheading 36	\frontmatter@footnote@produce@endnote 1175
\frontmatter@abstractheading 719, 761	\frontmatter@footnote@produce@footnote 1175 , 1192
\frontmatter@abstractwidth	36	\frontmatter@footnotemark	636, 650, 656
\frontmatter@abstractwidth	784	\frontmatter@footnotetext	712, 731 , 1184, 1332
\frontmatter@addressnewline 1077, 1236	\frontmatter@init 19
\frontmatter@affiliationfont 46	\frontmatter@init	271 , 278, 290, 300, 310, 404, 538, 546, 653, 673, 690, 694, 811, 1189
\frontmatter@affiliationfont	. 987, 1076, 1231 , 1329	\frontmatter@keys@format	1166, 1234
\frontmatter@and 56	\frontmatter@makefnmark	.. 872, 1200
\frontmatter@and 379, 1298	\frontmatter@makefntext	... 37
\frontmatter@author 56	\frontmatter@makefntext	.. 738, 1205
\frontmatter@author	. 294, 1285	\frontmatter@maketitle 56
\frontmatter@author@produce	42 , 47 , 48	\frontmatter@maketitle	... 826, 862, 1288, 1291
\frontmatter@author@produce@group 48	\frontmatter@noaffiliation	395, 1294
\frontmatter@author@produce@group 877, 1039	\frontmatter@PACS@format	1153, 1233
\frontmatter@author@produce@script 42 , 44	\frontmatter@postabstractspace 809, 814 , 1240
\frontmatter@author@produce@script 879, 918	\frontmatter@preabstractspace	789, 795, 814 , 1240 , 1331
\frontmatter@authorbelow	1053, 1055, 1326	\frontmatter@RRAP@format	.. 53
\frontmatter@authorformat	930, 1042, 1227 , 1325	\frontmatter@RRAP@format	1216, 1232 , 1330
\frontmatter@collaboration@above 955, 963	\frontmatter@RRAPformat	... 53
\frontmatter@date 56	\frontmatter@RRAPformat	.. 881, 1213
\frontmatter@date	... 676, 1286	\frontmatter@setup	.. 873, 1212
\frontmatter@description	. 769	\frontmatter@syntax@sw	... 236, 237, 1282, 1283
\frontmatter@descriptionlabel 774, 779	\frontmatter@thanks 56
\frontmatter@finalspace	.. 896, 1235	\frontmatter@thanks	. 573, 1296
\frontmatter@foot@mark 34	\frontmatter@thefootnote	. 662, 1183, 1196
\frontmatter@foot@mark	641, 649	\frontmatter@title 56
\frontmatter@footnote	606, 628 , 908, 977, 992, 1135	\frontmatter@title	.. 273, 1284
\frontmatter@footnote@produce			

`\frontmatter@title@above` .. 42
`\frontmatter@title@above` . 902,
 915, 1322
`\frontmatter@title@below` .. 42
`\frontmatter@title@below` . 911,
 915, 1324
`\frontmatter@title@format` . 42
`\frontmatter@title@format` 903,
 915, 1323
`\frontmatter@title@produce` 875,
 899
`frontmatter@titlepage` environment
 56
`\frontmatterverbose@sw` 17
`\frontmatterverbose@sw` ... 234,
 235, 314, 342, 345, 361, 364,
 384, 396, 459, 471, 498, 536,
 921, 1043

G

`\g@addto@macro` 651
`\gappdef` 693, 1309
`\GetFileInfo` 34
`\groupauthors@sw` . 17, 18, 26, 48
`\groupauthors@sw` . 240, 243, 249,
 255, 261, 477, 876
`\groupedaddress` 241
`groupedaddress` document class op-
 tion 12, 17, 18, 29, 32, 47,
 48, 50, 51, 54

H

`\H@@footnotemark` 850
`\H@@footnotetext` 851
`\homepage` .. 11, 13, 14, 19, 30, 32
`\homepage` 551, 565
`\href` 355, 563, 568, 570
`\ht` 800
`\Hy@maketitle@end` 856
`\Hy@maketitle@optarg` 853
`\Hy@raisedlink` 53
`\Hy@raisedlink` 1208
`\Hy@saved@footnotemark` ... 848
`\Hy@saved@footnotetext` ... 849
`\HyOrg@maketitle` 855
`\hyper@anchorend` 1208

`\hyper@anchorstart` 1208
`\hyper@linkend` 664
`\hyper@linkstart` 660
`hyperref` document class . 33, 36,
 37, 40, 53

I

`\if@titlepage` 56
`\if@titlepage` 1321
`\iffalse` 51
`\ifx` 48
`\ignorespaces` 603, 739, 958, 975,
 991, 1223
`\issuenumber` 1252
`\item` 100, 105, 116, 119, 123, 125,
 127, 132, 134
`\itemindent` 773
`\itshape` 1231, 1329

K

`\keywords` 15, 35
`\keywords` 669

L

`\l@section` 55
`\label` 874
`\labelsep` 780
`\labelwidth` 772
`\LARGE` 1323
`\large` 763, 1325, 1330
`\lastskip` 1237
`\LaTeX` . 37, 66, 67, 77, 87, 90, 106,
 112, 115, 117, 143, 216
`latex/` 3
`\LaTeXe` 71, 96, 227
`\leftmargin` 771
`\let@environment` 716, 1299, 1300
`\let@mark` 914
`\listand` 43
`\listand` 598
`\listcomma` 43
`\ltx@footnote@pop` 868
`\ltx@no@footnote` 744
`\ltx@no@footwarn` 744
`\ltx@no@xfootmark` 746, 751
`\ltx@no@xfootnote` 745, 749

`\ltx@no@xfoottext` 747, 753
`\ltx@no@yfootmark` 746, 752
`\ltx@no@yfootnote` 745, 750
`\ltx@no@yfoottext` 747, 754
`\ltx@xfootmark` 746
`\ltx@xfootnote` 745
`\ltx@xfoottext` 747
`\ltx@yfootmark` 746
`\ltx@yfootnote` 745
`\ltx@yfoottext` 747
`ltxdoc` document class 5, 10
`ltxfront` 3, 57
`ltxfront` document class 1, 3, 16, 57
`ltxfront-test.tex` 3
`ltxfront.dtx` 3
`ltxfront.dtx` document class 3
`ltxfront.pdf` 1
`ltxfront.pdf` document class 3
`ltxfront.sty` 1, 3
`ltxfront.sty` document class 3
`ltxgrid` document class 56
`ltxutil` document class 16, 37, 53

M

`makeindex` 3
`\makelabel` 774
`\maketitle` 11, 15, 16, 19, 34, 36, 40, 55–58
`\maketitle` 56, 213, 826, 860–862, 1243, 1244, 1288, 1292
`\maketitle@Hy` 847
`\mini@note` 36
`\mini@note` 721
`\mini@notes` 808, 811
`\minipage` 36
`minipage` environment 36
`\minipagefootnote@drop` 742
`\minipagefootnote@here` 726
`\minipagefootnote@init` 713
`\minipagefootnote@pick` 732
`miscellaneous␣text`, argument 13
`\move@AF` 20, 26
`\move@AF` 315, 346, 367, 385, 397, 398, 421
`\move@AU` 20–22

`\move@AU` 315, 324, 346, 385, 397
`\move@AUAF` 20
`\move@AUAF` 315, 370, 399, 497
`\mp@footnotetext` 37

N

`\newbox` 697
`\newcounter` 19, 20
`\noaffiliation` 13, 22–25, 27, 46, 47, 50, 51
`\noaffiliation` 360, 363, 395, 1294, 1302
`nobibnotes` document class option 14
`\normalfont` 781, 1202
`noshowkeys` document class option 15
`noshowpacs` document class option 15

O

`\onecolumngrid` 817
`optional␣text`, optional argument 13
`\OptionNotUsed` 267

P

`package` 2, 16
`\package@name` 225, 226, 230
`\PackageInfo` 226
`\pacs` 15
`\pacs` 686
`\PACS@warn` 1158, 1162
`\pageref` 1258, 1260
`\parindent` 36
`\parindent` 1206
`\parskip` 36
`\parskip` 1091, 1325
`\phantomsection` 700, 906
`placeholder`
 `⟨address⟩` 29
 `⟨affiliation ID⟩` 29
 `⟨author⟩` 29
 `⟨auxiliary info⟩` 29
 `⟨auxilliary info⟩` 29
 `⟨class customization commands⟩` 10

<collaboration ID> 29
<date> 11
<your document here> 10
\post@absbox 806, 813
\prep@absbox 804, 812
\prepdef 1292
\preprint 16
\preprint 693
preprint document class option 15
\preprintsty@sw 787, 1189
\present@bibnote 52
\present@FM@footnote 1176, 1180
\prevdepth 800
\print@toc 1261
\produce@RRAP 53
\produce@RRAP ... 882–886, 1213
\protected@edef 736
\providecommand 571
\ProvidesFile 6
\ps@empty 1247
\ps@titlepage 1247
\published 35
\published 676
\Published@name 684, 1273
\punct@RRAP 53
\punct@RRAP 1213

R

README-LTXFRONT 3, 5
\received 35
\received 676
\Received@name 678, 1273
\RecordChanges 32
\relax 23, 40, 47, 50
\removelastskip 1214
\RequirePackage . 25, 27, 29, 231
\revised 35
\revised 211, 676
\Revised@name 680, 1273
revtex/ 3
revtex4 document class 54
\robustify@contents 1278
\rule 739
\runinaddress 253
runinaddress document class option 17, 18,

48

\runinaddress@sw 17, 18
\runinaddress@sw . 238, 245, 251, 257, 263, 1088

S

\sanitize@url 555, 560, 565
\say 342, 361, 364, 459, 471, 498, 536, 921, 1043
\sc 87
\section 55
\section 83, 215, 1263
\set@footnotefont 733
\set@footnotewidth 734
\set@listcomma@count 31
\set@listcomma@count 579, 1067
\set@listcomma@list 31
\set@listcomma@list . 579, 934, 961, 1045
\set@listindent 714
\set@listindent@ 714
showkeys document class option 15
\showKEYS@sw 1164
showpacs document class option 15
\showPACS@sw 1151
\skip@ 1237
source/ 3
\spacefactor 658, 666
\special 36
\startpage 1257
\stepcounter 639
\StopEventually 6
\string .. 314, 345, 360, 363, 384, 396, 551, 757, 758, 861, 921, 1043, 1280
\strutbox 739
\subsection 93, 139
\superscriptaddress 259
superscriptaddress document class option 12, 13, 17, 18, 23, 26, 32, 42, 44–46, 54, 73
\suppressfloats 829
\surname 15
\surname 377

T

`\tableofcontents` 81
`\temp@sw` 24–26, 33
`\temp@sw` . 423, 429, 474, 490, 518,
 522, 610, 613, 619, 622, 630,
 635
`\TeX` 71, 102, 117
`tex/` 3
`texmf-local/` 3
`\textsuperscript` 47
`\textsuperscript` .. 1000, 1030,
 1143
`\texttt` .. 49, 113, 114, 121, 130,
 133, 136, 163, 164, 183
`\textwidth` 708, 784
`\thanks` . 11, 13, 14, 19, 30–32, 57
`\thanks` 38, 42,
 49, 203, 207, 551, 573, 758,
 840, 1279, 1295, 1296, 1323,
 1325
`\thanks@latex` . 1295, 1306, 1323,
 1325
`\the` 19, 20, 34
`\theaffil` 19
`\thecollab` 20
`\thempfn` 711, 870
`\thempfootnote` 711, 870
`\thispagestyle` 818, 874
`\tightenlines@sw` 1090
`\title` 11, 14, 19, 56, 57
`title`, argument 11
`\title` 36, 200, 273, 1284
`\title@column` 828, 1189
`\titleblock@produce` .. 828, 866
`titlepage` (environment) ... 816
`\titlepage@sw` .. 842, 1289, 1321
`\toclevel@abstract` 698
`\toclevel@title` 899
`\today` 11, 58
`\true@sw` 32
`\true@sw` 479, 484, 1031
`\tw@` 32, 46
`\twocolumn@sw` 817, 821
`\twocolumngrid` 821
`\twoside@sw` 822

U

`\undefined` 40
`\unpenalty` 1237
`\unskip` .. 603, 725, 905, 936, 958,
 1223, 1237
`\unsortedaddress` 247
`unsortedaddress` document class op-
 tion 12, 13, 17, 18,
 48
`\unvbox` 805
`\unvcopy` 799
`URL`, argument 13
`\url` 26, 62, 68
`\usepackage` 4

V

`\vadjust` 739
`\vbox` 706
`\volumenumber` 1250
`\volumeyear` 1248
`\vtop` 799

X

`\x@match` 33
`\x@match` 519, 609

Y

`\y@match` 33
`\y@match` 618, 633
`<your document here>` placeholder
 10

Z

`\z@` 50
`\z@skip` 739, 1038

Change History

4.0b	<ul style="list-style-type: none"> <code>\@author@join</code>: Change handling of <code>\@author</code> to prevent parsing problems. (Helps in error recovery when syntax errors exist) 20 <code>\@pacs@produce</code>: Separate option now controls production 51 <code>\titleblock@produce</code>: Set <code>\footnote</code> to L^AT_EX standard version for this scope. 41 General: Change handling of <code>\@author</code> to prevent parsing problems. (Helps in error recovery when syntax errors exist) 4 Gathered all code for the abstract environment together and abstracted out the formatting details for journals to override. 4, 36 Separate option now controls production 4 Set <code>\footnote</code> to L^AT_EX standard version for this scope. 4 	4.0e	<ul style="list-style-type: none"> <code>\@keywords@produce</code>: Keywords on same footing as PACS . . . 52 <code>\@pacs@produce</code>: Warn if no production 51 General: Keywords on same footing as PACS 4 Warn if no production 4
		4.0f	<ul style="list-style-type: none"> <code>\@author@finish</code>: Actually append <code>\AU@grp</code> to <code>\@AAClist</code>. 22 General: Actually append <code>\AU@grp</code> to <code>\@AAClist</code>. 4
		4.0g	<ul style="list-style-type: none"> General: multiple preprint commands 4, 35
		4.0h	<ul style="list-style-type: none"> <code>\@author@present@script</code>: Changes to support groups of affiliations 46 <code>\frontmatter@addressnewline</code>: new hook 54 <code>\move@AUAF</code>: Changes to support groups of affiliations 27 General: Changes to support groups of affiliations 4 new hook 4
4.0c	<ul style="list-style-type: none"> General: grid changes with ltxgrid 4 <code>titlepage</code>: grid changes with ltxgrid 39 	4.0i	<ul style="list-style-type: none"> <code>\altaffiliation</code>: add optional argument handling back 31 <code>\frontmatter@author@produce@script</code>: Changes to add collaboration processing, which now means doing comma/and processing on each sublist 42 <code>\set@listcomma@count</code>: macro added 31 General: add optional argument handling back 4 Changes to add collaboration processing, which now means doing comma/and processing on each sublist 4 macro added 4
4.0d	<ul style="list-style-type: none"> <code>\@affil@present@group</code>: <code>\comma@space</code> 51 <code>\@pacs@produce</code>: PACS boxed to width of abstract 51 <code>\altaffiliation</code>: change name from <code>\tempaffiliation</code> 31 <code>\maketitle</code>: hookify 40 General: <code>\comma@space</code> 4 change name from <code>\tempaffiliation</code> 4 hookify 4 If empty <code>\abstractname</code> omit spacing 4 PACS boxed to width of abstract 4 <code>abstract</code>: hookify 36 If empty <code>\abstractname</code> omit spacing 36 	4.1a	<ul style="list-style-type: none"> <code>\affil@present@script</code>: removed code that had been commented

out	45	\affiliation: Use \@affil@def	
\affils@present@script:		for all access to \@affil	23
removed code that had been		\affils@present@group: Provide	
commented out	44	for diagnostics via	
\email: (AO, 496) remove default		\frontmatterverbose@sw ...	48
prependation to \email.	30	\author: Make the syntax of this	
\homepage: (AO, 496) remove		package switch optional	20
default prependation to		\c@collab: (AO, 486)	
\homepage.	30	\collaboration to work with	
General: (AO, 443) create an entry		groupedaddress	19
in the PDF bookmarks for the		\collaboration: (AO, 486)	
abstract via the toc	4	\collaboration to work with	
(AO, 496) remove default		groupedaddress	20
prependation to \email.	4	\do@title: Make the syntax of	
(AO, 496) remove default		this package switch optional ..	19
prependation to \homepage. ...	4	\doauthor: Provide facility	
removed code that had been		\affil@cutoff: if there is only	
commented out	4	one affiliation on the title page,	
abstract: (AO, 443) create an		no superscript	32
entry in the PDF bookmarks		\frontmatter@author@produce@group:	
for the abstract via the toc ..	36	Provide for diagnostics via	
4.1b		\frontmatterverbose@sw ...	47
\@affil@join: Use \@affil@def		\frontmatter@author@produce@script:	
for all access to \@affil	24	Provide for diagnostics via	
\@affil@match: (AO, 486)		\frontmatterverbose@sw ...	42
\collaboration to work with		\frontmatter@title@produce:	
groupedaddress	26	(AO, 443) PDF Bookmark for	
\@author@finish: (AO, 486)		title page	42
\collaboration to work with		\move@AF: (AO, 486)	
groupedaddress	22	\collaboration to work with	
Provide for diagnostics via		groupedaddress	24
\frontmatterverbose@sw ...	22	Provide for diagnostics via	
Use \@affil@def for all access		\frontmatterverbose@sw ...	26
to \@affil	22	\move@AUAF: (AO, 486)	
\@author@join: (AO, 486)		\collaboration to work with	
\collaboration to work with		groupedaddress	27
groupedaddress	20	Change csname \AFS@opr to	
Use \frontmatter@init as the		\AFG@opr	27
vehicle for all initialization ..	20	Provide for diagnostics via	
\@published: Make the syntax of		\frontmatterverbose@sw ...	27
this package switch optional ..	35	\noaffiliation: Use \@affil@def	
\@shorttitle: Use		for all access to \@affil	23
\frontmatter@init as the		\thanks: Make the syntax of this	
vehicle for all initialization ..	19	package switch optional	31
\add@AUCO@grp: (AO, 486)		General: (AO, 443) PDF	
\collaboration to work with		Bookmark for title page	4
groupedaddress	21	(AO, 455) provide a	
Provide for diagnostics via		description environment for	
\frontmatterverbose@sw ...	22	the abstract	4

(AO, 486) <code>\collaboration</code> to work with <code>groupedaddress</code> . . . 4	defined in <code>ltxutil</code> 4
Change csname <code>\AFS@opr</code> to <code>\AFG@opr</code> 4	<code>\@author@finish</code> : (AO, 535) Robustify <code>\footnote</code> while <code>\class@warn</code> is expanding its argument 22
Make the syntax of this package switch optional 4, 56	General: (AO, 535) Robustify <code>\footnote</code> while <code>\class@warn</code> is expanding its argument 4
Provide facility <code>\affil@cutoff</code> : if there is only one affiliation on the title page, no superscript 4	(AO, 539) Robustify <code>\class@warn</code> against TOC processing 4, 56
Provide for diagnostics via <code>\frontmatterverbose@sw</code> 4	
Use <code>\@affil@def</code> for all access to <code>\@affil</code> 4	
Use <code>\frontmatter@init</code> as the vehicle for all initialization . . . 4	<code>\@author@finish</code> : (AO, 540) More runtime diagnostics via <code>\frontmatterverbose@sw</code> . . . 22
<code>frontmatter@description</code> : (AO, 455) provide a <code>description</code> environment for the abstract . 38	<code>\@author@join</code> : (AO, 540) More runtime diagnostics via <code>\frontmatterverbose@sw</code> . . . 21
<code>titlepage</code> : Make the syntax of this package switch optional . 39	<code>\affiliation</code> : (AO, 540) More runtime diagnostics via <code>\frontmatterverbose@sw</code> . . . 23
4.1c <code>\def@after@address@empty</code> : Parametrize the production after the address 50	<code>\frontmatter@author@produce@group</code> : (AO, 540) More runtime diagnostics via <code>\frontmatterverbose@sw</code> . . . 48
<code>\maketitle@Hy</code> : Hyperref compatibility: take <code>\maketitle</code> back. 40	<code>\frontmatter@author@produce@script</code> : (AO, 540) More runtime diagnostics via <code>\frontmatterverbose@sw</code> . . . 42
<code>\titleblock@produce</code> : Produce PACS, keywords only if specified 41	<code>\move@AF</code> : (AO, 540) Rationalize code that appends to <code>\AF@grp</code> 24, 26
General: Hyperref compatibility: take <code>\maketitle</code> back. 4	<code>\move@AUAF</code> : (AO, 540) More runtime diagnostics via <code>\frontmatterverbose@sw</code> . . . 27
Parametrize the production after the address 4	<code>\noaffiliation</code> : (AO, 540) More runtime diagnostics via <code>\frontmatterverbose@sw</code> . . . 23
Produce PACS, keywords only if specified 4	General: (AO, 540) More runtime diagnostics via <code>\frontmatterverbose@sw</code> 4
4.1d <code>\@affil@group</code> : (AO, 410) compare <code>\@tempa</code> to <code>\blankaffiliation</code> 51	(AO, 540) Optimize boolean logic 4
General: (AO, 410) compare <code>\@tempa</code> to <code>\blankaffiliation</code> 4	(AO, 540) Rationalize code that appends to <code>\AF@grp</code> 4
4.1f <code>\frontmatter@footnotetext</code> : (AO, 515) Use <code>\set@footnotefont</code> , which is defined in <code>ltxutil</code> 37	(AO, 544) Class options <code>ruinaddress</code> and <code>unsortedaddress</code> stopped working 4
General: (AO, 515) Use <code>\set@footnotefont</code> , which is	

4.1m	
\@author@finish: (AO, 563)	authors' extra information,
\collaboration to work with	such as \email 32
both groupedaddress and	\frontmatter@footnote: (AO,
superscriptaddress 22	572) Independent footnote
\@collaboration@gobble: (AO,	counter for title block.
563) Let	Abstract footnote counter
\@collaboration@gobble	shared with body. 34
parse all three arguments of	\frontmatter@footnote@produce@endnote:
\C0@opr 32	(AO, 572) Independent
\frontmatter@author@produce@group:	footnote counter for title block.
(AO, 563) More complete	Abstract footnote counter
runtime diagnostics via	shared with body. 52
\frontmatterverbose@sw . . . 48	\frontmatter@footnotetext:
\frontmatter@author@produce@script:	(AO, 571) allow split after last
(AO, 563) More complete	line of footnote 37
runtime diagnostics via	(AO, 572) Independent footnote
\frontmatterverbose@sw . . . 42	counter for title block.
\move@AUAF: (AO, 563)	Abstract footnote counter
\collaboration to work with	shared with body. 37
both groupedaddress and	\frontmatter@makefntext: (AO,
superscriptaddress 28	572) Independent footnote
General: (AO, 563) Let	counter for title block.
\@collaboration@gobble	Abstract footnote counter
parse all three arguments of	shared with body. 53
\C0@opr 4	\frontmatter@thefootnote: (AO,
(AO, 563) More complete	572) Independent footnote
runtime diagnostics via	counter for title block.
\frontmatterverbose@sw 4	Abstract footnote counter
(AO, 563) \collaboration to	shared with body. 52
work with both	\homepage: (AO) remove http://
groupedaddress and	from \href call 30
superscriptaddress 4	\move@AF: (AO, 567) Handle
	\noaffiliation case 24
	\noaffiliation: (AO, 567)
4.1n	Handle \noaffiliation case . 23
\@affil@join: (AO, 567) Handle	\titleblock@produce: (AO, 572)
\noaffiliation case 24	Independent footnote counter
\@affil@present@script@: (AO,	for title block. Abstract
567) Handle punctuation for	footnote counter shared with
superscriptaddress style	body. 41
authors' extra information,	General: (AO) remove http://
such as \email 47	from \href call 4
\@author@finish: (AO, 567)	(AO, 567) Handle
Handle \noaffiliation case . 22	\noaffiliation case 4
\@author@present@script: (AO,	(AO, 567) Handle punctuation
567) Handle \noaffiliation	for superscriptaddress style
case 46	authors' extra information,
\doauthor: (AO, 567) Handle	such as \email 4
punctuation for	(AO, 571) Interface
superscriptaddress style	\set@footnotewidth for

determining the set width of	shared with body.	4, 57, 58
footnotes	4	4.2a
(AO, 571) allow split after last		
line of footnote	4	
(AO, 572) Independent footnote		General: (MD) Updated name of
counter for title block.		README file and use
Abstract footnote counter		standard fonts when
		typesetting
		4