

siunitx – A comprehensive (SI) units package*

Joseph Wright[†]

Released 2021-06-09

Contents

| | | |
|------------|---|-----------|
| I | siunitx – Overall set up | 1 |
| 1 | siunitx implementation | 1 |
| 1.1 | Initial set up | 1 |
| 1.2 | Safety checks | 1 |
| 1.3 | Provide a kernel command | 2 |
| 1.4 | Top-level scratch space | 2 |
| 1.5 | Load time options | 2 |
| 1.6 | Option handling | 3 |
| 1.7 | User interfaces | 3 |
| 1.7.1 | Preamble commands | 3 |
| 1.7.2 | Document commands | 3 |
| 1.8 | “Glue” commands | 6 |
| 1.9 | Table column | 7 |
| 1.10 | Document commands in bookmarks | 8 |
| II | siunitx-angle – Formatting angles | 12 |
| 1 | Formatting angles | 12 |
| 1.1 | Key-value options | 12 |
| 2 | siunitx-angle implementation | 13 |
| III | siunitx-compound – Compound numbers and quantities | 20 |
| 1 | siunitx-compound implementation | 22 |
| 1.1 | General mechanism | 22 |
| 1.2 | Lists | 31 |
| 1.3 | Products | 32 |
| 1.4 | Ranges | 33 |
| 1.5 | Standard settings for module options | 34 |

*This file describes v3.0.12, last revised 2021-06-09.

[†]E-mail: joseph.wright@morningstar2.co.uk

| | | |
|-------------|--|------------|
| IV | siunitx-locale – Localisation | 36 |
| 1 | siunitx-locale implementation | 36 |
| 1.1 | Locales | 36 |
| 1.2 | Localisation | 37 |
| V | siunitx-number – Parsing and formatting numbers | 38 |
| 1 | Formatting numbers | 38 |
| 1.1 | Key-value options | 40 |
| 2 | siunitx-number implementation | 43 |
| 2.1 | Initial set-up | 43 |
| 2.2 | Main formatting routine | 43 |
| 2.3 | Parsing numbers | 44 |
| 2.4 | Processing numbers | 60 |
| 2.5 | Number modification | 78 |
| 2.6 | Outputting parsed numbers | 79 |
| 2.7 | Miscellaneous tools | 87 |
| 2.8 | Messages | 89 |
| 2.9 | Standard settings for module options | 89 |
| VI | siunitx-print – Printing material with font control | 91 |
| 1 | Printing quantities | 91 |
| 1.1 | Key-value options | 92 |
| 2 | siunitx-print implementation | 94 |
| 2.1 | Initial set up | 94 |
| 2.2 | Printing routines | 94 |
| 2.3 | Standard settings for module options | 103 |
| VII | siunitx-quantity – Quantities | 104 |
| 1 | siunitx-quantity implementation | 104 |
| 1.1 | Initial set-up | 105 |
| 1.2 | Main formatting routine | 105 |
| 1.3 | Standard settings for module options | 108 |
| 1.4 | Adjustments to units | 108 |
| VIII | siunitx-symbol – Symbol-related settings | 110 |
| 1 | siunitx-symbol implementation | 110 |
| 1.1 | Bookmark definitions | 113 |
| IX | siunitx-table – Formatting numbers in tables | 114 |

| | | |
|------------|---|------------|
| 1 | Numbers in tables | 114 |
| 1.1 | Key-value options | 114 |
| 2 | siunitx-table implementation | 116 |
| 2.1 | Interface functions | 116 |
| 2.2 | Collecting tokens | 116 |
| 2.3 | Separating collected material | 119 |
| 2.4 | Printing numbers in cells: spacing | 121 |
| 2.5 | Printing just text | 122 |
| 2.6 | Number alignment: core ideas | 123 |
| 2.7 | Directly printing without collection | 126 |
| 2.8 | Printing numbers in cells: main functions | 128 |
| 2.9 | Standard settings for module options | 135 |
| X | siunitx-unit – Parsing and formatting units | 137 |
| 1 | Formatting units | 137 |
| 2 | Defining symbolic units | 139 |
| 3 | Per-unit options | 140 |
| 4 | Units in (PDF) strings | 140 |
| 5 | Pre-defined symbolic unit components | 140 |
| 5.1 | Key-value options | 143 |
| 6 | siunitx-unit implementation | 145 |
| 6.1 | Initial set up | 145 |
| 6.2 | Defining symbolic unit | 146 |
| 6.3 | Applying unit options | 148 |
| 6.4 | Non-standard symbolic units | 149 |
| 6.5 | Main formatting routine | 150 |
| 6.6 | Formatting literal units | 152 |
| 6.7 | (PDF) String creation | 155 |
| 6.8 | Parsing symbolic units | 155 |
| 6.9 | Formatting parsed units | 160 |
| 6.10 | Non-Latin character support | 172 |
| 6.11 | Pre-defined unit components | 173 |
| 6.12 | Messages | 175 |
| 6.13 | Standard settings for module options | 176 |
| XI | siunitx-abbreviations – Abbreviations | 177 |
| 1 | siunitx-abbreviation implementation | 179 |
| XII | siunitx-binary – Binary units | 183 |

| | | |
|---|--|------------|
| 1 | siunitx-binary implementation | 183 |
| XIII siunitx-command – Units as document command | | 184 |
| 1 | Creating units as document commands | 184 |
| 1.1 | Key-value options | 184 |
| 2 | siunitx-command implementation | 185 |
| 2.1 | Options | 185 |
| 2.2 | Creation of unit document commands | 186 |
| 2.3 | Standard settings for module options | 187 |
| XIV siunitx-emulation – Emulation | | 188 |
| 1 | siunitx-emulation implementation | 188 |
| 1.1 | Load-time option | 189 |
| 1.2 | Angle options | 189 |
| 1.3 | Combination functions options | 189 |
| 1.4 | Command options | 190 |
| 1.5 | Print options | 190 |
| 1.6 | Symbol options | 192 |
| 1.7 | Number options | 192 |
| 1.7.1 | Table options | 196 |
| 1.8 | Unit options | 198 |
| 1.9 | Quantity units | 199 |
| 1.10 | Preamble commands | 200 |
| 1.11 | Document commands | 201 |
| 1.12 | Symbol commands | 202 |
| Index | | 206 |

Part I

siunitx – Overall set up

1 siunitx implementation

Start the DocStrip guards.

```
1  {*package}
   Identify the internal prefix (LATEX3 DocStrip convention).
2  {@@=siunitx}
```

1.1 Initial set up

```
3  {*init}
```

Set up a couple of commands in recent-ish L^AT_EX 2_E releases.

```
4  \providecommand\DeclareRelease[3]{}
5  \providecommand\DeclareCurrentRelease[2]{}
```

Allow rollback to version 2: if we need to, version 1 could eventually be added here too.

```
6  \DeclareRelease{2}{2010-05-23}{siunitx-v2.sty}
7  \DeclareRelease{v2}{2010-05-23}{siunitx-v2.sty}
8  \DeclareCurrentRelease{}{2021-05-17}
```

Load only the essential support (expl3) “up-front”, and only if required.

```
9  \@ifundefined{ExplFileVersion}
10   {\RequirePackage{expl3}}
11   {}
```

Make sure that the version of l3kernel in use is sufficiently new. We use \ExplFileVersion as \@ifpackagelater doesn’t work for pre-loaded expl3 in the absence of the package.

```
12  \@ifl@t@r\ExplFileVersion{2018-06-01}
13  {}
14  {%
15   \PackageError{siunitx}{Support package expl3 too old}
16   {%
17    You need to update your installation of the bundles 'l3kernel' and
18    'l3packages'. \MessageBreak
19    Loading~siunitx~will~abort!%
20   }%
21   \endinput
22 }
```

Identify the package and give the over all version information.

```
23  \ProvidesExplPackage {siunitx} {2021-06-09} {3.0.12}
24  {A comprehensive (SI) units package}
```

1.2 Safety checks

__siunitx_load_check: There are a number of packages that are incompatible with siunitx as they cover the same concepts and in some cases define the same command names. These are all tested at the point of loading to try to trap issues, and a couple are also tested later as it’s possible for them to load without an obvious error if siunitx was loaded first.

```

25 \msg_new:nnn { siunitx } { incompatible-package }
26   { Package~'#1'~incompatible. }
27   { The~#1-package~and~siunitx~are~incompatible. }
28 \cs_new_protected:Npn \__siunitx_load_check:n #1
29   {
30     \c_ifpackageloaded{#1}
31     { \msg_error:nn { siunitx } { incompatible-package } {#1} }
32     { }
33   }
34 \clist_map_function:nN
35   { SIunits , sistyle , unitsdef , fancyunits }
36   \__siunitx_load_check:n
37 \AtBeginDocument
38   {
39     \clist_map_function:nN { SIunits , sistyle }
40     \__siunitx_load_check:n
41   }

```

(End definition for `__siunitx_load_check:..`)

1.3 Provide a kernel command

`\IfFormatAtLeastTF` Not present in older kernels: use the L^AT_EX 2 _{ε} mechanism as this is correct for this case.

```

42 \providecommand \IfFormatAtLeastTF { \c_ifl@t@r \fmtversion }

```

(End definition for `\IfFormatAtLeastTF`. This function is documented on page ??.)

1.4 Top-level scratch space

`\l__siunitx_tmp_tl` Scratch space for the interfaces.

```

43 \tl_new:N \l__siunitx_tmp_tl

```

(End definition for `\l__siunitx_tmp_tl`.)

```

44 ⟨/init⟩

```

```

45 ⟨*options⟩

```

1.5 Load time options

`\l__siunitx_column_type_tl`

```

46 \keys_define:nn { siunitx }
47   {
48     table-column-type .tl_set:N =
49     \l__siunitx_column_type_tl
50   }
51 \keys_set:nn { siunitx }
52   {
53     table-column-type = S
54   }

```

(End definition for `\l__siunitx_column_type_tl`.)

1.6 Option handling

```
55 \RequirePackage { 13keys2e }
56 \ProcessKeysOptions { siunitx }
57 {/options}
```

1.7 User interfaces

```
58 {*interfaces}
```

The user interfaces are defined in terms of documented code-level ones. This is all done here, and will appear in the .sty file before the relevant code. Things could be re-arranged by DocStrip but there is no advantage.

User level interfaces are all created by `xparse`

```
59 \IfFormatAtLeastTF { 2020-10-01 }
60 {
61   { \RequirePackage { xparse } }
```

1.7.1 Preamble commands

```
\DeclareSIPower Pass data to the code layer.
\DeclareSIPrefix
\DeclareSIQualifier
\DeclareSIUnit
62 \NewDocumentCommand \DeclareSIPower { +m +m m }
63 {
64   \siunitx_declare_power:Nn #1 #2 {#3}
65 }
66 \NewDocumentCommand \DeclareSIPrefix { +m m m }
67 {
68   \siunitx_declare_prefix:Nn #1 {#3} {#2}
69 }
70 \NewDocumentCommand \DeclareSIQualifier { +m m }
71 {
72   \siunitx_declare_qualifier:Nn #1 {#2}
73 }
74 \NewDocumentCommand \DeclareSIUnit { o +m m }
75 {
76   \IfNoValueTF {#1}
77   {
78     \siunitx_declare_unit:Nn #2 {#3}
79     \siunitx_declare_unit:Nnn #2 {#3} {#1}
}
```

(End definition for `\DeclareSIPower` and others. These functions are documented on page ??.)

1.7.2 Document commands

```
\qty
80 \@ifpackageloaded { physics }
81 {
82   \msg_new:nnn { siunitx } { physics-pkg }
83   {
84     Detected-the-~"physics"-~package: \\
85     Omitting~definition~of~\token_to_str:N \qty.
86   }
87   \msg_warning:nn { siunitx } { physics-pkg }
88   \use_none:nnnn
89 }
```

```

90      { }
91  \NewDocumentCommand \qty { O { } m > { \TrimSpaces } m }
92      {
93          \mode_leave_vertical:
94          \group_begin:
95              \siunitx_unit_options_apply:n {#3}
96              \keys_set:nn { siunitx } {#1}
97              \siunitx_quantity:nn {#2} {#3}
98          \group_end:
99      }

```

(End definition for `\qty`. This function is documented on page ??.)

`\ang` All of a standard form: start a paragraph (if required), set local key values, do the
`\num` formatting, print the result.

```

100 \NewDocumentCommand \ang { O { } > { \SplitArgument { 2 } { ; } } m }
101     {
102         \mode_leave_vertical:
103         \group_begin:
104             \keys_set:nn { siunitx } {#1}
105             \__siunitx_angle:nnn #2
106         \group_end:
107     }
108 \NewDocumentCommand \num { O { } m }
109     {
110         \mode_leave_vertical:
111         \group_begin:
112             \keys_set:nn { siunitx } {#1}
113             \siunitx_number_format:nN {#2} \l__siunitx_tmp_tl
114             \siunitx_print_number:V \l__siunitx_tmp_tl
115         \group_end:
116     }
117 \NewDocumentCommand \unit { O { } > { \TrimSpaces } m }
118     {
119         \mode_leave_vertical:
120         \group_begin:
121             \siunitx_unit_options_apply:n {#2}
122             \keys_set:nn { siunitx } {#1}
123             \siunitx_unit_format:nN {#2} \l__siunitx_tmp_tl
124             \siunitx_print_unit:V \l__siunitx_tmp_tl
125         \group_end:
126     }

```

(End definition for `\ang`, `\num`, and `\unit`. These functions are documented on page ??.)

`\qtylist` Interfaces for compound values.
`\numlist`
`\qtyproduct`
`\numproduct`
`\qtyproduct`
`\numproduct`
`\qtyrange`
`\groupbegin`
`\groupend`

```

127 \NewDocumentCommand \qtylist
128     { O { } > { \SplitList { ; } } m > { \TrimSpaces } m }
129     {
130         \mode_leave_vertical:
131         \group_begin:
132             \siunitx_unit_options_apply:n {#3}
133             \keys_set:nn { siunitx } {#1}
134             \siunitx_quantity_list:nn {#2} {#3}

```

```

135     \group_end:
136   }
137 \NewDocumentCommand \numlist { O { } > { \SplitList { ; } } m }
138   {
139     \mode_leave_vertical:
140     \group_begin:
141       \keys_set:nn { siunitx } {#1}
142       \siunitx_number_list:nn {#2}
143     \group_end:
144   }
145 \NewDocumentCommand \qtyproduct
146   { O { } > { \SplitList { x } } m > { \TrimSpaces } m }
147   {
148     \mode_leave_vertical:
149     \group_begin:
150       \siunitx_unit_options_apply:n {#3}
151       \keys_set:nn { siunitx } {#1}
152       \siunitx_quantity_product:nn {#2} {#3}
153     \group_end:
154   }
155 \NewDocumentCommand \numproduct
156   { O { } > { \SplitList { x } } > { \TrimSpaces } m }
157   {
158     \mode_leave_vertical:
159     \group_begin:
160       \keys_set:nn { siunitx } {#1}
161       \siunitx_number_product:n {#2}
162     \group_end:
163   }
164 \NewDocumentCommand \qtyrange { O { } m m > { \TrimSpaces } m }
165   {
166     \mode_leave_vertical:
167     \group_begin:
168       \siunitx_unit_options_apply:n {#4}
169       \keys_set:nn { siunitx } {#1}
170       \siunitx_quantity_range:nnn {#2} {#3} {#4}
171     \group_end:
172   }
173 \NewDocumentCommand \numrange { O { } m m }
174   {
175     \mode_leave_vertical:
176     \group_begin:
177       \keys_set:nn { siunitx } {#1}
178       \siunitx_number_range:nn {#2} {#3}
179     \group_end:
180   }

```

(End definition for `\qtylist` and others. These functions are documented on page ??.)

```

\complexnum Interfaces for complex numbers.
\complexqty
181 \NewDocumentCommand \complexnum { O { } m }
182   {
183     \mode_leave_vertical:
184     \group_begin:

```

```

185      \keys_set:nn { siunitx } {#1}
186      \siunitx_complex_number:n {#2} \l_siunitx_tmp_tl
187      \group_end:
188  }
189 \NewDocumentCommand \complexqty { O { } m m }
190 {
191     \mode_leave_vertical:
192     \group_begin:
193         \siunitx_unit_options_apply:n {#3}
194         \keys_set:nn { siunitx } {#1}
195         \siunitx_complex_quantity:nn {#2} {#3}
196     \group_end:
197 }

```

(End definition for `\complexnum` and `\complexqty`. These functions are documented on page ??.)

`\tablenum` Slightly odd set up at present: we have to have the `\ignorespaces`.

```

198 \NewDocumentCommand \tablenum { O { } m }
199 {
200     \mode_leave_vertical:
201     \group_begin:
202         \keys_set:nn { siunitx } {#1}
203         \siunitx_cell_begin:w
204             \ignorespaces #2
205         \siunitx_cell_end:
206     \group_end:
207 }

```

(End definition for `\tablenum`. This function is documented on page ??.)

`\sisetup` A very thin wrapper.

```

208 \NewDocumentCommand \sisetup { m }
209   { \keys_set:nn { siunitx } {#1} }

```

(End definition for `\sisetup`. This function is documented on page ??.)

1.8 “Glue” commands

`_siunitx_angle:nnn` The document level interface for `\ang` needs some “glue” to work with the code-level API.

```

210 \cs_new_protected:Npn \_siunitx_angle:nnn #1#2#3
211   {
212     \tl_if_no_value:nTF {#2}
213       { \siunitx_angle:n {#1} }
214       {
215         \tl_if_no_value:nTF {#3}
216           { \siunitx_angle:nnn {#1} {#2} { } }
217           { \siunitx_angle:nnn {#1} {#2} {#3} }
218       }
219   }

```

(End definition for `_siunitx_angle:nnn`.)

1.9 Table column

User interfaces in tabular constructs are provided using the mechanisms from the `array` package.

```
220 \RequirePackage { array }
```

`_siunitx_declare_column:Nnn`

Creating numerical columns requires that these are declared before anything else in `\NC@list`: this is necessary to work with optional arguments. This means a bit of manual effort after the simple declaration of a new column type. The token assigned to the column type is not fixed as this allows the same code to be used in compatibility with version 2.

```
221 \cs_new_protected:Npn \_siunitx_declare_column:Nnn #1#2#3
222   {
223     \cs_if_exist:cT { NC@find@ #1 }
224     {
225       \cs_undefine:c { NC@find@ #1 }
226       \msg_warning:nnn { siunitx } { column-overwritten } {#1}
227     }
228     \newcolumntype {#1} { }
229     \cs_set_protected:Npn \_siunitx_tmp:w \NC@do ##1##2 \NC@do #1
230       { \NC@list { \NC@do ##1 \NC@do #1 ##2 } }
231     \exp_after:wN \_siunitx_tmp:w \the \NC@list
232     \exp_args:NNc \renewcommand * { NC@rewrite@ #1 } [ 1 ] [ ]
233     {
234       \otemptokena \expandafter
235         {
236           \the \otemptokena
237             > {#2} c < {#3}
238         }
239       \NC@find
240     }
241   }
242 \msg_new:nnn { siunitx } { column-overwritten }
243   { Tabular-column-type~"#1"~overwritten-with-siunitx-definition. }
```

When `mdwtab` is loaded the syntax required is slightly different.

```
244 \AtBeginDocument
245   {
246     \ifpackageloaded { mdwtab }
247     {
248       \cs_set_protected:Npn \_siunitx_declare_column:Nnn #1#2#3
249         {
250           \cs_if_exist:cT { NC@find@ #1 }
251             {
252               \cs_undefine:c { NC@find@ #1 }
253               \msg_warning:nnn { siunitx } { column-overwritten } {#1}
254             }
255             \newcolumntype {#1} [ 1 ] [ ]
256               { > {#2} c < {#3} }
257         }
258     }
259   { }
260   \tl_map_inline:Nn \l__siunitx_column_type_tl
261     {
```

```

262      \_siunitx_declare_column:Nnn #1
263      {
264          \keys_set:nn { siunitx } {##1}
265          \siunitx_cell_begin:w
266      }
267      { \siunitx_cell_end: }
268  }
269 }
```

(End definition for `_siunitx_declare_column:Nnn`.)

1.10 Document commands in bookmarks

In bookmarks, the `siunitx` document commands need to produce simple strings that represent their input as far as possible.

`_siunitx_bookmark_cmd:Nn`

To keep things fast, expandable versions of the document command are created only once. As here we are at the top-level for internal names, we can use the various parts of `siunitx-compound` that would otherwise be inaccessible.

```

270 \cs_new_protected:Npn \_siunitx_bookmark_cmd:Nnn #1#2#3
271 {
272     \exp_args:Nc \DeclareExpandableDocumentCommand
273         { \cs_to_str:N #1 \c_space_tl ( pdfstring ~ context ) }
274         {#2} {#3}
275 }
276 \_siunitx_bookmark_cmd:Nnn \qty { o m m } { #2 ~ #3 }
277 \_siunitx_bookmark_cmd:Nnn \ang { m } { \_siunitx_angle:n {#1} }
278 \_siunitx_bookmark_cmd:Nnn \num { o m } { #2 }
279 \_siunitx_bookmark_cmd:Nnn \unit { o m } { #2 }
280 \_siunitx_bookmark_cmd:Nnn \numlist { o m }
281 {
282     \_siunitx_list_use:nnVVV {#2} { }
283     \l_siunitx_list_separator_pair_tl
284     \l_siunitx_list_separator_tl
285     \l_siunitx_list_separator_final_tl
286 }
287 \_siunitx_bookmark_cmd:Nnn \qtylist { o m m }
288 {
289     \_siunitx_list_use:nnVVV {#2} {#3}
290     \l_siunitx_list_separator_pair_tl
291     \l_siunitx_list_separator_tl
292     \l_siunitx_list_separator_final_tl
293 }
294 \_siunitx_bookmark_cmd:Nnn \numproduct { o m } { }
295 \_siunitx_bookmark_cmd:Nnn \qtyproduct { o m m } { }
296 \_siunitx_bookmark_cmd:Nnn \numrange { o m m }
297 { #2 \tl_use:N \l_siunitx_range_phrase_tl #3 }
298 \_siunitx_bookmark_cmd:Nnn \qtyrange { o m m m }
299 { #2 ~ #4 \tl_use:N \l_siunitx_range_phrase_tl #3 ~ #4 }
```

(End definition for `_siunitx_bookmark_cmd:Nn`.)

We also need the v2 names.

```

300 \_siunitx_bookmark_cmd:Nnn \si { o m } { #2 }
301 \_siunitx_bookmark_cmd:Nnn \SI { o m O { } m } { #3 #2 ~ #4 }
```

```

302 \_siunitx_bookmark_cmd:Nnn \SIList { o m m }
303 {
304     \_siunitx_list_use:nnVVV {#2} {#3}
305     \l_siunitx_list_separator_pair_tl
306     \l_siunitx_list_separator_tl
307     \l_siunitx_list_separator_final_tl
308 }
309 \_siunitx_bookmark_cmd:Nnn \SIrange { o m m m }
310 { #2 ~ #4 \tl_use:N \l_siunitx_range_phrase_tl #3 ~ #4 }

```

\c_siunitx_bookmark_seq Commands usable in bookmarks

```

311 \seq_const_from_clist:Nn \c\_siunitx_bookmark_seq
312 {
313     \ang , \qty , \num , \unit ,
314     \numlist , \qtylist ,
315     \numrange , \qtyrange ,
316     \si , \SI , \SIList , \SIrange
317 }

```

(End definition for \c_siunitx_bookmark_seq.)

Activate the document commands here: the unit macros are handled in siunitx-final.

```

318 \AtBeginDocument
319 {
320     \@ifpackageloaded{hyperref}{%
321         \pdfstringdefDisableCommands{%
322             \seq_map_inline:Nn \c\_siunitx_bookmark_seq{%
323                 \cs_set_eq:Nc{#1}{\cs_to_str:N{#1}\c_space_tl(\pdfstring~context)}%
324             }%
325         }%
326         \pdfstringdefDisableCommands{%
327             \siunitx_unit_pdfstring_context: %
328             \cs_if_exist:NT{\FB@fg}{\def\fg{\FB@fg}}%
329             \edef\H{%
330                 \exp_not:c{PU-cmd}%
331                 \exp_not:N\H%
332                 \exp_not:c{PU\token_to_str:N\H}%
333             }%
334         }%
335     }%
336 }
337 }
338 }
339 }
340 }
341 }
342 }
343 }

```

_siunitx_angle:n Expandable splitting of the angle: simply enough, also outputs the

_siunitx_angle:w

```

344 \cs_new:Npn \_siunitx_angle:n #1
345 { \_siunitx_angle:w #1 ; ; \q_stop }
346 \cs_new:Npn \_siunitx_angle:w #1 ; #2 ; #3 ; #4 \q_stop
347 {
348     \tl_if_blank:nF {#1}

```

```

349      { #1 \degree }
350      \tl_if_blank:nF {#2}
351      {
352          \tl_if_blank:nF {#1} { \c_space_tl }
353          #2 \arcminute
354      }
355      \tl_if_blank:nF {#3}
356      {
357          \tl_if_blank:nF {#1#2} { \c_space_tl }
358          #3 \arcsecond
359      }
360  }

```

(End definition for `_siunitx_angle:n` and `_siunitx_angle:w`.)

`_siunitx_list_use:nnnn`
`_siunitx_list_use:nnVVV`
`_siunitx_list_use_aux:nnmn`
`_siunitx_list_use_auxi:nnw`
`_siunitx_list_use_auxii:nnw`
`_siunitx_list_count:n`
`_siunitx_list_count:w`

Copies of the ideas in the `_list` module but using ; as a list separator. The functions have to be extended to allow for a unit argument.

```

361 \cs_new:Npn \_siunitx_list_use:nnnnn #1#2#3#4#5
362   {
363     \tl_if_blank:nTF {#2}
364     { \_siunitx_list_use_aux:nnnnn {#1} { } }
365     { \_siunitx_list_use_aux:nnnnn {#1} { ~ #2 } }
366     {#3} {#4} {#5}
367   }
368 \cs_generate_variant:Nn \_siunitx_list_use:nnnnn { nnVVV }
369 \cs_new:Npn \_siunitx_list_use_aux:nnnnn #1#2#3#4#5
370   {
371     \int_case:nnF { \_siunitx_list_count:n {#1} }
372     {
373       { 0 } { }
374       { 1 } { \_siunitx_list_use_auxi:nw {#2} #1 ; { } }
375       { 2 } { \_siunitx_list_use_auxi:nw {#2} #1 ; {#3} }
376     }
377   {
378     \_siunitx_list_use_auxii:nnw {#2} { } #1 ;
379     \q_mark ; { \_siunitx_list_use_auxii:nnw {#2} {#4} }
380     \q_mark ; { \_siunitx_list_use_auxiii:nnw {#2} {#5} }
381     \q_stop {#2}
382   }
383 }
384 \cs_new:Npn \_siunitx_list_use_auxi:nw #1#2 ; #3 ; #4
385   { #2 #1 #4 #3 \tl_if_blank:nF {#3} {#1} }
386 \cs_new:Npn \_siunitx_list_use_auxii:nnw
387   #1#2#3 ; #4 ; #5 ; #6 \q_mark ; #7#8 \q_stop #9
388   { #7 {#4} ; {#5} ; #6 \q_mark ; {#7} #8 \q_stop { #9 #2 #3 #1 } }
389 \cs_new:Npn \_siunitx_list_use_auxiii:nnw #1#2#3 ; #4 \q_stop #5
390   { #5 #2 #3 #1 }
391 \cs_new:Npx \_siunitx_list_count:n #1
392   {
393     \exp_not:N \int_eval:n
394     {
395       0
396       \exp_not:N \_siunitx_list_count:w \c_space_tl
397       #1 \exp_not:n { ; \q_recursion_tail ; \q_recursion_stop }

```

```

398      }
399  }
400 \cs_new:Npx \__siunitx_list_count:w #1 ;
401 {
402   \exp_not:n { \exp_args:Nf \quark_if_recursion_tail_stop:n } {#1}
403   \exp_not:N \tl_if_blank:nF {#1} { + 1 }
404   \exp_not:N \__siunitx_list_count:w \c_space_tl
405 }

(End definition for \__siunitx_list_use:nnnnn and others.)

406 ⟨/interfaces⟩
407 ⟨/package⟩

```

Part II

siunitx-angle – Formatting angles

1 Formatting angles

```
\siunitx_angle:n {<angle>}
\siunitx_angle:nnn {<degrees>} {<minutes>} {<seconds>}
```

Typeset the *<angle>* (which may be given as separate *<degree>*, *<minute>* and *<second>* components). The *<angle>* (or components) may be given as expressions. The *<angle>* should be a number as understood by `\siunitx_format_number:nN`, with no uncertainty, exponent or imaginary part. The unit symbols for degrees, minutes and seconds are `\degree`, `\arcminute` and `\arcsecond`, respectively

1.1 Key-value options

The options defined by this submodule are available within the `l3keys siunitx` tree.

```
angle-mode = <choice>
```

Selects how angles are formatted: a choice from the options `arc`, `decimal` and `input`. The option `arc` means that angles will always be typeset in arc (degree, minute, second) format, whilst `decimal` means that angles are typeset as a single decimal value. The `input` setting means that the input format (*i.e.* difference between `\siunitx_angle:n` and `\siunitx_angle:nnn`) is maintained. The standard setting is `input`.

```
angle-symbol-degree = <symbol>
```

Sets the symbol used for arc degrees, minutes or seconds, respectively.

```
angle-symbol-over-decimal = true|false
```

Determines if the arc separator is printed over the decimal marker, a format used in astronomy. The standard setting is `false`.

```
arc-separator = <separator>
```

Inserted between arc parts (degree, minute and second components). The standard setting is `\,`.

```
fill-angle-degrees = true|false
```

Determines whether a missing degrees part is zero-filled when printing an arc. The standard setting is `false`.

```
fill-angle-minutes = true|false
```

Determines whether a missing minutes part is zero-filled when printing an arc. The standard setting is `false`.

fill-angle-seconds

```
fill-arc-seconds = true|false
```

Determines whether a missing seconds part is zero-filled when printing an arc. The standard setting is `false`.

number-angle-product

```
number-angle-product = <separator>
```

Inserted between the value of an angle and the unit (degree, minute or second component). The standard setting is `\,.`

2 siunitx-angle implementation

Start the DocStrip guards.

```
1  {*package}
```

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
2  (@@=siunitx_angle)
```

Scratch space.

```
3  \bool_new:N \l_siunitx_angle_tmp_bool  
4  \dim_new:N \l_siunitx_angle_tmp_dim  
5  \tl_new:N \l_siunitx_angle_tmp_tl
```

(End definition for `\l_siunitx_angle_tmp_bool`, `\l_siunitx_angle_tmp_dim`, and `\l_siunitx_angle_tmp_tl`.)

```
\l_siunitx_angle_symbol_degree_tl  
\l_siunitx_angle_symbol_minute_tl  
\l_siunitx_angle_symbol_second_tl  
\l_siunitx_angle_force_arc_bool  
\l_siunitx_angle_force_decimal_bool  
\l_siunitx_angle_astronomy_bool  
\l_siunitx_angle_separator_tl  
\l_siunitx_angle_fill_degrees_bool  
\l_siunitx_angle_fill_minutes_bool  
\l_siunitx_angle_fill_seconds_bool  
\l_siunitx_angle_product_tl
```

```
6  \keys_define:nn { siunitx }  
7  {  
8    angle-mode .choice: ,  
9    angle-mode / arc .code:n =  
10   {  
11     \bool_set_true:N \l_siunitx_angle_force_arc_bool  
12     \bool_set_false:N \l_siunitx_angle_force_decimal_bool  
13   } ,  
14   angle-mode / decimal .code:n =  
15   {  
16     \bool_set_false:N \l_siunitx_angle_force_arc_bool  
17     \bool_set_true:N \l_siunitx_angle_force_decimal_bool  
18   } ,  
19   angle-mode / input .code:n =  
20   {  
21     \bool_set_false:N \l_siunitx_angle_force_arc_bool  
22     \bool_set_false:N \l_siunitx_angle_force_decimal_bool  
23   } ,  
24   angle-symbol-degree .tl_set:N =  
25   \l_siunitx_angle_symbol_degree_tl ,  
26   angle-symbol-minute .tl_set:N =  
27   \l_siunitx_angle_symbol_minute_tl ,  
28   angle-symbol-second .tl_set:N =  
29   \l_siunitx_angle_symbol_second_tl ,  
30   angle-symbol-over-decimal .bool_set:N =  
31   \l_siunitx_angle_astronomy_bool ,
```

```

32   angle-separator .tl_set:N =
33     \l_siunitx_angle_separator_tl ,
34   fill-angle-degrees .bool_set:N =
35     \l_siunitx_angle_fill_degrees_bool ,
36   fill-angle-minutes .bool_set:N =
37     \l_siunitx_angle_fill_minutes_bool ,
38   fill-angle-seconds .bool_set:N =
39     \l_siunitx_angle_fill_seconds_bool ,
40   number-angle-product .tl_set:N =
41     \l_siunitx_angle_product_tl
42   }
43 \bool_new:N \l_siunitx_angle_force_arc_bool
44 \bool_new:N \l_siunitx_angle_force_decimal_bool

```

(End definition for `\l_siunitx_angle_symbol_degree_tl` and others.)

`\siunitx_angle:n`
`\siunitx_angle:nnn`
`_siunitx_angle_arc_convert:n`

```

45 \cs_new_protected:Npn \siunitx_angle:n #1
46 {
47   \bool_if:NTF \l_siunitx_angle_force_arc_bool
48   { \exp_args:Ne \_siunitx_angle_arc_convert:n { \fp_eval:n {#1} } }
49   {
50     \siunitx_number_parse:nN {#1} \l_siunitx_angle_degrees_tl
51     \tl_set:Nx \l_siunitx_angle_degrees_tl
52       { \siunitx_number_output:NN \l_siunitx_angle_degrees_tl \q_nil }
53     \_siunitx_angle弧印:VVV
54       \l_siunitx_angle_degrees_tl
55       \c_empty_tl
56       \c_empty_tl
57   }
58 }
59 \cs_new_protected:Npn \siunitx_angle:nnn #1#2#3
60 {
61   \bool_if:NTF \l_siunitx_angle_force_decimal_bool
62   {
63     \exp_args:Ne \siunitx_angle:n
64     { \fp_eval:n { #1 + (#2) / 60 + (#3) / 3600 } }
65   }
66   { \_siunitx_angle弧签:nnn {#1} {#2} {#3} }
67 }
68 \cs_new_protected:Npn \_siunitx_angle_arc_convert:n #1
69 {
70   \use:x
71   {
72     \siunitx_angle:nnn
73       { \fp_eval:n { trunc(#1,0) } }
74       { \fp_eval:n { trunc((#1 - trunc(#1,0)) * 60,0) } }
75       {
76         \fp_eval:n
77         {
78           (
79             (#1 - trunc(#1,0)) * 60

```

```

80           - trunc((#1 - trunc(#1,0)) * 60,0)
81       )
82   * 60
83 }
84 }
85 }
86 }

```

(End definition for `\siunitx_angle:n`, `\siunitx_angle:nnn`, and `_siunitx_angle_arc_convert:n`. These functions are documented on page 12.)

`\l_siunitx_angle_degrees_tl`
`\l_siunitx_angle_minutes_tl`
`\l_siunitx_angle_seconds_tl`

Space for formatting parsed numbers.

```

87 \tl_new:N \l_siunitx_angle_degrees_tl
88 \tl_new:N \l_siunitx_angle_minutes_tl
89 \tl_new:N \l_siunitx_angle_seconds_tl

```

(End definition for `\l_siunitx_angle_degrees_tl`, `\l_siunitx_angle_minutes_tl`, and `\l_siunitx_angle_seconds_tl`.)

`\l_siunitx_angle_sign_tl` For the “sign shuffle”.

```
90 \tl_new:N \l_siunitx_angle_sign_tl
```

(End definition for `\l_siunitx_angle_sign_tl`.)

To get the sign in the right place whilst dealing with zero filling means doing some shuffling. That means doing processing of each number manually.

```

91 \cs_new_protected:Npn \_siunitx_angle_arc_sign:nnn #1#2#3
92 {
93     \group_begin:
94     \keys_set:nn { siunitx }
95     {
96         input-close-uncertainty = ,
97         input-exponent-markers = ,
98         input-open-uncertainty = ,
99         input-uncertainty-signs =
100    }
101    \tl_clear:N \l_siunitx_angle_sign_tl
102    \_siunitx_angle_arc_sign:nn {#1} { degrees }
103    \_siunitx_angle_arc_sign:nn {#2} { minutes }
104    \_siunitx_angle_arc_sign:nn {#3} { seconds }
105    \tl_if_empty:NF \l_siunitx_angle_sign_tl
106    {
107        \clist_map_inline:nn { degrees , minutes , seconds }
108        {
109            \tl_if_empty:cF { l_siunitx_angle_ ##1 _tl }
110            {
111                \tl_set:cx { l_siunitx_angle_ ##1 _tl }
112                {
113                    {
114                        { \exp_not:V \l_siunitx_angle_sign_tl }
115                        \exp_after:wN \exp_after:wN \exp_after:wN
116                        \_siunitx_angle_sign:nnnnnnn
117                        \cs:w l_siunitx_angle_ ##1 _tl \cs_end:
118                    }
119                    \clist_map_break:

```

```

120         }
121     }
122   }
123 \clist_map_inline:nn { degrees , minutes , seconds }
124   {
125     \tl_if_empty:cF { l__siunitx_angle_ ##1 _tl }
126     {
127       \tl_set:cx { l__siunitx_angle_ ##1 _tl }
128       {
129         \exp_args:Nc \siunitx_number_output:NN
130           { l__siunitx_angle_ ##1 _tl } \q_nil
131       }
132     }
133   }
134 \__siunitx_angle_arc_print:VVV
135   \l__siunitx_angle_degrees_tl
136   \l__siunitx_angle_minutes_tl
137   \l__siunitx_angle_seconds_tl
138 \group_end:
139 }
140 \cs_new_protected:Npn \__siunitx_angle_arc_sign:nn #1#2
141   {
142     \tl_if_blank:nTF {#1}
143     {
144       \bool_if:cTF { l__siunitx_angle_fill_ #2 _bool }
145       {
146         \tl_set:cn { l__siunitx_angle_ #2 _tl }
147           { { } { } { 0 } { } { } { } { 0 } }
148       }
149       { \tl_clear:c { l__siunitx_angle_ #2 _tl } }
150     }
151     {
152       \siunitx_number_parse:nN {#1} \l__siunitx_angle_tmp_tl
153       \exp_after:wN \__siunitx_angle_extract_sign:nnnnnnnn \l__siunitx_angle_tmp_tl {#2}
154     }
155   }
156 \cs_new_protected:Npn \__siunitx_angle_extract_sign:nnnnnnnn #1#2#3#4#5#6#7#8
157   {
158     \tl_if_blank:nTF {#2}
159     {
160       \tl_set_eq:cN { l__siunitx_angle_ #8 _tl } \l__siunitx_angle_tmp_tl
161       {
162         \tl_set:cn { l__siunitx_angle_ #8 _tl }
163           { {#1} { } {#3} {#4} {#5} {#6} {#7} }
164         \tl_set:Nn \l__siunitx_angle_sign_tl {#2}
165         \keys_set:nn { siunitx }
166           { input-comparators = , input-signs = }
167       }
168     }
169   }
170 \cs_new:Npn \__siunitx_angle_sign:nnnnnnnn #1#2#3#4#5#6#7
171   { \exp_not:n { {#3} {#4} {#5} {#6} {#7} } }

(End definition for \__siunitx_angle_arc_sign:nn and others.)

```

\l__siunitx_angle_marker_box For “astronomy style” angles.
\l__siunitx_angle_unit_box

```

170 \box_new:N \l_siunitx_angle_marker_box
171 \box_new:N \l_siunitx_angle_unit_box

```

(End definition for `\l_siunitx_angle_marker_box` and `\l_siunitx_angle_unit_box`.)

The final stage of printing an angle is to put together the three parts: this works even for decimal angles as they will blank arguments for the other two parts. The need to handle astronomy-style formatting means that the number has to be decomposed into parts.

```

172 \cs_new_protected:Npn \_siunitx_angle_arc_print:nnn #1#2#3
173 {
174     \_siunitx_angle_arc_print_auxi:nVn
175     \l_siunitx_angle_symbol_degree_tl {#2#3}
176     \_siunitx_angle_arc_print_auxi:nVn {#2}
177     \l_siunitx_angle_symbol_minute_tl {#3}
178     \_siunitx_angle_arc_print_auxi:nVn {#3}
179     \l_siunitx_angle_symbol_second_tl { }
180 }
181 \cs_generate_variant:Nn \_siunitx_angle_arc_print:nnn { VVV }
182 \cs_new_protected:Npn \_siunitx_angle_arc_print_auxi:nnn #1#2#3
183 {
184     \tl_if_blank:nF {#1}
185     {
186         \bool_if:NTF \l_siunitx_angle_astronomy_bool
187             { \_siunitx_angle_arc_print_auxii:nw {#2} #1 \q_stop }
188             {
189                 \_siunitx_angle_arc_print_auxv:w #1 \q_stop
190                 \_siunitx_angle_arc_print_auxvi:n {#2}
191             }
192         \tl_if_blank:nF {#3}
193         {
194             \nobreak
195             \l_siunitx_angle_separator_tl
196         }
197     }
198 }
199 \cs_generate_variant:Nn \_siunitx_angle_arc_print_auxi:nnn { nV }
200 %     \end{macrocode}
201 %     To align the two parts of the astronomy-style marker, we need to allow
202 %     for the \scriptspace.
203 %     \begin{macrocode}
204 \cs_new_protected:Npn \_siunitx_angle_arc_print_auxii:nw
205     #1#2 \q_nil #3 \q_nil #4 \q_nil #5 \q_nil #6 \q_nil #7 \q_nil #8 \q_stop
206 {
207     \mode_if_math:TF
208         { \bool_set_true:N \l_siunitx_angle_tmp_bool }
209         { \bool_set_false:N \l_siunitx_angle_tmp_bool }
210     \siunitx_print_number:n {#2#3#4}
211     \tl_if_blank:nTF {#6}
212         { \_siunitx_angle_arc_print_auxvi:n {#1} }
213         {
214             \hbox_set:Nn \l_siunitx_angle_marker_box
215             {
216                 \_siunitx_angle_arc_print_auxiii:n
217                     { \siunitx_print_number:n {#5} }

```

```

218 }
219 \hbox_set:Nn \l_siunitx_angle_unit_box
220 {
221   \l_siunitx_angle_arc_print_auxiii:n
222   {
223     \siunitx_unit_format:nN {#1} \l_siunitx_angle_tmp_tl
224     \siunitx_print_unit:V \l_siunitx_angle_tmp_tl
225     \skip_horizontal:n { -\scriptspace }
226   }
227 }
228 \dim_compare:nNnTF { \box_wd:N \l_siunitx_angle_marker_box } >
229   { \box_wd:N \l_siunitx_angle_unit_box }
230 {
231   \l_siunitx_angle_arc_print_auxiv:NN
232   \l_siunitx_angle_marker_box
233   \l_siunitx_angle_unit_box
234 }
235 {
236   \l_siunitx_angle_arc_print_auxiv:NN
237   \l_siunitx_angle_unit_box
238   \l_siunitx_angle_marker_box
239 }
240 \hbox_set_to_wd:Nnn \l_siunitx_angle_marker_box
241   \l_siunitx_angle_tmp_dim
242 {
243   \hbox_overlap_right:n
244   { \box_use_drop:N \l_siunitx_angle_marker_box }
245   \hbox_overlap_right:n
246   { \box_use_drop:N \l_siunitx_angle_unit_box }
247   \tex_hfil:D
248 }
249 \box_use:N \l_siunitx_angle_marker_box
250 \skip_horizontal:N \scriptspace
251 \siunitx_print_number:n {#6}
252 }
253 }
254 \cs_new_protected:Npn \l_siunitx_angle_arc_print_auxiii:n #1
255 {
256   \bool_if:NTF \l_siunitx_angle_tmp_bool
257   { \ensuremath }
258   { \use:n }
259   {#1}
260 }
261 \cs_new_protected:Npn \l_siunitx_angle_arc_print_auxiv:NN #1#2
262 {
263   \dim_set:Nn \l_siunitx_angle_tmp_dim { \box_wd:N #1 }
264   \hbox_set_to_wd:Nnn #2
265   \l_siunitx_angle_tmp_dim
266   {
267     \tex_hss:D
268     \hbox_unpack_drop:N #2
269     \tex_hss:D
270   }
271 }

```

```

272 \cs_new_protected:Npn \__siunitx_angle_arc_print_auxv:w
273   #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_nil #5 \q_nil #6 \q_stop
274   { \siunitx_print_number:n {#1#2#3#4#5} }
275 \cs_new_protected:Npn \__siunitx_angle_arc_print_auxvi:n #1
276   {
277     \nobreak
278     \l__siunitx_angle_product_tl
279     \siunitx_unit_format:nN {#1} \l__siunitx_angle_tmp_tl
280     \siunitx_print_unit:V \l__siunitx_angle_tmp_tl
281   }

(End definition for \__siunitx_angle_arc_print:nnn and others.)

282 \keys_set:nn { siunitx }
283   {
284     angle-mode           = input      ,
285     angle-symbol-degree = \degree   ,
286     angle-symbol-minute = \arcminute ,
287     angle-symbol-over-decimal = false   ,
288     angle-symbol-second = \arcsecond ,
289     angle-separator      =
290     fill-angle-degrees   = false   ,
291     fill-angle-minutes   = false   ,
292     fill-angle-seconds   = false   ,
293     number-angle-product =
294   }
295 
```

Part III

siunitx-compound – Compound numbers and quantities

| | | |
|--|--|---|
| <u>\siunitx_compound_number:n</u> | <code>\siunitx_compound_number:n {<entries>}</code> | Prints a set of numbers in the <i><entries></i> , each of which should be given as a <i>(balanced text)</i> . Unlike <code>\siunitx_number_list:nn</code> , this function may semantically take any form |
| <u>\siunitx_compound_quantity:nn</u> | <code>\siunitx_compound_quantity:nn \siunitx_compound_quantity:nn {<entries>} {<unit>}</code> | Prints a set of quantities in the <i><entries></i> , each of which should be given as a <i>(balanced text)</i> . Unlike <code>\siunitx_quantity_list:nn</code> , this function may semantically take any form |
| <u>\siunitx_number_list:nn</u> | <code>\siunitx_number_list:nn {<entries>}</code> | Prints the list of numbers in the <i><entries></i> , each of which should be given as a <i>(balanced text)</i> . |
| <u>\siunitx_quantity_list:nn</u> | <code>\siunitx_quantity_list:nn {<entries>} {<unit>}</code> | Prints the list of quantities in the <i><entries></i> , each of which should be given as a <i>(balanced text)</i> . |
| <u>\siunitx_number_product:n</u> | <code>\siunitx_number_product:n {<entries>}</code> | Prints the series of numbers in the <i><entries></i> , each of which should be given as a <i>(balanced text)</i> . |
| <u>\siunitx_quantity_product:nn</u> | <code>\siunitx_quantity_product:nn \siunitx_number_product:n {<entries>} {<unit>}</code> | Prints the series of quantities in the <i><entries></i> , each of which should be given as a <i>(balanced text)</i> . |
| <u>\siunitx_number_range:nn</u> | <code>\siunitx_number_range:nn {<start>} {<end>}</code> | Prints the range of numbers from the <i><start></i> to the <i><end></i> . |
| <u>\siunitx_quantity_range:nnn</u> | <code>\siunitx_quantity_range:nnn \siunitx_number_range:nn {<start>} {<end>} {<unit>}</code> | Prints the range of quantities from the <i><start></i> to the <i><end></i> . |
| <u>\l_siunitx_list_separator_pair_tl</u> <u>\l_siunitx_list_separator_tl</u> <u>\l_siunitx_list_separator_final_tl</u> | | Separators for lists of numbers and quantities. |

| | |
|-----------------------------------|---|
| <u>\l_siunitx_range_phrase_t1</u> | Phrase (or similar) used between limits of a range. |
| <u>compound-exponents</u> | compound-exponents = combine combine-bracket individual |
| <u>compound-final-separator</u> | compound-final-separator = <i><text></i> |
| <u>compound-pair-separator</u> | compound-pair-separator = <i><text></i> |
| <u>compound-separator</u> | compound-separator = <i><text></i> |
| <u>compound-separator-mode</u> | compound-separator-mode = number text |
| <u>compound-units</u> | compound-units = bracket repeat single |
| <u>list-exponents</u> | list-exponents = combine combine-bracket individual |
| <u>list-final-separator</u> | list-final-separator = <i><text></i> |
| <u>list-pair-separator</u> | list-pair-separator = <i><text></i> |
| <u>list-separator</u> | list-separator = <i><text></i> |
| <u>list-units</u> | list-units = bracket repeat single |
| <u>product-exponents</u> | product-exponents = combine combine-bracket individual |
| <u>product-mode</u> | product-mode = phrase choice |
| <u>product-phrase</u> | product-phrase = <i><text></i> |
| <u>product-symbol</u> | product-symbol = <i><symbol></i> |
| <u>range-exponents</u> | range-exponents = combine combine-bracket individual |

range-phrase range-phrase = *<text>*

range-units range-units = bracket|repeat|single

Start the DocStrip guards.

1 (*package)

1 **siunitx-compound** implementation

2 \cs_generate_variant:Nn \keys_set:nn { nx }

1.1 General mechanism

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

3 (@@=siunitx_compound)

Typesetting lists, ranges and products of numbers or quantities has shared features which mean they are best handled using a common mechanism. The aim therefore is to abstract out enough of the process such that output-specific aspects can be left to separate processes.

\l_siunitx_compound_tmp_fp Scratch space.

4 \fp_new:N \l_siunitx_compound_tmp_fp
 5 \seq_new:N \l_siunitx_compound_tmp_seq
 6 \tl_new:N \l_siunitx_compound_tmp_tl

(End definition for \l_siunitx_compound_tmp_fp, \l_siunitx_compound_tmp_seq, and \l_siunitx_compound_tmp_tl.)

\l_siunitx_compound_first_tl The first number in the list in internal format.

7 \tl_new:N \l_siunitx_compound_first_tl

(End definition for \l_siunitx_compound_first_tl.)

\l_siunitx_compound_exp_tl For storing the combined exponent, if present.

8 \tl_new:N \l_siunitx_compound_exp_tl

(End definition for \l_siunitx_compound_exp_tl.)

\l_siunitx_compound_start_tl Data on the end-of-list.

9 \tl_new:N \l_siunitx_compound_start_tl
 10 \tl_new:N \l_siunitx_compound_end_tl

(End definition for \l_siunitx_compound_start_tl and \l_siunitx_compound_end_tl.)

\l_siunitx_compound_count_int Data on the length-of-list.

11 \int_new:N \l_siunitx_compound_count_int

(End definition for \l_siunitx_compound_count_int.)

\l_siunitx_compound_unit_bool

12 \bool_new:N \l_siunitx_compound_unit_bool
 13 \tl_new:N \l_siunitx_compound_unit_tl

(End definition for `\l_siunitx_compound_unit_bool` and `\l_siunitx_compound_unit_tl`.)

Purely internal for the present.

```
14 \tl_new:N \l_siunitx_compound_bracket_close_tl  
15 \tl_new:N \l_siunitx_compound_bracket_open_tl  
16 \tl_set:Nn \l_siunitx_compound_bracket_open_tl { () }  
17 \tl_set:Nn \l_siunitx_compound_bracket_close_tl { () }
```

(End definition for `\l_siunitx_compound_bracket_close_tl` and `\l_siunitx_compound_bracket_open_tl`.)

List options.

```
18 \bool_new:N \l_siunitx_compound_exp_bracket_bool  
19 \bool_new:N \l_siunitx_compound_exp_combine_bool  
20 \bool_new:N \l_siunitx_compound_separator_text_bool  
21 \bool_new:N \l_siunitx_compound_unit_bracket_bool  
22 \bool_new:N \l_siunitx_compound_unit_power_bool  
23 \bool_new:N \l_siunitx_compound_unit_repeat_bool  
24 \keys_define:nn { siunitx }  
25 {  
26   compound-exponents .choice: ,  
27   compound-exponents / combine .code:n =  
28   {  
29     \bool_set_false:N \l_siunitx_compound_exp_bracket_bool  
30     \bool_set_true:N \l_siunitx_compound_exp_combine_bool  
31   } ,  
32   compound-exponents / combine-bracket .code:n =  
33   {  
34     \bool_set_true:N \l_siunitx_compound_exp_bracket_bool  
35     \bool_set_true:N \l_siunitx_compound_exp_combine_bool  
36   } ,  
37   compound-exponents / individual .code:n =  
38   {  
39     \bool_set_false:N \l_siunitx_compound_exp_bracket_bool  
40     \bool_set_false:N \l_siunitx_compound_exp_combine_bool  
41   } ,  
42   compound-final-separator .tl_set:N =  
43     \l_siunitx_compound_separator_final_tl ,  
44   compound-pair-separator .tl_set:N =  
45     \l_siunitx_compound_separator_pair_tl ,  
46   compound-separator .tl_set:N =  
47     \l_siunitx_compound_separator_tl ,  
48   compound-separator-mode .choice: ,  
49   compound-separator-mode / number .code:n =  
50   { \bool_set_false:N \l_siunitx_compound_separator_text_bool } ,  
51   compound-separator-mode / text .code:n =  
52   { \bool_set_true:N \l_siunitx_compound_separator_text_bool } ,  
53   compound-units .choice: ,  
54   compound-units / bracket .code:n =  
55   {  
56     \bool_set_true:N \l_siunitx_compound_unit_bracket_bool  
57     \bool_set_false:N \l_siunitx_compound_unit_power_bool  
58     \bool_set_false:N \l_siunitx_compound_unit_repeat_bool  
59   } ,
```

```

60   compound-units / bracket-power .code:n =
61   {
62     \bool_set_true:N \l__siunitx_compound_unit_bracket_bool
63     \bool_set_true:N \l__siunitx_compound_unit_power_bool
64     \bool_set_false:N \l__siunitx_compound_unit_repeat_bool
65   } ,
66   compound-units / power .code:n =
67   {
68     \bool_set_false:N \l__siunitx_compound_unit_bracket_bool
69     \bool_set_true:N \l__siunitx_compound_unit_power_bool
70     \bool_set_false:N \l__siunitx_compound_unit_repeat_bool
71   } ,
72   compound-units / repeat .code:n =
73   {
74     \bool_set_false:N \l__siunitx_compound_unit_bracket_bool
75     \bool_set_false:N \l__siunitx_compound_unit_power_bool
76     \bool_set_true:N \l__siunitx_compound_unit_repeat_bool
77   } ,
78   compound-units / single .code:n =
79   {
80     \bool_set_false:N \l__siunitx_compound_unit_bracket_bool
81     \bool_set_false:N \l__siunitx_compound_unit_power_bool
82     \bool_set_false:N \l__siunitx_compound_unit_repeat_bool
83   }
84 }
```

(End definition for `\l__siunitx_compound_separator_final_t1` and others.)

`\siunitx_compound_number:n`
`__siunitx_compound_format:n`
`__siunitx_compound_format:nn`
`__siunitx_compound_format:nnn`

Printing a generic set starts with the question of whether we want to extract exponents. If we do, then there is the work to do with extraction. Either way, the printing is handed off to a common function. We do a quick count up-front to avoid excess work when there is not actually a list.

```

85 \cs_new_protected:Npn \siunitx_compound_number:n #1
86 {
87   \group_begin:
88   \bool_set_false:N \l__siunitx_compound_unit_bool
89   \_\_siunitx_compound_format:nn {#1} { }
90   \_\_siunitx_compound_print:N \siunitx_print_number:x
91   \group_end:
92 }
93 \cs_new_protected:Npn \_\_siunitx_compound_format:nn #1#2
94 {
95   \seq_clear:N \l__siunitx_compound_tmp_seq
96   \bool_if:NTF \l__siunitx_number_parse_bool
97   {
98     \exp_args:Nxx \_\_siunitx_compound_format:nnn
99     { \tl_head:n {#1} }
100    { \tl_tail:n {#1} }
101    {#2}
102  }
103  { \tl_map_function:nN {#1} \_\_siunitx_compound_unparsed:n }
104 }
```

Formatting at a low level needs to know about units and numbers: we have to exchange data between the two. Most of the business of handling the units is left to a dedicated

auxiliary.

```

105 \cs_new_protected:Npn \__siunitx_compound_format:nnn #1#2#3
106 {
107     \siunitx_number_parse:nN {#1} \l__siunitx_compound_tmp_tl
108     \bool_if:NTF \l__siunitx_compound_unit_bool
109     { \__siunitx_compound_format_units:nn {#2} {#3} }
110     { \siunitx_number_process:NN \l__siunitx_compound_tmp_tl \l__siunitx_compound_first_tl
111 \bool_lazy_and:nnTF
112     { \l__siunitx_compound_exp_combine_bool }
113     { \int_compare_p:nNn { \tl_count:n {#2} } > 0 }
114     { \__siunitx_compound_extract_exponents: }
115     {
116         \bool_if:NTF \l__siunitx_compound_unit_bool
117         {
118             \tl_set:Nx \l__siunitx_compound_tmp_tl
119             { \siunitx_number_output:NN \l__siunitx_compound_first_tl \q_nil }
120             \tl_set:Nx \l__siunitx_compound_tmp_tl
121             { \__siunitx_compound_uncert_bracket:N \l__siunitx_compound_tmp_tl }
122         }
123         {
124             \tl_set:Nx \l__siunitx_compound_tmp_tl
125             { \siunitx_number_output:N \l__siunitx_compound_first_tl }
126         }
127         \seq_put_right:NV \l__siunitx_compound_tmp_seq \l__siunitx_compound_tmp_tl
128     }
129     \tl_map_function:nN {#2} \__siunitx_compound_parsed:n
130 }
```

Extracting exponents means dealing with the first entry as a special case. After that, apply fixed processing to all other entries, tidying up using the number formatter.

```

\__siunitx_compound_extract_exponents:
\__siunitx_compound_extract_exponents_auxi:w
\__siunitx_compound_extract_exponents_auxii:nw
\__siunitx_compound_extract_exponents_auxiii:nnnnnnn
131 \cs_new_protected:Npn \__siunitx_compound_extract_exponents:
132 {
133     \tl_set:Nx \l__siunitx_compound_tmp_tl
134     { \siunitx_number_output:NN \l__siunitx_compound_first_tl \q_nil }
135     \exp_after:wN \__siunitx_compound_extract_exponents_auxi:w
136     \l__siunitx_compound_tmp_tl \q_stop
137 }
138 \cs_new_protected:Npn \__siunitx_compound_extract_exponents_auxi:w
139 #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_nil #5 \q_nil #6 \q_nil #7 \q_nil #8
140 \q_nil #9 \q_stop
141 {
142     \__siunitx_compound_extract_exponents_auxi:nw {#1#2#3#4#5#6#7#8} #9 \q_stop
143 }
144 \cs_new_protected:Npn \__siunitx_compound_extract_exponents_auxii:nw
145 #1#2 \q_nil #3 \q_nil #4 \q_stop
146 {
147     \seq_put_right:Nn \l__siunitx_compound_tmp_seq { #1#2 }
148     \tl_set:Nn \l__siunitx_compound_exp_tl { #3#4 }
149     \exp_after:wN \__siunitx_compound_extract_exponents_auxiii:nnnnnnn
150     \l__siunitx_compound_first_tl
151 }
152 \cs_new_protected:Npn \__siunitx_compound_extract_exponents_auxiii:nnnnnnn
153 #1#2#3#4#5#6#7
154 {
```

```

155   \keys_set:nn { siunitx }
156   {
157     drop-exponent = true ,
158     exponent-mode = fixed ,
159     fixed-exponent = #6#7
160   }
161 }
```

(End definition for `\siunitx_compound_number:n` and others. This function is documented on page 20.)

`_siunitx_compound_parsed:n`

`_siunitx_compound_unparsed:n`

The simple cases for parsing (or not) all entries.

```

162 \cs_new_protected:Npn \_siunitx_compound_parsed:n #1
163 {
164   \bool_if:NTF \l_siunitx_compound_unit_bool
165   {
166     \siunitx_number_parse:nN {#1} \l_siunitx_compound_tmp_tl
167     \siunitx_number_process:NN \l_siunitx_compound_tmp_tl \l_siunitx_compound_tmp_tl
168     \tl_set:Nx \l_siunitx_compound_tmp_tl
169     { \siunitx_number_output:NN \l_siunitx_compound_tmp_tl \q_nil }
170     \tl_set:Nx \l_siunitx_compound_tmp_tl
171     { \_siunitx_compound_uncert_bracket:N \l_siunitx_compound_tmp_tl }
172   }
173   { \siunitx_number_format:nN {#1} \l_siunitx_compound_tmp_tl }
174   \seq_put_right:NV \l_siunitx_compound_tmp_seq \l_siunitx_compound_tmp_tl
175 }
176 \cs_new_protected:Npn \_siunitx_compound_unparsed:n #1
177 {
178   \seq_put_right:Nn \l_siunitx_compound_tmp_seq { \ensuremath {#1} }
179 }
```

(End definition for `_siunitx_compound_parsed:n` and `_siunitx_compound_unparsed:n`.)

`_siunitx_compound_format_units:nn`

`_siunitx_compound_format_combine-exponent:nn`

`_siunitx_compound_format_extract-exponent:n`

`_siunitx_compound_format_input:n`

`_siunitx_compound_format_combine-exponent:nn`

`_siunitx_compound_format_extract-exponent:nn`

`_siunitx_compound_format_combine-exponent_aux:n`

`_siunitx_compound_format_extract-exponent_aux:n`

`_siunitx_compound_extract_exp:nN`

`_siunitx_compound_extract_exp:nnnnnnN`

Actually formatting the units is much the same as is done in the quantities module, except that we have to cover the multiplication cases too: gets a bit repetitive. Notice that when combining exponents, there is no adjustment to the original exponent: we purely need to extract it.

```

180 \cs_new_protected:Npn \_siunitx_compound_format_units:nn #1#2
181 {
182   \bool_if:NTF \l_siunitx_compound_unit_power_bool
183   {
184     \use:c { __siunitx_compound_format_ \l_siunitx_quantity_prefix_mode_tl :nn }
185     {#2} { \tl_count:n {#1} + 1 }
186   }
187   {
188     \use:c { __siunitx_compound_format_ \l_siunitx_quantity_prefix_mode_tl :n } {#2}
189   }
190 }
191 \cs_new_protected:cpx { __siunitx_compound_format_combine-exponent:n } #1
192 {
193   \exp_not:c { __siunitx_compound_format_combine-exponent_aux:n }
194   {
195     \exp_not:N \siunitx_unit_format_combine_exponent:nnN
196     {#1}
197 }
```

```

198 }
199 \cs_new_protected:cpx { __siunitx_compound_format_combine-exponent:nn } #1#2
200 {
201     \exp_not:c { __siunitx_compound_format_combine-exponent_aux:n }
202     {
203         \exp_not:N \siunitx_unit_format_multiply_combine_exponent:nnnN
204         {#1} {#2}
205     }
206 }
207 \cs_new_protected:cpn { __siunitx_compound_format_combine-exponent_aux:n } #1
208 {
209     \bool_set_true:N \l_siunitx_compound_exp_combine_bool
210     \siunitx_number_process:NN \l_siunitx_compound_tmp_tl \l_siunitx_compound_first_tl
211     \exp_args:NV \__siunitx_compound_extract_exp:nN
212     \l_siunitx_compound_first_tl \l_siunitx_compound_tmp_fp
213     #1 \l_siunitx_compound_tmp_fp \l_siunitx_compound_unit_tl
214 }
215 \cs_new_protected:cpx { __siunitx_compound_format_extract-exponent:n } #1
216 {
217     \exp_not:c { __siunitx_compound_format_extract-exponent_aux:n }
218     { \exp_not:N \siunitx_unit_format_extract_prefixes:nNN {#1} }
219 }
220 \cs_new_protected:cpx { __siunitx_compound_format_extract-exponent:nn } #1#2
221 {
222     \exp_not:c { __siunitx_compound_format_extract-exponent_aux:n }
223     {
224         \exp_not:N \siunitx_unit_format_multiply_extract_prefixes:nnNN
225         {#1} {#2}
226     }
227 }
228 \cs_new_protected:cpn { __siunitx_compound_format_extract-exponent_aux:n } #1
229 {
230     #1 \l_siunitx_compound_unit_tl \l_siunitx_compound_tmp_fp
231     \tl_set:Nx \l_siunitx_compound_tmp_tl
232     { \siunitx_number_adjust_exponent:Nn \l_siunitx_compound_tmp_tl \l_siunitx_compound_t
233     \siunitx_number_process:NN \l_siunitx_compound_tmp_tl \l_siunitx_compound_first_tl
234     \bool_set_true:N \l_siunitx_compound_exp_combine_bool
235 }
236 \cs_new_protected:Npn \__siunitx_compound_format_input:n #1
237 {
238     \siunitx_number_process:NN \l_siunitx_compound_tmp_tl \l_siunitx_compound_first_tl
239     \siunitx_unit_format:nN {#1} \l_siunitx_compound_unit_tl
240 }
241 \cs_new_protected:Npn \__siunitx_compound_format_input:nn #1#2
242 {
243     \siunitx_number_process:NN \l_siunitx_compound_tmp_tl \l_siunitx_compound_first_tl
244     \siunitx_unit_format_multiply:nnN {#1} {#2} \l_siunitx_compound_unit_tl
245 }
246 \cs_new_protected:Npn \__siunitx_compound_extract_exp:nN #1#2
247 { \__siunitx_compound_extract_exp:nnnnnnnN #1 #2 }
248 \cs_new_protected:Npn \__siunitx_compound_extract_exp:nnnnnnnN #1#2#3#4#5#6#7#8
249 { \fp_set:Nn #8 {#6#7} }

```

(End definition for `__siunitx_compound_format_units:nn` and others.)

\siunitx_compound_quantity:nn

For quantities, life is more complex as there are interactions between the options for exponents and units.

```

250 \cs_new_protected:Npn \siunitx_compound_quantity:nn #1#2
251 {
252     \group_begin:
253         \bool_if:NT \l__siunitx_compound_unit_bracket_bool
254             { \bool_set_true:N \l__siunitx_compound_exp_bracket_bool }
255         \bool_if:NT \l__siunitx_compound_unit_repeat_bool
256             { \bool_set_false:N \l__siunitx_compound_exp_combine_bool }
257         \bool_lazy_or:nnT
258             { \l__siunitx_compound_unit_bracket_bool }
259             { ! \l__siunitx_compound_unit_repeat_bool }
260             { \bool_set_false:N \l__siunitx_number_bracket_ambiguous_bool }
261         \bool_set_true:N \l__siunitx_compound_unit_bool
262         \__siunitx_compound_format:nn {#1} {#2}
263         \str_if_eq:VnT \l__siunitx_quantity_prefix_mode_tl { combine-exponent }
264             { \tl_clear:N \l__siunitx_compound_exp_tl }
265         \bool_if:NTF \l__siunitx_compound_unit_repeat_bool
266             { \__siunitx_compound_print:N \__siunitx_compound_print_quantity:x }
267             {
268                 \bool_lazy_and:nnTF
269                     { \l__siunitx_compound_unit_bracket_bool }
270                     { \tl_if_empty_p:N \l__siunitx_compound_exp_tl }
271                 {
272                     \siunitx_print_number:V \l__siunitx_compound_bracket_open_tl
273                     \__siunitx_compound_print:N \siunitx_print_number:x
274                     \siunitx_print_number:V \l__siunitx_compound_bracket_close_tl
275                 }
276                 { \__siunitx_compound_print:N \siunitx_print_number:x }
277                 \__siunitx_compound_print_quantity:n { }
278             }
279         \group_end:
280     }

```

(End definition for \siunitx_compound_quantity:nn. This function is documented on page 20.)

```

\__siunitx_compound_print:N
    \__siunitx_compound_print:nnN
        \__siunitx_compound_print:xxN
    \__siunitx_compound_print:mmN
        \__siunitx_compound_print_aux:n
    \__siunitx_compound_print_aux:nn
\__siunitx_compound_print_quantity:n
\__siunitx_compound_print_quantity:x
\__siunitx_compound_print_separators:n
\__siunitx_compound_print_separators:V

```

We now need to know how many entries there are: the reason we don't use \seq_use:Nnnn is that we want to be able to insert \siunitx_print_...:n in a controlled way.

```

281 \cs_new_protected:Npn \__siunitx_compound_print:N #1
282 {
283     \bool_lazy_and:nnTF
284         { \l__siunitx_compound_exp_bracket_bool }
285         { ! \tl_if_empty_p:N \l__siunitx_compound_exp_tl }
286     {
287         \__siunitx_compound_print:xxN
288             { \exp_not:V \l__siunitx_compound_bracket_open_tl }
289             {
290                 \exp_not:V \l__siunitx_compound_bracket_close_tl
291                 \exp_not:V \l__siunitx_compound_exp_tl
292             }
293         #1
294     }
295     { \__siunitx_compound_print:xxN { } { \exp_not:V \l__siunitx_compound_exp_tl } #1 }

```

```

296    }
297 \cs_new_protected:Npn \__siunitx_compound_print:nnN #1#2#3
298 {
299     \exp_args:Nx \__siunitx_compound_print:nnnN
300     { \seq_count:N \l__siunitx_compound_tmp_seq } {#1} {#2} #3
301 }
302 \cs_generate_variant:Nn \__siunitx_compound_print:nnN { xx }

A rather long auxiliary as we want a way to have the brackets/exponent available. The
actual flow is simple enough: see how many entries there are and print as required. To
keep everything generic, we have some slightly tricky saving of data to allow everything
to go to the mapping.

303 \cs_new_protected:Npn \__siunitx_compound_print:nnnN #1#2#3#4
304 {
305     \int_case:nnF {#1}
306     {
307         { 0 } { }
308         { 1 }
309         {
310             #4
311             { \seq_item:Nn \l__siunitx_compound_tmp_seq { 1 } }
312         }
313         { 2 }
314         {
315             #4
316             {
317                 \exp_not:n {#2}
318                 \seq_item:Nn \l__siunitx_compound_tmp_seq { 1 }
319             }
320             \__siunitx_compound_print_separator:V \l__siunitx_compound_separator_pair_tl
321             #4
322             {
323                 \seq_item:Nn \l__siunitx_compound_tmp_seq { 2 }
324                 \exp_not:n {#3}
325             }
326         }
327     }
328     {
329         \int_set:Nn \l__siunitx_compound_count_int {#1}
330         \tl_set:Nn \l__siunitx_compound_start_tl {#2}
331         \tl_set:Nn \l__siunitx_compound_end_tl {#3}
332         \cs_set_eq:NN \__siunitx_compound_print_aux:n #4
333         \seq_map_indexed_function:NN
334             \l__siunitx_compound_tmp_seq
335             \__siunitx_compound_print_aux:nn
336     }
337 }
338 \cs_new_protected:Npn \__siunitx_compound_print_aux:n #1 { }
339 \cs_new_protected:Npn \__siunitx_compound_print_aux:nn #1#2
340 {
341     \int_case:nnF {#1}
342     {
343         { 1 }
344         {

```

```

345     \_siunitx_compound_print_aux:n
346     {
347         \exp_not:V \l_siunitx_compound_start_tl
348         \exp_not:n {#2}
349     }
350     \_siunitx_compound_print_separator:V \l_siunitx_compound_separator_tl
351 }
352 { \l_siunitx_compound_count_int - 1 }
353 {
354     \_siunitx_compound_print_aux:n { \exp_not:n {#2} }
355     \_siunitx_compound_print_separator:V \l_siunitx_compound_separator_final_tl
356 }
357 { \l_siunitx_compound_count_int }
358 {
359     \_siunitx_compound_print_aux:n
360     {
361         \exp_not:n {#2}
362         \exp_not:V \l_siunitx_compound_end_tl
363     }
364 }
365 }
366 {
367     \_siunitx_compound_print_aux:n { \exp_not:n {#2} }
368     \_siunitx_compound_print_separator:V \l_siunitx_compound_separator_tl
369 }
370 }
371 \cs_new_protected:Npn \_siunitx_compound_print_quantity:n #1
372 { \siunitx_quantity_print:nV {#1} \l_siunitx_compound_unit_tl }
373 \cs_generate_variant:Nn \_siunitx_compound_print_quantity:n { x }
374 \cs_new_protected:Npn \_siunitx_compound_print_separator:n #1
375 {
376     \bool_if:NTF \l_siunitx_compound_separator_text_bool
377     { #1 }
378     { \siunitx_print_number:n {#1} }
379 }
380 \cs_generate_variant:Nn \_siunitx_compound_print_separator:n { V }

(End definition for \_siunitx_compound_print:N and others.)

```

Check for the case where there is a separate uncertainty but not exponent, when we are handling units.

```

381 \cs_new:Npn \_siunitx_compound_uncert_bracket:N #1
382 { \exp_after:wN \_siunitx_compound_uncert_bracket:w #1 \q_stop }
383 \cs_new:Npn \_siunitx_compound_uncert_bracket:w
384 #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_nil #5 \q_nil #6 \q_nil #7 \q_nil
385 #8 \q_nil #9 \q_stop
386 { \_siunitx_compound_uncert_bracket:nnw {#1#2#3#4#5#6} {#7#8} #9 \q_stop }
387 \cs_new:Npn \_siunitx_compound_uncert_bracket:nnw #1#2 #3 \q_nil #4 \q_nil #5 \q_stop
388 {
389     \bool_lazy_or:nnTF
390     { \tl_if_blank_p:n {#2#3} }
391     { ! \tl_if_blank_p:n {#5} }
392     { \exp_not:n {#1#2#3#4#5} }
393 }

```

```

394     \exp_not:V \l_siunitx_compound_bracket_open_tl
395     \exp_not:n {#1#2#3}
396     \exp_not:V \l_siunitx_compound_bracket_close_tl
397     \exp_not:n {#4#5}
398   }
399 }

```

(End definition for `_siunitx_compound_uncert_bracket:N`, `_siunitx_compound_uncert_bracket:w`, and `_siunitx_compound_uncert_bracket:nnw`.)

1.2 Lists

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
400 <@=siunitx_list>
```

`\l_siunitx_list_separator_tl`

```

401 \tl_new:N \l_siunitx_list_exp_tl
402 \tl_new:N \l_siunitx_list_units_tl
403 \keys_define:nn { siunitx }
404 {
405   list-exponents .choices:nn =
406   { combine , combine-bracket , individual }
407   { \tl_set_eq:NN \l_siunitx_list_exp_tl \l_keys_choice_tl } ,
408   list-final-separator .tl_set:N = \l_siunitx_list_separator_final_tl ,
409   list-pair-separator .tl_set:N = \l_siunitx_list_separator_pair_tl ,
410   list-separator .tl_set:N = \l_siunitx_list_separator_tl ,
411   list-units .choices:nn =
412   { bracket , repeat , single }
413   { \tl_set_eq:NN \l_siunitx_list_units_tl \l_keys_choice_tl }
414 }
```

(End definition for `\l_siunitx_list_separator_tl` and others. These variables are documented on page 20.)

`\siunitx_number_list:nn`

`\siunitx_quantity_list:nn`

`_siunitx_list_aux:`

```

415 \cs_new_protected:Npn \siunitx_number_list:nn #1
416   {
417     \group_begin:
418       \_siunitx_list_aux:
419       \siunitx_compound_number:n {#1}
420     \group_end:
421   }
422 \cs_new_protected:Npn \siunitx_quantity_list:nn #1#2
423   {
424     \group_begin:
425       \_siunitx_list_aux:
426       \siunitx_compound_quantity:nn {#1} {#2}
427     \group_end:
428   }
429 \cs_new_protected:Npn \_siunitx_list_aux:
430   {
431     \keys_set:nx { siunitx }
432   }
```

```

433     compound-exponents      = \l_siunitx_list_exp_tl ,
434     compound-final-separator =
435     { \exp_not:V \l_siunitx_list_separator_final_tl } ,
436     compound-pair-separator =
437     { \exp_not:V \l_siunitx_list_separator_pair_tl } ,
438     compound-separator      =
439     { \exp_not:V \l_siunitx_list_separator_tl } ,
440     compound-separator-mode = text ,
441     compound-units          = \l_siunitx_list_units_tl
442   }
443 }

(End definition for \siunitx_number_list:nn, \siunitx_quantity_list:nn, and \__siunitx_list-
aux:. These functions are documented on page 20.)

```

1.3 Products

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
444 <@=siunitx_product>
```

Options for products.

```

445 \tl_new:N \l_siunitx_product_exp_tl
446 \bool_new:N \l_siunitx_product_phrase_bool
447 \tl_new:N \l_siunitx_product_symbol_tl
\l_siunitx_product_units_tl
448 \keys_define:nn { siunitx }
449 {
450   product-exponents .choices:nn =
451   { combine , combine-bracket , individual }
452   { \tl_set_eq:NN \l_siunitx_product_exp_tl \l_keys_choice_tl } ,
453   product-mode .choice: ,
454   product-mode / phrase .code:n =
455   { \bool_set_true:N \l_siunitx_product_phrase_bool } ,
456   product-mode / symbol .code:n =
457   { \bool_set_false:N \l_siunitx_product_phrase_bool } ,
458   product-phrase .tl_set:N = \l_siunitx_product_phrase_tl ,
459   product-symbol .tl_set:N = \l_siunitx_product_symbol_tl ,
460   product-units .choices:nn =
461   { bracket , bracket-power , power , repeat , single }
462   { \tl_set_eq:NN \l_siunitx_product_units_tl \l_keys_choice_tl }
463 }

(End definition for \l_siunitx_product_exp_tl and others.)
```

\siunitx_number_product:n Simply recover the settings and use as a list.

```

\siunitx_quantity_product:nn
\__siunitx_product_aux:
\__siunitx_product_aux:n
\__siunitx_product_aux:x
464 \cs_new_protected:Npn \siunitx_number_product:n #1
465   {
466     \group_begin:
467     \__siunitx_product_aux:
468     \siunitx_compound_number:n {#1}
469     \group_end:
470   }
471 \cs_new_protected:Npn \siunitx_quantity_product:nn #1#2
472   {
```

```

473   \group_begin:
474     \_\_siunitx_product_aux:
475     \siunitx_compound_quantity:nn {#1} {#2}
476   \group_end:
477 }
478 \cs_new_protected:Npn \_\_siunitx_product_aux:
479 {
480   \bool_if:NTF \l_\_siunitx_product_phrase_bool
481   { \_\_siunitx_product_aux:x { \exp_not:V \l_\_siunitx_product_phrase_tl } }
482   { \_\_siunitx_product_aux:x { { } \exp_not:V \l_\_siunitx_product_symbol_tl { } } }
483 }
484 \cs_new_protected:Npn \_\_siunitx_product_aux:n #1
485 {
486   \keys_set:nx { siunitx }
487   {
488     compound-exponents      = \l_\_siunitx_product_exp_tl ,
489     compound-final-separator = { \exp_not:n {#1} } ,
490     compound-pair-separator = { \exp_not:n {#1} } ,
491     compound-separator      = { \exp_not:n {#1} } ,
492     compound-separator-mode =
493       \bool_if:NTF \l_\_siunitx_product_phrase_bool { text } { number } ,
494     compound-units          = \l_\_siunitx_product_units_tl
495   }
496 }
497 \cs_generate_variant:Nn \_\_siunitx_product_aux:n { x }

```

(End definition for `\siunitx_number_product:n` and others. These functions are documented on page 20.)

1.4 Ranges

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
498 <@=siunitx_range>
```

`\l__siunitx_range_exp_tl` Options for products.

```

499 \tl_new:N \l_\_siunitx_range_exp_tl
500 \tl_new:N \l_\_siunitx_range_units_tl
501 \keys_define:nn { siunitx }
502 {
503   range-exponents .choices:nn =
504   { combine , combine-bracket , individual }
505   { \tl_set_eq:NN \l_\_siunitx_range_exp_tl \l_keys_choice_tl } ,
506   range-phrase .tl_set:N = \l_\_siunitx_range_phrase_tl ,
507   range-units .choices:nn =
508   { bracket , repeat , single }
509   { \tl_set_eq:NN \l_\_siunitx_range_units_tl \l_keys_choice_tl }
510 }

```

(End definition for `\l__siunitx_range_exp_tl`, `\l__siunitx_range_phrase_tl`, and `\l__siunitx_range_units_tl`. This variable is documented on page 21.)

`\siunitx_number_range:nn` Simply recover the settings and use as a list.

```

511 \cs_new_protected:Npn \siunitx_number_range:nn #1#2
\_\_siunitx_range_aux:
```

```

512 {
513   \group_begin:
514     \__siunitx_range_aux:
515     \siunitx_compound_number:n { {#1} {#2} }
516   \group_end:
517 }
518 \cs_new_protected:Npn \siunitx_quantity_range:nnn #1#2#3
519 {
520   \group_begin:
521     \__siunitx_range_aux:
522     \siunitx_compound_quantity:nn { {#1} {#2} } {#3}
523   \group_end:
524 }
525 \cs_new_protected:Npn \__siunitx_range_aux:
526 {
527   \keys_set:nx { siunitx }
528   {
529     compound-exponents      = \l__siunitx_range_exp_tl ,
530     compound-pair-separator = { \exp_not:V \l_siunitx_range_phrase_tl } ,
531     compound-separator-mode = text ,
532     compound-units          = \l__siunitx_range_units_tl
533   }
534 }

```

(End definition for `\siunitx_number_range:nn`, `\siunitx_quantity_range:nnn`, and `__siunitx_range_aux`. These functions are documented on page 20.)

1.5 Standard settings for module options

Some of these follow naturally from the point of definition (*e.g.* boolean variables are always `false` to begin with), but for clarity everything is set here.

```

535 \keys_set:nn { siunitx }
536 {
537   compound-exponents      = individual ,
538   compound-final-separator =
539   {
540     \ifmmode \ \else \space \fi
541     \text { and }
542     \ifmmode \ \else \space \fi
543   } ,
544   compound-pair-separator =
545   {
546     \ifmmode \ \else \space \fi
547     \text { and }
548     \ifmmode \ \else \space \fi
549   } ,
550   compound-separator      =
551   { , \ifmmode \ \else \space \fi } ,
552   compound-separator-mode = text ,
553   compound-units          = repeat ,
554   list-exponents          = individual ,
555   list-final-separator    =
556   {
557     \ifmmode \ \else \space \fi

```

```

558      \text { and }
559      \ifmmode \ \else \space \fi
560    } ,
561  list-pair-separator      =
562  {
563    \ifmmode \ \else \space \fi
564    \text { and }
565    \ifmmode \ \else \space \fi
566  } ,
567  list-separator          =
568  { , \ifmmode \ \else \space \fi } ,
569  list-units                = repeat ,
570  product-exponents        = individual ,
571  product-mode              = symbol ,
572  product-phrase            =
573  {
574    \ifmmode \ \else \space \fi
575    \text { by }
576    \ifmmode \ \else \space \fi
577  } ,
578  product-symbol            = \times ,
579  product-units             = repeat ,
580  range-exponents          = individual ,
581  range-phrase              =
582  {
583    \ifmmode \ \else \space \fi
584    \text { to }
585    \ifmmode \ \else \space \fi
586  } ,
587  range-units                = repeat
588 }
589 </package>

```

Part IV

siunitx-locale – Localisation

This submodule is concerned with localisation of `siunitx` output based on the locale. If the `translations` package is available, this is loaded here and used to provide various fixed strings for output.

`locale` `locale = <locale>`

Selects the `<locale>` used to apply standard settings for other keys, principally `exponent-product`, `inter-unit-product` and `output-decimal-marker`.

1 siunitx-locale implementation

Start the DocStrip guards.

`1 {*package}`

Identify the internal prefix (`LATEX3` DocStrip convention): only internal material in this *submodule* should be used directly.

`2 @@=siunitx_locale`

1.1 Locales

The basics for defining locales are easy: these are just meta keys.

```
3 \keys_define:nn { siunitx }
4   {
5     locale .choice: ,
6     locale / DE .meta:n =
7       {
8         exponent-product      = \cdot ,
9         inter-unit-product    = \, ,
10        output-decimal-marker = { , }
11      } ,
12     locale / FR .meta:n =
13       {
14         exponent-product      = \times ,
15         inter-unit-product    = \, ,
16         output-decimal-marker = { , }
17      } ,
18     locale / UK .meta:n =
19       {
20         exponent-product      = \times ,
21         inter-unit-product    = \, ,
22         output-decimal-marker = .
23      },
24     locale / US .meta:n =
25       {
26         exponent-product      = \times ,
27         inter-unit-product    = \, ,
28         output-decimal-marker = .
29      },
```

```

30     locale / ZA .meta:n =
31     {
32         exponent-product      = \times ,
33         inter-unit-product   = \cdot ,
34         output-decimal-marker = { , }
35     }
36 }
```

1.2 Localisation

Localisation makes use of the `translator` package. This only happens if it is available, and is transparent to the user.

```

37 \file_if_exist:nT { translations.sty }
38 {
39     \RequirePackage { translations }
40     \DeclareTranslation { English } { to-(numerical-range) } { to }
41     \DeclareTranslation { French } { to-(numerical-range) } { à }
42     \DeclareTranslation { German } { to-(numerical-range) } { bis }
43     \DeclareTranslation { Spanish } { to-(numerical-range) } { a }
44     \keys_set:nn { siunitx }
45     {
46         list-final-separator =
47         {
48             \ifmmode \ \else \space \fi
49             \text { \GetTranslation { and } }
50             \ifmmode \ \else \space \fi
51         } ,
52         list-pair-separator =
53         {
54             \ifmmode \ \else \space \fi
55             \text { \GetTranslation { and } }
56             \ifmmode \ \else \space \fi
57         } ,
58         range-phrase          =
59         {
60             \ifmmode \ \else \space \fi
61             \text { \GetTranslation { to-(numerical-range) } }
62             \ifmmode \ \else \space \fi
63         }
64     }
65 }
```

Part V

siunitx-number – Parsing and formatting numbers

This submodule is dedicated to parsing and formatting numbers. A small number of L^AT_EX 2 _{ε} math mode commands are assumed to be available as part of the formatted output. The sign commands \mp , \pm , \ll , \leq , \gg and \geq are used to replace two-character input; \pm is also required for the output of uncertainties. The standard settings require \times . For the display of colored negative numbers, the command \color is assumed to be available. Where the latter may apply, numbers should be printed inside a group: note that T_EX grouping is not added *within* formatted numbers as they may need to be decomposed into parts (see `\siunitx_number_output:NN`). Such a color will be the *first* part of the result, meaning that a test for an initial \color and following brace group may be used to detect/remove/adjust this part.

1 Formatting numbers

`\siunitx_number_parse:nN` { $\langle number \rangle$ } $\langle tl \ var \rangle$

Parses the *number* and stores the resulting internal representation in the $\langle tl \ var \rangle$. The parsing is influenced by the various key–value settings for numerical input. The $\langle number \rangle$ should comprise a single real value, possibly with comparator, uncertainty and exponent parts. If the number is invalid, or if number parsing is disabled, the result will be an entirely empty $\langle tl \ var \rangle$.

The structure of a valid number is:

$$\{ \langle comparator \rangle \} \{ \langle sign \rangle \} \{ \langle integer \rangle \} \{ \langle decimal \rangle \} \{ \langle uncertainty \rangle \} \\ \{ \langle exponent sign \rangle \} \{ \langle exponent \rangle \}$$

where the two sign parts must be single tokens if present, and all other components must be given in braces. The number will have at least one digit for both the $\langle integer \rangle$ and $\langle exponent \rangle$ parts: these are required. The $\langle uncertainty \rangle$ part should either be blank or contain an $\langle identifier \rangle$ (as a brace group), followed by one or more data entries. Valid $\langle identifiers \rangle$ currently are

S A single symmetrical uncertainty (*e.g.* a statistical standard uncertainty)

| | |
|---|---|
| <code>\siunitx_number_process:NN</code> | <code>\siunitx_number_process:N <tl var1> <tl var2></code> |
| | Applies a set of number processing operations to the <i><internal number></i> stored in the <i><tl var1></i> , <i>viz.</i> in order |
| | <ol style="list-style-type: none"> 1. Dropping uncertainty 2. Converting to scientific mode (or similar) 3. Rounding 4. Dropping zero decimal part 5. Forcing a minimum number of digits |
| | with the result stored in <i><tl var2></i> . |

```
\siunitx_number_output:N ☆ \siunitx_number_output:N <number>
\siunitx_number_output:n ☆ \siunitx_number_output:NN <number> <marker>
\siunitx_number_output:NN ☆
\siunitx_number_output:nN ☆
```

Formats the *<number>* (in the `siunitx` internal format), producing the result in a form suitable for typesetting in math mode. The details for the formatting are controlled by a number of key-value options. Note that *formatting* does not apply any manipulation (processing) to the number. This function is usable in an e- or x-type expansion, and further uncontrolled expansion is prevented by appropriate use of `\exp_not:n` internally.

In the NN version, the *<marker>* token is inserted at each possible alignment position in the output, *viz.*

- Between the comparator and the integer (*before* any sign for the integer)
- Between the sign and the first digit of the integer
- Both sides of the decimal marker
- Both sides of the separated uncertainty sign (*i.e.* after the decimal part and before any integer uncertainty part)
- Both sides of the decimal marker for a separated uncertainty
- Both sides of the multiplication symbol for the exponent part.

The n and nN version take a token list, which should be in the internal `siunitx` format.

| | |
|--|--|
| <code>\siunitx_number_format:nN</code> | <code>\siunitx_number_format:nN {<number>} <tl var></code> |
|--|--|

Carries out a combination of `\siunitx_number_parse:nN`, `\siunitx_number_process:NN` and `\siunitx_number_output:N` using x-type expansion to place the result in the *<tl var>*. If `\l_siunitx_number_parse_bool` if false, the input is simply stored inside the *<tl var>* inside `\ensuremath`.

| | |
|---|--|
| <code>\siunitx_number_adjust_exponent:Nn *</code> | <code>\siunitx_number_adjust_exponent:Nn <number> {{fp expr}}</code> |
|---|--|

Adjusts the exponent of the *<number>* (in internal format) by the *<fp expr>* and leaves the result in the input stream.

```
\siunitx_number_normalize_symbols:N \siunitx_number_normalize_symbols:N <tl var>
```

Replaces all multi-token signs and comparators in the $\langle tl\ var\rangle$ with their single-token equivalents. Replaces any active hyphen tokens with non-active versions.

```
\siunitx_if_number_p:n * \siunitx_if_number_token:NTF {\langle tokens\rangle}
\siunitx_if_number:nTF * {\langle true code\rangle} {\langle false code\rangle}
```

Determines if the $\langle tokens\rangle$ form a valid number which can be fully parsed by **siunitx**.

```
\siunitx_if_number_token:NTF \siunitx_if_number_token:NTF {\langle token\rangle}
{\langle true code\rangle} {\langle false code\rangle}
```

Determines if the $\langle token\rangle$ is valid in a number based on those tokens currently set up for detection in a number.

```
\l_siunitx_bracket_ambiguous_bool
```

A switch to control whether ambiguous numbers are bracketed: this can also be covered in quantity formatting by a setting there.

```
\l_siunitx_number_parse_bool
```

A switch to control whether any parsing is attempted for numbers.

```
\l_siunitx_number_comparator_tl
\l_siunitx_number_exponent_tl
\l_siunitx_number_sign_tl
```

The list of possible input comparators, exponent markers and signs.

```
\l_siunitx_number_input_decimal_tl
\l_siunitx_number_output_decimal_tl
```

The list of possible input decimal marker(s), and the output marker.

1.1 Key-value options

The options defined by this submodule are available within the `l3keys siunitx` tree.

```
bracket-ambiguous-numbers bracket-ambiguous-numbers = true|false
```

```
bracket-negative-numbers bracket-negative-numbers = true|false
```

```
drop-exponent drop-exponent = true|false
```

```
drop-uncertainty drop-uncertainty = true|false
```

```
drop-zero-decimal drop-zero-decimal = true|false
```

| | |
|--------------------------------|---|
| <u>evaluate-expression</u> | evaluate-expression = true false |
| <u>exponent-base</u> | exponent-base = $\langle \text{base} \rangle$ |
| <u>exponent-mode</u> | exponent-mode = engineering fixed input scientific |
| <u>exponent-product</u> | exponent-product = $\langle \text{symbol} \rangle$ |
| <u>expression</u> | expression = $\langle \text{expression} \rangle$ |
| <u>fixed-exponent</u> | fixed-exponent = $\langle \text{exponent} \rangle$ |
| <u>group-digits</u> | group-digits = all decimal integer none |
| <u>group-minimum-digits</u> | group-minimum-digits = $\langle \text{value} \rangle$ |
| <u>group-separator</u> | group-separator = $\langle \text{symbol} \rangle$ |
| <u>input-close-uncertainty</u> | input-close-uncertainty = $\langle \text{tokens} \rangle$ |
| <u>input-comparators</u> | input-comparators = $\langle \text{tokens} \rangle$ |
| <u>input-close-uncertainty</u> | input-close-uncertainty = $\langle \text{tokens} \rangle$ |
| <u>input-decimal-markers</u> | input-decimal-markers = $\langle \text{tokens} \rangle$ |
| <u>input-digits</u> | input-digits = $\langle \text{tokens} \rangle$ |
| <u>input-exponent-markers</u> | input-exponent-markers = $\langle \text{tokens} \rangle$ |
| <u>input-open-uncertainty</u> | input-open-uncertainty = $\langle \text{tokens} \rangle$ |
| <u>input-signs</u> | input-signs = $\langle \text{tokens} \rangle$ |
| <u>input-uncertainty-signs</u> | input-uncertainty-signs = $\langle \text{tokens} \rangle$ |

```
minimum-decimal-digits    minimum-decimal-digits = <min>

minimum-integer-digits    minimum-integer-digits = <min>

negative-color            negative-color = <color>

output-close-uncertainty  output-close-uncertainty = <symbol>

output-decimal-marker     output-decimal-marker = <symbol>

output-open-uncertainty   output-open-uncertainty = <symbol>

parse-numbers             parse-numbers = true|false

print-implicit-plus       print-implicit-plus = true|false

print-unity-mantissa      print-unity-mantissa = true|false

print-zero-exponent       print-zero-exponent = true|false

retain-explicit-plus      retain-explicit-plus = true|false

retain-zero-uncertainty   retain-zero-uncertainty = true|false

round-half                round-half = even|up

round-minimum             round-minimum = <min>

round-mode                round-mode = figures|none|places|uncertainty

round-pad                 round-pad = true|false

round-precision            round-precision = <precision>

tight-spacing              tight-spacing = true|false
```

uncertainty-mode uncertainty-mode = compact|compact-marker|full|separate

uncertainty-separator uncertainty-separator = *<separator>*

2 siunitx-number implementation

Start the DocStrip guards.

1 *(*package)*

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

2 *(@@=siunitx_number)*

2.1 Initial set-up

Variants not provided by `expl3`.

3 *\cs_generate_variant:Nn \tl_if_blank:nTF { f }*
4 *\cs_generate_variant:Nn \tl_if_blank_p:n { f }*
5 *\cs_generate_variant:Nn \tl_if_in:NnTF { NV }*
6 *\cs_generate_variant:Nn \tl_replace_all:Nnn { NnV }*

`\l_siunitx_number_tmp_tl` Scratch space.

7 *\tl_new:N \l_siunitx_number_tmp_tl*

(End definition for \l_siunitx_number_tmp_tl.)

2.2 Main formatting routine

`\l_siunitx_number_outputted_tl` A token list for the final formatted result: may or may not be generated by the parser, depending on settings which are active.

8 *\tl_new:N \l_siunitx_number_outputted_tl*

(End definition for \l_siunitx_number_outputted_tl.)

`\l_siunitx_number_parse_bool` Tracks whether to parse numbers: public as this may affect other behaviors.

9 *\tl_new:N \l_siunitx_number_parse_bool*

(End definition for \l_siunitx_number_parse_bool. This variable is documented on page 40.)

`\l_siunitx_number_parse_bool` Top-level options.

10 *\keys_define:nn { siunitx } {*
11 *parse-numbers .bool_set:N = \l_siunitx_number_parse_bool*
12 *}*
13 }

(End definition for \l_siunitx_number_parse_bool. This variable is documented on page 40.)

```

\siunitx_number_format:nN
14 \cs_new_protected:Npn \siunitx_number_format:nN #1#2
15 {
16   \group_begin:
17     \bool_if:NTF \l_siunitx_number_parse_bool
18     {
19       \siunitx_number_parse:nN {#1} \l_siunitx_number_parsed_tl
20       \siunitx_number_process:NN \l_siunitx_number_parsed_tl \l_siunitx_number_parsed_t1
21       \tl_set:Nx \l_siunitx_number_outputted_t1
22       { \siunitx_number_output:N \l_siunitx_number_parsed_tl }
23     }
24     { \tl_set:Nn \l_siunitx_number_outputted_t1 { \ensuremath {#1} } }
25   \exp_args:NNNV \group_end:
26   \tl_set:Nn #2 \l_siunitx_number_outputted_t1
27 }

```

(End definition for `\siunitx_number_format:nN`. This function is documented on page 39.)

2.3 Parsing numbers

Before numbers can be manipulated or formatted they need to be parsed into an internal form. In particular, if multiple code paths are to be avoided, it is necessary to do such parsing even for relatively simple cases such as converting `1e10` to `1 \times 10^{10}`.

Storing the result of such parsing can be done in a number of ways. In the first version of `siunitx` a series of separate data stores were used. This is potentially quite fast (as recovery of items relies only on `TeX`'s hash table) but makes managing the various data entries somewhat tedious and error-prone. For version two of the package, a single data structure (property list) was used for each part of the parsed number. Whilst this is easy to manage and extend, it is somewhat slower as at a `TeX` level there are repeated pack–unpack steps. In particular, the fact that there are a limited number of items to track for a “number” means that a more efficient approach is desirable (contrast parsing units, which is open-ended and therefore fits well with using a property list).

In this release, the structure of a valid number is:

$$\{ \langle \text{comparator} \rangle \langle \text{sign} \rangle \{ \langle \text{integer} \rangle \} \{ \langle \text{decimal} \rangle \} \{ \langle \text{uncertainty} \rangle \} \\ \langle \text{exponent sign} \rangle \{ \langle \text{exponent} \rangle \} \}$$

where all components must be given in braces. *All* of the components must be present in a stored number (*i.e.* at the end of parsing). The number must have at least one digit for both the `\langle integer \rangle` and `\langle exponent \rangle` parts.

A non-empty `\langle uncertainty \rangle` must contain one leading brace group containing an identifier, then zero or more brace groups which contain the uncertainty data. In this release, the known uncertainty types are

- **S:** A symmetrical statistical uncertainty made up of a single value. These are stored as uncertainty in significant digits, with no radix point in the stored value.

`\l_siunitx_number_input_decimal_tl` The input decimal marker(s).

```

28 \tl_new:N \l_siunitx_number_input_decimal_tl

```

(End definition for `\l_siunitx_number_input_decimal_tl`. This variable is documented on page 40.)

```
\l_siunitx_number_expression_bool
```

Options which determine the various valid parts of a parsed number.

```
29 \keys_define:nn { siunitx }
30   {
31     evaluate-expression .bool_set:N =
32       \l_siunitx_number_expression_bool ,
33     expression .code:n =
34       \cs_set:Npn \_siunitx_number_expression:n ##1 {#1} ,
35     input-close-uncertainty .tl_set:N =
36       \l_siunitx_number_input_uncert_close_tl ,
37     input-comparators .tl_set:N =
38       \l_siunitx_number_input_comparator_tl ,
39     input-decimal-markers .tl_set:N =
40       \l_siunitx_number_input_decimal_tl ,
41     input-digits .tl_set:N =
42       \l_siunitx_number_input_digit_tl ,
43     input-exponent-markers .tl_set:N =
44       \l_siunitx_number_input_exponent_tl ,
45     input-ignore .tl_set:N =
46       \l_siunitx_number_input_ignore_tl ,
47     input-open-uncertainty .tl_set:N =
48       \l_siunitx_number_input_uncert_open_tl ,
49     input-signs .tl_set:N =
50       \l_siunitx_number_input_sign_tl ,
51     input-uncertainty-signs .code:n =
52   {
53     \tl_set:Nn \l_siunitx_number_input_uncert_sign_tl {#1}
54     \tl_map_inline:nn {#1}
55     {
56       \tl_if_in:NnF \l_siunitx_number_input_sign_tl {##1}
57         { \tl_put_right:Nn \l_siunitx_number_input_sign_tl {##1} }
58     }
59   },
60   parse-numbers .bool_set:N =
61     \l_siunitx_number_parse_bool ,
62   retain-explicit-plus .bool_set:N =
63     \l_siunitx_number_explicit_plus_bool ,
64   retain-zero-uncertainty .bool_set:N =
65     \l_siunitx_number_zero_uncert_bool
66   }
67 \cs_new:Npn \_siunitx_number_expression:n #1 { }
68 \tl_new:N \l_siunitx_number_input_uncert_sign_tl
```

(End definition for `\l_siunitx_number_expression_bool` and others. These variables are documented on page ??.)

```
\l_siunitx_number_arg_tl
```

The input argument or a part thereof, depending on the position in the parsing routine.

```
69 \tl_new:N \l_siunitx_number_arg_tl
```

(End definition for `\l_siunitx_number_arg_tl`.)

```
\l_siunitx_number_comparator_tl
```

A comparator, if found, is held here.

```
70 \tl_new:N \l_siunitx_number_comparator_tl
```

(End definition for `\l_siunitx_number_comparator_tl`.)

\l_siunitx_number_exponent_tl The exponent part of a parsed number. It is easiest to find this relatively early in the parsing process, but as it needs to go at the end of the internal format is held separately until required.

71 \tl_new:N \l_siunitx_number_exponent_tl

(*End definition for \l_siunitx_number_exponent_tl.*)

\l_siunitx_number_flex_tl In a number with an uncertainty, the exact meaning of a second part is not fully resolved until parsing is complete. That is handled using this “flexible” store.

72 \tl_new:N \l_siunitx_number_flex_tl

(*End definition for \l_siunitx_number_flex_tl.*)

\l_siunitx_number_parsed_tl The number parsed into internal format.

73 \tl_new:N \l_siunitx_number_parsed_tl

(*End definition for \l_siunitx_number_parsed_tl.*)

\l_siunitx_number_input_tl The numerical input exactly as given by the user.

74 \tl_new:N \l_siunitx_number_input_tl

(*End definition for \l_siunitx_number_input_tl.*)

\l_siunitx_number_partial_tl To avoid needing to worry about the fact that the final data stores are somewhat tricky to add to token-by-token, a simple store is used to build up the parsed part of a number before transferring in one go.

75 \tl_new:N \l_siunitx_number_partial_tl

(*End definition for \l_siunitx_number_partial_tl.*)

\l_siunitx_number_validate_bool Used to set up for validation with no error production.

76 \bool_new:N \l_siunitx_number_validate_bool

(*End definition for \l_siunitx_number_validate_bool.*)

\siunitx_number_normalize_symbols:N
_\siunitx_number_normalize_aux:N
_\siunitx_number_normalize_sign:N
\c_siunitx_number_normalize_tl

There are two parts to the replacement code. First, any active hyphens signs are normalised: these can come up with some packages and cause issues. Multi-token signs then are converted to the single token equivalents so that everything else can work on a one token basis.

```

77 \cs_new_protected:Npn \siunitx_number_normalize_symbols:N #1
  {
    \_\siunitx_number_normalize_minus:N #1
    \exp_after:wN \_\siunitx_number_normalize_aux:NnN \exp_after:wN #1
    \c\_siunitx_number_normalize_tl
    { ? } \q_recursion_tail
    \q_recursion_stop
  }
78 \cs_set_protected:Npn \_\siunitx_number_normalize_aux:NnN #1#2#3
  {
    \quark_if_recursion_tail_stop:N #3
    \tl_replace_all:Nnn #1 {#2} {#3}
    \_\siunitx_number_normalize_aux:NnN #1
  }
79 \tl_const:Nn \c\_siunitx_number_normalize_tl
```

```

92     {
93     { -+ } \mp
94     { +- } \pm
95     { << } \ll
96     { <= } \le
97     { >> } \gg
98     { >= } \ge
99   }
100 \group_begin:
101   \char_set_catcode_active:N \-
102   \cs_new_protected:Npx \_siunitx_number_normalize_minus:N #1
103   {
104     \tl_replace_all:Nnn #1
105     { \exp_not:N - } { \token_to_str:N - }
106   }
107 \group_end:

```

(End definition for `\siunitx_number_normalize_symbols:N` and others. This function is documented on page 40.)

```
\siunitx_number_parse:nN
\siunitx_number_parse:VN
\_siunitx_number_parse:nN
```

After some initial set up, the parser expands the input and then replaces as far as possible tricky tokens with ones that can be handled using delimited arguments. To avoid multiple conditionals here, the parser is set up as a chain of commands initially, with a loop only later. This avoids more conditionals than are necessary.

```

108 \cs_new_protected:Npn \siunitx_number_parse:nN #1#2
109   {
110     \bool_if:NTF \l_siunitx_number_parse_bool
111     { \_siunitx_number_parse:nN {#1} #2 }
112     { \tl_clear:N #2 }
113   }
114 \cs_generate_variant:Nn \siunitx_number_parse:nN { V }
115 \cs_new_protected:Npn \_siunitx_number_parse:nN #1#2
116   {
117     \group_begin:
118     \tl_clear:N \l__siunitx_number_parsed_tl
119     \protected@edef \l__siunitx_number_arg_tl
120     {
121       \bool_if:NTF \l__siunitx_number_expression_bool
122       { \fp_eval:n { \_siunitx_number_expression:n {#1} } }
123       {#1}
124     }
125     \tl_set_eq:NN \l__siunitx_number_input_tl \l__siunitx_number_arg_tl
126     \siunitx_number_normalize_symbols:N \l__siunitx_number_arg_tl
127     \tl_if_empty:NF \l__siunitx_number_arg_tl
128     { \_siunitx_number_parse_comparator: }
129     \_siunitx_number_parse_check:
130     \exp_args:NNNV \group_end:
131     \tl_set:Nn #2 \l__siunitx_number_parsed_tl
132   }
```

(End definition for `\siunitx_number_parse:nN` and `_siunitx_number_parse:nN`. This function is documented on page 38.)

```
\_siunitx_number_parse_check:
```

After the loop there is one case that might need tidying up. If a separated uncertainty was found it will be currently in `\l__siunitx_number_flex_tl` and needs moving. A

series of tests pick up that case, then the check is made that some content was found

```

133 \cs_new_protected:Npn \__siunitx_number_parse_check:
134   {
135     \tl_if_empty:NF \l__siunitx_number_flex_tl
136     {
137       \bool_lazy_and:nNTF
138         {
139           \tl_if_blank_p:f
140             { \exp_after:wN \use_iv:nnnn \l__siunitx_number_parsed_tl }
141         }
142         {
143           \tl_if_blank_p:f
144             { \exp_after:wN \use_iv:nnnn \l__siunitx_number_flex_tl }
145         }
146         {
147           \tl_set:Nx \l__siunitx_number_tmp_tl
148             { \exp_after:wN \use_i:nnnn \l__siunitx_number_flex_tl }
149           \tl_if_in:NVT \l__siunitx_number_input_uncert_sign_tl
150             \l__siunitx_number_tmp_tl
151               { \__siunitx_number_parse_combine_uncert: }
152               { \tl_clear:N \l__siunitx_number_parsed_tl }
153         }
154         { \tl_clear:N \l__siunitx_number_parsed_tl }
155     }
156   \tl_if_empty:NTF \l__siunitx_number_parsed_tl
157   {
158     \bool_if:NF \l__siunitx_number_validate_bool
159     {
160       \msg_error:nnx { siunitx } { invalid-number }
161       { \exp_not:V \l__siunitx_number_input_tl }
162     }
163   }
164   { \__siunitx_number_parse_finalise: }
165 }
```

(End definition for `__siunitx_number_parse_check`.)

Conversion of a second numerical part to an uncertainty needs a bit of work. The first step is to extract the useful information from the two stores: the sign, integer and decimal parts from the real number and the integer and decimal parts from the second number. That is done using the input stack to avoid lots of assignments.

```

166 \cs_new_protected:Npn \__siunitx_number_parse_combine_uncert:
167   {
168     \exp_after:wN \exp_after:wN \exp_after:wN
169     \__siunitx_number_parse_combine_uncert_auxi:nnnnnnnn
170       \exp_after:wN \l__siunitx_number_parsed_tl \l__siunitx_number_flex_tl
171   }
```

Here, #4, #5 and #8 are all junk arguments simply there to mop up tokens, while #1 will be recovered later from `\l__siunitx_number_parsed_tl` so does not need to be passed about. The difference in places between the two decimal parts is now found: this is done just once to avoid having to parse token lists twice. The value is then used to generate a number of filler 0 tokens, and these are added to the appropriate part of the number.

Finally, everything is recombined: the integer part only needs a test to avoid an empty main number.

```

172 \cs_new_protected:Npn
173   \_siunitx_number_parse_combine_uncert_auxi:nnnnnnnn #1#2#3#4#5#6#7#8
174 {
175   \int_compare:nNnTF { \tl_count:n {#6} } > { \tl_count:n {#2} }
176   {
177     \tl_clear:N \l__siunitx_number_parsed_tl
178     \tl_clear:N \l__siunitx_number_flex_tl
179   }
180   {
181     \_siunitx_number_parse_combine_uncert_auxii:fnnnn
182     { \int_eval:n { \tl_count:n {#3} - \tl_count:n {#7} } }
183     {#2} {#3} {#6} {#7}
184   }
185 }
186 \cs_new_protected:Npn
187   \_siunitx_number_parse_combine_uncert_auxii:nnnn #1
188 {
189   \_siunitx_number_parse_combine_uncert_auxiii:fnnnnn
190   { \prg_replicate:nn { \int_abs:n {#1} } { 0 } }
191   {#1}
192 }
193 \cs_generate_variant:Nn \_siunitx_number_parse_combine_uncert_auxii:nnnnn { f }
194 \cs_new_protected:Npn
195   \_siunitx_number_parse_combine_uncert_auxiii:nnnnnn #1#2#3#4#5#6
196 {
197   \int_compare:nNnTF {#2} > 0
198   {
199     \_siunitx_number_parse_combine_uncert_auxiv:nnnn
200     {#3} {#4} {#5} {#6} {#1}
201   }
202   {
203     \_siunitx_number_parse_combine_uncert_auxiv:nnnn
204     {#3} {#4} {#1} {#5} {#6}
205   }
206 }
207 \cs_generate_variant:Nn
208   \_siunitx_number_parse_combine_uncert_auxiii:nnnnnn { f }
209 \cs_new_protected:Npn
210   \_siunitx_number_parse_combine_uncert_auxiv:nnnn #1#2#3#4
211 {
212   \tl_set:Nx \l__siunitx_number_parsed_tl
213   {
214     { \tl_head:V \l__siunitx_number_parsed_tl }
215     { \exp_not:n {#1} }
216     {
217       \bool_lazy_and:nnTF
218         { \tl_if_blank_p:n {#2} }
219         { ! \tl_if_blank_p:n {#4} }
220         { 0 }
221         { \exp_not:n {#2} }
222     }
223   }

```

```

224     \_siunitx_number_parse_combine_uncert_auxv:w #3#4
225         \q_recursion_tail \q_recursion_stop
226     }
227 }
228 }
```

A short routine to remove any leading zeros in the uncertainty part, which are not needed for the compact representation used by the module.

```

229 \cs_new:Npn \_siunitx_number_parse_combine_uncert_auxv:w #1
230 {
231     \quark_if_recursion_tail_stop_do:Nn #1
232     {
233         \bool_if:NT \l_siunitx_number_zero_uncert_bool
234             { { S } { 0 } }
235     }
236     \str_if_eq:nnTF {#1} { 0 }
237         { \_siunitx_number_parse_combine_uncert_auxv:w }
238         { \_siunitx_number_parse_combine_uncert_auxvi:w #1 }
239 }
240 \cs_new:Npn \_siunitx_number_parse_combine_uncert_auxvi:w
241     #1 \q_recursion_tail \q_recursion_stop
242     { { S } { \exp_not:n {#1} } }
```

(End definition for `_siunitx_number_parse_combine_uncert:` and others.)

A comparator has to be the very first token in the input. A such, the test for this can be very fast: grab the first token, do a check and if appropriate store the result.

```

243 \cs_new_protected:Npn \_siunitx_number_parse_comparator:
244 {
245     \exp_after:wN \_siunitx_number_parse_comparator_aux:Nw
246     \l_siunitx_number_arg_tl \q_stop
247 }
248 \cs_new_protected:Npn \_siunitx_number_parse_comparator_aux:Nw #1#2 \q_stop
249 {
250     \tl_if_in:NnTF \l_siunitx_number_input_comparator_tl {#1}
251     {
252         \tl_set:Nn \l_siunitx_number_comparator_tl {#1}
253         \tl_set:Nn \l_siunitx_number_arg_tl {#2}
254     }
255     { \tl_clear:N \l_siunitx_number_comparator_tl }
256     \tl_if_empty:NF \l_siunitx_number_arg_tl
257     { \_siunitx_number_parse_sign: }
258 }
```

(End definition for `_siunitx_number_parse_comparator:` and `_siunitx_number_parse_comparator_aux:Nw`.)

An exponent part of a number has to come at the end and can only occur once. Thus it is relatively easy to parse. First, there is a check that an exponent part is allowed, and if so a split is made (the previous part of the chain checks that there is some content in `\l_siunitx_number_arg_tl` before calling this function). After splitting, if there is no exponent then simply save a default. Otherwise, check for a sign and then store either this or an implicit plus, and the digits after a check that nothing else is present after the `e`. The only slight complication to all of this is allowing an arbitrary token in the input to represent the exponent: this is done by setting any exponent tokens to the first

```

\_siunitx_number_parse_exponent:
\_siunitx_number_parse_exponent_auxi:nn
\_siunitx_number_parse_exponent_auxii:Nw
\_siunitx_number_parse_exponent_auxiii:Nw
\_siunitx_number_parse_exponent_auxiv:nn
\_siunitx_number_parse_exponent_zero_test:N
\_siunitx_number_parse_exponent_check:N
\_siunitx_number_parse_exponent_cleanup:N
```

of the allowed list, then using that in a delimited argument set up. Once an exponent part is found, there is a loop to check that each of the tokens is a digit then a tidy up step to remove any leading zeros.

```

259 \cs_new_protected:Npn \_siunitx_number_parse_exponent:
260   {
261     \tl_if_empty:NTF \l_siunitx_number_input_exponent_tl
262     {
263       \tl_set:Nn \l_siunitx_number_exponent_tl { { } 0 }
264       \tl_if_empty:NF \l_siunitx_number_parsed_tl
265       { \_siunitx_number_parse_loop: }
266     }
267   {
268     \tl_set:Nx \l_siunitx_number_tmp_tl
269     { \tl_head:V \l_siunitx_number_input_exponent_tl }
270     \tl_map_inline:Nn \l_siunitx_number_input_exponent_tl
271     {
272       \tl_replace_all:NnV \l_siunitx_number_arg_tl
273       {##1} \l_siunitx_number_tmp_tl
274     }
275     \use:x
276     {
277       \cs_set_protected:Npn
278         \exp_not:N \_siunitx_number_parse_exponent_auxi:w
279         #####1 \exp_not:V \l_siunitx_number_tmp_tl
280         #####2 \exp_not:V \l_siunitx_number_tmp_tl
281         #####3 \exp_not:N \q_stop
282     }
283     { \_siunitx_number_parse_exponent_auxii:nn {##1} {##2} }
284     \use:x
285     {
286       \_siunitx_number_parse_exponent_auxi:w
287         \exp_not:V \l_siunitx_number_arg_tl
288         \exp_not:V \l_siunitx_number_tmp_tl \exp_not:N \q_nil
289         \exp_not:V \l_siunitx_number_tmp_tl \exp_not:N \q_stop
290     }
291   }
292 }
293 \cs_new_protected:Npn \_siunitx_number_parse_exponent_auxi:w { }
294 \cs_new_protected:Npn \_siunitx_number_parse_exponent_auxii:nn #1#2
295   {
296     \quark_if_nil:nTF {#2}
297     { \tl_set:Nn \l_siunitx_number_exponent_tl { { } 0 } }
298     {
299       \tl_set:Nn \l_siunitx_number_arg_tl {#1}
300       \tl_if_blank:nTF {#2}
301         { \tl_clear:N \l_siunitx_number_parsed_tl }
302         { \_siunitx_number_parse_exponent_auxiii:Nw #2 \q_stop }
303     }
304     \tl_if_empty:NF \l_siunitx_number_parsed_tl
305     { \_siunitx_number_parse_loop: }
306   }
307 \cs_new_protected:Npn \_siunitx_number_parse_exponent_auxiii:Nw #1#2 \q_stop
308   {
309     \tl_if_in:NnTF \l_siunitx_number_input_sign_tl {#1}

```

```

310      { \_siunitx_number_parse_exponent_auxiv:nn {#1} {#2} }
311      { \_siunitx_number_parse_exponent_auxiv:nn { } {#1#2} }
312      \tl_if_empty:NT \l_siunitx_number_exponent_tl
313      { \tl_clear:N \l_siunitx_number_parsed_tl }
314  }
315 \cs_new_protected:Npn \_siunitx_number_parse_exponent_auxiv:nn #1#2
316  {
317      \bool_lazy_or:nnTF
318      { \l_siunitx_number_explicit_plus_bool }
319      { ! \str_if_eq_p:nn {#1} {+} }
320      { \tl_set:Nn \l_siunitx_number_exponent_tl {#1} }
321      { \tl_set:Nn \l_siunitx_number_exponent_tl { } }
322      \tl_if_blank:nTF {#2}
323      { \tl_clear:N \l_siunitx_number_parsed_tl }
324      {
325          \_siunitx_number_parse_exponent_zero_test:N #2
326          \q_recursion_tail \q_recursion_stop
327      }
328  }
329 \cs_new_protected:Npn \_siunitx_number_parse_exponent_zero_test:N #1
330  {
331      \quark_if_recursion_tail_stop_do:Nn #1
332      { \tl_set:Nn \l_siunitx_number_exponent_tl { } 0 }
333      \str_if_eq:nnTF {#1} {0}
334      { \_siunitx_number_parse_exponent_zero_test:N }
335      { \_siunitx_number_parse_exponent_check:N #1 }
336  }
337 \cs_new_protected:Npn \_siunitx_number_parse_exponent_check:N #1
338  {
339      \quark_if_recursion_tail_stop:N #1
340      \tl_if_in:NnTF \l_siunitx_number_input_digit_tl {#1}
341      {
342          \tl_put_right:Nn \l_siunitx_number_exponent_tl {#1}
343          \_siunitx_number_parse_exponent_check:N
344      }
345      { \_siunitx_number_parse_exponent_cleanup:wN }
346  }
347 \cs_new_protected:Npn \_siunitx_number_parse_exponent_cleanup:wN
348 #1 \q_recursion_stop
349 { \tl_clear:N \l_siunitx_number_parsed_tl }

```

(End definition for `_siunitx_number_parse_exponent:` and others.)

`_siunitx_number_parse_finalise:` Combine all of the bits of a number together: both the real and imaginary parts contain all of the data.

```

350 \cs_new_protected:Npn \_siunitx_number_parse_finalise:
351  {
352      \tl_if_empty:NF \l_siunitx_number_parsed_tl
353      {
354          \tl_set:Nx \l_siunitx_number_parsed_tl
355          {
356              { \exp_not:V \l_siunitx_number_comparator_tl }
357              \exp_not:V \l_siunitx_number_parsed_tl
358              \exp_after:wN \_siunitx_number_parse_finalise:nw

```

```

359             \l_siunitx_number_exponent_tl \q_stop
360         }
361     }
362 }
363 \cs_new:Npn \_siunitx_number_parse_finalise:nw #1#2 \q_stop
364 {
365     { \exp_not:n {#1} }
366     { \exp_not:n {#2} }
367 }

```

(End definition for `_siunitx_number_parse_finalise:` and `_siunitx_number_parse_finalise:nw`.)

```

\_siunitx_number_parse_loop:
\_siunitx_number_parse_loop_first:N
\_siunitx_number_parse_loop_main:NNNNN
\_siunitx_number_parse_loop_main_end>NN
\_siunitx_number_parse_loop_main_digit:NNNNN
\_siunitx_number_parse_loop_main_decimal:NN
\_siunitx_number_parse_loop_main_uncert:NNN
\_siunitx_number_parse_loop_main_sign:NNN
\_siunitx_number_parse_loop_main_store:NNN
siunitx_number_parse_loop_after_decimal:NNN
\_siunitx_number_parse_loop_root_swap:NwNNN
    \_siunitx_number_parse_loop_break:wN

```

At this stage, the partial input `\l_siunitx_number_arg_tl` will contain any mantissa, which may contain an uncertainty or complex part. Parsing this and allowing for all of the different formats possible is best done using a token-by-token approach. However, as at each stage only a subset of tokens are valid, the approach take is to use a set of semi-dedicated functions to parse different components along with switches to allow a sensible amount of code sharing.

```

368 \cs_new_protected:Npn \_siunitx_number_parse_loop:
369 {
370     \tl_clear:N \l_siunitx_number_partial_tl
371     \exp_after:wN \_siunitx_number_parse_loop_first:NNN
372     \exp_after:wN \l_siunitx_number_parsed_tl \exp_after:wN \c_true_bool
373     \l_siunitx_number_arg_tl
374     \q_recursion_tail \q_recursion_stop
375 }

```

The very first token of the input is handled with a dedicated function. Valid cases here are

- Entirely blank if the original input was for example `+e10`: simply clean up if in the integer part of issue an error if in a second part (complex number, *etc.*).
- An integer part digit: pass through to the main collection routine.
- A decimal marker: store an empty integer part and move to the main collection routine for a decimal part.

Anything else is invalid and sends the code to the abort function.

```

376 \cs_new_protected:Npn \_siunitx_number_parse_loop_first:NNN #1#2#3
377 {
378     \quark_if_recursion_tail_stop_do:Nn #3
379     {
380         \bool_if:NTF #2
381             { \tl_put_right:Nn #1 { { 1 } { } { } } }
382             { \_siunitx_number_parse_loop_break:wN \q_recursion_stop }
383     }
384     \tl_if_in:NnTF \l_siunitx_number_input_digit_tl {#3}
385     {
386         \_siunitx_number_parse_loop_main:NNNNN
387         #1 \c_true_bool \c_false_bool #2 #3
388     }
389     {
390         \tl_if_in:NnTF \l_siunitx_number_input_decimal_tl {#3}
391         {

```

```

392         \tl_put_right:Nn #1 { { 0 } }
393         \_siunitx_number_parse_loop_after_decimal:NNN #1 #2
394     }
395     { \_siunitx_number_parse_loop_break:wN }
396 }
397 }
```

A single function is used to cover the “main” part of numbers: finding real, complex or separated uncertainty parts and covering both the integer and decimal components. This works because these elements share a lot of concepts: a small number of switches can be used to differentiate between them. To keep the code at least somewhat readable, this main function deals with the validity testing but hands off other tasks to dedicated auxiliaries for each case.

The possibilities are

- The number terminates, meaning that some digits were collected and everything is simply tidied up (as far as the loop is concerned).
- A digit is found: this is the common case and leads to a storage auxiliary (which handles non-significant zeros).
- A decimal marker is found: only valid in the integer part and there leading to a store-and-switch situation.
- An open-uncertainty token: switch to the dedicated collector for uncertainties.
- A sign token (if allowed): stop collecting this number and restart collection for the second part.

```

398 \cs_new_protected:Npn \_siunitx_number_parse_loop_main:NNNNN #1#2#3#4#5
399 {
400     \quark_if_recursion_tail_stop_do:Nn #5
401     { \_siunitx_number_parse_loop_main_end:NN #1#2 }
402     \tl_if_in:NnTF \l_siunitx_number_input_digit_tl {\#5}
403     { \_siunitx_number_parse_loop_main_digit:NNNNN #1#2#3#4#5 }
404     {
405         \tl_if_in:NnTF \l_siunitx_number_input_decimal_tl {\#5}
406         {
407             \bool_if:NTF #2
408             { \_siunitx_number_parse_loop_main_decimal:NN #1 #4 }
409             { \_siunitx_number_parse_loop_break:wN }
410         }
411         {
412             \tl_if_in:NnTF \l_siunitx_number_input_uncert_open_tl {\#5}
413             { \_siunitx_number_parse_loop_main_uncert:NNN #1#2 #4 }
414             {
415                 \bool_if:NTF #4
416                 {
417                     \tl_if_in:NnTF \l_siunitx_number_input_sign_tl {\#5}
418                     {
419                         \_siunitx_number_parse_loop_main_sign:NNN
420                         #1#2 #5
421                     }
422                     { \_siunitx_number_parse_loop_break:wN }
423                 }

```

```

424             { \_siunitx_number_parse_loop_break:wN }
425         }
426     }
427 }
428 }
```

If the main loop finds the end marker then there is a tidy up phase. The current partial number is stored either as the integer or decimal, depending on the setting for the indicator switch. For the integer part, if no number has been collected then one or more non-significant zeros have been dropped. Exactly one zero is therefore needed to make sure the parsed result is correct.

```

429 \cs_new_protected:Npn \_siunitx_number_parse_loop_main_end:NN #1#2
430 {
431     \bool_lazy_and:nnT
432     {#2} { \tl_if_empty_p:N \l_siunitx_number_partial_tl }
433     { \tl_set:Nn \l_siunitx_number_partial_tl { 0 } }
434     \tl_put_right:Nx #1
435     {
436         { \exp_not:V \l_siunitx_number_partial_tl }
437         \bool_if:NT #2 { { } }
438     }
439 }
440 }
```

The most common case for the main loop collector is to find a digit. Here, in the integer part it is possible that zeros are non-significant: that is handled using a combination of a switch and a string test. Other than that, the situation here is simple: store the input and loop.

```

441 \cs_new_protected:Npn \_siunitx_number_parse_loop_main_digit:NNNNN #1#2#3#4#5
442 {
443     \bool_lazy_or:nnTF
444     {#3} { ! \str_if_eq_p:nn {#5} { 0 } }
445     {
446         \tl_put_right:Nn \l_siunitx_number_partial_tl {#5}
447         \_siunitx_number_parse_loop_main:NNNNN #1 #2 \c_true_bool #4
448     }
449     { \_siunitx_number_parse_loop_main:NNNNN #1 #2 \c_false_bool #4 }
450 }
```

When a decimal marker was found, move the integer part to the store and then go back to the loop with the flags set correctly. There is the case of non-significant zeros to cover before that, of course.

```

451 \cs_new_protected:Npn \_siunitx_number_parse_loop_main_decimal:NN #1#2
452 {
453     \_siunitx_number_parse_loop_main_store:NNN #1 \c_false_bool \c_false_bool
454     \_siunitx_number_parse_loop_after_decimal:NNN #1 #2
455 }
```

Starting an uncertainty part means storing the number to date as in other cases, with the possibility of a blank decimal part allowed for. The uncertainty itself is collected by a dedicated function as it is extremely restricted.

```

456 \cs_new_protected:Npn \_siunitx_number_parse_loop_main_uncert:NNN #1#2#3
457 {
458     \_siunitx_number_parse_loop_main_store:NNN #1 #2 \c_false_bool
```

```

459     \_siunitx_number_parse_uncert:NN #1
460 }

```

If a sign is found, terminate the current number, store the sign as the first token of the second part and go back to do the dedicated first-token function.

```

461 \cs_new_protected:Npn \_siunitx_number_parse_loop_main_sign:NNN #1#2#3
462 {
463     \_siunitx_number_parse_loop_main_store:NNN #1 #2 \c_true_bool
464     \tl_set:Nn \l_siunitx_number_flex_tl { #3 }
465     \_siunitx_number_parse_loop_first:NNN
466     \l_siunitx_number_flex_tl \c_false_bool
467 }

```

A common auxiliary for the various non-digit token functions: tidy up the integer and decimal parts of a number. Here, the two flags are used to indicate if empty decimal and uncertainty parts should be included in the storage cycle.

```

468 \cs_new_protected:Npn \_siunitx_number_parse_loop_main_store:NNN #1#2#3
469 {
470     \tl_if_empty:NT \l_siunitx_number_partial_tl
471     { \tl_set:Nn \l_siunitx_number_partial_tl { 0 } }
472     \tl_put_right:Nx #1
473     {
474         { \exp_not:V \l_siunitx_number_partial_tl }
475         \bool_if:NT #2 { { } }
476         \bool_if:NT #3 { { } }
477     }
478     \tl_clear:N \l_siunitx_number_partial_tl
479 }

```

After a decimal marker there has to be a digit if there wasn't one before it. That is handled by using a dedicated function, which checks for an empty integer part first then either simply hands off or looks for a digit.

```

480 \cs_new_protected:Npn \_siunitx_number_parse_loop_after_decimal:NNN #1#2#3
481 {
482     \tl_if_blank:fTF { \exp_after:wN \use_none:n #1 }
483     {
484         \quark_if_recursion_tail_stop_do:Nn #3
485         { \_siunitx_number_parse_loop_break:wN \q_recursion_stop }
486         \tl_if_in:NnTF \l_siunitx_number_input_digit_tl {#1}
487         {
488             \tl_put_right:Nn \l_siunitx_number_partial_tl {#3}
489             \_siunitx_number_parse_loop_main:NNNNN
490             #1 \c_false_bool \c_true_bool #2
491         }
492         { \_siunitx_number_parse_loop_break:wN }
493     }
494     {
495         \_siunitx_number_parse_loop_main:NNNNN
496         #1 \c_false_bool \c_true_bool #2 #3
497     }
498 }

```

Something is not right: remove all of the remaining tokens from the number and clear the storage areas as a signal for the next part of the code.

```

499 \cs_new_protected:Npn \_siunitx_number_parse_loop_break:wN

```

```

500 #1 \q_recursion_stop
501 {
502   \tl_clear:N \l_siunitx_number_flex_tl
503   \tl_clear:N \l_siunitx_number_parsed_tl
504 }

```

(End definition for `_siunitx_number_parse_loop`: and others.)

`_siunitx_number_parse_sign:`
`_siunitx_number_parse_sign_aux:Nw`

The first token of a number after a comparator could be a sign. A quick check is made and if found stored. For the number to be valid it has to be more than just a sign, so the next part of the chain is only called if that is the case.

```

505 \cs_new_protected:Npn \_siunitx_number_parse_sign:
506 {
507   \exp_after:wN \_siunitx_number_parse_sign_aux:Nw
508   \l_siunitx_number_arg_tl \q_stop
509 }
510 \cs_new_protected:Npn \_siunitx_number_parse_sign_aux:Nw #1#2 \q_stop
511 {
512   \tl_if_in:NnTF \l_siunitx_number_input_sign_tl {#1}
513   {
514     \tl_set:Nn \l_siunitx_number_arg_tl {#2}
515     \bool_lazy_and:nntF
516     { \token_if_eq_charcode_p:NN #1 + }
517     { ! \l_siunitx_number_explicit_plus_bool }
518     { \tl_set:Nn \l_siunitx_number_parsed_tl { { } } }
519     { \tl_set:Nn \l_siunitx_number_parsed_tl { {#1} } }
520   }
521   { \tl_set:Nn \l_siunitx_number_parsed_tl { { } } }
522   \tl_if_empty:NTF \l_siunitx_number_arg_tl
523   {
524     \tl_clear:N \l_siunitx_number_parsed_tl
525     { \_siunitx_number_parse_exponent: }
526   }

```

(End definition for `_siunitx_number_parse_sign`: and `_siunitx_number_parse_sign_aux:Nw`.)

`_siunitx_number_parse_uncert:NN`
`_siunitx_number_parse_uncert>NNNN`
`_siunitx_number_parse_uncert_auxi:NN`
`_siunitx_number_parse_uncert_auxii:NN`
`_siunitx_number_parse_uncert_auxiii:N`
`_siunitx_number_parse_uncert_marker:N`
`_siunitx_number_parse_uncert_after:N`

Parsing a combined uncertainty has a very restricted range of allowed tokens. A closing uncertainty token in the first place is an error, so we filter that out explicitly. After that, we check for digits, which require checking for significant digits. The non-digit function is separate to make the flow clearer.

```

526 \cs_new_protected:Npn \_siunitx_number_parse_uncert:NN #1#2
527 {
528   \quark_if_recursion_tail_stop_do:Nn #2
529   { \_siunitx_number_parse_loop_break:wN \q_recursion_stop }
530   \tl_if_in:NnTF \l_siunitx_number_input_uncert_close_tl {#2}
531   { \_siunitx_number_parse_loop_break:wN }
532   {
533     \_siunitx_number_parse_uncert:NNNN
534     #1 \c_false_bool \_siunitx_number_parse_uncert_auxi:NN #2
535   }
536 }

```

Deal with digits: a simple question of whether they are significant.

```

537 \cs_new_protected:Npn \_siunitx_number_parse_uncert:NNNN #1#2#3#4
538 {

```

```

539 \quark_if_recursion_tail_stop_do:Nn #4
540   { \_siunitx_number_parse_loop_break:wN \q_recursion_stop }
541 \tl_if_in:NnTF \l_siunitx_number_input_digit_tl {#4}
542   {
543     \bool_lazy_or:nnTF
544       {#2} { ! \str_if_eq_p:nn {#4} { 0 } }
545     {
546       \tl_put_right:Nn \l_siunitx_number_partial_tl {#4}
547       \_siunitx_number_parse_uncert:NNNN #1 \c_true_bool #3
548     }
549     { \_siunitx_number_parse_uncert:NNNN #1 \c_false_bool #3 }
550   }
551   { #3 #1#4 }
552 }

```

For the two auxiliaries, the difference is the handling of a decimal marker: one may be present, but only exactly one.

```

553 \cs_new_protected:Npn \_siunitx_number_parse_uncert_auxi:NN #1#2
554   {
555     \tl_if_in:NnTF \l_siunitx_number_input_uncert_close_tl {#2}
556     {
557       \_siunitx_number_parse_uncert_auxiii:N #1
558       \_siunitx_number_parse_uncert_after:N
559     }
560     {
561       \tl_if_in:NnTF \l_siunitx_number_input_decimal_tl {#2}
562         { \_siunitx_number_parse_uncert_marker:N #1 }
563         { \_siunitx_number_parse_loop_break:wN }
564     }
565   }
566 \cs_new_protected:Npn \_siunitx_number_parse_uncert_auxii:NN #1#2
567   {
568     \tl_if_in:NnTF \l_siunitx_number_input_uncert_close_tl {#2}
569     {
570       \_siunitx_number_parse_uncert_auxiii:N #1
571       \_siunitx_number_parse_uncert_after:N
572     }
573     { \_siunitx_number_parse_loop_break:wN }
574   }

```

Deal with the closing bracket, which might leave us with nothing if there were no significant digits.

```

575 \cs_new_protected:Npn \_siunitx_number_parse_uncert_auxiii:N #1
576   {
577     \tl_if_empty:NTF \l_siunitx_number_partial_tl
578     {
579       \tl_put_right:Nx #1
580       {
581         \bool_if:NT \l_siunitx_number_zero_uncert_bool
582           { { S } { 0 } }
583         }
584       }
585     }
586   {

```

```

588     \tl_set:Nx \l_siunitx_number_partial_tl
589     { { S } { \exp_not:V \l_siunitx_number_partial_tl } }
590     \_siunitx_number_parse_loop_main_store:NNN #1
591     \c_false_bool \c_false_bool
592   }
593 }

```

Handling a decimal marker in the uncertainty is a bit tricky: we need to make sure it's valid. First, we need to be sure that the integer part of the captured uncertainty is not too long. Then we need to check that the decimal part is not too long. Both of these require data from the collected partial number, so we extract that first. Checking the decimal part needs the length of the not-yet-collected uncertainty. Handily, we know that it should be a set of digits then a closing marker. So we can use that as a length: if it's too long we can stop.

```

594 \cs_new_protected:Npn \_siunitx_number_parse_uncert_marker:N #1
595   { \exp_after:wN \_siunitx_number_parse_uncert_marker:nnN #1 #1 }
596 \cs_new_protected:Npn \_siunitx_number_parse_uncert_marker:nnN #1#2#3#4
597   {
598     \int_compare:nNnTF
599     { \tl_count:N \l_siunitx_number_partial_tl } > { \tl_count:n {#2} }
600     { \_siunitx_number_parse_loop_break:wN }
601     { \_siunitx_number_parse_uncert_marker:nNw {#3} #4 }
602   }
603 \cs_new_protected:Npn \_siunitx_number_parse_uncert_marker:nNw
604   #1#2#3 \q_recursion_tail \q_recursion_stop
605   {
606     \int_compare:nNnTF
607     { \tl_count:n {#3} - 1 } = { \tl_count:n {#1} }
608     {
609       \str_if_eq:eeTF
610       { \exp_not:V \l_siunitx_number_partial_tl }
611       { \prg_replicate:nn { \tl_count:N \l_siunitx_number_partial_tl } { 0 } }
612       {
613         \_siunitx_number_parse_uncert>NNNN
614         #2 \c_false_bool
615       }
616     {
617       \_siunitx_number_parse_uncert>NNNN
618       #2 \c_true_bool
619     }
620     \_siunitx_number_parse_uncert_auxii>NN
621   }
622   { \_siunitx_number_parse_loop_break:wN }
623   #3 \q_recursion_tail \q_recursion_stop
624 }

```

No further tokens are allowed after an uncertainty in parenthesis.

```

625 \cs_new_protected:Npn \_siunitx_number_parse_uncert_after:N #1
626   {
627     \quark_if_recursion_tail_stop:N #1
628     \_siunitx_number_parse_loop_break:wN
629   }

```

(End definition for `_siunitx_number_parse_uncert>NN` and others.)

2.4 Processing numbers

```

\l_siunitx_number_drop_exponent_bool
\l_siunitx_number_drop_uncertainty_bool
\l_siunitx_number_drop_zero_decimal_bool
\l_siunitx_number_exponent_mode_tl
\l_siunitx_number_exponent_fixed_int
\l_siunitx_number_min_decimal_int
\l_siunitx_number_min_integer_int
\l_siunitx_number_round_half_even_bool
\l_siunitx_number_round_mode_tl
\l_siunitx_number_round_pad_bool
\l_siunitx_number_round_precision_int

630 \keys_define:nn { siunitx }
631 {
632   drop-exponent .bool_set:N =
633     \l_siunitx_number_drop_exponent_bool ,
634   drop-uncertainty .bool_set:N =
635     \l_siunitx_number_drop_uncertainty_bool ,
636   drop-zero-decimal .bool_set:N =
637     \l_siunitx_number_drop_zero_decimal_bool ,
638   exponent-mode .choices:nn =
639     { engineering , fixed , input , scientific }
640     { \tl_set_eq:NN \l_siunitx_number_exponent_mode_tl \l_keys_choice_tl } ,
641   fixed-exponent .int_set:N =
642     \l_siunitx_number_exponent_fixed_int ,
643   minimum-decimal-digits .int_set:N =
644     \l_siunitx_number_min_decimal_int ,
645   minimum-integer-digits .int_set:N =
646     \l_siunitx_number_min_integer_int ,
647   round-half .choice: ,
648   round-half / even .code:n =
649     { \bool_set_true:N \l_siunitx_number_round_half_even_bool } ,
650   round-half / up .code:n =
651     { \bool_set_false:N \l_siunitx_number_round_half_even_bool } ,
652   round-minimum .code:n =
653     { \l_siunitx_number_set_round_min:n {#1} } ,
654   round-mode .choices:nn =
655     { figures , none , places , uncertainty }
656     { \tl_set_eq:NN \l_siunitx_number_round_mode_tl \l_keys_choice_tl } ,
657   round-pad .bool_set:N =
658     \l_siunitx_number_round_pad_bool ,
659   round-precision .int_set:N =
660     \l_siunitx_number_round_precision_int ,
661 }

662 \bool_new:N \l_siunitx_number_round_half_even_bool
663 \tl_new:N \l_siunitx_number_exponent_mode_tl
664 \tl_new:N \l_siunitx_number_round_mode_tl

(End definition for \l_siunitx_number_drop_exponent_bool and others.)

```

\l_siunitx_number_round_min_tl

For storing the minimum for rounding.

```
665 \tl_new:N \l_siunitx_number_round_min_tl
```

(End definition for \l_siunitx_number_round_min_tl.)

\l_siunitx_number_set_round_min:n
\l_siunitx_number_set_round_min:nnnnnnn

For setting the rounding minimum, the aim is to do as much of the work now as possible. That's mainly a question of checking if there are any significant digits in the mantissa given.

```

666 \cs_new_protected:Npn \l_siunitx_number_set_round_min:n #1
667 {
668   \siunitx_number_parse:nN {#1} \l_siunitx_number_tmp_tl
669   \exp_after:wN \l_siunitx_number_set_round_min:nnnnnnn \l_siunitx_number_tmp_tl
670 }
```

```

671 \cs_new:Npn \__siunitx_number_set_round_min:nnnnnnn #1#2#3#4#5#6#7
672 {
673   \tl_set:Nx \l__siunitx_number_round_min_tl
674   {
675     \bool_lazy_and:nnF
676     { \str_if_eq_p:nn {#3} { 0 } }
677     {
678       \str_if_eq_p:ee
679       { \exp_not:n {#4} }
680       { \prg_replicate:nn { \tl_count:n {#4} } { 0 } }
681     }
682     { \exp_not:n { {#3} {#4} } }
683   }
684 }
```

(End definition for `__siunitx_number_set_round_min:n` and `__siunitx_number_set_round_min:nnnnnnn`.)

`\siunitx_number_process:NN`

A top-level interface for the processing tools. Rounding happens in all cases, but exponents are only processed if the value is not 0.

```

685 \cs_new_protected:Npn \siunitx_number_process:NN #1#2
686 {
687   \tl_if_empty:NTF #1
688   { \tl_clear:N #2 }
689   {
690     \__siunitx_number_drop_uncertainty:NN #1 #2
691     \exp_after:wN \__siunitx_number_process:nnnnnnnNN #2 #2 #2
692     \__siunitx_number_drop_exponent:NN #2 #2
693     \__siunitx_number_zero_decimal:NN #2 #2
694     \__siunitx_number_digits:NN #2 #2
695   }
696 }
697 \cs_new_protected:Npn \__siunitx_number_process:nnnnnnnNN #1#2#3#4#5#6#7#8#9
698 {
699   \bool_lazy_and:nnTF
700   { \str_if_eq_p:nn {#3} { 0 } }
701   {
702     \str_if_eq_p:ee
703     { \exp_not:n {#4} } { \prg_replicate:nn { \tl_count:n {#4} } { 0 } }
704   }
705   { \__siunitx_number_round:NN #8 #9 }
706   {
707     \__siunitx_number_exponent:NN #8 #9
708     \__siunitx_number_round:NN #9 #9
709   }
710 }
```

(End definition for `\siunitx_number_process:NN` and `__siunitx_number_process:nnnnnnnNN`. This function is documented on page 39.)

`__siunitx_number_exponent>NN`

Manipulating an exponent is done using a single expansion function *unless* dealing with engineering-style output. The latter is easier to handle by first converting to scientific output, then post-processing. (Once e-type expansion is generally available, this will be handled using a single `\tl_set:Nx`.)

```
711 \cs_new_protected:Npn \__siunitx_number_exponent:NN #1#2
```

```

712 {
713   \tl_set:Nx #2
714   {
715     \cs:w
716       __siunitx_number_exponent_ \l_siunitx_number_exponent_mode_tl :nnnnnnn
717       \exp_after:wN
718     \cs_end: #1
719   }
720   \str_if_eq:VnT \l_siunitx_number_exponent_mode_tl { engineering }
721   {
722     \tl_set:Nx #2
723     { \exp_after:wN \__siunitx_number_exponent_engineering_aux:nnnnnnn #2 }
724   }
725 }
726 \cs_new:Npn \__siunitx_number_exponent_fixed:nnnnnnn #1#2#3#4#5#6#7
727 {
728   \exp_args:Nf \__siunitx_number_exponent_fixed:nnnnnnnnn
729   { \int_eval:n { \l_siunitx_number_exponent_fixed_int - (#6#7) } }
730   {#1} {#2} {#3} {#4} {#5} {#6} {#7}
731 }
732 \cs_new:Npn \__siunitx_number_exponent_fixed:nnnnnnnnn #1#2#3#4#5#6#7#8
733 {
734   \exp_not:n { {#2} {#3} }
735   \__siunitx_number_exponent_shift:nnn {#1} {#4} {#5}
736   \__siunitx_number_exponent_uncert:n {#6}
737   \exp_not:n { {#7} } { \int_use:N \l_siunitx_number_exponent_fixed_int }
738 }
739 \cs_new:Npn \__siunitx_number_exponent_input:nnnnnnn #1#2#3#4#5#6#7
740   { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#6} {#7} } }

```

To convert to scientific notation, the key question is to find the number of significant places. That is easy enough if the number has a non-zero integer component. For a pure decimal, we have to trim off leading zeros in a loop.

```

741 \cs_new:Npn \__siunitx_number_exponent_scientific:nnnnnnn #1#2#3#4#5#6#7
742 {
743   \exp_args:Nf \__siunitx_number_exponent_scientific:nnnnnnnnn
744   { \int_eval:n { \tl_count:n {#3} } }
745   {#1} {#2} {#3} {#4} {#5} {#6} {#7}
746 }
747 \cs_new:Npn \__siunitx_number_exponent_scientific:nnnnnnnn #1#2#3#4#5#6#7#8
748 {
749   \exp_not:n { {#2} {#3} }
750   \int_compare:nNnTF {#1} = 1
751   {
752     \str_if_eq:nnTF {#4} { 0 }
753     {
754       \__siunitx_number_exponent_scientific:nnnw
755       { 0 } {#6} { #7#8 } #5 \q_stop
756     }
757     { \exp_not:n { {#4} {#5} {#6} {#7} {#8} } }
758   }
759   {
760     \__siunitx_number_exponent_shift:nnn { #1 - 1 } {#4} {#5}
761     \__siunitx_number_exponent_uncert:n {#6}

```

```

762         \_siunitx_number_exponent_finalise:n { #1 + #7#8 - 1 }
763     }
764   }
765 \cs_new_eq:NN \_siunitx_number_exponent_engineering:nnnnnnn
766   \_siunitx_number_exponent_scientific:nnnnnnn
767 \cs_new:Npn \_siunitx_number_exponent_scientific:nnnw #1#2#3#4#5 \q_stop
768   {
769     \str_if_eq:nnTF {#4} { 0 }
770     {
771       \_siunitx_number_exponent_scientific:nnnw
772         { #1 - 1 } {#2} {#3} #5 \q_stop
773     }
774     {
775       \exp_not:n { {#4} {#5} {#2} }
776       \_siunitx_number_exponent_finalise:n { #1 + #3 - 1 }
777     }
778   }

```

When adjusting the exponent position, there are two paths depending on which way the shift takes place.

```

779 \cs_new:Npn \_siunitx_number_exponent_shift:nnn #1#2#3
780   {
781     \int_compare:nNnTF {#1} > 0
782     { \_siunitx_number_exponent_shift_down:nnnw {#1} {#3} { } #2 \q_stop }
783     {
784       \int_compare:nNnTF {#1} < 0
785       { \_siunitx_number_exponent_shift_up:nnn {#1} {#2} {#3} }
786       { {#2} {#3} }
787     }
788   }
789 \cs_generate_variant:Nn \_siunitx_number_exponent_shift:nnn { nnf }

```

For shifting the exponent down, there is first a loop to reserve the integer part before doing the work: that of course has to be undone for any remainder at the end of the process.

```

790 \cs_new:Npn \_siunitx_number_exponent_shift_down:nnnw #1#2#3#4#5 \q_stop
791   {
792     \tl_if_blank:nTF {#5}
793     { \_siunitx_number_exponent_shift_down:nnn {#1} { #4 #3 } {#2} }
794     { \_siunitx_number_exponent_shift_down:nnnw {#1} {#2} { #4 #3 } #5 \q_stop }
795   }
796 \cs_new:Npn \_siunitx_number_exponent_shift_down:nnn #1#2#3
797   {
798     \int_compare:nNnTF {#1} = 0
799     { { \tl_reverse:n {#2} } \exp_not:n { {#3} } }
800     { \_siunitx_number_exponent_shift_down:nw {#1} #2 \q_stop {#3} }
801   }
802 \cs_new:Npn \_siunitx_number_exponent_shift_down:nw #1#2#3 \q_stop #4
803   {
804     \tl_if_blank:nTF {#3}
805     { \_siunitx_number_exponent_shift_down:nnn { #1 - 1 } { 0 } { #2#4 } }
806     { \_siunitx_number_exponent_shift_down:nnn { #1 - 1 } {#3} { #2#4 } }
807   }

```

For shifting the exponent up, we can run out of decimal digits, at which point filling is easy. Other than that a simple loop as we are picking input off the front of the decimal part. We also need to deal with leading zeros: these cannot accumulate.

```

808 \cs_new:Npn \__siunitx_number_exponent_shift_up:nnn #1#2#3
809   {
810     \tl_if_blank:nTF {#3}
811     {
812       \__siunitx_number_exponent_shift_up_aux:ffn
813       { \int_eval:n { #1 + 1 } }
814       { \str_if_eq:nnF {#2} { 0 } {#2} 0 }
815       { }
816       \__siunitx_number_exponent_shift_uncert:nw { 1 }
817     }
818     { \__siunitx_number_exponent_shift_up:nnw {#1} {#2} #3 \q_stop }
819   }
820 \cs_new:Npn \__siunitx_number_exponent_shift_up:nnw #1#2#3#4 \q_stop
821   {
822     \__siunitx_number_exponent_shift_up_aux:ffn
823     { \int_eval:n { #1 + 1 } }
824     { \str_if_eq:nnF {#2} { 0 } {#2} #3 }
825     {#4}
826   }
827 \cs_new:Npn \__siunitx_number_exponent_shift_up_aux:nnn #1#2#3
828   {
829     \int_compare:nNnTF {#1} = 0
830     { \exp_not:n { {#2} {#3} } }
831     {
832       \tl_if_blank:nTF {#3}
833       {
834         {
835           \exp_not:n {#2}
836           \prg_replicate:nn { \int_abs:n {#1} } { 0 }
837         }
838         {
839           \__siunitx_number_exponent_shift_uncert:nw { \int_abs:n {#1} }
840         }
841         { \__siunitx_number_exponent_shift_up:nnn {#1} {#2} {#3} }
842       }
843     }
844 \cs_generate_variant:Nn \__siunitx_number_exponent_shift_up_aux:nnn { f , ff }

If the shift has put digits into the integer part, we have to adjust the uncertainty accordingly. First, we grab the data, then adjust by the number of places that have been transferred.

845 \cs_new:Npn \__siunitx_number_exponent_shift_uncert:nw
846   #1#2 \__siunitx_number_exponent_uncert:n #3
847   {
848     \tl_if_blank:nTF {#3}
849     {
850       #2
851       \__siunitx_number_exponent_uncert:n { }
852     }
853     {
854       \str_if_eq:nnTF {#3} { 0 }

```

```

855   {
856     #2
857     \_siunitx_number_exponent_uncert:n { { S } { 0 } }
858   }
859   {
860     \use:c { __siunitx_number_exponent_shift_uncert_ \use_i:nn #3 :fnnn }
861     { \prg_replicate:nn {#1} { 0 } }
862     {#2}
863     #3
864   }
865 }
866 }
867 \cs_new:Npn \_siunitx_number_exponent_shift_uncert_S:nnnn #1#2#3#4
868 {
869   #2
870   \_siunitx_number_exponent_uncert:n { { S } { #4#1 } }
871 }
872 \cs_generate_variant:Nn \_siunitx_number_exponent_shift_uncert_S:nnnn { f }
873 \cs_new:Npn \_siunitx_number_exponent_uncert:n #1 { { \exp_not:n {#1} } }
```

Tidy up the exponent to put the sign in the right place.

```

874 \cs_new:Npn \_siunitx_number_exponent_finalise:n #1
875 {
876   \int_compare:nNnTF {#1} < 0
877   { { - } }
878   { { } }
879   { \int_abs:n {#1} }
880 }
```

This could (and eventually will) be combined with the main function above: that will need e-type expansion. The input has already been normalised such that the integer part is in the range $1 \leq n < 10$. Thus there are only three cases to deal with, depending on the required adjustment to the exponent.

```

881 \cs_new:Npn \_siunitx_number_exponent_engineering_aux:nnnnnnn #1#2#3#4#5#6#7
882 {
883   \exp_not:n { {#1} {#2} }
884   \use:c
885   {
886     __siunitx_number_exponent_engineering_
887     \int_compare:nNnTF {#6#7} < 0
888     {
889       \int_case:nnF { \int_mod:nn { #7 } { 3 } }
890       {
891         { 1 } { 2 }
892         { 2 } { 1 }
893       }
894       { 0 }
895     }
896     { \int_mod:nn {#7} { 3 } }
897     :nnnn
898   }
899   {#3} {#4} {#5} {#6#7}
900 }
901 \cs_new:cpn { __siunitx_number_exponent_engineering_0:nnnn } #1#2#3#4
902 {
```

```

903     \exp_not:n { #1} {#2} {#3} }
904     \_siunitx_number_exponent_finalise:n {#4}
905   }
906 \cs_new:cpn { _siunitx_number_exponent_engineering_1:nnnn } #1#2#3#4
907   {
908     \tl_if_blank:nTF {#2}
909     {
910       { \exp_not:n { #1 0 } } { }
911       { \_siunitx_number_exponent_engineering_uncert:nn {#3} { 0 } }
912     }
913     {
914       { \exp_not:n {#1} \exp_not:o { \tl_head:w #2 \q_stop } }
915       { \exp_not:f { \tl_tail:n {#2} } }
916       { \exp_not:n {#3} }
917     }
918     \_siunitx_number_exponent_finalise:n { #4 - 1 }
919   }
920 \cs_new:cpn { _siunitx_number_exponent_engineering_2:nnnn } #1#2#3#4
921   {
922     \tl_if_blank:nTF {#2}
923     {
924       { \exp_not:n { #1 00 } } { }
925       { \_siunitx_number_exponent_engineering_uncert:nn {#3} { 00 } }
926     }
927     { \_siunitx_number_exponent_engineering:nnNw {#1} {#3} #2 \q_stop }
928     \_siunitx_number_exponent_finalise:n { #4 - 2 }
929   }
930 \cs_new:Npn \_siunitx_number_exponent_engineering:nnNw #1#2#3#4 \q_stop
931   {
932     \tl_if_blank:nTF {#4}
933     {
934       { \exp_not:n { #1#3 0 } } { }
935       { \_siunitx_number_exponent_engineering_uncert:nn {#2} { 0 } }
936     }
937     {
938       { \exp_not:n {#1#3} \exp_not:o { \tl_head:w #4 \q_stop } }
939       { \exp_not:f { \tl_tail:n {#4} } }
940       { \exp_not:n {#2} }
941     }
942   }
943 \cs_new:Npn \_siunitx_number_exponent_engineering_uncert:nn #1#2
944   {
945     \tl_if_blank:nF {#1}
946     {
947       \use:c { _siunitx_number_exponent_engineering_uncert_ \use_i:nn #1 :nnn }
948       #1 {#2}
949     }
950   }
951 \cs_new:Npn \_siunitx_number_exponent_engineering_uncert_S:nnn #1#2#3
952   {
953     { S }
954   {
955     \exp_not:n {#2}
956     \str_if_eq:nnF {#2} { 0 } {#3}

```

```

957     }
958 }
```

(End definition for `_siunitx_number_exponent>NN` and others.)

Forcing a minimum number of digits in each part is quite easy. As the common case is that we don't do anything here, there is no real need to optimise the calculation (normally also numbers have only a few digits).

```

959 \cs_new_protected:Npn \_siunitx_number_digits:NN #1#2
960 {
961     \tl_set:Nx #2
962     { \exp_after:wN \_siunitx_number_digits:nnnnnnn #1 }
963 }
964 \cs_new:Npn \_siunitx_number_digits:nnnnnnn #1#2#3#4#5#6#7
965 {
966     \exp_not:n { #1} {#2}
967 }
968     \_siunitx_number_digits:Nn \l_siunitx_number_min_integer_int {#3}
969     \exp_not:n {#3}
970 }
971 {
972     \exp_not:n {#4}
973     \_siunitx_number_digits:Nn \l_siunitx_number_min_decimal_int {#4}
974 }
975 { \tl_if_blank:nF {#5} { \_siunitx_number_digits_uncert:nn #5 } }
976     \exp_not:n { #6} {#7}
977 }
978 \cs_new:Npn \_siunitx_number_digits:Nn #1#2
979 {
980     \int_compare:nNnT
981     { #1 - \tl_count:n {#2} } > 0
982     { \prg_replicate:nn { #1 - \tl_count:n {#2} } { 0 } }
983 }
984 \cs_new:Npn \_siunitx_number_digits_uncert:nn #1#2
985 {
986     { #1 }
987     { \use:c { __siunitx_number_digits_uncert_ #1 :n } {#2} }
988 }
989 \cs_new:Npn \_siunitx_number_digits_uncert_S:n #1
990 {
991     \exp_not:n {#1}
992     \_siunitx_number_digits:Nn \l_siunitx_number_min_decimal_int {#1}
993 }
```

(End definition for `_siunitx_number_digits>NN` and others.)

Simple stripping of the exponent.

```

994 \cs_new_protected:Npn \_siunitx_number_drop_exponent>NN #1#2
995 {
996     \bool_if:NT \l_siunitx_number_drop_exponent_bool
997     {
998         \tl_set:Nx #2
999         { \exp_after:wN \_siunitx_number_drop_exponent:nnnnnnn #1 }
1000 }
```

```

1001   }
1002 \cs_new:Npn \_siunitx_number_drop_exponent:nnnnnnn #1#2#3#4#5#6#7
1003   { \exp_not:n { #1} {#2} {#3} {#4} {#5} { } { 0 } } }

(End definition for \_siunitx_number_drop_exponent:NN and \_siunitx_number_drop_exponent:nnnnnnn.)
```

Simple stripping of the uncertainty.

```

1004 \cs_new_protected:Npn \_siunitx_number_drop_uncertainty:NN #1#2
1005   {
1006     \bool_if:NTF \l_siunitx_number_drop_uncertainty_bool
1007     {
1008       \tl_set:Nx #2
1009       { \exp_after:wN \_siunitx_number_drop_uncertainty:nnnnnnn #1 }
1010     }
1011   { \tl_set_eq:NN #2 #1 }

1012 }
1013 \cs_new:Npn \_siunitx_number_drop_uncertainty:nnnnnnn #1#2#3#4#5#6#7
1014   { \exp_not:n { #1} {#2} {#3} {#4} { } {#6} {#7} } }

(End definition for \_siunitx_number_drop_uncertainty:NN and \_siunitx_number_drop_uncertainty:nnnnnnn.)
```

_siunitx_number_round:NN
_siunitx_number_round_none:nnnnnnn Rounding is at the top level simple enough: fire off the expandable set up which does the work.

```

1016 \cs_new_protected:Npn \_siunitx_number_round:NN #1#2
1017   {
1018     \tl_set:Nx #2
1019     {
1020       \cs:w
1021         \_siunitx_number_round_ \l_siunitx_number_round_mode_tl :nnnnnnn
1022         \exp_after:wN
1023         \cs_end: #1
1024     }
1025   }
1026 \cs_new:Npn \_siunitx_number_round_none:nnnnnnn #1#2#3#4#5#6#7
1027   { \exp_not:n { #1} {#2} {#3} {#4} {#5} {#6} {#7} } }

(End definition for \_siunitx_number_round:NN and \_siunitx_number_round_none:nnnnnnn.)
```

_siunitx_number_round:nnn
_siunitx_number_round:fnn
_siunitx_number_round_auxi:nnN
_siunitx_number_round_auxii:nnN
_siunitx_number_round_auxiii:nnN
_siunitx_number_round_auxiv:nnN
_siunitx_number_round_auxv:nnN
_siunitx_number_round_auxvi:nN
_siunitx_number_round_auxvii:nnN
_siunitx_number_round_auxviii:nnN
_siunitx_number_round_final_integer:nnN
_siunitx_number_round_final_decimal:nnN
_siunitx_number_round_final_output:nn
_siunitx_number_round_final_output:ff
_siunitx_number_round_final:nn
_siunitx_number_round_final:fn
_siunitx_number_round_final_shift:nn
_siunitx_number_round_final_shift:ff
_siunitx_number_round_final_shift:Nw
_siunitx_number_round_engineering:nn
_siunitx_number_round_fixed:nn
_siunitx_number_round_input:nn
_siunitx_number_round_scientific:nn
_siunitx_number_round_engineering>NNNNn
_siunitx_number_round_engineering:nnN Actually doing the rounding needs us to work from the least significant digit, so we start by reversing the input. We could also drop digits in this phase, but tracking everything would be horrible, so we go slightly slower but clearer and split the steps. First we reverse the decimal part, then the integer.

```

1028 \cs_new:Npn \_siunitx_number_round:nnn #1#2#3
1029   {
1030     \_siunitx_number_round_auxi:nnn {#1} {#2} { }
1031     #3 \q_recursion_tail \q_recursion_stop
1032   }
1033 \cs_generate_variant:Nn \_siunitx_number_round:nnn { f }
1034 \cs_new:Npn \_siunitx_number_round_auxi:nnnN #1#2#3#4
1035   {
1036     \quark_if_recursion_tail_stop_do:Nn #4
1037     {
1038       \_siunitx_number_round_auxii:nnnN {#1} {#3} { } #2
```

```

1039          \q_recursion_tail \q_recursion_stop
1040      }
1041      \_siunitx_number_round_auxi:nnnN {#1} {#2} {#4#3}
1042  }
1043 \cs_new:Npn \_siunitx_number_round_auxii:nnnN #1#2#3#4
1044 {
1045     \quark_if_recursion_tail_stop_do:Nn #4
1046     {
1047         \tl_if_blank:nTF {#2}
1048         {
1049             \_siunitx_number_round_auxiv:nnnN {#1} { } { } #3
1050             \q_recursion_tail \q_recursion_stop
1051         }
1052         {
1053             \_siunitx_number_round_auxiii:nnnN {#1} {#3} { } #2
1054             \q_recursion_tail \q_recursion_stop
1055         }
1056     }
1057     \_siunitx_number_round_auxii:nnnN {#1} {#2} {#4#3}
1058 }

```

We now have the input reversed plus how many digits we need to discard (#1). We have two functions, one which deals with the decimal part, one of which deals with the integer. In the latter, we should never hit the end before we've dropped all the digits: the fixed-zero is a fall-back in case something weird happens. For the integer case, we need to collect up zeros to pad the length back out correctly later.

```

1059 \cs_new:Npn \_siunitx_number_round_auxiii:nnnN #1#2#3#4
1060 {
1061     \quark_if_recursion_tail_stop_do:Nn #4
1062     {
1063         \_siunitx_number_round_auxiv:nnnN {#1} { } {#3} #2
1064         \q_recursion_tail \q_recursion_stop
1065     }
1066     \int_compare:nNnTF {#1} > 0
1067     {
1068         \exp_args:Nf \_siunitx_number_round_auxiii:nnnN
1069         { \int_eval:n { #1 - 1 } } {#2} { #4#3 }
1070     }
1071     { \_siunitx_number_round_auxv:nnN {#3} {#2} #4 }
1072 }
1073 \cs_new:Npn \_siunitx_number_round_auxiv:nnnN #1#2#3#4
1074 {
1075     \quark_if_recursion_tail_stop_do:Nn #4
1076     { { 0 } { } }
1077     \int_compare:nNnTF {#1} > 0
1078     {
1079         \exp_args:Nf \_siunitx_number_round_auxiv:nnnN
1080         { \int_eval:n { #1 - 1 } } { #2 0 } { #4#3 }
1081     }
1082     { \_siunitx_number_round_auxvi:nnnN {#3} {#2} #4 }
1083 }

```

The lead off to rounding proper needs to deal with the half-even rule: it can only apply at this stage, when the *discarded* value can be exactly half.

```

1084 \cs_new:Npn __siunitx_number_round_auxv:nnN #1#2#3
1085 {
1086     \quark_if_recursion_tail_stop_do:Nn #3
1087     {
1088         __siunitx_number_round_auxvi:nnN
1089         {#1} { } #2 \q_recursion_tail \q_recursion_stop
1090     }
1091     \bool_lazy_or:nnTF
1092     { \int_compare_p:nNn { 0 \tl_head:n {#1} } < 5 }
1093     {
1094         \bool_lazy_all_p:n
1095         {
1096             { \l__siunitx_number_round_half_even_bool }
1097             { \int_if_odd_p:n {#3} }
1098             { \__siunitx_number_round_if_half_p:n {#1} }
1099         }
1100     }
1101     { \__siunitx_number_round_final_decimal:nnw }
1102     { \__siunitx_number_round_auxvii:nnN }
1103     {#2} { } #3
1104 }
1105 \cs_new:Npn __siunitx_number_round_auxvi:nnnN #1#2#3
1106 {
1107     \quark_if_recursion_tail_stop_do:Nn #3
1108     { { 0 } { } }
1109     \bool_lazy_or:nnTF
1110     { \int_compare_p:nNn { 0 \tl_head:n {#1} } < 5 }
1111     {
1112         \bool_lazy_all_p:n
1113         {
1114             { \l__siunitx_number_round_half_even_bool }
1115             { \int_if_odd_p:n {#3} }
1116             { \__siunitx_number_round_if_half_p:n {#1} }
1117         }
1118     }
1119     { \__siunitx_number_round_final_integer:nnw }
1120     { \__siunitx_number_round_auxviii:nnN }
1121     { } {#2} #3
1122 }

```

The main rounding routines. These are only every called when there is rounding to do, so there is no need to carry a flag forward. Thus the question to ask is simple: is the next value a 9 or not (as that continues the sequence). There is a general need to handle the case where a zero is rounded up: that automatically means a need to trim the other end.

```

1123 \cs_new:Npn __siunitx_number_round_auxvii:nnN #1#2#3
1124 {
1125     \quark_if_recursion_tail_stop_do:Nn #3
1126     {
1127         \str_if_eq:nnTF {#1} { 0 }
1128         {
1129             __siunitx_number_round_final_output:ff
1130             { 1 }
1131             { \__siunitx_number_round_truncate:n {#2} }

```

```

1132     }
1133 {
1134     \_siunitx_number_round_auxviii:nnN {\#2} { } #1
1135         \q_recursion_tail \q_recursion_stop
1136     }
1137 }
1138 \int_compare:nNnTF {\#3} = 9
1139 { \_siunitx_number_round_auxvii:nnN {\#1} { 0 #2 } }
1140 {
1141     \int_compare:nNnTF {\#3} = 0
1142 {
1143     \_siunitx_number_round_final_decimal:nnw
1144         {\#1} { 1 \_siunitx_number_round_truncate:n {\#2} }
1145     }
1146 {
1147     \_siunitx_number_round_final:fn
1148         { \int_eval:n { \#3 + 1 } }
1149         { \_siunitx_number_round_final_decimal:nnw {\#1} {\#2} }
1150     }
1151 }
1152 }
1153 \cs_new:Npn \_siunitx_number_round_auxviii:nnN #1#2#3
1154 {
1155     \quark_if_recursion_tail_stop_do:Nn #3
1156 {
1157     \tl_if_blank:nTF {\#1}
1158     {
1159         \_siunitx_number_round_final_shift:ff
1160         {
1161             \exp_last_unbraced:Nf 1
1162                 { \_siunitx_number_round_truncate_direct:n {\#2} } 0
1163             }
1164             {
1165             }
1166             {
1167                 \_siunitx_number_round_final_shift:ff
1168                     { 1 #2 }
1169                     { \_siunitx_number_round_truncate:n {\#1} }
1170                 }
1171             }
1172 \int_compare:nNnTF {\#3} = 9
1173 { \_siunitx_number_round_auxviii:nnN {\#1} { 0 #2 } }
1174 {
1175     \_siunitx_number_round_final:fn
1176         { \int_eval:n { \#3 + 1 } }
1177         { \_siunitx_number_round_final_integer:nnw {\#1} {\#2} }
1178     }
1179 }

```

Tidying up means grabbing the remaining digits and undoing the reversal.

```

1180 \cs_new:Npn \_siunitx_number_round_final_decimal:nnw
1181 #1#2#3 \q_recursion_tail \q_recursion_stop
1182 {
1183     \_siunitx_number_round_final_output:ff
1184         { \tl_reverse:n {\#1} }

```

```

1185     { \tl_reverse:n {#3} #2 }
1186   }
1187 \cs_new:Npn \__siunitx_number_round_final_integer:nnw
1188   #1#2#3 \q_recursion_tail \q_recursion_stop
1189   {
1190     \__siunitx_number_round_final_output:ff
1191     { \tl_reverse:n {#3} #2 }
1192     {#1}
1193   }
1194 \cs_new:Npn \__siunitx_number_round_final_output:nn #1#2 { {#1} {#2} }
1195 \cs_generate_variant:Nn \__siunitx_number_round_final_output:nn { ff }
1196 \cs_new:Npn \__siunitx_number_round_final:nn #1#2
1197   { #2 #1 }
1198 \cs_generate_variant:Nn \__siunitx_number_round_final:nn { f }

```

Here we deal with the case where rounding applies along with an exponent set based on number of places. We can only get here if an additional integer digit has been added, so there is no need to test for that. There are two cases for action: when using `scientific` mode, where we always need to shift by one, and when using `engineering` mode if we now have four digits. The latter is a bit more work: we need to trim digits off as required.

```

1199 \cs_new:Npn \__siunitx_number_round_final_shift:nn #1#2
1200   {
1201     \str_if_eq:VnTF \l__siunitx_number_round_mode_t1 { places }
1202     {
1203       \use:c
1204         { __siunitx_number_round_ \l__siunitx_number_exponent_mode_t1 :nn }
1205         {#1} {#2}
1206     }
1207     { {#1} {#2} }
1208   }
1209 \cs_generate_variant:Nn \__siunitx_number_round_final_shift:nn { ff }
1210 \cs_new:Npn \__siunitx_number_round_engineering:nn #1#2
1211   {
1212     \int_compare:nNnTF { \tl_count:n {#1} } = 4
1213     {
1214       \__siunitx_number_round_engineering:NNNNn #1 {#2}
1215       { }
1216       \__siunitx_number_round_final_shift:Nw 3
1217     }
1218     { {#1} {#2} }
1219   }
1220 \cs_new:Npn \__siunitx_number_round_engineering:NNNNn #1#2#3#4#5
1221   {
1222     {#1}
1223     \exp_args:NV \__siunitx_number_round_engineering:nnN
1224     { \l__siunitx_number_round_precision_int } { }
1225     #2#3#4#5 \q_recursion_tail \q_recursion_stop
1226   }
1227 \cs_new:Npn \__siunitx_number_round_engineering:nnN #1#2#3
1228   {
1229     \quark_if_recursion_tail_stop_do:Nn #3 { {#2} }
1230     \int_compare:nNnTF {#1} = { 0 }
1231     { \use_i_delimit_by_q_recursion_stop:nw { {#2} } }
1232     { \__siunitx_number_round_engineering:nnN { #1 - 1 } { #2#3 } }

```

```

1233   }
1234 \cs_new:Npn \__siunitx_number_round_fixed:nn #1#2 { {#1} {#2} }
1235 \cs_new:Npn \__siunitx_number_round_input:nn #1#2 { {#1} {#2} }
1236 \cs_new:Npn \__siunitx_number_round_scientific:nn #1#2
1237   {
1238     \__siunitx_number_exponent_shift:nnf
1239     { 1 } {#1} { \__siunitx_number_round_truncate_direct:n {#2} }
1240     { }
1241     \__siunitx_number_round_final_shift:Nw 1
1242   }
1243 \cs_new:Npn \__siunitx_number_round_final_shift:Nw #1#2 \__siunitx_number_round_places_end:nn
1244   { \__siunitx_number_exponent_finalise:n { #3#4 + #1 } }

```

When we have rounded up to the next power of ten, we need to go back and remove one more digit. That only happens when rounding to a number of figures or when dealing with an integer part.

```

1245 \cs_new:Npn \__siunitx_number_round_truncate:n #1
1246   {
1247     \str_if_eq:VnTF \l__siunitx_number_round_mode_t1 { figures }
1248     { \__siunitx_number_round_truncate_direct:n {#1} }
1249     {#1}
1250   }
1251 \cs_new:Npn \__siunitx_number_round_truncate_direct:n #1
1252   {
1253     \__siunitx_number_round_truncate:nnN { } { }
1254     #1 \q_recursion_tail \q_recursion_stop
1255   }
1256 \cs_new:Npn \__siunitx_number_round_truncate:nnN #1#2#3
1257   {
1258     \quark_if_recursion_tail_stop_do:Nn #3 { #1 }
1259     \__siunitx_number_round_truncate:nnN {#1#2} {#3}
1260   }

```

(End definition for `__siunitx_number_round:nnn` and others.)

`__siunitx_number_round_if_half:p`:
`__siunitx_number_round_if_half:N`:

```

1261 \prg_new_conditional:Npnn \__siunitx_number_round_if_half:n #1 { p }
1262   {
1263     \int_compare:nNnTF { \tl_head:n { #1 0 } } = 5
1264     {
1265       \exp_after:wN \__siunitx_number_round_if_half:N \use_none:n #1 0
1266       \q_recursion_tail \q_recursion_stop
1267     }
1268     { \prg_return_false: }
1269   }
1270 \cs_new:Npn \__siunitx_number_round_if_half:N #1
1271   {
1272     \quark_if_recursion_tail_stop_do:Nn #1
1273     { \prg_return_true: }
1274     \int_compare:nNnTF {#1} = 0
1275     { \__siunitx_number_round_if_half:N }
1276     { \use_i_delimit_by_q_recursion_stop:nw { \prg_return_false: } }
1277   }

```

(End definition for `_siunitx_number_round_if_half_p:n` and `_siunitx_number_round_if_half:N`.)

`_siunitx_number_round_pad:nnn`

The case where we are short of digits is easy enough to handle: generate zeros to pad it out.

```

1278 \cs_new:Npn \_siunitx_number_round_pad:nnn #1#2#3
1279   {
1280     {#2}
1281   {
1282     #3
1283     \bool_if:NT \l__siunitx_number_round_pad_bool
1284       { \prg_replicate:nn {#1} { 0 } }
1285   }
1286 }
```

(End definition for `_siunitx_number_round_pad:nnn`.)

`_siunitx_number_round_figures:nnnnnn`
`_siunitx_number_round_figures_aux:nnnnnn`
`_siunitx_number_round_figures_count:nnN`
`_siunitx_number_round_figures_count:nnN`

Rounding to figures only makes sense if the number is not 0, so we start by filtering out that case. We then check that there is no uncertainty, and that the number of figures requested is positive: if not, the result is always fixed at zero.

```

1287 \cs_new:Npn \_siunitx_number_round_figures:nnnnnn #1#2#3#4#5#6#7
1288   {
1289     \bool_lazy_and:nnTF
1290       { \str_if_eq_p:nn {#3} { 0 } }
1291     {
1292       \str_if_eq_p:ee
1293         { \exp_not:n {#4} } { \prg_replicate:nn { \tl_count:n {#4} } { 0 } }
1294     }
1295     { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#6} {#7} } }
1296     { \_siunitx_number_round_figures_aux:nnnnnn {#1} {#2} {#3} {#4} {#5} {#6} {#7} }
1297   }
1298 \cs_new:Npn \_siunitx_number_round_figures_aux:nnnnnn #1#2#3#4#5#6#7
1299   {
1300     \tl_if_blank:nTF {#5}
1301     {
1302       \int_compare:nNnTF \l__siunitx_number_round_precision_int > 0
1303         {
1304           \exp_not:n { {#1} {#2} }
1305           \_siunitx_number_round_figures_count:nnN {#3} {#4} #3#4
1306             \q_recursion_tail \q_recursion_stop
1307             \exp_not:n { { } {#6} {#7} }
1308         }
1309         { { } { } { 0 } { } { } { } { 0 } }
1310     }
1311     { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#6} {#7} } }
1312 }
```

The first real step is to count up the number of significant figures. The only tricky issue here is dealing with leading zeros.

```

1313 \cs_new:Npn \_siunitx_number_round_figures_count:nnN #1#2#3
1314   {
1315     \quark_if_recursion_tail_stop_do:Nn #3
1316       { { } { } { 0 } { } { } { } { 0 } }
1317     \int_compare:nNnTF {#3} = 0
1318       { \_siunitx_number_round_figures_count:nnN {#1} {#2} }
```

```

1319     { \_siunitx_number_round_figures_count:nnnN { 1 } {#1} {#2} }
1320   }
1321 \cs_new:Npn \_siunitx_number_round_figures_count:nnnN #1#2#3#4
1322   {
1323     \quark_if_recursion_tail_stop_do:Nn #4
1324   {
1325     \int_compare:nNnTF {#1} > \l_siunitx_number_round_precision_int
1326     {
1327       \_siunitx_number_round:fnn
1328       { \int_eval:n { #1 - \l_siunitx_number_round_precision_int } }
1329       {#2} {#3}
1330     }
1331   {
1332     \_siunitx_number_round_pad:nnn
1333     { \l_siunitx_number_round_precision_int - (#1) } {#2} {#3}
1334   }
1335 }
1336 \exp_args:Nf \_siunitx_number_round_figures_count:nnnN
1337   { \int_eval:n { #1 + 1 } } {#2} {#3}
1338 }

```

(End definition for `_siunitx_number_round_figures:nnnnnnn` and others.)

The first step when rounding to a fixed number of places is to establish if this is in the decimal or integer parts. The two require different calculations for how many digits to drop from the input. The no-op end function here is to allow tidying up in some cases: see the finalisation of rounding.

```

1339 \cs_new:Npn \_siunitx_number_round_places:nnnnnnn #1#2#3#4#5#6#7
1340   {
1341     \tl_if_blank:nTF {#5}
1342   {
1343     \exp_args:Ne \_siunitx_number_round_places_finalise:n
1344   {
1345     \exp_not:n { {#1} {#2} }
1346     \int_compare:nNnTF \l_siunitx_number_round_precision_int > 0
1347     { \_siunitx_number_round_places_decimal:nn }
1348     { \_siunitx_number_round_places_integer:nn }
1349     {#3} {#4}
1350     \_siunitx_number_round_places_end:nn {#6} {#7}
1351   }
1352 }
1353 { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#6} {#7} } }
1354 }
1355 \cs_new:Npn \_siunitx_number_round_places_end:nn #1#2 { { } \exp_not:n { {#1} {#2} } }
1356 \cs_new:Npn \_siunitx_number_round_places_decimal:nn #1#2
1357   {
1358     \int_compare:nNnTF
1359     { \l_siunitx_number_round_precision_int - 0 \tl_count:n {#2} } > 0
1360   {
1361     \_siunitx_number_round_pad:nnn
1362     { \l_siunitx_number_round_precision_int - 0 \tl_count:n {#2} }
1363     {#1} {#2}
1364   }
1365 }

```

```

1366     \_siunitx_number_round:fnn
1367     {
1368         \int_eval:n
1369             { 0 \tl_count:n {#2} - \l_siunitx_number_round_precision_int }
1370         }
1371         {#1} {#2}
1372     }
1373 }
1374 \cs_new:Npn \_siunitx_number_round_places_integer:nn #1#2
1375 {
1376     \_siunitx_number_round:fnn
1377     {
1378         \int_eval:n
1379             { 0 \tl_count:n {#2} - \l_siunitx_number_round_precision_int }
1380         }
1381         {#1} {#2}
1382     }

```

To finalise rounding to places, we have to worry about a minimum value: that is basically a case of looking for value of zero and rearranging. We also need to worry about a “negative zero” arising.

```

1383 \cs_new:Npn \_siunitx_number_round_places_finalise:n #1
1384     { \_siunitx_number_round_places_finalise:nnnnnnn #1 }
1385 \cs_new:Npn \_siunitx_number_round_places_finalise:nnnnnnn #1#2#3#4#5#6#7
1386 {
1387     \bool_lazy_and:nnTF
1388         { \str_if_eq_p:nn {#3} { 0 } }
1389     {
1390         \str_if_eq_p:ee
1391             { \exp_not:n {#4} } { \prg_replicate:nn { \tl_count:n {#4} } { 0 } }
1392     }
1393     {
1394         \tl_if_empty:NTF \l_siunitx_number_round_min_tl
1395         {
1396             \exp_not:n { {#1} }
1397             { \str_if_eq:nnF {#2} { - } { \exp_not:n {#2} } }
1398             \exp_not:n { {#3} {#4} {#5} {#6} {#7} }
1399         }
1400         {
1401             \exp_after:wN \_siunitx_number_round_places_finalise:nnnn
1402                 \l_siunitx_number_round_min_tl {#2} {#6} {#7}
1403         }
1404     }
1405     { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#6} {#7} } }
1406 }
1407 \cs_new:Npn \_siunitx_number_round_places_finalise:nnnn #1#2#3#4#5
1408 {
1409     {
1410         \str_if_eq:nnTF {#3} { - }
1411             { > }
1412             { < }
1413     }
1414     \exp_not:n { {#3} {#1} {#2} { } {#4} {#5} }
1415 }

```

(End definition for `_siunitx_number_round_places:nnnnnnn` and others.)

Rounding to an uncertainty can only happen where the result will have some uncertainty left: otherwise we simply drop the uncertainty entirely. Only S-type uncertainties can be used for rounding.

```

1416 \cs_new:Npn \_siunitx_number_round_uncertainty:nnnnnnn #1#2#3#4#5#6#7
1417 {
1418     \bool_lazy_or:nnTF
1419         { \tl_if_blank_p:n {#5} }
1420         { ! \int_compare_p:nNn \l_siunitx_number_round_precision_int > 0 }
1421         { \exp_not:n { {#1} #2 {#3} {#4} { } #6 {#7} } }
1422     {
1423         \str_if_eq:eeTF { \tl_head:n {#5} } { S }
1424         {
1425             \exp_not:n { {#1} {#2} }
1426             \exp_args:Nnno \_siunitx_number_round_uncertainty:nnn
1427                 {#3} {#4} { \use_i:nn #5 }
1428             \exp_not:n { {#6} {#7} }
1429         }
1430         { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#6} {#7} } }
1431     }
1432 }
```

Round the uncertainty first: this is needed to get the number of places correct (for the case where the uncertainty rounds up to 1...). Once that is done, it's just a question of working out the digits in the main part.

```

1433 \cs_new:Npn \_siunitx_number_round_uncertainty:nnn #1#2#3
1434 {
1435     \exp_last_unbraced:Nf \_siunitx_number_round_uncertainty:nnnnn
1436     {
1437         \_siunitx_number_round:fnn
1438         {
1439             \int_eval:n
1440                 { \tl_count:n {#3} - \l_siunitx_number_round_precision_int }
1441             }
1442             {#3}
1443         }
1444         {#1} {#2} {#3}
1445     }
1446 \cs_new:Npn \_siunitx_number_round_uncertainty:nnnnn #1#2#3#4#5
1447 {
1448     \exp_args:Nf \_siunitx_number_round_uncertainty_aux:nnnnn
1449     { \int_eval:n { \tl_count:n {#5} - \tl_count:n {#2} } }
1450     {#1} {#2} {#3} {#4}
1451 }
```

The first argument here deals with the case where we've lost digits in the uncertainty and it's purely located in the integer part.

```

1452 \cs_new:Npn \_siunitx_number_round_uncertainty_aux:nnnnn #1#2#3#4#5
1453 {
1454     \exp_args:Nf \_siunitx_number_round_uncertainty_aux:nnnnnn
1455     {
1456         \tl_if_blank:nT {#5}
1457         { \prg_replicate:nn {#1} { 0 } }
```

```

1458     }
1459     {#1} {#2} {#3} {#4} {#5}
1460   }
1461 \cs_new:Npn \__siunitx_number_round_uncertainty_aux:nnnnnn #1#2#3#4#5#6
1462   {
1463     \tl_if_blank:nTF {#3}
1464     {
1465       \__siunitx_number_round:nnn
1466       {#2}
1467       {#5} {#6}
1468       { { S } { #4 #1 } }
1469     }
1470   {
1471     \__siunitx_number_round:fnn
1472     { \int_eval:n { #2 + 1 } }
1473     {#6}
1474     { { S } { #3 \__siunitx_number_round_truncate_direct:n {#4} #1 } }
1475   }
1476 }

```

(End definition for `__siunitx_number_round_uncertainty:nnnnnnn` and others.)

`__siunitx_number_zero_decimal:NN`

```

\__siunitx_number_zero_decimal:nnnnnnn
1477 \cs_new_protected:Npn \__siunitx_number_zero_decimal:NN #1#2
1478   {
1479     \bool_if:NT \l__siunitx_number_drop_zero_decimal_bool
1480     {
1481       \tl_set:Nx #2
1482       { \exp_after:wN \__siunitx_number_zero_decimal:nnnnnnn #1 }
1483     }
1484   }
1485 \cs_new:Npn \__siunitx_number_zero_decimal:nnnnnnn #1#2#3#4#5#6#7
1486   {
1487     \exp_not:n { {#1} {#2} {#3} }
1488     \str_if_eq:eeTF
1489     { \exp_not:n {#4} }
1490     { \prg_replicate:nn { \tl_count:n {#4} } { 0 } }
1491     { { } }
1492     { \exp_not:n { {#4} } }
1493     \exp_not:n { {#5} {#6} {#7} }
1494   }

```

(End definition for `__siunitx_number_zero_decimal:NN` and `__siunitx_number_zero_decimal:nnnnnnn`.)

2.5 Number modification

A simply case of breaking down and rebuilding the number.

```

\siunitx_number_adjust_exponent:nn
\siunitx_number_adjust_exponent:Nn
\__siunitx_number_adjust_exp:nnnnnnn
\__siunitx_number_adjust_exp:nn
\__siunitx_number_adjust_exp:nNw
1495 \cs_new:Npn \siunitx_number_adjust_exponent:nn #1#2
1496   { \__siunitx_number_adjust_exp:nnnnnnn #1 {#2} }
1497 \cs_new:Npn \siunitx_number_adjust_exponent:Nn #1#2
1498   {
1499     \tl_if_empty:NF #1
1500     { \exp_args:NV \siunitx_number_adjust_exponent:nn #1 {#2} }
1501   }

```

```

1502 \cs_new:Npn \__siunitx_number_adjust_exp:n#####8
1503 {
1504     \exp_not:n { #1} {#2} {#3} {#4} {#5} }
1505     \exp_args:N e \__siunitx_number_adjust_exp:nn { \fp_eval:n { #6#7 + #8 } } {#6}
1506 }
1507 \cs_new:Npn \__siunitx_number_adjust_exp:nn #1#2
1508 { \__siunitx_number_adjust_exp:nNw {#2} #1 \q_stop }
1509 \cs_new:Npn \__siunitx_number_adjust_exp:nNw #1#2#3 \q_stop
1510 {
1511     \token_if_eq_meaning:NNTF #2 -
1512     { { - } { \exp_not:n {#3} } }
1513     { { \str_if_eq:nnT {#1} { + } { + } } { \exp_not:n {#2#3} } }
1514 }

```

(End definition for `\siunitx_number_adjust_exponent:nn` and others. These functions are documented on page 39.)

2.6 Outputting parsed numbers

Purely internal for the present.

```

1515 \tl_new:N \l_siunitx_number_bracket_close_tl
1516 \tl_new:N \l_siunitx_number_bracket_open_tl
1517 \tl_set:Nn \l_siunitx_number_bracket_open_tl { ( }
1518 \tl_set:Nn \l_siunitx_number_bracket_close_tl { ) }

```

(End definition for `\l_siunitx_number_bracket_close_tl` and `\l_siunitx_number_bracket_open-tl`.)

`\l_siunitx_number_bracket_ambiguous_bool`

```
1519 \bool_new:N \l_siunitx_number_bracket_ambiguous_bool
```

(End definition for `\l_siunitx_number_bracket_ambiguous_bool`. This variable is documented on page ??.)

`\l_siunitx_number_output_decimal_tl`

```
1520 \tl_new:N \l_siunitx_number_output_decimal_tl
```

(End definition for `\l_siunitx_number_output_decimal_tl`. This variable is documented on page 40.)

Keys producing tokens in the output.

```

1521 \keys_define:nn { siunitx }
1522 {
1523     bracket-ambiguous-numbers .bool_set:N =
1524         \l_siunitx_number_bracket_ambiguous_bool ,
1525     bracket-negative-numbers .bool_set:N =
1526         \l_siunitx_number_bracket_negative_bool ,
1527     exponent-base .tl_set:N =
1528         \l_siunitx_number_exponent_base_tl ,
1529     exponent-product .tl_set:N =
1530         \l_siunitx_number_exponent_product_tl ,
1531     group-digits .choice: ,
1532     group-digits / all .code:n =
1533     {
1534         \bool_set_true:N \l_siunitx_number_group_decimal_bool
1535         \bool_set_true:N \l_siunitx_number_group_integer_bool

```

```

1536     } ,
1537     group-digits / decimal .code:n =
1538     {
1539         \bool_set_true:N \l_siunitx_number_group_decimal_bool
1540         \bool_set_false:N \l_siunitx_number_group_integer_bool
1541     } ,
1542     group-digits / integer .code:n =
1543     {
1544         \bool_set_false:N \l_siunitx_number_group_decimal_bool
1545         \bool_set_true:N \l_siunitx_number_group_integer_bool
1546     } ,
1547     group-digits / none .code:n =
1548     {
1549         \bool_set_false:N \l_siunitx_number_group_decimal_bool
1550         \bool_set_false:N \l_siunitx_number_group_integer_bool
1551     } ,
1552     group-digits .default:n = all ,
1553     group-minimum-digits .int_set:N =
1554         \l_siunitx_number_group_minimum_int ,
1555     group-separator .tl_set:N =
1556         \l_siunitx_number_group_separator_tl ,
1557     negative-color .tl_set:N =
1558         \l_siunitx_number_negative_color_tl ,
1559     output-close-uncertainty .tl_set:N =
1560         \l_siunitx_number_output_uncert_close_tl ,
1561     output-decimal-marker .tl_set:N =
1562         \l_siunitx_number_output_decimal_tl ,
1563     output-exponent-marker .tl_set:N =
1564         \l_siunitx_number_output_exp_marker_tl ,
1565     output-open-uncertainty .tl_set:N =
1566         \l_siunitx_number_output_uncert_open_tl ,
1567     print-implicit-plus .bool_set:N =
1568         \l_siunitx_number_implicit_plus_bool ,
1569     print-unity-mantissa .bool_set:N =
1570         \l_siunitx_number_unity_mantissa_bool ,
1571     print-zero-exponent .bool_set:N =
1572         \l_siunitx_number_zero_exponent_bool ,
1573     tight-spacing .bool_set:N =
1574         \l_siunitx_number_tight_bool ,
1575     uncertainty-mode .choices:nn =
1576         { compact , compact-marker , full , separate }
1577         { \tl_set_eq:NN \l_siunitx_number_uncert_mode_tl \l_keys_choice_tl } ,
1578     uncertainty-separator .tl_set:N =
1579         \l_siunitx_number_uncert_separator_tl
1580     }
1581 \bool_new:N \l_siunitx_number_group_decimal_bool
1582 \bool_new:N \l_siunitx_number_group_integer_bool
1583 \tl_new:N \l_siunitx_number_uncert_mode_tl

```

(End definition for `\l_siunitx_number_bracket_negative_bool` and others.)

`\siunitx_number_output:N` The approach to formatting a single number is to split into the constituent parts. All of the parts are assembled including inserting tabular alignment markers (which may be empty) for each separate unit.

`\siunitx_number_output:nN`

```

\__siunitx_number_output:NN
\__siunitx_number_output:nn
    \__siunitx_number_output:mnnnnn
\__siunitx_number_output_bracket:nn
    \__siunitx_number_output_bracket:w
\__siunitx_number_output_comparator:nn
    \__siunitx_number_output_sign:nnn
    \__siunitx_number_output_sign:nN
    \__siunitx_number_output_sign:N
\__siunitx_number_output_align:center

```

```

1584 \cs_new:Npn \siunitx_number_output:N #1
1585   { \__siunitx_number_output:Nn #1 { } }
1586 \cs_new:Npn \siunitx_number_output:n #1
1587   { \__siunitx_number_output:nn #1 { } }
1588 \cs_new:Npn \siunitx_number_output:NN #1#2
1589   { \__siunitx_number_output:Nn #1 {#2} }
1590 \cs_new:Npn \siunitx_number_output:nN #1#2
1591   { \__siunitx_number_output:nn #1 {#2} }
1592 \cs_new:Npn \__siunitx_number_output:Nn #1#2
1593   {
1594     \tl_if_empty:NF #1
1595       { \exp_after:wN \__siunitx_number_output:nnnnnnn #1 {#2} }
1596   }
1597 \cs_new:Npn \__siunitx_number_output:nn #1#2
1598   {
1599     \tl_if_empty:nF {#1}
1600       { \__siunitx_number_output:nnnnnnn #1 {#2} }
1601   }
1602 \cs_new:Npn \__siunitx_number_output:nnnnnnn #1#2#3#4#5#6#7#8
1603   {
1604     \__siunitx_number_output_color:n {#2}
1605     \__siunitx_number_output_comparator:nn {#1} {#8}
1606     \__siunitx_number_output_bracket:nn {#5} {#7}
1607     \__siunitx_number_output_sign:nnn {#1} {#2} {#8}
1608     \__siunitx_number_output_integer:nnn {#3} {#4} {#7}
1609     \__siunitx_number_output_decimal:nn {#4} {#8}
1610     \__siunitx_number_output_uncertainty:nnn {#5} {#4} {#8}
1611     \__siunitx_number_output_exponent:nnnn {#6} {#7} {#3 . #4} {#8}
1612     \__siunitx_number_output_end:
1613   }

```

Adding brackets for the combination of a separate uncertainty with an exponent may need brackets. This needs testing up-front, so has to come before the main formatting routines.

```

1614 \cs_new:Npn \__siunitx_number_output_bracket:nn #1#2
1615   {
1616     \bool_lazy_all:nT
1617   {
1618     { \str_if_eq_p:Vn \l__siunitx_number_uncert_mode_tl { separate } }
1619     { \l_siunitx_number_bracket_ambiguous_bool }
1620     { ! \tl_if_blank_p:n {#1} }
1621   {
1622     \bool_lazy_or_p:nn
1623       { \l__siunitx_number_zero_exponent_bool }
1624       { ! \str_if_eq_p:nn {#2} { 0 } }
1625   }
1626   }
1627   \__siunitx_number_output_bracket:w
1628 }
1629 \cs_new:Npn \__siunitx_number_output_bracket:w #1 \__siunitx_number_output_exponent:nnnn
1630   {
1631     \exp_not:V \l__siunitx_number_bracket_open_tl
1632     #1
1633     \exp_not:V \l__siunitx_number_bracket_close_tl

```

```

1634     \_\_siunitx_number_output_exponent:nnnn
1635 }

```

As color for negative values applies to the *whole* output, we have to deal with it before anything else.

```

1636 \cs_new:Npn \_\_siunitx_number_output_color:n #1
1637 {
1638     \bool_lazy_and:nnT
1639     { \str_if_eq_p:nn {#1} { - } }
1640     { ! \tl_if_empty_p:N \l_\_siunitx_number_negative_color_tl }
1641     { \exp_not:N \color { \exp_not:V \l_\_siunitx_number_negative_color_tl } }
1642 }

```

To get the spacing correct this needs to be an ordinary math character.

```

1643 \cs_new:Npn \_\_siunitx_number_output_comparator:nn #1#2
1644 {
1645     \tl_if_blank:nF {#1}
1646     { \exp_not:n { \mathord {#1} } }
1647     \exp_not:n {#2}
1648 }

```

Formatting signs has to deal with some additional formatting requirements for negative numbers. Making such numbers by bracketing them needs some rearrangement of the order of tokens, which is set up in the main formatting macro by the dedicated do-nothing end function. We also have the comparator passed here: if it is present, we need to deal with tighter spacing.

```

1649 \cs_new:Npn \_\_siunitx_number_output_sign:nnn #1#2#3
1650 {
1651     \tl_if_blank:nTF {#2}
1652     {
1653         \bool_if:NT \l_\_siunitx_number_implicit_plus_bool
1654         { \_\_siunitx_number_output_sign:nN {#1} + }
1655     }
1656     {
1657         \str_if_eq:nnTF {#2} { - }
1658         {
1659             \bool_if:NTF \l_\_siunitx_number_bracket_negative_bool
1660             { \_\_siunitx_number_output_sign_brackets:w }
1661             { \_\_siunitx_number_output_sign:nN {#1} #2 }
1662         }
1663         { \_\_siunitx_number_output_sign:nN {#1} #2 }
1664     }
1665     \exp_not:n {#3}
1666 }
1667 \cs_new:Npn \_\_siunitx_number_output_sign:nN #1#2
1668 {
1669     \tl_if_blank:nTF {#1}
1670     { \_\_siunitx_number_output_sign:N #2 }
1671     { \exp_not:n { \mathord {#2} } }
1672 }
1673 \cs_new:Npn \_\_siunitx_number_output_sign:N #1
1674 {
1675     \bool_if:NTF \l_\_siunitx_number_tight_bool
1676     { \exp_not:n { \mathord {#1} } }
1677     { \exp_not:n {#1} }

```

```

1678    }
1679 \cs_new:Npn
1680   \__siunitx_number_output_sign_brackets:w #1 \__siunitx_number_output_end:
1681 {
1682   \exp_not:V \l__siunitx_number_bracket_open_tl
1683   #1
1684   \exp_not:V \l__siunitx_number_bracket_close_tl
1685   \__siunitx_number_output_end:
1686 }

```

Digit formatting leads off with separate functions to allow for a few “up front” items before using a common set of tests for some common cases. The code then splits again as the two types of grouping need different strategies.

```

1687 \cs_new:Npn \__siunitx_number_output_integer:nnn #1#2#3
1688 {
1689   \bool_lazy_or:nnT
1690   { \l__siunitx_number_unity_mantissa_bool }
1691   { ! \str_if_eq_p:nn { #1 . #2 } { 1. } }
1692   { \__siunitx_number_output_digits:nn { integer } {#1} }
1693 }
1694 \cs_new:Npn \__siunitx_number_output_decimal:nn #1#2
1695 {
1696   \exp_not:n {#2}
1697   \tl_if_blank:nF {#1}
1698   {
1699     \str_if_eq:VnTF \l_siunitx_number_output_decimal_tl { , }
1700     { \exp_not:N \mathord }
1701     { \use:n }
1702     { \exp_not:V \l_siunitx_number_output_decimal_tl }
1703   }
1704   \exp_not:n {#2}
1705   \__siunitx_number_output_digits:nn { decimal } {#1}
1706 }
1707 \cs_generate_variant:Nn \__siunitx_number_output_decimal:nn { f }
1708 \cs_new:Npn \__siunitx_number_output_digits:nn #1#2
1709 {
1710   \bool_if:cTF { \l__siunitx_number_group_ #1 _ bool }
1711   {
1712     \int_compare:nNnTF
1713     { \tl_count:n {#2} } < \l__siunitx_number_group_minimum_int
1714     { \exp_not:n {#2} }
1715     { \use:c { __siunitx_number_output_ #1 _aux:n } {#2} }
1716   }
1717   { \exp_not:n {#2} }
1718 }

```

For integers, we need to know how many digits there are to allow for the correct insertion of separators. That is done using a two-part set up such that there is no separator on the first pass.

```

1719 \cs_new:Npn \__siunitx_number_output_integer_aux:n #1
1720 {
1721   \use:c
1722   {
1723     __siunitx_number_output_integer_aux_
1724     \int_eval:n { \int_mod:nn { \tl_count:n {#1} } { 3 } }

```

```

1725          :n
1726      } {#1}
1727  }
1728 \cs_new:cpn { __siunitx_number_output_integer_aux_0:n } #1
1729   { __siunitx_number_output_integer_first:nnNN #1 \q_nil }
1730 \cs_new:cpn { __siunitx_number_output_integer_aux_1:n } #1
1731   { __siunitx_number_output_integer_first:nnNN { } { } #1 \q_nil }
1732 \cs_new:cpn { __siunitx_number_output_integer_aux_2:n } #1
1733   { __siunitx_number_output_integer_first:nnNN { } #1 \q_nil }
1734 \cs_new:Npn __siunitx_number_output_integer_first:nnNN #1#2#3#4
1735   {
1736     \exp_not:n {#1#2#3}
1737     \quark_if_nil:NF #4
1738     { __siunitx_number_output_integer_loop:NNNN #4 }
1739   }
1740 \cs_new:Npn __siunitx_number_output_integer_loop:NNNN #1#2#3#4
1741   {
1742     \str_if_eq:VnTF \l__siunitx_number_group_separator_tl { , }
1743     { \exp_not:N \mathord }
1744     { \use:n }
1745     { \exp_not:V \l__siunitx_number_group_separator_tl }
1746     \exp_not:n {#1#2#3}
1747     \quark_if_nil:NF #4
1748     { __siunitx_number_output_integer_loop:NNNN #4 }
1749   }

```

For decimals, no need to do any counting, just loop using enough markers to find the end of the list. By passing the decimal marker, it is possible not to have to use a check on the content of the rest of the number. The `\use_none:n(n)` mop up the remaining `\q_nil` tokens.

```

1750 \cs_new:Npn __siunitx_number_output_decimal_aux:n #1
1751   {
1752     __siunitx_number_output_decimal_loop:NNNN \c_empty_tl
1753     #1 \q_nil \q_nil \q_nil
1754   }
1755 \cs_new:Npn __siunitx_number_output_decimal_loop:NNNN #1#2#3#4
1756   {
1757     \quark_if_nil:NF #2
1758     {
1759       \exp_not:V #1
1760       \exp_not:n {#2}
1761       \quark_if_nil:NTF #3
1762       { \use_none:n }
1763       {
1764         \exp_not:n {#3}
1765         \quark_if_nil:NTF #4
1766         { \use_none:nn }
1767         {
1768           \exp_not:n {#4}
1769           __siunitx_number_output_decimal_loop:NNNN
1770             \l__siunitx_number_group_separator_tl
1771           }
1772         }
1773   }

```

```
1774 }
```

Uncertainties which are directly attached are easy to deal with. For those that are separated, the first step is to find if they are entirely contained within the decimal part, and to pad if they are. For the case where the boundary is crossed to the integer part, the correct number of digit tokens need to be removed from the start of the uncertainty and the split result sent to the appropriate auxiliaries.

```
1775 \cs_new:Npn \__siunitx_number_output_uncertainty:n {#1} {#3}
1776 {
1777     \tl_if_blank:nTF {#1}
1778     {
1779         \__siunitx_number_output_uncertainty_unaligned:n {#3}
1780         {
1781             \use:c { __siunitx_number_output_uncert_ \tl_head:n {#1} :nnnw }
1782             {#2} {#3} #1
1783         }
1784     }
1785 \cs_new:Npn \__siunitx_number_output_uncertainty_unaligned:n {#1}
1786 {
1787     \exp_not:n {#1} {#1} {#1} {#1}
1788 \cs_new:Npn \__siunitx_number_output_uncert_S:nnnw {#1} {#3} {#4}
1789 {
1790     \str_if_eq:VnTF \l__siunitx_number_uncert_mode_tl {separate}
1791     {
1792         \exp_not:n {#2}
1793         \__siunitx_number_output_sign:N \pm
1794         \exp_not:n {#2}
1795         \__siunitx_number_output_uncert_S_aux:nnn
1796         {
1797             \int_eval:n { \tl_count:n {#4} - \tl_count:n {#1} }
1798             {#4} {#2}
1799         }
1800     }
1801     {
1802         \exp_not:V \l__siunitx_number_uncert_separator_tl
1803         \exp_not:V \l__siunitx_number_output_uncert_open_tl
1804         \use:c { __siunitx_number_output_uncert_S_ \l__siunitx_number_uncert_mode_tl :nn } {#2}
1805         \exp_not:V \l__siunitx_number_output_uncert_close_tl
1806         \__siunitx_number_output_uncertainty_unaligned:n {#2}
1807     }
1808 }
1809 \cs_new:Npn \__siunitx_number_output_uncert_S_aux:nnn {#1} {#3} {#4}
1810 {
1811     \int_compare:nNnTF {#1} > 0
1812     {
1813         \__siunitx_number_output_uncert_S_aux:fnnw
1814         {
1815             \int_eval:n {#1 - 1}
1816             {#3}
1817             {#4}
1818             #2 \q_nil
1819         }
1820     }
1821 }
```

```

1822          {#3}
1823      }
1824  }
1825 \cs_generate_variant:Nn \__siunitx_number_output_uncert_S_aux:nnn { f }
1826 \cs_new:Npn \__siunitx_number_output_uncert_S_aux:nnnw #1#2#3#4
1827 {
1828     \quark_if_nil:NF #4
1829     {
1830         \int_compare:nNnTF {#1} = 0
1831             { \__siunitx_number_output_uncert_S_aux:nnw {#3#4} {#2} }
1832             {
1833                 \__siunitx_number_output_uncert_S_aux:fnnw
1834                     { \int_eval:n {#1 - 1} }
1835                     {#2}
1836                     {#3#4}
1837             }
1838         }
1839     }
1840 \cs_generate_variant:Nn \__siunitx_number_output_uncert_S_aux:nnnw { f }
1841 \cs_new:Npn \__siunitx_number_output_uncert_S_aux:nnw #1#2#3 \q_nil
1842 {
1843     \__siunitx_number_output_digits:nn { integer } {#1}
1844     \__siunitx_number_output_decimal:nn {#3} {#2}
1845 }

```

Handle the content of brackets: the only complex case is the mixed situation.

```

1846 \cs_new:Npn \__siunitx_number_output_uncert_S_compact:nn #1#2
1847     { \exp_not:n {#2} }
1848 \cs_new:cpn { __siunitx_number_output_uncert_S_compact-marker:nn } #1#2
1849     {
1850         \bool_lazy_or:nnTF
1851             { \tl_if_blank_p:n {#1} }
1852             { ! \int_compare_p:nNn { \tl_count:n {#2} } > { \tl_count:n {#1} } }
1853             { \__siunitx_number_output_uncert_S_compact:nn }
1854             { \__siunitx_number_output_uncert_S_full:nn }
1855             {#1} {#2}
1856     }
1857 \cs_new:Npn \__siunitx_number_output_uncert_S_full:nn #1#2
1858     {
1859         \__siunitx_number_output_uncert_S_aux:fnn
1860             { \int_eval:n { \tl_count:n {#2} - \tl_count:n {#1} } }
1861             {#2} { }
1862     }

```

Setting the exponent part requires some information about the mantissa: was it there or not. This means that whilst only the sign and value for the exponent are typeset here, there is a need to also have access to the combined mantissa part (with a decimal marker). The rest of the work is about picking up the various options and getting the combinations right. For signs, the auxiliary from the main sign routine can be used, but not the main function: negative exponents don't have special handling.

```

1863 \cs_new:Npn \__siunitx_number_output_exponent:nnnn #1#2#3#4
1864     {
1865         \exp_not:n {#4}
1866         \bool_lazy_or:nnTF

```

```

1867 { \l_siunitx_number_zero_exponent_bool }
1868 { ! \str_if_eq_p:nn {#2} { 0 } }
1869 {
1870     \tl_if_empty:NTF \l_siunitx_number_output_exp_marker_tl
1871         { \_siunitx_number_output_exponent_auxi:nnnn }
1872         { \_siunitx_number_output_exponent_auxii:nnnn }
1873             {#1} {#2} {#3} {#4}
1874     }
1875     { \exp_not:n {#4} }
1876 }
1877 \cs_new:Npn \_siunitx_number_output_exponent_auxi:nnnn #1#2#3#4
1878 {
1879     \bool_lazy_or:nnTF
1880         { \l_siunitx_number_unity_mantissa_bool }
1881         { ! \str_if_eq_p:nn {#3} { 1. } }
1882     {
1883         \bool_if:NTF \l_siunitx_number_tight_bool
1884             { \exp_not:N \mathord }
1885             { \use:n }
1886                 { \exp_not:V \l_siunitx_number_exponent_product_tl }
1887             \exp_not:n {#4}
1888     }
1889     { \exp_not:n {#4} }
1890     \exp_not:V \l_siunitx_number_exponent_base_tl
1891     {
1892         { \_siunitx_number_output_exponent_auxiii:nn {#1} {#2} }
1893     }
1894 \cs_new:Npn \_siunitx_number_output_exponent_auxii:nnnn #1#2#3#4
1895 {
1896     \exp_not:n {#4}
1897     \exp_not:V \l_siunitx_number_output_exp_marker_tl
1898         \_siunitx_number_output_exponent_auxiii:nn {#1} {#2}
1899     }
1900 \cs_new:Npn \_siunitx_number_output_exponent_auxiii:nn #1#2
1901 {
1902     \tl_if_blank:nTF {#1}
1903     {
1904         \bool_if:NT \l_siunitx_number_implicit_plus_bool
1905             { \_siunitx_number_output_sign:N + }
1906         }
1907         { \_siunitx_number_output_sign:N #1 }
1908         \_siunitx_number_output_digits:nn { integer } {#2}
1909     }

```

A do-nothing marker used to allow shuffling of the output and so expandable operations for formatting.

```
1910 \cs_new:Npn \_siunitx_number_output_end: { }
```

(End definition for `\siunitx_number_output:N` and others. These functions are documented on page 39.)

2.7 Miscellaneous tools

`\l_siunitx_number_valid_tl` The list of valid tokens.

```
1911 \tl_new:N \l_siunitx_number_valid_tl
```

(End definition for `\l_siunitx_number_valid_t1`.)

`\siunitx_if_number:nTF` Test if an entire number is valid: this means parsing the number but not returning anything.

```
1912 \prg_new_protected_conditional:Npnn \siunitx_if_number:n #1
1913   { T , F , TF }
1914   {
1915     \group_begin:
1916       \bool_set_true:N \l_siunitx_number_validate_bool
1917       \bool_set_true:N \l_siunitx_number_parse_bool
1918       \siunitx_number_parse:nN {#1} \l_siunitx_number_parsed_t1
1919       \tl_if_empty:NTF \l_siunitx_number_parsed_t1
1920       {
1921         \group_end:
1922         \prg_return_false:
1923       }
1924       {
1925         \group_end:
1926         \prg_return_true:
1927       }
1928 }
```

(End definition for `\siunitx_if_number:nTF`. This function is documented on page 40.)

A simple conditional to answer the question of whether a specific token is possibly valid in a number.

`\siunitx_if_number_token:N`

```
1929 \prg_new_conditional:Npnn \siunitx_if_number_token:N #1
1930   { p , T , F , TF }
1931   {
1932     \__siunitx_number_if_token_auxi:NN #1
1933       \l_siunitx_number_input_decimal_tl
1934       \l_siunitx_number_input_uncert_close_tl
1935       \l_siunitx_number_input_comparator_tl
1936       \l_siunitx_number_input_digit_tl
1937       \l_siunitx_number_input_exponent_tl
1938       \l_siunitx_number_input_ignore_tl
1939       \l_siunitx_number_input_uncert_open_tl
1940       \l_siunitx_number_input_sign_tl
1941       \l_siunitx_number_input_uncert_sign_tl
1942       \q_recursion_tail
1943       \q_recursion_stop
1944   }
1945 \cs_new:Npn \__siunitx_number_token_auxi:NN #1#2
1946   {
1947     \quark_if_recursion_tail_stop_do:Nn #2 { \prg_return_false: }
1948     \__siunitx_number_token_auxii:NN #1 #2
1949     \__siunitx_number_token_auxi:NN #1
1950   }
1951 \cs_new:Npn \__siunitx_number_token_auxii:NN #1#2
1952   {
1953     \exp_after:wN \__siunitx_number_token_auxiii:NN \exp_after:wN #1
1954     #2 \q_recursion_tail \q_recursion_stop
1955   }
1956 \cs_new:Npn \__siunitx_number_token_auxiii:NN #1#2
```

```

1957  {
1958  \quark_if_recursion_tail_stop:N #2
1959  \str_if_eq:nnT {\#1} {\#2}
1960  {
1961      \use_i_delimit_by_q_recursion_stop:nw
1962      {
1963          \use_i_delimit_by_q_recursion_stop:nw
1964          { \prg_return_true: }
1965      }
1966  }
1967  \_siunitx_number_token_auxii:NN #1
1968 }

```

(End definition for `\siunitx_if_number_token:NTF` and others. This function is documented on page 40.)

2.8 Messages

```

1969 \msg_new:nnn { siunitx } { invalid-number }
1970   { Invalid-number~'#1'. }
1971   {
1972     The~input~'#1'~could~not~be~parsed~as~a~number~following~the~
1973     format~defined~in~module~documentation.
1974 }

```

2.9 Standard settings for module options

Some of these follow naturally from the point of definition (e.g. boolean variables are always `false` to begin with), but for clarity everything is set here.

```

1975 \keys_set:nn { siunitx }
1976   {
1977     bracket-ambiguous-numbers = true ,
1978     bracket-negative-numbers = false ,
1979     drop-exponent = false ,
1980     drop-uncertainty = false ,
1981     drop-zero-decimal = false ,
1982     evaluate-expression = false ,
1983     exponent-base = 10 ,
1984     exponent-mode = input ,
1985     exponent-product = \times ,
1986     expression = #1 ,
1987     fixed-exponent = 0 ,
1988     group-digits = all ,
1989     group-minimum-digits = 5 ,
1990     group-separator = \, , % (
1991     input-close-uncertainty = ) ,
1992     input-comparators = { <=}\approx\ge\geq\gg\le\leq\ll\sim ,
1993     input-decimal-markers = { . } ,
1994     input-digits = 0123456789 ,
1995     input-exponent-markers = dDeE ,
1996     input-ignore = \,
1997     input-open-uncertainty = ( , % )
1998     input-signs = +-}\mp\pm ,
1999     input-uncertainty-signs = \pm ,
2000     minimum-decimal-digits = 0 ,

```

```

2001   minimum-integer-digits      = 0
2002   negative-color            =
2003   output-close-uncertainty = )
2004   output-decimal-marker    = .
2005   output-open-uncertainty = (
2006   parse-numbers           = true
2007   print-implicit-plus     = false
2008   print-unity-mantissa    = true
2009   print-zero-exponent    = false
2010   retain-explicit-plus   = false
2011   retain-zero-uncertainty= false
2012   round-half              = up
2013   round-minimum          = 0
2014   round-mode              = none
2015   round-pad              = true
2016   round-precision         = 2
2017   tight-spacing          = false
2018   uncertainty-mode        = compact
2019   uncertainty-separator  =
2020   }
2021 </package>

```

Part VI

siunitx-print – Printing material with font control

1 Printing quantities

This submodule is focussed on providing controlled printing for numbers and units. Key to this is control of font: conventions for printing quantities mean that the exact nature of the output is important. At the same time, this module provides flexibility for the user in terms of which aspects of the font are responsive to the surrounding general text. Printing material may also take place in text or math mode.

The printing routines assume that normal L^AT_EX 2 _{ε} font selection commands are available, in particular `\bfseries`, `\mathrm`, `\mathversion`, `\fontfamily`, `\fontseries` and `\fontshape`, `\familydefault`, `\seriesdefault`, `\shapedefault` and `\selectfont`. It also requires the standard L^AT_EX 2 _{ε} kernel commands `\ensuremath`, `\mbox`, `\textsubscript` and `\textsuperscript` for printing in text mode. The following packages are also required to provide the functionality detailed.

- `color`: support for color using `\textcolor`
- `textcomp`: `\textminus`, `\textpm` `\texttimes` and `\textcenteredperiod` for printing in text mode
- `amstext`: the `\text` command for printing in text mode

For detection of math mode fonts, as well as `\mathrm`, the existence of `\symoperators` is assumed; other math font commands are not *required* to exist.

```
\siunitx_print_number:n
\siunitx_print_number:(V|x)
\siunitx_print_unit:n
\siunitx_print_unit:(V|x)
```

```
\siunitx_print_number:n {<material>}
\siunitx_print_unit:n {<material>}
```

Prints the `<material>` according the the prevailing settings for the submodule as applicable to the `<type>` of content (`number` or `unit`). The `<material>` should comprise normal L^AT_EX mark-up for numbers or units. In particular, units will typically use `\mathrm` to indicate material to be printed in the current upright roman font, and `^` and `_` will typically be used to indicate super- and subscripts, respectively. These elements will be correctly handled when printing for example using `\mathsf` in math mode, or using only text fonts.

```
\siunitx_print_match:n
\siunitx_print_math:n
\siunitx_print_text:n
```

```
\siunitx_print_match:n {<material>}
\siunitx_print_math:n {<material>}
\siunitx_print_text:n {<material>}
```

Prints the `<material>` as described for `\siunitx_print_...:n` but with a fixed text or math mode output. The printing does *not* set color (which is managed on a `unit/number` basis), but otherwise sets the font as described above. The `match` function uses either the prevailing math or text mode.

1.1 Key–value options

The options defined by this submodule are available within the `\I3keys siunitx` tree.

color `color = <color>`

Color to apply to printed output: the latter should be a named color defined for use with `\textcolor`. The standard setting is empty (no color).

mode `mode = match|math|text`

Selects which mode (math or text) the output is printed in: a choice from the options `match`, `math` or `text`. The option `match` matches the mode prevailing at the point `\siunitx_print_...:n` is called. The `math` and `text` options choose the relevant `TEX` mode for printing. The standard setting is `math`.

number-color `number-color = <color>`

Color to apply to numbers in output: the latter should be a named color defined for use with `\textcolor`. The standard setting is empty (no color).

number-mode `number-mode = match|math|text`

Selects which mode (math or text) the numbers are printed in: a choice from the options `match`, `math` or `text`. The option `match` matches the mode prevailing at the point `\siunitx_prin_number:n` is called. The `math` and `text` options choose the relevant `TEX` mode for printing. The standard setting is `math`.

propagate-math-font `propagate-math-font = true|false`

Switch to determine if the currently-active math font is applied within printed output. This is relevant only when `\siunitx_print_...:n` is called from within math mode: in text mode there is not active math font. When not active, math mode material will be typeset using standard math mode fonts without any changes being made to the supplied argument. The standard setting is `false`.

reset-math-version `reset-math-version = true|false`

Switch to determine whether the active `\mathversion` is reset to `normal` when printing in math mode. Note that math version is typically used to select `\boldsymbol`, though it is also be used by *e.g.* `sansmath`. The standard setting is `true`.

reset-text-family `reset-text-family = true|false`

Switch to determine whether the active text family is reset to `\rmfamily` when printing in text mode. The standard setting is `true`.

reset-text-series `reset-text-series = true|false`

Switch to determine whether the active text series is reset to `\mdseries` when printing in text mode. The standard setting is `true`.

reset-text-shape `reset-text-shape = true|false`

Switch to determine whether the active text shape is reset to `\upshape` when printing in text mode. The standard setting is `true`.

text-family-to-math**text-family-to-math = true|false**

Switch to determine if the family of the current text font should be applied (where possible) to printing in math mode. The standard setting is **false**.

text-font-command**text-font-command = <cmd>**

Command applied to text during output, inserted after any reset of font set-up. This can therefore be used to apply non-standard font set up when printing in text mode. The standard setting is empty.

text-series-to-math**text-series-to-math = true|false**

Switch to determine if the weight of the current text font should be applied (where possible) to printing in math mode. This is achieved by setting the **\mathversion**, and so will override **reset-math-version**. The mappings between text and math weight are set . The standard setting is **false**.

unit-color**unit-color = <color>**

Color to apply to units in output: the latter should be a named color defined for use with **\textcolor**. The standard setting is empty (no color).

unit-mode**unit-mode = match|math|text**

Selects which mode (math or text) units are printed in: a choice from the options **match**, **math** or **text**. The option **match** matches the mode prevailing at the point **\siunitx-print_...:n** is called. The **math** and **text** options choose the relevant **T_EX** mode for printing. The standard setting is **math**.

series-version-mapping**series-version-mapping / <weight> = <version>**

Defines how **siunitx** maps from text font weight to math font version. The pre-defined weights are those used as-standard by **autoinst**:

- **ul**
- **el**
- **l**
- **sl**
- **m**
- **sb**
- **b**
- **eb**
- **ub**

As standard, the **m** weight maps to **normal** math version whilst all of the **b** weights map to **bold** and all of the **l** weights map to **light**.

2 siunitx-print implementation

Start the DocStrip guards.

1 `(*package)`

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

2 `(@=siunitx_print)`

2.1 Initial set up

The printing routines depend on `amstext` for text mode working.

3 `\RequirePackage { amstext }`

Color support is always required.

4 `\RequirePackage { color }`

`\tl_replace_all:NVN` Required variants.

5 `\cs_generate_variant:Nn \tl_replace_all:Nnn { NV }`

(End definition for `\tl_replace_all:NVN`. This function is documented on page ??.)

`\l_siunitx_print_tmp_tl` Scratch space.

6 `\tl_new:N \l_siunitx_print_tmp_tl`

(End definition for `\l_siunitx_print_tmp_tl`.)

2.2 Printing routines

Options which apply to the main formatting routine, and so are not tied to either symbolic or literal input.

7 `\tl_new:N \l_siunitx_print_number_mode_tl`

8 `\tl_new:N \l_siunitx_print_unit_mode_tl`

9 `\keys_define:nn { siunitx }`

10 `{`

11 `color .meta:n =`

12 `{ number-color = #1 , unit-color = #1 } ,`

13 `mode .meta:n =`

14 `{ number-mode = #1 , unit-mode = #1 } ,`

15 `number-color .tl_set:N =`

16 `\l_siunitx_print_number_color_tl ,`

17 `number-mode .choices:nn =`

18 `{ match , math , text }`

19 `{`

20 `\tl_set_eq:NN`

21 `\l_siunitx_print_number_mode_tl \l_keys_choice_tl`

22 `} ,`

23 `propagate-math-font .bool_set:N =`

24 `\l_siunitx_print_math_font_bool ,`

25 `reset-math-version .bool_set:N =`

26 `\l_siunitx_print_math_version_bool ,`

27 `reset-text-family .bool_set:N =`

28 `\l_siunitx_print_text_family_bool ,`

29 `reset-text-series .bool_set:N =`

```

30      \l_siunitx_print_text_series_bool ,
31      reset-text-shape .bool_set:N =
32          \l_siunitx_print_text_shape_bool ,
33          text-family-to-math .bool_set:N =
34              \l_siunitx_print_math_family_bool ,
35              text-font-command .tl_set:N =
36                  \l_siunitx_print_text_font_tl ,
37                  text-series-to-math .bool_set:N =
38                      \l_siunitx_print_math_weight_bool ,
39                      unit-color .tl_set:N =
40                          \l_siunitx_print_unit_color_tl ,
41                          unit-mode .choices:nn =
42                              { match , math , text }
43                              {
44                                  \tl_set_eq:NN
45                                      \l_siunitx_print_unit_mode_tl \l_keys_choice_tl
46                              }
47  }

```

(End definition for `\l_siunitx_print_number_color_tl` and others.)

`\l_siunitx_print_version_ul_tl`

```

48 \keys_define:nn { siunitx / series-version-mapping }
49   {
50     ul . tl_set:N = \l_siunitx_print_version_ul_tl ,
51     el . tl_set:N = \l_siunitx_print_version_el_tl ,
52     l . tl_set:N = \l_siunitx_print_version_l_tl ,
53     sl . tl_set:N = \l_siunitx_print_version_sl_tl ,
54     m . tl_set:N = \l_siunitx_print_version_m_tl ,
55     sb . tl_set:N = \l_siunitx_print_version_sb_tl ,
56     b . tl_set:N = \l_siunitx_print_version_b_tl ,
57     eb . tl_set:N = \l_siunitx_print_version_eb_tl ,
58     ub . tl_set:N = \l_siunitx_print_version_ub_tl
59   }

```

(End definition for `\l_siunitx_print_version_ul_tl` and others.)

`\siunitx_print_number:n`

`\siunitx_print_number:V`

`\siunitx_print_number:x`

`\siunitx_print_unit:n`

`\siunitx_print_unit:V`

`\siunitx_print_unit:x`

`_siunitx_print_aux:nn`

The main printing function doesn't actually need to do very much: just set the color and select the correct sub-function.

```

60 \cs_new_protected:Npn \siunitx_print_number:n #1
61   { \_siunitx_print_aux:nn { number } {#1} }
62 \cs_generate_variant:Nn \siunitx_print_number:n { V , x }
63 \cs_new_protected:Npn \siunitx_print_unit:n #1
64   { \_siunitx_print_aux:nn { unit } {#1} }
65 \cs_generate_variant:Nn \siunitx_print_unit:n { V , x }
66 \cs_new_protected:Npn \_siunitx_print_aux:nn #1#2
67   {
68     \tl_if_empty:cTF { \l_siunitx_print_ #1 _color_tl }
69     { \use:n }
70     { \exp_args:Nv \textcolor { \l_siunitx_print_ #1 _color_tl } { }
71     }
72     \use:c
73     {
74       siunitx_print_

```

```

75           \tl_use:c { l_siunitx_print_ #1 _mode_tl } :n
76       }
77   {
78     }
79 }
```

(End definition for `\siunitx_print_number:n`, `\siunitx_print_unit:n`, and `_siunitx_print_aux:nn`. These functions are documented on page 91.)

`\siunitx_print_match:n`

When the *output* mode should match the input, a simple selection of route can be made.

```

80 \cs_new_protected:Npn \siunitx_print_match:n #1
81   {
82     \mode_if_math:TF
83     { \siunitx_print_math:n {#1} }
84     { \siunitx_print_text:n {#1} }
85   }
```

(End definition for `\siunitx_print_match:n`. This function is documented on page 91.)

`_siunitx_replace_font:N`

A simple auxiliary for “zapping” the unit font.

```

86 \cs_new_protected:Npn \_siunitx_replace_font:N #1
87   {
88     \tl_if_empty:NF \l_siunitx_unit_font_tl
89     {
90       \tl_replace_all:NVn #1
91       \l_siunitx_unit_font_tl
92       { \use:n }
93     }
94 }
```

(End definition for `_siunitx_replace_font:N`.)

Font widths where the `m` for weight is omitted.

```

95 \clist_map_inline:nn { uc , ec , c , sc , sx , x , ex , ux }
96   { \tl_const:cn { c_siunitx_weight_ #1 _tl } { m } }
```

(End definition for `\c_siunitx_weight_uc_tl` and others.)

Font widths with one letter.

```

97 \clist_map_inline:nn { l , m , b }
98   { \tl_const:cn { c_siunitx_weight_ #1 _tl } { #1 } }
```

(End definition for `\c_siunitx_weight_l_tl`, `\c_siunitx_weight_m_tl`, and `\c_siunitx_weight_b_tl`.)

`\siunitx_print_math:n`

The first step in setting in math mode is to check on the math version. The starting point is the question of whether text series needs to propagate to math mode: if so, check on the mapping, otherwise check on the current math version.

```

99 \cs_new_protected:Npn \siunitx_print_math:n #1
100   {
101     \bool_if:NTF \l_siunitx_print_math_weight_bool
102     {
103       \tl_set:Nx \l_siunitx_print_tmp_tl
104       { \exp_after:wN \_siunitx_print_extract_series:Nw \f@series ? \q_stop }
105     \tl_if_empty:NTF \l_siunitx_print_tmp_tl
```

```

106      { \__siunitx_print_math_auxi:n {#1} }
107      { \__siunitx_print_math_version:Vn \l__siunitx_print_tmp_t1 {#1} }
108    }
109    { \__siunitx_print_math_auxi:n {#1} }
110  }

```

Look up the math version from the text series. The weight is omitted if it is `m` plus there are either one or two letters, so we have a little work to do. To keep things fast, we use a hash table based lookup rather than a sequence or property list.

```

111 \cs_new:Npn \__siunitx_print_extract_series:Nw #1#2 ? #3 \q_stop
112   {
113     \cs_if_exist:cTF { c__siunitx_print_weight_ #1#2 _tl }
114     { \__siunitx_print_convert_series:v { c__siunitx_print_weight_ #1#2 _tl } }
115     {
116       \cs_if_exist:cTF { c__siunitx_print_weight_ #1 _tl }
117       { \__siunitx_print_convert_series:v { c__siunitx_print_weight_ #1 _tl } }
118       { \__siunitx_print_convert_series:n {#1#2} }
119     }
120   }
121 \cs_new:Npn \__siunitx_print_convert_series:n #1
122   { \tl_use:c { l__siunitx_print_version_ #1 _tl } }
123 \cs_generate_variant:Nn \__siunitx_print_convert_series:n { v }
124 \cs_new_protected:Npn \__siunitx_print_math_auxi:n #1
125   {
126     \bool_if:NTF \l__siunitx_print_math_version_bool
127     { \__siunitx_print_math_version:nn { normal } {#1} }
128     { \__siunitx_print_math_auxi:n {#1} }
129   }

```

Any setting which changes the math version can only be set from text mode (as it applies at the level of a formula). As such, the first test is to see if that needs to be to check if the math version has to be set: if so, switch to text mode, sort it out and switch back. That of course means that in such cases, line breaking will not be possible.

```

130 \cs_new_protected:Npn \__siunitx_print_math_version:nn #1#2
131   {
132     \str_if_eq:VnTF \math@version { #1 }
133     { \__siunitx_print_math_auxi:n {#2} }
134     {
135       \mode_if_math:TF
136         { \text }
137         { \use:n }
138         {
139           \mathversion {#1}
140           \__siunitx_print_math_auxi:n {#2}
141         }
142       }
143     }
144 \cs_generate_variant:Nn \__siunitx_print_math_version:nn { V }

```

At this point, force math mode then start dealing with setting math font based on text family. If the text family is roman, life is slightly different to if it is sanserif or monospaced. In all cases, the outcomes can be handled using the same routines as for normal math mode treatment. The test here is on a string basis as `\f@family` and the `\...default` commands have different `\long` status.

```

145 \cs_new_protected:Npn \__siunitx_print_math_auxii:n #1
146   { \ensuremath { \__siunitx_print_math_auxiii:n {#1} } }
147 \cs_new_protected:Npn \__siunitx_print_math_auxiii:n #1
148   {
149     \bool_if:NTF \l__siunitx_print_math_family_bool
150     {
151       \str_case_e:nnF { \f@family }
152       {
153         { \rmdefault } { \__siunitx_print_math_auxv:n }
154         { \sfdefault } { \__siunitx_print_math_aux:Nn \mathsf }
155         { \ttdefault } { \__siunitx_print_math_aux:Nn \mathtt }
156       }
157       { \__siunitx_print_math_auxiv:n }
158     }
159     { \__siunitx_print_math_auxiv:n }
160     {#1}
161   }

```

Now we deal with the font selection in math mode. There are two possible cases. First, we are retaining the current math font, and the active one is \mathsf or \mathtt : that needs to be applied to the argument. Alternatively, if the current font is not retained, ensure that normal math mode rules are active.

```

162 \cs_new_protected:Npn \__siunitx_print_math_auxiv:n #1
163   {
164     \bool_if:NTF \l__siunitx_print_math_font_bool
165     { \__siunitx_print_math_aux:N \mathsf \mathtt \q_recursion_tail \q_recursion_stop }
166     { \__siunitx_print_math_auxv:n }
167     {#1}
168   }
169 \cs_new_protected:Npn \__siunitx_print_math_auxv:n #1
170   {
171     \bool_lazy_or:nnTF
172     { \int_compare_p:nNn \fam = { -1 } }
173     { \int_compare_p:nNn \fam = \symoperators }
174     { \use:n }
175     { \mathrm }
176     {#1}
177   }
178 \cs_new_protected:Npn \__siunitx_print_math_aux:N #1
179   {
180     \quark_if_recursion_tail_stop_do:Nn #1 { \use:n }
181     \exp_after:wN \exp_after:wN \exp_after:wN \__siunitx_print_math_aux:w
182     \cs:w \cs_to_str:N #1 \c_space_tl \cs_end:
183     \use@mathgroup ? { -2 } \q_stop #1
184   }
185 \cs_new_protected:Npn \__siunitx_print_math_aux:w #1 \use@mathgroup #2#3 #4 \q_stop #5
186   {
187     \int_compare:nNnTF \fam = {#3}
188     { \use_i_delimit_by_q_recursion_stop:nw { \__siunitx_print_math_aux:Nn #5 } }
189     { \__siunitx_print_math_aux:N }
190   }

```

Search-and-replace fun: deal with any font commands in the argument and also inside sub/superscripts.

```

191 \cs_new_protected:Npx \_siunitx_print_math_aux:Nn #1#2
192 {
193     \group_begin:
194         \tl_set:Nn \exp_not:N \l_siunitx_print_tmp_tl {#2}
195         \_siunitx_print_replace_font:N \exp_not:N \l_siunitx_print_tmp_tl
196         \tl_replace_all:Nnn \exp_not:N \l_siunitx_print_tmp_tl
197             { \char_generate:nn { '\_ } { 8 } }
198             { \exp_not:N \_siunitx_print_math_sub:n }
199         \tl_replace_all:Nnn \exp_not:N \l_siunitx_print_tmp_tl
200             { ^ }
201             { \exp_not:N \_siunitx_print_math_super:n }
202         #1 { \exp_not:N \tl_use:N \exp_not:N \l_siunitx_print_tmp_tl }
203     \group_end:
204 }
205 \cs_generate_variant:Nn \_siunitx_print_math_aux:Nn { c }
206 \cs_new_protected:Npx \_siunitx_print_math_sub:n #1
207 {
208     \char_generate:nn { '\_ } { 8 }
209     { \exp_not:N \_siunitx_print_math_script:n {#1} }
210 }
211 \cs_new_protected:Npn \_siunitx_print_math_super:n #1
212 { ^ { \_siunitx_print_math_script:n {#1} } }
213 \cs_new_protected:Npn \_siunitx_print_math_script:n #1
214 {
215     \group_begin:
216         \tl_set:Nn \l_siunitx_print_tmp_tl {#1}
217         \_siunitx_print_replace_font:N \l_siunitx_print_tmp_tl
218         \tl_use:N \l_siunitx_print_tmp_tl
219     \group_end:
220 }

```

For `tex4ht`, we need to have category code 12 `^` tokens in math mode. We handle that by intercepting at the first auxiliary that makes sense.

```

221 \AtBeginDocument
222 {
223     \@ifpackageloaded { tex4ht }
224     {
225         \cs_set_protected:Npn \_siunitx_print_math_auxii:n #1
226         {
227             \tl_set:Nn \l_siunitx_print_tmp_tl {#1}
228             \exp_args:NNnx \tl_replace_all:Nnn \l_siunitx_print_tmp_tl
229                 { ^ } { \token_to_str:N ^ }
230             \ensuremath { \exp_args:NV \_siunitx_print_math_auxiii:n \l_siunitx_print_tmp_t }
231         }
232     }
233 }
234

```

(End definition for `\siunitx_print_math:n` and others. This function is documented on page 91.)

`\siunitx_print_text:n`

`_siunitx_print_text_replace:`

`_siunitx_print_text_replace:`

`_siunitx_print_text_replace:NNn`

`_siunitx_print_text_sub:n`

`_siunitx_print_text_super:n`

`_siunitx_print_text_scripts:NnN`

`_siunitx_print_text_scripts:`

`_siunitx_print_text_scripts_one:NnN`

`_siunitx_print_text_scripts_two:NnNn`

`_siunitx_print_text_scripts_two:nn`

`_siunitx_print_text_scripts_two:n`

`_siunitx_print_text_fraction:Nnn`

```

238 {
239   \bool_if:NT \l__siunitx_print_text_family_bool
240     { \fontfamily { \familydefault } }
241   \bool_if:NT \l__siunitx_print_text_series_bool
242     { \fontseries { \seriesdefault } }
243   \bool_if:NT \l__siunitx_print_text_shape_bool
244     { \fontshape { \shapedefault } }
245   \bool_lazy_any:nT
246   {
247     { \l__siunitx_print_text_family_bool }
248     { \l__siunitx_print_text_series_bool }
249     { \l__siunitx_print_text_shape_bool }
250   }
251   { \selectfont }
252   \tl_use:N \l__siunitx_print_text_font_tl
253   \exp_args:NnV \tl_if_head_eq_meaning:nNTF {#1} \l_siunitx_unit_fraction_tl
254     { \l__siunitx_print_text_fraction:Nnn #1 }
255     { \l__siunitx_print_text_replace:n {#1} }
256   }
257 }

```

To get math mode material to print in text mode, various search-and-replace steps are needed.

```

258 \cs_new_protected:Npn \l__siunitx_print_text_replace:n #1
259 {
260   \group_begin:
261   \tl_set:Nn \l__siunitx_print_tmp_tl {#1}
262   \l__siunitx_print_text_replace:N \l__siunitx_print_tmp_tl
263   \tl_use:N \l__siunitx_print_tmp_tl
264   \group_end:
265 }
266 \cs_new_protected:Npx \l__siunitx_print_text_replace:N #1
267 {
268   \l__siunitx_print_replace_font:N #1
269   \exp_not:N \l__siunitx_print_text_replace>NNN #1
270     \exp_not:N \mathord { }
271     \exp_not:N \pm
272       { \exp_not:N \textpm }
273     \exp_not:N \mp
274       { \exp_not:n { \ensuremath { \mp } } }
275     -
276       { \exp_not:N \textminus }
277     \exp_not:N \times
278       { \exp_not:N \texttimes }
279     \exp_not:N \cdot
280       { \exp_not:N \textperiodcentered }
281     \char_generate:nn { '_ } { 8 }
282       { \exp_not:N \l__siunitx_print_text_sub:n }
283     ^
284       { \exp_not:N \l__siunitx_print_text_super:n }
285     \exp_not:N \q_recursion_tail
286       { ? }
287     \exp_not:N \q_recursion_stop
288 }

```

```

289 \cs_new_protected:Npn \__siunitx_print_text_replace:Nnn #1#2#3
290 {
291     \quark_if_recursion_tail_stop:N #2
292     \tl_replace_all:Nnn #1 {#2} {#3}
293     \__siunitx_print_text_replace:Nnn #1
294 }

```

When the `bidi` package is loaded, we need to make sure that `\text` is doing the correct thing.

```

295 \sys_if_engine_xetex:T
296 {
297     \AtBeginDocument
298     {
299         \Ifpackageloaded{bidi}{%
300             \cs_set_protected:Npn \__siunitx_print_text_replace:n #1
301             {
302                 \group_begin:
303                     \tl_set:Nn \l__siunitx_print_tmp_tl {#1}
304                     \__siunitx_print_text_replace:N \l__siunitx_print_tmp_tl
305                     \LRE{ \tl_use:N \l__siunitx_print_tmp_tl }
306                 \group_end:
307             }
308         }
309     }
310 }
311 }
312 }

```

Sub- and superscripts can be in any order in the source. The first step of handling them is therefore to do a look-ahead to work out whether only one or both are present.

```

313 \cs_new_protected:Npn \__siunitx_print_text_sub:n #1
314 {
315     \__siunitx_print_text_scripts:NnN
316     \textsubscript{#1} \__siunitx_print_text_super:n
317 }
318 \cs_new_protected:Npn \__siunitx_print_text_super:n #1
319 {
320     \__siunitx_print_text_scripts:NnN
321     \textsuperscript{#1} \__siunitx_print_text_sub:n
322 }
323 \cs_new_protected:Npn \__siunitx_print_text_scripts:NnN #1#2#3
324 {
325     \cs_set_protected:Npn \__siunitx_print_text_scripts:
326     {
327         \if_meaning:w \l_peek_token #3
328             \exp_after:wN \__siunitx_print_text_scripts_two:NnNn
329         \else:
330             \exp_after:wN \__siunitx_print_text_scripts_one:Nn
331         \fi:
332         #1 {#2}
333     }
334     \peek_after:Nw \__siunitx_print_text_scripts:
335 }
336 \cs_new_protected:Npn \__siunitx_print_text_scripts: { }

```

In the simple case of one script item, we have to do a search-and-replace to deal with anything inside the argument.

```

337 \cs_new_protected:Npn \__siunitx_print_text_scripts_one:Nn #1#2
338 {
339   \group_begin:
340     \tl_set:Nn \l__siunitx_print_tmp_tl {#2}
341     \__siunitx_print_text_replace:N \l__siunitx_print_tmp_tl
342     \exp_args:NNV \group_end:
343     #1 \l__siunitx_print_tmp_tl
344 }

```

For the two scripts case, we cannot use `\textsubscript`/`\textsuperscript` as they don't stack directly. Instead, we sort out the ordering then use an implementation for both parts that is the same as the kernel text scripts.

```

345 \cs_new_protected:Npn \__siunitx_print_text_scripts_two:NnNn #1#2#3#4
346 {
347   \cs_if_eq:NNTF #1 \textsubscript
348   {
349     \__siunitx_print_text_scripts_two:nn {#4} {#2} }
350     \__siunitx_print_text_scripts_two:nn {#2} {#4} }
351 }
351 \cs_new_protected:Npx \__siunitx_print_text_scripts_two:nn #1#2
352 {
353   \group_begin:
354     \exp_not:N \m@th
355     \exp_not:N \ensuremath
356     {
357       ^ { \exp_not:N \__siunitx_print_text_scripts_two:n {#1} }
358       \char_generate:nn { '_ } { 8 }
359       { \exp_not:N \__siunitx_print_text_scripts_two:n {#2} }
360     }
361   \group_end:
362 }
363 \cs_new_protected:Npn \__siunitx_print_text_scripts_two:n #1
364 {
365   \mbox
366   {
367     \fontsize \sf@size \z@ \selectfont
368     \__siunitx_print_text_scripts_one:Nn \use:n {#1}
369   }
370 }

```

Fraction commands are always math mode, so we have to go back and forth: this is done after general font setting for performance reasons.

```

371 \cs_new_protected:Npn \__siunitx_print_text_fraction:Nnn #1#2#3
372 {
373   \ensuremath
374   {
375     #1
376     { \mbox { \__siunitx_print_text_replace:n {#2} } }
377     { \mbox { \__siunitx_print_text_replace:n {#3} } }
378   }
379 }

```

(End definition for `\siunitx_print_text:n` and others. This function is documented on page 91.)

2.3 Standard settings for module options

Some of these follow naturally from the point of definition (*e.g.* boolean variables are always `false` to begin with), but for clarity everything is set here.

```
380 \keys_set:nn { siunitx }
381   {
382     color          =      ,
383     mode           = math ,
384     number-color   =      ,
385     number-mode    = math ,
386     propagate-math-font = false ,
387     reset-math-version = true ,
388     reset-text-shape  = true ,
389     reset-text-series = true ,
390     reset-text-family = true ,
391     text-family-to-math = false ,
392     text-font-command =      ,
393     text-series-to-math = false ,
394     unit-color      =      ,
395     unit-mode       = math
396   }
```

These are separate as they all fall inside the same key.

```
397 \keys_set:nn { siunitx / series-version-mapping }
398   {
399     ul = light ,
400     el = light ,
401     l  = light ,
402     sl = light ,
403     m  = normal ,
404     sb = bold ,
405     b  = bold ,
406     eb = bold ,
407     ub = bold
408   }
409 </package>
```

Part VII

siunitx-quantity – Quantities

This submodule is focussed on providing controlled printing for quantities: the combination of a number and a unit. It largely builds on the submodules `siunitx-number` and `siunitx-unit`. A small number of adjustments are made to standard set up in the latter to reflect additional functionality added here.

`\siunitx_quantity:nn` `\siunitx_quantity:nn {<number>} {<unit>}`

Parses the `<number>` and the `<unit>` as detailed for `\siunitx_number_parse:nN` and `\siunitx_unit_format:nN`, the prints the results using `\siunitx_print_unit:n`.

`\siunitx_quantity_print:nn` `\siunitx_quantity_print:nn {<number>} {<unit>}`
`\siunitx_quantity_print:(nV|VV|xV)`

A low-level function which prints the quantity directly: there is no processing applied to either the `<number>` or `<unit>`. The two parts are printed using `\siunitx_print_unit:n` and appropriate spacing and break-prevention is applied.

`allow-quantity-breaks` `allow-quantity-breaks = true|false`

Specifies whether breaks are permitted between units. The standard setting is `false`.

`prefix-mode` `prefix-mode = combine-exponent|extract-exponent|input`

Selects the method used for producing prefixes: a choice from the options `combine-exponent`, `extract-exponent` and `input`. The option `combine-exponent` combines any exponent from the number with the prefix of the first unit, and prints the updated prefix. The option `extract-exponent` removes all prefixes from the unit, and combines them with the exponent of number. The option `input` prints prefixes and exponent as given in the source. The standard setting is `input`.

`quantity-product` `quantity-product = <tokens>`

The product marker used between a number and the unit. The standard setting is `\,.`

`separate-uncertainty-units` `separate-uncertainty-units = bracket|repeat|single`

Specifies how units are applied when a separated uncertainty is present: a choice from `bracket`, `repeat` and `single`. The option `bracket` places brackets around the number, with the unit given after these. The option `repeat` means that the unit is printed with the main value and with the uncertainty. When `single` is set, the unit is printed only once and no brackets are applied. The standard setting is `bracket`.

1 siunitx-quantity implementation

Start the DocStrip guards.

`_ (*package)`

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

`_ (@@=siunitx_quantity)`

1.1 Initial set-up

Scratch space.

```
3 \tl_new:N \l_siunitx_quantity_tmp_fp  
4 \tl_new:N \l_siunitx_quantity_tmp_tl
```

(End definition for `\l_siunitx_quantity_tmp_fp` and `\l_siunitx_quantity_tmp_tl`.)

1.2 Main formatting routine

Purely internal for the present.

```
5 \tl_new:N \l_siunitx_quantity_bracket_close_tl  
6 \tl_new:N \l_siunitx_quantity_bracket_open_tl  
7 \tl_set:Nn \l_siunitx_quantity_bracket_open_tl { () }  
8 \tl_set:Nn \l_siunitx_quantity_bracket_close_tl { () }
```

(End definition for `\l_siunitx_quantity_bracket_close_tl` and `\l_siunitx_quantity_bracket_open_tl`.)

`\l_siunitx_quantity_prefix_mode_tl`

```
9 \tl_new:N \l_siunitx_quantity_prefix_mode_tl  
10 \bool_new:N \l_siunitx_quantity_uncert_bracket_bool  
11 \bool_new:N \l_siunitx_quantity_uncert_repeat_bool  
12 \keys_define:nn { siunitx }  
13 {  
14   allow-quantity-breaks .bool_set:N =  
15   \l_siunitx_quantity_break_bool ,  
16   prefix-mode .choices:nn =  
17   { combine-exponent , extract-exponent , input }  
18   { \tl_set_eq:NN \l_siunitx_quantity_prefix_mode_tl \l_keys_choice_tl } ,  
19   quantity-product .tl_set:N =  
20   \l_siunitx_quantity_product_tl ,  
21   separate-uncertainty-units .choice: ,  
22   separate-uncertainty-units / bracket .code:n =  
23   {  
24     \bool_set_true:N \l_siunitx_quantity_uncert_bracket_bool  
25     \bool_set_false:N \l_siunitx_quantity_uncert_repeat_bool  
26   } ,  
27   separate-uncertainty-units / repeat .code:n =  
28   {  
29     \bool_set_false:N \l_siunitx_quantity_uncert_bracket_bool  
30     \bool_set_true:N \l_siunitx_quantity_uncert_repeat_bool  
31   } ,  
32   separate-uncertainty-units / single .code:n =  
33   {  
34     \bool_set_false:N \l_siunitx_quantity_uncert_bracket_bool  
35     \bool_set_false:N \l_siunitx_quantity_uncert_repeat_bool  
36   }  
37 }
```

(End definition for `\l_siunitx_quantity_prefix_mode_tl` and others. This variable is documented on page ??.)

```

\l_siunitx_quantity_number_tl
\l_siunitx_quantity_unit_tl
38 \tl_new:N \l_siunitx_quantity_number_tl
39 \tl_new:N \l_siunitx_quantity_unit_tl

(End definition for \l_siunitx_quantity_number_tl and \l_siunitx_quantity_unit_tl.)

```

\siunitx_quantity:nn
 $_siunitx_quantity_parsed:nn$
 $_siunitx_quantity_parsed_combine-exponent:n$
 $_siunitx_quantity_parsed_combine-exponent:n$

```

\l_siunitx_quantity_parsed_input:n
\l_siunitx_quantity_parsed_aux:w
\l_siunitx_quantity_parsed_aux:mmw
\l_siunitx_quantity_parsed_aux:nnn
40 \cs_new_protected:Npn \siunitx_quantity:nn #1#2
41 {
42   \group_begin:
43     \siunitx_unit_options_apply:n {#2}
44     \tl_if_blank:nTF {#1}
45     {
46       \siunitx_unit_format:nN {#2} \l_siunitx_quantity_unit_tl
47       \siunitx_print_unit:V \l_siunitx_quantity_unit_tl
48     }
49     {
50       \bool_if:NTF \l_siunitx_number_parse_bool
51         { \l_siunitx_quantity_parsed:nn {#1} {#2} }
52         {
53           \tl_set:Nn \l_siunitx_quantity_number_tl { \ensuremath {#1} }
54           \siunitx_unit_format:nN {#2} \l_siunitx_quantity_unit_tl
55           \siunitx_quantity_print:VV
56             \l_siunitx_quantity_number_tl \l_siunitx_quantity_unit_tl
57         }
58     }
59   \group_end:
60 }
```

For parsed numbers, we have two major questions to think about: whether we are combining prefixes, and whether we have a multi-part numbers to handle. Number processing has to be delayed it needs to come after any extracted exponent is combined.

```

61 \cs_new_protected:Npn \l_siunitx_quantity_parsed:nn #1#2
62 {
63   \bool_set_false:N \l_siunitx_number_bracket_ambiguous_bool
64   \siunitx_number_parse:nN {#1} \l_siunitx_quantity_number_tl
65   \use:c { _siunitx_quantity_parsed_ \l_siunitx_quantity_prefix_mode_tl :n } {#2}
66   \tl_set:Nx \l_siunitx_quantity_number_tl
67   { \siunitx_number_output:NN \l_siunitx_quantity_number_tl \q_nil }
68   \exp_after:wN \l_siunitx_quantity_parsed_aux:w \l_siunitx_quantity_number_tl \q_stop
69 }
70 \cs_new_protected:cpx { _siunitx_quantity_parsed_combine-exponent:n } #1
71 {
72   \siunitx_number_process:NN \l_siunitx_quantity_number_tl \l_siunitx_quantity_number_tl
73   \exp_args:NV \l_siunitx_quantity_extract_exp:nNN
74   \l_siunitx_quantity_number_tl \l_siunitx_quantity_tmp_fp \l_siunitx_quantity_number_
75   \siunitx_unit_format_combine_exponent:nnN {#1}
76   \l_siunitx_quantity_tmp_fp \l_siunitx_quantity_unit_tl
77 }
78 \cs_new_protected:cpx { _siunitx_quantity_parsed_extract-exponent:n } #1
79 {
```

```

80   \siunitx_unit_format_extract_prefixes:nNN {#1}
81     \l_siunitx_quantity_unit_tl \l_siunitx_quantity_tmp_fp
82   \tl_set:Nx \l_siunitx_quantity_number_tl
83   {
84     \siunitx_number_adjust_exponent:Nn
85       \l_siunitx_quantity_number_tl \l_siunitx_quantity_tmp_fp
86   }
87   \siunitx_number_process:NN \l_siunitx_quantity_number_tl \l_siunitx_quantity_number_tl
88 }
89 \cs_new_protected:Npn \_siunitx_quantity_parsed_input:n #1
90 {
91   \siunitx_number_process:NN \l_siunitx_quantity_number_tl \l_siunitx_quantity_number_tl
92   \siunitx_unit_format:nN {#1} \l_siunitx_quantity_unit_tl
93 }

```

To find out if we need to work harder, we first need to split the formatted number into the constituent parts. That is done using the table-like approach: that avoids needing to both check the settings and break down the input separately.

```

94 \cs_new_protected:Npn \_siunitx_quantity_parsed_aux:w
95   #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_nil #5 \q_nil #6 \q_nil #7 \q_nil
96   #8 \q_nil #9 \q_stop
97   { \_siunitx_quantity_parsed_aux:nnnw {#1} {#2#3#4#5} {#6#7#8} #9 \q_stop }
98 \cs_new_protected:Npn \_siunitx_quantity_parsed_aux:nnnw
99   #1#2#3 #4 \q_nil #5 \q_nil #6 \q_stop
100  { \_siunitx_quantity_parsed_aux:nnnn {#1} {#2} {#3#4} {#5#6} }
101 \cs_new_protected:Npn \_siunitx_quantity_parsed_aux:nnnn #1#2#3#4
102  {
103   \tl_if_blank:nTF {#3}
104     { \siunitx_quantity_print:nV {#1#2#4} \l_siunitx_quantity_unit_tl }
105   {
106     \bool_if:NTF \l_siunitx_quantity_uncert_bracket_bool
107     {
108       \siunitx_quantity_print:xV
109       {
110         \exp_not:n {#1}
111         \exp_not:V \l_siunitx_quantity_bracket_open_tl
112         \exp_not:n {#2#3}
113         \exp_not:V \l_siunitx_quantity_bracket_close_tl
114         \exp_not:n {#4}
115       }
116       \l_siunitx_quantity_unit_tl
117     }
118   {
119     \bool_if:NTF \l_siunitx_quantity_uncert_repeat_bool
120     {
121       \siunitx_quantity_print:nV {#1#2}
122         \l_siunitx_quantity_unit_tl
123       \siunitx_quantity_print:nV { { } #3 }
124         \l_siunitx_quantity_unit_tl
125       \siunitx_print_number:n { { } #4 }
126     }
127     { \siunitx_quantity_print:nV {#1#2#3#4} \l_siunitx_quantity_unit_tl }
128   }
129 }

```

```
130 }
```

(End definition for `_siunitx_quantity:nn` and others. This function is documented on page 104.)

To extract the exponent part for a combined prefix, we decompose the value and remove it.

```
131 \cs_new_protected:Npn \_siunitx_quantity_extract_exp:nNN #1#2#3
132   { \_siunitx_quantity_extract_exp:nnnnnnnNN #1 #2 #3 }
133 \cs_new_protected:Npn \_siunitx_quantity_extract_exp:nnnnnnnNN #1#2#3#4#5#6#7#8#9
134   {
135     \fp_set:Nn #8 {#6#7}
136     \tl_set:Nx #9
137     { {#1} {#2} {#3} {#4} {#5} { } { 0 } }
138   }
```

(End definition for `_siunitx_quantity_extract_exp:nNN` and `_siunitx_quantity_extract_exp:nnnnnnnNN`.)

`\siunitx_quanity_print:nn`
`\siunitx_quanity_print:nV`
`\siunitx_quanity_print:VV`
`\siunitx_quanity_print:xV` For printing a single part of a quantity. This is needed for compound quantities and so is public: that's also the reason for passing both argument explicitly.

```
139 \cs_new_protected:Npn \siunitx_quantity_print:nn #1#2
140   {
141     \siunitx_print_number:n {#1}
142     \tl_if_blank:nF {#2}
143     {
144       \tl_use:N \l__siunitx_quantity_product_tl
145       \bool_if:NTF \l__siunitx_quantity_break_bool
146         { \penalty \binoppenalty }
147         { \nobreak }
148       \siunitx_print_unit:n {#2}
149     }
150   }
151 \cs_generate_variant:Nn \siunitx_quantity_print:nn { nV , VV , xV }
```

(End definition for `\siunitx_quanity_print:nn`. This function is documented on page ??.)

1.3 Standard settings for module options

Some of these follow naturally from the point of definition (e.g. boolean variables are always `false` to begin with), but for clarity everything is set here.

```
152 \keys_set:nn { siunitx }
153   {
154     allow-quantity-breaks      = false ,
155     prefix-mode                = input ,
156     quantity-product           = \, ,
157     separate-uncertainty-units = bracket
158 }
```

1.4 Adjustments to units

As in `siunitx-unit`, but internal in both cases as it's rather specialised.

```
159 \bool_lazy_or:nnTF
160   { \sys_if_engine_luatex_p: }
161   { \sys_if_engine_xetex_p: }
162   {
```

```

163   \cs_new:Npn \__siunitx_quantity_non_latin:n #1
164     { \char_generate:nn {#1} { \char_value_catcode:n {#1} } }
165   }
166   {
167     \cs_new:Npn \__siunitx_quantity_non_latin:n #1
168     {
169       \exp_last_unbraced:Nf \__siunitx_quantity_non_latin:nnnn
170         { \char_to_utfviii_bytes:n {#1} }
171     }
172     \cs_new:Npn \__siunitx_quantity_non_latin:nnnn #1#2#3#4
173     {
174       \exp_after:wN \exp_after:wN \exp_after:wN
175         \exp_not:N \char_generate:nn {#1} { 13 }
176       \exp_after:wN \exp_after:wN \exp_after:wN
177         \exp_not:N \char_generate:nn {#2} { 13 }
178     }
179   }

```

(End definition for `__siunitx_quantity_non_latin:n` and `__siunitx_quantity_non_latin:nnnn`.)

\degree The `\degree` unit is re-declared here: this is needed for using it in quantities. This is done here as it avoids a dependency in `siunitx-unit` on options it does not contain.

```

180 \siunitx_declare_unit:Nxn \degree
181   { \__siunitx_quantity_non_latin:n { "00B0" } }
182   { quantity-product = { } }

```

(End definition for `\degree`. This function is documented on page 142.)

```
183 
```

Part VIII

siunitx-symbol – Symbol-related settings

1 siunitx-symbol implementation

Start the DocStrip guards.

`1 {*package}`

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

`2 (@@=siunitx_symbol)`

`\l_siunitx_symbol_tma_t1` Scratch space.

`\l_siunitx_symbol_tmpb_t1`
`3 \tl_new:N \l_siunitx_symbol_tma_t1`
`4 \tl_new:N \l_siunitx_symbol_tmpb_t1`

(End definition for `\l_siunitx_symbol_tma_t1` and `\l_siunitx_symbol_tmpb_t1`.)

A small number of commands are needed from the companion fonts when working with 8-bit engines. These are loaded by modern L^AT_EX 2_E kernel, so for older ones, force loading them using `textcomp`.

```
5 \AtBeginDocument
6   {
7     \cs_if_free:cT { TOTS1 }
8     { \RequirePackage { textcomp } }
9   }
```

As in `siunitx-unit`, but internal in both cases as it's rather specialised.

```
10 \bool_lazy_or:nnTF
11   { \sys_if_engine_luatex_p: }
12   { \sys_if_engine_xetex_p: }
13   {
14     \cs_new:Npn \__siunitx_symbol_non_latin:n #1
15     { \char_generate:nn {#1} { \char_value_catcode:n {#1} } }
16   }
17   {
18     \cs_new:Npn \__siunitx_symbol_non_latin:n #1
19     {
20       \exp_last_unbraced:Nf \__siunitx_symbol_non_latin:nnnn
21       { \char_to_utfviii_bytes:n {#1} }
22     }
23     \cs_new:Npn \__siunitx_symbol_non_latin:nnnn #1#2#3#4
24     {
25       \__siunitx_symbol_deal_with_utf:
26       \exp_after:wN \exp_after:wN \exp_after:wN
27         \exp_not:N \char_generate:nn {#1} { 13 }
28       \exp_after:wN \exp_after:wN \exp_after:wN
29         \exp_not:N \char_generate:nn {#2} { 13 }
30     }
31   }
32 \cs_new:Npn \__siunitx_symbol_deal_with_utf: { }
```

(End definition for `_siunitx_symbol_non_latin:n` and `_siunitx_symbol_non_latin:nnnn`.)

`_siunitx_symbol_if_replace:NnT` A test to see if the unit definition which applies is still one we expect: here that means it is just using a (Unicode) codepoint. The comparison is string-based as `unicode-math` (at least) can alter some of them. Active characters are set to `\scan_stop:` so that the code here gives exactly the tokens (bytes) we want: needed for encodings other than UTF-8.

```

33 \prg_new_protected_conditional:Npnn \_siunitx_symbol_if_replace:Nn #1#2 { T , TF }
34 {
35   \group_begin:
36     \protected@edef \l_siunitx_symbol_tmpa_tl
37       { \exp_not:N \mathrm { \_siunitx_symbol_non_latin:n {#2} } }
38     \int_step_inline:nnn { "80 } { "FF }
39       { \char_set_active_eq:nN {##1} \scan_stop: }
40     \keys_set:nn { siunitx } { parse-units = false }
41     \siunitx_unit_format:nn {#1} \l_siunitx_symbol_tmpb_tl
42     \str_if_eq:VVTF \l_siunitx_symbol_tmpa_tl \l_siunitx_symbol_tmpb_tl
43     {
44       \group_end:
45       \prg_return_true:
46     }
47   {
48     \group_end:
49     \prg_return_false:
50   }
51 }
```

(End definition for `_siunitx_symbol_if_replace:NnT`.)

At the start of the document, fonts are fixed and the user may have altered unit set up. If things are unchanged, we can alter the settings such that they use something “more sensible”.

```

52 \AtBeginDocument
53 {
54   \_siunitx_symbol_if_replace:NnT \arcminute { "02B9 }
55   {
56     \siunitx_declare_unit:Nn \arcminute
57       { \exp_not:N \ensuremath { \{ \} ' } }
58   }
59   \_siunitx_symbol_if_replace:NnT \arcsecond { "02BA }
60   {
61     \siunitx_declare_unit:Nn \arcsecond
62       { \exp_not:N \ensuremath { \{ \} '' } }
63 }
```

For `\degree`, direct input works in text mode so there is only a need to tidy up for math mode. If `fontspec` is loaded then that problem goes away, so nothing needs to be done.

```

64   \_siunitx_symbol_if_replace:NnT \degree { "00B0 }
65   {
66     \@ifpackageloaded { fontspec }
67       { }
68     {
69       \siunitx_declare_unit:Nxn \degree
70         {
71           \exp_not:N \text
72             { }
```

```

73           \@ifpackageloaded { inputenc }
74             { \exp_not:N \textdegree }
75             { \_siunitx_symbol_non_latin:n { "00B0 } }
76         }
77     }
78   { quantity-product = { } }
79 }
80 }
```

For `\degreeCelsius`, much the same to think about but the comparison must be done by hand.

```

81   \group_begin:
82     \tl_set:Nx \l_siunitx_symbol_tmpa_tl { \_siunitx_symbol_non_latin:n { "00B0 } C }
83     \protected@edef \l_siunitx_symbol_tmpa_tl
84       { \exp_not:N \mathrm { \l_siunitx_symbol_tmpa_tl } }
85     \keys_set:nn { siunitx } { parse-units = false }
86     \siunitx_unit_format:nn { \degreeCelsius } \l_siunitx_symbol_tmpb_tl
87     \str_if_eq:VVT \l_siunitx_symbol_tmpa_tl \l_siunitx_symbol_tmpb_tl
88     {
89       \group_end:
90       \ifpackageloaded { fontspec }
91         { }
92         {
93           \siunitx_declare_unit:Nx \degreeCelsius
94             {
95               \exp_not:N \text
96               {
97                 \ifpackageloaded { inputenc }
98                   { \exp_not:N \textdegree }
99                   { \_siunitx_symbol_non_latin:n { "00B0 } }
100             }
101             C
102           }
103         }
104     }
105   { \group_end: }
```

For `\ohm`, there is a math mode symbol we can use, so there has to be a mode-dependent definition.

```

106   \_siunitx_symbol_if_replace:NnT \ohm { "03A9 }
107   {
108     \siunitx_declare_unit:Nx \ohm
109     {
110       \exp_not:N \ifmmode
111         \cs_if_exist:NTF \upOmega
112           { \exp_not:N \upOmega }
113           { \exp_not:N \Omega }
114       \exp_not:N \else
115         \exp_not:N \text
116         {
117           \bool_lazy_or:nnTF
118             { \sys_if_engine_luatex_p: }
119             { \sys_if_engine_xetex_p: }
120             { \_siunitx_symbol_non_latin:n { "03A9 } }
121             { \exp_not:N \textohm }
```

```

122         }
123         \exp_not:N \fi
124     }
125 }
```

Only a text mode command is available for `\micro` in the standard set up.

```

126 \__siunitx_symbol_if_replace:NnT \micro { "03BC }
127 {
128     \siunitx_declare_prefix:Nnx \micro { -6 }
129     {
130         \exp_not:N \text
131         {
132             \bool_lazy_or:nnTF
133             {
134                 \sys_if_engine_luatex_p:
135             }
136             {
137                 \__siunitx_symbol_non_latin:n { "00B5 } }
138             {
139                 \exp_not:N \textmu
140             }
141 }
```

1.1 Bookmark definitions

Inside PDF strings we disable the text printing function. The definition of `\ohm` is also reset as otherwise engine-dependent strings are generated (X_ET_EX and Lu_AT_EX give different outcomes using for example `\textohm`).

```

141 \AtBeginDocument
142 {
143     \@ifpackageloaded { hyperref }
144     {
145         \exp_args:Nx \pdfstringdefDisableCommands
146         {
147             \cs_set_eq:NN \siunitx_print_text:n \exp_not:N \use:n
148             \siunitx_declare_unit:Nn \exp_not:N \ohm
149             {
150                 \__siunitx_symbol_non_latin:n { "03A9 } }
151             }
152             {
153             }
154 }
```

Part IX

siunitx-table – Formatting numbers in tables

1 Numbers in tables

This submodule is concerned with formatting numbers in table cells or similar fixed-width contexts. The main function, `\siunitx_cell_begin:w`, is designed to work with the normal L^AT_EX 2_< tabular cell construct featuring `\ignorespaces`. Therefore, if used outside of a L^AT_EX 2_< tabular, it is necessary to provide this token.

```
\siunitx_cell_begin:w
\siunitx_cell_end:
```

Collects the `<preamble>` and `<content>` tokens, and determines if it is text or a number (as parsed by `\siunitx_number_parse:nN`). It produces output of a fixed width suitable for alignment in a table, although it is not *required* that the code is used within a cell. Note that `\ignorespaces` must occur in the “cell”: it marks the end of the TeX `\halign` template.

1.1 Key–value options

The options defined by this submodule are available within the l3keys `siunitx` tree.

```
table-align-comparator
```

```
table-align-comparator = true|false
```

Switch which determines whether alignment of comparators is attempted within table cells. The standard setting is `true`.

```
table-align-exponent
```

```
table-align-exponent = true|false
```

Switch which determines whether alignment of exponents is attempted within table cells. The standard setting is `true`.

```
table-align-text-after
```

```
table-align-text-after = true|false
```

Switch which determines whether alignment of text falling after a number is attempted within table cells. The standard setting is `true`.

```
table-align-text-before
```

```
table-align-text-before = true|false
```

Switch which determines whether alignment of text falling before a number is attempted within table cells. The standard setting is `true`.

```
table-align-uncertainty
```

```
table-align-uncertainty = true|false
```

Switch which determines whether alignment of separated uncertainty values is attempted within table cells. The standard setting is `true`.

table-alignment**table-alignment** = center|left|right

Selects the alignment of all tabular content with the margins of the table cell (or other boundary). See also **table-number-alignment** and **table-text-alignment**. The standard setting is **center**.

table-alignment-mode**table-alignment-mode** = format|marker|none

Selects the method used to align numbers with the desired position in the cell (set by **table-alignment**). When set to **format**, a dedicated amount of space is calculated from the **table-format**. When **marker** is selected, alignment is carried out symmetrically around the decimal marker. Finally, **none** switches off all alignment: numbers are parsed and formatted but with no attempt at placement within the cell. The standard setting is **marker**.

table-auto-round**table-auto-round** = true|false

Switch which determines whether numbers are rounded to fit within the **table-format** specification (if possible). The standard setting is **false**.

table-column-width**table-column-width** = *<width>*

Sets the width of the table column used for numbers. This is only used when **table-fixed-width** is **true**.

table-fixed-width**table-fixed-width** = true|false

Switch which determines whether a fixed-width column is used for numbers in tables. When **true**, the width is taken from **table-column-width**. The standard setting is **false**.

table-format**table-format** = *<format>*

Describes the amount of space that should be reserved when **table-alignment-mode** is set to **format**. The *<format>* takes the same general form as input for a table cell, with the numerical parts describing how many digits to reserve space for. For example, `1.2e3` would allow space for one digit in the integer part, two in the decimal part and three in the exponent part. Signs can be allowed for using any valid input sign, so for example `+1.2 \pm 1.2` would allow for a sign, a number with one integer and two decimal digits and an uncertainty of the same size.

table-number-alignment**table-number-alignment** = center|left|right

Selects the alignment of numerical content with the margins of the table cell (or other boundary). See also **table-alignment** and **table-text-alignment**. The standard setting is **center**.

table-text-alignment**table-text-alignment** = center|left|right

Selects the alignment of non-numerical content with the margins of the table cell (or other boundary). See also **table-alignment** and **table-number-alignment**. The standard setting is **center**.

2 siunitx-table implementation

Start the DocStrip guards.

1 `(*package)`

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

2 `(@=siunitx_table)`

Scratch space.

3 `\box_new:N \l_siunitx_table_tmp_box`
4 `\dim_new:N \l_siunitx_table_tmp_dim`
5 `\tl_new:N \l_siunitx_table_tmp_tl`

(End definition for `\l_siunitx_table_tmp_box`, `\l_siunitx_table_tmp_dim`, and `\l_siunitx_table_tmp_tl`.)

2.1 Interface functions

`\l_siunitx_table_text_bool` Used to track that a cell is purely text.
6 `\bool_new:N \l_siunitx_table_text_bool`

(End definition for `\l_siunitx_table_text_bool`.)

`\siunitx_cell_begin:w` The start and end of the cell need to deal with the possibility of a cell containing only text.
`\siunitx_cell_end:`

7 `\cs_new_protected:Npn \siunitx_cell_begin:w`
8 `{`
9 `\bool_set_false:N \l_siunitx_table_text_bool`
10 `\bool_if:NTF \l_siunitx_number_parse_bool`
11 `\l_siunitx_table_collect_begin: }`
12 `\l_siunitx_table_direct_begin: }`
13 `}`
14 `\cs_new_protected:Npn \siunitx_cell_end:`
15 `{`
16 `\bool_if:NF \l_siunitx_table_text_bool`
17 `\bool_if:NTF \l_siunitx_number_parse_bool`
18 `\l_siunitx_table_collect_end: }`
19 `\l_siunitx_table_direct_end: }`
20 `}`
21 `}`
22 `}`

(End definition for `\siunitx_cell_begin:w` and `\siunitx_cell_end:`. These functions are documented on page 114.)

2.2 Collecting tokens

`\l_siunitx_table_collect_tl` Space for tokens.
23 `\tl_new:N \l_siunitx_table_collect_tl`

(End definition for `\l_siunitx_table_collect_tl`.)

```
\_siunitx_table_collect_begin:
\_siunitx_table_collect_begin:w
```

Collecting a tabular cell means doing a token-by-token collection. In previous versions of `siunitx` that was done along with picking out the numerical part, but the code flow ends up very tricky. Here, therefore, we just collect up the unchanged tokens first. The definition of `\cr` is used to allow collection of any tokens inserted after the main content when dealing with the last cell of a row: the “group” around it is needed to avoid issues with the underlying `\halign`. (The approach is based on that in `colcell`.) Whilst the group formed by a cell will normally tidy up `\cr`, we add an extra one as the collected material could be a tabular in itself. We use an auxiliary to fish out the `\ignorespaces` from the template: that has to go to avoid issues with the peek-ahead code (everything before the `#` needs to be read *before* the Appendix D trick gets applied). Some packages add additional tokens before the `\ignorespaces`, which are dealt with by the delimited argument.

```
24 \cs_new_protected:Npn \_siunitx_table_collect_begin:
25   {
26     \group_begin:
27       \tl_clear:N \l_siunitx_table_collect_tl
28       \if_false: { \fi:
29         \cs_set_protected:Npn \cr
30         {
31           \_siunitx_table_collect_loop:
32           \tex_cr:D
33         }
34         \if_false: } \fi:
35         \_siunitx_table_collect_begin:w
36     }
37 \cs_new_protected:Npn \_siunitx_table_collect_begin:w #1 \ignorespaces
38   { \_siunitx_table_collect_loop: #1 }
```

(End definition for `_siunitx_table_collect_begin:` and `_siunitx_table_collect_begin:w`.)

```
\_siunitx_table_collect_loop:
\_siunitx_table_collect_group:n
\_siunitx_table_collect_token:N
\_siunitx_table_collect_token_aux:N
\_siunitx_table_collect_relax:N
\_siunitx_table_collect_search:NnF
\_siunitx_table_collect_search_aux:NnN
```

Collecting up the cell content needs a loop: this is done using a `peek` approach as it’s most natural. (A slower approach is possible using something like the `\text_lowercase:n` loop code.) The set of possible tokens is somewhat limited compared to an arbitrary cell (*cf.* the approach in `colcell`): the special cases are pulled out for manual handling. The flexible lookup approach is more-or-less the same idea as in the kernel `case` functions. The `\relax` special case covers the case where `\` has been expanded in an empty cell. This has to be an explicit token as we can get the same meaning from `\protect`.

```
39 \cs_new_protected:Npn \_siunitx_table_collect_loop:
40   {
41     \peek_catcode_ignore_spaces:NTF \c_group_begin_token
42     { \_siunitx_table_collect_group:n }
43     { \_siunitx_table_collect_token:N }
44   }
45 \cs_new_protected:Npn \_siunitx_table_collect_group:n #1
46   {
47     \tl_put_right:Nn \l_siunitx_table_collect_tl { {#1} }
48     \_siunitx_table_collect_loop:
49   }
50 \cs_new_protected:Npn \_siunitx_table_collect_token:N #1
51   {
52     \_siunitx_table_collect_search:NnF #1
53     {
54       \unskip
55       { \_siunitx_table_collect_loop: }
```

```

55      \end          { \tabularnewline \end }
56      \relax         { \_siunitx_table_collect_relax:N #1 }
57      \tabularnewline { \tabularnewline }
58      \siunitx_cell_end: { \siunitx_cell_end: }
59    }
60    { \_siunitx_table_collect_token_aux:N #1 }
61  }
62 \cs_new_protected:Npn \_siunitx_table_collect_token_aux:N #1
63 {
64   \tl_put_right:Nn \l_siunitx_table_collect_tl {#1}
65   \_siunitx_table_collect_loop:
66 }
67 \cs_new_protected:Npn \_siunitx_table_collect_relax:N #1
68 {
69   \str_if_eq:nnTF {#1} { \relax }
70   { \relax }
71   { \_siunitx_table_collect_token_aux:N #1 }
72 }
73 \AtBeginDocument
74 {
75   @ifpackageloaded { mdwtab }
76   {
77     \cs_set_protected:Npn \_siunitx_table_collect_token:N #1
78     {
79       \_siunitx_table_collect_search:NnF #1
80       {
81         \maybe@unskip    { \_siunitx_table_collect_loop: }
82         \tab@setcr      { \_siunitx_table_collect_loop: }
83         \unskip        { \_siunitx_table_collect_loop: }
84         \end           { \tabularnewline \end }
85         \relax          { \_siunitx_table_collect_relax:N #1 }
86         \tabularnewline { \tabularnewline }
87         \siunitx_cell_end: { \siunitx_cell_end: }
88       }
89       { \_siunitx_table_collect_token_aux:N #1 }
90     }
91   }
92   { }
93 }
94 \cs_new_protected:Npn \_siunitx_table_collect_search:NnF #1#2#3
95 {
96   \_siunitx_table_collect_search_aux>NNn #1
97   #2
98   #1 {#3}
99   \q_stop
100 }
101 \cs_new_protected:Npn \_siunitx_table_collect_search_aux>NNn #1#2#3
102 {
103   \token_if_eq_meaning:NNTF #1 #2
104   { \use_i_delimit_by_q_stop:nw {#3} }
105   { \_siunitx_table_collect_search_aux>NNn #1 }
106 }

```

(End definition for _siunitx_table_collect_loop: and others.)

2.3 Separating collected material

The input needs to be divided into numerical tokens and those which appear before and after them. This needs a second loop and validation.

```
\l_siunitx_table_before_tl
\l_siunitx_table_number_tl
\l_siunitx_table_after_tl
```

Space for tokens.

```
107 \tl_new:N \l_siunitx_table_before_tl
108 \tl_new:N \l_siunitx_table_number_tl
109 \tl_new:N \l_siunitx_table_after_tl
```

(End definition for `\l_siunitx_table_before_tl`, `\l_siunitx_table_number_tl`, and `\l_siunitx_table_after_tl`.)

```
\_siunitx_table_collect_end:
\_\siunitx_table_collect_end:n
\_\siunitx_table_collect_end_aux:n
\_\siunitx_table_collect_end:w
```

At the end of the cell, escape the group and check for expansion. We only do that if the entire content is not a brace group: there is more likely to be problematic content in the case of a header.

```
110 \cs_new_protected:Npn \_siunitx_table_collect_end:
111 {
112     \exp_args:NNV \group_end:
113     \_siunitx_table_collect_end:n \l_siunitx_table_collect_tl
114     \exp_args:NV \_siunitx_table_split:nNNN
115         \l_siunitx_table_collect_tl
116         \l_siunitx_table_before_tl
117         \l_siunitx_table_number_tl
118         \l_siunitx_table_after_tl
119         \tl_if_empty:NTF \l_siunitx_table_number_tl
120             { \_siunitx_table_print_text:V \l_siunitx_table_before_tl }
121             {
122                 \_siunitx_table_print:VVV
123                 \l_siunitx_table_before_tl
124                 \l_siunitx_table_number_tl
125                 \l_siunitx_table_after_tl
126             }
127 }
```

To cover the use of REVTeX, we need to allow for the insertion of `\array@row@rst` into cell content: that explodes inside `\protected@edef`. We use the classical solution of making locally equal to `\scan_stop`:

```
128 \cs_new_protected:Npn \_siunitx_table_collect_end:n #1
129 {
130     \str_if_eq:eeTF { \exp_not:n {#1} }
131         { { \_siunitx_table_collect_end_aux:n {#1} } }
132         { \tl_set:Nn }
133         {
134             \cs_if_exist:NT \array@row@rst
135                 { \cs_set_eq:NN \array@row@rst \scan_stop: }
136             \protected@edef
137         }
138         \l_siunitx_table_collect_tl {#1}
139 }
140 \cs_new:Npn \_siunitx_table_collect_end_aux:n #1
141     { \exp_after:wN \_siunitx_table_collect_end:w #1 \q_stop }
142 \cs_new:Npn \_siunitx_table_collect_end:w #1 \q_stop
143     { \exp_not:n {#1} }
```

(End definition for `_siunitx_table_collect_end`: and others.)

```

\_\_siunitx_table_split:nNNN
  \_\_siunitx_table_split_loop:NNNn
    \_\_siunitx_table_split_group:NNNn
      \_\_siunitx_table_split_token:NNNN

144 \cs_new_protected:Npn \_\_siunitx_table_split:nNNN #1#2#3#4
145   {
146     \tl_clear:N #2
147     \tl_clear:N #3
148     \tl_clear:N #4
149     \_\_siunitx_table_split_loop:NNN #2#3#4 #1 \q_recursion_tail \q_recursion_stop
150     \_\_siunitx_table_split_tidy:N #2
151     \_\_siunitx_table_split_tidy:N #4
152   }
153 \cs_new_protected:Npn \_\_siunitx_table_split_loop:NNN #1#2#3
154   {
155     \peek_catcode_ignore_spaces:NTF \c_group_begin_token
156     { \_\_siunitx_table_split_group:NNNn #1#2#3 }
157     { \_\_siunitx_table_split_token:NNNN #1#2#3 }
158   }
159 \cs_new_protected:Npn \_\_siunitx_table_split_group:NNNn #1#2#3#4
160   {
161     \tl_if_empty:NTF #2
162     { \tl_put_right:Nn #1 { {#4} } }
163     { \tl_put_right:Nn #3 { {#4} } }
164     \_\_siunitx_table_split_loop:NNN #1#2#3
165   }
166 \cs_new_protected:Npn \_\_siunitx_table_split_token:NNNN #1#2#3#4
167   {
168     \quark_if_recursion_tail_stop:N #4
169     \tl_if_empty:NTF \l_\_siunitx_table_after_tl
170     {
171       \siunitx_if_number_token:NTF #4
172       { \tl_put_right:Nn #2 {#4} }
173       {
174         \tl_if_empty:NTF #2
175           { \tl_put_right:Nn #1 {#4} }
176           { \tl_put_right:Nn #3 {#4} }
177       }
178     }
179     { \tl_put_right:Nn #3 {#4} }
180     \_\_siunitx_table_split_loop:NNN #1#2#3
181   }

```

(End definition for `_siunitx_table_split:nNNN` and others.)

`__siunitx_table_split_tidy:N`
`__siunitx_table_split_tidy:Nn`
`__siunitx_table_split_tidy:NV`

```

182 \cs_new_protected:Npn \_\_siunitx_table_split_tidy:N #1
183   {
184     \tl_if_empty:NF #1
185     { \_\_siunitx_table_split_tidy:NV #1 #1 }
186   }
187 \cs_new_protected:Npn \_\_siunitx_table_split_tidy:Nn #1#2

```

```

188   {
189     \str_if_eq:onT { \exp_after:wN { \use:n #2 } } {#2}
190       { \tl_set:Nn #1 { \use:n #2 } }
191   }
192 \cs_generate_variant:Nn \__siunitx_table_split_tidy:Nn { NV }

(End definition for \__siunitx_table_split_tidy:N and \__siunitx_table_split_tidy:Nn.)

```

2.4 Printing numbers in cells: spacing

Getting the general alignment correct in tables is made more complex than one would like by the `colortbl` package. In the original L^AT_EX 2 _{ϵ} definition, cell material is centred by a construction of the (primitive) form

```
\hfil
#
\hfil
```

which only uses `fil` stretch. That is altered by `colortbl` to broadly

```
\hskip Opt plus 0.5fill
\kern Opt
#
\hskip Opt plus 0.5fill
```

which means there is `fill` stretch to worry about and the kern as well.

__siunitx_table_skip:n

To prevent combination of skips, a kern is inserted after each one. This is best handled as a short auxiliary.

```

193 \cs_new_protected:Npn \__siunitx_table_skip:n #1
194   {
195     \skip_horizontal:n {#1}
196     \tex_kern:D \c_zero_skip
197   }
```

(End definition for __siunitx_table_skip:n.)

\l_siunitx_table_column_width_dim
\l_siunitx_table_fixed_width_bool

Settings which apply to aligned columns in general.

```

198 \keys_define:nn { siunitx }
199   {
200     table-column-width .dim_set:N =
201       \l_siunitx_table_column_width_dim ,
202     table-fixed-width .bool_set:N =
203       \l_siunitx_table_fixed_width_bool
204   }
```

(End definition for \l_siunitx_table_column_width_dim and \l_siunitx_table_fixed_width_bool.)

_siunitx_table_align_center:n
_siunitx_table_align_left:n
_siunitx_table_align_right:n
_siunitx_table_align_auxi:nn
_siunitx_table_align_auxii:nn

The beginning and end of each table cell have to adjust the position of the content using glue. When `colortbl` is loaded the glue is done in two parts: one for our positioning and one to explicitly override that from the package. Using a two-step auxiliary chain avoids needing to repeat any code and the impact of the extra expansion should be trivial.

```

205 \cs_new_protected:Npn \__siunitx_table_align_center:n #1
206   { \__siunitx_table_align_auxi:nn {#1} { Opt~plus~-0.5fill } }
```

```

207 \cs_new_protected:Npn \__siunitx_table_align_left:n #1
208   { \__siunitx_table_align_auxi:nn {#1} { Opt } }
209 \cs_new_protected:Npn \__siunitx_table_align_right:n #1
210   { \__siunitx_table_align_auxi:nn {#1} { Opt-plus~1fill } }
211 \cs_new_protected:Npn \__siunitx_table_align_auxi:nn #1#2
212   {
213     \bool_if:NTF \l__siunitx_table_fixed_width_bool
214       { \hbox_to_wd:nn \l__siunitx_table_column_width_dim }
215       { \use:n }
216     {
217       \__siunitx_table_skip:n {#2}
218       #1
219       \__siunitx_table_skip:n { Opt-plus~1fill - #2 }
220     }
221   }
222 \AtBeginDocument
223 {
224   \c@ifpackageloaded{colortbl}{}
225   {
226     \cs_new_eq:NN
227       \__siunitx_table_align_auxii:nn
228       \__siunitx_table_align_auxi:nn
229     \cs_set_protected:Npn \__siunitx_table_align_auxi:nn #1#2
230     {
231       \__siunitx_table_skip:n { Opt-plus~-0.5fill }
232       \__siunitx_table_align_auxii:nn {#1} {#2}
233       \__siunitx_table_skip:n { Opt-plus~-0.5fill }
234     }
235   }
236   { }
237 }

```

(End definition for `__siunitx_table_align_center:n` and others.)

2.5 Printing just text

In cases where there is no numerical part, `siunitx` allows alignment of the “escaped” text independent of the underlying column type.

`\l__siunitx_table_align_text_tl`

Alignment is handled using a `tl` as this allows a fast lookup at the point of use.

```

238 \keys_define:nn { siunitx }
239   {
240     table-text-alignment .choices:nn =
241       { center , left , right }
242       { \tl_set:Nn \l__siunitx_table_align_text_tl {#1} } ,
243   }
244 \tl_new:N \l__siunitx_table_align_text_tl

```

(End definition for `\l__siunitx_table_align_text_tl`.)

`__siunitx_table_print_text:n`
`__siunitx_table_print_text:V`

Printing escaped text is easy: just place it in correctly in the column.

```

245 \cs_new_protected:Npn \__siunitx_table_print_text:n #1
246   {
247     \bool_set_true:N \l__siunitx_table_text_bool

```

```

248     \use:c { __siunitx_table_align_ \l__siunitx_table_align_text_tl :n } {#1}
249   }
250 \cs_generate_variant:Nn \__siunitx_table_print_text:n { V }

(End definition for \__siunitx_table_print_text:n.)

```

2.6 Number alignment: core ideas

\l__siunitx_table_integer_box Boxes for the content before and after the decimal marker.

```

251 \box_new:N \l__siunitx_table_integer_box
252 \box_new:N \l__siunitx_table_decimal_box

```

(End definition for \l__siunitx_table_integer_box and \l__siunitx_table_decimal_box.)

__siunitx_table_fil: Primitives renamed.

```

\__siunitx_table_fill: 253 \cs_new_eq:NN \__siunitx_table_fil: \tex_hfil:D
254 \cs_new_eq:NN \__siunitx_table_fill: \tex_hfill:D

```

(End definition for __siunitx_table_fil: and __siunitx_table_fill:.)

__siunitx_table_cleanup_decimal:w To remove the excess marker tokens in a decimal part.

```

255 \cs_new:Npn \__siunitx_table_cleanup_decimal:w
256   #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_nil #5 \q_nil #6 \q_nil #7 \q_nil
257   { #1#2#3#4#5#6#7 }

```

(End definition for __siunitx_table_cleanup_decimal:w.)

__siunitx_table_color_check:N Handle the fact that splitting a number can leave a negative color dangling.

```

\__siunitx_table_color_check:w 258 \cs_new_protected:Npn \__siunitx_table_color_check:N #1
\__siunitx_table_color_check:Nw 259   { \exp_after:wN \__siunitx_table_color_check:w #1 \q_stop }
\__siunitx_table_color_check:Nnw 260 \cs_new_protected:Npn \__siunitx_table_color_check:w #1 \q_nil #2 \q_stop
261   {
262     \tl_if_head_eq_meaning:nNT {#1} \color
263     { \__siunitx_table_color_check:Nnw #1 \q_stop }
264   }
265 \cs_new_protected:Npn \__siunitx_table_color_check:Nnw #1#2#3 \q_stop
266   { \keys_set:nn { siunitx } { number-color = #2 } }

```

(End definition for __siunitx_table_color_check:N, __siunitx_table_color_check:w, and __siunitx_table_color_check:Nnw.)

__siunitx_table_center_marker: When centering on the decimal marker, the easiest approach is to simply re-box the two parts. That is needed whether or not we are parsing numbers, so is best as a short auxiliary. Notice that we need to allow for the width of the decimal marker itself.

```

267 \cs_new_protected:Npn \__siunitx_table_center_marker:
268   {
269     \hbox_set:Nn \l__siunitx_table_tmp_box
270     { \ensuremath { \mathord { \l_siunitx_number_output_decimal_tl } } }
271   \dim_compare:nNnTF
272     { \box_wd:N \l__siunitx_table_integer_box }
273     >
274     {
275       \box_wd:N \l__siunitx_table_decimal_box
276       - \box_wd:N \l__siunitx_table_tmp_box
277     }

```

```

278 {
279   \hbox_set_to_wd:Nnn \l_siunitx_table_decimal_box
280   {
281     \box_wd:N \l_siunitx_table_integer_box
282     + \box_wd:N \l_siunitx_table_tmp_box
283   }
284   {
285     \hbox_unpack:N \l_siunitx_table_decimal_box
286     \l_siunitx_table_fil:
287   }
288 }
289 {
290   \hbox_set_to_wd:Nnn \l_siunitx_table_integer_box
291   {
292     \box_wd:N \l_siunitx_table_decimal_box
293     - \box_wd:N \l_siunitx_table_tmp_box
294   }
295   {
296     \l_siunitx_table_fil:
297     \hbox_unpack:N \l_siunitx_table_integer_box
298   }
299 }
300 }

```

(End definition for `\l_siunitx_table_center_marker`.)

`\l_siunitx_table_auto_round_bool`

`\l_siunitx_table_align_mode_tl`
`\l_siunitx_table_align_number_tl`

Options for tables with defined space.

```

301 \keys_define:nn { siunitx }
302   {
303     table-alignment .meta:n =
304       { table-number-alignment = #1 , table-text-alignment = #1 },
305     table-alignment-mode .choices:nn =
306       { none , format , marker }
307       { \tl_set_eq:NN \l_siunitx_table_align_mode_tl \l_keys_choice_t1 } ,
308     table-auto-round .bool_set:N =
309       \l_siunitx_table_auto_round_bool ,
310     table-format .code:n =
311       {
312         \l_siunitx_table_split:nNNN {#1}
313         \l_siunitx_table_before_model_tl
314         \l_siunitx_table_model_tl
315         \l_siunitx_table_after_model_tl
316         \exp_args:NV \l_siunitx_table_generate_model:n \l_siunitx_table_model_tl
317         \tl_set:Nn \l_siunitx_table_align_mode_tl { format }
318       } ,
319     table-number-alignment .choices:nn =
320       { center , left , right }
321       { \tl_set_eq:NN \l_siunitx_table_align_number_tl \l_keys_choice_t1 }
322   }
323 \tl_new:N \l_siunitx_table_align_mode_tl
324 \tl_new:N \l_siunitx_table_align_number_tl

```

(End definition for `\l_siunitx_table_auto_round_bool`, `\l_siunitx_table_align_mode_tl`, and
`\l_siunitx_table_align_number_tl`.)

\l_siunitx_table_format_tl The input and output versions of the model entry in a table.

```

325 \tl_new:N \l_siunitx_table_format_tl
326 \tl_new:N \l_siunitx_table_before_model_tl
327 \tl_new:N \l_siunitx_table_model_tl
328 \tl_new:N \l_siunitx_table_after_model_tl

```

(End definition for \l_siunitx_table_format_tl and \l_siunitx_table_model_tl.)

Creating a model for a table at this stage means parsing the format and converting that to an appropriate model. Things are quite straight-forward other than the uncertainty part. At this stage there is no point in formatting the model: that has to happen at point-of-use. Notice that the uncertainty part needs to allow for the case where we cross the decimal.

```

329 \cs_new_protected:Npn \_siunitx_table_generate_model:n
330 {
331   \group_begin:
332     \bool_set_true:N \l_siunitx_number_parse_bool
333     \keys_set:nn { siunitx } { retain-explicit-plus = true }
334     \siunitx_number_parse:nN {#1} \l_siunitx_table_format_tl
335   \exp_args:NNNV \group_end:
336   \tl_set:Nn \l_siunitx_table_format_tl \l_siunitx_table_format_tl
337   \tl_if_empty:NF \l_siunitx_table_format_tl
338   {
339     \exp_after:wN \_siunitx_table_generate_model:nnnnnnn
340     \l_siunitx_table_format_tl
341   }
342 }
343 \cs_new_protected:Npn \_siunitx_table_generate_model:nnnnnnn #1#2#3#4#5#6#7
344 {
345   \tl_set:Nx \l_siunitx_table_model_tl
346   {
347     \exp_not:n { {#1} {#2} }
348     { \prg_replicate:nn {#3} { 8 } }
349     { \prg_replicate:nn { 0 #4 } { 8 } }
350     {
351       \tl_if_blank:nF {#5}
352       {
353         \use:c { _siunitx_table_generate_model_ \tl_head:n {#5} :nnw }
354         {#4} #5
355       }
356     }
357     \exp_not:n { {#6} }
358   {
359     \int_compare:nNnTF {#7} = 0
360     { 0 }
361     { \prg_replicate:nn {#7} { 8 } }
362   }
363 }
364 }
365 \cs_new:Npn \_siunitx_table_generate_model_S:nnw #1#2#3
366 {
367   { S }
368   {
369     \exp_args:Nff \_siunitx_table_generate_model_S:nn

```

```

370     { \tl_count:n {#1} } { \tl_count:n {#3} }
371     {#3}
372   }
373 }
374 \cs_new:Npn \__siunitx_table_generate_model_S:nnn #1#2#3
375 {
376   \prg_replicate:nn
377   {
378     \int_compare:nNnTF {#2} > {#1}
379     {
380       \str_range:nnn {#3} { 1 } {#1}
381       +
382       \str_range:nnn {#3} { 1 + #1 } {#2}
383     }
384     {#3}
385   }
386   { 8 }
387 }

```

(End definition for `__siunitx_table_generate_model:n` and others.)

2.7 Directly printing without collection

Collecting the number allows for various effects but is not as fast as simply aligning on the first token that is a decimal marker. The strategy here is that used by `dcolumn`.

```

\__siunitx_table_direct_begin:
\__siunitx_table_direct_begin:w
\__siunitx_table_direct_end:
  \__siunitx_table_direct_marker:
\__siunitx_table_direct_marker_switch:
  \__siunitx_table_direct_marker_end:
    \__siunitx_table_direct_format:
\__siunitx_table_direct_format:nnnnnn
  \__siunitx_table_direct_format:w
\__siunitx_table_direct_format_switch:
  \__siunitx_table_direct_format_end:
    \__siunitx_table_direct_none:
\__siunitx_table_direct_none_end:

```

After removing the `\ignorespaces` at the start of the cell (see comments for `__siunitx_table_collect_begin:N`), check to see if there is a `{` and branch as appropriate.

```

388 \cs_new_protected:Npn \__siunitx_table_direct_begin:
389   { \__siunitx_table_direct_begin:w }
390 \cs_new_protected:Npn \__siunitx_table_direct_begin:w #1 \ignorespaces
391   {
392     #1
393     \peek_catcode_ignore_spaces:NTF \c_group_begin_token
394     { \__siunitx_table_print_text:n }
395     {
396       \m@th
397       \use:c { __siunitx_table_direct_ \l_siunitx_table_align_mode_t1 : }
398     }
399   }
400 \cs_new_protected:Npn \__siunitx_table_direct_end:
401   { \use:c { __siunitx_table_direct_ \l_siunitx_table_align_mode_t1 _end: } }

```

When centring the content about a decimal marker, the trick is to collect everything into two boxes and then compare the sizes. As we are always in math mode, we can use a math active token to make the switch. The up-front setting of the `decimal` box deals with the case where there is no decimal part.

```

402 \cs_new_protected:Npn \__siunitx_table_direct_marker:
403   {
404     \hbox_set:Nn \l_siunitx_table_tmp_box
405     { \ensuremath { \mathord { \l_siunitx_number_output_decimal_t1 } } }
406     \hbox_set_to_wd:Nnn \l_siunitx_table_decimal_box
407     { \box_wd:N \l_siunitx_table_tmp_box }
408     { \__siunitx_table_file: }

```

```

409  \hbox_set:Nw \l_siunitx_table_integer_box
410    \c_math_toggle_token
411    \tl_map_inline:Nn \l_siunitx_number_input_decimal_tl
412    {
413      \char_set_active_eq:NN ##1 \__siunitx_table_direct_marker_switch:
414      \char_set_mathcode:nn { '##1 } { "8000 }
415    }
416  }
417 \cs_new_protected:Npn \__siunitx_table_direct_marker_switch:
418  {
419    \c_math_toggle_token
420    \hbox_set_end:
421    \hbox_set:Nw \l_siunitx_table_decimal_box
422      \c_math_toggle_token
423      \l_siunitx_number_output_decimal_tl
424    }
425 \cs_new_protected:Npn \__siunitx_table_direct_marker_end:
426  {
427    \c_math_toggle_token
428    \hbox_set_end:
429    \__siunitx_table_center_marker:
430    \use:c { __siunitx_table_align_ \l_siunitx_table_align_text_tl :n }
431    {
432      \box_use_drop:N \l_siunitx_table_integer_box
433      \box_use_drop:N \l_siunitx_table_decimal_box
434    }
435  }

```

For the version where there is space reserved, first format and decompose that, then create appropriately-sized boxes.

```

436 \cs_new_protected:Npn \__siunitx_table_direct_format:
437  {
438    \tl_set:Nx \l_siunitx_table_tmp_tl
439      { \siunitx_number_output:NN \l_siunitx_table_model_tl \q_nil }
440    \exp_after:wN \__siunitx_table_direct_format_aux:w
441      \l_siunitx_table_tmp_tl \q_stop
442  }
443 \cs_new_protected:Npn \__siunitx_table_direct_format_aux:w
444  #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_stop
445  {
446    \hbox_set:Nn \l_siunitx_table_tmp_box
447      { \ensuremath { \__siunitx_table_cleanup_decimal:w #4 } }
448    \hbox_set_to_wd:Nnn \l_siunitx_table_decimal_box
449      { \box_wd:N \l_siunitx_table_tmp_box }
450      { \__siunitx_table_file: }
451    \hbox_set:Nn \l_siunitx_table_tmp_box { \ensuremath { #1#2#3 } }
452    \hbox_set_to_wd:Nnw \l_siunitx_table_integer_box
453      { \box_wd:N \l_siunitx_table_tmp_box }
454      \c_math_toggle_token
455      \tl_map_inline:Nn \l_siunitx_number_input_decimal_tl
456      {
457        \char_set_active_eq:NN ##1 \__siunitx_table_direct_format_switch:
458        \char_set_mathcode:nn { '##1 } { "8000 }
459      }

```

```

460      \_\_siunitx_table_fill:
461    }
462 \cs_new_protected:Npn \_\_siunitx_table_direct_format_switch:
463 {
464   \c_math_toggle_token
465   \hbox_set_end:
466   \hbox_set_to_wd:Nnw \l\_siunitx_table_decimal_box
467   { \box_wd:N \l\_siunitx_table_decimal_box }
468   \c_math_toggle_token
469   \mathord { \l_siunitx_number_output_decimal_t1 }
470 }
471 \cs_new_protected:Npn \_\_siunitx_table_direct_format_end:
472 {
473   \c_math_toggle_token
474   \_\_siunitx_table_fil:
475   \hbox_set_end:
476   \use:c { \_\_siunitx_table_align_ \l\_siunitx_table_align_number_t1 :n }
477   {
478     \box_use_drop:N \l\_siunitx_table_integer_box
479     \box_use_drop:N \l\_siunitx_table_decimal_box
480   }
481 }
```

No parsing and no alignment is easy.

```

482 \cs_new_protected:Npn \_\_siunitx_table_direct_none: { \c_math_toggle_token }
483 \cs_new_protected:Npn \_\_siunitx_table_direct_none_end: { \c_math_toggle_token }
```

(End definition for `__siunitx_table_direct_begin:` and others.)

2.8 Printing numbers in cells: main functions

For alignment of text outside of a number.

```

484 \box_new:N \l\_siunitx_table_before_box
485 \box_new:N \l\_siunitx_table_after_box
```

(End definition for `\l_siunitx_table_before_box` and `\l_siunitx_table_after_box`.)

`\l_siunitx_table_before_dim` Space reserved for any non-numerical text before the number: as we need to allow for this to be available after setting the integer part, we need to carry it along for a bit.

```
486 \dim_new:N \l\_siunitx_table_before_dim
```

(End definition for `\l_siunitx_table_before_dim`.)

`\l_siunitx_table_carry_dim` Used to “carry forward” the amount of white space which needs to be inserted after the decimal marker.

```
487 \dim_new:N \l\_siunitx_table_carry_dim
```

(End definition for `\l_siunitx_table_carry_dim`.)

`\l_siunitx_table_align_comparator_bool` Alignment is handled using a `tl` as this allows a fast lookup at the point of use.

```

488 \keys_define:nn { siunitx }
489 {
490   table-align-comparator .bool_set:N =
491   \l\_siunitx_table_align_comparator_bool ,
492   table-align-exponent .bool_set:N =
```

```

493     \l_siunitx_table_align_exponent_bool ,
494     table-align-text-after .bool_set:N =
495         \l_siunitx_table_align_after_bool ,
496     table-align-text-before .bool_set:N =
497         \l_siunitx_table_align_before_bool ,
498     table-align-uncertainty .bool_set:N =
499         \l_siunitx_table_align_uncertainty_bool
500 }

```

(End definition for `\l_siunitx_table_align_comparator_bool` and others.)

```

\_\_siunitx_table_print:nnn
\_\_siunitx_table_print:VVV
    \_\_siunitx_table_print_marker:nnn
        \_\_siunitx_table_print_marker:w
    \_\_siunitx_table_print_marker:nnn
        \_\_siunitx_table_print_format:nnnnn
    \_\_siunitx_table_print_format:nnnnnn
    \_\_siunitx_table_print_format:auxi:w
    \_\_siunitx_table_print_format:auxii:w
    \_\_siunitx_table_print_format:auxiii:w
    \_\_siunitx_table_print_format:auxiv:w
    \_\_siunitx_table_print_format:auxv:w
    \_\_siunitx_table_print_format:auxvi:w
    \_\_siunitx_table_print_format:auxvii:w
    \_\_siunitx_table_print_format:box:Nn
    \_\_siunitx_table_print_format:after:N
        \_\_siunitx_table_print_none:nnn

```

```

501 \cs_new_protected:Npn \_\_siunitx_table_print:nnn #1#2#3
502     { \use:c { __siunitx_table_print_ \l_siunitx_table_align_mode_tl :nnn } {#1} {#2} {#3} }
503 \cs_generate_variant:Nn \_\_siunitx_table_print:nnn { VVV }

```

When centering on the decimal marker, alignment is relatively simple, and close in concept to that used without parsing. First we need to deal with any text before or after the number. For text *before*, there's the case where it has no width and might be a font or color change: that has to be filtered out first. Then we can adjust the size of this material and that after the number such that they are equal. The number itself can then be formatted, splitting at the decimal marker. A bit more size adjustment, then the number itself and any text at the end can be inserted.

```

504 \cs_new_protected:Npn \_\_siunitx_table_print_marker:nnn #1#2#3
505     {
506         \hbox_set:Nn \l_siunitx_table_before_box {#1}
507         \dim_compare:nNnT { \box_wd:N \l_siunitx_table_before_box } = { 0pt }
508         {
509             \box_clear:N \l_siunitx_table_before_box
510             #1
511         }
512         \hbox_set:Nn \l_siunitx_table_after_box {#3}
513         \dim_compare:nNnTF
514             { \box_wd:N \l_siunitx_table_after_box }
515             > { \box_wd:N \l_siunitx_table_before_box }
516             {
517                 \hbox_set_to_wd:Nnn \l_siunitx_table_before_box
518                 { \box_wd:N \l_siunitx_table_after_box }
519                 {
520                     \_\_siunitx_table_fil:
521                     \hbox_unpack:N \l_siunitx_table_before_box
522                 }
523             }
524             {
525                 \hbox_set_to_wd:Nnn \l_siunitx_table_after_box
526                 { \box_wd:N \l_siunitx_table_before_box }
527                 {
528                     \hbox_unpack:N \l_siunitx_table_after_box
529                     \_\_siunitx_table_fil:
530                 }
531             }
532             \box_use_drop:N \l_siunitx_table_before_box
533             \siunitx_number_parse:nN {#2} \l_siunitx_table_tmp_t1
534             \siunitx_number_process:NN \l_siunitx_table_tmp_t1 \l_siunitx_table_tmp_t1

```

```

535   \tl_set:Nx \l_siunitx_table_tmp_tl
536     { \siunitx_number_output:NN \l_siunitx_table_tmp_tl \q_nil }
537   \__siunitx_table_color_check:N \l_siunitx_table_tmp_tl
538   \exp_after:wN \__siunitx_table_print_marker:w
539     \l_siunitx_table_tmp_tl \q_stop
540   \box_use_drop:N \l_siunitx_table_after_box
541 }
542 \cs_new_protected:Npn \__siunitx_table_print_marker:w
543 #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_stop
544 {
545   \hbox_set:Nn \l_siunitx_table_integer_box
546     { \siunitx_print_number:n { #1#2#3 } }
547   \hbox_set:Nn \l_siunitx_table_decimal_box
548   {
549     \siunitx_print_number:x
550       { \__siunitx_table_print_marker_aux:w #4 }
551   }
552   \__siunitx_table_center_marker:
553   \use:c { __siunitx_table_align_ \l_siunitx_table_align_text_t1 :n }
554   {
555     \box_use_drop:N \l_siunitx_table_integer_box
556     \box_use_drop:N \l_siunitx_table_decimal_box
557   }
558 }
559 \cs_new:Npn \__siunitx_table_print_marker_aux:w
560 #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_nil #5 \q_nil #6 \q_nil #7 \q_nil
561 {
562   \exp_not:n { #1#2#3#4#5}
563   \tl_if_blank:nT {#1#2#3#4#5} { { } }
564   \exp_not:n {#6#7}
565 }
566 }

```

For positioning based on a format, we have to work part-by-part as there are a number of alignment points to get right. As for the `marker` approach, first we check if the material before the numerical content is of zero width. Next we need to format the model and content numbers, before starting an auxiliary chain to pick out the various parts in order. We have to carry the amount of space for the non-numerical material before the cell forward: this may end up being enlarged by unused parts of the integer.

```

566 \cs_new_protected:Npn \__siunitx_table_print_format:nnn #1#2#3
567 {
568   \hbox_set:Nn \l_siunitx_table_tmp_box { \l_siunitx_table_before_model_t1 }
569   \hbox_set:Nn \l_siunitx_table_before_box {#1}
570   \dim_compare:nNnT { \box_wd:N \l_siunitx_table_before_box } = { 0pt }
571   {
572     \box_clear:N \l_siunitx_table_before_box
573     #1
574   }
575   \dim_set:Nn \l_siunitx_table_before_dim { \box_wd:N \l_siunitx_table_tmp_box }
576   \siunitx_number_parse:nN {#2} \l_siunitx_table_tmp_t1
577   \group_begin:
578     \bool_if:NT \l_siunitx_table_auto_round_bool
579     {
580       \exp_args:Nx \keys_set:nn { siunitx }
581     }

```

```

582     round-mode      = places ,
583     round-pad       = true   ,
584     round-precision =
585         \exp_after:wN \__siunitx_table_print_format:nnnnnn
586             \l__siunitx_table_format_tl
587     }
588 }
589 \siunitx_number_process:NN \l__siunitx_table_tmp_tl \l__siunitx_table_tmp_tl
590 \exp_args:NNNV \group_end:
591 \tl_set:Nn \l__siunitx_table_tmp_tl \l__siunitx_table_tmp_tl
592 \tl_set:Nx \l__siunitx_table_tmp_tl
593 {
594     \siunitx_number_output:NN \l__siunitx_table_model_tl \q_nil
595     \exp_not:N \q_mark
596     \siunitx_number_output:NN \l__siunitx_table_tmp_tl \q_nil
597 }
598 \exp_after:wN \__siunitx_table_print_format_auxi:w
599     \l__siunitx_table_tmp_tl \q_stop
600 \hbox_set:Nn \l__siunitx_table_tmp_box { \l__siunitx_table_after_model_tl }
601 \hbox_set_to_wd:Nnn \l__siunitx_table_after_box
602     { \box_wd:N \l__siunitx_table_tmp_box + \l__siunitx_table_carry_dim }
603 {
604     \bool_if:NT \l__siunitx_table_align_after_bool
605         { \skip_horizontal:n { \l__siunitx_table_carry_dim } }
606     #3
607     \__siunitx_table_fil:
608 }
609 \use:c { __siunitx_table_align_ \l__siunitx_table_align_number_tl :n }
610 {
611     \box_use_drop:N \l__siunitx_table_before_box
612     \box_use_drop:N \l__siunitx_table_integer_box
613     \box_use_drop:N \l__siunitx_table_decimal_box
614     \box_use_drop:N \l__siunitx_table_after_box
615 }
616 }
617 \cs_new:Npn \__siunitx_table_print_format:nnnnnn #1#2#3#4#5#6#
618     { 0 #4 }

```

The first numerical part to handle is the comparator. Any white space we need to add goes into the text part *if* alignment is not active (*i.e.* we are looking “backwards” to place this filler).

```

619 \cs_new_protected:Npn \__siunitx_table_print_format_auxi:w
620     #1 \q_nil #2 \q_mark #3 \q_nil #4 \q_stop
621 {
622     \__siunitx_table_color_check:w #3 \q_nil \q_stop
623     \__siunitx_table_print_format_box:Nn \l__siunitx_table_tmp_box {#1}
624     \bool_if:NTF \l__siunitx_table_align_before_bool
625     {
626         \hbox_set_to_wd:Nnn \l__siunitx_table_integer_box
627             { \box_wd:N \l__siunitx_table_tmp_box }
628         {
629             \__siunitx_table_fil:
630             \tl_if_blank:nF {#3}
631                 { \siunitx_print_number:n {#3} }

```

```

632         }
633     }
634     {
635         \__siunitx_table_print_format_box:Nn \l__siunitx_table_integer_box {#3}
636         \dim_add:Nn \l__siunitx_table_before_dim
637         {
638             \box_wd:N \l__siunitx_table_tmp_box
639             - \box_wd:N \l__siunitx_table_integer_box
640         }
641     }
642     \__siunitx_table_print_format_auxii:w #2 \q_mark #4 \q_stop
643 }

```

The integer part follows much the same pattern, except now it is control of the comparator alignment that determines where the white space goes. As we already have content in the `integer` box, we need to measure how much *extra* material has been added. To avoid using more boxes or re-setting, we do that by recording sizes before and after the change. (In effect, `\l__siunitx_table_tmp_dim` is here “`l_@@_comparator_dim`”.) As the integer part is completed here, we are able to finalise the width of the pre-numeral part, reboxing it to have the correct width and possibly to force a single overfull warning if appropriate.

```

644 \cs_new_protected:Npn \__siunitx_table_print_format_auxii:w
645   #1 \q_nil #2 \q_nil #3 \q_mark #4 \q_nil #5 \q_nil #6 \q_stop
646   {
647       \__siunitx_table_print_format_box:Nn \l__siunitx_table_tmp_box {#1#2}
648       \bool_lazy_and:nnTF
649       {
650           \l__siunitx_table_align_comparator_bool
651           \dim_compare_p:nNn \box_wd:N \l__siunitx_table_integer_box } > { Opt } }
652       {
653           \hbox_set_to_wd:Nnn \l__siunitx_table_integer_box
654           {
655               \box_wd:N \l__siunitx_table_integer_box
656               + \box_wd:N \l__siunitx_table_tmp_box
657           }
658           {
659               \hbox_unpack:N \l__siunitx_table_integer_box
660               \__siunitx_table_fil:
661               \siunitx_print_number:n {#4#5}
662           }
663       }
664       \bool_if:NTF \l__siunitx_table_align_before_bool
665       {
666           \hbox_set_to_wd:Nnn \l__siunitx_table_integer_box
667           {
668               \box_wd:N \l__siunitx_table_integer_box
669               + \box_wd:N \l__siunitx_table_tmp_box
670           }
671           {
672               \__siunitx_table_fil:
673               \hbox_unpack:N \l__siunitx_table_integer_box
674               \siunitx_print_number:n {#4#5}
675           }
676       }

```

```

677   {
678     \dim_set:Nn \l_siunitx_table_tmp_dim
679       { \box_wd:N \l_siunitx_table_integer_box }
680     \hbox_set:Nn \l_siunitx_table_integer_box
681       {
682         \hbox_unpack:N \l_siunitx_table_integer_box
683         \siunitx_print_number:n {#4#5}
684       }
685     \dim_add:Nn \l_siunitx_table_before_dim
686       {
687         + \box_wd:N \l_siunitx_table_tmp_box
688         + \l_siunitx_table_tmp_dim
689         - \box_wd:N \l_siunitx_table_integer_box
690       }
691     }
692   }
693 \hbox_set_to_wd:Nnn \l_siunitx_table_before_box \l_siunitx_table_before_dim
694   {
695     \l_siunitx_table_fil:
696     \hbox_unpack:N \l_siunitx_table_before_box
697   }
698 \l_siunitx_table_print_format_auxiii:w #3 \q_mark #6 \q_stop
699 }

```

We now deal with the decimal part: there is nothing already in the `decimal` box, so the basics are easy. We need to “carry forward” any white space, as where it gets inserted depends on the options for subsequent parts.

```

700 \cs_new_protected:Npn \l_siunitx_table_print_format_auxiii:w
701   #1 \q_nil #2 \q_mark #3 \q_nil #4 \q_nil #5 \q_nil #6 \q_stop
702   {
703     \l_siunitx_table_print_format_box:Nn \l_siunitx_table_tmp_box {#1#2}
704     \l_siunitx_table_print_format_box:Nn \l_siunitx_table_decimal_box {#4#5}
705     \dim_set:Nn \l_siunitx_table_carry_dim
706       {
707         \box_wd:N \l_siunitx_table_tmp_box
708         - \box_wd:N \l_siunitx_table_decimal_box
709       }
710     \l_siunitx_table_print_format_auxiv:w #3 \q_mark #6 \q_stop
711   }

```

Any separated uncertainty is now picked up. That has a number of parts, so the first step is to look for a sign (which will be `#1`). We then split, either simply tidying up the markers if there is no uncertainty, or setting it.

```

712 \cs_new_protected:Npn \l_siunitx_table_print_format_auxiv:w
713   #1 \q_nil #2 \q_mark #3 \q_nil #4 \q_stop
714   {
715     \tl_if_blank:nTF {#1}
716       { \l_siunitx_table_print_format_auxv:w }
717       { \l_siunitx_table_print_format_auxvi:w }
718       #1#2 \q_mark #3#4 \q_stop
719   }
720 \cs_new_protected:Npn \l_siunitx_table_print_format_auxv:w
721   #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_mark
722   #5 \q_nil #6 \q_nil #7 \q_nil #8 \q_stop
723   { \l_siunitx_table_print_format_auxvii:w #4 \q_mark #8 \q_stop }

```

Sorting out the placement of the uncertainty requires both the model and real data widths, so we store the former to avoiding needing more boxes. It's then just a case of putting the carry-over white space in the right place.

```

724 \cs_new_protected:Npn \__siunitx_table_print_format_auxvi:w
725   #1 \q_nil #2 \q_nil #3 \q_nil #4 \q_mark
726   #5 \q_nil #6 \q_nil #7 \q_nil #8 \q_stop
727   {
728     \__siunitx_table_print_format_box:Nn \l__siunitx_table_tmp_box { { } #1#2#3 }
729     \dim_set:Nn \l__siunitx_table_tmp_dim { \box_wd:N \l__siunitx_table_tmp_box }
730     \__siunitx_table_print_format_box:Nn \l__siunitx_table_tmp_box { { } #5#6#7 }
731     \__siunitx_table_print_format_after:N \l__siunitx_table_align_uncertainty_bool
732     \__siunitx_table_print_format_auxvii:w #4 \q_mark #8 \q_stop
733   }

```

Finally, we get to the exponent part: the multiplication symbol is #1 and the number itself is #2. The code is almost the same as for uncertainties, which allows a shared auxiliary to be used.

```

734 \cs_new_protected:Npn \__siunitx_table_print_format_auxvii:w
735   #1 \q_nil #2 \q_mark #3 \q_nil #4 \q_stop
736   {
737     \tl_if_blank:nF {#2}
738     {
739       \__siunitx_table_print_format_box:Nn \l__siunitx_table_tmp_box { { } #1#2 }
740       \dim_set:Nn \l__siunitx_table_tmp_dim { \box_wd:N \l__siunitx_table_tmp_box }
741       \__siunitx_table_print_format_box:Nn \l__siunitx_table_tmp_box { { } #3#4 }
742       \__siunitx_table_print_format_after:N \l__siunitx_table_align_exponent_bool
743     }
744   }

```

A simple auxiliary to avoid relatively expensive use of the print routine for empty parts.

```

745 \cs_new_protected:Npn \__siunitx_table_print_format_box:Nn #1#2
746   {
747     \hbox_set:Nn #1
748     {
749       \tl_if_blank:nF {#2}
750       {
751         \siunitx_print_number:n {#2}
752       }
753     }

```

A common routine for placing material after the decimal marker and “shuffling”.

```

753 \cs_new_protected:Npn \__siunitx_table_print_format_after:N #1
754   {
755     \bool_if:NTF #1
756     {
757       \hbox_set_to_wd:Nnn \l__siunitx_table_decimal_box
758       {
759         \box_wd:N \l__siunitx_table_decimal_box
760         +
761         \l__siunitx_table_carry_dim
762         +
763         \box_wd:N \l__siunitx_table_tmp_box
764       }
765     }
766     \hbox_unpack:N \l__siunitx_table_decimal_box
767     \__siunitx_table_fil:
768     \hbox_unpack:N \l__siunitx_table_tmp_box
769   }

```

```

768     \dim_set:Nn \l_siunitx_table_carry_dim
769     {
770         \l_siunitx_table_tmp_dim
771         - \box_wd:N \l_siunitx_table_tmp_box
772     }
773 }
774 {
775     \hbox_set:Nn \l_siunitx_table_decimal_box
776     {
777         \hbox_unpack:N \l_siunitx_table_decimal_box
778         \hbox_unpack:N \l_siunitx_table_tmp_box
779     }
780     \dim_add:Nn \l_siunitx_table_carry_dim
781     {
782         \l_siunitx_table_tmp_dim
783         - \box_wd:N \l_siunitx_table_tmp_box
784     }
785 }
786 }

```

With no alignment, everything supplied is treated more-or-less the same as `\num` (but without the `xparse` wrapper).

```

787 \cs_new_protected:Npn \__siunitx_table_print_none:nnn #1#2#3
788 {
789     \use:c { __siunitx_table_align_ \l_siunitx_table_align_number_tl :n }
790     {
791         #1
792         \siunitx_number_format:nN {#2} \l_siunitx_table_tmp_tl
793         \siunitx_print_number:V \l_siunitx_table_tmp_tl
794         #3
795     }
796 }

```

(End definition for `__siunitx_table_print:nnn` and others.)

2.9 Standard settings for module options

Some of these follow naturally from the point of definition (*e.g.* boolean variables are always `false` to begin with), but for clarity everything is set here.

```

797 \keys_set:nn { siunitx }
798 {
799     table-align-comparator = true ,
800     table-align-exponent = true ,
801     table-align-text-after = true ,
802     table-align-text-before = true ,
803     table-align-uncertainty = true ,
804     table-alignment = center ,
805     table-auto-round = false ,
806     table-column-width = 0pt ,
807     table-fixed-width = false ,
808     table-format = 2.2 ,
809     table-number-alignment = center ,
810     table-text-alignment = center ,

```

Out of order as `table-format` sets this implicitly too.

```
811      table-alignment-mode      = marker
812      }
813  </package>
```

Part X

siunitx-unit – Parsing and formatting units

This submodule is dedicated to formatting physical units. The main function, `\siunitx_unit_format:nN`, takes user input specify physical units and converts it into a formatted token list suitable for typesetting in math mode. While the formatter will deal correctly with “literal” user input, the key strength of the module is providing a method to describe physical units in a “symbolic” manner. The output format of these symbolic units can then be controlled by a number of key–value options made available by the module.

A small number of L^AT_EX 2 _{ε} math mode commands are assumed to be available as part of the formatted output. The `\mathchoice` command (normally the T_EX primitive) is needed when using `per-mode = symbol-or-fraction`. The commands `\frac`, `\mathrm`, `\mbox`, `\lrcorner` and `\cancel`, are used by the standard module settings. For the display of colored (highlighted) and cancelled units, the commands `\textcolor` and `\cancel` are assumed to be available.

1 Formatting units

`\siunitx_unit_format:nN`
`\siunitx_unit_format:xN`

`\siunitx_unit_format:nN {<units>} {tl var}`

This function converts the input `<units>` into a processed `<tl var>` which can then be inserted in math mode to typeset the material. Where the `<units>` are given in symbolic form, described elsewhere, this formatting process takes place in two stages: the `<units>` are parsed into a structured form before the generation of the appropriate output form based on the active settings. When the `<units>` are given as literals, processing is minimal: the characters `.` and `~` are converted to unit products (boundaries). In both cases, the result is a series of tokens intended to be typeset in math mode with appropriate choice of font for typesetting of the textual parts.

For example,

`\siunitx_unit_format:nN { \kilo \metre \per \second } \l_tmpa_tl`

will, with standard settings, result in `\l_tmpa_tl` being set to

`\mathrm{km}, \mathrm{s}^{-1}`

```
\siunitx_unit_format_extract_prefixes:nNN  \siunitx_unit_format_extract_prefixes:nNN {<units>} {tl var}
                                                {fp var}
```

This function formats the *<units>* in the same way as described for `\siunitx_unit_format:nN`. When the input is given in symbolic form, any decimal unit prefixes will be extracted and the overall power of ten that these represent will be stored in the *<fp var>*.

For example,

```
\siunitx_unit_format_extract_prefixes:nNN { \kilo \metre \per \second }
                                         \l_tmpa_tl \l_tmpa_fp
```

will, with standard settings, result in `\l_tmpa_tl` being set to

```
\mathrm{m}\,,\mathrm{s}^{-1}
```

with `\l_tmpa_fp` taking value 3. Note that the latter is a floating point variable: it is possible for non-integer values to be obtained here.

```
\siunitx_unit_format_combine_exponent:nnN  \siunitx_unit_format_combine_exponent:nnN {<units>}
                                                {<exponent>} {tl var}
```

This function formats the *<units>* in the same way as described for `\siunitx_unit_format:nN`. The *<exponent>* is combined with any prefix for the *first* unit of the *<units>*, and an updated prefix is introduced.

For example,

```
\siunitx_unit_format_combine_exponent:nnN { \metre \per \second }
                                         { 3 } \l_tmpa_tl
```

will, with standard settings, result in `\l_tmpa_tl` being set to

```
\mathrm{km}\,,\mathrm{s}^{-1}
```

```
\siunitx_unit_format_multiply:nnN
\siunitx_unit_format_multiply_extract_prefixes:nnNN
\siunitx_unit_format_multiply_combine_exponent:nnnN
```

```
\siunitx_unit_format_multiply:nnN {<units>}
{<factor>} {tl var}
\siunitx_unit_format_multiply_extract-
prefixes:nnNN
{<units>} {<factor>} {tl var} {fp var}
\siunitx_unit_format_multiply_combine-
exponent:nnnN
{<units>} {<factor>} {<exponent>} {tl var}
```

These function formats the *<units>* in the same way as described for `\siunitx_unit_format:nN`. The units are multiplied by the *<factor>*, and further processing takes place as previously described.

For example,

```
\siunitx_unit_format_multiply:nnN { \metre \per \second }
                                         { 3 } \l_tmpa_tl
```

will, with standard settings, result in `\l_tmpa_tl` being set to

```
\mathrm{km}^3\,,\mathrm{s}^{-3}
```

2 Defining symbolic units

```
\siunitx_declare_prefix:Nnn \siunitx_declare_prefix:Nnn <prefix> {<power>} {<symbol>}
\siunitx_declare_prefix:Nnx
```

Defines a symbolic $\langle prefix \rangle$ (which should be a control sequence such as `\kilo`) to be converted by the parser to the $\langle symbol \rangle$. The latter should consist of literal content (*e.g.* `k`). In literal mode the $\langle symbol \rangle$ will be typeset directly. The prefix should represent an integer $\langle power \rangle$ of 10, and this information may be used to convert from one or more $\langle prefix \rangle$ symbols to an overall power applying to a unit. See also `\siunitx_declare_prefix:Nn`.

```
\siunitx_declare_prefix:Nn \siunitx_declare_prefix:Nn <prefix> {<symbol>}
```

Defines a symbolic $\langle prefix \rangle$ (which should be a control sequence such as `\kilo`) to be converted by the parser to the $\langle symbol \rangle$. The latter should consist of literal content (*e.g.* `k`). In literal mode the $\langle symbol \rangle$ will be typeset directly. In contrast to `\siunitx_declare_prefix:Nnn`, there is no assumption about the mathematical nature of the $\langle prefix \rangle$, *i.e.* the prefix may represent a power of any base. As a result, no conversion of the $\langle prefix \rangle$ to a numerical power will be possible.

```
\siunitx_declare_power>NNn \siunitx_declare_power:NNn <pre-power> <post-power> {<value>}
```

Defines *two* symbolic $\langle powers \rangle$ (which should be control sequences such as `\squared`) to be converted by the parser to the $\langle value \rangle$. The latter should be an integer or floating point number in the format defined for `I3fp`. Powers may precede a unit or be give after it: both forms are declared at once, as indicated by the argument naming. In literal mode, the $\langle value \rangle$ will be applied as a superscript to either the next token in the input (for the $\langle pre-power \rangle$) or appended to the previously-typeset material (for the $\langle post-power \rangle$).

```
\siunitx_declare_qualifier:Nn \siunitx_declare_qualifier:Nn <qualifier> {<meaning>}
```

Defines a symbolic $\langle qualifier \rangle$ (which should be a control sequence such as `\catalyst`) to be converted by the parser to the $\langle meaning \rangle$. The latter should consist of literal content (*e.g.* `cat`). In literal mode the $\langle meaning \rangle$ will be typeset following a space after the unit to which it applies.

```
\siunitx_declare_unit:Nn \siunitx_declare_unit:Nx
\siunitx_declare_unit:Nnn \siunitx_declare_unit:Nxn
```

Defines a symbolic $\langle unit \rangle$ (which should be a control sequence such as `\kilogram`) to be converted by the parser to the $\langle meaning \rangle$. The latter may consist of literal content (*e.g.* `kg`), other symbolic unit commands (*e.g.* `\kilo\gram`) or a mixture of the two. In literal mode the $\langle meaning \rangle$ will be typeset directly. The version taking an $\langle options \rangle$ argument may be used to support per-unit options: these are applied at the top level or using `\siunitx_unit_options_apply:n`.

```
\l_siunitx_unit_font_tl
```

The font function which is applied to the text of units when constructing formatted units: set by `font-command`.

\l_siunitx_unit_fraction_tl

The fraction function which is applied when constructing fractional units: set by **fraction-command**.

\l_siunitx_unit_symbolic_seq

This sequence contains all of the symbolic names defined: these will be in the form of control sequences such as `\kilogram`. The order of the sequence is unimportant. This includes prefixes and powers as well as units themselves.

\l_siunitx_unit_seq

This sequence contains all of the symbolic *unit* names defined: these will be in the form of control sequences such as `\kilogram`. In contrast to `\l_siunitx_unit_symbolic_seq`, it *only* holds units themselves

3 Per-unit options

\siunitx_unit_options_apply:n \siunitx_unit_options_apply:n <unit(s)>

Applies any unit-specific options set up using `\siunitx_declare_unit:Nnn`. This allows there use outside of unit formatting, for example to influence spacing in quantities. The options are applied only once at a given group level, which allows for user over-ride via `\keys_set:nn { siunitx } { ... }`.

4 Units in (PDF) strings

\siunitx_unit_pdfstring_context: \group_begin: \siunitx_unit_pdfstring_context: <Expansion context> <units> \group_end:

Sets symbol unit macros to generate text directly. This is needed in expansion contexts where units must be converted to simple text. This function is itself not expandable, so must be using within a surrounding group as show in the example.

5 Pre-defined symbolic unit components

The unit parser is defined to recognise a number of pre-defined units, prefixes and powers, and also interpret a small selection of “generic” symbolic parts.

Broadly, the pre-defined units are those defined by the BIPM in the documentation for the *International System of Units* (SI) [1]. As far as possible, the names given to the command names for units are those used by the BIPM, omitting spaces and using only ASCII characters. The standard symbols are also taken from the same documentation. In the following documentation, the order of the description of units broadly follows the SI Brochure.

`\kilogram` The base units as defined in the SI Brochure [2]. Notice that `\meter` is defined as an alias for `\metre` as the former spelling is common in the US (although the latter is the official spelling).
`\metre`
`\meter`
`\mole`
`\kelvin`
`\candela`
`\second`
`\ampere`

`\gram` The base unit `\kilogram` is defined using an SI prefix: as such the (derived) unit `\gram` is required by the module to correctly produce output for the `\kilogram`.

`\yocto`
`\zepto`
`\atto`
`\femto`
`\pico`
`\nano`
`\micro`
`\milli`
`\centi`
`\deci`
`\deca`
`\deka`
`\hecto`
`\kilo`
`\mega`
`\giga`
`\tera`
`\peta`
`\exa`
`\zetta`
`\yotta`

Prefixes, all of which are integer powers of 10: the powers are stored internally by the module and can be used for conversion from prefixes to their numerical equivalent. These prefixes are documented in Section 3.1 of the SI Brochure.

Note that the `\kilo` prefix is required to define the base `\kilogram` unit. Also note the two spellings available for `\deca`/`\deka`.

```
\becquerel
\degreeCelsius
\coulomb
\farad
\gray
\hertz
\henry
\joule
\katal
\lumen
\lux
\newton
\ohm
\pascal
\radian
\siemens
\sievert
\steradian
\tesla
\volt
\watt
\weber
```

The defined SI units with defined names and symbols, as given in Table 4 of the SI Brochure. Notice that the names of the units are lower case with the exception of \degreeCelsius, and that this unit name includes “degree”.

```
\astronomicalunit
\bel
\dalton
\day
\decibel
\electronvolt
\hectare
\hour
\litre
\liter
\neper
\minute
\tonne
```

Units accepted for use with the SI: here \minute is a unit of time not of plane angle. These units are taken from Table 8 of the SI Brochure.

For the unit \litre, both l and L are listed as acceptable symbols: the latter is the standard setting of the module. The alternative spelling \liter is also given for this unit for US users (as with \metre, the official spelling is “re”).

```
\arcminute
\arcsecond
\degree
```

Units for plane angles accepted for use with the SI: to avoid a clash with units for time, here \arcminute and \arcsecond are used in place of \minute and \second. These units are taken from Table 8 of the SI Brochure.

```
\percent
```

The mathematical concept of percent, usable with the SI as detailed in Section 5.4.7 of the SI Brochure.

```
\square
\cubic
```

```
\square <prefix> <unit>
\cubic <prefix> <unit>
```

Pre-defined unit powers which apply to the next $\langle prefix \rangle / \langle unit \rangle$ combination.

\squared $\langle \text{prefix} \rangle \langle \text{unit} \rangle \backslash \text{squared}$
\cubed $\langle \text{prefix} \rangle \langle \text{unit} \rangle \backslash \text{cubed}$

Pre-defined unit powers which apply to the preceding $\langle \text{prefix} \rangle / \langle \text{unit} \rangle$ combination.

\per $\backslash \text{per} \langle \text{prefix} \rangle \langle \text{unit} \rangle \langle \text{power} \rangle$

Indicates that the next $\langle \text{prefix} \rangle / \langle \text{unit} \rangle / \langle \text{power} \rangle$ combination is reciprocal, *i.e.* raises it to the power -1 . This symbolic representation may be applied in addition to a **\power**, and will work correctly if the **\power** itself is negative. In literal mode **\per** will print a slash (“/”).

\cancel $\backslash \text{cancel} \langle \text{prefix} \rangle \langle \text{unit} \rangle \langle \text{power} \rangle$

Indicates that the next $\langle \text{prefix} \rangle / \langle \text{unit} \rangle / \langle \text{power} \rangle$ combination should be “cancelled out”. In the parsed output, the entire unit combination will be given as the argument to a function **\cancel**, which is assumed to be available at a higher level. In literal mode, the same higher-level **\cancel** will be applied to the next token. It is the responsibility of the calling code to provide an appropriate definition for **\cancel** outside of the scope of the unit parser.

\highlight $\backslash \text{highlight} \{ \langle \text{color} \rangle \} \langle \text{prefix} \rangle \langle \text{unit} \rangle \langle \text{power} \rangle$

Indicates that the next $\langle \text{prefix} \rangle / \langle \text{unit} \rangle / \langle \text{power} \rangle$ combination should be highlighted in the specified $\langle \text{color} \rangle$. In the parsed output, the entire unit combination will be given as the argument to a function **\textcolor**, which is assumed to be available at a higher level. In literal mode, the same higher-level **\textcolor** will be applied to the next token. It is the responsibility of the calling code to provide an appropriate definition for **\textcolor** outside of the scope of the unit parser.

\of $\langle \text{prefix} \rangle \langle \text{unit} \rangle \langle \text{power} \rangle \backslash \text{of} \{ \langle \text{qualifier} \rangle \}$

Indicates that the $\langle \text{qualifier} \rangle$ applies to the current $\langle \text{prefix} \rangle / \langle \text{unit} \rangle / \langle \text{power} \rangle$ combination. In parsed mode, the display of the result will depend upon module options. In literal mode, the $\langle \text{qualifier} \rangle$ will be printed in parentheses following the preceding $\langle \text{unit} \rangle$ and a full-width space.

\raiseto $\backslash \text{raiseto} \{ \langle \text{power} \rangle \} \langle \text{prefix} \rangle \langle \text{unit} \rangle$
\tothe $\langle \text{prefix} \rangle \langle \text{unit} \rangle \backslash \text{tothe} \{ \langle \text{power} \rangle \}$

Indicates that the $\langle \text{power} \rangle$ applies to the current $\langle \text{prefix} \rangle / \langle \text{unit} \rangle$ combination. As shown, **\raiseto** applies to the next $\langle \text{unit} \rangle$ whereas **\tothe** applies to the preceding unit. In literal mode the **\power** will be printed as a superscript attached to the next token (**\raiseto**) or preceding token (**\tothe**) as appropriate.

5.1 Key–value options

The options defined by this submodule are available within the **\3keys siunitx** tree.

bracket-unit-denominator

bracket-unit-denominator = **true|false**

Switch to determine whether brackets are added to the denominator part of a unit when printed using inline fractional form (with **per-mode** as **repeated-symbol**, **symbol** or **symbol-or-fraction**). The standard setting is **true**.

extract-mass-in-kilograms

```
extract-mass-in-kilograms = true|false
```

Determines whether prefix extraction treats kilograms as a base unit; when set **false**, grams are used. The standard setting is **true**.

forbid-literal-units

```
forbid-literal-units = true|false
```

Switch which determines if literal units are allowed when parsing is active; does not apply when **parse-units** is **false**.

fraction-command

```
fraction-command = <command>
```

Command used to create fractional output when **per-mode** is set to **fraction**. The standard setting is `\frac`.

inter-unit-product

```
inter-unit-product = <separator>
```

Inserted between unit combinations in parsed mode, and used to replace `.` and `~` in literal mode. The standard setting is `\,.`.

parse-units

```
parse-units = true|false
```

Determines whether parsing of unit symbols is attempted or literal mode is used directly. The standard setting is **true**.

per-mode

```
per-mode =  
fraction|power|power-positive-first|repeated-symbol|symbol|symbol-or-fraction
```

Selects how the negative powers (`\per`) are formatted: a choice from the options **fraction**, **power**, **power-positive-first**, **repeated-symbol**, **symbol** and **symbol-or-fraction**. The option **fraction** generates fractional output when appropriate using the command specified by the **fraction-command** option. The setting **power** uses reciprocal powers leaving the units in the order of input, while **power-positive-first** uses the same display format but sorts units such that the positive powers come before negative ones. The **symbol** setting uses a symbol (specified by **per-symbol**) between positive and negative powers, while **repeated-symbol** uses the same symbol but places it before *every* unit with a negative power (this is mathematically “wrong” but often seen in real work). Finally, **symbol-or-fraction** acts like **symbol** for inline output and like **fraction** when the output is used in a display math environment. The standard setting is **power**.

per-symbol

```
per-symbol = <symbol>
```

Specifies the symbol to be used to denote negative powers when the option **per-mode** is set to **repeated-symbol**, **symbol** or **symbol-or-fraction**. The standard setting is `/`.

qualifier-mode

```
qualifier-mode = bracket|combine|phrase|subscript
```

Selects how qualifiers are formatted: a choice from the options **bracket**, **combine**, **phrase** and **subscript**. The option **bracket** wraps the qualifier in parenthesis, **combine** joins the qualifier with the unit directly, **phrase** joins the material using **qualifier-phrase** as a link, and **subscript** formats the qualifier as a subscript. The standard setting is **subscript**.

qualifier-phrase

```
qualifier-phrase = <phrase>
```

Defines the `<phrase>` used when **qualifier-mode** is set to **phrase**.

sticky-per `sticky-per = true|false`

Used to determine whether `\per` should be applied one a unit-by-unit basis (when `false`) or should apply to all following units (when `true`). The latter mode is somewhat akin conceptually to the TeX `\over` primitive. The standard setting is `false`.

unit-font-command `unit-font-command = <command>`

Command applied to text during output of units: should be command usable in math mode for font selection. Notice that in a typical unit this does not (necessarily) apply to all output, for example powers or brackets. The standard setting is `\mathrm`.

6 siunitx-unit implementation

Start the DocStrip guards.

`1 (*package)`

Identify the internal prefix (LATEX3 DocStrip convention): only internal material in this *submodule* should be used directly.

`2 (@@=siunitx_unit)`

6.1 Initial set up

The mechanisms defined here need a few variables to exist and to be correctly set: these don't belong to one subsection and so are created in a small general block.

Variants not provided by `expl3`.

`3 \cs_generate_variant:Nn \tl_replace_all:Nnn { NnV }`

`\l_siunitx_unit_tmp_fp` Scratch space.

`4 \fp_new:N \l_siunitx_unit_tmp_fp`
`5 \int_new:N \l_siunitx_unit_tmp_int`
`6 \tl_new:N \l_siunitx_unit_tmp_tl`

(*End definition for* `\l_siunitx_unit_tmp_fp`, `\l_siunitx_unit_tmp_int`, and `\l_siunitx_unit_tmp_tl`.)

`\c_siunitx_unit_math_subscript_tl` Useful tokens with awkward category codes.

`7 \tl_const:Nx \c_siunitx_unit_math_subscript_tl`
`8 { \char_generate:nn { '_ } { 8 } }`

(*End definition for* `\c_siunitx_unit_math_subscript_tl`.)

`\l_siunitx_unit_parsing_bool`

A boolean is used to indicate when the symbolic unit functions should produce symbolic or literal output. This is used when the symbolic names are used along with literal input, and ensures that there is a sensible fall-back for these cases.

`9 \bool_new:N \l_siunitx_unit_parsing_bool`

(*End definition for* `\l_siunitx_unit_parsing_bool`.)

`\l_siunitx_unit_test_bool`

A switch used to indicate that the code is testing the input to find if there is any typeset output from individual unit macros. This is needed to allow the “base” macros to be found, and also to pick up the difference between symbolic and literal unit input.

`10 \bool_new:N \l_siunitx_unit_test_bool`

(End definition for `\l_siunitx_unit_test_bool`.)

`_siunitx_unit_if_symbolic:nTF`

The test for symbolic units is needed in two places. First, there is the case of “pre-parsing” input to check if it can be parsed. Second, when parsing there is a need to check if the current unit is built up from others (symbolic) or is defined in terms of some literals. To do this, the approach used is to set all of the symbolic unit commands expandable and to do nothing, with the few special cases handled manually.

```
11 \prg_new_protected_conditional:Npnn \_siunitx_unit_if_symbolic:n #1 { TF }
12   {
13     \group_begin:
14       \bool_set_true:N \l_siunitx_unit_test_bool
15       \protected@edef \l_siunitx_unit_tmp_t1 {\#1}
16     \exp_args:NNV \group_end:
17     \tl_if_blank:nTF \l_siunitx_unit_tmp_t1
18       { \prg_return_true: }
19       { \prg_return_false: }
20   }
```

(End definition for `_siunitx_unit_if_symbolic:nTF`.)

6.2 Defining symbolic unit

Unit macros and related support are created here. These exist only within the scope of the unit processor code, thus not polluting document-level namespace and allowing overlap with other areas in the case of useful short names (for example `\pm`). Setting up the mechanisms to allow this requires a few additional steps on top of simply saving the data given by the user in creating the unit.

`\l_siunitx_unit_symbolic_seq`

A list of all of the symbolic units, *etc.*, set up. This is needed to allow the symbolic names to be defined within the scope of the unit parser but not elsewhere using simple mappings.

```
21 \seq_new:N \l_siunitx_unit_symbolic_seq
```

(End definition for `\l_siunitx_unit_symbolic_seq`. This variable is documented on page 140.)

`\l_siunitx_unit_seq`

A second list featuring only the units themselves.

```
22 \seq_new:N \l_siunitx_unit_seq
```

(End definition for `\l_siunitx_unit_seq`. This variable is documented on page 140.)

`_siunitx_unit_set_symbolic:Nnn`
`_siunitx_unit_set_symbolic:Npnn`
`_siunitx_unit_set_symbolic:Nnnn`

The majority of the work for saving each symbolic definition is the same irrespective of the item being defined (unit, prefix, power, qualifier). This is therefore all carried out in a single internal function which does the common tasks. The three arguments here are the symbolic macro name, the literal output and the code to insert when doing full unit parsing. To allow for the “special cases” (where arguments are required) the entire mechanism is set up in a two-part fashion allowing for flexibility at the slight cost of additional functions.

Importantly, notice that the unit macros are declared as expandable. This is required so that literals can be correctly converted into a token list of material which does not depend on local redefinitions for the unit macros. That is required so that the unit formatting system can be grouped.

```
23 \cs_new_protected:Npn \_siunitx_unit_set_symbolic:Nnn #1
24   { \_siunitx_unit_set_symbolic:Nnnn #1 { } }
```

```

25 \cs_new_protected:Npn \__siunitx_unit_set_symbolic:Npnn #1#2#
26   { \__siunitx_unit_set_symbolic:Nnnn #1 {#2} }
27 \cs_new_protected:Npn \__siunitx_unit_set_symbolic:Nnnn #1#2#3#4
28   {
29     \seq_put_right:Nn \l__siunitx_unit_symbolic_seq {#1}
30     \cs_set:cpn {__siunitx_unit_} \token_to_str:N #1 :w } #2
31   {
32     \bool_if:NF \l__siunitx_unit_test_bool
33     {
34       \bool_if:NTF \l__siunitx_unit_parsing_bool
35         {#4}
36         {#3}
37     }
38   }
39 }

(End definition for \__siunitx_unit_set_symbolic:Nnn, \__siunitx_unit_set_symbolic:Npnn, and
\__siunitx_unit_set_symbolic:Nnnn.)
```

\siunitx_declare_power:NNn

Powers can come either before or after the unit. As they always come (logically) in matching, we handle this by declaring two commands, and setting each up separately.

```

40 \cs_new_protected:Npn \siunitx_declare_power:NNn #1#2#3
41   {
42     \__siunitx_unit_set_symbolic:Nnn #1
43     { \__siunitx_unit_literal_power:nn {#3} }
44     { \__siunitx_unit_parse_power:nnN {#1} {#3} \c_true_bool }
45     \__siunitx_unit_set_symbolic:Nnn #2
46     { ^ {#3} }
47     { \__siunitx_unit_parse_power:nnN {#2} {#3} \c_false_bool }
48 }
```

(End definition for \siunitx_declare_power:NNn. This function is documented on page 139.)

\siunitx_declare_prefix:Nn

\siunitx_declare_prefix:Nnn

\siunitx_declare_prefix:Nnx

For prefixes there are a couple of options. In all cases, the basic requirement is to set up to parse the prefix using the appropriate internal function. For prefixes which are powers of 10, there is also the need to be able to do conversion to/from the numerical equivalent. That is handled using two properly lists which can be used to supply the conversion data later.

```

49 \cs_new_protected:Npn \siunitx_declare_prefix:Nn #1#2
50   {
51     \__siunitx_unit_set_symbolic:Nnn #1
52     {#2}
53     { \__siunitx_unit_parse_prefix:Nn #1 {#2} }
54   }
55 \cs_new_protected:Npn \siunitx_declare_prefix:Nnn #1#2#3
56   {
57     \siunitx_declare_prefix:Nn #1 {#3}
58     \prop_put:Nnn \l__siunitx_unit_prefixes_forward_prop {#3} {#2}
59     \prop_put:Nnn \l__siunitx_unit_prefixes_reverse_prop {#2} {#3}
60   }
61 \cs_generate_variant:Nn \siunitx_declare_prefix:Nnn { Nnx }
62 \prop_new:N \l__siunitx_unit_prefixes_forward_prop
63 \prop_new:N \l__siunitx_unit_prefixes_reverse_prop
```

(End definition for `\siunitx_declare_prefix:Nn` and others. These functions are documented on page 139.)

`\siunitx_declare_qualifier:Nn` Qualifiers are relatively easy to handle: nothing to do other than save the input appropriately.

```
64 \cs_new_protected:Npn \siunitx_declare_qualifier:Nn #1#2
65   {
66     \_siunitx_unit_set_symbolic:Nnn #1
67     { ~ ( #2 ) }
68     { \_siunitx_unit_parse_qualifier:nn {#1} {#2} }
69   }
```

(End definition for `\siunitx_declare_qualifier:Nn`. This function is documented on page 139.)

`\siunitx_declare_unit:Nn`
`\siunitx_declare_unit:Nx`
`\siunitx_declare_unit:Nnn`
`\siunitx_declare_unit:Nxn` For the unit parsing, allowing for variations in definition order requires that a test is made for the output of each unit at point of use.

```
70 \cs_new_protected:Npn \siunitx_declare_unit:Nn #1#2
71   { \siunitx_declare_unit:Nnn #1 {#2} { } }
72 \cs_generate_variant:Nn \siunitx_declare_unit:Nn { Nx }
73 \cs_new_protected:Npn \siunitx_declare_unit:Nnn #1#2#3
74   {
75     \seq_put_right:Nn \l_siunitx_unit_seq {#1}
76     \_siunitx_unit_set_symbolic:Nnn #1
77     {#2}
78     {
79       \_siunitx_unit_if_symbolic:nTF {#2}
80       {#2}
81       { \_siunitx_unit_parse_unit:Nn #1 {#2} }
82     }
83     \tl_clear_new:c { l_siunitx_unit_options_ \token_to_str:N #1 _tl }
84     \tl_if_empty:nF {#3}
85     { \tl_set:cn { l_siunitx_unit_options_ \token_to_str:N #1 _tl } {#3} }
86   }
87 \cs_generate_variant:Nn \siunitx_declare_unit:Nnn { Nx }
```

(End definition for `\siunitx_declare_unit:Nn` and `\siunitx_declare_unit:Nnn`. These functions are documented on page 139.)

6.3 Applying unit options

```
\l_siunitx_unit_options_bool
88 \bool_new:N \l_siunitx_unit_options_bool
(End definition for \l_siunitx_unit_options_bool.)
```

`\siunitx_unit_options_apply:n` Options apply only if they have not already been set at this group level.

```
89 \cs_new_protected:Npn \siunitx_unit_options_apply:n #1
90   {
91     \bool_if:NF \l_siunitx_unit_options_bool
92     {
93       \tl_if_single_token:nT {#1}
94       {
95         \tl_if_exist:cT { l_siunitx_unit_options_ \token_to_str:N #1 _tl }
96       }
97     }
98   }
```

```

97          \keys_set:nv { siunitx }
98          { l_siunitx_unit_options_ \token_to_str:N #1 _tl }
99      }
100     }
101   }
102   \bool_set_true:N \l_siunitx_unit_options_bool
103 }

```

(End definition for `\siunitx_unit_options_apply:n`. This function is documented on page 140.)

6.4 Non-standard symbolic units

A few of the symbolic units require non-standard definitions: these are created here. They all use parts of the more general code but have particular requirements which can only be addressed by hand. Some of these could in principle be used in place of the dedicated definitions above, but at point of use that would then require additional expansions for each unit parsed: as the macro names would still be needed, this does not offer any real benefits.

- \per** The `\per` symbolic unit is a bit special: it has a mechanism entirely different from everything else, so has to be set up by hand. In literal mode it is represented by a very simple symbol!

```

104 \__siunitx_unit_set_symbolic:Nnn \per
105   { / }
106   { \__siunitx_unit_parse_per: }

```

(End definition for `\per`. This function is documented on page 143.)

- \cancel** The two special cases, `\cancel` and `\highlight`, are easy to deal with when parsing.
\highlight When not parsing, a precaution is taken to ensure that the user level equivalents always get a braced argument.

```

107 \__siunitx_unit_set_symbolic:Npnn \cancel
108   { }
109   { \__siunitx_unit_parse_special:n { \cancel } }
110 \__siunitx_unit_set_symbolic:Npnn \highlight #1
111   { \__siunitx_unit_literal_special:nN { \textcolor{#1}{} } }
112   { \__siunitx_unit_parse_special:n { \textcolor{#1}{} } }

```

(End definition for `\cancel` and `\highlight`. These functions are documented on page 143.)

- \of** The generic qualifier is simply the same as the dedicated ones except for needing to grab an argument.

```

113 \__siunitx_unit_set_symbolic:Npnn \of #1
114   { \ ( #1 ) }
115   { \__siunitx_unit_parse_qualifier:nn { \of {#1} } {#1} }

```

(End definition for `\of`. This function is documented on page 143.)

- \raiseto** Generic versions of the pre-defined power macros. These require an argument and so cannot be handled using the general approach. Other than that, the code here is very similar to that in `\siunitx_unit_power_set:NnN`.

```

116 \__siunitx_unit_set_symbolic:Npnn \raiseto #1
117   { \__siunitx_unit_literal_power:nn {#1} }
118   { \__siunitx_unit_parse_power:nnN { \raiseto {#1} } {#1} \c_true_bool }

```

```

119 \_siunitx_unit_set_symbolic:Npnn \tothe #1
120 { ^ {#1} }
121 { \_siunitx_unit_parse_power:nnN { \tothe {#1} } {#1} \c_false_bool }

```

(End definition for `\raiseto` and `\tothe`. These functions are documented on page 143.)

6.5 Main formatting routine

Unit input can take two forms, “literal” units (material to be typeset directly) or “symbolic” units (macro-based). Before any parsing or typesetting is carried out, a small amount of pre-parsing has to be carried out to decide which of these cases applies.

`\l_siunitx_unit_font_tl` Options which apply to the main formatting routine, and so are not tied to either symbolic or literal input.

```

122 \keys_define:nn { siunitx }
123 {
124   extract-mass-in-kilograms .bool_set:N =
125     \l_siunitx_unit_mass_kilogram_bool ,
126   inter-unit-product .tl_set:N =
127     \l_siunitx_unit_product_tl ,
128   unit-font-command .tl_set:N =
129     \l_siunitx_unit_font_tl
130 }

```

(End definition for `\l_siunitx_unit_font_tl`, `\l_siunitx_unit_product_tl`, and `\l_siunitx_unit_mass_kilogram_bool`. This variable is documented on page 139.)

`\l_siunitx_unit_formatted_tl` A token list for the final formatted result: may or may not be generated by the parser, depending on the nature of the input.

```
131 \tl_new:N \l_siunitx_unit_formatted_tl
```

(End definition for `\l_siunitx_unit_formatted_tl`.)

`\siunitx_unit_format:nN` `\siunitx_unit_format_extract_prefixes:nNN` `\siunitx_unit_format_combine_exponent:nnN` `\siunitx_unit_format_multiply:nnN` `\siunitx_unit_format_multiply_extract_prefixes:nnNN` `\siunitx_unit_format_multiply_combine_exponent:nnNN` `_siunitx_unit_format:nNN` `_siunitx_unit_format_aux:` Formatting parsed units can take place either with the prefixes printed or separated out into a power of ten. This variation is handled using two separate functions: as this submodule does not really deal with numbers, formatting the numeral part here would be tricky and it is better therefore to have a mechanism to return a simple numerical power. At the same time, most uses will no want this more complex return format and so a version of the code which does not do this is also provided.

The main unit formatting routine groups all of the parsing/formatting, so that the only value altered will be the return token list. As definitions for the various unit macros are not globally created, the first step is to map over the list of names and active the unit definitions: these do different things depending on the switches set. There is then a decision to be made: is the unit input one that can be parsed (“symbolic”), or is it one containing one or more literals. In the latter case, there is still the need to convert the input into an expanded token list as some parts of the input could still be using unit macros.

Notice that for `\siunitx_unit_format:nN` a second return value from the auxiliary has to be allowed for, but is simply discarded.

```

132 \cs_new_protected:Npn \siunitx_unit_format:nN #1#2
133 {
134   \bool_set_false:N \l_siunitx_unit_prefix_exp_bool
135   \fp_zero:N \l_siunitx_unit_combine_exp_fp

```

```

136      \fp_set:Nn \l_siunitx_unit_multiple_fp { \c_one_fp }
137      \_siunitx_unit_format:nNN {#1} #2 \l_siunitx_unit_tmp_fp
138    }
139  \cs_new_protected:Npn \siunitx_unit_format_extract_prefixes:nNN #1#2#3
140  {
141    \bool_set_true:N \l_siunitx_unit_prefix_exp_bool
142    \fp_zero:N \l_siunitx_unit_combine_exp_fp
143    \fp_set:Nn \l_siunitx_unit_multiple_fp { \c_one_fp }
144    \_siunitx_unit_format:nNN {#1} #2 #3
145  }
146  \cs_new_protected:Npn \siunitx_unit_format_combine_exponent:nnN #1#2#3
147  {
148    \bool_set_false:N \l_siunitx_unit_prefix_exp_bool
149    \fp_set:Nn \l_siunitx_unit_combine_exp_fp {#2}
150    \fp_set:Nn \l_siunitx_unit_multiple_fp { \c_one_fp }
151    \_siunitx_unit_format:nNN {#1} #3 \l_siunitx_unit_tmp_fp
152  }
153  \cs_new_protected:Npn \siunitx_unit_format_multiply:nnN #1#2#3
154  {
155    \bool_set_false:N \l_siunitx_unit_prefix_exp_bool
156    \fp_zero:N \l_siunitx_unit_combine_exp_fp
157    \fp_set:Nn \l_siunitx_unit_multiple_fp {#2}
158    \_siunitx_unit_format:nNN {#1} #3 \l_siunitx_unit_tmp_fp
159  }
160  \cs_new_protected:Npn \siunitx_unit_format_multiply_extract_prefixes:nnNN
161  #1#2#3#4
162  {
163    \bool_set_true:N \l_siunitx_unit_prefix_exp_bool
164    \fp_zero:N \l_siunitx_unit_combine_exp_fp
165    \fp_set:Nn \l_siunitx_unit_multiple_fp {#2}
166    \_siunitx_unit_format:nNN {#1} #3 #4
167  }
168  \cs_new_protected:Npn \siunitx_unit_format_multiply_combine_exponent:nnnN
169  #1#2#3#4
170  {
171    \bool_set_false:N \l_siunitx_unit_prefix_exp_bool
172    \fp_set:Nn \l_siunitx_unit_combine_exp_fp {#3}
173    \fp_set:Nn \l_siunitx_unit_multiple_fp {#2}
174    \_siunitx_unit_format:nNN {#1} #4 \l_siunitx_unit_tmp_fp
175  }
176  \cs_new_protected:Npn \_siunitx_unit_format:nNN #1#2#3
177  {
178    \group_begin:
179    \seq_map_inline:Nn \l_siunitx_unit_symbolic_seq
180      { \cs_set_eq:Nc ##1 { \_siunitx_unit_ \token_to_str:N ##1 :w } }
181    \tl_clear:N \l_siunitx_unit_formatted_tl
182    \fp_zero:N \l_siunitx_unit_prefix_fp
183    \bool_if:NTF \l_siunitx_unit_parse_bool
184      {
185        \_siunitx_unit_if_symbolic:nTF {#1}
186      }
187      \_siunitx_unit_parse:n {#1}
188      \prop_if_empty:NF \l_siunitx_unit_parsed_prop
189      { \_siunitx_unit_format_parsed: }

```

```

190      }
191      {
192          \bool_if:NTF \l_siunitx_unit_forbid_literal_bool
193              { \msg_error:nnn { siunitx } { unit / literal } {#1} }
194              { \l_siunitx_unit_format_literal:n {#1} }
195      }
196  }
197  { \l_siunitx_unit_format_literal:n {#1} }
198 \cs_set_protected:Npx \l_siunitx_unit_format_aux:
199  {
200      \tl_set:Nn \exp_not:N #2
201          { \exp_not:V \l_siunitx_unit_formatted_tl }
202      \fp_set:Nn \exp_not:N #3
203          { \fp_use:N \l_siunitx_unit_prefix_fp }
204  }
205  \exp_after:wN \group_end:
206  \l_siunitx_unit_format_aux:
207 }
208 \cs_new_protected:Npn \l_siunitx_unit_format_aux: { }

(End definition for \siunitx_unit_format:nN and others. These functions are documented on page
137.)

```

6.6 Formatting literal units

While in literal mode no parsing occurs, there is a need to provide a few auxiliary functions to handle one or two special cases.

For printing literal units which are given before the unit they apply to, there is a slight rearrangement. This is ex[EXP]pandable to cover the case of creation of a PDF string.

```

209 \cs_new:Npn \l_siunitx_unit_literal_power:nn #1#2 { #2 ^ {#1} }

(End definition for \l_siunitx_unit_literal_power:nn.)

```

When dealing with the special cases, there is an argument to absorb. This should be braced to be passed up to the user level, which is dealt with here.

```

210 \cs_new:Npn \l_siunitx_unit_literal_special:nN #1#2 { #1 {#2} }

(End definition for \l_siunitx_unit_literal_special:nN.)

```

To format literal units, there are two tasks to do. The input is x-type expanded to force any symbolic units to be converted into their literal representation: this requires setting the appropriate switch. In the resulting token list, all . and ~ tokens are then replaced by the current unit product token list. To enable this to happen correctly with a normal (active) ~, a small amount of “protection” is needed first. To cover active sub- and superscript tokens, appropriate definitions are provided at this stage. Those have to be expandable macros rather than implicit character tokens.

As with other code dealing with user input, \protected@edef is used here rather than \tl_set:Nx as L^AT_EX 2 _{ϵ} robust commands may be present.

```

211 \group_begin:
212     \char_set_catcode_active:n { '\~ }
213     \cs_new_protected:Npx \l_siunitx_unit_format_literal:n #1
214     {
215         \group_begin:

```

```

216   \exp_not:n { \bool_set_false:N \l_siunitx_unit_parsing_bool }
217   \tl_set:Nn \exp_not:N \l_siunitx_unit_tmp_tl {#1}
218   \tl_replace_all:Nnn \exp_not:N \l_siunitx_unit_tmp_tl
219     { \token_to_str:N ^ } { ^ }
220   \tl_replace_all:Nnn \exp_not:N \l_siunitx_unit_tmp_tl
221     { \token_to_str:N _ } { \c_siunitx_unit_math_subscript_tl }
222   \char_set_active_eq:NN ^
223     \exp_not:N \_siunitx_unit_format_literal_superscript:
224   \char_set_active_eq:NN -
225     \exp_not:N \_siunitx_unit_format_literal_subscript:
226   \char_set_active_eq:NN \exp_not:N ~
227     \exp_not:N \_siunitx_unit_format_literal_tilde:
228   \exp_not:n
229   {
230     \protected@edef \l_siunitx_unit_tmp_tl
231       { \l_siunitx_unit_tmp_tl }
232     \tl_clear:N \l_siunitx_unit_formatted_tl
233     \tl_if_empty:NF \l_siunitx_unit_tmp_tl
234     {
235       \exp_after:wN \_siunitx_unit_format_literal_auxi:w
236         \l_siunitx_unit_tmp_tl .
237         \q_recursion_tail . \q_recursion_stop
238     }
239   \exp_args:NNNV \group_end:
240   \tl_set:Nn \l_siunitx_unit_formatted_tl
241     \l_siunitx_unit_formatted_tl
242   }
243 }
244 \group_end:
245 \cs_new:Npx \_siunitx_unit_format_literal_subscript: { \c_siunitx_unit_math_subscript_tl }
246 \cs_new:Npn \_siunitx_unit_format_literal_superscript: { ^ }
247 \cs_new:Npn \_siunitx_unit_format_literal_tilde: { . }

```

To introduce the font changing commands while still allowing for line breaks in literal units, a loop is needed to replace one . at a time. To also allow for division, a second loop is used within that to handle /: as a result, the separator between parts has to be tracked.

```

248 \cs_new_protected:Npn \_siunitx_unit_format_literal_auxi:w #1 .
249   {
250     \quark_if_recursion_tail_stop:n {#1}
251     \_siunitx_unit_format_literal_auxii:n {#1}
252     \tl_set_eq:NN \l_siunitx_unit_separator_tl \l_siunitx_unit_product_tl
253       \_siunitx_unit_format_literal_auxi:w
254   }
255 \cs_set_protected:Npn \_siunitx_unit_format_literal_auxii:n #1
256   {
257     \_siunitx_unit_format_literal_auxiii:w
258       #1 / \q_recursion_tail / \q_recursion_stop
259   }
260 \cs_new_protected:Npn \_siunitx_unit_format_literal_auxiii:w #1 /
261   {
262     \quark_if_recursion_tail_stop:n {#1}
263     \_siunitx_unit_format_literal_auxiv:n {#1}
264     \tl_set:Nn \l_siunitx_unit_separator_tl { / }

```

```

265      \_siunitx_unit_format_literal_auxiii:w
266    }
267 \cs_new_protected:Npn \_siunitx_unit_format_literal_auxiv:n #1
268 {
269   \_siunitx_unit_format_literal_auxv:nw { }
270   #1 \q_recursion_tail \q_recursion_stop
271 }

```

To deal properly with literal formatting, we have to worry about super- and subscript markers. That can be complicated as they could come anywhere in the input: we handle that by iterating through the input and picking them out. This avoids any issue with losing braces for mid-input scripts. We also have to deal with fractions, hence needing a series of nested loops and a change of separator.

```

272 \cs_new_protected:Npn \_siunitx_unit_format_literal_auxv:nw
273   #1#2 \q_recursion_stop
274 {
275   \tl_if_head_is_N_type:nTF {#2}
276   { \_siunitx_unit_format_literal_auxvi:nN }
277   { \_siunitx_unit_format_literal_auxvii:nn }
278   {#1} #2 \q_recursion_stop
279 }
280 \cs_new_protected:Npx \_siunitx_unit_format_literal_auxvi:nN #1#2
281 {
282   \exp_not:N \quark_if_recursion_tail_stop_do:Nn #2
283   { \exp_not:N \_siunitx_unit_format_literal_add:n {#1} }
284   \exp_not:N \token_if_eq_meaning:NNTF #2 ^
285   { \exp_not:N \_siunitx_unit_format_literal_super:nn {#1} }
286   {
287     \exp_not:N \token_if_eq_meaning:NNTF
288     #2 \c_siunitx_unit_math_subscript_tl
289     { \exp_not:N \_siunitx_unit_format_literal_sub:nn {#1} }
290     { \exp_not:N \_siunitx_unit_format_literal_auxvii:nN {#1} #2 }
291   }
292 }

```

We need to make sure \protect sticks with the next token.

```

293 \cs_new_protected:Npn \_siunitx_unit_format_literal_auxvii:nN #1#2
294 {
295   \str_if_eq:nnTF {#2} { \protect }
296   { \_siunitx_unit_format_literal_auxviii:nN {#1} }
297   { \_siunitx_unit_format_literal_auxvi:nN {#1#2} }
298 }
299 \cs_new_protected:Npn \_siunitx_unit_format_literal_auxviii:nN #1#2
300   { \_siunitx_unit_format_literal_auxv:nw { #1 \protect #2 } }
301 \cs_new_protected:Npn \_siunitx_unit_format_literal_super:nn #1#2
302 {
303   \quark_if_recursion_tail_stop:n {#2}
304   \_siunitx_unit_format_literal_add:n {#1}
305   \tl_put_right:Nn \l_siunitx_unit_formatted_tl { ^ {#2} }
306   \_siunitx_unit_format_literal_auxvi:nN { }
307 }
308 \cs_new_protected:Npx \_siunitx_unit_format_literal_sub:nn #1#2
309 {
310   \exp_not:N \quark_if_recursion_tail_stop:n {#2}
311   \exp_not:N \_siunitx_unit_format_literal_add:n {#1}

```

```

312   \tl_put_right:Nx \exp_not:N \l_siunitx_unit_formatted_tl
313   {
314     \c_siunitx_unit_math_subscript_tl
315     {
316       \exp_not:N \exp_not:V
317       \exp_not:N \l_siunitx_unit_font_tl
318       { \exp_not:N \exp_not:n {#2} }
319     }
320   }
321   \exp_not:N \__siunitx_unit_format_literal_auxvi:nN { }
322 }
323 \cs_new_protected:Npn \__siunitx_unit_format_literal_add:n #1
324 {
325   \tl_put_right:Nx \l_siunitx_unit_formatted_tl
326   {
327     \tl_if_empty:NF \l_siunitx_unit_formatted_tl
328     { \exp_not:V \l_siunitx_unit_separator_tl }
329     \tl_if_empty:nF {#1}
330     { \exp_not:V \l_siunitx_unit_font_tl { \exp_not:n {#1} } }
331   }
332   \tl_clear:N \l_siunitx_unit_separator_tl
333 }
334 \cs_new_protected:Npn \__siunitx_unit_format_literal_auxvii:nn #1#2
335 { \__siunitx_unit_format_literal_auxvi:nN { #1 {#2} } }
336 \tl_new:N \l_siunitx_unit_separator_tl

```

(End definition for `__siunitx_unit_format_literal:n` and others.)

6.7 (PDF) String creation

`\siunitx_unit_pdfstring_context:` A simple function that sets up to make units equal to their text representation.

```

337 \cs_new_protected:Npn \siunitx_unit_pdfstring_context:
338 {
339   \bool_set_false:N \l_siunitx_unit_parsing_bool
340   \seq_map_inline:Nn \l_siunitx_unit_symbolic_seq
341   { \cs_set_eq:Nc ##1 { \__siunitx_unit_ \token_to_str:N ##1 :w } }
342 }

```

(End definition for `\siunitx_unit_pdfstring_context:`. This function is documented on page 140.)

6.8 Parsing symbolic units

Parsing units takes place by storing information about each unit in a `prop`. As well as the unit itself, there are various other optional data points, for example a prefix or a power. Some of these can come before the unit, others only after. The parser therefore tracks the number of units read and uses the current position to allocate data to individual units.

The result of parsing is a property list (`\l_siunitx_unit_parsed_prop`) which contains one or more entries for each unit:

- `prefix-n` The symbol for the prefix which applies to this unit, *e.g.* for `\kilo` with (almost certainly) would be `k`.
- `unit-n` The symbol for the unit itself, *e.g.* for `\metre` with (almost certainly) would be `m`.

- **power-*n*** The power which a unit is raised to. During initial parsing this will (almost certainly) be positive, but is combined with **per-*n*** to give a “fully qualified” power before any formatting takes place
- **per-*n*** Indicates that **per** applies to the current unit: stored during initial parsing then combined with **power-*n*** (and removed from the list) before further work.
- **qualifier-*n*** Any qualifier which applies to the current unit.
- **special-*n*** Any “special effect” to apply to the current unit.
- **command-1** The command corresponding to **unit-*n***: needed to track base units; used for **\gram** only.

`\l_siunitx_unit_sticky_per_bool`

There is one option when *parsing* the input (as opposed to *formatting* for output): how to deal with **\per**.

```
343 \keys_define:nn { siunitx }
344   {
345     sticky-per .bool_set:N = \l_siunitx_unit_sticky_per_bool
346   }
```

(End definition for `\l_siunitx_unit_sticky_per_bool`.)

`\l_siunitx_unit_parsed_prop`
`\l_siunitx_unit_per_bool`
`\l_siunitx_unit_position_int`

Parsing units requires a small number of variables are available: a **prop** for the parsed units themselves, a **bool** to indicate if **\per** is active and an **int** to track how many units have been parsed.

```
347 \prop_new:N \l_siunitx_unit_parsed_prop
348 \bool_new:N \l_siunitx_unit_per_bool
349 \int_new:N \l_siunitx_unit_position_int
```

(End definition for `\l_siunitx_unit_parsed_prop`, `\l_siunitx_unit_per_bool`, and `\l_siunitx_unit_position_int`.)

`_siunitx_unit_parse:n`

The main parsing function is quite simple. After initialising the variables, each symbolic unit is set up. The input is then simply inserted into the input stream: the symbolic units themselves then do the real work of placing data into the parsing system. There is then a bit of tidying up to ensure that later stages can rely on the nature of the data here.

```
350 \cs_new_protected:Npn \_siunitx_unit_parse:n #1
351   {
352     \prop_clear:N \l_siunitx_unit_parsed_prop
353     \bool_set_true:N \l_siunitx_unit_parsing_bool
354     \bool_set_false:N \l_siunitx_unit_per_bool
355     \bool_set_false:N \l_siunitx_unit_test_bool
356     \int_zero:N \l_siunitx_unit_position_int
357     \siunitx_unit_options_apply:n {#1}
358     #1
359     \int_step_inline:nn \l_siunitx_unit_position_int
360       { \_siunitx_unit_parse_finalise:n {##1} }
361     \_siunitx_unit_parse_finalise:
362   }
```

(End definition for `_siunitx_unit_parse:n`.)

```
\_siunitx_unit_parse_add:nnnn
```

In all cases, storing a data item requires setting a temporary `t1` which will be used as the key, then using this to store the value. The `t1` is set using x-type expansion as this will expand the unit index and any additional calculations made for this.

```
363 \cs_new_protected:Npn \_siunitx_unit_parse_add:nnnn #1#2#3#4
364 {
365   \tl_set:Nx \l_siunitx_unit_tmp_t1 { #1 - #2 }
366   \prop_if_in:NVTF \l_siunitx_unit_parsed_prop
367     \l_siunitx_unit_tmp_t1
368   {
369     \msg_error:nxxx { siunitx } { unit / duplicate-part }
370     { \exp_not:n {#1} } { \token_to_str:N #3 }
371   }
372   {
373     \prop_put:NVn \l_siunitx_unit_parsed_prop
374       \l_siunitx_unit_tmp_t1 {#4}
375   }
376 }
```

(End definition for `_siunitx_unit_parse_add:nnnn`.)

```
\_siunitx_unit_parse_prefix:Nn
\_siunitx_unit_parse_power:nnN
\_siunitx_unit_parse_qualifier:nn
\_siunitx_unit_parse_special:n
```

Storage of the various optional items follows broadly the same pattern in each case. The data to be stored is passed along with an appropriate key name to the underlying storage system. The details for each type of item should be relatively clear. For example, prefixes have to come before their “parent” unit and so there is some adjustment to do to add them to the correct unit.

```
377 \cs_new_protected:Npn \_siunitx_unit_parse_prefix:Nn #1#2
378 {
379   \int_set:Nn \l_siunitx_unit_tmp_int { \l_siunitx_unit_position_int + 1 }
380   \_siunitx_unit_parse_add:nnnn { prefix }
381   { \int_use:N \l_siunitx_unit_tmp_int } {#1} {#2}
382 }
383 \cs_new_protected:Npn \_siunitx_unit_parse_power:nnN #1#2#3
384 {
385   \tl_set:Nx \l_siunitx_unit_tmp_t1
386   { unit- \int_use:N \l_siunitx_unit_position_int }
387   \bool_lazy_or:nnTF
388   {#3}
389   {
390     \prop_if_in_p:NV
391       \l_siunitx_unit_parsed_prop \l_siunitx_unit_tmp_t1
392   }
393   {
394     \_siunitx_unit_parse_add:nnnn { power }
395     {
396       \int_eval:n
397         { \l_siunitx_unit_position_int \bool_if:NT #3 { + 1 } }
398     }
399     {#1} {#2}
400   }
401   {
402     \msg_error:nxxx { siunitx }
403     { unit / part-before-unit } { power } { \token_to_str:N #1 }
404   }
405 }
```

```

406 \cs_new_protected:Npn \_siunitx_unit_parse_qualifier:nn #1#2
407   {
408     \tl_set:Nx \l__siunitx_unit_tmp_tl
409       { unit- \int_use:N \l__siunitx_unit_position_int }
410     \prop_if_in:NVTF \l__siunitx_unit_parsed_prop \l__siunitx_unit_tmp_tl
411       {
412         \_siunitx_unit_parse_add:nnnn { qualifier }
413           { \int_use:N \l__siunitx_unit_position_int } {#1} {#2}
414       }
415       {
416         \msg_error:nnnn { siunitx }
417           { unit / part-before-unit } { qualifier } { \token_to_str:N #1 }
418       }
419   }

```

Special (exceptional) items should always come before the relevant units.

```

420 \cs_new_protected:Npn \_siunitx_unit_parse_special:n #1
421   {
422     \_siunitx_unit_parse_add:nnnn { special }
423       { \int_eval:n { \l__siunitx_unit_position_int + 1 } }
424       {#1} {#1}
425   }

```

(End definition for `_siunitx_unit_parse_prefix:Nn` and others.)

`_siunitx_unit_parse_unit:Nn` Parsing units is slightly more involved than the other cases: this is the one place where the tracking value is incremented. If the switch `\l__siunitx_unit_per_bool` is set true then the current unit is also reciprocal: this can only happen if `\l__siunitx_unit_sticky_per_bool` is also true, so only one test is required.

```

426 \cs_new_protected:Npn \_siunitx_unit_parse_unit:Nn #1#2
427   {
428     \int_incr:N \l__siunitx_unit_position_int
429     \tl_if_eq:nnT {#1} { \gram }
430       {
431         \_siunitx_unit_parse_add:nnnn { command }
432           { \int_use:N \l__siunitx_unit_position_int }
433           {#1} {#1}
434       }
435     \_siunitx_unit_parse_add:nnnn { unit }
436       { \int_use:N \l__siunitx_unit_position_int }
437       {#1} {#2}
438     \bool_if:NT \l__siunitx_unit_per_bool
439       {
440         \_siunitx_unit_parse_add:nnnn { per }
441           { \int_use:N \l__siunitx_unit_position_int }
442           { \per } { true }
443       }
444   }

```

(End definition for `_siunitx_unit_parse_unit:Nn`.)

`_siunitx_unit_parse_per:` Storing the `\per` command requires adding a data item separate from the power which applies: this makes later formatting much more straight-forward. This data could in principle be combined with the `power`, but depending on the output format required that may make life more complex. Thus this information is stored separately for later

retrieval. If `\per` is set to be “sticky” then after parsing the first occurrence, any further uses are in error.

```

445 \cs_new_protected:Npn \_siunitx_unit_parse_per:
446   {
447     \bool_if:NTF \l_siunitx_unit_sticky_per_bool
448     {
449       \bool_set_true:N \l_siunitx_unit_per_bool
450       \cs_set_protected:Npn \per
451         { \msg_error:nn { siunitx } { unit / duplicate-sticky-per } }
452     }
453     {
454       \_siunitx_unit_parse_add:nnn
455         { per } { \int_eval:n { \l_siunitx_unit_position_int + 1 } }
456         { \per } { true }
457     }
458   }

```

(End definition for `_siunitx_unit_parse_per`.)

`_siunitx_unit_parse_finalise:`

If `\per` applies to the current unit, the power needs to be multiplied by -1 . That is done using an `fp` operation so that non-integer powers are supported. The flag for `\per` is also removed as this means we don’t have to check that the original power was positive. To be on the safe side, there is a check for a trivial power at this stage.

```

459 \cs_new_protected:Npn \_siunitx_unit_parse_finalise:n #1
460   {
461     \tl_set:Nx \l_siunitx_unit_tmp_tl { per- #1 }
462     \prop_if_in:NVT \l_siunitx_unit_parsed_prop \l_siunitx_unit_tmp_tl
463     {
464       \prop_remove:NV \l_siunitx_unit_parsed_prop
465         \l_siunitx_unit_tmp_tl
466       \tl_set:Nx \l_siunitx_unit_tmp_tl { power- #1 }
467       \prop_get:NVNTF
468         \l_siunitx_unit_parsed_prop
469         \l_siunitx_unit_tmp_tl
470         \l_siunitx_unit_part_tl
471       {
472         \tl_set:Nx \l_siunitx_unit_part_tl
473           { \fp_eval:n { \l_siunitx_unit_part_tl * -1 } }
474         \fp_compare:nNnTF \l_siunitx_unit_part_tl = 1
475           {
476             \prop_remove:NV \l_siunitx_unit_parsed_prop
477               \l_siunitx_unit_tmp_tl
478           }
479           {
480             \prop_put:NVV \l_siunitx_unit_parsed_prop
481               \l_siunitx_unit_tmp_tl \l_siunitx_unit_part_tl
482           }
483         }
484         {
485           \prop_put:NVn \l_siunitx_unit_parsed_prop
486             \l_siunitx_unit_tmp_tl { -1 }
487         }
488     }
489   }

```

(End definition for `_siunitx_unit_parse_finalise:n`.)

`_siunitx_unit_parse_finalise`: The final task is to check that there is not a “dangling” power or prefix: these are added to the “next” unit so are easy to test for.

```

490 \cs_new_protected:Npn \__siunitx_unit_parse_finalise:
491 {
492     \clist_map_inline:nn { per , power , prefix }
493     {
494         \tl_set:Nx \l__siunitx_unit_tmp_tl
495         { ##1 - \int_eval:n { \l__siunitx_unit_position_int + 1 } }
496         \prop_if_in:NVT \l__siunitx_unit_parsed_prop \l__siunitx_unit_tmp_tl
497         { \msg_error:nnn { siunitx } { unit / dangling-part } { ##1 } }
498     }
499 }

```

(End definition for __siunitx_unit_parse_finalise::)

6.9 Formatting parsed units

Set up the options which apply to formatting

```

\l_siunitx_unit_denominator_bracket_bool      500 \keys_define:nn { siunitx }
\l_siunitx_unit_forbid_literal_bool           501 {
\l_siunitx_unit_parse_bool                   502   bracket-unit-denominator .bool_set:N =
\l_siunitx_unit_per_symbol_tl                503     \l_siunitx_unit_denominator_bracket_bool ,
\l_siunitx_unit_qualifier_mode_tl            504   forbid-literal-units .bool_set:N =
\l_siunitx_unit_qualifier_phrase_tl          505     \l_siunitx_unit_forbid_literal_bool ,
\l_siunitx_unit_fraction_tl                  506   fraction-command .tl_set:N =
\l_siunitx_unit_parse_units                 507     \l_siunitx_unit_fraction_tl ,
\l_siunitx_unit_parse_bool                  508   parse-units .bool_set:N =
\l_siunitx_unit_per_mode_choice             509     \l_siunitx_unit_parse_bool ,
\l_siunitx_unit_per_mode_fraction           510   per-mode .choice: ,
\l_siunitx_unit_per_mode_code               511   per-mode / fraction .code:n =
\l_siunitx_unit_per_mode_code              512   {
\l_siunitx_unit_per_symbol_bool             513     \bool_set_false:N \l_siunitx_unit_autofrac_bool
\l_siunitx_unit_per_symbol_bool             514     \bool_set_false:N \l_siunitx_unit_per_symbol_bool
\l_siunitx_unit_powers_positive_bool       515     \bool_set_true:N \l_siunitx_unit_powers_positive_bool
\l_siunitx_unit_powers_positive_bool       516     \bool_set_true:N \l_siunitx_unit_two_part_bool
\l_siunitx_unit_per_symbol_bool             517   },
\l_siunitx_unit_per_mode_code              518   per-mode / power .code:n =
\l_siunitx_unit_per_mode_code              519   {
\l_siunitx_unit_per_symbol_bool             520     \bool_set_false:N \l_siunitx_unit_autofrac_bool
\l_siunitx_unit_per_symbol_bool             521     \bool_set_false:N \l_siunitx_unit_per_symbol_bool
\l_siunitx_unit_powers_positive_bool       522     \bool_set_false:N \l_siunitx_unit_powers_positive_bool
\l_siunitx_unit_powers_positive_bool       523     \bool_set_false:N \l_siunitx_unit_two_part_bool
\l_siunitx_unit_per_symbol_bool             524   },
\l_siunitx_unit_per_mode_code              525   per-mode / power-positive-first .code:n =
\l_siunitx_unit_per_mode_code              526   {
\l_siunitx_unit_per_symbol_bool             527     \bool_set_false:N \l_siunitx_unit_autofrac_bool
\l_siunitx_unit_per_symbol_bool             528     \bool_set_false:N \l_siunitx_unit_per_symbol_bool
\l_siunitx_unit_powers_positive_bool       529     \bool_set_false:N \l_siunitx_unit_powers_positive_bool
\l_siunitx_unit_powers_positive_bool       530     \bool_set_true:N \l_siunitx_unit_two_part_bool
\l_siunitx_unit_per_symbol_bool             531   },
\l_siunitx_unit_per_mode_code              532   per-mode / repeated-symbol .code:n =
\l_siunitx_unit_per_mode_code              533   {

```

```

534     \bool_set_false:N \l_siunitx_unit_autofrac_bool
535     \bool_set_true:N \l_siunitx_unit_per_symbol_bool
536     \bool_set_true:N \l_siunitx_unit_powers_positive_bool
537     \bool_set_false:N \l_siunitx_unit_two_part_bool
538   } ,
539   per-mode / symbol .code:n =
540   {
541     \bool_set_false:N \l_siunitx_unit_autofrac_bool
542     \bool_set_true:N \l_siunitx_unit_per_symbol_bool
543     \bool_set_true:N \l_siunitx_unit_powers_positive_bool
544     \bool_set_true:N \l_siunitx_unit_two_part_bool
545   } ,
546   per-mode / symbol-or-fraction .code:n =
547   {
548     \bool_set_true:N \l_siunitx_unit_autofrac_bool
549     \bool_set_true:N \l_siunitx_unit_per_symbol_bool
550     \bool_set_true:N \l_siunitx_unit_powers_positive_bool
551     \bool_set_true:N \l_siunitx_unit_two_part_bool
552   } ,
553   per-symbol .tl_set:N =
554   \l_siunitx_unit_per_symbol_tl ,
555   qualifier-mode .choices:nn =
556   { bracket , combine , phrase , subscript }
557   { \tl_set_eq:NN \l_siunitx_unit_qualifier_mode_tl \l_keys_choice_tl } ,
558   qualifier-phrase .tl_set:N =
559   \l_siunitx_unit_qualifier_phrase_tl
560 }

```

(End definition for `\l_siunitx_unit_fraction_tl` and others. This variable is documented on page [140](#).)

`\l_siunitx_unit_bracket_bool`

A flag to indicate that the unit currently under construction will require brackets if a power is added.

```
561 \bool_new:N \l_siunitx_unit_bracket_bool
```

(End definition for `\l_siunitx_unit_bracket_bool`.)

Abstracted out but currently purely internal.

```

562 \tl_new:N \l_siunitx_unit_bracket_open_tl
563 \tl_new:N \l_siunitx_unit_bracket_close_tl
564 \tl_set:Nn \l_siunitx_unit_bracket_open_tl { ( }
565 \tl_set:Nn \l_siunitx_unit_bracket_close_tl { ) }
```

(End definition for `\l_siunitx_unit_bracket_open_tl` and `\l_siunitx_unit_bracket_close_tl`.)

`\l_siunitx_unit_font_bool`

A flag to control when font wrapping is applied to the output.

```
566 \bool_new:N \l_siunitx_unit_font_bool
```

(End definition for `\l_siunitx_unit_font_bool`.)

Dealing with the various ways that reciprocal (`\per`) can be handled requires a few different switches.

```

567 \bool_new:N \l_siunitx_unit_autofrac_bool
568 \bool_new:N \l_siunitx_unit_per_symbol_bool
569 \bool_new:N \l_siunitx_unit_powers_positive_bool
570 \bool_new:N \l_siunitx_unit_two_part_bool
```

(End definition for `\l_siunitx_unit_autofrac_bool` and others.)

`\l_siunitx_unit_numerator_bool` Indicates that the current unit should go into the numerator when splitting into two parts (fractions or other “sorted” styles).

⁵⁷¹ `\bool_new:N \l_siunitx_unit_numerator_bool`

(End definition for `\l_siunitx_unit_numerator_bool`.)

`\l_siunitx_unit_qualifier_mode_tl` For storing the text of options which are best handled by picking function names.

⁵⁷² `\tl_new:N \l_siunitx_unit_qualifier_mode_tl`

(End definition for `\l_siunitx_unit_qualifier_mode_tl`.)

`\l_siunitx_unit_combine_exp_fp` For combining an exponent with the first unit.

⁵⁷³ `\fp_new:N \l_siunitx_unit_combine_exp_fp`

(End definition for `\l_siunitx_unit_combine_exp_fp`.)

`\l_siunitx_unit_prefix_exp_bool` Used to determine if prefixes are converted into powers. Note that while this may be set as an option “higher up”, at this point it is handled as an internal switch (see the two formatting interfaces for reasons).

⁵⁷⁴ `\bool_new:N \l_siunitx_unit_prefix_exp_bool`

(End definition for `\l_siunitx_unit_prefix_exp_bool`.)

`\l_siunitx_unit_prefix_fp` When converting prefixes to powers, the calculations are done as an fp.

⁵⁷⁵ `\fp_new:N \l_siunitx_unit_prefix_fp`

(End definition for `\l_siunitx_unit_prefix_fp`.)

`\l_siunitx_unit_multiple_fp` For multiplying units.

⁵⁷⁶ `\fp_new:N \l_siunitx_unit_multiple_fp`

(End definition for `\l_siunitx_unit_multiple_fp`.)

`\l_siunitx_unit_current_tl`
`\l_siunitx_unit_part_tl` Building up the (partial) formatted unit requires some token list storage. Each part of the unit combination that is recovered also has to be placed in a token list: this is a dedicated one to leave the scratch variables available.

⁵⁷⁷ `\tl_new:N \l_siunitx_unit_current_tl`

⁵⁷⁸ `\tl_new:N \l_siunitx_unit_part_tl`

(End definition for `\l_siunitx_unit_current_tl` and `\l_siunitx_unit_part_tl`.)

`\l_siunitx_unit_denominator_tl` For fraction-like units, space is needed for the denominator as well as the numerator (which is handled using `\l_siunitx_unit_formatted_tl`).

⁵⁷⁹ `\tl_new:N \l_siunitx_unit_denominator_tl`

(End definition for `\l_siunitx_unit_denominator_tl`.)

`\l_siunitx_unit_total_int` The formatting routine needs to know both the total number of units and the current unit. Thus an `int` is required in addition to `\l_siunitx_unit_position_int`.

⁵⁸⁰ `\int_new:N \l_siunitx_unit_total_int`

(End definition for `\l_siunitx_unit_total_int`.)

```
\_\_siunitx\_unit\_format\_parsed:  
\_\_siunitx\_unit\_format\_parsed\_aux:n
```

The main formatting routine is essentially a loop over each position, reading the various parts of the unit to build up complete unit combination.

```
581 \cs_new_protected:Npn \_\_siunitx\_unit\_format\_parsed:  
582 {  
583     \int_set_eq:NN \l_\_siunitx\_unit\_total_int \l_\_siunitx\_unit\_position_int  
584     \tl_clear:N \l_\_siunitx\_unit\_denominator_tl  
585     \tl_clear:N \l_\_siunitx\_unit\_formatted_tl  
586     \fp_zero:N \l_\_siunitx\_unit\_prefix_fp  
587     \int_zero:N \l_\_siunitx\_unit\_position_int  
588     \fp_compare:nNnf \l_\_siunitx\_unit\_combine_exp_fp = \c_zero_fp  
589     { \_\_siunitx\_unit\_format\_combine\_exp: }  
590     \fp_compare:nNnf \l_\_siunitx\_unit\_multiple_fp = \c_one_fp  
591     { \_\_siunitx\_unit\_format\_multiply: }  
592     \bool_lazy_and:nnT  
593     { \l_\_siunitx\_unit\_prefix\_exp\_bool }  
594     { \l_\_siunitx\_unit\_mass\_kilogram\_bool }  
595     { \_\_siunitx\_unit\_format\_mass\_to\_kilogram: }  
596     \int_do_while:nNn  
597     \l_\_siunitx\_unit\_position_int < \l_\_siunitx\_unit\_total_int  
598     {  
599         \bool_set_false:N \l_\_siunitx\_unit\_bracket_bool  
600         \tl_clear:N \l_\_siunitx\_unit\_current_tl  
601         \bool_set_false:N \l_\_siunitx\_unit\_font_bool  
602         \bool_set_true:N \l_\_siunitx\_unit\_numerator_bool  
603         \int_incr:N \l_\_siunitx\_unit\_position_int  
604         \clist_map_inline:nn { prefix , unit , qualifier , power , special }  
605         { \_\_siunitx\_unit\_format\_parsed\_aux:n {##1} }  
606         \_\_siunitx\_unit\_format\_output:  
607     }  
608     \_\_siunitx\_unit\_format\_finalise:  
609 }  
610 \cs_new_protected:Npn \_\_siunitx\_unit\_format\_parsed\_aux:n #1  
611 {  
612     \tl_set:Nx \l_\_siunitx\_unit\_tmp_tl  
613     { #1 - \int_use:N \l_\_siunitx\_unit\_position_int }  
614     \prop_get:NVNT \l_\_siunitx\_unit\_parsed\_prop  
615     \l_\_siunitx\_unit\_tmp_tl \l_\_siunitx\_unit\_part_tl  
616     { \use:c { \_\_siunitx\_unit\_format\_ #1 : } }  
617 }
```

(End definition for `__siunitx_unit_format_parsed:` and `__siunitx_unit_format_parsed_aux:n`.)

```
\_\_siunitx\_unit\_format\_combine\_exp:
```

To combine an exponent into the first prefix, we first adjust for any power, then deal with any existing prefix, before looking up the final result.

```
618 \cs_new_protected:Npn \_\_siunitx\_unit\_format\_combine\_exp:  
619 {  
620     \prop_get:NnNF \l_\_siunitx\_unit\_parsed\_prop { power-1 } \l_\_siunitx\_unit\_tmp\_tl  
621     { \tl_set:Nn \l_\_siunitx\_unit\_tmp\_tl { 1 } }  
622     \fp_set:Nn \l_\_siunitx\_unit\_tmp\_fp  
623     { \l_\_siunitx\_unit\_combine\_exp_fp / \l_\_siunitx\_unit\_tmp\_tl }  
624     \prop_get:NnNTF \l_\_siunitx\_unit\_parsed\_prop { prefix-1 } \l_\_siunitx\_unit\_tmp\_tl  
625     {  
626         \prop_get:NVNF \l_\_siunitx\_unit\_prefixes\_forward\_prop  
627         \l_\_siunitx\_unit\_tmp\_tl \l_\_siunitx\_unit\_tmp\_tl
```

```

628   {
629     \prop_get:NnN \l_siunitx_unit_parsed_prop { prefix-1 } \l_siunitx_unit_tmp_tl
630     \msg_error:n { siunitx } { unit / non-numeric-exponent }
631     { \l_siunitx_unit_tmp_tl }
632     \tl_set:Nn \l_siunitx_unit_tmp_tl { 0 }
633   }
634 }
635 { \tl_set:Nn \l_siunitx_unit_tmp_tl { 0 } }
636 \tl_set:Nx \l_siunitx_unit_tmp_tl
637 { \fp_eval:n { \l_siunitx_unit_tmp_fp + \l_siunitx_unit_tmp_tl } }
638 \fp_compare:nNnTF \l_siunitx_unit_tmp_tl = \c_zero_fp
639 { \prop_remove:Nn \l_siunitx_unit_parsed_prop { prefix-1 } }
640 {
641   \prop_get:NVNTF \l_siunitx_unit_prefixes_reverse_prop
642   \l_siunitx_unit_tmp_tl \l_siunitx_unit_tmp_tl
643   { \prop_put:NnV \l_siunitx_unit_parsed_prop { prefix-1 } \l_siunitx_unit_tmp_tl }
644   {
645     \msg_error:n { siunitx } { unit / non-convertible-exponent }
646     { \l_siunitx_unit_tmp_tl }
647   }
648 }
649 }

```

(End definition for `_siunitx_unit_format_combine_exp::`)

`_siunitx_unit_format_multiply:` A simple mapping.

```

650 \cs_new_protected:Npn \_siunitx_unit_format_multiply:
651 {
652   \int_step_inline:nn { \prop_count:N \l_siunitx_unit_parsed_prop }
653   {
654     \prop_get:NnNF \l_siunitx_unit_parsed_prop { power- ##1 } \l_siunitx_unit_tmp_tl
655     { \tl_set:Nn \l_siunitx_unit_tmp_tl { 1 } }
656     \fp_set:Nn \l_siunitx_unit_tmp_fp
657     { \l_siunitx_unit_tmp_tl * \l_siunitx_unit_multiple_fp }
658     \fp_compare:nNnTF \l_siunitx_unit_tmp_fp = \c_one_fp
659     { \prop_remove:N \l_siunitx_unit_parsed_prop { power- ##1 } }
660     {
661       \prop_put:Nnx \l_siunitx_unit_parsed_prop { power- ##1 }
662       { \fp_use:N \l_siunitx_unit_tmp_fp }
663     }
664   }
665 }

```

(End definition for `_siunitx_unit_format_multiply::`)

`_siunitx_unit_format_mass_to_kilogram:`

To deal correctly with prefix extraction in combination with kilograms, we need to coerce the prefix for grams. Currently, only this one special case is recorded in the property list, so we do not actually need to check the value. If there is then no prefix we do a bit of gymnastics to create one and then shift the starting point for the prefix extraction.

```

666 \cs_new_protected:Npn \_siunitx_unit_format_mass_to_kilogram:
667 {
668   \int_step_inline:nn \l_siunitx_unit_total_int
669   {
670     \prop_if_in:NnT \l_siunitx_unit_parsed_prop { command- ##1 }

```

```

671   {
672     \prop_if_in:NnF \l_siunitx_unit_parsed_prop { prefix- ##1 }
673   {
674     \group_begin:
675       \bool_set_false:N \l_siunitx_unit_parsing_bool
676       \tl_set:Nx \l_siunitx_unit_tmp_t1 { \kilo }
677     \exp_args:NNNV \group_end:
678     \tl_set:Nn \l_siunitx_unit_tmp_t1 \l_siunitx_unit_tmp_t1
679     \prop_put:NnV \l_siunitx_unit_parsed_prop { prefix- ##1 }
680       \l_siunitx_unit_tmp_t1
681     \prop_get:NnnF \l_siunitx_unit_parsed_prop { power- ##1 }
682       \l_siunitx_unit_tmp_t1
683       { \tl_set:Nn \l_siunitx_unit_tmp_t1 { 1 } }
684     \fp_set:Nn \l_siunitx_unit_prefix_fp
685       { \l_siunitx_unit_prefix_fp - 3 * \l_siunitx_unit_tmp_t1 }
686   }
687 }
688 }
689 }
```

(End definition for `_siunitx_unit_format_mass_to_kilogram:..`)

`_siunitx_unit_format_bracket:N` A quick utility function which wraps up a token list variable in brackets if they are required.

```

690 \cs_new:Npn \_siunitx_unit_format_bracket:N #1
691   {
692     \bool_if:NTF \l_siunitx_unit_bracket_bool
693     {
694       \exp_not:V \l_siunitx_unit_bracket_open_t1
695       \exp_not:V #1
696       \exp_not:V \l_siunitx_unit_bracket_close_t1
697     }
698     { \exp_not:V #1 }
699   }
```

(End definition for `_siunitx_unit_format_bracket:N`.)

`_siunitx_unit_format_power:` `_siunitx_unit_format_power_aux:wTF` `_siunitx_unit_format_power_positive:` `_siunitx_unit_format_power_negative:` `_siunitx_unit_format_power_negative_aux:wTF` `_siunitx_unit_format_power_superscript:` Formatting powers requires a test for negative numbers and depending on output format requests some adjustment to the stored value. This could be done using an `fp` function, but that would be slow compared to a dedicated if lower-level approach based on delimited arguments.

```

700 \cs_new_protected:Npn \_siunitx_unit_format_power:
701   {
702     \_siunitx_unit_format_font:
703     \exp_after:wN \_siunitx_unit_format_power_aux:wTF
704       \l_siunitx_unit_part_t1 - \q_stop
705       { \_siunitx_unit_format_power_negative: }
706       { \_siunitx_unit_format_power_positive: }
707   }
708 \cs_new:Npn \_siunitx_unit_format_power_aux:wTF #1 - #2 \q_stop
709   { \tl_if_empty:nTF {#1} }
```

In the case of positive powers, there is little to do: add the power as a subscript (must be required as the parser ensures it's $\neq 1$).

```

710 \cs_new_protected:Npn \__siunitx_unit_format_power_positive:
711   { \__siunitx_unit_format_power_superscript: }

```

Dealing with negative powers starts by flipping the switch used to track where in the final output the current part should get added to. For the case where the output is fraction-like, strip off the \sim then ensure that the result is not the trivial power 1. Assuming all is well, addition to the current unit combination goes ahead.

```

712 \cs_new_protected:Npn \__siunitx_unit_format_power_negative:
713   {
714     \bool_set_false:N \l__siunitx_unit_numerator_bool
715     \bool_if:NTF \l__siunitx_unit_powers_positive_bool
716     {
717       \tl_set:Nx \l__siunitx_unit_part_tl
718       {
719         \exp_after:wN \__siunitx_unit_format_power_negative_aux:w
720         \l__siunitx_unit_part_tl \q_stop
721       }
722       \str_if_eq:VnF \l__siunitx_unit_part_tl { 1 }
723       { \__siunitx_unit_format_power_superscript: }
724     }
725     { \__siunitx_unit_format_power_superscript: }
726   }
727 \cs_new:Npn \__siunitx_unit_format_power_negative_aux:w - #1 \q_stop
728   { \exp_not:n {#1} }

```

Adding the power as a superscript has the slight complication that there is the possibility of needing some brackets. The superscript itself uses `\sp` as that avoids any category code issues and also allows redirection at a higher level more readily.

```

729 \cs_new_protected:Npn \__siunitx_unit_format_power_superscript:
730   {
731     \exp_after:wN \__siunitx_unit_format_power_superscript:w
732     \l__siunitx_unit_part_tl . . \q_stop
733   }
734 \cs_new_protected:Npn \__siunitx_unit_format_power_superscript:w #1 . #2 . #3 \q_stop
735   {
736     \tl_if_blank:nTF {#2}
737     {
738       \tl_set:Nx \l__siunitx_unit_current_tl
739       {
740         \__siunitx_unit_format_bracket:N \l__siunitx_unit_current_tl
741         ^ { \exp_not:n {#1} }
742       }
743     }
744     {
745       \tl_set:Nx \l__siunitx_unit_tmp_tl
746       {
747         { }
748         \tl_if_head_eq_charcode:nNTF {#1} -
749         { { - } { \exp_not:o { \use_none:n #1 } } }
750         { { } { \exp_not:n {#1} } }
751       {#2}
752       { }
753       { }
754       { 0 }

```

```

755     }
756     \tl_set:Nx \l_siunitx_unit_current_tl
757     {
758         \_siunitx_unit_format_bracket:N \l_siunitx_unit_current_tl
759         ~ { \siunitx_number_output:N \l_siunitx_unit_tmp_tl }
760     }
761 }
762 \bool_set_false:N \l_siunitx_unit_bracket_bool
763 }
```

(End definition for `_siunitx_unit_format_power:` and others.)

Formatting for prefixes depends on whether they are to be expressed as symbols or collected up to be returned as a power of 10. The latter case requires a bit of processing, which includes checking that the conversion is possible and allowing for any power that applies to the current unit.

```

764 \cs_new_protected:Npn \_siunitx_unit_format_prefix:
765 {
766     \bool_if:NTF \l_siunitx_unit_prefix_exp_bool
767     { \_siunitx_unit_format_prefix_exp: }
768     { \_siunitx_unit_format_prefix_symbol: }
769 }
770 \cs_new_protected:Npn \_siunitx_unit_format_prefix_exp:
771 {
772     \prop_get:NVNTF \l_siunitx_unit_prefixes_forward_prop
773     \l_siunitx_unit_part_tl \l_siunitx_unit_part_tl
774     {
775         \bool_if:NT \l_siunitx_unit_mass_kilogram_bool
776         {
777             \tl_set:Nx \l_siunitx_unit_tmp_tl
778             { command- \int_use:N \l_siunitx_unit_position_int }
779             \prop_if_in:NVT \l_siunitx_unit_parsed_prop \l_siunitx_unit_tmp_tl
780             { \_siunitx_unit_format_prefix_gram: }
781         }
782         \tl_set:Nx \l_siunitx_unit_tmp_tl
783             { power- \int_use:N \l_siunitx_unit_position_int }
784         \prop_get:NVNF \l_siunitx_unit_parsed_prop
785             \l_siunitx_unit_tmp_tl \l_siunitx_unit_tmp_tl
786             { \tl_set:Nn \l_siunitx_unit_tmp_tl { 1 } }
787         \fp_add:Nn \l_siunitx_unit_prefix_fp
788             { \l_siunitx_unit_tmp_tl * \l_siunitx_unit_part_tl }
789     }
790     { \_siunitx_unit_format_prefix_symbol: }
791 }
```

When the units in use are grams, we may need to deal with conversion to kilograms.

```

792 \cs_new_protected:Npn \_siunitx_unit_format_prefix_gram:
793 {
794     \tl_set:Nx \l_siunitx_unit_part_tl
795     { \int_eval:n { \l_siunitx_unit_part_tl - 3 } }
796     \group_begin:
797         \bool_set_false:N \l_siunitx_unit_parsing_bool
798         \tl_set:Nx \l_siunitx_unit_current_tl { \kilo }
799     \exp_args:NNNV \group_end:
```

```

800     \tl_set:Nn \l__siunitx_unit_current_tl \l__siunitx_unit_current_tl
801   }
802 \cs_new_protected:Npn \__siunitx_unit_format_prefix_symbol:
803   { \tl_set_eq:NN \l__siunitx_unit_current_tl \l__siunitx_unit_part_tl }

(End definition for \__siunitx_unit_format_prefix: and others.)

```

There are various ways that a qualifier can be added to the output. The idea here is to modify the “base” text appropriately and then add to the current unit. Notice that when the qualifier is just treated as “text”, the auxiliary is actually a no-op.

```

804 \cs_new_protected:Npn \__siunitx_unit_format_qualifier:
805   {
806     \use:c
807     {
808       __siunitx_unit_format_qualifier_
809       \l__siunitx_unit_qualifier_mode_tl :
810     }
811     \tl_put_right:NV \l__siunitx_unit_current_tl \l__siunitx_unit_part_tl
812   }
813 \cs_new_protected:Npn \__siunitx_unit_format_qualifier_bracket:
814   {
815     __siunitx_unit_format_font:
816     \tl_set:Nx \l__siunitx_unit_part_tl
817     {
818       \exp_not:V \l__siunitx_unit_bracket_open_tl
819       \exp_not:V \l__siunitx_unit_font_tl
820       { \exp_not:V \l__siunitx_unit_part_tl }
821       \exp_not:V \l__siunitx_unit_bracket_close_tl
822     }
823   }
824 \cs_new_protected:Npn \__siunitx_unit_format_qualifier_combine: { }
825 \cs_new_protected:Npn \__siunitx_unit_format_qualifier_phrase:
826   {
827     __siunitx_unit_format_font:
828     \tl_set:Nx \l__siunitx_unit_part_tl
829     {
830       \exp_not:V \l__siunitx_unit_qualifier_phrase_tl
831       \exp_not:V \l__siunitx_unit_font_tl
832       { \exp_not:V \l__siunitx_unit_part_tl }
833     }
834   }
835 \cs_new_protected:Npn \__siunitx_unit_format_qualifier_subscript:
836   {
837     __siunitx_unit_format_font:
838     \tl_set:Nx \l__siunitx_unit_part_tl
839     {
840       \c__siunitx_unit_math_subscript_tl
841       {
842         \exp_not:V \l__siunitx_unit_font_tl
843         { \exp_not:V \l__siunitx_unit_part_tl }
844       }
845     }
846   }

(End definition for \__siunitx_unit_format_qualifier: and others.)

```

_siunitx_unit_format_special: Any special odds and ends are handled by simply making the current combination into an argument for the recovered code. Font control needs to be *inside* the special formatting here.

```

847 \cs_new_protected:Npn \_siunitx_unit_format_special:
848   {
849     \tl_set:Nx \l_siunitx_unit_current_tl
850     {
851       \exp_not:V \l_siunitx_unit_part_tl
852       {
853         \bool_if:NTF \l_siunitx_unit_font_bool
854           { \use:n }
855           { \exp_not:V \l_siunitx_unit_font_tl }
856           { \exp_not:V \l_siunitx_unit_current_tl }
857       }
858     }
859     \bool_set_true:N \l_siunitx_unit_font_bool
860   }

```

(End definition for _siunitx_unit_format_special:.)

_siunitx_unit_format_unit: A very simple task: add the unit to the output currently being constructed.

```

861 \cs_new_protected:Npn \_siunitx_unit_format_unit:
862   {
863     \tl_put_right:NV
864       \l_siunitx_unit_current_tl \l_siunitx_unit_part_tl
865   }

```

(End definition for _siunitx_unit_format_unit:.)

The first step here is to make a choice based on whether the current part should be stored as part of the numerator or denominator of a fraction. In all cases, if the switch \l_siunitx_unit_numerator_bool is true then life is simple: add the current part to the numerator with a standard separator

```

866 \cs_new_protected:Npn \_siunitx_unit_format_output:
867   {
868     \_siunitx_unit_format_font:
869     \bool_set_false:N \l_siunitx_unit_bracket_bool
870     \use:c
871     {
872       \_siunitx_unit_format_output_
873       \bool_if:NTF \l_siunitx_unit_numerator_bool
874         { aux: }
875         { denominator: }
876     }
877   }
878 \cs_new_protected:Npn \_siunitx_unit_format_output_aux:
879   {
880     \_siunitx_unit_format_output_aux:nV { formatted }
881       \l_siunitx_unit_product_tl
882   }

```

There are a few things to worry about at this stage if the current part is in the denominator. Powers have already been dealt with and some formatting outcomes only need a branch at the final point of building the entire unit. That means that there are three

possible outcomes here: if collecting two separate parts, add to the denominator with a product separator, or if only building one token list there may be a need to use a symbol separator. When the `repeated-symbol` option is in use there may be a need to add a leading 1 to the output in the case where the first unit is in the denominator: that can be picked up by looking for empty output in combination with the flag for using a symbol in the output but not a two-part strategy.

```

883 \cs_new_protected:Npn \_siunitx_unit_format_output_denominator:
884 {
885     \bool_if:NTF \l_siunitx_unit_two_part_bool
886     {
887         \bool_lazy_and:nnT
888         { \l_siunitx_unit_denominator_bracket_bool }
889         { ! \tl_if_empty_p:N \l_siunitx_unit_denominator_tl }
890         { \bool_set_true:N \l_siunitx_unit_bracket_bool }
891         \_siunitx_unit_format_output_aux:nV { denominator }
892         \l_siunitx_unit_product_tl
893     }
894     {
895         \bool_lazy_and:nnT
896         { \l_siunitx_unit_per_symbol_bool }
897         { \tl_if_empty_p:N \l_siunitx_unit_formatted_tl }
898         { \tl_set:Nn \l_siunitx_unit_formatted_tl { 1 } }
899         \_siunitx_unit_format_output_aux:nv { formatted }
900         {
901             \l_siunitx_unit_
902             \bool_if:NTF \l_siunitx_unit_per_symbol_bool
903                 { per_symbol }
904                 { product }
905             _tl
906         }
907     }
908 }
909 \cs_new_protected:Npn \_siunitx_unit_format_output_aux:nn #1#2
910 {
911     \tl_set:cx { \l_siunitx_unit_ #1 _tl }
912     {
913         \exp_not:v { \l_siunitx_unit_ #1 _tl }
914         \tl_if_empty:cF { \l_siunitx_unit_ #1 _tl }
915         { \exp_not:n {#2} }
916         \exp_not:V \l_siunitx_unit_current_tl
917     }
918 }
919 \cs_generate_variant:Nn \_siunitx_unit_format_output_aux:nn { nV , nv }
```

(End definition for `_siunitx_unit_format_output:` and others.)

`_siunitx_unit_format_font:` A short auxiliary which checks if the font has been applied to the main part of the output: if not, add it and set the flag.

```

920 \cs_new_protected:Npn \_siunitx_unit_format_font:
921 {
922     \bool_if:NF \l_siunitx_unit_font_bool
923     {
924         \tl_set:Nx \l_siunitx_unit_current_tl
925         {
```

```

926         \exp_not:V \l_siunitx_unit_font_tl
927         { \exp_not:V \l_siunitx_unit_current_tl }
928     }
929     \bool_set_true:N \l_siunitx_unit_font_bool
930 }
931

```

(End definition for `_siunitx_unit_format_font`.)

Finalising the unit format is really about picking up the cases involving fractions: these require assembly of the parts with the need to add additional material in some cases

```

932 \cs_new_protected:Npn \_siunitx_unit_format_finalise:
933 {
934     \tl_if_empty:NTF \l_siunitx_unit_denominator_tl
935     {
936         \bool_if:NTF \l_siunitx_unit_powers_positive_bool
937         { \_siunitx_unit_format_finalise_fractional: }
938         { \_siunitx_unit_format_finalise_power: }
939     }
940 }

```

For fraction-like output, there are three possible choices and two actual styles. In all cases, if the numerator is empty then it is set here to 1. To deal with the “auto-format” case, the two styles (fraction and symbol) are handled in auxiliaries: this allows both to be used at the same time! Beyond that, the key here is to use a single `\tl_set:Nx` to keep down the number of assignments.

```

941 \cs_new_protected:Npn \_siunitx_unit_format_finalise_fractional:
942 {
943     \tl_if_empty:NT \l_siunitx_unit_formatted_tl
944     { \tl_set:Nn \l_siunitx_unit_formatted_tl { 1 } }
945     \bool_if:NTF \l_siunitx_unit_autofrac_bool
946     { \_siunitx_unit_format_finalise_autofrac: }
947     {
948         \bool_if:NTF \l_siunitx_unit_per_symbol_bool
949         { \_siunitx_unit_format_finalise_symbol: }
950         { \_siunitx_unit_format_finalise_fraction: }
951     }
952 }

```

For the “auto-selected” fraction method, the two other auxiliary functions are used to do both forms of formatting. So that everything required is available, this needs one group so that the second auxiliary receives the correct input. After that it is just a case of applying `\mathchoice` to the formatted output.

```

953 \cs_new_protected:Npn \_siunitx_unit_format_finalise_autofrac:
954 {
955     \group_begin:
956     \_siunitx_unit_format_finalise_fraction:
957     \exp_args:NNNV \group_end:
958     \tl_set:Nn \l_siunitx_unit_tmp_tl \l_siunitx_unit_formatted_tl
959     \_siunitx_unit_format_finalise_symbol:
960     \tl_set:Nx \l_siunitx_unit_formatted_tl
961     {
962         \mathchoice
963         { \exp_not:V \l_siunitx_unit_tmp_tl }

```

```

964     { \exp_not:V \l_siunitx_unit_formatted_tl }
965     { \exp_not:V \l_siunitx_unit_formatted_tl }
966     { \exp_not:V \l_siunitx_unit_formatted_tl }
967   }
968 }
```

When using a fraction function the two parts are now assembled.

```

969 \cs_new_protected:Npn \_siunitx_unit_format_finalise_fraction:
970   {
971     \tl_set:Nx \l_siunitx_unit_formatted_tl
972     {
973       \exp_not:V \l_siunitx_unit_fraction_tl
974       { \exp_not:V \l_siunitx_unit_formatted_tl }
975       { \exp_not:V \l_siunitx_unit_denominator_tl }
976     }
977   }
978 \cs_new_protected:Npn \_siunitx_unit_format_finalise_symbol:
979   {
980     \tl_set:Nx \l_siunitx_unit_formatted_tl
981     {
982       \exp_not:V \l_siunitx_unit_formatted_tl
983       \exp_not:V \l_siunitx_unit_per_symbol_tl
984       \_siunitx_unit_format_bracket:N \l_siunitx_unit_denominator_tl
985     }
986   }
```

In the case of sorted powers, there is a test to make sure there was at least one positive power, and if so a simple join of the two parts with the appropriate product.

```

987 \cs_new_protected:Npn \_siunitx_unit_format_finalise_power:
988   {
989     \tl_if_empty:NTF \l_siunitx_unit_formatted_tl
990     {
991       \tl_set_eq:NN
992         \l_siunitx_unit_formatted_tl
993         \l_siunitx_unit_denominator_tl
994     }
995   {
996     \tl_set:Nx \l_siunitx_unit_formatted_tl
997     {
998       \exp_not:V \l_siunitx_unit_formatted_tl
999       \exp_not:V \l_siunitx_unit_product_tl
1000      \exp_not:V \l_siunitx_unit_denominator_tl
1001    }
1002  }
1003 }
```

(End definition for `_siunitx_unit_format_finalise:` and others.)

6.10 Non-Latin character support

A small amount of code to make it convenient to include non-Latin characters in units without having to directly include them in the sources directly.

```

1004 \bool_lazy_or:nnTF
1005   { \sys_if_engine_luatex_p: }
1006   { \sys_if_engine_xetex_p: }
```

```

1007  {
1008    \cs_new:Npn \__siunitx_unit_non_latin:n #1
1009      { \char_generate:nn {#1} { \char_value_catcode:n {#1} } }
1010  }
1011  {
1012    \cs_new:Npn \__siunitx_unit_non_latin:n #1
1013      {
1014        \exp_last_unbraced:Nf \__siunitx_unit_non_latin:nnnn
1015          { \char_to_utfviii_bytes:n {#1} }
1016      }
1017    \cs_new:Npn \__siunitx_unit_non_latin:nnnn #1#2#3#4
1018      {
1019        \exp_after:wN \exp_after:wN \exp_after:wN
1020          \exp_not:N \char_generate:nn {#1} { 13 }
1021        \exp_after:wN \exp_after:wN \exp_after:wN
1022          \exp_not:N \char_generate:nn {#2} { 13 }
1023      }
1024  }

```

(End definition for `__siunitx_unit_non_latin:n` and `__siunitx_unit_non_latin:nnnn`.)

6.11 Pre-defined unit components

Quite a number of units can be predefined: while this is a code-level module, there is little point having a unit parser which does not start off able to parse any units!

\kilogram The basic SI units: technically the correct spelling is `\metre` but US users tend to use `\meter`.

\metre `\siunitx_declare_unit:Nn \kilogram { \kilo \gram }`

\meter `\siunitx_declare_unit:Nn \metre { m }`

\kelvin `\siunitx_declare_unit:Nn \meter { \metre }`

\candela `\siunitx_declare_unit:Nn \mole { mol }`

\second `\siunitx_declare_unit:Nn \second { s }`

\ampere `\siunitx_declare_unit:Nn \ampere { A }`

\kelvin `\siunitx_declare_unit:Nn \kelvin { K }`

\candela `\siunitx_declare_unit:Nn \candela { cd }`

(End definition for `\kilogram` and others. These functions are documented on page 141.)

\gram The gram is an odd unit as it is needed for the base unit kilogram.

`\siunitx_declare_unit:Nn \gram { g }`

(End definition for `\gram`. This function is documented on page 141.)

\yocto The various SI multiple prefixes are defined here: first the small ones.

\zepto `\siunitx_declare_prefix:Nnn \yocto { -24 } { y }`

\atto `\siunitx_declare_prefix:Nnn \zepto { -21 } { z }`

\femto `\siunitx_declare_prefix:Nnn \atto { -18 } { a }`

\pico `\siunitx_declare_prefix:Nnn \femto { -15 } { f }`

\nano `\siunitx_declare_prefix:Nnn \pico { -12 } { p }`

\micro `\siunitx_declare_prefix:Nnn \nano { -9 } { n }`

\milli `\siunitx_declare_prefix:Nnx \micro { -6 } { __siunitx_unit_non_latin:n { "03BC" } }`

\centi `\siunitx_declare_prefix:Nnn \milli { -3 } { m }`

\deci `\siunitx_declare_prefix:Nnn \centi { -2 } { c }`

\yocto `\siunitx_declare_prefix:Nnn \deci { -1 } { d }`

(End definition for `\yocto` and others. These functions are documented on page 141.)

```
\deca Now the large ones.  
\deka 1044 \siunitx_declare_prefix:Nnn \deca { 1 } { da }  
\hecto 1045 \siunitx_declare_prefix:Nnn \deka { 1 } { da }  
\kilo 1046 \siunitx_declare_prefix:Nnn \hecto { 2 } { h }  
\mega 1047 \siunitx_declare_prefix:Nnn \kilo { 3 } { k }  
\giga 1048 \siunitx_declare_prefix:Nnn \mega { 6 } { M }  
\tera 1049 \siunitx_declare_prefix:Nnn \giga { 9 } { G }  
\peta 1050 \siunitx_declare_prefix:Nnn \tera { 12 } { T }  
\exa 1051 \siunitx_declare_prefix:Nnn \peta { 15 } { P }  
\zetta 1052 \siunitx_declare_prefix:Nnn \exa { 18 } { E }  
\yotta 1053 \siunitx_declare_prefix:Nnn \zetta { 21 } { Z }  
1054 \siunitx_declare_prefix:Nnn \yotta { 24 } { Y }
```

(End definition for `\deca` and others. These functions are documented on page 141.)

`\becquerel` Named derived units: first half of alphabet.

```
\degreeCelsius 1055 \siunitx_declare_unit:Nn \becquerel { Bq }  
\coulomb 1056 \siunitx_declare_unit:Nx \degreeCelsius { \_siunitx_unit_non_latin:n { "00B0 } C }  
\farad 1057 \siunitx_declare_unit:Nn \coulomb { C }  
\gray 1058 \siunitx_declare_unit:Nn \farad { F }  
\hertz 1059 \siunitx_declare_unit:Nn \gray { Gy }  
\henry 1060 \siunitx_declare_unit:Nn \hertz { Hz }  
\joule 1061 \siunitx_declare_unit:Nn \henry { H }  
\katal 1062 \siunitx_declare_unit:Nn \joule { J }  
\lumen 1063 \siunitx_declare_unit:Nn \katal { kat }  
\lux 1064 \siunitx_declare_unit:Nn \lumen { lm }  
1065 \siunitx_declare_unit:Nn \lux { lx }
```

(End definition for `\becquerel` and others. These functions are documented on page 142.)

`\newton` Named derived units: second half of alphabet.

```
\ohm 1066 \siunitx_declare_unit:Nn \newton { N }  
\pascal 1067 \siunitx_declare_unit:Nx \ohm { \_siunitx_unit_non_latin:n { "03A9 } }  
\radian 1068 \siunitx_declare_unit:Nn \pascal { Pa }  
\siemens 1069 \siunitx_declare_unit:Nn \radian { rad }  
\sievert 1070 \siunitx_declare_unit:Nn \siemens { S }  
\steradian 1071 \siunitx_declare_unit:Nn \sievert { Sv }  
\tesla 1072 \siunitx_declare_unit:Nn \steradian { sr }  
\volt 1073 \siunitx_declare_unit:Nn \tesla { T }  
\watt 1074 \siunitx_declare_unit:Nn \volt { V }  
\weber 1075 \siunitx_declare_unit:Nn \watt { W }  
1076 \siunitx_declare_unit:Nn \weber { Wb }
```

(End definition for `\newton` and others. These functions are documented on page 142.)

`\astronomicalunit` Non-SI, but accepted for general use. Once again there are two spellings, here for litre and with different output in this case.

```
\bel  
\dalton 1077 \siunitx_declare_unit:Nn \astronomicalunit { au }  
\day 1078 \siunitx_declare_unit:Nn \bel { B }  
\decibel 1079 \siunitx_declare_unit:Nn \decibel { \deci \bel }  
\electronvolt 1080 \siunitx_declare_unit:Nn \dalton { Da }  
\hectare 1081 \siunitx_declare_unit:Nn \day { d }  
\hour  
\litre  
\liter  
\minute  
\neper  
\tonne
```

```

1082 \siunitx_declare_unit:Nn \electronvolt      { eV }
1083 \siunitx_declare_unit:Nn \hectare          { ha }
1084 \siunitx_declare_unit:Nn \hour             { h }
1085 \siunitx_declare_unit:Nn \litre            { L }
1086 \siunitx_declare_unit:Nn \liter            { litre }
1087 \siunitx_declare_unit:Nn \minute           { min }
1088 \siunitx_declare_unit:Nn \neper             { Np }
1089 \siunitx_declare_unit:Nn \tonne            { t }

```

(End definition for `\astronomicalunit` and others. These functions are documented on page 142.)

`\arcminute` Arc units: again, non-SI, but accepted for general use.

```

1090 \siunitx_declare_unit:Nx \arcminute { \_siunitx_unit_non_latin:n { "02B9" } }
1091 \siunitx_declare_unit:Nx \arcsecond { \_siunitx_unit_non_latin:n { "02BA" } }
1092 \siunitx_declare_unit:Nx \degree { \_siunitx_unit_non_latin:n { "00B0" } }

```

(End definition for `\arcminute`, `\arcsecond`, and `\degree`. These functions are documented on page 142.)

`\percent` For percent, the raw character is the most flexible way of handling output.

```
1093 \siunitx_declare_unit:Nx \percent { \cs_to_str:N \% }
```

(End definition for `\percent`. This function is documented on page 142.)

`\square` Basic powers.

```

1094 \siunitx_declare_power>NNn \square \squared { 2 }
1095 \siunitx_declare_power>NNn \cubic \cubed { 3 }

```

(End definition for `\square` and others. These functions are documented on page 142.)

6.12 Messages

```

1096 \msg_new:nnnn { siunitx } { unit / dangling-part }
1097   { Found-#1-part-with-no-unit. }
1098   {
1099     Each-#1-part-must-be-associated-with-a-unit:-a-#1-part-was-found-
1100     but-no-following-unit-was-given.
1101   }
1102 \msg_new:nnnn { siunitx } { unit / duplicate-part }
1103   { Duplicate-#1-part:#2. }
1104   {
1105     Each-unit-may-have-only-one-#1:\\
1106     the-additional-#1-part-'#2'-will-be-ignored.
1107   }
1108 \msg_new:nnnn { siunitx } { unit / duplicate-sticky-per }
1109   { Duplicate-\token_to_str:N \per. }
1110   {
1111     When-the-'sticky-per'-option-is-active,-only-one-
1112     \token_to_str:N \per \ may-appear-in-a-unit.
1113   }
1114 \msg_new:nnnn { siunitx } { unit / literal }
1115   { Literal-units-disabled. }
1116   {
1117     You-gave-the-literal-input-'#1'-
1118     but-literal-unit-output-is-disabled.

```

```

1119    }
1120 \msg_new:nnnn { siunitx } { unit / non-convertible-exponent }
1121   { Exponent~'#1'~cannot~be~converted~into~a~symbolic~prefix. }
1122   {
1123     The~exponent~'#1'~does~not~match~with~any~of~the~symbolic~prefixes~
1124     set~up.
1125   }
1126 \msg_new:nnnn { siunitx } { unit / non-numeric-exponent }
1127   { Prefix~'#1'~does~not~have~a~numerical~value. }
1128   {
1129     The~prefix~'#1'~needs~to~be~combined~with~a~number,~but~it~has~no
1130     numerical~value.
1131   }
1132 \msg_new:nnnn { siunitx } { unit / part-before-unit }
1133   { Found~#1~part~before~first~unit:~#2. }
1134   {
1135     The~#1-part~'#2'~must~follow~after~a~unit:~
1136     it~cannot~appear~before~any~units~and~will~therefore~be~ignored.
1137   }

```

6.13 Standard settings for module options

Some of these follow naturally from the point of definition (*e.g.* boolean variables are always `false` to begin with), but for clarity everything is set here.

```

1138 \keys_set:nn { siunitx }
1139   {
1140     bracket-unit-denominator = true ,
1141     forbid-literal-units = false ,
1142     fraction-command = \frac ,
1143     inter-unit-product = \, ,
1144     extract-mass-in-kilograms = true ,
1145     parse-units = true ,
1146     per-mode = power ,
1147     per-symbol = / ,
1148     qualifier-mode = subscript ,
1149     qualifier-phrase = ,
1150     sticky-per = false ,
1151     unit-font-command = \mathrm
1152   }
1153 
```

References

- [1] *The International System of Units (SI)*, <https://www.bipm.org/en/measurement-units/>.
- [2] *SI base units*, <https://www.bipm.org/en/measurement-units/si-base-units>.

Part XI

siunitx-abbreviations – Abbreviations

\A Abbreviations for currents.
\pA
\nA
\uA
\mA
\kA

\fg Abbreviations for masses.
\pg
\ng
\ug
\mg
\g
\kg

\K Abbreviations for temperature.

\m Abbreviations for lengths.
\pm
\nm
\um
\mm
\cm
\dm
\km

\s Abbreviations for times.
\as
\fs
\ps
\ns
\us
\ms

\Hz Abbreviations for frequencies.
\mHz
\kHz
\MHz
\GHz
\THz

\mol Abbreviations for moles.
\fmol
\pmol
\nmol
\umol
\mmol
\kmol

\V Abbreviations for potentials.
\pV
\nV
\uV
\mV
\kV

\hl Abbreviations for volumes.
\l
\ml
\ul
\hL
\L
\mL
\uL

\W Abbreviations for powers.
\uW
\mW
\kW
\MW
\GW

\kJ Abbreviations for energies.
\J
\mJ
\uJ
\eV
\meV
\keV
\MeV
\GeV
\TeV

\N Abbreviations for forces.
\mN
\kN
\MN

`\Pa` Abbreviations for pressures.
`\kPa`
`\MPa`
`\GPa`

`\mohm` Abbreviations for resistance.
`\kohm`
`\Mohm`

`\F` Abbreviations for capacitance.
`\fF`
`\pF`
`\nF`
`\uF`

`\dB` Abbreviation for decibel.

`\kWh` Abbreviation for kilowatt-hours.

1 **siunitx-abbreviation** implementation

Start the DocStrip guards.

`1 (*package)`

The abbreviation file contains a number of short (mainly two or three letter) versions of the usual long names. They are divided up into related groups, mainly to avoid an overly long list in one place.

`\A` Currents.
`\pA` 2 `\siunitx_declare_unit:Nn \A { \ampere }`
`\nA` 3 `\siunitx_declare_unit:Nn \pA { \pico \ampere }`
`\uA` 4 `\siunitx_declare_unit:Nn \nA { \nano \ampere }`
`\mA` 5 `\siunitx_declare_unit:Nn \uA { \micro \ampere }`
`\kA` 6 `\siunitx_declare_unit:Nn \mA { \milli \ampere }`
7 `\siunitx_declare_unit:Nn \kA { \kilo \ampere }`

(End definition for `\A` and others. These functions are documented on page 177.)

`\Hz` Then frequencies.

`\mHz` 8 `\siunitx_declare_unit:Nn \Hz { \hertz }`
`\kHz` 9 `\siunitx_declare_unit:Nn \mHz { \milli \hertz }`
`\MHz` 10 `\siunitx_declare_unit:Nn \kHz { \kilo \hertz }`
`\GHz` 11 `\siunitx_declare_unit:Nn \MHz { \mega \hertz }`
`\THz` 12 `\siunitx_declare_unit:Nn \GHz { \giga \hertz }`
13 `\siunitx_declare_unit:Nn \THz { \tera \hertz }`

(End definition for `\Hz` and others. These functions are documented on page 177.)

`\mol` Amounts of substance (moles).

```
14 \siunitx_declare_unit:Nn \mol { \mole }
15 \siunitx_declare_unit:Nn \fmol { \femto \mole }
16 \siunitx_declare_unit:Nn \pmol { \pico \mole }
17 \siunitx_declare_unit:Nn \nmol { \nano \mole }
18 \siunitx_declare_unit:Nn \umol { \micro \mole }
19 \siunitx_declare_unit:Nn \mmol { \milli \mole }
20 \siunitx_declare_unit:Nn \kmol { \kilo \mole }
```

(End definition for `\mol` and others. These functions are documented on page 178.)

`\V` Potentials.

```
21 \siunitx_declare_unit:Nn \V { \volt }
22 \siunitx_declare_unit:Nn \pV { \pico \volt }
23 \siunitx_declare_unit:Nn \nV { \nano \volt }
24 \siunitx_declare_unit:Nn \uV { \micro \volt }
25 \siunitx_declare_unit:Nn \mV { \milli \volt }
26 \siunitx_declare_unit:Nn \kV { \kilo \volt }
```

(End definition for `\V` and others. These functions are documented on page 178.)

`\hl` Volumes.

```
27 \siunitx_declare_unit:Nn \hl { \hecto \litre }
28 \siunitx_declare_unit:Nn \l { \litre }
29 \siunitx_declare_unit:Nn \ml { \milli \litre }
30 \siunitx_declare_unit:Nn \ul { \micro \litre }
31 \siunitx_declare_unit:Nn \hL { \hecto \liter }
32 \siunitx_declare_unit:Nn \L { \liter }
33 \siunitx_declare_unit:Nn \mL { \milli \liter }
34 \siunitx_declare_unit:Nn \uL { \micro \liter }
```

(End definition for `\hl` and others. These functions are documented on page 178.)

`\fg` Masses.

```
35 \siunitx_declare_unit:Nn \fg { \femto \gram }
36 \siunitx_declare_unit:Nn \pg { \pico \gram }
37 \siunitx_declare_unit:Nn \ng { \nano \gram }
38 \siunitx_declare_unit:Nn \ug { \micro \gram }
39 \siunitx_declare_unit:Nn \mg { \milli \gram }
40 \siunitx_declare_unit:Nn \g { \gram }
41 \siunitx_declare_unit:Nn \kg { \kilo \gram }
```

(End definition for `\fg` and others. These functions are documented on page 177.)

`\W` Energies and powers

```
42 \siunitx_declare_unit:Nn \W { \watt }
43 \siunitx_declare_unit:Nn \uW { \micro \watt }
44 \siunitx_declare_unit:Nn \mW { \milli \watt }
45 \siunitx_declare_unit:Nn \kW { \kilo \watt }
46 \siunitx_declare_unit:Nn \MW { \mega \watt }
47 \siunitx_declare_unit:Nn \GW { \giga \watt }
48 \siunitx_declare_unit:Nn \J { \joule }
49 \siunitx_declare_unit:Nn \uJ { \micro \joule }
```

`\uJ`

`\eV`

`\meV`

`\keV`

`\MeV`

`\GeV`

`\TeV`

`\kWh`

```

50 \siunitx_declare_unit:Nn \mJ { \milli \joule }
51 \siunitx_declare_unit:Nn \kJ { \kilo \joule }
52 \siunitx_declare_unit:Nn \eV { \electronvolt }
53 \siunitx_declare_unit:Nn \meV { \milli \electronvolt }
54 \siunitx_declare_unit:Nn \keV { \kilo \electronvolt }
55 \siunitx_declare_unit:Nn \MeV { \mega \electronvolt }
56 \siunitx_declare_unit:Nn \GeV { \giga \electronvolt }
57 \siunitx_declare_unit:Nn \TeV { \tera \electronvolt }
58 \siunitx_declare_unit:Nnn \kWh { \kilo \watt \hour }
59 { inter-unit-product = }

```

(End definition for `\W` and others. These functions are documented on page 178.)

\m Lengths.

```

\pm 60 \siunitx_declare_unit:Nn \m { \metre }
\nm 61 \siunitx_declare_unit:Nn \pm { \pico \metre }
\nm 62 \siunitx_declare_unit:Nn \nm { \nano \metre }
\mm 63 \siunitx_declare_unit:Nn \um { \micro \metre }
\cm 64 \siunitx_declare_unit:Nn \mm { \milli \metre }
\dm 65 \siunitx_declare_unit:Nn \cm { \centi \metre }
\km 66 \siunitx_declare_unit:Nn \dm { \deci \metre }
\km 67 \siunitx_declare_unit:Nn \km { \kilo \metre }

```

(End definition for `\m` and others. These functions are documented on page 177.)

\K Temperatures.

```

68 \siunitx_declare_unit:Nn \K { \kelvin }

```

(End definition for `\K`. This function is documented on page 177.)

\dB

```

69 \siunitx_declare_unit:Nn \dB { \deci \bel }

```

(End definition for `\dB`. This function is documented on page 179.)

\F Capacitance.

```

\fF 70 \siunitx_declare_unit:Nn \F { \farad }
\pF 71 \siunitx_declare_unit:Nn \fF { \femto \farad }
\nF 72 \siunitx_declare_unit:Nn \pF { \pico \farad }
\uF 73 \siunitx_declare_unit:Nn \nF { \nano \farad }
\UF 74 \siunitx_declare_unit:Nn \uF { \micro \farad }

```

(End definition for `\F` and others. These functions are documented on page 179.)

\H Capacitance.

```

\mH 75 \siunitx_declare_unit:Nn \H { \henry }
\uH 76 \siunitx_declare_unit:Nn \mH { \milli \henry }
\uH 77 \siunitx_declare_unit:Nn \uH { \micro \henry }

```

(End definition for `\H`, `\mH`, and `\uH`. These functions are documented on page ??.)

\N Forces.

```

\mN 78 \siunitx_declare_unit:Nn \N { \newton }
\kN 79 \siunitx_declare_unit:Nn \mN { \milli \newton }
\MN 80 \siunitx_declare_unit:Nn \kN { \kilo \newton }
\MN 81 \siunitx_declare_unit:Nn \MN { \mega \newton }

```

(End definition for `\N` and others. These functions are documented on page 178.)

`\Pa` Pressures.
`\kPa` 82 `\siunitx_declare_unit:Nn \Pa { \pascal }`
`\MPa` 83 `\siunitx_declare_unit:Nn \kPa { \kilo \pascal }`
`\GPa` 84 `\siunitx_declare_unit:Nn \MPa { \mega \pascal }`
85 `\siunitx_declare_unit:Nn \GPa { \giga \pascal }`

(End definition for `\Pa` and others. These functions are documented on page 179.)

`\mohm` Resistances.
`\kohm` 86 `\siunitx_declare_unit:Nn \mohm { \milli \ohm }`
`\Mohm` 87 `\siunitx_declare_unit:Nn \kohm { \kilo \ohm }`
88 `\siunitx_declare_unit:Nn \Mohm { \mega \ohm }`

(End definition for `\mohm`, `\kohm`, and `\Mohm`. These functions are documented on page 179.)

`\s` Finally, times.
`\as` 89 `\siunitx_declare_unit:Nn \s { \second }`
`\fs` 90 `\siunitx_declare_unit:Nn \as { \atto \second }`
`\ps` 91 `\siunitx_declare_unit:Nn \fs { \femto \second }`
`\ns` 92 `\siunitx_declare_unit:Nn \ps { \pico \second }`
`\us` 93 `\siunitx_declare_unit:Nn \ns { \nano \second }`
`\ms` 94 `\siunitx_declare_unit:Nn \us { \micro \second }`
95 `\siunitx_declare_unit:Nn \ms { \milli \second }`

(End definition for `\s` and others. These functions are documented on page 177.)

96 `</package>`

Part XII

siunitx-binary – Binary units

This submodule provides binary units and prefixes. These are not formally part of the SI but are recommended by BIPM as units of information.

| | |
|--------------|---|
| <u>\kibi</u> | Prefixes, all of which are integer powers of 2: the powers are <i>not</i> stored or available for conversion. |
| <u>\mebi</u> | |
| <u>\gibi</u> | |
| <u>\tebi</u> | |
| <u>\pebi</u> | |
| <u>\exbi</u> | |
| <u>\zebi</u> | |
| <u>\yobi</u> | |
| | |
| <u>\bit</u> | Units for bits and bytes. |
| <u>\byte</u> | |

1 siunitx-binary implementation

Start the DocStrip guards.

`1 <*package>`

`\kibi` All very simple.
`\mebi` 2 `\siunitx_declare_prefix:Nn \kibi { Ki }`
`\gibi` 3 `\siunitx_declare_prefix:Nn \mebi { Mi }`
`\tebi` 4 `\siunitx_declare_prefix:Nn \gibi { Gi }`
`\pebi` 5 `\siunitx_declare_prefix:Nn \tebi { Ti }`
`\exbi` 6 `\siunitx_declare_prefix:Nn \pebi { Pi }`
`\zebi` 7 `\siunitx_declare_prefix:Nn \exbi { Ei }`
`\yobi` 8 `\siunitx_declare_prefix:Nn \zebi { Zi }`
 9 `\siunitx_declare_prefix:Nn \yobi { Yi }`

(End definition for `\kibi` and others. These functions are documented on page 183.)

`\bit`
`\byte` 10 `\siunitx_declare_unit:Nn \bit { bit }`
 11 `\siunitx_declare_unit:Nn \byte { B }`

(End definition for `\bit` and `\byte`. These functions are documented on page 183.)

`12 </package>`

Part XIII

siunitx-command – Units as document command

This submodule provides support for creating free-standing document commands for unit macros.

1 Creating units as document commands

\siunitx_command_create:

`\siunitx_command_create:`

Maps over the list of known unit commands and creates the appropriate document command to support them, as controlled by the options below.

1.1 Key-value options

The options defined by this submodule are available within the `\I3keys siunitx` tree.

These options are all preamble-only.

free-standing-units

`free-standing-units = true|false`

Switch to determine whether free standing document commands are created for symbolic units. This will include not only units themselves but also prefixes, *etc.* The standard setting is `false`.

overwrite-commands

`overwrite-commands = true|false`

Switch to determine whether when creating free standing document commands, any existing document commands are overwritten. The standard setting is `false`.

space-before-unit

`space-before-unit = true|false`

Switch to determine whether a space is inserted before free standing document commands. The standard setting is `false`.

unit-optional-argument

`unit-optional-argument = true|false`

Switch to determine whether free standing document commands take an optional argument (a number). The standard setting is `false`.

use-xspace

`use-xspace = true|false`

Switch to determine whether free standing document commands use the `xparse` package to insert space after the command names. The standard setting is `false`. When set `true`, the `xparse` package will be loaded at the start of the document if not already available.

2 siunitx-command implementation

Start the DocStrip guards.

1 `(*package)`

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

2 `(@=siunitx_command)`

```
\l_siunitx_command_tmp_t1
 3 \tl_new:N \l_siunitx_command_tmp_t1
```

(End definition for `\l_siunitx_command_tmp_t1`.)

2.1 Options

```
\l_siunitx_command_create_bool
\l_siunitx_command_overwrite_bool
\l_siunitx_command_prespace_bool
\l_siunitx_command_optarg_bool
\l_siunitx_command_xspace_bool
4 \keys_define:nn { siunitx }
5 {
6   free-standing-units .bool_set:N =
7     \l_siunitx_command_create_bool ,
8   overwrite-commands .bool_set:N =
9     \l_siunitx_command_overwrite_bool ,
10  space-before-unit .bool_set:N =
11    \l_siunitx_command_prespace_bool ,
12  unit-optional-argument .bool_set:N =
13    \l_siunitx_command_optarg_bool ,
14  use-xspace .bool_set:N =
15    \l_siunitx_command_xspace_bool
16 }
```

(End definition for `\l_siunitx_command_create_bool` and others.)

These preamble-only options are all disabled at the start of the document.

```
17 \AtBeginDocument
18 {
19   \clist_map_inline:nn
20   {
21     free-standing-units ,
22     overwrite-commands ,
23     space-before-unit ,
24     unit-optional-argument ,
25     use-xspace
26   }
27   {
28     \keys_define:nn { siunitx }
29     {
30       #1 .code:n =
31         { \msg_warning:nnn { siunitx } { option-preamble-only } {#1} }
32     }
33   }
34 }
35 \msg_new:nnn { siunitx } { option-preamble-only }
36   { Option-'#1'~only~available~in~the~preamble. }
```

2.2 Creation of unit document commands

```
\siunitx_command_create:  
\_siunitx_command_create:  
\_siunitx_command_create:N
```

Creating document commands is all done by a single function which is set up using expansion: that way the tests are only run once. Other than that, this is all just a question of picking up all the various routes. Where the `soulpos` package is loaded *after* `siunitx`, the commands `\hl` and `\ul` will be created only after the hook is used. The `soul` package creates those using `\newcommand`, so we have to avoid an issue.

```
37 \cs_new_protected:Npn \siunitx_command_create:  
38 {  
39     \bool_if:NT \l_siunitx_command_create_bool  
40     {  
41         \_siunitx_command_create:  
42         \c_ifpackageloaded { soulpos }  
43         {  
44             \c_ifpackageloaded { soul }  
45             { }  
46             {  
47                 \cs_undefine:N \hl  
48                 \cs_undefine:N \ul  
49             }  
50         }  
51     }  
52 }
```

At the beginning of table cells and inside `x`-type expansion, all symbolic units need to have *some* definition.

```
53 \seq_map_inline:Nn \l_siunitx_unit_symbolic_seq  
54 {  
55     \cs_if_free:NT ##1  
56     { \cs_set_protected:Npn ##1 { \ERROR } }  
57 }  
58 }  
59 \AtBeginDocument { \siunitx_command_create: }  
60 \cs_new_protected:Npn \_siunitx_command_create:  
61 {  
62     \bool_if:NT \l_siunitx_command_xspace_bool  
63     { \RequirePackage { xspace } }  
64     \bool_if:NT \l_siunitx_command_overwrite_bool  
65     {  
66         \seq_map_inline:Nn \l_siunitx_unit_symbolic_seq  
67         { \cs_undefine:N ##1 }  
68     }  
69     \cs_set_protected:Npx \_siunitx_command_create:N ##1  
70     {  
71         \ProvideDocumentCommand ##1 { \bool_if:NT \l_siunitx_command_optarg_bool { o } }  
72         {  
73             \mode_leave_vertical:  
74             \group_begin:  
75                 \bool_if:NTF \l_siunitx_command_optarg_bool  
76                 { \exp_not:N \IfNoValueTF {####1} }  
77                 { \use_i:nn }  
78                 {  
79                     \siunitx_unit_options_apply:n {##1}  
80                     \bool_if:NT \l_siunitx_command_prespace_bool { \exp_not:N \ }
```

```

81      \siunitx_unit_format:nN {##1}
82      \exp_not:N \l_siunitx_command_tmp_tl
83      \siunitx_print_unit:V
84      \exp_not:N \l_siunitx_command_tmp_tl
85    }
86    { \siunitx_quantity:nn {####1} {##1} }
87  \group_end:
88  \bool_if:NT \l_siunitx_command_xspace_bool { \exp_not:N \xspace }
89 }
90 }
91 \seq_map_function:NN \l_siunitx_unit_seq \__siunitx_command_create:N
92 }
93 \cs_new_protected:Npn \__siunitx_command_create:N #1 { }

```

(End definition for `\siunitx_command_create:`, `_siunitx_command_create:`, and `__siunitx_command_create:N`. This function is documented on page 184.)

2.3 Standard settings for module options

Some of these follow naturally from the point of definition (e.g. boolean variables are always `false` to begin with), but for clarity everything is set here.

```

94 \keys_set:nn { siunitx }
95 {
96   free-standing-units = false ,
97   overwrite-commands = false ,
98   space-before-unit = false ,
99   unit-optional-argument = false ,
100  use-xspace = false
101 }
102 
```

Part XIV

siunitx-emulation – Emulation

1 siunitx-emulation implementation

Identify the internal prefix (L^AT_EX3 DocStrip convention). In contrast to other parts of the bundle, the functions here may need to redefine those from various submodules.

```
1  <@=siunitx>
    Start the DocStrip guards.
2  <*package>
3  <*options>
    Some messages.
4  \msg_new:nnn { siunitx } { option-deprecated }
5  {
6      Option~"#1"~has~been~deprecated~in~this~release. \\ \\
7      Use~"#2"~as~a~replacement.
8  }
9  \msg_new:nnn { siunitx } { option-removed }
10   { Option~"#1"~has~been~removed~in~this~release. }
```

Abstract out a simple wrapper.

```
11 \cs_new_protected:Npn \_siunitx_option_deprecated:nn #1#2
12 {
13     \msg_info:nnnn { siunitx } { option-deprecated } {#1} {#2}
14     \keys_set:nn { siunitx } {#2}
15 }
16 \cs_new_protected:Npn \_siunitx_option_deprecated:nnn #1#2#3
17 {
18     \msg_info:nnnn { siunitx } { option-deprecated } {#1} {#2}
19     \keys_set:nn { siunitx } { #2 = #3 }
20 }
21 \cs_generate_variant:Nn \_siunitx_option_deprecated:nnn { nnV }
```

(End definition for `_siunitx_option_deprecated:nn` and `_siunitx_option_deprecated:nnn`.)

Abstract out a simple wrapper.

```
22 \cs_new_protected:Npn \_siunitx_option_removed:n #1
23 {
24     \msg_warning:nnx { siunitx } { option-removed }
25     {#1}
26 }
27 \cs_generate_variant:Nn \_siunitx_option_removed:n { V }
```

(End definition for `_siunitx_option_removed:n`.)

1.1 Load-time option

```
28 \clist_map_inline:nn
29   {
30     abbreviations      ,
31     binary-units      ,
32     load-configurations ,
33     version-1-compatibility
34   }
35   {
36     \keys_define:nn { siunitx } { #1 .code:n = \__siunitx_option_removed:n {#1} }
37 }
```

1.2 Angle options

All straight-forward emulation.

```
38 \keys_define:nn { siunitx }
39   {
40     add-arc-degree-zero .code:n =
41     {
42       \__siunitx_option_DEPRECATED:nV
43         { add-arc-degree-zero }
44         { fill-angle-degrees }
45         \l_keys_value_tl
46     } ,
47     add-arc-degree-zero .default:n = true ,
48     add-arc-minute-zero .code:n =
49     {
50       \__siunitx_option_DEPRECATED:nV
51         { add-arc-minute-zero }
52         { fill-angle-minutes }
53         \l_keys_value_tl
54     } ,
55     add-arc-minute-zero .default:n = true ,
56     add-arc-second-zero .code:n =
57     {
58       \__siunitx_option_DEPRECATED:nV
59         { add-arc-second-zero }
60         { fill-angle-seconds }
61         \l_keys_value_tl
62     } ,
63     add-arc-second-zero .default:n = true ,
64     arc-separator .code:n =
65     {
66       \__siunitx_option_DEPRECATED:nV
67         { arc-separator }
68         { angle-separator }
69         \l_keys_value_tl
70     }
71 }
```

1.3 Combination functions options

```
72 \keys_define:nn { siunitx }
73   {
```

```

74   list-units / brackets .code:n =
75   {
76     \_siunitx_option_deprecated:nn
77     { list-units{=brackets} }
78     { list-units{=bracket} }
79   } ,
80   range-units / brackets .code:n =
81   {
82     \_siunitx_option_deprecated:nn
83     { range-units{=brackets} }
84     { range-units{=bracket} }
85   } ,
86   product-units / brackets .code:n =
87   {
88     \_siunitx_option_deprecated:nn
89     { product-units{=brackets} }
90     { product-units{=bracket} }
91   }
92 }
```

1.4 Command options

```

93 \keys_define:nn { siunitx }
94   {
95     overwrite-functions .code:n =
96     {
97       \_siunitx_option_deprecated:nnV
98       { overwrite-functions }
99       { overwrite-commands }
100      \l_keys_value_tl
101    } ,
102    overwrite-functions .default:n = true
103 }
```

1.5 Print options

```

104 \keys_define:nn { siunitx }
105   {
106     detect-all .code:n =
107     {
108       \_siunitx_option_deprecated:nn
109       { detect-all }
110       {
111         mode{=match} , ~
112         propagate-math-font{=true} , ~
113         reset-math-version{=false} , ~
114         reset-text-family{=false} , ~
115         reset-text-series{=false} , ~
116         text-family-to-math{=true} , ~
117         text-series-to-math{=true}
118       }
119     } ,
120     detect-family .code:n =
121     {
122       \_siunitx_option_deprecated:nn
123       { detect-family }
```

```

124     {
125         reset-text-family=-false , ~
126         text-family-to-math=-true
127     }
128 },
129 detect-mode .code:n =
130 {
131     \_siunitx_option_deprecated:nn
132     { detect-mode }
133     { mode=-match }
134 },
135 detect-none .code:n =
136 {
137     \_siunitx_option_deprecated:nn
138     { detect-none }
139     {
140         mode=-math , ~
141         propagate-math-font=-false , ~
142         reset-math-version=-true , ~
143         reset-text-family=-true , ~
144         reset-text-series=-true , ~
145         text-family-to-math=-false , ~
146         text-series-to-math=-false
147     }
148 },
149 detect-shape .code:n =
150 {
151     \_siunitx_option_deprecated:nn
152     { detect-shape }
153     { reset-text-shape=-false }
154 },
155 detect-weight .code:n =
156 {
157     \_siunitx_option_deprecated:nn
158     { detect-weight }
159     {
160         reset-text-series=-false , ~
161         text-series-to-math=-true
162     }
163 }
164 \clist_map_inline:nn
165 {
166     detect-display-math ,
167     detect-inline-family ,
168     detect-inline-weight
169 }
170 {
171     \keys_define:nn { siunitx } { #1 .code:n = \_siunitx_option_removed:n {#1} }
172 }
173 }

The old font insertion options.

174 \clist_map_inline:nn
175 {
176     math-rm

```

```

177   math-sf      ,
178   math-tt      ,
179   number-math-rm ,
180   number-math-sf ,
181   number-math-tt ,
182   number-text-rm ,
183   number-text-sf ,
184   number-text-tt ,
185   text-rm       ,
186   text-sf       ,
187   text-tt       ,
188   unit-math-rm ,
189   unit-math-sf ,
190   unit-math-tt ,
191   unit-text-rm ,
192   unit-text-sf ,
193   unit-text-tt
194 }
195 {
196 \keys_define:nn { siunitx } { #1 .code:n = \__siunitx_option_removed:n {#1} }
197 }

```

1.6 Symbol options

```

198 \clist_map_inline:nn
199 {
200   math-angstrom ,
201   math-arcminute ,
202   math-arcsecond ,
203   math-celsius ,
204   math-degree ,
205   math-micro ,
206   math-ohm ,
207   text-angstrom ,
208   text-arcminute ,
209   text-arcsecond ,
210   text-celsius ,
211   text-degree ,
212   text-micro ,
213   text-ohm ,
214 }
215 {
216 \keys_define:nn { siunitx } { #1 .code:n = \__siunitx_option_removed:n {#1} }
217 }

```

1.7 Number options

```

218 \keys_define:nn { siunitx }
219 {
220   group-digits / false .code:n =
221   {
222     \__siunitx_option_deprecated:nn
223     { group-digits ~ = ~ false }
224     { group-digits ~ = ~ none }
225   },
226   group-digits / true .code:n =

```

```

227   {
228     \_siunitx_option_deprecated:nn
229       { group-digits ~ = ~ true }
230       { group-digits ~ = ~ all }
231   } ,
232   input-symbols .code:n =
233   {
234     \msg_info:nnn { siunitx } { option-deprecated }
235       { input-symbols } { input-digits }
236       \tl_put_right:Nn \l_siunitx_number_input_digit_tl {#1}
237   } ,
238   separate-uncertainty .choice: ,
239   separate-uncertainty / false .code:n =
240   {
241     \_siunitx_option_deprecated:nn
242       { separate-uncertainty }
243       { uncertainty-mode=compact }
244   } ,
245   separate-uncertainty / true .code:n =
246   {
247     \_siunitx_option_deprecated:nn
248       { separate-uncertainty }
249       { uncertainty-mode=separate }
250   } ,
251   separate-uncertainty .default:n = true
252 }
```

A small number of removed options.

```

253 \clist_map_inline:nn
254   {
255     input-protect-tokens ,
256     input-quotient ,
257     output-product ,
258     quotient-mode
259   }
260   {
261     \keys_define:nn { siunitx } { #1 .code:n = \_siunitx_option_removed:n {#1} }
262   }
```

Options for number processing: largely removals.

```

263 \keys_define:nn { siunitx }
264   {
265     add-decimal-zero .choice: ,
266     add-decimal-zero / false .code:n =
267   {
268     \_siunitx_option_deprecated:nn
269       { add-decimal-zero }
270       { minimum-decimal-digits=-0 }
271   } ,
272   add-decimal-zero / true .code:n =
273   {
274     \_siunitx_option_deprecated:nn
275       { add-decimal-zero }
276       { minimum-decimal-digits=-1 }
277   },
```

```

278   add-decimal-zero .default:n = true ,
279   add-integer-zero .code:n =
280     { \_siunitx_option_removed:V \l_keys_key_tl } ,
281   close-bracket .code:n =
282     { \_siunitx_option_removed:V \l_keys_key_tl } ,
283   bracket-numbers .choice: ,
284   bracket-numbers / false .code:n =
285   {
286     \_siunitx_option_deprecated:nn
287       { bracket-numbers }
288       { bracket-ambiguous-numbers==false }
289   } ,
290   bracket-numbers / true .code:n =
291   {
292     \_siunitx_option_deprecated:nn
293       { bracket-numbers }
294       { bracket-ambiguous-numbers==true }
295   } ,
296   bracket-numbers .default:n = true ,
297   explicit-sign .code:n =
298   {
299     \str_if_eq:nnTF {#1} { + }
300     {
301       \_siunitx_option_deprecated:nn
302         { explicit-sign }
303         { print-implicit-plus==true }
304     }
305     { \_siunitx_option_removed:V \l_keys_key_tl }
306   } ,
307   group-four-digits .choice: ,
308   group-four-digits / false .code:n =
309   {
310     \_siunitx_option_deprecated:nn
311       { group-four-digits==false }
312       { group-minimum-digits==5 }
313   } ,
314   group-four-digits / true .code:n =
315   {
316     \_siunitx_option_deprecated:nn
317       { group-four-digits==false }
318       { group-minimum-digits==4 }
319   } ,
320   bracket-numbers .default:n = true ,
321   omit-uncertainty .code:n =
322   {
323     \_siunitx_option_deprecated:nnV
324       { omit-uncertainty }
325       { drop-uncertainty }
326       \l_keys_value_tl
327   } ,
328   omit-uncertainty .default:n = true ,
329   open-bracket .code:n =
330     { \_siunitx_option_removed:V \l_keys_key_tl } ,
331   retain-unity-mantissa .code:n =

```

```

332 {
333   \_\_siunitx\_option\_deprecated:nnV
334     { retain-unity-mantissa }
335     { print-unity-mantissa }
336     \l_keys_value_tl
337   } ,
338   retain-unity-mantissa .default:n = true ,
339   retain-zero-exponent .code:n =
340   {
341     \_\_siunitx\_option\_deprecated:nnV
342       { retain-zero-exponent }
343       { print-zero-exponent }
344       \l_keys_value_tl
345   } ,
346   retain-zero-exponent .default:n = true ,
347   round-integer-to-decimal .code:n =
348   { \_\_siunitx\_option\_removed:V \l_keys_key_t1 } ,
349   scientific-notation .choice: ,
350   scientific-notation / engineering .code:n =
351   {
352     \_\_siunitx\_option\_deprecated:nn
353       { scientific-notation-==engineering }
354       { exponent-mode-==engineering }
355   } ,
356   scientific-notation / fixed .code:n =
357   {
358     \_\_siunitx\_option\_deprecated:nn
359       { scientific-notation-==fixed }
360       { exponent-mode-==fixed }
361   } ,
362   scientific-notation / false .code:n =
363   {
364     \_\_siunitx\_option\_deprecated:nn
365       { scientific-notation-==false }
366       { exponent-mode-==input }
367   } ,
368   scientific-notation / true .code:n =
369   {
370     \_\_siunitx\_option\_deprecated:nn
371       { scientific-notation-==true }
372       { exponent-mode-==scientific }
373   } ,
374   scientific-notation .default:n = true ,
375   zero-decimal-to-integer .code:n =
376   {
377     \_\_siunitx\_option\_deprecated:nnV
378       { zero-decimal-to-integer }
379       { drop-zero-decimal }
380       \l_keys_value_tl
381   } ,
382   zero-decimal-to-integer .default:n = true
383 }
```

1.7.1 Table options

All straight-forward emulation.

```
384 \keys_define:nn { siunitx }
385   {
386     table-align-text-post .code:n =
387     {
388       \__siunitx_option_deprecated:nnV
389         { table-align-text-post }
390         { table-align-text-after }
391         \l_keys_value_tl
392     } ,
393     table-align-text-post .default:n = true ,
394     table-align-text-pre .code:n =
395     {
396       \__siunitx_option_deprecated:nnV
397         { table-align-text-pre }
398         { table-align-text-before }
399         \l_keys_value_tl
400     } ,
401     table-align-text-pre .default:n = true ,
402     table-number-alignment / center-decimal-marker .code:n =
403     {
404       \msg_info:nnnn { siunitx } { option-deprecated }
405         { table-number-alignment~~center-decimal-marker }
406         { table-alignment-mode~~marker }
407       \keys_set:nn
408         { siunitx }
409         { table-alignment-mode = marker }
410     } ,
411     table-omit-exponent .code:n =
412     {
413       \__siunitx_option_deprecated:nnV
414         { table-omit-exponent }
415         { drop-exponent }
416         \l_keys_value_tl
417     } ,
418     table-omit-exponent .default:n = true ,
419     table-parse-only .code:n =
420     {
421       \msg_info:nnnn { siunitx } { option-deprecated }
422         { table-parse-only }
423         { table-alignment-mode~~none }
424       \str_if_eq:VnTF \l_keys_value_tl { false }
425         {
426           \keys_set:nn
427             { siunitx }
428             { table-alignment-mode = marker }
429         }
430         {
431           \keys_set:nn
432             { siunitx }
433             { table-alignment-mode = none }
434         }
435 }
```

```

435     } ,
436     table-space-text-post .code:n =
437     {
438       \msg_info:nnn { siunitx } { option-deprecated }
439         { table-space-text-post }
440         { table-format }
441       \tl_set:Nn \l_siunitx_table_after_model_tl {#1}
442     } ,
443     table-space-text-pre .code:n =
444     {
445       \msg_info:nnn { siunitx } { option-deprecated }
446         { table-space-text-post }
447         { table-format }
448       \tl_set:Nn \l_siunitx_table_before_model_tl {#1}
449     }
450   }

\_\_siunitx_option table_format:n
\_\_siunitx_option_table_comparator:nnnnnnnn
\_\_siunitx_option_table_figures:decimal:nnnnnnnn
\_\_siunitx_option_table_figures-exponent:nnnnnnnn
\_\_siunitx_option_table_figures-integer:nnnnnnnn
\_\_siunitx_option_table_figures-uncertainty:nnnnnnnn
\_\_siunitx_option_table_sign-exponent:nnnnnnnn
\_\_siunitx_option_table_sign-mantissa:nnnnnnnn

451 \cs_new_protected:Npn \_\_siunitx_option_table_format:n #1
452   {
453     \msg_info:nnn { siunitx } { option-deprecated }
454       { table- #1 }
455       { table-format }
456     \tl_set:Nx \l_siunitx_table_format_tl
457     {
458       \cs:w __siunitx_option_table_ #1 :nnnnnnnn
459         \exp_after:wN \exp_after:wN \exp_after:wN \cs_end:
460           \exp_after:wN \l_siunitx_table_format_tl
461           \exp_after:wN { \l_keys_value_tl }
462     }
463     \exp_after:wN \_\_siunitx_table_generate_model:nnnnnnnn
464       \l_siunitx_table_format_tl
465   }
466 \cs_new:Npn \_\_siunitx_option_table_comparator:nnnnnnnn #1#2#3#4#5#6#7#8
467   { \exp_not:n { {#8} {#2} {#3} {#4} {#5} {#6} {#7} } }
468 \cs_new:cpx { __siunitx_option_table_figures:decimal:nnnnnnnn } #1#2#3#4#5#6#7#8
469   { \exp_not:n { {#1} {#2} {#3} {#8} {#5} {#6} {#7} } }
470 \cs_new:cpx { __siunitx_option_table_figures-exponent:nnnnnnnn } #1#2#3#4#5#6#7#8
471   { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#6} {#8} } }
472 \cs_new:cpx { __siunitx_option_table_figures-integer:nnnnnnnn } #1#2#3#4#5#6#7#8
473   { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#6} {#8} } }
474 \cs_new:cpx { __siunitx_option_table_figures-uncertainty:nnnnnnnn } #1#2#3#4#5#6#7#8
475   { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#6} {#7} } }
476 \cs_new:cpx { __siunitx_option_table_sign-exponent:nnnnnnnn } #1#2#3#4#5#6#7#8
477   { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#8} {#6} {#7} } }
478 \cs_new:cpx { __siunitx_option_table_sign-mantissa:nnnnnnnn } #1#2#3#4#5#6#7#8
479   { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#8} {#7} {#6} } }
480 \cs_new:cpx { __siunitx_option_table_sign-mantissa:nnnnnnnn } #1#2#3#4#5#6#7#8
481   { \exp_not:n { {#1} {#2} {#3} {#4} {#5} {#8} {#7} {#6} } }
482 \cs_new:cpx { __siunitx_option_table_sign-mantissa:nnnnnnnn } #1#2#3#4#5#6#7#8
483   { \exp_not:n { {#1} {#8} {#3} {#4} {#5} {#6} {#7} {#2} } }
484 \cs_new:cpx { __siunitx_option_table_sign-mantissa:nnnnnnnn } #1#2#3#4#5#6#7#8
485   { \exp_not:n { {#1} {#8} {#3} {#4} {#5} {#6} {#7} {#2} } }

(End definition for \_\_siunitx_option_table_format:n and others.)

```

Options which all use the same emulation set up.

```

486 \keys_define:nn { siunitx }
487   {
488     table-comparator .code:n =
489       { \_siunitx_option_table_format:n { comparator } } ,
490     table-figures-decimal .code:n =
491       { \_siunitx_option_table_format:n { figures-decimal } } ,
492     table-figures-exponent .code:n =
493       { \_siunitx_option_table_format:n { figures-exponent } } ,
494     table-figures-integer .code:n =
495       { \_siunitx_option_table_format:n { figures-integer } } ,
496     table-figures-uncertainty .code:n =
497       { \_siunitx_option_table_format:n { figures-uncertainty } } ,
498     table-sign-exponent .code:n =
499       { \_siunitx_option_table_format:n { sign-exponent } } ,
500     table-sign-mantissa .code:n =
501       { \_siunitx_option_table_format:n { sign-mantissa } }
502   }

```

1.8 Unit options

```

503 \keys_define:nn { siunitx }
504   {
505     fraction-function .code:n =
506     {
507       \_siunitx_option_deprecated:nnV
508         { fraction-function }
509         { fraction-command }
510         \l_keys_value_tl
511     } ,
512     literal-superscript-as-power .code:n =
513       { \_siunitx_option_removed:V \l_keys_key_t1 } ,
514     per-mode / reciprocal .code:n =
515     {
516       \_siunitx_option_deprecated:nn
517         { per-mode=-reciprocal }
518         { per-mode=-power }
519     } ,
520     per-mode / reciprocal-positive-first .code:n =
521     {
522       \_siunitx_option_deprecated:nn
523         { per-mode=-reciprocal-positive-first }
524         { per-mode=-power-positive-first }
525     } ,
526     power-font .code:n =
527       { \_siunitx_option_removed:V \l_keys_key_t1 } ,
528     qualifier-mode / brackets .code:n =
529     {
530       \_siunitx_option_deprecated:nn
531         { qualifier-mode=-brackets }
532         { qualifier-mode=-bracket }
533     } ,
534     qualifier-mode / space .code:n =
535     {

```

```

536     \msg_info:nnn { siunitx } { option-deprecated }
537         { qualifier-mode==space }
538         { qualifier-mode==phrase"~plus~"qualifier-phrase=\ }
539     \keys_set:nn
540         { siunitx }
541         { qualifier-mode = phrase, qualifier-phrase = \ }
542     } ,
543     qualifier-mode / text .code:n =
544     {
545         \_siunitx_option_DEPRECATED:nn
546             { qualifier-mode==text }
547             { qualifier-mode==combine }
548     }
549 }
```

1.9 Quantity units

```

550 \keys_define:nn { siunitx }
551   {
552     allow-number-unit-breaks .code:n =
553     {
554         \_siunitx_option_DEPRECATED:nnV
555             { allow-number-unit-breaks }
556             { allow-quantity-breaks }
557             \l_keys_value_tl
558     } ,
559     allow-number-unit-breaks .default:n = true ,
560     exponent-to-prefix .choice: ,
561     exponent-to-prefix / false .code:n =
562     {
563         \_siunitx_option_DEPRECATED:nn
564             { exponent-to-prefix==false }
565             { prefix-mode==input }
566     } ,
567     exponent-to-prefix / true .code:n =
568     {
569         \_siunitx_option_DEPRECATED:nn
570             { exponent-to-prefix==true }
571             { prefix-mode==combine-exponent }
572     } ,
573     exponent-to-prefix .default:n = true ,
574     multi-part-units .choice: ,
575     multi-part-units / brackets . code:n =
576     {
577         \_siunitx_option_DEPRECATED:nn
578             { multi-part-units==brackets }
579             { separate-uncertainty-units==bracket }
580     } ,
581     multi-part-units / repeat . code:n =
582     {
583         \_siunitx_option_DEPRECATED:nn
584             { multi-part-units==repeat }
585             { separate-uncertainty-units==repeat }
586     } ,
587     multi-part-units / single . code:n =
```

```

588   {
589     \_siunitx_option_deprecated:nn
590       { multi-part-units=-single }
591       { separate-uncertainty-units=-single }
592   } ,
593   number-unit-product .code:n =
594   {
595     \_siunitx_option_deprecated:nnV
596       { number-unit-product }
597       { quantity-product }
598       \l_keys_value_tl
599   } ,
600   number-unit-separator .code:n =
601   {
602     \_siunitx_option_deprecated:nnV
603       { number-unit-separator }
604       { quantity-product }
605       \l_keys_value_tl
606   } ,
607   prefixes-as-symbols .choice: ,
608   prefixes-as-symbols / false . code:n =
609   {
610     \_siunitx_option_deprecated:nn
611       { prefixes-as-symbols=-false }
612       { prefix-mode=-extract-exponent }
613   } ,
614   prefixes-as-symbols / true . code:n =
615   {
616     \_siunitx_option_deprecated:nn
617       { prefixes-as-symbols=-true }
618       { prefix-mode=-input }
619   } ,
620   prefixes-as-symbols .default:n = true
621 }
622 
```

1.10 Preamble commands

623 (*interfaces)

\DeclareBinaryPrefix We simply drop #3.

```

624 \NewDocumentCommand \DeclareBinaryPrefix { +m m m }
625   {
626     \siunitx_declare_prefix:Nn #1 {#2}
627   }

```

(End definition for \DeclareBinaryPrefix. This function is documented on page ??.)

\DeclareSIPrePower Simply use a throw-away command for the part we do not need: this can be followed by
\DeclareSIPostPower some clean-up.

```

628 \NewDocumentCommand \DeclareSIPrePower { +m m }
629   {
630     \siunitx_declare_power:NNn #1 \_siunitx_tmp:w {#2}
631     \seq_remove_all:Nn \l_siunitx_unit_symbolic_seq { \_siunitx_tmp:w }
632   }

```

```

633 \NewDocumentCommand \DeclareSIPostPower { +m m }
634   {
635     \siunitx_declare_power:Nn \__siunitx_tmp:w #1 {#2}
636     \seq_remove_all:Nn \l_siunitx_unit_symbolic_seq { \__siunitx_tmp:w }
637   }

```

(End definition for `\DeclareSIPrePower` and `\DeclareSIPostPower`. These functions are documented on page ??.)

1.11 Document commands

`\si` A straight copy of `\unit`.

```

638 \NewDocumentCommand \si { O { } m }
639   {
640     \mode_leave_vertical:
641     \group_begin:
642       \keys_set:nn { siunitx } {#1}
643       \siunitx_unit_format:nn {#2} \l_siunitx_tmp_tl
644       \siunitx_print_unit:V \l_siunitx_tmp_tl
645     \group_end:
646   }

```

(End definition for `\si`. This function is documented on page ??.)

`\SI` Almost the same as `\qty`, but with the addition pre-unit.

```

647 \NewDocumentCommand \SI { O { } m o m }
648   {
649     \mode_leave_vertical:
650     \group_begin:
651       \keys_set:nn { siunitx } {#1}
652       \IfNoValueF {#3}
653       {
654         \siunitx_unit_format:nN {#3} \l_siunitx_tmp_tl
655         \siunitx_print_unit:V \l_siunitx_tmp_tl
656         \nobreak
657       }
658       \siunitx_quantity:nn {#2} {#4}
659     \group_end:
660   }

```

(End definition for `\SI`. This function is documented on page ??.)

`\SIlist` Straight copies.

```

661 \NewDocumentCommand \SIlist
662   { O { } > { \SplitList { ; } } m > { \TrimSpaces } m }
663   {
664     \mode_leave_vertical:
665     \group_begin:
666       \siunitx_unit_options_apply:n {#3}
667       \keys_set:nn { siunitx } {#1}
668       \siunitx_quantity_list:nn {#2} {#3}
669     \group_end:
670   }
671 \NewDocumentCommand \SIRange { O { } m m > { \TrimSpaces } m }

```

```

672   {
673     \mode_leave_vertical:
674     \group_begin:
675       \siunitx_unit_options_apply:n {#4}
676       \keys_set:nn { siunitx } {#1}
677       \siunitx_quantity_range:nnn {#2} {#3} {#4}
678     \group_end:
679   }

```

(End definition for `\SIlist` and `\SIrange`. These functions are documented on page ??.)

1.12 Symbol commands

```
680 <@=siunitx_emulation>
```

As in `siunitx-unit`, but internal in both cases as it's rather specialised.

```

\_\_siunitx_emulation non latin:n
\_\_siunitx_emulation_non_latin:nnn
681 \bool_lazy_or:nnTF
682   { \sys_if_engine_luatex_p: }
683   { \sys_if_engine_xetex_p: }
684   {
685     \cs_new:Npn \_\_siunitx_emulation_non_latin:n #1
686     { \char_generate:nn {#1} { \char_value_catcode:n {#1} } }
687   }
688   {
689     \cs_new:Npn \_\_siunitx_emulation_non_latin:n #1
690     {
691       \exp_last_unbraced:Nf \_\_siunitx_emulation_non_latin:nnnn
692       { \char_to_utfviii_bytes:n {#1} }
693     }
694     \cs_new:Npn \_\_siunitx_emulation_non_latin:nnnn #1#2#3#4
695     {
696       \exp_after:wN \exp_after:wN \exp_after:wN
697       \exp_not:N \char_generate:nn {#1} { 13 }
698       \exp_after:wN \exp_after:wN \exp_after:wN
699       \exp_not:N \char_generate:nn {#2} { 13 }
700     }
701   }

```

(End definition for `__siunitx_emulation_non_latin:n` and `__siunitx_emulation_non_latin:nnnn`.)

`\SIUnitSymbolAngstrom` The same setup as elsewhere but localised to the emulation module

```

\SIUnitSymbolArcminute
\SIUnitSymbolArcsecond
\SIUnitSymbolCelsius
\SIUnitSymbolDegree
\SIUnitSymbolMicro
\SIUnitSymbolOhm
702 \AtBeginDocument
703   {
704     \cs_new_protected:Npn \SIUnitSymbolArcminute
705     { \ensuremath { \text{\AA} } }
706     \cs_new_protected:Npn \SIUnitSymbolArcsecond
707     { \ensuremath { \text{\AA} } }
708     \ifpackageloaded { fontspec }
709     {
710       \cs_new_protected:Npx \SIUnitSymbolAngstrom
711       { \_\_siunitx_emulation_non_latin:n { "00C5 } }
712       \cs_new_protected:Npx \SIUnitSymbolDegree
713       { \_\_siunitx_emulation_non_latin:n { "00B0 } }
714       \cs_new_protected:Npx \SIUnitSymbolCelsius
715       { \_\_siunitx_emulation_non_latin:n { "00B0 } C } 
```

```

716 }
717 {
718   \cs_new_protected:Npx \SIUnitSymbolAngstrom
719   {
720     \siunitx_print_text:n
721     { \__siunitx_emulation_non_latin:n { "00C5 } }
722   }
723   \cs_new_protected:Npx \SIUnitSymbolCelsius
724   {
725     \siunitx_print_text:n
726     { \__siunitx_emulation_non_latin:n { "00B0 } } C
727   }
728   \cs_new_protected:Npx \SIUnitSymbolDegree
729   {
730     \siunitx_print_text:n
731     { \__siunitx_emulation_non_latin:n { "00B0 } }
732   }
733 }
734 \cs_new_protected:Npx \SIUnitSymbolMicro
735 {
736   \siunitx_print_text:n
737   {
738     \bool_lazy_or:nnTF
739     { \sys_if_engine_luatex_p: }
740     { \sys_if_engine_xetex_p: }
741     { \__siunitx_emulation_non_latin:n { "00B5 } }
742     { \exp_not:N \textmu }
743   }
744 }
745 \cs_new_protected:Npx \SIUnitSymbolOhm
746 {
747   \exp_not:N \ifmmode
748     \cs_if_exist:NTF \upOmega
749     { \exp_not:N \upOmega }
750     { \exp_not:N \Omega }
751   \exp_not:N \else
752     \siunitx_print_text:n
753     {
754       \bool_lazy_or:nnTF
755       { \sys_if_engine_luatex_p: }
756       { \sys_if_engine_xetex_p: }
757       { \__siunitx_emulation_non_latin:n { "03A9 } }
758       { \exp_not:N \textohm }
759     }
760   \exp_not:N \fi
761 }
762 }

```

(End definition for `\SIUnitSymbolAngstrom` and others. These functions are documented on page ??.)

`\celsius` Deprecated but should work.

```
763 \siunitx_declare_unit:Nn \celsius { \degreeCelsius }
```

(End definition for `\celsius`. This function is documented on page ??.)

Units that have been removed: to avoid issues, we mark them as deprecated.

```

764 \msg_new:nnn { siunitx } { unit-deprecated }
765   {
766     Unit-macro~#1-has-been-deprecated-in-this-release. \\ \\
767     The-BIPM-have-removed-this-unit-from-the-SI-Brochure.~
768     You-should-define-it-yourself-using-\token_to_str:N \DeclareSIUnit\ %
769     in-your-source.-The-current-definition-is\\ \\
770     \token_to_str:N \DeclareSIUnit #1 \{ #2 \}
771   }
772 \cs_gset_protected:Npn \__siunitx_emulation_tmp:w #1#2
773   {
774     \quark_if_recursion_tail_stop:N #1
775     \bool_new:c { g_siunitx_emulation_unit_warning_ \token_to_str:N #1 _bool }
776     \siunitx_declare_unit:Nx #1
777     {
778       \exp_not:N \bool_if:NF
779         \exp_not:c { g_siunitx_emulation_unit_warning_ \token_to_str:N #1 _bool }
780       {
781         \exp_not:N \bool_gset_true:N
782           \exp_not:c { g_siunitx_emulation_unit_warning_ \token_to_str:N #1 _bool }
783         \msg_warning:nnnn { siunitx } { unit-deprecated }
784           { \token_to_str:N #1 } { #2 }
785       }
786       #2
787     }
788     \__siunitx_emulation_tmp:w
789   }
790 \__siunitx_emulation_tmp:w
791   \atomicmassunit { u }
792   \bar { bar }
793   \barn { b }
794   \bohr
795   {
796     \exp_not:N \text
797       { \exp_not:N \ensuremath { a } } \char_generate:nn { '\_ } { 8 } { 0 }
798   }
799 \clight
800   {
801     \exp_not:N \text
802       { \exp_not:N \ensuremath { c } } \char_generate:nn { '\_ } { 8 } { 0 }
803   }
804 \electronmass
805   {
806     \exp_not:N \text { \exp_not:N \ensuremath { m } }
807     \char_generate:nn { '\_ } { 8 } { \exp_not:N \mathrm { e } }
808   }
809 \elementarycharge { \text { \ensuremath { e } } }
810 \hartree
811   {
812     \exp_not:N \text { \exp_not:N \ensuremath { E } }
813     \char_generate:nn { '\_ } { 8 } { \exp_not:N \mathrm { h } }
814   }
815 \knot { kn }
816 \mmHg { mmHg }
```

```

817 \nauticalmile { M }
818 \planckbar
819 { \exp_not:N \text { \exp_not:N \ensuremath { \exp_not:N \hbar } } }
820 \q_recursion_tail { }
821 \q_recursion_stop
822 \ifpackageloaded { fontspec }
823 {
824   \__siunitx_emulation_tmp:w \angstrom { \__siunitx_emulation_non_latin:n { "00C5 } }
825 }
826 {
827   \__siunitx_emulation_tmp:w \angstrom
828   { \exp_not:N \text { \__siunitx_emulation_non_latin:n { "00C5 } } }
829 }
830 \q_recursion_tail { }
831 \q_recursion_stop
832 ⟨/interfaces⟩
833 ⟨/package⟩

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

| Symbols | |
|---------------------------|--|
| \% | 1093 |
| \, | 104, <i>137, 9, 15, 21, 27, 156, 1143, 1990, 1996</i> |
| \- | 101 |
| \\" | 6, 84, 766, 769, 1105 |
| \{ | 770 |
| \} | 770 |
| _ | 8, 197, 208, 281, 358, 797, 802, 807, 813 |
| \~ | 212 |
| \u | 48, 50, 54, 56, 60, 62, 80, 114, 538, 540, 541, 542, 546, 548, 551, 557, 559, 563, 565, 568, 574, 576, 583, 585, 768, 1112 |
| A | |
| \A | 177, <u>2</u> |
| allow-quantity-breaks | 104 |
| \ampere | <i>141, 2, 3, 4, 5, 6, 7, 1025</i> |
| \ang | 6, <u>100</u> , 277, 313 |
| angle-mode | 12 |
| angle-symbol-degree | 12 |
| angle-symbol-minute | 12 |
| angle-symbol-over-decimal | 12 |
| angle-symbol-second | 12 |
| \angstrom | 824, 827 |
| \approx | 1992 |
| arc-separator | 12 |
| \arcminute | <i>142, 54, 56, 286, 353, 1090</i> |
| \arcsecond | <i>142, 59, 61, 288, 358, 1090</i> |
| \as | 177, <u>89</u> |
| \astronomicalunit | <i>142, 1077</i> |
| \AtBeginDocument | <i>5, 17, 37, 52, 59, 73, 141, 221, 222, 244, 297, 318, 702</i> |
| \atomicmassunit | 791 |
| \atto | <i>141, 90, 1034</i> |
| B | |
| \bar | 792 |
| \barn | 793 |
| \becquerel | <i>142, 1055</i> |
| \begin | 203 |
| \bel | <i>142, 69, 1077</i> |
| \bfseries | 91 |
| \binoppenalty | 146 |
| \bit | <i>183, 10</i> |
| \bohr | 794 |
| boldmath | |
| \boldmath | 92 |
| bool commands: | |
| \bool_gset_true:N | 781 |
| \bool_if:NTF | <i>10, 16, 17, 18, 32, 34, 39, 47, 50, 61, 62, 64, 71, 75, 80, 88, 91, 96, 101, 106, 108, 110, 116, 119, 121, 126, 144, 145, 149, 158, 164, 164, 182, 183, 186, 192, 213, 233, 239, 241, 243, 253, 255, 256, 265, 376, 380, 397, 407, 415, 437, 438, 447, 475, 476, 480, 493, 578, 582, 604, 624, 664, 692, 715, 755, 766, 775, 778, 853, 873, 885, 902, 922, 936, 945, 948, 996, 1006, 1283, 1479, 1653, 1659, 1675, 1710, 1883, 1904</i> |
| \bool_lazy_all:nTF | 1616 |
| \bool_lazy_all_p:n | 1094, 1112 |
| \bool_lazy_and:nnTF | <i>111, 137, 217, 268, 283, 431, 515, 592, 648, 675, 699, 887, 895, 1289, 1387, 1638</i> |
| \bool_lazy_any:nTF | 245 |
| \bool_lazy_or:nnTF | <i>10, 117, 132, 159, 171, 257, 317, 387, 389, 443, 543, 681, 738, 754, 1004, 1091, 1109, 1418, 1689, 1850, 1866, 1879</i> |
| \bool_lazy_or_p:nn | 1622 |
| \bool_new:N | <i>3, 6, 9, 10, 10, 11, 12, 18, 19, 20, 21, 22, 23, 43, 44, 76, 88, 348, 446, 561, 566, 567, 568, 569, 570, 571, 574, 662, 775, 1519, 1581, 1582</i> |
| \bool_set_false:N | <i>9, 12, 16, 21, 22, 25, 29, 29, 34, 35, 39, 40, 50, 57, 58, 63, 64, 68, 70, 74, 75, 80, 81, 82, 88, 134, 148, 155, 171, 209, 216, 256, 260, 339, 354, 355, 457, 513, 514, 520, 521, 522, 523, 527, 528, 529, 534, 537, 541, 599, 601, 651, 675, 714, 762, 797, 869, 1540, 1544, 1549, 1550</i> |
| \bool_set_true:N | <i>11, 14, 17, 24, 30, 30, 34, 35, 52, 56, 62, 63, 69, 76, 102, 141, 163, 208, 209, 234, 247, 254, 261, 332, 353, 449, 455, 515, 516, 530, 535, 536, 542, 543, 544, 548, 549, 550, 551, 602, 649, 859, 890</i> |

| | | |
|----------------------------|--|--|
| \c_false_bool | 47, 121, 387, 449, 453, 458, 466, 490, 496, 534, 549, 591, 614 | |
| \c_true_bool | 44, 118, 372, 387, 447, 463, 490, 496, 547, 618 | |
| box commands: | | |
| \box_clear:N | 509, 572 | |
| \box_new:N | 3, 170, 171, 251, 252, 484, 485 | |
| \box_use:N | 249 | |
| \box_use_drop:N | 244, 246, 432, 433, 478, 479, 532, 540, 555, 556, 611, 612, 613, 614 | |
| \box_wd:N .. | 228, 229, 263, 272, 275, 276, 281, 282, 292, 293, 407, 449, 453, 467, 507, 514, 515, 518, 526, 570, 575, 602, 627, 638, 639, 650, 654, 655, 668, 669, 679, 687, 689, 707, 708, 729, 740, 759, 761, 771, 783 | |
| bracket-ambiguous-numbers | 40 | |
| bracket-negative-numbers | 40 | |
| bracket-unit-denominator | 143 | |
| \byte | 183, 10 | |
| C | | |
| \cancel | 137, 143, 149, 107 | |
| \candela | 141, 1025 | |
| \cdot | 8, 33, 279 | |
| \celsius | 763 | |
| \centi | 141, 65, 1034 | |
| char commands: | | |
| \char_generate:nn | 8, 15, 27, 29, 164, 175, 177, 197, 208, 281, 358, 686, 697, 699, 797, 802, 807, 813, 1009, 1020, 1022 | |
| \char_set_active_eq:NN | 222, 224, 226, 413, 457 | |
| \char_set_active_eq:nN | 39 | |
| \char_set_catcode_active:N | 101 | |
| \char_set_catcode_active:n | 212 | |
| \char_set_mathcode:nn | 414, 458 | |
| \char_to_utfviii_bytes:n | 21, 170, 692, 1015 | |
| \char_value_catcode:n | 15, 164, 686, 1009 | |
| \clight | 799 | |
| clist commands: | | |
| \clist_map_break: | 119 | |
| \clist_map_function:nN | 34, 39 | |
| \clist_map_inline:nn | 19, 28, 95, 97, 107, 123, 165, 174, 198, 253, 492, 604 | |
| \cm | 177, 60 | |
| \color | 38, 262, 1641 | |
| color | 92 | |
| \complexnum | 181 | |
| \complexqty | 181 | |
| compound-exponents | 21 | |
| compound-final-separator | 21 | |
| compound-pair-separator | 21 | |
| compound-separator | 21 | |
| compound-separator-mode | 21 | |
| compound-units | 21 | |
| \coulomb | 142, 1055 | |
| \cr | 117, 29 | |
| cs commands: | | |
| \cs:w | 117, 182, 458, 715, 1020 | |
| \cs_end: | 117, 182, 459, 718, 1023 | |
| \cs_generate_variant:Nn | 2, 3, 3, 4, 5, 5, 6, 21, 27, 61, 62, 65, 72, 87, 114, 123, 144, 151, 181, 192, 193, 199, 205, 207, 250, 302, 368, 373, 380, 497, 503, 789, 844, 872, 919, 1033, 1195, 1198, 1209, 1707, 1825, 1840 | |
| \cs_gset_protected:Npn | 772 | |
| \cs_if_eq:NNTF | 347 | |
| \cs_if_exist:NTF | 111, 113, 116, 134, 223, 250, 333, 748 | |
| \cs_if_free:NTF | 7, 55 | |
| \cs_new:Npn | 14, 18, 23, 32, 67, 111, 121, 140, 142, 163, 167, 168, 172, 209, 210, 229, 240, 246, 247, 255, 344, 346, 361, 363, 365, 369, 374, 381, 383, 384, 386, 387, 389, 466, 468, 471, 474, 477, 480, 483, 559, 617, 671, 685, 689, 690, 694, 708, 726, 727, 732, 739, 741, 747, 767, 779, 790, 796, 802, 808, 820, 827, 845, 867, 873, 874, 881, 901, 906, 920, 930, 943, 951, 964, 978, 984, 989, 1002, 1008, 1012, 1014, 1017, 1026, 1028, 1034, 1043, 1059, 1073, 1084, 1105, 1123, 1153, 1180, 1187, 1194, 1196, 1199, 1210, 1220, 1227, 1234, 1235, 1236, 1243, 1245, 1251, 1256, 1270, 1278, 1287, 1298, 1313, 1321, 1339, 1355, 1356, 1374, 1383, 1385, 1407, 1416, 1433, 1446, 1452, 1461, 1485, 1495, 1497, 1502, 1507, 1509, 1584, 1586, 1588, 1590, 1592, 1597, 1602, 1614, 1629, 1636, 1643, 1649, 1667, 1673, 1679, 1687, 1694, 1708, 1719, 1728, 1730, 1732, 1734, 1740, 1750, 1755, 1775, 1784, 1786, 1805, 1826, 1841, 1846, 1848, 1857, 1863, 1877, 1894, 1900, 1910, 1945, 1951, 1956 | |
| \cs_new:Npx | 245, 391, 400 | |
| \cs_new_eq:NN | 226, 253, 254, 765 | |

| | | |
|---|---|----------|
| \cs_new_protected:Npn | 7 | |
| 11, 14, 14, 16, 22, 23, 24, 25, 27, | | |
| 28, 37, 37, 39, 40, 40, 45, 45, 49, | | |
| 50, 55, 59, 60, 60, 61, 62, 63, 64, | | |
| 66, 67, 68, 70, 70, 73, 77, 78, 80, | | |
| 85, 86, 89, 89, 91, 93, 93, 94, 94, | | |
| 98, 99, 101, 101, 105, 108, 110, | | |
| 115, 124, 128, 130, 131, 131, 132, | | |
| 133, 133, 138, 139, 139, 140, 144, | | |
| 144, 145, 146, 147, 152, 153, 153, | | |
| 156, 159, 160, 162, 162, 166, 166, | | |
| 168, 169, 172, 172, 176, 176, 178, | | |
| 180, 182, 182, 185, 186, 187, 193, | | |
| 194, 204, 205, 207, 207, 208, 209, | | |
| 209, 210, 211, 211, 213, 221, 228, | | |
| 235, 236, 241, 243, 245, 246, 248, | | |
| 248, 248, 250, 254, 258, 258, 259, | | |
| 260, 260, 261, 265, 267, 267, 270, | | |
| 272, 272, 275, 281, 289, 293, 293, | | |
| 294, 297, 299, 301, 303, 307, 313, | | |
| 315, 318, 323, 323, 329, 329, 334, | | |
| 336, 337, 337, 337, 338, 339, 343, | | |
| 345, 347, 350, 350, 363, 363, 368, | | |
| 371, 371, 374, 376, 377, 383, 388, | | |
| 390, 398, 400, 402, 406, 415, 417, | | |
| 420, 422, 425, 426, 429, 429, 436, | | |
| 441, 443, 445, 451, 451, 451, 456, 459, | | |
| 461, 462, 464, 468, 471, 471, 478, | | |
| 480, 482, 483, 484, 490, 499, 501, | | |
| 504, 505, 510, 511, 518, 525, 526, | | |
| 537, 542, 553, 566, 566, 575, 581, | | |
| 594, 596, 603, 610, 618, 619, 625, | | |
| 644, 650, 666, 666, 685, 697, 700, | | |
| 700, 704, 706, 710, 711, 712, 712, | | |
| 720, 724, 729, 734, 734, 745, 753, | | |
| 764, 770, 787, 792, 802, 804, 813, | | |
| 824, 825, 835, 847, 861, 866, 878, | | |
| 883, 909, 920, 932, 941, 953, 959, | | |
| 969, 978, 987, 994, 1004, 1016, 1477 | | |
| \cs_new_protected:Npx | | |
| 102, 191, 191, 199, 206, | | |
| 213, 215, 220, 266, 280, 308, 351, | | |
| 710, 712, 714, 718, 723, 728, 734, 745 | | |
| \cs_set:Npn | 30, 34 | |
| \cs_set_eq:NN | | |
| 135, 147, 180, 326, 332, 341 | | |
| \cs_set_protected:Npn | | |
| 29, 56, 77, 85, 225, | | |
| 229, 229, 248, 255, 277, 301, 325, 450 | | |
| \cs_set_protected:Npx | 69, 198 | |
| \cs_to_str:N | 182, 273, 327, 1093 | |
| \cs_undefine:N | 47, 48, 67, 225, 252 | |
| \cubed | 143, 1094 | |
| \cubic | 142, 1094 | |
| | | D |
| \dalton | 142, 1077 | |
| \day | 142, 1077 | |
| \dB | 179, 69 | |
| \deca | 141 | |
| \deci | 141, 66, 69, 1034, 1079 | |
| \decibel | 142, 1077 | |
| \DeclareBinaryPrefix | 624 | |
| \DeclareCurrentRelease | 5, 8 | |
| \DeclareExpandableDocumentCommand . | 272 | |
| \DeclareRelease | 4, 6, 7 | |
| \DeclareSIPostPower | 628 | |
| \DeclareSIPower | 62 | |
| \DeclareSIPrefix | 62 | |
| \DeclareSIPrePower | 628 | |
| \DeclareSIQualifier | 62 | |
| \DeclareSIUnit | 62, 768, 770 | |
| \DeclareTranslation | 40, 41, 42, 43 | |
| \def | 333 | |
| \degree | 109, 142, 64, 69, 180, 285, 349, 1090 | |
| \degreeCelsius | 142, 86, 93, 763, 1055 | |
| \deka | 141, 1044 | |
| dim commands: | | |
| \dim_add:Nn | 636, 685, 780 | |
| \dim_compare:nNnTF | | |
| 228, 271, 507, 513, 570 | | |
| \dim_compare_p:nNn | 650 | |
| \dim_new:N | 4, 4, 486, 487 | |
| \dim_set:Nn | | |
| 263, 575, 678, 705, 729, 740, 768 | | |
| \dm | 177, 60 | |
| drop-exponent | 40 | |
| drop-uncertainty | 40 | |
| drop-zero-decimal | 40 | |
| | | E |
| \edef | 334 | |
| \electronmass | 804 | |
| \electronvolt | | |
| 142, 52, 53, 54, 55, 56, 57, 1077 | | |
| \elementarycharge | 809 | |
| \else | 48, 50, 54, 56, 60, 62, 114, | |
| 540, 542, 546, 548, 551, 557, 559, | | |
| 563, 565, 568, 574, 576, 583, 585, 751 | | |
| else commands: | | |
| \else: | 329 | |
| \end | 55, 84, 200 | |
| \endinput | 21 | |
| \ensuremath | 39, 91, | |
| 24, 53, 57, 62, 146, 178, 230, 257, | | |
| 270, 274, 355, 373, 405, 447, 451, | | |
| 705, 707, 797, 802, 806, 809, 812, 819 | | |
| \ERROR | 56 | |
| \eV | 178, 42 | |

evaluate-expression 41
\exa 141, 1044
\exbi 183, 2
 exp commands:
 \exp_after:wN
 26, 28, 68, 80, 104, 115, 135, 140,
 141, 144, 148, 149, 153, 168, 170,
 174, 176, 181, 189, 205, 231, 235,
 245, 259, 328, 330, 339, 358, 371,
 372, 382, 440, 459, 460, 461, 463,
 482, 507, 538, 585, 595, 598, 669,
 691, 696, 698, 703, 717, 719, 723,
 731, 962, 999, 1009, 1019, 1021,
 1022, 1265, 1401, 1482, 1595, 1953
 \exp_args:Nc 129, 272
 \exp_args:Ne 48, 63, 1343, 1505
 \exp_args:Nf 402,
 728, 743, 1068, 1079, 1336, 1448, 1454
 \exp_args:Nff 369
 \exp_args:NNc 232
 \exp_args:Nnno 1426
 \exp_args:NNNV
 25, 130, 239, 335, 590, 677, 799, 957
 \exp_args:NNnx 228
 \exp_args:NNV 16, 112, 342
 \exp_args:NnV 253
 \exp_args:NV
 73, 114, 211, 230, 316, 1223, 1500
 \exp_args:Nv 70
 \exp_args:Nx 145, 299, 580
 \exp_args:Nxx 98
 \exp_last_unbraced:Nf
 20, 169, 691, 1014, 1161, 1435
 \exp_not:N 27, 29, 37, 57, 62,
 71, 74, 76, 80, 82, 84, 84, 88, 95, 98,
 105, 110, 112, 113, 114, 115, 121,
 123, 130, 136, 147, 148, 175, 177,
 193, 194, 195, 195, 196, 198, 199,
 200, 201, 201, 202, 202, 203, 209,
 217, 217, 218, 218, 220, 222, 223,
 224, 225, 226, 227, 269, 270, 271,
 272, 273, 276, 277, 278, 278, 279,
 280, 281, 282, 282, 283, 284, 284,
 285, 285, 287, 287, 288, 289, 289,
 290, 310, 311, 312, 316, 317, 318,
 321, 336, 337, 338, 354, 355, 357,
 359, 393, 396, 403, 404, 595, 697,
 699, 742, 747, 749, 750, 751, 758,
 760, 778, 779, 781, 782, 796, 797,
 801, 802, 806, 807, 812, 813, 819,
 828, 1020, 1022, 1641, 1700, 1743, 1884
 \exp_not:n 110,
 111, 112, 113, 114, 114, 130, 143,
 161, 169, 201, 215, 216, 221, 228,
 242, 274, 279, 280, 287, 288, 288,
 289, 290, 291, 295, 316, 317, 318,
 324, 328, 330, 347, 347, 348, 354,
 356, 357, 357, 361, 362, 365, 366,
 367, 370, 392, 394, 395, 396, 397,
 397, 402, 435, 436, 437, 439, 467,
 470, 473, 474, 476, 479, 481, 482,
 482, 485, 489, 490, 491, 530, 562,
 564, 589, 610, 679, 682, 694, 695,
 696, 698, 703, 728, 734, 737, 740,
 741, 749, 749, 750, 757, 775, 799,
 818, 819, 820, 821, 830, 830, 831,
 832, 835, 842, 843, 851, 855, 856,
 873, 883, 903, 910, 913, 914, 915,
 915, 916, 916, 924, 926, 927, 934,
 938, 939, 940, 955, 963, 964, 965,
 966, 966, 969, 972, 973, 974, 975,
 976, 982, 983, 991, 998, 999, 1000,
 1003, 1015, 1027, 1293, 1295, 1304,
 1307, 1311, 1345, 1353, 1355, 1391,
 1396, 1397, 1398, 1405, 1414, 1421,
 1425, 1428, 1430, 1487, 1489, 1492,
 1493, 1504, 1512, 1513, 1631, 1633,
 1641, 1646, 1647, 1665, 1671, 1676,
 1677, 1682, 1684, 1696, 1702, 1704,
 1714, 1717, 1736, 1745, 1746, 1759,
 1760, 1764, 1768, 1785, 1790, 1792,
 1798, 1799, 1801, 1847, 1865, 1875,
 1886, 1887, 1889, 1890, 1896, 1897
 \expandafter 234
 \ExplFileVersion 1, 12
 exponent-base 41
 exponent-mode 41
 exponent-product 41
 expression 41
 extract-mass-in-kilograms 144

F

\F 179, 70
\fam 172, 173, 187
\familydefault 91, 240
\farad 142, 70, 71, 72, 73, 74, 1055
\femto 141, 15, 35, 71, 91, 1034
\fF 179, 70
\fg 177, 35, 333
\fi 48, 50, 54, 56, 60, 62, 123,
 540, 542, 546, 548, 551, 557, 559,
 563, 565, 568, 574, 576, 583, 585, 760
 fi commands:
 \fi: 28, 34, 331
 file commands:
 \file_if_exist:nTF 37
 fill-angle-degrees 12
 fill-angle-minutes 12

| | |
|-------------------------|---|
| fill-angle-seconds | 13 |
| fixed-exponent | 41 |
| \fmol | 178, 14 |
| \fmtversion | 42 |
| \fontfamily | 91, 240 |
| \fontseries | 91, 242 |
| \fontshape | 91, 244 |
| \fontsize | 367 |
| forbid-literal-units | 144 |
| fp commands: | |
| \fp_add:Nn | 787 |
| \fp_compare:nNnTF | 474, 588, 590, 638, 658 |
| \fp_eval:n | 48, 64, 73, 74, 76, 122, 473, 637, 1505 |
| \fp_new:N | 4, 4, 573, 575, 576 |
| \fp_set:Nn | 135, 136, 143, 149, 150, 157, 165, 172, 173, 202, 249, 622, 656, 684 |
| \fp_use:N | 203, 662 |
| \fp_zero:N | 135, 142, 156, 164, 182, 586 |
| \c_one_fp | 136, 143, 150, 590, 658 |
| \l_tmpa_fp | 138 |
| \c_zero_fp | 588, 638 |
| \frac | 137, 1142 |
| fraction-command | 144 |
| free-standing-units | 184 |
| \fs | 177, 89 |
| G | |
| \g | 177, 35 |
| \ge | 38, 98, 1992 |
| \geq | 1992 |
| \GetTranslation | 49, 55, 61 |
| \GeV | 178, 42 |
| \gg | 38, 97, 1992 |
| \GHz | 177, 8 |
| \gibi | 183, 2 |
| \giga | 141, 12, 47, 56, 85, 1044 |
| \GPa | 179, 82 |
| \gram | 141, 156, 35, 36, 37, 38, 39, 40, 41, 429, 1025, 1033 |
| \gray | 142, 1055 |
| group commands: | |
| \group_begin: | 140, 13, 16, 26, 35, 42, 74, 81, 87, 93, 94, 100, 103, 111, 117, 120, 131, 140, 149, 159, 167, 176, 178, 184, 192, 193, 201, 211, 215, 215, 252, 260, 303, 331, 339, 353, 417, 424, 466, 473, 513, 520, 577, 641, 650, 665, 674, 674, 796, 955, 1915 |
| \c_group_begin_token | 41, 155, 393 |
| \group_end: | 140, 16, 25, 44, 48, 59, 87, 89, 91, 98, 105, 106, 107, 112, 115, 125, 130, 135, 138, 143, 153, 162, 171, 179, 187, 196, 203, 205, 206, 219, 239, 244, 264, 279, 307, 335, 342, 361, 420, 427, 469, 476, 516, 523, 590, 645, 659, 669, 677, 678, 799, 957, 1921, 1925 |
| group-digits | 41 |
| group-minimum-digits | 41 |
| group-separator | 41 |
| \GW | 178, 42 |
| H | |
| \H | 75, 334, 337, 338 |
| \hartree | 810 |
| \hbar | 819 |
| hbox commands: | |
| \hbox_overlap_right:n | 243, 245 |
| \hbox_set:Nn | 214, 219, 269, 404, 446, 451, 506, 512, 545, 547, 568, 569, 600, 680, 747, 775 |
| \hbox_set:Nw | 409, 421 |
| \hbox_set_end: | 420, 428, 465, 475 |
| \hbox_set_to_wd:Nnn | 240, 264, 279, 290, 406, 448, 517, 525, 601, 626, 652, 666, 693, 757 |
| \hbox_set_to_wd:Nnw | 452, 466 |
| \hbox_to_wd:nn | 214 |
| \hbox_unpack:N | 285, 297, 521, 528, 658, 673, 682, 696, 764, 766, 777, 778 |
| \hbox_unpack_drop:N | 268 |
| \hectare | 142, 1077 |
| \hecto | 141, 27, 31, 1044 |
| \henry | 142, 75, 76, 77, 1055 |
| \hertz | 142, 8, 9, 10, 11, 12, 13, 1055 |
| \highlight | 143, 149, 107 |
| \hL | 178, 27 |
| \hl | 178, 186, 27, 47 |
| \hour | 142, 58, 1077 |
| \Hz | 177, 8 |
| I | |
| if commands: | |
| \if_false: | 28, 34 |
| \if_meaning:w | 327 |
| \IfFormatAtLeastTF | 42, 59 |
| \ifmmode | 48, 50, 54, 56, 60, 62, 110, 540, 542, 546, 548, 551, 557, 559, 563, 565, 568, 574, 576, 583, 585, 747 |
| \IfNoValueF | 652 |
| \IfNoValueTF | 76, 76 |
| \ignorespaces | 114, 37, 204, 390 |
| input-close-uncertainty | 41 |

| | | |
|-------------------------|---|--|
| input-comparators | 41 | |
| input-decimal-markers | 41 | |
| input-digits | 41 | |
| input-exponent-markers | 41 | |
| input-open-uncertainty | 41 | |
| input-signs | 41 | |
| input-uncertainty-signs | 41 | |
| int commands: | | |
| \int_abs:n | 190, 836, 839, 879, 1819 | |
| \int_case:nnTF | 305, 341, 371, 889 | |
| \int_compare:nNnTF | 175, 187, 197, 359, 378, 598, 606, 750, 781, 784, 798, 829, 876, 887, 980, 1066, 1077, 1138, 1141, 1172, 1212, 1230, 1263, 1274, 1302, 1317, 1325, 1346, 1358, 1712, 1807, 1830 | |
| \int_compare_p:nNn | 113, 172, 173, 1092, 1110, 1420, 1852 | |
| \int_do_while:nNnn | 596 | |
| \int_eval:n | 182, 393, 396, 423, 455, 495, 729, 744, 795, 813, 823, 1069, 1080, 1148, 1176, 1328, 1337, 1368, 1378, 1439, 1449, 1472, 1724, 1794, 1810, 1834, 1860 | |
| \int_if_odd_p:n | 1097, 1115 | |
| \int_incr:N | 428, 603 | |
| \int_mod:nn | 889, 896, 1724 | |
| \int_new:N | 5, 11, 349, 580 | |
| \int_set:Nn | 329, 379 | |
| \int_set_eq:NN | 583 | |
| \int_step_inline:nn | 359, 652, 668 | |
| \int_step_inline:nnn | 38 | |
| \int_use:N | 381, 386, 409, 413, 432, 436, 441, 613, 737, 778, 783 | |
| \int_zero:N | 356, 587 | |
| inter-unit-product | 144 | |
| J | | |
| \J | 178, 42 | |
| \joule | 142, 48, 49, 50, 51, 1055 | |
| K | | |
| \K | 177, 68 | |
| \kA | 177, 2 | |
| \katal | 142, 1055 | |
| \kelvin | 141, 68, 1025 | |
| \keV | 178, 42 | |
| keys commands: | | |
| \l_keys_choice_tl | 18, 21, 45, 307, 321, 407, 413, 452, 462, 505, 509, 557, 640, 656, 1577 | |
| \keys_define:nn | 3, 4, 6, 9, 10, 12, 24, 28, 29, 36, 38, 46, 48, 72, 93, 104, 122, 172, 196, 198, 216, 218, 238, | |
| L | | |
| \L | 178, 27 | |
| \l | 178, 27 | |
| \le | 38, 96, 1992 | |
| \leq | 1992 | |
| list-exponents | 21 | |
| list-final-separator | 21 | |
| list-pair-separator | 21 | |
| list-separator | 21 | |
| list-units | 21 | |
| \liter | 142, 31, 32, 33, 34, 1077 | |
| \litre | 142, 27, 28, 29, 30, 1077 | |
| \ll | 38, 95, 1992 | |
| locale | 36 | |
| \LRE | 306 | |
| \lumen | 142, 1055 | |
| \lux | 142, 1055 | |
| M | | |
| \m | 177, 60 | |
| \mA | 177, 2 | |
| \mathchoice | 137, 171, 962 | |

| | | |
|---|---|---------|
| \mathord | 270, 270, 405, | 13, |
| 469, 1646, 1671, 1676, 1700, 1743, 1884 | | |
| \mathrm | 91, 137, 37, 84, 175, 807, 813, 1151 | |
| \mathsf | 98, 154, 165 | |
| \mathtt | 98, 155, 165 | |
| \mathversion | 91–93, 139 | |
| \mbox | 91, 137, 365, 376, 377 | |
| \mdseries | 92 | |
| \mebi | 183, 2 | 178, 21 |
| \mega | 141, 11, 46, 55, 81, 84, 88, 1044 | 178, 42 |
| \MessageBreak | 18 | 178, 42 |
| \meter | 141, 173, 1025 | |
| \metre | 141, 142, 155, 173, 60, 61, 62, 63, 64, 65, 66, 67, 1025 | 178, 78 |
| \MeV | 178, 42 | 177, 2 |
| \meV | 178, 42 | |
| \mg | 177, 35 | |
| \mH | 75 | 817 |
| \MHz | 177, 8 | |
| \mHz | 177, 8 | |
| \micro | 141, 5, 18, 24, 30, 34, 38, 43, 49, 63, 74, 77, 94, 126, 128, 1034 | 178, 42 |
| \milli | 141, 6, 9, 19, 25, 29, 33, 39, 44, 50, 53, 64, 76, 79, 86, 95, 1034 | 178, 42 |
| minimum-decimal-digits | 42 | |
| minimum-integer-digits | 42 | |
| \minute | 142, 1077 | |
| \mJ | 178, 42 | |
| \mL | 178, 27 | |
| \ml | 178, 27 | |
| \mm | 177, 60 | |
| \mmHg | 816 | |
| \mmol | 178, 14 | |
| \MN | 178, 78 | |
| \mN | 178, 78 | |
| mode | 92 | |
| mode commands: | | |
| \mode_if_math:TF | 82, 135, 207 | 178, 21 |
| \mode_leave_vertical: | 73, 93, 102, 110, 119, 130, 139, 148, 158, 166, 175, 183, 191, 200, 640, 649, 664, 673 | 178, 21 |
| \Mohm | 179, 86 | |
| \mohm | 179, 86 | |
| \mol | 178, 14 | |
| \mole | 141, 14, 15, 16, 17, 18, 19, 20, 1025 | |
| \mp | 38, 93, 273, 274, 1998 | |
| \MPa | 179, 82 | |
| \ms | 177, 89 | |
| msg commands: | | |
| \msg_error:nn | 451 | P |
| \msg_error:nnn | | |
| 31, 160, 193, 497, 630, 645 | 179, 82 | |
| \msg_error:nnnn | 369, 402, 416 | 177, 2 |
| 18, 234, 404, 421, 438, 445, 453, 536 | | |
| \msg_info:nnnn | 18, 234, 404, 421, 438, 445, 453, 536 | 177, 2 |
| \msg_new:nnn | 4, 9, 35, 82, 242, 764 | |
| \msg_new:nnnn | 25, 1096, 1102, 1108, 1114, 1120, 1126, 1132, 1969 | |
| \msg_warning:nn | 87 | |
| \msg_warning:nnn | 24, 31, 226, 253 | |
| \msg_warning:nnnn | 783 | |
| \mV | 178, 21 | |
| \MW | 178, 42 | |
| \mW | 178, 42 | |
| N | | |
| \N | 178, 78 | |
| \nA | 177, 2 | |
| \nano | 141, 4, 17, 23, 37, 62, 73, 93, 1034 | |
| \nauticalmile | 817 | |
| negative-color | 42 | |
| \neper | 142, 1077 | |
| \newcolumntype | 228, 255 | |
| \NewDocumentCommand | 62, 66, 70, 74, 91, 100, 108, 117, 127, 137, 145, 155, 164, 173, 181, 189, 198, 208, 624, 628, 633, 638, 647, 661, 671 | |
| \newton | 142, 78, 79, 80, 81, 1066 | |
| \nF | 179, 70 | |
| \ng | 177, 35 | |
| \nm | 177, 60 | |
| \nmol | 178, 14 | |
| \nobreak | 147, 194, 277, 656 | |
| \ns | 177, 89 | |
| \num | 135, 100, 278, 313 | |
| number-angle-product | 13 | |
| number-color | 92 | |
| number-mode | 92 | |
| \numlist | 127, 280, 314 | |
| \numproduct | 127, 294 | |
| \numrange | 173, 296, 315 | |
| \nV | 178, 21 | |
| O | | |
| \of | 143, 113 | |
| \ohm | 142, 86, 87, 88, 106, 108, 148, 1066 | |
| \Omegamega | 113, 750 | |
| output-close-uncertainty | 42 | |
| output-decimal-marker | 42 | |
| output-open-uncertainty | 42 | |
| \over | 145 | |
| overwrite-commands | 184 | |
| P | | |
| \Pa | 179, 82 | |
| \pA | 177, 2 | |
| \PackageError | 15 | |

| | |
|--------------------------------------|--|
| parse-numbers | 42 |
| parse-units | 144 |
| \pascal | 142, 82, 83, 84, 85, 1066 |
| \pdfstringdefDisableCommands | 145, 322, 330 |
| \pebi | 183, 2 |
| peek commands: | |
| \peek_after:Nw | 334 |
| \peek_catcode_ignore_spaces:NTF | 41, 155, 393 |
| \l_peek_token | 327 |
| \penalty | 146 |
| \per | 143–145, 149, 156, 158, 159, 161, 104, 442, 450, 456, 1109, 1112 |
| per-mode | 144 |
| per-symbol | 144 |
| \percent | 142, 1093 |
| \peta | 141, 1044 |
| \pF | 179, 70 |
| \pg | 177, 35 |
| \pico | 141, 3, 16, 22, 36, 61, 72, 92, 1034 |
| \planckbar | 818 |
| \pm | 38, 146, 177, 60, 94, 271, 1791, 1998, 1999 |
| \pmol | 178, 14 |
| \power | 143 |
| prefix-mode | 104 |
| prg commands: | |
| \prg_new_conditional:Npnn | 1261, 1929 |
| \prg_new_protected_conditional:Npnn | 11, 33, 1912 |
| \prg_replicate:nn | 190, 348, 349, 361, 376, 611, 680, 703, 836, 861, 982, 1284, 1293, 1391, 1457, 1490, 1819 |
| \prg_return_false: | 19, 49, 1268, 1276, 1922, 1947 |
| \prg_return_true: | 18, 45, 1273, 1926, 1964 |
| print-implicit-plus | 42 |
| print-unity-mantissa | 42 |
| print-zero-exponent | 42 |
| \ProcessKeysOptions | 56 |
| product-exponents | 21 |
| product-mode | 21 |
| product-phrase | 21 |
| product-symbol | 21 |
| prop commands: | |
| \prop_clear:N | 352 |
| \prop_count:N | 652 |
| \prop_get:NnN | 629 |
| \prop_get:NnNTF | 467, 614, 620, 624, 626, 641, 654, 681, 772, 784 |
| \prop_if_empty:NTF | 188 |
| \prop_if_in:NnTF | 366, 410, 462, 496, 670, 672, 779 |
| \prop_if_in_p:Nn | 390 |
| \prop_new:N | 62, 63, 347 |
| \prop_put:Nnn | 58, 59, 373, 480, 485, 643, 661, 679 |
| \prop_remove:N | 659 |
| \prop_remove:Nn | 464, 476, 639 |
| propagate-math-font | 92 |
| \protect | 295, 300 |
| \providecommand | 4, 5, 42 |
| \ProvideDocumentCommand | 71 |
| \ProvidesExplPackage | 23 |
| \ps | 177, 89 |
| \pV | 178, 21 |
| Q | |
| \qty | 201, 80, 276, 313 |
| \qtylist | 127, 287, 314 |
| \qtyproduct | 127, 295 |
| \qtyrange | 127, 298, 315 |
| qualifier-mode | 144 |
| qualifier-phrase | 144 |
| quantity-product | 104 |
| quark commands: | |
| \q_mark | 379, 380, 387, 388, 595, 620, 642, 645, 698, 701, 710, 713, 718, 721, 723, 725, 732, 735 |
| \q_nil | 52, 67, 95, 96, 99, 119, 130, 134, 139, 140, 145, 169, 205, 256, 260, 273, 288, 384, 385, 387, 439, 444, 536, 543, 560, 594, 596, 620, 622, 645, 701, 713, 721, 722, 725, 726, 735, 1729, 1731, 1733, 1753, 1813, 1841 |
| \quark_if_nil:NTF | 1737, 1747, 1757, 1761, 1765, 1828 |
| \quark_if_nil:nTF | 296 |
| \quark_if_recursion_tail_stop:N | 87, 168, 291, 339, 627, 774, 1958 |
| \quark_if_recursion_tail_stop:n | 250, 262, 303, 310, 402 |
| \quark_if_recursion_tail_stop_-do:Nn | 180, 231, 282, 331, 378, 400, 484, 528, 539, 1036, 1045, 1061, 1075, 1086, 1107, 1125, 1155, 1229, 1258, 1272, 1315, 1323, 1947 |
| \q_recursion_stop | 83, 149, 165, 225, 237, 241, 258, 270, 273, 278, 287, 326, 348, 374, 382, 397, 485, 500, 529, 540, 604, 623, 821, 831, 1031, 1039, 1050, 1054, 1064, 1089, 1135, 1181, 1188, 1225, 1254, 1266, 1306, 1943, 1954 |

| | |
|--|--------------------------------------|
| \q_recursion_tail | 311 |
| 82, 149, 165, 225, 237, 241, | 300 |
| 258, 270, 285, 326, 374, 397, 604, | 323 |
| 623, 820, 830, 1031, 1039, 1050, | 91 |
| 1054, 1064, 1089, 1135, 1181, 1188, | 333 |
| 1225, 1254, 1266, 1306, 1942, 1954 | 340 |
| \q_stop | 5, 21, 22 |
| 68, 96, 97, 99, 99, 104, | 28 |
| 111, 136, 140, 141, 142, 142, 145, | 29, 75, 127, 147, 174, 178 |
| 183, 185, 187, 189, 205, 246, 248, | 631, 636 |
| 259, 260, 263, 265, 273, 281, 289, | series-version-mapping |
| 302, 307, 345, 346, 359, 363, 381, | 93 |
| 382, 385, 386, 387, 387, 388, 389, | \seriesdefault |
| 441, 444, 508, 510, 539, 543, 599, | 91, 242 |
| 620, 622, 642, 645, 698, 701, 704, | \sfdefault |
| 708, 710, 713, 718, 720, 722, 723, | 154 |
| 726, 727, 732, 732, 734, 735, 755, | \shadedefault |
| 767, 772, 782, 790, 794, 800, 802, | 91, 244 |
| 818, 820, 914, 927, 930, 938, 1508, 1509 | \SI |
| | 301, 316, 647 |
| | \si |
| | 300, 316, 638 |
| | \siemens |
| | 142, 1066 |
| | \sievert |
| | 142, 1066 |
| | \SIlist |
| | 302, 316, 661 |
| | \sim |
| | 1992 |
| | \SIrange |
| | 309, 316, 661 |
| | \sisetup |
| | 208 |
| | \SIUnitSymbolAngstrom |
| | 702 |
| | \SIUnitSymbolArcminute |
| | 702 |
| | \SIUnitSymbolArcsecond |
| | 702 |
| | \SIUnitSymbolCelsius |
| | 702 |
| | \SIUnitSymbolDegree |
| | 702 |
| | \SIUnitSymbolMicro |
| | 702 |
| | \SIUnitSymbolOhm |
| | 702 |
| | siunitx commands: |
| | \siunitx_angle:n |
| | 12, 45, 213 |
| | \siunitx_angle:nnn .. |
| | 12, 45, 216, 217 |
| | \l_siunitx_bracket_ambiguous_- |
| | bool |
| | 40 |
| | \siunitx_cell_begin:w |
| | 114, 7, 203, 265 |
| | \siunitx_cell_end: |
| | 114, 7, 58, 87, 205, 267 |
| | \siunitx_command_create: . . . |
| | 184, 37 |
| | \siunitx_complex_number:n . . . |
| | 186 |
| | \siunitx_complex_quantity:nn .. |
| | 195 |
| | \siunitx_compound_number:n . . . |
| | 20, 85, 419, 468, 515 |
| | \siunitx_compound_quantity:nn .. |
| | 20, 250, 426, 475, 522 |
| | \siunitx_declare_power:NNn |
| | 139, 40, 64, 630, 635, 1094, 1095 |
| | \siunitx_declare_prefix:Nn |
| | 139, 2, 3, 4, 5, 6, 7, 8, 9, 49, 626 |
| | \siunitx_declare_prefix:Nnn |
| | 139, 49, 68, 128, 1034, 1035, 1036, |
| | 1037, 1038, 1039, 1040, 1041, 1042, |
| | 1043, 1044, 1045, 1046, 1047, 1048, |
| | 1049, 1050, 1051, 1052, 1053, 1054 |

```

\siunitx_declare_qualifier:Nn . . .
    ..... 139, 64, 72
\siunitx_declare_unit:Nn . 139,
    2, 3, 4, 5, 6, 7, 8, 9, 10, 10, 11, 11,
    12, 13, 14, 15, 16, 17, 18, 19, 20,
    21, 22, 23, 24, 25, 26, 27, 28, 29,
    30, 31, 32, 33, 34, 35, 36, 37, 38,
    39, 40, 41, 42, 43, 44, 45, 46, 47,
    48, 49, 50, 51, 52, 53, 54, 55, 56,
    56, 57, 60, 61, 61, 62, 63, 64, 65,
    66, 67, 68, 69, 70, 70, 71, 72, 73,
    74, 75, 76, 77, 77, 78, 79, 80, 81, 82,
    83, 84, 85, 86, 87, 88, 89, 90, 91, 92,
    93, 93, 94, 95, 108, 148, 763, 776,
    1025, 1026, 1027, 1028, 1029, 1030,
    1031, 1032, 1033, 1055, 1056, 1057,
    1058, 1059, 1060, 1061, 1062, 1063,
    1064, 1065, 1066, 1067, 1068, 1069,
    1070, 1071, 1072, 1073, 1074, 1075,
    1076, 1077, 1078, 1079, 1080, 1081,
    1082, 1083, 1084, 1085, 1086, 1087,
    1088, 1089, 1090, 1091, 1092, 1093
\siunitx_declare_unit:Nnn . . .
    ..... 139, 140, 58, 69, 70, 78, 180
\siunitx_format_number:nN . . .
    12
\siunitx_if_number:nTF . . .
    40, 1912
\siunitx_if_number_p:n . . .
    40
\siunitx_if_number_token:NTF . . .
    ..... 40, 171, 1929
\siunitx_if_number_token_p:N . 1929
\l_siunitx_list_separator_final-
    tl . . .
    20, 285, 292, 307, 401, 435
\l_siunitx_list_separator_pair-
    tl . . .
    20, 283, 290, 305, 401, 437
\l_siunitx_list_separator_tl . . .
    ..... 20, 284, 291, 306, 401, 439
\siunitx_number_adjust_exponent:Nn
    ..... 39, 84, 232, 1495
\siunitx_number_adjust_exponent:nn
    ..... 39, 1495
\l_siunitx_number_bracket-
    ambiguous_bool . . .
    ..... 63, 260, 1519, 1524, 1619
\l_siunitx_number_comparator_tl . 40
\l_siunitx_number_exponent_tl . 40
\siunitx_number_format:nN . . .
    ..... 39, 14, 113, 173, 792
\l_siunitx_number_input_comparator-
    tl . . .
    ..... 29, 250, 1935
\l_siunitx_number_input_decimal-
    tl . . .
    ..... 40,
    28, 40, 390, 405, 411, 455, 561, 1933
\l_siunitx_number_input_exponent-
    tl . . .
    ..... 29, 261, 269, 270, 1937
\l_siunitx_number_input_sign_tl .
    ..... 29, 309, 417, 512, 1940
\siunitx_number_list:nn . 20, 142, 415
\siunitx_number_normalize-
    symbols:N . . .
    ..... 40, 77, 126
\siunitx_number_output:N . . .
    ..... 39, 22, 125, 759, 1584
\siunitx_number_output:n . . .
    ..... 39, 1584
\siunitx_number_output>NN . . .
    ..... 38, 39, 52, 67, 119,
    129, 134, 169, 439, 536, 594, 596, 1584
\siunitx_number_output:nN . . .
    ..... 39, 1584
\l_siunitx_number_output_-
    decimal_tl . . .
    ..... 40, 270,
    405, 423, 469, 1520, 1562, 1699, 1702
\siunitx_number_parse:nN . . .
    ..... 38, 39, 104, 114, 19, 50, 64, 107,
    108, 152, 166, 334, 533, 576, 668, 1918
\l_siunitx_number_parse_bool . . .
    ..... 39, 40, 9,
    10, 10, 17, 18, 50, 61, 96, 110, 332, 1917
\siunitx_number_process:N . . .
    ..... 39
\siunitx_number_process>NN . . .
    ..... 39, 20, 72, 87, 91, 110,
    167, 210, 233, 238, 243, 534, 589, 685
\siunitx_number_product:n 20, 161, 464
\siunitx_number_range:nn 20, 178, 511
\l_siunitx_number_sign_tl . . .
    ..... 40
\siunitx_prin_number:n . . .
    ..... 92
\siunitx_print...:n . . .
    ..... 28, 91–93
\siunitx_print_match:n . . .
    ..... 91, 80
\siunitx_print_math:n . . .
    ..... 91, 83, 99
\siunitx_print_number:n . . .
    ..... 91,
    60, 90, 114, 125, 141, 210, 217,
    251, 272, 273, 274, 276, 378,
    546, 549, 631, 660, 674, 683, 750, 793
\siunitx_print_text:n . . .
    ..... 91,
    84, 147, 235, 720, 725, 730, 736, 752
\siunitx_print_unit:n . . .
    ..... 91, 104,
    47, 60, 83, 124, 148, 224, 280, 644, 655
\siunitx_quantity_print:nn . . .
    ..... 139
\siunitx_quantity:nn . . .
    ..... 104, 40, 86, 97, 658
\siunitx_quantity_list:nn . . .
    ..... 20, 134, 415, 668
\l_siunitx_quantity_prefix_mode-
    tl . . .
    ..... 9, 65, 184, 188, 263
\siunitx_quantity_print:nn . . .
    ..... 104, 55,
    104, 108, 121, 123, 127, 139, 151, 372
\siunitx_quantity_product:nn . . .
    ..... 20, 152, 464
\siunitx_quantity_range:nn . . .
    ..... 20, 170, 511, 677

```

```

\l_siunitx_range_phrase_tl .....
..... 21, 297, 299, 310, 499, 530
\l_siunitx_unit_font_tl .....
..... 139, 88, 91, 122, 317, 330, 819, 831, 842, 855, 926
\siunitx_unit_format:nN .... 104, 137, 138, 150, 41, 46, 54, 81, 86, 92, 123, 132, 223, 239, 279, 643, 654
\siunitx_unit_format_combine_-
exponent:nnN .... 138, 75, 132, 195
\siunitx_unit_format_extract_-
prefixes:nNN .... 138, 80, 132, 218
\siunitx_unit_format_multiply:nnN .... 138, 132, 244
\siunitx_unit_format_multiply_-
combine_exponent:nnnN 138, 132, 203
\siunitx_unit_format_multiply_-
extract_prefixes:nnNN 138, 132, 224
\l_siunitx_unit_fraction_tl ...
..... 140, 253, 500, 973
\siunitx_unit_options_apply:n ...
..... 139, 140, 43, 79, 89, 95, 121, 132, 150, 168, 193, 357, 666, 675
\siunitx_unit_pdfstring_context:
..... 140, 332, 337
\siunitx_unit_power_set:NnN ... 149
\l_siunitx_unit_seq ... 140, 22, 75, 91
\l_siunitx_unit_symbolic_seq ...
..... 140, 21, 29, 53, 66, 179, 340, 631, 636
siunitx internal commands:
\_\_siunitx_angle:n ..... 277, 344
\_\_siunitx_angle:nnn ..... 105, 210
\_\_siunitx_angle:w ..... 344
\_\_siunitx_angle_arc_convert:n .. 45
\_\_siunitx_angle_arc_print:nnn ...
..... 53, 134, 172
\_\_siunitx_angle_arc_print_-
auxi:nnn ..... 172
\_\_siunitx_angle_arc_print_-
auxii:nw ..... 187, 204
\_\_siunitx_angle_arc_print_-
auxii:w ..... 172
\_\_siunitx_angle_arc_print_-
auxiii:n ..... 172
\_\_siunitx_angle_arc_print_-
auxiv:NN ..... 172
\_\_siunitx_angle_arc_print_-
auxv:w ..... 172
\_\_siunitx_angle_arc_print_-
auxvi:n ..... 172
\_\_siunitx_angle_arc_sign:nn ... 91
\_\_siunitx_angle_arc_sign:nnn 66, 91
\l\_siunitx_angle_astronomy_bool ...
..... 6, 186
\l\_siunitx_angle_degrees_tl ...
..... 50, 51, 52, 54, 87, 135
\_\_siunitx_angle_extract_-
sign:nnnnnnnn ..... 91
\l\_siunitx_angle_fill_degrees_-
bool ..... 6
\l\_siunitx_angle_fill_minutes_-
bool ..... 6
\l\_siunitx_angle_fill_seconds_-
bool ..... 6
\l\_siunitx_angle_force_arc_bool ...
..... 6, 47
\l\_siunitx_angle_force_decimal_-
bool ..... 6, 61
\l\_siunitx_angle_marker_box ...
..... 170, 214, 228, 232, 238, 240, 244, 249
\l\_siunitx_angle_minutes_tl 87, 136
\l\_siunitx_angle_product_tl 6, 278
\l\_siunitx_angle_seconds_tl 87, 137
\l\_siunitx_angle_separator_tl 6, 195
\_\_siunitx_angle_sign:nnnnnnn ... 91
\l\_siunitx_angle_sign_tl ...
..... 90, 101, 105, 114, 163
\l\_siunitx_angle_symbol_degree_-
tl ..... 6, 175
\l\_siunitx_angle_symbol_minute_-
tl ..... 6, 177
\l\_siunitx_angle_symbol_second_-
tl ..... 6, 179
\l\_siunitx_angle_tmp_bool ...
..... 3, 208, 209, 256
\l\_siunitx_angle_tmp_dim ...
..... 3, 241, 263, 265
\l\_siunitx_angle_tmp_tl ...
..... 3, 152, 153, 159, 223, 224, 279, 280
\l\_siunitx_angle_unit_box ...
..... 170, 219, 229, 233, 237, 246
\_\_siunitx_bookmark_cmd:Nn ... 270
\_\_siunitx_bookmark_cmd:Nnn ...
..... 270, 276, 277, 278, 279, 280, 287, 294, 295, 296, 298, 300, 301, 302, 309
\c\_siunitx_bookmark_seq ... 311, 324
\l\_siunitx_column_type_tl .. 46, 260
\_\_siunitx_command_create: ...
..... 37
\_\_siunitx_command_create:N ...
..... 37
\l\_siunitx_command_create_bool ...
..... 4, 39
\l\_siunitx_command_optarg_bool ...
..... 4, 71, 75
\l\_siunitx_command_overwrite_-
bool ..... 4, 64
\l\_siunitx_command_prespace_-
bool ..... 4, 80
\l\_siunitx_command_tmp_tl ... 3, 82, 84

```

```

\l_siunitx_command_xspace_bool . . . . . 4, 62, 88
\l_siunitx_compound_bracket_-
  close_tl . . . . . 14, 274, 290, 396
\l_siunitx_compound_bracket_-
  open_tl . . . . . 14, 272, 288, 394
\l_siunitx_compound_count_int . . .
  . . . . . 11, 329, 352, 357
\l_siunitx_compound_end_tl . . .
  . . . . . 9, 331, 362
\l_siunitx_compound_exp_-
  bracket_bool . . . . . 18, 254, 284
\l_siunitx_compound_exp_-
  combine_bool . 18, 112, 209, 234, 256
\l_siunitx_compound_exp_tl . . .
  . . . . . 8, 148, 264, 270, 285, 291, 295
\l_siunitx_compound_extract_-
  exp:nN . . . . . 180
\l_siunitx_compound_extract_-
  exp:nnnnnnN . . . . . 180
\l_siunitx_compound_extract_-
  exponents: . . . . . 114, 131
\l_siunitx_compound_extract_-
  exponents_auxi:w . . . . . 131
\l_siunitx_compound_extract_-
  exponents_auxii:nw . . . . . 131
\l_siunitx_compound_extract_-
  exponents_auxiii:nnnnnn . . . . . 131
\l_siunitx_compound_first_tl . . .
  . . . . . 7, 110, 119,
  125, 134, 150, 210, 212, 233, 238, 243
\l_siunitx_compound_format:n . . . . . 85
\l_siunitx_compound_format:nn . 85, 262
\l_siunitx_compound_format:nnn . . . . . 85
\l_siunitx_compound_format_-
  combine-exponent:n . . . . . 180
\l_siunitx_compound_format_-
  combine-exponent:nn . . . . . 180
\l_siunitx_compound_format_-
  combine-exponent:nn . . . . . 180
\l_siunitx_compound_format_-
  extract-exponent:n . . . . . 180
\l_siunitx_compound_format_-
  extract-exponent:nn . . . . . 180
\l_siunitx_compound_format_-
  extract-exponent_aux:n . . . . . 180
\l_siunitx_compound_format_-
  extract-exponent_aux:n . . . . . 180
\l_siunitx_compound_format_-
  input:n . . . . . 180
\l_siunitx_compound_format_-
  input:nn . . . . . 241
\l_siunitx_compound_format_-
  units:nn . . . . . 109, 180
\l_siunitx_compound_parsed:n . 129, 162
\l_siunitx_compound_print:N . . .
  . . . . . 90, 266, 273, 276, 281
\l_siunitx_compound_print:nnN . . . . . 281
\l_siunitx_compound_print:nnnN . . . . . 281
\l_siunitx_compound_print_aux:n . . . . . 281
\l_siunitx_compound_print_aux:nn . . . . . 281
\l_siunitx_compound_print_-
  quantity:n . . . . . 266, 277, 281
\l_siunitx_compound_print_-
  separator:n . . . . . 281
\l_siunitx_compound_separator_-
  final_tl . . . . . 18, 355
\l_siunitx_compound_separator_-
  pair_tl . . . . . 18, 320
\l_siunitx_compound_separator_-
  text_bool . . . . . 18, 376
\l_siunitx_compound_separator_-
  tl . . . . . 18, 350, 368
\l_siunitx_compound_start_tl . . .
  . . . . . 9, 330, 347
\l_siunitx_compound_tmp_fp . . .
  . . . . . 4, 212, 213, 230, 232
\l_siunitx_compound_tmp_seq . . .
  . . . . . 4, 95, 127,
  147, 174, 178, 300, 311, 318, 323, 334
\l_siunitx_compound_tmp_tl . . .
  . . . . . 4, 107,
  110, 118, 120, 121, 124, 127, 133,
  136, 166, 167, 168, 169, 170, 171,
  173, 174, 210, 231, 232, 233, 238, 243
\l_siunitx_compound_uncert_-
  bracket:N . . . . . 121, 171, 381
\l_siunitx_compound_uncert_-
  bracket:nnw . . . . . 381
\l_siunitx_compound_uncert_-
  bracket:w . . . . . 381
\l_siunitx_compound_unit_bool . . .
  . . . . . 12, 88, 108, 116, 164, 261
\l_siunitx_compound_unit_-
  bracket_bool . . . . . 18, 253, 258, 269
\l_siunitx_compound_unit_power_-
  bool . . . . . 22, 57, 63, 69, 75, 81, 182
\l_siunitx_compound_unit_-
  repeat_bool . . . . . 18, 255, 259, 265
\l_siunitx_compound_unit_tl . . .
  . . . . . 12, 213, 230, 239, 244, 372
\l_siunitx_compound_unparsed:n . . .
  . . . . . 103, 162
\l_siunitx_declare_column:Nnn . . . . . 221
\l_siunitx_emulation_non_latin:n . . .
  . . . . . 681, 711, 713,
  715, 721, 726, 731, 741, 757, 824, 828
\l_siunitx_emulation_non_-
  latin:nnnn . . . . . 681

```

```

\__siunitx_emulation_tmp:w .....
    ..... 772, 788, 790, 824, 827
\__siunitx_list_aux: ..... 415
\__siunitx_list_count:n ..... 361
\__siunitx_list_count:w ..... 361
\l_siunitx_list_exp_tl .... 401, 433
\l_siunitx_list_units_tl .. 401, 441
\__siunitx_list_use:nnnn .....
    ..... 282, 289, 304, 361
\__siunitx_list_use_aux:nnnn .. 361
\__siunitx_list_use_auxi:nw .....
    ..... 374, 375, 384
\__siunitx_list_use_auxi:w .... 361
\__siunitx_list_use_auxii:nnw .. 361
\__siunitx_list_use_auxiii:nnw .. 361
\__siunitx_load_check: ..... 25
\__siunitx_load_check:n ... 28, 36, 40
\__siunitx_number_adjust_exp:nn 1495
\__siunitx_number_adjust_-
    exp:nnnnnnnn ..... 1495
\__siunitx_number_adjust_exp:nW
    ..... 1495
\l_siunitx_number_arg_tl ... 50,
    53, 69, 119, 125, 126, 127, 246, 253,
    256, 272, 287, 299, 373, 508, 514, 522
\l_siunitx_number_bracket_-
    close_tl ..... 1515, 1633, 1684
\l_siunitx_number_bracket_-
    negative_bool ..... 1521, 1659
\l_siunitx_number_bracket_open_-
    tl ..... 1515, 1631, 1682
\l_siunitx_number_comparator_tl
    ..... 70, 252, 255, 356
\__siunitx_number_digits:NN 694, 959
\__siunitx_number_digits:Nn ... 959
\__siunitx_number_digits:nn ... 959
\__siunitx_number_digits:nnnnnnn 959
\__siunitx_number_digits:S:n ... 959
\__siunitx_number_digits_-
    uncert:nn ..... 975, 984
\__siunitx_number_digits_uncert_-
    S:n ..... 989
\__siunitx_number_drop_exponent:NN
    ..... 692, 994
\__siunitx_number_drop_exponent:nnnnnnn
    ..... 994
\l_siunitx_number_drop_exponent_-
    bool ..... 630, 996
\__siunitx_number_drop_uncertainty:NN
    ..... 690, 1004
\__siunitx_number_drop_uncertainty:nnnnnnn
    ..... 1004
\l_siunitx_number_drop_uncertainty_-
    bool ..... 630, 1006
\l_siunitx_number_drop_zero_-
    decimal_bool ..... 630, 1479
\l_siunitx_number_explicit_-
    plus_bool ..... 29, 318, 517
\__siunitx_number_exponent:NN ...
    ..... 707, 711
\l_siunitx_number_exponent_-
    base_tl ..... 1521, 1890
\__siunitx_number_exponent_-
    engineering:nnnnnnn ..... 711
\__siunitx_number_exponent_-
    engineering:nnW ..... 711
\__siunitx_number_exponent_-
    engineering_0:nnnn ..... 711
\__siunitx_number_exponent_-
    engineering_1:nnnn ..... 711
\__siunitx_number_exponent_-
    engineering_2:nnnn ..... 711
\__siunitx_number_exponent_-
    engineering_aux:nnnnnnn .... 711
\__siunitx_number_exponent_-
    engineering_uncert:nn ..... 711
\__siunitx_number_exponent_-
    engineering_uncert_S:nnn .... 711
\__siunitx_number_exponent_-
    finalise:n ..... 711, 1244
\__siunitx_number_exponent_-
    fixed:nnnnnnn ..... 711
\__siunitx_number_exponent_-
    fixed:nnnnnnnn ..... 711
\l_siunitx_number_exponent_-
    fixed_int ..... 630, 729, 737
\__siunitx_number_exponent_-
    input:nnnnnnn ..... 711
\l_siunitx_number_exponent_-
    mode_tl ..... 630, 716, 720, 1204
\l_siunitx_number_exponent_-
    product_tl ..... 1521, 1886
\__siunitx_number_exponent_-
    scientific:nnnnnnn ..... 711
\__siunitx_number_exponent_-
    scientific:nnnnnnnn ..... 711
\__siunitx_number_exponent_-
    scientific:nnnw ..... 711
\__siunitx_number_exponent_-
    shift:nnn ..... 711, 1238
\__siunitx_number_exponent_-
    shift_down:nnn ..... 711
\__siunitx_number_exponent_-
    shift_down:nnw ..... 711
\__siunitx_number_exponent_-
    shift_down:nw ..... 711
\__siunitx_number_exponent_-
    shift_uncert:nw ..... 711

```

```

\__siunitx_number_exponent_-
    shift_uncert_S:nnnn ..... 711
\__siunitx_number_exponent_-
    shift_up:nnn ..... 711
\__siunitx_number_exponent_-
    shift_up:nnw ..... 711
\__siunitx_number_exponent_-
    shift_up_aux:nnn ..... 711
\l__siunitx_number_exponent_tl ..
    ..... 71,
    263, 297, 312, 320, 321, 332, 342, 359
\__siunitx_number_exponent_-
    uncert:n ..... 711
\__siunitx_number_expression:n ..
    ..... 29, 122
\l__siunitx_number_expression_-
    bool ..... 29, 121
\l__siunitx_number_flex_tl 47, 72,
    135, 144, 148, 170, 178, 464, 466, 502
\l__siunitx_number_group_-
    decimal_bool ..... 1521
\l__siunitx_number_group_-
    integer_bool ..... 1521
\l__siunitx_number_group_-
    minimum_int ..... 1521, 1713
\l__siunitx_number_group_-
    separator_tl 1521, 1742, 1745, 1770
\__siunitx_number_if_token_-
    auxi:NN ..... 1929
\__siunitx_number_if_token_-
    auxii:NN ..... 1929
\__siunitx_number_if_token_-
    auxiii:NN ..... 1929
\l__siunitx_number_implicit_-
    plus_bool ..... 1521, 1653, 1904
\l__siunitx_number_input_digit_-
    tl ..... 29,
    236, 340, 384, 402, 486, 541, 1936
\l__siunitx_number_input_ignore_-
    tl ..... 29, 1938
\l__siunitx_number_input_tl ...
    ..... 74, 125, 161
\l__siunitx_number_input_uncert_-
    close_tl ... 29, 530, 555, 568, 1934
\l__siunitx_number_input_uncert_-
    open_tl ..... 29, 412, 1939
\l__siunitx_number_input_uncert_-
    sign_tl ..... 29, 149, 1941
\l__siunitx_number_min_decimal_-
    int ..... 630, 973, 992
\l__siunitx_number_min_integer_-
    int ..... 630, 968
\l__siunitx_number_negative_-
    color_tl ..... 1521, 1640, 1641
\__siunitx_number_normalize_-
    aux:nN ..... 77
\__siunitx_number_normalize_-
    aux:NnN ..... 80, 85, 89
\__siunitx_number_normalize_-
    minus:N ..... 79, 102
\__siunitx_number_normalize_-
    sign:N ..... 77
\c__siunitx_number_normalize_tl . 77
\__siunitx_number_output:Nn .. 1584
\__siunitx_number_output:nn .. 1584
\__siunitx_number_output:nnnnnn
    ..... 1584
\__siunitx_number_output_-
    bracket:nn ..... 1584
\__siunitx_number_output_-
    bracket:w ..... 1584
\__siunitx_number_output_color:n
    ..... 1604, 1636
\__siunitx_number_output_-
    comparator:nn ..... 1584
\__siunitx_number_output_-
    decimal:nn ..... 1584
\__siunitx_number_output_-
    decimal_aux:n ..... 1584
\__siunitx_number_output_-
    decimal_loop>NNNN ..... 1584
\__siunitx_number_output_-
    digits:nn ..... 1584
\__siunitx_number_output_end: .
\l__siunitx_number_output_exp_-
    marker_tl ..... 1521, 1870, 1897
\__siunitx_number_output_-
    exponent:nnnn ..... 1584
\__siunitx_number_output_-
    exponent_auxi:nnnn ..... 1584
\__siunitx_number_output_-
    exponent_auxii:nnnn ..... 1584
\__siunitx_number_output_-
    exponent_auxiii:nn ..... 1584
\__siunitx_number_output_-
    integer:nnn ..... 1584
\__siunitx_number_output_-
    integer_aux:n ..... 1584
\__siunitx_number_output_-
    integer_aux_0:n ..... 1584
\__siunitx_number_output_-
    integer_aux_1:n ..... 1584
\__siunitx_number_output_-
    integer_aux_2:n ..... 1584
\__siunitx_number_output_-
    integer_first:nnNN ..... 1584
\__siunitx_number_output_-
    integer_loop>NNNN ..... 1584

```

```

\__siunitx_number_output_sign:N 1584
\__siunitx_number_output_sign:nN
    ..... 1584
\__siunitx_number_output_-
    sign:nnn ..... 1584
\__siunitx_number_output_sign_-
    brackets:w ..... 1584
\__siunitx_number_output_sign_-
    color:w ..... 1584
\l__siunitx_number_output_-
    uncert_close_tl ..... 1521, 1801
\l__siunitx_number_output_-
    uncert_open_tl ..... 1521, 1799
\__siunitx_number_output_uncert_-
    S:nnnw ..... 1584
\__siunitx_number_output_uncert_-
    S:nnw ..... 1584
\__siunitx_number_output_uncert_-
    S_aux:nnn ..... 1584
\__siunitx_number_output_uncert_-
    S_aux:nnnw . 1809, 1826, 1833, 1840
\__siunitx_number_output_uncert_-
    S_aux:nnw ..... 1831, 1841
\__siunitx_number_output_uncert_-
    S_compact-marker:nn ..... 1584
\__siunitx_number_output_uncert_-
    S_compact:nn ..... 1584
\__siunitx_number_output_uncert_-
    S_full:nn ..... 1584
\__siunitx_number_output_-
    uncertainty:nnn ..... 1584
\__siunitx_number_output_-
    uncertainty_unaligned:n ... 1584
\l__siunitx_number_outputted_tl .
    ..... 8, 21, 24, 26
\__siunitx_number_parse:nN .... 108
\__siunitx_number_parse_check: ...
    ..... 129, 133
\__siunitx_number_parse_combine_-
    uncert: ..... 151, 166
\__siunitx_number_parse_combine_-
    uncert_auxi:nnnnnnnn ..... 166
\__siunitx_number_parse_combine_-
    uncert_auxii:nnnnnn ..... 166
\__siunitx_number_parse_combine_-
    uncert_auxiii:nnnnnn ..... 166
\__siunitx_number_parse_combine_-
    uncert_auxiv:nnnn ..... 166
\__siunitx_number_parse_combine_-
    uncert_auxv:w ..... 166
\__siunitx_number_parse_combine_-
    uncert_auxvi:w ..... 166
\__siunitx_number_parse_comparator:
    ..... 128, 243
\__siunitx_number_parse_comparator_-
    aux:Nw ..... 243
\__siunitx_number_parse_exponent:
    ..... 259, 524
\__siunitx_number_parse_exponent_-
    auxi:w ..... 259
\__siunitx_number_parse_exponent_-
    auxii:nn ..... 259
\__siunitx_number_parse_exponent_-
    auxiii:Nw ..... 259
\__siunitx_number_parse_exponent_-
    auxiv:nn ..... 259
\__siunitx_number_parse_exponent_-
    check:N ..... 259
\__siunitx_number_parse_exponent_-
    cleanup:N ..... 259
\__siunitx_number_parse_exponent_-
    cleanup:wN ..... 345, 347
\__siunitx_number_parse_exponent_-
    zero_test:N ..... 259
\__siunitx_number_parse_finalise:
    ..... 164, 350
\__siunitx_number_parse_finalise:nw
    ..... 350
\__siunitx_number_parse_loop: ...
    ..... 265, 305, 368
\__siunitx_number_parse_loop_-
    after_decimal>NNN ..... 368
\__siunitx_number_parse_loop_-
    break:wN ..... 368,
    529, 531, 540, 563, 573, 600, 622, 628
\__siunitx_number_parse_loop_-
    first:N ..... 368
\__siunitx_number_parse_loop_-
    first>NNN ..... 371, 376, 465
\__siunitx_number_parse_loop_-
    main>NNNN ..... 368
\__siunitx_number_parse_loop_-
    main_decimal>NN ..... 368
\__siunitx_number_parse_loop_-
    main_digit>NNNN ..... 368
\__siunitx_number_parse_loop_-
    main_end>NN ..... 368
\__siunitx_number_parse_loop_-
    main_sign>NNN ..... 368
\__siunitx_number_parse_loop_-
    main_store>NNN ..... 368, 590
\__siunitx_number_parse_loop_-
    main_uncert>NNN ..... 368
\__siunitx_number_parse_loop_-
    root_swap>NNwNN ..... 368
\__siunitx_number_parse_sign: ...
    ..... 257, 505

```

```

\__siunitx_number_parse_sign_-
    aux:Nw ..... 505
\__siunitx_number_parse_uncert:NN
    ..... 459, 526
\__siunitx_number_parse_uncert:NNNN
    ..... 526
\__siunitx_number_parse_uncert_-
    after:N ..... 526
\__siunitx_number_parse_uncert_-
    auxi:NN ..... 526
\__siunitx_number_parse_uncert_-
    auxii:N ..... 526
\__siunitx_number_parse_uncert_-
    auxii:NN ..... 526
\__siunitx_number_parse_uncert_-
    auxiii:N ..... 557, 570, 575
\__siunitx_number_parse_uncert_-
    marker:N ..... 526
\__siunitx_number_parse_uncert_-
    marker:nnN ..... 595, 596
\__siunitx_number_parse_uncert_-
    marker:nNw ..... 601, 603
\l__siunitx_number_parsed_tl ...
    ..... 48, 19,
    20, 22, 73, 118, 131, 140, 152, 154,
    156, 170, 177, 212, 214, 264, 301,
    304, 313, 323, 349, 352, 354, 357,
    372, 503, 518, 519, 521, 523, 1918, 1919
\l__siunitx_number_partial_tl ...
    ..... 75, 370, 432,
    433, 436, 446, 470, 471, 474, 478,
    488, 546, 577, 588, 589, 599, 610, 611
\__siunitx_number_process:nnnnnnnNN
    ..... 685
\__siunitx_number_round:NN
    ..... 705, 708, 1016
\__siunitx_number_round:nnn 1028,
    1327, 1366, 1376, 1437, 1465, 1471
\__siunitx_number_round_auxi:nnnN
    ..... 1028
\__siunitx_number_round_auxii:nnnN
    ..... 1028
\__siunitx_number_round_auxiii:nnnN
    ..... 1028
\__siunitx_number_round_auxiv:nnN
    ..... 1028
\__siunitx_number_round_auxiv:nnN
    ..... 1049, 1063, 1073, 1079
\__siunitx_number_round_auxv:nnN
    ..... 1028
\__siunitx_number_round_auxvi:nN
    ..... 1028
\__siunitx_number_round_auxvi:nnN
    ..... 1088
\__siunitx_number_round_auxvi:nnN
    ..... 1082, 1105
\__siunitx_number_round_auxvii:nnN
    ..... 1028
\__siunitx_number_round_auxviii:nnN
    ..... 1028
\__siunitx_number_round_engineering:nn
    ..... 1028
\__siunitx_number_round_engineering:nnN
    ..... 1028
\__siunitx_number_round_engineering:NNNNn
    ..... 1028
\__siunitx_number_round_figures:nnnnnnn
    ..... 1287
\__siunitx_number_round_figures_-
    aux:nnnnnnn ..... 1287
\__siunitx_number_round_figures_-
    count:nnN ..... 1287
\__siunitx_number_round_figures_-
    count:nnnN ..... 1287
\__siunitx_number_round_final:nn
    ..... 1028
\__siunitx_number_round_final_-
    decimal:nnw ..... 1028
\__siunitx_number_round_final_-
    integer:nnw ..... 1028
\__siunitx_number_round_final_-
    output:nn ..... 1028
\__siunitx_number_round_final_-
    shift:nn ..... 1028
\__siunitx_number_round_final_-
    shift:Nw ..... 1028
\__siunitx_number_round_fixed:nn
    ..... 1028
\l__siunitx_number_round_half_-
    even_bool ..... 630, 1096, 1114
\__siunitx_number_round_if_-
    half:N ..... 1261
\__siunitx_number_round_if_-
    half:n ..... 1261
\__siunitx_number_round_if_half_-
    p:n ..... 1098, 1116, 1261
\__siunitx_number_round_input:nn
    ..... 1028
\l__siunitx_number_round_min_tl .
    ..... 665, 673, 1394, 1402
\l__siunitx_number_round_mode_tl
    ..... 630, 1021, 1201, 1247
\__siunitx_number_round_none:nnnnnnn
    ..... 1016
\__siunitx_number_round_pad:nnn
    ..... 1278, 1332, 1361
\l__siunitx_number_round_pad_-
    bool ..... 630, 1283

```

```

\__siunitx_number_round_places:nnnnnnn
    ..... 1339
\__siunitx_number_round_places_-
    decimal:nn ..... 1339
\__siunitx_number_round_places_-
    end:nn ..... 1243, 1339
\__siunitx_number_round_places_-
    finalise:n ..... 1339
\__siunitx_number_round_places_-
    finalise:nnnnn ..... 1339
\__siunitx_number_round_places_-
    finalise:nnnnnnn ..... 1339
\__siunitx_number_round_places_-
    integer:nn ..... 1339
\l_siunitx_number_round_-
    precision_int ..... 630,
    1224, 1302, 1325, 1328, 1333, 1346,
    1359, 1362, 1369, 1379, 1420, 1440
\__siunitx_number_round_scientific:nn
    ..... 1236
\__siunitx_number_round_scientific:nn
    ..... 1028
\__siunitx_number_round_truncate:n
    ..... 1028
\__siunitx_number_round_truncate:nnN
    ..... 1028
\__siunitx_number_round_truncate_-
    direct:n ..... 1028, 1474
\__siunitx_number_round_uncertainty:nnn
    ..... 1416
\__siunitx_number_round_uncertainty:nnnn
    ..... 1416
\__siunitx_number_round_uncertainty:nnnnnn
    ..... 1416
\__siunitx_number_round_uncertainty_-
    aux:nnnn ..... 1416
\__siunitx_number_round_uncertainty_-
    aux:nnnnnn ..... 1416
\__siunitx_number_set_round_-
    min:n ..... 653, 666
\__siunitx_number_set_round_-
    min:nnnnnnn ..... 666
\l_siunitx_number_tight_bool
    ..... 1521, 1675, 1883
\l_siunitx_number_tmp_tl
    ..... 7, 147, 150,
    268, 273, 279, 280, 288, 289, 668, 669
\__siunitx_number_token_auxi:NN
    ..... 1932, 1945, 1949
\__siunitx_number_token_auxii:NN
    ..... 1948, 1951
\__siunitx_number_token_auxiii:NN
    ..... 1953, 1956, 1967
\l_siunitx_number_uncert_mode_-
    tl ..... 1521, 1618, 1788, 1800
\l_siunitx_number_uncert_-
    separator_tl ..... 1521, 1798
\l_siunitx_number_unity_-
    mantissa_bool ... 1521, 1690, 1880
\l_siunitx_number_valid_tl .. 1911
\l_siunitx_number_validate_bool
    ..... 76, 158, 1916
\__siunitx_number_zero_decimal:NN
    ..... 693, 1477
\__siunitx_number_zero_decimal:nnnnnnn
    ..... 1477
\l_siunitx_number_zero_exponent_-
    bool ..... 1521, 1623, 1867
\l_siunitx_number_zero_uncert_-
    bool ..... 29, 233, 582
\__siunitx_option_DEPRECATED:nn
    ..... 11, 76, 82, 88, 108, 122, 131,
    137, 151, 157, 222, 228, 241, 247,
    268, 274, 286, 292, 301, 310, 316,
    352, 358, 364, 370, 516, 522, 530,
    545, 563, 569, 577, 583, 589, 610, 616
\__siunitx_option_DEPRECATED:nnm
    ..... 11,
    42, 50, 58, 66, 97, 323, 333, 341,
    377, 388, 396, 413, 507, 554, 595, 602
\__siunitx_option_removed:n
    ..... 22, 36, 172, 196, 216,
    261, 280, 282, 305, 330, 348, 513, 527
\__siunitx_option_table_comparator:nnnnnnn
    ..... 451
\__siunitx_option_table_comparator:nnnnnnnn
    ..... 466
\__siunitx_option_table_figures_decimal:nnnnnnnn
    ..... 451
\__siunitx_option_table_figures_exponent:nnnnnnnn
    ..... 451
\__siunitx_option_table_figures_integer:nnnnnnnn
    ..... 451
\__siunitx_option_table_figures_uncertainty:nnnnnnnn
    ..... 451
\__siunitx_option_table_format:n
    ..... 451, 489, 491, 493, 495, 497, 499, 501
\__siunitx_option_table_sign_exponent:nnnnnnnn
    ..... 451
\__siunitx_option_table_sign_mantissa:nnnnnnnn
    ..... 451
\__siunitx_print_aux:nn ..... 60
\__siunitx_print_convert_-
    series:n ..... 99
\__siunitx_print_extract_-
    series:Nw ..... 99
\__siunitx_print_math_aux:N .... 99

```

```

\__siunitx_print_math_aux:Nn . . . . . 99
\__siunitx_print_math_aux:w . . . . . 99
\__siunitx_print_math_auxi:n . . . . . 99
\__siunitx_print_math_auxii:n . . . . . 99
\__siunitx_print_math_auxiii:n . . . . . 99
\__siunitx_print_math_auxiv:n . . . . . 99
\__siunitx_print_math_auxv:n . . . . . 99
\l__siunitx_print_math_family_-
    bool . . . . . 7, 149
\l__siunitx_print_math_font_bool
    . . . . . 7, 164
\__siunitx_print_math_script:n . . . . . 99
\__siunitx_print_math_sub:n . . . . . 99
\__siunitx_print_math_super:n . . . . . 99
\__siunitx_print_math_text:n . . . . . 99
\__siunitx_print_math_version:nn . . . . . 99
\l__siunitx_print_math_version_-
    bool . . . . . 7, 126
\l__siunitx_print_math_weight_-
    bool . . . . . 7, 101
\l__siunitx_print_number_color_-
    tl . . . . . 7
\l__siunitx_print_number_mode_tl . . . . . 7
\__siunitx_replace_font:N .
    . . . . . 86, 195, 217, 268
\l__siunitx_print_text_family_-
    bool . . . . . 28, 239, 247
\l__siunitx_print_text_font_tl 7, 252
\__siunitx_print_text_fraction:Nnn
    . . . . . 235
\__siunitx_print_text_replace:N 235
\__siunitx_print_text_replace:n 235
\__siunitx_print_text_replace>NNn
    . . . . . 235
\__siunitx_print_text_scripts: . 235
\__siunitx_print_text_scripts:NnN
    . . . . . 235
\__siunitx_print_text_scripts_-
    one:Nn . . . . . 330, 337, 368
\__siunitx_print_text_scripts_-
    one:NnN . . . . . 235
\__siunitx_print_text_scripts_-
    two:n . . . . . 235
\__siunitx_print_text_scripts_-
    two:nn . . . . . 235
\__siunitx_print_text_scripts_-
    two:NnNn . . . . . 235
\l__siunitx_print_text_series_-
    bool . . . . . 30, 241, 248
\l__siunitx_print_text_shape_-
    bool . . . . . 32, 243, 249
\__siunitx_print_text_sub:n . . . . . 235
\__siunitx_print_text_super:n . . . . . 235
\l__siunitx_print_tmp_tl . . . . . 6, 103,
    105, 107, 194, 195, 196, 199, 202,
    216, 217, 218, 227, 228, 230, 261,
    262, 263, 304, 305, 306, 340, 341, 343
\l__siunitx_print_unit_color_tl . . . . . 7
\l__siunitx_print_unit_mode_tl . . . . . 7
\l__siunitx_print_version_b_tl . . . . . 48
\l__siunitx_print_version_eb_tl . . . . . 48
\l__siunitx_print_version_el_tl . . . . . 48
\l__siunitx_print_version_l_tl . . . . . 48
\l__siunitx_print_version_m_tl . . . . . 48
\l__siunitx_print_version_sb_tl . . . . . 48
\l__siunitx_print_version_sl_tl . . . . . 48
\l__siunitx_print_version_ub_tl . . . . . 48
\l__siunitx_print_version_ul_tl . . . . . 48
\c__siunitx_print_weight_b_tl . . . . . 97
\c__siunitx_print_weight_c_tl . . . . . 95
\c__siunitx_print_weight_ecl_tl . . . . . 95
\c__siunitx_print_weight_ex_tl . . . . . 95
\c__siunitx_print_weight_l_tl . . . . . 97
\c__siunitx_print_weight_m_tl . . . . . 97
\c__siunitx_print_weight_sc_tl . . . . . 95
\c__siunitx_print_weight_sx_tl . . . . . 95
\c__siunitx_print_weight_uc_tl . . . . . 95
\c__siunitx_print_weight_ux_tl . . . . . 95
\c__siunitx_print_weight_x_tl . . . . . 95
\__siunitx_product_aux: . . . . . 464
\__siunitx_product_aux:n . . . . . 464
\l__siunitx_product_exp_tl . . . . . 445, 488
\l__siunitx_product_phrase_bool .
    . . . . . 445, 480, 493
\l__siunitx_product_phrase_tl . . . . .
    . . . . . 445, 481
\l__siunitx_product_symbol_tl . . . . .
    . . . . . 445, 482
\l__siunitx_product_units_tl 445, 494
\l__siunitx_quantity_bracket_-
    close_tl . . . . . 5, 113
\l__siunitx_quantity_bracket_-
    open_tl . . . . . 5, 111
\l__siunitx_quantity_break_bool .
    . . . . . 9, 145
\__siunitx_quantity_extract_-
    exp:nNN . . . . . 73, 131
\__siunitx_quantity_extract_-
    exp:nnnnnnNN . . . . . 131
\__siunitx_quantity_non_latin:n .
    . . . . . 159, 181
\__siunitx_quantity_non_latin:nnnn
    . . . . . 159
\l__siunitx_quantity_number_tl .
    . . . . . 38, 53,
    56, 64, 66, 67, 68, 72, 74, 82, 85, 87, 91
\__siunitx_quantity_parsed:nn . . . . . 40

```

```

\__siunitx_quantity_parsed_-
    aux:nnnn ..... 40
\__siunitx_quantity_parsed_-
    aux:nnnw ..... 40
\__siunitx_quantity_parsed_aux:w 40
\__siunitx_quantity_parsed_-
    combine-exponent:n ..... 40
\__siunitx_quantity_parsed_-
    input:n ..... 40
\l__siunitx_quantity_product_tl .
    ..... 9, 144
\l__siunitx_quantity_tmp_fp ...
    ..... 3, 74, 76, 81, 85
\l__siunitx_quantity_tmp_tl ... 3
\l__siunitx_quantity_uncert_-
    bracket_bool ..... 9, 106
\l__siunitx_quantity_uncert_-
    repeat_bool ..... 9, 119
\l__siunitx_quantity_unit_tl ...
    ..... 38, 46, 47, 54,
      56, 76, 81, 92, 104, 116, 122, 124, 127
\__siunitx_range_aux: ..... 511
\l__siunitx_range_exp_tl ... 499, 529
\l__siunitx_range_units_tl . 499, 532
\__siunitx_symbol_deal_with_utf:
    ..... 25, 32
\__siunitx_symbol_if_replace:Nn . 33
\__siunitx_symbol_if_replace:NnTF
    ..... 33, 54, 59, 64, 106, 126
\__siunitx_symbol_non_latin:n ...
    ..... 10, 37, 75, 82, 99, 120, 135, 149
\__siunitx_symbol_non_latin:nnnn 10
\l__siunitx_symbol_tmptb_tl ...
    ..... 3, 36, 42, 82, 83, 84, 87
\l__siunitx_symbol_tmptb_tl ...
    ..... 3, 41, 42, 86, 87
\l__siunitx_table_after_box 484,
    512, 514, 518, 525, 528, 540, 601, 614
\l__siunitx_table_after_model_tl
    ..... 315, 328, 441, 600
\l__siunitx_table_after_tl ...
    ..... 107, 118, 125, 169
\l__siunitx_table_align_after_-
    bool ..... 488, 604
\__siunitx_table_align_auxi:nn . 205
\__siunitx_table_align_auxii:nn 205
\l__siunitx_table_align_before_-
    bool ..... 488, 624, 664
\__siunitx_table_align_center:n 205
\l__siunitx_table_align_comparator_-
    bool ..... 488, 649
\l__siunitx_table_align_exponent_-
    bool ..... 488, 742
\__siunitx_table_align_left:n . 205
\l__siunitx_table_align_mode_tl .
    ..... 301, 397, 401, 502
\l__siunitx_table_align_number_-
    tl ..... 301, 476, 609, 789
\__siunitx_table_align_right:n . 205
\l__siunitx_table_align_text_tl .
    ..... 238, 248, 430, 553
\l__siunitx_table_align_uncertainty_-
    bool ..... 488, 731
\l__siunitx_table_auto_round_-
    bool ..... 301, 578
\l__siunitx_table_before_box ...
    ..... 484, 506, 507, 509, 515, 517, 521,
      526, 532, 569, 570, 572, 611, 693, 696
\l__siunitx_table_before_dim ...
    ..... 486, 575, 636, 685, 693
\l__siunitx_table_before_model_-
    tl ..... 313, 326, 448, 568
\l__siunitx_table_before_tl ...
    ..... 107, 116, 120, 123
\l__siunitx_table_carry_dim ...
    ..... 487, 602, 605, 705, 760, 768, 780
\__siunitx_table_center_marker:
    ..... 267, 429, 552
\__siunitx_table_cleanup_-
    decimal:w ..... 255, 447
\__siunitx_table_collect_begin:
    ..... 11, 24
\__siunitx_table_collect_begin:N 126
\__siunitx_table_collect_begin:w 24
\__siunitx_table_collect_end: 19, 110
\__siunitx_table_collect_end:n . 110
\__siunitx_table_collect_end:w . 110
\__siunitx_table_collect_end_-
    aux:n ..... 110
\__siunitx_table_collect_group:n 39
\__siunitx_table_collect_loop:
    ..... 31, 38, 39
\__siunitx_table_collect_relax:N 39
\__siunitx_table_collect_-
    search:NnTF ..... 39
\__siunitx_table_collect_search_-
    aux:NNn ..... 39
\l__siunitx_table_collect_tl ...
    ..... 23, 27, 47, 64, 113, 115, 138
\__siunitx_table_collect_token:N 39
\__siunitx_table_collect_token_-
    aux:N ..... 39
\__siunitx_table_color_check:N ...
    ..... 258, 537
\__siunitx_table_color_check:Nnw 258
\__siunitx_table_color_check:w ...
    ..... 258, 622

```

```

\l_siunitx_table_column_width_-
    dim ..... 198, 214
\l_siunitx_table_decimal_box ...
    . 251, 275, 279, 285, 292, 406, 421,
    433, 448, 466, 467, 479, 547, 556,
    613, 704, 708, 757, 759, 764, 775, 777
\l_siunitx_table_direct_begin: ...
    ..... 12, 388
\l_siunitx_table_direct_begin:w 388
\l_siunitx_table_direct_end: 20, 388
\l_siunitx_table_direct_format: 388
\l_siunitx_table_direct_format:nnnnnnnn
    ..... 388
\l_siunitx_table_direct_format:w 388
\l_siunitx_table_direct_format_-
    aux:w ..... 440, 443
\l_siunitx_table_direct_format_-
    end: ..... 388
\l_siunitx_table_direct_format_-
    switch: ..... 388
\l_siunitx_table_direct_marker: 388
\l_siunitx_table_direct_marker_-
    end: ..... 388
\l_siunitx_table_direct_marker_-
    switch: ..... 388
\l_siunitx_table_direct_none: 388
\l_siunitx_table_direct_none_-
    end: ..... 388
\l_siunitx_table_fil: .....
    ... 253, 286, 296, 408, 450, 474,
    520, 529, 607, 629, 659, 672, 695, 765
\l_siunitx_table_fill: .... 253, 460
\l_siunitx_table_fixed_width_-
    bool ..... 198, 213
\l_siunitx_table_format_tl 325,
    334, 336, 337, 340, 456, 460, 464, 586
\l_siunitx_table_generate_-
    model:n ..... 316, 329
\l_siunitx_table_generate_-
    model:nnnnnnn ..... 329, 463
\l_siunitx_table_generate_model_-
    S:nnn ..... 329
\l_siunitx_table_generate_model_-
    S:nw ..... 329
\l_siunitx_table_integer_box ...
    ..... 251, 272, 281, 290,
    297, 409, 432, 452, 478, 545, 555,
    612, 626, 635, 639, 650, 652, 654,
    658, 666, 668, 673, 679, 680, 682, 689
\l_siunitx_table_model_tl .....
    ..... 314, 316, 325, 345, 439, 594
\l_siunitx_table_number_tl .....
    ..... 107, 117, 119, 124
\l_siunitx_table_print:nnn . 122, 501
\l_siunitx_table_print_format:nnn
    ..... 501
\l_siunitx_table_print_format:nnnnnnn
    ..... 501
\l_siunitx_table_print_format_-
    after:N ..... 501
\l_siunitx_table_print_format_-
    auxi:w ..... 501
\l_siunitx_table_print_format_-
    auxii:w ..... 501
\l_siunitx_table_print_format_-
    auxiii:w ..... 501
\l_siunitx_table_print_format_-
    auxiv:w ..... 501
\l_siunitx_table_print_format_-
    auxv:w ..... 501
\l_siunitx_table_print_format_-
    auxvi:w ..... 501
\l_siunitx_table_print_format_-
    auxvii:w ..... 501
\l_siunitx_table_print_format_-
    box:Nn ..... 501
\l_siunitx_table_print_marker:nnn
    ..... 501
\l_siunitx_table_print_marker:w 501
\l_siunitx_table_print_marker_-
    aux:w ..... 501
\l_siunitx_table_print_none:nnn 501
\l_siunitx_table_print_text:n ...
    ..... 120, 245, 394
\l_siunitx_table_skip:n .....
    ..... 193, 217, 219, 231, 233
\l_siunitx_table_split:nNNN .....
    ..... 114, 144, 312
\l_siunitx_table_split_group:NNNn
    ..... 144
\l_siunitx_table_split_loop:NNN 144
\l_siunitx_table_split_tidy:N ...
    ..... 150, 151, 182
\l_siunitx_table_split_tidy:Nn . 182
\l_siunitx_table_split_token:NNNN
    ..... 144
\l_siunitx_table_text_bool .....
    ..... 6, 9, 16, 247
\l_siunitx_table_tmp_box .....
    ..... 3, 269, 276, 282, 293, 404,
    407, 446, 449, 451, 453, 568, 575,
    600, 602, 623, 627, 638, 647, 655,
    669, 687, 703, 707, 728, 729, 730,
    739, 740, 741, 761, 766, 771, 778, 783
\l_siunitx_table_tmp_dim .....
    .. 132, 3, 678, 688, 729, 740, 770, 782

```

```

\l_siunitx_table_tmp_tl . 3, 438,
    441, 533, 534, 535, 536, 537, 539,
    576, 589, 591, 592, 596, 599, 792, 793
\l_siunitx_tmp:w . . . . .
    ..... 229, 231, 630, 631, 635, 636
\l_siunitx_tmp_tl . . . . 43, 113,
    114, 123, 124, 186, 643, 644, 654, 655
\l_siunitx_unit_autofrac_bool ..
    513, 520, 527, 534, 541, 548, 567, 945
\l_siunitx_unit_bracket_bool . .
    ..... 561, 599, 692, 762, 869, 890
\l_siunitx_unit_bracket_close_-
    tl . . . . . 562, 696, 821
\l_siunitx_unit_bracket_open_tl
    . . . . . 562, 694, 818
\l_siunitx_unit_combine_exp_fp .
    . . . . . 135,
    142, 149, 156, 164, 172, 573, 588, 623
\l_siunitx_unit_current_tl 577,
    600, 738, 740, 756, 758, 798, 800,
    803, 811, 849, 856, 864, 916, 924, 927
\l_siunitx_unit_denominator_-
    bracket_bool . . . . . 500, 888
\l_siunitx_unit_denominator_tl .
    579, 584, 889, 934, 975, 984, 993, 1000
\l_siunitx_unit_font_bool . .
    ..... 566, 601, 853, 859, 922, 929
\l_siunitx_unit_forbid_literal_-
    bool . . . . . 192, 500
\l_siunitx_unit_format:nNN . . .
    ..... 132
\l_siunitx_unit_format_aux: . . .
    ..... 132
\l_siunitx_unit_format_bracket:N
    . . . . . 690, 740, 758, 984
\l_siunitx_unit_format_combine_-
    exp: . . . . . 589, 618
\l_siunitx_unit_format_finalise:
    . . . . . 608, 932
\l_siunitx_unit_format_finalise_-
    autofrac: . . . . . 932
\l_siunitx_unit_format_finalise_-
    fraction: . . . . . 950, 956, 969
\l_siunitx_unit_format_finalise_-
    fractional: . . . . . 932
\l_siunitx_unit_format_finalise_-
    power: . . . . . 932
\l_siunitx_unit_format_finalise_-
    symbol: . . . . . 949, 959, 978
\l_siunitx_unit_format_font: . .
    ..... 702, 815, 827, 837, 868, 920
\l_siunitx_unit_format_literal:n
    . . . . . 194, 197, 211
\l_siunitx_unit_format_literal_-
    add:n . . . . . 211
\l_siunitx_unit_format_literal_-
    auxi:w . . . . . 211
\l_siunitx_unit_format_literal_-
    auxii:n . . . . . 251, 255
\l_siunitx_unit_format_literal_-
    auxii:w . . . . . 211
\l_siunitx_unit_format_literal_-
    auxiii:w . . . . . 211
\l_siunitx_unit_format_literal_-
    auxiv:n . . . . . 211
\l_siunitx_unit_format_literal_-
    auxv:nw . . . . . 211
\l_siunitx_unit_format_literal_-
    auxvi:nN . . . . . 211
\l_siunitx_unit_format_literal_-
    auxvii:nN . . . . . 211
\l_siunitx_unit_format_literal_-
    auxviii:nn . . . . . 211
\l_siunitx_unit_format_literal_-
    auxviii:nN . . . . . 211
\l_siunitx_unit_format_literal_-
    sub:nn . . . . . 211
\l_siunitx_unit_format_literal_-
    subscript: . . . . . 211
\l_siunitx_unit_format_literal_-
    super:nn . . . . . 211
\l_siunitx_unit_format_literal_-
    superscript: . . . . . 211
\l_siunitx_unit_format_literal_-
    tilde: . . . . . 211
\l_siunitx_unit_format_mass_to_-
    kilogram: . . . . . 595, 666
\l_siunitx_unit_format_multiply:
    . . . . . 591, 650
\l_siunitx_unit_format_output: . .
    . . . . . 606, 866
\l_siunitx_unit_format_output_-
    aux: . . . . . 866
\l_siunitx_unit_format_output_-
    aux:nn . . . . . 866
\l_siunitx_unit_format_output_-
    denominator: . . . . . 866
\l_siunitx_unit_format_parsed: . .
    . . . . . 189, 581
\l_siunitx_unit_format_parsed_-
    aux:n . . . . . 581
\l_siunitx_unit_format_power: . .
    ..... 700
\l_siunitx_unit_format_power_-
    aux:wTF . . . . . 700
\l_siunitx_unit_format_power_-
    negative: . . . . . 700
\l_siunitx_unit_format_power_-
    negative_aux:w . . . . . 700

```

```

\__siunitx_unit_format_power_-
    positive: ..... 700
\__siunitx_unit_format_power_-
    superscript:w ..... 731, 734
\__siunitx_unit_format_power_-
    superscript: ..... 700
\__siunitx_unit_format_prefix: . 764
\__siunitx_unit_format_prefix_-
    exp: ..... 764
\__siunitx_unit_format_prefix_-
    gram: ..... 764
\__siunitx_unit_format_prefix_-
    symbol: ..... 764
\__siunitx_unit_format_qualifier:
    ..... 804
\__siunitx_unit_format_qualifier_-
    bracket: ..... 804
\__siunitx_unit_format_qualifier_-
    combine: ..... 804
\__siunitx_unit_format_qualifier_-
    phrase: ..... 804
\__siunitx_unit_format_qualifier_-
    subscript: ..... 804
\__siunitx_unit_format_special: 847
\__siunitx_unit_format_unit: .. 861
\l__siunitx_unit_formatted_tl ...
    162, 131, 181, 201, 232, 240, 241,
    305, 312, 325, 327, 585, 897, 898,
    943, 944, 958, 960, 964, 965, 966,
    971, 974, 980, 982, 989, 992, 996, 998
\__siunitx_unit_if_symbolic:n ... 11
\__siunitx_unit_if_symbolic:nTF .
    ..... 11, 79, 185
\__siunitx_unit_literal_power:nn
    ..... 43, 117, 209
\__siunitx_unit_literal_special:nN
    ..... 111, 210
\l__siunitx_unit_mass_kilogram_-
    bool ..... 122, 594, 775
\c__siunitx_unit_math_subscript_-
    tl ..... 7, 221, 245, 288, 314, 840
\l__siunitx_unit_multiple_fp 136,
    143, 150, 157, 165, 173, 576, 590, 657
\__siunitx_unit_non_latin:n 1004,
    1040, 1056, 1067, 1090, 1091, 1092
\__siunitx_unit_non_latin:nnnn 1004
\l__siunitx_unit_numerator_bool .
    ..... 169, 571, 602, 714, 873
\l__siunitx_unit_options_bool ...
    ..... 88, 91, 102
\__siunitx_unit_parse:n .... 187, 350
\__siunitx_unit_parse_add:nnnn ..
    ..... 363,
    380, 394, 412, 422, 431, 435, 440, 454
\l__siunitx_unit_parse_bool 183, 500
\__siunitx_unit_parse_finalise: .
    ..... 361, 490
\__siunitx_unit_parse_finalise:n
    ..... 360, 459
\__siunitx_unit_parse_per: . 106, 445
\__siunitx_unit_parse_power:nnN .
    ..... 44, 47, 118, 121, 377
\__siunitx_unit_parse_prefix:Nn .
    ..... 53, 377
\__siunitx_unit_parse_qualifier:nn
    ..... 68, 115, 377
\__siunitx_unit_parse_special:n .
    ..... 109, 112, 377
\__siunitx_unit_parse_unit:Nn 81, 426
\l__siunitx_unit_parsed_prop ...
    ..... 155, 188,
    347, 352, 366, 373, 391, 410, 462,
    464, 468, 476, 480, 485, 496, 614,
    620, 624, 629, 639, 643, 652, 654,
    659, 661, 670, 672, 679, 681, 779, 784
\l__siunitx_unit_parsing_bool ...
    ..... 9, 34, 216, 339, 353, 675, 797
\l__siunitx_unit_part_tl ...
    ..... 470, 472, 473, 474,
    481, 577, 615, 704, 717, 720, 722,
    732, 773, 788, 794, 795, 803, 811,
    816, 820, 828, 832, 838, 843, 851, 864
\l__siunitx_unit_per_bool ...
    ..... 158, 347, 354, 438, 449
\l__siunitx_unit_per_symbol_bool
    ..... 514, 521,
    528, 535, 542, 549, 567, 896, 902, 948
\l__siunitx_unit_per_symbol_tl ...
    ..... 500, 983
\l__siunitx_unit_position_int ...
    ..... 162,
    347, 356, 359, 379, 386, 397, 409,
    413, 423, 428, 432, 436, 441, 455,
    495, 583, 587, 597, 603, 613, 778, 783
\l__siunitx_unit_powers_positive_-
    bool ..... 515,
    522, 529, 536, 543, 550, 567, 715, 936
\l__siunitx_unit_prefix_exp_bool
    ..... 134,
    141, 148, 155, 163, 171, 574, 593, 766
\l__siunitx_unit_prefix_fp ...
    ..... 182, 203, 575, 586, 684, 685, 787
\l__siunitx_unit_prefixes_-
    forward_prop ..... 49, 626, 772
\l__siunitx_unit_prefixes_-
    reverse_prop ..... 49, 641
\l__siunitx_unit_product_tl ...
    ..... 122, 252, 881, 892, 999

```

| | |
|---|--|
| \l_siunitx_unit_qualifier_mode_- | 1201, 1247, 1397, 1410, 1423, 1488, |
| tl | 500, 572, 809 |
| \l_siunitx_unit_qualifier_- | 1513, 1657, 1699, 1742, 1788, 1959 |
| phrase_tl | 500, 830 |
| \l_siunitx_unit_separator_tl .. | 211 |
| _siunitx_unit_set_symbolic:Nnn | \str_if_eq_p:nn |
| | 319, 444, 544, 676, 678, |
| _siunitx_unit_set_symbolic:Nnnn | 700, 702, 1290, 1292, 1388, 1390, |
| | 1618, 1624, 1639, 1691, 1868, 1881 |
| _siunitx_unit_set_symbolic:Nnnn | \str_range:n |
| | 380, 382 |
| \symoperators | 91, 173 |
| sys commands: | |
| \sys_if_engine_luatex_p: | 11, 118, 133, 160, 682, 739, 755, 1005 |
| \sys_if_engine_xetex:TF | 295 |
| \sys_if_engine_xetex_p: | 12, 119, 134, 161, 683, 740, 756, 1006 |
| T | |
| table-align-comparator | 114 |
| table-align-exponent | 114 |
| table-align-text-after | 114 |
| table-align-text-before | 114 |
| table-align-uncertainty | 114 |
| table-alignment | 115 |
| table-alignment-mode | 115 |
| table-auto-round | 115 |
| table-column-width | 115 |
| table-fixed-width | 115 |
| table-format | 115 |
| table-number-alignment | 115 |
| table-text-alignment | 115 |
| \tablenum | 198 |
| \tabularnewline | 55, 57, 84, 86 |
| \tebi | 183, 2 |
| \tera | 141, 13, 57, 1044 |
| \tesla | 142, 1066 |
| \TeV | 178, 42 |
| TeX and L ^A T _E X 2 _{<} commands: | |
| @\ifl@t@r | 12, 42 |
| @\ifpackagelater | 1 |
| @\ifpackageloaded | |
| .. | 30, 42, 44, 66, 73, 75, 80, 90, 97, |
| 143, 223, 224, 246, 299, 320, 708, 822 | |
| @\ifundefined | 9 |
| @\maybe@unskip | 81 |
| @\temptokena | 234, 236 |
| @\array@row@rst | 119, 134, 135 |
| \f@family | 151 |
| \f@series | 104 |
| \FB@fg | 333 |
| @m@th | 354, 396 |
| @\math@version | 132 |
| @\NC@do | 229, 230 |
| @\NC@find | 239 |
| @\NC@list | 7, 230, 231 |
| @\newcommand | 186 |

```

\protected@edef ..... 119, 152, 15, 36, 83, 119, 136, 230
\sf@size ..... 367
\tab@setcr ..... 82
\use@mathgroup ..... 183, 185
\z@ ..... 367
tex commands:
\tex_cr:D ..... 32
\tex_hfil:D ..... 247, 253
\tex_hfill:D ..... 254
\tex_hss:D ..... 267, 269
\tex_kern:D ..... 196
\tex 91, 101, 49, 55, 61, 71, 95, 115, 130,
136, 237, 541, 547, 558, 564, 575,
584, 796, 801, 806, 809, 812, 819, 828
text-family-to-math ..... 93
text-font-command ..... 93
text-series-to-math ..... 93
\textrmcenteredperiod ..... 91
\textrmcolor ... 91-93, 137, 143, 70, 111, 112
\textrmdegree ..... 74, 98
\textrmminus ..... 91, 276
\textrmmu ..... 136, 742
\textrmohm ..... 121, 758
\textrmperiodcentered ..... 280
\textrmpm ..... 91, 272
\textrmsubscript ..... 91, 316, 347
\textrmsuperscript ..... 91, 321
\textrmtimes ..... 91, 278
\the ..... 231, 236
\THz ..... 177, 8
tight-spacing ..... 42
\times ... 38, 14, 20, 26, 32, 277, 578, 1985
tl commands:
\c_empty_tl ..... 55, 56, 1752
\c_space_tl ..... 182, 273, 327, 352, 357, 396, 404
\tl_clear:N ..... 27, 101, 112, 118, 146, 147, 148, 149, 152, 154, 177, 178, 181, 232, 255, 264, 301, 313, 323, 332, 349, 370, 478, 502, 503, 523, 584, 585, 600, 688
\tl_clear_new:N ..... 83
\tl_const:Nn ..... 7, 91, 96, 98
\tl_count:N ..... 599, 611
\tl_count:n ..... 113, 175, 182, 185, 370, 599, 607, 680, 703, 744, 981, 982, 1212, 1293, 1359, 1362, 1369, 1379, 1391, 1440, 1449, 1490, 1713, 1724, 1794, 1852, 1860
\tl_head:n ..... 99, 214, 269, 353, 1092, 1110, 1263, 1423, 1780
\tl_head:w ..... 914, 938
\tl_if_blank:nTF ..... 3, 17, 44, 103, 142, 142, 158, 184, 192, 211, 300, 322, 348, 350, 351, 352, 355, 357, 363, 385, 403, 482, 563, 630, 715, 736, 737, 749, 792, 804, 810, 832, 848, 908, 922, 932, 945, 975, 1047, 1157, 1300, 1341, 1456, 1463, 1645, 1651, 1669, 1697, 1777, 1902
\tl_if_blank_p:n ..... 4, 139, 143, 218, 219, 390, 391, 1419, 1620, 1851
\tl_if_empty:NTF ..... 68, 88, 105, 105, 109, 119, 125, 127, 135, 156, 161, 169, 174, 184, 233, 256, 261, 264, 304, 312, 327, 337, 352, 470, 522, 577, 687, 914, 934, 943, 989, 1394, 1499, 1594, 1870, 1919
\tl_if_empty:nTF ... 84, 329, 709, 1599
\tl_if_empty_p:N ..... 270, 285, 432, 889, 897, 1640
\tl_if_eq:nnTF ..... 429
\tl_if_exist:NTF ..... 95
\tl_if_head_eq_charcode:nNTF ... 748
\tl_if_head_eq_meaning:nNTF ... 253, 262
\tl_if_head_is_N_type:nTF ..... 275
\tl_if_in:NnTF ... 5, 56, 149, 250, 309, 340, 384, 390, 402, 405, 412, 417, 486, 512, 530, 541, 555, 561, 568
\tl_if_novalue:nTF ..... 212, 215
\tl_if_single_token:nTF ..... 93
\tl_map_function:nN ..... 103, 129
\tl_map_inline:Nn ... 260, 270, 411, 455
\tl_map_inline:nn ..... 54
\tl_new:N ..... 3, 3, 3, 4, 4, 5, 5, 6, 6, 6, 7, 7, 7, 8, 8, 8, 9, 9, 9, 10, 13, 14, 15, 23, 28, 38, 39, 43, 68, 69, 70, 71, 72, 73, 74, 75, 87, 88, 89, 90, 107, 108, 109, 131, 244, 323, 324, 325, 326, 327, 328, 336, 401, 402, 445, 447, 499, 500, 562, 563, 572, 577, 578, 579, 663, 664, 665, 1515, 1516, 1520, 1583, 1911
\tl_put_right:Nn ..... 47, 57, 64, 162, 163, 172, 175, 176, 179, 236, 305, 312, 325, 342, 381, 392, 434, 446, 472, 488, 546, 579, 811, 863
\tl_replace_all:Nnn ..... 3, 5, 5, 6, 88, 90, 104, 196, 199, 218, 220, 228, 272, 292
\tl_reverse:n ... 799, 1184, 1185, 1191
\tl_set:Nn 61, 152, 171, 7, 8, 16, 17, 21, 24, 26, 51, 53, 53, 66, 82, 82, 85, 103, 111, 118, 120, 124, 127, 131, 132, 133, 136, 146, 147, 148, 161, 163, 168, 170, 190, 194, 200, 212,
```

| | | |
|---------------------------|--|--|
| \unit | 216, 217, 227, 231, 240, 242, 252, 253, 261, 263, 264, 268, 297, 299, 304, 317, 320, 321, 330, 331, 332, 336, 340, 345, 354, 365, 385, 408, 433, 438, 441, 448, 456, 461, 464, 466, 471, 472, 494, 514, 518, 519, 521, 535, 564, 565, 588, 591, 592, 612, 621, 632, 635, 636, 655, 673, 676, 678, 683, 713, 717, 722, 738, 745, 756, 777, 782, 786, 794, 798, 800, 816, 828, 838, 849, 898, 911, 924, 944, 958, 960, 961, 971, 980, 996, 998, 1008, 1018, 1481, 1517, 1518 | |
| \tl_set_eq:N | 18, 20, 44, 125, 159, 252, 307, 321, 407, 413, 452, 462, 505, 509, 557, 640, 656, 803, 991, 1011, 1577 | |
| \tl_tail:n | 100, 915, 939 | |
| \tl_use:N | 75, 122, 144, 202, 218, 252, 263, 297, 299, 306, 310 | |
| \l_tmpa_tl | 137, 138 | |
| token commands: | | |
| \c_math_toggle_token | 410, 419, 422, 427, 454, 464, 468, 473, 482, 483 | |
| \token_if_eq_charcode_p:N | 516 | |
| \token_if_eq_meaning:NNTF | 103, 284, 287, 1511 | |
| \token_to_str:N | 30, 83, 85, 85, 95, 98, 105, 180, 219, 221, 229, 338, 341, 370, 403, 417, 768, 770, 775, 779, 782, 784, 1109, 1112 | |
| \tonne | 142, 1077 | |
| \tothe | 143, 116 | |
| \TrimSpaces | 91, 117, 128, 146, 156, 164, 662, 671 | |
| \ttdefault | 155 | |
| U | | |
| \uA | 177, 2 | |
| \uF | 179, 70 | |
| \ug | 177, 35 | |
| \uH | 75 | |
| \uJ | 178, 42 | |
| \uL | 178, 27 | |
| \ul | 178, 186, 27, 48 | |
| \um | 177, 60 | |
| \umol | 178, 14 | |
| uncertainty-mode | 43 | |
| uncertainty-separator | 43 | |
| \unit | 201, 100, 279, 313 | |
| W | | |
| \W | 178, 42 | |
| \watt | ... 142, 42, 43, 44, 45, 46, 47, 58, 1066 | |
| \weber | 142, 1066 | |
| X | | |
| \xspace | 88 | |
| Y | | |
| \yobi | 183, 2 | |
| \yocto | 141, 1034 | |
| \yotta | 141, 1044 | |
| Z | | |
| \zebi | 183, 2 | |
| \zepto | 141, 1034 | |
| \zetta | 141, 1044 | |