

siunitx – A comprehensive (SI) units package*

Joseph Wright[†]

Released 2022-01-27

Contents

I	siunitx-angle – Formatting angles	1
1	Formatting angles	1
	1.1 Key–value options	1
II	siunitx-compound – Compound numbers and quantities	3
III	siunitx-locale – Localisation	5
IV	siunitx-number – Parsing and formatting numbers	6
1	Formatting numbers	6
	1.1 Key–value options	8
V	siunitx-print – Printing material with font control	12
1	Printing quantities	12
	1.1 Key–value options	13
VI	siunitx-quantity – Quantities	15
VII	siunitx-symbol – Symbol-related settings	16
VIII	siunitx-table – Formatting numbers in tables	17

*This file describes v3.0.45, last revised 2022-01-27.

[†]E-mail: joseph.wright@morningstar2.co.uk

1	Numbers in tables	17
1.1	Key-value options	17
IX	siunitx-unit – Parsing and formatting units	19
1	Formatting units	19
2	Defining symbolic units	21
3	Per-unit options	22
4	Units in (PDF) strings	22
5	Pre-defined symbolic unit components	22
5.1	Key-value options	25
X	siunitx-abbreviations – Abbreviations	28
XI	siunitx-binary – Binary units	31
XII	siunitx-command – Units as document command	32
1	Creating units as document commands	32
1.1	Key-value options	32
XIII	siunitx-emulation – Emulation	33
Index		34

Part I

siunitx-angle – Formatting angles

1 Formatting angles

```
\siunitx_angle:n {<angle>}
\siunitx_angle:nnn {<degrees>} {<minutes>} {<seconds>}
```

Typeset the *<angle>* (which may be given as separate *<degree>*, *<minute>* and *<second>* components). The *<angle>* (or components) may be given as expressions. The *<angle>* should be a number as understood by `\siunitx_format_number:nN`, with no uncertainty, exponent or imaginary part. The unit symbols for degrees, minutes and seconds are `\degree`, `\arcminute` and `\arcsecond`, respectively

1.1 Key-value options

The options defined by this submodule are available within the `l3keys siunitx` tree.

```
angle-mode = <choice>
```

Selects how angles are formatted: a choice from the options `arc`, `decimal` and `input`. The option `arc` means that angles will always be typeset in arc (degree, minute, second) format, whilst `decimal` means that angles are typeset as a single decimal value. The `input` setting means that the input format (*i.e.* difference between `\siunitx_angle:n` and `\siunitx_angle:nnn`) is maintained. The standard setting is `input`.

```
angle-symbol-degree = <symbol>
```

Sets the symbol used for arc degrees, minutes or seconds, respectively.

```
angle-symbol-over-decimal = true|false
```

Determines if the arc separator is printed over the decimal marker, a format used in astronomy. The standard setting is `false`.

```
arc-separator = <separator>
```

Inserted between arc parts (degree, minute and second components). The standard setting is `\,`.

```
fill-angle-degrees = true|false
```

Determines whether a missing degrees part is zero-filled when printing an arc. The standard setting is `false`.

```
fill-angle-minutes = true|false
```

Determines whether a missing minutes part is zero-filled when printing an arc. The standard setting is `false`.

fill-angle-seconds**fill-arc-seconds = true|false**

Determines whether a missing seconds part is zero-filled when printing an arc. The standard setting is **false**.

number-angle-product**number-angle-product = <separator>**

Inserted between the value of an angle and the unit (degree, minute or second component). The standard setting is \,.

Part II

siunitx-compound – Compound numbers and quantities

\siunitx_compound_number:n

`\siunitx_compound_number:n {<entries>}`

Prints a set of numbers in the *<entries>*, each of which should be given as a *(balanced text)*. Unlike `\siunitx_number_list:nn`, this function may semantically take any form

\siunitx_compound_quantity:nn

`\siunitx_compound_quantity:nn {<entries>} {<unit>}`

Prints a set of quantities in the *<entries>*, each of which should be given as a *(balanced text)*. Unlike `\siunitx_quantity_list:nn`, this function may semantically take any form

\siunitx_number_list:nn

`\siunitx_number_list:nn {<entries>}`

Prints the list of numbers in the *<entries>*, each of which should be given as a *(balanced text)*.

\siunitx_quantity_list:nn

`\siunitx_quantity_list:nn {<entries>} {<unit>}`

Prints the list of quantities in the *<entries>*, each of which should be given as a *(balanced text)*.

\siunitx_number_product:n

`\siunitx_number_product:n {<entries>}`

Prints the series of numbers in the *<entries>*, each of which should be given as a *(balanced text)*.

\siunitx_quantity_product:nn

`\siunitx_quantity_product:nn {<entries>} {<unit>}`

Prints the series of quantities in the *<entries>*, each of which should be given as a *(balanced text)*.

\siunitx_number_range:nn

`\siunitx_number_range:nn {<start>} {<end>}`

Prints the range of numbers from the *<start>* to the *<end>*.

\siunitx_quantity_range:nnn

`\siunitx_quantity_range:nnn {<start>} {<end>} {<unit>}`

Prints the range of quantities from the *<start>* to the *<end>*.

\l_siunitx_list_separator_pair_tl
\l_siunitx_list_separator_tl
\l_siunitx_list_separator_final_tl

Separators for lists of numbers and quantities.

<u>\l_siunitx_range_phrase_t1</u>	Phrase (or similar) used between limits of a range.
<u>compound-exponents</u>	compound-exponents = combine combine-bracket individual
<u>compound-final-separator</u>	compound-final-separator = <i><text></i>
<u>compound-pair-separator</u>	compound-pair-separator = <i><text></i>
<u>compound-separator</u>	compound-separator = <i><text></i>
<u>compound-separator-mode</u>	compound-separator-mode = number text
<u>compound-units</u>	compound-units = bracket repeat single
<u>list-exponents</u>	list-exponents = combine combine-bracket individual
<u>list-final-separator</u>	list-final-separator = <i><text></i>
<u>list-pair-separator</u>	list-pair-separator = <i><text></i>
<u>list-separator</u>	list-separator = <i><text></i>
<u>list-units</u>	list-units = bracket repeat single
<u>product-exponents</u>	product-exponents = combine combine-bracket individual
<u>product-mode</u>	product-mode = phrase choice
<u>product-phrase</u>	product-phrase = <i><text></i>
<u>product-symbol</u>	product-symbol = <i><symbol></i>
<u>range-exponents</u>	range-exponents = combine combine-bracket individual
<u>range-phrase</u>	range-phrase = <i><text></i>
<u>range-units</u>	range-units = bracket repeat single

Part III

siunitx-locale – Localisation

This submodule is concerned with localisation of `siunitx` output based on the locale. If the `translations` package is available, this is loaded here and used to provide various fixed strings for output.

`locale` `locale = <locale>`

Selects the `<locale>` used to apply standard settings for other keys, principally `exponent-product`, `inter-unit-product` and `output-decimal-marker`.

Part IV

siunitx-number – Parsing and formatting numbers

This submodule is dedicated to parsing and formatting numbers. A small number of L^AT_EX 2_E math mode commands are assumed to be available as part of the formatted output. The sign commands `\mp`, `\pm`, `\ll`, `\le`, `\gg` and `\ge` are used to replace two-character input; `\pm` is also required for the output of uncertainties. The standard settings require `\times`. For the display of colored negative numbers, the command `\color` is assumed to be available. Where the latter may apply, numbers should be printed inside a group: note that T_EX grouping is not added *within* formatted numbers as they may need to be decomposed into parts (see `\siunitx_number_output:NN`). Such a color will be the *first* part of the result, meaning that a test for an initial `\color` and following brace group may be used to detect/remove/adjust this part.

1 Formatting numbers

`\siunitx_number_parse:nN` {*number*} *tl var*

Parses the *number* and stores the resulting internal representation in the *tl var*. The parsing is influenced by the various key–value settings for numerical input. The *number* should comprise a single real value, possibly with comparator, uncertainty and exponent parts. If the number is invalid, or if number parsing is disabled, the result will be an entirely empty *tl var*.

The structure of a valid number is:

$$\{ \langle comparator \rangle \} \{ \langle sign \rangle \} \{ \langle integer \rangle \} \{ \langle decimal \rangle \} \{ \langle uncertainty \rangle \} \\ \{ \langle exponent sign \rangle \} \{ \langle exponent \rangle \}$$

where the two sign parts must be single tokens if present, and all other components must be given in braces. The number will have at least one digit for both the *integer* and *exponent* parts: these are required. The *uncertainty* part should either be blank or contain an *identifier* (as a brace group), followed by one or more data entries. Valid *identifiers* currently are

S A single symmetrical uncertainty (*e.g.* a statistical standard uncertainty)

<code>\siunitx_number_process:NN</code>	<code>\siunitx_number_process:N <tl var1> <tl var2></code>
	Applies a set of number processing operations to the <i><internal number></i> stored in the <i><tl var1></i> , <i>viz.</i> in order
	<ol style="list-style-type: none"> 1. Dropping uncertainty 2. Converting to scientific mode (or similar) 3. Rounding 4. Dropping zero decimal part 5. Forcing a minimum number of digits
	with the result stored in <i><tl var2></i> .

```
\siunitx_number_output:N ☆ \siunitx_number_output:N <number>
\siunitx_number_output:n ☆ \siunitx_number_output:NN <number> <marker>
\siunitx_number_output:NN ☆
\siunitx_number_output:nN ☆
```

Formats the *<number>* (in the siunitx internal format), producing the result in a form suitable for typesetting in math mode. The details for the formatting are controlled by a number of key-value options. Note that *formatting* does not apply any manipulation (processing) to the number. This function is usable in an e- or x-type expansion, and further uncontrolled expansion is prevented by appropriate use of `\exp_not:n` internally.

In the NN version, the *<marker>* token is inserted at each possible alignment position in the output, *viz.*

- Between the comparator and the integer (*before* any sign for the integer)
- Between the sign and the first digit of the integer
- Both sides of the decimal marker
- Both sides of the separated uncertainty sign (*i.e.* after the decimal part and before any integer uncertainty part)
- Both sides of the decimal marker for a separated uncertainty
- Both sides of the multiplication symbol for the exponent part.

The n and nN version take a token list, which should be in the internal siunitx format.

<code>\siunitx_number_format:nN</code>	<code>\siunitx_number_format:nN {<number>} <tl var></code>
--	--

Carries out a combination of `\siunitx_number_parse:nN`, `\siunitx_number_process:NN` and `\siunitx_number_output:N` using x-type expansion to place the result in the *<tl var>*. If `\l_siunitx_number_parse_bool` if false, the input is simply stored inside the *<tl var>* inside `\ensuremath`.

<code>\siunitx_number_adjust_exponent:Nn *</code>	<code>\siunitx_number_adjust_exponent:Nn <number> {{fp expr}}</code>
---	--

Adjusts the exponent of the *<number>* (in internal format) by the *<fp expr>* and leaves the result in the input stream.

```
\siunitx_number_normalize_symbols:N \siunitx_number_normalize_symbols:N <tl var>
```

Replaces all multi-token signs and comparators in the $\langle tl\ var\rangle$ with their single-token equivalents. Replaces any active hyphen tokens with non-active versions.

```
\siunitx_if_number_p:n * \siunitx_if_number_token:NTF {\langle tokens\rangle}
\siunitx_if_number:nTF * {\langle true code\rangle} {\langle false code\rangle}
```

Determines if the $\langle tokens\rangle$ form a valid number which can be fully parsed by **siunitx**.

```
\siunitx_if_number_token:NTF \siunitx_if_number_token:NTF {\langle token\rangle}
{\langle true code\rangle} {\langle false code\rangle}
```

Determines if the $\langle token\rangle$ is valid in a number based on those tokens currently set up for detection in a number.

```
\l_siunitx_bracket_ambiguous_bool
```

A switch to control whether ambiguous numbers are bracketed: this can also be covered in quantity formatting by a setting there.

```
\l_siunitx_number_parse_bool
```

A switch to control whether any parsing is attempted for numbers.

```
\l_siunitx_number_comparator_tl
\l_siunitx_number_exponent_tl
\l_siunitx_number_sign_tl
```

The list of possible input comparators, exponent markers and signs.

```
\l_siunitx_number_input_decimal_tl
\l_siunitx_number_output_decimal_tl
```

The list of possible input decimal marker(s), and the output marker.

1.1 Key–value options

The options defined by this submodule are available within the `l3keys siunitx` tree.

```
bracket-ambiguous-numbers bracket-ambiguous-numbers = true|false
```

```
bracket-negative-numbers bracket-negative-numbers = true|false
```

```
drop-exponent drop-exponent = true|false
```

```
drop-uncertainty drop-uncertainty = true|false
```

```
drop-zero-decimal drop-zero-decimal = true|false
```

<u>evaluate-expression</u>	evaluate-expression = true false
<u>exponent-base</u>	exponent-base = $\langle \text{base} \rangle$
<u>exponent-mode</u>	exponent-mode = engineering fixed input scientific
<u>exponent-product</u>	exponent-product = $\langle \text{symbol} \rangle$
<u>expression</u>	expression = $\langle \text{expression} \rangle$
<u>fixed-exponent</u>	fixed-exponent = $\langle \text{exponent} \rangle$
<u>group-digits</u>	group-digits = all decimal integer none
<u>group-minimum-digits</u>	group-minimum-digits = $\langle \text{value} \rangle$
<u>group-separator</u>	group-separator = $\langle \text{symbol} \rangle$
<u>input-close-uncertainty</u>	input-close-uncertainty = $\langle \text{tokens} \rangle$
<u>input-comparators</u>	input-comparators = $\langle \text{tokens} \rangle$
<u>input-close-uncertainty</u>	input-close-uncertainty = $\langle \text{tokens} \rangle$
<u>input-decimal-markers</u>	input-decimal-markers = $\langle \text{tokens} \rangle$
<u>input-digits</u>	input-digits = $\langle \text{tokens} \rangle$
<u>input-exponent-markers</u>	input-exponent-markers = $\langle \text{tokens} \rangle$
<u>input-open-uncertainty</u>	input-open-uncertainty = $\langle \text{tokens} \rangle$
<u>input-signs</u>	input-signs = $\langle \text{tokens} \rangle$
<u>input-uncertainty-signs</u>	input-uncertainty-signs = $\langle \text{tokens} \rangle$

```
minimum-decimal-digits    minimum-decimal-digits = <min>

minimum-integer-digits    minimum-integer-digits = <min>

negative-color            negative-color = <color>

output-close-uncertainty  output-close-uncertainty = <symbol>

output-decimal-marker     output-decimal-marker = <symbol>

output-open-uncertainty   output-open-uncertainty = <symbol>

parse-numbers             parse-numbers = true|false

print-implicit-plus       print-implicit-plus = true|false

print-unity-mantissa      print-unity-mantissa = true|false

print-zero-exponent       print-zero-exponent = true|false

retain-explicit-plus      retain-explicit-plus = true|false

retain-zero-uncertainty   retain-zero-uncertainty = true|false

round-half                round-half = even|up

round-minimum             round-minimum = <min>

round-mode                round-mode = figures|none|places|uncertainty

round-pad                 round-pad = true|false

round-precision            round-precision = <precision>

tight-spacing              tight-spacing = true|false
```

uncertainty-mode uncertainty-mode = compact|compact-marker|full|separate

uncertainty-separator uncertainty-separator = $\langle separator \rangle$

Part V

siunitx-print – Printing material with font control

1 Printing quantities

This submodule is focussed on providing controlled printing for numbers and units. Key to this is control of font: conventions for printing quantities mean that the exact nature of the output is important. At the same time, this module provides flexibility for the user in terms of which aspects of the font are responsive to the surrounding general text. Printing material may also take place in text or math mode.

The printing routines assume that normal L^AT_EX 2 _{ε} font selection commands are available, in particular `\bfseries`, `\mathrm`, `\mathversion`, `\fontfamily`, `\fontseries` and `\fontshape`, `\familydefault`, `\seriesdefault`, `\shapedefault` and `\selectfont`. It also requires the standard L^AT_EX 2 _{ε} kernel commands `\ensuremath`, `\mbox`, `\textsubscript` and `\textsuperscript` for printing in text mode. The following packages are also required to provide the functionality detailed.

- `color`: support for color using `\textcolor`
- `textcomp`: `\textminus`, `\textpm` `\texttimes` and `\textcenteredperiod` for printing in text mode
- `amstext`: the `\text` command for printing in text mode

For detection of math mode fonts, as well as `\mathrm`, the existence of `\symoperators` is assumed; other math font commands are not *required* to exist.

```
\siunitx_print_number:n
\siunitx_print_number:(V|x)
\siunitx_print_unit:n
\siunitx_print_unit:(V|x)
```

```
\siunitx_print_number:n {<material>}
\siunitx_print_unit:n {<material>}
```

Prints the `<material>` according the the prevailing settings for the submodule as applicable to the `<type>` of content (`number` or `unit`). The `<material>` should comprise normal L^AT_EX mark-up for numbers or units. In particular, units will typically use `\mathrm` to indicate material to be printed in the current upright roman font, and `^` and `_` will typically be used to indicate super- and subscripts, respectively. These elements will be correctly handled when printing for example using `\mathsf` in math mode, or using only text fonts.

```
\siunitx_print_match:n
\siunitx_print_math:n
\siunitx_print_text:n
```

```
\siunitx_print_match:n {<material>}
\siunitx_print_math:n {<material>}
\siunitx_print_text:n {<material>}
```

Prints the `<material>` as described for `\siunitx_print_...:n` but with a fixed text or math mode output. The printing does *not* set color (which is managed on a `unit/number` basis), but otherwise sets the font as described above. The `match` function uses either the prevailing math or text mode.

1.1 Key–value options

The options defined by this submodule are available within the `\I3keys siunitx` tree.

color `color = <color>`

Color to apply to printed output: the latter should be a named color defined for use with `\textcolor`. The standard setting is empty (no color).

mode `mode = match|math|text`

Selects which mode (math or text) the output is printed in: a choice from the options `match`, `math` or `text`. The option `match` matches the mode prevailing at the point `\siunitx_print_...:n` is called. The `math` and `text` options choose the relevant `TEX` mode for printing. The standard setting is `math`.

number-color `number-color = <color>`

Color to apply to numbers in output: the latter should be a named color defined for use with `\textcolor`. The standard setting is empty (no color).

number-mode `number-mode = match|math|text`

Selects which mode (math or text) the numbers are printed in: a choice from the options `match`, `math` or `text`. The option `match` matches the mode prevailing at the point `\siunitx_prin_number:n` is called. The `math` and `text` options choose the relevant `TEX` mode for printing. The standard setting is `math`.

propagate-math-font `propagate-math-font = true|false`

Switch to determine if the currently-active math font is applied within printed output. This is relevant only when `\siunitx_print_...:n` is called from within math mode: in text mode there is not active math font. When not active, math mode material will be typeset using standard math mode fonts without any changes being made to the supplied argument. The standard setting is `false`.

reset-math-version `reset-math-version = true|false`

Switch to determine whether the active `\mathversion` is reset to `normal` when printing in math mode. Note that math version is typically used to select `\boldsymbol`, though it is also be used by *e.g.* `sansmath`. The standard setting is `true`.

reset-text-family `reset-text-family = true|false`

Switch to determine whether the active text family is reset to `\rmfamily` when printing in text mode. The standard setting is `true`.

reset-text-series `reset-text-series = true|false`

Switch to determine whether the active text series is reset to `\mdseries` when printing in text mode. The standard setting is `true`.

reset-text-shape `reset-text-shape = true|false`

Switch to determine whether the active text shape is reset to `\upshape` when printing in text mode. The standard setting is `true`.

text-family-to-math**text-family-to-math = true|false**

Switch to determine if the family of the current text font should be applied (where possible) to printing in math mode. The standard setting is **false**.

text-font-command**text-font-command = <cmd>**

Command applied to text during output, inserted after any reset of font set-up. This can therefore be used to apply non-standard font set up when printing in text mode. The standard setting is empty.

text-series-to-math**text-series-to-math = true|false**

Switch to determine if the weight of the current text font should be applied (where possible) to printing in math mode. This is achieved by setting the **\mathversion**, and so will override **reset-math-version**. The mappings between text and math weight are set . The standard setting is **false**.

unit-color**unit-color = <color>**

Color to apply to units in output: the latter should be a named color defined for use with **\textcolor**. The standard setting is empty (no color).

unit-mode**unit-mode = match|math|text**

Selects which mode (math or text) units are printed in: a choice from the options **match**, **math** or **text**. The option **match** matches the mode prevailing at the point **\siunitx-print_...:n** is called. The **math** and **text** options choose the relevant **T_EX** mode for printing. The standard setting is **math**.

series-version-mapping**series-version-mapping / <weight> = <version>**

Defines how **siunitx** maps from text font weight to math font version. The pre-defined weights are those used as-standard by **autoinst**:

- **ul**
- **el**
- **l**
- **sl**
- **m**
- **sb**
- **b**
- **eb**
- **ub**

As standard, the **m** weight maps to **normal** math version whilst all of the **b** weights map to **bold** and all of the **l** weights map to **light**.

Part VI

siunitx-quantity – Quantities

This submodule is focussed on providing controlled printing for quantities: the combination of a number and a unit. It largely builds on the submodules `siunitx-number` and `siunitx-unit`. A small number of adjustments are made to standard set up in the latter to reflect additional functionality added here.

`\siunitx_quantity:nn` `\siunitx_quantity:nn {<number>} {<unit>}`

Parses the `<number>` and the `<unit>` as detailed for `\siunitx_number_parse:nN` and `\siunitx_unit_format:nN`, the prints the results using `\siunitx_print_unit:n`.

`\siunitx_quantity_print:nn` `\siunitx_quantity_print:nn {<number>} {<unit>}`
`\siunitx_quantity_print:(nV|VV|xV)`

A low-level function which prints the quantity directly: there is no processing applied to either the `<number>` or `<unit>`. The two parts are printed using `\siunitx_print_unit:n` and appropriate spacing and break-prevention is applied.

`allow-quantity-breaks` `allow-quantity-breaks = true|false`

Specifies whether breaks are permitted between units. The standard setting is `false`.

`prefix-mode` `prefix-mode = combine-exponent|extract-exponent|input`

Selects the method used for producing prefixes: a choice from the options `combine-exponent`, `extract-exponent` and `input`. The option `combine-exponent` combines any exponent from the number with the prefix of the first unit, and prints the updated prefix. The option `extract-exponent` removes all prefixes from the unit, and combines them with the exponent of number. The option `input` prints prefixes and exponent as given in the source. The standard setting is `input`.

`quantity-product` `quantity-product = <tokens>`

The product marker used between a number and the unit. The standard setting is `\,`.

`separate-uncertainty-units` `separate-uncertainty-units = bracket|repeat|single`

Specifies how units are applied when a separated uncertainty is present: a choice from `bracket`, `repeat` and `single`. The option `bracket` places brackets around the number, with the unit given after these. The option `repeat` means that the unit is printed with the main value and with the uncertainty. When `single` is set, the unit is printed only once and no brackets are applied. The standard setting is `bracket`.

Part VII

siunitx-symbol – Symbol-related settings

Part VIII

siunitx-table – Formatting numbers in tables

1 Numbers in tables

This submodule is concerned with formatting numbers in table cells or similar fixed-width contexts. The main function, `\siunitx_cell_begin:w`, is designed to work with the normal L^AT_EX 2 _{ε} tabular cell construct featuring `\ignorespaces`. Therefore, if used outside of a L^AT_EX 2 _{ε} tabular, it is necessary to provide this token.

```
\siunitx_cell_begin:w
\siunitx_cell_end:
```

Collects the `<preamble>` and `<content>` tokens, and determines if it is text or a number (as parsed by `\siunitx_number_parse:nN`). It produces output of a fixed width suitable for alignment in a table, although it is not *required* that the code is used within a cell. Note that `\ignorespaces` must occur in the “cell”: it marks the end of the TeX `\halign` template.

1.1 Key–value options

The options defined by this submodule are available within the l3keys `siunitx` tree.

```
table-align-comparator
```

```
table-align-comparator = true|false
```

Switch which determines whether alignment of comparators is attempted within table cells. The standard setting is `true`.

```
table-align-exponent
```

```
table-align-exponent = true|false
```

Switch which determines whether alignment of exponents is attempted within table cells. The standard setting is `true`.

```
table-align-text-after
```

```
table-align-text-after = true|false
```

Switch which determines whether alignment of text falling after a number is attempted within table cells. The standard setting is `true`.

```
table-align-text-before
```

```
table-align-text-before = true|false
```

Switch which determines whether alignment of text falling before a number is attempted within table cells. The standard setting is `true`.

```
table-align-uncertainty
```

```
table-align-uncertainty = true|false
```

Switch which determines whether alignment of separated uncertainty values is attempted within table cells. The standard setting is `true`.

table-alignment

```
table-alignment = center|left|right
```

Selects the alignment of all tabular content with the margins of the table cell (or other boundary). See also **table-number-alignment** and **table-text-alignment**. The standard setting is **center**.

table-alignment-mode

```
table-alignment-mode = format|marker|none
```

Selects the method used to align numbers with the desired position in the cell (set by **table-alignment**). When set to **format**, a dedicated amount of space is calculated from the **table-format**. When **marker** is selected, alignment is carried out symmetrically around the decimal marker. Finally, **none** switches off all alignment: numbers are parsed and formatted but with no attempt at placement within the cell. The standard setting is **marker**.

table-auto-round

```
table-auto-round = true|false
```

Switch which determines whether numbers are rounded to fit within the **table-format** specification (if possible). The standard setting is **false**.

table-column-width

```
table-column-width = <width>
```

Sets the width of the table column used for numbers. This is only used when **table-fixed-width** is **true**.

table-fixed-width

```
table-fixed-width = true|false
```

Switch which determines whether a fixed-width column is used for numbers in tables. When **true**, the width is taken from **table-column-width**. The standard setting is **false**.

table-format

```
table-format = <format>
```

Describes the amount of space that should be reserved when **table-alignment-mode** is set to **format**. The **<format>** takes the same general form as input for a table cell, with the numerical parts describing how many digits to reserve space for. For example, **1.2e3** would allow space for one digit in the integer part, two in the decimal part and three in the exponent part. Signs can be allowed for using any valid input sign, so for example **+1.2 \pm 1.2** would allow for a sign, a number with one integer and two decimal digits and an uncertainty of the same size.

table-number-alignment

```
table-number-alignment = center|left|right
```

Selects the alignment of numerical content with the margins of the table cell (or other boundary). See also **table-alignment** and **table-text-alignment**. The standard setting is **center**.

table-text-alignment

```
table-text-alignment = center|left|none|right
```

Selects the alignment of non-numerical content with the margins of the table cell (or other boundary). See also **table-alignment** and **table-number-alignment**. Notice the additional support for **none** here. The standard setting is **center**.

Part IX

siunitx-unit – Parsing and formatting units

This submodule is dedicated to formatting physical units. The main function, `\siunitx_unit_format:nN`, takes user input specify physical units and converts it into a formatted token list suitable for typesetting in math mode. While the formatter will deal correctly with “literal” user input, the key strength of the module is providing a method to describe physical units in a “symbolic” manner. The output format of these symbolic units can then be controlled by a number of key–value options made available by the module.

A small number of L^AT_EX 2_& math mode commands are assumed to be available as part of the formatted output. The `\mathchoice` command (normally the T_EX primitive) is needed when using `per-mode = symbol-or-fraction`. The commands `\frac`, `\mathrm`, `\mbox`, `\lrcorner` and `\cancel`, are used by the standard module settings. For the display of colored (highlighted) and cancelled units, the commands `\textcolor` and `\cancel` are assumed to be available.

1 Formatting units

```
\siunitx_unit_format:nN
\siunitx_unit_format:xN
```

This function converts the input $\langle \text{units} \rangle$ into a processed $\langle tl \ var \rangle$ which can then be inserted in math mode to typeset the material. Where the $\langle \text{units} \rangle$ are given in symbolic form, described elsewhere, this formatting process takes place in two stages: the $\langle \text{units} \rangle$ are parsed into a structured form before the generation of the appropriate output form based on the active settings. When the $\langle \text{units} \rangle$ are given as literals, processing is minimal: the characters `.` and `~` are converted to unit products (boundaries). In both cases, the result is a series of tokens intended to be typeset in math mode with appropriate choice of font for typesetting of the textual parts.

For example,

```
\siunitx_unit_format:nN { \kilo \metre \per \second } \l_tmpa_tl
```

will, with standard settings, result in `\l_tmpa_tl` being set to

```
\mathrm{km}, \mathrm{s}^{-1}
```

```
\siunitx_unit_format_extract_prefixes:nNN  \siunitx_unit_format_extract_prefixes:nNN {<units>} {tl var}
                                                <fp var>
```

This function formats the *<units>* in the same way as described for `\siunitx_unit_format:nN`. When the input is given in symbolic form, any decimal unit prefixes will be extracted and the overall power of ten that these represent will be stored in the *<fp var>*.

For example,

```
\siunitx_unit_format_extract_prefixes:nNN { \kilo \metre \per \second }
                                         \l_tmpa_tl \l_tmpa_fp
```

will, with standard settings, result in `\l_tmpa_tl` being set to

$$\text{mathrm}{m}, \text{mathrm}{s}^{-1}$$

with `\l_tmpa_fp` taking value 3. Note that the latter is a floating point variable: it is possible for non-integer values to be obtained here.

```
\siunitx_unit_format_combine_exponent:nnN  \siunitx_unit_format_combine_exponent:nnN {<units>}
                                                {<exponent>} {tl var}
```

This function formats the *<units>* in the same way as described for `\siunitx_unit_format:nN`. The *<exponent>* is combined with any prefix for the *first* unit of the *<units>*, and an updated prefix is introduced.

For example,

```
\siunitx_unit_format_combine_exponent:nnN { \metre \per \second }
                                         { 3 } \l_tmpa_tl
```

will, with standard settings, result in `\l_tmpa_tl` being set to

$$\text{mathrm}{km}, \text{mathrm}{s}^{-1}$$

```
\siunitx_unit_format_multiply:nnN
\siunitx_unit_format_multiply_extract_prefixes:nnNN
\siunitx_unit_format_multiply_combine_exponent:nnnN
```

```
\siunitx_unit_format_multiply:nnN {<units>}
{<factor>} {tl var}
\siunitx_unit_format_multiply_extract-
prefixes:nnNN
{<units>} {<factor>} {tl var} {fp var}
\siunitx_unit_format_multiply_combine-
exponent:nnnN
{<units>} {<factor>} {<exponent>} {tl var}
```

These function formats the *<units>* in the same way as described for `\siunitx_unit_format:nN`. The units are multiplied by the *<factor>*, and further processing takes place as previously described.

For example,

```
\siunitx_unit_format_multiply:nnN { \metre \per \second }
                                         { 3 } \l_tmpa_tl
```

will, with standard settings, result in `\l_tmpa_tl` being set to

$$\text{mathrm}{km}^3, \text{mathrm}{s}^{-3}$$

2 Defining symbolic units

```
\siunitx_declare_prefix:Nnn \siunitx_declare_prefix:Nnn <prefix> {<power>} {<symbol>}
\siunitx_declare_prefix:Nnx
```

Defines a symbolic $\langle prefix \rangle$ (which should be a control sequence such as `\kilo`) to be converted by the parser to the $\langle symbol \rangle$. The latter should consist of literal content (*e.g.* `k`). In literal mode the $\langle symbol \rangle$ will be typeset directly. The prefix should represent an integer $\langle power \rangle$ of 10, and this information may be used to convert from one or more $\langle prefix \rangle$ symbols to an overall power applying to a unit. See also `\siunitx_declare_prefix:Nn`.

```
\siunitx_declare_prefix:Nn \siunitx_declare_prefix:Nn <prefix> {<symbol>}
```

Defines a symbolic $\langle prefix \rangle$ (which should be a control sequence such as `\kilo`) to be converted by the parser to the $\langle symbol \rangle$. The latter should consist of literal content (*e.g.* `k`). In literal mode the $\langle symbol \rangle$ will be typeset directly. In contrast to `\siunitx_declare_prefix:Nnn`, there is no assumption about the mathematical nature of the $\langle prefix \rangle$, *i.e.* the prefix may represent a power of any base. As a result, no conversion of the $\langle prefix \rangle$ to a numerical power will be possible.

```
\siunitx_declare_power>NNn \siunitx_declare_power:NNn <pre-power> <post-power> {<value>}
```

Defines *two* symbolic $\langle powers \rangle$ (which should be control sequences such as `\squared`) to be converted by the parser to the $\langle value \rangle$. The latter should be an integer or floating point number in the format defined for `I3fp`. Powers may precede a unit or be give after it: both forms are declared at once, as indicated by the argument naming. In literal mode, the $\langle value \rangle$ will be applied as a superscript to either the next token in the input (for the $\langle pre-power \rangle$) or appended to the previously-typeset material (for the $\langle post-power \rangle$).

```
\siunitx_declare_qualifier:Nn \siunitx_declare_qualifier:Nn <qualifier> {<meaning>}
```

Defines a symbolic $\langle qualifier \rangle$ (which should be a control sequence such as `\catalyst`) to be converted by the parser to the $\langle meaning \rangle$. The latter should consist of literal content (*e.g.* `cat`). In literal mode the $\langle meaning \rangle$ will be typeset following a space after the unit to which it applies.

```
\siunitx_declare_unit:Nn \siunitx_declare_unit:Nx
\siunitx_declare_unit:Nnn \siunitx_declare_unit:Nxn
```

Defines a symbolic $\langle unit \rangle$ (which should be a control sequence such as `\kilogram`) to be converted by the parser to the $\langle meaning \rangle$. The latter may consist of literal content (*e.g.* `kg`), other symbolic unit commands (*e.g.* `\kilo\gram`) or a mixture of the two. In literal mode the $\langle meaning \rangle$ will be typeset directly. The version taking an $\langle options \rangle$ argument may be used to support per-unit options: these are applied at the top level or using `\siunitx_unit_options_apply:n`.

```
\l_siunitx_unit_font_tl
```

The font function which is applied to the text of units when constructing formatted units: set by `font-command`.

\l_siunitx_unit_fraction_tl

The fraction function which is applied when constructing fractional units: set by **fraction-command**.

\l_siunitx_unit_symbolic_seq

This sequence contains all of the symbolic names defined: these will be in the form of control sequences such as `\kilogram`. The order of the sequence is unimportant. This includes prefixes and powers as well as units themselves.

\l_siunitx_unit_seq

This sequence contains all of the symbolic *unit* names defined: these will be in the form of control sequences such as `\kilogram`. In contrast to `\l_siunitx_unit_symbolic_seq`, it *only* holds units themselves

3 Per-unit options

\siunitx_unit_options_apply:n \siunitx_unit_options_apply:n <unit(s)>

Applies any unit-specific options set up using `\siunitx_declare_unit:Nnn`. This allows there use outside of unit formatting, for example to influence spacing in quantities. The options are applied only once at a given group level, which allows for user over-ride *via* `\keys_set:nn { siunitx } { ... }`.

4 Units in (PDF) strings

\siunitx_unit_pdfstring_context: \group_begin: \siunitx_unit_pdfstring_context: <Expansion context> <units> \group_end:

Sets symbol unit macros to generate text directly. This is needed in expansion contexts where units must be converted to simple text. This function is itself not expandable, so must be using within a surrounding group as show in the example.

5 Pre-defined symbolic unit components

The unit parser is defined to recognise a number of pre-defined units, prefixes and powers, and also interpret a small selection of “generic” symbolic parts.

Broadly, the pre-defined units are those defined by the BIPM in the documentation for the *International System of Units* (SI) [1]. As far as possible, the names given to the command names for units are those used by the BIPM, omitting spaces and using only ASCII characters. The standard symbols are also taken from the same documentation. In the following documentation, the order of the description of units broadly follows the SI Brochure.

`\kilogram` The base units as defined in the SI Brochure [2]. Notice that `\meter` is defined as an alias for `\metre` as the former spelling is common in the US (although the latter is the official spelling).
`\metre`
`\meter`
`\mole`
`\kelvin`
`\candela`
`\second`
`\ampere`

`\gram` The base unit `\kilogram` is defined using an SI prefix: as such the (derived) unit `\gram` is required by the module to correctly produce output for the `\kilogram`.

`\yocto`
`\zepto`
`\atto`
`\femto`
`\pico`
`\nano`
`\micro`
`\milli`
`\centi`
`\deci`
`\deca`
`\deka`
`\hecto`
`\kilo`
`\mega`
`\giga`
`\tera`
`\peta`
`\exa`
`\zetta`
`\yotta`

Prefixes, all of which are integer powers of 10: the powers are stored internally by the module and can be used for conversion from prefixes to their numerical equivalent. These prefixes are documented in Section 3.1 of the SI Brochure.

Note that the `\kilo` prefix is required to define the base `\kilogram` unit. Also note the two spellings available for `\deca`/`\deka`.

```
\becquerel
\degreeCelsius
\coulomb
\farad
\gray
\hertz
\henry
\joule
\katal
\lumen
\lux
\newton
\ohm
\pascal
\radian
\siemens
\sievert
\steradian
\tesla
\volt
\watt
\weber
```

The defined SI units with defined names and symbols, as given in Table 4 of the SI Brochure. Notice that the names of the units are lower case with the exception of \degreeCelsius, and that this unit name includes “degree”.

```
\astronomicalunit
\bel
\dalton
\day
\decibel
\electronvolt
\hectare
\hour
\litre
\liter
\neper
\minute
\tonne
```

Units accepted for use with the SI: here \minute is a unit of time not of plane angle. These units are taken from Table 8 of the SI Brochure.

For the unit \litre, both l and L are listed as acceptable symbols: the latter is the standard setting of the module. The alternative spelling \liter is also given for this unit for US users (as with \metre, the official spelling is “re”).

```
\arcminute
\arcsecond
\degree
```

Units for plane angles accepted for use with the SI: to avoid a clash with units for time, here \arcminute and \arcsecond are used in place of \minute and \second. These units are taken from Table 8 of the SI Brochure.

```
\percent
```

The mathematical concept of percent, usable with the SI as detailed in Section 5.4.7 of the SI Brochure.

```
\square
\cubic
```

```
\square <prefix> <unit>
\cubic <prefix> <unit>
```

Pre-defined unit powers which apply to the next $\langle prefix \rangle / \langle unit \rangle$ combination.

<u>\squared</u>	$\langle \text{prefix} \rangle \langle \text{unit} \rangle \backslash \text{squared}$
<u>\cubed</u>	$\langle \text{prefix} \rangle \langle \text{unit} \rangle \backslash \text{cubed}$
	Pre-defined unit powers which apply to the preceding $\langle \text{prefix} \rangle / \langle \text{unit} \rangle$ combination.
<u>\per</u>	$\backslash \text{per} \langle \text{prefix} \rangle \langle \text{unit} \rangle \langle \text{power} \rangle$
	Indicates that the next $\langle \text{prefix} \rangle / \langle \text{unit} \rangle / \langle \text{power} \rangle$ combination is reciprocal, <i>i.e.</i> raises it to the power -1 . This symbolic representation may be applied in addition to a $\backslash \text{power}$, and will work correctly if the $\backslash \text{power}$ itself is negative. In literal mode $\backslash \text{per}$ will print a slash (“/”).
<u>\cancel</u>	$\backslash \text{cancel} \langle \text{prefix} \rangle \langle \text{unit} \rangle \langle \text{power} \rangle$
	Indicates that the next $\langle \text{prefix} \rangle / \langle \text{unit} \rangle / \langle \text{power} \rangle$ combination should be “cancelled out”. In the parsed output, the entire unit combination will be given as the argument to a function $\backslash \text{cancel}$, which is assumed to be available at a higher level. In literal mode, the same higher-level $\backslash \text{cancel}$ will be applied to the next token. It is the responsibility of the calling code to provide an appropriate definition for $\backslash \text{cancel}$ outside of the scope of the unit parser.
<u>\highlight</u>	$\backslash \text{highlight} \{ \langle \text{color} \rangle \} \langle \text{prefix} \rangle \langle \text{unit} \rangle \langle \text{power} \rangle$
	Indicates that the next $\langle \text{prefix} \rangle / \langle \text{unit} \rangle / \langle \text{power} \rangle$ combination should be highlighted in the specified $\langle \text{color} \rangle$. In the parsed output, the entire unit combination will be given as the argument to a function $\backslash \text{textcolor}$, which is assumed to be available at a higher level. In literal mode, the same higher-level $\backslash \text{textcolor}$ will be applied to the next token. It is the responsibility of the calling code to provide an appropriate definition for $\backslash \text{textcolor}$ outside of the scope of the unit parser.
<u>\of</u>	$\langle \text{prefix} \rangle \langle \text{unit} \rangle \langle \text{power} \rangle \backslash \text{of} \{ \langle \text{qualifier} \rangle \}$
	Indicates that the $\langle \text{qualifier} \rangle$ applies to the current $\langle \text{prefix} \rangle / \langle \text{unit} \rangle / \langle \text{power} \rangle$ combination. In parsed mode, the display of the result will depend upon module options. In literal mode, the $\langle \text{qualifier} \rangle$ will be printed in parentheses following the preceding $\langle \text{unit} \rangle$ and a full-width space.
<u>\raiseto</u>	$\backslash \text{raiseto} \{ \langle \text{power} \rangle \} \langle \text{prefix} \rangle \langle \text{unit} \rangle$
<u>\tothe</u>	$\langle \text{prefix} \rangle \langle \text{unit} \rangle \backslash \text{tothe} \{ \langle \text{power} \rangle \}$
	Indicates that the $\langle \text{power} \rangle$ applies to the current $\langle \text{prefix} \rangle / \langle \text{unit} \rangle$ combination. As shown, $\backslash \text{raiseto}$ applies to the next $\langle \text{unit} \rangle$ whereas $\backslash \text{tothe}$ applies to the preceding unit. In literal mode the $\backslash \text{power}$ will be printed as a superscript attached to the next token ($\backslash \text{raiseto}$) or preceding token ($\backslash \text{tothe}$) as appropriate.

5.1 Key–value options

The options defined by this submodule are available within the `l3keys siunitx` tree.

bracket-unit-denominator

`bracket-unit-denominator = true|false`

Switch to determine whether brackets are added to the denominator part of a unit when printed using inline fractional form (with `per-mode` as `repeated-symbol`, `symbol` or `symbol-or-fraction`). The standard setting is `true`.

<code>extract-mass-in-kilograms</code>	<code>extract-mass-in-kilograms = true false</code>
	Determines whether prefix extraction treats kilograms as a base unit; when set <code>false</code> , grams are used. The standard setting is <code>true</code> .
<code>forbid-literal-units</code>	<code>forbid-literal-units = true false</code>
	Switch which determines if literal units are allowed when parsing is active; does not apply when <code>parse-units</code> is <code>false</code> .
<code>fraction-command</code>	<code>fraction-command = <command></code>
	Command used to create fractional output when <code>per-mode</code> is set to <code>fraction</code> . The standard setting is <code>\frac</code> .
<code>inter-unit-product</code>	<code>inter-unit-product = <separator></code>
	Inserted between unit combinations in parsed mode, and used to replace <code>.</code> and <code>~</code> in literal mode. The standard setting is <code>\,.</code> .
<code>parse-units</code>	<code>parse-units = true false</code>
	Determines whether parsing of unit symbols is attempted or literal mode is used directly. The standard setting is <code>true</code> .
<code>per-mode</code>	<code>per-mode = fraction power power-positive-first repeated-symbol symbol symbol-or-fraction</code>
	Selects how the negative powers (<code>\per</code>) are formatted: a choice from the options <code>fraction</code> , <code>power</code> , <code>power-positive-first</code> , <code>repeated-symbol</code> , <code>symbol</code> and <code>symbol-or-fraction</code> . The option <code>fraction</code> generates fractional output when appropriate using the command specified by the <code>fraction-command</code> option. The setting <code>power</code> uses reciprocal powers leaving the units in the order of input, while <code>power-positive-first</code> uses the same display format but sorts units such that the positive powers come before negative ones. The <code>symbol</code> setting uses a symbol (specified by <code>per-symbol</code>) between positive and negative powers, while <code>repeated-symbol</code> uses the same symbol but places it before <i>every</i> unit with a negative power (this is mathematically “wrong” but often seen in real work). Finally, <code>symbol-or-fraction</code> acts like <code>symbol</code> for inline output and like <code>fraction</code> when the output is used in a display math environment. The standard setting is <code>power</code> .
<code>per-symbol</code>	<code>per-symbol = <symbol></code>
	Specifies the symbol to be used to denote negative powers when the option <code>per-mode</code> is set to <code>repeated-symbol</code> , <code>symbol</code> or <code>symbol-or-fraction</code> . The standard setting is <code>/</code> .
<code>qualifier-mode</code>	<code>qualifier-mode = bracket combine phrase subscript</code>
	Selects how qualifiers are formatted: a choice from the options <code>bracket</code> , <code>combine</code> , <code>phrase</code> and <code>subscript</code> . The option <code>bracket</code> wraps the qualifier in parenthesis, <code>combine</code> joins the qualifier with the unit directly, <code>phrase</code> joins the material using <code>qualifier-phrase</code> as a link, and <code>subscript</code> formats the qualifier as a subscript. The standard setting is <code>subscript</code> .
<code>qualifier-phrase</code>	<code>qualifier-phrase = <phrase></code>
	Defines the <code><phrase></code> used when <code>qualifier-mode</code> is set to <code>phrase</code> .

sticky-per `sticky-per = true|false`

Used to determine whether `\per` should be applied one a unit-by-unit basis (when `false`) or should apply to all following units (when `true`). The latter mode is somewhat akin conceptually to the TeX `\over` primitive. The standard setting is `false`.

unit-font-command `unit-font-command = <command>`

Command applied to text during output of units: should be command usable in math mode for font selection. Notice that in a typical unit this does not (necessarily) apply to all output, for example powers or brackets. The standard setting is `\mathrm`.

References

- [1] *The International System of Units (SI)*, <https://www.bipm.org/en/measurement-units/>.
- [2] *SI base units*, <https://www.bipm.org/en/measurement-units/si-base-units>.

Part X

siunitx-abbreviations – Abbreviations

\A Abbreviations for currents.

\pA
\nA
\uA
\mA
\kA

\fg Abbreviations for masses.

\pg
\ng
\ug
\mg
\g
\kg

\K Abbreviations for temperature.

\m Abbreviations for lengths.

\pm
\nm
\um
\mm
\cm
\dm
\km

\s Abbreviations for times.

\as
\fs
\ps
\ns
\us
\ms

\Hz Abbreviations for frequencies.

\mHz
\kHz
\MHz
\GHz
\THz

\mol Abbreviations for moles.

\fmol
\pmol
\nmol
\umol
\mmol
\kmol

\V Abbreviations for potentials.

\pV
\nV
\uV
\mV
\kV

\hl Abbreviations for volumes.

\l
\ml
\ul
\hL
\L
\mL
\uL

\W Abbreviations for powers.

\uW
\mW
\kW
\MW
\GW

\kJ Abbreviations for energies.

\J
\mJ
\uJ
\eV
\meV
\keV
\MeV
\GeV
\TeV

\N Abbreviations for forces.

\mN
\kN
\MN

\Pa Abbreviations for pressures.

\kPa

\MPa

\GPa

\mohm Abbreviations for resistance.

\kohm

\Mohm

\F Abbreviations for capacitance.

\fF

\pF

\nF

\uF

\dB Abbreviation for decibel.

\kWh Abbreviation for kilowatt-hours.

Part XI

siunitx-binary – Binary units

This submodule provides binary units and prefixes. These are not formally part of the SI but are recommended by BIPM as units of information.

\kibi Prefixes, all of which are integer powers of 2: the powers are *not* stored or available for conversion.

\mebi
\gibi
\tebi
\pebi
\exbi
\zebi
\yobi

\bit Units for bits and bytes.
\byte

Part XII

siunitx-command – Units as document command

This submodule provides support for creating free-standing document commands for unit macros.

1 Creating units as document commands

`\siunitx_command_create:`

Maps over the list of known unit commands and creates the appropriate document command to support them, as controlled by the options below.

1.1 Key-value options

The options defined by this submodule are available within the `\I3keys siunitx` tree.
These options are all preamble-only.

`free-standing-units`

`free-standing-units = true|false`

Switch to determine whether free standing document commands are created for symbolic units. This will include not only units themselves but also prefixes, *etc.* The standard setting is `false`.

`overwrite-commands`

`overwrite-commands = true|false`

Switch to determine whether when creating free standing document commands, any existing document commands are overwritten. The standard setting is `false`.

`space-before-unit`

`space-before-unit = true|false`

Switch to determine whether a space is inserted before free standing document commands. The standard setting is `false`.

`unit-optional-argument`

`unit-optional-argument = true|false`

Switch to determine whether free standing document commands take an optional argument (a number). The standard setting is `false`.

`use-xspace`

`use-xspace = true|false`

Switch to determine whether free standing document commands use the `xparse` package to insert space after the command names. The standard setting is `false`. When set `true`, the `xparse` package will be loaded at the start of the document if not already available.

Part XIII

siunitx-emulation – Emulation

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols		
\,	<i>15, 19</i>	\day
		\dB
		\deca
		\deci
		\decibel
		\degree
		\degreeCelsius
		\deka
		\dm
		drop-exponent
		drop-uncertainty
		drop-zero-decimal
		E
		\electronvolt
		\ensuremath
		\eV
		evaluate-expression
		\exa
		\exbi
		exponent-base
		exponent-mode
		exponent-product
		expression
		extract-mass-in-kilograms
		F
		\F
		\familydefault
		\farad
		\femto
		\fF
		\fg
		fill-angle-degrees
		fill-angle-minutes
		fill-angle-seconds
		fixed-exponent
		\fmol
		\fontfamily
		\fontseries
		\fontshape
		forbid-literal-units
		fp commands:
		\l_tmpa_fp
		\frac
		fraction-command
		free-standing-units
		\fs
		D
		\dalton

G			
\g	28	\kilo	23
\ge	6	\kilogram	23
\GeV	29	\kJ	29
\gg	6	\km	28
\GHz	28	\kmol	29
\gibi	31	\kohm	30
\giga	23	\kPa	30
\GPa	30	\kV	29
\gram	23	\kW	29
\gray	24	\kWh	30
group commands:			
\group_begin:	22		L
\group_end:	22	\L	29
group-digits	9	\l	29
group-minimum-digits	9	\le	6
group-separator	9	list-exponents	4
\GW	29	list-final-separator	4
		list-pair-separator	4
		list-separator	4
H			
\hectare	24	list-units	4
\hecto	23	\liter	24
\henry	24	\litre	24
\hertz	24	\ll	6
\highlight	25	locale	5
\hL	29	\lumen	24
\hl	29	\lux	24
\hour	24		M
\Hz	28		
I			
\ignorespaces	17	\m	28
input-close-uncertainty	9	\mA	28
input-comparators	9	\mathchoice	19
input-decimal-markers	9	\mathrm	12, 19
input-digits	9	\mathversion	12–14
input-exponent-markers	9	\mbox	12, 19
input-open-uncertainty	9	\mdseries	13
input-signs	9	\mebi	31
input-uncertainty-signs	9	\mega	23
inter-unit-product	26	\meter	23
		\metre	23, 24
		\MeV	29
		\meV	29
J			
\J	29	\mg	28
\joule	24	\MHz	28
		\mHz	28
K			
\K	28	\micro	23
\kA	28	\milli	23
\katal	24	minimum-decimal-digits	10
\kelvin	23	minimum-integer-digits	10
\keV	29	\minute	24
\kg	28	\mJ	29
\kHz	28	\mL	29
\kibi	31	\ml	29
		\mm	28

\mmol	29	\pg	28
\MN	29	\pico	23
\mN	29	\pm	6, 28
mode	13	\pmol	29
\Mohm	30	\power	25
\mohm	30	prefix-mode	15
\mol	29	print-implicit-plus	10
\mole	23	print-unity-mantissa	10
\mp	6	print-zero-exponent	10
\MPa	30	product-exponents	4
\ms	28	product-mode	4
\mV	29	product-phrase	4
\MW	29	product-symbol	4
\mW	29	propagate-math-font	13
		\ps	28
		\pV	29
N			
\N	29		
\nA	28	Q	
\nano	23	qualifier-mode	26
negative-color	10	qualifier-phrase	26
\neper	24	quantity-product	15
\newton	24		
\nF	30	R	
\ng	28	\radian	24
\nm	28	\raiseto	25
\nmol	29	range-exponents	4
\ns	28	range-phrase	4
number-angle-product	2	range-units	4
number-color	13	reset-math-version	13
number-mode	13	reset-text-family	13
\nV	29	reset-text-series	13
		reset-text-shape	13
O			
\of	25	retain-explicit-plus	10
\ohm	24	retain-zero-uncertainty	10
output-close-uncertainty	10	\rmfamily	13
output-decimal-marker	10	round-half	10
output-open-uncertainty	10	round-minimum	10
\over	27	round-mode	10
overwrite-commands	32	round-pad	10
		round-precision	10
P			
\Pa	30	\s	28
\pA	28	\second	23, 24
parse-numbers	10	\selectfont	12
parse-units	26	separate-uncertainty-units	15
\pascal	24	series-version-mapping	14
\pebi	31	\seriesdefault	12
\per	25–27	\shapedefault	12
per-mode	26	\siemens	24
per-symbol	26	\sievert	24
\percent	24	siunitx commands:	
\peta	23	\siunitx_angle:n	1
\pF	30	\siunitx_angle:nnn	1
S			

\l_siunitx_bracket_ambiguous_-		\siunitx_quantity:nn	15
bool	8	\siunitx_quantity_list:nn	3
\siunitx_cell_begin:w	17	\siunitx_quantity_print:nn	15
\siunitx_cell_end:	17	\siunitx_quantity_product:nn	3
\siunitx_command_create:	32	\siunitx_quantity_range:nnn	3
\siunitx_compound_number:n	3	\l_siunitx_range_phrase_tl	4
\siunitx_compound_quantity:nn	3	\l_siunitx_unit_font_tl	21
\siunitx_declare_power>NNn	21	\siunitx_unit_format:nn	15, 19, 20
\siunitx_declare_prefix:Nn	21	\siunitx_unit_format_combine_-	
\siunitx_declare_prefix:Nnn	21	exponent:nnN	20
\siunitx_declare_qualifier:Nn	21	\siunitx_unit_format_extract_-	
\siunitx_declare_unit:Nn	21	prefixes:nNN	20
\siunitx_declare_unit:Nnn	21, 22	\siunitx_unit_format_multiply:nnN	
\siunitx_format_number:nN	1	20
\siunitx_if_number:nTF	8	\siunitx_unit_format_multiply_-	
\siunitx_if_number_p:n	8	combine_exponent:nnmN	20
\siunitx_if_number_token:NTF	8	\siunitx_unit_format_multiply_-	
\l_siunitx_list_separator_final_-		extract_prefixes:nnNN	20
tl	3	\l_siunitx_unit_fraction_tl	22
\l_siunitx_list_separator_pair_-		\siunitx_unit_options_apply:n	21, 22
tl	3	\siunitx_unit_pdfstring_context:	22
\l_siunitx_list_separator_tl	3	\l_siunitx_unit_seq	22
\siunitx_number_adjust_exponent:Nn		\l_siunitx_unit_symbolic_seq	22
.....	7	space-before-unit	32
\siunitx_number_adjust_exponent:nn		\square	24
.....	7	\squared	25
\l_siunitx_number_comparator_tl	8	\steradian	24
\l_siunitx_number_exponent_tl	8	sticky-per	27
\siunitx_number_format:nN	7	\symoperators	12
\l_siunitx_number_input_decimal_-			T
tl	8	table-align-comparator	17
\siunitx_number_list:nn	3	table-align-exponent	17
\siunitx_number_normalize_-		table-align-text-after	17
symbols:N	8	table-align-text-before	17
\siunitx_number_output:N	7	table-align-uncertainty	17
\siunitx_number_output:n	7	table-alignment	18
\siunitx_number_output:NN	6, 7	table-alignment-mode	18
\siunitx_number_output:nN	7	table-auto-round	18
\l_siunitx_number_output_-		table-column-width	18
decimal_tl	8	table-fixed-width	18
\siunitx_number_parse:nN	6, 7, 15, 17	table-format	18
\l_siunitx_number_parse_bool	7, 8	table-number-alignment	18
\siunitx_number_process:N	7	table-text-alignment	18
\siunitx_number_process:NN	7	\tebi	31
\siunitx_number_product:n	3	\tera	23
\siunitx_number_range:nn	3	\tesla	24
\l_siunitx_number_sign_tl	8	\TeV	29
\siunitx_prin_number:n	13	\text	12
\siunitx_print_...:n	12-14	text-family-to-math	14
\siunitx_print_match:n	12	text-font-command	14
\siunitx_print_math:n	12	text-series-to-math	14
\siunitx_print_number:n	12	\textcenteredperiod	12
\siunitx_print_text:n	12	\textcolor	12-14, 19, 25
\siunitx_print_unit:n	12, 15		

\textminus	12	unit-mode	14
\textpm	12	unit-optional-argument	32
\textsubscript	12	\upshape	13
\textsuperscript	12	\us	28
\texttimes	12	use-xspace	32
\THz	28	\uV	29
tight-spacing	10	\uW	29
\times	6		
tl commands:		V	
\l_tmpa_tl	19, 20	\V	29
\tonne	24	\volt	24
\tothe	25		
U		W	
\uA	28	\W	29
\uF	30	\watt	24
\ug	28	\weber	24
\uJ	29		
\uL	29	Y	
\uL	29	\yobi	31
\um	28	\yocto	23
\umol	29	\yotta	23
uncertainty-mode	11		
uncertainty-separator	11	Z	
unit-color	14	\zebi	31
unit-font-command	27	\zepto	23
		\zetta	23