

Tabularray: Typeset Tabulars and Arrays with \LaTeX 3

Jianrui Lyu (tolvjr@163.com)

Version 2021L (2021-07-01)

<https://github.com/lvjr/tabularray>

Contents

1	Overview of Features	2
1.1	Vertical Space	2
1.2	Multiline Cells	3
1.3	Cell Alignment	3
1.4	Multirow Cells	4
1.5	Multi Rows and Columns	5
1.6	Column Types	6
1.7	Row Types	7
1.8	Hlines and Vlines	7
1.9	Colorful Tables	8
1.10	New Table Commands	9
2	The Old Interfaces	10
2.1	Hline Commands	10
2.2	Cell Commands	11
2.3	Row Commands	11
2.4	Column Types	12
2.5	Row Types	12
3	The New Interfaces	13
3.1	Hlines and Vlines	13
3.2	Cells and Spancells	15
3.3	Rows and Columns	16
3.4	The Whole Table	18
3.5	Default Specifications	21
3.6	Counters and Lengths	21
3.7	Tracing Tabularray	22
4	Use Long Tables	23
4.1	A Simple Example	23
4.2	Customize Templates	27
4.3	Change Styles	30
4.4	Define Themes	31
5	Use Some Libraries	32
5.1	Library <code>booktabs</code>	32
5.2	Library <code>diagbox</code>	32
5.3	Library <code>siunitx</code>	33
6	The Source Code	34

Chapter 1

Overview of Features

1.1 Vertical Space

After loading `tabularray` package in the preamble, we can use `tblr` environments to typeset tabulars and arrays. The name `tblr` is short for `tabularray` or `top-bottom-left-right`. The following is our first example:

```
\begin{tabular}{lccr}
\hline
Alpha & Beta & Gamma & Delta \\
\hline
Epsilon & Zeta & Eta & Theta \\
\hline
Iota & Kappa & Lambda & Mu \\
\hline
\end{tabular}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

```
\begin{tblr}{lccr}
\hline
Alpha & Beta & Gamma & Delta \\
\hline
Epsilon & Zeta & Eta & Theta \\
\hline
Iota & Kappa & Lambda & Mu \\
\hline
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

You may notice that there is extra space above and below the table rows with `tblr` environment. This space makes the table look better. If you don't like it, you could use `\SetTblrInner` command:

```
\SetTblrInner{rowsep=0pt}
\begin{tblr}{lccr}
\hline
Alpha & Beta & Gamma & Delta \\
\hline
Epsilon & Zeta & Eta & Theta \\
\hline
Iota & Kappa & Lambda & Mu \\
\hline
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

But in many cases, this `rowsep` is useful:

```

 $\begin{array}{rrr}
\hline
\frac{2}{3} & \frac{2}{3} & \frac{1}{3} \\
\frac{2}{3} & -\frac{1}{3} & -\frac{2}{3} \\
\frac{1}{3} & -\frac{2}{3} & \frac{2}{3} \\
\hline
\end{array}$ 

```

$\frac{2}{3}$	$\frac{2}{3}$	$\frac{1}{3}$
$\frac{2}{3}$	$-\frac{1}{3}$	$-\frac{2}{3}$
$\frac{1}{3}$	$-\frac{2}{3}$	$\frac{2}{3}$
$\frac{2}{3}$	$-\frac{2}{3}$	$\frac{2}{3}$

```

 $\begin{tblr}{rrr}
\hline
\frac{2}{3} & \frac{2}{3} & \frac{1}{3} \\
\frac{2}{3} & -\frac{1}{3} & -\frac{2}{3} \\
\frac{1}{3} & -\frac{2}{3} & \frac{2}{3} \\
\hline
\end{tblr}$ 

```

$\frac{2}{3}$	$\frac{2}{3}$	$\frac{1}{3}$
$\frac{2}{3}$	$\frac{2}{3}$	$\frac{1}{3}$
$\frac{2}{3}$	$-\frac{1}{3}$	$-\frac{2}{3}$
$\frac{1}{3}$	$-\frac{2}{3}$	$\frac{2}{3}$
$\frac{1}{3}$	$-\frac{2}{3}$	$\frac{2}{3}$

Note that you can use `tblr` in both text and math modes.

1.2 Multiline Cells

It's quite easy to write multiline cells without fixing the column width in `tblr` environments: just enclose the cell text with braces and use `\\` to break lines:

```

 $\begin{tblr}{|l|c|r|}
\hline
Left & {Center \\ Cent \\ C} & {Right \\ R} \\
\hline
{L \\ Left} & {C \\ Cent \\ Center} & R \\
\hline
\end{tblr}$ 

```

Left	Center Cent C	Right R
L Left	C Cent Center	R

1.3 Cell Alignment

From time to time, you may want to specify the horizontal and vertical alignment of cells at the same time. `Tabulararray` package provides a `Q` column for this (In fact, `Q` column is the only primitive column, other columns are defined as `Q` columns with some options):

```

 $\begin{tblr}{|Q[l,t]|Q[c,m]|Q[r,b]|}
\hline
{Top Baseline \\ Left Left} & Middle Center & {Right Right \\ Bottom Baseline} \\
\hline
\end{tblr}$ 

```

Top Baseline Left Left	Middle Center	Right Right Bottom Baseline
---------------------------	---------------	--------------------------------

Note that you can use more meaningful `t` instead of `p` for top baseline alignment. For some users who are familiar with word processors, these `t` and `b` columns are counter-intuitive. In `tabulararray` package, there are another two column types `h` and `f`, which will align cell text at row head and row foot, respectively:

```

\begin{tblr}{Q[h,4em]Q[t,4em]Q[m,4em]Q[b,4em]Q[f,4em]}
\hline
{row\head} & {top\line} & {middle} & {line\bottom} & {row\foot} \\
\hline
{row\head} & {top\line} & {11\22\mid\44\55} & {line\bottom} & {row\foot} \\
\hline
\end{tblr}

```

row			line	
head	top	middle	bottom	row
	line			foot
row		11		
head		22	line	
	top	mid	bottom	
	line	44		row
		55		foot

1.4 Multirow Cells

The above `h` and `f` columns are necessary for multirow cells. In `tabulararray`, the `t` and `b` in the optional argument of `\multirow` commands will be treated as `h` and `f`, respectively:

```

\begin{tabular}{|l|l|l|l|}
\hline
\multirow[t]{4}{1.5cm}{Multirow Cell One} & Alpha & & \\
\multirow[b]{4}{1.5cm}{Multirow Cell Two} & Alpha & & \\
& Beta & & Beta \\
& Gamma & & Gamma \\
& Delta & & Delta \\
\hline
\end{tabular}

```

Multirow Cell One	Alpha Beta Gamma Delta		Alpha Beta Gamma Delta
		Multirow Cell Two	

```

\begin{tblr}{|l|l|l|l|}
\hline
\multirow[t]{4}{1.5cm}{Multirow Cell One} & Alpha & & \\
\multirow[b]{4}{1.5cm}{Multirow Cell Two} & Alpha & & \\
& Beta & & Beta \\
& Gamma & & Gamma \\
& Delta & & Delta \\
\hline
\end{tblr}

```

Multirow Cell One	Alpha Beta Gamma Delta		Alpha Beta Gamma Delta
		Multirow Cell Two	

Note that you don't need to load `multirow` package first, since `tabulararray` doesn't depend on it. Furthermore, `tabulararray` will always typeset decent multirow cells. First, it will set correct vertical `c` alignment, even though some rows have large height:

```

\begin{tabular}{|l|m{4em}|}
\hline
\multirow[c]{4}{1.5cm}{Multirow} & Alpha \\
& Beta \\
& Gamma \\
& Delta Delta Delta \\
\hline
\end{tabular}

```

Multirow	Alpha
	Beta
	Gamma
	Delta

```

\begin{tblr}{|l|m{4em}|}
\hline
\multirow[c]{4}{1.5cm}{Multirow} & Alpha \\
& Beta \\
& Gamma \\
& Delta Delta Delta \\
\hline
\end{tblr}

```

Multirow	Alpha
	Beta
	Gamma
	Delta

Second, it will enlarge row heights if the multirow cells have large height, therefore it always avoids vertical overflow:

```

\begin{tabular}{|l|m{4em}|}
\hline
\multirow[c]{2}{1cm}{Line \\ Line \\ Line \\ Line} & Alpha \\
\cline{2-2}
& Beta \\
\hline
\end{tabular}

```

Line	Alpha
Line	Beta
Line	
Line	

```

\begin{tblr}{|l|m{4em}|}
\hline
\multirow[c]{2}{1cm}{Line \\ Line \\ Line \\ Line} & Alpha \\
\cline{2}
& Beta \\
\hline
\end{tblr}

```

Line	Alpha
Line	
Line	Beta
Line	

1.5 Multi Rows and Columns

It was a hard job to typeset cells with multiple rows and multiple columns. For example:

```

\begin{tabular}{|c|c|c|c|c|}
\hline
\multirow{2}{*}{2 Rows}
& \multicolumn{2}{c|}{2 Columns}
& \multicolumn{2}{c|}{\multirow{2}{*}{2 Rows 2 Columns}} \\
\cline{2-3}
& 2-2 & 2-3 & \multicolumn{2}{c|}{} \\
\hline
3-1 & 3-2 & 3-3 & 3-4 & 3-5 \\
\hline
\end{tabular}

```

2 Rows	2 Columns		2 Rows 2 Columns	
	2-2	2-3		
3-1	3-2	3-3	3-4	3-5

With `tabularray` package, you can set spanned cells with `\SetCell` command: within the optional argument of `\SetCell` command, option `r` is for rowspan number, and `c` for colspan number; within the

mandatory argument of it, horizontal and vertical alignment options are accepted. Therefore it's much simpler to typeset spanned cells:

```
\begin{tblr}{|c|c|c|c|c|}
\hline
\SetCell[r=2]{c} 2 Rows
& \SetCell[c=2]{c} 2 Columns
& & \SetCell[r=2,c=2]{c} 2 Rows 2 Columns & \\
\hline
& 2-2 & 2-3 & & \\
\hline
3-1 & 3-2 & 3-3 & 3-4 & 3-5 \\
\hline
\end{tblr}
```

2 Rows	2 Columns		2 Rows 2 Columns	
	2-2	2-3		
3-1	3-2	3-3	3-4	3-5

Using `\multicolumn` command, the omitted cells **must** be removed. On the contrary, using `\multirow` command, the omitted cells **must not** be removed. `\SetCell` command behaves the same as `\multirow` command in this aspect.

With `tblr` environment, any `\hline` segments inside a spanned cell will be ignored, therefore we're free to use `\hline` in the above example. Also, any omitted cell will definitely be ignored when typesetting, no matter it's empty or not. With this feature, we could put row and column numbers into the omitted cells, which will help us to locate cells when the tables are rather complex:

```
\begin{tblr}{|l|l|c|rr|}
\hline
\SetCell[r=3,c=2]{h} r=3 c=2 & 1-2 & \SetCell[r=2,c=3]{r} r=2 c=3 & 1-4 & 1-5 \\
2-1 & 2-2 & 2-3 & 2-4 & 2-5 \\
\hline
3-1 & 3-2 & MIDDLE & \SetCell[r=3,c=2]{f} r=3 c=2 & 3-5 \\
\hline
\SetCell[r=2,c=3]{l} r=2 c=3 & 4-2 & 4-3 & 4-4 & 4-5 \\
5-1 & 5-2 & 5-3 & 5-4 & 5-5 \\
\hline
\end{tblr}
```

r=3 c=2	r=2 c=3	
	MIDDLE	
r=2 c=3		r=3 c=2

1.6 Column Types

`Tabularray` package supports all normal column types, as well as the extendable `X` column type, which first occurred in `tabularx` package and was largely improved by `tabu` package:

```
\begin{tblr}{|X[2,1]|X[3,1]|X[1,r]|X[r]|}
\hline
Alpha & Beta & Gamma & Delta \\
\hline
\end{tblr}
```

Alpha	Beta	Gamma	Delta
-------	------	-------	-------

Also, `X` columns with negative coefficients are possible:

```
\begin{tblr}{|X[2,1]|X[3,1]|X[-1,r]|X[r]|}
\hline
Alpha & Beta & Gamma & Delta \\
\hline
\end{tblr}
```

Alpha	Beta	Gamma	Delta
-------	------	-------	-------

We need the width to typeset a table with X columns. If unset, the default is `\linewidth`. To change the width, we have to first put all column specifications into `colspec={...}`:

```
\begin{tblr}{width=0.8\linewidth,colspec={|X[2,1]|X[3,1]|X[-1,r]|X[r]|}}
\hline
Alpha & Beta & Gamma & Delta \\
\hline
\end{tblr}
```

Alpha	Beta	Gamma	Delta
-------	------	-------	-------

You can define new column types with `\NewColumnType` command. For example, in `tabularray` package, `b` and `X` columns are defined as special `Q` columns:

```
\NewColumnType{b}[1]{Q[b,wd=#1]}
\NewColumnType{X}[1]{}{Q[co=1,#1]}
```

1.7 Row Types

Now that we have column types and `colspec` option, you may ask for row types and `rowspec` option. Yes, they are here:

```
\begin{tblr}{colspec={Q[1]Q[c]Q[r]},rowspec={|Q[t]|Q[m]|Q[b]|}}
{Alpha \\ Alpha} & Beta & & Gamma \\
Delta & & Epsilon & {Zeta \\ Zeta} \\
Eta & & {Theta \\ Theta} & Iota \\
\end{tblr}
```

Alpha	Beta	Gamma
Alpha		
Delta	Epsilon	Zeta
		Zeta
	Theta	
Eta	Theta	Iota

Same as column types, `Q` is the only primitive row type, and other row types are defined as `Q` types with different options. It's better to specify horizontal alignment in `colspec`, and vertical alignment in `rowspec`, respectively.

Inside `rowspec`, `|` is the `hline` type. Therefore we need not to write `\hline` command, which makes table code cleaner.

1.8 Hlines and Vlines

Hlines and vlines have been improved too. You can specify the widths and styles of them:

```

\begin{tblr}{|l|[dotted]|2pt|c|r|[solid]| [dashed] |}
\hline
One & Two & Three \\
\hline\hline[dotted]\hline
Four & Five & Six \\
\hline[dashed]\hline[1pt]
Seven & Eight & Nine \\
\hline
\end{tblr}

```

One	Two	Three
Four	Five	Six
Seven	Eight	Nine

1.9 Colorful Tables

To add colors to your tables, you need to load `xcolor` package first. `Tabularray` package will also load `ninecolors` package for proper color contrast. First you can specify background option for `Q` rows/columns inside `rowspec/colspec`:

```

\begin{tblr}{colspec={lcr},rowspec={|Q[cyan7]|Q[azure7]|Q[blue7]|}}
Alpha & Beta & Gamma \\
Epsilon & Zeta & Eta \\
Iota & Kappa & Lambda \\
\end{tblr}

```

Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda

```

\begin{tblr}{colspec={Q[1,brown7]Q[c,yellow7]Q[r,olive7]},rowspec={|Q|Q|Q|}}
Alpha & Beta & Gamma \\
Epsilon & Zeta & Eta \\
Iota & Kappa & Lambda \\
\end{tblr}

```

Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda

Also you can use `\SetRow` or `\SetColumn` command to specify row or column colors:

```

\begin{tblr}{colspec={lcr},rowspec={|Q|Q|Q|}}
\SetRow{cyan7} Alpha & Beta & Gamma \\
\SetRow{azure7} Epsilon & Zeta & Eta \\
\SetRow{blue7} Iota & Kappa & Lambda \\
\end{tblr}

```

Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda

```

\begin{tblr}{colspec={lcr},rowspec={|Q|Q|Q|}}
\SetColumn{brown7}
Alpha & \SetColumn{yellow7}
Beta & \SetColumn{olive7}
Gamma \\
Epsilon & Zeta & Eta \\
Iota & Kappa & Lambda \\
\end{tblr}

```

Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda

Hlines and vlines can also have colors:

```
\begin{tblr}{colspec={lcr},rowspec={|[2pt,green7]Q|[teal7]Q|[green7]Q|[3pt,teal7]}}
Alpha & Beta & Gamma \\
Epsilon & Zeta & Eta \\
Iota & Kappa & Lambda \\
\end{tblr}
```

Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda

```
\begin{tblr}{colspec={|[2pt,violet5]l|[2pt,magenta5]c|[2pt,purple5]r|[2pt,red5]}}
Alpha & Beta & Gamma \\
Epsilon & Zeta & Eta \\
Iota & Kappa & Lambda \\
\end{tblr}
```

Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda

1.10 New Table Commands

All commands which change the specifications of tables **must** be defined with `\NewTableCommand`. The following example demonstrates how to define similar rules as in `booktabs` package:

```
\NewTableCommand\toprule{\hline[0.08em]}
\NewTableCommand\midrule{\hline[0.05em]}
\NewTableCommand\bottomrule{\hline[0.08em]}
\begin{tblr}{llll}
\toprule
Alpha & Beta & Gamma & Delta \\
\midrule
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
Nu & Xi & Omicron & Pi \\
\bottomrule
\end{tblr}
```

Chapter 2

The Old Interfaces

With `tabularray` package, you can still use improved table commands to change the styles of tables. Same as `tabular` and `array` environments, all table commands **must** be put at the beginning of the cell text. Also, new table commands **must** be defined with `\NewTableCommand`.

2.1 Hline Commands

The `\hline` command has an optional argument which accepts key-value options. The available keys are described in Table 3.1.

```
\begin{tblr}{l1l1l1l1}  
\hline  
Alpha & Beta & Gamma & Delta \\  
\hline[dashed]  
Epsilon & Zeta & Eta & Theta \\  
\hline[dotted]  
Iota & Kappa & Lambda & Mu \\  
\hline[2pt,blue5]  
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

The `\cline` command also has an optional argument which is the same as `\hline`.

```
\begin{tblr}{l1l1l1l1}  
\cline{1-4}  
Alpha & Beta & Gamma & Delta \\  
\cline[dashed]{1,3}  
Epsilon & Zeta & Eta & Theta \\  
\cline[dashed]{2,4}  
Iota & Kappa & Lambda & Mu \\  
\cline[2pt,blue5]{-}  
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

You can use child selectors in the mandatory argument of `\cline`.

```
\begin{tblr}{l1l1l1l1}  
\cline{1-4}  
Alpha & Beta & Gamma & Delta \\  
\cline[dashed]{odd}  
Epsilon & Zeta & Eta & Theta \\  
\cline[dashed]{even}  
Iota & Kappa & Lambda & Mu \\  
\cline[2pt,blue5]{-}  
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

2.2 Cell Commands

The `\SetCell` command has a mandatory argument for setting the styles of current cell. The available keys are described in Table 3.2.

```
\begin{tblr}{l1l1l1}
\hline[1pt]
Alpha & \SetCell{bg=teal2,fg=white} Beta & Gamma & Delta \\
\hline
Epsilon & Zeta & \SetCell{r,font=\scshape} Eta & Theta \\
\hline
Iota & Kappa & Lambda & Mu \\
\hline[1pt]
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	ETA	Theta
Iota	Kappa	Lambda	Mu

The `\SetCell` command also has an optional argument for setting the multispans of current cell. The available keys are described in Table 3.3.

```
\begin{tblr}{|X|X|X|X|X|X|}
\hline
Alpha & Beta & Gamma & Delta & Epsilon & Zeta \\
\hline
\SetCell[c=2]{c} Eta & 2-2
& \SetCell[c=2]{c} Iota & 2-4
& \SetCell[c=2]{c} Lambda & 2-6 \\
\hline
\SetCell[c=3]{1} Nu & 3-2 & 3-3
& \SetCell[c=3]{1} Pi & 3-5 & 3-6 \\
\hline
\SetCell[c=6]{r} Tau & 4-2 & 4-3 & 4-4 & 4-5 & 4-6 \\
\hline
\end{tblr}
```

Alpha	Beta	Gamma	Delta	Epsilon	Zeta
Eta		Iota		Lambda	
Nu			Pi		
Tau					

2.3 Row Commands

The `\SetRow` command has a mandatory argument for setting the styles of current row. The available keys are described in Table 3.4.

```
\begin{tblr}{l1l1l1}
\hline[1pt]
\SetRow{azure8} Alpha & Beta & Gamma & Delta \\
\hline
\SetRow{blue8,c} Epsilon & Zeta & Eta & Theta \\
\hline
\SetRow{violet8} Iota & Kappa & Lambda & Mu \\
\hline[1pt]
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

2.4 Column Types

The `tabularray` package has only one type of primitive column: the `Q` column. Other types of columns are defined as `Q` columns with some keys.

```
\NewColumnType{l}{Q[l]}
\NewColumnType{c}{Q[c]}
\NewColumnType{r}{Q[r]}
\NewColumnType{t}[1]{Q[t,wd=#1]}
\NewColumnType{m}[1]{Q[m,wd=#1]}
\NewColumnType{b}[1]{Q[b,wd=#1]}
\NewColumnType{h}[1]{Q[h,wd=#1]}
\NewColumnType{f}[1]{Q[f,wd=#1]}
\NewColumnType{X}[1][]{Q[co=1,#1]}
```

```
\begin{tblr}{|t{15mm}|m{15mm}|b{20mm}|}
Alpha & Beta & {Gamma\\Gamma} \\
Epsilon & Zeta & {Eta\\Eta} \\
Iota & Kappa & {Lambda\\Lambda} \\
\end{tblr}
```

Alpha	Beta	Gamma Gamma
Epsilon	Zeta	Eta Eta
Iota	Kappa	Lambda Lambda

Any new column type must be defined with `\NewColumnType` command. It can have an optional argument when it's defined.

2.5 Row Types

The `tabularray` package has only one type of primitive row: the `Q` row. Other types of rows are defined as `Q` rows with some keys.

```
\NewRowType{l}{Q[l]}
\NewRowType{c}{Q[c]}
\NewRowType{r}{Q[r]}
\NewRowType{t}[1]{Q[t,ht=#1]}
\NewRowType{m}[1]{Q[m,ht=#1]}
\NewRowType{b}[1]{Q[b,ht=#1]}
\NewRowType{h}[1]{Q[h,ht=#1]}
\NewRowType{f}[1]{Q[f,ht=#1]}
```

```
\begin{tblr}{rowspec={|t{12mm}|m{10mm}|b{10mm}|}}
Alpha & Beta & {Gamma\\Gamma} \\
Epsilon & Zeta & {Eta\\Eta} \\
Iota & Kappa & {Lambda\\Lambda} \\
\end{tblr}
```

Alpha	Beta	Gamma Gamma
Epsilon	Zeta	Eta Eta
Iota	Kappa	Lambda Lambda

Any new row type must be defined with `\NewRowType` command. It can have an optional argument when it's defined.

Chapter 3

The New Interfaces

With `tabularray` package, you can separate style and content totally in tables.

3.1 Hlines and Vlines

All available keys for hlines and vlines are described in Table 3.1.

Table 3.1: Keys for Hlines and Vlines

Key	Description and Values	Initial Value
<code>dash</code>	dash style: <code>solid</code> , <code>dashed</code> or <code>dotted</code>	<code>solid</code>
<code>text</code>	replace hline/vline with text (like <code>!</code> specifier in <code>colspec</code>)	<code>None</code>
<code>wd</code>	rule width dimension	<code>None</code>
<code>fg</code>	rule color name	<code>None</code>

Note: In most cases, you can omit the underlined key names and write only their values.

Options `hlines` and `vlines` are for setting all hlines and vlines, respectively. With empty value, all hlines/vlines will be solid.

```
\begin{tblr}{hlines,vlines}
Alpha & Beta & Gamma & Delta \\
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
Nu & Xi & Omicron & Pi \\
Rho & Sigma & Tau & Upsilon \\
Phi & Chi & Psi & Omega \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi
Rho	Sigma	Tau	Upsilon
Phi	Chi	Psi	Omega

With values inside one pair of braces, all hlines/vlines will be styled.

```
\begin{tblr}{
hlines = {1pt,solid},
vlines = {red3,dashed},
}
Alpha & Beta & Gamma & Delta \\
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
Nu & Xi & Omicron & Pi \\
Rho & Sigma & Tau & Upsilon \\
Phi & Chi & Psi & Omega \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi
Rho	Sigma	Tau	Upsilon
Phi	Chi	Psi	Omega

Another pair of braces before will select segments in all hlines/vlines.

```
\begin{tblr}{
  vlines = {1,3,5}{dashed},
  vlines = {2,4,6}{solid},
}
Alpha & Beta & Gamma & Delta & \\
Epsilon & Zeta & Eta & Theta & \\
Iota & Kappa & Lambda & Mu & \\
Nu & Xi & Omicron & Pi & \\
Rho & Sigma & Tau & Upsilon & \\
Phi & Chi & Psi & Omega & \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi
Rho	Sigma	Tau	Upsilon
Phi	Chi	Psi	Omega

The above example can be simplified with `odd` and `even` values. (More child selectors can be defined with `NewChildSelector` command. Advanced users could read the source code for this.)

```
\begin{tblr}{
  vlines = {odd}{dashed},
  vlines = {even}{solid},
}
Alpha & Beta & Gamma & Delta & \\
Epsilon & Zeta & Eta & Theta & \\
Iota & Kappa & Lambda & Mu & \\
Nu & Xi & Omicron & Pi & \\
Rho & Sigma & Tau & Upsilon & \\
Phi & Chi & Psi & Omega & \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi
Rho	Sigma	Tau	Upsilon
Phi	Chi	Psi	Omega

Another pair of braces before will draw more hlines/vlines (in which `-` stands for all line segments).

```
\begin{tblr}{
  hlines = {1}{-}{dashed},
  hlines = {2}{-}{solid},
}
Alpha & Beta & Gamma & Delta & \\
Epsilon & Zeta & Eta & Theta & \\
Iota & Kappa & Lambda & Mu & \\
Nu & Xi & Omicron & Pi & \\
Rho & Sigma & Tau & Upsilon & \\
Phi & Chi & Psi & Omega & \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi
Rho	Sigma	Tau	Upsilon
Phi	Chi	Psi	Omega

Options `hline{i}` and `vline{j}` are for setting some hlines and vlines, respectively.

```
\begin{tblr}{
  hline{1,7} = {1pt,solid},
  hline{3-5} = {blue3,dashed},
  vline{1,5} = {3-4}{dotted},
}
Alpha & Beta & Gamma & Delta & \\
Epsilon & Zeta & Eta & Theta & \\
Iota & Kappa & Lambda & Mu & \\
Nu & Xi & Omicron & Pi & \\
Rho & Sigma & Tau & Upsilon & \\
Phi & Chi & Psi & Omega & \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi
Rho	Sigma	Tau	Upsilon
Phi	Chi	Psi	Omega

At last we show the usage of `text` key by the following example*:

* Code from <https://tex.stackexchange.com/questions/603023/tabularray-and-tabularx-column-separator>.

```

\begin{tblr}{
  vlines, hlines,
  colspec = {lX[c]X[c]X[c]X[c]},
  vline{2} = {1}{text=\clap{:}},
  vline{3} = {1}{text=\clap{\ch{+}}},
  vline{4} = {1}{text=\clap{\ch{->}}},
  vline{5} = {1}{text=\clap{\ch{+}}},
}
Equation & \ch{CH4} & \ch{2 O2} & \ch{CO2} & \ch{2 H2O} \\
Initial & $n_1$ & $n_2$ & 0 & 0 \\
Final & $n_1 - x$ & $n_2 - 2x$ & $x$ & $2x$ \\
\end{tblr}

```

Equation :	CH ₄	+	2 O ₂	→	CO ₂	+	2 H ₂ O
Initial	n_1		n_2		0		0
Final	$n_1 - x$		$n_2 - 2x$		x		$2x$

You need to load `chemmacros` package for the `\ch` command.

3.2 Cells and Spancells

All available keys for cells are described in Table 3.2 and Table 3.3.

Table 3.2: Keys for the Content of Cells

Key	Description and Values	Initial Value
<u>halign</u>	horizontal alignment: l (left), c (center), or r (right)	l
<u>valign</u>	vertical alignment: t (top), m (middle), b (bottom), h (head) or f (foot)	t
<u>wd</u>	width dimension	None
<u>bg</u>	background color name	None
<u>fg</u>	foreground color name	None
<u>font</u>	font commands	None
<u>preto</u>	prepend text to the cell	None
<u>appto</u>	append text to the cell	None
<u>cmd</u>	execute command for the cell text	None

Note: In most cases, you can omit the underlined key names and write only their values.

Table 3.3: Keys for Multispan of Cells

Key	Description and Values	Initial Value
<u>r</u>	number of rows the cell spans	1
<u>c</u>	number of columns the cell spans	1

Option `cells` is for setting all cells.

```

\begin{tblr}{hlines={white}, cells={c, blue7}}
Alpha & Beta & Gamma & Delta \\
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
Nu & Xi & Omicron & Pi \\
\end{tblr}

```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi

Option `cell{i}{j}` is for setting some cells.

```
\begin{tblr}{
  hlines = {white},
  vlines = {white},
  cell{1,6}{odd} = {teal7},
  cell{1,6}{even} = {green7},
  cell{2,4}{1,4} = {red7},
  cell{3,5}{1,4} = {purple7},
  cell{2}{2} = {r=4,c=2}{c,azure7},
}
Alpha & Beta & Gamma & Delta & \\\
Epsilon & Zeta & Eta & Theta & \\\
Iota & Kappa & Lambda & Mu & \\\
Nu & Xi & Omicron & Pi & \\\
Rho & Sigma & Tau & Upsilon & \\\
Phi & Chi & Psi & Omega & \\\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta		Theta
Iota	Zeta		Mu
Nu	Zeta		Pi
Rho	Zeta		Upsilon
Phi	Chi	Psi	Omega

3.3 Rows and Columns

All available keys for rows and columns are described in Table 3.4 and Table 3.5.

Table 3.4: Keys for Rows

Key	Description and Values	Initial Value
<u>halign</u>	horizontal alignment: <code>l</code> (left), <code>c</code> (center), or <code>r</code> (right)	<code>l</code>
<u>valign</u>	vertical alignment: <code>t</code> (top), <code>m</code> (middle), <code>b</code> (bottom), <code>h</code> (head) or <code>f</code> (foot)	<code>t</code>
<u>ht</u>	height dimension	None
<u>bg</u>	background color name	None
<u>fg</u>	foreground color name	None
<u>font</u>	font commands	None
<u>abovesep</u>	set vertical space above the row	<code>2pt</code>
<u>abovesep+</u>	increase vertical space above the row	None
<u>belowsep</u>	set vertical space below the row	<code>2pt</code>
<u>belowsep+</u>	increase vertical space below the row	None
<u>rowsep</u>	set vertical space above and below the row	<code>2pt</code>
<u>rowsep+</u>	increase vertical space above and below the row	None
<u>preto</u>	prepend text to every cell (like <code>></code> specifier in <code>rowspec</code>)	None
<u>appto</u>	append text to every cell (like <code><</code> specifier in <code>rowspec</code>)	None
<u>cmd</u>	execute command for every cell text	None

Note: In most cases, you can omit the underlined key names and write only their values.

Table 3.5: Keys for Columns

Key	Description and Values	Initial Value
<u>halign</u>	horizontal alignment: <code>l</code> (left), <code>c</code> (center), or <code>r</code> (right)	<code>l</code>
<u>valign</u>	vertical alignment: <code>t</code> (top), <code>m</code> (middle), <code>b</code> (bottom), <code>h</code> (head) or <code>f</code> (foot)	<code>t</code>
<u>wd</u>	width dimension	None

Continued on next page

Table 3.5: Keys for Columns (Continued)

Key	Description and Values	Initial Value
<u>co</u>	coefficient for the extendable column (X column)	None
<u>bg</u>	background color name	None
<u>fg</u>	foreground color name	None
<u>font</u>	font commands	None
<u>leftsep</u>	set horizontal space to the left of the column	6pt
<u>leftsep+</u>	increase horizontal space to the left of the column	None
<u>rightsep</u>	set horizontal space to the right of the column	6pt
<u>rightsep+</u>	increase horizontal space to the right of the column	None
<u>colsep</u>	set horizontal space to both sides of the column	6pt
<u>colsep+</u>	increase horizontal space to both sides of the column	None
<u>preto</u>	prepend text to every cell (like > specifier in <code>colspec</code>)	None
<u>appto</u>	append text to every cell (like < specifier in <code>colspec</code>)	None
<u>cmd</u>	execute command for every cell text	None

Note: In most cases, you can omit the underlined key names and write only their values.

Options `rows` and `columns` are for setting all rows and columns, respectively.

```
\begin{tblr}{
  hlines,
  vlines,
  rows = {7mm},
  columns = {15mm,c},
}
Alpha & Beta & Gamma & Delta \\
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

Options `row{i}` and `column{j}` are for setting some rows and columns, respectively.

```
\begin{tblr}{
  hlines = {1pt,white},
  row{odd} = {blue7},
  row{even} = {azure7},
  column{1} = {purple7,c},
}
Alpha & Beta & Gamma & Delta \\
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
Nu & Xi & Omicron & Pi \\
Rho & Sigma & Tau & Upsilon \\
Phi & Chi & Psi & Omega \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi
Rho	Sigma	Tau	Upsilon
Phi	Chi	Psi	Omega

The following example demonstrates the usages of `bg`, `fg` and `font` keys.

```
\begin{tblr}{
row{odd} = {bg=azure8},
row{1} = {bg=azure3, fg=white, font=\sffamily},
}
Alpha & Beta & & Gamma & \\\
Delta & Epsilon & & Zeta & \\\
Eta & & Theta & & Iota & \\\
Kappa & & Lambda & & Mu & \\\
Nu Xi Omikron & & Pi Rho Sigma & & Tau Upsilon Phi & \\\
\end{tblr}
```

Alpha	Beta	Gamma
Delta	Epsilon	Zeta
Eta	Theta	Iota
Kappa	Lambda	Mu
Nu Xi Omikron	Pi Rho Sigma	Tau Upsilon Phi

The following example demonstrates the usages of `abovesep`, `belowsep`, `leftsep`, `rightsep` keys.

```
\begin{tblr}{
hlines,
vlines,
rows = {abovesep=1pt,belowsep=5pt},
columns = {leftsep=1pt,rightsep=5pt},
}
Alpha & & Beta & & Gamma & & Delta & \\\
Epsilon & & Zeta & & Eta & & Theta & \\\
Iota & & Kappa & & Lambda & & Mu & \\\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

The following example shows that we can replace `\\[dimen]` with `belowsep+` key.

```
\begin{tblr}{
hlines, row{2} = {belowsep+=5pt},
}
Alpha & & Beta & & Gamma & & Delta & \\\
Epsilon & & Zeta & & Eta & & Theta & \\\
Iota & & Kappa & & Lambda & & Mu & \\\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

3.4 The Whole Table

All available keys for the whole table are described in Table 3.6.

Table 3.6: Keys for the Whole Table

Key	Description and Values	Initial Value
<code>rowspec</code>	set row specifications with row type specifiers	None
<code>colspec</code>	set column specifications with column type specifiers	None
<code>width</code>	width of the table with extendable columns	None
<code>rulesep</code>	space between two hlines or vlines	2pt
<code>stretch</code>	stretch ratio for struts added to cell text	1

Continued on next page

Table 3.6: Keys for the Whole Table (Continued)

Key	Description and Values	Initial Value
<code>abovesep</code>	set vertical space above every row	2pt
<code>belowsep</code>	set vertical space below every row	2pt
<code>rowsep</code>	set vertical space above and below every row	2pt
<code>leftsep</code>	set horizontal space to the left of every column	6pt
<code>rightsep</code>	set horizontal space to the right of every column	6pt
<code>colsep</code>	set horizontal space to both sides of every column	6pt
<code>hspan</code>	horizontal span algorithm: <code>default</code> , <code>even</code> , or <code>minimal</code>	<code>default</code>
<code>vspan</code>	vertical span algorithm: <code>default</code> or <code>even</code>	<code>default</code>

The following example demonstrates the usage of `width` key.

```
\begin{tblr}{width=0.8\textwidth, colspec={|l|X[2]|X[3]|X[-1]|}}
Alpha & Beta & Gamma & Delta \\
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

The following example shows that we can replace `\doublerulesep` parameter with `rulesep` key.

```
\begin{tblr}{
colspec={|l|l|l|l|}, rowspec={|QQQ|}, rulesep=4pt,
}
Alpha & Beta & Gamma & Delta \\
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

The following example shows that we can replace `\arraystretch` parameter with `stretch` key.

```
\begin{tblr}{hlines, stretch=1.5}
Alpha & Beta & Gamma & Delta \\
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

The following example uses `rowsep` and `colsep` keys to set padding for all rows and columns.

```
\SetTblrInner{rowsep=2pt, colsep=2pt}
\begin{tblr}{hlines, vlines}
Alpha & Beta & Gamma & Delta \\
Epsilon & Zeta & Eta & Theta \\
Iota & Kappa & Lambda & Mu \\
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu

With `hspan=default` or `hspan=even`, `tabularray` package will compute column widths from span widths. But with `hspan=minimal`, it will compute span widths from column widths. The following examples show the results from different `hspan` values.

```
\SetTblrInner{hlines, vlines, hspan=default}
\begin{tblr}{cell{2}{1}={c=2}{1}, cell{3}{1}={c=3}{1}, cell{4}{2}={c=2}{1}}
  111 111 & 222 222 & 333 333 \\
  12 Multi Columns Multi Columns 12 & & 333 \\
  13 Multi Columns Multi Columns Multi Columns 13 & & \\
  111 & 23 Multi Columns Multi Columns 23 & \\
\end{tblr}
```

111 111	222 222	333 333
12 Multi Columns	Multi Columns 12	333
13 Multi Columns	Multi Columns Multi Columns	13
111	23 Multi Columns	Multi Columns 23

```
\SetTblrInner{hlines, vlines, hspan=even}
\begin{tblr}{cell{2}{1}={c=2}{1}, cell{3}{1}={c=3}{1}, cell{4}{2}={c=2}{1}}
  111 111 & 222 222 & 333 333 \\
  12 Multi Columns Multi Columns 12 & & 333 \\
  13 Multi Columns Multi Columns Multi Columns 13 & & \\
  111 & 23 Multi Columns Multi Columns 23 & \\
\end{tblr}
```

111 111	222 222	333 333
12 Multi Columns	Multi Columns 12	333
13 Multi Columns	Multi Columns Multi Columns	13
111	23 Multi Columns	Multi Columns 23

```
\SetTblrInner{hlines, vlines, hspan=minimal}
\begin{tblr}{cell{2}{1}={c=2}{1}, cell{3}{1}={c=3}{1}, cell{4}{2}={c=2}{1}}
  111 111 & 222 222 & 333 333 \\
  12 Multi Columns Multi Columns 12 & & 333 \\
  13 Multi Columns Multi Columns Multi Columns 13 & & \\
  111 & 23 Multi Columns Multi Columns 23 & \\
\end{tblr}
```

111 111	222 222	333 333
12 Multi Columns	Multi Columns 12	333
13 Multi Columns	Multi Columns Multi Columns	13
111	23 Multi Columns	Multi Columns 23

The following examples show the results from different `vspan` values.

```
\SetTblrInner{hlines, vlines, vspan=default}
\begin{tblr}{column{2}={3.25cm}, cell{2}{2}={r=3}{1}}
  Column1 & Column2 \\
  Row1 & Long text that needs multiple lines.
        Long text that needs multiple lines.
        Long text that needs multiple lines. \\
  Row2 & \\
  Row3 & \\
  Row4 & Short text \\
\end{tblr}
```

Column1	Column2
Row1	Long text that needs multiple lines. Long text that needs multiple lines. Long text that needs multiple lines.
Row2	
Row3	
Row4	Short text

```

\SetTblrInner{hlines, vlines, vspan=even}
\begin{tblr}{column{2}={3.25cm}, cell{2}{2}={r=3}{1}}
  Column1 & Column2 \\
  Row1 & Long text that needs multiple lines.
         Long text that needs multiple lines.
         Long text that needs multiple lines. \\
  Row2 & \\
  Row3 & \\
  Row4 & Short text \\
\end{tblr}

```

Column1	Column2
Row1	Long text that needs multiple lines. Long text that needs multiple lines. Long text that needs multiple lines.
Row2	Long text that needs multiple lines. Long text that needs multiple lines.
Row3	Long text that needs multiple lines.
Row4	Short text

3.5 Default Specifications

Tabularray package provides `\SetTblrInner` and `\SetTblrOuter` commands for you to change the default inner and outer specifications of tables. Inner specifications are all specifications written in the mandatory argument of the `tblr` environment, while outer specifications are all specifications written in the optional argument of the `tblr` environment. At this time, most of the outer specifications are used for long tables (see Chapter 4).

In the below example, the first line draws all `hlines` and `vlines` for all tables created afterwards, while the second line makes all tables created afterwards vertically align at bottom.

```

\SetTblrInner{hlines,vlines}
\SetTblrOuter{valign=b}

```

You can define new `tabularray` environments using `\NewTblrEnviron` command:

```

\NewTblrEnviron{mytblr}
\SetTblrInner[mytblr]{hlines,vlines}
\SetTblrOuter[mytblr]{valign=b}
Text \begin{mytblr}{cccc}
  Alpha & Beta & Gamma & Delta \\
  Epsilon & Zeta & Eta & Theta \\
  Iota & Kappa & Lambda & Mu \\
\end{mytblr} Text

```

	Alpha	Beta	Gamma	Delta	
	Epsilon	Zeta	Eta	Theta	
Text	Iota	Kappa	Lambda	Mu	Text

3.6 Counters and Lengths

Counters `rownum`, `colnum`, `rowcount`, `colcount` can be used in cell text:

```

\begin{tblr}{hlines}
  Cell[\arabic{rownum}][\arabic{colnum}] & Cell[\arabic{rownum}][\arabic{colnum}] &
  Cell[\arabic{rownum}][\arabic{colnum}] & Cell[\arabic{rownum}][\arabic{colnum}] \\
  Row=\arabic{rowcount}, Col=\arabic{colcount} &
  Row=\arabic{rowcount}, Col=\arabic{colcount} &
  Row=\arabic{rowcount}, Col=\arabic{colcount} &
  Row=\arabic{rowcount}, Col=\arabic{colcount} \\
  Cell[\arabic{rownum}][\arabic{colnum}] & Cell[\arabic{rownum}][\arabic{colnum}] &
  Cell[\arabic{rownum}][\arabic{colnum}] & Cell[\arabic{rownum}][\arabic{colnum}] \\
\end{tblr}

```

Cell[1][1]	Cell[1][2]	Cell[1][3]	Cell[1][4]
Row=3, Col=4	Row=3, Col=4	Row=3, Col=4	Row=3, Col=4
Cell[3][1]	Cell[3][2]	Cell[3][3]	Cell[3][4]

Also, lengths `\leftsep`, `\rightsep`, `\abovesep`, `\belowsep` can be used in cell text.

3.7 Tracing Tabularray

To trace internal data behind `tblr` environment, you can use `\SetTblrTracing` command. For example, `\SetTblrTracing{all}` will turn on all tracings, and `\SetTblrTracing{none}` will turn off all tracings. `\SetTblrTracing{+row,+column}` will only tracing row and column data. All tracing messages will be written to the log files.

Chapter 4

Use Long Tables

The interfaces in this chapter should be seen as **experimental** and are likely to change in future releases, if necessary. Don't use them in important documents.

4.1 A Simple Example

In fact, to make a decent long table with header and footer, it is better to separate header/footer as table head/foot (which includes caption, footnotes, continuation text) and row head/foot (which includes some rows of the table that should appear in every page). By this approach, alternating row colors should work as expected.

Table 4.1: A Long Long Long Long Long Long Long Table

Head	Head	Head
Head	Head	Head
Alpha	Beta	Gamma
Epsilon	Zeta ^a	Eta
Iota	Kappa [†]	Lambda
Nu	Xi	Omicron
Rho	Sigma	Tau
Phi	Chi	Psi
Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda
Nu	Xi	Omicron
Rho	Sigma	Tau
Phi	Chi	Psi
Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda
Nu	Xi	Omicron
Rho	Sigma	Tau
Foot	Foot	Foot

Continued on next page

Table 4.1: A Long Long Long Long Long Long Long Table (Continued)

Head	Head	Head
Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda
Nu	Xi	Omicron
Rho	Sigma	Tau
Phi	Chi	Psi
Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda
Nu	Xi	Omicron
Rho	Sigma	Tau
Phi	Chi	Psi
Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda
Nu	Xi	Omicron
Rho	Sigma	Tau
Phi	Chi	Psi
Alpha	Beta	Gamma [*]
Epsilon	Zeta	Eta
Iota	Kappa	Lambda
Nu	Xi	Omicron
Rho	Sigma	Tau
Phi	Chi	Psi
Alpha	Beta	Gamma
Epsilon	Zeta	Eta
Iota	Kappa	Lambda
Nu	Xi	Omicron
Rho	Sigma	Tau
Phi	Chi	Psi
Foot	Foot	Foot

^a It is the first footnote.

[†] It is the second long long long long long long footnote.

Note: Some general note. Some general note. Some general note.

Source: Made up by myself. Made up by myself. Made up by myself.

As you can see in the above example, the appearance of long tables of `tabularray` package is similar to that of `threeparttable` and `threeparttablex` packages. We support table footnotes, but not page footnotes in `tabularray` package.

The source code for the above long table is shown below. It is mainly self-explanatory.

```

\NewTblrTheme{fancy}{
  \SetTblrStyle{firsthead}{font=\bfseries}
  \SetTblrStyle{firstfoot}{fg=blue2}
  \SetTblrStyle{middlefoot}{\itshape}
  \SetTblrStyle{caption-tag}{red2}
}
\begin{longtblr}[
  theme = fancy,
  caption = {A Long Long Long Long Long Long Table},
  entry = {Short Caption},
  label = {tblr:test},
  note{a} = {It is the first footnote.},
  note{${\dag$}} = {It is the second long long long long long long footnote.},
  remark{Note} = {Some general note. Some general note. Some general note.},
  remark{Source} = {Made up by myself. Made up by myself. Made up by myself.},
]{
  colspec = {XXX}, width = 0.85\linewidth,
  row{odd} = {gray9}, row{even} = {brown9}, rowhead = 2, rowfoot = 1,
}
\hline
\SetRow{purple7} Head & Head & Head \\
\hline
\SetRow{purple7} Head & Head & Head \\
\hline
Alpha & Beta & Gamma \\
\hline
Epsilon & Zeta\TblrNote{a} & Eta \\
\hline
Iota & Kappa\TblrNote{${\dag$}} & Lambda \\
\hline
Nu & Xi & Omicron \\
\hline
Rho & Sigma & Tau \\
\hline
Phi & Chi & Psi \\
\hline
.....
\hline
Alpha & Beta & Gamma \\
\hline
Epsilon & Zeta & Eta \\
\hline
Iota & Kappa & Lambda \\
\hline
Nu & Xi & Omicron \\
\hline
Rho & Sigma & Tau \\
\hline
Phi & Chi & Psi \\
\hline
\SetRow{blue7} Foot & Foot & Foot \\
\hline
\end{longtblr}

```

As you can see in the above code, we typeset long tables with `longtblr` environment. And we can totally separate contents and styles of long tables with `tabularray` package.

Row head and row foot consist of some lines of the table and should appear in every page. Their options

are inner specifications and should be put in the mandatory argument of the `longtblr` environment. In the above example, We set `rowhead=2` and `rowfoot=1`.

Table 4.2: Inner Specifications for Row Heads and Row Foots

Key Nama	Key Description	Initial Value
<code>rowhead</code>	number of the first rows of the table appear in every page	0
<code>rowfoot</code>	number of the last rows of the table appear in every page	0

Table head and table foot consist of the caption, continuation text, footnotes and remarks. Their options are outer specifications and should be put in the optional argument of the `longtblr` environment.

Table 4.3: Outer Specifications for Table Heads and Table Foots

Key Nama	Key Description	Initial Value
<code>headsep</code>	vertical space between table head and table body	6pt
<code>footsep</code>	vertical space between table foot and table body	6pt
<code>presep</code>	vertical space between table head and the above text	<code>1.5\bigskipamount</code>
<code>postsep</code>	vertical space between table foot and the below text	<code>1.5\bigskipamount</code>
<code>theme</code>	table theme (including settings for templates and styles)	None
<code>caption</code>	table caption	None
<code>entry</code>	short table caption to be put in List of Tables	None
<code>label</code>	table label	None
<code>note{<name>}</code>	table note with <name> as tag	None
<code>remark{<name>}</code>	table remark with <name> as tag	None

4.2 Customize Templates

4.2.1 Overview of Templates

The template system for table heads and table foots in `tabularray` is largely inspired by `beamer`, `caption` and `longtable` packages. You can use `\DefTblrTemplate` command to define and modify templates, and `\SetTblrTemplate` command to choose default templates. In defining templates, you can include other templates with `\UseTblrTemplate` and `\ExpTblrTemplate` commands.

Table 4.4: Templates for Table Heads and Table Foots

Template Name	Template Description
<code>contfoot-text</code>	continuation text in the foot, normally “Continued on next page”
<code>contfoot</code>	continuation paragraph in the foot, normally including <code>contfoot-text</code> template
<code>conthead-text</code>	continuation text in the head, normally “(Continued)”
<code>conthead</code>	continuation paragraph in the head, normally including <code>conthead-text</code> template
<code>caption-tag</code>	caption tag, normally like “Table 4.2”
<code>caption-sep</code>	caption separator, normally like “: ”
<code>caption-text</code>	caption text, normally using user provided value
<code>caption</code>	including <code>caption-tag</code> + <code>caption-sep</code> + <code>caption-text</code>

Continued on next page

Table 4.4: Templates for Table Heads and Table Foots (Continued)

Template Name	Template Description
note-tag	note tag, normally using user provided value
note-sep	note separator, normally like “ ”
note-text	note tag, normally using user provided value
note	including <code>note-tag</code> + <code>note-sep</code> + <code>note-text</code>
remark-tag	remark tag, normally using user provided value
remark-sep	remark separator, normally like “: ”
remark-text	remark text, normally using user provided value
remark	including <code>remark-tag</code> + <code>remark-sep</code> + <code>remark-text</code>
firsthead	table head on the first page, normally including <code>caption</code> template
middlehead	table head on middle pages, normally including <code>caption</code> and <code>conthead</code> templates
lasthead	table head on the last page, normally including <code>caption</code> and <code>conthead</code> templates
head	setting all of <code>firsthead</code> , <code>middlehead</code> and <code>lasthead</code>
firstfoot	table foot on the first page, normally including <code>contfoot</code> template
middlefoot	table foot on middle pages, normally including <code>contfoot</code> template
lastfoot	table foot on the last page, normally including <code>note</code> and <code>remark</code> templates
foot	setting all of <code>firstfoot</code> , <code>middlefoot</code> and <code>lastfoot</code>

A template which only includes short text is called a sub template. Normally there is one - in the name of a sub template. A template which includes one or more paragraphs is called a main template. Normally there isn't any - in the name of a main template.

4.2.2 Continuation Templates

Let us have a look at the code for defining templates of continuation text first:

```
\DefTblrTemplate{contfoot-text}{normal}{Continued on next page}
\SetTblrTemplate{contfoot-text}{normal}
\DefTblrTemplate{conthead-text}{normal}{(Continued)}
\SetTblrTemplate{conthead-text}{normal}
```

In the above code, command `\DefTblrTemplate` defines the templates with name `normal`, and then command `\SetTblrTemplate` sets the templates with name `normal` as default. The `normal` template is always defined and set as default for any template element in `tabulararray`. Therefore you had better use another name when defining new templates.

If you use `default` as template name in `\DefTblrTemplate`, you define and set it as default at the same time. Therefore the above code can be written in another way:

```
\DefTblrTemplate{contfoot-text}{default}{Continued on next page}
\DefTblrTemplate{conthead-text}{default}{(Continued)}
```

You may modify the code to customize continuation text to fit your needs.

The `contfoot` and `conthead` templates normally include their sub templates with `\UseTblrTemplate` commands. But you can also handle user settings such as horizontal alignment here.

```
\DefTblrTemplate{contfoot}{default}{\UseTblrTemplate{contfoot-text}{default}}
\DefTblrTemplate{conthead}{default}{\UseTblrTemplate{conthead-text}{default}}
```

4.2.3 Caption Templates

Normally a caption consists of three parts, and their templates are defined with the follow code:

```
\DefTblrTemplate{caption-tag}{default}{Table\hspace{0.25em}\thetable}
\DefTblrTemplate{caption-sep}{default}{:\enskip}
\DefTblrTemplate{caption-text}{default}{\InsertTblrText{caption}}
```

The command `\InsertTblrText{caption}` inserts the value of `caption` key, which you could write in the optional argument of `longtblr` environment.

The `caption` template normally includes three sub templates with `\UseTblrTemplate` commands: The `caption` template will be used in `firsthead` template.

```
\DefTblrTemplate{caption}{default}{
  \UseTblrTemplate{caption-tag}{default}
  \UseTblrTemplate{caption-sep}{default}
  \UseTblrTemplate{caption-text}{default}
}
```

Furthermore `capcont` template includes `conthead` template as well. The `capcont` template will be used in `middlehead` and `lasthead` templates.

```
\DefTblrTemplate{capcont}{default}{
  \UseTblrTemplate{caption-tag}{default}
  \UseTblrTemplate{caption-sep}{default}
  \UseTblrTemplate{caption-text}{default}
  \UseTblrTemplate{conthead}{default}
}
```

4.2.4 Note and Remark Templates

The templates for table notes can be defined like this:

```
\DefTblrTemplate{note-tag}{default}{\textsuperscript{\InsertTblrNoteTag}}
\DefTblrTemplate{note-sep}{default}{\space}
\DefTblrTemplate{note-text}{default}{\InsertTblrNoteText}
```

```
\DefTblrTemplate{note}{default}{
  \MapTblrNotes{
    \noindent
    \UseTblrTemplate{note-tag}{default}
    \UseTblrTemplate{note-sep}{default}
    \UseTblrTemplate{note-text}{default}
  }
  \par
}
```

The `\MapTblrNotes` command loops for all table notes, which are written in the optional argument of `longtblr` environment. Inside the loop, you can use `\InsertTblrNoteTag` and `\InsertTblrNoteText` commands to insert current note tag and note text, respectively.

The definition of remark templates are similar to note templates.

```
\DefTblrTemplate{remark-tag}{default}{\InsertTblrRemarkTag}
\DefTblrTemplate{remark-sep}{default}{:\space}
\DefTblrTemplate{remark-text}{default}{\InsertTblrRemarkText}
```

```

\DefTblrTemplate{remark}{default}{
  \MapTblrRemarks{
    \noindent
    \UseTblrTemplate{remark-tag}{default}
    \UseTblrTemplate{remark-sep}{default}
    \UseTblrTemplate{remark-text}{default}
  }
}

```

4.2.5 Head and Foot Templates

The templates for table heads and foots are defined as including other templates:

```

\DefTblrTemplate{firsthead}{default}{
  \UseTblrTemplate{caption}{default}
}
\DefTblrTemplate{middlehead,lasthead}{default}{
  \UseTblrTemplate{capcont}{default}
}
\DefTblrTemplate{firstfoot,middlefoot}{default}{
  \UseTblrTemplate{contfoot}{default}
}
\DefTblrTemplate{lastfoot}{default}{
  \UseTblrTemplate{note}{default}
  \UseTblrTemplate{remark}{default}
}

```

Note that you can define the same template for multiple elements in `\DefTblrTemplate` command.

4.3 Change Styles

You may change the styles of template elements.

```

\SetTblrStyle{firsthead}{font=\bfseries}
\SetTblrStyle{firstfoot}{fg=blue2}
\SetTblrStyle{middlefoot}{\itshape}
\SetTblrStyle{caption-tag}{red2}

```

All available keys for template elements are described in Table 4.5.

Table 4.5: Keys for the Styles of Template Elements

Key Name	Key Description
<u>fg</u>	foreground color
<u>font</u>	font commands
<u>halign</u>	horizontal alignment: l (left), c (center), or r (right)
<u>indent</u>	parindent value
<u>hang</u>	hangindent value

Note: In most cases, you can omit the underlined key names and write only their values. The keys `halign`, `indent` and `hang` are only for main templates.

When you write `\UseTblrTemplate{element}{default}` in defining a template, beside including the code of template `element`, the foreground color and font commands of the template `element` will be set up automatically. In contrast, `\ExpTblrTemplate{element}{default}` will only include template code.

4.4 Define Themes

You may define your own themes for table heads and foots with `\NewTblrTheme` command. a theme consists of some template and style settings. For example:

```
\NewTblrTheme{fancy}{  
  \DefTblrTemplate{conthead}{default}{[[Continued]]}  
  \SetTblrStyle{firsthead}{font=\bfseries}  
  \SetTblrStyle{firstfoot}{fg=blue2}  
  \SetTblrStyle{middlefoot}{\itshape}  
  \SetTblrStyle{caption-tag}{red2}  
}
```

After defining the theme `fancy`, you can use it by writing `theme=fancy` in the optional argument of `longtblr` environment.

Chapter 5

Use Some Libraries

The interfaces in this chapter should be seen as **experimental** and are likely to change in future releases, if necessary. Don't use them in important documents.

The `tabularray` package emulates or fixes some commands in other packages. To avoid potential conflict, you need to enable them with `\UseTblrLibrary` command.

5.1 Library booktabs

When you write `\UseTblrLibrary{booktabs}`, `tabularray` package will define commands `\toprule`, `\midrule`, `\bottomrule` and `\cmidrule` inside `tblr` environment.

```
\begin{tblr}{l1111}  
\toprule  
Alpha & Beta & Gamma & Delta \\  
\midrule  
Epsilon & Zeta & Eta & Theta \\  
\cmidrule{1-3}  
Iota & Kappa & Lambda & Mu \\  
\cmidrule{2-4}  
Nu & Xi & Omicron & Pi \\  
\bottomrule  
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi

At this moment, `trim` options for `\cmidrule` command are not supported. But rule colors are possible just like `\hline` and `\cline` commands.

```
\begin{tblr}{l1111}  
\toprule[purple3]  
Alpha & Beta & Gamma & Delta \\  
\midrule[blue3]  
Epsilon & Zeta & Eta & Theta \\  
\cmidrule[azure3]{1-3}  
Iota & Kappa & Lambda & Mu \\  
\cmidrule[azure3]{2-4}  
Nu & Xi & Omicron & Pi \\  
\bottomrule[purple3]  
\end{tblr}
```

Alpha	Beta	Gamma	Delta
Epsilon	Zeta	Eta	Theta
Iota	Kappa	Lambda	Mu
Nu	Xi	Omicron	Pi

5.2 Library diagbox

When writing `\UseTblrLibrary{diagbox}` in the preamble of the document, `tabularray` package loads `diagbox` package, and you can use `\diagbox` and `\diagboxthree` commands inside `tblr` environment.

```
\begin{tblr}{hlines,vlines}
\diagbox{Aa}{Pp} & Beta & Gamma \\
Epsilon & Zeta & Eta \\
Iota & Kappa & Lambda \\
\end{tblr}
```

	Pp	Beta	Gamma
Aa			
Epsilon	Zeta	Eta	
Iota	Kappa	Lambda	

```
\begin{tblr}{hlines,vlines}
\diagboxthree{Aa}{Pp}{Hh} & Beta & Gamma \\
Epsilon & Zeta & Eta \\
Iota & Kappa & Lambda \\
\end{tblr}
```

Pp	Hh	Beta	Gamma
Aa			
Epsilon	Zeta	Eta	
Iota	Kappa	Lambda	

You can also use `\diagbox` and `\diagboxthree` commands in math mode.

```
$$\begin{tblr}{|c|cc|}
\hline
\diagbox{X_1}{X_2} & 0 & 1 \\
\hline
0 & 0.1 & 0.2 \\
1 & 0.3 & 0.4 \\
\hline
\end{tblr}$$
```

	X_2	0	1
X_1			
0		0.1	0.2
1		0.3	0.4

5.3 Library `siunitx`

When writing `\UseTblrLibrary{siunitx}` in the preamble of the document, `tabularray` package loads `siunitx` package, and defines `S` column for `tblr` environment.

```
\begin{tblr}{
hlines, vlines,
colspec={
S[table-format=2.2]
S[table-format=2.2]
S[table-format=2.2]
}
}
{{{Head}}} & {{{Head}}} & {{{Head}}} \\
11 & 11 & 11 \\
2.1 & 2.2 & 2.3 \\
33.11 & 33.22 & 33.33 \\
\end{tblr}
```

Head	Head	Head
11	11	11
2.1	2.2	2.3
33.11	33.22	33.33

Note that you need to use triple pairs of braces to guard non-numeric cells. If you need to apply other specifications for the `S` columns, you need to move `siunitx` options into `si` keys of the `Q` columns.

```
\begin{tblr}{
hlines, vlines,
colspec={
Q[si={table-format=2.2},blue7]
Q[si={table-format=2.2},teal7]
Q[si={table-format=2.2},purple7]
}
}
{{{Head}}} & {{{Head}}} & {{{Head}}} \\
11 & 11 & 11 \\
2.1 & 2.2 & 2.3 \\
33.11 & 33.22 & 33.33 \\
\end{tblr}
```

Head	Head	Head
11	11	11
2.1	2.2	2.3
33.11	33.22	33.33

Chapter 6

The Source Code

```
%%% % -*- coding: utf-8 -*-
%%% -----
%%% Tabularray: Typeset tabulars and arrays with LaTeX3
%%% Author      : Jianrui Lyu <tolvjr@163.com>
%%% Repository: https://github.com/lvjr/tabularray
%%% License     : The LaTeX Project Public License 1.3
%%% -----

%%% -----
%% \section{Scratch Variables and Function Variants}
%%% -----

\NeedsTeXFormat{LaTeX2e}
\RequirePackage{expl3}
\ProvidesExplPackage{tabularray}{2021-07-01}{2021L}
  {Typeset tabulars and arrays with LaTeX3}

\RequirePackage{xparse}

\AtBeginDocument
{
  \@ifpackageloaded{xcolor}{\RequirePackage{ninecolors}}{}
  \@ifpackageloaded{hyperref}{\hypersetup{pdfborder={0 0 0}}}{ }
}

\ExplSyntaxOn

%% Backport \tl_if_eq:NnTF for old texlive 2020
\cs_if_exist:NF \tl_if_eq:NnTF
{
  \tl_new:N \l__tblr_backport_b_tl
  \prg_new_protected_conditional:Npnn \tl_if_eq:Nn #1 #2 { T, F, TF }
  {
    \group_begin:
      \tl_set:Nn \l__tblr_backport_b_tl {#2}
      \exp_after:wN
    \group_end:
    \if_meaning:w #1 \l__tblr_backport_b_tl
      \prg_return_true:
    \else:
      \prg_return_false:
    \fi:
  }
}
```

```

    }
    \prg_generate_conditional_variant:Nnn \tl_if_eq:Nn { c } { TF, T, F }
  }

%% Compatible with texlive 2020
\cs_if_exist:NF \seq_map_indexed_function:NN
{
  \cs_set_eq:NN \seq_map_indexed_function:NN \seq_indexed_map_function:NN
}

\cs_generate_variant:Nn \msg_error:nmmm { nnVn }
\cs_generate_variant:Nn \prop_item:Nn { Ne, NV }
\cs_generate_variant:Nn \prop_put:Nnn { Nxn, Nxx, NxV }
\cs_generate_variant:Nn \regex_replace_all:NnN { NVN }
\cs_generate_variant:Nn \seq_map_indexed_inline:Nn { cn }
\cs_generate_variant:Nn \tl_const:Nn { ce }
\cs_generate_variant:Nn \tl_log:n { x }
\cs_generate_variant:Nn \tl_gput_right:Nn { Nf }
\prg_generate_conditional_variant:Nnn \clist_if_in:Nn { Nx } { TF }
\prg_generate_conditional_variant:Nnn \prop_if_in:Nn { c } { T }
\prg_generate_conditional_variant:Nnn \str_if_eq:nn { xn } { TF }
\prg_generate_conditional_variant:Nnn \tl_if_eq:nn { en } { T, TF }
\prg_generate_conditional_variant:Nnn \tl_if_head_eq_catcode:nN { VN } { TF }
\prg_generate_conditional_variant:Nnn \tl_if_head_eq_meaning:nN { VN } { T, TF }

\tl_new:N \l__tblr_a_tl
\tl_new:N \l__tblr_b_tl
\tl_new:N \l__tblr_c_tl
\tl_new:N \l__tblr_d_tl
\tl_new:N \l__tblr_e_tl
\tl_new:N \l__tblr_f_tl
\tl_new:N \l__tblr_h_tl
\tl_new:N \l__tblr_i_tl % for row index
\tl_new:N \l__tblr_j_tl % for column index
\tl_new:N \l__tblr_k_tl
\tl_new:N \l__tblr_n_tl
\tl_new:N \l__tblr_o_tl
\tl_new:N \l__tblr_r_tl
\tl_new:N \l__tblr_s_tl
\tl_new:N \l__tblr_t_tl
\tl_new:N \l__tblr_u_tl
\tl_new:N \l__tblr_v_tl
\tl_new:N \l__tblr_w_tl
\tl_new:N \l__tblr_x_tl
\tl_new:N \l__tblr_y_tl
\int_new:N \l__tblr_a_int
\int_new:N \l__tblr_c_int % for column number
\int_new:N \l__tblr_r_int % for row number
\dim_new:N \l__tblr_d_dim % for depth
\dim_new:N \l__tblr_h_dim % for height
\dim_new:N \l__tblr_o_dim
\dim_new:N \l__tblr_p_dim
\dim_new:N \l__tblr_q_dim
\dim_new:N \l__tblr_r_dim
\dim_new:N \l__tblr_s_dim
\dim_new:N \l__tblr_t_dim
\dim_new:N \l__tblr_v_dim

```

```

\dim_new:N \l__tblr_w_dim % for width
\box_new:N \l__tblr_a_box
\box_new:N \l__tblr_b_box
\box_new:N \l__tblr_c_box % for cell box
\box_new:N \l__tblr_d_box

%% Total number of tblr tables
\int_new:N \g__tblr_table_count_int

%% Some commands for horizontal alignment
\cs_new_eq:NN \__tblr_halign_command_l: \raggedright
\cs_new_eq:NN \__tblr_halign_command_c: \centering
\cs_new_eq:NN \__tblr_halign_command_r: \raggedleft

%% Some counters for row and column numbering
\newcounter{rownum}
\newcounter{colnum}
\newcounter{rowcount}
\newcounter{colcount}

%% Some dimensions for row and column spacing
\dim_new:N \abovesep
\dim_new:N \belowsep
\dim_new:N \leftsep
\dim_new:N \rightsep

%%% -----
%%% \section{Data Structures Based on Property Lists}
%%% -----

\int_new:N \g__tblr_level_int % store table nesting level

\cs_new_protected:Npn \__tblr_clear_prop_lists:
{
  \prop_gclear_new:c { g__tblr_text_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_command_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_inner_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_note_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_remark_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_more_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_row_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_column_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_cell_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_hline_ \int_use:N \g__tblr_level_int _prop }
  \prop_gclear_new:c { g__tblr_vline_ \int_use:N \g__tblr_level_int _prop }
}

\cs_new_protected:Npn \__tblr_prop_gput:nnn #1 #2 #3
{
  \prop_gput:cnn
    { g__tblr_#1_ \int_use:N \g__tblr_level_int _prop } { #2 } { #3 }
}

\cs_generate_variant:Nn \__tblr_prop_gput:nnn { nnx, nnV, nxn, nxx, nxV }

\cs_new:Npn \__tblr_prop_item:nn #1 #2

```

```

{
  \prop_item:cn { g__tblr_#1_ \int_use:N \g_tblr_level_int _prop } { #2 }
}
\cs_generate_variant:Nn \__tblr_prop_item:nn { ne }

\cs_new_protected:Npn \__tblr_prop_if_in:nnT #1
{
  \prop_if_in:cnT { g__tblr_#1_ \int_use:N \g_tblr_level_int _prop }
}
\cs_new_protected:Npn \__tblr_prop_if_in:nnF #1
{
  \prop_if_in:cnF { g__tblr_#1_ \int_use:N \g_tblr_level_int _prop }
}
\cs_new_protected:Npn \__tblr_prop_if_in:nnTF #1
{
  \prop_if_in:cnTF { g__tblr_#1_ \int_use:N \g_tblr_level_int _prop }
}
\prg_generate_conditional_variant:Nnn \__tblr_prop_if_in:nn { nx } { T, F, TF }

\cs_new_protected:Npn \__tblr_prop_log:n #1
{
  \prop_log:c { g__tblr_#1_ \int_use:N \g_tblr_level_int _prop }
}

\cs_new_protected:Npn \__tblr_prop_map_inline:nn #1 #2
{
  \prop_map_inline:cn { g__tblr_#1_ \int_use:N \g_tblr_level_int _prop } {#2}
}

\cs_new_protected:Npn \__tblr_prop_gput_if_larger:nnn #1 #2 #3
{
  \__tblr_gput_if_larger:cnn
  { g__tblr_#1_ \int_use:N \g_tblr_level_int _prop } { #2 } { #3 }
}
\cs_generate_variant:Nn \__tblr_prop_gput_if_larger:nnn { nnx, nnV, nxn, nxx, nxV }

\cs_new_protected:Npn \__tblr_prop_gadd_dimen_value:nnn #1 #2 #3
{
  \__tblr_gadd_dimen_value:cnn
  { g__tblr_#1_ \int_use:N \g_tblr_level_int _prop } { #2 } { #3 }
}
\cs_generate_variant:Nn \__tblr_prop_gadd_dimen_value:nnn { nnx, nnV, nxn, nxx }

%% Put the dimension to the prop list only if it's larger than the old one

\tl_new:N \l__tblr_put_if_larger_tl

\cs_new_protected:Npn \__tblr_put_if_larger:Nnn #1 #2 #3
{
  \tl_set:Nx \l__tblr_put_if_larger_tl { \prop_item:Nn #1 { #2 } }
  \bool_lazy_or:nnT
  { \tl_if_empty_p:N \l__tblr_put_if_larger_tl }
  { \dim_compare_p:nNn { #3 } > { \l__tblr_put_if_larger_tl } }
  { \prop_put:Nnn #1 { #2 } { #3 } }
}
\cs_generate_variant:Nn \__tblr_put_if_larger:Nnn { Nnx, Nxn, Nxx, NnV }

```

```

\cs_new_protected:Npn \__tblr_gput_if_larger:Nnn #1 #2 #3
{
  \tl_set:Nx \l__tblr_put_if_larger_tl { \prop_item:Nn #1 { #2 } }
  \bool_lazy_or:nnT
    { \tl_if_empty_p:N \l__tblr_put_if_larger_tl }
    { \dim_compare_p:nNn { #3 } > { \l__tblr_put_if_larger_tl } }
    { \prop_gput:Nnn #1 { #2 } { #3 } }
}
\cs_generate_variant:Nn \__tblr_gput_if_larger:Nnn { Nnx, Nxn, Nxx, cnn }

%% Add the dimension to some key value of the prop list
%% #1: the prop list, #2: the key, #3: the dimen to add

\cs_new_protected:Npn \__tblr_add_dimen_value:Nnn #1 #2 #3
{
  \prop_put:Nnx #1 { #2 } { \dim_eval:n { \prop_item:Nn #1 { #2 } + #3 } }
}
\cs_generate_variant:Nn \__tblr_add_dimen_value:Nnn { cnn }

\cs_new_protected:Npn \__tblr_gadd_dimen_value:Nnn #1 #2 #3
{
  \prop_gput:Nnx #1 { #2 } { \dim_eval:n { \prop_item:Nn #1 { #2 } + #3 } }
}
\cs_generate_variant:Nn \__tblr_gadd_dimen_value:Nnn { cnn }

%%% -----
%% \section{Data Structures Based on Token Lists}
%%% -----

\cs_new_protected:Npn \__tblr_clear_spec_lists:
{
  %\__tblr_clear_one_spec_lists:n { row }
  %\__tblr_clear_one_spec_lists:n { column }
  %\__tblr_clear_one_spec_lists:n { cell }
  \__tblr_clear_one_spec_lists:n { text }
  \__tblr_clear_one_spec_lists:n { hline }
  \__tblr_clear_one_spec_lists:n { vline }
  \__tblr_clear_one_spec_lists:n { outer }
}

\cs_new_protected:Npn \__tblr_clear_one_spec_lists:n #1
{
  \clist_if_exist:cTF { g__tblr_#1_ \int_use:N \g__tblr_level_int _clist }
  {
    \clist_map_inline:cn { g__tblr_#1_ \int_use:N \g__tblr_level_int _clist }
    {
      \tl_gclear:c { g__tblr_spec_ \int_use:N \g__tblr_level_int _#1_#1_tl }
    }
  }
  { \clist_new:c { g__tblr_#1_ \int_use:N \g__tblr_level_int _clist } }
}

\cs_new_protected:Npn \__tblr_spec_gput:nnn #1 #2 #3
{
  \tl_gset:cn
  { g__tblr_spec_ \int_use:N \g__tblr_level_int _#1_#2_tl } {#3}
}

```

```

\clist_gput_right:cx { g__tblr_#1_ \int_use:N \g_tblr_level_int _clist } {#2}
}
\cs_generate_variant:Nn \__tblr_spec_gput:nnn { nne, nnV, nen, nee, neV }

\cs_new:Npn \__tblr_spec_item:nn #1 #2
{
\tl_if_exist:cT { g__tblr_spec_ \int_use:N \g_tblr_level_int _#1_#2_tl }
{
\exp_args:Nv \exp_not:n
{ g__tblr_spec_ \int_use:N \g_tblr_level_int _#1_#2_tl }
}
}
\cs_generate_variant:Nn \__tblr_spec_item:nn { ne }

\cs_new_protected:Npn \__tblr_spec_gput_if_larger:nnn #1 #2 #3
{
\tl_set:Nx \l__tblr_put_if_larger_tl { \__tblr_spec_item:nn {#1} {#2} }
\bool_lazy_or:nnT
{ \tl_if_empty_p:N \l__tblr_put_if_larger_tl }
{ \dim_compare_p:nNn {#3} > { \l__tblr_put_if_larger_tl } }
{ \__tblr_spec_gput:nnn {#1} {#2} {#3} }
}
\cs_generate_variant:Nn \__tblr_spec_gput_if_larger:nnn { nne, nnV, nen, nee, neV }

\cs_new_protected:Npn \__tblr_spec_gadd_dimen_value:nnn #1 #2 #3
{
\__tblr_spec_gput:nne {#1} {#2}
{ \dim_eval:n { \__tblr_spec_item:ne {#1} {#2} + #3 } }
}
\cs_generate_variant:Nn \__tblr_spec_gadd_dimen_value:nnn { nne, nnV, nen, nee }

\cs_new_protected:Npn \__tblr_spec_log:n #1
{
\clist_gremove_duplicates:c
{ g__tblr_#1_ \int_use:N \g_tblr_level_int _clist }
\tl_log:x
{
The ~ spec ~ list ~ #1 _ \int_use:N \g_tblr_level_int
\space contains ~ the ~ pairs:
}
\clist_map_inline:cn { g__tblr_#1_ \int_use:N \g_tblr_level_int _clist }
{
\tl_log:x
{
\space { ##1 } ~\space=>~\space { \__tblr_spec_item:nn {#1} {##1} }
}
}
}

%%% -----
%%% \section{Data Structures Based on Integer Arrays}
%%% -----

\msg_new:nnn { tabularray } { intarray-beyond-bound }
{ Position ~ #2 ~ is ~ beyond ~ the ~ bound ~ of ~ intarray ~ #1.}

```

```

\cs_new_protected:Npn \__tblr_intarray_gset:Nnn #1 #2 #3
{
  \bool_lazy_or:nnTF
    { \int_compare_p:nNn {#2} < {0} }
    { \int_compare_p:nNn {#2} > {\intarray_count:N #1} }
  {
    \bool_if:NT \g__tblr_tracing_intarray_bool
      { \msg_warning:nnnn { tabularray } { intarray-beyond-bound } {#1} {#2} }
  }
  { \intarray_gset:Nnn #1 {#2} {#3} }
}
\cs_generate_variant:Nn \__tblr_intarray_gset:Nnn { cnn }

%% #1: data name; #2: key name; #3: value type
\cs_new_protected:Npn \__tblr_data_new_key:nnn #1 #2 #3
{
  \int_gincr:c { g__tblr_data_#1_key_count_int }
  \tl_const:ce
  {
    g__tblr_data_#1_key_name_
    \int_use:c { g__tblr_data_#1_key_count_int } _tl
  }
  { #2 }
  \tl_const:ce { g__tblr_data_#1_key_number_#2_tl }
  { \int_use:c { g__tblr_data_#1_key_count_int } }
  \tl_const:cn { g__tblr_data_#1_key_type_#2_tl } {#3}
}

\int_new:N \g__tblr_data_row_key_count_int
__tblr_data_new_key:nnn { row } { height } { dim }
__tblr_data_new_key:nnn { row } { coefficient } { dec }
__tblr_data_new_key:nnn { row } { abovesep } { dim }
__tblr_data_new_key:nnn { row } { belowsep } { dim }
__tblr_data_new_key:nnn { row } { @row-height } { dim }
__tblr_data_new_key:nnn { row } { @row-head } { dim }
__tblr_data_new_key:nnn { row } { @row-foot } { dim }
__tblr_data_new_key:nnn { row } { @row-upper } { dim }
__tblr_data_new_key:nnn { row } { @row-lower } { dim }

\int_new:N \g__tblr_data_column_key_count_int
__tblr_data_new_key:nnn { column } { width } { dim }
__tblr_data_new_key:nnn { column } { coefficient } { dec }
__tblr_data_new_key:nnn { column } { leftsep } { dim }
__tblr_data_new_key:nnn { column } { rightsep } { dim }
__tblr_data_new_key:nnn { column } { @col-width } { dim }

\int_new:N \g__tblr_data_cell_key_count_int
__tblr_data_new_key:nnn { cell } { width } { dim }
__tblr_data_new_key:nnn { cell } { rowspan } { int }
__tblr_data_new_key:nnn { cell } { colspan } { int }
__tblr_data_new_key:nnn { cell } { halign } { str }
__tblr_data_new_key:nnn { cell } { valign } { str }
__tblr_data_new_key:nnn { cell } { background } { str }
__tblr_data_new_key:nnn { cell } { font } { str }
__tblr_data_new_key:nnn { cell } { omit } { int }
__tblr_data_new_key:nnn { cell } { @cell-width } { dim }
__tblr_data_new_key:nnn { cell } { @cell-height } { dim }

```

```

\__tblr_data_new_key:nnn { cell } { @cell-depth } { dim }

\clist_const:Nn \g__tblr_data_clist { row, column, cell }
\tl_const:Nn \g__tblr_data_row_count_tl { \c@rowcount }
\tl_const:Nn \g__tblr_data_column_count_tl { \c@colcount }
\tl_const:Nn \g__tblr_data_cell_count_tl { \c@rowcount * \c@colcount }
\tl_const:Nn \g__tblr_data_row_index_number_tl {1}
\tl_const:Nn \g__tblr_data_column_index_number_tl {1}
\tl_const:Nn \g__tblr_data_cell_index_number_tl {2}
\int_new:N \g__tblr_array_int

\cs_new_protected:Npn \__tblr_init_table_data:
{
  \clist_map_function:NN \g__tblr_data_clist \__tblr_init_one_data:n
}

\cs_new_protected:Npn \__tblr_init_one_data:n #1
{
  \int_gincr:N \g__tblr_array_int
  \intarray_new:cn { g__tblr_#1_ \int_use:N \g__tblr_array_int _intarray }
  {
    \int_use:c { g__tblr_data_#1_key_count_int }
    * \tl_use:c { g__tblr_data_#1_count_tl }
  }
  \cs_set_eq:cc { g__tblr_#1_ \int_use:N \g__tblr_level_int _intarray }
  { g__tblr_#1_ \int_use:N \g__tblr_array_int _intarray }
  %\intarray_log:c { g__tblr_#1_ \int_use:N \g__tblr_level_int _intarray }
}

%% #1: data name; #2: data index; #3: key name
\cs_new:Npn \__tblr_data_key_to_int:nnn #1 #2 #3
{
  ( #2 - 1 ) * \int_use:c { g__tblr_data_#1_key_count_int }
  + \tl_use:c { g__tblr_data_#1_key_number_#3_tl }
}

%% #1: data name; #2: data index 1; #3: data index 2; #4: key name
\cs_new:Npn \__tblr_data_key_to_int:nnnn #1 #2 #3 #4
{
  ( #2 - 1 ) * \c@colcount * \int_use:c { g__tblr_data_#1_key_count_int }
  + ( #3 - 1 ) * \int_use:c { g__tblr_data_#1_key_count_int }
  + \tl_use:c { g__tblr_data_#1_key_number_#4_tl }
}

\int_new:N \l__tblr_key_count_int
\int_new:N \l__tblr_key_quotient_int
\int_new:N \l__tblr_key_quotient_two_int
\int_new:N \l__tblr_key_remainder_int

%% #1: data name; #2: array position;
%% #3: returning tl with index; #4: returning tl with key name
\cs_new:Npn \__tblr_data_int_to_key:nnNN #1 #2 #3 #4
{
  \int_set_eq:Nc \l__tblr_key_count_int { g__tblr_data_#1_key_count_int }
  \int_set:Nn \l__tblr_key_quotient_int
  {

```

```

        \int_div_truncate:nn
        { #2 + \l__tblr_key_count_int - 1 } { \l__tblr_key_count_int }
    }
\int_set:Nn \l__tblr_key_remainder_int
{
    #2 + \l__tblr_key_count_int
    - \l__tblr_key_quotient_int * \l__tblr_key_count_int
}
\int_compare:nNnT { \l__tblr_key_remainder_int } = { 0 }
{ \int_set_eq:NN \l__tblr_key_remainder_int \l__tblr_key_count_int }
\tl_set:Nx #3 { \int_use:N \l__tblr_key_quotient_int }
\tl_set_eq:Nc #4
{ g__tblr_data_#1_key_name_ \int_use:N \l__tblr_key_remainder_int _tl }
}

%% #1: data name; #2: array position;
%% #3: returning tl with index 1; #4: returning tl with index 2;
%% #5: returning tl with key name
\cs_new:Npn \__tblr_data_int_to_key:nnNNN #1 #2 #3 #4 #5
{
    \int_set_eq:Nc \l__tblr_key_count_int { g__tblr_data_#1_key_count_int }
    \int_set:Nn \l__tblr_key_quotient_int
    {
        \int_div_truncate:nn
        { #2 + \l__tblr_key_count_int - 1 } { \l__tblr_key_count_int }
    }
    \int_set:Nn \l__tblr_key_remainder_int
    {
        #2 + \l__tblr_key_count_int
        - \l__tblr_key_quotient_int * \l__tblr_key_count_int
    }
    \int_compare:nNnT { \l__tblr_key_remainder_int } = { 0 }
    { \int_set_eq:NN \l__tblr_key_remainder_int \l__tblr_key_count_int }
    \tl_set_eq:Nc #5
    { g__tblr_data_#1_key_name_ \int_use:N \l__tblr_key_remainder_int _tl }
    \int_set:Nn \l__tblr_key_quotient_two_int
    {
        \int_div_truncate:nn
        { \l__tblr_key_quotient_int + \c@colcount - 1 } { \c@colcount }
    }
    \int_set:Nn \l__tblr_key_remainder_int
    {
        \l__tblr_key_quotient_int + \c@colcount
        - \l__tblr_key_quotient_two_int * \c@colcount
    }
    \int_compare:nNnT { \l__tblr_key_remainder_int } = { 0 }
    { \int_set_eq:NN \l__tblr_key_remainder_int \c@colcount }
    \tl_set:Nx #4 { \int_use:N \l__tblr_key_remainder_int }
    \tl_set:Nx #3 { \int_use:N \l__tblr_key_quotient_two_int }
}

\tl_new:N \g__tblr_data_int_from_value_tl

%% #1: data name; #2: key name; #3: value
%% The result will be stored in \g__tblr_data_int_from_value_tl
\cs_new_protected:Npn \__tblr_data_int_from_value:nnn #1 #2 #3
{

```

```

\cs:w
  __tblr_data_int_from_ \tl_use:c { g__tblr_data_#1_key_type_#2_tl } :n
\cs_end:
{#3}
}

%% #1: data name; #2: key name; #3: int
\cs_new:Npn \__tblr_data_int_to_value:nnn #1 #2 #3
{
  \cs:w
    __tblr_data_int_to_ \tl_use:c { g__tblr_data_#1_key_type_#2_tl } :n
  \cs_end:
  {#3}
}
\cs_generate_variant:Nn \__tblr_data_int_to_value:nnn { nne, nVe }

\cs_new_protected:Npn \__tblr_data_int_from_int:n #1
{
  \tl_gset:Nn \g__tblr_data_int_from_value_tl {#1}
}

\cs_new:Npn \__tblr_data_int_to_int:n #1
{
  #1
}

\cs_new_protected:Npn \__tblr_data_int_from_dim:n #1
{
  \tl_gset:Nx \g__tblr_data_int_from_value_tl { \dim_to_decimal_in_sp:n {#1} }
}

%% Return a dimension in pt so that it's easier to understand in tracing messages
\cs_new:Npn \__tblr_data_int_to_dim:n #1
{
  %#1 sp
  %\dim_eval:n { #1 sp }
  \dim_to_decimal:n { #1 sp } pt
}

\cs_new_protected:Npn \__tblr_data_int_from_dec:n #1
{
  \tl_gset:Nx \g__tblr_data_int_from_value_tl
    { \dim_to_decimal_in_sp:n {#1 pt} }
}

\cs_new:Npn \__tblr_data_int_to_dec:n #1
{
  \dim_to_decimal:n {#1 sp}
}

\int_new:N \g__tblr_data_str_value_count_int
\tl_set:cn { g__tblr_data_0_to_str_tl } { }

\cs_new_protected:Npn \__tblr_data_int_from_str:n #1
{

```

```

\tl_if_exist:cTF { g__tblr_data_ \tl_to_str:n {#1} _to_int_tl }
{
  \tl_gset_eq:Nc \g__tblr_data_int_from_value_tl
  { g__tblr_data_ \tl_to_str:n {#1} _to_int_tl }
}
{
  \int_gincr:N \g__tblr_data_str_value_count_int
  \tl_gset:cx { g__tblr_data_ \tl_to_str:n {#1} _to_int_tl }
  { \int_use:N \g__tblr_data_str_value_count_int }
  \tl_gset:cn
  { g__tblr_data_ \int_use:N \g__tblr_data_str_value_count_int _to_str_tl }
  { \exp_not:n {#1} }
  \tl_gset:Nx \g__tblr_data_int_from_value_tl
  { \int_use:N \g__tblr_data_str_value_count_int }
}
}

\cs_new:Npn \__tblr_data_int_to_str:n #1
{
  \tl_use:c { g__tblr_data_#1_to_str_tl }
}

%% #1: data name; #2: data index; #3: key; #4: value
\cs_new_protected:Npn \__tblr_data_gput:nnnn #1 #2 #3 #4
{
  \__tblr_data_int_from_value:nnn {#1} {#3} {#4}
  \__tblr_intarray_gset:cnn
  { g__tblr_#1_ \int_use:N \g__tblr_level_int _intarray }
  { \__tblr_data_key_to_int:nnn {#1} {#2} {#3} }
  { \g__tblr_data_int_from_value_tl }
}

\cs_generate_variant:Nn \__tblr_data_gput:nnnn
{ nnne, nnnV, nenn, nene, nenV, nVnn }

%% #1: data name; #2: data index 1; #3: data index 2; #4: key; #5: value
\cs_new_protected:Npn \__tblr_data_gput:nnnnn #1 #2 #3 #4 #5
{
  \__tblr_data_int_from_value:nnn {#1} {#4} {#5}
  \__tblr_intarray_gset:cnn
  { g__tblr_#1_ \int_use:N \g__tblr_level_int _intarray }
  { \__tblr_data_key_to_int:nnnn {#1} {#2} {#3} {#4} }
  { \g__tblr_data_int_from_value_tl }
}

\cs_generate_variant:Nn \__tblr_data_gput:nnnnn
{ nnnne, nnnnV, neenn, neene, neenV, neeen, nVnn }

%% #1: data name; #2: data index; #3: key
\cs_new:Npn \__tblr_data_item:nnn #1 #2 #3
{
  \__tblr_data_int_to_value:nne {#1} {#3}
  {
    \intarray_item:cn { g__tblr_#1_ \int_use:N \g__tblr_level_int _intarray }
    { \__tblr_data_key_to_int:nnn {#1} {#2} {#3} }
  }
}

\cs_generate_variant:Nn \__tblr_data_item:nnn { nen }

```

```

%% #1: data name; #2: data index 1; #3: data index 2; #4: key
\cs_new:Npn \__tblr_data_item:nmmm #1 #2 #3 #4
{
  \__tblr_data_int_to_value:nne {#1} {#4}
  {
    \intarray_item:cn { g__tblr_#1_ \int_use:N \g_tblr_level_int _intarray }
    { \__tblr_data_key_to_int:nmmm {#1} {#2} {#3} {#4} }
  }
}
\cs_generate_variant:Nn \__tblr_data_item:nmmm { neen }

\tl_new:N \l__tblr_data_key_tl
\tl_new:N \l__tblr_data_index_tl
\tl_new:N \l__tblr_data_index_two_tl

\cs_new_protected:Npn \__tblr_data_log:n #1
{
  \use:c { __tblr_data_log_ \use:c { g__tblr_data_#1_index_number_tl } :n } {#1}
  \__tblr_prop_log:n {#1}
}

\cs_new_protected:cpn { __tblr_data_log_1:n } #1
{
  %\intarray_log:c { g__tblr_#1_ \int_use:N \g_tblr_level_int _intarray }
  \tl_set:Nx \l_tmpa_tl { g__tblr_#1_ \int_use:N \g_tblr_level_int _intarray }
  \tl_log:n { ----- }
  \int_step_inline:nn
  { \intarray_count:c { \l_tmpa_tl } }
  {
    \__tblr_data_int_to_key:nmNN {#1} {##1}
    \l__tblr_data_index_tl \l__tblr_data_key_tl
    \tl_log:x
    {
      \space
      { #1 [\l__tblr_data_index_tl] / \l__tblr_data_key_tl }
      ~\space => ~\space
      {
        \__tblr_data_int_to_value:nVe {#1} \l__tblr_data_key_tl
        { \intarray_item:cn { \l_tmpa_tl } {##1} }
      }
    }
  }
}

\cs_new_protected:cpn { __tblr_data_log_2:n } #1
{
  %\intarray_log:c { g__tblr_#1_ \int_use:N \g_tblr_level_int _intarray }
  \tl_set:Nx \l_tmpa_tl { g__tblr_#1_ \int_use:N \g_tblr_level_int _intarray }
  \tl_log:n { ----- }
  \int_step_inline:nn
  { \intarray_count:c { \l_tmpa_tl } }
  {
    \__tblr_data_int_to_key:nmNNN {#1} {##1}
    \l__tblr_data_index_tl \l__tblr_data_index_two_tl \l__tblr_data_key_tl
    \tl_log:x
    {
      \space
    }
  }
}

```

```

    {
      #1 [\l__tblr_data_index_tl][\l__tblr_data_index_two_tl]
        / \l__tblr_data_key_tl
    }
    ~\space => ~\space
    {
      \__tblr_data_int_to_value:nVe {#1} \l__tblr_data_key_tl
        { \intarray_item:cn { \l_tmpa_tl } {##1} }
    }
  }
}

%% #1: data name; #2: row index; #3: key; #4: value
\cs_new_protected:Npn \__tblr_data_gput_if_larger:nnnn #1 #2 #3 #4
{
  \__tblr_data_int_from_value:nnn {#1} {#3} {#4}
  \__tblr_array_gput_if_larger:cnn
  { g__tblr_#1_ \int_use:N \g__tblr_level_int_intarray }
  { \__tblr_data_key_to_int:nnn {#1} {#2} {#3} }
  { \g__tblr_data_int_from_value_tl }
}
\cs_generate_variant:Nn \__tblr_data_gput_if_larger:nnnn { nnne, nnnV, nene, nenV }

\cs_new_protected:Npn \__tblr_array_gput_if_larger:Nnn #1 #2 #3
{
  \int_compare:nNnT {#3} > { \intarray_item:Nn #1 {#2} }
  { \__tblr_intarray_gset:Nnn #1 {#2} {#3} }
}
\cs_generate_variant:Nn \__tblr_array_gput_if_larger:Nnn { cnn }

%% #1: data name; #2: data index; #3: key; #4: value
\cs_new_protected:Npn \__tblr_data_gadd_dimen_value:nnnn #1 #2 #3 #4
{
  \__tblr_data_int_from_value:nnn {#1} {#3} {#4}
  \__tblr_array_gadd_value:cnn
  { g__tblr_#1_ \int_use:N \g__tblr_level_int_intarray }
  { \__tblr_data_key_to_int:nnn {#1} {#2} {#3} }
  { \g__tblr_data_int_from_value_tl }
}
\cs_generate_variant:Nn \__tblr_data_gadd_dimen_value:nnnn
{ nnne, nnnV, nenn, nene }

\cs_new_protected:Npn \__tblr_array_gadd_value:Nnn #1 #2 #3
{
  \__tblr_intarray_gset:Nnn #1 {#2} { \intarray_item:Nn #1 {#2} + #3 }
}
\cs_generate_variant:Nn \__tblr_array_gadd_value:Nnn { cnn }

\bool_new:N \g__tblr_use_intarray_bool
\bool_set_true:N \g__tblr_use_intarray_bool

\AtBeginDocument
{
  \bool_if:NF \g__tblr_use_intarray_bool
  {

```

```

\cs_set_protected:Npn \__tblr_data_gput:nnnn #1 #2 #3 #4
{
  \__tblr_spec_gput:nnn {#1} { [#2] / #3 } {#4}
}
\cs_set_protected:Npn \__tblr_data_gput:nnnnn #1 #2 #3 #4 #5
{
  \__tblr_spec_gput:nnn {#1} { [#2][#3] / #4 } {#5}
}
\cs_set:Npn \__tblr_data_item:nnn #1 #2 #3
{
  \__tblr_spec_item:nn {#1} { [#2] / #3 }
}
\cs_set:Npn \__tblr_data_item:nnnn #1 #2 #3 #4
{
  \__tblr_spec_item:nn {#1} { [#2][#3] / #4 }
}
\cs_set_protected:Npn \__tblr_data_log:n #1
{
  \__tblr_spec_log:n {#1}
}
\cs_set_protected:Npn \__tblr_data_gput_if_larger:nnnn #1 #2 #3 #4
{
  \__tblr_spec_gput_if_larger:nnn {#1} { [#2] / #3 } {#4}
}
\cs_set_protected:Npn \__tblr_data_gput_if_larger:nnnnn #1 #2 #3 #4 #5
{
  \__tblr_spec_gput_if_larger:nnn {#1} { [#2][#3] / #4 } {#5}
}
\cs_set_protected:Npn \__tblr_data_gadd_dimen_value:nnnn #1 #2 #3 #4
{
  \__tblr_spec_gadd_dimen_value:nnn {#1} { [#2] / #3 } {#4}
}
\cs_set_protected:Npn \__tblr_data_gadd_dimen_value:nnnnn #1 #2 #3 #4 #5
{
  \__tblr_spec_gadd_dimen_value:nnn {#1} { [#2][#3] / #4 } {#5}
}
}
}

%%% -----
%% \section{Child Selectors}
%%% -----

\clist_new:N \g_tblr_used_child_selectors_clist

\tl_new:N \l__tblr_childs_arg_spec_tl

\msg_new:nnn { tabularray } { used-child-selector }
{ Child ~ selector ~ name ~ "#1" ~ has ~ been ~ used! }

\NewDocumentCommand \NewChildSelector { m O{} o m }
{
  \__tblr_new_child_selector_aux:xnnn { \tl_trim_spaces:n {#1} } {#2} {#3} {#4}
}

\cs_new_protected:Npn \__tblr_new_child_selector_aux:nnnn #1 #2 #3 #4

```

```

{
  \clist_if_in:NnTF \g_tblr_used_child_selectors_clist { #1 }
  {
    \msg_error:nnn { tabularray } { used-child-selector } { #1 }
    \clist_log:N \g_tblr_used_child_selectors_clist
  }
  {
    \__tblr_make_xparse_arg_spec:nnN { #2 } { #3 } \l__tblr_childs_arg_spec_tl
    \exp_args:NcV \NewDocumentCommand
      { __tblr_child_selector_ #1 :w } \l__tblr_childs_arg_spec_tl { #4 }
    \clist_gput_right:Nn \g_tblr_used_child_selectors_clist { #1 }
  }
}
\cs_generate_variant:Nn \__tblr_new_child_selector_aux:nnnn { xnnn }

%% #1: argument number, #2: optional argument default, #3: result tl
\cs_new_protected:Npn \__tblr_make_xparse_arg_spec:nnN #1 #2 #3
{
  \tl_clear:N #3
  \int_compare:nNnT { #1 } > { 0 }
  {
    \IfValueTF { #2 }
    { \tl_set:Nn #3 { 0{#2} } }
    { \tl_set:Nn #3 { m } }
    \tl_put_right:Nx #3 { \prg_replicate:nn { #1 - 1 } { m } }
  }
}

\clist_new:N \l_tblr_childs_clist
\tl_new:N \l_tblr_childs_total_tl

\NewChildSelector { odd }
{
  \int_step_inline:nnnn {1} {2} { \l_tblr_childs_total_tl }
  { \clist_put_right:Nn \l_tblr_childs_clist {##1} }
}

\NewChildSelector { even }
{
  \int_step_inline:nnnn {2} {2} { \l_tblr_childs_total_tl }
  { \clist_put_right:Nn \l_tblr_childs_clist {##1} }
}

\regex_const:Nn \c__tblr_split_selector_name_regex { ^ ( [A-Za-z] {2,} ) ( . * ) }
\seq_new:N \l__tblr_childs_split_seq
\seq_new:N \l__tblr_childs_regex_seq
\tl_new:N \l__tblr_childs_selector_tl

%% #1, child specifications; #2, total number.
%% The result will be put into \l_tblr_childs_clist
\cs_new_protected:Npn \__tblr_get_childs:nn #1 #2
{
  \clist_clear:N \l_tblr_childs_clist
  \tl_set:Nx \l_tblr_childs_total_tl {#2}
  \regex_extract_once:NnNTF \c__tblr_split_selector_name_regex {#1}
  \l__tblr_childs_regex_seq

```

```

    {
      \tl_set:No \l__tblr_childs_selector_tl
      {
        \cs:w
          __tblr_child_selector_ \seq_item:Nn \l__tblr_childs_regex_seq {2} :w
        \cs_end:
      }
      \exp_args:Nx \l__tblr_childs_selector_tl
      { \seq_item:Nn \l__tblr_childs_regex_seq{3} }
    }
    {
      \tl_if_eq:nnTF {#1} {-}
      { \__tblr_get_childs_normal:nn {1-#2} {#2} }
      { \__tblr_get_childs_normal:nn {#1} {#2} }
    }
    %\clist_log:N \l__tblr_childs_clist
  }
\cs_generate_variant:Nn \__tblr_get_childs:nn { nx }

\cs_new_protected:Npn \__tblr_get_childs_normal:nn #1 #2
{
  \seq_set_split:Nnn \l__tblr_childs_split_seq {,} {#1}
  \seq_map_inline:Nn \l__tblr_childs_split_seq
  {
    \tl_if_in:nnTF {##1} {-}
    { \__tblr_get_childs_normal_aux:w ##1 \scan_stop }
    { \__tblr_get_childs_normal_aux:w ##1 - ##1 \scan_stop }
  }
}

\cs_new_protected_nopar:Npn \__tblr_get_childs_normal_aux:w #1 - #2 \scan_stop
{
  \int_step_inline:nnn {#1} {#2}
  { \clist_put_right:Nn \l__tblr_childs_clist {##1} }
}

%%% -----
%% \section{New Table Commands}
%%% -----

%% We need some commands to modify table/row/column/cell specifications.
%% These commands must be defined with \NewTableCommand command,
%% so that we could extract them, execute them once, then disable them.

\clist_new:N \g__tblr_table_commands_clist

\msg_new:nnn { tabularray } { defined-table-command }
{ Table ~ commnad ~ #1 has ~ been ~ defined! }

\NewDocumentCommand \NewTableCommand { m O{0} o m }
{
  \clist_if_in:NnTF \g__tblr_table_commands_clist { #1 }
  {
    \msg_error:nnn { tabularray } { defined-table-command } { #1 }
    \clist_log:N \g__tblr_table_commands_clist
  }
}

```

```

    {
      \__tblr_make_xparse_arg_spec:nnN { #2 } { #3 } \l__tblr_a_tl
      \exp_args:NcV \NewDocumentCommand
        { __tblr_table_command_ \cs_to_str:N #1 :w } \l__tblr_a_tl { #4 }
      \exp_args:NcV \NewDocumentCommand
        { __tblr_table_command_ \cs_to_str:N #1 _gobble :w } \l__tblr_a_tl { }
      \IfValueTF { #3 }
        {
          \tl_gset:cn { g__tblr_table_cmd_ \cs_to_str:N #1 _arg_num_b_tl } {-#2}
        }
        {
          \tl_gset:cn { g__tblr_table_cmd_ \cs_to_str:N #1 _arg_num_b_tl } {#2}
        }
      \clist_gput_right:Nn \g__tblr_table_commands_clist { #1 }
    }
  }

\cs_new_protected:Npn \__tblr_enable_table_commands:
{
  \clist_map_inline:Nn \g__tblr_table_commands_clist
    { \cs_set_eq:Nc ##1 { __tblr_table_command_ \cs_to_str:N ##1 :w } }
}

\cs_new_protected:Npn \__tblr_disable_table_commands:
{
  \clist_map_inline:Nn \g__tblr_table_commands_clist
    { \cs_set_eq:Nc ##1 { __tblr_table_command_ \cs_to_str:N ##1 _gobble:w } }
}

\cs_new_protected:Npn \__tblr_execute_table_commands:
{
  \__tblr_prop_map_inline:nn { command }
    {
      \__tblr_set_row_col_from_key_name:w ##1
      ##2
    }
  \LogTblrTracing { cell }
}

\cs_new_protected:Npn \__tblr_set_row_col_from_key_name:w [#1] [#2]
{
  \int_set:Nn \c@rownum {#1}
  \int_set:Nn \c@colnum {#2}
}

%%% -----
%%> \section{New Content Commands}
%%% -----

%% We need to emulate or fix some commands such as \diagbox in other packages
%% These commands must be defined with \NewContentCommand command
%% We only enable them inside tblr environment to avoid potential conflict

\clist_new:N \g__tblr_content_commands_clist

\msg_new:nnn { tabularray } { defined-content-command }

```

```

{ Content ~ commnad ~ #1 has ~ been ~ defined! }

\NewDocumentCommand \NewContentCommand { m O{0} o m }
{
  \clist_if_in:NnTF \g__tblr_content_commands_clist { #1 }
  {
    \msg_warning:nnn { tabularray } { defined-content-command } { #1 }
    \clist_log:N \g__tblr_content_commands_clist
  }
  {
    \__tblr_make_xparse_arg_spec:nnN { #2 } { #3 } \l__tblr_a_tl
    \exp_args:NcV \NewDocumentCommand
      { __tblr_content_command_ \cs_to_str:N #1 :w } \l__tblr_a_tl { #4 }
    \clist_gput_right:Nn \g__tblr_content_commands_clist { #1 }
  }
}

\cs_new_protected:Npn \__tblr_enable_content_commands:
{
  \clist_map_inline:Nn \g__tblr_content_commands_clist
  { \cs_set_eq:Nc ##1 { __tblr_content_command_ \cs_to_str:N ##1 :w } }
}

%%% -----
%% \section{New Dash Styles}
%%% -----

%% \NewDashStyle commands

\dim_zero_new:N \rulewidth
\dim_set:Nn \rulewidth {0.4pt}

\prop_gset_from_keyval:Nn \g__tblr_defined_hdash_styles_prop
{ solid = \hrule height \rulewidth }
\prop_gset_from_keyval:Nn \g__tblr_defined_vdash_styles_prop
{ solid = \vrule width \rulewidth }

\NewDocumentCommand \NewDashStyle { m m }
{
  \seq_set_split:Nnn \l_tmpa_seq { ~ } {#2}
  \tl_set:Nx \l__tblr_a_tl { \seq_item:Nn \l_tmpa_seq {1} }
  \tl_set:Nx \l__tblr_b_tl { \seq_item:Nn \l_tmpa_seq {2} }
  \tl_set:Nx \l__tblr_c_tl { \seq_item:Nn \l_tmpa_seq {3} }
  \tl_set:Nx \l__tblr_d_tl { \seq_item:Nn \l_tmpa_seq {4} }
  \tl_if_eq:NnT \l__tblr_a_tl { on }
  {
    \tl_if_eq:NnT \l__tblr_c_tl { off }
    {
      \__tblr_dash_style_make_boxes:nxx {#1}
      { \dim_eval:n {\l__tblr_b_tl} } { \dim_eval:n {\l__tblr_d_tl} }
    }
  }
}

\cs_new_protected:Npn \__tblr_dash_style_make_boxes:nnn #1 #2 #3
{

```

```

\dim_set:Nn \l_tmpa_dim { #2 + #3 }
\tl_set:Nn \l__tblr_h_tl { \hbox_to_wd:nn }
\tl_put_right:Nx \l__tblr_h_tl { { \dim_use:N \l_tmpa_dim } }
\tl_put_right:Nn \l__tblr_h_tl
{
  { \hss \vbox:n { \hbox_to_wd:nn {#2} {} \hrule height \rulewidth } \hss }
}
\prop_gput:NnV \g__tblr_defined_hdash_styles_prop {#1} \l__tblr_h_tl
%\prop_log:N \g__tblr_defined_hdash_styles_prop
\tl_set:Nn \l__tblr_v_tl { \vbox_to_ht:nn }
\tl_put_right:Nx \l__tblr_v_tl { { \dim_use:N \l_tmpa_dim } }
\tl_put_right:Nn \l__tblr_v_tl
{
  { \vss \hbox:n { \vbox_to_ht:nn {#2} {} \vrule width \rulewidth } \vss }
}
\prop_gput:NnV \g__tblr_defined_vdash_styles_prop {#1} \l__tblr_v_tl
%\prop_log:N \g__tblr_defined_vdash_styles_prop
}
\cs_generate_variant:Nn \__tblr_dash_style_make_boxes:nnn { nxx }

\cs_new_protected:Npn \__tblr_get_hline_dash_style:N #1
{
  \tl_set:Nx \l_tmpa_tl
  { \prop_item:NV \g__tblr_defined_hdash_styles_prop #1 }
  \tl_if_empty:NF \l_tmpa_tl { \tl_set_eq:NN #1 \l_tmpa_tl }
}

\cs_new_protected:Npn \__tblr_get_vline_dash_style:N #1
{
  \tl_set:Nx \l_tmpa_tl
  { \prop_item:NV \g__tblr_defined_vdash_styles_prop #1 }
  \tl_if_empty:NF \l_tmpa_tl { \tl_set_eq:NN #1 \l_tmpa_tl }
}

\NewDashStyle {dashed} {on ~ 2pt ~ off ~ 2pt}
\NewDashStyle {dotted} {on ~ 0.4pt ~ off ~ 1pt}

%%% -----
%% \section{Set Hlines and Vlines}
%%% -----

\tl_set:Nn \@tblr@dash { dash }
\tl_set:Nn \@tblr@text { text }

\regex_const:Nn \c__tblr_is_color_key_regex { ^[A-Za-z] }

%% \SetHlines command for setting every hline in the table
\NewTableCommand \SetHlines [3] [+]{
  {
    \tblr_set_every_hline:nnn {#1} {#2} {#3}
  }
}

%% We put all code inside a group to avoid affecting other table commands
\cs_new_protected:Npn \tblr_set_every_hline:nnn #1 #2 #3
{
  \group_begin:

```

```

\int_step_inline:nn { \int_eval:n { \c@rowcount + 1 } }
{
  \int_set:Nn \c@rownum {##1}
  \tblr_set_hline:nnn {#1} {#2} {#3}
}
\group_end:
}

%% Check the number of arguments and call \tblr_set_every_hline in different ways
%% This function is called when parsing table specifications
\cs_new_protected:Npn \__tblr_set_every_hline_aux:n #1
{
  \tl_if_head_is_group:nTF {#1}
  {
    \int_compare:nNnTF { \tl_count:n {#1} } = {3}
    { \tblr_set_every_hline:nnn #1 }
    { \tblr_set_every_hline:nnn {1} #1 }
  }
  { \tblr_set_every_hline:nnn {1} {-} {#1} }
}

%% Add \SetHline, \hline and \cline commands

\tl_new:N \l__tblr_hline_count_tl % the count of all hlines
\tl_new:N \l__tblr_hline_num_tl % the index of the hline
\tl_new:N \l__tblr_hline_cols_tl % the columns of the hline
\tl_new:N \l__tblr_hline_dash_tl % dash style
\tl_new:N \l__tblr_hline_fg_tl % dash foreground
\tl_new:N \l__tblr_hline_wd_tl % dash width

\NewTableCommand \cline [2] [] { \SetHline [=] {#2} {#1} }

\NewTableCommand \hline [1] [] { \SetHline [+ ] {-} {#1} }

%% #1: the index of the hline (may be + or =)
%% #2: which columns of the hline, separate by commas
%% #3: key=value pairs
\NewTableCommand \SetHline [3] [+ ]
{
  \tblr_set_hline:nnn {#1} {#2} {#3}
}

%% We need to check "text" key first
%% If it does exist and has empty value, then do nothing
\cs_new_protected:Npn \tblr_set_hline:nnn #1 #2 #3
{
  \group_begin:
  \keys_set_groups:nnn { tblr-hline } { text } {#3}
  \tl_if_eq:NnF \l__tblr_hline_dash_tl { \exp_not:N \@tblr@text }
  {
    \__tblr_set_hline_num:n {#1}
    \tl_clear:N \l__tblr_hline_dash_tl
    \keys_set:nn { tblr-hline } { dash = solid, #3 }
    \__tblr_set_hline_cmd:n {#2}
  }
  \group_end:
}

```

```

}

\cs_new_protected:Npn \tblr_set_hline:nnnn #1 #2 #3 #4
{
  \group_begin:
  \__tblr_get_childs:nx {#1} { \int_eval:n { \c@rowcount + 1 } }
  \clist_map_inline:Nn \l__tblr_childs_clist
  {
    \int_set:Nn \c@rownum {##1}
    \tblr_set_hline:nmn {#2} {#3} {#4}
  }
  \group_end:
}

%% Check the number of arguments and call \tblr_set_hline in different ways
%% Note that #1 always includes an outer pair of braces
%% This function is called when parsing table specifications
\cs_new_protected:Npn \__tblr_set_hline_aux:nn #1 #2
{
  \tl_if_head_is_group:nTF {#2}
  {
    \int_compare:nNnTF { \tl_count:n {#2} } = {3}
    { \tblr_set_hline:nnnn #1 #2 }
    { \tblr_set_hline:nnnn #1 {1} #2 }
  }
  { \tblr_set_hline:nnnn #1 {1} {-} {#2} }
}
\cs_generate_variant:Nn \__tblr_set_hline_aux:nn { Vn }

%% #1: the index of hline to set (may be + or =)
\cs_new_protected:Npn \__tblr_set_hline_num:n #1
{
  \tl_clear:N \l__tblr_hline_num_tl
  \tl_set:Nx \l__tblr_hline_count_tl
  { \__tblr_spec_item:ne { hline } { [\int_use:N \c@rownum] / @hline-count } }
  %% \l__tblr_hline_count_tl may be empty when rowspec has extra |'s
  \int_compare:nNnTF { \l__tblr_hline_count_tl + 0 } = {0}
  {
    \tl_set:Nx \l__tblr_hline_num_tl { 1 }
    \__tblr_spec_gput:nen { hline }
    { [\int_use:N \c@rownum] / @hline-count } { 1 }
  }
  {
    \tl_if_eq:nnTF {#1} {+}
    { \__tblr_set_hline_num_incr: }
    {
      \tl_if_eq:nnTF {#1} {=}
      { \tl_set_eq:NN \l__tblr_hline_num_tl \l__tblr_hline_count_tl }
      {
        \int_compare:nNnTF {#1} > { \l__tblr_hline_count_tl }
        { \__tblr_set_hline_num_incr: }
        { \tl_set:Nn \l__tblr_hline_num_tl {#1} }
      }
    }
  }
}
}

```

```

\cs_new_protected:Npn \__tblr_set_hline_num_incr:
{
  \tl_set:Nx \l__tblr_hline_count_tl
    { \int_eval:n { \l__tblr_hline_count_tl + 1 } }
  \__tblr_spec_gput:nee { hline }
    { [\int_use:N \c@rownum] / @hline-count } { \l__tblr_hline_count_tl }
  \tl_set_eq:NN \l__tblr_hline_num_tl \l__tblr_hline_count_tl
}

\keys_define:nn { tblr-hline }
{
  dash .code:n = \tl_set:Nn \l__tblr_hline_dash_tl { \exp_not:N \@tblr@dash #1 },
  text .code:n = \tl_set:Nn \l__tblr_hline_dash_tl { \exp_not:N \@tblr@text #1 },
  text .groups:n = { text },
  wd .code:n = \tl_set:Nn \l__tblr_hline_wd_tl { \dim_eval:n {#1} },
  fg .code:n = \tl_set:Nn \l__tblr_hline_fg_tl {#1},
  baseline .code:n = \__tblr_hline_set_baseline:n {#1},
  unknown .code:n = \__tblr_hline_unknown_key:V \l_keys_key_str,
}

\cs_new_protected:Npn \__tblr_hline_unknown_key:n #1
{
  \prop_if_in:NnTF \g__tblr_defined_hdash_styles_prop {#1}
    { \tl_set:Nn \l__tblr_hline_dash_tl { \exp_not:N \@tblr@dash #1 } }
    {
      \regex_match:NnTF \c__tblr_is_color_key_regex {#1}
        { \tl_set:Nn \l__tblr_hline_fg_tl {#1} }
        {
          \tl_set_rescan:Nnn \l__tblr_v_tl {} {#1}
          \tl_set:Nn \l__tblr_hline_wd_tl { \dim_eval:n {\l__tblr_v_tl} }
        }
      }
}

\cs_generate_variant:Nn \__tblr_hline_unknown_key:n { V }

\cs_new_protected_nopar:Npn \__tblr_set_hline_cmd:n #1
{
  \__tblr_get_childs:nx {#1} { \int_use:N \c@colcount }
  \clist_map_inline:Nn \l_tblr_childs_clist
    {
      \__tblr_spec_gput:nee { hline }
        { [\int_use:N \c@rownum][##1](\l__tblr_hline_num_tl) / @dash }
        { \l__tblr_hline_dash_tl }
      \tl_if_empty:NF \l__tblr_hline_wd_tl
        {
          \__tblr_spec_gput:nee { hline }
            { [\int_use:N \c@rownum][##1](\l__tblr_hline_num_tl) / wd }
            { \l__tblr_hline_wd_tl }
        }
      \tl_if_empty:NF \l__tblr_hline_fg_tl
        {
          \__tblr_spec_gput:nee { hline }
            { [\int_use:N \c@rownum][##1](\l__tblr_hline_num_tl) / fg }
            { \l__tblr_hline_fg_tl }
        }
    }
}

```

```

\NewTableCommand \firsthline [1] [] { \SetHline [+] {-} { #1, baseline=below } }
\NewTableCommand \lasthline [1] [] { \SetHline [+] {-} { #1, baseline=above } }

\cs_new_protected:Npn \__tblr_hline_set_baseline:n #1
{
  \tl_if_eq:nnTF {#1} {above}
  {
    \__tblr_prop_gput:nnx { inner }
      { baseline } { \int_eval:n { \c@rownum - 1 } }
  }
  {
    \tl_if_eq:nnT {#1} {below}
    {
      \__tblr_prop_gput:nnx { inner } { baseline } { \int_use:N \c@rownum }
    }
  }
}

%% \SetVlines command for setting every vline in the table
\NewTableCommand \SetVlines [3] [+]
{
  \tblr_set_every_vline:nnn {#1} {#2} {#3}
}

%% We put all code inside a group to avoid affecting other table commands
\cs_new_protected:Npn \tblr_set_every_vline:nnn #1 #2 #3
{
  \group_begin:
  \int_step_inline:nn { \int_eval:n { \c@colcount + 1 } }
  {
    \int_set:Nn \c@colnum {##1}
    \tblr_set_vline:nnn {#1} {#2} {#3}
  }
  \group_end:
}

%% Check the number of arguments and call \tblr_set_every_vline in different ways
%% This function is called when parsing table specifications
\cs_new_protected:Npn \__tblr_set_every_vline_aux:n #1
{
  \tl_if_head_is_group:nTF {#1}
  {
    \int_compare:nNnTF { \tl_count:n {#1} } = {3}
    { \tblr_set_every_vline:nnn #1 }
    { \tblr_set_every_vline:nnn {1} #1 }
  }
  { \tblr_set_every_vline:nnn {1} {-} {#1} }
}

%% Add \SetVline, \vline and \rline commands

\tl_new:N \l__tblr_vline_count_tl % the count of all vlines
\tl_new:N \l__tblr_vline_num_tl % the index of the vline
\tl_new:N \l__tblr_vline_rows_tl % the rows of the vline
\tl_new:N \l__tblr_vline_dash_tl % dash style
\tl_new:N \l__tblr_vline_fg_tl % dash foreground

```

```

\tl_new:N \l__tblr_vline_wd_tl    % dash width

\NewTableCommand \rline [2] [] { \SetVline [=] {#2} {#1} }

\NewTableCommand \vline [1] [] { \SetVline [+ ] {-} {#1} }

%% #1: the index of the vline (may be + or =)
%% #2: which rows of the vline, separate by commas
%% #3: key=value pairs
\NewTableCommand \SetVline [3] [+ ]
{
  \tblr_set_vline:nnn {#1} {#2} {#3}
}

%% We need to check "text" key first
%% If it does exist and has empty value, then do nothing
\cs_new_protected:Npn \tblr_set_vline:nnn #1 #2 #3
{
  \group_begin:
  \keys_set_groups:nnn { tblr-vline } { text } {#3}
  \tl_if_eq:NnF \l__tblr_vline_dash_tl { \exp_not:N \@tblr@text }
  {
    \__tblr_set_vline_num:n {#1}
    \tl_clear:N \l__tblr_vline_dash_tl
    \keys_set:nn { tblr-vline } { dash = solid, #3 }
    \__tblr_set_vline_cmd:n {#2}
  }
  \group_end:
}

\cs_new_protected:Npn \tblr_set_vline:nnnn #1 #2 #3 #4
{
  \group_begin:
  \__tblr_get_childs:nx {#1} { \int_eval:n { \c@colcount + 1 } }
  \clist_map_inline:Nn \l__tblr_childs_clist
  {
    \int_set:Nn \c@colnum {##1}
    \tblr_set_vline:nnn {#2} {#3} {#4}
  }
  \group_end:
}

%% Check the number of arguments and call \tblr_set_vline in different ways
%% Note that #1 always includes an outer pair of braces
%% This function is called when parsing table specifications
\cs_new_protected:Npn \__tblr_set_vline_aux:nn #1 #2
{
  \tl_if_head_is_group:nTF {#2}
  {
    {
      \int_compare:nNnTF { \tl_count:n {#2} } = {3}
      { \tblr_set_vline:nnnn #1 #2 }
      { \tblr_set_vline:nnnn #1 {1} #2 }
    }
    { \tblr_set_vline:nnnn #1 {1} {-} {#2} }
  }
}

\cs_generate_variant:Nn \__tblr_set_vline_aux:nn { Vn }

```

```

%% #1: the index of vline to set (may be + or =)
\cs_new_protected:Npn \__tblr_set_vline_num:n #1
{
  \tl_clear:N \l__tblr_vline_num_tl
  \tl_set:Nx \l__tblr_vline_count_tl
    { \__tblr_spec_item:ne { vline } { [\int_use:N \c@colnum] / @vline-count } }
  %% \l__tblr_vline_count_tl may be empty when colspec has extra |'s
  \int_compare:nNnTF { \l__tblr_vline_count_tl + 0 } = {0}
  {
    \tl_set:Nx \l__tblr_vline_num_tl { 1 }
    \__tblr_spec_gput:nen { vline }
    { [\int_use:N \c@colnum] / @vline-count } { 1 }
  }
}

\tl_if_eq:nnTF {#1} {+}
{ \__tblr_set_vline_num_incr: }
{
  \tl_if_eq:nnTF {#1} {=}
  { \tl_set_eq:NN \l__tblr_vline_num_tl \l__tblr_vline_count_tl }
  {
    \int_compare:nNnTF {#1} > { \l__tblr_vline_count_tl }
    { \__tblr_set_vline_num_incr: }
    { \tl_set:Nn \l__tblr_vline_num_tl {#1} }
  }
}
}

\cs_new_protected:Npn \__tblr_set_vline_num_incr:
{
  \tl_set:Nx \l__tblr_vline_count_tl
    { \int_eval:n { \l__tblr_vline_count_tl + 1 } }
  \__tblr_spec_gput:nee { vline }
    { [\int_use:N \c@colnum] / @vline-count } { \l__tblr_vline_count_tl }
  \tl_set_eq:NN \l__tblr_vline_num_tl \l__tblr_vline_count_tl
}

\keys_define:nn { tblr-vline }
{
  dash .code:n = \tl_set:Nn \l__tblr_vline_dash_tl { \exp_not:N \@tblr@dash #1 },
  text .code:n = \tl_set:Nn \l__tblr_vline_dash_tl { \exp_not:N \@tblr@text #1 },
  text .groups:n = { text },
  wd .code:n = \tl_set:Nn \l__tblr_vline_wd_tl { \dim_eval:n {#1} },
  fg .code:n = \tl_set:Nn \l__tblr_vline_fg_tl {#1},
  unknown .code:n = \__tblr_vline_unknown_key:V \l_keys_key_str,
}

\cs_new_protected:Npn \__tblr_vline_unknown_key:n #1
{
  \prop_if_in:NnTF \g__tblr_defined_vdash_styles_prop {#1}
  { \tl_set:Nn \l__tblr_vline_dash_tl { \exp_not:N \@tblr@dash #1 } }
  {
    \regex_match:NnTF \c__tblr_is_color_key_regex {#1}
    { \tl_set:Nn \l__tblr_vline_fg_tl {#1} }
    {
      \tl_set_rescan:Nnn \l__tblr_v_tl {} {#1}
      \tl_set:Nn \l__tblr_vline_wd_tl { \dim_eval:n {\l__tblr_v_tl} }
    }
  }
}

```

```

    }
  }
}
\cs_generate_variant:Nn \_tblr_vline_unknown_key:n { V }

\cs_new_protected_nopar:Npn \_tblr_set_vline_cmd:n #1
{
  \_tblr_get_childs:nx {#1} { \int_use:N \c@rowcount }
  \clist_map_inline:Nn \l_tblr_childs_clist
  {
    \_tblr_spec_gput:nee { vline }
    { [##1][\int_use:N \c@colnum](\l_tblr_vline_num_tl) / @dash }
    { \l_tblr_vline_dash_tl }
    \tl_if_empty:NF \l_tblr_vline_wd_tl
    {
      \_tblr_spec_gput:nee { vline }
      { [##1][\int_use:N \c@colnum](\l_tblr_vline_num_tl) / wd }
      { \l_tblr_vline_wd_tl }
    }
    \tl_if_empty:NF \l_tblr_vline_fg_tl
    {
      \_tblr_spec_gput:nee { vline }
      { [##1][\int_use:N \c@colnum](\l_tblr_vline_num_tl) / fg }
      { \l_tblr_vline_fg_tl }
    }
  }
}

%%% -----
%% \section{Set Cells}
%%% -----

%% \SetCells command for setting every cell in the table
\NewTableCommand \SetCells [2] []
{
  \tblr_set_every_cell:n {#1} {#2}
}

%% We put all code inside a group to avoid affecting other table commands
\cs_new_protected:Npn \tblr_set_every_cell:n #1 #2
{
  \group_begin:
  \int_step_inline:nn { \c@rowcount }
  {
    \int_set:Nn \c@rownum {##1}
    \int_step_inline:nn { \c@colcount }
    {
      \int_set:Nn \c@colnum {####1}
      \tblr_set_cell:n {#1} {#2}
    }
  }
  \group_end:
}

%% Check the number of arguments and call \tblr_set_every_cell in different ways
%% This function is called when parsing table specifications
\cs_new_protected:Npn \_tblr_set_every_cell_aux:n #1

```

```

{
  \tl_if_head_is_group:nTF {#1}
    { \tblr_set_every_cell:nn #1 }
    { \tblr_set_every_cell:nn {} {#1} }
}

%% \SetCell command for multirow and/or multicolumn cells

\NewTableCommand \SetCell [2] []
{
  \tblr_set_cell:nn { #1 } { #2 }
}

\tl_new:N \l__tblr_row_span_num_tl
\tl_new:N \l__tblr_col_span_num_tl

\cs_new_protected:Npn \tblr_set_cell:nn #1 #2
{
  \tl_set:Nn \l__tblr_row_span_num_tl { 1 }
  \tl_set:Nn \l__tblr_col_span_num_tl { 1 }
  \keys_set:nn { tblr-cell-span } { #1 }
  \keys_set:nn { tblr-cell-spec } { #2 }
  \__tblr_set_span_spec:VV \l__tblr_row_span_num_tl \l__tblr_col_span_num_tl
}
\cs_generate_variant:Nn \tblr_set_cell:nn { nV }

\cs_new_protected:Npn \tblr_set_cell:nmnn #1 #2 #3 #4
{
  \group_begin:
  \__tblr_get_childs:nx {#1} { \int_use:N \c@rowcount }
  \clist_set_eq:NN \l_tmpa_clist \l_tblr_childs_clist
  \__tblr_get_childs:nx {#2} { \int_use:N \c@colcount }
  \clist_set_eq:NN \l_tmpb_clist \l_tblr_childs_clist
  \clist_map_inline:Nn \l_tmpa_clist
  {
    \int_set:Nn \c@rownum {##1}
    \clist_map_inline:Nn \l_tmpb_clist
    {
      \int_set:Nn \c@colnum {####1}
      \tblr_set_cell:nn {#3} {#4}
    }
  }
  \group_end:
}

%% Check the number of arguments and call \tblr_set_cell in different ways
%% Note that #1 is always of the type {<i>}{<j>}
%% This function is called when parsing table specifications
\cs_new_protected:Npn \__tblr_set_cell_aux:nn #1 #2
{
  \tl_if_head_is_group:nTF {#2}
    { \tblr_set_cell:nmnn #1 #2 }
    { \tblr_set_cell:nmnn #1 {} {#2} }
}
\cs_generate_variant:Nn \__tblr_set_cell_aux:nn { Vn }

```

```

\keys_define:nn { tblr-cell-span }
{
  r .tl_set:N = \l__tblr_row_span_num_tl,
  c .tl_set:N = \l__tblr_col_span_num_tl,
}

\keys_define:nn { tblr-cell-spec }
{
  halign .code:n = \__tblr_cell_gput:nn { halign } {#1},
  valign .code:n = \__tblr_cell_gput:nn { valign } {#1},
  l .meta:n = { halign = l },
  c .meta:n = { halign = c },
  r .meta:n = { halign = r },
  t .meta:n = { valign = t },
  p .meta:n = { valign = t },
  m .meta:n = { valign = m },
  b .meta:n = { valign = b },
  h .meta:n = { valign = h },
  f .meta:n = { valign = f },
  wd .code:n = \__tblr_cell_gput:ne { width } {#1},
  bg .code:n = \__tblr_cell_gput:ne { background } {#1},
  preto .code:n = \__tblr_cell_preto_text:n {#1},
  appto .code:n = \__tblr_cell_appto_text:n {#1},
  cmd .code:n = \__tblr_cell_process_text:n {#1},
  fg .code:n = \__tblr_cell_preto_text:n { \color{#1} },
  font .code:n = \__tblr_cell_gput:nn { font } { #1 \selectfont },
  unknown .code:n = \__tblr_cell_unknown_key:V \l_keys_key_str,
}

\cs_new_protected:Npn \__tblr_cell_gput:nn #1 #2
{
  \__tblr_data_gput:neenn { cell }
  { \int_use:N \c@rownum } { \int_use:N \c@colnum } {#1} {#2}
}

\cs_generate_variant:Nn \__tblr_cell_gput:nn { ne }

\cs_new_protected:Npn \__tblr_cell_gput:nnnn #1 #2 #3 #4
{
  \__tblr_data_gput:nnnn { cell } {#1} {#2} {#3} {#4}
}

\cs_generate_variant:Nn \__tblr_cell_gput:nnnn
{ nenn, ennn, eenn, nene, enne, eene }

\tl_new:N \l__tblr_cell_text_tl

\cs_new_protected:Npn \__tblr_cell_preto_text:n #1
{
  \__tblr_cell_preto_text:een
  { \int_use:N \c@rownum } { \int_use:N \c@colnum } {#1}
}

\cs_new_protected:Npn \__tblr_cell_preto_text:nnn #1 #2 #3
{
  \tl_set:Nx \l__tblr_cell_text_tl { \__tblr_spec_item:nn { text } { [#1][#2] } }
  \tl_put_left:Nn \l__tblr_cell_text_tl {#3}
  \__tblr_spec_gput:nnV { text } { [#1][#2] } \l__tblr_cell_text_tl
}

```

```

}
\cs_generate_variant:Nn \__tblr_cell_preto_text:nnn { nen, enn, een }

\cs_new_protected:Npn \__tblr_cell_appto_text:n #1
{
  \__tblr_cell_appto_text:een
  { \int_use:N \c@rownum } { \int_use:N \c@colnum } {#1}
}

\cs_new_protected:Npn \__tblr_cell_appto_text:nnn #1 #2 #3
{
  \tl_set:Nx \l__tblr_cell_text_tl { \__tblr_spec_item:ne { text } { [#1][#2] } }
  \tl_put_right:Nn \l__tblr_cell_text_tl {#3}
  \__tblr_spec_gput:neV { text } { [#1][#2] } \l__tblr_cell_text_tl
}
\cs_generate_variant:Nn \__tblr_cell_appto_text:nnn { nen, enn, een }

\cs_new_protected:Npn \__tblr_cell_process_text:n #1
{
  \__tblr_cell_process_text:een
  { \int_use:N \c@rownum } { \int_use:N \c@colnum } {#1}
}

\cs_new_protected:Npn \__tblr_cell_process_text:nnn #1 #2 #3
{
  \tl_set:Nx \l__tblr_cell_text_tl
  {
    { \__tblr_spec_item:nn { text } { [#1][#2] } }
  }
  \tl_put_left:Nn \l__tblr_cell_text_tl {#3}
  \__tblr_spec_gput:nnV { text } { [#1][#2] } \l__tblr_cell_text_tl
}
\cs_generate_variant:Nn \__tblr_cell_process_text:nnn { nen, enn, een }

\cs_new_protected:Npn \__tblr_cell_unknown_key:n #1
{
  \regex_match:NnTF \c__tblr_is_color_key_regex {#1}
  {
    \__tblr_data_gput:neene { cell }
    { \int_use:N \c@rownum } { \int_use:N \c@colnum } { background } {#1}
  }
  {
    \tl_set_rescan:Nnn \l__tblr_v_tl {} {#1}
    \__tblr_data_gput:neene { cell }
    { \int_use:N \c@rownum } { \int_use:N \c@colnum } { width }
    { \dim_eval:n { \l__tblr_v_tl } }
  }
}
\cs_generate_variant:Nn \__tblr_cell_unknown_key:n { V }

\cs_new_protected:Npn \__tblr_set_span_spec:nn #1 #2
{
  \int_compare:nNnT { #1 } > { 1 }
  {
    \__tblr_prop_gput:nnn { inner } { rowspan } { true }
    \__tblr_data_gput:neenn { cell }
  }
}

```

```

        { \int_use:N \c@rownum } { \int_use:N \c@colnum } { rowspan } {#1}
    }
\int_compare:nNnT { #2 } > { 1 }
{
    \__tblr_prop_gput:nnn { inner } { colspan } { true }
    \__tblr_data_gput:neenn { cell }
        { \int_use:N \c@rownum } { \int_use:N \c@colnum } { colspan } {#2}
    }
\int_step_variable:nnNn
{ \int_use:N \c@rownum } { \int_eval:n { \c@rownum + #1 - 1 } } \l__tblr_i_tl
{
    \int_step_variable:nnNn
        { \int_use:N \c@colnum } { \int_eval:n { \c@colnum + #2 - 1 } }
        \l__tblr_j_tl
        {
            \bool_lazy_and:nnF
                { \int_compare_p:nNn { \l__tblr_i_tl } = { \c@rownum } }
                { \int_compare_p:nNn { \l__tblr_j_tl } = { \c@colnum } }
            {
                \__tblr_data_gput:neenn { cell }
                    { \l__tblr_i_tl } { \l__tblr_j_tl } { omit } {1}
            }
            \int_compare:nNnF { \l__tblr_i_tl } = { \c@rownum }
            {
                \__tblr_spec_gput:nen { hline }
                    { [\l__tblr_i_tl][\l__tblr_j_tl] / omit } {true}
            }
            \int_compare:nNnF { \l__tblr_j_tl } = { \c@colnum }
            {
                \__tblr_spec_gput:nee { vline }
                    { [\l__tblr_i_tl][\l__tblr_j_tl] / omit } {true}
            }
        }
    }
}
}
}
\cs_generate_variant:Nn \__tblr_set_span_spec:nn { VV }

%% Legacy \multicolumn and \multirow commands
%% Both of them could be replaced with \SetCell command
%% Note that they don't have cell text as the last arguments

%% If \multicolumn is followed by \multirow,
%% We need to call \tblr_set_cell together
%% in order to omit all hlines inside the span cell.
\tl_new:N \g__tblr_multicolumn_num_tl
\tl_new:N \g__tblr_multicolumn_spec_tl

%% There maybe p{2em} inside #2 of \multicolumn command
\NewTableCommand \multicolumn [2]
{
    \tl_gclear:N \g__tblr_multicolumn_num_tl
    \tl_gclear:N \g__tblr_multicolumn_spec_tl
    \tl_map_inline:nn {#2}
    {
        \bool_lazy_and:nnF
            { \tl_if_single_token_p:n {##1} }
            { \token_if_eq_charcode_p:NN ##1 | }
    }
}

```

```

        { \tl_put_right:Nn \g__tblr_multicolumn_spec_tl {,##1} }
    }
\peek_meaning:NTF \multirow
{ \tl_gset:Nn \g__tblr_multicolumn_num_tl {#1} }
{ \tblr_set_cell:nV { c = #1 } \g__tblr_multicolumn_spec_tl }
}

\NewTableCommand \multirow [3] [m]
{
  \tl_if_eq:nnTF {#1} {c}
  { \tl_set:Nn \l_tmpa_tl {, m} }
  {
    \tl_if_eq:nnTF {#1} {t}
    { \tl_set:Nn \l_tmpa_tl {, h} }
    { \tl_if_eq:nnTF {#1} {b}
      { \tl_set:Nn \l_tmpa_tl {, f} }
      { \tl_set:Nn \l_tmpa_tl {, #1} }
    }
  }
  \tl_if_eq:nnF {#3} {*}
  { \tl_if_eq:nnF {#3} {=} { \tl_put_right:Nn \l_tmpa_tl {, wd=#3} } }
  \tl_if_empty:NTF \g__tblr_multicolumn_num_tl
  { \tblr_set_cell:nV { r = #2 } \l_tmpa_tl }
  {
    \tl_put_left:NV \l_tmpa_tl \g__tblr_multicolumn_spec_tl
    \exp_args:Nx \tblr_set_cell:nV
      { c = \g__tblr_multicolumn_num_tl, r = #2 } \l_tmpa_tl
    \tl_gclear:N \g__tblr_multicolumn_num_tl
  }
}

%%% -----
%%% \section{Set Columns and Rows}
%%% -----

%% \SetColumns command for setting every column in the table
\NewTableCommand \SetColumns [2] []
{
  \tblr_set_every_column:nn {#1} {#2}
}

%% We put all code inside a group to avoid affecting other table commands
\cs_new_protected:Npn \tblr_set_every_column:#1 #2
{
  \group_begin:
  \int_step_inline:nn { \c@colcount }
  {
    \int_set:Nn \c@colnum {##1}
    \tblr_set_column:nn {#1} {#2}
  }
  \group_end:
}

%% Check the number of arguments and call \tblr_set_every_column in different ways
%% This function is called when parsing table specifications
\cs_new_protected:Npn \__tblr_set_every_column_aux:n #1
{

```

```

\l_if_head_is_group:nTF {#1}
  { \tblr_set_every_column:nn #1 }
  { \tblr_set_every_column:nn {} {#1} }
}

%% \SetColumn command for current column or each cells in the column

\NewTableCommand \SetColumn [2] []
{
  \tblr_set_column:nn {#1} {#2}
}

\cs_new_protected:Npn \tblr_set_column:nn #1 #2
{
  \keys_set:nn { tblr-column } {#2}
}

\cs_new_protected:Npn \tblr_set_column:nnn #1 #2 #3
{
  \group_begin:
  \__tblr_get_childs:nx {#1} { \int_use:N \c@colcount }
  \clist_map_inline:Nn \l_tblr_childs_clist
  {
    \int_set:Nn \c@colnum {##1}
    \tblr_set_column:nn {#2} {#3}
  }
  \group_end:
}

%% Check the number of arguments and call \tblr_set_column in different ways
%% Note that #1 always includes an outer pair of braces
%% This function is called when parsing table specifications
\cs_new_protected:Npn \__tblr_set_column_aux:nn #1 #2
{
  \l_if_head_is_group:nTF {#2}
  { \tblr_set_column:nnn #1 #2 }
  { \tblr_set_column:nnn #1 {} {#2} }
}

\cs_generate_variant:Nn \__tblr_set_column_aux:nn { Vn }

\keys_define:nn { tblr-column }
{
  halign .code:n = \__tblr_column_gput_cell:nn { halign } {#1},
  valign .code:n = \__tblr_column_gput_cell:nn { valign } {#1},
  l .meta:n = { halign = l },
  c .meta:n = { halign = c },
  r .meta:n = { halign = r },
  t .meta:n = { valign = t },
  p .meta:n = { valign = t },
  m .meta:n = { valign = m },
  b .meta:n = { valign = b },
  h .meta:n = { valign = h },
  f .meta:n = { valign = f },
  bg .code:n = \__tblr_column_gput_cell:nn { background } {#1},
  fg .code:n = \__tblr_preto_text_for_every_column_cell:n { \color{#1} },
  font .code:n = \__tblr_column_gput_cell:nn { font } { #1 \selectfont },
}

```

```

wd      .code:n = \__tblr_column_gput:ne { width } { \dim_eval:n {#1} },
co      .code:n = \__tblr_column_gput:ne { coefficient } {#1},
preto   .code:n = \__tblr_preto_text_for_every_column_cell:n {#1},
appto   .code:n = \__tblr_appto_text_for_every_column_cell:n {#1},
cmd      .code:n = \__tblr_process_text_for_every_column_cell:n {#1},
leftsep .code:n = \__tblr_column_gput:ne { leftsep } { \dim_eval:n {#1} },
rightsep .code:n = \__tblr_column_gput:ne { rightsep } { \dim_eval:n {#1} },
colsep  .meta:n = { leftsep = #1, rightsep = #1},
leftsep+ .code:n = \__tblr_column_gadd_dimen:ne
          { leftsep } { \dim_eval:n {#1} },
rightsep+ .code:n = \__tblr_column_gadd_dimen:ne
          { rightsep } { \dim_eval:n {#1} },
colsep+  .meta:n = { leftsep+ = #1, rightsep+ = #1},
unknown  .code:n = \__tblr_column_unknown_key:V \l_keys_key_str,
}

%% #1: key; #2: value
\cs_new_protected:Npn \__tblr_column_gput:nn #1 #2
{
  \__tblr_data_gput:nenn { column } { \int_use:N \c@colnum } {#1} {#2}
}
\cs_generate_variant:Nn \__tblr_column_gput:nn { ne }

\cs_new_protected:Npn \__tblr_column_gadd_dimen:nn #1 #2
{
  \__tblr_data_gadd_dimen_value:nenn { column }
    { \int_use:N \c@colnum } {#1} {#2}
}
\cs_generate_variant:Nn \__tblr_column_gadd_dimen:nn { ne }

%% #1: key; #2: value
\cs_new_protected:Npn \__tblr_column_gput_cell:nn #1 #2
{
  \int_step_inline:nn { \c@rowcount }
  {
    \__tblr_cell_gput:nenn {##1} { \int_use:N \c@colnum } {#1} {#2}
  }
}
\cs_generate_variant:Nn \__tblr_column_gput_cell:nn { ne }

\cs_new_protected:Npn \__tblr_preto_text_for_every_column_cell:n #1
{
  \int_step_inline:nn { \c@rowcount }
  {
    \__tblr_cell_preto_text:nen {##1} { \int_use:N \c@colnum } {#1}
  }
}

\cs_new_protected:Npn \__tblr_appto_text_for_every_column_cell:n #1
{
  \int_step_inline:nn { \c@rowcount }
  {
    \__tblr_cell_appto_text:nen {##1} { \int_use:N \c@colnum } {#1}
  }
}

\cs_new_protected:Npn \__tblr_process_text_for_every_column_cell:n #1

```

```

{
  \int_step_inline:nn { \c@rowcount }
  {
    \__tblr_cell_process_text:nen {##1} { \int_use:N \c@colnum } {#1}
  }
}

\regex_const:Nn \c__tblr_is_number_key_regex { ^[\+|-]? (\d+|\d*\.\d+)$ }

\cs_new_protected:Npn \__tblr_column_unknown_key:n #1
{
  \regex_match:NnTF \c__tblr_is_number_key_regex {#1}
  { \__tblr_column_gput:ne { coefficient } {#1} }
  {
    \regex_match:NnTF \c__tblr_is_color_key_regex {#1}
    { \__tblr_column_gput_cell:nn { background } {#1} }
    {
      \tl_set_rescan:Nnn \l__tblr_v_tl {} {#1}
      \__tblr_column_gput:ne { width } { \dim_eval:n { \l__tblr_v_tl } }
    }
  }
}

\cs_generate_variant:Nn \__tblr_column_unknown_key:n { V }

%% \SetRows command for setting every row in the table
\NewTableCommand \SetRows [2] []
{
  \tblr_set_every_row:nn {#1} {#2}
}

%% We put all code inside a group to avoid affecting other table commands
\cs_new_protected:Npn \tblr_set_every_row:nn #1 #2
{
  \group_begin:
  \int_step_inline:nn { \c@rowcount }
  {
    \int_set:Nn \c@rownum {##1}
    \tblr_set_row:nn {#1} {#2}
  }
  \group_end:
}

%% Check the number of arguments and call \tblr_set_every_row in different ways
%% This function is called when parsing table specifications
\cs_new_protected:Npn \__tblr_set_every_row_aux:n #1
{
  \tl_if_head_is_group:nTF {#1}
  { \tblr_set_every_row:nn #1 }
  { \tblr_set_every_row:nn {} {#1} }
}

%% \SetRow command for current row or each cells in the row

\NewTableCommand \SetRow [2] []
{
  \tblr_set_row:nn {#1} {#2}
}

```

```

}

\cs_new_protected:Npn \tblr_set_row:nn #1 #2
{
  \keys_set:nn { tblr-row } {#2}
}

\cs_new_protected:Npn \tblr_set_row:nnn #1 #2 #3
{
  \group_begin:
  \__tblr_get_childs:nx {#1} { \int_use:N \c@rowcount }
  \clist_map_inline:Nn \l__tblr_childs_clist
  {
    \int_set:Nn \c@rownum {##1}
    \tblr_set_row:nn {#2} {#3}
  }
  \group_end:
}

%% Check the number of arguments and call \tblr_set_row in different ways
%% Note that #1 always includes an outer pair of braces
%% This function is called when parsing table specifications
\cs_new_protected:Npn \__tblr_set_row_aux:nn #1 #2
{
  \tl_if_head_is_group:nTF {#2}
  { \tblr_set_row:nnn #1 #2 }
  { \tblr_set_row:nnn #1 {} {#2} }
}

\cs_generate_variant:Nn \__tblr_set_row_aux:nn { Vn }

\keys_define:nn { tblr-row }
{
  halign .code:n = \__tblr_row_gput_cell:nn { halign } {#1},
  valign .code:n = \__tblr_row_gput_cell:nn { valign } {#1},
  l .meta:n = { halign = l },
  c .meta:n = { halign = c },
  r .meta:n = { halign = r },
  t .meta:n = { valign = t },
  p .meta:n = { valign = t },
  m .meta:n = { valign = m },
  b .meta:n = { valign = b },
  h .meta:n = { valign = h },
  f .meta:n = { valign = f },
  bg .code:n = \__tblr_row_gput_cell:nn { background } {#1},
  fg .code:n = \__tblr_preto_text_for_every_row_cell:n { \color{#1} },
  font .code:n = \__tblr_row_gput_cell:nn { font } { #1 \selectfont },
  ht .code:n = \__tblr_row_gput:ne { height } { \dim_eval:n {#1} },
  co .code:n = \__tblr_row_gput:ne { coefficient } {#1},
  preto .code:n = \__tblr_preto_text_for_every_row_cell:n {#1},
  appto .code:n = \__tblr_appto_text_for_every_row_cell:n {#1},
  cmd .code:n = \__tblr_process_text_for_every_row_cell:n {#1},
  abovesep .code:n = \__tblr_row_gput:ne { abovesep } { \dim_eval:n {#1} },
  belowsep .code:n = \__tblr_row_gput:ne { belowsep } { \dim_eval:n {#1} },
  rowsep .meta:n = { abovesep = #1, belowsep = #1},
  abovesep+ .code:n = \__tblr_row_gadd_dimen:ne { abovesep } { \dim_eval:n {#1} },
  belowsep+ .code:n = \__tblr_row_gadd_dimen:ne { belowsep } { \dim_eval:n {#1} },
  rowsep+ .meta:n = { abovesep+ = #1, belowsep+ = #1},

```

```

nobreak    .code:n = \__tblr_prop_gput:nxx { row }
            { [\int_eval:n {\c@rownum - 1}] / nobreak } { true },
unknown    .code:n = \__tblr_row_unknown_key:V \l_keys_key_str,
}

%% #1: key; #2: value
\cs_new_protected:Npn \__tblr_row_gput:nn #1 #2
{
  \__tblr_data_gput:nenn { row } { \int_use:N \c@rownum } {#1} {#2}
}
\cs_generate_variant:Nn \__tblr_row_gput:nn { ne }

\cs_new_protected:Npn \__tblr_row_gadd_dimen:nn #1 #2
{
  \__tblr_data_gadd_dimen_value:nenn { row } { \int_use:N \c@rownum } {#1} {#2}
}
\cs_generate_variant:Nn \__tblr_row_gadd_dimen:nn { ne }

%% #1: key; #2: value
\cs_new_protected:Npn \__tblr_row_gput_cell:nn #1 #2
{
  \int_step_inline:nn { \c@colcount }
  {
    \__tblr_cell_gput:ennn { \int_use:N \c@rownum } {##1} {#1} {#2}
  }
}
\cs_generate_variant:Nn \__tblr_row_gput_cell:nn { ne }

\cs_new_protected:Npn \__tblr_preto_text_for_every_row_cell:n #1
{
  \int_step_inline:nn { \c@colcount }
  {
    \__tblr_cell_preto_text:enn { \int_use:N \c@rownum } {##1} {#1}
  }
}

\cs_new_protected:Npn \__tblr_appto_text_for_every_row_cell:n #1
{
  \int_step_inline:nn { \c@colcount }
  {
    \__tblr_cell_appto_text:enn { \int_use:N \c@rownum } {##1} {#1}
  }
}

\cs_new_protected:Npn \__tblr_process_text_for_every_row_cell:n #1
{
  \int_step_inline:nn { \c@colcount }
  {
    \__tblr_cell_process_text:enn { \int_use:N \c@rownum } {##1} {#1}
  }
}

\cs_new_protected:Npn \__tblr_row_unknown_key:n #1
{
  \regex_match:NnTF \c__tblr_is_number_key_regex {#1}
  {

```

```

    \_tblr_data_gput:nene { row } { \int_use:N \c@rownum }
      { coefficient } {#1}
    }
  {
    \regex_match:NnTF \c__tblr_is_color_key_regex {#1}
      { \_tblr_row_gput_cell:nn { background } {#1} }
      {
        \tl_set_rescan:Nnn \l__tblr_v_tl {} {#1}
        \_tblr_row_gput:ne { height } { \dim_eval:n { \l__tblr_v_tl } }
      }
    }
  }
}
\cs_generate_variant:Nn \_tblr_row_unknown_key:n { V }

%%% -----
%% \section{Column Types and Row Types}
%%% -----

%% Some primitive column/row types

\str_const:Nn \c_tblr_primitive_colrow_types_str { Q | < > }
\tl_new:N \g__tblr_expanded_colrow_spec_tl

\exp_args:Nc \NewDocumentCommand { tblr_primitive_column_type_Q } { 0{} }
{
  \keys_set:nn { tblr-column } { #1 }
  \int_incr:N \c@colnum
  \_tblr_execute_colrow_spec_next:N
}
\exp_args:Nc \NewDocumentCommand { tblr_column_type_Q } { 0{} }
{
  \tl_gput_right:Nn \g__tblr_expanded_colrow_spec_tl { Q[#1] }
  \_tblr_expand_colrow_spec_next:N
}

\exp_args:Nc \NewDocumentCommand { tblr_primitive_row_type_Q } { 0{} }
{
  \keys_set:nn { tblr-row } { #1 }
  \int_incr:N \c@rownum
  \_tblr_execute_colrow_spec_next:N
}
\exp_args:Nc \NewDocumentCommand { tblr_row_type_Q } { 0{} }
{
  \tl_gput_right:Nn \g__tblr_expanded_colrow_spec_tl { Q[#1] }
  \_tblr_expand_colrow_spec_next:N
}

\exp_args:Nc \NewDocumentCommand { tblr_primitive_column_type_ | } { 0{} }
{
  \vline [#1]
  \_tblr_execute_colrow_spec_next:N
}
\exp_args:Nc \NewDocumentCommand { tblr_column_type_ | } { 0{} }
{
  \tl_gput_right:Nn \g__tblr_expanded_colrow_spec_tl { |[#1] }
  \_tblr_expand_colrow_spec_next:N
}

```

```

}

\exp_args:Nc \NewDocumentCommand { tblr_primitive_row_type_ | } { 0{} }
{
  \hline [#1]
  \__tblr_execute_colrow_spec_next:N
}

\exp_args:Nc \NewDocumentCommand { tblr_row_type_ | } { 0{} }
{
  \tl_gput_right:Nn \g__tblr_expanded_colrow_spec_tl { |[#1] }
  \__tblr_expand_colrow_spec_next:N
}

\exp_args:Nc \NewDocumentCommand { tblr_primitive_column_type_ > } { 0{} m }
{
  \tl_if_blank:nF {#1}
  {
    \__tblr_data_gput:nene
    { column }
    { \int_use:N \c@colnum } { leftsep }
    { \dim_eval:n {#1} }
  }
  \tl_if_blank:nF {#2}
  {
    \__tblr_preto_text_for_every_column_cell:n {#2}
  }
  \__tblr_execute_colrow_spec_next:N
}

\exp_args:Nc \NewDocumentCommand { tblr_column_type_ > } { 0{} m }
{
  \tl_gput_right:Nn \g__tblr_expanded_colrow_spec_tl { >[#1]{#2} }
  \__tblr_expand_colrow_spec_next:N
}

\exp_args:Nc \NewDocumentCommand { tblr_primitive_row_type_ > } { 0{} m }
{
  \tl_if_blank:nF {#1}
  {
    \__tblr_data_gput:nene { row } { \int_use:N \c@rownum }
    { abovesep } { \dim_eval:n { #1 } }
  }
  \tl_if_blank:nF {#2}
  {
    \__tblr_preto_text_for_every_row_cell:n {#2}
  }
  \__tblr_execute_colrow_spec_next:N
}

\exp_args:Nc \NewDocumentCommand { tblr_row_type_ > } { 0{} m }
{
  \tl_gput_right:Nn \g__tblr_expanded_colrow_spec_tl { >[#1]{#2} }
  \__tblr_expand_colrow_spec_next:N
}

\exp_args:Nc \NewDocumentCommand { tblr_primitive_column_type_ < } { 0{} m }
{
  \tl_if_blank:nF {#1}
  {

```

```

    \tblr_data_gput:nene { column }
      { \int_eval:n {\c@colnum - 1} } { rightsep } { \dim_eval:n {#1} }
  }
  \tblr_if_blank:nF {#2}
  {
    \group_begin:
    \int_decr:N \c@colnum
    \tblr_appto_text_for_every_column_cell:n {#2}
    \group_end:
  }
  \tblr_execute_colrow_spec_next:N
}
\exp_args:Nc \NewDocumentCommand { tblr_column_type_ < } { 0 } m }
{
  \tblr_gput_right:Nn \g__tblr_expanded_colrow_spec_tl { <[#1]{#2} }
  \tblr_expand_colrow_spec_next:N
}

\exp_args:Nc \NewDocumentCommand { tblr_primitive_row_type_ < } { 0 } m }
{
  \tblr_if_blank:nF {#1}
  {
    \tblr_data_gput:nene { row } { \int_eval:n {\c@rownum - 1} }
      { belowsep } { \dim_eval:n {#1} }
  }
  \tblr_if_blank:nF {#2}
  {
    \group_begin:
    \int_decr:N \c@rownum
    \tblr_appto_text_for_every_row_cell:n {#2}
    \group_end:
  }
  \tblr_execute_colrow_spec_next:N
}
\exp_args:Nc \NewDocumentCommand { tblr_row_type_ < } { 0 } m }
{
  \tblr_gput_right:Nn \g__tblr_expanded_colrow_spec_tl { <[#1]{#2} }
  \tblr_expand_colrow_spec_next:N
}

%% \NewColumnType/\NewRowType command and predefined column/row types

\str_new:N \g__tblr_used_column_types_str
\str_gset_eq:NN \g__tblr_used_column_types_str \c__tblr_primitive_colrow_types_str

\str_new:N \g__tblr_used_row_types_str
\str_gset_eq:NN \g__tblr_used_row_types_str \c__tblr_primitive_colrow_types_str

\bool_new:N \g__tblr_colrow_spec_expand_stop_bool
\tl_new:N \g__tblr_column_or_row_tl

\msg_new:nnn { tabularray } { used-colrow-type }
  { #1 ~ type ~ name ~ #2 ~ has ~ been ~ used! }

\NewDocumentCommand \NewColumnType { m 0 } o m }
{

```

```

\__tblr_new_column_or_row_type:nnnn {#1} {#2} {#3} {#4}
}

\NewDocumentCommand \NewRowType { m O{0} o m }
{
\__tblr_new_column_or_row_type:nnnn {#1} {#2} {#3} {#4}
}

\NewDocumentCommand \NewColumnRowType { m O{0} o m }
{
\__tblr_new_column_or_row_type:nnnn {#1} {#2} {#3} {#4}
\__tblr_new_column_or_row_type:nnnn {#1} {#2} {#3} {#4}
}

\cs_new_protected:Npn \__tblr_new_column_or_row_type:nnnn #1 #2 #3 #4
{
\str_if_in:cnTF { g_tblr_used_ \g__tblr_column_or_row_tl _types_str } {#1}
{
\__tblr_new_column_or_row_type:nnnn {#1} {#2} {#3} {#4}
\msg_warning:nnnn { tabularray } { used-colrow-type } { Row } {#1} }
\msg_warning:nnnn { tabularray } { used-colrow-type } { Column } {#1} }
\str_log:c { g_tblr_used_ \g__tblr_column_or_row_tl _types_str }
}
}

\__tblr_make_xparse_arg_spec:nnN {#2} {#3} \l__tblr_a_tl
\exp_args:NcV \NewDocumentCommand
{ tblr_ \g__tblr_column_or_row_tl _type_ #1 } \l__tblr_a_tl
{
\bool_gset_false:N \g__tblr_colrow_spec_expand_stop_bool
\__tblr_expand_colrow_spec_next:N
}
\str_gput_right:cn
{ g_tblr_used_ \g__tblr_column_or_row_tl _types_str } {#1}
}
}

\NewColumnRowType { l } { Q[l] }
\NewColumnRowType { c } { Q[c] }
\NewColumnRowType { r } { Q[r] }

\NewColumnType { t } [1] { Q[t,wd=#1] }
\NewColumnType { p } [1] { Q[p,wd=#1] }
\NewColumnType { m } [1] { Q[m,wd=#1] }
\NewColumnType { b } [1] { Q[b,wd=#1] }
\NewColumnType { h } [1] { Q[h,wd=#1] }
\NewColumnType { f } [1] { Q[f,wd=#1] }

\NewRowType { t } [1] { Q[t,ht=#1] }
\NewRowType { p } [1] { Q[p,ht=#1] }
\NewRowType { m } [1] { Q[m,ht=#1] }
\NewRowType { b } [1] { Q[b,ht=#1] }

```

```

\NewRowType { h } [1] { Q[h,ht=#1] }
\NewRowType { f } [1] { Q[f,ht=#1] }

\NewColumnRowType { X } [1] [] { Q[co=1,#1] }

\NewColumnRowType { ! } [1] { |[text={#1}] }
\NewColumnRowType { @ } [1] { <[Opt]{} |[text={#1}] >[Opt]{} }
\NewColumnRowType { * } [2] { \prg_replicate:nn {#1} {#2} }

\cs_new_protected:Npn \__tblr_parse_colrow_spec:nn #1 #2
{
  \tl_gset:Nn \g__tblr_column_or_row_tl {#1}
  \tl_gset:Nn \g__tblr_expanded_colrow_spec_tl {#2}
  \__tblr_expand_colrow_spec:N \g__tblr_expanded_colrow_spec_tl
  \__tblr_execute_colrow_spec:N \g__tblr_expanded_colrow_spec_tl
}

%% Expand defined column/row types

\cs_new_protected:Npn \__tblr_expand_colrow_spec:N #1
{
  \bool_do_until:Nn \g__tblr_colrow_spec_expand_stop_bool
  {
    \LogTblrTracing { colspec, rowspec }
    \bool_gset_true:N \g__tblr_colrow_spec_expand_stop_bool
    \tl_set_eq:NN \l_tmpa_tl #1
    \tl_gclear:N #1
    \exp_last_unbraced:NV
      \__tblr_expand_colrow_spec_next:N \l_tmpa_tl \scan_stop:
  }
}

\msg_new:nnn { tabularray } { unexpandable-colrow-type }
{ Unexpandable ~ command ~ #2 inside ~ #1 ~ type! }

\msg_new:nnn { tabularray } { unknown-colrow-type }
{ Unknown ~ #1 ~ type ~ #2! }

\cs_new_protected:Npn \__tblr_expand_colrow_spec_next:N #1
{
  \token_if_eq_catcode:NNTF #1 \scan_stop:
  {
    \token_if_eq_meaning:NNF #1 \scan_stop:
    {
      \msg_error:nnVn { tabularray } { unexpandable-colrow-type }
      \g__tblr_column_or_row_tl {#1}
    }
  }
  {
    \str_if_in:cnTF { g__tblr_used_ \g__tblr_column_or_row_tl _types_str } {#1}
    { \cs:w tblr_ \g__tblr_column_or_row_tl _type_ #1 \cs_end: }
    {
      \msg_error:nnVn { tabularray } { unknown-colrow-type }
      \g__tblr_column_or_row_tl {#1}
      \str_log:c { g__tblr_used_ \g__tblr_column_or_row_tl _types_str }
    }
  }
}

```

```

    }
}

%% Execute primitive column/row types

\cs_new_protected:Npn \__tblr_execute_colrow_spec:N #1
{
  \tl_if_eq:NnTF \g__tblr_column_or_row_tl { row }
    { \int_set:Nn \c@rownum {1} }
    { \int_set:Nn \c@colnum {1} }
  \exp_last_unbraced:NV \__tblr_execute_colrow_spec_next:N #1 \scan_stop:
}

\cs_new_protected:Npn \__tblr_execute_colrow_spec_next:N #1
{
  \token_if_eq_meaning:NNF #1 \scan_stop:
  { \cs:w tblr_primitive_ \g__tblr_column_or_row_tl _type_ #1 \cs_end: }
}

%%% -----
%% \section{Set Environments and New Environments}
%%% -----

\tl_new:N \l__tblr_initial_tblr_outer_tl
\tl_set:Nn \l__tblr_initial_tblr_outer_tl
{
  halign = c, valign = m, headsep = 6pt, footsep = 6pt,
  presep = 1.5\bigskipamount, postsep = 1.5\bigskipamount,
}

%% #1: env name; #2: specifications
\NewDocumentCommand \SetTblrInner { 0{tblr} m }
{
  \tl_put_right:cn { l__tblr_default_ #1 _inner_tl } { , #2 }
  \ignorespaces
}

\cs_new_eq:NN \SetTblrDefault \SetTblrInner

%% #1: env name; #2: specifications
\NewDocumentCommand \SetTblrOuter { 0{tblr} m }
{
  \tl_put_right:cn { l__tblr_default_ #1 _outer_tl } { , #2 }
  \ignorespaces
}

%% #1: env name
\NewDocumentCommand \NewTblrEnviron { m }
{
  \tl_new:c { l__tblr_default_ #1 _outer_tl }
  \tl_set_eq:cN { l__tblr_default_ #1 _outer_tl } \l__tblr_initial_tblr_outer_tl
  \tl_new:c { l__tblr_default_ #1 _inner_tl }
  \NewDocumentEnvironment {#1} { 0{c} m +b }
  {
    \__tblr_environ_code:nnnn {#1} {##1} {##2} {##3}
  } { }
  \ignorespaces
}

```

```

}

%% Create tblr and longtblr environments
\NewTblrEnviron { tblr }
\NewTblrEnviron { longtblr }
\SetTblrOuter [ longtblr ] { long }

\tl_new:N \l__tblr_env_name_tl
\bool_new:N \l__tblr_math_mode_bool

%% Main environment code
\cs_new_protected:Npn \__tblr_envIRON_code:nnnn #1 #2 #3 #4
{
  \int_gincr:N \g__tblr_table_count_int
  \tl_set:Nn \l__tblr_env_name_tl {#1}
  \mode_if_math:TF
    { \bool_set_true:N \l__tblr_math_mode_bool }
    { \bool_set_false:N \l__tblr_math_mode_bool }
  \__tblr_builder:nnn {#2} {#3} {#4}
}

%% Read, split and build the table
\cs_new_protected:Npn \__tblr_builder:nnn #1 #2 #3
{
  \int_gincr:N \g_tblr_level_int
  \__tblr_clear_prop_lists:
  \__tblr_clear_spec_lists:
  \__tblr_enable_table_commands:
  \LogTblrTracing { step = split ~ table}
  \__tblr_split_table:n {#3}
  \LogTblrTracing { command }
  \LogTblrTracing { step = init ~ table ~ outer ~ spec}
  \__tblr_init_table_outer_spec:
  \LogTblrTracing { outer }
  \LogTblrTracing { step = parse ~ table ~ options }
  \__tblr_parse_table_option:n {#1}
  \LogTblrTracing { option }
  \bool_if:NT \g__tblr_use_intarray_bool { \__tblr_init_table_data: }
  \LogTblrTracing { step = init ~ table ~ inner ~ spec}
  \__tblr_init_table_inner_spec:
  \LogTblrTracing { inner }
  \LogTblrTracing { step = parse ~ table ~ inner ~ spec}
  \__tblr_parse_table_spec:n {#2}
  \LogTblrTracing { step = execute ~ table ~ commands}
  \__tblr_execute_table_commands:
  \__tblr_disable_table_commands:
  \LogTblrTracing { step = calculate ~ cell ~ and ~ line ~ sizes}
  \__tblr_enable_content_commands:
  \__tblr_calc_cell_and_line_sizes:
  \LogTblrTracing { step = build ~ the ~ whole ~ table}
  \__tblr_build_whole:
  \int_gdecr:N \g_tblr_level_int
}

%%% -----
%% \section{Split Table Contents}
%%% -----

```

```

%% Insert and remove braces for nesting environments inside cells
%% These make line split and cell split workable
%% We need to replace N times for N level nestings
\regex_const:Nn \c__tblr_insert_braces_regex
{
  \c{begin} \cB\{ (\c[BE.*) \cE\} (.*) \c{end} \cB\{ (\c[BE.*) \cE\}
}
\tl_const:Nn \c__tblr_insert_braces_tl
{
  \c{begin} \cB\{ \cB\{ \1 \cE\} \2 \c{end} \cE\} \cB\{ \3 \cE\}
}
\regex_const:Nn \c__tblr_remove_braces_regex
{
  \c{begin} \cB\{ \cB\{ (.*) \c{end} \cE\}
}
\tl_const:Nn \c__tblr_remove_braces_tl
{
  \c{begin} \cB\{ \1 \c{end}
}
\cs_new_protected:Npn \__tblr_insert_braces:N #1
{
  \regex_replace_all:NVN \c__tblr_insert_braces_regex \c__tblr_insert_braces_tl #1
  \regex_replace_all:NVN \c__tblr_insert_braces_regex \c__tblr_insert_braces_tl #1
}
\cs_new_protected:Npn \__tblr_remove_braces:N #1
{
  \regex_replace_all:NVN \c__tblr_remove_braces_regex \c__tblr_remove_braces_tl #1
  \regex_replace_all:NVN \c__tblr_remove_braces_regex \c__tblr_remove_braces_tl #1
}

%% Split table content to cells and store them
%% #1: table content

\seq_new:N \l_tblr_lines_seq

\cs_new_protected:Npn \__tblr_split_table:n #1
{
  \int_zero:N \c@rowcount
  \int_zero:N \c@colcount
  \__tblr_split_table_to_lines:nN { #1 } \l_tblr_lines_seq
  \__tblr_split_lines_to_cells:N \l_tblr_lines_seq
}

%% Split table content to a sequence of lines
%% #1: table content, #2: resulting sequence of lines
\cs_new_protected:Npn \__tblr_split_table_to_lines:nN #1 #2
{
  \tl_set:Nn \l_tmpa_tl { #1 }
  \__tblr_insert_braces:N \l_tmpa_tl
  \seq_set_split:NnV \l_tmpa_seq { \ } \l_tmpa_tl
  \seq_clear:N #2
  \seq_map_inline:Nn \l_tmpa_seq
  {
    \tl_if_head_eq_meaning:nNTF {##1} *
    {
      \tl_set:Nn \l__tblr_b_tl { \SetRow{nobreak} }
      \tl_set:Nx \l__tblr_c_tl { \tl_tail:n {##1} }
    }
  }
}

```

```

\tl_trim_spaces:N \l__tblr_c_tl %% Ignore spaces between * and [dimen]
\tl_log:N \l__tblr_c_tl
\tl_if_head_eq_meaning:VNT \l__tblr_c_tl [
  {
    \tl_put_right:Nn \l__tblr_b_tl { \RowBefore@AddBelowSep }
  }
\tl_put_right:NV \l__tblr_b_tl \l__tblr_c_tl
\seq_put_right:NV #2 \l__tblr_b_tl
}
{
\tl_if_head_eq_meaning:nNTF { ##1 } [
  { \seq_put_right:Nn #2 { \RowBefore@AddBelowSep ##1 } }
  { \seq_put_right:Nn #2 { ##1 } }
]
}
}
\int_set:Nn \c@rowcount { \seq_count:N #2 }
}

%% Treat \[dimen] command
\NewTableCommand \RowBefore@AddBelowSep [1] []
{
  \IfValueT { #1 }
  {
    \__tblr_data_gadd_dimen_value:nene { row }
    { \int_eval:n {\c@rownum - 1} } { belowsep } {#1}
  }
}

%% Split table lines to cells and store them
%% #1: sequence of lines
\cs_new_protected:Npn \__tblr_split_lines_to_cells:N #1
{
  \seq_map_indexed_function:NN #1 \__tblr_split_one_line:nn
  \LogTblrTracing { text }
}

%% Split one line into cells and store them
%% #1: row number, #2 the line text
\cs_new_protected:Npn \__tblr_split_one_line:nn #1 #2
{
  \seq_set_split:Nnn \l_tmpa_seq { & } { #2 }
  \int_set:Nn \c@rownum {#1}
  \int_zero:N \c@colnum
  \seq_map_inline:Nn \l_tmpa_seq
  {
    \tl_set:Nn \l_tmpa_tl { ##1 }
    \__tblr_remove_braces:N \l_tmpa_tl
    \int_incr:N \c@colnum
    \__tblr_extract_table_commands:N \l_tmpa_tl
    \__tblr_spec_gput:neV { text } { [#1][\int_use:N \c@colnum] } \l_tmpa_tl
    \__tblr_add_multicolumn_empty_cell:
  }
}

%% Decrease row count by 1 if the last row has only one empty cell text
%% We need to do it here since the > or < column type may add text to cells
\bool_lazy_and:nnTF
{ \int_compare_p:nNn {\c@colnum} = {1} }
{ \tl_if_empty_p:N \l_tmpa_tl }

```

```

    { \int_decr:N \c@rowcount }
    {
      \__tblr_prop_gput:nxx
      {row} { [#1] / cell-number } { \int_use:N \c@colnum }
      \int_compare:nT { \c@colnum > \c@colcount }
      {
        \int_set_eq:NN \c@colcount \c@colnum
      }
    }
  }
}

%% Add empty cells after the \multicolumn span cell
\cs_new_protected:Npn \__tblr_add_multicolumn_empty_cell:
{
  \int_step_inline:nn { \l__multicolumn_cell_number_int - 1 }
  {
    \int_incr:N \c@colnum
    \__tblr_spec_gput:nen { text }
    { [\int_use:N \c@rownum][\int_use:N \c@colnum] } { }
  }
}

%%% -----
%%% \section{Extract Table Commands from Cell Text}
%%% -----

%% Extract table commands defined with \NewTableCommand from cell text

\clist_gset:Nn \g__tblr_table_commands_unbrace_next_clist {\multirow, \multicolumn}
\bool_new:N \l__tblr_table_command_unbrace_next_bool
\int_new:N \l__multicolumn_cell_number_int
\tl_new:N \l__tblr_saved_table_commands_before_cell_text_tl
\tl_new:N \l__tblr_saved_cell_text_after_table_commands_tl

\cs_new_protected:Npn \__tblr_extract_table_commands:N #1
{
  \tl_clear:N \l__tblr_saved_table_commands_before_cell_text_tl
  \tl_clear:N \l__tblr_saved_cell_text_after_table_commands_tl
  \int_set:Nn \l__multicolumn_cell_number_int {1}
  \exp_last_unbraced:NV \__tblr_extract_table_commands_next:w #1 \q_stop
  \tl_if_empty:NF \l__tblr_saved_table_commands_before_cell_text_tl
  {
    \__tblr_prop_gput:nxV { command }
    {[\int_use:N \c@rownum][\int_use:N \c@colnum]}
    \l__tblr_saved_table_commands_before_cell_text_tl
  }
  \tl_set_eq:NN #1 \l__tblr_saved_cell_text_after_table_commands_tl
}

%% #1 maybe a single token or multiple tokens given in braces
\cs_new_protected:Npn \__tblr_extract_table_commands_next:w #1
{
  \clist_if_in:NnTF \g__tblr_table_commands_clist { #1 }
  {
    \clist_if_in:NnTF \g__tblr_table_commands_unbrace_next_clist { #1 }
    { \bool_set_true:N \l__tblr_table_command_unbrace_next_bool }
  }
}

```

```

        { \bool_set_false:N \l__tblr_table_command_unbrace_next_bool }
\token_if_eq_meaning:NNTF #1 \multicolumn
    { \__tblr_extract_multicolumn_command:Nn #1 }
    { \__tblr_extract_one_table_command:N #1 }
}
{
\l_if_single_token:nTF {#1}
    {
        \token_if_eq_meaning:NNTF #1 \q_stop
        { \__tblr_save_real_cell_text:w #1 }
    }
    { \__tblr_save_real_cell_text:w {#1} }
}
}

\cs_new_protected:Npn \__tblr_extract_multicolumn_command:Nn #1 #2
{
    \int_set:Nn \l__multicolumn_cell_number_int {#2}
    \__tblr_extract_one_table_command:N #1 {#2}
}

\cs_new_protected:Npn \__tblr_extract_one_table_command:N #1
{
    \int_set:Nn \l__tblr_a_int
    { \cs:w g__tblr_table_cmd_ \cs_to_str:N #1 _arg_num_tl \cs_end: }
    \tl_put_right:Nn \l__tblr_saved_table_commands_before_cell_text_tl {#1}
    \int_compare:nNnTF {\l__tblr_a_int} < {0}
    {
        \int_set:Nn \l__tblr_a_int { \int_abs:n {\l__tblr_a_int} - 1 }
        \peek_charcode:NNTF [
            { \__tblr_extract_table_command_arg_o:w }
            { \__tblr_extract_table_command_arg_next: }
        ]
    }
    { \__tblr_extract_table_command_arg_next: }
}

\cs_new_protected:Npn \__tblr_extract_table_command_arg_o:w [#1]
{
    \tl_put_right:Nn \l__tblr_saved_table_commands_before_cell_text_tl { [#1] }
    \__tblr_extract_table_command_arg_next:
}

\cs_new_protected:Npn \__tblr_extract_table_command_arg_m:n #1
{
    \tl_put_right:Nn \l__tblr_saved_table_commands_before_cell_text_tl { {#1} }
    \__tblr_extract_table_command_arg_next:
}

\cs_new_protected:Npn \__tblr_extract_table_command_arg_next:
{
    \int_compare:nNnTF {\l__tblr_a_int} > {0}
    {
        \int_decr:N \l__tblr_a_int
        \__tblr_extract_table_command_arg_m:n
    }
    {
        \bool_if:NNTF \l__tblr_table_command_unbrace_next_bool

```

```

        { \tblr_last_unbraced:Nn \tblr_extract_table_commands_next:w }
        { \tblr_extract_table_commands_next:w }
    }
}

\cs_new_protected:Npn \tblr_last_unbraced:Nn #1 #2 { #1 #2 }

%% The outermost set of braces of cell text #1 will be removed
\cs_new_protected:Npn \tblr_save_real_cell_text:w #1 \q_stop
{
  \tbl_set:Nn \l__tblr_saved_cell_text_after_table_commands_tl {#1}
}

%%% -----
%% \section{Initialize Table Inner Specifications}
%%% -----

\prop_gset_from_keyval:Nn \g__tblr_initial_table_prop
{
  stretch = 1,
  rulesep = 2pt,
}

\prop_gset_from_keyval:Nn \g__tblr_initial_rows_prop
{
  abovesep = 2pt,
  belowsep = 2pt,
  @row-height = 0pt,
  @row-head = 0pt,
  @row-foot = 0pt,
  @row-upper = 0pt,
  @row-lower = 0pt,
}

\prop_gset_from_keyval:Nn \g__tblr_initial_columns_prop
{
  leftsep = 6pt,
  rightsep = 6pt,
  width = -1pt, % column width unset
  coefficient = 0, % column coefficient unset
  @col-width = 0pt,
}

\prop_gset_from_keyval:Nn \g__tblr_initial_cells_prop
{
  halign = l,
  valign = t,
  width = -1pt, % cell width unset
  rowspan = 1,
  colspan = 1,
  omit = 0,
}

\prop_gset_from_keyval:Nn \g__tblr_initial_hlines_prop
{
  @hline-count = 0,
}

```

```

}

\prop_gset_from_keyval:Nn \g__tblr_initial_vlines_prop
{
  @vline-count = 0,
}

\cs_new_protected:Npn \__tblr_init_table_inner_spec:
{
  \prop_map_inline:Nn \g__tblr_initial_table_prop
  {
    \__tblr_prop_gput:nxn { inner } { ##1 } {##2}
  }
  \int_step_variable:nNn { \c@rowcount } \l__tblr_i_tl
  {
    \prop_map_inline:Nn \g__tblr_initial_rows_prop
    {
      \__tblr_data_gput:nVnn { row } \l__tblr_i_tl {##1} {##2}
    }
    \prop_map_inline:Nn \g__tblr_initial_hlines_prop
    {
      \__tblr_spec_gput:nen { hline } { [\l__tblr_i_tl] / ##1 } {##2}
    }
    \int_step_variable:nNn { \c@colcount } \l__tblr_j_tl
    {
      \prop_map_inline:Nn \g__tblr_initial_cells_prop
      {
        \__tblr_data_gput:neeen { cell }
          { \l__tblr_i_tl } { \l__tblr_j_tl } {##1} {##2}
      }
    }
  }
}

\prop_map_inline:Nn \g__tblr_initial_hlines_prop
{
  \__tblr_spec_gput:nen { hline }
  { [\int_eval:n { \c@rowcount + 1}] / ##1 } {##2}
}

\int_step_variable:nNn { \c@colcount } \l__tblr_j_tl
{
  \prop_map_inline:Nn \g__tblr_initial_columns_prop
  {
    \__tblr_data_gput:nenn { column } { \l__tblr_j_tl } {##1} {##2}
  }
  \prop_map_inline:Nn \g__tblr_initial_vlines_prop
  {
    \__tblr_spec_gput:nen { vline } { [\l__tblr_j_tl] / ##1 } {##2}
  }
}

\prop_map_inline:Nn \g__tblr_initial_vlines_prop
{
  \__tblr_spec_gput:nen { vline }
  { [\int_eval:n { \c@colcount + 1}] / ##1 } {##2}
}

\keys_set:nv { tblr } { l__tblr_default_ \l__tblr_env_name_tl _inner_tl }
}

%%% -----

```

```

%%> \section{Parse Table Inner Specifications}
%%% -----

\clist_new:N \g__tblr_table_known_keys_clist
\clist_gset:Nn \g__tblr_table_known_keys_clist
{
  colspec, rowspec, width, hspan, vspan, stretch,
  column, row, cell, vline, hline, columns, rows, cells, vlines, hlines,
  leftsep, rightsep, colsep, abovesep, belowsep, rowsep, rulesep,
  rowhead, rowfoot,
}

\keys_define:nn { tblr }
{
  colspec .code:n = \__tblr_parse_colrow_spec:nn { column } {#1},
  rowspec .code:n = \__tblr_parse_colrow_spec:nn { row } {#1},
  width .code:n = \__tblr_keys_gput:nx { width } { \dim_eval:n {#1} },
  hspan .code:n = \__tblr_keys_gput:nn { hspan } {#1},
  vspan .code:n = \__tblr_keys_gput:nn { vspan } {#1},
  stretch .code:n = \__tblr_keys_gput:nn { stretch } {#1},
  columns .code:n = \__tblr_set_every_column_aux:n {#1},
  rows .code:n = \__tblr_set_every_row_aux:n {#1},
  cells .code:n = \__tblr_set_every_cell_aux:n {#1},
  hlines .code:n = \__tblr_set_every_hline_aux:n {#1},
  vlines .code:n = \__tblr_set_every_vline_aux:n {#1},
  leftsep .code:n = \tblr_set_every_column:nn { } { leftsep = #1 },
  rightsep .code:n = \tblr_set_every_column:nn { } { rightsep = #1 },
  colsep .meta:n = { leftsep = #1, rightsep = #1 },
  abovesep .code:n = \tblr_set_every_row:nn { } { abovesep = #1 },
  belowsep .code:n = \tblr_set_every_row:nn { } { belowsep = #1 },
  rowsep .meta:n = { abovesep = #1, belowsep = #1 },
  rulesep .code:n = \__tblr_keys_gput:nn { rulesep } {#1},
  rowhead .code:n = \__tblr_keys_gput:nn { rowhead } {#1},
  rowfoot .code:n = \__tblr_keys_gput:nn { rowfoot } {#1},
  unknown .code:n = \__tblr_table_special_key:Vn \l_keys_key_str {#1},
}

\regex_const:Nn \c__tblr_split_key_name_regex { ^ ( [a-z] + ) ( . * ) }

\cs_new_protected:Npn \__tblr_table_special_key:nn #1 #2
{
  \regex_extract_once:NnNT \c__tblr_split_key_name_regex {#1} \l_tmpa_seq
  {
    \tl_set:Nx \l__tblr_a_tl { \seq_item:Nn \l_tmpa_seq {2} }
    \tl_set_rescan:Nnx \l__tblr_b_tl {} { \seq_item:Nn \l_tmpa_seq {3} }
    \cs:w __tblr_set_ \l__tblr_a_tl _aux:Vn \cs_end: \l__tblr_b_tl {#2}
  }
}

\cs_generate_variant:Nn \__tblr_table_special_key:nn { Vn }

%% If the first key name is known, treat #1 is the table spec;
%% otherwise, treat #1 as colspec.

\regex_const:Nn \c__tblr_first_key_name_regex { ^ \s * ( [A-Za-z\-\] + ) }

\cs_new_protected:Npn \__tblr_parse_table_spec:n #1

```

```

{
  \regex_extract_once:NnNTF \c__tblr_first_key_name_regex {#1} \l_tmpa_seq
  {
    \clist_if_in:NxTF \g__tblr_table_known_keys_clist
      { \seq_item:Nn \l_tmpa_seq {2} }
      { \keys_set:nn { tblr } {#1} }
      { \__tblr_parse_colrow_spec:nn { column } {#1} }
    }
  { \__tblr_parse_colrow_spec:nn { column } {#1} }
}

\cs_new_protected:Npn \__tblr_keys_gput:nn #1 #2
{
  \__tblr_prop_gput:nnn { inner } {#1} {#2}
}

\cs_generate_variant:Nn \__tblr_keys_gput:nn { nx }

%%% -----
%%% \section{Initialize and Parse Table Outer Specifications}
%%% -----

%% #1: theme names; #2: template and style commands
\NewDocumentCommand \NewTblrTheme { m +m }
{
  \tl_set:cn { g__tblr_theme_ #1 _code_tl } {#2}
  \ignorespaces
}

\cs_new_protected:Npn \__tblr_use_theme:n #1
{
  \ignorespaces
  \tl_use:c { g__tblr_theme_ #1 _code_tl }
}

\cs_new_protected:Npn \__tblr_init_table_outer_spec:
{
  \keys_set:nv { tblr-outer } { l__tblr_default_ \l__tblr_env_name_tl _outer_tl }
}

\cs_new_protected:Npn \__tblr_parse_table_option:n #1
{
  \keys_set:nn { tblr-outer } {#1}
}

\keys_define:nn { tblr-outer }
{
  long .code:n = \__tblr_outer_gput_spec:nn { long } {true},
  halign .code:n = \__tblr_outer_gput_spec:nn { halign } {#1},
  valign .code:n = \__tblr_outer_gput_spec:nn { valign } {#1},
  l .meta:n = { halign = l },
  c .meta:n = { halign = c },
  r .meta:n = { halign = r },
  t .meta:n = { valign = t },
  m .meta:n = { valign = m },
  b .meta:n = { valign = b },
  headsep .code:n = \__tblr_outer_gput_spec:nn { headsep } {#1},
}

```

```

    footsep .code:n = \__tblr_outer_gput_spec:nn { footsep } {#1},
    presep  .code:n = \__tblr_outer_gput_spec:nn { presep  } {#1},
    postsep .code:n = \__tblr_outer_gput_spec:nn { postsep } {#1},
    theme   .code:n = \__tblr_use_theme:n {#1},
    caption .code:n = \__tblr_outer_gput_spec:nn { caption } {#1},
    entry   .code:n = \__tblr_outer_gput_spec:nn { entry   } {#1},
    label   .code:n = \__tblr_outer_gput_spec:nn { label   } {#1},
    unknown .code:n = \__tblr_table_option_key:Vn \l_keys_key_str {#1},
  }

\cs_new_protected:Npn \__tblr_outer_gput_spec:nn #1 #2
{
  \__tblr_spec_gput:nen { outer } {#1} {#2}
}

\regex_const:Nn \c__tblr_option_key_name_regex { ^ [A-Za-z\-\_ ] + $ }

\msg_new:nnn { tabularray } { unknown-outer-key }
{ Unknown ~ outer ~ key ~ name ~ #1! }

\cs_new_protected:Npn \__tblr_table_option_key:nn #1 #2
{
  \regex_match:NnTF \c__tblr_option_key_name_regex {#1}
  { \msg_error:nnn { tabularray } { unknown-outer-key } {#1} }
  {
    \regex_extract_once:NnNT \c__tblr_split_key_name_regex {#1} \l_tmpa_seq
    {
      \tl_set:Nx \l__tblr_a_tl { \seq_item:Nn \l_tmpa_seq {2} }
      \tl_set_rescan:Nnx \l__tblr_b_tl {} { \seq_item:Nn \l_tmpa_seq {3} }
      \tl_set:Nx \l__tblr_c_tl { \tl_head:N \l__tblr_b_tl }
      \use:c { __tblr_outer_gput_ \l__tblr_a_tl :Vn } \l__tblr_c_tl {#2}
    }
  }
}

\cs_generate_variant:Nn \__tblr_table_option_key:nn { Vn }

\cs_new_protected:Npn \__tblr_outer_gput_note:nn #1 #2
{
  \__tblr_prop_gput:nnn { note } {#1} {#2}
}

\cs_generate_variant:Nn \__tblr_outer_gput_note:nn { Vn }

\cs_new_protected:Npn \__tblr_outer_gput_remark:nn #1 #2
{
  \__tblr_prop_gput:nnn { remark } {#1} {#2}
}

\cs_generate_variant:Nn \__tblr_outer_gput_remark:nn { Vn }

\cs_new_protected:Npn \__tblr_outer_gput_more:nn #1 #2
{
  \__tblr_prop_gput:nnn { more } {#1} {#2}
}

\cs_generate_variant:Nn \__tblr_outer_gput_more:nn { Vn }

%% -----
%% \section{Typeset and Calculate Sizes}

```

```

%%% -----

%% Calculate the width and height for every cell and border

\cs_new_protected:Npn \__tblr_calc_cell_and_line_sizes:
{
  \__tblr_make_strut_box:
  \__tblr_calculate_line_sizes:
  \__tblr_calculate_cell_sizes:
  \LogTblrTracing { cell, row, column, hline, vline }
  \__tblr_compute_extendable_column_width:
  \__tblr_adjust_sizes_for_span_cells:
}

%% make strut box from stretch option of the table

\box_new:N \l__tblr_strut_ht_box
\box_new:N \l__tblr_strut_dp_box

\cs_new_protected:Npn \__tblr_make_strut_box:
{
  \tl_set:Nx \l__tblr_s_tl { \__tblr_prop_item:ne { inner } { stretch } }
  \hbox_set:Nn \l__tblr_strut_ht_box
  { \vrule height \l__tblr_s_tl \box_ht:N \strutbox width ~ Opt }
  \hbox_set:Nn \l__tblr_strut_dp_box
  { \vrule depth \l__tblr_s_tl \box_dp:N \strutbox width ~ Opt }
}

%% Calculate the thickness for every hline and vline
\cs_new_protected:Npn \__tblr_calculate_line_sizes:
{
  %% We need these two counters in executing hline and vline commands
  \int_zero:N \c@rownum
  \int_zero:N \c@colnum
  \int_step_inline:nn { \c@rowcount + 1 }
  {
    \int_incr:N \c@rownum
    \int_zero:N \c@colnum
    \int_step_inline:nn { \c@colcount + 1 }
    {
      \int_incr:N \c@colnum
      \int_compare:nNnT { ##1 } < { \c@rowcount + 1 }
      {
        \__tblr_measure_and_update_vline_size:nn { ##1 } { ####1 }
      }
      \int_compare:nNnT { ####1 } < { \c@colcount + 1 }
      {
        \__tblr_measure_and_update_hline_size:nn { ##1 } { ####1 }
      }
    }
  }
}

%% Measure and update thickness of the vline
%% #1: row number, #2 column number
\cs_new_protected:Npn \__tblr_measure_and_update_vline_size:nn #1 #2

```

```

{
  \dim_zero:N \l__tblr_w_dim
  \tl_set:Nx \l__tblr_n_tl
  { \__tblr_spec_item:ne { vline } { [#2] / @vline-count } }
  \int_compare:nNnT { \l__tblr_n_tl } > {0}
  {
    \tl_set:Nx \l__tblr_s_tl
    { \__tblr_prop_item:ne { inner } { rulesep } }
    \int_step_inline:nn { \l__tblr_n_tl }
    {
      \vbox_set_to_ht:Nnn \l__tblr_b_box {1pt}
      {
        \__tblr_get_vline_segment_child:nnnnn
          {#1} {#2} {##1} {1pt} {1pt}
      }
      \tl_set:Nx \l__tblr_w_tl { \dim_eval:n { \box_wd:N \l__tblr_b_box } }
      \__tblr_spec_gput_if_larger:nee { vline }
        { [#2](##1) / @vline-width } { \l__tblr_w_tl }
      \dim_add:Nn \l__tblr_w_dim { \l__tblr_w_tl }
      \dim_add:Nn \l__tblr_w_dim { \l__tblr_s_tl }
    }
    \dim_add:Nn \l__tblr_w_dim { - \l__tblr_s_tl }
  }
  \__tblr_spec_gput_if_larger:nee { vline }
    { [#2]/ @vline-width } { \dim_use:N \l__tblr_w_dim }
}

%% Get text of a vline segment
%% #1: row number, #2: column number; #3: index number; #4: height; #5: depth
%% We put all code inside a group to avoid conflicts of local variables
\cs_new_protected:Npn \__tblr_get_vline_segment_child:nnnnn #1 #2 #3 #4 #5
{
  \group_begin:
  \tl_set:Nx \l__tblr_w_tl
  { \__tblr_spec_item:ne { vline } { [#1][#2](#3) / wd } }
  \tl_if_empty:NF \l__tblr_w_tl { \dim_set:Nn \rulewidth { \l__tblr_w_tl } }
  \tl_set:Nx \l__tblr_d_tl
  { \__tblr_spec_item:ne { vline } { [#1][#2](#3) / @dash } }
  \tl_set:Nx \l__tblr_a_tl { \tl_head:N \l__tblr_d_tl }
  \tl_set:Nx \l__tblr_b_tl { \tl_tail:N \l__tblr_d_tl }
  \exp_args:NV \tl_if_eq:NNTF \l__tblr_a_tl \@tblr@dash
  {
    \__tblr_get_vline_dash_style:N \l__tblr_b_tl
    \xleaders \l__tblr_b_tl \vfil
  }
  {
    \hbox_set:Nn \l__tblr_d_box { \l__tblr_b_tl }
    \box_set_ht:Nn \l__tblr_d_box {#4}
    \box_set_dp:Nn \l__tblr_d_box {#5}
    \box_use:N \l__tblr_d_box
  }
  \group_end:
}
\cs_generate_variant:Nn \__tblr_get_vline_segment_child:nnnnn { nnnxx }

%% Measure and update thickness of the hline
%% #1: row number, #2 column number
\cs_new_protected:Npn \__tblr_measure_and_update_hline_size:nn #1 #2

```

```

{
  \dim_zero:N \l__tblr_h_dim
  \tl_set:Nx \l__tblr_n_tl
  { \__tblr_spec_item:ne { hline } { [#1] / @hline-count } }
  \int_compare:nNnT { \l__tblr_n_tl } > {0}
  {
    \tl_set:Nx \l__tblr_s_tl
    { \__tblr_prop_item:ne { inner } { rulesep } }
    \int_step_inline:nn { \l__tblr_n_tl }
    {
      \hbox_set_to_wd:Nnn \l__tblr_b_box {1pt}
      { \__tblr_get_hline_segment_child:nnn {#1} {#2} {##1} }
      \tl_set:Nx \l__tblr_h_tl
      {
        \dim_eval:n
        { \box_ht:N \l__tblr_b_box + \box_dp:N \l__tblr_b_box }
      }
      \__tblr_spec_gput_if_larger:nee { hline }
      { [#1](##1) / @hline-height } { \l__tblr_h_tl }
      \dim_add:Nn \l__tblr_h_dim { \l__tblr_h_tl }
      \dim_add:Nn \l__tblr_h_dim { \l__tblr_s_tl }
    }
    \dim_add:Nn \l__tblr_h_dim { - \l__tblr_s_tl }
  }
  \__tblr_spec_gput_if_larger:nee { hline }
  { [#1] / @hline-height } { \dim_use:N \l__tblr_h_dim }
}

%% Get text of a hline segment
%% #1: row number, #2: column number; #3: index number
\cs_new_protected:Npn \__tblr_get_hline_segment_child:nnn #1 #2 #3
{
  \group_begin:
  \tl_set:Nx \l__tblr_w_tl
  { \__tblr_spec_item:ne { hline } { [#1][#2](#3) / wd } }
  \tl_if_empty:NF \l__tblr_w_tl { \dim_set:Nn \rulewidth { \l__tblr_w_tl } }
  \tl_set:Nx \l__tblr_d_tl
  { \__tblr_spec_item:ne { hline } { [#1][#2](#3) / @dash } }
  \tl_set:Nx \l__tblr_a_tl { \tl_head:N \l__tblr_d_tl }
  \tl_set:Nx \l__tblr_b_tl { \tl_tail:N \l__tblr_d_tl }
  \exp_args:NV \tl_if_eq:NNTF \l__tblr_a_tl \@tblr@dash
  {
    \__tblr_get_hline_dash_style:N \l__tblr_b_tl
    \xleaders \l__tblr_b_tl \hfil
  }
  { \l__tblr_b_tl \hfil }
  \group_end:
}

%% current cell alignments
\tl_new:N \g__tblr_cell_halign_tl
\tl_new:N \g__tblr_cell_valign_tl
\tl_new:N \g__tblr_cell_middle_tl

\tl_const:Nn \c__tblr_valign_h_tl { h }
\tl_const:Nn \c__tblr_valign_m_tl { m }
\tl_const:Nn \c__tblr_valign_f_tl { f }

```

```

\tl_const:Nn \c__tblr_valign_t_tl { t }
\tl_const:Nn \c__tblr_valign_b_tl { b }

\tl_const:Nn \c__tblr_middle_t_tl { t }
\tl_const:Nn \c__tblr_middle_m_tl { m }
\tl_const:Nn \c__tblr_middle_b_tl { b }

%% #1: row number; #2: column number
\cs_new_protected:Npn \__tblr_get_cell_alignments:nn #1 #2
{
  \group_begin:
  \tl_gset:Nx \g__tblr_cell_halign_tl
    { \__tblr_data_item:neen { cell } {#1} {#2} { halign } }
  \tl_set:Nx \l__tblr_v_tl
    { \__tblr_data_item:neen { cell } {#1} {#2} { valign } }
  \tl_case:NnF \l__tblr_v_tl
    {
      \c__tblr_valign_t_tl
      {
        \tl_gset:Nn \g__tblr_cell_valign_tl {m}
        \tl_gset:Nn \g__tblr_cell_middle_tl {t}
      }
      \c__tblr_valign_m_tl
      {
        \tl_gset:Nn \g__tblr_cell_valign_tl {m}
        \tl_gset:Nn \g__tblr_cell_middle_tl {m}
      }
      \c__tblr_valign_b_tl
      {
        \tl_gset:Nn \g__tblr_cell_valign_tl {m}
        \tl_gset:Nn \g__tblr_cell_middle_tl {b}
      }
    }
  {
    \tl_gset_eq:NN \g__tblr_cell_valign_tl \l__tblr_v_tl
    \tl_gclear:N \g__tblr_cell_middle_tl
  }
  \group_end:
}

%% current cell dimensions
\dim_new:N \g__tblr_cell_wd_dim
\dim_new:N \g__tblr_cell_ht_dim
\dim_new:N \g__tblr_cell_head_dim
\dim_new:N \g__tblr_cell_foot_dim

%% Calculate the width and height for every cell
\cs_new_protected:Npn \__tblr_calculate_cell_sizes:
{
  %% You can use these two counters in cell text
  \int_zero:N \c@rownum
  \int_zero:N \c@colnum
  \int_step_inline:nn { \c@rowcount }
  {
    \int_incr:N \c@rownum
    \int_zero:N \c@colnum
    \__tblr_update_rowsep_registers:
  }
}

```

```

\tl_set:Nx \l__tblr_h_tl
  { \__tblr_data_item:nen { row } { \int_use:N \c@rownum } { height } }
%% We didn't initialize row heights with -1pt
\dim_compare:nNnF { \l__tblr_h_tl } = { Opt }
  {
    \__tblr_data_gput:nenV { row } { \int_use:N \c@rownum }
      { @row-height } \l__tblr_h_tl
  }
\int_step_inline:nn { \c@colcount }
  {
    \int_incr:N \c@colnum
    \__tblr_update_colsep_registers:
    \__tblr_measure_cell_update_sizes:nnNNNN
      { \int_use:N \c@rownum }
      { \int_use:N \c@colnum }
      \g__tblr_cell_wd_dim
      \g__tblr_cell_ht_dim
      \g__tblr_cell_head_dim
      \g__tblr_cell_foot_dim
  }
}
\int_step_inline:nn { \c@colcount }
  {
    \tl_set:Nx \l__tblr_w_tl
      { \__tblr_data_item:nen { column } {##1} { width } }
    \dim_compare:nNnF { \l__tblr_w_tl } < { Opt }
      {
        \__tblr_data_gput:nenV { column } {##1} { @col-width } \l__tblr_w_tl
      }
  }
}

\cs_new_protected:Npn \__tblr_update_rowsep_registers:
  {
    \dim_set:Nn \abovesep
      { \__tblr_data_item:nen { row } { \int_use:N \c@rownum } { abovesep } }
    \dim_set:Nn \belowsep
      { \__tblr_data_item:nen { row } { \int_use:N \c@rownum } { belowsep } }
  }

\cs_new_protected:Npn \__tblr_update_colsep_registers:
  {
    \dim_set:Nn \leftsep
      { \__tblr_data_item:nen { column } { \int_use:N \c@colnum } { leftsep } }
    \dim_set:Nn \rightsep
      { \__tblr_data_item:nen { column } { \int_use:N \c@colnum } { rightsep } }
  }

%% Measure and update natural dimensions of the row/column/cell
%% #1: row number; #2 column number; #3: width dimension;
%% #4: total height dimension; #5: head dimension; #6: foot dimension
\cs_new_protected:Npn \__tblr_measure_cell_update_sizes:nnNNNN #1 #2 #3 #4 #5 #6
  {
    \__tblr_get_cell_alignments:nn {#1} {#2}
    \hbox_set:Nn \l_tmpa_box { \__tblr_get_cell_text:nn {#1} {#2} }
    \__tblr_update_cell_size:nnNNNN {#1} {#2} #3 #4 #5 #6
    \__tblr_update_row_size:nnNNN {#1} {#2} #4 #5 #6
  }

```

```

    \_tblr_update_col_size:nN {#2} #3
  }

%% #1: row number, #2: column number
\cs_new_protected:Npn \_tblr_get_cell_text:nn #1 #2
{
  \int_compare:nNnTF { \_tblr_data_item:neen { cell } {#1} {#2} { omit } } > {0}
  {
    \dim_gzero:N \g__tblr_cell_wd_dim
    \dim_gzero:N \g__tblr_cell_ht_dim
    \dim_gzero:N \g__tblr_cell_head_dim
    \dim_gzero:N \g__tblr_cell_foot_dim
  }
  { \_tblr_get_cell_text_real:nn { #1 } { #2 } }
}

%% Get cell text, #1: row number, #2: column number
%% If the width of the cell is not set, split it with \ and compute the width
%% Therefore we always get a vbox for any cell
\cs_new_protected:Npn \_tblr_get_cell_text_real:nn #1 #2
{
  \group_begin:
  \tl_set:Nx \l__tblr_c_tl { \_tblr_spec_item:ne { text } {[#1][#2]} }
  \tl_set:Nx \l__tblr_f_tl { \_tblr_data_item:neen { cell } {#1} {#2} { font } }
  \tl_set:Nx \l__tblr_w_tl
  { \_tblr_data_item:neen { cell } {#1} {#2} { width } }
  \dim_compare:nNnT { \l__tblr_w_tl } < { Opt } % cell width unset
  {
    \int_compare:nNnT
    { \_tblr_data_item:neen { cell } {#1} {#2} { colspan } } < {2}
    {
      \tl_set:Nx \l__tblr_w_tl
      { \_tblr_data_item:neen { column } {#2} { width } }
    }
  }
  \dim_compare:nNnT { \l__tblr_w_tl } < { Opt } % column width unset
  {
    \bool_if:NTF \l__tblr_math_mode_bool
    {
      \hbox_set:Nn \l_tmpa_box { $\l__tblr_c_tl$ }
      \tl_set:Nx \l__tblr_w_tl { \box_wd:N \l_tmpa_box }
    }
    {
      \tl_set_eq:NN \l_tmpb_tl \l__tblr_c_tl
      \_tblr_insert_braces:N \l_tmpb_tl
      \seq_set_split:NnV \l_tmpa_seq { \ } \l_tmpb_tl
      \tl_set:Nn \l__tblr_w_tl { Opt }
      \seq_map_variable:NNn \l_tmpa_seq \l_tmpa_tl
      {
        \_tblr_remove_braces:N \l_tmpa_tl
        \hbox_set:Nn \l_tmpa_box { \l__tblr_f_tl \l_tmpa_tl }
        \tl_set:Nx \l__tblr_w_tl
        { \dim_max:nn { \l__tblr_w_tl } { \box_wd:N \l_tmpa_box } }
      }
    }
  }
  \tl_put_left:NV \l__tblr_c_tl \l__tblr_f_tl
  \_tblr_get_vcell_and_sizes:NN \l__tblr_c_tl \l__tblr_w_tl
}

```

```

    \group_end:
  }

%% #1: cell text; #2: box width
\cs_new_protected:Npn \__tblr_get_vcell_and_sizes:NN #1 #2
{
  \group_begin:
  \vbox_set_top:Nn \l_tmpa_box { \__tblr_make_vcell_text:nN #1 #2 }
  \vbox_set:Nn \l_tmpb_box { \__tblr_make_vcell_text:nN #1 #2 }
  \dim_gset:Nn \g__tblr_cell_wd_dim { \box_wd:N \l_tmpb_box }
  \dim_gset:Nn \g__tblr_cell_ht_dim
    { \box_ht:N \l_tmpb_box + \box_dp:N \l_tmpb_box }
  \dim_gset:Nn \g__tblr_cell_head_dim { \box_ht:N \l_tmpa_box }
  \dim_gset:Nn \g__tblr_cell_foot_dim { \box_dp:N \l_tmpb_box }
  \tl_case:Nn \g__tblr_cell_valign_tl
  {
    \c__tblr_valign_h_tl
    { \box_use:N \l_tmpa_box }
    \c__tblr_valign_m_tl
    {
      \tl_case:Nn \g__tblr_cell_middle_tl
      {
        \c__tblr_middle_t_tl
        { \box_use:N \l_tmpa_box }
        \c__tblr_middle_m_tl
        {
          \tl_set:Nx \l__tblr_b_tl
          {
            \dim_eval:n
            {
              ( \g__tblr_cell_ht_dim - \g__tblr_cell_head_dim
                - \g__tblr_cell_foot_dim ) / 2
            }
          }
          \box_set_ht:Nn \l_tmpb_box
            { \g__tblr_cell_head_dim + \l__tblr_b_tl }
          \box_set_dp:Nn \l_tmpb_box
            { \g__tblr_cell_foot_dim + \l__tblr_b_tl }
          \box_use:N \l_tmpb_box
        }
        \c__tblr_middle_b_tl
        { \box_use:N \l_tmpb_box }
      }
    }
    \c__tblr_valign_f_tl
    { \box_use:N \l_tmpa_box }
  }
  \group_end:
}

%% #1: cell text; #2: box width
%% All halign commands are defined at the beginning of the file
\cs_new_protected:Npn \__tblr_make_vcell_text:nN #1 #2
{
  \dim_set:Nn \tex_hsize:D { #2 }
  \@arrayparboxrestore
  \cs:w__tblr_halign_command_ \g__tblr_cell_halign_tl : \cs_end:
  \mode_leave_vertical:
}

```

```

\box_use:N \l__tblr_strut_ht_box
\bool_if:NTF \l__tblr_math_mode_bool { $#1$ } { #1 }
\box_use:N \l__tblr_strut_dp_box
}

%% #1: total height dimension; #2: head dimension; #3: foot dimension;
%% #4: tl for resulting upper size; #5: tl for resulting lower size

\tl_new:N \l__tblr_middle_body_tl

\cs_new_protected:Npn \__tblr_get_middle_cell_upper_lower:NNNNN #1 #2 #3 #4 #5
{
  \tl_case:Nn \g__tblr_cell_middle_tl
  {
    \c__tblr_middle_t_tl
    {
      \tl_set:Nx #4 { \dim_use:N #2 }
      \tl_set:Nx #5 { \dim_eval:n { #1 - #2 } }
    }
    \c__tblr_middle_m_tl
    {
      \tl_set:Nx \l__tblr_middle_body_tl { \dim_eval:n { #1 - #2 - #3 } }
      \tl_set:Nx #4 { \dim_eval:n { #2 + \l__tblr_middle_body_tl / 2 } }
      \tl_set:Nx #5 { \dim_eval:n { #3 + \l__tblr_middle_body_tl / 2 } }
    }
    \c__tblr_middle_b_tl
    {
      \tl_set:Nx #4 { \dim_eval:n { #1 - #3 } }
      \tl_set:Nx #5 { \dim_use:N #3 }
    }
  }
}

%% Update natural dimensions of the cell
%% #1: row number; #2 column number; #3: width dimension;
%% #4: total height dimension; #5: head dimension; #6: foot dimension
\cs_new_protected:Npn \__tblr_update_cell_size:nnNNNN #1 #2 #3 #4 #5 #6
{
  \group_begin:
  \tl_set:Nx \l__tblr_c_tl
  { \__tblr_data_item:neen { cell } {#1} {#2} { colspan } }
  \int_compare:nNnT { \l__tblr_c_tl } > {1}
  {
    \__tblr_data_gput:neene { cell } {#1} {#2} { @cell-width } { \dim_use:N #3 }
    \dim_gzero:N #3 % don't affect column width
  }
  \tl_set:Nx \l__tblr_r_tl
  { \__tblr_data_item:neen { cell } {#1} {#2} { rowspan } }
  \int_compare:nNnT { \l__tblr_r_tl } > {1}
  {
    \tl_case:Nn \g__tblr_cell_valign_tl
    {
      \c__tblr_valign_h_tl
      {
        \tl_set:Nx \l__tblr_u_tl { \dim_use:N #5 }
        \tl_set:Nx \l__tblr_v_tl { \dim_eval:n { #4 - #5 } }
        %% Update the head size of the first span row here
      }
    }
  }
}

```

```

        \_tblr_data_gput_if_larger:nene
        { row } {#1} { @row-head } { \dim_use:N #5 }
    }
\c__tblr_valign_f_tl
{
    \tl_set:Nx \l__tblr_u_tl { \dim_eval:n { #4 - #6 } }
    \tl_set:Nx \l__tblr_v_tl { \dim_use:N #6 }
    %% Update the foot size of the last span row here
    \_tblr_data_gput_if_larger:nene
    { row }
    { \int_eval:n { #1 + \l__tblr_r_tl - 1 } }
    { @row-foot }
    { \dim_use:N #6 }
}
\c__tblr_valign_m_tl
{
    \_tblr_get_middle_cell_upper_lower:NNNNN
    #4 #5 #6 \l__tblr_u_tl \l__tblr_v_tl
}
}
\_tblr_data_gput:neenV { cell } {#1} {#2} { @cell-height } \l__tblr_u_tl
\_tblr_data_gput:neenV { cell } {#1} {#2} { @cell-depth } \l__tblr_v_tl
%% Don't affect row sizes
\dim_gzero:N #4
\dim_gzero:N #5
\dim_gzero:N #6
}
\group_end:
}

%% Update size of the row. #1: row number; #2: column number;
%% #3: total height dimension; #4: head dimension; #5: foot dimension
\cs_new_protected:Npn \_tblr_update_row_size:nnNNN #1 #2 #3 #4 #5
{
    \group_begin:
    %% Note that \l__tblr_h_tl may be empty
    \tl_set:Nx \l__tblr_h_tl
    { \_tblr_data_item:nene { row } {#1} { @row-height } }
    \tl_if_eq:NNTF \g__tblr_cell_valign_tl \c__tblr_valign_m_tl
    {
        \tl_set:Nx \l__tblr_a_tl
        { \_tblr_data_item:nene { row } {#1} { @row-upper } }
        \tl_set:Nx \l__tblr_b_tl
        { \_tblr_data_item:nene { row } {#1} { @row-lower } }
        \_tblr_get_middle_cell_upper_lower:NNNNN
        #3 #4 #5 \l__tblr_u_tl \l__tblr_v_tl
        \dim_compare:nNnT { \l__tblr_u_tl } > { \l__tblr_a_tl }
        {
            \tl_set_eq:NN \l__tblr_a_tl \l__tblr_u_tl
            \_tblr_data_gput:nenV { row } {#1} { @row-upper } \l__tblr_a_tl
        }
        \dim_compare:nNnT { \l__tblr_v_tl } > { \l__tblr_b_tl }
        {
            \tl_set_eq:NN \l__tblr_b_tl \l__tblr_v_tl
            \_tblr_data_gput:nenV { row } {#1} { @row-lower } \l__tblr_b_tl
        }
        \dim_compare:nNnT
        { \l__tblr_a_tl + \l__tblr_b_tl } > { \l__tblr_h_tl + Opt }
    }
}

```

```

    {
      \tblr_data_gput:nene { row } {#1} { @row-height }
      { \dim_eval:n { \l__tblr_a_tl + \l__tblr_b_tl } }
    }
  }
  {
    \tl_set:Nx \l__tblr_e_tl
      { \tblr_data_item:nene { row } {#1} { @row-head } }
    \tl_set:Nx \l__tblr_f_tl
      { \tblr_data_item:nene { row } {#1} { @row-foot } }
    \dim_compare:nNnT {#4} > { \l__tblr_e_tl }
    {
      \tblr_data_gput:nene { row } {#1} { @row-head } { \dim_use:N #4 }
    }
    \dim_compare:nNnT {#5} > { \l__tblr_f_tl }
    {
      \tblr_data_gput:nene { row } {#1} { @row-foot } { \dim_use:N #5 }
    }
    \tl_set:Nx \l__tblr_x_tl { \dim_max:nn {#4} { \l__tblr_e_tl } }
    \tl_set:Nx \l__tblr_y_tl { \dim_max:nn {#5} { \l__tblr_f_tl } }
    \dim_compare:nNnT
      { #3 - #4 - #5 } > { \l__tblr_h_tl - \l__tblr_x_tl - \l__tblr_y_tl }
    {
      \tblr_data_gput:nene { row } {#1} { @row-height }
      {
        \dim_eval:n
          {
            \l__tblr_x_tl
            + \dim_use:N #3 - \dim_use:N #4 - \dim_use:N #5
            + \l__tblr_y_tl
          }
      }
    }
  }
}
\group_end:
}

%% Update size of the column. #1: column number; #2: width dimension

\cs_new_protected:Npn \tblr_update_col_size:nN #1 #2
{
  \tl_set:Nx \l_tmpb_tl
    { \tblr_data_item:nene { column } {#1} { @col-width } }
  \bool_lazy_or:nnT
    { \tl_if_empty_p:N \l_tmpb_tl }
    { \dim_compare_p:nNn { \dim_use:N #2 } > { \l_tmpb_tl } }
    {
      \tblr_data_gput:nene { column } {#1} { @col-width } { \dim_use:N #2 }
    }
}

%%% -----
%% \section{Calculate and Adjust Extendable Columns}
%%% -----

%% Compute column widths when there are some extendable columns

```

```

\dim_new:N \l__column_target_dim
\prop_new:N \l__column_coefficient_prop
\prop_new:N \l__column_natural_width_prop
\prop_new:N \l__column_computed_width_prop

\msg_new:nnn { tabularray } { table-width-too-small }
  { Table ~ width ~ is ~ too ~ small, ~ need ~ #1 ~ more! }

\cs_new_protected:Npn \__tblr_compute_extendable_column_width:
{
  \__tblr_collect_extendable_column_width:
  \dim_compare:nNnTF { \l__column_target_dim } < { Opt }
  {
    \msg_warning:nnx { tabularray } { table-width-too-small }
      { \dim_abs:n { \l__column_target_dim } }
  }
  {
    \prop_if_empty:NF \l__column_coefficient_prop
      { \__tblr_adjust_extendable_column_width: }
  }
}

\cs_new_protected:Npn \__tblr_collect_extendable_column_width:
{
  \tl_set:Nx \l_tmpa_tl { \__tblr_prop_item:nn { inner } { width } }
  \tl_if_empty:NTF \l_tmpa_tl
  { \dim_set_eq:NN \l__column_target_dim \linewidth }
  { \dim_set:Nn \l__column_target_dim { \l_tmpa_tl } }
  \prop_clear:N \l__column_coefficient_prop
  \prop_clear:N \l__column_natural_width_prop
  \prop_clear:N \l__column_computed_width_prop
  \int_step_variable:nNn { \c@colcount } \l__tblr_j_tl
  {
    \tl_set:Nx \l__tblr_a_tl
      { \__tblr_data_item:nen { column } { \l__tblr_j_tl } { width } }
    \tl_set:Nx \l__tblr_b_tl
      { \__tblr_data_item:nen { column } { \l__tblr_j_tl } { coefficient } }
    \tl_set:Nx \l__tblr_c_tl
      { \__tblr_data_item:nen { column } { \l__tblr_j_tl } { @col-width } }
    \dim_compare:nNnTF { \l__tblr_a_tl } < { Opt } % column width unset
    {
      \dim_compare:nNnTF { \l__tblr_b_tl pt } = { Opt }
      { \dim_sub:Nn \l__column_target_dim { \l__tblr_c_tl } }
      {
        \prop_put:Nxx \l__column_coefficient_prop
          { \l__tblr_j_tl } { \l__tblr_b_tl }
        \prop_put:Nxn \l__column_computed_width_prop
          { \l__tblr_j_tl } { Opt }
        \dim_compare:nNnF { \l__tblr_b_tl pt } > { Opt }
        {
          \prop_put:Nxx \l__column_natural_width_prop
            { \l__tblr_j_tl } { \l__tblr_c_tl }
        }
      }
    }
  }
  { \dim_sub:Nn \l__column_target_dim { \l__tblr_a_tl } }
  \tl_set:Nx \l__tblr_a_tl

```

```

        { \__tblr_spec_item:ne { vline } { [\l__tblr_j_tl] / @vline-width } }
\__tblr_data_item:nen { column } { \l__tblr_j_tl } { leftsep } }
\__tblr_data_item:nen { column } { \l__tblr_j_tl } { rightsep } }
\dim_set:Nn \l__column_target_dim
  { \l__column_target_dim - \l__tblr_a_tl - \l__tblr_b_tl - \l__tblr_c_tl }
}
\__tblr_spec_item:ne { vline }
  { [\int_eval:n {\c@colcount + 1}] / @vline-width }
}
\__tblr_data_gput:nne { column } { ##1 } { width } { ##2 }
\__tblr_data_gput:nnnn { column } { ##1 } { @col-width } { Opt }
}
\__tblr_calculate_cell_sizes:
}

%% If all columns have negative coefficients and small natural widths,
%% \l__column_coefficient_prop will be empty after one or more rounds
\cs_new_protected:Npn \__tblr_adjust_extendable_column_width:
{
  \bool_while_do:nn
    { \dim_compare_p:nNn { \l__column_target_dim } > { \hfuzz } }
    {
      \prop_if_empty:NTF \l__column_coefficient_prop
        { \__tblr_adjust_extendable_column_width_negative: }
        { \__tblr_adjust_extendable_column_width_once: }
    }
  \prop_map_inline:Nn \l__column_computed_width_prop
    {
      \__tblr_data_gput:nne { column } { ##1 } { width } { ##2 }
      \__tblr_data_gput:nnnn { column } { ##1 } { @col-width } { Opt }
    }
  \__tblr_calculate_cell_sizes:
}

%% We use dimen register, since the coefficient may be a decimal number
\cs_new_protected:Npn \__tblr_adjust_extendable_column_width_once:
{
  \dim_zero:N \l_tmpa_dim
  \prop_map_inline:Nn \l__column_coefficient_prop
    {
      \dim_add:Nn \l_tmpa_dim { \dim_abs:n { ##2 pt } }
    }
  \tl_set:Nx \l__tblr_w_tl
    { \dim_ratio:nn { \l__column_target_dim } { \l_tmpa_dim } }
  \dim_zero:N \l__column_target_dim
  \prop_map_inline:Nn \l__column_coefficient_prop
    {
      \tl_set:Nx \l__tblr_a_tl
        { \dim_eval:n { \dim_abs:n { ##2 pt } * \l__tblr_w_tl } }
      \dim_compare:nNnTF { ##2 pt } > { Opt }
        {
          \__tblr_add_dimen_value:Nnn
            \l__column_computed_width_prop { ##1 } { \l__tblr_a_tl }
        }
    }
}

```

```

\tl_set:Nx \l__tblr_b_tl
  { \prop_item:Nn \l__column_natural_width_prop { ##1 } }
\tl_set:Nx \l__tblr_c_tl
  { \prop_item:Nn \l__column_computed_width_prop { ##1 } }
\dim_compare:nNnTF { \l__tblr_a_tl + \l__tblr_c_tl } > { \l__tblr_b_tl }
  {
    \prop_put:Nnx \l__column_computed_width_prop
      { ##1 } { \l__tblr_b_tl }
    \dim_add:Nn \l__column_target_dim
      { \l__tblr_a_tl + \l__tblr_c_tl - \l__tblr_b_tl }
    \prop_remove:Nn \l__column_coefficient_prop { ##1 }
  }
  {
    \__tblr_add_dimen_value:Nnn
      \l__column_computed_width_prop { ##1 } { \l__tblr_a_tl }
  }
}
}
}
\LogTblrTracing { target }
}

\cs_new_protected:Npn \__tblr_adjust_extendable_column_width_negative:
{
  \dim_zero:N \l_tmpa_dim
  \prop_map_inline:Nn \l__column_natural_width_prop
    { \dim_add:Nn \l_tmpa_dim { ##2 } }
  \tl_set:Nx \l_tmpa_tl
    { \dim_ratio:nn { \l__column_target_dim } { \l_tmpa_dim } }
  \dim_zero:N \l__column_target_dim
  \prop_map_inline:Nn \l__column_natural_width_prop
    {
      \tl_set:Nx \l_tmpb_tl { \dim_eval:n { ##2 * \l_tmpa_tl } }
      \__tblr_add_dimen_value:Nnn
        \l__column_computed_width_prop { ##1 } { \l_tmpb_tl }
    }
  \LogTblrTracing { target }
}

%%% -----
%%% \section{Calculate and Adjust Multispan Cells}
%%% -----

%% Compute and adjust widths when there are some span cells.
%% By default, we will compute column widths from span widths;
%% but if we set table option "hspan = minimal",
%% we will compute span widths from column widths.

\cs_new_protected:Npn \__tblr_adjust_sizes_for_span_cells:
{
  \__tblr_prop_if_in:nnT { inner } { colspan }
  {
    \__tblr_collect_column_widths_skips:
    \str_if_eq:xnTF
      { \__tblr_prop_item:ne { inner } { hspan } } { minimal }
      {
        \__tblr_set_span_widths_from_column_widths:
      }
  }
}

```

```

    {
      \tblr_collect_span_widths:
      \tblr_set_column_widths_from_span_widths:
    }
    \LogTblrTracing { column }
    \tblr_calculate_cell_sizes:
  }
  \tblr_prop_if_in:nnT { inner } { rowspan }
  {
    \tblr_collect_row_heights_skips:
    \tblr_collect_span_heights:
    \tblr_set_row_heights_from_span_heights:
    \LogTblrTracing { row }
  }
}

\prop_new:N \l__tblr_col_item_skip_size_prop
\prop_new:N \l__tblr_col_span_size_prop
\prop_new:N \l__tblr_row_item_skip_size_prop
\prop_new:N \l__tblr_row_span_size_prop

\cs_new_protected:Npn \tblr_collect_column_widths_skips:
{
  \prop_clear:N \l__tblr_col_item_skip_size_prop
  \int_step_variable:nNn { \c@colcount } \l__tblr_j_tl
  {
    \int_compare:nNnTF { \l__tblr_j_tl } > { 1 }
    {
      \prop_put:Nxx \l__tblr_col_item_skip_size_prop { skip[\l__tblr_j_tl] }
      {
        \dim_eval:n
        {
          \tblr_data_item:nen { column }
          { \int_eval:n { \l__tblr_j_tl - 1 } } { rightsep }
          +
          \tblr_spec_item:ne { vline }
          { [\l__tblr_j_tl] / @vline-width }
          +
          \tblr_data_item:nen { column } { \l__tblr_j_tl } { leftsep }
        }
      }
    }
  }
  \prop_put:Nxn \l__tblr_col_item_skip_size_prop { skip[\l__tblr_j_tl] }
  { Opt }
}
\prop_put:Nxx \l__tblr_col_item_skip_size_prop { item[\l__tblr_j_tl] }
{ \tblr_data_item:nen { column } { \l__tblr_j_tl } { @col-width } }
}
\tblr_do_if_tracing:nn { cellspan }
{ \prop_log:N \l__tblr_col_item_skip_size_prop }
}

\cs_new_protected:Npn \tblr_collect_row_heights_skips:
{
  \prop_clear:N \l__tblr_row_item_skip_size_prop
  \int_step_variable:nNn { \c@rowcount } \l__tblr_i_tl

```

```

{
  \int_compare:nNnTF { \l__tblr_i_tl } > { 1 }
  {
    \prop_put:Nxx \l__tblr_row_item_skip_size_prop { skip[\l__tblr_i_tl] }
    {
      \dim_eval:n
      {
        \__tblr_data_item:nen { row }
        { \int_eval:n { \l__tblr_i_tl - 1 } } { belowsep }
        +
        \__tblr_spec_item:ne { hline }
        { [ \l__tblr_i_tl ] / @hline-height }
        +
        \__tblr_data_item:nen { row } { \l__tblr_i_tl } { abovesep }
      }
    }
  }
  {
    \prop_put:Nxn \l__tblr_row_item_skip_size_prop { skip[\l__tblr_i_tl] }
    { Opt }
  }
  \__tblr_collect_one_row_height:NN \l__tblr_i_tl \l__tblr_h_tl
  \prop_put:Nxx \l__tblr_row_item_skip_size_prop
  { item[\l__tblr_i_tl] } { \l__tblr_h_tl }
}
\__tblr_do_if_tracing:nn { cellspan }
{ \prop_log:N \l__tblr_row_item_skip_size_prop }
}

%% #1: row number; #2: tl with result
\cs_new_protected:Npn \__tblr_collect_one_row_height:NN #1 #2
{
  \tl_set:Nx #2 { \__tblr_data_item:nen { row } { #1 } { @row-height } }
}

\cs_new_protected:Npn \__tblr_collect_span_widths:
{
  \prop_clear:N \l__tblr_col_span_size_prop
  \int_step_variable:nNn { \c@colcount } \l__tblr_j_tl
  {
    \int_step_variable:nNn { \c@rowcount } \l__tblr_i_tl
    {
      \tl_set:Nx \l__tblr_a_tl
      {
        \__tblr_data_item:neen { cell }
        { \l__tblr_i_tl } { \l__tblr_j_tl } { colspan }
      }
      \int_compare:nNnT { \l__tblr_a_tl } > { 1 }
      {
        \__tblr_put_if_larger:Nxx \l__tblr_col_span_size_prop
        {
          ( \l__tblr_j_tl -
            \int_eval:n { \l__tblr_j_tl + \l__tblr_a_tl - 1 } )
        }
        {
          \__tblr_data_item:neen { cell }
          { \l__tblr_i_tl } { \l__tblr_j_tl } { @cell-width }
        }
      }
    }
  }
}

```

```

    }
  }
}
__tblr_do_if_tracing:nn { colspan }
  { \prop_log:N \l__tblr_col_span_size_prop }
}

\prop_new:N \l__tblr_row_span_to_row_prop

\cs_new_protected:Npn \__tblr_collect_span_heights:
{
  \prop_clear:N \l__tblr_row_span_to_row_prop
  \prop_clear:N \l__tblr_row_span_size_prop
  \int_step_variable:nNn { \c@rowcount } \l__tblr_i_tl
  {
    \int_step_variable:nNn { \c@colcount } \l__tblr_j_tl
    {
      \tl_set:Nx \l__tblr_a_tl
      {
        \__tblr_data_item:neen { cell }
          { \l__tblr_i_tl } { \l__tblr_j_tl } { rowspan }
      }
      \int_compare:nNnT { \l__tblr_a_tl } > {1}
      {
        \tl_set:Nx \l__tblr_v_tl
        {
          \__tblr_data_item:neen { cell }
            { \l__tblr_i_tl } { \l__tblr_j_tl } { valign }
        }
        \tl_if_eq:NnT \l__tblr_v_tl { h }
        {
          \tl_set:Nx \l__tblr_h_tl
          {
            \__tblr_data_item:nen { row }
              { \l__tblr_i_tl } { @row-head }
          }
          \__tblr_data_gput:neenV { cell }
            { \l__tblr_i_tl } { \l__tblr_j_tl } { @cell-height }
            \l__tblr_h_tl
        }
        \tl_if_eq:NnT \l__tblr_v_tl { f }
        {
          \tl_set:Nx \l__tblr_d_tl
          {
            \__tblr_data_item:nen
              { row }
              { \int_eval:n { \l__tblr_i_tl + \l__tblr_a_tl - 1 } }
              { @row-foot }
          }
          \__tblr_data_gput:neenV { cell }
            { \l__tblr_i_tl } { \l__tblr_j_tl } { @cell-depth }
            \l__tblr_d_tl
        }
      }
      \__tblr_put_if_larger:Nxx \l__tblr_row_span_size_prop
      {
        ( \l__tblr_i_tl -
          \int_eval:n { \l__tblr_i_tl + \l__tblr_a_tl - 1 } )
      }
    }
  }
}

```

```

        {
            \dim_eval:n
            {
                \__tblr_data_item:neen { cell }
                { \l__tblr_i_tl } { \l__tblr_j_tl } { @cell-height }
                +
                \__tblr_data_item:neen { cell }
                { \l__tblr_i_tl } { \l__tblr_j_tl } { @cell-depth }
            }
        }
    \prop_put:Nxx \l__tblr_row_span_to_row_prop
    { [\l__tblr_i_tl][\l__tblr_j_tl] }
    { \int_eval:n {\l__tblr_i_tl + \l__tblr_a_tl - 1} }
}
}
}
\__tblr_do_if_tracing:nm { cellspan }
{
    \prop_log:N \l__tblr_row_span_to_row_prop
    \prop_log:N \l__tblr_row_span_size_prop
}
}

%% Compute and set column widths from span widths
\cs_new_protected:Npn \__tblr_set_column_widths_from_span_widths:
{
    \str_if_eq:xnTF
    { \__tblr_prop_item:ne { inner } { hspan } }
    { even }
    {
        \__tblr_distribute_span_sizes_even:xNN
        { \int_use:N \c@colcount }
        \l__tblr_col_item_skip_size_prop
        \l__tblr_col_span_size_prop
    }
    {
        \__tblr_distribute_span_sizes_default:xNN
        { \int_use:N \c@colcount }
        \l__tblr_col_item_skip_size_prop
        \l__tblr_col_span_size_prop
    }
}
\__tblr_set_all_column_widths:
}

%% Compute and set row heights from span heights
\cs_new_protected:Npn \__tblr_set_row_heights_from_span_heights:
{
    \str_if_eq:xnTF
    { \__tblr_prop_item:ne { inner } { vspan } }
    { even }
    {
        \__tblr_distribute_span_sizes_even:nNN
        { \int_use:N \c@rowcount }
        \l__tblr_row_item_skip_size_prop
        \l__tblr_row_span_size_prop
    }
    {
        \__tblr_distribute_span_sizes_default:xNN

```

```

        { \int_use:N \c@rowcount }
        \l__tblr_row_item_skip_size_prop
        \l__tblr_row_span_size_prop
    }
    \__tblr_set_all_row_heights:
}

%% See page 245 in Chapter 22 of TeXbook
%% #1: total number of items
%% #2: prop list with item sizes and skip sizes; #3: prop list with span sizes
\cs_new_protected:Npn \__tblr_distribute_span_sizes_default:nNN #1 #2 #3
{
    \int_step_variable:nNn { #1 } \l__tblr_j_tl
    {
        \dim_set:Nn \l__tblr_w_dim
        {
            \prop_item:Ne #2 { item[\l__tblr_j_tl] }
        }
        \int_step_variable:nNn { \l__tblr_j_tl - 1 } \l__tblr_i_tl
        {
            \tl_set:Nx \l__tblr_a_tl
            { \prop_item:Ne #3 { (\l__tblr_i_tl-\l__tblr_j_tl) } }
            \tl_if_empty:NF \l__tblr_a_tl
            {
                \int_step_variable:nnNn
                { \l__tblr_i_tl } { \l__tblr_j_tl - 1 } \l__tblr_k_tl
                {
                    \__tblr_do_if_tracing:nn { cellspan }
                    {
                        \tl_log:x
                        { \l__tblr_j_tl : \l__tblr_i_tl -> \l__tblr_k_tl }
                    }
                    \tl_set:Nx \l__tmpa_tl
                    {
                        \prop_item:Ne #2 { itemskip[\l__tblr_k_tl] }
                    }
                    \tl_set:Nx \l__tblr_a_tl
                    { \dim_eval:n { \l__tblr_a_tl - \l__tmpa_tl } }
                }
                \dim_compare:nNnT { \l__tblr_a_tl } > { \l__tblr_w_dim }
                {
                    \dim_set:Nn \l__tblr_w_dim { \l__tblr_a_tl }
                }
            }
        }
    }
    \prop_put:Nxx #2
    { item[\l__tblr_j_tl] } { \dim_use:N \l__tblr_w_dim }
    \int_compare:nNnT { \l__tblr_j_tl } < { #1 }
    {
        \tl_set:Nx \l__tmpb_tl
        {
            \prop_item:Ne #2
            { skip[\int_eval:n { \l__tblr_j_tl + 1 } ] }
        }
        \dim_add:Nn \l__tblr_w_dim { \l__tmpb_tl }
        \prop_put:Nxx #2
        { itemskip[\l__tblr_j_tl] } { \dim_use:N \l__tblr_w_dim }
    }
}

```

```

    }
    \__tblr_do_if_tracing:nn { colspan } { \prop_log:N #2 }
  }
\cs_generate_variant:Nn \__tblr_distribute_span_sizes_default:nNN { x }

%% #1: total number of items
%% #2: prop list with item sizes and skip sizes; #3: prop list with span sizes
\cs_new_protected:Npn \__tblr_distribute_span_sizes_even:nNN #1 #2 #3
{
  \prop_clear:N \l_tmpa_prop
  \prop_map_inline:Nn #3
  {
    \__tblr_get_span_from_to:w ##1
    \dim_set:Nn \l_tmpa_dim {##2}
    \dim_sub:Nn \l_tmpa_dim { \prop_item:Ne #2 { item[\l__tblr_a_tl] } }
    \int_step_inline:nnn { \l__tblr_a_tl + 1 } { \l__tblr_b_tl }
    {
      \dim_sub:Nn \l_tmpa_dim
      {
        \prop_item:Ne #2 { skip[####1] } + \prop_item:Nn #2 { item[####1] }
      }
    }
    \__tblr_do_if_tracing:nn { colspan }
    {
      \tl_log:x { \l__tblr_a_tl -> \l__tblr_b_tl : ~ \dim_use:N \l_tmpa_dim }
    }
    \dim_compare:nNnT {\l_tmpa_dim} > {Opt}
    {
      \tl_set:Nx \l_tmpa_tl
      { \dim_eval:n { \l_tmpa_dim / ( \l__tblr_b_tl - \l__tblr_a_tl + 1 ) } }
      \int_step_inline:nnn { \l__tblr_a_tl } { \l__tblr_b_tl }
      {
        \__tblr_put_if_larger:NnV \l_tmpa_prop {####1} \l_tmpa_tl
      }
    }
  }
}
\__tblr_do_if_tracing:nn { colspan } { \prop_log:N \l_tmpa_prop }
\prop_map_inline:Nn \l_tmpa_prop
{
  \__tblr_add_dimen_value:Nnn #2 {item[##1]} {##2}
}
\__tblr_do_if_tracing:nn { colspan } { \prop_log:N #2 }
}
\cs_generate_variant:Nn \__tblr_distribute_span_sizes_even:nNN { x }

\cs_new_protected:Npn \__tblr_get_span_from_to:w (#1-#2)
{
  \tl_set:Nn \l__tblr_a_tl {#1}
  \tl_set:Nn \l__tblr_b_tl {#2}
}

\cs_new_protected:Npn \__tblr_set_all_column_widths:
{
  \int_step_variable:nNn { \c@colcount } \l__tblr_j_tl
  {
    \__tblr_data_gput:nene { column }
    { \l__tblr_j_tl } { width }
  }
}

```

```

        { \prop_item:Ne \l__tblr_col_item_skip_size_prop { item[\l__tblr_j_tl] } }
    }
}

\cs_new_protected:Npn \__tblr_set_all_row_heights:
{
  \int_step_variable:nNn { \c@rowcount } \l__tblr_i_tl
  {
    \tl_set:Nx \l__tblr_h_tl
    {
      \__tblr_data_item:nen { row } { \l__tblr_i_tl } { @row-head }
    }
    \tl_set:Nx \l__tblr_d_tl
    {
      \__tblr_data_item:nen { row } { \l__tblr_i_tl } { @row-foot }
    }
    \tl_set:Nx \l__tblr_a_tl
    {
      \prop_item:Ne \l__tblr_row_item_skip_size_prop { item[\l__tblr_i_tl] }
    }
    \__tblr_collect_one_row_height:NN \l__tblr_i_tl \l__tblr_t_tl
    \__tblr_data_gput:nene { row }
    { \l__tblr_i_tl } { @row-height } { \l__tblr_a_tl }
  }
}

%% Compute and set span widths from column widths
\cs_new_protected:Npn \__tblr_set_span_widths_from_column_widths:
{
  \int_step_variable:nNn { \c@colcount } \l__tblr_j_tl
  {
    \int_step_variable:nNn { \c@rowcount } \l__tblr_i_tl
    {
      \tl_set:Nx \l__tblr_a_tl
      {
        \__tblr_data_item:neen { cell }
        { \l__tblr_i_tl } { \l__tblr_j_tl } { colspan }
      }
      \int_compare:nNnT { \l__tblr_a_tl } > {1}
      {
        \__tblr_calc_span_widths:xxN
        { \l__tblr_j_tl }
        { \int_eval:n { \l__tblr_j_tl + \l__tblr_a_tl - 1 } }
        \l__tblr_w_dim
        \__tblr_data_gput:neene { cell }
        { \l__tblr_i_tl } { \l__tblr_j_tl } { width }
        { \dim_use:N \l__tblr_w_dim }
      }
    }
  }
}

%% Cell is spanned from col #1 to col #2, #3 is the return dim
\cs_new_protected:Npn \__tblr_calc_span_widths:nnN #1 #2 #3
{
  \dim_zero:N #3
  \int_step_inline:nnn { #1 } { #2 }

```

```

    {
      \tl_set:Nx \l_tmpa_tl
        { \prop_item:Ne \l__tblr_col_item_skip_size_prop { skip[##1] } }
      \tl_set:Nx \l_tmpb_tl
        { \prop_item:Ne \l__tblr_col_item_skip_size_prop { item[##1] } }
      \dim_add:Nn #3 { \dim_eval:n { \l_tmpa_tl + \l_tmpb_tl } }
    }
  }
\cs_generate_variant:Nn \l__tblr_calc_span_widths:nnN { xxN }

%%% -----
%%> \section{Header and Footer Styles}
%%% -----

\prop_new:N \l__tblr_element_styles_prop

\cs_new_protected:Npn \__tblr_style_put:nn #1 #2
{
  \prop_put:Nnn \l__tblr_element_styles_prop {#1} {#2}
}
\cs_generate_variant:Nn \__tblr_style_put:nn { nV, ne, en }

\cs_new:Npn \__tblr_style_item:n #1
{
  \prop_item:Nn \l__tblr_element_styles_prop {#1}
}

\cs_new_protected:Npn \__tblr_style_log:
{
  \prop_log:N \l__tblr_element_styles_prop
}

\tl_new:N \l__tblr_element_name_tl
\tl_new:N \l__tblr_element_styles_tl

%% #1: list of element names; #2: element styles
\NewDocumentCommand \SetTblrStyle { m +m }
{
  \tl_set:Nn \l__tblr_element_styles_tl {#2}
  \keys_set:nn { tblr-element } {#1}
  \ignorespaces
}

\keys_define:nn { tblr-element }
{
  head .meta:n = { firsthead, middlehead, lasthead },
  foot .meta:n = { firstfoot, middlefoot, lastfoot },
  unknown .code:n = \__tblr_set_element_styles:V \l_keys_key_str,
}

\cs_new_protected:Npn \__tblr_set_element_styles:n #1
{
  \tl_set:Nn \l__tblr_element_name_tl {#1}
  \keys_set:nV { tblr-style } \l__tblr_element_styles_tl
}

```

```

\cs_generate_variant:Nn \__tblr_set_element_styles:n { V }

\keys_define:nn { tblr-style }
{
  halign .code:n = \__tblr_element_gput_style:nn { halign } {#1},
  l      .meta:n = { halign = l },
  c      .meta:n = { halign = c },
  r      .meta:n = { halign = r },
  fg     .code:n = \__tblr_element_gput_style:nn { fg } {#1},
  font   .code:n = \__tblr_element_gput_style:nn { font } {#1},
  hang   .code:n = \__tblr_element_gput_style:nn { hang } {#1},
  indent .code:n = \__tblr_element_gput_style:nn { indent } {#1},
  unknown .code:n = \__tblr_element_unknown_key:Vn \l_keys_key_str {#1},
}

\cs_new_protected:Npn \__tblr_element_gput_style:nn #1 #2
{
  \__tblr_style_put:en { \l__tblr_element_name_tl / #1 } {#2}
}

\cs_new_protected:Npn \__tblr_element_unknown_key:nn #1 #2
{
  \regex_match:NnTF \c__tblr_is_color_key_regex {#1}
  { \__tblr_style_put:en { \l__tblr_element_name_tl / fg } {#1} }
  {
    %% unknown key name has been changed to string in \l_keys_key_str
    \tl_set_rescan:Nnn \l__tblr_f_tl {} {#1}
    \tl_if_head_eq_catcode:VNTF \l__tblr_f_tl \scan_stop:
    {
      \__tblr_style_put:en { \l__tblr_element_name_tl / font } \l__tblr_f_tl
    }
    {
      \__tblr_style_put:en { \l__tblr_element_name_tl / #1 } {#2}
    }
  }
}

\cs_generate_variant:Nn \__tblr_element_unknown_key:nn { Vn }

%%% -----
%%> \section{Helper Functions for Templates}
%%% -----

\tl_new:N \l__tblr_template_name_tl
\tl_new:N \l__tblr_template_code_tl

\keys_define:nn { tblr-def-template }
{
  unknown .code:n = \__tblr_def_template:V \l_keys_key_str,
}

%% #1: head/foot element; #2: template name; #3: template code
%% If the template name = default, we enable the template at once
%% Otherwise, we may enable the template by using \SetTblrTemplate command
\NewDocumentCommand \DefTblrTemplate { m m +m }
{
  \tl_set:Nn \l__tblr_template_name_tl {#2}
}

```

```

\l_set:Nn \l__tblr_template_code_tl {#3}
\keys_set:nn { tblr-def-template } {#1}
\ignorespaces
}

\cs_new_protected:Npn \__tblr_def_template:n #1
{
\l_set_eq:cN { l__tblr_template_ #1 _ \l__tblr_template_name_tl _tl }
\l__tblr_template_code_tl
}
\cs_generate_variant:Nn \__tblr_def_template:n { V }

\keys_define:nn { tblr-set-template }
{
unknown .code:n = \__tblr_set_template:V \l_keys_key_str,
}

%% #1: head/foot element; #2: template name
\NewDocumentCommand \SetTblrTemplate { m m }
{
\l_set:Nn \l__tblr_template_name_tl {#2}
\keys_set:nn { tblr-set-template } {#1}
\ignorespaces
}

\cs_new_protected:Npn \__tblr_set_template:n #1
{
\l_set_eq:cc { l__tblr_template_ #1 _default_tl }
{ l__tblr_template_ #1 _ \l__tblr_template_name_tl _tl }
}
\cs_generate_variant:Nn \__tblr_set_template:n { V }

\NewExpandableDocumentCommand \GetTblrStyle { m m }
{
\__tblr_style_item:n { #1 / #2 }
}

\NewDocumentCommand \UseTblrFont { m }
{
\GetTblrStyle {#1} { font } \selectfont
}

\l_new:N \l__tblr_use_color_tl

\NewDocumentCommand \UseTblrColor { m }
{
\l_set:Nx \l__tblr_use_color_tl { \GetTblrStyle {#1} { fg } }
\l_if_empty:NF \l__tblr_use_color_tl { \color { \l__tblr_use_color_tl } }
}

%% All halign commands are defined at the beginning of the file
\NewDocumentCommand \UseTblrAlign { m }
{
\use:c { __tblr_halign_command_ \GetTblrStyle {#1} { halign } : }
}

```

```

\l_new:N \l__tblr_use_hang_tl

\NewDocumentCommand \UseTblrHang { m }
{
  \tl_set:Nx \l__tblr_use_hang_tl { \GetTblrStyle {#1} { hang } }
  \tl_if_empty:NF \l__tblr_use_hang_tl
  {
    \tl_put_left:Nn \l__tblr_use_hang_tl
      { \hangafter = 1 \relax \hangindent = }
    \tl_put_right:Nn \l__tblr_use_hang_tl { \relax }
    \exp_args:NV \everypar \l__tblr_use_hang_tl
  }
}

\l_new:N \l__tblr_use_indent_tl

\NewDocumentCommand \UseTblrIndent { m }
{
  \tl_set:Nx \l__tblr_use_indent_tl { \GetTblrStyle {#1} { indent } }
  \tl_if_empty:NF \l__tblr_use_indent_tl
  { \exp_args:NNV \setlength \parindent \l__tblr_use_indent_tl }
}

\AtBeginDocument
{
  \@ifpackageloaded{xcolor}{\RenewDocumentCommand \UseTblrColor {m} {}}
}

%% #1: head/foot element; #2: template name
\NewExpandableDocumentCommand \ExpTblrTemplate { m m }
{
  \tl_use:c { l__tblr_template_ #1 _ #2 _tl }
}

%% #1: head/foot element; #2: template name
\NewDocumentCommand \UseTblrTemplate { m m }
{
  \group_begin:
  \UseTblrFont {#1}
  \UseTblrColor {#1}
  \tl_use:c { l__tblr_template_ #1 _ #2 _tl }
  \group_end:
}

\NewDocumentCommand \MapTblrNotes { +m }
{
  \__tblr_prop_map_inline:nn { note }
  {
    \tl_set_rescan:Nnn \InsertTblrNoteTag {} {##1}
    \tl_set:Nn \InsertTblrNoteText {##2}
    #1
  }
}

\NewDocumentCommand \MapTblrRemarks { +m }
{

```

```

    \_tblr_prop_map_inline:nn { remark }
    {
      \tl_set_rescan:Nnn \InsertTblrRemarkTag {} {##1}
      \tl_set:Nn \InsertTblrRemarkText {##2}
      #1
    }
  }

\NewExpandableDocumentCommand \InsertTblrText { m }
{
  \_tblr_spec_item:nn { outer } {#1}
}

\NewExpandableDocumentCommand \InsertTblrMore { m }
{
  \_tblr_prop_item:nn { more } {#1}
}

%%% -----
%%> \section{Table Continuation Templates}
%%% -----

\DefTblrTemplate { contfoot-text } { normal } { Continued ~ on ~ next ~ page }
\SetTblrTemplate { contfoot-text } { normal }

\DefTblrTemplate { contfoot } { plain }
{
  \noindent
  \raggedleft
  \UseTblrTemplate { contfoot-text } { default }
  \par
}
\DefTblrTemplate { contfoot } { normal }
{
  %% need to set parindent after alignment
  \raggedleft
  \UseTblrAlign { contfoot }
  \UseTblrIndent { contfoot }
  \UseTblrHang { contfoot }
  \leavevmode
  \UseTblrTemplate { contfoot-text } { default }
  \par
}
\SetTblrTemplate { contfoot } { normal }

\DefTblrTemplate { conthead-text } { normal } { ( Continued ) }
\SetTblrTemplate { conthead-text } { normal }

\DefTblrTemplate { conthead } { plain }
{
  \noindent
  \raggedright
  \UseTblrTemplate { conthead-text } { default }
  \par
}
\DefTblrTemplate { conthead } { normal }

```

```

{
  %% need to set parindent after alignment
  \raggedright
  \UseTblrAlign { conthead }
  \UseTblrIndent { conthead }
  \UseTblrHang { conthead }
  \leavevmode
  \UseTblrTemplate { conthead-text } { default }
  \par
}
\SetTblrTemplate { conthead } { normal }

%%% -----
%%> \section{Table Caption Templates}
%%% -----

\tl_new:N \l__tblr_caption_short_tl

\DefTblrTemplate { caption-lot } { normal }
{
  \tl_set:Nx \l__tblr_caption_short_tl { \InsertTblrText { entry } }
  \tl_if_empty:NT \l__tblr_caption_short_tl
    { \tl_set:Nx \l__tblr_caption_short_tl { \InsertTblrText { caption } } }
  \addcontentsline { lot } { table }
    { \protect\numberline { \arabic { table } } { \l__tblr_caption_short_tl } }
}
\SetTblrTemplate { caption-lot } { normal }

%% We need to use \hspace and \enskip, but not ~ or \space,
%% since we want a correct hangindent caption paragraph.

\DefTblrTemplate { caption-tag } { normal } { Table \hspace{0.25em} \thetable }
\SetTblrTemplate { caption-tag } { normal }

\DefTblrTemplate { caption-sep } { normal } { : \enskip }
\SetTblrTemplate { caption-sep } { normal }

\DefTblrTemplate { caption-text } { normal } { \InsertTblrText { caption } }
\SetTblrTemplate { caption-text } { normal }

\box_new:N \l__tblr_caption_box
\box_new:N \l__tblr_caption_left_box

\DefTblrTemplate { caption } { plain }
{
  \hbox_set:Nn \l__tblr_caption_box
  {
    \UseTblrTemplate { caption-tag } { default }
    \UseTblrTemplate { caption-sep } { default }
    \UseTblrTemplate { caption-text } { default }
  }
  \dim_compare:nNnTF { \box_wd:N \l__tblr_caption_box } > { \hsize }
  {
    \noindent
    \hbox_unpack:N \l__tblr_caption_box
  }
}

```

```

    \par
  }
  {
    \centering
    \makebox [\hsize] [c] { \box_use:N \l__tblr_caption_box }
    \par
  }
}
\DefTblrTemplate { caption } { normal }
{
  \hbox_set:Nn \l__tblr_caption_box
  {
    \UseTblrTemplate { caption-tag } { default }
    \UseTblrTemplate { caption-sep } { default }
    \UseTblrTemplate { caption-text } { default }
  }
  \dim_compare:nNnTF { \box_wd:N \l__tblr_caption_box } > { \hsize }
  {
    \UseTblrAlign { caption }
    \UseTblrIndent { caption }
    \hbox_set:Nn \l__tblr_caption_left_box
    {
      \UseTblrTemplate { caption-tag } { default }
      \UseTblrTemplate { caption-sep } { default }
    }
    \hangindent = \box_wd:N \l__tblr_caption_left_box
    \hangafter = 1
    \UseTblrHang { caption }
    \leavevmode
    \hbox_unpack:N \l__tblr_caption_box
    \par
  }
  {
    \centering
    \makebox [\hsize] [c] { \box_use:N \l__tblr_caption_box }
    \par
  }
}
\SetTblrTemplate { caption } { normal }

\DefTblrTemplate { capcont } { plain }
{
  \hbox_set:Nn \l__tblr_caption_box
  {
    \UseTblrTemplate { caption-tag } { default }
    \UseTblrTemplate { caption-sep } { default }
    \UseTblrTemplate { caption-text } { default }
    \space
    \UseTblrTemplate { conthead-text } { default }
  }
  \dim_compare:nNnTF { \box_wd:N \l__tblr_caption_box } > { \hsize }
  {
    \noindent
    \hbox_unpack:N \l__tblr_caption_box
    \par
  }
  {
    \centering

```

```

        \makebox [\hsize] [c] { \box_use:N \l__tblr_caption_box }
    \par
}
}
\DefTblrTemplate { capcont } { normal }
{
    \hbox_set:Nn \l__tblr_caption_box
    {
        \UseTblrTemplate { caption-tag } { default }
        \UseTblrTemplate { caption-sep } { default }
        \UseTblrTemplate { caption-text } { default }
        \space
        \UseTblrTemplate { conthead-text } { default }
    }
    \dim_compare:nNnTF { \box_wd:N \l__tblr_caption_box } > { \hsize }
    {
        \UseTblrAlign { capcont }
        \UseTblrIndent { capcont }
        \hbox_set:Nn \l__tblr_caption_left_box
        {
            \UseTblrTemplate { caption-tag } { default }
            \UseTblrTemplate { caption-sep } { default }
        }
        \hangindent = \box_wd:N \l__tblr_caption_left_box
        \hangafter = 1
        \UseTblrHang { capcont }
        \leavevmode
        \hbox_unpack:N \l__tblr_caption_box
        \par
    }
    {
        \centering
        \makebox [\hsize] [c] { \box_use:N \l__tblr_caption_box }
        \par
    }
}
\SetTblrTemplate { capcont } { normal }

%%% -----
%%> \section{Table Notes Templates}
%%% -----

%% By default the targets generated by \hypertarget are too low
%% Therefore we need to use \Hy@raisedlink command to fix this problem
%% See https://tex.stackexchange.com/questions/17057
%% We also use \use:c in case the private command \Hy@raisedlink is removed
\cs_new_protected:Npn \__tblr_hyper_target:n #1
{
    \cs_if_exist:NT \hypertarget
    {
        \use:c { Hy@raisedlink }
        {
            \hypertarget
            { tblr / \int_use:N \g__tblr_table_count_int / \tl_to_str:n {#1} }
            { }
        }
    }
}

```

```

\cs_generate_variant:Nn \_tblr_hyper_target:n { V }

\cs_new_protected:Npn \_tblr_hyper_link:nn #1 #2
{
  \cs_if_exist:NTF \hyperlink
  {
    \hyperlink
      { tblr / \int_use:N \g__tblr_table_count_int / \tl_to_str:n {#1} }
      { #2 }
  }
  { #2 }
}

\NewDocumentCommand \TblrNote { m }
{
  \_tblr_hyper_link:nn {#1}
  { \textsuperscript { \sffamily \UseTblrFont { note-tag } #1 } }
}

\DefTblrTemplate { note-tag } { normal }
{
  \textsuperscript { \sffamily \UseTblrFont { note-tag } \InsertTblrNoteTag }
}
\SetTblrTemplate { note-tag } { normal }

\DefTblrTemplate { note-target } { normal }
{
  \_tblr_hyper_target:V \InsertTblrNoteTag
}
\SetTblrTemplate { note-target } { normal }

\DefTblrTemplate { note-sep } { normal } { \space }
\SetTblrTemplate { note-sep } { normal }

\DefTblrTemplate { note-text } { normal } { \InsertTblrNoteText }
\SetTblrTemplate { note-text } { normal }

\DefTblrTemplate { note } { plain }
{
  \MapTblrNotes
  {
    \noindent
    \UseTblrTemplate { note-tag } { default }
    \UseTblrTemplate { note-target } { default }
    \UseTblrTemplate { note-sep } { default }
    \UseTblrTemplate { note-text } { default }
  }
  \par
}
}

\DefTblrTemplate { note } { normal }
{
  \UseTblrAlign { note }
  \UseTblrIndent { note }
  \MapTblrNotes
  {
    \hangindent = 0.7em
  }
}

```

```

    \hangafter = 1
    \UseTblrHang { note }
    \leavevmode
    \hbox_to_wd:nn { \the\hangindent }
    {
        \UseTblrTemplate { note-tag } { default }
        \UseTblrTemplate { note-target } { default }
        \hfil
    }
    \UseTblrTemplate { note-text } { default }
    \par
}
}
\DefTblrTemplate { note } { inline }
{
    \UseTblrAlign { note }
    \UseTblrIndent { note }
    \UseTblrHang { note }
    \leavevmode
    \MapTblrNotes
    {
        \UseTblrTemplate { note-tag } { default }
        \UseTblrTemplate { note-target } { default }
        \UseTblrTemplate { note-sep } { default }
        \UseTblrTemplate { note-text } { default }
        \quad
    }
    \par
}
\SetTblrTemplate { note } { normal }

%%% -----
%%> \section{Table Remarks Templates}
%%% -----

\DefTblrTemplate { remark-tag } { normal }
{
    \itshape \UseTblrFont { remark-tag } \InsertTblrRemarkTag
}
\SetTblrTemplate { remark-tag } { normal }

\DefTblrTemplate { remark-sep } { normal } { : \space }
\SetTblrTemplate { remark-sep } { normal }

\DefTblrTemplate { remark-text } { normal } { \InsertTblrRemarkText }
\SetTblrTemplate { remark-text } { normal }

\DefTblrTemplate { remark } { plain }
{
    \MapTblrRemarks
    {
        \noindent
        \UseTblrTemplate { remark-tag } { default }
        \UseTblrTemplate { remark-sep } { default }
        \UseTblrTemplate { remark-text } { default }
        \par
    }
}

```

```

}
\DefTblrTemplate { remark } { normal }
{
  \UseTblrAlign { remark }
  \UseTblrIndent { remark }
  \MapTblrRemarks
  {
    \hangindent = 0.7em
    \hangafter = 1
    \UseTblrHang { remark }
    \leavevmode
    \UseTblrTemplate { remark-tag } { default }
    \UseTblrTemplate { remark-sep } { default }
    \UseTblrTemplate { remark-text } { default }
    \par
  }
}
\DefTblrTemplate { remark } { inline }
{
  \UseTblrAlign { remark }
  \UseTblrIndent { remark }
  \UseTblrHang { remark }
  \leavevmode
  \MapTblrRemarks
  {
    \UseTblrTemplate { remark-tag } { default }
    \UseTblrTemplate { remark-sep } { default }
    \UseTblrTemplate { remark-text } { default }
    \quad
  }
  \par
}
\SetTblrTemplate { remark } { normal }

%%% -----
%%> \section{Header and Footer Templates}
%%% -----

\tl_new:N \g__tblr_template_firsthead_default_tl
\tl_new:N \g__tblr_template_middlehead_default_tl
\tl_new:N \g__tblr_template_lasthead_default_tl
\tl_new:N \g__tblr_template_firstfoot_default_tl
\tl_new:N \g__tblr_template_middlefoot_default_tl
\tl_new:N \g__tblr_template_lastfoot_default_tl

\keys_define:nn { tblr-def-template }
{
  head .meta:n = { firsthead, middlehead, lasthead },
  foot .meta:n = { firstfoot, middlefoot, lastfoot },
}

\keys_define:nn { tblr-set-template }
{
  head .meta:n = { firsthead, middlehead, lasthead },
  foot .meta:n = { firstfoot, middlefoot, lastfoot },
}

```

```

\DefTblrTemplate { firsthead } { normal }
{
  \UseTblrTemplate { caption } { default }
  \UseTblrTemplate { caption-lot } { default }
}

\DefTblrTemplate { middlehead, lasthead } { normal }
{
  \UseTblrTemplate { capcont } { default }
}

\DefTblrTemplate { firstfoot, middlefoot } { normal }
{
  \UseTblrTemplate { contfoot } { default }
}

\DefTblrTemplate { lastfoot } { normal }
{
  \UseTblrTemplate { note } { default }
  \UseTblrTemplate { remark } { default }
}

\SetTblrTemplate { head } { normal }
\SetTblrTemplate { foot } { normal }

%%% -----
%%> \section{Build the Whole Table}
%%% -----

\cs_new:Npn \__tblr_box_height:N #1
{
  \dim_eval:n { \box_ht:N #1 + \box_dp:N #1 }
}

\cs_new_protected:Npn \__tblr_build_head_foot:
{
  \__tblr_build_row_head_foot:
  \__tblr_build_table_head_foot:
}

\tl_new:N \l__tblr_row_head_tl
\tl_new:N \l__tblr_row_foot_tl
\box_new:N \l__tblr_row_head_box
\box_new:N \l__tblr_row_foot_box
\dim_new:N \l__tblr_row_head_foot_dim

\cs_new_protected:Npn \__tblr_build_row_head_foot:
{
  %% \l__tblr_row_head_tl and \l__tblr_row_foot_tl may be empty
  \tl_set:Nx \l__tblr_row_head_tl { \__tblr_prop_item:ne { inner } { rowhead } }
  \int_compare:nNnTF { \l__tblr_row_head_tl + 0 } > { 0 }
  { \__tblr_build_one_table:nn {1} { \l__tblr_row_head_tl } }
  { \__tblr_build_one_hline:n {1} }
  \box_set_eq:NN \l__tblr_row_head_box \l__tblr_table_box
  \tl_set:Nx \l__tblr_row_foot_tl { \__tblr_prop_item:ne { inner } { rowfoot } }
}

```

```

\int_compare:nNnTF { \l__tblr_row_foot_tl + 0 } > { 0 }
{
  \__tblr_build_one_table:nn
    { \c@rowcount - \l__tblr_row_foot_tl + 1 } { \c@rowcount }
}
{ \__tblr_build_one_hline:n { \int_eval:n { \c@rowcount + 1 } } }
\box_set_eq:NN \l__tblr_row_foot_box \l__tblr_table_box
\dim_set:Nn \l__tblr_row_head_foot_dim
{
  \__tblr_box_height:N \l__tblr_row_head_box
  + \__tblr_box_height:N \l__tblr_row_foot_box
}
}

\dim_new:N \tablewidth

\cs_new_protected:Npn \__tblr_get_table_width:
{
  \dim_zero:N \tablewidth
  \int_step_inline:nn { \c@colcount }
  {
    \dim_add:Nn \tablewidth
      {
        \__tblr_spec_item:nn { vline } { [##1] / @vline-width }
        +
        \__tblr_data_item:nnn { column } {##1} { leftsep }
        +
        \__tblr_data_item:nnn { column } {##1} { @col-width }
        +
        \__tblr_data_item:nnn { column } {##1} { rightsep }
      }
  }
  \dim_add:Nn \tablewidth
  {
    \__tblr_spec_item:ne { vline }
    { [ \int_eval:n { \c@colcount + 1 } ] / @vline-width }
  }
}

\box_new:N \l__tblr_table_firsthead_box
\box_new:N \l__tblr_table_middlehead_box
\box_new:N \l__tblr_table_lasthead_box
\box_new:N \l__tblr_table_firstfoot_box
\box_new:N \l__tblr_table_middlefoot_box
\box_new:N \l__tblr_table_lastfoot_box

\cs_new_protected:Npn \__tblr_build_table_head_foot:
{
  \__tblr_get_table_width:
  \__tblr_build_table_head_aux:Nn \l__tblr_table_firsthead_box
  {
    \tl_set:Nn \l_tmpa_tl { \InsertTblrText { label } }
    \tl_if_empty:NF \l_tmpa_tl { \exp_args:NV \label \l_tmpa_tl }
    \UseTblrTemplate { firsthead } { default }
  }
  \__tblr_build_table_head_aux:Nn
  \l__tblr_table_middlehead_box { \UseTblrTemplate { middlehead } { default } }
}

```

```

    \__tblr_build_table_head_aux:Nn
      \l__tblr_table_lasthead_box { \UseTblrTemplate { lasthead } { default } }
    \__tblr_build_table_foot_aux:Nn
      \l__tblr_table_firstfoot_box { \UseTblrTemplate { firstfoot } { default } }
    \__tblr_build_table_foot_aux:Nn
      \l__tblr_table_middlefoot_box { \UseTblrTemplate { middlefoot } { default } }
    \__tblr_build_table_foot_aux:Nn
      \l__tblr_table_lastfoot_box { \UseTblrTemplate { lastfoot } { default } }
  }

\cs_new_protected:Npn \__tblr_build_table_head_aux:Nn #1 #2
{
  \vbox_set:Nn #1
  {
    \hsize = \tablewidth
    \parindent = 0pt \relax
    \vbox:n {#2}
    \skip_vertical:n { \__tblr_spec_item:nn { outer } { headsep } }
  }
}

\cs_new_protected:Npn \__tblr_build_table_foot_aux:Nn #1 #2
{
  \vbox_set:Nn #1
  {
    \hsize = \tablewidth
    \skip_vertical:n { \__tblr_spec_item:nn { outer } { footsep } }
    \parindent = 0pt \relax
    \vbox:n {#2}
  }
}

\cs_new_protected:Npn \__tblr_build_whole:
{
  \tl_if_eq:enTF { \__tblr_spec_item:nn { outer } { long } } { true }
  { \__tblr_build_long_table:e { \__tblr_spec_item:nn { outer } { halign } } }
  { \__tblr_build_short_table:e { \__tblr_spec_item:nn { outer } { valign } } }
}

\dim_new:N \l__tblr_remain_height_dim
\tl_new:N \l__tblr_long_from_tl
\tl_new:N \l__tblr_long_to_tl
\int_new:N \l__tblr_table_page_int
\bool_new:N \l__tblr_table_page_break_bool

%% #1: table alignment
%% For long table, we need to leave hmode first to get correct \pagetotal
%% Also remove topskip and presep if we are at the beginning of the page
\cs_new_protected:Npn \__tblr_build_long_table:n #1
{
  \LogTblrTracing { page }
  \par
  \LogTblrTracing { page }
  \dim_compare:nNnTF { \pagegoal } = { \maxdimen }
  { \hbox{} \kern-\topskip \nobreak }
  { \skip_vertical:n { \__tblr_spec_item:nn { outer } { presep } } }
  \LogTblrTracing { page }
}

```

```

\nointerlineskip
\mode_leave_vertical:
\LogTblrTracing { page }
\hrule height ~ Opt
\LogTblrTracing { page }
\int_set:Nn \l__tblr_table_page_int {1}
\refstepcounter { table }
\__tblr_build_head_foot:
\dim_set:Nn \l__tblr_remain_height_dim
  { \pagegoal - \pagetotal - \l__tblr_row_head_foot_dim }
\tl_set:Nx \l__tblr_long_from_tl { \int_eval:n { \l__tblr_row_head_tl + 1 } }
\tl_set:Nx \l__tblr_long_to_tl
  { \int_eval:n { \c@rowcount - ( \l__tblr_row_foot_tl + 0 ) } }
\int_step_variable:nnNn
  { \l__tblr_long_from_tl } { \l__tblr_long_to_tl } \l__tblr_i_tl
  {
    \dim_set:Nn \l_tmpa_dim
      {
        \__tblr_data_item:nen { row } { \l__tblr_i_tl } { abovesep }
        +
        \__tblr_data_item:nen { row } { \l__tblr_i_tl } { @row-height }
        +
        \__tblr_data_item:nen { row } { \l__tblr_i_tl } { belowsep }
        +
        \__tblr_spec_item:ne { hline }
        { [ \int_eval:n { \l__tblr_i_tl + 1 } ] / @hline-height }
      }
    \__tblr_check_table_page_break:NNN
      \l__tblr_remain_height_dim \l_tmpa_dim \l__tblr_table_page_break_bool
    \bool_if:NTF \l__tblr_table_page_break_bool
      {
        \__tblr_do_if_tracing:nn { page } { \tl_log:N \l__tblr_i_tl }
        \int_compare:nNnTF
          { \l__tblr_i_tl - \l__tblr_long_from_tl } > {1}
          {
            \__tblr_build_page_table:nmx {#1}
              { \l__tblr_long_from_tl } { \int_eval:n { \l__tblr_i_tl - 1 } }
            \int_incr:N \l__tblr_table_page_int
          }
        \newpage
        \hbox{}\kern-\topskip\nobreak
        \noindent
        \LogTblrTracing { page }
        \dim_set:Nn \l__tblr_remain_height_dim
          { \pagegoal - \pagetotal - \l__tblr_row_head_foot_dim - \l_tmpa_dim }
        \tl_set_eq:NN \l__tblr_long_from_tl \l__tblr_i_tl
      }
      {
        \dim_add:Nn \l__tblr_remain_height_dim { -\l_tmpa_dim }
      }
  }
}
\int_compare:nNnTF { \l__tblr_table_page_int } = {1}
{
  \box_set_eq:NN \l__tblr_table_head_box \l__tblr_table_firsthead_box
  \box_set_eq:NN \l__tblr_table_foot_box \l__tblr_table_lastfoot_box
}
{
  \box_set_eq:NN \l__tblr_table_head_box \l__tblr_table_lasthead_box
}

```

```

    \box_set_eq:NN \l__tblr_table_foot_box \l__tblr_table_lastfoot_box
  }
  \__tblr_build_page_table:nnn
  {#1} { \l__tblr_long_from_tl } { \l__tblr_long_to_tl }
  \skip_vertical:n { \__tblr_spec_item:nn { outer } { postsep } }
  \hrule height ~ Opt
}
\cs_generate_variant:Nn \__tblr_build_long_table:n { e }

\box_new:N \l__tblr_table_head_box
\box_new:N \l__tblr_table_foot_box
\dim_new:N \l__tblr_table_head_foot_dim
\dim_new:N \l__tblr_table_head_body_foot_dim

%% #1: remain dimension; #2: row dimension; #3: break page or not
\cs_new_protected:Npn \__tblr_check_table_page_break:NNN #1 #2 #3
{
  \int_compare:nNnTF { \l__tblr_table_page_int } = {1}
  {
    \dim_set:Nn \l__tblr_table_head_body_foot_dim
    {
      \__tblr_box_height:N \l__tblr_table_firsthead_box
      + #2 + \__tblr_box_height:N \l__tblr_table_firstfoot_box
    }
    \box_set_eq:NN \l__tblr_table_head_box \l__tblr_table_firsthead_box
    \dim_compare:nNnTF
    { \l__tblr_table_head_body_foot_dim } > {#1}
    {
      \bool_set_true:N #3
      \box_set_eq:NN \l__tblr_table_foot_box \l__tblr_table_firstfoot_box
    }
    { \bool_set_false:N #3 }
  }
  {
    \dim_set:Nn \l__tblr_table_head_body_foot_dim
    {
      \__tblr_box_height:N \l__tblr_table_middlehead_box
      + #2 + \__tblr_box_height:N \l__tblr_table_middlefoot_box
    }
    \box_set_eq:NN \l__tblr_table_head_box \l__tblr_table_middlehead_box
    \dim_compare:nNnTF
    { \l__tblr_table_head_body_foot_dim } > {#1}
    {
      \bool_set_true:N #3
      \box_set_eq:NN \l__tblr_table_foot_box \l__tblr_table_middlefoot_box
    }
    { \bool_set_false:N #3 }
  }
}

\box_new:N \l__tblr_table_box

%% #1: table alignment; #2: row from; #3: row to
\cs_new_protected:Npn \__tblr_build_page_table:nnn #1 #2 #3
{
  \bool_set_false:N \l__tblr_build_first_hline_bool
  \bool_set_false:N \l__tblr_build_last_hline_bool

```

```

\__tblr_build_one_table:nn {#2} {#3}
\ vbox_set:Nn \l__tblr_table_box
{
  \box_use:N \l__tblr_table_head_box
  \hrule height ~ Opt
  \box_use:N \l__tblr_row_head_box
  \hrule height ~ Opt
  \box_use:N \l__tblr_table_box
  \hrule height ~ Opt
  \box_use:N \l__tblr_row_foot_box
  \hrule height ~ Opt
  \box_use:N \l__tblr_table_foot_box
}
\__tblr_halign_whole:Nn \l__tblr_table_box #1
}
\cs_generate_variant:Nn \__tblr_build_page_table:nmm { nnx }

\cs_new_protected:Npn \__tblr_halign_whole:Nn #1 #2
{
  \noindent
  \hbox_to_wd:nn { \linewidth }
  {
    \tl_if_eq:nnF {#2} {l} { \hfil }
    \box_use:N #1
    \tl_if_eq:nnF {#2} {r} { \hfil }
  }
}

%% #1: table alignment
%% For short table, we need to leave vmode first
\cs_new_protected:Npn \__tblr_build_short_table:n #1
{
  \mode_leave_vertical:
  \__tblr_build_one_table:nn {1} {\c@rowcount}
  \__tblr_valign_whole:Nn \l__tblr_table_box #1
}
\cs_generate_variant:Nn \__tblr_build_short_table:n { e }

\bool_new:N \l__tblr_build_first_hline_bool
\bool_new:N \l__tblr_build_last_hline_bool
\bool_set_true:N \l__tblr_build_first_hline_bool
\bool_set_true:N \l__tblr_build_last_hline_bool

%% #1: row from; #2: row to
\cs_new_protected:Npn \__tblr_build_one_table:nn #1 #2
{
  \ vbox_set:Nn \l__tblr_table_box
  {
    \int_step_variable:nnNn {#1} {#2} \l__tblr_i_tl
    {
      \bool_lazy_or:nnT
      { \int_compare_p:nNn { \l__tblr_i_tl } > {#1} }
      { \bool_if_p:N \l__tblr_build_first_hline_bool }
      { \hbox:n { \__tblr_build_hline:V \l__tblr_i_tl } }
      \hrule height ~ Opt % remove lineskip between hlines and rows
      \hbox:n { \__tblr_build_row:N \l__tblr_i_tl }
      \hrule height ~ Opt
    }
  }
}

```

```

    }
    \bool_if:NT \l__tblr_build_last_hline_bool
    { \hbox:n { \__tblr_build_hline:n { \int_eval:n {#2 + 1} } } }
  }
  \bool_set_true:N \l__tblr_build_first_hline_bool
  \bool_set_true:N \l__tblr_build_last_hline_bool
}

%% #1: hline number
\cs_new_protected:Npn \__tblr_build_one_hline:n #1
{
  \vbox_set:Nn \l__tblr_table_box { \hbox:n { \__tblr_build_hline:n { #1 } } }
}

\tl_new:N \__tblr_vbox_align_tl
\tl_const:Nn \__tblr_vbox_t_tl {t}
\tl_const:Nn \__tblr_vbox_m_tl {m}
\tl_const:Nn \__tblr_vbox_c_tl {c}
\tl_const:Nn \__tblr_vbox_b_tl {b}

\cs_new_protected:Npn \__tblr_valign_whole:Nn #1 #2
{
  \group_begin:
  \tl_set:Nn \__tblr_vbox_align_tl {#2}
  \dim_set:Nn \l__tblr_t_dim { \box_ht:N #1 + \box_dp:N #1 }
  \tl_case:NnF \__tblr_vbox_align_tl
  {
    \__tblr_vbox_m_tl
    { \__tblr_valign_whole_middle:N #1 }
    \__tblr_vbox_c_tl
    { \__tblr_valign_whole_middle:N #1 }
    \__tblr_vbox_t_tl
    { \__tblr_valign_whole_top:N #1 }
    \__tblr_vbox_b_tl
    { \__tblr_valign_whole_bottom:N #1 }
  }
  { \__tblr_valign_whole_middle:N #1 }
  \group_end:
}

\cs_new_protected:Npn \__tblr_valign_whole_middle:N #1
{
  \hbox:n { $ \m@th \tex_vcenter:D { \vbox_unpack_drop:N #1 } $ }
}

\cs_new_protected:Npn \__tblr_valign_whole_top:N #1
{
  \tl_set:Nx \l__tblr_a_tl
  { \__tblr_spec_item:ne { hline } { [1] / @hline-height } }
  %% Note that \l__tblr_b_tl may be empty
  \tl_set:Nx \l__tblr_b_tl
  { \__tblr_prop_item:ne { inner } { baseline } }
  \bool_lazy_or:nnTF
  { \dim_compare_p:nNn { \l__tblr_a_tl } = { Opt } }
  { \int_compare_p:nNn { \l__tblr_b_tl + 0 } = { 1 } }
  {
    \dim_set:Nn \l__tblr_h_dim

```

```

    {
      \_tblr_data_item:nnn { row } {1} { abovesep }
      +
      ( \_tblr_data_item:nnn { row } {1} { @row-height }
      +
      \_tblr_data_item:nnn { row } {1} { @row-upper }
      -
      \_tblr_data_item:nnn { row } {1} { @row-lower }
      ) / 2
    }
    \dim_set:Nn \l__tblr_d_dim { \l__tblr_t_dim - \l__tblr_h_dim }
  }
  {
    \dim_set:Nn \l__tblr_h_dim { Opt }
    \dim_set_eq:NN \l__tblr_d_dim \l__tblr_t_dim
  }
  \box_set_ht:Nn #1 { \l__tblr_h_dim }
  \box_set_dp:Nn #1 { \l__tblr_d_dim }
  \box_use_drop:N #1
}

\cs_new_protected:Npn \_tblr_valign_whole_bottom:N #1
{
  \tl_set:Nx \l__tblr_a_tl
  {
    \_tblr_spec_item:ne { hline }
    { [\int_eval:n {\c@rowcount + 1}] / @hline-height }
  }
  %% Note that \l__tblr_b_tl may be empty
  \tl_set:Nx \l__tblr_b_tl
  { \_tblr_prop_item:ne { inner } { baseline } }
  \bool_lazy_or:nnTF
  { \dim_compare_p:nNn { \l__tblr_a_tl } = { Opt } }
  { \int_compare_p:nNn { \l__tblr_b_tl + 0 } = { \c@rowcount } }
  {
    \dim_set:Nn \l__tblr_d_dim
    {
      ( \_tblr_data_item:nen { row }
      { \int_use:N \c@rowcount } { @row-height }
      -
      \_tblr_data_item:nen { row }
      { \int_use:N \c@rowcount } { @row-upper }
      +
      \_tblr_data_item:nen { row }
      { \int_use:N \c@rowcount } { @row-lower }
      ) / 2
      +
      \_tblr_data_item:nnn { row } {1} { belowsep }
    }
    \dim_set:Nn \l__tblr_h_dim { \l__tblr_t_dim - \l__tblr_d_dim }
  }
  {
    \dim_set:Nn \l__tblr_d_dim { Opt }
    \dim_set_eq:NN \l__tblr_h_dim \l__tblr_t_dim
  }
  \box_set_ht:Nn #1 { \l__tblr_h_dim }
  \box_set_dp:Nn #1 { \l__tblr_d_dim }
  \box_use_drop:N #1
}

```

```

}

%%% -----
%%> \section{Build Table Components}
%%% -----

\dim_new:N \l__tblr_col_o_wd_dim
\dim_new:N \l__tblr_col_b_wd_dim

%% Build hline. #1: row number
\cs_new_protected:Npn \__tblr_build_hline:n #1
{
  \int_step_inline:nn { \c@colcount }
    { \__tblr_build_hline_segment:nn { #1 } { ##1 } }
}
\cs_generate_variant:Nn \__tblr_build_hline:n { x, V }

%% #1: row number, #2: column number
\cs_new_protected:Npn \__tblr_build_hline_segment:nn #1 #2
{
  \tl_set:Nx \l__tblr_n_tl
    { \__tblr_spec_item:ne { hline } { [#1] / @hline-count } }
  \tl_set:Nx \l__tblr_o_tl
    { \__tblr_spec_item:ne { hline } { [#1][#2] / omit } }
  \__tblr_get_col_outer_width_border_width:nNN {#2}
    \l__tblr_col_o_wd_dim \l__tblr_col_b_wd_dim
  \tl_if_empty:NTF \l__tblr_o_tl
    {
      \int_compare:nNnT { \l__tblr_n_tl } > {0}
        { \__tblr_build_hline_segment_real:nn {#1} {#2} }
    }
    { \__tblr_build_hline_segment_omit:nn {#1} {#2} }
}

%% #1: row number, #2: column number
\cs_new_protected:Npn \__tblr_build_hline_segment_omit:nn #1 #2
{
  \skip_horizontal:n { \l__tblr_col_o_wd_dim - \l__tblr_col_b_wd_dim }
}

%% #1: row number, #2: column number
\cs_new_protected:Npn \__tblr_build_hline_segment_real:nn #1 #2
{
  \tl_set:Nx \l__tblr_s_tl
    { \__tblr_prop_item:ne { inner } { rulesep } }
  \vbox_set:Nn \l__tblr_c_box
    {
      %% add an empty hbox to support vbox width
      \tex_hbox:D to \l__tblr_col_o_wd_dim {}
      \int_step_inline:nn { \l__tblr_n_tl }
        {
          \tl_set:Nx \l__tblr_h_tl
            { \__tblr_spec_item:ne { hline } { [#1](##1) / @hline-height } }
          \hrule height ~ 0pt % remove lineskip
          \hbox_set_to_wd:Nnn \l__tblr_b_box { \l__tblr_col_o_wd_dim }
            {

```

```

        \tl_set:Nx \l__tblr_f_tl
        { \__tblr_spec_item:ne { hline } { [#1][#2](##1) / fg } }
        \tl_if_empty:NF \l__tblr_f_tl { \color{\l__tblr_f_tl} }
        \__tblr_get_hline_segment_child:nnn {#1} {#2} {##1}
    }
    \box_set_ht:Nn \l__tblr_b_box { \l__tblr_h_tl }
    \box_set_dp:Nn \l__tblr_b_box { Opt }
    \box_use:N \l__tblr_b_box
    \skip_vertical:n { \l__tblr_s_tl }
}
\skip_vertical:n { - \l__tblr_s_tl }
}
\box_use:N \l__tblr_c_box
\skip_horizontal:n { - \l__tblr_col_b_wd_dim }
}

%% Read from table specifications and calculate the widths of row and border
%% column outer width = content width + colsep width + border width
%% #1: the column number, #2: outer width, #3: border width
\cs_new_protected:Npn \__tblr_get_col_outer_width_border_width:nNN #1 #2 #3
{
    \dim_set:Nn #3
    { \__tblr_spec_item:ne { vline } { [\int_eval:n {#1 + 1}] / @vline-width } }
    \dim_set:Nn #2
    {
        \__tblr_spec_item:ne { vline } { [#1] / @vline-width }
        +
        \__tblr_data_item:nen { column } {#1} { leftsep }
        +
        \__tblr_data_item:nen { column } {#1} { @col-width }
        +
        \__tblr_data_item:nen { column } {#1} { rightsep }
        +
        #3
    }
}

\dim_new:N \l__tblr_row_ht_dim
\dim_new:N \l__tblr_row_dp_dim
\dim_new:N \l__tblr_row_abovesep_dim
\dim_new:N \l__tblr_row_belowsep_dim

%% Build current row, #1: row number
\cs_new_protected:Npn \__tblr_build_row:N #1
{
    \int_set:Nn \c@rownum {#1}
    \__tblr_update_rowsep_registers:
    \__tblr_get_row_inner_height_depth:VNNNN #1
    \l__tblr_row_ht_dim \l__tblr_row_dp_dim
    \l__tblr_row_abovesep_dim \l__tblr_row_belowsep_dim
    \vrule width ~ Opt ~ height ~ \l__tblr_row_ht_dim ~ depth ~ \l__tblr_row_dp_dim
    \int_step_variable:nNn { \c@colcount } \l__tblr_j_tl
    {
        \__tblr_build_vline_segment:nn {#1} { \l__tblr_j_tl }
        \__tblr_build_cell:NN #1 \l__tblr_j_tl
    }
    \__tblr_build_vline_segment:nn {#1} { \int_eval:n { \c@colcount + 1 } }
}

```

```

}

%% Read from table specifications and calculate inner height/depth of the row
%% inner height = abovesep + above vspace + row upper
%% inner depth = row lower + below vspace + belowsep
%% #1: the row number; #2: resulting inner height; #3: resulting inner depth;
%% #4: resulting abovesep; #5: resulting belowsep.

\dim_new:N \l__row_upper_dim
\dim_new:N \l__row_lower_dim
\dim_new:N \l__row_vspace_dim

\cs_new_protected:Npn \__tblr_get_row_inner_height_depth:nNNNN #1 #2 #3 #4 #5
{
  \dim_set:Nn #4
    { \__tblr_data_item:nen { row } {#1} { abovesep } }
  \dim_set:Nn #5
    { \__tblr_data_item:nen { row } {#1} { belowsep } }
  \dim_set:Nn \l__row_upper_dim
    { \__tblr_data_item:nen { row } {#1} { @row-upper } }
  \dim_set:Nn \l__row_lower_dim
    { \__tblr_data_item:nen { row } {#1} { @row-lower } }
  \dim_set:Nn \l__row_vspace_dim
    {
      ( \__tblr_data_item:nen { row } {#1} { @row-height }
        - \l__row_upper_dim - \l__row_lower_dim ) / 2
    }
  \dim_set:Nn #2 { #4 + \l__row_vspace_dim + \l__row_upper_dim }
  \dim_set:Nn #3 { \l__row_lower_dim + \l__row_vspace_dim + #5 }
}
\cs_generate_variant:Nn \__tblr_get_row_inner_height_depth:nNNNN { V }

%% #1: row number, #2: column number
\cs_new_protected:Npn \__tblr_build_vline_segment:nn #1 #2
{
  \tl_set:Nx \l__tblr_n_tl
    { \__tblr_spec_item:ne { vline } { [#2] / @vline-count } }
  \tl_set:Nx \l__tblr_o_tl
    { \__tblr_spec_item:ne { vline } { [#1][#2] / omit } }
  \tl_if_empty:NTF \l__tblr_o_tl
  {
    \int_compare:nNnT { \l__tblr_n_tl } > {0}
    { \__tblr_build_vline_segment_real:nn {#1} {#2} }
  }
  { \__tblr_build_vline_segment_omit:nn {#1} {#2} }
}

%% #1: row number, #2: column number
\cs_new_protected:Npn \__tblr_build_vline_segment_omit:nn #1 #2
{
  \tl_set:Nx \l__tblr_w_tl
    { \__tblr_spec_item:ne { vline } { [#2] / @vline-width } }
  \skip_horizontal:N \l__tblr_w_tl
}

%% #1: row number, #2: column number

```

```

%% We make every vline segment intersect with first hline below
%% to remove gaps in vlines around multirow cells
\cs_new_protected:Npn \__tblr_build_vline_segment_real:nn #1 #2
{
  \tl_set:Nx \l__tblr_s_tl
  { \__tblr_prop_item:ne { inner } { rulesep } }
  \tl_set:Nx \l__tblr_b_tl
  {
    \__tblr_spec_item:ne { hline }
    { [\int_eval:n{#1 + 1}](1) / @hline-height }
  }
  \tl_if_empty:NT \l__tblr_b_tl { \tl_set:Nn \l__tblr_b_tl { Opt } }
  \hbox_set:Nn \l__tblr_a_box
  {
    \int_step_inline:nn { \l__tblr_n_tl }
    {
      \tl_set:Nx \l__tblr_w_tl
      { \__tblr_spec_item:ne { vline } { [#2](##1) / @vline-width } }
      \vbox_set_to_ht:Nnn \l__tblr_b_box
      { \dim_eval:n { \l__tblr_row_ht_dim + \l__tblr_row_dp_dim } }
      {
        \tl_set:Nx \l__tblr_f_tl
        { \__tblr_spec_item:ne { vline } { [#1][#2](##1) / fg } }
        \tl_if_empty:NF \l__tblr_f_tl { \color{\l__tblr_f_tl} }
        \__tblr_get_vline_segment_child:nnnx {#1} {#2} {##1}
        { \dim_eval:n { \l__tblr_row_ht_dim } }
        { \dim_eval:n { \l__tblr_row_dp_dim + \l__tblr_b_tl } }
        \skip_vertical:n { - \l__tblr_b_tl }
      }
      \box_set_wd:Nn \l__tblr_b_box { \l__tblr_w_tl }
      \box_use:N \l__tblr_b_box
      \skip_horizontal:n { \l__tblr_s_tl }
    }
    \skip_horizontal:n { - \l__tblr_s_tl }
  }
  \vbox_set:Nn \l__tblr_c_box { \box_use:N \l__tblr_a_box }
  \box_set_ht:Nn \l__tblr_c_box { \dim_use:N \l__tblr_row_ht_dim }
  \box_set_dp:Nn \l__tblr_c_box { \dim_use:N \l__tblr_row_dp_dim }
  \box_use:N \l__tblr_c_box
}

\__tblr_build_cell:nn

\tl_new:N \l__tblr_cell_rowspan_tl
\tl_new:N \l__tblr_cell_colspan_tl
\dim_new:N \l__tblr_cell_wd_dim
\dim_new:N \l__tblr_cell_ht_dim

\cs_new_protected:Npn \__tblr_build_cell:NN #1 #2
{
  \int_set:Nn \c@colnum {#2}
  \__tblr_update_colsep_registers:
  \group_begin:
  \tl_set:Nx \l__tblr_w_tl
  { \__tblr_data_item:nen { column } {#2} { @col-width } }
  \tl_set:Nx \l__tblr_h_tl
  { \__tblr_data_item:nen { row } {#1} { @row-height } }
  \tl_set:Nx \l__tblr_x_tl
  { \__tblr_data_item:nen { column } {#2} { leftsep } }
  \tl_set:Nx \l__tblr_y_tl

```

```

    { \_tblr_data_item:nen { column } {#2} { rightsep } }
\__tblr_data_item:nen { cell } {#1} {#2} { colspan } }
\__tblr_data_item:nen { cell } {#1} {#2} { colspan } }
\int_compare:nNnTF { \l__tblr_cell_colspan_tl } < {2}
{ \dim_set:Nn \l__tblr_cell_wd_dim { \l__tblr_w_tl } }
{
  \__tblr_get_span_horizontal_sizes:NNNNN #1 #2
  \l__tblr_o_dim \l__tblr_cell_wd_dim \l__tblr_q_dim
}
\__tblr_get_span_horizontal_sizes:NNNNN #1 #2
\l__tblr_o_dim \l__tblr_cell_wd_dim \l__tblr_q_dim
}
\__tblr_get_cell_alignments:nn {#1} {#2}
\__tblr_build_cell_background:NN #1 #2
\__tblr_build_cell_content:NN #1 #2
\group_end:
}

\cs_new_protected:Npn \__tblr_build_cell_content:NN #1 #2
{
  \hbox_set_to_wd:Nnn \l__tblr_a_box { \l__tblr_cell_wd_dim }
  {
    \tl_if_eq:NnF \g__tblr_cell_halign_tl {l} { \hfil }
    \__tblr_get_cell_text:nn {#1} {#2}
    \tl_if_eq:NnF \g__tblr_cell_halign_tl {r} { \hfil }
  }
  \vbox_set_to_ht:Nnn \l__tblr_b_box { \l__tblr_cell_ht_dim }
  {
    \tl_case:Nn \g__tblr_cell_valign_tl
    {
      \c__tblr_valign_m_tl
      {
        \vfil
        \int_compare:nNnT { \l__tblr_cell_rowspan_tl } < {2}
        {
          \box_set_ht:Nn \l__tblr_a_box
            { \_tblr_data_item:nen { row } {#1} { @row-upper } }
          \box_set_dp:Nn \l__tblr_a_box
            { \_tblr_data_item:nen { row } {#1} { @row-lower } }
        }
        \box_use:N \l__tblr_a_box
        \vfil
      }
      \c__tblr_valign_h_tl
      {
        \box_set_ht:Nn \l__tblr_a_box
          { \_tblr_data_item:nen { row } {#1} { @row-head } }
        \box_use:N \l__tblr_a_box
        \vfil
      }
      \c__tblr_valign_f_tl
      {
        \vfil
      }
    }
  }
}

```

```

\int_compare:nNnTF { \l__tblr_cell_rowspan_tl } < {2}
{
  \box_set_dp:Nn \l__tblr_a_box
  { \__tblr_data_item:nen { row } {#1} { @row-foot } }
}
{
  \box_set_dp:Nn \l__tblr_a_box
  {
    \__tblr_data_item:nen
    { row }
    { \int_eval:n { #1 + \l__tblr_cell_rowspan_tl - 1 } }
    { @row-foot }
  }
}
\box_use:N \l__tblr_a_box
}
}
\hrule height ~ Opt %% zero depth
}
\ vbox_set_to_ht:Nnn \l__tblr_c_box
{ \l__tblr_row_ht_dim - \l__tblr_row_avesep_dim }
{
  \box_use:N \l__tblr_b_box
  \vss
}
\skip_horizontal:n { \l__tblr_x_tl }
\box_use:N \l__tblr_c_box
\skip_horizontal:n { \l__tblr_y_tl - \l__tblr_cell_wd_dim + \l__tblr_w_tl }
}

\cs_new_protected:Npn \__tblr_build_cell_background:NN #1 #2
{
  \int_compare:nNnTF { \__tblr_data_item:neen { cell } {#1} {#2} { omit } } = {0}
  {
    \group_begin:
    \tl_set:Nx \l__tblr_b_tl
    { \__tblr_data_item:neen { cell } {#1} {#2} { background } }
    \tl_if_empty:NF \l__tblr_b_tl
    {
      \__tblr_get_cell_background_width:NNN #1 #2 \l_tmpa_dim
      \__tblr_get_cell_background_depth:NNN #1 #2 \l_tmpb_dim
      \__tblr_build_cell_background:nnnn
      { \dim_use:N \l_tmpa_dim }
      { \l__tblr_row_ht_dim }
      { \dim_use:N \l_tmpb_dim }
      { \l__tblr_b_tl }
    }
    \group_end:
  }
}

%% #1: row number; #2: column number; #3 resulting dimension
\cs_new_protected:Npn \__tblr_get_cell_background_width:NNN #1 #2 #3
{
  \int_compare:nNnTF { \l__tblr_cell_colspan_tl } < {2}
  { \dim_set:Nn #3 { \l__tblr_x_tl + \l__tblr_w_tl + \l__tblr_y_tl } }
  {
    \dim_set:Nn #3 { \l__tblr_o_dim + \l__tblr_cell_wd_dim + \l__tblr_q_dim }
  }
}

```

```

    }
}

%% #1: row number; #2: column number; #3 resulting dimension
\cs_new_protected:Npn \__tblr_get_cell_background_depth:NNN #1 #2 #3
{
  \int_compare:nNnTF { \l__tblr_cell_rowspan_tl } < {2}
  { \dim_set_eq:NN #3 \l__tblr_row_dp_dim }
  {
    \dim_set:Nn #3
    {
      \l__tblr_r_dim + \l__tblr_cell_ht_dim
      + \l__tblr_t_dim - \l__tblr_row_ht_dim
    }
  }
}

%% #1: width, #2: height, #3: depth, #4: color
\cs_new_protected:Npn \__tblr_build_cell_background:nnnn #1 #2 #3 #4
{
  \hbox_set:Nn \l__tblr_a_box
  {
    \color {#4}
    \vrule width ~ #1 ~ height ~ #2 ~ depth ~ #3
  }
  \box_set_dp:Nn \l__tblr_a_box { Opt }
  \box_use:N \l__tblr_a_box
  \skip_horizontal:n { - #1 }
}

%% #1: row number; #2: column number; #3: dimen register for rowsep above.
%% #4: dimen register for total height; #5: dimen register for rowsep below.
%% We can use \l__tblr_row_item_skip_size_prop which was made before
%% But when vspan=even, there are no itemskip in the prop list.
%% Therefore we need to calculate them from the sizes of items and skips
\cs_new_protected:Npn \__tblr_get_span_vertical_sizes:NNNNN #1 #2 #3 #4 #5
{
  \dim_set:Nn #3
  { \__tblr_data_item:nen { row } {#1} { abovesep } }
  \dim_zero:N #4
  \dim_add:Nn #4
  { \prop_item:Ne \l__tblr_row_item_skip_size_prop { item[#1] } }
  \int_step_inline:nnn { #1 + 1 } { #1 + \l__tblr_cell_rowspan_tl - 1 }
  {
    \dim_add:Nn #4
    {
      \prop_item:Ne \l__tblr_row_item_skip_size_prop { skip[##1] }
      +
      \prop_item:Ne \l__tblr_row_item_skip_size_prop { item[##1] }
    }
  }
  \dim_set:Nn #5
  {
    \__tblr_data_item:nen { row }
    { \int_eval:n { #1 + \l__tblr_cell_rowspan_tl - 1 } } { belowsep }
  }
  \t1_log:x { cell[#1][#2] ~::~ \dim_use:N #3, \dim_use:N #4, \dim_use:N #5 }
}

```

```

}

%% #1: row number; #2: column number; #3: dimen register for colsep left.
%% #4: dimen register for total width; #5: dimen register for colsep right.
%% We can use \l_tblr_col_item_skip_size_prop which was made before
%% But when hspan=even or hspan=minimal, there are no itemskip in the prop list.
%% Therefore we need to calculate them from the sizes of items and skips
\cs_new_protected:Npn \_tblr_get_span_horizontal_sizes:NNNNN #1 #2 #3 #4 #5
{
  \dim_set:Nn #3
    { \_tblr_data_item:nen { column } {#2} { leftsep } }
  \dim_zero:N #4
  \dim_add:Nn #4
    { \prop_item:Ne \l_tblr_col_item_skip_size_prop { item[#2] } }
  \int_step_inline:nnn { #2 + 1 } { #2 + \l_tblr_cell_colspan_tl - 1 }
  {
    \dim_add:Nn #4
      {
        \prop_item:Ne \l_tblr_col_item_skip_size_prop { skip[##1] }
        +
        \prop_item:Ne \l_tblr_col_item_skip_size_prop { item[##1] }
      }
  }
  \dim_set:Nn #5
  {
    \_tblr_data_item:nen { column }
    { \int_eval:n {#2 + \l_tblr_cell_colspan_tl - 1} } { rightsep }
  }
  %\tl_log:x { cell[#1][#2] ~::~ \dim_use:N #3, \dim_use:N #4, \dim_use:N #5 }
}

%%% -----
%% \section{Tracing Tabularray}
%%% -----

\NewDocumentCommand \SetTabularrayTracing { m }
{
  \keys_set:nn { tblr-set-tracing } {#1}
}
\cs_new_eq:NN \SetTblrTracing \SetTabularrayTracing

\bool_new:N \g__tblr_tracing_text_bool
\bool_new:N \g__tblr_tracing_command_bool
\bool_new:N \g__tblr_tracing_option_bool
\bool_new:N \g__tblr_tracing_theme_bool
\bool_new:N \g__tblr_tracing_outer_bool
\bool_new:N \g__tblr_tracing_inner_bool
\bool_new:N \g__tblr_tracing_column_bool
\bool_new:N \g__tblr_tracing_row_bool
\bool_new:N \g__tblr_tracing_cell_bool
\bool_new:N \g__tblr_tracing_vline_bool
\bool_new:N \g__tblr_tracing_hline_bool
\bool_new:N \g__tblr_tracing_colspec_bool
\bool_new:N \g__tblr_tracing_rowsec_bool
\bool_new:N \g__tblr_tracing_target_bool
\bool_new:N \g__tblr_tracing_cellspan_bool
\bool_new:N \g__tblr_tracing_intarray_bool

```

```

\bool_new:N \g__tblr_tracing_page_bool
\bool_new:N \g__tblr_tracing_step_bool

\bool_gset_true:N \g__tblr_tracing_step_bool

\keys_define:nn { tblr-set-tracing }
{
  +text .code:n = \bool_gset_true:N \g__tblr_tracing_text_bool,
  -text .code:n = \bool_gset_false:N \g__tblr_tracing_text_bool,
  +command .code:n = \bool_gset_true:N \g__tblr_tracing_command_bool,
  -command .code:n = \bool_gset_false:N \g__tblr_tracing_command_bool,
  +option .code:n = \bool_gset_true:N \g__tblr_tracing_option_bool,
  -option .code:n = \bool_gset_false:N \g__tblr_tracing_option_bool,
  +theme .code:n = \bool_gset_true:N \g__tblr_tracing_theme_bool,
  -theme .code:n = \bool_gset_false:N \g__tblr_tracing_theme_bool,
  +outer .code:n = \bool_gset_true:N \g__tblr_tracing_outer_bool,
  -outer .code:n = \bool_gset_false:N \g__tblr_tracing_outer_bool,
  +inner .code:n = \bool_gset_true:N \g__tblr_tracing_inner_bool,
  -inner .code:n = \bool_gset_false:N \g__tblr_tracing_inner_bool,
  +column .code:n = \bool_gset_true:N \g__tblr_tracing_column_bool,
  -column .code:n = \bool_gset_false:N \g__tblr_tracing_column_bool,
  +row .code:n = \bool_gset_true:N \g__tblr_tracing_row_bool,
  -row .code:n = \bool_gset_false:N \g__tblr_tracing_row_bool,
  +cell .code:n = \bool_gset_true:N \g__tblr_tracing_cell_bool,
  -cell .code:n = \bool_gset_false:N \g__tblr_tracing_cell_bool,
  +vline .code:n = \bool_gset_true:N \g__tblr_tracing_vline_bool,
  -vline .code:n = \bool_gset_false:N \g__tblr_tracing_vline_bool,
  +hline .code:n = \bool_gset_true:N \g__tblr_tracing_hline_bool,
  -hline .code:n = \bool_gset_false:N \g__tblr_tracing_hline_bool,
  +colspec .code:n = \bool_gset_true:N \g__tblr_tracing_colspec_bool,
  -colspec .code:n = \bool_gset_false:N \g__tblr_tracing_colspec_bool,
  +rowspec .code:n = \bool_gset_true:N \g__tblr_tracing_rowspec_bool,
  -rowspec .code:n = \bool_gset_false:N \g__tblr_tracing_rowspec_bool,
  +target .code:n = \bool_gset_true:N \g__tblr_tracing_target_bool,
  -target .code:n = \bool_gset_false:N \g__tblr_tracing_target_bool,
  +cellspan .code:n = \bool_gset_true:N \g__tblr_tracing_cellspan_bool,
  -cellspan .code:n = \bool_gset_false:N \g__tblr_tracing_cellspan_bool,
  +intarray .code:n = \bool_gset_true:N \g__tblr_tracing_intarray_bool,
  -intarray .code:n = \bool_gset_false:N \g__tblr_tracing_intarray_bool,
  +page .code:n = \bool_gset_true:N \g__tblr_tracing_page_bool,
  -page .code:n = \bool_gset_false:N \g__tblr_tracing_page_bool,
  +step .code:n = \bool_gset_true:N \g__tblr_tracing_step_bool,
  -step .code:n = \bool_gset_false:N \g__tblr_tracing_step_bool,
  all .code:n = \__tblr_enable_all_tracings:,
  none .code:n = \__tblr_disable_all_tracings:,
}

\cs_new_protected_nopar:Npn \__tblr_enable_all_tracings:
{
  \bool_gset_true:N \g__tblr_tracing_text_bool
  \bool_gset_true:N \g__tblr_tracing_command_bool
  \bool_gset_true:N \g__tblr_tracing_option_bool
  \bool_gset_true:N \g__tblr_tracing_theme_bool
  \bool_gset_true:N \g__tblr_tracing_outer_bool
  \bool_gset_true:N \g__tblr_tracing_inner_bool
  \bool_gset_true:N \g__tblr_tracing_column_bool
  \bool_gset_true:N \g__tblr_tracing_row_bool

```

```

\bool_gset_true:N \g__tblr_tracing_cell_bool
\bool_gset_true:N \g__tblr_tracing_vline_bool
\bool_gset_true:N \g__tblr_tracing_hline_bool
\bool_gset_true:N \g__tblr_tracing_colspec_bool
\bool_gset_true:N \g__tblr_tracing_rowspec_bool
\bool_gset_true:N \g__tblr_tracing_target_bool
\bool_gset_true:N \g__tblr_tracing_cellspan_bool
\bool_gset_true:N \g__tblr_tracing_intarray_bool
\bool_gset_true:N \g__tblr_tracing_page_bool
\bool_gset_true:N \g__tblr_tracing_step_bool
}

\cs_new_protected_nopar:Npn \__tblr_disable_all_tracings:
{
\bool_gset_false:N \g__tblr_tracing_text_bool
\bool_gset_false:N \g__tblr_tracing_command_bool
\bool_gset_false:N \g__tblr_tracing_option_bool
\bool_gset_false:N \g__tblr_tracing_theme_bool
\bool_gset_false:N \g__tblr_tracing_outer_bool
\bool_gset_false:N \g__tblr_tracing_inner_bool
\bool_gset_false:N \g__tblr_tracing_column_bool
\bool_gset_false:N \g__tblr_tracing_row_bool
\bool_gset_false:N \g__tblr_tracing_cell_bool
\bool_gset_false:N \g__tblr_tracing_vline_bool
\bool_gset_false:N \g__tblr_tracing_hline_bool
\bool_gset_false:N \g__tblr_tracing_colspec_bool
\bool_gset_false:N \g__tblr_tracing_rowspec_bool
\bool_gset_false:N \g__tblr_tracing_target_bool
\bool_gset_false:N \g__tblr_tracing_cellspan_bool
\bool_gset_false:N \g__tblr_tracing_intarray_bool
\bool_gset_false:N \g__tblr_tracing_page_bool
\bool_gset_false:N \g__tblr_tracing_step_bool
}

\NewDocumentCommand \LogTabularrayTracing { m }
{
\keys_set:nn { tblr-log-tracing } {#1}
}
\cs_new_eq:NN \LogTblrTracing \LogTabularrayTracing

\keys_define:nn { tblr-log-tracing }
{
step .code:n = \__tblr_log_tracing_step:n {#1},
unknown .code:n = \__tblr_log_tracing:N \l_keys_key_str
}

\cs_new_protected:Npn \__tblr_log_tracing:N #1
{
\bool_if:cT { g__tblr_tracing_ #1 _bool }
{ \cs:w __tblr_log_tracing_ #1 : \cs_end: }
}

\cs_new_protected:Npn \__tblr_log_tracing_text:
{
\__tblr_spec_log:n { text }
}

```

```
\cs_new_protected:Npn \__tblr_log_tracing_command:
{
  \__tblr_prop_log:n { command }
}

\cs_new_protected:Npn \__tblr_log_tracing_option:
{
  \__tblr_prop_log:n { note }
  \__tblr_prop_log:n { remark }
  \__tblr_prop_log:n { more }
}

\cs_new_protected:Npn \__tblr_log_tracing_theme:
{
  \__tblr_style_log:
}

\cs_new_protected:Npn \__tblr_log_tracing_outer:
{
  \__tblr_spec_log:n { outer }
}

\cs_new_protected:Npn \__tblr_log_tracing_inner:
{
  \__tblr_prop_log:n { inner }
}

\cs_new_protected:Npn \__tblr_log_tracing_column:
{
  \__tblr_data_log:n { column }
}

\cs_new_protected:Npn \__tblr_log_tracing_row:
{
  \__tblr_data_log:n { row }
}

\cs_new_protected:Npn \__tblr_log_tracing_cell:
{
  \__tblr_data_log:n { cell }
}

\cs_new_protected:Npn \__tblr_log_tracing_vline:
{
  \__tblr_spec_log:n { vline }
}

\cs_new_protected:Npn \__tblr_log_tracing_hline:
{
  \__tblr_spec_log:n { hline }
}

\cs_new_protected:Npn \__tblr_log_tracing_colspec:
{
  \tl_if_eq:NnT \g__tblr_column_or_row_tl { column }
}
```

```

    { \tl_log:N \g__tblr_expanded_colrow_spec_tl }
  }

\cs_new_protected:Npn \__tblr_log_tracing_rowspec:
{
  \tl_if_eq:NnT \g__tblr_column_or_row_tl { row }
  { \tl_log:N \g__tblr_expanded_colrow_spec_tl }
}

\cs_new_protected:Npn \__tblr_log_tracing_target:
{
  \dim_log:N \l__column_target_dim
  \prop_log:N \l__column_coefficient_prop
  \prop_log:N \l__column_natural_width_prop
  \prop_log:N \l__column_computed_width_prop
}

\cs_new_protected:Npn \__tblr_log_tracing_cellspan:
{
  \prop_log:N \l__tblr_col_item_skip_size_prop
  \prop_log:N \l__tblr_col_span_size_prop
  \prop_log:N \l__tblr_row_item_skip_size_prop
  \prop_log:N \l__tblr_row_span_size_prop
  \prop_log:N \l__tblr_row_span_to_row_prop
}

\cs_new_protected:Npn \__tblr_log_tracing_page:
{
  \dim_log:N \pagegoal
  \dim_log:N \pagetotal
}

\cs_new_protected:Npn \__tblr_log_tracing_step:n #1
{
  \bool_if:NT \g__tblr_tracing_step_bool { \tl_log:x {Step :~ #1} }
}

\cs_new_protected:Npn \__tblr_do_if_tracing:nn #1 #2
{
  \bool_if:cT { g__tblr_tracing_ #1 _bool } {#2}
}

%%% -----
%% \section{Tabularray Libraries}
%%% -----

%% \NewTblrLibrary and \UseTblrLibrary commands

\NewDocumentCommand \NewTblrLibrary { m m }
{
  \cs_new_protected:cpn { __tblr_use_lib_ #1: } {#2}
}

\NewDocumentCommand \UseTblrLibrary { m }
{

```

```

\clist_map_inline:nn {#1} { \use:c { __tblr_use_lib_ ##1: } }
}

%% Library booktabs and commands \toprule, \midrule, \bottomrule

\NewTblrLibrary { booktabs }
{
  \NewTableCommand \toprule [1] [] { \hline [0.08em, ##1] }
  \NewTableCommand \midrule [1] [] { \hline [0.05em, ##1] }
  \NewTableCommand \bottomrule [1] [] { \hline [0.08em, ##1] }
  \NewTableCommand \cmidrule [2] [] { \cline [0.03em, ##1] { ##2 } }
}

%% Library diagbox and command \diagbox

\NewTblrLibrary { diagbox }
{
  \RequirePackage{ diagbox }
  \cs_set_eq:NN \__tblr_lib_saved_diagbox:w \diagbox
  \NewContentCommand \diagbox [3] []
  {
    \__tblr_lib_diagbox_fix:n
    {
      \__tblr_lib_saved_diagbox:w
      [ leftsep=\leftsep, rightsep=\rightsep, ##1 ]
      { \__tblr_lib_diagbox_math_or_text:n {##2} }
      { \__tblr_lib_diagbox_math_or_text:n {##3} }
    }
  }
  \NewContentCommand \diagboxthree [4] []
  {
    \__tblr_lib_diagbox_fix:n
    {
      \__tblr_lib_saved_diagbox:w
      [ leftsep=\leftsep, rightsep=\rightsep, ##1 ]
      { \__tblr_lib_diagbox_math_or_text:n {##2} }
      { \__tblr_lib_diagbox_math_or_text:n {##3} }
      { \__tblr_lib_diagbox_math_or_text:n {##4} }
    }
  }
}

\cs_new_protected:Npn \__tblr_lib_diagbox_math_or_text:n #1
{
  \bool_if:NTF \l__tblr_math_mode_bool {$#1$} {#1}
}

\box_new:N \l__tblr_diag_box

\cs_new_protected:Npn \__tblr_lib_diagbox_fix:n #1
{
  \hbox_set:Nn \l__tblr_diag_box {#1}
  \box_set_ht:Nn \l__tblr_diag_box { \box_ht:N \l__tblr_diag_box - \abovesep }
  \box_set_dp:Nn \l__tblr_diag_box { \box_dp:N \l__tblr_diag_box - \belowsep }
  \box_use:N \l__tblr_diag_box
}

```

```

%% Library siunitx and S columns

\NewTblrLibrary { siunitx }
{
  \RequirePackage { siunitx }
  \NewColumnType { S } [1] [] { Q[si = {##1}] }
  \_tblr_data_new_key:nnn { cell } { si } { str }
  \keys_define:nn { tblr-column }
  {
    si .code:n = \_tblr_siunitx_setcolumn:n {##1}
  }
  \cs_new_protected:Npn \_tblr_siunitx_setcolumn:n ##1
  {
    \_tblr_column_gput_cell:nn { si } {##1}
    \_tblr_process_text_for_every_column_cell:n { \_tblr_siunitx_tablenum:n }
  }
  \cs_new_protected:Npn \_tblr_siunitx_tablenum:n ##1
  {
    \tl_if_head_is_group:nTF {##1}
    { ##1 }
    {
      \group_begin:
      \tl_set:Nx \l_tmpa_tl
      {
        \_tblr_data_item:neen { cell }
        { \int_use:N \c@rownum } { \int_use:N \c@colnum } { si }
      }
      \exp_args:NV \sisetup \l_tmpa_tl
      \tablenum {##1}
      \group_end:
    }
  }
}

\ExplSyntaxOff

```