

# More Titlepage Styles with Package `uni-titlepage`

Markus Kohm

v1.1 2022/08/05

## Abstract

Creation of title pages is something most authors should not have to do. But reality is not perfect, so a lot of authors have to do it. In 2009 KOMA started the title page project at <https://komascript.de/titlepage> to collect real title pages and implement them with a well defined interface. In 2021 the project has been moved to <https://github.com/komascript/uni-titlepage> and renamed.

Now, changing from one title page style to another would be very simple. Nevertheless implementation of a new title page style may be still difficult. But maybe the guys of the title page project would help you. Just ask!

## Contents

<b>1 Loading the Package</b>	<b>2</b>
<b>2 The Title Page Styles and their Options</b>	<b>2</b>
2.1 Style DHBW . . . . .	6
2.2 Style KOMAScript . . . . .	7
2.3 Style Markus-1 . . . . .	9
2.4 Style Markus-2 . . . . .	11
2.5 Style Spacer . . . . .	13
2.6 Style TU-DD . . . . .	15
2.7 Style TU-HH . . . . .	16
2.8 Style KIT . . . . .	17
2.9 Style JT-Aufsaetze . . . . .	18
2.10 Style JT-Geschichte . . . . .	19
2.11 Style JT-Typography . . . . .	20
2.12 Style WWUM . . . . .	21
2.13 Style UKoLa . . . . .	22
<b>3 Additonal Commands</b>	<b>23</b>
<b>4 Implementation</b>	<b>24</b>
4.1 The Installation Driver ‘ <code>uni-titlepage.ins</code> ’ . . . . .	24
4.2 The Package <code>scrbase</code> . . . . .	26
4.3 The <code>titlepage</code> Drivers . . . . .	38
4.4 The Examples and the Manual . . . . .	57

## 1 Loading the Package

You may load this package like all the other package, simply using:

```
\usepackage{uni-titlepage}
```

This package declares several options for title page manipulation. We will describe all those options in the following. Most of the options are package options as well, but some are style options only. You may use every package option already as optional argument of `\usepackage` and even of `\documentclass`. But in most cases it would be better to use them as optional argument of `\TitlePageStyle` or `\maketitle`. We show this way below.

## 2 The Title Page Styles and their Options

`TitlePageStyle` Several title page styles are supported. You may select a title page style using:

```
\TitlePageStyle[<option>=<value>,...]{<style>}.
```

The available styles are shown at the following sub-sections. Options may be every package option and every style option.

`maketitle` After loading a style you may generate title pages using:

```
\maketitle[<option>=<value>,...].
```

Again, you may use every package option and every style option as optional argument.

`TitleOption` Another way to set an option is to use either

`TitleOptions`

```
\TitleOption{<option>}{<value>}
```

or

```
\TitleOptions[<option>=<value>,...].
```

You can set every package option an every option of already loaded title page styles.

For every main option, that expects a string argument exists a corresponding command with the same name. So you may set, e.g., the title either using `\TitleOptions{title={This is the Title}}` or `\TitleOption{title}{This is the Title}` or `\maketitle[title={This is the Title}]` or `\TitlePageStyle [title={This is the Title}]{...}` or `\title{This is the Title}`. The most robust way is to use the command `\title` instead of the option at one of the other commands. If you use the option you may need to add `\protect` in front of some commands inside the option value. But note: This is not valid for alias options like `student`, because alias options do not have a corresponding command!

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
<b>advisor</b>	TU-DD, UKoLa	if your personal advisor differs from the advising professor, this is the name of the advisor
<b>author</b>	<i>every style</i>	the authors, with some styles (currently not with DHBW or UKoLa) you may separate multiple authors by \and
<b>chair</b>	TU-DD, KIT, WWUM, UKoLa	the chair or institute of the faculty of the university where you've made or presented your work
<b>company</b>	DHBW	some works are made not only at a university but in cooperation with a company; at Duale Hochschule Baden-Württemberg this is the default case
<b>course</b>	DHBW	the shortcut for your discipline or course
<b>date</b>	DHBW, KIT, KOMAScript, Markus-1, Markus-2, Spacer, TU-HH, TU-DD, JT-Typography, WWUM	the documents main date, this may be, e.g., the release date, the semester of a thesis or any other most valid date
<b>dedication</b>	KOMAScript, Markus-1, Markus-2, Spacer	sometimes it is nice to dedicate the work to someone, e.g., your wife, your children, your grandmother or your first love
<b>academicgrade</b>	DHBW, TU-HH, WUMM, UKoLa	the academic grade or degree you reach with the work
<b>discipline</b>	DHBW, TU-DD, WUMM	the discipline in which you've made your work or reach your academic grade
<b>duration</b>	DHBW	the processing time for your work
<b>faculty</b>	TU-DD, KIT, WUMM	the faculty of the university where you've made or presented your work
<b>homepage</b>	KIT	the www-address of the homepage

...

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
<code>mainlogo</code>	DHBW, KIT, UKoLa	a logo at the main title (currently used for the DHBW or the KIT logo at the default of <code>titlehead</code> and the main logo of style <code>UKoLa</code> )
<code>secondlogo</code>	UKoLa	a secondary logo
<code>matriculationnumber</code>	DHBW, TU-DD	if you were a student while you've made the work, this is your number
<code>oralexaminationdate</code>	TU-HH, WUMM	sometimes the date of the oral examination is not the main date but has to be shown too
<code>place</code>	DHBW, TU-HH, JT-Geschichte, JT-Typography, WUMM, UKoLa	the place, in general the city, where you've made the work or where the Duale Hochschule or the publisher resides
<code>professor</code>	TU-DD, WUMM	the name of the professor who advised you during your work
<code>publisher</code>	KOMAScript, Markus-1, Markus-2, Spacer, JT-Aufsaetze, JT-Geschichte, JT-Typography	most written works have a publisher
<code>referee</code>	DHBW, TU-HH, UKoLa	every academic work will be referred; with some styles (currently TU-HH, WWUM, UKoLa) multiple referees may be separated with \and
<code>science</code>	WWUM	kind of science, e.g., "Naturwissenschaften"
<code>student</code>	<i>see author</i>	alias option to <code>author</code>
<code>subject</code>	<i>every style</i>	the kind of work, there are special predefined subjects; if you use one of <code>bachelor</code> , <code>academicgrade</code> , <code>diploma</code> , <code>master</code> , <code>project</code> , <code>seminar</code> , or <code>studentresearch</code> a language dependend replacement will be done; to avoid this, you may set the value in parenthesis

...

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
<code>subtitle</code>	KOMAScript, Markus-1, Markus-2, Spacer, TU-HH	the sub-title of the document
<code>title</code>	<i>every style</i>	the main title of the document
<code>titlehead</code>	DHBW, KOMAScript, Markus-2, Spacer, KIT	page head over the main title of the document
<code>university</code>	DHBW, TU-DD, TU-HH, KIT, WWUM	the university where you've made or presented your work

**Note:** Depending on the used style some elements are mandatory. You will get an error message like

```
Package uni-titlepage Error: empty title element 'author'.
```

if such a mandatory element has not been set. In this case use either the option or the corresponding command to setup at least a dummy value, e.g.

```
\author{DON'T FORGET TO CHANGE THE AUTHOR}
```

before the corresponding `\maketitle`.

Let's have a look at the already defined title page styles. You should find an example L<sup>A</sup>T<sub>E</sub>X file for each of them at the documentation folder. If not, ask your distributor or administrator for those! But you may find the code of all examples in `docstrip` syntax even at [subsection 4.4](#) starting at [page 57](#). At the shown examples most variable contents have been made red.

## 2.1 Style DHBW

Josef Schmidbauer asked me for a title page usable for bachelor thesis at the “Duale Hochschulen Baden-Württemberg”. This is a only one title page style.

The page (in example `titlepage-DHBW.tex`)  
is:

1. main title page with `titlehead`,  
`mainlogo`, `title`, `subject`,  
`academicgrade`, `discipline`,  
`place`, `author`, `duration`,  
`matriculationnumber`, `course`,  
`company`, `referee`, `university`, and  
`date`.



Note: The upper right corner is the logo placeholder. If you'd download the logo from the DHBW homepage <http://www.dhbw.de> and save it with the name `DHBW_d_MOS_195x95_rgb_300.jpg` it would be used automatically. The logo file is also available from [https://de.wikipedia.org/wiki/Datei:DHBW\\_d\\_MOS\\_195x95\\_rgb\\_300.jpg](https://de.wikipedia.org/wiki/Datei:DHBW_d_MOS_195x95_rgb_300.jpg). This original logo has a large white border, so it would be much smaller than the red box at the example. The example file also contains comments for an optional company logo at the upper left corner.


## 2.2 Style KOMAScript

This is a style similar to the title pages of KOMA-Script classes.

The pages (in twoside example `titlepage-KOMAScript.tex`) are:

1. defined by `extratitle`, which is not a package option but a style option. You may set it using `\TitleOption` or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.
2. empty and only in twoside mode with `extratitle` used.
3. main title page with `titlehead`, `subject`, `title`, `subtitle`, `author`, `date`, `plublisher`. You may use `\thanks` at any of these.

	<p>Das ist ein Schmutztitel im Stil KOMAScript</p>
	<p>Den Kopfbereich kann man auf diese Weise füllen.  Eine Klassifizierung der Arbeit  <b>Titel im Stil KOMAScript</b> Untertitel  Einen Verlag kann man ebenfalls angeben</p>




4. only in twoside mode defined by `uppertitleback` and `lowertitleback`, which are not package options but style options. You may set them using `\TitleOption` or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.
5. optional post title with `dedication`.
6. empty and only in twoside mode with `dedication` used.


## 2.3 Style Markus-1

This is a style similar to the one of the title of the KOMA-Script book.

The pages (in twoside example `titlepage-Markus-1.tex`) are:

1. defined by `publisher`; may be omitted by `publisher={}`.
2. only in twoside mode with `publisher` defined by `author`.
3. main title page with `subject`, `title`, `subtitle`, and `date`.





Oberer Bereich der Rückseite des Haupttitels im Stil Markus-1.

Eine Widmung im Stil Markus-1




4. only in twoside mode defined by `uppertitleback` and `lowertitleback`, which are not package options but style options. You may set them using `\TitleOption` or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.
5. optional post title with `dedication`.
6. empty and only in twoside mode with `dedication` used.


## 2.4 Style Markus-2

This style is not a real live style, but similar styles are often used:

The pages (in twoside example `titlepage-Markus-2.tex`) are:


1. defined by `extratitle`.
2. empty and only in twoside mode with `extratitle` used.
3. main title page with `titlehead` placed at the page head (if this is to high, it might be put outside the page; if it is to deep, it might overwrite parts of the title), `rulewidth`, `rulesep` and `rulecolor` for the vertical rule (these aren't package options but style options), `subject`, `title`, `subtitle`, `author`, `date`, and `publisher`. Note: If you want to use option `rulecolor` you have to load a package, that defines `\color`, e.g., `color` or `xcolor`. Otherwise the color will be ignored.





Oberer Bereich der Rückseite des Haupttitels im Stil `Markus-2`.

Eine Widmung im Stil `Markus-2`



Unterer Bereich der Rückseite des Haupttitels im Stil `Markus-2`.

4. only in twoside mode defined by `uppertitleback` and `lowertitleback`, which are not package options but style options. You may set them using `\TitleOption` or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.
5. optional post title with `dedication`.
6. empty and only in twoside mode with `dedication` used.


## 2.5 Style Spacer

This style is a variant of style Markus-2 from subsection 2.4. It was asked by spacer2012 at the original titlepage project on <https://komascript.de/titlepage>. In difference to Markus-2 the title head will not be placed at the page head but at the body.

The pages (in twoside example `titlepage-Spacer.tex`) are:

1. defined by `extratitle`.
2. empty and only in twoside mode with `extratitle` used.
3. main title page with `titlehead` placed at the page head, `rulewidth`, `rulesep` and `rulecolor` for the vertical rule (these aren't package options but style options), `subject`, `title`, `subtitle`, `author`, `date`, and `publisher`. Note: If you want to use option `rulecolor` you have to load a package, that defines `\color`, e.g., `color` or `xcolor`. Otherwise the color will be ignored.

	<p>Das ist ein Schmutztitel im Stil Spacer</p>
	<p>Eine Klassifizierung der Arbeit Markus Kohm Titel im Stil Spacer Untertitel  Verlag</p>




4. only in twoside mode defined by `uppertitleback` and `lowertitleback`, which are not package options but style options. You may set them using `\TitleOption` or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.
5. optional post title with `dedication`.
6. empty and only in twoside mode with `dedication` used.

## 2.6 Style TU-DD

This style is used at the “Technische Universität Dresden”. I was asked for this several years ago. Only one title page is defined!

The page (in example `titlepage-TU-DD.tex`) is:

1. main title page with university, faculty, chair, professor, title, subject, author, discipline, matriculationnumber, advisor, place, and date.



But there is another variant. If option `blackborder` was set to true, a black border is put around the page:

The page (in example `titlepage-TU-DD.tex` with option `blackborder`) is:

1. main title page with university, faculty, chair, professor, title, subject, author, discipline, matriculationnumber, advisor, place, and date.



## 2.7 Style TU-HH

This style is used at the “Technische Universität Hamburg-Harburg”. I was asked for this several years ago. Only two title pages are defined!

The pages (in twoside example `titlepage-TU-HH.tex`) are:

1. main title page with `title`, `subtitle`, `university`, `academicgrade`, `subject`, `author`, `place`, and `date`. Some additional text depending on the selected language will be used also.

Vom Promotionsausschuss der  
Technischen Universität Hamburg-Harburg  
zur Erlangung des akademischen Grades  
Doktor der Naturwissenschaften (Dr. rer. nat.)  
genehmigte Dissertation

**Titel im Stil TU-HH**

von  
Vorname und Name

aus  
(Geburtsort)

(aktuelles Jahr)

2. only in twoside mode with `referee` and `oralexaminationdate`.

1. Gutachter: Name des ersten Gutachters  
2. Gutachter: Name des zweiten Gutachters

Datum der mündlichen Prüfung: 29. Februar 2009

The output of style TU-HH differs, if you use option `final`, which is a style option, not a package option. You may set it using `\TitleOption` or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.


## 2.8 Style KIT

This style is used at the “KIT – University of the State of Baden-Württemberg and National Research Center of the Helmholtz Association”. I’ve made this because of the ugly L<sup>A</sup>T<sub>E</sub>X class and template made by the KIT itself. Only one title page is defined!

The page (in example `titlepage-KIT.tex`) is:

1. main title page with `titlehead`, `mainlogo`, `title`, `subject`, `author`, `referee`, `advisor`, `university`, `duration`, and `homepage`. Some additional text depending on the selected language will be used also.

If `titlehead` is empty or unused left aligned `mainlogo` will be used. If `mainlogo` is empty or unused, and if you have a logo file `KITLogo_RGB.pdf`, this will be used. As an alternative also `2560px-Logo_KIT.svg.png`, `2000px-Logo_KIT.svg.png`, `1280px-Logo_KIT.svg.png`, `1024px-Logo_KIT.svg.png`, `1000px-Logo_KIT.svg.png`, `800px-Logo_KIT.svg.png`, `640px-Logo_KIT.svg.png`, or `500px-Logo_KIT.svg.png` from [https://de.wikipedia.org/wiki/Datei:Logo\\_KIT.svg](https://de.wikipedia.org/wiki/Datei:Logo_KIT.svg) would be auto-detected. Several other elements will be set to defaults too, if they are empty. So you don’t need to set all the elements, that has been set at the example file.




## 2.9 Style JT-Aufsaetze

The style is based on the front cover of “Jan Tschichold: Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie, Birkhäuser Verlag Basel, 1975, ISBN: 3-7643-1946-1”. I’ve made this, because the book is a major book of classic typography. It seems to be old fashioned and indeed it is. Note, that the front cover of a book an the main title of a book are not the same! Nevertheless, here I’ve made a main title from a front cover. Currently only one title page is defined, but you may also use `extratitle`, `uppertitleback`, and `lowertitleback`.

The `titlepage` page (in example `titlepage-JT-Aufsaetze.tex`) is:

1. main title page with `author`, `title`, `publisher`, `rulewidth`, `rulesep` for width of the horizontal rules and the distance between them and `rulecolor` for the color of the rules (these aren’t package options but style options).  
Note: If you want to use option `rulecolor` you have to load a package, that defines `\color`, e.g., `color` or `xcolor`. Otherwise the color will be ignored.




## 2.10 Style JT-Geschichte

The style is based on “Jan Tschichold: Geschichte der Schrift in Bildern; Holbein-Verlag, 1947”. This is another major book of classic typography. It seems to be old fashioned and indeed it is. Currently only one title page is defined, but you may also use `extratitle`, `uppertitleback`, and `lowertitleback`.

The title page (in example `titlepage-JT-Geschichte.tex`) is:

1. main title page with `author`, `title`, `publisher`, `place`, `rulewidth` and `rulesep` for width of the horizontal rules and the distance between them and `rulecolor` for the color of them (these aren't package options but style options). Note: If you want to use option `rulecolor` you have to load a package, that defines `\color`, e.g., `color` or `xcolor`. Otherwise the color will be ignored.

Note, that the default for `titlepagefont` prints everything but the `title` with ad-hoc letterspacing in upper-case letters if `\lsstyle` is available and without letterspacing but in small capitals otherwise. Changing the default of `titlepagefont` will also change this automatism.



## 2.11 Style JT-Typography

The style is based on “Jan Tschichold: The New Typography; University of California Press, Berkley and Los Angeles, California 1995”. This is the English translation of another major book of classic typography. Some things like missing letterspacing at the upper-case title seems to be wrong. Currently only one title page is defined, but you may also use `extratitle`, `uppertitleback`, and `lowertitleback`.

The title page (in example `titlepage-JT-Geschichte.tex`) is:

1. main title page with `author`, `title`, `subtitle`, `place`, `date`, `publisher`.



## 2.12 Style WWUM

Tobias Südkamp asked me for that title for the Westfälischen Wilhelms-Universität Münster. The `professor` is more likely the `chairman`. Female referees should be prefixed by [f]. You can omit the examination date defining an empty `\examinationdate`.

	<p>The pages (in example <code>tilepage-WWUM.tex</code>) are:</p> <ol style="list-style-type: none"><li>1. cover page with <code>author</code>, <code>title</code>, <code>\the\year</code></li><li>2. the backside of the cover page is empty if it exists</li><li>3. main title page with <code>chair</code>, <code>title</code>, <code>subject</code>, <code>academicgrade</code>, <code>sience</code>, <code>discipline</code>, <code>faculty</code></li><li>4. main title back side with <code>professor</code>, <code>referee</code>, <code>oralexaminationdate</code> (normally empty)</li></ol>
	<p>Experimentelle Physik</p> <p>Titel der Arbeit</p> <p>Inaugural-Dissertation zur Erlangung des Doktorgrades der Naturwissenschaften im Fachbereich Physik der Mathematisch-Naturwissenschaftlichen Fakultät der Westfälischen Wilhelms-Universität Münster</p> <p>vorgelegt von <b>Mein Name</b> aus <b>Geburtsort</b> -2022</p> <p>Dokan/Dekanin: <b>Klaus Naseschwarz</b> Erster Gutachter: <b>Peter Mustermann</b> Zweite Gutachterin: <b>Petra Musterfrau</b> Datum der mündlichen Prüfung: Tag der Promotion:</p>

## 2.13 Style UKoLa

In 2007 several students asked me for the title of the Universität Koblenz-Landau. At that time, I've made a package for the title they asked for. The package has been published at <https://komascript.de/unikoblenzlandau> only. In 2021, after I've published [uni-titlepage](#), it was time to implement this title also as a title style definition. Note, this is not an official style of the University Koblenz-Landau. Several referees can be separated by \and. Female referees should be prefixed by [f].

The page (in example `titlepage-UKoLa.tex`) is:

1. main title page with `mainlogo`, `secondlogo`, `title`, `subject`, `academicgrade`, `chair`, `discipline`, `place`, `author`, `referee`, and `date`.



Note: The upper left corner is the logo placeholder. If you'd download the logo from <http://www.uni-koblenz-landau.de/logo.png> and save it with the name `uni-koblenz-landau.png`, it would be used automatically.

### 3 Additonal Commands

\NowButAfterBeginDocument Command

```
\NowButAfterBeginDocument{\code}
```

is something like \AtBeginDocument, but if you call it somewhere after \begin{document} argument `\code` will be used immediately. This command is used inside some of the title page styles, because you may load them either at the preamble or even after \begin{document}, but some code should not be executed before \begin{document}.

**titlepage** (*env.*) In oposite to the **titlepage** environment of the standard classes,

```
\begin{titlepage}[options]  
...  
\end{titlepage}
```

knows some options. These are **pagestyle**=`<style>` and **pagenumber**=`<number>`. The first one changes the page style of the generated title page to the given `<style>`. If the option is not set, the default **empty** will be used. The second one sets the logical page number of the generated title page to the given `<number>` and sets the counter **pagenumber** to this value. If the option is not used, the value of counter **pagenumber** will be increased by one and the result is used for the logical page number.

**fullsizetitle** (*env.*) Using

```
\begin{fullsizetitle}[options]  
...  
\end{fullsizetitle}
```

is almost the same like above. But **fullsizetitle** removes the margins from the generated title page. Nevertheless if binding correction (aka binding offset) of package **typearea** or **geometry** could be recognized, it will not be removed. Some of the title page styles use this environment instead of **titlepage** inside \maketitle. With this the margins of the title page do not depend on the type area of the document.

\usetitleelement Command

```
\usetitleelement{\code}
```

gives the content of the corresponding title `<element>`. Each main `<element>` defined by the package may be used. Those are currently: **advisor**, **author**, **chair**, **company**, **course**, **date**, **dedication**, **academicgrade**, **discipline**, **duration**, **faculty**, **homepage**, **mainlogo**, **matriculationnumber**, **oralexaminationdate**, **place**, **professor**, **publisher**, **referee**, **subject**, **subtitle**, **title**, **titlehead**, and **university**. Note: **student** isn't a main `<element>`, because it's only an alias for **author**.

\usenonemptytitleelement Command

```
\usenonemptytitleelement{\code}
```

is a variant of \usetitleelement that not only reports an error for a not existing `<element>` but also for an empty `<element>`. It should be used to print mandatory elements.

## 4 Implementation

Note: To generate all files, developers and beta testers should simply use the source from <https://github.com/komascript/uni-titlepage> and call

```
l3build unpack  
l3build doc
```

The resulting documentation will be placed in the main folder. The unpacked style file are in `build/unpacked`, You can use

```
l3build install
```

to install them in `TEXMFHOME`. See the manual of `l3build` for more information.

As an alternative you can use the source distribution from CTAN and run:

```
tex uni-titlepage.dtx
```

The documentation is usually part of the source distribution at CTAN. Note, that all the generated `tex` files are example files. Do not copy them to the run-time files but the documentation folder!

### 4.1 The Installation Driver ‘`uni-titlepage.ins`’

First of all we produce `uni-titlepage.ins`, the installation driver. It starts very common with loading `docstrip`, preamble declaration and start of generation.

```
1 \def\batchfile{uni-titlepage.dtx}  
2 \input docstrip.tex  
3 \ifToplevel{  
4   \Msg{*****}  
5   \Msg{*}  
6   \Msg{* Steps of uni-titlepage generation:}  
7   \Msg{* ======}  
8   \Msg{*}  
9   \Msg{* - Generation of all needed files:}  
10  \keepsilent  
11  \askforoverwritefalse  
12 }  
13  
14 \preamble  
15 Copyright (c) 2009-2022 by Markus Kohm <komascript(at)gmx.info>  
16  
17 This file was generated from file(s) of uni-titlepage distribution.  
18  
19 -----  
20  
21 This work may be distributed and/or modified under the conditions of  
22 the LaTeX Project Public License, version 1.3c of the license.  
23 The latest version of this license is in  
24   http://www.latex-project.org/lppl.txt  
25 and version 1.3c or later is part of all distributions of LaTeX  
26 version 2005/12/01 or later.  
27  
28 This work has the LPPL maintenance status "maintained".  
29
```

```

30 The Current Maintainer and author of this work is Markus Kohm.
31
32 This file may only be distributed together with
33 the file ‘uni-titlepage.dtx’.
34 You may however distribute the file ‘uni-titlepage.dtx’ without this file.
35
36 \endpreamble
37
38 \generate{%

```

But while the dtx file is the ins file itself, we will never generate this file.

```

39 % \file{uni-titlepage.ins}{\from{uni-titlepage.dtx}{ins}}% not needed
40 \file{uni-titlepage.drv}{\from{uni-titlepage.dtx}{doc,manual}}%
41 \file{uni-titlepage.sty}{\from{uni-titlepage.dtx}{package}}%
42 \file{title-DHBW.def}{\from{uni-titlepage.dtx}{driver,DHBW}}%
43 \file{title-KOMAScript.def}{\from{uni-titlepage.dtx}{driver,KOMAScript}}%
44 \file{title-Markus-1.def}{\from{uni-titlepage.dtx}{driver,Markus,1}}%
45 \file{title-Markus-2.def}{\from{uni-titlepage.dtx}{driver,Markus,2}}%
46 \file{title-Spacer.def}{\from{uni-titlepage.dtx}{driver,Spacer}}%
47 \file{title-TU-DD.def}{\from{uni-titlepage.dtx}{driver,TU-DD}}%
48 \file{title-TU-HH.def}{\from{uni-titlepage.dtx}{driver,TU-HH}}%
49 \file{title-KIT.def}{\from{uni-titlepage.dtx}{driver,KIT}}%
50 \file{title-JT-Aufsaetze.def}{\from{uni-titlepage.dtx}{driver,JT-Aufsaetze}}%
51 \file{title-JT-Geschichte.def}{\from{uni-titlepage.dtx}{driver,JT-Geschichte}}%
52 \file{title-JT-Typography.def}{\from{uni-titlepage.dtx}{driver,JT-Typography}}%
53 \file{title-WWUM.def}{\from{uni-titlepage.dtx}{driver,WWUM}}%
54 \file{title-UKoLa.def}{\from{uni-titlepage.dtx}{driver,UKoLa}}%
55 \file{titlepage-DHBW.tex}{\from{uni-titlepage.dtx}{doc,example,DHBW}}%
56 \file{titlepage-KOMAScript.tex}{\from{uni-titlepage.dtx}{doc,example,KOMAScript}}%
57 \file{titlepage-Markus-1.tex}{\from{uni-titlepage.dtx}{doc,example,Markus,1}}%
58 \file{titlepage-Markus-2.tex}{\from{uni-titlepage.dtx}{doc,example,Markus,2}}%
59 \file{titlepage-Spacer.tex}{\from{uni-titlepage.dtx}{doc,example,Spacer}}%
60 \file{titlepage-TU-DD.tex}{\from{uni-titlepage.dtx}{doc,example,TU-DD}}%
61 \file{titlepage-TU-HH.tex}{\from{uni-titlepage.dtx}{doc,example,TU-HH}}%
62 \file{titlepage-KIT.tex}{\from{uni-titlepage.dtx}{doc,example,KIT}}%
63 \file{titlepage-JT-Aufsaetze.tex}{\from{uni-titlepage.dtx}{doc,example,JT-Aufsaetze}}%
64 \file{titlepage-JT-Geschichte.tex}{\from{uni-titlepage.dtx}{doc,example,JT-Geschichte}}%
65 \file{titlepage-JT-Typography.tex}{\from{uni-titlepage.dtx}{doc,example,JT-Typography}}%
66 \file{titlepage-WWUM.tex}{\from{uni-titlepage.dtx}{doc,example,WWUM}}%
67 \file{titlepage-UKoLa.tex}{\from{uni-titlepage.dtx}{doc,example,UKoLa}}%
68 \nopreamble\nopostamble
69 \file{README.md}{\from{uni-titlepage.dtx}{README}}%
70 }%
71
72 \ifTopLevel{%
73   \Msg{* \space\space done.}
74   \Msg{*}
75   \Msg{* You may install all the files now.}
76   \Msg{*}
77   \Msg{*****}
78 }

```

At docstrip run we like to finish the file know:

```
79 \csname endinput\endcsname
```

## 4.2 The Package `scrbase`

\TitleOptions We use the extended option handling of KOMA-Script, so we load package `scr-base` and declare a family, a member and a something like \KOMAoptions and \KOMAoption but for this package.

```

80 \RequirePackage{scrbase}[2014/12/03]
81 \DefineFamily{title}
82 \DefineFamilyMember{title}
83 \newcommand*\TitleOptions{\FamilyOptions{title}}
84 \newcommand*\TitleOption{\FamilyOption{title}}


pagenumber (opt.)
85 \newcounter{titlepage}\setcounter{titlepage}{\@ne}
86 \DefineFamilyKey{title}{pagenumber}{%
87   \setcounter{titlepage}{#1}\FamilyKeyStateProcessed
88 }

\titelpagestyle
pagestyle (opt.)
89 \providecommand*\titelpagestyle{}
90 \renewcommand*\titelpagestyle[empty]{%
91 \DefineFamilyKey{title}{pagestyle}{%
92   \renewcommand*\titelpagestyle[#1]\FamilyKeyStateProcessed
93 }}

\if@resonecol
94 \ifcsname @restonecolfalse\endcsname
95   \expandafter\@gobble
96 \else
97   \expandafter\@firstofone
98 \fi
99 {\newif\if@restonecol}

titlepage (env.)
100 \scr@ifundefinedorrelax{titlepage}{\def\titlepage{}{}}
101 \scr@ifundefinedorrelax{endtitlepage}{\def\endtitlepage{}{}}
102 \providecommand*\maketitle[1]{}{}


\inittitle Set of commands, that define a title style:
\makepretitle
103 \newcommand*\tp@undefinedtitle[1]{%
104   \PackageInfo{uni-titlepage}{leaving not defined #1-title page empty}%
105 }
\makemaintitle
106 \newcommand*\inittitle{}%
\makepretitleback
107 \newcommand*\makepretitle[1]{\tp@undefinedtitle{pre}}
\makemaintitleback
108 \newcommand*\makepretitleback{\tp@undefinedtitle{back of pre}}
\makeposttitle
109 \newcommand*\makemaintitle[1]{\tp@undefinedtitle{main}}
\makeposttitleback
110 \newcommand*\makemaintitleback{\tp@undefinedtitle{back of main}}
\exittitle
111 \newcommand*\makeposttitle[1]{\tp@undefinedtitle{post}}
\tp@undefinedtitle
112 \newcommand*\makeposttitleback{\tp@undefinedtitle{back of post}}
113 \newcommand*\exittitle{}%
```

`\inittitlestyle` Will be called before loading a title style:

```
114 \newcommand*{\inittitlestyle}{%
115   \renewenvironment{titlepage}[1] []{%
116     \TitleOptions{##1}%
117     \clearpage
118     \if@twocolumn
119       \o@restonecoltrue\onecolumn
120     \else
121       \o@restonecolfalse
122     \fi
123     \ifx\titlepagestyle\empty\else\thispagestyle{\titlepagestyle}\fi
124     \if@twoside% im einseitigen Satz ist mir alles egal
125       \ifodd\value{page}%
126         aktuelle Seite ist ungerade
127       \else
128         Current page number is odd ...
129       \fi
130     \else
131       ... wanted page number is even: put in empty page.
132       \null\newpage
133     \fi
134   \else
135     Current page number is even ...
136     \ifodd\value{titlepage}%
137       ... wanted page number is off: put in empty page.
138       \null\newpage % Leerseite
139     \fi
140   \setcounter{page}{\value{titlepage}}%
141   \ifx\titlepagestyle\empty\else\thispagestyle{\titlepagestyle}\fi
142 }{%
143   \renewcommand*{\maketitle}[1] []{%
144     \begin{group}
145       \TitleOptions{##1}%
146       \inittitle
147       \makepretitle\if@twoside\makepretitleback\fi
148       \makemaintitle\if@twoside\makemaintitleback\fi
149       \makeposttitle\if@twoside\makeposttitleback\fi
150       \exittitle
151     \endgroup
152   }%
153 }
```

```
154 \renewcommand*{\inittitle}{}%
155 \renewcommand*{\makepretitle}{\tp@undefinedtitle{pre}}%
156 \renewcommand*{\makepretitleback}{\tp@undefinedtitle{back of pre}}%
157 \renewcommand*{\makemaintitle}{\tp@undefinedtitle{main}}%
158 \renewcommand*{\makemaintitleback}{\tp@undefinedtitle{back of main}}%
159 \renewcommand*{\makeposttitle}{\tp@undefinedtitle{post}}%
```

```

160  \renewcommand*{\makeposttitleback}{\tp@undefinedtitle{back of post}}%
161  \renewcommand*{\exittitle}{}%
162 }
163 \inittitlestyle

\titulo New environment for full page titles (with respect to BCOR or Gm@bindingoffset
\fullsizetitle if defined)
164 \newsavebox\titulo
165 \newenvironment{fullsizetitle}[1][]{%
166   \TitleOptions{#1}%
167   \begin{lrbox}{\titulo}
168     \hsize\paperwidth
169     \scr@ifundefinedorrelax{ta@bcor}{%
170       \scr@ifundefinedorrelax{Gm@bindingoffset}{}{%
171         \advance\hsize-\Gm@bindingoffset}%
172     }{%
173       \advance\hsize-\ta@bcor
174       \scr@ifundefinedorrelax{Gm@bindingoffset}{}{%
175         \ifdim \Gm@bindingoffset=\ta@bcor\else
176           \PackageWarning{uni-titlepage}{Ignoring geometry's binding
177             correction.\MessageBreak
178             using typearea's binding correction.\MessageBreak
179             If you're using geometry and typearea,\MessageBreak
180             you should set both options to the same value,\MessageBreak
181             e.g. \string\KOMAoptions{BCOR=\the\ta@bcor}\MessageBreak
182             \space\space\space\space\space
183             \string\geometry{bindingoffset=\the\ta@bcor}\MessageBreak
184             to make uni-titlepage use this value}%
185       }%
186       \fi
187     }%
188   }%
189   \vsize\paperheight
190   \linewidth\hsize
191   \columnwidth\hsize
192   \textwidth\hsize
193   \textheight\vsize
194   \noindent\minipage{\hsize}%
195 }{%
196   \endminipage
197 \end{lrbox}
198 \begin{titlepage}%
199   \vspace*{-1in}\vskip-\topmargin\vskip-\headheight\vskip-\headsep
200   \vskip-\topskip
201   \raggedright
202   \leavevmode
203   \hskip-1in
204   \ifodd\c@page
205     \hskip-\oddsidemargin
206     \scr@ifundefinedorrelax{ta@bcor}{}{%
207       \scr@ifundefinedorrelax{Gm@bindingoffset}{}{%
208         \hskip\Gm@bindingoffset}%
209       }{\hskip\ta@bcor}%
210   \else

```

```

211      \hskip-\evensidemargin
212      \fi
213      \vbox to\z@{\hsize\z@
214          \vskip-\baselineskip
215          \makebox[0pt][l]{\usebox\titlebox}%
216          \vss
217      }%
218  \end{titlepage}
219 }

\DefineSimpleTitleKey Define title page “variables”:
\DefineReplaceTitleKey 220 \newcommand*{\tp@replacewarning}[2]{%
  \tp@replacewarning 221  \PackageWarning{uni-titlepage}{%
    \tp@dokeys 222    Using ‘#2’ instead of ‘#1’,\MessageBreak
    because ‘#1’ not defined%
  }%
  225 }
  226 \newcommand*{\tp@dokeys}{}%
  227 \newcommand*{\DefineSimpleTitleKey}[2][.\@currname.\@currext]{%
  228   \l@addto@macro\tp@dokeys{\do{#2}}%
  229   \expandafter\newcommand\expandafter*\csname @#2\endcsname{}%
  230   \expandafter\newcommand\expandafter*\csname #2\endcsname[1]{%
  231     \expandafter\gdef\csname @#2\endcsname{##1}%
  232     \DefineFamilyKey[{#1}]{title}{#2}{%
  233       \csname #2\endcsname{##1}%
  234       \FamilyKeyStateProcessed
  235     }%
  236 }
  237 \newcommand*{\DefineReplaceTitleKey}[3][.\@currname.\@currext]{%
  238   \DefineFamilyKey[{#1}]{title}{#2}{%
  239     \tp@replacewarning{#2}{#3}%
  240     \FamilyOptions{title}{#3=##1}%
  241   }%
  242 }

  \titlehead
  \@titlehead 243 \providecommand*{\@titlehead}{}%
titlehead (opt.) 244 \providecommand{\titlehead}[1]{\gdef\@titlehead{#1}}%
  245 \DefineFamilyKey{title}{titlehead}{\titlehead{#1}\FamilyKeyStateProcessed}

  \homepage
  \@homepage 246 \providecommand*{\@homepage}{}%
homepage (opt.) 247 \providecommand{\homepage}[1]{\gdef\@homepage{#1}}%
  248 \DefineFamilyKey{title}{homepage}{\homepage{#1}\FamilyKeyStateProcessed}

  \title
  \@title 249 \let\@title\relax\let\title\relax\DefineSimpleTitleKey{title}%
title (opt.) 

  \author
  \@author 250 \let\@author\relax\let\author\relax\DefineSimpleTitleKey{author}%
author (opt.)

```

```

\date
 \@date 251 \let\@date\relax\let\date\relax\DefineSimpleTitleKey{date}
 date (opt.)
\duration
 \@duration 252 \DefineSimpleTitleKey{duration}
 duration (opt.)
\course
 \@course 253 \DefineSimpleTitleKey{course}
 course (opt.)
\company
 \@company 254 \DefineSimpleTitleKey{company}
 company (opt.)
\subtitle
 \@subtitle 255 \let\@subtitle\relax\let\subtitle\relax\DefineSimpleTitleKey{subtitle}
 subtitle (opt.)
\university
 \@university 256 \DefineSimpleTitleKey{university}
 university (opt.)
\faculty
 \@faculty 257 \DefineSimpleTitleKey{faculty}
 faculty (opt.)
\chair
 \@chair 258 \DefineSimpleTitleKey{chair}
 chair (opt.)
\professor
 \@professor 259 \DefineSimpleTitleKey{professor}
 professor (opt.)
\subject
 \@subject 260 \providecommand*\{@subject}{}%
 subject (opt.) 261 \providecommand*\{@subject}[1]{\gdef\@subject{\#1}}%
 262 \l@addto@macro\tp@dokeys{\do{\subject}}%
 263 \DefineFamilyKey{title}{subject}{%
 264 \Ifstr{\#1}{project}{\subject{\projectpapername}}{%
 265 \Ifstr{\#1}{seminar}{\subject{\seminarpapername}}{%
 266 \Ifstr{\#1}{studentresearch}{\subject{\studentresearchname}}{%
 267 \Ifstr{\#1}{diploma}{\subject{\diplomathesisname}}{%
 268 \Ifstr{\#1}{degree}{\subject{\degreethesisname}}{%
 269 \Ifstr{\#1}{master}{\subject{\masterthesisname}}{%
 270 \Ifstr{\#1}{bachelor}{\subject{\bachelorthesisname}}{%
 271 \subject{\#1}}%
 272 }%
 273 }%
 274 }%
 275 }%
 276 }%
 277 }%
 278 }%
 279 \FamilyKeyStateProcessed
 280 }

```

```

\Ifstr For compatibility with old versions of scrbase the macro is provided based on
\ifstr if it has not been defined by scrbase.
281 \providecommand*\{Ifstr}{\ifstr}

student (opt.)
282 \DefineReplaceTitleKey{student}{author}

\sience
@science 283 \DefineSimpleTitleKey{sience}
sience (opt.)

\discipline
@discipline 284 \DefineSimpleTitleKey{discipline}
discipline (opt.)

\academicgrade
@academicgrade 285 \DefineSimpleTitleKey{academicgrade}
academicgrade (opt.)

\matriculationnumber
@matriculationnumber 286 \DefineSimpleTitleKey{matriculationnumber}
matriculationnumber (opt.)

\advisor
@advisor 287 \DefineSimpleTitleKey{advisor}
advisor (opt.)

\referee
@referee 288 \DefineSimpleTitleKey{referee}
referee (opt.)

\place
@place 289 \DefineSimpleTitleKey{place}
place (opt.)

\publisher
@publisher 290 \DefineSimpleTitleKey{publisher}
publisher (opt.) 291 \renewcommand*\{@publisher}{\csname @publishers\endcsname}

\mainlogo
@mainlogo 292 \DefineSimpleTitleKey{mainlogo}
mainlogo (opt.)

\secondlogo
@secondlogo 293 \DefineSimpleTitleKey{secondlogo}
secondlogo (opt.)

\oralexaminationdate
@oralexaminationdate 294 \DefineSimpleTitleKey{oralexaminationdate}
oralexaminationdate (opt.)

```

```

\dedication
@dedication 295 \providecommand*\{@dedication}{}%
dedication (opt.) 296 \providecommand{\dedication}[1]{\gdef\@dedication{#1}}%
297 \DefineFamilyKey{title}{dedication}{\dedication{#1}\FamilyKeyStateProcessed}

```

\usetitleelement Users cannot simply use, e.g., \@title, \mainlogo etc. So we need a command \usetitleelement@error to get them:

```

298 \newcommand*\usetitleelement[1]{%
299   \scr@ifundefinedorrelax{#1}{%
300     \usetitleelement@error{#1}%
301   }{%
302     \scr@ifundefinedorrelax{#1}{%
303       \usetitleelement@error{#1}%
304     }{%
305       \nameuse{#1}%
306     }%
307   }%
308 }
309 \newcommand*\@usetitleelement@error[1]{%
310   \PackageError{uni-titlepage}{‘#1’ isn’t a title element}{%
311     You should use \string\usetitleelement\space for title elements
312     only!\MessageBreak
313     If you’ll continue, command will be ignored.}%
314 }

```

\usenonemptytitleelement Sometimes we want to use a title element that must not be empty.

```

315 \newcommand*\usenonemptytitleelement[1]{%
316   \expandafter\ifx\csname @#1\endcsname\empty
317   \PackageError{uni-titlepage}{empty title element ‘#1’}{%
318     Title element ‘#1’ is empty but mandatory for the used title page
319     style.\MessageBreak
320     So it must not be empty.\MessageBreak
321     Please see the manual for more information about assigning
322     values to\MessageBreak
323     main title elements via options or commands.\MessageBreak
324     If you’ll continue, a \string\strut\space will be used.}%
325   \strut
326 \else
327   \usetitleelement{#1}%
328 \fi
329 }

```

Some variables use their own configurable font:

```

titlepagefont (opt.)
@titlepagefont 330 \scr@ifundefinedorrelax{\newkomafont}{%
331   \newcommand*\@titlepagefont{}%
332 }{%
333   \newkomafont{titlepage}{}%
334 }
335 \DefineFamilyKey{title}{titlepagefont}{%
336   \renewcommand*\@titlepagefont{#1}%
}

```

```

337   \FamilyKeyStateProcessed
338 }

subjectfont (opt.)
  \subject@font 339 \providecommand*\{\subject@font\}{\bfseries}
  340 \DefineFamilyKey{title}{subjectfont}{%
  341   \renewcommand*\{\subject@font\}{#1}%
  342   \FamilyKeyStateProcessed
  343 }

titlefont (opt.)
  \title@font 344 \providecommand*\{\titlefont\}{\bfseries}
  345 \DefineFamilyKey{title}{titlefont}{%
  346   \renewcommand*\{\titlefont\}{#1}%
  347   \FamilyKeyStateProcessed
  348 }

subtitlefont (opt.)
  \@subtitlefont 349 \providecommand*\{@subtitlefont\}{\bfseries}
  350 \DefineFamilyKey{title}{subtitlefont}{%
  351   \renewcommand*\{@subtitlefont\}{#1}%
  352   \FamilyKeyStateProcessed
  353 }

\TitlePageStyle Load a title page style from file
  354 \newcommand*\{\TitlePageStyle\}[2] [] {%
  355   \IfFileExists{title-#2.def}{%
  356     \begingroup
  357       \edef@\tempa{\endgroup
  358         \noexpand\inittitlestyle
  359         \noexpand\makeatletter
  360         \noexpand\input{title-#2.def}%
  361         \noexpand\catcode`\noexpand\@=\the\catcode`@
  362       }%
  363     \@tempa
  364     \TitleOptions{#1}%
  365   }{%
  366     \PackageError{uni-titlepage}{No title definition for '#2' found}{%
  367       You've tried to set title page style '#2', but no title page
  368       style definition file\MessageBreak
  369       'title-#2.def' may be found%
  370     }%
  371   }
  372 }

\NowButAfterBeginDocument Nice shortcut:
  373 \newcommand*\{\NowButAfterBeginDocument\}{%
  374   \if@atdocument
  375     \expandafter\@firstofone
  376   \else
  377     \expandafter\AtBeginDocument
  378   \fi
  379 }

```

```

380 \DeclareOption*{\expandafter\TitlePageStyle\expandafter{\CurrentOption}}
381 \FamilyProcessOptions*\relax

\chairmannname Language dependent terms:
\projectpapername 382 \providecommand*{\chairmannname}{Chairman}
\seminarpapername 383 \providecommand*{\projectpapername}{Project Paper}
\studentreserchname 384 \providecommand*{\seminarpapername}{Seminar Paper}
\diplomathesisname 385 \providecommand*{\studentresearchname}{Student Research Project}
\degreethesisname 386 \providecommand*{\diplomathesisname}{Diploma Thesis}
\masterthesisname 387 \providecommand*{\degreethesisname}{Degree Thesis}
\bachelorthesisname 388 \providecommand*{\masterthesisname}{Master Thesis}
\presentedbyname 389 \providecommand*{\bachelorthesisname}{Bachelor Thesis}
\advisorname 390 \providecommand*{\presentedbyname}{presented by}
\thename 391 \providecommand*{\advisorname}{Advisor}
\ofthename 392 \providecommand*{\thename}{}
\fromname 393 \providecommand*{\ofthename}{of the}
\fromplacename 394 \providecommand*{\fromname}{from}
\malereferee 395 \providecommand*{\fromplacename}{from}
\malereferee 396 \providecommand*{\referee}{Referee}
\femalereferee 397 \providecommand*{\malereferee}{\referee}
\femalereferee 398 \providecommand*{\femalereferee}{\referee}
\ordinalmalereferee 399 \providecommand*{\femalereferee}{\englishordinalmalereferee}
\ordinalfemalereferee 400 \providecommand*{\ordinalmalereferee}{\englishordinalfemalereferee}
\oralexaminationdate 401 \providecommand*{\oralexaminationdate}{Date of Oral Examination}
\ordinal 402 \providecommand*{\atthename}{at}
\maleordinal 403 \providecommand*{\durationname}{Processing Time}
\femaleordinal 404 \providecommand*{\matriculationnumbername}{Matriculationnumber}
\indatename 405 \providecommand*{\coursename}{Course}
\indatename 406 \providecommand*{\companyname}{Training Company}
\indatename 407 \providecommand*{\examinationname}{Examination}
\indatename 408 \providecommand*{\examinationdate}{Date of Examination}
\newcommand*{\ordinal}{\englishordinal}
\newcommand*{\femaleordinal}{\ordinal}
\newcommand*{\maleordinal}{\ordinal}
\indatename 412 \providecommand*{\indatename}{in}
\providecaptionname{american,australian,british,canadian,%
413 english,newzealand,UKEnglish,USenglish}{\chairmannname}{Chairmain}%
\providecaptionname{american,australian,british,canadian,%
414 english,newzealand,UKEnglish,USenglish}{\projectpapername}{Project Paper}%
\providecaptionname{american,australian,british,canadian,%
415 english,newzealand,UKEnglish,USenglish}{\seminarpapername}{Seminar Paper}%
\providecaptionname{american,australian,british,canadian,%
416 english,newzealand,UKEnglish,USenglish}{\studentresearchname}{Student
417 Research Project}%
\providecaptionname{american,australian,british,canadian,%
418 english,newzealand,UKEnglish,USenglish}{\diplomathesisname}{Diploma Thesis}%
\providecaptionname{american,australian,british,canadian,%
419 english,newzealand,UKEnglish,USenglish}{\degreethesisname}{Degree Thesis}%
\providecaptionname{american,australian,british,canadian,%
420 english,newzealand,UKEnglish,USenglish}{\masterthesisname}{Master Thesis}%
\providecaptionname{american,australian,british,canadian,%
421 english,newzealand,UKEnglish,USenglish}{\bachelorthesisname}{Bachelor
422 Thesis}%
\providecaptionname{american,australian,british,canadian,%
423 english,newzealand,UKEnglish,USenglish}{\diplomathesisname}{Diploma Thesis}%
\providecaptionname{american,australian,british,canadian,%
424 english,newzealand,UKEnglish,USenglish}{\degreethesisname}{Degree Thesis}%
\providecaptionname{american,australian,british,canadian,%
425 english,newzealand,UKEnglish,USenglish}{\masterthesisname}{Master Thesis}%
\providecaptionname{american,australian,british,canadian,%
426 english,newzealand,UKEnglish,USenglish}{\bachelorthesisname}{Bachelor
427 Thesis}%
\providecaptionname{american,australian,british,canadian,%
428 english,newzealand,UKEnglish,USenglish}{\bachelorthesisname}{Bachelor
429 Thesis}%
\providecaptionname{american,australian,british,canadian,%
430 english,newzealand,UKEnglish,USenglish}{\bachelorthesisname}{Bachelor
431 Thesis}%

```

```

432 english,newzealand,UKEnglish,USEnglish}{\ordinal}{\englishordinal}%
433 \providecaptionname{american,australian,british,canadian,%
434 english,newzealand,UKEnglish,USEnglish}{\presentedbyname}{presented by}%
435 \providecaptionname{american,australian,british,canadian,%
436 english,newzealand,UKEnglish,USEnglish}{\advisorname}{Advisor}%
437 \providecaptionname{american,australian,british,canadian,%
438 english,newzealand,UKEnglish,USEnglish}{\thename}{}%
439 \providecaptionname{american,australian,british,canadian,%
440 english,newzealand,UKEnglish,USEnglish}{\ofthename}{of the}%
441 \providecaptionname{american,australian,british,canadian,%
442 english,newzealand,UKEnglish,USEnglish}{\fromname}{from}%
443 \providecaptionname{american,australian,british,canadian,%
444 english,newzealand,UKEnglish,USEnglish}{\fromplacename}{from}%
445 \providecaptionname{american,australian,british,canadian,%
446 english,newzealand,UKEnglish,USEnglish}{\refereename}{Referee}%
447 \providecaptionname{american,australian,british,canadian,%
448 english,newzealand,UKEnglish,USEnglish}{\ordinalmalerefereename}{%
449 \englishordinalmalerefereename}%
450 \providecaptionname{american,australian,british,canadian,%
451 english,newzealand,UKEnglish,USEnglish}{\ordinalfemalerefereename}{%
452 \englishordinalfemalerefereename}%
453 \providecaptionname{american,australian,british,canadian,%
454 english,newzealand,UKEnglish,USEnglish}{\oralexaminationdatename}{Date of
455 Oral Examination}%
456 \providecaptionname{american,australian,british,canadian,%
457 english,newzealand,UKEnglish,USEnglish}{\durationname}{Processing Time}%
458 \providecaptionname{american,australian,british,canadian,%
459 english,newzealand,UKEnglish,USEnglish}{\matriculationnumbername}{Matriculationnumber}%
460 \providecaptionname{american,australian,british,canadian,%
461 english,newzealand,UKEnglish,USEnglish}{\coursename}{Course}%
462 \providecaptionname{american,australian,british,canadian,%
463 english,newzealand,UKEnglish,USEnglish}{\companyname}{Training Company}%
464 \providecaptionname{american,australian,british,canadian,%
465 english,newzealand,UKEnglish,USEnglish}{\examinationname}{Examination}%
466 \providecaptionname{american,australian,british,canadian,%
467 english,newzealand,UKEnglish,USEnglish}{\examinationdatename}{Date of
468 Examination}%
469 \providecaptionname{american,australian,british,canadian,%
470 english,newzealand,UKEnglish,USEnglish}{\indatename}{in}%
471 \providecaptionname{german,ngerman,austrian,naustrian,%
472 swissgerman,nswissgerman}{\chairmanname}{Dekan/Dekanin}%
473 \providecaptionname{german,ngerman,austrian,naustrian,%
474 swissgerman,nswissgerman}{\projectpapername}{Projektarbeit}%
475 \providecaptionname{german,ngerman,austrian,naustrian,%
476 swissgerman,nswissgerman}{\seminarpapername}{Seminararbeit}%
477 \providecaptionname{german,ngerman,austrian,naustrian,%
478 swissgerman,nswissgerman}{\studentresearchname}{Studienarbeit}%
479 \providecaptionname{german,ngerman,austrian,naustrian,%
480 swissgerman,nswissgerman}{\diplomathesisname}{Diplomarbeit}%
481 \providecaptionname{german,ngerman,austrian,naustrian,%
482 swissgerman,nswissgerman}{\degreethesisname}{Dissertation}%
483 \providecaptionname{german,ngerman,austrian,naustrian,%
484 swissgerman,nswissgerman}{\masterthesisname}{Master-Arbeit}%
485 \providecaptionname{german,ngerman,austrian,naustrian,%

```

```

486 swissgerman,nswissgerman}{\bachelorthesisname}{Bachelor-Arbeit}%
487 \providecaptionname{german,ngerman,austrian,naustrian,%
488 swissgerman,nswissgerman}{\ordinal}{\germanordinal}%
489 \providecaptionname{german,ngerman,austrian,naustrian,%
490 swissgerman,nswissgerman}{\femaleordinal}{\germanfemaleordinal}%
491 \providecaptionname{german,ngerman,austrian,naustrian,%
492 swissgerman,nswissgerman}{\maleordinal}{\germanmaleordinal}%
493 \providecaptionname{german,ngerman,austrian,naustrian,%
494 swissgerman,nswissgerman}{\presentedbyname}{eingereicht von}%
495 \providecaptionname{german,ngerman,austrian,naustrian,%
496 swissgerman,nswissgerman}{\advisorname}{Betreuer}%
497 \providecaptionname{german,ngerman,austrian,naustrian,%
498 swissgerman,nswissgerman}{\thename}{den}%
499 \providecaptionname{german,ngerman,austrian,naustrian,%
500 swissgerman,nswissgerman}{\ofthename}{der}%
501 \providecaptionname{german,ngerman,austrian,naustrian,%
502 swissgerman,nswissgerman}{\fromname}{von}%
503 \providecaptionname{german,ngerman,austrian,naustrian,%
504 swissgerman,nswissgerman}{\fromplacename}{aus}%
505 \providecaptionname{german,ngerman,austrian,naustrian,%
506 swissgerman,nswissgerman}{\refereename}{Gutachter}%
507 \providecaptionname{german,ngerman,austrian,naustrian,%
508 swissgerman,nswissgerman}{\ordinalmalerefereename}{%
509 \germanordinalmalerefereename}%
510 \providecaptionname{german,ngerman,austrian,naustrian,%
511 swissgerman,nswissgerman}{\ordinalfemalerefereename}{%
512 \germanordinalfemalerefereename}%
513 \providecaptionname{german,ngerman,austrian,naustrian,%
514 swissgerman,nswissgerman}{\femalerefereename}{Gutachterin}%
515 \providecaptionname{german,ngerman,austrian,naustrian,%
516 swissgerman,nswissgerman}{\oralexaminationdatename}{Datum der m\"undlichen
517 Pr\"ufung}%
518 \providecaptionname{german,ngerman,austrian,naustrian,%
519 swissgerman,nswissgerman}{\durationname}{Bearbeitungszeitraum}%
520 \providecaptionname{german,ngerman,austrian,naustrian,%
521 swissgerman,nswissgerman}{\matriculationnumbername}{Matrikelnummer}%
522 \providecaptionname{german,ngerman,austrian,naustrian,%
523 swissgerman,nswissgerman}{\coursename}{Kurs}%
524 \providecaptionname{german,ngerman,austrian,naustrian,%
525 swissgerman,nswissgerman}{\companynamen}{Ausbildungsfirma}%
526 \providecaptionname{german,ngerman,austrian,naustrian,%
527 swissgerman,nswissgerman}{\examinationname}{Pr\"ufung}%
528 \providecaptionname{german,ngerman,austrian,naustrian,%
529 swissgerman,nswissgerman}{\examinationdatename}{Tag der Pr\"ufung}%
530 \providecaptionname{german,ngerman,austrian,naustrian,%
531 swissgerman,nswissgerman}{\indatename}{im}}%
\englishordinalmalerefereename
532 \newcommand*\englishordinalmalerefereename[1]{%
533 \englishordinal{\#1} \refereename%
534 }
\englishordinalfemalerefereename

```

```

535 \newcommand*{\englishordinalfemalerefereename}[1]{%
536   \englishordinalmalerefereename{#1}%
537 }

\germanordinalmalerefereename
538 \newcommand*{\germanordinalmalerefereename}[1]{%
539   \ifnum #1<\@ne
540     \PackageError{uni-titlepage}{Ordinal of ‘#1’ not defined}{%
541       This package does only define German ordinal names for referees from 1}%
542   \else
543     \ifcase #1\or Erstgutachter\or Zweitgutachter\or Drittgutachter%
544     \or Viertgutachter\else
545       \PackageError{uni-titlepage}{Ordinal of ‘#1’ not defined}{%
546         This package does only define German ordinal names for referees up
547         to 4}%
548     \fi
549   \fi
550 }

germanordinalfemalerefereename
551 \newcommand*{\germanordinalfemalerefereename}[1]{%
552   \germanordinalfemalerefereename{#1}in%
553 }

germanordinalmalecorrectorname
554 \newcommand*{\germanordinalmalecorrectorname}[1]{%
555   \ifnum #1<\@ne
556     \PackageError{uni-titlepage}{Ordinal of ‘#1’ not defined}{%
557       This package does only define German ordinal names for correctors from 1}%
558   \else
559     \ifcase #1\or Erstkorrektor\or Zweitkorrektor\or Drittkorrektor%
560     \or Viertkorrektor\else
561       \PackageError{uni-titlepage}{Ordinal of ‘#1’ not defined}{%
562         This package does only define German ordinal names for correctors up
563         to 6}%
564     \fi
565   \fi
566 }

rmanordinalfemalecorrectorname
567 \newcommand*{\germanordinalfemalecorrectorname}[1]{%
568   \germanordinalmalecorrectorname{#1}in%
569 }

\englishordinal
570 \newcommand*{\englishordinal}[1]{%
571   \ifcsname engordnumber\endcsname
572     \engordnumber{#1}%
573   \else
574     \ifnum #1<\@ne

```

```

575     \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
576         This package does only define English ordinals from 1}%
577     \else
578         \ifcase #1\or 1st\or 2nd\or 3rd\or 4th\or 5th\or 6th\or 7th\or 8th\or
579             9th\or 10th\else
580             \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
581                 This package does only define English ordinals from 1 to
582                 10.\MessageBreak
583                 You may load package 'engord' to improve support of english
584                 ordinals}%
585         \fi
586     \fi
587 \fi
588 }

\germanordinal
\germanmaleordinal 589 \newcommand*{\germanordinal}[1]{%
\germanfemaleordinal 590   \ifnum #1<\@ne
591     \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
592         This package does only define german ordinals from 1}%
593     \else
594         #1.%\fi
595     \fi
596 }
597 \newcommand*{\germanmaleordinal}[1]{%
598   \ifcase #1
599     \PackageError{uni-titlepage}{Male ordinal of '#1' not defined}{%
600         This package does only define german male ordinals from 1}%
601     \or Erster\or Zweiter\or Dritter\or Vierter\or F\"unfter\or Sechster\%
602     \or Siebter\or Achter\or Neunter\or Zehnter\else
603     \PackageError{uni-titlepage}{Male ordinal of '#1' not defined}{%
604         This package does only define german male ordinals up to 10}%
605   \fi
606 }
607 \newcommand*{\germanfemaleordinal}[1]{%
608   \ifcase #1
609     \PackageError{uni-titlepage}{Female ordinal of '#1' not defined}{%
610         This package does only define german female ordinals from 1}%
611     \or Erste\or Zweite\or Dritte\or Vierte\or F\"unfte\or Sechste\%
612     \or Siebte\or Achte\or Neunte\or Zehnte\else
613     \PackageError{uni-titlepage}{Female ordinal of '#1' not defined}{%
614         This package does only define german female ordinals up to 10}%
615   \fi
616 }

```

### 4.3 The titlepage Drivers

```

617 \begingroup
618   \def\PackageNotLoadedError#1{%
619     \GenericError{%
620       (#1)\@spaces\@spaces\@spaces\@spaces
621     }{%
622       File '#1' Error: package 'uni-titlepage' hasn't been loaded%

```

```

623     }{%
624     This definition file was made to be loaded by package
625     ‘uni-titlepage’.\MessageBreak
626     You may not use it without package ‘uni-titlepage’!\MessageBreak
627     See the documentation of package ‘uni-titlepage’ for explanation.%}
628   }%
629 }%
630 \ifx\csname uni-titlepage.sty@vers\endcsname\relax
631   \PackageNotLoadedError{%
632   {DHBW}      title-DHBW.def%
633   {KOMAScript} title-KOMAScript.def%
634   {TU-DD}      title-TU-DD.def%
635   {TU-HH}      title-TU-HH.def%
636   {Markus & 1} title-Markus-1.def%
637   {Markus & 2} title-Markus-2.def%
638   {Spacer}     title-Spacer.def%
639   {KIT}        title-KIT.def%
640   {JT-Aufsaetze} title-JT-Aufsaetze.def%
641   {JT-Geschichte} title-JT-Geschichte.def%
642   {JT-Typography} title-JT-Typography.def%
643   {WWUM}       title-WWUM.def%
644   {UKoLA}      title-UKoLa.def%
645 }%
646 \fi
647 \endgroup

```

Each style corresponds with an own member. Nevertheless most styles will not have options in their own, because string options should be global to make change of style very easy.

```

648 \DefineFamilyMember{%
649   {DHBW}  DHBW%
650   {KOMAScript} KOMAScript%
651   {TU-DD}  TU-DD%
652   {TU-HH}  TU-HH%
653   {Markus & 1} Markus-1%
654   {Markus & 2} Markus-2%
655   {Spacer}  Spacer%
656   {KIT}    KIT%
657   {JT-Aufsaetze} JT-Aufsaetze%
658   {JT-Geschichte} JT-Geschichte%
659   {JT-Typography} JT-Typography%
660   {WWUM}   WWUM%
661   {UKoLa}  UKoLa%
662 }{title}

```

Nevertheless some styles have their own switches:

**blackborder** (*opt.*) *Trauerrand* at style TU-DD:

```
663 {TU-DD}\FamilyBoolKey[TU-DD]{title}{blackborder}{blackborder}
```

**final** (*opt.*) Style TU-HH distinguishes between drafts and final thesis.

```
664 {TU-HH}\FamilyBoolKey[TU-HH]{title}{final}{final}
```

**rulewidth** (*opt.*) Some styles have some variable rules at the title:

```
\title@rulewidth 665 {*Spacer | JT-Aufsaetze | JT-Geschichte | Markus & 2}
\rulesep (opt.)
\title@rulesep
\rulecolor (opt.)
\title@rulecolor
```

```

666 \providecommand*{\title@rulewidth}{%
667 <Spacer | Markus & 2> 0pt%
668 <JT-Aufsaetze | JT-Geschichte> .25\textwidth
669 }
670 \providecommand*{\title@rulesep}{%
671 <Spacer | Markus & 2> \ifdim \title@rulewidth>\z@ 10pt\else \z@\fi
672 <JT-Aufsaetze | JT-Geschichte> 1.5pt%
673 }
674 \providecommand*{\title@rulecolor}{}
675 \DefineFamilyKey[%
676 <Markus & 2> Markus-2%
677 <JT-Aufsaetze> JT-Aufsaetze%
678 <JT-Geschichte> JT-Geschichte%
679 <Spacer> Spacer%
680 ]{title}{rulewidth}{%
681   \gdef\title@rulewidth{\dimexpr #1\relax}%
682   \FamilyKeyStateProcessed
683 }
684 \DefineFamilyKey[%
685 <Markus & 2> Markus-2%
686 <JT-Aufsaetze> JT-Aufsaetze%
687 <JT-Geschichte> JT-Geschichte%
688 <Spacer> Spacer%
689 ]{title}{rulesep}{%
690   \gdef\title@rulesep{\dimexpr #1\relax}%
691   \FamilyKeyStateProcessed
692 }
693 \FamilyStringKey[%
694 <Markus & 2> Markus-2%
695 <JT-Aufsaetze> JT-Aufsaetze%
696 <JT-Geschichte> JT-Geschichte%
697 <Spacer> Spacer%
698 ]{title}{rulecolor}{\title@rulecolor}
699 </Spacer | JT-Aufsaetze | JT-Geschichte | Markus & 2>

```

An some has their own terms:

```

\presentationinformationUKoLA
\presentationinformationWWUM
\presentationinformationTUHH
\presentationinformationDHBW
\presentationinformationKIT
700 % \changes{v1.0}{2022/03/22}{using \cs{usenonemptytitleelement}}
701 <*UKoLa>
702 \providecommand*{\presentationinformationUKoLa}{%
703   to obtain the degree\\
704   \usenonemptytitleelement{academicgrade}\\
705   of \usenonemptytitleelement{discipline}\\
706 }
707 \providetext{american,australian,british,canadian,%
708   english,newzealand,UKenglish,USenglish}{\presentationinformationUKoLa}{%
709   to obtain the degree\\
710   \usenonemptytitleelement{academicgrade}\\
711   of \usenonemptytitleelement{discipline}\\
712 }
713 \providetext{german,ngerman,austrian,naustrian,%
714   swissgerman,nswissgerman}{\presentationinformationUKoLa}{%
715   zur Erlangung des Grades eines\\

```

```

716  \usenonemptytitleelement{academicgrade} \\
717  im Studiengang \usenonemptytitleelement{discipline} \\
718 }%
719 </UKoLa>
720 <*DHBW>
721 \providecommand*{\presentationinformationDHBW}{%
722  for the \examinationname{} of \[.5\baselineskip]
723  \usenonemptytitleelement{academicgrade} \[Opt plus 1fill]
724  of \usenonemptytitleelement{discipline} \[.5\baselineskip]
725  at the \usenonemptytitleelement{university}\ifx\@place\@empty\else\space\@place\fi
726 }
727 \providecaptionname{american,australian,british,canadian,%
728  english,newzealand,UKenglish,USenglish}\presentationinformationDHBW}{%
729  for the \examinationname{}\[.5\baselineskip]
730  \usenonemptytitleelement{academicgrade} \[Opt plus 1fill]
731  of degree course \usenonemptytitleelement{discipline}\[.5\baselineskip]
732  at the \usenonemptytitleelement{university}\ifx\@place\@empty\else\space\@place\fi
733 }%
734 \providecaptionname{german,ngerman,austrian,naustrian,%
735  swissgerman,nswissgerman}\presentationinformationDHBW}{%
736  f\"ur die \examinationname{} zum \[.5\baselineskip]
737  \usenonemptytitleelement{academicgrade} \[Opt plus 1fill]
738  des Studienganges \usenonemptytitleelement{discipline}\[.5\baselineskip]
739  an der \usenonemptytitleelement{university}\ifx\@place\@empty\else\space\@place\fi
740 }%
741 </DHBW>
742 <*TU-HH>
743 \providecommand*{\presentationinformationTUHH}{%
744  \iffinal Of the \else The \fi Graduation Committee of the\ \
745  \usenonemptytitleelement{university}\[.5ex]
746  to the Acquisition of the Academic Degree\\[.5ex]
747  \usenonemptytitleelement{academicgrade}\[.5ex]
748  \iffinal approved \else submitted \fi\@subject}
749 \providecaptionname{american,australian,british,canadian,%
750  english,newzealand,UKenglish,USenglish}\presentationinformationTUHH}{%
751  \iffinal Of the \else The \fi Graduation Committee of the\ \
752  \usenonemptytitleelement{university}\[.5ex]
753  to the Acquisition of the Academic Degree\\[.5ex]
754  \usenonemptytitleelement{academicgrade}\[.5ex]
755  \iffinal approved \else submitted \fi\@subject}
756 \providecaptionname{german,ngerman,austrian,naustrian,%
757  swissgerman,nswissgerman}\presentationinformationTUHH}{%
758  \iffinal Vom \else Dem \fi Promotionsausschuss der\ \
759  \usenonemptytitleelement{university}\[.5ex]
760  zur Erlangung des akademischen Grades\\[.5ex]
761  \usenonemptytitleelement{academicgrade}\[.5ex]
762  \iffinal genehmigte \else vorgelegte \fi\@subject}%
763 </TU-HH>
764 <*KIT>
765 \providecommand*{\presentationinformationKIT}{%
766  At the \usenonemptytitleelement{faculty}\ \
767  \strut\ignorespaces\@chair\ \
768 }
769 \providecaptionname{american,australian,british,canadian,%

```

```

770   english,newzealand,UKenglish,USenglish}{\presentationinformationKIT}{%
771   At the \usenonemptytitleelement{faculty} \\
772   \strut\ignorespaces{@chair}\\
773 }%
774 \providecaptionname{german,ngerman,austrian,naustrian,%
775   swissgerman,nswissgerman}{\presentationinformationKIT}{%
776   An der \usenonemptytitleelement{faculty} \\
777   \strut\ignorespaces{@chair}\\
778 }%
779 {/KIT}
780 {*WWUM}
781 \providecommand*\{\presentationinformationWWUM}{%
782   \usenonemptytitleelement{subject} \\
783   to the Aquisition of the Academic Degree \\
784   \usenonemptytitleelement{academicgrade} \\
785   of the \usenonemptytitleelement{sience} of \usenonemptytitleelement{discipline} \\
786   of the \usenonemptytitleelement{faculty} faculty \\
787   of the \usenonemptytitleelement{university}%
788 }
789 \providecaptionname{american,australian,british,canadian,%
790   english,newzealand,UKenglish,USenglish}{\presentationinformationWWUM}{%
791   \usenonemptytitleelement{subject} \\
792   to the Aquisition of the Academic Degree \\
793   \usenonemptytitleelement{academicgrade} \\
794   of the \usenonemptytitleelement{sience} of \usenonemptytitleelement{discipline} \\
795   of the \usenonemptytitleelement{faculty} faculty \\
796   of the \usenonemptytitleelement{university}%
797 }
798 \providecaptionname{german,ngerman,austrian,naustrian,%
799   swissgerman,nswissgerman}{\presentationinformationWWUM}{%
800   \usenonemptytitleelement{subject} \\
801   zur Erlangung des \usenonemptytitleelement{academicgrade} \\
802   der \usenonemptytitleelement{sience} im Fachbereich \\
803   \usenonemptytitleelement{discipline} \\
804   der \usenonemptytitleelement{faculty} Fakult"at \\
805   der \usenonemptytitleelement{university}%
806 }
807 {/WWUM}

\KITlongname
\fromname 808 {*KIT}
\refereename 809 \providecaptionname{american,australian,british,canadian,%
\KITurl 810   english,newzealand,UKenglish,USenglish}{\KITlongname}{%
811   University of the State of Baden-W"urttemberg and National Research Center
812   of the Helmholtz Association%
813 }%
814 \providecaptionname{german,ngerman,austrian,naustrian,%
815   swissgerman,nswissgerman}{\KITlongname}{%
816   Universit"at des Landes Baden-W"urttemberg und nationales
817   Forschungszentrum in der Helmholtz-Gemeinschaft
818 }%
819 \scr@ifundefinedorrelax{captionsamerican}{}{%
820   \renewcaptionname{american}{\fromname}{of}%
821   \renewcaptionname{american}{\refereename}{Reviewer}%

```

```

822 }%
823 \scr@ifundefinedorrelax{captionsaustralian}{}{%
824   \renewcaptionname{australian}{\fromname}{of}%
825   \renewcaptionname{australian}{\refereename}{Reviewer}%
826 }%
827 \scr@ifundefinedorrelax{captionsbritish}{}{%
828   \renewcaptionname{british}{\fromname}{of}%
829   \renewcaptionname{british}{\refereename}{Reviewer}%
830 }%
831 \scr@ifundefinedorrelax{captionscanadian}{}{%
832   \renewcaptionname{canadian}{\fromname}{of}%
833   \renewcaptionname{canadian}{\refereename}{Reviewer}%
834 }%
835 \scr@ifundefinedorrelax{captionsenglish}{}{%
836   \renewcaptionname{english}{\fromname}{of}%
837   \renewcaptionname{english}{\refereename}{Reviewer}%
838 }%
839 \scr@ifundefinedorrelax{captionsnewzealand}{}{%
840   \renewcaptionname{newzealand}{\fromname}{of}%
841   \renewcaptionname{newzealand}{\refereename}{Reviewer}%
842 }%
843 \scr@ifundefinedorrelax{captionsUKenglish}{}{%
844   \renewcaptionname{UKenglish}{\fromname}{of}%
845   \renewcaptionname{UKenglish}{\refereename}{Reviewer}%
846 }%
847 \scr@ifundefinedorrelax{captionsUSenglish}{}{%
848   \renewcaptionname{USenglish}{\fromname}{of}%
849   \renewcaptionname{USenglish}{\refereename}{Reviewer}%
850 }%
851 \newcommand*\KITurl{www.kit.edu}
852 
```

```

\presentedbyname
\ordinalmalereferee 853 {*WWUM | UKoLa}
\ordinalfemalereferee 854 \NowButAfterBeginDocument
855 {%
856   \providecaptionname{german,ngerman,austrian,naustrian,
857     swissgerman,nswissgerman}{\presentedbyname}{vorgelegt von}%
858   \scr@ifundefinedorrelax{captionsgerman}{}{%
859     \renewcaptionname{german}{\presentedbyname}{vorgelegt von}%
860     \renewcaptionname{german}{\ordinalmalereferee}{%
861       \ordinalfemalecorrectorname}%
862   }%
863   \scr@ifundefinedorrelax{captionsngerman}{}{%
864     \renewcaptionname{ngerman}{\presentedbyname}{vorgelegt von}%
865     \renewcaptionname{ngerman}{\ordinalmalereferee}{%
866       \germanordinalmalecorrectorname}%
867     \renewcaptionname{ngerman}{\ordinalfemalereferee}{%
868       \germanordinalfemalecorrectorname}%
869   }%
870   \scr@ifundefinedorrelax{captionsaustrian}{}{%
871     \renewcaptionname{austrian}{\presentedbyname}{vorgelegt von}%
872     \renewcaptionname{austrian}{\ordinalmalereferee}{%

```

```

873     \germanordinalmalecorrectorname}%
874     \renewcaptionname{austrian}{\ordinalfemalerefereename}{%
875         \germanordinalfemalecorrectorname}%
876     }%
877     \scr@ifundefinedorrelax{captionsaustrian}{}{%
878         \renewcaptionname{austrian}{\presentedbyname}{vorgelegt von}%
879         \renewcaptionname{austrian}{\ordinalmalerefereename}{%
880             \germanordinalmalecorrectorname}%
881         \renewcaptionname{austrian}{\ordinalfemalerefereename}{%
882             \germanordinalfemalecorrectorname}%
883     }%
884     \scr@ifundefinedorrelax{captionsswissgerman}{}{%
885         \renewcaptionname{swissgerman}{\presentedbyname}{vorgelegt von}%
886         \renewcaptionname{swissgerman}{\ordinalmalerefereename}{%
887             \germanordinalmalecorrectorname}%
888         \renewcaptionname{swissgerman}{\ordinalfemalerefereename}{%
889             \germanordinalfemalecorrectorname}%
890     }%
891     \scr@ifundefinedorrelax{captionsnswissgerman}{}{%
892         \renewcaptionname{nswissgerman}{\presentedbyname}{vorgelegt von}%
893         \renewcaptionname{nswissgerman}{\ordinalmalerefereename}{%
894             \germanordinalmalecorrectorname}%
895         \renewcaptionname{nswissgerman}{\ordinalfemalerefereename}{%
896             \germanordinalfemalecorrectorname}%
897     }%
898 }
899 </WWUM | UKoLa>

```

While style initialization, something may change:

```

900 \renewcommand*{\inittitle}{%
style KOMAScript redefines some footnote macros:

```

```

901 <*KOMAScript>
902   \let\footnotesize\small
903   \let\footnoterule\relax
904   \let\footnote\thanks
905   \renewcommand*{\thefootnote}{\@fnsymbol\c@footnote}%
906   \let\@oldmakefnmark\@makefnmark
907   \renewcommand*{\@makefnmark}{\rlap{\@oldmakefnmark}}%
908 </KOMAScript>

```

styles DHBW, TU-DD, TU-HH, KIT, and UKoLa set some variable if not already done

```

909 <*DHBW | TU-DD | TU-HH | KIT | WWUM>
910   \ifx\@university\@empty
911     \university{%
912     <DHBW>      Dualen Hochschule%
913     <TU-DD>      Technische\nobreakspace Universit\"at\nobreakspace Dresden%
914     <TU-HH>      Technische\nobreakspace Universit\"at\nobreakspace
915     <TU-HH>      Hamburg-Harburg%
916     <KIT>        KIT -- \KITlongname
917     <WWUM>       Westf\"alischen Wilhelms-Universit\"at M\"unster%
918   }%
919   \fi
920 </DHBW | TU-DD | TU-HH | KIT | WWUM>
921 <*DHBW | TU-DD | TU-HH | KIT | WWUM | UKoLa>

```

```

922   \ifx\@place\@empty
923     \place{%
924   <DHBW>      Baden-W\"urttemberg%
925   <TU-DD>      Dresden%
926   <TU-HH>      Hamburg%
927   <KIT>        Karlsruhe%
928   <*WWUM>
929     \PackageError{uni-titlepage}{Birth ‘place’ missing}{%
930       Style ‘WWUM’ needs the birth place of the student, so option ‘place=...’
931       resp. \MessageBreak
932       command ‘\string\place{...}’ is mandatory}%
933   </WWUM>
934   <UKoLa>      Koblenz%
935   }
936   \fi
937   <*DHBW | UKoLa>
938   \ifx\@mainlogo\@empty
939   <DHBW>      \IfFileExists{DHBW_d_MOS_195x95_rgb_300.jpg}{%
940   <UKoLa>      \IfFileExists{uni-koblenz-landau.png}{%
941     \scr@ifundefinedorrelax{includegraphics}{%
942       \if@atdocument\else\RequirePackage{graphicx}\fi
943     }{}%
944     \scr@ifundefinedorrelax{includegraphics}{}{%
945       \mainlogo{%
946   <*DHBW>
947     \includegraphics[width=57mm,height=27mm]
948     {DHBW_d_MOS_195x95_rgb_300.jpg}%
949   </DHBW>
950   <*UKoLa>
951     \includegraphics[width=63mm,height=10mm]
952     {uni-koblenz-landau.png}%
953   </UKoLa>
954   }{}%
955   }{}%
956   }{}%
957   \fi
958   </DHBW | UKoLa>
959   <*DHBW>
960   \ifx\@titlehead\@empty
961     \titlehead{\hspace*\{\fill\}\@mainlogo}%
962   \fi
963   </DHBW>
964   <*DHBW | UKoLa>
965   \ifx\@titlepagefont\@empty
966     \renewcommand*{\@titlepagefont}{%
967   <DHBW>      \normalfont\sffamily
968   <UKoLa>      \normalfont
969   }%
970   \fi
971   </DHBW | UKoLa>
972   <*KIT>
973   \ifx\@homepage\@empty
974     \homepage{\KITurl}%
975   \fi

```

```

976 \ifx\@mainlogo\@empty
Try to detect one of the suitable PNGs of the KIT logo from https://de.wikipedia.org/wiki/Datei:Logo\_KIT.svg.
977 \def\KIT@logo{KITLogo_RGB.pdf}\IfFileExists{\KIT@logo}{%
978   \def\KIT@logo{2560px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{%
979     \def\KIT@logo{2000px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{%
980       \def\KIT@logo{1280px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{%
981         \def\KIT@logo{1024px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{%
982           \def\KIT@logo{1000px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{%
983             \def\KIT@logo{800px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{%
984               \def\KIT@logo{640px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{%
985                 \def\KIT@logo{500px-Logo_KIT.svg.png}%
986               }}}}}}}}}}}%
987 \IfFileExists{\KIT@logo}{%
988   \scr@ifundefinedorrelax{includegraphics}{%
989     \if@atdocument\else\RequirePackage{graphicx}\fi
990   }{%
991     \scr@ifundefinedorrelax{includegraphics}{%
992       \mainlogo{%
993         \includegraphics[width=40mm,height=18.5mm]{\KIT@logo}%
994       }%
995     }%
996   }{%
997   }\fi
998 \ifx\@titlehead\@empty
999   \titlehead{\@mainlogo\hspace*{\fill}}%
1000 \fi
1001 \ifx\@titlepagefont\@empty
1002   \renewcommand*\@titlepagefont{\usefont{T1}{phv}{m}{n}}%
1003 \fi
1004 </KIT>
1005 <*WWUM>
1006 \ifx\@titlepagefont\@empty
1007   \renewcommand*\@titlepagefont{\normalfont\large}%
1008 \fi
1009 </WWUM>
1010 </DHBW | TU-DD | TU-HH | KIT | WWUM | UKoLa>
```

style Markus-2 uses it's own pagestyle at the first title page

```

1011 <*Markus & 2>
1012 \def\ps@maintitle{%
1013   \ps@empty
1014   \def\@oddhead{%
1015     \parbox[b][\headheight][b]{\hsize}{\@titlepagefont{%
1016       \csname @titlehead\endcsname}}%
1017   }%
1018   \let\@evenhead\@oddhead
1019 }%
1020 </Markus & 2>
```

styles JT-Aufsaetze and JT-Geschichte set some font defaults:

```

1021 <*JT-Aufsaetze | JT-Geschichte>
1022 \ifx\@titlepagefont\@empty
1023 <JT-Aufsaetze> \renewcommand*\@titlepagefont{\normalfont\Huge\itshape}%

```

```

1024 <*JT-Geschichte>
1025   \scr@ifundefinedorrelax{\lsstyle}{%
1026     \renewcommand*{\@titlepagefont}{\normalfont\let\@tpf@extra\scshape}%
1027   }{%
1028     \renewcommand*{\@titlepagefont}{%
1029       \normalfont\def\@tpf@extra{\lsstyle\MakeUppercase}%
1030     }%
1031   }%
1032 </JT-Geschichte>
1033   \fi
1034   \ifx\titlefont\empty
1035     \renewcommand*{\titlefont}{\normalfont}%
1036   \fi
1037 </JT-Aufsaetze | JT-Geschichte>
1038 <*JT-Typography>
1039   \ifx\@titlepagefont\empty
1040     \renewcommand*{\@titlepagefont}{\normalfont\sffamily\bfseries}%
1041   \fi
1042 </JT-Typography>
1043 }

```

\publishers KOMA-Script defines this macro. But we use \publisher instead.

```
1044 <KOMAScript>\providecommand*{\publishers}{\publisher}
```

\makemaintitle This differs from style to style:

```

1045 \renewcommand*{\makemaintitle}{%
1046   \begin{%
1047     (DHBW | TU-DD | TU-HH | KIT)      fullsizetitle}%
1048     <*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM | UKoLa)%
1049       titlepage}%
1050   </KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM | UKoLa)%
1051     \setlength{\parskip}{\z@}%
1052     \setlength{\parindent}{\z@}%
1053     \setlength{\parfillskip}{\z@\@plus 1fil}%
1054     \linespread{1}\selectfont
1055     \titlepagefont
1056   <*DHBW>
1057     \vspace*{12mm}%
1058     \centering
1059     \begin{minipage}[t]{[\dimexpr\vsiz-36mm\relax]\dimexpr\hsiz-40mm\relax}%
1060       \titlehead\par
1061       \centering
1062       \Large
1063       \vfill
1064       {\titlefont{\Large\useonemptytitleelement{title}}}\par
1065       \vfill
1066       {\subjectfont{\Large\useonemptytitleelement{subject}}}\par
1067       \vfill
1068       \presentationinformationDHBW\par
1069       \vfill
1070       \fromname\\[.5\baselineskip]
1071       \useonemptytitleelement{author}\par

```

```

1072     \vfill
1073     \@date\par
1074     \vfill
1075     \begin{tabular}{*2{p{.5\dimexpr\linewidth-3\tabcolsep\relax}}@{}}
1076         \durationname & \@duration \\ [.5ex]
1077         \matriculationnumbername, \coursename & \usenonemptytitleelement{matriculationnum}
1078                                         & \usenonemptytitleelement{course} \\ [.5ex]
1079         \companyname & \usenonemptytitleelement{company} \\ [.5ex]
1080         \advisorname{} \ofthename{} \companyname & \usenonemptytitleelement{advisor} \\ [.5ex]
1081         \referee{} \ofthename{} \university & \usenonemptytitleelement{referee}
1082     \end{tabular}
1083     \end{minipage}
1084 /DHBW
1085 *KOMAScript
1086     \ifx\@titlehead\empty \else
1087         \begin{minipage}[t]{\textwidth}%
1088             \@titlehead
1089         \end{minipage}\par
1090     \fi
1091     \null\vfill
1092     \begingroup
1093         \centering
1094         \ifx\@subject\empty \else
1095             {\@subject\font{\@subject \par}}%
1096             \vskip 3em
1097         \fi
1098         {\@titlefont{\huge \usenonemptytitleelement{title}\par}}%
1099         \vskip 1em
1100         {\ifx\@subtitle\empty\else\@subtitlefont{\@subtitle}\par\fi}%
1101         \vskip 2em
1102         {\Large \lineskip 0.75em
1103             \begin{tabular}[t]{c}
1104                 \author
1105             \end{tabular}\par
1106         }%
1107         \vskip 1.5em
1108         {\Large \@date \par}%
1109         \vskip \z@ \oplus3fill
1110         {\Large \@publisher \par}%
1111         \vskip 3em
1112     \endgroup
1113     \@thanks
1114     \vfill\null\vskip-\baselineskip
1115 /KOMAScript
1116 *TU-DD
1117     \rule{0pt}{5mm}\par
1118     \ifblackborder
1119         \leavevmode\hspace{1cm}
1120         \setlength{\fboxrule}{1pt}%
1121         \expandafter\fbox
1122     \else
1123         \expandafter\mbox
1124     \fi
1125     {%

```

```

1126 \begin{minipage}[t][\dimexpr\textheight-2.5cm\relax][t]{%
1127   \dimexpr\linewidth\ifblackborder-3cm\fi\relax}
1128   \sffamily
1129   \centering
1130   \vskip 3cm
1131   {\fontsize{28pt}{34pt}\selectfont
1132     \strut\ignorespaces@university\unskip\strut\\}
1133   {\fontsize{24pt}{28pt}\selectfont
1134     \strut\ignorespaces@faculty\unskip\strut\\}
1135   {\fontsize{20pt}{24pt}\selectfont
1136     \strut\ignorespaces@chair\unskip\strut\\
1137     \strut\ignorespaces@professor\unskip\strut\\
1138     \vfill
1139     {\bfseries\strut\ignorespaces@title\unskip\strut\\}
1140     \strut\ignorespaces@subject\unskip\strut\\
1141     \vfill
1142     \raggedright
1143     \hspace*{.25\linewidth}%
1144     \strut\ignorespaces\presentedbyname\unskip\strut\\
1145     \hspace*{.25\linewidth}\quad
1146   \begin{tabular}{@{}l@{}}
1147     \strut\ignorespaces@author\unskip\strut\\
1148     \strut\ignorespaces@discipline\unskip\strut\\
1149     \strut\ignorespaces@matriculationnumber\unskip\strut\\
1150   \end{tabular}\\
1151   \vskip\baselineskip
1152   \hspace*{.25\linewidth}%
1153   \strut\ignorespaces\advisorname\unskip:\strut\\
1154   \hspace*{.25\linewidth}\quad
1155   \begin{tabular}{@{}l@{}}
1156     \strut\ignorespaces\useonemptytitleelement{advisor}\unskip\strut\\
1157   \end{tabular}\\
1158   \vskip2\baselineskip
1159   \hspace*{.25\linewidth}%
1160   \strut\ignorespaces@place,\nobreakspace\thename\nobreakspace@date
1161   \par
1162   \vspace*{5mm}
1163 \end{minipage}
1164 }%
1165 
1166 
1167   \sffamily
1168   \centering
1169   \vspace{5cm}
1170   {\LARGE\bfseries\strut\ignorespaces@title\\}
1171   {\Large\strut\ignorespaces@subtitle\\}
1172   \vspace{2.5cm}
1173   {\Large\presentationinformationTUHH\\}
1174   \vspace{2.5cm}
1175   {\Large\strut\ignorespaces\fromname\\
1176     \strut\ignorespaces\useonemptytitleelement{author}\\}
1177   \vspace{2.5cm}
1178   {\Large\strut\ignorespaces\fromplacename\\
1179     \strut\ignorespaces\useonemptytitleelement{place}\\}

```

```

1180      \vspace{2.5cm}
1181      {\Large\@date}
1182 {/TU-HH}
1183 {*WWUM}
1184      \centering
1185      \useanonemptytitleelement{chair} \\
1186      \vspace{2cm}
1187      \useanonemptytitleelement{title} \\
1188      \vfill
1189      \presentationinformationWWUM \\
1190      \vfill
1191      \presentedbyname \\
1192      \useanonemptytitleelement{author} \\
1193      \ifx\@place\@empty\else\fromplacename{}\ \@place\\ \fi
1194      --\,\the\year\,--
1195{/WWUM}
1196 {*Markus & 1}
1197      \raggedright
1198      {\subject@font%
1199          \large\strut\ignorespaces\@subject\par\vskip 2\baselineskip}%
1200      {\titlefont{\LARGE\strut\ignorespaces\@title\par}}%
1201      {\@subtitlefont{%
1202          \large\vskip.5\baselineskip\strut\ignorespaces\@subtitle\par}}%
1203      \vfill
1204      {\csname @datefont\endcsname{\large\strut\ignorespaces\@date\par}}%
1205{/Markus & 1}
1206 {*Spacer | Markus & 2}
1207      \raggedright
1208 {*Markus & 2} \thispagestyle{maintitle}%
1209      \raisebox{0pt}[{\ht\strutbox}][{\dimexpr\textheight-\ht\strutbox\relax}]{%
1210          \ifx\title@rulecolor\@empty\else
1211              \color{\title@rulecolor}%
1212          \fi
1213          \rule[{\dimexpr-.667\headsep-\textheight}\relax]
1214              {\title@rulewidth}
1215              {\dimexpr\textheight+2\headsep\relax}\kern\title@rulesep
1216      }%
1217      \parbox[t]{\textheight}[t]
1218          {\dimexpr\textheight-\title@rulewidth-\title@rulesep\relax}%
1219      \raggedright
1220 {*Spacer}
1221      \ifx\@titlehead\@empty\else
1222          \raisebox{\dimexpr\ht\strutbox-\totalheight\relax}{%
1223              \parbox[t]{\ linewidth}{\@titlehead}%
1224          }\par
1225          \vskip 2\baselineskip
1226      \fi
1227{/Spacer}
1228      {\leavevmode\subject@font{%
1229          \large\strut\ignorespaces\@subject\par\vskip 2\baselineskip}%
1230          {\def\and{\ \ }\csname @authorfont\endcsname{\large\@author}\par
1231          \vskip .5\baselineskip}%
1232          {\titlefont{\LARGE\strut\ignorespaces\@title\par}}%
1233          {\@subtitlefont{%

```

```

1234      \large\vskip.5\baselineskip\strut\ignorespaces{@subtitle\par}%%
1235      \vfill
1236      {\csname @publisherfont\endcsname{\large\@publisher\par}%%
1237      {\csname @datefont\endcsname{\large\strut\ignorespaces{@date\par}%%
1238      }%
1239 
```

/Spacer | Markus & 2)

\*KIT

```

1240      \setlength{\unitlength}{1mm}%
1241      \begin{picture}(0,0)
1242          \put(15,-12){%
1243              \line(1,0){\dimexpr\paperwidth-37mm\relax\@gobble}%
1244          }%
1245          \put(\dimexpr\paperwidth-22mm\@gobble,-19){\oval(14,14)[rt]}%
1246          \put(\dimexpr\paperwidth-15mm\@gobble,-19){%
1247              \line(0,-1){\dimexpr\paperheight-37mm\relax\@gobble}%
1248          }%
1249          \put(22,-\dimexpr\paperheight-18mm\relax\@gobble){%
1250              \line(1,0){\dimexpr\paperwidth-37mm\relax\@gobble}%
1251          }%
1252          \put(22,-\dimexpr\paperheight-25mm\relax\@gobble){\oval(14,14)[lb]}%
1253          \put(15,-\dimexpr\paperheight-25mm\relax\@gobble){%
1254              \line(0,1){\dimexpr\paperheight-37mm\relax\@gobble}%
1255          }%
1256      \end{picture}\par
1257      \vskip\dimexpr -\baselineskip+25mm\relax
1258      \hspace*{27mm}%
1259      \begin{minipage}[t]{\dimexpr\paperheight-68mm\relax}[t]
1260          {\dimexpr\paperwidth-54mm\relax}
1261          \raggedright\@titlehead\par
1262          \centering
1263          \vskip 25mm
1264          {\@titlepagefont\@title\par}%
1265          \vskip 20mm
1266          {\Large\@subject\par\fromname\par}
1267          \vskip 1cm
1268          {\huge\usenonemptytitleelement{author}\par}
1269          \vskip 1cm
1270          {\Large\presentationinformationKIT\par}
1271          \vskip 2cm
1272          {\Large
1273              \let\@tempa\refereename
1274              \def\@tempb{1}%
1275              \def\and{%
1276                  \\
1277                  \xdef\@tempb{\the\numexpr\@tempb+1\relax}%
1278                  \expandafter\ordinal\expandafter{\@tempb}\~\@tempa: \&
1279              }%
1280              \begin{tabular}{@{}lr@{}}
1281                  \refereename: \& \referee \\
1282                  \global\let\@tempa\advisorname\xdef\@tempb{1}%
1283                  \advisorname: \& \advisor \\
1284              \end{tabular}\par
1285          }
1286          \vfill

```

```

1288      {\large \durationname: \@duration\par}
1289  \end{minipage}
1290  \vskip 35mm
1291  \hspace*{27mm}\makebox[\dimexpr\paperwidth-56mm\relax]{%
1292      \tiny\@university\hfill\large\textrm{\@homepage}\%%
1293  }%
1294 /KIT
1295 *JT-Aufsaetze
1296  \centering
1297  \ifx\@author\empty\else\@author\%
1298  \begin{picture}(\title@rulewidth\gobble,
1299      \dimexpr .3ex+1pt+\title@rulesep\relax\gobble)
1300  \ifx\title@rulecolor\empty\else
1301      \color{\title@rulecolor}%
1302  \fi
1303  \put(0,\dimexpr .15ex+.5pt+\title@rulesep\relax\gobble){%
1304      \linethickness{.3ex}\line(1,0){\title@rulewidth\gobble}%
1305  }%
1306  \put(0,0){%
1307      \linethickness{1pt}\line(1,0){\title@rulewidth\gobble}%
1308  }%
1309  \end{picture}\[\baselineskip]
1310 \fi
1311 {\titlefont{\@title\par}}%
1312 \vfill
1313 \@publisher
1314 /JT-Aufsaetze
1315 *JT-Geschichte
1316  \centering
1317  \large{@tpf@extra{\@author\unskip\strut}}\[\dp\strutbox]
1318  {\titlefont{\Huge\@title\par}}
1319  \vfill
1320  \begin{picture}(\title@rulewidth\gobble,
1321      \dimexpr 4pt+1pt+\title@rulesep\relax\gobble)
1322  \ifx\title@rulecolor\empty\else
1323      \color{\title@rulecolor}%
1324  \fi
1325  \put(0,\dimexpr 2pt+.5pt+\title@rulesep\relax\gobble){%
1326      \linethickness{1pt}\line(1,0){\title@rulewidth\gobble}%
1327  }%
1328  \put(0,0){%
1329      \linethickness{4pt}\line(1,0){\title@rulewidth\gobble}%
1330  }%
1331  \end{picture}\[\dp\strutbox]
1332  @tpf@extra{\@publisher}%
1333  \ifx\@place\empty\else
1334      \unskip@tpf@extra{\strut}\[\dp\strutbox]@tpf@extra{\@place}%
1335  \fi
1336 /JT-Geschichte
1337 *JT-Typography
1338  \raggedright
1339  {\Large\MakeUppercase{\@author}\unskip\strut\[\baselineskip]}
1340  {\titlefont{\Huge\MakeUppercase{\@title}\unskip\strut\[]}}
1341  {\@subtitlefont{\normalsize\MakeUppercase{\@subtitle}\unskip\strut\[]}}

```

```

1342   \vfill
1343   {\normalsize\MakeUppercase{\@place}\ifx\@place\empty\else\enskip\fi
1344     {\LARGE\MakeUppercase{\@date}}%
1345     \ifx\@publisher\empty\else\unskip\strut\\[1.5\baselineskip]
1346       \MakeUppercase{\@publisher}%
1347   \fi}
1348 {/JT-Typography}
1349 {*UKoLa}
1350   \begin{tabular}[t]{@{}c@{}}
1351     \raisebox{\dimexpr\ht\strutbox-\height}{\@mainlogo} \\
1352     \@chair \\
1353   \end{tabular}\hfill
1354   \begin{tabular}[r]{@{}c@{}}
1355     \raisebox{\dimexpr\ht\strutbox-\height}{\@secondlogo} \\
1356   \end{tabular}\par
1357   \vspace{5\baselineskip}
1358   \centering
1359   {\LARGE\bfseries\titlefont{\@title\par}}%
1360   \vspace{5\baselineskip}
1361   {\Large\subjectfont{\@subject\par}}%
1362   \vspace{\baselineskip}
1363   \presentationinformationUKoLa\par
1364   \vspace{5\baselineskip}
1365   \presentedbyname\\[\baselineskip]
1366   {\Large\csname @authorfont\endcsname{\useonemptytitleelement{author}\par}}%
1367   \vfill
1368   \raggedright
1369   \hangfrom{\advisorname: }{\@advisor\par}%
1370   \newcommand*{\test@male@female}[1][m]{%
1371     \global\advance\tempcnta by\@ne
1372     \Ifstr{##1}{f}{\def\fe@male@female}{\def\fe@male@male}%
1373     \hangfrom{\csname ordinal\fe@male referee\endcsname{\@tempcnta}: }%
1374     \def\and{\par\test@male@female}%
1375   }%
1376   \atempcnta \z@%
1377   \expandafter\test@male@female\referee\par
1378   \vspace{3\baselineskip}
1379   \@place, \Ifstr{\indatename}{}{\indatename\ }{\@date\par}
1380 {/UKoLa}
1381   \end{%
1382 {/DHBW | TU-DD | TU-HH | KIT}    fullsizetitle}
1383 {*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM | UKoLa}
1384   titlepage}
1385 {/KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM | UKoLa}
1386 }

```

Some of the styles need additional string options for the back of the main title.  
These are more structural than logical, so we do not define those globally!

```

uppertitleback (opt.)
\uppertitleback 1387 {*KOMAScript | Markus | Spacer}
@uppertitlebacke 1388 \providecommand*{\@uppertitleback}{}
lowertitleback (opt.) 1389 \providecommand{\uppertitleback}[1]{\gdef\@uppertitleback{\#1}}
\lowertitleback 1390 \DefineFamilyKey{%
\@lowertitleback

```

```

1391 <KOMAScript> KOMAScript%
1392 <Markus & 1> Markus-1%
1393 <Markus & 2> Markus-2%
1394 <Spacer> Spacer%
1395 <JT-Aufsaetze> JT-Aufsaetze%
1396 <JT-Geschichte> JT-Geschichte%
1397 <JT-Geschichte> JT-Typography%
1398 ]{title}{uppertitleback}{\uppertitleback{\#1}\FamilyKeyStateProcessed}
1399 \providecommand*\@lowertitleback{}%
1400 \providecommand{\lowertitleback}[1]{\gdef\@lowertitleback{\#1}}
1401 \DefineFamilyKey[%
1402 <KOMAScript> KOMAScript%
1403 <Markus & 1> Markus-1%
1404 <Markus & 2> Markus-2%
1405 <Spacer> Spacer%
1406 <JT-Aufsaetze> JT-Aufsaetze%
1407 <JT-Geschichte> JT-Geschichte%
1408 <JT-Geschichte> JT-Typography%
1409 ]{title}{lowertitleback}{\lowertitleback{\#1}\FamilyKeyStateProcessed}
1410 </KOMAScript | Markus | Spacer>

```

\makemaintitleback Only some of the styles define this:

```

1411 <*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1412 \renewcommand*\makemaintitleback{%
1413   \begin{titlepage}
1414     \begin{minipage}[t]{\textwidth}
1415       \titlepagefont{\@uppertitleback}%
1416     \end{minipage}\par
1417     \vfill
1418     \begin{minipage}[b]{\textwidth}
1419       \titlepagefont{\@lowertitleback}%
1420     \end{minipage}
1421   \end{titlepage}
1422 }
1423 </KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1424 <*TU-HH>
1425 \renewcommand*\makemaintitleback{%
1426   \begin{titlepage}
1427     \vspace*\fill
1428     \iffinal
1429       \tempcnta\z@
1430       \def\and{%
1431         \par\advance\tempcnta by\@ne
1432         \hangfrom{%
1433           \expandafter\ordinal\expandafter{\the\tempcnta}\~\refereename:\enskip
1434         }%
1435       }\and\referee
1436     \fi
1437     \vskip 1cm
1438     \iffinal
1439       \hangfrom{\oralexaminationdatename:\enskip}{\oralexaminationdate}%
1440     \fi
1441   \end{titlepage}
1442 }

```

```

1443 </TU-HH>
1444 <*WWUM>
1445 \renewcommand*{\makemaintitleback}{%
1446   \begin{titlepage}
1447     \vspace*{\fill}
1448     \noindent
1449     \tempcnta\z@%
1450     \def\arraystretch{2}%
1451     \newcommand*{\test@malefemale}[1] [m]{%
1452       \global\advance\tempcnta by\@ne
1453       \Ifstr{##1}{f}{\def\fe@male{female}}{\def\fe@male{male}}%
1454       \csname \fe@male ordinal\endcsname{\tempcnta}\space
1455       \csname \fe@male refereename\endcsname: &
1456       \def\and{\\\test@malefemale}%
1457     }%
1458     \begin{tabular}{@{}l l @{}}
1459       \chairmanname: & \professor \\
1460       \expandafter\test@malefemale
1461       \referee \\
1462       \oralexaminationdatename: & \coralexaminationdate
1463       \ifx\examinationdatename\empty\else
1464         \\\examinationdatename: &
1465       \fi
1466     \\
1467     \end{tabular}
1468   \end{titlepage}
1469 }
1470 </WWUM>

```

Some of the styles need additional string options for the pre title. These are more structural than logical, so we do not define those globally!

```

extratitle (opt.)
\extratitle 1471 <*KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
@extratitle 1472 \providecommand*{\@extratitle}{}
             \providecommand{\extratitle}[1]{\gdef\@extratitle{#1}}
             \DefineFamilyKey[%]
               {KOMAScript} {KOMAScript%}
               {Markus & 2} {Markus-2%}
               {Spacer} {Spacer%}
               {JT-Aufsaetze} {JT-Aufsaetze%}
               {JT-Geschichte} {JT-Geschichte%}
               {JT-Typography} {JT-Typography%}
             ]{\title}{extratitle}{\extratitle{#1}\FamilyKeyStateProcessed}
1482 </KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>

```

\makepretitle Only some styles have pre titles:

```

\makepretitleback 1483 <*KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1484 \renewcommand*{\makepretitle}{%
1485   \ifx\@extratitle\empty\else
1486     \begin{titlepage}
1487       \noindent\@extratitle
1488     \end{titlepage}
1489   \fi

```

```

1490 }%
1491 </KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1492 <*Markus & 1>
1493 \renewcommand*{\makepretitle}{%
1494   \ifx\@publisher\@empty\else
1495     \begin{titlepage}
1496       \raggedleft
1497       {\@titlepagefont{%
1498         \large\strut\ignorespaces\@publisher\par}}%
1499     \end{titlepage}
1500   \fi
1501 }
1502 </Markus & 1>
1503 <*WWUM>
1504 \renewcommand*{\makepretitle}{%
1505   \begin{fullsizetitle}
1506     \@titlepagefont
1507     \vspace*{.33\vsizetop}%
1508     \centering
1509     \useanonemptytitleelement{author}\\\[1ex]
1510     \useanonemptytitleelement{title}\\\[1ex]
1511     \the\year
1512   \end{fullsizetitle}
1513 }
1514 </WWUM>
1515 </KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1516 <*KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1517 \renewcommand*{\makepretitleback}{%
1518   \ifx\@extratitle\@empty\else\begin{titlepage}\null\end{titlepage}\fi
1519 }
1520 </KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1521 <*Markus & 1>
1522 \renewcommand*{\makepretitleback}{%
1523   \ifx\@author\@empty\else
1524     \ifx\@publisher\@empty\begin{titlepage}\end{titlepage}\fi
1525     \begin{titlepage}
1526       \raggedleft
1527       {\@titlepagefont{%
1528         \large\null\vskip 2\baselineskip
1529         \LARGE\strut{\def\and{\hspace{1em}\linebreak[3]}%
1530           \csname @authorfont\endcsname{\large\ignorespaces\@author\par}}}}%
1531     \end{titlepage}
1532   \fi
1533 }
1534 </Markus & 1>
1535 <*WWUM>
1536 \renewcommand*{\makepretitleback}{%
1537   \if@twoside\begin{titlepage}\null\end{titlepage}\fi
1538 }
1539 </WWUM>

```

\makeposttitle And only some styles provides one more title page with dedication.

\makeposttitleback 1540 <\*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>

```

1541 \renewcommand*{\makeposttitle}{%
1542   \ifx\@dedication\empty\else
1543     \begin{titlepage}
1544       \null\vfill
1545       {\centering\csname\@dedicationfont\endcsname{\@dedication \par}}%
1546       \vskip \z@\plus 3fill
1547     \end{titlepage}
1548   \fi
1549 }
1550 \renewcommand*{\makeposttitleback}{%
1551   \ifx\@dedication\empty\else\begin{titlepage}\null\end{titlepage}\fi
1552 }
1553 //KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography

```

#### 4.4 The Examples and the Manual

```

1554 \documentclass[a4paper, pagesize]{scrbook}
1555 \usepackage[ngerman]{babel}
1556 \usepackage{iftex}
1557 \iftutex
1558 { *TU-HH | TU-DD }
1559   \usepackage{fontspec}
1560   \setmainfont{TeX Gyre Termes}
1561   \setsansfont{TeX Gyre Heros}
1562 { /TU-HH | TU-DD }
1563 \else
1564   \usepackage[T1]{fontenc}
1565   \usepackage{lmodern}
1566 { (TU-HH | TU-DD) \usepackage{mathpazo}
1567 { (TU-HH | TU-DD) \usepackage[scaled]{helvet}
1568 \fi
1569 { (JT-Geschichte) \usepackage{microtype}
1570 { (DHBW | Spacer | KIT | UKoLa) \usepackage[demo]{graphicx} % remove option demo if you have the local file
1571 \usepackage{xcolor}
1572 { (JT-Geschichte | JT-Typography) \colorlet{RED}{red} % because of \MakeUppercase{\textcolor{red}{...}}
1573 \usepackage{uni-titlepage}
1574 \begin{document}
1575 { *DHBW
1576 \TitlePageStyle{DHBW}
1577 \makeatletter\providecommand*{\@titlepagefont}{\normalfont\sffamily}\makeatother
1578 \setkomafont{subject}{\sffamily\bfseries}
1579 \maketitle[%]
1580   titlefont=\sffamily,
1581   mainlogo=\textcolor{red}{%}
1582     % You may add a company logo here!
1583     % NOTE: The original logo has a large white border!
1584     \includegraphics[width=57mm, height=27mm]%
1585     {DHBW_d_MOS_195x95_rgb_300.jpg}%
1586 },
1587 % You may additionally change titlehead. The original definition of
1588 % titlehead is:
1589 titlehead={\hspace*{\fill}\useitlelement{mainlogo}},
1590 title=\textcolor{red}{Bachelorarbeitsthema},
1591 subject=\textcolor{red}{BACHELORARBEIT},

```

```

1592 academicgrade=\textcolor{red}{Bachelor of Engineering},
1593 discipline=\textcolor{red}{Studiengang},
1594 place={Baden-Württemberg \textcolor{red}{Stadt}},
1595 student=\textcolor{red}{Vorname Nachname},
1596 duration=\textcolor{red}{12 Wochen},
1597 matriculationnumber=\textcolor{red}{Matrikelnummer},
1598 course=\textcolor{red}{Kurskürzel},
1599 company=\textcolor{red}{Firmenname, Stadt},
1600 advisor=\textcolor{red}{Titel Vorname Nachname},
1601 referee=\textcolor{red}{Titel Vorname Nachname},
1602 date=\textcolor{red}{Abgabedatum}
1603 ]
1604 //DHBW)
1605 {*TU-DD}
1606 \TitlePageStyle{TU-DD}
1607 \maketitle[%]
1608 title=\textcolor{red}{Titel im Stil \texttt{TU-DD}},%
1609 university=\textcolor{red}{%
1610 Technische\nobreakspace Universit\"at\nobreakspace Dresden},%
1611 faculty=\textcolor{red}{Fakultät Wirtschaftswissenschaften},%
1612 chair=\textcolor{red}{SAP-Stiftungslehrstuhl für\%
1613 Entrepreneurship und Innovation},%
1614 professor=\textcolor{red}{Prof.\,Dr.\,Michael Schefcyk},%
1615 % subject=diploma, % one of: project, seminar, studentresearch,
1616 % % diploma, degree, master, bachelor, or ...
1617 subject=\textcolor{red}{Seminararbeit\|(bzw. Diplomarbeit)},% ... direct value
1618 student=\textcolor{red}{Vorname und Name},%
1619 discipline=\textcolor{red}{Studienrichtung},%
1620 matriculationnumber=\textcolor{red}{Matrikel-Nr.},%
1621 advisor=\textcolor{red}{(mit akadem. Grad, Vor- und Zuname)},%
1622 date=\textcolor{red}{(Datum der Abgabe)}
1623 ]
1624
1625 \TitleOptions[pagenumber=1,blackborder]%
 same with ‘Trauerrand’
1626 \maketitle% everything else, like above
1627 //TU-DD)
1628 {*KOMAScript}
1629 \TitlePageStyle[pagenumber=1]{KOMAScript}
1630 \maketitle[%
1631 extratitle=\textcolor{red}{Das ist ein Schmutztitel im Stil \texttt{KOMAScript}},%
1632 titlehead=\textcolor{red}{Den Kopfbereich kann man auf diese Weise f\"ullen.},%
1633 subject=\textcolor{red}{Eine Klassifizierung der Arbeit},%
1634 title=\textcolor{red}{Titel im Stil \texttt{KOMAScript}},%
1635 subtitle=\textcolor{red}{Untertitel},%
1636 publisher=\textcolor{red}{Einen Verlag kann man ebenfalls angeben},%
1637 uppertitleback=\textcolor{red}{Oberer Bereich der Rückseite des Haupttitels im Stil
1638 \texttt{KOMAScript}.},%
1639 lowertitleback=\textcolor{red}{Unterer Bereich der Rückseite des Haupttitels im Stil
1640 \texttt{KOMAScript}.},%
1641 dedication=\textcolor{red}{Eine Widmung im Stil \texttt{KOMAScript}}%
1642 ]
1643 //KOMAScript)
1644 {*TU-HH}
1645 \TitlePageStyle[pagenumber=1]{TU-HH}

```

```

1646 \maketitle[%  

1647   final,  

1648   title=\textcolor{red}{Titel im Stil \texttt{TU-HH}},  

1649   university=\textcolor{red}{Technischen Universität Hamburg-Harburg},  

1650   subject=degree,  

1651   author=\textcolor{red}{Vorname und Name},  

1652   academicgrade=\textcolor{red}{Doktor der Naturwissenschaften (Dr.\,rer.\,nat\,)},  

1653   place=\textcolor{red}{(Geburtsort)},  

1654   date=\textcolor{red}{(aktuelles Jahr)},  

1655   referee=\textcolor{red}{Name des ersten Gutachters\protect\and Name des zweiten  
Gutachters},  

1657   oralexaminationdate=\textcolor{red}{29. Februar 2009}  

1658 ]  

1659 </TU-HH>  

1660 <*Markus | Spacer>  

1661 % Maybe we should define one more option for this:  

1662 \setkomafont{subject}{\normalfont\sffamily}% because of KOMA-Script class  

1663 \setkomafont{title}{\normalfont\sffamily}% because of KOMA-Script class  

1664 <*1>  

1665 \TitlePageStyle[pagenumber=1]{Markus-1}  

1666 \maketitle[%  

1667   titlepagefont={\normalfont\sffamily},% to show is without KOMA-Script class  

1668   title=\textcolor{red}{Titel im Stil \texttt{Markus-1}},  

1669   subject=\textcolor{red}{Eine Klassifizierung der Arbeit},  

1670   subtitle=\textcolor{red}{Untertitel},  

1671   publisher=\textcolor{red}{Verlag},  

1672   uppertitleback=\textcolor{red}{Überer Bereich der Rückseite des Haupttitels  
im Stil \texttt{Markus-1}.},  

1674   lowertitleback=\textcolor{red}{Unterer Bereich der Rückseite des Haupttitels  
im Stil \texttt{Markus-1}.},  

1676   dedication=\textcolor{red}{Eine Widmung im Stil \texttt{Markus-1}},  

1677   author=\textcolor{red}{Markus~Kohm\protect\and Sonst~Jemand}  

1678 ]  

1679 </1>  

1680 <*2 | Spacer>  

1681 <2>\TitlePageStyle[pagenumber=1]{Markus-2}  

1682 <Spacer>\TitlePageStyle[pagenumber=1]{Spacer}>  

1683 \maketitle[%  

1684   rulewidth=2pt,  

1685   extratitle=\textcolor{red}{Das ist ein Schmutztitel im Stil \texttt{Markus-2}},  

1686 <2>      Markus-2},  

1687 <Spacer>      Spacer},  

1688 <*Spacer>  

1689   titlehead=\textcolor{red}{\includegraphics{Logo}},  

1690 </Spacer>  

1691   title=\textcolor{red}{Titel im Stil \texttt{Markus-2}},  

1692 <2>      Markus-2},  

1693 <Spacer>      Spacer},  

1694   subject=\textcolor{red}{Eine Klassifizierung der Arbeit},  

1695   subtitle=\textcolor{red}{Untertitel},  

1696   publisher=\textcolor{red}{Verlag},  

1697   uppertitleback=\textcolor{red}{Überer Bereich der Rückseite des Haupttitels  
im Stil \texttt{Markus-2}.},  

1699 <2>      Markus-2}.

```

```

1700 <Spacer>      Spacer}.},
1701   lowertitleback=\textcolor{red}{Unterer Bereich der Rückseite des Haupttitels
1702     im Stil \texttt{%
1703 <2>      Markus-2}.},
1704 <Spacer>      Spacer}.},
1705   dedication=\textcolor{red}{Eine Widmung im Stil \texttt{%
1706 <2>      Markus-2}}},%
1707 <Spacer>      Spacer}}},%
1708   author=\textcolor{red}{Markus~Kohm}
1709 ]
1710 </2 | Spacer>
1711 </Markus | Spacer>
1712 <*KIT>
1713 \TitlePageStyle{KIT}
1714 \maketitle[%]
1715   mainlogo=\textcolor{red}{%
1716     \includegraphics[width=40mm,height=18.5mm]{KITLogo_RGB}}},%
1717   % You may additionally change titlehead. Original definition of titlehead
1718   % is:
1719   titlehead=\usetitleelement{mainlogo}\hspace*\fill},%
1720   title=\textcolor{red}{Titel der Arbeit\im Stil \texttt{KIT}}},%
1721   subject=\textcolor{red}{Klassifizierung der Arbeit},%
1722   author=\textcolor{red}{Markus~Kohm},%
1723   faculty=\textcolor{red}{Fakultät für Informatik},%
1724   chair=\textcolor{red}{%
1725     Institute for Program Structures\and Data Organization (IPA)},%
1726   advisor=\textcolor{red}{Titel Vorname Nachname}\and
1727     \textcolor{red}{Titel Vorname Nachname}},%
1728   referee=\textcolor{red}{Titel Vorname Nachname}\and
1729     \textcolor{red}{Titel Vorname Nachname}},%
1730   duration=\textcolor{red}{XX. Monat 20XX -- XX. Monat 20XX},%
1731   university=\textcolor{red}{\KITlongname},%
1732   homepage=\textcolor{red}{\KITurl}}
1733 ]
1734 </KIT>
1735 <*JT-Aufsaetze>
1736 \TitlePageStyle{JT-Aufsaetze}
1737 \maketitle[%]
1738   % There are only three official elements:
1739   author=\textcolor{red}{Markus Kohm},%
1740   title=\textcolor{red}{Titel der Arbeit angelehnt an Jan Tschicholds
1741     ausgewählte Aufsätze über Fragen der Gestalt des Buches und der
1742     Typographie}},%
1743   titlefont=\normalfont,% You may change the font of the main title
1744   publisher=\textcolor{red}{Der Verlag}
1745   % Nevertheless, you may use extratitle, lowertitleback and uppertitleback.
1746   % See Markus-2 for more information about those.
1747 ]
1748 </JT-Aufsaetze>
1749 <*JT-Geschichte>
1750 \TitlePageStyle{JT-Geschichte}
1751 \maketitle[%]
1752   % There are only four official elements:
1753   author=\textcolor{red}{Markus Kohm},%

```

```

1754 title={\textcolor{red}{Titel der Arbeit angelehnt an Jan Tschicholds
1755     Geschichte der Schrift in Bildern}},
1756 titlefont=\itshape,% You may change the font of the main title
1757 publisher={\textcolor{red}{Der Verlag in seiner Langform}},
1758 place={\textcolor{red}{Der Ort}}
1759 % Nevertheless, you may use extratitle, lowertitleback and uppertitleback.
1760 % See Markus-2 for more information about those.
1761 ]
1762 </JT-Geschichte>
1763 <*JT-Typography>
1764 \TitlePageStyle{JT-Typography}
1765 \maketitle[%]
1766 % There are only four official elements:
1767 author={\textcolor{red}{Markus Kohm}},%
1768 title={\textcolor{red}{Titel der Arbeit}},%
1769 subtitle={\textcolor{red}{angelehnt an the new Typography}},%
1770 publisher={\textcolor{red}{Veröffentlicht für einen Verlag oder auch nicht}},%
1771 place={\textcolor{red}{Der Ort}},%
1772 date={\textcolor{red}{2012}}%
1773 % Nevertheless, you may use extratitle, lowertitleback and uppertitleback.
1774 % See Markus-2 for more information about those.
1775 ]
1776 </JT-Typography>
1777 <*WWUM>
1778 \TitlePageStyle{WWUM}
1779 \renewcaptionname{ngerman}{\examinationdatename}{Tag der Promotion}
1780 \% \renewcaptionname{ngerman}{\examinationdatename}{}
1781 \% \renewcaptionname{ngerman}{\chairmannname}{Dekan}
1782 \% \renewcaptionname{ngerman}{\chairmannname}{Dekanin}
1783 \maketitle[%]
1784 title={\textcolor{red}{Titel der Arbeit}},%
1785 subject={\textcolor{red}{Inaugural-Dissertation}},%
1786 academicgrade={\textcolor{red}{Doktorgrades}},%
1787 discipline={\textcolor{red}{Physik}},%
1788 science={\textcolor{red}{Naturwissenschaften}},%
1789 chair={\textcolor{red}{Experimentelle Physik}},%
1790 faculty={\textcolor{red}{Mathematisch-Naturwissenschaftlichen}},%
1791 author={\textcolor{red}{Mein Name}},%
1792 place={\textcolor{red}{Geburtsort}},%
1793 referee={\textcolor{red}{Peter Mustermann}}\and
1794 [f]\textcolor{red}{Petra Musterfrau}},%
1795 professor={\textcolor{red}{Klaus Naseschwarz}}
1796 ]
1797 </WWUM>
1798 <*UKoLa>
1799 \TitlePageStyle{UKoLa}
1800 \maketitle[%]
1801 titlefont=\sffamily,
1802 mainlogo=\textcolor{red}{{
1803     \includegraphics[height=10mm,width=63mm]%
1804     {uni-koblenz-landau}%
1805 }},%
1806 chair=\textcolor{red}{Nummer des Instituts:},
1807 Name des Instituts},

```

```

1808 secondlogo=\textcolor{red}{Optionales weiteres Logo},
1809 title=\textcolor{red}{Titel der Studien-, Bachelor-, Master- oder Diplomarbeit},
1810 subject=\textcolor{red}{Diplomarbeit},
1811 academicgrade=\textcolor{red}{Diplom-Informatikers},
1812 discipline=\textcolor{red}{Name des Studiengangs},
1813 place=\textcolor{red}{Koblenz}),
1814 author=\textcolor{red}{Vorname und Nachname des Absolventen / der
1815 Absolventin},
1816 advisor=\textcolor{red}{Title{}}
1817 Vorname{}
1818 Name,
1819 Institut, Fachbereich innerhalb der Universität /
1820 Institution außerhalb der Universität},
1821 referee=\textcolor{red}{Title{}}
1822 Vorname{}
1823 Name,
1824 Institut, Fachbereich innerhalb der Universität /
1825 Institution außerhalb der Universität}%
1826 \and[f]\textcolor{red}{Title{}}
1827 Vorname{}
1828 Name,
1829 Institut, Fachbereich innerhalb der Universität /
1830 Institution außerhalb der Universität}%
1831 },%
1832 date=\textcolor{red}{Abgabemonat},
1833 ]
1834
1835 //UKoLa
1836 \end{document}

1837 (*!README)
1838 \documentclass{ltxdoc}
1839 \IfPackageAtLeastTF{doc}{2022/01/01}{}{%
1840   \errhelp{To avoid this error message, use doc.sty v3 instead of v2}%
1841   \errmessage{Package `doc' is to old!}%
1842 }
1843 \usepackage[english]{babel}
1844 \usepackage{xltabular}
1845 \usepackage{ragged2e}
1846 \usepackage{booktabs}
1847 \usepackage{graphicx}
1848 \usepackage{hvlogos}
1849 \newcommand*\NewIn[1]{\leavevmode\marginpar{\footnotesize\hfill added in #1}}
1850 \newcommand*\ChangedIn[1]{\leavevmode\marginpar{\footnotesize\hfill changed in
1851      #1}}
1852 \NewDocElement[macrolike = true,
1853               toplevel = false,
1854               idxtype = ,
1855               idxgroup = User commands,
1856               printtype =
1857               ]{InterfaceMacro}{imacro}
1858 \NewDocElement[macrolike = false,
1859               toplevel = false,
1860               idxtype = opt.,
1861               idxgroup = Title options,

```

```

1862         printtype = \textit{opt.}
1863         ]{Option}{option}
1864 \NewDocumentCommand{\pkg}{s0{https://www.ctan.org/pkg/#3}m}{%
1865   \IfBooleanTF{#1}{\gobble}{%
1866     \csname tl_if_blank:nTF\endcsname{#2}{\gobble}{\href}%
1867   }%
1868   {#2}{\textsf{#3}}%
1869 }
1870 \newcommand*{\File}{\texttt}
1871 \CodelineIndex
1872 \RecordChanges
1873 \EnableCrossrefs
1874 \GetFileInfo{uni-titlepage.drv}
1875 \begin{document}
1876 \title{More Titlepage Styles with Package \pkg{uni-titlepage}}
1877 \author{\href{mailto:komascript@gmx.info}{Markus Kohm}}
1878 \date{\fileversion{} \filedate}
1879 \maketitle
1880 \begin{abstract}
1881 //!README
1882 /*README}
1883 -----
1884
1885 This work may be distributed and/or modified under the conditions of
1886 the LaTeX Project Public License, version 1.3c of the license.
1887 The latest version of this license is in
1888   http://www.latex-project.org/lppl.txt
1889 and version 1.3c or later is part of all distributions of LaTeX
1890 version 2005/12/01 or later.
1891
1892 This work has the LPPL maintenance status "maintained".
1893
1894 The Current Maintainer and author of this work is Markus Kohm.
1895
1896 -----
1897
1898 # ABSTRACT
1899
1900 /*README}
1901 Creation of title pages is something most authors should not have to do.
1902 But reality is not perfect, so a lot of authors have to do it. In 2009
1903 /*README}KOMA started the title page project at \url{https://komascript.de/titlepage}
1904 /*README}KOMA started the title page project at <https://komascript.de/titlepage>
1905 to collect real title pages and implement them with a well defined interface.
1906 /*README}In 2021 the project has been moved to \url{https://github.com/komascript/uni-titlepage}
1907 /*README}In 2021 the project has been moved to <https://github.com/komascript/uni-titlepage>
1908 and renamed.
1909
1910 Now, changing from one title page style to another would be very
1911 simple. Nevertheless implementation of a new title page style may be still
1912 difficult. But maybe the guys of the title page project would help you. Just
1913 ask!
1914 /*README}
1915

```

```

1916 # Unpacking and Installation for Developers and Distributors
1917
1918 To unpack and install all files, you can download the source from github
1919 and then run:
1920
1921     l3build install
1922
1923 Afterwards you can build the manual and the PDFs of the examples using:
1924
1925     l3build doc
1926
1927 As an alternative you can use the CTAN source distribution. This already
1928 contains the user manual and the PDFs of the example files. So you only have
1929 to run
1930
1931     tex uni-titlepage.dtx
1932
1933 to generate the package file ‘uni-titlepage.sty’, the title definition files
1934 ‘title-*.def’ and the example titlepages ‘titlepage-*.tex’.
1935
1936 Please note, the ‘title-*.def’ files are run-time files. Together with
1937 ‘uni-titlepage.sty’ they have to be placed in ‘tex/latex/uni-titlepage’ inside
1938 a TDS tree. All files ‘titlepage-*.tex’ and ‘titlepage-*.pdf’ as well as
1939 ‘uni-titlepage.pdf’ are part of the documentation and should be placed in
1940 ‘doc/latex/uni-titlepage/’ of the TDS tree.
1941
1942 # Unpacking and Installation for Users
1943
1944 Users can use the installation described at
1945 [Unpacking and Installation for Developers and Distributors]. However, if
1946 your TeX distributor already distributes a ready for installation package, you
1947 do not need and should not create files and copy them yourself. Just use the
1948 package manager of your TeX distribution to install the package.
1949
1950 # How to Contribute
1951
1952 If you have made a title definition that is not specific for a single project
1953 but could be of interest for other users, you can either
1954
1955 * make your own ‘uni-titlepage-FOO’ package with its own manual and [upload it
1956 to ctan](https://www.ctan.org/upload),
1957 * contribute in adding it to ‘uni-titlepage’.
1958
1959 The first option has the advantage, that you are free. There won’t be any code
1960 reviews by the ‘uni-titlepage’ developers. You don’t need to use the same
1961 coding style. There is not need to accept the license of ‘uni-titlepage’
1962 etc. But in this case you have to take care to keep it compatible with future
1963 releases of ‘uni-titlepage’ and it will not be presented in the
1964 ‘uni-titlepage’ manual.
1965
1966 The second option has the advantage, that after accepting your code, the
1967 ‘uni-titlepage’ developers will try to keep it working even if they change
1968 ‘uni-titlepage’. But there are several restrictions to your code, before it
1969 will be accepted. For example, you should always try to use general options,

```

1970 if possible. \*Static text\* (not handled by options) should be configurable via  
 1971 ‘\newcaptionname’, ‘\providetitlepage’ and ‘\renewcaptionname’ and should be  
 1972 available at least in English and German (but if we can, we help in  
 1973 translating them). The coding style and quality is also a criterion.  
 1974  
 1975 ⟨/README⟩  
 1976 ⟨!\*!README⟩  
 1977 \end{abstract}  
 1978 \DocInput{uni-titlepage.dtx}  
 1979 \end{document}  
 1980 ⟨//!README⟩

## Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols			
\" . . . . .	516, 517, 527, 529, 601, 611, 736, 804, 811, 816, 913, 914, 917, 924, 1610	998, 1001, 1006, 1022, 1034, 1039, 1086, 1094, 1100, 1193, 1210,	\@lowertitleback . . . . . 1387, 1419
\, . . . . .	1194, 1614, 1652	1221, 1297, 1300, 1322, 1333, 1343,	\@mainlogo 292, 938, 961, 976, 999, 1351
\@ . . . . .	361	1345, 1463,	\@makefnmark . . . 906, 907
\@academicgrade . . . . .	285	1485, 1494,	\@matriculationnumber . . . . . 286, 1149
\@advisor . . . . .	287, 1284, 1369	1518, 1523,	\@nameuse . . . . . 305
\@author . . . . .	250, 1104, 1147, 1230, 1297, 1317, 1339, 1523, 1530	1524, 1542, 1551 \@evenhead . . . . . 1018 \@extratitle . . . . . 1471, 1485, 1487, 1518	\@ne . . . . . 85, 539, 555, 574, 590, 1371, 1431, 1452
\@chair . . . . .	258, 767, 772, 777, 1136, 1352	\@faculty . . . . . 257, 1134	\@oddhead . . . . . 1014, 1018
\@company . . . . .	254	\@firstofone . . . . . 97, 375	\@oldmakefnmark 906, 907
\@course . . . . .	253	\@fnsymbol . . . . . 905	\@oralexaminationdate . . . . . 294, 1439, 1462
\@currext . . . . .	227, 237	\@gobble . . . . . 95,	\@place 289, 725, 732, 739, 922, 1160, 1193, 1333, 1334, 1343, 1379
\@currname . . . . .	227, 237	1244, 1246, 1247, 1248,	\@plus . . . . . 1053, 1109, 1546
\@date . . . . .	251, 1073, 1108, 1160, 1181, 1204, 1237, 1344, 1379	1250, 1251, 1253, 1254, 1255, 1298, 1299, 1303,	\@professor . . . . . 259, 1137, 1459
\@dedication . . . . .	295, 1542, 1545, 1551	1304, 1307, 1320, 1321, 1325, 1326,	\@publisher . . . . . 1110, 1236, 1313, 1332, 1345, 1346, 1494, 1498, 1524
\@discipline . . . . .	284, 1148	1329, 1865, 1866	\@referee 288, 1282, 1377, 1435, 1461
\@duration . . . . .	. . . . . 252, 1076, 1288	\@changefrom . . . . . 1369, 1373, 1432, 1439	\@restonecolfalse . . 121
\@empty . . . . .	123, 137, 316, 725, 732, 739, 910, 922, 938, 960, 965, 973, 976,	\@homepage 246, 973, 1292 \@ifundefined . . . . . . . . 1211, 1301, 1323	\@restonecoltrue . . 119 \@secondlogo . . . . . 293, 1355 \@science . . . . . 283 \@spaces . . . . . 620

\@subject . . . .	260,	730, 731, 736,	\askforoverwritefalse
748, 755, 762,		737, 738, 744,	. . . . . 11
1094, 1095,		745, 746, 747,	\AtBeginDocument . . . 377
1140, 1199,		751, 752, 753,	\atthename . . . . . 402
1229, 1267, 1361		754, 758, 759,	
\@subtitle . . . . .		760, 761, 766,	<b>B</b>
255, 1100, 1171,		767, 771, 772,	\baselineskip . . 214,
1202, 1234, 1341		776, 777, 782,	722, 724, 729,
\@subtitlefont . . . . .		783, 784, 785,	731, 736, 738,
. . . 349, 1100,		786, 791, 792,	1070, 1114,
1201, 1233, 1341		793, 794, 795,	1151, 1158,
\@tempa . . . . .	357, 363,	800, 801, 803,	1199, 1202,
1274, 1279, 1283		804, 1070, 1076,	1225, 1229,
\@tempb . . . . .	1275,	1078, 1079,	1231, 1234,
1278, 1279, 1283		1080, 1132,	1258, 1309,
\@tempcnta	1371, 1373,	1134, 1136,	1339, 1345,
1376, 1429,		1137, 1139,	1357, 1360,
1431, 1433,		1140, 1144,	1362, 1364,
1449, 1452, 1454		1147, 1148,	1365, 1378, 1528
\@thanks . . . . .	1113	1149, 1150,	\batchfile . . . . . 1
\@title . . . . .	249,	1153, 1156,	\begin . . . . . 167,
1139, 1170,		1170, 1171,	198, 1046, 1059,
1200, 1232,		1173, 1175,	1075, 1087,
1265, 1311,		1176, 1178,	1103, 1126,
1318, 1340, 1359		1179, 1185,	1146, 1155,
\@titlehead . . . .	243,	1187, 1189,	1242, 1260,
960, 998, 1060,		1191, 1192,	1281, 1298,
1086, 1088,		1193, 1230,	1320, 1350,
1221, 1223, 1262		1277, 1282,	1354, 1413,
\@titlepagefont . . . . .		1284, 1297,	1414, 1418,
. . . 330, 965,		1309, 1317,	1426, 1446,
966, 1001, 1002,		1331, 1334,	1458, 1486,
1006, 1007,		1339, 1340,	1495, 1505,
1015, 1022,		1341, 1345,	1518, 1524,
1023, 1026,		1351, 1352,	1525, 1537,
1028, 1039,		1355, 1365,	1543, 1551,
1040, 1055,		1456, 1459,	1574, 1875, 1880
1265, 1415,		1461, 1464,	\begingroup . . . . .
1419, 1497,		1466, 1510,	144, 356, 617, 1092
1506, 1527, 1577		1511, 1612,	\bfseries . . 339, 344,
\@tpf@extra . . . . .		1617, 1720, 1725	349, 1040, 1139,
. . . 1026, 1029,			1170, 1359, 1578
1317, 1332, 1334		\u . . . . . 1379	
\@university	256, 910,		<b>A</b>
1081, 1132, 1292		\advance . . . . . 173,	\c@footnote . . . . . 905
\@uppertitleback . . .		1371, 1431, 1452	\c@page . . . . . 204
. . 1388, 1389, 1415		\advanve . . . . . 171	\catcode . . . . . 361
\@uppertitlebacke	1387	\and . . . . . 1230, 1276,	\centering . . . 1058,
\@usetitleelement@error		1374, 1430,	1061, 1093,
. . . . . 298		1435, 1456,	1129, 1168,
\\"	703, 704, 705, 709,	1529, 1655,	1184, 1263,
710, 711, 715,		1677, 1726,	1296, 1316,
716, 717, 722,		1728, 1793, 1826	1358, 1509, 1545
723, 724, 729,		\arraystretch . . . 1450	\ChangedIn . . . . . 1850

\changes	700	1260,	1261,	229, 230, 231,
\clearpage	117	1291,	1299,	233, 291, 316,
\CodelineIndex	1871	1303,	1321,	571, 630, 1016,
\color	1211, 1301, 1323	1325,	1351, 1355	1204, 1230,
\colorlet	1572	\do	228, 262	1236, 1237,
\columnwidth	191	\DocInput	1978	1366, 1373,
\companyname	406, 463, 525, 1079, 1080	\documentclass	....	1454, 1455,
\coursesname	405, 461, 523, 1077	.....	1554, 1838	1530, 1545, 1866
\cs	700	\dp	1317, 1331, 1334	\endgroup
\csname	79, 229, 230, 231, 233, 291, 316, 630, 1016, 1204, 1230, 1236, 1237, 1366, 1373, 1454, 1455, 1530, 1545, 1866	\durationname	403, 457, 519, 1076, 1288	151, 357, 647, 1112
\CurrentOption	380	\edef	....	\endminipage
<b>D</b>		\else	96, 120, 123, 127, 130, 137, 139, 175, 210, 326, 376, 542, 544, 558, 560, 573, 577, 579, 593, 602, 612, 671, 725, 732, 739, 744, 748, 751, 755, 758, 762, 942, 989, 1086, 1094, 1100, 1122, 1193, 1210, 1221, 1297, 1300, 1322, 1333, 1343, 1345, 1463, 1485, 1494, 1518, 1523, 1542, 1551, 1563	\endpreamble
\DeclareOption	380	\enablecrossrefs	. 1873	\endtitlepage
\def	1, 100, 101, 618, 977, 978, 979, 980, 981, 982, 983, 984, 985, 1012, 1014, 1029, 1230, 1275, 1276, 1372, 1374, 1430, 1450, 1453, 1456, 1529	\end	197, 218, 1082, 1083, 1089, 1105, 1150, 1157, 1163, 1257, 1285, 1289, 1309, 1331, 1353, 1356, 1381, 1416, 1420, 1421, 1441, 1467, 1468, 1488, 1499, 1513, 1518, 1524, 1531, 1537, 1547, 1551, 1836, 1977, 1979	\englishordinalmalereferencename
\DefineFamily	81			..... 536
\DefineFamilyKey	.. ..... 86, 91, 232, 238, 245, 248, 263, 297, 335, 340, 345, 350, 675, 684, 1390, 1401, 1474	\familyboolkey	663, 664	
\DefineFamilyMember	..... 82, 648	\familykeystateprocessed	87, 92, 234, 245, 248, 279, 297, 337, 342, 347, 352, 682, 691, 1398, 1409, 1481	
\dimexpr	..... 681, 690, 1059, 1075, 1126, 1127, 1209, 1213, 1215, 1218, 1222, 1244, 1246, 1247, 1248, 1250, 1251, 1253, 1254, 1255, 1258,	\familyoption	84	
		\familyoptions	83, 240	
		\familyprocessoptions	..... 381	
		\familystringkey	693	
		\fbox	..... 1121	
		\fboxrule	..... 1120	
		\fe@male	1372, 1373,	
		\endcsname	.. 79, 94, 1453, 1454, 1455	

```

\fi ..... 98, 122,
123, 129, 133,
134, 135, 137,
139, 147, 148,
149, 186, 212,
328, 378, 548,
549, 564, 565,
585, 586, 587,
595, 605, 615,
646, 671, 725,
732, 739, 744,
748, 751, 755,
758, 762, 919,
936, 942, 957,
962, 970, 975,
989, 997, 1000,
1003, 1008,
1033, 1036,
1041, 1090,
1097, 1100,
1124, 1127,
1193, 1212,
1226, 1302,
1310, 1324,
1335, 1343,
1347, 1436,
1440, 1465,
1489, 1500,
1518, 1524,
1532, 1537,
1548, 1551, 1568
\File ..... 1870
\file 39, 40, 41, 42, 43,
44, 45, 46, 47,
48, 49, 50, 51,
52, 53, 54, 55,
56, 57, 58, 59,
60, 61, 62, 63,
64, 65, 66, 67, 69
\filedate ..... 1878
\fileversion ..... 1878
\fill . 961, 999, 1427,
1447, 1589, 1719
\fontsize ..... .
.. 1131, 1133, 1135
\footnote ..... 904
\footnoterule ..... 903
\footnotesize . .
.. 902, 1849, 1850
\from 39, 40, 41, 42, 43,
44, 45, 46, 47,
48, 49, 50, 51,
52, 53, 54, 55,
56, 57, 58, 59,
60, 61, 62, 63,
64, 65, 66, 67, 69
\fullsizetitle (env.) 23
\gdef ..... 231,
244, 247, 261,
296, 681, 690,
1389, 1400, 1473
\generate ..... 38
\GenericError ..... 619
\geometry ..... 183
\GetFileInfo ..... 1874
\global 1283, 1371, 1452
\Gm@bindingoffset .
\iffinal ..... 744,
748, 751, 755,
758, 762, 1428, 1438
\ifevenodd ..... 23
\IfPackageAtLeastTF
\ifnum ..... 1839
\ifstr ..... 281
\ifToplevel ..... 3, 72
\iftutex ..... 1557
\ifx ..... 123, 137,
316, 630, 725,
732, 739, 910,
922, 938, 960,
965, 973, 976,
998, 1001, 1006,
1022, 1034,
1039, 1086,
1094, 1100,
1193, 1210,
1221, 1297,
1300, 1322,
1333, 1343,
1345, 1463,
1485, 1494,
1518, 1523,
1524, 1542, 1551
\ignorespaces ..... .
.... 767, 772,
777, 1132, 1134,
1136, 1137,
1139, 1140,
1144, 1147,
1148, 1149,
1153, 1156,
1160, 1170,
1171, 1175,
1176, 1178,
1179, 1199,
1200, 1202,
1204, 1229,
1232, 1234,
1237, 1498, 1530
\includegraphics 947,
951, 993, 1584,
1689, 1716, 1803
\input ..... 2, 360
\itshape ... 1023, 1756
\IfFileExists ..... .
.... 355, 939,
\keepsilent ..... 10

```

\kern . . . . .	1215	1630,	1646,	\noexpand . . . . .
\KIT@logo . . .	977,	1666,	1683,	. 358, 359, 360, 361
978, 979,	980,	1714,	1737,	\noindent 194, 1448, 1487
981, 982,	983,	1751,	1765,	\nopostamble . . . . . 68
984, 985,	987, 993	1783,	1800, 1879	\nopreamble . . . . . 68
\KOMAoptions . . .	181	\MakeUppercase	1029,	\normalfont . . . . . 967,
<b>L</b>		1339,	1340,	968, 1007, 1023,
\l@addto@macro	228, 262	1341,	1343,	1026, 1029,
\LARGE . . . .	1170,	1344,	1346, 1572	1035, 1040,
1200,	1232,	\marginpar	. 1849, 1850	1577, 1662,
1344, 1359,	1529	\matriculationnumbername	404, 459, 521, 1077	1663, 1667, 1743
\Large . . .	1062, 1064,	\mbox	. . . . . 1123	\normalsize . 1341, 1343
1066,	1102,	\MessageBreak	. 177,	\null . . . . . 128,
1108,	1110,	178, 179, 180,		132, 1091, 1114,
1171,	1173,	181, 183, 222,		1518, 1528,
1175,	1178,	312, 319, 320,		1537, 1544, 1551
1181,	1267,	322, 323, 368,		\numexpr . . . . . 1278
1271,	1273,	582, 625, 626, 931		
1339, 1361,	1366	\minipage	. . . . . 194	<b>O</b>
\large . . .	1007, 1199,	\Msg	. . . . . 4, 5, 6, 7, 8,	\oddsidemargin . . . . . 205
1202,	1204,	9, 73, 74, 75, 76, 77		\onecolumn . . . . . 119
1229,	1230,			\or . . . . . 543, 544, 559,
1234,	1236,			560, 578, 579,
1237,	1288,			601, 602, 611, 612
1292,	1317,			\ordinalfemalecorrectorname
1498, 1528,	1530			. . . . . 861
\leavevmode	202, 1119,			\oval . . . . . 1246, 1253
1228,	1849, 1850			
\let . . .	249, 250, 251,			<b>P</b>
255,	902, 903,			\PackageError . . . . .
904, 906,	1018,			. . . . . 310, 317,
1026,	1274, 1283			366, 540, 545,
\line	1244, 1248, 1251,			556, 561, 575,
1255,	1304,			580, 591, 599,
1307, 1326,	1329			603, 609, 613, 929
\linebreak . . . .	1529			\PackageInfo . . . . . 104
\lineskip . . . .	1102			\PackageNotLoadedError
\linespread . . . .	1054			. . . . . 618, 631
\linethickness	1304,			\PackageWarning 176, 221
1307, 1326,	1329			\paperheight . . . . .
\linewidth	190, 1075,			. . . . . 189, 1248,
1127,	1143,			1250, 1253,
1145,	1152,			1254, 1255, 1260
1154,	1159, 1223			\paperwidth 168, 1244,
\lsstyle . . . . .	1029			1246, 1247,
<b>M</b>				1251, 1261, 1291
\makeatletter	359, 1577			\par 1060, 1064, 1066,
\makeatother . . . .	1577			1068, 1071,
\makebox . . .	215, 1291			1073, 1089,
\maketitle . . . . .				1095, 1098,
102, 143,	1579,			1100, 1105,
1607,	1626,			1108, 1110,
				1117, 1161,
				1199, 1200,

1202,	1204,	344, 349, 382,	836, 837, 840,
1224,	1229,	383, 384, 385,	841, 844, 845,
1230,	1232,	386, 387, 388,	848, 849, 859,
1234,	1236,	389, 390, 391,	860, 864, 865,
1237,	1257,	392, 393, 394,	867, 871, 872,
1262,	1265,	395, 396, 397,	874, 878, 879,
1267,	1269,	398, 399, 400,	881, 885, 886,
1271,	1285,	401, 402, 403,	888, 892, 893,
1288,	1311,	404, 405, 406,	895, 1779, 1780,
1318,	1356,	407, 408, 412,	1781, 1782, 1971
1359,	1361,	666, 670, 674,	\renewcommand ... 90,
1363,	1366,	702, 721, 743,	92, 143, 154,
1369,	1374,	765, 781, 1044,	155, 156, 157,
1377,	1379,	1388, 1389,	158, 159, 160,
1416,	1431,	1399, 1400,	161, 291, 336,
1498,	1530, 1545	1472, 1473, 1577	341, 346, 351,
\parbox	1015, 1217, 1223	\ps@empty .....	900, 905, 907,
\parfillskip	.... 1053	\ps@maintitle .....	966, 1002, 1007,
\parindent	.... 1052	\put 1243, 1246, 1247,	1023, 1026,
\parskip	.... 1051	1250, 1253,	1028, 1035,
\pkg	1864, 1876	1254, 1303,	1040, 1045,
\preamble	.... 14	1306, 1325, 1328	1412, 1425,
\presentationinformationUKoLa			1445, 1484,
	702, 708, 714, 1363		1493, 1504,
\protect	... 1655, 1677	\quad .....	1517, 1522,
\providetcaptionname			1536, 1541, 1550
	.... 413, 415,		\renewenvironment . 115
	417, 419, 422,	\raggedleft . 1496, 1526	\RequirePackage ...
	424, 426, 428,	\raggedright .. 201,	.... 80, 942, 989
	431, 433, 435,	1142, 1197,	\rlap .....
	437, 439, 441,	1207, 1219,	907
	443, 445, 447,	1262, 1338, 1368	\rule .....
	450, 453, 456,	\raisebox .... 1209,	1117, 1213
	458, 460, 462,	1222, 1351, 1355	
	464, 466, 469,	\RecordChanges ... 1872	<b>S</b>
	471, 473, 475,	\relax .... 249, 250,	\scr@ifundefinedorrelax
	477, 479, 481,	251, 255, 381,	.... 100,
	483, 485, 487,	630, 681, 690,	101, 169, 170,
	489, 491, 493,	903, 1059, 1075,	174, 206, 207,
	495, 497, 499,	1126, 1127,	299, 302, 330,
	501, 503, 505,	1209, 1213,	819, 823, 827,
	507, 510, 513,	1215, 1218,	831, 835, 839,
	515, 518, 520,	1222, 1244,	843, 847, 858,
	522, 524, 526,	1248, 1250,	863, 870, 877,
	528, 530, 707,	1251, 1253,	884, 891, 941,
	713, 727, 734,	1254, 1255,	944, 988, 991, 1025
	749, 756, 769,	1258, 1260,	\scshape .....
	774, 789, 798,	1261, 1278,	1026
	809, 814, 856, 1971	1291, 1299,	\selectfont ... 1054,
\providecommand	...	1303, 1321, 1325	1131, 1133, 1135
	.. 89, 102, 243,	\renewcaptionname ..	\setcounter . 85, 87, 136
	244, 246, 247,	.... 820, 821,	\setkomafont .....
	260, 261, 281,	824, 825, 828,	.. 1578, 1662, 1663
	295, 296, 339,	829, 832, 833,	\setlength 1051, 1052,
			1053, 1120, 1241
			\setmainfont .....
			1560
			\setsansfont .....
			1561

\sffamily	967, 1040, 1128, 1167, 1577, 1578, 1580, 1662, 1663, 1667, 1801	1597, 1599, 1601, 1608, 1611,	1598, 1600, 1602, 1609, 1612,	\textit{ ... } 1862 \textsf{ ... } 1868 \texttt{ ... } 1608, 1631, 1634, 1638, 1640, 1641, 1648, 1668, 1673, 1675, 1676, 1685, 1691, 1698, 1702, 1705, 1720, 1870
\small	... 902	1614,	1617,	\textwidth{ ... } 192, 668, 1087, 1218, 1414, 1418
\space	... 73, 182, 311, 324, 725, 732, 739, 1454	1618, 1620, 1622,	1619, 1621, 1631,	\thanks{ ... } 904
\stepcounter	... 140	1632,	1633,	\the{ ... } 181, 183, 361, 1194, 1278, 1433, 1512
\string	... 181, 183, 311, 324, 932	1634, 1636,	1635, 1637,	\thefootnote{ ... } 905
\strut	... 324, 325, 767, 772, 777, 1132, 1134, 1136, 1137, 1139, 1140, 1144, 1147, 1148, 1149, 1153, 1156, 1160, 1170, 1171, 1175, 1176, 1178, 1179, 1199, 1200, 1202, 1204, 1229, 1232, 1234, 1237, 1317, 1334, 1339, 1340, 1341, 1345, 1498, 1529	1639, 1648, 1651, 1653, 1655, 1668, 1670, 1672, 1676, 1685, 1691, 1695, 1697, 1705, 1715, 1721, 1723, 1726, 1728, 1730, 1732, 1740, 1753, 1757, 1767, 1769, 1771, 1784, 1786, 1788, 1790, 1792, 1794, 1802, 1808, 1810, 1812, 1814, 1821,	1641, 1649, 1652, 1654, 1657, 1669, 1671, 1674, 1677, 1689, 1694, 1696, 1701, 1708, 1720, 1722, 1724, 1727, 1729, 1731, 1739, 1744, 1754, 1758, 1768, 1770, 1772, 1785, 1787, 1789, 1791, 1793, 1795, 1806, 1809, 1811, 1813, 1816, 1826,	\thispagestyle{ ... } ... 123, 137, 1208 \tiny{ ... } 1292
Title options:				
				academicgrade ... 285 advisor ... 287 author ... 250 blackborder ... 663 chair ... 258 company ... 254 course ... 253 date ... 251 dedication ... 295 discipline ... 284 duration ... 252 extratitle ... 1471 faculty ... 257 final ... 664 homepage ... 246 lowertitleback ... 1387 mainlogo ... 292 matriculationnumber ... ... 286 oralexaminationdate ... ... 294
T				
\ta@bcor	... 173, 175, 181, 183, 209	1788,	1789,	pagenumber ... 85
\tabcolsep	... 1075	1790,	1791,	pagestyle ... 89
\test@male@female	... 1370, 1374, 1377	1792,	1793,	place ... 289
\test@malefemale	... 1451, 1456, 1460	1794, 1802, 1808,	1795, 1806, 1809,	professor ... 259
\textbf	... 1292	1810,	1811,	publisher ... 290
\textcolor	... 1572, 1581, 1590, 1591, 1592,	1812, 1814,	1813, 1816,	referee ... 288
	1593, 1594, 1595, 1596,	1821, 193, 1126, 1209, 1826, 1832, 1213, 1215, 1217	1826, 1832, 1213, 1215, 1217	rulecolor ... 665 rulesep ... 665 rulewidth ... 665 secondlogo ... 293

sience .....	283	1334, 1339,	\exittitle .....
student .....	282	1340, 1341, 1345	.... 103, 150, 161
subject .....	260	\url .....	\extratitle ... 1471
subjectfont .....	339	\usebox .....	\faculty .....
subtitle .....	255	\usefont .....	\femaleordinal . 382
subtitlefont .....	349	\usepackage .....	\femalerefereeename
title .....	249	.... 1555, 1556,	..... 382
titlefont .....	344	1559, 1564,	\fromname .....
titlehead .....	243	1565, 1566,	.... 382, 808,
titlepagefont .....	330	1567, 1569,	1070, 1175, 1267
university .....	256	1570, 1571,	\fromplacename ..
uppertitleback .....	1387	1573, 1843,	.... 382, 1178, 1193
\title@font .....	344	1844, 1845,	\fullsizetitle . 164
\title@rulecolor .....	665, 1210,	1846, 1847, 1848	\germanfemaleordinal
.... 1211,	1300,	User commands:	..... 490, 589
1301, 1322, 1323		\academicgrade . 285	\germanmaleordinal
\title@rulesep .....	665, 1215,	\advisor .....	..... 492, 589
.... 1218,	1299,	\advisorname ...	\germanordinal .
1303, 1321, 1325		.... 382, 1080, 1153,	.... 488, 589
\title@rulewidth .....	665, 1214,	1283, 1284, 1369	\germanordinalfemalecorrectorname
.... 1218,	1298,	\author .. 250, 1877	.... 567, 868,
1304, 1307,		\bachelorthesisname	875, 882, 889, 896
1320, 1326, 1329		.... 270, 382	\germanordinalfemalerefereeename
\titlebox .....	164	\chair .....	.... 512, 551
\titlefont .....	344, 346, 1034,	\chairmanname ..	\germanordinalmalecorrectorname
.... 1035,	1064,	.... 382,	.... 554, 568, 866,
1098,	1200,	1459, 1781, 1782	873, 880, 887, 894
1232,	1311,	\company .....	\germanordinalmalerefereeename
1318,	1340, 1359	254	.... 509, 538
\titlepage .....	100	\course .....	\homepage .. 246, 974
titlepage (env.)	23, 100	253	\Ifstr . 264, 265,
\topmargin .....	199	\date .... 251, 1878	266, 267, 268,
\topskip .....	200	\dedication .... 295	269, 270, 281,
\totalheight .....	1222	\DefineReplaceTitleKey	1372, 1379, 1453
\tp@dokeys .....	220, 262	.... 220, 282	\indatename 382, 1379
\tp@replacewarning ..	220	\DefineSimpleTitleKey	\inittitle .....
\tp@undefinedtitle ..	103, 155, 156,	.... 220,	.... 103, 146, 154, 900
.... 157, 158, 159,	160	249, 250, 251,	\inittitlestyle
\twocolumn .....	139	252, 253, 254,	.... 114, 358
U		255, 256, 257,	\KITlongname ...
\unitlength .....	1241	258, 259, 283,	.... 808, 916, 1731
\unskip .....	1132,	284, 285, 286,	\KITurl 808, 974, 1732
.... 1134,	1136,	287, 288, 289,	\lowertitleback 1387
1137,	1139,	290, 292, 293, 294	\mainlogo .....
1140,	1144,	\degreethesisname	.... 292, 945, 992
1147,	1148,	.... 268, 382	\makemaintitle .
1149,	1153,	\diplomathesisname	.... 103, 148, 157, 1045
1156,	1317,	.... 267, 382	\makemaintitleback
		\discipline .... 284	.... 103, 148, 158, 1411
		\duration .... 252	\englishordinalfemalerefereeename
		\englishordinal	.... 400, 452, 535
		.... 409, 432, 533, 570	\englishordinalposttitle .
		\englishordinalmalerefereeename	.... 103, 149, 159, 1540
		\englishordinalposttitleback	.... 399, 449, 532
			.... 103, 149, 160, 1540

\makepretitle ..	\seminarpapername .....	23,
103, 147, 155, 1483	..... 265, 382	298, 327, 1589, 1719
\makepretitleback .....	\science .....	<b>V</b>
103,	..... 382	\value 125, 126, 131, 136
147, 156, 1483,	\subject .....	\vbox .....
1517, 1522, 1536	\subtitle .....	213
\maketitle .....	\thename .. 382, 1160	\vfill .. 1063, 1065,
\maleordinal ... 382	\title .. 249, 1876	1067, 1069,
\malerefereeename 382	\titlehead .....	1072, 1074,
\masterthesisname .....	.... 243, 961, 999	1091, 1114,
269, 382	\TitleOption .. 2, 80	1138, 1141,
\matriculationnumber .....	\TitleOptions ..	1188, 1190,
286	\TitlePageStyle ..	1203, 1235,
\NowButAfterBeginDocument .....	... 2, 80, 116,	1287, 1312,
.... 23, 373, 854	145, 166, 364, 1625	1319, 1342,
\ofthename .....	\TitleStyle .. 2, 354,	1367, 1417, 1544
.. 382, 1080, 1081	..... 380, 1576, 1606,	\vsizer .....
\oralexaminationdate .....	1629, 1645,	189, 193, 1059, 1507
294	1665, 1681,	\vskip .....
\oralexaminationdatename .....	1682, 1713,	199,
.. 382, 1439, 1462	1736, 1750,	200, 214, 1096,
\ordinal .....	1764, 1778, 1799	1099, 1101,
.. 382, 1279, 1433	\titlepagestyle .....	1107, 1109,
\ordinalfemalerefereeename .....	.... 89, 123, 137	1111, 1114,
382, 853	\ordinalmalerefereeename .....	1130, 1151,
\place . 289, 923, 932	\university .. 256, 911	1158, 1199,
\presentationinformationDHBW .....	\uppertitleback .. 1387	1202, 1225,
.... 700, 1068	\usenonemptytitleelement .....	1229, 1231,
\presentationinformationKIT .....	23, 315,	1234, 1258,
.... 700, 1271	704, 705, 710,	1264, 1266,
\presentationinformationTUHH .....	711, 716, 717,	1268, 1270,
.... 700, 1173	723, 724, 725,	1272, 1290,
\presentationinformationUKoLA .....	730, 731, 732,	1437, 1528, 1546
.... 700	737, 738, 739,	\vspace .....
\presentationinformationWWUM .....	745, 747, 752,	199, 1057,
.... 700, 1189	754, 759, 761,	1162, 1169,
\presentedbyname .....	766, 771, 776,	1172, 1174,
.... 382, 853,	782, 784, 785,	1177, 1180,
1144, 1191, 1365	786, 787, 791,	1186, 1357,
\professor .....	793, 794, 795,	1360, 1362,
259	796, 800, 801,	1364, 1378,
\projectpapername .....	802, 803, 804,	1427, 1447, 1507
264, 382	805, 1064, 1066,	\vss .....
\publisher .. 290, 1044	1071, 1077,	216
\publishers ... 1044	1078, 1079,	<b>X</b>
\referee .....	1080, 1081,	\xdef .....
288	1098, 1156,	1278, 1283
\refereeename .....	1176, 1179,	<b>Y</b>
382, 808, 1081,	1185, 1187,	\year .....
1274, 1282, 1433	1192, 1269,	1194, 1512
\secondlogo .....	1366, 1510, 1511	<b>Z</b>
293	\usetitleelement .....	\z@ .. 213, 671, 1051,
		1052, 1053,
		1109, 1376,
		1429, 1449, 1546

## Change History

0.5e	\presentationinformationDHBW: \if replaced by \ifx . . . . .	40	provide sevaral English and German languages . . . . .	42
v0.1	General: Start of project . . . . .	24	\KITlongname: \NowButAfterBeginDocument not needed any more . . . . .	42
v0.2	General: First version using docstrip . . . . .	24	provide sevaral English and German languages . . . . .	42
	new style DHBW . . . . .	38	\maleordinal: added . . . . .	34
	new style Spacer . . . . .	38	\malerefereename: added . . . . .	34
v0.2a	\makemaintitle: Markus-2: \leavevmode added before \subject@font to avoid line break after \subject@font using package color or xcolor .	47	\presentationinformationDHBW: \NowButAfterBeginDocument not needed any more . . . . .	40
	\makepretitle: Markus-1: Usage of \@titlepagefont fixed .	55	provide sevaral English and German languages . . . . .	40
v0.3	General: new style KIT . . . . .	38	\presentationinformationKIT: \NowButAfterBeginDocument not needed any more . . . . .	40
	\@homepage: added . . . . .	29	provide sevaral English and German languages . . . . .	40
	\homepage: added . . . . .	29	\presentationinformationTUHH: \NowButAfterBeginDocument not needed any more . . . . .	40
	homepage: added . . . . .	29	provide sevaral English and German languages . . . . .	40
v0.4	General: new style JT-Aufsaetze .	38	\presentationinformationWWUM: new style WWUM . . . . .	40
	new style JT-Geschichte .	38	\presentedbyname: changed value for WWUM . . . . .	43
	new style JT-Typography .	38	\refereename: \NowButAfterBeginDocument not needed any more . . . . .	42
	\@mainlogo: added . . . . .	31	provide sevaral English and German languages . . . . .	42
	\@usetitleelement@error: added	32	\sience: added . . . . .	31
	\mainlogo: added . . . . .	31	\sience: added . . . . .	31
	\mainlogo: added . . . . .	31	v0.5a	
	\@usetitleelement: added . . .	32	\presentedbyname: fixed swissgerman instead of swiss	43
v0.4a	\makemaintitle: fix influence of height of titlehead to vertical alignment of rule . . . . .	50	v0.5b	
v0.4b	\makepretitle: Markus-1: publisher page may be omitted	55	\presentedbyname: changes have to be delayed . . . . .	43
v0.4c	\subject: typing error fixed (mrpiggi) . . . . .	30	v0.5c	
v0.5	\@sience: added . . . . .	31	\advisorname: not needed \AtBeginDocument removed . .	34
	\chairmanname: added . . . . .	34	\bachelorthesisname: not needed \AtBeginDocument removed . .	34
	\femaleordinal: added . . . . .	34	\chairmanname: not needed \AtBeginDocument removed . .	34
	\femalerefereename: added . . .	34	\degreethesisname: not needed \AtBeginDocument removed . .	34
	\fromname: \NowButAfterBeginDocument not needed any more . . . . .	42		

\diplomathesisname: not needed		\academicgrade: renamed “degree”
\AtBeginDocument removed ..	34	to “academic grade” to avoid
\femaleordinal: not needed		name clash with the degree
\AtBeginDocument removed ..	34	symbol ..... 31
\femalerefereename: not needed		\academicgrade: renamed “degree”
\AtBeginDocument removed ..	34	to “academic grade” to avoid
\fromname: not needed		name clash with the degree
\AtBeginDocument removed ..	34	symbol ..... 31
\fromplacename: not needed		v0.7
\AtBeginDocument removed ..	34	General: don’t use <code>inputenc</code> any
\malerefereename: not needed		longer ..... 57
\AtBeginDocument removed ..	34	new style UKoLa ..... 22
\masterthesisname: not needed		\@secondlogo: added ..... 31
\AtBeginDocument removed ..	34	\englishordinalfemalerefereename:
\ofthename: not needed		added ..... 36
\AtBeginDocument removed ..	34	\englishordinalmalerefereename:
\oralexaminationdatename: not		added ..... 36
needed \AtBeginDocument		\germanordinalfemalecorrectorname:
removed ..... 34		added ..... 37
\ordinal: not needed		\germanordinalfemalerefereename:
\AtBeginDocument removed ..	34	added ..... 37
\presentedbyname: not needed		\germanordinalmalecorrectorname:
\AtBeginDocument removed ..	34	added ..... 37
\projectpapername: not needed		\germanordinalmalerefereename:
\AtBeginDocument removed ..	34	added ..... 37
\refereename: not needed		\indatename: added ..... 34
\AtBeginDocument removed ..	34	\ordinalfemalerefereename:
\seminarpapername: not needed		added ..... 34
\AtBeginDocument removed ..	34	changed value for UKoLa ..... 43
\studentreserchname: not needed		\ordinalmalerefereename: added ..... 34
\AtBeginDocument removed ..	34	changed value for UKoLa ..... 43
\thename: not needed		\presentationinformationUKoLA:
\AtBeginDocument removed ..	34	added ..... 40
v0.5e		\presentedbyname: changed value
\makemaintitleback: \ifstr in		also for UKoLa ..... 43
scrbase renamed to \Ifstr ..	54	\secondlogo: added ..... 31
subject: \ifstr in scrbase		\secondlogo: added ..... 31
renamed to \Ifstr ..... 30		v0.7a
v0.5f		\ordinalfemalerefereename:
General: autodetect several logo		typofix for austrian ..... 43
picture files ..... 46		\ordinalmalerefereename: typofix
usage of <code>l3build</code> ..... 1		for austrian ..... 43
v0.6		v0.7b
General: package renamed from		\germanordinalmalecorrectorname:
gobble-		missing \fi added ..... 37
https://www.ctan.org/pkg/titlepagetitlepage		\germanordinalmalerefereename:
into		missing \fi added ..... 37
gobblehttps://www.ctan.org/pkg/uni-v0.7c		\germanordinalmalerefereename:
titlepageuni-titlepage ..... 1		orphan empty line removed .. 37
\@academicgrade: renamed		v1.0
“degree” to “academic grade” to		General: prepared for engines
avoid name clash with the		using tu encoding ..... 57
degree symbol ..... 31		

using class <code>ltxdoc</code> instead of	
<code>scrdoc</code> .....	<b>62</b>
<code>\makemaintitle: JT-Aufsaetze</code>	
allows empty author .....	<b>47</b>
<code>\presentationinformationDHBW:</code>	
using	
<code>\usenonemptytitleelement</code> ..	<b>40</b>
<code>\presentationinformationTUHH:</code>	
using	
<code>\usenonemptytitleelement</code> ..	<b>40</b>
<code>\presentationinformationUKoLA:</code>	
v1.1	
<code>rulecolor: new</code> .....	<b>39</b>
<code>\title@rulecolor: new</code> .....	<b>39</b>
using	
<code>\usenonemptytitleelement</code> ..	<b>40</b>
<code>\presentationinformationWWUM:</code>	
using	
<code>\usenonemptytitleelement</code> ..	<b>40</b>
<code>\usenonemptytitleelement:</code>	
added .....	<b>32</b>