

More Titlepage Styles with Package `uni-titlepage`^{*}

Markus Kohm[†]

v0.7b[‡]2022/01/24

Creation of title pages is something most authors should not have to do. But reality is not perfect, so a lot of authors have to do it. In 2009 KOMA started the title page project at <https://komascript.de/titlepage> to collect real title pages and implement them with a well defined interface. In 2021 the project has been moved to <https://github.com/komascript/uni-titlepage> and renamed.

Now, changing from one title page style to another would be very simple. Nevertheless implementation of a new title page style may be still difficult. But maybe the guys of the title page project would help you. Just ask!

Contents

1 Loading the Package	2
2 The Title Page Styles and their Options	2
2.1 Style DHBW	7
2.2 Style KOMAScript	8
2.3 Style Markus-1	10
2.4 Style Markus-2	12
2.5 Style Spacer	14
2.6 Style TU-DD	16
2.7 Style TU-HH	17
2.8 Style KIT	19
2.9 Style JT-Aufsaetze	20

^{*}This is file version v0.7b of file `uni-titlepage.drv`.

[†]Markus Kohm <komascript@gmx.info>

[‡]**Note:** All version below 0.9 are ALPHA versions. Everything may change. Everything may break. Everything may happen.

2.10	Style JT-Geschichte	21
2.11	Style JT-Typography	22
2.12	Style WWUM	23
2.13	Style UKoLa	24
3	Additional Commands	25
4	Implementation	26
4.1	The Installation Driver ‘uni-titlepage.ins’	26
4.2	The Package ‘scrbase.sty’	28
4.3	The titlepage Drivers	41
4.4	The Examples and the Manual	61

1 Loading the Package

You may load this package like all the other package, simply using:

```
\usepackage{uni-titlepage}
```

This package declares several options for title page manipulation. We will declare all those options in the following. Most of the options are package options as well, but some are style options only. You may use every package option already as optional argument of `\usepackage` and even of `\documentclass`. But in most cases it would be better to use them as optional argument of `\TitlePageStyle` or `\maketitle`. We show this way below.

2 The Title Page Styles and their Options

`TitlePageStyle` Several title page styles are supported. You may select a title page style using:

```
\TitlePageStyle[<option>=<value>,...]{<style>}.
```

The available styles are shown at the following sub-sections. Options may be every package option and every style option.

`maketitle` After loading a style you may generate title pages using:

```
\maketitle[<option>=<value>,...].
```

Again, you may use every package option and every style option as optional argument.

Another way to set an option is to use either

```
\TitleOption{<option>}{<value>}
```

or

`\TitleOptions{<option>}=<value>, ...}.`

You can set every package option an every option of already loaded title page styles.

For every option, that expects a string argument exists a corresponding command with the same name. So you may set, e.g., the title either using `\TitleOptions{title={This is the Title}}` or `\TitleOption{title}{This is the Title}` or `\maketitle[title={This is the Title}]` or `\TitlePageStyle[title={This is the Title}]{...}` or `\title{This is the Title}`. The most robust way is to use the command `\title` instead of the option at one of the other commands! If you use the option you may need to add `\protect` in front of commands inside the option value!

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
<code>advisor</code>	<code>TU-DD, UKoLa</code>	if your personal advisor differs from the advising professor, this is the name of the advisor
<code>author</code>	<code>every style</code>	the authors, with some styles (currently not with DHBW or UKoLa) you may seperate multiple authors by <code>\and</code>
<code>chair</code>	<code>TU-DD, KIT, WWUM, UKoLa</code>	the chair or institute of the faculty of the university where you've made or presented your work
<code>company</code>	<code>DHBW</code>	some works are made not only at a university but in cooperation with a company; at Duale Hochschule Baden-Württemberg this is the default case
<code>course</code>	<code>DHBW</code>	the shortcut for your discipline or course
...		

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
<code>date</code>	DHBW, KIT, KOMAScript, Markus-1, Markus-2, Spacer, TU-HH, TU-DD, JT-Typography, WWUM	the documents main date, this may by, e.g., the release date, the semester of a thesis or any other most valid date
<code>dedication</code>	KOMAScript, Markus-1, Markus-2, Spacer	sometimes it is nice to dedicate the work to someone, e.g., your wife, your children, your grandmother or your first love
<code>academicgrade</code>	DHBW, TU-HH, WUMM, UKoLa	the academic grade or degree you reach with the work
<code>discipline</code>	DHBW, TU-DD, WUMM	the discipline in which you've made your work or reach your academic grade
<code>duration</code>	DHBW	the processing time for your work
<code>faculty</code>	TU-DD, KIT, WUMM	the faculty of the university where you've made or presented your work
<code>homepage</code>	KIT	the www-address of the homepage
<code>mainlogo</code>	DHBW, KIT, UKoLa	a logo at the main title (currently used for the DHBW or the KIT logo at the default of <code>titlehead</code> and the main logo of style UKoLa)
<code>secondlogo</code>	UKoLa	a secondary logo
<code>matriculationnumber</code>	DHBW, TU-DD	if you were a student while you've made the work, this is your number

...

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
<code>oralexaminationdate</code>	<code>TU-HH, WUMM</code>	sometimes the date of the oral examination is not the main date but has to be shown too
<code>place</code>	<code>DHBW, TU-HH, JT-Geschichte, JT-Typography, WUMM, UKoLa</code>	the place, in general the city, where you've made the work or where the Duale Hochschule or the publisher resides
<code>professor</code>	<code>TU-DD, WUMM</code>	the name of the professor who advised you during your work
<code>publisher</code>	<code>KOMAScript, Markus-1, Markus-2, Spacer, JT-Aufsaetze, JT-Geschichte, JT-Typography</code>	most written works have a publisher
<code>referee</code>	<code>DHBW, TU-HH, UKoLa</code>	every academic work will be referred; with some styles (currently <code>TU-HH, WWUM, UKoLa</code>) multiple referees may be separated with <code>\and</code>
<code>sience</code>	<code>WWUM</code>	kind of science, e.g., "Naturwissenschaften"
<code>student</code> <code>subject</code>	<i>see author</i> <i>every style</i>	same like <code>author</code> the kind of work, there are special predefined subjects; if you use one of <code>bachelor</code> , <code>academicgrade</code> , <code>diploma</code> , <code>master</code> , <code>project</code> , <code>seminar</code> , or <code>studentresearch</code> a language dependend replacement will be done; to avoid this, you may set the value in parenthesis

...

<i>String Option</i>	<i>Styles</i>	<i>Common Meaning</i>
<code>subtitle</code>	KOMAScript, Markus-1, Markus-2, Spacer, TU-HH	the sub-title of the document
<code>title</code>	<i>every style</i>	the main title of the document
<code>titlehead</code>	DHBW, KOMAScript, Markus-2, Spacer, KIT	page head over the main title of the document
<code>university</code>	DHBW, TU-DD, TU-HH, KIT, WWUM	the university where you've made or presented your work

Let's have a look at the already defined title page styles. You should find an example L^AT_EX file for each of them at the documentation folder. If not, ask you distributor or administrator for those! But you may find the code of all examples in `docstrip` syntax even at [subsection 4.4](#) starting at [page 61](#). At the shown examples most variable contents was made red.

2.1 Style DHBW

Josef Schmidbauer asked me for a title page usable for bachelor thesis at the “Duale Hochschulen Baden-Württemberg”. This is a only one title page style.

The page (in example `titlepage-DHBW.tex`) is:

1. main title page with `titlehead`, `mainlogo`, `title`, `subject`, `academicgrade`, `discipline`, `place`, `author`, `duration`, `matriculationnumber`, `course`, `company`, `referee`, `university`, and `date`.



Note: The upper right corner is the logo placeholder. If you'd download the logo from the DHBW homepage <http://www.dhbw.de> and save it with the name `DHBW_d_MOS_195x95_rgb_300.jpg` it would be used automatically. The logo file is also available from https://de.wikipedia.org/wiki/Datei:DHBW_d_MOS_195x95_rgb_300.jpg. This original logo has a large white border, so it would be much smaller than the red box at the example. The example file also contains comments for an optional company logo at the upper left corner.

2.2 Style KOMAScript

This is a style similar to the title pages of KOMA-Script classes.

The pages (in `twoside` example `titlepage-KOMAScript.tex`) are:

1. defined by `extratitle`, which is not a package option but a style option. You may set it using `\TitleOption` or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.
2. empty and only in `twoside` mode with `extratitle` used.
3. main title page with `titlehead`, `subject`, `title`, `subtitle`, `author`, `date`, `plublisher`. You may use `\thanks` at any of these.

	<p>Das ist ein Schutztitel im Stil KOMAScript</p>
	<p>Den Kopfbereich kann man auf diese Weise füllen. Eine Klassifizierung der Arbeit Titel im Stil KOMAScript Untertitel Einen Verlag kann man ebenfalls angeben</p>



<p>Oberer Bereich der Rückseite des Haupttitels im Stil KOMAScript.</p>	<p>Eine Widmung im Stil KOMAScript</p>
<p>Unterer Bereich der Rückseite des Haupttitels im Stil KOMAScript.</p>	<ol style="list-style-type: none"> 4. only in twoside mode defined by <code>uppertitleback</code> and <code>lowertitleback</code>, which are not package options but style options. You may set them using <code>\TitleOption</code> or <code>\TitleOptions</code> after loading the style or with the optional argument of <code>\maketitle</code> or <code>\TitlePageStyle</code>. 5. optional post title with <code>dedication</code>. 6. empty and only in twoside mode with <code>dedication</code> used.



2.3 Style Markus-1

This is a style similar to the one of the title of the KOMA-Script book.

The pages (in twoside example `titlepage-Markus-1.tex`) are:

1. defined by `publisher`; may be omitted by `publisher={}`.
2. only in twoside mode with `publisher` defined by `author`.
3. main title page with `subject`, `title`, `subtitle`, and `date`.

	
	<p>Verlag</p> <p>Eine Klassifizierung der Arbeit</p> <p>Markus Kohm Sonst Jemand</p> <p>Titel im Stil Markus-1 Untertitel</p>

<p>Oberer Bereich der Rückseite des Haupttitels im Stil Markus-1.</p>  <p>Unterer Bereich der Rückseite des Haupttitels im Stil Markus-1.</p> 	<p>Eine Widmung im Stil Markus-1</p> 
	<ul style="list-style-type: none"> 4. only in twoside mode defined by <code>uppertitleback</code> and <code>lowertitleback</code>, which are not package options but style options. You may set them using <code>\TitleOption</code> or <code>\TitleOptions</code> after loading the style or with the optional argument of <code>\maketitle</code> or <code>\TitlePageStyle</code>. 5. optional post title with <code>dedication</code>. 6. empty and only in twoside mode with <code>dedication</code> used.



2.4 Style Markus-2

This style is not a real live style, but similar styles are often used:

The pages (in twoside example `titlepage-Markus-2.tex`) are:

1. defined by `extratitle`.
2. empty and only in twoside mode with `extratitle` used.
3. main title page with `titlehead` placed at the page head (if this is to high, it might be put outside the page; if it is to deep, it might overwrite parts of the title), `rulewidth` and `rulesep` for the vertical rule (these aren't package options but style options), `subject`, `title`, `subtitle`, `author`, `date`, and `publisher`.

	<p>Das ist ein Schmutztitel im Stil Markus-2</p>
	<p>Eine Klassifizierung der Arbeit Markus Kohm Titel im Stil Markus-2 Untertitel Verlag</p>


<p>Oberer Bereich der Rückseite des Haupttitels im Stil Markus-2.</p>  <p>Unterer Bereich der Rückseite des Haupttitels im Stil Markus-2.</p> 	<p>Eine Widmung im Stil Markus-2</p> 
	<ul style="list-style-type: none"> 4. only in twoside mode defined by <code>uppertitleback</code> and <code>lowertitleback</code>, which are not package options but style options. You may set them using <code>\TitleOption</code> or <code>\TitleOptions</code> after loading the style or with the optional argument of <code>\maketitle</code> or <code>\TitlePageStyle</code>. 5. optional post title with <code>dedication</code>. 6. empty and only in twoside mode with <code>dedication</code> used.

2.5 Style Spacer

This style is a variant of style `Markus-2` from subsection 2.4. It was asked by `spacer2012` at the original `titlepage` project on <https://komascript.de/titlepage>. In difference to `Markus-2` the title head will not be placed at the page head but at the body.

The pages (in `twoside` example `titlepage-Spacer.tex`) are:

1. defined by `extratitle`.
2. empty and only in `twoside` mode with `extratitle` used.
3. main title page with `titlehead` placed at the page head, `rulewidth` and `rulesep` for the vertical rule (these aren't package options but style options), `subject`, `title`, `subtitle`, `author`, `date`, and `publisher`.




<p>Oberer Bereich der Rückseite des Haupttitels im Stil Spacer.</p> <p>Unterer Bereich der Rückseite des Haupttitels im Stil Spacer.</p>	<p>Eine Widmung im Stil Spacer</p>
	<ul style="list-style-type: none"> 4. only in twoside mode defined by <code>uppertitleback</code> and <code>lowertitleback</code>, which are not package options but style options. You may set them using <code>\TitleOption</code> or <code>\TitleOptions</code> after loading the style or with the optional argument of <code>\maketitle</code> or <code>\TitlePageStyle</code>. 5. optional post title with <code>dedication</code>. 6. empty and only in twoside mode with <code>dedication</code> used.

2.6 Style TU-DD

This style is used at the “Technische Universität Dresden”. I was asked fot this several years ago. Only one title page is defined! The page (in example `titlepage-TU-DD.tex`) is:


1. main title page with `university`, `faculty`, `chair`, `professor`, `title`, `subject`, `author`, `discipline`, `matriculationnumber`, `advisor`, `place`, and `date`.



But there is another variant. If option `blackborder` was set to true, an black border is put around the page:

The page (in example `titlepage-TU-DD.tex` with option `blackborder`) is:

1. main title page with `university`, `faculty`, `chair`, `professor`, `title`, `subject`, `author`, `discipline`, `matriculationnumber`, `advisor`, `place`, and `date`.




2.7 Style TU-HH

This style is used at the “Technische Universität Hamburg-Harburg”. I was asked for this several years ago. Only two title pages are defined!

The pages (in twoside example `titlepage-TU-HH.tex`) are:

1. main title page with `title`, `subtitle`, `university`, `academicgrade`, `subject`, `author`, `place`, and `date`. Some additional text depending on the selected language will be used also.



2. only in twoside mode with `referee` and `oralexaminationdate`.



The output of style TU-HH differs, if you use option `final`, which is a style option, not a package option. You may set it using `\TitleOption`

or `\TitleOptions` after loading the style or with the optional argument of `\maketitle` or `\TitlePageStyle`.


2.8 Style KIT

This style is used at the “KIT – University of the State of Baden-Württemberg and National Research Center of the Helmholtz Association”. I’ve made this because of the ugly L^AT_EX class and template made by the KIT itself. Only one title page is defined!

The page (in example `titlepage-KIT.tex`) is:

1. main title page with `titlehead`, `mainlogo`, `title`, `subject`, `author`, `referee`, `advisor`, `university`, `duration`, and `homepage`. Some additional text depending on the selected language will be used also.

If `titlehead` is empty or unused left aligned `mainlogo` will be used. If `mainlogo` is empty or unused, and if you have a logo file `KITLogo_RGB.pdf`, this will be used. As an alternative also `2560px-Logo_KIT.svg.png`, `2000px-Logo_KIT.svg.png`, `1280px-Logo_KIT.svg.png`, `1024px-Logo_KIT.svg.png`, `1000px-Logo_KIT.svg.png`, `800px-Logo_KIT.svg.png`, `640px-Logo_KIT.svg.png`, or `500px-Logo_KIT.svg.png` from https://de.wikipedia.org/wiki/Datei:Logo_KIT.svg would be auto-detected. Several other elements will be set to defaults too, if they are empty. So you don’t need to set all the elements, that has been set at the example file.




2.9 Style JT-Aufsaetze

The style is based on the front cover of “Jan Tschichold: Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie, Birkhäuser Verlag Basel, 1975, ISBN: 3-7643-1946-1”. I’ve made this, because the book is a major book of classic typography. It seems to be old fashioned and indeed it is. Note, that the front cover of a book an the main title of a book are not the same! Nevertheless, here I’ve made a main title from a front cover. Currently only one title page is defined, but you may also use `extratitle`, `uppertitleback`, and `lowertitleback`.

The page (in example `titlepage-JT-Aufsaetze.tex`) is:

1. main title page with `author`, `title`, `publisher`, `rulewidth` and `rulesep` for width of the horizontal rules and the distance between them (these aren’t package options but style options).




2.10 Style JT-Geschichte

The style is based on “Jan Tschichold: Geschichte der Schrift in Bildern; Holbein-Verlag, 1947”. This is another major book of classic typography. It seems to be old fashioned and indeed it is. Currently only one title page is defined, but you may also use `extratitle`, `uppertitleback`, and `lowertitleback`.

The title page (in example `titlepage-JT-Geschichte.tex`) is:

1. main title page with `author`, `title`, `publisher`, `place`, `rulewidth` and `rulesep` for width of the horizontal rules and the distance between them (these aren't package options but style options).

Note, that the default for `titlepagefont` prints everything but the `title` with ad-hoc letterspacing in upper-case letters if `\lsstyle` is available and without letterspacing but in small capitals otherwise. Changing the default of `titlepagefont` will also change this automatism.




2.11 Style JT-Typography

The style is based on “Jan Tschichold: The New Typography; University of California Press, Berkley and Los Angeles, California 1995”. This is the English translation of another major book of classic typography. Some things like missing letterspacing at the upper-case title seems to be wrong. Currently only one title page is defined, but you may also use `extratitle`, `uppertitleback`, and `lowertitleback`.



The title page (in example `titlepage-JT-Geschichte.tex`) is:

1. main title page with `author`, `title`, `subtitle`, `place`, `date`, `publisher`.



2.12 Style WWUM

Tobias Südkamp asked me for that title for the Westfälischen Wilhelms-Universität Münster. The `professor` is more likely the `chairman`. Female referees should be prefixed by [f]. You can omit the examination date defining an empty `\examinationdate`.

	<p>The <code>pages</code> (in example <code>titlepage-WWUM.tex</code>) are:</p> <ol style="list-style-type: none"> 1. cover page with <code>author</code>, <code>title</code>, <code>\the\year</code> 2. the backside of the cover page is empty if it exists 3. main title page with <code>chair</code>, <code>title</code>, <code>subject</code>, <code>academicgrade</code>, <code>sience</code>, <code>discipline</code>, <code>faculty</code> 4. main title back side with <code>professor</code>, <code>referee</code>, <code>oralexaminationdate</code> (normally empty)
	

2.13 Style UKoLa

In 2007 several students asked me for the title of the Universität Koblenz-Landau. At that time, I've made a package for the title they asked for. The package has been published at <https://komascript.de/unikoblenzlandau> only. In 2021, after I've published `uni-titlepage`, it was time to implement this title also as a title style definition. Note, this is not an official style of the University Koblenz-Landau. Several referees can be separated by `\and`. Female referees should be prefixed by [f].

The page (in example `titlepage-UKoLa.tex`) is:

1. main title page with `mainlogo`, `secondlogo`, `title`, `subject`, `academicgrade`, `chair`, `dicipline`, `place`, `author`, `referee`, and `date`.



Note: The upper left corner is the logo placeholder. If you'd download the logo from <http://www.uni-koblenz-landau.de/logo.png> and save it with the name `uni-koblenz-landau.png`, it would be used automatically.

3 Additional Commands

\NowButAfterBeginDocument Command

```
\NowButAfterBeginDocument{\langle code\rangle}
```

is something like \AtBeginDocument, but if you call it somewhere after \begin{document} argument *code* will be used immediately. This command is used inside some of the title page styles, because you may load them either at the preamble or even after \begin{document}, but some code should not be executed before \begin{document}.

titlepage In oposite to the **titlepage** environment of the standard classes,

```
\begin{titlepage}[⟨options⟩]
...
\end{titlepage}
```

knows some options. These are **pagestyle=***style* and **pagenumber=***number*. The first one changes the page style of the generated title page to the given *style*. If the option is not set, the default **empty** will be used. The second one sets the logical page number of the generated title page to the given *number* and sets the counter **pagenumber** to this value. If the option is not used, the value of counter **pagenumber** will be increased by one and the result is used for the logical page number.

fullsizetitle Using

```
\begin{fullsizetitle}[⟨options⟩]
...
\end{fullsizetitle}
```

is almost the same like above. But **fullsizetitle** removes the margins from the generated title page. Nevertheless if binding correction (aka binding offset) of package **typearea** or **geometry** could be recognized, it will not be removed. Some of the title page styles use this environment instead of **titlepage** inside \maketitle. With this the margins of the title page do not depend on the type area of the document.

\usetitleelement Command

```
\usetitleelement{\langle element\rangle}
```

gives the content of the corresponding title *element*. Each main *element* defined by the package may be used. Those are currently: **advisor**, **author**, **chair**, **company**, **course**, **date**, **dedication**, **academicgrade**, **discipline**, **duration**, **faculty**, **homepage**, **mainlogo**, **matriculationnumber**, **oralexaminationdate**, **place**, **professor**, **publisher**, **referee**, **subject**, **subtitle**, **title**, **titlehead**, and **university**. Note: **student** isn't a main *element*, because it's only an alias for **author**.

4 Implementation

Note: To generate all files, developers and beta testers should simply use the source from <https://github.com/komascript/uni-titlepage> and call

```
l3build unpack  
l3build doc
```

The resulting documentation will be placed in the main folder. The unpacked style file are in `build/unpacked`, You can use

```
l3build install
```

to install them in `TEXMFHOME`. See the manual of `l3build` for more information.

As an alternative you can use the source distribution from CTAN and run:

```
tex uni-titlepage.dtx
```

The documentation is usually part of the source distribution at CTAN. Note, that all the generated `tex` files are example files. Do not copy them to the run-time files but the documentation folder!

4.1 The Installation Driver ‘`uni-titlepage.ins`’

First of all we produce `uni-titlepage.ins`, the installation driver. It starts very common with loading `docstrip`, preamble declaration and start of generation.

```
1 \def\batchfile{uni-titlepage.dtx}  
2 \input docstrip.tex  
3 \ifToplevel{  
4   \Msg{*****}  
5   \Msg{*}  
6   \Msg{* Steps of uni-titlepage generation:}  
7   \Msg{* ======}  
8   \Msg{*}  
9   \Msg{* - Generation of all needed files:}  
10  \keepsilent  
11  \askforoverwritefalse  
12 }  
13  
14 \preamble  
15 Copyright (c) 2009-2021 by Markus Kohm <komascript(at)gmx.info>  
16
```

```

17 This file was generated from file(s) of uni-titlepage distribution.
18
19 -----
20
21 This work may be distributed and/or modified under the conditions of
22 the LaTeX Project Public License, version 1.3c of the license.
23 The latest version of this license is in
24   http://www.latex-project.org/lppl.txt
25 and version 1.3c or later is part of all distributions of LaTeX
26 version 2005/12/01 or later.
27
28 This work has the LPPL maintenance status "maintained".
29
30 The Current Maintainer and author of this work is Markus Kohm.
31
32 This file may only be distributed together with
33 the file 'uni-titlepage.dtx'.
34 You may however distribute the file 'uni-titlepage.dtx' without this file.
35
36 \endpreamble
37
38 \generate{%

```

But while the dtx file is the ins file itself, we will never generate this file.

```

39 %  \file{uni-titlepage.ins}{\from{uni-titlepage.dtx}{ins}}% not needed
40 \file{uni-titlepage.drv}{\from{uni-titlepage.dtx}{doc,manual}}%
41 \file{uni-titlepage.sty}{\from{uni-titlepage.dtx}{package}}%
42 \file{title-DHBW.def}{\from{uni-titlepage.dtx}{driver,DHBW}}%
43 \file{title-KOMAScript.def}{\from{uni-titlepage.dtx}{driver,KOMAScript}}%
44 \file{title-Markus-1.def}{\from{uni-titlepage.dtx}{driver,Markus,1}}%
45 \file{title-Markus-2.def}{\from{uni-titlepage.dtx}{driver,Markus,2}}%
46 \file{title-Spacer.def}{\from{uni-titlepage.dtx}{driver,Spacer}}%
47 \file{title-TU-DD.def}{\from{uni-titlepage.dtx}{driver,TU-DD}}%
48 \file{title-TU-HH.def}{\from{uni-titlepage.dtx}{driver,TU-HH}}%
49 \file{title-KIT.def}{\from{uni-titlepage.dtx}{driver,KIT}}%
50 \file{title-JT-Aufsaetze.def}{\from{uni-titlepage.dtx}{driver,JT-Aufsaetze}}%
51 \file{title-JT-Geschichte.def}{\from{uni-titlepage.dtx}{driver,JT-Geschichte}}%
52 \file{title-JT-Typography.def}{\from{uni-titlepage.dtx}{driver,JT-Typography}}%
53 \file{title-WWUM.def}{\from{uni-titlepage.dtx}{driver,WWUM}}%
54 \file{title-UKoLa.def}{\from{uni-titlepage.dtx}{driver,UKoLa}}%
55 \file{titlepage-DHBW.tex}{\from{uni-titlepage.dtx}{doc,example,DHBW}}%
56 \file{titlepage-KOMAScript.tex}{\from{uni-titlepage.dtx}{doc,example,KOMAScript}}%
57 \file{titlepage-Markus-1.tex}{\from{uni-titlepage.dtx}{doc,example,Markus,1}}%
58 \file{titlepage-Markus-2.tex}{\from{uni-titlepage.dtx}{doc,example,Markus,2}}%
59 \file{titlepage-Spacer.tex}{\from{uni-titlepage.dtx}{doc,example,Spacer}}%
60 \file{titlepage-TU-DD.tex}{\from{uni-titlepage.dtx}{doc,example,TU-DD}}%
61 \file{titlepage-TU-HH.tex}{\from{uni-titlepage.dtx}{doc,example,TU-HH}}%
62 \file{titlepage-KIT.tex}{\from{uni-titlepage.dtx}{doc,example,KIT}}%
63 \file{titlepage-JT-Aufsaetze.tex}{\from{uni-titlepage.dtx}{doc,example,JT-Aufsaetze}}%
64 \file{titlepage-JT-Geschichte.tex}{\from{uni-titlepage.dtx}{doc,example,JT-Geschichte}}%

```

```

65  \file{titlepage-JT-Typography.tex}{\from{uni-titlepage.dtx}{doc,example,JT-Ty}
66  \file{titlepage-WWUM.tex}{\from{uni-titlepage.dtx}{doc,example,WWUM}}%
67  \file{titlepage-UKoLa.tex}{\from{uni-titlepage.dtx}{doc,example,UKoLa}}%
68  \nopreamble\nopostamble
69  \file{README.md}{\from{uni-titlepage.dtx}{README}}%
70 }%
71
72 \ifTopLevel{%
73   \Msg{* \space\space done.}
74   \Msg{*}
75   \Msg{* You may install all the files now.}
76   \Msg{*}
77   \Msg{*****}
78 }

```

At docstrip run we like to finish the file know:

```
79 \csname endinput\endcsname
```

4.2 The Package ‘`scrbase.sty`’

\TitleOptions	We use the extended option handling of KOMA-Script, so we load package <code>scrbase</code> and declare a family, a member and a something like <code>\KOMAoptions</code> and <code>\KOMAoption</code> but for this package.
	80 \RequirePackage{scrbase}[2014/12/03]
	81 \DefineFamily{title}
	82 \DefineFamilyMember{title}
	83 \newcommand*{\TitleOptions}{\FamilyOptions{title}}
	84 \newcommand*{\TitleOption}{\FamilyOption{title}}
 pagenumber	
	85 \newcounter{titlepage}\setcounter{titlepage}{\@ne}
	86 \DefineFamilyKey{title}{pagenumber}{%
	87 \setcounter{titlepage}{\#1}\FamilyKeyStateProcessed
	88 }
 \titlepagestyle	
\pagestyle	89 \providecommand*{\titlepagestyle}{}%
	90 \renewcommand*{\titlepagestyle}{\emptyset}
	91 \DefineFamilyKey{title}{pagestyle}{%
	92 \renewcommand*{\titlepagestyle}{\#1}\FamilyKeyStateProcessed
	93 }
 \if@resonecol	
	94 \ifcsname @restonecolfalse\endcsname
	95 \expandafter\@gobble
	96 \else
	97 \expandafter\@firstofone
	98 \fi
	99 {\newif\if@restonecol}

```

titlepage
100 \scr@ifundefinedorrelax{titlepage}{\def\titlepage{}{}}
101 \scr@ifundefinedorrelax{endtitlepage}{\def\endtitlepage{}{}}
102 \providecommand*\maketitle}[1] [] {}

\inittitle Set of commands, that define a title style:
\makepretitle
\makepretitleback
\makemaintitle
\makemaintitleback
\makeposttitle
\makeposttitleback
\exittitle
\tp@undefinedtitle

\inittitlestyle Will be called before loading a title style:
\newcommand*\inittitlestyle[%]
\renewenvironment{titlepage}[1] []{%
\TitleOptions{##1}%
\clearpage
\if@twocolumn
\@restonecoltrue\onecolumn
\else
\@restonecolfalse
\fi
\ifx\titlepagestyle\empty\else\thispagestyle{\titlepagestyle}\fi
\if@twoside% im einseitigen Satz ist mir alles egal
\ifodd\value{page}% aktuelle Seite ist ungerade
\fi
\fi
\ifodd\value{titlepage}%
\else
\fi
...
wanted page number is even: put in empty page.
\else
\fi
\fi
\setcounter{page}{\value{titlepage}}%

```

Current page number is odd ...

```

126 \ifodd\value{titlepage}%
127 \else
...
wanted page number is even: put in empty page.
128 \null\newpage
129 \fi
130 \else

```

Current page number is even ...

```

131 \ifodd\value{titlepage}%
...
wanted page number is off: put in empty page.
132 \null\newpage % Leerseite
133 \fi
134 \fi
135 \fi
136 \setcounter{page}{\value{titlepage}}%

```

```

137   \ifx\titlepagestyle\@empty\else\thispagestyle{\titlepagestyle}\fi
138 }%
139   \if@restonecol\twocolumn \else \newpage\fi
140   \stepcounter{titlepage}%
141 }%
142
143 \renewcommand*{\maketitle}[1] []{%
144   \begingroup
145     \TitleOptions{##1}%
146     \inittitle
147     \makepretitle\if@twoside\makepretitleback\fi
148     \makemaintitle\if@twoside\makemaintitleback\fi
149     \makeposttitle\if@twoside\makeposttitleback\fi
150     \exittitle
151   \endgroup
152 }%
153
154 \renewcommand*{\inittitle}{}%
155 \renewcommand*{\makepretitle}{\tp@undefinedtitle{pre}}%
156 \renewcommand*{\makepretitleback}{\tp@undefinedtitle{back of pre}}%
157 \renewcommand*{\makemaintitle}{\tp@undefinedtitle{main}}%
158 \renewcommand*{\makemaintitleback}{\tp@undefinedtitle{back of main}}%
159 \renewcommand*{\makeposttitle}{\tp@undefinedtitle{post}}%
160 \renewcommand*{\makeposttitleback}{\tp@undefinedtitle{back of post}}%
161 \renewcommand*{\exittitle}{}%
162 }
163 \inittitlestyle

\titlebox New environment for full page titles (with respect to BCOR or Gm@bindingoffset
fullsizetitle if defined)
164 \newsavebox\titlebox
165 \newenvironment{fullsizetitle}[1] []{%
166   \TitleOptions{#1}%
167   \begin{lrbox}{\titlebox}
168     \hspace*{\paperwidth}
169     \scr@ifundefinedorrelax{\ta@bcor}{%
170       \scr@ifundefinedorrelax{\Gm@bindingoffset}{}{%
171         \advance\hspace*{-\Gm@bindingoffset}%
172     }%
173     \advance\hspace*{-\ta@bcor}
174     \scr@ifundefinedorrelax{\Gm@bindingoffset}{}{%
175       \ifdim \Gm@bindingoffset=\ta@bcor\else
176         \PackageWarning{uni-titlepage}{Ignoring geometry's binding
177           correction,\MessageBreak
178           using typearea's binding correction.\MessageBreak
179           If you're using geometry and typearea,\MessageBreak
180           you should set both options to the same value,\MessageBreak
181           e.g. \string\KOMAoptions{BCOR=\the\ta@bcor}\MessageBreak
182           \space\space\space\space\space

```

```

183          \string\geometry{bindingoffset=\the\ta@bcor}\MessageBreak
184          to make uni-titlepage use this value%
185      }%
186      \fi
187  }%
188 }%
189 \vsize\paperheight
190 \linewidth\hsize
191 \columnwidth\hsize
192 \textwidth\hsize
193 \textheight\vsize
194 \noindent\minipage{\hsize}
195 }{%
196 \endminipage
197 \end{lrbox}
198 \begin{titlepage}%
199 \vspace*{-1in}\vskip-\topmargin\vskip-\headheight\vskip-\headsep
200 \vskip-\topskip
201 \raggedright
202 \leavevmode
203 \hskip-1in
204 \ifodd\c@page
205   \hskip-\oddsidemargin
206   \scr@ifundefinedorrelax{\ta@bcor}{%
207     \scr@ifundefinedorrelax{\Gm@bindingoffset}{%
208       \hskip\Gm@bindingoffset}%
209     }{\hskip\ta@bcor}%
210 \else
211   \hskip-\evensidemargin
212 \fi
213 \vbox to\z@{\hsize\z@
214   \vskip-\baselineskip
215   \makebox[0pt][l]{\usebox\titlebox}%
216   \vss
217 }%
218 \end{titlepage}
219 }

\DefineSimpleTitleKey Define title page “variables”:
\DefineReplaceTitleKey 220 \newcommand*{\tp@replacewarning}[2]{%
\tp@replacewarning 221   \PackageWarning{uni-titlepage}{%
\tp@dokeys 222     Using ‘#2’ instead of ‘#1’,\MessageBreak
223     because ‘#1’ not defined%
224   }%
225 }
226 \newcommand*{\tp@dokeys}{}%
227 \newcommand*{\DefineSimpleTitleKey}[2][]{.\currname.\currext]{%
228   \l@addto@macro\tp@dokeys{\do{\#2}}%
229   \expandafter\newcommand\expandafter*\csname @#2\endcsname{}%

```

```

230  \expandafter\newcommand\expandafter*\csname #2\endcsname[1]{%
231   \expandafter\gdef\csname @#2\endcsname{##1}}%
232 \DefineFamilyKey[{#1}]{title}{#2}{%
233   \csname #2\endcsname{##1}%
234   \FamilyKeyStateProcessed
235 }%
236 }
237 \newcommand*{\DefineReplaceTitleKey}[3] [.\@currname.\@currext]{%
238   \DefineFamilyKey[{#1}]{title}{#2}{%
239     \tp@replacewarning{#2}{#3}%
240     \FamilyOptions{title}{#3=##1}%
241   }%
242 }

\titlehead
\@titlehead 243 \providecommand*{\@titlehead}{}%
titlehead 244 \providecommand{\titlehead}[1]{\gdef\@titlehead{#1}%
245 \DefineFamilyKey{title}{titlehead}{\titlehead{#1}\FamilyKeyStateProcessed}%

\homepage
\@homepage 246 \providecommand*{\@homepage}{}%
homepage 247 \providecommand{\homepage}[1]{\gdef\@homepage{#1}%
248 \DefineFamilyKey{title}{homepage}{\homepage{#1}\FamilyKeyStateProcessed}%

\title
\@title 249 \let\@title\relax\let\title\relax\DefineSimpleTitleKey{title}%
title
\author
\@author 250 \let\@author\relax\let\author\relax\DefineSimpleTitleKey{author}%
author
\date
\@date 251 \let\@date\relax\let\date\relax\DefineSimpleTitleKey{date}%
date
\duration
\@duration 252 \DefineSimpleTitleKey{duration}%
duration
\course
\@course 253 \DefineSimpleTitleKey{course}%
course
\company
\@company 254 \DefineSimpleTitleKey{company}%
company
\subtitle
\@subtitle 255 \let\@subtitle\relax\let\subtitle\relax\DefineSimpleTitleKey{subtitle}%
subtitle
\university
\@university 256 \DefineSimpleTitleKey{university}%
university

```

```

\faculty
@faculty 257 \DefineSimpleTitleKey{faculty}
    faculty
        \chair
    @chair 258 \DefineSimpleTitleKey{chair}
        chair
\professor
@professor 259 \DefineSimpleTitleKey{professor}
    professor
        \subject
@subject 260 \providecommand*{\@subject}{}%
261 \providecommand*{\subject}[1]{\gdef\@subject{\#1}%
262 \l@addto@macro\tp@dokeys{\do{\subject}}%}
263 \DefineFamilyKey{title}{subject}{%
264 \Ifstr{\#1}{project}{\subject{\projectpapername}}{%
265 \Ifstr{\#1}{seminar}{\subject{\seminarpapername}}{%
266 \Ifstr{\#1}{studentresearch}{\subject{\studentresearchname}}{%
267 \Ifstr{\#1}{diploma}{\subject{\diplomathesisname}}{%
268 \Ifstr{\#1}{degree}{\subject{\degreethesisname}}{%
269 \Ifstr{\#1}{master}{\subject{\masterthesisname}}{%
270 \Ifstr{\#1}{bachelor}{\subject{\bachelorthesisname}}{%
271 \subject{\#1}}%
272 }%
273 }%
274 }%
275 }%
276 }%
277 }%
278 }%
279 \FamilyKeyStateProcessed
280 }

```

\Ifstr For compatibility with old versions of `scrbase` the macro is provided based on `\ifstr` if it has not been defined by `scrbase`.

```

281 \providecommand*{\Ifstr}{\ifstr}

```

```

student
282 \DefineReplaceTitleKey{student}{author}

\sience
@science 283 \DefineSimpleTitleKey{sience}
    sience
\discipline
@discipline 284 \DefineSimpleTitleKey{discipline}
    discipline
\academicgrade
@academicgrade 285 \DefineSimpleTitleKey{academicgrade}
    academicgrade

```

```

\matriculationnumber
\@matriculationnumber 286 \DefineSimpleTitleKey{matriculationnumber}
matriculationnumber
  \advisor
    \@advisor 287 \DefineSimpleTitleKey{advisor}
      advisor
      \referee
        \referee
          \place
            \@place 288 \DefineSimpleTitleKey{referee}
              referee
              \place
                \place
                  \publisher
                    \@publisher 289 \DefineSimpleTitleKey{place}
                      publisher 290 \DefineSimpleTitleKey{publisher}
                      \renewcommand*{\@publisher}{\csname @publishers\endcsname}

                      \mainlogo
                        \@mainlogo 292 \DefineSimpleTitleKey{mainlogo}
                          mainlogo
                          \secondlogo
                            \@secondlogo 293 \DefineSimpleTitleKey{secondlogo}
                              secondlogo
                              \oralexaminationdate
                                \oralexaminationdate 294 \DefineSimpleTitleKey{oralexaminationdate}
                                  oralexaminationdate
                                  \dedication
                                    \@dedication 295 \providecommand*{\@dedication}{}%
                                      296 \providecommand{\dedication}[1]{\gdef\@dedication{#1}}
                                      297 \DefineFamilyKey{title}{dedication}{\dedication\#1}\FamilyKeyStateProcessed}

\usetitleelement
\@usetitleelement@error 298 \newcommand*{\usetitleelement}[1]{%
  299   \scr@ifundefinedorrelax{\#1}{%
    300     \@usetitleelement@error{\#1}%
  301   }{%
    302     \scr@ifundefinedorrelax{\#1}{%
      303       \@usetitleelement@error{\#1}%
    304     }{%
      305       \nameuse{\#1}%
    306     }%
  307   }%
308 }
309 \newcommand*{\@usetitleelement@error}[1]{%
  310   \PackageError{uni-titlepage}{‘#1’ isn’t a title element}{%
    311     You should use \string\usetitleelement\space for title elements
    312     only!\MessageBreak
    313     If you’ll continue, command will be ignored.}%
314 }

```

Users cannot simply use, e.g., `\@title`, `\@mainlogo` etc. So we need a command to get them:

Some variables use their own configurable font:

```
titlepagefont
\@titlepagefont 315 \scr@ifundefinedorrelax{newkomafont}{%
316   \newcommand*\{@titlepagefont}{}%
317 }{%
318   \newkomafont{titlepage}{}%
319 }
320 \DefineFamilyKey{title}{titlepagefont}{%
321   \renewcommand*\{@titlepagefont}{#1}%
322   \FamilyKeyStateProcessed
323 }

subjectfont
\subject@font 324 \providecommand*\subject@font}{\bfseries}
325 \DefineFamilyKey{title}{subjectfont}{%
326   \renewcommand*\subject@font}{#1}%
327   \FamilyKeyStateProcessed
328 }

titlefont
\title@font 329 \providecommand*\titlefont}{\bfseries}
330 \DefineFamilyKey{title}{titlefont}{%
331   \renewcommand*\titlefont}{#1}%
332   \FamilyKeyStateProcessed
333 }

subtitlefont
\@subtitlefont 334 \providecommand*\@subtitlefont}{\bfseries}
335 \DefineFamilyKey{title}{subtitlefont}{%
336   \renewcommand*\@subtitlefont}{#1}%
337   \FamilyKeyStateProcessed
338 }

\TitlePageStyle Load a title page style from file
339 \newcommand*\TitlePageStyle}[2] []{%
340   \IfFileExists{title-#2.def}{%
341     \begingroup
342       \edef\@tempa{\endgroup
343         \noexpand\inittitlestyle
344         \noexpand\makeatletter
345         \noexpand\input{title-#2.def}%
346         \noexpand\catcode`\'\noexpand\@=\the\catcode`\@
347     }%
348     \@tempa
349     \TitleOptions{#1}%
350   }{%
351     \PackageError{uni-titlepage}{No title definition for '#2' found}{%
352       You've tried to set title page style '#2', but no title page
353     }
354   }
355 }
```

```

353     style definition file\MessageBreak
354     'title-#2.def' may be found%
355   }%
356 }
357 }

```

\NowButAfterBeginDocument Nice shortcut:

```

358 \newcommand*{\NowButAfterBeginDocument}{%
359   \if@atdocument
360     \expandafter\@firstofone
361   \else
362     \expandafter\AtBeginDocument
363   \fi
364 }

365 \DeclareOption*{\expandafter\TitlePageStyle\expandafter{\CurrentOption}}
366 \FamilyProcessOptions*\relax

```

\chairmannname Language dependent terms:

```

367 \providecommand*{\chairmannname}{Chairman}
368 \providecommand*{\projectpapername}{Project Paper}
369 \providecommand*{\seminarpapername}{Seminar Paper}
370 \providecommand*{\studentreserchname}{Student Research Project}
371 \providecommand*{\diplomathesisname}{Diploma Thesis}
372 \providecommand*{\degreethesisname}{Degree Thesis}
373 \providecommand*{\masterthesisname}{Master Thesis}
374 \providecommand*{\bachelorthesisname}{Bachelor Thesis}
375 \providecommand*{\presentedbyname}{presented by}
376 \providecommand*{\advisorname}{Advisor}
377 \providecommand*{\thename}{}}
378 \providecommand*{\ofthename}{of the}
379 \providecommand*{\fromname}{from}
380 \providecommand*{\fromplacename}{from}
381 \providecommand*{\refereename}{Referee}
382 \providecommand*{\malerefereename}{\refereename}
383 \providecommand*{\femalerefereename}{\refereename}
384 \providecommand*{\ordinalmalerefereename}{\englishordinalmalerefereename}
385 \providecommand*{\ordinalfemalerefereename}{\englishordinalfemalerefereename}
386 \providecommand*{\oralexaminationdatename}{Date of Oral Examination}
387 \providecommand*{\atthename}{at}
388 \providecommand*{\durationname}{Processing Time}
389 \providecommand*{\matriculationnumbername}{Matriculationnumber}
390 \providecommand*{\coursename}{Course}
391 \providecommand*{\companyname}{Training Company}
392 \providecommand*{\examinationname}{Examination}
393 \providecommand*{\examinationdatename}{Date of Examination}
394 \newcommand*{\ordinal}{\englishordinal}
395 \newcommand*{\femaleordinal}{\ordinal}
396 \newcommand*{\maleordinal}{\ordinal}

```

```

397 \providecommand*\{\\in datename\}{in}
398 \providecaptionname{american,australian,british,canadian,%
399   english,newzealand,UKenglish,USenglish}{\\chairmanname\}{Chairmain}%
400 \providecaptionname{american,australian,british,canadian,%
401   english,newzealand,UKenglish,USenglish}{\\projectpapername\}{Project Paper}%
402 \providecaptionname{american,australian,british,canadian,%
403   english,newzealand,UKenglish,USenglish}{\\seminarpapername\}{Seminar Paper}%
404 \providecaptionname{american,australian,british,canadian,%
405   english,newzealand,UKenglish,USenglish}{\\studentresearchname\}{Student
406   Research Project}%
407 \providecaptionname{american,australian,british,canadian,%
408   english,newzealand,UKenglish,USenglish}{\\diplomathesisname\}{Diploma Thesis}%
409 \providecaptionname{american,australian,british,canadian,%
410   english,newzealand,UKenglish,USenglish}{\\degreethesisname\}{Degree Thesis}%
411 \providecaptionname{american,australian,british,canadian,%
412   english,newzealand,UKenglish,USenglish}{\\masterthesisname\}{Master Thesis}%
413 \providecaptionname{american,australian,british,canadian,%
414   english,newzealand,UKenglish,USenglish}{\\bachelorthesisname\}{Bachelor
415   Thesis}%
416 \providecaptionname{american,australian,british,canadian,%
417   english,newzealand,UKenglish,USenglish}{\\ordinal\}{\\englishordinal}%
418 \providecaptionname{american,australian,british,canadian,%
419   english,newzealand,UKenglish,USenglish}{\\presentedbyname\}{presented by}%
420 \providecaptionname{american,australian,british,canadian,%
421   english,newzealand,UKenglish,USenglish}{\\advisorname\}{Advisor}%
422 \providecaptionname{american,australian,british,canadian,%
423   english,newzealand,UKenglish,USenglish}{\\thename\}{}}%
424 \providecaptionname{american,australian,british,canadian,%
425   english,newzealand,UKenglish,USenglish}{\\ofthename\}{of the}%
426 \providecaptionname{american,australian,british,canadian,%
427   english,newzealand,UKenglish,USenglish}{\\fromname\}{from}%
428 \providecaptionname{american,australian,british,canadian,%
429   english,newzealand,UKenglish,USenglish}{\\fromplacename\}{from}%
430 \providecaptionname{american,australian,british,canadian,%
431   english,newzealand,UKenglish,USenglish}{\\referee\}{Referee}%
432 \providecaptionname{american,australian,british,canadian,%
433   english,newzealand,UKenglish,USenglish}{\\ordinalmalereferee\}{%
434   \\englishordinalmalereferee}%
435 \providecaptionname{american,australian,british,canadian,%
436   english,newzealand,UKenglish,USenglish}{\\ordinalfemalereferee\}{%
437   \\englishordinalfemalereferee}%
438 \providecaptionname{american,australian,british,canadian,%
439   english,newzealand,UKenglish,USenglish}{\\oralexaminationdatename\}{Date of
440   Oral Examination}%
441 \providecaptionname{american,australian,british,canadian,%
442   english,newzealand,UKenglish,USenglish}{\\durationname\}{Processing Time}%
443 \providecaptionname{american,australian,british,canadian,%
444   english,newzealand,UKenglish,USenglish}{\\matriculationnumbername\}{Matriculati
445 \providecaptionname{american,australian,british,canadian,%

```

```

446 english,newzealand,UKenglish,USenglish}{\coursename}{Course}%
447 \providecaptionname{american,australian,british,canadian,%
448 english,newzealand,UKenglish,USenglish}{\companyname}{Training Company}%
449 \providecaptionname{american,australian,british,canadian,%
450 english,newzealand,UKenglish,USenglish}{\examinationname}{Examination}%
451 \providecaptionname{american,australian,british,canadian,%
452 english,newzealand,UKenglish,USenglish}{\examinationdatename}{Date of
453 Examination}%
454 \providecaptionname{american,australian,british,canadian,%
455 english,newzealand,UKenglish,USenglish}{\indatename}{in}%
456 \providecaptionname{german,ngerman,austrian,naustrian,%
457 swissgerman,nswissgerman}{\chairmanname}{Dekan/Dekanin}%
458 \providecaptionname{german,ngerman,austrian,naustrian,%
459 swissgerman,nswissgerman}{\projectpapername}{Projektarbeit}%
460 \providecaptionname{german,ngerman,austrian,naustrian,%
461 swissgerman,nswissgerman}{\seminarpapername}{Seminararbeit}%
462 \providecaptionname{german,ngerman,austrian,naustrian,%
463 swissgerman,nswissgerman}{\studentresearchname}{Studienarbeit}%
464 \providecaptionname{german,ngerman,austrian,naustrian,%
465 swissgerman,nswissgerman}{\diplomathesisname}{Diplomarbeit}%
466 \providecaptionname{german,ngerman,austrian,naustrian,%
467 swissgerman,nswissgerman}{\degreethesisname}{Dissertation}%
468 \providecaptionname{german,ngerman,austrian,naustrian,%
469 swissgerman,nswissgerman}{\masterthesisname}{Master-Arbeit}%
470 \providecaptionname{german,ngerman,austrian,naustrian,%
471 swissgerman,nswissgerman}{\bachelorthesisname}{Bachelor-Arbeit}%
472 \providecaptionname{german,ngerman,austrian,naustrian,%
473 swissgerman,nswissgerman}{\ordinal}{\germanordinal}%
474 \providecaptionname{german,ngerman,austrian,naustrian,%
475 swissgerman,nswissgerman}{\femaleordinal}{\germanfemaleordinal}%
476 \providecaptionname{german,ngerman,austrian,naustrian,%
477 swissgerman,nswissgerman}{\maleordinal}{\germanmaleordinal}%
478 \providecaptionname{german,ngerman,austrian,naustrian,%
479 swissgerman,nswissgerman}{\presentedbyname}{eingereicht von}%
480 \providecaptionname{german,ngerman,austrian,naustrian,%
481 swissgerman,nswissgerman}{\advisorname}{Betreuer}%
482 \providecaptionname{german,ngerman,austrian,naustrian,%
483 swissgerman,nswissgerman}{\thename}{den}%
484 \providecaptionname{german,ngerman,austrian,naustrian,%
485 swissgerman,nswissgerman}{\ofthename}{der}%
486 \providecaptionname{german,ngerman,austrian,naustrian,%
487 swissgerman,nswissgerman}{\fromname}{von}%
488 \providecaptionname{german,ngerman,austrian,naustrian,%
489 swissgerman,nswissgerman}{\fromplacename}{aus}%
490 \providecaptionname{german,ngerman,austrian,naustrian,%
491 swissgerman,nswissgerman}{\refereename}{Gutachter}%
492 \providecaptionname{german,ngerman,austrian,naustrian,%
493 swissgerman,nswissgerman}{\ordinalmalereferee}{%
494 \germanordinalmalereferee}%

```

```

495 \providecaptionname{german,ngerman,austrian,naustrian,%
496   swissgerman,nswissgerman}{\ordinalfemalerefereename}{%
497   \germanordinalfemalerefereename}%
498 \providecaptionname{german,ngerman,austrian,naustrian,%
499   swissgerman,nswissgerman}{\femalerefereename}{Gutachterin}%
500 \providecaptionname{german,ngerman,austrian,naustrian,%
501   swissgerman,nswissgerman}{\oralexaminationdatename}{Datum der m\"undlichen
502 Pr\"ufung}%
503 \providecaptionname{german,ngerman,austrian,naustrian,%
504   swissgerman,nswissgerman}{\durationname}{Bearbeitungszeitraum}%
505 \providecaptionname{german,ngerman,austrian,naustrian,%
506   swissgerman,nswissgerman}{\matriculationnumbername}{Matrikelnummer}%
507 \providecaptionname{german,ngerman,austrian,naustrian,%
508   swissgerman,nswissgerman}{\coursesname}{Kurs}%
509 \providecaptionname{german,ngerman,austrian,naustrian,%
510   swissgerman,nswissgerman}{\companyname}{Ausbildungsfirma}%
511 \providecaptionname{german,ngerman,austrian,naustrian,%
512   swissgerman,nswissgerman}{\examinationname}{Pr\"ufung}%
513 \providecaptionname{german,ngerman,austrian,naustrian,%
514   swissgerman,nswissgerman}{\examinationdatename}{Tag der Pr\"ufung}%
515 \providecaptionname{german,ngerman,austrian,naustrian,%
516   swissgerman,nswissgerman}{\indatename}{im}%

```

englishordinalmalerefereename

```

517 \newcommand*{\englishordinalmalerefereename}[1]{%
518   \englishordinal{\#1} \refereename%
519 }

```

englishordinalfemalerefereename

```

520 \newcommand*{\englishordinalfemalerefereename}[1]{%
521   \englishordinalmalerefereename{\#1}%
522 }

```

\germanordinalmalerefereename

```

523 \newcommand*{\germanordinalmalerefereename}[1]{%
524   \ifnum #1<\@ne
525     \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
526       This package does only define German ordinal names for referees from 1}%
527   \else
528     \ifcase #1\or Erstgutachter\or Zweitgutachter\or Drittgutachter%
529     \or Viertgutachter\else
530       \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
531         This package does only define German ordinal names for referees up
532         to 4}%
533   \fi
534 \fi
535 \fi
536 }

```

```

\germanordinalfemalerefereename
 537 \newcommand*{\germanordinalfemalerefereename}[1]{%
 538   \germanordinalfemalerefereename{#1}in%
 539 }

\germanordinalmalecorrectorname
 540 \newcommand*{\germanordinalmalecorrectorname}[1]{%
 541   \ifnum #1<\@ne
 542     \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
 543       This package does only define German ordinal names for correctors from 1}
 544   \else
 545     \ifcase #1\or Erstkorrektor\or Zweitkorrektor\or Drittkorrektor%
 546     \or Viertkorrektor\else
 547       \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
 548         This package does only define German ordinal names for correctors up
 549         to 6}%
 550     \fi
 551   \fi
 552 }

\manordinalfemalecorrectorname
 553 \newcommand*{\manordinalfemalecorrectorname}[1]{%
 554   \germanordinalmalecorrectorname{#1}in%
 555 }

\englishordinal
 556 \newcommand*{\englishordinal}[1]{%
 557   \ifcsname engordnumber\endcsname
 558     \engordnumber{#1}%
 559   \else
 560     \ifnum #1<\@ne
 561       \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
 562         This package does only define English ordinals from 1}%
 563     \else
 564       \ifcase #1\or 1st\or 2nd\or 3rd\or 4th\or 5th\or 6th\or 7th\or 8th\or
 565       9th\or 10th\else
 566         \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
 567           This package does only define English ordinals from 1 to
 568           10.\MessageBreak
 569           You may load package 'engord' to improve support of english
 570           ordinals}%
 571     \fi
 572   \fi
 573 \fi
 574 }

\germanordinal
\germanmaleordinal
\germanfemaleordinal
 575 \newcommand*{\germanordinal}[1]{%
 576   \ifnum #1<\@ne

```

```

577     \PackageError{uni-titlepage}{Ordinal of '#1' not defined}{%
578         This package does only define german ordinals from 1}%
579     \else
580         #1.%  

581     \fi
582 }
583 \newcommand*\germanmaleordinal[1]{%
584     \ifcase #1
585         \PackageError{uni-titlepage}{Male ordinal of '#1' not defined}{%
586             This package does only define german male ordinals from 1}%
587             \or Erster\or Zweiter\or Dritter\or Vierter\or F\"unfter\or Sechster%
588             \or Siebter\or Achter\or Neunter\or Zehnter\else
589             \PackageError{uni-titlepage}{Male ordinal of '#1' not defined}{%
590                 This package does only define german male ordinals up to 10}%
591     \fi
592 }
593 \newcommand*\germanfemaleordinal[1]{%
594     \ifcase #1
595         \PackageError{uni-titlepage}{Female ordinal of '#1' not defined}{%
596             This package does only define german female ordinals from 1}%
597             \or Erste\or Zweite\or Dritte\or Vierte\or F\"unfte\or Sechste%
598             \or Siebte\or Achte\or Neunte\or Zehnte\else
599             \PackageError{uni-titlepage}{Female ordinal of '#1' not defined}{%
600                 This package does only define german female ordinals up to 10}%
601     \fi
602 }

```

4.3 The titlepage Drivers

```

603 \begingroup
604     \def\PackageNotLoadedError#1{%
605         \GenericError{%
606             (#1)\@spaces \@spaces \@spaces \@spaces
607         }{%
608             File '#1' Error: package 'uni-titlepage' hasn't been loaded%
609         }{%
610             This definition file was made to be loaded by package
611             'uni-titlepage'.\MessageBreak
612             You may not use it without package 'uni-titlepage'!\MessageBreak
613             See the documentation of package 'uni-titlepage' for explanation.%
614         }%
615     }%
616     \ifx\csname uni-titlepage.sty@vers\endcsname\relax
617         \PackageNotLoadedError{%
618             \DHBW title-DHBW.def%
619             \KOMAScript title-KOMAScript.def%
620             \TU-DD title-TU-DD.def%
621             \TU-HH title-TU-HH.def%
622             \Markus title-Markus-1.def%

```

```

623 <Markus & 2>      title-Markus-2.def%
624 <Spacer>        title-Spacer.def%
625 <KIT>          title-KIT.def%
626 <JT-Aufsaetze>    title-JT-Aufsaetze.def%
627 <JT-Geschichte>   title-JT-Geschichte.def%
628 <JT-Typography>   title-JT-Typography.def%
629 <WWUM>          title-WWUM.def%
630 <UKoLA>         title-UKoLa.def%
631   }%
632   \fi
633 \endgroup

```

Each style corresponds with an own member. Nevertheless most styles will not have options in their own, because string options should be global to make change of style very easy.

```

634 \DefineFamilyMember[%]
635 <DHBW>  DHBW%
636 <KOMAScript> KOMAScript%
637 <TU-DD>  TU-DD%
638 <TU-HH>  TU-HH%
639 <Markus & 1> Markus-1%
640 <Markus & 2> Markus-2%
641 <Spacer>  Spacer%
642 <KIT>    KIT%
643 <JT-Aufsaetze> JT-Aufsaetze%
644 <JT-Geschichte> JT-Geschichte%
645 <JT-Typography> JT-Typography%
646 <WWUM>   WWUM%
647 <UKoLa>  UKoLa%
648 ]{title}

```

Nevertheless some styles have their own switches:

blackborder *Trauerrand* at style TU-DD:

```
649 <TU-DD>\FamilyBoolKey[TU-DD]{title}{blackborder}{blackborder}
```

final Style TU-HH distinguishes between drafts and final thesis.

```
650 <TU-HH>\FamilyBoolKey[TU-HH]{title}{final}{final}
```

rulewidth Some styles have some variable rules at the title:

```

\title@rulewidth
  rulesep
\title@rulesep
  651 <*Spacer | JT-Aufsaetze | JT-Geschichte | Markus & 2>
  652 \providecommand*{\title@rulewidth}{%
  653 <Spacer | Markus & 2> 0pt%
  654 <JT-Aufsaetze | JT-Geschichte> .25\textwidth
  655 }
  656 \providecommand*{\title@rulesep}{%
  657 <Spacer | Markus & 2> \ifdim \title@rulewidth>\z@ 10pt\else \z@\fi
  658 <JT-Aufsaetze | JT-Geschichte> 1.5pt%
  659 }
  660 \DefineFamilyKey[%]

```

```

661 <Markus & 2> Markus-2%
662 <JT-Aufsaetze> JT-Aufsaetze%
663 <JT-Geschichte> JT-Geschichte%
664 <Spacer> Spacer%
665 ]{title}{rulewidth}{%
666   \gdef\title@rulewidth{\dimexpr #1\relax}%
667   \FamilyKeyStateProcessed
668 }
669 \DefineFamilyKey[%
670 <Markus & 2> Markus-2%
671 <JT-Aufsaetze> JT-Aufsaetze%
672 <JT-Geschichte> JT-Geschichte%
673 <Spacer> Spacer%
674 ]{title}{rulesep}{%
675   \gdef\title@rulesep{\dimexpr #1\relax}%
676   \FamilyKeyStateProcessed
677 }
678 </Spacer | JT-Aufsaetze | JT-Geschichte | Markus & 2>

```

An some has their own terms:

```

\presentationinformationUKoLA
\presentationinformationWWUM
\presentationinformationTUHH
\presentationinformationDHBW
\presentationinformationKIT

679 <*UKoLa>
680 \providecommand*{\presentationinformationUKoLa}{%
681   to optain the degree\\
682   \@academicgrade\\
683   of \@discipline\\
684 }
685 \providecaptionname{american,australian,british,canadian,%
686   english,newzealand,UKenglish,USenglish}{\presentationinformationUKoLa}{%
687   to optain the degree\\
688   \@academicgrade\\
689   of \@discipline\\
690 }%
691 \providecaptionname{german,ngerman,austrian,naustrian,%
692   swissgerman,nswissgerman}{\presentationinformationUKoLa}{%
693   zur Erlangung des Grades eines\\
694   \@academicgrade\\
695   im Studiengang \@discipline\\
696 }%
697 </UKoLa>
698 <*DHBW>
699 \providecommand*{\presentationinformationDHBW}{%
700   for the \examinationname{} of\\ [.5\baselineskip]
701   \@academicgrade\\ [Opt plus 1fill]
702   of \@discipline\\ [.5\baselineskip]
703   at the \@university{} \@place\\
704 }
705 \providecaptionname{american,australian,british,canadian,%
706   english,newzealand,UKenglish,USenglish}{\presentationinformationDHBW}{%

```

```

707   for the \examinationname\\[.5\baselineskip]
708   \@academicgrade\\[Opt plus 1fill]
709   of degree course \@discipline\\[.5\baselineskip]
710   at the \@university\ifx\@place\@empty\else\space\@place\fi
711 }%
712 \providecaptionname{german,ngerman,austrian,naustrian,%
713 swissgerman,nswissgerman}{\presentationinformationDHBW}{%
714 f\"ur die \examinationname{} zum\\[.5\baselineskip]
715 \@academicgrade\\[Opt plus 1fill]
716 des Studienganges \@discipline\\[.5\baselineskip]
717 an der \@university{}\ifx\@place\@empty\else\space\@place\fi
718 }%
719 /DHBW
720 (*TU-HH)
721 \providecommand*\{\presentationinformationTUHH}{%
722 \iffinal Of the \else The \fi Graduation Committee of the\\
723 \@university\\[.5ex]
724 to the Acquisition of the Academic Degree\\[.5ex]
725 \@academicgrade\\[.5ex]
726 \iffinal approved \else submitted \fi\@subject}
727 \providecaptionname{american,australian,british,canadian,%
728 english,newzealand,UKenglish,USenglish}{\presentationinformationTUHH}{%
729 \iffinal Of the \else The \fi Graduation Committee of the\\
730 \@university\\[.5ex]
731 to the Acquisition of the Academic Degree\\[.5ex]
732 \@academicgrade\\[.5ex]
733 \iffinal approved \else submitted \fi\@subject}
734 \providecaptionname{german,ngerman,austrian,naustrian,%
735 swissgerman,nswissgerman}{\presentationinformationTUHH}{%
736 \iffinal Vom \else Dem \fi Promotionsausschuss der\\
737 \@university\\[.5ex]
738 zur Erlangung des akademischen Grades\\[.5ex]
739 \@academicgrade\\[.5ex]
740 \iffinal genehmigte \else vorgelegte \fi\@subject}%
741 /KIT
742 (*KIT)
743 \providecommand*\{\presentationinformationKIT}{%
744 At the \@faculty\\
745 \strut\ignorespaces\@chair\\
746 }
747 \providecaptionname{american,australian,british,canadian,%
748 english,newzealand,UKenglish,USenglish}{\presentationinformationKIT}{%
749 At the \@faculty\\
750 \strut\ignorespaces\@chair\\
751 }%
752 \providecaptionname{german,ngerman,austrian,naustrian,%
753 swissgerman,nswissgerman}{\presentationinformationKIT}{%
754 An der \@faculty\\
755 \strut\ignorespaces\@chair\\

```

```

756 }%
757 </KIT>
758 <*WWUM>
759 \providecommand*\{presentationinformationWWUM}\{%
760   \@subject\%
761   to the Aquisition of the Academic Degree\%
762   \@academicgrade\%
763   of the \@science{} of \@discipline\%
764   of the \@faculty{} faculty\%
765   of the \@university
766 }
767 \providetextname{american,australian,british,canadian,%
768   english,newzealand,UKenglish,USenglish}\{presentationinformationWWUM}\{%
769   \@subject\%
770   to the Aquisition of the Academic Degree\%
771   \@academicgrade\%
772   of the \@science{} of \@discipline\%
773   of the \@faculty{} faculty\%
774   of the \@university
775 }
776 \providetextname{german,ngerman,austrian,naustrian,%
777   swissgerman,nswissgerman}\{presentationinformationWWUM}\{%
778   \@subject\%
779   zur Erlangung des \@academicgrade\%
780   der \@science{} im Fachbereich \@discipline\%
781   der \@faculty{} Fakult"at\%
782   der \@university
783 }
784 </WWUM>

\KITlongname
  \fromname
    785 <*KIT>
  \refereename
    786 \providetextname{american,australian,british,canadian,%
    787   english,newzealand,UKenglish,USenglish}\{\KITlongname}\{%
    788   University of the State of Baden-W"urttemberg and National Research Center
    789   of the Helmholtz Association%
    790 }%
    791 \providetextname{german,ngerman,austrian,naustrian,%
    792   swissgerman,nswissgerman}\{\KITlongname}\{%
    793   Universit"at des Landes Baden-W"urttemberg und nationales
    794   Forschungszentrum in der Helmholtz-Gemeinschaft
    795 }%
    796 \scr@ifundefinedorrelax{captionsamerican}{}\{%
    797   \renewcaptionname{american}\{\fromname\}{of}\%
    798   \renewcaptionname{american}\{\refereename\}{Reviewer}\%
    799 }%
    800 \scr@ifundefinedorrelax{captionsaustralian}{}\{%
    801   \renewcaptionname{australian}\{\fromname\}{of}\%
    802   \renewcaptionname{australian}\{\refereename\}{Reviewer}\%

```

```

803 }%
804 \scr@ifundefinedorrelax{captionsbritish}{}{%
805   \renewcaptionname{british}{\fromname}{of}%
806   \renewcaptionname{british}{\refereename}{Reviewer}%
807 }%
808 \scr@ifundefinedorrelax{captionscanadian}{}{%
809   \renewcaptionname{canadian}{\fromname}{of}%
810   \renewcaptionname{canadian}{\refereename}{Reviewer}%
811 }%
812 \scr@ifundefinedorrelax{captionsenglish}{}{%
813   \renewcaptionname{english}{\fromname}{of}%
814   \renewcaptionname{english}{\refereename}{Reviewer}%
815 }%
816 \scr@ifundefinedorrelax{captionsnewzealand}{}{%
817   \renewcaptionname{newzealand}{\fromname}{of}%
818   \renewcaptionname{newzealand}{\refereename}{Reviewer}%
819 }%
820 \scr@ifundefinedorrelax{captionsUKenglish}{}{%
821   \renewcaptionname{UKenglish}{\fromname}{of}%
822   \renewcaptionname{UKenglish}{\refereename}{Reviewer}%
823 }%
824 \scr@ifundefinedorrelax{captionsUSenglish}{}{%
825   \renewcaptionname{USenglish}{\fromname}{of}%
826   \renewcaptionname{USenglish}{\refereename}{Reviewer}%
827 }%
828 \newcommand*\KITurl{www.kit.edu}
829 </KIT>

\presentedbyname
\ordinalmalerefereename
830 <*WWUM | UKoLa>
831 \NowButAfterBeginDocument
832 }%
833 \providecaptionname{german,ngerman,austrian,naustrian,
834   swissgerman,nswissgerman}{\presentedbyname}{vorgelegt von}%
835 \scr@ifundefinedorrelax{captionsgerman}{}{%
836   \renewcaptionname{german}{\presentedbyname}{vorgelegt von}%
837   \renewcaptionname{german}{\ordinalmalerefereename}{%
838     \ordinalfemalecorrectorname}%
839 }%
840 \scr@ifundefinedorrelax{captionsngerman}{}{%
841   \renewcaptionname{ngerman}{\presentedbyname}{vorgelegt von}%
842   \renewcaptionname{ngerman}{\ordinalmalerefereename}{%
843     \germanordinalmalecorrectorname}%
844   \renewcaptionname{ngerman}{\ordinalfemalecorrectorname}{%
845     \germanordinalfemalecorrectorname}%
846 }%
847 \scr@ifundefinedorrelax{captionsaustrian}{}{%
848   \renewcaptionname{austrian}{\presentedbyname}{vorgelegt von}%
849   \renewcaptionname{austrian}{\ordinalmalerefereename}{%

```

```

850      \germanordinalmalecorrectorname}%
851      \renewcaptionname{austrian}{\ordinalfemalerefereename}{%
852          \germanordinalfemalecorrectorname}%
853  }%
854  \scr@ifundefinedorrelax{captionsnaustrian}{}{%
855      \renewcaptionname{naustrian}{\presentedbyname}{vorgelegt von}%
856      \renewcaptionname{naustrian}{\ordinalmalerefereename}{%
857          \germanordinalmalecorrectorname}%
858      \renewcaptionname{naustrian}{\ordinalfemalerefereename}{%
859          \germanordinalfemalecorrectorname}%
860  }%
861  \scr@ifundefinedorrelax{captionsswissgerman}{}{%
862      \renewcaptionname{swissgerman}{\presentedbyname}{vorgelegt von}%
863      \renewcaptionname{swissgerman}{\ordinalmalerefereename}{%
864          \germanordinalmalecorrectorname}%
865      \renewcaptionname{swissgerman}{\ordinalfemalerefereename}{%
866          \germanordinalfemalecorrectorname}%
867  }%
868  \scr@ifundefinedorrelax{captionsnswissgerman}{}{%
869      \renewcaptionname{nswissgerman}{\presentedbyname}{vorgelegt von}%
870      \renewcaptionname{nswissgerman}{\ordinalmalerefereename}{%
871          \germanordinalmalecorrectorname}%
872      \renewcaptionname{nswissgerman}{\ordinalfemalerefereename}{%
873          \germanordinalfemalecorrectorname}%
874  }%
875 }
876 </WWUM | UKoLa>

```

While style initialization, something may change:

```
877 \renewcommand*{\inittitle}{%
```

style KOMAScript redefines some footnote macros:

```

878 {*KOMAScript}
879   \let\footnotesize\small
880   \let\footnoterule\relax
881   \let\footnote\thanks
882   \renewcommand*\thefootnote{@fnsymbol\c@footnote}%
883   \let\@oldmakefnmark\@makefnmark
884   \renewcommand*{\@makefnmark}{\rlap{\@oldmakefnmark}}%
885 </KOMAScript>
```

styles DHBW, TU-DD, TU-HH, KIT, and UKoLa set some variable if not already done

```

886 <*DHBW | TU-DD | TU-HH | KIT | WWUM>
887   \ifx\@university\@empty
888     \university{%
889     <DHBW>      Dualen Hochschule%
890     <TU-DD>      Technische\nobreakspace Universit\"at\nobreakspace Dresden%
891     <TU-HH>      Technische\nobreakspace Universit\"at\nobreakspace
892     <TU-HH>      Hamburg-Harburg%}
```

```

893 <KIT>      KIT -- \KITlongname
894 <WWUM>       Westf\"alischen Wilhelms-Universit\"at M\"unster%
895   }%
896   \fi
897 </DHBW | TU-DD | TU-HH | KIT | WWUM>
898 <*DHBW | TU-DD | TU-HH | KIT | WWUM | UKoLa>
899   \ifx\@place\@empty
900     \place{%
901   <DHBW>      Baden-W\"urttemberg%
902   <TU-DD>      Dresden%
903   <TU-HH>      Hamburg%
904   <KIT>        Karlsruhe%
905   <*WWUM>
906     \PackageWarning{uni-titlepage}{Birth place missing.\MessageBreak
907       Style 'WWUM' needs the birth place of\MessageBreak
908       the student}%
909   </WWUM>
910   <UKoLa>      Koblenz%
911   }
912   \fi
913 <*DHBW | UKoLa>
914   \ifx\@mainlogo\@empty
915   <DHBW>      \IfFileExists{DHBW_d_MOS_195x95_rgb_300.jpg}{}%
916   <UKoLa>      \IfFileExists{uni-koblenz-landau.png}{}%
917     \scr@ifundefinedorrelax{includegraphics}{}%
918       \if@atdocument\else\RequirePackage{graphicx}\fi
919     }{}%
920     \scr@ifundefinedorrelax{includegraphics}{}{}%
921       \mainlogo{}%
922 <*DHBW>
923   \includegraphics[width=57mm,height=27mm]
924           {DHBW_d_MOS_195x95_rgb_300.jpg}%
925 </DHBW>
926 <*UKoLa>
927   \includegraphics[width=63mm,height=10mm]
928           {uni-koblenz-landau.png}
929 </UKoLa>
930   }%
931   }%
932   }{}%
933   \fi
934 </DHBW | UKoLa>
935 <*DHBW>
936   \ifx\@titlehead\@empty
937     \titlehead{\hspace*{\fill}\@mainlogo}%
938   \fi
939 </DHBW>
940 <*DHBW | UKoLa>
941   \ifx\@titlepagefont\@empty

```

```

942      \renewcommand*{\@titlepagefont}{%
943 <DHBW>      \normalfont\sffamily
944 <UKoLa>      \normalfont
945     }%
946   \fi
947 </DHBW | UKoLa>
948 <*KIT>
949   \ifx\@homepage\empty
950     \homepage{\KITurl}%
951   \fi
952   \ifx\@mainlogo\empty

```

Try to detect one of the suitable PNGs of the KIT logo from https://de.wikipedia.org/wiki/Datei:Logo_KIT.svg.

```

953   \def\KIT@logo{KITLogo_RGB.pdf}\IfFileExists{\KIT@logo}{}{%
954     \def\KIT@logo{2560px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
955       \def\KIT@logo{2000px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
956         \def\KIT@logo{1280px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
957           \def\KIT@logo{1024px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
958             \def\KIT@logo{1000px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
959               \def\KIT@logo{800px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
960                 \def\KIT@logo{640px-Logo_KIT.svg.png}\IfFileExists{\KIT@logo}{}{%
961                   \def\KIT@logo{500px-Logo_KIT.svg.png}%
962                 }}}}}}}}}%
963   \IfFileExists{\KIT@logo}{}%
964     \scr@ifundefinedorrelax{includegraphics}{%
965       \if@atdocument\else\RequirePackage{graphicx}\fi
966     }{%
967     \scr@ifundefinedorrelax{includegraphics}{%
968       \mainlogo{%
969         \includegraphics[width=40mm,height=18.5mm]{\KIT@logo}}%
970       }%
971     }%
972   }{%
973   \fi
974   \ifx\@titlehead\empty
975     \titlehead{\@mainlogo\hspace*{\fill}}%
976   \fi
977   \ifx\@titlepagefont\empty
978     \renewcommand*{\@titlepagefont}{\usefont{T1}{phv}{m}{n}}%
979   \fi
980 </KIT>
981 <*WWUM>
982   \ifx\@titlepagefont\empty
983     \renewcommand*{\@titlepagefont}{\normalfont\large}%
984   \fi
985 </WWUM>
986 </DHBW | TU-DD | TU-HH | KIT | WWUM | UKoLa>

```

style Markus-2 uses it's own pagestyle at the first title page

```

987 < *Markus & 2>
988   \def\ps@maintitle{%
989     \ps@empty
990     \def\@oddhead{%
991       \parbox[b]{\headheight}[b]{\hsize}{\@titlepagefont{%
992         \csname @titlehead\endcsname}}%
993     }%
994     \let\@evenhead\@oddhead
995   }%
996 </Markus & 2>

styles JT-Aufsaetze and JT-Geschichte set some font defaults:
997 < *JT-Aufsaetze | JT-Geschichte>
998   \ifx\@titlepagefont\empty
999   <JT-Aufsaetze> \renewcommand*\@titlepagefont{\normalfont\Huge\itshape}%
1000 < *JT-Geschichte>
1001   \scr@ifundefinedorrelax{\lsstyle}{%
1002     \renewcommand*\@titlepagefont{\normalfont\let\@tpf@extra\scshape}%
1003   }%
1004   \renewcommand*\@titlepagefont{%
1005     \normalfont\def\@tpf@extra{\lsstyle\MakeUppercase}%
1006   }%
1007   }%
1008 </JT-Geschichte>
1009   \fi
1010   \ifx\titlefont\empty
1011     \renewcommand*\titlefont{\normalfont}%
1012   \fi
1013 </JT-Aufsaetze | JT-Geschichte>
1014 < *JT-Typography>
1015   \ifx\@titlepagefont\empty
1016     \renewcommand*\@titlepagefont{\normalfont\sffamily\bfseries}%
1017   \fi
1018 </JT-Typography>
1019 }

\publishers KOMA-Script defines this macro. But we use \publisher instead.
1020 <KOMAScript>\providecommand*\publishers{\publisher}

\makemaintitle This differs from style to style:
1021 \renewcommand*\makemaintitle{%
1022   \begin{%
1023     <DHBW | TU-DD | TU-HH | KIT>    fullsizetitle}%
1024   < *KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM | UKoLa
1025     titlepage}%
1026 </KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM | UKoLa
1027   \setlength{\parskip}{\z@}%
1028   \setlength{\parindent}{\z@}%
1029   \setlength{\parfillskip}{\z@\plus 1fil}%

```

```

1030     \linespread{1}\selectfont
1031     \@titlepagefont
1032 {*DHBW}
1033     \vspace*{12mm}%
1034     \centering
1035     \begin{minipage}[t]{\dimexpr\vsiz-36mm\relax}{\dimexpr\hsize-40mm\relax}%
1036         \@titlehead\par
1037         \centering
1038         \Large
1039         \vfill
1040         {\@titlefont{\Large \@title}}\par
1041         \vfill
1042         {\@subject@font{\Large \@subject}\par}%
1043         \vfill
1044         \presentationinformationDHBW\par
1045         \vfill
1046         \fromname\\[.5\baselineskip]
1047         \author\par
1048         \vfill
1049         \date\par
1050         \vfill
1051         \begin{tabular}{*2{p{.5\dimexpr\linewidth-3\tabcolsep\relax}}@{}}
1052             \durationname & \duration \\ [.5ex]
1053             \matriculationnumbername, \coursename & \matriculationnumber,
1054                                         \course\\ [.5ex]
1055             \companyname & \company \\ [.5ex]
1056             \advisorname{} \ofthename{} \companyname & \advisor \\ [.5ex]
1057             \referee{} \ofthename{} \university & \referee
1058         \end{tabular}
1059     \end{minipage}
1060 
1061 {*KOMAScript}
1062     \ifx\@titlehead\empty \else
1063     \begin{minipage}[t]{\textwidth}%
1064         \@titlehead
1065     \end{minipage}\par
1066     \fi
1067     \null\vfill
1068     \begingroup
1069         \centering
1070         \ifx\@subject\empty \else
1071             {\@subject@font{\@subject}\par}%
1072             \vskip 3em
1073         \fi
1074         {\@titlefont{\huge \@title}\par}%
1075         \vskip 1em
1076         {\ifx\@subtitle\empty\else\@subtitlefont{\@subtitle}\par\fi}%
1077         \vskip 2em
1078         {\Large \lineskip 0.75em

```

```

1079      \begin{tabular}[t]{c}
1080          \author
1081          \end{tabular}\par
1082      }%
1083      \vskip 1.5em
1084      {\Large \@date \par}%
1085      \vskip \z@ \plus3fill
1086      {\Large \@publisher \par}%
1087      \vskip 3em
1088      \endgroup
1089      \thanks
1090      \vfill\null\vskip-\baselineskip
1091 \>{/KOMAScript}
1092 \>{*TU-DD}
1093     \rule{0pt}{5mm}\par
1094     \ifblackborder
1095         \leavevmode\hskip 1cm
1096         \setlength{\fboxrule}{1pt}%
1097         \expandafter\fbox
1098     \else
1099         \expandafter\mbox
1100     \fi
1101     }%
1102     \begin{minipage}[t][\dimexpr\textheight-2.5cm\relax][t]{%
1103         \dimexpr\linewidth\ifblackborder-3cm\fi\relax}
1104         \sffamily
1105         \centering
1106         \vskip 3cm
1107         {\fontsize{28pt}{34pt}\selectfont
1108             \strut\ignorespaces@university\unskip\strut\\}
1109         {\fontsize{24pt}{28pt}\selectfont
1110             \strut\ignorespaces@faculty\unskip\strut\\}
1111         {\fontsize{20pt}{24pt}\selectfont
1112             \strut\ignorespaces@chair\unskip\strut\\
1113             \strut\ignorespaces@professor\unskip\strut\\
1114             \vfill
1115             {\bfseries\strut\ignorespaces@title\unskip\strut\\}
1116             \strut\ignorespaces@subject\unskip\strut\\
1117             \vfill
1118             \raggedright
1119             \hskip*.25\linewidth}%
1120             \strut\ignorespaces\presentedbyname\unskip\strut\\
1121             \hskip*.25\linewidth\quad
1122             \begin{tabular}{@{}l@{}}
1123                 \strut\ignorespaces@author\unskip\strut\\
1124                 \strut\ignorespaces@discipline\unskip\strut\\
1125                 \strut\ignorespaces@matriculationnumber\unskip\strut\\
1126             \end{tabular} \\
1127             \vskip\baselineskip

```

```

1128          \hspace*{.25\linewidth}%
1129          \strut\ignorespaces\advisorname\unskip:\strut\%
1130          \hspace*{.25\linewidth}\quad
1131          \begin{tabular}{@{}l@{}}
1132              \strut\ignorespaces\@advisor\unskip\strut\%
1133          \end{tabular}
1134          \vskip2\baselineskip
1135          \hspace*{.25\linewidth}%
1136          \strut\ignorespaces\@place,\nobreakspace\thename\nobreakspace\@date
1137          \par}
1138          \vspace*{5mm}
1139      \end{minipage}
1140  }%
1141 </TU-DD>
1142 <*TU-HH>
1143     \sffamily
1144     \centering
1145     \vspace{5cm}
1146     {\LARGE\bfseries\strut\ignorespaces\@title\%}
1147     {\Large\strut\ignorespaces\@subtitle\%}
1148     \vspace{2.5cm}
1149     {\Large\presentationinformationTUHH\%}
1150     \vspace{2.5cm}
1151     {\Large\strut\ignorespaces\fromname\%
1152         \strut\ignorespaces\@author\%}
1153     \vspace{2.5cm}
1154     {\Large\strut\ignorespaces\fromplacename\%
1155         \strut\ignorespaces\@place\%}
1156     \vspace{2.5cm}
1157     {\Large\@date}
1158 </TU-HH>
1159 <*WWUM>
1160     \centering
1161     \@chair\%
1162     \vspace{2cm}
1163     \@title\%
1164     \vfill
1165     \presentationinformationWWUM\%
1166     \vfill
1167     \presentedbypname\%
1168     \@author\%
1169     \ifx\@place\@empty\else\fromplacename{}\ \@place\%\fi
1170     --\,\the\year\,--
1171 </WWUM>
1172 <*Markus & 1>
1173     \raggedright
1174     {\subject@font{%
1175         \large\strut\ignorespaces\@subject\par\vskip 2\baselineskip\%}
1176         {\titlefont{\LARGE\strut\ignorespaces\@title\par}}\%}

```

```

1177      {\@subtitlefont{%
1178          \large\skip.5\baselineskip\strut\ignorespaces\@subtitle\par}}%
1179      \vfill
1180      {\csname @datefont\endcsname{\large\strut\ignorespaces\@date\par}}%
1181 〈/Markus & 1〉
1182 〈*Spacer | Markus & 2〉
1183      \raggedright
1184 〈Markus & 2〉      \thispagestyle{maintitle}%
1185      \raisebox{0pt}[\ht\strutbox][\dimexpr\textheight-\ht\strutbox\relax]{%
1186          \rule[\dimexpr-.667\headsep-\textheight\relax]{\title@rulewidth}{%
1187              \dimexpr\textheight+2\headsep\relax}\kern\title@rulesep}%
1188      \parbox[t][\textheight][t]{\dimexpr\textheight-\title@rulewidth-\title@rulesep\relax}%
1189      \parbox[t][\textheight][t]{\dimexpr\textheight-\title@rulewidth-\title@rulesep\relax}%
1190      \raggedright
1191 〈*Spacer〉
1192      \ifx\@titlehead\empty\else
1193          \raisebox{\dimexpr\ht\strutbox-\totalheight\relax}{%
1194              \parbox[t]{\linewidth}{\@titlehead}}%
1195          \par
1196          \vskip 2\baselineskip
1197      \fi
1198 〈/Spacer〉
1199      {\leavevmode\subject@font{%
1200          \large\strut\ignorespaces\@subject\par\vskip 2\baselineskip}%
1201          {\def\and{\ }\csname @authorfont\endcsname{\large\@author}\par
1202              \vskip .5\baselineskip}%
1203          {\titlefont{\LARGE\strut\ignorespaces\@title\par}}%
1204          {\@subtitlefont{%
1205              \large\skip.5\baselineskip\strut\ignorespaces\@subtitle\par}}%
1206          \vfill
1207          {\csname @publisherfont\endcsname{\large\@publisher\par}}%
1208          {\csname @datefont\endcsname{\large\strut\ignorespaces\@date\par}}%
1209      }%
1210 〉%
1211 〈/Spacer | Markus & 2〉
1212 〈*KIT〉
1213      \setlength{\unitlength}{1mm}%
1214      \begin{picture}(0,0)
1215          \put(15,-12){%
1216              \line(1,0){\dimexpr\paperwidth-37mm\relax\@gobble}%
1217          }%
1218          \put(\dimexpr\paperwidth-22mm\@gobble,-19){\oval(14,14)[rt]}%
1219          \put(\dimexpr\paperwidth-15mm\@gobble,-19){%
1220              \line(0,-1){\dimexpr\paperheight-37mm\relax\@gobble}%
1221          }%
1222          \put(22,-\dimexpr\paperheight-18mm\relax\@gobble){%
1223              \line(1,0){\dimexpr\paperwidth-37mm\relax\@gobble}%
1224          }%
1225          \put(22,-\dimexpr\paperheight-25mm\relax\@gobble){\oval(14,14)[lb]}%

```

```

1226      \put(15,-\dimexpr\paperheight-25mm\relax\@gobble){%
1227          \line(0,1){\dimexpr\paperheight-37mm\relax\@gobble}%
1228      }%
1229      \end{picture}\par
1230      \vskip\dimexpr -\baselineskip+25mm\relax
1231      \hspace*{27mm}%
1232      \begin{minipage}[t][\dimexpr\paperheight-68mm\relax][t]
1233          \dimexpr\paperwidth-54mm\relax
1234          \raggedright\@titlehead\par
1235          \centering
1236          \vskip 25mm
1237          {\@titlepagefont\@title\par}%
1238          \vskip 20mm
1239          {\Large\@subject\\\fromname\par}
1240          \vskip 1cm
1241          {\huge\@author\par}
1242          \vskip 1cm
1243          {\Large\presentationinformationKIT\par}
1244          \vskip 2cm
1245          {\Large
1246              \let\@tempa\refereename
1247              \def\@tempb{1}%
1248              \def\and{%
1249                  \\
1250                  \xdef\@tempb{\the\numexpr\@tempb+1\relax}%
1251                  \expandafter\ordinal\expandafter{\@tempb}~\@tempa: &
1252              }%
1253              \begin{tabular}{@{}lr@{}}
1254                  \refereename: & \@referee \\
1255                  \global\let\@tempa\advisorname\xdef\@tempb{1}%
1256                  \advisorname: & \@advisor \\
1257              \end{tabular}\par
1258          }
1259          \vfill
1260          {\large \durationname: \@duration\par}
1261      \end{minipage}
1262      \vskip 35mm
1263      \hspace*{27mm}\makebox[\dimexpr\paperwidth-56mm\relax]{%
1264          \tiny\@university\hfill\large\textrm{\bf{\@homepage}}%
1265      }%
1266  
```

```

1267  */<JT-Aufsaetze>
1268  \centering
1269  \author\%
1270  \begin{picture}(\title@rulewidth\@gobble,
1271      \dimexpr .3ex+1pt+\title@rulesep\relax\@gobble)
1272      \put(0,\dimexpr .15ex+.5pt+\title@rulesep\relax\@gobble){%
1273          \linethickness{.3ex}\line(1,0){\title@rulewidth\@gobble}%
1274      }%

```

```

1275      \put(0,0){%
1276          \linethickness{1pt}\line(1,0){\title@rulewidth\@gobble}%
1277      }%
1278      \end{picture}\\\[\baselineskip]
1279      {\titlefont{\@title\par}}%
1280      \vfill
1281      \@publisher
1282 </JT-Aufsaetze>
1283 <*JT-Geschichte>
1284      \centering
1285      \large{\@tpf@extra{\@author\unskip\strut}}\\[\dp\strutbox]
1286      {\titlefont{\Huge \@title\par}}%
1287      \vfill
1288      \begin{picture}(\title@rulewidth\@gobble,
1289          \dimexpr 4pt+1pt+\title@rulesep\relax\@gobble)
1290          \put(0,\dimexpr 2pt+.5pt+\title@rulesep\relax\@gobble){%
1291              \linethickness{1pt}\line(1,0){\title@rulewidth\@gobble}%
1292          }%
1293          \put(0,0){%
1294              \linethickness{4pt}\line(1,0){\title@rulewidth\@gobble}%
1295          }%
1296          \end{picture}\\[\dp\strutbox]
1297          \@tpf@extra{\@publisher}%
1298          \ifx\@place\empty\else
1299              \unskip\@tpf@extra{\strut}\\[\dp\strutbox]\@tpf@extra{\@place}%
1300          \fi
1301 </JT-Geschichte>
1302 <*JT-Typography>
1303      \raggedright
1304      {\Large\MakeUppercase{\@author}}\\[\baselineskip]
1305      {\titlefont{\Huge\MakeUppercase{\@title}\unskip\strut}}%
1306      {\@subtitlefont{\normalsize\MakeUppercase{\@subtitle}}}%
1307      \vfill
1308      {\normalsize\MakeUppercase{\@place}\ifx\@place\empty\else\enskip\fi
1309          {\LARGE\MakeUppercase{\@date}}%
1310          \ifx\@publisher\empty\else\unskip\strut\\[1.5\baselineskip]
1311              \MakeUppercase{\@publisher}%
1312          \fi}
1313 </JT-Typography>
1314 <*UKoLa>
1315      \begin{tabular}[t]{@{}c@{}}
1316          \raisebox{\dimexpr\ht\strutbox-\height}{\@mainlogo}\\
1317          \@chair\\
1318      \end{tabular}\hfill
1319      \begin{tabular}[r]{@{}c@{}}
1320          \raisebox{\dimexpr\ht\strutbox-\height}{\@secondlogo}\\
1321      \end{tabular}\par
1322      \vspace{5\baselineskip}
1323      \centering

```

```

1324   {\LARGE\bfseries\titlefont{\@title\par}}%
1325   \vspace{5\baselineskip}
1326   {\Large\subjectfont{\@subject\par}}%
1327   \vspace{\baselineskip}
1328   \presentationinformationUKoLa\par
1329   \vspace{5\baselineskip}
1330   \presentedbyname\\[\baselineskip]
1331   {\Large\csname @authorfont\endcsname{\@author\par}}%
1332   \vfill
1333   \raggedright
1334   \changefrom{\advisorname: }{\@advisor\par}%
1335   \newcommand*{\test@male@female}[1][m]{%
1336     \global\advance\@tempcnta by\@ne
1337     \Ifstr{##1}{f}{\def\fe@male@female}{\def\fe@male@male}%
1338     \changefrom{\csname ordinal\fe@male referee\endcsname{\@tempcnta}: }{%
1339       \def\and{\par\test@male@female}%
1340     }%
1341     \atempcnta \z@%
1342     \expandafter\test@male@female\@referee\par
1343     \vspace{3\baselineskip}
1344     \place, \Ifstr{\indatename}{\{}{\{}\indatename\ }\@\date\par
1345   }/{UKoLa}
1346   \end{%
1347   {DHBW | TU-DD | TU-HH | KIT}    fullsizetitle}
1348   {*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM | UKoLa
1349   titlepage}
1350   /{KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography | WWUM | UKoLa
1351 }

```

Some of the styles need additional string options for the back of the main title. These are more structural than logical, so we do not define those globally!

```

upptitleback
\upptitleback
 1352 {*KOMAScript | Markus | Spacer}
@upptitleback
 1353 \providecommand*{\@upptitleback}{}%
 1354 \providecommand{\upptitleback}[1]{\gdef\@upptitleback{#1}}
 1355 \DefineFamilyKey[%]
 1356 {KOMAScript} KOMAScript%
 1357 {Markus & 1} Markus-1%
 1358 {Markus & 2} Markus-2%
 1359 {Spacer} Spacer%
 1360 {JT-Aufsaetze} JT-Aufsaetze%
 1361 {JT-Geschichte} JT-Geschichte%
 1362 {JT-Geschichte} JT-Typography%
 1363 ]{title}{upptitleback}{\upptitleback{#1}\FamilyKeyStateProcessed}
 1364 \providecommand*{\@lowertitleback}{}%
 1365 \providecommand{\lowertitleback}[1]{\gdef\@lowertitleback{#1}}
 1366 \DefineFamilyKey[%]

```

```

1367 <KOMAScript> KOMAScript%
1368 <Markus & 1> Markus-1%
1369 <Markus & 2> Markus-2%
1370 <Spacer> Spacer%
1371 <JT-Aufsaetze> JT-Aufsaetze%
1372 <JT-Geschichte> JT-Geschichte%
1373 <JT-Geschichte> JT-Typography%
1374 ]{title}{lowertitleback}{\lowertitleback{\#1}\FamilyKeyStateProcessed}
1375 </KOMAScript | Markus | Spacer>

```

\makemaintitleback Only some of the styles define this:

```

1376 {*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography}
1377 \renewcommand*{\makemaintitleback}{%
1378   \begin{titlepage}
1379     \begin{minipage}[t]{\textwidth}
1380       \titlepagefont{\@uppertitleback}%
1381     \end{minipage}\par
1382     \vfill
1383     \begin{minipage}[b]{\textwidth}
1384       \titlepagefont{\@lowertitleback}%
1385     \end{minipage}
1386   \end{titlepage}
1387 }
1388 </KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1389 <*TU-HH>
1390 \renewcommand*{\makemaintitleback}{%
1391   \begin{titlepage}
1392     \vspace*{\fill}
1393     \iffinal
1394       \@tempcnta\z@%
1395       \def\and{%
1396         \par\advance\@tempcnta by\@ne
1397         \hangfrom{%
1398           \expandafter\ordinal\expandafter{\the\@tempcnta}\~\refereename:\enskip
1399         }%
1400       }\and\@referee
1401     \fi
1402     \vskip 1cm
1403     \iffinal
1404       \hangfrom{\oralexaminationdatename:\enskip}{\oralexaminationdate}%
1405     \fi
1406   \end{titlepage}
1407 }
1408 </TU-HH>
1409 <*WWUM>
1410 \renewcommand*{\makemaintitleback}{%
1411   \begin{titlepage}
1412     \vspace*{\fill}
1413     \noindent

```

```

1414     \z@tempcnta\z@
1415     \def\arraystretch{2}%
1416     \newcommand*\test@malefemale}[1][m]{%
1417         \global\advance\z@tempcnta by@ne
1418         \Ifstr{##1}{f}{\def\fe@male{female}}{\def\fe@male{male}}%
1419         \csname \fe@male ordinal\endcsname\z@tempcnta\space
1420         \csname \fe@male refereename\endcsname: &
1421         \def\and{\\\test@malefemale}%
1422     }%
1423     \begin{tabular}{@{}l@{}}
1424         \chairmanname: & \professor \\
1425         \expandafter\test@malefemale
1426         \referee \\
1427         \oralexaminationdatename: & \oralexaminationdate
1428         \ifx\examinationdatename\empty\else
1429             \\\examinationdatename: &
1430         \fi
1431         \\
1432     \end{tabular}
1433 \end{titlepage}
1434 }
1435 
```

Some of the styles need additional string options for the pre title. These are more structural than logical, so we do not define those globally!

```

extratitle
\extratitle 1436 {*KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography}
@extratitle 1437 \providecommand*\@extratitle(){}
1438 \providecommand{\extratitle}[1]{\gdef\@extratitle{#1}}
1439 \DefineFamilyKey[%]
1440 {KOMAScript} KOMAScript%
1441 {Markus & 2} Markus-2%
1442 {Spacer} Spacer%
1443 {JT-Aufsaetze} JT-Aufsaetze%
1444 {JT-Geschichte} JT-Geschichte%
1445 {JT-Typography} JT-Typography%
1446 ]{title}{extratitle}{\extratitle{#1}\FamilyKeyStateProcessed}
1447 
```

\makepretitle Only some styles have pre titles:

```

\makepretitleback 1448 {*KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography}
1449 \renewcommand*\makepretitle}{%
1450     \ifx\@extratitle\empty\else
1451         \begin{titlepage}
1452             \noindent\@extratitle
1453         \end{titlepage}
1454     \fi
1455 }%
```

```

1456 </KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1457 <*Markus & 1>
1458 \renewcommand{\makepretitle}{%
1459   \ifx\@publisher\empty\else
1460     \begin{titlepage}
1461       \raggedleft
1462       {\@titlepagefont{%
1463         \large\strut\ignorespaces\@publisher\par}}%
1464     \end{titlepage}
1465   \fi
1466 }
1467 </Markus & 1>
1468 <*WWUM>
1469 \renewcommand{\makepretitle}{%
1470   \begin{fullsizetitle}
1471     \@titlepagefont
1472     \vspace{.33\vsizetitle}%
1473   \centering
1474   \author\,[1ex]
1475   \title\,[1ex]
1476   \the\year
1477   \end{fullsizetitle}
1478 }
1479 </WWUM>
1480 </KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1481 \renewcommand{\makepretitleback}{%
1482   \ifx\@extratitle\empty\else\begin{titlepage}\null\end{titlepage}\fi
1483 }
1484 </KOMAScript | Markus & 2 | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography>
1485 <*Markus & 1>
1486 \renewcommand{\makepretitleback}{%
1487   \ifx\@author\empty\else
1488     \ifx\@publisher\empty\begin{titlepage}\end{titlepage}\fi
1489     \begin{titlepage}
1490       \raggedleft
1491       {\@titlepagefont{%
1492         \large\null\vskip 2\baselineskip
1493         \LARGE\strut{\def\and{\hspace{1em}}\linebreak[3]}%
1494         \csname @authorfont\endcsname{\large\ignorespaces\@author\par}}}%
1495     \end{titlepage}
1496   \fi
1497 }
1498 </Markus & 1>
1499 <*WWUM>
1500 \renewcommand{\makepretitleback}{%
1501   \if@twoside\begin{titlepage}\null\end{titlepage}\fi
1502 }
1503 </WWUM>

```

```

\makeposttitle    And only some styles provides one more title page with dedication.
\makeposttitleback
1505 {*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography}
1506 \renewcommand*{\makeposttitle}{%
1507   \ifx\@dedication\empty\else
1508     \begin{titlepage}
1509       \null\fill
1510       {\centering\csname\@dedicationfont\endcsname{\@dedication \par}}%
1511       \vskip \z@ \plus 3fill
1512     \end{titlepage}
1513   \fi
1514 }
1515 \renewcommand*{\makeposttitleback}{%
1516   \ifx\@dedication\empty\else\begin{titlepage}\null\end{titlepage}\fi
1517 }
1518 {*KOMAScript | Markus | Spacer | JT-Aufsaetze | JT-Geschichte | JT-Typography}

```

4.4 The Examples and the Manual

```

1519 \documentclass[a4paper, pagesize]{scrbook}
1520 \usepackage[ngerman]{babel}
1521 \usepackage[T1]{fontenc}
1522 \usepackage{lmodern}
1523 {JT-Geschichte}\usepackage{microtype}
1524 {TU-HH | TU-DD}\usepackage{mathpazo}
1525 {TU-HH | TU-DD}\usepackage[scaled]{helvet}
1526 {DHBW | Spacer | KIT | UKoLa}\usepackage[demo]{graphicx}% remove option demo if you
1527 \usepackage{xcolor}
1528 {JT-Geschichte | JT-Typography}\colorlet{RED}{red}% because of \MakeUppercase{\texttt{...}}
1529 \usepackage{uni-titlepage}
1530 \begin{document}
1531 {*DHBW}
1532 \TitlePageStyle{DHBW}
1533 \makeatletter\providecommand*{\@titlepagefont}{\normalfont\sffamily}\makeatother
1534 \setkomafont[subject]{\sffamily\bfseries}
1535 \maketitle[%]
1536   titlefont=\sffamily,
1537   mainlogo=\textcolor{red}{{}%
1538     % You may add a company logo here!
1539     % NOTE: The original logo has a large white border!
1540     \includegraphics[width=57mm, height=27mm]%
1541     {DHBW_d_MOS_195x95_rgb_300.jpg}%
1542   },
1543   % You may additionally change titlehead. The original definition of
1544   % titlehead is:
1545   titlehead={\hspace*{\fill}\useitlelement{mainlogo}},
1546   title=\textcolor{red}{Bachelorarbeitsthema},
1547   subject=\textcolor{red}{BACHELORARBEIT},
1548   academicgrade=\textcolor{red}{Bachelor of Engineering},
1549   discipline=\textcolor{red}{Studiengang},

```

```

1550 place=\textcolor{red}{\{Baden-Württemberg \textcolor{red}{\{Stadt}\}},}
1551 student=\textcolor{red}{\{Vorname Nachname\}},%
1552 duration=\textcolor{red}{\{12 Wochen\}},%
1553 matriculationnumber=\textcolor{red}{\{Matrikelnummer\}},%
1554 course=\textcolor{red}{\{Kurskürzel\}},%
1555 company=\textcolor{red}{\{Firmenname, Stadt\}},%
1556 advisor=\textcolor{red}{\{Titel Vorname Nachname\}},%
1557 referee=\textcolor{red}{\{Titel Vorname Nachname\}},%
1558 date=\textcolor{red}{\{Abgabedatum\}}
1559 ]
1560 
```

1561 <*TU-DD>

1562 \TitlePageStyle{TU-DD}

1563 \maketitle[%

1564 title=\textcolor{red}{\{Titel im Stil \texttt{TU-DD}\}},%
1565 university=\textcolor{red}{\{%

1566 Technische\nobreakspace Universit\"at\nobreakspace Dresden\},%

1567 faculty=\textcolor{red}{\{Fakultät Wirtschaftswissenschaften\}},%

1568 chair=\textcolor{red}{\{SAP-Stiftungslehrstuhl für\\

1569 Entrepreneurship und Innovation\}},

1570 professor=\textcolor{red}{\{Prof.\,Dr.\,Michael Schefcyk\}},

1571 % subject=diploma, % one of: project, seminar, studentresearch,%
1572 % % diploma, degree, master, bachelor, or ...

1573 subject=\textcolor{red}{\{Seminararbeit\|(bzw. Diplomarbeit)\},% ... direct value}}

1574 student=\textcolor{red}{\{Vorname und Name\}},

1575 discipline=\textcolor{red}{\{Studienrichtung\}},

1576 matriculationnumber=\textcolor{red}{\{Matrikel-Nr.\}},

1577 advisor=\textcolor{red}{\{(mit akadem. Grad, Vor- und Zuname\)},

1578 date=\textcolor{red}{\{(Datum der Abgabe\)}}}

1579]

1580

1581 \TitleOptions[pagenumber=1,blackborder]\% same with 'Trauerrand'

1582 \maketitle\% everything else, like above

1583

1584 <*KOMAScript>

1585 \TitlePageStyle[pagenumber=1]{KOMAScript}

1586 \maketitle[

1587 extratitle=\textcolor{red}{\{Das ist ein Schmutztitel im Stil \texttt{KOMAScript}\}},

1588 titlehead=\textcolor{red}{\{Den Kopfbereich kann man auf diese Weise füllen.\}},

1589 subject=\textcolor{red}{\{Eine Klassifizierung der Arbeit\}},

1590 title=\textcolor{red}{\{Titel im Stil \texttt{KOMAScript}\}},

1591 subtitle=\textcolor{red}{\{Untertitel\}},

1592 publisher=\textcolor{red}{\{Einen Verlag kann man ebenfalls angeben\}},

1593 uppertitleback=\textcolor{red}{\{Oberer Bereich der Rückseite des Haupttitels i

1594 \texttt{KOMAScript}\}},

1595 lowertitleback=\textcolor{red}{\{Unterer Bereich der Rückseite des Haupttitels i

1596 \texttt{KOMAScript}\}},

1597 dedication=\textcolor{red}{\{Eine Widmung im Stil \texttt{KOMAScript}\}}}

1598]

```

1599 </KOMAScript>
1600 <*TU-HH>
1601 \TitlePageStyle[pagenumber=1]{TU-HH}
1602 \maketitle[%]
1603   final,
1604   title=\textcolor{red}{Titel im Stil \texttt{TU-HH}}},
1605   university=\textcolor{red}{Technischen Universität Hamburg-Harburg},
1606   subject=degree,
1607   academicgrade=\textcolor{red}{Doktor der Naturwissenschaften (Dr.\,rer.\,nat\,)}},
1608   place=\textcolor{red}{(Geburtsort)},
1609   date=\textcolor{red}{(aktuelles Jahr)},
1610   referee=\textcolor{red}{Name des ersten Gutachters\protect\and Name des zweiten Gutachters},
1611   oralexaminationdate=\textcolor{red}{29. Februar 2009}
1612 ]
1613 ]
1614 </TU-HH>
1615 <*Markus | Spacer>
1616 % Maybe we should define one more option for this:
1617 \setkomafont{subject}{\normalfont\sffamily}% because of KOMA-Script class
1618 \setkomafont{title}{\normalfont\sffamily}% because of KOMA-Script class
1619 <*>
1620 \TitlePageStyle[pagenumber=1]{Markus-1}
1621 \maketitle[%]
1622   titlepagefont={\normalfont\sffamily},% to show is without KOMA-Script class
1623   title=\textcolor{red}{Titel im Stil \texttt{Markus-1}}},
1624   subject=\textcolor{red}{Eine Klassifizierung der Arbeit},
1625   subtitle=\textcolor{red}{Untertitel},
1626   publisher=\textcolor{red}{Verlag},
1627   uppertitleback=\textcolor{red}{Oberer Bereich der Rückseite des Haupttitels
1628   im Stil \texttt{Markus-1}.},
1629   lowertitleback=\textcolor{red}{Unterer Bereich der Rückseite des Haupttitels
1630   im Stil \texttt{Markus-1}.},
1631   dedication=\textcolor{red}{Eine Widmung im Stil \texttt{Markus-1}}},
1632   author=\textcolor{red}{Markus~Kohm\protect\and Sonst~Jemand}
1633 ]
1634 </1>
1635 <*2 | Spacer>
1636 <2> \TitlePageStyle[pagenumber=1]{Markus-2}
1637 <Spacer> \TitlePageStyle[pagenumber=1]{Spacer}
1638 \maketitle[%]
1639   rulewidth=2pt,
1640   extratitle=\textcolor{red}{Das ist ein Schmutztitel im Stil \texttt{%
1641 <2>      Markus-2}}},
1642 <Spacer>      Spacer}},
1643 <*Spacer>
1644   titlehead=\textcolor{red}{\includegraphics{Logo}}},
1645 </Spacer>
1646   title=\textcolor{red}{Titel im Stil \texttt{%
1647 <2>      Markus-2}}},

```

```

1648 <Spacer>      Spacer}},
1649   subject=\textcolor{red}{Eine Klassifizierung der Arbeit},
1650   subtitle=\textcolor{red}{Untertitel},
1651   publisher=\textcolor{red}{Verlag},
1652   uppertitleback=\textcolor{red}{Oberer Bereich der Rückseite des Haupttitels
1653     im Stil \texttt{%
1654 <2>      Markus-2}.},
1655 <Spacer>      Spacer}.},
1656   lowertitleback=\textcolor{red}{Unterer Bereich der Rückseite des Haupttitels
1657     im Stil \texttt{%
1658 <2>      Markus-2}.},
1659 <Spacer>      Spacer}.},
1660   dedication=\textcolor{red}{Eine Widmung im Stil \texttt{%
1661 <2>      Markus-2}},
1662 <Spacer>      Spacer}},
1663   author=\textcolor{red}{Markus~Kohm}
1664 ]
1665 </2 | Spacer>
1666 </Markus | Spacer>
1667 <*KIT>
1668 \TitlePageStyle{KIT}
1669 \maketitle[%  

1670   mainlogo={\textcolor{red}{%
1671     \includegraphics[width=40mm,height=18.5mm]{KITLogo_RGB}}},%
1672   % You may additionally change titlehead. Original definition of titlehead
1673   % is:
1674   titlehead={\usetitleelement{mainlogo}\hspace*\{\fill\}},%
1675   title=\textcolor{red}{Titel der Arbeit\im Stil \texttt{KIT}}},%
1676   subject=\textcolor{red}{Klassifizierung der Arbeit},%
1677   author=\textcolor{red}{Markus~Kohm},%
1678   faculty=\textcolor{red}{Fakultät für Informatik},%
1679   chair=\textcolor{red}{%
1680     Institute for Program Structures\and Data Organization (IPA)},%
1681   advisor={\textcolor{red}{Titel Vorname Nachname}\and
1682     \textcolor{red}{Titel Vorname Nachname}},%
1683   referee={\textcolor{red}{Titel Vorname Nachname}\and
1684     \textcolor{red}{Titel Vorname Nachname}},%
1685   duration=\textcolor{red}{XX. Monat 20XX -- XX. Monat 20XX}},%
1686   university=\textcolor{red}{\KITlongname},%
1687   homepage=\textcolor{red}{\KITurl}}%
1688 ]
1689 </KIT>
1690 <*JT-Aufsaetze>
1691 \TitlePageStyle{JT-Aufsaetze}
1692 \maketitle[%  

1693   % There are only three official elements:
1694   author={\textcolor{red}{Markus Kohm}},%
1695   title={\textcolor{red}{Titel der Arbeit angelehnt an Jan Tschicholds
1696     ausgewählte Aufsätze über Fragen der Gestalt des Buches und der

```

```

1697     Typography}},
1698     titlefont=\normalfont,% You may change the font of the main title
1699     publisher={\textcolor{red}{Der Verlag}}
1700     % Nevertheless, you may use extratitle, lowertitleback and uppertitleback.
1701     % See Markus-2 for more information about those.
1702 ]
1703 </JT-Aufsaetze>
1704 <*JT-Geschichte>
1705 \TitlePageStyle{JT-Geschichte}
1706 \maketitle[%]
1707     % There are only four official elements:
1708     author={\textcolor{red}{Markus Kohm}},%
1709     title={\textcolor{red}{Titel der Arbeit angelehnt an Jan Tschicholds
1710         Geschichte der Schrift in Bildern}}},
1711     titlefont=\itshape,% You may change the font of the main title
1712     publisher={\textcolor{red}{Der Verlag in seiner Langform}},%
1713     place={\textcolor{red}{Der Ort}}}
1714     % Nevertheless, you may use extratitle, lowertitleback and uppertitleback.
1715     % See Markus-2 for more information about those.
1716 ]
1717 </JT-Geschichte>
1718 <*JT-Typography>
1719 \TitlePageStyle{JT-Typography}
1720 \maketitle[%]
1721     % There are only four official elements:
1722     author={\textcolor{red}{Markus Kohm}},%
1723     title={\textcolor{red}{Titel der Arbeit}},%
1724     subtitle={\textcolor{red}{angelehnt an the new Typography}},%
1725     publisher={\textcolor{red}{Veröffentlicht für einen Verlag oder auch nicht}},%
1726     place={\textcolor{red}{Der Ort}}},%
1727     date={\textcolor{red}{2012}}}
1728     % Nevertheless, you may use extratitle, lowertitleback and uppertitleback.
1729     % See Markus-2 for more information about those.
1730 ]
1731 </JT-Typography>
1732 <*WWUM>
1733 \TitlePageStyle{WWUM}
1734 \renewcaptionname{ngerman}{\examinationdatename}{Tag der Promotion}
1735 \% \renewcaptionname{ngerman}{\examinationdatename}{}
1736 \% \renewcaptionname{ngerman}{\chairmannname}{Dekan}
1737 \% \renewcaptionname{ngerman}{\chairmannname}{Dekanin}
1738 \maketitle[%]
1739     title={\textcolor{red}{Titel der Arbeit}},%
1740     subject={\textcolor{red}{Inaugural-Dissertation}},%
1741     academicgrade={\textcolor{red}{Doktorgrades}},%
1742     discipline={\textcolor{red}{Physik}},%
1743     science={\textcolor{red}{Naturwissenschaften}}},%
1744     chair={\textcolor{red}{Experimentelle Physik}},%
1745     faculty={\textcolor{red}{Mathematisch-Naturwissenschaftlichen}},%

```

```

1746   author=\textcolor{red}{Mein Name},
1747   place=\textcolor{red}{Geburtsort},
1748   referee=\textcolor{red}{Peter Mustermann}\and
1749     [f]\textcolor{red}{Petra Musterfrau},
1750   professor=\textcolor{red}{Klaus Naseschwarz}
1751 ]
1752 </WWUM>
1753 <*UKoLa>
1754 \TitlePageStyle{UKoLa}
1755 \maketitle[%  

1756   titlefont=\sffamily,  

1757   mainlogo=\textcolor{red}{\%  

1758     \includegraphics[height=10mm,width=63mm]\%  

1759     \uni-koblenz-landau\%  

1760   \}},  

1761   chair=\textcolor{red}{Nummer des Instituts:  

1762     Name des Instituts},  

1763   secondlogo=\textcolor{red}{Optionales weiteres Logo},  

1764   title=\textcolor{red}{Titel der Studien-, Bachelor-, Master- oder Diplomarbei  

1765   subject=\textcolor{red}{Diplomarbeit},  

1766   academicgrade=\textcolor{red}{Diplom-Informatikers},  

1767   discipline=\textcolor{red}{Name des Studiengangs},  

1768   place=\textcolor{red}{Koblenz}},  

1769   author=\textcolor{red}{Vorname und Nachname des Absolventen / der  

1770     Absolventin},  

1771   advisor=\textcolor{red}{Title{}  

1772     Vorname{}  

1773     Name,  

1774     Institut, Fachbereich innerhalb der Universität /  

1775     Institution außerhalb der Universität},  

1776   referee=\textcolor{red}{Title{}  

1777     Vorname{}  

1778     Name,  

1779     Institut, Fachbereich innerhalb der Universität /  

1780     Institution außerhalb der Universität\%  

1781 \and[f]\textcolor{red}{Title{}  

1782     Vorname{}  

1783     Name,  

1784     Institut, Fachbereich innerhalb der Universität /  

1785     Institution außerhalb der Universität\%  

1786 },%  

1787   date=\textcolor{red}{Abgabemonat},  

1788 ]
1789
1790 </UKoLa>
1791 \end{document}

1792 <!*README>
1793 \documentclass{scrdoc}
1794 \usepackage[utf8]{inputenc}

```

```

1795 \usepackage[T1]{fontenc}
1796 \usepackage{lmodern}
1797 \usepackage[english]{babel}
1798 \usepackage{xltabular}
1799 \usepackage{ragged2e}
1800 \usepackage{booktabs}
1801 \usepackage{graphicx}
1802 \usepackage{hypdoc}
1803 \CodelineIndex
1804 \RecordChanges
1805 \EnableCrossrefs
1806 \GetFileInfo{uni-titlepage.drv}
1807 \begin{document}
1808 \title{More Titlepage Styles with Package \File{uni-titlepage}\footnote{This is
1809     version \fileversion{} of file \File{\filename}.}}
1810 \author{Markus Kohm\footnote{Markus Kohm \textless komascript\textgreater\textcircled{\tiny
1811     at}gmx.info\textgreater}}
1812 \date{\fileversion{}\footnote{\textbf{Note:} All version below 0.9 are ALPHA
1813     versions. Everything may change. Everything may break. Everything may
1814     happen.} \filedate}
1815 \maketitle
1816 \begin{abstract}
1817 <!/README>
1818 <*README>
1819 -----
1820
1821 This work may be distributed and/or modified under the conditions of
1822 the LaTeX Project Public License, version 1.3c of the license.
1823 The latest version of this license is in
1824 http://www.latex-project.org/lppl.txt
1825 and version 1.3c or later is part of all distributions of LaTeX
1826 version 2005/12/01 or later.
1827
1828 This work has the LPPL maintenance status "maintained".
1829
1830 The Current Maintainer and author of this work is Markus Kohm.
1831
1832 -----
1833
1834 # ABSTRACT
1835
1836 </README>
1837 Creation of title pages is something most authors should not have to do.
1838 But reality is not perfect, so a lot of authors have to do it. In 2009
1839 <!README>KOMA started the title page project at \url{https://komascript.de/tit
1840 <README>KOMA started the title page project at <https://komascript.de/titlepag
1841 to collect real title pages and implement them with a well defined interface.
1842 <!README>In 2021 the project has been moved to \url{https://github.com/komasc
1843 <README>In 2021 the project has been moved to <https://github.com/komascript/v

```

```

1844 and renamed.
1845
1846 Now, changing from one title page style to another would be very
1847 simple. Nevertheless implementation of a new title page style may be still
1848 difficult. But maybe the guys of the title page project would help you. Just
1849 ask!
1850 {*README}
1851
1852 # Unpacking and Installation for Developers and Distributors
1853
1854 To unpack and install all files, you can download the source from github
1855 and then run:
1856
1857     l3build install
1858
1859 Afterwards you can build the manual and the PDFs of the examples using:
1860
1861     l3build doc
1862
1863 As an alternative you can use the CTAN source distribution. This already
1864 contains the user manual and the PDFs of the example files. So you only have
1865 to run
1866
1867     tex uni-titlepage.dtx
1868
1869 to generate the package file ‘uni-titlepage.sty’, the title definition files
1870 ‘title-*.def’ and the example titlepages ‘titlepage-*.tex’.
1871
1872 Please note, the ‘title-*.def’ files are run-time files. Together with
1873 ‘uni-titlepage.sty’ they have to be placed in ‘tex/latex/uni-titlepage’ inside
1874 a TDS tree. All files ‘titlepage-*.tex’ and ‘titlepage-*.pdf’ as well as
1875 ‘uni-titlepage.pdf’ are part of the documentation and should be placed in
1876 ‘doc/latex/uni-titlepage/’ of the TDS tree.
1877
1878 # Unpacking and Installation for Users
1879
1880 Users can use the installation described at
1881 [Unpacking and Installation for Developers and Distributors]. However, if
1882 your TeX distributor already distributes a ready for installation package, you
1883 do not need and should not create files and copy them yourself. Just use the
1884 package manager of your TeX distribution to install the package.
1885
1886 # How to Contribute
1887
1888 If you have made a title definition that is not specific for a single project
1889 but could be of interest for other users, you can either
1890
1891 * make your own ‘uni-titlepage-FOO’ package with its own manual and [upload it
1892 to ctan] (https://www.ctan.org/upload),

```

1893 * contribute in adding it to ‘uni-titlepage’.
 1894
 1895 The first option has the advantage, that you are free. There won’t be any code
 1896 reviews by the ‘uni-titlepage’ developers. You don’t need to use the same
 1897 coding style. There is not need to accept the license of ‘uni-titlepage’
 1898 etc. But in this case you have to take care to keep it compatible with future
 1899 releases of ‘uni-titlepage’ and it will not be presented in the
 1900 ‘uni-titlepage’ manual.
 1901
 1902 The second option has the advantage, that after accepting your code, the
 1903 ‘uni-titlepage’ developers will try to keep it working even if they change
 1904 ‘uni-titlepage’. But there are several restrictions to your code, before it
 1905 will be accepted. For example, you should always try to use general options,
 1906 if possible. *Static text* (not handled by options) should be configurable via
 1907 ‘\newcaptionname’, ‘\providecaptionname’ and ‘\renewcaptionname’ and should be
 1908 available at least in English and German (but if we can, we help in
 1909 translating them). The coding style and quality is also a criterion.
 1910
 1911 ⟨/README⟩
 1912 ⟨*!README⟩
 1913 \end{abstract}
 1914 \DocInput{uni-titlepage.dtx}
 1915 \end{document}
 1916 ⟨!/README⟩

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\\"	501, 502, 512, 514, 587, 597, 714, 781, 788, 793, 890, 891, 894, 901, 1566
\,	1170, 1570, 1607
\@	346
\@academicgrade	<u>285</u> , 682, 688, 694, 701, 708, 715, 725, 732, 739, 762, 771, 779
\@advisor	<u>287</u> , 1056, 1132, 1256, 1334
\@author	<u>250</u> , 1047, 1080, 1123, 1152, 1168, 1202, 1241, 1269, 1285, 1304, 1331, 1475, 1488, 1495
\@chair	<u>258</u> , 745, 750, 755, 1112, 1161, 1317
\@company	<u>254</u> , 1055
\@course	<u>253</u> , 1054
\@currext	227, 237
\@currname	227, 237
\@date	<u>251</u> , 1049, 1084, 1136, 1157, 1180, 1209, 1309, 1344
\@dedication	<u>295</u> , 1507, 1510, 1516
\@discipline	<u>284</u> , 683, 689, 695, 702, 709, 716, 763, 772, 780, 1124
\@duration	<u>252</u> , 1052, 1260
\@evenhead	994
\@extratitle	<u>1436</u> , 1450, 1452, 1483
\@faculty	<u>257</u> , 744, 749, 754, 764, 773, 781, 1110
\@firstofone	97, 360
\@fnsymbol	882
\@gobble 95, 1216, 1218, 1219, 1220,

\@university	256, 703,
	710, 717, 723, 730, 737, 765,
	774, 782, 887, 1057, 1108, 1264
\@uppertitleback	1353, 1354, 1380
\@uppertitlebacke	1352
\@usetitleelement@error	298
\□	1344
A	
\academicgrade	285
academicgrade (Option)	285
\advanve	171
\advisor	287
advisor (Option)	287
\advisornname	367,
	1056, 1129, 1255, 1256, 1334
\and	1202, 1248, 1339,
	1395, 1400, 1421, 1494, 1610,
	1632, 1681, 1683, 1748, 1781
\arraystretch	1415
\askforoverwritefalse	11
\AtBeginDocument	362
\atthename	387
\author	250, 1810
author (Option)	250
B	
\bachelorthesisname	270, 367
\baselineskip	214, 700,
	702, 707, 709, 714, 716, 1046,
	1090, 1127, 1134, 1175, 1178,
	1197, 1201, 1203, 1206, 1230,
	1278, 1304, 1310, 1322, 1325,
	1327, 1329, 1330, 1343, 1493
\batchfile	1
blackborder (Option)	649
C	
\c@footnote	882
\catcode	346
\chair	258
chair (Option)	258
\chairmannname	367, 1424, 1736, 1737
\colorlet	1528
\columnwidth	191
\company	254
company (Option)	254

\companyname	79, 94, 229, 230, 231, 233, 291, 557, 616, 992, 1180, 1202, 1208, 1209, 1331, 1338, 1419, 1420, 1495, 1510
\course	253
course (Option)	253
\coursename	390, 446, 508, 1053
\csname	79, 229, 230, 231, 233, 291, 616, 992, 1180, 1202, 1208, 1209, 1331, 1338, 1419, 1420, 1495, 1510
D	
\date	251, 1812
date (Option)	251
\dedication	295
dedication (Option)	295
\DefineFamily	81
\DefineFamilyKey	86, 91, 232, 238, 245, 248, 263, 297, 320, 325, 330, 335, 660, 669, 1355, 1366, 1439
\DefineFamilyMember	82, 634
\DefineReplaceTitleKey	220, 282
\DefineSimpleTitleKey	220, 249, 250, 251, 252, 253, 254, 255, 256, 257, 258, 259, 283, 284, 285, 286, 287, 288, 289, 290, 292, 293, 294
\degreethesisname	268, 367
\dimexpr	666, 675, 1035, 1051, 1102, 1103, 1185, 1186, 1188, 1190, 1194, 1216, 1218, 1219, 1220, 1222, 1223, 1225, 1226, 1227, 1230, 1232, 1233, 1263, 1271, 1272, 1289, 1290, 1316, 1320
\diplomathesisname	267, 367
\discipline	284
discipline (Option)	284
\do	228, 262
\DocInput	1914
\documentclass	1519, 1793
\dp	1285, 1296, 1299
\duration	252
duration (Option)	252
\durationname	388, 442, 504, 1052, 1260
E	
\edef	342
\endcsname	79, 94, 229, 230, 231, 233, 291, 557, 616, 992, 1180, 1202, 1208, 1209, 1331, 1338, 1419, 1420, 1495, 1510
\endminipage	196
\endpreamble	36
\englishordinal	394, 417, 518, 556
\englishordinalfemalerefereename	385, 437, 520
\englishordinalmalerefereename	384, 434, 517
\englishordinalmalerefereename	521
\engordnumber	558
\enskip	1308, 1398, 1404
\evensidemargin	211
\examinationdatename	393, 452, 514, 1428, 1429, 1734, 1735
\examinationname	392, 450, 512, 700, 707, 714
\exittitle	103, 150, 161
\extratitle	1436
extratitle (Option)	1436
F	
\faculty	257
faculty (Option)	257
\FamilyBoolKey	649, 650
\FamilyKeyStateProcessed	87, 92, 234, 245, 248, 279, 297, 322, 327, 332, 337, 667, 676, 1363, 1374, 1446
\FamilyOption	84
\FamilyOptions	83, 240
\FamilyProcessOptions	366
\fbox	1097
\fe@male	1337, 1338, 1418, 1419, 1420
\femaleordinal	367
\femalerefereename	367
\File	1808, 1809
\file	39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 69
\filedate	1814
\filename	1809
\fileversion	1809, 1812
\fill	937, 975, 1392, 1412, 1545, 1674
final (Option)	650
\fontsize	1107, 1109, 1111

\footnote	881, 1808, 1810, 1812
\footnoterule	880
\footnotesize	879
\from	39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 69
\fromname	367, 785, 1046, 1151, 1239
\fromplace	367, 1154, 1169
\fullsizetitle	164
\fullsizetitle (Umgebung)	25
G	
\generate	38
\GenericError	605
\geometry	183
\germanfemaleordinal	475, 575
\germanmaleordinal	477, 575
\germanordinal	473, 575
\germanordinalfemalecorrectorname	553, 845, 852, 859, 866, 873
\germanordinalfemalerefereename	497, 537
\germanordinalmalecorrectorname	540, 554, 843, 850, 857, 864, 871
\germanordinalmalerefereename	494, 523
\GetFileInfo	1806
\Gm@bindingoffset	171, 175, 208
H	
\headheight	199, 991
\headsep	199, 1186, 1188
\height	1316, 1320
\hfill	1264, 1318
\homepage	246, 950
homepage (Option)	246
\ht	1185, 1194, 1316, 1320
\Huge	999, 1286, 1305
\huge	1074, 1241
I	
\if@atdocument	359, 918, 965
\if@resonecol	94
\if@restonecol	99, 139
\if@twocolumn	118
\if@twoside	124, 147, 148, 149, 1502
\ifblackborder	1094, 1103
\ifcstype	94, 557
\IfFileExists	340, 915, 916, 953, 954, 955, 956, 957, 958, 959, 960, 963
\iffinal	722, 726, 729, 733, 736, 740, 1393, 1403
\Ifstr	264, 265, 266, 267, 268, 269, 270, 281, 1337, 1344, 1418
\ifstr	281
\ifToplevel	3, 72
\ignorespaces	745, 750, 755, 1108, 1110, 1112, 1113, 1115, 1116, 1120, 1123, 1124, 1125, 1129, 1132, 1136, 1146, 1147, 1151, 1152, 1154, 1155, 1175, 1176, 1178, 1180, 1201, 1204, 1206, 1209, 1463, 1495
\includegraphics	923, 927, 969, 1540, 1644, 1671, 1758
\indatename	367, 1344
\inittitle	103, 146, 154, 877
\inittitlestyle	114, 343
K	
\keepsilent	10
\KIT@logo	953, 954, 955, 956, 957, 958, 959, 960, 961, 963, 969
\KITlongname	785, 893, 1686
\KITurl	785, 950, 1687
\KOMAoptions	181
L	
\l@addto@macro	228, 262
\LARGE	1146, 1176, 1204, 1309, 1324, 1494
\Large	1038, 1040, 1042, 1078, 1084, 1086, 1147, 1149, 1151, 1154, 1157, 1239, 1243, 1245, 1304, 1326, 1331
\large	983, 1175, 1178, 1180, 1201, 1202, 1206, 1208, 1209, 1260, 1264, 1285, 1463, 1493, 1495
\line	1216, 1220, 1223, 1227, 1273, 1276, 1291, 1294
\linebreak	1494
\linespread	1030
\linethickness	1273, 1276, 1291, 1294
\linewidth	190, 1051, 1103, 1119, 1121, 1128, 1130, 1135, 1195
\lowertitleback	1352

lowertitleback (Option)	1352	\ofthename	367, 1056, 1057
\lsstyle	1005	\onecolumn	119
Optionen:			
\academicgrade	285	\advisor	287
\author	250	\blackborder	649
\chair	258	\company	254
\course	253	\date	251
\dedication	295	\discipline	284
\duration	252	\extratitle	1436
\faculty	257	\final	650
\homepage	246	\lowertitleback	1352
\mainlogo	292	\mainlogo	292
\matriculationnumber	286	\oralexaminationdate	294
\pagename	85	\pagestyle	89
\place	289	\professor	259
\publisher	290	\referee	288
\rulesep	651	\rulewidth	651
\secondlogo	293	\science	283
\student	282	\subjectfont	324
\subject	260	\subtitlefont	334
\titlefont	329	\subtitle	255
\titlehead	243	\titlefont	329
\titlepagefont	315	\title	249
\university	256	\uppertitleback	1352
\oralexaminationdate	294	\oralexaminationdate	294
\oralexaminationdate (Option)	294	\oralexaminationdatename	367, 1404, 1427
\ordinal	367, 1251, 1398	\ordinalfemalecorrectorname	838
M			
\mainlogo	292, 921, 968		
\mainlogo (Option)	292		
\makeatletter	344, 1533		
\makeatother	1533		
\makebox	215, 1263		
\makemaintitle	103, 148, 157, 1021		
\makemaintitleback	103, 148, 158, 1376		
\makeposttitle	103, 149, 159, 1505		
\makeposttitleback	103, 149, 160, 1505		
\makepretitle	103, 147, 155, 1448		
\makepretitleback	103, 147, 156, 1448, 1482, 1487, 1501		
\maketitle	2, 102, 143, 1535, 1563, 1582, 1586, 1602, 1621, 1638, 1669, 1692, 1706, 1720, 1738, 1755, 1815		
\MakeUppercase	1005, 1304, 1305, 1306, 1308, 1309, 1311, 1528		
\maleordinal	367		
\malerefereename	367		
\masterthesisname	269, 367		
\matriculationnumber	286		
\matriculationnumber (Option)	286		
\matriculationnumbername	389, 444, 506, 1053		
\mbox	1099		
\minipage	194		
\Msg	4, 5, 6, 7, 8, 9, 73, 74, 75, 76, 77		
N			
\newcaptionname	1907		
\newif	99		
\newkomafont	318		
\newsavebox	164		
\nobreakspace	890, 891, 1136, 1566		
\noexpand	343, 344, 345, 346		
\nopostamble	68		
\nopreamble	68		
\NowButAfterBeginDocument	25, 358, 831		
\numexpr	1250		
O			
\oddsidemargin	205		

\ordinalfemalerefereename	367 , 830	\publisher	290 , 1020
\ordinalmalerefereename	367 , 830	publisher (Option)	290
\oval	1218 , 1225	\publishers	1020
		\put	1215 , 1218 , 1219 , 1222 , 1225 , 1226 , 1272 , 1275 , 1290 , 1293
		P	
\PackageNotFoundError	604 , 617	\quad	1121 , 1130
\PackageWarning	176 , 221 , 906		
\pagenumber	(Option)	R	
		\raisebox	1185 , 1194 , 1316 , 1320
\pagestyle	(Option)	\RecordChanges	1804
		\referee	288
\paperheight		\referee (Option)	288
	189 , 1220 , 1222 , 1225 , 1226 , 1227 , 1232	\refereename	
\paperwidth			367 , 785 , 1057 , 1246 , 1254 , 1398
	168 , 1216 , 1218 , 1219 , 1223 , 1233 , 1263	\renewcaptionname	797 , 798 , 801 , 802 , 805 , 806 , 809 , 810 , 813 , 814 , 817 , 818 , 821 , 822 , 825 , 826 , 836 , 837 , 841 , 842 , 844 , 848 , 849 , 851 , 855 , 856 , 858 , 862 , 863 , 865 , 869 , 870 , 872 , 1734 , 1735 , 1736 , 1737 , 1907
\parfillskip		\renewenvironment	115
\parindent		\rlap	884
\parskip		\rule	1093 , 1186
\place		rulesep (Option)	651
\place	(Option)	rulewidth (Option)	651
\preamble			
\presentationinformationDHBW		S	
	679 , 1044	\scr@ifundefinedorrelax	
\presentationinformationKIT			100 , 101 , 169 , 170 , 174 , 206 , 207 , 299 , 302 , 315 , 796 , 800 , 804 , 808 , 812 , 816 , 820 , 824 , 835 , 840 , 847 , 854 , 861 , 868 , 917 , 920 , 964 , 967 , 1001
\presentationinformationTUHH		\secondlogo	293
	679 , 1149	secondlogo (Option)	293
\presentationinformationUKoLA	679	\selectfont	1030 , 1107 , 1109 , 1111
\presentationinformationUKoLa		\seminarpapername	265 , 367
	680 , 686 , 692 , 1328	\setkomafont	1534 , 1617 , 1618
\presentationinformationWWUM		\science	283
	679 , 1165	science (Option)	283
\presentedbyname		\small	879
	367 , 830 , 1120 , 1167 , 1330	\stepcounter	140
\professor		\strut	745 , 750 , 755 , 1108 , 1110 , 1112 , 1113 , 1115 , 1116 , 1120 , 1123 , 1124 , 1125 , 1129 , 1132 , 1136 , 1146 , 1147 , 1151 , 1152 , 1154 ,
\professor	(Option)		
\projectpapername			
\providecaptionname			
	398 , 400 , 402 , 404 , 407 , 409 , 411 , 413 , 416 , 418 , 420 , 422 , 424 , 426 , 428 , 430 , 432 , 435 , 438 , 441 , 443 , 445 , 447 , 449 , 451 , 454 , 456 , 458 , 460 , 462 , 464 , 466 , 468 , 470 , 472 , 474 , 476 , 478 , 480 , 482 , 484 , 486 , 488 , 490 , 492 , 495 , 498 , 500 , 503 , 505 , 507 , 509 , 511 , 513 , 515 , 685 , 691 , 705 , 712 , 727 , 734 , 747 , 752 , 767 , 776 , 786 , 791 , 833 , 1907		
\ps@empty			
\ps@maintitle			

\textcolor{red}{1155}, \textcolor{red}{1175}, \textcolor{red}{1176}, \textcolor{red}{1178}, \textcolor{red}{1180},	\texttheight	193,
1201, 1204, 1206, 1209, 1285,	1102, 1185, 1186, 1188, 1189	
1299, 1305, 1310, 1463, 1494		
\strutbox	\textless	1810
1185, 1194,	\texttt	1564, 1587,
1285, 1296, 1299, 1316, 1320	1590, 1594, 1596, 1597, 1604,	
student (Option)	1623, 1628, 1630, 1631, 1640,	
\studentresearchname	1646, 1653, 1657, 1660, 1675	
266, 370, 405, 463	\textwidth	
\studentreserchname	192, 654, 1063, 1190, 1379, 1383	
\subject	\thanks	881
260	\thefootnote	882
subject (Option)	\thename	367, 1136
\subject@font	\tiny	1264, 1810
324, 1042, 1071, 1174, 1200, 1326	\title	249, 1808
\subjectfont (Option)	title (Option)	249
\subtitle	\title@font	329
255	\title@rulesep	651, 1188,
subtitle (Option)	1190, 1271, 1272, 1289, 1290	
\subtitlefont (Option)	\title@rulewidth	
334	651, 1187, 1190, 1270,	
	1273, 1276, 1288, 1291, 1294	
	\titlebox	164
	\titlefont	329, 331,
	1010, 1011, 1040, 1074, 1176,	
	1204, 1279, 1286, 1305, 1324	
	titlefont (Option)	329
	\titlehead	243, 937, 975
	titlehead (Option)	243
	\TitleOption	2, 80
	\TitleOptions	
	. 2, 80, 116, 145, 166, 349, 1581	
	\titlepage	100
	titlepage (Umgebung)	25
	titlepage (Umgebung)	100
	titlepagefont (Option)	315
	\TitlePageStyle	2,
	339, 365, 1532, 1562, 1585,	
	1601, 1620, 1636, 1637, 1668,	
	1691, 1705, 1719, 1733, 1754	
	\titlepagestyle	89, 123, 137
	\topmargin	199
	\topskip	200
	\totalheight	1194
	\tp@dokeys	220, 262
	\tp@replacewarning	220
	\tp@undefinedtitle	
	103, 155, 156, 157, 158, 159, 160	
\textgreater		
1811		

U	V
Umgebungen:	
<code>fullsizetitle</code>	<code>\usepackage</code> 1520, 1521, 1522,
<code>titlepage</code>	1523, 1524, 1525, 1526, 1527,
<code>\unitlength</code>	1529, 1794, 1795, 1796, 1797,
<code>\university</code>	1798, 1799, 1800, 1801, 1802
<code>university</code> (Option)	<code>\usetitleelement</code> 25, 298, 1545, 1674
<code>\unskip</code>	
1108, 1110, 1112, 1113, 1115, 1116, 1120, 1123, 1124, 1125, 1129, 1132, 1285, 1299, 1305, 1310	
<code>\uppertitleback</code>	<code>\value</code> 125, 126, 131, 136
<code>uppertitleback</code> (Option)	<code>\vbox</code> 213
<code>\url</code>	<code>\vsizer</code> 189, 193, 1035, 1472
<code>\usebox</code>	<code>\vskip</code> 199, 200, 214, 1072, 1075, 1077, 1083, 1085, 1087, 1090, 1106, 1127, 1134, 1175, 1178, 1197, 1201, 1203, 1206, 1230, 1236, 1238, 1240, 1242, 1244, 1262, 1402, 1493, 1511
<code>\usefont</code>	<code>\vss</code> 216

Change History

0.5e	<code>\@usetitleelement@error:</code>
	new (internal) 34
	General: new style
	<code>JT-Aufsaetze</code> 41
	new style <code>JT-Geschichte</code> 41
	new style <code>JT-Typography</code> 41
	<code>\mainlogo</code> : new 34
	<code>mainlogo</code> : new 34
	<code>\usetitleelement</code> : new 34
v0.1	
	General: Start of project 26
v0.2	
	General: First version using
	<code>docstrip</code> 26
	new style DHBW 41
	new style Spacer 41
v0.2a	
	<code>\makemaintitle</code> : Markus-2:
	<code>\leavevmode</code> added before
	<code>\subject@font</code> to avoid line
	break after <code>\subject@font</code>
	using package <code>color</code> or <code>xcolor</code> 50
	<code>\makepretitle</code> : Markus-1:
	Usage of <code>\@titlepagefont</code>
	fixed 59
v0.3	
	<code>\@homepage</code> : new internal 32
	General: new style KIT 41
	<code>\homepage</code> : new command 32
	<code>homepage</code> : new option 32
v0.4	
	<code>\@mainlogo</code> : new (internal) 34
	<code>\@science</code> : new 33
	<code>\chairmanname</code> : new 36
	<code>\femaleordinal</code> : new 36
	<code>\femalerefereename</code> : new 36
	<code>\fromname</code> :
	<code>\NowButAfterBeginDocument</code>
	<code>\@science</code> : new 33
	<code>\chairmanname</code> : new 36
	<code>\femaleordinal</code> : new 36
	<code>\femalerefereename</code> : new 36

not needed any more	45	\chairmannname: not needed \AtBeginDocument removed	36
provide sevaral English and German languages	45	\degreethesisname: not needed \AtBeginDocument removed	36
\KITlongname: \NowButAfterBeginDocument not needed any more	45	\diplomathesisname: not needed \AtBeginDocument removed	36
provide sevaral English and German languages	45	\femaleordinal: not needed \AtBeginDocument removed	36
\maleordinal: new	36	\femalerefereename: not needed \AtBeginDocument removed	36
\malerefereename: new	36	\fromname: not needed \AtBeginDocument removed	36
\presentationinformationDHBW: \NowButAfterBeginDocument not needed any more	43	\fromplacename: not needed \AtBeginDocument removed	36
provide sevaral English and German languages	43	\malerefereename: not needed \AtBeginDocument removed	36
\presentationinformationKIT: \NowButAfterBeginDocument not needed any more	43	\masterthesisname: not needed \AtBeginDocument removed	36
provide sevaral English and German languages	43	\ofthename: not needed \AtBeginDocument removed	36
\presentationinformationTUHH: \NowButAfterBeginDocument not needed any more	43	\oralexaminationdatename: not needed \AtBeginDocument removed	36
provide sevaral English and German languages	43	\ordinal: not needed \AtBeginDocument removed	36
\presentationinformationWWUM: new style WWUM	43	\presentedbyname: not needed \AtBeginDocument removed	36
\presentedbyname: changed value for WWUM	46	\projectpapername: not needed \AtBeginDocument removed	36
\refereename: \NowButAfterBeginDocument not needed any more	45	\refereename: not needed \AtBeginDocument removed	36
provide sevaral English and German languages	45	\seminarpapername: not needed \AtBeginDocument removed	36
\science: new	33	\studentreserchname: not needed \AtBeginDocument removed	36
sience: new	33	\thename: not needed \AtBeginDocument removed	36
v0.5a		v0.5e	
\presentedbyname: fixed swissgerman instead of swiss	46	\makemaintitleback: \ifstr in scrbase renamed to \Ifstr	58
v0.5b		subject: \ifstr in scrbase renamed to \Ifstr	33
\presentedbyname: changes have to be delayed	46	v0.5f	
v0.5c		General: autodetect several logo picture files	49
\advisorname: not needed \AtBeginDocument removed	36		
\bachelorthesisname: not needed \AtBeginDocument removed	36		

usage of 13build	1	\germanordinalfemalerefereename:	
v0.6		new 40	
\@academicgrade: renamed “degree” to “academic grade” to avoid name clash with the degree symbol ...	33	\germanordinalmalecorrectorname:	
General: package renamed from titlepage into uni-titlepage	1	new 40	
\academicgrade: renamed “degree” to “academic grade” to avoid name clash with the degree symbol ...	33	\germanordinalmalerefereename:	
academicgrade: renamed “degree” to “academic grade” to avoid name clash with the degree symbol ...	33	new 39	
v0.7		\indatename: new 36	
\@secondlogo: new (internal) .	34	\ordinalfemalerefereename:	
General: don't use inputenc any longer	61	changed value for UKoLa .. 46	
new style UKoLa	24	new 36	
\englishordinalfemalerefereename:		\ordinalmalerefereename:	
new 39		changed value for UKoLa .. 46	
\englishordinalmalerefereename:		new 36	
new 39		\presentationinformationUKoLA:	
\germanordinalfemalecorrectorname:		new 43	
new	40	\presentedbypname: changed	
value also for UKoLa .. .	46	\secondlogo: new 34	
\secondlogo: new	34	\secondlogo: new 34	
v0.7a		v0.7b	
\ordinalfemalerefereename:		\germanordinalmalecorrectorname:	
typofix for austrian	46	missing \fi added 40	
\ordinalmalerefereename:		\germanordinalmalerefereename:	
typofix for austrian .. .	46	missing \fi added 39	