

# The luamplib package

Hans Hagen, Taco Hoekwater, Elie Roux, Philipp Gesang and Kim Dohyun  
Maintainer: LuaLaTeX Maintainers – Support: <[lualatex-dev@tug.org](mailto:lualatex-dev@tug.org)>

2022/01/12 v2.23.0

## Abstract

Package to have metapost code typeset directly in a document with  $\text{\LaTeX}$ .

## 1 Documentation

This packages aims at providing a simple way to typeset directly metapost code in a document with  $\text{\LaTeX}$ .  $\text{\LaTeX}$  is built with the `luamplib` library, that runs metapost code. This package is basically a wrapper (in Lua) for the `Luamplib` functions and some  $\text{\TeX}$  functions to have the output of the `mp` functions in the pdf.

In the past, the package required PDF mode in order to output something. Starting with version 2.7 it works in DVI mode as well, though DVIPDFMx is the only DVI tool currently supported.

The metapost figures are put in a  $\text{\TeX}$  `hbox` with dimensions adjusted to the metapost code.

Using this package is easy: in Plain, type your metapost code between the macros `\mp` and `\endmp`, and in  $\text{\LaTeX}$  in the `mp` environment.

The code is from the `luatest-mp`.lua and `luatest-mp`.tex files from Con $\text{\TeX}$ t, they have been adapted to  $\text{\LaTeX}$  and Plain by Elie Roux and Philipp Gesang, new functionalities have been added by Kim Dohyun. The changes are:

- a  $\text{\TeX}$  environment
- all  $\text{\TeX}$  macros start by `mp`
- use of `luatestbase` for errors, warnings and declaration
- possibility to use `btx ... etex` to typeset  $\text{\TeX}$  code. `texttext()` is a more versatile macro equivalent to `TEX()` from `TEX.mp`. `TEX()` is also allowed and is a synonym of `texttext()`.

N.B. Since v2.5, `btx ... etex` input from external `mp` files will also be processed by `luamplib`.

N.B. Since v2.20, `verbatimtex ... etex` from external `mp` files will be also processed by `luamplib`. Warning: This is a change from previous version.

Some more changes and cautions are:

**\mplibforcehmode** When this macro is declared, every `mplibcode` figure box will be typeset in horizontal mode, so `\centering`, `\raggedleft` etc will have effects. `\mplibnoforcehmode`, being default, reverts this setting. (Actually these commands redefine `\prependtomplibbox`. You can define this command with anything suitable before a box.)

**\mpliblegacybehavior{enable}** By default, `\mpliblegacybehavior{enable}` is already declared, in which case a `\verb+verbatimtex ... etex+` that comes just before `beginfig()` is not ignored, but the `\TeX` code will be inserted before the following `mplib` hbox. Using this command, each `mplib` box can be freely moved horizontally and/or vertically. Also, a box number might be assigned to `mplib` box, allowing it to be reused later (see test files).

```
\mplibcode
verbatimtex \moveright 3cm etex; beginfig(0); ... endfig;
verbatimtex \leavevmode etex; beginfig(1); ... endfig;
verbatimtex \leavevmode\lower 1ex etex; beginfig(2); ... endfig;
verbatimtex \endgraf\moveright 1cm etex; beginfig(3); ... endfig;
\endmplibcode
```

N.B. `\endgraf` should be used instead of `\par` inside `verbatimtex ... etex`.

By contrast, `\TeX` code in `\VerbatimTeX{...}` or `\verb+verbatimtex ... etex+` between `beginfig()` and `endfig` will be inserted after flushing out the `mplib` figure.

```
\mplibcode
D := sqrt(2)**7;
beginfig(0);
draw fullcircle scaled D;
VerbatimTeX("\gdef\Dia{" & decimal D & "}");
endfig;
\endmplibcode
diameter: \Dia bp.
```

**\mpliblegacybehavior{disabled}** If `\mpliblegacybehavior{disabled}` is declared by user, any `\verb+verbatimtex ... etex+` will be executed, along with `\verb+btexte ... etex+`, sequentially one by one. So, some `\TeX` code in `verbatimtex ... etex` will have effects on `btexte ... etex` codes that follows.

```
\begin{mplibcode}
beginfig(0);
draw btext ABC etex;
verbatimtex \bfseries etex;
draw btext DEF etex shifted (1cm,0); % bold face
draw btext GHI etex shifted (2cm,0); % bold face
endfig;
\end{mplibcode}
```

**About figure box metrics** Notice that, after each figure is processed, macro `\MPwidth` stores the width value of latest figure; `\MPheight`, the height value. Incidentally, also note that `\MPllx`, `\MPlly`, `\MPurx`, and `\MPury` store the bounding box information of latest figure without the unit bp.

**`\everymplib`, `\everyendmplib`** Since v2.3, new macros `\everymplib` and `\everyendmplib` redefine the lua table containing MetaPost code which will be automatically inserted at the beginning and ending of each `mplibcode`.

```
\everymplib{ beginfig(0); }
\everyendmplib{ endfig; }
\mplibcode % beginfig/endfig not needed
  draw fullcircle scaled 1cm;
\endmplibcode
```

**`\mpdim`** Since v2.3, `\mpdim` and other raw TeX commands are allowed inside `mplib` code. This feature is inspired by `gmp.sty` authored by Enrico Gregorio. Please refer the manual of `gmp` package for details.

```
\begin{mplibcode}
draw origin--(\mpdim{\linewidth},0) withpen pencircle scaled 4
dashed evenly scaled 4 withcolor \mpcolor{orange};
\end{mplibcode}
```

**N.B.** Users should not use the protected variant of `btx ... etex` as provided by `gmp` package. As `luamplib` automatically protects TeX code inbetween, `\btx` is not supported here.

**`\mpcolor`** With `\mpcolor` command, color names or expressions of `color/xcolor` packages can be used inside `mplibcode` environment (after `withcolor` operator), though `luamplib` does not automatically load these packages. See the example code above. For spot colors, `(x)spotcolor` (in PDF mode) and `xespotcolor` (in DVI mode) packages are supported as well.

**`\mplibnumbersystem`** Users can choose `numbersystem` option since v2.4. The default value `scaled` can be changed to `double` or `decimal` by declaring `\mplibnumbersystem{double}` or `\mplibnumbersystem{decimal}`. For details see <http://github.com/lualatex/luamplib/issues/21>.

**Settings regarding cache files** To support `btx ... etex` in external `.mp` files, `luamplib` inspects the content of each and every `.mp` input files and makes caches if necessary, before returning their paths to LuaTeX's `mplib` library. This would make the compilation time longer wastefully, as most `.mp` files do not contain `btx ... etex` command. So `luamplib` provides macros as follows, so that users can give instruction about files that do not require this functionality.

- `\mplibmakencache{<filename>[,<filename>,...]}`

- `\mplibcancelnocache{<filename>[,<filename>,...]}`

where `<filename>` is a file name excluding `.mp` extension. Note that `.mp` files under `$TEXMFMAIN/metapost/base` and `$TEXMFMAIN/metapost/context/base` are already registered by default.

By default, cache files will be stored in `$TEXMFVAR/luamplib_cache` or, if it's not available, in the same directory as where pdf/dvi output file is saved. This however can be changed by the command `\mplibcachedir{<directory path>}`, where tilde (`~`) is interpreted as the user's home directory (on a windows machine as well). As backslashes (`\`) should be escaped by users, it would be easier to use slashes (`/`) instead.

**`\mplibtexttextlabel`** Starting with v2.6, `\mplibtexttextlabel{enable}` enables string labels typeset via `texttext()` instead of `infont` operator. So, `label("my text",origin)` thereafter is exactly the same as `label(texttext("my text"),origin)`. N.B. In the background, luamplib redefines `infont` operator so that the right side argument (the font part) is totally ignored. Every string label therefore will be typeset with current  $\text{\TeX}$  font. Also take care of `char` operator in the left side argument, as this might bring unpermitted characters into  $\text{\TeX}$ .

**`\mplibcodeinherit`** Starting with v2.9, `\mplibcodeinherit{enable}` enables the inheritance of variables, constants, and macros defined by previous `mplibcode` chunks. On the contrary, the default value `\mplibcodeinherit{disable}` will make each code chunks being treated as an independent instance, and never affected by previous code chunks.

**Separate instances for  $\text{\TeX}$  environment** v2.22 has added the support for several named MetaPost instances in  $\text{\TeX}$  `mplibcode` environment. Syntax is like so:

```
\begin{mplibcode}[instanceName]
  % some mp code
\end{mplibcode}
```

Behaviour is as follows.

- All the variables and functions are shared only among all the environments belonging to the same instance.
- `\mplibcodeinherit` only affects environments with no instance name set (since if a name is set, the code is intended to be reused at some point).
- `btx ... etex` labels still exist separately and require `\mplibglobaltexttext`.
- When an instance names is set, respective `\currentmpinstancename` is set.

In parallel with this functionality, v2.23 and after supports optional argument of instance name for `\everymplib` and `\everyendmplib`, affecting only those `mplibcode` environments of the same name. Unnamed `\everymplib` affects not only those instances with no name, but also those with name but with no corresponding `\everymplib`. Syntax is:

```
\everymplib[instanceName]{...}
\everyendmplib[instanceName]{...}
```

**\mplibglobaltexttext** To inherit btex ... etex labels as well as metapost variables, it is necessary to declare \mplibglobaltexttext{enable} in advance. On this case, be careful that normal TeX boxes can conflict with btex ... etex boxes, though this would occur very rarely. Notwithstanding the danger, it is a ‘must’ option to activate \mplibglobaltexttext if you want to use graph.mp with \mplibcodeinherit functionality.

```
\mplibcodeinherit{enable}
\mplibglobaltexttext{enable}
\everymplib{ beginfig(0); } \everyendmplib{ endfig; }
\mplibcode
  label(btex $ \sqrt{2} $ etex, origin);
  draw fullcircle scaled 20;
  picture pic; pic := currentpicture;
\endmplibcode
\mplibcode
  currentpicture := pic scaled 2;
\endmplibcode
```

**\mplibverbatim** Starting with v2.11, users can issue \mplibverbatim{enable}, after which the contents of mplibcode environment will be read verbatim. As a result, except for \mpdim and \mpcolor, all other TeX commands outside btex ... etex or verbatimtex ... etex are not expanded and will be fed literally into the mplib process.

**\mplibshowlog** When \mplibshowlog{enable} is declared, log messages returned by \mplib instance will be printed into the .log file. \mplibshowlog{disable} will revert this functionality. This is a TeX side interface for luamplib.showlog. (v2.20.8)

**luamplib.cfg** At the end of package loading, luamplib searches luamplib.cfg and, if found, reads the file in automatically. Frequently used settings such as \everymplib or \mplibforcehmode are suitable for going into this file.

There are (basically) two formats for metapost: *plain* and *metafun*. By default, the *plain* format is used, but you can set the format to be used by future figures at any time using \mplibsetformat{*format name*}.

## 2 Implementation

### 2.1 Lua module

```
1
2 luatexbase.provides_module {
3   name      = "luamplib",
4   version   = "2.23.0",
5   date      = "2022/01/12",
6   description = "Lua package to typeset Metapost with LuaTeX's MPLib.",
7 }
```

```

8
9 local format, abs = string.format, math.abs
10
11 local err = function(...)
12   return luatexbase.module_error ("luamplib", select("#", ...) > 1 and format(...) or ...)
13 end
14 local warn = function(...)
15   return luatexbase.module_warning("luamplib", select("#", ...) > 1 and format(...) or ...)
16 end
17 local info = function(...)
18   return luatexbase.module_info ("luamplib", select("#", ...) > 1 and format(...) or ...)
19 end
20

```

Use the luamplib namespace, since `mplib` is for the metapost library itself. ConTeXt uses metapost.

```

21 luamplib      = luamplib or { }
22 local luamplib = luamplib
23
24 luamplib.showlog = luamplib.showlog or false
25

```

This module is a stripped down version of libraries that are used by ConTeXt. Provide a few “shortcuts” expected by the imported code.

```

26 local tableconcat = table.concat
27 local tex sprint = tex.sprint
28 local texprint    = tex.tprint
29
30 local texget     = tex.get
31 local texgettoks = tex.gettoks
32 local texgetbox  = tex.getbox
33 local texruntoks = tex.runtoks

```

We don't use `tex.scantoks` anymore. See below regarding `tex.runtoks`.

```
local texscantoks = tex.scantoks
```

```

34
35 if not texruntoks then
36   err("Your LuaTeX version is too old. Please upgrade it to the latest")
37 end
38
39 local mplib = require ('mplib')
40 local kpse  = require ('kpse')
41 local lfs   = require ('lfs')
42
43 local lfsattributes = lfs.attributes
44 local lfsisdir     = lfs.isdir
45 local lfsmkdir    = lfs.mkdir
46 local lfstouch    = lfs.touch
47 local ioopen       = io.open
48

```

Some helper functions, prepared for the case when l-file etc is not loaded.

```
49 local file = file or { }
50 local replacesuffix = file.replacesuffix or function(filename, suffix)
51   return (filename:gsub("%.[%a%d]+$","")) .. "." .. suffix
52 end
53 local stripsuffix = file.stripsuffix or function(filename)
54   return (filename:gsub("%.[%a%d]+$",""))
55 end
56
57 local is_writable = file.is_writable or function(name)
58   if lfs.isdir(name) then
59     name = name .. "/_luamplib_temp_file_"
60     local fh = io.open(name,"w")
61     if fh then
62       fh:close(); os.remove(name)
63     return true
64   end
65 end
66 end
67 local mk_full_path = lfs.mkdirs or function(path)
68   local full = ""
69   for sub in path:gmatch("/*[^\\/]+") do
70     full = full .. sub
71     lfsmkdir(full)
72   end
73 end
74
```

btex ... etex in input .mp files will be replaced in finder. Because of the limitation of MPLib regarding make\_text, we might have to make cache files modified from input files.

```
75 local luamplibtime = kpse.find_file("luamplib.lua")
76 luamplibtime = luamplibtime and lfs.attributes(luamplibtime,"modification")
77
78 local currenttime = os.time()
79
80 local outputdir
81 if lfstouch then
82   local texmfvar = kpse.expand_var('$TEXMFVAR')
83   if texmfvar and texmfvar ~= "" and texmfvar ~= '$TEXMFVAR' then
84     for _,dir in next, texmfvar:explode(os.type == "windows" and ";" or ":") do
85       if not lfs.isdir(dir) then
86         mk_full_path(dir)
87       end
88       if is_writable(dir) then
89         local cached = format("%s/luamplib_cache",dir)
90         lfsmkdir(cached)
91         outputdir = cached
92         break
93       end
94     end
95   end
96 end
```

```

94     end
95 end
96 end
97 if not outputdir then
98   outputdir = "."
99   for _,v in ipairs(arg) do
100     local t = v:match("%-output%-directory=(.+)")
101     if t then
102       outputdir = t
103       break
104     end
105   end
106 end
107
108 function luamplib.getcachedir(dir)
109   dir = dir:gsub("##", "#")
110   dir = dir:gsub("^~",
111     os.type == "windows" and os.getenv("UserProfile") or os.getenv("HOME"))
112   if lfstouch and dir then
113     if lfs.isdir(dir) then
114       if is_writable(dir) then
115         luamplib.cachedir = dir
116       else
117         warn("Directory '%s' is not writable!", dir)
118       end
119     else
120       warn("Directory '%s' does not exist!", dir)
121     end
122   end
123 end
124

```

Some basic MetaPost files not necessary to make cache files.

```

125 local noneedtoreplace = {
126   ["boxes.mp"] = true, -- ["format.mp"] = true,
127   ["graph.mp"] = true, ["marith.mp"] = true, ["mfplain.mp"] = true,
128   ["mpost.mp"] = true, ["plain.mp"] = true, ["rboxes.mp"] = true,
129   ["sarith.mp"] = true, ["string.mp"] = true, -- ["TEX.mp"] = true,
130   ["metafun.mp"] = true, ["metafun.mpiiv"] = true, ["mp-abck.mpiiv"] = true,
131   ["mp-apos.mpiiv"] = true, ["mp-asnc.mpiiv"] = true, ["mp-bare.mpiiv"] = true,
132   ["mp-base.mpiiv"] = true, ["mp-blob.mpiiv"] = true, ["mp-butt.mpiiv"] = true,
133   ["mp-char.mpiiv"] = true, ["mp-chem.mpiiv"] = true, ["mp-core.mpiiv"] = true,
134   ["mp-crop.mpiiv"] = true, ["mp-figs.mpiiv"] = true, ["mp-form.mpiiv"] = true,
135   ["mp-func.mpiiv"] = true, ["mp-grap.mpiiv"] = true, ["mp-grid.mpiiv"] = true,
136   ["mp-grph.mpiiv"] = true, ["mp-idea.mpiiv"] = true, ["mp-luas.mpiiv"] = true,
137   ["mp-mlib.mpiiv"] = true, ["mp-node.mpiiv"] = true, ["mp-page.mpiiv"] = true,
138   ["mp-shap.mpiiv"] = true, ["mp-step.mpiiv"] = true, ["mp-text.mpiiv"] = true,
139   ["mp-tool.mpiiv"] = true,
140 }
141 luamplib.noneedtoreplace = noneedtoreplace

```

```

142
format.mp is much complicated, so specially treated.
143 local function replaceformatmp(file,newfile,ofmodify)
144   local fh = ioopen(file,"r")
145   if not fh then return file end
146   local data = fh:read("*all"); fh:close()
147   fh = ioopen(newfile,"w")
148   if not fh then return file end
149   fh:write(
150     "let normalinfont = infont;\n",
151     "primarydef str infont name = rawtexttext(str) enddef;\n",
152     data,
153     "vardef Fmant_(expr x) = rawtexttext(decimal abs x) enddef;\n",
154     "vardef Fexp_(expr x) = rawtexttext(\"$^{\"&decimal x&}$\") enddef;\n",
155     "let infont = normalinfont;\n"
156   ); fh:close()
157   lfstouch(newfile,currentTime,ofmodify)
158   return newfile
159 end
160

Replace btex ... etex and verbatimtex ... etex in input files, if needed.
161 local name_b = "%f[%a_]"
162 local name_e = "%f[^%a_]"
163 local btex_etex = name_b.."btex"..name_e.."%"..name_b.."etex"..name_e
164 local verbatimtex_etex = name_b.."verbatimtex"..name_e.."%"..name_b.."etex"..name_e
165
166 local function replaceinputmpfile (name,file)
167   local ofmodify = lfsattributes(file,"modification")
168   if not ofmodify then return file end
169   local cachedir = luamplib.cachedir or outputdir
170   local newfile = name:gsub("%w","_")
171   newfile = cachedir .."/luamplib_input_"..newfile
172   if newfile and luamplibtime then
173     local nf = lfsattributes(newfile)
174     if nf and nf.mode == "file" and
175       ofmodify == nf.modification and luamplibtime < nf.access then
176       return nf.size == 0 and file or newfile
177     end
178   end
179
180   if name == "format.mp" then return replaceformatmp(file,newfile,ofmodify) end
181
182   local fh = ioopen(file,"r")
183   if not fh then return file end
184   local data = fh:read("*all"); fh:close()
185
```

"etex" must be followed by a space or semicolon as specified in *LuaTeX* manual, which is not the case of standalone MetaPost though.

```

186 local count,cnt = 0,0
187 data, cnt = data:gsub(btex_etex, "btex %1 etex ") -- space
188 count = count + cnt
189 data, cnt = data:gsub(verbatimtex_etex, "verbatimtex %1 etex;") -- semicolon
190 count = count + cnt
191
192 if count == 0 then
193   noneedtoreplace[name] = true
194   fh = ioopen(newfile,"w");
195   if fh then
196     fh:close()
197     lfstouch(newfile,currenttime,ofmodify)
198   end
199   return file
200 end
201
202 fh = ioopen(newfile,"w")
203 if not fh then return file end
204 fh:write(data); fh:close()
205 lfstouch(newfile,currenttime,ofmodify)
206 return newfile
207 end
208

```

As the finder function for MPLib, use the kpse library and make it behave like as if MetaPost was used. And replace it with cache files if needed. See also #74, #97.

```

209 local mpkpse
210 do
211   local exe = 0
212   while arg[exe+1] do
213     exe = exe+1
214   end
215   mpkpse = kpse.new(arg[exe], "mpost")
216 end
217
218 local special_ftype = {
219   pfb = "type1 fonts",
220   enc = "enc files",
221 }
222
223 local function finder(name, mode, ftype)
224   if mode == "w" then
225     return name
226   else
227     ftype = special_ftype[ftype] or ftype
228     local file = mpkpse:find_file(name,ftype)
229     if file then
230       if not lfstouch or ftype ~= "mp" or noneedtoreplace[name] then
231         return file
232       end

```

```

233     return replaceinputmpfile(name,file)
234   end
235   return mpkpse:find_file(name, name:match("%a+$"))
236 end
237 end
238 luamplib.finder = finder
239

Create and load MPLib instances. We do not support ancient version of MPLib any
more. (Don't know which version of MPLib started to support make_text and run_script;
let the users find it.)

240 if tonumber(mpplib.version()) <= 1.50 then
241   err("luamplib no longer supports mpplib v1.50 or lower. "..
242     "Please upgrade to the latest version of LuaTeX")
243 end
244
245 local preamble = [[
246   boolean mpplib ; mpplib := true ;
247   let dump = endinput ;
248   let normalfontsize = fontsize;
249   input %s ;
250 ]]
251
252 local logatload
253 local function reporterror (result, indeed)
254   if not result then
255     err("no result object returned")
256   else
257     local t, e, l = result.term, result.error, result.log
log has more information than term, so log first (2021/08/02)
258     local log = l or t or "no-term"
259     log = log:gsub("%(Please type a command or say 'end')%",""):gsub("\n+","\n")
260     if result.status > 0 then
261       warn(log)
262       if result.status > 1 then
263         err(e or "see above messages")
264       end
265     elseif indeed then
266       local log = logatload..log
v2.6.1: now luamplib does not disregard show command, even when luamplib.showlog
is false. Incidentally, it does not raise error but just prints a warning, even if output has
no figure.
267     if log:find"\n>>" then
268       warn(log)
269     elseif log:find"%g" then
270       if luamplib.showlog then
271         info(log)
272       elseif not result.fig then
273         info(log)

```

```

274         end
275     end
276     logatload = ""
277   else
278     logatload = log
279   end
280   return log
281 end
282 end
283
284 local function luamplibload (name)
285   local mpx = mp.new {
286     ini_version = true,
287     find_file   = luamplib.finder,

```

Make use of `make_text` and `run_script`, which will co-operate with LuaTeX's `tex.runtoks`. And we provide `numbersystem` option since v2.4. Default value "scaled" can be changed by declaring `\mpplibnumbersystem{double}` or `\mpplibnumbersystem{decimal}`. See <https://github.com/lualatex/luamplib/issues/21>.

```

288   make_text    = luamplib.maketext,
289   run_script  = luamplib.runscript,
290   math_mode   = luamplib.numbersystem,
291   random_seed = math.random(4095),
292   extensions  = 1,
293 }

```

Append our own MetaPost preamble to the preamble above.

```

294 local preamble = preamble .. luamplib.mplicodepreamble
295 if luamplib.legacy_verbatimtex then
296   preamble = preamble .. luamplib.legacyverbatimtexpreamble
297 end
298 if luamplib.textextlabel then
299   preamble = preamble .. luamplib.textextlabelpreamble
300 end
301 local result
302 if not mpx then
303   result = { status = 99, error = "out of memory" }
304 else
305   result = mpx:execute(format(preamble, replacesuffix(name,"mp")))
306 end
307 reporterror(result)
308 return mpx, result
309 end
310

```

plain or metafun, though we cannot support metafun format fully.

```

311 local currentformat = "plain"
312
313 local function setformat (name)
314   currentformat = name
315 end

```

```

316 luamplib.setformat = setformat
317
318 local function process_indeed (mpx, data)
319   local converted, result = false, {}
320   if mpx and data then
321     result = mpx:execute(data)
322     local log = reporterror(result, true)
323     if log then
324       if result.fig then
325         converted = luamplib.convert(result)
326       else
327         warn("No figure output. Maybe no beginfig/endfig")
328       end
329     end
330   else
331     err("Mem file unloadable. Maybe generated with a different version of mpilib?")
332   end
333   return converted, result
334 end
335

v2.9 has introduced the concept of "code inherit"
336 luamplib.codeinherit = false
337 local mpilibinstances = {}
338
339 local function process (data, instancename)

The workaround of issue #70 seems to be unnecessary, as we use make_text now.

if not data:find(name_b.."beginfig%s*%([%+-%s]*%d[%.%d%s]*%)") then
  data = data .. "beginfig(-1);endfig;"
end

340 local defaultinstancename = currentformat .. (luamplib.numberformat or "scaled")
341   .. tostring(luamplib.texlabel) .. tostring(luamplib.legacy_verbatimtex)
342 local currfmt = instancename or defaultinstancename
343 if #currformt == 0 then
344   currformt = defaultinstancename
345 end
346 local mpx = mpilibinstances[currformt]
347 local standalone = false
348 if currformt == defaultinstancename then
349   standalone = not luamplib.codeinherit
350 end
351 if mpx and standalone then
352   mpx:finish()
353 end
354 if standalone or not mpx then
355   mpx = luamplibload(currentformat)

```

```

356     mplibinstances[currfmt] = mpx
357 end
358 return process_indeed(mpx, data)
359 end
360

```

`make_text` and some `run_script` uses `LuaTeX's` `tex.runtoks`, which made possible running `\TeX` code snippets inside `\directlua`.

```

361 local catlatex = luatexbase.registernumber("catcodetable@latex")
362 local catat11  = luatexbase.registernumber("catcodetable@atletter")
363

```

`tex.scantoks` sometimes fail to read catcode properly, especially `\#`, `\&`, or `\%`. After some experiment, we dropped using it. Instead, a function containing `tex.script` seems to work nicely.

```

local function run_tex_code_no_use (str, cat)
    cat = cat or catlatex
    texscantoks("mplibtmptoks", cat, str)
    texruntoks("mplibtmptoks")
end

```

```

364 local function run_tex_code (str, cat)
365   cat = cat or catlatex
366   texruntoks(function() texprint(cat, str) end)
367 end
368

```

Indefinite number of boxes are needed for `btx ... etex`. So starts at somewhat huge number of box registry. Of course, this may conflict with other packages using many many boxes. (When `codeinherit` feature is enabled, boxes must be globally defined.) But I don't know any reliable way to escape this danger.

```

369 local tex_box_id = 2047
      For conversion of sp to bp.
370 local factor = 65536*(7227/7200)
371
372 local texttext_fmt = [[image(addto currentpicture doublepath unitsquare )]..
373   [[xscaled %f yscaled %f shifted (0,-%f) ]][..]
374   [[withprescript "mplibtexboxid=%i:%f:%f"]]]
375
376 local function process_tex_text (str)
377   if str then
378     tex_box_id = tex_box_id + 1
379     local global = luamplib.globaltexttext and "\\\global" or ""
380     run_tex_code(format("%s\\setbox%i\\hbox{%s}", global, tex_box_id, str))
381     local box = texgetbox(tex_box_id)
382     local wd  = box.width / factor
383     local ht  = box.height / factor
384     local dp  = box.depth / factor

```

```

385     return texttext_fmt:format(wd, ht+dp, dp, tex_box_id, wd, ht+dp)
386   end
387   return ""
388 end
389

```

Make color or xcolor's color expressions usable, with \mpcolor or `mplibcolor`. These commands should be used with graphical objects.

```

390 local mplibcolor_fmt = [[\begingroup\let\XC@mcolor\relax]..
391   [[\def\set@color{\global\mplibtmptoks\expandafter{\current@color}}]..
392   [[\color %s \endgroup]]]
393
394 local function process_color (str)
395   if str then
396     if not str:find("{.-}") then
397       str = format("{%s}",str)
398     end
399     run_tex_code(mplibcolor_fmt:format(str), catat11)
400     return format('1 withprescript "MPlib0overrideColor=%s" , texgettoks"mplibtmptoks")"
401   end
402   return ""
403 end
404

```

\mpdim is expanded before MPLib process, so code below will not be used for `mplibcode` data. But who knows anyone would want it in .mp input file. If then, you can say `mplibdimen("5\textwidth")` for example.

```

405 local function process_dimen (str)
406   if str then
407     str = str:gsub("{{(.+)}}","%"..tostring(str))
408     run_tex_code(format([[{\begingroup\mplibtmptoks\expandafter{\the\dimexpr %s\relax}}]], str))
409     return format("begingroup %s endgroup", texgettoks"mplibtmptoks")
410   end
411   return ""
412 end
413

```

Newly introduced method of processing verbatimtex ... etex. Used when `\mpliblegacybehavior{false}` is declared.

```

414 local function process_verbatimtex_text (str)
415   if str then
416     run_tex_code(str)
417   end
418   return ""
419 end
420

```

For legacy verbatimtex process. verbatimtex ... etex before beginfig() is not ignored, but the TeX code is inserted just before the mplib box. And TeX code inside beginfig() ... endfig is inserted after the mplib box.

```

421 local tex_code_pre_mplib = {}

```

```

422 luamplib.figid = 1
423 luamplib.in_the_fig = false
424
425 local function legacy_mplibcode_reset ()
426   tex_code_pre_mplib = {}
427   luamplib.figid = 1
428 end
429
430 local function process_verbatimtex_prefig (str)
431   if str then
432     tex_code_pre_mplib[luamplib.figid] = str
433   end
434   return ""
435 end
436
437 local function process_verbatimtex_infig (str)
438   if str then
439     return format('special "postmplibverbtex=%s";', str)
440   end
441   return ""
442 end
443
444 local runscript_funcs = {
445   luamplibtext = process_tex_text,
446   luamplibcolor = process_color,
447   luamplibdimen = process_dimen,
448   luamplibprefig = process_verbatimtex_prefig,
449   luamplibinfig = process_verbatimtex_infig,
450   luamplibverbtex = process_verbatimtex_text,
451 }
452
For metafun format. see issue #79.

453 mp = mp or {}
454 local mp = mp
455 mp.mf_path_reset = mp.mf_path_reset or function() end
456 mp.mf_finish_saving_data = mp.mf_finish_saving_data or function() end
457
metafun 2021-03-09 changes crashes luamplib.

458 catcodes = catcodes or {}
459 local catcodes = catcodes
460 catcodes.numbers = catcodes.numbers or {}
461 catcodes.numbers.ctxcatcodes = catcodes.numbers.ctxcatcodes or catlateX
462 catcodes.numbers.texcatcodes = catcodes.numbers.texcatcodes or catlateX
463 catcodes.numbers.luacatcodes = catcodes.numbers.luacatcodes or catlateX
464 catcodes.numbers.notcatcodes = catcodes.numbers.notcatcodes or catlateX
465 catcodes.numbers.vrbcatcodes = catcodes.numbers.vrbcatcodes or catlateX
466 catcodes.numbers.prtcatcodes = catcodes.numbers.prtcatcodes or catlateX
467 catcodes.numbers.txtcatcodes = catcodes.numbers.txtcatcodes or catlateX
468

```

A function from ConTeXt general.

```
469 local function mpprint(buffer,...)
470   for i=1,select("#",...) do
471     local value = select(i,...)
472     if value ~= nil then
473       local t = type(value)
474       if t == "number" then
475         buffer[#buffer+1] = format("%.16f",value)
476       elseif t == "string" then
477         buffer[#buffer+1] = value
478       elseif t == "table" then
479         buffer[#buffer+1] = "(" .. tableconcat(value,",") .. ")"
480       else -- boolean or whatever
481         buffer[#buffer+1] = tostring(value)
482       end
483     end
484   end
485 end
486
487 function luamplib.runscript (code)
488   local id, str = code:match("(.-){(.*)}")
489   if id and str then
490     local f = runscript_funcs[id]
491     if f then
492       local t = f(str)
493       if t then return t end
494     end
495   end
496   local f = loadstring(code)
497   if type(f) == "function" then
498     local buffer = {}
499     function mp.print(...)
500       mpprint(buffer,...)
501     end
502     f()
503     buffer = tableconcat(buffer)
504     if buffer and buffer ~= "" then
505       return buffer
506     end
507     buffer = {}
508     mpprint(buffer, f())
509     return tableconcat(buffer)
510   end
511   return ""
512 end
513
      make_text must be one liner, so comment sign is not allowed.
514 local function protecttexcontents (str)
515   return str:gsub("\\%%", "\0PerCent\0")
```

```

516      :gsub("%%.-\n", "")
517      :gsub("%$.-", "")
518      :gsub("%zPerCent%z", "\%\%")
519      :gsub("%s+", " ")
520 end
521
522 luamplib.legacy_verbatimtex = true
523
524 function luamplib.maketext (str, what)
525   if str and str ~= "" then
526     str = protecttexcontents(str)
527     if what == 1 then
528       if not str:find("\\documentclass"..name_e) and
529         not str:find("\\begin%{document}") and
530         not str:find("\\documentstyle"..name_e) and
531         not str:find("\\usepackage"..name_e) then
532       if luamplib.legacy_verbatimtex then
533         if luamplib.in_the_fig then
534           return process_verbatimtex_infig(str)
535         else
536           return process_verbatimtex_prefig(str)
537         end
538       else
539         return process_verbatimtex_text(str)
540       end
541     end
542     else
543       return process_tex_text(str)
544     end
545   end
546   return ""
547 end
548

```

### Our MetaPost preambles

```

549 local mplibcodepreamble = [[
550 texscriptmode := 2;
551 def rawtexttext (expr t) = runscript("luamplibtext{"&t&"}") enddef;
552 def mplibcolor (expr t) = runscript("luamplibcolor{"&t&"}") enddef;
553 def mplibdimen (expr t) = runscript("luamplibdimen{"&t&"}") enddef;
554 def VerbatimTeX (expr t) = runscript("luamplibverbtex{"&t&"}") enddef;
555 if known context_mlib:
556   defaultfont := "cmtt10";
557   let infont = normalinfont;
558   let fontsize = normalfontsize;
559   vardef thelabel@#(expr p,z) =
560     if string p :
561       thelabel@#(p infont defaultfont scaled defaultscale,z)
562     else :
563       p shifted (z + labeloffset*mfun_laboff@# -

```

```

564      (mfun_labxf@#*lrcorner p + mfun_labyf@#*ulcorner p +
565      (1-mfun_labxf@#-mfun_labyf@#)*llcorner p))
566    fi
567  enddef;
568 def graphictext primary filename =
569   if (readfrom filename = EOF):
570     errmessage "Please prepare '&filename&' in advance with"&
571     " 'pstoedit -ssp -dt -f mpost yourfile.ps &filename&'";
572   fi
573   closefrom filename;
574   def data_mpy_file = filename enddef;
575   mfun_do_graphic_text (filename)
576 enddef;
577 else:
578   vardef texttext@# (text t) = rawtexttext (t) enddef;
579 fi
580 def externalfigure primary filename =
581   draw rawtexttext("\includegraphics{& filename &}")
582 enddef;
583 def TEX = texttext enddef;
584 ]]
585 luamplib.mplibcodepreamble = mplibcodepreamble
586
587 local legacyverbatimtexpreamble = [[
588 def specialVerbatimTeX (text t) = runscript("luamplibprefig{\"&t&}") enddef;
589 def normalVerbatimTeX (text t) = runscript("luamplibinfig(\"&t&\")") enddef;
590 let VerbatimTeX = specialVerbatimTeX;
591 extra_beginfig := extra_beginfig & " let VerbatimTeX = normalVerbatimTeX;"&
592   "runscript(\" &ditto& \"luamplib.in_the_fig=true\" &ditto& \");";
593 extra_endfig := extra_endfig & " let VerbatimTeX = specialVerbatimTeX;"&
594   "runscript(\" &ditto&
595   \"if luamplib.in_the_fig then luamplib.figid=luamplib.figid+1 end \"&
596   \"luamplib.in_the_fig=false\" &ditto& \");";
597 ]]
598 luamplib.legacyverbatimtexpreamble = legacyverbatimtexpreamble
599
600 local texttextlabelpreamble = [[
601 primarydef s infont f = rawtexttext(s) enddef;
602 def fontsize expr f =
603   begingroup
604   save size; numeric size;
605   size := mplibdimen("1em");
606   if size = 0: 10pt else: size fi
607   endgroup
608 enddef;
609 ]]
610 luamplib.texttextlabelpreamble = texttextlabelpreamble
611

```

When `\mplibverbatim` is enabled, do not expand `mplibcode` data.

```

612 luamplib.verbatiminput = false
613
614 local function protect_expansion (str)
615   if str then
616     str = str:gsub("\\", "!!Control!!!")
617     :gsub("%%", "!!Comment!!!")
618     :gsub("#", "!!HashSign!!!")
619     :gsub("{", "!!LBrace!!!")
620     :gsub("}", "!!RBrace!!!")
621   return format("\unexpanded{%s}",str)
622 end
623 end
624
625 local function unprotect_expansion (str)
626   if str then
627     return str:gsub("!!Control!!!", "\\")
628       :gsub("!!Comment!!!", "%%")
629       :gsub("!!HashSign!!!", "#")
630       :gsub("!!LBrace!!!", "{")
631       :gsub("!!RBrace!!!", "}")
632 end
633 end
634
635 luamplib.everymplib = { [""] = "" }
636 luamplib.everyendmplib = { [""] = "" }
637
638 local function process_mplicode (data, instancename)
639   This is needed for legacy behavior regarding verbatimtex
640   legacy_mplicode_reset()
641   local everymplib = luamplib.everymplib[instancename] or
642     luamplib.everymplib[""]
643   local everyendmplib = luamplib.everyendmplib[instancename] or
644     luamplib.everyendmplib[""]
645   data = format("\n%s\n%s\n%s\n", everymplib, data, everyendmplib)
646   data = data:gsub("\r", "\n")
647
648   data = data:gsub("\\mpcolor%s+(-%b{})", "mplicolor(\"%1\")")
649   data = data:gsub("\\mpdim%s+(%b{})", "mplicidimen(\"%1\")")
650   data = data:gsub("\\mpdim%s+(\\%a+)", "mplicidimen(\"%1\")")
651
652   data = data:gsub(btex_etex, function(str)
653     return format("btex %s etex ", -- space
654       luamplib.verbatiminput and str or protect_expansion(str)))
655   end)
656   data = data:gsub(verbatimtex_etex, function(str)
657     return format("verbatimtex %s etex; ", -- semicolon
658       luamplib.verbatiminput and str or protect_expansion(str)))

```

```
659   end)
660
```

If not `mplibverbatim`, expand `mplibcode` data, so that users can use TeX codes in it. It has turned out that no comment sign is allowed.

```
661 if not luamplib.verbatiminput then
662   data = data:gsub("\\".."-\\\"", protect_expansion)
663
664   data = data:gsub("\\%%", "\0Percent\0")
665   data = data:gsub("%%.-\n", "")
666   data = data:gsub("%zPercent%z", "\\%%")
667
668   run_tex_code(format("\\\\mplibmptoks\\\\expanded{{%s}}",data))
669   data = texgettoks"mplibmptoks"
```

Next line to address issue #55

```
670   data = data:gsub("##", "#")
671   data = data:gsub("\\".."-\\\"", unprotect_expansion)
672   data = data:gsub(btex_etex, function(str)
673     return format("btex %s etex", unprotect_expansion(str)))
674   end)
675   data = data:gsub(verbatimtex_etex, function(str)
676     return format("verbatimtex %s etex", unprotect_expansion(str)))
677   end)
678 end
679
680 process(data, instancename)
681 end
682 luamplib.process_mplibcode = process_mplibcode
683
```

For parsing `prescript` materials.

```
684 local further_split_keys =
685   mplibtexboxid = true,
686   sh_color_a    = true,
687   sh_color_b    = true,
688 }
689
690 local function script2table(s)
691   local t = {}
692   for _,i in ipairs(s:explode("\13+")) do
693     local k,v = i:match("(.-)=(.*)") -- v may contain = or empty.
694     if k and v and k ~= "" then
695       if further_split_keys[k] then
696         t[k] = v:explode(":")
697       else
698         t[k] = v
699       end
700     end
701   end
702   return t
```

```

703 end
704
    Codes below for inserting PDF literals are mostly from ConTeXt general, with small
    changes when needed.
705 local function getobjects(result,figure,f)
706   return figure:objects()
707 end
708
709 local function convert(result, flusher)
710   luamplib.flush(result, flusher)
711   return true -- done
712 end
713 luamplib.convert = convert
714
715 local function pdf_startfigure(n,llx,lly,urx,ury)
716   texprint(format("\\"..plibstarttoPDF{f}{f}{f}{f}",llx,lly,urx,ury))
717 end
718
719 local function pdf_stopfigure()
720   texprint("\\"..plibstopoPDF")
721 end
722
tex.tprint with catcode regime -2, as sometimes # gets doubled in the argument of
pdfliteral.
723 local function pdf_literalcode(fmt,...) -- table
724   texprint({"\\"..plibtoPDF"},{-2,format(fmt,...)},{""})
725 end
726
727 local function pdf_textfigure(font,size,text,width,height,depth)
728   text = text:gsub(".",function(c)
729     return format("\\"..hbox{\\"..char%i}",string.byte(c)) -- kerning happens in metapost
730   end)
731   texprint(format("\\"..plibtexttext{s}{f}{s}{s}{f}",font,size,text,0,-( 7200/ 7227)/65536*depth))
732 end
733
734 local bend_tolerance = 131/65536
735
736 local rx, sx, sy, ry, tx, ty, divider = 1, 0, 0, 1, 0, 0, 1
737
738 local function pen_characteristics(object)
739   local t = plib.pen_info(object)
740   rx, ry, sx, sy, tx, ty = t.rx, t.ry, t.sx, t.sy, t.tx, t.ty
741   divider = sx*sy - rx*ry
742   return not (sx==1 and rx==0 and ry==0 and sy==1 and tx==0 and ty==0), t.width
743 end
744
745 local function concat(px, py) -- no tx, ty here
746   return (sy*px-ry*py)/divider,(sx*py-rx*px)/divider

```

```

747 end
748
749 local function curved(ith,pth)
750   local d = pth.left_x - ith.right_x
751   if abs(ith.right_x - ith.x_coord - d) <= bend_tolerance and abs(pth.x_coord - pth.left_x - d) <= bend_tolerance then
752     d = pth.left_y - ith.right_y
753     if abs(ith.right_y - ith.y_coord - d) <= bend_tolerance and abs(pth.y_coord - pth.left_y - d) <= bend_tolerance then
754       return false
755     end
756   end
757   return true
758 end
759
760 local function flushnormalpath(path,open)
761   local pth, ith
762   for i=1,#path do
763     pth = path[i]
764     if not ith then
765       pdf_literalcode("%f %f m",pth.x_coord, pth.y_coord)
766     elseif curved(ith, pth) then
767       pdf_literalcode("%f %f %f %f %f c",ith.right_x,ith.right_y, pth.left_x, pth.left_y, pth.x_coord, pth.y_coord)
768     else
769       pdf_literalcode("%f %f l",pth.x_coord, pth.y_coord)
770     end
771     ith = pth
772   end
773   if not open then
774     local one = path[1]
775     if curved(pth, one) then
776       pdf_literalcode("%f %f %f %f %f c", pth.right_x, pth.right_y, one.left_x, one.left_y, one.x_coord, one.y_coord )
777     else
778       pdf_literalcode("%f %f l", one.x_coord, one.y_coord)
779     end
780   elseif #path == 1 then -- special case .. draw point
781     local one = path[1]
782     pdf_literalcode("%f %f l", one.x_coord, one.y_coord)
783   end
784 end
785
786 local function flushconcatpath(path,open)
787   pdf_literalcode("%f %f %f %f %f cm", sx, rx, ry, sy, tx ,ty)
788   local pth, ith
789   for i=1,#path do
790     pth = path[i]
791     if not ith then
792       pdf_literalcode("%f %f m",concat(pth.x_coord, pth.y_coord))
793     elseif curved(ith, pth) then
794       local a, b = concat(ith.right_x, ith.right_y)
795       local c, d = concat(pth.left_x, pth.left_y)
796       pdf_literalcode("%f %f %f %f %f c", a,b,c,d,concat(pth.x_coord, pth.y_coord))

```

```

797     else
798       pdf_literalcode("%f %f 1",concat(pth.x_coord, pth.y_coord))
799     end
800   ith = pth
801 end
802 if not open then
803   local one = path[1]
804   if curved(pth,one) then
805     local a, b = concat(pth.right_x, pth.right_y)
806     local c, d = concat(one.left_x, one.left_y)
807     pdf_literalcode("%f %f %f %f %f %f c", a, b, c, d, concat(one.x_coord, one.y_coord))
808   else
809     pdf_literalcode("%f %f 1", concat(one.x_coord, one.y_coord))
810   end
811 elseif #path == 1 then -- special case .. draw point
812   local one = path[1]
813   pdf_literalcode("%f %f 1", concat(one.x_coord, one.y_coord))
814 end
815 end
816

dvipdfmx is supported, though nobody seems to use it.

817 local pdfoutput = tonumber(texget("outputmode")) or tonumber(texget("pdfoutput"))
818 local pdfmode = pdfoutput > 0
819
820 local function start_pdf_code()
821   if pdfmode then
822     pdf_literalcode("q")
823   else
824     texprint("\special{pdf:bcontent}") -- dvipdfmx
825   end
826 end
827 local function stop_pdf_code()
828   if pdfmode then
829     pdf_literalcode("Q")
830   else
831     texprint("\special{pdf:econtent}") -- dvipdfmx
832   end
833 end
834
```

Now we process hboxes created from `btx ... etex` or `textext(...)` or `TEX(...)`, all being the same internally.

```

835 local function put_tex_boxes (object,prescript)
836   local box = prescript.mplibtexboxid
837   local n,tw,th = box[1],tonumber(box[2]),tonumber(box[3])
838   if n and tw and th then
839     local op = object.path
840     local first, second, fourth = op[1], op[2], op[4]
841     local tx, ty = first.x_coord, first.y_coord
842     local sx, rx, ry, sy = 1, 0, 0, 1
```

```

843     if tw ~= 0 then
844         sx = (second.x_coord - tx)/tw
845         rx = (second.y_coord - ty)/tw
846         if sx == 0 then sx = 0.00001 end
847     end
848     if th ~= 0 then
849         sy = (fourth.y_coord - ty)/th
850         ry = (fourth.x_coord - tx)/th
851         if sy == 0 then sy = 0.00001 end
852     end
853     start_pdf_code()
854     pdf_literalcode("%f %f %f %f %f cm",sx,rx,ry,sy,tx,ty)
855     texprint(format("\\\mplibputtextbox{%-i}",n))
856     stop_pdf_code()
857 end
858 end
859

```

### Colors and Transparency

```

860 local pdf_objs = {}
861 local token, getpageres, setpageres = newtoken or token
862 local pgf = { bye = "pgfutil@everybye", extgs = "pgf@sys@addpdfresource@extgs@plain" }
863
864 if pdfmode then -- repect luatdfload-colors
865     getpageres = pdf.getpageresources or function() return pdf.pageresources end
866     setpageres = pdf.setpageresources or function(s) pdf.pageresources = s end
867 else
868     texprint("\\special{pdf:obj @MPlibTr<>>}",
869                  "\\special{pdf:obj @MPlibSh<>>}")
870 end
871
872 local function update_pdfobjs (os)
873     local on = pdf_objs[os]
874     if on then
875         return on, false
876     end
877     if pdfmode then
878         on = pdf.immediateobj(os)
879     else
880         on = pdf_objs.cnt or 0
881         pdf_objs.cnt = on + 1
882     end
883     pdf_objs[os] = on
884     return on, true
885 end
886
887 local transparancy_modes = { [0] = "Normal",
888     "Normal",      "Multiply",      "Screen",      "Overlay",
889     "SoftLight",    "HardLight",    "ColorDodge",   "ColorBurn",
890     "Darken",       "Lighten",       "Difference",  "Exclusion",

```

```

891 "Hue",           "Saturation",   "Color",        "Luminosity",
892 "Compatible",
893 }
894
895 local function update_tr_res(res, mode, opaq)
896   local os = format("<</BM /%s/ca %.3f/CA %.3f/AIS false>>", mode, opaq, opaq)
897   local on, new = update_pdfobjs(os)
898   if new then
899     if pdfmode then
900       res = format("%s/MPlibTr%i %i 0 R", res, on, on)
901     else
902       if pgf.loaded then
903         texsprint(format("\csname %s\endcsname{/MPlibTr%i%s}", pgf.extgs, on, os))
904       else
905         texsprint(format("\special{pdf:put @MPlibTr<</MPlibTr%i%s>>}", on, os))
906       end
907     end
908   end
909   return res, on
910 end
911
912 local function tr_pdf_pageresources(mode, opaq)
913   if token and pgf.bye and not pgf.loaded then
914     pgf.loaded = token.create(pgf.bye).cmdname == "assign_toks"
915     pgf.bye = pgf.loaded and pgf.bye
916   end
917   local res, on_on, off_on = "", nil, nil
918   res, off_on = update_tr_res(res, "Normal", 1)
919   res, on_on = update_tr_res(res, mode, opaq)
920   if pdfmode then
921     if res ~= "" then
922       if pgf.loaded then
923         texsprint(format("\csname %s\endcsname[%s]", pgf.extgs, res))
924       else
925         local tpr, n = getpageres() or "", 0
926         tpr, n = tpr:gsub("/ExtGState<<", "%1..res")
927         if n == 0 then
928           tpr = format("%s/ExtGState<<%s>>", tpr, res)
929         end
930         setpageres(tpr)
931       end
932     end
933   else
934     if not pgf.loaded then
935       texsprint(format("\special{pdf:put @resources<</ExtGState @MPlibTr>>}"))
936     end
937   end
938   return on_on, off_on
939 end
940

```

### Shading with metafun format. (maybe legacy way)

```

941 local shading_res
942
943 local function shading_initialize ()
944   shading_res = {}
945   if pdfmode and luatexbase.callbacktypes.finish_pdffile then -- ltluatex
946     local shading_obj = pdf.reserveobj()
947     setpageres(format("%s/Shading %i 0 R",getpageres() or "",shading_obj))
948     luatexbase.add_to_callback("finish_pdffile", function()
949       pdf.immediateobj(shading_obj,format("<<%s>>",tableconcat(shading_res)))
950     end, "luamplib.finish_pdffile")
951   pdf_objs.finishpdf = true
952 end
953 end
954
955 local function sh_pdffpageresources(shtype,domain,colorspace,colora,colorb,coordinates)
956   if not shading_res then shading_initialize() end
957   local os = format("<</FunctionType 2/Domain [ %s ]/C0 [ %s ]/C1 [ %s ]/N 1>>",
958                     domain, colora, colorb)
959   local funcobj = pdfmode and format("%i 0 R",update_pdfobjs(os)) or os
960   os = format("<</ShadingType %i/ColorSpace /%s/Function %s/Coords [ %s ]/Extend [ true true ]/AntiAlias true>>",
961             shtype, colorspace, funcobj, coordinates)
962   local on, new = update_pdfobjs(os)
963   if pdfmode then
964     if new then
965       local res = format("/MPlibSh%i %i 0 R", on, on)
966       if pdf_objs.finishpdf then
967         shading_res[#shading_res+1] = res
968       else
969         local pageres = getpageres() or ""
970         if not pageres:find("/Shading<<.*>>") then
971           pageres = pageres.."/Shading<>>"
972         end
973         pageres = pageres:gsub("/Shading<<","%1..res")
974         setpageres(pageres)
975       end
976     end
977   else
978     if new then
979       texprint(format("\\\special{pdf:put @MPlibSh<</MPlibSh%i%s>>}",on,os))
980     end
981     texprint(format("\\\special{pdf:put @resources<</Shading @MPlibSh>>}"))
982   end
983   return on
984 end
985
986 local function color_normalize(ca,cb)
987   if #cb == 1 then
988     if #ca == 4 then

```

```

989      cb[1], cb[2], cb[3], cb[4] = 0, 0, 0, 1-cb[1]
990  else -- #ca = 3
991    cb[1], cb[2], cb[3] = cb[1], cb[1], cb[1]
992  end
993 elseif #cb == 3 then -- #ca == 4
994   cb[1], cb[2], cb[3], cb[4] = 1-cb[1], 1-cb[2], 1-cb[3], 0
995 end
996 end
997
998 local prev_override_color
999
1000 local function do_preobj_color(object,prescript)
1001   transparency
1002   local opaq = prescript and prescript.tr_transparency
1003   local tron_no, troff_no
1004   if opaq then
1005     local mode = prescript.tr_alternative or 1
1006     mode = transparancy_modes[tonumber(mode)]
1007     tron_no, troff_no = tr_pdf_pageresources(mode,opaq)
1008     pdf_literalcode("/MPlibTr%i gs",tron_no)
1009   end
1010   color
1011   local override = prescript and prescript.MPlibOverrideColor
1012   if override then
1013     if pdfmode then
1014       pdf_literalcode(override)
1015       override = nil
1016     else
1017       texprint(format("\\special{color push %s}",override))
1018     end
1019   else
1020     local cs = object.color
1021     if cs and #cs > 0 then
1022       pdf_literalcode(luamplib.colorconverter(cs))
1023       prev_override_color = nil
1024     elseif not pdfmode then
1025       override = prev_override_color
1026       if override then
1027         texprint(format("\\special{color push %s}",override))
1028       end
1029     end
1030   end
1031   shading
1032   local sh_type = prescript and prescript.sh_type
1033   if sh_type then
1034     local domain = prescript.sh_domain
1035     local centera = prescript.sh_center_a:explode()

```

```

1034     local centerb = prescript.sh_center_b:explode()
1035     for _,t in pairs({centera,centerb}) do
1036         for i,v in ipairs(t) do
1037             t[i] = format("%f",v)
1038         end
1039     end
1040     centera = tableconcat(centera," ")
1041     centerb = tableconcat(centerb," ")
1042     local colora = prescript.sh_color_a or {0};
1043     local colorb = prescript.sh_color_b or {1};
1044     for _,t in pairs({colora,colorb}) do
1045         for i,v in ipairs(t) do
1046             t[i] = format("%.3f",v)
1047         end
1048     end
1049     if #colora > #colorb then
1050         color_normalize(colora,colorb)
1051     elseif #colorb > #colora then
1052         color_normalize(colorb,colora)
1053     end
1054     local colorspace
1055     if #colorb == 1 then colorspace = "DeviceGray"
1056     elseif #colorb == 3 then colorspace = "DeviceRGB"
1057     elseif #colorb == 4 then colorspace = "DeviceCMYK"
1058     else    return troff_no,override
1059     end
1060     colora = tableconcat(colora, " ")
1061     colorb = tableconcat(colorb, " ")
1062     local shade_no
1063     if sh_type == "linear" then
1064         local coordinates = tableconcat({centera,centerb}, " ")
1065         shade_no = sh_pdffpageresources(2, domain, colorspace, colora, colorb, coordinates)
1066     elseif sh_type == "circular" then
1067         local radiusa = format("%f",prescript.sh_radius_a)
1068         local radiusb = format("%f",prescript.sh_radius_b)
1069         local coordinates = tableconcat({centera,radiusa,centerb,radiusb}, " ")
1070         shade_no = sh_pdffpageresources(3, domain, colorspace, colora, colorb, coordinates)
1071     end
1072     pdf_literalcode("q /Pattern cs")
1073     return troff_no,override,shade_no
1074 end
1075 return troff_no,override
1076 end
1077
1078 local function do_postobj_color(tr,over,sh)
1079     if sh then
1080         pdf_literalcode("W n /MplibSh%sh Q",sh)
1081     end
1082     if over then
1083         texsprint("\\special{color pop}")

```

```

1084   end
1085   if tr then
1086     pdf_literalcode("/MPlibTr%i gs",tr)
1087   end
1088 end
1089

Finally, flush figures by inserting PDF literals.

1090 local function flush(result,flusher)
1091   if result then
1092     local figures = result.fig
1093     if figures then
1094       for f=1, #figures do
1095         info("flushing figure %s",f)
1096         local figure = figures[f]
1097         local objects = getobjects(result,figure,f)
1098         local fignum = tonumber(figure:filename():match("(%d)+$") or figure:charcode() or 0)
1099         local miterlimit, linecap, linejoin, dashed = -1, -1, -1, false
1100         local bbox = figure:boundingbox()
1101         local llx, lly, urx, ury = bbox[1], bbox[2], bbox[3], bbox[4] -- faster than unpack
1102         if urx < llx then

```

luamplib silently ignores this invalid figure for those that do not contain beginfig ... endfig.  
(issue #70) Original code of ConTeXt general was:

```

-- invalid
pdf_startfigure(fignum,0,0,0,0)
pdf_stopfigure()

1103   else

```

For legacy behavior. Insert ‘pre-fig’ TeX code here, and prepare a table for ‘in-fig’ codes.

```

1104     if tex_code_pre_mplib[f] then
1105       texprint(tex_code_pre_mplib[f])
1106     end
1107     local TeX_code_bot = {}
1108     pdf_startfigure(fignum,llx,lly,urx,ury)
1109     start_pdf_code()
1110     if objects then
1111       local savedpath = nil
1112       local savedhtap = nil
1113       for o=1,#objects do
1114         local object      = objects[o]
1115         local objecttype = object.type

```

The following 5 lines are part of btex...etex patch. Again, colors are processed at this stage.

```

1116     local prescript    = object.prescript
1117     prescript = prescript and script2table(prescript) -- prescript is now a table
1118     local tr_opaq,cr_over,shade_no = do_preobj_color(object,prescript)

```

```

1119     if prescript and prescript.mplibtexboxid then
1120         put_tex_boxes(object,prescript)
1121     elseif objecttype == "start_bounds" or objecttype == "stop_bounds" then --skip
1122     elseif objecttype == "start_clip" then
1123         local evenodd = not object.istext and object.postscript == "evenodd"
1124         start_pdf_code()
1125         flushnormalpath(object.path,false)
1126         pdf_literalcode(evenodd and "%* n" or "% n")
1127     elseif objecttype == "stop_clip" then
1128         stop_pdf_code()
1129         miterlimit, linecap, linejoin, dashed = -1, -1, -1, false
1130     elseif objecttype == "special" then
1131
1132     Collect TeX codes that will be executed after flushing. Legacy behavior.
1133
1134         if prescript and prescript.postmplibverbtex then
1135             TeX_code_bot[#TeX_code_bot+1] = prescript.postmplibverbtex
1136             end
1137         elseif objecttype == "text" then
1138             local ot = object.transform -- 3,4,5,6,1,2
1139             start_pdf_code()
1140             pdf_literalcode("%f %f %f %f %f cm",ot[3],ot[4],ot[5],ot[6],ot[1],ot[2])
1141             pdf_textfigure(object.font,object.dsize,object.text,object.width,object.height,object.depth)
1142             stop_pdf_code()
1143         else
1144             local evenodd, collect, both = false, false, false
1145             local postscript = object.postscript
1146             if not object.istext then
1147                 if postscript == "evenodd" then
1148                     evenodd = true
1149                 elseif postscript == "collect" then
1150                     collect = true
1151                 elseif postscript == "both" then
1152                     both = true
1153                 elseif postscript == "eoboth" then
1154                     evenodd = true
1155                     both = true
1156                 end
1157             end
1158             if collect then
1159                 if not savedpath then
1160                     savedpath = { object.path or false }
1161                     savedhtap = { object.htap or false }
1162                 else
1163                     savedpath[#savedpath+1] = object.path or false
1164                     savedhtap[#savedhtap+1] = object.htap or false
1165                 end
1166             else
1167                 local ml = object.miterlimit
1168                 if ml and ml ~= miterlimit then
1169                     miterlimit = ml

```

```

1167         pdf_literalcode("%f M",ml)
1168     end
1169     local lj = object.linejoin
1170     if lj and lj ~= linejoin then
1171         linejoin = lj
1172         pdf_literalcode("%i j",lj)
1173     end
1174     local lc = object.linecap
1175     if lc and lc ~= linecap then
1176         linecap = lc
1177         pdf_literalcode("%i J",lc)
1178     end
1179     local dl = object.dash
1180     if dl then
1181         local d = format("[%s] %f d",tableconcat(dl.dashes or {}," "),dl.offset)
1182         if d ~= dashed then
1183             dashed = d
1184             pdf_literalcode(dashed)
1185         end
1186         elseif dashed then
1187             pdf_literalcode("[] 0 d")
1188             dashed = false
1189         end
1190         local path = object.path
1191         local transformed, penwidth = false, 1
1192         local open = path and path[1].left_type and path[#path].right_type
1193         local pen = object.pen
1194         if pen then
1195             if pen.type == 'elliptical' then
1196                 transformed, penwidth = pen_characteristics(object) -- boolean, value
1197                 pdf_literalcode("%f w",penwidth)
1198                 if objecttype == 'fill' then
1199                     objecttype = 'both'
1200                 end
1201                 else -- calculated by mpplib itself
1202                     objecttype = 'fill'
1203                 end
1204             end
1205             if transformed then
1206                 start_pdf_code()
1207             end
1208             if path then
1209                 if savedpath then
1210                     for i=1,#savedpath do
1211                         local path = savedpath[i]
1212                         if transformed then
1213                             flushconcatpath(path,open)
1214                         else
1215                             flushnormalpath(path,open)
1216                         end

```

```

1217         end
1218         savedpath = nil
1219     end
1220     if transformed then
1221         flushconcatpath(path,open)
1222     else
1223         flushnormalpath(path,open)
1224     end

```

Change from ConTeXt general: there was color stuffs.

```

1225         if not shade_no then -- conflict with shading
1226             if objecttype == "fill" then
1227                 pdf_literalcode(evenodd and "h f*" or "h f")
1228             elseif objecttype == "outline" then
1229                 if both then
1230                     pdf_literalcode(evenodd and "h B*" or "h B")
1231                 else
1232                     pdf_literalcode(open and "S" or "h S")
1233                 end
1234             elseif objecttype == "both" then
1235                 pdf_literalcode(evenodd and "h B*" or "h B")
1236             end
1237         end
1238     end
1239     if transformed then
1240         stop_pdf_code()
1241     end
1242     local path = object.htap
1243     if path then
1244         if transformed then
1245             start_pdf_code()
1246         end
1247         if savedhtap then
1248             for i=1,#savedhtap do
1249                 local path = savedhtap[i]
1250                 if transformed then
1251                     flushconcatpath(path,open)
1252                 else
1253                     flushnormalpath(path,open)
1254                 end
1255             end
1256             savedhtap = nil
1257             evenodd = true
1258         end
1259         if transformed then
1260             flushconcatpath(path,open)
1261         else
1262             flushnormalpath(path,open)
1263         end
1264     if objecttype == "fill" then

```

```

1265           pdf_literalcode(evenodd and "h f*" or "h f")
1266 elseif objecttype == "outline" then
1267     pdf_literalcode(open and "S" or "h S")
1268 elseif objecttype == "both" then
1269     pdf_literalcode(evenodd and "h B*" or "h B")
1270 end
1271 if transformed then
1272     stop_pdf_code()
1273 end
1274 end
1275 end
1276 end

```

Added to ConTeXt general: color stuff. And execute legacy verbatimtex code.

```

1277         do_postobj_color(tr_opaq,cr_over,shade_no)
1278     end
1279 end
1280 stop_pdf_code()
1281 pdf_stopfigure()
1282 if #TeX_code_bot > 0 then texsprint(TeX_code_bot) end
1283 end
1284 end
1285 end
1286 end
1287 end
1288 luamplib.flush = flush
1289
1290 local function colorconverter(cr)
1291     local n = #cr
1292     if n == 4 then
1293         local c, m, y, k = cr[1], cr[2], cr[3], cr[4]
1294         return format("%.3f %.3f %.3f %.3f k %.3f %.3f %.3f K",c,m,y,k,c,m,y,k), "0 g 0 G"
1295     elseif n == 3 then
1296         local r, g, b = cr[1], cr[2], cr[3]
1297         return format("%.3f %.3f %.3f rg %.3f %.3f %.3f RG",r,g,b,r,g,b), "0 g 0 G"
1298     else
1299         local s = cr[1]
1300         return format("%.3f g %.3f G",s,s), "0 g 0 G"
1301     end
1302 end
1303 luamplib.colorconverter = colorconverter

```

## 2.2 TeX package

First we need to load some packages.

```

1304 \bgroup\expandafter\expandafter\expandafter\egroup
1305 \expandafter\ifx\csname selectfont\endcsname\relax
1306   \input lltuatem
1307 \else
1308   \NeedsTeXFormat{LaTeX2e}

```

```

1309  \ProvidesPackage{luamplib}
1310      [2022/01/12 v2.23.0 mplib package for LuaTeX]
1311  \ifx\newluafunction@\undefined
1312  \input ltluatex
1313  \fi
1314 \fi

        Loading of lua code.

1315 \directlua{require("luamplib")}

        Support older engine. Seems we don't need it, but no harm.

1316 \ifx\pdfoutput\undefined
1317   \let\pdfoutput\outputmode
1318   \protected\def\pdfliteral{\pdfextension literal}
1319 \fi

        Unfortuantely there are still packages out there that think it is a good idea to manually set \pdfoutput which defeats the above branch that defines \pdfliteral. To cover that case we need an extra check.

1320 \ifx\pdfliteral\undefined
1321   \protected\def\pdfliteral{\pdfextension literal}
1322 \fi

        Set the format for metapost.

1323 \def\mplibsetformat#1{\directlua{luamplib.setformat("#1")}}

        luamplib works in both PDF and DVI mode, but only DVIPDFMx is supported currently among a number of DVI tools. So we output a warning.

1324 \ifnum\pdfoutput>0
1325   \let\mplibtoPDF\pdfliteral
1326 \else
1327   \def\mplibtoPDF#1{\special{pdf:literal direct #1}}
1328   \ifcsname PackageWarning\endcsname
1329     \PackageWarning{luamplib}{take dvipdfmx path, no support for other dvi tools currently.}
1330   \else
1331     \write128{}
1332     \write128{luamplib Warning: take dvipdfmx path, no support for other dvi tools currently.}
1333     \write128{}
1334   \fi
1335 \fi

        Make \mplibcode typesetted always in horizontal mode.

1336 \def\mplibforcehmode{\let\prependtomplibbox\leavevmode}
1337 \def\mplibnoforcehmode{\let\prependtomplibbox\relax}
1338 \mplibnoforcehmode

        Catcode. We want to allow comment sign in \mplibcode.

1339 \def\mplibsetupcatcodes{%
1340   %catcode`{=12 %catcode`}=12
1341   \catcode`\#=12 \catcode`\^=12 \catcode`\~=12 \catcode`\_=12
1342   \catcode`\&=12 \catcode`\$=12 \catcode`\%=12 \catcode`\^^M=12
1343 }

```

Make btex...etex box zero-metric.

```
1344 \def\mplibputtextbox#1{\vbox to 0pt{\vss\hbox to 0pt{\raise\dp#1\copy#1\hss}}}
```

The Plain-specific stuff.

```
1345 \unless\ifcsname ver@luamplib.sty\endcsname
1346 \def\mplibcode{%
1347   \begingroup
1348   \begingroup
1349   \mplibsetupcatcodes
1350   \mplibdocode
1351 }
1352 \long\def\mplibdocode#1\endmplibcode{%
1353   \endgroup
1354   \directlua{luamplib.process_mplibcode([==[\unexpanded{#1}]==], "")}%
1355   \endgroup
1356 }
1357 \else
```

The L<sup>A</sup>T<sub>E</sub>X-specific part: a new environment.

```
1358 \newenvironment{mplibcode}[1][]{%
1359   \global\def\currentmpinstancename{#1}%
1360   \mplibtmptoks{}\\ltxdomplibcode
1361 }{%
1362 \def\ltxdomplibcode{%
1363   \begingroup
1364   \mplibsetupcatcodes
1365   \ltxdomplibcodeindeed
1366 }
1367 \def\mplib@mplibcode{mplibcode}
1368 \long\def\ltxdomplibcodeindeed#1\end#2{%
1369   \endgroup
1370   \mplibtmptoks\expandafter{\the\mplibtmptoks#1}%
1371   \def\mplibtemp@a{#2}%
1372   \ifx\mplib@mplibcode\mplibtemp@a
1373     \directlua{luamplib.process_mplibcode([==[\the\mplibtmptoks]==], "\currentmpinstancename")}%
1374     \end{mplibcode}%
1375   \else
1376     \mplibtmptoks\expandafter{\the\mplibtmptoks\end{#2}}%
1377     \expandafter\ltxdomplibcode
1378   \fi
1379 }
1380 \fi}
```

User settings.

```
1381 \def\mplibshowlog#1{\directlua{%
1382   local s = string.lower("#1")
1383   if s == "enable" or s == "true" or s == "yes" then
1384     luamplib.showlog = true
1385   else
1386     luamplib.showlog = false
1387   end}}
```

```

1388 }}
1389 \def\mpliblegacybehavior#1{\directlua{
1390     local s = string.lower("#1")
1391     if s == "enable" or s == "true" or s == "yes" then
1392         luamplib.legacy_verbatimtex = true
1393     else
1394         luamplib.legacy_verbatimtex = false
1395     end
1396 }
1397 \def\mplibverbatim#1{\directlua{
1398     local s = string.lower("#1")
1399     if s == "enable" or s == "true" or s == "yes" then
1400         luamplib.verbatiminput = true
1401     else
1402         luamplib.verbatiminput = false
1403     end
1404 }
1405 \newtoks\mplibtmtoks
\everymplib & \everyendmplib: macros resetting luamplib.every(end)mplib tables

1406 \protected\def\everymplib{%
1407     \begingroup
1408     \mplibsetupcatcodes
1409     \mplibdoeverymplib
1410 }
1411 \protected\def\everyendmplib{%
1412     \begingroup
1413     \mplibsetupcatcodes
1414     \mplibdoeveryendmplib
1415 }
1416 \ifcsname ver@luamplib.sty\endcsname
1417     \newcommand\mplibdoeverymplib[2][]{%
1418         \endgroup
1419         \directlua{
1420             luamplib.everymplib["#1"] = [==[\unexpanded{#2}]==]
1421         }%
1422     }
1423     \newcommand\mplibdoeveryendmplib[2][]{%
1424         \endgroup
1425         \directlua{
1426             luamplib.everyendmplib["#1"] = [==[\unexpanded{#2}]==]
1427         }%
1428     }
1429 \else
1430     \long\def\mplibdoeverymplib#1{%
1431         \endgroup
1432         \directlua{
1433             luamplib.everymplib[""] = [==[\unexpanded{#1}]==]
1434         }%
1435     }

```

```

1436 \long\def\mplibdoeveryendmplib#1{%
1437   \endgroup
1438   \directlua{
1439     luamplib.everyendmplib[""] = [===[\unexpanded{#1}]==]
1440   }%
1441 }
1442 \fi

```

Allow TeX dimen/color macros. Now runscript does the job, so the following lines are not needed for most cases. But the macros will be expanded when they are used in another macro.

```

1443 \def\mpdim#1{ \mplbdimen("#1") }
1444 \def\mpcolor#1#2{\domplibcolor{#1}{#2}}
1445 \def\domplibcolor#1#2{ \mplbcolor("#1{#2}) }

```

MPLib's number system. Now binary has gone away.

```

1446 \def\mplibnumbersystem#1{\directlua{
1447   local t = "#1"
1448   if t == "binary" then t = "decimal" end
1449   luamplib.numbersystem = t
1450 }}

```

Settings for .mp cache files.

```

1451 \def\mplibmakenocache#1{\mplibdomakenocache #1,*,*}
1452 \def\mplibdomakenocache#1{%
1453   \ifx\empty#1\empty
1454     \expandafter\mplibdomakenocache
1455   \else
1456     \ifx*#1\else
1457       \directlua{luamplib.noneedtoreplace["#1.mp"]=true}%
1458       \expandafter\expandafter\expandafter\mplibdomakenocache
1459     \fi
1460   \fi
1461 }
1462 \def\mplibcancelnocache#1{\mplibdocancelnocache #1,*,*}
1463 \def\mplibdocancelnocache#1{%
1464   \ifx\empty#1\empty
1465     \expandafter\mplibdocancelnocache
1466   \else
1467     \ifx*#1\else
1468       \directlua{luamplib.noneedtoreplace["#1.mp"]=false}%
1469       \expandafter\expandafter\expandafter\mplibdocancelnocache
1470     \fi
1471   \fi
1472 }
1473 \def\mplibcachedir#1{\directlua{luamplib.getcachedir("\unexpanded{#1})}}

```

More user settings.

```

1474 \def\mplibtextlabel#1{\directlua{
1475   local s = string.lower("#1")
1476   if s == "enable" or s == "true" or s == "yes" then

```

```

1477     luamplib.texttextlabel = true
1478   else
1479     luamplib.texttextlabel = false
1480   end
1481 }
1482 \def\mplibcodeinherit#1{\directlua{
1483   local s = string.lower("#1")
1484   if s == "enable" or s == "true" or s == "yes" then
1485     luamplib.codeinherit = true
1486   else
1487     luamplib.codeinherit = false
1488   end
1489 }
1490 \def\mplibglobaltexttext#1{\directlua{
1491   local s = string.lower("#1")
1492   if s == "enable" or s == "true" or s == "yes" then
1493     luamplib.globaltexttext = true
1494   else
1495     luamplib.globaltexttext = false
1496   end
1497 }

```

The followings are from ConTeXt general, mostly. We use a dedicated scratchbox.

```
1498 \ifx\mplibscratchbox\undefined \newbox\mplibscratchbox \fi
```

We encapsulate the litterals.

```

1499 \def\mplibstarttoPDF#1#2#3#4{%
1500   \prependtomplibbox
1501   \hbox\bgroup
1502   \xdef\MPllx{#1}\xdef\MPlly{#2}%
1503   \xdef\MPurx{#3}\xdef\MPury{#4}%
1504   \xdef\MPwidth{\the\dimexpr#3bp-#1bp\relax}%
1505   \xdef\MPheight{\the\dimexpr#4bp-#2bp\relax}%
1506   \parskip0pt%
1507   \leftskip0pt%
1508   \parindent0pt%
1509   \everypar{}%
1510   \setbox\mplibscratchbox\vbox\bgroup
1511   \noindent
1512 }
1513 \def\mplibstopoPDF{%
1514   \egroup %
1515   \setbox\mplibscratchbox\hbox %
1516   {\hskip-\MPllx bp%
1517   \raise-\MPlly bp%
1518   \box\mplibscratchbox}%
1519   \setbox\mplibscratchbox\vbox to \MPheight
1520   {\vfill
1521   \hsize\MPwidth
1522   \wd\mplibscratchbox0pt%
1523   \ht\mplibscratchbox0pt%

```

```
1524     \dp\mplibscratchbox0pt%
1525     \box\mplibscratchbox}%
1526 \wd\mplibscratchbox\MPwidth
1527 \ht\mplibscratchbox\MPheight
1528 \box\mplibscratchbox
1529 \egroup
1530 }
```

Text items have a special handler.

```
1531 \def\mpplibtextext#1#2#3#4#5{%
1532   \begingroup
1533   \setbox\mplibscratchbox\hbox
1534   {\font\temp=#1 at #2bp%
1535     \temp
1536     #3}%
1537   \setbox\mplibscratchbox\hbox
1538   {\hskip#4 bp%
1539     \raise#5 bp%
1540     \box\mplibscratchbox}%
1541   \wd\mplibscratchbox0pt%
1542   \ht\mplibscratchbox0pt%
1543   \dp\mplibscratchbox0pt%
1544   \box\mplibscratchbox
1545 \endgroup
1546 }
```

Input luamplib.cfg when it exists.

```
1547 \openin0=luamplib.cfg
1548 \ifeof0 \else
1549   \closein0
1550   \input luamplib.cfg
1551 \fi
```

That's all folks!

### 3 The GNU GPL License v2

The GPL requires the complete license text to be distributed along with the code. I recommend the canonical source, instead: <http://www.gnu.org/licenses/old-licenses/gpl-2.0.html>. But if you insist on an included copy, here it is. You might want to zoom in.

#### GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright © 1989, 1991 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

#### Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the General Public License is intended to guarantee that you have the freedom to share and change free software--to make sure that the same freedoms that others enjoyed are also available to you. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can use it for your programs as well.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to redistribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things. To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have, and you must not reflect on the original authors' reputation for doing something that you are not capable of doing.

You must also cause any recipient to receive the source code (in the specific manner described above) either directly or through a third party that receives the source code along with it.

The precise terms and conditions for copying, distribution and modification follow.

#### TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

1. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of the General Public License. The "Program" below refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing portions of the Program, or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is addressed as "modification".) Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

2. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy a appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License, and to the absence of any warranty; and give all other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

3. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

(a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

(b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

(c) If the modified program normally sends command-line arguments that run you must cause the modified version to give those arguments an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) for any modified version; it must also preserve the copyright notices and disclaimer that are present in the program; it must not link or otherwise associate itself with the Program or any program that displays copyright notices and disclaimers containing a different copyright holder's name or logo; it must not claim that the modified version is the original program.

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably separated at low cost in time and/or money, then such sections may be distributed separately under their own terms (but not under their original license), and the original license and this License will not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be

on the terms of this License, whose permissions for other licenses extend to the entire whole, and thus to each and every part regardless of who wrote it. Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

4. You may copy and distribute the Program (or a work based on it, under Section 3) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

(a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange;

(b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange;

(c) Accompany it with the information at the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Sub-section 3 above.)

The source code for a work means the preferred form of the work for making modifications to it. For an application program, this means source code in a form where it can be edited, like assembly language or source code of a high-level programming language, rather than binary object code or a form that is not intended to be used interactively with the application. The source code need not include anything that is normally distributed in the source code, even though it is technically extractable; for example, an application interface definition file, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed must include any source code that is normally distributed (in either source or binary form) with the program (or object code for the program) as part of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code is considered distributions, even if it is not made available in the same place counts as distribution of the source code, even though the parties are not compelled to copy the source along with the object code.

5. You may not copy, modify, or distribute the Program except as expressly provided by this License. Any attempt otherwise to copy, modify, sublicense or redistribute the Program is void, and automatically terminates your rights under this License. However, parties who have received copies, or rights, from a previous holder are not compelled to copy the source along with that party remains in full compliance.

6. Because the copyright holder provides this License to you, you have no obligation to provide further updates or support to your users, or to pass on any benefits that may result from improvements in the software. You may distribute the Program as you receive it, but you are not obligated to provide any support or warranty to your users.

7. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on their rights.

8. If as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, you may end up distributing the Program as modified versions of it under your own terms, so long as you are not required to oblige those who receive copies of the Program to comply with those conditions.

9. If the distribution of the Program, and your modification of it, causes a conflict with the patent rights of other parties, the original copyright holders and/or their assigns are free to assert such rights against you, and you must not distribute the Program so as to avoid causing such a problem.

10. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version will be given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version of this License, you may choose any version ever published by the Free Software Foundation.

11. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. One decision will be guided by two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

#### NO WARRANTY

12. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

13. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE, OR INABILITY TO USE, THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN THOUGH SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#### END OF TERMS AND CONDITIONS

#### Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and also include them in the output of any program compilation or distribution process. You should also get your employer (if you work for one) to sign a "copyright disclaimer" for the program, if necessary. Here is a sample:

one line to give the program's name and a brief idea of what it does.

Copyright (C) yyyy name of author

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts an interactive mode:

Gnomovision version 69, Copyright (C) yyyy name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.

This is free software, and you are welcome to redistribute it under certain conditions; type 'show c' for details.

The hypothetical commands 'show c' and 'show w' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something else; that's okay, provided they actually mean the same thing.

You should also get your employer (if you work for one) to sign a "copyright disclaimer" for the program, if necessary. Here is a sample:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program 'Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989

Ty Coon, President of VICE

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it legal to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.