

The `asymptote` package

John Bowman, Tom Prince, and Will Robertson

2015/05/10 v1.29

Abstract

This package provides integration of inline and external Asymptote graphics within a \LaTeX document.

Contents

1 Introduction

This is the documentation for the \LaTeX package `asymptote` which accompanies the Asymptote drawing package. For further details on Asymptote, please see its documentation in `asymptote.pdf`.

2 User syntax

2.1 Package loading and options

The package may take two options at load time: `inline` or `attach`. These options can also be set at any time with the `\asysetup{<options>}` command, or specified individually in the optional argument to each `asy` environment or `asyinclude` command.

The `inline` option uses Asymptote's 'inline' mode whereby included graphics have their labels typeset in the environment of the document they are contained within. Otherwise the Asymptote graphics are self-contained and their formatting is independent of the document.

The `attach` option allows generated graphics to be embedded within the PDF using the `attachfile2` package; please load that package separately if you wish to use it. The `attach` option takes precedence over the `inline` option.

This package produces quite a number of output files, which by default are created in the same directory as the \LaTeX document that is being compiled. To keep things more tidy, you can specify an output directory for these files by defining the `\asydir` command. For example, if you wish to store the figure files in the subdirectory `asytmp/`, then you would write `\renewcommand\asydir{asytmp}`.

Alternatively (and tentatively), you may write `dir=asytmp` in either the `asy` environment options or the options to `\asysetup`.

2.2 Commands for inserting Asymptote graphics

The main environment defined by the package is the `asy` environment, in which verbatim Asymptote code is placed that will be compiled for generating a graphic in the document. For example,

```
\begin{figure}
\begin{asy}[ <options> ]
<ASYMPTOTE CODE>
\end{asy}
\caption{...}\label{...}
```

If you have Asymptote code in a separate file, you can include it with the `\asyinclude[<options>]{<filename>}` command.

For Asymptote code that should be included in *every* graphic, define it using the `asydef` environment.

2.3 Graphics options

Both the `asy` environment and the `\asyinclude` command take optional parameters for controlling aspects of the graphics creation. In addition to locally setting `inline` and `attach`, the following options may also be used:

width Width of the figure

height Height of the figure

keepAspect Maintain aspect ratio [default true]

viewportwidth Viewport width for 3D figures

viewportheight Viewport height for 3D figures

These may also be set globally using the `\asysetup` command.

3 Processing the document

After running \LaTeX on the document, it is necessary to process the Asymptote graphics so they can be included in the next compilation. The simplest procedure is a recipe such as

```
pdflatex mydoc
asy mydoc-*.asy
pdflatex mydoc
```

This technique will recompile each graphic every time, however. To only recompile graphics that have changed, use the `latexmk` tool. Asymptote is distributed with a `latexmkrc` configuration file; place this file in a place where `latexmk` will find it and your document may be compiled, including the `asy` compilations, with `latexmk mydoc` or `latexmk --pdf mydoc`.

4 Implementation

```
1 \def\Asymptote{\tt Asymptote}
2 \InputIfFileExists{\jobname.pre}{\}{}{}
```

4.1 Allocations

Allocations

```
3 \newbox\ASYbox
4 \newcounter{asy}
5 \newwrite\AsyStream
6 \newwrite\AsyPreStream
7 \newif\ifASYinline
8 \newif\ifASYattach
9 \newif\ifASYkeepAspect
10 \ASYkeepAspecttrue
```

4.2 Packages

```
11 \RequirePackage{keyval}
12 \RequirePackage{ifthen}
13 \RequirePackage{color,graphicx}
```

Emulating packages We cannot assume that Asymptote users have recent T_EX distributions. (E.g., Fedora until recently still shipped teTeX.) So load ifpdf and ifxetex if they exist; otherwise, emulate them.

In due course, delete this code and just load the packages.

```
14 \IfFileExists{ifpdf.sty}{
15   \RequirePackage{ifpdf}
16 }{
17   \expandafter\newif\csname ifpdf\endcsname
18   \ifx\pdfoutput\@undefined\else
19     \ifcase\pdfoutput\else
20       \pdftrue
21     \fi
22   \fi
23 }

24 \IfFileExists{ifxetex.sty}{
25   \RequirePackage{ifxetex}
26 }{
27   \expandafter\newif\csname ifxetex\endcsname
28   \ifx\XeTeXversion\@undefined\else
29     \xetextrue
30   \fi
31 }
```

`\CatchFileDef` Used for `\asyinclude`. Note that the fallback definition is not as robust as the one provided by `catchfile`.

```

32 \IfFileExists{catchfile.sty}{
33   \RequirePackage{catchfile}
34 }{
35   \newcommand\CatchFileDef[3]{%
36     \begingroup
37     \everyeof{%
38       \ENDCATCHFILEMARKER
39     }
40   }%
41   \long\def\@tempa###1\ENDCATCHFILEMARKER{%
42     \endgroup
43     \def##1{###1}%
44   }%
45   ##3%
46   \expandafter\@tempa\@input ##2\relax
47 }
48 }

```

Ensuring attachfile2 is loaded if [attach] is requested

```

49 \newif\if@asy@attachfile@loaded
50 \AtBeginDocument{%
51   \ifpackageloaded{attachfile2}{\@asy@attachfile@loadedtrue}{}%
52   \let\asy@check@attachfile\asy@check@attachfile@loaded
53 }
54 \newcommand\asy@check@attachfile@loaded{%
55   \if@asy@attachfile@loaded\else
56     \PackageError{asyptote}{You must load the attachfile2 package}{^^J%
57       You have requested the [attach] option for some or all of your^^J%
58       Asymptote graphics, which requires the attachfile2 package.^^J%
59       Please load it in the document preamble.^^J%
60   }%
61   \fi
62 }
63 \newcommand\asy@check@attachfile{%
64   \AtBeginDocument{\asy@check@attachfile@loaded}%
65   \let\asy@check@attachfile\@empty
66 }

```

Macros

```

67 \def\csarg#1#2{\expandafter#1\csname#2\endcsname}

```

4.3 Package options

```

68 \DeclareOption{inline}{%
69   \ASYinlinetrue
70 }
71 \DeclareOption{attach}{%

```

```

72 \asy@check@attachfile
73 \ASYattachtrue
74 }
75 \ProcessOptions*
76 \def\asylatexdir{}
77 \def\asydir{}
78 \def\ASYasydir{}
79 \def\ASYprefix{}

```

4.4 Testing for PDF output

Note this is not quite the same as `\ifpdf`, since we still want PDF output when using XeTeX.

```

80 \newif\ifASYPDF
81 \ifxetex
82   \ASYPDFtrue
83   \usepackage{everypage}
84 \else
85   \ifpdf
86     \ASYPDFtrue
87   \fi
88 \fi
89 \ifASYPDF
90   \def\AsyExtension{pdf}
91 \else
92   \def\AsyExtension{eps}
93 \fi

```

4.5 Bug squashing

```

94 \def\unquoteJobname#1"#2"#3\relax{%
95   \def\rawJobname{#1}%
96   \ifx\rawJobname\empty
97     \def\rawJobname{#2}%
98   \fi
99 }
100 \expandafter\unquoteJobname\jobname""\relax

```

Work around jobname bug in MiKTeX 2.5 and 2.6: Turn stars in file names (resulting from spaces, etc.) into minus signs

```

101 \def\fixstar#1*#2\relax{%
102   \def\argtwo{#2}%
103   \ifx\argtwo\empty
104     \gdef\Jobname{#1}%
105   \else
106     \fixstar#1-#2\relax
107   \fi
108 }
109 \expandafter\fixstar\rawJobname*\relax

```

Work around bug in dvips.def: allow spaces in file names.

```

110 \def\Ginclude@eps#1{%
111   \message{<#1>}%
112   \bgroup
113   \def\@tempa{!}%
114   \dimen@\Gin@req@width
115   \dimen@ii.1bp\relax
116   \divide\dimen@\dimen@ii
117   \@tempdima\Gin@req@height
118   \divide\@tempdima\dimen@ii
119   \special{PSfile=#1\space
120     llx=\Gin@llx\space
121     lly=\Gin@lly\space
122     urx=\Gin@urx\space
123     ury=\Gin@ury\space
124     \ifx\Gin@scalex\@tempa\else rwi=\number\dimen@\space\fi
125     \ifx\Gin@scaley\@tempa\else rhi=\number\@tempdima\space\fi
126     \ifGin@clip clip\fi}%
127   \egroup
128 }

```

4.6 Input/Output

```

129 \immediate\openout\AsyPreStream=\jobname.pre\relax
130 \AtEndDocument{\immediate\closeout\AsyPreStream}

131 \def\WriteAsyLine#1{%
132   \immediate\write\AsyStream{\detokenize{#1}}%
133 }

134 \def\globalASYdefs{}
135 \def\WriteGlobalAsyLine#1{%
136   \expandafter\g@addto@macro
137   \expandafter\globalASYdefs
138   \expandafter{\detokenize{#1^^J}}%
139 }

```

4.7 Commands for verbatim processing environments

```

140 \def\ProcessAsymptote#1{%
141   \begingroup
142   \def\CurrentAsymptote{#1}%
143   \let\do\@makeother \dospecials
144   \@makeother\^^L% and whatever other special cases
145   \catcode'\ =10
146   \endlinechar'\^^M \catcode'\^^M=12 \xAsymptote
147 }

```

Need lots of comment chars here because *(line end)* is no longer a space character.

```

148 \begingroup
149   \catcode'\^^M=12 \endlinechar=-1\relax%
150   \gdef\xAsymptote{%
151     \expandafter\ProcessAsymptoteLine%
152   }

```

```

153 \gdef\ProcessAsymptoteLine#1^~M{%
154   \def\@tempa{#1}%
155   {%
156     \escapechar=-1\relax%
157     \xdef\@tempb{\string\end\string\{\CurrentAsymptote\string\}}%
158   }%
159   \ifx\@tempa\@tempb%
160     \edef\next{\endgroup\noexpand\end{\CurrentAsymptote}}%
161   \else%
162     \ThisAsymptote{#1}%
163     \let\next\ProcessAsymptoteLine%
164   \fi%
165   \next%
166 }
167 \endgroup
168 \def\asy@init{
169   \def\ASYlatexdir{}
170   \ifx\asylatexdir\empty\else
171     \def\ASYlatexdir{\asylatexdir/}%
172   \fi
173   \ifx\asydir\empty\else
174     \def\ASYasydir{\asydir/}%
175   \fi
176   \def\ASYprefix{\ASYlatexdir\ASYasydir}%
177 }

```

4.8 User interface

```

178 \newcommand\asy[1][]{%
179   \stepcounter{asy}%
180   \setkeys{ASYkeys}{#1}%

```

Disable the "inline" option if "attach" is enabled:

```

181   \ifASYattach
182     \ASYinlinefalse
183   \fi
184   \asy@init
185   \immediate\write\AsyPreStream{%
186     \noexpand\InputIfFileExists{%
187       \ASYprefix\noexpand\jobname-\the\c@asy.pre}{-}{-}%
188   }
189   \asy@write@graphic@header
190   \let\ThisAsymptote\WriteAsyLine
191   \ProcessAsymptote{asy}%
192 }
193 \def\endasy{%
194   \asy@finalise@stream
195   \asy@input@graphic
196 }
197 \def\asy@write@graphic@header{%

```

```

218 \immediate\openout\AsyStream=\ASYasydir\jobname-\the\c@asy.asy\relax
219 \gdef\AsyFile{\ASYprefix\Jobname-\the\c@asy}%
220 \immediate\write\AsyStream{%
221     if(!settings.multipleView) settings.batchView=false;^^J%
222     \ifxetex
223         settings.tex="xelatex";^^J%
224     \else\ifASYPDF
225         settings.tex="pdflatex";^^J%
226     \fi\fi
227     \ifASYinline
228         settings.inlinetex=true;^^J%
229         deletepreamble();^^J%
230     \fi
231     defaultfilename="\Jobname-\the\c@asy";^^J%
232     if(settings.render < 0) settings.render=4;^^J%
233     settings.outformat="";^^J%
234     \ifASYattach
235         settings.inlineimage=false;^^J%
236         settings.embed=false;^^J%
237         settings.toolbar=true;^^J%
238     \else
239         settings.inlineimage=true;^^J%
240         settings.embed=true;^^J%
241         settings.toolbar=false;^^J%
242         viewportmargin=(2,2);^^J%
243     \fi
244     \globalASYdefs
245 }%
246 }
247 \def\asy@expand@keepAspect{%
248     \ifASYkeepAspect keepAspect=true%
249     \else keepAspect=false%
250     \fi%
251 }
252 \def\asy@finalise@stream{%
    Setting size(). Only inserted if one of the dimensions is set explicitly (i.e., if
    both height and width are not empty).
253     \ifx\ASYwidth\@empty
254         \ifx\ASYheight\@empty
255             % write nothing!
256         \else
257             \immediate\write\AsyStream{size(0,\ASYheight,\asy@expand@keepAspect);}%
258         \fi
259     \else
260         \ifx\ASYheight\@empty
261             \immediate\write\AsyStream{size(\ASYwidth,0,\asy@expand@keepAspect);}%
262         \else
263             \immediate\write\AsyStream{size(\ASYwidth,\ASYheight,\asy@expand@keepAspect);}%
264         \fi

```



```

245 \fi
    Setting viewportsize=(). Same logic as for size().
246 \ifx\ASYviewportwidth\empty
247 \ifx\ASYviewportheight\empty
248 % write nothing!
249 \else
250 \immediate\write\AsyStream{viewportsize=(0,\ASYviewportheight);}%
251 \fi
252 \else
253 \ifx\ASYviewportheight\empty
254 \immediate\write\AsyStream{viewportsize=(\ASYviewportwidth,0);}%
255 \else
256 \immediate\write\AsyStream{%
257 viewportsize=(\ASYviewportwidth,\ASYviewportheight);}%
258 \fi
259 \fi
260 \immediate\closeout\AsyStream
261 }

262 \def\asy@input@graphic{%
263 \ifASYinline
264 \IfFileExists{"\AsyFile.tex"}{%
265 \catcode'\:=12\relax
266 \@input"\AsyFile.tex"\relax
267 }{%
268 \PackageWarning{asyptote}{file '\AsyFile.tex' not found}%
269 }%
270 \else
271 \IfFileExists{"\AsyFile.\AsyExtension"}{%
272 \ifASYattach
273 \ifASYPDF
274 \IfFileExists{"\AsyFile+0.pdf"}{%
275 \setbox\ASYbox=\hbox{\includegraphics[hiresbb]{"\AsyFile+0.pdf"}}%
276 }{%
277 \setbox\ASYbox=\hbox{\includegraphics[hiresbb]{"\AsyFile".pdf}}%
278 }%
279 \else
280 \setbox\ASYbox=\hbox{\includegraphics[hiresbb]{"\AsyFile.eps"}}%
281 \fi
282 \textattachfile{\AsyFile.\AsyExtension}{\phantom{\copy\ASYbox}}%
283 \vskip-\ht\ASYbox
284 \indent
285 \box\ASYbox
286 \else
287 \ifASYPDF
288 \includegraphics[hiresbb]{"\AsyFile".pdf}%
289 \else
290 \includegraphics[hiresbb]{"\AsyFile.eps"}%
291 \fi
292 \fi

```

```

293 }{%
    3D PRC figures require inline mode.
294 \IfFileExists{"\AsyFile.tex"}{%
295     \catcode': =12
296     \@input"\AsyFile.tex"\relax
297 }{%
298     \PackageWarning{asyptote}{%
299         file '\AsyFile.\AsyExtension' not found%
300     }%
301 }%
302 }%
303 \fi
304 }
305 \def\asydef{%
306     \let\ThisAsymptote\WriteGlobalAsyLine
307     \ProcessAsymptote{asydef}%
308 }
309 \newcommand\asyinclude[2][{}]{%
310     \begingroup
311     \stepcounter{asy}%
312     \setkeys{ASYkeys}{#1}%
313     \ifASYattach
314         \ASYinlinefalse
315     \fi
316     \asy@init
317     \immediate\write\AsyPreStream{%
318         \noexpand\input\IfFileExists{%
319             \ASYprefix\noexpand\jobname-\the\c@asy.pre}{-}{-}%
320     }%
321     \asy@write@graphic@header
322     \IfFileExists{#2.asy}{%
323         \CatchFileDef\@tempa{#2.asy}{%
324             \let\do\@makeother
325             \dospecials
326             \endlinechar=10\relax
327         }%
328     }{%
329         \IfFileExists{#2}{%
330             \CatchFileDef\@tempa{#2}{%
331                 \let\do\@makeother
332                 \dospecials
333                 \endlinechar=10\relax
334             }%
335         }{%
336             \PackageWarning{asyptote}{file #2 not found}%
337             \def\@tempa{}%
338         }%
339     }%
340     \immediate\write\AsyStream{\unexpanded\expandafter{\@tempa}}%

```

```

341 \asy@finalise@stream
342 \asy@input@graphic
343 \endgroup
344 }

345 \newcommand{\ASYanimategraphics}[5][[]]{%
346 \IfFileExists{_#3.pdf}{%
347 \animategraphics[#1][#2]{_#3}{#4}{#5}%
348 }{}%
349 }

```

4.9 Keys for graphics processing

```

350 \newcommand\asysetup[1]{\setkeys{ASYkeys}{#1}}

351 \define@key{ASYkeys}{dir}{%
352 \def\asydir{#1}%
353 }
354 \def\ASYwidth{}
355 \define@key{ASYkeys}{width}{%
356 \edef\ASYwidth{\the\dimexpr#1\relax}%
357 }
358 \def\ASYheight{}
359 \define@key{ASYkeys}{height}{%
360 \edef\ASYheight{\the\dimexpr#1\relax}%
361 }
362 \define@key{ASYkeys}{keepAspect}[true]{%
363 \ifthenelse{\equal{#1}{true}}
364 {\ASYkeepAspecttrue}
365 {\ASYkeepAspectfalse}%
366 }
367 \def\ASYviewportwidth{}
368 \define@key{ASYkeys}{viewportwidth}{%
369 \edef\ASYviewportwidth{\the\dimexpr#1\relax}%
370 }
371 \def\ASYviewportheight{}
372 \define@key{ASYkeys}{viewportheight}{%
373 \edef\ASYviewportheight{\the\dimexpr#1\relax}%
374 }

375 \define@key{ASYkeys}{inline}[true]{%
376 \ifthenelse{\equal{#1}{true}}
377 {\ASYinlinetrue}
378 {\ASYinlinefalse}%
379 }
380 \define@key{ASYkeys}{attach}[true]{%
381 \ifthenelse{\equal{#1}{true}}
382 {\ASYattachtrue}
383 {\ASYattachfalse}%
384 }

```