

TUG

RICHARD KOCH

1. INTRODUCTION

This is the root document for a series of related documents which explain how to construct MacTeX.

This document is provided inside a build tree for MacTeX. Do not rearrange folders in this tree. As MacTeX is constructed, these folders will gradually be filled with bits and pieces of the package, until finally the complete package is inside one of the folders.

The MacTeX install package contains a series of subpackages which install the various pieces of MacTeX. A user can choose which packages to install by clicking the “Custom” button during installation. Each subpackage is built in a folder of the build system, and each such folder contains a subfolder named “TUG” with the documentation needed to build that portion of MacTeX. The subpackages needed for MacTeX are Ghostscript, GUI Applications, and TeX Live.

We build a special version of MacTeX for the DVD. That portion requires Ghostscript, GUI Applications, and TeXDist.

Finally we build two extra packages: BasicTeX, and Ghostscript.

2. BUILDING BINARIES

To create a new TeX Live and MacTeX release, it is first necessary to compile the TeX Live binaries. This step is entirely covered by the material in the *Binary* folder of this Build tree. The resulting binaries aren’t used directly; instead they are forwarded to Karl Berry, who inserts them into TeX Live.

One document in the Binary folder is so important that it is duplicated at the top level of the folder as the file *BuildStatus-2018*. This is a plain text document. The document explains everything needed to obtain the source code and compile it. The end result of that operation will be a folder containing 64 bit Intel binaries. To compile, just copy Terminal commands from the BuildStatus document, paste them into Terminal, and execute.

Date: March 30, 2018.

Asymptote is a special case. Its source is contained in the TeX Live source, but it is built separately. A folder in *Build* called *AsymptoteBuild* contains all material needed to do that. To build, copy this folder to the build platform. Then follow the instructions in the document *AsymptoteBuild-2018* inside the *AsymptoteBuild* folder.

Both the asy binary and the TeX Live binaries should be copied to *Binary/RawCodeFromCompile*. A shell script in the *Binary* directory combines these binaries and create tar.xz files to be sent to Karl Berry.

The documents BuildStatus-2018 and AsymptoteBuild-2018 are plain text files so they can be easily edited. New flags or compile steps may be required in a subsequent year. They should immediately be added to these documents during compiling so there is an accurate record for the future.

In 2018 and the future, we support the versions of macOS still supported with security updates by Apple. In practice, this means the last three systems of macOS. For example, in 2018 we should support El Capitan, Sierra, and High Sierra. Apple will introduce a beta of the next macOS at the June developer conference WWDC, and release it in the fall, and we always make certain that MacTeX supports that. So for most of the year we support four versions of macOS.

However, 2018 turned out to be a special case. At first we compiled binaries on El Capitan. But testing then revealed that these binaries immediately crashed with an “unsupported command” on two different models running El Capitan. One was a portable built in 2007, and the other was an iMac built in 2007. Apple made these two machines obsolete after El Capitan, and neither can run Sierra. This is the first time that TeX Live was built on a given macOS, but failed to run on some machines running that macOS.

To solve this problem, we compiled all 2018 binaries on Yosemite. These binaries ran fine on the 2007 machines which could not run the El Capitan version.

Therefore, in 2018 our binaries support five systems: Yosemite, El Capitan, Sierra, High Sierra, and the new system to be released at WWDC-2018. In 2019, we return to the policy of supporting four systems starting with Sierra.

3. ABOUT APPLE’S PACKAGEMAKER

Before 2012, MacTeX was built using Apple’s original PackageMaker application, version 2. This was replaced in Leopard with a new PackageMaker, version 3, but we continued to use the original version until 2012.

Install packages created by the original PackageMaker were actually folders; the Finder disguised these folders to look like flat files to the user. The packages had extension “.pkg” if they installed a single package, and “.mpkg” if they contained several pieces which the user could selectively install. The “.mpkg” folders contained the individual “.pkg” folders inside an encompassing folder.

Apple introduced a new operating system, Mountain Lion, in late summer of 2012. Install packages for this system must be *signed*. Install packages created by PageMaker 2 cannot be signed, so we had to switch to PackageMaker 3. This software has a “legacy” mode which creates the original packages we had been using, but these legacy packages cannot be signed. Thus it is necessary to switch to version 3 of PackageMaker, and use it to create modern install packages which install on Leopard and higher systems.

MacTeX can be constructed on any system which runs the modern PackageMaker and the separate signing software. This software runs on High Sierra, and in 2018 the install packages were made on that system.

As of February, 2015, PackageMaker is available to Apple Developers in the downloads section of the developer website, under the link “Additional Downloads”, as “Auxiliary Tools for Xcode Late July 2012” with a date of August 7, 2012. This version, 3.0.6, was released on June 15, 2012. We have not bothered in 2018 to check that these links are up to date because we include PackageMaker in the MacTeX build folder.

The link

<http://stackoverflow.com/questions/11487596/making-os-x-installer-packages-like-a-pro-xcode4-developer-id-mountain-lion-re>

leads to suggested alternatives, including an open source packagemaker by Stephane Sudre,

<http://s.sudre.free.fr/Software/Packages/about.html>

Just to be safe, the modern version of PackageMaker is in the MacTeX build folder in a subfolder named PackageMaker-ML. If Apple were to truly deprecate PackageMaker, they would also remove the software to install these packages, and then even the open source program would be useless and we’d have to start over in some other way.

The new PackageMaker creates flat files rather than folders. This has a great advantage: it is no longer necessary to zip these packages before placing them on the internet. Before 2012, users often downloaded with a different browser than Safari, and unzipped with a third party application rather than Apple’s default utility. Unhappily, some third party unzipping applications don’t preserve Unix line feeds, so the resulting packages contain postinstall scripts which won’t run.

Switching to the modern PackageMaker has one additional consequence. With the original PackageMaker, we created a “.pkg” install package for each component: TeXLive, Ghostscript, GUI-Applications, etc. Then these install packages were combined to create the final “.mpkg” MacTeX package. The new PackageMaker requires that we create a “root” folder for each individual package containing the data to be installed, but does not require that we finish the task and create the individual install packages. Consequently, the various individual folders for TeXLive, Ghostscript, etc. support an optional final step to create individual install packages, but this step can be skipped when creating MacTeX.

Creating the install package for the TeX Live piece with the modern PackageMaker is very time consuming, so the step should certainly be avoided for that package. On the other hand, it is useful to create a separate flat package for Ghostscript so it can be tested independently of MacTeX.

4. DETAILS FOR BUILDING THE FULL MACTEX PACKAGE

To show how this works in practice, we'll outline the steps required to build the full MacTeX. The first step is to build the “root” folders in Ghostscript-9.23, TeXLive-2018, and GUI-Applications.

Take Ghostscript-9.23 for example. We compile Ghostscript on Intel-64, once with support for X11 and once without this support. These binaries are in a subfolder of the Ghostscript folder named RawBinaries-2018. After that, a script places these binaries in the package which will be installed on a user's machine.

Next we install Ghostscript on the machine used to build the final install packages. Then we run the script buildPackage.sh in the Ghostscript folder. It copies the installation in `/usr/local` to the root folder in the Ghostscript folder, and adds the above binaries.

Making the TeX-Live root folder is easier. We sent the Mac binaries to Karl Berry at TUG after compiling them, and he inserted them in the TeX Live pretest package. We install the TeX Live pretest using the TeX Live install script. Then we run buildPackage.sh, which copies this installation to the root folder, making a few minor changes. Precise details are in the TeX-Live folder of this build system.

The GUI-Applications root folder is constructed in a slightly different way. We put the pieces of this installation in a subfolder named “apps” in the GUI-Applications folder. . Again we run buildPackage.sh, which copies these pieces into a root folder.

In the end, we have root folders in each of Ghostscript, GUI-Applications, and TeX Live.

Now turn to the MacTeX-2018 folder. It contains two copies of the graphic template used to make MacTeX, called “MacTeXMaker” and “MacTeXMaker.copy”. The reason for the copy will become clear in a moment.

Double click MacTeXMaker to open it in PackageMaker. This template contains five major sections. The first is activated by clicking “Edit Interface” at the top right. PackageMaker then shows the full installation as a user would see it, and allows you to edit the various things seen by this user. Making changes here is only necessary once a year. Indeed, the actual interface just shows the files background.jpg, License.rtf, ReadMe.rtf, and Welcome.rtf, and editing the interface is just a matter of editing these four files.

Four sections remain, the MacTeX-2018 Distribution piece at top left, and the TeXLive-2018, GUI-Applications, and Ghostscript-9.23 pieces at bottom left. These last three pieces correspond to the three choices available for a custom install.

Clicking on any of the four sections reveals settable items at the right. These items need editing only once a year as new packages are created, and the changes required are immediately obvious.

So the sections seen so far only change once a year, and need not be checked during the creation of a new beta of MacTeX. But notice that each of the three sections on bottom left have a “disclosure arrow.” Turning these arrows reveals three additional sections. These three pieces correspond to the three root files which will be used to make MacTeX.

During the beta test period, the contents of these root folders will change. When we converted to the new Packagemaker, some tests convinced us that Packagemaker would become confused by new contents in the root folders, and not actually install changed versions. So the method we have adopted is to always recreate the three pieces of MacTeX which depend on the three root files.

To do this, open both “MacTeXMaker” and “MacTeXMaker copy”. Place them side by side, keeping track of which is not a copy. Open the disclosure arrow on the copy for Ghostscript-9.23. For a very brief moment, a “busy rotor” will appear as Packagemaker reads in the Ghostscript data. It is very important to wait until this rotor is gone, since two rotors running at the same time can crash Packagemaker.

Now open the disclosure arrow on the active MacTeXMaker for Ghostscript-9.23 and wait until its rotor is gone. On this active copy, drag the “local” icon on the left to the trash. The item will vanish, together with its configuration data to the right. Reach into the Ghostscript-9.23 folder, find the “root” subfolder. Drag this “root/usr/local” to the active MacTeXMaker, dropping it on the Ghostscript-9.23 item. This will create a new “local” piece. A rotor will appear as PackageMaker reads the new data. Wait until it disappears.

Next we recreate the configuration data to the right. Use the copy of MacTeXMaker to find the correct data (that’s why it is there). Under the first “Configuration” tab, only the “Install:”, “Destination:”, and “Package Identifier:” items need to be changed. The “Install” item only needs to be changed to show a relative path. Under the “Contents” tab find the button named “Apply Recommendations” and push it. This gives each installed file the permissions recommended by Apple. Under the “Components” tab there will be nothing showing. Finally under the “Scripts” tab, change the “Scripts directory:” and “PostInstall:” entries.

Repeat these tasks for the TeXLive and GUI-Applications pieces. The TeXLive case will work exactly like the Ghostscript case *except* that it takes Packagemaker a long time to read the root data, so the rotor will turn and turn. Have patience.

In the GUI case, there will be entries under the “Components” tab near the very end of the process. These contents will show all of the GUI applications to be installed, with a checked box to indicate that the installer permits relocation. These boxes are very dangerous because they allow MacTeX to search the entire disk and update any copy of the GUI apps it happens to find. So it is very, very important to uncheck the checked entries in this panel. Complete the final “Scripts” tab items as usual.

Finally click the “Build” button at the top of the template and a MacTeX install package will be created. A save dialog allows you to change where it is saved. Be sure to save inside the “MacTeX-2018” folder containing these pieces.

The only remaining problem is that the package isn’t yet signed. Issue the command “sh signPackage.sh” while inside the MacTeX-2018 folder to sign the package. As explained later in the document, this requires that the developer be a registered Apple developer. The short “signPackage” script must be edited slightly to provide credentials for the new developer.

In 2018, something was wrong with my developer signature on High Sierra, so I did the final “signing step” on Sierra.

5. IMPORTANT WARNINGS

This section contains lessons learned in 2013. The material here is important for all packages made with the new PackageMaker.

Folders in which packages are built should live on the hard disk rather than an external disk. Building constructs subfolders named “root” which contain copies of material to be installed. This root folder and its contents are usually owned by root. But material on an external drive is owned by the user instead, so owners will be incorrect after installing.

The final MacTeX template refers to root folders of the various sub-projects. In the template, each sub-project is listed in the left column; clicking on an arrow there reveals a panel in which the root folder is determined and configured.

As explained earlier, we accept Apple’s recommendation for permissions on installed files. For binary files like `texlive/2018/bin/x86_64-darwin`, the recommendations are unexpected. Actual binaries have owner root and group wheel, but symbolic links have owner an individual user and group wheel. Permissions are `-rwxr-xr-x`. Experiments and email conversations show that these choices work well.

For the GUI-package, the third tab, “Components”, is very important. It lists actual apps and offers to relocate them. *Turn this off*. Otherwise the installer won’t upgrade programs in `/Applications/TeX`, but instead will search the disk for a copy to update. Always check that these items are off.

6. MACTEX PRODUCTS

There are four main products: MacTeX, BasicTeX, Ghostscript-9.23, and MacTeX Install Step 2. The first is the main distribution for the web. The second is a much smaller TeX distribution for users with limited download bandwidth; it only contains a TeX distribution, without GUI applications, Ghostscript, etc. The third is Ghostscript alone, for instance for BasicTeX users. The fourth is a variant of the first for the DVD; TeX Live is installed from a copy elsewhere on the DVD, but configured by a piece of this package.

It is useful to create Ghostscript several months before everything else since it does not depend on TeX Live.

7. HOW TO MAKE YEARLY UPDATES IN PACKAGES

There are some universal steps required to update scripts for a new year. I'll describe the steps here, using the Ghostscript package as an example.

Some packages retain the same name from year to year, while other package names change. When the name changes, it typically contains a year or version number; for example, Ghostscript-9.23.pkg. Although it will be obvious that the name changes, the individual package TUG document will confirm this fact.

It is important that some packages get new names for the following reason. When a user installs a Package, their Mac stores a receipt for the package. If a new version of the package is later installed, the installer updates files which changed in the new package, installs additional files from the new package, *and removes files that used to be in the package, but now aren't*. Ghostscript 9.23 installs support files in `/usr/local/share/ghostscript/9.23`, which depend on a version number. If the name of the package didn't change, the old support files would be removed, but we want to preserve them in case the user retreats to the older version. Renaming is particularly important for TeX Live itself, since we certainly don't want the installer to remove the old copy of TeX Live.

To switch to the new name:

- Edit the “buildPackage.sh” script, which may contain references which differ from year to year.
- Edit the files to be shown to the user during installation: `License.rtf`, `ReadMe.rtf`, and `Welcome.rtf`. Edit these files to reflect the new package name and release date. Make other changes as appropriate.

8. MAKING INSTALL PACKAGES USING THE PACKAGEMAKER GUI

Details of using this GUI for individual packages are given in the TUG documentation for these packages. One GUI item to be set for packages is titled “Requirements”. This item can be used to ensure that the operating system is sufficient to support the package.

9. SIGNING PACKAGES

Starting with Mac OS 10.8, Mountain Lion, install packages must be signed. Signing requires a “Signing Certificate” from Apple, which is kept in the developer’s keychain and maintained by the program /Applications/Utilities/Keychain Access. The signature is not kept in this MacTeX Developer package — when install packages are signed, the software looks up the developer’s signature in their keychain.

The PackageMaker GUI interface contains an entry which tells the software the name of the appropriate signature. Tests show that this entry does not work. Ignore this GUI setting.

Instead, packages must be signed after they are constructed using the command line program “productsign”. “Productsign” accepts an input package and outputs a corresponding signed package, so after building, individual portions of this developer package will contain two install packages. The command to run productsign is inside a short script in each folder named “signPackage.”

Obtaining a certificate requires a developer account at <https://developer.apple.com/>. I believe accounts are free, but they might require a fee; full access costs \$100 a year. As soon as you log in, you’ll see an entry “Developer Certificate Utility” with lots of information about certificates.

You will ultimately be given two certificates, one for signing install packages and another for signing applications. For instance, my certificates are called “Developer ID Installer: Richard Koch” and “Developer ID Application: Richard Koch”. The system will reject the “Application” certificate when signing packages, so use the “Installer” certificate.

Obtaining certificates can be tricky. A description of the process, using XCode, can be found in the “developer_id_tutorial.pdf” file included in the “Signing” section of this package. Read the section titled *Obtaining Developer ID Certificates*. This seems to describe the latest process, but you will find other Apple documentation which describes contradictory and more complicated methods. I already had certificates, so my process didn’t exactly follow the scheme in this document. Good luck.

Apple delivers the certificates in just a few minutes, but the exact name of the certificate is important. I spent several days debugging because I neglected the space between “Installer:” and “Richard Koch”. If you are like me, you’ll have *lots* of certificates managed by Keychain Access, some obsolete, and it can be difficult to keep straight the active ones.

Follow the instructions from Apple carefully, since the process isn't quite as straightforward as it first seems.

Testing signed packages is itself tricky. First, the "Security and Privacy" preference pane must be set to allow applications downloaded from "Mac App Store and identified developers" only. After that, if an unsigned package is moved to a current system via wireless or a USB Flash Drive, it will install fine. To test, an install package must be placed on a server and then downloaded with Safari or another browser. Then an incorrectly signed package will refuse to install.