

SticksToo

Michael Sharpe

May 8, 2018

1 In short

SticksToo is a repackaging for \LaTeX of the text part of STIX2 that was released in early May 2018. The style file `stix2.sty` does offer support for text processing at a rather basic level, but does not provide much access to the riches of the STIX2 Text fonts. With SticksToo there are most of the options and macros that are part of the `newtxtext` package, but with Times fonts replaced by `StixTwoText` fonts. As of the initial release of STIX2, the math fonts have some problem which make them unsuited to high quality mathematical typesetting, and so I'm offering an update of `newtxmath` with option `stix2` that makes use of the Roman and Greek letters from STIX2 (the two year old beta version, not the one now available on CTAN) together with math symbols from `newtx`. In my opinion, the STIX2 fonts are a great improvement over Times based fonts—more readable because of the increased x-height, fewer spacing issues with overly sloped Italic shapes, and handsome new Greek glyphs.

The symbols in `newtx` are thinner than those in STIX2—56em versus 66em—and the appearance is therefore somewhat lighter. The math axis with `newtx` is 2 units less than with STIX2, an amount that few would notice. There is no mixing of math symbols from STIX2 and `newtx` where the difference in math axis, however small, might be observable.

2 Options and Macros

`scaled`, `scale`:

Rescales every font in the package. E.g.,

```
\usepackage[scaled=1.15]{stickstootext}
```

scales everything up by 15%.

`proportional` (`p`), `tabular`, `lining`, `osf`:

These affect the figure style used in text. The default is `tabular`, `lining`, which is appropriate for math usage, and will be used in math mode no matter how you set the text figure option. E.g., `p`, `osf` sets the text figure style to `proportional`, `oldstyle`, like 12345.

`scosf`:

This option makes `osf` the default figure style in small cap text.

`theoremfont`:

This option redefines the meaning of `\textsl` and substitutes it for `\textit` in the definition of the

plain theorem style. *This is how the Theorem font looks: it is Italic but has upright punctuation symbols ;,!/? etc. The figures are not changed, but should in many cases be tabular lining figures, accessed using, e.g., `\textttlf`.*

sup:

This makes superior figures to be used in footnote markers except in minipages. This option is prevented when used the KOMA classes, with which it may conflict. The option has no effect if you define a non-default handling of footnote markers in your preamble before loading `stickstootext`.

For other options, run

```
texdoc newtx
```

and look at its discussion of the `newtx` text options.

`\textosf`, `\texttosf`, `\textlf`, `\textttlf`, `\textsu`, `\textin`, `\textnu`, `\textde`: These macros provide ways to use other figures styles, no matter what defaults may have been set. They denote respectively proportional oldstyle, tabular oldstyle, lining, tabular lining, superiors, inferiors, numerators and denominators, which render as follows.

```
\textosf{0123456789} 0123456789
\texttosf{0123456789} 0123456789
\textlf{0123456789} 0123456789
\textttlf{0123456789} 0123456789
\textsu{0123456789abc+--()} 0123456789abc+.=()
\textin{0123456789} 0123456789
\textnu{0123456789} 0123456789
\textde{0123456789} 0123456789
\textsu{1}\textnu{1}; \textin{1}\textde{1}1111 Note the differences in size and baseline
\textfrac{17}{32} 17/32 Constructs fractions using \textnu and \textde.
```

3 Example preamble with math

Caution: If you have an up-to-date distribution (TeXLive or MiKTeX), then there is an important change to note in the AMS classes, making the option `noamsfonts` viable. If you plan to use the `newtxmath` package with an AMS class, be sure to enable this option, as it will save you two of your precious sixteen math families. (The equivalent symbols are already in `newtxmath` at a weight appropriate to Times and STIX2.)

EXAMPLE PREAMBLE:

```
\usepackage[11pt,noamsfonts]{amsart}
\usepackage[p,osf]{stickstootext} % loads Helvetica as SF, newtxtt as TT
% T1 and textcomp are loaded by package. Change that here, if you want
% load replacements for Helvetica and newtxtt here, if desired
\usepackage{amsthm}% must be loaded before newtxmath
% amsmath and amssymb should not be loaded
\usepackage{stix,vvarbb}{newtxmath}
% vvarbb selects the STIX version of blackboard bold. See below.
```

4 Choices for blackboard bold

Unless you specify in the options a choice (one of `varbb`, `vvarbb` for your blackboard bold alphabet, `\mathbb` will use the default blackboard bold alphabet: $\mathbb{A} \dots \mathbb{Z}$ (upper-case only), which I find unappealing because the uneven separations between boundaries makes the gray level likewise uneven. There are two macros which provide access to other alphabets other alphabets: `\varmathbb` gives you $\mathbb{A} \dots \mathbb{Z} \mathbb{I} \mathbb{J}$, and `\vvarmathbb` gives you $\mathbb{A} \dots \mathbb{Z} \mathbb{I} \mathbb{J}$. These work similarly to those in the original `newtxmath`, but have some advantages.

- both have full uppercase and lowercase, plus `\imath` (dotlessi) and `\jmath` (dotlessj);
- both work correctly on strings with more than one token, correctly rendering $\mathbb{A}..z$, `\imath` and `\jmath` and passing through all other control sequences. For example, `\varmathbb{A\imath z\dots\jmath\alpha}` renders as $\mathbb{A}\mathbb{I}z \dots \mathbb{J}\alpha$, the control sequences `\dots` and `\alpha` having passed through to LaTeX for processing. The macro `\vvarmathbb` works similarly and renders as STIX blackboard bold.

Option `varbb` causes `\mathbb` to be let equal to `\varmathbb`, effectively DSSerif, and option `vvarbb`, causes `\mathbb` to be let equal to `\vvarmathbb`, effectively STIX blackboard bold.

5 Some math samples

The following snippets mostly originated with the `TEXBook` and were adapted for `LATEX` from Karl Berry's torture test for plain tex math fonts.

$$x + y - z, \quad x + y * z, \quad z * y / z, \quad (x + y)(x - y) = x^2 - y^2,$$

$$x \times y \cdot z = [x y z], \quad x \circ y \bullet z, \quad x \cup y \cap z, \quad x \sqcup y \sqcap z,$$

$$x \vee y \wedge z, \quad x \pm y \mp z, \quad x = y / z, \quad x := y, \quad x \leq y \neq z, \quad x \sim y \simeq z \equiv y \neq z, \quad x \subset y \subseteq z$$

$$\sin 2\theta = 2 \sin \theta \cos \theta, \quad O(n \log n \log n), \quad \Pr(X > x) = \exp(-x/\mu),$$

$$(x \in A(n) \mid x \in B(n)), \quad \bigcup_n X_n \parallel \bigcap_n Y_n$$

In text matrices $\begin{pmatrix} 1 & 1 \\ 0 & 1 \end{pmatrix}$ and $\begin{pmatrix} a & b & c \\ 1 & m & n \end{pmatrix}$

$$a_0 + \frac{1}{a_1 + \frac{1}{a_2 + \frac{1}{a_3 + \frac{1}{a_4}}}}$$

$$\binom{p}{2} x^2 y^{p-2} - \frac{1}{1-x} \frac{1}{1-x^2} = \frac{a+1}{b} \Big/ \frac{c+1}{d}.$$

$$\sqrt{1 + \sqrt{1 + \sqrt{1 + \sqrt{1 + \sqrt{1 + x}}}}}$$

$$\left(\frac{\partial^2}{\partial x^2}+\frac{\partial^2}{\partial y^2}\right)|\phi(x+iy)|^2=0$$

$$\pi(n)=\sum_{m=2}^n\left[\left(\sum_{k=1}^{m-1}\lfloor (m/k)/\lceil m/k\rceil\rfloor\right)^{-1}\right].$$

$$\int_0^\infty \frac{t-ib}{t^2+b^2}e^{iat}\,dt=e^{ab}E_1(ab),\quad a,b>0.$$

$$\mathbf{A}:=\begin{pmatrix}x-\lambda & 1 & 0 \\ 0 & x-\lambda & 1 \\ 0 & 0 & x-\lambda\end{pmatrix}.$$

$$\begin{pmatrix}a & b & c \\ d & e & f\end{pmatrix}\begin{pmatrix}u & x \\ v & y \\ w & z\end{pmatrix}$$

$$\mathbf{A}=\begin{pmatrix}a_{11} & a_{12} & \ldots & a_{1n} \\ a_{21} & a_{22} & \ldots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{m1} & a_{m2} & \ldots & a_{mn}\end{pmatrix}$$

$$\mathbf{M} = I \begin{array}{c} C \\ C \\ C' \end{array} \begin{pmatrix} 1 & 0 & 0 \\ b & 1-b & 0 \\ 0 & a & 1-a \end{pmatrix} \begin{array}{c} C' \\ \\ \end{array}$$

$$\sum_{n=0}^\infty a_n z^n \qquad \text{converges if} \qquad |z| < \Big(\limsup_{n\rightarrow\infty} \sqrt[n]{|a_n|}\Big)^{-1}.$$

$$\frac{f(x+\Delta x)-f(x)}{\Delta x}\rightarrow f'(x) \qquad \text{as } \Delta x\rightarrow 0.$$

$$\|u_i\|=1, \qquad u_i\cdot u_j=0 \quad \text{if } i\neq j.$$

$$\text{The confluent image of } \left\{ \begin{array}{l} \text{an arc} \\ \text{a circle} \\ \text{a fan} \end{array} \right\} \text{ is } \left\{ \begin{array}{l} \text{an arc} \\ \text{an arc or a circle} \\ \text{a fan or an arc} \end{array} \right\}.$$

$$\begin{aligned} T(n) &\leq T(2^{\lceil \lg n \rceil}) \leq c(3^{\lceil \lg n \rceil} - 2^{\lceil \lg n \rceil}) \\ &< 3c \cdot 3^{\lg n} \\ &= 3c\, n^{\lg 3}. \end{aligned}$$

$$\begin{aligned}
(x+y)(x-y) &= x^2 - xy + yx - y^2 \\
&= x^2 - y^2 \\
(x+y)^2 &= x^2 + 2xy + y^2.
\end{aligned}$$

$$\begin{aligned}
\left(\int_{-\infty}^{\infty} e^{-x^2} dx\right)^2 &= \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} e^{-(x^2+y^2)} dx dy \\
&= \int_0^{2\pi} \int_0^{\infty} e^{-r^2} dr d\theta \\
&= \int_0^{2\pi} \left(e^{-\frac{r^2}{2}} \Big|_{r=0}^{r=\infty} \right) d\theta \\
&= \pi.
\end{aligned}$$

$$\prod_{k \geq 0} \frac{1}{(1 - q^k z)} = \sum_{n \geq 0} z^n \Big/ \prod_{1 \leq k \leq n} (1 - q^k).$$

$$\sum_{\substack{0 < i \leq m \\ 0 < j \leq n}} p(i,j) \neq \sum_{i=1}^p \sum_{j=1}^q \sum_{k=1}^r a_{ij} b_{jk} c_{ki} \neq \sum_{\substack{1 \leq i \leq p \\ 1 \leq j \leq q \\ 1 \leq k \leq r}} a_{ij} b_{jk} c_{ki}$$

$$\max_{1 \leq n \leq m} \log_2 P_n \quad \text{and} \quad \lim_{x \rightarrow 0} \frac{\sin x}{x} = 1$$

$$p_1(n)=\lim_{m\rightarrow\infty}\sum_{\nu=0}^\infty(1-\cos^{2m}(\nu!^n\pi/n))$$

6 Caution

This work should be considered experimental, being based essentially on a beta version of STIX2. This package may change substantially as that family changes. Moreover, some features of this package and newtxmath with stix2 option may change in a way that is incompatible with previous versions. It is also possible that it will not follow the evolution of STIX2.