

The Russian Language in the `babel` system

Version 1.3g

Igor A. Kotelnikov*

Released 2015/05/01

Contents

1	The Russian Language Definition File	2
2	Usage	2
2.1	<code>ETEX</code>	3
2.2	<code>LuaETEX</code>	3
2.3	<code>XeTEX</code>	4
2.4	Modern and Ancient spelling	4
3	User's commands	5
3.1	Active character	6
3.2	Math commands	7
4	TeXnical details	7
5	Known problems	7
6	History	8
7	Implementation	9
7.1	Initial setup	9
7.2	Output encoding	10
7.3	Input encoding	13
7.4	Shorthands	14
7.4.1	Quotes	14
7.4.2	Emdash, endash and hyphenation sign	15
7.5	Switching to and from Russian	16
7.5.1	Caption names	16
7.5.2	Date in Russian	22
7.5.3	Hyphenation patterns	23
7.5.4	Extra definitions	23
7.6	Alphabetic counters	24
7.7	Cyrillic math	26
7.8	Final settings	27

*E-mail: `kia999 at mail dot ru`.

1 The Russian Language Definition File

The file `russianb.1df`¹ is the source file for the Russian Language Definition file `russianb.1df` to be loaded by the `babel` package with the option `russian`. It was derived by Igor A. Kotelnikov from the original version of `russianb.1df`, first released by Olga Lapko and Johannes Braams and then adapted to the T2* and X2 Cyrillic encodings by Vladimir Volovich and Werner Lemberg.

Starting the version 1.2, `russianb.1df` is designed to work both with legacy non-unicode (8-bit) and new unicode encodings of the source document files (input encodings) and of the font files (font encodings). This is achieved by excluding (bypassing) the `\cyr...` macros, which map every letter in a source file with given input encoding to a corresponding code point in a font file with a given font encoding when running modern engines, such as `LuaLATEX` or `XeLATEX`, in native unicode mode instead of legacy engines, such as `LATEX` or `PDFLATEX`, or unicode engines in a compatibility (8-bit) mode. A few obsolete and controversial macros has been eliminated in first public release of version 1.2 of `russianb.1df`.

The version 1.3 of `russianb.1df` has been adapted to new features introduced in the version 3.9 of the `babel` package. In particular, the language attribute `ancient` has been introduced to support typesetting ancient and Church Slavonic books.

2 Usage

Typesetting Russian texts implies that a special input and output encodings should be used. Input encodings are those which are used in source (`.tex`) file. Output encoding is also known as the font encoding. It is implemented within the font files.

Generally, the user may choose between different available Cyrillic encodings. The current support for Cyrillic uses LH family of MetaFont fonts and theirs Postscript versions such as CM-super. `LuaLATEX` and `XeLATEX`, being the Unicode-based successors of `LATEX`, allow also for any Open Type (OTF) and True Type (TTF) fonts which has Cyrillic script, e.g. Computer Modern Unicode, Linux Libertine, and many other system fonts that came with Linux, Mac and Windows operating systems.

With the advent of Unicode, `LATEX` community are moving towards eliminating all existing encodings in favor of Unicode, but nowadays one should take care when switching from `LATEX` to `LuaLATEX` or `XeLATEX` since different packages should be loaded for those compilers.

Since earlier versions `babel` did not support `XeLATEX` (at least for some languages including Russian), the `polyglossia` package was generally recommended in the past for use with `XeLATEX` as a replacement for `babel`. Nowadays, `babel` can be used with any engines, including `LATEX`, `PDFLATEX`, `LuaLATEX`, and `XeLATEX`. Nevertheless some troubles may occur with some languages which have no promptly updated `.1df` files.

¹The file described in this document has the version number 1.3g and was last revised on 2015/05/01.

2.1 L^AT_EX

When user's document is compiled with `latex.exe` or `pdflatex.exe`, recommended set of packages includes the `inputenc` and `fontenc` packages. They should be loaded before `babel`, for example,

```
\usepackage[T1,T2A]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[english,russian]{babel}
```

Some variations in the order of loading the packages are allowed in this case but it is better to follow one and the same convention at all circumstances: the `babel` package should go last, and `fontenc` must be the first.

Input encoding should be declared as option to the `inputenc` package. Known Cyrillic encodings include `cp866` (MS DOS), `cp1251` (Windows), `koi8-u` (UNIX) and their variants. Nowadays, this list is appended with `utf8` input encoding.

Output encodings (also known as font encodings) are declared as options to the `fontenc` package. Known Cyrillic encodings are `T2A`, `T2B`, `T2C`, `LCY`, and `X2`; `LWN` is excluded from Russian support stating version 1.2 of `russianb.1df` since `LWN` is excluded from the `cyrillic` bundle of related files.

2.2 LuaL^AT_EX

If Unicode fonts are not available, LuaL^AT_EX can run in compatibility (8-bit) mode to use same font as L^AT_EX does. However the package `inputenc` does not work with LuaL^AT_EX and should be substituted with `luainputenc`. Source file is to be converted to UTF8 (Unicode-8) encoding; it is the only input encoding accepted by LuaL^AT_EX. The 8-bit mode is invoked by the following sequence of packages:

```
\usepackage[T1,T2A]{fontenc}
\usepackage[utf8]{luainputenc}
\usepackage[english,russian]{babel}
```

The order of the packages is crucial for LuaL^AT_EX in 8-bit mode. Since both `luainputenc` and `babel` should know what is a selected font encoding, the `fontenc` package should be loaded first. Input encoding management for LuaT_EX is needed only for compatibility with old documents. For new documents, using UTF-8 encoding and Unicode fonts is strongly recommended. You've been warned! See tex.stackexchange.com/questions/31709/can-one-instruct-lualatex-to-use-t2a-encoded-fonts.

To invoke Unicode mode, one needs to load the `fontspec` package instead of `luainputenc` and `fontspec` and explicitly indicate which True Type or Open Type fonts should be used for romanic, sans-serif and monospaced types. The following example shows how to load Computer Modern Unicode (CMU) fonts, which is a part of all modern L^AT_EX distributions:

```
\usepackage{fontspec}
\defaultfontfeatures{Renderer=Basic,Ligatures={TeX}}
\setmainfont{CMU Serif}
\setsansfont{CMU Sans Serif}
\setmonofont{CMU Typewriter Text}
\usepackage[english,russian]{babel}
```

The `\defaultfontfeatures` declares default font features for subsequent `\setmainfont` (which sets romanic fonts), `\setsansfont` (sans-serif) and `\setmonofont` (monospaced font). Font features can be set up on per font bases; for example

```
\usepackage{fontspec}
\setmainfont[Renderer=Basic,Ligatures={TeX}]{CMU Serif}
\setsansfont[Renderer=Basic,Ligatures={TeX,Historic}]{CMU Sans Serif}
\setmonofont{CMU Typewriter Text}
\usepackage[english,russian]{babel}
```

Here `Renderer=Basic,Ligatures={TeX}` activates ligatures which are existed in L^AT_EX.

Recall that the language enlisted last in the list of options of the `babel` package is assumed to be the main language of the document, which is also active language right after `\begin{document}`. As of version 3.9, the main language can be set as a value of the `main` option as follows

```
\usepackage{fontspec}
\usepackage[english,main=russian,german]{babel}
```

2.3 XeL^AT_EX

In XeL^AT_EX, there is also a special mode for 8-bit compatibility. One can use `\XeTeXinputencoding` to change the input encoding temporarily, and the "bytes" encoding makes XeL^AT_EX works like a 8-bit L^AT_EX engine:

```
\XeTeXinputencoding "bytes"
\usepackage[utf8]{inputenc}
\usepackage[T2A]{fontenc}
\usepackage[english,russian]{babel}
```

XeL^AT_EX can use a different input encoding but it always uses the Unicode internally, so that `\XeTeXinputencoding` performs a conversion of the input into Unicode; see tex.stackexchange.com/questions/36188/do-xetex-and-luatex-always-use-unicode.

Unicode mode is set up same way as for LuaL^AT_EX, however the option `Renderer=Basic` can be dropped:

```
\usepackage{fontspec}
\defaultfontfeatures{Ligatures={TeX}}
\setmainfont{CMU Serif}
\setsansfont{CMU Sans Serif}
\setmonofont{CMU Typewriter Text}
\usepackage[english,russian]{babel}
```

2.4 Modern and Ancient spelling

By default, a modern spelling is enabled. For Church Slavonic and other old books ancient spelling can be enabled by setting the attribute to `ancient`. To set an attribute, put the `\languageattribute` macro within a document preamble after `babel`, for example,

```
\usepackage[english,russian]{babel}
\languageattribute{russian}{ancient}
```

Setting the `ancient` attribute changes the built-in strings (caption names) and a date format. For example, the bibliography will be entitled as ‘Литература’ by default and as ‘Бібліографія’ if the Russian language attribute is set to `ancient`. Same result can be achieved using a modifier as follows:

```
\usepackage[english,russian.ancient]{babel}
```

Using a modifier in a package option is often better. A modifier is set after the language name, and is prefixed with a dot (only when the language is set as package option – neither global options nor the main key accept them).

3 User’s commands

In a multilingual document, some typographic rules are language dependent and should apply to the whole document.

Regarding local typography, the macro `\selectlanguage{russian}` switches to the Russian language, with the following effects:

1. Russian hyphenation patterns are made active;
2. `\today` prints the date in Russian;
3. the caption names are translated into Russian (\LaTeX only);
4. emdash typed by the ligature `---` might be 20% shorter when Russian is the current language; the result depends on the current encoding; `---` always produce long emdash in \LaTeX and \XeTeX since these engines use same encodings for all languages;
5. emdash typed by the ligature `”---` in Russian is 20% shorter, however the ligature `”---` might not be defined in other languages; a shorter emdash (i.e. `\cyrdash`) can be typeset in any language using special macros enlisted in table 1.

By default, a modern spelling is used for built-in strings (caption names) and the date. The spelling can be reverted to ancient by setting the language attribute to `ancient` in the document preamble as discussed in Sec. 2.4.

Since Russian has its own numbering system, `russianb.1df` adds macros `\asbuk{<counter>}` and `\Asbuk{<counter>}` for formatting numbers appropriately the alphabetic sequence in the Russian alphabet. Additional commands are provided to typeset quotes:

1. French quotation marks can be entered using the commands `\guillemotleft` and `\guillemotright` which work in $\text{\LaTeX}_2\epsilon$ and \PlainTeX .
2. German quotation marks can be entered using the commands `\glqq` and `\grqq` which work in $\text{\LaTeX}_2\epsilon$ and \PlainTeX .

The macro `\Russian` is now defined as an alias for `\selectlanguage{russian}`, and its “opponent” `\English`, existed in `russianb.1df` prior to version 1.2 has been removed since the Russian language definition file is wrong place for definition of macros which switch to a distinct other language.

The macro `\textcyrillic{<text>}` is intended to typeset small chunks of text in Russian; it is essentially an alias for `\foreignlanguage{russian}{<text>}`.

3.1 Active character

Table 1 shows macros and active string which can be used to typeset various dashes and quotes. In the Russian language, the character ” is made active. It can be considered as second escape character in addition to \. Some dashes and all quotes can be typed using both active character ” and ordinary macros as indicated in the table. However, some shorthanded hyphenations have no macro counterpart.

Table 1: Extra definitions made by `russianb.ldf`

<code>\glqq</code>	”“	German left double quotes (looks like „).
<code>\grqq</code>	”“	German right double quotes (looks like “).
<code>\guillemotleft</code>	”<	French left double quotes (looks like <<).
<code>\guillemotright</code>	”>	French right double quotes (looks like >>).
<code>\dq</code>	”	Original quotes character (’).
<code>\babelhyphen{soft}</code>	”-	Optional (soft) hyphen sign, similar to \- but allows hyphenation in the rest of the word; equivalent to <code>\babelhyphen{soft}</code> in <code>babel</code> 3.9.
<code>\babelhyphen{empty}</code>	””	Similar to ”- but does not print hyphen; equivalent to <code>\babelhyphen{empty}</code> in <code>babel</code> 3.9.
<code>\babelhyphen*{nobreak}</code>	”~	A compound word mark without a breakpoint, prints hyphen prohibiting hyphenation at the point; equivalent to <code>\babelhyphen*{nobreak}</code> in <code>babel</code> 3.9.
<code>\babelhyphen{hard}</code>	”=	A compound word mark with a breakpoint, prints hyphen allowing hyphenation in the composing words. equivalent to <code>\babelhyphen{hard}</code> in <code>babel</code> 3.9.
<code>\babelhyphen{nobreak}</code>	”	Disables ligature at this position; equivalent to <code>\babelhyphen{nobreak}</code> (??) in <code>babel</code> 3.9.
<code>\cyrdash</code>	---	Row Cyrillic emdash (does not care spaces around).
<code>\cdash---</code>	”---	Cyrillic emdash in plain text.
<code>\cdash--~</code>	”--~	Cyrillic emdash in compound names (as in Mendeleev--~Klapoiron).
<code>\cdash--*</code>	”--*	Cyrillic emdash in direct speech.
	”,	Thin space (allows further hyphenation as in D.,,Mendeleev).

Note that the standard soft hyphen \- is equivalent to `\babelhyphen*{soft}`.

The quotation marks traditionally used in Russian were borrowed from other languages (e.g., French and German) so they keep their original names.

The French quotes are also available as ligatures ‘<<’ and ‘>>’ in 8-bit Cyrillic font encodings (LCY, X2, T2*) and in unicode encodings (EU1 and EU2) and as ‘<’ and ‘>’ characters in 7-bit Cyrillic font encodings (OT2 and LWN).

In Unicode encodings EU1 and EU2 cyrdashes and quotes can be typed as single character if text editor makes it possible to insert characters which absent of

standard keyboard. This method works as well for 8-bit fonts encoded according to T2A if source file is encoded with cp1251 or utf8.

By default, active double quote is switched on. It can be switched off any time using `\shorthandon{”}` and the switched on again using `\shorthandon{”}`. The aliases `\mdqoff` and `\mdqon` for these two macros has been removed from `russianb.1df` starting from version 1.3 in favour of the macros `\shorthandon` and `\shorthandoff` provided in the `babel` core.

3.2 Math commands

`russianb.1df` defines few macros than can be used independently of current language. These are 9 macros to be used in math mode to type the names of trigonometric functions common for Russian documents: `\sh`, `\ch`, `\tg`, `\ctg`, `\arctg`, `\arcctg`, `\th`, `\cth`, and `\cosec`. Cyrillic letters in math mode can be typed with the aid of text commands such as `\textbf`, `\textsf`, `\textit`, `\texttt`, e.t.c.

The macros `\Prob`, `\Variance`, `\NOD`, `\nod`, `\NOK`, `\nok`, `\Proj` print some rare Russian mathematical symbols.

4 TEXnical details

The packages `inputenc` and `luainputenc` make Cyrillic letters active so that a compiler converts them into corresponding `\cyr...` macro at compilation time. For example, Russian letter ‘a’ matches macro `\cyra`, and capital Russian letter ‘A’ matches `\CYRA`. The package `fontenc` then matches every macro `\cyr...` to corresponding glyph in a font file depending on a declared font encoding.

Nowadays, Unicode makes `\cyr...` macros outdated since both source file and font file are encoded consistently. These macros should therefore be removed because mixing them with unicode characters breaks sorting mechanism of such utilities as `bibtex` and `makeindex`. For the sake of backward compatibility, `\cyr...` are still kept for LTEX, but they are bypassed if `LuaLTEX` or `XeLTEX` are detected.

Some inconsistencies of prior versions of `russianb.1df` was also overcame in the version 1.2. Those users who used `\selectlanguage` macro, defined in the core `babel` system, to switch between different languages should not worry. However, the macros `\Russian`, `\Englsih` and their aliases `\Rus`, `\cyr`, `\Eng` are modified or removed as they did not conform the mechanism of language switching encoded into the core of `babel` and therefore can mess it.

5 Known problems

Before switching from a legacy 8-bit engine (`tex`, `pdftex`) to an Unicode engine (`xetex`, `luatex`) and vise versa delete all `.aux`, `.toc`, `.lot`, `.lof` files as they might have stored incompatible internal encodings.

T2* font encodings do not have old Slavonic letter ‘yat’ (Ђ, Ѓ), which is hard-coded in ancient caption names. Be sure to use an Unicode engine or borrow `\cyryat` and `\CYRYAT` commands from X2 font encoding when setting the language attribute to “ancient”, for example:

```
\usepackage[X2,T2A]{fontenc}
\usepackage[utf8]{inputenc}
```

```
\DeclareUnicodeCharacter{0462}{\CYRYAT}
\DeclareTextSymbolDefault{\CYRYAT}{X2}
\DeclareUnicodeCharacter{0463}{\cyryat}
\DeclareTextSymbolDefault{\cyryat}{X2}
\usepackage[english,russian.ancient]{babel}
```

None of Cyrillic font encoding has ‘iotated E’ (ІЄ, іє). When running legacy engines you are advised to substitute it with \CYRIE, \cyrie (Є, є):

```
\DeclareUnicodeCharacter{0464}{\CYRIE}
\DeclareUnicodeCharacter{0465}{\cyrie}
```

6 History

Changes in version 1.3g

- Added support for `revtex4` and `revtex4-1` classes.

Changes in version 1.3f

- A documentation file `russianb.pdf` can now be generated by running `pdflatex.exe` over `russianb.dtx` although `xelatex.exe` is still recommended.
- `russianb.ins` was missed in version 1.3e.

Changes in version 1.3e

- All stuff is now generated from single `dtx` file.

Changes in version 1.3d

- Bug fix in `\Proj`.

Changes in version 1.3c

- Bug fix in `\daterussian`.

Changes in version 1.3b

- Added support for the packages `listing`, `nomencl`, and `omentbl`.

Changes in version 1.3a

- Added the Russian language attribute `ancient` for typesetting ancient slavonic books.

Changes in version 1.3

- Updated for `babel 3.9`.
- The `\alph` and `\Alph` commands are not redefined any more by the `russianb.ldf`.

Changes in version 1.2a

- Indentation of the first paragraph after sectioning command has been removed. Use `indentfirst` to make first paragraph indented.

Changes in version 1.2

- Font encoding LWN is not supported any more.
- Macros `\Rus`, `\English`, `\Eng` have been removed. `\Russian` is now alias of `\selectlanguage{russian}`. Former definition of `\Russian` is preserved in the macros `\cyrillictext` and `\cyr` which should not be used at user level.
- Lua^LT_EX and Xe^LT_EX are now supported; `\cyr...` commands are bypassed if Lua^LT_EX or Xe^LT_EX run.
- The shorthands ”<” and ”>” are redefined; now they match `\guillemotleft` and `\guillemotright`, respectively, rather than `\fllqq` and `\frqq`.
- Definitions of `\latinencoding` and `\latintext` are removed since these macros are defined in `babel.def`.
- `\cyrmathbf`, `\cyrmathsf`, `\cyrmathit`, and `\cyrmathtt` commands are removed; they do work in math mode; instead of them it is advised to use corresponding `\text...` command.
- The macro `\No` is removed since the Cyrillic number sign is available on keyboard and can also be typed using the `\textnumero` macro.
- Added translation for Glossary.

7 Implementation

7.1 Initial setup

The macro `\LdfInit` performs a couple of standard checks that must be made at the beginning of a language definition file, such as checking the category code of the @-sign, preventing the `.ldf` file from being processed twice, etc.

```
1 \LdfInit{russian}{captionsrussian}
```

First, we check if Lua^LT_EX or Xe^LT_EX is running. If so, we set boolean key `\if@uni@ode` to true. It will be used to eliminate `\cyr...` commands, which were introduced in L^AT_EX2e to handle various Cyrillic input encoding. With the advent of unicode L^AT_EX is moving to universal input encoding, so we consider these `\cyr...` commands as obsolete. They are preserved though for backward compatibility in case if L^AT_EX or PDFL^AT_EX are running.

We don't load the `ifluatex` or `ifxetex` package because `\RequirePackage` is not allowed at the stage of processing options (note that `babel` loads this file right when it processes its own options) but we borrow code from these packages.

```
2 \ifdef{\if@uni@ode}
3   \PackageError{babel}{if@uni@ode already defined.}\MessageBreak
4   Please contact author of russianb.ldf}
5   \relax
```

```

6 \fi
7 \newif\if@uni@ode
8 \ifdefined\luatexversion \@uni@odetrue \else
9 \ifdefined\XeTeXrevision \@uni@odetrue \fi\fi

```

Check if hyphenation patterns for the Russian language have been loaded in `language.dat`. Namely, we check for the existence of `\l@russian`. If it is not defined, we declare Russian as dialect for the default language number 0 which almost for sure is English.

```

10 \ifx\l@russian\@undefined
11   \nopatterns{Russian}
12   \adddialect\l@russian0
13 \fi

```

Now `\l@russian` is always defined.

7.2 Output encoding

We need to know font encoding that is supposed to be active at the end of the `babel` package. Default font encoding, set by `LATEX` core, is `OT1`. This can be changed by the `fontenc` package in case of `LATEX` and by `fontspec` package in case of `LuATEX`. It matters whether these packages are loaded before or after `babel`. In the latter case or if these packages are not loaded at all, `russianb.1df` ignores their effect and tries to provide some reasonable settings. In particular, `T2A` will be selected for Russian language if `LATEX` is running but `EU1` in case of `XeLATEX` and `EU2` in case of `LuATEX`.

- `\latinencoding` The macro `\latinencoding` keeps the name of Latin encoding. It is defined in `babel.def` and is wrapped into `\AtBeginDocument` to allow for late loading `fontenc`. Therefore it does not matter whether `babel` is loaded before or after the `fontenc`. As of version 1.2, definition of `\latinencoding` was removed from `russianb.1df` since it is overruled in `babel.def`. For example, after

```

\usepackage[T1,T2A]{fontenc}
\usepackage[english,russian]{babel}

```

as well as after

```

\usepackage[english,russian]{babel}
\usepackage[T1,T2A]{fontenc}

```

`\latinencoding` will be set to `T1`. After

```

\usepackage[english,russian]{babel}

```

`\latinencoding` will be `OT1`.

In Unicode mode, the package `fontspec` should be loaded instead of `fontenc` to make font preparation; `fontspec` loads the package `xunicode` which sets current encoding (kept in `\cf@encoding`) to `EU1` for `XeLATEX` and `EU2` for `LuATEX`, and the `babel` package sets the macro `\latinencoding` to `\cf@encoding`. Since `babel` scans for value `\cf@encoding` within `\AtBeginDocument`, `\latinencoding` will be set to either `EU1` for `XeLATEX` or `EU2` for `LuATEX` no matter which of the packages, `babel` or `fontspec` is loaded first.

\cyrilllicencoding There is a limited list of encodings appropriate for Cyrillic text. We will look which of them is declared and keep its name in the macro `\cyrilllicencoding`. Correct (but obsolete and now deleted) 7-bit Cyrillic encoding is LWN. Correct 8-bit Cyrillic encodings are T2A (default for 8-bit compilers), T2B, T2C, LCY and X2. Correct utf8 encodings are EU1 (default for Xe^LT_EX), EU2 (default for Lua^LT_EX).

In 8-bit (L^AT_EX) mode, user may choose between different non-unicode Cyrillic encodings—e.g., X2 or LCY. If user wants to use another font encoding rather than default (T2A), he has to load the corresponding file before `babel.sty`.

Remember that for the Russian language, the T2A encoding is better than X2, because X2 does not contain Latin letters, and users should be very careful to switch the language every time they want to typeset a Latin word inside a Russian phrase or vice versa.

We parse the `\cdp@list` containing encodings known to L^AT_EX in the order they were loaded by the time when `babel` is loaded. We set the `\cyrilllicencoding` to the last loaded encoding in the list of supported Cyrillic encodings: OT2, LCY, X2, T2C, T2B, T2A. In Unicode mode we also try the unicode encodings EU1 and EU2; 8-bit encodings are kept for unicode compilers (Lua^LT_EX and Xe^LT_EX) since they can run in compatibility (8-bit) mode.

```

14 \def\@setcyrilllicencoding{%
15   \def\sce@a##1##2{%
16     \edef\sce@b{##1}%
17     \edef\sce@c{##2}%
18     \ifx\sce@b\sce@c
19       \let\cyrilllicencoding\sce@c
20     \fi}%
21   \def\cdp@elt##1##2##3##4{%
22     \sce@a{##1}{OT2}%
23     \sce@a{##1}{LCY}%
24     \sce@a{##1}{X2}%
25     \sce@a{##1}{T2C}%
26     \sce@a{##1}{T2B}%
27     \sce@a{##1}{T2A}%
28     \if@uni@ode
29       \sce@a{##1}{EU1}%
30       \sce@a{##1}{EU2}%
31     \fi}%
32   \cdp@list
33 }
34 \@setcyrilllicencoding
35 \@onlypreamble\@setcyrilllicencoding
36 \@onlypreamble\sce@a
37 \@onlypreamble\sce@b
38 \@onlypreamble\sce@c

```

The last lines are to free the memory occupied by the macros `\@setcyrilllicencoding` and `\sce@x` that are useless in the document. The contents of `\@begindocumenthook` is cleared automatically.

If `\cyrilllicencoding` is still undefined, we issue warning and provide reasonable default value for `\cyrilllicencoding`. We then load default encoding definitions; we use the lowercase names (i.e., `lcyclenc.def` instead of `LCYenc.def`) when we do that.

```
39 \ifdefined\cyrilllicencoding
```

```

40 \else
41   \if@uni@code
42     \ifdefined\XeTeXrevision
43       \edef\cyrillicencoding{EU1}
44     \else\ifdefined\luatexversion
45       \edef\cyrillicencoding{EU2}
46     \fi\fi
47   \else
48     \edef\cyrillicencoding{T2A}
49   \fi
50 \PackageWarning{babel}%
51   {No Cyrillic font encoding has been loaded so far.\MessageBreak
52     A font encoding should be declared before babel.\MessageBreak
53     Default ‘\cyrillicencoding’ encoding will be loaded
54   }%
55 \lowercase\expandafter{\expandafter\input\cyrillicencoding enc.def\relax}%

```

As final wisdom, we repeat `\@setcyrillicencoding` at `\begin{document}` time. We could not avoid previous call to `\@setcyrillicencoding` since compiler scan `.aux` file before it executes delayed code, and `.aux` may contain `\set@language{russian}`; the latter rises an error if `\cyrillicencoding` would not be defined by that time.

```

56 \AtBeginDocument{\@setcyrillicencoding}
57 \fi

```

\Russian For the sake of backward compatibility we keep the macro `\Russian` but redefine its meaning; now `\Russian` is simply an alias for `\selectlanguage{russian}`.

\cyr

We define `\cyrillictext` and its alias `\cyr` but remove another alias `\Rus`; these macros are intended for use within `babel` macros and do not perform complete switch of the language. In particular, they to do no switch captions and the name of current language stored in the macro `\languagename`. This inconsistency might break some assumptions embedded into `babel`'s. For example, the `\iflanguage` macro will fail.

Second, `\cyrillictext` does not activate shorthands, so that “<, ”>, ”“, ””, ”---, e.t.c. will not work.

And third, `\cyrillictext` does not write its trace to `.aux` file, which might result in wrong typesetting of table of content, list of table and list of figures in multilingual documents.

Due to any of these reasons the use of the declaration `\cyrillictext` and its aliases in ordinary text is strongly discouraged. Instead of the declaration `\cyrillictext` it is recommended to use `\Russian` or the command `\foreignlanguage` defined in the `babel` core; their functionality is similar to `\selectlanguage{russian}` but they did not switch caption names, dates and shorthands.

```

58 \DeclareRobustCommand{\Russian}{\selectlanguage{\russian}}
59 \DeclareRobustCommand{\cyrillictext}{%
60   \fontencoding{cyrillicencoding}\selectfont
61   \let\encodingdefault\cyrillicencoding
62   \expandafter\set@hyphenmins\russianhyphenmins
63   \language\l@russian}%
64 \let\cyr\cyrillictext

```

Starting from version v.1.2 we remove the `\English` macro and its aliases. We believe that reasonable place for defining these macros would be `englishb.1df`. Note also that the macro `\English` and its alias `\Eng` are absent in `russianb.1df`'s counterpart in the package `polyglossia`, analog of `babel` for Xe^LT_EX.

```
65 %%\DeclareRobustCommand{\English}{%
66 %%  \fontencoding\latinencoding\selectfont
67 %%  \let\encodingdefault\latinencoding
68 %%  \expandafter\set@hyphenmins\englishhyphenmins
69 %%  \language\l@english}%
70 %%\let\Eng\English
```

NEXT PART OF CODE SHOULD BE MOVED TO `X2enc.def`, `X2enc.dfu`, IF NEEDED. Since the `X2` encoding does not contain Latin letters, we should make some redefinitions of L^AT_EX macros which implicitly produce Latin letters.

Unfortunately, the commands `\AA` and `\aa` are not encoding dependent in L^AT_EX (unlike e.g., `\oe` or `\DH`). They are defined as `\r{A}` and `\r{a}`. This leads to unpredictable results when the font encoding does not contain the Latin letters ‘A’ and ‘a’ (like `X2`).

```
71 \expandafter\ifx\csname T@X2\endcsname\relax\else
72   \DeclareTextSymbolDefault{\AA}{OT1}
73   \DeclareTextSymbolDefault{\aa}{OT1}
74   \DeclareTextCommand{\aa}{OT1}{\r a}
75   \DeclareTextCommand{\AA}{OT1}{\r A}
76 \fi
```

The macro `\cyrillictext` switches current (e.g., Latin) font encoding to a Cyrillic font encoding stored in `\cyrillicencoding`. The macro `\latintext` switches back. This method assumes that a font encoding is a Latin one. But in fact the latter assumption does not matter if any other language is switched on using same method, i.e. if corresponding `.1df` file defines required macros to switch that language on from same standard (Latin) state. Since `\latintext` is defined by the core of `babel` we do not repeat its definition here.

```
77 %\DeclareRobustCommand{\latintext}{%
78 %  \fontencoding{\latinencoding}\selectfont
79 %  \def\encodingdefault{\latinencoding}%
80 %\let\lat\latintext
```

`\textcyrillic` {⟨text⟩}

The macros `\cyrillictext` and `\latintext` are declarations. For shorter chunks of text the commands `\textcyrillic` and `\textlatin` can be used.

The macro `\textcyrillic` takes an argument which is then typeset using the requested font encoding. It is thus an equivalent of `\foreignlanguage{russian}`.

```
81 \DeclareTextFontCommand{\textcyrillic}{\cyrillictext}
```

7.3 Input encoding

User should use the `inputenc` package when any 8-bit Cyrillic font encoding is used, selecting one of the Cyrillic input encodings. We do not assume any default input encoding, so the `inputenc` package should be explicitly called by `\usepackage{inputenc}` before `babel`. Note however that default font encoding

T2A fits well enough to Russian version of Windows ANSI encoding which is almost equivalent to cp1251.

SHOULD WE WRAP THIS CHUNK INTO AT BEGIN DOCUMENT?

```

82 \@ifpackageloaded{inputenc}{%
83   \if@uni@ode
84     \PackageWarning{babel}{inputenc should not be used with LuaTeX or XeTeX}
85   \fi
86 }{%
87   \%def\reserved@a{LWN}%
88   \%ifx\reserved@a\cyrillicencoding\else
89     \def\reserved@a{\OT2}%
90   \ifx\reserved@a\cyrillicencoding\else
91     \def\reserved@a{\EU1}%
92   \ifx\reserved@a\cyrillicencoding\else
93     \def\reserved@a{\EU2}%
94   \ifx\reserved@a\cyrillicencoding\else
95     \PackageWarning{babel}%
96     {No input encoding specified for Russian language}
97   \fi\fi\fi
98 }%
99 }
```

7.4 Shorthands

The double quote character ” is declared to be active in Russian language.

```
100 \initiate@active@char{”}
```

\mdqon Obsolete: Active double quote can be both activated and deactivated at any time
\mdqoff using the macros \mdqon and \mdqoff.

```

101 \%def\mdqon{\bb@activate{”}}
102 \%def\mdqoff{\bb@deactivate{”}}
```

Initial activation state will set to on later in section 7.5.4.

\dq The active character ” is used as indicated in table 1. We save the original double quote character in the \dq macro to keep it available. The math accent \” can now be typed as “”.

```

103 \begingroup \catcode`'12
104 \def\reserved@a{\endgroup
105   \def\@SS{\mathchar"7019 }
106   \def\dq{”}
107 \reserved@a
```

7.4.1 Quotes

We set “” and ”” as shorthands for \quotedblbase and \textquotedblleft, respectively. Prior to ver.1.2, these shorthands were defined through german quotes \glqq and \grqq, which in their turn are defined in `babel.def` via \quotedblbase and \textquotedblleft, respectively. It occurred, that old definition caused errors in Unicode mode if `fontspec` is loaded.

Prior to version 1.2, the shorthands ”< and ”> were declared to be equivalents for the French quotes \f1qq and \frqq, respectively. They are defined in `babel.def` via \guillemotleft and \guillemotright. However, \f1qq and \guillemotleft (and their right counterparts) are typeset differently if current encoding is not T1. Therefore, since v.1.2, we define ”< and ”> directly through \guillemotleft and \guillemotright.

```
108 \declare@shorthand{russian}{"`"}{\quotedblbase}
109 \declare@shorthand{russian}{"`"}{\textquotedblleft}
110 \declare@shorthand{russian}{"<"}{\guillemotleft}
111 \declare@shorthand{russian}{">"}{\guillemotright}
```

Next set of shorthands is intended for variations of standard macro \- which indicates explicitly breakpoint for hyphenation in a word. Meaning of these shorthands is explained in table 1.

```
112 \declare@shorthand{russian}{"``"}{\hskip\zskip}
113 \declare@shorthand{russian}{"``"}{\textormath{\leavevmode\hbox{-}\{-}}
114 \declare@shorthand{russian}{"=-"}{\nobreak-\hskip\zskip}
115 \declare@shorthand{russian}{"||"}{%
116   \textormath{\nobreak\discretionary{-}{\kern.03em}\allowhyphens{}}}
```

7.4.2 Emdash, endash and hyphenation sign

To distinguish between ”- and ”--- we must check whether the next after - token is a hyphen character. If it is, we output an emdash, otherwise a hyphen sign. Therefor \TeX looks for the next token after the first ‘-’, writes its meaning to \russian@sh@next and finally call for \russian@sh@tmp.

```
117 \declare@shorthand{russian}{"-"}{%
118   \def\russian@sh@tmp{%
119     \if\russian@sh@next-\expandafter\russian@sh@emdash
120     \else\expandafter\russian@sh@hyphen\fi}%
121   \futurelet\russian@sh@next\russian@sh@tmp}
```

Two macros \russian@sh@hyphen and \russian@sh@emdash called by \russian@sh@tmp are defined below. The second of them has two parameters since it must gobble next two hyphen signs.

```
122 \def\russian@sh@hyphen{\nobreak\-\bb@allowhyphens}
123 \def\russian@sh@emdash#1#2{\cdash-#1#2}
```

\cdash In its turn, \russian@sh@emdash simply calls for \cdash which has rich use. It analyses 3rd of 3 characters and calls for one of few predefined macros \@Acdash, \@Bcdash, \@Ccdash.

```
124 \def\cdash#1#2#3{\def\texpx@{#3}%
125 \def\tempa@{-}\def\tempb@{~}\def\tempc@{*}%
126 \ifx\texpx@\tempa@\@Acdash\else
127 \ifx\texpx@\tempb@\@Bcdash\else
128 \ifx\texpx@\tempc@\@Ccdash\else
129 \errmessage{Wrong usage of cdash}\fi\fi\fi}
```

All these 3 internal macros call for \cyrdash, which type Cyrillic emdash, but put different spaces around the dash.

\@Acdash is invoked by ”---. It types Cyrillic emdash to be used inside a text and puts an unbreakable thin space before the dash if a space is placed before

”--- in the source file; can be used after display maths formulae, formatted lists, enumerations, etc.

```
130 \def\@Acdash{\ifdim\lastskip>\z@\unskip\nobreak\hskip.2em\fi  
131   \cyrdash\hskip.2em\ignorespaces}%
```

\@Bcdash is invoked by ”--~. It types Cyrillic emdash in compound names (like Mendeleev–Klapeiron); requires no space characters around and adds extra space after the dash.

```
132 \def\@Bcdash{\leavevmode\ifdim\lastskip>\z@\unskip\fi  
133   \nobreak\cyrdash\penalty\exhyphenpenalty\hskip\z@skip\ignorespaces}%
```

\@Ccdash is invoked by ”--*. It denotes direct speech and adds small space after the dash.

```
134 \def\@Ccdash{\leavevmode  
135   \nobreak\cyrdash\nobreak\hskip.35em\ignorespaces}%
```

\cyrdash The \cyrdash can be defined in a fontenc file as it is done for the T2* encodings. We provide fake definition of \cyrdash only if it is not defined there.

Cyrillic T2* fonts contains shorter (Cyrillic) emdash. It can be typeset also via the ligature ---. So, if \latinencoding differs from T2* switching of languages also changes the emdash length typed as ligature in the source file.

```
136 \ifx\cyrdash\undefined  
137   \def\cyrdash{\hbox{.8em{--}\hss--}}  
138   \PackageInfo{babel}{\string\cyrdash\space is defined}  
139 \fi
```

Finally, we define a shorthand thin space to be placed between initials as in D.”,Mendeleev. When used instead of \, as in D.\,Mendeleev it allows hyphenation in the next word.

```
140 \declare@shorthand{russian}{"}{\nobreak\hskip.2em\ignorespaces}
```

7.5 Switching to and from Russian

Now we define additional macros used to reset current language to Russian and back to some original state. The package `babel` based on the assumption that original state is characterized by a Latin encoding. Previously, for back reset the macro `\OriginalTeX` was used, but now use `\latintext` for the same purpose.

7.5.1 Caption names

First, we define Russian equivalents for Russian caption names.

\captionsrussian The macro \captionsrussian defines caption names used in the four standard document classes provided with L^AT_EX. The macro \cyr activates Cyrillic encoding. It could be dropped if we would be sure that Russian captions are called only if current language is Russian. However, the macros such as \Russian do not conform to strict rules of the package `babel` as explained in the above.

As of version v.1.2 we eliminate \cyr... macros from caption names if unicode engine is running. In the latter case, Cyrillic letters are typed in by their unicode code-points, the ^~~~abcd notation is not used since it causes error at compilation time in case if L^AT_EX is running and utf8 input encoding is not declared.

```

141 \if@uni@code
142   %\captionsrussian@modern
143   \addto\captionsrussian{%
144     \def\prefacename{Предисловие}%
145     \def\refname{Список литературы}%
146     \def\abstractname{Аннотация}%
147     \def\bibname{Литература}%
148     \def\chaptername{Глава}%
149     \def\appendixname{Приложение}%

```

Note that two names for the Table of Contents can be used in Russian publications. For books (and reports) the second variant is appropriate, but for proceedings the first variant is preferred:

```

150   \@ifundefined{thechapter}
151     {\def\contentsname{Содержание}%
152      \def\contentsname{Оглавление}%
153      \let\tocname=\contentsname
154      \def\listfigurename{Список иллюстраций}%
155      \def\listtablename{Список таблиц}%
156      \def\indexname{Предметный указатель}%
157      \def\authorname{Именной указатель}%
158      \def\figurename{Рис.}%
159      \def\tablename{Таблица}%
160      \def\partname{Часть}%
161      \def\enclname{вкл.}%
162      \def\ccname{исх.}%
163      \def\headtoname{вх.}%
164      \def\pagename{с.}%
165      \def\seename{см.}%
166      \def\alsoename{см. \ также}%
167      \def\proofname{Доказательство}%
168      \def\glossaryname{Словарь терминов}%
169      \def\acronymname{Аббревиатуры}%
170      \def\lstlistingname{Листинг}%
171      \def\lstlistlistingname{Листинги}%
172      \def\notesname{Заметки}%
173    }%

```

Additional definitions for the package `nomencl`:

```

174  %% =====
175  %% nomencl
176  \ifdefined\nomname
177    \addto\captionsrussian{%
178      \def\nomname{Обозначения}%
179      \def\eqdeclaration#1{, см.\nobreakspace (#1)}%
180      \def\pagedeclaration#1{, стр.\nobreakspace #1}%
181    }%
182  \fi

```

Additional captions for the `revtex` class.

```

183  %% =====
184  %% RevTeX4 & RevTeX4-1
185  %%\@ifclassloaded{revtex4-1}

```

```

186  %%{<true code>}
187  %%{<false coode>}%
188  %\ifclassloaded{revtex4-1}
189  %%
190  \ifnum\@ifclassloaded{revtex4}{1}{\@ifclassloaded{revtex4-1}{1}{0}}>0
191      \addto\captionsrussian{%
192          \def\lofname{\listfigurename}
193          \def\lotname{\listtablename}
194          \def\figuresname{Рисунки}{Figures}%
195          \def\tablesname{Таблицы}{Tables}%
196          \def\appendicesname{Приложения}{Appendixes}%
197          \def\acknowledgmentsname{Благодарности}{Acknowledgments}%
198          \def\andname{и}{and}
199          \def\pacsn@name{PACS коды: }%{PACS numbers: }%
200          \def\keys@name{Ключевые слова: }%{Keywords: }%
201          \def\dated@name{Дата: }%{Dated: }%
202          \def\Received@name{Получено }%{Received }%
203          \def\Revised@name{Исправленная версия }%{Revised }%
204          \def\Accepted@name{Принято }%{Accepted }%
205          \def\Published@name{Опубликовано }%{Published }%
206          }%
207      }%
208  \fi

```

Now we proceed to the ancient version in unicode encoding.

```

209  \addto\captionsrussian@ancient{%
210      \def\prefacename{Предисловие}%
211      \def\refname{Примѣчанія}%
212      \def\abstractname{Аннотація}%
213      \def\bibname{Библіографія}%
214      \def\chaptername{Глава}%
215      \def\appendixname{Приложение}%
216      \@ifundefined{thechapter}
217          {\def\contentsname{Содержание}%
218          {\def\contentsname{Углавление}}%
219          \let\tocname=\contentsname
220          \def\listfigurename{Списокъ иллюстрацій}%
221          \def\listtablename{Списокъ таблицъ}%
222          \def\indexname{Предмѣтный указатель}%
223          \def\authorname{Именной указатель}%
224          \def\figurename{Рис.}%
225          \def\ tablename{Таблица}%
226          \def\partname{Часть}%
227          \def\enclname{вкл.}%
228          \def\ccnname{исх.}%
229          \def\headtoname{вх.}%
230          \def\pagename{с.}%
231          \def\seename{см.}%
232          \def\alsoename{см. ~также}%
233          \def\proofname{Доказательство}%
234          \def\glossaryname{Словарь терминов}%
235          \def\acronymname{Аббревиатуры}%
236          \def\lstlistingname{Листинг}%
237          \def\lstlistlistingname{Листинги}%
238          \%\\ifdefined\nomname

```

```

239 % see http://old_russian.academic.ru/8433/%D0%BE%D0%B1%D1%8A%CB%AB%D0%B0%D0%B2%D0%BB%D0%B5
240 \def\nomname{Обозначения}{Объявление} <-- #0465
241 \%fi
242 \def\notesname{Заметки}%
243 }
244 %% =====
245 %% RevTeX4 & RevTeX4-1
246 \%@ifclassloaded{revtex4-1}
247 \%{%
248 \ifnum@\ifclassloaded{revtex4}{1}{\@ifclassloaded{revtex4-1}{1}{0}}>0
249 \addto\captionsrussian@ancient{%
250 \def\lofname{\listfigurename}
251 \def\lotname{\listtablename}
252 \def\figuresname{Рисунки}{Figures}%
253 \def\tablesname{Таблицы}{Tables}%
254 \def\appendicesname{Приложения}{Appendices}%
255 \def\acknowledgmentsname{Благодарности}{Acknowledgments}%
256 \def\andname{и}{and}%
257 \def@pacs@name{PACS коды: }{PACS numbers: }%
258 \def@keys@name{Ключевые слова: }{Keywords: }%
259 \def\Dated@name{Дата: }{Dated: }%
260 \def\Received@name{Получено }{Received }%
261 \def\Revised@name{Исправленная версия }{Revised }%
262 \def\Accepted@name{Принято }{Accepted }%
263 \def\Published@name{Опубликовано }{Published }%
264 }%
265 \%}{}%
266 \fi
267 %% =====
268 \else
269 \%@def\captionsrussian@modern{%
270 \addto\captionsrussian{%
271 \def\prefacename{%
272 {\cyr\CYRP\cyrr\cyre\cyrd\cyri\cyrs\cyrl\cyro\cyrv\cyri\cyre}}%
273 \def\refname{%
274 {\cyr\CYRS\cyrp\cyri\cyrs\cyro\cyrk\%
275 \cyrl\cyri\cyre\cyrr\cyra\cyrt\cyru\cyrr\cyrery}}%
276 \def\abstractname{%
277 {\cyr\CYRA\cyrn\cyro\cyrt\cyra\cyrc\cyri\cyrya}}%
278 \def\bibname{%
279 {\cyr\CYRL\cyri\cyrt\cyre\cyrr\cyra\cyrt\cyru\cyrr\cyra}}%
280 \def\chaptername{ {\cyr\CYRG\cyrl\cyra\cyrv\cyra}}%
281 \def\appendixname{%
282 {\cyr\CYRP\cyrr\cyri\cyrl\cyro\cyrz\cyre\cyrn\cyri\cyre}}%
283 \@ifundefined{thechapter}%
284 {\def\contentsname{%
285 {\cyr\CYRS\cyro\cyrd\cyre\cyrr\cyrz\cyra\cyrn\cyri\cyre}}}}%
286 {\def\contentsname{%
287 {\cyr\CYR\cyrg\cyrl\cyra\cyrv\cyrl\cyre\cyrn\cyri\cyre}}}}%
288 \let\tocname=\contentsname
289 \def\listfigurename{%
290 {\cyr\CYRS\cyrp\cyri\cyrs\cyro\cyrk\%
291 \cyri\cyrl\cyrl\cyryu\cyrs\cyrt\cyrr\cyra\cyrc\cyri\cyrishrt}}%
292 \def\listtablename{%

```

```

293 { \cyr \CYRS \cyrp \cyri \cyrs \cyro \cyrk
294   \ \cyrt \cyra \cyrb \cyrl \cyri \cyrc } %
295 \def \indexname{%
296   {\cyr \CYRP \cyrr \cyre \cyrd \cyrm \cyre \cyrt \cyrn \cyrery \cyrishrt
297     \ \cyru \cyrk \cyra \cyrz \cyra \cyrt \cyre \cyrl \cystsfn } %
298 \def \authorname{%
299   {\cyr \CYR \cyrm \cyre \cyrn \cyrn \cyro \cyrishrt
300     \ \cyru \cyrk \cyra \cyrz \cyra \cyrt \cyre \cyrl \cystsfn } %
301 \def \figurename{\{\cyr \CYRR \cyri \cyrs .\} %}
302 \def \tablename{\{\cyr \CYRT \cyra \cyrb \cyrl \cyri \cyrc \cyra\} %}
303 \def \partname{\{\cyr \CYRCH \cyra \cyrs \cyrt \cystsfn\} %}
304 \def \enclname{\{\cyr \cyrv \cyrk \cyrl.\} %}
305 \def \ccname{\{\cyr \cyri \cyrs \cyrh.\} %}
306 \def \headtoname{\{\cyr \cyrv \cyrh.\} %}
307 \def \pagename{\{\cyr \cyrs .\} %}
308 \def \seename{\{\cyr \cyrs \cymn.\} %}
309 \def \alsoame{\{\cyr \cyrs \cymn. \ \cyrt \cyra \cyrk \cyrzh \cyre\} %}
310 \def \proofname{\{\cyr \CYRD \cyro \cyrk \cyra \cyrz \cyra \cyrt
311   \ \cyre \cyrl \cystsfn \cyrs \cyrt \cyrv \cyro\} %}
312 \def \glossaryname{\{\cyr \CYRS \cyrl \cyro \cyrv \cyra \cyrr \cystsfn \
313   \ \cyrt \cyre \cyrr \cyrm \cyri \cyrn \cyro \cyrv\} %}
314 \def \acronymname{\CYRA \cyrb \cyrb \cyrr \cyre \cyrv \cyri \cyra \cyrt \cyru \cyrr \cyrery\} %
315 \def \lstlistingname{\CYRL \cyri \cyrs \cyrt \cyri \cyrn \cyrq\} %
316 \def \lstlistlistingname{\CYRL \cyri \cyrs \cyrt \cyri \cyrn \cyrq \cyri\} %
317 \def \nomname{\CYR0 \cyrb \cyro \cyrz \cyrn \cyra \cyrch \cyre \cyrn \cyri \cyrya\} %
318 \def \notesname{\CYRZ \cyra \cyrm \cyre \cyrt \cyrk \cyri\} %
319 }%
320 %% =====
321 %% RevTeX4 & RevTeX4-1
322 \ifnum `@ifclassloaded{revtex4}{1}{`@ifclassloaded{revtex4-1}{1}{0}}>0
323   \addto \captionsrussian{%
324     \def \lofname{\listfigurename}
325     \def \lotname{\listtablename}
326     \def \figuresname{\CYRR \cyri \cyrs \cyru \cyrn \cyrk \cyri\} % {Figures} %
327     \def \tablesname{\CYRT \cyra \cyrb \cyrl \cyri \cyrc \cyrery\} % {Tables} %
328     \def \appendicesname{\CYRP \cyrr \cyri \cyrl \cyro \cyrzh \cyre \cyrn \cyri\} % {Appendixes} %
329     \def \acknowledgmentsname{\CYRB \cyrl \cyrar \cyro \cyrd \cyra \cyrr \cyrn \cyro \cyrs \cyrt \cyri\} %
330     \def \andname{\cyri\} % {and}
331     \def @pacs@name{PACS \cyrk \cyro \cyrd \cyrery: } % {PACS numbers: }
332     \def @keys@name{\CYRK \cyrl \cyryu \cyrch \cyre \cyrv \cyrery \cyre \cyrs \cyrl \cyro \cyrv \cyra: } %
333     words: } %
334     \def \Dated@name{\CYRD \cyra \cyrt \cyra: } % {Dated: }
335     \def \Received@name{\CYRP \cyro \cyrl \cyru \cyrch \cyre \cyrn \cyro } % {Received }
336     \def \Revised@name{\CYRI \cyrs \cyrp \cyrr \cyra \cyrv \cyrl \cyre \cyrn \cyra\} % {Revised }
337     \def \Accepted@name{\CYRP \cyrr \cyri \cyrn \cyrya \cyrt \cyro } % {Accepted }
338     \def \Published@name{\CYR0 \cyrp \cyru \cyrb \cyrl \cyri \cyrk \cyro \cyrv \cyra \cyrn \cyro } % {Published }
339   }%
340 %% =====
341 \addto \captionsrussian@ancient{%
342   \def \prefacename{%
343     {\cyr \CYRP \cyrr \cyre \cyrd \cyri \cyrs \cyrl \cyro \cyrv \cyrii \cyre\} %}

```

```

344 \def\refname{%
345   {\cyr\CYRP\cyrr\cyri\cyrm\cyryat\cyrch\cyra\cyrn\cyrii\cyrya}}% <-
346 - Примѣчанія, нет \cyryat в кодировке T2*
347 \def\abstractname{%
348   {\cyr\CYRA\cyrn\cyrn\cyro\cyrt\cyra\cyrc\cyrii\cyrya}}%
349 \def\bibname{%
350   {\cyr\CYRB\cyri\cyrb\cyrl\cyrii\cyro\cyrg\cyrr\cyra\cyrf\cyrii\cyrya}}% <-
351 - Библиографія
352 \def\chaptername{{\cyr\CYRG\cyrl\cyra\cyrv\cyra}}%
353 \def\appendixname{%
354   {\cyr\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyrii\cyre}}%
355 \@ifundefined{thechapter}%
356   {\def\contentsname{%
357     {\cyr\CYRS\cyro\cyrd\cyre\cyrr\cyrzh\cyra\cyrn\cyrii\cyre}}%
358 \let\tocname=\contentsname
359 % Списокъ иллюстрацій
360 \def\listfigurename{%
361   {\cyr\CYRS\cyrp\cyri\cyrs\cyro\cyrk\cyrhdsn\
362     \cyri\cyrl\cyrl\cyru\cyrs\cyrt\cyrr\cyra\cyrc\cyrii\cyrishrt}}%
363 % Списокъ таблицъ
364 \def\listtablename{%
365   {\cyr\CYRS\cyrp\cyri\cyrs\cyro\cyrk\cyrhdsn\
366     \cyrt\cyra\cyrb\cyrl\cyri\cyrc\cyrhdsn}}%
367 % Предмѣтный указатель, Ѳ (\cyryat) in X2 encoding only
368 \def\indexname{%
369   {\cyr\CYRP\cyrr\cyre\cyrd\cyrm\cyryat\cyrt\cyrn\cyrery\cyrishrt\space
370     \cyru\cyrk\cyra\cyrz\cyra\cyrt\cyre\cyrl\crysftsn}}%
371 \def\authorname{%
372   {\cyr\CYRI\cyrm\cyre\cyrn\cyrn\cyro\cyrishrt\
373     \cyru\cyrk\cyra\cyrz\cyra\cyrt\cyre\cyrl\crysftsn}}%
374 \def\figurename{{\cyr\CYRR\cyri\cyrs.}}%
375 \def\ tablename{{\cyr\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyra}}%
376 \def\partname{{\cyr\CYRCH\cyra\cyrs\cyrt\crysftsn}}%
377 \def\enclname{{\cyr\cyrv\cyrk\cyrl.}}%
378 \def\ccname{{\cyr\cyri\cyrs\cyrh.}}%
379 \def\headtoname{{\cyr\cyrv\cyrh.}}%
380 \def\pagename{{\cyr\cyrs.}}%
381 \def\seename{{\cyr\cyrs\cyrm.}}%
382 \def\alsoiname{{\cyr\cyrs\cyrm.\ \cyrt\cyra\cyrk\cyrzh\cyre}}%
383 \def\proofname{{\cyr\CYRD\cyro\cyrk\cyra\cyrz\cyra\cyrt
384   \cyre\cyrl\crysftsn\cyrs\cyrt\cyrv\cyro}}%
385 \def\glossaryname{{\cyr\CYRS\cyrl\cyro\cyrv\cyra\cyrr\crysftsn\
386   \cyrt\cyre\cyrr\cyrm\cyri\cyrn\cyro\cyrv}}% <- Needs translation
387 \def\acronymname{{\CYRA\cyrb\cyrb\cyrr\cyre\cyrv\cyri\cyra\cyrt\cyru\cyrr\cyrery}}%
388 \def\lstlistingname{{\CYRL\cyri\cyrs\cyrt\cyri\cyrn\cyrg}}%
389 \def\lstlistlistingname{{\CYRL\cyri\cyrs\cyrt\cyri\cyrn\cyrg\cyri}}%
390 \def\nomname{{\CYR0\cyrb\cyro\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrii\cyrya}}%
391 \def\notesname{{\CYRZ\cyra\cyrm\cyre\cyrt\cyrk\cyri}}%
392 }%
393 %% =====
394 %% RevTeX4 & RevTeX4-1
395 \ifnum \ifclassloaded{revtex4}{1}\ifclassloaded{revtex4-1}{1}\else{0}\fi>0

```

```

396 \addto\captionsrussian@ancient{%
397 \def\lofname{\listfigurename}
398 \def\lotname{\listtablename}
399 \def\figuresname{\CYRR\cyri\cyrs\cyr\cyrn\cyrk\cyri}{Figures}%
400 \def\tablesname{\CYRT\cyra\cyrb\cyr\cyr\cyrn\cyrk\cyri}{Tables}%
401 \def\appendicesname{\CYRP\cyrr\cyri\cyr\cyr\cyrn\cyrk\cyri}{Appendices}%
402 \def\acknowledgmentsname{\CYRB\cyr\cyr\cyr\cyr\cyrn\cyrk\cyri}{Acknowledgments}%
403 \def\andname{\cyri}{and}%
404 \def\PACS@name{\cyrk\cyro\cyr\cyr\cyrn\cyrk\cyri}{PACS numbers: }%
405 \def\keys@name{\CYRK\cyr\cyr\cyr\cyr\cyrn\cyrk\cyri}{Keys: }%
406 \def\words: }%
407 \def\@pacs@name{\cyrk\cyro\cyr\cyr\cyrn\cyrk\cyri}{PACS numbers: }%
408 \def\@keys@name{\cyrk\cyro\cyr\cyr\cyrn\cyrk\cyri}{Keys: }%
409 \def\@pacs@name{\cyrk\cyro\cyr\cyr\cyrn\cyrk\cyri}{PACS numbers: }%
410 \def\@keys@name{\cyrk\cyro\cyr\cyr\cyrn\cyrk\cyri}{Keys: }%
411 \def\@pacs@name{\cyrk\cyro\cyr\cyr\cyrn\cyrk\cyri}{PACS numbers: }%
412 \def\@keys@name{\cyrk\cyro\cyr\cyr\cyrn\cyrk\cyri}{Keys: }%
413 =====
414 \fi

```

7.5.2 Date in Russian

\daterussian The macro \daterussian is used to reset the macro \today in Russian.

```

415 \if@uni@ode
416 \addto\daterussian{%
417 \def\today{\number\day`~\ifcase\month\or
418 января\or
419 февраля\or
420 марта\or
421 апреля\or
422 мая\or
423 июня\or
424 июля\or
425 августа\or
426 сентября\or
427 октября\or
428 ноября\or
429 декабря\fi
430 \space \number\year`~г.}}
431 \def\daterussian@ancient{%
432 \def\today{\number\day`~\ifcase\month\or%
433 января\or
434 февраля\or
435 марта\or
436 апреля\or
437 мая\or
438 июня\or
439 июля\or
440 августа\or
441 сентября\or

```

```

442     октября\or
443     ноября\or
444     декабря\fi%
445     \space \number\year~г.}}
446 \else
447   \def\daterussian{%
448     \def\today{\number\day`\ifcase\month\or
449       \cyrya\cyrn\cyrv\cyra\cyrr\cyrya\or
450       \cyrf\cyre\cyrv\cyrr\cyra\cyrl\cyrya\or
451       \cyrm\cyra\cyrr\cyrt\cyra\or
452       \cyra\cyrp\cyrr\cyre\cyrl\cyrya\or
453       \cyrm\cyra\cyrya\or
454       \cyri\cyryu\cyrn\cyrya\or
455       \cyri\cyryu\cyrl\cyrya\or
456       \cyra\cyrv\cyrg\cyru\crys\cyrt\cyra\or
457       \cyrs\cyre\cyrn\cyrt\cyra\cyrb\cyrr\cyrya\or
458       \cyro\cyrk\cyrt\cyra\cyrb\cyrr\cyrya\or
459       \cyrn\cyro\cyrya\cyrb\cyrr\cyrya\or
460       \cyrd\cyre\cyrk\cyra\cyrb\cyrr\cyrya\fi
461     \space \number\year`\cyrg.}}
462   \def\daterussian@ancient{%
463     \def\today{\number\day`\ifcase\month\or
464       \cyrya\cyrn\cyrv\cyra\cyrr\cyrya\or
465       \cyrf\cyre\cyrv\cyrr\cyra\cyrl\cyrya\or
466       \cyrm\cyra\cyrr\cyrt\cyra\or
467       \cyra\cyrp\cyrr\cyre\cyrl\cyrya\or
468       \cyrm\cyra\cyrya\or
469       \cyrii\cyryu\cyrn\cyrya\or
470       \cyrii\cyryu\cyrl\cyrya\or
471       \cyra\cyrv\cyrg\cyru\crys\cyrt\cyra\or
472       \cyrs\cyre\cyrn\cyrt\cyra\cyrb\cyrr\cyrya\or
473       \cyro\cyrk\cyrt\cyra\cyrb\cyrr\cyrya\or
474       \cyrn\cyro\cyrya\cyrb\cyrr\cyrya\or
475       \cyrd\cyre\cyrk\cyra\cyrb\cyrr\cyrya\fi
476     \space \number\year`\cyrg.}}
477 \fi

```

7.5.3 Hyphenation patterns

Russian hyphenation patterns are automatically activated every time Russian language is selected via `\selectlanguage`, `\foreignlanguage` or equivalent command. But we need to declare values of `\lefthyphenmin` and `\righthyphenmin`; both are set to 2.

As of v.1.2 we removed a definition for `\englishhyphenmins`. It is not deal of `russianb.ldf`.

```

478 \providehyphenmins{\CurrentOption}{\tw@\tw@}
479 \providehyphenmins{russian}{\tw@\tw@}

```

7.5.4 Extra definitions

`\extrasrussian` The macro `\extrasrussian` performs extra definitions in addition to resetting the `\noextrasrussian`

caption names and date. The macro `\noextrasrussian` is used to cancel the actions of `\extrasrussian`.

First, we instruct `babel` to switch font encoding using earlier defined macros `\cyrillictext` and `\latintext`.

```
480 \addto\extrasrussian{\cyrillictext}
481 \addto\noextrasrussian{\latintext}
```

Second, we specify that the Russian group of shorthands should be used.

```
482 \addto\extrasrussian{\languageshorthands{russian}}
483 \addto\extrasrussian{\bb@activate{''{}}
484 \addto\noextrasrussian{\bb@deactivate{''{}}}
```

Now the action `\extrasrussian` has to execute is to make sure that the command `\frenchspacing` is in effect. If this is not the case the execution of `\noextrasrussian` will switch it off again.

```
485 \addto\extrasrussian{\bb@frenchspacing}
486 \addto\noextrasrussian{\bb@nonfrenchspacing}
```

7.6 Alphabetic counters

Do we need to reset `\@alph` and `\@Alph`? They are used in the L^AT_EX core to define the macros `\alph` and `\Alph`, respectively, which type a counter with a corresponding letter of Latin alphabet. We just want to make sure that correct `\latinencoding` is used instead of `\latinencoding` to typeset the counter. Starting from v.1.2 we do not reset these macros since all Cyrillic encoding but X2 do have Latin letters. When using the X2 encoding user must himself take care about selecting correct encoding when he switches his keyboard. Our decision is motivated as follows. If selected Cyrillic font is visually different from Latin font, the macro `\@alph` and `\@Alph` will produce visually different output from surrounding text if they are used with Russian text, which is completely legitimate.

Notice for commented code:

We put `\latinencoding` in braces to avoid problems with `\@alph` inside minipages (e.g., footnotes inside minipages) where `\@alph` is expanded and we get for example ‘`\fontencoding OT1`’ (`\fontencoding` is robust).

Note added on 2013/03/22: `{\fontencoding{\latinencoding}\selectfont` rises an error with recent version of `microtype` package after the `\appendix` declaration (which resets `\thechapter` to `\@Alph\c@chapter`). Most languages do not reset `\@alph` and `\@Alph` macros and only `ukrainian` and `bulgarian` add `\fontencoding` to `\@alph` and `\@Alph`.

Since v.1.3 we do not reset `\@alph` and `\@Alph` here. Resetting `\fontencoding` in `\@alph` and `\@Alph` causes an error if the package `smartref` is loaded and a `\sref` occurs after the `\appendix` declaration which resets `\thechapter` to `\@Alph\c@chapter`.

```
487 %\def\@alph#1{\fontencoding{\latinencoding}\selectfont
488 %  \ifcase#1\or
489 %    a\or b\or c\or d\or e\or f\or g\or h\or
490 %    i\or j\or k\or l\or m\or n\or o\or p\or
491 %    q\or r\or s\or t\or u\or v\or w\or x\or
492 %    y\or z\else\@ctrerr\fi\}%
493 %\def\@Alph#1{\fontencoding{\latinencoding}\selectfont
494 %  \ifcase#1\or
```

```

495 %     A\or B\or C\or D\or E\or F\or G\or H\or
496 %     I\or J\or K\or L\or M\or N\or O\or P\or
497 %     Q\or R\or S\or T\or U\or V\or W\or X\or
498 %     Y\or Z\else{@ctrerr\fi}}%

```

We add new enumeration style for Russian manuscripts with Cyrillic letters.

\Asbuk We begin by defining `\Asbuk` which works like `\Alph`, but produces (uppercase) Cyrillic letters instead of Latin ones. The letters YO, ISHRT, HRDSN, ERY, and SFTSN are skipped, as usual for such enumeration.

```

499 \def\Asbuk#1{\expandafter\russian@Alph\csname c@#1\endcsname}
500 \if@uni@ode
501   \def\russian@Alph#1{\ifcase#1\or
502     А\or Б\or Г\or Д\or Е\or Х\or
503     З\or И\or К\or Л\or М\or Н\or О\or
504     П\or Р\or С\or Т\or У\or В\or Ш\or Х\or
505     Ц\or Ч\or І\or ІІ\or Ѕ\or ЅІ\or Ѓ\or ЃІ\or Ї\or ЇІ\or Й\else{@ctrerr\fi}}
506 \else
507   \def\russian@Alph#1{\ifcase#1\or
508     \CYRA\or\CYRB\or\CYRV\or\CYRG\or\CYRD\or\CYRE\or\CYRZH\or
509     \CYRZ\or\CYRI\or\CYRK\or\CYRL\or\CYRM\or\CYRN\or\CYRO\or
510     \CYRP\or\CYRR\or\CYRS\or\CYRT\or\CYRU\or\CYRF\or\CYRH\or
511     \CYRC\or\CYRCH\or\CYRSH\or\CYRSHCH\or\CYREREV\or\CYRYU\or
512     \CYRYA\else{@ctrerr\fi}}
513 \fi

```

\asbuk The macro `\asbuk` is similar to `\alph`; it produces lowercase Russian letters.

```

514 \def\asbuk#1{\expandafter\russian@alph\csname c@#1\endcsname}
515 \if@uni@ode
516   \def\russian@alph#1{\ifcase#1\or
517     а\or б\or г\or д\or е\or х\or
518     з\or и\or к\or л\or м\or н\or о\or
519     п\or р\or с\or т\or у\or в\or ш\or х\or
520     ц\or ч\or і\or іі\or іІ\or іІІ\or ѕ\or ѕІ\or ч\or чІ\or љ\else{@ctrerr\fi}}
521 \else
522   \def\russian@alph#1{\ifcase#1\or
523     \cyra\or\cyrb\or\cyrv\or\cyrg\or\cyrd\or\cyre\or\cyrzh\or
524     \cyrz\or\cyri\or\cyrk\or\cyrl\or\cyrm\or\cyrn\or\cyro\or
525     \cyrp\or\cyrr\or\cyrs\or\cyrt\or\cyru\or\cyrf\or\cyrh\or
526     \cyrc\or\cyrch\or\cyrsh\or\cyrshch\or\cyrerev\or\cyryu\or
527     \cyrya\else{@ctrerr\fi}}
528 \fi

```

Babel 3.9 has introduced a notion of a language attribute. An `ancient` attribute changes default behavior, which uses modern Russian spelling, and activates an alternative set of captions and date macros suitable for typesetting ancient Slavonic and Church books.

```

529 \bb@declare@ttribute{russian}{ancient}{%
530   \PackageInfo{babel}{Russian attribute set to ancient}%
531   \let\captionsrussian=\captionsrussian@ancient
532   \let\daterussian=\daterussian@ancient
533 }

```

We don't want for long internal macros to waste memory. So we declare them to be usable within the preamble only.

```
534 \@onlypreamble\captionsrussian@ancient
535 \@onlypreamble\daterussian@ancient
```

7.7 Cyrillic math

For compatibility with older Russian packages we could define the `\No` macro. However the Russian number sign is now superseded with `\textnumero`. Moreover, it can be found of Russian keyboard. Therefore we discard `\No` since v.1.2.

```
536 \%{\ DeclareRobustCommand{\No}{%
537 \% \ifmmode{\nfss@text{\textnumero}}\else\textnumero\fi}
```

As of version 1.2 the macros `\cyrmath..` are not supported any more. They requires package `textmath` which is not available now. Instead of `\cyrmath..` it is advised to use corresponding `\text..` commands; they do work in math mode.

```
538 \%{\RequirePackage{textmath}%
539 \% @ifundefined{sym}\cyrillicencoding letters}{\{}%
540 \% \SetSymbolFont{\cyrillicencoding letters}{bold}\cyrillicencoding
541 \% \rmdefault\bfdefault\updefault
542 \% \DeclareSymbolFontAlphabet\cyrmathrm{\cyrillicencoding letters}
```

And we need few commands to switch to different variants.

```
543 \%{\DeclareMathAlphabet\cyrmathbf{\cyrillicencoding}
544 \% \rmdefault\bfdefault\updefault
545 \%{\DeclareMathAlphabet\cyrmathsf{\cyrillicencoding}
546 \% \sfdefault\mddefault\updefault
547 \%{\DeclareMathAlphabet\cyrmathit{\cyrillicencoding}
548 \% \rmdefault\mddefault\itdefault
549 \%{\DeclareMathAlphabet\cyrmathtt{\cyrillicencoding}
550 \% \ttdefault\mddefault\updefault
551 \% \SetMathAlphabet\cyrmathsf{bold}\cyrillicencoding
552 \% \sfdefault\bfdefault\updefault
553 \% \SetMathAlphabet\cyrmathit{bold}\cyrillicencoding
554 \% \rmdefault\bfdefault\itdefault
555 \% \rmdefault\bfdefault\itdefault
556 \%}
```

\sh We also define few math operator names according to Russian typesetting traditions. Some math functions in Russian math books have names different from English writings. For example, `sinh` in Russian is called `sh`. Special consideration needs the macro `\th` that conflicts with the text symbol `\th` defined in Latin 1 encoding:

```
557 \def\sh{\mathop{\operatorname{sh}}\nolimits}
558 \def\ch{\mathop{\operatorname{ch}}\nolimits}
559 \def\tg{\mathop{\operatorname{tg}}\nolimits}
560 \def\ctg{\mathop{\operatorname{ctg}}\nolimits}
561 \def\arctg{\mathop{\operatorname{arctg}}\nolimits}
562 \def\arcctg{\mathop{\operatorname{arcctg}}\nolimits}
563 \addto\extrasrussian{%
564 \babel@save{\th}%
565 \let\ltx@th\th}
```

```

566 \def\th{\textormath{\ltx@th}%
567 {\mathop{\operator@font th}\nolimits}}%
568 }
569 \def\cth{\mathop{\operator@font cth}\nolimits}
570 \def\cosec{\mathop{\operator@font cosec}\nolimits}

\Prob Finally, we define some rare Russian mathematical symbols:
\Variance
\nod
\nok
\nod
\nok
\Proj
571 \def\Prob{\mathop{\kern\z@\mathsf{P}}\nolimits}
572 \def\Variance{\mathop{\kern\z@\mathsf{D}}\nolimits}
573 \if@uni@ode
574 \def\nod{\mathop{\mathrm{н.о.д.}}\nolimits}
575 \def\nok{\mathop{\mathrm{н.о.к.}}\nolimits}
576 \def\NOD{\mathop{\mathrm{НОД}}\nolimits}
577 \def\NOK{\mathop{\mathrm{НОК}}\nolimits}
578 \def\Proj{\mathop{\mathrm{Пр}}\nolimits}
579 \else
580 \def\nod{\mathop{\cyrmathrm{\cyrn.\cyro.\cyrd.}}\nolimits}
581 \def\nok{\mathop{\cyrmathrm{\cyrn.\cyro.\cyrk.}}\nolimits}
582 \def\NOD{\mathop{\cyrmathrm{\CYRN\CYR0\CYRD}}\nolimits}
583 \def\NOK{\mathop{\cyrmathrm{\CYRN\CYR0\CYRK}}\nolimits}
584 \def\Proj{\mathop{\cyrmathrm{\CYRP\cyrr}}\nolimits}
585 \fi

```

7.8 Final settings

The macro `\ldf@finish` does work needed at the end of each `.ldf` file. This includes resetting the category code of the `@`-sign, loading a local configuration file, and preparing the language to be activated at `\begin{document}` time.

```
586 \ldf@finish{russian}
```

Change History

1.1a	General: use <code>\russianhyphenmins</code> to store the correct values	23	Now use <code>\LdfInit</code> to perform initial checks	9		
	Use the new mechanism for dealing with active characters	14	1.1e	General: Added closing brace to second argument of <code>\LdfInit</code>	9	
1.1b	General: Added switch to LWN encoding	24	1.1f	General: Add macro for thin space between initials	16	
	1.1c	General: Replaced <code>\undefined</code> with <code>\@undefined</code> and <code>\empty</code> with <code>\@empty</code> for consistency with L ^A T _E X	9	Added definitions of Cyrillic em-dash stuff and thinspace	9	
	1.1d	General: Moved the definition of <code>\atcatcode</code> right to the beginning.	9	Added switch for doublequote shorthands	14	
		Now use <code>\ldf@finish</code> to wrap up	27	1.1k	General: replaced all <code>\penalty\@M</code> with <code>\nobreak</code>	9
				1.1l	General: Made not using <code>inputenc</code> a warning instead of an error	14

1.1m		Warning is added if \cyrdash defined	16	
	General: Now use \providehyphenmins to provide a default value	23		
1.1o		\latinencoding: Removed \latinencoding	10	
	General: \latintext is already defined by the core of babel	13		
	\textlatin already defined by the core of babel	13		
1.2		1.2a		
	General: \englishhyphenmins is removed	23	General: Indentation of 1st paragraph removed	9
	\lat removed	13		
	Added EU1 and EU2 encodings	14	1.2b	
	Change definition of \th only for this language	26	General: Renamed to russianu to work with babel-beta 3.9	9
	Check for LuaTeX	9		
	EU1 and EU2 encodings added	11	1.3	
	Removed \English macro	13	General: Removed \@alph and \@Alph	24
	Removed LWN encoding	14	Removed switch for doublequote shorthands	14
	Removed test for present of encoding files	11		
	Unicode code-points added for LuaLaTeX	16, 22	1.3b	
		General: Renamed to russianb to work with babel 3.9	9	
		1.3c		
		General: Fix bug in \daterussian	9	
		1.3d		
		General: Fix bug in \Proj	9	
		1.3e		
		General: Update documentation	9	

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	\@pacs@name	\acronymname
\\"	103	169, 235, 314, 387
\-	122	\adddialect 12
\@Acdash	126, 130	\addto 143, 177, 191, 209, 249, 270, 323, 341, 396, 416, 480, 481, 482, 483, 484, 485, 486, 563
\@Alph	493	\allowhyphens 116
\@Bcdash	127, 132	\alsoname 166, 232, 309, 382
\@CcDash	128, 134	\andname 198, 256, 330, 403
\@SS	105	\appendixesname 196, 254, 328, 401
\@alph	487	\appendixname 149, 215, 281, 351
\@ctrerr	492, 498, 505, 512, 520, 527	\arcctg 562
\@ifclassloaded 185, 188, 190, 246, 248, 322, 395	\arctg 561
\@ifpackageloaded	82	\Asbuk 499
\@ifundefined	150, 216, 283, 353, 539	\asbuk 514
\@keys@name 200, 258, 332, 405	\AtBeginDocument 56
\@nopatterns	11	
\@onlypreamble	35, 36, 37, 38, 534, 535	
	\abstractname 146, 212, 276, 346	
	\Accepted@name 204, 262, 336, 409	
	\acknowledgmentsname 197, 255, 329, 402	

\authorname	350, 352, 355,	460, 475, 523, 580
. 157, 223, 298, 371	357, 361, 365,	\cyrdash .. 131, 133,
	369, 372, 374,	135, 136, 137, 138
B	375, 376, 377,	\CYRE 508
\babel@save	378, 379, 380,	\cyre 272,
\bb@activate .. 101, 483	381, 382, 383, 385	275, 279, 282,
\bb@allowhyphens . 122	\CYRA 277,	285, 287, 296,
\bb@deactivate 102, 484	314, 347, 387, 508	297, 299, 300,
\bb@declare@ttribute	\cyra 275, 277,	309, 311, 313,
. 529	279, 280, 285,	314, 317, 318,
\bb@frenchspacing 485	287, 291, 294,	328, 332, 334,
\bb@nonfrenchspacing	297, 300, 302,	335, 343, 352,
. 486	303, 309, 310,	355, 357, 369,
\begingroup	312, 314, 317,	370, 372, 373,
\bfdefault	318, 327, 329,	382, 384, 386,
. 541, 544, 553, 555	332, 333, 335,	387, 390, 391,
\bibname 147, 213, 278, 348	337, 345, 347,	401, 405, 407,
	349, 350, 355,	408, 450, 452,
C	357, 362, 366,	457, 460, 465,
\captionsrussian ..	370, 373, 375,	467, 472, 475, 523
. 143, 177,	376, 382, 383,	\CYREREV 511
191, 270, 323, 531	385, 387, 390,	\cyrerev 526
\captionsrussian@ancient	391, 400, 402,	\cyrery 275,
. 209, 249,	405, 406, 408,	296, 314, 327,
341, 396, 531, 534	410, 449, 450,	331, 332, 369,
\captionsrussian@modern	451, 452, 453,	387, 400, 404, 405
. 142, 269	456, 460, 464,	\CYRF 510
\catcode	465, 466, 467,	\cyrf .. 349, 450, 465, 525
\ccname 162, 228, 305, 378	468, 471, 475, 523	\CYRG 280, 350, 508
\cdash	\cyrar 329, 402	\cyrg 287, 315,
\cdp@elt	\cyra 335, 408	316, 349, 357,
\cdp@list	\CYRB .. 329, 349, 402, 508	388, 389, 456,
\ch	\cyrb .. 294, 302, 314,	461, 471, 476, 523
\chaptername	317, 327, 337,	\CYRH 510
. 148, 214, 280, 350	349, 366, 375,	\cyrh 305,
\contentsname	387, 390, 400,	306, 378, 379, 525
. 151, 152,	410, 457, 458,	\cyhrdsn .. 361, 365, 366
153, 217, 218,	459, 460, 472,	\CYRI 299,
219, 284, 286,	473, 474, 475, 523	335, 372, 408, 509
288, 354, 356, 358	\CYRC 511	\cyri 272, 274,
\cosec	\cyrc 277,	275, 277, 279,
\csname 71, 499, 514	291, 294, 302,	282, 285, 287,
\ctg	327, 347, 362,	290, 291, 293,
\cth	366, 375, 400, 526	294, 301, 302,
\CurrentOption 478	\CYRCH 303, 376, 511	305, 313, 314,
\cyr 64, 272, 274, 277,	\cyrch 317,	315, 316, 317,
279, 280, 282,	332, 334, 345,	318, 326, 327,
285, 287, 290,	390, 405, 407, 526	328, 329, 330,
293, 296, 299,	\CYRD 310, 333,	336, 337, 343,
301, 302, 303,	383, 406, 508, 582	345, 349, 352,
304, 305, 306,	\cyrd 272,	361, 362, 365,
307, 308, 309,	285, 296, 329,	366, 374, 375,
310, 312, 343,	331, 343, 355,	378, 386, 387,
345, 347, 349,	369, 402, 404,	388, 389, 391,

399, 400, 401,	\cyrmathbf	543	296, 312, 313,
402, 403, 409,	\cyrmathit	547, 554	314, 328, 329,
410, 454, 455, 524	\cyrmathrm	542, 580,	335, 336, 343,
\cyrii		581, 582, 583, 584	345, 349, 352,
345, 347, 349,	\cyrmathsf	545, 552	355, 362, 369,
352, 355, 357,	\cyrmathtt	549	385, 386, 387,
362, 390, 469, 470	\CYRN	509, 582, 583	401, 402, 408,
\cyrillicencoding 19,	\cyrn	277, 282, 285,	409, 449, 450,
39, 43, 45, 48, 53,		287, 296, 299,	451, 452, 457,
55, 60, 61, 88, 90,		313, 315, 316,	458, 459, 460,
92, 94, 539, 540,		317, 326, 328,	464, 465, 466,
542, 543, 545,		329, 334, 335,	467, 472, 473,
547, 549, 552, 554		336, 337, 345,	474, 475, 525, 584
\cyrillictext		347, 352, 355,	\CYRS 274, 285, 290,
.... 59, 64, 81, 480		357, 369, 372,	293, 312, 355,
\cyrishrt		386, 388, 389,	361, 365, 385, 510
291, 296, 299, 362, 369, 372		390, 399, 401,	\crys 272, 274, 290,
\cyria		402, 407, 408,	291, 293, 301,
328, 335, 401, 408		409, 410, 449,	303, 305, 307,
\CYRK		454, 457, 459,	308, 309, 311,
332, 405, 509, 583		464, 469, 472,	315, 316, 326,
\cyrk		474, 524, 580, 581	329, 332, 335,
274, 290, 293, 297,	\CYRO	287, 317,	343, 361, 362,
300, 304, 309,		337, 357, 390,	365, 374, 376,
310, 318, 326,		410, 509, 582, 583	378, 380, 381,
331, 337, 361,	\cyro	272,	382, 384, 388,
365, 370, 373,		274, 277, 282,	389, 399, 402,
377, 382, 383,		285, 290, 293,	405, 408, 456,
391, 399, 404,		299, 310, 311,	457, 471, 472, 525
410, 458, 460,		312, 313, 317,	\cyrsoftsn
473, 475, 524, 581		328, 329, 331,	. 297, 300, 303,
\CYRL		332, 334, 336,	311, 312, 370,
279, 315, 316, 388, 389, 509		337, 343, 347,	373, 376, 384, 385
\cyr1		349, 352, 355,	\CYRSH 511
272, 275, 280, 282,		361, 365, 372,	\cyrsh 526
287, 291, 294,		383, 384, 385,	\CYRSHCH 511
297, 300, 302,		386, 390, 401,	\cyrshch 526
304, 311, 312,		402, 404, 405,	\CYRT 302,
327, 328, 329,		407, 409, 410,	327, 375, 400, 510
332, 334, 335,		458, 459, 473,	\cyrt 275,
337, 343, 349,	\CYRP	474, 524, 580, 581	277, 279, 291,
350, 352, 357,		296, 328, 334,	294, 296, 297,
362, 366, 370,		336, 343, 345,	300, 303, 309,
373, 375, 377,		352, 369, 401,	310, 311, 313,
384, 385, 400,		407, 409, 510, 584	314, 315, 316,
401, 402, 405,	\cyp	274, 290,	318, 329, 333,
407, 408, 410,		293, 335, 337,	336, 347, 362,
450, 452, 455,		361, 365, 408,	366, 369, 370,
465, 467, 470, 524		410, 452, 467, 525	373, 376, 382,
\CYRM		\CYRR	383, 384, 386,
509		301,	387, 388, 389,
\cyrm		326, 374, 399, 510	391, 402, 406,
296, 299, 308, 309, 313,	\cyr	272, 275, 279,	409, 451, 456,
318, 345, 369,		282, 285, 291,	457, 458, 466,
372, 381, 382,			
386, 391, 451,			
453, 466, 468, 524			

471, 472, 473, 525	111, 112, 113,	303, 304, 305,
\CYRU	114, 115, 117, 140	306, 307, 308,
\cyrus	\DeclareMathAlphabet . 543, 545, 547, 549	309, 310, 312,
275, 279, 297, 300,	\DeclareRobustCommand . 58, 59, 65, 77, 536	314, 315, 316,
314, 326, 334,	\DeclareSymbolFontAlphabet . 337, 370, 373,	317, 318, 324,
387, 399, 407,	\DeclareTextCommand . 410, 456, 471, 525	325, 326, 327,
410, 456, 471, 525 542	328, 329, 330,
\CYRV	\DeclareTextCommand . 508	331, 332, 333,
\cyrv	\DeclareTextFontCommand . 272, 280, 287,	334, 335, 336,
304, 306, 311,	\DeclareTextSymbolDefault . 312, 313, 314,	337, 342, 344,
332, 335, 337,	\def 14, 15, 21, 79, 87, . 343, 350, 357,	346, 348, 350,
377, 379, 384,	89, 91, 93, 101, . 385, 386, 387,	351, 354, 356,
405, 408, 410,	102, 104, 105, . 449, 450, 456,	360, 364, 368,
464, 465, 471, 523	106, 118, 122, . 123, 124, 125,	371, 374, 375,
\CYRYA	130, 132, 134, . 277,	376, 377, 378,
\cyrya	137, 144, 145, . 317, 336, 345,	379, 380, 381,
347, 349, 390,	146, 147, 148, . 409, 449, 450,	382, 383, 385,
452, 453, 454,	149, 151, 152, . 455, 457, 458,	387, 388, 389,
459, 460, 464,	154, 155, 156, . 465, 467, 468,	390, 391, 397,
469, 470, 472,	157, 158, 159, . 473, 474, 475, 527	398, 399, 400,
\cyryat	160, 161, 162, . 163, 164, 165,	401, 402, 403,
\CYRYU	166, 167, 168, . 169, 170, 171,	404, 405, 406,
\cyryu	172, 178, 179, . 180, 192, 193,	407, 408, 409,
362, 405, 454,	194, 195, 196, . 455, 469, 470, 526	410, 417, 431,
\CYRZ	197, 198, 199, . 200, 201, 202,	432, 447, 448,
\cyrz	203, 204, 205, . 210, 211, 212,	462, 463, 487,
310, 317, 370,	213, 214, 215, . 373, 383, 390, 524	493, 499, 501,
\CYRZH	217, 218, 220, . 221, 222, 223,	507, 514, 516,
\cyrzh	224, 225, 226, . 227, 228, 229,	522, 557, 558,
282, 285, . 309, 328, 352,	230, 231, 232, . 233, 234, 235,	559, 560, 561,
355, 382, 401, 523	236, 237, 240, . 242, 250, 251,	562, 566, 569,
D	252, 253, 254, . 255, 256, 257,	570, 571, 572,
\Dated@name	258, 259, 260, . 261, 262, 263,	574, 575, 576,
\daterussian 416, 447, 532	269, 271, 273, . 276, 278, 280,	577, 578, 580,
\daterussian@ancient	281, 284, 286, . 289, 292, 295,	581, 582, 583, 584
. 431, 462, 532, 535	298, 301, 302,	\discretionary 116
\day		\dq 106
\declare@shorthand		
. 108, 109, 110,		
		E
\edef		\edef 16, 17, 43, 45, 48
\else		\else 8, 40, 44,
		47, 71, 88, 90, 92,
		94, 120, 126, 127,
		128, 268, 446,
		492, 498, 505,
		506, 512, 520,
		521, 527, 537, 579
\enclname		\enclname 161, 227, 304, 377
\encodingdefault		\encodingdefault 61, 67, 79
\endcsname		\endcsname 71, 499, 514
\endgroup		\endgroup 104
\Eng		\Eng 70

F
\fi 6, 9, 13, 20, 31,
46, 49, 57, 76, 85,
97, 98, 120, 129,
130, 132, 139,
182, 208, 241,
266, 339, 412,
414, 429, 444,
460, 475, 477,
492, 498, 505,
512, 513, 520,
527, 528, 537, 585
\figurename
. 158, 224, 301, 374
\figuresname
. 194, 252, 326, 399
\fontencoding
60, 66, 78, 487, 493
\futurelet 121
G
\glossaryname
. 168, 234, 312, 385
\guillemotleft 110
\guillemotright 111
H
\hbox 113, 137
\headtoname
. 163, 229, 306, 379
\hskip 112, 114, 130,
131, 133, 135, 140
\hss 137
I
\if 119
\if@uni@ode 2,
7, 28, 41, 83, 141,
415, 500, 515, 573
\ifcase 417, 432, 448,
463, 488, 494,
501, 507, 516, 522
\ifdef 2, 8, 9,
39, 42, 44, 176, 238
K
\kern 116, 571, 572
L
\l@english 69
\l@russian 10, 12, 63
\language 63, 69
\languageshorthands 482
\lastskip 130, 132
\lat 80
\latinencoding 14, 66,
67, 78, 79, 487, 493
\latintext 77, 80, 481
\ldf@finish 586
\LdfInit 1
\leavevmode 113, 132, 134
\let 19, 61, 64, 67, 70,
80, 153, 219, 288,
358, 531, 532, 565
\listfigurename 154,
192, 220, 250,
289, 324, 360, 397
\listtablename 155,
193, 221, 251,
292, 325, 364, 398
\lofname 192, 250, 324, 397
\lotname 193, 251, 325, 398
\lowercase 55
\lstlistingname
. 170, 236, 315, 388
\lstlistlistingname
. 171, 237, 316, 389
\ltx@th 565, 566
\luatexversion 8, 44
M
\mathchar 105
\mathop 557, 558,
559, 560, 561,
562, 567, 569, 570
\mathrm 574,
575, 576, 577, 578
\mathsf 571, 572
\mddefault 546, 548, 550
\mdqoff 101
\mdqon 101
\MessageBreak 3, 51, 52
\month 417, 432, 448, 463
N
\newif 7
\nfss@text 537
\No 536
\nobreak 114, 116, 122,
130, 133, 135, 140
\nobreakspace 179, 180
\NOD 576, 582
\nod 574, 580
\noextrasrussian
. 481, 484, 486
\NOK 577, 583
\nok 575, 581
\nolimits 557, 558,
559, 560, 561,
562, 567, 569,
570, 571, 572,
574, 575, 576,
577, 578, 580,
581, 582, 583, 584
\nomname 176, 178,
238, 240, 317, 390
\notesname
. 172, 242, 318, 391
\number 417,
430, 432, 445,
448, 461, 463, 476
O
\operator@font
. 557, 558,
559, 560, 561,
562, 567, 569, 570
\or 417, 418,
419, 420, 421,
422, 423, 424,
425, 426, 427,
428, 432, 433,
434, 435, 436,
437, 438, 439,

440, 441, 442,	R	\space 138, 369, 430, 445, 461, 476
443, 448, 449,		\string 138
450, 451, 452,		
453, 454, 455,		
456, 457, 458,		
459, 463, 464,		
465, 466, 467,		
468, 469, 470,		
471, 472, 473,		
474, 488, 489,		
490, 491, 492,		
494, 495, 496,		
497, 498, 501,		
502, 503, 504,		
505, 507, 508,		
509, 510, 511,		
516, 517, 518,		
519, 520, 522,		
523, 524, 525, 526		
	P	
\PackageError 3		\r 74, 75
\PackageInfo . . 138, 530		\Received@name 202, 260, 334, 407
\PackageWarning 50, 84, 95		\refname 145, 211, 273, 344
\pagedeclaration . . 180		\relax 5, 55, 71
\pagename 164, 230, 307, 380		\RequirePackage 538
\partname 160, 226, 303, 376		\reserved@a 87, 88, 89, 90, 91, 92, 93, 94, 104, 107
\penalty 133		\Revised@name 203, 261, 335, 408
\prefacename 144, 210, 271, 342		\rmdefault 541, 544, 548, 555
\Prob 571		\Russian 58
\Proj 578, 584		\russian 58
\proofname 167, 233, 310, 383		\russian@Alph 499, 501, 507
\providehyphenmins 478, 479		\russian@alph 514, 516, 522
\Published@name 205, 263, 337, 410		\russian@sh@emdash . 119, 123
	Q	\russian@sh@hyphen . 120, 122
\quotedblbase 108		\russian@sh@next 119, 121
		\russian@sh@tmp 118, 121
		\russianhyphenmins . . 62
	S	
		\sce@a . . 15, 22, 23, 24, 25, 26, 27, 29, 30, 36
		\sce@b 16, 18, 37
		\sce@c 17, 18, 19, 38
		\seename 165, 231, 308, 381
		\selectfont 60, 66, 78, 487, 493
		\selectlanguage 58
		\set@hyphenmins . . 62, 68
		\SetMathAlphabet 552, 554
		\SetSymbolFont 540
		\sfdefault 546, 553
		\sh 557
	T	
		\space 138, 369, 430, 445, 461, 476
		\tablename 159, 225, 302, 375
		\tablesname 195, 253, 327, 400
		\tempa@ 125, 126
		\tempb@ 125, 127
		\tempc@ 125, 128
		\tempx@ 124, 126, 127, 128
		\textcyrillic 81
		\textnumero 537
		\textormath 113, 116, 566
		\textquotedblleft . . 109
		\tg 559
		\th 564, 565, 566
		\tocname 153, 219, 288, 358
		\today . . 417, 432, 448, 463
		\ttdefault 550
		\tw@ 478, 479
	U	
		\undefined 136
		\unskip 130, 132
		\updefault 541, 544, 546, 550, 553
	V	
		\Variance 572
	X	
		\XeTeXrevision 9, 42
	Y	
		\year 430, 445, 461, 476
	Z	
		\z@ 130, 132, 571, 572
		\z@skip 112, 114, 133