

# The file `greek.fdd` for use with $\text{\LaTeX} 2_{\epsilon}$ .\*

Claudio Beccari, Apostolos Syropoulos and Johannes Braams

2001/01/30

## 1 Introduction

The file ‘`greek.fdd`’ provides font definitions for typesetting greek texts. This version of the file has been updated, since now the official fonts for the `greek` option of the `babel` package are the `cb` fonts.

## 2 The `docstrip` modules

The following modules are used to direct `docstrip` in generating external files:

<code>driver</code>	produce a documentation driver file
<code>LGRenc</code>	The encoding definition file
<code>LGRcmr</code>	The Roman font shapes
<code>LGRcmro</code>	The Outline Roman font shapes
<code>LGRcmss</code>	The Sans Serif font shapes
<code>LGRcmmt</code>	The typewriter font shapes
<code>LGRlcmss</code>	The slide size Sans Serif font shapes
<code>LGRlcmmt</code>	The slide size typewriter fonts

A typical `DOCSTRIP` command file would then have entries like:

```
\generateFile{lgrcmr.fd}{t}{\from{greek.fdd}{fd,LGRcmr}}
```

## 3 The encoding definition file

This file defines the fontencoding `LGR` for greek text. Moreover, it provides the `\EC@family` macro, since the Greek fonts have the same naming conventions as the Latin ones produced by Jörg Knappen that are now the official fonts of  $\text{\LaTeX} 2_{\epsilon}$ . It also makes some definitions to ensure that commands such as `\TeX`, `\copyright` give “expected results” ( $\text{\TeX}$ , ©).

```
1 <(*fd)
2 \providecommand{\EC@family}[5]{%
3   \DeclareFontShape{#1}{#2}{#3}{#4}
4     {<5><6><7><8><9><10><10.95><12><14.4>%
5       <17.28><20.74><24.88><29.86><35.83>genb*#5}{}}
6 </fd>
7 <(*LGRenc)
8 \DeclareFontEncoding{LGR}{}{}
9 \DeclareFontSubstitution{LGR}{cmr}{m}{n}
10 \DeclareErrorFont{LGR}{cmr}{m}{n}{10}
```

First we define a few commands in the `LGR` encoding.

```
11 \ProvideTextCommand{\textcopyright}{LGR}{%
12   \textcircled{\textlatin{c}}}%
13 \ProvideTextCommand{\textregistered}{LGR}{%
```

---

\*This file has version number v2.2e, dated 2001/01/30.

```

14 \textcircled{\textlatin{\textsc r}}}
15 \ProvideTextCommand{\texttrademark}{LGR}{%
16 \textsuperscript{\textlatin{TM}}}
17 \ProvideTextCommand{\SS}{LGR}{%
18 \textlatin{SS}}
19 \LGRenc

```

## 4 The font definition files

In the previous release of the greek option we used the `kd` family of fonts, which were made by K.J. Dryllerakis. Now, we have switched to the `cb` fonts by Claudio Beccari, mainly because these fonts are complete, in any sense of the word, and moreover fit nicely with the Computer Modern font family.

We begin with the definitions for the Greek Computer Modern fonts.

```

20 (*LGRcmr)
21 \DeclareFontFamily{LGR}{cmr}{}
22 \EC@family{LGR}{cmr}{m}{n} {grmn}
23 \EC@family{LGR}{cmr}{m}{sl} {grmo}
24 \EC@family{LGR}{cmr}{m}{it} {grmi}
25 \EC@family{LGR}{cmr}{m}{sc} {grmc}
26 \EC@family{LGR}{cmr}{m}{ui} {grmu}
27 \EC@family{LGR}{cmr}{bx}{sc} {grxc}
28 \EC@family{LGR}{cmr}{bx}{n} {grxn}
29 \EC@family{LGR}{cmr}{bx}{sl} {grxo}
30 \EC@family{LGR}{cmr}{bx}{it} {grxi}
31 \EC@family{LGR}{cmr}{bx}{ui} {grxu}
32 \DeclareFontShape{LGR}{cmr}{b}{n}
33 {<->ssub*cmr/bx/n}{}
34 \DeclareFontShape{LGR}{cmr}{b}{sc}
35 {<->ssub*cmr/bx/sc}{}
36 \LGRcmr

```

The greek outline family is now complete with the same five shapes and the two series as the roman family.

```

37 (*LGRcmro)
38 \DeclareFontFamily{LGR}{cmro}{}
39 \EC@family{LGR}{cmro}{m}{n} {gomn}
40 \EC@family{LGR}{cmro}{m}{sl} {gomo}
41 \EC@family{LGR}{cmro}{m}{it} {gomi}
42 \EC@family{LGR}{cmro}{m}{sc} {gomc}
43 \EC@family{LGR}{cmro}{m}{ui} {gomu}
44 \EC@family{LGR}{cmro}{bx}{sc} {goxc}
45 \EC@family{LGR}{cmro}{bx}{n} {goxn}
46 \EC@family{LGR}{cmro}{bx}{sl} {goxo}
47 \EC@family{LGR}{cmro}{bx}{it} {goxi}
48 \EC@family{LGR}{cmro}{bx}{ui} {goxu}
49 \DeclareFontShape{LGR}{cmro}{b}{n}
50 {<->ssub*cmro/bx/n}{}
51 \DeclareFontShape{LGR}{cmro}{b}{sc}
52 {<->ssub*cmro/bx/sc}{}
53 \LGRcmro

```

Then we have the typewriter fonts...

```

54 (*LGRcmtt)
55 \DeclareFontFamily{LGR}{cmtt}{\hyphenchar\font\m@ne}% \hyphenchar = -1
56 \EC@family{LGR}{cmtt}{m}{n} {gttn}
57 \EC@family{LGR}{cmtt}{m}{sl} {gtto}
58 \EC@family{LGR}{cmtt}{m}{sc} {gttc}
59 \EC@family{LGR}{cmtt}{m}{it} {gtti}
60 \EC@family{LGR}{cmtt}{m}{ui} {gttu}
61 \DeclareFontShape{LGR}{cmtt}{b}{n}

```

```

62      {<->ssub*cmmt/m/n}{ }
63 \DeclareFontShape{LGR}{cmmt}{bx}{sl}
64      {<->ssub*cmmt/m/sl}{ }
65 \DeclareFontShape{LGR}{cmmt}{bx}{it}
66      {<->ssub*cmmt/m/it}{ }
67 \DeclareFontShape{LGR}{cmmt}{bx}{sc}
68      {<->ssub*cmmt/m/sc}{ }
69 \DeclareFontShape{LGR}{cmmt}{bx}{ui}
70      {<->ssub*cmmt/m/ui}{ }
71 /LGRcmmt)

```

Now we come to the Sans Serif font to be used in greek texts.

```

72 (*LGRcmss)
73 \DeclareFontFamily{LGR}{cmss}{ }
74 \EC@family{LGR}{cmss}{m}{n}      {gsmn}
75 \EC@family{LGR}{cmss}{m}{sl}     {gsmo}
76 \EC@family{LGR}{cmss}{m}{sc}     {gsmc}
77 \EC@family{LGR}{cmss}{m}{it}     {gsmi}
78 \EC@family{LGR}{cmss}{m}{ui}     {gsmu}
79 \EC@family{LGR}{cmss}{bx}{n}     {gsxn}
80 \EC@family{LGR}{cmss}{bx}{sl}    {gsxo}
81 \EC@family{LGR}{cmss}{bx}{sc}    {gsxc}
82 \EC@family{LGR}{cmss}{bx}{it}    {gsmi}
83 \EC@family{LGR}{cmss}{bx}{ui}    {gsmu}
84 /LGRcmss)

```

We have finished with the “regular” fonts. We now provide the fonts definition files for the fonts used only in slides. First comes the typewriter font.

```

85 (*LGRlcmmt)
86 \DeclareFontFamily{LGR}{lcmmt}{\hyphenchar\font\m@ne}
87 \DeclareFontShape{LGR}{lcmmt}{m}{n}{%
88 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
89 genb * gltn}{ }
90 \DeclareFontShape{LGR}{lcmmt}{m}{In}{%
91 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
92 genb * gljn}{ }
93 \DeclareFontShape{LGR}{lcmmt}{m}{it}{%
94 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
95 genb * glto}{ }
96 \DeclareFontShape{LGR}{lcmmt}{m}{Iit}{%
97 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
98 genb * gljo}{ }
99 \DeclareFontShape{LGR}{lcmmt}{m}{sl}{%
100 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
101 ssub * lcmmt/m/it}{ }
102 \DeclareFontShape{LGR}{lcmmt}{m}{Isl}{%
103 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
104 ssub * lcmmt/m/Iit}{ }
105 \DeclareFontShape{LGR}{lcmmt}{m}{sc}{%
106 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
107 genb * gltc}{ }
108 \DeclareFontShape{LGR}{lcmmt}{m}{Isc}{%
109 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
110 genb * gljc}{ }
111 /LGRlcmmt)

```

And then the Sans Serif font.

```

112 (*LGRlcmss)
113 \DeclareFontFamily{LGR}{lcmss}{ }
114 \DeclareFontShape{LGR}{lcmss}{m}{n}{%
115 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
116 genb * glmn}{ }
117 \DeclareFontShape{LGR}{lcmss}{m}{In}{%
118 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>

```

```

119 genb * glin}{%
120 \DeclareFontShape{LGR}{lcmss}{m}{sl}{%
121 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
122 genb * glmo}{%
123 \DeclareFontShape{LGR}{lcmss}{m}{Is1}{%
124 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
125 genb * glio}{%
126 \DeclareFontShape{LGR}{lcmss}{m}{it}{%
127 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
128 genb * glmi}{%
129 \DeclareFontShape{LGR}{lcmss}{m}{Iit}{%
130 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
131 genb * glii}{%
132 \DeclareFontShape{LGR}{lcmss}{m}{ui}{%
133 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
134 genb * glmu}{%
135 \DeclareFontShape{LGR}{lcmss}{bx}{n}{%
136 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
137 genb * glxn}{%
138 \DeclareFontShape{LGR}{lcmss}{bx}{In}{%
139 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
140 genb * glwn}{%
141 \DeclareFontShape{LGR}{lcmss}{bx}{s1}{%
142 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
143 genb * glxo}{%
144 \DeclareFontShape{LGR}{lcmss}{bx}{Is1}{%
145 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
146 genb * glwo}{%
147 \DeclareFontShape{LGR}{lcmss}{bx}{it}{%
148 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
149 genb * glxi}{%
150 \DeclareFontShape{LGR}{lcmss}{bx}{Iit}{%
151 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
152 genb * glwi}{%
153 \DeclareFontShape{LGR}{lcmss}{m}{sc}{%
154 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
155 genb * glmc}{%
156 \DeclareFontShape{LGR}{lcmss}{m}{Isc}{%
157 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
158 genb * glic}{%
159 \DeclareFontShape{LGR}{lcmss}{bx}{sc}{%
160 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
161 genb * glxc}{%
162 \DeclareFontShape{LGR}{lcmss}{bx}{Isc}{%
163 <7><8><10><12><13.82><16.59><19.91><23.89><28.66><34.4><41.28>
164 genb * glwc}{%
165 \endinput

```

The next line goes into all files and in addition prevents DOCSTRIP from adding any further code from the main source file (such as a character table.

```
166 \endinput
```