

dowith.sty

Apply Command to Each Item in a List of Arguments in “T_EX’s Mouth”*

Uwe Lück[†]

May 18, 2012

Abstract

This package provides macros for applying a “command” to all items in a “list of possible macro arguments,” and also for extending and reducing macros storing such lists. “Brace groups” are single items of such lists, as opposed to token lists. Applications in mind belonged to L^AT_EX, but the package should work with other formats as well. Loop and list macros in other packages are discussed. Iteration is implemented within “T_EX’s mouth,” so works within `\write` as with `blog.sty`. There is no need for ε -T_EX.

Related packages: `etextools`, `etoolbox`, `forarray`, `forloop`, `multido`, `moredefs`, `lmake`, `texapi`, `xfor`, `xspace`

Keywords: programming structures; macro programming, loops, list macros

Contents

1	Usage and Features	2
1.1	Installing and Calling	2
1.2	What It Does With What Lists	2
1.3	The Notion of Arglists for L ^A T _E X Users	3
1.4	T _E X’s Tokens	4
1.5	Arglists vs. Lists of Tokens—Example	5
1.6	Another Notation and the Example’s Steps	6
1.7	Summary of Possible Arglist Items	7

*This document describes version [v0.21](#) of `dowith.sty` as of 2012/05/14.

[†]<http://contact-ednotes.sty.de.vu>

2	Similar Commands in other Packages	8
2.1	“Heavy” Packages	8
2.2	Separators	8
2.3	Iterators	8
2.4	“For” Loops vs. “Foreach” Loops	9
2.5	Separator Macros	9
2.6	Ye Olde <code>\loop</code>	10
2.7	Without Iterator and Separators	10
3	Implementation	11
3.1	Package File Header (Legalese)	11
3.2	Proceeding without <code>L^AT_EX</code>	11
3.3	Applying a Command	12
3.3.1	Core	12
3.3.2	<code>\do</code> being the Command	12
3.3.3	Expand List Macro	13
3.4	Handling List Macros	13
3.4.1	Initializing	13
3.4.2	Testing for Occurrence of a Token	14
3.4.3	Adding and Removing	14
3.5	Leaving and History	15

1 Usage and Features

1.1 Installing and Calling

The file `dowith.sty` is provided ready, installation only requires putting it somewhere where `TEX` finds it (which may need updating the filename data base).¹

With `LATEX`, you load `dowith.sty` (as usually) by

```
\usepackage{dowith}
```

below the `\documentclass` line(s) and above `\begin{document}`. However, the package can also be used with other formats, just

```
\input dowith.sty
```

The single commands that the package provides are described below together with their implementation.

1.2 What It Does With What Lists

The term ‘list’ may refer to various things and need clarification here.

First of all, we are not referring to `LATEX` `list` environments such as `enumerate` or `itemize`; neither to “TODO” lists of what needs to be done soon.

¹<http://www.tex.ac.uk/cgi-bin/texfaq2html?label=inst-wlcf>

Rather, `dowith` allows you to abbreviate

$$\langle cmd \rangle \langle arg-1 \rangle \langle cmd \rangle \langle arg-2 \rangle \dots \langle cmd \rangle \langle arg-n \rangle$$

by

$$\backslash DoWith \langle cmd \rangle \langle arg-1 \rangle \langle arg-2 \rangle \dots \langle arg-n \rangle \backslash StopDoing$$

or by

$$\backslash DoWithAllOf \langle cmd \rangle \{ \langle arg-1 \rangle \langle arg-2 \rangle \dots \langle arg-n \rangle \}$$

With small n , one may doubt whether this really is an abbreviation ...; anyway,

$$\langle arg-1 \rangle \langle arg-2 \rangle \dots \langle arg-n \rangle$$

was an attempt to refer to the kind of lists we are dealing with.

$$\langle arg-1 \rangle, \langle arg-2 \rangle, \dots, \langle arg-n \rangle$$

are the “items” of the list. The question is: what counts as an item?

We might say that `aa` is a list of *two* items, $\langle arg-1 \rangle$ being `a` and $\langle arg-2 \rangle$ being `a`, too.

When we do *three* keystrokes to get `a_a` instead of `aa`, we still have *two* items, $\langle arg-1 \rangle$ being `a` and $\langle arg-2 \rangle$ being `a` too. Strange, isn’t it?

Also, when in `aa` we replace the first `a` by a backslash, `\`, we get `\a`, and this is a list of a *single* item, $\langle arg-1 \rangle = \backslash a$...

You shouldn’t believe these stories of mine entirely. What I am alluding to is that the “*items*” `dowith` is about are determined in terms of $T_{E}X$ ’s *tokens*, and the relation between the “characters you type” and $T_{E}X$ ’s *tokens* is not entirely straightforward.

1.3 The Notion of Arglists for \LaTeX Users

Still, it may suffice to clarify what counts as an $\langle arg-i \rangle$ without speaking of *tokens* explicitly: It is simply what a *one-parameter macro* (where the parameter is *not delimited* in terms of *The T_EXbook* pp. 203f.) can take as an *argument*.

The lists `dowith` is about then are lists of *possible arguments* in the previous sense—let me call them “*arglists*.”² The single *items* of such lists are those single possible arguments. They become *actual* arguments beginning from the leftmost *possible* one when `dowith` presents them to that $\langle cmd \rangle$ mentioned earlier—where $\langle cmd \rangle$ *should* be a one-parameter macro (or some $T_{E}X$ primitive parsing arguments similarly).

The reader perhaps has an *intuitive* understanding of what can be an argument of a one-parameter macro. A *strict* \LaTeX user may think that such an argument $\langle arg-i \rangle$ just has form $\{ \langle ark-i \rangle \}$, i.e., $\langle arg-i \rangle = \{ \langle ark-i \rangle \}$ for some $\langle ark-i \rangle$. Such arguments are also called “*brace groups*”. (\LaTeX ’s *optional* arguments [*extra*]) do not count as possible arguments here, they are not macro

²Not to be confused with German Arglist.

arguments in the sense of *The T_EXbook*.) In this restricted L^AT_EX sense, arglists consist of brace groups

$$\{\langle ark-1 \rangle\} \{\langle ark-2 \rangle\} \dots \{\langle ark-n \rangle\},$$

and each single brace group is an *item* of it.

The *T_EX macro writer*, by contrast, knows that a macro argument doesn't need outer braces. In an intuitive sense, a single “command” can be a macro argument, too. “Command” may be understood as “control sequence” (starting with a backslash), but some authors also have considered single *characters* (character *tokens*?) “commands.” Blank spaces, by contrast, are ignored when a macro looks for its argument.

1.4 T_EX's Tokens

What T_EXnically matters is what happens in “T_EX's mouth,”³ as some authors have suggested a metaphor,⁴ or somewhere deeper. The *dowith* package is a tool to control those events (and actually, it is confined to T_EX's mouth).

The “characters you type” are somewhere in front of “T_EX's mouth”, while *in* T_EX's mouth, there are *tokens*. Before T_EX *swallows* them, it often manipulates them in some ways, after they got *into* its mouth.

More formally, T_EX has a *character buffer*. It forms a single token from an initial segment of the buffer content—unless there is a special situation with blank spaces or something pathological. When an *escape character*, as the backslash usually is one, has been noticed recently (that isn't followed by another one immediately), the character buffer may need to be feeded from more outside, until it contains enough material to form a token from. The character(s) *after* the escape character until some delimiting character form a *string* that is the *name* of the token that is formed. What has been used to form a token is removed from the character buffer.

There are *two kinds of tokens* here: *named tokens* and *character tokens*. “Named” tokens usually are referred to as “control sequence tokens” or just “control sequences”—I really want to avoid those horrible confusions from *The T_EXbook*. There never are any “parameter tokens” in T_EX's mouth (perhaps unless one considers a one-step macro expansion a two-or-more-step procedure).

For every *string of characters*, there is exactly one (possible) *named token* whose name the string is.⁵ It is so common (starting from *The T_EXbook*) to denote the token whose name is $\langle string \rangle$ by ‘\($\langle string \rangle$)’. For instance, the token whose name is *input* is denoted by ‘\input’. On the other hand, on page 7 of *The T_EXbook* ‘\input’ is a “string of characters.” With this notation, it is already difficult to explain what the L^AT_EX command `\DeclareRobustCommand` does or what the difference between a starred L^AT_EX command and a starred L^AT_EX environment is.⁶ *The T_EXbook* makes it worse by saying on page 39: “A control sequence is considered to be a single object that is no longer composed of a sequence of symbols.” So “it depends” whether ‘\input’ is a string of characters or not—it *is before* tokenization, but *no*

³Cf. *The T_EXbook* p. 46.

⁴Alan Jeffrey: “Lists in T_EX's Mouth,” TUGboat Volume 11 No. 2 (1990), pp. 237–245), tug.org/TUGboat/tb11-2/tb28jeffrey.pdf.

⁵“Possible” refers to the fact that T_EX does not store named tokens anywhere before they appear in its mouth, maybe apart from “primitive” tokens that have a “pre-assigned meaning” when a T_EXrun starts.—What is more bad with my claim is that the T_EX program by design cannot extend its memory arbitrarily—even not using the “cloud”—, so it doesn't support tokens whose name lengths are above a certain limit.

⁶A reader knowing L^AT_EX only thinks that ‘__’ is the result of typing a double backslash and a space and that ‘\equation*’ is the “command” `\equation` followed by a *.

longer afterwards. So if you have two computers and start a T_EX run on each of them with a little difference in time, there will be a moment where ‘\input’ is a string on the one computer but not on the other? This is like saying “When we apply the square root function to the number 4, the number 4 will no longer be the number 4, it will be the number 2 instead.”

The *T_EXbook* does offer an alternative notation for named tokens: “boxing;” so the token whose name is `input` can be denoted by the rather “graphical” notation ‘`\input`’ (used only exceptionally).⁷ I would suggest something like ‘`\ntok(input)`’ for clarity and ‘`?input`’ for brevity.⁸

Character tokens get into T_EX’s mouth by tokenization when characters begin the buffer content while *not* scanning a name for a named token. A single character then is removed from the character buffer, and a token storing its character code and current category code is pushed into T_EX’s mouth.

Named tokens may get into T_EX’s mouth by “tokenization” as described above, i.e., they are drawn from the character buffer. But they also can appear in T_EX’s mouth “from within,” by the manipulation inside T_EX’s mouth.

More formally, those manipulations are called “expansion,” and T_EX’s mouth can be conceived of as a *token buffer* that is feeded to the right (or end) by tokenization from the character buffer. Expansion means that certain tokens in the token buffer are substituted by other ones. This way tokens may get into T_EX’s mouth that emerged from tokenization a “long time ago”, maybe in a previous run that created the *format* (T_EX’s variant INITEX); or tokens may appear by some hardwired expansion function.

However, *named tokens* may get into T_EX’s mouth also by *expansion*, never having been drawn by tokenization and not being hardwired. This happens by the `\csname` name construct. The input *code* may contain

```
\csname\tupni\endcsname
```

This may be converted into 7 tokens entering T_EX’s mouth, the first one being `\ntok(csname)`, the last one `\ntok(endcsname)`, and five character tokens in between. Due to some *function* (which I would denote as `*csname`) originally associated with the token `\ntok(csname)`, those seven tokens then are replaced by `\ntok(tupni)`, the named token whose name is `tupni`. It is not required that the T_EX program knows about a token `\ntok(tupni)`, neither anybody must type ‘`\tupni`’ in any file.⁹

1.5 Arglists vs. Lists of Tokens—Example

Let us reconsider the examples from Sections 1.2 and 1.3, and pack them into a single example. If you type a file line

```
a_a\{a}
```

(1)

(*eight* keystrokes), it should usually be converted into this *seven*-item list of (five) tokens:

```
a_11 \_10 a_11 \ntok(a) {_1 a_11 }_2
```

(2)

⁷The box notation is introduced on page 38 without explanation, as if it explained something.

⁸I am suggesting the question mark for named tokens since T_EX “must look up the current definition” of a named token according to *The T_EXbook* p. 39, while the meaning of character tokens rather is “fixed,” at least according to *The T_EXbook* p. 39. However, *active*-character such as `.` are in the same situation as named tokens as to this respect. The dot notation may be fine for them, though.

⁹These considerations may not be essential here, rather a draft for a paper. Using `\dowith`, one better just thinks of the arglist items one actually lists.

—with notation from Section 1.4 and *The T_EXbook*’s notation $\langle char \rangle_{\langle cat \rangle}$ for the *character token* that T_EX’s tokenizer forms from $\langle char \rangle$ in the character buffer when $\langle char \rangle$ ’s category code is $\langle cat \rangle$.

It turns out that the token list in 2 provides an arglist of *four* items: The token `a11` at the first and third place, the named token `ntok(a)`, and the entire token list $\{_1 a_{11}\}_2$ as a single item—a “brace group.” The space token is ignored.¹⁰

You can try this after `\renewcommand{\a}{A}`¹¹ with `dowith`:

$$\backslash\mathrm{DoWith}\backslash\mathrm{typein}_a_a\backslash a\{a\}\backslash\mathrm{StopDoing} \quad (3)$$

Then L^AT_EX shows `a`, `a`, `A` from `\a`, and another `a` from within the braces—`\typein` (as any macro with arguments) removes them.

I have avoided saying 2 *were* an arglist of 4 items. The mathematical basic way of writing lists—understood as finite *sequences*—as “comma-separated lists” within brackets may clarify the difference (that the juxtaposition notation tends to conceal). The *token* list is

$$(a_{11}, _10, a_{11}, \mathrm{ntok}(a), \{_1, a_{11}, \}_2) \quad (4)$$

while the list of macro arguments is

$$(a_{11}, a_{11}, \mathrm{ntok}(a), (\{_1, a_{11}, \}_2)). \quad (5)$$

2 or 4 simply is *not* an arglist (since neither $\{_1$ nor $\}_2$ can be a macro argument), and the arglist 5 “provided” by the list of tokens is *not* a list of *tokens*—its final item is a three-item list of tokens, and a token cannot be a list of two or more tokens itself(!?).

1.6 Another Notation and the Example’s Steps

To write token lists easier and hopefully easier to read, I would suggest writing ‘ $\langle char \rangle$ ’ for the character token that the tokenizer “usually” forms from character $\langle char \rangle$, i.e., adding the *standard* category code as in *The T_EXbook* (page 37). Then 2 would read¹²

$$.a._a?a.\{.a.\} \quad (6)$$

and the corresponding arglist is

$$(.a., .a., ?a., \{.a.\}) \quad (7)$$

In “retrospect,” the result of tokenizing 2 should be

$$?\mathrm{DoWith}?\mathrm{typein}.a._a?a.\{.a.\}?\mathrm{StopDoing} \quad (8)$$

and the intention is that it works like

$$?\mathrm{typein}.a?\mathrm{typein}.a?\mathrm{typein}?a?\mathrm{typein}\{.a.\} \quad (9)$$

¹⁰*The T_EXbook* p. 201: “T_EX doesn’t use single spaces as undelimited arguments.”

¹¹Otherwise `\a` is a one-parameter macro that breaks `dowith`’s control.

¹²See Section 1.4 for the question mark.

However, \TeX rather tries to work with as few tokens ahead as possible. When it finds `?DoWith` and the latter's meaning is the one intended by `dowith`, it first looks for nothing more than the two arguments required by our definition of `\DoWith`. A few moments later, the token buffer's content will just be¹³

`?typein.a?expandafter?DoWith?expandafter?typein?fi` (10)

Next `?typein.a` is expanded according to the code for `\typein` in `latex.ltx`. Some unexpandable tokens will emerge and be moved into the “command buffer,” and you should get a screen message with `a` and a prompt. When you have entered something, the remaining `?expandafter` tokens and the `?fi` will be removed from the character buffer, and it contains only

`?DoWith?typein` (11)

Another token is ordered from the tokenizer to provide a second argument for expanding `?DoWith`. The token `␣` comes in, but that doesn't serve as a macro argument. It is removed, and the next token is `.a`. The same story as before happens, until the named token `?a` is found ...

1.7 Summary of Possible Arglist Items

For $0 \leq i \leq 15$, let X_i be the set of character tokens of category code i . X_1 is the set of tokens working like $\{1$, and X_2 is the set of tokens working like $\}$.

Let E be the set $\{3, 4, 6, 7, 8, 11, 12, 13\}$. These numbers are the category codes for *math*, *align*, *parameter*, *super*, *sub*, *letter*, *other*, *active* respectively. Let X_E be the set of character tokens of category code in E (so $X_E = \bigcup_{i \in E} X_i$).

Let \circ be the *concatenation* operation among token lists.¹⁴

The following kinds of token lists form a single arglist item, i.e., can serve as an argument for an undelimited parameter:

1. a *named* token, or the single-token list consisting of it, if you prefer that;
2. a *character* token from X_E or the list consisting of it;
3. a *brace group*. That is a token list meeting the following conditions: (i) its *first* token is in X_1 , (ii) its *last* token is in X_2 , (iii) it has as many occurrences of tokens from X_1 as from X_2 , (iv) if it is split as $\lambda \circ \rho$, there are not more X_2 occurrences in λ than X_1 occurrences in ρ (“don't close before opening”).

The second claim can be checked with

`\DoWith\typein$#^_a1^\StopDoing` (12)

as to what works. (The claim is not affected by one or two surprises.)¹⁵ Characters with different category codes either are not converted into a character token¹⁶ or are not accepted as macro arguments. The latter applies to “brace” tokens in X_1 , X_2 and to the single space token $_10$.

As to “*brace groups*”, the third and fourth condition above are intended to say that what is between the two outer tokens is ⟨balanced text⟩ in the sense of *The \TeX book* pp. 275f.

¹³If you use `\DoWithAll10f\typein{a␣a{a}}` instead, the entire token sequence 8 will appear in the token buffer “at once.”

¹⁴TODO: Define for representations by maps, or: “Concatenation is about as basic as natural numbers and is understood in terms of axioms rather than by a definition.”—See notes from 2011 (even with attempts with Category theory) the English Wikipedia for sequences—German article too much restricted to maps.

¹⁵Moreover, `\DoWith\typein#1\StopDoing` tells something about “parameter tokens.”

¹⁶*The \TeX book* p. 47.

and 385; i.e., for two tokens a , b and a token list β , $(a) \circ \beta \circ (b)$ is a brace group exactly if a is from X_1 , b is from X_2 , and β is (balanced text). The conditions are more formal than what I can find in *The TeXbook*, but still they don't give me an idea of all possibilities. This should be improved by the following recursive definition:

B1. The empty list is balanced text. B2. For any token t not in X_1 or X_2 , the single-item token list (t) is balanced text. (Such a token is either a *named* token or a *character* token from X_E or the *space token* `_10`.) B3. If α and β are balanced texts, then $\alpha \circ \beta$ is balanced text. B4. If β is balanced text, a is from X_1 , and b is from X_2 , then $(a) \circ \beta \circ (b)$ is balanced text. (This is a brace group, and the only way of getting a brace group.) B5. Nothing else is balanced text.

In other words, a token list is a brace group if and only if it is balanced text and starts with a token from X_1 and ends with a token from X_2 .¹⁷

2 Similar Commands in other Packages

2.1 “Heavy” Packages

The ε -TeX-related packages `etextools` (Florent Chervet), `etoolbox` (Philipp Lehman), and `texapi` (Paul Isambert) seem to include and (very much) extend the functionality of `dowith`. Also the `\ForEach...` macros of `forarray` (Christian Schröppel) seem to extend the present `\DoWith...` commands. `moredefs` (Matt Swift) provides list handling commands like the few that are here.¹⁸ (I do not want to load that much.)

2.2 Separators

Regarding L^AT_EX macros in `latex.ltx`, the basic macro `\DoWith` of the present package resembles `\@tfor` very much, which likewise deals with lists without separators. By contrast, L^AT_EX's `\@for` deals with *comma-separated* lists (such as lists of package options). With comma-separated lists, a “string” of characters counts as an item when it is delimited by commas, or by a comma and the list “border”, or spaces may be used as separators additionally. However, when L^AT_EX analyzes such lists (in “T_EX's mouth”), it uses representations by *character tokens* of them.

The more recent `lmake` (Shengjun Pan) provides a key-value syntax for printing lists of complex mathematical expressions easily (using some assignments) as well as defining commands according to a pattern from a list. Those lists are comma-separated.

2.3 Iterators

A major difference between `\DoWith` and `\@tfor` is that the latter uses a “loop variable” or rather “iterator” to which the elements of the list are assigned. `\DoWith{cmd}` does not use such a loop variable or such assignments and thus

¹⁷ Again, this may be more of a draft for a paper, or notes for it, than package documentation.

¹⁸ `arrayjobx` provides somewhat “exotic” handling of “lists”.

is “expandable” at least when $\langle cmd \rangle$ (and the elements, depending on $\langle cmd \rangle$) are expandable. On the other hand, `\@tfor` applies some procedure to the list elements without needing a *name* for the procedure (or a *macro* storing the procedure).

“Expandability” is essential especially within `\write`. Assignments do not work there. A major motivation for developing `dowith` developed with the `blog` package that `\writes` HTML code. Assignments happen somewhere *behind* “TeX’s mouth.” That place might be called the “command buffer” to which the “expansion processor” moves items from the incoming token buffer that cannot be expanded (any more).

2.4 “For” Loops vs. “Foreach” Loops

What about `forloop` (Nick Setzer), `multido` (Timothy Van Zandt, Rolf Niepraksch, Herbert Voß), and `xfor` (Nicola Talbot)?

`xfor` is just a reimplementaion of `\@for`. `forloop` and `multido` are more close to “real ‘for’ loops” (cf. *Wikipedia*). Loops of the latter kind go through a certain set as well, but such sets rather consist of *numbers* and are exhausted by incrementing (or also decrementing) variables (counters). This is essentially not needed when a list literally is *enumerated*—such loops are distinguished as “foreach loops.” I wondered whether behind L^AT_EX’s `\@tfor` (and `\@for`) there was an “ideological” consideration such as “A loop must have a loop variable!” However, avoiding usage of a macro name (to store the “loop body” code) and a macro parameter (to incorporate the list item into the body code) may have been a good reason.

2.5 Separator Macros

Commands like `\DoWith` also could save tokens thinking of list macros (in L^AT_EX/`latex.ltx`) that use a *separator macro* which may be used as a *command* to be applied to the list elements. One example is `\dospecials` that already is in Plain T_EX and expands to

```
\do\_\do\\\do\{\do\}\do\$\do\&\do\#\do\^\do\_ \do\%\do\~
```

An important application of `\dospecials` is temporarily switching off the “special” functionality of the “elements” in `\dospecials`. With L^AT_EX, this may happen thus:

```
\let\do\@makeother\dospecials
```

With `dowith`, you can do the same with a shorter variant `\specials` of `\dospecials`, defined by

```
\def\specials{\_\{\}\$\&\#\^\\_ \%\~}
```

and then

```
\DoWithAllIn\@makeother\specials
```

`latex.ltx` uses `\@elt` instead of `\do` for its own list macros.

2.6 Ye Olde `\loop`

There also is `\loop<loop-body>\repeat` in Plain `TEX` and a refined version of it in `latex.ltx`. It is *not* expandable since it starts with an assignment for `\body` (Plain `TEX`) or `\iterate` (`latex.ltx`). As to the programming structure, it is so simple and general that you cannot immediately see what kind of loops it addresses. However, the applications I have seen have been “for” or (rather) “while” loops. “While” loops can “emulate” “for” and “foreach” loops by having the “incrementation” method or the “enumeration” method in their body. This is quite obvious for “for” loops, not quite so for “foreach” loops; which for practical application (in my view) means that neither `LATEX`/`TEX`’s `\loop` macro nor in general “while” loops is/are very helpful for implementing “foreach” loops, as rather `\DoWith` and similar constructions are. The reason for this is (as it seems to me) is that you (a human being) can much more easily enumerate (“list”) the items of a list (you have in mind) than define the *method* that (allegedly) is behind your enumeration. *Example:*

```
\DoWithAllOf{\printsamplearea}{\red\green\blue}
```

—*how* (according to what “method”?) did you “proceed” from `\red` to `\green` and from `\green` to `\blue`?

2.7 Without Iterator and Separators

In `LATEX`’s tools bundle, `xspace` was developed in the nineties by David Carlisle. It had a rather fixed exception list implemented by a deeply nested conditional. In 2004 Morton Høgholm joined, and now `xspace` has a list macro `\@xspace@exceptions@tlp` without separators. It is handled like here, except that it “breaks” the loop when an item is found that applies. After the “next” token is stored by the usual `\futurelet`, the exception list is searched without using an iterator. Addition and removal commands are provided as well.

3 Implementation

3.1 Package File Header (Legalese)

```

1 \def\filename{dowith} \def\fileinfo{simple list loop (UL)}
2 \def\filedate{2012/05/14} \def\fileversion{v0.21}
3 %% Copyright (C) 2011 Uwe Lueck,
4 %% http://www.contact-ednotes.sty.de.vu
5 %% -- author-maintained in the sense of LPPL below --
6 %%
7 %% This file can be redistributed and/or modified under
8 %% the terms of the LaTeX Project Public License; either
9 %% version 1.3c of the License, or any later version.
10 %% The latest version of this license is in
11 %% http://www.latex-project.org/lppl.txt
12 %% We did our best to help you, but there is NO WARRANTY.
13 %%
14 %% Please report bugs, problems, and suggestions via
15 %%
16 %% http://www.contact-ednotes.sty.de.vu

```

3.2 Proceeding without L^AT_EX

A little L^AT_EX as in Bernd Raichle's `ngerman.sty`:

```

17 \chardef\atcode=\catcode'\@
18 \catcode'\@=11 % \makeatletter
19 \begingroup\expandafter\expandafter\expandafter\endgroup

```

I need `\ProvidesPackage` for `fileinfo`, my package version tools.

```

20 \expandafter\ifx\csname ProvidesPackage\endcsname\relax

```

When `\ProvidesPackage` is not defined, we provide a version of L^AT_EX's `\in@` (an old version that may wrongly claim to have found an occurrence of a sequence, but is correct for single tokens) for checking token list macros. L^AT_EX must not see `\ifin@` when it parses the `\ifx` conditional:

```

21 \expandafter\newif\csname ifin@\endcsname
22 \def\in@#1#2{%
23   \def\in@@##1##2##3\in@@{%
24     \ifx\in@@#2\in@false\else\in@true\fi}%
25   \in@@#2#1\in@\in@@}

```

`readprov` stops reading the file at `\Provides...`, therefore ...

```

26 \long\def\@gobble#1{} \expandafter\@gobble
27 \else
28 \expandafter\@firstofone
29 \fi
30 { \ProvidesPackage{\filename}[\filedate\space
31   \fileversion\space \fileinfo] }

```

3.3 Applying a Command

3.3.1 Core

`\DoWith{<cmd>}{<list>\StopDoing}` applies `<cmd>` to all elements of `<list>`. An element of `<list>` (after tokenizing) may be either a single token or a group `{<balanced>}`.

```
32 \def\DoWith#1#2{%
33     \ifx\StopDoing#2%
34         \else#1{#2}\expandafter\DoWith\expandafter#1\fi}
```

`\StopDoing` delimits the list:

```
35 \let\StopDoing\DoWith
```

... something arbitrary that is not expected to occur in a list. With

```
\let\StopDoing*
```

instead, the star would end lists.

`\DoWithAllOf{<cmd>}{<list>}` works like

```
\DoWith{<cmd>}{<list>\StopDoing :
```

```
36 \def\DoWithAllOf#1#2{\DoWith#1#2\StopDoing}
```

3.3.2 \do being the Command

When the `<list>` is worked at a single time in the T_EX run where assignments are possible, instead of introducing a new macro name for `<cmd>` you can use `\do` for `<cmd>` as a “temporary” macro and define it right before

```
\DoWith{\do}{<list>\StopDoing
```

However, we provide

```
\DoDoWith{<cmd>}{<list>\StopDoing
```

as a substitute for the former line that at least saves one token. For the definition of `\do`, we provide `\setdo{<def-text>}`. It works similarly to

```
\renewcommand{\do}[1]{<def-text>},
```

so `<def-text>` should contain a `#1`:

```
37 \def\setdo{\long\def\do##1}
```

With `\letdo<cmd>` that is provided next where `<cmd>` is defined elsewhere, you could type

```
\letdo<cmd>\DoDoWith<list>\StopDoing
```

It seems to me, however, that you better type

```
\dowith<cmd><list>\StopDoing
```

instead. So I provide `\letdo` although I consider it useless here. It is provided somewhat for the sake of “completeness,” thinking that it might be useful at other occasions such as preceding `\dospecials`.

```
38 \def\letdo{\let\do}
```

`\DoDoWith` has been described above:

```
39 \def\DoDoWith{\DoWith\do}
```

By analogy to `\DoWithAllOf`, we provide `\DoDoWithAllOf<list>`:

```
40 \def\DoDoWithAllOf{\DoWithAllOf\do}
```

3.3.3 Expand List Macro

The former facilities may be quite useless as such a `<list>` will not be typed at a single place in the source code, rather the items to run `<cmd>` on may be collected occasionally when some routines run. The elements may be collected in a macro `<list-macro>` expanding to `<list>`. So we provide

```
\DoWithAllIn{<cmd>}{<list-macro>}
```

(or `\DoWithAllIn<cmd><list-macro>`). There is no need to type `\StopDoing` here:

```
41 \def\DoWithAllIn#1#2{%
```

```
42 \expandafter\DoWith\expandafter#1#2\StopDoing}
```

`\DoDoWithAllIn<list-macro>` saves a backslash or token for `\do` as above in Sec. 3.3.2:

```
43 \def\DoDoWithAllIn{\DoWithAllIn\do}
```

3.4 Handling List Macros

3.4.1 Initializing

Here is some advanced `\let<cmd>\empty`, perhaps a little irrelevant for practical purposes. Both

```
\InitializeListMacro{<list-macro>}
```

and

```
\ReInitializeListMacro{<list-macro>}
```

attempt to “empty” `<list-macro>`, and when we don’t believe that \LaTeX has been loaded, both do the same indeed. Otherwise the first one complains when `<list-macro>` seems to have been used earlier while the second complains when `<list-macro>` seems *not* to have been used before:

```

44 \expandafter\ifx\cname @latex@error\endcsname\relax
45 \def\InitializeListMacro#1{\let#1\empty} %% not \@empty 2011/11/07
46 \let\ReInitializeListMacro\InitializeListMacro
47 \else
48 \def\InitializeListMacro#1{\@ifdefinable#1{\let#1\empty}}
49 \def\ReInitializeListMacro#1{%
50 \edef\@tempa{\expandafter\@gobble\string#1}%
51 \expandafter\@ifundefined\expandafter{\@tempa}%
52 {\@latex@error{noexpand#1undefined}\@ehc}%
53 {\let#1\empty}}
54 \fi

```

`\ToListMacroAdd{<list-macro>}{<cmd-or>}` appends `<cmd-or>` to the replacement token list of `<list-macro>`. `<cmd-or>` may either be tokenized into a single token, or it is some `{<balanced>}`.

```

55 \def\ToListMacroAdd#1#2{\DefExpandStart#1{#1#2}}
56 \def\DefExpandStart#1{\expandafter\def\expandafter#1\expandafter}

```

3.4.2 Testing for Occurrence of a Token

`\TestListMacroForToken{<list-macro>}{<cmd>}` sets `\in@true` when `<cmd>` occurs in `<list-macro>` and sets `\in@false` otherwise:

```

57 \def\TestListMacroForToken#1#2{%
58 \expandafter \in@ \expandafter #2\expandafter{#1}}

```

Indeed I removed an earlier `\IfTokenInListMacro`, now it's a kind of compromise between having a shorthand macro below and a generalization for users of the package.

3.4.3 Adding and Removing

`\FromTokenListMacroRemove{<list-macro>}{<cmd>}` removes the token corresponding to `<cmd>` from the list stored in `<list-macro>` (our parsing method does not work with braces):

```

59 \def\FromTokenListMacroRemove#1#2{%

```

I am not happy about defining *two* parser macros, but for now ...

```

60 \TestListMacroForToken#1#2%
61 \ifin@
62 \def\RemoveThisToken##1#2{##1}%
63 \expandafter \DefExpandStart
64 \expandafter #1\expandafter {%
65 \expandafter\RemoveThisToken #1}%

```

TODO warning otherwise?

```

66 \fi}

```

... but this only removes a single occurrence ...

```
\InTokenListMacroProvide{\list-macro}\{cmd\}
```

avoids multiple entries of a token by *not* adding anything when $\langle cmd \rangle$ already occurs in $\langle list-macro \rangle$ (again, this does not work with braces, try $\backslash in@{\{ }\{\{ }\}$).

```
67 \def\InTokenListMacroProvide#1#2{%
68     \TestListMacroForToken#1#2%
69     \ifin@ \else                %% TODO warning?
70     \ToListMacroAdd#1#2%
71     \fi}
```

3.5 Leaving and History

```
72 \catcode'\@=\atcode
73 \endinput
74
75 VERSION HISTORY
76 v0.1    2011/06/23/28  stored separately
77 v0.2    2011/11/02    simpler, documented
78         2011/11/03    corrected \if/\else for init
79         2011/11/07    \TestListMacroForToken, \InListMacroProvide;
80         doc.: \pagebreak, structure
81         2011/11/19    modified LaTeX supplements
82 v0.21   2012/05/14    fix for "generic" and 'typeoutfileinfo':
83         @ before ...!
84
```