

# The VPtoVF processor

(Version 1.6, January 2014)

	Section	Page
Introduction .....	1	202
Property list description of font metric data .....	5	203
Basic input routines .....	23	212
Basic scanning routines .....	36	216
Scanning property names .....	44	219
Scanning numeric data .....	59	227
Storing the property values .....	77	232
The input phase .....	91	237
Assembling the mappings .....	122	246
The checking and massaging phase .....	138	251
The TFM output phase .....	156	257
The VF output phase .....	175	262
The main program .....	180	264
System-dependent changes .....	182	265
Index .....	183	266

**1. Introduction.** The VPtoVF utility program converts virtual-property-list (“VPL”) files into an equivalent pair of files called a virtual font (“VF”) file and a TeX font metric (“TFM”) file. It also makes a thorough check of the given VPL file, so that the VF file should be acceptable to device drivers and the TFM file should be acceptable to TeX.

VPtoVF is an extended version of the program PLtoTF, which is part of the standard TeXware library. The idea of a virtual font was inspired by the work of David R. Fuchs who designed a similar set of conventions in 1984 while developing a device driver for ArborText, Inc. He wrote a somewhat similar program called PLFONT.

The *banner* string defined here should be changed whenever VPtoVF gets modified.

```
define banner ≡ 'This is VPtoVF, Version 1.6' { printed when the program starts }
```

**2.** This program is written entirely in standard Pascal, except that it has to do some slightly system-dependent character code conversion on input. Furthermore, lower case letters are used in error messages; they could be converted to upper case if necessary. The input is read from *vpl\_file*, and the output is written on *vf\_file* and *tfm\_file*; error messages and other remarks are written on the *output* file, which the user may choose to assign to the terminal if the system permits it.

The term *print* is used instead of *write* when this program writes on the *output* file, so that all such output can be easily deflected.

```
define print(#) ≡ write(#)
define print_ln(#) ≡ write_ln(#)

program VPtoVF(vpl_file, vf_file, tfm_file, output);
const { Constants in the outer block 3 }
type { Types in the outer block 23 }
var { Globals in the outer block 5 }
procedure initialize; { this procedure gets things started properly }
  var { Local variables for initialization 25 }
begin print_ln(banner);
  { Set initial values 6 }
end;
```

**3.** The following parameters can be changed at compile time to extend or reduce VPtoVF’s capacity.

```
{ Constants in the outer block 3 } ≡
buf_size = 60; { length of lines displayed in error messages }
max_header_bytes = 100; { four times the maximum number of words allowed in the TFM file header
block, must be 1024 or less }
vf_size = 10000; { maximum length of vf data, in bytes }
max_stack = 100; { maximum depth of simulated DVI stack }
max_param_words = 30; { the maximum number of fontdimen parameters allowed }
max_lig_steps = 5000; { maximum length of ligature program, must be at most 32767 - 257 = 32510 }
max_kerns = 500; { the maximum number of distinct kern values }
hash_size = 5003;
{ preferably a prime number, a bit larger than the number of character pairs in lig/kern steps }
```

This code is used in section 2.

**4.** Here are some macros for common programming idioms.

```
define incr(#) ≡ # ← # + 1 { increase a variable by unity }
define decr(#) ≡ # ← # - 1 { decrease a variable by unity }
define do_nothing ≡ { empty statement }
```

**5. Property list description of font metric data.** The idea behind VPL files is that precise details about fonts, i.e., the facts that are needed by typesetting routines like T<sub>E</sub>X, sometimes have to be supplied by hand. The nested property-list format provides a reasonably convenient way to do this.

A good deal of computation is necessary to parse and process a VPL file, so it would be inappropriate for T<sub>E</sub>X itself to do this every time it loads a font. T<sub>E</sub>X deals only with the compact descriptions of font metric data that appear in TFM files. Such data is so compact, however, it is almost impossible for anybody but a computer to read it.

Device drivers also need a compact way to describe mappings from T<sub>E</sub>X's idea of a font to the actual characters a device can produce. They can do this conveniently when given a packed sequence of bytes called a VF file.

The purpose of VPtoVF is to convert from a human-oriented file of text to computer-oriented files of binary numbers. There's a companion program, VFtoVP, which goes the other way.

*< Globals in the outer block 5 >* ≡  
*vpl\_file:* *text*;

See also sections 21, 24, 27, 29, 31, 36, 44, 46, 47, 52, 67, 75, 77, 82, 86, 89, 91, 113, 123, 138, 143, 147, 158, 161, 167, and 175.  
This code is used in section 2.

**6. < Set initial values 6 >** ≡  
*reset(vpl\_file);*

See also sections 22, 26, 28, 30, 32, 45, 49, 68, 80, 84, and 148.  
This code is used in section 2.

7. A VPL file is like a PL file with a few extra features, so we can begin to define it by reviewing the definition of PL files. The material in the next few sections is copied from the program PLtoTF.

A PL file is a list of entries of the form

```
(PROPERTYNAME VALUE)
```

where the property name is one of a finite set of names understood by this program, and the value may itself in turn be a property list. The idea is best understood by looking at an example, so let's consider a fragment of the PL file for a hypothetical font.

```
(FAMILY NOVA)
(FACE F MIE)
(CODINGScheme ASCII)
(DESIGNSIZE D 10)
(DESIGNUNITS D 18)
(COMMENT A COMMENT IS IGNORED)
(COMMENT (EXCEPT THIS ONE ISN'T))
(COMMENT (ACTUALLY IT IS, EVEN THOUGH
          IT SAYS IT ISN'T))
(FONTDIMEN
  (SLANT R -.25)
  (SPACE D 6)
  (SHRINK D 2)
  (STRETCH D 3)
  (XHEIGHT R 10.55)
  (QUAD D 18)
  )
(LIGTABLE
  (LABEL C f)
  (LIG C f O 200)
  (SKIP D 1)
  (LABEL O 200)
  (LIG C i O 201)
  (KRN O 51 R 1.5)
  (/LIG C ? C f)
  (STOP)
  )
(CHARACTER C f
  (CHARWD D 6)
  (CHARHT R 13.5)
  (CHARIC R 1.5)
  )
```

This example says that the font whose metric information is being described belongs to the hypothetical NOVA family; its face code is medium italic extended; and the characters appear in ASCII code positions. The design size is 10 points, and all other sizes in this PL file are given in units such that 18 units equals the design size. The font is slanted with a slope of  $-.25$  (hence the letters actually slant backward—perhaps that is why the family name is NOVA). The normal space between words is 6 units (i.e., one third of the 18-unit design size), with glue that shrinks by 2 units or stretches by 3. The letters for which accents don't need to be raised or lowered are 10.55 units high, and one em equals 18 units.

The example ligature table is a bit trickier. It specifies that the letter *f* followed by another *f* is changed to code '200, while code '200 followed by *i* is changed to '201; presumably codes '200 and '201 represent the ligatures 'ff' and 'ffi'. Moreover, in both cases *f* and '200, if the following character is the code '51 (which is

a right parenthesis), an additional 1.5 units of space should be inserted before the ‘51. (The ‘SKIP D 1’ skips over one LIG or KRN command, which in this case is the second LIG; in this way two different ligature/kern programs can come together.) Finally, if either f or ‘200 is followed by a question mark, the question mark is replaced by f and the ligature program is started over. (Thus, the character pair ‘f?’ would actually become the ligature ‘ff’, and ‘ff?’ or ‘f?f’ would become ‘fff’. To avoid this restart procedure, the /LIG command could be replaced by /LIG>; then ‘f?’ would become ‘ff’ and ‘f?f’ would become ‘fff’.)

Character f itself is 6 units wide and 13.5 units tall, in this example. Its depth is zero (since CHARDP is not given), and its italic correction is 1.5 units.

8. The example above illustrates most of the features found in PL files. Note that some property names, like FAMILY or COMMENT, take a string as their value; this string continues until the first unmatched right parenthesis. But most property names, like DESIGNSIZE and SLANT and LABEL, take a number as their value. This number can be expressed in a variety of ways, indicated by a prefixed code; D stands for decimal, H for hexadecimal, O for octal, R for real, C for character, and F for “face.” Other property names, like LIG, take two numbers as their value. And still other names, like FONTDIMEN and LIGTABLE and CHARACTER, have more complicated values that involve property lists.

A property name is supposed to be used only in an appropriate property list. For example, CHARWD shouldn’t occur on the outer level or within FONTDIMEN.

The individual property-and-value pairs in a property list can appear in any order. For instance, ‘SHRINK’ precedes ‘STRETCH’ in the example above, although the TFM file always puts the stretch parameter first. One could even give the information about characters like ‘f’ before specifying the number of units in the design size, or before specifying the ligature and kerning table. However, the LIGTABLE itself is an exception to this rule; the individual elements of the LIGTABLE property list can be reordered only to a certain extent without changing the meaning of that table.

If property-and-value pairs are omitted, a default value is used. For example, we have already noted that the default for CHARDP is zero. The default for every numeric value is, in fact, zero, unless otherwise stated below.

If the same property name is used more than once, VPtoVF will not notice the discrepancy; it simply uses the final value given. Once again, however, the LIGTABLE is an exception to this rule; VPtoVF will complain if there is more than one label for some character. And of course many of the entries in the LIGTABLE property list have the same property name.

9. A VPL file also includes information about how to create each character, by typesetting characters from other fonts and/or by drawing lines, etc. Such information is the value of the ‘MAP’ property, which can be illustrated as follows:

```
(MAPFONT D 0 (FONTNAME Times-Roman))
(MAPFONT D 1 (FONTNAME Symbol))
(MAPFONT D 2 (FONTNAME cmr10)(FONTAT D 20))
(CHARACTER O 0 (MAP (SELECTFONT D 1)(SETCHAR C G)))
(CHARACTER O 76 (MAP (SETCHAR O 277)))
(CHARACTER D 197 (MAP
  (PUSH)(SETCHAR C A)(POP)
  (MOVEUP R 0.937)(MOVERIGHT R 1.5)(SETCHAR O 312)))
(CHARACTER O 200 (MAP (MOVEDOWN R 2.1)(SETRULE R 1 R 8)))
(CHARACTER O 201 (MAP
  (SPECIAL ps: /SaveGray currentgray def .5 setgray)
  (SELECTFONT D 2)(SETCHAR C A)
  (SPECIAL ps: SaveGray setgray)))
```

(These specifications appear in addition to the conventional PL information. The MAP attribute can be mixed in with other attributes like CHARWD or it can be given separately.)

In this example, the virtual font is composed of characters that can be fabricated from three actual fonts, ‘Times-Roman’, ‘Symbol’, and ‘cmr10 at 20\u’ (where \u is the unit size in this VPL file). Character ‘0’ is typeset as a ‘G’ from the symbol font. Character ‘76’ is typeset as character ‘277’ from the ordinary Times font. (If no other font is selected, font number 0 is the default. If no MAP attribute is given, the default map is a character of the same number in the default font.)

Character 197 (decimal) is more interesting: First an A is typeset (in the default font Times), and this is enclosed by PUSH and POP so that the original position is restored. Then the accent character ‘312’ is typeset, after moving up .937 units and right 1.5 units.

To typeset character ‘200’ in this virtual font, we move down 2.1 units, then typeset a rule that is 1 unit high and 8 units wide.

Finally, to typeset character ‘201’, we do something that requires a special ability to interpret PostScript commands; this example sets the PostScript “color” to 50% gray and typesets an ‘A’ from cmr10 at 20\u in that color.

In general, the MAP attribute of a virtual character can be any sequence of typesetting commands that might appear in a page of a DVI file. A single character might map into an entire page.

**10.** But instead of relying on a hypothetical example, let's consider a complete grammar for VPL files, beginning with the (unchanged) grammatical rules for PL files. At the outer level, the following property names are valid in any PL file:

**CHECKSUM** (four-byte value). The value, which should be a nonnegative integer less than  $2^{32}$ , is used to identify a particular version of a font; it should match the check sum value stored with the font itself. An explicit check sum of zero is used to bypass check sum testing. If no checksum is specified in the VPL file, VPtoVF will compute the checksum that METAFONT would compute from the same data.

**DESIGNSIZE** (numeric value, default is 10). The value, which should be a real number in the range  $1.0 \leq x < 2048$ , represents the default amount by which all quantities will be scaled if the font is not loaded with an 'at' specification. For example, if one says '\font\A=cmr10 at 15pt' in TeX language, the design size in the TFM file is ignored and effectively replaced by 15 points; but if one simply says '\font\A=cmr10' the stated design size is used. This quantity is always in units of printer's points.

**DESIGNUNITS** (numeric value, default is 1). The value should be a positive real number; it says how many units equals the design size (or the eventual 'at' size, if the font is being scaled). For example, suppose you have a font that has been digitized with 600 pixels per em, and the design size is one em; then you could say '(DESIGNUNITS R 600)' if you wanted to give all of your measurements in units of pixels.

**CODINGScheme** (string value, default is 'UNSPECIFIED'). The string should not contain parentheses, and its length must be less than 40. It identifies the correspondence between the numeric codes and font characters. (TeX ignores this information, but other software programs make use of it.)

**FAMILY** (string value, default is 'UNSPECIFIED'). The string should not contain parentheses, and its length must be less than 20. It identifies the name of the family to which this font belongs, e.g., 'HELVETICA'. (TeX ignores this information; but it is needed, for example, when converting DVI files to PRESS files for Xerox equipment.)

**FACE** (one-byte value). This number, which must lie between 0 and 255 inclusive, is a subsidiary identification of the font within its family. For example, bold italic condensed fonts might have the same family name as light roman extended fonts, differing only in their face byte. (TeX ignores this information; but it is needed, for example, when converting DVI files to PRESS files for Xerox equipment.)

**SEVENBITSAFEFLAG** (string value, default is 'FALSE'). The value should start with either 'T' (true) or 'F' (false). If true, character codes less than 128 cannot lead to codes of 128 or more via ligatures or charlists or extensible characters. (TeX82 ignores this flag, but older versions of TeX would only accept TFM files that were seven-bit safe.) VPtoVF computes the correct value of this flag and gives an error message only if a claimed "true" value is incorrect.

**HEADER** (a one-byte value followed by a four-byte value). The one-byte value should be between 18 and a maximum limit that can be raised or lowered depending on the compile-time setting of *max\_header\_bytes*. The four-byte value goes into the header word whose index is the one-byte value; for example, to set *header*[18]  $\leftarrow$  1, one may write '(HEADER D 18 0 1)'. This notation is used for header information that is presently unnamed. (TeX ignores it.)

**FONTDIMEN** (property list value). See below for the names allowed in this property list.

**LIGTABLE** (property list value). See below for the rules about this special kind of property list.

**BOUNDARYCHAR** (one-byte value). If this character appears in a LIGTABLE command, it matches "end of word" as well as itself. If no boundary character is given and no LABEL BOUNDARYCHAR occurs within LIGTABLE, word boundaries will not affect ligatures or kerning.

**CHARACTER**. The value is a one-byte integer followed by a property list. The integer represents the number of a character that is present in the font; the property list of a character is defined below. The default is an empty property list.

**11.** Numeric property list values can be given in various forms identified by a prefixed letter.

C denotes an ASCII character, which should be a standard visible character that is not a parenthesis. The numeric value will therefore be between '41 and '176 but not '50 or '51.

D denotes an unsigned decimal integer, which must be less than  $2^{32}$ , i.e., at most 'D 4294967295'.

F denotes a three-letter Xerox face code; the admissible codes are MRR, MIR, BRR, BIR, LRR, LIR, MRC, MIC, BRC, BIC, LRC, LIC, MRE, MIE, BRE, BIE, LRE, and LIE, denoting the integers 0 to 17, respectively.

O denotes an unsigned octal integer, which must be less than  $2^{32}$ , i.e., at most 'O 377777777777'.

H denotes an unsigned hexadecimal integer, which must be less than  $2^{32}$ , i.e., at most 'H FFFFFFFF'.

R denotes a real number in decimal notation, optionally preceded by a '+' or '-' sign, and optionally including a decimal point. The absolute value must be less than 2048.

**12.** The property names allowed in a FONTDIMEN property list correspond to various TeX parameters, each of which has a (real) numeric value. All of the parameters except SLANT are in design units. The admissible names are SLANT, SPACE, STRETCH, SHRINK, XHEIGHT, QUAD, EXTRASPACE, NUM1, NUM2, NUM3, DENOM1, DENOM2, SUP1, SUP2, SUP3, SUB1, SUB2, SUPDROP, SUBDROP, DELIM1, DELIM2, and AXISHEIGHT, for parameters 1 to 22. The alternate names DEFALTRULETHICKNESS, BIGOPSPACING1, BIGOPSPACING2, BIGOPSPACING3, BIGOPSPACING4, and BIGOPSPACING5, may also be used for parameters 8 to 13.

The notation 'PARAMETER *n*' provides another way to specify the *n*th parameter; for example, '(PARAMETER D 1 R -.25)' is another way to specify that the SLANT is -0.25. The value of *n* must be positive and less than *max\_param\_words*.

**13.** The elements of a CHARACTER property list can be of six different types.

CHARWD (real value) denotes the character's width in design units.

CHARHT (real value) denotes the character's height in design units.

CHARDP (real value) denotes the character's depth in design units.

CHARIC (real value) denotes the character's italic correction in design units.

NEXTLARGER (one-byte value), specifies the character that follows the present one in a "charlist." The value must be the number of a character in the font, and there must be no infinite cycles of supposedly larger and larger characters.

VARCHAR (property list value), specifies an extensible character. This option and NEXTLARGER are mutually exclusive; i.e., they cannot both be used within the same CHARACTER list.

The elements of a VARCHAR property list are either TOP, MID, BOT or REP; the values are integers, which must be zero or the number of a character in the font. A zero value for TOP, MID, or BOT means that the corresponding piece of the extensible character is absent. A nonzero value, or a REP value of zero, denotes the character code used to make up the top, middle, bottom, or replicated piece of an extensible character.

**14.** A **LIGTABLE** property list contains elements of four kinds, specifying a program in a simple command language that **TeX** uses for ligatures and kerns. If several **LIGTABLE** lists appear, they are effectively concatenated into a single list.

**LABEL** (one-byte value) means that the program for the stated character value starts here. The integer must be the number of a character in the font; its **CHARACTER** property list must not have a **NEXTLARGER** or **VARCHAR** field. At least one **LIG** or **KRN** step must follow.

**LABEL BOUNDARYCHAR** means that the program for beginning-of-word ligatures starts here.

**LIG** (two one-byte values). The instruction '(**LIG** *c r*)' means, "If the next character is *c*, then insert character *r* and possibly delete the current character and/or *c*; otherwise go on to the next instruction." Characters *r* and *c* must be present in the font. **LIG** may be immediately preceded or followed by a slash, and then immediately followed by > characters not exceeding the number of slashes. Thus there are eight possible forms:

/LIG	/LIG/	/LIG>	/LIG/ /	/LIG/ />	/LIG/ />/	/LIG/ />/>
------	-------	-------	---------	----------	-----------	------------

The slashes specify retention of the left or right original character; the > signs specify passing over the result without further ligature processing.

**KRN** (a one-byte value and a real value). The instruction '(**KRN** *c r*)' means, "If the next character is *c*, then insert a blank space of width *r* between the current character character and *c*; otherwise go on to the next instruction." The value of *r*, which is in design units, is often negative. Character code *c* must exist in the font.

**STOP** (no value). This instruction ends a ligature/kern program. It must follow either a **LIG** or **KRN** instruction, not a **LABEL** or **STOP** or **SKIP**.

**SKIP** (value in the range 0 .. 127). This instruction specifies continuation of a ligature/kern program after the specified number of **LIG** or **KRN** steps has been skipped over. The number of subsequent **LIG** and **KRN** instructions must therefore exceed this specified amount.

**15.** In addition to all these possibilities, the property name **COMMENT** is allowed in any property list. Such comments are ignored.

**16.** So that is what PL files hold. In a VPL file additional properties are recognized; two of these are valid on the outermost level:

**VTITLE** (string value, default is empty). The value will be reproduced at the beginning of the VF file (and printed on the terminal by VFtoVP when it examines that file).

**MAPFONT**. The value is a nonnegative integer followed by a property list. The integer represents an identifying number for fonts used in **MAP** attributes. The property list, which identifies the font and relative size, is defined below.

And one additional "virtual property" is valid within a **CHARACTER**:

**MAP**. The value is a property list consisting of typesetting commands. Default is the single command **SETCHAR** *c*, where *c* is the current character number.

**17.** The elements of a MAPFONT property list can be of the following types.

**FONTNAME** (string value, default is **NULL**). This is the font's identifying name.

**FONTAREA** (string value, default is empty). If the font appears in a nonstandard directory, according to local conventions, the directory name is given here. (This is system dependent, just as in DVI files.)

**FONTCHECKSUM** (four-byte value, default is zero). This value, which should be a nonnegative integer less than  $2^{32}$ , can be used to check that the font being referred to matches the intended font. If nonzero, it should equal the **CHECKSUM** parameter in that font.

**FONTAT** (numeric value, default is the **DESIGNUNITS** of the present virtual font). This value is relative to the design units of the present virtual font, hence it will be scaled when the virtual font is magnified or reduced. It represents the value that will effectively replace the design size of the font being referred to, so that all characters will be scaled appropriately.

**FONTDSIZE** (numeric value, default is 10). This value is absolute, in units of printer's points. It should equal the **DESIGNSIZE** parameter in the font being referred to.

If any of the string values contain parentheses, the parentheses must be balanced. Leading blanks are removed from the strings, but trailing blanks are not.

**18.** Finally, the elements of a MAP property list are an ordered sequence of typesetting commands chosen from among the following:

**SELECTFONT** (four-byte integer value). The value must be the number of a previously defined MAPFONT. This font (or more precisely, the final font that is mapped to that code number, if two MAPFONT properties happen to specify the same code) will be used in subsequent **SETCHAR** instructions until overridden by another **SELECTFONT**. The first-specified MAPFONT is implicitly selected before the first **SELECTFONT** in every character's map.

**SETCHAR** (one-byte integer value). There must be a character of this number in the currently selected font. (VPtoVF doesn't check that the character is valid, but VFtoVP does.) That character is typeset at the current position, and the typesetter moves right by the **CHARWD** in that character's TFM file.

**SETRULE** (two real values). The first value specifies height, the second specifies width, in design units. If both height and width are positive, a rule is typeset at the current position. Then the typesetter moves right, by the specified width.

**MOVERIGHT**, **MOVELEFT**, **MOVEUP**, **MOVEDOWN** (real value). The typesetter moves its current position by the number of design units specified.

**PUSH**. The current typesetter position is remembered, to be restored on a subsequent **POP**.

**POP**. The current typesetter position is reset to where it was on the most recent unmatched **PUSH**. The **PUSH** and **POP** commands in any MAP must be properly nested like balanced parentheses.

**SPECIAL** (string value). The subsequent characters, starting with the first nonblank and ending just before the first ')' that has no matching '(', are interpreted according to local conventions with the same system-dependent meaning as a 'special' (xxx) command in a DVI file.

**SPECIALHEX** (hexadecimal string value). The subsequent nonblank characters before the next ')' must consist entirely of hexadecimal digits, and they must contain an even number of such digits. Each pair of hex digits specifies a byte, and this string of bytes is treated just as the value of a **SPECIAL**. (This convention permits arbitrary byte strings to be represented in an ordinary text file.)

**19.** Virtual font mapping is a recursive process, like macro expansion. Thus, a MAPFONT might specify another virtual font, whose characters are themselves mapped to other fonts. As an example of this possibility, consider the following curious file called `recurse.vpl`, which defines a virtual font that is self-contained and self-referential:

```
(VTITLE Example of recursion)
(MAPFONT D 0 (FONTNAME recurse) (FONTAT D 2))
(CHARACTER C A (CHARWD D 1)(CHARHT D 1)(MAP (SETRULE D 1 D 1)))
(CHARACTER C B (CHARWD D 2)(CHARHT D 2)(MAP (SETCHAR C A)))
(CHARACTER C C (CHARWD D 4)(CHARHT D 4)(MAP (SETCHAR C B)))
```

The design size is 10 points (the default), hence the character A in font `recurse` is a  $10 \times 10$  point black square. Character B is typeset as character A in `recurse` scaled 2000, hence it is a  $20 \times 20$  point black square. And character C is typeset as character B in `recurse` scaled 2000, hence its size is  $40 \times 40$ .

Users are responsible for making sure that infinite recursion doesn't happen.

**20.** So that is what VPL files hold. From these rules, you can guess (correctly) that VPtoVF operates in four main stages. First it assigns the default values to all properties; then it scans through the VPL file, changing property values as new ones are seen; then it checks the information and corrects any problems; and finally it outputs the VF and TFM files.

**21.** The next question is, “What are VF and TFM files?” A complete answer to that question appears in the documentation of the companion programs, VFtoVP and TFtoPL, so the details will not be repeated here. Suffice it to say that a VF or TFM file stores all of the relevant font information in a sequence of 8-bit bytes. The number of bytes is always a multiple of 4, so we could regard the files as sequences of 32-bit words; but TeX uses the byte interpretation, and so does VPtoVF. Note that the bytes are considered to be unsigned numbers.

```
{ Globals in the outer block 5 } +≡
vf_file: packed file of 0 .. 255;
tfm_file: packed file of 0 .. 255;
```

**22.** On some systems you may have to do something special to write a packed file of bytes. For example, the following code didn't work when it was first tried at Stanford, because packed files have to be opened with a special switch setting on the Pascal that was used.

```
{ Set initial values 6 } +≡
rewrite(vf_file); rewrite(tfm_file);
```

**23. Basic input routines.** For the purposes of this program, a *byte* is an unsigned eight-bit quantity, and an *ASCII\_code* is an integer between '40' and '177'. Such ASCII codes correspond to one-character constants like "A" in WEB language.

{ Types in the outer block 23 } ≡

```
byte = 0 .. 255; { unsigned eight-bit quantity }
ASCII_code = '40' .. '177'; { standard ASCII code numbers }
```

See also sections 66, 71, 78, and 81.

This code is used in section 2.

**24.** One of the things VPtoVF has to do is convert characters of strings to ASCII form, since that is the code used for the family name and the coding scheme in a TFM file. An array *xord* is used to do the conversion from *char*; the method below should work with little or no change on most Pascal systems.

```
define first_ord = 0 { ordinal number of the smallest element of char }
define last_ord = 127 { ordinal number of the largest element of char }
```

{ Globals in the outer block 5 } +≡

```
xord: array [char] of ASCII_code; { conversion table }
```

**25.** { Local variables for initialization 25 } ≡

```
k: integer; { all-purpose initialization index }
```

See also sections 48, 79, and 83.

This code is used in section 2.

**26.** Characters that should not appear in VPL files (except in comments) are mapped into '177.

```
define invalid_code = '177' { code deserving an error message }
```

{ Set initial values 6 } +≡

```
for k ← first_ord to last_ord do xord[chr(k)] ← invalid_code;
xord['_'] ← "_"; xord['!'] ← "!"; xord['"'] ← """"; xord['#'] ← "#"; xord['$'] ← "$";
xord['%'] ← "%"; xord['&'] ← "&"; xord[''''] ← "'"; xord['('] ← "("; xord[')'] ← ")";
xord['*'] ← "*"; xord['+'] ← "+"; xord[','] ← ","; xord['-'] ← "-"; xord['.'] ← ".";
xord['/] ← "/"; xord['0'] ← "0"; xord['1'] ← "1"; xord['2'] ← "2"; xord['3'] ← "3";
xord['4'] ← "4"; xord['5'] ← "5"; xord['6'] ← "6"; xord['7'] ← "7"; xord['8'] ← "8";
xord['9'] ← "9"; xord[':]' ← ":"; xord[';'] ← ";" xord['<'] ← "<"; xord['='] ← "=";
xord['>'] ← ">"; xord['?'] ← "?"; xord['@'] ← "@"; xord['A'] ← "A"; xord['B'] ← "B";
xord['C'] ← "C"; xord['D'] ← "D"; xord['E'] ← "E"; xord['F'] ← "F"; xord['G'] ← "G";
xord['H'] ← "H"; xord['I'] ← "I"; xord['J'] ← "J"; xord['K'] ← "K"; xord['L'] ← "L";
xord['M'] ← "M"; xord['N'] ← "N"; xord['O'] ← "O"; xord['P'] ← "P"; xord['Q'] ← "Q";
xord['R'] ← "R"; xord['S'] ← "S"; xord['T'] ← "T"; xord['U'] ← "U"; xord['V'] ← "V";
xord['W'] ← "W"; xord['X'] ← "X"; xord['Y'] ← "Y"; xord['Z'] ← "Z"; xord['['] ← "[";
xord['\'] ← "\"; xord[']'] ← "]"; xord['^'] ← "^"; xord['_'] ← "_"; xord['~~'] ← "~~";
xord['a'] ← "a"; xord['b'] ← "b"; xord['c'] ← "c"; xord['d'] ← "d"; xord['e'] ← "e";
xord['f'] ← "f"; xord['g'] ← "g"; xord['h'] ← "h"; xord['i'] ← "i"; xord['j'] ← "j";
xord['k'] ← "k"; xord['l'] ← "l"; xord['m'] ← "m"; xord['n'] ← "n"; xord['o'] ← "o";
xord['p'] ← "p"; xord['q'] ← "q"; xord['r'] ← "r"; xord['s'] ← "s"; xord['t'] ← "t";
xord['u'] ← "u"; xord['v'] ← "v"; xord['w'] ← "w"; xord['x'] ← "x"; xord['y'] ← "y";
xord['z'] ← "z"; xord['{'] ← "{"; xord['|'] ← "|"; xord['}'] ← "}"; xord['~~'] ← "~~";
```

**27.** In order to help catch errors of badly nested parentheses, VPtoVF assumes that the user will begin each line with a number of blank spaces equal to some constant times the number of open parentheses at the beginning of that line. However, the program doesn't know in advance what the constant is, nor does it want to print an error message on every line for a user who has followed no consistent pattern of indentation.

Therefore the following strategy is adopted: If the user has been consistent with indentation for ten or more lines, an indentation error will be reported. The constant of indentation is reset on every line that should have nonzero indentation.

```
< Globals in the outer block 5 > +≡
line: integer; { the number of the current line }
good_indent: integer; { the number of lines since the last bad indentation }
indent: integer; { the number of spaces per open parenthesis, zero if unknown }
level: integer; { the current number of open parentheses }
```

**28.** { Set initial values 6 } +≡  
 $line \leftarrow 0; good\_indent \leftarrow 0; indent \leftarrow 0; level \leftarrow 0;$

**29.** The input need not really be broken into lines of any maximum length, and we could read it character by character without any buffering. But we shall place it into a small buffer so that offending lines can be displayed in error messages.

```
< Globals in the outer block 5 > +≡
left_ln, right_ln: boolean; { are the left and right ends of the buffer at end-of-line marks? }
limit: 0 .. buf_size; { position of the last character present in the buffer }
loc: 0 .. buf_size; { position of the last character read in the buffer }
buffer: array [1 .. buf_size] of char;
input_has_ended: boolean; { there is no more input to read }
```

**30.** { Set initial values 6 } +≡  
 $limit \leftarrow 0; loc \leftarrow 0; left\_ln \leftarrow true; right\_ln \leftarrow true; input\_has\_ended \leftarrow false;$

**31.** Just before each CHARACTER property list is evaluated, the character code is printed in octal notation. Up to eight such codes appear on a line; so we have a variable to keep track of how many are currently there.

```
< Globals in the outer block 5 > +≡
chars_on_line: 0 .. 8; { the number of characters printed on the current line }
```

**32.** { Set initial values 6 } +≡  
 $chars\_on\_line \leftarrow 0;$

**33.** The following routine prints an error message and an indication of where the error was detected. The error message should not include any final punctuation, since this procedure supplies its own.

```

define err_print(#) ≡
  begin if chars_on_line > 0 then print_ln(` `);
  print(#); show_error_context;
  end

procedure show_error_context; { prints the current scanner location }
  var k: 0 .. buf_size; { an index into buffer }
  begin print_ln(` `(line` , line : 1, ` `));
  if ¬left_ln then print(` ... `);
  for k ← 1 to loc do print(buffer[k]); { print the characters already scanned }
  print_ln(` `);
  if ¬left_ln then print(` ` ` `);
  for k ← 1 to loc do print(` `); { space out the second line }
  for k ← loc + 1 to limit do print(buffer[k]); { print the characters yet unseen }
  if right_ln then print_ln(` `) else print_ln(` ... `);
  chars_on_line ← 0;
  end;

```

**34.** Here is a procedure that does the right thing when we are done reading the present contents of the buffer. It keeps *buffer*[*buf\_size*] empty, in order to avoid range errors on certain Pascal compilers.

An infinite sequence of right parentheses is placed at the end of the file, so that the program is sure to get out of whatever level of nesting it is in.

On some systems it is desirable to modify this code so that tab marks in the buffer are replaced by blank spaces. (Simply setting *xord*[*chr*('11)] ← " " would not work; for example, two-line error messages would not come out properly aligned.)

```

procedure fill_buffer;
  begin left_ln ← right_ln; limit ← 0; loc ← 0;
  if left_ln then
    begin if line > 0 then read_ln(vpl_file);
    incr(line);
    end;
  if eof(vpl_file) then
    begin limit ← 1; buffer[1] ← ` `; right_ln ← false; input_hasEnded ← true;
    end
  else begin while (limit < buf_size - 2) ∧ (¬eoln(vpl_file)) do
    begin incr(limit); read(vpl_file, buffer[limit]);
    end;
    buffer[limit + 1] ← ` `; right_ln ← eoln(vpl_file);
  if right_ln then
    begin incr(limit); buffer[limit + 1] ← ` `;
    end;
  if left_ln then { Set loc to the number of leading blanks in the buffer, and check the indentation 35 };
  end;
end;

```

**35.** The interesting part about *fill\_buffer* is the part that learns what indentation conventions the user is following, if any.

```

define bad_indent(#) ≡
  begin if good_indent ≥ 10 then err_print(#);
  good_indent ← 0; indent ← 0;
  end

{ Set loc to the number of leading blanks in the buffer, and check the indentation 35 } ≡
begin while (loc < limit) ∧ (buffer[loc + 1] = ' ') do incr(loc);
if loc < limit then
  begin if level = 0 then
    if loc = 0 then incr(good_indent)
    else bad_indent(`Warning: Indented line occurred at level zero')
  else if indent = 0 then
    if loc mod level = 0 then
      begin indent ← loc div level; good_indent ← 1;
      end
    else good_indent ← 0
    else if indent * level = loc then incr(good_indent)
    else bad_indent(`Warning: Inconsistent indentation; ',
      `you are at parenthesis level ', level : 1);
  end;
end

```

This code is used in section 34.

**36. Basic scanning routines.** The global variable *cur\_char* holds the ASCII code corresponding to the character most recently read from the input buffer, or to a character that has been substituted for the real one.

```
( Globals in the outer block 5 ) +≡
cur_char: ASCII_code; { we have just read this }
```

**37.** Here is a procedure that sets *cur\_char* to an ASCII code for the next character of input, if that character is a letter or digit or slash or >. Otherwise it sets *cur\_char*  $\leftarrow$  "□", and the input system will be poised to reread the character that was rejected, whether or not it was a space. Lower case letters are converted to upper case.

```
procedure get_keyword_char;
begin while (loc = limit)  $\wedge$  ( $\neg$ right_ln) do fill_buffer;
if loc = limit then cur_char  $\leftarrow$  "□" { end-of-line counts as a delimiter }
else begin cur_char  $\leftarrow$  xord[buffer[loc + 1]];
if cur_char  $\geq$  "a" then cur_char  $\leftarrow$  cur_char - '40;
if ((cur_char  $\geq$  "0")  $\wedge$  (cur_char  $\leq$  "9")) then incr(loc)
else if ((cur_char  $\geq$  "A")  $\wedge$  (cur_char  $\leq$  "Z")) then incr(loc)
else if cur_char = "/" then incr(loc)
else if cur_char = ">" then incr(loc)
else cur_char  $\leftarrow$  "□";
end;
end;
```

**38.** The following procedure sets *cur\_char* to the next character code, and converts lower case to upper case. If the character is a left or right parenthesis, it will not be “digested”; the character will be read again and again, until the calling routine does something like ‘*incr(loc)*’ to get past it. Such special treatment of parentheses insures that the structural information they contain won’t be lost in the midst of other error recovery operations.

```
define backup ≡
begin if (cur_char > ")")  $\vee$  (cur_char < "(") then decr(loc);
end { undoes the effect of get_next }

procedure get_next; { sets cur_char to next, balks at parentheses }
begin while loc = limit do fill_buffer;
incr(loc); cur_char  $\leftarrow$  xord[buffer[loc]];
if cur_char  $\geq$  "a" then
  if cur_char  $\leq$  "z" then cur_char  $\leftarrow$  cur_char - '40 { uppercasify }
else begin if cur_char = invalid_code then
  begin err_print('Illegal character in the file'); cur_char  $\leftarrow$  "?";
  end;
end
else if (cur_char  $\leq$  ")")  $\wedge$  (cur_char  $\geq$  "(") then decr(loc);
end;
```

**39.** Here's a procedure that scans a hexadecimal digit or a right parenthesis.

```
function get_hex: byte;
var a: integer; { partial result }
begin repeat get_next;
until cur_char ≠ ">";
a ← cur_char - ")";
if a > 0 then
begin a ← cur_char - "0";
if cur_char > "9" then
  if cur_char < "A" then a ← -1
  else a ← cur_char - "A" + 10;
end;
if (a < 0) ∨ (a > 15) then
begin err_print(`Illegal_hexadecimal_digit`); get_hex ← 0;
end
else get_hex ← a;
end;
```

**40.** The next procedure is used to ignore the text of a comment, or to pass over erroneous material. As such, it has the privilege of passing parentheses. It stops after the first right parenthesis that drops the level below the level in force when the procedure was called.

```
procedure skip_to_end_of_item;
var l: integer; { initial value of level }
begin l ← level;
while level ≥ l do
begin while loc = limit do fill_buffer;
incr(loc);
if buffer[loc] = ')' then decr(level)
else if buffer[loc] = '(' then incr(level);
end;
if input_has-ended then err_print(`File-ended-unexpectedly: No closing)`"`);
cur_char ← ">"; { now the right parenthesis has been read and digested }
end;
```

41. A similar procedure copies the bytes remaining in an item. The copied bytes go into an array *vf* that we'll declare later. Leading blanks are ignored.

```

define vf_store(#) ≡
  begin vf[vf_ptr] ← #;
  if vf_ptr = vf_size then err_print(`I'm out of memory---increase my vysize!')
  else incr(vf_ptr);
  end

procedure copy_to_end_of_item;
label 30;
var l: integer; { initial value of level }
  nonblank_found: boolean; { have we seen a nonblank character yet? }
begin l ← level; nonblank_found ← false;
while true do
  begin while loc = limit do fill_buffer;
  if buffer[loc + 1] = `)` then
    if level = l then goto 30 else decr(level);
    incr(loc);
  if buffer[loc] = `(` then incr(level);
  if buffer[loc] ≠ ` ` then nonblank_found ← true;
  if nonblank_found then
    if xord[buffer[loc]] = invalid_code then
      begin err_print(`Illegal character in the file'); vf_store("?");
      end
    else vf_store(xord[buffer[loc]]);
  end;
30: end;

```

42. Sometimes we merely want to skip past characters in the input until we reach a left or a right parenthesis. For example, we do this whenever we have finished scanning a property value and we hope that a right parenthesis is next (except for possible blank spaces).

```

define skip_to_paren ≡
  repeat get_next until (cur_char = "(") ∨ (cur_char = ")")
define skip_error(#) ≡
  begin err_print(#); skip_to_paren;
  end { this gets to the right parenthesis if something goes wrong }
define flush_error(#) ≡
  begin err_print(#); skip_to_end_of_item;
  end { this gets past the right parenthesis if something goes wrong }

```

43. After a property value has been scanned, we want to move just past the right parenthesis that should come next in the input (except for possible blank spaces).

```

procedure finish_the_property; { do this when the value has been scanned }
begin while cur_char = ` ` do get_next;
if cur_char ≠ ")" then err_print(`Junk after property value will be ignored');
skip_to_end_of_item;
end;

```

**44. Scanning property names.** We have to figure out the meaning of names that appear in the VPL file, by looking them up in a dictionary of known keywords. Keyword number  $n$  appears in locations  $start[n]$  through  $start[n + 1] - 1$  of an array called *dictionary*.

```
define max_name_index = 100 { upper bound on the number of keywords }
define max_letters = 666 { upper bound on the total length of all keywords }
⟨ Globals in the outer block 5 ⟩ +≡
start: array [1 .. max_name_index] of 0 .. max_letters;
dictionary: array [0 .. max_letters] of ASCII_code;
start_ptr: 0 .. max_name_index; { the first available place in start }
dict_ptr: 0 .. max_letters; { the first available place in dictionary }
```

**45.** ⟨ Set initial values 6 ⟩ +≡  
 $start\_ptr \leftarrow 1; start[1] \leftarrow 0; dict\_ptr \leftarrow 0;$

**46.** When we are looking for a name, we put it into the *cur\_name* array. When we have found it, the corresponding *start* index will go into the global variable *name\_ptr*.

```
define longest_name = 20 { length of DEFALTRULETHICKNESS }
⟨ Globals in the outer block 5 ⟩ +≡
cur_name: array [1 .. longest_name] of ASCII_code; { a name to look up }
name_length: 0 .. longest_name; { its length }
name_ptr: 0 .. max_name_index; { its ordinal number in the dictionary }
```

**47.** A conventional hash table with linear probing (cf. Algorithm 6.4L in *The Art of Computer Programming*) is used for the dictionary operations. If  $nhash[h] = 0$ , the table position is empty, otherwise  $nhash[h]$  points into the *start* array.

```
define hash_prime = 141 { size of the hash table }
⟨ Globals in the outer block 5 ⟩ +≡
nhash: array [0 .. hash_prime - 1] of 0 .. max_name_index;
cur_hash: 0 .. hash_prime - 1; { current position in the hash table }
```

**48.** ⟨ Local variables for initialization 25 ⟩ +≡  
 $h: 0 .. hash\_prime - 1; \{ runs through the hash table \}$

**49.** ⟨ Set initial values 6 ⟩ +≡  
 $\text{for } h \leftarrow 0 \text{ to } hash\_prime - 1 \text{ do } nhash[h] \leftarrow 0;$

50. Since there is no chance of the hash table overflowing, the procedure is very simple. After *lookup* has done its work, *cur\_hash* will point to the place where the given name was found, or where it should be inserted.

```

procedure lookup; { finds cur_name in the dictionary }
  var k: 0 .. longest_name; { index into cur_name }
    j: 0 .. max_letters; { index into dictionary }
    not_found: boolean; { clumsy thing necessary to avoid goto statement }
  begin { Compute the hash code, cur_hash, for cur_name 51 };
    not_found ← true;
    while not_found do
      begin if cur_hash = 0 then cur_hash ← hash_prime - 1 else decr(cur_hash);
        if nhash[cur_hash] = 0 then not_found ← false
        else begin j ← start[nhash[cur_hash]];
          if start[nhash[cur_hash] + 1] = j + name_length then
            begin not_found ← false;
              for k ← 1 to name_length do
                if dictionary[j + k - 1] ≠ cur_name[k] then not_found ← true;
              end;
            end;
          end;
        end;
      end;
    name_ptr ← nhash[cur_hash];
  end;

```

51. { Compute the hash code, *cur\_hash*, for *cur\_name* 51 } ≡  
*cur\_hash* ← *cur\_name*[1];  
**for** *k* ← 2 **to** *name\_length* **do** *cur\_hash* ← (*cur\_hash* + *cur\_hash* + *cur\_name*[*k*]) **mod** *hash\_prime*

This code is used in section 50.

52. The “meaning” of the keyword that begins at *start*[*k*] in the dictionary is kept in *equiv*[*k*]. The numeric *equiv* codes are given symbolic meanings by the following definitions.

```
define comment_code = 0
define check_sum_code = 1
define design_size_code = 2
define design_units_code = 3
define coding_scheme_code = 4
define family_code = 5
define face_code = 6
define seven_bit_safe_flag_code = 7
define header_code = 8
define font_dimen_code = 9
define lig_table_code = 10
define boundary_char_code = 11
define virtual_title_code = 12
define map_font_code = 13
define character_code = 14
define font_name_code = 20
define font_area_code = 21
define font_checksum_code = 22
define font_at_code = 23
define font_dsize_code = 24
define parameter_code = 30
define char_info_code = 60
define width = 1
define height = 2
define depth = 3
define italic = 4
define char_wd_code = char_info_code + width
define char_ht_code = char_info_code + height
define char_dp_code = char_info_code + depth
define char_ic_code = char_info_code + italic
define next_larger_code = 65
define map_code = 66
define var_char_code = 67
define select_font_code = 80
define set_char_code = 81
define set_rule_code = 82
define move_right_code = 83
define move_down_code = 85
define push_code = 87
define pop_code = 88
define special_code = 89
define special_hex_code = 90
define label_code = 100
define stop_code = 101
define skip_code = 102
define krn_code = 103
define lig_code = 104
```

{ Globals in the outer block 5 } +≡

*equiv*: array [0 .. *max\_name\_index*] of byte;

*cur\_code*: byte; { equivalent most recently found in *equiv* }

**53.** We have to get the keywords into the hash table and into the dictionary in the first place (sigh). The procedure that does this has the desired *equiv* code as a parameter. In order to facilitate WEB macro writing for the initialization, the keyword being initialized is placed into the last positions of *cur\_name*, instead of the first positions.

```

procedure enter_name(v : byte); { cur_name goes into the dictionary }
  var k: 0 .. longest_name;
  begin for k  $\leftarrow$  1 to name_length do cur_name[k]  $\leftarrow$  cur_name[k + longest_name - name_length];
    { now the name has been shifted into the correct position }
    lookup; { this sets cur_hash to the proper insertion place }
    nhash[cur_hash]  $\leftarrow$  start_ptr; equiv[start_ptr]  $\leftarrow$  v;
    for k  $\leftarrow$  1 to name_length do
      begin dictionary[dict_ptr]  $\leftarrow$  cur_name[k]; incr(dict_ptr);
      end;
      incr(start_ptr); start[start_ptr]  $\leftarrow$  dict_ptr;
    end;

```

54. Here are the macros to load a name of up to 20 letters into the dictionary. For example, the macro *load5* is used for five-letter keywords.

```
define tail(#) ≡ enter_name(#)
define t20(#) ≡ cur_name[20] ← #; tail
define t19(#) ≡ cur_name[19] ← #; t20
define t18(#) ≡ cur_name[18] ← #; t19
define t17(#) ≡ cur_name[17] ← #; t18
define t16(#) ≡ cur_name[16] ← #; t17
define t15(#) ≡ cur_name[15] ← #; t16
define t14(#) ≡ cur_name[14] ← #; t15
define t13(#) ≡ cur_name[13] ← #; t14
define t12(#) ≡ cur_name[12] ← #; t13
define t11(#) ≡ cur_name[11] ← #; t12
define t10(#) ≡ cur_name[10] ← #; t11
define t9(#) ≡ cur_name[9] ← #; t10
define t8(#) ≡ cur_name[8] ← #; t9
define t7(#) ≡ cur_name[7] ← #; t8
define t6(#) ≡ cur_name[6] ← #; t7
define t5(#) ≡ cur_name[5] ← #; t6
define t4(#) ≡ cur_name[4] ← #; t5
define t3(#) ≡ cur_name[3] ← #; t4
define t2(#) ≡ cur_name[2] ← #; t3
define t1(#) ≡ cur_name[1] ← #; t2
define load3 ≡ name_length ← 3; t18
define load4 ≡ name_length ← 4; t17
define load5 ≡ name_length ← 5; t16
define load6 ≡ name_length ← 6; t15
define load7 ≡ name_length ← 7; t14
define load8 ≡ name_length ← 8; t13
define load9 ≡ name_length ← 9; t12
define load10 ≡ name_length ← 10; t11
define load11 ≡ name_length ← 11; t10
define load12 ≡ name_length ← 12; t9
define load13 ≡ name_length ← 13; t8
define load14 ≡ name_length ← 14; t7
define load15 ≡ name_length ← 15; t6
define load16 ≡ name_length ← 16; t5
define load17 ≡ name_length ← 17; t4
define load18 ≡ name_length ← 18; t3
define load19 ≡ name_length ← 19; t2
define load20 ≡ name_length ← 20; t1
```

55. (Thank goodness for keyboard macros in the text editor used to create this WEB file.)

{Enter all the PL names and their equivalents, except the parameter names 55} ≡

```

equiv[0] ← comment_code; { this is used after unknown keywords }
load8("C")("H")("E")("C")("K")("S")("U")("M")(check_sum_code);
load10("D")("E")("S")("I")("G")("N")("S")("I")("Z")("E")(design_size_code);
load11("D")("E")("S")("I")("G")("N")("U")("N")("I")("T")("S")(design_units_code);
load12("C")("O")("D")("I")("N")("G")("S")("C")("H")("E")("M")("E")(coding_scheme_code);
load6("F")("A")("M")("I")("L")("Y")(family_code);
load4("F")("A")("C")("E")(face_code);
load16("S")("E")("V")("E")("N")("B")("I")("T")
    ("S")("A")("F")("E")("F")("A")("G")(seven_bit_safe_flag_code);
load6("H")("E")("A")("D")("E")("R")(header_code);
load9("F")("O")("N")("T")("D")("I")("M")("E")("N")(font_dimen_code);
load8("L")("I")("G")("T")("A")("B")("L")("E")(lig_table_code);
load12("B")("O")("U")("N")("D")("A")("R")("Y")("C")("H")("A")("R")(boundary_char_code);
load9("C")("H")("A")("R")("A")("C")("T")("E")("R")(character_code);
load9("P")("A")("R")("A")("M")("E")("T")("E")("R")(parameter_code);
load6("C")("H")("A")("R")("W")("D")(char_wd_code);
load6("C")("H")("A")("R")("H")("T")(char_ht_code);
load6("C")("H")("A")("R")("D")("P")(char_dp_code);
load6("C")("H")("A")("R")("I")("C")(char_ic_code);
load10("N")("E")("X")("T")("L")("A")("R")("G")("E")("R")(next_larger_code);
load7("V")("A")("R")("C")("H")("A")("R")(var_char_code);
load3("T")("O")("P")(var_char_code + 1);
load3("M")("I")("D")(var_char_code + 2);
load3("B")("O")("T")(var_char_code + 3);
load3("R")("E")("P")(var_char_code + 4);
load3("E")("X")("T")(var_char_code + 4); { compatibility with older PL format }
load7("C")("O")("M")("M")("E")("N")("T")(comment_code);
load5("L")("A")("B")("E")("L")(label_code);
load4("S")("T")("O")("P")(stop_code);
load4("S")("K")("I")("P")(skip_code);
load3("K")("R")("N")(krn_code);
load3("L")("I")("G")(lig_code);
load4("//")("L")("I")("G")(lig_code + 2);
load5("//")("L")("I")("G")(">")(lig_code + 6);
load4("L")("I")("G")("//")(lig_code + 1);
load5("L")("I")("G")("//")(">")(lig_code + 5);
load5("//")("L")("I")("G")("//")(lig_code + 3);
load6("//")("L")("I")("G")("//")(">")(lig_code + 7);
load7("//")("L")("I")("G")("//")(">")(" > ")(lig_code + 11);

```

This code is used in section 180.

**56.** VPL files may contain the following in addition to the PL names.

(Enter all the VPL names 56) ≡

```

load6("V")("T")("I")("T")("L")("E")(virtual_title_code);
load7("M")("A")("P")("F")("O")("N")("T")(map_font_code);
load3("M")("A")("P")(map_code);
load8("F")("O")("N")("T")("N")("A")("M")("E")(font_name_code);
load8("F")("O")("N")("T")("A")("R")("E")("A")(font_area_code);
load12("F")("O")("N")("T")("C")("H")("E")("C")("K")("S")("U")("M")(font_checksum_code);
load6("F")("O")("N")("T")("A")("T")(font_at_code);
load9("F")("O")("N")("T")("D")("S")("I")("Z")("E")(font_dsize_code);
load10("S")("E")("L")("E")("C")("T")("F")("O")("N")("T")(select_font_code);
load7("S")("E")("T")("C")("H")("A")("R")(set_char_code);
load7("S")("E")("T")("R")("U")("L")("E")(set_rule_code);
load9("M")("O")("V")("E")("R")("I")("G")("H")("T")(move_right_code);
load8("M")("O")("V")("E")("L")("E")("F")("T")(move_right_code + 1);
load8("M")("O")("V")("E")("D")("O")("W")("N")(move_down_code);
load6("M")("O")("V")("E")("U")("P")(move_down_code + 1);
load4("P")("U")("S")("H")(push_code);
load3("P")("O")("P")(pop_code);
load7("S")("P")("E")("C")("I")("A")("L")(special_code);
load10("S")("P")("E")("C")("I")("A")("L")("H")("E")("X")(special_hex_code);

```

This code is used in section 180.

## 57. {Enter the parameter names 57} ≡

```

load5("S")("L")("A")("N")("T")(parameter_code + 1);
load5("S")("P")("A")("C")("E")(parameter_code + 2);
load7("S")("T")("R")("E")("T")("C")("H")(parameter_code + 3);
load6("S")("H")("R")("I")("N")("K")(parameter_code + 4);
load7("X")("H")("E")("I")("G")("H")("T")(parameter_code + 5);
load4("Q")("U")("A")("D")(parameter_code + 6);
load10("E")("X")("T")("R")("A")("S")("P")("A")("C")("E")(parameter_code + 7);
load4("N")("U")("M")("1")(parameter_code + 8);
load4("N")("U")("M")("2")(parameter_code + 9);
load4("N")("U")("M")("3")(parameter_code + 10);
load6("D")("E")("N")("O")("M")("1")(parameter_code + 11);
load6("D")("E")("N")("O")("M")("2")(parameter_code + 12);
load4("S")("U")("P")("1")(parameter_code + 13);
load4("S")("U")("P")("2")(parameter_code + 14);
load4("S")("U")("P")("3")(parameter_code + 15);
load4("S")("U")("B")("1")(parameter_code + 16);
load4("S")("U")("B")("2")(parameter_code + 17);
load7("S")("U")("P")("D")("R")("O")("P")(parameter_code + 18);
load7("S")("U")("B")("D")("R")("O")("P")(parameter_code + 19);
load6("D")("E")("L")("I")("M")("1")(parameter_code + 20);
load6("D")("E")("L")("I")("M")("2")(parameter_code + 21);
load10("A")("X")("I")("S")("H")("E")("I")("G")("H")("T")(parameter_code + 22);
load20("D")("E")("F")("A")("U")("L")("T")("R")("U")("L")("E")
    ("T")("H")("I")("C")("K")("N")("E")("S")("S")(parameter_code + 8);
load13("B")("I")("G")("O")("P")("S")("P")("A")("C")("I")("N")("G")("1")(parameter_code + 9);
load13("B")("I")("G")("O")("P")("S")("P")("A")("C")("I")("N")("G")("2")(parameter_code + 10);
load13("B")("I")("G")("O")("P")("S")("P")("A")("C")("I")("N")("G")("3")(parameter_code + 11);
load13("B")("I")("G")("O")("P")("S")("P")("A")("C")("I")("N")("G")("4")(parameter_code + 12);
load13("B")("I")("G")("O")("P")("S")("P")("A")("C")("I")("N")("G")("5")(parameter_code + 13);

```

This code is used in section 180.

58. When a left parenthesis has been scanned, the following routine is used to interpret the keyword that follows, and to store the equivalent value in *cur\_code*.

```

procedure get_name;
begin incr(loc); incr(level); { pass the left parenthesis }
cur_char ← " ";
while cur_char = " " do get_next;
if (cur_char > ")") ∨ (cur_char < "(") then decr(loc); { back up one character }
name_length ← 0; get_keyword_char; { prepare to scan the name }
while cur_char ≠ " " do
begin if name_length = longest_name then cur_name[1] ← "X" { force error }
else incr(name_length);
cur_name[name_length] ← cur_char; get_keyword_char;
end;
lookup;
if name_ptr = 0 then err_print(`Sorry, I don't know that property name');
cur_code ← equiv[name_ptr];
end;

```

**59. Scanning numeric data.** The next thing we need is a trio of subroutines to read the one-byte, four-byte, and real numbers that may appear as property values. These subroutines are careful to stick to numbers between  $-2^{31}$  and  $2^{31} - 1$ , inclusive, so that a computer with two's complement 32-bit arithmetic will not be interrupted by overflow.

**60.** The first number scanner, which returns a one-byte value, surely has no problems of arithmetic overflow.

```
function get_byte: byte; { scans a one-byte property value }
var acc: integer; { an accumulator }
t: ASCII_code; { the type of value to be scanned }
begin repeat get_next;
until cur_char ≠ " "; { skip the blanks before the type code }
t ← cur_char; acc ← 0;
repeat get_next;
until cur_char ≠ " "; { skip the blanks after the type code }
if t = "C" then { Scan an ASCII character code 61 }
else if t = "D" then { Scan a small decimal number 62 }
else if t = "O" then { Scan a small octal number 63 }
else if t = "H" then { Scan a small hexadecimal number 64 }
else if t = "F" then { Scan a face code 65 }
else skip_error('You need "C" or "D" or "O" or "H" or "F" here');
cur_char ← " "; get_byte ← acc;
end;
```

**61.** The *get\_next* routine converts lower case to upper case, but it leaves the character in the buffer, so we can unconvert it.

```
{ Scan an ASCII character code 61 } ≡
if (cur_char ≥ '41') ∧ (cur_char ≤ '76') ∧ ((cur_char < "(") ∨ (cur_char > ")")) then
  acc ← xord[buffer[loc]]
else skip_error('C' value must be standard ASCII and not a paren')
```

This code is used in section 60.

```
62. { Scan a small decimal number 62 } ≡
begin while (cur_char ≥ "0") ∧ (cur_char ≤ "9") do
  begin acc ← acc * 10 + cur_char - "0";
  if acc > 255 then
    begin skip_error('This value shouldn't exceed 255'); acc ← 0; cur_char ← " ";
    end
  else get_next;
  end;
  backup;
end
```

This code is used in section 60.

**63.** ⟨ Scan a small octal number 63 ⟩ ≡

```

begin while (cur_char ≥ "0") ∧ (cur_char ≤ "7") do
  begin acc ← acc * 8 + cur_char - "0";
  if acc > 255 then
    begin skip_error(`This value shouldn't exceed ``377`); acc ← 0; cur_char ← " ";
    end
  else get_next;
  end;
  backup;
end

```

This code is used in section 60.

**64.** ⟨ Scan a small hexadecimal number 64 ⟩ ≡

```

begin while ((cur_char ≥ "0") ∧ (cur_char ≤ "9")) ∨ ((cur_char ≥ "A") ∧ (cur_char ≤ "F")) do
  begin if cur_char ≥ "A" then cur_char ← cur_char + "0" + 10 - "A";
  acc ← acc * 16 + cur_char - "0";
  if acc > 255 then
    begin skip_error(`This value shouldn't exceed ``FF`); acc ← 0; cur_char ← " ";
    end
  else get_next;
  end;
  backup;
end

```

This code is used in section 60.

**65.** ⟨ Scan a face code 65 ⟩ ≡

```

begin if cur_char = "B" then acc ← 2
else if cur_char = "L" then acc ← 4
  else if cur_char ≠ "M" then acc ← 18;
get_next;
if cur_char = "I" then incr(acc)
else if cur_char ≠ "R" then acc ← 18;
get_next;
if cur_char = "C" then acc ← acc + 6
else if cur_char = "E" then acc ← acc + 12
  else if cur_char ≠ "R" then acc ← 18;
if acc ≥ 18 then
  begin skip_error(`Illegal face code, unchanged bit to MRR`); acc ← 0;
  end;
end

```

This code is used in section 60.

**66.** The routine that scans a four-byte value puts its output into *cur\_bytes*, which is a record containing (yes, you guessed it) four bytes.

⟨ Types in the outer block 23 ⟩ +≡

```

four_bytes = record b0: byte; b1: byte; b2: byte; b3: byte;
end;

```

**67.** **define**  $c_0 \equiv cur\_bytes.b_0$   
**define**  $c_1 \equiv cur\_bytes.b_1$   
**define**  $c_2 \equiv cur\_bytes.b_2$   
**define**  $c_3 \equiv cur\_bytes.b_3$

{ Globals in the outer block 5 } +≡  
*cur\_bytes*: four-bytes; { a four-byte accumulator }  
*zero\_bytes*: four-bytes; { four bytes all zero }

**68.** { Set initial values 6 } +≡  
*zero\_bytes.b0* ← 0; *zero\_bytes.b1* ← 0; *zero\_bytes.b2* ← 0; *zero\_bytes.b3* ← 0;

**69.** Since the *get\_four\_bytes* routine is used very infrequently, no attempt has been made to make it fast; we only want it to work.

```
procedure get_four_bytes; { scans an unsigned constant and sets four_bytes }
  var c: integer; { local two-byte accumulator }
    r: integer; { radix }
  begin repeat get_next;
    until cur_char ≠ " "; { skip the blanks before the type code }
    r ← 0; cur_bytes ← zero_bytes; { start with the accumulator zero }
    if cur_char = "H" then r ← 16
    else if cur_char = "0" then r ← 8
    else if cur_char = "D" then r ← 10
    else skip_error(`Decimal(`D`), `octal(`0`), `or_hex(`H`)) value needed here`);
    if r > 0 then
      begin repeat get_next;
        until cur_char ≠ " "; { skip the blanks after the type code }
        while ((cur_char ≥ "0") ∧ (cur_char ≤ "9")) ∨ ((cur_char ≥ "A") ∧ (cur_char ≤ "F")) do
          { Multiply by r, add cur_char - "0", and get_next 70 };
        end;
      end;
    end;
```

**70.** { Multiply by *r*, add *cur\_char* - "0", and *get\_next* 70 } +≡

```
begin if cur_char ≥ "A" then cur_char ← cur_char + "0" + 10 - "A";
if cur_char ≥ "0" + r then skip_error(`Illegal digit`)
else begin c ← c3 * r + cur_char - "0"; c3 ← c mod 256;
  c ← c2 * r + c div 256; c2 ← c mod 256;
  c ← c1 * r + c div 256; c1 ← c mod 256;
  c ← c0 * r + c div 256;
  if c < 256 then c0 ← c
  else begin cur_bytes ← zero_bytes;
    if r = 8 then skip_error(`Sorry, the maximum octal value is 03777777777`)
    else if r = 10 then skip_error(`Sorry, the maximum decimal value is D4294967295`)
    else skip_error(`Sorry, the maximum hex value is HFFFFFFF`);
    end;
  get_next;
  end;
end
```

This code is used in section 69.

**71.** The remaining scanning routine is the most interesting. It scans a real constant and returns the nearest *fix\_word* approximation to that constant. A *fix\_word* is a 32-bit integer that represents a real value that has been multiplied by  $2^{20}$ . Since VPtoVF restricts the magnitude of reals to 2048, the *fix\_word* will have a magnitude less than  $2^{31}$ .

```
define unity ≡ '4000000 { 220, the fix_word 1.0 }
⟨Types in the outer block 23⟩ +≡
fix_word = integer; { a scaled real value with 20 bits of fraction }
```

**72.** When a real value is desired, we might as well treat ‘D’ and ‘R’ formats as if they were identical.

```
function get_fix: fix_word; { scans a real property value }
var negative: boolean; { was there a minus sign? }
acc: integer; { an accumulator }
int_part: integer; { the integer part }
j: 0 .. 7; { the number of decimal places stored }
begin repeat get_next;
until cur_char ≠ " "; { skip the blanks before the type code }
negative ← false; acc ← 0; { start with the accumulators zero }
if (cur_char ≠ "R") ∧ (cur_char ≠ "D") then skip_error('An "R" or "D" value is needed here')
else begin {Scan the blanks and/or signs after the type code 73};
  while (cur_char ≥ "0") ∧ (cur_char ≤ "9") do {Multiply by 10, add cur_char - "0", and get_next 74};
  int_part ← acc; acc ← 0;
  if cur_char = "." then {Scan the fraction part and put it in acc 76};
  if (acc ≥ unity) ∧ (int_part = 2047) then skip_error('Real constants must be less than 2048')
  else acc ← int_part * unity + acc;
end;
if negative then get_fix ← -acc else get_fix ← acc;
end;
```

**73.** {Scan the blanks and/or signs after the type code 73} ≡

```
repeat get_next;
if cur_char = "-" then
  begin cur_char ← " "; negative ← ¬negative;
  end
else if cur_char = "+" then cur_char ← " ";
until cur_char ≠ " "
```

This code is used in section 72.

**74.** {Multiply by 10, add cur\_char - "0", and get\_next 74} ≡

```
begin acc ← acc * 10 + cur_char - "0";
if acc ≥ 2048 then
  begin skip_error('Real constants must be less than 2048'); acc ← 0; cur_char ← " ";
  end
else get_next;
end
```

This code is used in section 72.

**75.** To scan the fraction  $.d_1 d_2 \dots$ , we keep track of up to seven of the digits  $d_j$ . A correct result is obtained if we first compute  $f' = \lfloor 2^{21}(d_1 \dots d_j)/10^j \rfloor$ , after which  $f = \lfloor (f' + 1)/2 \rfloor$ . It is possible to have  $f = 1.0$ .

```
⟨Globals in the outer block 5⟩ +≡
fraction_digits: array [1 .. 7] of integer; { 221 times dj }
```

76.  $\langle$  Scan the fraction part and put it in *acc*  $\rangle \equiv$

```
begin j  $\leftarrow$  0; get_next;  
while (cur_char  $\geq$  "0")  $\wedge$  (cur_char  $\leq$  "9") do  
begin if j < 7 then  
  begin incr(j); fraction_digits[j]  $\leftarrow$  '10000000 * (cur_char - "0");  
  end;  
  get_next;  
  end;  
acc  $\leftarrow$  0;  
while j > 0 do  
begin acc  $\leftarrow$  fraction_digits[j] + (acc div 10); decr(j);  
end;  
acc  $\leftarrow$  (acc + 10) div 20;  
end
```

This code is used in section 72.

**77. Storing the property values.** When property values have been found, they are squirreled away in a bunch of arrays. The header information is unpacked into bytes in an array called *header\_bytes*. The ligature/kerning program is stored in an array of type *four\_bytes*. Another *four\_bytes* array holds the specifications of extensible characters. The kerns and parameters are stored in separate arrays of *fix\_word* values. Virtual font data goes into an array *vf* of single-byte values.

We maintain information about at most 256 local fonts. (If this is inadequate, several arrays need to be made longer and we need to output font definitions that go beyond *font1* and *font\_def1* in the VF file.)

Instead of storing the design size in the header array, we will keep it in a *fix\_word* variable until the last minute. The number of units in the design size is also kept in a *fix\_word*.

```

⟨Globals in the outer block 5⟩ +≡
header_bytes: array [header_index] of byte; { the header block }
header_ptr: header_index; { the number of header bytes in use }
design_size: fix_word; { the design size }
design_units: fix_word; { reciprocal of the scaling factor }
frozen_du: boolean; { have we used design_units irrevocably? }
seven_bit_safe_flag: boolean; { does the file claim to be seven-bit-safe? }
lig_kern: array [0 .. max_lig_steps] of four_bytes; { the ligature program }
nl: 0 .. 32767; { the number of ligature/kern instructions so far }
min_nl: 0 .. 32767; { the final value of nl must be at least this }
kern: array [0 .. max_kerns] of fix_word; { the distinct kerning amounts }
nk: 0 .. max_kerns; { the number of entries of kern }
exten: array [0 .. 255] of four_bytes; { extensible character specs }
ne: 0 .. 256; { the number of extensible characters }
param: array [1 .. max_param_words] of fix_word; { FONTDIMEN parameters }
np: 0 .. max_param_words; { the largest parameter set nonzero }
check_sum_specified: boolean; { did the user name the check sum? }
bchar: 0 .. 256; { the right boundary character, or 256 if unspecified }
vf: array [0 .. vf_size] of byte; { stored bytes for VF file }
vf_ptr: 0 .. vf_size; { first unused location in vf }
vttitle_start: 0 .. vf_size; { starting location of VTITLE string }
vttitle_length: byte; { length of VTITLE string }
packet_start: array [byte] of 0 .. vf_size; { beginning location of character packet }
packet_length: array [byte] of integer; { length of character packet }
font_ptr: 0 .. 256; { number of distinct local fonts seen }
cur_font: 0 .. 256; { number of the current local font }
fname_start: array [byte] of 0 .. vf_size; { beginning of local font name }
fname_length: array [byte] of byte; { length of local font name }
farea_start: array [byte] of 0 .. vf_size; { beginning of local font area }
farea_length: array [byte] of byte; { length of local font area }
font_checksum: array [byte] of four_bytes; { local font checksum }
font_number: array [0 .. 256] of four_bytes; { local font id number }
font_at: array [byte] of fix_word; { local font “at size” }
font_dsize: array [byte] of fix_word; { local font design size }

```

**78.** ⟨Types in the outer block 23⟩ +≡

*header\_index* = 0 .. *max\_header\_bytes*; *indx* = 0 .. '77777;

**79.** ⟨Local variables for initialization 25⟩ +≡

*d*: *header\_index*; { an index into *header\_bytes* }

80. We start by setting up the default values.

```
define check_sum_loc = 0
define design_size_loc = 4
define coding_scheme_loc = 8
define family_loc = coding_scheme_loc + 40
define seven_flag_loc = family_loc + 20
define face_loc = seven_flag_loc + 3

⟨ Set initial values 6 ⟩ +≡
for d ← 0 to 18 * 4 - 1 do header_bytes[d] ← 0;
header_bytes[8] ← 11; header_bytes[9] ← "U"; header_bytes[10] ← "N"; header_bytes[11] ← "S";
header_bytes[12] ← "P"; header_bytes[13] ← "E"; header_bytes[14] ← "C"; header_bytes[15] ← "I";
header_bytes[16] ← "F"; header_bytes[17] ← "I"; header_bytes[18] ← "E"; header_bytes[19] ← "D";
for d ← family_loc to family_loc + 11 do header_bytes[d] ← header_bytes[d - 40];
design_size ← 10 * unity; design_units ← unity; frozen_du ← false; seven_bit_safe_flag ← false;
header_ptr ← 18 * 4; nl ← 0; min_nl ← 0; nk ← 0; ne ← 0; np ← 0;
check_sum_specified ← false; bchar ← 256;
vf_ptr ← 0; vtitle_start ← 0; vtitle_length ← 0; font_ptr ← 0;
for k ← 0 to 255 do packet_start[k] ← vf_size;
for k ← 0 to 127 do packet_length[k] ← 1;
for k ← 128 to 255 do packet_length[k] ← 2;
```

81. Most of the dimensions, however, go into the *memory* array. There are at most 257 widths, 257 heights, 257 depths, and 257 italic corrections, since the value 0 is required but it need not be used. So *memory* has room for 1028 entries, each of which is a *fix\_word*. An auxiliary table called *link* is used to link these words together in linear lists, so that sorting and other operations can be done conveniently.

We also add four “list head” words to the *memory* and *link* arrays; these are in locations *width* through *italic*, i.e., 1 through 4. For example, *link*[*height*] points to the smallest element in the sorted list of distinct heights that have appeared so far, and *memory*[*height*] is the number of distinct heights.

```
define mem_size = 1028 + 4 { number of nonzero memory addresses }

⟨ Types in the outer block 23 ⟩ +≡
pointer = 0 .. mem_size; { an index into memory }
```

82. The arrays *char\_wd*, *char\_ht*, *char\_dp*, and *char\_ic* contain pointers to the *memory* array entries where the corresponding dimensions appear. Two other arrays, *char\_tag* and *char\_remainder*, hold the other information that TFM files pack into a *char\_info\_word*.

```
define no_tag = 0 { vanilla character }
define lig_tag = 1 { character has a ligature/kerning program }
define list_tag = 2 { character has a successor in a charlist }
define ext_tag = 3 { character is extensible }
define bchar_label ≡ char_remainder[256] { beginning of ligature program for left boundary }

⟨ Globals in the outer block 5 ⟩ +≡
memory: array [pointer] of fix_word; { character dimensions and kerns }
mem_ptr: pointer; { largest memory word in use }
link: array [pointer] of pointer; { to make lists of memory items }
char_wd: array [byte] of pointer; { pointers to the widths }
char_ht: array [byte] of pointer; { pointers to the heights }
char_dp: array [byte] of pointer; { pointers to the depths }
char_ic: array [byte] of pointer; { pointers to italic corrections }
char_tag: array [byte] of no_tag .. ext_tag; { character tags }
char_remainder: array [0 .. 256] of 0 .. 65535;
{ pointers to ligature labels, next larger characters, or extensible characters }
```

83. { Local variables for initialization 25 } +≡  
 $c$ : byte; { runs through all character codes }

84. { Set initial values 6 } +≡  
 $bchar\_label \leftarrow '777777';$   
**for**  $c \leftarrow 0$  **to** 255 **do**  
  **begin**  $char\_wd[c] \leftarrow 0$ ;  $char\_ht[c] \leftarrow 0$ ;  $char\_dp[c] \leftarrow 0$ ;  $char\_ic[c] \leftarrow 0$ ;  
     $char\_tag[c] \leftarrow no\_tag$ ;  $char\_remainder[c] \leftarrow 0$ ;  
  **end**;  
 $memory[0] \leftarrow '1777777777777777'$ ; { an “infinite” element at the end of the lists }  
 $memory[width] \leftarrow 0$ ;  $link[width] \leftarrow 0$ ; { width list is empty }  
 $memory[height] \leftarrow 0$ ;  $link[height] \leftarrow 0$ ; { height list is empty }  
 $memory[depth] \leftarrow 0$ ;  $link[depth] \leftarrow 0$ ; { depth list is empty }  
 $memory[italic] \leftarrow 0$ ;  $link[italic] \leftarrow 0$ ; { italic list is empty }  
 $mem\_ptr \leftarrow italic$ ;

85. As an example of these data structures, let us consider the simple routine that inserts a potentially new element into one of the dimension lists. The first parameter indicates the list head (i.e.,  $h = width$  for the width list, etc.); the second parameter is the value that is to be inserted into the list if it is not already present. The procedure returns the value of the location where the dimension appears in  $memory$ . The fact that  $memory[0]$  is larger than any legal dimension makes the algorithm particularly short.

We do have to handle two somewhat subtle situations. A width of zero must be put into the list, so that a zero-width character in the font will not appear to be nonexistent (i.e., so that its  $char\_wd$  index will not be zero), but this does not need to be done for heights, depths, or italic corrections. Furthermore, it is necessary to test for memory overflow even though we have provided room for the maximum number of different dimensions in any legal font, since the VPL file might foolishly give any number of different sizes to the same character.

```
function sort_in( $h$  : pointer;  $d$  : fix_word): pointer; { inserts into list }
  var  $p$ : pointer; { the current node of interest }
  begin if ( $d = 0$ )  $\wedge$  ( $h \neq width$ ) then sort_in  $\leftarrow 0$ 
  else begin  $p \leftarrow h$ ;
    while  $d \geq memory[link[p]]$  do  $p \leftarrow link[p]$ ;
    if ( $d = memory[p]$ )  $\wedge$  ( $p \neq h$ ) then sort_in  $\leftarrow p$ 
    else if  $mem\_ptr = mem\_size$  then
      begin err_print(`Memory_overflow:_more_than_1028_widths,_etc`);
        print_ln(`Congratulations!_It's_hard_to_make_this_error.`); sort_in  $\leftarrow p$ ;
      end
    else begin incr(mem_ptr);  $memory[mem\_ptr] \leftarrow d$ ;  $link[mem\_ptr] \leftarrow link[p]$ ;  $link[p] \leftarrow mem\_ptr$ ;
      incr(memory[h]); sort_in  $\leftarrow mem\_ptr$ ;
    end;
  end;
end;
```

**86.** When these lists of dimensions are eventually written to the TFM file, we may have to do some rounding of values, because the TFM file allows at most 256 widths, 16 heights, 16 depths, and 64 italic corrections. The following procedure takes a given list head  $h$  and a given dimension  $d$ , and returns the minimum  $m$  such that the elements of the list can be covered by  $m$  intervals of width  $d$ . It also sets  $next\_d$  to the smallest value  $d' > d$  such that the covering found by this procedure would be different. In particular, if  $d = 0$  it computes the number of elements of the list, and sets  $next\_d$  to the smallest distance between two list elements. (The covering by intervals of width  $next\_d$  is not guaranteed to have fewer than  $m$  elements, but in practice this seems to happen most of the time.)

```
{ Globals in the outer block 5 } +≡
next_d: fix_word; { the next larger interval that is worth trying }
```

**87.** Once again we can make good use of the fact that  $memory[0]$  is “infinite.”

```
function min_cover(h : pointer; d : fix_word): integer;
var p: pointer; { the current node of interest }
l: fix_word; { the least element covered by the current interval }
m: integer; { the current size of the cover being generated }
begin m ← 0; p ← link[h]; next_d ← memory[0];
while p ≠ 0 do
begin incr(m); l ← memory[p];
while memory[link[p]] ≤ l + d do p ← link[p];
p ← link[p];
if memory[p] - l < next_d then next_d ← memory[p] - l;
end;
min_cover ← m;
end;
```

**88.** The following procedure uses  $min\_cover$  to determine the smallest  $d$  such that a given list can be covered with at most a given number of intervals.

```
function shorten(h : pointer; m : integer): fix_word; { finds best way to round }
var d: fix_word; { the current trial interval length }
k: integer; { the size of a minimum cover }
begin if memory[h] > m then
begin excess ← memory[h] - m; k ← min_cover(h, 0); d ← next_d; { now the answer is at least d }
repeat d ← d + d; k ← min_cover(h, d);
until k ≤ m; { first we ascend rapidly until finding the range }
d ← d div 2; k ← min_cover(h, d); { now we run through the feasible steps }
while k > m do
begin d ← next_d; k ← min_cover(h, d);
end;
shorten ← d;
end
else shorten ← 0;
end;
```

**89.** When we are nearly ready to output the TFM file, we will set  $index[p] ← k$  if the dimension in  $memory[p]$  is being rounded to the  $k$ th element of its list.

```
{ Globals in the outer block 5 } +≡
index: array [pointer] of byte;
excess: byte; { number of words to remove, if list is being shortened }
```

90. Here is the procedure that sets the *index* values. It also shortens the list so that there is only one element per covering interval; the remaining elements are the midpoints of their clusters.

```

procedure set_indices(h : pointer; d : fix_word); { reduces and indexes a list }
  var p: pointer; { the current node of interest }
    q: pointer; { trails one step behind p }
    m: byte; { index number of nodes in the current interval }
    l: fix_word; { least value in the current interval }
  begin q ← h; p ← link[q]; m ← 0;
  while p ≠ 0 do
    begin incr(m); l ← memory[p]; index[p] ← m;
    while memory[link[p]] ≤ l + d do
      begin p ← link[p]; index[p] ← m; decr(excess);
        if excess = 0 then d ← 0;
        end;
      link[q] ← p; memory[p] ← l + (memory[p] - l) div 2; q ← p; p ← link[p];
    end;
    memory[h] ← m;
  end;

```

**91. The input phase.** We're ready now to read and parse the VPL file, storing property values as we go.

```
(Globals in the outer block 5) +≡
c: byte; { the current character or byte being processed }
x: fix_word; { current dimension of interest }
k: integer; { general-purpose index }
```

**92. (Read all the input 92)** ≡

```
cur_char ← " ";
repeat while cur_char = " " do get_next;
  if cur_char = "(" then (Read a font property value 94)
  else if (cur_char = ")") ∧ ¬input_has-ended then
    begin err_print('Extra_right_parenthesis'); incr(loc); cur_char ← " ";
    end
  else if ¬input_has-ended then junk_error;
until input_has-ended
```

This code is used in section 180.

**93.** The *junk\_error* routine just referred to is called when something appears in the forbidden area between properties of a property list.

```
procedure junk_error; { gets past no man's land }
begin err_print('There ``s_junk_here_that_is_not_in_parentheses'); skip_to_paren;
end;
```

**94.** For each font property, we are supposed to read the data from the left parenthesis that is the current value of *cur\_char* to the right parenthesis that matches it in the input. The main complication is to recover with reasonable grace from various error conditions that might arise.

```
(Read a font property value 94) ≡
begin get_name;
if cur_code = comment_code then skip_to_end_of_item
else if cur_code > character_code then
  flush_error('This_property_name_doesn``t_belong_on_the_outer_level')
  else begin (Read the font property value specified by cur_code 95);
    finish_the_property;
    end;
end
```

This code is used in section 92.

95.  $\langle \text{Read the font property value specified by } cur\_code \text{ 95} \rangle \equiv$

```

case cur_code of
  check_sum_code: begin check_sum_specified  $\leftarrow$  true; read_four_bytes(check_sum_loc);
  end;
  design_size_code:  $\langle \text{Read the design size 98} \rangle$ ;
  design_units_code:  $\langle \text{Read the design units 99} \rangle$ ;
  coding_scheme_code: read_BCPL(coding_scheme_loc, 40);
  family_code: read_BCPL(family_loc, 20);
  face_code: header_bytes[face_loc]  $\leftarrow$  get_byte;
  seven_bit_safe_flag_code:  $\langle \text{Read the seven-bit-safe flag 100} \rangle$ ;
  header_code:  $\langle \text{Read an indexed header word 101} \rangle$ ;
  font_dimen_code:  $\langle \text{Read font parameter list 102} \rangle$ ;
  lig_table_code: read_lig_kern;
  boundary_char_code: bchar  $\leftarrow$  get_byte;
  virtual_title_code: begin vtitle_start  $\leftarrow$  vf_ptr; copy_to_end_of_item;
    if vf_ptr  $>$  vtitle_start + 255 then
      begin err_print('VTITLE_clipped_to_255_characters'); vtitle_length  $\leftarrow$  255;
      end
    else vtitle_length  $\leftarrow$  vf_ptr - vtitle_start;
    end;
  map_font_code:  $\langle \text{Read a local font list 104} \rangle$ ;
  character_code: read_char_info;
end

```

This code is used in section 94.

96. The **case** statement just given makes use of three subroutines that we haven't defined yet. The first of these puts a 32-bit octal quantity into four specified bytes of the header block.

```

procedure read_four_bytes(l : header_index);
  begin get_four_bytes; header_bytes[l]  $\leftarrow$  c0; header_bytes[l + 1]  $\leftarrow$  c1; header_bytes[l + 2]  $\leftarrow$  c2;
  header_bytes[l + 3]  $\leftarrow$  c3;
end;

```

**97.** The second little procedure is used to scan a string and to store it in the “BCPL format” required by TFM files. The string is supposed to contain at most  $n$  bytes, including the first byte (which holds the length of the rest of the string).

```
procedure read_BCPL(l : header_index; n : byte);
  var k: header_index;
begin k ← l;
  while cur_char = " " do get_next;
  while (cur_char ≠ "(") ∧ (cur_char ≠ ")") do
    begin if k < l + n then incr(k);
    if k < l + n then header_bytes[k] ← cur_char;
    get_next;
    end;
  if k = l + n then
    begin err_print(`String is too long; its first ', n - 1 : 1, ` characters will be kept');
    decr(k);
    end;
  header_bytes[l] ← k - l;
  while k < l + n - 1 do { tidy up the remaining bytes by setting them to nulls }
    begin incr(k); header_bytes[k] ← 0;
    end;
  end;
```

**98.** {Read the design size 98} ≡

```
begin next_d ← get_fix;
if next_d < unity then err_print(`The design size must be at least 1')
else design_size ← next_d;
end
```

This code is used in section 95.

**99.** {Read the design units 99} ≡

```
begin next_d ← get_fix;
if next_d ≤ 0 then err_print(`The number of units per design size must be positive')
else if frozen_du then err_print(`Sorry, it's too late to change the design units')
  else design_units ← next_d;
end
```

This code is used in section 95.

**100.** {Read the seven-bit-safe flag 100} ≡

```
begin while cur_char = " " do get_next;
if cur_char = "T" then seven_bit_safe_flag ← true
else if cur_char = "F" then seven_bit_safe_flag ← false
  else err_print(`The flag value should be "TRUE" or "FALSE" ');
skip_to_paren;
end
```

This code is used in section 95.

101.  $\langle$  Read an indexed header word 101  $\rangle \equiv$

```

begin  $c \leftarrow get\_byte$ ;
if  $c < 18$  then skip_error(`HEADER_indices_should_be_18_or_more')
else if  $4 * c + 4 > max\_header\_bytes$  then
    skip_error(`This_HEADER_index_is_too_big_for_my_present_table_size')
else begin while  $header\_ptr < 4 * c + 4$  do
    begin  $header\_bytes[header\_ptr] \leftarrow 0$ ; incr(header_ptr);
    end;
    read_four_bytes( $4 * c$ );
    end;
end

```

This code is used in section 95.

102. The remaining kinds of font property values that need to be read are those that involve property lists on higher levels. Each of these has a loop similar to the one that was used at level zero. Then we put the right parenthesis back so that ‘*finish\_the\_property*’ will be happy; there is probably a more elegant way to do this.

```

define finish_inner_property_list  $\equiv$ 
begin decr(loc); incr(level); cur_char  $\leftarrow ")$ ;
end

⟨Read font parameter list 102⟩  $\equiv$ 
begin while  $level = 1$  do
begin while  $cur\_char = " \wedge$  do get.next;
if  $cur\_char = "("$  then ⟨Read a parameter value 103⟩
else if  $cur\_char = ")"$  then skip_to_end_of_item
else junk_error;
end;
finish_inner_property_list;
end

```

This code is used in section 95.

103.  $\langle$  Read a parameter value 103  $\rangle \equiv$

```

begin get_name;
if cur_code = comment_code then skip_to_end_of_item
else if ( $cur\_code < parameter\_code$ )  $\vee$  ( $cur\_code \geq char\_wd\_code$ ) then
    flush_error(`This_property_name_doesn't_belong_in_a_FONTDIMEN_list')
else begin if  $cur\_code = parameter\_code$  then  $c \leftarrow get\_byte$ 
    else  $c \leftarrow cur\_code - parameter\_code$ ;
    if  $c = 0$  then flush_error(`PARAMETER_index_must_not_be_zero')
    else if  $c > max\_param\_words$  then
        flush_error(`This_PARAMETER_index_is_too_big_for_my_present_table_size')
    else begin while  $np < c$  do
        begin incr(np); param[np]  $\leftarrow 0$ ;
        end;
        param[c]  $\leftarrow get\_fix$ ; finish_the_property;
        end;
    end;
end

```

This code is used in section 102.

**104.** **define** *numbers\_differ*  $\equiv$  (*font\_number[cur\_font].b3*  $\neq$  *font\_number[font\_ptr].b3*)  $\vee$   
           (*font\_number[cur\_font].b2*  $\neq$  *font\_number[font\_ptr].b2*)  $\vee$   
           (*font\_number[cur\_font].b1*  $\neq$  *font\_number[font\_ptr].b1*)  $\vee$   
           (*font\_number[cur\_font].b0*  $\neq$  *font\_number[font\_ptr].b0*)

*<Read a local font list 104>*  $\equiv$   
**begin** *get\_four\_bytes*; *font\_number[font\_ptr]*  $\leftarrow$  *cur\_bytes*; *cur\_font*  $\leftarrow$  0;  
**while** *numbers\_differ* **do** *incr(cur\_font)*;  
**if** *cur\_font* = *font\_ptr* **then** { it's a new font number }  
**if** *font\_ptr* < 256 **then** { Initialize a new local font 105 }  
**else** *err\_print*(`I can handle only 256 different mapfonts');  
**if** *cur\_font* = *font\_ptr* **then** *skip\_to\_end\_of\_item*  
**else while** *level* = 1 **do**  
**begin while** *cur\_char* = " " **do** *get.next*;  
**if** *cur\_char* = "(" **then** { Read a local font property 106 }  
**else if** *cur\_char* = ")" **then** *skip\_to\_end\_of\_item*  
**else** *junk\_error*;  
**end**;  
*finish\_inner\_property\_list*;  
**end**

This code is used in section 95.

**105.** { Initialize a new local font 105 }  $\equiv$   
**begin** *incr(font\_ptr)*; *fname\_start[cur\_font]*  $\leftarrow$  *vf\_size*; *fname\_length[cur\_font]*  $\leftarrow$  4; { NULL }  
*farea\_start[cur\_font]*  $\leftarrow$  *vf\_size*; *farea\_length[cur\_font]*  $\leftarrow$  0; *font\_checksum[cur\_font]*  $\leftarrow$  *zero\_bytes*;  
*font\_at[cur\_font]*  $\leftarrow$  '4000000'; { denotes design size of this virtual font }  
*font\_dsize[cur\_font]*  $\leftarrow$  '50000000; { the fix\_word for 10 }  
**end**

This code is used in section 104.

**106.** { Read a local font property 106 }  $\equiv$   
**begin** *get\_name*;  
**if** *cur\_code* = *comment\_code* **then** *skip\_to\_end\_of\_item*  
**else if** (*cur\_code* < *font\_name\_code*)  $\vee$  (*cur\_code* > *font\_dsize\_code*) **then**  
*flush\_error*(`This property name doesn't belong in a MAPFONT list')  
**else begin case** *cur\_code* **of**  
*font\_name\_code*: { Read a local font name 107 };  
*font\_area\_code*: { Read a local font area 108 };  
*font\_checksum\_code*: **begin** *get\_four\_bytes*; *font\_checksum[cur\_font]*  $\leftarrow$  *cur\_bytes*;  
**end**;  
*font\_at\_code*: **begin** *frozen\_du*  $\leftarrow$  *true*;  
**if** *design\_units* = *unity* **then** *font\_at[cur\_font]*  $\leftarrow$  *get\_fix*  
**else** *font\_at[cur\_font]*  $\leftarrow$  *round*((*get\_fix* / *design\_units*) \* 1048576.0);  
**end**;  
*font\_dsize\_code*: *font\_dsize[cur\_font]*  $\leftarrow$  *get\_fix*;  
**end**; { there are no other cases }  
*finish\_the\_property*;  
**end**;  
**end**

This code is used in section 104.

**107.**  $\langle$  Read a local font name 107  $\rangle \equiv$

```
begin fname_start[cur_font] ← vf_ptr; copy_to_end_of_item;
if vf_ptr > fname_start[cur_font] + 255 then
begin err_print(`FONTNAME_clipped_to_255_characters`); fname_length[cur_font] ← 255;
end
else fname_length[cur_font] ← vf_ptr - fname_start[cur_font];
end
```

This code is used in section 106.

**108.**  $\langle$  Read a local font area 108  $\rangle \equiv$

```
begin farea_start[cur_font] ← vf_ptr; copy_to_end_of_item;
if vf_ptr > farea_start[cur_font] + 255 then
begin err_print(`FONAREA_clipped_to_255_characters`); farea_length[cur_font] ← 255;
end
else farea_length[cur_font] ← vf_ptr - farea_start[cur_font];
end
```

This code is used in section 106.

**109.**  $\langle$  Read ligature/kern list 109  $\rangle \equiv$

```
begin lk_step-ended ← false;
while level = 1 do
begin while cur_char = "\ " do get_next;
if cur_char = "(" then ⟨Read a ligature/kern command 110⟩
else if cur_char = ")" then skip_to_end_of_item
else junk_error;
end;
finish_inner_property_list;
end
```

This code is used in section 180.

**110.**  $\langle$  Read a ligature/kern command 110  $\rangle \equiv$

```
begin get_name;
if cur_code = comment_code then skip_to_end_of_item
else if cur_code < label_code then
flush_error(`This_property_name doesn't belong in a LIGTABLE list`)
else begin case cur_code of
label_code: ⟨Read a label step 112⟩;
stop_code: ⟨Read a stop step 114⟩;
skip_code: ⟨Read a skip step 115⟩;
kern_code: ⟨Read a kerning step 117⟩;
lig_code, lig_code + 1, lig_code + 2, lig_code + 3, lig_code + 5, lig_code + 6, lig_code + 7, lig_code + 11:
⟨Read a ligature step 116⟩;
end; { there are no other cases  $\geq$  label_code }
finish_the_property;
end;
end
```

This code is used in section 109.

**111.** When a character is about to be tagged, we call the following procedure so that an error message is given in case of multiple tags.

```
procedure check_tag(c : byte); { print error if c already tagged }
begin case char_tag[c] of
  no_tag: do_nothing;
  lig_tag: err_print(`This character already appeared in a LIGTABLE LABEL`);
  list_tag: err_print(`This character already has a NEXTLARGER spec`);
  ext_tag: err_print(`This character already has a VARCHAR spec`);
end;
end;
```

**112.**  $\langle$  Read a label step 112  $\rangle \equiv$

```
begin while cur_char = " " do get_next;
if cur_char = "B" then
  begin bchar_label ← nl; skip_to_paren; { LABEL BOUNDARYCHAR }
  end
else begin backup; c ← get_byte; check_tag(c); char_tag[c] ← lig_tag; char_remainder[c] ← nl;
  end;
if min_nl ≤ nl then min_nl ← nl + 1;
lk_step_ended ← false;
end
```

This code is used in section 110.

**113.** define stop\_flag = 128 { value indicating ‘STOP’ in a lig/kern program }

```
define kern_flag = 128 { op code for a kern step }
```

$\langle$  Globals in the outer block 5  $\rangle \equiv$

```
lk_step_ended: boolean; { was the last LIGTABLE property LIG or KRN? }
kern_ptr: 0 .. max_kerns; { an index into kern }
```

**114.**  $\langle$  Read a stop step 114  $\rangle \equiv$

```
if ¬lk_step_ended then err_print(`STOP must follow LIG or KRN`)
else begin lig_kern[nl - 1].b0 ← stop_flag; lk_step_ended ← false;
end
```

This code is used in section 110.

**115.**  $\langle$  Read a skip step 115  $\rangle \equiv$

```
if ¬lk_step_ended then err_print(`SKIP must follow LIG or KRN`)
else begin c ← get_byte;
  if c ≥ 128 then err_print(`Maximum SKIP amount is 127`)
  else if nl + c ≥ max_lig_steps then err_print(`Sorry, LIGTABLE too long for me to handle`)
  else begin lig_kern[nl - 1].b0 ← c;
    if min_nl ≤ nl + c then min_nl ← nl + c + 1;
    end;
  lk_step_ended ← false;
end
```

This code is used in section 110.

**116.**  $\langle$  Read a ligature step 116  $\rangle \equiv$

```
begin lig_kern[nl].b0 ← 0; lig_kern[nl].b2 ← cur_code − lig_code; lig_kern[nl].b1 ← get_byte;
lig_kern[nl].b3 ← get_byte;
if nl ≥ max_lig_steps − 1 then err_print(`Sorry, LIGTABLE too long for me to handle')
else incr(nl);
lk_step_ended ← true;
end
```

This code is used in section 110.

**117.**  $\langle$  Read a kerning step 117  $\rangle \equiv$

```
begin lig_kern[nl].b0 ← 0; lig_kern[nl].b1 ← get_byte; kern[nk] ← get_fix; krn_ptr ← 0;
while kern[krn_ptr] ≠ kern[nk] do incr(krn_ptr);
if krn_ptr = nk then
begin if nk < max_kerns then incr(nk)
else begin err_print(`Sorry, too many different kerns for me to handle'); decr(krn_ptr);
end;
end;
lig_kern[nl].b2 ← kern_flag + (krn_ptr div 256); lig_kern[nl].b3 ← krn_ptr mod 256;
if nl ≥ max_lig_steps − 1 then err_print(`Sorry, LIGTABLE too long for me to handle')
else incr(nl);
lk_step_ended ← true;
end
```

This code is used in section 110.

**118.** Finally we come to the part of VPtoVF's input mechanism that is used most, the processing of individual character data.

$\langle$  Read character info list 118  $\rangle \equiv$

```
begin c ← get_byte; { read the character code that is being specified }
⟨ Print c in octal notation 137 ⟩;
while level = 1 do
begin while cur_char = " " do get_next;
if cur_char = "(" then ⟨ Read a character property 119 ⟩
else if cur_char = ")" then skip_to_end_of_item
else junk_error;
end;
if char_wd[c] = 0 then char_wd[c] ← sort_in(width, 0); { legitimatize c }
finish_inner_property_list;
end
```

This code is used in section 180.

**119.**  $\langle$  Read a character property 119  $\rangle \equiv$

```

begin get_name;
if cur_code = comment_code then skip_to_end_of_item
else if (cur_code < char_wd_code)  $\vee$  (cur_code > var_char_code) then
    flush_error(`This_property_name_doesn't_belong_in_a_CHARACTER_list')
else begin case cur_code of
    char_wd_code: char_wd[c]  $\leftarrow$  sort_in(width, get_fix);
    char_ht_code: char_ht[c]  $\leftarrow$  sort_in(height, get_fix);
    char_dp_code: char_dp[c]  $\leftarrow$  sort_in(depth, get_fix);
    char_ic_code: char_ic[c]  $\leftarrow$  sort_in(italic, get_fix);
    next_larger_code: begin check_tag(c); char_tag[c]  $\leftarrow$  list_tag; char_remainder[c]  $\leftarrow$  get_byte;
        end;
    map_code: read_packet(c);
    var_char_code:  $\langle$  Read an extensible recipe for c 120  $\rangle$ ;
        end;
    finish_the_property;
    end;
end

```

This code is used in section 118.

**120.**  $\langle$  Read an extensible recipe for c 120  $\rangle \equiv$

```

begin if ne = 256 then err_print(`At_most_256_VARCHAR_specs_are_allowed')
else begin check_tag(c); char_tag[c]  $\leftarrow$  ext_tag; char_remainder[c]  $\leftarrow$  ne;
exten[ne]  $\leftarrow$  zero_bytes;
while level = 2 do
    begin while cur_char = "_" do get_next;
    if cur_char = "(" then  $\langle$  Read an extensible piece 121  $\rangle$ 
    else if cur_char = ")" then skip_to_end_of_item
        else junk_error;
    end;
    incr(ne); finish_inner_property_list;
    end;
end

```

This code is used in section 119.

**121.**  $\langle$  Read an extensible piece 121  $\rangle \equiv$

```

begin get_name;
if cur_code = comment_code then skip_to_end_of_item
else if (cur_code < var_char_code + 1)  $\vee$  (cur_code > var_char_code + 4) then
    flush_error(`This_property_name_doesn't_belong_in_a_VARCHAR_list')
else begin case cur_code - (var_char_code + 1) of
    0: exten[ne].b0  $\leftarrow$  get_byte;
    1: exten[ne].b1  $\leftarrow$  get_byte;
    2: exten[ne].b2  $\leftarrow$  get_byte;
    3: exten[ne].b3  $\leftarrow$  get_byte;
    end;
    finish_the_property;
    end;
end

```

This code is used in section 120.

**122. Assembling the mappings.** Each MAP property is a sequence of DVI instructions, for which we need to know some of the opcodes.

```
define set_char_0 = 0 { DVI command to typeset character 0 and move right }
define set1 = 128 { typeset a character and move right }
define set_rule = 132 { typeset a rule and move right }
define push = 141 { save the current positions }
define pop = 142 { restore previous positions }
define right1 = 143 { move right }
define w0 = 147 { move right by w }
define w1 = 148 { move right and set w }
define x0 = 152 { move right by x }
define x1 = 153 { move right and set x }
define down1 = 157 { move down }
define y0 = 161 { move down by y }
define y1 = 162 { move down and set y }
define z0 = 166 { move down by z }
define z1 = 167 { move down and set z }
define fnt_num_0 = 171 { set current font to 0 }
define fnt1 = 235 { set current font }
define xxx1 = 239 { extension to DVI primitives }
define xxx4 = 242 { potentially long extension to DVI primitives }
define fnt_def1 = 243 { define the meaning of a font number }
define pre = 247 { preamble }
define post = 248 { postamble beginning }
```

**123.** We keep stacks of movement values, in order to optimize the DVI code in simple cases.

```
{ Globals in the outer block 5 } +≡
hstack: array [0 .. max_stack] of 0 .. 2; { number of known horizontal movements }
vstack: array [0 .. max_stack] of 0 .. 2; { number of known vertical movements }
wstack, xstack, ystack, zstack: array [0 .. max_stack] of fix_word;
stack_ptr: 0 .. max_stack;
```

**124.** The packet is built by straightforward assembly of DVI instructions.

```

⟨ Declare the vf_fix procedure 128 ⟩
procedure read_packet(c : byte);
  var cc: byte; { character being typeset }
  x: fix-word; { movement }
  h, v: 0 .. 2; { top of hstack and vstack }
  special_start: 0 .. vf_size; { location of xxx1 command }
  k: 0 .. vf_size; { loop index }
begin packet_start[c] ← vf_ptr; stack_ptr ← 0; h ← 0; v ← 0; cur_font ← 0;
while level = 2 do
  begin while cur_char = " " do get_next;
  if cur_char = "(" then ⟨ Read and assemble a list of DVI commands 125 ⟩
  else if cur_char = ")" then skip_to_end_of_item
    else junk_error;
  end;
while stack_ptr > 0 do
  begin err_print(`Missing_`POP_`supplied`); vf_store(pop); decr(stack_ptr);
  end;
packet_length[c] ← vf_ptr - packet_start[c]; finish_inner_property_list;
end;
```

**125.** ⟨ Read and assemble a list of DVI commands 125 ⟩ ≡

```

begin get_name;
if cur_code = comment_code then skip_to_end_of_item
else if (cur_code < select_font_code) ∨ (cur_code > special_hex_code) then
  flush_error(`This_property_name_doesn't_belong_in_a_MAP_list`)
else begin case cur_code of
  select_font_code: ⟨ Assemble a font selection 126 ⟩;
  set_char_code: ⟨ Assemble a typesetting instruction 127 ⟩;
  set_rule_code: ⟨ Assemble a rulesetting instruction 129 ⟩;
  move_right_code, move_right_code + 1: ⟨ Assemble a horizontal movement 130 ⟩;
  move_down_code, move_down_code + 1: ⟨ Assemble a vertical movement 131 ⟩;
  push_code: ⟨ Assemble a stack push 132 ⟩;
  pop_code: ⟨ Assemble a stack pop 133 ⟩;
  special_code, special_hex_code: ⟨ Assemble a special command 134 ⟩;
end;
finish_the_property;
end;
end
```

This code is used in section 124.

**126.** ⟨ Assemble a font selection 126 ⟩ ≡

```

begin get_four_bytes; font_number[font_ptr] ← cur_bytes; cur_font ← 0;
while numbers_differ do incr(cur_font);
if cur_font = font_ptr then err_print(`Undefined_MAPFONT_cannot_be_selected`)
else if cur_font < 64 then vf_store(fnt_num_0 + cur_font)
  else begin vf_store(fnt1); vf_store(cur_font);
  end;
end
```

This code is used in section 125.

**127.** *(Assemble a typesetting instruction 127) ≡*  
**if** *cur\_font = font\_ptr* **then** *err\_print(`Character cannot be typeset in undefined font`)*  
**else begin** *cc*  $\leftarrow$  *get\_byte*;  
  **if** *cc*  $\geq$  128 **then** *vf\_store*(*set1*);  
  *vf\_store*(*cc*);  
**end**

This code is used in section 125.

**128.** Here's a procedure that converts a *fix\_word* to a sequence of DVI bytes.

*(Declare the vf\_fix procedure 128) ≡*  
**procedure** *vf\_fix(opcode : byte; x : fix\_word);*  
  **var** *negative*: boolean; *k*: 0 .. 4; { number of bytes to typeset }  
  *t*: integer; { threshold }  
**begin** *frozen\_du*  $\leftarrow$  true;  
  **if** *design\_units*  $\neq$  unity **then** *x*  $\leftarrow$  round(*(x/design\_units) \* 1048576.0*);  
  **if** *x*  $\geq$  0 **then** *negative*  $\leftarrow$  false  
  **else begin** *negative*  $\leftarrow$  true; *x*  $\leftarrow$  -1 - *x*; **end**;  
  **if** *opcode* = 0 **then**  
    **begin** *k*  $\leftarrow$  4; *t*  $\leftarrow$  '100000000'; **end**  
  **else begin** *t*  $\leftarrow$  127; *k*  $\leftarrow$  1;  
    **while** *x*  $>$  *t* **do**  
      **begin** *t*  $\leftarrow$  256 \* *t* + 255; *incr(k)*;  
      **end**;  
      *vf\_store*(*opcode* + *k* - 1); *t*  $\leftarrow$  *t div 128* + 1;  
      **end**;  
    **repeat if** *negative* **then**  
      **begin** *vf\_store*(255 - (*x div t*)); *negative*  $\leftarrow$  false; *x*  $\leftarrow$  (*x div t*) \* *t* + *t* - 1 - *x*;  
      **end**  
    **else** *vf\_store*((*x div t*) mod 256);  
      *decr(k)*; *t*  $\leftarrow$  *t div 256*;  
    **until** *k* = 0;  
  **end**;

This code is used in section 124.

**129.** *(Assemble a rulesetting instruction 129) ≡*  
**begin** *vf\_store*(*set\_rule*); *vf\_fix(0, get\_fix)*; *vf\_fix(0, get\_fix)*;  
**end**

This code is used in section 125.

**130.** *(Assemble a horizontal movement 130) ≡*  
**begin if** *cur\_code* = move\_right\_code **then** *x*  $\leftarrow$  *get\_fix* **else** *x*  $\leftarrow$  -*get\_fix*;  
**if** *h* = 0 **then**  
  **begin** *wstack[stack\_ptr]*  $\leftarrow$  *x*; *h*  $\leftarrow$  1; *vf\_fix(w1, x)*; **end**  
**else if** *x* = *wstack[stack\_ptr]* **then** *vf\_store*(*w0*)  
  **else if** *h* = 1 **then**  
    **begin** *xstack[stack\_ptr]*  $\leftarrow$  *x*; *h*  $\leftarrow$  2; *vf\_fix(x1, x)*; **end**  
    **else if** *x* = *xstack[stack\_ptr]* **then** *vf\_store*(*x0*)  
    **else** *vf\_fix(right1, x)*;  
  **end**

This code is used in section 125.

**131.** ⟨ Assemble a vertical movement 131 ⟩ ≡

```

begin if cur_code = move_down_code then x ← get_fix else x ← -get_fix;
if v = 0 then
  begin ystack[stack_ptr] ← x; v ← 1; vf_fix(y1, x); end
else if x = ystack[stack_ptr] then vf_store(y0)
else if v = 1 then
  begin zstack[stack_ptr] ← x; v ← 2; vf_fix(z1, x); end
  else if x = zstack[stack_ptr] then vf_store(z0)
  else vf_fix(down1, x);
end

```

This code is used in section 125.

**132.** ⟨ Assemble a stack push 132 ⟩ ≡

```

if stack_ptr = max_stack then { too pushy }
  err_print(`Don't push so much---stack is full!')
else begin vf_store(push); hstack[stack_ptr] ← h;.vstack[stack_ptr] ← v; incr(stack_ptr); h ← 0; v ← 0;
end

```

This code is used in section 125.

**133.** ⟨ Assemble a stack pop 133 ⟩ ≡

```

if stack_ptr = 0 then err_print(`Empty stack cannot be popped')
else begin vf_store(pop); decr(stack_ptr); h ← hstack[stack_ptr]; v ← vstack[stack_ptr];
end

```

This code is used in section 125.

**134.** ⟨ Assemble a special command 134 ⟩ ≡

```

begin vf_store(xxx1); vf_store(0); { dummy length }
special_start ← vf_ptr;
if cur_code = special_code then copy_to_end_of_item
else begin repeat x ← get_hex;
  if cur_char > ")" then vf_store(x * 16 + get_hex);
  until cur_char ≤ ")";
end;
if vf_ptr - special_start > 255 then ⟨ Convert xxx1 command to xxxx4 135 ⟩
else vf[special_start - 1] ← vf_ptr - special_start;
end

```

This code is used in section 125.

**135.** ⟨ Convert xxx1 command to xxxx4 135 ⟩ ≡

```

if vf_ptr + 3 > vf_size then
  begin err_print(`Special command being clipped---no room left!');
  vf_ptr ← special_start + 255; vf[special_start - 1] ← 255;
end
else begin for k ← vf_ptr downto special_start do vf[k + 3] ← vf[k];
  x ← vf_ptr - special_start; vf_ptr ← vf_ptr + 3; vf[special_start - 2] ← xxxx4;
  vf[special_start - 1] ← x div 100000000; vf[special_start] ← (x div 200000) mod 256;
  vf[special_start + 1] ← (x div 400) mod 256; vf[special_start + 2] ← x mod 256;
end

```

This code is used in section 134.

**136.** The input routine is now complete except for the following code, which prints a progress report as the file is being read.

```
procedure print_octal(c : byte); { prints three octal digits }
begin print('---,(c div 64) : 1,((c div 8) mod 8) : 1,(c mod 8) : 1);
end;
```

**137.** ⟨Print  $c$  in octal notation 137⟩ ≡

```
begin if chars_on_line = 8 then
  begin print_ln(' ');
    chars_on_line ← 1;
  end
else begin if chars_on_line > 0 then print(' ');
  incr(chars_on_line);
end;
print_octal(c); { progress report }
end
```

This code is used in section 118.

**138. The checking and massaging phase.** Once the whole VPL file has been read in, we must check it for consistency and correct any errors. This process consists mainly of running through the characters that exist and seeing if they refer to characters that don't exist. We also compute the true value of *seven\_unsafe*; we make sure that the charlists and ligature programs contain no loops; and we shorten the lists of widths, heights, depths, and italic corrections, if necessary, to keep from exceeding the required maximum sizes.

⟨ Globals in the outer block 5 ⟩ +≡  
*seven\_unsafe*: boolean; { do seven-bit characters generate eight-bit ones? }

**139. ⟨ Correct and check the information 139 ⟩ ≡**

```

if nl > 0 then ⟨ Make sure the ligature/kerning program ends appropriately 145 ⟩;
seven_unsafe ← false;
for c ← 0 to 255 do
  if char_wd[c] ≠ 0 then ⟨ For all characters g generated by c, make sure that char_wd[g] is nonzero,
    and set seven_unsafe if c < 128 ≤ g 140 ⟩;
  if bchar_label < 77777 then
    begin c ← 256; ⟨ Check ligature program of c 149 ⟩;
    end;
  if seven_bit_safe_flag ∧ seven_unsafe then print_ln(`The font is not really seven-bit-safe!`);
  ⟨ Check for infinite ligature loops 154 ⟩;
  ⟨ Doublecheck the lig/kern commands and the extensible recipes 155 ⟩;
  for c ← 0 to 255 do ⟨ Make sure that c is not the largest element of a charlist cycle 142 ⟩;
  ⟨ Put the width, height, depth, and italic lists into final form 144 ⟩

```

This code is used in section 180.

**140.** The checking that we need in several places is accomplished by three macros that are only slightly tricky.

```

define existence_tail(#) ≡
  begin char_wd[g] ← sort_in(width, 0); print(#, ` `); print_octal(c);
  print_ln(`had no CHARACTER spec.`);
  end;
end

define check_existence_and_safety(#) ≡
  begin g ← #;
  if (g ≥ 128) ∧ (c < 128) then seven_unsafe ← true;
  if char_wd[g] = 0 then existence_tail

define check_existence(#) ≡
  begin g ← #;
  if char_wd[g] = 0 then existence_tail

⟨ For all characters g generated by c, make sure that char_wd[g] is nonzero, and set seven_unsafe if
  c < 128 ≤ g 140 ⟩ ≡
case char_tag[c] of
  no_tag: do_nothing;
  lig_tag: ⟨ Check ligature program of c 149 ⟩;
  list_tag: check_existence_and_safety(char_remainder[c])(`The character NEXTLARGER than`);
  ext_tag: ⟨ Check the pieces of exten[c] 141 ⟩;
end

```

This code is used in section 139.

**141.**  $\langle$  Check the pieces of  $exten[c]$  141  $\rangle \equiv$   
**begin if**  $exten[char\_remainder[c]].b0 > 0$  **then**  
   $check\_existence\_and\_safety(exten[char\_remainder[c]].b0)$ (‘TOP piece of character’);  
**if**  $exten[char\_remainder[c]].b1 > 0$  **then**  
   $check\_existence\_and\_safety(exten[char\_remainder[c]].b1)$ (‘MID piece of character’);  
**if**  $exten[char\_remainder[c]].b2 > 0$  **then**  
   $check\_existence\_and\_safety(exten[char\_remainder[c]].b2)$ (‘BOT piece of character’);  
   $check\_existence\_and\_safety(exten[char\_remainder[c]].b3)$ (‘REP piece of character’);  
**end**

This code is used in section 140.

**142.**  $\langle$  Make sure that  $c$  is not the largest element of a charlist cycle 142  $\rangle \equiv$   
**if**  $char\_tag[c] = list\_tag$  **then**  
  **begin**  $g \leftarrow char\_remainder[c]$ ;  
  **while** ( $g < c$ )  $\wedge (char\_tag[g] = list\_tag)$  **do**  $g \leftarrow char\_remainder[g]$ ;  
  **if**  $g = c$  **then**  
    **begin**  $char\_tag[c] \leftarrow no\_tag$ ;  
     $print(‘A cycle of NEXTLARGER characters has been broken at ‘)$ ;  $print\_octal(c)$ ;  
     $print\_ln(‘.’)$ ;  
    **end**;  
  **end**;  
**end**

This code is used in section 139.

**143.**  $\langle$  Globals in the outer block 5  $\rangle + \equiv$   
 $delta: fix\_word$ ; { size of the intervals needed for rounding }

**144. define**  $round\_message(\#) \equiv$   
**if**  $delta > 0$  **then**  
   $print\_ln(‘I had to round some , #, s by , (((delta+1)div2)/‘4000000) : 1 : 7, ‘units.)$   
 $\langle$  Put the width, height, depth, and italic lists into final form 144  $\rangle \equiv$   
   $delta \leftarrow shorten(width, 255)$ ;  $set\_indices(width, delta)$ ;  $round\_message(‘width’)$ ;  
   $delta \leftarrow shorten(height, 15)$ ;  $set\_indices(height, delta)$ ;  $round\_message(‘height’)$ ;  
   $delta \leftarrow shorten(depth, 15)$ ;  $set\_indices(depth, delta)$ ;  $round\_message(‘depth’)$ ;  
   $delta \leftarrow shorten(italic, 63)$ ;  $set\_indices(italic, delta)$ ;  $round\_message(‘italic correction’)$ ;

This code is used in section 139.

**145. define**  $clear\_lig\_kern\_entry \equiv$  { make an unconditional STOP }  
   $lig\_kern[nl].b0 \leftarrow 255$ ;  $lig\_kern[nl].b1 \leftarrow 0$ ;  $lig\_kern[nl].b2 \leftarrow 0$ ;  $lig\_kern[nl].b3 \leftarrow 0$   
 $\langle$  Make sure the ligature/kerning program ends appropriately 145  $\rangle \equiv$   
**begin if**  $bchar\_label < ‘77777$  **then** { make room for it }  
  **begin clear\_lig\_kern\_entry; incr(nl);**  
  **end;** {  $bchar\_label$  will be stored later }  
**while**  $min\_nl > nl$  **do**  
  **begin clear\_lig\_kern\_entry; incr(nl);**  
  **end;**  
**if**  $lig\_kern[nl - 1].b0 = 0$  **then**  $lig\_kern[nl - 1].b0 \leftarrow stop\_flag$ ;  
**end**

This code is used in section 139.

**146.** It's not trivial to check for infinite loops generated by repeated insertion of ligature characters. But fortunately there is a nice algorithm for such testing, copied here from the program **TFToPL** where it is explained further.

```
define simple = 0 {  $f(x, y) = z$  }
define left_z = 1 {  $f(x, y) = f(z, y)$  }
define right_z = 2 {  $f(x, y) = f(x, z)$  }
define both_z = 3 {  $f(x, y) = f(f(x, z), y)$  }
define pending = 4 {  $f(x, y)$  is being evaluated }
```

**147.** ⟨ Globals in the outer block 5 ⟩ +≡

```
lig_ptr: 0 .. max_lig_steps; { an index into lig_kern }
hash: array [0 .. hash_size] of 0 .. 66048; {  $256x + y + 1$  for  $x \leq 257$  and  $y \leq 255$  }
class: array [0 .. hash_size] of simple .. pending;
lig_z: array [0 .. hash_size] of 0 .. 257;
hash_ptr: 0 .. hash_size; { the number of nonzero entries in hash }
hash_list: array [0 .. hash_size] of 0 .. hash_size; { list of those nonzero entries }
h, hh: 0 .. hash_size; { indices into the hash table }
tt: idx; { temporary register }
x_lig_cycle, y_lig_cycle: 0 .. 256; { problematic ligature pair }
```

**148.** ⟨ Set initial values 6 ⟩ +≡

```
hash_ptr ← 0; y_lig_cycle ← 256;
for k ← 0 to hash_size do hash[k] ← 0;
```

**149.** define lig\_exam ≡ lig\_kern[lig\_ptr].b1

```
define lig_gen ≡ lig_kern[lig_ptr].b3
```

⟨ Check ligature program of c 149 ⟩ ≡

```
begin lig_ptr ← char_remainder[c];
repeat if hash_input(lig_ptr, c) then
  begin if lig_kern[lig_ptr].b2 < kern_flag then
    begin if lig_exam ≠ bchar then check_existence(lig_exam)(`LIG_character_examined_by`);
      check_existence(lig_gen)(`LIG_character_generated_by`);
      if lig_gen ≥ 128 then
        if (c < 128) ∨ (c = 256) then
          if (lig_exam < 128) ∨ (lig_exam = bchar) then seven_unsafe ← true;
    end
  else if lig_exam ≠ bchar then check_existence(lig_exam)(`KRN_character_examined_by`);
  end;
  if lig_kern[lig_ptr].b0 ≥ stop_flag then lig_ptr ← nl
  else lig_ptr ← lig_ptr + 1 + lig_kern[lig_ptr].b0;
until lig_ptr ≥ nl;
end
```

This code is used in sections 139 and 140.

**150.** The *hash\_input* procedure is copied from TFtoPL, but it is made into a boolean function that returns *false* if the ligature command was masked by a previous one.

```

function hash_input(p, c : indx): boolean;
    { enter data for character c and command in location p, unless it isn't new }
label 30; { go here for a quick exit }
var cc: simple .. both_z; { class of data being entered }
    zz: 0 .. 255; { function value or ligature character being entered }
    y: 0 .. 255; { the character after the cursor }
    key: integer; { value to be stored in hash }
    t: integer; { temporary register for swapping }
begin if hash_ptr = hash_size then
    begin hash_input ← false; goto 30; end;
{ Compute the command parameters y, cc, and zz 151 };
key ← 256 * c + y + 1; h ← (1009 * key) mod hash_size;
while hash[h] > 0 do
    begin if hash[h] ≤ key then
        begin if hash[h] = key then
            begin hash_input ← false; goto 30; { unused ligature command }
            end;
            t ← hash[h]; hash[h] ← key; key ← t; { do ordered-hash-table insertion }
            t ← class[h]; class[h] ← cc; cc ← t; { namely, do a swap }
            t ← lig_z[h]; lig_z[h] ← zz; zz ← t;
            end;
        if h > 0 then decr(h) else h ← hash_size;
        end;
        hash[h] ← key; class[h] ← cc; lig_z[h] ← zz; incr(hash_ptr); hash_list[hash_ptr] ← h;
        hash_input ← true;
    30: end;

```

**151.** { Compute the command parameters *y, cc*, and *zz* 151 } ≡  
 $y \leftarrow \text{lig\_kern}[p].b1; t \leftarrow \text{lig\_kern}[p].b2; cc \leftarrow \text{simple}; zz \leftarrow \text{lig\_kern}[p].b3;$   
**if** *t* ≥ kern\_flag **then** *zz* ← *y*  
**else begin case** *t* **of**  
 0, 6: *do\_nothing*; { LIG,/LIG> }  
 5, 11: *zz* ← *y*; { LIG/>, /LIG/>> }  
 1, 7: *cc* ← left\_z; { LIG/, /LIG/> }  
 2: *cc* ← right\_z; { /LIG }  
 3: *cc* ← both\_z; { /LIG/ }  
**end;** { there are no other cases }  
**end**

This code is used in section 150.

## 152. (More good stuff from TToPL.)

```

function f(h, x, y : indx): indx; forward; { compute f for arguments known to be in hash[h] }
function eval(x, y : indx): indx; { compute f(x, y) with hashtable lookup }

  var key: integer; { value sought in hash table }
  begin key  $\leftarrow$  256 * x + y + 1; h  $\leftarrow$  (1009 * key) mod hash_size;
  while hash[h] > key do
    if h > 0 then decr(h) else h  $\leftarrow$  hash_size;
    if hash[h] < key then eval  $\leftarrow$  y { not in ordered hash table }
    else eval  $\leftarrow$  f(h, x, y);
  end;

```

153. Pascal's beastly convention for *forward* declarations prevents us from saying **function** *f(h, x, y : indx): indx* here.

```

function f;
  begin case class[h] of
    simple: do_nothing;
    left_z: begin class[h]  $\leftarrow$  pending; lig_z[h]  $\leftarrow$  eval(lig_z[h], y); class[h]  $\leftarrow$  simple;
      end;
    right_z: begin class[h]  $\leftarrow$  pending; lig_z[h]  $\leftarrow$  eval(x, lig_z[h]); class[h]  $\leftarrow$  simple;
      end;
    both_z: begin class[h]  $\leftarrow$  pending; lig_z[h]  $\leftarrow$  eval(eval(x, lig_z[h]), y); class[h]  $\leftarrow$  simple;
      end;
    pending: begin x_lig_cycle  $\leftarrow$  x; y_lig_cycle  $\leftarrow$  y; lig_z[h]  $\leftarrow$  257; class[h]  $\leftarrow$  simple;
      end; { the value 257 will break all cycles, since it's not in hash }
    end; { there are no other cases }
    f  $\leftarrow$  lig_z[h];
  end;

```

## 154. { Check for infinite ligature loops 154 } ≡

```

if hash_ptr < hash_size then
  for hh  $\leftarrow$  1 to hash_size do
    begin tt  $\leftarrow$  hash_list[hh];
    if class[tt] > simple then { make sure f is well defined }
      tt  $\leftarrow$  f(tt, (hash[tt] - 1) div 256, (hash[tt] - 1) mod 256);
    end;
if (hash_ptr = hash_size)  $\vee$  (y_lig_cycle < 256) then
  begin if hash_ptr < hash_size then
    begin print(`Infinite ligature loop starting with `);
    if x_lig_cycle = 256 then print(`boundary`) else print_octal(x_lig_cycle);
    print(` and `); print_octal(y_lig_cycle); print_ln(`!`);
    end
  else print_ln(`Sorry, I haven't room for so many ligature/kern pairs!`);
  print_ln(`All ligatures will be cleared.`);
  for c  $\leftarrow$  0 to 255 do
    if char_tag[c] = lig_tag then
      begin char_tag[c] ← no_tag; char_remainder[c] ← 0;
      end;
    nl  $\leftarrow$  0; bchar  $\leftarrow$  256; bchar_label  $\leftarrow$  '777777';
  end

```

This code is used in section 139.

**155.** The lig/kern program may still contain references to nonexistent characters, if parts of that program are never used. Similarly, there may be extensible characters that are never used, because they were overridden by NEXTLARGER, say. This would produce an invalid TFM file; so we must fix such errors.

```

define double_check_tail(#)
    if char_wd[0] = 0 then char_wd[0] ← sort_in(width, 0);
    print(`Unused\_\_`, #, `refers\_\_to\_\_nonexistent\_\_character\_\_`); print_octal(c); print_ln(`!`);
    end ;
    end
define double_check_lig(#) ≡
    begin c ← lig_kern[lig_ptr].#;
    if char_wd[c] = 0 then
        if c ≠ bchar then
            begin lig_kern[lig_ptr].# ← 0; double_check_tail
define double_check_ext(#) ≡
    begin c ← exten[g].#;
    if c > 0 then
        if char_wd[c] = 0 then
            begin exten[g].# ← 0; double_check_tail
define double_check_rep(#) ≡
    begin c ← exten[g].#;
    if char_wd[c] = 0 then
        begin exten[g].# ← 0; double_check_tail
⟨ Doublecheck the lig/kern commands and the extensible recipes 155 ⟩ ≡
if nl > 0 then
    for lig_ptr ← 0 to nl – 1 do
        if lig_kern[lig_ptr].b2 < kern_flag then
            begin if lig_kern[lig_ptr].b0 < 255 then
                begin double_check_lig(b1)(`LIG\_\_step`); double_check_lig(b3)(`LIG\_\_step`);
                end;
            end
        else double_check_lig(b1)(`KRN\_\_step`);
if ne > 0 then
    for g ← 0 to ne – 1 do
        begin double_check_ext(b0)(`VARCHAR\_\_TOP`); double_check_ext(b1)(`VARCHAR\_\_MID`);
        double_check_ext(b2)(`VARCHAR\_\_BOT`); double_check_rep(b3)(`VARCHAR\_\_REP`);
        end

```

This code is used in section 139.

**156. The TFM output phase.** Now that we know how to get all of the font data correctly stored in VPtoVF's memory, it only remains to write the answers out.

First of all, it is convenient to have an abbreviation for output to the TFM file:

```
define out(#) ≡ write(tfm_file, #)
```

**157.** The general plan for producing TFM files is long but simple:

$\langle \text{Do the TFM output } 157 \rangle \equiv$

```
( Compute the twelve subfile sizes 159 );
( Output the twelve subfile sizes 160 );
( Output the header block 162 );
( Output the character info 164 );
( Output the dimensions themselves 166 );
( Output the ligature/kern program 171 );
( Output the extensible character recipes 172 );
( Output the parameters 173 )
```

This code is used in section 181.

**158.** A TFM file begins with 12 numbers that tell how big its subfiles are. We already know most of these numbers; for example, the number of distinct widths is  $\text{memory}[width] + 1$ , where the +1 accounts for the zero width that is always supposed to be present. But we still should compute the beginning and ending character codes (*bc* and *ec*), the number of header words (*lh*), and the total number of words in the TFM file (*lf*).

```
( Globals in the outer block 5 ) +≡
bc: byte; { the smallest character code in the font }
ec: byte; { the largest character code in the font }
lh: byte; { the number of words in the header block }
lf: 0 .. 32767; { the number of words in the entire TFM file }
not_found: boolean; { has a font character been found? }
temp_width: fix_word; { width being used to compute a check sum }
```

**159.** It might turn out that no characters exist at all. But VPtoVF keeps going and writes the TFM anyway. In this case *ec* will be 0 and *bc* will be 1.

```
( Compute the twelve subfile sizes 159 ) ≡
lh ← header_ptr div 4;
not_found ← true; bc ← 0;
while not_found do
  if (char_wd[bc] > 0) ∨ (bc = 255) then not_found ← false
  else incr(bc);
  not_found ← true; ec ← 255;
while not_found do
  if (char_wd[ec] > 0) ∨ (ec = 0) then not_found ← false
  else decr(ec);
  if bc > ec then bc ← 1;
  incr(memory[width]); incr(memory[height]); incr(memory[depth]); incr(memory[italic]);
  ( Compute the ligature/kern program offset 168 );
  lf ← 6 + lh + (ec - bc + 1) + memory[width] + memory[height] + memory[depth] + memory[italic] + nl +
    lk_offset + nk + ne + np;
```

This code is used in section 157.

**160.** **define** *out\_size*(#)  $\equiv$  *out*((#) **div** 256); *out*((#) **mod** 256)

*<Output the twelve subfile sizes 160>*  $\equiv$

```
out_size(lf); out_size(lh); out_size(bc); out_size(ec); out_size(memory[width]);
out_size(memory[height]); out_size(memory[depth]); out_size(memory[italic]); out_size(nl + lk_offset);
out_size(nk); out_size(ne); out_size(np);
```

This code is used in section 157.

**161.** The routines that follow need a few temporary variables of different types.

*<Globals in the outer block 5>*  $\equiv$

```
j: 0 .. max_header_bytes; { index into header_bytes }
p: pointer; { index into memory }
q: width .. italic; { runs through the list heads for dimensions }
par_ptr: 0 .. max_param_words; { runs through the parameters }
```

**162.** The header block follows the subfile sizes. The necessary information all appears in *header\_bytes*, except that the design size and the seven-bit-safe flag must still be set.

*<Output the header block 162>*  $\equiv$

```
if  $\neg$ check_sum_specified then { Compute the check sum 163 };
header_bytes[design_size_loc]  $\leftarrow$  design_size div '100000000; { this works since design_size > 0 }
header_bytes[design_size_loc + 1]  $\leftarrow$  (design_size div '200000) mod 256;
header_bytes[design_size_loc + 2]  $\leftarrow$  (design_size div 256) mod 256;
header_bytes[design_size_loc + 3]  $\leftarrow$  design_size mod 256;
if  $\neg$ seven_unsafe then header_bytes[seven_flag_loc]  $\leftarrow$  128;
for j  $\leftarrow$  0 to header_ptr - 1 do out(header_bytes[j]);
```

This code is used in section 157.

**163.** { Compute the check sum 163 }  $\equiv$

```
begin c0  $\leftarrow$  bc; c1  $\leftarrow$  ec; c2  $\leftarrow$  bc; c3  $\leftarrow$  ec;
for c  $\leftarrow$  bc to ec do
  if char_wd[c] > 0 then
    begin temp_width  $\leftarrow$  memory[char_wd[c]];
    if design_units  $\neq$  unity then temp_width  $\leftarrow$  round((temp_width / design_units) * 1048576.0);
    temp_width  $\leftarrow$  temp_width + (c + 4) * '20000000; { this should be positive }
    c0  $\leftarrow$  (c0 + c0 + temp_width) mod 255; c1  $\leftarrow$  (c1 + c1 + temp_width) mod 253;
    c2  $\leftarrow$  (c2 + c2 + temp_width) mod 251; c3  $\leftarrow$  (c3 + c3 + temp_width) mod 247;
    end;
    header_bytes[check_sum_loc]  $\leftarrow$  c0; header_bytes[check_sum_loc + 1]  $\leftarrow$  c1;
    header_bytes[check_sum_loc + 2]  $\leftarrow$  c2; header_bytes[check_sum_loc + 3]  $\leftarrow$  c3;
  end
```

This code is used in section 162.

**164.** The next block contains packed *char\_info*.

*<Output the character info 164>*  $\equiv$

```
index[0]  $\leftarrow$  0;
for c  $\leftarrow$  bc to ec do
  begin out(index[char_wd[c]]); out(index[char_ht[c]] * 16 + index[char_dp[c]]);
  out(index[char_ic[c]] * 4 + char_tag[c]); out(char_remainder[c]);
  end
```

This code is used in section 157.

**165.** When a scaled quantity is output, we may need to divide it by *design-units*. The following subroutine takes care of this, using floating point arithmetic only if *design-units*  $\neq 1.0$ .

```
procedure out_scaled(x : fix_word); { outputs a scaled fix_word }
  var n: byte; { the first byte after the sign }
    m: 0 .. 65535; { the two least significant bytes }
  begin if abs(x/design_units)  $\geq 16.0$  then
    begin print_ln(`The relative dimension, x/`4000000 : 1 : 3, `is too large. `);
      print(`Must be less than 16*designsize`);
      if design_units  $\neq$  unity then print(`=`, design_units/`200000 : 1 : 3, `designunits`);
      print_ln(` `); x  $\leftarrow 0$ ;
    end;
    if design_units  $\neq$  unity then x  $\leftarrow$  round((x/design_units) * 1048576.0);
    if x  $< 0$  then
      begin out(255); x  $\leftarrow$  x + `100000000;
      if x  $\leq 0$  then x  $\leftarrow 1$ ;
    end;
    else begin out(0);
      if x  $\geq 100000000$  then x  $\leftarrow 77777777$ ;
    end;
    n  $\leftarrow$  x div `200000; m  $\leftarrow$  x mod `200000; out(n); out(m div 256); out(m mod 256);
  end;
```

**166.** We have output the packed indices for individual characters. The scaled widths, heights, depths, and italic corrections are next.

{ Output the dimensions themselves 166 }  $\equiv$

```
for q  $\leftarrow$  width to italic do
  begin out(0); out(0); out(0); out(0); { output the zero word }
  p  $\leftarrow$  link[q]; { head of list }
  while p  $> 0$  do
    begin out_scaled(memory[p]); p  $\leftarrow$  link[p];
    end;
  end;
```

This code is used in section 157.

**167.** One embarrassing problem remains: The ligature/kern program might be very long, but the starting addresses in *char\_remainder* can be at most 255. Therefore we need to output some indirect address information; we want to compute *lk\_offset* so that addition of *lk\_offset* to all remainders makes all but *lk\_offset* distinct remainders less than 256.

For this we need a sorted table of all relevant remainders.

{ Globals in the outer block 5 }  $\equiv$

```
label_table: array [0 .. 256] of record rr: -1 .. 77777; { sorted label values }
  cc: byte; { associated characters }
end;
label_ptr: 0 .. 256; { index of highest entry in label_table }
sort_ptr: 0 .. 256; { index into label_table }
lk_offset: 0 .. 256; { smallest offset value that might work }
t: 0 .. 77777; { label value that is being redirected }
extra_loc_needed: boolean; { do we need a special word for bchar? }
```

**168.** ⟨ Compute the ligature/kern program offset 168 ⟩ ≡  
 ⟨ Insert all labels into *label\_table* 169 ⟩;  
**if** *bchar* < 256 **then**  
 begin *extra\_loc\_needed* ← *true*; *lk\_offset* ← 1;  
 end  
**else begin** *extra\_loc\_needed* ← *false*; *lk\_offset* ← 0;  
**end;**  
⟨ Find the minimum *lk\_offset* and adjust all remainders 170 ⟩;  
**if** *bchar\_label* < '77777 **then**  
begin *lig\_kern*[*nl* - 1].*b2* ← (*bchar\_label* + *lk\_offset*) **div** 256;  
*lig\_kern*[*nl* - 1].*b3* ← (*bchar\_label* + *lk\_offset*) **mod** 256;  
**end**

This code is used in section 159.

**169.** ⟨ Insert all labels into *label\_table* 169 ⟩ ≡  
*label\_ptr* ← 0; *label\_table*[0].*rr* ← -1; { sentinel }  
**for** *c* ← *bc* **to** *ec* **do**  
**if** *char\_tag*[*c*] = *lig\_tag* **then**  
begin *sort\_ptr* ← *label\_ptr*; { there's a hole at position *sort\_ptr* + 1 }  
**while** *label\_table*[*sort\_ptr*].*rr* > *char\_remainder*[*c*] **do**  
begin *label\_table*[*sort\_ptr* + 1] ← *label\_table*[*sort\_ptr*]; *decr*(*sort\_ptr*); { move the hole }  
**end**;  
*label\_table*[*sort\_ptr* + 1].*cc* ← *c*; *label\_table*[*sort\_ptr* + 1].*rr* ← *char\_remainder*[*c*]; *incr*(*label\_ptr*);  
**end**

This code is used in section 168.

**170.** ⟨ Find the minimum *lk\_offset* and adjust all remainders 170 ⟩ ≡  
begin *sort\_ptr* ← *label\_ptr*; { the largest unallocated label }  
**if** *label\_table*[*sort\_ptr*].*rr* + *lk\_offset* > 255 **then**  
begin *lk\_offset* ← 0; *extra\_loc\_needed* ← *false*; { location 0 can do double duty }  
**repeat** *char\_remainder*[*label\_table*[*sort\_ptr*].*cc*] ← *lk\_offset*;  
**while** *label\_table*[*sort\_ptr* - 1].*rr* = *label\_table*[*sort\_ptr*].*rr* **do**  
begin *decr*(*sort\_ptr*); *char\_remainder*[*label\_table*[*sort\_ptr*].*cc*] ← *lk\_offset*;  
**end**;  
*incr*(*lk\_offset*); *decr*(*sort\_ptr*);  
**until** *lk\_offset* + *label\_table*[*sort\_ptr*].*rr* < 256;  
{ N.B.: *lk\_offset* = 256 satisfies this when *sort\_ptr* = 0 }  
**end**;  
**if** *lk\_offset* > 0 **then**  
**while** *sort\_ptr* > 0 **do**  
begin *char\_remainder*[*label\_table*[*sort\_ptr*].*cc*] ← *char\_remainder*[*label\_table*[*sort\_ptr*].*cc*] + *lk\_offset*;  
*decr*(*sort\_ptr*);  
**end**;  
**end**

This code is used in section 168.

**171.**  $\langle$  Output the ligature/kern program 171  $\rangle \equiv$

```

if extra_loc_needed then { lk_offset = 1 }
begin out(255); out(bchar); out(0); out(0);
end
else for sort_ptr  $\leftarrow$  1 to lk_offset do { output the redirection specs }
begin t  $\leftarrow$  label_table[label_ptr].rr;
if bchar < 256 then
begin out(255); out(bchar);
end
else begin out(254); out(0);
end;
out_size(t + lk_offset);
repeat decr(label_ptr);
until label_table[label_ptr].rr < t;
end;
if nl > 0 then
for lig_ptr  $\leftarrow$  0 to nl - 1 do
begin out(lig_kern[lig_ptr].b0); out(lig_kern[lig_ptr].b1); out(lig_kern[lig_ptr].b2);
out(lig_kern[lig_ptr].b3);
end;
if nk > 0 then
for krn_ptr  $\leftarrow$  0 to nk - 1 do out_scaled(kern[krn_ptr])

```

This code is used in section 157.

**172.**  $\langle$  Output the extensible character recipes 172  $\rangle \equiv$

```

if ne > 0 then
for c  $\leftarrow$  0 to ne - 1 do
begin out(exten[c].b0); out(exten[c].b1); out(exten[c].b2); out(exten[c].b3);
end;

```

This code is used in section 157.

**173.** For our grand finale, we wind everything up by outputting the parameters.

$\langle$  Output the parameters 173  $\rangle \equiv$

```

for par_ptr  $\leftarrow$  1 to np do
begin if par_ptr = 1 then  $\langle$  Output the slant (param[1]) without scaling 174  $\rangle$ 
else out_scaled(param[par_ptr]);
end

```

This code is used in section 157.

**174.**  $\langle$  Output the slant (param[1]) without scaling 174  $\rangle \equiv$

```

begin if param[1] < 0 then
begin param[1]  $\leftarrow$  param[1] + '1000000000; out((param[1] div '100000000) + 256 - 64);
end
else out(param[1] div '100000000);
out((param[1] div '200000) mod 256); out((param[1] div 256) mod 256); out(param[1] mod 256);
end

```

This code is used in section 173.

**175. The VF output phase.** Output to *vf\_file* is considerably simpler.

```
define id_byte = 202 { current version of VF format }
define vout(#) ≡ write(vf_file, #)
⟨ Globals in the outer block 5 ⟩ +≡
vcount: integer; { number of bytes written to vf_file }
```

**176.** We need a routine to output integers as four bytes. Negative values will never be less than  $-2^{24}$ .

```
procedure vout_int(x: integer);
begin if x ≥ 0 then vout(x div '100000000)
else begin vout(255); x ← x + '100000000;
end;
vout((x div '200000) mod 256); vout((x div '400) mod 256); vout(x mod 256);
end;
```

**177.** ⟨ Do the VF output 177 ⟩ ≡  
*vout(pre); vout(id\_byte); vout(vtitle\_length);*  
**for**  $k \leftarrow 0$  **to** *vtitle\_length* - 1 **do** *vout(vf[vtitle\_start + k]);*  
**for**  $k \leftarrow \text{check\_sum\_loc}$  **to** *design\_size\_loc* + 3 **do** *vout(header\_bytes[k]);*  
*vcount*  $\leftarrow$  *vtitle\_length* + 11;  
**for** *cur\_font*  $\leftarrow 0$  **to** *font\_ptr* - 1 **do** ⟨ Output a local font definition 178 ⟩;  
**for** *c*  $\leftarrow bc$  **to** *ec* **do**  
  **if** *char\_wd[c] > 0* **then** ⟨ Output a packet for character *c* 179 ⟩;  
  **repeat** *vout(post); incr(vcount);*  
  **until** *vcount mod 4 = 0*

This code is used in section 180.

**178.** ⟨ Output a local font definition 178 ⟩ ≡

```
begin vout(fnt_def1); vout(cur_font);
vout(font_checksum[cur_font].b0); vout(font_checksum[cur_font].b1); vout(font_checksum[cur_font].b2);
vout(font_checksum[cur_font].b3); vout_int(font_at[cur_font]); vout_int(font_dsize[cur_font]);
vout(farea_length[cur_font]); vout(fname_length[cur_font]);
for k ← 0 to farea_length[cur_font] - 1 do vout(vf[farea_start[cur_font] + k]);
if fname_start[cur_font] = vf_size then
  begin vout("N"); vout("U"); vout("L"); vout("L");
  end
else for k ← 0 to fname_length[cur_font] - 1 do vout(vf[fname_start[cur_font] + k]);
vcount ← vcount + 12 + farea_length[cur_font] + fname_length[cur_font];
end
```

This code is used in section 177.

179.  $\langle$  Output a packet for character  $c$  179  $\rangle \equiv$

```
begin  $x \leftarrow memory[char\_wd[c]]$ ;
if  $design\_units \neq unity$  then  $x \leftarrow round((x/design\_units) * 1048576.0)$ ;
if ( $packet\_length[c] > 241$ )  $\vee (x < 0) \vee (x \geq '1000000000)$  then
begin  $vout(242)$ ;  $vout\_int(packet\_length[c])$ ;  $vout\_int(c)$ ;  $vout\_int(x)$ ;
 $vcount \leftarrow vcount + 13 + packet\_length[c]$ ;
end;
else begin  $vout(packet\_length[c])$ ;  $vout(c)$ ;  $vout(x \text{ div } '200000)$ ;  $vout((x \text{ div } '400) \text{ mod } 256)$ ;
 $vout(x \text{ mod } 256)$ ;  $vcount \leftarrow vcount + 5 + packet\_length[c]$ ;
end;
if  $packet\_start[c] = vf\_size$  then
begin if  $c \geq 128$  then  $vout(set1)$ ;
 $vout(c)$ ;
end
else for  $k \leftarrow 0$  to  $packet\_length[c] - 1$  do  $vout(vf[packet\_start[c] + k])$ ;
end
```

This code is used in section 177.

**180. The main program.** The routines sketched out so far need to be packaged into separate procedures, on some systems, since some Pascal compilers place a strict limit on the size of a routine. The packaging is done here in an attempt to avoid some system-dependent changes.

```

procedure param_enter;
begin {Enter the parameter names 57};
end;

procedure vpl_enter;
begin {Enter all the VPL names 56};
end;

procedure name_enter; { enter all names and their equivalents }
begin {Enter all the PL names and their equivalents, except the parameter names 55};
vpl_enter; param_enter;
end;

procedure read_lig_kern;
var krn_ptr: 0 .. max_kerns; { an index into kern }
c: byte; { runs through all character codes }
begin {Read ligature/kern list 109};
end;

procedure read_char_info;
var c: byte; { the char }
begin {Read character info list 118};
end;

procedure read_input;
var c: byte; { header or parameter index }
begin {Read all the input 92};
end;

procedure corr_and_check;
var c: 0 .. 256; { runs through all character codes }
hh: 0 .. hash_size; { an index into hash_list }
lig_ptr: 0 .. max_lig_steps; { an index into lig_kern }
g: byte; { a character generated by the current character c }
begin {Correct and check the information 139}
end;

procedure vf_output;
var c: byte; { runs through all character codes }
cur_font: 0 .. 256; { runs through all local fonts }
k: integer; { loop index }
begin {Do the VF output 177};
end;

```

**181.** Here is where VPtoVF begins and ends.

```

begin initialize;
name_enter;
read_input; print_ln(`.`);
corr_and_check;
{Do the TFM output 157};
vf_output;
end.

```

**182. System-dependent changes.** This section should be replaced, if necessary, by changes to the program that are necessary to make VPtoVF work at a particular installation. It is usually best to design your change file so that all changes to previous sections preserve the section numbering; then everybody's version will be consistent with the printed program. More extensive changes, which introduce new sections, can be inserted here; then only the index itself will get a new section number.

**183. Index.** Pointers to error messages appear here together with the section numbers where each identifier is used.

a: 39  
 A cycle of NEXTLARGER...: 142  
 abs: 165  
 acc: 60, 61, 62, 63, 64, 65, 72, 74, 76  
 An "R" or "D" ... needed here: 72  
 ASCII\_code: 23, 24, 36, 44, 46, 60  
 At most 256 VARCHAR specs...: 120  
 backup: 38, 62, 63, 64, 112  
 bad\_indent: 35  
 banner: 1, 2  
 bc: 158, 159, 160, 163, 164, 169, 177  
 bchar: 77, 80, 95, 149, 154, 155, 167, 168, 171  
 bchar\_label: 82, 84, 112, 139, 145, 154, 168  
 boolean: 29, 41, 50, 72, 77, 113, 128, 138,  
     150, 158, 167  
 BOT piece of character...: 141  
 both\_z: 146, 150, 151, 153  
 boundary\_char\_code: 52, 55, 95  
 buf\_size: 3, 29, 33, 34  
 buffer: 29, 33, 34, 35, 37, 38, 40, 41, 61  
 byte: 23, 39, 52, 53, 60, 66, 77, 82, 83, 89, 90, 91,  
     97, 111, 124, 128, 136, 158, 165, 167, 180  
 b0: 66, 67, 68, 104, 114, 115, 116, 117, 121, 141,  
     145, 149, 155, 171, 172, 178  
 b1: 66, 67, 68, 104, 116, 117, 121, 141, 145, 149,  
     151, 155, 171, 172, 178  
 b2: 66, 67, 68, 104, 116, 117, 121, 141, 145, 149,  
     151, 155, 168, 171, 172, 178  
 b3: 66, 67, 68, 104, 116, 117, 121, 141, 145, 149,  
     151, 155, 168, 171, 172, 178  
 c: 69, 83, 91, 124, 150, 180  
 "C" value must be...: 61  
 cc: 124, 127, 150, 151, 167, 169, 170  
 char: 24, 29  
 char\_dp: 82, 84, 119, 164  
 char\_dp\_code: 52, 55, 119  
 char\_ht: 82, 84, 119, 164  
 char\_ht\_code: 52, 55, 119  
 char\_ic: 82, 84, 119, 164  
 char\_ic\_code: 52, 55, 119  
 char\_info: 164  
 char\_info\_code: 52  
 char\_info\_word: 82  
 char\_remainder: 82, 84, 112, 119, 120, 140, 141,  
     142, 149, 154, 164, 167, 169, 170  
 char\_tag: 82, 84, 111, 112, 119, 120, 140, 142,  
     154, 164, 169  
 char\_wd: 82, 84, 85, 118, 119, 139, 140, 155,  
     159, 163, 164, 177, 179  
 char\_wd\_code: 52, 55, 103, 119  
 Character cannot be typeset...: 127  
 character\_code: 52, 55, 94, 95  
 chars\_on\_line: 31, 32, 33, 137  
 check\_existence: 140, 149  
 check\_existence\_and\_safety: 140, 141  
 check\_sum\_code: 52, 55, 95  
 check\_sum\_loc: 80, 95, 163, 177  
 check\_sum\_specified: 77, 80, 95, 162  
 check\_tag: 111, 112, 119, 120  
 chr: 26, 34  
 class: 147, 150, 153, 154  
 clear\_lig\_kern\_entry: 145  
 coding\_scheme\_code: 52, 55, 95  
 coding\_scheme\_loc: 80, 95  
 comment\_code: 52, 55, 94, 103, 106, 110, 119,  
     121, 125  
 copy\_to\_end\_of\_item: 41, 95, 107, 108, 134  
 corr\_and\_check: 180, 181  
 cur\_bytes: 66, 67, 69, 70, 104, 106, 126  
 cur\_char: 36, 37, 38, 39, 40, 42, 43, 58, 60, 61, 62,  
     63, 64, 65, 69, 70, 72, 73, 74, 76, 92, 94, 97,  
     100, 102, 104, 109, 112, 118, 120, 124, 134  
 cur\_code: 52, 58, 94, 95, 103, 106, 110, 116, 119,  
     121, 125, 130, 131, 134  
 cur\_font: 77, 104, 105, 106, 107, 108, 124, 126,  
     127, 177, 178, 180  
 cur\_hash: 47, 50, 51, 53  
 cur\_name: 46, 50, 51, 53, 54, 58  
 c0: 67, 70, 96, 163  
 c1: 67, 70, 96, 163  
 c2: 67, 70, 96, 163  
 c3: 67, 70, 96, 163  
 d: 79, 85, 87, 88, 90  
 Decimal ("D"), octal ("0"), or hex...: 69  
 decr: 4, 38, 40, 41, 50, 58, 76, 90, 97, 102, 117,  
     124, 128, 133, 150, 152, 159, 169, 170, 171  
 delta: 143, 144  
 depth: 52, 84, 119, 144, 159, 160  
 design\_size: 77, 80, 98, 162  
 design\_size\_code: 52, 55, 95  
 design\_size\_loc: 80, 162, 177  
 design\_units: 77, 80, 99, 106, 128, 163, 165, 179  
 design\_units\_code: 52, 55, 95  
 dict\_ptr: 44, 45, 53  
 dictionary: 44, 50, 53  
 do\_nothing: 4, 111, 140, 151, 153  
 Don't push so much...: 132  
 double\_check\_ext: 155  
 double\_check\_lig: 155  
 double\_check\_rep: 155

*double\_check\_tail*: 155  
*down1*: 122, 131  
*ec*: 158, 159, 160, 163, 164, 169, 177  
**Empty stack...**: 133  
*enter\_name*: 53, 54  
*eof*: 34  
*coln*: 34  
*equiv*: 52, 53, 55, 58  
*err\_print*: 33, 35, 38, 39, 40, 41, 42, 43, 58, 85, 92, 93, 95, 97, 98, 99, 100, 104, 107, 108, 111, 114, 115, 116, 117, 120, 124, 126, 127, 132, 133, 135  
*eval*: 152, 153  
*excess*: 88, 89, 90  
*existence\_tail*: 140  
*ext\_tag*: 82, 111, 120, 140  
*exten*: 77, 120, 121, 141, 155, 172  
**Extra right parenthesis**: 92  
*extra\_loc\_needed*: 167, 168, 170, 171  
*f*: 152, 153  
*face\_code*: 52, 55, 95  
*face\_loc*: 80, 95  
*false*: 30, 34, 41, 50, 72, 80, 100, 109, 112, 114, 115, 128, 139, 150, 159, 168, 170  
*family\_code*: 52, 55, 95  
*family\_loc*: 80, 95  
*farea\_length*: 77, 105, 108, 178  
*farea\_start*: 77, 105, 108, 178  
**File ended unexpectedly...**: 40  
*full\_buffer*: 34, 35, 37, 38, 40, 41  
*finish\_inner\_property\_list*: 102, 104, 109, 118, 120, 124  
*finish\_the\_property*: 43, 94, 102, 103, 106, 110, 119, 121, 125  
*first\_ord*: 24, 26  
*fix\_word*: 71, 72, 77, 81, 82, 85, 86, 87, 88, 90, 91, 105, 123, 124, 128, 143, 158, 165  
*flush\_error*: 42, 94, 103, 106, 110, 119, 121, 125  
*fname\_length*: 77, 105, 107, 178  
*fname\_start*: 77, 105, 107, 178  
*fnr\_def1*: 77, 122, 178  
*fnr\_num\_0*: 122, 126  
*fnr1*: 77, 122, 126  
*font\_area\_code*: 52, 56, 106  
*font\_at*: 77, 105, 106, 178  
*font\_at\_code*: 52, 56, 106  
*font\_checksum*: 77, 105, 106, 178  
*font\_checksum\_code*: 52, 56, 106  
*font\_dimen\_code*: 52, 55, 95  
*font\_dsize*: 77, 105, 106, 178  
*font\_dsize\_code*: 52, 56, 106  
*font\_name\_code*: 52, 56, 106  
*font\_number*: 77, 104, 126  
*font\_ptr*: 77, 80, 104, 105, 126, 127, 177  
**FONTAREA clipped...**: 108  
**FONTNAME clipped...**: 107  
*forward*: 152, 153  
*four\_bytes*: 66, 67, 69, 77  
*fraction\_digits*: 75, 76  
*frozen\_du*: 77, 80, 99, 106, 128  
**Fuchs, David Raymond**: 1  
*g*: 180  
*get\_byte*: 60, 95, 101, 103, 112, 115, 116, 117, 118, 119, 121, 127  
*get\_fix*: 72, 98, 99, 103, 106, 117, 119, 129, 130, 131  
*get\_four\_bytes*: 69, 96, 104, 106, 126  
*get\_hex*: 39, 134  
*get\_keyword\_char*: 37, 58  
*get\_name*: 58, 94, 103, 106, 110, 119, 121, 125  
*get\_next*: 38, 39, 42, 43, 58, 60, 61, 62, 63, 64, 65, 69, 70, 72, 73, 74, 76, 92, 97, 100, 102, 104, 109, 112, 118, 120, 124  
*good\_indent*: 27, 28, 35  
*h*: 48, 85, 87, 88, 90, 124, 147, 152  
*hash*: 147, 148, 150, 152, 153, 154  
*hash\_input*: 149, 150  
*hash\_list*: 147, 150, 154, 180  
*hash\_prime*: 47, 48, 49, 50, 51  
*hash\_ptr*: 147, 148, 150, 154  
*hash\_size*: 3, 147, 148, 150, 152, 154, 180  
*header*: 10  
**HEADER indices...**: 101  
*header\_bytes*: 77, 79, 80, 95, 96, 97, 101, 161, 162, 163, 177  
*header\_code*: 52, 55, 95  
*header\_index*: 77, 78, 79, 96, 97  
*header\_ptr*: 77, 80, 101, 159, 162  
*height*: 52, 81, 84, 119, 144, 159, 160  
*hh*: 147, 154, 180  
*hstack*: 123, 124, 132, 133  
**I can handle only 256...**: 104  
**I had to round...**: 144  
**I'm out of memory...**: 41  
*id\_byte*: 175, 177  
**Illegal character...**: 38, 41  
**Illegal digit**: 70  
**Illegal face code...**: 65  
**Illegal hexadecimal digit**: 39  
*incr*: 4, 34, 35, 37, 38, 40, 41, 53, 58, 65, 76, 85, 87, 90, 92, 97, 101, 102, 103, 104, 105, 116, 117, 120, 126, 128, 132, 137, 145, 150, 159, 169, 170, 177  
*indent*: 27, 28, 35  
*index*: 89, 90, 164  
*indx*: 78, 147, 150, 152, 153

**Infinite ligature loop...:** 154  
**initialize:** 2, 181  
**input\_has\_ended:** 29, 30, 34, 40, 92  
**int\_part:** 72  
**integer:** 25, 27, 39, 40, 41, 60, 69, 71, 72, 75, 77, 87, 88, 91, 128, 150, 152, 175, 176, 180  
**invalid\_code:** 26, 38, 41  
**italic:** 52, 81, 84, 119, 144, 159, 160, 161, 166  
**j:** 50, 72, 161  
**Junk after property value...:** 43  
**junk\_error:** 92, 93, 102, 104, 109, 118, 120, 124  
**k:** 25, 33, 50, 53, 88, 91, 97, 124, 128, 180  
**kern:** 77, 113, 117, 171, 180  
**kern\_flag:** 113, 117, 149, 151, 155  
**key:** 150, 152  
**KRN character examined...:** 149  
**krn\_code:** 52, 55, 110  
**krn\_ptr:** 113, 117, 171, 180  
**l:** 40, 41, 87, 90  
**label\_code:** 52, 55, 110  
**label\_ptr:** 167, 169, 170, 171  
**label\_table:** 167, 169, 170, 171  
**last\_ord:** 24, 26  
**left\_ln:** 29, 30, 33, 34  
**left\_z:** 146, 151, 153  
**level:** 27, 28, 35, 40, 41, 58, 102, 104, 109, 118, 120, 124  
**lf:** 158, 159, 160  
**lh:** 158, 159, 160  
**LIG character examined...:** 149  
**LIG character generated...:** 149  
**lig\_code:** 52, 55, 110, 116  
**lig\_exam:** 149  
**lig\_gen:** 149  
**lig\_kern:** 77, 114, 115, 116, 117, 145, 147, 149, 151, 155, 168, 171, 180  
**lig\_ptr:** 147, 149, 155, 171, 180  
**lig\_table\_code:** 52, 55, 95  
**lig\_tag:** 82, 111, 112, 140, 154, 169  
**lig\_z:** 147, 150, 153  
**limit:** 29, 30, 33, 34, 35, 37, 38, 40, 41  
**line:** 27, 28, 33, 34  
**link:** 81, 82, 84, 85, 87, 90, 166  
**list\_tag:** 82, 111, 119, 140, 142  
**lk\_offset:** 159, 160, 167, 168, 170, 171  
**lk\_step\_ended:** 109, 112, 113, 114, 115, 116, 117  
**load10:** 54, 55, 56, 57  
**load11:** 54, 55  
**load12:** 54, 55, 56  
**load13:** 54, 57  
**load14:** 54  
**load15:** 54

**load16:** 54, 55  
**load17:** 54  
**load18:** 54  
**load19:** 54  
**load20:** 54, 57  
**load3:** 54, 55, 56  
**load4:** 54, 55, 56, 57  
**load5:** 54, 55, 57  
**load6:** 54, 55, 56, 57  
**load7:** 54, 55, 56, 57  
**load8:** 54, 55, 56  
**load9:** 54, 55, 56  
**loc:** 29, 30, 33, 34, 35, 37, 38, 40, 41, 58, 61, 92, 102  
**longest\_name:** 46, 50, 53, 58  
**lookup:** 50, 53, 58  
**m:** 87, 90, 165  
**map\_code:** 52, 56, 119  
**map\_font\_code:** 52, 56, 95  
**max\_header\_bytes:** 3, 10, 78, 101, 161  
**max\_kerns:** 3, 77, 113, 117, 180  
**max\_letters:** 44, 50  
**max\_lig\_steps:** 3, 77, 115, 116, 117, 147, 180  
**max\_name\_index:** 44, 46, 47, 52  
**max\_param\_words:** 3, 12, 77, 103, 161  
**max\_stack:** 3, 123, 132  
**Maximum SKIP amount...:** 115  
**mem\_ptr:** 82, 84, 85  
**mem\_size:** 81, 85  
**memory:** 81, 82, 84, 85, 87, 88, 89, 90, 158, 159, 160, 161, 163, 166, 179  
**Memory overflow...:** 85  
**MID piece of character...:** 141  
**min\_cover:** 87, 88  
**min\_nl:** 77, 80, 112, 115, 145  
**Missing POP supplied:** 124  
**move\_down\_code:** 52, 56, 125, 131  
**move\_right\_code:** 52, 56, 125, 130  
**n:** 165  
**name\_enter:** 180, 181  
**name\_length:** 46, 50, 51, 53, 54, 58  
**name\_ptr:** 46, 50, 58  
**ne:** 77, 80, 120, 121, 155, 159, 160, 172  
**negative:** 72, 73, 128  
**next\_d:** 86, 87, 88, 98, 99  
**next\_larger\_code:** 52, 55, 119  
**nhash:** 47, 49, 50, 53  
**nk:** 77, 80, 117, 159, 160, 171  
**nl:** 77, 80, 112, 114, 115, 116, 117, 139, 145, 149, 154, 155, 159, 160, 168, 171  
**no\_tag:** 82, 84, 111, 140, 142, 154  
**nonblank\_found:** 41  
**not\_found:** 50, 158, 159

np: 77, 80, 103, 159, 160, 173  
 numbers\_differ: 104, 126  
 opcode: 128  
 out: 156, 160, 162, 164, 165, 166, 171, 172, 174  
 out\_scaled: 165, 166, 171, 173  
 out\_size: 160, 171  
 output: 2  
 p: 85, 87, 90, 150, 161  
 packet\_length: 77, 80, 124, 179  
 packet\_start: 77, 80, 124, 179  
 par\_ptr: 161, 173  
 param: 77, 103, 173, 174  
 param\_enter: 180  
 PARAMETER index must not...: 103  
 parameter\_code: 52, 55, 57, 103  
 pending: 146, 147, 153  
 pointer: 81, 82, 85, 87, 88, 89, 90, 161  
 pop: 122, 124, 133  
 pop\_code: 52, 56, 125  
 post: 122, 177  
 pre: 122, 177  
 print: 2, 33, 136, 137, 140, 142, 154, 155, 165  
 print\_ln: 2, 33, 85, 137, 139, 140, 142, 144, 154, 155, 165, 181  
 print\_octal: 136, 137, 140, 142, 154, 155  
 push: 122, 132  
 push\_code: 52, 56, 125  
 q: 90, 161  
 r: 69  
 read: 34  
 read\_BCPL: 95, 97  
 read\_char\_info: 95, 180  
 read\_four\_bytes: 95, 96, 101  
 read\_input: 180, 181  
 read\_lig\_kern: 95, 180  
 read\_ln: 34  
 read\_packet: 119, 124  
 Real constants must be...: 72, 74  
 REP piece of character...: 141  
 reset: 6  
 rewrite: 22  
 right\_ln: 29, 30, 33, 34, 37  
 right\_z: 146, 151, 153  
 right1: 122, 130  
 round: 106, 128, 163, 165, 179  
 round\_message: 144  
 rr: 167, 169, 170, 171  
 select\_font\_code: 52, 56, 125  
 set\_char\_code: 52, 56, 125  
 set\_char\_0: 122  
 set\_indices: 90, 144  
 set\_rule: 122, 129  
 set\_rule\_code: 52, 56, 125  
 set1: 122, 127, 179  
 seven\_bit\_safe\_flag: 77, 80, 100, 139  
 seven\_bit\_safe\_flag\_code: 52, 55, 95  
 seven\_flag\_loc: 80, 162  
 seven\_unsafe: 138, 139, 140, 149, 162  
 shorten: 88, 144  
 show\_error\_context: 33  
 simple: 146, 147, 150, 151, 153, 154  
 SKIP must follow LIG or KRN: 115  
 skip\_code: 52, 55, 110  
 skip\_error: 42, 60, 61, 62, 63, 64, 65, 69, 70, 72, 74, 101  
 skip\_to\_end\_of\_item: 40, 42, 43, 94, 102, 103, 104, 106, 109, 110, 118, 119, 120, 121, 124, 125  
 skip\_to\_paren: 42, 93, 100, 112  
 Sorry, I don't know...: 58  
 Sorry, I haven't room...: 154  
 Sorry, it's too late...: 99  
 Sorry, LIGTABLE too long...: 115, 116, 117  
 Sorry, the maximum...: 70  
 Sorry, too many different kerns...: 117  
 sort\_in: 85, 118, 119, 140, 155  
 sort\_ptr: 167, 169, 170, 171  
 Special command being clipped...: 135  
 special\_code: 52, 56, 125, 134  
 special\_hex\_code: 52, 56, 125  
 special\_start: 124, 134, 135  
 stack\_ptr: 123, 124, 130, 131, 132, 133  
 start: 44, 45, 46, 47, 50, 52, 53  
 start\_ptr: 44, 45, 53  
 STOP must follow LIG or KRN: 114  
 stop\_code: 52, 55, 110  
 stop\_flag: 113, 114, 145, 149  
 String is too long...: 97  
 system dependencies: 2, 22, 24, 34, 182  
 t: 60, 128, 150, 167  
 tail: 54  
 temp\_width: 158, 163  
 text: 5  
 tfm\_file: 2, 21, 22, 156  
 The character NEXTLARGER...: 140  
 The design size must...: 98  
 The flag value should be...: 100  
 The font is not...safe: 139  
 The number of units...: 99  
 The relative dimension...: 165  
 There's junk here...: 93  
 This character already...: 111  
 This HEADER index is too big...: 101  
 This PARAMETER index is too big...: 103

This property name doesn't belong...: 94, 103, 106, 110, 119, 121, 125  
This value shouldn't...: 62, 63, 64  
TOP piece of character...: 141  
true: 30, 34, 41, 50, 95, 100, 106, 116, 117, 128, 140, 149, 150, 159, 168  
tt: 147, 154  
t1: 54  
t10: 54  
t11: 54  
t12: 54  
t13: 54  
t14: 54  
t15: 54  
t16: 54  
t17: 54  
t18: 54  
t19: 54  
t2: 54  
t20: 54  
t3: 54  
t4: 54  
t5: 54  
t6: 54  
t7: 54  
t8: 54  
t9: 54  
Undefined MAPFONT...: 126  
unity: 71, 72, 80, 98, 106, 128, 163, 165, 179  
UNSPECIFIED: 80  
Unused KRN step...: 155  
Unused LIG step...: 155  
Unused VARCHAR...: 155  
v: 124  
var\_char\_code: 52, 55, 119, 121  
vcount: 175, 177, 178, 179  
vf: 3, 41, 77, 134, 135, 177, 178, 179  
vf\_file: 2, 21, 22, 175  
vf\_fix: 128, 129, 130, 131  
vf\_output: 180, 181  
vf\_ptr: 41, 77, 80, 95, 107, 108, 124, 134, 135  
vf\_size: 3, 41, 77, 80, 105, 124, 135, 178, 179  
vf\_store: 41, 124, 126, 127, 128, 129, 130, 131, 132, 133, 134  
virtual\_title\_code: 52, 56, 95  
vout: 175, 176, 177, 178, 179  
vout\_int: 176, 178, 179  
vpl\_enter: 180  
vpl\_file: 2, 5, 6, 34  
VPtoVF: 2  
vstack: 123, 124, 132, 133  
VTITLE clipped...: 95

vtitle\_length: 77, 80, 95, 177  
vtitle\_start: 77, 80, 95, 177  
Warning: Inconsistent indentation...: 35  
Warning: Indented line...: 35  
width: 52, 81, 84, 85, 118, 119, 140, 144, 155, 158, 159, 160, 161, 166  
write: 2, 156, 175  
write\_ln: 2  
wstack: 123, 130  
w0: 122, 130  
w1: 122, 130  
x: 91, 124, 128, 152, 176  
x\_lig\_cycle: 147, 153, 154  
xord: 24, 26, 34, 37, 38, 41, 61  
xstack: 123, 130  
xxx1: 122, 124, 134  
xxx4: 122, 135  
x0: 122, 130  
x1: 122, 130  
y: 150, 152  
y\_lig\_cycle: 147, 148, 153, 154  
You need "C" or "D" ...here: 60  
ystack: 123, 131  
y0: 122, 131  
y1: 122, 131  
zero\_bytes: 67, 68, 69, 70, 105, 120  
zstack: 123, 131  
zz: 150, 151  
z0: 122, 131  
z1: 122, 131

⟨ Assemble a font selection 126 ⟩ Used in section 125.  
⟨ Assemble a horizontal movement 130 ⟩ Used in section 125.  
⟨ Assemble a rulesetting instruction 129 ⟩ Used in section 125.  
⟨ Assemble a special command 134 ⟩ Used in section 125.  
⟨ Assemble a stack pop 133 ⟩ Used in section 125.  
⟨ Assemble a stack push 132 ⟩ Used in section 125.  
⟨ Assemble a typesetting instruction 127 ⟩ Used in section 125.  
⟨ Assemble a vertical movement 131 ⟩ Used in section 125.  
⟨ Check for infinite ligature loops 154 ⟩ Used in section 139.  
⟨ Check ligature program of *c* 149 ⟩ Used in sections 139 and 140.  
⟨ Check the pieces of *exten*[*c*] 141 ⟩ Used in section 140.  
⟨ Compute the check sum 163 ⟩ Used in section 162.  
⟨ Compute the command parameters *y*, *cc*, and *zz* 151 ⟩ Used in section 150.  
⟨ Compute the hash code, *cur\_hash*, for *cur\_name* 51 ⟩ Used in section 50.  
⟨ Compute the ligature/kern program offset 168 ⟩ Used in section 159.  
⟨ Compute the twelve subfile sizes 159 ⟩ Used in section 157.  
⟨ Constants in the outer block 3 ⟩ Used in section 2.  
⟨ Convert *xxx1* command to *xxx4* 135 ⟩ Used in section 134.  
⟨ Correct and check the information 139 ⟩ Used in section 180.  
⟨ Declare the *vf\_fix* procedure 128 ⟩ Used in section 124.  
⟨ Do the TFM output 157 ⟩ Used in section 181.  
⟨ Do the VF output 177 ⟩ Used in section 180.  
⟨ Doublecheck the lig/kern commands and the extensible recipes 155 ⟩ Used in section 139.  
⟨ Enter all the PL names and their equivalents, except the parameter names 55 ⟩ Used in section 180.  
⟨ Enter all the VPL names 56 ⟩ Used in section 180.  
⟨ Enter the parameter names 57 ⟩ Used in section 180.  
⟨ Find the minimum *lk\_offset* and adjust all remainders 170 ⟩ Used in section 168.  
⟨ For all characters *g* generated by *c*, make sure that *char\_wd*[*g*] is nonzero, and set *seven\_unsafe* if  $c < 128 \leq g$  140 ⟩ Used in section 139.  
⟨ Globals in the outer block 5, 21, 24, 27, 29, 31, 36, 44, 46, 47, 52, 67, 75, 77, 82, 86, 89, 91, 113, 123, 138, 143, 147, 158, 161, 167, 175 ⟩ Used in section 2.  
⟨ Initialize a new local font 105 ⟩ Used in section 104.  
⟨ Insert all labels into *label\_table* 169 ⟩ Used in section 168.  
⟨ Local variables for initialization 25, 48, 79, 83 ⟩ Used in section 2.  
⟨ Make sure that *c* is not the largest element of a charlist cycle 142 ⟩ Used in section 139.  
⟨ Make sure the ligature/kerning program ends appropriately 145 ⟩ Used in section 139.  
⟨ Multiply by 10, add *cur\_char* – "0", and *get\_next* 74 ⟩ Used in section 72.  
⟨ Multiply by *r*, add *cur\_char* – "0", and *get\_next* 70 ⟩ Used in section 69.  
⟨ Output a local font definition 178 ⟩ Used in section 177.  
⟨ Output a packet for character *c* 179 ⟩ Used in section 177.  
⟨ Output the character info 164 ⟩ Used in section 157.  
⟨ Output the dimensions themselves 166 ⟩ Used in section 157.  
⟨ Output the extensible character recipes 172 ⟩ Used in section 157.  
⟨ Output the header block 162 ⟩ Used in section 157.  
⟨ Output the ligature/kern program 171 ⟩ Used in section 157.  
⟨ Output the parameters 173 ⟩ Used in section 157.  
⟨ Output the slant (*param*[1]) without scaling 174 ⟩ Used in section 173.  
⟨ Output the twelve subfile sizes 160 ⟩ Used in section 157.  
⟨ Print *c* in octal notation 137 ⟩ Used in section 118.  
⟨ Put the width, height, depth, and italic lists into final form 144 ⟩ Used in section 139.  
⟨ Read a character property 119 ⟩ Used in section 118.  
⟨ Read a font property value 94 ⟩ Used in section 92.

`<Read a kerning step 117>` Used in section 110.  
`<Read a label step 112>` Used in section 110.  
`<Read a ligature step 116>` Used in section 110.  
`<Read a ligature/kern command 110>` Used in section 109.  
`<Read a local font area 108>` Used in section 106.  
`<Read a local font list 104>` Used in section 95.  
`<Read a local font name 107>` Used in section 106.  
`<Read a local font property 106>` Used in section 104.  
`<Read a parameter value 103>` Used in section 102.  
`<Read a skip step 115>` Used in section 110.  
`<Read a stop step 114>` Used in section 110.  
`<Read all the input 92>` Used in section 180.  
`<Read an extensible piece 121>` Used in section 120.  
`<Read an extensible recipe for c 120>` Used in section 119.  
`<Read an indexed header word 101>` Used in section 95.  
`<Read and assemble a list of DVI commands 125>` Used in section 124.  
`<Read character info list 118>` Used in section 180.  
`<Read font parameter list 102>` Used in section 95.  
`<Read ligature/kern list 109>` Used in section 180.  
`<Read the design size 98>` Used in section 95.  
`<Read the design units 99>` Used in section 95.  
`<Read the font property value specified by cur_code 95>` Used in section 94.  
`<Read the seven-bit-safe flag 100>` Used in section 95.  
`<Scan a face code 65>` Used in section 60.  
`<Scan a small decimal number 62>` Used in section 60.  
`<Scan a small hexadecimal number 64>` Used in section 60.  
`<Scan a small octal number 63>` Used in section 60.  
`<Scan an ASCII character code 61>` Used in section 60.  
`<Scan the blanks and/or signs after the type code 73>` Used in section 72.  
`<Scan the fraction part and put it in acc 76>` Used in section 72.  
`<Set initial values 6, 22, 26, 28, 30, 32, 45, 49, 68, 80, 84, 148>` Used in section 2.  
`<Set loc to the number of leading blanks in the buffer, and check the indentation 35>` Used in section 34.  
`<Types in the outer block 23, 66, 71, 78, 81>` Used in section 2.