

PDFMSYM

version 1.0.2

S. Lurp

`slurper04@gmail.com`

December 15, 2022

The PDFMSYM package (the PDF Math Symbols package) was created as an extension to the math macros provided by \TeX and \LaTeX . It provides more obscure symbols not found in popular preexisting and reimplements macros which were viewed as flawed.

A big part of the package was implemented through `\pdf literals` and other PDF primitives. So the PDFMSYM package is intended for use with PDF \TeX , \L u a\TeX , \Xe\TeX , and their \LaTeX counterparts. Unfortunately, some macros are not supported by \Xe\TeX .

1. An Introduction to PDFMSYM

The main motivator for creating PDFMSYM was TeX's poor implementation of the `\overrightarrow` macro which many times yields unsavory results. For example `\overrightarrow{\hbox{ABC}}` yields:

$$\overrightarrow{ABC}$$

As you can see, the arrow overlaps with the ABC which is undesirable. This can be fixed by altering the `\rightarrow` macro, but I decided to make a more versatile alternative. The PDFMSYM alternative, `\vecc`, on the other hand yields:

$$\overrightarrow{ABC}$$

Along with a few other features, PDFMSYM provides a simple interface for creating your own style of arrows.

PDFMSYM requires the current font size in order to properly scale its symbols, which must be provided after `\input pdfmsym.tex`. This can be done with the `\pdfmsymsetscalefactor` macro. If your font is 12pt then you can load PDFMSYM like so:

```
\input pdfmsym
\pdfmsymsetscalefactor{12}
```

It is *imperative* that you set the scale factor after loading `pdfmsym` as otherwise almost none of the macros will work.

2. The Predefined Symbols

This section will simply be an exhaustive list of all the predefined symbols PDFMSYM provides.

2.1. Math Symbols

<code>\dwedge:</code>	A	<code>\dcup:</code>	\cup
<code>\displaystyle</code>	$A \wedge B$	<code>\displaystyle</code>	$A \cup B$
<code>\textstyle</code>	$A \wedge B$	<code>\textstyle</code>	$A \cup B$
<code>\scriptstyle</code>	$A \wedge B$	<code>\scriptstyle</code>	$A \cup B$
<code>\scriptscriptstyle</code>	$A \wedge B$	<code>\scriptscriptstyle</code>	$A \cup B$
<code>\bigdwedge:</code>	\bigwedge	<code>\bigdcup:</code>	\bigcup
<code>\displaystyle</code>	$A \wedge \bigwedge_{n=1}^N B_n$	<code>\displaystyle</code>	$A \cup \bigcup_{n=1}^N B_n$
<code>\textstyle</code>	$A \wedge \bigwedge_{n=1}^N B_n$	<code>\textstyle</code>	$A \cup \bigcup_{n=1}^N B_n$
<code>\scriptstyle</code>	$A \wedge \bigwedge_{n=1}^N B_n$	<code>\scriptstyle</code>	$A \cup \bigcup_{n=1}^N B_n$
<code>\scriptscriptstyle</code>	$A \wedge \bigwedge_{n=1}^N B_n$	<code>\scriptscriptstyle</code>	$A \cup \bigcup_{n=1}^N B_n$

$\backslashaint:$	f		
\backslashdisplaystyle	$f(x) + \int_a^b g(x) dx$	$\backslashdivs:$	
\backslashtextstyle	$f(x) + \int_a^b g(x) dx$	\backslashtextstyle	$n \vdash m$
\backslashscriptstyle	$f(x) + \int_a^b g(x) dx$	\backslashscriptstyle	$n \vdash m$
$\backslashscriptscriptstyle$	$f(x) + \int_a^b g(x) dx$	$\backslashscriptscriptstyle$	$n \vdash m$
$\backslashndivs:$	\nearrow		
\backslashdisplaystyle	$n \nearrow m$		
\backslashtextstyle	$n \nearrow m$		
\backslashscriptstyle	$n \nearrow m$		
$\backslashscriptscriptstyle$	$n \nearrow m$		

Additionally, \backslashlightning is provided as a textmode command and renders $\not\int$.

2.2. Vector Symbols

Each vector comes as a pair: the normal form and the short form. The normal form is meant to cover longer material while the short form covers shorter material.

$\backslashvecc:$	\backslashvecc	\backslashshortvecc
\backslashdisplaystyle	\overrightarrow{ABC}	\vec{d}
\backslashtextstyle	\overrightarrow{ABC}	\vec{a}
\backslashscriptstyle	\overrightarrow{ABC}	\vec{a}
$\backslashscriptscriptstyle$	\overrightarrow{ABC}	\vec{a}
$\backslashlvecc:$	\backslashlvecc	\backslashshortlvecc
\backslashdisplaystyle	\overleftarrow{ABC}	\hat{a}
\backslashtextstyle	\overleftarrow{ABC}	\hat{a}
\backslashscriptstyle	\overleftarrow{ABC}	\hat{a}
$\backslashscriptscriptstyle$	\overleftarrow{ABC}	\hat{a}
$\backslashoverrightharp:$	\backslashoverrightharp	$\backslashshortoverrightharp$
\backslashdisplaystyle	\overrightarrow{ABC}	\vec{a}
\backslashtextstyle	\overrightarrow{ABC}	\vec{a}
\backslashscriptstyle	\overrightarrow{ABC}	\vec{a}
$\backslashscriptscriptstyle$	\overrightarrow{ABC}	\vec{a}

<code>\overleftharp:</code>	<code>\overleftharp</code>	<code>\shortoverleftharp</code>
<code>\displaystyle</code>	\overleftharpoon{ABC}	\overleftarrow{a}
<code>\textstyle</code>	\overleftharpoon{ABC}	\overleftarrow{a}
<code>\scriptstyle</code>	\overleftharpoon{ABC}	\overleftarrow{a}
<code>\scriptscriptstyle</code>	\overleftharpoon{ABC}	\overleftarrow{a}
<code>\oveleftrrightvecc:</code>	<code>\oveleftrrightvecc</code>	<code>\shortoveleftrrightvecc</code>
<code>\displaystyle</code>	$\overleftrightarpoon{ABC}$	\overleftrightarrow{a}
<code>\textstyle</code>	$\overleftrightarpoon{ABC}$	\overleftrightarrow{a}
<code>\scriptstyle</code>	$\overleftrightarpoon{ABC}$	\overleftrightarrow{a}
<code>\scriptscriptstyle</code>	$\overleftrightarpoon{ABC}$	\overleftrightarrow{a}
<code>\oveleftrrightharp:</code>	<code>\oveleftrrightharp</code>	<code>\shortoveleftrrightharp</code>
<code>\displaystyle</code>	$\overleftrightharpoon{ABC}$	\overleftarrow{a}
<code>\textstyle</code>	$\overleftrightharpoon{ABC}$	\overleftarrow{a}
<code>\scriptstyle</code>	$\overleftrightharpoon{ABC}$	\overleftarrow{a}
<code>\scriptscriptstyle</code>	$\overleftrightharpoon{ABC}$	\overleftarrow{a}
<code>\overrightleftharp:</code>	<code>\overrightleftharp</code>	<code>\shortoverrightleftharp</code>
<code>\displaystyle</code>	$\overrightleftharpoon{ABC}$	\overrightarrow{a}
<code>\textstyle</code>	$\overrightleftharpoon{ABC}$	\overrightarrow{a}
<code>\scriptstyle</code>	$\overrightleftharpoon{ABC}$	\overrightarrow{a}
<code>\scriptscriptstyle</code>	$\overrightleftharpoon{ABC}$	\overrightarrow{a}
<code>\straightvecc:</code>	<code>\straightvecc</code>	<code>\shortstraightvecc</code>
<code>\displaystyle</code>	\overrightarrow{ABC}	\vec{a}
<code>\textstyle</code>	\overrightarrow{ABC}	\vec{a}
<code>\scriptstyle</code>	\overrightarrow{ABC}	\vec{a}
<code>\scriptscriptstyle</code>	\overrightarrow{ABC}	\vec{a}
<code>\straightlvecc:</code>	<code>\straightlvecc</code>	<code>\shortstraightlvecc</code>
<code>\displaystyle</code>	\overleftarrow{ABC}	\overleftarrow{a}
<code>\textstyle</code>	\overleftarrow{ABC}	\overleftarrow{a}
<code>\scriptstyle</code>	\overleftarrow{ABC}	\overleftarrow{a}
<code>\scriptscriptstyle</code>	\overleftarrow{ABC}	\overleftarrow{a}

The `\constvec` macro has the following usage:

```
\constvec{vector macro}{material}
```

And it centers the `vector macro` above `material` as if it had the same height as `x`, cropping anything above that height. So for example `\constvec{\vecc{abc}}` yields \overleftarrow{abc} . This macro cannot be used in X_HT_EX.

2.3. Arrow Symbols

Each arrow comes as a triplet: the normal form, the long form, and the extendable form. The extendable form is similar to `\xrightarrow` and friends, an extendable arrow has the following use:

`\xarrow{<top material>} [<bottom material>]`

And creates an extended arrow to fit both the top and bottom material.

<code>\varrightarrow:</code>	<code>\varrightarrow</code>	<code>\longvarrightarrow</code>	<code>\xvarrightarrow</code>
<code>\displaystyle</code>	$A \rightarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\textstyle</code>	$A \rightarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\scriptstyle</code>	$A \rightarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\scriptscriptstyle</code>	$A \rightarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\varleftarrow:</code>	<code>\varleftarrow</code>	<code>\longvarleftarrow</code>	<code>\xvarleftarrow</code>
<code>\displaystyle</code>	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
<code>\textstyle</code>	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
<code>\scriptstyle</code>	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
<code>\scriptscriptstyle</code>	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
<code>\varrightthickspace:</code>	<code>\varrightthickspace</code>	<code>\longvarrightthickspace</code>	<code>\xvarrightthickspace</code>
<code>\displaystyle</code>	$A \rightsquigarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\textstyle</code>	$A \rightsquigarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\scriptstyle</code>	$A \rightsquigarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\scriptscriptstyle</code>	$A \rightsquigarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\varleftharpoonup:</code>	<code>\varleftharpoonup</code>	<code>\longvarleftharpoonup</code>	<code>\xvarleftharpoonup</code>
<code>\displaystyle</code>	$A \leftharpoonup B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
<code>\textstyle</code>	$A \leftharpoonup B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
<code>\scriptstyle</code>	$A \leftharpoonup B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
<code>\scriptscriptstyle</code>	$A \leftharpoonup B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
<code>\varleftrightharpoonup:</code>	<code>\varleftrightharpoonup</code>	<code>\longvarleftrightharpoonup</code>	<code>\xvarleftrightharpoonup</code>
<code>\displaystyle</code>	$A \rightrightarpoonup B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\textstyle</code>	$A \rightrightarpoonup B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\scriptstyle</code>	$A \rightrightarpoonup B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\scriptscriptstyle</code>	$A \rightrightarpoonup B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
<code>\varleftrightarrow:</code>	<code>\varleftrightarrow</code>	<code>\longvarleftrightarrow</code>	<code>\xvarleftrightarrow</code>
<code>\displaystyle</code>	$A \leftrightarrow B$	$A \longleftrightarrow B$	$A \xleftrightarrow[abc]{ABC} B$
<code>\textstyle</code>	$A \leftrightarrow B$	$A \longleftrightarrow B$	$A \xleftrightarrow[abc]{ABC} B$
<code>\scriptstyle</code>	$A \leftrightarrow B$	$A \longleftrightarrow B$	$A \xleftrightarrow[abc]{ABC} B$
<code>\scriptscriptstyle</code>	$A \leftrightarrow B$	$A \longleftrightarrow B$	$A \xleftrightarrow[abc]{ABC} B$

$\backslash varleftrightharp:$	$\backslash varleftrightharp$	$\backslash longvarleftrightharp$	$\backslash xvarleftrightharp$
$\backslash displaystyle$	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
$\backslash textstyle$	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
$\backslash scriptstyle$	$A \overleftarrow{B}$	$A \overleftarrow{B}$	$A \overleftarrow[abc]{ABC} B$
$\backslash scriptscriptstyle$	$A \overleftarrow{B}$	$A \overleftarrow{B}$	$A \overleftarrow[abc]{ABC} B$
$\backslash varrightleftharp:$	$\backslash varrightleftharp$	$\backslash longvarrightleftharp$	$\backslash xvarrightleftharp$
$\backslash displaystyle$	$A \leftarrow B$	$A \longrightarrow B$	$A \xleftarrow[abc]{ABC} B$
$\backslash textstyle$	$A \leftarrow B$	$A \longrightarrow B$	$A \xleftarrow[abc]{ABC} B$
$\backslash scriptstyle$	$A \overleftarrow{B}$	$A \overrightarrow{B}$	$A \overleftarrow[abc]{ABC} B$
$\backslash scriptscriptstyle$	$A \overleftarrow{B}$	$A \overrightarrow{B}$	$A \overleftarrow[abc]{ABC} B$
$\backslash varmapsto:$	$\backslash varmapsto$	$\backslash longvarmapsto$	$\backslash xvarmapsto$
$\backslash displaystyle$	$A \mapsto B$	$A \longmapsto B$	$A \xmapsto[abc]{ABC} B$
$\backslash textstyle$	$A \mapsto B$	$A \longmapsto B$	$A \xmapsto[abc]{ABC} B$
$\backslash scriptstyle$	$A \mapsto B$	$A \longmapsto B$	$A \xmapsto[abc]{ABC} B$
$\backslash scriptscriptstyle$	$A \mapsto B$	$A \longmapsto B$	$A \xmapsto[abc]{ABC} B$
$\backslash varhookrightarrow:$	$\backslash varhookrightarrow$	$\backslash longvarhookrightarrow$	$\backslash xvarhookrightarrow$
$\backslash displaystyle$	$A \rightarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
$\backslash textstyle$	$A \rightarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
$\backslash scriptstyle$	$A \rightarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
$\backslash scriptscriptstyle$	$A \rightarrow B$	$A \longrightarrow B$	$A \xrightarrow[abc]{ABC} B$
$\backslash varhookleftarrow:$	$\backslash varhookleftarrow$	$\backslash longvarhookleftarrow$	$\backslash xvarhookleftarrow$
$\backslash displaystyle$	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
$\backslash textstyle$	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
$\backslash scriptstyle$	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
$\backslash scriptscriptstyle$	$A \leftarrow B$	$A \longleftarrow B$	$A \xleftarrow[abc]{ABC} B$
$\backslash vardoublerightarrow:$	$\backslash vardoublerightarrow$	$\backslash longvardoublerightarrow$	$\backslash xvardoublerightarrow$
$\backslash displaystyle$	$A \Rightarrow B$	$A \Longrightarrow B$	$A \xRightarrow[abc]{ABC} B$
$\backslash textstyle$	$A \Rightarrow B$	$A \Longrightarrow B$	$A \xRightarrow[abc]{ABC} B$
$\backslash scriptstyle$	$A \Rightarrow B$	$A \Longrightarrow B$	$A \xRightarrow[abc]{ABC} B$
$\backslash scriptscriptstyle$	$A \Rightarrow B$	$A \Longrightarrow B$	$A \xRightarrow[abc]{ABC} B$

<code>\vardoubleleftarrow:</code>	<code>\vardoubleleftarrow</code>	<code>\longvardoubleleftarrow</code>	<code>\xvardoubleleftarrow</code>
<code>\displaystyle</code>	$A \Leftarrow B$	$A \Longleftarrow B$	$A \xLeftarrow{ABC} B$
<code>\textstyle</code>	$A \Leftarrow B$	$A \Leftarrow B$	$A \xLeftarrow{ABC} B$
<code>\scriptstyle</code>	$A \Leftarrow B$	$A \Leftarrow B$	$A \xLeftarrow{ABC} B$
<code>\scriptscriptstyle</code>	$A \Leftarrow B$	$A \Leftarrow B$	$A \xLeftarrow{ABC} B$
<code>\varcirclerightarrow:</code>	<code>\varcirclerightarrow</code>	<code>\longvarcirclerightarrow</code>	<code>\xvarcirclerightarrow</code>
<code>\displaystyle</code>	$A \circrightarrow B$	$A \longrightarrow B$	$A \xrightarrow{ABC} B$
<code>\textstyle</code>	$A \circrightarrow B$	$A \longrightarrow B$	$A \xrightarrow{ABC} B$
<code>\scriptstyle</code>	$A \circrightarrow B$	$A \longrightarrow B$	$A \xrightarrow{ABC} B$
<code>\scriptscriptstyle</code>	$A \circrightarrow B$	$A \longrightarrow B$	$A \xrightarrow{ABC} B$
<code>\varcircleleftarrow:</code>	<code>\varcircleleftarrow</code>	<code>\longvarcircleleftarrow</code>	<code>\xvarcircleleftarrow</code>
<code>\displaystyle</code>	$A \leftrightharpoonup B$	$A \longleftharpoonup B$	$A \xleftharpoonup{ABC} B$
<code>\textstyle</code>	$A \leftrightharpoonup B$	$A \longleftharpoonup B$	$A \xleftharpoonup{ABC} B$
<code>\scriptstyle</code>	$A \leftrightharpoonup B$	$A \longleftharpoonup B$	$A \xleftharpoonup{ABC} B$
<code>\scriptscriptstyle</code>	$A \leftrightharpoonup B$	$A \longleftharpoonup B$	$A \xleftharpoonup{ABC} B$

2.4. Wide Accents

Wide accents provide variants to the commonly used accents like `\widehat` and `\widetilde`. Unlike these accents, PDFMSYM's wide accents can grow arbitrarily large.

<code>\varwidehat:</code>	<code>\varwidecheck:</code>		
<code>\displaystyle</code>	$\widehat{ABC} + D$	<code>\displaystyle</code>	$\widehat{ABC} + D$
<code>\textstyle</code>	$\widehat{ABC} + D$	<code>\textstyle</code>	$\widehat{ABC} + D$
<code>\scriptstyle</code>	$\widehat{ABC} + D$	<code>\scriptstyle</code>	$\widehat{ABC} + D$
<code>\scriptscriptstyle</code>	$\widehat{ABC} + D$	<code>\scriptscriptstyle</code>	$\widehat{ABC} + D$
<code>\varwidetilde:</code>			
<code>\displaystyle</code>	$\widetilde{ABC} + D$		
<code>\textstyle</code>	$\widetilde{ABC} + D$		
<code>\scriptstyle</code>	$\widetilde{ABC} + D$		
<code>\scriptscriptstyle</code>	$\widetilde{ABC} + D$		

2.5. Extendable Operators

Extendible operators extend to the width of the material in their limits. These operators should only be used in display mode, since they use the display modes of the operators. They are `\suum` and `\prood`:

$$\sum_{\text{abcdef}}^{\text{ABCDEF}}$$

$$\prod_{\text{abcdef}}^{\text{ABCDEF}}$$

These are not available in X_ET_EX.

3. Defining Your Own Symbols

PDFMSYM provides an interface for creating your own mathematical symbols through the use of `\pdfliteral`s. This interface requires prior knowledge of drawing with PDFs.

`\@linehead@type {\pdfcode}{\width}` : This creates a “linehead” which is used to cap lines, like `\@rarrow` (`\rarr`). `\pdfcode` is the actual code used to draw the symbol, and it should be noted that all necessary transformations to the linehead are done by `\@linehead@type` and should not be included in the code. This includes the setting of the width and transforming the coordinate system. The `width` is the width of the drawing of the `\pdfcode`.

This macro actually accepts more parameters, but they’re used internally and therefore aren’t necessary to explain. Therefore the only use this macro should be for is defining line heads. For example, the definition of `\@rarrow` is:

```
\def\@rarrow{\@linehead{0 0 m 2 0 1 1 0 0 1 0 1.5 c 2 0 m 1 0 0 -1 0 -1.5 c S}{2}}
```

The predefine lineheads are `\@rarrow`, `\@larrow`, `\@rsharp`, `\@lsharp`, `\@rdsharp`, `\@rlsharp`, `\@mapcap`, `\@rsarrow`, `\@lsarrow`, `\@backhook`, `\@fronthook`, `\@doublerarrow`, `\@doublelarrow`, `\@circlecap`.

`\@vecc@def {\vectorname}{\leftcap}{\rightcap}` : This creates a vector macro, like `\vecc`. This creates both the normal and short variations of the vector. For example, the definition of the `vecc` vectors is:

```
\@vecc@def{\vecc}{\linecap}{\rarrow}
```

`\@arrow@def {\arrowname}{\leftcap}{\rightcap}` : This creates an arrow macro, like `\varrightarrow`. This creates the normal, long, and extendable versions of the arrow. For example, the definition of the `varrightarrow` vectors is:

```
\@arrow@def{\varrightarrow}{\linecap}{\rarrow}
```

`\@wide@accent {\pdfcode}` : This creates a wide accent, like `\varwidecheck`. The width of the drawing by the `\pdfcode` should be 1, and it should be filled not stroked (since the accent is transformed to stretch over the material beneath it). Again this macro should only be used to define wide accents. For example, the definition of `\varwidecheck` is:

```
\def\varwidecheck{\@wide@accent{0 1.3 m .5 -.4 1 1 1.3 1 1 1.6 1 .5 .3 1 0 1.6 1 f}}
```

`\pdf@drawing@macro {\name}{\pdfcode}{\width}{\height}{\horizontalskew}{\depth}` : This creates a text mode symbol like `\lightning`. It is important that the `\pdfcode` fits inside the box created by `width`, `height`, and `depth` since the drawing is placed inside of an XForm and so anything outside the box will be cropped. The `horizontal skew` can be used to shift the symbol so that it fits horizontally inside the box. For example, the definition of `\lightning` is:

```
\pdf@drawing@macro{lightning} % The lightning symbol is drawn upright
{.86603 -.5 .5 .86603 0 0 cm % and rotated 30 degrees
 1 J 1 j .6 w
 -3 10 m -3 4.133975 1 0 5.866025 1 0 0 1 -1.125 1.5 1 0 0 1 1.125 1.5 1 S}
{4.2pt}{10.5pt}{.5pt}{.9pt}
```

`\pdf@drawing@math@macro {\name}{\pdfcode}{\width}{\height}{\skew}{\depth}{\style scaling}` : This creates a math mode symbol like `\divs`. The first few parameters are identical in use as `\pdf@drawing@macro`’s, and `style scaling` is used to set the scaling for the symbol in different math styles. `style scaling` should be three groups: the first group is the scaling used in `textstyle`, the second in `scriptstyle`, and the third in `scriptscriptstyle`. Each of these scalings should consist of two components: the fractional scaling and the decimal scaling. So for example if we’d like to scale it by 0.6 the scaling would be `\{6 / 10\}{0.6}`. This is necessary since `\dimexpr` doesn’t play with decimals nicely, but `\pdfliteral` requires them. For example, the definition of `\divs` is:

```
\pdf@drawing@math@macro{@divs}
{1.3 w 1 j
 2.5 1 0 .1 re
 2.5 5 0 .1 re
 2.5 9 0 .1 re B}
{5.4pt}{10pt}{0pt}{.2pt}
{{1}{1}}{{7 / 10}{.7}}{{11 / 20}{.55}}
\def\divs{\mathrel{\@divs}} % Make divs a relation
```

`\putsym {<main symbol>} {<secondary symbol>}` : This centers the *secondary symbol* over the *main symbol*, and can be used to create symbols like `\aint`. Note that doing this creates a symbol which acts like an Ord on the left side and whatever type of atom *main symbol* is on the right (glue-wise). So it may be necessary to add some math atom “hackery” around the `\putsym` in order to get the target glue. For example, the definition of `\aint` is:

```
\def\aint{\mathop{}\mathclose{}\putsym\int-}
```

The `\mathop{}\mathclose{}` makes it act like an Op on the left (the `\mathclose` removes any glue added on the right of the `\mathop`). Usually the definition is simpler, but this is slightly more complicated since `\int` has specially placed limits. Another example, this time the definition of `\bigdcup` is:

```
\def\bigdcup{\mathop{\putsym\bigcup\cdotp}}
```

`\@wide@operator {<name>} {<operator>} {<first cut>} {<second cut>}` : This creates an extendable operator of *operator* whose name is *name*, like `\suum`. *first cut* is a decimal value which is where on the width of *operator* to make the first slice, and similar for *second cut*. The extendable part of the new operator is the area between the two cuts. For example, the definition of `\suum` is:

```
\@wide@operator{suum}\sum{.52}{.6}
```

You can see where the slices are for a wide operator using the `\@show@slices` macro, for example

```
\@show@slices{suum}
```

gives:



These macros are not available for X_ET_EX.