

The `pst-pdf` package^{*}

Rolf Niepraschk[†] Hubert Gäßlein

2006/07/14

1 Introduction

The package `pst-pdf` simplifies the use of graphics from PStricks and other PostScript code in PDF documents. As in building a bibliography with `BIBTEX` additional external programmes are being invoked. In this case they are used to create a PDF file (`\PDFcontainer`) that will contain all this graphics material. In the final document this contents will be inserted instead of the original PostScript code.

2 Usage

2.1 Package options

active Activates the extraction mode (DVI output). An explicit declaration usually is not necessary (default in `LATEX` mode).

inactive No special actions; only the packages `pstricks` and `graphicx` are loaded (default in `VTEX`). Can be used to just convert the document with `LATEX` into a DVI file while avoiding the automatic extraction mode.

pstricks The package `pstricks` is loaded (default).

nopstricks The package `pstricks` does not get loaded. Once it is detected that `pstricks` was loaded however in some other way, the `pspicture` environment is treated as if the option “`pstricks`” was given.

draft From the `\PDFcontainer` file included graphics is displayed as frame in `pdfLATEX` mode.

final From the `\PDFcontainer` file included graphics is correctly displayed in `pdfLATEX` mode (default).

tightpage The graphics’ dimensions in the `\PDFcontainer` file match exactly those of the corresponding `TEX` boxes (default).

notightpage The dimensions of the `TEX` box corresponding to its graphics is not always correct, since a PostScript statement can draw outside its box. The option “`notightpage`” makes the graphics in the `\PDFcontainer` file to be at

^{*}This document corresponds to `pst-pdf` v1.1n, dated 2006/07/14. Thanks to Peter Dyballa for the translation.

[†]`Rolf.Niepraschk@ptb.de`

least the size of the whole page. To be able to make use of the graphics' in a later pdfL^AT_EX run, the \PDFcontainer file needs to be finished in a way that each graphics gets reduced in size to its visible part. For this an external programme like **pdfcrop**¹ can be useful. Its use can save declaring the option "trim" (see also section 2.4).

displaymath In PDF mode the mathematical environments **displaymath**, **eqnarray**, and **\$\$** get also extracted and included as graphics. This way additional PStricks extensions can easily be added to the contents of these environments. (Question: how do AMSL^AT_EX environments behave?)

<other> All other options are passed to **pstricks** package.

2.2 Program calls

The following table shows the course necessary to create a PDF document containing PostScript graphics². As comparison the analogous course for a bibliography is shown.

PostScript graphics	bibliography
pdflatex document.tex	pdflatex document.tex
<i>auxiliary calls</i>	
latex document.tex	
dvips -o document-pics.ps document.dvi	
ps2pdf document-pics.ps	bibtex document.aux
pdflatex document.tex	pdflatex document.tex

While creating the output only code from inside a **pspicture** or **postscript** environment is considered. PostScript graphics files, which are passed as parameter of an **\includegraphics** statement, too are included into the \PDFcontainer file. This file's name is by default **(\jobname)-pics.pdf**. It can be changed by re-defining the macro \PDFcontainer.

2.3 User commands

pspicture `\begin{pspicture}[(keys)] ((x0,x1))((y0,y1)) ... \end{pspicture}`
 The **pspicture** environment is not available when the option "nopstricks" was given. It is to be used the same way as if in PStricks. In pdfL^AT_EX mode this environment's contents is only displayed when the \PDFcontainer file was created before.

postscript `\begin{postscript}[(keys)] ... \end{postscript}`
 The **postscript** environment can contain any code except floats. In pdfL^AT_EX mode its contents is take too off the \PDFcontainer file. Other as in the **pspicture** environment the necessary space is not always preserved when the \PDFcontainer file does not exist yet.

\includegraphics `\includegraphics[(keys)]{\filename}`

¹CTAN: support/pdfcrop/

²The TeX distribution "teTeX" contains a UNIX shell script **ps4pdf** which executes all the necessary steps. See: CTAN: **macros/latex/contrib/ps4pdf/**

To be used as in `graphics/graphicx` defined. In pdfL^AT_EX mode it is now additionally feasable to pass the name of an EPS file. Its visible contents too is taken from the `\PDFcontainer` file.

```
\includegraphicx          \includegraphicx[<keys>]{<pxfadd>}<>{<ovpfd>}[<ovpbgd>]{<filename>}
Wie im Paket psfragx definiert zu verwenden.

\savepicture           \savepicture{<name>}
The last output graphics (result of the pspicture or postscript environments or the \includegraphics statement with an PostScript file as argument) is being saved in a file under the name as given by the parameter.

\usepicture            \usepicture[<keys>]{<name>}
Die zuvor mit \savepicture gespeicherte Grafik wird ausgegeben. Der optionale Parameter entpricht dem bei der Anweisung \includegraphics möglichen.

pst-pdf-defs          \begin{pst-pdf-defs} ... \end{pst-pdf-defs}
Sollen eigene Makros oder Umgebungen definiert werden, die das Zeichen & (andere?) im Ersetzungstext enthalten, so müssen diese Definitionen von der Umgebung pst-pdf-defs umschlossen werden.
```

2.4 Command options

The behaviour of the `\includegraphics` and `\usepicture` statements and the `postscript` environment can be modified with any of the following parameters (key value syntax):

frame=<true|false> As with the `\fbox` statement a frame is drawn around the graphics. Any change of size due to rotation is taken into account. Drawing happens in pdfL^AT_EX mode; before, in creating the `\PDFcontainer` file, it is ignored. Default: false.

innerframe=<true|false> As in “frame”, but the frame is drawn around the graphics, not its box.

ignore=<true|false> If “true” no graphics is output. With `\savepicture{<name>}` the graphics can be used later in a different place via `\usepicture`. Default: false.

showname=<true|false> A caption of minimal font size records the used file’s name. Default: false.

namefont= Controls the font used when “showname=true” is set. Default: `\ttfamily\tiny`

All parameters can be set globally as in `\setkeys{Gin}{<key=>value}`.

3 Implementation

¹ `(*package)`

3.1 Package options

² `\newcommand*\ppf@TeX@mode{-1}`

```

3 \newcommand*\ppf@draft{false}
4 \newif\if@ppf@PST@used\@ppf@PST@usedtrue
5 \newif\if@ppf@tightpage \@ppf@tightpagetrue
6 \DeclareOption{active}{\def\ppf@TeX@mode{0}}
7 \DeclareOption{inactive}{\def\ppf@TeX@mode{9}}
8 \DeclareOption{ignore}{\def\ppf@TeX@mode{999}}
9 \DeclareOption{pstricks}{\@ppf@PST@usedtrue}
10 \DeclareOption{nopstricks}{\@ppf@PST@usedfalse}
11 \DeclareOption{displaymath}{%
12   \PassOptionsToPackage{\CurrentOption{preview}}}
13 \DeclareOption{draft}{\def\ppf@draft{true}}
14 \DeclareOption{final}{\def\ppf@draft{false}}%
15   \PassOptionsToPackage{\CurrentOption{graphicx}}%
16 \DeclareOption{notightpage}{\@ppf@tightpagefalse}%
17 \DeclareOption{tightpage}{\@ppf@tightpagetrue}%
18 \DeclareOption*{%
19   \PassOptionsToPackage{\CurrentOption{pstricks}}}
20 \ProcessOptions\relax
21 \ifnum\ppf@TeX@mode=999\relax\expandafter\endinput\fi

```

3.2 Compiler tests

It is tested which \TeX compiler in which mode of operation is actually used (see ‘`graphics.cfg`’ in $\text{te}\text{\TeX}/\text{T}\text{\TeX}$ Live). Accordingly the environments `pspicture` and `postscript` gain each a different range of functions. This test is only executed when the options `active` or `inactive` were not given.

```

22 \ifnum\ppf@TeX@mode=-1\relax
23   \begingroup
Default ( $\text{\TeX}$  with a dvi-to-ps converter)
24   \chardef\x=0 %
Check pdf $\text{\TeX}$ 
25   \@ifundefined{pdfoutput}{}{%
26     \ifcase\pdfoutput\else
27       \chardef\x=1 %
28     \fi
29   }%
Check V $\text{\TeX}$ 
30   \@ifundefined{OpMode}{}{\chardef\x=2 }%
31 \expandafter\endgroup
32 \ifcase\x
  ⇒ DVI mode
33   \def\ppf@TeX@mode{0}%
34 \or
  ⇒ pdf $\text{\TeX}$  is running in PDF mode
35   \def\ppf@TeX@mode{1}%
36 \else
  ⇒ V $\text{\TeX}$  is running
37   \def\ppf@TeX@mode{9}%
38 \fi
39 \fi

```

```

40 \newcommand*\PDFcontainer{}
41 \edef\PDFcontainer{\jobname-pics.pdf}
42 \newcounter{pspicture}
43 \newcommand*\ppf@other@extensions[1]{}
44 \newcommand*\usepicture[2][]{}
45 \newcommand*\savepicture[1]{}

pst-pdf-defs
46 \newenvironment*{pst-pdf-defs}%
47 {%
48   \endgroup
49 %   ??? \currenvline
50 }%
51 \begingroup
52 \def\currenvir{pst-pdf-defs}%
53 }

54 \RequirePackage{graphicx}%
55 \let\ppf@Ginclude@graphics\Ginclude@graphics
56 \let\ppf@Gin@extensions\Gin@extensions
57 \let\ppf@Gin@ii\Gin@ii
58 \newif\if@ppf@pdftex@graphic
59 \newif\if@Gin@frame\Gin@framefalse
60 \newif\if@Gin@innerframe\Gin@innerframefalse
61 \newif\if@Gin@showname\Gin@shownamefalse
62 \newif\if@Gin@ignore\Gin@ignorefalse

\ifpr@outer in fact is defined in package preview. We have to do it here too since
otherwise TeX could “stumble and fall” while parsing the \ifcase structure.
63 \newif\ifpr@outer

\ppf@is@pdfTeX@graphic Parameter #1 is the name of a graphics file with or without extension, parameter
#2 contains the valid extensions in PDF mode, parameter #3 contains the valid
extensions in DVI mode. If it works to process the graphics in PDF mode, then
the statements in #4 are executed, otherwise those in #5.
64 \newcommand*\ppf@is@pdfTeX@graphic[5]{%
65   \if@ppf@pdftex@graphicfalse%
66   \begingroup
67     \edef\pdfTeXext{#2}%

Instead of loading the found graphics, only a test on file name extension.
68 \def\Gin@setfile##1##2##3{%
69   \edef\@tempb{##2}%
70   \for@tempa:=\pdfTeXext\do{%
71     \ifx\@tempa\@tempb\global\@ppf@pdftex@graphictrue\fi}%
}

File types for both modes need to be determined to prevent a wrong error message
“File ‘#1’ not found”.
72 \edef\Gin@extensions{#2,#3}%

Trial invocation. Output is completely inhibited.
73 \pr@outerfalse\ppf@Ginclude@graphics{#1}%
74 \endgroup
75 \if@ppf@pdftex@graphic#4\else#5\fi
76 }

```

```
77 \ifcase\ppf@TeX@mode\relax
```

3.3 Extraction mode (DVI output)

The `pspicture` environment retains any definition from `pstricks.tex`. Only the code from the environments `pspicture` and `postscript` as well as `\includegraphics` with PostScript files leads to records into the DVI file. The remainder of the document's code is ignored for output. After conversion of the DVI file via PostScript ("dvips") into PDF (`\PDFcontainer` file) each graphics takes exactly one page in the `\PDFcontainer` file. The `\TeX` compiler with DVI output and the package option "active" both force this mode.

```
78 \PackageInfo{pst-pdf}{%
79   MODE: \ppf@TeX@mode\space (dvi -- extraction mode)}
80 \nofiles
81 \if@ppf@PST@used\RequirePackage{pstricks}\fi
82 \RequirePackage[active,dvips,tightpage]{preview}[2005/01/29]%
83 \newcommand*\ppf@PreviewBbAdjust{}%
84 \newcommand*\ppf@RestoreBbAdjust{}%
85 \let\PreviewBbAdjust\ppf@PreviewBbAdjust}%
```

The pdf^LA_TE_X mode compliant graphics file formats are needed too.

```
86 \begingroup
87   \let\AtBeginDocument\gobble \let\PackageWarningNoLine\gobbletwo
88   \def\pdftexversion{121}\input{pdftex.def}%
89   \edef\x{\endgroup\def\noexpand\ppf@other@extensions{\Gin@extensions}}
90   }%
91 \x
```

In PDF mode no rules must be defined for its compliant (PNG, JPEG, PDF) graphics file formats (because of for example 'dvips' extensions). The universal EPS rule is used to at least find these files.

```
92 \AtBeginDocument{%
93   \@for\@tempa:=\ppf@other@extensions\do{%
94     \expandafter\let\csname Gin@rule@\@tempa\endcsname\relax}%
95   \DeclareGraphicsRule{*}{eps}{*}{}}
```

No function in this mode.

```
96 \define@key{Gin}{innerframe}[true]{}
97 \define@key{Gin}{frame}[true]{}
98 \define@key{Gin}{ignore}[true]{}
99 \define@key{Gin}{showname}[true]{}
100 \define@key{Gin}{namefont}{}

101 \if@ppf@tightpage\else
102   \def\PreviewBbAdjust{%
103     -.5\paperwidth -.5\paperheight .5\paperwidth .5\paperheight}%
104   \AtEndDocument{%
105     \PackageWarningNoLine{pst-pdf}{Picture container needs cropping.}}%
106 \fi
```

`postscript` The `postscript` environment utilises the `trim` option in the same manner as does `\includegraphics` (any specification without dimension is interpreted as if given in bp).

```
107 \newenvironment{postscript}[1][]{}
```

```

108  {%
109   \global\let\ppf@PreviewBbAdjust\PreviewBbAdjust
110   \if@ppf@tightpage
111     \begingroup
112       \setkeys{Gin}{#1}%
113       \xdef\PreviewBbAdjust{%
114         -\Gin@vllx bp -\Gin@vlly bp \Gin@vurx bp \Gin@vury bp}%
115     \endgroup
116   \fi
117   \ignorespaces
118 }%
119 {\aftergroup\ppf@RestoreBbAdjust}%

120 \PreviewEnvironment{postscript}%
121 \AtBeginDocument{%
122   \@ifundefined{PSTricksLoaded}{}%
123 }%

```

pspicture Announce preview original definition.

```

124   \PreviewEnvironment{pspicture}%

```

psmatrix Announce preview original definition.

```

125   \@ifundefined{psmatrix}{}%
126   {%
127     \PreviewEnvironment{psmatrix}%
128     \newcommand*\ppf@set@mode{}%
129     \newcommand*\ppf@test@mmode{}%
130     \ifmmode
131       \ifinner
132         \let\ppf@set@mode=$%
133       \else
134         \def\ppf@set@mode{\$}%
135       \fi
136     \else
137       \let\ppf@set@mode=\empty
138     \fi
139   }%
140   \let\ppf@psmatrix=\psmatrix
141   \expandafter\let\expandafter\ppf@pr@psmatrix%
142     \expandafter=\csname pr@\string\psmatrix\endcsname
143   \let\ppf@endpsmatrix=\endpsmatrix
144   \def\psmatrix{\ppf@test@mmode\ppf@psmatrix}
145   \expandafter\def\csname pr@\string\psmatrix\endcsname{%
146     \ppf@set@mode\ppf@pr@psmatrix}%
147   \def\endpsmatrix{\ppf@endpsmatrix\ppf@set@mode}%
148 }%

```

Announce internal macro `\pst@object` to enable the use of some PStricks code outside of `pspicture` environments. At the moment invocations of the following kind are feasible:

```

\pst@object {[m]}[*]{o}{o}{o}{o}{o}{o}
(m = necessary, * = optional, o = optional)

```

More than three optional arguments at the call's end, as in \psline possible, do not work yet.

```
149 \PreviewMacro[{}]*[]%  
150     ?\bgroup{\#1}{\#1}}}{}}%  
151     ?\bgroup{\#1}{\#1}}}{}}%  
152     ?{\#1}{\#1}}}{}}%  
153     ?{\#1}{\#1}}}{}}%  
154     ?{\#1}{\#1}}}{}}%  
155     }]{\pst@object}
```

Prevent multiple test-wise setting of table contents by “`tabularx`”.

```
156     \@ifundefined{tabularx}{}{\%  
157         \def\tabularx#1#2{\tabular[#2]\%  
158             \newcolumntype{X}{c}\%  
159             \let\endtabularx=\endtabular}\%
```

Support of \includegraphicx from the package psfragx.

```
160     \@ifundefined{pfx@includegraphicx}{}{%
161         \PreviewMacro[{\{}{\}}]{\pfx@includegraphicx}%
162     }%
```

`\Ginclusion@graphics` All graphics content of well known format (for instance EPS files) is treated in a regular way, which in this mode denotes that it is subject to preview functions. Other graphics content (for instance PDF files) is ignored.

```
163 \def\Ginclude@graphics#1{%
164   \ifpr@outer
```

Generally pdfTeX supported graphics formats are intended to be preferred (inclusion in final pdfTeX run). If it's a PostScript type graphics, then the original definition is in function again and registration for the `preview` package is necessary in order to convert this PostScript type graphics into PDF.

165 \ppf@is@pdfTeX@graphic{\ppf@other@extensions}{\Gin@extensions} %
Dummy box to prevent a division by zero while scaling or rotating. Otherwise ignored.

```
166      {\rule{10pt}{10pt}}%  
167      {\ppf@Ginclude@graphics{#1}}%  
168  \else
```

Inside a PostScript environment (`pspicture` etc.) `\includegraphics` has to behave as in its original definition (only DVIPS supported graphics formats are allowed).

```
169     \ppf@Ginclude@graphics{#1}%
170   \fi
171 }%
```

```
172  \PreviewMacro[{\{}}]{\ppf@Ginclude@graphics}%
173  \let\pdfliteral\@gobble%
174 \or
```

3.4 pdfLATEX mode (PDF output)

When the `\PDFcontainer` file (default: `\jobname-pics.pdf`) exists, the contents of the environments `pspicture` and `postscript` is ignored. Instead the corresponding graphics from the `\PDFcontainer` file is used.

```

175  \PackageInfo{pst-pdf}{MODE: \ppf@TeX@mode\space (pdfTeX mode)}%
176  \o@temptokena{%
177    \let\Gin@PS@file@header\@gobble\let\Gin@PS@literal@header\@gobble
178    \let\Gin@PS@raw\@gobble\let\Gin@PS@restored\@gobble
179    \o@ifundefined{PSTricksLoaded}{}{%

```

Necessary if PSTricks < 2.0.

```

180    \PSTricksOff
181    \o@ifundefined{c@lor@to@ps}{\def\c@lor@to@ps#1 #2\o@{}{}}{%

```

Prevent pdfTeX's message Non-PDF special ignored!.

```

182  \if\ppf@PST@used
183    \let\ppf@temp\AtBeginDvi\let\AtBeginDvi\@gobble
184    \RequirePackage{pstricks}\let\AtBeginDvi\ppf@temp
185  \fi

```

PostScript output is now inhibited and later once again.

```

186  \the\o@temptokena %% ?????
187  \expandafter\AtBeginDocument\expandafter
188  {\the\o@temptokena\o@temptokena{}{}}%
189  \o@ifundefined{PSTricksLoaded}{}{%
190  \f%

```

To parse the arguments of PSTricks' `\pst@object` we load `preview` in active mode, but restore the default definitions of `\output` and `\shipout`. `\pr@startbox` and `\pr@endbox` serve here only to disable `\pst@object` and to load the corresponding graphics from the `\PDFcontainer` file. At present a maximum of three optional parameters in round braces (parenthesis) at the end of `\pst@object` is supported, which is sufficient, but not always enough.

```

191  \newtoks\ppf@temptoken
192  \ppf@temptoken\expandafter{\the\output}%
193  \let\ppf@nofiles\nofiles \let\nofiles\relax
194  \RequirePackage[active]{preview}[2005/01/29]%
195  \let\shipout=\pr@shipout \let\nofiles\ppf@nofiles
196  \output\expandafter{\the\ppf@temptoken}%
197  \ppf@temptoken{}{%

```

`\pr@startbox`, `\pr@endbox`: simpler over original definitions.

```

198  \long\def\pr@startbox#1#2{%
199  \ifpr@outer
200    \toks@{#2}%
201    \edef\pr@cleanup{\the\toks@}%
202    \setbox\@tempboxa\vbox\bgroup
203    \everydisplay{}%
204    \pr@outerfalse%
205    \expandafter\@firstofone
206  \else
207    \expandafter\@gobble
208  \fi{#1}{}%
209  \def\pr@endbox{%
210    \egroup
211    \setbox\@tempboxa\box\voidb@x
212    \ppf@@getpicture
213    \pr@cleanup}%

```

(See also the identical definition in DVI mode.)

```

214     \AtBeginDocument{%
215         \@ifundefined{pst@object}{}{%
216             {%
217                 \PreviewMacro[{{}*[]}{%
218                     ?\bgroup{\#1}{\#1}}{}{%
219                     ?\bgroup{\#1}{\#1}}{}{%
220                     ?(\#1){(\#1)}{}{%
221                     ?(\#1){(\#1)}{}{%
222                     ?(\#1){(\#1)}{}{%
223                     }]{\pst@object}}{}{%
224                 }{%
225             }{%
226         }{%
227     }{%
228 }
```

Too the supported file name extensions from DVI mode are needed.

```

226     \begingroup
227         \input{dvips.def}%
228         \edef\x{\endgroup\def\noexpand\ppf@other@extensions{\Gin@extensions}}%
229     \x
```

Dummy definition for in DVI mode supported file formats.

```

230     \DeclareGraphicsRule{*}{eps}{*}{%
231         \define@key{Gin}{innerframe}[true]{%
232             \lowercase{\Gin@boolkey{#1}{innerframe}}{%
233             \define@key{Gin}{frame}[true]{%
234                 \lowercase{\Gin@boolkey{#1}{frame}}{%
235                 \define@key{Gin}{ignore}[true]{%
236                     \lowercase{\Gin@boolkey{#1}{ignore}}{%
237                     \define@key{Gin}{frame@@}{%
238                         (For internal use only!)%
239                         \edef\@tempa{\toks@{\noexpand\frame{\the\toks@}}}{%
240                             \ifcase#1\relax
241                                 \ifGin@innerframe\else\let\@tempa\relax\fi
242                             \or
243                                 \ifGin@frame\else\let\@tempa\relax\fi
244                             \fi
245                         \@tempa
246                         }{%
247                             \lowercase{\Gin@boolkey{#1}{showname}}{%
248                             \define@key{Gin}{namefont}{%
249                                 \begingroup
250                                     \temptokena\expandafter{\ppf@namefont#1}{%
251                                         \edef\x{\endgroup\def\noexpand\ppf@namefont{\the\temptokena}}{%
252                                         \x
253                                         }{%
254                                         \newcommand*\ppf@filename{}{%
255                                         \newcommand*\ppf@namefont{\tiny\ttfamily}{%
256                                         \newcommand*\ppf@Gin@keys{}{%
257                                         \let\ppf@Gin@setfile\Gin@setfile
```

\Gin@setfile Save real file name and, if applicable, page number for later use.

```

258     \def\Gin@setfile#1#2#3{\ppf@Gin@setfile{#1}{#2}{#3}}%
259     \xdef\ppf@filename{%
260         #3\ifx\GPT@page\empty\else(\GPT@page)\fi}}%
```

```
\Gin@ii Examine the options “frame”, “ignore”, etc. as soon as other special cases.
```

```
261 \def\Gin@ii[#1]#2{%
262     \begingroup
```

The value of `\ifGin@innerframe` has to be known before the inner frame is drawn. The values for `\ifGin@showname` and `\ppf@namefont` need to be available after rendering the graphics too. Thus beforehand and protected inside a group examine the options.

```
263     \setkeys{Gin}{#1}%
264     \temptokena{#1}\def\tempb{#2}%
```

Finds empty file name when calling `\usepicture`.

```
265     \ifx\tempb\empty\else
266         \ppf@is@pdfTeX@graphic{#2}{\Gin@extensions}{\ppf@other@extensions}%
```

Graphics out of `\PDFcontainer` are complete – scaled, rotated, etc. Don’t apply these things again and therefore ignore the optional parameters.

```
267     {%
268         \ifx\tempb\PDFcontainer
269             \temptokena{page=\GPT@page}%
270         \fi
271     }%
272     {%
273         \refstepcounter{pspicture}%
274         \temptokena{page=\the\c@pspicture}\def\tempb{\PDFcontainer}%
275     }%
276     \fi
277     \ifGin@ignore\else
        “frame@=0” = inner frame, “frame@=1” = outer frame.
278     \edef\tempa{\noexpand\ppf@Gin@ii[frame@=0,\the\temptokena,
279         frame@=1]{\tempb}}%
280     \tempa
281     \ifGin@showname
282         \ppf@namefont
283         \raisebox{-\ht\strutbox}[0pt][0pt]{\llap{\ppf@filename}}%
284         \gdef\ppf@filename{}%
285     \fi
286     \fi
287     \endgroup
288 }%
```

```
289 \IfFileExists{\PDFcontainer}%
290 {%
```

```
\ppf@container@max The number of pages as contained in \PDFcontainer file.
```

```
291 \pdfximage{\PDFcontainer}%
292 \edef\ppf@container@max{\the\pdflastximagepages}%
```

```
293 \AtEndDocument{%
294     \ifnum\c@pspicture>\z@
```

A warning only makes sense when a graphics is needed at all.

```
295     \ifnum\c@pspicture=\ppf@container@max\else
296         \PackageWarningNoLine{pst-pdf}{%
297             ‘\PDFcontainer’ contains \ppf@container@max space pages}
```

```

298      \MessageBreak but \the\c@pspicture\space pages are requested:
299      \MessageBreak File '\PDFcontainer' is no more valid!
300      \MessageBreak Recreate it
301      }%
302      \fi
303      \fi
304      }%
305      }%
306      \%
307      \def\ppf@container@max{0}%
308      \AtEndDocument{%
309          \ifnum\c@pspicture>\z@
310              \filename@parse{\PDFcontainer}%
311              \PackageWarningNoLine{pst-pdf}{%
312                  File '\PDFcontainer' not found.\MessageBreak
313                  Use the following commands to create it:\MessageBreak
314                  -----
315                  \MessageBreak
316                  latex \jobname.tex\MessageBreak
317                  dvips -o \filename@base.ps \jobname.dvi\MessageBreak
318                  ps2pdf \filename@base.ps\MessageBreak
319                  -----
320          }%
321          \fi
322      }%
323      }%

```

\ppf@isnum If parameter #1 is numeric, the instructions in #2, otherwise those in #3 are executed (see `bibtopic.sty`).

```

324  \newcommand\ppf@isnum[1]{%
325      \if!\ifnum9<1#1!\else_\fi\expandafter\@firstoftwo
326      \else\expandafter\@secondoftwo\fi}%

```

`postscript` Both environments ignore their contents and load instead the corresponding graphics out of the `\PDFcontainer` file. The value of the herein used `pspicture` counter's value can be used in `\label`/`\ref`.

`psmatrix`

```

327  \newcommand*\ppf@set@mode{}%
328  \newcommand*\ppf@test@emode{}%
329  \ifmmode
330      \ifinner
331          \let\ppf@set@mode=$%
332      \else
333          \def\ppf@set@mode{$$}%
334      \fi
335  \else
336      \let\ppf@set@mode=\empty
337  \fi
338 }
339 \newenvironment{postscript}[1] []
340 {%
341     \ppf@test@emode
342     \gdef\ppf@Gin@keys{}%

```

```

343      \def\@tempa{postscript}\ifx\@tempa\@currenvir\gdef\ppf@Gin@keys{\#1}\fi
Inside this environment parsing of \pst@object's arguments is not necessary, thus
the original definition is used again.
344      \expandafter\let\expandafter\pst@object
345          \csname pr@string\pst@object\endcsname
346          \pr@outerfalse
Needed for \psmatrix.
347      \makeother\&%
348      \def\Gin@ii[##1##2{}]\setbox\@tempboxa=\vbox\bgroup
349          \ppf@set@mode
350      \%
351      {\ppf@set@mode\egroup\aftergroup\ppf@@getpicture}%
352      \AtBeginDocument{%
353          \@ifundefined{PSTricksLoaded}{}%
354      \%
355          \iffalse
356              \PreviewEnvironment{pspicture}% Why doesn't it work?
357              \g@addto@macro\pspicture{%
358                  \%\pr@outerfalse% necessary, or already there anyway?
359                  \makeother\&% necessary?
360                  \def\Gin@ii[##1##2{}]{%
361                  \%
362                      \g@addto@macro\endpspicture{\ppf@@getpicture}%
363                  \else
364                      \def\pst@@picture[##1](##2,##3)(##4,##5){\postscript}%
365                      \def\endpspicture{\endpostscript\endgroup}%
366                  \fi
367                  \ifundefined{psmatrix}{}%
368                  {\let\psmatrix=\postscript\let\endpsmatrix=\endpostscript}%
369              }%
370          \ifundefined{pfx@includegraphicx}{}{%

```

Die im pdfTeX-Modus unnütze Umdefinition von `\includegraphics` (Paket `psfragx`) führt zu zweifachem Einfügen des Ergebnisses, weshalb die Originaldefinition wiederhergestellt wird.

```

371      \let\includegraphics=pfx@includegraphics
372      \def\pfx@includegraphicx#1#2{\ppf@@getpicture}%
373      \%
374  }%

```

`\savepicture` Saves the recent graphics' number in a macro named `\ppf@@#1`.

```

375  \def\savepicture#1{%
376      \expandafter\xdef\csname ppf@@#1\endcsname{\the\pdflastximage}}%

```

`\usepicture` Inserts graphics with symbolic name #2. This name has to be declared beforehand in `\savepicture{<name>}`. Instead of a name a number can be used too, which directly addresses a graphics in the `\PDFcontainer` file. The optional parameter #1 corresponds to the one in `\includegraphics`.

```

377  \renewcommand*\usepicture[2][]{%
378      \ifundefined{ppf@@#2}{%
379      \%
380          \ppf@isnum{#2}%
381          {\ppf@getpicture{#1}{#2}}%

```

```

382      {\@latex@error{picture '#2' undefined}\@ehc}%
383  }%
384  {%
385      \begingroup
386          \def\Ginclude@graphics##1{%
387              \xdef\ppf@filename{#2}%
388              \setbox\z@\hbox{\pdfrefximage\@nameuse{ppf@@#2}}%
389              \Gin@nat@height\ht\z@ \Gin@nat@width\wd\z@
390              \def\Gin@llx{0} \let\Gin@lly\Gin@llx
391              \Gin@defaultbp\Gin@curx{\Gin@nat@width}%
392              \Gin@defaultbp\Gin@cury{\Gin@nat@height}%
393              \Gin@bboxtrue\Gin@viewport@code
394              \Gin@nat@height\Gin@ury bp%
395              \advance\Gin@nat@height-\Gin@lly bp%
396              \Gin@nat@width\Gin@curx bp%
397              \advance\Gin@nat@width-\Gin@llx bp%
398              \Gin@req@sizes
399              \ht\z@\Gin@req@height \wd\z@\Gin@req@width
400              \leavevmode\box\z@}%
401          \define@key{Gin}{type}{}{%
402              \includegraphics[scale=1,#1]{}%
403          \endgroup
404      }%

```

\ppf@getpicture Inserts the page (graphics) with number #2 from the \PDFcontainer file. Parameter #1: any option as in \includegraphics.

```

405  \newcommand*\ppf@getpicture[2]{%
406      \tempcnta=#2\relax%
407      \ifnum\tempcnta>\ppf@container@max
408          \PackageWarningNoLine{pst-pdf}{%
409              pspicture No. \the\tempcnta space undefined}%
410      \else
411          \includegraphics[draft=\ppf@draft,#1,page=\the\tempcnta]{%
412              \PDFcontainer}%
413      \fi
414      \gdef\ppf@Gin@keys{}%

```

\ppf@@getpicture Inserts next page (graphics) from the \PDFcontainer file.

```

415  \newcommand*\ppf@@getpicture{%
416      \ifpr@outer
417          \refstepcounter{pspicture}%
418          \expandafter\ppf@getpicture\expandafter{\ppf@Gin@keys}%
419          {\the\c@pspicture}%
420      \fi}%

```

pst-pdf-defs Umgebung, die keine eigene Gruppe aufmacht. Innerhalb der Umgebung bekommt das Zeichen & den Kategoriecode "other". Gedacht für eigene Makros, die z. B. eine psmatrix enthalten. (Einen "Hook" verwenden, falls andere Zeichen auch noch benötigt werden!?)

```

421  \renewenvironment*pst-pdf-defs}%
422  {}%
423  \endgroup
424 %    ??? \currenvline

```

```

425      \chardef\ppf@temp=\catcode`\&%
426      \@makeother\&%
427  }{%
428      \catcode`\&=\ppf@temp
429      \begingroup
430      \def\@currenvir{pst-pdf-defs}%
431  }

```

```
432 \else
```

3.5 Inactive Mode

Only the packages `pstricks` and `graphicx` are loaded – no further exertion of influence. The package option “`inactive`” as soon as the VTEXcompiler force this mode.

```

433 \PackageInfo{pst-pdf}{MODE: \ppf@TeX@mode\space (inactive mode)}%
434 \newenvironment{postscript}[1][]{\ignorespaces}{}
435 \let\ppf@is@pdfTeX@graphic\relax
436 \fi
437 \InputIfFileExists{pst-pdf.cfg}{%
438   \PackageInfo{pst-pdf}{Local config file pst-pdf.cfg used}}{}%
439 
```

Change History

v1.0a	General: Initial version.	1	putting a PSTricks graphic in a box or something else. (RN)	13
v1.0b	General: Some code and documen- tation cleaning. (RN)	1	General: Definition of <code>\PDFcontainer</code> now with <code>\edef</code> . (RN)	5
v1.0c	General: New options “ <code>pstricks</code> ”, “ <code>nopstricks</code> ”, “ <code>draft</code> ” and “ <code>final</code> ”. (RN)	3	<code>\usepicture</code> : Now <code>\usepspicture</code> does accept a numerical param- eter. (RN)	13
v1.0d	General: Redefinition of <code>\includegraphics</code> in modes 0 and 1. Now using of eps graph- ics directly in pdfL <small>A</small> T <small>E</small> X is pos- sible. (RN)	1	<code>\postscript</code> : Based no more on the comment environment from the verbatim package. (RN)	12
v1.0e	<code>\postscript</code> : “ <code>trim</code> ” option added. (RN)	6	<code>\ppf@is@pdfTeX@graphic</code> : No more errors for given files without ex- tensions. (RN)	5
v1.0f	General: Config file loading added. (RN)	15	<code>\v1.0j</code>	
	<code>\savepicture</code> : New macro <code>\savepspicture</code> . (RN)	13	General: Check <code>AtBeginDocument</code> for package ‘ <code>pstricks</code> ’ even if “ <code>nopstricks</code> ” is given. (RN)	1
	<code>\usepicture</code> : New macro <code>\usepspicture</code> . Useful for		<code>\Gin@setfile</code> : Show also the pa- ge number if exists. (RN)	10
			<code>\Gin@include@graphics</code> : Prevent divi- sion by zero. (RN)	8

v1.0l	General: Options “framesep”, “framerule”, “linewidth” removed, “fname” and “inner-frame” added. (RN)	1	Supress handling of pdfL ^A T _E X graphic formats in DVI mode. (RN)	6	
v1.0m	General: New package option “notightpage” added. (RN)	1	psmatrix : Support for PStricks environment “psmatrix”. (RN)	12	
v1.0n	General: Changed macro names (<code>\savepicture</code> and <code>\usepicture</code>). (RN)	1	v1.1e	General: New option “display-math” (see preview package). (HjG/RN)	3
	Some code cleaning. (RN)	1	v1.1f	General: Package option “ignore” reimplemented. Now the compilation of the dtx file in L ^A T _E X mode is possible. (RN)	3
v1.0o	General: New code for “notight-page”. (RN)	6	v1.1g	psmatrix : “psmatrix” environment (preserve math mode). (RN/HjG)	12
	Option “fname” renamed to “showname”. (RN)	1	pspicture : pspicture environment must still parse its arguments. (RN/HjG)	12	
v1.0p	General: Some code and documentation cleaning. (RN)	1	v1.1h	\Ginclusion@graphics : Check if inside of a PS-related environment (correct graphic inclusion). (RN)	8
v1.0q	\usepspicture : Now <code>\usepspicture</code> works for all kind of graphics. (RN)	13	v1.1i	General: <code>\ifpr@outer</code> must be pre-defined. (HjG/RN)	5
v1.0r	\ppf@is@pdfTeX@graphic : Changed <code>\ppf@is@known@graphic</code> to <code>\ppf@is@pdfTeX@graphic</code> . Now pdfL ^A T _E X graphics are preferred. (RN)	5		Package option “final” also for “graphicx”. (RN)	4
v1.0s	General: Scaling e.g. of PostScript pictures now only in extraction mode. Some code cleaning. (RN)	1	\Ginclusion@graphics : Correction of the inside check. (RN/HjG)	8	
	\Gin@ii : Rewritten. (RN)	11	v1.1k	General: New environment <code>pst-pdf-defs</code> : Support for PStricks environment “psmatrix” inside user definitions. (RN,HjG)	1
v1.1a	General: Support for the internal PStricks macro <code>\pst@object</code> . (HjG/RN)	8	v1.1l	General: Support for the package “psfragx”. (RN)	8
v1.1b	General: Ignore the call of <code>\nofiles</code> inside of <code>preview</code> . (RN)	9	v1.1m	General: Merge english and german version of the documentation. (RN)	1
	Some code and documentation cleaning. (RN)	1	v1.1n	General: <code>\nofiles</code> added (suggestion of Torsten Bronger).	6
v1.1c	General: New package option “tight-page” added. (RN)	1			
	Special support for “tabularx”. (RN)	8			

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\&	347, 359, 425, 426, 428	environments:postscript postscript 2
\@currenvir	52, 343, 430	environments:pspicture pspicture 2
\@currenvline 49, 424	
\@ehc 382	environments:pst-pdf- defs
\@firstofone 205	pst-pdf-defs 3
\@latex@error 382	\everydisplay 203
\@makeother	347, 359, 426	
\@ppf@PST@usedfalse	10	F
\@ppf@PST@usedtrue	4, 9	\filename@base 317, 318
\@ppf@pdftex@graphicfalse 65	\filename@parse 310
\@ppf@pdftex@graphictrue 71	\frame 238
\@ppf@tightpagefalse	16	
\@ppf@tightpagetrue 5, 17	G
A		\Gin@bboxtrue 393
\AtBeginDvi 183, 184	\Gin@boolkey 232, 234, 236, 247
C		\Gin@defaultbp 391, 392
\c@lor@to@ps 181	\Gin@extensions 56, 72, 89, 165, 228, 266
\c@pspicture	274, 294, 295, 298, 309, 419	\Gin@framefalse 59
\catcode 425, 428	\Gin@ignorefalse 62
\CurrentOption	12, 15, 19	\Gin@ii 57, 261, 348, 360
D		\Gin@innerframefalse 60
\DeclareGraphicsRule 95, 230	\Gin@llx 390, 397
\define@key 96–100, 231, 233, 235, 237, 246, 248, 401	\Gin@lly 390, 395
E		\Gin@nat@height 389, 392, 394, 395
\endpostscript	365, 368	\Gin@nat@width 389, 391, 396, 397
\endpsmatrix 143, 147, 368	\Gin@PS@file@header 177
\endpspicture 362, 365	\Gin@PS@literal@header 177
\endtabular 159	\Gin@PS@raw 178
\endtabularx 159	\Gin@PS@restored 178
environments:		\Gin@req@height 399
postscript 107, 327	\Gin@req@sizes 398
psmatrix 125, 327	\Gin@req@width 399
pspicture 124, 327	\Gin@setfile 68, 257, 258
pst-pdf-defs 46, 421	\Gin@shownamefalse 61
		\Gin@urx 391, 396
		\Gin@ury 392, 394
		\Gin@viewport@code 393
		\Gin@vllx 114
		\Gin@vly 114
		\Gin@vurx 114
		\Gin@vury 114
I		
\if@ppf@pdftex@graphic 58, 75	
\if@ppf@PST@used 4, 81, 182	
\if@ppf@tightpage 5, 101, 110	
\ifGin@frame 59, 242	
\ifGin@ignore 62, 277	
\ifGin@innerframe 60, 240	
\ifGin@showname 61, 281	
\ifinner 131, 330	
\ifmmode 130, 329	
\ifpr@outer 63, 164, 199, 416	
\includegraphics 2, 371, 402, 411	
\includegraphicx 3	
J		
\jobname 41, 316, 317	
L		
\leavevmode 400	
\long 198	
N		
\newcolumntype 158	
\nofiles 80, 193, 195	
O		
\output 192, 196	
P		
\paperheight 103	
\paperwidth 103	
\PassOptionsToPackage 12, 15, 19	
\PDFcontainer 40, 41, 268, 274, 289, 291, 297, 299, 310, 312, 412	
\pdflastximage 376	

```

\pdflastximagepages 292
\pdfliteral ..... 173
\pdfoutput ..... 26
\pdfrefximage ..... 388
\pdfTeXext ..... 67, 70
\pdftexversion ..... 88
\pdfximage ..... 291
\pfx@includegraphics ..... 371
\pfx@includegraphicx ..... 161, 372
\postscript ... 364, 368
postscript (environment) . 2, 107, 327
\ppf@getpicture 212, 351, 362, 372, 415
\ppf@container@max ..... 291, 295, 297, 307, 407
\ppf@draft 3, 13, 14, 411
\ppf@endpsmatrix ..... 143, 147
\ppf@filename . 254, 259, 283, 284, 387
\ppf@getpicture ... 381, 405, 418
\ppf@Gin@extensions 56
\ppf@Gin@ii ..... 57, 278
\ppf@Gin@keys . 256, 342, 343, 414, 418
\ppf@Gin@setfile ..... 257, 258
\ppf@Gin@include@graphics ..... 55, 73, 167, 169, 172
\ppf@is@pdfTeX@graphic . 64, 165, 266, 435
\ppf@isnum ... 324, 380
\ppf@namefont ..... 250, 251, 255, 282
\ppf@nofiles .. 193, 195
\ppf@other@extensions ..... 43, 89, 93, 165, 228, 266
\ppf@pr@psmatrix .. ..... 141, 146
\ppf@PreviewBbAdjust ..... 83, 85, 109
\ppf@psmatrix . 140, 144
\ppf@RestoreBbAdjust ..... 84, 119
\ppf@set@mode ..... 128, 132, 134, 137, 146, 147, 327, 331, 333, 336, 349, 351
\ppf@temp ..... 183, 184, 425, 428
\ppf@temptoken ..... 191, 192, 196, 197
\ppf@test@mmode ... 129, 144, 328, 341
\ppf@TeX@mode . 2, 6– 8, 21, 22, 33, 35, 37, 77, 79, 175, 433
\pr@cleanup ... 201, 213
\pr@endbox ..... 209
\pr@outerfalse ..... 73, 204, 346, 358
\pr@shipout ..... 195
\pr@startbox ..... 198
\PreviewBbAdjust .. . 85, 102, 109, 113
\PreviewEnvironment ..... 120, 124, 127, 356
\PreviewMacro ..... 149, 161, 172, 217
\psmatrix .... 140, 142, 144, 145, 368
psmatrix (environment) ... 125, 327
\pspicture ..... 357
pspicture (environment) . 2, 124, 327
pst-pdf-defs (environment) .. 3, 46, 421
\pst@picture ..... 364
\pst@object ..... 155, 223, 344, 345
\PSTricksOff ..... 180

```

R

```

\raisebox ..... 283
\refstepcounter 273, 417
\rule ..... 166

```

S

```

\savepicture . 3, 45, 375
\setkeys ..... 112, 263
\shipout ..... 195
\string ... 142, 145, 345
\strutbox ..... 283

```

T

```

\tabular ..... 157
\tabularx ..... 157

```

U

```

\usepicture ... 3, 44, 377

```

V

```

\voidb@x ..... 211

```