

PSTricks - 2008
new macros and bugfixes for the basic packages
pstricks, pst-plot, pst-tree,
and pst-node

Herbert Voß*

May 25, 2008

*Herbert.Voss@pstricks.de;
thanks to Patrick Drechsler.

Contents

I pstricks – package	4
1 pstricks.sty	4
1.1 Error messages	4
1.2 Optional arguments	4
2 pstricks.tex (1.24– 2008/04/23)	5
2.1 Option <i>shift</i>	5
2.2 Option <i>gridfont</i>	5
2.3 <i>linejoin</i>	6
2.4 <i>linecap</i>	7
2.5 New arrowtype <i>D></i> and <i>D>D></i>	8
2.6 Transparent colors	9
2.6.1 Options <i>strokeopacity</i> and <i>opacity</i>	9
2.6.2 Fill style <i>shape</i>	11
2.7 \addtopsstyle	13
2.8 \pscircleOA	14
2.9 \psTextFrame	14
2.10 Special coordinates	16
2.11 Octogon-Symbol	16
2.12 Code changes	17
3 The PostScript header files	17
3.1 pstricks.pro	17
3.2 pst-dots.pro	17
II pst-node – package	19
4 pst-node.tex (1.00– 2007/10/16)	19
4.1 Bugfix for <i>psmatrix</i>	19
4.2 New option <i>pcRef</i>	19
III pst-plot – package	22
5 pst-plot.tex (1.01– 2008/01/26)	22
5.1 New options <i>LineToXAxis</i> and <i>LineToYAxis</i>	22

IV pst-tree – package **24**

6 pst-tree.tex (1.01– 2007/06/26) **24**

Part I

pstricks – package

1 pstricks.sty

1.1 Error messages

- Loading the package `pstricks` by L^AT_EX will now write a message into the file list of file version and date for the file `pstricks.pro`.
- A frequently done error is choosing a file name for the document, which is already a name of one PStricks package, e.g. `pstricks.tex`. The error message in the log file was not really helpful. There is now an extended message (example for a document file called `pstricks.tex`):

```
! LaTeX Error: 'pstricks.tex' is a forbidden name for your document,  
it is already a name of a package.
```

See the LaTeX manual or LaTeX Companion for explanation.

Type H <return> for immediate help.

...

```
1.13 \documentclass  
          {article}  
? H  
Choose another name for your document
```


1.2 Optional arguments

`pstricks` supports transparent colors with Ghostscript's `.setopacityalpha`, `.setblendmode`, and `.setshapealpha`. These functions are not known to VTeX or Adobes Distiller. The optional argument `vtex` disables transparencies and `distiller` overrides the Ghostscript functions with the ones from the Distiller.

2 pstricks.tex (1.24– 2008/04/23)

2.1 Option shift

The optional argument `shift` can be used for a vertical alignment of the `pspicture` box. With `shift=*`, instead of a value or a length it is possible to center the `pspicture` box vertically to the baseline of the current line.




```
1 \usepackage{pstricks}
2 \rule{5mm}{0.5pt}%
3 \psframebox{%
4 \begin{pspicture}[showgrid=true,
5     shift=*(-0.3,-0.4)(3.2,3.3)
6     \psarc[showpoints=true](1,1)
7     {2}{-45}{120}
8 \end{pspicture}}\rule{5mm}{0.5pt}
```

2.2 Option gridfont

By default the grid labels were printed always in Helvetica. With the new keyword `gridfont` one can define another PostScript Font. Available are at least


Helvetica (default) - Helvetica-Narrow - Times-Roman - Courier - AvantGard -NewCenturySchlbk - Palatino-Roman - Bookman-Demi - ZapfDingbats - Symbol



```
1 \usepackage{pstricks}
2 \begin{pspicture}[showgrid=true](3,2)
3 \end{pspicture}\rule[20pt]{0pt}{0pt}
4 \begin{pspicture}(3,2)
5 \psgrid[style=gridstyle,gridfont=
6 AvantGard-Demi]
7 \end{pspicture}\rule[20pt]{0pt}{0pt}
8 \begin{pspicture}(3,2)
9 \psgrid[style=gridstyle,gridfont=
10 ZapfDingbats]
11 \end{pspicture}
```

2.3 linejoin

Connecting lines can be done in several ways and is controlled on PS level by the `setlinejoin` command. With this version of PSTricks it is possible to control this by an optional argument, called `linejoin`. It is preset to 0 and can take values of 0,1,2. Other values will have no effect.



```
1 \psset{linewidth=3mm,unit=0.8}
2 \begin{pspicture} [showgrid=true] (3,2)
3   \psline(0,0)(1,2)(2,0)(3,2)
4 \end{pspicture}\[10pt]
5 \begin{pspicture} [showgrid=true] (4,2)
6   \psline[linejoin=1](0,0)(1,2)(2,0)(3,2)
7     (4,0)%
8 \end{pspicture}\[10pt]
9 \begin{pspicture} [showgrid=true] (3,2)
10  \psline[linejoin=2](0,0)(1,2)(2,0)(3,2)%
11 \end{pspicture}
```

2.4 linecap


The value of `linecap` determines how the line ends are drawn:

0 lines are cut (default)

1 lines are ended by a filled semicircle of radius $0.5 \cdot \text{\pslinewidth}$

2 lines are ended by a filled half square of radius $0.5 \cdot \text{\pslinewidth}$

The following example shows that using `linecap` for lines is the same than using the arrow option.




```

1 \begin{pspicture} [showgrid=true] (4,4)%
2 \psset{linewidth=5mm}
3 \psline[arrows=C-C](0,3.75)(4,3.75)
4 \psline[linecap=2](0,3)(4,3)
5 \psline[arrows=c-c](0,2.25)(4,2.25)
6 \psline[linecap=1](0,1.5)(4,1.5)
7 \psline[arrows=-](0,0.75)(4,0.75)
8 \psline(4,0)
9 \end{pspicture}

```

Using this optional argument makes only sense in some special cases, because it is the same as the arrow type `c-c`. But the arrows are not part of the current path and filling an open curve with the `linecap` option is different to a curve using the `c-c` arrow.




```

1 \psset{unit=5cm,linewidth=5mm}
2 \begin{pspicture}(-0.2,-0.6)(0.2,0.5)%
3 \def\curve{\pscurve(-.1,.1)(-.15,.15)(0,.2)(.15,.15)(.1,.1)}
4 \rput(0,.2){\psset{arrows=c-c}\curve}
5 \rput(0,-.2){%
6   \psset{fillstyle=solid,fillcolor=red,arrows=c-c}
7   \curve}
8 \rput(0,-.6){%
9   \psset{fillstyle=solid,fillcolor=red,linecap=1}
10 \curve}
11 \end{pspicture}

```

2.5 New arrowtype D> and D>D>

All arrows are drawn as polygons. The new arrow type D> or <D for the other way round, draws its lines as bezier curves, which looks nicer for big arrows.



```
1 \psset{arrowscale=5}
2 \begin{pspicture}(4,2)
3 \psline{<D<D-D>D>}(0,2)(4,2)
4 \psline[arrows=<-D>,arrowlength=2](0,1)(4,1)
5 \psline[arrowinset=0]{<D-D>}(0,0.25)(4,0.25)
6 \end{pspicture}
```


2.6 Transparent colors

The package `pstricks-add` already defined a fillstyle for transparency colors by using the Ghostscript's blendmode. It now moves into the main `pstricks` package, together with another possibility for creating transparent colors. Transparency is only seen with the PDF output (version 1.4 or greater), as nearly all PostScript viewer cannot show transparencies.

Loading the `pstricks` package with the option `vtex`, disables the transparency effects and everything works as before.


2.6.1 Options `strokeopacity` and `opacity`

For the existing fill style `solid` the new option `opacity` can be used to get also transparent colors. It is predefined by 1 (0...1), which is the old behaviour, no transparency. The option is valid only for PostScript's fill commands. Lines and curves can be transparent with setting the option `strokeopacity`, which can have a different value than the `opacity` option.




```
1 \begin{pspicture}[linewidth=1cm] (4,4)
2   \psline[linecolor=red](0,0)(4,4)
3   \psline[linecolor=blue,strokeopacity=0.5](0,4)(4,0)
4   \psline[linecolor=green,strokeopacity=0.5](0,3.5)
5     (4,3.5)
6   \psline[linecolor=yellow,strokeopacity=0.5](0,0.5)
7     (4,0.5)
8 \end{pspicture}
```


```
1 \begin{pspicture}[linewidth=1cm] (4,4)
2   \psline[linecolor=red](0,0)(4,4)
3   \pscircle*[opacity=0.5](2,2){2}
4   \psline[linecolor=blue,strokeopacity=0.6](0,4)(4,0)
5 \end{pspicture}
```



```
1 \begin{pspicture} [linewidth=3mm] (4,5.5)
2   \multido{\rA=0.0+0.5}{9}{%
3     \psline [linecolor=red!40] (\rA,0)(\rA,5)}
4   \multido{\rA=0.0+0.5,\rB=0.0+0.1}{11}{%
5     \psline [arrows=<D-D>,linecolor=blue,
6       linewidth=5pt,arrowscale=1.5,
7       strokeopacity=\rB] (0,\rA)(4,\rA)}
8 \end{pspicture}
```



```
1 \begin{pspicture}(5,5)
2   \psset{fillstyle=solid}
3   \psframe[fillcolor=red](0,1)(3,4)
4   \psframe[fillcolor=blue,opacity=0.7](2,2)(5,5)
5   \psframe[fillcolor=green,opacity=0.7](1,0)(4,3)
6   \pscircle[fillcolor=cyan,
7     opacity=0.5](1.5,3.5){1.25}
8 \end{pspicture}
```




```
1 \begin{pspicture}(5,5)
2   \psset{fillstyle=solid}
3   \psframe[fillcolor=red](0,1)(3,4)
4   \psframe[fillcolor=blue,opacity=0.3](2,2)(5,5)
5   \psframe[fillcolor=green,opacity=0.3](1,0)(4,3)
6   \pscircle[fillcolor=cyan,
7     opacity=0.5](1.5,3.5){1.25}
8 \end{pspicture}
```

2.6.2 Fill style shape

There is now one more fill style for transparent colors: `shape` with using the `shapealpha` value and one of the possible blendmodes:

```
/Normal      ->0
/Compatible  ->1
/Screen      ->2
/Multiply   ->3
```

The fill style `solid` uses Ghostscript's `.setopacityalpha` function and the new style `shape` and the `blendmode` together with `.setshapealpha`. `shapealpha` is predefined with 0.6 and both alpha values can be chosen from the range $0 \leq \alpha \leq 1$.



```

1 \begin{pspicture}(5,5)% default blendmode
2   \psframe*[linecolor=red](0,1)(3,4)
3   \psframe[fillcolor=blue,fillstyle=shape](2,2)(5,5)
4   \psframe[fillcolor=green,fillstyle=shape](1,0)(4,3)
5   \pscircle[fillcolor=cyan,fillstyle=shape,
6     shapealpha=0.3](1.5,3.5){1.25}
7   \rput(1.5,3.5){\huge\textrm{\bf 0}}
```

```


8 \end{pspicture}
9 \hfill
10 \begin{pspicture}(5,5)
11 \psset{blendmode=1}% type /Compatible
12 \psframe*[linecolor=red](0,1)(3,4)
13 \psframe[fillcolor=blue,fillstyle=shape](2,2)(5,5)
14 \psframe[fillcolor=green,fillstyle=shape](1,0)(4,3)
15 \pscircle[fillcolor=cyan,fillstyle=shape,
16 shapealpha=0.3](1.5,3.5){1.25}
17 \rput(1.5,3.5){\huge\textrm{1}}
18 \end{pspicture}
19
20 \begin{pspicture}(5,5)
21 \psset{blendmode=2}% type /Screen
22 \psframe*[linecolor=red](0,1)(3,4)
23 \psframe[fillcolor=blue,fillstyle=shape](2,2)(5,5)
24 \psframe[fillcolor=green,fillstyle=shape](1,0)(4,3)
25 \pscircle[fillcolor=cyan,fillstyle=shape,
26 shapealpha=0.3](1.5,3.5){1.25}
27 \rput(1.5,3.5){\huge\textrm{2}}
28 \end{pspicture}
29 \hfill
30 \begin{pspicture}(5,5)
31 \psset{blendmode=3}% type /Multiply
32 \psframe*[linecolor=red](0,1)(3,4)
33 \psframe[fillcolor=blue,fillstyle=shape](2,2)(5,5)
34 \psframe[fillcolor=green,fillstyle=shape](1,0)(4,3)
35 \pscircle[fillcolor=cyan,fillstyle=shape,
36 shapealpha=0.3](1.5,3.5){1.25}
37 \rput(1.5,3.5){\huge\textrm{3}}
38 \end{pspicture}

```

2.7 \addtopsstyle

```
\addtopsstyle{style-name}{settings}
```

This macro allows to add some more settings to an existing style. If the style is not defined, then `\addtopsstyle` behaves like the already defined `\newpsstyle` macro.




```
1 \newpsstyle{Fiber}{linewidth=2pt}
2 \begin{pspicture}(5,5)
3   \psline[style=Fiber](0,0)(5,1)
4   \addtopsstyle{Fiber}{linecolor=green}
5   \psline[style=Fiber](0,1)(5,2)
6   \addtopsstyle{Fiber}{linestyle=dotted}
7   \psline[style=Fiber](0,2)(5,3)
8   \addtopsstyle{Fiber}{}
9   \psline[style=Fiber](0,3)(5,4)
10  \addtopsstyle{Fiber}{linecolor=red}
11  \psline[style=Fiber](0,4)(5,5)
12 \end{pspicture}
```

2.8 \pscircleOA

```
\pscircleOA[settings](x0,y0)(xA,yA)
```

(x_0, y_0) is the center and (x_A, y_A) a given point of the circle. The radius is calculated by TeX.




```
1 \begin{pspicture} [showgrid=true] (-2,0)(8,8)
2 \pscircleOA(6,4)(4,4)
3 \pscircleOA[linecolor=blue](4,6)(4,4)
4 \pscircleOA[linewidth=2pt,linecolor=yellow](3,5)(4,4)
5 \pscircleOA*[opacity=0.3,linecolor=red](2,2)(4,4)
6 \end{pspicture}
```

2.9 \psTextFrame

```
\psTextFrame[settings](x1,y1)(x2,y2){Text}
```

The *Text* cannot have a linebreak. In case it is needed, put the *Text* into a `minipage` or `parbox`, as seen in the following example. The `ref`-option allows different placing and the `rot`-option allows the rotating of the *Text*. The macro itself first uses the `\psframe` and the `\rput` macro with calculated coordinates.




```

1 \begin{pspicture}[showgrid=true](0,-0.5)(10,10)
2 \psTextFrame[linecolor=lightgray,ref=l](0,0.5)(4,1.5){Hallo}
3 \psTextFrame[linecolor=blue](2,4)(4,7){\color{blue}Hallo}
4 \psTextFrame[linestyle=dashed](9,9)(10,10){\huge H}
5 \psTextFrame*[linecolor=red,linestyle=dashed](7,7)(9,9){\Huge H}
6 \psTextFrame*[linecolor=red!40,ref=LB](7,4)(9,6){\Huge H}
7 \psTextFrame*[linecolor=blue!40,ref=rt](7,1)(9,3){\Huge H}
8 \psTextFrame[linestyle=dashed](4.5,0)(6.5,10){%
9   \parbox{2cm}{\centering Here comes some more text over several
10   lines, which is also horizontally and vertically centered and
11   written in a parbox.}}
12 \psTextFrame*[linecolor=cyan!20,rot=90](.5,2)(1.5,10){%
13   \parbox{8cm}{\centering Here comes some more text over several
14   lines and rotated by 90 degrees.}}
15 \end{pspicture}

```

2.10 Special coordinates

Additionally to the existing `!`-operator for PostScript coordinates, there is now a `*`-operator, which invokes the algebraic parser before the coordinates are passed to the default `!`-operator. The syntax is pretty easy: (`<value> {f(x)}`). In the following example the predefined value of Pi from `pstricks.pro` is used. The x value and the function must be enclosed in braces when they contain spaces, round braces or symbolic names, like `Pi` for the x value.




```

1 \SpecialCoor
2 \begin{pspicture}(0,-1)(5,1)
3   \psaxes{->}(0,0)(0,-1)(5,1)
4   \psline(0,0)(*\Pi\sqrt{abs(cos(x)))})
5   \psline{<->}(*\Pi\cos(x))(*5\sin(x)*cos(x))
6 \end{pspicture}

```

For a macro definition of the algebraic function the `\string` command has to be used, otherwise TeX expects the math mode in the following example.



```

1 \def\F{\string x^2 }
2 \begin{pspicture}[showgrid=true](2,4)
3   \psline[linecolor=red](*1 {\F} )(*2 {\F} )
4 \end{pspicture}

```


2.11 Octagon-Symbol

An octagon symbol was added.

```

\newpsfontdotH{Octogon}[1 0 0 1 0 0]{PSTricksDotFont}{(f)}{(g)}
\newpsfontdotH{BoldOctogon}[1 0 0 1 0 0]{PSTricksDotFont}{(F)}{(g)}
\newpsfontdot{SolidOctogon}[1 0 0 1 0 0]{PSTricksDotFont}{(g)}

```



```

1 \psset{dotscale=4}
2 \begin{pspicture} [showgrid=true] (4,4)
3 \psdot [dotstyle=Octogon] (1,1)
4 \psdot [dotstyle=BoldOctogon] (2,2)
5 \psdot [dotstyle=SolidOctogon] (3,3)
6 \end{pspicture}
```

2.12 Code changes

```
% hv 2007-10-16 to fix the bug in pst-node with \\[name=...]
\def\ps@ifnextchar#1#2#3{%
  \let\reserved@d= #1%
  \def\reserved@a{#2}\def\reserved@b{#3}%
  \futurelet\@let@token\ps@ifnch}
\def\ps@ifnch{%
  \ifx\@let@token\reserved@d \let\reserved@b\reserved@a \fi
  \reserved@b
}
```

3 The PostScript header files

3.1 pstricks.pro

```
/Pyth2 { % Pythagoras, xA yA xB yB
  3 -1 roll % xA xB yB yA
  sub % xA xB yB-yA
  3 1 roll % yB-yA xA xB
  sub % yB-yA xA-xB
  Pyth } def
```

This new PostScript function allows to calculate the distance between two points, given by their coordinates whereas the existing /Pyth does this for two values.

3.2 pst-dots.pro

`pst-dots.pro` ist the file which defines the so called softfont PSTRocksFont-Dot, which collects all PSTricks symbols, which are not part of one of the standard PostScript fonts. The octagon symbol is defined as:

```
/OctogonPath {  
    228 550 moveto 7 { -456 0 rlineto 45 rotate } repeat closepath  
} def  
/SolidOctogon { OctogonPath fill } def  
/Octogon { OctogonPath .89 .89 scale OctogonPath eofill } def  
/BoldOctogon { OctogonPath .79 .79 scale OctogonPath eofill } def  
%
```


Part II

pst-node – package

4 `pst-node.tex` (1.00– 2007/10/16)

4.1 Bugfix for `psmatrix`

A long standing bug with `psmatrix` and using the `name` option is now fixed. The following works as expected:



```


1 \begin{psmatrix} [rowsep=5mm]
2 [name=a]a\\
3 [name=b]b\\[1cm]
4 [name=c]c\\
5 \end{psmatrix}
6 \ncline{a}{b}
7 \ncarc{a}{c}
```

An optional argument after `\\\` is now scanned in the correct way.


4.2 New option `pcRef`

There is a new option `pcRef` for the `\ncangles` connection. By default, the reference point for the `armA` option is the border of the node. This makes it difficult to get horizontally aligned lines for different node images. With `pcRef=true` the node center is the reference point and the connection is still drawn from the border of the node.

The first three images show the default behaviour:



The next three images display the influence of `pcRef=true`; the horizontal line for the three examples is on the same height:



```

1 \begin{pspicture}(5,4)
2   \cnode(2.5,3.5){0.2}{A}
3   \cnode(0.5,1){0.2}{B1}
4   \cnode(1.5,1){0.4}{B2}
5   \cnode(2.6,1){0.6}{B3}
6   \cnode(4,1){0.8}{B4}
7   \psset{angleB=90,angleA=-90,armA=1cm}
8   \ncangles[pcRef=true]{A}{B1}
9   \ncangles[pcRef=true]{A}{B2}
10  \ncangles[pcRef=true]{A}{B3}
11  \ncangles[pcRef=true]{A}{B4}
12 \end{pspicture}
13 %
14 \begin{pspicture}(5,4)
15   \cnode(2.5,3.5){0.4}{A}
16   \cnode(0.5,1){0.2}{B1}
17   \cnode(1.5,1){0.4}{B2}
18   \cnode(2.6,1){0.6}{B3}
19   \cnode(4,1){0.8}{B4}
20   \psset{angleB=90,angleA=-90,armA=1cm}
21   \ncangles[pcRef=true]{A}{B1}
22   \ncangles[pcRef=true]{A}{B2}
23   \ncangles[pcRef=true]{A}{B3}
24   \ncangles[pcRef=true]{A}{B4}
25 \end{pspicture}
26 %
27 \begin{pspicture}(5,4)
28   \cnode(2.5,3.5){0.8}{A}
29   \cnode(0.5,1){0.2}{B1}
30   \cnode(1.5,1){0.4}{B2}
31   \cnode(2.6,1){0.6}{B3}
32   \cnode(4,1){0.8}{B4}
33   \psset{angleB=90,angleA=-90,armA=1cm}
34   \ncangles[pcRef=true]{A}{B1}
35   \ncangles[pcRef=true]{A}{B2}

```


```
36 |     \ncangles[pcRef=true]{A}{B3}
37 |     \ncangles[pcRef=true]{A}{B4}
38 | \end{pspicture}
```

Part III


pst-plot – package

5 `pst-plot.tex` (1.01– 2008/01/26)

5.1 New options `LineToXAxis` and `LineToYAxis`



```
1 \psset{xunit=0.0333cm,yunit=2.5cm}
2 \begin{pspicture}(0,-1)(400,1)
3   \psline[->](0,0)(400,0)
4   \psline[->](0,-1)(0,1)
5   \psplot[plotstyle=LineToXAxis,linestyle=dashed,plotpoints=50,
6         linecolor=red!40,
7         showpoints=true,dotstyle=o,dotsize=0.2]{0}{360}{x sin}
8 \end{pspicture}
```



```
1 \psset{xunit=0.0333cm,yunit=2.5cm}
2 \begin{pspicture}(0,-1.2)(400,1.4)
3   \psline{->}(0,0)(390,0)
4   \psline{->}(0,-1.1)(0,1.2)
5   \psplot[plotstyle=LineToYAxis,linestyle=dashed,plotpoints=50,
6         linecolor=blue!40,
7         showpoints=true]{0}{360}{x cos}
8 \end{pspicture}
```

Part IV

pst-tree – package

6 `pst-tree.tex` (1.01– 2007/06/26)

There was a bug with `style=...` due to a missing `\use@par` in `\pstree@ii`.

References

- [1] Michel Goosens, Frank Mittelbach, Sebastian Rahtz, Denis Roegel, and Herbert Voß. *The L^AT_EX Graphics Companion*. Addison-Wesley Publishing Company, Reading, Mass., 2007.
- [2] Laura E. Jackson and Herbert Voß. Die Plot-Funktionen von `pst-plot`. *Die T_EXnische Komödie*, 2/02:27–34, June 2002.
- [3] Nikolai G. Kollock. *PostScript richtig eingesetzt: vom Konzept zum praktischen Einsatz*. IWT, Vaterstetten, 1989.
- [4] Manuel Luque. *Vue en 3D*. <http://members.aol.com/Mluque5130/vue3d16112002.zip>, 2002.
- [5] Herbert Voß. Die mathematischen Funktionen von Postscript. *Die T_EXnische Komödie*, 1/02:40–47, March 2002.
- [6] Herbert Voss. *PSTricks Support for pdf*. <http://PSTricks.de/pdf/pdfoutput.phtml>, 2002.
- [7] Herbert Voß. *L^AT_EX Referenz*. DANTE – Lehmanns, Heidelberg/Hamburg, 1. edition, 2007.
- [8] Herbert Voß. *PSTricks – Grafik für T_EX und L^AT_EX*. DANTE – Lehmanns, Heidelberg/Hamburg, 4. edition, 2007.
- [9] Michael Wiedmann and Peter Karp. *References for T_EX and Friends*. <http://www.miwie.org/tex-refs/>, 2003.
- [10] Timothy Van Zandt. *PSTricks - PostScript macros for Generic TeX*. <http://www.tug.org/application/PSTricks>, 1993.

Index

π , 16
*, 5
*-operator, 16
.setblendmode, 4
.setopacityalpha, 4, 11
.setshapealpha, 4, 11
/Pyth, 17
 $\langle D$, 8
 $\rangle\!\!,$ 19
`\addtopsstyle`, 13
algebraic parser, 16
`armA`, 19
arrow, 7
arrow type, 7
`AvantGard`, 5
blendmode, 9
`blendmode`, 11
Bookman-Demi, 5
`c-c`, 7
calculated coordinates, 14
`Courier`, 5
current path, 7
`D>`, 8
Dimension
 `\pslinewidth`, 7
Distiller, 4
`distiller`, 4
Environment
 `minipage`, 14
 `psmatrix`, 19
 `pspicture`, 5
 error message, 4
File
 `pstricks.pro`, 4, 16
 `pstricks.tex`, 4
fill style, 11
filling, 7
Ghostscript, 4, 9, 11
grid label, 5
`gridfont`, 5
Helvetica, 5
Helvetica, 5
Helvetica-Narrow, 5
Keyword
 `armA`, 19
 `blendmode`, 11
 `gridfont`, 5
 `linecap`, 7
 `linejoin`, 6
 `name`, 19
 `opacity`, 9
 `pcRef`, 19
 `ref`, 14
 `rot`, 14
 `shape`, 11
 `shapealpha`, 11
 `shift`, 5
 `strokeopacity`, 9
 `linecap`, 7
 `linejoin`, 6
Macro
 $\rangle\!\!$, 19
 `\addtopsstyle`, 13
 `\ncangles`, 19
 `\newpsstyle`, 13
 `\parbox`, 14

```

\psframe, 14
\pstree@ii, 24
\rput, 14
\use@par, 24
minipage, 14
name, 19
\ncangles, 19
NewCenturySchlbk, 5
\newpsstyle, 13
node connection, 19
opacity, 9
open curve, 7
Package
  pstricks, 4, 9
  pstricks-add, 9
Package option
  distiller, 4
  vtex, 4, 9
Palatino-Roman, 5
\parbox, 14
pcRef, 19
PDF, 9
PostScript, 16
  .setblendmode, 4
  .setopacityalpha, 4, 11
  .setshapealpha, 4, 11
  /Pyth, 17
  setlinejoin, 6
PostScript Font, 5
\psframe, 14
\pslinewidth, 7
psmatrix, 19
pspicture, 5
\pstree@ii, 24
pstricks, 4, 9
pstricks-add, 9
pstricks.pro, 4, 16
pstricks.tex, 4
ref, 14
rot, 14
rotating, 14
\rput, 14
setlinejoin, 6
shape, 11
shapealpha, 11
shift, 5
solid, 9, 11
strokeopacity, 9
style, 13
Symbol, 5
Times-Roman, 5
transparent colors, 4, 11
transparent lines, 9
transpareny, 9
\use@par, 24
Value
  *, 5
  <D, 8
  AvantGard, 5
  Bookman-Demi, 5
  c-c, 7
  Courier, 5
  D>, 8
  Helvetica, 5
  Helvetica-Narrow, 5
  NewCenturySchlbk, 5
  Palatino-Roman, 5
  shape, 11
  solid, 9, 11
  Symbol, 5
  Times-Roman, 5
  ZapfDingbats, 5
m , 4
vtex, 4, 9
ZapfDingbats, 5

```