

xstring

v1.82

User's manual

Christian TELLECHEA
unbonpetit@netc.fr

1 February 2019

Abstract

This package which requires ε -TeX, provides macros manipulating strings of tokens. For a basic use, tokens can be alphanumeric chars, but the macros can also be useful for manipulating tokens, i.e. TeX code. Main features are:

- ▷ tests:
 - does a string contains at least n times an another?
 - does a string starts (or ends) with another? etc.
 - is a string an integer? A decimal?
 - are 2 strings equal?
- ▷ extractions of substrings:
 - what is on the left (or the right) of the n^{th} occurrence of a substring;
 - what is between the occurrences of 2 substrings;
 - substring between 2 positions;
 - serach of a group with its identifier.
- ▷ substitution of all, or the n first occurrences of a substring for an other substring;
- ▷ calculation of numbers:
 - length of a string;
 - position of the n^{th} occurrence of a substring;
 - how many times a string contains a substring?
 - comparison of 2 strings: position of the first difference;
 - identifier of the group in which a macro made a cut or a search.

Other macros allow to use special characters forbidden in arguments (# and %) and manage differences between catcodes for advanced programming purposes.

Contents

1	Presentation	2
1.1	Description	2
1.2	Motivation	2
2	The macros	2
2.1	The tests	3
2.1.1	<code>\IfSubStr</code>	3
2.1.2	<code>\IfSubStrBefore</code>	3
2.1.3	<code>\IfSubStrBehind</code>	3
2.1.4	<code>\IfBeginWith</code>	4
2.1.5	<code>\IfEndWith</code>	4
2.1.6	<code>\IfInteger</code>	4
2.1.7	<code>\IfDecimal</code>	4
2.1.8	<code>\IfStrEq</code>	5
2.1.9	<code>\IfEq</code>	5
2.1.10	<code>\IfStrEqCase</code>	5
2.1.11	<code>\IfEqCase</code>	6
2.2	Extraction of substrings	6
2.2.1	<code>\StrBefore</code>	6
2.2.2	<code>\StrBehind</code>	6
2.2.3	<code>\StrCut</code>	7
2.2.4	<code>\StrBetween</code>	7
2.2.5	<code>\StrSubstitute</code>	8
2.2.6	<code>\StrDel</code>	8
2.2.7	<code>\StrGobbleLeft</code>	8
2.2.8	<code>\StrLeft</code>	9
2.2.9	<code>\StrGobbleRight</code>	9
2.2.10	<code>\StrRight</code>	9
2.2.11	<code>\StrChar</code>	9
2.2.12	<code>\StrMid</code>	9
2.3	Macros returning a number	10
2.3.1	<code>\StrLen</code>	10
2.3.2	<code>\StrCount</code>	10
2.3.3	<code>\StrPosition</code>	10
2.3.4	<code>\StrCompare</code>	11
3	Operating modes	11
3.1	Expansion of arguments	11
3.1.1	The commands <code>\fullexpandarg</code> , <code>\expandarg</code> and <code>\noexpandarg</code>	11
3.1.2	Chars and tokens allowed in arguments	13
3.2	Expansion of macros, optional argument	13
3.3	How does xstring read the arguments?	13
3.3.1	Syntax unit by syntax unit	13
3.3.2	Exploration of groups	14
3.4	Catcode and starred macros	14
4	Advanced macros for programming	15
4.1	Finding a group, macros <code>\StrFindGroup</code> and <code>\groupID</code>	16
4.2	Splitting a string, the macro <code>\StrSplit</code>	17
4.3	Assign a verb content, the macro <code>\verbtocs</code>	17
4.4	Tokenization of a text to a control sequence, the macro <code>\tokenize</code>	18
4.5	Expansion of a control sequence before verbatimize, the macros <code>\StrExpand</code> and <code>\scans</code>	18
4.6	Inside the definition of a macro	19
4.7	The macro <code>\StrRemoveBraces</code>	19
4.8	Examples	20
4.8.1	Example 1	20
4.8.2	Exemple 2	20
4.8.3	Example 3	21
4.8.4	Example 4	21
4.8.5	Example 5	21

This manual is a translation of the french manual. I apologize for my poor english but I did my best¹, and I hope that the following is comprehensible!

1 Presentation

1.1 Description

This extension² provides macros and tests operating on "strings of tokens", as other programming languages have. They provides the usual strings operations, such as: test if a string contains another, begins or ends with another, extractions of strings, calculation of the position of a substring, of the number of occurrences, etc.

A "string of tokens" is a list of tokens of any nature, except that braces must be balanced and tokens catcode 6 and 14 (usually % et #) are not allowed. Apart from this, any token is allowed (including `\par`), in any order in the list, whatever be the resulting code.

`xstring` reads the arguments of the macros syntax unit by syntax unit³ : when syntax units are "simple" chars (catcode 10, 11 and 12), `xstring` logically read the argument char by char. `xstring` can also be used for programming purpose, including in arguments other tokens such as control sequences, braces and tokens with other catcodes. See chapter on reading mode and arguments expansion (page 13), the command `\verbtocs` (page 17) and the command `\scancs` (page 18).

As the arguments may contain any token, advanced users could have problems with catcodes leading to unexpected behaviours. These behaviours can be controlled: read page 14.

Certainly, other packages exist (for example `substr` and `stringstrings`), but as well as differences on features, they do not take into account occurrences so I found them too limited and difficult to use for programming.

1.2 Motivation

I decided to write this package of macros because I have never really found tools in \TeX suiting my needs for strings. So, over the last few months, I wrote a few macros that I occasionally or regularly used. Their numbers have increased and become a little too dispersed in directories in my computer, so I have grouped them together in this package.

Thus, writing a coherent set of macros forces more discipline and leads to necessary improvements, which took most of the time I spent writing this package. This package is my first one as I recently discovered \TeX ⁴, so my main motivation was to make progress in programming with \TeX , and to tackle its specific methods.

2 The macros

For a better understanding, let's see first the macros with the simpler arguments possible. No special catcode, no exotic token, no control sequence neither: only alphanumeric chars will be contained in the arguments.

In the following chapters, all the macros will be presented this plan:

- the syntax⁵ and the value of optional arguments
- a short description of the operation;
- the operation under special conditions. For each conditions considered, the operation described has priority on that (those) below;
- finally, several examples⁶ are given. I tried to find them most easily comprehensible and most representative of the situations met in normal use. If a doubt is possible with spaces in the result, this one will be delimited by "|", given that an empty string is represented by "||".

Important: in the following, a $\langle number \rangle$ can be an integer written with numeric chars, a counter, or the result of an arithmetic operation made with the command `\numexpr`.

All the macros of `xstring` are displayed in red.

¹Any email to tell me errors would be appreciated!

²This extension does not require \TeX and can be compiled with Plain $\epsilon\text{-}\TeX$.

³In the \TeX code, a syntax unit is a control sequence, a group between brace or a single char. See also page 13.

⁴In november 2007, I will be a noob for a long time...

⁵The optional star, the optional argument in last position will be explained later. See page 14 for starred macros and page 13 for the optional argument.

⁶For much more examples, see the test file.

2.1 The tests

2.1.1 \IfSubStr

`\IfSubStr` $\langle[*]\rangle[\langle number\rangle][\langle string\rangle]\{\langle stringA\rangle\}\{\langle true\rangle\}\{\langle false\rangle\}$

The value of the optional argument $\langle number\rangle$ is 1 by default.

Tests if $\langle string\rangle$ contains at least $\langle number\rangle$ times $\langle stringA\rangle$ and runs $\langle true\rangle$ if so, and $\langle false\rangle$ otherwise.

- ▷ If $\langle number\rangle \leq 0$, runs $\langle false\rangle$;
- ▷ If $\langle string\rangle$ or $\langle stringA\rangle$ is empty, runs $\langle false\rangle$.

<pre>1 \IfSubStr{xstring}{tri}{true}{false} 2 \IfSubStr{xstring}{a}{true}{false} 3 \IfSubStr{a bc def}{c d}{true}{false} 4 \IfSubStr{a bc def}{cd}{true}{false} 5 \IfSubStr[2]{1a2a3a}{a}{true}{false} 6 \IfSubStr[3]{1a2a3a}{a}{true}{false} 7 \IfSubStr[4]{1a2a3a}{a}{true}{false}</pre>	<pre>true false true false true true false</pre>
--	--

2.1.2 \IfSubStrBefore

`\IfSubStrBefore` $\langle[*]\rangle[\langle number1\rangle,\langle number2\rangle][\langle string\rangle]\{\langle stringA\rangle\}\{\langle stringB\rangle\}\{\langle true\rangle\}\{\langle false\rangle\}$

The values of the optional arguments $\langle number1\rangle$ and $\langle number2\rangle$ are 1 by default.

In $\langle string\rangle$, tests if the $\langle number1\rangle^{\text{th}}$ occurrence of $\langle stringA\rangle$ is on the left of the $\langle number2\rangle^{\text{th}}$ occurrence of $\langle stringB\rangle$. Runs $\langle true\rangle$ if so, and $\langle false\rangle$ otherwise.

- ▷ If one of the occurrences is not found, it runs $\langle false\rangle$;
- ▷ If one of the arguments $\langle string\rangle$, $\langle stringA\rangle$ or $\langle stringB\rangle$ is empty, runs $\langle false\rangle$;
- ▷ If one of the optional arguments is negative or zero, runs $\langle false\rangle$.

<pre>1 \IfSubStrBefore{xstring}{st}{in}{true}{false} 2 \IfSubStrBefore{xstring}{ri}{s}{true}{false} 3 \IfSubStrBefore{LaTeX}{LaT}{TeX}{true}{false} 4 \IfSubStrBefore{a bc def}{b}{ef}{true}{false} 5 \IfSubStrBefore{a bc def}{ab}{ef}{true}{false} 6 \IfSubStrBefore[2,1]{b1b2b3}{b}{2}{true}{false} 7 \IfSubStrBefore[3,1]{b1b2b3}{b}{2}{true}{false} 8 \IfSubStrBefore[2,2]{baobab}{a}{b}{true}{false} 9 \IfSubStrBefore[2,3]{baobab}{a}{b}{true}{false}</pre>	<pre>true false false true false true false false true</pre>
--	--

2.1.3 \IfSubStrBehind

`\IfSubStrBehind` $\langle[*]\rangle[\langle number1\rangle,\langle number2\rangle][\langle string\rangle]\{\langle stringA\rangle\}\{\langle stringB\rangle\}\{\langle true\rangle\}\{\langle false\rangle\}$

The values of the optional arguments $\langle number1\rangle$ and $\langle number2\rangle$ are 1 by default.

In $\langle string\rangle$, tests if the $\langle number1\rangle^{\text{th}}$ occurrence of $\langle stringA\rangle$ is on the right of the $\langle number2\rangle^{\text{th}}$ occurrence of $\langle stringB\rangle$. Runs $\langle true\rangle$ if so, and $\langle false\rangle$ otherwise.

- ▷ If one of the occurrences is not found, it runs $\langle false\rangle$;
- ▷ If one of the arguments $\langle string\rangle$, $\langle stringA\rangle$ or $\langle stringB\rangle$ is empty, runs $\langle false\rangle$;
- ▷ If one of the optional arguments is negative or zero, runs $\langle false\rangle$.

<pre>1 \IfSubStrBehind{xstring}{ri}{xs}{true}{false} 2 \IfSubStrBehind{xstring}{s}{i}{true}{false} 3 \IfSubStrBehind{LaTeX}{TeX}{LaT}{true}{false} 4 \IfSubStrBehind{a bc def}{d}{a}{true}{false} 5 \IfSubStrBehind{a bc def}{cd}{a b}{true}{false} 6 \IfSubStrBehind[2,1]{b1b2b3}{b}{2}{true}{false} 7 \IfSubStrBehind[3,1]{b1b2b3}{b}{2}{true}{false} 8 \IfSubStrBehind[2,2]{baobab}{b}{a}{true}{false} 9 \IfSubStrBehind[2,3]{baobab}{b}{a}{true}{false}</pre>	<pre>false false false false false false true false false</pre>
---	---

2.1.4 \IfBeginWith

`\IfBeginWith` $\langle[*]\rangle\{\langle string\rangle\}\{\langle stringA\rangle\}\{\langle true\rangle\}\{\langle false\rangle\}$

Tests if $\langle string\rangle$ begins with $\langle stringA\rangle$, and runs $\langle true\rangle$ if so, and $\langle false\rangle$ otherwise.

▷ If $\langle string\rangle$ or $\langle stringA\rangle$ is empty, runs $\langle false\rangle$.

<pre>1 \IfBeginWith{xstring}{xst}{true}{false} 2 \IfBeginWith{LaTeX}{a}{true}{false} 3 \IfBeginWith{a bc def }{a b}{true}{false} 4 \IfBeginWith{a bc def }{ab}{true}{false}</pre>	<pre>true false true false</pre>
---	----------------------------------

2.1.5 \IfEndWith

`\IfEndWith` $\langle[*]\rangle\{\langle string\rangle\}\{\langle stringA\rangle\}\{\langle Behind\rangle\}\{\langle false\rangle\}$

Tests if $\langle string\rangle$ ends with $\langle stringA\rangle$, and runs $\langle true\rangle$ if so, and $\langle false\rangle$ otherwise.

▷ If $\langle string\rangle$ or $\langle stringA\rangle$ is empty, runs $\langle false\rangle$.

<pre>1 \IfEndWith{xstring}{ring}{true}{false} 2 \IfEndWith{LaTeX}{a}{true}{false} 3 \IfEndWith{a bc def }{ef }{true}{false} 4 \IfEndWith{a bc def }{ef}{true}{false}</pre>	<pre>true false true false</pre>
--	----------------------------------

2.1.6 \IfInteger

`\IfInteger` $\{\langle number\rangle\}\{\langle true\rangle\}\{\langle false\rangle\}$

Tests if $\langle number\rangle$ is an integer (i.e whose decimal part is empty or 0), and runs $\langle true\rangle$ if so, and $\langle false\rangle$ otherwise.

If test is false because unexpected characters, the control sequence `\@xs@afterinteger` and `\afterinteger` both contain the illegal part of $\langle number\rangle$.

<pre>1 \IfInteger{13}{true}{false} 2 \IfInteger{-219}{true}{false} 3 \IfInteger{+9}{true}{false} 4 \IfInteger{3.14}{true}{false} 5 \IfInteger{8.0}{true}{false} 6 \IfInteger{0}{true}{false} 7 \IfInteger{49a}{true}{false} 8 \IfInteger{+}{true}{false} 9 \IfInteger{-}{true}{false} 10 \IfInteger{0000}{true}{false}</pre>	<pre>true true true false true true false false false false true</pre>
--	--

2.1.7 \IfDecimal

`\IfDecimal` $\{\langle number\rangle\}\{\langle true\rangle\}\{\langle false\rangle\}$

Tests if $\langle number\rangle$ is a decimal, and runs $\langle true\rangle$ if so, and $\langle false\rangle$ otherwise.

Counters `\integerpart` and `\decimalpart` contain the integer part and decimal part of $\langle number\rangle$.

If test is false because unexpected characters, the control sequence `\@xs@afterdecimal` and `\afterdecimal` both contain the illegal part of $\langle number\rangle$, whereas if test is false because decimal part is empty after decimal separator, they contain "X".

- ▷ Decimal separator can be a dot or a comma;
- ▷ If what is on the right of decimal separator (if it exists) is empty, the test is false;
- ▷ If what is on the left of decimal separator (if it exists) is empty, the integer part is assumed to be 0;

1	<code>\IfDecimal{3.14}{true}{false}</code>	true
2	<code>\IfDecimal{3,14}{true}{false}</code>	true
3	<code>\IfDecimal{-0.5}{true}{false}</code>	true
4	<code>\IfDecimal{.7}{true}{false}</code>	true
5	<code>\IfDecimal{,9}{true}{false}</code>	true
6	<code>\IfDecimal{1..2}{true}{false}</code>	false
7	<code>\IfDecimal{+6}{true}{false}</code>	true
8	<code>\IfDecimal{-15}{true}{false}</code>	true
9	<code>\IfDecimal{1.}{true}{false}</code>	false
10	<code>\IfDecimal{2,}{true}{false}</code>	false
11	<code>\IfDecimal{.}{true}{false}</code>	false
12	<code>\IfDecimal{,}{true}{false}</code>	false
13	<code>\IfDecimal{+}{true}{false}</code>	false
14	<code>\IfDecimal{-}{true}{false}</code>	false

2.1.8 \IfStrEq

`\IfStrEq⟨[*]⟩{⟨stringA⟩}{⟨stringB⟩}{⟨true⟩}{⟨false⟩}`

Tests if the strings *⟨stringA⟩* and *⟨stringB⟩* are equal, i.e. if they contain successively the same syntax units in the same order. Runs *⟨true⟩* if so, and *⟨false⟩* otherwise.

1	<code>\IfStrEq{a1b2c3}{a1b2c3}{true}{false}</code>	true
2	<code>\IfStrEq{abcdef}{abcd}{true}{false}</code>	false
3	<code>\IfStrEq{abc}{abcdef}{true}{false}</code>	false
4	<code>\IfStrEq{3,14}{3,14}{true}{false}</code>	true
5	<code>\IfStrEq{12.34}{12.340}{true}{false}</code>	false
6	<code>\IfStrEq{abc}{}{true}{false}</code>	false
7	<code>\IfStrEq{}{abc}{true}{false}</code>	false
8	<code>\IfStrEq{}{}{true}{false}</code>	true

2.1.9 \IfEq

`\IfEq{⟨stringA⟩}{⟨stringB⟩}{⟨true⟩}{⟨false⟩}`

Tests if the strings *⟨stringA⟩* and *⟨stringB⟩* are equal, *except* if both *⟨stringA⟩* and *⟨stringB⟩* contain numbers in which case the macro tests if these numbers are equal. Runs *⟨true⟩* if so, and *⟨false⟩* otherwise.

- ▷ The definition of *number* is given with the macro `\IfDecimal` (see page 4), and thus :
- ▷ ”+” signs are optional;
- ▷ Decimal separator can be a dot or a comma.

1	<code>\IfEq{a1b2c3}{a1b2c3}{true}{false}</code>	true
2	<code>\IfEq{abcdef}{ab}{true}{false}</code>	false
3	<code>\IfEq{ab}{abcdef}{true}{false}</code>	false
4	<code>\IfEq{12.34}{12,34}{true}{false}</code>	true
5	<code>\IfEq{+12.34}{12.340}{true}{false}</code>	true
6	<code>\IfEq{10}{+10}{true}{false}</code>	true
7	<code>\IfEq{-10}{10}{true}{false}</code>	false
8	<code>\IfEq{+0,5}{,5}{true}{false}</code>	true
9	<code>\IfEq{1.001}{1.01}{true}{false}</code>	false
10	<code>\IfEq{3*4+2}{14}{true}{false}</code>	false
11	<code>\IfEq{\number\numexpr3*4+2}{14}{true}{false}</code>	true
12	<code>\IfEq{0}{-0.0}{true}{false}</code>	true
13	<code>\IfEq{}{}{true}{false}</code>	true

2.1.10 \IfStrEqCase

`\IfStrEqCase⟨[*]⟩{⟨string⟩}{%
 {⟨string1⟩}{⟨code1⟩}%
 {⟨string2⟩}{⟨code2⟩}%
 etc...
 {⟨stringN⟩}{⟨codeN⟩}}[⟨other cases code⟩]`

Tests successively if $\langle string \rangle$ is equal to $\langle string1 \rangle$, $\langle string2 \rangle$, etc. Comparison is made with `\IfStrEq` (see above). If the test number i is positive (the $\langle string \rangle$ matches $\langle string i \rangle$), the macro runs $\langle code i \rangle$ and ends. If all tests fail, the macro runs the optional $\langle other cases code \rangle$, if present.

<pre> 1 \IfStrEqCase{b}{a}{AA}{b}{BB}{c}{CC} 2 \IfStrEqCase{abc}{a}{AA}{b}{BB}{c}{CC} 3 \IfStrEqCase{c}{a}{AA}{b}{BB}{c}{CC}[other] 4 \IfStrEqCase{d}{a}{AA}{b}{BB}{c}{CC}[other] 5 \IfStrEqCase{+3}{1}{one}{2}{two}{3}{three}[other] 6 \IfStrEqCase{0.5}{0}{zero}{.5}{half}{1}{one}[other] </pre>	BB CC other other other
---	---

2.1.11 \IfEqCase

```

\IfEqCase{[*]}{ $\langle string \rangle$ }{%
  { $\langle string1 \rangle$ }{ $\langle code1 \rangle$ }%
  { $\langle string2 \rangle$ }{ $\langle code2 \rangle$ }%
  etc...
  { $\langle stringN \rangle$ }{ $\langle codeN \rangle$ }[ $\langle other cases code \rangle$ ]

```

Tests successively if $\langle string \rangle$ is equal to $\langle string1 \rangle$, $\langle string2 \rangle$, etc. Comparison is made with `\IEq` (see above). If the test number i is positive (the $\langle string \rangle$ matches $\langle string i \rangle$), the macro runs $\langle code i \rangle$ and ends. If all tests fail, the macro runs the optional $\langle other cases code \rangle$, if present.

<pre> 1 \IfEqCase{b}{a}{AA}{b}{BB}{c}{CC} 2 \IfEqCase{abc}{a}{AA}{b}{BB}{c}{CC} 3 \IfEqCase{c}{a}{AA}{b}{BB}{c}{CC}[other] 4 \IfEqCase{d}{a}{AA}{b}{BB}{c}{CC}[other] 5 \IfEqCase{+3}{1}{one}{2}{two}{3}{three}[other] 6 \IfEqCase{0.5}{0}{zero}{.5}{half}{1}{one}[other] </pre>	BB CC other three half
---	--

2.2 Extraction of substrings

2.2.1 \StrBefore

```
\StrBefore{[*]}[ $\langle number \rangle$ ]{ $\langle string \rangle$ }{ $\langle stringA \rangle$ }[ $\langle name \rangle$ ]
```

The value of the optional argument $\langle number \rangle$ is 1 by default.

In $\langle string \rangle$, returns what is leftwards the $\langle number \rangle^{\text{th}}$ occurrence of $\langle stringA \rangle$.

- ▷ If $\langle string \rangle$ or $\langle stringA \rangle$ is empty, an empty string is returned;
- ▷ If $\langle number \rangle < 1$ then the macro behaves as if $\langle number \rangle = 1$;
- ▷ If the occurrence is not found, an empty string is returned.

<pre> 1 \StrBefore{xstring}{tri} 2 \StrBefore{LaTeX}{e} 3 \StrBefore{LaTeX}{p} 4 \StrBefore{LaTeX}{L} 5 \StrBefore{a bc def }{def} 6 \StrBefore{a bc def }{cd} 7 \StrBefore[1]{1b2b3}{b} 8 \StrBefore[2]{1b2b3}{b} </pre>	xs LaT a bc 1 1b2
---	--

2.2.2 \StrBehind

```
\StrBehind{[*]}[ $\langle number \rangle$ ]{ $\langle string \rangle$ }{ $\langle stringA \rangle$ }[ $\langle name \rangle$ ]
```

The value of the optional argument $\langle number \rangle$ is 1 by default.

In $\langle string \rangle$, returns what is rightwards the $\langle number \rangle^{\text{th}}$ occurrence of $\langle stringA \rangle$.

- ▷ If $\langle string \rangle$ or $\langle stringA \rangle$ is empty, an empty string is returned;

- ▷ If $\langle number \rangle < 1$ then the macro behaves as if $\langle number \rangle = 1$;
- ▷ If the occurrence is not found, an empty string is returned.

1 \StrBehind{xstring}{tri}	ng
2 \StrBehind{LaTeX}{e}	X
3 \StrBehind{LaTeX}{p}	
4 \StrBehind{LaTeX}{X}	
5 \StrBehind{a bc def }{bc}	def
6 \StrBehind{a bc def }{cd}	
7 \StrBehind[1]{1b2b3}{b}	2b3
8 \StrBehind[2]{1b2b3}{b}	3
9 \StrBehind[3]{1b2b3}{b}	

2.2.3 \StrCut

Here is the syntax of this macro:

`\StrCut[$\langle n \rangle$][$\langle number \rangle$]{ $\langle string \rangle$ }{ $\langle stringA \rangle$ }{ $\langle macroA \rangle$ }{ $\langle macroB \rangle$ }`

The optional argument $\langle number \rangle$ is 1 by default.

The $\langle string \rangle$ is cut in two parts at the occurrence [$\langle number \rangle$] of $\langle stringA \rangle$. The left part is stored in the control sequence $\langle macroA \rangle$ and the right part in $\langle macroB \rangle$.

Since this macro returns *two strings*, it does *not* display anything. Consequently, it does not provide the optional argument in last position.

- ▷ If $\langle string \rangle$ or $\langle stringA \rangle$ is empty, $\langle macroA \rangle$ and $\langle macroB \rangle$ are empty;
- ▷ If $\langle number \rangle < 1$, the macro behaves as if $\langle number \rangle = 1$;
- ▷ If the occurrence is not found, $\langle macroA \rangle$ receives the whole $\langle string \rangle$ while $\langle macroB \rangle$ is empty.

1 \StrCut{abracadabra}{a}\csA\csB \csA \csB \par	bracadabra
2 \StrCut[2]{abracadabra}{a}\csA\csB \csA \csB \par	abr cadabra
3 \StrCut[3]{abracadabra}{a}\csA\csB \csA \csB \par	abrac dabra
4 \StrCut[4]{abracadabra}{a}\csA\csB \csA \csB \par	abracad bra
5 \StrCut[5]{abracadabra}{a}\csA\csB \csA \csB \par	abracadabr
6 \StrCut[6]{abracadabra}{a}\csA\csB \csA \csB \par	abracadabra
7 \StrCut[-4]{abracadabra}{a}\csA\csB \csA \csB \par	bracadabra
8 \StrCut{abracadabra}{brac}\csA\csB \csA \csB \par	a adabra
9 \StrCut{abracadabra}{foo}\csA\csB \csA \csB \par	abracadabra
10 \StrCut{abracadabra}{}\csA\csB \csA \csB	

2.2.4 \StrBetween

`\StrBetween[$\langle n \rangle$][$\langle number1 \rangle$, $\langle number2 \rangle$]{ $\langle string \rangle$ }{ $\langle stringA \rangle$ }{ $\langle stringB \rangle$ }[$\langle name \rangle$]`

The values of the optional arguments $\langle number1 \rangle$ and $\langle number2 \rangle$ are 1 by default.

In $\langle string \rangle$, returns the substring between⁷ the $\langle number1 \rangle^{\text{th}}$ occurrence of $\langle stringA \rangle$ and $\langle number2 \rangle^{\text{th}}$ occurrence of $\langle stringB \rangle$.

- ▷ If the occurrences are not in this order — $\langle stringA \rangle$ followed by $\langle stringB \rangle$ — in $\langle string \rangle$, an empty string is returned;
- ▷ If one of the 2 occurrences doesn't exist in $\langle string \rangle$, an empty string is returned;
- ▷ If one of the optional arguments $\langle number1 \rangle$ ou $\langle number2 \rangle$ is negative or zero, an empty string is returned.

1 \StrBetween{xstring}{xs}{ng}	tri
2 \StrBetween{xstring}{i}{n}	
3 \StrBetween{xstring}{a}{tring}	
4 \StrBetween{a bc def }{a}{d}	bc
5 \StrBetween{a bc def }{a }{f}	bc de
6 \StrBetween{a1b1a2b2a3b3}{a}{b}	1
7 \StrBetween[2,3]{a1b1a2b2a3b3}{a}{b}	2b2a3
8 \StrBetween[1,3]{a1b1a2b2a3b3}{a}{b}	1b1a2b2a3
9 \StrBetween[3,1]{a1b1a2b2a3b3}{a}{b}	
10 \StrBetween[3,2]{abracadabra}{a}{bra}	da

⁷In a strict sense, i.e. *without* the strings $\langle stringA \rangle$ and $\langle stringB \rangle$

2.2.5 \StrSubstitute

`\StrSubstitute[⟨number⟩]{⟨string⟩}{⟨stringA⟩}{⟨stringB⟩}[⟨name⟩]`

The value of the optional argument `⟨number⟩` is 0 by default.

In `⟨string⟩`, substitute the `⟨number⟩` first occurrences of `⟨stringA⟩` for `⟨stringB⟩`, except if `⟨number⟩ = 0` in which case *all* the occurrences are substituted.

- ▷ If `⟨string⟩` is empty, an empty string is returned;
- ▷ If `⟨stringA⟩` is empty or doesn't exist in `⟨string⟩`, the macro is ineffective;
- ▷ If `⟨number⟩` is greater than the number of occurrences of `⟨stringA⟩`, then all the occurrences are substituted;
- ▷ If `⟨number⟩ < 0` the macro behaves as if `⟨number⟩ = 0`;
- ▷ If `⟨stringB⟩` is empty, the occurrences of `⟨stringA⟩`, if they exist, are deleted.

<pre> 1 \StrSubstitute{xstring}{i}{a} 2 \StrSubstitute{abracadabra}{a}{o} 3 \StrSubstitute{abracadabra}{br}{TeX} 4 \StrSubstitute{LaTeX}{m}{n} 5 \StrSubstitute{a bc def }{ }{M} 6 \StrSubstitute{a bc def }{ab}{AB} 7 \StrSubstitute[1]{a1a2a3}{a}{B} 8 \StrSubstitute[2]{a1a2a3}{a}{B} 9 \StrSubstitute[3]{a1a2a3}{a}{B} 10 \StrSubstitute[4]{a1a2a3}{a}{B} </pre>	<pre> xstrang obrocodobro aTeXacadaTeXa LaTeX aMbcMdefM a bc def B1a2a3 B1B2a3 B1B2B3 B1B2B3 </pre>
--	---

2.2.6 \StrDel

`\StrDel[*][⟨number⟩]{⟨string⟩}{⟨stringA⟩}[⟨name⟩]`

The value of the optional argument `⟨number⟩` is 0 by default.

Delete the `⟨number⟩` first occurrences of `⟨stringA⟩` in `⟨string⟩`, except if `⟨number⟩ = 0` in which case *all* the occurrences are deleted.

- ▷ If `⟨string⟩` is empty, an empty string is returned;
- ▷ If `⟨stringA⟩` is empty or doesn't exist in `⟨string⟩`, the macro is ineffective;
- ▷ If `⟨number⟩` greater then the number of occurrences of `⟨stringA⟩`, then all the occurrences are deleted;
- ▷ If `⟨number⟩ < 0` the macro behaves as if `⟨number⟩ = 0`;

<pre> 1 \StrDel{abracadabra}{a} 2 \StrDel[1]{abracadabra}{a} 3 \StrDel[4]{abracadabra}{a} 4 \StrDel[9]{abracadabra}{a} 5 \StrDel{a bc def }{ } 6 \StrDel{a bc def }{def} </pre>	<pre> brcdbr bracadabra brcdbra brcdbr abcdef a bc </pre>
---	--

2.2.7 \StrGobbleLeft

`\StrGobbleLeft{⟨string⟩}{⟨number⟩}[⟨name⟩]`

In `⟨string⟩`, delete the `⟨number⟩` first characters on the left.

- ▷ If `⟨string⟩` is empty, an empty string is returned;
- ▷ If `⟨number⟩ ≤ 0`, no character is deleted;
- ▷ If `⟨number⟩ ≥ ⟨lengthString⟩`, all the characters are deleted.

<pre> 1 \StrGobbleLeft{xstring}{2} 2 \StrGobbleLeft{xstring}{9} 3 \StrGobbleLeft{LaTeX}{4} 4 \StrGobbleLeft{LaTeX}{-2} 5 \StrGobbleLeft{a bc def }{4} </pre>	<pre> tring X LaTeX def </pre>
--	---------------------------------------

2.2.8 \StrLeft

`\StrLeft{⟨string⟩}{⟨number⟩}[⟨name⟩]`

In `⟨string⟩`, returns the `⟨number⟩` first characters on the left.

- ▷ If `⟨string⟩` is empty, an empty string is returned;
- ▷ If `⟨number⟩ ≤ 0`, no character is returned;
- ▷ If `⟨number⟩ ≥ ⟨lengthString⟩`, all the characters are returned.

<pre> 1 \StrLeft{xstring}{2} 2 \StrLeft{xstring}{9} 3 \StrLeft{LaTeX}{4} 4 \StrLeft{LaTeX}{-2} 5 \StrLeft{a bc def }{5} </pre>	<pre> xs xstring LaTeX a bc </pre>
--	--

2.2.9 \StrGobbleRight

`\StrGobbleRight{⟨string⟩}{⟨number⟩}[⟨name⟩]`

In `⟨string⟩`, delete the `⟨number⟩` last characters on the right.

<pre> 1 \StrGobbleRight{xstring}{2} 2 \StrGobbleRight{xstring}{9} 3 \StrGobbleRight{LaTeX}{4} 4 \StrGobbleRight{LaTeX}{-2} 5 \StrGobbleRight{a bc def }{4} </pre>	<pre> xstri L LaTeX a bc </pre>
---	---

2.2.10 \StrRight

`\StrRight{⟨string⟩}{⟨number⟩}[⟨name⟩]`

In `⟨string⟩`, returns the `⟨number⟩` last characters on the right.

<pre> 1 \StrRight{xstring}{2} 2 \StrRight{xstring}{9} 3 \StrRight{LaTeX}{4} 4 \StrRight{LaTeX}{-2} 5 \StrRight{a bc def }{5} </pre>	<pre> ng xstring aTeX def </pre>
---	-------------------------------------

2.2.11 \StrChar

`\StrChar[*]{⟨string⟩}{⟨number⟩}[⟨name⟩]`

Returns the syntax unit at the position `⟨number⟩` in `⟨string⟩`.

- ▷ If `⟨string⟩` is empty, no character is returned;
- ▷ If `⟨number⟩ ≤ 0` or if `⟨number⟩ > ⟨lengthString⟩`, no character is returned.

<pre> 1 \StrChar{xstring}{4} 2 \StrChar{xstring}{9} 3 \StrChar{xstring}{-5} 4 \StrChar{a bc def }{6} </pre>	<pre> r d </pre>
---	------------------------

2.2.12 \StrMid

`\StrMid{⟨string⟩}{⟨numberA⟩}{⟨numberB⟩}[⟨name⟩]`

In `⟨string⟩`, returns the substring between⁸ the positions `⟨numberA⟩` and `⟨numberB⟩`.

- ▷ If `⟨string⟩` is empty, an empty string is returned;

⁸In the broad sense, i.e. that the strings characters of the "border" are returned.

- ▷ If $\langle numberA \rangle > \langle numberB \rangle$, an empty string is returned;
- ▷ If $\langle numberA \rangle < 1$ and $\langle numberB \rangle < 1$ an empty string is returned;
- ▷ If $\langle numberA \rangle > \langle lengthString \rangle$ et $\langle numberB \rangle > \langle lengthString \rangle$, an empty string is returned;
- ▷ If $\langle numberA \rangle < 1$, the macro behaves as if $\langle numberA \rangle = 1$;
- ▷ If $\langle numberB \rangle > \langle lengthString \rangle$, the macro behaves as if $\langle numberB \rangle = \langle lengthString \rangle$.

<pre> 1 \StrMid{xstring}{2}{5} 2 \StrMid{xstring}{-4}{2} 3 \StrMid{xstring}{5}{1} 4 \StrMid{xstring}{6}{15} 5 \StrMid{xstring}{3}{3} 6 \StrMid{a bc def }{2}{7} </pre>	<pre> stri xs ng t bc de </pre>
--	---------------------------------------

2.3 Macros returning a number

2.3.1 \StrLen

\StrLen{ $\langle string \rangle$ }[$\langle name \rangle$]

Return the length of $\langle string \rangle$.

<pre> 1 \StrLen{xstring} 2 \StrLen{A} 3 \StrLen{a bc def } </pre>	<pre> 7 1 9 </pre>
---	--------------------

2.3.2 \StrCount

\StrCount{ $\langle string \rangle$ }{ $\langle stringA \rangle$ }[$\langle name \rangle$]

Counts how many times $\langle stringA \rangle$ is contained in $\langle string \rangle$.

- ▷ If one at least of the arguments $\langle string \rangle$ or $\langle stringA \rangle$ is empty, the macro return 0.

<pre> 1 \StrCount{abracadabra}{a} 2 \StrCount{abracadabra}{bra} 3 \StrCount{abracadabra}{tic} 4 \StrCount{aaaaaa}{aa} </pre>	<pre> 5 2 0 3 </pre>
--	----------------------

2.3.3 \StrPosition

\StrPosition[$\langle number \rangle$]{ $\langle string \rangle$ }{ $\langle stringA \rangle$ }[$\langle name \rangle$]

The value of the optional argument $\langle number \rangle$ is 1 by default.

In $\langle string \rangle$, returns the position of the $\langle number \rangle^{\text{th}}$ occurrence of $\langle stringA \rangle$.

- ▷ If $\langle number \rangle$ is greater than the number of occurrences of $\langle stringA \rangle$, then the macro returns 0;
- ▷ If $\langle string \rangle$ doesn't contain $\langle stringA \rangle$, then the macro returns 0.

<pre> 1 \StrPosition{xstring}{ring} 2 \StrPosition[4]{abracadabra}{a} 3 \StrPosition[2]{abracadabra}{bra} 4 \StrPosition[9]{abracadabra}{a} 5 \StrPosition{abracadabra}{z} 6 \StrPosition{a bc def }{d} 7 \StrPosition[3]{aaaaaa}{aa} </pre>	<pre> 4 8 9 0 0 6 5 </pre>
--	----------------------------

2.3.4 \StrCompare

`\StrCompare` \langle `[*]` \rangle $\{\langle$ *stringA* $\rangle\}\{\langle$ *stringB* $\rangle\}[\langle$ *name* $\rangle]$

This macro has 2 tolerances: the "normal" tolerance, used by default, and the "strict" tolerance.

- The normal tolerance is activated with `\comparenormal`.
The macro compares characters from left to right in \langle *stringA* \rangle and \langle *stringB* \rangle until a difference appears or the end of the shortest string is reached. The position of the first difference is returned and if no difference is found, the macro return 0.
- The strict tolerance is activated with `\comparestrict`.
The macro compares the 2 strings. If they are equal, it returns 0. If not, the position of the first difference is returned.

It is possible to save the comparison mode with `\savecomparemode`, then modify this comparison mode and come back to the situation when it was saved with `\restorecomparemode`.

Examples with the normal tolerance:

1	<code>\StrCompare{abcd}{abcd}</code>	0
2	<code>\StrCompare{abcd}{abc}</code>	0
3	<code>\StrCompare{abc}{abcd}</code>	0
4	<code>\StrCompare{a b c}{abc}</code>	2
5	<code>\StrCompare{aaa}{baaa}</code>	1
6	<code>\StrCompare{abc}{xyz}</code>	1
7	<code>\StrCompare{123456}{123457}</code>	6
8	<code>\StrCompare{abc}{}</code>	0

Examples with the strict tolerance:

1	<code>\StrCompare{abcd}{abcd}</code>	0
2	<code>\StrCompare{abcd}{abc}</code>	4
3	<code>\StrCompare{abc}{abcd}</code>	4
4	<code>\StrCompare{a b c}{abc}</code>	2
5	<code>\StrCompare{aaa}{baaa}</code>	1
6	<code>\StrCompare{abc}{xyz}</code>	1
7	<code>\StrCompare{123456}{123457}</code>	6
8	<code>\StrCompare{abc}{}</code>	1

3 Operating modes

3.1 Expansion of arguments

3.1.1 The commands `\fullexpandarg`, `\expandarg` and `\noexpandarg`

The command `\fullexpandarg` is called by default, so all the arguments are fully expanded (an `\edef` is used) before the the macro works on them. In most of the cases, this expansion mode avoids chains of `\expandafter` and allows lighter code.

Of course, the expansion of argument can be canceled to find back the usual behaviour of T_EX with the commands `\noexpandarg` or `\normalexpandarg`.

Another expansion mode can be called with `\expandarg`. In this case, the **first token** of each argument is expanded *one time* while all other tokens are left unchanged (if you want the expansion of all tokens one time, you should call the macro `\StrExpand`, see page 18).

The commands `\fullexpandarg`, `\noexpandarg`, `\normalexpandarg` and `\expandarg` can be called at any moment in the code; they behave as "switches" and they can be locally used in a group.

It is possible to save the expansion mode with `\saveexpandmode`, then modify this expansion mode and come back to the situation when it was saved with `\restoreexpandmode`.

In the following list, for every macro of the previous chapter, the arguments colored in purple will possibly be expanded, according to the expansion mode:

- `\IfSubStr` \langle `[*]` \rangle $\{\langle$ *number* $\rangle\}\{\langle$ *string* $\rangle\}\{\langle$ *stringA* $\rangle\}\{\langle$ *true* $\rangle\}\{\langle$ *false* $\rangle\}$

- \IfSubStrBefore[***][*number1*,*number2*]{*string*}{*stringA*}{*stringB*}{*true*}{*false*}
- \IfSubStrBehind[***][*number1*,*number2*]{*string*}{*stringA*}{*stringB*}{*true*}{*false*}
- \IfBeginWith[***]{*string*}{*stringA*}{*true*}{*false*}
- \IfEndWith[***]{*string*}{*stringA*}{*true*}{*false*}
- \IfInteger{*number*}{*true*}{*false*}
- \IfDecimal{*number*}{*true*}{*false*}
- \IfStrEq[***]{*stringA*}{*stringB*}{*true*}{*false*}
- \IfEq[***]{*stringA*}{*stringB*}{*true*}{*false*}
- \IfStrEqCase[***]{*string*}{*string1*}{*code1*}{*string2*}{*code2*}{...
string n}{*code n*}}[*other cases code*]
- \IfEqCase[***]{*string*}{*string1*}{*code1*}{*string2*}{*code2*}{...
string n}{*code n*}}[*other cases code*]
- \StrBefore[***][*number*]{*string*}{*stringA*}[*name*]
- \StrBehind[***][*number*]{*string*}{*stringA*}[*name*]
- \StrBetween[***][*number1*,*number2*]{*string*}{*stringA*}{*stringB*}[*name*]
- \StrSubstitute[*number*]{*string*}{*stringA*}{*stringB*}[*name*]
- \StrDel[*number*]{*string*}{*stringA*}[*name*]
- \StrSplit{*string*}{*number*}{*stringA*}{*stringB*} (see macro StrSplit page 17)
- \StrGobbleLeft{*string*}{*number*}[*name*]
- \StrLeft{*string*}{*number*}[*name*]
- \StrGobbleRight{*string*}{*number*}[*name*]
- \StrRight{*string*}{*number*}[*name*]
- \StrChar{*string*}{*number*}[*name*]
- \StrMid{*string*}{*number1*}{*number2*}[*name*]
- \StrLen{*string*}[*name*]
- \StrCount{*string*}{*stringA*}[*name*]
- \StrPosition[*number*]{*string*}{*stringA*}[*name*]
- \StrCompare{*stringA*}{*stringB*}[*name*]

3.1.2 Chars and tokens allowed in arguments

First of all, whatever be the current expansion mode, **tokens with catcode 6 and 14 (usually # and %) are forbidden in all the arguments**⁹.

When full expansion mode is activated with `\fullexpandarg`, arguments are expanded with an `\edef` before they are read by the macro. Consequently, are allowed in arguments:

- letters (uppercase or lowercase, accented¹⁰ or not), figures, spaces, and any other character with a catcode of 10, 11 ou 12 (punctuation signs, calculation signs, parenthesis, square bracket, etc).;
- tokens with catcode 1 to 4, usually : { }¹¹ \$ &
- tokens with catcode 7 and 8, usually : ^ _
- any purely expandable control sequence¹² or tokens with catcode 13 (active chars) whose expansion is allowed chars.

When arguments are not expanded with the use of `\noexpandarg`, other tokens can be put in a string whatever be the code they make: any control sequence, even undefined, any token catcode 13. Moreover, test tokens are allowed like `\if` or `\ifx`, even without their `\fi`. On the same way, a `\csname` without its `\endcsname` is allowed.

In this example, the argument contains a `\ifx` without the `\fi`: the `\StrBetween` command extracts and displays what is between `\ifx` and `\else`:

```
1 \noexpandarg
2 \StrBetween{\ifx ab false \else true}{\ifx}{\else}
ab false
```

When `\expandarg` is used, the first token needs precaution since it is expanded one time: it must be defined. The other tokens are left unchanged like with `\noexpandarg`.

3.2 Expansion of macros, optional argument

The macros of this package are not purely expandable, i.e. they cannot be put in the argument of an `\edef`. Nestling macros is not possible neither.

For this reason, all the macros returning a result (i.e. all excepted the tests) have an optional argument in last position. The syntax is [*<name>*], where *<name>* is the name of the control sequence that will receive the result of the macro: the assignment is made with an `\edef` which make the result of the macro *<name>* purely expandable. Of course, if an optional argument is present, the macro does not display anything.

Thus, this structure not allowed, supposed to assign to `\Result` the 4 chars on the left of `xstring`:

```
\edef\Result{\StrLeft{xstring}{4}}
```

is equivalent to :

```
\StrLeft{xstring}{4}[\Result]
```

And this nested structure, not allowed neither, supposed to remove the first and last char of `xstring`:

```
\StrGobbleLeft{\StrGobbleRight{xstring}{1}}{1}
```

should be written like this:

```
\StrGobbleRight{xstring}{1}[\mystring]
\StrGobbleleft{\mystring}{1}
```

3.3 How does xstring read the arguments?

3.3.1 Syntax unit by syntax unit

The macros of `xstring` read their arguments syntax unit par syntax unit. In the \TeX code, a syntax unit¹³ is either:

- a control sequence;
- a group, i.e. what is between 2 balanced braces (usually tokens catcode 1 and 2);

⁹Maybe, the token # will be allowed in a future version.

¹⁰For a reliable operation with accented letters, the `\fontenc` package with option [T1] and `\inputenc` with appropriated option must be loaded

¹¹Warning : braces **must** be balanced in arguments !

¹²i.e. this control sequence can be `\edefed`.

¹³For advanced users used to \LaTeX programming, a syntax unit is what is gobbled by the macro `\@gobble` whose code is: `\def\@gobble#1{}`

- a char.

Let's see what is a syntax unit with an example. Let's take this argument : "ab\textbf{xyz}cd"
It has 6 syntax units: "a", "b", "\textbf", "{xyz}", "c" and "d".

What will happen if, while `\noexpandarg` is active, we ask xstring to find the length of this argument and find its 4th "char"

<pre> 1 \noexpandarg 2 \StrLen{ab\textbf{xyz}cd}\par 3 \StrChar{ab\textbf{xyz}cd}{4}[\mychar] 4 \meaning\mychar </pre>	<pre> 6 macro:->{xyz} </pre>
--	---------------------------------

It is necessary to use `\meaning` to see the real expansion of `\mychar`, and not simply call `\mychar` to display it, which make loose informations (braces here). We do not obtain a "char" but a syntax unit, as expected.

3.3.2 Exploration of groups

By default, the command `\noexploregroups` is called, so in the argument containing the string of tokens, xstring does not look into groups, and simply consider them as a syntax unit.

For specific uses, it can be necessary to look into groups: `\exploregroups` changes the exploration mode and forces the macros to look inside groups.

What does this exploration mode in the previous example? xstring does not count the group as a single syntax unit but looks inside it and counts the syntax unit found inside (x, y and z), and so on if there were several nested groups:

<pre> 1 \noexpandarg 2 \exploregroups 3 \StrLen{ab\textbf{xyz}cd}\par 4 \StrChar{ab\textbf{xyz}cd}{4}[\mychar] 5 \meaning\mychar </pre>	<pre> 8 macro:->x </pre>
---	-----------------------------

Exploring the groups can be usefull for counting a substring in a string (`\StrCount`), for the position of a substring in a string (`\StrPosition`) or for tests, but has a severe limitation with macros returning a string: when a string is cut inside a group, **the result does not take into account what is outside this group**. This exploration mode must be used knowingly this limitation when calling macros returning a string.

Let's see what this means with an example. We want to know what is on the left of the second appearance of `\a` in the argument `\a1{\b1\ a2}\a3`. As groups are explored, this appearance is inside this group : `{\b1\ a2}`. The result will be `\b1`. Let's check:

<pre> 1 \noexpandarg 2 \exploregroups 3 \StrBefore[2]{\a1{\b1\ a2}\a3}{\a}[\mycs] 4 \meaning\mycs </pre>	<pre> macro:->\b 1 </pre>
--	------------------------------

Exploring the groups¹⁴ can change the behaviour of most of the macros of xstring, excepted these macros untouched by the exploration mode; their behaviour is the same in any case: `\IfInteger`, `\IfDecimal`, `\IfStrEq`, `\StrEq` et `\StrCompare`.

Moreover, 2 macros run in `\noexploregroups` mode, whatever be the current mode: `\StrBetween` et `\StrMid`.

It is possible to save the exploration mode with `\saveexploremode`, then modify it and come back to the situation when it was saved with `\restoreexploremode`.

3.4 Catcode and starred macros

Macros of this package take the catcodes of tokens into account. To avoid unexpected behaviour (particulary with tests), you should keep in mind that tokens *and their catcodes* are examined.

For instance, these two arguments:

`{\string a\string b}` and `{ab}`

¹⁴The file test of xstring has many examples underlining differences between exploration modes.

do *not* expand into equal strings for `xstring`! Because of the command `\string`, the first expands into "ab" with catcodes 12 while the second have characters with their natural catcodes 11. Catcodes do not match! It is necessary to be aware of this, particularly with \TeX commands like `\string` whose expansions are a strings with chars catcodes 12 and 10 : `\detokenize`, `\meaning`, `\jobname`, `\fontname`, `\romannumeral`, etc.

Starred macros do not take catcodes into account. They simply convert some arguments into arguments with catcodes 10, 11 and 12, and call the non-starred macros with these modified arguments. The optional arguments are not modified and the catcodes are left unchanged.

Here is an example:

<pre> 1 \IfStrEq{\string a\string b}{ab}{true}{false}\par 2 \IfStrEq*\string a\string b}{ab}{true}{false} </pre>	<pre> false true </pre>
--	-------------------------

The strings do not match because of catcode differences: the test is negative in the non-starred macro.

Warning: the use of a starred macro has consequences! The arguments are "detokenized", thus, there is no more control sequences, groups, neither any special char: everything is converted into chars with "harmless" catcodes.

For the macros returning a string, if the starred version is used, the result will be a string in which chars have catcodes 12 and 10 for space. For example, after a "`\StrBefore*{a \b c d}{c}[\mytext]`", the control sequence `\mytext` expands to "`a12␣10b12␣10`".

The macro with a starred version are listed below. For these macros, if starred version is used, the **purple** arguments will be detokenized:

- `\IfSubStr<[*]>[<number>]{<string>}{<stringA>}{<true>}{<false>}`
- `\IfSubStrBefore<[*]>[<number1>,<number2>]{<string>}{<stringA>}{<stringB>}{<true>}{<false>}`
- `\IfSubStrBehind<[*]>[<number1>,<number2>]{<string>}{<stringA>}{<stringB>}{<true>}{<false>}`
- `\IfBeginWith<[*]>{<string>}{<stringA>}{<true>}{<false>}`
- `\IfEndWith<[*]>{<string>}{<stringA>}{<true>}{<false>}`
- `\IfStrEq<[*]>{<stringA>}{<stringB>}{<true>}{<false>}`
- `\IfEq<[*]>{<stringA>}{<stringB>}{<true>}{<false>}`
- `\IfStrEqCase<[*]>{<string>}{<string1>}{<code1>}`
`{<string2>}{<code2>}`
`...`
`{<string n>}{<code n>}}[<other cases code>]`
- `\IfEqCase<[*]>{<string>}{<string1>}{<code1>}`
`{<string2>}{<code2>}`
`...`
`{<string n>}{<code n>}}[<other cases code>]`
- `\StrBefore<[*]>[<number>]{<string>}{<stringA>}[<name>]`
- `\StrBehind<[*]>[<number>]{<string>}{<stringA>}[<name>]`
- `\StrBetween<[*]>[<number1>,<number2>]{<string>}{<stringA>}{<stringB>}[<name>]`
- `\StrCompare<[*]>{<stringA>}{<stringB>}[<name>]`

4 Advanced macros for programming

Though `xstring` is able to read arguments containing \TeX or \LaTeX code, for some advanced programming needs, it can be insufficient. This chapter presents other macros able to get round some limitations.

4.1 Finding a group, macros `\StrFindGroup` and `\groupID`


When `\exploregroups` mode is active, the macro `\StrFindGroup` finds a group between braces with its identifier:

`\StrFindGroup{⟨argument⟩}{⟨identifier⟩}[⟨name⟩]`

When the group matching the identifier does not exist, an empty string is assigned to `⟨name⟩`. If the group is found, this group *with its braces* is assigned to `⟨name⟩`.

This identifier characterizes the nestling position of the group. It is a list of one or several integers separated with commas. n_1 , the first integer is the number of the group (not nested in another) in which the sought group is. Inside this group, the second integer n_2 is the number of the group (not nested in another) in which the sought group is...and so on until the necessary nestling depth is reached to obtain the sought after group.

Let's take an example with 3 levels of nested groups. In this example, braces delimiting groups are colored in red for nestling level 1, in blue for level 2 and in green for level 3. The groups are numbered with the rule seen above:



In this example:

- the group `{{bc}d{efg}}` has the identifier: **1**
- the group `{ij}` has the identifier: **2, 1**
- the group `{no}` has the identifier: **2, 3, 2**
- the whole argument `a{{bc}d{efg}}h{{ij}{k}{l{m}{no}}}p` has the identifier 0, only case where the integer 0 is appears in the identifier of a group.

Here is the full example:

```

1 \exploregroups
2 \expandarg
3 \def\mystring{a{{bc}d{efg}}h{{ij}{k}{l{m}{no}}}p}
4 \StrFindGroup{\mystring}{1}[\mygroup]
5 \meaning\mygroup\par
6 \StrFindGroup{\mystring}{2,1}[\mygroup]
7 \meaning\mygroup\par
8 \StrFindGroup{\mystring}{2,3,2}[\mygroup]
9 \meaning\mygroup\par
10 \StrFindGroup{\mystring}{2,5}[\mygroup]
11 \meaning\mygroup\par

```

macro:->{{bc}d{efg}}
macro:->{ij}
macro:->{no}
macro:->

The reverse process exists, and several macros of `xstring` provide the identifier of the group in which they made a cut or they found a substring. These macros are: `\IfSubStr`, `\StrBefore`, `\StrBehind`, `\StrSplit`, `\StrLeft`, `\StrGobbleLeft`, `\StrRight`, `\StrGobbleRight`, `\StrChar`, `\StrPosition`.

After these macros, the control sequence `\groupID` expands to the identifier of the group where the cut has been done or the search has succeeded. When not cut can be done or the search fails, `\groupID` is empty. Obviously, the use of `\groupID` has sense only when `\exploregroups` mode is active and when non starred macros are used.

Here are some examples with the macro `\StrChar`:

```

1 \exploregroups
2 char 1 = \StrChar{a{b{cd}{e{f}g}h}ijkl}{1}\qquad
3 \string\groupID = \groupID\par
4 char 4 = \StrChar{a{b{cd}{e{f}g}h}ijkl}{4}\qquad
5 \string\groupID = \groupID\par
6 char 6 = \StrChar{a{b{cd}{e{f}g}h}ijkl}{6}\qquad
7 \string\groupID = \groupID\par
8 char 20 = \StrChar{a{b{cd}{e{f}g}h}ijkl}{20}\qquad
9 \string\groupID = \groupID

```

char 1 = a \groupID= 0
char 4 = d \groupID= 1,1
char 6 = f \groupID= 1,1,2,1
char 20 = \groupID=

4.2 Splitting a string, the macro `\StrSplit`

Here is the syntax:

`\StrSplit{⟨string⟩}{⟨number⟩}{⟨stringA⟩}{⟨stringB⟩}`

The `⟨string⟩`, is splitted after the syntax unit at position `⟨number⟩`. The left part is assigned to the control sequence `⟨stringA⟩` and the right part is assigned to `⟨stringB⟩`.

This macro returns two strings, so it does *not* display anything. Consequently, it does not provide the optional argument in last position.

- ▷ If `⟨number⟩ ≤ 0`, `⟨stringA⟩` is empty and `⟨stringB⟩` is equal to `⟨string⟩`;
- ▷ If `⟨number⟩ ≥ lengthString`, `⟨stringA⟩` is equal to `⟨string⟩` and `⟨stringB⟩` is empty;
- ▷ If `⟨string⟩` is empty, `⟨stringA⟩` and `⟨stringB⟩` are empty, whatever be the integer `⟨number⟩`.

<pre> 1 \def\redsep{\color{red}}}% 2 \StrSplit{abcdef}{4}{\csA}{\csB} \csA\redsep\csB 3 \StrSplit{a b c}{2}{\csA}{\csB} \csA\redsep\csB 4 \StrSplit{abcdef}{1}{\csA}{\csB} \csA\redsep\csB 5 \StrSplit{abcdef}{5}{\csA}{\csB} \csA\redsep\csB 6 \StrSplit{abcdef}{9}{\csA}{\csB} \csA\redsep\csB 7 \StrSplit{abcdef}{-3}{\csA}{\csB} \csA\redsep\csB </pre>	<pre> abcd ef a b c a bcdef abcde f abcdef abcdef </pre>
---	---

When the exploration of groups is active and the cut is made at the end of a group, the content of the left string will be the entire group while the right string will be empty. The example shows this:

<pre> 1 \explore groups 2 \StrSplit{ab{cd{ef}gh}ij}{6}\strA\strB 3 \meaning\strA\par 4 \meaning\strB </pre>	<pre> macro:->ef macro:-> </pre>
---	--

This macro provides a star version: in this case, the cut is made just before the syntax unit which follows the syntax unit at position `⟨number⟩`. Both version give same results, except when the cut is made at the end of a group; in that case, `\StrSplit` closes as many group as necessary until it finds the next syntax unit: the cut is made just before this syntax unit.

<pre> 1 \explore groups 2 Use without star : \par 3 \StrSplit{ab{cd{ef}gh}ij}{6}\strA\strB 4 \meaning\strA\par 5 \meaning\strB\par 6 \string\groupID\ = \groupID\par\medskip 7 Use with star : \par 8 \StrSplit*{ab{cd{ef}gh}ij}{6}\strA\strB 9 \meaning\strA\par 10 \meaning\strB\par 11 \string\groupID\ = \groupID </pre>	<pre> Use without star : macro:->ef macro:-> \groupID = 1,1 Use with star : macro:->cd{ef} macro:->gh \groupID = 1,1 </pre>
--	--

4.3 Assign a verb content, the macro `\verbtoct`

The macro `\verbtoct` allow to read the content of a "verb" argument containing special characters: `&`, `~`, `\`, `{`, `}`, `_`, `#`, `$`, `^` and `%`. The catcodes of "normal" characters are left unchanged while special characters take a catcode 12. Then, these characters are assigned to a control sequence. The syntax is:

`\verbtoct{⟨name⟩}{⟨characters⟩}`

`⟨name⟩` is the name of the control sequence receiving, with an `\edef`, the `⟨characters⟩`. `⟨name⟩` thus contains tokens with catcodes 12 (or 10 for space).

By default, the token delimiting the verb content is `"|"`. Obviously, this token cannot be both delimiting and being contained into what it delimits. If you need to verbatimize strings containing `"|"`, you can change at any time the token delimiting the verb content with the macro:

`\setverbdelim{⟨character⟩}`

Any `⟨token⟩` can be used¹⁵. For example, after `\setverbdelim{=}`, a verb argument look like this: `=⟨characters⟩=`.

¹⁵Several tokens can be used, but the syntax of `\verbtoct` becomes less readable ! For this reason, a warning occurs when the argument of `\setverbdelim` contains more than a single token.

About verb arguments, keep in mind that:

- all the characters before $\langle characters \rangle$ are ignored;
- inside the verb argument, all the spaces are taken into account, even if they are consecutive.

Example:

<pre> 1 \verbto{ \result } a & b{ c% d\$ e \f 2 I display the result : \par \result </pre>	<p>I display the result :</p> <p>a & b{ c% d\$ e \f</p>
---	---

4.4 Tokenization of a text to a control sequence, the macro `\tokenize`

The reverse process of what has been seen above is to transform chars into tokens. This is done by the macro:

`\tokenize{⟨name⟩}{⟨control sequences⟩}`

$\langle control sequences \rangle$ is fully expanded if `\fullexpandarg` has been called, and is not expanded if `\noexpandarg` or `\expandarg` are active. After expansion, the chars are tokenized to tokens and assigned to $\langle name \rangle$ with a `\def`.

Example:

<pre> 1 \verbto{ \text } \textbf{a} \$ \frac{1}{2} \$ 2 text : \text 3 \tokenize{ \result } { \text } \par 4 result : \result </pre>	<p>text : <code>\textbf{a} \$ \frac{1}{2} \$</code></p> <p>result : <code>a $\frac{1}{2}$</code></p>
--	---

Obviously, the control sequence `\result` can be called at the last line since the control sequences it contains are defined.

4.5 Expansion of a control sequence before verbatimize, the macros `\StrExpand` and `\scancs`

The macro `\StrExpand` expands the tokens of a string:

`\StrExpand[⟨number⟩]{⟨string⟩}{⟨name⟩}`

By default, $\langle number \rangle$ is 1 and represents the number of times each token of $\langle string \rangle$ has to be expanded. The $\langle name \rangle$ is a control sequence receiving the result of the expansions.

Macro works sequentially and by pass: in a pass, each token from left to right is replaced by its 1-expansion. After this expansion, if the $\langle number \rangle$ of expansions is not reached, an other pass starts, and so on.

Here is an example:

<pre> 1 \def\csA{1 2} 2 \def\csB{a \csA} 3 \def\csC{\csB \space} 4 \def\csD{x\csA y\csB\csC z} 5 Expansion of \string\csD at \par 6 \StrExpand[0]{\csD}{\csE} depth 0 : 7 \detokenize\expandafter{\csE} \par 8 \StrExpand[1]{\csD}{\csE} depth 1 : 9 \detokenize\expandafter{\csE} \par 10 \StrExpand[2]{\csD}{\csE} depth 2 : 11 \detokenize\expandafter{\csE} \par 12 \StrExpand[3]{\csD}{\csE} depth 3 : 13 \detokenize\expandafter{\csE} \par 14 \StrExpand[4]{\csD}{\csE} depth 4 : 15 \detokenize\expandafter{\csE} </pre>	<p>Expansion of <code>\csD</code> at</p> <p>depth 0 : <code>\csD</code></p> <p>depth 1 : <code>x\csA y\csB \csC z</code></p> <p>depth 2 : <code>x{1 2y}a \csA \csB \space z</code></p> <p>depth 3 : <code>x{1 2y}a 1 2{a \csA z}</code></p> <p>depth 4 : <code>x{1 2y}a 1 2{a 1 2 z}</code></p>
--	---

The macro expands each token consecutively, and does not see what follows: tokens whose expansion depends on other tokens cannot be expanded with this macro. For instance, though `"\iftrue A\else B\fi"` has a natural expansion (`"A"`), it cannot be put in the argument of `\StrExpand` and:

`\StrExpand{\iftrue A\else B\fi}\resultat`

provokes an error because the first token `"\iftrue"` is expanded *alone* without seeing its `\fi` which makes \TeX angry.

Expansion inside groups is *independent* of the exploration mode: this macro has its own command to expand or not what is inside the groups. By default, tokens inside groups are expanded, but this can be changed with the macro `\noexpandinggroups`. The default behaviour can be recovered with `\expandinggroups`.

The `\scancs` macro returns the detokenized result:

```
\scancs[⟨number⟩]{⟨name⟩}{⟨string⟩}
```

The `⟨number⟩` is 1 by default and represents the number of expansions.

`\scancs` has been kept for compatibility with older versions of xstring. This macro is now unnecessary, simply takes the result of `\StrExpand` and `\detokenize` it.

4.6 Inside the definition of a macro

Some difficulties arise inside the definition of a macro, i.e. between braces following a `\def\macro` or a `\newcommand\macro`.

It is forbidden to use the command `\verb` inside the definition of a macro. For the same reasons:

Do not use `\verbtocs` inside the definition of a macro.

But then, how to manipulate special characters and "verbatimize" inside the definition of macros ?

The `\detokenize` primitive of ϵ -TeX can be used but it has limitations:

- braces must be balanced;
- consecutive spaces make a single space;
- the % sign is not allowed;
- a space is inserted after each control sequence;
- # signs become ##.

It is better to use `\scancs` and define *outside the definition of the macros* control sequences containing special characters with `\verbtocs`. It is also possible to use `\tokenize` to transform the final result (which is generally `text10,11,12`) into control sequences. See example using these macros at the end of this manual, page 20.

In the following teaching example¹⁶, the macro `\bracearg` adds braces to its argument. To make this possible, 2 control sequences `\Ob` and `\Cb` containing "{" and "}" are defined outside the definition of `\bracearg`, and expanded inside it:

<pre> 1 \verbtocs{\Ob}{ { 2 \verbtocs{\Cb}{ } 3 \newcommand\bracearg[1]{% 4 \def\text{#1}% 5 \scancs{\result}{\Ob\text\Cb}% 6 \result} 7 8 \bracearg{xstring}\par 9 \bracearg{\a} </pre>	<pre> {xstring} {\a } </pre>
--	------------------------------

4.7 The macro `\StrRemoveBraces`

Advanced users may need to remove the braces of an argument.

The macro `\StrRemoveBraces` does this. Its syntax is:

```
\StrRemoveBraces{⟨string⟩}[⟨name⟩]
```

This macro is sensitive to exploration mode and will remove *all* the braces with `\exploregroups` while it will remove braces of lower level with `\noexploregroups`.

¹⁶It is possible to make much more simple using `\detokenize`. The macro becomes:
`\newcommand\bracearg[1]{\detokenize{#1}}`

```

1 \noexploregroups
2 \StrRemoveBraces{a{b{c}d}e{f}g}[\mycs]
3 \meaning\mycs
4
5 \exploregroups
6 \StrRemoveBraces{a{b{c}d}e{f}g}[\mycs]
7 \meaning\mycs

```

macro:->ab{c}defg
macro:->abcdefg

4.8 Examples

Here are some very simple examples involving the macros of this package in programming purposes.

4.8.1 Example 1

We want to substitute the 2 first `\textit` by `\textbf` in the control sequence `\myCS` which contains

`\textit{A}\textit{B}\textit{C}`

We expect: **ABC**

```

1 \expandarg
2 \def\myCS{\textit{A}\textit{B}\textit{C}}
3 \def\pattern{\textit}
4 \def\replace{\textbf}
5 \StrSubstitute[2]{\myCS}{\pattern}{\replace}

```

ABC

It is possible to avoid to define `\pattern` and `\replace`: a "snare" can be used. It can be a control sequence which expansion is empty, like the famous `\empty`. The code would have been:

`\StrSubstitute[2]{\myCS}{\empty\textit}{\empty\textbf}`

With this code, in both arguments, the first token `\empty` is expanded to "nothing" and the following significant tokens `\textit` and `\textbf` are left unchanged.

By this way, `\empty` is a way to "hack" `\expandarg`: it allows to avoid the expansion of all the other tokens. The control sequence `\noexpand` can be used instead of `\empty` for the same result.

4.8.2 Example 2

Here, we try to write a macro which gobbles `n` syntax units in a string from a given position, and assigns the result to a control sequence.

Let's call this macro `StringDel` and let's give it this syntax:

`\StringDel{string}{position}{n}{\name_of_result}`

We can proceed like this: take the string before the position and save it. Then remove `n + position` syntax units from the initial string, and add (concatenate) this result to the string previously saved. This gives the following code:

```

1 \newcommand\StringDel[4]{%
2   \begingroup
3   \expandarg% locally in this group
4   \StrLeft{\empty#1}{\number\numexpr#2-1}[\#4]%
5   \StrGobbleLeft{\empty#1}{\numexpr#2+#3-1}[\StrA]%
6   \expandafter\expandafter\expandafter\endgroup
7   \expandafter\expandafter\expandafter\def
8   \expandafter\expandafter\expandafter#4%
9   \expandafter\expandafter\expandafter
10  {\expandafter#4\StrA}%
11 }
12
13 \noexploregroups
14 \StringDel{abcdefgh}{2}{3}{\cmd}
15 \meaning\cmd
16
17 \StringDel{a\textbf{1}b\textbf{2c}3d}{3}{4}{\cmd}
18 \meaning\cmd

```

macro:->aefgh
macro:->a\textbf 3d

To concatenate, the \LaTeX macro `\g@addto@macro` could have been used, leading to a lighter code without the huge bridge of `\expandafter`. The assignment¹⁷ can be written like this:

```
\expandafter\g@addto@macro\expandafter#4\expandafter{\StrA}\endgroup
```

4.8.3 Example 3

Let's try to write a macro `\tofrac` that transforms an argument of this type "a/b" into " $\frac{a}{b}$ ".

First of all, let's cancel the expansion of arguments with `\noexpandarg`, we do not need expansion here. Then, it's easy to cut what is before and behind the first occurrence of "/" (assumed there is a single occurrence) and assign it to `\num` and `\den` and simply call the macro `\frac` :

```
1 \noexpandarg
2 \newcommand\tofrac[1]{%
3   \StrBefore{#1}{/}[ \num]%
4   \StrBehind{#1}{/}[ \den]%
5   $\frac{\num}{\den}$%
6 }
7 \tofrac{15/9}
8 \tofrac{u_{n+1}/u_n}
9 \tofrac{a^m/a^n}
10 \tofrac{x+\sqrt{x}}{\sqrt{x^2+x+1}}
```

$$\frac{15}{9} \frac{u_{n+1}}{u_n} \frac{a^m}{a^n} \frac{x+\sqrt{x}}{\sqrt{x^2+x+1}}$$

4.8.4 Example 4

Let's try to write a macro `\boldafter` which writes in bold the first word that follows the word contained in the expansion of `\word`.

```
1 \newcommand\boldafter[2]{%
2   \noexpandarg
3   \StrBehind[1]{#1}{ #2 }[ \word]%
4   \expandarg
5   \StrBefore{\word}{ }[ \word]%
6   \StrSubstitute[1]{#1}{\word}{\textbf{\word}}%
7 }
8
9 \boldafter{The xstring package is new}{xstring}
10
11 \boldafter{The xstring package is new}{ring}
12
13 \boldafter{The xstring package is new}{is}
```

The xstring **package** is new
The xstring package is new
The xstring package is **new**

4.8.5 Example 5

How to reverse the order of the 2 first control sequences? For this, a macro `\swaptwofirst` does the job and displays the result. But this time, it is not possible to seek the token `\` (catcode 0) with the macros of xstring. This is why the use of `\scancs` is necessary: after the detokenization of the argument, it becomes possible to search the char `\` (catcode 12). At line 5, a retokenization is done by `\tokenize` and `\before` and `\after` are swapped at this moment.

¹⁷The macro `\g@addto@macro` can be used if the catcode of "@" is temporarily changed with `\makeatletter` and restored with `\makeatother`

```

1 \verbtocs{\antislash}|\|
2 \newcommand\swaptwofirst[1]{%
3   \begingroup
4   \fullexpandarg
5   \scans[0]\mystring{#1}%
6   \StrBefore[3]{\mystring}{\antislash}[\firsttwo]%
7   \StrBehind{\mystring}{\firsttwo}[\others]
8   \StrBefore[2]{\firsttwo}{\antislash}[\before]
9   \StrBehind{\firsttwo}{\before}[\after]%
10  \tokenize\myCS{\after\before\others}%
11  \myCS
12  \endgroup
13 }
14
15 \swaptwofirst{\underline{A}\textbf{B}\textit{C}}
16
17 \swaptwofirst{\Large\underline{A}\textbf{B}123}

```

BAC
AB123

4.8.6 Example 6

In a string, we want to find the n^{th} word between 2 given delimiters. For this, let's write a macro `\findword` with an optional argument which content is the delimiter (space by default), 1 argument containing the string and an other argument containing the number n .

The macro `\findword` artfully uses `\StrBetween` and `\numexpr`:

```

1 \newcommand\findword[3][ ]{%
2   \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}{#1}%
3 }
4 \noexpandarg
5 |\findword{a bc d\textbf{e f} gh}{3}|
6
7 |\findword[\nil]{1 \nil 2 3 \nil4\nil5}{2}|

```

|de f|
|2 3|

★
★ ★

That's all, I hope you will find this package useful!

Please, send me an [email](#) if you find a bug or if you have any idea of improvement...

Christian Tellechea