

# L<sup>A</sup>T<sub>E</sub>X News

Issue 36, November 2022 — DRAFT version for upcoming release

## Contents

<b>Introduction</b>	<b>1</b>
Auto-detecting key–value arguments . . . . .	1
Encoding subsets for TS1 encoded fonts . . . .	1
<b>New or improved commands</b>	<b>1</b>
<b>Code improvements</b>	<b>1</b>
Support for slanted small caps in the EC-fonts	1
EC sans serif at small sizes . . . . .	2
Detect nested <code>minipage</code> environments . . . .	2
Lua <sub>T</sub> <sub>E</sub> <sub>X</sub> callback efficiency improvement . . . .	2
Improve <code>l3docstrip</code> integration into <code>docstrip</code> . .	2
Improve font series handling with incorrect <code>.fd</code> files . . . . .	2
<b>Bug fixes</b>	<b>2</b>
Prevent <sub>T</sub> <sub>E</sub> <sub>X</sub> from loosing a <code>\smash</code> . . . . .	2
Resolve an issue with <code>\mathchoice</code> and <code>localalphabets</code> . . . . .	2
<b>Changes to packages in the <code>amsmath</code> category</b>	<b>2</b>
<b>Changes to packages in the <code>graphics</code> category</b>	<b>2</b>
Fix a <code>\mathcolor</code> bug . . . . .	2
<b>Changes to packages in the <code>tools</code> category</b>	<b>3</b>
<code>array</code> : Correctly identify single-line m-cells . . .	3

## Introduction

*to be written*

### Auto-detecting key–value arguments

To allow extension of the core L<sup>A</sup>T<sub>E</sub>X syntax, `ltxcmd` now supports a `=...` modifier when grabbing arguments. This modifier instructs L<sup>A</sup>T<sub>E</sub>X that the argument should be passed to the underlying code as a set of keyvals. If the argument does not “look like” a set of keyvals, it will be converted into a single key–value pair, with the argument to `=` specifying the name of that key. For example, the `\caption` command could be defined as

```
\DeclareDocumentCommand\caption
  {s ={\short-text}+0{#3} +m}
{...}
```

which would mean that if the optional argument does *not* contain keyval data, it will be converted to a single keyval pair with the key name `short-text`.

Arguments which begin with `=`, are always interpreted as keyvals even if they do not contain further `=` signs. Any `=` signs enclosed within `$...$` or `\(...\)`, i.e. in inline math mode, are ignored, meaning that only `=` outside of math mode will generally cause interpretation as keyval material.

In case the argument contains a “textual” `=` sign that is mistaken as key/value indicator you can hide it using a brace group as you would do in other places, e.g.,

```
\caption[{\Use of = signs}]
  {\Use of = signs in optional arguments}
```

However, because a `=` sign in math mode are already ignored, this should seldom be necessary.

### Encoding subsets for TS1 encoded fonts

The text companion encoding TS1 is unfortunately not very faithfully supported in fonts that are not close cousins to the Computer Modern fonts. It was therefore necessary to provide the notion of “sub-encodings” on a per font basis. These sub-encodings are declared for a font family with the help of a `\DeclareEncodingSubset` declaration, see [5] for details.

Maintainers of font bundles that include TS1 encoded font files should add an appropriate declaration into the corresponding `ts1family.fd` file, because otherwise the default subencoding is assumed, which is probably disabling too many glyphs that are actually available in the font.<sup>1</sup> (*github issue 905*)

## New or improved commands

### Code improvements

#### Support for slanted small caps in the EC-fonts

Since some time L<sup>A</sup>T<sub>E</sub>X supports the combination of the shapes small caps and italic/slanted. The EC-fonts contain slanted small caps fonts but using them required the loading of an external package. Suitable font definitions have now been added to `tlcmd.fd` and so from now on

```
\textsc{\textsl{slanted small}}
\textsc{\textit{italic small caps}}
\bfseries
```

<sup>1</sup>The L<sup>A</sup>T<sub>E</sub>X format contains declarations for many font families already. This was done in 2020 to quickstart the use of the symbols in the kernel, but it is really the wrong place for such declarations. Thus, for new fonts the declarations should be placed into the corresponding `.fd` files.

`\textsc{\textsl{bold slanted small caps}}`  
`\textsc{\textit{bold italic small caps}}`

will give the expected result: *SLANTED SMALL ITALIC*  
*SMALL CAPS BOLD SLANTED SMALL CAPS BOLD*  
*ITALIC SMALL CAPS* (github issue 782)

#### EC sans serif at small sizes

The EC (T1 encoded Computer Modern) sans serif fonts have errors at small sizes: the medium weight is bolder and wider than the bold extended. This makes them unusable at these small sizes. The default `.fd` file has therefore been adjusted to use a scaled down 8pt font instead. (github issue 879)

#### Detect nested minipage environments

Nesting of `minipage` environments is only partially supported in L<sup>A</sup>T<sub>E</sub>X and can lead to incorrect output, such as overfull boxes or footnotes appearing in the wrong place; see [1, p. 106]. However, until now there was no warning if that happened. This has been changed and the environment now warns if you nest it in another `minipage` environment that already contains footnotes. (github issue 168)

#### LuaT<sub>E</sub>X callback efficiency improvement

The mechanism for providing the `pre/post_mlist_to_hlist_filter` callbacks in LuaT<sub>E</sub>X has been improved to make it more reusable and to avoid overhead if these callbacks are not used. (github issue 830)

#### Improve l3docstrip integration into docstrip

In 2020 we merged `l3docstrip.tex` into `docstrip.tex` to support the `%<@=<module>` syntax of `expl3`; see [2]. However, this support was incomplete, because it didn't cover `docstrip` lines of the form `%<+...>` or `%<-...>`. This was never noticed until now, because usually `%<*...>` blocks are used. Now all lines in a `.dtx` file are subject to the `@@` replacement approach. (github issue 903)

#### Improve font series handling with incorrect .fd files

By convention, the font series value is supposed to contain no `m`, unless you refer to the “medium” series (which is represented by a single `m`). For example, one should write `c` for “medium weight, condensed width” and not `mc`. This was one of the many space-conserving methods necessary in the early days of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

Some older `.fd` files do not obey that convention but use `mc`, `bm`, etc., in their declarations. As a result, some font selection scheme functionality was not working when confronted with such `.fd` files. We have therefore augmented `\DeclareSymbolFont` and `\SetSymbolFont` to strip their series argument from any surplus `m` so that they do not unnecessarily trigger font substitutions.

Regardless of this support such `.fd` files should get fixed by their maintainers. (github issue 918)

## Bug fixes

#### Prevent T<sub>E</sub>X from loosing a \smash

When T<sub>E</sub>X is typesetting a fraction, it will rebox the material in either numerator or the denominator depending on which is wider. If the repackaged part consists of a single box, that box gets new dimensions and if it was built using a `\smash` that effect vanishes (because a `smash` is nothing other than zeroing some box dimension, which now got undone). For example, in the line

`\frac{1}{2} = \frac{1}{\smash{2^X}}`  
`\neq \frac{100}{\smash{2^X}}`

the 2 in the denominators was not always at the same vertical position, because the second `\smash` was ignored due to reboxing:

$$\frac{1}{2} = \frac{1}{2^X} \neq \frac{100}{2^X}$$

The differences are subtle but noticeable. This is now corrected and the `\smash` is always honored. Thus now you get this output:

$$\frac{1}{2} = \frac{1}{2^X} \neq \frac{100}{2^X}$$

(github issue 517)

#### Resolve an issue with \mathchoice and local alphabets

The code for keeping a number of math alphabets local (introduced in 2021; see [3]) used `\aftergroup` to do some cleanup actions after a formula had finished. Unfortunately, `\aftergroup` can't be used inside the arguments of the `\mathchoice` primitive and as a result one got low-level errors if the freezing happened in such a place. The implementation was therefore revised to avoid the `\aftergroup` approach altogether. (github issue 921)

## Changes to packages in the amsmath category

### Changes to packages in the graphics category

#### Fix a \mathcolor bug

The `\mathcolor` command introduced in [4] needs to scan for following sub and superscripts, but if it did so at the end of an alignment cell, e.g., in a `array` environment, the `&` was evaluated too early causing some internal errors. This is now properly guarded for. (github issue 901)

## *Changes to packages in the tools category*

*array*: Correctly identify single-line m-cells

Cells in m-columns that only contain a single line are supposed to behave like single-line p-cells and align at the same baseline. To test for the condition, `array` used to compare the height of the cell to the height of the strut used for the table rows. However, the height of that strut depends on the setting of `\arraystretch` and if you made this negative (or very large) the test came out wrong. Therefore, we now test against the height of a normal strut to ensure that single-line cells are correctly identified as such (unless their content is truly very tall, in which case aligning is pointless anyway).

(*github issue 766*)

## *References*

- [1] Leslie Lamport. *L<sup>A</sup>T<sub>E</sub>X: A Document Preparation System: User's Guide and Reference Manual*. Addison-Wesley, Reading, MA, USA, 2nd edition, 1994. ISBN 0-201-52983-1. Reprinted with corrections in 1996.
- [2] L<sup>A</sup>T<sub>E</sub>X Project Team: *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> news 32*.  
<https://latex-project.org/news/latex2e-news/ltnews32.pdf>
- [3] L<sup>A</sup>T<sub>E</sub>X Project Team: *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> news 34*.  
<https://latex-project.org/news/latex2e-news/ltnews34.pdf>
- [4] L<sup>A</sup>T<sub>E</sub>X Project Team: *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> news 35*.  
<https://latex-project.org/news/latex2e-news/ltnews35.pdf>
- [5] L<sup>A</sup>T<sub>E</sub>X Project Team: *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> font selection*.  
<https://latex-project.org/help/documentation/>