

LATEX Class for the Association for Computing Machinery^{*}

Boris Veytsman[†]

2017/12/14, v1.48

Abstract

This package provides a class for typesetting publications of the Association for Computing Machinery.

Contents

1	Introduction	3
2	User's guide	3
2.1	Installation	3
2.2	Invocation and options	6
2.3	Top matter	7
2.4	Algorithms	20
2.5	Figures and tables	20
2.6	Theorems	22
2.7	Online-only and offline-only material	22
2.8	Note about anonymous mode	22
2.9	Acknowledgments	23
2.10	Bibliography	23
2.11	Colors	26
2.12	Other notable packages and typographic remarks	27
2.13	A note for wizards: <code>acmart-preload-hook.tex</code>	27
3	Implementation	29
3.1	Identification	29
3.2	Preload hook	29
3.3	Options	29
3.4	Setting switches	32

^{*}©2016–2017, Association for Computing Machinery

[†]borisv@lk.net, boris@varphi.com

3.5	Loading the base class and package	33
3.6	Citations	34
3.7	Paper size and paragraphing	40
3.8	Fonts	44
3.9	Floats	45
3.10	Lists	46
3.11	Top-matter data	48
3.12	Concepts system	61
3.13	Copyright system	62
3.14	Typesetting top matter	67
3.15	Headers and Footers	82
3.16	Sectioning	86
3.17	TOC lists	88
3.18	Theorems	88
3.19	Acknowledgments	91
3.20	Conditional typesetting	92
3.21	Additional bibliography commands	92
3.22	End of Class	92

1 Introduction

The Association for Computing Machinery¹ is the world’s largest educational and scientific computing society, which delivers resources that advance computing as a science and a profession. It was one of the early adopters of \TeX for its typesetting.

It provided several different classes for a number of journals and conference proceedings. Unfortunately during the years since these classes were written, the code was patched many times, and supporting different versions of the classes became difficult.

This package provides the uniform interface for all ACM publications. It is intended to replace all the different classes and packages and provide an up-to-date \LaTeX package.

This package uses only free \TeX packages and fonts included in $\text{\TeX}Live$, Mik \TeX and other popular \TeX distributions. It is intended to be published in these distributions itself, which minimizes users’ efforts in the installation and support of this package.

I am grateful to Michael D. Adams, Leif Andersen, Dirk Beyer, Benjamin Byholm, Michael Ekstrand, Matthew Fluet, Paolo G. Giarrusso, Ben Greenman, Jamie Davis, LianTze Lim, Ben Liblit, Kai Mindermann, Frank Mittelbach, Serguei Mokhov, Ross Moore, John Owens, Joel Nider, Tobias Pape, Mathias Rav, Andreas Reichinger, Matteo Riondato, Craig Rodkin, Bernard Rous, David Shamma, Stephen Spencer, Daniel Thomas, Zack Weinberg, John Wickerson and many others for their invaluable help.

The development version of the package is available at <https://github.com/borisveytsman/acmart>.

2 User’s guide

This class uses many commands and customizaton options, so it might appear intimidating for a casual user. Do not panic! Many of these commands and options can be safely left with their default values or the values recommended by your conference or journal editors. If you have problems or questions, do not hesitate to ask me directly or the community at <https://github.com/borisveytsman/acmart>, <https://tex.stackexchange.com> or the closest \TeX Users Group. The world-wide \TeX Users Group is at <https://tug.org/>; please consider joining us if you use \TeX regularly.

2.1 Installation

Most probably, you already have this package installed in your favorite \TeX distribution; if not, you may want to upgrade. You may need to upgrade it anyway since this package uses a number of relatively recent packages, especially the ones related to fonts.

The latest released version of this package can be found on CTAN: <https://www.ctan.org/pkg/acmart>. The development version can be found on GitHub: <https://github.com/borisveytsman/acmart>. At this address you can file a bug report—or even contribute your own enhancement by making a pull request.

Please note that the version on Github is a development (or experimental) version: please download it for testing new features. The production version is the one on CTAN and ACM sites.

¹<http://www.acm.org/>

Most users should not attempt to install this package themselves but should rather rely on their \TeX distributions to provide it. If you decide to install the package yourself, follow the standard rules:

1. Run `latex acmart.ins`. This will produce the file `acmart.cls`
2. Put the files `acmart.cls` and `ACM-Reference-Format.bst` in places where \LaTeX can find them (see [1] or the documentation for your \TeX system).
3. Update the database of file names. Again, see [1] or the documentation for your \TeX system for the system-specific details.
4. The file `acmart.pdf` provides the documentation for the package. (This is probably the file you are reading now.)

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

This class uses a number of other packages. They are included in all major \TeX distributions ($\text{\TeX}Live$, Mac \TeX , Mik \TeX) of 2015 and later, so you probably have them installed. Just in case here is the list of these packages:

- *amscls*, <http://www.ctan.org/pkg/amscls>
- *amsfonts*, <http://www.ctan.org/pkg/amsfonts>
- *amsmath*, <http://www.ctan.org/pkg/amsmath>
- *binhex*, <http://www.ctan.org/pkg/binhex>
- *caption*, <http://www.ctan.org/pkg/caption>
- *comment*, <http://www.ctan.org/pkg/comment>
- *cm-super*, <http://www.ctan.org/pkg/cm-super>
- *cmap*, <http://www.ctan.org/pkg/cmap>
- *draftwatermark*, <http://www.ctan.org/pkg/draftwatermark>
- *environ*, <http://www.ctan.org/pkg/environ>
- *etoolbox*, <http://www.ctan.org/pkg/etoolbox>
- *fancyhdr*, <http://www.ctan.org/pkg/fancyhdr>
- *float*, <http://www.ctan.org/pkg/float>
- *fontaxes*, <http://www.ctan.org/pkg/fontaxes>
- *geometry*, <http://www.ctan.org/pkg/geometry>
- *graphics*, <http://www.ctan.org/pkg/graphics>
- *hyperref*, <http://www.ctan.org/pkg/hyperref>

- *ifluatex*, <http://www.ctan.org/pkg/ifluatex>
- *ifxetex*, <http://www.ctan.org/pkg/ifxetex>
- *inconsolata*, <http://www.ctan.org/pkg/inconsolata>
- *libertine*, <http://www.ctan.org/pkg/libertine>
- *manyfoot*, <http://www.ctan.org/pkg/manyfoot>
- *microtype*, <http://www.ctan.org/pkg/microtype>
- *mmap*, <http://www.ctan.org/pkg/mmap>
- *ms*, <http://www.ctan.org/pkg/ms>
- *mweights*, <http://www.ctan.org/pkg/mweights>
- *natbib*, <http://www.ctan.org/pkg/natbib>
- *nccfoots*, <http://www.ctan.org/pkg/nccfoots>
- *newtx*, <http://www.ctan.org/pkg/newtx>
- *oberdiek*, <http://www.ctan.org/pkg/oberdiek>
- *pdftex-def*, <http://www.ctan.org/pkg/pdftex-def>
- *refcount*, <http://www.ctan.org/pkg/refcount>
- *setspace*, <http://www.ctan.org/pkg/setspace>
- *textcase*, <http://www.ctan.org/pkg/textcase>
- *totpages*, <http://www.ctan.org/pkg/totpages>
- *trimspaces*, <http://www.ctan.org/pkg/trimspaces>
- *upquote*, <http://www.ctan.org/pkg/upquote>
- *url*, <http://www.ctan.org/pkg/url>
- *xcolor*, <http://www.ctan.org/pkg/xcolor>
- *xkeyval*, <http://www.ctan.org/pkg/xkeyval>
- *xstring*, <http://www.ctan.org/pkg/xstring>

2.2 Invocation and options

To use this class, put in the preamble of your document

```
\documentclass[<options>]{acmart}
```

There are several options corresponding to the type of the document and its general appearance. They are described below. Generally speaking, the options have key=value forms, for example,

```
\documentclass[format=acmsmall, screen=true, review=false]{acmart}
```

The option `format` describes the format of the output. There are several possible values for this option, for example,

```
\documentclass[format=acmtog]{acmart}
```

Actually the words `format=` can be omitted, e.g.,

```
\documentclass[acmtog, review=false]{acmart}
```

The possible formats are listed in Table 1. Note that formats starting with `acm` are intended for journals and transactions, while formats starting with `sig` are intended for proceedings published as books.

Note that sometimes conference proceedings are published as a special issue (or issues) of an ACM journal. In this case, you should use the journal format for a conference paper. Please contact your conference committee if in doubt.

There are several Boolean options that can take `true` or `false` values. They are listed in Table 2. The words `=true` can be omitted when setting a Boolean option, so instead of `screen=true` one can write just `screen`, for example,

```
\documentclass[acmsmall, screen, review]{acmart}
```

The option `review` is useful when combined with the `manuscript` format option. It provides a version suitable for reviewers and copy editors.

The default for the option `screen` depends on the publication. At present it is `false` for all publications *but* PACM, since PACM is now electronic-only. Thus PACM titles (see Table 3) set this option to `true`. In the future this option may involve additional features suitable for on-screen versions of articles.

The option `natbib` is used when the corresponding `BIBTEX` style is based on `natbib`. In most cases you do not need to set it. See Section 2.10.

The option `anonymous` is used for anonymous review processes and causes all author information to be obscured.

The option `timestamp` is used to include a time stamp in the footer of each page. When preparing a document, this can help avoid confusing different revisions. The footer also includes the page range of the document. This helps detect missing pages in hard copies.

Table 1: The possible values for the `format` option

Value	Meaning
<code>manuscript</code>	A manuscript. This is the default.
<code>acmsmall</code>	Small single-column format. Used for CIE, CSUR, JACM, JDIQ, JEA, JERIC, JETC, PACMHCI, PACMPL, TAAS, TACCESS, TACO, TALG, TALLIP (formerly TALIP), TCPS, TEAC, TECS, THRI, TIIS, TISSEC, TIST, TKDD, TMIS, TOCE, TOCHI, TOCL, TOCS, TOCT, TODAES, TODS, TOIS, TOIT, TOMACS, TOMM (formerly TOMCCAP), TOMPECS, TOMS, TOPC, TOPLAS, TOPS, TOS, TOSEM, TOSN, TRETS, TSAS, TSC, TSLP and TWEB, including special issues.
<code>acmlarge</code>	Large single-column format. Used for IMWUT, JOCCH, POMACS and TAP, including special issues.
<code>acmtog</code>	Large double-column format. Used for TOG, including annual conference Technical Papers.
<code>sigconf</code>	Proceedings format for most ACM conferences (with the exceptions listed below) and all ICPS volumes.
<code>sigplan</code>	Proceedings format for SIGPLAN conferences.
<code>sigchi</code>	Proceedings format for SIGCHI conferences.
<code>sigchi-a</code>	Format for SIGCHI extended abstracts.

The option `authordraft` is intended for author’s drafts that are not intended for distribution. It typesets a copyright block to give the author an idea of its size and the overall size of the paper but overprints it with the phrase “Unpublished working draft. Not for distribution.”, which is also used as a watermark. This option sets `timestamp` and `review` to `true`, but these can be overridden by setting these options to `false` after setting `authordraft` to `true`.

2.3 Top matter

A number of commands set up *top matter* or (in computer science jargon) *metadata* for an article. They establish the publication name, article title, authors, DOI and other data. Some of these commands, like `\title` and `\author`, should be put by the authors. Others, like `\acmVolume` and `\acmDOI`—by the editors. Below we describe these commands and mention who should issue them. These macros should be used *before* the `\maketitle` command. Note that in previous versions of ACM classes some of these commands should be used before `\maketitle`, and some after it. Now they all must be used before `\maketitle`.

This class internally loads the `amsart` class, so many top-matter commands are inherited from `amsart` [2].

`\acmJournal` The macro `\acmJournal{<shortName>}` sets the name of the journal or transaction for journals and transactions. The argument is the short name of the publication *in uppercase*, for example,

```
\acmJournal{TOMS}
```

Table 2: Boolean options

Option	Default	Meaning
review	false	A review version: lines are numbered and hyperlinks are colored
screen	see text	A screen version: hyperlinks are colored
natbib	true	Whether to use the natbib package (see Section 2.10)
anonymous	false	Whether to make author(s) anonymous
authorversion	false	Whether to generate a special version for the authors' personal use or posting (see Section 2.3)
timestamp	false	Whether to put a time stamp in the footer of each page
authordraft	false	Whether author's-draft mode is enabled
acmthm	true	Whether to define theorem-like environments, see Section 2.6

The currently recognized journals are listed in Table 3. Note that conference proceedings published in *book* form do not set this macro.

It is expected that this command is inserted by the author of the manuscript when she decides to which journal to submit the manuscript.

\acmConference

The macro \acmConference[<short name>]{<name>}{<date>}{<venue>} is used for conference proceedings published in the book form. The arguments are the following:

short name: the abbreviated name of the conference (optional).

name: the name of the conference.

date: the date(s) of the conference.

venue: the place of the conference.

Examples:

```
\acmConference[TD'15]{Technical Data Conference}{November  
12--16}{Dallas, TX, USA}  
\acmConference{SA'15 Art Papers}{November 02--06, 2015}{Kobe, Japan}
```

\acmBooktitle

By default we assume that conference proceedings are published in the book named *Proceedings of CONFERENCE*, where CONFERENCE is the name of the conference inferred from the command \acmConference above. However, sometimes the book title is different. The command \acmBooktitle can be used to set this title, for example,

```
\acmBooktitle{Companion to the first International Conference on the  
Art, Science and Engineering of Programming (Programming '17)}
```

Table 3: ACM publications and arguments of the \acmJournal command

Abbreviation	Publication
CIE	ACM Computers in Entertainment
CSUR	ACM Computing Surveys
IMWUT	PACM on Interactive, Mobile, Wearable and Ubiquitous Technologies
JACM	Journal of the ACM
JDIQ	ACM Journal of Data and Information Quality
JEA	ACM Journal of Experimental Algorithms
JERIC	ACM Journal of Educational Resources in Computing
JETC	ACM Journal on Emerging Technologies in Computing Systems
JOCCH	ACM Journal on Computing and Cultural Heritage
PACMHCI	PACM on Human-Computer Interaction
PACMPL	PACM on Programming Languages
POMACS	PACM on Measurement and Analysis of Computing Systems
TAAS	ACM Transactions on Autonomous and Adaptive Systems
TACCESS	ACM Transactions on Accessible Computing
TACO	ACM Transactions on Architecture and Code Optimization
TALG	ACM Transactions on Algorithms
TALLIP	ACM Transactions on Asian and Low-Resource Language Information Processing
TAP	ACM Transactions on Applied Perception
TCPS	ACM Transactions on Cyber-Physical Systems
TEAC	ACM Transactions on Economics and Computation
TECS	ACM Transactions on Embedded Computing Systems
THRI	ACM Transactions on Human-Robot Interaction
TIIS	ACM Transactions on Interactive Intelligent Systems
TISSEC	ACM Transactions on Information and System Security
TIST	ACM Transactions on Intelligent Systems and Technology
TKDD	ACM Transactions on Knowledge Discovery from Data
TMIS	ACM Transactions on Management Information Systems
TOCE	ACM Transactions on Computing Education
TOCHI	ACM Transactions on Computer-Human Interaction
TOCL	ACM Transactions on Computational Logic
TOCS	ACM Transactions on Computer Systems
TOCT	ACM Transactions on Computation Theory
TODAES	ACM Transactions on Design Automation of Electronic Systems
TODS	ACM Transactions on Database Systems
TOG	ACM Transactions on Graphics
TOIS	ACM Transactions on Information Systems
TOIT	ACM Transactions on Internet Technology
TOMACS	ACM Transactions on Modeling and Computer Simulation
TOMM	ACM Transactions on Multimedia Computing, Communications and Applications
TOMPECS	ACM Transactions on Modeling and Performance Evaluation of Computing Systems
TOMS	ACM Transactions on Mathematical Software
TOPC	ACM Transactions on Parallel Computing
TOPLAS	ACM Transactions on Programming Languages and Systems
TOPS	ACM Transactions on Privacy and Security
TOS	ACM Transactions on Storage
TOSEM	ACM Transactions on Software Engineering and Methodology
TOSN	ACM Transactions on Sensor Networks
TRETS	ACM Transactions on Reconfigurable Technology and Systems
TSAS	ACM Transactions on Spatial Algorithms and Systems
TSC	ACM Transactions on Social Computing
TSLP	ACM Transactions on Speech and Language Processing
TWEB	ACM Transactions on the Web

\editor In most cases, conference proceedings are edited. You can use the command \editor{\{*editor*\}} to set the editor of the volume. This command can be repeated, for example,

```
\editor{Jennifer B. Sartor}
\editor{Theo D'Hondt}
\editor{Wolfgang De Meuter}
```

\title The command \title, as in the amsart class, has two arguments: one optional, and one mandatory:

```
\title[<ShortTitle>]{<FullTitle>}
```

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

It is expected that this command is inserted by the author of the manuscript.

\subtitle Besides title, ACM classes allow a subtitle, set with the \subtitle{\{*subtitle*\}} macro.

The commands for specifying authors are highly structured. The reason is they serve double duty: the authors' information is typeset in the manuscript *and* is used by the metadata extraction tools for indexing and cataloguing. Therefore it is very important to follow the guidelines exactly.

\author \orcid \affiliation \email The basic commands are \author, \orcid (for the researchers registered with ORCID, <http://www.orcid.org/>), \affiliation and \email. In the simplest case, you enter them in this order:

```
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
```

Do *not* use the L^AT_EX \and macro! Each author deserves his or her own \author command.

Note that some formats do not typeset e-mails or ORCID identifiers. Do not worry: the metadata tools will get them.

Sometimes an author has several affiliations. In this case, the \affiliation command should be repeated:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
```

Similarly you can repeat the \email command.

You may have several authors with the same affiliation, different affiliations, or overlapping affiliations (author A_1 is affiliated with institutions I_1 and I_2 , while author A_2 is

affiliated with I_2 only, author A_3 is affiliated with I_1 and I_3 , etc.). The recommended solution is to put the \affiliation commands after each author, possibly repeating them:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
@email{...}
\author{...}
\orcid{...}
\affiliation{...}
@email{...}
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
@email{...}
```

In some cases, when several authors share the same affiliation, you can try to save space using the format

```
\author{...}
@email{...}
\author{...}
@email{...}
\affiliation{...}
```

However, this format is not generally recommended.

\additionalaffiliation
In some cases, too many affiliations can take too much space. The command \additionalaffiliation{\langle affiliation\rangle} creates a footnote after an author's name with the words "Also with {\langle affiliation\rangle}." You should use this command only as a last resort. An example of usage is:

```
\author{G. Tobin}
\author{Ben Trovato}
\additionalaffiliation{%
  \institution{The Th\o rv\aa ld Group}
  \streetaddress{1 Th\o rv\aa ld Circle}
  \city{Hekla}
  \country{Iceland}}
\affiliation{%
  \institution{Institute for Clarity in Documentation}
  \streetaddress{P.O. Box 1212}
  \city{Dublin}
  \state{Ohio}
  \postcode{43017-6221}}
```

Here Trovato and Tobin share their affiliation with the Institute for Clarity in Documentation, but only Ben Trovato is affiliated with The Thørváld Group.

```
\position  
\institution  
\department  
\streetaddress  
    \city  
    \state  
\postcode  
\country
```

The `\affiliation` and `\additionalaffiliation` commands are further structured to interact with the metadata extraction tools. Inside these commands you should use the `\position`, `\institution`, `\department`, `\city`, `\streetaddress`, `\state`, `\postcode` and `\country` macros to indicate the corresponding parts of the affiliation. Note that in some cases (for example, journals) these parts are not printed in the resulting copy, but they *are* necessary since they are used by the XML metadata extraction programs. Do *not* put commas or `\\"` between the elements of `\affiliation`. They will be provided automatically.

An example of the author block:

```
\author{A. U. Thor}  
\orcid{1234-4564-1234-4565}  
\affiliation{  
    \institution{University of New South Wales}  
    \department{School of Biomedical Engineering}  
    \streetaddress{Samuels Building (F25), Kensington Campus}  
    \city{Sidney}  
    \state{NSW}  
    \postcode{2052}  
    \country{Australia}}  
\email{author@nsw.au.edu}  
\author{A. N. Other}  
\affiliation{  
    \institution{University of New South Wales}  
    \city{Sidney}  
    \state{NSW}  
    \country{Australia}}  
\author{C. O. Respondent}  
\orcid{1234-4565-4564-1234}  
\affiliation{  
    \institution{University of Pennsylvania}  
    \city{Philadelphia}  
    \state{PA}  
    \country{USA}}  
\affiliation{  
    \institution{University of New South Wales}  
    \city{Sidney}  
    \state{NSW}  
    \country{Australia}}
```

Note that the old ACM conference formats did not allow more than six authors and required some effort from authors to achieve alignment. The new format is much better in this.

Sometimes an author works in several departments within the same institution. There could be two situations: the departments are independent, or one department is within another. In the first case, just repeat the command `\department` several times. To handle

the second case the command has an optional numerical parameter. The departments with higher numbers are higher in the organizational chart. Compare

```
\affiliation{%
  \department[0]{Department of Lunar Studies} % 0 is the default
  \department[1]{John Doe Institute} % higher than 0
  \institution{University of San Serriffe}
  \country{San Serriffe}}
```

and

```
\affiliation{%
  \department{Department of Lunar Studies} % Not in the John Doe Institute!
  \department{John Doe Institute}
  \institution{University of San Serriffe}
  \country{San Serriffe}}
```

The command `\affiliation` formats its output according to American conventions. This might be wrong for some cases. Consider, for example, a German address. In Germany, the postcode is put before the city and is not separated by a comma. We can handle this order using

```
\affiliation{%
  \institution{Fluginstitut}
  \streetaddress{Sonnenallee 17}
  \postcode{123456}
  \city{Helm}
  \country{Germany}}
```

However, the comma after the postcode is unfortunate: the address will be typeset (in some formats) as

```
Fluginstitut
Sonnenallee 17
123456, Helm, Germany
```

To overcome this problem, the command `\affiliation` has an optional parameter `obeypunctuation`, which can be `false` (the default) or `true`. If this parameter is `true`, `\affiliation` obeys the author's command. Thus

```
\affiliation[obeypunctuation=true]{%
  \institution{Fluginstitut} \\
  \streetaddress{Sonnenallee 17} \\
  \postcode{123456} \\
  \city{Helm}, \\
  \country{Germany}}
```

will be typeset as

```
Fluginstitut  
Sonenallee 17  
123456 Helm, Germany
```

Note that you should *not* use this option for journals.

It is expected that these commands are inserted by the author of the manuscript.

Like `amsart` (and unlike standard L^AT_EX), we allow `\thanks` only *outside* of the commands `\title` and `\author`. This command is obsolete and should *not* be used in most cases. Do not list your acknowledgments or grant sponsors here. Put this information in the `acks` environment (see Section 2.9).

`\authorsaddresses` In some formats, addresses are printed as a footnote on the first page. By default L^AT_EX typesets them itself using the information you give it. However, you can override its choice using the command `\authorsaddresses{<contact addresses>}`, for example,

```
\authorsaddresses{%
  Authors' addresses: G.~Zhou, Computer Science Department, College of
  William and Mary, 104 Jameson Rd, Williamsburg, PA 23185, US;
  V.~B'eranger, Inria Paris-Rocquencourt, Rocquencourt, France;
  A.~Patel, Rajiv Gandhi University, Rono-Hills, Doimukh, Arunachal
  Pradesh, India; H.~Chan, Tsinghua University, 30 Shuangqing Rd,
  Haidian Qu, Beijing Shi, China; T.~Yan, Eaton Innovation Center,
  Prague, Czech Republic; T.~He, C.~Huang, J.~A.~Stankovic University
  of Virginia, School of Engineering Charlottesville, VA 22903, USA;
  T. F. Abdelzaher, (Current address) NASA Ames Research Center,
  Moffett Field, California 94035.}
```

You can *suppress* printing authors' addresses by setting them to an empty string: `\authorsaddresses{}`.

`\titlenote` `\subtitlenote` `\authornote` While the command `\thanks` generates a note without a footnote mark, sometimes the authors might need notes more tightly connected to the title, subtitle or author. The commands `\titlenote`, `\subtitlenote` and `\authornote` that follow the corresponding commands (`\title`, `\subtitle` and `\author`) generate such notes. For example,

```
\title{This is a title}
\titlenote{This is a titlenote}
\author{A. U. Thor}
\authornote{This is an authornote}
```

Please never use a `\footnote` inside an `\author` or `\title` command since this confuses the metadata extraction software. (Actually these commands now produce errors.)

`\authornotemark` Sometimes one may need to have the same footnote connected to several authors. The command `\authornotemark[<number>]` adds just the footnote mark, for example,

```
\author{A. U. Thor}
\authornote{Both authors contributed equally to the paper}
```

```
...  
\author{A. N. Other}  
\authornotemark[1]
```

The correct numbering of these marks is the responsibility of the user.

The macros `\acmVolume`, `\acmNumber`, `\acmArticle`, `\acmYear` and `\acmMonth` are inserted by the editor and set the journal volume, issue, article number, year and month correspondingly. The arguments of all these commands, including `\acmMonth`, is numerical. For example,

```
\acmVolume{9}  
\acmNumber{4}  
\acmArticle{39}  
\acmYear{2010}  
\acmMonth{3}
```

Note that `\acmArticle` is used not only for journals but also for some conference proceedings.

`\acmArticleSeq`

The articles in the same issue of a journal have a *sequence number*. It is used to vertically position the black blob on the first page of some formats. By default it is the same as the article number, but the command `\acmArticleSeq{<n>}` can be used to change it:

```
\acmArticle{39} % The sequence number will be 39 by default  
\acmArticleSeq{5} % We redefine it to 5
```

Setting this number to zero suppresses the blob.

`\acmSubmissionID`

If your paper got a Submission ID from the Conference Management System, put it here:

```
\acmSubmissionID{123-A56-BU3}
```

`\acmPrice`

The macro `\acmPrice{<price>}` sets the price for the article, for example,

```
\acmPrice{25.00}
```

Note that you do not need to put the dollar sign here, just the amount. By default the price is \$15.00, unless the copyright is set to usgov or rightsretained, when it is suppressed. Note that to override the defaults you need to set the price *after* the `\setcopyright` command. Also, the command `\acmPrice{}` suppresses the printing of the price.

`\acmISBN`

Book-like volumes have ISBN numbers attached to them. The macro `\acmISBN{<ISBN>}` sets it. Normally it is set by the typesetter, for example,

```
\acmISBN{978-1-4503-3916-2}
```

\acmDOI Setting it to the empty string, as \acmISBN{}, suppresses printing the ISBN.
The macro \acmDOI{\textit{DOI}} sets the DOI of the article, for example,

```
\acmDOI{10.1145/9999997.9999999}
```

\acmBadgeR It is normally set by the typesetter. Setting it to the empty string, as \acmDOI{}, suppresses the DOI.
\acmBadgeL Some conference articles get special distinctions, for example, the artifact evaluation
for PPoPP 2016 (see <http://ctuning.org/ae/ppopp2016.html>). These articles display
special badges supplied by the conference organizers. This class provides commands to
add these badges: \acmBadgeR[\textit{url}]\{\textit{graphics}\} and \acmBadgeL[\textit{url}]\{\textit{graphics}\}.
The first command puts the badge to the right of the title, and the second one—to the
left. The exception is the sigchi-a mode for SIGCHI extended abstracts, which puts
the badges on the left margin. The arguments have the following meaning: [\textit{url}], if
provided, sets the link to the badge authority in the screen version, while {\textit{graphics}}
sets the graphics file with the badge image. The file must be a cropped square, which is
scaled to a standard size in the output. For example, if the badge image is ae-logo.pdf,
the command is

```
\acmBadgeR[http://ctuning.org/ae/ppopp2016.html]{ae-logo}
```

\startPage The macro \startPage{\textit{page}} sets the first page of the article in a journal or book.
It is used by the typesetter.
\terms The command \keywords{\textit{keyword}, \textit{keyword}, ...} sets keywords for the article.
\keywords They must be separated by commas, for example,

```
\keywords{wireless sensor networks, media access control,  
multi-channel, radio interference, time synchronization}
```

\CCSXML ACM publications are classified according to the ACM Computing Classification
\ccsdesc Scheme (CCS). CCS codes are used both in the typeset version of the publications *and* in
the metadata in various databases. Therefore you need to provide both TeX commands
and XML metadata with the paper.

The tool at <http://dl.acm.org/ccs.cfm> can be used to generate CCS codes. After
you select the topics, click on “Generate CCS codes” to get results like the following:

```
\begin{CCSXML}  
<ccs2012>  
  <concept>  
    <concept_id>10010520.10010553.10010562</concept_id>  
    <concept_desc>Computer systems organization~Embedded systems</concept_desc>  
    <concept_significance>500</concept_significance>  
  </concept>  
  <concept>  
    <concept_id>10010520.10010575.10010755</concept_id>  
    <concept_desc>Computer systems organization~Redundancy</concept_desc>  
    <concept_significance>300</concept_significance>
```

```

    </concept>
<concept>
<concept_id>10010520.10010553.10010554</concept_id>
<concept_desc>Computer systems organization~Robotics</concept_desc>
<concept_significance>100</concept_significance>
</concept>
<concept>
<concept_id>10003033.10003083.10003095</concept_id>
<concept_desc>Networks~Network reliability</concept_desc>
<concept_significance>100</concept_significance>
</concept>
</ccs2012>
\end{CCSXML}

\ccsdesc[500]{Computer systems organization~Embedded systems}
\ccsdesc[300]{Computer systems organization~Redundancy}
\ccsdesc{Computer systems organization~Robotics}
\ccsdesc[100]{Networks~Network reliability}

```

You just need to copy this code and paste it in your paper anywhere before `\maketitle`.

`\setcopyright`

There are several possibilities for the copyright of the papers published by the ACM: the authors may transfer the rights to the ACM, license them to the ACM, some or all authors might be employees of the US or Canadian governments, etc. Accordingly the command `\setcopyright{...}` is introduced. Its argument is the copyright status of the paper, for example, `\setcopyright{acmcopyright}`. The possible values for this command are listed in Table 4.

The ACM submission software should generate the right command for you to paste into your file.

`\copyrightyear`

Each copyright statement must have the year of copyright. By default it is the same as `\acmYear`, but you can override this using the macro `\copyrightyear`, e.g.,

```

\acmYear{2016}
\copyrightyear{2015}

```

There is a special case for a personal copy that the authors may be allowed to generate for their use or a posting on a personal site (check the instructions for the specific journal or conference for the details). The document option `authorversion=true` produces a special form of the copyright statement for this case. Note that you still need the `\setcopyright` command and (optionally) `\copyrightyear` command to tell `\TeX` about the copyright owner and year. Also, you should be aware that due to the different sizes of the permission blocks for the printed version and authors' version, the page breaks might be different between them.

`abstract`

The environment `abstract` must precede the `\maketitle` command. Again, this is different from the standard `\TeX`.

`teaserfigure`

A special kind of figure is used for many two-column conference proceedings.

Table 4: Parameters for the `\setcopyright` command

Parameter	Meaning
<code>none</code>	The copyright and permission information is not typeset. (This is the option for some ACM conferences.)
<code>acmcopyright</code>	The authors transfer the copyright to the ACM (the “traditional” choice).
<code>acmlicensed</code>	The authors retain the copyright but license the publication rights to the ACM.
<code>rightsretained</code>	The authors retain the copyright and publication rights to themselves or somebody else.
<code>usgov</code>	All the authors are employees of the US government.
<code>usgovmixed</code>	Some authors are employees of the US government.
<code>cagov</code>	All the authors are employees of the Canadian government.
<code>cagovmixed</code>	Some authors are employees of the Canadian government.
<code>licensedusgovmixed</code>	Some authors are employees of the US government, and the publication rights are licensed to the ACM.
<code>licensedcagov</code>	All the authors are employees of the Canadian government, and the publication rights are licensed to the ACM.
<code>licensedcagovmixed</code>	Some authors are employees of the Canadian government, and the publication rights are licensed to the ACM.
<code>othergov</code>	Authors are employees of a government other than the US or Canada.
<code>licensedothergov</code>	Authors are employees of a government other than the US or Canada, and the publication rights are licensed to the ACM.
<code>iw3c2w3</code>	Special statement for conferences organized by IW3C2.
<code>iw3c2w3g</code>	Special statement for conferences organized by IW3C2, when some authors are approved Google employees.

Table 5: Settings for the \settopmatter command

Parameter	Values	Meaning
printccs	true/false	Whether to print CCS categories
printacmref	true/false	Whether to print the ACM bibliographic entry
printfolios	true/false	Whether to print page numbers (folios)
authorsperrow	numeric	Number of authors per row for the title page in conference proceedings formats

This figure is placed just after the authors but before the main text. The environment `teaserfigure` is used for these figures. This environment must be used *before* `\maketitle`, for example,

```
\begin{teaserfigure}
\includegraphics[width=\textwidth]{sampleteaser}
\caption{This is a teaser}
\label{fig:teaser}
\end{teaserfigure}
```

`\settopmatter` Some information in the top matter is printed for certain journals or proceedings and suppressed for others. You can override these defaults using the command `\settopmatter{<settings>}`. The settings and their meanings are listed in Table 5. For example,

```
\settopmatter{printacmref=false, printccs=true, printfolios=true}
```

The parameter `authorsperrow` requires some explanation. In conference proceedings authors' information is typeset in boxes, several boxes per row (see `sample-sigconf.pdf`, `sample-sigplan.pdf`, etc.). The number of boxes per row is determined automatically. If you want to override this, you can do it using this parameter, for example,

```
\settopmatter{authorsperrow=4}
```

However, in most cases you should *not* do this and should use the default settings. Setting `authorsperrow` to 0 will revert it to the default settings.

`\received` The command `\received[<stage>]{<date>}` sets the history of the publication. The `[<stage>]` argument is optional; the default is Received for the first date and revised for the subsequent ones. For example,

```
\received{February 2007}
\received[revised]{March 2009}
\received[accepted]{June 2009}
```

`\maketitle` The macro `\maketitle` must be the last command in the top-matter group. That is

`\shortauthors` it must follow the commands defined in this section.

After the command `\maketitle`, the macro `\shortauthors` stores the names of the authors for the running head. You can redefine it if the list of author's name is too long, e.g.,

```
\maketitle  
\renewcommand{\shortauthors}{Zhou et al.}
```

2.4 Algorithms

There are now several good packages for typesetting algorithms [3, 4, 5], and the authors are free to choose their favorite one.

2.5 Figures and tables

The new ACM styles use the standard L^AT_EX interface for figures and tables. There are some important items to be aware of, however.

1. The captions for figures must be entered *after* the figure bodies and for tables *before* the table bodies.

2. The ACM uses the standard types for figures and tables and adds several new ones. In total there are the following types:

figure, table: a standard figure or table taking a full text width in one-column formats and one column width in two-column formats.

figure*, table* in two-column formats, a special figure or table taking a full text width.

teaserfigure: a special figure before `\maketitle`.

sidebar, marginfigure, marginable: in the sigchi-a format, special sidebars, tables and figures in the margin.

3. Accordingly, when scaling images, one should use the following sizes:

- (a) For `teaserfigure`, `figure` in one-column mode or `figure*` in two-column mode, use `\textwidth`. In one-column mode, you can also use `\columnwidth`, which coincides with `\textwidth` in this case.
- (b) For `figure` in two-column mode, use `\columnwidth`.
- (c) For `marginfigure`, use `\marginparwidth`.
- (d) For `figure*` in SIGCHI extended abstracts, use `\fulltextwidth`.

It is strongly recommended to use the package `booktabs` [6] and follow its main principles of typography with respect to tables:

1. Never, ever use vertical rules.
2. Never use double rules.

It is also a good idea not to overuse horizontal rules.

For table *footnotes* you have several options described in the TeX FAQ [1]. The simplest one is to use a `\minipage` environment:

```
\begin{table}
\caption{Simulation Configuration}
\label{tab:conf}
\begin{minipage}{\columnwidth}
\begin{center}
\begin{tabular}{ll}
\toprule
TERRAIN\footnote{This is a table footnote. This is a table footnote. This is a table footnote.} & \\
(200\,,m$\times$200\,,m) Square\\
Node Number & 289\\
Node Placement & Uniform\\
Application & Many-to-Many/Gossip CBR Streams\\
Payload Size & 32 bytes\\
Routing Layer & GF\\
MAC Layer & CSMA/MMSN\\
Radio Layer & RADIO-ACCNOISE\\
Radio Bandwidth & 250Kbps\\
Radio Range & 20m--45m\\
\bottomrule
\end{tabular}
\end{center}
\bigskip
\footnotesize\emph{Source:} This is a table
sourcenote. This is a table sourcenote. This is a table
sourcenote.

\emph{Note:} This is a table footnote.
\end{minipage}
\end{table}
```

`sidebar`
`marginfigure`
`margintable` SIGCHI extended abstracts use margin space extensively. This package provides three environments for this with optional captions:

sidebar: textual information in the margin

marginfigure: a figure in the margin

margintable: a table in the margin

Tables and figures (including margin tables and margin figures) are by default centered. However, in some cases (for example, when you use several subimages per figure) you may need to override this. A good way to do so is to put the contents into a `\minipage` of the width `\columnwidth`.

2.6 Theorems

The ACM classes define two theorem styles and several pre-defined theorem environments:

acmplain: this is the style used for theorem, conjecture, proposition, lemma and corollary, and

acmdefinition: this is the style used for example and definition.

These environments are defined by default. In the unusual circumstance that a user does not wish to have these environments defined, the option `acmthm=false` in the preamble will suppress them.

2.7 Online-only and offline-only material

`printonly`
`screenonly` Some supplementary material in ACM publications is put online but not in the printed version. The text inside the environment `screenonly` will be typeset only when the option `screen` (see Section 2.2) is set to true. Conversely, the text inside the environment `printonly` is typeset only when this option is set to false. For example,

```
\section{Supplementary materials}

\begin{printonly}
    Supplementary materials are available in the online version of this paper.
\end{printonly}

\begin{screenonly}
    (The actual supplementary materials.)
\end{screenonly}
```

We use the `comment` package for typesetting this code, so `\begin{...}` and `\end{...}` should start on a line of their own with no leading or trailing spaces.

2.8 Note about anonymous mode

`anonsuppress` When the option `anonymous` is selected, TeX suppresses author information (including the number of authors) for a blind review. However, sometimes the information identifying the authors may be present in the body of the paper. For example,

```
\begin{anonsuppress}
    This is the continuation of the previous work by the author
    \cite{prev1, prev2}.
\end{anonsuppress}
```

As for the `printonly` and `screenonly` environments, `\begin{anonsuppress}` and `\end{anonsuppress}` should start on a line of their own with no leading or trailing spaces.

2.9 Acknowledgments

The traditional “Acknowledgments” section is conventionally used to thank persons and granting agencies for their help and support. However, there are several important considerations about this section.

First, in anonymous mode this section must be omitted: it gives too much information to reviewers. Second, data about grants is extracted and stored separately by the postprocessing software. ACM classes provide facilities for both these tasks.

The environment `acks` starts an unnumbered section “Acknowledgments” unless the anonymous mode is chosen. Put all thanks inside this environment.

As for the `printonly` and `screenonly` environments, `\begin{acks}` and `\end{acks}` should start on a line of their own with no leading or trailing spaces.

All financial support *must* be listed using the commands `\grantsponsor` and `\grantnum`. These commands tell the postprocessing software about the granting organization and grant. The format of these commands is the following:

```
\grantsponsor{\langle sponsorID \rangle}{\langle name \rangle}{\langle url \rangle}
\grantnum[\langle url \rangle]{\langle sponsorID \rangle}{\langle number \rangle}.
```

Here `\langle sponsorID \rangle` is the unique ID used to match grants to sponsors, `\langle name \rangle` is the name of the sponsor, `\langle url \rangle` is its URL, and `\langle number \rangle` is the grant number. The `\langle sponsorID \rangle` of the `\grantnum` command must correspond to the `\langle sponsorID \rangle` of a `\grantsponsor` command. Some awards have their own web pages, which you can include using the optional argument of the `\grantnum` command.

At present `\langle sponsorID \rangle` is chosen by the authors and can be an arbitrary key in the same way the label of a `\cite` is arbitrarily chosen. There might be a change to this policy if the ACM decides to create a global database of sponsoring organizations.

Example:

```
\begin{acks}
The authors would like to thank Dr. Yuhua Li for providing the
matlab code of the \textit{BEPs} method.

The authors would also like to thank the anonymous referees for
their valuable comments and helpful suggestions. This work is
supported by the \grantsponsor{GS501100001809}{National Natural
Science Foundation of
China}{\url{https://doi.org/10.13039/501100001809}} under Grant
No.: \grantnum{GS501100001809}{61273304}
and \grantnum[\url{http://www.nnsf.cn/youngscientists}]{GS501100001809}{Young
Scientists' Support Program}.
\end{acks}
```

2.10 Bibliography

The ACM uses the `natbib` package for formatting references and the Bib_TE_X style file `ACM-Reference-Format.bst` for Bib_TE_X processing. You can disable loading of `natbib` using the option `natbib=false` in `\documentclass`. However, it is not recommended,

as well as the use of Bib_TE_X styles other than ACM-Reference-Format.bst, and may delay the processing of the manuscript.

\citetstyle If you use natbib, you can select one of two predefined citation styles using the command \citetstyle: the author-year format acmauthoryear or the numeric format acmnumeric. For example,

```
\citetstyle{acmauthoryear}
```

Note that numeric citations are the default mode for most formats.

\setcitetstyle You can further customize natbib using the \setcitetstyle command, for example,

```
\setcitetstyle{numbers,sort&compress}
```

If you use natbib, then commands like \citep and \citeauthor are automatically supported. The command \shortcite is the same as \cite in numerical mode and cites the year in author-date mode.

Note that before version 1.48 the command \citeyear put the year in parentheses. In version 1.48 and later it produces just the year; the command \citeyearpar can be used to emulate its old behavior.

There are several customized Bib_TE_X entry types and fields in the ACM style file ACM-Reference-Format.bst that you may want to be aware of.

The style supports the fields doi and url, for example,

```
doi = "10.1145/1188913.1188915",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.pdf",
```

The style supports the arXiv-recommended fields eprint and (optionally) primaryclass, for example,

```
eprint = "960935712",
primaryclass = "cs",
```

See the examples at <http://arxiv.org/hypertex/bibstyles/>.

There are the special entry types online and game for Web pages and games, for example,

```
@online{Thornburg01,
author = "Harry Thornburg",
year = "2001",
title = "Introduction to Bayesian Statistics",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.html",
month = mar,
lastaccessed = "March 2, 2005",
}
```

For these entry types you can use the `lastaccessed` field to add the access date for the URL.

There are two ways to enter video or audio sources in the bibliography corresponding to two different possibilities. For standalone sources available online, you can use an `online` entry and set its `howpublished` field. For example,

```
@online{Obama08,
    author = "Barack Obama",
    year = "2008",
    title = "A more perfect union",
    howpublished = "Video",
    day = "5",
    url = "http://video.google.com/videoplay?docid=6528042696351994555",
    month = mar,
    lastaccessed = "March 21, 2008",
}
```

For sources available as attachments to conference proceedings and similar documents, you can use the usual `inproceedings` entry type and set its `howpublished` field:

```
@Inproceedings{Novak03,
    author = "Dave Novak",
    title = "Solder man",
    booktitle = "ACM SIGGRAPH 2003 Video Review on Animation theater Program",
    year = "2003",
    publisher = "ACM Press",
    address = "New York, NY",
    pages = "4",
    month = "March 21, 2008",
    doi = "10.9999/woot07-S422",
    howpublished = "Video",
}
```

Sometimes you need to cite a complete issue of a journal. The `periodical` entry type is intended for this:

```
@periodical{JCohen96,
    key = "Cohen",
    editor = "Jacques Cohen",
    title = "Special issue: Digital Libraries",
    journal = "Communications of the {ACM}",
    volume = "39",
    number = "11",
    month = nov,
    year = "1996",
}
```

If you do not know the year of publication, the style will add “[n. d.]” (for “no date”) to the entry.

If you do not know the author (this is often the case for online entries), use the key field to add a key for sorting and citations, for example,

```
@online{TUGInstmem,  
key = {TUG},  
year = 2017,  
title = "Institutional members of the {\TeX} Users Group",  
url = "http://www.tug.org/instmem.html",  
lastaccessed = "May 27, 2017",  
}
```

2.11 Colors

While printed ACM publications are usually black and white, screen mode allows the use of colors. The ACM classes pre-define several colors according to [7]: ACMBlue, ACMYellow, ACMOrange, ACMRed, ACMLightBlue, ACMGreen, ACMPurple and ACMDarkBlue. You can use them in color assignments.

The ACM provides the following recommendation on color use.

The most accessible approach would be to ensure that your article is still readable when printed in greyscale. The most notable reasons for this are:

1. The most common type of inherited Color Vision Deficiency (CVD) is red-green (in which similar-brightness colors that differ only in their amounts of red or green are often confused), and it affects up to 8% of males and 0.5% of females of Northern European descent.
2. The most common type of acquired Color Vision Deficiency (CVD) is blue-yellow (including mild cases for many older adults).
3. Most printing is in black and white.
4. Situational impairments (e.g., bright sunlight shining on a mobile screen) tend to reduce the entire color gamut, reducing color discriminability.

Note: It is *not* safe to encode information using only variations in color (i.e., only differences in hue and/or saturation) as there is bound to be someone affected!

To ensure that you are using the most accessible colors, the ACM recommends that you choose sets of colors to help ensure suitable variations in when printed in greyscale by using either of the following tools:

1. ColourBrewer: <http://colorbrewer2.org/>
2. ACE: The Accessible Colour Evaluator: <http://daprlab.com/ace/> for designing WCAG 2.0 compliant palettes.

2.12 Other notable packages and typographic remarks

Several other packages are recommended for specialized tasks.

The package `subcaption` [8] is recommended for complex figures with several subplots or subfigures that require separate subcaptioning. The packages `nomenc` [9] and `glossaries` [10] can be used for the automatic creation of the lists of symbols and concepts used.

By default `acmart` prevents all widows and orphans (i.e., lonely lines at the beginning or end of the page) and hyphenation at the end of the page. This is done by the rather strict settings

```
\widowpenalty=10000  
\clubpenalty=10000  
\brokenpenalty=10000
```

However, this may lead to frustrating results when the authors must obey a page limit. Setting these penalties to smaller values may help if you absolutely need to.

Another problem might be the too strict line breaking rules. Again, a strategically placed `\sloppy` command or putting the problematic paragraph inside `sloppypar` environment might help—but beware, the results might be, well, sloppy.

Note that the uppercasing in section titles is done using the `textcase` package [11], so the command `\NoCaseChange` inside the title may help to prevent extraneous uppercasing.

2.13 A note for wizards: `acmart-preload-hook.tex`

Sometimes you need to change the behavior of `acmart`. The usual way to do this is to redefine commands in the preamble. However, these definitions are executed *after* `acmart` is loaded and certain decisions are made. This presents a number of problems.

For example, one may want to use the `titletoc` package with `acmart`. This package should be loaded before `hyperref`. However, since `acmart` loads `hyperref` itself, the line `\usepackage{titletoc}` in the preamble will lead to grief (see <http://tex.stackexchange.com/questions/357265/using-titletoc-with-acm-acmart-style>).

Another example is passing options to a package. Suppose you want to use the `dvipsnames` option of the `xcolor` package. Normally you cannot do this because `acmart` loads this package itself without options.

The file `acmart-preload-hook.tex` can be used to solve these problems. If this file exists, it will be processed before any other package. You can use this file to load packages or pass options to them. For example, if you put in this file

```
\let\LoadClassOrig\LoadClass  
\renewcommand\LoadClass[2][]{\LoadClassOrig[#1]{#2}%  
\usepackage{titletoc}}
```

then `titletoc` will be loaded before `hyperref`. If you put in this file

```
\PassOptionsToPackage{dvipsnames}{xcolor}
```

you will pass dvipsnames to xcolor.

Important note. This hook makes it too easy to create a manuscript that is not acceptable by the ACM. It is even easier to create a file that cannot be compiled. So please do not use it *unless you know what you are doing*. And if you use it, *do not ask for support*. If you decide to use this hook, you are on your own.

3 Implementation

3.1 Identification

We start with a declaration of who we are. Most .dtx files put driver code in a separate .drv driver file. We roll this code into the main file and use the pseudo-guard <gobble> for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 <*gobble>
3 \ProvidesFile{acmart.dtx}
4 </gobble>
5 <class>\ProvidesClass{acmart}
6 [2017/12/14 v1.48 Typesetting articles for the Association for
7 Computing Machinery]
```

And the driver code:

```
8 <*gobble>
9 \documentclass{ltxdoc}
10 \usepackage{array,booktabs,amsmath,graphicx,fancyvrb,tabularx}
11 \usepackage[tt=false, type1=true]{libertine}
12 \usepackage[varqu]{zi4}
13 \usepackage[libertine]{newtxmath}
14 \usepackage[tableposition=top]{caption}
15 \usepackage{hypdoc}
16 \PageIndex
17 \CodelineIndex
18 \RecordChanges
19 \EnableCrossrefs
20 \begin{document}
21   \DocInput{acmart.dtx}
22 \end{document}
23 </gobble>
24 <*class>
25 \def\@classname{acmart}
```

3.2 Preload hook

We preload acmart-preload-hook:

```
26 \InputIfFileExists{acmart-preload-hook.tex}{%
27   \ClassWarning{\@classname}{%
28     I am loading acmart-preload-hook.tex. You are fully responsible
29     for any problems from now on.}}{}
```

3.3 Options

We need xkeyval since some of our options may have values:

```
30 \RequirePackage{xkeyval}
We use xstring to check whether user input is integer
31 \RequirePackage{xstring}
```

```

format The possible formats
32 \define@choicekey*+{acmart.cls}{format}[\ACM@format\ACM@format@nr]{%
33   manuscript, acmsmall, acmlarge, acmtog, sigconf, siggraph,
34   sigplan, sigchi, sigchi-a}[manuscript]{()}%
35   \ClassError{@classname}{The option format must be manuscript,
36     acmsmall, acmlarge, acmtog, sigconf, siggraph,
37     sigplan, sigchi or sigchi-a}%
38 \def@\DeclareACMFormat#1{\DeclareOptionX{#1}{\setkeys{acmart.cls}{format=#1}}}
39 \@DeclareACMFormat{manuscript}
40 \@DeclareACMFormat{acmsmall}
41 \@DeclareACMFormat{acmlarge}
42 \@DeclareACMFormat{acmtog}
43 \@DeclareACMFormat{sigconf}
44 \@DeclareACMFormat{siggraph}
45 \@DeclareACMFormat{sigplan}
46 \@DeclareACMFormat{sigchi}
47 \@DeclareACMFormat{sigchi-a}
48 \ExecuteOptionsX{format}

\if@ACM@screen Whether we use screen mode
49 \define@boolkey+{acmart.cls}[@ACM@]{screen}[true]{%
50   \if@ACM@screen
51     \PackageInfo{@classname}{Using screen mode}%
52   \else
53     \PackageInfo{@classname}{Not using screen mode}%
54   \fi}{\PackageError{@classname}{The option screen can be either true or
55     false}}
56 \ExecuteOptionsX{screen=false}

\if@ACM@acmthm Whether we define theorem-like environments.
57 \define@boolkey+{acmart.cls}[@ACM@]{acmthm}[true]{%
58   \if@ACM@acmthm
59     \PackageInfo{@classname}{Requiring acmthm}%
60   \else
61     \PackageInfo{@classname}{Suppressing acmthm}%
62   \fi}{\PackageError{@classname}{The option acmthm can be either true or
63     false}}
64 \ExecuteOptionsX{acmthm=true}

\if@ACM@review Whether we use review mode
65 \define@boolkey+{acmart.cls}[@ACM@]{review}[true]{%
66   \if@ACM@review
67     \PackageInfo{@classname}{Using review mode}%
68     \AtBeginDocument{@ACM@printfoliotrue}%
69   \else
70     \PackageInfo{@classname}{Not using review mode}%
71   \fi}{\PackageError{@classname}{The option review can be either true or
72     false}}
73 \ExecuteOptionsX{review=false}

```

```

\if@ACM@authorversion Whether we use author's-version mode
74 \define@boolkey+{acmart.cls}[@ACM@]{authorversion}[true]{%
75   \if@ACM@authorversion
76     \PackageInfo{@classname}{Using authorversion mode}%
77   \else
78     \PackageInfo{@classname}{Not using authorversion mode}%
79   \fi}{\PackageError{@classname}{The option authorversion can be either true or
80   false}}
81 \ExecuteOptionsX{authorversion=false}

\if@ACM@natbib@override This macro is no longer used.

\if@ACM@natbib Whether we use natbib mode
82 \define@boolkey+{acmart.cls}[@ACM@]{natbib}[true]{%
83   \if@ACM@natbib
84     \PackageInfo{@classname}{Explicitly selecting natbib mode}%
85   \else
86     \PackageInfo{@classname}{Explicitly deselecting natbib mode}%
87   \fi}{\PackageError{@classname}{The option natbib can be either true or
88   false}}
89 \ExecuteOptionsX{natbib=true}

\if@ACM@anonymous Whether we use anonymous mode
90 \define@boolkey+{acmart.cls}[@ACM@]{anonymous}[true]{%
91   \if@ACM@anonymous
92     \PackageInfo{@classname}{Using anonymous mode}%
93   \else
94     \PackageInfo{@classname}{Not using anonymous mode}%
95   \fi}{\PackageError{@classname}{The option anonymous can be either true or
96   false}}
97 \ExecuteOptionsX{anonymous=false}

\if@ACM@timestamp Whether we use timestamp mode
98 \define@boolkey+{acmart.cls}[@ACM@]{timestamp}[true]{%
99   \if@ACM@timestamp
100     \PackageInfo{@classname}{Using timestamp mode}%
101   \else
102     \PackageInfo{@classname}{Not using timestamp mode}%
103   \fi}{\PackageError{@classname}{The option timestamp can be either true or
104   false}}
105 \ExecuteOptionsX{timestamp=false}

\if@ACM@authordraft Whether we use author-draft mode
106 \define@boolkey+{acmart.cls}[@ACM@]{authordraft}[true]{%
107   \if@ACM@authordraft
108     \PackageInfo{@classname}{Using authordraft mode}%
109     \@ACM@timestamptrue
110     \@ACM@reviewtrue
111   \else

```

```

112      \PackageInfo{@classname}{Not using authordraft mode}%
113  \fi{\PackageError{@classname}{The option authordraft can be either true or
114    false}}
115 \ExecuteOptionsX{authordraft=false}

\ACM@fontsize The font size to pass to the base class
116 \def\ACM@fontsize{}
117 \DeclareOptionX{9pt}{\edef\ACM@fontsize{\CurrentOption}}
118 \DeclareOptionX{10pt}{\edef\ACM@fontsize{\CurrentOption}}
119 \DeclareOptionX{11pt}{\edef\ACM@fontsize{\CurrentOption}}
120 \DeclareOptionX{12pt}{\edef\ACM@fontsize{\CurrentOption}}

121 \DeclareOptionX{draft}{\PassOptionsToClass{\CurrentOption}{amsart}}
122 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
123 \ProcessOptionsX
124 \ClassInfo{@classname}{Using format \ACM@format, number \ACM@format@nr}

```

3.4 Setting switches

\if@ACM@manuscript Whether we use manuscript mode
125 \newif\if@ACM@manuscript

\if@ACM@journal There are two kinds of publications: journals and books
126 \newif\if@ACM@journal

\if@ACM@sigchiamode The formatting of SIGCHI extended abstracts is quite unusual. We have a special switch for them.
127 \newif\if@ACM@sigchiamode

Setting up switches

```

128 \ifnum\ACM@format@nr=5\relax % siggraph
129   \ClassWarning{@classname}{The format siggraph is now obsolete.
130   I am switching to sigconf.}
131   \setkeys{acmart.cls}{format=sigconf}
132 \fi
133 \ifnum\ACM@format@nr=0\relax
134   \ACM@manuscripttrue
135 \else
136   \ACM@manuscriptfalse
137 \fi
138 \ACM@sigchiamodefalse
139 \ifcase\ACM@format@nr
140   \relax % manuscript
141   \ACM@journaltrue
142 \or % acmsmall
143   \ACM@journaltrue
144 \or % acmlarge
145   \ACM@journaltrue

```

```

146 \or % acmtog
147   \@ACM@journaltrue
148 \or % sigconf
149   \@ACM@journalfalse
150 \or % siggraph
151   \@ACM@journalfalse
152 \or % sigplan
153   \@ACM@journalfalse
154 \or % sigchi
155   \@ACM@journalfalse
156 \or % sigchi-a
157   \@ACM@journalfalse
158   \@ACM@sigchiamodetrue
159 \fi

```

3.5 Loading the base class and package

At this point we either have `\ACM@fontsize` or use defaults

```

160 \ifx\ACM@fontsize\empty
161   \ifcase\ACM@format@nr
162     \relax % manuscript
163     \def\ACM@fontsize{9pt}%
164   \or % acmsmall
165     \def\ACM@fontsize{10pt}%
166   \or % acmlarge
167     \def\ACM@fontsize{10pt}%
168   \or % acmtog
169     \def\ACM@fontsize{9pt}%
170   \or % sigconf
171     \def\ACM@fontsize{9pt}%
172   \or % siggraph
173     \def\ACM@fontsize{9pt}%
174   \or % sigplan
175     \def\ACM@fontsize{10pt}%
176   \or % sigchi
177     \def\ACM@fontsize{10pt}%
178   \or % sigchi-a
179     \def\ACM@fontsize{10pt}%
180   \fi
181 \fi
182 \ClassInfo{@classname}{Using fontsize \ACM@fontsize}
183 \LoadClass[\ACM@fontsize, reqno]{amsart}
184 \RequirePackage{microtype}

```

We need `etoolbox` for delayed code

```
185 \RequirePackage{etoolbox}
```

We need `totpages` to calculate the number of pages and `refcount` to use that number

```
186 \RequirePackage{refcount}
```

```

187 \RequirePackage{totpages}

The \collect@body macro in amsmath is defined using \def. We load environ to
access the \long version of this command

188 \RequirePackage{environ}

We use setspace for double spacing

189 \if@ACM@manuscript
190 \RequirePackage{setspace}
191 \onehalfspacing
192 \fi

We need textcase for better upcasing

193 \RequirePackage{textcase}

```

3.6 Citations

We patch \setcitestyle to allow, for example, \setcitestyle{sort} and \setcitestyle{nosort}. We patch \citestyle to warn about undefined citation styles.

```

194 \if@ACM@natbib
195 \RequirePackage{natbib}
196 \renewcommand{\bibsection}{%
197   \section*{\refname}%
198   \phantomsection\addcontentsline{toc}{section}{\refname}%
199 }
200 \renewcommand{\bibfont}{\bibliofont}
201 \renewcommand\setcitestyle[1]{%
202 @for\@tempa:=#1\do
203 {\def\@tempb{round}\ifx\@tempa\@tempb
204   \renewcommand\NAT@open{()}\renewcommand\NAT@close{}{}\fi
205   \def\@tempb{square}\ifx\@tempa\@tempb
206   \renewcommand\NAT@open[]{}\renewcommand\NAT@close[]{}\fi
207   \def\@tempb{angle}\ifx\@tempa\@tempb
208   \renewcommand\NAT@open{$<$}\renewcommand\NAT@close{$>$}\fi
209   \def\@tempb{curly}\ifx\@tempa\@tempb
210   \renewcommand\NAT@open{\{}{}\renewcommand\NAT@close{\}}{}\fi
211   \def\@tempb{semicolon}\ifx\@tempa\@tempb
212   \renewcommand\NAT@sep{;}\fi
213   \def\@tempb{colon}\ifx\@tempa\@tempb
214   \renewcommand\NAT@sep{;}\fi
215   \def\@tempb{comma}\ifx\@tempa\@tempb
216   \renewcommand\NAT@sep{,}\fi
217   \def\@tempb{authoryear}\ifx\@tempa\@tempb
218   \NAT@numbersfalse\fi
219   \def\@tempb{numbers}\ifx\@tempa\@tempb
220   \NAT@numberstrue\NAT@superfalse\fi
221   \def\@tempb{super}\ifx\@tempa\@tempb
222   \NAT@numberstrue\NAT@supertrue\fi
223   \def\@tempb{nobibstyle}\ifx\@tempa\@tempb
224   \let\bibstyle=\@gobble\fi

```

```

225  \def\@tempb{bibstyle}\ifx\@tempa\@tempb
226    \let\bibstyle=\@citestyle\fi
227  \def\@tempb{sort}\ifx\@tempa\@tempb
228    \def\nat@sort{\@ne}\fi
229  \def\@tempb{nosort}\ifx\@tempa\@tempb
230    \def\nat@sort{\z@\fi
231  \def\@tempb{compress}\ifx\@tempa\@tempb
232    \def\nat@cmprs{\@ne}\fi
233  \def\@tempb{nocompress}\ifx\@tempa\@tempb
234    \def\nat@cmprs{\z@\fi
235  \def\@tempb{sort&compress}\ifx\@tempa\@tempb
236    \def\nat@sort{\@ne}\def\nat@cmprs{\@ne}\fi
237  \def\@tempb{mcite}\ifx\@tempa\@tempb
238    \let\nat@merge\@ne\fi
239  \def\@tempb{merge}\ifx\@tempa\@tempb
240    \@ifnum{\nat@merge<\tw@}{\let\nat@merge\tw@}\fi
241  \def\@tempb{elide}\ifx\@tempa\@tempb
242    \@ifnum{\nat@merge<\thr@}{\let\nat@merge\thr@}\fi
243  \def\@tempb{longnamesfirst}\ifx\@tempa\@tempb
244    \nat@longnamestru\fi
245  \def\@tempb{nonamebreak}\ifx\@tempa\@tempb
246    \def\nat@nmfmt#1{\mbox{\nat@up#1}}\fi
247  \expandafter\nat@find@eq\@tempa=\relax@nil
248  \if\@tempc\relax\else
249    \expandafter\nat@rem@eq\@tempc
250  \def\@tempb{open}\ifx\@tempa\@tempb
251    \xdef\nat@open{\@tempc}\fi
252  \def\@tempb{close}\ifx\@tempa\@tempb
253    \xdef\nat@close{\@tempc}\fi
254  \def\@tempb{aysep}\ifx\@tempa\@tempb
255    \xdef\nat@aysep{\@tempc}\fi
256  \def\@tempb{yysep}\ifx\@tempa\@tempb
257    \xdef\nat@yrsep{\@tempc}\fi
258  \def\@tempb{notesep}\ifx\@tempa\@tempb
259    \xdef\nat@cmt{\@tempc}\fi
260  \def\@tempb{citesep}\ifx\@tempa\@tempb
261    \xdef\nat@sep{\@tempc}\fi
262  \fi
263 }%
264 \nat@setcites
265 }
266 \renewcommand\citetitle[1]{%
267   \ifcsname bibstyle@\#1\endcsname%
268     \csname bibstyle@\#1\endcsname\let\bibstyle@gobble%
269   \else%
270     \@latex@error{Undefined '#1' citestyle}%
271   \fi
272 }%
273 \fi

```

\bibstyle@acmauthoryear The default author-year format:

```

274 \newcommand{\bibstyle@acmauthoryear}{%
275   \setcitetstyle{%
276     authoryear,%
277     open={[],close={}},citesep={;},%
278     aysep={},yysep={,,},%
279     notesep={, }}}

```

\bibstyle@acmnumeric The default numeric format:

```

280 \newcommand{\bibstyle@acmnumeric}{%
281   \setcitetstyle{%
282     numbers,sort&compress,%
283     open={[],close={}},citesep={,,},%
284     notesep={, }})

```

The default is numeric:

```

285 \if@ACM@natbib
286 \citetstyle{acmnumeric}
287 \fi

```

\@startsection Before we call hyperref, we redefine \startsection commands to their L^AT_EX defaults since the amsart ones are too AMS-specific. We need to do this early since we want hyperref to have a chance to redefine them again:

```

288 \def\@startsection#1#2#3#4#5#6{%
289   \if@noskipsec \leavevmode \fi
290   \par
291   \tempskipa #4\relax
292   \afterindenttrue
293   \ifdim \tempskipa <\z@
294     \tempskipa -\tempskipa \afterindentfalse
295   \fi
296   \ifnobreak
297     \everypar{}%
298   \else
299     \addpenalty\secpenalty\addvspace\tempskipa
300   \fi
301   \ifstar
302     {\@sect{#3}{#4}{#5}{#6}}%
303     {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}
304 \def\@sect#1#2#3#4#5#6[#7]{%
305   \edef\@toclevel{\ifnum#2=\@m 0\else\number#2\fi}%
306   \ifnum #2>\secnumdepth
307     \let\@svsec\empty
308   \else
309     \refstepcounter{#1}%
310     \protected@edef\@svsec{\@seccntformat{#1}\relax}%
311   \fi
312   \tempskipa #5\relax
313   \ifdim \tempskipa>\z@

```

```

314 \begingroup
315 #6{%
316   \hangfrom{\hskip #3\relax\@svsec}%
317   \interlinepenalty \zM #8@@par}%
318 \endgroup
319 \csname #1mark\endcsname{#7}%
320 \ifnum #2>\c@secnumdepth \else
321   \tochangemeasure{\csname the#1\endcsname}%
322 \fi
323 \addcontentsline{toc}{#1}{%
324   \ifnum #2>\c@secnumdepth \else
325     \protect\numberline{\csname the#1\endcsname}%
326   \fi
327   #7}%
328 \else
329   \def\@svsechd{%
330     #6{\hskip #3\relax
331     \@svsec #8}%
332     \csname #1mark\endcsname{#7}%
333     \ifnum #2>\c@secnumdepth \else
334       \tochangemeasure{\csname the#1\endcsname\space}%
335     \fi
336     \addcontentsline{toc}{#1}{%
337       \ifnum #2>\c@secnumdepth \else
338         \protect\numberline{\csname the#1\endcsname}%
339       \fi
340       #7}}%
341 \fi
342 \def\xsect[#5]{%
343 \def\@xsect#1{%
344   \tempskipa #1\relax
345   \ifdim \tempskipa>\z@
346     \par \nobreak
347     \vskip \tempskipa
348     \afterheading
349   \else
350     \nobreakfalse
351     \global\noskipsectrue
352     \everypar{%
353       \ifnoskipsec
354         \global\noskipsecfalse
355         {\setbox\z@\lastbox}%
356         \clubpenalty\zM
357         \begingroup \@svsechd \endgroup
358         \unskip
359         \tempskipa #1\relax
360         \hskip -\tempskipa
361       \else
362         \clubpenalty \clubpenalty
363         \everypar{}%}

```

```

364      \fi}%
365  \fi
366  \ignorespaces}
367 \def\@secCntFormat#1{\csname the#1\endcsname\quad}
368 \def\@ssect#1#2#3#4#5{%
369   \atempSkipa #3\relax
370   \ifdim \atempSkipa>\z@
371     \begingroup
372       #4{%
373         \hangfrom{\hskip #1}%
374         \interlinepenalty \zM #5\@@par}%
375     \endgroup
376   \else
377     \def\@svsechd{#4{\hskip #1\relax #5}}%
378   \fi
379 }@\xsect{#3}}

```

\@startsection The amsart package redefines \startsection. Here we redefine it again to make the table of contents work.

```

380 \def\@starttoc#1#2{\begingroup\makeatletter
381   \setTrue{#1}%
382   \par\removelastskip\vskip\z@skip
383   \atstartsection{section}\@M\z@\{\linespacing\@plus\linespacing}%
384   {.5\linespacing}{\centering\contentsnamefont}{#2}%
385   \input{\jobname.#1}%
386   \if@filesw
387     \xp\newwrite\csname tf#1\endcsname
388     \immediate\xp\openout\csname tf#1\endcsname \jobname.#1\relax
389   \fi
390   \global\nobreakfalse \endgroup
391   \addvspace{32\p@\oplus14\p@}%
392 }

```

\l@section Section spacing is more generous than for amsart

```
393 \def\l@section{\@tocline{1}{0pt}{1pc}{2pc}{}}
```

\l@subsection The spacing in amsart is too large

```
394 \def\l@subsection{\@tocline{2}{0pt}{1pc}{3pc}{}}
```

\l@subsubsection The spacing in amsart is too large

```
395 \def\l@subsubsection{\@tocline{2}{0pt}{1pc}{5pc}{}}
```

And hyperref

```

396 \let\footnotemark@nolink\@footnotemark
397 \let\footnotetext@nolink\@footnotetext
398 \RequirePackage[bookmarksnumbered,unicode]{hyperref}
399 \pdfstringdefDisableCommands{%
400   \def\unskip{}%
401   \def\textbullet{- }%

```

```

402 \def\textrightarrow{ -> }%
403 \def\footnotemark{}%
404 }
405 \urlstyle{rm}
406 \ifcase\ACM@format@nr
407 \relax % manuscript
408 \or % acmsmall
409 \or % acmlarge
410 \or % acmtog
411 \or % sigconf
412 \or % siggraph
413 \or % sigplan
414 \urlstyle{sf}
415 \or % sigchi
416 \or % sigchi-a
417 \urlstyle{sf}
418 \fi
419 \AtEndPreamble{%
420 \if@ACM@screen
421   \hypersetup{colorlinks,
422     linkcolor=ACMRed,
423     citecolor=ACMPurple,
424     urlcolor=ACMDarkBlue,
425     filecolor=ACMDarkBlue}
426   \else
427   \hypersetup{hidelinks}
428 \fi}

Bibliography mangling.

429 \if@ACM@natbib
430   \let\citeN\cite
431   \let\cite\citet
432   \let\citeANP\citeauthor
433   \let\citeNN\citeyearpar
434   \let\citeyearNP\citeyear
435   \let\citeNP\citealt
436   \DeclareRobustCommand\citeA
437   {\begingroup\NAT@swafalse
438     \let\NAT@ctype\@ne\NAT@partrue\NAT@fullfalse\NAT@open\NAT@citetp}%
439   \providecommand\newblock{}%
440 \else
441   \AtBeginDocument{%
442     \let\shortcite\cite%
443     \providecommand\citename[1]{#1}}
444 \fi
445 \newcommand\shortcite[2][]{%
446   \ifNAT@numbers\cite[#1]{#2}\else\citeyearpar[#1]{#2}\fi}

```

\bibliographystyle The `amsart` package redefines `\bibliographystyle` since it prefers the AMS bibliography style. We turn it back to the L^AT_EX definition:

```

447 \def\bibliographystyle#1{%
448   \ifx\@begindocumenthook\undefined\else
449     \expandafter\AtBeginDocument
450   \fi
451   {\if@files
452     \immediate\write\@auxout{\string\bibstyle{#1}}%
453   \fi}}

```

Graphics and color.

```

454 \RequirePackage{graphicx}
455 \RequirePackage[prologue]{xcolor}

```

We define ACM colors according to [7]:

```

456 \definecolor[named]{ACMBlue}{cmyk}{1,0.1,0,0.1}
457 \definecolor[named]{ACMYellow}{cmyk}{0,0.16,1,0}
458 \definecolor[named]{ACMOrange}{cmyk}{0,0.42,1,0.01}
459 \definecolor[named]{ACMRed}{cmyk}{0,0.90,0.86,0}
460 \definecolor[named]{ACMLightBlue}{cmyk}{0.49,0.01,0,0}
461 \definecolor[named]{ACMGreen}{cmyk}{0.20,0,1,0.19}
462 \definecolor[named]{ACMPurple}{cmyk}{0.55,1,0,0.15}
463 \definecolor[named]{ACMDarkBlue}{cmyk}{1,0.58,0,0.21}

```

Author-draft mode

```

464 \if@ACM@authordraft
465   \RequirePackage{draftwatermark}
466   \SetWatermarkFontSize{0.5in}
467   \SetWatermarkColor[gray]{.9}
468   \SetWatermarkText{\parbox{12em}{\centering
469     Unpublished working draft.\\
470     Not for distribution.}}
471 \fi

```

3.7 Paper size and paragraphing

We use geometry for dimensions. Note that the present margins do not depend on the font size option—we might need to change this. See <https://github.com/borisveytsman/acmart/issues/5#issuecomment-272881329>.

```

472 \RequirePackage{geometry}
473 \ifcase\ACM@format@nr
474   \relax % manuscript
475   \geometry{letterpaper,head=13pt,
476   marginparwidth=6pc,heightrounded}%
477 \or % acmsmall
478   \geometry{twoside=true,
479   includeheadfoot, head=13pt, foot=2pc,
480   paperwidth=6.75in, paperheight=10in,
481   top=58pt, bottom=44pt, inner=46pt, outer=46pt,
482   marginparwidth=2pc,heightrounded
483 }%
484 \or % acmlarge

```

```

485   \geometry{twoside=true, head=13pt, foot=2pc,
486     paperwidth=8.5in, paperheight=11in,
487     includeheadfoot,
488     top=78pt, bottom=114pt, inner=81pt, outer=81pt,
489     marginparwidth=4pc, heightrounded
490   }%
491 \or % acmtog
492   \geometry{twoside=true, head=13pt, foot=2pc,
493     paperwidth=8.5in, paperheight=11in,
494     includeheadfoot, columnsep=24pt,
495     top=52pt, bottom=75pt, inner=52pt, outer=52pt,
496     marginparwidth=2pc, heightrounded
497   }%
498 \or % sigconf
499   \geometry{twoside=true, head=13pt,
500     paperwidth=8.5in, paperheight=11in,
501     includeheadfoot, columnsep=2pc,
502     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
503     marginparwidth=2pc, heightrounded
504   }%
505 \or % siggraph
506   \geometry{twoside=true, head=13pt,
507     paperwidth=8.5in, paperheight=11in,
508     includeheadfoot, columnsep=2pc,
509     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
510     marginparwidth=2pc, heightrounded
511   }%
512 \or % sigplan
513   \geometry{twoside=true, head=13pt,
514     paperwidth=8.5in, paperheight=11in,
515     includeheadfoot=false, columnsep=2pc,
516     top=1in, bottom=1in, inner=0.75in, outer=0.75in,
517     marginparwidth=2pc, heightrounded
518   }%
519 \or % sigchi
520   \geometry{twoside=true, head=13pt,
521     paperwidth=8.5in, paperheight=11in,
522     includeheadfoot, columnsep=2pc,
523     top=66pt, bottom=73pt, inner=54pt, outer=54pt,
524     marginparwidth=2pc, heightrounded
525   }%
526 \or % sigchi-a
527   \geometry{twoside=false, head=13pt,
528     paperwidth=11in, paperheight=8.5in,
529     includeheadfoot, marginparsep=72pt,
530     marginparwidth=170pt, columnsep=20pt,
531     top=72pt, bottom=72pt, left=314pt, right=72pt
532   }%
533   \@mparswitchfalse
534   \reversemarginpar

```

	535 \fi
\parindent	Paragraphing
\parskip	536 \setlength{\parindent}{10\p@} 537 \setlength{\parskip}{\z@} 538 \ifcase\ACM@format@nr 539 \relax % manuscript 540 \or % acmsmall 541 \or % acmlarge 542 \or % acmtog 543 \setlength{\parindent}{9\p@}% 544 \or % sigconf 545 \or % siggraph 546 \or % sigplan 547 \or % sigchi 548 \or % sigchi-a 549 \fi
\normalparindent	The amsart package defines the \normalparindent length and initializes it to 12pt (the value of \parindent in amsart). It is later used to set the \listparindent length in the quotation environment and the \parindent length in the \@footnotetext command. We set \normalparindent to the value of \parindent as selected by acmart for consistent paragraph indents.
	550 \setlength{\normalparindent}{\parindent}
	Footnotes require some consideration. We have several layers of footnotes: front-matter footnotes, “regular” footnotes and the special insert for the bibstrip. In the old ACM classes, the bibstrip was a \@float. The problem with floats is that they tend to, well, float—and we want the guarantee they stay.
	We use manyfoot for layered footnotes instead.
\copyrightpermissionfootnoterule	This is the footnote rule that separates the bibstrip from the rest of the paper. It is a full width rule.
	551 \def\copyrightpermissionfootnoterule{\kern-3\p@ 552 \hrule \width \columnwidth \kern 2.6\p@} 553 \RequirePackage{manyfoot} 554 \SelectFootnoteRule[2]{copyrightpermission} 555 \DeclareNewFootnote{authorsaddresses} 556 \SelectFootnoteRule[2]{copyrightpermission} 557 \DeclareNewFootnote{copyrightpermission}
\footnoterule	Tschichold’s rules:
	558 \def\footnoterule{\kern-3\p@ 559 \hrule \width 4pc \kern 2.6\p@}
\endminipage	We do not use footnote rules in minipages
	560 \def\endminipage{% 561 \par}

```

562     \unskip
563     \ifvoid@mpfootins\else
564         \vskip\skip@mpfootins
565         \normalcolor
566         \unvbox@\mpfootins
567     \fi
568     \minipagetrue
569 \color@endgroup
570 \egroup
571 \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}

\@makefntext We do not use indentation for footnotes
572 \def\@makefntext{\noindent\@makefnmark}

\@footnotetext In sigchi-a mode our footnotes are in the margin!
573 \if@ACM@sigchiamode
574 \long\def\@footnotetext#1{\marginpar{%
575     \reset@font\small
576     \interlinepenalty\interfootnotelinepenalty
577     \protected@edef\@currentlabel{%
578         \csname p@footnote\endcsname\@thefnmark
579     }%
580     \color@begingroup
581         \@makefntext{%
582             \rule{z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
583         \color@endgroup}}%
584 \fi

\@mpfootnotetext We want the footnotes in minipages centered:
585 \long\def\@mpfootnotetext#1{%
586     \global\setbox\@mpfootins\vbox{%
587         \unvbox@\mpfootins
588         \reset@font\footnotesize
589         \hsize\columnwidth
590         \parboxrestore
591         \protected@edef\@currentlabel
592             {\csname p@mpfootnote\endcsname\@thefnmark}%
593         \color@begingroup\centering
594             \@makefntext{%
595                 \rule{z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
596         \color@endgroup}}}

\@makefnmark AMS classes use a buggy definition of \makefnmark. We revert to the standard one.
597 \def\@makefnmark{\hbox{\textsuperscript{\normalfont\@thefnmark}}}

\@textbottom Add some stretch according to David Carlisle's advice at http://tex.stackexchange.com/a/62318/5522
598 \def\@textbottom{\vskip \z@ \relax 1pt}
599 \let\@texttop\relax

```

3.8 Fonts

Somewhat PDFTeX and XeTeX require different incantations to make a PDF compliant with the current Acrobat bugs. Xpdf is much better.

The code below is by Ross Moore.

```
600 \RequirePackage{iftex}
601 \ifPDFTeX
602 \input{glyptounicode}
603 \pdfglyptounicode{f_f}{FB00}
604 \pdfglyptounicode{f_f_i}{FB03}
605 \pdfglyptounicode{f_f_l}{FB04}
606 \pdfglyptounicode{f_i}{FB01}
607 \pdfglyptounicode{t_t}{00740074}
608 \pdfglyptounicode{f_t}{00660074}
609 \pdfglyptounicode{T_h}{00540068}
610 \pdfgentounicode=1
611 \fi
612 \RequirePackage{cmap}
```

\if@ACM@newfonts Whether we load the new fonts

```
613 \newif\if@ACM@newfonts
614 \if@ACM@newfontstrue
615 \IfFileExists{libertine.sty}{}{\ClassWarning{@classname}{You do not
616 have the libertine package installed. Please upgrade your
617 TeX}\@ACM@newfontsfalse}
618 \IfFileExists{zi4.sty}{}{\ClassWarning{@classname}{You do not
619 have the zi4 package installed. Please upgrade your
620 TeX}\@ACM@newfontsfalse}
621 \IfFileExists{newtxmath.sty}{}{\ClassWarning{@classname}{You do not
622 have the newtxmath package installed. Please upgrade your
623 TeX}\@ACM@newfontsfalse}
```

We use Libertine throughout.

```
624 \if@ACM@newfonts
625 \RequirePackage[tt=false, type1=true]{libertine}
626 \RequirePackage[varqu]{zi4}
627 \RequirePackage[libertine]{newtxmath}
628 \RequirePackage[T1]{fontenc}
629 \fi
```

\liningnums Libertine defines \liningnums, which makes fontspec unhappy. While we do not use fontspec, some users do.

```
630 \let\liningnums\undefined
631 \AtEndPreamble{%
632   \DeclareTextFontCommand{\liningnums}{\libertineLF}}
```

The SIGCHI extended abstracts are sans serif:

```
633 \if@ACM@sighchiemode
634   \renewcommand{\familydefault}{\sfdefault}
635 \fi
```

3.9 Floats

We use the `caption` package

```
636 \RequirePackage{caption, float}
637 \captionsetup[table]{position=top}
638 \if@ACM@journal
639   \captionsetup{labelfont={sf, small},
640     textfont={sf, small}, margin=\z@}
641   \captionsetup[figure]{name={Fig.}}
642 \else
643   \captionsetup{labelfont={bf},
644     textfont={bf}, labelsep=colon, margin=\z@}
645 \ifcase\ACM@format@nr
646   \relax % manuscript
647 \or % acmsmall
648 \or % acmlarge
649 \or % acmtog
650 \or % sigconf
651 \or % siggraph
652   \captionsetup{textfont={it}}
653 \or % sigplan
654   \captionsetup{labelfont={bf},
655     textfont={normalfont}, labelsep=period, margin=\z@}
656 \or % sigchi
657   \captionsetup[figure]{labelfont={bf, small},
658     textfont={bf, small}}
659 \or % sigchi-a
660   \captionsetup[figure]{labelfont={bf, small},
661     textfont={bf, small}}
662 \fi
663 \fi
```

`sidebar` The `sidebar` environment:

```
664 \newfloat{sidebar}{}{sbar}
665 \floatname{sidebar}{Sidebar}
666 \renewenvironment{sidebar}{\Collect@Body\@sidebar}{}  
667 \long\def\@sidebar#1{\bgroup\captionsetup{type=sidebar}%
668   \marginpar{\small#1}\egroup}
```

`\@sidebar` The processing of the saved text

```
669 \newenvironment{marginfigure}{\Collect@Body\@marginfigure}{}  
670 \long\def\@marginfigure#1{\bgroup\captionsetup{type=figure}%
671   \marginpar{\centering\small#1}\egroup}
```

`marginfigure` The `marginfigure` environment:

```
672 \newenvironment{margintable}{\Collect@Body\@margintable}{}  
673 \long\def\@margintable#1{\bgroup\captionsetup{type=table}%
674   \marginpar{\small#1}\egroup}
```

`\@marginfigure` The processing of the saved text

```
675 \long\def\@margintable#1{\bgroup\captionsetup{type=table}%
676   \marginpar{\small#1}\egroup}
```

`margintable` The `margintable` environment:

```
677 \long\def\@margintable#1{\bgroup\captionsetup{type=table}%
678   \marginpar{\small#1}\egroup}
```

```

@marginable The processing of the saved text
673 \long\def\@marginable#1{\bgroup\captionsetup{type=table}%
674   \marginpar{\centering\small#1}\egroup}

SIGCHI extended abstracts provide an interesting possibility to push into the margin.
Here we use figure* and table* for this.

\fulltextwidth We define the width of the boxes as
675 \newdimen\fulltextwidth
676 \fulltextwidth=\dimexpr(\textwidth+\marginparwidth+\marginparsep)

\dblfloat We redefine the double-float command. First, we make the size bigger. Second, our
default position is going to be tp (to give marginalia a chance)
677 \if@ACM@sigchiamode
678 \def\dblfloat{\bgroup\columnwidth=\fulltextwidth
679   \let\endfloatbox\@endwidefloatbox
680   \def\fpsadddefault{\def\fps{tp}}%
681   \@float}
682 \fi

\enddblfloat And the end. Just adding a \bgroup.
683 \if@ACM@sigchiamode
684 \def\enddblfloat{%
685   \endfloat\egroup}
686 \fi

@endwidefloatbox This is the end of a wide box—we basically move everything to the left
687 \def@endwidefloatbox{%
688   \par\vskip\z@skip
689   \minipagetrue
690   \outer@nobreak
691   \egroup
692   \color@endbox
693   \global\setbox\@currbox=\vbox{\moveleft
694     \dimexpr(\fulltextwidth-\textwidth)\box\@currbox}%
695   \wd\@currbox=\textwidth
696 }

```

3.10 Lists

```

697 \ifcase\ACM@format@nr
698 \relax % manuscript
699 \or % acmsmall
700 \or % acmlarge
701 \or % acmtog
702 \or % sigconf
703 \or % siggraph
704 \or % sigplan
705 \def\labelenumi{\theenumi.}

```

```

706 \def\labelenumii{\theenumii.}
707 \def\labelenumiii{\theenumiii.}
708 \def\labelenumiv{\theenumiv.}
709 \or % sigchi
710 \or % sigchi-a
711 \fi

The AMS uses generous margins for lists. Note that amsart defines \leftmargin values for list levels at the beginning of the document, so we must redefine them in the same manner. Also, note that amsart redefines the enumerate and itemize environments with a \makelabel command that uses \llap, so the \labelwidth value is (effectively) irrelevant; nonetheless, we follow amsart and set \labelwidth to \leftmargin minus \labelsep.
712 \newdimen\@ACM@labelwidth
713 \AtBeginDocument{%
714   \setlength\labelsep{4pt}
715   \setlength{\@ACM@labelwidth}{6.5pt}
716
717   %% First-level list: when beginning after the first line of an
718   %% indented paragraph or ending before an indented paragraph, labels
719   %% should not hang to the left of the preceding/following text.
720   \setlength\leftmargini{\z@}
721   \addtolength\leftmargini{\parindent}
722   \addtolength\leftmargini{2\labelsep}
723   \addtolength\leftmargini{\@ACM@labelwidth}
724
725   %% Second-level and higher lists.
726   \setlength\leftmarginii{\z@}
727   \addtolength\leftmarginii{0.5\labelsep}
728   \addtolength\leftmarginii{\@ACM@labelwidth}
729   \setlength\leftmarginiii{\leftmarginii}
730   \setlength\leftmarginiv{\leftmarginii}
731   \setlength\leftmarginv{\leftmarginii}
732   \setlength\leftmarginvi{\leftmarginii}
733   \@listi
734 \newskip\listisep
735 \listisep\smallskipamount
736 \def@listI{\leftmargin\leftmargini
737   \labelwidth\leftmargini \advance\labelwidth-\labelsep
738   \listparindent\z@
739   \topsep\listisep}
740 \let@listi@listI
741 \def@listii{\leftmargin\leftmarginii
742   \labelwidth\leftmarginii \advance\labelwidth-\labelsep
743   \topsep\z@skip}
744 \def@listiii{\leftmargin\leftmarginiii
745   \labelwidth\leftmarginiii \advance\labelwidth-\labelsep}
746 \def@listiv{\leftmargin\leftmarginiv
747   \labelwidth\leftmarginiv \advance\labelwidth-\labelsep}
748 \def@listv{\leftmargin\leftmarginv}

```

```

749 \labelwidth\leftmarginv \advance\labelwidth-\labelsep}
750 \def@listvi{\leftmargin\leftmarginvi
751 \labelwidth\leftmarginvi \advance\labelwidth-\labelsep}

\descriptionlabel We do not use a colon by default like amsart does:
752 \renewcommand{\descriptionlabel}[1]{\upshape\bfseries #1}

\description Make the description environment indentation consistent with that of the itemize
and enumerate environments.
753 \renewenvironment{description}{\list{}{%
754 \labelwidth@\ACM@labelwidth
755 \let\makelabel\descriptionlabel}%
756 }{
757 \endlist
758 }
759 \let\enddescription=\endlist % for efficiency

```

3.11 Top-matter data

We use the xkeyval interface to define journal titles and the relevant information

```

760 \define@choicekey*+{ACM}{acmJournal}[\@journalCode\journalCode@nr]{%
761 CIE,%
762 CSUR,%
763 IMWUT,%
764 JACM,%
765 JDIQ,%
766 JEA,%
767 JERIC,%
768 JETC,%
769 JOCH,%
770 PACMHCI,%
771 PACMPL,%
772 POMACS,%
773 TAAS,%
774 TACCESS,%
775 TACO,%
776 TALG,%
777 TALLIP,%
778 TAP,%
779 TCPS,%
780 TEAC,%
781 TECS,%
782 THRI,%
783 TIIS,%
784 TISSEC,%
785 TIST,%
786 TKDD,%
787 TMIS,%
788 TOCE,%

```

```

789 TOCHI,%
790 TOCL,%
791 TOCS,%
792 TOCT,%
793 TODAES,%
794 TODS,%
795 TOG,%
796 TOIS,%
797 TOIT,%
798 TOMACS,%
799 TOMM,%
800 TOMPECS,%
801 TOMS,%
802 TOPC,%
803 TOPS,%
804 TOPLAS,%
805 TOS,%
806 TOSEM,%
807 TOSN,%
808 TRETS,%
809 TSAS,%
810 TSC,%
811 TSLP,%
812 TWEB%
813 }{%
814 \ifcase\@journalCode@nr
815 \relax % CIE
816 \def\@journalName{ACM Computers in Entertainment}%
817 \def\@journalNameShort{ACM Comput. Entertain.}%
818 \def\@permissionCodeOne{1544-3574}%
819 \or % CSUR
820 \def\@journalName{ACM Computing Surveys}%
821 \def\@journalNameShort{ACM Comput. Surv.}%
822 \def\@permissionCodeOne{0360-0300}%
823 \or % IMWUT
824 \def\@journalName{Proceedings of the ACM on Interactive, Mobile,
825 Wearable and Ubiquitous Technologies}%
826 \def\@journalNameShort{Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.}%
827 \def\@permissionCodeOne{2474-9567}%
828 \@ACM@screentru
829 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
830 \or % JACM
831 \def\@journalName{Journal of the ACM}%
832 \def\@journalNameShort{J. ACM}%
833 \def\@permissionCodeOne{0004-5411}%
834 \or % JDIQ
835 \def\@journalName{ACM Journal of Data and Information Quality}%
836 \def\@journalNameShort{ACM J. Data Inform. Quality}%
837 \def\@permissionCodeOne{1936-1955}%
838 \or % JEA

```

```

839  \def \@journalName{ACM Journal of Experimental Algorithms}%
840  \def \@journalNameShort{ACM J. Exp. Algor.}%
841  \def \@permissionCodeOne{1084-6654}%
842 \or % JERIC
843  \def \@journalName{ACM Journal of Educational Resources in Computing}%
844  \def \@journalNameShort{ACM J. Edu. Resources in Comput.}%
845  \def \@permissionCodeOne{1073-0516}%
846 \or % JETC
847  \def \@journalName{ACM Journal on Emerging Technologies in Computing Systems}%
848  \def \@journalNameShort{ACM J. Emerg. Technol. Comput. Syst.}%
849  \def \@permissionCodeOne{1550-4832}%
850 \or % JOCH
851  \def \@journalName{ACM Journal on Computing and Cultural Heritage}%
852  \def \@journalNameShort{ACM J. Comput. Cult. Herit.}%
853 \or % PACMHCI
854  \def \@journalName{Proceedings of the ACM on Human-Computer Interaction}%
855  \def \@journalNameShort{Proc. ACM Hum.-Comput. Interact.}%
856  \def \@permissionCodeOne{2573-0142}%
857  \@ACM@screentru
858  \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
859 \or % PACML
860  \def \@journalName{Proceedings of the ACM on Programming Languages}%
861  \def \@journalNameShort{Proc. ACM Program. Lang.}%
862  \def \@permissionCodeOne{2475-1421}%
863  \@ACM@screentru
864  \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
865 \or % POMACS
866  \def \@journalName{Proceedings of the ACM on Measurement and Analysis of Computing Systems}%
867  \def \@journalNameShort{Proc. ACM Meas. Anal. Comput. Syst.}%
868  \def \@permissionCodeOne{2476-1249}%
869  \@ACM@screentru
870  \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
871 \or % TAAS
872  \def \@journalName{ACM Transactions on Autonomous and Adaptive Systems}%
873  \def \@journalNameShort{ACM Trans. Autonom. Adapt. Syst.}%
874  \def \@permissionCodeOne{1556-4665}%
875 \or % TACCESS
876  \def \@journalName{ACM Transactions on Accessible Computing}%
877  \def \@journalNameShort{ACM Trans. Access. Comput.}%
878  \def \@permissionCodeOne{1936-7228}%
879 \or % TACO
880  \def \@journalName{ACM Transactions on Architecture and Code Optimization}%
881  \def \@journalNameShort{ACM Trans. Arch. Code Optim.}%
882 \or % TALG
883  \def \@journalName{ACM Transactions on Algorithms}%
884  \def \@journalNameShort{ACM Trans. Algor.}%
885  \def \@permissionCodeOne{1549-6325}%
886 \or % TALLIP
887  \def \@journalName{ACM Transactions on Asian and Low-Resource Language Information Processing}%
888  \def \@journalNameShort{ACM Trans. Asian Low-Resour. Lang. Inf. Process.}%

```

```

889 \def \@permissionCodeOne{2375-4699}%
890 \or % TAP
891 \def \@journalName{ACM Transactions on Applied Perception}%
892 \or % TCPS
893 \def \@journalName{ACM Transactions on Cyber-Physical Systems}%
894 \or % TEAC
895 \def \@journalName{ACM Transactions on Economics and Computation}%
896 \or % TECS
897 \def \@journalName{ACM Transactions on Embedded Computing Systems}%
898 \def \@journalNameShort{ACM Trans. Embedd. Comput. Syst.}%
899 \def \@permissionCodeOne{1539-9087}%
900 \or % THRI
901 \def \@journalName{ACM Transactions on Human-Robot Interaction}%
902 \def \@journalNameShort{ACM Trans. Hum.-Robot Interact.}%
903 \def \@permissionCodeOne{2573-9522}%
904 \or % TIIS
905 \def \@journalName{ACM Transactions on Interactive Intelligent Systems}%
906 \def \@journalNameShort{ACM Trans. Interact. Intell. Syst.}%
907 \def \@permissionCodeOne{2160-6455}%
908 \or % TISSEC
909 \def \@journalName{ACM Transactions on Information and System Security}%
910 \def \@journalNameShort{ACM Trans. Info. Syst. Sec.}%
911 \def \@permissionCodeOne{1094-9224}%
912 \or % TIST
913 \def \@journalName{ACM Transactions on Intelligent Systems and Technology}%
914 \def \@journalNameShort{ACM Trans. Intell. Syst. Technol.}%
915 \def \@permissionCodeOne{2157-6904}%
916 \or % TKDD
917 \def \@journalName{ACM Transactions on Knowledge Discovery from Data}%
918 \def \@journalNameShort{ACM Trans. Knowl. Discov. Data.}%
919 \def \@permissionCodeOne{1556-4681}%
920 \or % TMIS
921 \def \@journalName{ACM Transactions on Management Information Systems}%
922 \def \@journalNameShort{ACM Trans. Manag. Inform. Syst.}%
923 \def \@permissionCodeOne{2158-656X}%
924 \or % TOCE
925 \def \@journalName{ACM Transactions on Computing Education}%
926 \def \@journalNameShort{ACM Trans. Comput. Educ.}%
927 \def \@permissionCodeOne{1946-6226}%
928 \or % TOCHI
929 \def \@journalName{ACM Transactions on Computer-Human Interaction}%
930 \def \@journalNameShort{ACM Trans. Comput.-Hum. Interact.}%
931 \def \@permissionCodeOne{1073-0516}%
932 \or % TOCL
933 \def \@journalName{ACM Transactions on Computational Logic}%
934 \def \@journalNameShort{ACM Trans. Comput. Logic}%
935 \def \@permissionCodeOne{1529-3785}%
936 \or % TOCS
937 \def \@journalName{ACM Transactions on Computer Systems}%
938 \def \@journalNameShort{ACM Trans. Comput. Syst.}%

```

```

939  \def \@permissionCodeOne{0734-2071}%
940  \or % TOCT
941  \def \@journalName{ACM Transactions on Computation Theory}%
942  \def \@journalNameShort{ACM Trans. Comput. Theory}%
943  \def \@permissionCodeOne{1942-3454}%
944  \or % TODAES
945  \def \@journalName{ACM Transactions on Design Automation of Electronic Systems}%
946  \def \@journalNameShort{ACM Trans. Des. Autom. Electron. Syst.}%
947  \def \@permissionCodeOne{1084-4309}%
948  \or % TODS
949  \def \@journalName{ACM Transactions on Database Systems}%
950  \def \@journalNameShort{ACM Trans. Datab. Syst.}%
951  \def \@permissionCodeOne{0362-5915}%
952  \or % TOG
953  \def \@journalName{ACM Transactions on Graphics}%
954  \def \@journalNameShort{ACM Trans. Graph.}%
955  \def \@permissionCodeOne{0730-0301}%
956  \or % TOIS
957  \def \@journalName{ACM Transactions on Information Systems}%
958  \def \@permissionCodeOne{1046-8188}%
959  \or % TOIT
960  \def \@journalName{ACM Transactions on Internet Technology}%
961  \def \@journalNameShort{ACM Trans. Internet Technol.}%
962  \def \@permissionCodeOne{1533-5399}%
963  \or % TOMACS
964  \def \@journalName{ACM Transactions on Modeling and Computer Simulation}%
965  \def \@journalNameShort{ACM Trans. Model. Comput. Simul.}%
966  \or % TOMM
967  \def \@journalName{ACM Transactions on Multimedia Computing, Communications and Applications}%
968  \def \@journalNameShort{ACM Trans. Multimedia Comput. Commun. Appl.}%
969  \def \@permissionCodeOne{1551-6857}%
970  \def \@permissionCodeTwo{0100}%
971  \or % TOMPECS
972  \def \@journalName{ACM Transactions on Modeling and Performance Evaluation of Computing Systems}%
973  \def \@journalNameShort{ACM Trans. Model. Perform. Eval. Comput. Syst.}%
974  \def \@permissionCodeOne{2376-3639}%
975  \or % TOMS
976  \def \@journalName{ACM Transactions on Mathematical Software}%
977  \def \@journalNameShort{ACM Trans. Math. Softw.}%
978  \def \@permissionCodeOne{0098-3500}%
979  \or % TOPC
980  \def \@journalName{ACM Transactions on Parallel Computing}%
981  \def \@journalNameShort{ACM Trans. Parallel Comput.}%
982  \def \@permissionCodeOne{1539-9087}%
983  \or % TOPS
984  \def \@journalName{ACM Transactions on Privacy and Security}%
985  \def \@journalNameShort{ACM Trans. Priv. Sec.}%
986  \def \@permissionCodeOne{2471-2566}%
987  \or % TOPLAS
988  \def \@journalName{ACM Transactions on Programming Languages and Systems}%

```

```

989 \def \@journalNameShort{ACM Trans. Program. Lang. Syst.}%
990 \def \@permissionCodeOne{0164-0925}%
991 \or % TOS
992 \def \@journalName{ACM Transactions on Storage}%
993 \def \@journalNameShort{ACM Trans. Storage}%
994 \def \@permissionCodeOne{1553-3077}%
995 \or % TOSEM
996 \def \@journalName{ACM Transactions on Software Engineering and Methodology}%
997 \def \@journalNameShort{ACM Trans. Softw. Eng. Methodol.}%
998 \def \@permissionCodeOne{1049-331X}%
999 \or % TOSN
1000 \def \@journalName{ACM Transactions on Sensor Networks}%
1001 \def \@journalNameShort{ACM Trans. Sensor Netw.}%
1002 \def \@permissionCodeOne{1550-4859}%
1003 \or % TRETS
1004 \def \@journalName{ACM Transactions on Reconfigurable Technology and Systems}%
1005 \def \@journalNameShort{ACM Trans. Reconfig. Technol. Syst.}%
1006 \def \@permissionCodeOne{1936-7406}%
1007 \or % TSAS
1008 \def \@journalName{ACM Transactions on Spatial Algorithms and Systems}%
1009 \def \@journalNameShort{ACM Trans. Spatial Algorithms Syst.}%
1010 \def \@permissionCodeOne{2374-0353}%
1011 \or % TSC
1012 \def \@journalName{ACM Transactions on Social Computing}%
1013 \def \@journalNameShort{ACM Trans. Soc. Comput.}%
1014 \def \@permissionCodeOne{2469-7818}%
1015 \or % TSLP
1016 \def \@journalName{ACM Transactions on Speech and Language Processing}%
1017 \def \@journalNameShort{ACM Trans. Speech Lang. Process.}%
1018 \def \@permissionCodeOne{1550-4875}%
1019 \or % TWEB
1020 \def \@journalName{ACM Transactions on the Web}%
1021 \def \@journalNameShort{ACM Trans. Web}%
1022 \def \@permissionCodeOne{1559-1131}%
1023 \fi
1024 \ClassInfo{@classname}{Using journal code \@journalCode}%
1025 }{%
1026 \ClassError{@classname}{Incorrect journal #1}%
1027 }%

```

\acmJournal And the syntactic sugar around it

```

1028 \def \acmJournal#1{\setkeys{ACM}{acmJournal=#1}}

```

The defaults:

```

1029 \def \@journalCode@nr{0}
1030 \def \@journalName{}%
1031 \def \@journalNameShort{\@journalName}%
1032 \def \@permissionCodeOne{XXXX-XXXX}%
1033 \def \@permissionCodeTwo{}%

```

```

\acmConference This is the conference command
1034 \newcommand{\acmConference}[4][]{
1035   \gdef\acmConference@shortname{#1}%
1036   \gdef\acmConference@name{#2}%
1037   \gdef\acmConference@date{#3}%
1038   \gdef\acmConference@venue{#4}%
1039   \ifx\acmConference@shortname\empty
1040     \gdef\acmConference@shortname{#2}%
1041   \fi}
1042 \acmConference[Conference'17]{ACM Conference}{July 2017}{Washington,
1043 DC, USA}

\acmBooktitle The book title of the conference:
\@acmBooktitle 1044 \def\acmBooktitle#1{\gdef\@acmBooktitle{#1}}
1045 \acmBooktitle{Proceedings of \acmConference@name
1046   \ifx\acmConference@name\acmConference@shortname\else
1047     (\acmConference@shortname)\fi}

\@editorsAbbrev How to abbreviate editors
1048 \def\@editorsAbbrev{(Ed.)}

\@acmEditors The list of editors
1049 \def\@acmEditors{}

\editor Add a new editor to the list
1050 \def\editor#1{\ifx\@acmEditors\empty
1051   \gdef\@acmEditors{#1}%
1052 \else
1053   \gdef\@editorsAbbrev{(\Eds.)}%
1054   \g@addto@macro\@acmEditors{\and#1}%
1055 \fi}

\subtitle The subtitle macro
1056 \def\subtitle#1{\def\@subtitle{#1}}
1057 \subtitle{}


\num@authorgroups The total number of “groups”. Each group is several authors with the same affiliations(s)
1058 \newcount\num@authorgroups
1059 \num@authorgroups=0\relax

\num@authors The total number of authors
1060 \newcount\num@authors
1061 \num@authors=0\relax

\if@insideauthorgroup Whether we are continuing an author group
1062 \newif\if@insideauthorgroup
1063 \if@insideauthorgroupfalse

```

\author Adding an author to the list of authors and addresses

```

1064 \renewcommand\author[2][]{
1065   \global\advance\num@authors by 1\relax
1066   \if@insideauthorgroup\else
1067     \global\advance\num@authorgroups by 1\relax
1068     \global\@insideauthorgrouptrue
1069   \fi
1070   \ifx\addresses\empty
1071     \if@ACM@anonymous
1072       \gdef\addresses{@author{Anonymous Author(s)}}
1073       \gdef\authors{Anonymous Author(s)}
1074     \else
1075       \gdef\addresses{@author{#2}}
1076       \gdef\authors{#2}
1077     \fi
1078   \else
1079     \if@ACM@anonymous\else
1080       \g@addto@macro\addresses{\and\@author{#2}}
1081       \g@addto@macro\authors{\and#2}
1082     \fi
1083   \fi
1084   \if@ACM@anonymous
1085     \ifx\shortauthors\empty
1086       \gdef\shortauthors{Anon.}
1087     \fi
1088   \else
1089     \def@tempa{#1}
1090     \ifx@tempa\empty
1091       \ifx\shortauthors\empty
1092         \gdef\shortauthors{#2}
1093       \else
1094         \g@addto@macro\shortauthors{\and#2}
1095       \fi
1096     \else
1097       \ifx\shortauthors\empty
1098         \gdef\shortauthors{#1}
1099       \else
1100         \g@addto@macro\shortauthors{\and#1}
1101       \fi
1102     \fi
1103   \fi
1104 }
```

\affiliation The macro \affiliation mimics \address from amsart. Note that it has an optional argument, which we use differently from amsart.

```

1104 \newcommand{\affiliation}[2][]{
1105   \global\@insideauthorgroupfalse
1106   \if@ACM@anonymous\else
1107     \g@addto@macro\addresses{\affiliation{#1}{#2}}
1108   \fi}
```

```

@ACM@affiliation@obeypunctuation Whether to use the author's punctuation (false by default, which adds American-style
address punctuation)
1109 \define@boolkey+{@ACM@affiliation@}{@ACM@affiliation@}{obeypunctuation}%
1110 [true]{\ClassError{@classname}{The option obeypunctuation can be either true or false}}}

\additionalaffiliation Additional affiliations go to footnotes
1111 \def\additionalaffiliation#1{\authornote{\additionalaffiliation{#1}}}

@additionalaffiliation Process \additionalaffiliation inside \authornote
1112 \def\@additionalaffiliation#1{\bgroup
1113   \def\position##1{\ignorespaces}%
1114   \def\institution##1{##1\ignorespaces}%
1115   \def\department{\ifnextchar[{\@department}{\@department[]}}%
1116   \def\@department[##1]{##2{\unskip, ##2\ignorespaces}%
1117   \let\streetaddress\position
1118   \let\city\position
1119   \let\state\position
1120   \let\postcode\position
1121   \let\country\position
1122   Also with #1\unskip.\egroup}

\email The macro \email mimics \email from amsart. Again, it has an optional argument that
we do not currently need but keep for possible future use.
1123 \renewcommand{\email}[2][]{%
1124   \if@ACM@anonymous\else
1125     \g@addto@macro\addresses{\email{#1}{#2}}%
1126   \fi}

\orcid Right now we do not typeset ORCIDs
1127 \def\orcid#1{\unskip\ignorespaces}

\authorsaddresses Setting up authors' addresses
1128 \def\authorsaddresses#1{\def\@authorsaddresses{#1}}
1129 \authorsaddresses{\mkauthorsaddresses}

@titlenotes The title notes
1130 \def\@titlenotes{}

\titlenote Adding a note to the title
1131 \def\titlenote#1{%
1132   \g@addto@macro\@title{\footnotemark}%
1133   \if@ACM@anonymous
1134     \g@addto@macro\@titlenotes{%
1135       \stepcounter{footnote}\footnotetext{Title note}}%
1136   \else
1137     \g@addto@macro\@titlenotes{\stepcounter{footnote}\footnotetext{#1}}%
1138   \fi}

```

```

\@subtitlenotes The subtitle notes
1139 \def\@subtitlenotes{}

\subtitlenote Adding a note to the subtitle
1140 \def\subtitlenote#1{%
1141   \g@addto@macro\@subtitle{\footnotemark}%
1142   \if@ACM@anonymous
1143     \g@addto@macro\@subtitlenotes{%
1144       \stepcounter{footnote}\footnotetext{Subtitle note}}%
1145   \else
1146     \g@addto@macro\@subtitlenotes{%
1147       \stepcounter{footnote}\footnotetext{#1}}%
1148   \fi}

\@authornotes The author notes
1149 \def\@authornotes{}

\authornote Adding a note to the author
1150 \def\authornote#1{%
1151   \if@ACM@anonymous\else
1152     \g@addto@macro\addresses{@authornotemark}%
1153     \g@addto@macro\@authornotes{%
1154       \stepcounter{footnote}\footnotetext{#1}}%
1155   \fi}

\authornotemark Adding a footnote mark to the authors
1156 \newcommand\authornotemark[1][\relax]{%
1157   \ifx#1\relax\relax\relax
1158   \g@addto@macro\addresses{@authornotemark}%
1159   \else
1160   \g@addto@macro\addresses{@@authornotemark{#1}}%
1161   \fi}

\acmVolume The current volume
1162 \def\acmVolume#1{\def\@acmVolume{#1}}
1163 \acmVolume{1}

\acmNumber The current number
1164 \def\acmNumber#1{\def\@acmNumber{#1}}
1165 \acmNumber{1}

\acmArticle The current article
1166 \def\acmArticle#1{\def\@acmArticle{#1}}
1167 \acmArticle{1}

\acmArticleSeq The sequence number
1168 \def\acmArticleSeq#1{\def\@acmArticleSeq{#1}}
1169 \acmArticleSeq{@acmArticle}

```

```

\acmYear The current year
1170 \def\acmYear#1{\def\@acmYear{#1}}
1171 \acmYear{\the\year}

\acmMonth The current month
1172 \def\acmMonth#1{\def\@acmMonth{#1}}
1173 \acmMonth{\the\month}

\@acmPubDate The publication date
1174 \def\@acmPubDate{\ifcase\@acmMonth\or
1175   January\or February\or March\or April\or May\or June\or
1176   July\or August\or September\or October\or November\or
1177   December\fi^\@acmYear}

\acmPrice The price
1178 \def\acmPrice#1{\def\@acmPrice{#1}}
1179 \acmPrice{15.00}

\acmSubmissionID The submission ID
1180 \def\acmSubmissionID#1{\def\@acmSubmissionID{#1}}
1181 \acmSubmissionID{}

\acmISBN The book ISBN
1182 \def\acmISBN#1{\def\@acmISBN{#1}}
1183 \acmISBN{978-x-xxxx-xxxx-x/YY/MM}

\acmDOI The paper DOI
1184 \def\acmDOI#1{\def\@acmDOI{#1}}
1185 \acmDOI{10.1145/nnnnnnn.nnnnnnnn}

\if@ACM@badge Whether to print a badge. Note that either a left or right badge triggers it:
1186 \newif\if@ACM@badge
1187 \@ACM@badgefalse

\@ACM@badge@width The width of the badge
1188 \newlength\@ACM@badge@width
1189 \setlength\@ACM@badge@width{5pc}

\@ACM@title@width The width of the badge
1190 \newlength\@ACM@title@width

\@ACM@badge@skip The space between the badge and the title
1191 \newlength\@ACM@badge@skip
1192 \setlength\@ACM@badge@skip{1pc}

```

```

\acmBadgeR Setting the right badge
1193 \newcommand\acmBadgeR[2][]{\@ACM@badgetrue
1194   \def\@acmBadgeR@url{\#1}%
1195   \def\@acmBadgeR@image{\#2}%
1196 \def\@acmBadgeR@url{}
1197 \def\@acmBadgeR@image{}

\acmBadgeL Setting the left badge
1198 \newcommand\acmBadgeL[2][]{\@ACM@badgetrue
1199   \def\@acmBadgeL@url{\#1}%
1200   \def\@acmBadgeL@image{\#2}%
1201 \def\@acmBadgeL@url{}
1202 \def\@acmBadgeL@image{}

\startPage The start page of the paper
1203 \def\startPage#1{\def\@startPage{#1}}
1204 \startPage{}

\terms Terms are obsolete. We use CCS now.
1205 \def\terms#1{\ClassWarning{@classname}{The command \string\terms{} is
1206   obsolete. I am going to ignore it}{}}

\keywords Keywords are mostly obsolete. We use CCS now. Still it makes sense to keep them for
compatibility.
1207 \def\keywords#1{\def\@keywords{#1}}
1208 \keywords{}

abstract The amsart package puts abstract in a box. Since we do not know whether we will
use two-column mode, we prefer to save the text
1209 \renewenvironment{abstract}{\Collect@Body\@saveabstract}{} 

\@saveabstract And saving the abstract
1210 \long\def\@saveabstract#1{\long\gdef\@abstract{#1}}
1211 \@saveabstract{}

\@empty The long version of \@empty (to compare with \abstrac)
1212 \long\def\@empty{}

\if@ACM@printccs Whether to print CCS
1213 \define@boolkey+{@ACM@topmatter@}{@ACM@}{printccs}[true]{%
1214   \if@ACM@printccs
1215     \ClassInfo{@classname}{Printing CCS}%
1216   \else
1217     \ClassInfo{@classname}{Suppressing CCS}%
1218   \fi}{\ClassError{@classname}{The option printccs can be either true or false}}%

```

```

\if@ACM@printacmref Whether to print the ACM bibstrip
1219 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printacmref}[true]{%
1220   \if@ACM@printacmref
1221     \ClassInfo{@\classname}{Printing bibformat}%
1222   \else
1223     \ClassInfo{@\classname}{Suppressing bibformat}%
1224   \fi}{\ClassError{@\classname}{The option printacmref can be either true or false}}


\if@ACM@printfolios Whether to print folios
1225 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printfolios}[true]{%
1226   \if@ACM@printfolios
1227     \ClassInfo{@\classname}{Printing folios}%
1228   \else
1229     \ClassInfo{@\classname}{Suppressing folios}%
1230   \fi}{\ClassError{@\classname}{The option printfolios can be either true or false}}


\@ACM@authorsperrow The number of authors per row. 0 means use the default algorithm.
1231 \define@cmdkey{@ACM@topmatter@}[@ACM@]{authorsperrow}[0]{%
1232   \IfInteger{#1}{\ClassInfo{@\classname}{Setting authorsperrow to
1233     #1}}{\ClassWarning{@\classname}{The parameter authorsperrow must be
1234     numerical. Ignoring the input #1}\gdef\@ACM@authorsperrow{0}}}

\settopmatter The usual syntactic sugar
1235 \def\settopmatter#1{\setkeys{@ACM@topmatter@}{#1}}


Now the settings
1236 \settopmatter{printccs=true, printacmref=true}
1237 \if@ACM@manuscript
1238   \settopmatter{printfolios=true}
1239 \else
1240   \if@ACM@journal
1241     \settopmatter{printfolios=true}
1242   \else
1243     \settopmatter{printfolios=false}
1244   \fi
1245 \fi
1246 \settopmatter{authorsperrow=0}

\@received The container for the paper history
1247 \def\@received{}


\received The \received command
1248 \newcommand\received[2][]{\def\@tempa{#1}%
1249   \ifx\@tempa\empty
1250     \ifx\@received\empty
1251       \gdef\@received{Received #2}%
1252     \else
1253       \g@addto@macro{\@received}{; revised #2}%
1254     \fi

```

```

1255 \else
1256   \ifx\@received\@empty
1257     \gdef\@received{\#1 #2}%
1258   \else
1259     \g@addto@macro{\@received}{; #1 #2}%
1260   \fi
1261 \fi}
1262 \AtEndDocument{%
1263   \ifx\@received\@empty\else
1264     \par\bigskip\noindent\small\normalfont\@received\par
1265   \fi}

```

3.12 Concepts system

We exclude CCSXML stuff generated by the ACM system:

```

1266 \RequirePackage{comment}
1267 \excludecomment{CCSXML}

```

- \@concepts This is the storage macro for concepts


```

1268 \let\@concepts\@empty

```
- \ccsdesc The first argument is the significance, the second is the concept(s)


```

1269 \newcommand\ccsdesc[2][100]{%
1270   \ccsdesc@parse#1^#2^~\ccsdesc@parse@end}

```
- \ccsdesc@parse The parser of the expression Significance^General^Specific (we need textcomp for \textrightarrow). Note that Specific can be empty!


```

1271 \RequirePackage{textcomp}
1272 \def\ccsdesc@parse#1^#2^#3^{%
1273   \expandafter\ifx\csname CCS@General@\#2\endcsname\relax
1274     \expandafter\gdef\csname CCS@General@\#2\endcsname{\textbullet}%
1275     \textbf{#2}%
1276   \expandafter\gdef\csname CCS@Punctuation@\#2\endcsname{; }%
1277   \expandafter\gdef\csname CCS@Specific@\#2\endcsname{}%
1278   \g@addto@macro{\@concepts}{\csname CCS@General@\#2\endcsname
1279     \csname CCS@Punctuation@\#2\endcsname
1280     \csname CCS@Specific@\#2\endcsname}%
1281 \fi
1282 \ifx#3\relax\relax\else
1283   \expandafter\gdef\csname CCS@Punctuation@\#2\endcsname{
1284     \textrightarrow\ }%
1285   \expandafter\g@addto@macro\expandafter{\csname CCS@Specific@\#2\endcsname}{%
1286     \ifnum#1>499\textbf{#3}; \else
1287     \ifnum#1>299\textit{#3}; \else
1288     #3; \fi\fi}%
1289 \fi
1290 \ccsdesc@parse@finish}

```
- \ccdesc@parse@finish Gobble everything to \ccsdesc@parse@end


```

1291 \def\ccsdesc@parse@finish#1\ccsdesc@parse@end{}

```

3.13 Copyright system

This is from acmcopyright.sty

```
\if@printcopyright Whether to print a copyright symbol
1292 \newif\if@printcopyright
1293 \if@printcopyrighttrue

\if@printpermission Whether to print the permission block
1294 \newif\if@printpermission
1295 \if@printpermissiontrue

\if@acmowned Whether the ACM owns the rights to the paper
1296 \newif\if@acmowned
1297 \if@acmownedtrue
```

Keys:

```
1298 \define@choicekey*{ACM@}{acmcopyrightmode}[%%
1299   \acm@copyrightinput\acm@copyrightmode]{none,%
1300   acmcopyright,acmlicensed,rightsretained,%
1301   usgov,usgovmixed,cagov,cagovmixed,licensedusgovmixed,%
1302   licensedcagov,licensedcagovmixed,othergov,licensedothergov,%
1303   iw3c2w3,iw3c2w3g}{%
1304   \if@printpermissiontrue
1305   \if@printcopyrighttrue
1306   \if@acmownedtrue
1307   \ifnum\acm@copyrightmode=0\relax % none
1308   \if@printpermissionfalse
1309   \if@printcopyrightfalse
1310   \if@acmownedfalse
1311   \fi
1312   \ifnum\acm@copyrightmode=2\relax % acmlicensed
1313   \if@acmownedfalse
1314   \fi
1315   \ifnum\acm@copyrightmode=3\relax % rightsretained
1316   \if@acmownedfalse
1317   \acmPrice{}%
1318   \fi
1319   \ifnum\acm@copyrightmode=4\relax % usgov
1320   \if@printpermissiontrue
1321   \if@printcopyrightfalse
1322   \if@acmownedfalse
1323   \acmPrice{}%
1324   \fi
1325   \ifnum\acm@copyrightmode=6\relax % cagov
1326   \if@acmownedfalse
1327   \fi
1328   \ifnum\acm@copyrightmode=8\relax % licensedusgovmixed
1329   \if@acmownedfalse
1330   \fi
```

```

1331 \ifnum\acm@copyrightmode=9\relax % licensedcagov
1332   \@acmownedfalse
1333 \fi
1334 \ifnum\acm@copyrightmode=10\relax % licensedcagovmixed
1335   \@acmownedfalse
1336 \fi
1337 \ifnum\acm@copyrightmode=11\relax % othergov
1338   \@acmownedtrue
1339 \fi
1340 \ifnum\acm@copyrightmode=12\relax % licensedothergov
1341   \@acmownedfalse
1342 \fi
1343 \ifnum\acm@copyrightmode=13\relax % iw3c2w3
1344   \@acmownedfalse
1345 \fi
1346 \ifnum\acm@copyrightmode=14\relax % iw3c2w3g
1347   \@acmownedfalse
1348 \fi}

\setcopyright This is the syntactic sugar around setting keys.
1349 \def\setcopyright#1{\setkeys{ACM@}{acmcopyrightmode=#1}}
1350 \setcopyright{acmcopyright}

\@copyrightowner Here is the owner of the copyright
1351 \def\@copyrightowner{%
1352   \ifcase\acm@copyrightmode\relax % none
1353     \or % acmcopyright
1354     Association for Computing Machinery.
1355     \or % acmlicensed
1356     Copyright held by the owner/author(s). Publication rights licensed to
1357     the Association for Computing Machinery.
1358     \or % rightsretained
1359     Copyright held by the owner/author(s).
1360     \or % usgov
1361     \or % usgovmixed
1362     Association for Computing Machinery.
1363     \or % cagov
1364     Crown in Right of Canada.
1365     \or %cagovmixed
1366     Association for Computing Machinery.
1367     \or %licensedusgovmixed
1368     Copyright held by the owner/author(s). Publication rights licensed to
1369     the Association for Computing Machinery.
1370     \or % licensedcagov
1371     Crown in Right of Canada. Publication rights licensed to
1372     the Association for Computing Machinery.
1373     \or %licensedcagovmixed
1374     Copyright held by the owner/author(s). Publication rights licensed to
1375     the Association for Computing Machinery.
1376     \or % othergov

```

```

1377 Association for Computing Machinery.
1378 \or % licensedothergov
1379 Copyright held by the owner/author(s). Publication rights licensed to
1380 the Association for Computing Machinery.
1381 \or % ic2w3www
1382 IW3C2 (International World Wide Web Conference Committee), published
1383 under Creative Commons CC~BY~4.0 License.
1384 \or % ic2w3wwwgoogle
1385 IW3C2 (International World Wide Web Conference Committee), published
1386 under Creative Commons CC~BY-NC-ND~4.0 License.
1387 \fi}

\@formatdoi Print a clickable DOI
1388 \def\@formatdoi#1{\url{https://doi.org/#1} }

\@copyrightpermission The canned permission block.
1389 \def\@copyrightpermission{%
1390   \ifcase\acm@copyrightmode\relax % none
1391     \or % acmcopyright
1392       Permission to make digital or hard copies of all or part of this
1393       work for personal or classroom use is granted without fee provided
1394       that copies are not made or distributed for profit or commercial
1395       advantage and that copies bear this notice and the full citation on
1396       the first page. Copyrights for components of this work owned by
1397       others than ACM must be honored. Abstracting with credit is
1398       permitted. To copy otherwise, or republish, to post on servers or to
1399       redistribute to lists, requires prior specific permission
1400       and\hspace*{.5pt}/or a fee. Request permissions from
1401       permissions@acm.org.
1402   \or % acmlicensed
1403     Permission to make digital or hard copies of all or part of this
1404     work for personal or classroom use is granted without fee provided
1405     that copies are not made or distributed for profit or commercial
1406     advantage and that copies bear this notice and the full citation on
1407     the first page. Copyrights for components of this work owned by
1408     others than the author(s) must be honored. Abstracting with credit
1409     is permitted. To copy otherwise, or republish, to post on servers
1410     or to redistribute to lists, requires prior specific permission
1411     and\hspace*{.5pt}/or a fee. Request permissions from
1412     permissions@acm.org.
1413   \or % rightsretained
1414     Permission to make digital or hard copies of part or all of this work
1415     for personal or classroom use is granted without fee provided that
1416     copies are not made or distributed for profit or commercial advantage
1417     and that copies bear this notice and the full citation on the first
1418     page. Copyrights for third-party components of this work must be
1419     honored. For all other uses, contact the
1420     owner\hspace*{.5pt}/author(s).
1421   \or % usgov
1422     This paper is authored by an employee(s) of the United States

```

1423 Government and is in the public domain. Non-exclusive copying or
1424 redistribution is allowed, provided that the article citation is
1425 given and the authors and agency are clearly identified as its
1426 source.

1427 \or % usgovmixed

1428 ACM acknowledges that this contribution was authored or co-authored
1429 by an employee, contractor, or affiliate of the United States government. As such,
1430 the United States government retains a nonexclusive, royalty-free right to
1431 publish or reproduce this article, or to allow others to do so, for
1432 government purposes only.

1433 \or % cagov

1434 This article was authored by employees of the Government of Canada.
1435 As such, the Canadian government retains all interest in the
1436 copyright to this work and grants to ACM a nonexclusive,
1437 royalty-free right to publish or reproduce this article, or to allow
1438 others to do so, provided that clear attribution is given both to
1439 the authors and the Canadian government agency employing them.
1440 Permission to make digital or hard copies for personal or classroom
1441 use is granted. Copies must bear this notice and the full citation
1442 on the first page. Copyrights for components of this work owned by
1443 others than the Canadian Government must be honored. To copy
1444 otherwise, distribute, republish, or post, requires prior specific
1445 permission and\hspace*{.5pt}/or a fee. Request permissions from
1446 permissions@acm.org.

1447 \or % cagovmixed

1448 ACM acknowledges that this contribution was co-authored by an
1449 affiliate of the national government of Canada. As such, the Crown
1450 in Right of Canada retains an equal interest in the copyright.
1451 Reprints must include clear attribution to ACM and the author's
1452 government agency affiliation. Permission to make digital or hard
1453 copies for personal or classroom use is granted. Copies must bear
1454 this notice and the full citation on the first page. Copyrights for
1455 components of this work owned by others than ACM must be honored.
1456 To copy otherwise, distribute, republish, or post, requires prior
1457 specific permission and\hspace*{.5pt}/or a fee. Request permissions
1458 from permissions@acm.org.

1459 \or % licensedusgovmixed

1460 Publication rights licensed to ACM\@. ACM acknowledges that this
1461 contribution was authored or co-authored by an employee, contractor
1462 or affiliate of the United States government. As such, the
1463 Government retains a nonexclusive, royalty-free right to publish or
1464 reproduce this article, or to allow others to do so, for Government
1465 purposes only.

1466 \or % licensedcagov

1467 This article was authored by employees of the Government of Canada.
1468 As such, the Canadian government retains all interest in the
1469 copyright to this work and grants to ACM a nonexclusive,
1470 royalty-free right to publish or reproduce this article, or to allow
1471 others to do so, provided that clear attribution is given both to
the authors and the Canadian government agency employing them.

1473 Permission to make digital or hard copies for personal or classroom
1474 use is granted. Copies must bear this notice and the full citation
1475 on the first page. Copyrights for components of this work owned by
1476 others than the Canadian Government must be honored. To copy
1477 otherwise, distribute, republish, or post, requires prior specific
1478 permission and\hspace*{.5pt}/or a fee. Request permissions from
1479 permissions@acm.org.
1480 \or % licensedcagovmixed
1481 Publication rights licensed to ACM\@. ACM acknowledges that this
1482 contribution was authored or co-authored by an employee, contractor
1483 or affiliate of the national government of Canada. As such, the
1484 Government retains a nonexclusive, royalty-free right to publish or
1485 reproduce this article, or to allow others to do so, for Government
1486 purposes only.
1487 \or % othergov
1488 ACM acknowledges that this contribution was authored or co-authored
1489 by an employee, contractor or affiliate of a national government. As
1490 such, the Government retains a nonexclusive, royalty-free right to
1491 publish or reproduce this article, or to allow others to do so, for
1492 Government purposes only.
1493 \or % licensedothergov
1494 Publication rights licensed to ACM\@. ACM acknowledges that this
1495 contribution was authored or co-authored by an employee, contractor
1496 or affiliate of a national government. As such, the Government
1497 retains a nonexclusive, royalty-free right to publish or reproduce
1498 this article, or to allow others to do so, for Government purposes
1499 only.
1500 \or % iw3c2w3
1501 This paper is published under the Creative Commons Attribution~4.0
1502 International (CC~BY~4.0) license. Authors reserve their rights to
1503 disseminate the work on their personal and corporate Web sites with
1504 the appropriate attribution. In case of republication, reuse, etc.,
1505 the following attribution should be used: ‘‘Published in
1506 WWW\@acmYear{} Proceedings \textcopyright{} \@copyrightyear{}
1507 International World Wide Web Conference Committee, published under
1508 Creative Commons~CC~BY~4.0 License.’’
1509 \or % iw3c2w3g
1510 This paper is published under the Creative Commons
1511 Attribution-NonCommercial-NoDerivs~4.0 International
1512 (CC~BY-NC-ND~4.0) license. Authors reserve their rights to
1513 disseminate the work on their personal and corporate Web sites with
1514 the appropriate attribution. In case of republication, reuse, etc.,
1515 the following attribution should be used: ‘‘Published in
1516 WWW\@acmYear{} Proceedings \textcopyright{} \@copyrightyear{}
1517 International World Wide Web Conference Committee, published under
1518 Creative Commons CC~BY-NC-ND~4.0 License.’’
1519 \fi}

\copyrightyear By default, the copyright year is the same as \acmYear, but one can override this:
1520 \def\copyrightyear{\def\@copyrightyear{#1}}

```

1521 \copyrightyear{@acmYear}

@teaserfigures The teaser figures container
1522 \def@teaserfigures{}

teaserfigure The teaser figure
1523 \newenvironment{teaserfigure}{\Collect@Body@saveteaser}{}

@saveteaser Saving the teaser
1524 \long\def@saveteaser#1{\g@addto@macro@teaserfigures{@teaser{#1}}}

\thanks We redefine amsart \thanks so the anonymous key works
1525 \renewcommand{\thanks}[1]{%
1526   \ifnotempty{#1}{%
1527     \if@ACM@anonymous
1528       \g@addto@macro\thankses{\thanks{A note}}%
1529     \else
1530       \g@addto@macro\thankses{\thanks{#1}}%
1531     \fi}%
}

```

3.14 Typesetting top matter

```

@mkttitle@bx Some of our formats use a two-column design. Some use a one-column design. In all
cases we use a wide title. Thus we typeset the top matter in a special box to be used in
the construction \@twocolumn[<box>].
1532 \newbox@mkttitle@bx

\maketitle The (in)famous \maketitle. Note that in sigchi-a mode, authors are not in the title
box.
Another note: there is a subtle difference between author notes, title notes and
thanks. The latter two refer to the paper itself and therefore belong to the copy-
right/permission block. By the way, this was the default behavior of the old ACM classes.
1533 \def\maketitle{%
1534   \if@ACM@anonymous
1535     % Anonymize omission of \author-s
1536     \ifnum\num@authorgroups=0\author{}\fi
1537   \fi
1538   \begingroup
1539   \let\@footnotemark\@footnotemark@nolink
1540   \let\@footnotetext\@footnotetext@nolink
1541   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1542   \global\@topnum\z@ % this prevents floats from falling
1543           % at the top of page 1
1544   \global\@botnum\z@ % we do not want them to be on the bottom either
1545   \hsize=\textwidth
1546   \def\@makefnmark{\hbox{\@textsuperscript{\@thefnmark}}}%
1547   \mkttitle\if@ACM@sigchiamode\else\mkauthors\fi\mkteasers
1548   \printtopmatter
}

```

```

1549 \if@ACM@sigchiamode\@mkauthors\fi
1550 \setcounter{footnote}{0}%
1551 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}%
1552 \@titlenotes
1553 \@subtitlenotes
1554 \@authornotes
1555 \let\@makefnmark\relax
1556 \let\@thefnmark\relax
1557 \let\@makefntext\noindent
1558 \ifx\@empty\thankses\else
1559   \footnotetextauthorsaddresses{%
1560     \def\par{\let\par\@par}\par\indent\z@\@setthanks}%
1561 \fi
1562 \ifx\@empty\@authorsaddresses\else
1563   \if@ACM@anonymous\else
1564     \if@ACM@journal
1565       \footnotetextauthorsaddresses{%
1566         \def\par{\let\par\@par}\par\indent\z@\@setauthorsaddresses}%
1567       \fi
1568     \fi
1569   \fi
1570 \footnotetextcopyrightpermission{%
1571   \if@ACM@authordraft
1572     \raisebox{-2ex}{[\z@][\z@]{\makebox[0pt][l]{\large\bfseries
1573       Unpublished working draft. Not for distribution.}}}%
1574     \color[gray]{0.9}%
1575   \fi
1576   \par\indent\z@\parskip0.1\baselineskip
1577   \if@ACM@authorversion\else
1578     \if@printpermission\@copyrightpermission\par\fi
1579   \fi
1580   \if@ACM@manuscript\else
1581     \if@ACM@journal\else % Print the conference information
1582       \itshape \acmConference@shortname, \acmConference@date, \acmConference@venue\par
1583     \fi
1584   \fi
1585   \if@printcopyright
1586     \copyright\ \@copyrightyear\ \@copyrightowner\\
1587   \else
1588     \@copyrightyear.\
1589   \fi
1590   \if@ACM@manuscript
1591     Manuscript submitted to ACM\\
1592   \else
1593     \if@ACM@authorversion
1594       This is the author's version of the work. It is posted here for
1595       your personal use. Not for redistribution. The definitive Version
1596       of Record was published in
1597       \if@ACM@journal
1598         \emph{\@journalName}%

```

```

1599      \else
1600          \emph{@acmBooktitle}%
1601      \fi
1602      \ifx{@acmDOI}{\empty}
1603      .
1604      \else
1605          , \@formatdoi{@acmDOI}.
1606      \fi \\
1607  \else
1608      \if@ACM@journal
1609          \@permissionCodeOne/@acmYear/@acmMonth-ART@acmArticle
1610          \ifx{@acmPrice}{\empty}\else\ $@acmPrice\fi\\
1611          \@formatdoi{@acmDOI}%
1612      \else % Conference
1613          \ifx{@acmISBN}{\empty}\else ACM~ISBN~@acmISBN
1614          \ifx{@acmPrice}{\empty}. \else\ dots\$@acmPrice\fi\\
1615          \ifx{@acmDOI}{\empty}\else \@formatdoi{@acmDOI}\fi%
1616          \fi
1617          \fi
1618      \fi
1619  \endgroup
1620  \setcounter{footnote}{0}%
1621  \mkabstract
1622  \if@ACM@printccs
1623      \ifx{@concepts}{\empty}\else\bgroup
1624          \specialsection{CCS Concepts}%
1625          \@concepts\par\egroup
1626      \fi
1627  \fi
1628  \ifx{@keywords}{\empty}\else\bgroup
1629      \if@ACM@journal
1630          \@specialsection{Additional Key Words and Phrases}%
1631      \else
1632          \@specialsection{Keywords}%
1633      \fi
1634      \@keywords\par\egroup
1635  \fi
1636  \andify{authors}
1637  \andify{shortauthors}
1638  \global\let{authors}=\authors
1639  \global\let{shortauthors}=\shortauthors
1640  \if@ACM@printacmref
1641      \mkbibcitation
1642  \fi
1643  \hypersetup{%
1644      pdflang={English},
1645      pdfdisplaydoctitle,
1646      pdfauthor={\authors},
1647      pdftitle={\@title},
1648      pdfsubject={\@concepts},

```

```

1649     pdfkeywords={\@keywords},
1650     pdfcreator={LaTeX with acmart
1651         \csname ver@acmart.cls\endcsname\space
1652         and hyperref
1653         \csname ver@hyperref.sty\endcsname}\}%
1654     \@printendtopmatter
1655     \@afterindentfalse
1656     \@afterheading
1657 }

\@specialsection This macro starts sections for proceedings and uses \small for journals
1658 \def\@specialsection#1{%
1659   \ifcase\ACM@format@nr
1660     \relax % manuscript
1661     \par\medskip\small\noindent#1: %
1662   \or % acmsmall
1663     \par\medskip\small\noindent#1: %
1664   \or % acmlarge
1665     \par\medskip\small\noindent#1: %
1666   \or % acmtog
1667     \par\medskip\small\noindent#1: %
1668   \or % sigconf
1669     \section*{\#1}%
1670   \or % siggraph
1671     \section*{\#1}%
1672   \or % sigplan
1673     \paragraph*{\#1}%
1674   \or % sigchi
1675     \section*{\#1}%
1676   \or % sigchi-a
1677     \section*{\#1}%
1678   \fi}

\@printtopmatter The printing of top matter starts a new page and uses the given title box. Note that
for sigchi-a we print badges here rather than in \mkttitle since we want them in the
margins.
1679 \def\@printtopmatter{%
1680   \ifx\@startPage\@empty
1681     \gdef\@startPage{1}%
1682   \else
1683     \setcounter{page}{\@startPage}%
1684   \fi
1685   \thispagestyle{firstpagestyle}%
1686   \noindent
1687   \ifcase\ACM@format@nr
1688     \relax % manuscript
1689     \box\mkttitle@bx\par
1690   \or % acmsmall
1691     \box\mkttitle@bx\par

```

```

1692 \or % acmlarge
1693   \box\mkttitle@bx\par
1694 \or % acmtog
1695   \twocolumn[\box\mkttitle@bx]%
1696 \or % sigconf
1697   \twocolumn[\box\mkttitle@bx]%
1698 \or % siggraph
1699   \twocolumn[\box\mkttitle@bx]%
1700 \or % sigplan
1701   \twocolumn[\box\mkttitle@bx]%
1702 \or % sigchi
1703   \twocolumn[\box\mkttitle@bx]%
1704 \or % sigchi-a
1705   \par\box\mkttitle@bx\par\bigskip
1706   \if@ACM@badge
1707     \marginpar{\noindent
1708       \ifx\@acmBadgeL@image\empty\else
1709         \href{(\@acmBadgeL@url)}{%
1710           \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}%
1711         \hskip\@ACM@badge@skip
1712       \fi
1713       \ifx\@acmBadgeR@image\empty\else
1714         \href{(\@acmBadgeR@url)}{%
1715           \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}%
1716       \fi}%
1717     \fi
1718   \fi
1719 }

@mkttitle The title of the article
1720 \def@mkttitle{%
1721   \ifcase\ACM@format@nr
1722     \relax % manuscript
1723     \mkttitle@i
1724   \or % acmsmall
1725     \mkttitle@i
1726   \or % acmlarge
1727     \mkttitle@i
1728   \or % acmtog
1729     \mkttitle@i
1730   \or % sigconf
1731     \mkttitle@iii
1732   \or % siggraph
1733     \mkttitle@iii
1734   \or % sigplan
1735     \mkttitle@iii
1736   \or % sigchi
1737     \mkttitle@iii
1738   \or % sigchi-a
1739     \mkttitle@iv

```

```

1740 \fi
1741 }

\@titlefont The font to typeset the title
1742 \def\@titlefont{%
1743   \ifcase\ACM@format@nr
1744     \relax % manuscript
1745     \LARGE\sffamily\bfseries
1746   \or % acmsmall
1747     \LARGE\sffamily\bfseries
1748   \or % acmlarge
1749     \LARGE\sffamily\bfseries
1750   \or % acmtog
1751     \Huge\sffamily
1752   \or % sigconf
1753     \Huge\sffamily\bfseries
1754   \or % siggraph
1755     \Huge\sffamily\bfseries
1756   \or % sigplan
1757     \Huge\bfseries
1758   \or % sigchi
1759     \Huge\sffamily\bfseries
1760   \or % sigchi-a
1761     \Huge\bfseries
1762   \fi}

\@subtitlefont The font to typeset the subtitle
1763 \def\@subtitlefont{\normalsize
1764   \ifcase\ACM@format@nr
1765     \relax % manuscript
1766     \mdseries
1767   \or % acmsmall
1768     \mdseries
1769   \or % acmlarge
1770     \mdseries
1771   \or % acmtog
1772     \LARGE
1773   \or % sigconf
1774     \LARGE\mdseries
1775   \or % siggraph
1776     \LARGE\mdseries
1777   \or % sigplan
1778     \LARGE\mdseries
1779   \or % sigchi
1780     \LARGE\mdseries
1781   \or % sigchi-a
1782     \mdseries
1783   \fi}

```

```

\@mkttitle@i The version of \mkttitle for most journals
1784 \def\@mkttitle@i{\hsize=\textwidth
1785   \@ACM@title@width=\hsize
1786   \ifx\@acmBadgeL@image\empty\else
1787     \advance\@ACM@title@width by -\@ACM@badge@width
1788     \advance\@ACM@title@width by -\@ACM@badge@skip
1789   \fi
1790   \ifx\@acmBadgeR@image\empty\else
1791     \advance\@ACM@title@width by -\@ACM@badge@width
1792     \advance\@ACM@title@width by -\@ACM@badge@skip
1793   \fi
1794   \setbox\mkttitle@bx=\vbox{\noindent\@titlefont
1795     \ifx\@acmBadgeL@image\empty\else
1796       \raisebox{-.5\baselineskip}{[\z@][\z@]{\href{\@acmBadgeL@url}{%
1797         \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}}}%
1798       \hskip\@ACM@badge@skip
1799     \fi
1800     \parbox[t]{\@ACM@title@width}{\raggedright
1801       \@titlefont\noindent
1802       \@title
1803     \ifx\@subtitle\empty\else
1804       \par\noindent{\@subtitlefont\@subtitle}
1805     \fi}%
1806   \ifx\@acmBadgeR@image\empty\else
1807     \hskip\@ACM@badge@skip
1808     \raisebox{-.5\baselineskip}{[\z@][\z@]{\href{\@acmBadgeR@url}{%
1809       \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}}%
1810   \fi
1811   \par\bigskip}%
1812
\@mkttitle@ii The version of \mkttitle for TOG. Since v1.06, this is subsumed by the \mkttitle@i
macro
1813
\@mkttitle@iii The version of \mkttitle for SIG proceedings. Note that since the title is centered, we
leave space for the left badge even if only the right badge is defined.
1814 \def\@mkttitle@iii{\hsize=\textwidth
1815   \setbox\mkttitle@bx=\vbox{\@titlefont\centering
1816     \@ACM@title@width=\hsize
1817     \if@ACM@badge
1818       \advance\@ACM@title@width by -2\@ACM@badge@width
1819       \advance\@ACM@title@width by -2\@ACM@badge@skip
1820       \parbox[b]{\@ACM@badge@width}{\strut
1821         \ifx\@acmBadgeL@image\empty\else
1822           \raisebox{-.5\baselineskip}{[\z@][\z@]{\href{\@acmBadgeL@url}{%
1823             \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}}}%
1824           \hskip\@ACM@badge@skip
1825         \fi
1826         \parbox[t]{\@ACM@title@width}{\centering\@titlefont

```

```

1826      \@title
1827      \ifx\@subtitle\@empty\else
1828          \par\noindent{\@subtitlefont\@subtitle}
1829      \fi
1830  }%
1831 \if@ACM@badge
1832     \hskip\@ACM@badge@skip
1833     \parbox[b]{\@ACM@badge@width}{\strut
1834         \ifx\@acmBadgeR@image\@empty\else
1835             \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeR@url}{%
1836                 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}}%
1837     \fi}%
1838 \fi
1839 \par\bigskip}%

```

\@mktitle@iv The version of \@mktitle for sigchi-a

```

1840 \def\@mktitle@iv{\hsize=\textwidth
1841   \setbox\mktitle@bx=\vbox{\raggedright\leftskip5pc\@titlefont
1842     \noindent\leavevmode\leaders\hrule height 2pt\hfill\kern0pt\par
1843     \noindent\@title
1844     \ifx\@subtitle\@empty\else
1845       \par\noindent\@subtitlefont\@subtitle
1846     \fi
1847   \par\bigskip}%

```

\@ACM@addtoaddress This macro adds an item to the address using the following rules:

1. If we start a paragraph, add the item
2. Otherwise, add a comma and the item
3. However, the comma is deleted if it is at the end of a line. We use the magic \cleaders trick for this.

```

1848 \newbox\@ACM@commabox
1849 \def\@ACM@addtoaddress#1{%
1850   \ifvmode\else
1851     \if@ACM@affiliation\obeypunctuation\else
1852       \setbox\@ACM@commabox=\hbox{, }%
1853       \unskip\cleaders\copy\@ACM@commabox\hskip\wd\@ACM@commabox
1854     \fi\fi
1855   #1}

```

\institution \position \department Theoretically we can define the macros for \affiliation inside the \@mkauthors-style commands. However, this would lead to a strange error if an author uses them outside \affiliation. Of course we can make them produce an error message, but...

```

1856 \def\streetaddress#1{\unskip\ignorespaces}
1857 \def\postcode#1{\unskip\ignorespaces}
1858 \if@ACM@journal
1859   \def\position#1{\unskip\ignorespaces}
1860 \country

```

```

1860 \def\institution#1{\unskip~#1\ignorespaces}
1861 \def\city#1{\unskip\ignorespaces}
1862 \def\state#1{\unskip\ignorespaces}
1863 \newcommand\department[2][0]{\unskip\ignorespaces}
1864 \def\country#1{\if@ACM@affiliation@obeypunctuation\else, \fi#1\ignorespaces}
1865 \else
1866 \def\position#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1867 \def\institution#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1868 \newcommand\department[2][0]{\if@ACM@affiliation@obeypunctuation
1869     #2\else#2\par\fi}%
1870 % \def\streetaddress#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1871 \let\city\@ACM@addtoaddress
1872 \let\state\@ACM@addtoaddress
1873 % \def\postcode#1{\if@ACM@affiliation@obeypunctuation#1\else\unskip\space#1\fi}%
1874 \let\country\@ACM@addtoaddress
1875 \fi

\@mkauthors Typesetting the authors
1876 \def\@mkauthors{\begingroup
1877   \hsize=\textwidth
1878   \ifcase\ACM@format@nr
1879     \relax % manuscript
1880     \@mkauthors@i
1881   \or % acmsmall
1882     \@mkauthors@i
1883   \or % acmlarge
1884     \@mkauthors@i
1885   \or % acmtog
1886     \@mkauthors@i
1887   \or % sigconf
1888     \@mkauthors@iii
1889   \or % siggraph
1890     \@mkauthors@iii
1891   \or % sigplan
1892     \@mkauthors@iii
1893   \or % sigchi
1894     \@mkauthors@iii
1895   \or % sigchi-a
1896     \@mkauthors@iv
1897   \fi
1898   \endgroup
1899 }

\@authorfont Somehow different conferences use different fonts for author names. Why?
1900 \def\@authorfont{\Large\sffamily}

\@affiliationfont Font for affiliations
1901 \def\@affiliationfont{\normalsize\normalfont}

```

Adjusting fonts for different formats

```
1902 \ifcase\ACM@format@nr
1903   \relax % manuscript
1904   \or % acmsmall
1905     \def\@authorfont{\large\sffamily}
1906     \def\@affiliationfont{\small\normalfont}
1907   \or % acmlarge
1908   \or % acmtog
1909     \def\@authorfont{\LARGE\sffamily}
1910     \def\@affiliationfont{\large}
1911   \or % sigconf
1912     \def\@authorfont{\LARGE}
1913     \def\@affiliationfont{\large}
1914   \or % siggraph
1915     \def\@authorfont{\normalsize\normalfont}
1916     \def\@affiliationfont{\normalsize\normalfont}
1917   \or % sigplan
1918     \def\@authorfont{\Large\normalfont}
1919     \def\@affiliationfont{\normalsize\normalfont}
1920   \or % sigchi
1921     \def\@authorfont{\bfseries}
1922     \def\@affiliationfont{\mdseries}
1923   \or % sigchi-a
1924     \def\@authorfont{\bfseries}
1925     \def\@affiliationfont{\mdseries}
1926 \fi
```

\@typeset@author@line At this point we have \@currentauthors and \@currentaffiliations. We typeset them in the journal style

```
1927 \def\@typeset@author@line{%
1928   \andify{\@currentauthors}\par\noindent
1929   {\@currentauthors}\def\@currentauthors{}%
1930   \ifx{\@currentaffiliations}{\empty}\else
1931     \andify{\@currentaffiliations}
1932     \unskip, {\@currentaffiliations}\par
1933   \fi
1934 }{\@currentaffiliations{}}
```

\@mkauthors@i This version is used in most journal formats. Note that \and between authors with the same affiliation becomes and:

```
1935 \def\@mkauthors@i{%
1936   \def\@currentauthors{}%
1937   \def\@currentaffiliations{}%
1938   \global\let\and\@typeset@author@line
1939   \def\@author##1{%
1940     \ifx{\@currentauthors}{\empty}
1941       \gdef\@currentauthors{\@authorfont\MakeTextUppercase{##1}}%
1942     \else
1943       \g@addto@macro{\@currentauthors}{\and\MakeTextUppercase{##1}}%
```

```

1944     \fi
1945     \gdef\and{}%
1946 \def\email##1##2{%
1947 \def\affiliation##1##2{%
1948   \def\@tempa{##2}\ifx\@tempa\empty\else
1949     \ifx\@currentaffiliations\empty
1950       \gdef\@currentaffiliations{%
1951         \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1952         \setkeys{@ACM@affiliation@}{##1}%
1953         \@affiliationfont##2}%
1954   \else
1955     \g@addto@macro{\@currentaffiliations}{\and
1956       \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1957       \setkeys{@ACM@affiliation@}{##1}##2}%
1958   \fi
1959 \fi
1960   \global\let\and\@typeset@author@line}%
1961 \global\setbox\mkttitle@bx=\vbox{\noindent\box\mkttitle@bx\par\medskip
1962   \noindent\addresses\@typeset@author@line
1963   \par\medskip}%
1964 }

```

\@mkauthors@ii The \@mkauthors@ii command was the version used in acmtog. It is no longer necessary.

\author@bx The box to put an individual author in
1965 \newbox\author@bx

\author@bx@wd The width of the author box
1966 \newdimen\author@bx@wd

\author@bx@sep The separation between author boxes
1967 \newskip\author@bx@sep
1968 \author@bx@sep=1pc\relax

\@typeset@author@bx Typesetting the box with authors. Note that in sigchi-a the box is not centered.
1969 \def\@typeset@author@bx{\bgroup\hsize=\author@bx@wd\def\and{\par}%
1970 \global\setbox\author@bx=\vtop{\if@ACM@sigchiamode\else\centering\fi
1971 \authorfont\@currentauthors\par\affiliationfont
1972 \currentaffiliation\egroup
1973 \box\author@bx\hskip{\author@bx@sep}%
1974 \gdef\@currentauthors{}%
1975 \gdef\@currentaffiliation{}}

\@mkauthors@iii The sigconf version. Here we use a centered design with each author in a separate box.
1976 \def\@mkauthors@iii{%

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must

be of width $(\text{textwidth} - \text{author@bx@sep})/N - \text{author@bx@sep}$, where N is the number of boxes per row.

```

1977  \author@bx@wd=\textwidth\relax
1978  \advance\author@bx@wd by -\author@bx@sep\relax
1979  \ifnum@ACM@authorsperrow>0\relax
1980    \divide\author@bx@wd by \@ACM@authorsperrow\relax
1981  \else
1982    \ifcase\num@authorgroups
1983      \relax % 0?
1984      \or % 1=one author per row
1985      \or % 2=two authors per row
1986        \divide\author@bx@wd by \num@authorgroups\relax
1987      \or % 3=three authors per row
1988        \divide\author@bx@wd by \num@authorgroups\relax
1989      \or % 4=two authors per row (!)
1990        \divide\author@bx@wd by 2\relax
1991      \else % three authors per row
1992        \divide\author@bx@wd by 3\relax
1993    \fi
1994  \fi
1995  \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

1996  \gdef\@currentauthors{}%
1997  \gdef\@currentaffiliation{}%
1998  \def\@author##1{\ifx\@currentauthors\@empty
1999    \gdef\@currentauthors{\par##1}%
2000  \else
2001    \g@addto@macro\@currentauthors{\par##1}%
2002  \fi
2003  \gdef\and{}%
2004  \def\email##1##2{\ifx\@currentaffiliation\@empty
2005    \gdef\@currentaffiliation{\nolinkurl{##2}}%
2006  \else
2007    \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
2008  \fi}%
2009  \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
2010    \gdef\@currentaffiliation{%
2011      \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2012      \setkeys{@ACM@affiliation@}{##1##2}%
2013  \else
2014    \g@addto@macro\@currentaffiliation{\par
2015      \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2016      \setkeys{@ACM@affiliation@}{##1##2}%
2017  \fi
2018  \global\let\and\@typeset@author@bx
2019 }%

```

Actual typesetting is done by the \and macro:

```
2020  \hsize=\textwidth
```

```

2021 \global\setbox\mktitle@bx=\vbox{\noindent
2022   \box\mktitle@bx\par\medskip\leavevmode
2023   \lineskip=1pc\relax\centering\hspace*{-1em}%
2024   \addresses\let\and@\typeset@author@bx\and\par\bigskip}}

```

\@mkauthors@iv The sigchi-a version. We put authors in the main text with no more than 2 authors per line, unless overriden.

```

2025 \def\@mkauthors@iv{%

```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width (\textwidth - \author@bx@sep)/N - \author@bx@sep, where N is the number of boxes per row.

```

2026 \author@bx@wd=\columnwidth\relax
2027 \advance\author@bx@wd by -\author@bx@sep\relax
2028 \ifnum@\ACM@authorsperrow>0\relax
2029   \divide\author@bx@wd by \ACM@authorsperrow\relax
2030 \else
2031   \ifcase\num@authorgroups
2032     \relax % 0?
2033     \or % 1=one author per row
2034     \else % 2=two authors per row
2035       \divide\author@bx@wd by 2\relax
2036     \fi
2037   \fi
2038 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

2039 \gdef\@currentauthors{}%
2040 \gdef\@currentaffiliation{}%
2041 \def\@author##1{\ifx\@currentauthors\@empty
2042   \gdef\@currentauthors{\par##1}%
2043 \else
2044   \g@addto@macro\@currentauthors{\par##1}%
2045 \fi
2046 \gdef\and{}%
2047 \def\email##1##2{\ifx\@currentaffiliation\@empty
2048   \gdef\@currentaffiliation{\nolinkurl{##2}}%
2049 \else
2050   \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
2051 \fi}%
2052 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
2053   \gdef\@currentaffiliation{%
2054     \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2055     \setkeys{@ACM@affiliation@}{##1##2}%
2056   \else
2057     \g@addto@macro\@currentaffiliation{\par
2058       \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2059       \setkeys{@ACM@affiliation@}{##1##2}%
2060   \fi

```

```

2061 \global\let\and\@typeset@author@bx}%
2062 %
Actual typesetting is done by the \and macro
2063 \bgroup\hsize=\columnwidth
2064 \par\raggedright\leftskip=\z@
2065 \lineskip=1pc\noindent
2066 \addresses\let\and\@typeset@author@bx\and\par\bigskip\egroup}

\@mkauthorsaddresses Typesetting authors' addresses in the footnote style
2067 \def\@mkauthorsaddresses{%
2068 \ifnum\num@authors>1\relax
2069 Authors' \else Author's \fi
2070 \ifnum\num@authorgroups>1\relax
2071 addresses: \else address: \fi
2072 \bgroup
2073 \def\streetaddress##1{\unskip\@addpunct, ##1}%
2074 \def\postcode##1{\unskip\@addpunct, ##1}%
2075 \def\position##1{\unskip\ignorespaces}%
2076 \def\institution##1{\unskip\@addpunct, ##1}%
2077 \def\city##1{\unskip\@addpunct, ##1}%
2078 \def\state##1{\unskip\@addpunct, ##1}%
2079 \renewcommand\department[2][0]{\unskip\@addpunct, ##2}%
2080 \def\country##1{\unskip\@addpunct, ##1}%
2081 \def\and{\unskip\@addpunct; }%
2082 \def\author##1{##1}%
2083 \def\email##1##2{\unskip\@addpunct, \nolinkurl{##2}}%
2084 \addresses
2085 \egroup}

\@setaddresses This is an amsart macro that we do not need.
2086 \def\@setaddresses{}

\@authornotemark Adding a footnote mark to authors. This version adds a “normal” footnote mark.
2087 \def\@authornotemark{\g@addto@macro\@currentauthors{\footnotemark\relax}}
```

\@authornotemark Adding a footnote mark to authors with a given number

```
2088 \def\@authornotemark#1{\g@addto@macro\@currentauthors{\footnotemark[#1]}}
```

\@mkteasers Typesetting the teasers

```

2089 \def\@mkteasers{%
2090 \ifx\@teaserfigures\empty\else
2091 \def\@teaser##1{\par\bigskip\bgroup
2092 \captionsetup{type=figure}##1\egroup\par}
2093 \global\setbox\mkttitle@bx=\vbox{\noindent\box\mkttitle@bx\par
2094 \noindent\@teaserfigures\par\medskip}%
2095 \fi}
```

```

\@mkabstract Typesetting the abstract
2096 \def\@mkabstract{\bgroup
2097   \ifx\@abstract\@empty\else
2098     {\phantomsection\addcontentsline{toc}{section}{Abstract}%
2099       \if@ACM@journal
2100         \everypar{\setbox\z@\lastbox\everypar{}}\small
2101       \else
2102         \section*{Abstract}%
2103       \fi
2104     \ignorespaces\@abstract\par}%
2105   \fi\egroup}

\@mkbibcitation Print the bibcitation format
2106 \def\@mkbibcitation{\bgroup
2107   \def\@pages@word{\ifnum\getrefnumber{TotPages}=1\relax page\else pages\fi}%
2108   \def\footnotemark{}%
2109   \def\\{\unskip{} \ignorespaces}%
2110   \def\footnote{\ClassError{\@classname}{Please do note use footnotes
2111     inside a \string\title{} or \string\author{} command! Use
2112     \string\titlenote{} or \string\authornote{} instead!}}%
2113   \def\@article@string{\ifx\@acmArticle\@empty\else,
2114     Article\~\@acmArticle\ \fi}%
2115   \par\medskip\small\noindent\bfseries ACM Reference Format:\par\nobreak
2116   \noindent\authors. \@acmYear. \@title
2117   \ifx\@subtitle\@empty. \else: \@subtitle. \fi
2118   \if@ACM@journal
2119     \textit{\@journalNameShort}
2120     \@acmVolume, \@acmNumber \@article@string (\@acmPubDate),
2121     \ref{TotPages}\~\@pages@word.
2122   \else
2123     In \textit{\@acmBooktitle}%
2124     \ifx\@acmEditors\@empty\textit{.}\else
2125       \andify\@acmEditors\textit{, } \@acmEditors\~\@editorsAbbrev.%
2126     \fi\%
2127     ACM, New York, NY, USA%
2128     \@article@string\unskip, \ref{TotPages}\~\@pages@word.
2129   \fi
2130   \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi
2131 \par\egroup}

\@printendtopmatter End the top matter
2132 \def\@printendtopmatter{\par\bigskip}

\@setthanks We redefine \setthanks using \long
2133 \def\@setthanks{\long\def\thanks{\par\#1\@addpunct.\ }\thanksses}

\@setauthorsaddresses
2134 \def\@setauthorsaddresses{@authorsaddresses\unskip\@addpunct.}

```

3.15 Headers and Footers

We use `fancyhdr` for our headers and footers:

```
2135 \RequirePackage{fancyhdr}

\ACM@linecount@bx This is the box displayed in review mode
2136 \if@ACM@review
2137   \newsavebox{\ACM@linecount@bx}
2138   \newlength\ACM@linecount@bxht
2139   \newcount\ACM@linecount
2140   \ACM@linecount\@ne\relax
2141   \def\ACM@mk@linecount{%
2142     \savebox{\ACM@linecount@bx}[4em][t]{\parbox[t]{4em}{%
2143       \setlength{\ACM@linecount@bxht}{0pt}%
2144       \loop{\color{red}\scriptsize\the\ACM@linecount}\
2145       \global\advance\ACM@linecount by \@ne
2146       \addtolength{\ACM@linecount@bxht}{\baselineskip}%
2147       \ifdim\ACM@linecount@bxht<\textheight\repeat
2148       {\color{red}\scriptsize\the\ACM@linecount}\hfill
2149       \global\advance\ACM@linecount by \@ne}}}
2150 \fi

\ACM@linecountL How to display the box on the left
2151 \def\ACM@linecountL{%
2152   \if@ACM@review
2153   \ACM@mk@linecount
2154   \begin{picture}(0,0)%
2155     \put(-26,-22){\usebox{\ACM@linecount@bx}}%
2156   \end{picture}%
2157 \fi}

\ACM@linecountR How to display the box on the right
2158 \def\ACM@linecountR{%
2159   \if@ACM@review
2160   \ACM@mk@linecount
2161   \begin{picture}(0,0)%
2162     \put(20,-22){\usebox{\ACM@linecount@bx}}%
2163   \end{picture}%
2164 \fi}

\ACM@timestamp The timestamp system
2165 \if@ACM@timestamp
2166   % Subtracting 30 from \time gives us the effect of rounding down despite
2167   % \numexpr rounding to nearest
2168   \newcounter{ACM@time@hours}
2169   \setcounter{ACM@time@hours}{\numexpr (\time - 30) / 60 \relax}
2170   \newcounter{ACM@time@minutes}
2171   \setcounter{ACM@time@minutes}{\numexpr \time - \theACM@time@hours * 60 \relax}
2172   \newcommand\ACM@timestamp{%
```

```

2173   \footnotesize%
2174   \ifx\@acmSubmissionID\empty\relax\else
2175   Submission ID: \@acmSubmissionID.{ }%
2176   \fi
2177   \the\year-\two@digits{\the\month}-\two@digits{\the\day}{ }%
2178   \two@digits{\theACM@time@hours}:\two@digits{\theACM@time@minutes}{. }%
2179   Page \thepage\ of \@startPage--\pageref*{TotPages}.%
2180 }
2181 \fi

\@shortauthors Even if the author redefined \shortauthors, we do not print it in the headers when in anonymous mode:
2182 \def\@shortauthors{\if@ACM@anonymous Anon.\else\shortauthors\fi}

\@headfootfont The font to typeset header and footer text.
2183 \def\@headfootfont{\sffamily}

standardpagestyle The page style for all pages but the first one
2184 \fancypagestyle{standardpagestyle}{%
2185   \fancyhf{}%
2186   \renewcommand{\headrulewidth}{\z@}%
2187   \renewcommand{\footrulewidth}{\z@}%
2188   \ifcase\ACM@format@nr
2189     \relax % manuscript
2190     \fancyhead[LE]{\ACM@linecountL\if@ACM@printfolios\thepage\fi}%
2191     \fancyhead[RO]{\if@ACM@printfolios\thepage\fi}%
2192     \fancyhead[RE]{\@shortauthors}%
2193     \fancyhead[LO]{\ACM@linecountL\shorttitle}%
2194     \fancyfoot[RO,LE]{\footnotesize Manuscript submitted to ACM}%
2195   \or % acmsmall
2196     \fancyhead[LE]{\ACM@linecountL@\headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2197     \fancyhead[RO]{\@headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2198     \fancyhead[RE]{\@headfootfont\@shortauthors}%
2199     \fancyhead[LO]{\ACM@linecountL@\headfootfont\shorttitle}%
2200     \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \acmVolume, No.%
2201     \@acmNumber, Article \@acmArticle. Publication date: \acmPubDate.}%
2202   \or % acmlarge
2203     \fancyhead[LE]{\ACM@linecountL@\headfootfont
2204     \@acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2205     \fancyhead[LO]{\ACM@linecountL}%
2206     \fancyhead[RO]{\@headfootfont
2207     \shorttitle\quad\textbullet\quad\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2208     \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \acmVolume, No.%
2209     \@acmNumber, Article \@acmArticle. Publication date: \acmPubDate.}%
2210   \or % acmtog
2211     \fancyhead[LE]{\ACM@linecountL@\headfootfont
2212     \@acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2213     \fancyhead[LO]{\ACM@linecountL}%
2214     \fancyhead[RE]{\ACM@linecountR}%

```

```

2215 \fancyhead[RO]{\@headfootfont
2216 \shorttitle\quad\textbullet\quad\@acmArticle\if@ACM@printfolios:\thepage\fi\ACM@linecountR}%
2217 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2218 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2219 \else % Proceedings
2220 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2221 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2222 \fancyhead[RE]{\@headfootfont\@shortauthors\ACM@linecountR}%
2223 \fancyhead[LE]{\ACM@linecountL\@headfootfont\acmConference@shortname,
2224 \acmConference@date, \acmConference@venue}%
2225 \fancyhead[RO]{\@headfootfont\acmConference@shortname,
2226 \acmConference@date, \acmConference@venue\ACM@linecountR}%
2227 \fi
2228 \if@ACM@sigchiamode
2229 \fancyhead[offset[L]{\dimexpr(\marginparsep+\marginparwidth)}]%
2230 \fi
2231 \if@ACM@timestamp
2232 \fancyfoot[LO,RE]{\ACM@timestamp}%
2233 \fi
2234 }
2235 \pagestyle{standardpagestyle}

\@folio@wd Folio blob width, height, offsets and max number
\@folio@ht 2236 \newdimen\@folio@wd
\@folio@voffset 2237 \@folio@wd=\z@
\@folio@max 2238 \newdimen\@folio@ht
2239 \@folio@ht=\z@
2240 \newdimen\@folio@voffset
2241 \@folio@voffset=\z@
2242 \def\@folio@max{1}
2243 \ifcase\ACM@format@nr
2244 \relax % manuscript
2245 \or % acmsmall
2246 \@folio@wd=45.75pt\relax
2247 \@folio@ht=1.25in\relax
2248 \@folio@voffset=.2in\relax
2249 \def\@folio@max{8}
2250 \or % acmlarge
2251 \@folio@wd=43.25pt\relax
2252 \@folio@ht=79pt\relax
2253 \@folio@voffset=.55in\relax
2254 \def\@folio@max{10}
2255 \fi

\@folioblob The macro to typeset the folio blob.
2256 \def\@folioblob{\@tempcnta=0\@acmArticleSeq\relax
2257 \ifnum\@tempcnta=0\relax\else
First, we calculate \@acmArticleSeq modulo \@folio@max
2258 \loop

```

```

2259   \ifnum\@tempcnda>\@folio@max\relax
2260     \advance\@tempcnda by - \@folio@max
2261   \repeat
2262   \advance\@tempcnda by -1\relax
2263   \atempdima=\@folio@ht\relax
2264   \multiply\@tempdima by \the\@tempcnda\relax
2265   \advance\@tempdima by -\@folio@voffset\relax
2266   \begin{picture}(0,0)
2267   \makebox[\z@]{\raisebox{-\@tempdima}{%
2268     \rlap{%
2269       \raisebox{-0.45\@folio@ht}{\z@}{\z@}{%
2270         \rule{\@folio@wd}{\@folio@ht}}}}%
2271     \parbox{\@folio@wd}{%
2272       \centering
2273       \textcolor{white}{\LARGE\sffamily\bfseries\@acmArticle}}}}
2274   \end{picture}\fi
2275

```

firstpagestyle The page style for the first page only.

```

2276 \fancypagestyle{firstpagestyle}{%
2277   \fancyhf{}%
2278   \renewcommand{\headrulewidth}{\z@}%
2279   \renewcommand{\footrulewidth}{\z@}%
2280   \ifcase\ACM@format@nr
2281     \relax % manuscript
2282     \fancyhead[L]{\ACM@linecountL}%
2283     \fancyfoot[RO,LE]{\if@ACM@printfolios\small\thepage\fi}%
2284     \fancyfoot[RE,LO]{\footnotesize Manuscript submitted to ACM}%
2285   \or % acmsmall
2286     \fancyfoot[RO,LE]{\footnotesize \journalName, Vol. \acmVolume, No.
2287     \acmNumber, Article \acmArticle. Publication date:
2288     \acmPubDate.}%
2289     \fancyhead[LE]{\ACM@linecountL\folioblob}%
2290     \fancyhead[LO]{\ACM@linecountL}%
2291     \fancyhead[RO]{\folioblob}%
2292     \fancyheadoffset[RO,LE]{0.6\@folio@wd}%
2293   \or % acmlarge
2294     \fancyfoot[RO,LE]{\footnotesize \journalName, Vol. \acmVolume, No.
2295     \acmNumber, Article \acmArticle. Publication date:
2296     \acmPubDate.}%
2297     \fancyhead[RO]{\folioblob}%
2298     \fancyhead[LE]{\ACM@linecountL\folioblob}%
2299     \fancyhead[LO]{\ACM@linecountL}%
2300     \fancyheadoffset[RO,LE]{1.4\@folio@wd}%
2301   \or % acmtog
2302     \fancyfoot[RO,LE]{\footnotesize \journalName, Vol. \acmVolume, No.
2303     \acmNumber, Article \acmArticle. Publication date:
2304     \acmPubDate.}%
2305     \fancyhead[L]{\ACM@linecountL}%

```

```

2306   \fancyhead[R]{\ACM@linecountR}%
2307   \else % Conference proceedings
2308   \fancyhead[L]{\ACM@linecountL}%
2309   \fancyhead[R]{\ACM@linecountR}%
2310   \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2311 \fi
2312 \if@ACM@timestamp
2313   \ifnum\ACM@format@nr=0\relax % Manuscript
2314   \fancyfoot[LO,RE]{\ACM@timestamp\quad}
2315     \footnotesize Manuscript submitted to ACM}
2316   \else
2317   \fancyfoot[LO,RE]{\ACM@timestamp}
2318   \fi
2319 \fi
2320 }

```

\ACM@restore@pagestyle The following code by Ross Moore protects against changes by the `totpages` package:

```

2321 \let\ACM@ps@plain\ps@plain
2322 \let\ACM@ps@myheadings\ps@myheadings
2323 \let\ACM@ps@headings\ps@headings
2324 \def\ACM@restore@pagestyle{%
2325   \let\ps@plain\ACM@ps@plain
2326   \let\ps@myheadings\ACM@ps@myheadings
2327   \let\ps@headings\ACM@ps@headings}
2328 \AtBeginDocument{\ACM@restore@pagestyle}

```

3.16 Sectioning

Sectioning is different for different levels

```

2329 \renewcommand\section{@startsection{section}{1}{\z@}%
2330 {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2331 {.25\baselineskip}%
2332 {\@secfont}}
2333 \renewcommand\subsection{@startsection{subsection}{2}{\z@}%
2334 {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2335 {.25\baselineskip}%
2336 {\@subsecfont}}
2337 \renewcommand\subsubsection{@startsection{subsubsection}{3}{10pt}%
2338 {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2339 {-3.5\p@}%
2340 {\@subsubsecfont\@adddotafter}}
2341 \renewcommand\paragraph{@startsection{paragraph}{4}{\parindent}%
2342 {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2343 {-3.5\p@}%
2344 {\@parfont\@adddotafter}}
2345 \renewcommand\part{@startsection{part}{9}{\z@}%
2346 {-10\p@ \@plus -4\p@ \@minus -2\p@}%
2347 {4\p@}%
2348 {\@parfont}}

```

```

\section@raggedright Special version of \raggedright compatible with \MakeUppercase
2349 \def\section@raggedright{\@rightskip\@flushglue
2350   \rightskip\@rightskip
2351   \leftskip\z@skip
2352   \parindent\z@}

\@secfont Fonts for sections etc. are different for different formats.
\@subsecfont 2353 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
\@subsubsecfont 2354 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
\@parfont 2355 \def\@subsubsecfont{\sffamily\itshape}
2356 \def\@parfont{\itshape}
2357 \setcounter{secnumdepth}{3}
2358 \ifcase\ACM@format@nr
2359 \relax % manuscript
2360 \or % acmsmall
2361 \or % acmlarge
2362 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2363 \def\@subsecfont{\sffamily\large\section@raggedright}
2364 \or % acmto
2365 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2366 \def\@subsecfont{\sffamily\large\section@raggedright}
2367 \or % sigconf
2368 \def\@secfont{\bfseries\Large\section@raggedright\MakeTextUppercase}
2369 \def\@subsecfont{\bfseries\Large\section@raggedright}
2370 \or % siggraph
2371 \def\@secfont{\sffamily\bfseries\Large\section@raggedright\MakeTextUppercase}
2372 \def\@subsecfont{\sffamily\bfseries\Large\section@raggedright}
2373 \or % sigplan
2374 \def\@secfont{\bfseries\Large\section@raggedright}
2375 \def\@subsecfont{\bfseries\section@raggedright}
2376 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
2377   {-.75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2378   {.25\baselineskip}%
2379   {\@subsubsecfont}}
2380 \def\@subsubsecfont{\bfseries\section@raggedright}
2381 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
2382   {-.5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2383   {-3.5\p@}%
2384   {\@parfont\@addspaceafter}}}
2385 \def\@parfont{\bfseries\itshape}
2386 \renewcommand\ subparagraph{\@startsection{subparagraph}{5}{\z@}%
2387   {-.5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2388   {-3.5\p@}%
2389   {\@subparfont\@addspaceafter}}}
2390 \def\@subparfont{\itshape}
2391 \or % sigchi
2392 \setcounter{secnumdepth}{1}
2393 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
2394 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2395 \or % sigchi-a

```

```

2396 \setcounter{secnumdepth}{0}
2397 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
2398 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2399 \fi

\@adddotafter Add punctuation after a sectioning command
2400 \def\@adddotafter{\#1\@addpunct{.} }

\@addspaceafter Add space after a sectioning command
2401 \def\@addspaceafter{\#1\@addpunct{\enspace} }

```

3.17 TOC lists

\@dotsep Related to the \tableofcontents are all the horizontal fillers. Base L^AT_EX defines \@dottedtocline, which we should not disable. Yet, this command expects \@dotsep to be defined but leaves this to the class implementation. Since amsart does not provide this, we copy the standard variant from article here.

```
2402 \providecommand*\@dotsep{4.5}
```

3.18 Theorems

\@acmplainbodyfont The font to typeset the body of the acmplain theorem style.
2403 \def\@acmplainbodyfont{\itshape}

\@acmplainindent The amount to indent the acmplain theorem style.
2404 \def\@acmplainindent{\parindent}

\@acmplainheadfont The font to typeset the head of the acmplain theorem style.
2405 \def\@acmplainheadfont{\scshape}

\@acmplainnotefont The font to typeset the note of the acmplain theorem style.
2406 \def\@acmplainnotefont{\emptyset}

Customization of the acmplain theorem style:

```

2407 \ifcase\ACM@format@nr
2408 \relax % manuscript
2409 \or % acmsmall
2410 \or % acmlarge
2411 \or % acmtog
2412 \or % sigconf
2413 \or % siggraph
2414 \or % sigplan
2415 \def\@acmplainbodyfont{\itshape}
2416 \def\@acmplainindent{\z@}
2417 \def\@acmplainheadfont{\bfseries}
2418 \def\@acmplainnotefont{\normalfont}
2419 \or % sigchi
2420 \or % sigchi-a
2421 \fi

```

```

acmplain The acmplain theorem style
2422 \newtheoremstyle{acmplain}%
2423   {.5\baselineskip \@plus.2\baselineskip
2424     \@minus.2\baselineskip}% space above
2425   {.5\baselineskip \@plus.2\baselineskip
2426     \@minus.2\baselineskip}% space below
2427   {@acmplainbodyfont}% body font
2428   {@acmplainindent}% indent amount
2429   {@acmplainheadfont}% head font
2430   {.}% punctuation after head
2431   {.5em}% spacing after head
2432   {\thmname{\#1}\thmnumber{\#2}\thmnote{ {\@acmplainnotefont(\#3)}}}% head spec

{@acmdefinitionbodyfont The font to typeset the body of the acmdefinition theorem style.
2433 \def{@acmdefinitionbodyfont}{\normalfont}

{@acmdefinitionindent The amount to indent the acmdefinition theorem style.
2434 \def{@acmdefinitionindent}{\parindent}

{@acmdefinitionheadfont The font to typeset the head of the acmdefinition theorem style.
2435 \def{@acmdefinitionheadfont}{\itshape}

{@acmdefinitionnotefont The font to typeset the note of the acmdefinition theorem style.
2436 \def{@acmdefinitionnotefont}{\emptyset}

Customization of the acmdefinition theorem style:
2437 \ifcase\ACM@format@nr
2438 \relax % manuscript
2439 \or % acmsmall
2440 \or % acmlarge
2441 \or % acmtog
2442 \or % sigconf
2443 \or % siggraph
2444 \or % sigplan
2445 \def{@acmdefinitionbodyfont}{\normalfont}
2446 \def{@acmdefinitionindent}{\z@}
2447 \def{@acmdefinitionheadfont}{\bfseries}
2448 \def{@acmdefinitionnotefont}{\normalfont}
2449 \or % sigchi
2450 \or % sigchi-a
2451 \fi

acmdefinition The acmdefinition theorem style
2452 \newtheoremstyle{acmdefinition}%
2453   {.5\baselineskip \@plus.2\baselineskip
2454     \@minus.2\baselineskip}% space above
2455   {.5\baselineskip \@plus.2\baselineskip
2456     \@minus.2\baselineskip}% space below
2457   {@acmdefinitionbodyfont}% body font

```

```

2458 {\\@acmdefinitionindent}\\% indent amount
2459 {\\@acmdefinitionheadfont}\\% head font
2460 {.}\\% punctuation after head
2461 {.5em}\\% spacing after head
2462 {\\thmname{#1}\\thmnumber{ #2}\\thmnote{ {\\@acmdefinitionnotefont(#3)}}}\\% head spec

```

Make acmplain the default theorem style.

```
2463 \\theoremstyle{acmplain}
```

Delay defining the theorem environments until after other packages have been loaded. In particular, the `cleveref` package must be loaded before the theorem environments are defined in order to show the correct environment name (see <https://github.com/borisveytsman/acmart/issues/138>). The `acmthm` option is used to suppress the definition of any theorem environments. Also, to avoid obscure errors arising from these environment definitions conflicting with environments defined by the user or by user-loaded packages, we only define environments that have not yet been defined.

```

2464 \\AtEndPreamble{%
2465   \\if@ACM@acmthm
2466     \\theoremstyle{acmplain}
2467     \\@ifundefined{theorem}{%
2468       \\newtheorem{theorem}{Theorem}[section]
2469     }{%
2470       \\@ifundefined{conjecture}{%
2471         \\newtheorem{conjecture}[theorem]{Conjecture}
2472       }{%
2473         \\@ifundefined{proposition}{%
2474           \\newtheorem{proposition}[theorem]{Proposition}
2475         }{%
2476           \\@ifundefined{lemma}{%
2477             \\newtheorem{lemma}[theorem]{Lemma}
2478           }{%
2479             \\@ifundefined{corollary}{%
2480               \\newtheorem{corollary}[theorem]{Corollary}
2481             }{%
2482               \\theoremstyle{acmdefinition}
2483               \\@ifundefined{example}{%
2484                 \\newtheorem{example}[theorem]{Example}
2485               }{%
2486                 \\@ifundefined{definition}{%
2487                   \\newtheorem{definition}[theorem]{Definition}
2488                 }{%
2489                   \\fi
2490                   \\theoremstyle{acmplain}
2491     }

```

`\\@proofnamefont` The font to typeset the proof name.

```
2492 \\def\\@proofnamefont{\\scshape}
```

```

{@proofindent Whether or not to indent proofs.
2493 \def{@proofindent}{\indent}

    Customization of the proof environment.

2494 \ifcase\ACM@format@nr
2495 \relax % manuscript
2496 \or % acmsmall
2497 \or % acmlarge
2498 \or % acmtog
2499 \or % sigconf
2500 \or % siggraph
2501 \or % sigplan
2502 \def{@proofnamefont}{\itshape}
2503 \def{@proofindent}{\noindent}
2504 \or % sigchi
2505 \or % sigchi-a
2506 \fi

proof We want some customization of the proof environment.

2507 \renewenvironment{proof}[1][\proofname]{\par
2508   \pushQED{\qed}%
2509   \normalfont \topsep6\p@\oplus6\p@\relax
2510   \trivlist
2511   \item[\@proofindent\hspace{\labelsep
2512     {\@proofnamefont #1}\@addpunct{.}}]\ignorespaces
2513 }{%
2514   \popQED\endtrivlist\endpefalse
2515 }

```

3.19 Acknowledgments

```

\acks This is a comment-like structure

2516 \specialcomment{acks}{%
2517   \begingroup
2518   \section*{Acknowledgments}
2519   \phantomsection\addcontentsline{toc}{section}{Acknowledgments}
2520 }{%
2521   \endgroup
2522 }

\grantsponsor We just typeset the name of the sponsor

2523 \def\grantsponsor#1#2#3{#2}

\grantnum

2524 \newcommand\grantnum[3][]{\#3%
2525   \def\@tempa{\#1}\ifx\@tempa\empty\else\space(\url{\#1})\fi}

```

3.20 Conditional typesetting

We use the `comment` package for conditional typesetting:

```
2526 \AtEndPreamble{%
2527 \if@ACM@screen
2528   \includecomment{screenonly}
2529   \excludecomment{printonly}
2530 \else
2531   \excludecomment{screenonly}
2532   \includecomment{printonly}
2533 \fi
2534 \if@ACM@anonymous
2535   \excludecomment{anonsuppress}
2536   \excludecomment{acks}
2537 \else
2538   \includecomment{anonsuppress}
2539 \fi}
```

3.21 Additional bibliography commands

- \showeprint The command `\showeprint` has two arguments: the (optional) prefix and the eprint number. Right now the only prefix we understand is the (lowercase) word ‘arxiv’ (see <http://arxiv.org/hyperref/bibstyles/>).

```
2540 \newcommand\showeprint[2][arxiv]{%
2541   \def\@tempa{\#1}%
2542   \ifx\@tempa\empty\def\@tempa{arxiv}\fi
2543   \def\@tempb{arxiv}%
2544   \ifx\@tempa\@tempb
2545     arXiv:\href{http://arxiv.org/abs/#2}{\#2}\else arXiv:#2%
2546   \fi}
```

3.22 End of Class

```
2547 \normalsize\normalfont\frenchspacing
2548 </class>
```

References

- [1] UK TeX Users Group. UK list of TeX frequently asked questions. <http://www.tex.ac.uk>, 2016.
- [2] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://www.ctan.org/pkg/amslatex>.
- [3] Cristophe Fiorio. *algorithm2e.sty—package for algorithms*, October 2015. <http://www.ctan.org/pkg/algorithm2e>.
- [4] Rogério Brito. *The algorithms bundle*, August 2009. <http://www.ctan.org/pkg/algorithms>.
- [5] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*, June 2015. <http://www.ctan.org/pkg/listings>.
- [6] Simon Fear. *Publication quality tables in L^AT_EX*, April 2005. <http://www.ctan.org/pkg/booktabs>.
- [7] Association for Computing Machinery. *ACM Visual Identity Standards*, 2007. <http://identitystandards.acm.org>.
- [8] Axel Sommerfeldt. *The subcaption package*, April 2013. <http://www.ctan.org/pkg/subcaption>.
- [9] Boris Veytsman, Bern Schandl, Lee Netherton, and C. V. Radhakrishnan. *A package to create a nomenclature*, September 2005. <http://www.ctan.org/pkg/nomenc>.
- [10] Nicola L. C. Talbot. *User Manual for glossaries.sty v4.25*, June 2016. <http://www.ctan.org/pkg/subcaption>.
- [11] David Carlisle. *The textcase package*, October 2004. <http://www.ctan.org/pkg/textcase>.

Change History

1.48	\acmDOI: Name change by Matthew Fluet	58
	\acmISBN: Name change by Matthew Fluet	58
	General: Updated bibliography for siggraph	29
v1.00	General: First released version	29
v1.01	General: Changed hyperref colors in screen mode (closes https://github.com/borisveytsman/acmart/issues/1)	29
	Defined ACM colors	29
	Explicitly put draft option (closes https://github.com/borisveytsman/acmart/issues/4)	32
	Set headheight to 1pc for all formats (closes https://github.com/borisveytsman/acmart/issues/5)	29
v1.02	General: Added TOPS and TSC (closes https://github.com/borisveytsman/acmart/issues/12)	29
	Documentation changes (closes https://github.com/borisveytsman/acmart/issues/13)	29
v1.03	\@formatdoi: Added macro	64
	\if@ACM@authorversion: Added macro	31
	\maketitle: Added special case of authorversion	67
	General: Added anonsuppress environment	29
	Added authorversion option (closes https://github.com/borisveytsman/acmart/issues/9)	29
v1.04	\acmArticleSeq: Name change by Matthew Fluet	57
v1.05	General: Added processing doi numbers for acmsiggraph and doi numbers for sigproc.bib	29
	Patched \setcitestyle command; closes https://github.com/borisveytsman/acmart/issues/19	29
v1.06	\@ACM@badge@skip: Added macro	58
	\@ACM@badge@width: Added macro	58
	\@ACM@title@width: Added macro	58
	\@mktitle@i: Added processing badges	72
	Made generic	72
	\@mktitle@ii: Now this macro is obsolete	73
	\@mktitle@iii: Added processing badges	73
	Made more generic	73
	\@mktitle@iv: Made more generic	74
	\@printtopmatter: Added processing badges	70
	\@subtitlefont: Added macro	72
	\@titlefont: Added macro	72
	\acmBadgeL: Added macro	59
	\acmBadgeR: Added macro	59
	\if@ACM@badge: Added macro	58
v1.07	\maketitle: Corrected a bug with abstract footnotes	67
	Corrected a bug with permission and footnotes order	67
v1.08	General: SIGPLAN reformatting by Matthew Fluet	29
	Typos corrected (Tobias Pape)	29
v1.09	General: Revert SIGPLAN caption rules	29

v1.10	\maketitle: Corrected a bug with doi in manuscript and author vertson, https://github.com/borisveytsman/ acmart/issues/36	67	standardpagestyle: Added headers for sigs	83	
	General: Changes of 'licensedothergov' wording	62	Expanded headers for sigchi-a	83	
	standardpagestyle: Reversed folios location	83	Suppressed folios if sig	83	
v1.11	General: Customization of ACM theorem styles and proof environment by Matthew Fluet	29	v1.14	\bibstyle@acmauthoryear: Moved def of \bibstyle@acmauthoryear before use	35
v1.12	\@marginfigure: Now centering by default	45	\bibstyle@acmnumeric: Moved def of \bibstyle@numeric before use	36	
	\@margintable: Now centering by default	46	General: \citetstyle updates (Matthew Fluet)	29	
	\@parfont: Moved to \section@raggedright	87	Patched \citetstyle	34	
	\copyrightpermissionfootnoterule: Added macro	42	v1.15	\@ACM@addtoaddress: Added macro	74
	\descriptionlabel: Redefined	48	\@mkauthors@iii: New authors system	77	
	\footnoterule: Made shorter	42	\@shortauthors: Introduced macro	83	
	\if@ACM@natbib@override: Added macro	31	\@typeset@author@bx: Moved to separate macro	77	
	\if@ACM@newfonts: Added macro	44	\acks: Added macro	91	
	\maketitle: Moved thankses to copyrightpermission box	67	\affiliation: Added code for author groups	55	
	\section@raggedright: Introduced macro	87	\author: Added code for author groups	55	
	General: Added graceful behavior when libertine fonts are absent	44	\city: Added macro	74	
	Documentation updates	29	\country: Added macro	74	
v1.13	\@mpfootnotetext: Made minipage footnotes centered	43	\department: Added macro	74	
	\bibliographystyle: Redefined macro	39	\grantnum: Added macro	91	
	\bibstyle@acmauthoryear: Added macro	35	\grantsponsor: Added macro	91	
	\bibstyle@acmnumeric: Added macro	36	\if@insideauthorgroup: Introduced macro	54	
	\if@ACM@printfolios: Added macro	60	\institution: Added macro	74	
	General: Font adjustments for acmsmall	75	\num@authorgroups: Renamed	54	
	Increased font size for ACM Large	33	\orcid: Introduced macro	56	
	Print bibliographic information by default for the proceedings	60	\position: Added macro	74	
			\postcode: Added macro	74	
			\state: Added macro	74	
			\streetaddress: Added macro	74	
			standardpagestyle: Better handling of anonymous mode	83	
v1.16	\headfootfont: Added macro	83			
	General: Formatting header/footer (Matthew Fluet)	29			
	standardpagestyle: Customize header/footer text font	83			
v1.17	\makefnmark: Redefined	43			

\@mkauthors: TOG now uses the same authors block as other journals	75	v1.23	General: Add PACMPL journal option	29
\@mkauthors@ii: Deleted	77	v1.24	General: Add IMWUT journal option	48
\@mkbibcitation: Added \nobreak	81	v1.25	General: Updated PACMPL	48
Changed format for sigs	81	v1.26	General: Corrected \shortcite bug	29
\acmArticle: The default is now numerical	57	v1.26	Documentation typos fixed (thanks to Stephen Spencer)	29
\acmMonth: The default must be numerical. Closes #50.	58	v1.27	\if@ACM@printccs: Typo corrected	59
\acmNumber: The default is now numerical	57	v1.28	\ccsdesc@parse: Change from \to to \textrightarrow (Matteo Riondato)	61
\acmVolume: The default is now numerical	57	v1.29	General: Corrected option natbib behavior	36
\acmYear: The default is now numerical	58	v1.29	Got rid of warnings in pdf keywords	38
\description: Decreased indent	48	v1.29	\@mkabstract: Removed spurious indentation (John Wickerson)	81
\grantnum: Added url	91	v1.29	\ccsdesc@parse: Add spacing after bullet and around rightarrow; semicolon separators no longer in bold/italic (John Wickerson)	61
\grantsponsor: Renamed	91	v1.29	General: Increased head to 13pt	40
\if@ACM@printacmref: Renamed from \if@ACM@printbib	60	v1.29	standardpagestyle: Corrected printfolios (Matthew Fluet)	83
General: Slightly decreased margins for sigs	40	v1.29	\department: Added optional parameter	74
\standardpagestyle: Added paper title to sigs	83	v1.29	General: Added \frenchspacing	92
v1.18		v1.29	Bibtex style now recognizes https:// in doi	29
\@mkauthors@i: Now we andify affiliations	76	v1.30	Switched to T1: looks like libertine has problems with \l in OT1	44
@\typeset@author@line: Added macro	76	v1.31	Updated IMWUT and PACMPL	48
General: Natbib is now the default for all formats	29	v1.31	\@additionalaffiliation: Added macro	56
v1.19		v1.31	\@mkbibcitation: Disabled linebreak	81
\@mkabstract: Include 'Abstract' in PDF bookmarks (Matthew Fluet)	81	v1.31	\@startsection: Added \tochangmeasure	36
\acks: Include 'Acknowledgements' in PDF bookmarks (Matthew Fluet)	91	v1.31	Redefined macro	38
General: Include 'Abstract', 'Acknowledgements', and 'References' in PDF bookmarks (Matthew Fluet)	29	v1.31	\@textbottom: Redefined	43
Include 'References' in PDF bookmarks (Matthew Fluet)	34	v1.31	\acmMonth: The default now is the current month (Matteo Riondato)	58
v1.20		v1.31	\acmYear: The default now is the current year (Matteo Riondato)	58
\@mkabstract: Deleted spurious space	81			
General: Bug fixes for bst	29			
v1.21				
\showeprint: Added macro	92			
v1.22				
General: More bibliography changes for Aptara	29			

\additionalaffiliation: Added macro	56	\streetaddress: Added obeypunctuation code	74
\l@subsection: Redefined macro	38	General: Added acmart-preload-hook	29
\l@subsubsection: Redefined macro	38	Added cmap and glyptounicode	44
General: Documentation changes	29	BibTeX comma before articleno bug corrected	29
v1.32		BibTeX crossref bug corrected	29
\@formatdoi: New doi format	64	BibTeX numpages bug corrected	29
General: Added POMACS journal option	29	Documentation updates	29
Format siggraph is now obsolete	29	Moved \citemname definition for non-natbib bibliography, so a package may redefine it	39
v1.33		Switched to Type 1 fonts for libertine even if OTF-capable engine is used (Kai Mindermann)	44
\@ACM@addtoaddress: Added obeypunctuation code	74	firstpagestyle: Added right linecount for two-column formats	85
\@mkauthors@i: Added obeypunctuation code	76	Added timestamp (Michael D. Adams)	85
\@mkauthors@ii: Added obeypunctuation code	77	standardpagestyle: Added right linecount for two-column formats	83
\@mkauthors@iv: Added obeypunctuation code	79	Added timestamp (Michael D. Adams)	83
\@subtitlefont: Added \normalsize	72	v1.34	
\ACM@linecountL: Renamed macro	82	\@mkbibcitation: Deleted DOI from doi numbers	81
\ACM@linecountR: Added macro	82	\ACM@linecount@bx: Rulers now are continuous	82
\ACM@timestamp: Added current page number	82	\ACM@linecountL: Rulers now are continuous	82
Added macro (Michael D. Adams)	82	\ACM@linecountR: Rulers now are continuous	82
Added submission id	82	\maketitle: Added date to the bibstrip in conf proceedings	67
\acmSubmissionID: Added macro	58	Deleted 'DOI' from doi numbers	67
\city: Added obeypunctuation code	74	Rearranged bibstrip	67
\country: Added obeypunctuation code	74	The \terms command is now obsolete	67
\department: Added obeypunctuation code	74	\terms: The \terms command now just produces a warning	59
\if@ACM@affiliation@obeypunctuation: Added macro	56	v1.35	
\if@ACM@authordraft: Added macro	31	\bibstyle@acmauthoryear: Square brackets for author-year style	35
\if@ACM@natbib@override: Deleted macro	31	General: BibTeX bug fixed: et al.	29
\if@ACM@timestamp: Added macro (Michael D. Adams)	31	If the copyright is set to usgov or rigtsretained, the price is suppressed	62
\institution: Added obeypunctuation code	74	v1.36	
\maketitle: Fixed the bug with figures on top and bottom of the title page, thanks to David Epstein	67	\@ACM@authorsperrow: Added macro	60
\position: Added obeypunctuation code	74		
\postcode: Added obeypunctuation code	74		
\state: Added obeypunctuation code	74		

\@mkauthors@iii: Added		\state: We now do not print this even	
authorsperrow override	77	in SIG	74
\@mkauthors@iv: Added		\streetaddress: We now do not	
authorsperrow override	79	print this even in SIG	74
\if@ACM@authordraft: Corrected		General: Added ‘textcase’ package . .	34
typo, thanks to bargteil	31	Added heightrounded to geometry	40
General: Added PACMHCI journal		Added new copyright version:	
options	48	licensedcagov	29
Added the possibility to adjust		Added package cleveref	29
number of author boxes per row		Added Ross Moore code for	
in conference formats	29	glyptounicode	44
v1.37		Bibliography changes	29
\description: Reduce list		v1.41	
indentation (Matthew Fluet)	48	General: Added new badges	29
\descriptionlabel: Reduce list		v1.42	
indentation (Matthew Fluet)	48	General: Deleted ACM badges	29
\normalparindent: Set		v1.43	
\normalparindent (Matthew		\@startsection: Added	
Fluet)	42	\makeatletter	38
General: Reduce list indentation		\country: Added comma before	
(Matthew Fluet)	47	country for journals	74
Set \normalparindent; Reduce list		v1.44	
indentation (Matthew Fluet)	29	\@acmBooktitle: Added macro	54
v1.38		\@acmEditors: Added macro	54
General: Increase default font size for		\@editorsAbbrev: Added macro	54
SIGPLAN	29, 33	\@folioblob: Suppress the blob if	
v1.39		acmArticleSeq is empty	84
\@@authornotemark: Added macro . .	80	\@mkbibcitation: If the paper has	
\authornotemark: Added macro . . .	57	just one page, use ‘page’ instead of	
v1.40		‘pages’	81
\@copyrightowner: Added new		\ACM@restore@pagestyle: Added	
copyright version: licensedcagov .	63	macro	86
\@copyrightpermission: Added new		\acmArticle: The default is now	
copyright version: licensedcagov .	64	empty	57
\@mkauthors@i: Switched to		\acmArticleSeq: Now acmArticle	
MakeTextUppercase	76	might be empty	57
\@parfont: Switched to		\acmBooktitle: Added macro	54
MakeTextUppercase	87	\editor: Added macro	54
\ACM@linecount@bx: Work around a		\if@ACM@acmthm: Added macro	30
bug in xcolor: looks like cmyk		\maketitle: Empty DOI or ISBN are	
colors in boxes do not work	82	not printed (by Michael Ekstrand) .	67
\ccdesc@parse@finish: Added		General: Added package refcount . . .	29
macro	61	Deleted package cleveref	29
\city: We now do not print this even		Put theorem defs in a separate style .	29
in SIG	74		
\country: Fixed bugs with extra		v1.45	
spaces	74	\@folioblob: Switched	
\l@subsection: Redefined macro . .	38	\bfseries\sffamily to	
\postcode: We now do not print this		\sffamily\bfseries	84
even in SIG	74		

\@parfont: Switched	Bst file bug fixes: label width is calculated correctly	29
\bfseries\sffamily to		
\sffamily\bfseries	87	
\@titlefont: Switched	Delayed hypersetup since journal options may change screen mode	38
\bfseries\sffamily to		
\sffamily\bfseries	72	
v1.46	PACM now set screen to true	48
\@mkauthorsaddresses: Introduced	Restore theorem defs to class file	29
macro		
\@mkbibcitation: Added subtitle		
\@printendtopmatter: Made it	General: New journal: THRI	29
\par\bigskip uniformly		
\@printtopmatter: Deleted rule	v1.48	
\@setauthorsaddresses: Introduced	\@headfootfont: Deleted unnecessary switch (Michael D. Adams)	83
macro		
\ACM@linecount@bx: Rearranged the code to get rid of spurious underfull messages (Benjamin Byholm)	\@mkabstract: Removed spurious indentation if abstract is followed by an empty line	81
\author: Started counting authors	\ACM@timestamp: Fromatting change (Michael D. Adams)	82
\authorsaddresses: Introduced	\if@ACM@review: Review mode now switches on folios	30
macro	\maketitle: Added acmart and version info to pdfcreator tag	67
\country: Corrected spacing for institution	Added language and doctitle attributes to PDF (Andreas Reichinger)	67
\if@ACM@acmthm: Modified description	Suppressed empty DOI (Serguei Mokhov)	67
\liningnums: Workaround for compatibility with fontspec	General: \citeyear no longer behaves like \citeyearpar	39
\maketitle: Added authors' addresses	Code prettying (Michael D. Adams)	29
Thankses go before authors' addresses	Initial support for Biblatex (Daniel Thomas)	29
\num@authors: Introduced macro	Misc entries in the bibliography no longer produce a separate date	29
General: Added etoolbox	Typos fixed (Jamie Davis)	29

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols			
\\$	1610, 1614	@ACM@title@width ..	2218, 2288, 2296, 2304
\@	1460, 1481, 1494 1190,	\@acmSubmissionID ..
\@eauthornotemark ..		1785, 1787, 1788,	... 1180, 2174, 2175
..... 1160, 2088		1791, 1792, 1800,	\@acmVolume 1162,
\@epar	317, 374	1814, 1816, 1817, 1825	2120, 2200, 2208,
\@ACM@addtoaddress ..		\@DeclareACMFormat .	2217, 2286, 2294, 2302
..... 1848, 1871, 1872, 1874		... 38, 39, 40, 41,	\@acmYear
\@ACM@authorsperrow ..		42, 43, 44, 45, 46, 47	1170, 1177, 1506,
..... 1231,		\@M 317, 356, 374, 383	1516, 1521, 1609, 2116
1979, 1980, 2028, 2029		\@abstract 1210, 2097, 2104	\@acmdefinitionbodyfont
\@ACM@badge@skip ..		\@acmArticle 1166, 1169,	... 2433, 2445, 2457
.... 1191, 1711,		1609, 2113, 2114,	\@acmdefinitionheadfont
1788, 1792, 1798,		2196, 2197, 2201,	... 2435, 2447, 2459
1807, 1817, 1823, 1832		2204, 2207, 2209,	\@acmdefinitionindent
\@ACM@badge@width ..		2212, 2216, 2218,	... 2434, 2446, 2458
.... 1188, 1710,		2273, 2287, 2295, 2303	\@acmdefinitionnotefont
1715, 1787, 1791,		\@acmArticleSeq 1168, 2256	... 2436, 2448, 2462
1797, 1809, 1816,		\@acmBadgeL@image ..	\@acmownedfalse . 1310,
1818, 1821, 1833, 1836	 1200, 1202,	1313, 1316, 1322,
\@ACM@badgefalse ..	1187	1708, 1710, 1786,	1326, 1329, 1332,
\@ACM@badgetrue 1193, 1198		1795, 1797, 1819, 1821	1335, 1341, 1344, 1347
\@ACM@commabox ..		\@acmBadgeL@url . 1199,	\@acmownedtrue ..
.... 1848, 1852, 1853		1201, 1709, 1796, 1820	... 1297, 1306, 1338
\@ACM@journalfalse ..		\@acmBadgeR@image ..	\@acmplainbodyfont .
149, 151, 153, 155, 157	 1195, 1197,	... 2403, 2415, 2427
\@ACM@journaltrue ..		1713, 1715, 1790,	\@acmplainheadfont .
.... 141, 143, 145, 147		1806, 1809, 1834, 1836	... 2405, 2417, 2429
\@ACM@labelwidth ..		\@acmBadgeR@url . 1194,	\@acmplainindent ..
712, 715, 723, 728, 754		1196, 1714, 1808, 1835	... 2404, 2416, 2428
\@ACM@manuscriptfalse 136		\@acmBooktitle ..	\@acmplainnotefont .
\@ACM@manuscripttrue 134		... 1044, 1600, 2123	... 2406, 2418, 2432
\@ACM@newfontsfalse ..		\@acmDOI .. 1184, 1602,	\@adddotafter ..
.... 617, 620, 623		1605, 1611, 1615, 2130	... 2340, 2344, 2400
\@ACM@newfontstrue .	614	\@acmEditors 1049, 1050,	\@additionalaffiliation
\@ACM@printfoliostrue 68		1051, 1054, 2124, 2125 1111, 1112
\@ACM@reviewtrue ... 110		\@acmISBN 1182, 1613	\@addpunct .. 2073,
\@ACM@screentru ..		\@acmMonth 1172, 1174, 1609	2074, 2076, 2077,
... 828, 857, 863, 869		\@acmNumber 1164,	2078, 2079, 2080,
\@ACM@sigchiamodefalse ..		2120, 2201, 2209,	2081, 2083, 2133,
.... 138		2218, 2287, 2295, 2303	2134, 2400, 2401, 2512
\@ACM@sigchiamodetrue 158		\@acmPrice 1178, 1610, 1614	\@addspaceafter ..
\@ACM@timestamptrue 109		\@acmPubDate ... 1174,	... 2384, 2389, 2401
		2120, 2201, 2209,	

```

 \@affiliationfont . . . . . 1901, 1906, 1910, 1913, 1916, 1919, 1922, 1925, 1953, 1971
 \@afterheading . . . . . 348, 1656
 \@afterindentfalse . . . . . 294, 1655
 \@afterindenttrue . . . . . 292
 \@article@string . . . . . 2113, 2120, 2128
 \@author . . . . . 1072, 1075, 1080, 1939, 1998, 2041, 2082
 \@authorfont . . . . . 1900, 1905, 1909, 1912, 1915, 1918, 1921, 1924, 1941, 1971
 \@authornotemark . . . . . 1152, 1158, 2087
 \@authornotes . . . . . 1149, 1153, 1554
 \@authorsaddresses . . . . . 1128, 1562, 2134
 \@auxout . . . . . 452
 \@begindocumenthook . . . . . 448
 \@botnum . . . . . 1544
 \@citestyle . . . . . 226
 \@classname . . . . . 25, 27, 35, 51, 53, 54, 59, 61, 62, 67, 70, 71, 76, 78, 79, 84, 86, 87, 92, 94, 95, 100, 102, 103, 108, 112, 113, 124, 129, 182, 615, 618, 621, 829, 858, 864, 870, 1024, 1026, 1110, 1205, 1215, 1217, 1218, 1221, 1223, 1224, 1227, 1229, 1230, 1232, 1233, 2110
 \@clubpenalty . . . . . 362
 \@concepts . . . . . 1268, 1278, 1623, 1625, 1648
 \@copyrightowner . . . . . 1351, 1586
 \@copyrightpermission . . . . . 1389, 1578
 \@copyrightyear . . . . . 1506, 1516, 1520, 1586, 1588
 \@currbox . . . . . 693, 694, 695
 \@currentaffiliation . . . . . 1972, 1975, 1997, 2004, 2005, 2007, 2009, 2010, 2014, 2040, 2047, 2048, 2050, 2052, 2053, 2057
 \@currentaffiliations . . . . . 1930, 1931, 1932, 1934, 1937, 1949, 1950, 1955
 \@currentauthors . . . . . 1928, 1929, 1936, 1940, 1941, 1943, 1971, 1974, 1996, 1998, 1999, 2001, 2039, 2041, 2042, 2044, 2087, 2088
 \@currentlabel . . . . . 577, 591
 \@dblarg . . . . . 303
 \@dblfloat . . . . . 677
 \@department . . . . . 1115, 1116
 \@dotsep . . . . . 2402
 \@editorsAbbrev . . . . . 1048, 1053, 2125
 \@empty . . . . . 160, 307, 1039, 1050, 1070, 1085, 1090, 1091, 1097, 1249, 1250, 1256, 1263, 1268, 1558, 1562, 1602, 1610, 1613, 1614, 1615, 1623, 1628, 1680, 1708, 1713, 1786, 1790, 1795, 1803, 1806, 1819, 1827, 1834, 1844, 1930, 1940, 1948, 1949, 1998, 2004, 2009, 2041, 2047, 2052, 2090, 2113, 2117, 2124, 2130, 2174, 2406, 2436, 2525, 2542
 \@endfloatbox . . . . . 679
 \@endpfalse . . . . . 2514
 \@endwidedefloatbox . . . . . 679, 687
 \@finalstrut . . . . . 582, 595
 \@float . . . . . 681
 \@flushglue . . . . . 2349
 \@fnssymbol . . . . . 1541
 \@folio@ht . . . . . 2236, 2263, 2269, 2270
 \@folio@max . . . . . 2236, 2259, 2260
 \@folio@voffset . . . . . 2236, 2265
 \@folio@wd . . . . . 2236, 2270, 2271, 2292, 2300
 \@folioblob . . . . . 2256, 2289, 2291, 2297, 2298
 \@footnotemark . . . . . 396, 1539
 \@footnotemark@nolink . . . . . 396, 1539
 \@footnotetext . . . . . 397, 573, 1540
 \@footnotetext@nolink . . . . . 397, 1540
 \@for . . . . . 202
 \@formatdoi . . . . . 1388, 1605, 1611, 1615, 2130
 \@fps . . . . . 680
 \@fpsadddefault . . . . . 680
 \@gobble . . . . . 224, 268
 \@hangfrom . . . . . 316, 373
 \@headfootfont . . . . .
 2183, 2196, 2197, 2198, 2199, 2203, 2206, 2211, 2215, 2221, 2222, 2223, 2225
 \@ifnextchar . . . . . 1115
 \@ifnotempty . . . . . 1526
 \@ifnum . . . . . 240, 242
 \@ifstar . . . . . 301
 \@ifundefined . . . . .
 2467, 2470, 2473, 2476, 2479, 2483, 2486
 \@iiiparbox . . . . . 571
 \@input . . . . . 385
 \@insideauthorgroupfalse . . . . .
 1063, 1105
 \@insideauthorgrouptrue . . . . .
 1068
 \@journalCode . . . . . 760, 829, 858, 864, 870, 1024
 \@journalCode@nr . . . . .
 760, 814, 1029
 \@journalName . . . . . 816, 820, 824, 831, 835, 839, 843, 847, 851, 854, 860, 866, 872, 876, 880, 883, 887, 891, 893, 895, 897,

```

901, 905, 909, 913, \@mkauthors@i . . 1880, \@plus . . 383, 391, 598,
 917, 921, 925, 929, 1882, 1884, 1886, 1935 2330, 2334, 2338,
 933, 937, 941, 945, \@mkauthors@ii 1965 2342, 2346, 2377,
 949, 953, 957, 960, \@mkauthors@iii . 1888, 2382, 2387, 2423,
 964, 967, 972, 976, 1890, 1892, 1894, 1976 2425, 2453, 2455, 2509
 980, 984, 988, 992, \@mkauthors@iv . 1896, 2025 \@printcopyrightfalse
 996, 1000, 1004, 1129, 2067 1309, 1321
 1008, 1012, 1016, \@mkbibcitation . 1641, 2106 \@printcopyrighttrue
 1020, 1030, 1031, \@mkteasers 1547, 2089 1293, 1305
 1598, 2200, 2208, \@mktitle 1547, 1720 \@printendtopmatter
 2217, 2286, 2294, 2302 \@mktitle@i 1723, 1654, 2132
\@journalNameShort . 1725, 1727, 1729, 1784 \@printpermissionfalse
 817, 821, 826, 832, \@mktitle@ii 1812 1308
 836, 840, 844, 848, \@mktitle@iii 1731, \@printpermissiontrue
 852, 855, 861, 867, 1733, 1735, 1737, 1812 1295, 1304, 1320
 873, 877, 881, 884, \@mktitle@iv 1739, 1840 \@printtopmatter . .
 888, 898, 902, 906, \@mpargs 571 1548, 1679
 910, 914, 918, 922, \@mpargswitchfalse 533 \@proofindent . . .
 926, 930, 934, 938, \@mpfootins 563, 564, 566, 586, 587 2493, 2503, 2511
 942, 946, 950, 954, \@mpfootnotetext 585 \@proofnamefont . . .
 961, 965, 968, 973, \@one 228, 232, 236, 238, 2492, 2502, 2512
 977, 981, 985, 989, \@nil 438, 2140, 2145, 2149 \@received . . 1247, 1250,
 993, 997, 1001, 234, 235, 236, 237, 1251, 1253, 1256,
 1005, 1009, 1013, 1257, 1259, 1263, 1264
 1017, 1021, 1031, 2119 \@rightskip 2349, 2350
\@keywords 1207, 1628, 1634, 1649 \@saveabstract . 1209, 1210
\@latex@error 270 \@noskipsecfalse 350, 390 \@saveteaser 1523, 1524
\@empty 1212, 2097 \@noskipsectrue 351 \@seccntformat 310, 367
\@listI 736, 740 \@pages@word 2107, 2121, 2128 \@secfont 2332, 2353
\@listi 733, 740 \@par 1560, 1566 \@secpenalty 299
\@listii 741 \@parboxrestore 590 \@sect 303, 304
\@listiii 744 \@parfont 2344, 2348, 2353 \@setaddresses 2086
\@listiv 746 \@permissionCodeOne 1566, 2134
\@listv 748 \@setthanks 1560, 2133 \@setauthorsaddresses
\@listvi 750 1566, 2134 1566, 2134
\@m 305 1566, 2134 1566, 2134
\@makefnmark 572, 597, 1546, 1551, 1555 \@shortauthors
\@makefntext 572, 581, 594, 1557 2182, 2192,
\@marginfigure 669, 670 2198, 2204, 2212, 2222
\@marginable 672, 673 \@sidebar 666, 667
\@minipagefalse 568, 689 \@specialsection
\@minus 2330, 2334, 1624, 1630, 1632, 1658
 2338, 2342, 2346, \@ssect 302, 368
 2377, 2382, 2387, \@startPage 1203,
 2424, 2426, 2454, 2456 1680, 1681, 1683, 2179
\@mkabstract 1621, 2096 \@startsection
\@mkauthors 1547, 1549, 1876 \@permissionCodeTwo
 288, 380, 2329, 288, 380, 2329,
 2333, 2337, 2341, 2333, 2337, 2341,
 2345, 2376, 2381, 2386 2345, 2376, 2381, 2386
 970, 1033 970, 1033
\@starttoc 380
\@subparfont 2389, 2390

```

 \@subsecfont .. 2336, 2353  \@title ... 1132, 1647, 697, 1659, 1687,
 \@subsubsecfont 2340, 2353  1802, 1826, 1843, 2116 1721, 1743, 1764,
 \@subtitle . 1056, 1141, 1803, 1804, 1827, 1828, 1844, 1845, 2117 1878, 1902, 2188,
 \@subtitlefont .... 1763, 1804, 1828, 1845 1801, 1813, 1825, 1841 2243, 2280, 2313,
 \@subtitlenotes .... 1139, 1143, 1146, 1553 1130, 1134, 1137, 1552 2358, 2407, 2437, 2494
 \@svsec . 307, 310, 316, 331 1@tochangmeasure 321, 334 \ACM@linecount ....
 \@svsechd ... 329, 357, 377 1@toplevel ..... 305 .... 2139, 2140,
 \@teaser .... 1524, 2091 1@tocline ... 393, 394, 395 \ACM@linecount@bx ...
 \@teaserfigures .... 1522, 1524, 2090, 2094 1@topnum ..... 1542 ... 2136, 2155, 2162
 \@tempa .... 202, 203, 205, 207, 209, 211, 213, 215, 217, 219, 221, 223, 225, 227, 229, 231, 233, 235, 237, 239, 241, 243, 245, 247, 250, 252, 254, 256, 258, 260, 1089, 1090, 1248, 1249, 1948, 2525, 2541, 2542, 2544 1@undefined ..... 448, 630 \ACM@linecountR ...
 \@tempb .... 203, 205, 207, 209, 211, 213, 215, 217, 219, 221, 223, 225, 227, 229, 231, 233, 235, 237, 239, 241, 243, 245, 250, 252, 254, 256, 258, 260, 2543, 2544 1@width ..... 552, 559 \ACM@mk@linecount ...
 \@tempboxa .... 571 1@xp ..... 387, 388 \ACM@ps@headings ...
 \@tempc . 248, 249, 251, 253, 255, 257, 259, 261 1@xsect ..... 342, 343, 379 2141, 2153, 2160
 \@tempcnya . 2256, 2257, 2259, 2260, 2262, 2264 1@z ..... 234 \ACM@ps@myheadings ...
 \@tempdimax . 1312, 1315, 1319, 1325, 1328, 1331, 1334, 1337, 1340, 1343, 1346, 1352, 1390 \ACM@ps@plain ...
 \@tempskipa .... 291, 293, 294, 299, 312, 313, 344, 345, 347, 359, 360, 369, 370 1209, 1299, 1307, 1312, 1315, 1319, 1325, 1328, 1331, 1334, 1337, 1340, 1343, 1346, 1352, 1390 \ACM@timestamp ...
 \@textbottom .... 598 1216, 160, 163, 165, 167, 169, 171, 173, 175, 177, 179, 182, 183 \acmArticle ... 17, 2516, 2516 \acmArticle ...
 \@textsuperscript ... 597, 1546, 1551 1220, 1223, 1224, 1225 \acmArticleSeq ... 15, 1166
 \@texttop .... 599 1226, 2306, 2309 \acmBadgeL ..... 16, 1198 \acmBadgeR ..... 16, 1193
 \@thefnmark . 578, 592, 597, 1546, 1551, 1556 1227, 2322, 2326 \acmBooktitle ... 8, 1044 \acmConference ... 8, 1034
 \ACM@format .... 32, 124 \ACM@format@nr 32, 124, 128, 133, 139, 161, 406, 473, 538, 645 \acmConference@date ...
 \ACM@fontsize .... 116, 160, 163, 165, 167, 169, 171, 173, 175, 177, 179, 182, 183 \acmConference@name ...
 \ACM@shortname ..... 1035, 1039, 1040, 1046, 1047, 1582, 2223, 2225 \acmConference@shortname ...
 \ACM@format@nr 32, 124, 128, 133, 139, 161, 406, 473, 538, 645 \acmConference@venue ...
 \ACM@definition .... 2452 \acmConference@venue ...

```

\acmDOI	16, 1184	\author	10,	\bibliographystyle .	447
\acmISBN	15, 1182		1064, 1535, 1536, 2111	\bibsection	196
\acmJournal	7, 1028	\author@bx	1965, 1970, 1973	\bibstyle	224, 226, 268, 452
\acmMonth	15, 1172	\author@bx@sep	1967, 1973,	\bibstyle@acmauthoryear	274
\acmNumber	15, 1164		1978, 1995, 2027, 2038	\bibstyle@acmnumeric	280
\acmplain	2422	\author@bx@wd	1966, 1969,	\bigskip	1264, 1705,
\acmPrice		1977, 1978, 1980,	1811, 1839, 1847,	
	15, 1178, 1317, 1323		1986, 1988, 1990,	2024, 2066, 2091, 2132	
\acmSubmissionID	15, 1180		1992, 1995, 2026,	\box	694, 1689, 1691, 1693,
\acmVolume	15, 1162		2027, 2029, 2035, 2038	1695, 1697, 1699,	
\acmYear	15, 1170	\authornote	14, 1111, 1150, 2112	1701, 1703, 1705,	
\addcontentsline	198,	\authornotemark	14, 1156	1961, 1973, 2022, 2093	
\additionalaffiliation	323, 336, 2098, 2519	\authors			
\addpenalty	299	1073, 1076, 1081,		C	
\addresses		1636, 1638, 1646, 2116			
	1070, 1072, 1075,		\c@footnote	1541	
	1080, 1107, 1125,		\c@secnumdepth		
	1152, 1158, 1160,		306, 320, 324, 333, 337		
	1962, 2024, 2066, 2084	\authorsaddresses	14, 1128		
\addtolength ...	721,				
	722, 723, 727, 728, 2146				
\addvspace	299, 391	B			
\advance	737,	\baselineskip			
	742, 745, 747,	1576, 1796,			
	749, 751, 1065,	1808, 1820, 1835,			
	1067, 1787, 1788,	2146, 2330, 2331,			
	1791, 1792, 1816,	2334, 2335, 2338,			
	1817, 1978, 1995,	2342, 2377, 2378,			
	2027, 2038, 2145,	2382, 2387, 2423,			
	2149, 2260, 2262, 2265	2424, 2425, 2426,			
\affiliation	10,	2453, 2454, 2455, 2456			
	1104, 1947, 2009, 2052	\begin	20, 2154, 2161, 2266		
\and	1054, 1080,	\begingroup			
	1081, 1094, 1100,	314, 357, 371, 380,			
	1938, 1943, 1945,	437, 1538, 1876, 2517			
	1955, 1960, 1969,				
	2003, 2018, 2024,	\bfseries	752, 1572,		
	2046, 2061, 2066, 2081		1745, 1747, 1749,		
\andify	1636,		1753, 1755, 1757,		
	1637, 1928, 1931, 2125		1759, 1761, 1921,		
anonsuppress (environ-			1924, 2115, 2273,		
ment)	22		2353, 2354, 2368,		
\AtBeginDocument ...			2369, 2371, 2372,		
	68, 441, 449, 713, 2328		2374, 2375, 2380,		
\AtEndDocument	1262		2385, 2393, 2394,		
\AtEndPreamble		2397, 2398, 2417, 2447		
	419, 631, 2464, 2526	\bgroup	667, 670, 673,		
			678, 1112, 1623,		
			1628, 1969, 2063,		
			2072, 2091, 2096, 2106		
		\bibfont	200		
		\biblofont	200		

\ClassError		\def . . .	25, 38, 116, 163,	978, 980, 981, 982,
. . . 35, 1026, 1110,		165, 167, 169, 171,	984, 985, 986, 988,	
1218, 1224, 1230, 2110		173, 175, 177, 179,	989, 990, 992, 993,	
\ClassInfo		203, 205, 207, 209,	994, 996, 997, 998,	
. . . 124, 182, 1024,		211, 213, 215, 217,	1000, 1001, 1002,	
1215, 1217, 1221,		219, 221, 223, 225,	1004, 1005, 1006,	
1223, 1227, 1229, 1232		227, 228, 229, 230,	1008, 1009, 1010,	
\ClassWarning		231, 232, 233, 234,	1012, 1013, 1014,	
. 27, 129, 615,		235, 236, 237, 239,	1016, 1017, 1018,	
618, 621, 1205, 1233		241, 243, 245, 246,	1020, 1021, 1022,	
\cleaders	1853	250, 252, 254, 256,	1028, 1029, 1030,	
\clubpenalty . . .	356, 362	258, 260, 288, 304,	1031, 1032, 1033,	
\CodelineIndex	17	329, 343, 367, 368,	1044, 1048, 1049,	
\Collect@Body . . .	666,	377, 380, 393, 394,	1050, 1056, 1089,	
669, 672, 1209, 1523		395, 400, 401, 402,	1111, 1112, 1113,	
\color . . .	1574, 2144, 2148	403, 447, 551, 558,	1114, 1115, 1116,	
\color@begingroup	580, 593	560, 572, 574, 585,	1127, 1128, 1130,	
\color@endbox	692	597, 598, 667, 670,	1131, 1139, 1140,	
\color@endgroup		673, 678, 680, 684,	1149, 1150, 1162,	
. 569, 583, 596		687, 705, 706, 707,	1164, 1166, 1168,	
\columnwidth . . .	552,	708, 736, 741, 744,	1170, 1172, 1174,	
589, 678, 2026, 2063		746, 748, 750, 816,	1178, 1180, 1182,	
\contentsnamefont . . .	384	817, 818, 820, 821,	1184, 1194, 1195,	
\copy	1853	822, 824, 826, 827,	1196, 1197, 1199,	
\copyright	1586	831, 832, 833, 835,	1200, 1201, 1202,	
\copyrightpermissionfootnoterule		836, 837, 839, 840,	1203, 1205, 1207,	
. 551		841, 843, 844, 845,	1210, 1212, 1235,	
\copyrightyear . .	17, 1520	847, 848, 849, 851,	1247, 1248, 1272,	
\country . .	12, 1121, 1856, 2080	852, 854, 855, 856,	1291, 1349, 1351,	
\csname	268, 319,	860, 861, 862, 866,	1388, 1389, 1520,	
321, 325, 332, 334,		867, 868, 872, 873,	1522, 1524, 1533,	
338, 367, 387, 388,		874, 876, 877, 878,	1546, 1551, 1560,	
578, 592, 1273,		880, 881, 883, 884,	1566, 1658, 1679,	
1274, 1276, 1277,		885, 887, 888, 889,	1720, 1742, 1763,	
1278, 1279, 1280,		891, 893, 895, 897,	1784, 1812, 1840,	
1283, 1285, 1651, 1653		898, 899, 901, 902,	1849, 1856, 1857,	
\CurrentOption . .	117,	903, 905, 906, 907,	1859, 1860, 1861,	
118, 119, 120, 121, 122		909, 910, 911, 913,	1862, 1864, 1866,	
D				
\day	2177	914, 915, 917, 918,	1867, 1870, 1873,	
\DeclareNewFootnote		919, 921, 922, 923,	1876, 1900, 1901,	
. 555, 557		925, 926, 927, 929,	1905, 1906, 1909,	
\DeclareOptionX		930, 931, 933, 934,	1910, 1912, 1913,	
. 38, 117,		935, 937, 938, 939,	1915, 1916, 1918,	
118, 119, 120, 121, 122		941, 942, 943, 945,	1919, 1921, 1922,	
\DeclareRobustCommand . .	436	946, 947, 949, 950,	1924, 1925, 1927,	
\DeclareTextFontCommand		951, 953, 954, 955,	1929, 1934, 1935,	
. 632		957, 958, 960, 961,	1936, 1937, 1939,	
		962, 964, 965, 967,	1946, 1947, 1948,	
		968, 969, 970, 972,	1969, 1976, 1998,	
		973, 974, 976, 977,	2004, 2009, 2025,	

	E	
\edef	117, 118, 119, 120, 305	\email 10, 1123, 1946, 2004, 2047, 2083
\editor 10, 1050	\emph 1598, 1600
\egroup 570, 668, 671, 674, 685, 691, 1122, 1625, 1634, 1972, 2066, 2085, 2092, 2105, 2131	\EnableCrossrefs 19 \end 22, 2156, 2163, 2274 \end@dblfloat 683 \end@float 685
\else 52, 60, 69, 77, 85, 93, 101, 111, 135, 248, 269, 298, 305, 308, 320, 324, 328, 333, 337, 349, 361, 376, 426, 440, 446, 448, 563, 642, 1046, 1052, 1066, 1074, 1078, 1079, 1088, 1093, 1096, 1099, 1106, 1124, 1136, 1145, 1151, 1159, 1216, 1222, 1228, 1239, 1242, 1252, 1255, 1258, 1263, 1282, 1286, 1287, 1529, 1547, 1558, 1562, 1563, 1577, 1580, 1581, 1587, 1592, 1599, 1604, 1607, 1610, 1612, 1613, 1614, 1615, 1623, 1628, 1631, 1682, 1708, 1713, 1786, 1790, 1795, 1803, 1806, 1819, 1827, 1834, 1844, 1850, 1851, 1864, 1865, 1866, 1867, 1869, 1870, 1873, 1930, 1942, 1948, 1954, 1970, 1981, 1991, 2000, 2006, 2013, 2030, 2034, 2043, 2049, 2056, 2069, 2071, 2090, 2097, 2101, 2107, 2113, 2117, 2122, 2124, 2130, 2174, 2182, 2219, 2257, 2307, 2316, 2525, 2530, 2537, 2545	\endcsname 267, 268, 319, 321, 325, 332, 334, 338, 367, 387, 388, 578, 592, 1273, 1274, 1276, 1277, 1278, 1279, 1280, 1283, 1285, 1651, 1653 \enddescription 759 \endgroup 318, 357, 375, 390, 1619, 1898, 2521 \endlist 757, 759 \endminipage 560 \endtrivlist 2514 \enspace 2401 environments: abstract 17 acks 23 anonsuppress 22 CCSXML 16 marginfigure 21 marginable 21 printonly 22 screenonly 22 sidebar 21 teaserfigure 17 \everypar 297, 352, 363, 2100 \excludecomment 1267, 2529, 2531, 2535, 2536 \ExecuteOptionsX 48, 56, 64, 73, 81, 89, 97, 105, 115 \expandafter 247, 249, 449, 571, 1273, 1274, 1276, 1277, 1283, 1285
	F	
\familydefault 634	\fancyfoot 2194, 2200, 2208, 2217, 2220, 2232, 2283, 2284, 2286, 2294, 2302, 2310, 2314, 2317

\fancyhead . 2190, 2191,
 2192, 2193, 2196,
 2197, 2198, 2199,
 2203, 2205, 2206,
 2211, 2213, 2214,
 2215, 2221, 2222,
 2223, 2225, 2282,
 2289, 2290, 2291,
 2297, 2298, 2299,
 2305, 2306, 2308, 2309
 \fancyheadoffset . . .
 . . . 2229, 2292, 2300
 \fancyhf . . . 2185, 2277
 \fancypagestyle 2184, 2276
 \fi 54, 62, 71, 79, 87, 95,
 103, 113, 132, 137,
 159, 180, 181, 192,
 204, 206, 208, 210,
 212, 214, 216, 218,
 220, 222, 224, 226,
 228, 230, 232, 234,
 236, 238, 240, 242,
 244, 246, 251, 253,
 255, 257, 259, 261,
 262, 271, 273, 287,
 289, 295, 300, 305,
 311, 322, 326, 335,
 339, 341, 364, 365,
 378, 389, 418, 428,
 444, 446, 450, 453,
 471, 535, 549, 567,
 584, 611, 629, 635,
 662, 663, 682, 686,
 711, 1023, 1041,
 1047, 1055, 1069,
 1077, 1082, 1083,
 1087, 1095, 1101,
 1102, 1103, 1108,
 1126, 1138, 1148,
 1155, 1161, 1177,
 1218, 1224, 1230,
 1244, 1245, 1254,
 1260, 1261, 1265,
 1281, 1288, 1289,
 1311, 1314, 1318,
 1324, 1327, 1330,
 1333, 1336, 1339,
 1342, 1345, 1348,
 1387, 1519, 1531,
 1536, 1537, 1547,
 1549, 1561, 1567,
 1568, 1569, 1575,
 1578, 1579, 1583,
 1584, 1589, 1601,
 1606, 1610, 1614,
 1615, 1616, 1617,
 1618, 1626, 1627,
 1633, 1635, 1642,
 1678, 1684, 1712,
 1716, 1717, 1718,
 1740, 1762, 1783,
 1789, 1793, 1799,
 1805, 1810, 1822,
 1824, 1829, 1837,
 1838, 1846, 1854,
 1864, 1866, 1867,
 1869, 1870, 1873,
 1875, 1897, 1926,
 1933, 1944, 1958,
 1959, 1970, 1993,
 1994, 2002, 2008,
 2017, 2036, 2037,
 2045, 2051, 2060,
 2069, 2071, 2095,
 2103, 2105, 2107,
 2114, 2117, 2126,
 2129, 2130, 2150,
 2157, 2164, 2176,
 2181, 2182, 2190,
 2191, 2196, 2197,
 2204, 2207, 2212,
 2216, 2220, 2227,
 2230, 2233, 2255,
 2274, 2283, 2310,
 2311, 2318, 2319,
 2399, 2421, 2451,
 2489, 2506, 2525,
 2533, 2539, 2542, 2546
 \firstpagestyle . . . 2276
 \floatname 665
 \footnote 2110
 \footnotemark 403, 1132,
 1141, 2087, 2088, 2108
 \footnoterule 558
 \footnotesep 582, 595
 \footnotesize
 588, 2173, 2194,
 2200, 2208, 2217,
 2220, 2284, 2286,
 2294, 2302, 2310, 2315
 \footnotetext . . . 1135,
 1137, 1144, 1147, 1154
 \footnotetextauthorsaddresses
 1559, 1565
 \footnotetextcopyrightpermission
 1570
 \footrulewidth 2187, 2279
 \format 32
 \frenchspacing 2547
 \fulltextwidth
 675, 678, 694

G

\g@addto@macro . . .
 1054, 1080, 1081,
 1094, 1100, 1107,
 1125, 1132, 1134,
 1137, 1141, 1143,
 1146, 1152, 1153,
 1158, 1160, 1253,
 1259, 1278, 1285,
 1524, 1528, 1530,
 1943, 1955, 2001,
 2007, 2014, 2044,
 2050, 2057, 2087, 2088
 \gdef 1035,
 1036, 1037, 1038,
 1040, 1044, 1051,
 1053, 1072, 1073,
 1075, 1076, 1086,
 1092, 1098, 1210,
 1234, 1251, 1257,
 1274, 1276, 1277,
 1283, 1681, 1941,
 1945, 1950, 1974,
 1975, 1996, 1997,
 1999, 2003, 2005,
 2010, 2039, 2040,
 2042, 2046, 2048, 2053
 \geometry
 475, 478, 485, 492,
 499, 506, 513, 520, 527
 \getrefnumber 2107
 \global
 351, 354, 390, 586,
 693, 1065, 1067,
 1068, 1105, 1542,
 1544, 1638, 1639,
 1938, 1960, 1961,

1970, 2018, 2021,	\if@ACM@manuscript .	\ifnum 128, 133,
2061, 2093, 2145, 2149 125,	305, 306, 320, 324,
\grantnum 23, 2524	189, 1237, 1580, 1590	333, 337, 1286,
\grantsponsor 23, 2523	\if@ACM@natbib	1287, 1307, 1312,
	... 82, 194, 285, 429	1315, 1319, 1325,
	\if@ACM@natbib@override	1328, 1331, 1334,
 82	1337, 1340, 1343,
	\if@ACM@newfonts 613, 624	1346, 1536, 1979,
	\if@ACM@printacmref	2028, 2068, 2070,
 1219, 1640	2107, 2257, 2259, 2313
	\if@ACM@printccs	\ifPDFTeX 601
 1213, 1622	\ifvmode 1850
	\if@ACM@printfolios	\ifvoid 563
 1225, 2190,	\ifx . 160, 203, 205, 207,
	2191, 2196, 2197,	209, 211, 213, 215,
	2204, 2207, 2212,	217, 219, 221, 223,
	2216, 2220, 2283, 2310	225, 227, 229, 231,
	\if@ACM@review	233, 235, 237, 239,
	. 65, 2136, 2152, 2159	241, 243, 245, 250,
	\if@ACM@screen 49, 420, 2527	252, 254, 256, 258,
	\if@ACM@sigchiemode	260, 448, 1039,
 127,	1046, 1050, 1070,
	573, 633, 677, 683,	1085, 1090, 1091,
	1547, 1549, 1970, 2228	1097, 1157, 1249,
	\if@ACM@timestamp	1250, 1256, 1263,
	. 98, 2165, 2231, 2312	1273, 1282, 1558,
	\if@acmowned 1296	1562, 1602, 1610,
	\if@filesw 386, 451	1613, 1614, 1615,
	\if@insideauthorgroup	1623, 1628, 1680,
 1062, 1066	1708, 1713, 1786,
	\if@nobreak 296	1790, 1795, 1803,
	\if@ACM@affiliation@obeypunct	1806, 1819, 1827,
 1109, \if@printcopyright .	1834, 1844, 1930,
	1851, 1864, 1866, 1292, 1585	1940, 1948, 1949,
	1867, 1868, 1870, 1873 \if@printpermission	1998, 2004, 2009,
 1294, 1578	2041, 2047, 2052,
	\ifcase	2090, 2097, 2113,
	139, 161, 406, 473,	2117, 2124, 2130,
	538, 645, 697, 814,	2174, 2525, 2542, 2544
	1174, 1352, 1390, \ignorespaces	\ignorespaces
	1659, 1687, 1721, 366, 582, 595,	
	1743, 1764, 1878, 1113, 1114, 1116,	
	1902, 1982, 2031, 1127, 1856, 1857,	
	2188, 2243, 2280, 1859, 1860, 1861,	
	2358, 2407, 2437, 2494 1862, 1863, 1864,	
	\ifcsname 267	2075, 2104, 2109, 2512
	\ifdim 293, 313, 345, 370, 2147 \immediate 388, 452	
	\IfFileExists 615, 618, 621 \includecomment	
	\IfInteger 1232 2528, 2532, 2538	
	\ifNAT@numbers 446 \includegraphics	

	1710, 1715, 1797, 1809, 1821, 1836	\leftmargini	720, 721, 722, 723, 736, 737	\marginfigure	669
\indent	2493	\leftmarginii	726,	\marginfigure (environ-		
\input	602	\leftmarginiv	727, 728, 729, 741, 742	ment)	21
\InputIfFileExists	..	26	\leftmarginiii	729, 730, 744, 745	\marginpar	574,
\institution 12, 1114, 1856, 2076	\leftmarginiv	730, 731, 746, 747	668, 671, 674, 1707		
\interfootnotelinepenalty	576	\leftmarginv	731, 732, 748, 749	\marginparsep	..	676, 2229
\interlinepenalty	..	317, 374, 576	\leftmarginvi	732, 750, 751	\marginparwidth	.	676, 2229
\item	2511	\leftskip	.	1841, 2064, 2351	\marginitable	672
\itshape	..	1582, 2355, 2356, 2385, 2390, 2403, 2415, 2435, 2502	\let	224, 226, 238, 240, 242, 268, 307, 396, 397, 430, 431, 432, 433, 434, 435, 438, 442, 599,	\marginitable (environ-		
	J				630, 679, 740, 755, 759, 1117, 1118,	ment)	21
	K				1119, 1120, 1121,	\mbox	246
\kern	551, 552, 558, 559, 1842				1268, 1539, 1540,	\mdseries	
\keywords	16, 1207			1555, 1556, 1557,	1766, 1768, 1770,		
	L				1560, 1566, 1638,	1774, 1776, 1778,		
\l@section	393			1639, 1871, 1872,	1780, 1782, 1922, 1925		
\l@subsection	..	393, 394			1874, 1938, 1960,	\medskip	..	1661, 1663,
\l@subsubsection	..	395			2018, 2024, 2061,	1665, 1667, 1961,		
\labelenumi	705			2066, 2321, 2322,	1963, 2022, 2094, 2115		
\labelenumii	706	\libertineLF	2323, 2325, 2326, 2327	\mkttitle@bx	1532,
\labelenumiii	707	\lineskip	632	1689, 1691, 1693,		
\labelenumiv	708	\linespacing	...	2023, 2065	1695, 1697, 1699,		
\labelsep	714, 722, 727, 737, 742, 745, 747, 749, 751, 2511	\liningnums	383, 384	1701, 1703, 1705,		
\labelwidth	..	737, 742, 745, 747, 749, 751, 754	\list	630	1794, 1813, 1841,		
\LARGE	1745, 1747, 1749, 1772, 1774, 1776, 1778, 1780, 1909, 1912, 2273	\listsep	...	753	1961, 2021, 2022, 2093		
\Large	1900, 1918, 2368, 2369, 2371, 2372, 2374		\listparindent	734, 735, 739	\month	1173, 2177
\large	1572, 1905, 1910, 1913, 2362, 2363, 2365, 2366	\LoadClass	738	\moveleft	693
\lastbox	355, 2100	\long	183	\multiply	2264
\leaders	1842			574,			
\leavevmode	289, 1842, 2022				585, 667, 670, 673,	N		
\leftmargin	736, 741, 744, 746, 748, 750	\loop	1210, 1212, 1524, 2133	\NAT@setcites	264
	M				2144, 2258	\NAT@aysep	255
			\makeatletter	574,	\NAT@citetp	438
			\makebox	585, 667, 670, 673,	\NAT@close		
			\makelabel	1210, 1212, 1524, 2133	204, 206, 208, 210, 253		
					585, 667, 670, 673,	\NAT@cmprs	..	232, 234, 236
					1210, 1212, 1524, 2133	\NAT@cmt	259
					585, 667, 670, 673,	\NAT@ctype	438
					1210, 1212, 1524, 2133	\NAT@find@eq	247
					585, 667, 670, 673,	\NAT@fullfalse	438
					1210, 1212, 1524, 2133	\NAT@longnamestrue	..	244
					585, 667, 670, 673,	\NAT@merge	..	238, 240, 242
					1210, 1212, 1524, 2133	\NAT@nmfmt	246
					585, 667, 670, 673,	\NAT@numbersfalse	..	218
					1210, 1212, 1524, 2133	\NAT@numberstrue	..	220, 222
					585, 667, 670, 673,	\NAT@open	204,
					1210, 1212, 1524, 2133	206, 208, 210, 251, 438		
					585, 667, 670, 673,	\NAT@partrue	438
					1210, 1212, 1524, 2133	\NAT@rem@eq	249
					585, 667, 670, 673,	\NAT@sep	212, 214, 216, 261	
					1210, 1212, 1524, 2133	\NAT@sort	..	228, 230, 236

\NAT@superfalse	220	1919, 2418, 2433, 2445, 2448, 2509, 2547	1378, 1381, 1384, 1391, 1402, 1413,
\NAT@supertrue	222	\normalparindent	1421, 1427, 1433,
\NAT@swafalse	437	\normalsize 1763, 1901, 1915, 1916, 1919, 2547	1447, 1459, 1466, 1480, 1487, 1493,
\NAT@up	246	\num@authorgroups	1500, 1509, 1662, 1664, 1666, 1668,
\NAT@yrsep	257 1058, 1067, 1536, 1982, 1986, 1988, 2031, 2070	1670, 1672, 1674, 1676, 1690, 1692,
\NeedsTeXFormat	1	\num@authors	1694, 1696, 1698, 1700, 1702, 1704,
\newblock	439 1060, 1065, 2068	1724, 1726, 1728,
\newbox	1532, 1848, 1965	\number 305	1730, 1732, 1734,
\newcommand	274, 280, 445, 1034, 1104, 1156, 1193, 1198, 1248, 1269, 1863, 1868, 2172, 2524, 2540	\numberline 325, 338	1736, 1738, 1746, 1748, 1750, 1752,
\newcount	1058, 1060, 2139	\numexpr 2167, 2169, 2171	1754, 1756, 1758, 1760, 1767, 1769,
\newcounter	2168, 2170	O	1771, 1773, 1775,
\newdimen	675, 712, 1966, 2236, 2238, 2240	\onehalfspacing	1777, 1779, 1781,
\newenvironment	669, 672, 1523	\openout 388	1881, 1883, 1885, 1887, 1889, 1891,
\newfloat	664	\or 142, 144, 146, 148, 150, 152, 154, 156, 164, 166, 168, 170, 172, 174, 176, 178, 408, 409, 410, 411, 412, 413, 415, 416, 477, 484, 491, 498, 505, 512, 519, 526, 540, 541, 542, 544, 545, 546, 547, 548, 647, 648, 649, 650, 651, 653, 656, 659, 699, 700, 701, 702, 703, 704, 709, 710, 819, 823, 830, 834, 838, 842, 846, 850, 853, 859, 865, 871, 875, 879, 882, 886, 890, 892, 894, 896, 900, 904, 908, 912, 916, 920, 924, 928, 932, 936, 940, 944, 948, 952, 956, 959, 963, 966, 971, 975, 979, 983, 987, 991, 995, 999, 1003, 1007, 1011, 1015, 1019, 1174, 1175, 1176, 1353, 1355, 1358, 1360, 1361, 1363, 1365, 1367, 1370, 1373, 1376,	1893, 1895, 1904, 1907, 1908, 1911, 1914, 1917, 1920, 1923, 1984, 1985, 1987, 1989, 2033, 2195, 2202, 2210, 2245, 2250, 2285, 2293, 2301, 2360, 2361, 2364, 2367, 2370, 2373, 2391, 2395, 2409, 2410, 2411, 2412, 2413, 2414, 2419, 2420, 2439, 2440, 2441, 2442, 2443, 2444, 2449, 2450, 2496, 2497, 2498, 2499, 2500, 2501, 2504, 2505
\newlinkurl	2005, 2007, 2048, 2050, 2083	\orcid 10, 1127	
\normalcolor	565	\outer@nobreak	690
\normalfont	597, 1264, 1551, 1901, 1906, 1915, 1916, 1918,	P	
		\p@ 391,	

\PackageError . 54, 62, 71, 79, 87, 95, 103, 113
 \PackageInfo 51, 53, 59, 61, 67, 70, 76, 78, 84, 86, 92, 94, 100, 102, 108, 112, 829, 858, 864, 870
 \PageIndex 16
 \pageref 2179
 \pagestyle 2235
 \par . 290, 346, 382, 561, 688, 1264, 1560, 1566, 1578, 1582, 1625, 1634, 1661, 1663, 1665, 1667, 1689, 1691, 1693, 1705, 1804, 1811, 1828, 1839, 1842, 1845, 1847, 1866, 1867, 1869, 1870, 1928, 1932, 1961, 1963, 1969, 1971, 1999, 2001, 2007, 2014, 2022, 2024, 2042, 2044, 2050, 2057, 2064, 2066, 2091, 2092, 2093, 2094, 2104, 2115, 2131, 2132, 2133, 2507
 \paragraph 1673, 2341, 2381
 \parbox 468, 1800, 1818, 1825, 1833, 2142, 2271
 \parindent 536, 550, 721, 1560, 1566, 1576, 2341, 2352, 2404, 2434
 \parskip 536, 1576
 \part 2345
 \PassOptionsToClass 121, 122
 \pdffgentounicode 610
 \pdffglyptounicode 603, 604, 605, 606, 607, 608, 609
 \pdfstringdefDisableCommands 399
 \phantomsection 198, 2098, 2519
 \popQED 2514
 \position 12, 1113, 1117, 1118, 1119, 1120, 1121, 1856, 2075, \postcode 12, 1120, 1856, 2074
 printonly (environment) 22
 \ProcessOptionsX 123
 \proof 2507
 \prooffname 2507
 \protect 325, 338
 \protected@edef 310, 577, 591
 \providecommand 439, 443, 2402
 \ProvidesClass 5
 \ProvidesFile 3
 \ps@headings 2323, 2327
 \ps@myheadings 2322, 2326
 \ps@plain 2321, 2325
 \pushQED 2508
 \put 2155, 2162
 \removelastskip 382
Q
 \qed 2508
 \quad 367, 2204, 2207, 2212, 2216, 2314
R
 \raggedright 1800, 1841, 2064
 \raisebox 1572, 1796, 1808, 1820, 1835, 2267, 2269
 \received 19, 1248
 \RecordChanges 18
 \ref 2121, 2128
 \refname 197, 198
 \refstepcounter 309
 \relax 128, 133, 140, 162, 247, 248, 291, 310, 312, 316, 330, 344, 359, 369, 377, 388, 407, 474, 539, 599, 646, 698, 815, 1059, 1061, 1065, 1067, 1156, 1157, 1273, 1282, 1307, 1312, 1315, 1319, 1325, 1328, 1331, 1334, 1337, 1340, 1343, 1346, 1352, 1390, 1555, 1556, 1660, 1688, 1722, 1744, 1765, 1879, 1903, 1968, 1977, 1978, 1979, 1980, 1983, 1986, 1988, 1990, 1992, 1995, 2023, 2026, 2027, 2028, 2029, 2032, 2035, 2038, 2068, 2070, 2087, 2107, 2140, 2169, 2171, 2174, 2189, 2244, 2246, 2247, 2248, 2251, 2252, 2253, 2256, 2257, 2259, 2262, 2263, 2264, 2265, 2281, 2313, 2359, 2408, 2438, 2495, 2509
 \renewcommand 196, 200, 201, 204, 206, 208, 210, 212, 214, 216, 266, 634, 752, 1064, 1123, 1525, 1541, 2079, 2186, 2187, 2278, 2279, 2329, 2333, 2337, 2341, 2345, 2376, 2381, 2386
 \renewenvironment 666, 753, 1209, 2507
 \repeat 2147, 2261
 \RequirePackage 30, 31, 184, 185, 186, 187, 188, 190, 193, 195, 398, 454, 455, 465, 472, 553, 600, 612, 625, 626, 627, 628, 636, 1266, 1271, 2135
 \reset@font 575, 588
 \reversemarginpar 534
 \rightskip 2350
 \rlap 2268
 \rule 582, 595, 2270
S
 \savebox 2142
 screenonly (environment) 22

```

\scriptsize ... 2144, 2148
\scshape ..... 2405, 2492
\section ..... 197,
1669, 1671, 1675,
1677, 2102, 2329, 2518
\section@raggedright
.... 2349, 2353,
2354, 2362, 2363,
2365, 2366, 2368,
2369, 2371, 2372,
2374, 2375, 2380,
2393, 2394, 2397, 2398
>SelectFootnoteRule
..... 554, 556
\setbox .... 355, 586,
693, 1794, 1813,
1841, 1852, 1961,
1970, 2021, 2093, 2100
\setcitestyle .....
... 24, 201, 275, 281
\setcopyright .. 17, 1349
\setcounter .... 1550,
1620, 1683, 2169,
2171, 2357, 2392, 2396
\setkeys .....
38,
131, 1028, 1235,
1349, 1951, 1952,
1956, 1957, 2011,
2012, 2015, 2016,
2054, 2055, 2058, 2059
\setlength 536, 537, 543,
550, 714, 715, 720,
726, 729, 730, 731,
732, 1189, 1192, 2143
\settopmatter .....
.. 19, 1235, 1236,
1238, 1241, 1243, 1246
\setTrue ..... 381
\SetWatermarkColor . 467
\SetWatermarkFontSize 466
\SetWatermarkText .. 468
\sfdefault .....
634
\sffamily .....
1745, 1747, 1749,
1751, 1753, 1755,
1759, 1900, 1905,
1909, 2183, 2273,
2353, 2354, 2355,
2362, 2363, 2365,
\scriptsize ... 2144, 2148
\scshape ..... 2405, 2492
\section ..... 197,
1669, 1671, 1675,
1677, 2102, 2329, 2518
\section@raggedright
.... 2349, 2353,
2354, 2362, 2363,
2365, 2366, 2368,
2369, 2371, 2372,
2374, 2375, 2380,
2393, 2394, 2397, 2398
\shortauthors 20, 1085,
1086, 1091, 1092,
1094, 1097, 1098,
1100, 1637, 1639, 2182
\shortcite .....
442, 445
\shorttitle .....
2193,
2199, 2207, 2216, 2221
\showeprint .....
2540
\sidebar .....
664
\sidebar (environment) . 21
\skip .....
564
\small ...
575, 668, 671,
674, 1264, 1661,
1663, 1665, 1667,
1906, 2100, 2115, 2283
\smallskipamount ...
735
\space 334, 1651, 1873, 2525
\specialcomment .....
2516
\standardpagestyle .
2184
\startPage .....
16, 1203
\state . 12, 1119, 1856, 2078
\stepcounter ...
1135,
1137, 1144, 1147, 1154
\streetaddress ...
12, 1117, 1856, 2073
\string 452, 1205, 2111, 2112
\strut .....
1818, 1833
\strutbox .....
582, 595
\subparagraph .....
2386
\subsection .....
2333
\subsubsection 2337, 2376
\subtitle .....
10, 1056
\subtitlenote ...
14, 1140
\textwidth 676, 694, 695,
1545, 1784, 1812,
1840, 1877, 1977, 2020
\thanks .....
14, 1525, 2133
\thankses .....
1528, 1530, 1558, 2133
\the .....
1171, 1173,
2144, 2148, 2177, 2264
\theACM@time@hours .
..... 2171, 2178
\theACM@time@minutes 2178
\theenumi .....
705
\theenumii .....
706
\theenumiii .....
707
\theenumiv .....
708
\thefootnote .....
1541
\theoremstyle .....
2463, 2466, 2482, 2490
\thepage ..
2179, 2190,
2191, 2196, 2197,
2204, 2207, 2212,
2216, 2220, 2283, 2310
>thispagestyle .....
1685
\thmname .....
2432, 2462
\thmnote .....
2432, 2462
\thmnumber .....
2432, 2462
\thr@ .....
242
\time .....
2166, 2169, 2171
\title .....
10, 2111
\titlenote ...
14, 1131, 2112
\topsep ...
739, 743, 2509
\trivlist .....
2510
\tw@ .....
240
\two@digits ...
2177, 2178
\twocolumn .....
1695,
1697, 1699, 1701, 1703

```

T

```

\teaserfigure .....
1523
\teaserfigure (environment) .....
17
\terms .....
16, 1205
\textbf .....
1275, 1286
\textbullet 401, 1274,
2204, 2207, 2212, 2216
\textcolor .....
2273
\textcopyright 1506, 1516
\textheight .....
2147
\textit .....
1287,
2119, 2123, 2124, 2125
\textrightarrow . 402, 1284

```

U

```

\unskip .....
358,
400, 562, 1116,
1122, 1127, 1853,
1856, 1857, 1859,
1860, 1861, 1862,
1863, 1873, 1932,
2073, 2074, 2075,
2076, 2077, 2078,
2079, 2080, 2081,
2083, 2109, 2128, 2134
\unvbox .....
566, 571, 587
\upshape .....
752

```

\url	1388, 2525	W	582, 595, 598, 640,
\urlstyle	405, 414, 417	\wd	644, 655, 720, 726,
\usebox	2155, 2162	\write	738, 1542, 1544,
\usepackage	10, 11, 12, 13, 14, 15	X	1560, 1566, 1572,
		\xdef	1576, 1796, 1808,
			1820, 1835, 2064,
			2100, 2186, 2187,
			2237, 2239, 2241,
		Y	2267, 2269, 2278,
\vbox	586, 693, 1794, 1813, 1841, 1961, 2021, 2093	\year	2279, 2329, 2333,
\vskip	347, 382, 564, 598, 688	Z	2345, 2352, 2376,
\vtop	1970	\z@...	2381, 2386, 2416, 2446
		2355, 370, 383, 537,	\z@skip 382, 688, 743, 2351