

# **LATEX Class for Association for Computing Machinery<sup>\*</sup>**

Boris Veytsman<sup>†</sup>

2017/06/25, v1.41

## **Abstract**

This package provides a class for typesetting publications of Association for Computing Machinery.

## **Contents**

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>User's guide</b>	<b>3</b>
2.1	Installation . . . . .	3
2.2	Invocation and options . . . . .	5
2.3	Topmatter commands . . . . .	7
2.4	Algorithms . . . . .	19
2.5	Figures and tables . . . . .	19
2.6	Theorems . . . . .	21
2.7	Online-only and offline-only material . . . . .	21
2.8	Note about anonymous mode . . . . .	21
2.9	Acknowledgments . . . . .	21
2.10	Bibliography . . . . .	22
2.11	Colors . . . . .	25
2.12	Other notable packages and typographic remarks . . . . .	25
2.13	A note for wizards: <code>acmart-preload-hook.tex</code> . . . . .	26
<b>3</b>	<b>Implementation</b>	<b>27</b>
3.1	Identification . . . . .	27
3.2	Preload . . . . .	27
3.3	Options . . . . .	27
3.4	Setting switches . . . . .	30

---

<sup>\*</sup>©2016–2017, Association for Computing Machinery

<sup>†</sup>[borisv@lk.net](mailto:borisv@lk.net), [boris@varphi.com](mailto:boris@varphi.com)

3.5	Loading base class and package	31
3.6	Paper size and paragraphing	38
3.7	Fonts	41
3.8	Floats	42
3.9	Lists	44
3.10	Top matter data	45
3.11	Concepts system	57
3.12	Copyright system	58
3.13	Typesetting top matter	63
3.14	Headers and Footers	77
3.15	Sectioning	81
3.16	TOC Lists	83
3.17	Theorems	83
3.18	Acknowledgments	86
3.19	Conditional typesetting	86
3.20	Additional bibliography commands	87
3.21	End of Class	87

# 1 Introduction

Association for Computing Machinery is the world's largest educational and scientific computing society, which delivers resources that advance computing as a science and a profession<sup>1</sup>. It was one of the early adopters of  $\text{\TeX}$  for its typesetting.

It provided several different classes for a number of journal and conference proceedings. Unfortunately during the years since these classes were written, the code was patched many times, and the support of the different versions of the classes became difficult.

This package provides the uniform interface for all ACM publications. It is intended to replace all different classes and packages and provide an up to date  $\text{\LaTeX}$  package.

The package uses only free  $\text{\TeX}$  packages and fonts included in  $\text{\TeX}Live$ ,  $\text{MiK}\text{\TeX}$  and other popular  $\text{\TeX}$  distributions. It is intended to be published in these distributions itself, which minimizes users' efforts in the installation and support of the package.

I am grateful to Matthew Fluet, John Owens, Craig Rodkin, Bernard Rous, David Shamma, Stephen Spencer and many others for their invaluable help.

The development version of the package is available at <https://github.com/borisveytsman/acmart>.

## 2 User's guide

### 2.1 Installation

Most probably, you already have this package installed in your favorite  $\text{\TeX}$  distribution; if not, you may want to upgrade. You may need to upgrade it anyway since the package uses a number of relatively recent packages, especially the ones related to the fonts.

The latest released version of the package can be found on CTAN: <https://www.ctan.org/pkg/acmart>. The development version can be found on GitHub: <https://github.com/borisveytsman/acmart>. At this address you can file a bug report—or even contribute your own enhancement making a pull request.

Most users should not attempt to install this package themselves, and rather rely on their  $\text{\TeX}$  distributions to provide it. If you decide to install the package yourself, follow the standard rules:

1. Run `latex` on `acmart.ins`. This will produce the file `acmart.cls`.
2. Put the file `acmart.cls` and the bibliography files `*.bst` to the places where  $\text{\LaTeX}$  can find them (see [1] or the documentation for your  $\text{\TeX}$  system).
3. Update the database of file names. Again, see [1] or the documentation for your  $\text{\TeX}$  system for the system-specific details.
4. The file `acmart.pdf` provides the documentation for the package (this is the file you are probably reading now).

---

<sup>1</sup><http://www.acm.org/>

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

The class uses a number of other packages. They are included in all major  $\text{\TeX}$  distributions ( $\text{\TeX}^{\text{Live}}$ , Mac $\text{\TeX}$ , Mik $\text{\TeX}$ ) of 2015 and later, so you probably have them installed. Just in case here is the list of these packages:

- *amscls*, <http://www.ctan.org/pkg/amscls>
- *amsfonts*, <http://www.ctan.org/pkg/amsfonts>
- *amsmath*, <http://www.ctan.org/pkg/amsmath>
- *binhex*, <http://www.ctan.org/pkg/binhex>
- *caption*, <http://www.ctan.org/pkg/caption>
- *comment*, <http://www.ctan.org/pkg/comment>
- *cm-super*, <http://www.ctan.org/pkg/cm-super>
- *cmap*, <http://www.ctan.org/pkg/cmap>
- *cleveref*, <http://www.ctan.org/pkg/cleveref>
- *draftwatermark*, <http://www.ctan.org/pkg/draftwatermark>
- *environ*, <http://www.ctan.org/pkg/environ>
- *fancyhdr*, <http://www.ctan.org/pkg/fancyhdr>
- *float*, <http://www.ctan.org/pkg/float>
- *fontaxes*, <http://www.ctan.org/pkg/fontaxes>
- *geometry*, <http://www.ctan.org/pkg/geometry>
- *graphics*, <http://www.ctan.org/pkg/graphics>
- *hyperref*, <http://www.ctan.org/pkg/hyperref>
- *ifluatex*, <http://www.ctan.org/pkg/ifluatex>
- *ifxetex*, <http://www.ctan.org/pkg/ifxetex>
- *inconsolata*, <http://www.ctan.org/pkg/inconsolata>
- *libertine*, <http://www.ctan.org/pkg/libertine>
- *manyfoot*, <http://www.ctan.org/pkg/manyfoot>
- *microtype*, <http://www.ctan.org/pkg/microtype>
- *mmap*, <http://www.ctan.org/pkg/mmap>
- *ms*, <http://www.ctan.org/pkg/ms>

- *mweights*, <http://www.ctan.org/pkg/mweights>
- *natbib*, <http://www.ctan.org/pkg/natbib>
- *nccfoots*, <http://www.ctan.org/pkg/nccfoots>
- *newtx*, <http://www.ctan.org/pkg/newtx>
- *oberdiek*, <http://www.ctan.org/pkg/oberdiek>
- *pdftex-def*, <http://www.ctan.org/pkg/pdftex-def>
- *setspace*, <http://www.ctan.org/pkg/setspace>
- *textcase*, <http://www.ctan.org/pkg/textcase>
- *totpages*, <http://www.ctan.org/pkg/totpages>
- *trimspaces*, <http://www.ctan.org/pkg/trimspaces>
- *upquote*, <http://www.ctan.org/pkg/upquote>
- *url*, <http://www.ctan.org/pkg/url>
- *xcolor*, <http://www.ctan.org/pkg/xcolor>
- *xkeyval*, <http://www.ctan.org/pkg/xkeyval>
- *xstring*, <http://www.ctan.org/pkg/xstring>

## 2.2 Invocation and options

To use the class put in the preamble of your document

```
\documentclass[<options>]{acmart}
```

There are several options corresponding to the type of the document and its general appearance. They are described below. Generally speaking, the options have key=value forms, for example

```
\documentclass[format=acmsmall, screen=true, review=false]{acmart}
```

The option `format` describes the format of the output. There are several possible values for this option, for example,

```
\documentclass[format=acmtog]{acmart}
```

Actually the words `format=` can be omitted, e.g.,

```
\documentclass[acmtog, review=false]{acmart}
```

Table 1: The possible values for the `format` option

Value	Meaning
<code>manuscript</code>	A manuscript. This is the default
<code>acmsmall</code>	Small single column format, used for CIE, CSUR, JACM, JDIQ, JEA, JERIC, JETC, PACMHCI, PACMPL, TAAS, TACCESS, TACO, TALG, TALLIP (formerly TALIP), TCPS, TEAC, TECS, TIIS, TISSEC, TIST, TKDD, TMIS, TOCE, TOCHI, TOCL, TOCS, TOCT, TODAES, TODS, TOIS, TOIT, TOMACS, TOMM (formerly TOMCCAP), TOMPECS, TOMS, TOPC, TOPLAS, TOPS, TOS, TOSEM, TOSN, TRETS, TSAS, TSC, TSLP, TWEB, including special issues.
<code>acmlarge</code>	Large single column format, used for IMWUT, JOCCH, POMACS, TAP, including special issues.
<code>acmtog</code>	Large double column format, used for TOG, including special issues.
<code>sigconf</code>	Proceedings format for most of ACM conferences (with the exceptions listed below) and all ICPS volumes.
<code>siggraph</code>	As of March 2017, this format is no longer used. Please use <code>sigconf</code> for SIGGRAPH conferences.
<code>sigplan</code>	Proceedings format for SIGPLAN conferences.
<code>sigchi</code>	Proceedings format for SIGCHI conferences.
<code>sigchi-a</code>	Format for SIGCHI extended abstract.

The possible formats are listed in Table 1. Note that formats starting with `acm` are intended for journals and transactions, while formats starting with `sig` are intended for proceedings published as books.

Note that sometimes conference proceedings are published as a special issue (or issues) of an ACM journal. In this case you should use the journal format for a conference paper. Please contact your conference committee if in doubt.

There are several Boolean options which can take `true` or `false` values. They are listed in Table 2. The words `=true` can be omitted when setting the Boolean option, so instead of `screen=true` one can write just `screen`, for example,

```
\documentclass[acmsmall, screen, review]{acmart}
```

The option `review` is useful when combined with the `manuscript` format option: it provides a version suitable for reviewers and copyeditors.

The option `screen` may in the future involve additional features suitable for on-screen versions of the articles.

The option `natbib` is used when the corresponding `BIBTEX` style is based on `natbib`. In most cases you do not need to set it. See Section 2.10.

The option `anonymous` is used for anonymous review process: all author information becomes obscured.

The option `timestamp` is used to include a time stamp in the footer of each page. When preparing a document, this can help avoid confusing different revisions. The

Table 2: Boolean options

Option	Default	Meaning
review	false	A review version: lines are numbered, hyperlinks are colored
screen	false	A screen version: hyperlinks are colored
natbib	true	Whether to use natbib package (see Section 2.10)
anonymous	false	Whether to make author(s) anonymous
authorversion	false	Whether to generate a special version for authors' personal use or posting (see Section 2.3)
timestamp	false	Whether to put a time stamp in the footer of each page
authordraft	false	Whether author's draft mode is enabled

footer also include the page range of the document. This helps detect missing pages in hard copies.

The option `authordraft` is intended for the authors' drafts, not intended for distribution. It typesets copyright block to give the authors the idea of its size and overall size of the paper, but overprints it with the phrase "Unpublished working draft. Not for distribution", which also is used as a watermark. This option sets `timestamp` and `review` to true, but these decisions can be overridden by setting these options to false *after* `authordraft`.

### 2.3 Topmatter commands

A number of commands set up *top matter* information, or, in the computer science jargon, *metadata* for the article. They establish the publication name, article title, authors, doi and other data. Some of these commands, like `\title` or `\author`, should be put by the authors. Others, like `\acmVolume` or `\acmDOI`—by the editors. Below we describe these commands and mention who should issue them. These macros should be used *before* the `\maketitle` command. Note that in the previous versions of ACM classes some of these commands should be used before `\maketitle`, and some after it. Now they all must be used before `\maketitle`.

The class internally loads `amsart` class, so many top matter commands are inherited from `amsart` [2].

`\acmJournal` The macro `\acmJournal{<shortName>}` sets the name of the journal or transaction for journals and transactions. The argument is the short name of the publication *in uppercase*, for example,

```
\acmJournal{TOMS}
```

The currently recognized journals are listed in Table 3. Note that conference proceedings published in *book* form do not set this macro.

It is expected that this command is inserted by the author of the manuscript when she decides to which journal to submit the manuscript.

Table 3: ACM publications and arguments of the \acmJournal command

Abbreviation	Publication
CIE	ACM Computers in Entertainment
CSUR	ACM Computing Surveys
IMWUT	PACM on Interactive, Mobile, Wearable and Ubiquitous Technologies
JACM	Journal of the ACM
JDIQ	ACM Journal of Data and Information Quality
JEA	ACM Journal of Experimental Algorithms
JERIC	ACM Journal of Educational Resources in Computing
JETC	ACM Journal on Emerging Technologies in Computing Systems
JOCCH	ACM Journal on Computing and Cultural Heritage
PACMHCI	PACM on Human-Computer Interaction
PACMPL	PACM on Programming Languages
POMACS	PACM on Measurement and Analysis of Computing Systems
TAAS	ACM Transactions on Autonomous and Adaptive Systems
TACCESS	ACM Transactions on Accessible Computing
TACO	ACM Transactions on Architecture and Code Optimization
TALG	ACM Transactions on Algorithms
TALLIP	ACM Transactions on Asian and Low-Resource Language Information Processing
TAP	ACM Transactions on Applied Perception
TCPS	ACM Transactions on Cyber-Physical Systems
TEAC	ACM Transactions on Economics and Computation
TECS	ACM Transactions on Embedded Computing Systems
TIIS	ACM Transactions on Interactive Intelligent Systems
TISSEC	ACM Transactions on Information and System Security
TIST	ACM Transactions on Intelligent Systems and Technology
TKDD	ACM Transactions on Knowledge Discovery from Data
TMIS	ACM Transactions on Management Information Systems
TOCE	ACM Transactions on Computing Education
TOCHI	ACM Transactions on Computer-Human Interaction
TOCL	ACM Transactions on Computational Logic
TOCS	ACM Transactions on Computer Systems
TOCT	ACM Transactions on Computation Theory
TODAES	ACM Transactions on Design Automation of Electronic Systems
TODS	ACM Transactions on Database Systems
TOG	ACM Transactions on Graphics
TOIS	ACM Transactions on Information Systems
TOIT	ACM Transactions on Internet Technology
TOMACS	ACM Transactions on Modeling and Computer Simulation
TOMM	ACM Transactions on Multimedia Computing, Communications and Applications
TOMPECS	ACM Transactions on Modeling and Performance Evaluation of Computing Systems
TOMS	ACM Transactions on Mathematical Software
TOPC	ACM Transactions on Parallel Computing
TOPLAS	ACM Transactions on Programming Languages and Systems
TOPS	ACM Transactions on Privacy and Security
TOS	ACM Transactions on Storage
TOSEM	ACM Transactions on Software Engineering and Methodology
TOSN	ACM Transactions on Sensor Networks
TRETS	ACM Transactions on Reconfigurable Technology and Systems
TSAS	ACM Transactions on Spatial Algorithms and Systems
TSC	ACM Transactions on Social Computing
TSLP	ACM Transactions on Speech and Language Processing
TWEB	ACM Transactions on the Web

\acmConference[*short name*]{*name*}{*date*}{*venue*} is used for conference proceedings published in the book form. The arguments are the following:

**short name:** the abbreviated name of the conference (optional).

**name:** the name of the conference or the name of the book as set by the editor.

**date:** the date(s) of the conference.

**venue:** the place of the conference.

Examples:

```
\acmConference[TD'15]{Technical Data Conference}{November  
12--16}{Dallas, TX, USA}  
\acmConference{SA'15 Art Papers}{November 02--06, 2015}{Kobe, Japan}
```

Normally this command is entered either by the editor or by the typesetter.

\title The command \title, as in amsart class, has two arguments: one optional, and one mandatory:

```
\title[ShortTitle]{FullTitle}
```

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

It is expected that this command is inserted by the author of the manuscript.

\subtitle Besides title, ACM classes allow subtitle, set with the \subtitle{*subtitle*} macro.

The commands for specification of authors are highly structured. The reason is, they serve double duty: the authors' information is typeset in the manuscript, and is used by the metadata extraction tools for indexing and cataloguing. Therefore it is very important to follow the guidelines exactly.

\author The basic commands are \author, \orcid (for the researchers registered with ORCID, <http://www.orcid.org/>), \affiliation and \email. In the simplest case you enter them in this order:

```
\author{...}  
\orcid{...}  
\affiliation{...}  
\email{...}
```

Do *not* use L<sup>A</sup>T<sub>E</sub>X \and macro! Each author deserves his or her own \author command.

Note that some formats do not typeset e-mails or ORCID identifiers. Do not worry: metadata tools will get them.

Sometimes an author has several affiliations. In this case the \affiliation command should be repeated:

```
\author{...}  
\orcid{...}
```

```
\affiliation{...}
\affiliation{...}
\email{...}
```

Similarly you can repeat \email command.

You may have several authors with the same affiliation, different affiliations or overlapping affiliations (author  $A_1$  is affiliated with institutions  $I_1$  and  $I_2$ , while author  $A_2$  is affiliated with  $I_2$  only, and author  $A_3$  is affiliated with  $I_1$  and  $I_3$ , ...). The recommended solution is to put the \affiliation commands after each author, possibly repeating them:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
```

In some cases when several authors share the same affiliation you may try to save the space using the format

```
\author{...}
\email{...}
\author{...}
\email{...}
\affiliation{...}
```

However, this format is not generally recommended.

\additionalaffiliation

In some cases too many affiliations take too much space. The command \additionalaffiliation{<affiliation>} creates a footnote after author's name with the words "Also with {<affiliation>}". You should use this command only as the last resort. An example of usage is:

```
\author{G. Tobin}
\author{Ben Trovato}
\additionalaffiliation{%
    \institution{The Th{\o}rv{\\"a}ld Group}
    \streetaddress{1 Th{\o}rv{\\"a}ld Circle}
    \city{Hekla}
    \country{Iceland}}
\affiliation{%
```

```

    \institution{Institute for Clarity in Documentation}
    \streetaddress{P.O. Box 1212}
    \city{Dublin}
    \state{Ohio}
    \postcode{43017-6221}
}

```

Here Trovato and Tobin share their affiliation with the Institute for Clarity in Documentation, but only Ben Trovato is affiliated with The Thørváld Group.

```

\position
\institution
\department
\streetaddress
\city
\state
\postcode
\country

```

The `\affiliation` and `\additionalaffiliation` commands are further structured to interact with the metadata extraction tools. Inside the `this` command you should use `\position`, `\institution`, `\department`, `\city`, `\streetaddress`, `\state`, `\postcode` and `\country` macros to indicate the corresponding parts of the affiliation. Note that in some cases (for example, journals) these parts are not printed in the resulting copy, but they *are* necessary since they are used by the XML metadata extraction programs. Do *not* put commas or `\` between the elements of `\affiliation`: they will be provided automatically.

An example of the author block:

```

\author{A. U. Thor}
\orcid{1234-4564-1234-4565}
\affiliation{%
    \institution{University of New South Wales}
    \department{School of Biomedical Engineering}
    \streetaddress{Samuels Building (F25), Kensington Campus}
    \city{Sidney}
    \state{NSW}
    \postcode{2052}
    \country{Australia}}
\email{author@nsw.au.edu}
\author{A. N. Other}
\affiliation{%
    \institution{University of New South Wales}
    \city{Sidney}
    \state{NSW}
    \country{Australia}}
\author{C. O. Respondent}
\orcid{1234-4565-4564-1234}
\affiliation{%
    \institution{University of Pennsylvania}
    \city{Philadelphia}
    \state{PA}
    \country{USA}}
\affiliation{%
    \institution{University of New South Wales}
    \city{Sidney}
    \state{NSW}
    \country{Australia}}

```

Note that old ACM conference formats did not allow for more than six authors and required some efforts from the authors to achieve alignment. The new format is much better in this.

Sometimes an author works in several departments within the same institution. There could be two situations: the departments are independent, or one department is within another. In the first case just repeat the command \department several times. To handle the second case the command has an optional numerical parameter. The departments with higher numbers are higher in the organizational chart. Compare

```
\affiliation{%
\department[0]{Department of Lunar Studies} % 0 is the default
\department[1]{John Doe Institute} % higher than 0
\institution{University of San Serriffe}
\country{San Serriffe}}
```

and

```
\affiliation{%
\department{Department of Lunar Studies} % Not within JD Inst!
\department{John Doe Institute}
\institution{University of San Serriffe}
\country{San Serriffe}}
```

The command \affiliation formats the output according to American conventions. This might be wrong for some cases. Consider, for example, a German address. In Germany postcode is put before city and is not separated by a comma. We can handle this order using

```
\affiliation{%
\institution{Fluginstitut}
\streetaddress{Sonnenallee 17}
\postcode{123456}
\city{Helm}
\country{Germany}
}
```

However, the comma after postcode is unfortunate: the address will be typeset (in some formats) as

```
Fluginstitut
Sonenallee 17
123456, Helm, Germany
```

To overcome this problem, the command \affiliation has an optional parameter `obeypunctuation`, which can be false (the default) or true. If this parameter is true, \affiliation obeys the author's command. Thus

```
\affiliation[obeypunctuation=true]{%
  \institution{Fluginstitut} \\
  \streetaddress{Sonnenallee 17} \\
  \postcode{123456} \\
  \city{Helm}, \\
  \country{Germany}
}
```

will be typeset as

```
Fluginstitut
Sonnenallee 17
123456 Helm, Germany
```

Note that you should *not* use this option for journals.

It is expected that these commands are inserted by the author of the manuscript.

`\thanks` Like amsart (and unlike standard L<sup>A</sup>T<sub>E</sub>X), we allow `\thanks` only *outside* of commands `\title` and `\author`. Example:

```
\thanks{This work is supported by the Widget Corporation Grant
  \#312-001. \\
  Author's address: D. Pineo, Kingsbury Hall, 33 Academic Way, Durham,
  N.H. 03824; email: dspineo@comcast.net; Colin Ware, Jere A. Chase
  Ocean Engineering Lab, 24 Colovos Road, Durham, NH 03824; email:
  cware@ccom.unh.edu;
  Sean Fogarty, (Current address) NASA Ames Research Center, Moffett
  Field, California 94035.}
```

It is expected that this command is inserted by the author of the manuscript.

While the command `\thanks` generates a note without footnote mark, sometimes the authors might need notes more tightly connected to the title, subtitle or author. The commands `\titlenote`, `\subtitlenote` and `\authornote` that follow the corresponding commands (`\title`, `\subtitle` and `\author`) generate such notes, for example

```
\title{This is a title}
\titlenote{This is a titlenote}
\author{A. U. Thor}
\authornote{This is an authornote}
```

Please never use `\footnotes` inside `\author` or `\title` commands, since this confuses metadata extraction software (actually these commands now produce errors).

Sometimes one may need to have the same footnote connected to several authors. The command `\authornotemark[<number>]` adds just the footnote mark, for example

```
\author{A. U. Thor}
\authornote{Both authors contributed equally to the paper}
...
```

```
\author{A. N. Other}  
\authornotemark[1]
```

The correct numbering of these marks is the responsibility of the user.

The macros `\acmVolume`, `\acmNumber`, `\acmArticle`, `\acmYear` and `\acmMonth` are inserted by the editor and set the journal volume, issue, article number, year and month correspondingly. The arguments of all these commands, including `\acmMonth` is numerical, including `\acmMonth`, for example,

```
\acmVolume{9}  
\acmNumber{4}  
\acmArticle{39}  
\acmYear{2010}  
\acmMonth{3}
```

`\acmArticleSeq` The articles in the same issue of a journal have a *sequential number*. It is used to vertically position the black blob in some formats. By default it is the same as article number, but the command `\acmArticleSeq{<n>}` can be used to change it:

```
\acmArticle{39} % The sequence number will be 39 by default  
\acmArticleSeq{5} % We redefine it to 5
```

`\acmSubmissionID` If your paper got a Submission ID from the Conference Management System, put it here:

```
\acmSubmissionID{123-A56-BU3}
```

`\acmPrice` The macro `\acmPrice{<price>}` sets the price for the article  
`\acmPrice{25.00}`

Note that you do not need to put the dollar sign here, just the amount. By default the price is \$15.00, unless the copyright is set to usgov or rightsretained, when it is suppressed. Note that to override the defaults you need to set the price *after* the `\setcopyright` command to override the default. Also, the command `\acmPrice{}` suppresses the printing of the price.

`\acmISBN` Book-like volumes have ISBN numbers attached to them. The macro `\acmISBN{<ISBN>}` sets it. Normally it is set by the typesetter, for example,

```
\acmISBN{978-1-4503-3916-2}
```

`\acmDOI` The macro `\acmDOI{<DOI>}` sets the DOI number of the article, for example,  
`\acmDOI{10.1145/9999997.9999999}`

\acmBadgeR  
\acmBadgeL

It is normally set by the typesetter.

Some conference articles get special distinction, for example, the artifact evaluation for PPoPP 2016 (see <http://ctuning.org/ae/ppopp2016.html>). These articles display special badges supplied by the conference organizers. The class provides commands to add these badges: \acmBadgeR[⟨url⟩]{⟨graphics⟩} and \acmBadgeL[⟨url⟩]{⟨graphics⟩}. The first command puts the badge to the right of the title, and the second one—to the left. The exception is the sigchi-a mode for SIGCHI Extended abstract, which puts the badges on the left margin. The argument have the following meaning: [⟨url⟩], if provided, sets the link to the badge authority in the screen version, while {⟨graphics⟩} sets the graphics file with the badge image. The file must be a cropped square, which is scaled to a standard size in the output. For example, if the badge image is ae-logo.pdf, the command is

```
\acmBadgeR[http://ctuning.org/ae/ppopp2016.html]{ae-logo}
```

\startPage  
\terms  
\keywords

Some badges provided by the ACM are `artifacts_available`, `artifacts_evaluated_functional`, `artifacts_evaluated_reusable`, `results_replicated`, and `results_reproduced`.

The macro \startPage{⟨page⟩} sets the first page of the article in the journal or book. It is used by the typesetter.

The command \keywords{⟨keyword, keyword,...⟩} sets keywords for the article. They must be separated by commas, for example,

```
\keywords{wireless sensor networks, media access control,  
multi-channel, radio interference, time synchronization}
```

CCSXML  
\ccsdesc

ACM publications are classified according to the ACM Computing Classification Scheme (CCS). CCS codes are used both in the typeset version of the publications *and* in the metadata in the various databases. Therefore you need to provide both TeX commands and XML metadata with the paper.

The tool at <http://dl.acm.org/ccs.cfm> can be used to generate CCS codes. After you select the topics, click on “Generate CCS codes” to get the result like the following:

```
\begin{CCSXML}  
<ccs2012>  
  <concept>  
    <concept_id>10010520.10010553.10010562</concept_id>  
    <concept_desc>Computer systems organization~Embedded systems</concept_desc>  
    <concept_significance>500</concept_significance>  
  </concept>  
  <concept>  
    <concept_id>10010520.10010575.10010755</concept_id>  
    <concept_desc>Computer systems organization~Redundancy</concept_desc>  
    <concept_significance>300</concept_significance>  
  </concept>  
  <concept>  
    <concept_id>10010520.10010553.10010554</concept_id>  
    <concept_desc>Computer systems organization~Robotics</concept_desc>
```

```

<concept_significance>100</concept_significance>
</concept>
<concept>
  <concept_id>10003033.10003083.10003095</concept_id>
  <concept_desc>Networks~Network reliability</concept_desc>
  <concept_significance>100</concept_significance>
</concept>
</ccs2012>
\end{CCSXML}

\ccsdesc[500]{Computer systems organization~Embedded systems}
\ccsdesc[300]{Computer systems organization~Redundancy}
\ccsdesc{Computer systems organization~Robotics}
\ccsdesc[100]{Networks~Network reliability}

```

You need to just copy this code and paste it in your paper anywhere before `\maketitle`.

`\setcopyright`

There are several possibilities for the copyright of the papers published by ACM: the authors may transfer the rights to ACM, license them to ACM, some or all authors might be employees of the US or Canada Government, etc. Accordingly the command `\setcopyright{...}` is introduced. Its argument is the copyright status of the paper, for example, `\setcopyright{acmcopyright}`. The possible values for this command are listed in Table 4.

The ACM submission software should generate the right command for you to paste into your file.

`\copyrightyear`

Each copyright statement must have the year of copyright. By default it is the same as `\acmYear`, but you can override this decision using the macro `\copyrightyear`, e.g.,

```

\acmYear{2016}
\copyrightyear{2015}

```

There is a special case for a personal copy that the authors may be allowed to generate for their use or a posting on a personal site (check the instructions for the specific journal or conference for the details). The document option `authorversion=true` produces the special form of the copyright statement for this case. Note that you still need the `\setcopyright` command and (optionally) `\copyrightyear` command to tell `\TeX` about the copyright owner and year. Also, you should be aware that due to the different sizes of the permission blocks for the printed version and authors' version the page breaks might be different between them.

`abstract`

The environment `abstract` must *precede* `\maketitle` command. Again, this is different from the standard `\TeX`.

`teaserfigure`

A special kind of figure is used for many two-column conference proceedings. This figure is placed just after the authors, but before the main text. The environment `teaserfigure` is used for these figures. This environment must be used *before* `\maketitle`, for example,

```

\begin{teaserfigure}

```

Table 4: Parameters for \setcopyright command

Parameter	Meaning
none	The copyright and permission information is not typeset (this is the option for some ACM conferences).
acmcopyright	The authors transfer the copyright to ACM (the “traditional” choice).
acmlicensed	The authors retain the copyright but license the publication rights to ACM.
rightsretained	The authors retain the copyright and publication rights to themselves or somebody else.
usgov	All the authors are employees of the US Government.
usgovmixed	Some authors are employees of the US Government.
cagov	All the authors are employees of the Canadian Government.
cagovmixed	Some authors are employees of the Canadian Government.
licensedusgovmixed	Some authors are employees of the US Government, and the publication rights are licensed to ACM.
licensedcagov	All the authors are employees of the Canadian Government, and the publication rights are licensed to ACM.
licensedcagovmixed	Some authors are employees of the Canadian Government, and the publication rights are licensed to ACM.
othergov	Authors are employees of a Government other than US or Canada.
licensedothergov	Authors are employees of a Government other than US or Canada, and the publication rights are licensed to ACM.

Table 5: Settings for `\settopmatter` command

Parameter	Values	Meaning
<code>printccs</code>	true/false	Whether to print CCS categories
<code>printacmref</code>	true/false	Whether to print ACM bibliographic entry
<code>printfolios</code>	true/false	Whether to print page numbers (folios)
<code>authorsperrow</code>	numeric	Number of authors per row for title page in conference proceedings formats

```
\includegraphics[width=\textwidth]{sampleteaser}
\caption{This is a teaser}
\label{fig:teaser}
\end{figure}
```

`\settopmatter` Some information in the top matter is printed for certain journals or proceedings and suppressed for others. You may override these defaults using the command `\settopmatter{<settings>}`. The settings and their meanings are listed in Table 5. For example,

```
\settopmatter{printacmref=false, printccs=true, printfolios=true}
```

The parameter `authorsperrow` requires some explanation. In conference proceedings authors' information is typeset in boxes, several boxes per row (see `sample-sigconf.pdf`, `sample-sigplan.pdf` etc.). The number of the boxes per row is determined automatically. If you want to override this decision, you may do it using this parameter, for example,

```
\settopmatter{authorsperrow=4}
```

However, in most cases you should *not* do this and use the default settings. Setting `authorsperrow` to 0 will revert to default settings.

`\received` The command `\received[<stage>]{<date>}` sets the history of the publication. The `[<stage>]` argument is optional; the default is Received for the first date and revised for the subsequent ones. For example

```
\received[February 2007]
\received[revised]{March 2009}
\received[accepted]{June 2009}
```

`\maketitle` The macro `\maketitle` must be the last command in the top matter group: i.e., it must follow the commands defined in this section.

`\shortauthors` After the command `\maketitle` the macro `\shortauthors` stores the names of the authors for the running head. You may redefine it if the list of author's name is too long, e.g.,

```
\maketitle
\renewcommand{\shortauthors}{Zhou et al.}
```

## 2.4 Algorithms

There are now several good packages for typesetting algorithms [3, 4, 5], and the authors are now free to choose their favorite one.

## 2.5 Figures and tables

New ACM styles use the standard L<sup>A</sup>T<sub>E</sub>X interface for figures and tables. There are some important items to be aware of, however.

1. The captions for figures must be entered *after* the figure bodies, and for the tables *before* the table bodies.
2. ACM uses the standard types for figures and types and adds several new ones. In total there are the following types:

**figure, table:** a standard figure or table, taking full text width in one-column formats and one column in two-column formats.

**figure\*, table\*** in two-column formats, a special figure or table taking full text width.

**teaserfigure:** a special figure before \maketitle.

**sidebar, marginfigure, margintable:** in the sigchi-a format, special sidebars, tables and figures on the margin.

3. Accordingly, when scaling the images, one should use the following sizes:
  - (a) For **figure** in one-column mode, **figure\*** in two-column mode or **teaserfigure**—\textwidth (in the one-column you can also use \columnwidth, which coincides with \textwidth in this case).
  - (b) For **figure** in two-column mode—\columnwidth.
  - (c) For **marginfigure**—\marginparwidth.
  - (d) For **figure\*** in SIGCHI Extended abstracts—\fulltextwidth.

It is strongly recommended to use the package booktabs [6] and follow its main principles of typography with respect to tables:

1. Never, ever use vertical rules.
2. Never use double rules.

It is also a good idea not to overuse horizontal rules.

For table *footnotes* you have several options described in TeX FAQ [1]. The simplest one is to use \minipage environment:

```
\begin{table}
\caption{Simulation Configuration}
\label{tab:conf}
\begin{minipage}{\columnwidth}
\begin{center}
\begin{tabular}{ll}
\toprule
TERRAIN\footnote{This is a table footnote. This is a table footnote. This is a table footnote.} & \\
(200\,,m\$200\,,m) Square\\
Node Number & 289\\
Node Placement & Uniform\\
Application & Many-to-Many/Gossip CBR Streams\\
Payload Size & 32 bytes\\
Routing Layer & GF\\
MAC Layer & CSMA/MMSN\\
Radio Layer & RADIO-ACCNOISE\\
Radio Bandwidth & 250Kbps\\
Radio Range & 20m--45m\\
\bottomrule
\end{tabular}
\end{center}
\bigskip
\footnotesize\emph{Source:} This is a table
sourcenote. This is a table sourcenote. This is a table
sourcenote.

\emph{Note:} This is a table footnote.
\end{minipage}
\end{table}
```

**sidebar**  
**marginfigure**  
**margintable** SIGCHI extended abstract extensively uses margin space. The package provides three environments for this with option captions:

**sidebar:** textual information on the margin

**marginfigure:** a figure on the margin

**margintable:** a table on the margin

Tables and figures (including margin tables and margin figures) are by default centered. However, in some cases (for example, when you use several subimages per figure) you may need to override this decision. A good way to do so is to put the contents into a \minipage of the width \columnwidth.

## 2.6 Theorems

ACM classes define two theorem styles and several pre-defined theorem environments:

**acmplain:** this is the style used for `theorem`, `conjecture`, `proposition`, `lemma`, and `corollary`, and

**acmdefinition:** this is the style used for `example` and `definition`.

## 2.7 Online-only and offline-only material

`printonly` Some supplementary material in ACM publication is put online, but not in the printed version. The text inside the environment `screenonly` will be typeset only when the option `screen` (see Section 2.2) is set to `true`. Conversely, the text inside the environment `printonly` is typeset only when this option is set to `false`. For example

```
\section{Supplementary materials}

\begin{printonly}
  This section is included in the online version of the paper.
\end{printonly}

\begin{screenonly}
  (The actual section).
\end{screenonly}
```

We use `comment` package for typesetting this code, so `\begin{...}` and `\end{...}` should start at the first positions of the lines of their own (no initial spaces etc.).

## 2.8 Note about anonymous mode

`anonsuppress` When the option `anonymous` is selected, TeX suppresses author information (including number of authors) for a blind review. However, sometimes the information identifying the authors may be present in the body of the paper

```
\begin{anonsuppress}
  This is the continuation of the previous work by the author
  \cite{prev1, prev2}.
\end{anonsuppress}
```

As for `printonly` and `screenonly` environments, `\begin{anonsuppress}` and `\end{anonsuppress}` should start the line of their own (no leading or trailing spaces).

## 2.9 Acknowledgments

The traditional “Acknowledgments” section is conventionally used to thank persons and granting agencies for their help and support. However, there are several important considerations about this section.

First, in the anonymous mode this section must be omitted: it gives too much information to the reviewers. Second, the data about the grants is extracted and stored separately by the postprocessing software. ACM classes provide facilities for both these tasks.

- acks      The environment `acks` starts an unnumbered section “Acknowledgments” unless the anonymous mode is chosen. Put all thanks inside this environment.
- `\grantsponsor`      As for `printonly` and `screenonly` environments, `\begin{acks}` and `\end{acks}` should start the line of their own (no leading or trailing spaces).
- `\grantnum`      All the financial support *must* be listed using the commands `\grantsponsor` and `\grantnum`. These commands tell the postprocessing software about the granting organization and the grant. The format of the command is the following:

```
\grantsponsor{\langle sponsorID \rangle}{\langle name \rangle}{\langle url \rangle}
\grantnum[\langle url \rangle]{\langle sponsorID \rangle}{\langle number \rangle}.
```

Here `\langle sponsorID \rangle` is the unique ID used to match grants to sponsors, `\langle name \rangle` is the name of the sponsor, `\langle url \rangle` is its URL, and `\langle number \rangle` is the grant number. The `\langle sponsorID \rangle` of the `\grantnum` command must correspond to `\sponsorID` of a `\grantsponsor` command. Some awards have their own web pages, which you can include using the optional argument of `\grantnum` command.

At present `\langle sponsorID \rangle` is chosen by the authors and can be an arbitrary key, in the same way the label of `\cite` is arbitrarily chosen. There might be a change to this policy if ACM decides to create a global database of sponsoring organizations.

Example:

```
\begin{acks}
The authors would like to thank Dr. Yuhua Li for providing the
matlab code of the \textit{BEPS} method.

The authors would also like to thank the anonymous referees for
their valuable comments and helpful suggestions. The work is
supported by the \grantsponsor{GS501100001809}{National Natural
Science Foundation of
China}{\url{https://doi.org/10.13039/501100001809}} under Grant
No.:~\grantnum{GS501100001809}{61273304}
and~\grantnum[\url{http://www.nnsf.cn/youngscientsts}]{GS501100001809}{Young
Scientists' Support Program}.
\end{acks}
```

## 2.10 Bibliography

ACM uses the `natbib` package for formatting references and the style `ACM-Reference-Format.bst` for Bib<sub>T</sub>E<sub>X</sub> processing. You may disable loading of `natbib` by using the option `natbib=false` in `\documentclass`. However, it is not recommended, as well as the use of Bib<sub>T</sub>E<sub>X</sub> styles other than `ACM-Reference-Format.bst`, and may delay the processing of the manuscript.

- `\citetstyle`      If you use `natbib`, you can select one of two predefined citation styles: the author-

year format `acmauthoryear` or the numeric format `acmnumeric` using the command `\citetestyle`, for example,

```
\citetestyle{acmauthoryear}
```

Note that numeric citations are the default mode for most formats.

`\setcitetestyle` You may further customize `natbib` using `\setcitetestyle` command, for example,

```
\setcitetestyle{numbers,sort&compress}
```

If you use `natbib`, then commands like `\citep` and `\citeauthor` are automatically supported. The command `\shortcite` is the same as `\cite` in numerical mode, and cites the year in the author-date mode.

There are several customized BibTeX entries and fields in ACM style ACM-Reference-Format.  
`.bst` you may want to be aware of.

The style supports fields `doi` and `url`, for example,

```
doi = "10.1145/1188913.1188915",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.pdf",
```

The style supports arXiv recommended fields `eprint` and (optionally) `primaryclass`, for example,

```
eprint = "960935712",
primaryclass = "cs",
```

See the examples at <http://arxiv.org/hypertex/bibstyles/>.

There are special entries `online` and `game` for Web pages and games, for example,

```
@online{Thornburg01,
  author = "Harry Thornburg",
  year = "2001",
  title = "Introduction to Bayesian Statistics",
  url = "http://ccrma.stanford.edu/~jos/bayes/bayes.html",
  month = mar,
  lastaccessed = "March 2, 2005",
}
```

For these entries you can use the `lastaccessed` field to add the access date to the URL.

There are two ways to enter video and audio sources in the bibliography corresponding to two different possibilities. For standalone sources available on WWW you can use an `online` entry, setting there `howpublished` field, for example,

```
@online{Obama08,
  author = "Barack Obama",
  year = "2008",
  title = "A more perfect union",
```

```

howpublished = "Video",
day      =      "5",
url      =      "http://video.google.com/videoplay?docid=6528042696351994555",
month    =      mar,
lastaccessed = "March 21, 2008",
}

```

For the sources available as attachments to conference proceedings and similar documents, you can use the usual `inproceedings` entry, again setting the `howpublished` field:

```

@Inproceedings{Novak03,
author =      "Dave Novak",
title =       "Solder man",
booktitle =   "ACM SIGGRAPH 2003 Video Review on Animation theater Program",
year =        "2003",
publisher =   "ACM Press",
address =     "New York, NY",
pages =       "4",
month =       "March 21, 2008",
doi =         "10.9999/woot07-S422",
howpublished = "Video",
}

```

Sometimes you need to cite a complete issue of a journal. The entry `periodical` is intended for this:

```

@periodical{JCohen96,
key =          "Cohen",
editor =        "Jacques Cohen",
title =         "Special issue: Digital Libraries",
journal =       "Communications of the {ACM}",
volume =        "39",
number =        "11",
month =         nov,
year =          "1996",
}

```

If you do not know the year of publication, the style will add “[n. d.]” (for “no date”) entry.

If you do not know the author (this is often the case for online entries), use `key` field to add a key for sorting and citations, for example,

```

@online{TUGInstmem,
key =          {TUG},
year =         2017,
title =        "Institutional members of the {\TeX} Users Group",
url =          "http://www.tug.org/instmem.html",
}

```

```
lastaccessed = "May 27, 2017",
}
```

## 2.11 Colors

While printed ACM publications are usually black and white, screen mode allows the use of colors. The ACM classes pre-define several colors according to [7]: ACMBrown, ACMYellow, ACMOrange, ACMRed, ACMLightBlue, ACMGreen, ACMPurple, ACMDarkBlue. You can use them in the color assignments.

ACM provides the following recommendation on color use.

The most accessible approach would be to ensure that your article is still readable when printed in greyscale. The most notable reasons for this are:

1. The most common type of inherited Color Vision Deficiency (CVD) is red-green (in which similar-brightness colors that only differ in their amounts of red or green are often confused), and it affects up to 8% of males and 0.5% of females of Northern European descent.
2. The most common type of acquired Color Vision Deficiency (CVD) is blue-yellow (including mild cases for many older adults).
3. Most printing is in Black & White.
4. Situational impairments (e.g., bright sunlight shining on a mobile screen) tend to reduce the entire color gamut, reducing color discriminability.

**Note:** It is *not* safe to encode information using only variations in color (i.e., only differences in hue and/or saturation), as there is bound to be someone affected!

To ensure that you are using the most accessible colors, ACM recommends that you choose sets of colors to help ensure suitable variations in Black & White using either of the following tools:

1. ColourBrewer: <http://colorbrewer2.org/>
2. ACE: The Accessible Colour Evaluator: <http://daprlab.com/ace/> for designing WCAG 2.0 compliant palettes.

## 2.12 Other notable packages and typographic remarks

Several other packages are recommended for specialized tasks.

The package *subcaption* [8] is recommended for complex figures with several subplots or subfigures that require separate subcaptioning. The packages *nomencl* [9] and *glossaries* [10] can be used for the automatic creation of the lists of symbols and concepts used.

By default *acmart* prevents all widows and orphans (i.e. lonely lines at the beginning and the end of the page) and hyphenation at the end of the page. This is done by rather strict settings

```
\widowpenalty=10000
\clubpenalty=10000
\brokenpenalty=10000
```

However, this may lead to frustrating results when the authors must obey a page limit. Setting these penalties to smaller values may help if you absolutely need to.

Another problem might be the too strict line breaking rules. Again, a strategically placed `\sloppy` command or putting the problematic paragraph inside `sloppypar` environment might help—but beware the results might be, well, sloppy.

Note that the uppercasing in section titles is done using `textcase` package [11], so command `\NoCaseChange` inside title may help to prevent extraneous uppercasing.

## 2.13 A note for wizards: `acmart-preload-hook.tex`

Sometimes you need to change the behavior of `acmart`. The usual way to do this is to redefine commands in the preamble. However, these definitions are executed *after* `acmart` is loaded, and certain decisions are made. This presents a number of problems.

For example, one may want to use `titletoc` package with `acmart`. This package should be loaded before `hyperref`. However, since `acmart` loads `hyperref` itself, the line `\usepackage{titletoc}` in the preamble will lead to grief (see <http://tex.stackexchange.com/questions/357265/using-titletoc-with-acm-acmart-style>).

Another example is passing options to package. Suppose you want to use `dvipsnames` option of `xcolor` package. Normally you cannot do this because `acmart` loads this package itself without options.

The file `acmart-preload-hook.tex` may be used to solve these problems. If this file exists, it will be processed before any other package. You can use this file to load packages or pass options to them. For example, if you put in this file

```
\let\LoadClassOrig\LoadClass
\renewcommand\LoadClass[2][]{\LoadClassOrig[#1]{#2}%
\usepackage{titletoc}}
```

then `titletoc` will be loaded before `hyperref`. If you put in this file

```
\PassOptionsToPackage{dvipsnames}{xcolor}
```

you will pass `dvipsnames` to `xcolor`.

**Important note.** This hook makes it too easy to create a manuscript which is not acceptable by ACM. Even easier it is to create a file which cannot be compiled. So please do not use it *unless you know what you are doing*. And if you use it, *do not ask for support*. If you decided to use this hook, you are on your own.

## 3 Implementation

### 3.1 Identification

We start with the declaration who we are. Most .dtx files put driver code in a separate driver file .drv. We roll this code into the main file, and use the pseudo-guard <gobble> for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 <*gobble>
3 \ProvidesFile{acmart.dtx}
4 </gobble>
5 <class>\ProvidesClass{acmart}
6 [2017/06/25 v1.41 Typesetting articles for Association of
7 Computing Machinery]
```

And the driver code:

```
8 <*gobble>
9 \documentclass{ltxdoc}
10 \usepackage{array,booktabs,amsmath,graphicx,fancyvrb,tabularx}
11 \usepackage[tt=false, type1=true]{libertine}
12 \usepackage[varqu]{zi4}
13 \usepackage[libertine]{newtxmath}
14 \usepackage[tableposition=top]{caption}
15 \usepackage{hypdoc}
16 \PageIndex
17 \CodelineIndex
18 \RecordChanges
19 \EnableCrossrefs
20 \begin{document}
21   \DocInput{acmart.dtx}
22 \end{document}
23 </gobble>
24 <*class>
25 \def\@classname{acmart}
```

### 3.2 Preload

We preload acmart-preload-hook:

```
26 \InputIfFileExists{acmart-preload-hook.tex}{%
27   \ClassWarning{\@classname}{%
28     I am loading acmart-preload-hook.tex. You are fully responsible
29     for any problems from now on.}}{}
```

### 3.3 Options

We need xkeyval since some of our options may have values:

```
30 \RequirePackage{xkeyval}
We use xstring to check whether user input is integer
31 \RequirePackage{xstring}
```

```

format The possible formats
32 \define@choicekey*+{acmart.cls}{format}[\ACM@format\ACM@format@nr]{%
33   manuscript, acmsmall, acmlarge, acmtog, sigconf, siggraph,
34   sigplan, sigchi, sigchi-a}[manuscript]{}
35 \ClassError{@classname}{The option format must be manuscript,
36   acmsmall, acmlarge, acmtog, sigconf, siggraph,
37   sigplan, sigchi or sigchi-a}}
38 \def@\DeclareACMFormat#1{\DeclareOptionX[#1]{\setkeys{acmart.cls}{format=#1}}}
39 \@DeclareACMFormat{manuscript}
40 \@DeclareACMFormat{acmsmall}
41 \@DeclareACMFormat{acmlarge}
42 \@DeclareACMFormat{acmtog}
43 \@DeclareACMFormat{sigconf}
44 \@DeclareACMFormat{siggraph}
45 \@DeclareACMFormat{sigplan}
46 \@DeclareACMFormat{sigchi}
47 \@DeclareACMFormat{sigchi-a}
48 \ExecuteOptionsX{format}

\if@ACM@screen Whether we use screen mode
49 \define@boolkey+{acmart.cls}[@ACM@]{screen}[true]{%
50   \if@ACM@screen
51     \PackageInfo{@classname}{Using screen mode}%
52   \else
53     \PackageInfo{@classname}{Not using screen mode}%
54   \fi}{\PackageError{@classname}{Option screen can be either true or
55   false}}
56 \ExecuteOptionsX{screen=false}

\if@ACM@review Whether we use review mode
57 \define@boolkey+{acmart.cls}[@ACM@]{review}[true]{%
58   \if@ACM@review
59     \PackageInfo{@classname}{Using review mode}%
60   \else
61     \PackageInfo{@classname}{Not using review mode}%
62   \fi}{\PackageError{@classname}{Option review can be either true or
63   false}}
64 \ExecuteOptionsX{review=false}

\if@ACM@authorversion Whether we use author's version
65 \define@boolkey+{acmart.cls}[@ACM@]{authorversion}[true]{%
66   \if@ACM@authorversion
67     \PackageInfo{@classname}{Using authorversion mode}%
68   \else
69     \PackageInfo{@classname}{Not using authorversion mode}%
70   \fi}{\PackageError{@classname}{Option authorversion can be either true or
71   false}}
72 \ExecuteOptionsX{authorversion=false}

\if@ACM@natbib@override

```

```

\if@ACM@natbib Whether we use natbib mode
73 \define@boolkey+{acmart.cls}[@ACM@]{natbib}[true]{%
74   \if@ACM@natbib
75     \PackageInfo{@classname}{Explicitly selecting natbib mode}%
76   \else
77     \PackageInfo{@classname}{Explicitly deselecting natbib mode}%
78   \fi}{\PackageError{@classname}{Option natbib can be either true or
79   false}}
80 \ExecuteOptionsX{natbib=true}

\if@ACM@anonymous Whether we use anonymous mode
81 \define@boolkey+{acmart.cls}[@ACM@]{anonymous}[true]{%
82   \if@ACM@anonymous
83     \PackageInfo{@classname}{Using anonymous mode}%
84   \else
85     \PackageInfo{@classname}{Not using anonymous mode}%
86   \fi}{\PackageError{@classname}{Option anonymous can be either true or
87   false}}
88 \ExecuteOptionsX{anonymous=false}

\if@ACM@timestamp Whether we use timestamp mode
89 \define@boolkey+{acmart.cls}[@ACM@]{timestamp}[true]{%
90   \if@ACM@timestamp
91     \PackageInfo{@classname}{Using timestamp mode}%
92   \else
93     \PackageInfo{@classname}{Not using timestamp mode}%
94   \fi}{\PackageError{@classname}{Option timestamp can be either true or
95   false}}
96 \ExecuteOptionsX{timestamp=false}

\if@ACM@authordraft Whether we use authordraft mode
97 \define@boolkey+{acmart.cls}[@ACM@]{authordraft}[true]{%
98   \if@ACM@authordraft
99     \PackageInfo{@classname}{Using authordraft mode}%
100    \@ACM@timestamptrue
101    \@ACM@reviewtrue
102   \else
103     \PackageInfo{@classname}{Not using authordraft mode}%
104   \fi}{\PackageError{@classname}{Option authordraft can be either true or
105   false}}
106 \ExecuteOptionsX{authordraft=false}

\ACM@fontsize The font size to pass to the base class
107 \def\ACM@fontsize{}
108 \DeclareOptionX{9pt}{\edef\ACM@fontsize{\CurrentOption}}
109 \DeclareOptionX{10pt}{\edef\ACM@fontsize{\CurrentOption}}
110 \DeclareOptionX{11pt}{\edef\ACM@fontsize{\CurrentOption}}
111 \DeclareOptionX{12pt}{\edef\ACM@fontsize{\CurrentOption}}

```

```

112 \DeclareOptionX{draft}{\PassOptionsToClass{\CurrentOption}{amsart}}
113 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
114 \ProcessOptionsX
115 \ClassInfo{\@classname}{Using format \ACM@format, number \ACM@format@nr}

```

### 3.4 Setting switches

- \if@ACM@manuscript Whether we use manuscript mode
  - 116 \newif\if@ACM@manuscript
- \if@ACM@journal There are two kinds of publications: journals and books
  - 117 \newif\if@ACM@journal
- \if@ACM@sigchiamode The formatting of SIGCHI abstracts is quite unusual. We have a special switch for them.
  - 118 \newif\if@ACM@sigchiamode

#### Setting up switches

```

119 \ifnum\ACM@format@nr=5\relax % siggraph
120   \ClassWarning{@classname}{The format ‘siggraph’ is now obsolete.
121   I am switching to sigconf.}
122   \setkeys{acmart.cls}{format=sigconf}
123 \fi
124 \ifnum\ACM@format@nr=0\relax
125   \@ACM@manuscripttrue
126 \else
127   \@ACM@manuscriptfalse
128 \fi
129 \@ACM@sigchiamodefalse
130 \ifcase\ACM@format@nr
131 \relax % manuscript
132   \@ACM@journaltrue
133 \or % acmsmall
134   \@ACM@journaltrue
135 \or % acmlarge
136   \@ACM@journaltrue
137 \or % acmtog
138   \@ACM@journaltrue
139 \or % sigconf
140   \@ACM@journalfalse
141 \or % siggraph
142   \@ACM@journalfalse
143 \or % sigplan
144   \@ACM@journalfalse
145 \or % sigchi
146   \@ACM@journalfalse
147 \or % sigchi-a
148   \@ACM@journalfalse
149   \@ACM@sigchiamodetrue
150 \fi

```

### 3.5 Loading base class and package

At this point we either have `\ACM@fontsize`, or use defaults

```
151 \ifx\ACM@fontsize\empty
152   \ifcase\ACM@format@nr
153     \relax % manuscript
154     \def\ACM@fontsize{9pt}%
155   \or % acmsmall
156     \def\ACM@fontsize{10pt}%
157   \or % acmlarge
158     \def\ACM@fontsize{10pt}%
159   \or % acmtog
160     \def\ACM@fontsize{9pt}%
161   \or % sigconf
162     \def\ACM@fontsize{9pt}%
163   \or % siggraph
164     \def\ACM@fontsize{9pt}%
165   \or % sigplan
166     \def\ACM@fontsize{10pt}%
167   \or % sigchi
168     \def\ACM@fontsize{10pt}%
169   \or % sigchi-a
170     \def\ACM@fontsize{10pt}%
171   \fi
172 \fi
173 \ClassInfo{@classname}{Using fontsize \ACM@fontsize}
174 \LoadClass[\ACM@fontsize, reqno]{amsart}
175 \RequirePackage{microtype}
```

We need `totpages` package to calculate the number of pages

```
176 \RequirePackage{totpages}
```

The `amsmath` `\collect@body` is defined using `\def`. We load `environ` to access the `\long` version of the command

```
177 \RequirePackage{environ}
```

We use `setspace` for doublespacing

```
178 \if@ACM@manuscript
179 \RequirePackage{setspace}
180 \onehalfspacing
181 \fi
```

We need `textcase` for better upcasing

```
182 \RequirePackage{textcase}
```

Citations. We patch `\setcitestyle` to allow, e.g., `\setcitestyle{sort}` and `\setcitestyle{nosort}`. We patch `\citetstyle` to warn about undefined citation styles.

```
183 \if@ACM@natbib
184   \RequirePackage{natbib}
185   \renewcommand{\bibsection}{%
```

```

186      \section*{\refname}%
187      \phantomsection\addcontentsline{toc}{section}{\refname}%
188  }
189 \renewcommand{\bibfont}{\bibliofont}
190 \renewcommand\setcitestyle[1]{%
191 @for\@tempa:=#1\do
192 {\def\@tempb{round}\ifx\@tempa\@tempb
193   \renewcommand\nat@open{} \renewcommand\nat@close{}\fi
194 \def\@tempb{square}\ifx\@tempa\@tempb
195   \renewcommand\nat@open[] \renewcommand\nat@close[]\fi
196 \def\@tempb{angle}\ifx\@tempa\@tempb
197   \renewcommand\nat@open{$$} \renewcommand\nat@close{$$}\fi
198 \def\@tempb{curly}\ifx\@tempa\@tempb
199   \renewcommand\nat@open{\{} \renewcommand\nat@close{\}}\fi
200 \def\@tempb{semicolon}\ifx\@tempa\@tempb
201   \renewcommand\nat@sep{;}\fi
202 \def\@tempb{colon}\ifx\@tempa\@tempb
203   \renewcommand\nat@sep{;}\fi
204 \def\@tempb{comma}\ifx\@tempa\@tempb
205   \renewcommand\nat@sep{,}\fi
206 \def\@tempb{authoryear}\ifx\@tempa\@tempb
207   \nat@numbersfalse\fi
208 \def\@tempb{numbers}\ifx\@tempa\@tempb
209   \nat@numberstrue\nat@superfalse\fi
210 \def\@tempb{super}\ifx\@tempa\@tempb
211   \nat@numberstrue\nat@supertrue\fi
212 \def\@tempb{nobibstyle}\ifx\@tempa\@tempb
213   \let\bibstyle=\@gobble\fi
214 \def\@tempb{bibstyle}\ifx\@tempa\@tempb
215   \let\bibstyle=\@citestyle\fi
216 \def\@tempb{sort}\ifx\@tempa\@tempb
217   \def\nat@sort{\@ne}\fi
218 \def\@tempb{nosort}\ifx\@tempa\@tempb
219   \def\nat@sort{\z@\fi
220 \def\@tempb{compress}\ifx\@tempa\@tempb
221   \def\nat@cmprs{\@ne}\fi
222 \def\@tempb{nocompress}\ifx\@tempa\@tempb
223   \def\nat@cmprs{\z@\fi
224 \def\@tempb{sort&compress}\ifx\@tempa\@tempb
225   \def\nat@sort{\@ne}\def\nat@cmprs{\@ne}\fi
226 \def\@tempb{mcite}\ifx\@tempa\@tempb
227   \let\nat@merge\@ne\fi
228 \def\@tempb{merge}\ifx\@tempa\@tempb
229   \@ifnum{\nat@merge<\tw@}{\let\nat@merge\tw@}\fi
230 \def\@tempb{elide}\ifx\@tempa\@tempb
231   \@ifnum{\nat@merge<\thr@}{\let\nat@merge\thr@}\fi
232 \def\@tempb{longnamesfirst}\ifx\@tempa\@tempb
233   \nat@longnamestrue\fi
234 \def\@tempb{nonamebreak}\ifx\@tempa\@tempb
235   \def\nat@nmfmt{\mbox{\nat@up#1}}\fi

```

```

236   \expandafter\NAT@find@eq@\tempa=\relax\@nil
237   \if\@tempc\relax\else
238     \expandafter\NAT@rem@eq@\tempc
239     \def\@tempb{\open}\ifx\@tempa\@tempb
240       \xdef\NAT@open{\@tempc}\fi
241     \def\@tempb{\close}\ifx\@tempa\@tempb
242       \xdef\NAT@close{\@tempc}\fi
243     \def\@tempb{\aysep}\ifx\@tempa\@tempb
244       \xdef\NAT@aysep{\@tempc}\fi
245     \def\@tempb{\yysep}\ifx\@tempa\@tempb
246       \xdef\NAT@yysep{\@tempc}\fi
247     \def\@tempb{\notesep}\ifx\@tempa\@tempb
248       \xdef\NAT@cmt{\@tempc}\fi
249     \def\@tempb{\citesep}\ifx\@tempa\@tempb
250       \xdef\NAT@sep{\@tempc}\fi
251   \fi
252 }%
253 \NAT@setcites
254 }
255 \renewcommand{\citestyle}[1]{%
256   \ifcsname bibstyle@\#1\endcsname%
257     \csname bibstyle@\#1\endcsname\let\bibstyle@gobble%
258   \else%
259     \@latex@error{Undefined ‘#1’ citestyle}%
260   \fi
261 }%
262 \fi

```

\bibstyle@acmauthoryear The default author-year format:

```

263 \newcommand{\bibstyle@acmauthoryear}{%
264   \setcitestyle{%
265     authoryear,%
266     open={},close={},citesep={;},%
267     aysep={},yysep={,,},%
268     notesep={, }}}

```

\bibstyle@acmnumeric The default numeric format:

```

269 \newcommand{\bibstyle@acmnumeric}{%
270   \setcitestyle{%
271     numbers,sort&compress,%
272     open={},close={},citesep={,,},%
273     notesep={, }})

```

The default is numeric:

```

274 \if@ACM@natbib
275 \citestyle{acmnumeric}
276 \fi

```

\@startsection Before we call `hyperref`, we redefine `\startsection` commands to their L<sup>A</sup>T<sub>E</sub>X defaults, since `amsart` ones are too AMS-specific. We need to do this early since we want `hyperref` to have a chance to redefine them again:

```

277 \def\@startsection#1#2#3#4#5#6{%
278   \if@noskipsec \leavevmode \fi
279   \par
280   \tempskipa #4\relax
281   \ifdim \tempskipa <\z@
282     \tempskipa -\tempskipa \ifdimfalse
283   \fi
284   \ifnobreak
285     \everypar{}%
286   \else
287     \addpenalty\secpenalty\addvspace\tempskipa
288   \fi
289   \ifstar
290     {\@ssect{\#3}{\#4}{\#5}{\#6}}%
291     {\@dblarg{\@sect{\#1}{\#2}{\#3}{\#4}{\#5}{\#6}}}
292   \def\@sect#1#2#3#4#5#6[#7]{#8}%
293   \edef\@toclevel{\ifnum#2=\z@ \else\number#2\fi}%
294   \ifnum #2>\c@sectiondepth
295     \let\@svsec\empty
296   \else
297     \refstepcounter{\#1}%
298     \protected@edef\@svsec{\@secntformat{\#1}\relax}%
299   \fi
300   \tempskipa #5\relax
301   \ifdim \tempskipa>\z@
302     \begingroup
303       \#6{%
304         \hangfrom{\hspace{\#3}\relax\@svsec}%
305         \interlinepenalty \z@ \elsepar}%
306     \endgroup
307     \csname #1mark\endcsname{\#7}%
308   \ifnum #2>\c@sectiondepth \else
309     \tochangemeasure{\csname the#1\endcsname}%
310   \fi
311   \addcontentsline{toc}{\#1}{%
312     \ifnum #2>\c@sectiondepth \else
313       \protect\numberline{\csname the#1\endcsname}%
314     \fi
315     \#7}%
316   \else
317     \def\@svsechd{%
318       \#6{\hspace{\#3}\relax
319       \@svsec \#8}%
320       \csname #1mark\endcsname{\#7}%
321     \ifnum #2>\c@sectiondepth \else
322

```

```

323      \@tochangmeasure{\csname the#1\endcsname\space}%
324      \fi
325      \addcontentsline{toc}{#1}{%
326          \ifnum #2>\c@secnumdepth \else
327              \protect\numberline{\csname the#1\endcsname}%
328          \fi
329      #7}%
330  \fi
331  \@xsect{#5}
332 \def\@xsect#1{%
333     \@tempskipa #1\relax
334     \ifdim \@tempskipa>\z@
335         \par \nobreak
336         \vskip \@tempskipa
337         \afterheading
338     \else
339         \nobreakfalse
340         \global\@noskipsectrue
341         \everypar{%
342             \if@noskipsec
343                 \global\@noskipsecfalse
344                 \setbox\z@\lastbox}%
345                 \clubpenalty\@M
346                 \begingroup \svsechd \endgroup
347                 \unskip
348                 \@tempskipa #1\relax
349                 \hskip -\@tempskipa
350             \else
351                 \clubpenalty \clubpenalty
352                 \everypar{}%
353             \fi}%
354     \fi
355     \ignorespaces}
356 \def\@seccntformat#1{\csname the#1\endcsname\quad}
357 \def\@ssect#1#2#3#4#5{%
358     \@tempskipa #3\relax
359     \ifdim \@tempskipa>\z@
360         \begingroup
361             #4{%
362                 \hangfrom{\hskip #1}%
363                 \interlinepenalty \M #5\@@par}%
364         \endgroup
365     \else
366         \def\@svsechd{#4{\hskip #1\relax #5}}%
367     \fi
368     \@xsect{#3}}

```

\@startsection Amsart redefines \startsection. Here we redefine it again to make TOC working

```

369 \def\@starttoc#1#2{\begingroup
370   \setTrue{#1}%

```

```

371 \par\removelastskip\vskip\z@skip
372 \@startsection{section}{\@M\z@\{\linespacing\@plus\linespacing\}%
373   {.5\linespacing}\{\centering\contentsnamefont\}{#2}\%}
374 \input{\jobname.\#1}%
375 \if@filesw
376   \xp\newwrite\csname tf\#1\endcsname
377   \immediate\xp\openout\csname tf\#1\endcsname \jobname.\#1\relax
378 \fi
379 \global\nobreakfalse \endgroup
380 \addvspace{32\p@\@plus14\p@\%}
381 }

\l@section Section spacing is more generous than for amsart
382 \def\l@section{\@tocline{1}{0pt}{1pc}{2pc}{}}

\l@subsection Amsart has too large spacing
383 \def\l@subsection{\@tocline{2}{0pt}{1pc}{3pc}{}}

\l@subsubsection Amsart has too large spacing
384 \def\l@subsubsection{\@tocline{2}{0pt}{1pc}{5pc}{}}

And hyperref
385 \let@\footnotemark@nolink@\footnotemark
386 \let@\footnotetext@nolink@\footnotetext
387 \RequirePackage[bookmarksnumbered,unicode]{hyperref}
388 \pdfstringdefDisableCommands{%
389   \def\unskip{}%
390   \def\textbullet{- }%
391   \def\textrightarrow{->}%
392   \def\footnotemark{}%
393 }
394 \urlstyle{rm}
395 \ifcase\ACM@format@nr
396 \relax % manuscript
397 \or % acmsmall
398 \or % acmlarge
399 \or % acmtog
400 \or % sigconf
401 \or % siggraph
402 \or % sigplan
403 \urlstyle{sf}
404 \or % sigchi
405 \or % sigchi-a
406 \urlstyle{sf}
407 \fi
408 \if@ACM@screen
409   \hypersetup{colorlinks,
410     linkcolor=ACMRed,
411     citecolor=ACMPurple,

```

```

412     urlcolor=ACMDarkBlue,
413     filecolor=ACMDarkBlue}
414 \else
415   \hypersetup{hidelinks}
416 \fi
417 \RequirePackage{cleveref}

    Bibliography mangling.

418 \if@ACM@natbib
419   \let\citeN\cite
420   \let\cite\citep
421   \let\citeANP\citeauthor
422   \let\citeNN\citeyearpar
423   \let\citeyearNP\citeyear
424   \let\citeyear\citeyearpar
425   \let\citeNP\citealt
426   \DeclareRobustCommand{\citeA}
427     {\begingroup\nAT@swafalse
428       \let\nAT@ctype@\ne\nAT@partrue\nAT@fullfalse\nAT@open\nAT@citetp}%
429   \providecommand{\newblock}{}}%
430 \else
431   \AtBeginDocument{%
432     \let\shortcite\cite%
433     \providecommand{\citename}[1]{#1}}
434 \fi
435 \newcommand{\shortcite}[2]{%
436   \ifNAT@numbers\cite[#1]{#2}\else\citeyear[#1]{#2}\fi}

```

\bibliographystyle Amsart redefines \bibliographystyle since it prefers AMS bibliography. We turn it back to L<sup>A</sup>T<sub>E</sub>X definition:

```

437 \def\bibliographystyle#1{%
438   \ifx\@begindocumenthook\undefined\else
439     \expandafter\AtBeginDocument
440   \fi
441   {\if@filesw
442     \immediate\write\auxout{\string\bibstyle{#1}}%
443   \fi}}

```

#### Graphics and color

```
444 \RequirePackage{graphicx, xcolor}
```

We define ACM colors according to [7]:

```

445 \definecolor[named]{ACMBlue}{cmyk}{1,0.1,0,0.1}
446 \definecolor[named]{ACMYellow}{cmyk}{0,0.16,1,0}
447 \definecolor[named]{ACMOOrange}{cmyk}{0,0.42,1,0.01}
448 \definecolor[named]{ACMRed}{cmyk}{0,0.90,0.86,0}
449 \definecolor[named]{ACMLightBlue}{cmyk}{0.49,0.01,0,0}
450 \definecolor[named]{ACMGreen}{cmyk}{0.20,0,1,0.19}
451 \definecolor[named]{ACMPurple}{cmyk}{0.55,1,0,0.15}
452 \definecolor[named]{ACMDarkBlue}{cmyk}{1,0.58,0,0.21}

```

Author draft mode

```
453 \if@ACM@authordraft
454   \RequirePackage{draftwatermark}
455   \SetWatermarkFontSize{0.5in}
456   \SetWatermarkColor[gray]{.9}
457   \SetWatermarkText{\parbox{12em}{\centering
458     Unpublished working draft\
459     Not for distribution}}
460 \fi
```

### 3.6 Paper size and paragraphing

We use `geometry` for dimensions. Note the presently margins do not depend on the font size option - maybe we will need to change this. See <https://github.com/borisveytsman/acmart/issues/5#issuecomment-272881329>.

```
461 \RequirePackage{geometry}
462 \ifcase\ACM@format@nr
463   \relax % manuscript
464   \geometry{letterpaper,head=13pt,
465   marginparwidth=6pc,heightrounded}%
466 \or % acmsmall
467   \geometry{twoside=true,
468   includeheadfoot, head=13pt, foot=2pc,
469   paperwidth=6.75in, paperheight=10in,
470   top=58pt, bottom=44pt, inner=46pt, outer=46pt,
471   marginparwidth=2pc,heightrounded
472 }%
473 \or % acmlarge
474   \geometry{twoside=true, head=13pt, foot=2pc,
475   paperwidth=8.5in, paperheight=11in,
476   includeheadfoot,
477   top=78pt, bottom=114pt, inner=81pt, outer=81pt,
478   marginparwidth=4pc,heightrounded
479 }%
480 \or % acmtog
481   \geometry{twoside=true, head=13pt, foot=2pc,
482   paperwidth=8.5in, paperheight=11in,
483   includeheadfoot, columnsep=24pt,
484   top=52pt, bottom=75pt, inner=52pt, outer=52pt,
485   marginparwidth=2pc,heightrounded
486 }%
487 \or % sigconf
488   \geometry{twoside=true, head=13pt,
489   paperwidth=8.5in, paperheight=11in,
490   includeheadfoot, columnsep=2pc,
491   top=57pt, bottom=73pt, inner=54pt, outer=54pt,
492   marginparwidth=2pc,heightrounded
493 }%
494 \or % siggraph
```

```

495   \geometry{twoside=true, head=13pt,
496     paperwidth=8.5in, paperheight=11in,
497     includeheadfoot, columnsep=2pc,
498     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
499     marginparwidth=2pc, heightrounded
500   }%
501 \or % sigplan
502   \geometry{twoside=true, head=13pt,
503     paperwidth=8.5in, paperheight=11in,
504     includeheadfoot=false, columnsep=2pc,
505     top=1in, bottom=1in, inner=0.75in, outer=0.75in,
506     marginparwidth=2pc, heightrounded
507   }%
508 \or % sigchi
509   \geometry{twoside=true, head=13pt,
510     paperwidth=8.5in, paperheight=11in,
511     includeheadfoot, columnsep=2pc,
512     top=66pt, bottom=73pt, inner=54pt, outer=54pt,
513     marginparwidth=2pc, heightrounded
514   }%
515 \or % sigchi-a
516   \geometry{twoside=false, head=13pt,
517     paperwidth=11in, paperheight=8.5in,
518     includeheadfoot, marginparsep=72pt,
519     marginparwidth=170pt, columnsep=20pt,
520     top=72pt, bottom=72pt, left=314pt, right=72pt
521   }%
522   \@mparswitchfalse
523   \reversemarginpar
524 \fi

\parindent Paragraphing
\parskip 525 \setlength{\parindent}{10\p@}
526 \setlength{\parskip}{\z@}
527 \ifcase\ACM@format@nr
528   \relax % manuscript
529 \or % acmsmall
530 \or % acmlarge
531 \or % acmtog
532   \setlength{\parindent}{9\p@}%
533 \or % sigconf
534 \or % siggraph
535 \or % sigplan
536 \or % sigchi
537 \or % sigchi-a
538 \fi

\normalparindent amsart defines the \normalparindent length and initializes it to 12pt (the value of \parindent in amsart). It is later used to set the \listparindent length in the quotation environment and the \parindent length in the \@footnotetext command.

```

We set `\normalparindent` to the value of `\parindent` as selected by `acmart` for consistent paragraph indents.

```
539 \setlength{\normalparindent}{\parindent}
```

Footnotes require some consideration. We have several layers of footnotes: front-matter footnotes, “regular” footnotes and the special insert for `bibstrip`. In the old ACM classes `bibstrip` was a `@float`. The problem with floats is that they tend to, well, float—and we want the guarantee they stay.

We use `manyfoot` for layered footnotes instead.

`\copyrightpermissionfootnoterule` This is the footnote rule that separates `bibstrip` from the rest of the paper. It is a full width rule.

```
540 \def\copyrightpermissionfootnoterule{\kern-3\p@  
541   \hrule \width \columnwidth \kern 2.6\p@}  
  
542 \RequirePackage{manyfoot}  
543 \SelectFootnoteRule[2]{copyrightpermission}  
544 \DeclareNewFootnote{copyrightpermission}
```

`\footnoterule` Tschichold’s rules:

```
545 \def\footnoterule{\kern-3\p@  
546   \hrule \width 4pc \kern 2.6\p@}
```

`\endminipage` We do not use footnote rules in minipages

```
547 \def\endminipage{  
548   \par  
549   \unskip  
550   \ifvoid\@mpfootins\else  
551     \vskip\skip\@mpfootins  
552     \normalcolor  
553     \unvbox\@mpfootins  
554   \fi  
555   \@minipagetrue %% added 24 May 89  
556 \color@endgroup  
557 \egroup  
558 \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}}
```

`\@makefntext` We do note use indentation for footnotes

```
559 \def\@makefntext{\noindent\@makefnmark}
```

`\@footnotetext` In sigchi-a mode our footnotes are on the margins!

```
560 \if@ACM@sigchiamode  
561 \long\def\@footnotetext#1{\marginpar{  
562   \reset@font\small  
563   \interlinepenalty\interfootnotelinepenalty  
564   \protected@edef\@currentlabel{  
565     \csname p@footnote\endcsname\@thefnmark  
566   }%  
567   \color@begingroup
```

```

568      \@makefntext{%
569          \rule{z}{\footnotesep}\ignorespaces#1\@finalstrut\strutbox}%
570      \color@endgroup}}%
571 \fi

\@mpfootnotetext We want the footnotes in minipages centered:
572 \long\def\@mpfootnotetext#1{%
573   \global\setbox\@mpfootins\vbox{%
574     \unvbox\@mpfootins
575     \reset@font\footnotesize
576     \hsize\columnwidth
577     \parboxrestore
578     \protected@edef\@currentlabel
579       {\csname p@mpfootnote\endcsname\@thefnmark}%
580     \color@begingroup\centering
581     \@makefntext{%
582       \rule{z}{\footnotesep}\ignorespaces#1\@finalstrut\strutbox}%
583     \color@endgroup}}
584 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}

\@textbottom Added some stretch according to David Carlisle's advice at http://tex.stackexchange.com/a/62318/5522
585 \def\@textbottom{\vskip \z@ \oplus 1pt}
586 \let\@texttop\relax

```

### 3.7 Fonts

Somehow PDFTeX and XeTeX require different incantations to make PDF compliant with the current Acrobat bugs. Xpdf is much better.

The code below is by Ross Moore.

```

587 \RequirePackage{ifthen}
588 \ifPDFTeX
589 \input{glyptounicode}
590 \pdfglyptounicode{f_f}{FB00}
591 \pdfglyptounicode{f_f_i}{FB03}
592 \pdfglyptounicode{f_f_l}{FB04}
593 \pdfglyptounicode{f_i}{FB01}
594 \pdfglyptounicode{t_t}{00740074}
595 \pdfglyptounicode{f_t}{00660074}
596 \pdfglyptounicode{T_h}{00540068}
597 \pdfgentounicode=1
598 \fi
599 \RequirePackage{cmap}

```

```

\if@ACM@newfonts Whether we load the new fonts
600 \newif\if@ACM@newfonts
601 \if@ACM@newfontstrue
602 \IfFileExists{libertine.sty}{}{\ClassWarning{@classname}{You do not

```

```

603     have libertine package installed. Please upgrade your
604     TeX}\@ACM@newfontsfalse}
605 \IfFileExists{zi4.sty}{}{\ClassWarning{\classname}{You do not
606     have zi4 package installed. Please upgrade your TeX}\@ACM@newfontsfalse}
607 \IfFileExists{newtxmath.sty}{}{\ClassWarning{\classname}{You do not
608     have newtxmath package installed. Please upgrade your
609     TeX}\@ACM@newfontsfalse}}

```

We use Libertine throughout.

```

610 \if@ACM@newfonts
611 \RequirePackage[tt=false, type1=true]{libertine}
612 \RequirePackage[varqu]{zi4}
613 \RequirePackage[libertine]{newtxmath}
614 \RequirePackage[T1]{fontenc}
615 \fi

```

The SIGCHI extended abstracts are sans serif:

```

616 \if@ACM@sigchiamode
617   \renewcommand{\familydefault}{\sfdefault}
618 \fi

```

### 3.8 Floats

We use caption package

```

619 \RequirePackage[caption, float]
620 \captionsetup[table]{position=top}
621 \if@ACM@journal
622   \captionsetup[labelfont={sf, small},
623     textfont={sf, small}, margin=\z@}
624   \captionsetup[figure]{name={Fig.}}
625 \else
626   \captionsetup[labelfont={bf},
627     textfont={bf}, labelsep=colon, margin=\z@}
628 \ifcase\ACM@format@nr
629   \relax % manuscript
630   \or % acmsmall
631   \or % acmlarge
632   \or % acmtog
633   \or % sigconf
634   \or % siggraph
635     \captionsetup{textfont={it}}
636   \or % sigplan
637     \captionsetup[labelfont={bf},
638       textfont={normalfont}, labelsep=period, margin=\z@}
639   \or % sigchi
640     \captionsetup[figure]{labelfont={bf, small},
641       textfont={bf, small}}}
642   \or % sigchi-a
643     \captionsetup[figure]{labelfont={bf, small},
644       textfont={bf, small}}}

```

```

645 \fi
646 \fi

sidebar The sidebar environment:
647 \newfloat{sidebar}{}{sbar}
648 \floatname{sidebar}{Sidebar}
649 \renewenvironment{sidebar}{\Collect@Body@\sidebar}{} 

\@sidebar The processing of the saved text
650 \long\def\@sidebar#1{\bgroup\captionsetup{type=sidebar}%
651 \marginpar{\small#1}\egroup}

marginfigure The marginfigure environment:
652 \newenvironment{marginfigure}{\Collect@Body@\marginfigure}{} 

\@marginfigure The processing of the saved text
653 \long\def\@marginfigure#1{\bgroup\captionsetup{type=figure}%
654 \marginpar{\centering\small#1}\egroup}

margitable The margitable environment:
655 \newenvironment{margitable}{\Collect@Body@\margitable}{} 

\@margitable The processing of the saved text
656 \long\def\@margitable#1{\bgroup\captionsetup{type=table}%
657 \marginpar{\centering\small#1}\egroup}

      SIGCHI extended abstract provides an interesting possibility to push into the margin.
      Here we use figure* and table* for this.

\fulltextwidth We define the width of the boxes as
658 \newdimen\fulltextwidth
659 \fulltextwidth=\dimexpr(\textwidth+\marginparwidth+\marginparsep)

\dblfloat We redefine the double float command. First, we make the size bigger. Second, our
default position is going to be tp (to give marginalia a chance)
660 \if@ACM@sigchiamode
661 \def\@dblfloat{\bgroup\columnwidth=\fulltextwidth
662 \let\@endfloatbox\@endwidefloatbox
663 \def\@fpsadddefault{\def\@fps{tp}}%
664 \@float}
665 \fi

\enddblfloat And the end. Just adding a \bgroup.
666 \if@ACM@sigchiamode
667 \def\end\@dblfloat{%
668 \end\@float\egroup}
669 \fi

```

```
\@endwidefloatbox This is the end of a wide box - we basically move everything to the left
```

```
670 \def\@endwidefloatbox{%
671   \par\vskip\z@skip
672   \minipagetrue
673   \outer@nobreak
674   \egroup
675   \color@endbox
676   \global\setbox\currbox=\vbox{\moveleft
677     \dimexpr(\fulltextwidth-\textwidth)\box\currbox}%
678   \wd\currbox=\textwidth
679 }
```

### 3.9 Lists

```
680 \ifcase\ACM@format@nr
681   \relax % manuscript
682   \or % acmsmall
683   \or % acmlarge
684   \or % acmtog
685   \or % sigconf
686   \or % siggraph
687   \or % sigplan
688   \def\labelenumi{\theenumi.}
689   \def\labelenumii{\theenumii.}
690   \def\labelenumiii{\theenumiii.}
691   \def\labelenumiv{\theenumiv.}
692   \or % sigchi
693   \or % sigchi-a
694 \fi
```

AMS uses generous margins for the lists. Note that `amsart` defines `\leftmargin` values for list levels at begin document, so we must redefine them in the same manner. Also, note that `amsart` redefines `enumerate` and `itemize` environments with a `\makelabel` command that uses `\llap`, so the `\labelwidth` value is (effectively) irrelevant; nonetheless, we follow `amsart` and set `\labelwidth` to `\leftmargin` minus `\labelsep`.

```
695 \newdimen\@ACM@labelwidth
696 \AtBeginDocument{%
697   \setlength\labelsep{4pt}
698   \setlength{\@ACM@labelwidth}{6.5pt}
699
700   %% First-level list: when beginning after the first line of an
701   %% indented paragraph or ending before an indented paragraph, labels
702   %% should not hang to the left of the preceding/following text.
703   \setlength\leftmargini{\z@}
704   \addtolength\leftmargini{\parindent}
705   \addtolength\leftmargini{2\labelsep}
706   \addtolength\leftmargini{\@ACM@labelwidth}
707
708   %% Second-level and higher lists.
709   \setlength\leftmarginii{\z@}
```

```

710  \addtolength{\leftmarginii}{0.5\labelsep}
711  \addtolength{\leftmarginii}{\@ACM@labelwidth}
712  \setlength{\leftmarginiii}{\leftmarginii}
713  \setlength{\leftmarginiv}{\leftmarginii}
714  \setlength{\leftmarginv}{\leftmarginiv}
715  \setlength{\leftmarginvi}{\leftmarginv}
716  \@listi
717 \newskip\listisep
718 \listisep\smallskipamount
719 \def@listI{\leftmargin\leftmargini
720   \labelwidth\leftmargini \advance\labelwidth-\labelsep
721   \listparindent\z@
722   \topsep\listisep}
723 \let@\listi@\listI
724 \def@listii{\leftmargin\leftmarginii
725   \labelwidth\leftmarginii \advance\labelwidth-\labelsep
726   \topsep\z@skip}
727 \def@listiii{\leftmargin\leftmarginiii
728   \labelwidth\leftmarginiii \advance\labelwidth-\labelsep}
729 \def@listiv{\leftmargin\leftmarginiv
730   \labelwidth\leftmarginiv \advance\labelwidth-\labelsep}
731 \def@listv{\leftmargin\leftmarginv
732   \labelwidth\leftmarginv \advance\labelwidth-\labelsep}
733 \def@listvi{\leftmargin\leftmarginvi
734   \labelwidth\leftmarginvi \advance\labelwidth-\labelsep}

\descriptionlabel We do not use default colon as \amsart does:
735 \renewcommand{\descriptionlabel}[1]{\upshape\bfseries #1}

\description Make description environment indentation consistent with that of itemize and
enumeration environments.
736 \renewenvironment{description}{\list{}{%
737   \labelwidth\@ACM@labelwidth
738   \let\makelabel\descriptionlabel}%
739 }{%
740   \endlist
741 }
742 \let\enddescription=\endlist % for efficiency

```

### 3.10 Top matter data

We use keyval interface to define journal title and relevant information

```

743 \define@choicekey*+{ACM}{acmJournal}[\@journalCode\@journalCode@nr]{%
744   CIE,%
745   CSUR,%
746   IMWUT,%
747   JACM,%
748   JDIQ,%
749   JEA,%

```

```

750 JERIC,%
751 JETC,%
752 JOCCH,%
753 PACMHCI,%
754 PACMPL,%
755 POMACS,%
756 TAAS,%
757 TACCESS,%
758 TACO,%
759 TALG,%
760 TALLIP,%
761 TAP,%
762 TCPS,%
763 TEAC,%
764 TECS,%
765 TIIS,%
766 TISSEC,%
767 TIST,%
768 TKDD,%
769 TMIS,%
770 TOCE,%
771 TOCHI,%
772 TOCL,%
773 TOCS,%
774 TOCT,%
775 TODAES,%
776 TODS,%
777 TOG,%
778 TOIS,%
779 TOIT,%
780 TOMACS,%
781 TOMM,%
782 TOMPECS,%
783 TOMS,%
784 TOPC,%
785 TOPS,%
786 TOPLAS,%
787 TOS,%
788 TOSEM,%
789 TOSN,%
790 TRETS,%
791 TSAS,%
792 TSC,%
793 TSLP,%
794 TWEB%
795 }{%
796 \ifcase\@journalCode@nr
797 \relax % CIE
798 \def\@journalName{ACM Computers in Entertainment}%
799 \def\@journalNameShort{ACM Comput. Entertain.}%

```

```

800  \def \@permissionCodeOne{1544-3574}%
801 \or % CSUR
802  \def \@journalName{ACM Computing Surveys}%
803  \def \@journalNameShort{ACM Comput. Surv.}%
804  \def \@permissionCodeOne{0360-0300}%
805 \or % IMWUT
806  \def \@journalName{Proceedings of the ACM on Interactive, Mobile,
807      Wearable and Ubiquitous Technologies}%
808  \def \@journalNameShort{Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.}%
809  \def \@permissionCodeOne{2474-9567}%
810 \or % JACM
811  \def \@journalName{Journal of the ACM}%
812  \def \@journalNameShort{J. ACM}%
813  \def \@permissionCodeOne{0004-5411}%
814 \or % JDIQ
815  \def \@journalName{ACM Journal of Data and Information Quality}%
816  \def \@journalNameShort{ACM J. Data Inform. Quality}%
817  \def \@permissionCodeOne{1936-1955}%
818 \or % JEA
819  \def \@journalName{ACM Journal of Experimental Algorithms}%
820  \def \@journalNameShort{ACM J. Exp. Algor.}%
821  \def \@permissionCodeOne{1084-6654}%
822 \or % JERIC
823  \def \@journalName{ACM Journal of Educational Resources in Computing}%
824  \def \@journalNameShort{ACM J. Edu. Resources in Comput.}%
825  \def \@permissionCodeOne{1073-0516}%
826 \or % JETC
827  \def \@journalName{ACM Journal on Emerging Technologies in Computing Systems}%
828  \def \@journalNameShort{ACM J. Emerg. Technol. Comput. Syst.}%
829  \def \@permissionCodeOne{1550-4832}%
830 \or % JOCCH
831  \def \@journalName{ACM Journal on Computing and Cultural Heritage}%
832  \def \@journalName{ACM J. Comput. Cult. Herit.}%
833 \or % PADMHCI
834  \def \@journalName{Proceedings of the ACM on Human-Computer Interaction}%
835  \def \@journalName{Proc. ACM Hum.-Comput. Interact.}%
836  \def \@permissionCodeOne{2573-0142}%
837 \or % PACMPL
838  \def \@journalName{Proceedings of the ACM on Programming Languages}%
839  \def \@journalName{Proc. ACM Program. Lang.}%
840  \def \@permissionCodeOne{2475-1421}%
841 \or % POMACS
842  \def \@journalName{Proceedings of the ACM on Measurement and Analysis of Computing Systems}%
843  \def \@journalName{Proc. ACM Meas. Anal. Comput. Syst.}%
844  \def \@permissionCodeOne{2476-1249}%
845 \or % TAAS
846  \def \@journalName{ACM Transactions on Autonomous and Adaptive Systems}%
847  \def \@journalNameShort{ACM Trans. Autonom. Adapt. Syst.}%
848  \def \@permissionCodeOne{1556-4665}%
849 \or % TACCESS

```

```

850 \def \@journalName{ACM Transactions on Accessible Computing}%
851 \def \@journalNameShort{ACM Trans. Access. Comput.}%
852 \def \@permissionCodeOne{1936-7228}%
853 \or % TACO
854 \def \@journalName{ACM Transactions on Architecture and Code Optimization}%
855 \or % TALG
856 \def \@journalName{ACM Transactions on Algorithms}%
857 \def \@journalNameShort{ACM Trans. Algor.}%
858 \def \@permissionCodeOne{1549-6325}%
859 \or % TALLIP
860 \def \@journalName{ACM Transactions on Asian and Low-Resource Language Information Processing}%
861 \def \@journalNameShort{ACM Trans. Asian Low-Resour. Lang. Inf. Process.}%
862 \def \@permissionCodeOne{2375-4699}%
863 \or % TAP
864 \def \@journalName{ACM Transactions on Applied Perception}%
865 \or % TCPS
866 \def \@journalName{ACM Transactions on Cyber-Physical Systems}%
867 \or % TEAC
868 \def \@journalName{ACM Transactions on Economics and Computation}%
869 \or % TECS
870 \def \@journalName{ACM Transactions on Embedded Computing Systems}%
871 \def \@journalNameShort{ACM Trans. Embedd. Comput. Syst.}%
872 \def \@permissionCodeOne{1539-9087}%
873 \or % TIIS
874 \def \@journalName{ACM Transactions on Interactive Intelligent Systems}%
875 \def \@journalNameShort{ACM Trans. Interact. Intell. Syst.}%
876 \def \@permissionCodeOne{2160-6455}%
877 \or % TISSEC
878 \def \@journalName{ACM Transactions on Information and System Security}%
879 \def \@journalNameShort{ACM Trans. Info. Syst. Sec.}%
880 \def \@permissionCodeOne{1094-9224}%
881 \or % TIST
882 \def \@journalName{ACM Transactions on Intelligent Systems and Technology}%
883 \def \@journalNameShort{ACM Trans. Intell. Syst. Technol.}%
884 \def \@permissionCodeOne{2157-6904}%
885 \or % TKDD
886 \def \@journalName{ACM Transactions on Knowledge Discovery from Data}%
887 \def \@journalNameShort{ACM Trans. Knowl. Discov. Data.}%
888 \def \@permissionCodeOne{1556-4681}%
889 \or % TMIS
890 \def \@journalName{ACM Transactions on Management Information Systems}%
891 \def \@journalNameShort{ACM Trans. Manag. Inform. Syst.}%
892 \def \@permissionCodeOne{2158-656X}%
893 \or % TOCE
894 \def \@journalName{ACM Transactions on Computing Education}%
895 \def \@journalNameShort{ACM Trans. Comput. Educ.}%
896 \def \@permissionCodeOne{1946-6226}%
897 \or % TOCHI
898 \def \@journalName{ACM Transactions on Computer-Human Interaction}%
899 \def \@journalNameShort{ACM Trans. Comput.-Hum. Interact.}%

```

```

900  \def \@permissionCodeOne{1073-0516}%
901  \or % TOCL
902  \def \@journalName{ACM Transactions on Computational Logic}%
903  \def \@journalNameShort{ACM Trans. Comput. Logic}%
904  \def \@permissionCodeOne{1529-3785}%
905 \or % TOCS
906  \def \@journalName{ACM Transactions on Computer Systems}%
907  \def \@journalNameShort{ACM Trans. Comput. Syst.}%
908  \def \@permissionCodeOne{0734-2071}%
909 \or % TOCT
910  \def \@journalName{ACM Transactions on Computation Theory}%
911  \def \@journalNameShort{ACM Trans. Comput. Theory}%
912  \def \@permissionCodeOne{1942-3454}%
913 \or % TODAES
914  \def \@journalName{ACM Transactions on Design Automation of Electronic Systems}%
915  \def \@journalNameShort{ACM Trans. Des. Autom. Electron. Syst.}%
916  \def \@permissionCodeOne{1084-4309}%
917 \or % TODS
918  \def \@journalName{ACM Transactions on Database Systems}%
919  \def \@journalNameShort{ACM Trans. Datab. Syst.}%
920  \def \@permissionCodeOne{0362-5915}%
921 \or % TOG
922  \def \@journalName{ACM Transactions on Graphics}%
923  \def \@journalNameShort{ACM Trans. Graph.}%
924  \def \@permissionCodeOne{0730-0301}%
925 \or % TOIS
926  \def \@journalName{ACM Transactions on Information Systems}%
927  \def \@journalNameShort{ACM Transactions on Information Systems}%
928  \def \@permissionCodeOne{1046-8188}%
929 \or % TOIT
930  \def \@journalName{ACM Transactions on Internet Technology}%
931  \def \@journalNameShort{ACM Trans. Internet Technol.}%
932  \def \@permissionCodeOne{1533-5399}%
933 \or % TOMACS
934  \def \@journalName{ACM Transactions on Modeling and Computer Simulation}%
935  \def \@journalNameShort{ACM Trans. Modeling and Computer Simulation}%
936  \def \@journalNameShort{ACM Trans. Model. Comput. Simul.}%
937 \or % TOMM
938  \def \@journalName{ACM Transactions on Multimedia Computing, Communications and Applications}%
939  \def \@journalNameShort{ACM Trans. Multimedia Comput. Commun. Appl.}%
940  \def \@permissionCodeOne{1551-6857}%
941  \def \@permissionCodeTwo{0100}%
942 \or % TOMEPCS
943  \def \@journalName{ACM Transactions on Modeling and Performance Evaluation of Computing Systems}%
944  \def \@journalNameShort{ACM Trans. Model. Perform. Eval. Comput. Syst.}%
945  \def \@permissionCodeOne{2376-3639}%
946 \or % TOMS
947  \def \@journalName{ACM Transactions on Mathematical Software}%
948  \def \@journalNameShort{ACM Trans. Math. Softw.}%
949  \def \@permissionCodeOne{0098-3500}%

```

```

950 \or % TOPC
951 \def \@journalName{ACM Transactions on Parallel Computing}%
952 \def \@journalNameShort{ACM Trans. Parallel Comput.}%
953 \def \@permissionCodeOne{1539-9087}%
954 \or % TOPS
955 \def \@journalName{ACM Transactions on Privacy and Security}%
956 \def \@journalNameShort{ACM Trans. Priv. Sec.}%
957 \def \@permissionCodeOne{2471-2566}%
958 \or % TOPLAS
959 \def \@journalName{ACM Transactions on Programming Languages and Systems}%
960 \def \@journalNameShort{ACM Trans. Program. Lang. Syst.}%
961 \def \@permissionCodeOne{0164-0925}%
962 \or % TOS
963 \def \@journalName{ACM Transactions on Storage}%
964 \def \@journalNameShort{ACM Trans. Storage}%
965 \def \@permissionCodeOne{1553-3077}%
966 \or % TOSEM
967 \def \@journalName{ACM Transactions on Software Engineering and Methodology}%
968 \def \@journalNameShort{ACM Trans. Softw. Eng. Methodol.}%
969 \def \@permissionCodeOne{1049-331X}%
970 \or % TOSN
971 \def \@journalName{ACM Transactions on Sensor Networks}%
972 \def \@journalNameShort{ACM Trans. Sensor Netw.}%
973 \def \@permissionCodeOne{1550-4859}%
974 \or % TRETS
975 \def \@journalName{ACM Transactions on Reconfigurable Technology and Systems}%
976 \def \@journalNameShort{ACM Trans. Reconfig. Technol. Syst.}%
977 \def \@permissionCodeOne{1936-7406}%
978 \or % TSAS
979 \def \@journalName{ACM Transactions on Spatial Algorithms and Systems}%
980 \def \@journalNameShort{ACM Trans. Spatial Algorithms Syst.}%
981 \def \@permissionCodeOne{2374-0353}%
982 \or % TSC
983 \def \@journalName{ACM Transactions on Social Computing}%
984 \def \@journalNameShort{ACM Trans. Soc. Comput.}%
985 \def \@permissionCodeOne{2469-7818}%
986 \or % TSLP
987 \def \@journalName{ACM Transactions on Speech and Language Processing}%
988 \def \@journalNameShort{ACM Trans. Speech Lang. Process.}%
989 \def \@permissionCodeOne{1550-4875}%
990 \or % TWEB
991 \def \@journalName{ACM Transactions on the Web}%
992 \def \@journalNameShort{ACM Trans. Web}%
993 \def \@permissionCodeOne{1559-1131}%
994 \fi
995 \ClassInfo{@classname}{Using journal code \@journalCode}%
996 }{%
997 \ClassError{@classname}{Incorrect journal #1}%
998 }%

```

```

\acmJournal And the syntactic sugar around it
999 \def\acmJournal#1{\setkeys{ACM}{acmJournal=#1}}


The defaults:
1000 \def@journalCode@nr{0}
1001 \def@journalName{ }%
1002 \def@journalNameShort{@journalName}%
1003 \def@permissionCodeOne{XXXX-XXXX}%
1004 \def@permissionCodeTwo{ }%


\acmConference This is the conference command
1005 \newcommand\acmConference[4][]{}%
1006 \gdef\acmConference@shortname{#1}%
1007 \gdef\acmConference@name{#2}%
1008 \gdef\acmConference@date{#3}%
1009 \gdef\acmConference@venue{#4}%
1010 \ifx\acmConference@shortname\empty
1011   \gdef\acmConference@shortname{#2}%
1012 \fi%
1013 \acmConference[Conference'17]{ACM Conference}{July 2017}{Washington,
1014 DC, USA} 


\subtitle The subtitle macro
1015 \def\subtitle#1{\def\@subtitle{#1}}
1016 \subtitle{ }%


\num@authorgroups The total number of “groups”. Each group is several authors with the same affiliations(s)
1017 \newcount\num@authorgroups
1018 \num@authorgroups=0\relax


\if@insideauthorgroup Whether we are continuing an author group @insideauthorgroup insideauthorgroup-true
\else
\fi


\author Adding an author to the list of authors and addresses
1019 \renewcommand\author[2][]{%
1020   \if@insideauthorgroup\else
1021     \global\advance\num@authorgroups by 1\relax
1022     \global\@insideauthorgrouptrue
1023   \fi
1024   \ifx\addresses\empty
1025     \if@ACM@anonymous
1026       \gdef\addresses{\@author{Anonymous Author(s)}}%
1027       \gdef\authors{Anonymous Author(s)}%
1028     \else
1029       \gdef\addresses{\@author{#2}}%
1030       \gdef\authors{#2}%
1031     \fi
1032   \else
1033     \if@ACM@anonymous\else

```

```

1034     \g@addto@macro\addresses{\and\@author{#2}}%
1035     \g@addto@macro\authors{\and#2}%
1036     \fi
1037   \fi
1038 \if@ACM@anonymous
1039   \ifx\shortauthors\empty
1040     \gdef\shortauthors{Anon.}%
1041   \fi
1042 \else
1043   \def\@tempa{#1}%
1044   \ifx\@tempa\empty
1045     \ifx\shortauthors\empty
1046       \gdef\shortauthors{#2}%
1047     \else
1048       \g@addto@macro\shortauthors{\and#2}%
1049     \fi
1050   \else
1051     \ifx\shortauthors\empty
1052       \gdef\shortauthors{#1}%
1053     \else
1054       \g@addto@macro\shortauthors{\and#1}%
1055     \fi
1056   \fi
1057 \fi}

```

\affiliation The macro \affiliation mimics \address from amsart. Note that it has an optional argument, which we use differently from amsart.

```

1058 \newcommand{\affiliation}[2][]{%
1059   \global\@insideauthorgroupfalse
1060   \if@ACM@anonymous\else
1061     \g@addto@macro\addresses{\affiliation{#1}{#2}}%
1062   \fi}

```

@ACM@affiliation@obeypunctuation Whether to use author's punctuation (by default false = add American punctuation)

```

1063 \define@boolkey+{@ACM@affiliation@}{@ACM@affiliation@}{obeypunctuation}%
1064 [true]{\ClassError{@classname}{obeypunctuation must be true or false}}

```

\additionalaffiliation Additional affiliations go to footnotes

```

1065 \def\additionalaffiliation#1{\authornote{\additionalaffiliation{#1}}}

```

@additionalaffiliation Process additionalaffiliation inside \authornote

```

1066 \def\@additionalaffiliation#1{\bgroup
1067   \def\position##1{\ignorespaces}%
1068   \def\institution##1{##1\ignorespaces}%
1069   \def\department{\ifnextchar[{\@department}{\@department[]}}%
1070   \def\@department##1##2{\unskip, ##2\ignorespaces}%
1071   \let\streetaddress\position
1072   \let\city\position
1073   \let\state\position

```

```

1074 \let\postcode\position
1075 \let\country\position
1076 Also with #1\unskip.\egroup}

\email The macro \email mimics \email from amsart. Again it has an optional argument we
do not currently need, but keep for the possible future use.
1077 \renewcommand{\email}[2][]{%
1078   \if@ACM@anonymous\else
1079     \g@addto@macro\addresses{\email{#1}{#2}}%
1080   \fi}

\orcid Right now we do not typeset orcids

\@titlenotes The titlenotes
1081 \def\@titlenotes{}

\titlenote Adding note to the title
1082 \def\titlenote#1{%
1083   \g@addto@macro\@title{\footnotemark}%
1084   \if@ACM@anonymous
1085     \g@addto@macro\@titlenotes{%
1086       \stepcounter{footnote}\footnotetext{Title note}}%
1087   \else
1088     \g@addto@macro\@titlenotes{\stepcounter{footnote}\footnotetext{#1}}%
1089   \fi}

\@subtitlenotes The subtitlenotes
1090 \def\@subtitlenotes{}

\subtitlenote Adding note to the subtitle
1091 \def\subtitlenote#1{%
1092   \g@addto@macro\@subtitle{\footnotemark}%
1093   \if@ACM@anonymous
1094     \g@addto@macro\@subtitlenotes{%
1095       \stepcounter{footnote}\footnotetext{Subtitle note}}%
1096   \else
1097     \g@addto@macro\@subtitlenotes{%
1098       \stepcounter{footnote}\footnotetext{#1}}%
1099   \fi}

\@authornotes The authornotes
1100 \def\@authornotes{}

\authornote Adding note to the author
1101 \def\authornote#1{%
1102   \if@ACM@anonymous\else
1103     \g@addto@macro\addresses{\@authornotemark}%
1104     \g@addto@macro\@authornotes{%
1105       \stepcounter{footnote}\footnotetext{#1}}%
1106   \fi}

```

```

\authornotemark Adding footnotemark to authors
1107 \newcommand\authornotemark[1][\relax]{%
1108   \ifx#1\relax\relax\relax
1109   \g@addto@macro\addresses{\@authornotemark}%
1110   \else
1111   \g@addto@macro\addresses{\@@authornotemark{#1}}%
1112   \fi}

\acmVolume The current volume
1113 \def\acmVolume#1{\def\@acmVolume{#1}}
1114 \acmVolume{1}

\acmNumber The current number
1115 \def\acmNumber#1{\def\@acmNumber{#1}}
1116 \acmNumber{1}

\acmArticle The current article
1117 \def\acmArticle#1{\def\@acmArticle{#1}}
1118 \acmArticle{1}

\acmArticleSeq The sequence number
1119 \def\acmArticleSeq#1{\def\@acmArticleSeq{#1}}
1120 \acmArticleSeq{\@acmArticle}

\acmYear The current year
1121 \def\acmYear#1{\def\@acmYear{#1}}
1122 \acmYear{\the\year}

\acmMonth The current month
1123 \def\acmMonth#1{\def\@acmMonth{#1}}
1124 \acmMonth{\the\month}

\@acmPubDate The publication date
1125 \def\@acmPubDate{\ifcase\@acmMonth\or
1126   January\or February\or March\or April\or May\or June\or
1127   July\or August\or September\or October\or November\or
1128   December\fi^{\@acmYear}}
```

\acmPrice The price

```

1129 \def\acmPrice#1{\def\@acmPrice{#1}}
1130 \acmPrice{15.00}
```

\acmSubmissionID The submission id

```

1131 \def\acmSubmissionID#1{\def\@acmSubmissionID{#1}}
1132 \acmSubmissionID{}
```

\acmISBN The book isbn

```

1133 \def\acmISBN#1{\def\@acmISBN{#1}}
1134 \acmISBN{978-x-xxxx-xxxx-x/YY/MM}
```

```

\acmDOI The paper doi
1135 \def\acmDOI#1{\def\@acmDOI{#1}}
1136 \acmDOI{10.1145/nnnnnnn.nnnnnnn}

\if@ACM@badge Whether to print badge. Note that either left or right badge triggers it:
1137 \newif\if@ACM@badge
1138 \@ACM@badgefalse

\@ACM@badge@width The width of the badge
1139 \newlength\@ACM@badge@width
1140 \setlength\@ACM@badge@width{5pc}

\@ACM@title@width The width of the badge
1141 \newlength\@ACM@title@width

\@ACM@badge@skip The space between the badge and the title
1142 \newlength\@ACM@badge@skip
1143 \setlength\@ACM@badge@skip{1pc}

\acmBadgeR Setting the right badge
1144 \newcommand\acmBadgeR[2][]{\@ACM@badgetrue
1145   \def\@acmBadgeR@url{#1}%
1146   \def\@acmBadgeR@image{#2}%
1147 \def\@acmBadgeR@url{}%
1148 \def\@acmBadgeR@image{}}

\acmBadgeL Setting the left badge
1149 \newcommand\acmBadgeL[2][]{\@ACM@badgetrue
1150   \def\@acmBadgeL@url{#1}%
1151   \def\@acmBadgeL@image{#2}%
1152 \def\@acmBadgeL@url{}%
1153 \def\@acmBadgeL@image{}}

\startPage The start page of the paper
1154 \def\startPage#1{\def\@startPage{#1}}
1155 \startPage{}

\terms Terms are obsolete, we use CCS now.
1156 \def\terms#1{\ClassWarning{\classname}{The command \string\terms{} is
1157   obsolete. I am going to ignore it}{}}

\keywords Keywords are mostly obsolete, we use CCS now. Still it makes sense to keep them for
compatibility.
1158 \def\keywords#1{\def\@keywords{#1}}
1159 \keywords{}

abstract Amsart puts abstract in the box. Since we do not know whether we will use two
column mode, we prefer to save the text
1160 \renewenvironment{abstract}{\Collect@Body\@saveabstract}{}}

```

```

\@saveabstract And saving the abstract
1161 \long\def\@saveabstract#1{\long\gdef\@abstract{#1}}
1162 \@saveabstract{}

\@empty The long version of \@empty (to compare with \@abstract)
1163 \long\def\@empty{}


\if@ACM@printccs Whether to print CCS
1164 \define@boolkey+{@ACM@topmatter@}{@ACM@}{printccs}[true]{%
1165   \if@ACM@printccs
1166     \ClassInfo{@classname}{Printing CCS}%
1167   \else
1168     \ClassInfo{@classname}{Suppressing CCS}%
1169   \fi}{\ClassError{@classname}{printccs must be true or false}}


\if@ACM@printacmref Whether to print ACM bib
1170 \define@boolkey+{@ACM@topmatter@}{@ACM@}{printacmref}[true]{%
1171   \if@ACM@printacmref
1172     \ClassInfo{@classname}{Printing bibformat}%
1173   \else
1174     \ClassInfo{@classname}{Suppressing bibformat}%
1175   \fi}{\ClassError{@classname}{printacmref must be true or false}}


\if@ACM@printfolios Whether to print folios
1176 \define@boolkey+{@ACM@topmatter@}{@ACM@}{printfolios}[true]{%
1177   \if@ACM@printfolios
1178     \ClassInfo{@classname}{Printing folios}%
1179   \else
1180     \ClassInfo{@classname}{Suppressing folios}%
1181   \fi}{\ClassError{@classname}{printfolios must be true or false}}


\@ACM@authorsperrow The number of authors per row. 0 means use default algorithm.
1182 \define@cmdkey{@ACM@topmatter@}{@ACM@}{authorsperrow}[0]{%
1183   \IfInteger{#1}{\ClassInfo{@classname}{Setting authorsperrow to
1184     #1}}{\ClassWarning{@classname}{Parameter authorsperrow must be
1185     numerical. Ignoring the input #1}\gdef\@ACM@authorsperrow{0}}{}}
```

\settopmatter The usual syntactic sugar

```

1186 \def\settopmatter#1{\setkeys{@ACM@topmatter@}{#1}}


Now the settings
1187 \settopmatter{printccs=true, printacmref=true}
1188 \if@ACM@manuscript
1189   \settopmatter{printfolios=true}
1190 \else
1191   \if@ACM@journal
1192     \settopmatter{printfolios=true}
1193 \else
```

```

1194     \settopmatter{printfolios=false}
1195   \fi
1196 \fi
1197 \settopmatter{authorsperrow=0}

\@received The container for the paper history
1198 \def\@received{}


\received The \received command
1199 \newcommand\received[2][]{\def\@tempa{\#1}%
1200   \ifx\@tempa\empty
1201     \ifx\@received\empty
1202       \gdef\@received{Received #2}%
1203     \else
1204       \g@addto@macro{\@received}{; revised #2}%
1205     \fi
1206   \else
1207     \ifx\@received\empty
1208       \gdef\@received{\#1 #2}%
1209     \else
1210       \g@addto@macro{\@received}{; #1 #2}%
1211     \fi
1212   \fi}
1213 \AtEndDocument{%
1214   \ifx\@received\empty\else
1215     \par\bigskip\noindent\small\normalfont\@received\par
1216   \fi}

```

### 3.11 Concepts system

We exclude CCSXML stuff generated by the ACM system:

```

1217 \RequirePackage{comment}
1218 \excludecomment{CCSXML}

```

```

\@concepts This is the storage macro for concepts
1219 \let\@concepts\empty

\ccsdesc The first argument is the significance, the second is the concept(s)
1220 \newcommand\ccsdesc[2][100]{%
1221   \ccsdesc@parse#1^#2^#3^{\relax
1222 \RequirePackage{textcomp}
1223 \def\ccsdesc@parse#1^#2^#3^{\%
1224   \expandafter\ifx\csname CCS@General@\#2\endcsname\relax
1225     \expandafter\gdef\csname CCS@General@\#2\endcsname{\textbullet\
1226       \textbf{#2}}%

```

```

1227      \expandafter\gdef\csname CCS@Punctuation@\#2\endcsname{; }%
1228      \expandafter\gdef\csname CCS@Specific@\#2\endcsname{}%
1229      \g@addto@macro{\@concepts}{\csname CCS@General@\#2\endcsname
1230          \csname CCS@Punctuation@\#2\endcsname
1231          \csname CCS@Specific@\#2\endcsname}%
1232      \fi
1233      \ifx#3\relax\relax\else
1234          \expandafter\gdef\csname CCS@Punctuation@\#2\endcsname{
1235              \textrightarrow\ }%
1236          \expandafter\g@addto@macro\expandafter{\csname CCS@Specific@\#2\endcsname}{%
1237              \ifnum#1>499\textbf{#3}; \else
1238              \ifnum#1>299\textit{#3}; \else
1239              #3; \fi\fi}%
1240      \fi
1241 \ccsdesc@parse@finish}

\ccdesc@parse@finish Gobble everything to \ccsdesc@parse@end
1242 \def\ccsdesc@parse@finish#1\ccsdesc@parse@end{}
```

### 3.12 Copyright system

This is from acmcopyright.sty

\if@printcopyright	A flag whether to print copyright symbol
1243 \newif\if@printcopyright	
1244 \@printcopyrighttrue	
\if@printpermission	Whether to print permission block
1245 \newif\if@printpermission	
1246 \@printpermissiontrue	
\if@acmowned	Whether ACM owns the rights to the paper
1247 \newif\if@acmowned	
1248 \@acmownedtrue	

Keys:

```

1249 \define@choicekey*{ACM@}{acmcopyrightmode}[%
1250   \acm@copyrightinput\acm@copyrightmode]{none,%
1251   acmcopyright,acmlicensed,rightsretained,%
1252   usgov,usgovmixed,cagov,cagovmixed,%
1253   licensedusgovmixed,%
1254   licensedcagov,licensedcagovmixed,othergov,licensedothergov}{%
1255   \@printpermissiontrue
1256   \@printcopyrighttrue
1257   \@acmownedtrue
1258   \ifnum\acm@copyrightmode=0\relax % none
1259   \@printpermissionfalse
1260   \@printcopyrightfalse
1261   \@acmownedfalse}
```

```

1262 \fi
1263 \ifnum\acm@copyrightmode=2\relax % acmlicensed
1264 \@acmownedfalse
1265 \fi
1266 \ifnum\acm@copyrightmode=3\relax % rightsretained
1267 \@acmownedfalse
1268 \acmPrice{}%
1269 \fi
1270 \ifnum\acm@copyrightmode=4\relax % usgov
1271 \@printpermissiontrue
1272 \@printcopyrightfalse
1273 \@acmownedfalse
1274 \acmPrice{}%
1275 \fi
1276 \ifnum\acm@copyrightmode=6\relax % cagov
1277 \@acmownedfalse
1278 \fi
1279 \ifnum\acm@copyrightmode=8\relax % licensedusgovmixed
1280 \@acmownedfalse
1281 \fi
1282 \ifnum\acm@copyrightmode=9\relax % licensedcagov
1283 \@acmownedfalse
1284 \fi
1285 \ifnum\acm@copyrightmode=10\relax % licensedcagovmixed
1286 \@acmownedfalse
1287 \fi
1288 \ifnum\acm@copyrightmode=11\relax % othergov
1289 \@acmownedtrue
1290 \fi
1291 \ifnum\acm@copyrightmode=12\relax % licensedothergov
1292 \@acmownedfalse
1293 \fi}

\setcopyright This is the syntactic sugar around setting keys.
1294 \def\setcopyright{\setkeys{ACM@}{acmcopyrightmode=#1}}
1295 \setcopyright{acmcopyright}

\@copyrightowner Here is the owner of the copyright
1296 \def\@copyrightowner{%
1297 \ifcase\acm@copyrightmode\relax % none
1298 \or % acmcopyright
1299 Association for Computing Machinery.
1300 \or % acmlicensed
1301 Copyright held by the owner/author(s). Publication rights licensed to
1302 Association for Computing Machinery.
1303 \or % rightsretained
1304 Copyright held by the owner/author(s).
1305 \or % usgov
1306 \or % usgovmixed
1307 Association for Computing Machinery.

```

```

1308 \or % cagov
1309 Crown in Right of Canada.
1310 \or %cagovmixed
1311 Association for Computing Machinery.
1312 \or %licensedusgovmixed
1313 Copyright held by the owner/author(s). Publication rights licensed to
1314 Association for Computing Machinery.
1315 \or % licensedcagov
1316 Crown in Right of Canada. Publication rights licensed to
1317 Association for Computing Machinery.
1318 \or %licensedcagovmixed
1319 Copyright held by the owner/author(s). Publication rights licensed to
1320 Association for Computing Machinery.
1321 \or % othergov
1322 Association for Computing Machinery.
1323 \or % licensedothergov
1324 Copyright held by the owner/author(s). Publication rights licensed to
1325 Association for Computing Machinery.
1326 \fi}

@formatdoi Print a clickable doi
1327 \def\@formatdoi#1{\url{https://doi.org/#1} }

@copyrightpermission The canned permission block.
1328 \def\@copyrightpermission{%
1329 \ifcase\acm@copyrightmode\relax % none
1330 \or % acmcopyright
1331 Permission to make digital or hard copies of all or part of this
1332 work for personal or classroom use is granted without fee provided
1333 that copies are not made or distributed for profit or commercial
1334 advantage and that copies bear this notice and the full citation on
1335 the first page. Copyrights for components of this work owned by
1336 others than ACM must be honored. Abstracting with credit is
1337 permitted. To copy otherwise, or republish, to post on servers or to
1338 redistribute to lists, requires prior specific permission
1339 and\hspace*{.5pt}/or a fee. Request permissions from
1340 permissions@acm.org.
1341 \or % acmlicensed
1342 Permission to make digital or hard copies of all or part of this
1343 work for personal or classroom use is granted without fee provided
1344 that copies are not made or distributed for profit or commercial
1345 advantage and that copies bear this notice and the full citation on
1346 the first page. Copyrights for components of this work owned by
1347 others than the author(s) must be honored. Abstracting with credit
1348 is permitted. To copy otherwise, or republish, to post on servers
1349 or to redistribute to lists, requires prior specific permission
1350 and\hspace*{.5pt}/or a fee. Request permissions from
1351 permissions@acm.org.
1352 \or % rightsretained
1353 Permission to make digital or hard copies of part or all of this work

```

1354 for personal or classroom use is granted without fee provided that  
1355 copies are not made or distributed for profit or commercial advantage  
1356 and that copies bear this notice and the full citation on the first  
1357 page. Copyrights for third-party components of this work must be  
1358 honored. For all other uses, contact the  
1359 owner\hspace{.5pt}/author(s).

1360 \or % usgov  
1361 This paper is authored by an employee(s) of the United States  
1362 Government and is in the public domain. Non-exclusive copying or  
1363 redistribution is allowed, provided that the article citation is  
1364 given and the authors and agency are clearly identified as its  
1365 source.

1366 \or % usgovmixed  
1367 ACM acknowledges that this contribution was authored or co-authored  
1368 by an employee, or contractor of the national government. As such,  
1369 the Government retains a nonexclusive, royalty-free right to  
1370 publish or reproduce this article, or to allow others to do so, for  
1371 Government purposes only. Permission to make digital or hard copies  
1372 for personal or classroom use is granted. Copies must bear this  
1373 notice and the full citation on the first page. Copyrights for  
1374 components of this work owned by others than ACM must be  
1375 honored. To copy otherwise, distribute, republish, or post,  
1376 requires prior specific permission and\hspace{.5pt}/or a  
1377 fee. Request permissions from permissions@acm.org.

1378 \or % cagov  
1379 This article was authored by employees of the Government of Canada.  
1380 As such, the Canadian government retains all interest in the  
1381 copyright to this work and grants to ACM a nonexclusive,  
1382 royalty-free right to publish or reproduce this article, or to allow  
1383 others to do so, provided that clear attribution is given both to  
1384 the authors and the Canadian government agency employing them.  
1385 Permission to make digital or hard copies for personal or classroom  
1386 use is granted. Copies must bear this notice and the full citation  
1387 on the first page. Copyrights for components of this work owned by  
1388 others than the Canadian Government must be honored. To copy  
1389 otherwise, distribute, republish, or post, requires prior specific  
1390 permission and\hspace{.5pt}/or a fee. Request permissions from  
1391 permissions@acm.org.

1392 \or % cagovmixed  
1393 ACM acknowledges that this contribution was co-authored by an  
1394 affiliate of the national government of Canada. As such, the Crown  
1395 in Right of Canada retains an equal interest in the copyright.  
1396 Reprints must include clear attribution to ACM and the author's  
1397 government agency affiliation. Permission to make digital or hard  
1398 copies for personal or classroom use is granted. Copies must bear  
1399 this notice and the full citation on the first page. Copyrights for  
1400 components of this work owned by others than ACM must be honored.  
1401 To copy otherwise, distribute, republish, or post, requires prior  
1402 specific permission and\hspace{.5pt}/or a fee. Request permissions  
1403 from permissions@acm.org.

```

1404 \or % licensedusgovmixed
1405 Publication rights licensed to ACM\@. ACM acknowledges that this
1406 contribution was authored or co-authored by an employee, contractor
1407 or affiliate of the United States government. As such, the
1408 Government retains a nonexclusive, royalty-free right to publish or
1409 reproduce this article, or to allow others to do so, for Government
1410 purposes only.
1411 \or % licensedcagov
1412 This article was authored by employees of the Government of Canada.
1413 As such, the Canadian government retains all interest in the
1414 copyright to this work and grants to ACM a nonexclusive,
1415 royalty-free right to publish or reproduce this article, or to allow
1416 others to do so, provided that clear attribution is given both to
1417 the authors and the Canadian government agency employing them.
1418 Permission to make digital or hard copies for personal or classroom
1419 use is granted. Copies must bear this notice and the full citation
1420 on the first page. Copyrights for components of this work owned by
1421 others than the Canadian Government must be honored. To copy
1422 otherwise, distribute, republish, or post, requires prior specific
1423 permission and\hspace*{.5pt}/or a fee. Request permissions from
1424 permissions@acm.org.
1425 \or % licensedcagovmixed
1426 Publication rights licensed to ACM\@. ACM acknowledges that this
1427 contribution was authored or co-authored by an employee, contractor
1428 or affiliate of the national government of Canada. As such, the
1429 Government retains a nonexclusive, royalty-free right to publish or
1430 reproduce this article, or to allow others to do so, for Government
1431 purposes only.
1432 \or % othergov
1433 ACM acknowledges that this contribution was authored or co-authored
1434 by an employee, contractor or affiliate of a national government. As
1435 such, the Government retains a nonexclusive, royalty-free right to
1436 publish or reproduce this article, or to allow others to do so, for
1437 Government purposes only.
1438 \or % licensedothergov
1439 Publication rights licensed to ACM\@. ACM acknowledges that this
1440 contribution was authored or co-authored by an employee, contractor
1441 or affiliate of a national government. As such, the Government
1442 retains a nonexclusive, royalty-free right to publish or reproduce
1443 this article, or to allow others to do so, for Government purposes
1444 only.
1445 \fi}

\copyrightyear By default, the copyright year is the same as \acmYear, but one can override this:
1446 \def\copyrightyear{\def\@copyrightyear{\#1}}
1447 \copyrightyear{\@acmYear}

@\teaserfigures The teaser figures container
1448 \def\@teaserfigures{}

```

```

teaserfigure The teaser figure
1449 \newenvironment{teaserfigure}{\Collect@Body\@saveteaser}{}}

\@saveteaser Saving the teaser
1450 \long\def\@saveteaser#1{\g@addto@macro\@teaserfigures{\@teaser{#1}}}

\thanks We redefine amsart \thanks, so the anonymous key works
1451 \renewcommand{\thanks}[1]{%
1452   \ifnotempty{#1}{%
1453     \if@ACM@anonymous
1454       \g@addto@macro\thankses{\thanks{A note}}%
1455     \else
1456       \g@addto@macro\thankses{\thanks{#1}}%
1457     \fi}%
}

```

### 3.13 Typesetting top matter

\mkttitle@bx Some of our formats use two column design, some use one column one. In all cases we use wide title. Thus we typeset the top matter in a special box to be use in the construction \atwocolumn[<box>].

```
1458 \newbox\mkttitle@bx
```

\maketitle The (in)famous \maketitle. Note that in sigchi-a mode authors are *not* in the title box. Another note: there is a subtle difference between author notes, title notes and thankses. The latter refer to the paper itself, and therefore belong to the copyright/permission block. By the way, this was the default behavior of the old ACM classes.

```

1459 \def\maketitle{%
1460   \if@ACM@anonymous
1461     % Anonymize omission of \author-s
1462     \ifnum\num@authorgroups=0\author{}\fi
1463   \fi
1464   \begingroup
1465   \let\@footnotemark\@footnotemark@nolink
1466   \let\@footnotetext\@footnotetext@nolink
1467   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1468   \global\@topnum\z@ % this prevents floats from falling
1469             % at the top of page 1
1470   \global\@botnum\z@ % we do not want them to be on bottom either
1471   \hsize=\textwidth
1472   \def\@makefnmark{\hbox{\@textsuperscript{\@thefnmark}}}%
1473   \mkttitle\if@ACM@sigchiamode\else\mkauthors\fi\mkteasers
1474   \printtopmatter
1475   \if@ACM@sigchiamode\mkauthors\fi
1476   \setcounter{footnote}{0}%
1477   \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}%
1478   \titlenotes
1479   \subtitlenotes
1480   \authornotes
}

```

```

1481 \let\@makefnmark\relax \let\@thefnmark\relax
1482 \let\@makefntext\noindent
1483 \ifx\@empty\thankses\else
1484   \footnotetextcopyrightpermission{%
1485     \def\par{\let\par\@par}\parindent\z@\@setthanks}%
1486 \fi
1487 \footnotetextcopyrightpermission{%
1488   \if@ACM@authordraft
1489     \raisebox{-2ex}{[\z@][\z@]{\makebox[0pt][l]{\large\bfseries
1490       Unpublished
1491       working draft. Not for distribution}}}%
1492     \color[gray]{0.9}%
1493   \fi
1494   \parindent\z@\parskip0.1\baselineskip
1495   \if@ACM@authorversion\else
1496     \if@printpermission\@copyrightpermission\par\fi
1497   \fi
1498   \if@ACM@manuscript\else
1499     \if@ACM@journal\else % Print the conference information
1500     {\itshape \acmConference@shortname, \acmConference@date, \acmConference@venue}\par
1501   \fi
1502 \fi
1503 \if@printcopyright
1504   \copyright\ \@copyrightyear\ \@copyrightowner\ \
1505 \else
1506   \@copyrightyear.\
1507 \fi
1508 \if@ACM@manuscript
1509   Manuscript submitted to ACM\ \
1510 \else
1511   \if@ACM@authorversion
1512     This is the author's version of the work. It is posted here for
1513     your personal use. Not for redistribution. The definitive Version
1514     of Record was published in
1515     \if@ACM@journal
1516       \emph{\@journalName}%
1517     \else
1518       \emph{Proceedings of \acmConference@name, \acmConference@date}%
1519     \fi
1520     \ifx\@acmDOI\@empty
1521     .
1522     \else
1523       , \@formatdoi{\@acmDOI}.
1524     \fi\ \
1525   \else
1526     \if@ACM@journal
1527       \@permissionCodeOne/\@acmYear/\@acmMonth-ART\@acmArticle
1528       \ifx\@acmPrice\@empty\else\ \$\@acmPrice\fi\
1529       \@formatdoi{\@acmDOI}%
1530   \else % Conference

```

```

1531     ACM~ISBN~\@acmISBN
1532     \ifx\@acmPrice\@empty.\else\@dots\$@\acmPrice\fi\\
1533     \@formatdoi{\@acmDOI}%
1534   \fi
1535   \fi
1536   \fi}
1537 \endgroup
1538 \setcounter{footnote}{0}%
1539 \mkabstract
1540 \if@ACM@printccs
1541   \ifx\@concepts\@empty\else\bgroup
1542     {\@specialsection{CCS Concepts}%
1543      \@concepts\par}\egroup
1544   \fi
1545 \fi
1546 \ifx\@keywords\@empty\else\bgroup
1547   {\if@ACM@journal
1548     \@specialsection{Additional Key Words and Phrases}%
1549   \else
1550     \@specialsection{Keywords}%
1551   \fi
1552     \@keywords\par}\egroup
1553 \fi
1554 \andifyauthors
1555 \andifyshortauthors
1556 \global\let\authors=\authors
1557 \global\let\shortauthors=\shortauthors
1558 \if@ACM@printacmref
1559   \mkbibcitation
1560 \fi
1561 \hypersetup{pdfauthor={\authors},
1562   pdftitle={\@title}, pdfkeywords={\@concepts}}%
1563 \printendtopmatter
1564 \afterindentfalse
1565 \afterheading
1566 }

```

\@specialsection This macro starts section for proceedings and uses small for journals

```

1567 \def\@specialsection#1{%
1568   \ifcase\@ACM@format@nr
1569     \relax % manuscript
1570     \par\medskip\small\noindent#1: %
1571   \or % acmsmall
1572     \par\medskip\small\noindent#1: %
1573   \or % acmlarge
1574     \par\medskip\small\noindent#1: %
1575   \or % acmtog
1576     \par\medskip\small\noindent#1: %
1577   \or % sigconf
1578     \section*{#1}%

```

```

1579 \or % siggraph
1580   \section*{#1}%
1581 \or % sigplan
1582   \paragraph*{#1}%
1583 \or % sigchi
1584   \section*{#1}%
1585 \or % sigchi-a
1586   \section*{#1}%
1587 \fi}

\@printtopmatter The printing of top matter starts the new page, and uses the given title box. Note that for sigchi-a we print badges here rather than in \mkttitle since we want them on the margins.
1588 \def\@printtopmatter{%
1589   \ifx\@startPage\empty
1590     \gdef\@startPage{1}%
1591   \else
1592     \setcounter{page}{\@startPage}%
1593   \fi
1594   \thispagestyle{firstpagestyle}%
1595   \noindent
1596   \ifcase\ACM@format@nr
1597     \relax % manuscript
1598     \box{\mkttitle@bx\par}
1599     \noindent\hrulefill\par
1600   \or % acmsmall
1601     \box{\mkttitle@bx\par}
1602     \noindent\hrulefill\par
1603   \or % acmlarge
1604     \box{\mkttitle@bx\par}
1605     \noindent\hrulefill\par
1606   \or % acmtog
1607     \twocolumn[\box{\mkttitle@bx}]%
1608   \or % sigconf
1609     \twocolumn[\box{\mkttitle@bx}]%
1610   \or % siggraph
1611     \twocolumn[\box{\mkttitle@bx}]%
1612   \or % sigplan
1613     \twocolumn[\box{\mkttitle@bx}]%
1614   \or % sigchi
1615     \twocolumn[\box{\mkttitle@bx}]%
1616   \or % sigchi-a
1617     \par\box{\mkttitle@bx\par}\bigskip
1618   \if@ACM@badge
1619     \marginpar{\noindent
1620       \ifx\@acmBadgeL\image\empty\else
1621         \href{\@acmBadgeL@url}{%
1622           \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}%
1623         \hspace{\@ACM@badge@skip}
1624       \fi

```

```

1625      \ifx\@acmBadgeR@image\empty\else
1626          \href{\@acmBadgeR@url}{%
1627              \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}%
1628      \fi}%
1629  \fi
1630 \fi
1631 }

\@mktitle The title of the article
1632 \def\@mktitle{%
1633   \ifcase\ACM@format@nr
1634     \relax % manuscript
1635     \@mktitle@i
1636   \or % acmsmall
1637     \@mktitle@i
1638   \or % acmlarge
1639     \@mktitle@i
1640   \or % acmtog
1641     \@mktitle@i
1642   \or % sigconf
1643     \@mktitle@iii
1644   \or % siggraph
1645     \@mktitle@iii
1646   \or % sigplan
1647     \@mktitle@iii
1648   \or % sigchi
1649     \@mktitle@iii
1650   \or % sigchi-a
1651     \@mktitle@iv
1652   \fi
1653 }

\@titlefont The font to typeset title
1654 \def\@titlefont{%
1655   \ifcase\ACM@format@nr
1656     \relax % manuscript
1657     \LARGE\bfseries\sffamily
1658   \or % acmsmall
1659     \LARGE\bfseries\sffamily
1660   \or % acmlarge
1661     \LARGE\bfseries\sffamily
1662   \or % acmtog
1663     \Huge\sffamily
1664   \or % sigconf
1665     \Huge\sffamily\bfseries
1666   \or % siggraph
1667     \Huge\sffamily\bfseries
1668   \or % sigplan
1669     \Huge\bfseries
1670   \or % sigchi

```

```

1671      \Huge\sffamily\bfseries
1672  \or % sigchi-a
1673      \Huge\bfseries
1674  \fi}

\@subtitlefont The font to typeset title
1675 \def\@subtitlefont{\normalsize
1676 \ifcase\ACM@format@nr
1677 \relax % manuscript
1678   \mdseries
1679 \or % acmsmall
1680   \mdseries
1681 \or % acmlarge
1682   \mdseries
1683 \or % acmtog
1684   \LARGE
1685 \or % sigconf
1686   \LARGE\mdseries
1687 \or % siggraph
1688   \LARGE\mdseries
1689 \or % sigplan
1690   \LARGE\mdseries
1691 \or % sigchi
1692   \LARGE\mdseries
1693 \or % sigchi-a
1694   \mdseries
1695 \fi}

\@mktitle@i The version of \mktitle for most journals
1696 \def\@mktitle@i{\hsize=\textwidth
1697 \ifACM@title@width=\hsize
1698 \ifx\@acmBadgeL@image\empty\else
1699   \advance\@ACM@title@width by -\@ACM@badge@width
1700   \advance\@ACM@title@width by -\@ACM@badge@skip
1701 \fi
1702 \ifx\@acmBadgeR@image\empty\else
1703   \advance\@ACM@title@width by -\@ACM@badge@width
1704   \advance\@ACM@title@width by -\@ACM@badge@skip
1705 \fi
1706 \setbox\mktitle@bx=\vbox{\noindent\@titlefont
1707   \ifx\@acmBadgeL@image\empty\else
1708     \raisebox{-.5\baselineskip}{[\z@][\z@]{\href{\@acmBadgeL@url}{%
1709       \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}}}%
1710     \hskip\@ACM@badge@skip
1711   \fi
1712   \parbox[t]{\@ACM@title@width}{\raggedright
1713     \@titlefont\noindent
1714     \@title
1715   \ifx\@subtitle\empty\else
1716     \par\noindent{\@subtitlefont\@subtitle}

```

```

1717   \fi}%
1718 \ifx\@acmBadgeR@image\@empty\else
1719   \hskip\@ACM@badge@skip
1720   \raisebox{-.5\baselineskip}{\z@\z@\{\href{\@acmBadgeR@url}{%
1721     \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}\}}%
1722 \fi
1723 \par\bigskip}%

\@mktitle@ii The version of \mktitle for TOG. Since v1.06 is subsumed by the \mktitle@i macro

\@mktitle@iii The version of \mktitle for sigproc. Note that since the title is centered, we leave the
space for the left badge even if only the right badge is defined.

1724 \def\@mktitle@iii{\hsize=\textwidth
1725   \setbox\mktitle@bx=\vbox{\@titlefont\centering
1726     \ACM@title@width=\hsize
1727     \if@ACM@badge
1728       \advance\ACM@title@width by -2\@ACM@badge@width
1729       \advance\ACM@title@width by -2\@ACM@badge@skip
1730       \parbox[b]{\@ACM@badge@width}{\strut
1731         \ifx\@acmBadgeL@image\@empty\else
1732           \raisebox{-.5\baselineskip}{\z@\z@\{\href{\@acmBadgeL@url}{%
1733             \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}\}}%
1734         \fi}%
1735         \hskip\@ACM@badge@skip
1736       \fi
1737       \parbox[t]{\@ACM@title@width}{\centering\@titlefont
1738         \title
1739         \ifx\@subtitle\@empty\else
1740           \par\noindent{\@subtitlefont\@subtitle}
1741         \fi
1742       }%
1743     \if@ACM@badge
1744       \hskip\@ACM@badge@skip
1745       \parbox[b]{\@ACM@badge@width}{\strut
1746         \ifx\@acmBadgeR@image\@empty\else
1747           \raisebox{-.5\baselineskip}{\z@\z@\{\href{\@acmBadgeR@url}{%
1748             \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}\}}%
1749         \fi}%
1750       \fi
1751     \par\bigskip}%

\@mktitle@iv The version of \mktitle for sigchi-a

1752 \def\@mktitle@iv{\hsize=\textwidth
1753   \setbox\mktitle@bx=\vbox{\raggedright\leftskip5pc\@titlefont
1754     \noindent\leavevmode\leaders\hrule height 2pt\hfill\kern0pt\par
1755     \noindent\@title
1756     \ifx\@subtitle\@empty\else
1757       \par\noindent\@subtitlefont\@subtitle
1758     \fi
1759     \par\bigskip}%

```

\@ACM@addtoaddress The macro adds an item to address using the following rules:

1. If we start a paragraph, add the item
2. Otherwise, add a comma and the item
3. However, the comma is deleted, if it is on the end of the line. We use the magic cleaders trick for this.

```

1760 \newbox{@ACM@commabox
1761 \def@ACM@addtoaddress#1{%
1762   \ifvmode\else
1763     \if@ACM@affiliation@obeypunctuation\else
1764       \setbox{@ACM@commabox=\hbox{, }%
1765       \unskip\cleaders\copy{@ACM@commabox\hskip\wd@ACM@commabox
1766     \fi\fi
1767   #1}%

```

\institution Theoretically we can define the macros for \affiliation inside the \@mkauthors-style commands. However, this would lead to a strange error if an author uses them outside \affiliation. Of course we can make them produce an error message, but...

\streetaddress We follow the strange American tradition of no comma before zip code.

```

1768 \def\streetaddress#1{\unskip\ignorespaces}
1769 \def\postcode#1{\unskip\ignorespaces}
1770 \if@ACM@journal
1771   \def\position#1{\unskip\ignorespaces}
1772   \def\institution#1{\#1\ignorespaces}
1773   \def\city#1{\unskip\ignorespaces}
1774   \def\state#1{\unskip\ignorespaces}
1775   \newcommand\department[2][0]{}
1776   \def\country#1{\unskip\ignorespaces}
1777 \else
1778   \def\position#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1779   \def\institution#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1780   \newcommand\department[2][0]{\if@ACM@affiliation@obeypunctuation
1781     #2\else#2\par\fi}%
1782 % \def\streetaddress#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1783 \let\city@ACM@addtoaddress
1784 \let\state@ACM@addtoaddress
1785 % \def\postcode#1{\if@ACM@affiliation@obeypunctuation#1\else\unskip\space#1\fi}%
1786 \let\country@ACM@addtoaddress
1787 \fi

```

\@mkauthors Typesetting authors

```

1788 \def@mkauthors{\begingroup
1789   \hsize=\textwidth
1790   \ifcase@ACM@format@nr
1791     \relax % manuscript
1792     \@mkauthors@i
1793     \or % acmsmall

```

```

1794     \@mkauthors@i
1795     \or % acmlarge
1796     \@mkauthors@i
1797     \or % acmtog
1798     \@mkauthors@i
1799     \or % sigconf
1800     \@mkauthors@iii
1801     \or % siggraph
1802     \@mkauthors@iii
1803     \or % sigplan
1804     \@mkauthors@iii
1805     \or % sigchi
1806     \@mkauthors@iii
1807     \or % sigchi-a
1808     \@mkauthors@iv
1809     \fi
1810     \endgroup
1811 }

\@authorfont Somehow different conferences use different fonts for author names. Why?
1812 \def\@authorfont{\Large\sffamily}

\@affiliationfont Font for affiliations
1813 \def\@affiliationfont{\normalsize\normalfont}

    Adjusting fonts for different formats

1814 \ifcase\ACM@format@nr
1815   \relax % manuscript
1816   \or % acmsmall
1817   \def\@authorfont{\large\sffamily}
1818   \def\@affiliationfont{\small\normalfont}
1819   \or % acmlarge
1820   \or % acmtog
1821   \def\@authorfont{\LARGE\sffamily}
1822   \def\@affiliationfont{\large}
1823   \or % sigconf
1824   \def\@authorfont{\LARGE}
1825   \def\@affiliationfont{\large}
1826   \or % siggraph
1827   \def\@authorfont{\normalsize\normalfont}
1828   \def\@affiliationfont{\normalsize\normalfont}
1829   \or % sigplan
1830   \def\@authorfont{\Large\normalfont}
1831   \def\@affiliationfont{\normalsize\normalfont}
1832   \or % sigchi
1833   \def\@authorfont{\bfseries}
1834   \def\@affiliationfont{\mdseries}
1835   \or % sigchi-a
1836   \def\@authorfont{\bfseries}

```

```

1837 \def\@affiliationfont{\mdseries}
1838 \fi

\@typeset@author@line At this point we have \@currentauthors and \@currentaffiliations. We typeset them in the journal style
1839 \def\@typeset@author@line{%
1840   \andify@\currentauthors\par\noindent
1841   \@currentauthors\def\@currentauthors{}%
1842   \ifx\@currentaffiliations\empty\else
1843     \andify@\currentaffiliations
1844     \unskip, {\@currentaffiliations}\par
1845   \fi
1846   \def\@currentaffiliations{}}

\@mkauthors@i This is version used in most journal formats. Note that \and between authors with the same affiliation becomes _and_:
1847 \def\@mkauthors@i{%
1848   \def\@currentauthors{}%
1849   \def\@currentaffiliations{}%
1850   \global\let\and\@typeset@author@line
1851   \def\@author##1{%
1852     \ifx\@currentauthors\empty
1853       \gdef\@currentauthors{\@authorfont\MakeTextUppercase{##1}}%
1854     \else
1855       \g@addto@macro{\@currentauthors}{\and\MakeTextUppercase{##1}}%
1856     \fi
1857     \gdef\and{}%
1858   \def\email##1##2{}%
1859   \def\affiliation##1##2{%
1860     \def\@tempa{##2}\ifx\@tempa\empty\else
1861       \ifx\@currentaffiliations\empty
1862         \gdef\@currentaffiliations{%
1863           \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1864           \setkeys{@ACM@affiliation@}{##1}%
1865           \@affiliationfont##2}%
1866       \else
1867         \g@addto@macro{\@currentaffiliations}{\and
1868           \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1869           \setkeys{@ACM@affiliation@}{##1##2}}%
1870     \fi
1871   \fi
1872   \global\let\and\@typeset@author@line}%
1873   \global\setbox\mkttitle@bx=\vbox{\noindent\box\mkttitle@bx\par\medskip
1874   \noindent\addresses\@typeset@author@line
1875   \par\medskip}%
1876 }

\@mkauthors@ii \@mkauthors@iI was version used in acmtog. No longer necessary

\author@bx The box to put individual author to

```

```

1877 \newbox\author@bx

\author@bx@wd The width of the author box
1878 \newdimen\author@bx@wd

\author@bx@sep The separation between the author boxes
1879 \newskip\author@bx@sep
1880 \author@bx@sep=1pc\relax

@typeset@author@bx Typesetting the box with authors. Note that in SIGCHI-A the box is not centered.
1881 \def@typeset@author@bx{\bgroup\hsize=\author@bx@wd\def\and{\par}%
1882   \global\setbox\author@bx=\vtop{\if@ACM@sighiamode\else\centering\fi
1883     \authorfont\currentauthors\par\affiliationfont
1884     \currentaffiliation\egroup
1885   \box\author@bx\hskip{\author@bx@sep}%
1886   \gdef\currentauthors{}%
1887   \gdef\currentaffiliation{}}

@mkauthors@iii The sigconf version. Here we use centered design with each author in a separate box.
1888 \def@mkauthors@iii{%
First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width ( $\textwidth - \author@bx@sep)/N - \author@bx@sep$ , where  $N$  is the number of boxes per row.
1889 \author@bx@wd=\textwidth\relax
1890 \advance\author@bx@wd by -\author@bx@sep\relax
1891 \ifnum@ACM@authorsperrow>0\relax
1892   \divide\author@bx@wd by \ACM@authorsperrow\relax
1893 \else
1894   \ifcase\num@authorgroups
1895     \relax % 0?
1896     \or % 1=one author per row
1897     \or % 2=two authors per row
1898       \divide\author@bx@wd by \num@authorgroups\relax
1899     \or % 3=three authors per row
1900       \divide\author@bx@wd by \num@authorgroups\relax
1901     \or % 4=two authors per row (!)
1902       \divide\author@bx@wd by 2\relax
1903     \else % three authors per row
1904       \divide\author@bx@wd by 3\relax
1905   \fi
1906 \fi
1907 \advance\author@bx@wd by -\author@bx@sep\relax

Now, parsing of \addresses:
1908 \gdef\currentauthors{}%
1909 \gdef\currentaffiliation{}%
1910 \def@author##1{\ifx\currentauthors\empty
1911   \gdef\currentauthors{\par##1}%

```

```

1912 \else
1913   \g@addto@macro{@currentauthors{\par##1}%
1914 \fi
1915 \gdef\and{}%
1916 \def\email##1##2{\ifx\@currentaffiliation\empty
1917   \gdef\@currentaffiliation{\nolinkurl{##2}}%
1918 \else
1919   \g@addto@macro{@currentaffiliation{\par\nolinkurl{##2}}%
1920 \fi}%
1921 \def\affiliation##1##2{\ifx\@currentaffiliation\empty
1922   \gdef\@currentaffiliation{%
1923     \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1924     \setkeys{@ACM@affiliation@}{##1}##2}%
1925 \else
1926   \g@addto@macro{@currentaffiliation{\par
1927     \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1928     \setkeys{@ACM@affiliation@}{##1}##2}%
1929 \fi
1930 \global\let\and\@typeset@author@bx
1931 }%

```

Actual typesetting is done by \and macro:

```

1932 \hsize=\textwidth
1933 \global\setbox\mktitle@bx=\vbox{\noindent
1934   \box\mktitle@bx\par\medskip\leavevmode
1935   \lineskip=1pc\relax\centering\hspace*{-1em}%
1936   \addresses\let\and\@typeset@author@bx\and\par\bigskip}}

```

\@mkauthors@iv The sigchia version. Now we put authors in the main text, and no more than 2 authors per line, unless overridden.

```
1937 \def\@mkauthors@iv{%
```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width ( $\textwidth - \author@bx@sep)/N - \author@bx@sep$ , where  $N$  is the number of boxes per row.

```

1938 \author@bx@wd=\columnwidth\relax
1939 \advance\author@bx@wd by -\author@bx@sep\relax
1940 \ifnum\@ACM@authorsperrow>0\relax
1941   \divide\author@bx@wd by \@ACM@authorsperrow\relax
1942 \else
1943   \ifcase\num@authorgroups
1944     \relax % 0?
1945     \or % 1=one author per row
1946     \else % 2=two authors per row
1947       \divide\author@bx@wd by 2\relax
1948   \fi
1949 \fi
1950 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

1951 \gdef\@currentauthors{}%
1952 \gdef\@currentaffiliation{}%
1953 \def\@author##1{\ifx\@currentauthors\@empty
1954   \gdef\@currentauthors{\par##1}%
1955 \else
1956   \g@addto@macro\@currentauthors{\par##1}%
1957 \fi
1958 \gdef\and{}%
1959 \def\email##1##2{\ifx\@currentaffiliation\@empty
1960   \gdef\@currentaffiliation{\nolinkurl{##2}}%
1961 \else
1962   \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
1963 \fi}%
1964 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
1965   \gdef\@currentaffiliation{%
1966     \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1967     \setkeys{@ACM@affiliation@}{##1}##2}%
1968 \else
1969   \g@addto@macro\@currentaffiliation{\par
1970     \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1971     \setkeys{@ACM@affiliation@}{##1}##2}%
1972 \fi
1973 \global\let\and\@typeset@author@bx}%
1974 %

```

Actual typesetting is done by \and macro

```

1975 \bgroup\hsize=\columnwidth
1976 \par\raggedright\leftskip=\z@
1977 \lineskip=1pc\noindent
1978 \addresses\let\and\@typeset@author@bx\and\par\bigskip\egroup}

```

\@authornotemark Adding footnotemark to authors. This version adds “normal” footnotemark.

```
1979 \def\@authornotemark{\g@addto@macro\@currentauthors{\footnotemark\relax}}
```

\@@authornotemark Adding footnotemark to authors with the given number

```
1980 \def\@@authornotemark#1{\g@addto@macro\@currentauthors{\footnotemark[#1]}}
```

\@mkteasers Typesetting teasers

```

1981 \def\@mkteasers{%
1982   \ifx\@teaserfigures\@empty\else
1983     \def\@teaser##1{\par\bigskip\bgroup
1984       \captionsetup{type=figure}##1\egroup\par}
1985     \global\setbox\mkttitle@bx=\vbox{\noindent\box\mkttitle@bx\par
1986       \noindent\@teaserfigures\par\medskip}%
1987   \fi}

```

\@setaddresses This is an amsart macro, which we do not need.

```
1988 \def\@setaddresses{}
```

```

\@mkabstract Typesetting abstract
1989 \def\@mkabstract{\bgroup
1990   \ifx\@abstract\@empty\else
1991     {\phantomsection\addcontentsline{toc}{section}{Abstract}%
1992       \if@ACM@journal
1993         \small\noindent
1994       \else
1995         \section*{Abstract}%
1996       \fi
1997     \ignorespaces\@abstract\par}%
1998   \fi\egroup}

\@mkbibcitation Print bibcitation format
1999 \def\@mkbibcitation{\bgroup
2000   \def\footnotemark{}%
2001   \def\\{\unskip{} \ignorespaces}%
2002   \def\footnote{\ClassError{\@classname}{Please do note use footnotes
2003     inside \string\title{} or \string\author{} command! Use
2004     \string\titlenote{} or \string\authornote{} instead!}}%
2005   \par\medskip\small\noindent\bfseries ACM Reference format:\par\nobreak
2006 \noindent\authors. \acmYear. \title.
2007 \if@ACM@journal
2008   \textit{\journalNameShort}
2009   \acmVolume, \acmNumber, Article\textsuperscript{\acmArticle} (\acmPubDate),
2010   \ref{TotPages}\textsuperscript{pages}.
2011 \else
2012   In \textit{Proceedings of \acmConference@name, \acmConference@venue,
2013   \acmConference@date
2014   \ifx\acmConference@name\acmConference@shortname\else
2015     \acmConference@shortname\fi
2016   ,} \ref{TotPages}\textsuperscript{pages}.
2017 \fi\par
2018 \noindent\formatdoi{\acmDOI}
2019 \par\egroup}

\@printendtopmatter End the top matter
2020 \def\@printendtopmatter{\par\medskip
2021 \ifcase\ACM@format@nr
2022   \relax % manuscript
2023   \noindent\hrulefill\par\medskip
2024   \or % acmsmall
2025   \noindent\hrulefill\par\medskip
2026   \or % acmlarge
2027   \noindent\hrulefill\par\medskip
2028   \or % acmtog
2029   \par\bigskip
2030   \or % sigconf
2031   \par\bigskip
2032   \or % siggraph

```

```

2033   \par\bigskip
2034   \or % sigplan
2035   \par\bigskip
2036   \or % sigchi
2037   \par\bigskip
2038   \or % sigchi-a
2039   \fi
2040 }

\@setthanks We redefine \setthanks using \long
2041 \def\@setthanks{\long\def\thanks{\par\@addpunct.\ }\\thankses}

```

### 3.14 Headers and Footers

We use `fancyhdr` for our headers and footers:

```

2042 \RequirePackage{fancyhdr}

\ACM@linecount@bx This is the box displayed in the review mode
2043 \if@ACM@review
2044   \newsavebox{\ACM@linecount@bx}
2045   \newlength\ACM@linecount@bxht
2046   \newcount\ACM@linecount
2047   \ACM@linecount@ne\relax
2048   \def\ACM@mk@linecount{%
2049     \savebox{\ACM@linecount@bx}[4em][t]{\parbox[t]{4em}{%
2050       \setlength{\ACM@linecount@bxht}{-\baselineskip}%
2051       \loop\color{red}\scriptsize\the\ACM@linecount\loop\global\advance\ACM@linecount by \ne\addtolength{\ACM@linecount@bxht}{\baselineskip}%
2052       \ifdim\ACM@linecount@bxht<\textheight\repeat}}}
2053   \ifdim\ACM@linecount@bxht<\textheight\repeat}}}
2054 \fi
2055 \fi

\ACM@linecountL How to display the box on the left
2056 \def\ACM@linecountL{%
2057   \if@ACM@review
2058   \ACM@mk@linecount
2059   \begin{picture}(0,0)%
2060     \put(-26,-22){\usebox{\ACM@linecount@bx}}%
2061   \end{picture}%
2062 \fi}

\ACM@linecountR How to display the box on the right
2063 \def\ACM@linecountR{%
2064   \if@ACM@review
2065   \ACM@mk@linecount
2066   \begin{picture}(0,0)%
2067     \put(20,-22){\usebox{\ACM@linecount@bx}}%
2068   \end{picture}%
2069 \fi}

```

```

\ACM@timestamp The timestamp system
2070 \if@ACM@timestamp
2071   % Subtracting 30 from \time gives us the effect of rounding-down despite
2072   % \numexpr rounding to nearest
2073   \newcounter{ACM@time@hours}
2074   \setcounter{ACM@time@hours}{\numexpr (\time - 30) / 60 \relax}
2075   \newcounter{ACM@time@minutes}
2076   \setcounter{ACM@time@minutes}{\numexpr \time - \theACM@time@hours * 60 \relax}
2077   \newcommand\ACM@timestamp{%
2078     \footnotesize%
2079     \the\year-\two@digits{\the\month}-\two@digits{\the\day}{ }%
2080     \two@digits{\theACM@time@hours}:\two@digits{\theACM@time@minutes}{ }%
2081     page^\the\page\ (pp. \startPage-\pageref*{TotPages})%
2082     \ifx\acmSubmissionID\empty\relax\else
2083     ~Submission^ID: \acmSubmissionID
2084     \fi
2085   }
2086 \fi

@\shortauthors Even if the author redefined \shortauthors, we do not print them in the anonymous
mode in the headers:
2087 \def\@shortauthors{\if@ACM@anonymous Anon.\else\shortauthors\fi}

@\headfootfont The font to typeset header and footer text.
2088 \def\@headfootfont{%
2089   \ifcase\ACM@format@nr
2090     \relax % manuscript
2091     \sffamily
2092   \or % acmsmall
2093     \sffamily
2094   \or % acmlarge
2095     \sffamily
2096   \or % acmtog
2097     \sffamily
2098   \or % sigconf
2099     \sffamily
2100   \or % siggraph
2101     \sffamily
2102   \or % sigplan
2103     \sffamily
2104   \or % sigchi
2105     \sffamily
2106   \or % sigchi-a
2107     \sffamily
2108   \fi}

```

standardpagestyle The pagestyle for all pages but the first one

```

2109 \fancypagestyle{standardpagestyle}{%
2110   \fancyhf{}%

```

```

2111 \renewcommand{\headrulewidth}{\z@}%
2112 \renewcommand{\footrulewidth}{\z@}%
2113 \ifcase\ACM@format@nr
2114 \relax % manuscript
2115 \fancyhead[LE]{\ACM@linecountL\if@ACM@printfolios\thepage\fi}%
2116 \fancyhead[RO]{\if@ACM@printfolios\thepage\fi}%
2117 \fancyhead[RE]{\@shortauthors}%
2118 \fancyhead[LO]{\ACM@linecountL\shorttitle}%
2119 \fancyfoot[RO,LE]{\footnotesize Manuscript submitted to ACM}%
2120 \or % acmsmall
2121 \fancyhead[LE]{\ACM@linecountL\@headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2122 \fancyhead[RO]{\@headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2123 \fancyhead[RE]{\@headfootfont\@shortauthors}%
2124 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2125 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.}%
2126 \acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2127 \or % acmlarge
2128 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2129 \@acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2130 \fancyhead[LO]{\ACM@linecountL}%
2131 \fancyhead[RO]{\@headfootfont
2132 \shorttitle\quad\textbullet\quad\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2133 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.}%
2134 \acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2135 \or % acmtog
2136 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2137 \@acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2138 \fancyhead[LO]{\ACM@linecountL}%
2139 \fancyhead[RE]{\ACM@linecountR}%
2140 \fancyhead[RO]{\@headfootfont
2141 \shorttitle\quad\textbullet\quad\@acmArticle\if@ACM@printfolios:\thepage\fi\ACM@linecountR}%
2142 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.}%
2143 \acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2144 \else % Proceedings
2145 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2146 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2147 \fancyhead[RE]{\@headfootfont\@shortauthors\ACM@linecountR}%
2148 \fancyhead[LE]{\ACM@linecountL\@headfootfont\acmConference@shortname,
2149 \acmConference@date, \acmConference@venue}%
2150 \fancyhead[RO]{\@headfootfont\acmConference@shortname,
2151 \acmConference@date, \acmConference@venue\ACM@linecountR}%
2152 \fi
2153 \if@ACM@sigchiamode
2154 \fancyheadoffset[L]{\dimexpr(\marginparsep+\marginparwidth)}%
2155 \fi
2156 \if@ACM@timestamp
2157 \fancyfoot[LO,RE]{\ACM@timestamp}%
2158 \fi
2159 }
2160 \pagestyle{standardpagestyle}

```

```

\f@folio@wd Folio blob width, height, offsets and max number
\f@folio@ht 2161 \newdimen\f@folio@wd
\f@folio@voffset 2162 \f@folio@wd=\z@
\f@folio@max 2163 \newdimen\f@folio@ht
2164 \f@folio@ht=\z@
2165 \newdimen\f@folio@voffset
2166 \f@folio@voffset=\z@
2167 \def\f@folio@max{1}
2168 \ifcase\ACM@format@nr
2169 \relax % manuscript
2170 \or % acmsmall
2171 \f@folio@wd=45.75pt\relax
2172 \f@folio@ht=1.25in\relax
2173 \f@folio@voffset=.2in\relax
2174 \def\f@folio@max{8}
2175 \or % acmlarge
2176 \f@folio@wd=43.25pt\relax
2177 \f@folio@ht=79pt\relax
2178 \f@folio@voffset=.55in\relax
2179 \def\f@folio@max{10}
2180 \fi

\f@folioblob The macro to typeset the folio blob.
2181 \def\f@folioblob{\@tempcpta=\@acmArticleSeq\relax
First, we calculate \@acmArticleSeq modulo \@folio@max
2182 \loop
2183   \ifnum@\tempcpta>\@folio@max\relax
2184     \advance@\tempcpta by -\@folio@max
2185   \repeat
2186   \advance@\tempcpta by -1\relax
2187   \tempdima=\@folio@ht\relax
2188   \multiply@\tempdima by \the@\tempcpta\relax
2189   \advance@\tempdima by -\f@folio@voffset\relax
2190   \begin{picture}(0,0)
2191   \makebox[\z@]{\raisebox{-\tempdima}{%
2192     \rlap{%
2193       \raisebox{-0.45\f@folio@ht}{\z@}{\z@}{%
2194         \rule{\f@folio@wd}{\f@folio@ht}}}}%
2195     \parbox{\f@folio@wd}{%
2196       \centering
2197       \textcolor{white}{\LARGE\bfseries\sffamily\@acmArticle}}}}
2198   \end{picture}}
2199

\firstpagestyle The pagestyle for the first page only.
2200 \fancypagestyle\firstpagestyle{%
2201   \fancyhf{}%
2202   \renewcommand{\headrulewidth}{\z@}%

```

```

2203 \renewcommand{\footrulewidth}{\z@}%
2204 \ifcase\ACM@format@nr
2205 \relax % manuscript
2206 \fancyhead[L]{\ACM@linecountL}%
2207 \fancyfoot[RO,LE]{\if@ACM@printfolios\small\thepage\fi}%
2208 \fancyfoot[RE,LO]{\footnotesize Manuscript submitted to ACM}%
2209 \or % acmsmall
2210 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \acmVolume, No.%
2211 \@acmNumber, Article \@acmArticle. Publication date:%
2212 \@acmPubDate.}%
2213 \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2214 \fancyhead[LO]{\ACM@linecountL}%
2215 \fancyhead[RO]{\@folioblob}%
2216 \fancyheadoffset[RO,LE]{0.6\@folio@wd}%
2217 \or % acmlarge
2218 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \acmVolume, No.%
2219 \@acmNumber, Article \@acmArticle. Publication date:%
2220 \@acmPubDate.}%
2221 \fancyhead[RO]{\@folioblob}%
2222 \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2223 \fancyhead[LO]{\ACM@linecountL}%
2224 \fancyheadoffset[RO,LE]{1.4\@folio@wd}%
2225 \or % acmtog
2226 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \acmVolume, No.%
2227 \@acmNumber, Article \@acmArticle. Publication date:%
2228 \@acmPubDate.}%
2229 \fancyhead[L]{\ACM@linecountL}%
2230 \fancyhead[R]{\ACM@linecountR}%
2231 \else % Conference proceedings
2232 \fancyhead[L]{\ACM@linecountL}%
2233 \fancyhead[R]{\ACM@linecountR}%
2234 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2235 \fi
2236 \if@ACM@timestamp
2237 \ifnum\ACM@format@nr=0\relax % Manuscript
2238 \fancyfoot[LO,RE]{\ACM@timestamp\quad}%
2239 \footnotesize Manuscript submitted to ACM}%
2240 \else
2241 \fancyfoot[LO,RE]{\ACM@timestamp}%
2242 \fi
2243 \fi
2244 }

```

### 3.15 Sectioning

Sectioning is different for different levels

```

2245 \renewcommand\section{@startsection{section}{1}{\z@}%
2246 {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2247 {.25\baselineskip}%

```

```

2248  {\@secfont}}
2249 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
2250  {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2251  {.25\baselineskip}%
2252  {\@subsecfont}}
2253 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{10pt}%
2254  {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2255  {-3.5\p@}%
2256  {\@subsubsecfont\@adddotafter}}
2257 \renewcommand\paragraph{\@startsection{paragraph}{4}{\parindent}%
2258  {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2259  {-3.5\p@}%
2260  {\@parfont\@adddotafter}}
2261 \renewcommand\part{\@startsection{part}{9}{\z@}%
2262  {-10\p@ \@plus -4\p@ \@minus -2\p@}%
2263  {4\p@}%
2264  {\@parfont}}

```

\section@raggedright Special version of \raggedright compatible with \MakeUppercase

```

2265 \def\section@raggedright{@rightskip\@flushglue
2266  \rightskip\@rightskip
2267  \leftskip\z@skip
2268  \parindent\z@}

```

\@secfont Fonts for sections etc. are different for different formats.

\@subsecfont

\@subsubsecfont

\@parfont

```

2269 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
2270 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2271 \def\@subsubsecfont{\sffamily\itshape}
2272 \def\@parfont{\itshape}
2273 \setcounter{secnumdepth}{3}
2274 \ifcase\ACM@format@nr
2275 \relax % manuscript
2276 \or % acmsmall
2277 \or % acmlarge
2278 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2279 \def\@subsecfont{\sffamily\large\section@raggedright}
2280 \or % acmtog
2281 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2282 \def\@subsecfont{\sffamily\large\section@raggedright}
2283 \or % sigconf
2284 \def\@secfont{\bfseries\Large\section@raggedright\MakeTextUppercase}
2285 \def\@subsecfont{\bfseries\Large\section@raggedright}
2286 \or % siggraph
2287 \def\@secfont{\bfseries\sffamily\Large\section@raggedright\MakeTextUppercase}
2288 \def\@subsecfont{\bfseries\sffamily\Large\section@raggedright}
2289 \or % sigplan
2290 \def\@secfont{\bfseries\Large\section@raggedright}
2291 \def\@subsecfont{\bfseries\section@raggedright}
2292 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
2293  {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%

```

```

2294   {.25\baselineskip}%
2295   {\@subsubsecfont}%
2296 \def\@subsubsecfont{\bfseries\section@raggedright}%
2297 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
2298   {-5\baselineskip \oplus -2\p@ \minus -.2\p@}%
2299   {-3.5\p@}%
2300   {\@parfont\@addspaceafter}}%
2301 \def\@parfont{\bfseries\itshape}%
2302 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\z@}%
2303   {-5\baselineskip \oplus -2\p@ \minus -.2\p@}%
2304   {-3.5\p@}%
2305   {\@subparfont\@addspaceafter}}%
2306 \def\@subparfont{\itshape}%
2307 \or % sigchi
2308 \setcounter{secnumdepth}{1}%
2309 \def\@secfont{\bfseries\sffamily\section@raggedright\MakeTextUppercase}%
2310 \def\@subsecfont{\bfseries\sffamily\section@raggedright}%
2311 \or % sigchi-a
2312 \setcounter{secnumdepth}{0}%
2313 \def\@secfont{\bfseries\sffamily\section@raggedright\MakeTextUppercase}%
2314 \def\@subsecfont{\bfseries\sffamily\section@raggedright}%
2315 \fi

\@adddotafter Add punctuation after the command
2316 \def\@adddotafter{\#1\@addpunct{.}}%

\@addspaceafter Add space after the command
2317 \def\@addspaceafter{\#1\@addpunct{\enspace}}%

```

### 3.16 TOC Lists

\@dotsep Related to the \tableofcontents are all the horizontal fillers. Base L<sup>A</sup>T<sub>E</sub>X defines \@dottedtocline, which we should not disable. Yet, this command expects \@dotsep to be defined, but leaves this to the class implementation. Since amsart does not provide this, we copy the standard variant from article here.

```
2318 \providecommand*\@dotsep{4.5}
```

### 3.17 Theorems

```

\@acmplainbodyfont The font to typeset the acmplain theorem style body.
2319 \def\@acmplainbodyfont{\itshape}%

\@acmplainindent The amount to indent the acmplain theorem style.
2320 \def\@acmplainindent{\parindent}%

\@acmplainheadfont The font to typeset the acmplain theorem style head.
2321 \def\@acmplainheadfont{\scshape}%

```

```

{@acmplainnotefont The font to typeset the acmplain theorem style note.
2322 \def{@acmplainnotefont}{\emptyset}

    Customization of acmplain theorem style:
2323 \ifcase\ACM@format@nr
2324 \relax % manuscript
2325 \or % acmsmall
2326 \or % acmlarge
2327 \or % acmtog
2328 \or % sigconf
2329 \or % siggraph
2330 \or % sigplan
2331   \def{@acmplainbodyfont}{\itshape}
2332   \def{@acmplainindent}{\z@}
2333   \def{@acmplainheadfont}{\bfseries}
2334   \def{@acmplainnotefont}{\normalfont}
2335 \or % sigchi
2336 \or % sigchi-a
2337 \fi

acmplain The acmplain theorem style
2338 \newtheoremstyle{acmplain}%
2339   {.5\baselineskip\plus.2\baselineskip%
2340   \minus.2\baselineskip}%
2341   {.5\baselineskip\plus.2\baselineskip%
2342   \minus.2\baselineskip}%
2343   {\@acmplainbodyfont}%
2344   {\@acmplainindent}%
2345   {\@acmplainheadfont}%
2346   {.}%
2347   {.5em}%
2348   {\thmname{\#1}\thmnumber{\#2}\thmnote{\{@acmplainnotefont(\#3)}}}%

```

{@acmdefinitionbodyfont The font to typeset the acmdefinition theorem style body.
2349 \def{@acmdefinitionbodyfont}{\normalfont}

{@acmdefinitionindent The amount to indent the acmdefinition theorem style.
2350 \def{@acmdefinitionindent}{\parindent}

{@acmdefinitionheadfont The font to typeset the acmdefinition theorem style head.
2351 \def{@acmdefinitionheadfont}{\itshape}

{@acmdefinitionnotefont The font to typeset the acmdefinition theorem style note.
2352 \def{@acmdefinitionnotefont}{\emptyset}

 Customization of acmdefinition theorem style:
2353 \ifcase\ACM@format@nr
2354 \relax % manuscript

```

2355 \or % acmsmall
2356 \or % acmlarge
2357 \or % acmtog
2358 \or % sigconf
2359 \or % siggraph
2360 \or % sigplan
2361 \def\@acmdefinitionbodyfont{\normalfont}
2362 \def\@acmdefinitionindent{\z@}
2363 \def\@acmdefinitionheadfont{\bfseries}
2364 \def\@acmdefinitionnotefont{\normalfont}
2365 \or % sigchi
2366 \or % sigchi-a
2367 \fi

```

`acmdefinition` The `acmdefinition` theorem style

```

2368 \newtheoremstyle{acmdefinition}%
2369   {.5\baselineskip\plus.2\baselineskip%
2370   \minus.2\baselineskip}%
2371   {.5\baselineskip\plus.2\baselineskip%
2372   \minus.2\baselineskip}%
2373   {\@acmdefinitionbodyfont}%
2374   {\@acmdefinitionindent}%
2375   {\@acmdefinitionheadfont}%
2376   {.}%
2377   {.5em}%
2378   {\thmname{\#1}\thmnumber{\ #2}\thmnote{ {\@acmdefinitionnotefont(\#3)}}}%

```

The definitions for theorems:

```

2379 \theoremstyle{acmplain}
2380 \newtheorem{theorem}{Theorem}[section]
2381 \newtheorem{conjecture}{theorem}{Conjecture}
2382 \newtheorem{proposition}{theorem}{Proposition}
2383 \newtheorem{lemma}{theorem}{Lemma}
2384 \newtheorem{corollary}{theorem}{Corollary}
2385 \theoremstyle{acmdefinition}
2386 \newtheorem{example}{theorem}{Example}
2387 \newtheorem{definition}{theorem}{Definition}
2388 \theoremstyle{acmplain}

```

`\@proofnamefont` The font to typeset the proof name.

```
2389 \def\@proofnamefont{\scshape}
```

`\@proofindent` Whether or not to indent proofs.

```
2390 \def\@proofindent{\indent}
```

Customization of proof environment.

```

2391 \ifcase\ACM@format@nr
2392 \relax % manuscript
2393 \or % acmsmall

```

```

2394 \or % acmlarge
2395 \or % acmtog
2396 \or % sigconf
2397 \or % siggraph
2398 \or % sigplan
2399   \def\@proofnamefont{\itshape}
2400   \def\@proofindent{\noindent}
2401 \or % sigchi
2402 \or % sigchi-a
2403 \fi

proof We want some customization of proof environment.
2404 \renewenvironment{proof}[1][\proofname]{\par
2405   \pushQED{\qed}%
2406   \normalfont \topsep6\p@\@plus6\p@\relax
2407   \trivlist
2408   \item[\@proofindent\hspace{\labelsep}\@proofnamefont #1\@addpunct{.}]\ignorespaces
2409 }{%
2410   \popQED\endtrivlist\@endpfalse
2411 }
2412 }

```

### 3.18 Acknowledgments

```

\acks This is a comment-like structure
2413 \specialcomment{acks}{%
2414   \begingroup
2415   \section*{Acknowledgments}
2416   \phantomsection\addcontentsline{toc}{section}{Acknowledgments}
2417 }{%
2418   \endgroup
2419 }

\grantsponsor We just typeset the name of the sponsor
2420 \def\grantsponsor#1#2#3{#2}

\grantnum
2421 \newcommand\grantnum[3][]{\#3%
2422   \def\@tempa{\#1}\ifx\@tempa\@empty\else\space(\url{\#1})\fi}

```

### 3.19 Conditional typesetting

We use the `comment` package for conditional typesetting:

```

2423 \if@ACM@screen
2424   \includecomment{screenonly}
2425   \excludecomment{printonly}
2426 \else
2427   \excludecomment{screenonly}

```

```

2428 \includecomment{printonly}
2429 \fi
2430 \if@ACM@anonymous
2431 \excludecomment{anonsuppress}
2432 \excludecomment{acks}
2433 \else
2434 \includecomment{anonsuppress}
2435 \fi

```

### 3.20 Additional bibliography commands

\showeprint The command \showeprint has two arguments: the (optional) prefix and the eprint number. Right now the only prefix we understand is the (lowercase) word ‘arxiv’ (see <http://arxiv.org/hyperref/bibstyles/>).

```

2436 \newcommand\showeprint[2][arxiv]{%
2437   \def\@tempa{\#1}%
2438   \ifx\@tempa\empty\def\@tempa{arxiv}\fi
2439   \def\@tempb{arxiv}%
2440   \ifx\@tempa\@tempb
2441     arXiv:\href{http://arxiv.org/abs/#2}{#2}\else arXiv:#2%
2442   \fi}

```

### 3.21 End of Class

```

2443 \normalsize\normalfont\frenchspacing
2444 \end{class}

```

## References

- [1] UK TeX Users Group. UK list of TeX frequently asked questions. <http://www.tex.ac.uk>, 2016.
- [2] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://www.ctan.org/pkg/amslatex>.
- [3] Cristophe Fiorio. *algorithm2e.sty—package for algorithms*, October 2015. <http://www.ctan.org/pkg/algorithm2e>.
- [4] Rogério Brito. *The algorithms bundle*, August 2009. <http://www.ctan.org/pkg/algorithms>.
- [5] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*, June 2015. <http://www.ctan.org/pkg/listings>.
- [6] Simon Fear. *Publication quality tables in L<sup>A</sup>T<sub>E</sub>X*, April 2005. <http://www.ctan.org/pkg/booktabs>.
- [7] Association for Computing Machinery. *ACM Visual Identity Standards*, 2007. <http://identitystandards.acm.org>.
- [8] Axel Sommerfeldt. *The subcaption package*, April 2013. <http://www.ctan.org/pkg/subcaption>.
- [9] Boris Veytsman, Bern Schandl, Lee Netherton, and C. V. Radhakrishnan. *A package to create a nomenclature*, September 2005. <http://www.ctan.org/pkg/nomenc>.
- [10] Nicola L. C. Talbot. *User Manual for glossaries.sty v4.25*, June 2016. <http://www.ctan.org/pkg/subcaption>.
- [11] David Carlisle. *The textcase package*, October 2004. <http://www.ctan.org/pkg/textcase>.

# Change History

v1.00		v1.05	
General: First released version . . . . .	27	General: Added processing doi numbers for acmsiggraph and doi numbers for sigproc.bib . . . . .	27
v1.01		Patched \setcitestyle command; closes <a href="https://github.com/borisveytsman/acmart/issues/19">https://github.com/borisveytsman/acmart/issues/19</a> . . . . .	27
General: Changed hyperref colors in screen mode (closes <a href="https://github.com/borisveytsman/acmart/issues/1">https://github.com/borisveytsman/acmart/issues/1</a> ) . . . . .	27	Defined ACM colors . . . . .	27
Explicitly put draft option (closes <a href="https://github.com/borisveytsman/acmart/issues/4">https://github.com/borisveytsman/acmart/issues/4</a> ) . . . . .	30	Set headheight to 1pc for all formats (closes <a href="https://github.com/borisveytsman/acmart/issues/5">https://github.com/borisveytsman/acmart/issues/5</a> ) . . . . .	27
v1.02		v1.06	
General: Added TOPS and TSC (closes <a href="https://github.com/borisveytsman/acmart/issues/12">https://github.com/borisveytsman/acmart/issues/12</a> ) . . . . .	27	\@ACM@badge@skip: Added macro . . . . .	55
Documentation changes (closes <a href="https://github.com/borisveytsman/acmart/issues/13">https://github.com/borisveytsman/acmart/issues/13</a> ) . . . . .	27	\@ACM@badge@width: Added macro . . . . .	55
v1.03		\@ACM@title@width: Added macro . . . . .	55
\@formatdoi: Added macro . . . . .	60	\@mkttitle@i: Added processing badges . . . . .	68
\if@ACM@authorversion: Added macro . . . . .	28	Made generic . . . . .	68
\maketitle: Added special case of authorversion . . . . .	63	\@mkttitle@ii: Now this macro is obsolete . . . . .	69
General: Added anonsuppress environment . . . . .	27	\@mkttitle@iii: Added processing badges . . . . .	69
Added authorversion option (closes <a href="https://github.com/borisveytsman/acmart/issues/9">https://github.com/borisveytsman/acmart/issues/9</a> ) . . . . .	27	Made more generic . . . . .	69
v1.04		\@mkttitle@iv: Made more generic . . . . .	69
\acmArticleSeq: Name change by Matthew Fluet . . . . .	54	\@printtopmatter: Added processing badges . . . . .	66
\acmDOI: Name change by Matthew Fluet . . . . .	55	\@subtitlefont: Added macro . . . . .	68
\acmISBN: Name change by Matthew Fluet . . . . .	54	\@titlefont: Added macro . . . . .	67
General: Updated bibliography for siggraph . . . . .	27	\acmBadgeL: Added macro . . . . .	55
		\acmBadgeR: Added macro . . . . .	55
		\if@ACM@badge: Added macro . . . . .	55
v1.07		v1.07	
		\maketitle: Corrected a bug with abstract footnotes . . . . .	63
		Corrected a bug with permssion and footnotes order . . . . .	63
v1.08		v1.08	
		General: SIGPLAN reformatting by Matthew Fluet . . . . .	27
		Typos corrected (Tobias Pape) . . . . .	27
v1.09		v1.09	
		General: Revert SIGPLAN caption rules . . . . .	27
v1.10		v1.10	
		\maketitle: Corrected a bug with doi in manuscript and author vertson, <a href="https://github.com/borisveytsman/acmart/issues/36">https://github.com/borisveytsman/acmart/issues/36</a> . . . . .	63

General: Changes of ‘licensedothergov’ wording . . . . .	58	v1.14
standardpagestyle: Reversed folios location . . . . .	78	\bibstyle@acmauthoryear: Moved def of \bibstyle@acmauthoryear before use . . . . .
v1.11		33
General: Customization of ACM theorem styles and proof environment by Matthew Fluet . . . . .	27	\bibstyle@acmnumeric: Moved def of \bibstyle@numeric before use . . . . .
v1.12		33
\@marginfigure: Now centering by default . . . . .	43	General: \citetitle updates (Matthew Fluet) . . . . .
\@marginintable: Now centering by default . . . . .	43	Patched \citetitle . . . . .
\@parfont: Moved to \section@raggedright . . . . .	82	v1.15
\copyrightpermissionfootnoterule: Added macro . . . . .	40	\@ACM@addtoaddress: Added macro
\descriptionlabel: Redefined . . . . .	45	\@mkauthors@iii: New authors system . . . . .
\footnoterule: Made shorter . . . . .	40	\@shortauthors: Introduced macro .
\if@ACM@natbib@override: Added macro . . . . .	28	\@typeset@author@bx: Moved to separate macro . . . . .
\if@ACM@newfonts: Added macro . . .	41	\acks: Added macro . . . . .
\maketitle: Moved thankses to copyrightpermission box . . . . .	63	\affiliation: Added code for author groups . . . . .
\section@raggedright: Introduced macro . . . . .	82	\author: Added code for author groups . . . . .
General: Added graceful behavior when libertine fonts are absent . . . . .	41	\city: Added macro . . . . .
Documentation updates . . . . .	27	\country: Added macro . . . . .
v1.13		\department: Added macro . . . . .
\@mpfootnotetext: Made minipage footnotes centered . . . . .	41	\grantnum: Added macro . . . . .
\bibliographystyle: Redefined macro . . . . .	37	\grantsponsor: Added macro . . . . .
\bibstyle@acmauthoryear: Added macro . . . . .	33	\if@insideauthorgroup: Introduced macro . . . . .
\bibstyle@acmnumeric: Added macro . . . . .	33	\institution: Added macro . . . . .
\if@ACM@printfolios: Added macro	56	\num@authorgroups: Renamed . . . . .
General: Font adjustments for acmsmall . . . . .	71	\orcid: Introduced macro . . . . .
Increased font size for ACM Large Print bibliographic information by default for the proceedings . . . . .	31	\position: Added macro . . . . .
standardpagestyle: Added headers for sigs . . . . .	78	\postcode: Added macro . . . . .
Expanded headers for sigchi-a . . . . .	78	\state: Added macro . . . . .
Suppressed folios if sig . . . . .	78	\streetaddress: Added macro . . . . .
v1.16		standardpagestyle: Better handling of anonymous mode . . . . .
\@headfootfont: Added macro . . . . .	78	v1.17
General: Formatting header/footer (Matthew Fluet) . . . . .	27	\makefnmark: Redefined . . . . .
standardpagestyle: Customize header/footer text font . . . . .	78	\mkauthors: TOG now uses the same authors block as other journals . . . . .
v1.17		70
\@mkauthors@ii: Deleted . . . . .	72	\mkbibcitation: Added \nobreak Changed format for sigs . . . . .
\mkbibcitation: Added \nobreak Changed format for sigs . . . . .	76	76

\acmArticle: The default is now numerical	54	v1.25	General: Updated PACMPL	45
\acmMonth: The default must be numerical. Closes #50.	54	v1.26	General: Corrected \shortcite bug	27
\acmNumber: The default is now numerical	54		Documentation typos fixed (thanks to Stephen Spencer)	27
\acmVolume: The default is now numerical	54	v1.27	\if@ACM@printccs: Typo corrected	56
\acmYear: The default is now numerical	54	v1.28	\ccsdesc@parse: Change from \to to \textrightarrow (Matteo Riondato)	57
\description: Decreased indent	45		General: Corrected option natbib behavior	33
\grantnum: Added url	86		Got rid of warnings in pdf keywords	36
\grantsponsor: Renamed	86	v1.29	\mkabstract: Removed spurious indentation (John Wickerson)	76
\if@ACM@printacmref: Renamed from \if@ACM@printbib	56		\ccsdesc@parse: Add spacing after bullet and around rightarrow; semicolon separators no longer in bold/italic (John Wickerson)	57
General: Slightly decreased margins for sigs	38		General: Increased head to 13pt	38
standardpagestyle: Added paper title to sigs	78		standardpagestyle: Corrected printfolios (Matthew Fluet)	78
v1.18		v1.30	\department: Added optional parameter	70
\@mkauthors@i: Now we andify affiliations	72		General: Added \frenchspacing	87
\@typeset@author@line: Added macro	72		Bibtex style now recognizes https:// in doi	27
General: Natbib is now the default for all formats	27		Switched to T1: looks like libertine has problems with \l in OT1	42
v1.19			Updated IMWUT and PACMPL	45
\@mkabstract: Include 'Abstract' in PDF bookmarks (Matthew Fluet)	76	v1.31	\@additionalaffiliation: Added macro	52
\acks: Include 'Acknowledgements' in PDF bookmarks (Matthew Fluet)	86		\@mkbibcitation: Disabled linebreak	76
General: Include 'Abstract', 'Acknowledgements', and 'References' in PDF bookmarks (Matthew Fluet)	27		\@startsection: Added \tochangemeasure	33
Include 'References' in PDF bookmarks (Matthew Fluet)	31		Redefined macro	35
v1.20			\@textbottom: Redefined	41
\@mkabstract: Deleted spurious space	76		\acmMonth: The default now is the current month (Matteo Riondato)	54
General: Bug fixes for bst	27		\acmYear: The default now is the current year (Matteo Riondato)	54
v1.21			\additionalaffiliation: Added macro	52
\showeprint: Added macro	87		\l@subsection: Redefined macro	36
v1.22			\l@subsubsection: Redefined macro	36
General: More bibliography changes for Aptara	27			
v1.23				
General: Add PACMPL journal option	27			
v1.24				
General: Add IMWUT journal option	45			

General: Documentation changes . . . . .	27
v1.32	
\@formatdoi: New doi format . . . . .	60
General: Added POMACS journal	
option . . . . .	27
Format siggraph is now obsolete . . . . .	27
v1.33	
\@ACM@addtoaddress: Added	
obeypunctuation code . . . . .	70
\@mkauthors@i: Added	
obeypunctuation code . . . . .	72
\@mkauthors@iii: Added	
obeypunctuation code . . . . .	73
\@mkauthors@iv: Added	
obeypunctuation code . . . . .	74
\@subtitlefont: Added	
\normalsize . . . . .	68
\ACM@linecountL: Renamed macro . . . . .	77
\ACM@linecountR: Added macro . . . . .	77
\ACM@timestamp: Added current page	
number . . . . .	78
Added macro (Michael D. Adams) . . . . .	78
Added submission id . . . . .	78
\acmSubmissionID: Added macro . . . . .	54
\city: Added obeypunctuation code . . . . .	70
\country: Added obeypunctuation	
code . . . . .	70
\department: Added obeypunctuation	
code . . . . .	70
\if@ACM@affiliation@obeypunctuation:	
Added macro . . . . .	52
\if@ACM@authordraft: Added macro . . . . .	29
\if@ACM@natbib@override: Deleted	
macro . . . . .	28
\if@ACM@timestamp: Added macro	
(Michael D. Adams) . . . . .	29
\institution: Added	
obeypunctuation code . . . . .	70
\maketitle: Fixed the bug with	
figures on top and bottom of the	
title page, thanks to David Epstein	63
\position: Added obeypunctuation	
code . . . . .	70
\postcode: Added obeypunctuation	
code . . . . .	70
\state: Added obeypunctuation code . . . . .	70
\streetaddress: Added	
obeypunctuation code . . . . .	70
General: Added acmart-preload-hook . . . . .	27
Added cmap and glyptounicode . . . . .	41
BibTeX comma before articleno bug	
corrected . . . . .	27
BibTeX crossref bug corrected . . . . .	27
BibTeX numpages bug corrected . . . . .	27
Documentation updates . . . . .	27
Moved \citemname definition for	
non-natbib bibliography, so a	
package may redefine it . . . . .	37
Switched to Type 1 fonts for	
libertine even if OTF-capable	
engine is used (Kai Mindermann) . . . . .	42
\firstpagestyle: Added right	
linecount for two column formats . . . . .	80
Added timestamp (Michael	
D. Adams) . . . . .	80
\standardpagestyle: Added right	
linecount for two column formats . . . . .	78
Added timestamp (Michael	
D. Adams) . . . . .	78
v1.34	
\@mkbibcitation: Deleted DOI from	
doi numbers . . . . .	76
\ACM@linecount@bx: Rulers now are	
continuous . . . . .	77
\ACM@linecountL: Rulers now are	
continuous . . . . .	77
\ACM@linecountR: Rulers now are	
continuous . . . . .	77
\maketitle: Added date to the	
bibstrip in conf proceedings . . . . .	63
Deleted ‘DOI’ from doi numbers . . . . .	63
Rearranged bibstrip . . . . .	63
The \terms command is now	
obsolete . . . . .	63
\terms: The \terms command now	
just produces a warning . . . . .	55
v1.35	
\bibstyle@acmauthoryear: Square	
brackets for author-year style . . . . .	33
General: BibTeX bug fixed: et al. . . . .	27
If the copyright is set to usgov or	
rightsretained, the price is	
suppressed . . . . .	58
v1.36	
\@ACM@authorsperrow: Added macro . . . . .	56
\@mkauthors@iii: Added	
authorsperrow override . . . . .	73
\@mkauthors@iv: Added	
authorsperrow override . . . . .	74

\if@ACM@authordraft: Corrected	
typo, thanks to bargteil . . . . .	29
General: Added PACMHCI journal	
options . . . . .	45
Added the possibility to adjust	
number of author boxes per row	
in conference formats . . . . .	27
v1.37	
\description: Reduce list	
indentation (Matthew Fluet) . . . . .	45
\descriptionlabel: Reduce list	
indentation (Matthew Fluet) . . . . .	45
\normalparindent: Set	
\normalparindent (Matthew	
Fluet) . . . . .	39
General: Reduce list indentation	
(Matthew Fluet) . . . . .	44
Set \normalparindent; Reduce list	
indentation (Matthew Fluet) . . . . .	27
v1.38	
General: Increase default font size for	
SIGPLAN . . . . .	27, 31
v1.39	
\@authornotemark: Added macro .	75
\authornotemark: Added macro . .	54
v1.40	
\copyrightowner: Added new	
copyright version: licensedcagov .	59
\copyrightpermission: Added new	
copyright version: licensedcagov .	60
\@mkauthors@i: Switched to	
MakeTextUppercase . . . . .	72
\@parfont: Switched to	
MakeTextUppercase . . . . .	82
\ACM@linecount@bx: Work around a	
bug in xcolor: looks like cmyk	
colors in boxes do not work . . . . .	77
\ccdesc@parse@finish: Added	
macro . . . . .	58
\city: We now do not print this even	
in SIG . . . . .	70
\country: Fixed bugs with extra	
spaces . . . . .	70
\l@subsection: Redefined macro . .	36
\postcode: We now do not print this	
even in SIG . . . . .	70
\state: We now do not print this even	
in SIG . . . . .	70
\streetaddress: We now do not	
print this even in SIG . . . . .	70
General: Added ‘textcase’ package . .	31
Added heightrounded to geometry	
Added new copyright version:	
licensedcagov . . . . .	27
Added package cleveref . . . . .	27
Added Ross Moore code for	
glyptounicode . . . . .	41
Bibliography changes . . . . .	27
v1.41	
General: Added new badges . . . . .	27

# Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\\$ . . . . .	1528, 1532	1703, 1704, 1712, 1726, 1728, 1729, 1737
\@ . . . . .	1405, 1426, 1439	\@DeclareACMFormat . ... 38, 39, 40, 41, 42, 43, 44, 45, 46, 47
\@eauthornotemark . . . . .	1111, 1980	\@acmdefinitionbodyfont ... 2349, 2361, 2373
\@eepar . . . . .	306, 363	\@acmdefinitionheadfont ... 2351, 2363, 2375
\@ACM@addtoaddress . . . . .	1760, 1783, 1784, 1786	\@acmdefinitionindent ... 2350, 2362, 2374
\@ACM@authorsperrow . . . . .	1182, 1891, 1892, 1940, 1941	\@acmdefinitionnotefont ... 2352, 2364, 2378
\@ACM@badge@skip . . . . .	1142, 1623, 1700, 1704, 1710, 1719, 1729, 1735, 1744	\@acmownedfalse . . . . . ... 1261, 1264, 1267, 1273, 1277, 1280, 1283, 1286, 1292
\@ACM@badge@width . . . . .	1139, 1622, 1627, 1699, 1703, 1709, 1721, 1728, 1730, 1733, 1745, 1748	\@acmownedtrue . . . . . ... 1248, 1257, 1289
\@ACM@badgefalse . . . . .	1138	\@acmplainbodyfont . ... 2319, 2331, 2343
\@ACM@badgetrue . . . . .	1144, 1149	\@acmplainheadfont . ... 2321, 2333, 2345
\@ACM@commabox . . . . .	1760, 1764, 1765	\@acmplainindent . . . . . ... 2320, 2332, 2344
\@ACM@journalfalse . . . . .	140, 142, 144, 146, 148	\@acmplainnotefont . ... 2322, 2334, 2348
\@ACM@journaltrue . . . . .	132, 134, 136, 138	\@adddotafter . . . . . ... 2256, 2260, 2316
\@ACM@labelwidth . . . . .	695, 698, 706, 711, 737	\@additionalaffiliation ..... 1065, 1066
\@ACM@manuscriptfalse . . . . .	127	\@addpunct . . . . . 2041, 2316, 2317, 2409
\@ACM@manuscripttrue . . . . .	125	\@addspaceafter . . . . . ... 2300, 2305, 2317
\@ACM@newfontsfalse . . . . .	604, 606, 609	\@affiliationfont . . . . .
\@ACM@newfontstrue . . . . .	601	1813, 1818, 1822, 1825, 1828, 1831, 1834, 1837, 1865, 1883
\@ACM@reviewtrue . . . . .	101	\@afterheading . 337, 1565
\@ACM@sigchiamodefalso . . . . .	129	\@afterindentfalse . . . . . ... 283, 1564
\@ACM@sigchiamodettrue . . . . .	149	\@afterindenttrue . . . . . 281
\@ACM@timestamptrue . . . . .	100	\@author . . . . . 1026, 1029, 1034, 1851, 1910, 1953
\@ACM@title@width . . . . .	1141, 1697, 1699, 1700,	\@acmVolume . . . . . 1113, 2009, 2125, 2133, 2142, 2210, 2218, 2226

\@authorfont . . . . .	1913, 1951, 1953, 1812, 1817, 1821, 1824, 1827, 1830, 1833, 1836, 1853, 1883	\@currentlabel . 564, 578	\@gobble . . . . . 213, 257
\@authornotemark . . . . .	1103, 1109, <u>1979</u>	\@dblfloat . . . . . 660	\@hangfrom . . . . . 305, 362
\@authornotes . . . . .	1100, 1104, 1480	\@dotsep . . . . . 2318	\@headfootfont . . . . . 2088, 2121, 2122, 2123, 2124, 2128, 2131, 2136, 2140, 2146, 2147, 2148, 2150
\@auxout . . . . .	442	\@empty . . . . . 151, 296, 1010, 1024, 1039, 1044, 1045, 1051, 1200, 1201, 1207, 1214, 1219, 1483, 1520, 1528, 1532, 1541, 1546, 1589, 1620, 1625, 1698, 1702, 1707, 1715, 1718, 1731, 1739, 1746, 1756, 1842, 1852, 1860, 1861, 1910, 1916, 1921, 1953, 1959, 1964, 1982, 2082, 2322, 2352, 2422, 2438	\@ifnextchar . . . . . 1069 \@ifnotempty . . . . . 1452 \@ifnum . . . . . 229, 231 \@ifstar . . . . . 290 \@iiparbox . . . . . 558 \@input . . . . . 374 \@insideauthorgroupfalse ..... 1059 \@insideauthorgrouptrue ..... 1022
\@begindocumenthook	438	\@endfloatbox . . . . . 662	\@journalCode . . . . . 743, 995
\@botnum . . . . .	1470	\@endprefalse . . . . . 2411	\@journalCode@nr . . . . . 743, 796, 1000
\@citestyle . . . . .	215	\@endwidedefloatbox . . . . . 662, 670	\@journalName . . . . . 798, 802, 806, 811, 815, 819, 823, 827,
\@classname . . . . . 25, 27, 35, 51, 53, 54, 59, 61, 62, 67, 69, 70, 75, 77, 78, 83, 85, 86, 91, 93, 94, 99, 103, 104, 115, 120, 173, 602, 605, 607, 995, 997, 1064, 1156, 1166, 1168, 1169, 1172, 1174, 1175, 1178, 1180, 1181, 1183, 1184, 2002	\@finalstrut . . . . . 569, 582 \@float . . . . . 664 \@flushglue . . . . . 2265 \@fnsymbol . . . . . 1467 \@folio@ht . . . . . 2161, 2187, 2193, 2194 \@folio@max . . . . . 2161, 2183, 2184 \@folio@voffset . . . . . 2161, 2189 \@folio@wd . . . . . 2161, 2194, 2195, 2216, 2224 \@folioblob . . . . . 2213, 2215, 2221, 2222 \@footnotemark . . . . . 385, 1465 \@footnotemark@nolink ..... 385, 1465 \@footnotetext . . . . . 386, 560, 1466 \@footnotetext@nolink ..... 386, 1466	\@endprefalse . . . . . 831, 832, 834, 835, 838, 839, 842, 843, 846, 850, 854, 856, 860, 864, 866, 868, 870, 874, 878, 882, 886, 890, 894, 898, 902, 906, 910, 914, 918, 922, 926, 927, 930, 934, 935, 938, 943, 947, 951, 955, 959, 963, 967, 971, 975, 979, 983, 987, 991, 1001, 1002, 1516, 2125, 2133, 2142, 2210, 2218, 2226 \@journalNameShort . 799, 803, 808, 812, 816, 820, 824, 828, 847, 851, 857, 861, 871, 875, 879, 883, 887, 891, 895, 899, 903, 907, 911, 915	
\@currbox . . . . . 676, 677, 678	\@for . . . . . 191	\@for . . . . . 191	
\@currentaffiliation . . . . .	1884, 1887, 1909, 1916, 1917, 1919, 1921, 1922, 1926, 1952, 1959, 1960, 1962, 1964, 1965, 1969	\@formatdoi . . . . . 1327, 1523, 1529, 1533, 2018	\@formatdoi . . . . . 1327, 1523, 1529, 1533, 2018
\@currentaffiliations . . . . .	1842, 1843, 1844, 1846, 1849, 1861, 1862, 1867	\@fpss . . . . . 663	\@fpss . . . . . 663
\@currentauthors . . . . .	1840, 1841, 1848, 1852, 1853, 1855, 1883, 1886, 1908, 1910, 1911,	\@fpsadddefault . . . . . 663	\@fpsadddefault . . . . . 663

\@keywords 1158, 1546, 1552    \@par ..... 1485    \@setthanks ... 1485, 2041  
 \@latex@error ..... 259    \@parboxrestore ..... 577    \@shortauthors .....  
 \@empty ..... 1163, 1990    \@parfont . 2260, 2264, 2269    ..... 2087, 2117,  
 \@listI ..... 719, 723    \@permissionCodeOne ..... 2123, 2129, 2137, 2147  
 \@listi ..... 716, 723    ..... 800, 804, 809    \@sidebar ..... 649, 650  
 \@listii ..... 724    813, 817, 821, 825    \@specialsection .....  
 \@listiii ..... 727    829, 836, 840, 844    1542, 1548, 1550, 1567  
 \@listiv ..... 729    848, 852, 858, 862    \@ssect ..... 291, 357  
 \@listv ..... 731    872, 876, 880, 884    \@startPage ..... 1154,  
 \@listvi ..... 733    888, 892, 896, 900    1589, 1590, 1592, 2081  
 \@m ..... 294    904, 908, 912, 916    \@startsection .....  
 \@makefnmark ... 559,  
       584, 1472, 1477, 1481    920, 924, 928, 932,  
 \@makefntext ..... 559, 568, 581, 1482    940, 945, 949, 953,  
 \@marginfigure . 652, 653    957, 961, 965, 969,  
 \@marginable .. 655, 656    973, 977, 981, 985,  
 \@minipagefalse . 555, 672    \@permissionCodeTwo ..... 941, 1004  
 \@minus ... 2246, 2250,  
       2254, 2258, 2262,  
       2293, 2298, 2303,  
       2340, 2342, 2370, 2372    \@plus .. 372, 380, 585,  
       2246, 2250, 2254,  
       2258, 2262, 2293,  
       2298, 2303, 2339,  
       2341, 2369, 2371, 2406    \@subtitle ..... 1015,  
 \@mkabstract .. 1539, 1989    1092, 1715, 1716,  
 \@mkauthors 1473, 1475, 1788    1739, 1740, 1756, 1757  
 \@mkauthors@i .. 1792,  
       1794, 1796, 1798, 1847    \@printcopyrightfalse ..... 1260, 1272  
 \@mkauthors@ii .. 1877    \@printcopyrighttrue ..... 1244, 1256  
 \@mkauthors@iii .. 1800,  
       1802, 1804, 1806, 1888    \@printendtopmatter ..... 1563, 2020  
 \@mkauthors@iv .. 1808, 1937    \@printpermissionfalse ..... 1259  
 \@mkbibcitation 1559, 1999    \@printpermissiontrue ..... 1246, 1255, 1271  
 \@mkteasers ... 1473, 1981    \@printtopmatter ...  
 \@mktitle ..... 1473, 1632    ..... 1474, 1588  
 \@mktitle@i .. 1635,  
       1637, 1639, 1641, 1696    \@proofindent .....  
 \@mktitle@ii .. 1724    ..... 2390, 2400, 2408  
 \@mktitle@iii .. 1643,  
       1645, 1647, 1649, 1724    \@proofnamefont .....  
 \@mktitle@iv .. 1651, 1752    ..... 2389, 2399, 2409  
 \@mpargs ..... 558    \@received .. 1198, 1201,  
 \@mparswitchfalse .. 522    1202, 1204, 1207,  
 \@mpfootins ..... 550, 551, 553, 573, 574    1208, 1210, 1214, 1215  
 \@mpfootnotetext ... 572    \@rightskip .. 2265, 2266  
 \@ne .... 217, 221, 225,  
       227, 428, 2047, 2052    \@saveabstract .. 1160, 1161  
 \@nil ..... 236    \@saveteaser .. 1449, 1450  
 \@nobreakfalse .. 339, 379    \@seccntformat .. 299, 356  
 \@noskipsecfalse .. 343    \@secfont ..... 2248, 2269  
 \@noskipsectrue .. 340    \@secpenalty ..... 288  
       343    \@sect ..... 292, 293  
       340    \@setaddresses .. 1988    \@tempb ..... 192, 194,  
       196, 198, 200, 202,  
       204, 206, 208, 210,  
       212, 214, 216, 218,  
       220, 222, 224, 226,  
       228, 230, 232, 234,  
       239, 241, 243, 245,  
       247, 249, 2439, 2440  
       340    \@tempboxa ..... 558

```

@tempc . 237, 238, 240,
      242, 244, 246, 248, 250
@tempcnta . . . . . 2181,
      2183, 2184, 2186, 2188
@tempdima . . . . .
      2187, 2188, 2189, 2191
@tempskipa . . . . .
      280, 282, 283, 288,
      301, 302, 333, 334,
      336, 348, 349, 358, 359
@textbottom . . . . . 585
@textsuperscript . .
      . . . . . 584, 1472, 1477
@texttop . . . . . 586
@thefnmark . 565, 579,
      584, 1472, 1477, 1481
@title . . . 1083, 1562,
      1714, 1738, 1755, 2006
@titlefont 1654, 1706,
      1713, 1725, 1737, 1753
@titlenotes . . . .
      1081, 1085, 1088, 1478
@tochangmeasure 310, 323
@toclevel . . . . . 294
@tocline . . . 382, 383, 384
@topnum . . . . . 1468
@typeset@author@bx
      . . . . . 1881,
      1930, 1936, 1973, 1978
@typeset@author@line
      1839, 1850, 1872, 1874
@undefined . . . . . 438
@width . . . . . 541, 546
@xp . . . . . 376, 377
@xsect . . . . . 331, 332, 368
@z . . . . . 223
\\ 458, 1504, 1509, 1524,
      1528, 1532, 2001, 2051
\{ . . . . . 199
\} . . . . . 199
\ 1225, 1235, 1504, 1506,
      1528, 2009, 2015, 2081
A
\abstract . . . . . 1160
abstract (environment) 16
\acks . . . . . 2413
acks (environment) . . . 22
\acm@copyrightinput 1250
\acm@copyrightmode .
      1250, 1258, 1263,
      1266, 1270, 1276,
      1279, 1282, 1285,
      1288, 1291, 1297, 1329
\ACM@fontsize . . . .
      107, 151, 154, 156,
      158, 160, 162, 164,
      166, 168, 170, 173, 174
\ACM@format . . . . . 32, 115
\ACM@format@nr . . . . . 32,
      115, 119, 124, 130,
      152, 395, 462, 527,
      628, 680, 1568,
      1596, 1633, 1655,
      1676, 1790, 1814,
      2021, 2089, 2113,
      2168, 2204, 2237,
      2274, 2323, 2353, 2391
\ACM@linecount . . .
      2046, 2047, 2051, 2052
\ACM@linecount@bx . .
      . . . . . 2043, 2060, 2067
\ACM@linecount@bxht
      2045, 2050, 2053, 2054
\ACM@linecountL . . .
      . . . . . 2056, 2115,
      2118, 2121, 2124,
      2128, 2130, 2136,
      2138, 2146, 2148,
      2206, 2213, 2214,
      2222, 2223, 2229, 2232
\ACM@linecountR . . .
      2063, 2139, 2141,
      2147, 2151, 2230, 2233
\ACM@mk@linecount . .
      . . . . . 2048, 2058, 2065
\ACM@timestamp . . .
      2070, 2157, 2238, 2241
\acmArticle . . . . . 14, 1117
\acmArticleSeq . . . . . 14, 1119
\acmBadgeL . . . . . 15, 1149
\acmBadgeR . . . . . 15, 1144
\acmConference . . . . . 9, 1005
\acmConference@date
      . . . . . 1008, 1500,
      1518, 2013, 2149, 2151
\acmConference@name
      1007, 1518, 2012, 2014
\acmConference@shortname
      . . . . . 1006,
      1010, 1011, 1500,
      2014, 2015, 2148, 2150
\acmConference@venue
      . . . . . 1009,
      1500, 2012, 2149, 2151
\acmdefinition . . . . . 2368
\acmDOI . . . . . 14, 1135
\acmISBN . . . . . 14, 1133
\acmJournal . . . . . 7, 999
\acmMonth . . . . . 14, 1123
\acmNumber . . . . . 14, 1115
\acmplain . . . . . 2338
\acmPrice . . . . .
      . . . . . 14, 1129, 1268, 1274
\acmSubmissionID 14, 1131
\acmVolume . . . . . 14, 1113
\acmYear . . . . . 14, 1121
\addcontentsline 187,
      312, 325, 1991, 2416
\additionalaffiliation
      . . . . . 10, 1065
\addpenalty . . . . . 288
\addresses . 1024, 1026,
      1029, 1034, 1061,
      1079, 1103, 1109,
      1111, 1874, 1936, 1978
\addtolength . . . . . 704,
      705, 706, 710, 711, 2053
\addvspace . . . . . 288, 380
\advance . . . . . 720,
      725, 728, 730, 732,
      734, 1021, 1699,
      1700, 1703, 1704,
      1728, 1729, 1890,
      1907, 1939, 1950,
      2052, 2184, 2186, 2189
\affiliation . . . . . 9,
      1058, 1859, 1921, 1964
\and . . . . . 1034, 1035, 1048,
      1054, 1850, 1855,
      1857, 1867, 1872,
      1881, 1915, 1930,
      1936, 1958, 1973, 1978
\andify . . . . .
      1554, 1555, 1840, 1843
anonsuppress (environment) . . . . . 21

```

\AtBeginDocument . . . . .	189	\citeyearpar . . . . .	422, 424
..... 431, 439, 696		\city . . . . .	11, 1072, 1768
\AtEndDocument . . . . .	1213	\ClassError . . . . .	
\author . . . . .	9, 1019, 1461, 1462, 2003	..... 35, 997, 1064,	
\author@bx . . . . .	1877, 1882, 1885	1169, 1175, 1181, 2002	
\author@bx@sep . . . . .	..... 1879, 1885, 1890, 1907, 1939, 1950	\ClassInfo . . . . .	115, 173, 995,
		1166, 1168, 1172,	
		1174, 1178, 1180, 1183	
\author@bx@wd . . . . .	..... 1878, 1881, 1889, 1890, 1892, 1898, 1900, 1902, 1904, 1907, 1938, 1939, 1941, 1947, 1950	\ClassWarning . . . . .	
	1215, 1617, 1723, 1751, 1759, 1936, 1978, 1983, 2029, 2031, 2033, 2035, 2037	... 27, 120, 602,	
\authornote . . . . .	..... 13, 1065, 1101, 2004	605, 607, 1156, 1184	
\authornotemark . . . . .	13, 1107	\cleaders . . . . .	1765
\authors . . . . .	1027, 1030, 1035, 1554, 1556, 1561, 2006	\clubpenalty . . . . .	345, 351
		\CodelineIndex . . . . .	17
		\Collect@Body . . . . .	649,
		652, 655, 1160, 1449	
		\color . . . . .	1492, 2051
		\color@begingroup . . . . .	567, 580
		\color@endbox . . . . .	675
		\color@endgroup . . . . .	
		..... 556, 570, 583	
		\columnwidth . . . . .	541,
		576, 661, 1938, 1975	
		\contentsnamefont . . . . .	373
		\copy . . . . .	1765
		\copyright . . . . .	1504
		\copyrightpermissionfootnoterule . . . . .	540
		\copyrightyear . . . . .	16, 1446
		\country . . . . .	11, 1075, 1768
		\csname . . . . .	257, 308, 310,
		314, 321, 323, 327,	
		356, 376, 377, 565,	
		579, 1224, 1225,	
		1227, 1228, 1229,	
		1230, 1231, 1234, 1236	
		\CurrentOption . . . . .	108,
		109, 110, 111, 112, 113	
			D
		\day . . . . .	2079
		\DeclareNewFootnote . . . . .	544
		\DeclareOptionX . . . . .	
		..... 38, 108,	
		109, 110, 111, 112, 113	
		\DeclareRobustCommand . . . . .	426
		\def . . . . .	25, 38, 107,
		154, 156, 158, 160,	
		162, 164, 166, 168,	
		170, 192, 194, 196,	

198, 200, 202, 204,  
 206, 208, 210, 212,  
 214, 216, 217, 218,  
 219, 220, 221, 222,  
 223, 224, 225, 226,  
 228, 230, 232, 234,  
 235, 239, 241, 243,  
 245, 247, 249, 277,  
 293, 318, 332, 356,  
 357, 366, 369, 382,  
 383, 384, 389, 390,  
 391, 392, 437, 540,  
 545, 547, 559, 561,  
 572, 584, 585, 650,  
 653, 656, 661, 663,  
 667, 670, 688, 689,  
 690, 691, 719, 724,  
 727, 729, 731, 733,  
 798, 799, 800, 802,  
 803, 804, 806, 808,  
 809, 811, 812, 813,  
 815, 816, 817, 819,  
 820, 821, 823, 824,  
 825, 827, 828, 829,  
 831, 832, 834, 835,  
 836, 838, 839, 840,  
 842, 843, 844, 846,  
 847, 848, 850, 851,  
 852, 854, 856, 857,  
 858, 860, 861, 862,  
 864, 866, 868, 870,  
 871, 872, 874, 875,  
 876, 878, 879, 880,  
 882, 883, 884, 886,  
 887, 888, 890, 891,  
 892, 894, 895, 896,  
 898, 899, 900, 902,  
 903, 904, 906, 907,  
 908, 910, 911, 912,  
 914, 915, 916, 918,  
 919, 920, 922, 923,  
 924, 926, 927, 928,  
 930, 931, 932, 934,  
 935, 936, 938, 939,  
 940, 941, 943, 944,  
 945, 947, 948, 949,  
 951, 952, 953, 955,  
 956, 957, 959, 960,  
 961, 963, 964, 965,  
 967, 968, 969, 971,  
 972, 973, 975, 976,  
 977, 979, 980, 981,  
 983, 984, 985, 987,  
 988, 989, 991, 992,  
 993, 999, 1000,  
 1001, 1002, 1003,  
 1004, 1015, 1043,  
 1065, 1066, 1067,  
 1068, 1069, 1070,  
 1081, 1082, 1090,  
 1091, 1100, 1101,  
 1113, 1115, 1117,  
 1119, 1121, 1123,  
 1125, 1129, 1131,  
 1133, 1135, 1145,  
 1146, 1147, 1148,  
 1150, 1151, 1152,  
 1153, 1154, 1156,  
 1158, 1161, 1163,  
 1186, 1198, 1199,  
 1223, 1242, 1294,  
 1296, 1327, 1328,  
 1446, 1448, 1450,  
 1459, 1472, 1477,  
 1485, 1567, 1588,  
 1632, 1654, 1675,  
 1696, 1724, 1752,  
 1761, 1768, 1769,  
 1771, 1772, 1773,  
 1774, 1776, 1778,  
 1779, 1782, 1785,  
 1788, 1812, 1813,  
 1817, 1818, 1821,  
 1822, 1824, 1825,  
 1827, 1828, 1830,  
 1831, 1833, 1834,  
 1836, 1837, 1839,  
 1841, 1846, 1847,  
 1848, 1849, 1851,  
 1858, 1859, 1860,  
 1881, 1888, 1910,  
 1916, 1921, 1937,  
 1953, 1959, 1964,  
 1979, 1980, 1981,  
 1983, 1988, 1989,  
 1999, 2000, 2001,  
 2002, 2020, 2041,  
 2048, 2056, 2063,  
 2087, 2088, 2167,  
 2174, 2179, 2181,  
 2265, 2269, 2270,  
 2271, 2272, 2278,  
 2279, 2281, 2282,  
 2284, 2285, 2287,  
 2288, 2290, 2291,  
 2296, 2301, 2306,  
 2309, 2310, 2313,  
 2314, 2316, 2317,  
 2319, 2320, 2321,  
 2322, 2331, 2332,  
 2333, 2334, 2349,  
 2350, 2351, 2352,  
 2361, 2362, 2363,  
 2364, 2389, 2390,  
 2399, 2400, 2420,  
 2422, 2437, 2438, 2439  
`\define@boolkey` 49, 57,  
 65, 73, 81, 89, 97,  
 1063, 1164, 1170, 1176  
`\define@choicekey` . . . . .  
 ..... 32, 743, 1249  
`\define@cmdkey` . . . . . 1182  
`\definecolor` . . . . .  
 ... 445, 446, 447,  
 448, 449, 450, 451, 452  
`\department` . 11, 1069, 1768  
`\description` . . . . . 736  
`\descriptionlabel` 735, 738  
`\dimexpr` .. 659, 677, 2154  
`\divide` 1892, 1898, 1900,  
 1902, 1904, 1941, 1947  
`\do` . . . . . 191  
`\DocInput` . . . . . 21  
`\documentclass` . . . . . 9  
`\dots` . . . . . 1532

## E

`\edef` 108, 109, 110, 111, 294  
`\egroup` . . . . . 557,  
 651, 654, 657,  
 668, 674, 1076,  
 1543, 1552, 1884,  
 1978, 1984, 1998, 2019  
`\else` . 52, 60, 68, 76, 84,  
 92, 102, 126, 237,  
 258, 287, 294, 297,  
 309, 313, 317, 322,  
 326, 338, 350, 365,  
 414, 430, 436, 438,  
 550, 625, 1020,

1028, 1032, 1033,	\enspace . . . . . 2317
1042, 1047, 1050,	
1053, 1060, 1078,	environments:
1087, 1096, 1102,	abstract . . . . . 16
1110, 1167, 1173,	acks . . . . . 22
1179, 1190, 1193,	anonsuppress . . . . . 21
1203, 1206, 1209,	CCSXML . . . . . 15
1214, 1233, 1237,	marginfigure . . . . . 20
1238, 1455, 1473,	marginable . . . . . 20
1483, 1495, 1498,	printonly . . . . . 21
1499, 1505, 1510,	screenonly . . . . . 21
1517, 1522, 1525,	sidebar . . . . . 20
1528, 1530, 1532,	teaserfigure . . . . . 16
1541, 1546, 1549,	\everypar . . . . . 286, 341, 352
1591, 1620, 1625,	\excludecomment . 1218,
1698, 1702, 1707,	2425, 2427, 2431, 2432
1715, 1718, 1731,	\ExecuteOptionsX . . . . .
1739, 1746, 1756,	. . . . . 48, 56,
1762, 1763, 1777,	64, 72, 80, 88, 96, 106
1778, 1779, 1781,	\expandafter . . . . .
1782, 1785, 1842,	. . . . . 236, 238, 439,
1854, 1860, 1866,	558, 1224, 1225,
1882, 1893, 1903,	1227, 1228, 1234, 1236
1912, 1918, 1925,	
1942, 1946, 1955,	F
1961, 1968, 1982,	\familydefault . . . . . 617
1990, 1994, 2011,	\fancyfoot . . . . . 2119,
2014, 2082, 2087,	2125, 2133, 2142,
2144, 2231, 2240,	2145, 2157, 2207,
2422, 2426, 2433, 2441	2208, 2210, 2218,
\email . . . . . 9,	2226, 2234, 2238, 2241
<u>1077</u> , 1858, 1916, 1959	\fancyhead . 2115, 2116,
\emph . . . . . 1516, 1518	2117, 2118, 2121,
\EnableCrossrefs . . . . . 19	2122, 2123, 2124,
\end . . . . . 22, 2061, 2068, 2198	2128, 2130, 2131,
\end@dblfloat . . . . . 666	2136, 2138, 2139,
\end@float . . . . . 668	2140, 2146, 2147,
\endcsname . . . . .	2148, 2150, 2206,
256, 257, 308, 310,	2213, 2214, 2215,
314, 321, 323, 327,	2221, 2222, 2223,
356, 376, 377, 565,	2229, 2230, 2232, 2233
579, 1224, 1225,	\fancyheadoffset . . . . .
1227, 1228, 1229,	. . . . . 2154, 2216, 2224
1230, 1231, 1234, 1236	\fancyhf . . . . . 2110, 2201
\enddescription . . . . . 742	\fancypagestyle 2109, 2200
\endgroup . . . . . 307, 346, 364,	\fi . . . . . 54, 62, 70, 78, 86,
379, 1537, 1810, 2418	94, 104, 123, 128,
\endlist . . . . . 740, 742	150, 171, 172, 181,
\endminipage . . . . . 547	193, 195, 197, 199,
\endtrivlist . . . . . 2411	201, 203, 205, 207,
	209, 211, 213, 215,

1987, 1996, 1998, 1011, 1026, 1027, \if@ACM@affiliation@obeypunctuation  
 2015, 2017, 2039, 1029, 1030, 1040, 1063, 1763, 1778,  
 2055, 2062, 2069, 1046, 1052, 1161, 1779, 1780, 1782, 1785  
 2084, 2086, 2087, 1185, 1202, 1208, \if@ACM@anonymous ..  
 2108, 2115, 2116, 1225, 1227, 1228, .. 81, 1025, 1033,  
 2121, 2122, 2129, 1234, 1590, 1853, 1038, 1060, 1078,  
 2132, 2137, 2141, 1857, 1862, 1886, 1084, 1093, 1102,  
 2145, 2152, 2155, 1887, 1908, 1909, 1453, 1460, 2087, 2430  
 2158, 2180, 2207, 1911, 1915, 1917, \if@ACM@authordraft ..  
 2234, 2235, 2242, 1922, 1951, 1952, ..... 97, 453, 1488  
 2243, 2315, 2337, 1954, 1958, 1960, 1965 \if@ACM@authorversion ..  
 2367, 2403, 2422, \geometry ..... 65, 1495, 1511  
 2429, 2435, 2438, 2442 464, 467, 474, 481, \if@ACM@badge ..  
 \firstpagestyle .... 2200 488, 495, 502, 509, 516 ..... 1137, 1618, 1727, 1743  
 \floatname ..... 648 \global ..... 340, \if@ACM@journal ..  
 \footnote ..... 2002 343, 379, 573, 676, ..... 117, 621, 1191,  
 \footnotemark 392, 1083, 1021, 1022, 1059, 1499, 1515, 1526,  
 1092, 1979, 1980, 2000 1468, 1470, 1556, 1547, 1770, 1992, 2007  
 \footnoterule ..... 545 1557, 1850, 1872, \if@ACM@manuscript ..  
 \footnotesep ... 569, 582 1873, 1882, 1930, ..... 116,  
 \footnotesize ..... 1933, 1973, 1985, 2052 178, 1188, 1498, 1508  
 ..... 575, 2078, 2119, \grantrnum ..... 22, 2421 \if@ACM@natbib ..  
 2125, 2133, 2142, \grantsponsor .. 22, 2420 ..... 73, 183, 274, 418  
 2145, 2208, 2210, \footnotetextcopyrightpermis\if@ACM@natbib@override ..  
 2218, 2226, 2234, 2239 \hbox . 584, 1472, 1477, 1764 ..... 1170, 1558  
 \footnotetext .. 1086, \headrulewidth 2111, 2202 \if@ACM@newfonts 600, 610  
 1088, 1095, 1098, 1105 \footnotetextcopyrightpermis\if@ACM@printacmref ..  
 \footnotetextcopyrightpermis\if@ACM@printccs ..  
 \footnotetextcopyrightpermis\if@ACM@printfolios ..  
 \footrulewidth 2112, 2203 \hbox . 1720, 1732, 1747, 2441 ..... 1164, 1540  
 \format ..... 32 \hrule ..... 541, 546, 1754 \if@ACM@review ..  
 \frenchspacing .... 2443 \hrulefill . 1599, 1602, ..... 57, 2043, 2057, 2064  
 \fulltextwidth ..... 1605, 2023, 2025, 2027 \hspace ..... 576,  
 ..... 658, 661, 677 1471, 1696, 1697, \if@ACM@screen 49, 408, 2423  
 \G ..... 1724, 1726, 1752, \hspace ..... 1789, 1881, 1932, 1975 \if@ACM@sigchiamode ..  
 \g@addto@macro .... 1789, 1881, 1932, 1975 ..... 118,  
 ..... 1034, 1035, \hspace ..... 305, 560, 616, 660, 666,  
 1048, 1054, 1061, 319, 349, 362, 366, 1473, 1475, 1882, 2153  
 1079, 1083, 1085, 1623, 1710, 1719, \if@ACM@timestamp ..  
 1088, 1092, 1094, 1735, 1744, 1765, 2408 ..... 89, 2070, 2156, 2236  
 1097, 1103, 1104, \hspace ..... 1339, 1350, \if@acmowned ..  
 1109, 1111, 1204, 1359, 1376, 1390, ..... 1247  
 1210, 1229, 1236, 1402, 1423, 1885, 1935 \if@files ..  
 1450, 1454, 1456, 1663, 1665, ..... 375, 441  
 1855, 1867, 1913, 1667, 1669, 1671, 1673 \if@insideauthorgroup ..  
 1919, 1926, 1956, \hypersetup ..... 409, 415, 1561 ..... 1019, 1020  
 1962, 1969, 1979, 1980 \if ..... 237 \if@nobreak ..  
 \gdef ..... 1006, \if ..... 237 \if@noskipsec ..  
 1007, 1008, 1009,

```

\if@printcopyright . 1953, 1959, 1964, 1686, 1688, 1690,
..... 1243, 1503 1982, 1990, 2014, 1692, 1821, 1824, 2197
\if@printpermission 2082, 2422, 2438, 2440 \Large 1812, 1830, 2284,
..... 1245, 1496 \ignorespaces .....
\ifcase . 130, 152, 395, 2285, 2287, 2288, 2290
..... 462, 527, 628, 680, 1067, 1068, 1070, 1817, 1822, 1825,
796, 1125, 1297, 1768, 1769, 1771, 2278, 2279, 2281, 2282
1329, 1568, 1596, 1772, 1773, 1774, \lastbox .....
1633, 1655, 1676, 1776, 1997, 2001, 2409 \leaders .....
1790, 1814, 1894, \immediate .....
1943, 2021, 2089, \includecomment .....
2113, 2168, 2204, 2424, 2428, 2434 \leftmargin .....
2274, 2323, 2353, 2391 \includegraphics ...
\ifcsname ..... 1622, 1627, 724, 727, 729, 731, 733
\ifdim 282, 302, 334, 359, 2054 1709, 1721, 1733, 1748 \leftmargini ... 703,
\IffileExists 602, 605, 607 \indent .....
\IfInteger ..... 1183 \input .....
\ifNAT@numbers ..... 436 \InputIfFileExists .. 26 \leftmarginii ... 709,
\ifnum ..... 119, 124, \institution 11, 1068, 1768 \leftmarginiii .....
294, 295, 309, 313, \interfootnotelinepenalty .....
322, 326, 1237, 563 \leftmarginiv .....
1238, 1258, 1263, \interlinepenalty ...
1266, 1270, 1276, 306, 363, 563 \leftmarginv .....
1279, 1282, 1285, \item .....
1288, 1291, 1462, 1500, 2271, \leftmarginvi 715, 733, 734
1891, 1940, 2183, 2237 2272, 2301, 2306, \leftskip . 1753, 1976, 2267
\ifPDFTeX ..... 588 2319, 2331, 2351, 2399 \let .....
\ifvmode ..... 1762 \jobname .....
\ifvoid ..... 550 J 213, 215, 227,
\ifx ..... 151, 229, 231, 257, 296,
..... 192, 194, 196, 198, 385, 386, 419, 420,
200, 202, 204, 206, 421, 422, 423, 424,
208, 210, 212, 214, 425, 428, 432, 586,
216, 218, 220, 222, \kern 540, 541, 545, 546, 1754
224, 226, 228, 230, \keywords .....
232, 234, 239, 241, 15, 1158
243, 245, 247, 249, \L
438, 1010, 1024, \l@section .....
1039, 1044, 1045, 382 \l@subsection ...
1051, 1108, 1200, 382, 383 \l@subsubsection ...
1201, 1207, 1214, \labelenumi .....
1224, 1233, 1483, \labelenumii .....
1520, 1528, 1532, \labelenumiii .....
1541, 1546, 1589, \labelsep .....
1620, 1625, 1698, 697, 705, 710, 720, 725, 691
1702, 1707, 1715, 728, 730, 732, 734, 2408 \lineskip .....
1718, 1731, 1739, \labelwidth . 720, 725, 728, 730, 732, 734, 737 \lineskip .....
1746, 1756, 1842, \LARGE .....
1852, 1860, 1861, 1657, \loop .....
1910, 1916, 1921, 1659, 1661, 1684, M \long .....
..... 1489, 2191 \makebox .....

```

```

\makelabel ..... 738 \NAT@numbersfalse .. 207 1985, 1986, 1993,
\MakeTextUppercase . \NAT@numberstrue 209, 211 2005, 2006, 2018,
.... 1853, 1855, \NAT@open ..... 193, 2023, 2025, 2027, 2400
2269, 2278, 2281, 195, 197, 199, 240, 428 \nolinkurl .....
2284, 2287, 2309, 2313 \NAT@partrue ..... 428 1917, 1919, 1960, 1962
\maketitle .... 18, 1459 \NAT@rem@eq ..... 238 \normalcolor .....
\marginfigure .... 652 \NAT@sep 201, 203, 205, 250 \normalfont 584, 1215,
marginfigure (environment) ..... 20 \NAT@sort ... 217, 219, 225 1477, 1813, 1818,
\marginpar ..... 561, \NAT@superfalse ..... 209 1827, 1828, 1830,
651, 654, 657, 1619 \NAT@supertrue ..... 211 1831, 2334, 2349,
\marginparsep .. 659, 2154 \NAT@swafalse ..... 427 2361, 2364, 2406, 2443
\marginparwidth . 659, 2154 \NAT@up ..... 235 \normalparindent ...
\marginitable .... 655 \NAT@yrsep ..... 246 \normalsize 1675, 1813,
marginitable (environment) ..... 20 \NeedsTeXFormat ..... 1 1827, 1828, 1831, 2443
\newblock ..... 429 \newbox .. 1458, 1760, 1877 \num@authorgroups ...
\mbox ..... 235 \newcommand . 263, 269, 1017, 1021, 1462,
\mdseries ..... 435, 1005, 1058, 1894, 1898, 1900, 1943
1678, 1680, 1682, \number ..... 294
1686, 1688, 1690, \numberline .... 314, 327
1692, 1694, 1834, 1837 1107, 1144, 1149, \numexpr . 2072, 2074, 2076
\medskip ..... 1199, 1220, 1775,
1570, 1572, 1574, \newcount ..... 1017, 2046 \o
1576, 1873, 1875, \newcounter ... 2073, 2075 \onehalfspacing .....
1934, 1986, 2005, \newdimen ... 658, 695, 180
2020, 2023, 2025, 2027 \newenvironment ..... 652, 655, 1449
\mkttitle@bx .... 1458, \newfloat ..... 647 \openout .....
1598, 1601, 1604, \newif 116, 117, 118, 600, 377
1607, 1609, 1611, 1137, 1243, 1245, 1247 \or .....
1613, 1615, 1617, \newlength ..... 1139, 1141, 1142, 2045 133,
1706, 1725, 1753, \newsavebox ..... 2044 135, 137, 139, 141,
1873, 1933, 1934, 1985 \newskip ..... 717, 1879 143, 145, 147, 155,
\month ..... 1124, 2079 \newtheorem ..... 2380, 2381, 2382, 157, 159, 161, 163,
\moveleft ..... 676 \newtheorempstyle ... 2383, 2384, 2386, 2387 165, 167, 169, 397,
\multiply ..... 2188 \newwrite ..... 376 398, 399, 400, 401,
\NAT@setcites .... 253 \nobreak ..... 335, 2005 402, 404, 405, 466,
\NAT@aysep ..... 244 \noindent ..... 2380, 2381, 2382, 473, 480, 487, 494,
\NAT@citetp ..... 428 \newtheoremstyle ... 2383, 2384, 2386, 2387 501, 508, 515, 529,
\NAT@close ..... 193, 195, 197, 199, 242 \newtheorempstyle ... 2338, 2368 530, 531, 533, 534,
\NAT@cmptrs .. 221, 223, 225 \newwrite ..... 376 535, 536, 537, 630,
\NAT@cmt ..... 248 \nobreak ..... 335, 2005 \noindent ..... 2380, 2381, 2382, 631, 632, 633, 634,
\NAT@ctype ..... 428 \noindent ..... 559, 1215, 1482, 636, 639, 642, 682,
\NAT@find@eq ..... 236 \noindent ..... 1570, 1572, 1574, 683, 684, 685, 686,
\NAT@fullfalse .... 428 \noindent ..... 1576, 1595, 1599, 687, 692, 693, 801,
\NAT@longnamestrue . 233 \noindent ..... 1602, 1605, 1619, 805, 810, 814, 818,
\NAT@merge .. 227, 229, 231 \noindent ..... 1706, 1713, 1716, 822, 826, 830, 833,
\NAT@nmfmt ..... 235 \noindent ..... 1740, 1754, 1755, 837, 841, 845, 849,
\NAT@numbersfalse .. 207 \noindent ..... 1757, 1840, 1873, 853, 855, 859, 863,
\NAT@numberstrue . 209, 211 \noindent ..... 1874, 1933, 1977, 865, 867, 869, 873,
\NAT@open ..... 193, 195, 197, 199, 242 \noindent ..... 1570, 1572, 1574, 877, 881, 885, 889,
\NAT@rem@eq ..... 238 \noindent ..... 1576, 1595, 1599, 893, 897, 901, 905,
\NAT@sep 201, 203, 205, 250 \noindent ..... 1602, 1605, 1619, 909, 913, 917, 921,
\NAT@sort ... 217, 219, 225 \noindent ..... 1706, 1713, 1716, 925, 929, 933, 937,
\NAT@superfalse ..... 209 \noindent ..... 1740, 1754, 1755, 942, 946, 950, 954,
\NAT@supertrue ..... 211 \noindent ..... 1757, 1840, 1873, 958, 962, 966, 970,
\NAT@swafalse ..... 427 \noindent ..... 1874, 1933, 1977,

```

\outer@nobreak . . . . .	673	\PassOptionsToClass . . . . .	112, 113
<b>P</b>		\pdfgentounicode . . . . .	597
\p@ . . . . .	380,	\pdfglyptounicode . . . . .	590, 591, 592, 593, 594, 595, 596
525, 532, 540, 541, 545, 546, 2246, 2250, 2254, 2255, 2258, 2259, 2262, 2263, 2293, 2298, 2299, 2303, 2304, 2406		\pdfstringdefDisableCommands . . . . .	388
\PackageError . . . . .	54, 62, 70, 78, 86, 94, 104	\phantomsection . . . . .	187, 1991, 2416
\PackageInfo . . . . .	51, 53, 59, 61, 67, 69, 75, 77, 83, 85, 91, 93, 99, 103	\popQED . . . . .	2411
\PageIndex . . . . .	16	\position . . . . .	11, 1067, 1071, 1072, 1073, 1074, 1075, 1768
\pageref . . . . .	2081	\postcode . . . . .	11, 1074, 1768
\pagestyle . . . . .	2160	\printonly (environment)	21
\par . . . . .	279, 335, 371, 548, 671, 1215, 1485, 1496, 1500, 1543, 1552, 1570, 1572, 1574, 1576, 1598, 1599, 1601, 1602, 1604, 1605, 1617, 1716, 1723, 1740, 1751, 1754, 1757, 1759, 1778, 1779, 1781, 1782, 1840, 1844, 1873, 1875, 1881, 1883, 1911, 1913, 1919, 1926, 1934, 1936, 1954, 1956, 1962, 1969, 1976, 1978, 1983, 1984, 1985, 1986, 1997, 2005, 2017, 2019, 2020, 2023, 2025, 2027, 2029, 2031, 2033, 2035, 2037, 2041, 2404	\ProcessOptionsX . . . . .	114
\paragraph . . . . .	1582, 2257, 2297	\proof . . . . .	2404
\parbox . . . . .	457, 1712, 1730, 1737, 1745, 2049, 2195	\proofname . . . . .	2404
\parindent .. . . .	525, 539, 704, 1485, 1494, 2257, 2268, 2320, 2350	\protect . . . . .	314, 327
\parskip . . . . .	525, 1494	\protected@edef . . . . .	299, 564, 578
\orcid . . . . .	9, 1081	\providecommand . . . . .	429, 433, 2318
		\ProvidesClass . . . . .	5
		\ProvidesFile . . . . .	3
		\pushQED . . . . .	2405
		\put . . . . .	2060, 2067
		<b>Q</b>	
		\qed . . . . .	2405
		\quad . . . . .	356, 2129, 2132, 2137, 2141, 2238
		<b>R</b>	
		\raggedright . . . . .	
		. . . . .	1712, 1753, 1976
		\raisebox . . . . .	
		1489, 1708, 1720, 1732, 1747, 2191, 2193	
		\received . . . . .	18, 1199
		\RecordChanges . . . . .	18
		\ref . . . . .	2010, 2016
		\refname . . . . .	186, 187
		\refstepcounter . . . . .	298
		\relax . . . . .	119, 124, 131, 153, 236, 237, 280, 299, 301, 305, 319, 333, 348, 358, 366, 377, 396, 463, 528,

<b>S</b>	<b>T</b>
\savebox . . . . . 2049	2099, 2101, 2103, 2105, 2107, 2197,
screenonly (environment) . . . . . 21	2269, 2270, 2271, 2278, 2279, 2281, 2282, 2287, 2288,
\scriptsize . . . . . 2051	2309, 2310, 2313, 2314
\scshape . . . . . 2321, 2389	
\section . . . . . 186, 1578, 1580, 1584, 1586, 1995, 2245, 2415	\shortauthors 18, 1039, 1040, 1045, 1046, 1048, 1051, 1052, 1054, 1555, 1557, 2087
\section@raggedright . . . . . 2265, 2269, 2270, 2278, 2279, 2281, 2282, 2284, 2285, 2287, 2288, 2290, 2291, 2296, 2309, 2310, 2313, 2314	\shortcite . . . . . 432, 435 \shorttitle . . . . . 2118, 2124, 2132, 2141, 2146
\SelectFootnoteRule 543	\showeprint . . . . . 2436
\setbox . . . . . 344, 573, 676, 1706, 1725, 1753, 1764, 1873, 1882, 1933, 1985	\sidebar . . . . . 647 sidebar (environment) . 20
\setcitestyle . . . . . 23, 190, 264, 270	\skip . . . . . 551
\setcopyright . . . . . 16, 1294	\small . . . . . 562, 651, 654, 657, 1215, 1570, 1572, 1574, 1576, 1818, 1993, 2005, 2207
\setcounter . . . . . 1476, 1538, 1592, 2074, 2076, 2273, 2308, 2312	\smallskipamount . . . . . 718
\setkeys . . . . . 38, 122, 999, 1186, 1294, 1863, 1864, 1868, 1869, 1923, 1924, 1927, 1928, 1966, 1967, 1970, 1971	\space . . . . . 323, 1785, 2422
\setlength 525, 526, 532, 539, 697, 698, 703, 709, 712, 713, 714, 715, 1140, 1143, 2050	\specialcomment . . . . . 2413
\settopmatter . . . . . 18, 1186, 1187, 1189, 1192, 1194, 1197	\standardpagestyle . . . . . 2109
\setTrue . . . . . 370	\startPage . . . . . 15, 1154
\SetWatermarkColor . . . . . 456	\state . . . . . 11, 1073, 1768
\SetWatermarkFontSize 455	\stepcounter . . . . . 1086, 1088, 1095, 1098, 1105
\SetWatermarkText . . . . . 457	\streetaddress . . . . . 11, 1071, 1768
\sfdefault . . . . . 617	\string 442, 1156, 2003, 2004
\sffamily . . . . . 1657, 1659, 1661, 1663, 1665, 1667, 1671, 1812,	\strut . . . . . 1730, 1745
\rlap . . . . . 2192	\strutbox . . . . . 569, 582
\rule . . . . . 569, 582, 2194	\ subparagraph . . . . . 2302
	\ subsection . . . . . 2249
	\ subsubsection . . . . . 2253, 2292
	\ subtitle . . . . . 9, 1015
	\ subtitlenote . . . . . 13, 1091
	\teaserfigure . . . . . 1449
	teaserfigure (environment) . . . . . 16
	\ terms . . . . . 15, 1156
	\textbf . . . . . 1226, 1237
	\textbullet . . . . . 390, 1225, 2129, 2132, 2137, 2141
	\textcolor . . . . . 2197
	\textheight . . . . . 2054

\textit ..	1238, 2008, 2012	\time .....	2071, 2074, 2076	\vtop .....	1882
\textrightarrow .	391, 1235	\title .....	9, 2003		
\textwidth	659, 677, 678, 1471, 1696, 1724, 1752, 1789, 1889, 1932	\titlenote ..	13, 1082, 2004	<b>W</b>	
\thanks .....	13, 1451, 2041	\topsep .....	722, 726, 2406	\wd .....	678, 1765
\thankses .....	1454, 1456, 1483, 2041	\trivlist .....	2407	\write .....	442
\the .....	1122, 1124, 2051, 2079, 2188	\tw@ .....	229		
\theACM@time@hours ..	2076, 2080	\two@digits .....	2079, 2080	<b>X</b>	
		\twocolumn .....	1607, 1609, 1611, 1613, 1615	\xdef .....	240, 242, 244, 246, 248, 250
		<b>U</b>		<b>Y</b>	
\unskip .....	347, 389, 549, 1070, 1076, 1765, 1768, 1769, 1771, 1773, 1774, 1776, 1785, 1844, 2001	\year .....	1122, 2079		
\theACM@time@minutes 2080				<b>Z</b>	
\theenumi .....	688			\z@ .....	219, 282, 302, 334, 344, 359, 372, 526, 569, 582, 585, 623, 627, 638, 703, 709, 721,
\theenumii .....	689				1468, 1470, 1485, 1489, 1494, 1708, 1720, 1732, 1747, 1976, 2111, 2112, 2162, 2164, 2166,
\theenumiii .....	690				2191, 2193, 2202, 2203, 2245, 2249, 2261, 2268, 2292, 2297, 2302, 2332, 2362
\theenumiv .....	691				
\thefootnote .....	1467				
\theoremstyle .....	2379, 2385, 2388				
\thepage ..	2081, 2115, 2116, 2121, 2122, 2129, 2132, 2137, 2141, 2145, 2207, 2234	\unvbox .....	553, 558, 574		
\thispagestyle .....	1594	\upshape .....	735		
\thmname .....	2348, 2378	\url .....	1327, 2422		
\thmnote .....	2348, 2378	\urlstyle .....	394, 403, 406		
\thmnumber .....	2348, 2378	\usebox .....	2060, 2067		
\thr@@ .....	231	\usepackage .....	. 10, 11, 12, 13, 14, 15		
		<b>V</b>			
\vbox .....	573,				