

LATEX Class for Association for Computing Machinery^{*}

Boris Veytsman[†]

2017/04/23, v1.35

Abstract

This package provides a class for typesetting publications of Association for Computing Machinery.

Contents

1	Introduction	3
2	User's guide	3
2.1	Installation	3
2.2	Invocation and options	5
2.3	Topmatter commands	7
2.4	Algorithms	17
2.5	Figures and tables	18
2.6	Theorems	19
2.7	Online-only and offline-only material	19
2.8	Note about anonymous mode	20
2.9	Acknowledgments	20
2.10	Bibliography	21
2.11	Colors	23
2.12	Other notable packages and typographic remarks	24
2.13	A note for wizards: <code>acmart-preload-hook.tex</code>	24
3	Implementation	26
3.1	Identification	26
3.2	Preload	26
3.3	Options	26
3.4	Setting switches	29

^{*}©2016–2017, Association for Computing Machinery

[†]borisv@lk.net, boris@varphi.com

3.5	Loading base class and package	30
3.6	Paper size and paragraphing	37
3.7	Fonts	40
3.8	Floats	40
3.9	Lists	42
3.10	Top matter data	43
3.11	Concepts system	54
3.12	Copyright system	55
3.13	Typesetting top matter	59
3.14	Headers and Footers	73
3.15	Sectioning	78
3.16	TOC Lists	80
3.17	Theorems	80
3.18	Acknowledgments	82
3.19	Conditional typesetting	83
3.20	Additional bibliography commands	83
3.21	End of Class	83

1 Introduction

Association for Computing Machinery is the world's largest educational and scientific computing society, which delivers resources that advance computing as a science and a profession¹. It was one of the early adopters of \TeX for its typesetting.

It provided several different classes for a number of journal and conference proceedings. Unfortunately during the years since these classes were written, the code was patched many times, and the support of the different versions of the classes became difficult.

This package provides the uniform interface for all ACM publications. It is intended to replace all different classes and packages and provide an up to date \LaTeX package.

The package uses only free \TeX packages and fonts included in $\text{\TeX}Live$, $\text{MiK}\text{\TeX}$ and other popular \TeX distributions. It is intended to be published in these distributions itself, which minimizes users' efforts in the installation and support of the package.

I am grateful to Matthew Fluet, John Owens, Craig Rodkin, Bernard Rous, David Shamma, Stephen Spencer and many others for their invaluable help.

The development version of the package is available at <https://github.com/borisveytsman/acmart>.

2 User's guide

2.1 Installation

Most probably, you already have this package installed in your favorite \TeX distribution; if not, you may want to upgrade. You may need to upgrade it anyway since the package uses a number of relatively recent packages, especially the ones related to the fonts.

The latest released version of the package can be found on CTAN: <https://www.ctan.org/pkg/acmart>. The development version can be found on GitHub: <https://github.com/borisveytsman/acmart>. At this address you can file a bug report—or even contribute your own enhancement making a pull request.

Most users should not attempt to install this package themselves, and rather rely on their \TeX distributions to provide it. If you decide to install the package yourself, follow the standard rules:

1. Run `latex` on `acmart.ins`. This will produce the file `acmart.cls`.
2. Put the file `acmart.cls` and the bibliography files `*.bst` to the places where \LaTeX can find them (see [1] or the documentation for your \TeX system).
3. Update the database of file names. Again, see [1] or the documentation for your \TeX system for the system-specific details.
4. The file `acmart.pdf` provides the documentation for the package (this is the file you are probably reading now).

¹<http://www.acm.org/>

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

The class uses a number of other packages. They are included in all major \TeX distributions ($\text{\TeX}^{\text{Live}}$, Mac \TeX , Mik \TeX) of 2015 and later, so you probably have them installed. Just in case here is the list of these packages:

- *amscls*, <http://www.ctan.org/pkg/amscls>
- *amsfonts*, <http://www.ctan.org/pkg/amsfonts>
- *amsmath*, <http://www.ctan.org/pkg/amsmath>
- *binhex*, <http://www.ctan.org/pkg/binhex>
- *caption*, <http://www.ctan.org/pkg/caption>
- *comment*, <http://www.ctan.org/pkg/comment>
- *cm-super*, <http://www.ctan.org/pkg/cm-super>
- *cmap*, <http://www.ctan.org/pkg/cmap>
- *draftwatermark*, <http://www.ctan.org/pkg/draftwatermark>
- *environ*, <http://www.ctan.org/pkg/environ>
- *fancyhdr*, <http://www.ctan.org/pkg/fancyhdr>
- *float*, <http://www.ctan.org/pkg/float>
- *fontaxes*, <http://www.ctan.org/pkg/fontaxes>
- *geometry*, <http://www.ctan.org/pkg/geometry>
- *graphics*, <http://www.ctan.org/pkg/graphics>
- *hyperref*, <http://www.ctan.org/pkg/hyperref>
- *ifluatex*, <http://www.ctan.org/pkg/ifluatex>
- *ifxetex*, <http://www.ctan.org/pkg/ifxetex>
- *inconsolata*, <http://www.ctan.org/pkg/inconsolata>
- *latex-tools*, <http://www.ctan.org/pkg/latex-tools>
- *libertine*, <http://www.ctan.org/pkg/libertine>
- *manyfoot*, <http://www.ctan.org/pkg/manyfoot>
- *microtype*, <http://www.ctan.org/pkg/microtype>
- *mmap*, <http://www.ctan.org/pkg/mmap>
- *ms*, <http://www.ctan.org/pkg/ms>

- *mweights*, <http://www.ctan.org/pkg/mweights>
- *natbib*, <http://www.ctan.org/pkg/natbib>
- *nccfoots*, <http://www.ctan.org/pkg/nccfoots>
- *newtx*, <http://www.ctan.org/pkg/newtx>
- *oberdiek*, <http://www.ctan.org/pkg/oberdiek>
- *pdftex-def*, <http://www.ctan.org/pkg/pdftex-def>
- *setspace*, <http://www.ctan.org/pkg/setspace>
- *totpages*, <http://www.ctan.org/pkg/totpages>
- *trimspaces*, <http://www.ctan.org/pkg/trimspaces>
- *upquote*, <http://www.ctan.org/pkg/upquote>
- *url*, <http://www.ctan.org/pkg/url>
- *xcolor*, <http://www.ctan.org/pkg/xcolor>
- *xkeyval*, <http://www.ctan.org/pkg/xkeyval>

2.2 Invocation and options

To use the class put in the preamble of your document

```
\documentclass[⟨options⟩]{acmart}
```

There are several options corresponding to the type of the document and its general appearance. They are described below. Generally speaking, the options have key=value forms, for example

```
\documentclass[format=acmsmall, screen=true, review=false]{acmart}
```

The option *format* describes the format of the output. There are several possible values for this option, for example,

```
\documentclass[format=acmtog]{acmart}
```

Actually the words *format=* can be omitted, e.g.,

```
\documentclass[acmtog, review=false]{acmart}
```

Table 1: The possible values for the `format` option

Value	Meaning
<code>manuscript</code>	A manuscript. This is the default
<code>acmsmall</code>	Small single column format, used for CIE, CSUR, JACM, JDIQ, JEA, JERIC, JETC, TAAS, TACCESS, TACO, TALG, TALLIP (formerly TALIP), TCPS, TEAC, TECS, TIIS, TISSEC, TIST, TKDD, TMIS, TOCE, TOCHI, TOCL, TOCS, TOCT, TODAES, TODS, TOIS, TOIT, TOMACS, TOMM (formerly TOMCCAP), TOMPECS, TOMS, TOPC, TOPLAS, TOPS, TOS, TOSEM, TOSN, TRETS, TSAS, TSC, TSLP, TWEB, including special issues.
<code>acmlarge</code>	Large single column format, used for IMWUT, JOCH, PACMPL, POMACS, TAP, including special issues.
<code>acmtog</code>	Large double column format, used for TOG, including special issues.
<code>sigconf</code>	Proceedings format for most of ACM conferences (with the exceptions listed below) and all ICPS volumes.
<code>siggraph</code>	As of March 2017, this format is no longer used. Please use <code>sigconf</code> for SIGGRAPH conferences.
<code>sigplan</code>	Proceedings format for SIGPLAN conferences.
<code>sigchi</code>	Proceedings format for SIGCHI conferences.
<code>sigchi-a</code>	Format for SIGCHI extended abstract.

The possible formats are listed in Table 1. Note that formats starting with `acm` are intended for journals and transactions, while formats starting with `sig` are intended for proceedings published as books.

Note that sometimes conference proceedings are published as a special issue (or issues) of an ACM journal. In this case you should use the journal format for a conference paper. Please contact your conference committee if in doubt.

There are several Boolean options which can take `true` or `false` values. They are listed in Table 2. The words `=true` can be omitted when setting the Boolean option, so instead of `screen=true` one can write just `screen`, for example,

```
\documentclass[acmsmall, screen, review]{acmart}
```

The option `review` is useful when combined with the `manuscript` format option: it provides a version suitable for reviewers and copyeditors.

The option `screen` may in the future involve additional features suitable for on-screen versions of the articles.

The option `natbib` is used when the corresponding `BIBTEX` style is based on `natbib`. In most cases you do not need to set it. See Section 2.10.

The option `anonymous` is used for anonymous review process: all author information becomes obscured.

The option `timestamp` is used to include a time stamp in the footer of each page. When preparing a document, this can help avoid confusing different revisions. The

Table 2: Boolean options

Option	Default	Meaning
review	false	A review version: lines are numbered, hyperlinks are colored
screen	false	A screen version: hyperlinks are colored
natbib	true	Whether to use natbib package (see Section 2.10)
anonymous	false	Whether to make author(s) anonymous
authorversion	false	Whether to generate a special version for authors' personal use or posting (see Section 2.3)
timestamp	false	Whether to put a time stamp in the footer of each page
authordraft	false	Whether author's draft mode is enabled

footer also include the page range of the document. This helps detect missing pages in hard copies.

The option `authordraft` is intended for the authors' drafts, not intended for distribution. It typesets copyright block to give the authors the idea of its size and overall size of the paper, but overprints it with the phrase "Unpublished working draft. Not for distribution", which also is used as a watermark. This option sets `timestamp` and `review` to true, but these decisions can be overridden by setting these options to false *after* `authordraft`.

2.3 Topmatter commands

A number of commands set up *top matter* information, or, in the computer science jargon, *metadata* for the article. They establish the publication name, article title, authors, doi and other data. Some of these commands, like `\title` or `\author`, should be put by the authors. Others, like `\acmVolume` or `\acmDOI`—by the editors. Below we describe these commands and mention who should issue them. These macros should be used *before* the `\maketitle` command. Note that in the previous versions of ACM classes some of these commands should be used before `\maketitle`, and some after it. Now they all must be used before `\maketitle`.

The class internally loads `amsart` class, so many top matter commands are inherited from `amsart` [2].

The macro `\acmJournal{<shortName>}` sets the name of the journal or transaction for journals and transactions. The argument is the short name of the publication *in uppercase*, for example,

```
\acmJournal{TOMS}
```

The currently recognized journals are listed in Table 3. Note that conference proceedings published in *book* form do not set this macro.

It is expected that this command is inserted by the author of the manuscript when she decides to which journal to submit the manuscript.

Table 3: ACM publications and arguments of the \acmJournal command

Abbreviation	Publication
CIE	ACM Computers in Entertainment
CSUR	ACM Computing Surveys
IMWUT	PACM on Interactive, Mobile, Wearable and Ubiquitous Technologies
JACM	Journal of the ACM
JDIQ	ACM Journal of Data and Information Quality
JEA	ACM Journal of Experimental Algorithms
JERIC	ACM Journal of Educational Resources in Computing
JETC	ACM Journal on Emerging Technologies in Computing Systems
JOCCH	ACM Journal on Computing and Cultural Heritage
PACMPL	PACM on Programming Languages
POMACS	PACM on Measurement and Analysis of Computing Systems
TAAS	ACM Transactions on Autonomous and Adaptive Systems
TACCESS	ACM Transactions on Accessible Computing
TACO	ACM Transactions on Architecture and Code Optimization
TALG	ACM Transactions on Algorithms
TALLIP	ACM Transactions on Asian and Low-Resource Language Information Processing
TAP	ACM Transactions on Applied Perception
TCPS	ACM Transactions on Cyber-Physical Systems
TEAC	ACM Transactions on Economics and Computation
TECS	ACM Transactions on Embedded Computing Systems
TIIS	ACM Transactions on Interactive Intelligent Systems
TISSEC	ACM Transactions on Information and System Security
TIST	ACM Transactions on Intelligent Systems and Technology
TKDD	ACM Transactions on Knowledge Discovery from Data
TMIS	ACM Transactions on Management Information Systems
TOCE	ACM Transactions on Computing Education
TOCHI	ACM Transactions on Computer-Human Interaction
TOCL	ACM Transactions on Computational Logic
TOCS	ACM Transactions on Computer Systems
TOCT	ACM Transactions on Computation Theory
TODAES	ACM Transactions on Design Automation of Electronic Systems
TODS	ACM Transactions on Database Systems
TOG	ACM Transactions on Graphics
TOIS	ACM Transactions on Information Systems
TOIT	ACM Transactions on Internet Technology
TOMACS	ACM Transactions on Modeling and Computer Simulation
TOMM	ACM Transactions on Multimedia Computing, Communications and Applications
TOMPECS	ACM Transactions on Modeling and Performance Evaluation of Computing Systems
TOMS	ACM Transactions on Mathematical Software
TOPC	ACM Transactions on Parallel Computing
TOPLAS	ACM Transactions on Programming Languages and Systems
TOPS	ACM Transactions on Privacy and Security
TOS	ACM Transactions on Storage
TOSEM	ACM Transactions on Software Engineering and Methodology
TOSN	ACM Transactions on Sensor Networks
TRETS	ACM Transactions on Reconfigurable Technology and Systems
TSAS	ACM Transactions on Spatial Algorithms and Systems
TSC	ACM Transactions on Social Computing
TSLP	ACM Transactions on Speech and Language Processing
TWEB	ACM Transactions on the Web

\acmConference[*short name*]{*name*}{*date*}{*venue*} is used for conference proceedings published in the book form. The arguments are the following:

short name: the abbreviated name of the conference (optional).

name: the name of the conference or the name of the book as set by the editor.

date: the date(s) of the conference.

venue: the place of the conference.

Examples:

```
\acmConference[TD'15]{Technical Data Conference}{November  
12--16}{Dallas, TX, USA}  
\acmConference{SA'15 Art Papers}{November 02--06, 2015}{Kobe, Japan}
```

Normally this command is entered either by the editor or by the typesetter.

\title The command \title, as in amsart class, has two arguments: one optional, and one mandatory:

```
\title[ShortTitle]{FullTitle}
```

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

It is expected that this command is inserted by the author of the manuscript.

\subtitle Besides title, ACM classes allow subtitle, set with the \subtitle{*subtitle*} macro.

The commands for specification of authors are highly structured. The reason is, they serve double duty: the authors' information is typeset in the manuscript, and is used by the metadata extraction tools for indexing and cataloguing. Therefore it is very important to follow the guidelines exactly.

\author The basic commands are \author, \orcid (for the researchers registered with ORCID, <http://www.orcid.org/>), \affiliation and \email. In the simplest case you enter them in this order:

```
\author{...}  
\orcid{...}  
\affiliation{...}  
\email{...}
```

Do *not* use L^AT_EX \and macro! Each author deserves his or her own \author command.

Note that some formats do not typeset e-mails or ORCID identifiers. Do not worry: metadata tools will get them.

Sometimes an author has several affiliations. In this case the \affiliation command should be repeated:

```
\author{...}  
\orcid{...}
```

```
\affiliation{...}
\affiliation{...}
\email{...}
```

Similarly you can repeat \email command.

You may have several authors with the same affiliation, different affiliations or overlapping affiliations (author A_1 is affiliated with institutions I_1 and I_2 , while author A_2 is affiliated with I_2 only, and author A_3 is affiliated with I_1 and I_3 , ...). The recommended solution is to put the \affiliation commands after each author, possibly repeating them:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
```

In some cases when several authors share the same affiliation you may try to save the space using the format

```
\author{...}
\email{...}
\author{...}
\email{...}
\affiliation{...}
```

However, this format is not generally recommended.

\additionalaffiliation

In some cases too many affiliations take too much space. The command \additionalaffiliation{<affiliation>} creates a footnote after author's name with the words "Also with {<affiliation>}". You should use this command only as the last resort. An example of usage is:

```
\author{G. Tobin}
\author{Ben Trovato}
\additionalaffiliation{%
    \institution{The Th{\o}rv{\\"a}ld Group}
    \streetaddress{1 Th{\o}rv{\\"a}ld Circle}
    \city{Hekla}
    \country{Iceland}}
\affiliation{%
```

```

    \institution{Institute for Clarity in Documentation}
    \streetaddress{P.O. Box 1212}
    \city{Dublin}
    \state{Ohio}
    \postcode{43017-6221}
}

```

Here Trovato and Tobin share their affiliation with the Institute for Clarity in Documentation, but only Ben Trovato is affiliated with The Thørváld Group.

```

\position
\institution
\department
\streetaddress
\city
\state
\postcode
\country

```

The `\affiliation` and `\additionalaffiliation` commands are further structured to interact with the metadata extraction tools. Inside the `this` command you should use `\position`, `\institution`, `\department`, `\city`, `\streetaddress`, `\state`, `\postcode` and `\country` macros to indicate the corresponding parts of the affiliation. Note that in some cases (for example, journals) these parts are not printed in the resulting copy, but they *are* necessary since they are used by the XML metadata extraction programs. Do *not* put commas or `\` between the elements of `\affiliation`: they will be provided automatically.

An example of the author block:

```

\author{A. U. Thor}
\orcid{1234-4564-1234-4565}
\affiliation{%
    \institution{University of New South Wales}
    \department{School of Biomedical Engineering}
    \streetaddress{Samuels Building (F25), Kensington Campus}
    \city{Sidney}
    \state{NSW}
    \postcode{2052}
    \country{Australia}}
\email{author@nsw.au.edu}
\author{A. N. Other}
\affiliation{%
    \institution{University of New South Wales}
    \city{Sidney}
    \state{NSW}
    \country{Australia}}
\author{C. O. Respondent}
\orcid{1234-4565-4564-1234}
\affiliation{%
    \institution{University of Pennsylvania}
    \city{Philadelphia}
    \state{PA}
    \country{USA}}
\affiliation{%
    \institution{University of New South Wales}
    \city{Sidney}
    \state{NSW}
    \country{Australia}}

```

Note that old ACM conference formats did not allow for more than six authors and required some efforts from the authors to achieve alignment. The new format is much better in this.

Sometimes an author works in several departments within the same institution. There could be two situations: the departments are independent, or one department is within another. In the first case just repeat the command \department several times. To handle the second case the command has an optional numerical parameter. The departments with higher numbers are higher in the organizational chart. Compare

```
\affiliation{%
\department[0]{Department of Lunar Studies} % 0 is the default
\department[1]{John Doe Institute} % higher than 0
\institution{University of San Serriffe}
\country{San Serriffe}}
```

and

```
\affiliation{%
\department{Department of Lunar Studies} % Not within JD Inst!
\department{John Doe Institute}
\institution{University of San Serriffe}
\country{San Serriffe}}
```

The command \affiliation formats the output according to American conventions. This might be wrong for some cases. Consider, for example, a German address. In Germany postcode is put before city and is not separated by a comma. We can handle this order using

```
\affiliation{%
\institution{Fluginstitut}
\streetaddress{Sonnenallee 17}
\postcode{123456}
\city{Helm}
\country{Germany}
}
```

However, the comma after postcode is unfortunate: the address will be typeset (with a SIG format) as

```
Fluginstitut
Sonenallee 17
123456, Helm, Germany
```

To overcome this problem, the command \affiliation has an optional parameter `obeypunctuation`, which can be false (the default) or true. If this parameter is true, \affiliation obeys the author's command. Thus

```
\affiliation[obeypunctuation=true]{%
  \institution{Fluginstitut} \\
  \streetaddress{Sonnenallee 17} \\
  \postcode{123456} \\
  \city{Helm}, \\
  \country{Germany}
}
```

will be typeset as

```
Fluginstitut
Sonnenallee 17
123456 Helm, Germany
```

Note that you should *not* use this option for journals.

It is expected that these commands are inserted by the author of the manuscript.

\thanks Like amsart (and unlike standard L^AT_EX), we allow \thanks only *outside* of commands \title and \author. Example:

```
\thanks{This work is supported by the Widget Corporation Grant
  \#312-001. \\
  Author's address: D. Pineo, Kingsbury Hall, 33 Academic Way, Durham,
  N.H. 03824; email: dspineo@comcast.net; Colin Ware, Jere A. Chase
  Ocean Engineering Lab, 24 Colovos Road, Durham, NH 03824; email:
  cware@ccom.unh.edu;
  Sean Fogarty, (Current address) NASA Ames Research Center, Moffett
  Field, California 94035.}
```

It is expected that this command is inserted by the author of the manuscript.

\titlenote While the command \thanks generates a note without footnote mark, sometimes the authors might need notes more tightly connected to the title, subtitle or author. The commands \titlenote, \subtitlenote and \authornote that follow the corresponding commands (\title, \subtitle and \author) generate such notes, for example

```
\title{This is a title}
\titlenote{This is a titlenote}
\author{A. U. Thor}
\authornote{This is an authornote}
```

Please never use \footnotes inside \author or \title commands, since this confuses metadata extraction software (actually these commands now produce errors).

\acmVolume The macros \acmVolume, \acmNumber, \acmArticle, \acmYear and \acmMonth are \acmNumber inserted by the editor and set the journal volume, issue, article number, year and month \acmArticle correspondingly. The arguments of all these commands, including \acmMonth is numerical, including \acmMonth, for example,

```
\acmVolume{9}
```

```
\acmNumber{4}
\acmArticle{39}
\acmYear{2010}
\acmMonth{3}
```

\acmArticleSeq The articles in the same issue of a journal have a *sequential number*. It is used to vertically position the black blob in some formats. By default it is the same as article number, but the command \acmArticleSeq{*n*} can be used to change it:

```
\acmArticle{39} % The sequence number will be 39 by default
\acmArticleSeq{5} % We redefine it to 5
```

\acmSubmissionID If your paper got a Submission ID from the Conference Management System, put it here:

```
\acmSubmissionID{123-A56-BU3}
```

\acmPrice The macro \acmPrice{*price*} sets the price for the article
\acmPrice{25.00}

Note that you do not need to put the dollar sign here, just the amount. By default the price is \$15.00, unless the copyright is set to usgov or rightsretained, when it is suppressed. Note that to override the defaults you need to set the price *after* the \setcopyright command to override the default. Also, the command \acmPrice{} suppresses the printing of the price.

\acmISBN Book-like volumes have ISBN numbers attached to them. The macro \acmISBN{*ISBN*} sets it. Normally it is set by the typesetter, for example,

```
\acmISBN{978-1-4503-3916-2}
```

\acmDOI The macro \acmDOI{*DOI*} sets the DOI number of the article, for example,
\acmDOI{10.1145/9999997.9999999}

It is normally set by the typesetter.

\acmBadgeR
\acmBadgeL Some conference articles get special distinction, for example, the artifact evaluation for PPoPP 2016 (see <http://ctuning.org/ae/ppopp2016.html>). These articles display special badges supplied by the conference organizers. The class provides commands to add these badges: \acmBadgeR[*url*]{*graphics*} and \acmBadgeL[*url*]{*graphics*}. The first command puts the badge to the right of the title, and the second one—to the left. The exception is the sigchi-a mode for SIGCHI Extended abstract, which puts the badges on the left margin. The arguments have the following meaning: [*url*], if provided, sets the link to the badge authority in the screen version, while {*graphics*} sets the graphics file with the badge image. The file must be a cropped square, which is

scaled to a standard size in the output. For example, if the badge image is ae-logo.pdf, the command is

```
\acmBadgeR[http://ctuning.org/ae/ppopp2016.html]{ae-logo}
```

\startPage The macro `\startPage{<page>}` sets the first page of the article in the journal or book. It is used by the typesetter.

\terms The command `\keywords{<keyword, keyword,...>}` sets keywords for the article. They must be separated by commas, for example,

```
\keywords{wireless sensor networks, media access control,  
multi-channel, radio interference, time synchronization}
```

CCSXML ACM publications are classified according to the ACM Computing Classification Scheme (CCS). CCS codes are used both in the typeset version of the publications *and* in the metadata in the various databases. Therefore you need to provide both `\TeX` commands and XML metadata with the paper.

The tool at <http://dl.acm.org/ccs.cfm> can be used to generate CCS codes. After you select the topics, click on “Generate CCS codes” to get the result like the following:

```
\begin{CCSXML}  
<ccs2012>  
  <concept>  
    <concept_id>10010520.10010553.10010562</concept_id>  
    <concept_desc>Computer systems organization~Embedded systems</concept_desc>  
    <concept_significance>500</concept_significance>  
  </concept>  
  <concept>  
    <concept_id>10010520.10010575.10010755</concept_id>  
    <concept_desc>Computer systems organization~Redundancy</concept_desc>  
    <concept_significance>300</concept_significance>  
  </concept>  
  <concept>  
    <concept_id>10010520.10010553.10010554</concept_id>  
    <concept_desc>Computer systems organization~Robotics</concept_desc>  
    <concept_significance>100</concept_significance>  
  </concept>  
  <concept>  
    <concept_id>10003033.10003083.10003095</concept_id>  
    <concept_desc>Networks~Network reliability</concept_desc>  
    <concept_significance>100</concept_significance>  
  </concept>  
</ccs2012>  
\end{CCSXML}  
  
\ccsdesc[500]{Computer systems organization~Embedded systems}  
\ccsdesc[300]{Computer systems organization~Redundancy}  
\ccsdesc{Computer systems organization~Robotics}
```

Table 4: Parameters for `\setcopyright` command

Parameter	Meaning
<code>none</code>	The copyright and permission information is not typeset (this is the option for some ACM conferences).
<code>acmcopyright</code>	The authors transfer the copyright to ACM (the “traditional” choice).
<code>acmlicensed</code>	The authors retain the copyright but license the publication rights to ACM.
<code>rightsretained</code>	The authors retain the copyright and publication rights to themselves or somebody else.
<code>usgov</code>	All the authors are employees of the US Government.
<code>usgovmixed</code>	Some authors are employees of the US Government.
<code>cagov</code>	All the authors are employees of the Canadian Government.
<code>cagovmixed</code>	Some authors are employees of the Canadian Government.

```
\ccsdesc[100]{Networks~Network reliability}
```

You need to just copy this code and paste it in your paper anywhere before `\maketitle`.

`\setcopyright` There are several possibilities for the copyright of the papers published by ACM: the authors may transfer the rights to ACM, license them to ACM, some or all authors might be employees of the US or Canada Government, etc. Accordingly the command `\setcopyright{...}` is introduced. Its argument is the copyright status of the paper, for example, `\setcopyright{acmcopyright}`. The possible values for this command are listed in Table 4.

The ACM submission software should generate the right command for you to paste into your file.

Each copyright statement must have the year of copyright. By default it is the same as `\acmYear`, but you can override this decision using the macro `\copyrightyear`, e.g.,

```
\acmYear{2016}
\copyrightyear{2015}
```

There is a special case for a personal copy that the authors may be allowed to generate for their use or a posting on a personal site (check the instructions for the specific journal or conference for the details). The document option `authorversion=true` produces the special form of the copyright statement for this case. Note that you still need the `\setcopyright` command and (optionally) `\copyrightyear` command to tell `\TeX` about the copyright owner and year. Also, you should be aware that due to the different sizes of the permission blocks for the printed version and authors’ version the page breaks might be different between them.

`\abstract` The environment `\abstract` must precede `\maketitle` command. Again, this is different from the standard `\TeX`.

Table 5: Settings for `\settopmatter` command

Parameter	Values	Meaning
<code>printccs</code>	true/false	Whether to print CCS categories
<code>printacmref</code>	true/false	Whether to print ACM bibliographic entry
<code>printfolios</code>	true/false	Whether to print page numbers (folios)

`teaserfigure` A special kind of figure is used for many two-column conference proceedings. This figure is placed just after the authors, but before the main text. The environment `teaserfigure` is used for these figures. This environment must be used *before* `\maketitle`, for example,

```
\begin{teaserfigure}
  \includegraphics[width=\textwidth]{sampleteaser}
  \caption{This is a teaser}
  \label{fig:teaser}
\end{teaserfigure}
```

`\settopmatter` Some information in the top matter is printed for certain journals or proceedings and suppressed for others. You may override these defaults using the command `\settopmatter{<settings>}`. The settings and their meanings are listed in Table 5. For example,

```
\settopmatter{printacmref=false, printccs=true, printfolios=true}
```

`\received` The command `\received[<stage>]{<date>}` sets the history of the publication. The `[<stage>]` argument is optional; the default is `Received` for the first date and `revised` for the subsequent ones. For example

```
\received{February 2007}
\received[revised]{March 2009}
\received[accepted]{June 2009}
```

`\maketitle` The macro `\maketitle` must be the last command in the top matter group: i.e., it must follow the commands defined in this section.
`\shortauthors` After the command `\maketitle` the macro `\shortauthors` stores the names of the authors for the running head. You may redefine it if the list of author's name is too long, e.g.,

```
\maketitle
\renewcommand{\shortauthors}{Zhou et al.}
```

2.4 Algorithms

There now several good packages for typesetting algorithms [3, 4, 5], and the authors are now free to choose their favorite one.

2.5 Figures and tables

New ACM styles use the standard L^AT_EX interface for figures and tables. There are some important items to be aware of, however.

1. The captions for figures must be entered *after* the figure bodies, and for the tables *before* the table bodies.

2. ACM uses the standard types for figures and types and adds several new ones. In total there are the following types:

figure, table: a standard figure or table, taking full text width in one-column formats and one column in two-column formats.

figure*, table* in two-column formats, a special figure or table taking full text width.

teaserfigure: a special figure before \maketitle.

sidebar, marginfigure, margitable: in the sigchi-a format, special sidebars, tables and figures on the margin.

3. Accordingly, when scaling the images, one should use the following sizes:

- (a) For figure in one-column mode, figure* in two-column mode or teaserfigure—\textwidth (in the one-column you can also use \columnwidth, which coincides with \textwidth in this case).
- (b) For figure in two-column mode—\columnwidth.
- (c) For marginfigure—\marginparwidth.
- (d) For figure* in SIGCHI Extended abstracts—\fulltextwidth.

It is strongly recommended to use the package booktabs [6] and follow its main principles of typography with respect to tables:

1. Never, ever use vertical rules.

2. Never use double rules.

It is also a good idea not to overuse horizontal rules.

For table *footnotes* you have several options described in TeX FAQ [1]. The simplest one is to use \minipage environment:

```
\begin{table}
\caption{Simulation Configuration}
\label{tab:conf}
\begin{minipage}{\columnwidth}
\begin{center}
\begin{tabular}{ll}
\toprule
TERRAIN\footnote{This is a table footnote. This is a table footnote. This is a table footnote.} &
\end{tabular}
\end{center}
\end{minipage}
```

```

(200\, ,m$\times$200\, ,m) Square\\
Node Number & 289\\
Node Placement & Uniform\\
Application & Many-to-Many/Gossip CBR Streams\\
Payload Size & 32 bytes\\
Routing Layer & GF\\
MAC Layer & CSMA/MMSN\\
Radio Layer & RADIO-ACCNOISE\\
Radio Bandwidth & 250Kbps\\
Radio Range & 20m--45m\\
\bottomrule
\end{tabular}
\end{center}
\bigskip
\footnotesize\emph{Source:} This is a table
sourcenote. This is a table sourcenote. This is a table
sourcenote.

\emph{Note:} This is a table footnote.
\end{minipage}
\end{table}

```

`sidebar` SIGCHI extended abstract extensively uses margin space. The package provides three environments for this with option captions:

sidebar: textual information on the margin

marginfigure: a figure on the margin

margintable: a table on the margin

Tables and figures (including margin tables and margin figures) are by default centered. However, in some cases (for example, when you use several subimages per figure) you may need to override this decision. A good way to do so is to put the contents into a `\minipage` of the width `\columnwidth`.

2.6 Theorems

ACM classes define two theorem styles and several pre-defined theorem environments:

acmplain: this is the style used for theorem, conjecture, proposition, lemma, and corollary, and

acmdefinition: this is the style used for example and definition.

2.7 Online-only and offline-only material

`printonly` Some supplementary material in ACM publication is put online, but not in the printed
`screenonly`

version. The text inside the environment `screenonly` will be typeset only when the option `screen` (see Section 2.2) is set to true. Conversely, the text inside the environment `printonly` is typeset only when this option is set to false. For example

```
\section{Supplementary materials}

\begin{printonly}
    This section is included in the online version of the paper.
\end{printonly}

\begin{screenonly}
    (The actual section).
\end{screenonly}
```

We use `comment` package for typesetting this code, so `\begin{...}` and `\end{...}` should start at the first positions of the lines of their own (no initial spaces etc.).

2.8 Note about anonymous mode

`anonsuppress` When the option `anonymous` is selected, TeX suppresses author information (including number of authors) for a blind review. However, sometimes the information identifying the authors may be present in the body of the paper

```
\begin{anonsuppress}
    This is the continuation of the previous work by the author
    \cite{prev1, prev2}.
\end{anonsuppress}
```

As for `printonly` and `screenonly` environments, `\begin{anonsuppress}` and `\end{anonsuppress}` should start the line of their own (no leading or trailing spaces).

2.9 Acknowledgments

The traditional “Acknowledgments” section is conventionally used to thank persons and granting agencies for their help and support. However, there are several important considerations about this section.

First, in the anonymous mode this section must be omitted: it gives too much information to the reviewers. Second, the data about the grants is extracted and stored separately by the postprocessing software. ACM classes provide facilities for both these tasks.

`acks` The environment `acks` starts an unnumbered section “Acknowledgments” unless the anonymous mode is chosen. Put all thanks inside this environment.

As for `printonly` and `screenonly` environments, `\begin{acks}` and `\end{acks}` should start the line of their own (no leading or trailing spaces).

`\grantsponsor` All the financial support *must* be listed using the commands `\grantsponsor` and `\grantnum`. These commands tell the postprocessing software about the granting organization and the grant. The format of the command is the following:

```
\grantsponsor{\langle sponsorID \rangle}{\langle name \rangle}{\langle url \rangle}
\grantnum[\langle url \rangle]{\langle sponsorID \rangle}{\langle number \rangle}.
```

Here $\{\langle sponsorID \rangle\}$ is the unique ID used to match grants to sponsors, $\{\langle name \rangle\}$ is the name of the sponsor, $\{\langle url \rangle\}$ is its URL, and $\{\langle number \rangle\}$ is the grant number. The $\{\langle sponsorID \rangle\}$ of the `\grantnum` command must correspond to `\sponsorID` of a `\grantsponsor` command. Some awards have their own web pages, which you can include using the optional argument of `\grantnum` command.

At present $\{\langle sponsorID \rangle\}$ is chosen by the authors and can be an arbitrary key, in the same way the label of `\cite` is arbitrarily chosen. There might be a change to this policy if ACM decides to create a global database of sponsoring organizations.

Example:

```
\begin{acks}
The authors would like to thank Dr. Yuhua Li for providing the
matlab code of the \textit{BEPS} method.

The authors would also like to thank the anonymous referees for
their valuable comments and helpful suggestions. The work is
supported by the \grantsponsor{GS501100001809}{National Natural
Science Foundation of
China}{\url{https://doi.org/10.13039/501100001809}} under Grant
No.: \grantnum{GS501100001809}{61273304}
and \grantnum[\url{http://www.nnsf.cn/youngscientsts}]{GS501100001809}{Young
Scientists' Support Program}.
\end{acks}
```

2.10 Bibliography

ACM uses the `natbib` package for formatting references and the style `ACM-Reference-Format.bst` for Bib_TE_X processing. You may disable loading of `natbib` by using the option `natbib=false` in `\documentclass`. However, it is not recommended, as well as the use of Bib_TE_X styles other than `ACM-Reference-Format.bst`, and may delay the processing of the manuscript.

`\citetstyle` If you use `natbib`, you can select one of two predefined citation styles: the author-year format `acmauthoryear` or the numeric format `acmnumeric` using the command `\citetstyle`, for example,

```
\citetstyle{acmauthoryear}
```

Note that numeric citations are the default mode for most formats.

`\setcitetstyle` You may further customize `natbib` using `\setcitetstyle` command, for example,

```
\setcitetstyle{numbers,sort&compress}
```

If you use `natbib`, then commands like `\citet` and `\citeauthor` are automatically supported. The command `\shortcite` is the same as `\cite` in numerical mode, and cites the year in the author-date mode.

There are several customized BIBTeX entries and fields in ACM style ACM-Reference-Format.
bst you may want to be aware of.

The style supports fields doi and url, for example,

```
doi = "10.1145/1188913.1188915",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.pdf",
```

The style supports arXiv recommended fields eprint and (optionally) primaryclass, for example,

```
eprint = "960935712",
primaryclass = "cs",
```

See the examples at <http://arxiv.org/hypertex/bibstyles/>.

There are special entries online and game for Web pages and games, for example,

```
@online{Thornburg01,
author = "Harry Thornburg",
year = "2001",
title = "Introduction to Bayesian Statistics",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.html",
month = mar,
lastaccessed = "March 2, 2005",
}
```

For these entries you can use the lastaccessed field to add the access date to the URL.

There are two ways to enter video and audio sources in the bibliography corresponding to two different possibilities. For standalone sources available on WWW you can use an online entry, setting there howpublished field, for example,

```
@online{Obama08,
author = "Barack Obama",
year = "2008",
title = "A more perfect union",
howpublished = "Video",
day = "5",
url = "http://video.google.com/videoplay?docid=6528042696351994555",
month = mar,
lastaccessed = "March 21, 2008",
}
```

For the sources available as attachments to conference proceedings and similar documents, you can use the usual inproceedings entry, again setting the howpublished field:

```
@Inproceedings{Novak03,
author = "Dave Novak",
```

```

title = "Solder man",
booktitle = "ACM SIGGRAPH 2003 Video Review on Animation theater Program",
year = "2003",
publisher = "ACM Press",
address = "New York, NY",
pages = "4",
month = "March 21, 2008",
doi = "10.9999/woot07-S422",
howpublished = "Video",
}

```

Sometimes you need to cite a complete issue of a journal. The entry `periodical` is intended for this:

```

@periodical{JCohen96,
key = "Cohen",
editor = "Jacques Cohen",
title = "Special issue: Digital Libraries",
journal = "Communications of the {ACM}",
volume = "39",
number = "11",
month = nov,
year = "1996",
}

```

2.11 Colors

While printed ACM publications are usually black and white, screen mode allows the use of colors. The ACM classes pre-define several colors according to [7]: `ACMBlue`, `ACMYellow`, `ACMOOrange`, `ACMRed`, `ACMLightBlue`, `ACMGreen`, `ACMPurple`, `ACMDarkBlue`. You can use them in the color assignments.

ACM provides the following recommendation on color use.

The most accessible approach would be to ensure that your article is still readable when printed in greyscale. The most notable reasons for this are:

1. The most common type of inherited Color Vision Deficiency (CVD) is red-green (in which similar-brightness colors that only differ in their amounts of red or green are often confused), and it affects up to 8% of males and 0.5% of females of Northern European descent.
2. The most common type of acquired Color Vision Deficiency (CVD) is blue-yellow (including mild cases for many older adults).
3. Most printing is in Black & White.
4. Situational impairments (e.g., bright sunlight shining on a mobile screen) tend to reduce the entire color gamut, reducing color discriminability.

Note: It is *not* safe to encode information using only variations in color (i.e., only differences in hue and/or saturation), as there is bound to be someone affected!

To ensure that you are using the most accessible colors, ACM recommends that you choose sets of colors to help ensure suitable variations in Black & White using either of the following tools:

1. ColourBrewer: <http://colorbrewer2.org/>
2. ACE: The Accessible Colour Evaluator: <http://daprlab.com/ace/> for designing WCAG 2.0 compliant palettes.

2.12 Other notable packages and typographic remarks

Several other packages are recommended for specialized tasks.

The package *subcaption* [8] is recommended for complex figures with several subplots or subfigures that require separate subcaptioning. The packages *nomencl* [9] and *glossaries* [10] can be used for the automatic creation of the lists of symbols and concepts used.

By default *acmart* prevents all widows and orphans (i.e. lonely lines at the beginning and the end of the page) and hyphenation at the end of the page. This is done by rather strict settings

```
\widowpenalty=10000  
\clubpenalty=10000  
\brokenpenalty=10000
```

However, this may lead to frustrating results when the authors must obey a page limit. Setting these penalties to smaller values may help if you absolutely need to.

Another problem might be the too strict line breaking rules. Again, a strategically placed *\sloppy* command or putting the problematic paragraph inside *sloppypar* environment might help—but beware the results might be, well, sloppy.

2.13 A note for wizards: *acmart-preload-hook.tex*

Sometimes you need to change the behavior of *acmart*. The usual way to do this is to redefine commands in the preamble. However, these definitions are executed *after* *acmart* is loaded, and certain decisions are made. This presents a number of problems.

For example, one may want to use *titletoc* package with *acmart*. This package should be loaded before *hyperref*. However, since *acmart* loads *hyperref* itself, the line *\usepackage{titletoc}* in the preamble will lead to grief (see <http://tex.stackexchange.com/questions/357265/using-titletoc-with-acm-acmart-style>).

Another example is passing options to package. Suppose you want to use *dvinames* option of *xcolor* package. Normally you cannot do this because *acmart* loads this package itself without options.

The file *acmart-preload-hook.tex* may be used to solve these problems. If this file exists, it will be processed before any other package. You can use this file to load packages or pass options to them. For example, if you put in this file

```
\let\LoadClassOrig\LoadClass
\renewcommand\LoadClass[2][]{{\LoadClassOrig[#1]{#2}}%
\usepackage{titletoc}}
```

then `titletoc` will be loaded before `hyperref`. If you put in this file

```
\PassOptionsToPackage{dvipsnames}{xcolor}
```

you will pass `dvipsnames` to `xcolor`.

Important note. This hook makes it too easy to create a manuscript which is not acceptable by ACM. Even easier it is to create a file which cannot be compiled. So please do not use it *unless you know what you are doing*. And if you use it, *do not ask for support*. If you decided to use this hook, you are on your own.

3 Implementation

3.1 Identification

We start with the declaration who we are. Most .dtx files put driver code in a separate driver file .drv. We roll this code into the main file, and use the pseudo-guard <gobble> for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 <*gobble>
3 \ProvidesFile{acmart.dtx}
4 </gobble>
5 <class>\ProvidesClass{acmart}
6 [2017/04/23 v1.35 Typesetting articles for Association of
7 Computing Machinery]
```

And the driver code:

```
8 <*gobble>
9 \documentclass{ltxdoc}
10 \usepackage{array,booktabs,amsmath,graphicx,fancyvrb,tabularx}
11 \usepackage[tt=false, type1=true]{libertine}
12 \usepackage[varqu]{zi4}
13 \usepackage[libertine]{newtxmath}
14 \usepackage[tableposition=top]{caption}
15 \usepackage{hypdoc}
16 \PageIndex
17 \CodelineIndex
18 \RecordChanges
19 \EnableCrossrefs
20 \begin{document}
21   \DocInput{acmart.dtx}
22 \end{document}
23 </gobble>
24 <*class>
25 \def\@classname{acmart}
```

3.2 Preload

We preload acmart-preload-hook:

```
26 \InputIfFileExists{acmart-preload-hook.tex}{%
27   \ClassWarning{\@classname}{%
28     I am loading acmart-preload-hook.tex. You are fully responsible
29     for any problems from now on.}}{}
```

3.3 Options

We need xkeyval since some of our options may have values:

```
30 \RequirePackage{xkeyval}
```

format The possible formats

```

31 \define@choicekey*+{acmart.cls}{format}[\ACM@format\ACM@format@nr]{%
32   manuscript, acmsmall, acmlarge, acmtog, sigconf, siggraph,
33   sigplan, sigchi, sigchi-a}[manuscript]{}{%
34   \ClassError{\@classname}{The option format must be manuscript,
35     acmsmall, acmlarge, acmtog, sigconf, siggraph,
36     sigplan, sigchi or sigchi-a}}
37 \def\@DeclareACMFormat#1{\DeclareOptionX{#1}{\setkeys{acmart.cls}{format=#1}}}
38 \@DeclareACMFormat{manuscript}
39 \@DeclareACMFormat{acmsmall}
40 \@DeclareACMFormat{acmlarge}
41 \@DeclareACMFormat{acmtog}
42 \@DeclareACMFormat{sigconf}
43 \@DeclareACMFormat{siggraph}
44 \@DeclareACMFormat{sigplan}
45 \@DeclareACMFormat{sigchi}
46 \@DeclareACMFormat{sigchi-a}
47 \ExecuteOptionsX{format}

\if@ACM@screen Whether we use screen mode
48 \define@boolkey+{acmart.cls}[@ACM@]{screen}[true]{%
49   \if@ACM@screen
50     \PackageInfo{\@classname}{Using screen mode}%
51   \else
52     \PackageInfo{\@classname}{Not using screen mode}%
53   \fi}{\PackageError{\@classname}{Option screen can be either true or
54     false}}
55 \ExecuteOptionsX{screen=false}

\if@ACM@review Whether we use review mode
56 \define@boolkey+{acmart.cls}[@ACM@]{review}[true]{%
57   \if@ACM@review
58     \PackageInfo{\@classname}{Using review mode}%
59   \else
60     \PackageInfo{\@classname}{Not using review mode}%
61   \fi}{\PackageError{\@classname}{Option review can be either true or
62     false}}
63 \ExecuteOptionsX{review=false}

\if@ACM@authorversion Whether we use author's version
64 \define@boolkey+{acmart.cls}[@ACM@]{authorversion}[true]{%
65   \if@ACM@authorversion
66     \PackageInfo{\@classname}{Using authorversion mode}%
67   \else
68     \PackageInfo{\@classname}{Not using authorversion mode}%
69   \fi}{\PackageError{\@classname}{Option authorversion can be either true or
70     false}}
71 \ExecuteOptionsX{authorversion=false}

\if@ACM@natbib@override

```

```

\if@ACM@natbib Whether we use natbib mode
72 \define@boolkey+{acmart.cls}[@ACM@]{natbib}[true]{%
73   \if@ACM@natbib
74     \PackageInfo{@classname}{Explicitly selecting natbib mode}%
75   \else
76     \PackageInfo{@classname}{Explicitly deselecting natbib mode}%
77   \fi}{\PackageError{@classname}{Option natbib can be either true or
78     false}}
79 \ExecuteOptionsX{natbib=true}

\if@ACM@anonymous Whether we use anonymous mode
80 \define@boolkey+{acmart.cls}[@ACM@]{anonymous}[true]{%
81   \if@ACM@anonymous
82     \PackageInfo{@classname}{Using anonymous mode}%
83   \else
84     \PackageInfo{@classname}{Not using anonymous mode}%
85   \fi}{\PackageError{@classname}{Option anonymous can be either true or
86     false}}
87 \ExecuteOptionsX{anonymous=false}

\if@ACM@timestamp Whether we use timestamp mode
88 \define@boolkey+{acmart.cls}[@ACM@]{timestamp}[true]{%
89   \if@ACM@timestamp
90     \PackageInfo{@classname}{Using timestamp mode}%
91   \else
92     \PackageInfo{@classname}{Not using timestamp mode}%
93   \fi}{\PackageError{@classname}{Option timestamp can be either true or
94     false}}
95 \ExecuteOptionsX{timestamp=false}

\if@ACM@authordraft Whether we use authordraft mode
96 \define@boolkey+{acmart.cls}[@ACM@]{authordraft}[true]{%
97   \if@ACM@authordraft
98     \PackageInfo{@classname}{Using authordraft mode}%
99     \@ACM@timestamptrue
100    \@ACM@reviewtrue
101  \else
102    \PackageInfo{@classname}{Not using authordraft mode}%
103  \fi}{\PackageError{@classname}{Option authordraft can be either true or
104    false}}
105 \ExecuteOptionsX{timestamp=false}

\ACM@fontsize The font size to pass to the base class
106 \def\ACM@fontsize{}
107 \DeclareOptionX{9pt}{\edef\ACM@fontsize{\CurrentOption}}
108 \DeclareOptionX{10pt}{\edef\ACM@fontsize{\CurrentOption}}
109 \DeclareOptionX{11pt}{\edef\ACM@fontsize{\CurrentOption}}
110 \DeclareOptionX{12pt}{\edef\ACM@fontsize{\CurrentOption}}

```

```

111 \DeclareOptionX{draft}{\PassOptionsToClass{\CurrentOption}{amsart}}
112 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
113 \ProcessOptionsX
114 \ClassInfo{\@classname}{Using format \ACM@format, number \ACM@format@nr}

```

3.4 Setting switches

- \if@ACM@manuscript Whether we use manuscript mode


```

115 \newif\if@ACM@manuscript

```
- \if@ACM@journal There are two kinds of publications: journals and books


```

116 \newif\if@ACM@journal

```
- \if@ACM@sigchiamode The formatting of SIGCHI abstracts is quite unusual. We have a special switch for them.


```

117 \newif\if@ACM@sigchiamode

```

Setting up switches

```

118 \ifnum\ACM@format@nr=5\relax % siggraph
119   \ClassWarning{@classname}{The format ‘siggraph’ is now obsolete.
120   I am switching to sigconf.}
121   \setkeys{acmart.cls}{format=sigconf}
122 \fi
123 \ifnum\ACM@format@nr=0\relax
124   \@ACM@manuscripttrue
125 \else
126   \@ACM@manuscriptfalse
127 \fi
128 \@ACM@sigchiamodefalse
129 \ifcase\ACM@format@nr
130 \relax % manuscript
131   \@ACM@journaltrue
132 \or % acmsmall
133   \@ACM@journaltrue
134 \or % acmlarge
135   \@ACM@journaltrue
136 \or % acmtog
137   \@ACM@journaltrue
138 \or % sigconf
139   \@ACM@journalfalse
140 \or % siggraph
141   \@ACM@journalfalse
142 \or % sigplan
143   \@ACM@journalfalse
144 \or % sigchi
145   \@ACM@journalfalse
146 \or % sigchi-a
147   \@ACM@journalfalse
148   \@ACM@sigchiamodetrue
149 \fi

```

3.5 Loading base class and package

At this point we either have `\ACM@fontsize`, or use defaults

```
150 \ifx\ACM@fontsize\empty
151   \ifcase\ACM@format@nr
152     \relax % manuscript
153     \def\ACM@fontsize{9pt}%
154   \or % acmsmall
155     \def\ACM@fontsize{10pt}%
156   \or % acmlarge
157     \def\ACM@fontsize{10pt}%
158   \or % acmtog
159     \def\ACM@fontsize{9pt}%
160   \or % sigconf
161     \def\ACM@fontsize{9pt}%
162   \or % siggraph
163     \def\ACM@fontsize{9pt}%
164   \or % sigplan
165     \def\ACM@fontsize{9pt}%
166   \or % sigchi
167     \def\ACM@fontsize{10pt}%
168   \or % sigchi-a
169     \def\ACM@fontsize{10pt}%
170   \fi
171 \fi
172 \ClassInfo{@classname}{Using fontsize \ACM@fontsize}
173 \LoadClass[\ACM@fontsize, reqno]{amsart}
174 \RequirePackage{microtype}
```

We need `totpages` package to calculate the number of pages

```
175 \RequirePackage{totpages}
```

The `amsmath` `\collect@body` is defined using `\def`. We load `environ` to access the `\long` version of the command

```
176 \RequirePackage{environ}
```

We use `setspace` for doublespacing

```
177 \if@ACM@manuscript
178 \RequirePackage{setspace}
179 \onehalfspacing
180 \fi
```

Citations. We patch `\setcitestyle` to allow, e.g., `\setcitestyle{sort}` and `\setcitestyle{nosort}`. We patch `\citetstyle` to warn about undefined citation styles.

```
181 \if@ACM@natbib
182   \RequirePackage{natbib}
183   \renewcommand{\bibsection}{%
184     \section*\{\refname\}%
185     \phantomsection\addcontentsline{toc}{section}{\refname}%
186   }
```

```

187 \renewcommand{\bibfont}{\bibliofont}
188 \renewcommand\setcitestyle[1]{
189   @for\@tempa:=#1\do
190     {\def\@tempb{round}\ifx\@tempa\@tempb
191       \renewcommand\NAT@open{}{\renewcommand\NAT@close{}}\fi
192     \def\@tempb{square}\ifx\@tempa\@tempb
193       \renewcommand\NAT@open[]{\renewcommand\NAT@close[]}\fi
194     \def\@tempb{angle}\ifx\@tempa\@tempb
195       \renewcommand\NAT@open{$< $}\renewcommand\NAT@close{$> $}\fi
196     \def\@tempb{curly}\ifx\@tempa\@tempb
197       \renewcommand\NAT@open{\{}{\renewcommand\NAT@close{\}}\fi
198     \def\@tempb{semicolon}\ifx\@tempa\@tempb
199       \renewcommand\NAT@sep{;}\fi
200     \def\@tempb{colon}\ifx\@tempa\@tempb
201       \renewcommand\NAT@sep{;}\fi
202     \def\@tempb{comma}\ifx\@tempa\@tempb
203       \renewcommand\NAT@sep{,}\fi
204     \def\@tempb{authoryear}\ifx\@tempa\@tempb
205       \NAT@numbersfalse\fi
206     \def\@tempb{numbers}\ifx\@tempa\@tempb
207       \NAT@numberstrue\NAT@superfalse\fi
208     \def\@tempb{super}\ifx\@tempa\@tempb
209       \NAT@numberstrue\NAT@supertrue\fi
210     \def\@tempb{nobibstyle}\ifx\@tempa\@tempb
211       \let\bibstyle=\@gobble\fi
212     \def\@tempb{bibstyle}\ifx\@tempa\@tempb
213       \let\bibstyle=\@citestyle\fi
214     \def\@tempb{sort}\ifx\@tempa\@tempb
215       \def\NAT@sort{\@ne}\fi
216     \def\@tempb{nosort}\ifx\@tempa\@tempb
217       \def\NAT@sort{\z@\fi
218     \def\@tempb{compress}\ifx\@tempa\@tempb
219       \def\NAT@cmprs{\@ne}\fi
220     \def\@tempb{nocompress}\ifx\@tempa\@tempb
221       \def\NAT@cmprs{\z@\fi
222     \def\@tempb{sort&compress}\ifx\@tempa\@tempb
223       \def\NAT@sort{\@ne}\def\NAT@cmprs{\@ne}\fi
224     \def\@tempb{mcite}\ifx\@tempa\@tempb
225       \let\NAT@merge\@ne\fi
226     \def\@tempb{merge}\ifx\@tempa\@tempb
227       @ifnum{\NAT@merge<\tw@}{\let\NAT@merge\tw@}{ }\fi
228     \def\@tempb{elide}\ifx\@tempa\@tempb
229       @ifnum{\NAT@merge<\thr@}{\let\NAT@merge\thr@}{ }\fi
230     \def\@tempb{longnamesfirst}\ifx\@tempa\@tempb
231       \NAT@longnamestrue\fi
232     \def\@tempb{nonamebreak}\ifx\@tempa\@tempb
233       \def\NAT@nmfmt#1{\mbox{\NAT@up#1}}\fi
234     \expandafter\NAT@find@eq\@tempa=\relax\@nil
235     \if\@tempc\relax\else
236       \expandafter\NAT@rem@eq\@tempc

```

```

237   \def\@tempb{open}\ifx\@tempa\@tempb
238     \xdef\NAT@open{\@tempc}\fi
239   \def\@tempb{close}\ifx\@tempa\@tempb
240     \xdef\NAT@close{\@tempc}\fi
241   \def\@tempb{aysep}\ifx\@tempa\@tempb
242     \xdef\NAT@aysep{\@tempc}\fi
243   \def\@tempb{yysep}\ifx\@tempa\@tempb
244     \xdef\NAT@yysep{\@tempc}\fi
245   \def\@tempb{notesep}\ifx\@tempa\@tempb
246     \xdef\NAT@cmt{\@tempc}\fi
247   \def\@tempb{citesep}\ifx\@tempa\@tempb
248     \xdef\NAT@sep{\@tempc}\fi
249   \fi
250 }%
251 \NAT@setcites
252 }
253 \renewcommand\citestyle[1]{%
254   \ifcsname bibstyle@\#1\endcsname%
255     \csname bibstyle@\#1\endcsname\let\bibstyle@gobble%
256   \else%
257     \@latex@error{Undefined '#1' citestyle}%
258   \fi
259 }%
260 \fi

```

\bibstyle@acmauthoryear The default author-year format:

```

261 \newcommand{\bibstyle@acmauthoryear}{%
262   \setcitestyle{%
263     authoryear,%
264     open={},close={},citesep={;},%
265     aysep={},yysep={,},%
266     notesep={, }}}

```

\bibstyle@acmnumeric The default numeric format:

```

267 \newcommand{\bibstyle@acmnumeric}{%
268   \setcitestyle{%
269     numbers,sort&compress,%
270     open={},close={},citesep={,},%
271     notesep={, }}}

```

The default is numeric:

```

272 \if@ACM@natbib
273 \citestyle{acmnumeric}
274 \fi

```

\@startsection Before we call hyperref, we redefine \startsection commands to their L^AT_EX defaults, since amsart ones are too AMS-specific. We need to do this early since we want hyperref to have a chance to redefine them again:

```

275 \def\@startsection#1#2#3#4#5#6{%

```

```

276 \if@noskipsec \leavevmode \fi
277 \par
278 \@tempskipa #4\relax
279 \@afterindenttrue
280 \ifdim \@tempskipa <\z@
281   \@tempskipa -\@tempskipa \@afterindentfalse
282 \fi
283 \if@nobreak
284   \everypar{}%
285 \else
286   \addpenalty\@secpenalty\addvspace\@tempskipa
287 \fi
288 \@ifstar
289   {\@ssect{\#3}{\#4}{\#5}{\#6}}%
290   {\@dblarg{\@sect{\#1}{\#2}{\#3}{\#4}{\#5}{\#6}}}
291 \def\@sect#1#2#3#4#5#6[#7]#8{%
292   \edef\@toclevel{\ifnum#2=\@m 0\else\number#2\fi}%
293   \ifnum #2>\c@secnumdepth
294     \let\@svsec\@empty
295   \else
296     \refstepcounter{\#1}%
297     \protected@edef\@svsec{\@secntformat{\#1}\relax}%
298   \fi
299   \@tempskipa #5\relax
300   \ifdim \@tempskipa>\z@
301     \begingroup
302       #6{%
303         \hangfrom{\hskip #3\relax\@svsec}%
304         \interlinepenalty \zM #8\@@par}%
305     \endgroup
306     \csname #1mark\endcsname{\#7}%
307   \ifnum #2>\c@secnumdepth \else
308     \tochangmeasure{\csname the#1\endcsname}%
309   \fi
310   \addcontentsline{toc}{\#1}{%
311     \ifnum #2>\c@secnumdepth \else
312       \protect\numberline{\csname the#1\endcsname}%
313     \fi
314     #7}%
315   \else
316     \def\@svsechd{%
317       #6{\hskip #3\relax
318       \@svsec #8}%
319       \csname #1mark\endcsname{\#7}%
320     \ifnum #2>\c@secnumdepth \else
321       \tochangmeasure{\csname the#1\endcsname\space}%
322     \fi
323     \addcontentsline{toc}{\#1}{%
324       \ifnum #2>\c@secnumdepth \else
325         \protect\numberline{\csname the#1\endcsname}%

```

```

326      \fi
327      #7} }%
328 \fi
329 \@xsect{#5}%
330 \def@\xsect#1{%
331   \tempskipa #1\relax
332   \ifdim \tempskipa>\z@
333     \par \nobreak
334     \vskip \tempskipa
335     \afterheading
336   \else
337     \nobreakfalse
338     \global\@noskipsectrue
339     \everypar{%
340       \if@noskipsec
341         \global\@noskipsecfalse
342         \setbox\z@\lastbox}%
343         \clubpenalty\@M
344         \begingroup \svsechd \endgroup
345         \unskip
346         \tempskipa #1\relax
347         \hskip -\tempskipa
348   \else
349     \clubpenalty \clubpenalty
350     \everypar{}%
351   \fi} }%
352 \fi
353 \ignorespaces}
354 \def@\secntformat#1{\csname the#1\endcsname\quad}
355 \def@\ssect#1#2#3#4#5{%
356   \tempskipa #3\relax
357   \ifdim \tempskipa>\z@
358     \begingroup
359     #4{%
360       \hangfrom{\hskip #1}%
361       \interlinepenalty \M#5\@par}%
362     \endgroup
363   \else
364     \def@\svsechd{#4{\hskip #1\relax #5}}%
365   \fi
366   \@xsect{#3}%

```

\@startsection Amsart redefines \startsection. Here we redefine it again to make TOC working

```

367 \def@\starttoc#1#2{\begingroup
368   \setTrue{#1}%
369   \par\removelastskip\vskip\z@skip
370   \startsection{section}\M\z@\{\linespacing\@plus\linespacing}%
371   {.5\linespacing}{\centering\contentsnamefont}{#2}%
372   \input{\jobname.#1}%
373   \if@filesw

```

```

374     \@xp\newwrite\csname tf@\#1\endcsname
375     \immediate\@xp\openout\csname tf@\#1\endcsname \jobname.\#1\relax
376   \fi
377   \global\nobreakfalse \endgroup
378   \addvspace{32\p@+\plus14\p@}%
379 }

\l@subsection Amsart has too large spacing
380 \def\l@subsection{\@tocline{2}{0pt}{1pc}{3pc}{}}

\l@subsubsection Amsart has too large spacing
381 \def\l@subsubsection{\@tocline{2}{0pt}{1pc}{5pc}{}}

      And hyperref
382 \let\@footnotemark@nolink\@footnotemark
383 \let\@footnotetext@nolink\@footnotetext
384 \RequirePackage[bookmarksnumbered,unicode]{hyperref}
385 \pdfstringdefDisableCommands{%
386   \def\unskip{}%
387   \def\textbullet{- }%
388   \def\textrightarrow{ -> }%
389   \def\footnotemark{}%
390 }
391 \urlstyle{rm}
392 \ifcase\ACM@format@nr
393 \relax % manuscript
394 \or % acmsmall
395 \or % acmlarge
396 \or % acmtog
397 \or % sigconf
398 \or % siggraph
399 \or % sigplan
400   \urlstyle{sf}
401 \or % sigchi
402 \or % sigchi-a
403   \urlstyle{sf}
404 \fi
405 \if@ACM@screen
406   \hypersetup{colorlinks,
407     linkcolor=ACMRed,
408     citecolor=ACMPurple,
409     urlcolor=ACMDarkBlue,
410     filecolor=ACMDarkBlue}%
411 \else
412   \hypersetup{hidelinks}%
413 \fi

      Bibliography mangling.
414 \if@ACM@natbib
415   \let\citeN\cite

```

```

416 \let\cite\citet
417 \let\citeNP\citeauthor
418 \let\citeNN\citeyearpar
419 \let\citeyearNP\citeyear
420 \let\citeyear\citeyearpar
421 \let\citeNP\citealt
422 \DeclareRobustCommand{\citeA}
423   {\begingroup\nAT@swafalse
424     \let\nAT@ctype@ne\nAT@partrue\nAT@fullfalse\nAT@open\nAT@citetp}%
425 \providecommand{\newblock}{}}%
426 \else
427   \AtBeginDocument{%
428     \let\shortcite\cite%
429     \providecommand{\citename}[1]{#1}}%
430 \fi
431 \newcommand{\shortcite}[2][]{%
432   \ifNAT@numbers\cite[#1]{#2}\else\citeyear[#1]{#2}\fi}%

```

\bibliographystyle Amsart redefines \bibliographystyle since it prefers AMS bibliography. We turn it back to L^AT_EX definition:

```

433 \def\bibliographystyle#1{%
434   \ifx\@begindocumenthook\undefined\else
435     \expandafter\AtBeginDocument
436   \fi
437   {\if@filesw
438     \immediate\write\auxout{\string\bibstyle{#1}}%
439   \fi}%

```

Graphics and color

```
440 \RequirePackage{graphicx, xcolor}
```

We define ACM colors according to [7]:

```

441 \definecolor[named]{ACMBlue}{cmyk}{1,0.1,0,0.1}
442 \definecolor[named]{ACMYellow}{cmyk}{0,0.16,1,0}
443 \definecolor[named]{ACMOrange}{cmyk}{0,0.42,1,0.01}
444 \definecolor[named]{ACMRed}{cmyk}{0,0.90,0.86,0}
445 \definecolor[named]{ACMLightBlue}{cmyk}{0.49,0.01,0,0}
446 \definecolor[named]{ACMGreen}{cmyk}{0.20,0,1,0.19}
447 \definecolor[named]{ACMPurple}{cmyk}{0.55,1,0,0.15}
448 \definecolor[named]{ACMDarkBlue}{cmyk}{1,0.58,0,0.21}

```

Author draft mode

```

449 \if@ACM@authordraft
450   \RequirePackage{draftwatermark}
451   \SetWatermarkFontSize{0.5in}
452   \SetWatermarkColor[gray]{.9}
453   \SetWatermarkText{\parbox{12em}{\centering
454     Unpublished working draft\\
455     Not for distribution}}%
456 \fi

```

3.6 Paper size and paragraphing

We use `geometry` for dimensions. Note the presently margins do not depend on the font size option - maybe we will need to change this. See <https://github.com/borisveytsman/acmart/issues/5#issuecomment-272881329>.

```
457 \RequirePackage{geometry}
458 \ifcase\ACM@format@nr
459 \relax % manuscript
460   \geometry{letterpaper,head=13pt,
461   marginparwidth=6pc}%
462 \or % acmsmall
463   \geometry{twoside=true,
464     includeheadfoot, head=13pt, foot=2pc,
465     paperwidth=6.75in, paperheight=10in,
466     top=58pt, bottom=44pt, inner=46pt, outer=46pt,
467     marginparwidth=2pc
468   }%
469 \or % acmlarge
470   \geometry{twoside=true, head=13pt, foot=2pc,
471     paperwidth=8.5in, paperheight=11in,
472     includeheadfoot,
473     top=78pt, bottom=114pt, inner=81pt, outer=81pt,
474     marginparwidth=4pc
475   }%
476 \or % acmtog
477   \geometry{twoside=true, head=13pt, foot=2pc,
478     paperwidth=8.5in, paperheight=11in,
479     includeheadfoot, columnsep=24pt,
480     top=52pt, bottom=75pt, inner=52pt, outer=52pt,
481     marginparwidth=2pc
482   }%
483 \or % sigconf
484   \geometry{twoside=true, head=13pt,
485     paperwidth=8.5in, paperheight=11in,
486     includeheadfoot, columnsep=2pc,
487     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
488     marginparwidth=2pc
489   }%
490 \or % siggraph
491   \geometry{twoside=true, head=13pt,
492     paperwidth=8.5in, paperheight=11in,
493     includeheadfoot, columnsep=2pc,
494     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
495     marginparwidth=2pc
496   }%
497 \or % sigplan
498   \geometry{twoside=true, head=13pt,
499     paperwidth=8.5in, paperheight=11in,
500     includeheadfoot=false, columnsep=2pc,
501     top=1in, bottom=1in, inner=0.75in, outer=0.75in,
```

```

502     marginparwidth=2pc
503     }%
504 \or % sigchi
505   \geometry{twoside=true, head=13pt,
506   paperwidth=8.5in, paperheight=11in,
507   includeheadfoot, columnsep=2pc,
508   top=66pt, bottom=73pt, inner=54pt, outer=54pt,
509   marginparwidth=2pc
510   }%
511 \or % sigchi-a
512   \geometry{twoside=false, head=13pt,
513   paperwidth=11in, paperheight=8.5in,
514   includeheadfoot, marginparsep=72pt,
515   marginparwidth=170pt, columnsep=20pt,
516   top=72pt, bottom=72pt, left=314pt, right=72pt
517   }%
518   \mparswitchfalse
519   \reversemarginpar
520 \fi

```

\parindent Paragraphing

```

\parskip 521 \setlength\parindent{10\p@}
522 \setlength\parskip{\z@}
523 \ifcase\ACM@format@nr
524 \relax % manuscript
525 \or % acmsmall
526 \or % acmlarge
527 \or % acmtog
528   \setlength\parindent{9\p@}%
529 \or % sigconf
530 \or % siggraph
531 \or % sigplan
532 \or % sigchi
533 \or % sigchi-a
534 \fi

```

Footnotes require some consideration. We have several layers of footnotes: front-matter footnotes, “regular” footnotes and the special insert for bibstrip. In the old ACM classes bibstrip was a \@float. The problem with floats is that they tend to, well, float—and we want the guarantee they stay.

We use *manyfoot* for layered footnotes instead.

\copyrightpermissionfootnoterule This is the footnote rule that separates bibstrip from the rest of the paper. It is a full width rule.

```

535 \def\copyrightpermissionfootnoterule{\kern-3\p@
536   \hrule \width \columnwidth \kern 2.6\p@}

537 \RequirePackage{manyfoot}
538 \SelectFootnoteRule[2]{copyrightpermission}
539 \DeclareNewFootnote{copyrightpermission}

```

```

\footnoterule Tschichold's rules:
540 \def\footnoterule{\kern-3\p@
541   \hrule \width 4pc \kern 2.6\p@}

\endminipage We do not use footnote rules in minipages
542 \def\endminipage{%
543   \par
544   \unskip
545   \ifvoid\@mpfootins\else
546     \vskip\skip\@mpfootins
547     \normalcolor
548     \unvbox\@mpfootins
549   \fi
550   \color@endgroup %% added 24 May 89
551 \color@endgroup
552 \egroup
553 \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}\}

\@makefntext We do note use indentation for footnotes
554 \def\@makefntext{\noindent\@makefnmark}

\@footnotetext In sigchi-a mode our footnotes are on the margins!
555 \if@ACM@\sigchiamode
556 \long\def\@footnotetext#1{\marginpar{%
557   \reset@font\small
558   \interlinepenalty\interfootnotelinepenalty
559   \protected@edef\@currentlabel{%
560     \csname p@footnote\endcsname\@thefnmark
561   }%
562   \color@begingroup
563   \color@begingroup%
564   \rule{z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
565   \color@endgroup}}%
566 \fi

\@mpfootnotetext We want the footnotes in minipages centered:
567 \long\def\@mpfootnotetext#1{%
568   \global\setbox\@mpfootins\vbox{%
569     \unvbox\@mpfootins
570     \reset@font\footnotesize
571     \hsize\columnwidth
572     \parboxrestore
573     \protected@edef\@currentlabel
574       {\csname p@mpfootnote\endcsname\@thefnmark}%
575     \color@begingroup\centering
576     \color@begingroup%
577     \rule{z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
578     \color@endgroup}}%

```

```

\@makefnmark  AMS classes use a buggy definition of \makefnmark. We revert to the standard one.
579 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}

\@textbottom Added some stretch according to David Carlisle's advice at http://tex.stackexchange.com/a/62318/5522
580 \def\@textbottom{\vskip \z@ \plus 1pt}
581 \let\@texttop\relax

```

3.7 Fonts

Somewhat PDFTeX and XeTeX require different incantations to make PDF compliant with the current Acrobat bugs. Xpdf is much better.

```

582 \RequirePackage{iftex}
583 \ifPDFTeX
584 \input{glyptounicode}
585 \pdfgentounicode=1
586 \fi
587 \RequirePackage{cmap}

```

\if@ACM@newfonts Whether we load the new fonts

```

588 \newif\if@ACM@newfonts
589 \if@ACM@newfontstrue
590 \IfFileExists{libertine.sty}{}{\ClassWarning{\classname}{You do not
591     have libertine package installed. Please upgrade your
592     TeX}\@ACM@newfontsfalse}
593 \IfFileExists{zi4.sty}{}{\ClassWarning{\classname}{You do not
594     have zi4 package installed. Please upgrade your TeX}\@ACM@newfontsfalse}
595 \IfFileExists{newtxmath.sty}{}{\ClassWarning{\classname}{You do not
596     have newtxmath package installed. Please upgrade your
597     TeX}\@ACM@newfontsfalse}

```

We use Libertine throughout.

```

598 \if@ACM@newfonts
599 \RequirePackage[tt=false, type1=true]{libertine}
600 \RequirePackage[varqu]{zi4}
601 \RequirePackage[libertine]{newtxmath}
602 \RequirePackage[T1]{fontenc}
603 \fi

```

The SIGCHI extended abstracts are sans serif:

```

604 \if@ACM@sigchiamode
605   \renewcommand{\familydefault}{\sfdefault}
606 \fi

```

3.8 Floats

We use caption package

```

607 \RequirePackage{caption, float}
608 \captionsetup[table]{position=top}

```

```

609 \if@ACM@journal
610   \captionsetup{labelfont={sf, small},
611     textfont={sf, small}, margin=\z@}
612   \captionsetup[figure]{name={Fig.}}
613 \else
614   \captionsetup{labelfont={bf},
615     textfont={bf}, labelsep=colon, margin=\z@}
616 \ifcase\ACM@format@nr
617   \relax % manuscript
618   \or % acmsmall
619   \or % acmlarge
620   \or % acmtog
621   \or % sigconf
622   \or % siggraph
623     \captionsetup{textfont={it}}
624   \or % sigplan
625     \captionsetup{labelfont={bf},
626       textfont={normalfont}, labelsep=period, margin=\z@}
627   \or % sigchi
628     \captionsetup[figure]{labelfont={bf, small},
629       textfont={bf, small}}
630   \or % sigchi-a
631     \captionsetup[figure]{labelfont={bf, small},
632       textfont={bf, small}}
633 \fi
634 \fi

```

sidebar The sidebar environment:

```

635 \newfloat{sidebar}{}{sbar}
636 \floatname{sidebar}{Sidebar}
637 \renewenvironment{sidebar}{\Collect@Body\@sidebar}{}

```

\@sidebar The processing of the saved text

```

638 \long\def\@sidebar#1{\bgroup\captionsetup{type=sidebar}%
639   \marginpar{\small#1}\egroup}

```

marginfigure The marginfigure environment:

```

640 \newenvironment{marginfigure}{\Collect@Body\@marginfigure}{}

```

\@marginfigure The processing of the saved text

```

641 \long\def\@marginfigure#1{\bgroup\captionsetup{type=figure}%
642   \marginpar{\centering\small#1}\egroup}

```

margintable The margintable environment:

```

643 \newenvironment{margintable}{\Collect@Body\@margintable}{}

```

\@margintable The processing of the saved text

```

644 \long\def\@margintable#1{\bgroup\captionsetup{type=table}%
645   \marginpar{\centering\small#1}\egroup}

```

SIGCHI extended abstract provides an interesting possibility to push into the margin.
Here we use `figure*` and `table*` for this.

`\fulltextwidth` We define the width of the boxes as
646 `\newdimen\fulltextwidth`
647 `\fulltextwidth=\dimexpr(\textwidth+\marginparwidth+\marginparsep)`

`\@dblfloat` We redefine the double float command. First, we make the size bigger. Second, our default position is going to be `tp` (to give marginalia a chance)
648 `\if@ACM@sigchiamode`
649 `\def\@dblfloat{\bgroup\columnwidth=\fulltextwidth`
650 `\let\@endfloatbox\@endwidefloatbox`
651 `\def\fpsadddefault{\def\fps{tp}}%`
652 `\@float}`
653 `\fi`

`\end@dblfloat` And the end. Just adding a `\bgroup`.
654 `\if@ACM@sigchiamode`
655 `\def\end@dblfloat{%`
656 `\end@float\egroup}`
657 `\fi`

`\@endwidefloatbox` This is the end of a wide box - we basically move everything to the left
658 `\def\@endwidefloatbox{%`
659 `\par\vskip\z@skip`
660 `\@minipagemodefalse`
661 `\outer\nobreak`
662 `\egroup`
663 `\color@endbox`
664 `\global\setbox\@currbox=\vbox{\moveleft`
665 `\dimexpr(\fulltextwidth-\textwidth)\box\@currbox}%`
666 `\wd\@currbox=\textwidth`
667 `}`

3.9 Lists

```
668 \ifcase\ACM@format@nr
669 \relax % manuscript
670 \or % acmsmall
671 \or % acmlarge
672 \or % acmtog
673 \or % sigconf
674 \or % siggraph
675 \or % sigplan
676 \def\labelenumi{\theenumi.}
677 \def\labelenumii{\theenumii.}
678 \def\labelenumiii{\theenumiii.}
679 \def\labelenumiv{\theenumiv.}
680 \or % sigchi
```

```

681 \or % sigchi-a
682 \fi

\descriptionlabel We do not use default colon as \amsart does:
683 \renewcommand{\descriptionlabel}[1]{\hspace\labelsep \upshape\bfseries #1}

\description AMS uses additional indent of 6pt. Frank recommends dropping it.
684 \renewenvironment{description}{\list{}{%
685   \itemindent-12\p@
686   \labelwidth\z@ \let\makelabel\descriptionlabel}%
687 }{%
688   \endlist
689 }
690 \let\enddescription=\endlist % for efficiency

```

3.10 Top matter data

We use keyval interface to define journal title and relevant information

```

691 \define@choicekey*+{ACM}{acmJournal}[\@journalCode\@journalCode@nr]{%
692   CIE,%
693   CSUR,%
694   IMWUT,%
695   JACM,%
696   JDIQ,%
697   JEA,%
698   JERIC,%
699   JETC,%
700   JOCCH,%
701   PACMPL,%
702   POMACS,%
703   TAAS,%
704   TACCESS,%
705   TACO,%
706   TALG,%
707   TALLIP,%
708   TAP,%
709   TCPS,%
710   TEAC,%
711   TECS,%
712   TIIS,%
713   TISSEC,%
714   TIST,%
715   TKDD,%
716   TMIS,%
717   TOCE,%
718   TOCHI,%
719   TOCL,%
720   TOCS,%
721   TOCT,%

```

```

722 TODAES,%
723 TODS,%
724 TOG,%
725 TOIS,%
726 TOIT,%
727 TOMACS,%
728 TOMM,%
729 TOMPECS,%
730 TOMS,%
731 TOPC,%
732 TOPS,%
733 TOPLAS,%
734 TOS,%
735 TOSEM,%
736 TOSN,%
737 TRETS,%
738 TSAS,%
739 TSC,%
740 TSLP,%
741 TWEB%
742 }{%
743 \ifcase\@journalCode@nr
744 \relax % CIE
745 \def\@journalName{ACM Computers in Entertainment}%
746 \def\@journalNameShort{ACM Comput. Entertain.}%
747 \def\@permissionCodeOne{1544-3574}%
748 \or % CSUR
749 \def\@journalName{ACM Computing Surveys}%
750 \def\@journalNameShort{ACM Comput. Surv.}%
751 \def\@permissionCodeOne{0360-0300}%
752 \or % IMWUT
753 \def\@journalName{Proceedings of the ACM on Interactive, Mobile,
754 Wearable and Ubiquitous Technologies}%
755 \def\@journalNameShort{Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.}%
756 \def\@permissionCodeOne{2474-9567}%
757 \or % JACM
758 \def\@journalName{Journal of the ACM}%
759 \def\@journalNameShort{J. ACM}%
760 \def\@permissionCodeOne{0004-5411}%
761 \or % JDIQ
762 \def\@journalName{ACM Journal of Data and Information Quality}%
763 \def\@journalNameShort{ACM J. Data Inform. Quality}%
764 \def\@permissionCodeOne{1936-1955}%
765 \or % JEA
766 \def\@journalName{ACM Journal of Experimental Algorithms}%
767 \def\@journalNameShort{ACM J. Exp. Algor.}%
768 \def\@permissionCodeOne{1084-6654}%
769 \or % JERIC
770 \def\@journalName{ACM Journal of Educational Resources in Computing}%
771 \def\@journalNameShort{ACM J. Edu. Resources in Comput.}%

```

```

772 \def \@permissionCodeOne{1073-0516}%
773 \or % JETC
774 \def \@journalName{ACM Journal on Emerging Technologies in Computing Systems}%
775 \def \@journalNameShort{ACM J. Emerg. Technol. Comput. Syst.}%
776 \def \@permissionCodeOne{1550-4832}%
777 \or % JOCCH
778 \def \@journalName{ACM Journal on Computing and Cultural Heritage}%
779 \def \@journalName{ACM J. Comput. Cult. Herit.}%
780 \or % PACMPL
781 \def \@journalName{Proceedings of the ACM on Programming Languages}%
782 \def \@journalName{Proc. ACM Program. Lang.}%
783 \def \@permissionCodeOne{2475-1421}%
784 \or % POMACS
785 \def \@journalName{Proceedings of the ACM on Measurement and Analysis of Computing Systems}%
786 \def \@journalName{Proc. ACM Meas. Anal. Comput. Syst.}%
787 \def \@permissionCodeOne{2476-1249}%
788 \or % TAAS
789 \def \@journalName{ACM Transactions on Autonomous and Adaptive Systems}%
790 \def \@journalNameShort{ACM Trans. Autonom. Adapt. Syst.}%
791 \def \@permissionCodeOne{1556-4665}%
792 \or % TACCESS
793 \def \@journalName{ACM Transactions on Accessible Computing}%
794 \def \@journalNameShort{ACM Trans. Access. Comput.}%
795 \def \@permissionCodeOne{1936-7228}%
796 \or % TACO
797 \def \@journalName{ACM Transactions on Architecture and Code Optimization}%
798 \or % TALG
799 \def \@journalName{ACM Transactions on Algorithms}%
800 \def \@journalNameShort{ACM Trans. Algor.}%
801 \def \@permissionCodeOne{1549-6325}%
802 \or % TALLIP
803 \def \@journalName{ACM Transactions on Asian and Low-Resource Language Information Processing}%
804 \def \@journalNameShort{ACM Trans. Asian Low-Resour. Lang. Inf. Process.}%
805 \def \@permissionCodeOne{2375-4699}%
806 \or % TAP
807 \def \@journalName{ACM Transactions on Applied Perception}%
808 \or % TCPS
809 \def \@journalName{ACM Transactions on Cyber-Physical Systems}%
810 \or % TEAC
811 \def \@journalName{ACM Transactions on Economics and Computation}%
812 \or % TECS
813 \def \@journalName{ACM Transactions on Embedded Computing Systems}%
814 \def \@journalNameShort{ACM Trans. Embedd. Comput. Syst.}%
815 \def \@permissionCodeOne{1539-9087}%
816 \or % TIIS
817 \def \@journalName{ACM Transactions on Interactive Intelligent Systems}%
818 \def \@journalNameShort{ACM Trans. Interact. Intell. Syst.}%
819 \def \@permissionCodeOne{2160-6455}%
820 \or % TISSEC
821 \def \@journalName{ACM Transactions on Information and System Security}%

```

```

822 \def \@journalNameShort{ACM Trans. Info. Syst. Sec.}%
823 \def \@permissionCodeOne{1094-9224}%
824 \or % TIST
825 \def \@journalName{ACM Transactions on Intelligent Systems and Technology}%
826 \def \@journalNameShort{ACM Trans. Intell. Syst. Technol.}%
827 \def \@permissionCodeOne{2157-6904}%
828 \or % TKDD
829 \def \@journalName{ACM Transactions on Knowledge Discovery from Data}%
830 \def \@journalNameShort{ACM Trans. Knowl. Discov. Data.}%
831 \def \@permissionCodeOne{1556-4681}%
832 \or % TMIS
833 \def \@journalName{ACM Transactions on Management Information Systems}%
834 \def \@journalNameShort{ACM Trans. Manag. Inform. Syst.}%
835 \def \@permissionCodeOne{2158-656X}%
836 \or % TOCE
837 \def \@journalName{ACM Transactions on Computing Education}%
838 \def \@journalNameShort{ACM Trans. Comput. Educ.}%
839 \def \@permissionCodeOne{1946-6226}%
840 \or % TOCHI
841 \def \@journalName{ACM Transactions on Computer-Human Interaction}%
842 \def \@journalNameShort{ACM Trans. Comput.-Hum. Interact.}%
843 \def \@permissionCodeOne{1073-0516}%
844 \or % TOCL
845 \def \@journalName{ACM Transactions on Computational Logic}%
846 \def \@journalNameShort{ACM Trans. Comput. Logic}%
847 \def \@permissionCodeOne{1529-3785}%
848 \or % TOCS
849 \def \@journalName{ACM Transactions on Computer Systems}%
850 \def \@journalNameShort{ACM Trans. Comput. Syst.}%
851 \def \@permissionCodeOne{0734-2071}%
852 \or % TOCT
853 \def \@journalName{ACM Transactions on Computation Theory}%
854 \def \@journalNameShort{ACM Trans. Comput. Theory}%
855 \def \@permissionCodeOne{1942-3454}%
856 \or % TODAES
857 \def \@journalName{ACM Transactions on Design Automation of Electronic Systems}%
858 \def \@journalNameShort{ACM Trans. Des. Autom. Electron. Syst.}%
859 \def \@permissionCodeOne{1084-4309}%
860 \or % TODS
861 \def \@journalName{ACM Transactions on Database Systems}%
862 \def \@journalNameShort{ACM Trans. Datab. Syst.}%
863 \def \@permissionCodeOne{0362-5915}%
864 \or % TOG
865 \def \@journalName{ACM Transactions on Graphics}%
866 \def \@journalNameShort{ACM Trans. Graph.}%
867 \def \@permissionCodeOne{0730-0301}%
868 \or % TOIS
869 \def \@journalName{ACM Transactions on Information Systems}%
870 \def \@journalNameShort{ACM Transactions on Information Systems}%
871 \def \@permissionCodeOne{1046-8188}%

```

```

872 \or % TOIT
873   \def \@journalName{ACM Transactions on Internet Technology}%
874   \def \@journalNameShort{ACM Trans. Internet Technol.}%
875   \def \@permissionCodeOne{1533-5399}%
876 \or % TOMACS
877   \def \@journalName{ACM Transactions on Modeling and Computer Simulation}%
878   \def \@journalNameShort{ACM Trans. Modeling and Computer Simulation}%
879   \def \@journalNameShort{ACM Trans. Model. Comput. Simul.}%
880 \or % TOMM
881   \def \@journalName{ACM Transactions on Multimedia Computing, Communications and Applications}%
882   \def \@journalNameShort{ACM Trans. Multimedia Comput. Commun. Appl.}%
883   \def \@permissionCodeOne{1551-6857}%
884   \def \@permissionCodeTwo{0100}%
885 \or % TOMPECS
886   \def \@journalName{ACM Transactions on Modeling and Performance Evaluation of Computing Systems}%
887   \def \@journalNameShort{ACM Trans. Model. Perform. Eval. Comput. Syst.}%
888   \def \@permissionCodeOne{2376-3639}%
889 \or % TOMS
890   \def \@journalName{ACM Transactions on Mathematical Software}%
891   \def \@journalNameShort{ACM Trans. Math. Softw.}%
892   \def \@permissionCodeOne{0098-3500}%
893 \or % TOPC
894   \def \@journalName{ACM Transactions on Parallel Computing}%
895   \def \@journalNameShort{ACM Trans. Parallel Comput.}%
896   \def \@permissionCodeOne{1539-9087}%
897 \or % TOPS
898   \def \@journalName{ACM Transactions on Privacy and Security}%
899   \def \@journalNameShort{ACM Trans. Priv. Sec.}%
900   \def \@permissionCodeOne{2471-2566}%
901 \or % TOPLAS
902   \def \@journalName{ACM Transactions on Programming Languages and Systems}%
903   \def \@journalNameShort{ACM Trans. Program. Lang. Syst.}%
904   \def \@permissionCodeOne{0164-0925}%
905 \or % TOS
906   \def \@journalName{ACM Transactions on Storage}%
907   \def \@journalNameShort{ACM Trans. Storage}%
908   \def \@permissionCodeOne{1553-3077}%
909 \or % TOSEM
910   \def \@journalName{ACM Transactions on Software Engineering and Methodology}%
911   \def \@journalNameShort{ACM Trans. Softw. Eng. Methodol.}%
912   \def \@permissionCodeOne{1049-331X}%
913 \or % TOSN
914   \def \@journalName{ACM Transactions on Sensor Networks}%
915   \def \@journalNameShort{ACM Trans. Sensor Netw.}%
916   \def \@permissionCodeOne{1550-4859}%
917 \or % TRETS
918   \def \@journalName{ACM Transactions on Reconfigurable Technology and Systems}%
919   \def \@journalNameShort{ACM Trans. Reconfig. Technol. Syst.}%
920   \def \@permissionCodeOne{1936-7406}%
921 \or % TSAS

```

```

922 \def\@journalName{ACM Transactions on Spatial Algorithms and Systems}%
923 \def\@journalNameShort{ACM Trans. Spatial Algorithms Syst.}%
924 \def\@permissionCodeOne{2374-0353}%
925 \or % TSC
926 \def\@journalName{ACM Transactions on Social Computing}%
927 \def\@journalNameShort{ACM Trans. Soc. Comput.}%
928 \def\@permissionCodeOne{2469-7818}%
929 \or % TSPL
930 \def\@journalName{ACM Transactions on Speech and Language Processing}%
931 \def\@journalNameShort{ACM Trans. Speech Lang. Process.}%
932 \def\@permissionCodeOne{1550-4875}%
933 \or % TWEB
934 \def\@journalName{ACM Transactions on the Web}%
935 \def\@journalNameShort{ACM Trans. Web}%
936 \def\@permissionCodeOne{1559-1131}%
937 \fi
938 \ClassInfo{@classname}{Using journal code \@journalCode}%
939 }%
940 \ClassError{@classname}{Incorrect journal #1}%
941 }%

```

\acmJournal And the syntactic sugar around it

```

942 \def\acmJournal#1{\setkeys{ACM}{acmJournal=#1}}

```

The defaults:

```

943 \def\@journalCode@nr{0}
944 \def\@journalName{}%
945 \def\@journalNameShort{\@journalName}%
946 \def\@permissionCodeOne{XXXX-XXXX}%
947 \def\@permissionCodeTwo{}%

```

\acmConference This is the conference command

```

948 \newcommand\acmConference[4][]{%
949   \gdef\acmConference@shortname{\#1}%
950   \gdef\acmConference@name{\#2}%
951   \gdef\acmConference@date{\#3}%
952   \gdef\acmConference@venue{\#4}%
953   \ifx\acmConference@shortname\empty
954     \gdef\acmConference@shortname{\#2}%
955   \fi}
956 \acmConference[Conference'17]{ACM Conference}{July 2017}{Washington,
957 DC, USA}

```

\subtitle The subtitle macro

```

958 \def\subtitle#1{\def\@subtitle{#1}}
959 \subtitle{}

```

\num@authorgroups The total number of “groups”. Each group is several authors with the same affiliations(s)

```

960 \newcount\num@authorgroups
961 \num@authorgroups=0\relax

```

\if@insideauthorgroup	Whether we are continuing an author group @insideauthorgroup insideauthorgroup- false
\author	Adding an author to the list of authors and addresses 962 \renewcommand\author[2][]{% 963 \if@insideauthorgroup\else 964 \global\advance\num@authorgroups by 1\relax 965 \global\@insideauthorgrouptrue 966 \fi 967 \ifx\addresses\empty 968 \if@ACM@anonymous 969 \gdef\addresses{\@author{Anonymous Author(s)}}% 970 \gdef\authors{\Anonymous Author(s)}% 971 \else 972 \gdef\addresses{\@author{\#2}}% 973 \gdef\authors{\#2}% 974 \fi 975 \else 976 \if@ACM@anonymous\else 977 \g@addto@macro\addresses{\and\@author{\#2}}% 978 \g@addto@macro\authors{\and\#2}% 979 \fi 980 \fi 981 \if@ACM@anonymous 982 \ifx\shortauthors\empty 983 \gdef\shortauthors{Anon.}% 984 \fi 985 \else 986 \def\@tempa{\#1}% 987 \ifx\@tempa\empty 988 \ifx\shortauthors\empty 989 \gdef\shortauthors{\#2}% 990 \else 991 \g@addto@macro\shortauthors{\and\#2}% 992 \fi 993 \else 994 \ifx\shortauthors\empty 995 \gdef\shortauthors{\#1}% 996 \else 997 \g@addto@macro\shortauthors{\and\#1}% 998 \fi 999 \fi 1000 \fi}
\affiliation	The macro \affiliation mimics \address from amsart. Note that it has an optional argument, which we use differently from amsart. 1001 \newcommand{\affiliation}[2][]{% 1002 \global\@insideauthorgroupfalse 1003 \if@ACM@anonymous\else

```

1004     \g@addto@macro\addresses{\affiliation{#1}{#2}}%
1005   \fi}

@ACM@affiliation@obeypunctuation Whether to use author's punctuation (by default false = add American punctuation)
1006 \define@boolkey+{@ACM@affiliation@}{@ACM@affiliation@}{obeypunctuation}%
1007 [true]{}{\ClassError{\classname}{obeypunctuation must be true or false}{}}

\additionalaffiliation Additional affiliations go to footnotes
1008 \def\additionalaffiliation#1{\authornote{\additionalaffiliation{#1}}}

@\additionalaffiliation Process additionalaffiliation inside \authornote
1009 \def@\additionalaffiliation#1{\bgroup
1010   \def\position##1{\ignorespaces}%
1011   \def\institution##1##1{\ignorespaces}%
1012   \def\department{\ifnextchar[{\@department}{\@department[]}}%
1013   \def \@department##1##2{\unskip, ##2\ignorespaces}%
1014   \let\streetaddress\position
1015   \let\city\position
1016   \let\state\position
1017   \let\postcode\position
1018   \let\country\position
1019   Also with #1\unskip.\egroup}

\email The macro \email mimics \email from amsart. Agian it has an optional argument we do not currently need, but keep for the possible future use.
1020 \renewcommand{\email}[2][]{%
1021   \if@ACM@anonymous\else
1022     \g@addto@macro\addresses{\email{#1}{#2}}%
1023   \fi}

\orcid Right now we do not typeset orcids gobble

@\titlenotes The titlenotes
1024 \def@\titlenotes{}

\titlenote Adding note to the title
1025 \def\titlenote#1{%
1026   \g@addto@macro\@title{\footnotemark}%
1027   \if@ACM@anonymous
1028     \g@addto@macro\@titlenotes{%
1029       \stepcounter{footnote}\footnotetext{Title note}}%
1030   \else
1031     \g@addto@macro\@titlenotes{\stepcounter{footnote}\footnotetext{#1}}%
1032   \fi}

@\subtitlenotes The subtitlenotes
1033 \def@\subtitlenotes{}

```

```

\subtitlenote Adding note to the subtitle
1034 \def\subtitlenote#1{%
1035   \g@addto@macro\@subtitle{\footnotemark}%
1036   \if@ACM@anonymous
1037     \g@addto@macro\@subtitlenotes{%
1038       \stepcounter{footnote}\footnotetext{Subtitle note}}%
1039   \else
1040     \g@addto@macro\@subtitlenotes{%
1041       \stepcounter{footnote}\footnotetext{#1}}%
1042   \fi}

\@authornotes The authornotes
1043 \def\@authornotes{}

\authornote Adding note to the author
1044 \def\authornote#1{%
1045   \if@ACM@anonymous\else
1046     \g@addto@macro\addresses{\@authornotemark}%
1047     \g@addto@macro\@authornotes{%
1048       \stepcounter{footnote}\footnotetext{#1}}%
1049   \fi}

\acmVolume The current volume
1050 \def\acmVolume#1{\def\@acmVolume{#1}}
1051 \acmVolume{1}

\acmNumber The current number
1052 \def\acmNumber#1{\def\@acmNumber{#1}}
1053 \acmNumber{1}

\acmArticle The current article
1054 \def\acmArticle#1{\def\@acmArticle{#1}}
1055 \acmArticle{1}

\acmArticleSeq The sequence number
1056 \def\acmArticleSeq#1{\def\@acmArticleSeq{#1}}
1057 \acmArticleSeq{\@acmArticle}

\acmYear The current year
1058 \def\acmYear#1{\def\@acmYear{#1}}
1059 \acmYear{\the\year}

\acmMonth The current month
1060 \def\acmMonth#1{\def\@acmMonth{#1}}
1061 \acmMonth{\the\month}

```

```

{@acmPubDate The publication date
1062 \def\@acmPubDate{\ifcase\@acmMonth\or
1063   January\or February\or March\or April\or May\or June\or
1064   July\or August\or September\or October\or November\or
1065   December\fi^{\@acmYear} }

@acmPrice The price
1066 \def\acmPrice#1{\def\@acmPrice{#1}}
1067 \acmPrice{15.00}

@acmSubmissionID The submission id
1068 \def\acmSubmissionID#1{\def\@acmSubmissionID{#1}}
1069 \acmSubmissionID{}

@acmISBN The book isbn
1070 \def\acmISBN#1{\def\@acmISBN{#1}}
1071 \acmISBN{978-x-xxxx-xxxx-x/YY/MM}

@acmDOI The paper doi
1072 \def\acmDOI#1{\def\@acmDOI{#1}}
1073 \acmDOI{10.1145/nnnnnnn.nnnnnnn}

@if@ACM@badge Whether to print badge. Note that either left or right badge triggers it:
1074 \newif\if@ACM@badge
1075 \if@ACM@badgeref\false

@ACM@badge@width The width of the badge
1076 \newlength\@ACM@badge@width
1077 \setlength\@ACM@badge@width{5pc}

@ACM@title@width The width of the badge
1078 \newlength\@ACM@title@width

@ACM@badge@skip The space between the badge and the title
1079 \newlength\@ACM@badge@skip
1080 \setlength\@ACM@badge@skip{1pc}

@acmBadgeR Setting the right badge
1081 \newcommand\acmBadgeR[2][]{\@ACM@badgetrue
1082   \def\@acmBadgeR@url{\#1}%
1083   \def\@acmBadgeR@image{\#2}%
1084 \def\@acmBadgeR@url{}%
1085 \def\@acmBadgeR@image{}}

@acmBadgeL Setting the left badge
1086 \newcommand\acmBadgeL[2][]{\@ACM@badgetrue
1087   \def\@acmBadgeL@url{\#1}%
1088   \def\@acmBadgeL@image{\#2}%
1089 \def\@acmBadgeL@url{}%
1090 \def\@acmBadgeL@image{}}

```

```

\startPage The start page of the paper
1091 \def\startPage#1{\def\@startPage{#1}}
1092 \startPage{}

\terms Terms are obsolete, we use CCS now.
1093 \def\terms#1{\ClassWarning{@classname}{The command \string\terms{} is
1094     obsolete. I am going to ignore it}{}}

\keywords Keywords are mostly obsolete, we use CCS now. Still it makes sense to keep them for
compatibility.
1095 \def\keywords#1{\def\@keywords{#1}}
1096 \keywords{}

abstract Amsart puts abstract in the box. Since we do not know whether we will use two
column mode, we prefer to save the text
1097 \renewenvironment{abstract}{\Collect@Body\@saveabstract}{} 

\@saveabstract And saving the abstract
1098 \long\def\@saveabstract#1{\long\gdef\@abstract{#1}}
1099 \@saveabstract{}

\@empty The long version of \@empty (to compare with \@abstract)
1100 \long\def\@empty{}


\if@ACM@printccs Whether to print CCS
1101 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printccs}[true]{%
1102   \if@ACM@printccs
1103     \ClassInfo{@classname}{Printing CCS}%
1104   \else
1105     \ClassInfo{@classname}{Suppressing CCS}%
1106   \fi}{\ClassError{@classname}{printccs must be true or false}{}}

\if@ACM@printacmref Whether to print ACM bib
1107 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printacmref}[true]{%
1108   \if@ACM@printacmref
1109     \ClassInfo{@classname}{Printing bibformat}%
1110   \else
1111     \ClassInfo{@classname}{Suppressing bibformat}%
1112   \fi}{\ClassError{@classname}{printacmref must be true or false}{}}

\if@ACM@printfolios Whether to print folios
1113 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printfolios}[true]{%
1114   \if@ACM@printfolios
1115     \ClassInfo{@classname}{Printing folios}%
1116   \else
1117     \ClassInfo{@classname}{Suppressing folios}%
1118   \fi}{\ClassError{@classname}{printfolios must be true or false}{}}

```

```

\settopmatter The usual syntactic sugar
1119 \def\settopmatter#1{\setkeys{@ACM@topmatter@}{#1}}


Now the settings
1120 \settopmatter{printccs=true, printacmref=true}
1121 \if@ACM@manuscript
1122   \settopmatter{printfolios=true}
1123 \else
1124   \if@ACM@journal
1125     \settopmatter{printfolios=true}
1126   \else
1127     \settopmatter{printfolios=false}
1128   \fi
1129 \fi

@received The container for the paper history
1130 \def\@received{}


\received The \received command
1131 \newcommand\received[2][]{\def\@tempa{#1}%
1132   \ifx\@tempa\empty
1133     \ifx\@received\empty
1134       \gdef\@received{Received #2}%
1135     \else
1136       \g@addto@macro{\@received}{; revised #2}%
1137     \fi
1138   \else
1139     \ifx\@received\empty
1140       \gdef\@received{#1 #2}%
1141     \else
1142       \g@addto@macro{\@received}{; #1 #2}%
1143     \fi
1144   \fi}
1145 \AtEndDocument{%
1146   \ifx\@received\empty\else
1147     \par\bigskip\noindent\small\normalfont\@received\par
1148   \fi}

```

3.11 Concepts system

We exclude CCSXML stuff generated by the ACM system:

```

1149 \RequirePackage{comment}
1150 \excludecomment{CCSXML}

```

```

@concepts This is the storage macro for concepts
1151 \let\@concepts\empty

```

```

\ccsdesc The first argument is the significance, the second is the concept(s)
1152 \newcommand\ccsdesc[2][100]{%
1153   \ccsdesc@parse#1^#2^}

\ccsdesc@parse The parser of the expression Significance^General^Specific (we need textcomp for
\\textrightarrow):
1154 \RequirePackage{textcomp}
1155 \def\ccsdesc@parse#1^#2^#3^{%
1156   \expandafter\ifx\csname CCS#2\endcsname\relax
1157   \expandafter\gdef\csname CCS#2\endcsname{\textbullet\ \textbf{#2}\textrightarrow\ }%
1158   \g@addto@macro{\@concepts}{\csname CCS#2\endcsname}\fi
1159   \expandafter\g@addto@macro\expandafter{\csname CCS#2\endcsname}{%
1160     \ifnum#1>499\textbf{#3}; \else
1161     \ifnum#1>299\textit{#3}; \else
1162     #3; \fi\fi}%

```

3.12 Copyright system

This is from acmcopyright.sty

```

\if@printcopyright A flag whether to print copyright symbol
1163 \newif\if@printcopyright
1164 \@printcopyrighttrue

\if@printpermission Whether to print permission block
1165 \newif\if@printpermission
1166 \@printpermissiontrue

\if@acmowned Whether ACM owns the rights to the paper
1167 \newif\if@acmowned
1168 \@acmownedtrue

```

Keys:

```

1169 \define@choicekey*{ACM@}{acmcopyrightmode}[%
1170   \acm@copyrightinput\acm@copyrightmode]{none,acmcopyright,acmlicensed,%
1171   rightsretained,usgov,usgovmixed,cagov,cagovmixed,%
1172   licensedusgovmixed,licensedcagovmixed,othergov,licensedothergov}{%
1173   \@printpermissiontrue
1174   \@printcopyrighttrue
1175   \@acmownedtrue
1176   \ifnum\acm@copyrightmode=0\relax % none
1177   \@printpermissionfalse
1178   \@printcopyrightfalse
1179   \@acmownedfalse
1180   \fi
1181   \ifnum\acm@copyrightmode=2\relax % acmlicensed
1182   \@acmownedfalse
1183   \fi

```

```

1184 \ifnum\acm@copyrightmode=3\relax % rightsretained
1185   \@acmownedfalse
1186   \acmPrice{}%
1187 \fi
1188 \ifnum\acm@copyrightmode=4\relax % usgov
1189   \@printpermissiontrue
1190   \@printcopyrightfalse
1191   \@acmownedfalse
1192   \acmPrice{}%
1193 \fi
1194 \ifnum\acm@copyrightmode=6\relax % cagov
1195   \@acmownedfalse
1196 \fi
1197 \ifnum\acm@copyrightmode=8\relax % licensedusgovmixed
1198   \@acmownedfalse
1199 \fi
1200 \ifnum\acm@copyrightmode=9\relax % licensedcagovmixed
1201   \@acmownedfalse
1202 \fi
1203 \ifnum\acm@copyrightmode=10\relax % othergov
1204   \@acmownedtrue
1205 \fi
1206 \ifnum\acm@copyrightmode=11\relax % licensedothergov
1207   \@acmownedfalse
1208 \fi}

\setcopyright This is the syntactic sugar around setting keys.
1209 \def\setcopyright#1{\setkeys{ACM@}{acmcopyrightmode=#1}}
1210 \setcopyright{acmcopyright}

\@copyrightowner Here is the owner of the copyright
1211 \def\@copyrightowner{%
1212   \ifcase\acm@copyrightmode\relax % none
1213     \or % acmcopyright
1214       Association for Computing Machinery.
1215     \or % acmlicensed
1216       Copyright held by the owner/author(s). Publication rights licensed to
1217       Association for Computing Machinery.
1218     \or % rightsretained
1219       Copyright held by the owner/author(s).
1220     \or % usgov
1221     \or % usgovmixed
1222       Association for Computing Machinery.
1223     \or % cagov
1224       Crown in Right of Canada.
1225     \or %cagovmixed
1226       Association for Computing Machinery.
1227     \or %licensedusgovmixed
1228       Copyright held by the owner/author(s). Publication rights licensed to
1229       Association for Computing Machinery.

```

```

1230 \or %licensedcagovmixed
1231 Copyright held by the owner/author(s). Publication rights licensed to
1232 Association for Computing Machinery.
1233 \or % othergov
1234 Association for Computing Machinery.
1235 \or % licensedothergov
1236 Copyright held by the owner/author(s). Publication rights licensed to
1237 Association for Computing Machinery.
1238 \fi}

\@formatdoi Print a clickable doi
1239 \def\@formatdoi#1{\url{https://doi.org/#1}}


\@copyrightpermission The canned permission block.
1240 \def\@copyrightpermission{%
1241 \ifcase\acm@copyrightmode\relax % none
1242 \or % acmcopyright
1243 Permission to make digital or hard copies of all or part of this
1244 work for personal or classroom use is granted without fee provided
1245 that copies are not made or distributed for profit or commercial
1246 advantage and that copies bear this notice and the full citation on
1247 the first page. Copyrights for components of this work owned by
1248 others than ACM must be honored. Abstracting with credit is
1249 permitted. To copy otherwise, or republish, to post on servers or to
1250 redistribute to lists, requires prior specific permission
1251 and\hspace*{.5pt}/or a fee. Request permissions from
1252 permissions@acm.org.
1253 \or % acmlicensed
1254 Permission to make digital or hard copies of all or part of this
1255 work for personal or classroom use is granted without fee provided
1256 that copies are not made or distributed for profit or commercial
1257 advantage and that copies bear this notice and the full citation on
1258 the first page. Copyrights for components of this work owned by
1259 others than the author(s) must be honored. Abstracting with credit
1260 is permitted. To copy otherwise, or republish, to post on servers
1261 or to redistribute to lists, requires prior specific permission
1262 and\hspace*{.5pt}/or a fee. Request permissions from
1263 permissions@acm.org.
1264 \or % rightsretained
1265 Permission to make digital or hard copies of part or all of this work
1266 for personal or classroom use is granted without fee provided that
1267 copies are not made or distributed for profit or commercial advantage
1268 and that copies bear this notice and the full citation on the first
1269 page. Copyrights for third-party components of this work must be
1270 honored. For all other uses, contact the
1271 owner\hspace*{.5pt}/author(s).
1272 \or % usgov
1273 This paper is authored by an employee(s) of the United States
1274 Government and is in the public domain. Non-exclusive copying or
1275 redistribution is allowed, provided that the article citation is

```

1276 given and the authors and agency are clearly identified as its
1277 source.
1278 \or % usgovmixed
1279 ACM acknowledges that this contribution was authored or co-authored
1280 by an employee, or contractor of the national government. As such,
1281 the Government retains a nonexclusive, royalty-free right to
1282 publish or reproduce this article, or to allow others to do so, for
1283 Government purposes only. Permission to make digital or hard copies
1284 for personal or classroom use is granted. Copies must bear this
1285 notice and the full citation on the first page. Copyrights for
1286 components of this work owned by others than ACM must be
1287 honored. To copy otherwise, distribute, republish, or post,
1288 requires prior specific permission and\hspace*{.5pt}/or a
1289 fee. Request permissions from permissions@acm.org.
1290 \or % cagov
1291 This article was authored by employees of the Government of Canada.
1292 As such, the Canadian government retains all interest in the
1293 copyright to this work and grants to ACM a nonexclusive,
1294 royalty-free right to publish or reproduce this article, or to allow
1295 others to do so, provided that clear attribution is given both to
1296 the authors and the Canadian government agency employing them.
1297 Permission to make digital or hard copies for personal or classroom
1298 use is granted. Copies must bear this notice and the full citation
1299 on the first page. Copyrights for components of this work owned by
1300 others than the Canadian Government must be honored. To copy
1301 otherwise, distribute, republish, or post, requires prior specific
1302 permission and\hspace*{.5pt}/or a fee. Request permissions from
1303 permissions@acm.org.
1304 \or % cagovmixed
1305 ACM acknowledges that this contribution was co-authored by an
1306 affiliate of the national government of Canada. As such, the Crown
1307 in Right of Canada retains an equal interest in the copyright.
1308 Reprints must include clear attribution to ACM and the author's
1309 government agency affiliation. Permission to make digital or hard
1310 copies for personal or classroom use is granted. Copies must bear
1311 this notice and the full citation on the first page. Copyrights for
1312 components of this work owned by others than ACM must be honored.
1313 To copy otherwise, distribute, republish, or post, requires prior
1314 specific permission and\hspace*{.5pt}/or a fee. Request permissions
1315 from permissions@acm.org.
1316 \or % licensedusgovmixed
1317 Publication rights licensed to ACM\@. ACM acknowledges that this
1318 contribution was authored or co-authored by an employee, contractor
1319 or affiliate of the United States government. As such, the
1320 Government retains a nonexclusive, royalty-free right to publish or
1321 reproduce this article, or to allow others to do so, for Government
1322 purposes only.
1323 \or % licensedcagovmixed
1324 Publication rights licensed to ACM\@. ACM acknowledges that this
1325 contribution was authored or co-authored by an employee, contractor

```

1326 or affiliate of the national government of Canada. As such, the
1327 Government retains a nonexclusive, royalty-free right to publish or
1328 reproduce this article, or to allow others to do so, for Government
1329 purposes only.
1330 \or % othergov
1331 ACM acknowledges that this contribution was authored or co-authored
1332 by an employee, contractor or affiliate of a national government. As
1333 such, the Government retains a nonexclusive, royalty-free right to
1334 publish or reproduce this article, or to allow others to do so, for
1335 Government purposes only.
1336 \or % licensedothergov
1337 Publication rights licensed to ACM\@. ACM acknowledges that this
1338 contribution was authored or co-authored by an employee, contractor
1339 or affiliate of a national government. As such, the Government
1340 retains a nonexclusive, royalty-free right to publish or reproduce
1341 this article, or to allow others to do so, for Government purposes
1342 only.
1343 \fi}

\copyrightyear By default, the copyright year is the same as \acmYear, but one can override this:
1344 \def\copyrightyear{\def\@copyrightyear{\acmYear}}
1345 \copyrightyear{\acmYear}

@\teaserfigures The teaser figures container
1346 \def\@teaserfigures{}

teaserfigure The teaser figure
1347 \newenvironment{teaserfigure}{\Collect@Body\saveteaser}{}{ }

@\saveteaser Saving the teaser
1348 \long\def\@saveteaser#1{\g@addto@macro\@teaserfigures{\@teaser{#1}}}

\thanks We redefine amsart \thanks, so the anonymous key works
1349 \renewcommand{\thanks}[1]{%
1350   \ifnotempty{#1}{%
1351     \if@ACM@anonymous
1352       \g@addto@macro\thankses{\thanks{A note}}%
1353     \else
1354       \g@addto@macro\thankses{\thanks{#1}}%
1355   \fi}%

```

3.13 Typesetting top matter

```

@mkttitle@bx Some of our formats use two column design, some use one column one. In all cases
we use wide title. Thus we typeset the top matter in a special box to be use in the
construction \@twocolumn[<box>].
1356 \newbox@mkttitle@bx

```

\maketitle The (in)famous \maketitle. Note that in sigchi-a mode authors are *not* in the title box.

Another note: there is a subtle difference between author notes, title notes and thankses. The latter refer to the paper itself, and therefore belong to the copyright/permission block. By the way, this was the default behavior of the old ACM classes.

```

1357 \def\maketitle{%
1358   \if@ACM@anonymous
1359     % Anonymize omission of \author-s
1360     \ifnum\num@authorgroups=0\author{}\fi
1361   \fi
1362   \begingroup
1363   \let\@footnotemark\@footnotemark@nolink
1364   \let\@footnotetext\@footnotetext@nolink
1365   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1366   \global\@topnum\z@ % this prevents floats from falling
1367           % at the top of page 1
1368   \global\@botnum\z@ % we do not want them to be on bottom either
1369   \hsize=\textwidth
1370   \def\@makefnmark{\hbox{\@textsuperscript{\@thefnmark}}}%
1371   \@mktitle\if@ACM@sigchiamode\else\@mkauthors\fi\@mkteasers
1372   \@printtopmatter
1373   \if@ACM@sigchiamode\@mkauthors\fi
1374   \setcounter{footnote}{0}%
1375   \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}%
1376   \@titlenotes
1377   \@subtitlenotes
1378   \@authornotes
1379   \let\@makefnmark\relax \let\@thefnmark\relax
1380   \let\@makefntext\noindent
1381   \ifx\@empty\thankses\else
1382     \footnotetextcopyrightpermission{%
1383       \def\par{\let\par\@par}\parindent\z@\@setthanks}%
1384   \fi
1385   \footnotetextcopyrightpermission{%
1386     \if@ACM@authordraft
1387       \raisebox{-2ex}{[\z@][\z@]{\makebox[0pt][l]{\large\bfseries
1388         Unpublished
1389         working draft. Not for distribution}}}
1390       \color[gray]{0.9}%
1391     \fi
1392     \parindent\z@\parskip0.1\baselineskip
1393     \if@ACM@authorversion\else
1394       \if@printpermission\copyrightpermission\par\fi
1395     \fi
1396     \if@ACM@manuscript\else
1397       \if@ACM@journal\else % Print the conference information
1398         \itshape \acmConference@shortname, \acmConference@date, \acmConference@venue\par
1399       \fi
1400     \fi
1401     \if@printcopyright

```

```

1402     \copyright\ \@copyrightyear\ \@copyrightowner\\
1403     \else
1404     \@copyrightyear.\@
1405     \fi
1406     \if@ACM@manuscript
1407         Manuscript submitted to ACM\\
1408     \else
1409     \if@ACM@authorversion
1410         This is the author's version of the work. It is posted here for
1411         your personal use. Not for redistribution. The definitive Version
1412         of Record was published in
1413         \if@ACM@journal
1414             \emph{\@journalName}%
1415         \else
1416             \emph{Proceedings of \acmConference@name, \acmConference@date}%
1417         \fi
1418         \ifx\@acmDOI\@empty
1419             .
1420         \else
1421             , \@formatdoi{\@acmDOI}.
1422         \fi \\
1423     \else
1424     \if@ACM@journal
1425         \@permissionCodeOne/\@acmYear/\@acmMonth-ART\@acmArticle
1426         \ifx\@acmPrice\@empty\else\ \$\@acmPrice\fi \\
1427         \@formatdoi{\@acmDOI}%
1428     \else % Conference
1429         ACM~ISBN^{\@acmISBN}
1430         \ifx\@acmPrice\@empty.\else\@dots\$@\acmPrice\fi \\
1431         \@formatdoi{\@acmDOI}%
1432     \fi
1433     \fi
1434     \fi}
1435 \endgroup
1436 \setcounter{footnote}{0}%
1437 \mkabstract
1438 \if@ACM@printccs
1439     \ifx\@concepts\@empty\else\bgroup
1440         {\@specialsection{CCS Concepts}%
1441             \@concepts\par}\egroup
1442     \fi
1443 \fi
1444 \ifx\@keywords\@empty\else\bgroup
1445     {\if@ACM@journal
1446         \@specialsection{Additional Key Words and Phrases}%
1447     \else
1448         \@specialsection{Keywords}%
1449     \fi
1450     \@keywords\par}\egroup
1451 \fi

```

```

1452 \andify\authors
1453 \andify\shortauthors
1454 \global\let\authors=\authors
1455 \global\let\shortauthors=\shortauthors
1456 \if@ACM@printacmref
1457   \@mkbibcitation
1458 \fi
1459 \hypersetup{pdfauthor={\authors},
1460   pdftitle={\@title}, pdfkeywords={\concepts}}%
1461 \@printendtopmatter
1462 \@afterindentfalse
1463 \@afterheading
1464 }

```

\@specialsection This macro starts section for proceedings and uses small for journals

```

1465 \def\@specialsection#1{%
1466   \ifcase\ACM@format@nr
1467     \relax % manuscript
1468     \par\medskip\small\noindent#1: %
1469   \or % acmsmall
1470   \par\medskip\small\noindent#1: %
1471   \or % acmlarge
1472   \par\medskip\small\noindent#1: %
1473   \or % acmtog
1474   \par\medskip\small\noindent#1: %
1475   \or % sigconf
1476   \section*{\#1}%
1477   \or % siggraph
1478   \section*{\#1}%
1479   \or % sigplan
1480   \paragraph*{\#1}%
1481   \or % sigchi
1482   \section*{\#1}%
1483   \or % sigchi-a
1484   \section*{\#1}%
1485 \fi}

```

\@printtopmatter The printing of top matter starts the new page, and uses the given title box. Note that for sigchi-a we print badges here rather than in \mkttitle since we want them on the margins.

```

1486 \def\@printtopmatter{%
1487   \ifx\@startPage\@empty
1488     \gdef\@startPage{1}%
1489   \else
1490     \setcounter{page}{\@startPage}%
1491   \fi
1492   \thispagestyle{firstpagestyle}%
1493   \noindent
1494   \ifcase\ACM@format@nr

```

```

1495 \relax % manuscript
1496 \box\mkttitle@bx\par
1497 \noindent\hrulefill\par
1498 \or % acmsmall
1499 \box\mkttitle@bx\par
1500 \noindent\hrulefill\par
1501 \or % acmlarge
1502 \box\mkttitle@bx\par
1503 \noindent\hrulefill\par
1504 \or % acmtog
1505 \twocolumn[\box\mkttitle@bx]%
1506 \or % sigconf
1507 \twocolumn[\box\mkttitle@bx]%
1508 \or % siggraph
1509 \twocolumn[\box\mkttitle@bx]%
1510 \or % sigplan
1511 \twocolumn[\box\mkttitle@bx]%
1512 \or % sigchi
1513 \twocolumn[\box\mkttitle@bx]%
1514 \or % sigchi-a
1515 \par\box\mkttitle@bx\par\bigskip
1516 \if@ACM@badge
1517 \marginpar{\noindent
1518 \ifx\@acmBadgeL@image\empty\else
1519 \href{\@acmBadgeL@url}{%
1520 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}%
1521 \hskip\@ACM@badge@skip
1522 \fi
1523 \ifx\@acmBadgeR@image\empty\else
1524 \href{\@acmBadgeR@url}{%
1525 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}%
1526 \fi}%
1527 \fi
1528 \fi
1529 }

\@mkttitle The title of the article
1530 \def\@mkttitle{%
1531 \ifcase\@ACM@format@nr
1532 \relax % manuscript
1533 \mkttitle@i
1534 \or % acmsmall
1535 \mkttitle@i
1536 \or % acmlarge
1537 \mkttitle@i
1538 \or % acmtog
1539 \mkttitle@i
1540 \or % sigconf
1541 \mkttitle@iii
1542 \or % siggraph

```

```

1543     \@mktitle@iii
1544 \or % sigplan
1545     \@mktitle@iii
1546 \or % sigchi
1547     \@mktitle@iii
1548 \or % sigchi-a
1549     \@mktitle@iv
1550 \fi
1551 }

\@titlefont The font to typeset title
1552 \def\@titlefont{%
1553   \ifcase\ACM@format@nr
1554     \relax % manuscript
1555     \LARGE\bfseries\sffamily
1556   \or % acmsmall
1557     \LARGE\bfseries\sffamily
1558   \or % acmlarge
1559     \LARGE\bfseries\sffamily
1560   \or % acmtog
1561     \Huge\sffamily
1562   \or % sigconf
1563     \Huge\sffamily\bfseries
1564   \or % siggraph
1565     \Huge\sffamily\bfseries
1566   \or % sigplan
1567     \Huge\bfseries
1568   \or % sigchi
1569     \Huge\sffamily\bfseries
1570   \or % sigchi-a
1571     \Huge\bfseries
1572 \fi}

\@subtitlefont The font to typeset title
1573 \def\@subtitlefont{\normalsize
1574   \ifcase\ACM@format@nr
1575     \relax % manuscript
1576     \mdseries
1577   \or % acmsmall
1578     \mdseries
1579   \or % acmlarge
1580     \mdseries
1581   \or % acmtog
1582     \LARGE
1583   \or % sigconf
1584     \LARGE\mdseries
1585   \or % siggraph
1586     \LARGE\mdseries
1587   \or % sigplan
1588     \LARGE\mdseries

```

```

1589 \or % sigchi
1590   \LARGE\mdseries
1591 \or % sigchi-a
1592   \mdseries
1593 \fi}

{@mkttitle@i} The version of \mkttitle for most journals
1594 \def@mkttitle@i{\hsize=\textwidth
1595   @ACM@title@width=\hsize
1596   \ifx@acmBadgeL@image@empty\else
1597     \advance@ACM@title@width by -@ACM@badge@width
1598     \advance@ACM@title@width by -@ACM@badge@skip
1599   \fi
1600   \ifx@acmBadgeR@image@empty\else
1601     \advance@ACM@title@width by -@ACM@badge@width
1602     \advance@ACM@title@width by -@ACM@badge@skip
1603   \fi
1604   \setbox@mkttitle@bx=\vbox{\noindent@titlefont
1605     \ifx@acmBadgeL@image@empty\else
1606       \raisebox{-.5\baselineskip}{\z@\z@{\href{@acmBadgeL@url}{%
1607         \includegraphics[width=@ACM@badge@width]{@acmBadgeL@image}}}}%
1608       \hskip@ACM@badge@skip
1609     \fi
1610     \parbox[t]{@ACM@title@width}{\raggedright
1611       @titlefont\noindent
1612       @title
1613     \ifx@subtitle@empty\else
1614       \par\noindent{@subtitlefont@subtitle}
1615     \fi}%
1616     \ifx@acmBadgeR@image@empty\else
1617       \hskip@ACM@badge@skip
1618       \raisebox{-.5\baselineskip}{\z@\z@{\href{@acmBadgeR@url}{%
1619         \includegraphics[width=@ACM@badge@width]{@acmBadgeR@image}}}}%
1620     \fi
1621   \par\bigskip}%
1622
{@mkttitle@ii} The version of \mkttitle for TOG. Since v1.06 is subsumed by the \mkttitle@i macro
{@mkttitle@iii} The version of \mkttitle for sigproc. Note that since the title is centered, we leave the
space for the left badge even if only the right badge is defined.
1622 \def@mkttitle@iii{\hsize=\textwidth
1623   \setbox@mkttitle@bx=\vbox{@titlefont\centering
1624     @ACM@title@width=\hsize
1625     \if@ACM@badge
1626       \advance@ACM@title@width by -2@ACM@badge@width
1627       \advance@ACM@title@width by -2@ACM@badge@skip
1628       \parbox[b]{@ACM@badge@width}{\strut
1629         \ifx@acmBadgeL@image@empty\else
1630           \raisebox{-.5\baselineskip}{\z@\z@{\href{@acmBadgeL@url}{%
1631             \includegraphics[width=@ACM@badge@width]{@acmBadgeL@image}}}}%

```

```

1632     \fi}%
1633     \hskip\@ACM@badge@skip
1634   \fi
1635   \parbox[t]{\@ACM@title@width}{\centering\@titlefont
1636     \@title
1637     \ifx\@subtitle\@empty\else
1638       \par\noindent{\@subtitlefont\@subtitle}
1639     \fi
1640   }%
1641   \if@ACM@badge
1642     \hskip\@ACM@badge@skip
1643     \parbox[b]{\@ACM@badge@width}{\strut
1644       \ifx\@acmBadgeR@image\@empty\else
1645         \raisebox{-.5\baselineskip}[.5\baselineskip][.5\baselineskip]{\@acmBadgeR@url}{%
1646           \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}}%
1647     \fi}%
1648   \fi
1649   \par\bigskip}%

```

\@mktitle@iv The version of \@mktitle for sigchi-a

```

1650 \def\@mktitle@iv{\hsize=\textwidth
1651   \setbox\mktitle@bx=\vbox{\raggedright\leftskip5pc\@titlefont
1652     \noindent\leavevmode\leaders\hrule height 2pt\hfill\kern0pt\par
1653     \noindent\@title
1654     \ifx\@subtitle\@empty\else
1655       \par\noindent\@subtitlefont\@subtitle
1656     \fi
1657   \par\bigskip}%

```

\@ACM@addtoaddress The macro adds an item to address using the following rules:

1. If we start a paragraph, add the item
2. Otherwise, add a comma and the item
3. However, the comma is deleted, if it is on the end of the line. We use the magic cleaders trick for this.

```

1658 \newbox\@ACM@commabox
1659 \def\@ACM@addtoaddress#1{%
1660   \ifvmode\else
1661     \if@ACM@affiliation@obeypunctuation\else
1662       \setbox\@ACM@commabox=\hbox{, }%
1663       \unskip\cleaders\copy\@ACM@commabox\hskip\wd\@ACM@commabox
1664     \fi\fi
1665   #1}

```

\institution Theoretically we can define the macros for \affiliation inside the \@mkauthors-style commands. However, this would lead to a strange error if an author uses them outside \affiliation. Of course we can make them produce an error message, but...

\position

\department

\streetaddress

\city

\state

\postcode

\country

We follow the strange American tradition of no comma before zip code.

```
1666 \if@ACM@journal
1667   \let\position\gobble
1668   \def\institution#1{\#1\ignorespaces}%
1669   \newcommand\department[2][0]{}%
1670   \let\streetaddress\gobble
1671   \let\city\gobble
1672   \let\state\gobble
1673   \let\postcode\gobble
1674   \let\country\gobble
1675 \else
1676   \def\position#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1677   \def\institution#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1678   \newcommand\department[2][0]{\if@ACM@affiliation@obeypunctuation
1679     #2\else#2\par\fi}%
1680   \def\streetaddress#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
1681   \let\city@\ACM@addtoaddress
1682   \let\state@\ACM@addtoaddress
1683   \def\postcode#1{\if@ACM@affiliation@obeypunctuation#1\else\unskip\space#1\fi}%
1684   \let\country@\ACM@addtoaddress
1685 \fi
```

\@mkauthors Typesetting authors

```
1686 \def\@mkauthors{\begingroup
1687   \hsize=\textwidth
1688   \ifcase\ACM@format@nr
1689     \relax % manuscript
1690     \@mkauthors@i
1691     \or % acmsmall
1692     \@mkauthors@i
1693     \or % acmlarge
1694     \@mkauthors@i
1695     \or % acmtog
1696     \@mkauthors@i
1697     \or % sigconf
1698     \@mkauthors@iii
1699     \or % siggraph
1700     \@mkauthors@iii
1701     \or % sigplan
1702     \@mkauthors@iii
1703     \or % sigchi
1704     \@mkauthors@iii
1705     \or % sigchi-a
1706     \@mkauthors@iv
1707   \fi
1708   \endgroup
1709 }
```

\@authorfont Somehow different conferences use different fonts for author names. Why?

```
1710 \def\@authorfont{\Large\sffamily}
```

```

\@affiliationfont  Font for affiliations
1711 \def\@affiliationfont{\normalsize\normalfont}

    Adjusting fonts for different formats
1712 \ifcase\ACM@format@nr
1713   \relax % manuscript
1714   \or % acmsmall
1715     \def\@authorfont{\large\sffamily}
1716     \def\@affiliationfont{\small\normalfont}
1717   \or % acmlarge
1718   \or % acmtog
1719     \def\@authorfont{\LARGE\sffamily}
1720     \def\@affiliationfont{\large}
1721   \or % sigconf
1722     \def\@authorfont{\LARGE}
1723     \def\@affiliationfont{\large}
1724   \or % siggraph
1725     \def\@authorfont{\normalsize\normalfont}
1726     \def\@affiliationfont{\normalsize\normalfont}
1727   \or % sigplan
1728     \def\@authorfont{\Large\normalfont}
1729     \def\@affiliationfont{\normalsize\normalfont}
1730 \or % sigchi
1731   \def\@authorfont{\bfseries}
1732   \def\@affiliationfont{\mdseries}
1733 \or % sigchi-a
1734   \def\@authorfont{\bfseries}
1735   \def\@affiliationfont{\mdseries}
1736 \fi

\@typeset@author@line At this point we have \@currentauthors and \@currentaffiliations. We typeset
them in the journal style
1737 \def\@typeset@author@line{%
1738   \andify\@currentauthors\par\noindent
1739   \@currentauthors\def\@currentauthors{}%
1740   \ifx\@currentaffiliations\empty\else
1741     \andify\@currentaffiliations
1742     \unskip, {\@currentaffiliations}\par
1743   \fi
1744   \def\@currentaffiliations{}}

\@mkauthors@i This is version used in most journal formats. Note that \and between authors with the
same affiliation becomes _and_:
1745 \def\@mkauthors@i{%
1746   \def\@currentauthors{}%
1747   \def\@currentaffiliations{}%
1748   \global\let\and\@typeset@author@line
1749   \def\@author##1{%
1750     \ifx\@currentauthors\empty

```

```

1751     \gdef\@currentauthors{\@authorfont\MakeUppercase{##1}}%
1752     \else
1753         \g@addto@macro{\@currentauthors}{\and\MakeUppercase{##1}}%
1754     \fi
1755     \gdef\and{}%
1756     \def\email##1##2{}%
1757     \def\affiliation##1##2{}%
1758     \def\@tempa{##2}\ifx\@tempa\empty\else
1759         \ifx\@currentaffiliations\empty
1760             \gdef\@currentaffiliations{%
1761                 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1762                 \setkeys{@ACM@affiliation@}{##1}%
1763                 \@affiliationfont##2}%
1764         \else
1765             \g@addto@macro{\@currentaffiliations}{\and
1766                 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1767                 \setkeys{@ACM@affiliation@}{##1}##2}%
1768         \fi
1769     \fi
1770     \global\let\and\@typeset@author@line}%
1771 \global\setbox\mkttitle@bx=\vbox{\noindent\box\mkttitle@bx\par\medskip
1772     \noindent\addresses\@typeset@author@line
1773     \par\medskip}%
1774 }

\@mkauthors@ii \@mkauthors@I was version used in acmtog. No longer necessary

@author@bx The box to put individual author to
1775 \newbox@author@bx

@author@bx@wd The width of the author box
1776 \newdimen@author@bx@wd

@author@bx@sep The separation between the author boxes
1777 \newskip@author@bx@sep
1778 \author@bx@sep=1pc\relax

@typeset@author@bx Typesetting the box with authors. Note that in SIGCHI-A the box is not centered.
1779 \def@typeset@author@bx{\bgroup\hsize=\author@bx@wd\def\and{\par}%
1780   \global\setbox@author@bx=\vtop{\if@ACM@sigchiamode\else\centering\fi
1781     \@authorfont\@currentauthors\par\@affiliationfont
1782     \@currentaffiliation\egroup
1783   \box@author@bx\hskip{\author@bx@sep}%
1784   \gdef\@currentauthors{}%
1785   \gdef\@currentaffiliation{}}}

\@mkauthors@iii The sigconf version. Here we use centered design with each author in a separate box.
1786 \def\@mkauthors@iii{%

```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width $(\text{\textwidth} - \text{\author@bx@sep})/N - \text{\author@bx@sep}$, where N is the number of boxes per row.

```

1787 \author@bx@wd=\textwidth\relax
1788 \advance\author@bx@wd by -\author@bx@sep\relax
1789 \ifcase\num@authorgroups
1790   \relax % 0?
1791   \or % 1=one author per row
1792   \or % 2=two authors per row
1793     \divide\author@bx@wd by \num@authorgroups\relax
1794   \or % 3=three authors per row
1795     \divide\author@bx@wd by \num@authorgroups\relax
1796   \or % 4=two authors per row (!)
1797     \divide\author@bx@wd by 2\relax
1798   \else % three authors per row
1799     \divide\author@bx@wd by 3\relax
1800 \fi
1801 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses :

```

1802 \gdef\@currentauthors{}%
1803 \gdef\@currentaffiliation{}%
1804 \def\@author##1{\ifx\@currentauthors\@empty
1805   \gdef\@currentauthors{\par##1}%
1806 \else
1807   \g@addto@macro\@currentauthors{\par##1}%
1808 \fi
1809 \gdef\and{}%
1810 \def\email##1##2{\ifx\@currentaffiliation\@empty
1811   \gdef\@currentaffiliation{\nolinkurl{##2}}%
1812 \else
1813   \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
1814 \fi}%
1815 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
1816   \gdef\@currentaffiliation{%
1817     \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1818     \setkeys{@ACM@affiliation@}{##1##2}%
1819 \else
1820   \g@addto@macro\@currentaffiliation{\par
1821     \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1822     \setkeys{@ACM@affiliation@}{##1##2}%
1823 \fi
1824 \global\let\and\@typeset@author@bx
1825 }%

```

Actual typesetting is done by \and macro:

```

1826 \hsize=\textwidth
1827 \global\setbox\mkttitle@bx=\vbox{\noindent
1828   \box\mkttitle@bx\par\medskip\leavevmode

```

```

1829     \lineskip=1pc\relax\centering\hspace*{-1em}%
1830     \addresses\let\and\@typeset@author@bx\and\par\bigskip\}}

```

\@mkauthors@iv The sigchia version. Now we put authors in the main text, and no more than 2 authors per line.

```
1831 \def\@mkauthors@iv{%
```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width ($\text{textwidth} - \text{\author@bx@sep})/N - \text{\author@bx@sep}$, where N is the number of boxes per row.

```

1832   \author@bx@wd=\columnwidth\relax
1833   \advance\author@bx@wd by -\author@bx@sep\relax
1834   \ifcase\num@authorgroups
1835     \relax % 0?
1836     \or % 1=one author per row
1837     \else % 2=two authors per row
1838       \divide\author@bx@wd by 2\relax
1839   \fi
1840   \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

1841   \gdef\@currentauthors{}%
1842   \gdef\@currentaffiliation{}%
1843   \def\@author##1{\ifx\@currentauthors\@empty
1844     \gdef\@currentauthors{\par##1}%
1845   \else
1846     \g@addto@macro\@currentauthors{\par##1}%
1847   \fi
1848   \gdef\and{}%
1849   \def\email##1##2{\ifx\@currentaffiliation\@empty
1850     \gdef\@currentaffiliation{\nolinkurl{##2}}%
1851   \else
1852     \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
1853   \fi}%
1854   \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
1855     \gdef\@currentaffiliation{%
1856       \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1857       \setkeys{@ACM@affiliation@}{##1}##2}%
1858   \else
1859     \g@addto@macro\@currentaffiliation{\par
1860       \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1861       \setkeys{@ACM@affiliation@}{##1}##2}%
1862   \fi
1863   \global\let\and\@typeset@author@bx}%
1864 %

```

Actual typesetting is done by \and macro

```

1865   \bgroup\hsize=\columnwidth
1866   \par\raggedright\leftskip=\z@

```

```

1867      \lineskip=1pc\noindent
1868      \addresses\let\and@typeset@author@bx\and\par\bigskip\egroup}

\@authornotemark Adding footnotemark to authors
1869 \def\@authornotemark{\g@addto@macro\@currentauthors{\footnotemark}}


\@mkteasers Typesetting teasers
1870 \def\@mkteasers{%
1871   \ifx\@teaserfigures\empty\else
1872     \def\@teaser##1{\par\bigskip\bgroup
1873       \captionsetup[type=figure]##1\egroup\par}
1874     \global\setbox\mktitle@bx=\vbox{\noindent\box\mktitle@bx\par
1875       \noindent\@teaserfigures\par\medskip}%
1876   \fi}

\@setaddresses This is an amsart macro, which we do not need.
1877 \def\@setaddresses{}


\@mkabstract Typesetting abstract
1878 \def\@mkabstract{\bgroup
1879   \ifx\@abstract\empty\else
1880     {\phantomsection\addcontentsline{toc}{section}{Abstract}%
1881       \if@ACM@journal
1882         \small\noindent
1883       \else
1884         \section*{Abstract}%
1885       \fi
1886     \ignorespaces\@abstract\par}%
1887   \fi\egroup}

\@mkbibcitation Print bibtex citation format
1888 \def\@mkbibcitation{\bgroup
1889   \def\footnotemark{}%
1890   \def\\{\unskip{}\ignorespaces}%
1891   \def\footnote{\ClassError{@classname}{Please do note use footnotes
1892     inside \string\title{} or \string\author{} command! Use
1893     \string\titlenote{} or \string\authornote{} instead!}}%
1894   \par\medskip\small\noindent\bfseries ACM Reference format:\par\nobreak
1895   \noindent\authors. \acmYear. \title.
1896   \if@ACM@journal
1897     \textit{\journalNameShort}
1898     \acmVolume, \acmNumber, Article\acmArticle\ (\acmPubDate),
1899     \ref{TotPages}\ignorespaces.
1900   \else
1901     In \textit{Proceedings of \acmConference@name, \acmConference@venue,
1902       \acmConference@date
1903       \ifx\acmConference@name\acmConference@shortname\else
1904         \acmConference@shortname\fi
1905       ,} \ref{TotPages}\ignorespaces.

```

```

1906   \fi\par
1907   \noindent\@formatdoi{\@acmDOI}
1908 \par\egroup}

\@printendtopmatter End the top matter
1909 \def\@printendtopmatter{\par\medskip
1910   \ifcase\ACM@format@nr
1911     \relax % manuscript
1912       \noindent\hrulefill\par\medskip
1913     \or % acmsmall
1914       \noindent\hrulefill\par\medskip
1915     \or % acmlarge
1916       \noindent\hrulefill\par\medskip
1917     \or % acmtog
1918       \par\bigskip
1919     \or % sigconf
1920       \par\bigskip
1921     \or % siggraph
1922       \par\bigskip
1923     \or % sigplan
1924       \par\bigskip
1925     \or % sigchi
1926       \par\bigskip
1927     \or % sigchi-a
1928   \fi
1929 }

\@setthanks We redefine \setthanks using \long
1930 \def\@setthanks{\long\def\thanks##1{\par##1\@addpunct.\ }\\@thankses}

```

3.14 Headers and Footers

We use `fancyhdr` for our headers and footers:

```

1931 \RequirePackage{fancyhdr}

\ACM@linecount@bx This is the box displayed in the review mode
1932 \if@ACM@review
1933   \newsavebox{\ACM@linecount@bx}
1934   \newlength\ACM@linecount@bxht
1935   \newcount\ACM@linecount
1936   \ACM@linecount@ne\relax
1937   \def\ACM@mk@linecount{%
1938     \savebox{\ACM@linecount@bx}[4em][t]{\parbox[t]{4em}{%
1939       \setlength{\ACM@linecount@bxht}{-\baselineskip}%
1940       \loop\color{ACMRed}\scriptsize\the\ACM@linecount\%\\%
1941       \global\advance\ACM@linecount by \@ne
1942       \addtolength{\ACM@linecount@bxht}{\baselineskip}%
1943       \ifdim\ACM@linecount@bxht<\textheight\repeat}}}
1944 \fi

```

\ACM@linecountL How to display the box on the left

```
1945 \def\ACM@linecountL{%
1946   \if@ACM@review
1947     \ACM@mk@linecount
1948     \begin{picture}(0,0)%
1949       \put(-26,-22){\usebox{\ACM@linecount@bx}}%
1950     \end{picture}%
1951   \fi}
```

\ACM@linecountR How to display the box on the right

```
1952 \def\ACM@linecountR{%
1953   \if@ACM@review
1954     \ACM@mk@linecount
1955     \begin{picture}(0,0)%
1956       \put(20,-22){\usebox{\ACM@linecount@bx}}%
1957     \end{picture}%
1958   \fi}
```

\ACM@timestamp The timestamp system

```
1959 \if@ACM@timestamp
1960   % Subtracting 30 from \time gives us the effect of rounding-down despite
1961   % \numexpr rounding to nearest
1962   \newcounter{ACM@time@hours}
1963   \setcounter{ACM@time@hours}{\numexpr (\time - 30) / 60 \relax}
1964   \newcounter{ACM@time@minutes}
1965   \setcounter{ACM@time@minutes}{\numexpr \time - \theACM@time@hours * 60 \relax}
1966   \newcommand\ACM@timestamp{%
1967     \footnotesize%
1968     \the\year-\two@digits{\the\month}-\two@digits{\the\day}{ }%
1969     \two@digits{\theACM@time@hours}:\two@digits{\theACM@time@minutes}{ }%
1970     page^\thepage\ (pp. \startPage-\pageref*{TotPages})%
1971     \ifx\acmSubmissionID\empty\relax\else
1972       ~Submission^ID: \acmSubmissionID
1973     \fi
1974   }
1975 \fi
```

\@shortauthors Even if the author redefined \shortauthors, we do not print them in the anonymous mode in the headers:

```
1976 \def\@shortauthors{\if@ACM@anonymous Anon.\else\shortauthors\fi}
```

\@headfootfont The font to typeset header and footer text.

```
1977 \def\@headfootfont{%
1978   \ifcase\ACM@format@nr
1979     \relax % manuscript
1980     \sffamily
1981   \or % acmsmall
1982     \sffamily
1983   \or % acmlarge
```

```

1984    \sffamily
1985    \or % acmtog
1986    \sffamily
1987    \or % sigconf
1988    \sffamily
1989    \or % siggraph
1990    \sffamily
1991    \or % sigplan
1992    \sffamily
1993    \or % sigchi
1994    \sffamily
1995    \or % sigchi-a
1996    \sffamily
1997    \fi}

```

standardpagestyle The pagestyle for all pages but the first one

```

1998 \fancypagestyle{standardpagestyle}{%
1999   \fancyhf{}%
2000   \renewcommand{\headrulewidth}{\z@}%
2001   \renewcommand{\footrulewidth}{\z@}%
2002   \ifcase\ACM@format@nr
2003     \relax % manuscript
2004     \fancyhead[LE]{\ACM@linecountL\if@ACM@printfolios\thepage\fi}%
2005     \fancyhead[RO]{\if@ACM@printfolios\thepage\fi}%
2006     \fancyhead[RE]{\@shortauthors}%
2007     \fancyhead[LO]{\ACM@linecountL\shorttitle}%
2008     \fancyfoot[RO,LE]{\footnotesize Manuscript submitted to ACM}%
2009   \or % acmsmall
2010   \fancyhead[LE]{\ACM@linecountL@\headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2011   \fancyhead[RO]{\@headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2012   \fancyhead[RE]{\@headfootfont\@shortauthors}%
2013   \fancyhead[LO]{\ACM@linecountL@\headfootfont\shorttitle}%
2014   \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \acmVolume, No.%
2015   \acmNumber, Article \acmArticle. Publication date: \acmPubDate.}%
2016   \or % acmlarge
2017   \fancyhead[LE]{\ACM@linecountL@\headfootfont
2018   \acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2019   \fancyhead[LO]{\ACM@linecountL}%
2020   \fancyhead[RO]{\@headfootfont
2021   \shorttitle\quad\textbullet\quad\acmArticle\if@ACM@printfolios:\thepage\fi}%
2022   \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \acmVolume, No.%
2023   \acmNumber, Article \acmArticle. Publication date: \acmPubDate.}%
2024   \or % acmtog
2025   \fancyhead[LE]{\ACM@linecountL@\headfootfont
2026   \acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2027   \fancyhead[LO]{\ACM@linecountL}%
2028   \fancyhead[RE]{\ACM@linecountR}%
2029   \fancyhead[RO]{\@headfootfont
2030   \shorttitle\quad\textbullet\quad\acmArticle\if@ACM@printfolios:\thepage\fi\ACM@linecountR}%
2031   \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \acmVolume, No.}

```

```

2032     \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2033 \else % Proceedings
2034   \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2035   \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2036   \fancyhead[RE]{\@headfootfont\shortauthors\ACM@linecountR}%
2037   \fancyhead[LE]{\ACM@linecountL\@headfootfont\acmConference@shortname,
2038     \acmConference@date, \acmConference@venue}%
2039   \fancyhead[RO]{\@headfootfont\acmConference@shortname,
2040     \acmConference@date, \acmConference@venue\ACM@linecountR}%
2041 \fi
2042 \if@ACM@sigchiamode
2043   \fancyheadoffset[L]{\dimexpr(\marginparsep+\marginparwidth)}%
2044 \fi
2045 \if@ACM@timestamp
2046   \fancyfoot[LO,RE]{\ACM@timestamp}
2047 \fi
2048 }
2049 \pagestyle{standardpagestyle}

\f@folio@wd Folio blob width, height, offsets and max number
\f@folio@ht \newdimen\f@folio@wd
\f@folio@voffset \f@folio@wd=\z@
\f@folio@max \newdimen\f@folio@ht
2053 \f@folio@ht=\z@
2054 \newdimen\f@folio@voffset
2055 \f@folio@voffset=\z@
2056 \def\f@folio@max{1}
2057 \ifcase\ACM@format@nr
2058 \relax % manuscript
2059 \or % acmsmall
2060   \f@folio@wd=45.75pt\relax
2061   \f@folio@ht=1.25in\relax
2062   \f@folio@voffset=.2in\relax
2063   \def\f@folio@max{8}
2064 \or % acmlarge
2065   \f@folio@wd=43.25pt\relax
2066   \f@folio@ht=79pt\relax
2067   \f@folio@voffset=.55in\relax
2068   \def\f@folio@max{10}
2069 \fi

\f@folioblob The macro to typeset the folio blob.
2070 \def\f@folioblob{\@tempcnta=\@acmArticleSeq\relax
First, we calculate \@acmArticleSeq modulo \@folio@max
2071   \loop
2072     \ifnum\@tempcnta>\@folio@max\relax
2073       \advance\@tempcnta by - \@folio@max
2074     \repeat

```

```

2075   \advance\@tempcpta by -1\relax
2076   \@tempdima=\@folio@ht\relax
2077   \multiply\@tempdima by \the\@tempcpta\relax
2078   \advance\@tempdima by -\@folio@voffset\relax
2079   \begin{picture}(0,0)
2080   \makebox[\z@]{\raisebox{-\@tempdima}{%
2081     \rlap{%
2082       \raisebox{-0.45\@folio@ht}{\z@[\z@]{%
2083         \rule{\@folio@wd}{\@folio@ht}}}}%
2084     \parbox{\@folio@wd}{%
2085       \centering
2086       \textcolor{white}{\LARGE\bfseries\sffamily\@acmArticle}}}}
2087   \end{picture}
2088

```

firstpagestyle The pagestyle for the first page only.

```

2089 \fancypagestyle{firstpagestyle}{%
2090   \fancyhf{}%
2091   \renewcommand{\headrulewidth}{\z@}%
2092   \renewcommand{\footrulewidth}{\z@}%
2093   \ifcase\ACM@format@nr
2094     \relax % manuscript
2095     \fancyhead[L]{\ACM@linecountL}%
2096     \fancyfoot[RO,LE]{\if@ACM@printfolios\small\thepage\fi}%
2097     \fancyfoot[RE,LO]{\footnotesize Manuscript submitted to ACM}%
2098   \or % acmsmall
2099     \fancyfoot[RO,LE]{\footnotesize \journalName, Vol. \acmVolume, No.
2100     \acmNumber, Article \acmArticle. Publication date:
2101     \acmPubDate.}%
2102     \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2103     \fancyhead[LO]{\ACM@linecountL}%
2104     \fancyhead[RO]{\@folioblob}%
2105     \fancyheadoffset[RO,LE]{0.6\@folio@wd}%
2106   \or % acmlarge
2107     \fancyfoot[RO,LE]{\footnotesize \journalName, Vol. \acmVolume, No.
2108     \acmNumber, Article \acmArticle. Publication date:
2109     \acmPubDate.}%
2110     \fancyhead[RO]{\@folioblob}%
2111     \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2112     \fancyhead[LO]{\ACM@linecountL}%
2113     \fancyheadoffset[RO,LE]{1.4\@folio@wd}%
2114   \or % acmtog
2115     \fancyfoot[RO,LE]{\footnotesize \journalName, Vol. \acmVolume, No.
2116     \acmNumber, Article \acmArticle. Publication date:
2117     \acmPubDate.}%
2118     \fancyhead[L]{\ACM@linecountL}%
2119     \fancyhead[R]{\ACM@linecountR}%
2120   \else % Conference proceedings
2121     \fancyhead[L]{\ACM@linecountL}%
2122     \fancyhead[R]{\ACM@linecountR}%

```

```

2123   \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2124   \fi
2125 \if@ACM@timestamp
2126   \ifnum\ACM@format@nr=0\relax % Manuscript
2127     \fancyfoot[L0,RE]{\ACM@timestamp\quad
2128       \footnotesize Manuscript submitted to ACM}
2129   \else
2130     \fancyfoot[L0,RE]{\ACM@timestamp}
2131   \fi
2132 \fi
2133 }

```

3.15 Sectioning

Sectioning is different for different levels

```

2134 \renewcommand\section{\@startsection{section}{1}{\z@}%
2135   {-.75\baselineskip \oplus -2\p@ \ominus -.2\p@}%
2136   {.25\baselineskip}%
2137   {\@secfont}}
2138 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
2139   {-.75\baselineskip \oplus -2\p@ \ominus -.2\p@}%
2140   {.25\baselineskip}%
2141   {\@subsecfont}}
2142 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{10pt}%
2143   {-.5\baselineskip \oplus -2\p@ \ominus -.2\p@}%
2144   {-3.5\p@}%
2145   {\@subsubsecfont\@adddotafter}}
2146 \renewcommand\paragraph{\@startsection{paragraph}{4}{\parindent}%
2147   {-.5\baselineskip \oplus -2\p@ \ominus -.2\p@}%
2148   {-3.5\p@}%
2149   {\@parfont\@adddotafter}}
2150 \renewcommand\part{\@startsection{part}{9}{\z@}%
2151   {-10\p@ \oplus -4\p@ \ominus -2\p@}%
2152   {4\p@}%
2153   {\@parfont}}

```

\section@raggedright Special version of \raggedright compatible with \MakeUppercase

```

2154 \def\section@raggedright{\rightskip\@flushglue
2155   \rightskip\rightskip
2156   \leftskip\z@skip
2157   \parindent\z@}

```

\@secfont Fonts for sections etc. are different for different formats.

```

2158 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeUppercase}
2159 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2160 \def\@subsubsecfont{\sffamily\itshape}
2161 \def\@parfont{\itshape}
2162 \setcounter{secnumdepth}{3}
2163 \ifcase\ACM@format@nr

```

```

2164 \relax % manuscript
2165 \or % acmsmall
2166 \or % acmlarge
2167 \def\@secfont{\sffamily\large\section@raggedright\MakeUppercase}
2168 \def\@subsecfont{\sffamily\large\section@raggedright}
2169 \or % acmtog
2170 \def\@secfont{\sffamily\large\section@raggedright\MakeUppercase}
2171 \def\@subsecfont{\sffamily\large\section@raggedright}
2172 \or % sigconf
2173 \def\@secfont{\bfseries\Large\section@raggedright\MakeUppercase}
2174 \def\@subsecfont{\bfseries\Large\section@raggedright}
2175 \or % siggraph
2176 \def\@secfont{\bfseries\sffamily\Large\section@raggedright\MakeUppercase}
2177 \def\@subsecfont{\bfseries\sffamily\Large\section@raggedright}
2178 \or % sigplan
2179 \def\@secfont{\bfseries\Large\section@raggedright}
2180 \def\@subsecfont{\bfseries\section@raggedright}
2181 \renewcommand\subsubsection{@startsection{subsubsection}{3}{\z@}%
2182 {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2183 {.25\baselineskip}%
2184 {\@subsubsecfont}}
2185 \def\@subsubsecfont{\bfseries\section@raggedright}
2186 \renewcommand\paragraph{@startsection{paragraph}{4}{\z@}%
2187 {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2188 {-3.5\p@}%
2189 {\@parfont\@addspaceafter}}
2190 \def\@parfont{\bfseries\itshape}
2191 \renewcommand\subparagraph{@startsection{subparagraph}{5}{\z@}%
2192 {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2193 {-3.5\p@}%
2194 {\@subparfont\@addspaceafter}}
2195 \def\@subparfont{\itshape}
2196 \or % sigchi
2197 \setcounter{secnumdepth}{1}
2198 \def\@secfont{\bfseries\sffamily\section@raggedright\MakeUppercase}
2199 \def\@subsecfont{\bfseries\sffamily\section@raggedright}
2200 \or % sigchi-a
2201 \setcounter{secnumdepth}{0}
2202 \def\@secfont{\bfseries\sffamily\section@raggedright\MakeUppercase}
2203 \def\@subsecfont{\bfseries\sffamily\section@raggedright}
2204 \fi

\@adddotafter Add punctuation after the command
2205 \def\@adddotafter{\#1{\#1\@addpunct{.}}}

\@addspaceafter Add space after the command
2206 \def\@addspaceafter{\#1{\#1\@addpunct{\enspace}}}

```

3.16 TOC Lists

\@dotsep Related to the \tableofcontents are all the horizontal fillers. Base L^AT_EX defines \@dottedtocline, which we should not disable. Yet, this command expects \@dotsep to be defined, but leaves this to the class implementation. Since amsart does not provide this, we copy the standard variant from article here.

2207 \providecommand*\@dotsep{4.5}

3.17 Theorems

\@acmplainbodyfont The font to typeset the acmplain theorem style body.

2208 \def\@acmplainbodyfont{\itshape}

\@acmplainindent The amount to indent the acmplain theorem style.

2209 \def\@acmplainindent{\parindent}

\@acmplainheadfont The font to typeset the acmplain theorem style head.

2210 \def\@acmplainheadfont{\scshape}

\@acmplainnotefont The font to typeset the acmplain theorem style note.

2211 \def\@acmplainnotefont{\emptyset}

Customization of acmplain theorem style:

2212 \ifcase\ACM@format@nr
2213 \relax % manuscript
2214 \or % acmsmall
2215 \or % acmlarge
2216 \or % acmtog
2217 \or % sigconf
2218 \or % siggraph
2219 \or % sigplan
2220 \def\@acmplainbodyfont{\itshape}
2221 \def\@acmplainindent{\z@}
2222 \def\@acmplainheadfont{\bfseries}
2223 \def\@acmplainnotefont{\normalfont}
2224 \or % sigchi
2225 \or % sigchi-a
2226 \fi

acmplain The acmplain theorem style

2227 \newtheoremstyle{acmplain}{}
2228 {.5\baselineskip\@plus.2\baselineskip
2229 \@minus.2\baselineskip}% space above
2230 {.5\baselineskip\@plus.2\baselineskip
2231 \@minus.2\baselineskip}% space below
2232 {\@acmplainbodyfont}% body font
2233 {\@acmplainindent}% indent amount
2234 {\@acmplainheadfont}% head font

```

2235  {. }% punctuation after head
2236  {.5em}% spacing after head
2237  {\thmname{#1}\thmnumber{ #2}\thmnote{ {\@acmplainnotefont(#3)}}}% head spec

\@acmdefinitionbodyfont The font to typeset the acmdefinition theorem style body.
2238 \def\@acmdefinitionbodyfont{\normalfont}

\@acmdefinitionindent The amount to indent the acmdefinition theorem style.
2239 \def\@acmdefinitionindent{\parindent}

\@acmdefinitionheadfont The font to typeset the acmdefinition theorem style head.
2240 \def\@acmdefinitionheadfont{\itshape}

\@acmdefinitionnotefont The font to typeset the acmdefinition theorem style note.
2241 \def\@acmdefinitionnotefont{\emptyset}

        Customization of acmdefinition theorem style:
2242 \ifcase\ACM@format@nr
2243 \relax % manuscript
2244 \or % acmsmall
2245 \or % acmlarge
2246 \or % acmtog
2247 \or % sigconf
2248 \or % siggraph
2249 \or % sigplan
2250 \def\@acmdefinitionbodyfont{\normalfont}
2251 \def\@acmdefinitionindent{\z@}
2252 \def\@acmdefinitionheadfont{\bfseries}
2253 \def\@acmdefinitionnotefont{\normalfont}
2254 \or % sigchi
2255 \or % sigchi-a
2256 \fi

acmdefinition The acmdefinition theorem style
2257 \newtheoremstyle{acmdefinition}%
2258  {.5\baselineskip\@plus.2\baselineskip%
2259   \@minus.2\baselineskip}% space above
2260  {.5\baselineskip\@plus.2\baselineskip%
2261   \@minus.2\baselineskip}% space below
2262  {\@acmdefinitionbodyfont}% body font
2263  {\@acmdefinitionindent}% indent amount
2264  {\@acmdefinitionheadfont}% head font
2265  {. }% punctuation after head
2266  {.5em}% spacing after head
2267  {\thmname{#1}\thmnumber{ #2}\thmnote{ {\@acmdefinitionnotefont(#3)}}}% head spec

        The definitions for theorems:
2268 \theoremstyle{acmplain}
2269 \newtheorem{theorem}{Theorem}[section]

```

```

2270 \newtheorem{conjecture}[theorem]{Conjecture}
2271 \newtheorem{proposition}[theorem]{Proposition}
2272 \newtheorem{lemma}[theorem]{Lemma}
2273 \newtheorem{corollary}[theorem]{Corollary}
2274 \theoremstyle{acmdefinition}
2275 \newtheorem{example}[theorem]{Example}
2276 \newtheorem{definition}[theorem]{Definition}
2277 \theoremstyle{acmplain}

\@proofnamefont The font to typeset the proof name.
2278 \def\@proofnamefont{\scshape}

\@proofindent Whether or not to indent proofs.
2279 \def\@proofindent{\indent}

Customization of proof environment.
2280 \ifcase\ACM@format@nr
2281   \relax % manuscript
2282   \or % acmsmall
2283   \or % acmlarge
2284   \or % acmtog
2285   \or % sigconf
2286   \or % siggraph
2287   \or % sigplan
2288   \def\@proofnamefont{\itshape}
2289   \def\@proofindent{\noindent}
2290   \or % sigchi
2291   \or % sigchi-a
2292 \fi

proof We want some customization of proof environment.
2293 \renewenvironment{proof}[1][\proofname]{\par
2294   \pushQED{\qed}%
2295   \normalfont \topsep6\p@\oplus6\p@\relax
2296   \trivlist
2297   \item[\@proofindent\hspace{\labelsep}\@proofnamefont #1\@addpunct{.}]\ignorespaces
2298   \def\@proofnamefont{\#1\@addpunct{.}}\ignorespaces
2299 }{%
2300   \popQED\endtrivlist\@endpefalse
2301 }

```

3.18 Acknowledgments

```

\acks This is a comment-like structure
2302 \specialcomment{acks}{%
2303   \begingroup
2304   \section*{Acknowledgments}
2305   \phantomsection\addcontentsline{toc}{section}{Acknowledgments}
2306 }{%

```

```

2307 \endgroup
2308 }

\grantsponsor We just typeset the name of the sponsor
2309 \def\grantsponsor#1#2#3{#2}

\grantnum
2310 \newcommand\grantnum[3][]{{#3}}
2311 \def\@tempa{#1}\ifx\@tempa\empty\else\space(\url{#1})\fi}

```

3.19 Conditional typesetting

We use the `comment` package for conditional typesetting:

```

2312 \if@ACM@screen
2313   \includecomment{screenonly}
2314   \excludecomment{printonly}
2315 \else
2316   \excludecomment{screenonly}
2317   \includecomment{printonly}
2318 \fi
2319 \if@ACM@anonymous
2320   \excludecomment{anonsuppress}
2321   \excludecomment{acks}
2322 \else
2323   \includecomment{anonsuppress}
2324 \fi

```

3.20 Additional bibliography commands

\showeprint The command `\showeprint` has two arguments: the (optional) prefix and the eprint number. Right now the only prefix we understand is the (lowercase) word ‘arxiv’ (see <http://arxiv.org/hypertex/bibstyles/>).

```

2325 \newcommand\showeprint[2][arxiv]{%
2326   \def\@tempa{#1}%
2327   \ifx\@tempa\empty\def\@tempa{arxiv}\fi
2328   \def\@tempb{arxiv}%
2329   \ifx\@tempa\@tempb
2330     arXiv:\href{http://arxiv.org/abs/#2}{#2}\else arXiv:#2%
2331   \fi}

```

3.21 End of Class

```

2332 \normalsize\normalfont\frenchspacing
2333 </class>

```

References

- [1] UK TeX Users Group. UK list of TeX frequently asked questions. <http://www.tex.ac.uk>, 2016.
- [2] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://www.ctan.org/pkg/amslatex>.
- [3] Cristophe Fiorio. *algorithm2e.sty—package for algorithms*, October 2015. <http://www.ctan.org/pkg/algorithm2e>.
- [4] Rogério Brito. *The algorithms bundle*, August 2009. <http://www.ctan.org/pkg/algorithms>.
- [5] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*, June 2015. <http://www.ctan.org/pkg/listings>.
- [6] Simon Fear. *Publication quality tables in L^AT_EX*, April 2005. <http://www.ctan.org/pkg/booktabs>.
- [7] Association for Computing Machinery. *ACM Visual Identity Standards*, 2007. <http://identitystandards.acm.org>.
- [8] Axel Sommerfeldt. *The subcaption package*, April 2013. <http://www.ctan.org/pkg/subcaption>.
- [9] Boris Veytsman, Bern Schandl, Lee Netherton, and C. V. Radhakrishnan. *A package to create a nomenclature*, September 2005. <http://www.ctan.org/pkg/nomenc>.
- [10] Nicola L. C. Talbot. *User Manual for glossaries.sty v4.25*, June 2016. <http://www.ctan.org/pkg/subcaption>.

Change History

v1.00	General: First released version	26	v1.05	General: Added processing doi numbers for acmsiggraph and doi numbers for sigproc.bib	26
v1.01	General: Changed hyperref colors in screen mode (closes https://github.com/borisveytsman/acmart/issues/1)	26		Patched \setcitestyle command; closes https://github.com/borisveytsman/acmart/issues/19	26
	Defined ACM colors	26	v1.06	\@ACM@badge@skip: Added macro	52
	Explicitly put draft option (closes https://github.com/borisveytsman/acmart/issues/4)	29		\@ACM@badge@width: Added macro	52
	Set headheight to 1pc for all formats (closes https://github.com/borisveytsman/acmart/issues/5)	26		\@ACM@title@width: Added macro	52
v1.02	General: Added TOPS and TSC (closes https://github.com/borisveytsman/acmart/issues/12)	26		\@mkttitle@i: Added processing badges	65
	Documentation changes (closes https://github.com/borisveytsman/acmart/issues/13)	26		Made generic	65
v1.03	\@formatdoi: Added macro	57	\@mkttitle@ii: Now this macro is obsolete	65	
	\if@ACM@authorversion: Added macro	27	\@mkttitle@iii: Added processing badges	65	
	\maketitle: Added special case of authorversion	60	Made more generic	65	
	General: Added anonsuppress environment	26	\@mkttitle@iv: Made more generic	66	
	Added authorversion option (closes https://github.com/borisveytsman/acmart/issues/9)	26	\@printtopmatter: Added processing badges	62	
v1.04	\acmArticleSeq: Name change by Matthew Fluet	51	\@subtitlefont: Added macro	64	
	\acmDOI: Name change by Matthew Fluet	52	\@titlefont: Added macro	64	
	\acmISBN: Name change by Matthew Fluet	52	\acmBadgeL: Added macro	52	
	General: Updated bibliography for siggraph	26	\acmBadgeR: Added macro	52	
			\if@ACM@badge: Added macro	52	
			v1.07	\maketitle: Corrected a bug with abstract footnotes	60
				Corrected a bug with permssion and footnotes order	60
			v1.08	General: SIGPLAN reformatting by Matthew Fluet	26
				Typos corrected (Tobias Pape)	26
			v1.09	General: Revert SIGPLAN caption rules	26
			v1.10	\maketitle: Corrected a bug with doi in manuscript and author vertson, https://github.com/borisveytsman/acmart/issues/36	60

General: Changes of ‘licensedothergov’ wording	55	v1.14
standardpagestyle: Reversed folios location	75	\bibstyle@acmauthoryear: Moved def of \bibstyle@acmauthoryear before use
v1.11		32
General: Customization of ACM theorem styles and proof environment by Matthew Fluet	26	\bibstyle@acmnumeric: Moved def of \bibstyle@numeric before use
v1.12		32
\@marginfigure: Now centering by default	41	General: \citetitle updates (Matthew Fluet)
\@marginintable: Now centering by default	41	Patched \citetitle
\@parfont: Moved to \section@raggedright	78	v1.15
\copyrightpermissionfootnoterule: Added macro	38	\@ACM@addtoaddress: Added macro
\descriptionlabel: Redefined	43	\@mkauthors@iii: New authors system
\footnoterule: Made shorter	39	\@shortauthors: Introduced macro .
\if@ACM@natbib@override: Added macro	27	\@typeset@author@bx: Moved to separate macro
\if@ACM@newfonts: Added macro . . .	40	\acks: Added macro
\maketitle: Moved thankses to copyrightpermission box	60	\affiliation: Added code for author groups
\section@raggedright: Introduced macro	78	\author: Added code for author groups
General: Added graceful behavior when libertine fonts are absent	40	49
Documentation updates	26	\city: Added macro
v1.13		66
\@mpfootnotetext: Made minipage footnotes centered	39	\country: Added macro
\bibliographystyle: Redefined macro	36	\department: Added macro
\bibstyle@acmauthoryear: Added macro	32	\grantnum: Added macro
\bibstyle@acmnumeric: Added macro	32	\grantsponsor: Added macro
\if@ACM@printfolios: Added macro	53	\if@insideauthorgroup: Introduced macro
General: Font adjustments for acmsmall	68	49
Increased font size for ACM Large Print bibliographic information by default for the proceedings	30	\institution: Added macro
standardpagestyle: Added headers for sigs	75	66
Expanded headers for sigchi-a	75	\num@authorgroups: Renamed
Suppressed folios if sig	75	48
v1.16		\orcid: Introduced macro
\@headfootfont: Added macro	74	50
General: Formatting header/footer (Matthew Fluet)	26	\position: Added macro
standardpagestyle: Customize header/footer text font	75	66
v1.17		\postcode: Added macro
\@makefnmark: Redefined	40	66
\@mkauthors: TOG now uses the same authors block as other journals	67	\state: Added macro
\@mkauthors@ii: Deleted	69	\streetaddress: Added macro
\@mkbibcitation: Added \nobreak Changed format for sigs	72	66

\acmArticle: The default is now numerical	51	v1.25	General: Updated PACMPL	43
\acmMonth: The default must be numerical. Closes #50.	51	v1.26	General: Corrected \shortcite bug	26
\acmNumber: The default is now numerical	51		Documentation typos fixed (thanks to Stephen Spencer)	26
\acmVolume: The default is now numerical	51	v1.27	\if@ACM@printccs: Typo corrected	53
\acmYear: The default is now numerical	51	v1.28	\ccsdesc@parse: Change from \to to \textrightarrow (Matteo Riondato)	55
\description: Decreased indent	43		General: Corrected option natbib behavior	32
\grantnum: Added url	83		Got rid of warnings in pdf keywords	35
\grantsponsor: Renamed	83	v1.29	\mkabstract: Removed spurious indentation (John Wickerson)	72
\if@ACM@printacmref: Renamed from \if@ACM@printbib	53		\ccsdesc@parse: Add spacing after bullet and around rightarrow; semicolon separators no longer in bold/italic (John Wickerson)	55
General: Slightly decreased margins for sigs	37		General: Increased head to 13pt	37
standardpagestyle: Added paper title to sigs	75		standardpagestyle: Corrected printfolios (Matthew Fluet)	75
v1.18		v1.30	\department: Added optional parameter	66
\mkauthors@i: Now we andify affiliations	68		General: Added \frenchspacing	83
\typeset@author@line: Added macro	68		Bibtex style now recognizes https:// in doi	26
General: Natbib is now the default for all formats	26		Switched to T1: looks like libertine has problems with \l in OT1	40
v1.19			Updated IMWUT and PACMPL	43
\mkabstract: Include 'Abstract' in PDF bookmarks (Matthew Fluet)	72	v1.31	\additionalaffiliation: Added macro	50
\acks: Include 'Acknowledgements' in PDF bookmarks (Matthew Fluet)	82		\mkbibcitation: Disabled linebreak	72
General: Include 'Abstract', 'Acknowledgements', and 'References' in PDF bookmarks (Matthew Fluet)	26		\startsection: Added \tochangemeasure	32
Include 'References' in PDF bookmarks (Matthew Fluet)	30		Redefined macro	34
v1.20			\textbottom: Redefined	40
\mkabstract: Deleted spurious space	72		\acmMonth: The default now is the current month (Matteo Riondato)	51
General: Bug fixes for bst	26		\acmYear: The default now is the current year (Matteo Riondato)	51
v1.21			\additionalaffiliation: Added macro	50
\showeprint: Added macro	83		\subection: Redefined macro	35
v1.22			\subsubsection: Redefined macro	35
General: More bibliography changes for Aptara	26			
v1.23				
General: Add PACMPL journal option	26			
v1.24				
General: Add IMWUT journal option	43			

General: Documentation changes . . .	26
v1.32	
\@formatdoi: New doi format	57
General: Added POMACS journal option	26
Format siggraph is now obsolete . . .	26
v1.33	
\@ACM@addtoaddress: Added obeypunctuation code	66
\@mkauthors@i: Added obeypunctuation code	68
\@mkauthors@ii: Added obeypunctuation code	69
\@mkauthors@iv: Added obeypunctuation code	71
\@subtitlefont: Added \normalsize	64
\ACM@linecountL: Renamed macro . . .	74
\ACM@linecountR: Added macro	74
\ACM@timestamp: Added current page number	74
Added macro (Michael D. Adams)	74
Added submission id	74
\acmSubmissionID: Added macro . . .	52
\city: Added obeypunctuation code . . .	66
\country: Added obeypunctuation code	66
\department: Added obeypunctuation code	66
\if@ACM@affiliation@obeypunctuation: Added macro	50
\if@ACM@authordraft: Added macro	28
\if@ACM@natbib@override: Deleted macro	27
\if@ACM@timestamp: Added macro (Michael D. Adams)	28
\institution: Added obeypunctuation code	66
\maketitle: Fixed the bug with figures on top and bottom of the title page, thanks to David Epstein	60
\position: Added obeypunctuation code	66
\postcode: Added obeypunctuation code	66
\state: Added obeypunctuation code	66
\streetaddress: Added obeypunctuation code	66
General: Added acmart-preload-hook	26
Added cmap and glyptounicode	40
BibTeX comma before articleno bug corrected	26
BibTeX crossref bug corrected	26
BibTeX numpages bug corrected	26
Documentation updates	26
Moved \citemname definition for non-natbib bibliography, so a package may redefine it	35
Switched to Type 1 fonts for libertine even if OTF-capable engine is used (Kai Mindermann)	40
\firstpagestyle: Added right linecount for two column formats	77
Added timestamp (Michael D. Adams)	77
\standardpagestyle: Added right linecount for two column formats	75
Added timestamp (Michael D. Adams)	75
v1.34	
\@mkbibcitation: Deleted DOI from doi numbers	72
\ACM@linecount@bx: Rulers now are continuous	73
\ACM@linecountL: Rulers now are continuous	74
\ACM@linecountR: Rulers now are continuous	74
\maketitle: Added date to the bibstrip in conf proceedings	60
Deleted ‘DOI’ from doi numbers	60
Rearranged bibstrip	60
The \terms command is now obsolete	60
\terms: The \terms command now just produces a warning	53
v1.35	
\style@acmauthoryear: Square brackets for author-year style	32
General: BibTeX bug fixed: et al.	26
If the copyright is set to usgov or rightsretained, the price is suppressed	55

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\\$	1426, 1430	\@acmArticle . . . 1054, 1057, 1425, 1898,
\@	1317, 1324, 1337	2010, 2011, 2015, 2018, 2021, 2023,
\@@par	304, 361	2026, 2030, 2032, 2086, 2100, 2108, 2116
\@ACM@addtoaddress	1658, 1681, 1682, 1684	\@acmdefinitionnotefont . . . 2241, 2253, 2267
\@ACM@badge@skip	1079, 1521, 1598, 1602, 1608, 1617, 1627, 1633, 1642	\@acmownedfalse . 1179, 1182, 1185, 1191, 1195, 1198, 1201, 1207
\@ACM@badge@width	1076, 1520, 1525, 1597, 1601, 1607, 1619, 1626, 1628, 1631, 1643, 1646	\@acmownedtrue . . . 1168, 1175, 1204
\@ACM@badgefalse	1075	\@acmplainbodyfont . . . 2208, 2220, 2232
\@ACM@badgetrue	1081, 1086	\@acmplainheadfont . . . 2210, 2222, 2234
\@ACM@commabox	1658, 1662, 1663	\@acmplainindent . . . 2209, 2221, 2233
\@ACM@journalfalse	139, 141, 143, 145, 147	\@acmplainnotefont . . . 2211, 2223, 2237
\@ACM@journaltrue	131, 133, 135, 137	\@adddotafter 2145, 2149, 2205
\@ACM@manuscriptfalse	126	\@additionalaffiliation 1008, 1009
\@ACM@manuscripttrue	124	\@addpunct 1930, 2205, 2206, 2298
\@ACM@newfontsfalses	592, 594, 597	\@addspaceafter 2189, 2194, 2206
\@ACM@newfontstrue	589	\@affiliationfont 1711, 1716, 1720, 1723, 1726, 1729, 1732, 1735, 1763, 1781
\@ACM@reviewtrue	100	\@afterheading 335, 1463
\@ACM@sigchiamafalse	128	\@afterindentfalse 281, 1462
\@ACM@sigchiamedetru	148	\@afterindenttrue 279
\@ACM@timestamptrue	99	\@author 969, 972, 977, 1749, 1804, 1843
\@ACM@title@width	1078, 1595, 1597, 1598, 1601, 1602, 1610, 1624, 1626, 1627, 1635	\@authorfont 1710, 1715, 1719, 1722, 1725, 1728, 1731, 1734, 1751, 1781
\@DeclareACMFormat	37, 38, 39, 40, 41, 42, 43, 44, 45, 46	\@authornotemark 1046, 1869
\@M	304, 343, 361, 370	\@authornotes 1043, 1047, 1378
\@abstract	1098, 1879, 1886	\@auxout 438
		\@begindocumenthook 434

```

{@botnum ..... 1368           1487, 1518, 1523,           {@input ..... 372
{@citestyle ..... 213          1596, 1600, 1605,           {@insideauthorgroupfalse
{@classname 25, 27, 34,        1613, 1616, 1629,           ..... 1002
      50, 52, 53, 58, 60,        1637, 1644, 1654,           {@insideauthorgrouptrue
      61, 66, 68, 69, 74,        1740, 1750, 1758,           ..... 965
      76, 77, 82, 84, 85,        1759, 1804, 1810,           {@journalCode .. 691, 938
      90, 92, 93, 98, 102,       1815, 1843, 1849,           {@journalCode@nr ...
      103, 114, 119, 172,       1854, 1871, 1971,           ..... 691, 743, 943
      590, 593, 595, 938,       2211, 2241, 2311, 2327,           {@journalName .. 745,
      940, 1007, 1093,           {@endfloatbox ..... 650           749, 753, 758, 762,
      1103, 1105, 1106,           {@endeffalse ..... 2300           766, 770, 774, 778,
      1109, 1111, 1112,           {@endwidetextbox 650, 658           779, 781, 782, 785,
      1115, 1117, 1118, 1891,     {@finalstrut ... 564, 577           786, 789, 793, 797,
{@clubpenalty ..... 349          {@float ..... 652           799, 803, 807, 809,
{@concepts ..... 1151,         {@flushglue ..... 2154           811, 813, 817, 821,
      1158, 1439, 1441, 1460,    {@fnssymbol ..... 1365           825, 829, 833, 837,
{@copyrightowner ...           {@folio@ht .....           841, 845, 849, 853,
      ..... 1211, 1402           2050, 2076, 2082, 2083           857, 861, 865, 869,
{@copyrightpermission ...       {@folio@max 2050, 2072, 2073           870, 873, 877, 878,
{@copyrightyear ...           {@folio@voffset 2050, 2078           881, 886, 890, 894,
      ..... 1344, 1402, 1404,    {@folio@wd ..... 2050,           898, 902, 906, 910,
{@currbox ... 664, 665, 666,   2083, 2084, 2105, 2113           914, 918, 922, 926,
{@currentaffiliation ...       {@folioblob ..... 2070,           930, 934, 944, 945,
      ..... 1782, 1785, 1803,    2102, 2104, 2110, 2111           1414, 2014, 2022,
      1810, 1811, 1813,           {@footnotemark . 382, 1363           2031, 2099, 2107, 2115
      1815, 1816, 1820,           {@footnotemark@nolink ..... 382, 1363           {@journalNameShort .
      1842, 1849, 1850,           {@footnotetext .....           746, 750, 755,
      1852, 1854, 1855, 1859,    383, 555, 1364           759, 763, 767, 771,
{@currentaffiliations ...       {@footnotetext@nolink ..... 383, 1364           775, 790, 794, 800,
      ..... 1740,               1421, 1427, 1431, 1907           804, 814, 818, 822,
      1741, 1742, 1744,           {@for ..... 189           826, 830, 834, 838,
      1747, 1759, 1760, 1765,    {@formatdoi ..... 1239,           842, 846, 850, 854,
{@currentauthors 1738,          1421, 1427, 1431, 1907           858, 862, 866, 874,
      1739, 1746, 1750,           {@fps ..... 651           879, 882, 887, 891,
      1751, 1753, 1781,           {@fpsadddefault ..... 651           895, 899, 903, 907,
      1784, 1802, 1804,           {@gobble ..... 211,           911, 915, 919, 923,
      1805, 1807, 1841,           255, 1667, 1670,           927, 931, 935, 945, 1897
      1843, 1844, 1846, 1869,    1671, 1672, 1673, 1674           {@keywords 1095, 1444, 1450
{@currentlabel . 559, 573,       {@hangfrom ..... 303, 360           {@latex@error ..... 257
{@dblarg ..... 290,             {@headfootfont .....           {@empty ..... 1100, 1879
{@dblfloat ..... 648,             1977, 2010, 2011,           {@em ..... 292
{@department .. 1012, 1013,    2012, 2013, 2017,           {@makefnmark ... 554,
{@dotsep ..... 2207,             2020, 2025, 2029,           579, 1370, 1375, 1379
{@empty . 150, 294, 953,       2035, 2036, 2037, 2039           {@makefntext ..... 554, 563, 576, 1380
      967, 982, 987, 988,           {@ifnextchar ..... 1012           {@marginfigure . 640, 641
      994, 1132, 1133,           {@ifnotempty ..... 1350           {@marginable .. 643, 644
      1139, 1146, 1151,           {@ifnum ..... 227, 229           {@minipagefalse . 550, 660
      1381, 1418, 1426,           {@ifstar ..... 288           {@minus ... 2135, 2139,
      1430, 1439, 1444,           {@iiiparbox ..... 553           2143, 2147, 2151,

```

2182, 2187, 2192, 2229, 2231, 2259, 2261
 \emkabstract .. 1437, 1878
 \emkauthors 1371, 1373, 1866
 \emkauthors@i .. 1690, 1692, 1694, 1696, 1745
 \emkauthors@ii .. 1775
 \emkauthors@iii .. 1698, 1700, 1702, 1704, 1786
 \emkauthors@iv 1706, 1831
 \emkbibcitation 1457, 1888
 \emkteasers ... 1371, 1870
 \emkttitle ... 1371, 1530
 \emkttitle@i ... 1533, 1535, 1537, 1539, 1594
 \emkttitle@ii ... 1622
 \emkttitle@iii ... 1541, 1543, 1545, 1547, 1622
 \emkttitle@iv ... 1549, 1650
 \empargs 553
 \mparswitchfalse .. 518
 \mpfootins 545, 546, 548, 568, 569
 \mpfootnotetext ... 567
 \one 215, 219, 223, 225, 424, 1936, 1941
 \nil 234
 \nobreakfalse .. 337, 377
 \noskipsecfalse ... 341
 \noskipsectrue ... 338
 \par 1383
 \parboxrestore ... 572
 \parfont . 2149, 2153, 2158
 \permissionCodeOne
 747,
 751, 756, 760, 764,
 768, 772, 776, 783,
 787, 791, 795, 801,
 805, 815, 819, 823,
 827, 831, 835, 839,
 843, 847, 851, 855,
 859, 863, 867, 871,
 875, 883, 888, 892,
 896, 900, 904, 908,
 912, 916, 920, 924,
 928, 932, 936, 946, 1425
 \permissionCodeTwo
 884, 947
 \oplus .. 370, 378, 580,
 2135, 2139, 2143,

2147, 2151, 2182, 2187, 2192, 2228,
 2230, 2258, 2260, 2295
 \printcopyrightfalse
 1178, 1190
 \printcopyrighttrue
 1164, 1174
 \printendtopmatter
 1461, 1909
 \printpermissionfalse
 1177
 \printpermissiontrue
 ... 1166, 1173, 1189
 \printtopmatter ...
 1372, 1486
 \proofindent ...
 ... 2279, 2289, 2297
 \proofnamefont ...
 ... 2278, 2288, 2298
 \received ... 1130, 1133,
 1134, 1136, 1139,
 1140, 1142, 1146, 1147
 \rightskip ... 2154, 2155
 \saveabstract 1097, 1098
 \saveteaser ... 1347, 1348
 \seccntformat . 297, 354
 \secfont ... 2137, 2158
 \secpenalty ... 286
 \sect ... 290, 291
 \setaddresses ... 1877
 \setthanks ... 1383, 1930
 \shortauthors ...
 ... 1976, 2006,
 2012, 2018, 2026, 2036
 \sidebar ... 637, 638
 \specialsection ...
 1440, 1446, 1448, 1465
 \ssect ... 289, 355
 \startPage ... 1091,
 1487, 1488, 1490, 1970
 \startsection ...
 ... 275, 367, 2134,
 2138, 2142, 2146,
 2150, 2181, 2186, 2191
 \starttoc ... 367
 \subparfont ... 2194, 2195
 \subsecfont ... 2141, 2158
 \subsubsecfont 2145, 2158

\subtitle ... 958,
 1035, 1613, 1614,
 1637, 1638, 1654, 1655
 \subtitlefont ...
 1573, 1614, 1638, 1655
 \subtitlenotes ...
 1033, 1037, 1040, 1377
 \svsec . 294, 297, 303, 318
 \svsechd ... 316, 344, 364
 \teaser ... 1348, 1872
 \teaserfigures ...
 1346, 1348, 1871, 1875
 \tempa
 189, 190, 192, 194,
 196, 198, 200, 202,
 204, 206, 208, 210,
 212, 214, 216, 218,
 220, 222, 224, 226,
 228, 230, 232, 234,
 237, 239, 241, 243,
 245, 247, 986, 987,
 1131, 1132, 1758,
 2311, 2326, 2327, 2329
 \tempb ... 190, 192,
 194, 196, 198, 200,
 202, 204, 206, 208,
 210, 212, 214, 216,
 218, 220, 222, 224,
 226, 228, 230, 232,
 237, 239, 241, 243,
 245, 247, 2328, 2329
 \tempboxa 553
 \tempc . 235, 236, 238,
 240, 242, 244, 246, 248
 \tempcnta 2070,
 2072, 2073, 2075, 2077
 \tempdim ...
 2076, 2077, 2078, 2080
 \tempskipa ...
 278, 280, 281, 286,
 299, 300, 331, 332,
 334, 346, 347, 356, 357
 \textbottom ... 580
 \textsuperscript ...
 579, 1370, 1375
 \texttop ... 581
 \thefnmark . 560, 574,
 579, 1370, 1375, 1379
 \title ... 1026, 1460,
 1612, 1636, 1653, 1895

```

\@titlefont 1552, 1604, 1611, 1623, 1635, 1651
\@titlenotes . . . . . 1024, 1028, 1031, 1376
\@tochangmeasure 308, 321
\@toclevel . . . . . 292
\@tocline . . . . . 380, 381
\@topnum . . . . . 1366
\@typeset@author@bx . . . . . 1779, 1824, 1830, 1863, 1868
\@typeset@author@line . . . . . 1737, 1748, 1770, 1772
\@undefined . . . . . 434
\@width . . . . . 536, 541
\@xp . . . . . 374, 375
\@xsect . . . . . 329, 330, 366
\@z . . . . . 221
\\ 454, 1402, 1407, 1422, 1426, 1430, 1890, 1940
\{ . . . . . 197
\} . . . . . 197
\_\_ . . . . . 1157, 1402, 1404, 1426, 1898, 1904, 1970

A
\abstract . . . . . 1097
abstract (environment) 16
\acks . . . . . 2302
acks (environment) . . . . 20
\acm@copyrightinput 1170
\acm@copyrightmode . . . . . 1170, 1176, 1181, 1184, 1188, 1194, 1197, 1200, 1203, 1206, 1212, 1241
\ACM@fontsize . . . . . 106, 150, 153, 155, 157, 159, 161, 163, 165, 167, 169, 172, 173
\ACM@format . . . . . 31, 114
\ACM@format@nr . . . . . 31, 114, 118, 123, 129, 151, 392, 458, 523, 616, 668, 1466, 1494, 1531, 1553, 1574, 1688, 1712, 1910, 1978, 2002,
\ACM@linecount . . . . . 2057, 2093, 2126, 2163, 2212, 2242, 2280
\ACM@linecount@bx . . . . . 1935, 1936, 1940, 1941
\ACM@linecount@bxht . . . . . 1932, 1949, 1956
\ACM@linecountL . . . . . 1945, 2004, 2007, 2010, 2013, 2017, 2019, 2025, 2027, 2035, 2037, 2095, 2102, 2103, 2111, 2112, 2118, 2121
\ACM@linecountR . . . . . 1952, 2028, 2030, 2036, 2040, 2119, 2122
\ACM@mk@linecount . . . . . 1937, 1947, 1954
\ACM@timestamp . . . . . 1959, 2046, 2127, 2130
\acmArticle . . . . . 13, 1054
\acmArticleSeq . . . . . 14, 1056
\acmBadgeL . . . . . 14, 1086
\acmBadgeR . . . . . 14, 1081
\acmConference . . . . . 9, 948
\acmConference@date . . . . . 951, 1398, 1416, 1902, 2038, 2040
\acmConference@name . . . . . 950, 1416, 1901, 1903
\acmConference@shortname . . . . . 949, 953, 954, 1398, 1903, 1904, 2037, 2039
\acmConference@venue . . . . . 952, 1398, 1901, 2038, 2040
\acmdefinition . . . . . 2257
\acmDOI . . . . . 14, 1072
\acmISBN . . . . . 14, 1070
\acmJournal . . . . . 7, 942
\acmMonth . . . . . 13, 1060
\acmNumber . . . . . 13, 1052
\acmplain . . . . . 2227
\acmPrice . . . . . 14, 1066, 1186, 1192
\acmSubmissionID . . . . . 14, 1068
\acmVolume . . . . . 13, 1050
\acmYear . . . . . 13, 1058
\addcontentsline . . . . . 185, 310, 323, 1880, 2305
\additionalaffiliation . . . . . 10, 1008
\addpenalty . . . . . 286
\addresses . . . . . 967, 969, 972, 977, 1004, 1022, 1046, 1772, 1830, 1868
\addtolength . . . . . 1942
\addvspace . . . . . 286, 378
\advance . . . . . 964, 1597, 1598, 1601, 1602, 1626, 1627, 1788, 1801, 1833, 1840, 1941, 2073, 2075, 2078
\affiliation . . . . . 9, 1001, 1757, 1815, 1854
\and . . . . . 977, 978, 991, 997, 1748, 1753, 1755, 1765, 1770, 1779, 1809, 1824, 1830, 1848, 1863, 1868
\andify . . . . . 1452, 1453, 1738, 1741
\anonsuppress (environment) . . . . . 20
\AtBeginDocument . . . . . 427, 435
\AtEndDocument . . . . . 1145
\author . . . . . 9, 962, 1359, 1360, 1892
\author@bx . . . . . 1775, 1780, 1783
\author@bx@sep . . . . . 1777, 1783, 1788, 1801, 1833, 1840
\author@bx@wd . . . . . 1776, 1779, 1787, 1788, 1793, 1795, 1797, 1799, 1801, 1832, 1833, 1838, 1840
\authornote . . . . . 13, 1008, 1044, 1893
\authors . . . . . 970, 973, 978, 1452, 1454, 1459, 1895
B
\baselineskip . . . . . 1392, 1606, 1618, 1630, 1645, 1939, 1942, 2135, 2136,

```

2139, 2140, 2143,	\ccsdesc@parse 1153, <u>1154</u>	374, 375, 560, 574,
2147, 2182, 2183,	CCSXML (environment) . . 15	1156, 1157, 1158, 1159
2187, 2192, 2228,	\centering 371, 453, 575,	\CurrentOption . 107,
2229, 2230, 2231,	642, 645, 1623,	108, 109, 110, 111, 112
2258, 2259, 2260, 2261	1635, 1780, 1829, 2085	
\begin . 20, 1948, 1955, 2079	\cite 415, 416, 428, 432	D
\begingroup	\citeA 422	\day 1968
301, 344, 358, 367,	\citealt 421	\DeclareNewFootnote 539
423, 1362, 1686, 2303	\citeANP 417	\DeclareOptionX
\bfseries . . . 683, 1387,	\citeauthor 417	37, 107,
1555, 1557, 1559,	\citeN 415	108, 109, 110, 111, 112
1563, 1565, 1567,	\citebyname 429	\DeclareRobustCommand 422
1569, 1571, 1731,	\citeNN 418	\def 25, 37, 106, 153,
1734, 1894, 2086,	\citeNP 421	155, 157, 159, 161,
2158, 2159, 2173,	\citep 416	163, 165, 167, 169,
2174, 2176, 2177,	\citetitle 21, 253, 273	190, 192, 194, 196,
2179, 2180, 2185,	\citeyear 419, 420, 432	198, 200, 202, 204,
2190, 2198, 2199,	\citeyearNP 419	206, 208, 210, 212,
2202, 2203, 2222, 2252	\citeyearpar 418, 420	214, 215, 216, 217,
\bgroup 638, 641,	\city 11, 1015, <u>1666</u>	218, 219, 220, 221,
644, 649, 1009,	\ClassError	222, 223, 224, 226,
1439, 1444, 1779,	34, 940, 1007,	228, 230, 232, 233,
1865, 1872, 1878, 1888	1106, 1112, 1118, 1891	237, 239, 241, 243,
\bibfont 187	\ClassInfo 114, 172,	245, 247, 275, 291,
\biblofont 187	938, 1103, 1105,	316, 330, 354, 355,
\bibliographystyle . . . 433	1109, 1111, 1115, 1117	364, 367, 380, 381,
\bibsection 183	\ClassWarning 27,	386, 387, 388, 389,
\bibstyle 211, 213, 255, 438	119, 590, 593, 595, 1093	433, 535, 540, 542,
\bibstyle@acmauthoryear	\cleaders 1663	554, 556, 567, 579,
..... 261	\clubpenalty 343, 349	580, 638, 641, 644,
\bibstyle@acmnumeric . . . 267	\CodelineIndex 17	649, 651, 655, 658,
\bigskip	\Collect@Body 637,	676, 677, 678, 679,
1147, 1515, 1621,	640, 643, 1097, 1347	745, 746, 747, 749,
1649, 1657, 1830,	\color 1390, 1940	750, 751, 753, 755,
1868, 1872, 1918,	\color@begingroup 562, 575	756, 758, 759, 760,
1920, 1922, 1924, 1926	\color@endbox 663	762, 763, 764, 766,
\box 665, 1496, 1499, 1502,	\color@endgroup	767, 768, 770, 771,
1505, 1507, 1509,	551, 565, 578	772, 774, 775, 776,
1511, 1513, 1515,	\columnwidth 536,	778, 779, 781, 782,
1771, 1783, 1828, 1874	571, 649, 1832, 1865	783, 785, 786, 787,
C	\contentsnamefont 371	789, 790, 791, 793,
\c@footnote 1365	\copy 1663	794, 795, 797, 799,
\c@secnumdepth 293, 307, 311, 320, 324	\copyright 1402	800, 801, 803, 804,
\captionsetup	\copyrightpermissionfootnoterule 535	805, 807, 809, 811,
... 608, 610, 612,	\copyrightyear 16, <u>1344</u>	813, 814, 815, 817,
614, 623, 625, 628,	\country 11, 1018, <u>1666</u>	818, 819, 821, 822,
631, 638, 641, 644, 1873	255, 306, 308, 312,	823, 825, 826, 827,
\ccsdesc 15, <u>1152</u>	319, 321, 325, 354,	829, 830, 831, 833,
		834, 835, 837, 838,
		839, 841, 842, 843,

845, 846, 847, 849,
 850, 851, 853, 854,
 855, 857, 858, 859,
 861, 862, 863, 865,
 866, 867, 869, 870,
 871, 873, 874, 875,
 877, 878, 879, 881,
 882, 883, 884, 886,
 887, 888, 890, 891,
 892, 894, 895, 896,
 898, 899, 900, 902,
 903, 904, 906, 907,
 908, 910, 911, 912,
 914, 915, 916, 918,
 919, 920, 922, 923,
 924, 926, 927, 928,
 930, 931, 932, 934,
 935, 936, 942, 943,
 944, 945, 946, 947,
 958, 986, 1008,
 1009, 1010, 1011,
 1012, 1013, 1024,
 1025, 1033, 1034,
 1043, 1044, 1050,
 1052, 1054, 1056,
 1058, 1060, 1062,
 1066, 1068, 1070,
 1072, 1082, 1083,
 1084, 1085, 1087,
 1088, 1089, 1090,
 1091, 1093, 1095,
 1098, 1100, 1119,
 1130, 1131, 1155,
 1209, 1211, 1239,
 1240, 1344, 1346,
 1348, 1357, 1370,
 1375, 1383, 1465,
 1486, 1530, 1552,
 1573, 1594, 1622,
 1650, 1659, 1668,
 1676, 1677, 1680,
 1683, 1686, 1710,
 1711, 1715, 1716,
 1719, 1720, 1722,
 1723, 1725, 1726,
 1728, 1729, 1731,
 1732, 1734, 1735,
 1737, 1739, 1744,
 1745, 1746, 1747,
 1749, 1756, 1757,
 1758, 1779, 1786,
 1804, 1810, 1815,
 1831, 1843, 1849,
 1854, 1869, 1870,
 1872, 1877, 1878,
 1888, 1889, 1890,
 1891, 1909, 1930,
 1937, 1945, 1952,
 1976, 1977, 2056,
 2063, 2068, 2070,
 2154, 2158, 2159,
 2160, 2161, 2167,
 2168, 2170, 2171,
 2173, 2174, 2176,
 2177, 2179, 2180,
 2185, 2190, 2195,
 2198, 2199, 2202,
 2203, 2205, 2206,
 2208, 2209, 2210,
 2211, 2220, 2221,
 2222, 2223, 2238,
 2239, 2240, 2241,
 2250, 2251, 2252,
 2253, 2278, 2279,
 2288, 2289, 2309,
 2311, 2326, 2327, 2328
 \define@boolkey
 48, 56,
 64, 72, 80, 88, 96,
 1006, 1101, 1107, 1113
 \define@choicekey
 31, 691, 1169
 \definecolor
 441, 442, 443,
 444, 445, 446, 447, 448
 \department 11, 1012, 1666
 \description 684
 \descriptionlabel 683, 686
 \dimexpr 647, 665, 2043
 \divide 1793,
 1795, 1797, 1799, 1838
 \do 189
 \DocInput 21
 \documentclass 9
 \dots 1430
 E
 \edef 107, 108, 109, 110, 292
 \egroup 552,
 639, 642, 645,
 656, 662, 1019,
 \email 9,
 1020, 1756, 1810, 1849
 \emph 1414, 1416
 \EnableCrossrefs 19
 \end 22, 1950, 1957, 2087
 \enddblfloat 654
 \endfloat 656
 \endcsname 254,
 255, 306, 308, 312,
 319, 321, 325, 354,
 374, 375, 560, 574,
 1156, 1157, 1158, 1159
 \enddescription 690

\endgroup	305, 344, 362, 377, 1435, 1708, 2307	122, 127, 149, 170, 171, 180, 191, 193,
\endlist	688, 690	195, 197, 199, 201,
\endminipage	542	203, 205, 207, 209,
\endtrivlist	2300	211, 213, 215, 217,
\enspace	2206	219, 221, 223, 225,
environments:		227, 229, 231, 233,
abstract	16	238, 240, 242, 244,
acks	20	246, 248, 249, 258,
anonsuppress	20	260, 274, 276, 282,
CCSXML	15	287, 292, 298, 309,
marginfigure	19	313, 322, 326, 328,
marginstable	19	351, 352, 365, 376,
printonly	19	404, 413, 430, 432,
screenonly	19	436, 439, 456, 520,
sidebar	19	534, 549, 566, 586,
teaserfigure	17	603, 606, 633, 634,
\everypar	284, 339, 350	653, 657, 682, 937,
\excludecomment	1150, 2314, 2316, 2320, 2321	955, 966, 974, 979, 980, 984, 992, 998,
\ExecuteOptionsX	47, 55, 63, 71, 79, 87, 95, 105	999, 1000, 1005, 1023, 1032, 1042, 1049, 1065, 1106,
\expandafter	234, 236, 435, 553, 1156, 1157, 1159	1112, 1118, 1128, 1129, 1137, 1143, 1144, 1148, 1158, 1162, 1180, 1183,
F		1187, 1193, 1196, 1199, 1202, 1205, 1208, 1238, 1343, 1355, 1360, 1361,
\familydefault	605	1371, 1373, 1384, 1391, 1394, 1395, 1399, 1400, 1405, 1417, 1422, 1426,
\fancyfoot	2008, 2014, 2022, 2031, 2034, 2046, 2096, 2097, 2099, 2107, 2115, 2123, 2127, 2130	1430, 1432, 1433, 1434, 1442, 1443, 1449, 1451, 1458, 1485, 1491, 1522,
\fancyhead	. 2004, 2005, 2006, 2007, 2010, 2011, 2012, 2013, 2017, 2019, 2020, 2025, 2027, 2028, 2029, 2035, 2036, 2037, 2039, 2095, 2102, 2103, 2104, 2110, 2111, 2112, 2118, 2119, 2121, 2122	1526, 1527, 1528, 1550, 1572, 1593, 1599, 1603, 1609, 1615, 1620, 1632, 1634, 1639, 1647, 1648, 1656, 1664, 1676, 1677, 1679,
\fancyheadoffset	2043, 2105, 2113	1680, 1683, 1685, 1707, 1736, 1743, 1754, 1768, 1769, 1780, 1800, 1808,
\fancyhf	1999, 2090	
\fancypagestyle	1998, 2089	
\fi	53, 61, 69, 77, 85, 93, 103,	
G		
\g@addto@macro	977, 978, 991, 997, 1004, 1022, 1026, 1028, 1031, 1035, 1037, 1040, 1046, 1047, 1136, 1142, 1158, 1159, 1348, 1352, 1354, 1753, 1765, 1807, 1813, 1820, 1846, 1852, 1859, 1869	

```

\gdef 949, 950, 951, 952, \if@ACM@affiliation@obeypunktcopyright .  

954, 969, 970, 972, 1006, 1661, 1676, ..... 1163, 1401  

973, 983, 989, 995, 1677, 1678, 1680, 1683 \if@printpermission  

1098, 1134, 1140, ..... 1165, 1394  

1157, 1488, 1751, .....  

1755, 1760, 1784, .....  

1785, 1802, 1803, .....  

1805, 1809, 1811, .....  

1816, 1841, 1842, .....  

1844, 1848, 1850, 1855 \if@ACM@anonymous ..  

\geometry .....  

460, 463, 470, 477, .....  

484, 491, 498, 505, 512 \if@ACM@authordraft ..  

\global ..... 338, .....  

341, 377, 568, 664, .....  

964, 965, 1002, .....  

1366, 1368, 1454, .....  

1455, 1748, 1770, .....  

1771, 1780, 1824, .....  

1827, 1863, 1874, 1941 \if@ACM@authorversion ..  

\grantnum ..... 20, 2310 \if@ACM@badge ..  

\grantsponsor .. 20, 2309 \if@ACM@journal ..  

\ifcsname ..... 254  

\ifdim 280, 300, 332, 357, 1943  

\IfFileExists 590, 593, 595  

\ifNAT@numbers ..... 432  

\ifnum ..... 118, 123,  

292, 293, 307, 311,  

320, 324, 1160,  

1161, 1176, 1181,  

1184, 1188, 1194,  

1197, 1200, 1203,  

1206, 1360, 2072, 2126  

\ifPDFTeX ..... 583  

\ifvmode ..... 1660  

\ifvoid ..... 545  

\ifx . 150, 190, 192, 194,  

196, 198, 200, 202,  

204, 206, 208, 210,  

212, 214, 216, 218,  

220, 222, 224, 226,  

228, 230, 232, 237,  

239, 241, 243, 245,  

247, 434, 953, 967,  

982, 987, 988, 994,  

1132, 1133, 1139,  

1146, 1156, 1381,  

1418, 1426, 1430,  

1439, 1444, 1487,  

1518, 1523, 1596,  

1600, 1605, 1613,  

1616, 1629, 1637,  

1644, 1654, 1740,  

1750, 1758, 1759,  

1804, 1810, 1815,  

1843, 1849, 1854,  

1871, 1879, 1903,  

1971, 2311, 2327, 2329  

H  

\hbox . 579, 1370, 1375, 1662 \if@ACM@newfonts 588, 598  

\headrulewidth 2000, 2091 \if@ACM@printacmref .....  

\hfill ..... 1652 \if@ACM@printccs ..  

\href . 1519, 1524, 1606, .....  

1618, 1630, 1645, 2330 \if@ACM@printfolios ..  

\hrule .... 536, 541, 1652 .....  

\hrulefill . 1497, 1500, .....  

1503, 1912, 1914, 1916 \if@ACM@review ..  

\hsize ..... 571, .....  

1369, 1594, 1595, .....  

1622, 1624, 1650, .....  

1687, 1779, 1826, 1865 \if@ACM@screen 48, 405, 2312  

\hskip ..... 303, \if@ACM@sigchiamode ..  

317, 347, 360, 364, .....  

1521, 1608, 1617, .....  

1633, 1642, 1663, 2297 \if@ACM@timestamp ..  

\hspace ... 683, 1251, .....  

1262, 1271, 1288, .....  

1302, 1314, 1783, 1829 \if@acmowned .. 1167  

\Huge ..... 1561, 1563, \if@filesw .. 373, 437  

1565, 1567, 1569, 1571 \if@insideauthorgroup ..  

\hypersetup 406, 412, 1459 .....  

\if@nobreak .. 283  

\if@noskipsec .. 276, 340  

I  

\if ..... 235

```

\ignorespaces	1652	\medskip
... 353, 564, 577,	1652	1468, 1470, 1472,
1010, 1011, 1013,	1652	1474, 1771, 1773,
1668, 1886, 1890, 2298	1652	1828, 1875, 1894,
\immediate	375, 438	1909, 1912, 1914, 1916
\includecomment	2313, 2317, 2323	\mkttitle@bx 1356,
\includegraphics	1520, 1525,	1496, 1499, 1502,
1607, 1619, 1631, 1646	1520	1505, 1507, 1509,
\indent	2279	1511, 1513, 1515,
\input	584	1604, 1623, 1651,
\InputIfFileExists ..	26	1771, 1827, 1828, 1874
\institution 11, 1011, 1666	1666	\month 1061, 1968
\interfootnotelinepenalty	558	\moveleft 664
\interlinepenalty	304, 361, 558	\multiply 2077
\item	2297	
\itemindent	685	
\itshape .. 1398, 2160,	1398	
2161, 2190, 2195,	2160	
2208, 2220, 2240, 2288	2160	
J		
\jobname	372, 375	
K		
\kern 535, 536, 540, 541, 1652	535	
\keywords	15, 1095	
L		
\l@subsection	380	
\l@subsubsection	381	
\labelenumi	676	
\labelenumii	677	
\labelenumiii	678	
\labelenumiv	679	
\labelsep	683, 2297	
\labelwidth	686	
\LARGE	1555,	
1557, 1559, 1582,	1555	
1584, 1586, 1588,	1557	
1590, 1719, 1722, 2086	1559	
\Large 1710, 1728, 2173,	1582	
2174, 2176, 2177, 2179	1586	
\large	1387,	
1715, 1720, 1723,	1588	
2167, 2168, 2170, 2171	1590	
\lastbox	342	
M		
\makebox	1387, 2080	
\makelabel	686	
\maketitle	17, 1357	
\MakeUppercase		
... 1751, 1753,		
2158, 2167, 2170,		
2173, 2176, 2198, 2202		
\marginfigure	640	
marginfigure (environment)	640	
\marginpar	556,	
639, 642, 645, 1517		
\marginparsep	647, 2043	
\marginparwidth	647, 2043	
\marginitable	643	
marginitable (environment)	643	
\mbox	233	
\mdseries		
1576, 1578, 1580,		
1584, 1586, 1588,		
1590, 1592, 1732, 1735		

\newcount	960, 1935	O	1583, 1585, 1587,
\newcounter . . .	1962, 1964	\onehalfspacing	1589, 1591, 1691,
\newdimen	646,	\openout	1693, 1695, 1697,
	1776, 2050, 2052, 2054	\or	1699, 1701, 1703,
\newenvironment		132,	1705, 1714, 1717,
	640, 643, 1347	134, 136, 138, 140,	1718, 1721, 1724,
\newfloat	635	142, 144, 146, 154,	1727, 1730, 1733,
\newif	115, 116, 117, 588,	156, 158, 160, 162,	1791, 1792, 1794,
	1074, 1163, 1165, 1167	164, 166, 168, 394,	1796, 1836, 1913,
\newlength		395, 396, 397, 398,	1915, 1917, 1919,
	1076, 1078, 1079, 1934	399, 401, 402, 462,	1921, 1923, 1925,
\newsavebox	1933	469, 476, 483, 490,	1927, 1981, 1983,
\newskip	1777	497, 504, 511, 525,	1985, 1987, 1989,
\newtheorem		526, 527, 529, 530,	1991, 1993, 1995,
	2269, 2270, 2271,	531, 532, 533, 618,	2009, 2016, 2024,
	2272, 2273, 2275, 2276	619, 620, 621, 622,	2059, 2064, 2098,
\newtheoremstyle	2227, 2257	624, 627, 630, 670,	2106, 2114, 2165,
\newwrite	374	671, 672, 673, 674,	2166, 2169, 2172,
\nobreak	333, 1894	675, 680, 681, 748,	2175, 2178, 2196,
\noindent		752, 757, 761, 765,	2200, 2214, 2215,
	. 554, 1147, 1380,	769, 773, 777, 780,	2216, 2217, 2218,
	1468, 1470, 1472,	784, 788, 792, 796,	2219, 2224, 2225,
	1474, 1493, 1497,	798, 802, 806, 808,	2244, 2245, 2246,
	1500, 1503, 1517,	810, 812, 816, 820,	2247, 2248, 2249,
	1604, 1611, 1614,	824, 828, 832, 836,	2254, 2255, 2282,
	1638, 1652, 1653,	840, 844, 848, 852,	2283, 2284, 2285,
	1655, 1738, 1771,	856, 860, 864, 868,	2286, 2287, 2290, 2291
	1772, 1827, 1867,	872, 876, 880, 885,	\orcid 9, 1024
	1874, 1875, 1882,	889, 893, 897, 901,	\outer@nobreak 661
	1894, 1895, 1907,	905, 909, 913, 917,	
	1912, 1914, 1916, 2289	921, 925, 929, 933,	
\nolinkurl		1062, 1063, 1064,	
	1811, 1813, 1850, 1852	1213, 1215, 1218,	
\normalcolor	547	1220, 1221, 1223,	
\normalfont	579, 1147,	1225, 1227, 1230,	
	1375, 1711, 1716,	1233, 1235, 1242,	P
	1725, 1726, 1728,	1253, 1264, 1272,	\p@ 378, 521,
	1729, 2223, 2238,	1278, 1290, 1304,	528, 535, 536, 540,
	2250, 2253, 2295, 2332	1316, 1323, 1330,	541, 685, 2135,
\normalsize	1573, 1711,	1336, 1469, 1471,	2139, 2143, 2144,
	1725, 1726, 1729, 2332	1473, 1475, 1477,	2147, 2148, 2151,
\num@authorgroups . . .		1479, 1481, 1483,	2152, 2182, 2187,
	. . 960, 964, 1360,	1498, 1501, 1504,	2188, 2192, 2193, 2295
	1789, 1793, 1795, 1834	1506, 1508, 1510,	\PackageError 53,
\number	292	1512, 1514, 1534,	61, 69, 77, 85, 93, 103
\numberline	312, 325	1536, 1538, 1540,	\PackageInfo 50, 52, 58,
\numexpr	1961, 1963, 1965	1542, 1544, 1546,	60, 66, 68, 74, 76,
		1548, 1556, 1558,	82, 84, 90, 92, 98, 102
		1560, 1562, 1564,	\PageIndex 16
		1566, 1568, 1570,	\pageref 1970
		1577, 1579, 1581,	\pagestyle 2049
			\par 277, 333, 369,
			543, 659, 1147,
			1383, 1394, 1398,
			1441, 1450, 1468,

1470, 1472, 1474,	\pushQED	2294	203, 253, 605, 683,
1496, 1497, 1499,	\put	1949, 1956	962, 1020, 1349,
1500, 1502, 1503,			1365, 2000, 2001,
1515, 1614, 1621,			2091, 2092, 2134,
1638, 1649, 1652,	\qed	2294	2138, 2142, 2146,
1655, 1657, 1676,	\quad	354, 2018,	2150, 2181, 2186, 2191
1677, 1679, 1680,	2021, 2026, 2030, 2127		\ renewenvironment . .
1738, 1742, 1771,			. 637, 684, 1097, 2293
1773, 1779, 1781,			\ repeat 1943, 2074
1805, 1807, 1813,	\raggedright		\ RequirePackage . . . 30,
1820, 1828, 1830,	... 1610, 1651, 1866		174, 175, 176, 178,
1844, 1846, 1852,	\raisebox		182, 384, 440, 450,
1859, 1866, 1868,	1387, 1606, 1618,		457, 537, 582, 587,
1872, 1873, 1874,	1630, 1645, 2080, 2082		599, 600, 601, 602,
1875, 1886, 1894,	\received	17, 1131	607, 1149, 1154, 1931
1906, 1908, 1909,	\RecordChanges	18	\ reset@font 557, 570
1912, 1914, 1916,	\ref	1899, 1905	\ reversemarginpar . . . 519
1918, 1920, 1922,	\refname	184, 185	\ rightskip 2155
1924, 1926, 1930, 2293	\refstepcounter	296	\rlap 2081
\paragraph	\relax	118, 123, 130,	\rule 564, 577, 2083
\parbox	152, 234, 235, 278,		
1635, 1643, 1938, 2084	297, 299, 303, 317,		S
\parindent	331, 346, 356, 364,		\ savebox 1938
. 521, 1383, 1392,	375, 393, 459, 524,		screenonly (environment) 19
2146, 2157, 2209, 2239	581, 617, 669, 744,		\ scriptsize 1940
\parskip	961, 964, 1156,		\ scshape 2210, 2278
\part	1176, 1181, 1184,		\ section 184,
\PassOptionsToClass	1188, 1194, 1197,		1476, 1478, 1482,
111, 112	1200, 1203, 1206,		1484, 1884, 2134, 2304
\pdfgentounicode	1212, 1241, 1379,		\ section@raggedright
\pdfstringdefDisableCommands	1467, 1495, 1532,	 2154, 2158,
385	1554, 1575, 1689,		2159, 2167, 2168,
\phantomsection	1713, 1778, 1787,		2170, 2171, 2173,
. 185, 1880, 2305	1788, 1790, 1793,		2174, 2176, 2177,
\popQED	1795, 1797, 1799,		2179, 2180, 2185,
\position	1801, 1829, 1832,		2198, 2199, 2202, 2203
11, 1010, 1014, 1015,	1833, 1835, 1838,		\ SelectFootnoteRule 538
1016, 1017, 1018, 1666	1840, 1911, 1936,		\ setbox 342,
\postcode	1963, 1965, 1971,		568, 664, 1604,
11, 1017, 1666	1979, 2003, 2058,		1623, 1651, 1662,
printonly (environment)	2060, 2061, 2062,		1771, 1780, 1827, 1874
\ProcessOptionsX	2065, 2066, 2067,		\ setcitestyle
113	2070, 2072, 2075,		. 21, 188, 262, 268
\proof	2076, 2077, 2078,		\ setcopyright 16, 1209
2293	2094, 2126, 2164,		\ setcounter 1374,
\proofname	2213, 2243, 2281, 2295		1436, 1490, 1963,
2293	\ removelastskip	369	1965, 2162, 2197, 2201
\protect	\ renewcommand	183,	\ setkeys
312, 325	187, 188, 191, 193,		37, 121, 942, 1119,
\protected@edef	195, 197, 199, 201,		
297, 559, 573			
\providecommand			
. 425, 429, 2207			
\ProvidesClass			
5			
\ProvidesFile			
3			

\strut	1209, 1761, 1762, 1766, 1767, 1817, 1818, 1821, 1822, 1856, 1857, 1860, 1861	\strutbox \subparagraph \subsection \subsubsection \subsubtitle \subtitlenote	564, 577 2191 2138 2142, 2181 9, 958 13, 1034	\trivlist \tw@ \two@digits \twocolumn 1507, 1509, 1511, 1513
\setlength 521, 522, 528, 1077, 1080, 1939			
\settopmatter	<u>17, 1119,</u> 1120, 1122, 1125, 1127			U
\setTrue 368	\teaserfigure teaserfigure (environment)	1347 17	\unskip 345, 386, 544, 1013, 1019, 1663, 1683, 1742, 1890
\SetWatermarkColor 452			
\SetWatermarkFontSize 451			
\SetWatermarkText 453	\terms \textbf \textbullet 2018, 2021, 2026, 2030	15, 1093 1157, 1160 387, 1157, 2018, 2021, 2026, 2030	\unvbox 548, 553, 569 \upshape 683 \url 1239, 2311 \urlstyle 391, 400, 403
\sfdefault 605	\textcolor \textheight \textit \textrightarrow \textwidth 1369, 1594, 1622, 1650, 1687, 1787, 1826	2086 1943 1161, 1897, 1901 388, 1157, 647, 665, 666, 1369, 1594, 1622, 1650, 1687, 1787, 1826	\usebox 1949, 1956 \usepackage 10, 11, 12, 13, 14, 15
\sffamily 1555, 1557, 1559, 1561, 1563, 1565, 1569, 1710, 1715, 1719, 1980, 1982, 1984, 1986, 1988, 1990, 1992, 1994, 1996, 2086, 2158, 2159, 2160, 2167, 2168, 2170, 2171, 2176, 2177, 2198, 2199, 2202, 2203	\textcolor \textheight \textit \textrightarrow \textwidth 1369, 1594, 1622, 1650, 1687, 1787, 1826	2086 1943 1161, 1897, 1901 388, 1157, 647, 665, 666, 1369, 1594, 1622, 1650, 1687, 1787, 1826	
\shortauthors 17, 982, 983, 988, 989, 991, 994, 995, 997, 1453, 1455, 1976	\thanks \thankses	1349, 1930 1352, 1354, 1381, 1930	V
\shortcite 428, 431	\the \theACM@time@hours .	1059, 1061, 1940, 1968, 2077 1965, 1969	\vbox 568, 664, 1604, 1623, 1651, 1771, 1827, 1874
\shorttitle 2007, 2013, 2021, 2030, 2035			\vskip 334, 369, 546, 580, 659 \vtop 1780
\showeprint 2325			
\sidebar 635			
sidebar (environment) 19			
\skip 546			
\small 557, 639, 642, 645, 1147, 1468, 1470, 1472, 1474, 1716, 1882, 1894, 2096	\theoremstyle 2268, 2274, 2277	W
\space 321, 1683, 2311	\thepage 2004, 2005, 2010, 2011, 2018, 2021, 2026, 2030, 2034, 2096, 2123	1970, 2004, 2005, 2010, 2011, 2018, 2021, 2026, 2030, 2034, 2096, 2123	\wd 666, 1663 \write 438
\specialcomment 2302			
\standardpagestyle 1998			
\startPage 15, 1091			
\state 11, 1016, 1666			
\stepcounter 1029, 1031, 1038, 1041, 1048			
\streetaddress 11, 1014, 1666			
\string 438, 1093, 1892, 1893			
\strut 1628, 1643			
				X
				\xdef 238, 240, 242, 244, 246, 248
				Y
				\year 1059, 1968
				Z
				\z@ 217, 280, 300, 332, 342, 357, 370, 522, 564, 577, 580, 611, 615, 626, 686, 1366, 1368, 1383, 1387, 1392, 1606, 1618, 1630, 1645, 1866, 2000, 2001, 2051, 2053, 2055, 2080, 2082, 2091, 2092, 2134, 2138, 2150, 2157, 2181, 2186, 2191, 2221, 2251
				\z@skip 369, 659, 2156