

The bangla Package

Nahid Hossain

Assistant Professor, United International University

Bangladesh

nahid@cse.uiu.ac.bd

mailbox.nahid@gmail.com

Version 1.8

June 20, 2021

Contents

1 Introduction

1.1 About bangla Package

The bangla package is a programming tool geared primarily towards LaTeX class and package authors. It provides all necessary LaTeX frontends for Bangla language.

1.2 Licence

Copyright © 2021 Nahid Hossain. Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License, version 1.3c or later.

2 Commands

2.1 Use Package

The basic command to use the package is-

`\usepackage{bangla}`

2.2 Font Selection

The default font of the `bangla` package is `Kalpurush`. If you do not mention any font name in the parameter, the `Kalpurush` will be your default font. However, an author can easily change the font using the parameter of the `usepackage` command.

```
\usepackage[<font name>]{bangla}
```

For example, if an author wants `Noto Serif Bengali` as the font for the whole article, he can write-

```
\usepackage[notoserifbengali]{bangla}
```

The following SIL Open Font Licence(OFL) Bangla fonts are currently associated with the `bangla` package-

Font Name	Command Keyword	Licence
<code>Kalpurush</code>	<code>kalpurush</code>	SIL OFL
<code>Shimanto</code>	<code>shimanto</code>	SIL OFL
<code>Noto Sans Bengali</code>	<code>notosansbengali</code>	SIL OFL
<code>Noto Serif Bengali</code>	<code>notoserifbengali</code>	SIL OFL

2.3 With Parameter Definitions

In this subsection, we have demonstrated the commands that requires parameters(at least one or more).

2.3.1 `\banglatext{<bangla text here>}`

`banglatext` displays any Bangla texts provided inside the parameter. Insert Bangla text in the parameter.

Command	Output
<code>\banglatext{আমি বাংলায় কথা বলি।}</code>	আমি বাংলায় কথা বলি।

2.3.2 `\banglabold{<bangla text here>}`

`banglabold` bolds the Bangla texts provided inside the parameter. It can make texts bold automatically of any font that has no bold fonts available.

Command	Output
<code>\banglabold{আমি বাংলায় কথা বলি।}</code>	আমি বাংলায় কথা বলি।

2.3.3 `\banglaitalic{<bangla text here>}`

`banglaitalic` makes the Bangla texts italic provided inside the parameter. It can make texts italic automatically of any font that has no italic fonts available.

Command	Output
<code>\banglaitalic{আমি বাংলায় কথা বলি।}</code>	আমি বাংলায় কথা বলি।

2.3.4 `\banglatranslit{<bangla text here>}`

`banglatranslit` generates a comprehensive and sophisticated transliteration of Bangla into Latin based on ISO 15919. `banglatranslit` works on character, word, and sentences as well.

Command	Output
<code>\banglatranslit{আমি বাংলায় কথা বলি।}</code>	āmi bānglāya kathā bali.

2.3.5 `\banglaipa{<bangla text here>}`

`banglaipa` generates equivalent International Phonetic Alphabets(IPA) symbols for Bangla alphabets. `banglaipa` works on character, word, and sentences as well.

Command	Output
<code>\banglaipa{আমি বাংলায় কথা বলি।}</code>	ami banla ^j kt ^h a bli.

2.4 Without Parameter Definitions

In this subsection, we have demonstrated the commands that require no parameter at all.

2.4.1 `\banglapage`

`banglapage` produces bangla page numbering. `banglapage` does not need any parameters. Put `banglapage` command before `\begin{document}` command. Such as:

```
\banglapage
```

2.4.2 `\banglasection`

`banglasection` produces bangla numbering for all sections in the article including all subsections. `banglasection` does not need any parameters. Put

bangalsection command before \begin{document} command. Such as:
`\bangalsection`

2.4.3 `\banglaenumerate`

banglaenumerate produces level-2 bangla numbering for enumerate or the list in latex for the whole article. banglaenumerate does not need any parameters. Put banglaenumerate command before \begin{document} command or anywhere above the enumerate. Such as:

`\banglaenumerate`

2.4.4 `\banglaequation`

banglaequation produces bangla numbering for all equations in the whole article. banglaequation does not need any parameters. Put banglaequation command before \begin{document} command or anywhere above the equations. Such as:

`\banglaequation`

2.4.5 `\banglatable`

banglatable produces bangla numbering for all tables in the whole article. banglatable does not need any parameters. Put banglatable command before \begin{document} command or anywhere above the tables. Such as:

`\banglatable`

2.4.6 `\banglafigure`

banglafigure produces bangla numbering for all figures/images in the whole article. banglafigure does not need any parameters. Put banglafigure command before \begin{document} command or anywhere above the figures. Such as:

`\banglafigure`

3 Reporting issues

To report any error or issue please send an email at nahid@cse.uiu.ac.bd or mailbox.nahid@gmail.com.

4 Revision History

Version 1.8 bug fixed.

Version 1.7 bug fixed.

Version 1.6 a new OFL SIL font added. bug fixed.

Version 1.5 solved font licence issues and fixed some bugs.
Version 1.0 primary version.