

The ifthen package*

David Carlisle

2001/05/26

Abstract

This file implements an `\ifthenelse` command for $\text{\LaTeX} 2_{\epsilon}$. The algorithm used is compatible with that used in the \LaTeX 2.09 `ifthen` style option. It has been recoded, making the resulting definitions somewhat more compact and efficient.

1 Introduction

`\ifthenelse` `\ifthenelse{<test>}{<then clause>}{<else clause>}`

Evaluates `<test>` as a boolean function, and then executes either `<then clause>` or `<else clause>`.

`<test>` is a boolean expression using the infix connectives, `\and`, `\or`, the unary `\not` and parentheses `\(\)`.

As an alternative notation `\AND`, `\OR` and `\NOT` can be used. This is safer since it can't be misinterpreted when appearing inside a \TeX -conditional in which `\or` has a different meaning.

The atomic propositions are:

`<number> < number>`
`<number> = <number>`
`<number> > <number>`
`\isodd{ <number> }`
`\isundefined{ <command name> }`
`\equal{<string>}{<string>}`
`\lengthtest{<dimen><dimen>}`
`\lengthtest{<dimen>=<dimen>}`
`\lengthtest{<dimen>><dimen>}`
`\boolean{<name>}`

The `<string>`s tested by `\equal` may be any sequence of commands that expand to a list of tokens. If these expansions are equal, then the proposition is true.

`\isodd` is true if the `<number>` is odd, and false otherwise (even if the argument is not a number).

`\isundefined{<cmd>}` is true if `<cmd>` is not defined.

`\boolean{xyz}` returns the truth value contained in the primitive \TeX `\if`, `\ifxyz`. This is usually used with boolean flags created with `\newboolean` and `\provideboolean` described below. It can also be used with the names of `\newif` created tokens, and primitive \TeX `\if` constructs, for example `\boolean{true}` (`\iftrue`), `\boolean{mmode}` (`\ifmmode`) etc.

The commands:

`\newboolean` `\newboolean{<name>}` and `\provideboolean{<name>}` are provided so the user
`\provideboolean` can easily create new boolean flags. As for `\newcommand`, `\newboolean` generates an error if the command name is not new. `\provideboolean` silently does nothing in that case.

The boolean flags may be set with:

`\setboolean` `\setboolean{<name>}{<value>}`

*This file has version number v1.1c, last revised 2001/05/26.

$\langle value \rangle$ may be either `true` or `false` (any CaSe).

Note that there is no precedence between `\and` and `\or`. The proposition is evaluated in a left right manner. `\not` only applies to the immediately following proposition. (This is consistent with Lamport’s `ifthen.sty`.) In this style, though the test is ‘lazily’ evaluated, so for instance if the first proposition in an `\or` is true, the second one is skipped. (On the second pass—the first pass in an `\edef` expands clauses in all propositions.)

Apart from the addition of the extra atomic propositions `\isodd`, `\boolean`, `\lengthtest` and `\isundefined`, the only known incompatibility is that in this package the expression `\not\not\langle P \rangle` is equivalent to $\langle P \rangle$. However in the original style it was equivalent to `\not\langle P \rangle`. This is intentional (bug fix:-).

`\whiledo` The command `\whiledo` is also defined (copied directly from the L^AT_EX 2.09 definition).

`\whiledo{⟨test⟩}{⟨while clause⟩}`

With $\langle test \rangle$ as above, repeatedly executes $\langle while\ clause \rangle$ while the test remains true.

2 The Implementation

1 `*package`

`\TE@throw` In order to support the syntax of `ifthen.sty`, which allows access to the primitive T_EX syntax for a numeric test, rather than a `{}` delimited argument form, it is most convenient to work ‘within’ an `\ifnum`. `\ift@throw` ‘throws’ you out of the current `\ifnum` so that you can (eg) start an `\ifdim` for the length tests.

2 `\def\TE@throw{\@ne=\@ne\noexpand\fi}`

`\boolean` A non-standard extension to `ifthen`, supporting boolean was previously available, this is a simpler implementation.

3 `\def\boolean#1#2{%`

4 `\TE@throw\expandafter\noexpand\csname if#1\endcsname#2}`

`\TE@length` Testing lengths. `#1` is the test. The extra argument gobbles spaces.

5 `\def\TE@length#1#2{\TE@throw\noexpand\ifdim#1#2}`

`\TE@odd` Testing odd/even. This is true if `#1` is an odd number, and false otherwise (even if `#1` is not a number at all).

It is hard to make this completely reliable. Here I have erred on the side of safety. This should not generate a T_EX error if given any robust commands as its argument. However it returns true on any argument that *starts* with an odd number 11xx which is bad, and it can not deal with T_EX’s count registers, although L^AT_EX counters work (via `\value`).

6 `\def\TE@odd#1#2{%`

7 `\TE@throw\noexpand\TE@@odd#1\noexpand\@nil\noexpand\ifodd\count@#2}`

`\TE@@odd` is not expanded on the first pass.

8 `\def\TE@@odd#1#2\@nil{%`

9 `\@defaultunits`

10 `\count@\if-#1-0\else0\expandafter#1\fi#2\relax\@nnil}`

`\TE@repl` `\TE@repl` replaces the single token `#1` by `#2`. (Not within `{}` groups.) It is used to replace `\or` by `\TE@or` without the need to redefine `\or`. Earlier versions just `\let\or\TE@or` but this has a bad effect on the expansion of commands which use the primitive `\or` internally, eg `\alph`, and so caused surprising results if these commands were used inside `\equal`.

11 `\def\TE@repl#1#2{%`

12 `\long\def\@tempc##1#1##2{%`

13 `\def\@tempa{##2}\def\@tempb{\@tempc}%`

14 `\ifx\@tempa\@tempb`

```

15     \toks@\expandafter{\the\toks@##1}%
16     \expandafter\@gobble
17   \else
18     \toks@\expandafter{\the\toks@##1#2}%
19     \expandafter\@tempc
20     \fi
21   ##2}%
22   \expandafter\toks@\expandafter{\expandafter}%
23   \expandafter\@tempc\the\toks@#1\@tempc}

```

`\ifthenelse` The remaining macros in this file are derived from the ones in `ifthen.sty` but recoded and simplified. The main simplification is that the original style (and the `\boolean` extensions) expressed logical values always in terms of `\ifnum`. As `\fi` is ‘untyped’ this is not necessary, so for example the length tests can return values via `\ifdim`, the trailing `\fi` will not complain, even though it was ‘expecting’ an `\ifnum`. Also the system of passing information via macros expanding to T or F has been completely replaced by a simpler system using `\iftrue`, which furthermore allows lazy evaluation on the second pass.

```

24 \long\def\ifthenelse#1{%

```

```

25   \toks@{#1}%
26   \TE@repl\or\TE@or
27   \TE@repl\and\TE@and
28   \TE@repl\not\TE@neg

```

Support alternate names for the boolean operators (strictly speaking only `\OR` would be necessary).

```

29   \TE@repl\OR\TE@or
30   \TE@repl\AND\TE@and
31   \TE@repl\NOT\TE@neg

```

The original `ifthen.sty` processed everything inside a box assignment, to catch any extra spaces before they appeared in the output. Instead I have added extra arguments to the commands so they each remove any following space.

Set up the user level names `\not` etc.

```

32   \begingroup
33     \let\protect\@unexpandable@protect
34     \def\@setref##1##2##3{%
35       \ifx##1\relax\z@\else\expandafter##2##1\fi}%
36     \def\value##1{\the\csname c@##1\endcsname}%
37     \let\equal\TE@equal \let\(\TE@lparen \let\)\TE@rparen
38     \let\isodd\TE@odd \let\lengthtest\TE@length
39     \let\isundefined\TE@undef

```

For the first pass, in a group, make various tokens non-expandable.

It is unfortunate that in order to remain compatible with `ifthen` syntax, it is necessary to have a two pass system. The first pass inside an `\edef` ‘exposes’ the `\if... \fi` tokens, so the correct clauses may be skipped on the second pass. This means that the whole `\ifthenelse` command does not work by expansion, and so possibly has only limited usefulness for macro code writers. The main problem with the `ifthen` syntax is that (unique for \LaTeX) it does not use a brace delimited argument form, and exposes the primitive \TeX syntax for $\langle number \rangle$. Pretty much the only way of parsing `1 > 2 \or 2 < 1` is to actually evaluate the primitive `\ifnum`s. A syntax such as:

```

\or{\numtest{1<2}}{\lengthtest{1pt<1in}}

```

could easily be evaluated in a one pass way, operating directly via expansion, and leaving no extra tokens in the token stream.

Still, on with the code... make `\@tempa` and `\@tempb` tokens non-expandable on the first pass.

```

40   \begingroup
41     \let\@tempa\relax\let\@tempb\relax
42     \xdef\@gtempa{\expandafter\TE@eval\the\toks@\TE@endeval}%

```

```

43         \endgroup
Now outside the group, execute \@gtempa which causes all the \ifs etc., to be
evaluated, the final truth value is contained in the \newif token \ifTE@val. Fi-
nally this is tested and either the first or second following argument is chosen
accordingly.
44         \@gtempa
45         \expandafter\endgroup\ifTE@val
46         \expandafter\@firstoftwo
47         \else
48         \expandafter\@secondoftwo
49         \fi}

\TE@eval  Initialise a term. (Expanded on the first pass).
50 \def\TE@eval{\noexpand\TE@negatefalse\noexpand\iftrue\noexpand\ifnum}

\ifTE@val  Two \newifs the first holds the current truth value of the expression. The second
\ifTE@negate is a temporary flag which is true if we need to negate the current proposition.
51 \newif\ifTE@val
52 \newif\ifTE@negate

\TE@endeval  Finalise a term. (Expanded on the first pass).
53 \def\TE@endeval{\relax
54     \noexpand\TE@setvaltrue\noexpand
55     \else
56     \noexpand\TE@setvalfalse\noexpand
57     \fi
58     \noexpand\TE@negatefalse\noexpand
59     \fi}

\TE@setvaltrue  Set the \ifTE@val to true or false depending on the value of the current proposi-
\TE@setvalfalse tion, and the negate flag. (Not expanded on the first pass.)
60 \def\TE@setvaltrue{%
61     \ifTE@negate\TE@valfalse\else\TE@valtrue\fi}
62 \def\TE@setvalfalse{\let\ifTE@val\ifTE@negate}

\TE@or  The internal version of \or. Ends the current term. If true skip the remaining
terms.
63 \def\TE@or{\TE@endeval\noexpand\ifTE@val\noexpand\else\noexpand\ifnum}

\TE@and  The internal version of \and. If false skip the remaining terms.
64 \def\TE@and{\TE@endeval\noexpand\ifTE@val\noexpand\ifnum}

\TE@neg  \not. Throw the current context, set a negate flag, then restart the \ifnum.
\TE@negswitch \TE@negswitch is not expanded on the first pass.
65 \def\TE@neg{\TE@throw\noexpand\TE@negswitch\noexpand\ifnum}
66 \def\TE@negswitch{\ifTE@negate\TE@negatefalse\else\TE@negatetrue\fi}

\TE@lparen  \(. Throw the current context, then restart a term inside a group.
67 \def\TE@lparen#1{\TE@throw\begin\group\TE@eval#1}

\TE@rparen  \) end the current term, and the local group started by \(. but pass on the boolean
value in \if\@val T. The \noexpand stops the \expandafter from expanding on
the first pass.
68 \def\TE@rparen#1{%
69     \TE@endeval
70     \noexpand\expandafter\end\group\noexpand\ifTE@val#1}

```

`\TE@equal` `\equal` greatly simplified from the original. `\def` may be used rather than `\edef` as the whole thing is expanded anyway in the first pass. The boolean can be directly encoded with the `\ifx`, there is no need to start an equivalent `\ifnum`.

```

71 \long\def\TE@equal#1#2#3{\TE@throw
72     \def\@tempa{#1}\def\@tempb{#2}%
73     \noexpand\ifx\@tempa\@tempb#3}

```

`\setboolean` `\setboolean` takes true or false, as #2, and sets #1 accordingly.

```

74 \def\setboolean#1#2{%
75     \lowercase{\def\@tempa{#2}}%
76     \@ifundefined{@tempa\@tempa}%
77     {\PackageError{ifthen}%
78         {You can only set a boolean to `true' or `false'}\@ehc}%
79     {\@ifundefined{#1\@tempa}%
80         {\PackageError{ifthen}{Boolean #1 undefined}\@ehc}%
81         {\csname#1\@tempa\endcsname}}}

```

`\newboolean` Define a new ‘boolean’.

```

82 \def\newboolean#1{%
83     \expandafter\ifdefinable\csname if#1\endcsname{%
84         \expandafter\newif\csname if#1\endcsname}}

```

`\provideboolean` Define a new ‘boolean’ if it is not already defined.

```

85 \def\provideboolean#1{%
86     \@ifundefined{if#1}{%
87         \expandafter\newif\csname if#1\endcsname}\relax}

```

`\whiledo` `\whiledo` copied directly from the original.
`\whiledo{<test>}{<body>}`
repeatedly evaluates `<body>` until `<test>` is true.

```

88 \long\def\whiledo#1#2{%
89     \ifthenelse{#1}%
90     {\@whiledottrue
91         \@whiles\if@whiledo\fi
92         {#2}%
93         \ifthenelse{#1}\@whiledottrue\@whiledofalse}}%
94     {}%
95 }

```

`\TE@undef` test if csname is defined. `\ifx` test.

```

96 \def\TE@undef#1#2{%
97     \TE@throw\noexpand\ifx\noexpand\@undefined\noexpand#1#2}

```

`\if@whiledo` Internal switch for `\whiledo`.

```

98 \newif\if@whiledo
99 \</package>

```