

The **bid**i Package

Support for bidirectional typesetting in plain T_EX and L^AT_EX 2_ε

Vafa Khalighi
vafaklg@gmail.com

October 6, 2011 Version 1.3.5

Contents

I	L^AT_EX Manual	2		
1	Basics	3		
1.1	Loading The Package	3		
1.2	Commands for Version number, and Date of The Package	4		
1.3	Turning TeX--XeT features on and off	4		
1.4	Options of The Package	4		
1.5	Paragraph Switching Commands	5		
1.6	Paragraph Switching Environments	6		
1.7	Typesetting Short LTR and RTL Texts	6		
1.8	Footnotes	7		
1.8.1	Footnote Rule	8		
1.9	Two Column Typesetting	8		
1.10	RTL cases	8		
1.11	Typesetting Logos	9		
1.12	Separation Mark	9		
1.13	\raggedright, \raggedleft commands, flushleft and flushright Environments	10		
1.14	Primitive-like commands	10		
1.15	Something To know about \hbox	10		
1.16	\bidillap and \bidirlap Commands	11		
1.17	LTRitems and RTLitems Environments	11		
1.18	LTRbibitems and RTLbibitems Environments	12		
1.19	\setLTRbibitems, \setRTLbibitems, and \setdefaultbibitems commands	13		
1.20	Typesetting margin par	14		
1.21	Typesetting of Headers and Footers	14		
1.22	Tabular Typesetting	14		
1.23	Equation Numbers	14		
2	Support For Various Packages and Classes	15		
2.1	Color	15		
2.2	The dblfnote package	15		
2.3	Hyperref	16		
2.4	flowfram Package	16		
2.5	Multicolumn Typesetting	16		
3	Extra bidi Packages and Classes	16		
3.1	Typesetting T _E X and L ^A T _E X Codes	16		
3.2	Typesetting Poems	16		
3.3	Typesetting Resumé	17		
3.4	Print Two Pages On A Single Page	17		
3.5	Producing Presentations	17		

3.5.1	bidipresentation Class	17	5.2	Commands for Version number, and Date of The Package	22
4	Some Useful Internal Macros and Programming Tips	19	5.3	Turning TeX--XeT features on and off	22
4.1	Equating Conditionals	19	5.4	Paragraph Switching Commands	22
4.2	RTL Conditional	19	5.5	Paragraph Switching Environments	23
4.3	Main RTL Conditional	20	5.6	Typesetting Short LTR and RTL Texts	23
4.4	Latin Conditional	20	5.7	Primitive-like commands	24
4.5	Tags Internal Macro	20	5.8	Something To know about \hbox	24
4.6	Definition File Loaded Internal Macro	20	5.9	Typesetting Logos	25
4.7	Tabular Conditional	20	6	Some Useful Internal Macros and Programming Tips	25
4.8	Footnote Conditional	20	6.1	RTL Conditional	25
4.9	Direction Ensuring Macros	21	6.2	Main RTL Conditional	25
4.10	Reset Direction Macro	21	6.3	Direction Ensuring Macros	25
II	Plain T _E X Manual	21	6.4	Reset Direction Macro	25
5	Basics	21			
5.1	Loading The Package	21			

Introduction

bid_i provides a convenient interface for typesetting bidirectional texts in plain T_EX and L^AT_EX.

The bid_i package at the moment only works with XeT_EX engine, but we will support other T_EX engines as well in the future.

bid_i Info On The Terminal and In The Log File

If you use bid_i package to write any input T_EX document, and then run `xelatex` on your document, bid_i writes some information about itself to the terminal and to the log file. The information is something like:

```

bidi package (Support for bidirectional typesetting in plain TeX and
LaTeX)
Description: A convenient interface for typesetting bidirectional texts
in plain TeX and LaTeX. The package includes adaptations for use
with many other commonly-used packages.
Copyright (c) 2009-2012 Vafa Khalighi
v1.3.5, 2012/01/01
License: LaTeX Project Public License, version 1.3c or higher (your
choice)
Location on CTAN: /macros/latex/contrib/bidi

```

Part I

L^AT_EX Manual

1 Basics

1.1 Loading The Package

You can load the package in the ordinary way;

```
\usepackage [Options] {bidi}
```

Where options of the package are explained later in [subsection 1.4](#).

When loading the package, it is important to know that:

- ❶ bidi should be the last package that you load, because otherwise you are certainly going to overwrite bidi's definitions and consequently, you will not get the expected output.
- ❷ In fact, bidi makes sure that some specific packages are loaded before bidi; these are those packages that bidi modifies them for bidirectional typesetting.

If you load bidi before any of these packages, then you will get an error saying that you should load bidi as your last package.

For instance, consider the following minimal example:

```
1 \documentclass{minimal}
2 \usepackage{bidi}
3 \usepackage{graphicx}
4 \begin{document}
5 This is just a test.
6 \end{document}
```

Where graphicx is loaded after bidi. If you run xelatex on this document, you will get an error which looks like this:

```
! Package bidi Error: Oops! you have loaded package graphicx after
bidi package. Please load package graphicx before bidi package, and
then try to run xelatex on your document again.
```

```
See the bidi package documentation for explanation.
```

```
Type H <return> for immediate help.
```

```
...
```

```
1.4 \begin{document}
```

```
?
```

1.2 Commands for Version number, and Date of The Package

`\bidiversion \bididate`

☞ `\bidiversion` gives the current version of the package.

☞ `\bididate` gives the current date of the package.

```
1 \documentclass{article}
2 \usepackage{bidi}
3 \begin{document}
4 This is typeset by \textsf{bidi} package, \bidiversion, \bididate.
5 \end{document}
```

1.3 Turning TeX--XeT features on and off

The bidirectional typesetting in XeTeX is based on TeX--XeT algorithm and `bidi` package automatically turns the feature on for typesetting bidirectional texts. As the internal data structures built by TeX--XeT differ from those built by TeX, the typesetting of a document by TeX--XeT may therefore differ from that performed by TeX. So you may notice that some packages behave differently when TeX--XeT feature is on and you may want to turn the feature off for a part of the text so that you get the default behaviour of original TeX. Two commands are provided for this purpose:

`\TeXXeTOn \TeXXeTOff`

☞ `\TeXXeTOn` turns TeX--XeT feature on, which is active by default when `bidi` package is loaded.

☞ `\TeXXeTOff` turns TeX--XeT feature off.

1.4 Options of The Package

There are three options, namely `RTLdocument` and `rldocument`, which are essentially equivalent. If you pass any of these options to the package, you will be typesetting a document containing mainly RTL texts with some LTR texts. These options activate `\setRTL` (explained in [subsection 5.4](#)), `\RTLdblcol` (explained in [subsection 1.9](#)) and `\autofootnoterule` (explained in [subsection 1.8.1](#)).

It is clear that if you do not pass any of these options to the package, you will be typesetting a document containing mainly LTR texts with some RTL texts.

There is also `extrafootnotefeatures` option that allows footnotes to be typeset in different formats:

```

\normalfootnotes
\twocolumnfootnotes \threecolumnfootnotes \fourcolumnfootnotes
\fivecolumnfootnotes \sixcolumnfootnotes \sevendcolumnfootnotes
\eightcolumnfootnotes \nincolumnfootnotes \tencolumnfootnotes
\RTLcolumnfootnotes \LTRcolumnfootnotes
\paragraphfootnotes
\setLTRparagraphfootnotes \setRTLparagraphfootnotes

```

- ☞ `\normalfootnotes` typesets footnotes in Standard L^AT_EX format.
- ☞ `\twocolumnfootnotes` to `\tencolumnfootnotes`, typeset footnotes in two-columns to ten-columns, respectively.
- ☞ `\RTLcolumnfootnotes` typesets footnotes columns RTL (first column on the RHS and each next column to the left of the previous column) and `\LTRcolumnfootnotes` typesets footnotes columns LTR (first column on the LHS and each next column to the right of the previous column). `\LTRcolumnfootnotes` is active by default.
- ☞ `\paragraphfootnotes` typesets footnotes in paragraph format.
- ☞ `\setLTRparagraphfootnotes` makes footnotes run from left to right. This comand is active by default.
- ☞ `\setRTLparagraphfootnotes` makes footnotes run from right to left.
- ☞ When using `extrafootnotefeatures`, `\textwidthfootnoterule` is active.

1.5 Paragraph Switching Commands

```

\setLTR \setLR \unsetRL \unsetRTL
\setRTL \setRL \unsetLTR

```

- ☞ With any of the commands in the first row, you can typeset LTR paragraphs.
- ☞ With any of the commands in the second row, you can typeset RTL paragraphs.

```

1 \documentclass{article}
2 \usepackage{fontspec}
3 \newfontfamily\Parsifont[Script=Arabic]{Yas}
4 \usepackage{bidi}
5 \begin{document}
6 \setRTL%
7 Anyone who reads Old and Middle English literary texts will be
8 familiar with the mid-brown volumes of the EETS, with the symbol
9 of Alfred's jewel embossed on the front cover.
10

```

```

11 \setLTR% Notice the blank line before \setLTR
12 Anyone who reads Old and Middle English literary texts will be
13 familiar with the mid-brown volumes of the EETS, with the symbol
14 of Alfred's jewel embossed on the front cover.
15 \end{document}

```

1.6 Paragraph Switching Environments

```

\begin{LTR}  <text>  \end{LTR}
\begin{RTL}  <text>  \end{RTL}

```

☞ With LTR environment, you can typeset LTR paragraphs.

☞ With RTL environment, you can typeset RTL paragraphs.

```

1 \documentclass{article}
2 \usepackage{bidi}
3 \begin{document}
4 \begin{RTL}
5 Anyone who reads Old and Middle English literary texts will be familiar
6 with the mid-brown volumes of the EETS, with the symbol
7 of Alfred's jewel embossed on the front cover.
8 \begin{LTR}
9 Anyone who reads Old and Middle English literary texts will be familiar
10 with the mid-brown volumes of the EETS, with the symbol
11 of Alfred's jewel embossed on the front cover.
12 \end{LTR}
13 And we are still typesetting RTL.
14 \end{RTL}
15 \end{document}

```

1.7 Typesetting Short LTR and RTL Texts

```

\LRE{<text>}  \LR{<text>}
\RLE{<text>}  \RL{<text>}

```

☞ With any of the commands in the first row, you can typeset short LTR text inside RTL paragraphs.

☞ With any of the commands in the second row, you can typeset short RTL text inside LTR paragraphs.

```

1 \begin{document}
2 \begin{RTL}
3 Anyone who reads Old and Middle English \LRE{Short LTR text} literary
  texts will be familiar

```

```

4 with the mid-brown volumes of the EETS, with the symbol
5 of Alfred's jewel embossed on the front cover.
6 \begin{LTR}
7 Anyone who reads Old and Middle English \RLE{Short RTL text} literary
8 texts will be familiar
9 with the mid-brown volumes of the EETS, with the symbol
10 of Alfred's jewel embossed on the front cover.
11 \end{LTR}
12 \end{RTL}
13 \end{document}

```

1.8 Footnotes

```

\footnote [num] {<text>} \LTRfootnote [num] {<text>} \RTLfootnote [num] {<text>}
\setfootnoteRL \setfootnoteLR \unsetfootnoteRL
\thanks{<text>} \LTRthanks{<text>} \RTLthanks{<text>}

```

- ☞ `\footnote` in RTL mode produces an RTL footnote while in LTR mode it produces an LTR footnote.
- ☞ `\LTRfootnote` will always produce an LTR footnote, independent on the current mode.
- ☞ `\RTLfootnote` will always produce an RTL footnote, independent on the current mode.
- ☞ Specifying a `\setfootnoteRL` command anywhere will make `\footnote` produce an RTL footnote.
- ☞ Specifying either a `\setfootnoteLR` or an `\unsetfootnoteRL` command anywhere will make `\footnote` produce an LTR footnote.
- ☞ `\thanks` (to be used only inside `\author` or `\title` argument) in RTL mode produces an RTL footnote while in LTR mode it produces an LTR footnote.
- ☞ `\LTRthanks` (to be used only inside `\author` or `\title` argument) will always produce an LTR footnote, independent on the current mode.
- ☞ `\RTLthanks` (to be used only inside `\author` or `\title` argument) will always produce an RTL footnote, independent on the current mode.

```

\footnotetext [num] {<text>} \LTRfootnotetext [num] {<text>}
\RTLfootnotetext [num] {<text>}

```

- ☞ `\footnotetext` used in conjunction with `\footnotemark`, in RTL mode produces an RTL footnote while in LTR mode it produces an LTR footnote.

☞ `\LTRfootnotetext` used in conjunction with `\footnotemark`, will always produce an LTR footnote, independent on the current mode.

☞ `\RTLfootnotetext` used in conjunction with `\footnotemark`, will always produce an RTL footnote, independent on the current mode.

1.8.1 Footnote Rule

The behavior of footnote rules can also be controlled.

```
\autofootnoterule \rightfootnoterule \leftfootnoterule
\LRfootnoterule \textwidthfootnoterule
```

☞ `\autofootnoterule` will draw the footnote rule right or left aligned based on the direction of the first footnote following the rule (i.e., put in the current page).

☞ `\rightfootnoterule` will put footnote rule on the right-hand side.

☞ `\leftfootnoterule` or `\LRfootnoterule` will put footnote rule on the left-hand side.

☞ `\textwidthfootnoterule` will draw the footnote rule with a width equal to `\textwidth`.

1.9 Two Column Typesetting

```
\RTLdblcol \LTRdblcol
```

If you pass the `twocolumn` option to the class file and if the main direction of the document is RTL, then you get RTL two column and if the main direction of the document is LTR, then you get LTR two column. In addition, `\RTLdblcol` allows you to have RTL two column typesetting and `\LTRdblcol` allows you to have LTR two column typesetting as the options of the class file.

1.10 RTL cases

```
\RTLcases{\text{⟨brach1⟩}\cr\text{⟨brach2⟩}\cr\text{⟨brach3⟩}...\cr}
\text{⟨main⟩}
```

`\RTLcases` is defined in `bidi` for typesetting RTL cases. `\text` is defined in `amsmath` package, so this means that you need to load `amsmath` package too.

```
1 \documentclass{article}
2 \usepackage{amsmath}
3 \usepackage{bidi}
4 \begin{document}
5 \setRTL
```

`\RTLcases` command was previously known as `\rcases` command but since there was a clash with `mathtools` package (`mathtools` defines `rcases` environment), we had to rename `\rcases` command to `\RTLcases` command.


```

6 \[\RTLcases{\text{men}\cr\text{women}}
7 \text{Humans Beings}
8 \]
9 \end{document}

```

1.11 Typesetting Logos

```
\XeTeX \XeLaTeX
```

bidi defines XeTeX and XeLaTeX logos and in addition, it makes sure that logos, TeX, LaTeX, LaTeX 2_ε are typeset LTR.

1.12 Separation Mark

```
\SepMark{<mark>} \@SepMark
```

Generally in Standard LaTeX, dot is used for separation between section numbers, equation numbers any anything else which needs to be separated. You can use \SepMark to use any other mark as the separation mark instead a dot.

```

1 \documentclass{article}
2 \usepackage{bidi}
3 \SepMark{-}
4 \begin{document}
5 \section{First}
6 \subsection{Second}
7 \subsubsection{Third}
8 \end{document}

```

If you decide to change the numbering of chapters, sections, subsections, equations, figures and ..., you should either load amsmath package and use \numberwithin macro to do this or do the ordinary way, but instead dot write \@SepMark. Using dot instead \SepMark will certainly make trouble.

```

1 \documentclass{article}
2 \usepackage{bidi}
3 \SepMark{-}
4 \makeatletter
5 \renewcommand\theequation{\thesection\@SepMark\@arabic\c@equation}
6 \makeatother
7 \begin{document}
8 \section{First}
9 \begin{equation}
10 x^2+y^2=z^2
11 \end{equation}
12 \end{document}

```

1.13 `\raggedright`, `\raggedleft` commands, `flushleft` and `flushright` Environments

`\raggedright` command and `flushleft` environment put the text on the left hand side and `\raggedleft` command and `flushright` environment put the text on the right hand side, independent on the current mode.

1.14 Primitive-like commands

<code>\hboxR</code> <code>\hboxL</code> <code>\vboxR</code> <code>\vboxL</code>

- ☞ The syntax of `\hboxR` is exactly the same as the syntax of `\hbox`, but its contents is always typeset RTL.
- ☞ The syntax of `\hboxL` is exactly the same as the syntax of `\hbox`, but its contents is always typeset LTR.
- ☞ The syntax of `\vboxR` is exactly the same as the syntax of `\vbox`, but its contents is always typeset RTL.
- ☞ The syntax of `\vboxL` is exactly the same as the syntax of `\vbox`, but its contents is always typeset LTR.

1.15 Something To know about `\hbox`

If you enable RTL typesetting and typeset an horizontal box at the beginning of the document:

<pre>1 \documentclass{article} 2 \usepackage{bidi} 3 \setRTL 4 \begin{document} 5 \hbox{This is a Test} 6 \end{document}</pre>
--

You see that even you have used `\setRTL`, the horizontal box appears LTR (It appears on the left hand side and its content is typeset left to right). This is because when \TeX starts, it is in the vertical mode so if you need to have that `\hbox` appear RTL, then write `\leavevmode` before `\hbox`:

<pre>1 \documentclass{article} 2 \usepackage{bidi} 3 \setRTL 4 \begin{document} 5 \leavevmode\hbox{This is a Test} 6 \end{document}</pre>

1.16 `\bidillap` and `\bidirlap` Commands

In RTL mode, `\llap` and `\rlap` do opposite things. Since these two macros are used in a lot of classes and packages, instead modifying these two macros, we have created two new macros `\bidillap` and `\bidirlap` which give logical results.

1.17 `LTRitems` and `RTLitems` Environments

If you typeset an `itemize`, or an `enumerate`, or a `description` environment where all `\items` are one directional, you have no problem at all as shown below:

```
1 \documentclass{article}
2 \begin{document}
3 Anyone who reads Old and Middle English literary texts will be familiar
  with the mid-brown volumes of the EETS, with the symbol of Alfred's
4 \begin{enumerate}
5 \item Anyone who reads Old and Middle English literary texts will be
  familiar with the mid-brown volumes of the EETS, with the symbol of
  Alfred's
6 \item Anyone who reads Old and Middle English literary texts will be
  familiar with the mid-brown volumes of the EETS, with the symbol of
  Alfred's
7 \end{enumerate}
8 \end{document}
```

However if the above example becomes bidirectional, as shown below:

```
1 \documentclass{article}
2 \usepackage{bidi}
3 \begin{document}
4 Anyone who reads Old and Middle English literary texts will be familiar
  with the mid-brown volumes of the EETS, with the symbol of Alfred's
5 \begin{enumerate}
6 \item Anyone who reads Old and Middle English literary texts will be
  familiar with the mid-brown volumes of the EETS, with the symbol of
  Alfred's
7 \setRTL
8 \item Anyone who reads Old and Middle English literary texts will be
  familiar with the mid-brown volumes of the EETS, with the symbol of
  Alfred's
9 \end{enumerate}
10 \end{document}
```

Then some people may argue that this typographically does not look promising. For this purpose, `RTLitems` environment is provided which has the following syntax:

```

\begin{RTLitems} [length]
  \item <text>
  ...
\end{RTLitems}

```

Where `[length]` is optional and if you do not give it, the value of `\rightskip` will be equal to the value of `\labelwidth+\labelsep` by default and if you give this optional length, then the value of `\rightskip` will be equal to the value of `\labelwidth+given length`. Thus by using the `RTLitems` environment, the previous example will look like the following:

```

1 \documentclass{article}
2 \usepackage{bidi}
3 \begin{document}
4   Anyone who reads Old and Middle English literary texts will be familiar
   with the mid-brown volumes of the EETS, with the symbol of Alfred's
5   \begin{enumerate}
6   \item Anyone who reads Old and Middle English literary texts will be
       familiar with the mid-brown volumes of the EETS, with the symbol of
       Alfred's
7   \begin{RTLitems}
8   \item Anyone who reads Old and Middle English literary texts will be
       familiar with the mid-brown volumes of the EETS, with the symbol of
       Alfred's
9   \end{RTLitems}
10  \end{enumerate}
11 \end{document}

```

Similarly, `LTRitems` environment is defined which has the following syntax:

```

\begin{LTRitems} [length]
  \item <text>
  ...
\end{LTRitems}

```

Where `[length]` is optional and if you do not give it, the value of `\leftskip` will be equal to the value of `\labelwidth+\labelsep` by default and if you give this optional length, then the value of `\leftskip` will be equal to the value of `\labelwidth+given length`.

1.18 LTRbibitems and RTLbibitems Environments

The syntax of `LTRbibitems` and `RTLbibitems` environments is exactly like the syntax of `LTRitems` and `RTLitems` environments but there are few differences:

- ☞ `LTRitems` and `RTLitems` environments should only be used for list-like environments (such as `itemize`, `enumerate` and `description` environments) but

LTRbibitems and RTLbibitems environments should only be used for thebibliography environment.

- ☞ Clearly instead of `\item`, you have `\bibitem` inside LTRbibitems and RTLbibitems environments.
- ☞ For LTRbibitems environment, if natbib package with `authoryear`¹ option is loaded and if you do not specify the optional `[length]`, then the value of `\leftskip` will be equal to the value of `2\labelsep` by default and if you give this optional length, then the value of `\leftskip` will be equal to the value of `\labelsep+given length`.
- ☞ For RTLbibitems environment, if natbib package with `authoryear` option is loaded and if you do not specify the optional `[length]`, then the value of `\rightskip` will be equal to the value of `2\labelsep` by default and if you give this optional length, then the value of `\rightskip` will be equal to the value of `\labelsep+given length`.

1.19 `\setLTRbibitems`, `\setRTLbibitems`, and `\setdefaultbibitems` commands

`\setLTRbibitems` `\setRTLbibitems` `\setdefaultbibitems`

- ☞ If your whole thebibliography environment is inside RTL mode, but all your `\bibitems` are LTR and you actually want to have `\bibname` to appear on the RHS, you can use `\setLTRbibitems` command before thebibliography environment.
- ☞ If your whole thebibliography environment is inside LTR mode, but all your `\bibitems` are RTL and you actually want to have `\bibname` to appear on the LHS, you can use `\setRTLbibitems` command before thebibliography environment.
- ☞ `\setdefaultbibitems` is the default, when your `\bibitems` are a mixture of LTR and RTL and it does not matter what mode (LTR or RTL) your thebibliography environment is in. Please note that you do not have to use `\setdefaultbibitems` command in this case at all.

Consider an example that your thebibliography environment is inside LTR mode and you have, say two `\bibitems`. The first `\bibitem` is LTR and the second `\bibitem` is RTL. One could typeset this senario as shown below:

```

1 \documentclass{article}
2 \usepackage{bidi}
3 \begin{document}
4 \begin{thebibliography}{99}
5 \bibitem This is the first bibitem which is LTR.
```

¹`authoryear` option is the default when natbib package is loaded.

```

6 \begin{RTLbibitems}
7 \bibitem This is the second bibitem which is RTL.
8 \end{RTLbibitems}
9 \end{thebibliography}
10 \end{document}

```

1.20 Typesetting margin par

By default, in RTL mode, `\marginpar` appears on LHS and its content is typeset RTL and in LTR mode, `\marginpar` appears on RHS and its content is typeset LTR. In addition, the following commands are provided:

```

\setRTLmarginpar \setLTRmarginpar \setdefaultmarginpar
\LTRmarginpar[⟨left-text⟩]{⟨right-text⟩}
\RTLmarginpar[⟨left-text⟩]{⟨right-text⟩}

```

- ☞ `\setRTLmarginpar` always makes `\marginpar` to appear on LHS and the content of `\marginpar` is typeset RTL (this is independent of the current mode).
- ☞ `\setLTRmarginpar` always makes `\marginpar` to appear on RHS and the content of `\marginpar` is typeset LTR (this is independent of the current mode).
- ☞ `\setdefaultmarginpar` gives the default behaviour of `\marginpar` as described above.
- ☞ `\LTRmarginpar` typesets `⟨left-text⟩` and `⟨right-text⟩` always LTR.
- ☞ `\RTLmarginpar` typesets `⟨left-text⟩` and `⟨right-text⟩` always RTL.
- ☞ in RTL mode, places of `⟨left-text⟩` and `⟨right-text⟩` swaps.

1.21 Typesetting of Headers and Footers

If the main direction of the document is RTL, then headers and footers are typeset RTL and if the main direction of the document is LTR, then headers and footers are typeset LTR.

1.22 Tabular Typesetting

In RTL mode, tabular are typeset RTL and in LTR mode, tabular are typeset LTR.

1.23 Equation Numbers

For `reqno`, equation numbers are on the right hand side and for `leqno`, equation numbers are on the left hand side, independent on the current mode.

2 Support For Various Packages and Classes

The `bidi` package supports `amsmath`, `amsthm`, `array`, `arydshln`, `breqn`, `caption`, `color`, `colortbl`, `dblfnote`, `draftwatermark`, `empheq`, `fancyhdr`, `float`, `flowfram`, `framed`, `graphicx`, `hvfloa`, `hyperref`, `lettrine`, `listings`, `minitoc`, `multicol`, `multienum`, `pdfpages`, `pstricks`, `quotchap`, `ragged2e`, `sidecap`, `stabular`, `subfig`, `subfigure`, `supertabular`, `xtab`, `tbls`, `tabulary`, `PGF & TIKZ`, `tocbibind`, `tocloft`, `tocstyle`, `wrapfig`, `xcolor`, `xltxtra` packages, `amsart`, `amsbook`, `artikel1`, `artikel2`, `artikel3`, `extarticle`, `flashcards`, `standrad` article, `boek`, `boek3`, `standard book`, `bookest`, `extbook`, `extletter`, `scrlettr`, `standard letter`, `memoir`, `extreport`, `rapport1`, `rapport3`, `refrep`, `standard report`, `scartcl`, `scrbook`, `screprt` classes and any other packages and classes that relies on these packages and classes. This means, you can use all these packages and classes in addition to other packages and classes that rely on these packages and classes and use their functionality fully for your bidirectional documents.

We now give some details that you should know about the supported packages or classes.

2.1 Color

You can use `color` and `xcolor` packages to typeset texts in colours and colour boxes produced by `\colorbox` and `\fcolorbox` commands. Please note that your Coloured text should not span more than a line, if your text spans more than a line, you will be in trouble which means your whole document, page or paragraph may be coloured. If your texts spans more than a line, then you should use `xecolour` package.

Also if you are going to use `\color` command to colour the text at the beginning of a paragraph, then you should have `\leavevmode` before `\color` command.

For having coloured tabular, you can use `colortbl` package.

2.2 The `dblfnote` package

The `dblfnote` package makes footnotes double-columned. In addition `bidi` package adds bidirectional support for the `dblfnote` package by providing the following commands:

<code>\RTLdfnmakecol</code> <code>\LTRdfnmakecol</code>

☞ `\RTLdfnmakecol` makes footnotes double-columned RTL.

☞ `\LTRdfnmakecol` makes footnotes double-columned LTR.

☞ If the main direction of the document is RTL, `\RTLdfnmakecol` is active and if the main direction of the document is LTR, `\LTRdfnmakecol` is active.

2.3 Hyperref

The `hyperref` package works fine with bidirectional documents if and only if, your link will not span more than a line. If your link spans more than a line, then your whole document, or page or paragraph may be linked.

2.4 flowfram Package

You can use `flowfram` package for your bidirectional documents. Please note that `flowfram` package provides support for bidirectional column typesetting, for details, see its manual.

2.5 Multicolumn Typesetting

In the previous versions of `bidi` package, it was recommended that you need to use `fmultico` package instead the original `multicol` package for RTL multicolumn typesetting. This is not the case any more and you should not use buggy `fmultico` package any more. Simply load the original `multicol` package before loading `bidi`. `bidi` now supports `multicol` package and you can typeset bidirectional multi columns.

In addition, you also can use `vwcol` package for variable width bidirectional column typesetting.

3 Extra bidi Packages and Classes

3.1 Typesetting \TeX and \LaTeX Codes

The \LaTeX codes in this manual are typeset using the `bidicode` package. In standard \LaTeX you can not use footnotes inside `\chapter`, `\part`, `\section`, `\subsection`, `\subsubsection` and any other section-like commands, `\caption` and tabular environment.

`bidi` package provides `bidiftnxtra` package that solves the issue of footnote in standard \LaTeX . `bidiftnxtra` package should be loaded after `bidi` package.

3.2 Typesetting Poems

The `bidi` package provides `bidipoem` package for typesetting Persian poems. It provides four environments, `traditionalpoem`, `modernpoem` and starred version of these. In the starred version of these environments you do not need to type `\` and that is the only difference with the normal version of the environments. The `traditionalpoem` environment and its starred version are also useful for typesetting Classic Arabic poetry, in fact this package may also be useful for other RTL languages.

When using `bidipoem` package, at least you need to run `xelatex` twice on your document. In fact, if you run `xelatex` just once on your document, you get a message saying “Unjustified poem. Rerun `XeLaTeX` to get poem right”.

When you typeset your poems, you might get underfull `\hbox` messages. This is absolutely normal and if you want to get rid of these underfull `\hbox` messages, then you would need to use Kashida.

If you need to change the default distance between two verses, you can do just that by:

```
\renewcommand\poemcolsepskip{<length>}
```

```
\begin{traditionalpoem}
<verse1>&<verse2>\\
<verse3>&<verse4>\\
...
\end{traditionalpoem}
```

```
\begin{traditionalpoem*}
<verse1>&<verse2>
<verse3>&<verse4>
...
\end{traditionalpoem*}
```

3.3 Typesetting Resumé

The `bidi` package provides `bidimoderncv`² class for typesetting resumé. There are two examples, namely `test-casualcv.tex` and `test-classiccv.tex`, in the `doc` folder than you can look and learn how you can use it.

3.4 Print Two Pages On A Single Page

`bidi` package provides `bidi2in1` package for printing two pages on a single (landscape) A4 page. Page numbers appear on the included pages, and not on the landscape 'container' page.

3.5 Producing Presentations

At the moment, there is only one class that you can prepare your presentations with.

3.5.1 `bidipresentation` Class

`bidipresentation` is a simple class for presentations to be shown on screen or beamer. It is derived from L^AT_EX's `article` class. The virtual paper size of documents produced by this class: width=128mm, height=96mm. `bidipresentation` requires that the `fancyhdr` and `geometry` packages are available on the system. Enhancements to the `bidipresentation` class are easily made available by other packages, these include slides with a background from a bitmap (`eso-pic` package).

²This class is the modified version of `moderncv` class.

Usage: The class is used with

`\documentclass [Options] {bidipresentation}`

Options of the article class are also available to `bidipresentation`, e. g. 10pt, 11pt, 12pt for selection of font size. However, not all options of the article class will be appropriate for a presentation class, e. g. `twocolumn`.

A simple example document:

```
1 \documentclass[12pt]{bidipresentation}
2 \usepackage{eso-pic}
3 \usepackage[RTLdocument]{bidi}
4 \pagestyle{pres}
5 \AddToShipoutPicture{
6 \includegraphics{gradient2.png}
7 }
8 \begin{document}
9 \begin{titlepage}
10 \centering
11 \distance{1}
12 {
13 \Huge \bfseries Title of the presentation \par
14 }
15 \vspace{1.3ex} \large
16 Author\|[2ex]Institution
17 \distance{2}
18 \end{titlepage}
19 \begin{plainslide}[Title of Page]
20 The first page
21 \end{plainslide}
22 \begin{rawslide}
23 The second page
24 \end{rawslide}
25 \end{document}
```

The title page can be created within the `titlepage` environment, the `\maketitle` command is not available. Slides may be created with the `plainslide` environment, you may add the title of the slide with the optional parameter. The contents of the slide are centered vertically. Another environment generating a slide is `rawslide`: slides are written without title, contents are not vertically centered.

The `\distance{<number>}` command allows to introduce vertical space into slides constructed with the `rawslide` and `titlepage` environments. You should use pairs of `\distance{}` commands with numbers indicating the relative height of empty space, see the titlepage in the example above.

Pictures can be included with the `\includegraphics` command of the `graphicx` package. Please be aware that the dimensions of the pages are 128mm × 96mm and therefore included graphics are scaled appropriately.

Enhancements to `bidipresentation`:

Fill background of a presentation with bitmaps: `eso-pic` package allows you to paint the background with a picture:

```
1 \usepackage{eso-pic}
2 ...
3 \AddToShipoutPicture{
4 \includegraphics{gradient2.png}
5 }
```

`\AddToShipoutPicture{}` puts the picture on every page, `\AddToShipoutPicture*{}` puts it on to the current page, `\ClearShipoutPicture` clears the background beginning with the current page. Details of `eso-pics` commands can be found in its own documentation.

4 Some Useful Internal Macros and Programming Tips

There are some useful internal macros and programming tips that might be helpful for you. This section, explains all these useful internals and programming tips.

4.1 Equating Conditionals

```
\eqnewif{<\newconditional1>}{<\newconditional2>}
```

In standard \LaTeX , `\newif` command is provided that you can define a new conditional with it. `\eqnewif` command is similar to `\newif` command but:

- ☞ With `\eqnewif` command, you can define two new conditionals instead one, so clearly it has two mandatory arguments.
- ☞ `\newconditional1` will be identical to `\newconditional2`, so that whenever `\newconditional1` is true, then `\newconditional2` is also true and whenever `\newconditional1` is false, then `\newconditional2` is also false and vice versa.

4.2 RTL Conditional

```
\if@RTL
```

`\if@RTL` conditional is true inside RTL mode and it is false in LTR mode.

4.3 Main RTL Conditional

`\if@RTLmain`

If the main direction of the document is RTL, `\if@RTLmain` is true and if the main direction of the document is LTR, `\if@RTLmain` is false.

4.4 Latin Conditional

`\if@Latin`

`\if@Latin` inside any environment that uses Latin font is true and inside any environment that uses RTL font is false.

4.5 Tags Internal Macro

```
\@iftagsloaded{<tags name>}{<do thing(s) if the tag is loaded>}
{<do thing(s) if the tag is not loaded>}
```

As you can see, the syntax of `\@iftagsloaded` is exactly the same as the syntax of `\@ifpackageloaded` and `\@ifclassloaded`. By tags, we mean things like `leqno` or `reqno`. Please note that in the argument `<tags name>`, the extension `clo` should not be given.

4.6 Definition File Loaded Internal Macro

```
\@ifdefinitionfileloaded{<definition file name>}
{<do thing(s) if the definition file is loaded>}
{<do thing(s) if the definition file is not loaded>}
```

As you can see, the syntax of `\@ifdefinitionfileloaded` is exactly the same as the syntax of `\@ifpackageloaded` and `\@ifclassloaded`. By definition file, we mean things like `hyperref-bidi.def` or `wrapfig-bidi.def`. Please note that in the argument `<definition file name>`, the extension `def` should not be given.

4.7 Tabular Conditional

`\if@RTLtab`

If the tabular is typeset RTL, `\if@RTLtab` is true and if the tabular is typeset LTR, `\if@RTLtab` is false.

4.8 Footnote Conditional

`\if@RTL@footnote`

When footnotes are typeset RTL, `\if@RTL@footnote` is true and when footnotes are typeset LTR, `\if@RTL@footnote` is false.

4.9 Direction Ensuring Macros

<code>\@ensure@RTL{<text>}</code> <code>\@ensure@RL{<text>}</code> <code>\@ensure@LTR{<text>}</code> <code>\@ensure@LR{<text>}</code> <code>\@ensure@dir{<text>}</code> <code>\@ensure@maindir{<text>}</code>
--

- ☞ `\@ensure@RTL` and `\@ensure@RL` internals make sure that `<text>` is always typeset RTL, independent on the current mode.
- ☞ `\@ensure@LTR` and `\@ensure@LR` internals make sure that `<text>` is always typeset LTR, independent on the current mode.
- ☞ `\@ensure@dir` and `\@ensure@maindir` if used in RTL mode, they put `<text>` inside `\RLE` and if used in LTR mode, they put the text as it is.

4.10 Reset Direction Macro

<code>\save@dir</code> <code>\saved@@dir</code> <code>\reset@dir</code>

- ☞ `\save@dir`, if the direction of typesetting is RTL, defines `\saved@@dir` to be RTL and if the direction of typesetting is LTR, defines `\saved@@dir` to be LTR.
- ☞ `\reset@dir`, if `\saved@@dir` is defined as RTL, inserts `\setRTL` otherwise, if `\saved@@dir` is defined as LTR, inserts `\setLTR`, otherwise does nothing.

Part II

Plain T_EX Manual

5 Basics

5.1 Loading The Package

You can load the package in the ordinary way;

<code>\input bidi</code>

When loading the package, it is important to know that: `bidi` should be the last package that you load, because otherwise you are certainly going to overwrite `bidi`'s definitions and consequently, you will not get the expected output.

5.2 Commands for Version number, and Date of The Package

```
\bidiversion \bididate
```

☞ `\bidiversion` gives the current version of the package.

☞ `\bididate` gives the current date of the package.

```
1 \input bidi
2 This is typeset by \textsf{bidi} package, \bidiversion, \bididate.
3 \end
```

5.3 Turning TeX--XeT features on and off

The bidirectional typesetting in XeTeX is based on TeX--XeT algorithm and `bidi` package automatically turns the feature on for typesetting bidirectional texts. As the internal data structures built by TeX--XeT differ from those built by TeX, the typesetting of a document by TeX--XeT may therefore differ from that performed by TeX. So you may notice that some packages behave differently when TeX--XeT feature is on and you may want to turn the feature off for a part of the text so that you get the default behaviour of original TeX. Two commands are provided for this purpose:

```
\TeXXeTOn \TeXXeTOff
```

☞ `\TeXXeTOn` turns TeX--XeT feature on, which is active by default when `bidi` package is loaded.

☞ `\TeXXeTOff` turns TeX--XeT feature off.

5.4 Paragraph Switching Commands

```
\setLTR \setLR \unsetRL \unsetRTL
\setRTL \setRL \unsetLTR
```

☞ With any of the commands in the first row, you can typeset LTR paragraphs.

☞ With any of the commands in the second row, you can typeset RTL paragraphs.

```
1 \input bidi
2 \setRTL%
3 Anyone who reads Old and Middle English literary texts will be
4 familiar with the mid-brown volumes of the EETS, with the symbol
5 of Alfred's jewel embossed on the front cover.
```

```

6
7 \setLTR% Notice the blank line before \setLTR
8 Anyone who reads Old and Middle English literary texts will be
9 familiar with the mid-brown volumes of the EETS, with the symbol
10 of Alfred's jewel embossed on the front cover.
11 \end

```

5.5 Paragraph Switching Environments

```

\LTR <text> \endLTR
\RTL <text> \endRTL

```

☞ With LTR environment, you can typeset LTR paragraphs.

☞ With RTL environment, you can typeset RTL paragraphs.

```

1 \input bidi
2 \RTL
3 Anyone who reads Old and Middle English literary texts will be familiar
4 with the mid-brown volumes of the EETS, with the symbol
5 of Alfred's jewel embossed on the front cover.
6 \LTR
7 Anyone who reads Old and Middle English literary texts will be familiar
8 with the mid-brown volumes of the EETS, with the symbol
9 of Alfred's jewel embossed on the front cover.
10 \endLTR
11 And we are still typesetting right to left.
12 \endRTL
13 \end

```

5.6 Typesetting Short LTR and RTL Texts

```

\LRE{<text>} \LR{<text>}
\RLE{<text>} \RL{<text>}

```

☞ With any of the commands in the first row, you can typeset short LTR text inside RTL paragraphs.

☞ With any of the commands in the second row, you can typeset short RTL text inside LTR paragraphs.

```

1 \input bidi
2 \RTL
3 Anyone who reads Old and Middle English \LRE{Short left to right text}
4 literary texts will be familiar
5 with the mid-brown volumes of the EETS, with the symbol

```

```

5 | of Alfred's jewel embossed on the front cover.
6 | \LTR
7 | Anyone who reads Old and Middle English \RLE{Short right to left text}
   | literary texts will be familiar
8 | with the mid-brown volumes of the EETS, with the symbol
9 | of Alfred's jewel embossed on the front cover.
10 | \endLTR
11 | \endRTL
12 | \end

```

5.7 Primitive-like commands

```
\hboxR \hboxL \vboxR \vboxL
```

- ☞ The syntax of `\hboxR` is exactly the same as the syntax of `\hbox`, but its contents is always typeset RTL.
- ☞ The syntax of `\hboxL` is exactly the same as the syntax of `\hbox`, but its contents is always typeset LTR.
- ☞ The syntax of `\vboxR` is exactly the same as the syntax of `\vbox`, but its contents is always typeset RTL.
- ☞ The syntax of `\vboxL` is exactly the same as the syntax of `\vbox`, but its contents is always typeset LTR.

5.8 Something To know about `\hbox`

If you enable RTL typesetting and typeset an horizontal box at the beginning of the document:

```

1 | \input bidi
2 | \setRTL
3 | \hbox{This is a Test}
4 | \end

```

You see that even you have used `\setRTL`, the horizontal box appears LTR (It appears on the left hand side and its content is typeset left to right). This is because when \TeX starts, it is in the vertical mode so if you need to have that `\hbox` appear RTL, then write `\leavevmode` before `\hbox`:

```

1 | \input bidi
2 | \setRTL
3 | \leavevmode\hbox{This is a Test}
4 | \end

```


5.9 Typesetting Logos

`\XeTeX`

bidi defines XeTeX logo and in addition, it makes sure that the logo, TeX is typeset LTR.

6 Some Useful Internal Macros and Programming Tips

There are some useful internal macros and programming tips that might be helpful for you. This section, explains all these useful internals and programming tips.

6.1 RTL Conditional

`\if@RTL`

`\if@RTL` conditional is true inside RTL mode and it is false in LTR mode.

6.2 Main RTL Conditional

`\if@RTLmain`

If the main direction of the document is RTL, `\if@RTLmain` is true and if the main direction of the document is LTR, `\if@RTLmain` is false.

6.3 Direction Ensuring Macros

`\@ensure@RTL{<text>}` `\@ensure@RL{<text>}` `\@ensure@LTR{<text>}`
`\@ensure@LR{<text>}` `\@ensure@dir{<text>}` `\@ensure@maindir{<text>}`

- ☞ `\@ensure@RTL` and `\@ensure@RL` internals make sure that `<text>` is always typeset RTL, independent on the current mode.
- ☞ `\@ensure@LTR` and `\@ensure@LR` internals make sure that `<text>` is always typeset LTR, independent on the current mode.
- ☞ `\@ensure@dir` and `\@ensure@maindir` if used in RTL mode, they put `<text>` inside `\RLE` and if used in LTR mode, they put the text as it is.

6.4 Reset Direction Macro

`\save@dir` `\saved@@dir` `\reset@dir`

- ☞ `\save@dir`, if the direction of typesetting is RTL, defines `\saved@@dir` to be RTL and if the direction of typesetting is LTR, defines `\saved@@dir` to be LTR.

☞ `\reset@dir`, if `\saved@@dir` is defined as `RTL`, inserts `\setRTL` otherwise,
if `\saved@@dir` is defined as `LTR`, inserts `\setLTR`, otherwise does nothing.