

bohr

vo.2b 2012/09/26

simple atom representation according to the Bohr model

Clemens NIEDERBERGER

<https://bitbucket.org/cgnieder/bohr/>
contact@mychemistry.eu

English documentation

This package provides means for the creation of simple Bohr models of atoms up to the atomic number 112. Additionally commands are provided to convert atomic numbers to element symbols or element names and vice versa.

The package is inspired by a question on <http://tex.stackexchange.com/>: Draw Bohr atomic model with electron shells in TeX?

Contents		
1 Licence and Requirements	4 Customization	2
2 Options	1 5 Additional Commands	4
3 Usage	1 6 Implementation	5
	2 Index	15

1 Licence and Requirements

BOHR is placed under the terms of the LaTeX Project Public License, version 1.3 or later (<http://www.latex-project.org/lppl.txt>). It has the status “maintained.”

BOHR loads and needs the packages tikz,¹ pgfopts² and etoolbox.³

2 Options

Every option described in the manual can also be used as package option. Options are indicated as **option** and are all key/value like options. Some options can be set without value, too. Then

¹ CTAN: [tikz](#) ² CTAN: [pgfopts](#) ³ CTAN: [etoolbox](#)

the underlined value is used.

3 Usage

BOHR is used like any other L^AT_EX 2_E package:


```
1 \usepackage{bohr}
```

The main command, `\bohr`, creates the models:

► `\bohr[<num of shells>]{<number of electrons>}{<atom name>}`


This is described best by an example:

```
1 \bohr{3}{Li}
```



There is not much more to it. Another example using the optional argument:

```
1 \bohr[2]{2}{$\mathrm{Li}^+$}
```



4 Customization

BOHR provides a handful of options to customize the appearance:

- `\setbohr{<options>}`
Options are set in a key/value syntax using this command.
- `insert-symbol = true|false` Default: `false`
If set to true **BOHR** will insert the atomic symbol suiting to the given electron number if *no* third argument is given.
- `insert-number = true|false` Default: `false`
If set to true **BOHR** will use the appropriate number of electrons for the given element symbol in the third argument if *no* second argument is given. This of course only works if the third argument is one of the 112 element symbols.


- ▶ `insert-missing` = `true|false` Default: `false`
Sets both `insert-symbol` and `insert-number`.
- ▶ `atom-style` = `<code>` (initially empty)
This code will be placed immediately before the third argument of `\bohr`. The last macro in it may need one argument.
- ▶ `name-options-set` = `<tikz>` (initially empty)
This value is passed to the options of the `\node` the third argument of `\bohr` is placed in.
- ▶ `name-options-add` = `<tikz>` (initially empty)
This value will be added to options set with `name-options-set`.
- ▶ `nucleus-option-set` = `<tikz>` Default: `draw=black!80,fill=black!10,opacity=.25`
This value is passed to the options of the `\draw` command that draws the circle around the name-node.
- ▶ `nucleus-options-add` = `<tikz>` (initially empty)
This value will be added to options set with `nucleus-option-set`.
- ▶ `nucleus-radius` = `<dim>` Default: `1em`
The radius of the circle around the name-node.
- ▶ `electron-options-set` = `<tikz>` Default: `blue!50!black!50`
This value is passed to the options of the `\fill` command that draws the electrons.
- ▶ `electron-options-add` = `<tikz>` (initially empty)
This value will be added to options set with `electron-options-set`.
- ▶ `electron-radius` = `<dim>` Default: `1.5pt`
The radius of the circles that represent the electrons.
- ▶ `shell-options-set` = `<tikz>` Default: `draw=blue!75,thin`
This value is passed to the options of the `\draw` command that draws the circles that represent the shells.
- ▶ `shell-options-add` = `<tikz>` (initially empty)
This value will be added to options set with `shell-options-set`.
- ▶ `shell-dist` = `<dim>` Default: `1em`
The distance between the nucleus and the first shell and between subsequent shells.
- ▶ `german` = `true|false` Default: `false`
If set to true the German names are defined (see section 5 to understand what I mean). They are also defined if you use `babel`⁴ and select language german or ngerman in the preamble. The same holds for polyglossia.⁵

⁴ CTAN: `babel` ⁵ CTAN: `polyglossia`

```

1 \setbohr{name-options-set={font=\footnotesize\sffamily}}
2 \bohr{2}{He} \bohr{7}{N}


```



```

1 % uses package 'chemmacros'
2 \setbohr{atom-style={\footnotesize\sffamily\ch}}
3 \bohr{0}{H+} \bohr{10}{F-}


```



```

1 \setbohr{
2   shell-options-add = dashed,
3   shell-dist         = .5em,
4   insert-missing
5 }
6 \bohr{6}{} \bohr{}{K}

```



5 Additional Commands

BOHR provides some additional commands that return the element symbol or the element name to a given atomic number and vice versa.

► **\elementsymbol{<atomic number>}|<element name>}**

Returns the element symbol for a given atomic number or element name. **\elementsymbol{80}**: Hg; **\elementsymbol{rhenium}**: Rh.

► **\elementname{<atomic number>}|<element symbol>}**

Returns the element name for a given atomic number or element symbol. **\elementname{80}**: Mercury; **\elementname{Rh}**: Rhenium.

► **\atomicnumber{<element name>}|<element symbol>}**

Returns the atomic number for a given element name or element symbol. **\atomicnumber{Hg}**: 80; **\atomicnumber{rhenium}** 75.

► **\Z**

If this command isn't defined by some other package it is available as an alias of **\atomicnumber**.

```
1 The elements \elementname{F}, \elementname{Cl}, \elementname{Br},  
2 \elementname{I} and \elementname{At} are called \emph{halogens}.
```

The elements Fluorine, Chlorine, Bromine, Iodine and Astatine are called *halogens*.

6 Implementation

```
1 % -----  
2 % the BOHR package  
3 %  
4 % simple atom representation according to the Bohr model  
5 %  
6 % -----  
7 % Clemens Niederberger  
8 % Web: https://bitbucket.org/cgnieder/bohr/  
9 % E-Mail: contact@mychemistry.eu  
10 % -----  
11 % Copyright 2012 Clemens Niederberger  
12 %  
13 % This work may be distributed and/or modified under the  
14 % conditions of the LaTeX Project Public License, either version 1.3  
15 % of this license or (at your option) any later version.  
16 % The latest version of this license is in  
17 % http://www.latex-project.org/lppl.txt  
18 % and version 1.3 or later is part of all distributions of LaTeX  
19 % version 2005/12/01 or later.  
20 %  
21 % This work has the LPPL maintenance status ‘maintained’.  
22 %  
23 % The Current Maintainer of this work is Clemens Niederberger.  
24 % -----  
25 % The bohr package consists of the files  
26 % - bohr.sty  
27 % - bohr_en.tex, bohr_en.pdf  
28 % - bohr_elements_english.def, bohr_elements_german.def  
29 % - README  
30 % -----  
31 % If you have any ideas, questions, suggestions or bugs to report, please  
32 % feel free to contact me.  
33 % -----  
34 \def\@bohr@date{2012/09/26}  
35 \def\@bohr@version{v0.2b}  
36 \def\@bohr@description{simple atom representation according to the Bohr model}  
37  
38 \ProvidesPackage{bohr}[\@bohr@date\space \@bohr@version\space \@bohr@description]  
39 \RequirePackage{tikz,etoolbox,pgfplots}  
40
```

```

41 % -----
42 % message handling
43 \def\@bohr@create@message#1{%
44   \ifstreq{\#1}{Error}
45   {%
46     \lowercase{\csdef{@bohr@#1}##1##2{%
47       \csuse{Package#1}{bohr}{##1}{##2}}}
48   }{%
49     \lowercase{\csdef{@bohr@#1}##1{%
50       \csuse{Package#1}{bohr}{##1}}}
51   }%
52   \@bohr@create@message{Error}
53   \@bohr@create@message{Warning}
54   \@bohr@create@message{WarningNoLine}
55   \@bohr@create@message{Info}
56
57 % -----
58 % the \bohr command
59 % optional #1: number of shells
60 % #2: number of electrons
61 % #3: atom name
62 \newrobustcmd*\bohr[3][]{\@bohr{\#1}{\#2}{\#3}}
63
64 \def\@bohr#1#2#3{%
65   \ifblank{\#2}{%
66     electron number given ?
67     {%
68       \ifboolexpr{ bool {\bohr@insert@number} and test {\ifblank{\#3}} }{%
69         \@bohr@error{I can't insert the electron number.}%
70         {I can't insert the electron number. You haven't specified the
71          element.}%
72       }{%
73         \ifboolexpr{%
74           bool {\bohr@insert@number} and not
75           test {\lowercase{\ifcvoid{@bohr@atom@number@#3}}}%
76         }{%
77           \lowercase{%
78             \def\@bohr@electron@current@number{\csuse{@bohr@atom@number@#3}}%
79           }{%
80             \@bohr@error{You must specify an electron number, possibly 0.}%
81             {You must specify an electron number, possibly 0.}%
82           }%
83         }%
84       }%
85     }%
86   }{%
87     \ifnum{\#2}<0\relax
88       \@bohr@error{The electron number cannot be negative!}%
89       {The electron number cannot be negative!}%

```

```

90      \else
91          \def\@bohr@electron@current@number{#2}%
92      \fi
93  }%
94 \ifblank{#1}
95     {@bohr@get@shell@num{@bohr@electron@current@number}}%
96  {
97     {@bohr@get@shell@num{@bohr@electron@current@number}}%
98  \ifnum#1<{@bohr@shell@num
99      @bohr@warning{The shell number you provided (#1) is too small for the
100         electron number you provided (@bohr@electron@current@number)! I'll
101         use @bohr@shell@num\space shells.}%
102 \else
103     \ifnum#1>7\relax
104         @bohr@warning{I know only of 7 electron shells. You gave me #1 so I'll
105             be using 7 instead.}%
106         \def\@bohr@shell@num{7}%
107     \else
108         \def\@bohr@shell@num{#1}%
109     \fi
110 \fi
111 }%
112 \tikzpicture[baseline=(nucleus.base)]
113 \expandafter\node\expandafter[@bohr@name@options]
114     (nucleus) at (0,0) {@bohr@insert@symbol{@bohr@electron@current@number}{#3}}%
115 ;
116 \expandafter\draw\expandafter[@bohr@nucleus@options]
117     (nucleus) circle (@bohr@nucleus@radius) ;
118 \foreach\@bohr@current@shell@num in {1,...,@bohr@shell@num}
119  {
120     \expandafter\draw\expandafter[@bohr@shell@options]
121         (nucleus) circle (@bohr@nucleus@radius+@bohr@current@shell@num*\@bohr@shell@dist) ;
122     \def\@bohr@draw@electrons{@bohr@electron@current@number}%
123 \endtikzpicture
124 }
125
126 \def\@bohr@get@shell@num#1{%
127     \ifnum#1<3\relax
128         \def\@bohr@shell@num{1}%
129     \else
130         \ifnum#1<11\relax
131             \def\@bohr@shell@num{2}%
132         \else
133             \ifnum#1<19\relax
134                 \def\@bohr@shell@num{3}%
135             \else
136                 \ifnum#1<37\relax

```

```

137     \def\@bohr@shell@num{4}%
138 \else
139     \ifnum#1<55\relax
140         \def\@bohr@shell@num{5}%
141     \else
142         \ifnum#1<87\relax
143             \def\@bohr@shell@num{6}%
144         \else
145             \ifnum#1<110\relax
146                 \def\@bohr@shell@num{7}%
147             \else
148                 \def\@bohr@shell@num{112}%
149                 \bohr@warning{I only know atoms up to 112 (Copernicium). You
150                     gave me #1 so I am using 112 instead.}
151             \fi
152         \fi
153     \fi
154 \fi
155 \fi
156 \fi
157 \fi
158 }

159 \def\@bohr@distribute@electrons#1#2#3#4{%
160     \pgfmathparse{#2}%
161     \let\@bohr@last@electron\pgfmathresult
162     \foreach\@bohr@electron@number in {#1,...,\@bohr@last@electron}
163     {
164         \expandafter\fill\expandafter[\@bohr@electron@options] (nucleus)
165             ++(#3*\@bohr@electron@number-#3:\@bohr@nucleus@radius+#4*\@bohr@shell@dist)
166             circle (\@bohr@electron@radius) ;
167     }
168 }

169 }

170 \def\@bohr@draw@electrons#1{%
171     \ifnum#1<1\relax\else
172     \ifnum#1<3\relax
173         \bohr@distribute@electrons{1}{#1}{180}{1}%
174     \else
175         \ifnum#1<11\relax
176             \bohr@distribute@electrons{1}{2}{180}{1}%
177             \bohr@distribute@electrons{1}{#1-2}{45}{2}%
178         \else
179             \ifnum#1<19\relax
180                 \bohr@distribute@electrons{1}{2}{180}{1}%
181                 \bohr@distribute@electrons{1}{8}{45}{2}%
182                 \bohr@distribute@electrons{1}{#1-10}{45}{3}%
183             \else
184                 \ifnum#1<37\relax

```

```

186     \@bohr@distribute@electrons{1}{2}{180}{1}%
187     \@bohr@distribute@electrons{1}{8}{45}{2}%
188     \@bohr@distribute@electrons{1}{8}{45}{3}%
189     \@bohr@distribute@electrons{1}{#1-18}{20}{4}%
190 \else
191     \ifnum#1<55\relax
192         \@bohr@distribute@electrons{1}{2}{180}{1}%
193         \@bohr@distribute@electrons{1}{8}{45}{2}%
194         \@bohr@distribute@electrons{1}{8}{45}{3}%
195         \@bohr@distribute@electrons{1}{18}{20}{4}%
196         \@bohr@distribute@electrons{1}{#1-36}{20}{5}%
197 \else
198     \ifnum#1<87\relax
199         \@bohr@distribute@electrons{1}{2}{180}{1}%
200         \@bohr@distribute@electrons{1}{8}{45}{2}%
201         \@bohr@distribute@electrons{1}{8}{45}{3}%
202         \@bohr@distribute@electrons{1}{18}{20}{4}%
203         \@bohr@distribute@electrons{1}{18}{20}{5}%
204         \@bohr@distribute@electrons{1}{#1-54}{11.25}{6}%
205 \else
206     \ifnum#1<113\relax
207         \@bohr@distribute@electrons{1}{2}{180}{1}%
208         \@bohr@distribute@electrons{1}{8}{45}{2}%
209         \@bohr@distribute@electrons{1}{8}{45}{3}%
210         \@bohr@distribute@electrons{1}{18}{20}{4}%
211         \@bohr@distribute@electrons{1}{18}{20}{5}%
212         \@bohr@distribute@electrons{1}{32}{11.25}{6}%
213         \@bohr@distribute@electrons{1}{#1-86}{11.25}{7}%
214     \fi
215     \fi
216     \fi
217     \fi
218     \fi
219     \fi
220     \fi
221     \fi
222 }
223
224 % -----
225 % atomic numbers and element symbols and names
226 \def\@bohr@define@atom@symbol#1#2{%
227     \csdef{@bohr@atom@symbol@num@\romannumeral#1}{#2}%
228     \lowercase{\csdef{@bohr@atom@number@#2}}{#1}%
229 \def\@bohr@define@atom@name#1#2#3{%
230     \csdef{@bohr@atom@name@\romannumeral#1}{#2}%
231     \lowercase{\csdef{@bohr@atom@name@num@#3}}{#1}%
232
233 % #1: optional name (umlauts...)
234 % #2: atomic number

```

```

235 % #3: element name
236 \newrobustcmd*\DeclareAtomName[3][]{%
237   \ifblank{#1}%
238     {\@bohr@define@atom@name{#2}{#3}{#3}}%
239     {\@bohr@define@atom@name{#2}{#3}{#1}}}%
240 % #1: atomic number
241 % #2: element symbol
242 \newrobustcmd*\DeclareAtomSymbol[2]{%
243   \@bohr@define@atom@symbol{#1}{#2}}%
244
245 \def\@bohr@get@atom@symbol#1{%
246   \csuse{@bohr@atom@symbol@num@\romannumeral#1}}%
247 \def\@bohr@get@atom@number#1{%
248   \lowercase{\csuse{@bohr@atom@number@#1}}}%
249 \def\@bohr@get@atom@name#1{%
250   \csuse{@bohr@atom@name@\romannumeral#1}}%
251
252 \def\@bohr@element@symbol#1{%
253   \lowercase{\ifcsdef{@bohr@atom@name@num@#1}}%
254   {\lowercase{\@bohr@get@atom@symbol{\csuse{@bohr@atom@name@num@#1}}}}%
255   {\@bohr@get@atom@symbol{#1}}}}%
256
257 \def\@bohr@atomic@number#1{%
258   \lowercase{\ifcsdef{@bohr@atom@number@#1}}%
259   {\@bohr@get@atom@number{#1}}%
260   {\lowercase{\csuse{@bohr@atom@name@num@#1}}}}%
261
262 \def\@bohr@ellemt@symbol#1{%
263   \if!\ifnum9<1#1!\@bohr@get@atom@name{#1}\fi%
264   \else%
265     \lowercase{\@bohr@get@atom@name{\csuse{@bohr@atom@number@#1}}}}%
266   \fi}%
267
268 \newrobustcmd*\elementsymbol[1]{\@bohr@element@symbol{#1}}%
269 \newrobustcmd*\atomicnumber[1]{\@bohr@atomic@number{#1}}%
270 \newrobustcmd*\elementname[1]{\@bohr@ellemt@symbol{#1}}%
271 \ifdef\Z{}{\let\Z\atomicnumber}%
272
273 \DeclareAtomSymbol{1}{H}
274 \DeclareAtomSymbol{2}{He}
275 \DeclareAtomSymbol{3}{Li}
276 \DeclareAtomSymbol{4}{Be}
277 \DeclareAtomSymbol{5}{B}
278 \DeclareAtomSymbol{6}{C}
279 \DeclareAtomSymbol{7}{N}
280 \DeclareAtomSymbol{8}{O}
281 \DeclareAtomSymbol{9}{F}
282 \DeclareAtomSymbol{10}{Ne}
283 \DeclareAtomSymbol{11}{Na}

```

```
284 \DeclareAtomSymbol{12}{Mg}
285 \DeclareAtomSymbol{13}{Al}
286 \DeclareAtomSymbol{14}{Si}
287 \DeclareAtomSymbol{15}{P}
288 \DeclareAtomSymbol{16}{S}
289 \DeclareAtomSymbol{17}{Cl}
290 \DeclareAtomSymbol{18}{Ar}
291 \DeclareAtomSymbol{19}{K}
292 \DeclareAtomSymbol{20}{Ca}
293 \DeclareAtomSymbol{21}{Sc}
294 \DeclareAtomSymbol{22}{Ti}
295 \DeclareAtomSymbol{23}{V}
296 \DeclareAtomSymbol{24}{Cr}
297 \DeclareAtomSymbol{25}{Mn}
298 \DeclareAtomSymbol{26}{Fe}
299 \DeclareAtomSymbol{27}{Co}
300 \DeclareAtomSymbol{28}{Ni}
301 \DeclareAtomSymbol{29}{Cu}
302 \DeclareAtomSymbol{30}{Zn}
303 \DeclareAtomSymbol{31}{Ga}
304 \DeclareAtomSymbol{32}{Ge}
305 \DeclareAtomSymbol{33}{As}
306 \DeclareAtomSymbol{34}{Se}
307 \DeclareAtomSymbol{35}{Br}
308 \DeclareAtomSymbol{36}{Kr}
309 \DeclareAtomSymbol{37}{Rb}
310 \DeclareAtomSymbol{38}{Sr}
311 \DeclareAtomSymbol{39}{Y}
312 \DeclareAtomSymbol{40}{Zr}
313 \DeclareAtomSymbol{41}{Nb}
314 \DeclareAtomSymbol{42}{Mo}
315 \DeclareAtomSymbol{43}{Tc}
316 \DeclareAtomSymbol{44}{Ru}
317 \DeclareAtomSymbol{45}{Rh}
318 \DeclareAtomSymbol{46}{Pd}
319 \DeclareAtomSymbol{47}{Ag}
320 \DeclareAtomSymbol{48}{Cd}
321 \DeclareAtomSymbol{49}{In}
322 \DeclareAtomSymbol{50}{Sn}
323 \DeclareAtomSymbol{51}{Sb}
324 \DeclareAtomSymbol{52}{Te}
325 \DeclareAtomSymbol{53}{I}
326 \DeclareAtomSymbol{54}{Xe}
327 \DeclareAtomSymbol{55}{Cs}
328 \DeclareAtomSymbol{56}{Ba}
329 \DeclareAtomSymbol{57}{La}
330 \DeclareAtomSymbol{58}{Ce}
331 \DeclareAtomSymbol{59}{Pr}
332 \DeclareAtomSymbol{60}{Nd}
```

```
333 \DeclareAtomSymbol{61}{Pm}
334 \DeclareAtomSymbol{62}{Sm}
335 \DeclareAtomSymbol{63}{Eu}
336 \DeclareAtomSymbol{64}{Gd}
337 \DeclareAtomSymbol{65}{Tb}
338 \DeclareAtomSymbol{66}{Dy}
339 \DeclareAtomSymbol{67}{Ho}
340 \DeclareAtomSymbol{68}{Er}
341 \DeclareAtomSymbol{69}{Tm}
342 \DeclareAtomSymbol{70}{Yb}
343 \DeclareAtomSymbol{71}{Lu}
344 \DeclareAtomSymbol{72}{Hf}
345 \DeclareAtomSymbol{73}{Ta}
346 \DeclareAtomSymbol{74}{W}
347 \DeclareAtomSymbol{75}{Rh}
348 \DeclareAtomSymbol{76}{Os}
349 \DeclareAtomSymbol{77}{Ir}
350 \DeclareAtomSymbol{78}{Pt}
351 \DeclareAtomSymbol{79}{Au}
352 \DeclareAtomSymbol{80}{Hg}
353 \DeclareAtomSymbol{81}{Tl}
354 \DeclareAtomSymbol{82}{Pb}
355 \DeclareAtomSymbol{83}{Bi}
356 \DeclareAtomSymbol{84}{Po}
357 \DeclareAtomSymbol{85}{At}
358 \DeclareAtomSymbol{86}{Rn}
359 \DeclareAtomSymbol{87}{Fr}
360 \DeclareAtomSymbol{88}{Ra}
361 \DeclareAtomSymbol{89}{Ac}
362 \DeclareAtomSymbol{90}{Th}
363 \DeclareAtomSymbol{91}{Pa}
364 \DeclareAtomSymbol{92}{U}
365 \DeclareAtomSymbol{93}{Np}
366 \DeclareAtomSymbol{94}{Pu}
367 \DeclareAtomSymbol{95}{Am}
368 \DeclareAtomSymbol{96}{Cm}
369 \DeclareAtomSymbol{97}{Bk}
370 \DeclareAtomSymbol{98}{Cf}
371 \DeclareAtomSymbol{99}{Es}
372 \DeclareAtomSymbol{100}{Fm}
373 \DeclareAtomSymbol{101}{Md}
374 \DeclareAtomSymbol{102}{No}
375 \DeclareAtomSymbol{103}{Lr}
376 \DeclareAtomSymbol{104}{Rf}
377 \DeclareAtomSymbol{105}{Db}
378 \DeclareAtomSymbol{106}{Sg}
379 \DeclareAtomSymbol{107}{Bh}
380 \DeclareAtomSymbol{108}{Hs}
381 \DeclareAtomSymbol{109}{Mt}
```

```

382 \DeclareAtomSymbol{110}{Ds}
383 \DeclareAtomSymbol{111}{Rg}
384 \DeclareAtomSymbol{112}{Cn}
385
386 % element names are defined in bohr_elements_english.def or
387 % bohr_elements_german.def, respectively. Now we need to decide
388 % which ones we want
389 \AfterEndPreamble{
390 \ifdef\bbbl@afterfi{}{\long\def\bbbl@afterfi#1{\fi#1}}
391 \ifboolexpr
392 {
393   test {\iflanguage{german}} or
394   test {\iflanguage{n german}}
395 }
396 {\booltrue{bohr@german}{}}
397 \ifbool{bohr@german}
398   {\input{bohr_elements_german.def}}
399   {\input{bohr_elements_english.def}}
400 }

401
402
403 % -----
404 % options
405 \def\@bohr@name@options{}
406 \def\@bohr@write@atom#1{#1}
407 \def\@bohr@nucleus@radius{1em}
408 \def\@bohr@electron@options{blue!50!black!50}
409 \def\@bohr@electron@radius{1.5pt}
410 \def\@bohr@shell@dist{1em}
411 \def\@bohr@nucleus@options{draw=black!80,fill=black!10,opacity=.25}
412 \def\@bohr@shell@options{draw=blue!75,thin}

413 \newbool{bohr@insert@symbol}
414 \newbool{bohr@insert@number}
415 \newbool{bohr@german}

416
417 \def\@bohr@insert@symbol#1#2{%
418   \ifbool{bohr@insert@symbol}
419     {\ifblank{#2}{\@bohr@get@atom@symbol{#1}}{\@bohr@write@atom{#2}}}
420     {\@bohr@write@atom{#2}}}

421
422 \pgfkeys{
423   bohr/.cd,
424     insert-symbol/.is if      = bohr@insert@symbol ,
425     insert-number/.is if     = bohr@insert@number ,
426     insert-missing/.is choice,
427     insert-missing/true/.code =
428       \booltrue{bohr@insert@symbol}\booltrue{bohr@insert@number} ,
429     insert-missing/false/.code =

```

```

431   \boolearn{bohr@insert@symbol}\boolearn{bohr@insert@number} ,
432   insert-missing/.default    = true ,
433   atom-style/.code          = \def\@bohr@write@atom{\#1} ,
434   name-options-set/.code    = \def\@bohr@name@options{\#1} ,
435   name-options-add/.code    =
436   \expandafter\def\expandafter\@bohr@name@options\expandafter{\
437   @bohr@name@options,\#1} ,
438   nucleus-radius/.code      = \def\@bohr@nucleus@radius{\#1} ,
439   nucleus-options-set/.code = \def\@bohr@nucleus@options{\#1} ,
440   nucleus-options-add/.code =
441   \expandafter\def\expandafter\@bohr@nucleus@options\expandafter{\
442   @bohr@nucleus@options,\#1} ,
443   electron-radius/.code     = \def\@bohr@electron@radius{\#1} ,
444   electron-options-set/.code = \def\@bohr@electron@options{\#1} ,
445   electron-options-add/.code =
446   \expandafter\def\expandafter\@bohr@electron@options\expandafter{\
447   @bohr@electron@options,\#1} ,
448   shell-dist/.code          = \def\@bohr@shell@dist{\#1} ,
449   german/.is if              = bohr@german ,
450   ngerman/.is if             = bohr@german
451 }
452 \newrobustcmd\setbohr[1]{\pgfqkeys{/bohr}{#1}}
453
454
455 \ProcessPgfOptions*
456 \endinput
457
458 % HISTORY
459 2012/09/21 v0.1a - first version on bitbucket
460 2012/09/22 v0.2 - added compatibility up to atomic number 112
461           - added the commands \elementname and \elementsymbol with
462             language support German and English
463           - improved error checking

```

Index

A

`atom-style` 3
`\atomicnumber` 4

B

`babel` 3
`\bohr` 2 f.

C

Customization 2 ff.

E

`electron-options-add` 3
`electron-options-set` 3
`electron-radius` 3
`\elementname` 4
`\elementsymbol` 4
`etoolbox` 1

G

`german` 3

I

`insert-missing` 3
`insert-number` 2 f.
`insert-symbol` 2 f.

L

License 1

N

`name-options-add` 3
`name-options-set` 3
`nucleus-option-set` 3
`nucleus-options-add` 3
`nucleus-options-set` 3
`nucleus-radius` 3

O

`option` 1
Options 1 f.

P

`pgfplots` 1
`polyglossia` 3

S

`\setbohr` 2
`shell-dist` 3
`shell-options-add` 3
`shell-options-set` 3

T

`tikz` 1

U

Usage 2

Z

`\Z` 4