

bohr

VO.2C 2012/12/30

simple atom representation according to the Bohr model

Clemens NIEDERBERGER

<https://bitbucket.org/cgnieder/bohr/>
contact@mychemistry.eu

English documentation

This package provides means for the creation of simple Bohr models of atoms up to the atomic number 112. Additionally commands are provided to convert atomic numbers to element symbols or element names and vice versa.

The package is inspired by a question on <http://tex.stackexchange.com/>: Draw Bohr atomic model with electron shells in TeX?

Contents		
1 Licence and Requirements	4 Customization	2
2 Options	1 5 Additional Commands	4
3 Usage	1 6 Implementation	5
	2 Index	15

1 Licence and Requirements

BOHR is placed under the terms of the L^AT_EX Project Public License, version 1.3 or later (<http://www.latex-project.org/lppl.txt>). It has the status “maintained.”

BOHR loads and needs the packages tikz,¹ pgfopts² and etoolbox.³

2 Options

Every option described in the manual can also be used as package option. Options are indicated as **option** and are all key/value like options. Some options can be set without value, too. Then

¹ CTAN: [tikz](#) ² CTAN: [pgfopts](#) ³ CTAN: [etoolbox](#)

the underlined value is used.

3 Usage

BOHR is used like any other L^AT_EX 2_E package:


```
\usepackage{bohr}
```

The main command, \bohr, creates the models:

► \bohr[<num of shells>]{<number of electrons>}{<atom name>}


This is described best by an example:

```
\bohr{3}{Li}
```



There is not much more to it. Another example using the optional argument:

```
\bohr[2]{2}{$\mathrm{Li}^+$}
```



4 Customization

BOHR provides a handful of options to customize the appearance:

► \setbohr{<options>}

Options are set in a key/value syntax using this command.

► **insert-symbol** = true|false

Default: false

If set to true **BOHR** will insert the atomic symbol suiting to the given electron number if *no* third argument is given.

► **insert-number** = true|false

Default: false

If set to true **BOHR** will use the appropriate number of electrons for the given element symbol in the third argument if *no* second argument is given. This of course only works if the third argument is one of the 112 element symbols.


- ▶ `insert-missing` = `true|false` Default: `false`
Sets both `insert-symbol` and `insert-number`.
- ▶ `atom-style` = `<code>` (initially empty)
This code will be placed immediately before the third argument of `\bohr`. The last macro in it may need one argument.
- ▶ `name-options-set` = `<tikz>` (initially empty)
This value is passed to the options of the `\node` the third argument of `\bohr` is placed in.
- ▶ `name-options-add` = `<tikz>` (initially empty)
This value will be added to options set with `name-options-set`.
- ▶ `nucleus-options-set` = `<tikz>` Default: `draw=black!80,fill=black!10,opacity=.25`
This value is passed to the options of the `\draw` command that draws the circle around the name-node.
- ▶ `nucleus-options-add` = `<tikz>` (initially empty)
This value will be added to options set with `nucleus-options-set`.
- ▶ `nucleus-radius` = `<dim>` Default: `1em`
The radius of the circle around the name-node.
- ▶ `electron-options-set` = `<tikz>` Default: `blue!50!black!50`
This value is passed to the options of the `\fill` command that draws the electrons.
- ▶ `electron-options-add` = `<tikz>` (initially empty)
This value will be added to options set with `electron-options-set`.
- ▶ `electron-radius` = `<dim>` Default: `1.5pt`
The radius of the circles that represent the electrons.
- ▶ `shell-options-set` = `<tikz>` Default: `draw=blue!75,thin`
This value is passed to the options of the `\draw` command that draws the circles that represent the shells.
- ▶ `shell-options-add` = `<tikz>` (initially empty)
This value will be added to options set with `shell-options-set`.
- ▶ `shell-dist` = `<dim>` Default: `1em`
The distance between the nucleus and the first shell and between subsequent shells.
- ▶ `german` = `true|false` Default: `false`
If set to true the German names are defined (see section 5 to understand what I mean). They are also defined if you use babel⁴ and select language german or ngerman in the preamble. The same holds for polyglossia.⁵

⁴ CTAN: babel ⁵ CTAN: polyglossia

```

1 \setbohr{name-options-set={font=\footnotesize\sffamily}}
2 \bohr{2}{He} \bohr{7}{N}


```



```

1 % uses package 'chemmacros'
2 \setbohr{atom-style={\footnotesize\sffamily\ch}}
3 \bohr{0}{H+} \bohr{10}{F-}


```



```

1 \setbohr{
2   shell-options-add = dashed,
3   shell-dist         = .5em,
4   insert-missing
5 }
6 \bohr{6}{} \bohr{}{K}

```



5 Additional Commands

BOHR provides some additional commands that return the element symbol or the element name to a given atomic number and vice versa.

- ▶ **\elementsymbol**{<atomic number>|<element name>}

Returns the element symbol for a given atomic number or element name. **\elementsymbol{80}**: Hg; **\elementsymbol{rhenium}**: Rh.

- ▶ **\elementname**{<atomic number>|<element symbol>}

Returns the element name for a given atomic number or element symbol. **\elementname{80}**: Mercury; **\elementname{Rh}**: Rhenium.

- ▶ **\atomicnumber**{<element name>|<element symbol>}

Returns the atomic number for a given element name or element symbol. **\atomicnumber{Hg}**: 80; **\atomicnumber{rhenium}** 75.

- ▶ **\Z**

If this command isn't defined by some other package it is available as an alias of **\atomicnumber**.

1 The elements \elementname{F}, \elementname{Cl}, \elementname{Br},
2 \elementname{I} and \elementname{At} are called \emph{halogens}.

The elements Fluorine, Chlorine, Bromine, Iodine and Astatine are called *halogens*.

6 Implementation

```
1 % -----  
2 % the BOHR package  
3 %  
4 % simple atom representation according to the Bohr model  
5 %  
6 % -----  
7 % Clemens Niederberger  
8 % Web: https://bitbucket.org/cgnieder/bohr/  
9 % E-Mail: contact@mychemistry.eu  
10 % -----  
11 % Copyright 2012 Clemens Niederberger  
12 %  
13 % This work may be distributed and/or modified under the  
14 % conditions of the LaTeX Project Public License, either version 1.3  
15 % of this license or (at your option) any later version.  
16 % The latest version of this license is in  
17 % http://www.latex-project.org/lppl.txt  
18 % and version 1.3 or later is part of all distributions of LaTeX  
19 % version 2005/12/01 or later.  
20 %  
21 % This work has the LPPL maintenance status ‘maintained’.  
22 %  
23 % The Current Maintainer of this work is Clemens Niederberger.  
24 % -----  
25 % The bohr package consists of the files  
26 % - bohr.sty  
27 % - bohr_en.tex, bohr_en.pdf  
28 % - bohr_elements_english.def, bohr_elements_german.def  
29 % - README  
30 % -----  
31 % If you have any ideas, questions, suggestions or bugs to report, please  
32 % feel free to contact me.  
33 % -----  
34 \def\@bohr@date{2012/12/30}  
35 \def\@bohr@version{v0.2c}  
36 \def\@bohr@description{simple atom representation according to the Bohr model}  
37  
38 \ProvidesPackage{bohr}[\@bohr@date\space \@bohr@version\space \@bohr@description]  
39 \RequirePackage{tikz,etoolbox,pgfplots}  
40
```

```

41 % -----
42 % message handling
43 \def\@bohr@create@message#1{%
44   \ifstreq{\#1}{Error}
45   {%
46     \lowercase{\csdef{@bohr@#1}##1##2}{%
47       \csuse{Package#1}{bohr}{##1}{##2}}%
48   }{%
49     \lowercase{\csdef{@bohr@#1}##1}{%
50       \csuse{Package#1}{bohr}{##1}}%
51   }%
52   \@bohr@create@message{Error}
53   \@bohr@create@message{Warning}
54   \@bohr@create@message{WarningNoLine}
55   \@bohr@create@message{Info}
56
57 % -----
58 % the \bohr command
59 % optional #1: number of shells
60 % #2: number of electrons
61 % #3: atom name
62 \newrobustcmd*\bohr[3][]{\@bohr{\#1}{\#2}{\#3}}
63
64 \def\@bohr#1#2#3{%
65   \ifblank{\#2}{%
66     electron number given ?
67     {%
68       \ifboolexpr{ bool {\bohr@insert@number} and test {\ifblank{\#3}} }{%
69         \@bohr@error{I can't insert the electron number.}%
70         {I can't insert the electron number. You haven't specified the
71          element.}%
72       }{%
73         \ifboolexpr{%
74           bool {\bohr@insert@number} and not
75           test {\lowercase{\ifcvoid{@bohr@atom@number@#3}}}%
76         }{%
77           \lowercase{%
78             \def\@bohr@electron@current@number{\csuse{@bohr@atom@number@#3}}%
79           }{%
80             \@bohr@error{You must specify an electron number, possibly 0.}%
81             {You must specify an electron number, possibly 0.}%
82           }%
83         }%
84       }%
85     }%
86   }{%
87     \ifnum{\#2}<0\relax
88       \@bohr@error{The electron number cannot be negative!}%
89       {The electron number cannot be negative!}%
90   }%
91 }

```

```

90 \else
91   \ifnum#2>112\relax
92     @bohr@warning{I only know atoms up to 112 (Copernicium). You
93       gave me #1 so I am using 112 instead.}
94     \def\@bohr@electron@current@number{112}%
95   \else
96     \def\@bohr@electron@current@number{#2}%
97   \fi
98   \fi
99 }%
100 \ifblank{#1}
101 { \@bohr@get@shell@num{\@bohr@electron@current@number} }
102 {
103   \@bohr@get@shell@num{\@bohr@electron@current@number}%
104   \ifnum#1<\@bohr@shell@num
105     \@bohr@warning{The shell number you provided (#1) is too small for the
106       electron number you provided (\@bohr@electron@current@number)! I'll
107       use \@bohr@shell@num\space shells.}%
108   \else
109     \ifnum#1>7\relax
110       \@bohr@warning{I know only of 7 electron shells. You gave me #1 so I'll
111         be using 7 instead.}
112       \def\@bohr@shell@num{7}%
113     \else
114       \def\@bohr@shell@num{#1}%
115     \fi
116     \fi
117 }%
118 \tikzpicture[baseline=(nucleus.base)]
119 \expandafter\node\expandafter[\@bohr@name@options]
120   (nucleus) at (0,0) {\@bohr@insert@symbol{\@bohr@electron@current@number}{#3}}%
121 ;
122 \expandafter\draw\expandafter[\@bohr@nucleus@options]
123   (nucleus) circle (\@bohr@nucleus@radius) ;
124 \foreach\@bohr@current@shell@num in {1,...,\@bohr@shell@num}
125 {
126   \expandafter\draw\expandafter[\@bohr@shell@options]
127     (nucleus) circle (\@bohr@nucleus@radius+\@bohr@current@shell@num*\@bohr@shell@dist) ;
128 }
129 \@bohr@draw@electrons{\@bohr@electron@current@number}
130 \endtikzpicture
131 }
132 \def\@bohr@get@shell@num#1{%
133   \ifnum#1<3\relax
134     \def\@bohr@shell@num{1}%
135   \else
136     \ifnum#1<11\relax

```

```

137   \def\@bohr@shell@num{2}%
138 \else
139   \ifnum#1<19\relax
140     \def\@bohr@shell@num{3}%
141 \else
142   \ifnum#1<37\relax
143     \def\@bohr@shell@num{4}%
144 \else
145   \ifnum#1<55\relax
146     \def\@bohr@shell@num{5}%
147 \else
148   \ifnum#1<87\relax
149     \def\@bohr@shell@num{6}%
150 \else
151   \def\@bohr@shell@num{7}%
152 \fi
153 \fi
154 \fi
155 \fi
156 \fi
157 \fi
158 }

159 \def\@bohr@distribute@electrons#1#2#3#4{%
160   \pgfmathparse{#2}%
161   \let\@bohr@last@electron\pgfmathresult
162   \foreach\@bohr@electron@number in {\#1,...,\@bohr@last@electron}
163   {
164     \expandafter\fill\expandafter[\@bohr@electron@options] (nucleus)
165       ++(#3*\@bohr@electron@number-#3:\@bohr@nucleus@radius+#4*\@bohr@shell@dist)
166       circle (\@bohr@electron@radius) ;
167   }
168 }

169 }

170 \def\@bohr@draw@electrons#1{%
171   \ifnum#1<1\relax\else
172     \ifnum#1<3\relax
173       \@bohr@distribute@electrons{1}{#1}{180}{1}%
174     \else
175       \ifnum#1<11\relax
176         \@bohr@distribute@electrons{1}{2}{180}{1}%
177         \@bohr@distribute@electrons{1}{#1-2}{45}{2}%
178       \else
179         \ifnum#1<19\relax
180           \@bohr@distribute@electrons{1}{2}{180}{1}%
181           \@bohr@distribute@electrons{1}{8}{45}{2}%
182           \@bohr@distribute@electrons{1}{#1-10}{45}{3}%
183         \else
184           \ifnum#1<37\relax

```

```

186      \@bohr@distribute@electrons{1}{2}{180}{1}%
187      \@bohr@distribute@electrons{1}{8}{45}{2}%
188      \@bohr@distribute@electrons{1}{8}{45}{3}%
189      \@bohr@distribute@electrons{1}{#1-18}{20}{4}%
190 \else
191     \ifnum#1<55\relax
192       \@bohr@distribute@electrons{1}{2}{180}{1}%
193       \@bohr@distribute@electrons{1}{8}{45}{2}%
194       \@bohr@distribute@electrons{1}{8}{45}{3}%
195       \@bohr@distribute@electrons{1}{18}{20}{4}%
196       \@bohr@distribute@electrons{1}{#1-36}{20}{5}%
197 \else
198     \ifnum#1<87\relax
199       \@bohr@distribute@electrons{1}{2}{180}{1}%
200       \@bohr@distribute@electrons{1}{8}{45}{2}%
201       \@bohr@distribute@electrons{1}{8}{45}{3}%
202       \@bohr@distribute@electrons{1}{18}{20}{4}%
203       \@bohr@distribute@electrons{1}{18}{20}{5}%
204       \@bohr@distribute@electrons{1}{#1-54}{11.25}{6}%
205 \else
206       \@bohr@distribute@electrons{1}{2}{180}{1}%
207       \@bohr@distribute@electrons{1}{8}{45}{2}%
208       \@bohr@distribute@electrons{1}{8}{45}{3}%
209       \@bohr@distribute@electrons{1}{18}{20}{4}%
210       \@bohr@distribute@electrons{1}{18}{20}{5}%
211       \@bohr@distribute@electrons{1}{32}{11.25}{6}%
212     \ifnum#1<113\relax
213       \@bohr@distribute@electrons{1}{#1-86}{11.25}{7}%
214     \else
215       \@bohr@distribute@electrons{1}{26}{11.25}{7}%
216       \@bohr@warning{I only know atoms up to 112 (Copernicium). You
217                     gave me #1 so I am using 112 instead.}
218     \fi
219   \fi
220   \fi
221   \fi
222   \fi
223   \fi
224   \fi
225   \fi
226 }
227 %
228 % -----
229 % atomic numbers and element symbols and names
230 \def\@bohr@define@atom@symbol#1#2{%
231   \csdef{@bohr@atom@symbol@num@\romannumeral#1}{#2}%
232   \lowercase{\csdef{@bohr@atom@number@#2}{#1}}%
233 \def\@bohr@define@atom@name#1#2#3{%
234   \csdef{@bohr@atom@name@\romannumeral#1}{#2}%

```

```

235      \lowercase{\csdef{@bohr@atom@name@num@#3}}{#1}}
236
237      % #1: optional name (umlauts...)
238      % #2: atomic number
239      % #3: element name
240      \newrobustcmd*\DeclareAtomName[3][]{%
241          \ifblank{#1}{%
242              {\@bohr@define@atom@name{#2}{#3}{#3}}{%
243                  {\@bohr@define@atom@name{#2}{#3}{#1}}}}{%
244              % #1: atomic number
245              % #2: element symbol
246              \newrobustcmd*\DeclareAtomSymbol[2]{%
247                  {\@bohr@define@atom@symbol{#1}{#2}}}}{%
248
249          \def\@bohr@get@atom@symbol#1{%
250              \csuse{@bohr@atom@symbol@num@\romannumeral#1}}}{%
251          \def\@bohr@get@atom@number#1{%
252              \lowercase{\csuse{@bohr@atom@number@#1}}}}{%
253          \def\@bohr@get@atom@name#1{%
254              \csuse{@bohr@atom@name@\romannumeral#1}}}{%
255
256          \def\@bohr@element@symbol#1{%
257              \lowercase{\ifcsdef{@bohr@atom@name@num@#1}}{%
258                  {\lowercase{\@bohr@get@atom@symbol{\csuse{@bohr@atom@name@num@#1}}}}{%
259                      {\@bohr@get@atom@symbol{#1}}}}}{%
260
261          \def\@bohr@atomic@number#1{%
262              \lowercase{\ifcsdef{@bohr@atom@number@#1}}{%
263                  {\@bohr@get@atom@number{#1}}}{%
264                      {\lowercase{\csuse{@bohr@atom@name@num@#1}}}}}{%
265
266          \def\@bohr@elemt@symbol#1{%
267              \if!\ifnum9<1#1!\@bohr@get@atom@name{#1}\fi{%
268                  \else{%
269                      \lowercase{\@bohr@get@atom@name{\csuse{@bohr@atom@number@#1}}}}{%
270                          \fi}}}{%
271
272          \newrobustcmd*\elementsymbol[1]{\@bohr@element@symbol{#1}}}{%
273          \newrobustcmd*\atomicnumber[1]{\@bohr@atomic@number{#1}}}{%
274          \newrobustcmd*\elementname[1]{\@bohr@elemt@symbol{#1}}}{%
275          \ifdef{\Z}{\let{\Z}{\atomicnumber}}}{%
276
277          \DeclareAtomSymbol{1}{H}}{%
278          \DeclareAtomSymbol{2}{He}}{%
279          \DeclareAtomSymbol{3}{Li}}{%
280          \DeclareAtomSymbol{4}{Be}}{%
281          \DeclareAtomSymbol{5}{B}}{%
282          \DeclareAtomSymbol{6}{C}}{%
283          \DeclareAtomSymbol{7}{N}}}
```

```

284 \DeclareAtomSymbol{8}{O}
285 \DeclareAtomSymbol{9}{F}
286 \DeclareAtomSymbol{10}{Ne}
287 \DeclareAtomSymbol{11}{Na}
288 \DeclareAtomSymbol{12}{Mg}
289 \DeclareAtomSymbol{13}{Al}
290 \DeclareAtomSymbol{14}{Si}
291 \DeclareAtomSymbol{15}{P}
292 \DeclareAtomSymbol{16}{S}
293 \DeclareAtomSymbol{17}{Cl}
294 \DeclareAtomSymbol{18}{Ar}
295 \DeclareAtomSymbol{19}{K}
296 \DeclareAtomSymbol{20}{Ca}
297 \DeclareAtomSymbol{21}{Sc}
298 \DeclareAtomSymbol{22}{Ti}
299 \DeclareAtomSymbol{23}{V}
300 \DeclareAtomSymbol{24}{Cr}
301 \DeclareAtomSymbol{25}{Mn}
302 \DeclareAtomSymbol{26}{Fe}
303 \DeclareAtomSymbol{27}{Co}
304 \DeclareAtomSymbol{28}{Ni}
305 \DeclareAtomSymbol{29}{Cu}
306 \DeclareAtomSymbol{30}{Zn}
307 \DeclareAtomSymbol{31}{Ga}
308 \DeclareAtomSymbol{32}{Ge}
309 \DeclareAtomSymbol{33}{As}
310 \DeclareAtomSymbol{34}{Se}
311 \DeclareAtomSymbol{35}{Br}
312 \DeclareAtomSymbol{36}{Kr}
313 \DeclareAtomSymbol{37}{Rb}
314 \DeclareAtomSymbol{38}{Sr}
315 \DeclareAtomSymbol{39}{Y}
316 \DeclareAtomSymbol{40}{Zr}
317 \DeclareAtomSymbol{41}{Nb}
318 \DeclareAtomSymbol{42}{Mo}
319 \DeclareAtomSymbol{43}{Tc}
320 \DeclareAtomSymbol{44}{Ru}
321 \DeclareAtomSymbol{45}{Rh}
322 \DeclareAtomSymbol{46}{Pd}
323 \DeclareAtomSymbol{47}{Ag}
324 \DeclareAtomSymbol{48}{Cd}
325 \DeclareAtomSymbol{49}{In}
326 \DeclareAtomSymbol{50}{Sn}
327 \DeclareAtomSymbol{51}{Sb}
328 \DeclareAtomSymbol{52}{Te}
329 \DeclareAtomSymbol{53}{I}
330 \DeclareAtomSymbol{54}{Xe}
331 \DeclareAtomSymbol{55}{Cs}
332 \DeclareAtomSymbol{56}{Ba}

```

```

333 \DeclareAtomSymbol{57}{La}
334 \DeclareAtomSymbol{58}{Ce}
335 \DeclareAtomSymbol{59}{Pr}
336 \DeclareAtomSymbol{60}{Nd}
337 \DeclareAtomSymbol{61}{Pm}
338 \DeclareAtomSymbol{62}{Sm}
339 \DeclareAtomSymbol{63}{Eu}
340 \DeclareAtomSymbol{64}{Gd}
341 \DeclareAtomSymbol{65}{Tb}
342 \DeclareAtomSymbol{66}{Dy}
343 \DeclareAtomSymbol{67}{Ho}
344 \DeclareAtomSymbol{68}{Er}
345 \DeclareAtomSymbol{69}{Tm}
346 \DeclareAtomSymbol{70}{Yb}
347 \DeclareAtomSymbol{71}{Lu}
348 \DeclareAtomSymbol{72}{Hf}
349 \DeclareAtomSymbol{73}{Ta}
350 \DeclareAtomSymbol{74}{W}
351 \DeclareAtomSymbol{75}{Rh}
352 \DeclareAtomSymbol{76}{Os}
353 \DeclareAtomSymbol{77}{Ir}
354 \DeclareAtomSymbol{78}{Pt}
355 \DeclareAtomSymbol{79}{Au}
356 \DeclareAtomSymbol{80}{Hg}
357 \DeclareAtomSymbol{81}{Tl}
358 \DeclareAtomSymbol{82}{Pb}
359 \DeclareAtomSymbol{83}{Bi}
360 \DeclareAtomSymbol{84}{Po}
361 \DeclareAtomSymbol{85}{At}
362 \DeclareAtomSymbol{86}{Rn}
363 \DeclareAtomSymbol{87}{Fr}
364 \DeclareAtomSymbol{88}{Ra}
365 \DeclareAtomSymbol{89}{Ac}
366 \DeclareAtomSymbol{90}{Th}
367 \DeclareAtomSymbol{91}{Pa}
368 \DeclareAtomSymbol{92}{U}
369 \DeclareAtomSymbol{93}{Np}
370 \DeclareAtomSymbol{94}{Pu}
371 \DeclareAtomSymbol{95}{Am}
372 \DeclareAtomSymbol{96}{Cm}
373 \DeclareAtomSymbol{97}{Bk}
374 \DeclareAtomSymbol{98}{Cf}
375 \DeclareAtomSymbol{99}{Es}
376 \DeclareAtomSymbol{100}{Fm}
377 \DeclareAtomSymbol{101}{Md}
378 \DeclareAtomSymbol{102}{No}
379 \DeclareAtomSymbol{103}{Lr}
380 \DeclareAtomSymbol{104}{Rf}
381 \DeclareAtomSymbol{105}{Db}

```

```

382 \DeclareAtomSymbol{106}{Sg}
383 \DeclareAtomSymbol{107}{Bh}
384 \DeclareAtomSymbol{108}{Hs}
385 \DeclareAtomSymbol{109}{Mt}
386 \DeclareAtomSymbol{110}{Ds}
387 \DeclareAtomSymbol{111}{Rg}
388 \DeclareAtomSymbol{112}{Cn}

389 % element names are defined in bohr_elements_english.def or
390 % bohr_elements_german.def, respectively. Now we need to decide
391 % which ones we want
392 \AfterEndPreamble{
393 \ifdef\bb@afterfi{}{\long\def\bb@afterfi#1{\fi#1}}
394 \ifboolexpr
395 {
396     test {\iflanguage{german}} or
397     test {\iflanguage{ngerman}}
398 }
399 {\booltrue{bohr@german}{}}
400 \ifbool{bohr@german}
401   {\input{bohr_elements_german.def}}
402   {\input{bohr_elements_english.def}}
403 }

404 }

405

406

407 % -----
408 % options
409 \def\@bohr@name@options{}
410 \def\@bohr@write@atom#1{#1}
411 \def\@bohr@nucleus@radius{1em}
412 \def\@bohr@electron@options{blue!50!black!50}
413 \def\@bohr@electron@radius{1.5pt}
414 \def\@bohr@shell@dist{1em}
415 \def\@bohr@nucleus@options{draw=black!80,fill=black!10,opacity=.25}
416 \def\@bohr@shell@options{draw=blue!75,thin}

417 \newbool{bohr@insert@symbol}
418 \newbool{bohr@insert@number}
419 \newbool{bohr@german}

420

421 \def\@bohr@insert@symbol#1#2{%
422     \ifbool{bohr@insert@symbol}
423       {\ifblank{#2}{\@bohr@get@atom@symbol{#1}}{\@bohr@write@atom{#2}}}
424       {\@bohr@write@atom{#2}}}

425

426 \pgfkeys{
427   bohr/.cd,
428     insert-symbol/.is if      = bohr@insert@symbol ,
429     insert-number/.is if      = bohr@insert@number ,

```

```

431     insert-missing/.is choice,
432     insert-missing/true/.code =
433         \booltrue{bohr@insert@symbol}\booltrue{bohr@insert@number} ,
434     insert-missing/false/.code =
435         \boolfalse{bohr@insert@symbol}\boolfalse{bohr@insert@number} ,
436     insert-missing/.default    = true ,
437     atom-style/.code          = \def\@bohr@write@atom{\#1} ,
438     name-options-set/.code    = \def\@bohr@name@options{\#1} ,
439     name-options-add/.code    =
440         \expandafter\def\expandafter\@bohr@name@options\expandafter{\\
441             @bohr@name@options,\#1} ,
442             nucleus-radius/.code      = \def\@bohr@nucleus@radius{\#1} ,
443             nucleus-options-set/.code = \def\@bohr@nucleus@options{\#1} ,
444             nucleus-options-add/.code =
445                 \expandafter\def\expandafter\@bohr@nucleus@options\expandafter{\\
446                     @bohr@nucleus@options,\#1} ,
447                     electron-radius/.code    = \def\@bohr@electron@radius{\#1} ,
448                     electron-options-set/.code = \def\@bohr@electron@options{\#1} ,
449                     electron-options-add/.code =
450                         \expandafter\def\expandafter\@bohr@electron@options\expandafter{\\
451                             @bohr@electron@options,\#1} ,
452                             shell-dist/.code          = \def\@bohr@shell@dist{\#1} ,
453                             shell-options-set/.code    = \def\@bohr@shell@options{\#1} ,
454                             shell-options-add/.code    =
455                                 \expandafter\def\expandafter\@bohr@shell@options\expandafter{\\
456                                     @bohr@shell@options,\#1} ,
457                                     german/.is if           = bohr@german ,
458                                     ngerman/.is if           = bohr@german
459     }
460
461
462 % HISTORY
463 2012/09/21 v0.1a - first version on bitbucket
464 2012/09/22 v0.2 - added compatibility up to atomic number 112
465         - added the commands \elementname and \elementsymbol with
466             language support German and English
467         - improved error checking
468 2012/12/30 v0.2c - bug fixes in error checking

```

Index

A	
<code>atom-style</code>	3
<code>\atomicnumber</code>	4
B	
<code>babel</code>	3
<code>\bohr</code>	2 f.
C	
Customization	2 ff.
E	
<code>electron-options-add</code>	3
<code>electron-options-set</code>	3
<code>electron-radius</code>	3
<code>\elementname</code>	4
<code>\elementsymbol</code>	4
<code>etoolbox</code>	1
G	
<code>german</code>	3
I	
<code>insert-missing</code>	3
<code>insert-number</code>	2 f.
<code>insert-symbol</code>	2 f.
L	
License	1
N	
<code>name-options-add</code>	3
<code>name-options-set</code>	3
<code>nucleus-options-add</code>	3
<code>nucleus-options-set</code>	3
<code>nucleus-radius</code>	3
O	
<code>option</code>	1
Options	1 f.
P	
<code>pgfplots</code>	1
<code>polyglossia</code>	3
S	
<code>\setbohr</code>	2
<code>shell-dist</code>	3
<code>shell-options-add</code>	3
<code>shell-options-set</code>	3
T	
<code>tikz</code>	1
U	
Usage	2
Z	
<code>\Z</code>	4